Component Count:		62
Ref	Quantity	Value
BT1,		1 BU2032SM-HD-G
C1,		1 220u
C3, C24,		2 1u
C5,		1 100u
C6,		1 4u7
C7, C8, C9, C4, C19, C2, C16, C22, C11,		9 100n
C10,		1 100u
C14,		1 4.7u
C15,		1 22u
C17,		1 10u
C18, C26, C27, C28, C29, C12,		6 33p
C21, C20, C13,		3 10p
C30, C31, C25, C23,		4 20p
D1,		1 D_Schottky
D2,		1 RCLAMP0854P.TCT
FB1,		1 100R
J1, '		1 Battery
J2,		1 PIEZOMETER
J3,		1 SWD
J4,		1 BOOT
J5,		1 Antenna 73251-2201
J6,		1 Sim Card 78646-3001
L1,		1 27n
L2,		1 22uH
Q1,		1 DTC114E
R1,		1 5.6k
R2,		1 1k
R3,		1 1K
R4,		10E
R6, R5,		2 100K
R7,		1 10k
R8, R9, R11,		3 22R
R10,		1 1M
SW1,		1 RESET
U1,		1 TPS76933
U2,		1 MT3608
U3,		1 M66 R2.0
U4,		1 STM32F103C8T6
Y1,		18MHz
Y2,		1 32.768KHz

Component name

Coin-cell holder

Polar-Capacitor

Ceramic-Capacitor

Polar-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Polar-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Ceramic-Capacitor

Schottky disode 3A

TVS Diode

Ferrite Bead Small

Screw_Terminal_01x02

Conn_01x05_Male

Conn_01x04_Male

Conn_02x03_Odd_Even

73251-2201

78646-3001

Inductor

Inductor

DTC114E

D 1 C 1 1 4 1

Resistor

Resistor

Resistor

Resistor

Resistor

Resistor

Resistor

Resistor Push-Button

TPS76933-Regulator_Linear

MT3608

M66FB-03-STD

STM32F103C8Tx

Crystal-SMD

Crystal_SMD

```
BAT BU2032SM-HD-G
Capacitor THT:CP Radial D8.0mm P2.50mm
Capacitor_SMD:C_0603_1608Metric_Pad1.08x0.95mm_HandSolder
Capacitor THT:CP Radial D7.5mm P2.50mm
Capacitor SMD:C 0603 1608Metric Pad1.08x0.95mm HandSolder
Capacitor_SMD:C_0603_1608Metric_Pad1.08x0.95mm_HandSolder
Capacitor Tantalum SMD:CP EIA-3528-21 Kemet-B Pad1.50x2.35mm HandSolder
Capacitor SMD:C 0603 1608Metric Pad1.08x0.95mm HandSolder
Capacitor SMD:C 0805 2012Metric Pad1.18x1.45mm HandSolder
Capacitor SMD:C 0805 2012Metric Pad1.18x1.45mm HandSolder
Capacitor SMD:C 0603 1608Metric Pad1.08x0.95mm HandSolder
Capacitor SMD:C 0603 1608Metric Pad1.08x0.95mm HandSolder
Capacitor SMD:C 0603 1608Metric Pad1.08x0.95mm HandSolder
Diode THT:D DO-201AD P15.24mm Horizontal
SON50P160X160X65-7N
Inductor SMD:L 0603 1608Metric Pad1.05x0.95mm HandSolder
TerminalBlock Phoenix:TerminalBlock Phoenix MKDS-1,5-2-5.08 1x02 P5.08mm Horizontal
TerminalBlock Phoenix:TerminalBlock Phoenix MKDS-1,5-4-5.08 1x04 P5.08mm Horizontal
Connector_PinHeader_2.54mm:PinHeader_1x04_P2.54mm_Vertical
Connector PinHeader 2.54mm:PinHeader 2x03 P2.54mm Vertical
73251-2200
78646-3001
Inductor SMD:L 0603 1608Metric Pad1.05x0.95mm HandSolder
Inductor_SMD:L_12x12mm_H6mm
Package_TO_SOT_SMD:SOT-23
Resistor SMD:R 0603 1608Metric Pad0.98x0.95mm HandSolder
Button Switch THT:SW PUSH 6mm H4.3mm
Package TO SOT SMD:TSOT-23-5_HandSoldering
SOT95P280X145-6N
XCVR_M66FB-03-STD
Package_QFP:LQFP-48_7x7mm_P0.5mm
Crystal: Crystal SMD HC49-SD HandSoldering
Crystal:Crystal_SMD_Abracon_ABS25-4Pin_8.0x3.8mm
```

Footprint

Description

Polarized capacitor, small symbol Unpolarized capacitor, small symbol

Polarized capacitor, small symbol

Unpolarized capacitor

Unpolarized capacitor

Polarized capacitor

Unpolarized capacitor, small symbol

Unpolarized capacitor

Unpolarized capacitor

Unpolarized capacitor

Unpolarized capacitor

Unpolarized capacitor, small symbol

Schottky diode

ESD Suppressors / TVS Diodes RCLAMP0854P 4LINES 8V SLP

Ferrite bead, small symbol

Generic screw terminal, single row, 01x02, script generated (kicad-library-utils/schlib/autogen/connector/)

Generic connector, single row, 01x05, script generated (kicad-library-utils/schlib/autogen/connector/)

Generic connector, single row, 01x04, script generated (kicad-library-utils/schlib/autogen/connector/)

Generic connector, double row, 02x03, odd/even pin numbering scheme (row 1 odd numbers, row 2 even numbers), script ge SMA Jack PCB gold plated 50 Ohms 90deg Molex Right Angle 50 Through Hole SMA Connector, jack, Solder Termination CONNECTOR, MICRO SIM, 6POS; Product Range:78646 Series; Connector Type:Micro SIM; No. of Contacts:6Contacts; Contacts; Contacts:6Contacts; Contacts; Contacts; Contacts; Contacts;

Inductor

Inductor

Digital NPN Transistor, 10k/10k, SOT-23

Resistor, small symbol

Resistor, small symbol Resistor, small symbol

Resistor, small symbol

Push button switch, generic, two pins

ARM Cortex-M3 MCU, 64KB flash, 20KB RAM, 72MHz, 2-3.6V, 37 GPIO, LQFP-48

Two pin crystal

Four pin crystal, GND on pins 2 and 3

Vendor