

INTRODUCTION TO FIRESTORE



What is our GOAL for this MODULE?

In this class we designed the collections and documents in the firestore database for the e-library app and programmed the submit button so that a book is issued or returned to a student as a library transaction.

What did we ACHIEVE in the class TODAY?

- Design e-library app database in firestore.
- Write code to issue/return a book by updating the database.

Which CONCEPTS/CODING BLOCKS did we cover today?

- Usage of firestore database
- Connecting firestore database to our app

How did we DO the activities?

1. Create a submit button and style it.

```

<View style={[styles.textinputContainer, { marginTop: 25 }]}>
  <TextInput
    style={styles.textinput}
    placeholder={"Student Id"}
    placeholderTextColor={"#FFFFFF"}
    value={studentId}
  />
  <TouchableOpacity
    style={styles.scanbutton}
    onPress={() => this.getCameraPermissions("studentId")}
  >
    <Text style={styles.scanbuttonText}>Scan</Text>
  </TouchableOpacity>
</View>
<TouchableOpacity
  style={[styles.button, { marginTop: 25 }]}
  >
    <Text style={styles.buttonText}>Submit</Text>
  </TouchableOpacity>
</View>
</ImageBackground>
</View>
);

```

```

scanbutton: {
  width: 100,
  height: 50,
  backgroundColor: "#9DFD24",
  borderTopRightRadius: 10,
  borderBottomRightRadius: 10,
  justifyContent: "center",
  alignItems: "center"
},
scanbuttonText: {
  fontSize: 24,
  color: "#0A0101",
  fontFamily: "Rajdhani_600SemiBold"
},
button: {

```

```
width: "43%",  
height: 55,  
justifyContent: "center",  
alignItems: "center",  
backgroundColor: "#F48D20",  
borderRadius: 15  
},  
buttonText: {  
  fontSize: 24,  
  color: "#FFFFFF",  
  fontFamily: "Rajdhani_600SemiBold"  
}  
});
```

Whitehatjr+Whitehatjr+Whitehatjr

2. Create a handle transaction function and call **this.handleTransaction** in the **onPress** prop for Submit Button.

```

    if (domState === "bookId") {
      this.setState({
        bookId: data,
        domState: "normal",
        scanned: true
      });
    } else if (domState === "studentId") {
      this.setState({
        studentId: data,
        domState: "normal",
        scanned: true
      });
    }
  };

  handleTransaction = () => {

  };

  render() {
    const { bookId, studentId, domState, scanned } = this.state;
    if (domState !== "normal") {
      return (
        <BarcodeScanner
          onBarcodeScanned={scanned ? undefined : this.handleBarcodeScanned}
          style={StyleSheet.absoluteFillObject}
        />
      );
    }
    return (
      <View style={styles.container}>
        <ImageBackground source={bgImage} style={styles.bgImage}>
          <View style={styles.upperContainer}>
            <Image source={appIcon} style={styles.appIcon} />
            <Image source={appName} style={styles.appName} />
          </View>
          <View style={styles.lowerContainer}>

```


```

      <TouchableOpacity
        style={[styles.button, { marginTop: 25 }]}
        onPress={this.handleTransaction}
      >
        <Text style={styles.buttonText}>Submit</Text>
      </TouchableOpacity>


```

3. Create a Firestore Database and learn how to use firestore in test mode.


- Click on add project.




- Add a name to the app.




- Disable google analytics.



- Click on continue.



- Click the code icon.




- Copy the credentials.

```
<!-- The core Firebase JS SDK is always required and must be listed first -->
<script src="https://www.gstatic.com/firebasejs/8.6.8/firebase-app.js"></script>

<!-- TODO: Add SDKs for Firebase products that you want to use
https://firebase.google.com/docs/web/setup#available-libraries -->

<script>
  // Your web app's Firebase configuration
  var firebaseConfig = {
    apiKey: "AIzaSyB3dzLbgE8DPcHufZzeVKYwgmpXD0HFZYs",
    authDomain: "e-library-5fd21.firebaseio.com",
    projectId: "e-library-5fd21",
    storageBucket: "e-library-5fd21.appspot.com",
    messagingSenderId: "665049297120",
    appId: "1:665049297120:web:7442fb17f050bde800e085"
  };
  // Initialize Firebase
  firebase.initializeApp(firebaseConfig);
</script>
```

- Click on database inside the panel.



- Add Firebase database to the app.

×

Add Firebase to your web app

1

Register app

App nickname ⓘ

e-library

☐ Also set up **Firebase Hosting** for this app. [Learn more](#) ⓘ


Hosting can also be set up later. It's free to get started anytime.

Register app


2

Add Firebase SDK


- Create a database.




- Start database in Test mode.




4. Firestore Database organizes all data in terms of collections and documents. Collection is the name given to a group of documents holding some common properties. Documents are data stored inside collections as separate entities.







5. Create a collection in Firestore. Each document inside the collection will contain information about one book in the library. We will have as many documents as there are books in the library.



6. Create a Students Collection with a sample student document containing the fields - **studentId**, **studentDetails**, **numberOfBooksIssued**.



7. e-library app will be used to issue or return books. Each issue or return is a transaction. Create a collection called transactions.
- It will contain the bookId, the student id, the date of transaction and the type of transaction (issue/return).



8. Let's create a **config.js** file in our app project where we initialize our firestore database and export **firebase.firestore()**.

```
JS config.js > ...
1  import firebase from "firebase";
2  require("@firebase/firestore");
3
4  const firebaseConfig = {
5    apiKey: "AIzaSyAkp3gQdHbMPD5pCfHbBzIIgFpdCJXD5KM",
6    authDomain: "e-library-v2.firebaseio.com",
7    projectId: "e-library-v2",
8    storageBucket: "e-library-v2.appspot.com",
9    messagingSenderId: "772559744213",
10   appId: "1:772559744213:web:9417b879882f231175065c",
11   measurementId: "G-H8Y352W6Z2"
12 };
13
14 firebase.initializeApp(firebaseConfig);
15
16 export default firebase.firestore();
17
```

```
C:\Users\ADMIN>npm install firebase
[.....] - rollbackFailedOptional: verb npm-session 734bf667a2aeba65
```

9. Import **firebase.firestore()** as db. There are a number of functions pre-defined on db which we are going to use to update or create documents in our database.

```
import React, { Component } from "react";
import {
  View,
  StyleSheet,
  TextInput,
  TouchableOpacity,
  Text,
  ImageBackground,
  Image
} from "react-native";
import * as Permissions from "expo-permissions";
import { BarCodeScanner } from "expo-barcode-scanner";
import db from "../config";

const bgImage = require("../assets/background2.png");
const appIcon = require("../assets/appIcon.png");
const appName = require("../assets/appName.png");

export default class TransactionScreen extends Component {
  constructor(props) {
    super(props);
    this.state = {
      bookId: "",
      studentId: "",
      domState: "normal",
      hasCameraPermissions: null,
      scanned: false
    };
  }
}
```

10. Create two QR codes corresponding to the studentId and bookId we created in our database so that we can test the code we are going to write.

```
Transaction.js X
screens > JS Transaction.js > TransactionScreen
46      this.setState({
49          bookId: data,
50          domState: "normal",
51          scanned: true
52      });
53  } else if (domState === "studentId") {
54      this.setState({
55          studentId: data,
56          domState: "normal",
57          scanned: true
58      });
59  }
60  };
61
62  handleTransaction = () => {
63      var { bookId } = this.state;
64      db.collection("books")
65        .doc(bookId)
66        .get()
67        .then(doc => {
68            console.log(doc.data())
69        });
70  };
71
72
73
74  render() {
75      const { bookId, studentId, domState, scanned } = this.state;
76      if (domState !== "normal") {
77          return (
78              <BarCodeScanner
79                  onBarCodeScanned={scanned ? undefined : this.handleBarCodeScanned}
80                  style={StyleSheet.absoluteFillObject}
81              />
82          );
83      }
84      return (
85          <View style={styles.container}>
86              <ImageBackground source={bgImage} style={styles.bgImage}>
87                  <View style={styles.upperContainer}>
```

```
Object {
  "book_details": Object {
    "book_author": "Abhijeet Holkar",
    "book_name": "Travel Magazine",
    "pages": 209,
    "price": 499,
  },
  "book_id": "BSC001",
  "is_book_available": false,
}
```


11. Write code to call **initiateBookIssue()** if the book is available or **initiateBookReturn()** when the book is not available.

```
screens > JS Transaction.js > TransactionScreen
53 } else if (domState === "studentId") {
54   this.setState({
55     studentId: data,
56     domState: "normal",
57     scanned: true
58   });
59 }
60 };
61
62 handleTransaction = () => {
63   var { bookId } = this.state;
64   db.collection("books")
65     .doc(bookId)
66     .get()
67     .then(doc => {
68       var book = doc.data();
69       if (book.is_book_available) {
70         this.initiateBookIssue();
71       } else {
72         this.initiateBookReturn();
73       }
74     });
75 };
76
77 |
78
79 render() {
80   const { bookId, studentId, domState, scanned } = this.state;
81   if (domState !== "normal") {
82     return (
83       <BarcodeScanner
84         onBarcodeScanned={scanned ? undefined : this.handleBarcodeScanned}
85         style={StyleSheet.absoluteFillObject}
86       />
87     );
88   }
89   return (
90     <View style={styles.container}>
91       <ImageBackground source={bgImage} style={styles.bgImage}>
92         <View style={styles.upperContainer}>
```


12. Get the bookAvailability field from the data. If the book is available, we want to issue the book. If the book is not available, we want to return the book. Use two abstract functions - initiateBookIssue() and initiateBookReturn() to write our code.

```
screens > JS Transaction.js > TransactionScreen
53   } else if (domState === "studentId") {
54     this.setState({
55       studentId: data,
56       domState: "normal",
57       scanned: true
58     });
59   }
60 };
61
62 handleTransaction = () => {
63   var { bookId } = this.state;
64   db.collection("books")
65     .doc(bookId)
66     .get()
67     .then(doc => {
68       var book = doc.data();
69       if (book.is_book_available) {
70         this.initiateBookIssue();
71       } else {
72         this.initiateBookReturn();
73       }
74     });
75 };
76
77 initiateBookIssue = () => {
78   console.log("Book issued to the student!");
79 };
80
81 initiateBookReturn = () => {
82   console.log("Book returned to the library!");
83 };
84
85 render() {
86   const { bookId, studentId, domState, scanned } = this.state;
87   if (domState !== "normal") {
88     return (
89       <BarcodeScanner
90         onBarcodeScanned={scanned ? undefined : this.handleBarcodeScanned}
91         style={StyleSheet.absoluteFillObject}
92       />

```



e-library

Book Id

Student Id

13. Create and style the submit button.

```
<View style={[styles.textinputContainer, { marginTop: 25 }]}>
  <TextInput
    style={styles.textinput}
    placeholder={"Student Id"}
    placeholderTextColor={"#FFFFFF"}
    value={studentId}
  />
  <TouchableOpacity
    style={styles.scanbutton}
    onPress={() => this.getCameraPermissions("studentId")}
  >
    <Text style={styles.scanbuttonText}>Scan</Text>
  </TouchableOpacity>
</View>

<TouchableOpacity
  style={[styles.button, { marginTop: 25 }]}
>
  <Text style={styles.buttonText}>Submit</Text>
</TouchableOpacity>

</View>
</ImageBackground>
</View>
);
}
}

const styles = StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: "#FFFFFF"
  },
  bgImage: {
    flex: 1,
    resizeMode: "cover",
    justifyContent: "center"
  },
});
```

screens > JS Transaction.js > TransactionScreen > render

```
187     borderRadius: 10,
188     borderWidth: 3,
189     fontSize: 18,
190     backgroundColor: "#5653D4",
191     fontFamily: "Rajdhani_600SemiBold",
192     color: "#FFFFFF"
193   },
194   scanbutton: {
195     width: 100,
196     height: 50,
197     backgroundColor: "#9DFD24",
198     borderTopRightRadius: 10,
199     borderBottomRightRadius: 10,
200     justifyContent: "center",
201     alignItems: "center"
202   },
203   scanbuttonText: {
204     fontSize: 24,
205     color: "#0A0101",
206     fontFamily: "Rajdhani_600SemiBold"
207   },
208   button: {
209     width: "43%",
210     height: 55,
211     justifyContent: "center",
212     alignItems: "center",
213     backgroundColor: "#F48D20",
214     borderRadius: 15
215   },
216   buttonText: {
217     fontSize: 24,
218     color: "#FFFFFF",
219     fontFamily: "Rajdhani_600SemiBold"
220   }
221 });
222
```

14. Create a firestore database with books, students and transaction collections and create a test book and student document.

```
C:\Users\ADMIN>npm install firebase  
[.....] - rollbackFailedOptional: verb npm-session 734bf667a2aeba65
```

```
JS config.js > ...  
1  import firebase from "firebase";  
2  require("@firebase/firestore");  
3  
4  const firebaseConfig = {  
5    apiKey: "AIzaSyAkp3gQdHbMPD5pCfHbBzIIgFpdCJXD5KM",  
6    authDomain: "e-library-v2.firebaseio.com",  
7    projectId: "e-library-v2",  
8    storageBucket: "e-library-v2.appspot.com",  
9    messagingSenderId: "772559744213",  
10   appId: "1:772559744213:web:9417b879882f231175065c",  
11   measurementId: "G-H8Y352W6Z2"  
12 };  
13  
14 firebase.initializeApp(firebaseConfig);  
15  
16 export default firebase.firestore();  
17
```

15. Create a function called **handleTransaction** which is called when the submit button is pressed.

```
screens > JS Transaction.js > TransactionScreen
53   } else if (domState === "studentId") {
54     this.setState({
55       studentId: data,
56       domState: "normal",
57       scanned: true
58     });
59   }
60 };
61
62 handleTransaction = () => {
63   var { bookId } = this.state;
64   db.collection("books")
65     .doc(bookId)
66     .get()
67     .then(doc => {
68       var book = doc.data();
69       if (book.is_book_available) {
70         this.initiateBookIssue();
71       } else {
72         this.initiateBookReturn();
73       }
74     });
75 };
76
77
78
79 render() {
80   const { bookId, studentId, domState, scanned } = this.state;
81   if (domState !== "normal") {
82     return (
83       <BarcodeScanner
84         onBarcodeScanned={scanned ? undefined : this.handleBarcodeScanned}
85         style={StyleSheet.absoluteFillObject}
86       />
87     );
88   }
89   return (
90     <View style={styles.container}>
91       <ImageBackground source={bgImage} style={styles.bgImage}>
92         <View style={styles.upperContainer}>
```

16. Get the book availability data from the scanned book id and call issue or return functions to complete the book transaction.

```
screens > JS Transaction.js > TransactionScreen
53     } else if (domState === "studentId") {
54         this.setState({
55             studentId: data,
56             domState: "normal",
57             scanned: true
58         });
59     }
60 };
61
62 handleTransaction = () => {
63     var { bookId } = this.state;
64     db.collection("books")
65         .doc(bookId)
66         .get()
67         .then(doc => {
68             var book = doc.data();
69             if (book.is_book_available) {
70                 this.initiateBookIssue();
71             } else {
72                 this.initiateBookReturn();
73             }
74         });
75 };
76
77 initiateBookIssue = () => {
78     console.log("Book issued to the student!");
79 };
80
81 initiateBookReturn = () => {
82     console.log("Book returned to the library!");
83 };
84
85 render() {
86     const { bookId, studentId, domState, scanned } = this.state;
87     if (domState !== "normal") {
88         return (
89             <BarcodeScanner
90                 onBarcodeScanned={scanned ? undefined : this.handleBarcodeScanned}
91                 style={StyleSheet.absoluteFillObject}
92             />
93         );
94     }
95 }
```

What's NEXT?

In the next class we will fix the issue of Keyboard Overlapping and show messages using Toasts.

EXTEND YOUR KNOWLEDGE

1. Cloud Firestore Documentation: <https://firebase.google.com/docs/firestore>

Whitehatjr+Whitehatjr+Whitehatjr