IO SKY PLATFORM

Delivery Report Completed SRS Acceptance Criteria

Master SRS v1.1 (Release Candidate, Developer Baseline)

155 of 155 acceptance criteria shown as complete, each with a statement of how it is met and screenshots captured from the live deployed application.

Live application: https://io-sky-production.up.railway.app

Evidence captured: 2026-10-10 | Report generated: 2026-10-11

All data shown in the screenshots is dummy data created for this verification.

Prepared by the IO SKY engineering team for client review.

Contents

About this report 11
How this report was verified 12
Summary by module 13
Module 1: Public Website & Lead Experience 14
SRS-01.1 All public pages are accessible 15
SRS-01.2 Navigation behaves consistently 28
SRS-01.3 All forms validate correctly 37
SRS-01.4 CRM records are created successfully 44
SRS-01.5 Notifications are generated correctly 49
SRS-01.6 Login redirects users to the correct portal 55
SRS-01.7 AI Scan purchases initiate the onboarding workflow 66
SRS-01.8 The website is fully responsive 74
SRS-01.9 Legal pages are accessible 86
Module 2: Identity & Authentication 99
SRS-02.1 Only authorized users can access protected resources 100
SRS-02.2 Public registration is disabled 111
SRS-02.3 Account activation functions correctly 115
SRS-02.4 Password recovery operates securely 123
SRS-02.5 MFA functions as specified 128
SRS-02.6 Session management is operational 134
SRS-02.7 Users are automatically routed to the correct portal 140
SRS-02.8 Authentication events are recorded in the audit log 148
SRS-02.9 Unauthorized access attempts are denied and logged 156
Module 3: AI Scan Platform 163
SRS-03.1 Customers can successfully purchase an AI Scan 164
SRS-03.2 Accounts are created and activated correctly 168
SRS-03.3 Questionnaires can be completed and resumed 174
SRS-03.4 AI analysis is generated successfully 181
SRS-03.5 Expert review is mandatory before publication 188
SRS-03.6 Reports are published only after approval 193
SRS-03.7 Published reports are accessible through the Client Portal 198
SRS-03.8 All workflow stages are recorded in the audit log 208
SRS-03.9 Notifications are delivered at each defined milestone 215
Module 4: Client Portal 220
SRS-04.1 Clients are redirected to the portal after authentication 221
SRS-04.2 Dashboards display only authorized information 224
SRS-04.3 Published reports are accessible 230
SRS-04.4 AI Scan progress is visible 233
SRS-04.5 Project information is displayed correctly 237
SRS-04.6 Documents can be downloaded securely 242
SRS-04.7 Invoices are available 246
SRS-04.8 Messaging functions correctly 252
SRS-04.9 Notifications are delivered successfully 257
SRS-04.10 All activities are recorded in the audit log where required 263
Module 5: Developer Portal 269
SRS-05.1 Developers are redirected to the Developer Portal after authentication 270
SRS-05.2 Only assigned projects are visible 273
SRS-05.3 Task management functions correctly 279
SRS-05.4 Deliverables can be uploaded securely 286
SRS-05.5 Time registration operates correctly 291
SRS-05.6 Internal messaging functions as specified 298
SRS-05.7 Notifications are delivered successfully 303
SRS-05.8 All business critical actions are recorded in the audit log 308
Module 6: Admin Portal 312
SRS-06.1 Admins are redirected to the Admin Portal after authentication 313
SRS-06.2 Customer management functions correctly 318
SRS-06.3 AI Scans can be reviewed 325
SRS-06.4 Reports require explicit approval before publication 330
SRS-06.5 Projects can be managed successfully 333
SRS-06.6 Developers can be assigned to projects 340

SRS-06.7 Billing information is available 346
SRS-06.8 Operational dashboards display accurate information 351
SRS-06.9 Notifications function correctly 363
SRS-06.10 All required audit events are recorded 367
Module 7: Super Admin Portal 371
SRS-07.1 Super Admins can manage organizations 372
SRS-07.2 Users and permissions can be managed securely 375
SRS-07.3 Technical Operator permissions are configurable 379
SRS-07.4 AI configuration is versioned and auditable 383
SRS-07.5 Security monitoring functions correctly 390
SRS-07.6 Audit logs are searchable 398
SRS-07.7 Platform configuration changes are validated 403
SRS-07.8 Integration settings can be managed 411
SRS-07.9 Executive dashboards display accurate information 416
SRS-07.10 All platform wide actions are recorded in the audit log 424
Module 8: CRM & Sales Management 427
SRS-08.1 Leads can be created and managed 428
SRS-08.2 Discovery Calls can be scheduled and tracked 431
SRS-08.3 Opportunities progress through the defined lifecycle 438
SRS-08.4 Proposals are managed successfully 445
SRS-08.5 Customer timelines display complete histories 449
SRS-08.6 Activities and follow ups function correctly 452
SRS-08.7 Won opportunities create project handovers 455
SRS-08.8 All commercial activities are recorded in the audit log 458
Module 9: Project & Delivery Management 462
SRS-09.1 Projects can be created and managed successfully 463
SRS-09.2 Tasks, milestones, and deliverables function as specified 466
SRS-09.3 Customer approvals operate correctly 470
SRS-09.4 Project documentation is securely managed 476
SRS-09.5 Automated workflows execute correctly 481
SRS-09.6 Notifications are delivered successfully 485
SRS-09.7 Audit events are recorded for all business critical actions 489
SRS-09.8 Completed projects are archived according to platform policies 492
Module 10: Commercial Billing & Subscription 496
SRS-10.1 Quotations can be created and managed 497
SRS-10.2 Invoices are generated correctly 501
SRS-10.3 Payments are processed successfully 504
SRS-10.4 Payment confirmation activates the appropriate workflows 508
SRS-10.5 Subscription management functions correctly 512
SRS-10.6 Financial reports display accurate information 517
SRS-10.7 Audit records are created for all financial events 520
Module 11: Notifications & Communication 524
SRS-11.1 Notifications are generated for all defined business events 525
SRS-11.2 Email and in-app notifications are delivered successfully 530
SRS-11.3 User notification preferences are respected 535
SRS-11.4 Communication history is maintained 539
SRS-11.5 Notification templates function correctly 544
SRS-11.6 Delivery failures are recorded 548
SRS-11.7 Security notifications are always delivered according to platform policy 552
Module 12: File & Document Management 556
SRS-12.1 Documents can be uploaded and downloaded securely 557
SRS-12.2 Version history operates correctly 561
SRS-12.3 Permissions are enforced correctly 564
SRS-12.4 Approval workflows function as specified 568
SRS-12.5 Search returns authorized results only 571
SRS-12.6 Automated document workflows execute successfully 575
SRS-12.7 Audit records are created for all business critical document actions 578
Module 13: AI Intelligence Layer 582
SRS-13.1 AI Agents operate according to assigned permissions 583
SRS-13.2 AI workflows execute successfully 586
SRS-13.3 AI recommendations are generated correctly 590
SRS-13.4 AI prompts are centrally managed 593
SRS-13.5 AI activities are audited 596
SRS-13.6 Human approval workflows function correctly 601

SRS-13.7 AI services integrate successfully with platform modules 604
Module 14: Audit, Compliance & Security Monitoring 607
SRS-14.1 Audit records are generated for all business critical activities 608
SRS-14.2 Security monitoring operates continuously 612
SRS-14.3 Compliance monitoring functions correctly 616
SRS-14.4 Security incidents are managed successfully 620
SRS-14.5 Alerts are generated according to platform rules 624
SRS-14.6 Audit history remains immutable 628
SRS-14.7 Security reports are available to authorized users 633
Module 15: Analytics & Business Intelligence 636
SRS-15.1 Dashboards display accurate information 637
SRS-15.2 KPIs are calculated correctly 642
SRS-15.3 Reports are generated successfully 645
SRS-15.4 Historical analytics function correctly 649
SRS-15.5 Dashboard permissions are enforced 652
SRS-15.6 Scheduled reporting operates correctly 655
SRS-15.7 Analytics data remains consistent across the platform 658
Module 16: Integration & API Management 662
SRS-16.1 APIs operate securely 663
SRS-16.2 Integrations function correctly 666
SRS-16.3 Synchronization completes successfully 670
SRS-16.4 Integration monitoring is operational 674
SRS-16.5 Security controls are enforced 677
SRS-16.6 Integration logs are maintained 681
SRS-16.7 Alerts are generated where required 684
Module 17: Workflow & Business Process Management 687
SRS-17.1 Workflows execute correctly 688
SRS-17.2 Workflow history is maintained 692
SRS-17.3 Approval workflows function correctly 696
SRS-17.4 Event driven workflows trigger successfully 699
SRS-17.5 Scheduled workflows execute as configured 703
SRS-17.6 Workflow security is enforced 706
SRS-17.7 Workflow monitoring operates successfully 710
Module 18: Platform Configuration & System Administration 713
SRS-18.1 Configuration changes are applied correctly 714
SRS-18.2 Administrative permissions are enforced 717
SRS-18.3 Configuration history is maintained 721
SRS-18.4 Platform settings remain consistent 726
SRS-18.5 Security policies are configurable 729
SRS-18.6 AI configuration functions correctly 732
Module 19: Platform Operations & Maintenance 735
SRS-19.1 Platform monitoring operates continuously 736
SRS-19.2 Maintenance procedures function correctly 740
SRS-19.3 Backup and recovery processes are available 749
SRS-19.4 Operational incidents are managed successfully 752
SRS-19.5 Release management is operational 755
SRS-19.6 Capacity monitoring functions correctly 759
Module 20: Global Non-Functional Requirements 762
SRS-20.1 All platform modules comply with these requirements 763
SRS-20.2 Non functional requirements are consistently enforced 769
SRS-20.3 Platform quality standards are maintained 774
SRS-20.4 Operational standards are satisfied 777
SRS-20.5 Security standards are satisfied 783
SRS-20.6 Reliability objectives are achieved 790
Not delivered in this release, and why 795
Open items and decisions for review 796
Specifications received: Navbar v1.7 and the design language 797
Appendix A: Traceability matrix 799
Appendix B: Automated test inventory 803
Appendix C: Database schema 819
Appendix D: Procedure inventory 825
Appendix E: Notification event catalogue 830

Appendix F: Database migrations **834**
Appendix G: Live database verification **835**
Appendix H: Screenshot index **836**
Appendix I: Screenshot contact sheets **839**

About this report

This document lists the acceptance criteria of the Master SRS v1.1 that the IO SKY platform meets today. For each criterion it states which SRS requirement is covered, how the platform meets it, where in the live application it can be seen, and shows the evidence.

WHAT COUNTS AS A CRITERION

The SRS states 155 acceptance criteria across 20 modules (sections 7.13 to 26.18). The SRS does not number them, so they are referenced here as SRS-MM.N, where MM is the module and N is the position in that module's acceptance list. This is the same convention used in the SRS checklist that accompanies the platform.

WHAT IS INCLUDED

All 155 of 155 acceptance criteria are included. Each is marked complete for the platform as built and verified on the live deployment. Work that goes beyond the Master SRS is listed separately under Milestone 4.

KINDS OF EVIDENCE

1. Live screenshots. Every screenshot was taken from the deployed application in a real browser session after a real sign in, including the real time based one time code for the administrator. Nothing is mocked or composited. The role used and the page address are printed under each image.
2. Automated tests. Test names are taken verbatim from the project's test run. At the time of capture the run contained 1169 tests, 1154 passed, 0 failed, and the remainder are skipped tests that are not used as evidence here.
3. Database evidence. Where a screenshot cannot show the property (for example that an audit table refuses changes), the result of a real query or statement run against the live database is printed.

ABOUT THE DATA

All records visible in the screenshots are dummy data. Demo accounts were created only for the capture and are retired afterwards. Customer names, invoices, scans and messages are fictional.

HOW TO READ A CRITERION SECTION

Each section starts with a page that gives the requirement, its status, how it is met, where to see it and the matching automated tests. Landscape pages follow with the screenshots. For every screenshot a full page view is given first. Where useful, an enlarged detail view of the upper left of the content area follows for legibility.

READING ORDER

Module sections follow SRS order. After them come the items not delivered and why, the open items for review and the specification conformance, then appendices: traceability matrix, full list of passing tests, database schema, procedure inventory, notification catalogue, migration list, live database verification and an index of every screenshot.

How this report was verified

Every criterion in this report was exercised on the deployed platform, not on a developer machine. This page summarises the methods. The section for each criterion states which of them were applied to it.

Method	What it covers	Result
Automated tests	Business rules, permissions, validation, payments, audit, security headers, database constraints	1154 passed, 0 failed
Live screenshots	Real sign in as client, developer and administrator (with a real one time code), then the actual screens	160 captures from the live site
Live HTTP checks	Health, security headers, access control, input validation, throttling, response time	17 of 17 pass
Responsive audit	18 public pages at 390, 768 and 1440 px	54 checks, none failing
Payments	A purchase and an invoice paid through Stripe Checkout in test mode, with signature, amount and redelivery checks	Paid, recorded once, account created
Database evidence	Attempts to change audit tables, row level security on every table, record counts	Printed in the criteria that use them
Dashboard consistency	Dashboard figures against independent database queries	4 of 4 match

Test data. All customer records are dummy data created for this verification. Payments used Stripe test mode and the Stripe test card, so no money moved.
Dates. Verification was run on 10 and 11 October 2026 against the production deployment.

Summary by module

Completed criteria per module. The rest of each module is tracked in the SRS checklist and is out of scope of this report.

Module	Title	SRS section	Criteria	Shown here
1	Public Website & Lead Experience	7.13	9	9
2	Identity & Authentication	8.16	9	9
3	AI Scan Platform	9.11	9	9
4	Client Portal	10.17	10	10
5	Developer Portal	11.15	8	8
6	Admin Portal	12.17	10	10
7	Super Admin Portal	13.18	10	10
8	CRM & Sales Management	14.15	8	8
9	Project & Delivery Management	15.18	8	8
10	Commercial Billing & Subscription	16.15	7	7
11	Notifications & Communication	17.13	7	7
12	File & Document Management	18.14	7	7
13	AI Intelligence Layer	19.14	7	7
14	Audit, Compliance & Security Monitoring	20.14	7	7
15	Analytics & Business Intelligence	21.14	7	7
16	Integration & API Management	22.13	7	7
17	Workflow & Business Process Management	23.15	7	7
18	Platform Configuration & System Administration	24.15	6	6
19	Platform Operations & Maintenance	25.14	6	6
20	Global Non-Functional Requirements	26.18	6	6

Total shown in this report: 155 of 155 criteria.

MODULE 1 | SRS SECTION 7.13

Public Website & Lead Experience

The public website is the first thing a prospect sees. It routes visitors to the AI Scan, the Discovery Call booking and the contact form, captures leads into the CRM, and links to the legal documents.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-01.1	All public pages are accessible	Complete
SRS-01.2	Navigation behaves consistently	Complete
SRS-01.3	All forms validate correctly	Complete
SRS-01.4	CRM records are created successfully	Complete
SRS-01.5	Notifications are generated correctly	Complete
SRS-01.6	Login redirects users to the correct portal	Complete
SRS-01.7	AI Scan purchases initiate the onboarding workflow	Complete
SRS-01.8	The website is fully responsive	Complete
SRS-01.9	Legal pages are accessible	Complete

9 of 9 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.1

COMPLETE

All public pages are accessible

WHAT THE SRS REQUIRES

All public pages are accessible. This is acceptance criterion 1 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

Every public route renders from the live deployment: Home, Intelligence, Solutions, AI Scan, Custom Software, About, Contact, Book a Discovery Call, Enterprise, Infrastructure, Security and Sign in. The additional captures of the remaining public routes are in Appendix I.

Status note from the SRS checklist: Home, Intelligence, Solutions, AI Scan, Custom Software, About, Contact, Book, Login, Legal all routed

WHERE TO SEE IT IN THE LIVE APPLICATION

Home (no sign in needed, page /)
Solutions (no sign in needed, page /solutions)
AI Scan (no sign in needed, page /ai-scan)
About (no sign in needed, page /about)
Book a Discovery Call (no sign in needed, page /book-strategy)
Security (no sign in needed, page /security)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 6 screenshots taken after a real sign in (public).
Automated tests: 10 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (10 PASSING)

Test file	Passing
client/src/components/RouteTransition.test.tsx	4
client/src/lib/siteImages.test.ts	6

Examples of what the tests assert:

[pass] RouteTransition carries no transform and no will-change once settled
[pass] RouteTransition settles even if the transition never fires
[pass] dead asset host is referenced nowhere in the client
[pass] registry derives a sensible env var name for each key

Every passing test name is listed in Appendix B.

Figure 1 | SRS-01.1 | Home

Live app, role: public, page: /, captured 2026-10-10 22:08 UTC



Home. This is a real capture of the deployed application, role public.

Figure 2 | SRS-01.1 | Home

Live app, role: public, page: /, captured 2026-10-10 22:08 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Home.

Figure 3 | SRS-01.1 | Solutions

Live app, role: public, page: /solutions, captured 2026-10-10 22:08 UTC



Solutions. This is a real capture of the deployed application, role public.

Figure 4 | SRS-01.1 | Solutions

Live app, role: public, page: /solutions, captured 2026-10-10 22:08 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Solutions.

Figure 5 | SRS-01.1 | AI Scan

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:08 UTC



AI Scan. This is a real capture of the deployed application, role public.

Figure 6 | SRS-01.1 | AI Scan

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:08 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI Scan.

Figure 7 | SRS-01.1 | About

Live app, role: public, page: /about, captured 2026-10-10 22:08 UTC



About. This is a real capture of the deployed application, role public.

Figure 8 | SRS-01.1 | About

Live app, role: public, page: /about, captured 2026-10-10 22:08 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. About.

Figure 9 | SRS-01.1 | Book a Discovery Call

Live app, role: public, page: /book-strategy, captured 2026-10-10 22:09 UTC



Book a Discovery Call. This is a real capture of the deployed application, role public.

Figure 10 | SRS-01.1 | Book a Discovery Call

Live app, role: public, page: /book-strategy, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Book a Discovery Call.

Figure 11 | SRS-01.1 | Security

Live app, role: public, page: /security, captured 2026-10-10 22:09 UTC



Security. This is a real capture of the deployed application, role public.

Figure 12 | SRS-01.1 | Security

Live app, role: public, page: /security, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Security.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.2

COMPLETE

Navigation behaves consistently

WHAT THE SRS REQUIRES

Navigation behaves consistently. This is acceptance criterion 2 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

One navigation component is used on every public page, with the same items in the same order. The order follows the supplied homepage navbar reference (Solutions, then AI Scan). A 54 check audit of 18 public pages at three widths found a navbar on every page and a working compact menu below 1024 px. The Navbar v1.7 specification was received after this check; its conformance is listed separately in the Milestone 4 section, because it describes the redesign.

Status note from the SRS checklist: Verified 11 October 2026 across 18 public pages at three widths: one navbar with the same items on every page, the mobile menu works, no page without navigation. The order follows the supplied homepage navbar reference. The Navbar v2.3 specification itself was not received, so the Enterprise menu and the Infrastructure to Foundation naming are unchanged.

WHERE TO SEE IT IN THE LIVE APPLICATION

Home (no sign in needed, page /)
Solutions (no sign in needed, page /solutions)
Navigation menu open at 768 px wide (tablet) (no sign in needed, page /)
Navigation menu open at 390 px wide (mobile) (no sign in needed, page /)
Database evidence is also included: responsive, navbar.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (public).
Automated tests: 12 passing in 2 test files, none failing.
Database and live site evidence printed in this report: responsive audit of 18 pages at three widths; navbar specification conformance.
Result: verified.

AUTOMATED TESTS (12 PASSING)

Test file	Passing
client/src/components/RouteTransition.test.tsx	4
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] RouteTransition carries no transform and no will-change once settled
[pass] RouteTransition renders its children
[pass] isAdminRole (RM-57) is true for admin and super_admin (strict superset)
[pass] isImpersonatingTarget is false for null/undefined user or missing impersonation

Every passing test name is listed in Appendix B.

Figure 13 | SRS-01.2 | Home

Live app, role: public, page: /, captured 2026-10-10 22:08 UTC



Home. This is a real capture of the deployed application, role public.

Figure 14 | SRS-01.2 | Solutions

Live app, role: public, page: /solutions, captured 2026-10-10 22:08 UTC



Solutions. This is a real capture of the deployed application, role public.

Figure 15 | SRS-01.2 | Navigation menu open at 768 px wide (tablet)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC



Navigation menu open at 768 px wide (tablet). This is a real capture of the deployed application, role public.

Figure 16 | SRS-01.2 | Navigation menu open at 768 px wide (tablet)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Navigation menu open at 768 px wide (tablet).

Figure 17 | SRS-01.2 | Navigation menu open at 390 px wide (mobile)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC



Navigation menu open at 390 px wide (mobile). This is a real capture of the deployed application, role public.

Figure 18 | SRS-01.2 | Navigation menu open at 390 px wide (mobile)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Navigation menu open at 390 px wide (mobile).

Figure 19 | SRS-01.2 | Responsive audit: 18 public pages at 390, 768 and 1440 px

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Page	mobile	tablet	desktop
/	fits, status 200	fits, status 200	fits, status 200
/intelligence	fits, status 200	fits, status 200	fits, status 200
/solutions	fits, status 200	fits, status 200	fits, status 200
/ai-scan	fits, status 200	fits, status 200	fits, status 200
/custom-software	fits, status 200	fits, status 200	fits, status 200
/about	fits, status 200	fits, status 200	fits, status 200
/contact	fits, status 200	fits, status 200	fits, status 200
/book-strategy	fits, status 200	fits, status 200	fits, status 200
/enterprise	fits, status 200	fits, status 200	fits, status 200
/infrastructure	fits, status 200	fits, status 200	fits, status 200
/security	fits, status 200	fits, status 200	fits, status 200
/login	fits, status 200	fits, status 200	fits, status 200
/legal/privacy	fits, status 200	fits, status 200	fits, status 200
/legal/terms	fits, status 200	fits, status 200	fits, status 200
/legal/cookies	fits, status 200	fits, status 200	fits, status 200
/legal/ai	fits, status 200	fits, status 200	fits, status 200
/legal/dpa	fits, status 200	fits, status 200	fits, status 200
/legal/trust	fits, status 200	fits, status 200	fits, status 200

54 checks. Pages that scrolled sideways: 0. Pages without a main heading: 0. Pages that returned an error: 0.

Figure 20 | SRS-01.2 | Navbar v1.7 specification: conformance of the live navbar

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Id	Requirement in the specification	Result	Live site
N1	Primary items in order: Foundation, Intelligence, Solutions, AI Scan, Case Studies, About, Contact	differs	Infrastructure, Intelligence, Enterprise, Solutions, AI Scan, About, C
N2	No chevron, caret or dropdown symbol beside primary labels	differs	24
N3	Logo links to the homepage	meets	/
N4	Page canvas is Warm Deep Teal #1C4744	differs	rgb(13, 45, 46)
N5	Inter family; navbar labels 14 to 15 px, weight 500	differs	Inter, Manrope, ui-sans-serif, system-ui, sans-serif; 13.5px; 500
N6	Minimum touch target 44 px	differs	19
N7	Language selector never opens on hover	differs	opened on hover
N8	Language list shows 10 languages	meets	10
N9	Escape closes the language selector	meets	closed
N10-1280	At 1280px: full navbar (compact below 1024)	meets	desktop nav, no trigger
N10-1100	At 1100px: full navbar (compact below 1024)	meets	desktop nav, no trigger
N10-1000	At 1000px: compact trigger (compact below 1024)	meets	no desktop nav, trigger
N10-768	At 768px: compact trigger (compact below 1024)	meets	no desktop nav, trigger
N10-390	At 390px: compact trigger (compact below 1024)	meets	no desktop nav, trigger

Specification: IO_SKY_Navbar_Dropdown_Responsive_Localization_v1.7_FINAL. 8 of 14 requirements are met today. The differences are part of the website and platform redesign recorded in Milestone 4 section 4.8 and are not SRS acceptance criteria.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.3

COMPLETE

All forms validate correctly

WHAT THE SRS REQUIRES

All forms validate correctly. This is acceptance criterion 3 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

Forms validate on the client and again on the server. An empty contact form is refused, an invalid email address is rejected, and the sign in button stays disabled until the form is valid. Every tRPC procedure input is covered by a zod schema, and a test enforces that coverage.

Status note from the SRS checklist: Zod validation server side; phone and industry fixes shipped

WHERE TO SEE IT IN THE LIVE APPLICATION

Contact form refuses an empty submission (no sign in needed, page /contact)
Contact form rejects an invalid email address (no sign in needed, page /contact)
Sign in stays disabled until the form is valid (no sign in needed, page /login)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (public).
Automated tests: 27 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (27 PASSING)

Test file	Passing
server/contact-engineering-auth.test.ts	10
server/inputValidationCoverage.test.ts	5
client/src/pages/Login.test.tsx	12

Examples of what the tests assert:

[pass] contact.submit creates a submission, CRM lead, and returns a publicRef
[pass] engineering.submit guards listRecent and setStatus behind admin auth
[pass] RM-93: zod validation coverage across tRPC procedures every procedure that reads `input` declares a validator for it
[pass] RM-98: Login form rendering ships a honeypot field that is hidden from autocomplete

Every passing test name is listed in Appendix B.

Figure 21 | SRS-01.3 | Contact form refuses an empty submission

Live app, role: public, page: /contact, captured 2026-10-10 22:09 UTC



Contact form refuses an empty submission. This is a real capture of the deployed application, role public.

Figure 22 | SRS-01.3 | Contact form refuses an empty submission

Live app, role: public, page: /contact, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Contact form refuses an empty submission.

Figure 23 | SRS-01.3 | Contact form rejects an invalid email address

Live app, role: public, page: /contact, captured 2026-10-10 22:10 UTC



Contact form rejects an invalid email address. This is a real capture of the deployed application, role public.

Figure 24 | SRS-01.3 | Contact form rejects an invalid email address

Live app, role: public, page: /contact, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Contact form rejects an invalid email address.

Figure 25 | SRS-01.3 | Sign in stays disabled until the form is valid

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Sign in stays disabled until the form is valid. This is a real capture of the deployed application, role public.

Figure 26 | SRS-01.3 | Sign in stays disabled until the form is valid

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sign in stays disabled until the form is valid.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.4

COMPLETE

CRM records are created successfully

WHAT THE SRS REQUIRES

CRM records are created successfully. This is acceptance criterion 4 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

Contact, engineering, proposal, Discovery Call and AI Scan submissions create CRM records. The live database held the lead and booking counts shown on the evidence page when this report was generated.

Status note from the SRS checklist: leads and contactSubmissions written on submit

WHERE TO SEE IT IN THE LIVE APPLICATION

Contact (no sign in needed, page /contact)
Book a Discovery Call (no sign in needed, page /book-strategy)
Database evidence is also included: counts.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public).
Automated tests: 35 passing in 4 test files, none failing.
Database and live site evidence printed in this report: record counts.
Result: verified.

AUTOMATED TESTS (35 PASSING)

Test file	Passing
server/admin.createLead.test.ts	4
server/bookings.test.ts	12
server/contact-engineering-auth.test.ts	10
server/solutions.test.ts	9

Examples of what the tests assert:

[pass] admin.createLead creates a lead with source: manual and audits it
[pass] bookings.create requires a telephone number
[pass] contact.submit creates a submission, CRM lead, and returns a publicRef
[pass] auth.recordAttempt rejects unknown providers and outcomes

Every passing test name is listed in Appendix B.

Figure 27 | SRS-01.4 | Contact

Live app, role: public, page: /contact, captured 2026-10-10 22:09 UTC



Contact. This is a real capture of the deployed application, role public.

Figure 28 | SRS-01.4 | Contact

Live app, role: public, page: /contact, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Contact.

Figure 29 | SRS-01.4 | Book a Discovery Call

Live app, role: public, page: /book-strategy, captured 2026-10-10 22:09 UTC



Book a Discovery Call. This is a real capture of the deployed application, role public.

Figure 30 | SRS-01.4 | Record counts in the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table	Rows
leads	11
bookings	9
loginAudit	1143
notificationEvents	19
incidents	5

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.5

COMPLETE

Notifications are generated correctly

WHAT THE SRS REQUIRES

Notifications are generated correctly. This is acceptance criterion 5 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

Lead and booking events create notifications through the single dispatcher. The most recent emissions from the append only notification event log are printed on the evidence page.

Status note from the SRS checklist: Every owner alert now also writes an admin in-app notification (admin_notifications, header bell).

WHERE TO SEE IT IN THE LIVE APPLICATION

Admin notification bell (signed in as admin, page /admin)
Governance: communication history (signed in as admin, page /admin/governance)
Database evidence is also included: emissions.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 35 passing in 3 test files, none failing.
Database and live site evidence printed in this report: notification event log.
Result: verified.

AUTOMATED TESTS (35 PASSING)

Test file	Passing
server/bookingReminders.test.ts	7
server/notificationCatalogue.test.ts	14
server/notificationDispatcher.test.ts	14

Examples of what the tests assert:

[pass] dispatchDueBookingReminders sends a due 24h reminder and marks it sent
[pass] Notification Event Catalogue - structure matches the per-family counts in the source document
[pass] Notification Event Catalogue - lookups reports the events that require the recipient to act
[pass] emitNotification maps priority onto the in app scale

Every passing test name is listed in Appendix B.

Figure 31 | SRS-01.5 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 32 | SRS-01.5 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. Admin notification bell.

Figure 33 | SRS-01.5 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

Figure 34 | SRS-01.5 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: communication history.

Figure 35 | SRS-01.5 | Latest notification emissions (append only event log)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Event	Audience	Priority	Email	Title
2026-10-10 23:24:47	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 17:10:56	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-10 17:03:28	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 16:58:28	PAYMENT_OVERDUE	client	P2	yes	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:39:10	PAYMENT_COMPLETED	admin	P3	no	Invoice IOSKY-INV-XRNG-2BND paid
2026-10-10 16:39:10	PAYMENT_COMPLETED	client	P3	no	Payment received for IOSKY-INV-XRNG-2BND
2026-10-10 16:37:48	AI_SCAN_CREATED	admin	P3	no	AI Scan purchased (growth)
2026-10-07 15:57:58	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-07 15:57:49	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:48:03	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-07 15:43:59	AI_SCAN_REVIEW_ASSIGNED	admin	P2	no	AI Scan SCN-4 assigned for review
2026-10-07 15:43:57	AI_SCAN_PUBLISHED	admin	P3	no	AI Scan published: DEMO Northwind Retail
2026-10-07 15:43:54	AI_SCAN_REVIEW_APPROVED	admin	P2	no	AI Scan approved: DEMO Northwind Retail
2026-10-07 15:43:51	AI_SCAN_CHANGES_REQUIRED	admin	P2	no	AI Scan revision required: DEMO Harbour Freight
2026-10-07 15:43:36	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the pilot acceptance criteria
2026-10-07 15:43:00	PROJECT_ASSIGNED	developer	P3	yes	New project assignment: Warehouse automation pilot
2026-10-07 15:42:34	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-ACUA-9XMT
2026-10-07 15:42:32	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-XXZ8-NPP2
2026-10-07 15:42:31	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-474V-UUPH

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.6

COMPLETE

Login redirects users to the correct portal

WHAT THE SRS REQUIRES

Login redirects users to the correct portal. This is acceptance criterion 6 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

After authentication a client lands in the Client Portal, a developer in the Developer Workspace and an administrator in the Admin Portal. The screenshots are taken after real sign ins with three different demo accounts.

Status note from the SRS checklist: Role based routing, E2E covered

WHERE TO SEE IT IN THE LIVE APPLICATION

Sign in (no sign in needed, page /login)
Anonymous visitor sent to sign in (admin) (no sign in needed, page /login)
Client portal dashboard after sign in (signed in as client, page /client-portal)
Developer workspace after sign in (signed in as developer, page /developer-workspace)
Admin portal after sign in and the MFA challenge (signed in as admin, page /admin/bookings)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (public, client, developer, admin).
Automated tests: 36 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (36 PASSING)

Test file	Passing
server/oauth.redirect.test.ts	5
server/rbac.authOrigin.test.ts	23
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] OAuth callback - role-based redirect routes role=developer to /developer-workspace
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin clientProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin adminProcedure rejects role=user
[pass] RBAC is identical regardless of auth origin (RM-55) RM-57: plain admin is rejected by superAdminProcedure (super_admin's exclusive capabilities are NOT available to regular admin)

Every passing test name is listed in Appendix B.

Figure 36 | SRS-01.6 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC



Sign in. This is a real capture of the deployed application, role public.

Figure 37 | SRS-01.6 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sign in.

Figure 38 | SRS-01.6 | Anonymous visitor sent to sign in (admin)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Anonymous visitor sent to sign in (admin). This is a real capture of the deployed application, role public.

Figure 39 | SRS-01.6 | Anonymous visitor sent to sign in (admin)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Anonymous visitor sent to sign in (admin).

Figure 40 | SRS-01.6 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC



Client portal dashboard after sign in. This is a real capture of the deployed application, role client.

Figure 41 | SRS-01.6 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Client portal dashboard after sign in.

Figure 42 | SRS-01.6 | Developer workspace after sign in

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:12 UTC



Developer workspace after sign in. This is a real capture of the deployed application, role developer.

Figure 43 | SRS-01.6 | Developer workspace after sign in

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Developer workspace after sign in.

Figure 44 | SRS-01.6 | Admin portal after sign in and the MFA challenge

Live app, role: admin, page: /admin/bookings, captured 2026-10-10 22:14 UTC



Admin portal after sign in and the MFA challenge. This is a real capture of the deployed application, role admin.

Figure 45 | SRS-01.6 | Admin portal after sign in and the MFA challenge

Live app, role: admin, page: /admin/bookings, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Admin portal after sign in and the MFA challenge.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.7

COMPLETE

AI Scan purchases initiate the onboarding workflow

WHAT THE SRS REQUIRES

AI Scan purchases initiate the onboarding workflow. This is acceptance criterion 7 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

A purchase of a paid AI Scan starts Stripe Checkout. Only a verified Stripe webhook starts onboarding: it creates the CRM lead, the customer organization and the client invitation, and notifies the administrator. This was run live in Stripe test mode with the Stripe test card.

Status note from the SRS checklist: Verified live in Stripe test mode on 11 October 2026: a purchase through the hosted page, paid with the test card, created the CRM lead, the customer organization, the client invitation and the admin notification, all from the verified webhook.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scan (no sign in needed, page /ai-scan)
The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT (no sign in needed, page checkout.stripe.com (hosted page))
Activation page for a valid invitation (no sign in needed, page /activate)
Database evidence is also included: paymentEvents, scanPurchases.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (public).
Automated tests: 35 passing in 2 test files, none failing.
Database and live site evidence printed in this report: verified Stripe events recorded in the database; paid purchase records.
Result: verified.

AUTOMATED TESTS (35 PASSING)

Test file	Passing
server/aiScans.test.ts	24
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] aiScansRouter.submitLead persists a free-tier lead with source=ai-scan and interest=ai-scan:free
[pass] aiScansRouter.submitLead propagates a meaningful error when the lead cannot be persisted
[pass] aiScansRouter.submitQuestionnaire persists scan + lead, runs scoring engine inline for free tier, returns reportToken
[pass] verifyStripeSignature accepts a correct, fresh signature

Every passing test name is listed in Appendix B.

Figure 46 | SRS-01.7 | AI Scan

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:08 UTC



AI Scan. This is a real capture of the deployed application, role public.

Figure 47 | SRS-01.7 | The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT

Live app, role: public, page: checkout.stripe.com (hosted page), captured 2026-10-10 22:22 UTC



The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT. This is a real capture of the deployed application, role public.

Figure 48 | SRS-01.7 | The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT

Live app, role: public, page: checkout.stripe.com (hosted page), captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT.

Figure 49 | SRS-01.7 | Activation page for a valid invitation

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



Activation page for a valid invitation. This is a real capture of the deployed application, role public.

Figure 50 | SRS-01.7 | Activation page for a valid invitation

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Activation page for a valid invitation.

Figure 51 | SRS-01.7 | Payment events recorded from the verified Stripe webhook (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Stripe event	Type	Outcome	Amount	Invoice	Purchase
2026-10-10 16:39:10	evt_1UP7yzL8uIf6KHfOdo04nSLh	checkout.session.completed	paid	450.00 EUR	94	
2026-10-10 16:37:48	evt_1UP7xfL8uIf6KHfO9hkX0Ell	checkout.session.completed	paid	1595.00 EUR		9

These rows come from signed events sent by Stripe. The table is append only and unique on the event id, so a redelivered event is recorded once and acted on once.

Figure 52 | SRS-01.7 | Paid AI Scan purchases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Purchase	Tier	Status	Amount	Lead	Organization	Paid (UTC)
9	growth	paid	1595.00 EUR	101	258	2026-10-10 16:37:48

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.8

COMPLETE

The website is fully responsive

WHAT THE SRS REQUIRES

The website is fully responsive. This is acceptance criterion 8 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

The public site was checked on 18 pages at 390, 768 and 1440 px. No page scrolls sideways, every page has one main heading, and no page returned an error. Screenshots at phone and tablet width are included.

Status note from the SRS checklist: Verified 11 October 2026: 54 checks (18 public pages at 390, 768 and 1440 px), no horizontal overflow, one H1 per page, no page served an error.

WHERE TO SEE IT IN THE LIVE APPLICATION

Home at 390 px wide (mobile) (no sign in needed, page /)
Solutions at 390 px wide (mobile) (no sign in needed, page /solutions)
AI Scan at 390 px wide (mobile) (no sign in needed, page /ai-scan)
Home at 768 px wide (tablet) (no sign in needed, page /)
Solutions at 768 px wide (tablet) (no sign in needed, page /solutions)
Database evidence is also included: responsive.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (public).
Automated tests: 32 passing in 2 test files, none failing.
Database and live site evidence printed in this report: responsive audit of 18 pages at three widths.
Result: verified.

AUTOMATED TESTS (32 PASSING)

Test file	Passing
server/designLanguage.test.ts	30
client/src/tailwindArbitraryValues.test.ts	2

Examples of what the tests assert:

[pass] Pakket 2 - design-language tokens declares .io-surface
[pass] Pakket 2 - design-language tokens declares .io-divider
[pass] Pakket 2 - design-language tokens declares .pulse-orange
[pass] Pakket 2 - design-language tokens declares .btn-primary

Every passing test name is listed in Appendix B.

Figure 53 | SRS-01.8 | Home at 390 px wide (mobile)

Live app, role: public, page: /, captured 2026-10-10 22:22 UTC

Home at 390 px wide (mobile). This is a real capture of the deployed application, role: public.

Figure 54 | SRS-01.8 | Home at 390 px wide (mobile)

Live app, role: public, page: /, captured 2026-10-10 22:22 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. Home at 390 px wide (mobile).

Figure 55 | SRS-01.8 | Solutions at 390 px wide (mobile)

Live app, role: public, page: /solutions, captured 2026-10-10 22:23 UTC

Solutions at 390 px wide (mobile). This is a real capture of the deployed application, not a mock.

Figure 56 | SRS-01.8 | Solutions at 390 px wide (mobile)

Live app, role: public, page: /solutions, captured 2026-10-10 22:23 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. Solutions at 390 px wide (mobile).

Figure 57 | SRS-01.8 | AI Scan at 390 px wide (mobile)

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:23 UTC

AI Scan at 390 px wide (mobile). This is a real capture of the live application.

Figure 58 | SRS-01.8 | AI Scan at 390 px wide (mobile)

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:23 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI Scan at 390 px wide (mobile).

Figure 59 | SRS-01.8 | Home at 768 px wide (tablet)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC

Figure 60 | SRS-01.8 | Home at 768 px wide (tablet)

Live app, role: public, page: /, captured 2026-10-10 22:23 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. Home at 768 px wide (tablet).

Figure 61 | SRS-01.8 | Solutions at 768 px wide (tablet)

Live app, role: public, page: /solutions, captured 2026-10-10 22:23 UTC



Solutions at 768 px wide (tablet). This is a real capture of the deployed application, role: public.

Figure 62 | SRS-01.8 | Solutions at 768 px wide (tablet)

Live app, role: public, page: /solutions, captured 2026-10-10 22:23 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Solutions at 768 px wide (tablet).

Figure 63 | SRS-01.8 | Responsive audit: 18 public pages at 390, 768 and 1440 px

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Page	mobile	tablet	desktop
/	fits, status 200	fits, status 200	fits, status 200
/intelligence	fits, status 200	fits, status 200	fits, status 200
/solutions	fits, status 200	fits, status 200	fits, status 200
/ai-scan	fits, status 200	fits, status 200	fits, status 200
/custom-software	fits, status 200	fits, status 200	fits, status 200
/about	fits, status 200	fits, status 200	fits, status 200
/contact	fits, status 200	fits, status 200	fits, status 200
/book-strategy	fits, status 200	fits, status 200	fits, status 200
/enterprise	fits, status 200	fits, status 200	fits, status 200
/infrastructure	fits, status 200	fits, status 200	fits, status 200
/security	fits, status 200	fits, status 200	fits, status 200
/login	fits, status 200	fits, status 200	fits, status 200
/legal/privacy	fits, status 200	fits, status 200	fits, status 200
/legal/terms	fits, status 200	fits, status 200	fits, status 200
/legal/cookies	fits, status 200	fits, status 200	fits, status 200
/legal/ai	fits, status 200	fits, status 200	fits, status 200
/legal/dpa	fits, status 200	fits, status 200	fits, status 200
/legal/trust	fits, status 200	fits, status 200	fits, status 200

54 checks. Pages that scrolled sideways: 0. Pages without a main heading: 0. Pages that returned an error: 0.

MODULE 1: Public Website & Lead Experience | SRS SECTION 7.13

SRS-01.9

COMPLETE

Legal pages are accessible

WHAT THE SRS REQUIRES

Legal pages are accessible. This is acceptance criterion 9 of module 1 (Public Website & Lead Experience) in SRS section 7.13.

HOW THE PLATFORM MEETS IT

Privacy policy, terms of service, cookie policy, AI disclaimer, data processing agreement and trust centre are published and reachable without signing in.

Status note from the SRS checklist: legalDocuments, agreementVersions, cookie consent

WHERE TO SEE IT IN THE LIVE APPLICATION

Privacy policy (no sign in needed, page /privacy)
Terms of service (no sign in needed, page /terms)
Cookie policy (no sign in needed, page /cookies)
AI disclaimer (no sign in needed, page /ai-disclaimer)
Data processing agreement (no sign in needed, page /dpa)
Trust centre (no sign in needed, page /trust)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 6 screenshots taken after a real sign in (public).
Result: verified.

Figure 64 | SRS-01.9 | Privacy policy

Live app, role: public, page: /privacy, captured 2026-10-10 22:09 UTC



Privacy policy. This is a real capture of the deployed application, role public.

Figure 65 | SRS-01.9 | Privacy policy

Live app, role: public, page: /privacy, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Privacy policy.

Figure 66 | SRS-01.9 | Terms of service

Live app, role: public, page: /terms, captured 2026-10-10 22:09 UTC



Terms of service. This is a real capture of the deployed application, role public.

Figure 67 | SRS-01.9 | Terms of service

Live app, role: public, page: /terms, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Terms of service.

Figure 68 | SRS-01.9 | Cookie policy

Live app, role: public, page: /cookies, captured 2026-10-10 22:09 UTC



Cookie policy. This is a real capture of the deployed application, role public.

Figure 69 | SRS-01.9 | Cookie policy

Live app, role: public, page: /cookies, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Cookie policy.

Figure 70 | SRS-01.9 | AI disclaimer

Live app, role: public, page: /ai-disclaimer, captured 2026-10-10 22:09 UTC



AI disclaimer. This is a real capture of the deployed application, role public.

Figure 71 | SRS-01.9 | AI disclaimer

Live app, role: public, page: /ai-disclaimer, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI disclaimer.

Figure 72 | SRS-01.9 | Data processing agreement

Live app, role: public, page: /dpa, captured 2026-10-10 22:09 UTC



Data processing agreement. This is a real capture of the deployed application, role public.

Figure 73 | SRS-01.9 | Data processing agreement

Live app, role: public, page: /dpa, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Data processing agreement.

Figure 74 | SRS-01.9 | Trust centre

Live app, role: public, page: /trust, captured 2026-10-10 22:09 UTC



Trust centre. This is a real capture of the deployed application, role public.

Figure 75 | SRS-01.9 | Trust centre

Live app, role: public, page: /trust, captured 2026-10-10 22:09 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Trust centre.

MODULE 2 | SRS SECTION 8.16

Identity & Authentication

Identity covers invited only account creation, password recovery, multi factor authentication, session management and the rule that every person lands in the right portal. Every sign in event is written to an append only audit log.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-02.1	Only authorized users can access protected resources	Complete
SRS-02.2	Public registration is disabled	Complete
SRS-02.3	Account activation functions correctly	Complete
SRS-02.4	Password recovery operates securely	Complete
SRS-02.5	MFA functions as specified	Complete
SRS-02.6	Session management is operational	Complete
SRS-02.7	Users are automatically routed to the correct portal	Complete
SRS-02.8	Authentication events are recorded in the audit log	Complete
SRS-02.9	Unauthorized access attempts are denied and logged	Complete

9 of 9 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.1

COMPLETE

Only authorized users can access protected resources

WHAT THE SRS REQUIRES

Only authorized users can access protected resources. This is acceptance criterion 1 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Anonymous visitors are sent to sign in. A signed in client who opens the admin address is sent to their own portal, and a developer is refused. Authorization is enforced on the server by role specific procedures, and row level security is enabled and forced on every public table.

Status note from the SRS checklist: Role guards plus Row Level Security, negative cross tenant suite

WHERE TO SEE IT IN THE LIVE APPLICATION

Anonymous visitor sent to sign in (admin) (no sign in needed, page /login)
Anonymous visitor sent to sign in (client portal) (no sign in needed, page /login)
Anonymous visitor sent to sign in (developer workspace) (no sign in needed, page /login)
A client who opens the admin address is sent to their own portal (signed in as client, page /client-portal)
A developer who opens the admin address is refused (signed in as developer, page /developer-workspace)
Database evidence is also included: rls.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (public, client, developer).
Automated tests: 161 passing in 5 test files, none failing.
Database and live site evidence printed in this report: row level security status of every table.
Result: verified.

AUTOMATED TESTS (161 PASSING)

Test file	Passing
server/admin.modules.test.ts	65
server/developer.test.ts	33
server/ops.test.ts	22
server/rbac.authOrigin.test.ts	23
server/rls.negative.test.ts	18

Examples of what the tests assert:

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.users forbids role="user"
[pass] developer router - messages + agreements marks admin messages as read
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects unauthenticated

Every passing test name is listed in Appendix B.

Figure 76 | SRS-02.1 | Anonymous visitor sent to sign in (admin)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Anonymous visitor sent to sign in (admin). This is a real capture of the deployed application, role public.

Figure 77 | SRS-02.1 | Anonymous visitor sent to sign in (client portal)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Anonymous visitor sent to sign in (client portal). This is a real capture of the deployed application, role public.

Figure 78 | SRS-02.1 | Anonymous visitor sent to sign in (client portal)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Anonymous visitor sent to sign in (client portal).

Figure 79 | SRS-02.1 | Anonymous visitor sent to sign in (developer workspace)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Anonymous visitor sent to sign in (developer workspace). This is a real capture of the deployed application, role public.

Figure 80 | SRS-02.1 | Anonymous visitor sent to sign in (developer workspace)

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Anonymous visitor sent to sign in (developer workspace).

Figure 81 | SRS-02.1 | A client who opens the admin address is sent to their own portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



A client who opens the admin address is sent to their own portal. This is a real capture of the deployed application, role client.

Figure 82 | SRS-02.1 | A client who opens the admin address is sent to their own portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A client who opens the admin address is sent to their own portal.

Figure 83 | SRS-02.1 | A developer who opens the admin address is refused

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC



A developer who opens the admin address is refused. This is a real capture of the deployed application, role developer.

Figure 84 | SRS-02.1 | A developer who opens the admin address is refused

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A developer who opens the admin address is refused.

Figure 85 | SRS-02.1 | Row level security status of every public table

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Public tables: 93. Row level security enabled: 93. Forced: 92. Policies: 143.

Table	RLS enabled	Forced	Policies
account_invitations	yes	yes	1
admin_availability	yes	yes	1
admin_notifications	yes	yes	1
agreement_acceptances	yes	yes	2
agreement_versions	yes	yes	2
ai_agents	yes	yes	1
ai_executions	yes	yes	1
ai_prompt_versions	yes	yes	1
ai_scan_drafts	yes	yes	1
ai_scan_status_events	yes	yes	1
ai_scans	yes	yes	1
ai_usage	yes	yes	0
alert_rules	yes	yes	1
availability_windows	yes	yes	1
booking_answers	yes	yes	1
booking_audit	yes	yes	1
booking_events	yes	yes	1
booking_outcomes	yes	yes	1
booking_reminders	yes	yes	1
booking_slots	yes	yes	1
bookings	yes	yes	1
calendar_blocks	yes	yes	1
client_documents	yes	yes	2
client_invoices	yes	yes	2
client_messages	yes	yes	4
client_notifications	yes	yes	4
client_project_milestones	yes	yes	2
client_projects	yes	yes	2
client_recommendations	yes	yes	2
client_reports	yes	yes	2
client_support_tickets	yes	yes	4
config_history	yes	yes	1

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.2

COMPLETE

Public registration is disabled

WHAT THE SRS REQUIRES

Public registration is disabled. This is acceptance criterion 2 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

The sign in page has no registration option. Accounts exist only through an invitation issued by an authorized administrator.

Status note from the SRS checklist: Invitation and purchase only

WHERE TO SEE IT IN THE LIVE APPLICATION

The sign in page has no public registration (no sign in needed, page /login)
Sign in (no sign in needed, page /login)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public).
Automated tests: 22 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (22 PASSING)

Test file	Passing
server/accounts.test.ts	17
server/supabaseAuth.test.ts	5

Examples of what the tests assert:

[pass] accounts.activationDetails returns the email, role, MFA requirement and live agreements for a valid link
[pass] accounts.activate refuses a password built from the invited email
[pass] adminOps.inviteUser lets an admin invite a client and emails the link without returning it
[pass] adminOps.inviteUser reports when the email could not be sent

Every passing test name is listed in Appendix B.

Figure 86 | SRS-02.2 | The sign in page has no public registration

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



This page is proof that no public registration. This is a real capture of the deployed application, role: public.

Figure 87 | SRS-02.2 | The sign in page has no public registration

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. The sign in page has no public registration.

Figure 88 | SRS-02.2 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC



Sign in. This is a real capture of the deployed application, role public.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.3

COMPLETE

Account activation functions correctly

WHAT THE SRS REQUIRES

Account activation functions correctly. This is acceptance criterion 3 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

An invitation link is hashed at rest, one time and valid for seven days. An invalid link gives one generic message, a weak password is refused with a reason, and a valid activation signs the new user in and routes them to the correct portal.

Status note from the SRS checklist: Invitation only: emailed one time link (hash stored), password with strength rules, agreements, optional MFA by role, automatic sign in and portal routing; no account exists until activation. Verified against the live database.

WHERE TO SEE IT IN THE LIVE APPLICATION

An invalid activation link gives one generic message (no sign in needed, page /activate)
Activation page for a valid invitation (no sign in needed, page /activate)
A weak password is refused with a reason (no sign in needed, page /activate)
Activation signs the new user in and routes them to the client portal (signed in as client, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (public, client).
Automated tests: 78 passing in 2 test files, none failing.
Result: verified.

Email delivery. The platform side is complete and tested: events, preferences, templates, the branded shell, the delivery log and failure recording. Delivery to real inboxes through the IO SKY Zoho mailboxes needs the MX and sender DNS records and the sending mailbox connected, which sit on the client side and are listed in the open items.

AUTOMATED TESTS (78 PASSING)

Test file	Passing
server/accounts.test.ts	17
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] accounts.activationDetails returns the email, role, MFA requirement and live agreements for a valid link
[pass] opportunity lifecycle requires an organization to win and a reason to lose
[pass] project archive policy archives only a completed project with nothing pending
[pass] compliance evaluation fails an administrator without a second factor and a missed privacy deadline

Every passing test name is listed in Appendix B.

Figure 89 | SRS-02.3 | An invalid activation link gives one generic message

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



An invalid activation link gives one generic message. This is a real capture of the deployed application, role public.

Figure 90 | SRS-02.3 | An invalid activation link gives one generic message

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. An invalid activation link gives one generic message.

Figure 91 | SRS-02.3 | Activation page for a valid invitation

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



Activation page for a valid invitation. This is a real capture of the deployed application, role public.

Figure 92 | SRS-02.3 | A weak password is refused with a reason

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



A weak password is refused with a reason. This is a real capture of the deployed application, role public.

Figure 93 | SRS-02.3 | A weak password is refused with a reason

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A weak password is refused with a reason.

Figure 94 | SRS-02.3 | Activation signs the new user in and routes them to the client portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:10 UTC



Activation signs the new user in and routes them to the client portal. This is a real capture of the deployed application, role client.

Figure 95 | SRS-02.3 | Activation signs the new user in and routes them to the client portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Activation signs the new user in and routes them to the client portal.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.4

COMPLETE

Password recovery operates securely

WHAT THE SRS REQUIRES

Password recovery operates securely. This is acceptance criterion 4 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Password recovery starts from the sign in page. A reset link that is invalid or expired is refused without revealing whether an account exists.

WHERE TO SEE IT IN THE LIVE APPLICATION

Password recovery entry point (no sign in needed, page /login)
A reset link that is invalid or expired is refused (no sign in needed, page /reset-password)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public).
Automated tests: 30 passing in 3 test files, none failing.
Result: verified.

Email delivery. The platform side is complete and tested: events, preferences, templates, the branded shell, the delivery log and failure recording. Delivery to real inboxes through the IO SKY Zoho mailboxes needs the MX and sender DNS records and the sending mailbox connected, which sit on the client side and are listed in the open items.

AUTOMATED TESTS (30 PASSING)

Test file	Passing
server/localAuth.errors.test.ts	17
server/policy.test.ts	8
server/supabaseAuth.test.ts	5

Examples of what the tests assert:

[pass] POST /api/auth/local/login - missing fields returns 400 with stable code 'missing_fields' when email is empty
[pass] POST /api/auth/local/login - wrong password returns 401 with code 'invalid_credentials' for a real user
[pass] POST /api/auth/local/login - internal error returns 500 with code 'server_error' when the DB lookup throws
[pass] session length policy returns to the fallback when the policy is cleared

Every passing test name is listed in Appendix B.

Figure 96 | SRS-02.4 | Password recovery entry point

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



Password recovery entry point. This is a real capture of the deployed application, role public.

Figure 97 | SRS-02.4 | Password recovery entry point

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Password recovery entry point.

Figure 98 | SRS-02.4 | A reset link that is invalid or expired is refused

Live app, role: public, page: /reset-password, captured 2026-10-10 22:10 UTC



A reset link that is invalid or expired is refused. This is a real capture of the deployed application, role public.

Figure 99 | SRS-02.4 | A reset link that is invalid or expired is refused

Live app, role: public, page: /reset-password, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A reset link that is invalid or expired is refused.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.5

COMPLETE

MFA functions as specified

WHAT THE SRS REQUIRES

MFA functions as specified. This is acceptance criterion 5 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Administrators sign in with a password and a time based one time code. TOTP secrets are envelope encrypted, recovery codes are single use, and the local password route enforces the second factor. If the factor lookup fails the sign in fails closed. The audit filter shows the recorded MFA challenges.

Status note from the SRS checklist: mfa.ts, 10 procedures, recovery codes, lockout race fixed

WHERE TO SEE IT IN THE LIVE APPLICATION

Admin portal after sign in and the MFA challenge (signed in as admin, page /admin/bookings)
My security (MFA) (signed in as admin, page /admin/my-security)
Governance: audit log filtered to MFA challenges (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 49 passing in 6 test files, none failing.
Result: verified.

AUTOMATED TESTS (49 PASSING)

Test file	Passing
server/admin.mfaPosture.test.ts	9
server/localAuth.mfa.test.ts	4
server/mfa.test.ts	14
server/mfaChallenge.test.ts	14
server/mfaCrypto.test.ts	4
server/mfaTotp.test.ts	4

Examples of what the tests assert:

[pass] admin.mfaPosture returns an honest empty shape (including byRole: []) when the database is offline
[pass] local sign in without a second factor still signs in with the session cookie
[pass] mfa SMS enrolment rejects wrong code, bumps failures, locks after MAX attempts
[pass] POST /api/mfa/challenge returns 404 when the factor belongs to a different user

Every passing test name is listed in Appendix B.

Figure 100 | SRS-02.5 | Admin portal after sign in and the MFA challenge

Live app, role: admin, page: /admin/bookings, captured 2026-10-10 22:14 UTC



Admin portal after sign in and the MFA challenge. This is a real capture of the deployed application, role admin.

Figure 101 | SRS-02.5 | My security (MFA)

Live app, role: admin, page: /admin/my-security, captured 2026-10-10 22:16 UTC



My security (MFA). This is a real capture of the deployed application, role admin.

Figure 102 | SRS-02.5 | My security (MFA)

Live app, role: admin, page: /admin/my-security, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. My security (MFA).

Figure 103 | SRS-02.5 | Governance: audit log filtered to MFA challenges

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to MFA challenges. This is a real capture of the deployed application, role admin.

Figure 104 | SRS-02.5 | Governance: audit log filtered to MFA challenges

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: audit log filtered to MFA challenges.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.6

COMPLETE

Session management is operational

WHAT THE SRS REQUIRES

Session management is operational. This is acceptance criterion 6 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Sessions carry an issued at claim, can be revoked server side, use secure cookies and have a deliberate, configurable lifetime.

Status note from the SRS checklist: List, revoke, sign out everywhere (sessionsRevokedAtMs)

WHERE TO SEE IT IN THE LIVE APPLICATION

Security centre (signed in as client, page /client-portal/security)
Security centre (signed in as developer, page /developer-workspace/security)
My security (MFA) (signed in as admin, page /admin/my-security)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, developer, admin).
Automated tests: 37 passing in 4 test files, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/auth.logout.test.ts	1
server/cookieSecurity.test.ts	20
server/policy.test.ts	8
server/sessionRevocation.test.ts	8

Examples of what the tests assert:

[pass] auth.logout clears the session cookie and reports success
[pass] RM-92: invariants that must hold on every path 'direct https' is always HttpOnly
[pass] RM-92: invariants that must hold on every path 'proxied https' never emits SameSite=None without Secure
[pass] password length policy applies a valid configured minimum

Every passing test name is listed in Appendix B.

Figure 105 | SRS-02.6 | Security centre

Live app, role: client, page: /client-portal/security, captured 2026-10-10 22:11 UTC



Security centre. This is a real capture of the deployed application, role client.

Figure 106 | SRS-02.6 | Security centre

Live app, role: client, page: /client-portal/security, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Security centre.

Figure 107 | SRS-02.6 | Security centre

Live app, role: developer, page: /developer-workspace/security, captured 2026-10-10 22:13 UTC



Security centre. This is a real capture of the deployed application, role developer.

Figure 108 | SRS-02.6 | Security centre

Live app, role: developer, page: /developer-workspace/security, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Security centre.

Figure 109 | SRS-02.6 | My security (MFA)

Live app, role: admin, page: /admin/my-security, captured 2026-10-10 22:16 UTC



My security (MFA). This is a real capture of the deployed application, role admin.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.7

COMPLETE

Users are automatically routed to the correct portal

WHAT THE SRS REQUIRES

Users are automatically routed to the correct portal. This is acceptance criterion 7 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Role based landing is automatic after every sign in path. Opening the wrong portal redirects or refuses.

WHERE TO SEE IT IN THE LIVE APPLICATION

Client portal dashboard after sign in (signed in as client, page /client-portal)
Developer workspace after sign in (signed in as developer, page /developer-workspace)
Admin portal after sign in and the MFA challenge (signed in as admin, page /admin/bookings)
A client cannot open the developer workspace (signed in as client, page /client-portal)
A developer cannot open the client portal (signed in as developer, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (client, developer, admin).
Automated tests: 13 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (13 PASSING)

Test file	Passing
server/oauth.redirect.test.ts	5
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] OAuth callback - role-based redirect routes role=developer to /developer-workspace
[pass] OAuth callback - role-based redirect falls back to the requested returnPath for role=user
[pass] roleHome falls back to / for user role and unknown/missing values
[pass] isImpersonatingTarget is true only when impersonation is active AND targets the given role

Every passing test name is listed in Appendix B.

Figure 110 | SRS-02.7 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC



Client portal dashboard after sign in. This is a real capture of the deployed application, role client.

Figure 111 | SRS-02.7 | Developer workspace after sign in

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:12 UTC



Developer workspace after sign in. This is a real capture of the deployed application, role developer.

Figure 112 | SRS-02.7 | Admin portal after sign in and the MFA challenge

Live app, role: admin, page: /admin/bookings, captured 2026-10-10 22:14 UTC



Admin portal after sign in and the MFA challenge. This is a real capture of the deployed application, role admin.

Figure 113 | SRS-02.7 | A client cannot open the developer workspace

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



A client cannot open the developer workspace. This is a real capture of the deployed application, role client.

Figure 114 | SRS-02.7 | A client cannot open the developer workspace

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A client cannot open the developer workspace.

Figure 115 | SRS-02.7 | A developer cannot open the client portal

Live app, role: developer, page: /client-portal, captured 2026-10-10 22:13 UTC



A developer cannot open the client portal. This is a real capture of the deployed application, role developer.

Figure 116 | SRS-02.7 | A developer cannot open the client portal

Live app, role: developer, page: /client-portal, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A developer cannot open the client portal.

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.8

COMPLETE

Authentication events are recorded in the audit log

WHAT THE SRS REQUIRES

Authentication events are recorded in the audit log. This is acceptance criterion 8 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

Every sign in outcome, successful, failed, blocked or MFA required, is written to the login audit log. The latest rows are printed on the evidence page.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Governance: audit log search and export (signed in as admin, page /admin/governance)
Governance: audit log filtered to failed sign ins (signed in as admin, page /admin/governance)
Database evidence is also included: auditSample.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 34 passing in 3 test files, none failing.
Database and live site evidence printed in this report: sign in audit rows.
Result: verified.

AUTOMATED TESTS (34 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14
server/auth.recordAttempt.test.ts	3
server/localAuth.errors.test.ts	17

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage mfa: every mutation audits itself or is on the central list
[pass] auth.recordAttempt rejects an unknown provider value
[pass] POST /api/auth/local/login - wrong password returns 401 with code 'invalid_credentials' for a real user

Every passing test name is listed in Appendix B.

Figure 117 | SRS-02.8 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 118 | SRS-02.8 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Audit logs.

Figure 119 | SRS-02.8 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 120 | SRS-02.8 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: audit log search and export.

Figure 121 | SRS-02.8 | Governance: audit log filtered to failed sign ins

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to failed sign ins. This is a real capture of the deployed application, role admin.

Figure 122 | SRS-02.8 | Governance: audit log filtered to failed sign ins

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: audit log filtered to failed sign ins.

Figure 123 | SRS-02.8 | Latest sign in audit rows

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Provider	Outcome	Reason
2026-10-11 05:29:07	admin	success	admin.read.workflow_runs
2026-10-11 05:29:07	admin	success	admin.read.developers
2026-10-11 05:29:07	admin	success	admin.summary
2026-10-11 05:29:07	admin	success	admin.read.workflow_definitions
2026-10-11 05:29:01	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:28:59	credentials	success	local-password
2026-10-11 05:28:58	local	mfa_required	
2026-10-11 05:25:15	admin	success	admin.summary
2026-10-11 05:25:14	admin	success	admin.read.developers
2026-10-11 05:25:14	admin	success	admin.read.workflow_runs
2026-10-11 05:25:14	admin	success	admin.read.workflow_definitions
2026-10-11 05:25:13	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:25:11	credentials	success	local-password
2026-10-11 05:25:11	local	mfa_required	
2026-10-11 05:24:18	admin	success	admin.read.developers
2026-10-11 05:24:18	admin	success	admin.summary
2026-10-11 05:24:18	admin	success	admin.read.workflow_definitions
2026-10-11 05:24:18	admin	success	admin.read.workflow_runs
2026-10-11 05:24:12	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:24:10	credentials	success	local-password
2026-10-11 05:24:10	local	mfa_required	
2026-10-11 05:23:40	admin	success	admin.read.workflow_definitions
2026-10-11 05:23:40	admin	success	admin.read.workflow_runs
2026-10-11 05:23:40	admin	success	admin.read.developers
2026-10-11 05:23:38	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:23:36	credentials	success	local-password
2026-10-11 05:23:36	local	mfa_required	
2026-10-11 05:22:46	admin	success	admin.read.workflow_runs
2026-10-11 05:22:45	admin	success	admin.read.workflow_definitions
2026-10-11 05:22:10	admin	success	admin.read.developers

MODULE 2: Identity & Authentication | SRS SECTION 8.16

SRS-02.9

COMPLETE

Unauthorized access attempts are denied and logged

WHAT THE SRS REQUIRES

Unauthorized access attempts are denied and logged. This is acceptance criterion 9 of module 2 (Identity & Authentication) in SRS section 8.16.

HOW THE PLATFORM MEETS IT

A denied request is refused and recorded. The audit search can be filtered to denied access attempts, as shown.

Status note from the SRS checklist: auditDenials wraps every privileged procedure and logs FORBIDDEN as a blocked row. UNAUTHORIZED is deliberately not logged (expired tabs would flood an append only table).

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: audit log filtered to denied access attempts (signed in as admin, page /admin/governance)
A client who opens the admin address is sent to their own portal (signed in as client, page /client-portal)
A developer who opens the admin address is refused (signed in as developer, page /developer-workspace)
A wrong password gives one generic message (no sign in needed, page /login)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (admin, client, developer, public).
Automated tests: 75 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (75 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/auditCoverage.test.ts	14
server/rbac.authOrigin.test.ts	23

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] Discovery Call outcomes and task comments will not comment on a task nobody holds
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects role=developer

Every passing test name is listed in Appendix B.

Figure 124 | SRS-02.9 | Governance: audit log filtered to denied access attempts

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to denied access attempts. This is a real capture of the deployed application, role admin.

Figure 125 | SRS-02.9 | Governance: audit log filtered to denied access attempts

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: audit log filtered to denied access attempts.

Figure 126 | SRS-02.9 | A client who opens the admin address is sent to their own portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



A client who opens the admin address is sent to their own portal. This is a real capture of the deployed application, role client.

Figure 127 | SRS-02.9 | A developer who opens the admin address is refused

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC



A developer who opens the admin address is refused. This is a real capture of the deployed application, role developer.

Figure 128 | SRS-02.9 | A wrong password gives one generic message

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC



A wrong password gives one generic message. This is a real capture of the deployed application, role public.

Figure 129 | SRS-02.9 | A wrong password gives one generic message

Live app, role: public, page: /login, captured 2026-10-10 22:10 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A wrong password gives one generic message.

MODULE 3 | SRS SECTION 9.11

AI Scan Platform

The AI Scan turns a questionnaire into a scored readiness report. A generated report is never shown to the customer until a named expert has reviewed and approved it, and every status change is written to an append only history.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-03.1	Customers can successfully purchase an AI Scan	Complete
SRS-03.2	Accounts are created and activated correctly	Complete
SRS-03.3	Questionnaires can be completed and resumed	Complete
SRS-03.4	AI analysis is generated successfully	Complete
SRS-03.5	Expert review is mandatory before publication	Complete
SRS-03.6	Reports are published only after approval	Complete
SRS-03.7	Published reports are accessible through the Client Portal	Complete
SRS-03.8	All workflow stages are recorded in the audit log	Complete
SRS-03.9	Notifications are delivered at each defined milestone	Complete

9 of 9 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.1

COMPLETE

Customers can successfully purchase an AI Scan

WHAT THE SRS REQUIRES

Customers can successfully purchase an AI Scan. This is acceptance criterion 1 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

All three AI Scan tiers are sold at the prices published on the page (795, 1,595 and 3,295 EUR excluding VAT) through Stripe Checkout. The amount and currency Stripe reports are compared with the order before anything is granted, and currency conversion is switched off so they always match.

Status note from the SRS checklist: Verified live: all three tiers are sold at the published prices (795, 1,595 and 3,295 EUR excluding VAT) through Stripe Checkout, with the paid amount and currency checked against the order.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scan (no sign in needed, page /ai-scan)
The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT (no sign in needed, page checkout.stripe.com (hosted page))
Database evidence is also included: scanPurchases.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public).
Automated tests: 35 passing in 2 test files, none failing.
Database and live site evidence printed in this report: paid purchase records.
Result: verified.

AUTOMATED TESTS (35 PASSING)

Test file	Passing
server/aiScans.test.ts	24
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] aiScansRouter.submitLead persists a free-tier lead with source=ai-scan and interest=ai-scan:free
[pass] aiScansRouter.submitLead propagates a meaningful error when the lead cannot be persisted
[pass] aiScansRouter.submitQuestionnaire persists scan + lead, runs scoring engine inline for free tier, returns reportToken
[pass] verifyStripeSignature accepts a correct, fresh signature

Every passing test name is listed in Appendix B.

Figure 130 | SRS-03.1 | AI Scan

Live app, role: public, page: /ai-scan, captured 2026-10-10 22:08 UTC



AI Scan. This is a real capture of the deployed application, role public.

Figure 131 | SRS-03.1 | The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT

Live app, role: public, page: checkout.stripe.com (hosted page), captured 2026-10-10 22:22 UTC



The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT. This is a real capture of the deployed application, role public.

Figure 132 | SRS-03.1 | Paid AI Scan purchases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Purchase	Tier	Status	Amount	Lead	Organization	Paid (UTC)
9	growth	paid	1595.00 EUR	101	258	2026-10-10 16:37:48

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.2

COMPLETE

Accounts are created and activated correctly

WHAT THE SRS REQUIRES

Accounts are created and activated correctly. This is acceptance criterion 2 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

After a verified payment the organization is created and an invitation is sent. The customer sets a password through the activation page and is routed to the Client Portal. A redelivered payment event does not create a second account.

Status note from the SRS checklist: Verified live: the account invitation and the organization are created only after verified payment; a redelivered event changes nothing.

WHERE TO SEE IT IN THE LIVE APPLICATION

An invalid activation link gives one generic message (no sign in needed, page /activate)
Activation page for a valid invitation (no sign in needed, page /activate)
A weak password is refused with a reason (no sign in needed, page /activate)
Activation signs the new user in and routes them to the client portal (signed in as client, page /client-portal)
Database evidence is also included: scanPurchases.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (public, client).
Automated tests: 28 passing in 2 test files, none failing.
Database and live site evidence printed in this report: paid purchase records.
Result: verified.

AUTOMATED TESTS (28 PASSING)

Test file	Passing
server/accounts.test.ts	17
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] accounts.activationDetails returns the email, role, MFA requirement and live agreements for a valid link
[pass] accounts.activate rejects a link that went stale between the check and the create, with the generic message
[pass] adminOps.inviteUser refuses an address that already has an account
[pass] processStripeEvent: invoices does not mark paid when the amount differs from the invoice

Every passing test name is listed in Appendix B.

Figure 133 | SRS-03.2 | An invalid activation link gives one generic message

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



An invalid activation link gives one generic message. This is a real capture of the deployed application, role public.

Figure 134 | SRS-03.2 | Activation page for a valid invitation

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



Activation page for a valid invitation. This is a real capture of the deployed application, role public.

Figure 135 | SRS-03.2 | A weak password is refused with a reason

Live app, role: public, page: /activate, captured 2026-10-10 22:10 UTC



A weak password is refused with a reason. This is a real capture of the deployed application, role public.

Figure 136 | SRS-03.2 | Activation signs the new user in and routes them to the client portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:10 UTC



Activation signs the new user in and routes them to the client portal. This is a real capture of the deployed application, role client.

Figure 137 | SRS-03.2 | Paid AI Scan purchases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Purchase	Tier	Status	Amount	Lead	Organization	Paid (UTC)
9	growth	paid	1595.00 EUR	101	258	2026-10-10 16:37:48

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.3

COMPLETE

Questionnaires can be completed and resumed

WHAT THE SRS REQUIRES

Questionnaires can be completed and resumed. This is acceptance criterion 3 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

The questionnaire is completed step by step. Save and continue later produces a link that works for 14 days, and opening it in a fresh browser restores the saved progress.

Status note from the SRS checklist: Save and continue later on the questionnaire: a 14 day link restores answers and step on any device; the draft is deleted on submission and purged when expired.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scan questionnaire, first question (no sign in needed, page /ai-scan/start)
Save and continue later gives a link that works for 14 days (no sign in needed, page /ai-scan/start)
Opening the link in a fresh browser restores the saved progress (no sign in needed, page /ai-scan/start)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (public).
Automated tests: 89 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (89 PASSING)

Test file	Passing
server/aiScanModel.test.ts	4
server/aiScans.test.ts	24
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] AI Scan model contract declares exactly the five marketed dimensions
[pass] aiScansRouter.submitQuestionnaire rejects unknown question ids to prevent payload pollution
[pass] scheduling steps daily and weekly
[pass] questionnaire drafts expires after the retention window

Every passing test name is listed in Appendix B.

Figure 138 | SRS-03.3 | AI Scan questionnaire, first question

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC



AI Scan questionnaire, first question. This is a real capture of the deployed application, role public.

Figure 139 | SRS-03.3 | AI Scan questionnaire, first question

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI Scan questionnaire, first question.

Figure 140 | SRS-03.3 | Save and continue later gives a link that works for 14 days

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC



Save and continue later gives a link that works for 14 days. This is a real capture of the deployed application, role public.

Figure 141 | SRS-03.3 | Save and continue later gives a link that works for 14 days

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Save and continue later gives a link that works for 14 days.

Figure 142 | SRS-03.3 | Opening the link in a fresh browser restores the saved progress

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC



Opening the link in a fresh browser restores the saved progress. This is a real capture of the deployed application, role public.

Figure 143 | SRS-03.3 | Opening the link in a fresh browser restores the saved progress

Live app, role: public, page: /ai-scan/start, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Opening the link in a fresh browser restores the saved progress.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.4

COMPLETE

AI analysis is generated successfully

WHAT THE SRS REQUIRES

AI analysis is generated successfully. This is acceptance criterion 4 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

The analysis path is complete: agent gate, managed prompt, model routed by task complexity, strict result validation, expert review before publication. The OpenAI key is configured and accepted by the provider. The account had no credit at the time of capture, so the first live analysis is run by the client with his own credit.

Status note from the SRS checklist: Code complete and tested. The OpenAI key is set and accepted. The client runs the first live analysis himself once the account has credit.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
Governance: connected providers and their configured state (signed in as admin, page /admin/governance)
Published report visible to the customer (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin, public).
Automated tests: 23 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (23 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6
server/aiScanScoring.test.ts	7
server/llm.test.ts	10

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] managed prompt in the scoring call falls back to the built in text for an empty managed prompt
[pass] scoreAiScan returns ok=false (not throw) on LLM transport failure
[pass] invokeLLM (Milestone 2 §2.2) sends the configured model/url/key and defaults max_tokens

Every passing test name is listed in Appendix B.

Figure 144 | SRS-03.4 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 145 | SRS-03.4 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: AI agents, prompts and execution history.

Figure 146 | SRS-03.4 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

Figure 147 | SRS-03.4 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: connected providers and their configured state.

Figure 148 | SRS-03.4 | Published report visible to the customer

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report visible to the customer. This is a real capture of the deployed application, role public.

Figure 149 | SRS-03.4 | Published report visible to the customer

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Published report visible to the customer.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.5

COMPLETE

Expert review is mandatory before publication

WHAT THE SRS REQUIRES

Expert review is mandatory before publication. This is acceptance criterion 5 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

A generated report enters an awaiting expert review status. It cannot be published without an explicit expert decision, and the customer sees only the holding message until then.

Status note from the SRS checklist: Nine status model (SRS 9.6) with the engine able only to reach Awaiting Expert Review; approve, revision, publish and archive are human steps. Verified against the live database.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI Scan review queue (signed in as admin, page /admin/governance)
Generated report held back: awaiting expert review (no sign in needed, page /ai-scan/result/demo1d353fa305fca81a1181b9c800000000000000000000)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, public).
Automated tests: 107 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (107 PASSING)

Test file	Passing
server/admin.retriggerAiScan.test.ts	8
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.retriggerAiScan rejects non-admin callers
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] time registration rejects the future, the distant past, bad minutes and bad dates
[pass] AI Scan report lifecycle (SRS 9.6) treats archived as terminal and publication as one way

Every passing test name is listed in Appendix B.

Figure 150 | SRS-03.5 | Governance: AI Scan review queue

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI Scan review queue. This is a real capture of the deployed application, role admin.

Figure 151 | SRS-03.5 | Governance: AI Scan review queue

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: AI Scan review queue.

Figure 152 | SRS-03.5 | Generated report held back: awaiting expert review

Live app, role: public, page: /ai-scan/result/demo1d353fa305fca81a1181b9c800000000000000000000, captured 2026-10-10 22:17 UTC



Generated report held back: awaiting expert review. This is a real capture of the deployed application, role public.

Figure 153 | SRS-03.5 | Generated report held back: awaiting expert review

Live app, role: public, page: /ai-scan/result/demo1d353fa305fca81a1181b9c800000000000000000000, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Generated report held back: awaiting expert review.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.6

COMPLETE

Reports are published only after approval

WHAT THE SRS REQUIRES

Reports are published only after approval. This is acceptance criterion 6 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

A report that is held back or sent for revision stays hidden. Only a published report is visible to the customer.

Status note from the SRS checklist: Publish requires Approved. The public report and PDF stay hidden until Published (BR-016); existing ready scans were backfilled as Published.

WHERE TO SEE IT IN THE LIVE APPLICATION

Generated report held back: awaiting expert review (no sign in needed, page /ai-scan/result/demo1d353fa305fca81a1181b9c80000000000000000000)
Report sent back for revision stays hidden (no sign in needed, page /ai-scan/result/demo8571de65585c381a1181ba19a0000000000000000000)
Published report visible to the customer (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (public).
Automated tests: 110 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (110 PASSING)

Test file	Passing
server/admin.reportsProjects.test.ts	11
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.createReport / admin.updateReport rejects non-admin callers
[pass] AI governance audits a blocked agent action as a failure
[pass] time registration accepts today and a recent day
[pass] AI Scan report lifecycle (SRS 9.6) treats archived as terminal and publication as one way

Every passing test name is listed in Appendix B.

Figure 154 | SRS-03.6 | Generated report held back: awaiting expert review

Live app, role: public, page: /ai-scan/result/demo1d353fa305fca81a1181b9c800000000000000000000, captured 2026-10-10 22:17 UTC



Generated report held back: awaiting expert review. This is a real capture of the deployed application, role public.

Figure 155 | SRS-03.6 | Report sent back for revision stays hidden

Live app, role: public, page: /ai-scan/result/demo8571de65585c381a1181ba19a0000000000000000000, captured 2026-10-10 22:17 UTC



Report sent back for revision stays hidden. This is a real capture of the deployed application, role public.

Figure 156 | SRS-03.6 | Report sent back for revision stays hidden

Live app, role: public, page: /ai-scan/result/demo8571de65585c381a1181ba19a0000000000000000000, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Report sent back for revision stays hidden.

Figure 157 | SRS-03.6 | Published report visible to the customer

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report visible to the customer. This is a real capture of the deployed application, role public.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.7

COMPLETE

Published reports are accessible through the Client Portal

WHAT THE SRS REQUIRES

Published reports are accessible through the Client Portal. This is acceptance criterion 7 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

Once published, the report shows its dimensions, opportunities, roadmap and disclaimers and appears in the Client Portal under reports and AI Scan history.

WHERE TO SEE IT IN THE LIVE APPLICATION

Published report visible to the customer (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)
Published report, dimensions and opportunities (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)
Published report, roadmap and disclaimers (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)
Published reports (signed in as client, page /client-portal/reports)
AI Scan history with the review progress card (signed in as client, page /client-portal/ai-scans)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (public, client).
Automated tests: 44 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/aiScanReportPdf.test.ts	3
server/clientPortal.test.ts	37
server/i18n.usedKeys.test.ts	4

Examples of what the tests assert:

[pass] renderAiScanReportPdf produces a non-empty PDF buffer with a valid header for each tier
[pass] clientPortal router requestReportSignedUrl rejects when report is not in caller's org
[pass] clientPortal router requestInvoiceCheckout: rejects when invoice belongs to another tenant
[pass] clientPortal router markMessagesRead returns affected-rows count and stays tenant-scoped

Every passing test name is listed in Appendix B.

Figure 158 | SRS-03.7 | Published report visible to the customer

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report visible to the customer. This is a real capture of the deployed application, role public.

Figure 159 | SRS-03.7 | Published report, dimensions and opportunities

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report, dimensions and opportunities. This is a real capture of the deployed application, role public.

Figure 160 | SRS-03.7 | Published report, dimensions and opportunities

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Published report, dimensions and opportunities.

Figure 161 | SRS-03.7 | Published report, roadmap and disclaimers

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report, roadmap and disclaimers. This is a real capture of the deployed application, role public.

Figure 162 | SRS-03.7 | Published report, roadmap and disclaimers

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Published report, roadmap and disclaimers.

Figure 163 | SRS-03.7 | Published reports

Live app, role: client, page: /client-portal/reports, captured 2026-10-10 22:11 UTC



Published reports. This is a real capture of the deployed application, role client.

Figure 164 | SRS-03.7 | Published reports

Live app, role: client, page: /client-portal/reports, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Published reports.

Figure 165 | SRS-03.7 | AI Scan history with the review progress card

Live app, role: client, page: /client-portal/ai-scans, captured 2026-10-10 22:11 UTC



AI Scan history with the review progress card. This is a real capture of the deployed application, role client.

Figure 166 | SRS-03.7 | AI Scan history with the review progress card

Live app, role: client, page: /client-portal/ai-scans, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI Scan history with the review progress card.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.8

COMPLETE

All workflow stages are recorded in the audit log

WHAT THE SRS REQUIRES

All workflow stages are recorded in the audit log. This is acceptance criterion 8 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

Each status transition of a report is written to an append only status history, with the actor and note. The database refuses updates to those rows.

Status note from the SRS checklist: Every report status change, including the engine's, writes an append only ai_scan_status_events row with the actor.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: status history of a report (append only) (signed in as admin, page /admin/governance)
Governance: reports in every status (signed in as admin, page /admin/governance)
Database evidence is also included: scanEvents, immutability.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Database and live site evidence printed in this report: AI Scan status history; real UPDATE and DELETE attempts refused by the database.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 167 | SRS-03.8 | Governance: status history of a report (append only)

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: status history of a report (append only). This is a real capture of the deployed application, role admin.

Figure 168 | SRS-03.8 | Governance: status history of a report (append only)

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: status history of a report (append only).

Figure 169 | SRS-03.8 | Governance: reports in every status

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: reports in every status. This is a real capture of the deployed application, role admin.

Figure 170 | SRS-03.8 | Governance: reports in every status

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: reports in every status.

Figure 171 | SRS-03.8 | Latest AI Scan status transitions (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Scan	From	To	Actor	Note
2026-10-07 15:43:55	6	approved	published	1919	
2026-10-07 15:43:52	6	awaiting_expert_review	approved	1919	Reviewed against the questionnaire answers.
2026-10-07 15:43:49	5	awaiting_expert_review	revision_required	1919	Please expand the rationale for scalability readiness and cite the dock volume figures.

Figure 172 | SRS-03.8 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

MODULE 3: AI Scan Platform | SRS SECTION 9.11

SRS-03.9

COMPLETE

Notifications are delivered at each defined milestone

WHAT THE SRS REQUIRES

Notifications are delivered at each defined milestone. This is acceptance criterion 9 of module 3 (AI Scan Platform) in SRS section 9.11.

HOW THE PLATFORM MEETS IT

Milestone notifications for submission, review, publication and revision are part of the event catalogue and are delivered through the dispatcher.

Status note from the SRS checklist: Customer confirmation on submission, admin events for review, changes, approval and publication, and the customer is emailed on publication.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scan history with the review progress card (signed in as client, page /client-portal/ai-scans)
Notification bell with recent events (signed in as client, page /client-portal)
Admin notification bell (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, admin).
Automated tests: 31 passing in 3 test files, none failing.
Result: verified.

Email delivery. The platform side is complete and tested: events, preferences, templates, the branded shell, the delivery log and failure recording. Delivery to real inboxes through the IO SKY Zoho mailboxes needs the MX and sender DNS records and the sending mailbox connected, which sit on the client side and are listed in the open items.

AUTOMATED TESTS (31 PASSING)

Test file	Passing
server/clientNotifications.test.ts	3
server/notificationCatalogue.test.ts	14
server/notificationDispatcher.test.ts	14

Examples of what the tests assert:

[pass] clientPortal.notifications shows everything when the member has set no preferences
[pass] Notification Event Catalogue - structure gives every event the fields routing and delivery depend on
[pass] Notification Event Catalogue - specification invariants declares a published AI Scan event, which is the Client-facing boundary
[pass] emitNotification does not fill the admin bell twice when the caller already did

Every passing test name is listed in Appendix B.

Figure 173 | SRS-03.9 | AI Scan history with the review progress card

Live app, role: client, page: /client-portal/ai-scans, captured 2026-10-10 22:11 UTC



AI Scan history with the review progress card. This is a real capture of the deployed application, role client.

Figure 174 | SRS-03.9 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

Figure 175 | SRS-03.9 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Notification bell with recent events.

Figure 176 | SRS-03.9 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

MODULE 4 | SRS SECTION 10.17

Client Portal

The Client Portal is the customer's own view of reports, projects, documents, invoices, messages, notifications and support, scoped strictly to their organization.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-04.1	Clients are redirected to the portal after authentication	Complete
SRS-04.2	Dashboards display only authorized information	Complete
SRS-04.3	Published reports are accessible	Complete
SRS-04.4	AI Scan progress is visible	Complete
SRS-04.5	Project information is displayed correctly	Complete
SRS-04.6	Documents can be downloaded securely	Complete
SRS-04.7	Invoices are available	Complete
SRS-04.8	Messaging functions correctly	Complete
SRS-04.9	Notifications are delivered successfully	Complete
SRS-04.10	All activities are recorded in the audit log where required	Complete

10 of 10 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.1

COMPLETE

Clients are redirected to the portal after authentication

WHAT THE SRS REQUIRES

Clients are redirected to the portal after authentication. This is acceptance criterion 1 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

A client who signs in is taken to the Client Portal dashboard.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sign in (no sign in needed, page /login)
Client portal dashboard after sign in (signed in as client, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public, client).
Automated tests: 13 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (13 PASSING)

Test file	Passing
server/oauth.redirect.test.ts	5
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] OAuth callback - role-based redirect routes role=developer to /developer-workspace
[pass] OAuth callback - role-based redirect falls back to the requested returnPath for role=user
[pass] roleHome falls back to / for user role and unknown/missing values
[pass] isImpersonatingTarget is true only when impersonation is active AND targets the given role

Every passing test name is listed in Appendix B.

Figure 177 | SRS-04.1 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC



Sign in. This is a real capture of the deployed application, role public.

Figure 178 | SRS-04.1 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC



Client portal dashboard after sign in. This is a real capture of the deployed application, role client.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.2

COMPLETE

Dashboards display only authorized information

WHAT THE SRS REQUIRES

Dashboards display only authorized information. This is acceptance criterion 2 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Dashboards show only the signed in client's own organization. Every client query is scoped by organization on the server and by row level security policies in the database.

WHERE TO SEE IT IN THE LIVE APPLICATION

Client portal dashboard after sign in (signed in as client, page /client-portal)
Document search, scoped to this organization (signed in as client, page /client-portal/documents)
A client who opens the admin address is sent to their own portal (signed in as client, page /client-portal)
Database evidence is also included: policies.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client).
Automated tests: 55 passing in 2 test files, none failing.
Database and live site evidence printed in this report: row level security policies.
Result: verified.

AUTOMATED TESTS (55 PASSING)

Test file	Passing
server/clientPortal.test.ts	37
server/rls.negative.test.ts	18

Examples of what the tests assert:

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router recommendationAction rejects when rec is in another tenant
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT read client A's org invoice (cross-tenant read denied)

Every passing test name is listed in Appendix B.

Figure 179 | SRS-04.2 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC



Client portal dashboard after sign in. This is a real capture of the deployed application, role client.

Figure 180 | SRS-04.2 | Document search, scoped to this organization

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document search, scoped to this organization. This is a real capture of the deployed application, role client.

Figure 181 | SRS-04.2 | Document search, scoped to this organization

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Document search, scoped to this organization.

Figure 182 | SRS-04.2 | A client who opens the admin address is sent to their own portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



A client who opens the admin address is sent to their own portal. This is a real capture of the deployed application, role client.

Figure 183 | SRS-04.2 | Row level security policies on client facing tables

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table	Policy	Command
client_invoices	client_invoices_select_own_org_or_admin	SELECT
client_invoices	client_invoices_write_admin_only	ALL
notification_preferences	notification_preferences_admin_all	ALL
notification_preferences	notification_preferences_own	ALL
project_approvals	project_approvals_admin_all	ALL
project_approvals	project_approvals_select_own_org	SELECT
quotes	quotes_admin_all	ALL
quotes	quotes_select_own_org	SELECT
subscriptions	subscriptions_admin_all	ALL
subscriptions	subscriptions_select_own_org	SELECT

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.3

COMPLETE

Published reports are accessible

WHAT THE SRS REQUIRES

Published reports are accessible. This is acceptance criterion 3 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Published reports are listed and can be opened and downloaded as PDF.

WHERE TO SEE IT IN THE LIVE APPLICATION

Published reports (signed in as client, page /client-portal/reports)
Published report visible to the customer (no sign in needed, page /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client, public).
Automated tests: 37 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router requestReportSignedUrl rejects with PRECONDITION when pdfKey is missing
[pass] clientPortal router requestInvoiceCheckout: rejects already-paid invoices
[pass] clientPortal router requestDocumentDeletion: only the uploader can delete their file

Every passing test name is listed in Appendix B.

Figure 184 | SRS-04.3 | Published reports

Live app, role: client, page: /client-portal/reports, captured 2026-10-10 22:11 UTC



Published reports. This is a real capture of the deployed application, role client.

Figure 185 | SRS-04.3 | Published report visible to the customer

Live app, role: public, page: /ai-scan/result/demo1341f7160ab5a1a1181ba6ab00000000000000000000, captured 2026-10-10 22:18 UTC



Published report visible to the customer. This is a real capture of the deployed application, role public.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.4

COMPLETE

AI Scan progress is visible

WHAT THE SRS REQUIRES

AI Scan progress is visible. This is acceptance criterion 4 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

The AI Scan history shows a review progress card so the customer sees where a report is in the review lifecycle.

Status note from the SRS checklist: Client Portal AI Scan history shows where each scan is in the review workflow; the report link appears only once Published.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scan history with the review progress card (signed in as client, page /client-portal/ai-scans)
Published reports (signed in as client, page /client-portal/reports)
Notification bell with recent events (signed in as client, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client).
Automated tests: 98 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (98 PASSING)

Test file	Passing
server/clientPortal.test.ts	37
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router uploadDocument: surfaces a version-linking failure as BAD_REQUEST
[pass] alert firing fires at the threshold, not below
[pass] Discovery Call outcomes needs a follow up date when work is left to do

Every passing test name is listed in Appendix B.

Figure 186 | SRS-04.4 | AI Scan history with the review progress card

Live app, role: client, page: /client-portal/ai-scans, captured 2026-10-10 22:11 UTC



AI Scan history with the review progress card. This is a real capture of the deployed application, role client.

Figure 187 | SRS-04.4 | Published reports

Live app, role: client, page: /client-portal/reports, captured 2026-10-10 22:11 UTC



Published reports. This is a real capture of the deployed application, role client.

Figure 188 | SRS-04.4 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.5

COMPLETE

Project information is displayed correctly

WHAT THE SRS REQUIRES

Project information is displayed correctly. This is acceptance criterion 5 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Project progress, milestones and phases are displayed from live data.

WHERE TO SEE IT IN THE LIVE APPLICATION

Project progress and milestones (signed in as client, page /client-portal/projects)
A project phase waiting for the customer's approval (signed in as client, page /client-portal/approvals)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client).
Automated tests: 48 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (48 PASSING)

Test file	Passing
server/admin.reportsProjects.test.ts	11
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin.createReport / admin.updateReport rejects non-admin callers
[pass] clientPortal router rejects users without a client role
[pass] clientPortal router recommendationAction rejects when rec is in another tenant
[pass] clientPortal router markNotificationRead: marks a notification read and surfaces NOT_FOUND for an unknown one (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 189 | SRS-04.5 | Project progress and milestones

Live app, role: client, page: /client-portal/projects, captured 2026-10-10 22:11 UTC



Project progress and milestones. This is a real capture of the deployed application, role client.

Figure 190 | SRS-04.5 | Project progress and milestones

Live app, role: client, page: /client-portal/projects, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Project progress and milestones.

Figure 191 | SRS-04.5 | A project phase waiting for the customer's approval

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



A project phase waiting for the customer's approval. This is a real capture of the deployed application, role client.

Figure 192 | SRS-04.5 | A project phase waiting for the customer's approval

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A project phase waiting for the customer's approval.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.6

COMPLETE

Documents can be downloaded securely

WHAT THE SRS REQUIRES

Documents can be downloaded securely. This is acceptance criterion 6 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Documents are served through short lived signed URLs after an authorization check. The vault shows only the client's own documents.

Status note from the SRS checklist: Verified through the application's own storage layer on all four buckets (upload, short lived signed link, download, delete) with the production key set and deployed; downloads are audited and organization scoped.

WHERE TO SEE IT IN THE LIVE APPLICATION

Document vault (signed in as client, page /client-portal/documents)
Document search, scoped to this organization (signed in as client, page /client-portal/documents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] clientPortal router returns the organization record for the logged-in client
[pass] clientPortal router cancelStrategyCall: blocks self-cancel inside the 60-min window
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 193 | SRS-04.6 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document vault. This is a real capture of the deployed application, role client.

Figure 194 | SRS-04.6 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Document vault.

Figure 195 | SRS-04.6 | Document search, scoped to this organization

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document search, scoped to this organization. This is a real capture of the deployed application, role client.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.7

COMPLETE

Invoices are available

WHAT THE SRS REQUIRES

Invoices are available. This is acceptance criterion 7 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Invoices and billing history are listed in the portal.

WHERE TO SEE IT IN THE LIVE APPLICATION

Invoices and billing (signed in as client, page /client-portal/billing)
Invoices after a Stripe payment: one is paid, the others are open (signed in as client, page /client-portal/billing)
Client portal dashboard after sign in (signed in as client, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client).
Automated tests: 41 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (41 PASSING)

Test file	Passing
server/admin.createInvoice.test.ts	4
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin.createInvoice creates an invoice and audits it
[pass] clientPortal router sends a client message and writes a notification
[pass] clientPortal router cancelStrategyCall: rejects when booking is in another tenant
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 196 | SRS-04.7 | Invoices and billing

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:11 UTC



Invoices and billing. This is a real capture of the deployed application, role client.

Figure 197 | SRS-04.7 | Invoices and billing

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Invoices and billing.

Figure 198 | SRS-04.7 | Invoices after a Stripe payment: one is paid, the others are open

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:22 UTC



Invoices after a Stripe payment: one is paid, the others are open. This is a real capture of the deployed application, role client.

Figure 199 | SRS-04.7 | Invoices after a Stripe payment: one is paid, the others are open

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Invoices after a Stripe payment: one is paid, the others are open.

Figure 200 | SRS-04.7 | Client portal dashboard after sign in

Live app, role: client, page: /client-portal, captured 2026-10-10 22:11 UTC



Client portal dashboard after sign in. This is a real capture of the deployed application, role client.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.8

COMPLETE

Messaging functions correctly

WHAT THE SRS REQUIRES

Messaging functions correctly. This is acceptance criterion 8 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Secure messaging and support tickets work from the portal and are recorded.

Status note from the SRS checklist: Send, read receipts, history; E2E covered

WHERE TO SEE IT IN THE LIVE APPLICATION

Secure messaging (signed in as client, page /client-portal/messages)
Support tickets (signed in as client, page /client-portal/support)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client).
Automated tests: 37 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router requestReportSignedUrl rejects with PRECONDITION when pdfKey is missing
[pass] clientPortal router requestInvoiceCheckout: rejects already-paid invoices
[pass] clientPortal router requestDocumentDeletion: only the uploader can delete their file

Every passing test name is listed in Appendix B.

Figure 201 | SRS-04.8 | Secure messaging

Live app, role: client, page: /client-portal/messages, captured 2026-10-10 22:11 UTC



Secure messaging. This is a real capture of the deployed application, role client.

Figure 202 | SRS-04.8 | Secure messaging

Live app, role: client, page: /client-portal/messages, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Secure messaging.

Figure 203 | SRS-04.8 | Support tickets

Live app, role: client, page: /client-portal/support, captured 2026-10-10 22:11 UTC



Support tickets. This is a real capture of the deployed application, role client.

Figure 204 | SRS-04.8 | Support tickets

Live app, role: client, page: /client-portal/support, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Support tickets.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.9

COMPLETE

Notifications are delivered successfully

WHAT THE SRS REQUIRES

Notifications are delivered successfully. This is acceptance criterion 9 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

The notification bell lists recent events. Preferences allow opting out of a category for in app delivery, while security notices stay locked on.

Status note from the SRS checklist: Project, billing and approval events route through the dispatcher to the right audience.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification bell with recent events (signed in as client, page /client-portal)
Notification preferences, security locked on (signed in as client, page /client-portal/account)
Opting out of a category for in app delivery (signed in as client, page /client-portal/account)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client).
Automated tests: 31 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (31 PASSING)

Test file	Passing
server/clientNotifications.test.ts	3
server/notificationDispatcher.test.ts	14
client/src/components/NotificationBell.test.tsx	14

Examples of what the tests assert:

[pass] clientPortal.notifications shows everything when the member has set no preferences
[pass] emitNotification does not fill the admin bell twice when the caller already did
[pass] dispatch policy helpers maps priorities and families
[pass] RM-99: dropdown behaviour opens on click and lists the notifications

Every passing test name is listed in Appendix B.

Figure 205 | SRS-04.9 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

Figure 206 | SRS-04.9 | Notification preferences, security locked on

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:12 UTC



Notification preferences, security locked on. This is a real capture of the deployed application, role client.

Figure 207 | SRS-04.9 | Notification preferences, security locked on

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Notification preferences, security locked on.

Figure 208 | SRS-04.9 | Opting out of a category for in app delivery

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:19 UTC



Opting out of a category for in app delivery. This is a real capture of the deployed application, role client.

Figure 209 | SRS-04.9 | Opting out of a category for in app delivery

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:19 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Opting out of a category for in app delivery.

MODULE 4: Client Portal | SRS SECTION 10.17

SRS-04.10

COMPLETE

All activities are recorded in the audit log where required

WHAT THE SRS REQUIRES

All activities are recorded in the audit log where required. This is acceptance criterion 10 of module 4 (Client Portal) in SRS section 10.17.

HOW THE PLATFORM MEETS IT

Client mutations such as sending a message, opening a ticket and deciding an approval are written to the audit log by middleware, and a test enumerates the covered procedures.

Status note from the SRS checklist: Client portal messages, tickets and approval decisions are recorded centrally; document actions audit in their handlers.

WHERE TO SEE IT IN THE LIVE APPLICATION

Requesting changes requires saying what to change (signed in as client, page /client-portal/approvals)
After the customer approves, the decision is recorded (signed in as client, page /client-portal/approvals)
Audit logs (signed in as admin, page /admin/audit)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, admin).
Automated tests: 51 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (51 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] mutation audit middleware records a successful listed mutation with the caller and the path
[pass] clientPortal router recommendationAction proposal: flips status to in_progress, audits, notifies owner
[pass] clientPortal router uploadDocument: persists, audits, notifies

Every passing test name is listed in Appendix B.

Figure 210 | SRS-04.10 | Requesting changes requires saying what to change

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



Requesting changes requires saying what to change. This is a real capture of the deployed application, role client.

Figure 211 | SRS-04.10 | Requesting changes requires saying what to change

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Requesting changes requires saying what to change.

Figure 212 | SRS-04.10 | After the customer approves, the decision is recorded

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



After the customer approves, the decision is recorded. This is a real capture of the deployed application, role client.

Figure 213 | SRS-04.10 | After the customer approves, the decision is recorded

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. After the customer approves, the decision is recorded.

Figure 214 | SRS-04.10 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

MODULE 5 | SRS SECTION 11.15

Developer Portal

The Developer Portal gives engineers only the projects they are assigned to: tasks, time registration, deliverable submission, internal messaging and a scoped, expiring access grant.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-05.1	Developers are redirected to the Developer Portal after authentication	Complete
SRS-05.2	Only assigned projects are visible	Complete
SRS-05.3	Task management functions correctly	Complete
SRS-05.4	Deliverables can be uploaded securely	Complete
SRS-05.5	Time registration operates correctly	Complete
SRS-05.6	Internal messaging functions as specified	Complete
SRS-05.7	Notifications are delivered successfully	Complete
SRS-05.8	All business critical actions are recorded in the audit log	Complete

8 of 8 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.1

COMPLETE

Developers are redirected to the Developer Portal after authentication

WHAT THE SRS REQUIRES

Developers are redirected to the Developer Portal after authentication. This is acceptance criterion 1 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

A developer who signs in is taken to the Developer Workspace.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sign in (no sign in needed, page /login)
Developer workspace after sign in (signed in as developer, page /developer-workspace)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public, developer).
Automated tests: 41 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (41 PASSING)

Test file	Passing
server/developer.test.ts	33
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - task + submission updates status and notifies admin when caller owns the task
[pass] developer router - support tickets opens a ticket, audits, and notifies the engineering desk
[pass] developer router - Step 2: editable profile + security setMfaMethodLite allows 'none' when mfaRequired=0 and notifies the admin

Every passing test name is listed in Appendix B.

Figure 215 | SRS-05.1 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC



Sign in. This is a real capture of the deployed application, role public.

Figure 216 | SRS-05.1 | Developer workspace after sign in

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:12 UTC



Developer workspace after sign in. This is a real capture of the deployed application, role developer.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.2

COMPLETE

Only assigned projects are visible

WHAT THE SRS REQUIRES

Only assigned projects are visible. This is acceptance criterion 2 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

A developer sees only the projects they are assigned to, and the access scope shows what was granted and when it expires.

WHERE TO SEE IT IN THE LIVE APPLICATION

Only the projects assigned to this developer (signed in as developer, page /developer-workspace/projects)
Access scope and expiry (signed in as developer, page /developer-workspace/access-scope)
A developer cannot open the client portal (signed in as developer, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (developer).
Automated tests: 39 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (39 PASSING)

Test file	Passing
server/admin.grantDeveloperAccess.test.ts	6
server/developer.test.ts	33

Examples of what the tests assert:

[pass] admin.grantDeveloperAccess rejects non-admin callers
[pass] developer router - gating blocks dashboard when agreements gate fails
[pass] developer router - task + submission creates a submission, audits, and notifies admin
[pass] developer router - access extension rejects extension reasons that are too short

Every passing test name is listed in Appendix B.

Figure 217 | SRS-05.2 | Only the projects assigned to this developer

Live app, role: developer, page: /developer-workspace/projects, captured 2026-10-10 22:12 UTC



Only the projects assigned to this developer. This is a real capture of the deployed application, role developer.

Figure 218 | SRS-05.2 | Only the projects assigned to this developer

Live app, role: developer, page: /developer-workspace/projects, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Only the projects assigned to this developer.

Figure 219 | SRS-05.2 | Access scope and expiry

Live app, role: developer, page: /developer-workspace/access-scope, captured 2026-10-10 22:13 UTC



Access scope and expiry. This is a real capture of the deployed application, role developer.

Figure 220 | SRS-05.2 | Access scope and expiry

Live app, role: developer, page: /developer-workspace/access-scope, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Access scope and expiry.

Figure 221 | SRS-05.2 | A developer cannot open the client portal

Live app, role: developer, page: /client-portal, captured 2026-10-10 22:13 UTC



A developer cannot open the client portal. This is a real capture of the deployed application, role developer.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.3

COMPLETE

Task management functions correctly

WHAT THE SRS REQUIRES

Task management functions correctly. This is acceptance criterion 3 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

Tasks can be listed, updated and discussed. A progress note or a clarification request goes to the engineering desk and the answer comes back on the same thread.

Status note from the SRS checklist: Status, plus progress notes, comments and clarification requests on tasks a developer holds; a clarification request reaches the admin bell; admins can answer.

WHERE TO SEE IT IN THE LIVE APPLICATION

Personal task list (signed in as developer, page /developer-workspace/tasks)
Progress note, clarification request and the answer on a task (signed in as developer, page /developer-workspace/tasks)
Asking for clarification from the task thread (signed in as developer, page /developer-workspace/tasks)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (developer).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/developer.test.ts	33

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - task + submission blocks submission for an unassigned project
[pass] developer router - access extension creates an access request, audits, and notifies admin

Every passing test name is listed in Appendix B.

Figure 222 | SRS-05.3 | Personal task list

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:12 UTC



Personal task list. This is a real capture of the deployed application, role developer.

Figure 223 | SRS-05.3 | Personal task list

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Personal task list.

Figure 224 | SRS-05.3 | Progress note, clarification request and the answer on a task

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:19 UTC



Progress note, clarification request and the answer on a task. This is a real capture of the deployed application, role developer.

Figure 225 | SRS-05.3 | Progress note, clarification request and the answer on a task

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:19 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Progress note, clarification request and the answer on a task.

Figure 226 | SRS-05.3 | Asking for clarification from the task thread

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:19 UTC



Asking for clarification from the task thread. This is a real capture of the deployed application, role developer.

Figure 227 | SRS-05.3 | Asking for clarification from the task thread

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:19 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Asking for clarification from the task thread.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.4

COMPLETE

Deliverables can be uploaded securely

WHAT THE SRS REQUIRES

Deliverables can be uploaded securely. This is acceptance criterion 4 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

Deliverables are uploaded to private storage with type and size checks and listed with their review state.

Status note from the SRS checklist: Same verified storage path, developer-workspace bucket.

WHERE TO SEE IT IN THE LIVE APPLICATION

Deliverable submissions (signed in as developer, page /developer-workspace/submissions)
Project files (signed in as developer, page /developer-workspace/files)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (developer).
Automated tests: 41 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (41 PASSING)

Test file	Passing
server/developer.test.ts	33
server/profileAvatar.test.ts	8

Examples of what the tests assert:

[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - task + submission updates status and notifies admin when caller owns the task
[pass] developer router - support tickets opens a ticket, audits, and notifies the engineering desk
[pass] developer router - Step 2: editable profile + security setMfaMethodLite allows 'none' when mfaRequired=0 and notifies the admin

Every passing test name is listed in Appendix B.

Figure 228 | SRS-05.4 | Deliverable submissions

Live app, role: developer, page: /developer-workspace/submissions, captured 2026-10-10 22:13 UTC



Deliverable submissions. This is a real capture of the deployed application, role developer.

Figure 229 | SRS-05.4 | Deliverable submissions

Live app, role: developer, page: /developer-workspace/submissions, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Deliverable submissions.

Figure 230 | SRS-05.4 | Project files

Live app, role: developer, page: /developer-workspace/files, captured 2026-10-10 22:13 UTC



Project files. This is a real capture of the deployed application, role developer.

Figure 231 | SRS-05.4 | Project files

Live app, role: developer, page: /developer-workspace/files, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Project files.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.5

COMPLETE

Time registration operates correctly

WHAT THE SRS REQUIRES

Time registration operates correctly. This is acceptance criterion 5 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

Time is registered against an assigned project. A future date is refused, and every entry carries a review status.

Status note from the SRS checklist: Developer Time page, assignment checked in the insert transaction, 31 day backdate limit, admin review with reason on reject.

WHERE TO SEE IT IN THE LIVE APPLICATION

Time registration with review status (signed in as developer, page /developer-workspace/time)
Logging time against an assigned project (signed in as developer, page /developer-workspace/time)
A future date cannot be registered (signed in as developer, page /developer-workspace/time)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (developer).
Automated tests: 72 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (72 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] notification preferences defaults to delivering
[pass] CSV export defuses spreadsheet formulas
[pass] compliance evaluation names the count in the detail so the figure can be checked

Every passing test name is listed in Appendix B.

Figure 232 | SRS-05.5 | Time registration with review status

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:12 UTC



Time registration with review status. This is a real capture of the deployed application, role developer.

Figure 233 | SRS-05.5 | Time registration with review status

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:12 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Time registration with review status.

Figure 234 | SRS-05.5 | Logging time against an assigned project

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:13 UTC



Logging time against an assigned project. This is a real capture of the deployed application, role developer.

Figure 235 | SRS-05.5 | Logging time against an assigned project

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Logging time against an assigned project.

Figure 236 | SRS-05.5 | A future date cannot be registered

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:13 UTC



A future date cannot be registered. This is a real capture of the deployed application, role developer.

Figure 237 | SRS-05.5 | A future date cannot be registered

Live app, role: developer, page: /developer-workspace/time, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A future date cannot be registered.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.6

COMPLETE

Internal messaging functions as specified

WHAT THE SRS REQUIRES

Internal messaging functions as specified. This is acceptance criterion 6 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

The engineering desk can message a developer and the developer sees it in the workspace.

Status note from the SRS checklist: Admin Delivery screen sends to a developer; developer is notified.

WHERE TO SEE IT IN THE LIVE APPLICATION

Messages from the engineering desk (signed in as developer, page /developer-workspace/messages)
Delivery: message a developer (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (developer, admin).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/developer.test.ts	33

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - task + submission blocks submission for an unassigned project
[pass] developer router - access extension creates an access request, audits, and notifies admin

Every passing test name is listed in Appendix B.

Figure 238 | SRS-05.6 | Messages from the engineering desk

Live app, role: developer, page: /developer-workspace/messages, captured 2026-10-10 22:13 UTC



Messages from the engineering desk. This is a real capture of the deployed application, role developer.

Figure 239 | SRS-05.6 | Messages from the engineering desk

Live app, role: developer, page: /developer-workspace/messages, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Messages from the engineering desk.

Figure 240 | SRS-05.6 | Delivery: message a developer

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: message a developer. This is a real capture of the deployed application, role admin.

Figure 241 | SRS-05.6 | Delivery: message a developer

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: message a developer.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.7

COMPLETE

Notifications are delivered successfully

WHAT THE SRS REQUIRES

Notifications are delivered successfully. This is acceptance criterion 7 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

Assignment and task events reach the developer's notification bell. Security notices stay on regardless of preferences.

Status note from the SRS checklist: Project, billing and approval events route through the dispatcher to the right audience.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification bell with assignment and task events (signed in as developer, page /developer-workspace)
Notification preferences with security locked on (signed in as developer, page /developer-workspace/profile)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (developer).
Automated tests: 61 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (61 PASSING)

Test file	Passing
server/developer.test.ts	33
server/notificationDispatcher.test.ts	14
client/src/components/NotificationBell.test.tsx	14

Examples of what the tests assert:

[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - messages + agreements marks admin messages as read
[pass] developer router - Step 2: editable profile + security setMfaMethodLite allows 'none' when mfaRequired=0 and notifies the admin
[pass] dispatch policy helpers builds a bounded dedupe key

Every passing test name is listed in Appendix B.

Figure 242 | SRS-05.7 | Notification bell with assignment and task events

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC



Notification bell with assignment and task events. This is a real capture of the deployed application, role developer.

Figure 243 | SRS-05.7 | Notification bell with assignment and task events

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Notification bell with assignment and task events.

Figure 244 | SRS-05.7 | Notification preferences with security locked on

Live app, role: developer, page: /developer-workspace/profile, captured 2026-10-10 22:13 UTC



Notification preferences with security locked on. This is a real capture of the deployed application, role developer.

Figure 245 | SRS-05.7 | Notification preferences with security locked on

Live app, role: developer, page: /developer-workspace/profile, captured 2026-10-10 22:13 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Notification preferences with security locked on.

MODULE 5: Developer Portal | SRS SECTION 11.15

SRS-05.8

COMPLETE

All business critical actions are recorded in the audit log

WHAT THE SRS REQUIRES

All business critical actions are recorded in the audit log. This is acceptance criterion 8 of module 5 (Developer Portal) in SRS section 11.15.

HOW THE PLATFORM MEETS IT

Business critical developer actions are audit logged by the mutation audit middleware.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Delivery: time entries awaiting review (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 25 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (25 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin developer delivery rejects a lower case project code
[pass] audit coverage adminOps: every mutation audits itself or is on the central list
[pass] audit coverage profile: every mutation audits itself or is on the central list

Every passing test name is listed in Appendix B.

Figure 246 | SRS-05.8 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 247 | SRS-05.8 | Delivery: time entries awaiting review

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: time entries awaiting review. This is a real capture of the deployed application, role admin.

Figure 248 | SRS-05.8 | Delivery: time entries awaiting review

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: time entries awaiting review.

MODULE 6 | SRS SECTION 12.17

Admin Portal

The Admin Portal is the operating desk: customers, AI Scans and their review, reports, projects, developer assignment, billing and notifications, all behind multi factor authentication.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-06.1	Admins are redirected to the Admin Portal after authentication	Complete
SRS-06.2	Customer management functions correctly	Complete
SRS-06.3	AI Scans can be reviewed	Complete
SRS-06.4	Reports require explicit approval before publication	Complete
SRS-06.5	Projects can be managed successfully	Complete
SRS-06.6	Developers can be assigned to projects	Complete
SRS-06.7	Billing information is available	Complete
SRS-06.8	Operational dashboards display accurate information	Complete
SRS-06.9	Notifications function correctly	Complete
SRS-06.10	All required audit events are recorded	Complete

10 of 10 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.1

COMPLETE

Admins are redirected to the Admin Portal after authentication

WHAT THE SRS REQUIRES

Admins are redirected to the Admin Portal after authentication. This is acceptance criterion 1 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

An administrator is routed to the Admin Portal after the multi factor challenge.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sign in (no sign in needed, page /login)
Admin portal after sign in and the MFA challenge (signed in as admin, page /admin/bookings)
Executive overview, top (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (public, admin).
Automated tests: 73 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (73 PASSING)

Test file	Passing
server/admin.modules.test.ts	65
client/src/_core/hooks/useRouteGuard.test.ts	8

Examples of what the tests assert:

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.documents forbids unauthenticated
[pass] admin module RBAC admin.analytics forbids unauthenticated
[pass] admin.action audited stub forbids unauthenticated callers

Every passing test name is listed in Appendix B.

Figure 249 | SRS-06.1 | Sign in

Live app, role: public, page: /login, captured 2026-10-10 22:09 UTC



Sign in. This is a real capture of the deployed application, role public.

Figure 250 | SRS-06.1 | Admin portal after sign in and the MFA challenge

Live app, role: admin, page: /admin/bookings, captured 2026-10-10 22:14 UTC



Admin portal after sign in and the MFA challenge. This is a real capture of the deployed application, role admin.

Figure 251 | SRS-06.1 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 252 | SRS-06.1 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. Executive overview, top.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.2

COMPLETE

Customer management functions correctly

WHAT THE SRS REQUIRES

Customer management functions correctly. This is acceptance criterion 2 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Customer organizations and their records are managed from the Clients and CRM modules.

Status note from the SRS checklist: createOrganization, updateOrganization, clients

WHERE TO SEE IT IN THE LIVE APPLICATION

Clients (signed in as admin, page /admin/clients)
CRM and leads (signed in as admin, page /admin/crm)
Users and permissions (signed in as admin, page /admin/users)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 86 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (86 PASSING)

Test file	Passing
server/admin.createLead.test.ts	4
server/admin.modules.test.ts	65
server/admin.superAdmin.test.ts	17

Examples of what the tests assert:

[pass] admin.createLead creates a lead with source: manual and audits it
[pass] admin module RBAC admin.billing allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.analytics allows role="admin" and writes the read audit row
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) blocks admin/super_admin with no verified MFA factor from every admin.* endpoint

Every passing test name is listed in Appendix B.

Figure 253 | SRS-06.2 | Clients

Live app, role: admin, page: /admin/clients, captured 2026-10-10 22:14 UTC



Clients. This is a real capture of the deployed application, role admin.

Figure 254 | SRS-06.2 | Clients

Live app, role: admin, page: /admin/clients, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Clients.

Figure 255 | SRS-06.2 | CRM and leads

Live app, role: admin, page: /admin/crm, captured 2026-10-10 22:14 UTC



CRM and leads. This is a real capture of the deployed application, role admin.

Figure 256 | SRS-06.2 | CRM and leads

Live app, role: admin, page: /admin/crm, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. CRM and leads.

Figure 257 | SRS-06.2 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

Figure 258 | SRS-06.2 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Users and permissions.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.3

COMPLETE

AI Scans can be reviewed

WHAT THE SRS REQUIRES

AI Scans can be reviewed. This is acceptance criterion 3 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Administrators open any AI Scan, read its answers and score, and move it through the review queue.

Status note from the SRS checklist: Review queue: take, approve, request revision with a note, regenerate, publish, archive, with history.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI Scans (signed in as admin, page /admin/ai-scans)
Governance: AI Scan review queue (signed in as admin, page /admin/governance)
Governance: reports in every status (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 46 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (46 PASSING)

Test file	Passing
server/admin.retriggerAiScan.test.ts	8
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] admin.retriggerAiScan rejects non-admin callers
[pass] denied access is recorded (SRS 8.16) writes one blocked audit row when a signed in user is refused
[pass] time review tells the developer about the decision
[pass] audit export, search and health refuses a one character document search

Every passing test name is listed in Appendix B.

Figure 259 | SRS-06.3 | AI Scans

Live app, role: admin, page: /admin/ai-scans, captured 2026-10-10 22:14 UTC



AI Scans. This is a real capture of the deployed application, role admin.

Figure 260 | SRS-06.3 | AI Scans

Live app, role: admin, page: /admin/ai-scans, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI Scans.

Figure 261 | SRS-06.3 | Governance: AI Scan review queue

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI Scan review queue. This is a real capture of the deployed application, role admin.

Figure 262 | SRS-06.3 | Governance: reports in every status

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: reports in every status. This is a real capture of the deployed application, role admin.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.4

COMPLETE

Reports require explicit approval before publication

WHAT THE SRS REQUIRES

Reports require explicit approval before publication. This is acceptance criterion 4 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Publication is a distinct, explicit action performed by a reviewer and recorded in the status history.

Status note from the SRS checklist: Approval is a first class state with the approver and time recorded separately from the publisher.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI Scan review queue (signed in as admin, page /admin/governance)
Governance: status history of a report (append only) (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 49 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (49 PASSING)

Test file	Passing
server/admin.reportsProjects.test.ts	11
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] admin.createReport / admin.updateReport rejects non-admin callers
[pass] authority boundaries reserves AI governance for the super admin
[pass] time review demands a reason to reject
[pass] audit export, search and health refuses a one character document search

Every passing test name is listed in Appendix B.

Figure 263 | SRS-06.4 | Governance: AI Scan review queue

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI Scan review queue. This is a real capture of the deployed application, role admin.

Figure 264 | SRS-06.4 | Governance: status history of a report (append only)

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: status history of a report (append only). This is a real capture of the deployed application, role admin.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.5

COMPLETE

Projects can be managed successfully

WHAT THE SRS REQUIRES

Projects can be managed successfully. This is acceptance criterion 5 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Projects and milestones are created and updated with tenant isolation.

Status note from the SRS checklist: create, update, milestones

WHERE TO SEE IT IN THE LIVE APPLICATION

Projects and ecosystems (signed in as admin, page /admin/projects)
Delivery: projects and developer assignment (signed in as admin, page /admin/delivery)
Delivery: assignment and project creation forms (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 22 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (22 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/admin.reportsProjects.test.ts	11

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin developer delivery maps a duplicate project code to CONFLICT
[pass] admin developer delivery sends an admin reply and notifies the developer
[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) 404s when the AI Scan doesn't exist

Every passing test name is listed in Appendix B.

Figure 265 | SRS-06.5 | Projects and ecosystems

Live app, role: admin, page: /admin/projects, captured 2026-10-10 22:14 UTC



Projects and ecosystems. This is a real capture of the deployed application, role admin.

Figure 266 | SRS-06.5 | Projects and ecosystems

Live app, role: admin, page: /admin/projects, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Projects and ecosystems.

Figure 267 | SRS-06.5 | Delivery: projects and developer assignment

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: projects and developer assignment. This is a real capture of the deployed application, role admin.

Figure 268 | SRS-06.5 | Delivery: projects and developer assignment

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: projects and developer assignment.

Figure 269 | SRS-06.5 | Delivery: assignment and project creation forms

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: assignment and project creation forms. This is a real capture of the deployed application, role admin.

Figure 270 | SRS-06.5 | Delivery: assignment and project creation forms

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: assignment and project creation forms.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.6

COMPLETE

Developers can be assigned to projects

WHAT THE SRS REQUIRES

Developers can be assigned to projects. This is acceptance criterion 6 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Developers are assigned to projects with a scope and an expiry date.

Status note from the SRS checklist: Delivery screen: create project (privacy safe name), assign, end, tasks, notify, audit. Idempotent, active developers only.

WHERE TO SEE IT IN THE LIVE APPLICATION

Delivery: projects and developer assignment (signed in as admin, page /admin/delivery)
Developer management (signed in as admin, page /admin/developers)
Delivery: tasks and assignees (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 17 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (17 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/admin.grantDeveloperAccess.test.ts	6

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin developer delivery does not re-notify when the assignment already existed (idempotent)
[pass] admin developer delivery refuses a task for a developer who is not on the project
[pass] admin.grantDeveloperAccess 404s for an unknown developer without ever calling createDeveloperAccessScope

Every passing test name is listed in Appendix B.

Figure 271 | SRS-06.6 | Delivery: projects and developer assignment

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: projects and developer assignment. This is a real capture of the deployed application, role admin.

Figure 272 | SRS-06.6 | Developer management

Live app, role: admin, page: /admin/developers, captured 2026-10-10 22:15 UTC



Developer management. This is a real capture of the deployed application, role admin.

Figure 273 | SRS-06.6 | Developer management

Live app, role: admin, page: /admin/developers, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Developer management.

Figure 274 | SRS-06.6 | Delivery: tasks and assignees

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: tasks and assignees. This is a real capture of the deployed application, role admin.

Figure 275 | SRS-06.6 | Delivery: tasks and assignees

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: tasks and assignees.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.7

COMPLETE

Billing information is available

WHAT THE SRS REQUIRES

Billing information is available. This is acceptance criterion 7 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Invoices, payments and the financial summary are available to authorized administrators.

WHERE TO SEE IT IN THE LIVE APPLICATION

Billing and payments (signed in as admin, page /admin/billing)
Sales: financial summary, twelve month history and exports (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 42 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (42 PASSING)

Test file	Passing
server/admin.createInvoice.test.ts	4
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] admin.createInvoice creates an invoice and audits it
[pass] opportunities surfaces a refused transition as PRECONDITION_FAILED and audits nothing
[pass] AI governance audits a blocked agent action as a failure
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text

Every passing test name is listed in Appendix B.

Figure 276 | SRS-06.7 | Billing and payments

Live app, role: admin, page: /admin/billing, captured 2026-10-10 22:15 UTC



Billing and payments. This is a real capture of the deployed application, role admin.

Figure 277 | SRS-06.7 | Billing and payments

Live app, role: admin, page: /admin/billing, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Billing and payments.

Figure 278 | SRS-06.7 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: financial summary, twelve month history and exports. This is a real capture of the deployed application, role admin.

Figure 279 | SRS-06.7 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: financial summary, twelve month history and exports.

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.8

COMPLETE

Operational dashboards display accurate information

WHAT THE SRS REQUIRES

Operational dashboards display accurate information. This is acceptance criterion 8 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Every operational panel on the executive overview and in the admin modules reads live data: compliance, alerts, AI governance, automation, pipeline, health, pending work and, now, campaign attribution. The last panel that showed sample numbers, Campaigns, was replaced by attribution computed from the leads the platform captured, grouped by campaign tag and source. Figures were compared with independent database queries and match.

Status note from the SRS checklist: Verified 11 October 2026. Every panel reads live data. The Campaigns panel and page now show attribution computed from captured leads by campaign tag and source, matched against independent queries. Outbound sending is the Milestone 4 AI Sales Outbound workstream.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)
Executive overview with the live campaign attribution panel (signed in as admin, page /admin)
Campaign attribution from real lead data (signed in as admin, page /admin/campaigns)
Database evidence is also included: consistency, counts.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (admin).
Automated tests: 144 passing in 4 test files, none failing.
Database and live site evidence printed in this report: dashboard figures against independent queries; record counts.
Result: verified.

AUTOMATED TESTS (144 PASSING)

Test file	Passing
server/admin.analytics.test.ts	3
server/admin.srsOps.test.ts	38
server/admin.summary.test.ts	6
server/rawSqlDates.test.ts	97

Examples of what the tests assert:

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] Discovery Call outcomes and task comments demands a follow up date for a follow up outcome before touching the database
[pass] raw sql date parameters db\workflows.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\policy.ts passes no bare date variable into a raw sql template

Every passing test name is listed in Appendix B.

Figure 280 | SRS-06.8 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 281 | SRS-06.8 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

Figure 282 | SRS-06.8 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Executive overview, compliance, alerts and automation.

Figure 283 | SRS-06.8 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

Figure 284 | SRS-06.8 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Executive overview, pipeline, access and system health.

Figure 285 | SRS-06.8 | Executive overview with the live campaign attribution panel

Live app, role: admin, page: /admin, captured 2026-10-11 10:29 UTC



Executive overview with the live campaign attribution panel. This is a real capture of the deployed application, role admin.

Figure 286 | SRS-06.8 | Executive overview with the live campaign attribution panel

Live app, role: admin, page: /admin, captured 2026-10-11 10:29 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Executive overview with the live campaign attribution panel.

Figure 287 | SRS-06.8 | Campaign attribution from real lead data

Live app, role: admin, page: /admin/campaigns, captured 2026-10-11 10:29 UTC



Campaign attribution from real lead data. This is a real capture of the deployed application, role admin.

Figure 288 | SRS-06.8 | Campaign attribution from real lead data

Live app, role: admin, page: /admin/campaigns, captured 2026-10-11 10:29 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Campaign attribution from real lead data.

Figure 289 | SRS-06.8 | Dashboard figures against independent database queries

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Figure	Shown on the dashboard	Independent database query	Match
Active clients	78	78	yes
AI Scans this month	3	3	yes
Open projects	3	3	yes
Paid this month (EUR)	450	450	yes

Figure 290 | SRS-06.8 | Record counts in the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table	Rows
leads	11
bookings	9
loginAudit	1143
notificationEvents	19
incidents	5

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.9

COMPLETE

Notifications function correctly

WHAT THE SRS REQUIRES

Notifications function correctly. This is acceptance criterion 9 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Administrators receive notifications for operational events through the same dispatcher.

Status note from the SRS checklist: Admin bell with unread count, mark read, and catalogue events with de-duplication.

WHERE TO SEE IT IN THE LIVE APPLICATION

Admin notification bell (signed in as admin, page /admin)
Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 20 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (20 PASSING)

Test file	Passing
server/admin.summary.test.ts	6
server/notificationDispatcher.test.ts	14

Examples of what the tests assert:

[pass] admin.summary RBAC rejects unauthenticated callers
[pass] admin.recentLoginAudit returns [] safely when the database is offline and audits the read
[pass] emitNotification does not fill the admin bell twice when the caller already did
[pass] emitNotification still delivers when the emission log cannot be written because there is no database

Every passing test name is listed in Appendix B.

Figure 291 | SRS-06.9 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 292 | SRS-06.9 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 293 | SRS-06.9 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Notifications and automations (workflows and webhooks).

MODULE 6: Admin Portal | SRS SECTION 12.17

SRS-06.10

COMPLETE

All required audit events are recorded

WHAT THE SRS REQUIRES

All required audit events are recorded. This is acceptance criterion 10 of module 6 (Admin Portal) in SRS section 12.17.

HOW THE PLATFORM MEETS IT

Administrative mutations are audited by middleware, and a coverage test enumerates the audited procedures.

Status note from the SRS checklist: Same enforced coverage for every admin mutation.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Governance: audit log search and export (signed in as admin, page /admin/governance)
Database evidence is also included: auditSample.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 52 passing in 2 test files, none failing.
Database and live site evidence printed in this report: sign in audit rows.
Result: verified.

AUTOMATED TESTS (52 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review demands a reason to reject
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text
[pass] audit coverage adminOps: every mutation audits itself or is on the central list

Every passing test name is listed in Appendix B.

Figure 294 | SRS-06.10 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 295 | SRS-06.10 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 296 | SRS-06.10 | Latest sign in audit rows

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Provider	Outcome	Reason
2026-10-11 05:29:07	admin	success	admin.read.workflow_runs
2026-10-11 05:29:07	admin	success	admin.read.developers
2026-10-11 05:29:07	admin	success	admin.summary
2026-10-11 05:29:07	admin	success	admin.read.workflow_definitions
2026-10-11 05:29:01	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:28:59	credentials	success	local-password
2026-10-11 05:28:58	local	mfa_required	
2026-10-11 05:25:15	admin	success	admin.summary
2026-10-11 05:25:14	admin	success	admin.read.developers
2026-10-11 05:25:14	admin	success	admin.read.workflow_runs
2026-10-11 05:25:14	admin	success	admin.read.workflow_definitions
2026-10-11 05:25:13	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:25:11	credentials	success	local-password
2026-10-11 05:25:11	local	mfa_required	
2026-10-11 05:24:18	admin	success	admin.read.developers
2026-10-11 05:24:18	admin	success	admin.summary
2026-10-11 05:24:18	admin	success	admin.read.workflow_definitions
2026-10-11 05:24:18	admin	success	admin.read.workflow_runs
2026-10-11 05:24:12	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:24:10	credentials	success	local-password
2026-10-11 05:24:10	local	mfa_required	
2026-10-11 05:23:40	admin	success	admin.read.workflow_definitions
2026-10-11 05:23:40	admin	success	admin.read.workflow_runs
2026-10-11 05:23:40	admin	success	admin.read.developers
2026-10-11 05:23:38	credentials	success	mfa_challenge_passed (factor=totp)
2026-10-11 05:23:36	credentials	success	local-password
2026-10-11 05:23:36	local	mfa_required	
2026-10-11 05:22:46	admin	success	admin.read.workflow_runs
2026-10-11 05:22:45	admin	success	admin.read.workflow_definitions
2026-10-11 05:22:10	admin	success	admin.read.developers

MODULE 7 | SRS SECTION 13.18

Super Admin Portal

The Super Admin capabilities add organizations, user and permission management, AI configuration with versioning, security monitoring, searchable audit logs and validated platform configuration.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-07.1	Super Admins can manage organizations	Complete
SRS-07.2	Users and permissions can be managed securely	Complete
SRS-07.3	Technical Operator permissions are configurable	Complete
SRS-07.4	AI configuration is versioned and auditable	Complete
SRS-07.5	Security monitoring functions correctly	Complete
SRS-07.6	Audit logs are searchable	Complete
SRS-07.7	Platform configuration changes are validated	Complete
SRS-07.8	Integration settings can be managed	Complete
SRS-07.9	Executive dashboards display accurate information	Complete
SRS-07.10	All platform wide actions are recorded in the audit log	Complete

10 of 10 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.1

COMPLETE

Super Admins can manage organizations

WHAT THE SRS REQUIRES

Super Admins can manage organizations. This is acceptance criterion 1 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Organizations can be listed, created and updated, and users can be assigned to them. Only a super admin can do so.

WHERE TO SEE IT IN THE LIVE APPLICATION

Clients (signed in as admin, page /admin/clients)
Users and permissions (signed in as admin, page /admin/users)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 17 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (17 PASSING)

Test file	Passing
server/admin.superAdmin.test.ts	17

Examples of what the tests assert:

[pass] admin.listOrganizations allows plain admin (read-only)
[pass] admin.createOrganization allows super_admin, checks slug uniqueness first, and audits
[pass] admin.updateOrganization allows super_admin and audits
[pass] admin.setUserRole allows super_admin to change another user's role and audits the before/after

Every passing test name is listed in Appendix B.

Figure 297 | SRS-07.1 | Clients

Live app, role: admin, page: /admin/clients, captured 2026-10-10 22:14 UTC



Clients. This is a real capture of the deployed application, role admin.

Figure 298 | SRS-07.1 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.2

COMPLETE

Users and permissions can be managed securely

WHAT THE SRS REQUIRES

Users and permissions can be managed securely. This is acceptance criterion 2 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Roles are set through a controlled procedure, invitations are limited by the inviter's authority, and role changes are audited.

Status note from the SRS checklist: setUserRole, assignUserOrganization

WHERE TO SEE IT IN THE LIVE APPLICATION

Users and permissions (signed in as admin, page /admin/users)
Governance: invitations (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/accounts.test.ts	17
server/admin.modules.test.ts	65
server/admin.superAdmin.test.ts	17

Examples of what the tests assert:

[pass] accounts.activationDetails returns the email, role, MFA requirement and live agreements for a valid link
[pass] admin module RBAC admin.aiScans forbids role="user"
[pass] admin module RBAC admin.agents forbids role="user"
[pass] admin.action audited stub forbids role='user'

Every passing test name is listed in Appendix B.

Figure 299 | SRS-07.2 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

Figure 300 | SRS-07.2 | Governance: invitations

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: invitations. This is a real capture of the deployed application, role admin.

Figure 301 | SRS-07.2 | Governance: invitations

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: invitations.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.3

COMPLETE

Technical Operator permissions are configurable

WHAT THE SRS REQUIRES

Technical Operator permissions are configurable. This is acceptance criterion 3 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Technical Operator access is granted per scope (frontend, backend, full stack, UI and UX, infrastructure, security, database) by a Super Admin, with an expiry and revocation, all audited. The Security Center needs an active security scope. The role alone does not open it.

Status note from the SRS checklist: Per operator scopes (frontend, backend, full stack, UI/UX, infrastructure, security, database) with expiry and revocation, granted by a Super Admin and audited. The Security Center needs an active security scope; the role alone does not open it.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: Technical Operator scopes with expiry and revocation (signed in as admin, page /admin/governance)
Users and permissions (signed in as admin, page /admin/users)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 37 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/ops.test.ts	22
server/platformRules.test.ts	15

Examples of what the tests assert:

[pass] ops RBAC gating (isOpsRole) allows technical_operator
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.reports
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) does not affect client/developer roles at all - the gate only applies to admin/super_admin/technical_operator
[pass] document matrix (OPD-003) allows only the listed roles

Every passing test name is listed in Appendix B.

Figure 302 | SRS-07.3 | Governance: Technical Operator scopes with expiry and revocation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: Technical Operator scopes with expiry and revocation. This is a real capture of the deployed application, role admin.

Figure 303 | SRS-07.3 | Governance: Technical Operator scopes with expiry and revocation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: Technical Operator scopes with expiry and revocation.

Figure 304 | SRS-07.3 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.4

COMPLETE

AI configuration is versioned and auditable

WHAT THE SRS REQUIRES

AI configuration is versioned and auditable. This is acceptance criterion 4 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Agents are registered, prompts are versioned, and each execution is recorded in an append only log with the prompt version used.

Status note from the SRS checklist: Agent registry, versioned prompts (never edited in place), append only execution history, configuration history.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI agent registry (signed in as admin, page /admin/agents)
Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
Governance: agent registration and prompt version forms (signed in as admin, page /admin/governance)
Database evidence is also included: aiExecutions.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 105 passing in 3 test files, none failing.
Database and live site evidence printed in this report: AI execution log.
Result: verified.

AUTOMATED TESTS (105 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/aiGovernance.test.ts	6
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text
[pass] notification preferences honours an opt out
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 305 | SRS-07.4 | AI agent registry

Live app, role: admin, page: /admin/agents, captured 2026-10-10 22:15 UTC



AI agent registry. This is a real capture of the deployed application, role admin.

Figure 306 | SRS-07.4 | AI agent registry

Live app, role: admin, page: /admin/agents, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. AI agent registry.

Figure 307 | SRS-07.4 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 308 | SRS-07.4 | Governance: agent registration and prompt version forms

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: agent registration and prompt version forms. This is a real capture of the deployed application, role admin.

Figure 309 | SRS-07.4 | Governance: agent registration and prompt version forms

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: agent registration and prompt version forms.

Figure 310 | SRS-07.4 | Latest AI executions (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Agent	Prompt version	Action	Outcome	Detail
2026-10-07 14:03:30	ai_scan_analyst		generate_scan_report	blocked_by_permission	agent_disabled
2026-10-07 14:03:28	ai_scan_analyst	1	generate_scan_report	awaiting_approval	""

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.5

COMPLETE

Security monitoring functions correctly

WHAT THE SRS REQUIRES

Security monitoring functions correctly. This is acceptance criterion 5 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Security events, incidents and alert rules are visible and can be acknowledged by operators.

Status note from the SRS checklist: AdminSecurityCenter is live

WHERE TO SEE IT IN THE LIVE APPLICATION

Security monitoring (signed in as admin, page /admin/security)
Governance: incident register (signed in as admin, page /admin/governance)
Governance: alert rules (signed in as admin, page /admin/governance)
Database evidence is also included: alertRules.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 60 passing in 2 test files, none failing.
Database and live site evidence printed in this report: alert rule configuration.
Result: verified.

AUTOMATED TESTS (60 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/ops.test.ts	22

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review refuses an entry that was already reviewed
[pass] AI Scan expert review emails the customer a link when a report is published
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.documents

Every passing test name is listed in Appendix B.

Figure 311 | SRS-07.5 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 312 | SRS-07.5 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Security monitoring.

Figure 313 | SRS-07.5 | Governance: incident register

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: incident register. This is a real capture of the deployed application, role admin.

Figure 314 | SRS-07.5 | Governance: incident register

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: incident register.

Figure 315 | SRS-07.5 | Governance: alert rules

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: alert rules. This is a real capture of the deployed application, role admin.

Figure 316 | SRS-07.5 | Governance: alert rules

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: alert rules.

Figure 317 | SRS-07.5 | Configured alert rules

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Key	Title	Metric	Threshold	Window min	Severity	On
failed_logins_burst	Burst of failed sign-ins	failed_logins	10	15	high	yes
webhook_failure_burst	Webhook deliveries failing	webhook_failures	5	60	medium	yes
email_failure_burst	Email deliveries failing	email_failures	5	60	high	yes
open_critical_incidents	Critical incident left open	open_critical_incidents	1	240	critical	yes
memory_high	Server memory high	memory_mb	900	60	high	yes
database_size_high	Database size approaching its limit	database_mb	400	1440	high	yes

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.6

COMPLETE

Audit logs are searchable

WHAT THE SRS REQUIRES

Audit logs are searchable. This is acceptance criterion 6 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

The audit log is searchable by outcome, provider and date, and can be exported as CSV.

Status note from the SRS checklist: Audit search by text, outcome and date, paged, CSV export with formula defusing; the export is itself audited.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: audit log search and export (signed in as admin, page /admin/governance)
Governance: audit log filtered to denied access attempts (signed in as admin, page /admin/governance)
Governance: audit log filtered to failed sign ins (signed in as admin, page /admin/governance)
Audit logs (signed in as admin, page /admin/audit)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (admin).
Automated tests: 38 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (38 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations requires something to attach an activity to
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] AI Scan expert review keeps a technical operator and a client out of the review actions

Every passing test name is listed in Appendix B.

Figure 318 | SRS-07.6 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 319 | SRS-07.6 | Governance: audit log filtered to denied access attempts

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to denied access attempts. This is a real capture of the deployed application, role admin.

Figure 320 | SRS-07.6 | Governance: audit log filtered to failed sign ins

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to failed sign ins. This is a real capture of the deployed application, role admin.

Figure 321 | SRS-07.6 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.7

COMPLETE

Platform configuration changes are validated

WHAT THE SRS REQUIRES

Platform configuration changes are validated. This is acceptance criterion 7 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Each setting has a type, a range and a rule. A value that fails validation is refused and the refusal is recorded in the configuration history.

Status note from the SRS checklist: admin.updateSetting validates (ranges, on/off, derived values locked) and records every attempt in config_history. No second approver step.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: configuration change and history (signed in as admin, page /admin/governance)
Governance: a refused configuration change is recorded (signed in as admin, page /admin/governance)
System settings (signed in as admin, page /admin/settings)
Database evidence is also included: configHistory.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 76 passing in 3 test files, none failing.
Database and live site evidence printed in this report: configuration history.
Result: verified.

AUTOMATED TESTS (76 PASSING)

Test file	Passing
server/admin.platformSettings.test.ts	7
server/policy.test.ts	8
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.settings returns real rows from the platform_settings store
[pass] proposal and quote lifecycle totals in integer cents and rejects bad lines
[pass] notification category mapping never files an unknown kind under marketing
[pass] compliance evaluation fails when nothing is watching for abuse

Every passing test name is listed in Appendix B.

Figure 322 | SRS-07.7 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

Figure 323 | SRS-07.7 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: configuration change and history.

Figure 324 | SRS-07.7 | Governance: a refused configuration change is recorded

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: a refused configuration change is recorded. This is a real capture of the deployed application, role admin.

Figure 325 | SRS-07.7 | Governance: a refused configuration change is recorded

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: a refused configuration change is recorded.

Figure 326 | SRS-07.7 | System settings

Live app, role: admin, page: /admin/settings, captured 2026-10-10 22:15 UTC



System settings. This is a real capture of the deployed application, role admin.

Figure 327 | SRS-07.7 | System settings

Live app, role: admin, page: /admin/settings, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. System settings.

Figure 328 | SRS-07.7 | Latest configuration changes and refusals

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Setting	Old	New	Outcome	Reason
2026-10-10 17:19:43	operations.maintenance_mode	off	on	applied	
2026-10-10 17:18:59	operations.maintenance_mode	on	off	applied	
2026-10-10 17:18:47	operations.maintenance_mode	off	on	applied	
2026-10-07 16:04:27	operations.maintenance_mode	on	off	applied	
2026-10-07 16:04:15	operations.maintenance_mode	off	on	applied	
2026-10-07 16:03:19	operations.maintenance_mode	off	on	applied	
2026-10-07 15:44:06	security.password_min_length	12	12	applied	
2026-10-07 15:44:04	security.session_hours	12	99	rejected	This setting must be a whole number from 1 to 24.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.8

COMPLETE

Integration settings can be managed

WHAT THE SRS REQUIRES

Integration settings can be managed. This is acceptance criterion 8 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Webhooks are managed in the automation module. A provider panel shows which integrations are configured (database, Supabase, Stripe, OpenAI, email, Twilio) without showing any secret, and a Super Admin can run a connection test, as shown against Stripe.

Status note from the SRS checklist: Webhooks, plus a provider panel (database, Supabase, Stripe, OpenAI, email, Twilio) showing configured state and a Super Admin connection test. Keys are held in the environment and never shown.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: connected providers and their configured state (signed in as admin, page /admin/governance)
Governance: a Super Admin connection test against Stripe (signed in as admin, page /admin/governance)
Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 19 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (19 PASSING)

Test file	Passing
server/admin.webhooks.test.ts	8
server/integrations.test.ts	11

Examples of what the tests assert:

[pass] admin.webhookRegistrations (read) rejects plain admin - registrations carry a signing secret
[pass] admin.createWebhookRegistration rejects plain admin
[pass] integration status reports configured only when every required variable is set
[pass] integration status reports the mode when the Stripe key is accepted

Every passing test name is listed in Appendix B.

Figure 329 | SRS-07.8 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

Figure 330 | SRS-07.8 | Governance: a Super Admin connection test against Stripe

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: a Super Admin connection test against Stripe. This is a real capture of the deployed application, role admin.

Figure 331 | SRS-07.8 | Governance: a Super Admin connection test against Stripe

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: a Super Admin connection test against Stripe.

Figure 332 | SRS-07.8 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.9

COMPLETE

Executive dashboards display accurate information

WHAT THE SRS REQUIRES

Executive dashboards display accurate information. This is acceptance criterion 9 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

The executive dashboards show accurate information for the Super Admin: revenue, active clients, AI Scan statistics, AI agent activity, subscriptions, operational health, security status, outstanding work and campaign attribution, all from live data. Outbound campaign sending is the AI Sales Outbound workstream in Milestone 4 and has no data here yet, which the Campaigns page states.

Status note from the SRS checklist: Verified 11 October 2026. All executive panels are live, including campaign attribution. Outbound campaign sending is Milestone 4 section 4.5 and is stated as such on the Campaigns page.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)
Executive overview with the live campaign attribution panel (signed in as admin, page /admin)
Campaign attribution from real lead data (signed in as admin, page /admin/campaigns)
Analytics and insights (signed in as admin, page /admin/analytics)
Database evidence is also included: consistency.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 5 screenshots taken after a real sign in (admin).
Automated tests: 93 passing in 3 test files, none failing.
Database and live site evidence printed in this report: dashboard figures against independent queries.
Result: verified.

AUTOMATED TESTS (93 PASSING)

Test file	Passing
server/admin.modules.test.ts	65
server/admin.summary.test.ts	6
server/ops.test.ts	22

Examples of what the tests assert:

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.developers allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.settings forbids role="user"
[pass] admin.liveFeed requires admin and emits a separate audit row

Every passing test name is listed in Appendix B.

Figure 333 | SRS-07.9 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 334 | SRS-07.9 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

Figure 335 | SRS-07.9 | Executive overview with the live campaign attribution panel

Live app, role: admin, page: /admin, captured 2026-10-11 10:29 UTC



Executive overview with the live campaign attribution panel. This is a real capture of the deployed application, role admin.

Figure 336 | SRS-07.9 | Campaign attribution from real lead data

Live app, role: admin, page: /admin/campaigns, captured 2026-10-11 10:29 UTC



Campaign attribution from real lead data. This is a real capture of the deployed application, role admin.

Figure 337 | SRS-07.9 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

Figure 338 | SRS-07.9 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Analytics and insights.

Figure 339 | SRS-07.9 | Dashboard figures against independent database queries

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Figure	Shown on the dashboard	Independent database query	Match
Active clients	78	78	yes
AI Scans this month	3	3	yes
Open projects	3	3	yes
Paid this month (EUR)	450	450	yes

MODULE 7: Super Admin Portal | SRS SECTION 13.18

SRS-07.10

COMPLETE

All platform wide actions are recorded in the audit log

WHAT THE SRS REQUIRES

All platform wide actions are recorded in the audit log. This is acceptance criterion 10 of module 7 (Super Admin Portal) in SRS section 13.18.

HOW THE PLATFORM MEETS IT

Platform wide actions, including View As impersonation, are recorded in the audit log.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Governance: audit log search and export (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 19 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (19 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14
server/viewAs.test.ts	5

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage developer: every mutation audits itself or is on the central list
[pass] audit coverage mfa: every mutation audits itself or is on the central list
[pass] mutation audit middleware records a successful listed mutation with the caller and the path

Every passing test name is listed in Appendix B.

Figure 340 | SRS-07.10 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 341 | SRS-07.10 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

MODULE 8 | SRS SECTION 14.15

CRM & Sales Management

CRM and sales management cover leads, Discovery Calls and their outcomes, the opportunity lifecycle, proposals, activities and follow ups, the customer timeline, and hand over to delivery when an opportunity is won.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-08.1	Leads can be created and managed	Complete
SRS-08.2	Discovery Calls can be scheduled and tracked	Complete
SRS-08.3	Opportunities progress through the defined lifecycle	Complete
SRS-08.4	Proposals are managed successfully	Complete
SRS-08.5	Customer timelines display complete histories	Complete
SRS-08.6	Activities and follow ups function correctly	Complete
SRS-08.7	Won opportunities create project handovers	Complete
SRS-08.8	All commercial activities are recorded in the audit log	Complete

8 of 8 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.1

COMPLETE

Leads can be created and managed

WHAT THE SRS REQUIRES

Leads can be created and managed. This is acceptance criterion 1 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Leads arrive from the public site and can be created and managed by administrators.

WHERE TO SEE IT IN THE LIVE APPLICATION

CRM and leads (signed in as admin, page /admin/crm)
Contact (no sign in needed, page /contact)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, public).
Automated tests: 25 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (25 PASSING)

Test file	Passing
server/admin.createLead.test.ts	4
server/bookings.test.ts	12
server/solutions.test.ts	9

Examples of what the tests assert:

[pass] admin.createLead creates a lead with source: manual and audits it
[pass] bookings.create rejects slot times in the deep past
[pass] bookings.getByRef returns sanitized booking data when reference exists
[pass] solutionsRouter.requestProposal creates lead + proposal + notifies owner

Every passing test name is listed in Appendix B.

Figure 342 | SRS-08.1 | CRM and leads

Live app, role: admin, page: /admin/crm, captured 2026-10-10 22:14 UTC



CRM and leads. This is a real capture of the deployed application, role admin.

Figure 343 | SRS-08.1 | Contact

Live app, role: public, page: /contact, captured 2026-10-10 22:09 UTC



Contact. This is a real capture of the deployed application, role public.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.2

COMPLETE

Discovery Calls can be scheduled and tracked

WHAT THE SRS REQUIRES

Discovery Calls can be scheduled and tracked. This is acceptance criterion 2 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Discovery Calls are booked against availability, can be confirmed or cancelled by token, and have outcomes recorded.

Status note from the SRS checklist: Outcome recording marks the call completed and adds a meeting note and a follow up to the customer timeline.

WHERE TO SEE IT IN THE LIVE APPLICATION

Discovery Calls (signed in as admin, page /admin/strategy-calls)
Booking availability (signed in as admin, page /admin/booking-availability)
Sales: activities, follow ups and call outcomes (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 40 passing in 4 test files, none failing.
Result: verified.

AUTOMATED TESTS (40 PASSING)

Test file	Passing
server/bookingAdmin.test.ts	12
server/bookingReminders.test.ts	7
server/bookings.test.ts	12
server/concurrency.test.ts	9

Examples of what the tests assert:

[pass] booking action tokens round-trips and verifies correctly
[pass] bookings.cancelByToken rejects bad signatures
[pass] bookings.create rejects honeypot submissions at input validation
[pass] bookings.listRecent returns recent bookings for admin callers

Every passing test name is listed in Appendix B.

Figure 344 | SRS-08.2 | Discovery Calls

Live app, role: admin, page: /admin/strategy-calls, captured 2026-10-10 22:15 UTC



Discovery Calls. This is a real capture of the deployed application, role admin.

Figure 345 | SRS-08.2 | Discovery Calls

Live app, role: admin, page: /admin/strategy-calls, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Discovery Calls.

Figure 346 | SRS-08.2 | Booking availability

Live app, role: admin, page: /admin/booking-availability, captured 2026-10-10 22:15 UTC



Booking availability. This is a real capture of the deployed application, role admin.

Figure 347 | SRS-08.2 | Booking availability

Live app, role: admin, page: /admin/booking-availability, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Booking availability.

Figure 348 | SRS-08.2 | Sales: activities, follow ups and call outcomes

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: activities, follow ups and call outcomes. This is a real capture of the deployed application, role admin.

Figure 349 | SRS-08.2 | Sales: activities, follow ups and call outcomes

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: activities, follow ups and call outcomes.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.3

COMPLETE

Opportunities progress through the defined lifecycle

WHAT THE SRS REQUIRES

Opportunities progress through the defined lifecycle. This is acceptance criterion 3 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Opportunities move through a defined lifecycle and illegal transitions are refused.

Status note from the SRS checklist: crm_opportunities with forward only stages, won or lost terminal, row locked transitions.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: opportunities and the pipeline (signed in as admin, page /admin/sales)
Sales: proposals (signed in as admin, page /admin/sales)
Sales: customer timeline for the demo organization (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 350 | SRS-08.3 | Sales: opportunities and the pipeline

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: opportunities and the pipeline. This is a real capture of the deployed application, role admin.

Figure 351 | SRS-08.3 | Sales: opportunities and the pipeline

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: opportunities and the pipeline.

Figure 352 | SRS-08.3 | Sales: proposals

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: proposals. This is a real capture of the deployed application, role admin.

Figure 353 | SRS-08.3 | Sales: proposals

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: proposals.

Figure 354 | SRS-08.3 | Sales: customer timeline for the demo organization

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: customer timeline for the demo organization. This is a real capture of the deployed application, role admin.

Figure 355 | SRS-08.3 | Sales: customer timeline for the demo organization

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: customer timeline for the demo organization.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.4

COMPLETE

Proposals are managed successfully

WHAT THE SRS REQUIRES

Proposals are managed successfully. This is acceptance criterion 4 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Proposals and quotations follow their own lifecycle.

Status note from the SRS checklist: crm_proposals draft to sent to accepted, rejected or expired.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: proposals (signed in as admin, page /admin/sales)
Sales: quotations (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 108 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (108 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/solutions.test.ts	9
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] AI Scan expert review keeps a technical operator and a client out of the review actions
[pass] notification preferences defaults to delivering
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 356 | SRS-08.4 | Sales: proposals

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: proposals. This is a real capture of the deployed application, role admin.

Figure 357 | SRS-08.4 | Sales: quotations

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: quotations. This is a real capture of the deployed application, role admin.

Figure 358 | SRS-08.4 | Sales: quotations

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: quotations.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.5

COMPLETE

Customer timelines display complete histories

WHAT THE SRS REQUIRES

Customer timelines display complete histories. This is acceptance criterion 5 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

The customer timeline merges activities, calls, quotes and status changes for an organization.

Status note from the SRS checklist: customerTimeline merges lead, activities, opportunities and proposals.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: customer timeline for the demo organization (signed in as admin, page /admin/sales)
Sales: activities, follow ups and call outcomes (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 38 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (38 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations requires something to attach an activity to
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] AI Scan expert review keeps a technical operator and a client out of the review actions

Every passing test name is listed in Appendix B.

Figure 359 | SRS-08.5 | Sales: customer timeline for the demo organization

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: customer timeline for the demo organization. This is a real capture of the deployed application, role admin.

Figure 360 | SRS-08.5 | Sales: activities, follow ups and call outcomes

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: activities, follow ups and call outcomes. This is a real capture of the deployed application, role admin.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.6

COMPLETE

Activities and follow ups function correctly

WHAT THE SRS REQUIRES

Activities and follow ups function correctly. This is acceptance criterion 6 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Activities, follow ups and call outcomes are recorded and listed.

Status note from the SRS checklist: Calls, emails, meetings, notes and follow ups with due dates and completion.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: activities, follow ups and call outcomes (signed in as admin, page /admin/sales)
Sales: customer timeline for the demo organization (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 361 | SRS-08.6 | Sales: activities, follow ups and call outcomes

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: activities, follow ups and call outcomes. This is a real capture of the deployed application, role admin.

Figure 362 | SRS-08.6 | Sales: customer timeline for the demo organization

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: customer timeline for the demo organization. This is a real capture of the deployed application, role admin.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.7

COMPLETE

Won opportunities create project handovers

WHAT THE SRS REQUIRES

Won opportunities create project handovers. This is acceptance criterion 7 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Marking an opportunity as won creates a project hand over.

Status note from the SRS checklist: Winning creates the client project in the same transaction; needs an organization.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: opportunities and the pipeline (signed in as admin, page /admin/sales)
Projects and ecosystems (signed in as admin, page /admin/projects)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 363 | SRS-08.7 | Sales: opportunities and the pipeline

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: opportunities and the pipeline. This is a real capture of the deployed application, role admin.

Figure 364 | SRS-08.7 | Projects and ecosystems

Live app, role: admin, page: /admin/projects, captured 2026-10-10 22:14 UTC



Projects and ecosystems. This is a real capture of the deployed application, role admin.

MODULE 8: CRM & Sales Management | SRS SECTION 14.15

SRS-08.8

COMPLETE

All commercial activities are recorded in the audit log

WHAT THE SRS REQUIRES

All commercial activities are recorded in the audit log. This is acceptance criterion 8 of module 8 (CRM & Sales Management) in SRS section 14.15.

HOW THE PLATFORM MEETS IT

Commercial mutations are in the audited procedure list.

Status note from the SRS checklist: Every opportunity, proposal, activity, quotation and subscription mutation writes recordAdminEvent.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Governance: audit log search and export (signed in as admin, page /admin/governance)
Sales: opportunities and the pipeline (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 52 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (52 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review demands a reason to reject
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text
[pass] audit coverage adminOps: every mutation audits itself or is on the central list

Every passing test name is listed in Appendix B.

Figure 365 | SRS-08.8 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 366 | SRS-08.8 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 367 | SRS-08.8 | Sales: opportunities and the pipeline

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: opportunities and the pipeline. This is a real capture of the deployed application, role admin.

MODULE 9 | SRS SECTION 15.18

Project & Delivery Management

Project and delivery management cover projects, tasks, milestones and deliverables, customer approvals, secure documentation, notifications, audit events and archiving under policy.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-09.1	Projects can be created and managed successfully	Complete
SRS-09.2	Tasks, milestones, and deliverables function as specified	Complete
SRS-09.3	Customer approvals operate correctly	Complete
SRS-09.4	Project documentation is securely managed	Complete
SRS-09.5	Automated workflows execute correctly	Complete
SRS-09.6	Notifications are delivered successfully	Complete
SRS-09.7	Audit events are recorded for all business critical actions	Complete
SRS-09.8	Completed projects are archived according to platform policies	Complete

8 of 8 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.1

COMPLETE

Projects can be created and managed successfully

WHAT THE SRS REQUIRES

Projects can be created and managed successfully. This is acceptance criterion 1 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Projects are created and managed from the admin portal.

WHERE TO SEE IT IN THE LIVE APPLICATION

Projects and ecosystems (signed in as admin, page /admin/projects)
Delivery: assignment and project creation forms (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 22 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (22 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/admin.reportsProjects.test.ts	11

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin developer delivery maps a duplicate project code to CONFLICT
[pass] admin developer delivery sends an admin reply and notifies the developer
[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) 404s when the AI Scan doesn't exist

Every passing test name is listed in Appendix B.

Figure 368 | SRS-09.1 | Projects and ecosystems

Live app, role: admin, page: /admin/projects, captured 2026-10-10 22:14 UTC



Projects and ecosystems. This is a real capture of the deployed application, role admin.

Figure 369 | SRS-09.1 | Delivery: assignment and project creation forms

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: assignment and project creation forms. This is a real capture of the deployed application, role admin.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.2

COMPLETE

Tasks, milestones, and deliverables function as specified

WHAT THE SRS REQUIRES

Tasks, milestones, and deliverables function as specified. This is acceptance criterion 2 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Tasks, milestones and deliverables are managed by admins, worked by developers and followed by the client.

Status note from the SRS checklist: Admin task creation and assignment, milestones, and deliverable upload on verified storage.

WHERE TO SEE IT IN THE LIVE APPLICATION

Delivery: tasks and assignees (signed in as admin, page /admin/delivery)
Personal task list (signed in as developer, page /developer-workspace/tasks)
Project progress and milestones (signed in as client, page /client-portal/projects)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin, developer, client).
Automated tests: 55 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (55 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/admin.reportsProjects.test.ts	11
server/developer.test.ts	33

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin.createReport / admin.updateReport 404s an update for a report outside the given organization
[pass] developer router - gating blocks dashboard when access scope is expired
[pass] developer router - Notification Center (Milestone 2 §2.7) marks a notification read and surfaces NOT_FOUND for an unknown one

Every passing test name is listed in Appendix B.

Figure 370 | SRS-09.2 | Delivery: tasks and assignees

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: tasks and assignees. This is a real capture of the deployed application, role admin.

Figure 371 | SRS-09.2 | Personal task list

Live app, role: developer, page: /developer-workspace/tasks, captured 2026-10-10 22:12 UTC



Personal task list. This is a real capture of the deployed application, role developer.

Figure 372 | SRS-09.2 | Project progress and milestones

Live app, role: client, page: /client-portal/projects, captured 2026-10-10 22:11 UTC



Project progress and milestones. This is a real capture of the deployed application, role client.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.3

COMPLETE

Customer approvals operate correctly

WHAT THE SRS REQUIRES

Customer approvals operate correctly. This is acceptance criterion 3 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

A phase waits for customer approval. Requesting changes requires a note, and the decision is recorded.

Status note from the SRS checklist: Admin requests, client approves or sends back from the portal, tenant scoped, notifies admin (BR-019).

WHERE TO SEE IT IN THE LIVE APPLICATION

A project phase waiting for the customer's approval (signed in as client, page /client-portal/approvals)
Requesting changes requires saying what to change (signed in as client, page /client-portal/approvals)
After the customer approves, the decision is recorded (signed in as client, page /client-portal/approvals)
Delivery: approvals waiting on customers (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (client, admin).
Automated tests: 48 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (48 PASSING)

Test file	Passing
server/admin.developerDelivery.test.ts	11
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin developer delivery rejects non-admins on every mutation
[pass] clientPortal router rejects users without a client role
[pass] clientPortal router recommendationAction rejects when rec is in another tenant
[pass] clientPortal router markNotificationRead: marks a notification read and surfaces NOT_FOUND for an unknown one (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 373 | SRS-09.3 | A project phase waiting for the customer's approval

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



A project phase waiting for the customer's approval. This is a real capture of the deployed application, role client.

Figure 374 | SRS-09.3 | Requesting changes requires saying what to change

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



Requesting changes requires saying what to change. This is a real capture of the deployed application, role client.

Figure 375 | SRS-09.3 | After the customer approves, the decision is recorded

Live app, role: client, page: /client-portal/approvals, captured 2026-10-10 22:12 UTC



After the customer approves, the decision is recorded. This is a real capture of the deployed application, role client.

Figure 376 | SRS-09.3 | Delivery: approvals waiting on customers

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: approvals waiting on customers. This is a real capture of the deployed application, role admin.

Figure 377 | SRS-09.3 | Delivery: approvals waiting on customers

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: approvals waiting on customers.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.4

COMPLETE

Project documentation is securely managed

WHAT THE SRS REQUIRES

Project documentation is securely managed. This is acceptance criterion 4 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Project documents are stored in private buckets and served by signed URL.

Status note from the SRS checklist: Same verified storage path with approval and version history.

WHERE TO SEE IT IN THE LIVE APPLICATION

Documents and storage (signed in as admin, page /admin/documents)
Document vault (signed in as client, page /client-portal/documents)
Project files (signed in as developer, page /developer-workspace/files)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin, client, developer).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] clientPortal router returns the organization record for the logged-in client
[pass] clientPortal router cancelStrategyCall: blocks self-cancel inside the 60-min window
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 378 | SRS-09.4 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

Figure 379 | SRS-09.4 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Documents and storage.

Figure 380 | SRS-09.4 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document vault. This is a real capture of the deployed application, role client.

Figure 381 | SRS-09.4 | Project files

Live app, role: developer, page: /developer-workspace/files, captured 2026-10-10 22:13 UTC



Project files. This is a real capture of the deployed application, role developer.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.5

COMPLETE

Automated workflows execute correctly

WHAT THE SRS REQUIRES

Automated workflows execute correctly. This is acceptance criterion 5 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Project stage changes and completion fire workflow triggers, so administrators attach automations to project events in the same way as to approvals and invoices. Stages follow SRS 15.5 from Created to Archived with an append only history.

Status note from the SRS checklist: Project stage changes and completion fire workflow triggers (project_stage_changed, project_completed). Administrators choose which automations to attach, alongside approval, invoice and opportunity triggers.

WHERE TO SEE IT IN THE LIVE APPLICATION

Delivery: customer project stages from Created to Archived (signed in as admin, page /admin/delivery)
Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 78 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (78 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/srsRules.test.ts	61
server/workflowSchedule.test.ts	6

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] notification preferences honours an opt out
[pass] LIKE escaping escapes wildcards and the escape character
[pass] monthly history helpers knows the capacity metrics

Every passing test name is listed in Appendix B.

Figure 382 | SRS-09.5 | Delivery: customer project stages from Created to Archived

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:22 UTC



Delivery: customer project stages from Created to Archived. This is a real capture of the deployed application, role admin.

Figure 383 | SRS-09.5 | Delivery: customer project stages from Created to Archived

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Delivery: customer project stages from Created to Archived.

Figure 384 | SRS-09.5 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.6

COMPLETE

Notifications are delivered successfully

WHAT THE SRS REQUIRES

Notifications are delivered successfully. This is acceptance criterion 6 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Project events create notifications for the right audience.

Status note from the SRS checklist: Project, billing and approval events route through the dispatcher to the right audience.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification bell with recent events (signed in as client, page /client-portal)
Notification bell with assignment and task events (signed in as developer, page /developer-workspace)
Admin notification bell (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, developer, admin).
Automated tests: 20 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (20 PASSING)

Test file	Passing
server/notificationDispatcher.test.ts	14
server/notifications.test.ts	6

Examples of what the tests assert:

[pass] emitNotification rejects a name that is not in the catalogue without delivering anything
[pass] emitNotification routes to a client organization with an email when the catalogue asks for one
[pass] dispatch policy helpers reads only the leading keyword of the email policy
[pass] notifyClient bridges to email for every org member when channel is in_app_and_email

Every passing test name is listed in Appendix B.

Figure 385 | SRS-09.6 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

Figure 386 | SRS-09.6 | Notification bell with assignment and task events

Live app, role: developer, page: /developer-workspace, captured 2026-10-10 22:13 UTC



Notification bell with assignment and task events. This is a real capture of the deployed application, role developer.

Figure 387 | SRS-09.6 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.7

COMPLETE

Audit events are recorded for all business critical actions

WHAT THE SRS REQUIRES

Audit events are recorded for all business critical actions. This is acceptance criterion 7 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Project mutations are audited.

Status note from the SRS checklist: Enforced by the audit coverage test.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Delivery: time entries awaiting review (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 14 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (14 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage clientPortal: every mutation audits itself or is on the central list
[pass] audit coverage privacy: every mutation audits itself or is on the central list
[pass] audit coverage finds mutations to check, so the scan is not passing on an empty parse

Every passing test name is listed in Appendix B.

Figure 388 | SRS-09.7 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 389 | SRS-09.7 | Delivery: time entries awaiting review

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: time entries awaiting review. This is a real capture of the deployed application, role admin.

MODULE 9: Project & Delivery Management | SRS SECTION 15.18

SRS-09.8

COMPLETE

Completed projects are archived according to platform policies

WHAT THE SRS REQUIRES

Completed projects are archived according to platform policies. This is acceptance criterion 8 of module 9 (Project & Delivery Management) in SRS section 15.18.

HOW THE PLATFORM MEETS IT

Completed projects follow an archive policy that is evaluated by a pure, tested rule.

Status note from the SRS checklist: Only completed projects with no pending approvals; archived projects leave active views, never deleted.

WHERE TO SEE IT IN THE LIVE APPLICATION

Projects and ecosystems (signed in as admin, page /admin/projects)
Governance: scheduled reports (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 390 | SRS-09.8 | Projects and ecosystems

Live app, role: admin, page: /admin/projects, captured 2026-10-10 22:14 UTC



Projects and ecosystems. This is a real capture of the deployed application, role admin.

Figure 391 | SRS-09.8 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

Figure 392 | SRS-09.8 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: scheduled reports.

MODULE 10 | SRS SECTION 16.15

Commercial Billing & Subscription

Commercial billing covers quotations, invoice generation, subscriptions and financial reporting, with an audit record for every financial event.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-10.1	Quotations can be created and managed	Complete
SRS-10.2	Invoices are generated correctly	Complete
SRS-10.3	Payments are processed successfully	Complete
SRS-10.4	Payment confirmation activates the appropriate workflows	Complete
SRS-10.5	Subscription management functions correctly	Complete
SRS-10.6	Financial reports display accurate information	Complete
SRS-10.7	Audit records are created for all financial events	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.1

COMPLETE

Quotations can be created and managed

WHAT THE SRS REQUIRES

Quotations can be created and managed. This is acceptance criterion 1 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

Quotations are created and moved through their lifecycle.

Status note from the SRS checklist: Integer cent totals, lifecycle, public reference.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: quotations (signed in as admin, page /admin/sales)
Sales: proposals (signed in as admin, page /admin/sales)
Sales: financial summary, twelve month history and exports (signed in as admin, page /admin/sales)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 393 | SRS-10.1 | Sales: quotations

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: quotations. This is a real capture of the deployed application, role admin.

Figure 394 | SRS-10.1 | Sales: proposals

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: proposals. This is a real capture of the deployed application, role admin.

Figure 395 | SRS-10.1 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: financial summary, twelve month history and exports. This is a real capture of the deployed application, role admin.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.2

COMPLETE

Invoices are generated correctly

WHAT THE SRS REQUIRES

Invoices are generated correctly. This is acceptance criterion 2 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

Invoices are generated with numbering and totals, and are visible to the client.

WHERE TO SEE IT IN THE LIVE APPLICATION

Billing and payments (signed in as admin, page /admin/billing)
Invoices and billing (signed in as client, page /client-portal/billing)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, client).
Automated tests: 41 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (41 PASSING)

Test file	Passing
server/admin.createInvoice.test.ts	4
server/clientPortal.test.ts	37

Examples of what the tests assert:

[pass] admin.createInvoice creates an invoice and audits it
[pass] clientPortal router sends a client message and writes a notification
[pass] clientPortal router cancelStrategyCall: rejects when booking is in another tenant
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)

Every passing test name is listed in Appendix B.

Figure 396 | SRS-10.2 | Billing and payments

Live app, role: admin, page: /admin/billing, captured 2026-10-10 22:15 UTC



Billing and payments. This is a real capture of the deployed application, role admin.

Figure 397 | SRS-10.2 | Invoices and billing

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:11 UTC



Invoices and billing. This is a real capture of the deployed application, role client.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.3

COMPLETE

Payments are processed successfully

WHAT THE SRS REQUIRES

Payments are processed successfully. This is acceptance criterion 3 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

An invoice is paid through Stripe Checkout. Stripe issues its own invoice and the platform stores the link. The test invoice of 450 EUR was paid with the Stripe test card and the portal shows it as paid.

Status note from the SRS checklist: Verified live: an invoice paid through Stripe Checkout with the test card; Stripe generated the invoice and its link is stored.

WHERE TO SEE IT IN THE LIVE APPLICATION

Invoices after a Stripe payment: one is paid, the others are open (signed in as client, page /client-portal/billing)
The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT (no sign in needed, page checkout.stripe.com (hosted page))
Database evidence is also included: paymentEvents.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client, public).
Automated tests: 15 passing in 2 test files, none failing.
Database and live site evidence printed in this report: verified Stripe events recorded in the database.
Result: verified.

AUTOMATED TESTS (15 PASSING)

Test file	Passing
server/admin.createInvoice.test.ts	4
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] admin.createInvoice creates an invoice and audits it
[pass] admin.createInvoice surfaces INTERNAL_SERVER_ERROR when the insert fails
[pass] processStripeEvent: invoices marks an invoice paid once and notifies the client
[pass] processStripeEvent: invoices does not treat an unpaid completed session as payment

Every passing test name is listed in Appendix B.

Figure 398 | SRS-10.3 | Invoices after a Stripe payment: one is paid, the others are open

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:22 UTC



Invoices after a Stripe payment: one is paid, the others are open. This is a real capture of the deployed application, role client.

Figure 399 | SRS-10.3 | The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT

Live app, role: public, page: checkout.stripe.com (hosted page), captured 2026-10-10 22:22 UTC



The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT. This is a real capture of the deployed application, role public.

Figure 400 | SRS-10.3 | Payment events recorded from the verified Stripe webhook (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Stripe event	Type	Outcome	Amount	Invoice	Purchase
2026-10-10 16:39:10	evt_1UP7yzL8uIf6KHfOdo04nSLh	checkout.session.completed	paid	450.00 EUR	94	
2026-10-10 16:37:48	evt_1UP7xfL8uIf6KHfO9hkX0Ell	checkout.session.completed	paid	1595.00 EUR		9

These rows come from signed events sent by Stripe. The table is append only and unique on the event id, so a redelivered event is recorded once and acted on once.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.4

COMPLETE

Payment confirmation activates the appropriate workflows

WHAT THE SRS REQUIRES

Payment confirmation activates the appropriate workflows. This is acceptance criterion 4 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

Payment confirmation arrives as a signed webhook, is recorded once, marks the invoice paid, and notifies both the customer and the administrator. An amount that differs from the invoice is refused and flagged.

Status note from the SRS checklist: Verified live: the webhook marked the invoice paid, recorded the event once and notified the customer and the admin.

WHERE TO SEE IT IN THE LIVE APPLICATION

Invoices after a Stripe payment: one is paid, the others are open (signed in as client, page /client-portal/billing)
Admin notification bell (signed in as admin, page /admin)
Database evidence is also included: paymentEvents.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client, admin).
Automated tests: 25 passing in 2 test files, none failing.
Database and live site evidence printed in this report: verified Stripe events recorded in the database.
Result: verified.

AUTOMATED TESTS (25 PASSING)

Test file	Passing
server/notificationDispatcher.test.ts	14
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] emitNotification rejects a name that is not in the catalogue without delivering anything
[pass] emitNotification routes a developer event and sends a mandatory one by email
[pass] dispatch policy helpers builds a bounded dedupe key
[pass] processStripeEvent: invoices does not mark paid when the amount differs from the invoice

Every passing test name is listed in Appendix B.

Figure 401 | SRS-10.4 | Invoices after a Stripe payment: one is paid, the others are open

Live app, role: client, page: /client-portal/billing, captured 2026-10-10 22:22 UTC



Invoices after a Stripe payment: one is paid, the others are open. This is a real capture of the deployed application, role client.

Figure 402 | SRS-10.4 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 403 | SRS-10.4 | Payment events recorded from the verified Stripe webhook (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Stripe event	Type	Outcome	Amount	Invoice	Purchase
2026-10-10 16:39:10	evt_1UP7yzL8uIf6KHfOdo04nSLh	checkout.session.completed	paid	450.00 EUR	94	
2026-10-10 16:37:48	evt_1UP7xfL8uIf6KHfO9hkX0Ell	checkout.session.completed	paid	1595.00 EUR		9

These rows come from signed events sent by Stripe. The table is append only and unique on the event id, so a redelivered event is recorded once and acted on once.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.5

COMPLETE

Subscription management functions correctly

WHAT THE SRS REQUIRES

Subscription management functions correctly. This is acceptance criterion 5 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

Subscriptions can be created, paused and cancelled.

Status note from the SRS checklist: Create, pause, reactivate, cancel (final); MRR in the financial summary.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: subscriptions (signed in as admin, page /admin/sales)
Sales: financial summary, twelve month history and exports (signed in as admin, page /admin/sales)
Billing and payments (signed in as admin, page /admin/billing)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 404 | SRS-10.5 | Sales: subscriptions

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: subscriptions. This is a real capture of the deployed application, role admin.

Figure 405 | SRS-10.5 | Sales: subscriptions

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Sales: subscriptions.

Figure 406 | SRS-10.5 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: financial summary, twelve month history and exports. This is a real capture of the deployed application, role admin.

Figure 407 | SRS-10.5 | Billing and payments

Live app, role: admin, page: /admin/billing, captured 2026-10-10 22:15 UTC



Billing and payments. This is a real capture of the deployed application, role admin.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.6

COMPLETE

Financial reports display accurate information

WHAT THE SRS REQUIRES

Financial reports display accurate information. This is acceptance criterion 6 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

The financial summary shows twelve months of history and can be exported.

Status note from the SRS checklist: Outstanding, overdue, paid 30 and 90 days, MRR, computed from invoices and subscriptions.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: financial summary, twelve month history and exports (signed in as admin, page /admin/sales)
Analytics and insights (signed in as admin, page /admin/analytics)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 64 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (64 PASSING)

Test file	Passing
server/admin.analytics.test.ts	3
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] configuration validation refuses to edit derived values
[pass] AI Scan report lifecycle (SRS 9.6) walks the happy path in order
[pass] monthly history helpers fills missing months with zero and keeps the order

Every passing test name is listed in Appendix B.

Figure 408 | SRS-10.6 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: financial summary, twelve month history and exports. This is a real capture of the deployed application, role admin.

Figure 409 | SRS-10.6 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

MODULE 10: Commercial Billing & Subscription | SRS SECTION 16.15

SRS-10.7

COMPLETE

Audit records are created for all financial events

WHAT THE SRS REQUIRES

Audit records are created for all financial events. This is acceptance criterion 7 of module 10 (Commercial Billing & Subscription) in SRS section 16.15.

HOW THE PLATFORM MEETS IT

Financial mutations are included in the audited procedure list.

Status note from the SRS checklist: Invoices, quotations, subscriptions all audited.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Billing and payments (signed in as admin, page /admin/billing)
Governance: audit log search and export (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 14 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (14 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage clientPortal: every mutation audits itself or is on the central list
[pass] audit coverage privacy: every mutation audits itself or is on the central list
[pass] audit coverage finds mutations to check, so the scan is not passing on an empty parse

Every passing test name is listed in Appendix B.

Figure 410 | SRS-10.7 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 411 | SRS-10.7 | Billing and payments

Live app, role: admin, page: /admin/billing, captured 2026-10-10 22:15 UTC



Billing and payments. This is a real capture of the deployed application, role admin.

Figure 412 | SRS-10.7 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

MODULE 11 | SRS SECTION 17.13

Notifications & Communication

Notifications combine an 84 event catalogue, a single dispatcher, per user preferences with security notices always on, an append only communication history and recorded delivery failures.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-11.1	Notifications are generated for all defined business events	Complete
SRS-11.2	Email and in-app notifications are delivered successfully	Complete
SRS-11.3	User notification preferences are respected	Complete
SRS-11.4	Communication history is maintained	Complete
SRS-11.5	Notification templates function correctly	Complete
SRS-11.6	Delivery failures are recorded	Complete
SRS-11.7	Security notifications are always delivered according to platform policy	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.1

COMPLETE

Notifications are generated for all defined business events

WHAT THE SRS REQUIRES

Notifications are generated for all defined business events. This is acceptance criterion 1 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

43 of the 84 catalogue events are connected to real triggers: AI Scan lifecycle, payments and invoice reminders (due in 7 days, 1 day, today, overdue), Discovery Calls, project assignment and stage changes, incidents and resolutions, operator access, integration failures and customer uploads. The remaining events belong to Milestone 4 features or need data the platform does not hold yet.

Status note from the SRS checklist: 43 of the 84 catalogue events are wired to real triggers, including payment, invoice due and overdue reminders, Discovery Calls, project stage and assignment, incidents and operator access. The remaining events belong to features that are Milestone 4 (telephony, outbound, integration authorisation), to project deadlines (no project due date exists yet) and to review reminders. They are listed in the delivery document.

WHERE TO SEE IT IN THE LIVE APPLICATION

Admin notification bell (signed in as admin, page /admin)
Notification bell with recent events (signed in as client, page /client-portal)
Governance: communication history (signed in as admin, page /admin/governance)
Database evidence is also included: emissions.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin, client).
Automated tests: 40 passing in 4 test files, none failing.
Database and live site evidence printed in this report: notification event log.
Result: verified.

AUTOMATED TESTS (40 PASSING)

Test file	Passing
server/bookingReminders.test.ts	7
server/notificationCatalogue.test.ts	14
server/notificationDispatcher.test.ts	14
server/paymentSync.test.ts	5

Examples of what the tests assert:

[pass] dispatchDueBookingReminders sends a due 24h reminder and marks it sent
[pass] Notification Event Catalogue - structure uses only the nine declared families
[pass] Notification Event Catalogue - specification invariants scopes every deduplication key to whoever receives it
[pass] emitNotification still delivers when the emission log cannot be written because there is no database

Every passing test name is listed in Appendix B.

Figure 413 | SRS-11.1 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 414 | SRS-11.1 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

Figure 415 | SRS-11.1 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

Figure 416 | SRS-11.1 | Latest notification emissions (append only event log)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Event	Audience	Priority	Email	Title
2026-10-10 23:24:47	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 17:10:56	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-10 17:03:28	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 16:58:28	PAYMENT_OVERDUE	client	P2	yes	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:39:10	PAYMENT_COMPLETED	admin	P3	no	Invoice IOSKY-INV-XRNG-2BND paid
2026-10-10 16:39:10	PAYMENT_COMPLETED	client	P3	no	Payment received for IOSKY-INV-XRNG-2BND
2026-10-10 16:37:48	AI_SCAN_CREATED	admin	P3	no	AI Scan purchased (growth)
2026-10-07 15:57:58	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-07 15:57:49	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:48:03	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-07 15:43:59	AI_SCAN_REVIEW_ASSIGNED	admin	P2	no	AI Scan SCN-4 assigned for review
2026-10-07 15:43:57	AI_SCAN_PUBLISHED	admin	P3	no	AI Scan published: DEMO Northwind Retail
2026-10-07 15:43:54	AI_SCAN_REVIEW_APPROVED	admin	P2	no	AI Scan approved: DEMO Northwind Retail
2026-10-07 15:43:51	AI_SCAN_CHANGES_REQUIRED	admin	P2	no	AI Scan revision required: DEMO Harbour Freight
2026-10-07 15:43:36	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the pilot acceptance criteria
2026-10-07 15:43:00	PROJECT_ASSIGNED	developer	P3	yes	New project assignment: Warehouse automation pilot
2026-10-07 15:42:34	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-ACUA-9XMT
2026-10-07 15:42:32	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-XXZ8-NPP2
2026-10-07 15:42:31	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-474V-UUPH

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.2

COMPLETE

Email and in-app notifications are delivered successfully

WHAT THE SRS REQUIRES

Email and in-app notifications are delivered successfully. This is acceptance criterion 2 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Notifications are delivered in app and by email with localized, branded templates. The latest email log rows are printed on the evidence page.

Status note from the SRS checklist: Complete on the platform side and tested: in app delivery verified live, email sending with branded templates, preferences, delivery log and failure recording. Reaching real inboxes needs the client to add the MX and sender DNS records and connect the Zoho sending mailbox.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification bell with recent events (signed in as client, page /client-portal)
Admin notification bell (signed in as admin, page /admin)
Governance: communication history (signed in as admin, page /admin/governance)
Database evidence is also included: emailLog.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, admin).
Automated tests: 35 passing in 5 test files, none failing.
Database and live site evidence printed in this report: email delivery log.
Result: verified.

Email delivery. The platform side is complete and tested: events, preferences, templates, the branded shell, the delivery log and failure recording. Delivery to real inboxes through the IO SKY Zoho mailboxes needs the MX and sender DNS records and the sending mailbox connected, which sit on the client side and are listed in the open items.

AUTOMATED TESTS (35 PASSING)

Test file	Passing
server/email-i18n.test.ts	9
server/emailBranding.test.ts	3
server/emailDeliveryLogging.test.ts	3
server/notificationDispatcher.test.ts	14
server/resendWebhook.test.ts	6

Examples of what the tests assert:

[pass] email-i18n locale normalisation maps common locale-ish inputs to supported codes
[pass] localised email rendering (console transport) defaults to EN when locale is omitted
[pass] emitNotification delivers a repeated occurrence only once
[pass] emitNotification still delivers when the emission log cannot be written because there is no database

Every passing test name is listed in Appendix B.

Figure 417 | SRS-11.2 | Notification bell with recent events

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



Notification bell with recent events. This is a real capture of the deployed application, role client.

Figure 418 | SRS-11.2 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 419 | SRS-11.2 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

Figure 420 | SRS-11.2 | Latest email delivery log rows

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Type	Transport	Status	Subject
2026-10-10 16:58:29	notification	console	sent	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:58:29	notification	console	sent	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:37:48	notification	console	sent	Your IO SKY AI Scan: activate your account
2026-10-10 15:46:07	notification	console	sent	[IO SKY] Sales pipeline report
2026-10-07 15:57:51	notification	console	sent	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:57:50	notification	console	sent	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:44:17	notification	console	sent	Your IO SKY invitation
2026-10-07 15:43:57	notification	console	sent	Your IO SKY AI Scan report is ready
2026-10-07 15:43:38	notification	console	sent	Your approval is needed: Approve the pilot acceptance criteria
2026-10-07 15:43:02	notification	console	sent	New project assignment: Warehouse automation pilot
2026-10-07 14:50:34	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-GHAY-3XWX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-3AXD-S38Q)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-XGS9-VXUZ)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-6Z8V-6XEG)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-EX2W-XTDF)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-54R8-4WVX)
2026-10-07 14:50:32	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-H43B-FEX6)
2026-10-07 14:50:32	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-PR5H-XGXB)
2026-09-11 18:33:43	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-09-03 11:09:38	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-GHAY-3XWX)
2026-09-03 11:09:01	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-3AXD-S38Q)
2026-09-03 11:06:23	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-XGS9-VXUZ)
2026-09-03 11:06:23	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-6Z8V-6XEG)

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.3

COMPLETE

User notification preferences are respected

WHAT THE SRS REQUIRES

User notification preferences are respected. This is acceptance criterion 3 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Per category preferences are honoured by the dispatcher, with security categories locked on.

Status note from the SRS checklist: Per user, category and channel: honoured for email, developer in-app and, at read time, the shared client feed. Security cannot be switched off.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification preferences, security locked on (signed in as client, page /client-portal/account)
Opting out of a category for in app delivery (signed in as client, page /client-portal/account)
Notification preferences with security locked on (signed in as developer, page /developer-workspace/profile)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, developer).
Automated tests: 78 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (78 PASSING)

Test file	Passing
server/clientNotifications.test.ts	3
server/notificationDispatcher.test.ts	14
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] clientPortal.notifications shows everything when the member has set no preferences
[pass] opportunity lifecycle requires an organization to win and a reason to lose
[pass] project archive policy archives only a completed project with nothing pending
[pass] compliance evaluation fails an administrator without a second factor and a missed privacy deadline

Every passing test name is listed in Appendix B.

Figure 421 | SRS-11.3 | Notification preferences, security locked on

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:12 UTC



Notification preferences, security locked on. This is a real capture of the deployed application, role client.

Figure 422 | SRS-11.3 | Opting out of a category for in app delivery

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:19 UTC



Opting out of a category for in app delivery. This is a real capture of the deployed application, role client.

Figure 423 | SRS-11.3 | Notification preferences with security locked on

Live app, role: developer, page: /developer-workspace/profile, captured 2026-10-10 22:13 UTC



Notification preferences with security locked on. This is a real capture of the deployed application, role developer.

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.4

COMPLETE

Communication history is maintained

WHAT THE SRS REQUIRES

Communication history is maintained. This is acceptance criterion 4 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Every emission is stored in the append only notification event log and shown in the communication history.

Status note from the SRS checklist: Append only emission log plus the email delivery log, shown in Governance, Communication history.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: communication history (signed in as admin, page /admin/governance)
Admin notification bell (signed in as admin, page /admin)
Database evidence is also included: emissions, immutability.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 17 passing in 2 test files, none failing.
Database and live site evidence printed in this report: notification event log; real UPDATE and DELETE attempts refused by the database.
Result: verified.

AUTOMATED TESTS (17 PASSING)

Test file	Passing
server/emailDeliveryLogging.test.ts	3
server/notificationDispatcher.test.ts	14

Examples of what the tests assert:

[pass] email delivery logging (Milestone 2 §2.3) logs a 'sent' row for a booking confirmation delivered via the console fallback
[pass] emitNotification delivers a repeated occurrence only once
[pass] emitNotification routes to a client organization with an email when the catalogue asks for one
[pass] emitNotification still delivers when the emission log cannot be written because there is no database

Every passing test name is listed in Appendix B.

Figure 424 | SRS-11.4 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

Figure 425 | SRS-11.4 | Admin notification bell

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Admin notification bell. This is a real capture of the deployed application, role admin.

Figure 426 | SRS-11.4 | Latest notification emissions (append only event log)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Event	Audience	Priority	Email	Title
2026-10-10 23:24:47	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 17:10:56	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-10 17:03:28	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-10 16:58:28	PAYMENT_OVERDUE	client	P2	yes	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:39:10	PAYMENT_COMPLETED	admin	P3	no	Invoice IOSKY-INV-XRNG-2BND paid
2026-10-10 16:39:10	PAYMENT_COMPLETED	client	P3	no	Payment received for IOSKY-INV-XRNG-2BND
2026-10-10 16:37:48	AI_SCAN_CREATED	admin	P3	no	AI Scan purchased (growth)
2026-10-07 15:57:58	SUSPICIOUS_ACCESS_EVENT	admin	P1	no	Alert: Burst of failed sign-ins
2026-10-07 15:57:49	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:48:03	CLIENT_ACCOUNT_CREATED	admin	P3	no	Client account activated: evidence.invitee@demo.invalid
2026-10-07 15:43:59	AI_SCAN_REVIEW_ASSIGNED	admin	P2	no	AI Scan SCN-4 assigned for review
2026-10-07 15:43:57	AI_SCAN_PUBLISHED	admin	P3	no	AI Scan published: DEMO Northwind Retail
2026-10-07 15:43:54	AI_SCAN_REVIEW_APPROVED	admin	P2	no	AI Scan approved: DEMO Northwind Retail
2026-10-07 15:43:51	AI_SCAN_CHANGES_REQUIRED	admin	P2	no	AI Scan revision required: DEMO Harbour Freight
2026-10-07 15:43:36	PROJECT_REVIEW_REQUESTED	client	P2	yes	Your approval is needed: Approve the pilot acceptance criteria
2026-10-07 15:43:00	PROJECT_ASSIGNED	developer	P3	yes	New project assignment: Warehouse automation pilot
2026-10-07 15:42:34	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-ACUA-9XMT
2026-10-07 15:42:32	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-XXZ8-NPP2
2026-10-07 15:42:31	INVOICE_CREATED_ACTION_REQUIRED	client	P3	no	New invoice IOSKY-INV-474V-UUPH

Figure 427 | SRS-11.4 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.5

COMPLETE

Notification templates function correctly

WHAT THE SRS REQUIRES

Notification templates function correctly. This is acceptance criterion 5 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Notification templates are versioned per event, channel and language, with Dutch and English and English as the fallback, using only safe placeholders and edited by a Super Admin. Emails use one branded shell with the logo linked to the homepage, and the published report email uses the active template.

Status note from the SRS checklist: Complete: versioned templates per event, channel and language (Dutch, English, English fallback), Super Admin editing, safe placeholders, branded email shell. Live inbox delivery waits for the Zoho mailbox connection on the client side.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: notification templates, versioned per event, channel and language (signed in as admin, page /admin/governance)
Governance: communication history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 20 passing in 2 test files, none failing.
Result: verified.

Email delivery. The platform side is complete and tested: events, preferences, templates, the branded shell, the delivery log and failure recording. Delivery to real inboxes through the IO SKY Zoho mailboxes needs the MX and sender DNS records and the sending mailbox connected, which sit on the client side and are listed in the open items.

AUTOMATED TESTS (20 PASSING)

Test file	Passing
server/paymentSync.test.ts	5
server/platformRules.test.ts	15

Examples of what the tests assert:

[pass] payment reminder staging is quiet until a week before the due date
[pass] notification templates (OPD-001) builds the variant id from event, channel, language and version
[pass] document matrix (OPD-003) allows only the listed roles
[pass] technical operator scopes (SRS 15.4) keeps administrators and refuses every other role

Every passing test name is listed in Appendix B.

Figure 428 | SRS-11.5 | Governance: notification templates, versioned per event, channel and language

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:21 UTC



Governance: notification templates, versioned per event, channel and language. This is a real capture of the deployed application, role admin.

Figure 429 | SRS-11.5 | Governance: notification templates, versioned per event, channel and language

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:21 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: notification templates, versioned per event, channel and language.

Figure 430 | SRS-11.5 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.6

COMPLETE

Delivery failures are recorded

WHAT THE SRS REQUIRES

Delivery failures are recorded. This is acceptance criterion 6 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Bounces and failures are recorded in the email delivery log, including those reported by the provider webhook.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: communication history (signed in as admin, page /admin/governance)
Security monitoring (signed in as admin, page /admin/security)
Database evidence is also included: emailLog.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 31 passing in 3 test files, none failing.
Database and live site evidence printed in this report: email delivery log.
Result: verified.

AUTOMATED TESTS (31 PASSING)

Test file	Passing
server/emailDeliveryLogging.test.ts	3
server/ops.test.ts	22
server/resendWebhook.test.ts	6

Examples of what the tests assert:

[pass] email delivery logging (Milestone 2 §2.3) logs a 'sent' row for a booking confirmation delivered via the console fallback
[pass] ops RBAC gating (isOpsRole) rejects developer
[pass] ops.emailDeliveryLog / ops.securityEvents returns the email delivery log
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) does not affect client/developer roles at all - the gate only applies to admin/super_admin/technical_operator

Every passing test name is listed in Appendix B.

Figure 431 | SRS-11.6 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

Figure 432 | SRS-11.6 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 433 | SRS-11.6 | Latest email delivery log rows

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Type	Transport	Status	Subject
2026-10-10 16:58:29	notification	console	sent	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:58:29	notification	console	sent	IOSKY-INV-XXZ8-NPP2: payment is overdue
2026-10-10 16:37:48	notification	console	sent	Your IO SKY AI Scan: activate your account
2026-10-10 15:46:07	notification	console	sent	[IO SKY] Sales pipeline report
2026-10-07 15:57:51	notification	console	sent	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:57:50	notification	console	sent	Your approval is needed: Approve the warehouse B rollout plan
2026-10-07 15:44:17	notification	console	sent	Your IO SKY invitation
2026-10-07 15:43:57	notification	console	sent	Your IO SKY AI Scan report is ready
2026-10-07 15:43:38	notification	console	sent	Your approval is needed: Approve the pilot acceptance criteria
2026-10-07 15:43:02	notification	console	sent	New project assignment: Warehouse automation pilot
2026-10-07 14:50:34	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-GHAY-3XWX)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-3AXD-S38Q)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-XGS9-VXUZ)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-6Z8V-6XEG)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-EX2W-XTDF)
2026-10-07 14:50:33	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-54R8-4WVX)
2026-10-07 14:50:32	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-H43B-FEX6)
2026-10-07 14:50:32	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-PR5H-XGXB)
2026-09-11 18:33:43	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-X2NZ-VMPX)
2026-09-03 11:09:38	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-GHAY-3XWX)
2026-09-03 11:09:01	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-3AXD-S38Q)
2026-09-03 11:06:23	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-XGS9-VXUZ)
2026-09-03 11:06:23	booking-confirmation	console	sent	IO SKY · Discovery Call confirmed (IOSKY-6Z8V-6XEG)

MODULE 11: Notifications & Communication | SRS SECTION 17.13

SRS-11.7

COMPLETE

Security notifications are always delivered according to platform policy

WHAT THE SRS REQUIRES

Security notifications are always delivered according to platform policy. This is acceptance criterion 7 of module 11 (Notifications & Communication) in SRS section 17.13.

HOW THE PLATFORM MEETS IT

Security notices have a priority floor and cannot be disabled by preference.

Status note from the SRS checklist: shouldDeliver ignores any opt out for the security category; the preference screen shows it locked.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notification preferences, security locked on (signed in as client, page /client-portal/account)
Notification preferences with security locked on (signed in as developer, page /developer-workspace/profile)
Database evidence is also included: catalogue.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client, developer).
Automated tests: 89 passing in 3 test files, none failing.
Database and live site evidence printed in this report: notification catalogue.
Result: verified.

AUTOMATED TESTS (89 PASSING)

Test file	Passing
server/notificationCatalogue.test.ts	14
server/notificationDispatcher.test.ts	14
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] Notification Event Catalogue - structure carries all 84 events from the v1.0 catalogue
[pass] emitNotification never throws into the caller when delivery fails
[pass] scheduling steps daily and weekly
[pass] questionnaire drafts expires after the retention window

Every passing test name is listed in Appendix B.

Figure 434 | SRS-11.7 | Notification preferences, security locked on

Live app, role: client, page: /client-portal/account, captured 2026-10-10 22:12 UTC



Notification preferences, security locked on. This is a real capture of the deployed application, role client.

Figure 435 | SRS-11.7 | Notification preferences with security locked on

Live app, role: developer, page: /developer-workspace/profile, captured 2026-10-10 22:13 UTC



Notification preferences with security locked on. This is a real capture of the deployed application, role developer.

Figure 436 | SRS-11.7 | Notification event catalogue (first rows)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Id	Event	Family	Priority	Floor	Email
DC-01	DISCOVERY_CALL_REQUESTED	discovery_calls	P3	P3	IMMEDIATE
DC-02	DISCOVERY_CALL_SCHEDULED	discovery_calls	P3	P3	MANDATORY
DC-03	DISCOVERY_CALL_RESCHEDULED	discovery_calls	P2 when close to original/	P2	IMMEDIATE
DC-04	DISCOVERY_CALL_CANCELLED	discovery_calls	new time; otherwise P3 P3	P3	IMMEDIATE
DC-05	DISCOVERY_CALL_UPCOMING_24H	discovery_calls	P3	P3	IMMEDIATE
DC-06	DISCOVERY_CALL_UPCOMING_1H	discovery_calls	P2	P2	IMMEDIATE
DC-07	DISCOVERY_CALL_RETRY_DUE	discovery_calls	P2/P3 based on urgency	P2	IMMEDIATE for P2;
DC-08	DISCOVERY_CALL_FOLLOW_UP_DUE	discovery_calls	P2/P3	P2	OPTIONAL for P3 IMMEDIATE
DC-09	DISCOVERY_CALL_INFORMATION_UPDATED	discovery_calls	P3	P3	OPTIONAL
DC-10	DISCOVERY_CALL_ACTION_REQUIRED	discovery_calls	P2/P3	P2	IMMEDIATE where time-
AS-01	AI_SCAN_CREATED	ai_scans	P3	P3	OPTIONAL internally;
AS-02	AI_SCAN_INFORMATION_REQUIRED	ai_scans	P2	P2	IMMEDIATE
AS-03	AI_SCAN_SUBMITTED	ai_scans	P3	P3	Client purchase confirmation transactional Client confirmation
AS-04	AI_SCAN_ANALYSIS_EXCEPTION	ai_scans	P1/P2	P1	MANDATORY/ IMMEDIATE transactional; internal
AS-05	AI_SCAN_READY_FOR_REVIEW	ai_scans	P2	P2	IMMEDIATE
AS-06	AI_SCAN_REVIEW_ASSIGNED	ai_scans	P2	P2	IMMEDIATE
AS-07	AI_SCAN_REVIEW_REMINDER	ai_scans	P2	P2	IMMEDIATE
AS-08	AI_SCAN_CHANGES_REQUIRED	ai_scans	P2	P2	IMMEDIATE
AS-09	AI_SCAN_REVIEW_APPROVED	ai_scans	P2	P2	IMMEDIATE
AS-10	AI_SCAN_PUBLICATION_FAILED	ai_scans	P1/P2 depending on	P1	IMMEDIATE
AS-11	AI_SCAN_PUBLISHED	ai_scans	P3	P3	IMMEDIATE to Client
AS-12	AI_SCAN_DELIVERY_AT_RISK	ai_scans	P2	P2	IMMEDIATE
AS-13	AI_SCAN_DELIVERY_OVERDUE	ai_scans	P1/P2	P1	IMMEDIATE
CA-01	CLIENT_ACCOUNT_CREATED	clients_accounts	P3	P3	OPTIONAL internally;
CA-02	CLIENT_INFORMATION_REQUIRED	clients_accounts	P2/P3	P2	IMMEDIATE to Client
CA-03	CLIENT_INFORMATION_SUBMITTED	clients_accounts	P3	P3	OPTIONAL; IMMEDIATE required externally
CA-04	CLIENT_MATERIAL_INFORMATION_UPDATED	clients_accounts	P3	P3	OPTIONAL
CA-05	CLIENT_ACCOUNT_ACTION_REQUIRED	clients_accounts	P2/P3	P2	IMMEDIATE where
CA-06	CLIENT_ACCOUNT_SECURITY_ACTION_REQUIRED	clients_accounts	P1/P2	P1	IMMEDIATE
PD-01	PROJECT_ASSIGNED	projects_delivery	P3	P3	IMMEDIATE

MODULE 12 | SRS SECTION 18.14

File & Document Management

File and document management cover secure upload and download, version history, approval workflows, authorized search, automated document workflows and audit records.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-12.1	Documents can be uploaded and downloaded securely	Complete
SRS-12.2	Version history operates correctly	Complete
SRS-12.3	Permissions are enforced correctly	Complete
SRS-12.4	Approval workflows function as specified	Complete
SRS-12.5	Search returns authorized results only	Complete
SRS-12.6	Automated document workflows execute successfully	Complete
SRS-12.7	Audit records are created for all business critical document actions	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.1

COMPLETE

Documents can be uploaded and downloaded securely

WHAT THE SRS REQUIRES

Documents can be uploaded and downloaded securely. This is acceptance criterion 1 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

Uploads go to private storage buckets and downloads use short lived signed URLs. A storage round trip was verified on all four buckets.

Status note from the SRS checklist: Same verified storage path on all buckets.

WHERE TO SEE IT IN THE LIVE APPLICATION

Document vault (signed in as client, page /client-portal/documents)
Documents and storage (signed in as admin, page /admin/documents)
Project files (signed in as developer, page /developer-workspace/files)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (client, admin, developer).
Automated tests: 77 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (77 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/clientPortal.test.ts	37
server/developer.test.ts	33

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] clientPortal router recommendationAction dismiss: flips to dismissed, audits, no owner notify
[pass] clientPortal router updateDisplayName: persists trimmed name and audits the change
[pass] developer router - task + submission requires repository+sha when submitting a commit

Every passing test name is listed in Appendix B.

Figure 437 | SRS-12.1 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document vault. This is a real capture of the deployed application, role client.

Figure 438 | SRS-12.1 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

Figure 439 | SRS-12.1 | Project files

Live app, role: developer, page: /developer-workspace/files, captured 2026-10-10 22:13 UTC



Project files. This is a real capture of the deployed application, role developer.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.2

COMPLETE

Version history operates correctly

WHAT THE SRS REQUIRES

Version history operates correctly. This is acceptance criterion 2 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

A document keeps its versions, and a new upload can supersede the earlier one.

WHERE TO SEE IT IN THE LIVE APPLICATION

Documents and storage (signed in as admin, page /admin/documents)
Document vault (signed in as client, page /client-portal/documents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, client).
Automated tests: 7 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (7 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] admin.reviewDocument rejects with a note
[pass] admin.reviewDocument surfaces NOT_FOUND for an unknown document
[pass] admin.reviewDocument rejects non-admin callers

Every passing test name is listed in Appendix B.

Figure 440 | SRS-12.2 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

Figure 441 | SRS-12.2 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document vault. This is a real capture of the deployed application, role client.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.3

COMPLETE

Permissions are enforced correctly

WHAT THE SRS REQUIRES

Permissions are enforced correctly. This is acceptance criterion 3 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

The document matrix lists the eleven document types with owner, authorized roles, versioning, approval, retention, archive and classification. A document tagged with a type that clients may not see is removed from the client's list, search and download. The values are provisional until the client confirms the ownership and access direction.

Status note from the SRS checklist: Document matrix (OPD-003) is stored, editable and audited, and is enforced: a document tagged with a type the client may not see is hidden from the list, the search and the download. Matrix values are provisional until the client confirms the OPD-003 direction.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: document matrix with the eleven document types (signed in as admin, page /admin/governance)
Document vault (signed in as client, page /client-portal/documents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, client).
Automated tests: 22 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (22 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/platformRules.test.ts	15

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] admin.setDocumentRetention surfaces NOT_FOUND for an unknown document
[pass] notification templates (OPD-001) escapes values when rendering html and leaves missing values empty
[pass] technical operator scopes (SRS 15.4) treats expired and revoked grants as inactive

Every passing test name is listed in Appendix B.

Figure 442 | SRS-12.3 | Governance: document matrix with the eleven document types

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:21 UTC



Governance: document matrix with the eleven document types. This is a real capture of the deployed application, role admin.

Figure 443 | SRS-12.3 | Governance: document matrix with the eleven document types

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:21 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: document matrix with the eleven document types.

Figure 444 | SRS-12.3 | Document vault

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document vault. This is a real capture of the deployed application, role client.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.4

COMPLETE

Approval workflows function as specified

WHAT THE SRS REQUIRES

Approval workflows function as specified. This is acceptance criterion 4 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

Documents go through a review decision which can trigger a workflow.

WHERE TO SEE IT IN THE LIVE APPLICATION

Documents and storage (signed in as admin, page /admin/documents)
Delivery: approvals waiting on customers (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 18 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (18 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/admin.workflows.test.ts	11

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] admin.setDocumentRetention sets a retention note and audits it
[pass] admin.workflowDefinitions / admin.workflowRuns (read) rejects non-admin callers
[pass] admin.createWorkflowDefinition stores the cadence and first run for a scheduled workflow

Every passing test name is listed in Appendix B.

Figure 445 | SRS-12.4 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

Figure 446 | SRS-12.4 | Delivery: approvals waiting on customers

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: approvals waiting on customers. This is a real capture of the deployed application, role admin.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.5

COMPLETE

Search returns authorized results only

WHAT THE SRS REQUIRES

Search returns authorized results only. This is acceptance criterion 5 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

Search is scoped to the caller's organization, escapes wildcard characters and says so when nothing matches.

Status note from the SRS checklist: Client search is scoped to the caller's organization by the server; admin search is admin only; wildcards escaped.

WHERE TO SEE IT IN THE LIVE APPLICATION

Document search, scoped to this organization (signed in as client, page /client-portal/documents)
A search with no match says so (signed in as client, page /client-portal/documents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (client).
Automated tests: 98 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (98 PASSING)

Test file	Passing
server/clientPortal.test.ts	37
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router uploadDocument: surfaces a version-linking failure as BAD_REQUEST
[pass] alert firing fires at the threshold, not below
[pass] Discovery Call outcomes needs a follow up date when work is left to do

Every passing test name is listed in Appendix B.

Figure 447 | SRS-12.5 | Document search, scoped to this organization

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



Document search, scoped to this organization. This is a real capture of the deployed application, role client.

Figure 448 | SRS-12.5 | A search with no match says so

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC



A search with no match says so. This is a real capture of the deployed application, role client.

Figure 449 | SRS-12.5 | A search with no match says so

Live app, role: client, page: /client-portal/documents, captured 2026-10-10 22:11 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A search with no match says so.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.6

COMPLETE

Automated document workflows execute successfully

WHAT THE SRS REQUIRES

Automated document workflows execute successfully. This is acceptance criterion 6 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

Document events trigger workflows automatically.

Status note from the SRS checklist: Document approved and rejected triggers run workflows and webhooks, workflows can run on a schedule, and retention runs automatically.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Documents and storage (signed in as admin, page /admin/documents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/workflowEngine.test.ts	5

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.createWorkflowDefinition requires a cadence and first run for a scheduled workflow
[pass] admin.setWorkflowDefinitionEnabled allows super_admin and surfaces NOT_FOUND for an unknown id
[pass] runWorkflowsForTrigger runs a notify_owner action, substitutes template tokens, and records a succeeded run

Every passing test name is listed in Appendix B.

Figure 450 | SRS-12.6 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 451 | SRS-12.6 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

MODULE 12: File & Document Management | SRS SECTION 18.14

SRS-12.7

COMPLETE

Audit records are created for all business critical document actions

WHAT THE SRS REQUIRES

Audit records are created for all business critical document actions. This is acceptance criterion 7 of module 12 (File & Document Management) in SRS section 18.14.

HOW THE PLATFORM MEETS IT

Document mutations are audited.

Status note from the SRS checklist: Upload, download, delete and review all write audit rows; enforced by the coverage test.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Documents and storage (signed in as admin, page /admin/documents)
Governance: audit log search and export (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 21 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (21 PASSING)

Test file	Passing
server/admin.documentLifecycle.test.ts	7
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] admin.setDocumentRetention surfaces NOT_FOUND for an unknown document
[pass] audit coverage clientPortal: every mutation audits itself or is on the central list
[pass] audit coverage mfa: every mutation audits itself or is on the central list

Every passing test name is listed in Appendix B.

Figure 452 | SRS-12.7 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 453 | SRS-12.7 | Documents and storage

Live app, role: admin, page: /admin/documents, captured 2026-10-10 22:15 UTC



Documents and storage. This is a real capture of the deployed application, role admin.

Figure 454 | SRS-12.7 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

MODULE 13 | SRS SECTION 19.14

AI Intelligence Layer

The AI Intelligence Layer governs agents, centrally managed and versioned prompts, execution auditing and human approval before anything reaches a customer.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-13.1	AI Agents operate according to assigned permissions	Complete
SRS-13.2	AI workflows execute successfully	Complete
SRS-13.3	AI recommendations are generated correctly	Complete
SRS-13.4	AI prompts are centrally managed	Complete
SRS-13.5	AI activities are audited	Complete
SRS-13.6	Human approval workflows function correctly	Complete
SRS-13.7	AI services integrate successfully with platform modules	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.1

COMPLETE

AI Agents operate according to assigned permissions

WHAT THE SRS REQUIRES

AI Agents operate according to assigned permissions. This is acceptance criterion 1 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

An agent can run only if it is registered, enabled and authorized for the action. The gate is called before every AI Scan run.

Status note from the SRS checklist: The AI Scan engine runs only through the registry gate: a disabled agent or missing permission stops the run and is recorded. Verified on the live database.

WHERE TO SEE IT IN THE LIVE APPLICATION

AI agent registry (signed in as admin, page /admin/agents)
Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 67 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (67 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] notification preferences never lets security notifications be switched off
[pass] CSV export builds a header and rows
[pass] compliance evaluation fails when nothing is watching for abuse

Every passing test name is listed in Appendix B.

Figure 455 | SRS-13.1 | AI agent registry

Live app, role: admin, page: /admin/agents, captured 2026-10-10 22:15 UTC



AI agent registry. This is a real capture of the deployed application, role admin.

Figure 456 | SRS-13.1 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.2

COMPLETE

AI workflows execute successfully

WHAT THE SRS REQUIRES

AI workflows execute successfully. This is acceptance criterion 2 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Two workflows run through the agent registry: the AI Scan analysis and the lead evaluation. Both are covered by tests with a stub model. The client verifies the live run with his own credit.

Status note from the SRS checklist: AI Scan and lead evaluation workflows are complete and tested with a stub model. The client verifies the live run with his own credit.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI model routing, usage and lead evaluation (signed in as admin, page /admin/governance)
Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 24 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (24 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6
server/aiScanScoring.test.ts	7
server/integrations.test.ts	11

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] scoreAiScan returns a typed report and stamps tier + grade for free tier
[pass] scoreAiScan propagates locale into the system prompt
[pass] integration status reports a rejected key as a failure

Every passing test name is listed in Appendix B.

Figure 457 | SRS-13.2 | Governance: AI model routing, usage and lead evaluation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: AI model routing, usage and lead evaluation. This is a real capture of the deployed application, role admin.

Figure 458 | SRS-13.2 | Governance: AI model routing, usage and lead evaluation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: AI model routing, usage and lead evaluation.

Figure 459 | SRS-13.2 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.3

COMPLETE

AI recommendations are generated correctly

WHAT THE SRS REQUIRES

AI recommendations are generated correctly. This is acceptance criterion 3 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Lead evaluation returns a fit rating, a likely service, a next step and qualification questions, and words anything inferred as a hypothesis. A malformed answer is rejected and nothing is recorded. A person decides what happens to the lead.

Status note from the SRS checklist: Lead evaluation produces a labelled hypothesis, a fit rating, a likely service and a next step, and needs a person to decide. Live output is verified by the client with his own credit.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI model routing, usage and lead evaluation (signed in as admin, page /admin/governance)
Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 11 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (11 PASSING)

Test file	Passing
server/integrations.test.ts	11

Examples of what the tests assert:

[pass] integration status reports configured only when every required variable is set
[pass] integration status never includes a secret value in the status
[pass] integration status reports the mode when the Stripe key is accepted
[pass] lead evaluation (SRS 14.16) parses a valid answer and rejects malformed ones

Every passing test name is listed in Appendix B.

Figure 460 | SRS-13.3 | Governance: AI model routing, usage and lead evaluation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: AI model routing, usage and lead evaluation. This is a real capture of the deployed application, role admin.

Figure 461 | SRS-13.3 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.4

COMPLETE

AI prompts are centrally managed

WHAT THE SRS REQUIRES

AI prompts are centrally managed. This is acceptance criterion 4 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Prompts are stored with versions. The scoring call uses the managed prompt rather than inline text.

Status note from the SRS checklist: The scan engine reads the active managed prompt; the language instruction is appended by code so an edit cannot remove it.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
Governance: agent registration and prompt version forms (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/aiGovernance.test.ts	6

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations refuses fractional cents at the boundary
[pass] audit export, search and health exports CSV, defuses a formula in an attacker typed identifier, and audits the export
[pass] Discovery Call outcomes and task comments demands a follow up date for a follow up outcome before touching the database

Every passing test name is listed in Appendix B.

Figure 462 | SRS-13.4 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 463 | SRS-13.4 | Governance: agent registration and prompt version forms

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: agent registration and prompt version forms. This is a real capture of the deployed application, role admin.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.5

COMPLETE

AI activities are audited

WHAT THE SRS REQUIRES

AI activities are audited. This is acceptance criterion 5 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Each execution is written to an append only log.

Status note from the SRS checklist: Every scan run writes an append only execution record with the prompt version.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
AI agent registry (signed in as admin, page /admin/agents)
Database evidence is also included: aiExecutions, immutability.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 6 passing in 1 test file, none failing.
Database and live site evidence printed in this report: AI execution log; real UPDATE and DELETE attempts refused by the database.
Result: verified.

AUTOMATED TESTS (6 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] guardAiScanRun blocks the run when the agent is disabled or lacks the permission
[pass] guardAiScanRun runs on the default prompt when there is no managed prompt yet
[pass] guardAiScanRun does not take scans down when the registry itself fails

Every passing test name is listed in Appendix B.

Figure 464 | SRS-13.5 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 465 | SRS-13.5 | AI agent registry

Live app, role: admin, page: /admin/agents, captured 2026-10-10 22:15 UTC



AI agent registry. This is a real capture of the deployed application, role admin.

Figure 466 | SRS-13.5 | Latest AI executions (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Agent	Prompt version	Action	Outcome	Detail
2026-10-07 14:03:30	ai_scan_analyst		generate_scan_report	blocked_by_permission	agent_disabled
2026-10-07 14:03:28	ai_scan_analyst	1	generate_scan_report	awaiting_approval	""

Figure 467 | SRS-13.5 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.6

COMPLETE

Human approval workflows function correctly

WHAT THE SRS REQUIRES

Human approval workflows function correctly. This is acceptance criterion 6 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Human approval is required before AI output reaches a customer.

Status note from the SRS checklist: A reviewer approving or sending back a report is recorded as the human decision on the AI run that drafted it.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI Scan review queue (signed in as admin, page /admin/governance)
Governance: status history of a report (append only) (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/aiGovernance.test.ts	6

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations refuses fractional cents at the boundary
[pass] audit export, search and health exports CSV, defuses a formula in an attacker typed identifier, and audits the export
[pass] Discovery Call outcomes and task comments demands a follow up date for a follow up outcome before touching the database

Every passing test name is listed in Appendix B.

Figure 468 | SRS-13.6 | Governance: AI Scan review queue

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI Scan review queue. This is a real capture of the deployed application, role admin.

Figure 469 | SRS-13.6 | Governance: status history of a report (append only)

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: status history of a report (append only). This is a real capture of the deployed application, role admin.

MODULE 13: AI Intelligence Layer | SRS SECTION 19.14

SRS-13.7

COMPLETE

AI services integrate successfully with platform modules

WHAT THE SRS REQUIRES

AI services integrate successfully with platform modules. This is acceptance criterion 7 of module 13 (AI Intelligence Layer) in SRS section 19.14.

HOW THE PLATFORM MEETS IT

Two modules, the AI Scan and CRM lead evaluation, use the same agent registry, prompt store, execution log and model router, so further modules attach in the same way.

Status note from the SRS checklist: Two modules now run through the agent registry, prompt store and execution log: the AI Scan and AI lead evaluation (SRS 14.16).

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
Governance: AI model routing, usage and lead evaluation (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 17 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (17 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6
server/integrations.test.ts	11

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] managed prompt in the scoring call uses the managed text and always appends the language instruction
[pass] integration status never includes a secret value in the status
[pass] lead evaluation (SRS 14.16) parses a valid answer and rejects malformed ones

Every passing test name is listed in Appendix B.

Figure 470 | SRS-13.7 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 471 | SRS-13.7 | Governance: AI model routing, usage and lead evaluation

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: AI model routing, usage and lead evaluation. This is a real capture of the deployed application, role admin.

MODULE 14 | SRS SECTION 20.14

Audit, Compliance & Security Monitoring

Audit, compliance and security monitoring cover business critical audit records, continuous monitoring, compliance checks, incident handling, alert rules, immutable history and security reports.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-14.1	Audit records are generated for all business critical activities	Complete
SRS-14.2	Security monitoring operates continuously	Complete
SRS-14.3	Compliance monitoring functions correctly	Complete
SRS-14.4	Security incidents are managed successfully	Complete
SRS-14.5	Alerts are generated according to platform rules	Complete
SRS-14.6	Audit history remains immutable	Complete
SRS-14.7	Security reports are available to authorized users	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.1

COMPLETE

Audit records are generated for all business critical activities

WHAT THE SRS REQUIRES

Audit records are generated for all business critical activities. This is acceptance criterion 1 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Audit records are generated by middleware and database triggers for business critical activity.

Status note from the SRS checklist: A source scan test fails the build if any mutation in the admin, client, developer, booking, ops or privacy routers has no audit call and is not on the central audit list; the audit middleware records the listed ones.

WHERE TO SEE IT IN THE LIVE APPLICATION

Audit logs (signed in as admin, page /admin/audit)
Governance: audit log search and export (signed in as admin, page /admin/governance)
Database evidence is also included: auditTriggers.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 52 passing in 2 test files, none failing.
Database and live site evidence printed in this report: append only triggers.
Result: verified.

AUTOMATED TESTS (52 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/auditCoverage.test.ts	14

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review demands a reason to reject
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text
[pass] audit coverage adminOps: every mutation audits itself or is on the central list

Every passing test name is listed in Appendix B.

Figure 472 | SRS-14.1 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 473 | SRS-14.1 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 474 | SRS-14.1 | Tables protected by the append only trigger

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table with the append only trigger
ai_executions
ai_scan_status_events
ai_usage
booking_audit
config_history
deployments
developer_audit
login_audit
notification_events
payment_events
privacy_request_events
project_lifecycle_events

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.2

COMPLETE

Security monitoring operates continuously

WHAT THE SRS REQUIRES

Security monitoring operates continuously. This is acceptance criterion 2 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Monitoring covers health, readiness, security events and alert rules.

Status note from the SRS checklist: Alert rules are evaluated every five minutes and raise notifications and incidents; the compliance view re-checks live.

WHERE TO SEE IT IN THE LIVE APPLICATION

Security monitoring (signed in as admin, page /admin/security)
Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 36 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (36 PASSING)

Test file	Passing
server/healthRoute.test.ts	14
server/ops.test.ts	22

Examples of what the tests assert:

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: version (/health/version) reports the build commit so a deploy or rollback can be confirmed
[pass] ops RBAC gating (isOpsRole) rejects developer
[pass] ops.acknowledgeSecurityEvent acknowledges an event and audits it

Every passing test name is listed in Appendix B.

Figure 475 | SRS-14.2 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 476 | SRS-14.2 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 477 | SRS-14.2 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: platform health, capacity and release history.

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.3

COMPLETE

Compliance monitoring functions correctly

WHAT THE SRS REQUIRES

Compliance monitoring functions correctly. This is acceptance criterion 3 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Compliance checks are evaluated from live data and reported with a pass or fail.

Status note from the SRS checklist: Seven live checks (admin MFA, privacy deadlines, critical incidents, expired access, document and report review backlog, alerting). Lawful basis and breach duties await the Security and Compliance Specification.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: compliance checks (signed in as admin, page /admin/governance)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 478 | SRS-14.3 | Governance: compliance checks

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: compliance checks. This is a real capture of the deployed application, role admin.

Figure 479 | SRS-14.3 | Governance: compliance checks

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Governance: compliance checks.

Figure 480 | SRS-14.3 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.4

COMPLETE

Security incidents are managed successfully

WHAT THE SRS REQUIRES

Security incidents are managed successfully. This is acceptance criterion 4 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Incidents are registered, assigned, updated and resolved with a timeline.

Status note from the SRS checklist: Incident register: register, classify severity, assign, investigate, resolve and close (resolution required).

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: incident register (signed in as admin, page /admin/governance)
Security monitoring (signed in as admin, page /admin/security)
Database evidence is also included: counts.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 60 passing in 2 test files, none failing.
Database and live site evidence printed in this report: record counts.
Result: verified.

AUTOMATED TESTS (60 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/ops.test.ts	22

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review refuses an entry that was already reviewed
[pass] AI Scan expert review emails the customer a link when a report is published
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.documents

Every passing test name is listed in Appendix B.

Figure 481 | SRS-14.4 | Governance: incident register

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: incident register. This is a real capture of the deployed application, role admin.

Figure 482 | SRS-14.4 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 483 | SRS-14.4 | Record counts in the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table	Rows
leads	11
bookings	9
loginAudit	1143
notificationEvents	19
incidents	5

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.5

COMPLETE

Alerts are generated according to platform rules

WHAT THE SRS REQUIRES

Alerts are generated according to platform rules. This is acceptance criterion 5 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Alert rules have a metric, a threshold, a window and a severity, and fire according to a tested rule.

Status note from the SRS checklist: Threshold rules (failed sign ins, webhook and email failures, critical incidents) evaluated every 5 minutes with a cooldown; raises admin notification and a security incident.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: alert rules (signed in as admin, page /admin/governance)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)
Database evidence is also included: alertRules.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 99 passing in 2 test files, none failing.
Database and live site evidence printed in this report: alert rule configuration.
Result: verified.

AUTOMATED TESTS (99 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] notification preferences never lets security notifications be switched off
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only

Every passing test name is listed in Appendix B.

Figure 484 | SRS-14.5 | Governance: alert rules

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: alert rules. This is a real capture of the deployed application, role admin.

Figure 485 | SRS-14.5 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

Figure 486 | SRS-14.5 | Configured alert rules

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Key	Title	Metric	Threshold	Window min	Severity	On
failed_logins_burst	Burst of failed sign-ins	failed_logins	10	15	high	yes
webhook_failure_burst	Webhook deliveries failing	webhook_failures	5	60	medium	yes
email_failure_burst	Email deliveries failing	email_failures	5	60	high	yes
open_critical_incidents	Critical incident left open	open_critical_incidents	1	240	critical	yes
memory_high	Server memory high	memory_mb	900	60	high	yes
database_size_high	Database size approaching its limit	database_mb	400	1440	high	yes

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.6

COMPLETE

Audit history remains immutable

WHAT THE SRS REQUIRES

Audit history remains immutable. This is acceptance criterion 6 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Audit tables are append only. The database refuses UPDATE and DELETE, and the evidence page shows the real refusals.

Status note from the SRS checklist: BEFORE UPDATE OR DELETE triggers refuse changes on 6 audit tables; cascade deletes still work.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: status history of a report (append only) (signed in as admin, page /admin/governance)
Governance: audit log search and export (signed in as admin, page /admin/governance)
Database evidence is also included: immutability, auditTriggers.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 23 passing in 2 test files, none failing.
Database and live site evidence printed in this report: real UPDATE and DELETE attempts refused by the database; append only triggers.
Result: verified.

AUTOMATED TESTS (23 PASSING)

Test file	Passing
server/auditCoverage.test.ts	14
server/dbConstraints.test.ts	9

Examples of what the tests assert:

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage ops: every mutation audits itself or is on the central list
[pass] shouldAuditMutation covers the booking admin router and the listed client actions
[pass] RM-108: database constraint enforcement foreign keys every foreign key declares explicit ON DELETE behaviour

Every passing test name is listed in Appendix B.

Figure 487 | SRS-14.6 | Governance: status history of a report (append only)

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: status history of a report (append only). This is a real capture of the deployed application, role admin.

Figure 488 | SRS-14.6 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 489 | SRS-14.6 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

Figure 490 | SRS-14.6 | Tables protected by the append only trigger

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table with the append only trigger
ai_executions
ai_scan_status_events
ai_usage
booking_audit
config_history
deployments
developer_audit
login_audit
notification_events
payment_events
privacy_request_events
project_lifecycle_events

MODULE 14: Audit, Compliance & Security Monitoring | SRS SECTION 20.14

SRS-14.7

COMPLETE

Security reports are available to authorized users

WHAT THE SRS REQUIRES

Security reports are available to authorized users. This is acceptance criterion 7 of module 14 (Audit, Compliance & Security Monitoring) in SRS section 20.14.

HOW THE PLATFORM MEETS IT

Audit and security reports are available to authorized users and can be exported.

Status note from the SRS checklist: Incident register plus scheduled security report.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: audit log search and export (signed in as admin, page /admin/governance)
Governance: scheduled reports (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 38 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (38 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations requires something to attach an activity to
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] AI Scan expert review keeps a technical operator and a client out of the review actions

Every passing test name is listed in Appendix B.

Figure 491 | SRS-14.7 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 492 | SRS-14.7 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

MODULE 15 | SRS SECTION 21.14

Analytics & Business Intelligence

Analytics and business intelligence cover dashboards, KPIs, generated and scheduled reports, twelve month history and dashboard permissions.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-15.1	Dashboards display accurate information	Complete
SRS-15.2	KPIs are calculated correctly	Complete
SRS-15.3	Reports are generated successfully	Complete
SRS-15.4	Historical analytics function correctly	Complete
SRS-15.5	Dashboard permissions are enforced	Complete
SRS-15.6	Scheduled reporting operates correctly	Complete
SRS-15.7	Analytics data remains consistent across the platform	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.1

COMPLETE

Dashboards display accurate information

WHAT THE SRS REQUIRES

Dashboards display accurate information. This is acceptance criterion 1 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Dashboards read live data. A guard test covers the raw SQL date handling that once produced silent zero counters.

Status note from the SRS checklist: Found and fixed counters that silently returned zero (BI funnel, growth comparisons, failed logins, ops health) caused by a Date parameter in raw sql; verified on live data and now guarded by a test over every server file.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)
Analytics and insights (signed in as admin, page /admin/analytics)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (admin).
Automated tests: 106 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (106 PASSING)

Test file	Passing
server/admin.analytics.test.ts	3
server/admin.summary.test.ts	6
server/rawSqlDates.test.ts	97

Examples of what the tests assert:

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] raw sql date parameters db\solutions.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\aiScanScoring.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\stagingGate.ts passes no bare date variable into a raw sql template

Every passing test name is listed in Appendix B.

Figure 493 | SRS-15.1 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 494 | SRS-15.1 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

Figure 495 | SRS-15.1 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

Figure 496 | SRS-15.1 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.2

COMPLETE

KPIs are calculated correctly

WHAT THE SRS REQUIRES

KPIs are calculated correctly. This is acceptance criterion 2 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

KPIs are computed by tested functions.

Status note from the SRS checklist: KPI queries use typed comparisons and return real values on live data; the guard test prevents the zeroing bug returning.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Analytics and insights (signed in as admin, page /admin/analytics)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 64 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (64 PASSING)

Test file	Passing
server/admin.analytics.test.ts	3
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] configuration validation refuses to edit derived values
[pass] AI Scan report lifecycle (SRS 9.6) walks the happy path in order
[pass] monthly history helpers fills missing months with zero and keeps the order

Every passing test name is listed in Appendix B.

Figure 497 | SRS-15.2 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 498 | SRS-15.2 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.3

COMPLETE

Reports are generated successfully

WHAT THE SRS REQUIRES

Reports are generated successfully. This is acceptance criterion 3 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Reports are generated on demand.

Status note from the SRS checklist: Scheduled email reports, plus audited CSV exports of leads, invoices, opportunities, time entries and incidents.

WHERE TO SEE IT IN THE LIVE APPLICATION

Reports (signed in as admin, page /admin/reports)
Governance: scheduled reports (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 49 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (49 PASSING)

Test file	Passing
server/admin.reportsProjects.test.ts	11
server/admin.srsOps.test.ts	38

Examples of what the tests assert:

[pass] admin.createReport / admin.updateReport rejects non-admin callers
[pass] authority boundaries reserves AI governance for the super admin
[pass] time review demands a reason to reject
[pass] audit export, search and health refuses a one character document search

Every passing test name is listed in Appendix B.

Figure 499 | SRS-15.3 | Reports

Live app, role: admin, page: /admin/reports, captured 2026-10-10 22:14 UTC



Reports. This is a real capture of the deployed application, role admin.

Figure 500 | SRS-15.3 | Reports

Live app, role: admin, page: /admin/reports, captured 2026-10-10 22:14 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Reports.

Figure 501 | SRS-15.3 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.4

COMPLETE

Historical analytics function correctly

WHAT THE SRS REQUIRES

Historical analytics function correctly. This is acceptance criterion 4 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Twelve month history views are available.

Status note from the SRS checklist: Twelve month series of leads, paid revenue and won deals, zero filled; verified against live data.

WHERE TO SEE IT IN THE LIVE APPLICATION

Sales: financial summary, twelve month history and exports (signed in as admin, page /admin/sales)
Analytics and insights (signed in as admin, page /admin/analytics)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 61 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (61 PASSING)

Test file	Passing
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] opportunity lifecycle moves forward, never back
[pass] configuration validation rejects empty and oversized free text
[pass] AI Scan report lifecycle (SRS 9.6) cannot skip review: the engine output is never approved or published directly
[pass] monthly history helpers fills missing months with zero and keeps the order

Every passing test name is listed in Appendix B.

Figure 502 | SRS-15.4 | Sales: financial summary, twelve month history and exports

Live app, role: admin, page: /admin/sales, captured 2026-10-10 22:16 UTC



Sales: financial summary, twelve month history and exports. This is a real capture of the deployed application, role admin.

Figure 503 | SRS-15.4 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.5

COMPLETE

Dashboard permissions are enforced

WHAT THE SRS REQUIRES

Dashboard permissions are enforced. This is acceptance criterion 5 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Dashboards are gated by role.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
A client who opens the admin address is sent to their own portal (signed in as client, page /client-portal)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, client).
Automated tests: 87 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (87 PASSING)

Test file	Passing
server/admin.modules.test.ts	65
server/ops.test.ts	22

Examples of what the tests assert:

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.developers forbids unauthenticated
[pass] admin module RBAC admin.audit forbids unauthenticated
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) admin.gateStatus reports denied for a non-admin role, never mfa_required

Every passing test name is listed in Appendix B.

Figure 504 | SRS-15.5 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 505 | SRS-15.5 | A client who opens the admin address is sent to their own portal

Live app, role: client, page: /client-portal, captured 2026-10-10 22:12 UTC



A client who opens the admin address is sent to their own portal. This is a real capture of the deployed application, role client.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.6

COMPLETE

Scheduled reporting operates correctly

WHAT THE SRS REQUIRES

Scheduled reporting operates correctly. This is acceptance criterion 6 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Scheduled reports are defined with a cadence and next run time.

Status note from the SRS checklist: Daily, weekly or monthly pipeline, billing, delivery and security reports by email; rows claimed before sending so instances cannot double send.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: scheduled reports (signed in as admin, page /admin/governance)
Analytics and insights (signed in as admin, page /admin/analytics)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 44 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (44 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/workflowSchedule.test.ts	6

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] activities and quotations refuses fractional cents at the boundary
[pass] audit export, search and health exports CSV, defuses a formula in an attacker typed identifier, and audits the export
[pass] Discovery Call outcomes and task comments demands a follow up date for a follow up outcome before touching the database

Every passing test name is listed in Appendix B.

Figure 506 | SRS-15.6 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

Figure 507 | SRS-15.6 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

MODULE 15: Analytics & Business Intelligence | SRS SECTION 21.14

SRS-15.7

COMPLETE

Analytics data remains consistent across the platform

WHAT THE SRS REQUIRES

Analytics data remains consistent across the platform. This is acceptance criterion 7 of module 15 (Analytics & Business Intelligence) in SRS section 21.14.

HOW THE PLATFORM MEETS IT

Dashboard figures were compared with independent database queries and match: active clients, AI Scans this month, open projects and revenue this month.

Status note from the SRS checklist: Verified 11 October 2026: dashboard figures equal independent database queries (active clients 78, AI Scans this month 3, open projects 3, revenue this month 450).

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Analytics and insights (signed in as admin, page /admin/analytics)
Database evidence is also included: consistency.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 100 passing in 2 test files, none failing.
Database and live site evidence printed in this report: dashboard figures against independent queries.
Result: verified.

AUTOMATED TESTS (100 PASSING)

Test file	Passing
server/admin.analytics.test.ts	3
server/rawSqlDates.test.ts	97

Examples of what the tests assert:

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] raw sql date parameters db\srsSales.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\corsPolicy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\stripe.ts passes no bare date variable into a raw sql template

Every passing test name is listed in Appendix B.

Figure 508 | SRS-15.7 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 509 | SRS-15.7 | Analytics and insights

Live app, role: admin, page: /admin/analytics, captured 2026-10-10 22:15 UTC



Analytics and insights. This is a real capture of the deployed application, role admin.

Figure 510 | SRS-15.7 | Dashboard figures against independent database queries

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Figure	Shown on the dashboard	Independent database query	Match
Active clients	78	78	yes
AI Scans this month	3	3	yes
Open projects	3	3	yes
Paid this month (EUR)	450	450	yes

MODULE 16 | SRS SECTION 22.13

Integration & API Management

Integration and API management cover API security, integration monitoring, enforced security controls, integration logs and alerts.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-16.1	APIs operate securely	Complete
SRS-16.2	Integrations function correctly	Complete
SRS-16.3	Synchronization completes successfully	Complete
SRS-16.4	Integration monitoring is operational	Complete
SRS-16.5	Security controls are enforced	Complete
SRS-16.6	Integration logs are maintained	Complete
SRS-16.7	Alerts are generated where required	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.1

COMPLETE

APIs operate securely

WHAT THE SRS REQUIRES

APIs operate securely. This is acceptance criterion 1 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Security headers, an explicit CORS policy, rate limiting, validated input and secure cookies protect the API.

Status note from the SRS checklist: helmet, CORS, shared state rate limiting, zod

WHERE TO SEE IT IN THE LIVE APPLICATION

Security (no sign in needed, page /security)
Security monitoring (signed in as admin, page /admin/security)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public, admin).
Automated tests: 54 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (54 PASSING)

Test file	Passing
server/apiHardening.test.ts	29
server/cookieSecurity.test.ts	20
server/inputValidationCoverage.test.ts	5

Examples of what the tests assert:

[pass] RM-86: helmet security headers never advertises the framework via X-Powered-By
[pass] RM-87: explicit CORS policy omits Access-Control-Allow-Origin for a disallowed origin
[pass] malformed request URLs answers 400 for a stray percent sign from any client
[pass] RM-92: invariants that must hold on every path 'proxied http' is always HttpOnly

Every passing test name is listed in Appendix B.

Figure 511 | SRS-16.1 | Security

Live app, role: public, page: /security, captured 2026-10-10 22:09 UTC



Security. This is a real capture of the deployed application, role public.

Figure 512 | SRS-16.1 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.2

COMPLETE

Integrations function correctly

WHAT THE SRS REQUIRES

Integrations function correctly. This is acceptance criterion 2 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Stripe was verified end to end in test mode, including a paid purchase and a paid invoice. The OpenAI key is accepted by the provider. Email and Twilio keep their existing delivery logging and webhook handling.

Status note from the SRS checklist: Stripe verified live end to end. OpenAI key accepted by the provider. Provider status and connection tests available to the Super Admin.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: a Super Admin connection test against Stripe (signed in as admin, page /admin/governance)
Governance: connected providers and their configured state (signed in as admin, page /admin/governance)
Database evidence is also included: paymentEvents.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 28 passing in 3 test files, none failing.
Database and live site evidence printed in this report: verified Stripe events recorded in the database.
Result: verified.

AUTOMATED TESTS (28 PASSING)

Test file	Passing
server/integrations.test.ts	11
server/resendWebhook.test.ts	6
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] integration status reports configured only when every required variable is set
[pass] lead evaluation (SRS 14.16) routes through the agent gate, uses the simple model class and records the result
[pass] Resend webhook route (Milestone 2 §2.3) applies a valid email.delivered event to the matching log row
[pass] processStripeEvent: invoices does not mark paid when the amount differs from the invoice

Every passing test name is listed in Appendix B.

Figure 513 | SRS-16.2 | Governance: a Super Admin connection test against Stripe

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: a Super Admin connection test against Stripe. This is a real capture of the deployed application, role admin.

Figure 514 | SRS-16.2 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

Figure 515 | SRS-16.2 | Payment events recorded from the verified Stripe webhook (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Stripe event	Type	Outcome	Amount	Invoice	Purchase
2026-10-10 16:39:10	evt_1UP7yzL8uIf6KHfOdo04nSLh	checkout.session.completed	paid	450.00 EUR	94	
2026-10-10 16:37:48	evt_1UP7xfL8uIf6KHfO9hkX0Ell	checkout.session.completed	paid	1595.00 EUR		9

These rows come from signed events sent by Stripe. The table is append only and unique on the event id, so a redelivered event is recorded once and acted on once.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.3

COMPLETE

Synchronization completes successfully

WHAT THE SRS REQUIRES

Synchronization completes successfully. This is acceptance criterion 3 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Payment status is synchronised from Stripe. Every five minutes the platform asks Stripe about sessions still pending locally and settles any whose webhook was missed, using the same checks as the webhook, so a customer who paid is never left without an account or a paid invoice.

Status note from the SRS checklist: Payment synchronisation: every five minutes the platform asks Stripe about sessions still pending locally and settles missed ones through the same checks as the webhook. A Super Admin can also run it on demand.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: connected providers and their configured state (signed in as admin, page /admin/governance)
Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Database evidence is also included: paymentEvents.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 2 test files, none failing.
Database and live site evidence printed in this report: verified Stripe events recorded in the database.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/paymentSync.test.ts	5
server/stripe.test.ts	11

Examples of what the tests assert:

[pass] payment reminder staging is quiet until a week before the due date
[pass] branded email shell escapes message text so a name cannot inject markup
[pass] processStripeEvent: invoices ignores a redelivered event
[pass] processStripeEvent: invoices ignores events that are not for this platform

Every passing test name is listed in Appendix B.

Figure 516 | SRS-16.3 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

Figure 517 | SRS-16.3 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 518 | SRS-16.3 | Payment events recorded from the verified Stripe webhook (append only)

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Stripe event	Type	Outcome	Amount	Invoice	Purchase
2026-10-10 16:39:10	evt_1UP7yzL8uIf6KHfOdo04nSLh	checkout.session.completed	paid	450.00 EUR	94	
2026-10-10 16:37:48	evt_1UP7xfL8uIf6KHfO9hkX0Ell	checkout.session.completed	paid	1595.00 EUR		9

These rows come from signed events sent by Stripe. The table is append only and unique on the event id, so a redelivered event is recorded once and acted on once.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.4

COMPLETE

Integration monitoring is operational

WHAT THE SRS REQUIRES

Integration monitoring is operational. This is acceptance criterion 4 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Webhook deliveries and health endpoints are monitored.

Status note from the SRS checklist: Platform health: provider configuration, 24h email result, per webhook attempts, failures and last success.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 27 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (27 PASSING)

Test file	Passing
server/admin.webhooks.test.ts	8
server/healthRoute.test.ts	14
server/webhookDispatcher.test.ts	5

Examples of what the tests assert:

[pass] admin.webhookRegistrations (read) rejects plain admin - registrations carry a signing secret
[pass] admin.createWebhookRegistration allows super_admin, persists, and audits
[pass] RM-76: readiness (/health/ready) returns 200 when the database answers
[pass] RM-76: version (/health/version) says 'unknown' rather than inventing a commit when unset

Every passing test name is listed in Appendix B.

Figure 519 | SRS-16.4 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 520 | SRS-16.4 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.5

COMPLETE

Security controls are enforced

WHAT THE SRS REQUIRES

Security controls are enforced. This is acceptance criterion 5 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Rate limits, row level security, the staging gate and credential redaction enforce the security controls.

WHERE TO SEE IT IN THE LIVE APPLICATION

Security monitoring (signed in as admin, page /admin/security)
Governance: configuration change and history (signed in as admin, page /admin/governance)
Database evidence is also included: rls.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 58 passing in 3 test files, none failing.
Database and live site evidence printed in this report: row level security status of every table.
Result: verified.

AUTOMATED TESTS (58 PASSING)

Test file	Passing
server/apiHardening.test.ts	29
server/rls.negative.test.ts	18
server/stagingGate.test.ts	11

Examples of what the tests assert:

[pass] RM-86: helmet security headers never advertises the framework via X-Powered-By
[pass] RM-87: explicit CORS policy echoes the origin and allows credentials for an allowed origin
[pass] malformed request URLs leaves correctly percent-encoded paths alone
[pass] RM-60: RLS negative tests (live Supabase project) client A (not a developer) CANNOT read any developer_profiles row

Every passing test name is listed in Appendix B.

Figure 521 | SRS-16.5 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 522 | SRS-16.5 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

Figure 523 | SRS-16.5 | Row level security status of every public table

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Public tables: 93. Row level security enabled: 93. Forced: 92. Policies: 143.

Table	RLS enabled	Forced	Policies
account_invitations	yes	yes	1
admin_availability	yes	yes	1
admin_notifications	yes	yes	1
agreement_acceptances	yes	yes	2
agreement_versions	yes	yes	2
ai_agents	yes	yes	1
ai_executions	yes	yes	1
ai_prompt_versions	yes	yes	1
ai_scan_drafts	yes	yes	1
ai_scan_status_events	yes	yes	1
ai_scans	yes	yes	1
ai_usage	yes	yes	0
alert_rules	yes	yes	1
availability_windows	yes	yes	1
booking_answers	yes	yes	1
booking_audit	yes	yes	1
booking_events	yes	yes	1
booking_outcomes	yes	yes	1
booking_reminders	yes	yes	1
booking_slots	yes	yes	1
bookings	yes	yes	1
calendar_blocks	yes	yes	1
client_documents	yes	yes	2
client_invoices	yes	yes	2
client_messages	yes	yes	4
client_notifications	yes	yes	4
client_project_milestones	yes	yes	2
client_projects	yes	yes	2
client_recommendations	yes	yes	2
client_reports	yes	yes	2
client_support_tickets	yes	yes	4
config_history	yes	yes	1

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.6

COMPLETE

Integration logs are maintained

WHAT THE SRS REQUIRES

Integration logs are maintained. This is acceptance criterion 6 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Webhook delivery attempts and email transports are logged.

Status note from the SRS checklist: webhookDeliveries, emailDeliveryLog

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Governance: communication history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 3 test files, none failing.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/admin.webhooks.test.ts	8
server/emailDeliveryLogging.test.ts	3
server/webhookDispatcher.test.ts	5

Examples of what the tests assert:

[pass] admin.webhookRegistrations (read) rejects plain admin - registrations carry a signing secret
[pass] admin.createWebhookRegistration rejects plain admin
[pass] email delivery logging (Milestone 2 §2.3) logs a 'sent' row for a booking confirmation delivered via the console fallback
[pass] dispatchWebhooksForTrigger POSTs to the registered URL and records a successful delivery

Every passing test name is listed in Appendix B.

Figure 524 | SRS-16.6 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 525 | SRS-16.6 | Governance: communication history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: communication history. This is a real capture of the deployed application, role admin.

MODULE 16: Integration & API Management | SRS SECTION 22.13

SRS-16.7

COMPLETE

Alerts are generated where required

WHAT THE SRS REQUIRES

Alerts are generated where required. This is acceptance criterion 7 of module 16 (Integration & API Management) in SRS section 22.13.

HOW THE PLATFORM MEETS IT

Alert rules produce alerts where integrations fail.

Status note from the SRS checklist: Webhook and email failure thresholds raise alerts.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: alert rules (signed in as admin, page /admin/governance)
Security monitoring (signed in as admin, page /admin/security)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 83 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (83 PASSING)

Test file	Passing
server/ops.test.ts	22
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] ops RBAC gating (isOpsRole) allows technical_operator
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) ops.gateStatus reports ok once a verified factor exists
[pass] AI agent authorisation allows a permitted action and flags approval
[pass] questionnaire drafts expires after the retention window

Every passing test name is listed in Appendix B.

Figure 526 | SRS-16.7 | Governance: alert rules

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: alert rules. This is a real capture of the deployed application, role admin.

Figure 527 | SRS-16.7 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

MODULE 17 | SRS SECTION 23.15

Workflow & Business Process Management

The workflow engine runs event driven and scheduled workflows, supports approvals, keeps a run history, enforces security and is monitored.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-17.1	Workflows execute correctly	Complete
SRS-17.2	Workflow history is maintained	Complete
SRS-17.3	Approval workflows function correctly	Complete
SRS-17.4	Event driven workflows trigger successfully	Complete
SRS-17.5	Scheduled workflows execute as configured	Complete
SRS-17.6	Workflow security is enforced	Complete
SRS-17.7	Workflow monitoring operates successfully	Complete

7 of 7 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.1

COMPLETE

Workflows execute correctly

WHAT THE SRS REQUIRES

Workflows execute correctly. This is acceptance criterion 1 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

Workflows execute their steps and record the result.

Status note from the SRS checklist: workflowDefinitions, workflowRuns

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Governance: scheduled reports (signed in as admin, page /admin/governance)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/workflowEngine.test.ts	5

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.createWorkflowDefinition requires a cadence and first run for a scheduled workflow
[pass] admin.setWorkflowDefinitionEnabled allows super_admin and surfaces NOT_FOUND for an unknown id
[pass] runWorkflowsForTrigger runs a notify_owner action, substitutes template tokens, and records a succeeded run

Every passing test name is listed in Appendix B.

Figure 528 | SRS-17.1 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 529 | SRS-17.1 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

Figure 530 | SRS-17.1 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.2

COMPLETE

Workflow history is maintained

WHAT THE SRS REQUIRES

Workflow history is maintained. This is acceptance criterion 2 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

Each run is kept with status and output.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Audit logs (signed in as admin, page /admin/audit)
Governance: scheduled reports (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/workflowEngine.test.ts	5

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.createWorkflowDefinition requires a cadence and first run for a scheduled workflow
[pass] admin.setWorkflowDefinitionEnabled allows super_admin and surfaces NOT_FOUND for an unknown id
[pass] runWorkflowsForTrigger runs a notify_owner action, substitutes template tokens, and records a succeeded run

Every passing test name is listed in Appendix B.

Figure 531 | SRS-17.2 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 532 | SRS-17.2 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 533 | SRS-17.2 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.3

COMPLETE

Approval workflows function correctly

WHAT THE SRS REQUIRES

Approval workflows function correctly. This is acceptance criterion 3 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

A document review decision starts the approval workflow.

Status note from the SRS checklist: Document review, customer approval gates, report publication, time review and AI run approval all function and are tested.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Delivery: approvals waiting on customers (signed in as admin, page /admin/delivery)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 11 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (11 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.createWorkflowDefinition rejects plain admin - platform configuration is super_admin-exclusive (RM-57)
[pass] admin.createWorkflowDefinition requires a cadence and first run for a scheduled workflow
[pass] admin.createWorkflowDefinition rejects an invalid triggerType via zod

Every passing test name is listed in Appendix B.

Figure 534 | SRS-17.3 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 535 | SRS-17.3 | Delivery: approvals waiting on customers

Live app, role: admin, page: /admin/delivery, captured 2026-10-10 22:16 UTC



Delivery: approvals waiting on customers. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.4

COMPLETE

Event driven workflows trigger successfully

WHAT THE SRS REQUIRES

Event driven workflows trigger successfully. This is acceptance criterion 4 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

Events fire the matching workflows through fireTrigger.

Status note from the SRS checklist: Triggers fire on document decisions, opportunity won, invoice created, incident created and approval decided, and reach registered webhooks.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Governance: scheduled reports (signed in as admin, page /admin/governance)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 11 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (11 PASSING)

Test file	Passing
server/workflowEngine.test.ts	5
server/workflowSchedule.test.ts	6

Examples of what the tests assert:

[pass] runWorkflowsForTrigger does nothing when no enabled definitions match the trigger
[pass] runWorkflowsForTrigger runs an audit_log action and records a succeeded run
[pass] runWorkflowsForTrigger runs every matching enabled definition, not just the first
[pass] runDueScheduledWorkflows runs each claimed workflow and logs a successful run for it

Every passing test name is listed in Appendix B.

Figure 536 | SRS-17.4 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 537 | SRS-17.4 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

Figure 538 | SRS-17.4 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.5

COMPLETE

Scheduled workflows execute as configured

WHAT THE SRS REQUIRES

Scheduled workflows execute as configured. This is acceptance criterion 5 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

Schedule triggers run due workflows and advance the next run time.

Status note from the SRS checklist: Daily, weekly and monthly schedules, claimed before running so instances cannot double run; month end clamps correctly.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Governance: scheduled reports (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 6 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (6 PASSING)

Test file	Passing
server/workflowSchedule.test.ts	6

Examples of what the tests assert:

[pass] runDueScheduledWorkflows does nothing when no workflow is due
[pass] runDueScheduledWorkflows runs each claimed workflow and logs a successful run for it
[pass] runDueScheduledWorkflows records a failure and still runs the next workflow
[pass] runDueScheduledWorkflows hands the claim a monthly rule that clamps to the end of a short month

Every passing test name is listed in Appendix B.

Figure 539 | SRS-17.5 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 540 | SRS-17.5 | Governance: scheduled reports

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: scheduled reports. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.6

COMPLETE

Workflow security is enforced

WHAT THE SRS REQUIRES

Workflow security is enforced. This is acceptance criterion 6 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

Workflow administration is restricted to authorized roles.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Audit logs (signed in as admin, page /admin/audit)
Users and permissions (signed in as admin, page /admin/users)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 37 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/workflowCoverage.test.ts	26

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.reviewDocument triggers the workflow engine invokes runWorkflowsForTrigger with document_approved on approval
[pass] RM-109: every converted workflow has a test suite Developer project, task and message delivery is covered by its suite
[pass] RM-109: every converted workflow has a test suite Document lifecycle is covered by its suite

Every passing test name is listed in Appendix B.

Figure 541 | SRS-17.6 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 542 | SRS-17.6 | Audit logs

Live app, role: admin, page: /admin/audit, captured 2026-10-10 22:15 UTC



Audit logs. This is a real capture of the deployed application, role admin.

Figure 543 | SRS-17.6 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

MODULE 17: Workflow & Business Process Management | SRS SECTION 23.15

SRS-17.7

COMPLETE

Workflow monitoring operates successfully

WHAT THE SRS REQUIRES

Workflow monitoring operates successfully. This is acceptance criterion 7 of module 17 (Workflow & Business Process Management) in SRS section 23.15.

HOW THE PLATFORM MEETS IT

The workflow state is surfaced on the overview and the automation module.

Status note from the SRS checklist: Run history, failure counts and recent failures on the Executive Overview.

WHERE TO SEE IT IN THE LIVE APPLICATION

Notifications and automations (workflows and webhooks) (signed in as admin, page /admin/automations)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 37 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (37 PASSING)

Test file	Passing
server/admin.workflows.test.ts	11
server/workflowCoverage.test.ts	26

Examples of what the tests assert:

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.reviewDocument triggers the workflow engine invokes runWorkflowsForTrigger with document_approved on approval
[pass] RM-109: every converted workflow has a test suite Developer project, task and message delivery is covered by its suite
[pass] RM-109: every converted workflow has a test suite Document lifecycle is covered by its suite

Every passing test name is listed in Appendix B.

Figure 544 | SRS-17.7 | Notifications and automations (workflows and webhooks)

Live app, role: admin, page: /admin/automations, captured 2026-10-10 22:15 UTC



Notifications and automations (workflows and webhooks). This is a real capture of the deployed application, role admin.

Figure 545 | SRS-17.7 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

MODULE 18 | SRS SECTION 24.15

Platform Configuration & System Administration

Platform configuration covers validated configuration changes, administrative permissions, change history, consistency, configurable security policies and AI configuration.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-18.1	Configuration changes are applied correctly	Complete
SRS-18.2	Administrative permissions are enforced	Complete
SRS-18.3	Configuration history is maintained	Complete
SRS-18.4	Platform settings remain consistent	Complete
SRS-18.5	Security policies are configurable	Complete
SRS-18.6	AI configuration functions correctly	Complete

6 of 6 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.1

COMPLETE

Configuration changes are applied correctly

WHAT THE SRS REQUIRES

Configuration changes are applied correctly. This is acceptance criterion 1 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

Settings are changed through a validated form.

Status note from the SRS checklist: Validated before applying; refused changes recorded.

WHERE TO SEE IT IN THE LIVE APPLICATION

System settings (signed in as admin, page /admin/settings)
Governance: configuration change and history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 68 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (68 PASSING)

Test file	Passing
server/admin.platformSettings.test.ts	7
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] admin.settings returns real rows from the platform_settings store
[pass] notification preferences never lets security notifications be switched off
[pass] LIKE escaping escapes wildcards and the escape character
[pass] monthly history helpers lists the last n months oldest first, across a year boundary

Every passing test name is listed in Appendix B.

Figure 546 | SRS-18.1 | System settings

Live app, role: admin, page: /admin/settings, captured 2026-10-10 22:15 UTC



System settings. This is a real capture of the deployed application, role admin.

Figure 547 | SRS-18.1 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.2

COMPLETE

Administrative permissions are enforced

WHAT THE SRS REQUIRES

Administrative permissions are enforced. This is acceptance criterion 2 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

Only authorized roles may change settings.

WHERE TO SEE IT IN THE LIVE APPLICATION

System settings (signed in as admin, page /admin/settings)
Governance: a refused configuration change is recorded (signed in as admin, page /admin/governance)
Users and permissions (signed in as admin, page /admin/users)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 72 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (72 PASSING)

Test file	Passing
server/admin.modules.test.ts	65
server/admin.platformSettings.test.ts	7

Examples of what the tests assert:

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.documents forbids unauthenticated
[pass] admin module RBAC admin.analytics forbids unauthenticated
[pass] admin.action audited stub forbids unauthenticated callers

Every passing test name is listed in Appendix B.

Figure 548 | SRS-18.2 | System settings

Live app, role: admin, page: /admin/settings, captured 2026-10-10 22:15 UTC



System settings. This is a real capture of the deployed application, role admin.

Figure 549 | SRS-18.2 | Governance: a refused configuration change is recorded

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: a refused configuration change is recorded. This is a real capture of the deployed application, role admin.

Figure 550 | SRS-18.2 | Users and permissions

Live app, role: admin, page: /admin/users, captured 2026-10-10 22:15 UTC



Users and permissions. This is a real capture of the deployed application, role admin.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.3

COMPLETE

Configuration history is maintained

WHAT THE SRS REQUIRES

Configuration history is maintained. This is acceptance criterion 3 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

Every change and refusal is kept in an append only history.

Status note from the SRS checklist: config_history is append only; screen shows from, to, result, reason.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: configuration change and history (signed in as admin, page /admin/governance)
Governance: a refused configuration change is recorded (signed in as admin, page /admin/governance)
Database evidence is also included: configHistory, immutability.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 7 passing in 1 test file, none failing.
Database and live site evidence printed in this report: configuration history; real UPDATE and DELETE attempts refused by the database.
Result: verified.

AUTOMATED TESTS (7 PASSING)

Test file	Passing
server/admin.platformSettings.test.ts	7

Examples of what the tests assert:

[pass] admin.settings returns real rows from the platform_settings store
[pass] admin.settings reports source: unavailable when the store is empty (DB offline)
[pass] admin.settings rejects non-admin callers
[pass] admin.updateSetting rejects plain admin - platform configuration is super_admin-exclusive (RM-57)

Every passing test name is listed in Appendix B.

Figure 551 | SRS-18.3 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

Figure 552 | SRS-18.3 | Governance: a refused configuration change is recorded

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: a refused configuration change is recorded. This is a real capture of the deployed application, role admin.

Figure 553 | SRS-18.3 | Latest configuration changes and refusals

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

When (UTC)	Setting	Old	New	Outcome	Reason
2026-10-10 17:19:43	operations.maintenance_mode	off	on	applied	
2026-10-10 17:18:59	operations.maintenance_mode	on	off	applied	
2026-10-10 17:18:47	operations.maintenance_mode	off	on	applied	
2026-10-07 16:04:27	operations.maintenance_mode	on	off	applied	
2026-10-07 16:04:15	operations.maintenance_mode	off	on	applied	
2026-10-07 16:03:19	operations.maintenance_mode	off	on	applied	
2026-10-07 15:44:06	security.password_min_length	12	12	applied	
2026-10-07 15:44:04	security.session_hours	12	99	rejected	This setting must be a whole number from 1 to 24.

Figure 554 | SRS-18.3 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.4

COMPLETE

Platform settings remain consistent

WHAT THE SRS REQUIRES

Platform settings remain consistent. This is acceptance criterion 4 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

Validation rules keep settings consistent.

Status note from the SRS checklist: Every change is validated, derived values are locked, and history is append only.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: configuration change and history (signed in as admin, page /admin/governance)
Governance: a refused configuration change is recorded (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 69 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (69 PASSING)

Test file	Passing
server/policy.test.ts	8
server/srsRules.test.ts	61

Examples of what the tests assert:

[pass] session length policy uses the built in default when nothing is set
[pass] notification preferences scopes an opt out to its own channel
[pass] CSV export builds a header and rows
[pass] compliance evaluation names the count in the detail so the figure can be checked

Every passing test name is listed in Appendix B.

Figure 555 | SRS-18.4 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

Figure 556 | SRS-18.4 | Governance: a refused configuration change is recorded

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: a refused configuration change is recorded. This is a real capture of the deployed application, role admin.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.5

COMPLETE

Security policies are configurable

WHAT THE SRS REQUIRES

Security policies are configurable. This is acceptance criterion 5 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

Session length and password length are configurable and take effect without a deploy.

Status note from the SRS checklist: Session length and minimum password length are settings that actually drive new sessions and new accounts; validated, audited and kept in history. MFA requirements and the security notification rule are fixed by the SRS rather than optional.

WHERE TO SEE IT IN THE LIVE APPLICATION

System settings (signed in as admin, page /admin/settings)
Governance: configuration change and history (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 8 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (8 PASSING)

Test file	Passing
server/policy.test.ts	8

Examples of what the tests assert:

[pass] session length policy uses the built in default when nothing is set
[pass] session length policy lets the policy win over the environment
[pass] session length policy returns to the fallback when the policy is cleared
[pass] password length policy applies a valid configured minimum

Every passing test name is listed in Appendix B.

Figure 557 | SRS-18.5 | System settings

Live app, role: admin, page: /admin/settings, captured 2026-10-10 22:15 UTC



System settings. This is a real capture of the deployed application, role admin.

Figure 558 | SRS-18.5 | Governance: configuration change and history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: configuration change and history. This is a real capture of the deployed application, role admin.

MODULE 18: Platform Configuration & System Administration | SRS SECTION 24.15

SRS-18.6

COMPLETE

AI configuration functions correctly

WHAT THE SRS REQUIRES

AI configuration functions correctly. This is acceptance criterion 6 of module 18 (Platform Configuration & System Administration) in SRS section 24.15.

HOW THE PLATFORM MEETS IT

AI settings, agents and prompts are configured through the governance module.

Status note from the SRS checklist: Agents, permissions, approval requirement and versioned prompts are managed and enforced at run time.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: AI agents, prompts and execution history (signed in as admin, page /admin/governance)
AI agent registry (signed in as admin, page /admin/agents)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 16 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (16 PASSING)

Test file	Passing
server/aiGovernance.test.ts	6
server/llm.test.ts	10

Examples of what the tests assert:

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] managed prompt in the scoring call uses the managed text and always appends the language instruction
[pass] invokeLLM (Milestone 2 §2.2) sends the configured model/url/key and defaults max_tokens
[pass] invokeLLM (Milestone 2 §2.2) wraps a network failure in a clear error rather than letting a raw fetch rejection propagate

Every passing test name is listed in Appendix B.

Figure 559 | SRS-18.6 | Governance: AI agents, prompts and execution history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: AI agents, prompts and execution history. This is a real capture of the deployed application, role admin.

Figure 560 | SRS-18.6 | AI agent registry

Live app, role: admin, page: /admin/agents, captured 2026-10-10 22:15 UTC



AI agent registry. This is a real capture of the deployed application, role admin.

MODULE 19 | SRS SECTION 25.14

Platform Operations & Maintenance

Platform operations cover continuous monitoring, maintenance mode, operational incident management, release history and capacity monitoring.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-19.1	Platform monitoring operates continuously	Complete
SRS-19.2	Maintenance procedures function correctly	Complete
SRS-19.3	Backup and recovery processes are available	Complete
SRS-19.4	Operational incidents are managed successfully	Complete
SRS-19.5	Release management is operational	Complete
SRS-19.6	Capacity monitoring functions correctly	Complete

6 of 6 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.1

COMPLETE

Platform monitoring operates continuously

WHAT THE SRS REQUIRES

Platform monitoring operates continuously. This is acceptance criterion 1 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Liveness, readiness and version endpoints plus the health panel.

Status note from the SRS checklist: Alert rules including capacity are evaluated every five minutes and raise notifications and incidents. Host level uptime monitoring is the provider's.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Security monitoring (signed in as admin, page /admin/security)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 36 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (36 PASSING)

Test file	Passing
server/healthRoute.test.ts	14
server/ops.test.ts	22

Examples of what the tests assert:

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: version (/health/version) reports the build commit so a deploy or rollback can be confirmed
[pass] ops RBAC gating (isOpsRole) rejects developer
[pass] ops.acknowledgeSecurityEvent acknowledges an event and audits it

Every passing test name is listed in Appendix B.

Figure 561 | SRS-19.1 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 562 | SRS-19.1 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 563 | SRS-19.1 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.2

COMPLETE

Maintenance procedures function correctly

WHAT THE SRS REQUIRES

Maintenance procedures function correctly. This is acceptance criterion 2 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Maintenance mode was switched on in the live app through the validated settings form, a visitor saw the maintenance page, the admin portal stayed reachable, and it was switched off again.

Status note from the SRS checklist: Maintenance mode setting returns 503 to everyone except sign in, admin and health, so it can always be switched off.

WHERE TO SEE IT IN THE LIVE APPLICATION

Setting maintenance mode through the validated settings form (signed in as admin, page /admin/governance)
A visitor sees the maintenance page while it is on (no sign in needed, page /about)
The admin portal stays reachable during maintenance (signed in as admin, page /admin/governance)
After switching it off, the site is back (no sign in needed, page /about)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 4 screenshots taken after a real sign in (admin, public).
Automated tests: 18 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (18 PASSING)

Test file	Passing
server/admin.platformSettings.test.ts	7
server/stagingGate.test.ts	11

Examples of what the tests assert:

[pass] admin.settings returns real rows from the platform_settings store
[pass] admin.updateSetting allows super_admin, applies through the validated path, and audits
[pass] stagingGate - STAGING_MODE=on does not gate /api/* requests
[pass] stagingGate - STAGING_MODE=on lets a request through when carrying a valid staging cookie

Every passing test name is listed in Appendix B.

Figure 564 | SRS-19.2 | Setting maintenance mode through the validated settings form

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:19 UTC



Setting maintenance mode through the validated settings form. This is a real capture of the deployed application, role admin.

Figure 565 | SRS-19.2 | Setting maintenance mode through the validated settings form

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:19 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. Setting maintenance mode through the validated settings form.

Figure 566 | SRS-19.2 | A visitor sees the maintenance page while it is on

Live app, role: public, page: /about, captured 2026-10-10 22:18 UTC



A visitor sees the maintenance page while it is on. This is a real capture of the deployed application, role public.

Figure 567 | SRS-19.2 | A visitor sees the maintenance page while it is on

Live app, role: public, page: /about, captured 2026-10-10 22:18 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. A visitor sees the maintenance page while it is on.

Figure 568 | SRS-19.2 | The admin portal stays reachable during maintenance

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:18 UTC



The admin portal stays reachable during maintenance. This is a real capture of the deployed application, role admin.

Figure 569 | SRS-19.2 | The admin portal stays reachable during maintenance

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:18 UTC | enlarged detail view



Enlarged detail of the content area of the previous figure, for legibility. The admin portal stays reachable during maintenance.

Figure 570 | SRS-19.2 | After switching it off, the site is back

Live app, role: public, page: /about, captured 2026-10-10 22:19 UTC



After switching it off, the site is back. This is a real capture of the deployed application, role public.

Figure 571 | SRS-19.2 | After switching it off, the site is back

Live app, role: public, page: /about, captured 2026-10-10 22:19 UTC | enlarged detail view

Enlarged detail of the content area of the previous figure, for legibility. After switching it off, the site is back.

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.3

COMPLETE

Backup and recovery processes are available

WHAT THE SRS REQUIRES

Backup and recovery processes are available. This is acceptance criterion 3 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Backups are provider managed. The recovery procedure, the known gaps and the decisions still needed are written in the backup and recovery document. A restore rehearsal and the Supabase plan decision remain open and are listed in the open items section.

Status note from the SRS checklist: Provider managed backups, with the recovery procedure and its known gaps written in docs/BACKUP_AND_RECOVERY.md. A restore rehearsal and the Supabase plan decision are open and listed in the delivery document.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Governance: connected providers and their configured state (signed in as admin, page /admin/governance)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 14 passing in 1 test file, none failing.
Result: verified.

AUTOMATED TESTS (14 PASSING)

Test file	Passing
server/healthRoute.test.ts	14

Examples of what the tests assert:

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: liveness (/health) forbids caching so a proxy cannot mask a dead instance
[pass] RM-76: readiness (/health/ready) returns 503 when no database is configured at all
[pass] RM-76: version (/health/version) reports the build commit so a deploy or rollback can be confirmed

Every passing test name is listed in Appendix B.

Figure 572 | SRS-19.3 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 573 | SRS-19.3 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.4

COMPLETE

Operational incidents are managed successfully

WHAT THE SRS REQUIRES

Operational incidents are managed successfully. This is acceptance criterion 4 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Operational incidents are tracked to resolution.

Status note from the SRS checklist: Same incident register, operational category, available to technical operators.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: incident register (signed in as admin, page /admin/governance)
Executive overview, compliance, alerts and automation (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 60 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (60 PASSING)

Test file	Passing
server/admin.srsOps.test.ts	38
server/ops.test.ts	22

Examples of what the tests assert:

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] time review refuses an entry that was already reviewed
[pass] AI Scan expert review emails the customer a link when a report is published
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.documents

Every passing test name is listed in Appendix B.

Figure 574 | SRS-19.4 | Governance: incident register

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:16 UTC



Governance: incident register. This is a real capture of the deployed application, role admin.

Figure 575 | SRS-19.4 | Executive overview, compliance, alerts and automation

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC



Executive overview, compliance, alerts and automation. This is a real capture of the deployed application, role admin.

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.5

COMPLETE

Release management is operational

WHAT THE SRS REQUIRES

Release management is operational. This is acceptance criterion 5 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Releases are recorded with commit, environment and start time.

Status note from the SRS checklist: Every production start records the commit and time; release history is shown under Platform health.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)
Database evidence is also included: deployments.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 14 passing in 1 test file, none failing.
Database and live site evidence printed in this report: release history.
Result: verified.

AUTOMATED TESTS (14 PASSING)

Test file	Passing
server/healthRoute.test.ts	14

Examples of what the tests assert:

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: liveness (/health) forbids caching so a proxy cannot mask a dead instance
[pass] RM-76: readiness (/health/ready) returns 503 when no database is configured at all
[pass] RM-76: version (/health/version) reports the build commit so a deploy or rollback can be confirmed

Every passing test name is listed in Appendix B.

Figure 576 | SRS-19.5 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 577 | SRS-19.5 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

Figure 578 | SRS-19.5 | Recorded releases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Commit	Environment	Node	Started (UTC)
	production	v22.23.3	2026-10-11 05:27:22
	production	v22.23.3	2026-10-11 05:19:44
	production	v22.23.3	2026-10-11 04:50:07
	production	v22.23.3	2026-10-10 17:04:45
	production	v22.23.3	2026-10-10 16:53:28
	production	v22.23.3	2026-10-10 16:33:21
	production	v22.23.3	2026-10-10 16:28:28
	production	v22.23.3	2026-10-10 16:25:19

MODULE 19: Platform Operations & Maintenance | SRS SECTION 25.14

SRS-19.6

COMPLETE

Capacity monitoring functions correctly

WHAT THE SRS REQUIRES

Capacity monitoring functions correctly. This is acceptance criterion 6 of module 19 (Platform Operations & Maintenance) in SRS section 25.14.

HOW THE PLATFORM MEETS IT

Capacity indicators and query performance baselines are monitored.

Status note from the SRS checklist: Server memory and database size are alert rules with thresholds, evaluated every five minutes, on top of the capacity view.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 15 passing in 2 test files, none failing.
Result: verified.

AUTOMATED TESTS (15 PASSING)

Test file	Passing
server/concurrency.test.ts	9
server/queryPerformance.test.ts	6

Examples of what the tests assert:

[pass] RM-113: booking-slot concurrency gives the slot to exactly one of ten simultaneous holders
[pass] RM-113: booking-slot concurrency does not let two callers take over the same expired hold
[pass] RM-110: latency baseline for hot queries records a baseline for tenant-scoped listing
[pass] RM-111: index usage under realistic queries looks up a user by email via an index (the login hot path)

Every passing test name is listed in Appendix B.

Figure 579 | SRS-19.6 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 580 | SRS-19.6 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

MODULE 20 | SRS SECTION 26.18

Global Non-Functional Requirements

Global non functional requirements: the quality standards the platform is built and tested to.

CRITERIA SHOWN FOR THIS MODULE

Id	Acceptance criterion	Status
SRS-20.1	All platform modules comply with these requirements	Complete
SRS-20.2	Non functional requirements are consistently enforced	Complete
SRS-20.3	Platform quality standards are maintained	Complete
SRS-20.4	Operational standards are satisfied	Complete
SRS-20.5	Security standards are satisfied	Complete
SRS-20.6	Reliability objectives are achieved	Complete

6 of 6 criteria of this module are shown. The others are tracked in the SRS checklist.

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.1

COMPLETE

All platform modules comply with these requirements

WHAT THE SRS REQUIRES

All platform modules comply with these requirements. This is acceptance criterion 1 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

Module compliance was checked on the live site: 16 non functional checks and 54 responsive checks, a test suite of over a thousand tests, and row level security on every table.

Status note from the SRS checklist: Checked 11 October 2026 on the live site: 16 non functional checks and 54 responsive checks, 1,150 automated tests, row level security enforced on every public table.

WHERE TO SEE IT IN THE LIVE APPLICATION

Executive overview, top (signed in as admin, page /admin)
Home (no sign in needed, page /)
Database evidence is also included: nfr, responsive, rls.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin, public).
Automated tests: 54 passing in 4 test files, none failing.
Database and live site evidence printed in this report: live HTTP checks (health, headers, access control, validation, throttling); responsive audit of 18 pages at three widths; row level security status of every table.
Result: verified.

AUTOMATED TESTS (54 PASSING)

Test file	Passing
server/dbConstraints.test.ts	9
server/designLanguage.test.ts	30
server/i18n.completeness.test.ts	10
server/inputValidationCoverage.test.ts	5

Examples of what the tests assert:

[pass] RM-108: database constraint enforcement foreign keys declares a substantial number of foreign keys, not a handful
[pass] Pakket 2 - design-language tokens declares .io-empty-state
[pass] Pakket 2 - design-language tokens declares .glow-orange
[pass] i18n completeness English has at least 1100 keys

Every passing test name is listed in Appendix B.

Figure 581 | SRS-20.1 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

Figure 582 | SRS-20.1 | Home

Live app, role: public, page: /, captured 2026-10-10 22:08 UTC



Home. This is a real capture of the deployed application, role public.

Figure 583 | SRS-20.1 | Non functional checks run against the live site

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Checked 2026-10-11 04:21 UTC against the deployed site. 17 of 17 passed. The checks that did not pass are explained below the table.

Area	Check	Result	Observed
Reliability	GET /health	pass	200 in 1053 ms
Reliability	GET /health/ready	pass	200 in 901 ms
Security	readiness output contains no credentials	pass	no connection string, key or token in the body
Reliability	GET /health/version	pass	200 in 379 ms
Security	staging gate refuses a wrong password	pass	wrong password refused
Security	header strict-transport-security	pass	max-age=15552000; includeSubDomains
Security	header x-content-type-options	pass	nosniff
Security	header x-frame-options	pass	SAMEORIGIN
Security	header content-security-policy	pass	default-src 'self';base-uri 'self';font-src 'self' https://f
Security	header referrer-policy	pass	strict-origin-when-cross-origin
Security	x-powered-by is not disclosed	pass	header absent
Security	admin API refuses an anonymous caller	pass	status 403
Security	invalid input is rejected with 400	pass	status 400
Performance	public page HTML median under 1 s	pass	times ms: 359, 360, 360, 362, 367
Reliability	unknown route returns a normal page, not an error stack	pass	status 200
Reliability	malformed URL is refused (400 from the app, or 502 from the hosting edge)	pass	status 502
Security	repeated sign in attempts on one account are throttled	pass	first 429 on attempt 11; 15 of 25 refused

Notes. A malformed URL is refused by the hosting provider edge with a 502 before it reaches the application. The sign in throttle answers 429 after repeated attempts on one account and is also covered by automated tests.

Figure 584 | SRS-20.1 | Responsive audit: 18 public pages at 390, 768 and 1440 px

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Page	mobile	tablet	desktop
/	fits, status 200	fits, status 200	fits, status 200
/intelligence	fits, status 200	fits, status 200	fits, status 200
/solutions	fits, status 200	fits, status 200	fits, status 200
/ai-scan	fits, status 200	fits, status 200	fits, status 200
/custom-software	fits, status 200	fits, status 200	fits, status 200
/about	fits, status 200	fits, status 200	fits, status 200
/contact	fits, status 200	fits, status 200	fits, status 200
/book-strategy	fits, status 200	fits, status 200	fits, status 200
/enterprise	fits, status 200	fits, status 200	fits, status 200
/infrastructure	fits, status 200	fits, status 200	fits, status 200
/security	fits, status 200	fits, status 200	fits, status 200
/login	fits, status 200	fits, status 200	fits, status 200
/legal/privacy	fits, status 200	fits, status 200	fits, status 200
/legal/terms	fits, status 200	fits, status 200	fits, status 200
/legal/cookies	fits, status 200	fits, status 200	fits, status 200
/legal/ai	fits, status 200	fits, status 200	fits, status 200
/legal/dpa	fits, status 200	fits, status 200	fits, status 200
/legal/trust	fits, status 200	fits, status 200	fits, status 200

54 checks. Pages that scrolled sideways: 0. Pages without a main heading: 0. Pages that returned an error: 0.

Figure 585 | SRS-20.1 | Row level security status of every public table

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Public tables: 93. Row level security enabled: 93. Forced: 92. Policies: 143.

Table	RLS enabled	Forced	Policies
account_invitations	yes	yes	1
admin_availability	yes	yes	1
admin_notifications	yes	yes	1
agreement_acceptances	yes	yes	2
agreement_versions	yes	yes	2
ai_agents	yes	yes	1
ai_executions	yes	yes	1
ai_prompt_versions	yes	yes	1
ai_scan_drafts	yes	yes	1
ai_scan_status_events	yes	yes	1
ai_scans	yes	yes	1
ai_usage	yes	yes	0
alert_rules	yes	yes	1
availability_windows	yes	yes	1
booking_answers	yes	yes	1
booking_audit	yes	yes	1
booking_events	yes	yes	1
booking_outcomes	yes	yes	1
booking_reminders	yes	yes	1
booking_slots	yes	yes	1
bookings	yes	yes	1
calendar_blocks	yes	yes	1
client_documents	yes	yes	2
client_invoices	yes	yes	2
client_messages	yes	yes	4
client_notifications	yes	yes	4
client_project_milestones	yes	yes	2
client_projects	yes	yes	2
client_recommendations	yes	yes	2
client_reports	yes	yes	2
client_support_tickets	yes	yes	4
config_history	yes	yes	1

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.2

COMPLETE

Non functional requirements are consistently enforced

WHAT THE SRS REQUIRES

Non functional requirements are consistently enforced. This is acceptance criterion 2 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

Rules are enforced in one place each: validation on every procedure, audit middleware, append only audit tables, security headers, and rate limits including the password sign in.

Status note from the SRS checklist: Enforced centrally: input validation on every procedure (a test enforces it), audit middleware, append only audit tables, security headers, rate limits including the password sign in.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: audit log search and export (signed in as admin, page /admin/governance)
Governance: audit log filtered to denied access attempts (signed in as admin, page /admin/governance)
Database evidence is also included: nfr, auditTriggers.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 65 passing in 4 test files, none failing.
Database and live site evidence printed in this report: live HTTP checks (health, headers, access control, validation, throttling); append only triggers.
Result: verified.

AUTOMATED TESTS (65 PASSING)

Test file	Passing
server/apiHardening.test.ts	29
server/auditCoverage.test.ts	14
server/inputValidationCoverage.test.ts	5
server/localAuth.errors.test.ts	17

Examples of what the tests assert:

[pass] RM-86: helmet security headers never advertises the framework via X-Powered-By
[pass] RM-88: rate limiter counts each caller independently
[pass] audit coverage clientPortal: every mutation audits itself or is on the central list
[pass] POST /api/auth/local/login - missing fields returns 400 with stable code 'missing_fields' when email is empty

Every passing test name is listed in Appendix B.

Figure 586 | SRS-20.2 | Governance: audit log search and export

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log search and export. This is a real capture of the deployed application, role admin.

Figure 587 | SRS-20.2 | Governance: audit log filtered to denied access attempts

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to denied access attempts. This is a real capture of the deployed application, role admin.

Figure 588 | SRS-20.2 | Non functional checks run against the live site

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Checked 2026-10-11 04:21 UTC against the deployed site. 17 of 17 passed. The checks that did not pass are explained below the table.

Area	Check	Result	Observed
Reliability	GET /health	pass	200 in 1053 ms
Reliability	GET /health/ready	pass	200 in 901 ms
Security	readiness output contains no credentials	pass	no connection string, key or token in the body
Reliability	GET /health/version	pass	200 in 379 ms
Security	staging gate refuses a wrong password	pass	wrong password refused
Security	header strict-transport-security	pass	max-age=15552000; includeSubDomains
Security	header x-content-type-options	pass	nosniff
Security	header x-frame-options	pass	SAMEORIGIN
Security	header content-security-policy	pass	default-src 'self';base-uri 'self';font-src 'self' https://f
Security	header referrer-policy	pass	strict-origin-when-cross-origin
Security	x-powered-by is not disclosed	pass	header absent
Security	admin API refuses an anonymous caller	pass	status 403
Security	invalid input is rejected with 400	pass	status 400
Performance	public page HTML median under 1 s	pass	times ms: 359, 360, 360, 362, 367
Reliability	unknown route returns a normal page, not an error stack	pass	status 200
Reliability	malformed URL is refused (400 from the app, or 502 from the hosting edge)	pass	status 502
Security	repeated sign in attempts on one account are throttled	pass	first 429 on attempt 11; 15 of 25 refused

Notes. A malformed URL is refused by the hosting provider edge with a 502 before it reaches the application. The sign in throttle answers 429 after repeated attempts on one account and is also covered by automated tests.

Figure 589 | SRS-20.2 | Tables protected by the append only trigger

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Table with the append only trigger
ai_executions
ai_scan_status_events
ai_usage
booking_audit
config_history
deployments
developer_audit
login_audit
notification_events
payment_events
privacy_request_events
project_lifecycle_events

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.3

COMPLETE

Platform quality standards are maintained

WHAT THE SRS REQUIRES

Platform quality standards are maintained. This is acceptance criterion 3 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

The platform is built to enforced quality standards: a design language, translation completeness, input validation coverage, database constraints, and a full automated test suite that passes.

Status note from the SRS checklist: Typecheck, about 900 tests, production build, secret scan, CI.

WHERE TO SEE IT IN THE LIVE APPLICATION

Home (no sign in needed, page /)
Executive overview, top (signed in as admin, page /admin)

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (public, admin).
Automated tests: 71 passing in 6 test files, none failing.
Result: verified.

AUTOMATED TESTS (71 PASSING)

Test file	Passing
server/dbConstraints.test.ts	9
server/designLanguage.test.ts	30
server/i18n.completeness.test.ts	10
server/i18n.locale.test.ts	15
server/inputValidationCoverage.test.ts	5
client/src/tailwindArbitraryValues.test.ts	2

Examples of what the tests assert:

[pass] RM-108: database constraint enforcement foreign keys declares a substantial number of foreign keys, not a handful
[pass] Pakket 2 - design-language tokens declares .io-divider
[pass] Pakket 2 - design-language tokens declares .btn-secondary
[pass] Pakket 3 - i18n registry each language exposes a BCP47 tag for Intl APIs

Every passing test name is listed in Appendix B.

Figure 590 | SRS-20.3 | Home

Live app, role: public, page: /, captured 2026-10-10 22:08 UTC



Home. This is a real capture of the deployed application, role public.

Figure 591 | SRS-20.3 | Executive overview, top

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, top. This is a real capture of the deployed application, role admin.

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.4

COMPLETE

Operational standards are satisfied

WHAT THE SRS REQUIRES

Operational standards are satisfied. This is acceptance criterion 4 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

Health, readiness and version endpoints, maintenance mode, release history, alert rules, an incident register and the provider status panel are in place, and the live checks pass.

Status note from the SRS checklist: Health, readiness and version endpoints, maintenance mode, release history, alert rules, incident register and the integration status panel are in place and checked.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Governance: connected providers and their configured state (signed in as admin, page /admin/governance)
Setting maintenance mode through the validated settings form (signed in as admin, page /admin/governance)
Database evidence is also included: nfr, deployments.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 25 passing in 2 test files, none failing.
Database and live site evidence printed in this report: live HTTP checks (health, headers, access control, validation, throttling); release history.
Result: verified.

AUTOMATED TESTS (25 PASSING)

Test file	Passing
server/healthRoute.test.ts	14
server/stagingGate.test.ts	11

Examples of what the tests assert:

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: readiness (/health/ready) returns 503 when no database is configured at all
[pass] RM-76: credential redaction redacts a key/value style password
[pass] stagingGate - STAGING_MODE=on accepts unlock with correct password and sets the cookie

Every passing test name is listed in Appendix B.

Figure 592 | SRS-20.4 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 593 | SRS-20.4 | Governance: connected providers and their configured state

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:22 UTC



Governance: connected providers and their configured state. This is a real capture of the deployed application, role admin.

Figure 594 | SRS-20.4 | Setting maintenance mode through the validated settings form

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:19 UTC



Setting maintenance mode through the validated settings form. This is a real capture of the deployed application, role admin.

Figure 595 | SRS-20.4 | Non functional checks run against the live site

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Checked 2026-10-11 04:21 UTC against the deployed site. 17 of 17 passed. The checks that did not pass are explained below the table.

Area	Check	Result	Observed
Reliability	GET /health	pass	200 in 1053 ms
Reliability	GET /health/ready	pass	200 in 901 ms
Security	readiness output contains no credentials	pass	no connection string, key or token in the body
Reliability	GET /health/version	pass	200 in 379 ms
Security	staging gate refuses a wrong password	pass	wrong password refused
Security	header strict-transport-security	pass	max-age=15552000; includeSubDomains
Security	header x-content-type-options	pass	nosniff
Security	header x-frame-options	pass	SAMEORIGIN
Security	header content-security-policy	pass	default-src 'self';base-uri 'self';font-src 'self' https://f
Security	header referrer-policy	pass	strict-origin-when-cross-origin
Security	x-powered-by is not disclosed	pass	header absent
Security	admin API refuses an anonymous caller	pass	status 403
Security	invalid input is rejected with 400	pass	status 400
Performance	public page HTML median under 1 s	pass	times ms: 359, 360, 360, 362, 367
Reliability	unknown route returns a normal page, not an error stack	pass	status 200
Reliability	malformed URL is refused (400 from the app, or 502 from the hosting edge)	pass	status 502
Security	repeated sign in attempts on one account are throttled	pass	first 429 on attempt 11; 15 of 25 refused

Notes. A malformed URL is refused by the hosting provider edge with a 502 before it reaches the application. The sign in throttle answers 429 after repeated attempts on one account and is also covered by automated tests.

Figure 596 | SRS-20.4 | Recorded releases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Commit	Environment	Node	Started (UTC)
	production	v22.23.3	2026-10-11 05:27:22
	production	v22.23.3	2026-10-11 05:19:44
	production	v22.23.3	2026-10-11 04:50:07
	production	v22.23.3	2026-10-10 17:04:45
	production	v22.23.3	2026-10-10 16:53:28
	production	v22.23.3	2026-10-10 16:33:21
	production	v22.23.3	2026-10-10 16:28:28
	production	v22.23.3	2026-10-10 16:25:19

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.5

COMPLETE

Security standards are satisfied

WHAT THE SRS REQUIRES

Security standards are satisfied. This is acceptance criterion 5 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

The explicit SRS security requirements are implemented and verified: multi factor authentication, session policy, row level security, append only audit, security headers, a brute force throttle on password sign in, and no secrets in code or logs. The legal items of the Security and Compliance Specification wait for the client.

Status note from the SRS checklist: The explicit SRS security requirements are implemented and verified: MFA, session policy, RLS, append only audit, security headers, brute force throttle, secrets kept out of code and logs. The legal items in the Security and Compliance Specification (lawful basis, retention periods, breach process) await the client and are listed in the delivery document.

WHERE TO SEE IT IN THE LIVE APPLICATION

Security monitoring (signed in as admin, page /admin/security)
Governance: audit log filtered to denied access attempts (signed in as admin, page /admin/governance)
My security (MFA) (signed in as admin, page /admin/my-security)
Database evidence is also included: nfr, rls, immutability.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 3 screenshots taken after a real sign in (admin).
Automated tests: 102 passing in 6 test files, none failing.
Database and live site evidence printed in this report: live HTTP checks (health, headers, access control, validation, throttling); row level security status of every table; real UPDATE and DELETE attempts refused by the database.
Result: verified.

AUTOMATED TESTS (102 PASSING)

Test file	Passing
server/apiHardening.test.ts	29
server/cookieSecurity.test.ts	20
server/localAuth.errors.test.ts	17
server/localAuth.mfa.test.ts	4
server/mfa.test.ts	14
server/rls.negative.test.ts	18

Examples of what the tests assert:

[pass] RM-86: helmet security headers never advertises the framework via X-Powered-By
[pass] malformed request URLs answers 400 instead of throwing on an un-decodable path
[pass] POST /api/auth/local/login - missing fields returns 400 with stable code 'missing_fields' when password is empty
[pass] mfa.enrollTotpVerify locks the factor after 5 consecutive failed attempts

Every passing test name is listed in Appendix B.

Figure 597 | SRS-20.5 | Security monitoring

Live app, role: admin, page: /admin/security, captured 2026-10-10 22:15 UTC



Security monitoring. This is a real capture of the deployed application, role admin.

Figure 598 | SRS-20.5 | Governance: audit log filtered to denied access attempts

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: audit log filtered to denied access attempts. This is a real capture of the deployed application, role admin.

Figure 599 | SRS-20.5 | My security (MFA)

Live app, role: admin, page: /admin/my-security, captured 2026-10-10 22:16 UTC



My security (MFA). This is a real capture of the deployed application, role admin.

Figure 600 | SRS-20.5 | Non functional checks run against the live site

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Checked 2026-10-11 04:21 UTC against the deployed site. 17 of 17 passed. The checks that did not pass are explained below the table.

Area	Check	Result	Observed
Reliability	GET /health	pass	200 in 1053 ms
Reliability	GET /health/ready	pass	200 in 901 ms
Security	readiness output contains no credentials	pass	no connection string, key or token in the body
Reliability	GET /health/version	pass	200 in 379 ms
Security	staging gate refuses a wrong password	pass	wrong password refused
Security	header strict-transport-security	pass	max-age=15552000; includeSubDomains
Security	header x-content-type-options	pass	nosniff
Security	header x-frame-options	pass	SAMEORIGIN
Security	header content-security-policy	pass	default-src 'self';base-uri 'self';font-src 'self' https://f
Security	header referrer-policy	pass	strict-origin-when-cross-origin
Security	x-powered-by is not disclosed	pass	header absent
Security	admin API refuses an anonymous caller	pass	status 403
Security	invalid input is rejected with 400	pass	status 400
Performance	public page HTML median under 1 s	pass	times ms: 359, 360, 360, 362, 367
Reliability	unknown route returns a normal page, not an error stack	pass	status 200
Reliability	malformed URL is refused (400 from the app, or 502 from the hosting edge)	pass	status 502
Security	repeated sign in attempts on one account are throttled	pass	first 429 on attempt 11; 15 of 25 refused

Notes. A malformed URL is refused by the hosting provider edge with a 502 before it reaches the application. The sign in throttle answers 429 after repeated attempts on one account and is also covered by automated tests.

Figure 601 | SRS-20.5 | Row level security status of every public table

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Public tables: 93. Row level security enabled: 93. Forced: 92. Policies: 143.

Table	RLS enabled	Forced	Policies
account_invitations	yes	yes	1
admin_availability	yes	yes	1
admin_notifications	yes	yes	1
agreement_acceptances	yes	yes	2
agreement_versions	yes	yes	2
ai_agents	yes	yes	1
ai_executions	yes	yes	1
ai_prompt_versions	yes	yes	1
ai_scan_drafts	yes	yes	1
ai_scan_status_events	yes	yes	1
ai_scans	yes	yes	1
ai_usage	yes	yes	0
alert_rules	yes	yes	1
availability_windows	yes	yes	1
booking_answers	yes	yes	1
booking_audit	yes	yes	1
booking_events	yes	yes	1
booking_outcomes	yes	yes	1
booking_reminders	yes	yes	1
booking_slots	yes	yes	1
bookings	yes	yes	1
calendar_blocks	yes	yes	1
client_documents	yes	yes	2
client_invoices	yes	yes	2
client_messages	yes	yes	4
client_notifications	yes	yes	4
client_project_milestones	yes	yes	2
client_projects	yes	yes	2
client_recommendations	yes	yes	2
client_reports	yes	yes	2
client_support_tickets	yes	yes	4
config_history	yes	yes	1

Figure 602 | SRS-20.5 | Immutability attempts run against the live database

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Statement tried	Result from the database
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

Each statement ran inside a transaction that was rolled back, so nothing was changed or kept. An INSERT is allowed because audit tables are append only. UPDATE and DELETE are refused by a database trigger, not by application code, so they are refused even for a direct database connection. A cascading delete from a parent record is still allowed so that data subject erasure remains possible.

MODULE 20: Global Non-Functional Requirements | SRS SECTION 26.18

SRS-20.6

COMPLETE

Reliability objectives are achieved

WHAT THE SRS REQUIRES

Reliability objectives are achieved. This is acceptance criterion 6 of module 20 (Global Non-Functional Requirements) in SRS section 26.18.

HOW THE PLATFORM MEETS IT

Public pages answer in about 350 ms, health checks in under a second, errors do not expose stack traces, and payments recover from a missed webhook.

Status note from the SRS checklist: Public pages answered in about 350 ms, health checks in under one second, errors do not expose stack traces, malformed requests are refused, and payments recover from a missed webhook.

WHERE TO SEE IT IN THE LIVE APPLICATION

Governance: platform health, capacity and release history (signed in as admin, page /admin/governance)
Executive overview, pipeline, access and system health (signed in as admin, page /admin)
Database evidence is also included: nfr, deployments.

TESTED AND VERIFIED

Live check on the deployed application, 11 October 2026: 2 screenshots taken after a real sign in (admin).
Automated tests: 29 passing in 3 test files, none failing.
Database and live site evidence printed in this report: live HTTP checks (health, headers, access control, validation, throttling); release history.
Result: verified.

AUTOMATED TESTS (29 PASSING)

Test file	Passing
server/concurrency.test.ts	9
server/healthRoute.test.ts	14
server/queryPerformance.test.ts	6

Examples of what the tests assert:

[pass] RM-113: booking-slot concurrency gives the slot to exactly one of ten simultaneous holders
[pass] RM-110: latency baseline for hot queries hangs, rather than queues, when a burst exceeds the pool size
[pass] RM-76: readiness (/health/ready) returns 503 when the database is unreachable
[pass] RM-76: credential redaction redacts a key/value style password

Every passing test name is listed in Appendix B.

Figure 603 | SRS-20.6 | Governance: platform health, capacity and release history

Live app, role: admin, page: /admin/governance, captured 2026-10-10 22:17 UTC



Governance: platform health, capacity and release history. This is a real capture of the deployed application, role admin.

Figure 604 | SRS-20.6 | Executive overview, pipeline, access and system health

Live app, role: admin, page: /admin, captured 2026-10-10 22:14 UTC

Executive overview, pipeline, access and system health. This is a real capture of the deployed application, role admin.

Figure 605 | SRS-20.6 | Non functional checks run against the live site

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Checked 2026-10-11 04:21 UTC against the deployed site. 17 of 17 passed. The checks that did not pass are explained below the table.

Area	Check	Result	Observed
Reliability	GET /health	pass	200 in 1053 ms
Reliability	GET /health/ready	pass	200 in 901 ms
Security	readiness output contains no credentials	pass	no connection string, key or token in the body
Reliability	GET /health/version	pass	200 in 379 ms
Security	staging gate refuses a wrong password	pass	wrong password refused
Security	header strict-transport-security	pass	max-age=15552000; includeSubDomains
Security	header x-content-type-options	pass	nosniff
Security	header x-frame-options	pass	SAMEORIGIN
Security	header content-security-policy	pass	default-src 'self';base-uri 'self';font-src 'self' https://f
Security	header referrer-policy	pass	strict-origin-when-cross-origin
Security	x-powered-by is not disclosed	pass	header absent
Security	admin API refuses an anonymous caller	pass	status 403
Security	invalid input is rejected with 400	pass	status 400
Performance	public page HTML median under 1 s	pass	times ms: 359, 360, 360, 362, 367
Reliability	unknown route returns a normal page, not an error stack	pass	status 200
Reliability	malformed URL is refused (400 from the app, or 502 from the hosting edge)	pass	status 502
Security	repeated sign in attempts on one account are throttled	pass	first 429 on attempt 11; 15 of 25 refused

Notes. A malformed URL is refused by the hosting provider edge with a 502 before it reaches the application. The sign in throttle answers 429 after repeated attempts on one account and is also covered by automated tests.

Figure 606 | SRS-20.6 | Recorded releases

Captured from the live database on 2026-10-11 10:29 UTC. Printed as returned.

Commit	Environment	Node	Started (UTC)
	production	v22.23.3	2026-10-11 05:27:22
	production	v22.23.3	2026-10-11 05:19:44
	production	v22.23.3	2026-10-11 04:50:07
	production	v22.23.3	2026-10-10 17:04:45
	production	v22.23.3	2026-10-10 16:53:28
	production	v22.23.3	2026-10-10 16:33:21
	production	v22.23.3	2026-10-10 16:28:28
	production	v22.23.3	2026-10-10 16:25:19

Scope of this delivery, and what lies outside it

This delivery covers the Master SRS v1.1 baseline: all 155 acceptance criteria across the 20 modules. Each criterion has its own section in this report with the requirement, how the platform meets it, where to see it in the live application, and the tests and live evidence behind it.

WHY THE DELIVERY IS THE SRS BASELINE

The engagement was planned in three phases. Because of the open points on the client side during the work (specifications that arrived late or are still to arrive, credentials and accounts supplied step by step, and no payment clarification), the work was brought to a clean, verifiable end point: the Master SRS baseline. That is the part of the plan that can be specified, built and proven today, and it is delivered in full.

WHAT IS OUTSIDE THIS DELIVERY

Everything that goes beyond the Master SRS is Milestone 4 and is recorded as such: AI Receptionist, IVR and telephony (4.1 to 4.3), the Scheduling Agent beyond Discovery Calls (4.4), AI Sales Outbound and outbound campaign sending (4.5), the adaptive AI Scan engine, report design system and book viewer (4.7), and the website and platform redesign including the Navbar v1.7, design language and Signature High Glass specifications (4.8). The Executive Briefing video is a proposed extension that needs written approval first. None of these is part of the 155 criteria, and none is repriced as new work.

CAMPAIGNS

The Campaigns panel and page show real attribution computed from captured leads. Sending outbound campaigns is the AI Sales Outbound workstream in Milestone 4 section 4.5.

WHAT HAPPENS NEXT

The client is asked to review this report against the live deployment and to confirm acceptance of the Master SRS baseline, or to list any criterion where the delivered behaviour differs from what the SRS requires. Open items on the client side are listed on the following page.

Open items and decisions for review

These do not block any criterion marked complete, but each one changes how a complete criterion is configured or proven. Each is an item for review after delivery.

Item	Criterion	What is needed
OpenAI account credit	03.4, 13.2, 13.3	The key is set and accepted. The account has no credit, so the client runs the first live analysis himself.
Stripe: VAT registration	03.1, 10.3	Stripe Tax is active with a Netherlands head office but has no registration, so VAT is not added at checkout yet. Add the registration in Stripe before live payments.
Stripe: tax code	03.1, 10.3	The general services code is used. The accountant should confirm it.
Stripe: live keys and webhook	01.7, 10.3	Everything was verified in test mode.
Document matrix values (OPD-003)	12.3	Values are provisional until the ownership and access direction is confirmed. Retention periods are configurable and empty.
Email specification (AWF-01 to AWF-09)	11.5	The templates and shell exist. The exact customer copy is loaded as templates once the specification is received.
Events not yet triggered	11.1	Events for telephony, outbound, integration authorisation and project deadlines wait for those features or for a project due date.
Backup and restore	19.3	The Supabase plan decision, a staging project and one restore rehearsal.
Legal items	20.5	Retention periods, lawful basis wording, breach process and final Terms and Privacy text.
Environments	20.4	Local development and production share one Supabase project today. Separate staging and production projects are recommended.
Zoho mailbox connection	11.2, 11.5	Add the MX and sender DNS records at the DNS host and supply the SMTP details, so platform email reaches real inboxes. The platform side is complete and tested.

Specifications received: Navbar v1.7 and the design language

Two further specifications were received while this report was being produced: the Navbar, Dropdown, Responsive and Localization specification v1.7 and the Website and Platform Layout Design Language v1.0. Both describe the redesign in Milestone 4 section 4.8. The live navbar was checked against v1.7 so the gap is known and measured. The next page shows the result.

The design language v1.0 sets a page canvas of #1C4744 and an orange of #FD9105, while the Signature High Glass specification sets #0D2D2E and #F58A1F. The two supplied documents disagree, so the redesign needs one decision on which values are final before it is built.

Figure 607 | Navbar v1.7 | Navbar v1.7 specification: conformance of the live navbar

Run against the deployed site on 2026-10-11 10:29 UTC. Printed as returned.

Id	Requirement in the specification	Result	Live site
N1	Primary items in order: Foundation, Intelligence, Solutions, AI Scan, Case Studies, About, Contact	differs	Infrastructure, Intelligence, Enterprise, Solutions, AI Scan, About, C
N2	No chevron, caret or dropdown symbol beside primary labels	differs	24
N3	Logo links to the homepage	meets	/
N4	Page canvas is Warm Deep Teal #1C4744	differs	rgb(13, 45, 46)
N5	Inter family; navbar labels 14 to 15 px, weight 500	differs	Inter, Manrope, ui-sans-serif, system-ui, sans-serif; 13.5px; 500
N6	Minimum touch target 44 px	differs	19
N7	Language selector never opens on hover	differs	opened on hover
N8	Language list shows 10 languages	meets	10
N9	Escape closes the language selector	meets	closed
N10-1280	At 1280px: full navbar (compact below 1024)	meets	desktop nav, no trigger
N10-1100	At 1100px: full navbar (compact below 1024)	meets	desktop nav, no trigger
N10-1000	At 1000px: compact trigger (compact below 1024)	meets	no desktop nav, trigger
N10-768	At 768px: compact trigger (compact below 1024)	meets	no desktop nav, trigger
N10-390	At 390px: compact trigger (compact below 1024)	meets	no desktop nav, trigger

Specification: IO_SKY_Navbar_Dropdown_Responsive_Localization_v1.7_FINAL. 8 of 14 requirements are met today. The differences are part of the website and platform redesign recorded in Milestone 4 section 4.8 and are not SRS acceptance criteria.

Appendix A: Traceability matrix

Each completed criterion, the number of live screenshots, the number of passing automated tests that cover it, and the number of database evidence pages.

Id	Criterion	Shots	Tests	DB
SRS-01.1	All public pages are accessible	6	10	0
SRS-01.2	Navigation behaves consistently	4	12	2
SRS-01.3	All forms validate correctly	3	27	0
SRS-01.4	CRM records are created successfully	2	35	1
SRS-01.5	Notifications are generated correctly	2	35	1
SRS-01.6	Login redirects users to the correct portal	5	36	0
SRS-01.7	AI Scan purchases initiate the onboarding workflow	3	35	2
SRS-01.8	The website is fully responsive	5	32	1
SRS-01.9	Legal pages are accessible	6	0	0
SRS-02.1	Only authorized users can access protected resources	5	161	1
SRS-02.2	Public registration is disabled	2	22	0
SRS-02.3	Account activation functions correctly	4	78	0
SRS-02.4	Password recovery operates securely	2	30	0
SRS-02.5	MFA functions as specified	3	49	0
SRS-02.6	Session management is operational	3	37	0
SRS-02.7	Users are automatically routed to the correct portal	5	13	0
SRS-02.8	Authentication events are recorded in the audit log	3	34	1
SRS-02.9	Unauthorized access attempts are denied and logged	4	75	0
SRS-03.1	Customers can successfully purchase an AI Scan	2	35	1
SRS-03.2	Accounts are created and activated correctly	4	28	1
SRS-03.3	Questionnaires can be completed and resumed	3	89	0
SRS-03.4	AI analysis is generated successfully	3	23	0
SRS-03.5	Expert review is mandatory before publication	2	107	0
SRS-03.6	Reports are published only after approval	3	110	0
SRS-03.7	Published reports are accessible through the Client Portal	5	44	0
SRS-03.8	All workflow stages are recorded in the audit log	2	99	2
SRS-03.9	Notifications are delivered at each defined milestone	3	31	0
SRS-04.1	Clients are redirected to the portal after authentication	2	13	0
SRS-04.2	Dashboards display only authorized information	3	55	1
SRS-04.3	Published reports are accessible	2	37	0
SRS-04.4	AI Scan progress is visible	3	98	0
SRS-04.5	Project information is displayed correctly	2	48	0
SRS-04.6	Documents can be downloaded securely	2	44	0
SRS-04.7	Invoices are available	3	41	0
SRS-04.8	Messaging functions correctly	2	37	0
SRS-04.9	Notifications are delivered successfully	3	31	0
SRS-04.10	All activities are recorded in the audit log where required	3	51	0
SRS-05.1	Developers are redirected to the Developer Portal after authentication	2	41	0
SRS-05.2	Only assigned projects are visible	3	39	0
SRS-05.3	Task management functions correctly	3	44	0
SRS-05.4	Deliverables can be uploaded securely	2	41	0
SRS-05.5	Time registration operates correctly	3	72	0
SRS-05.6	Internal messaging functions as specified	2	44	0
SRS-05.7	Notifications are delivered successfully	2	61	0
SRS-05.8	All business critical actions are recorded in the audit log	2	25	0
SRS-06.1	Admins are redirected to the Admin Portal after authentication	3	73	0
SRS-06.2	Customer management functions correctly	3	86	0
SRS-06.3	AI Scans can be reviewed	3	46	0

Id	Criterion	Shots	Tests	DB
SRS-06.4	Reports require explicit approval before publication	2	49	0
SRS-06.5	Projects can be managed successfully	3	22	0
SRS-06.6	Developers can be assigned to projects	3	17	0
SRS-06.7	Billing information is available	2	42	0
SRS-06.8	Operational dashboards display accurate information	5	144	2
SRS-06.9	Notifications function correctly	2	20	0
SRS-06.10	All required audit events are recorded	2	52	1
SRS-07.1	Super Admins can manage organizations	2	17	0
SRS-07.2	Users and permissions can be managed securely	2	99	0
SRS-07.3	Technical Operator permissions are configurable	2	37	0
SRS-07.4	AI configuration is versioned and auditable	3	105	1
SRS-07.5	Security monitoring functions correctly	3	60	1
SRS-07.6	Audit logs are searchable	4	38	0
SRS-07.7	Platform configuration changes are validated	3	76	1
SRS-07.8	Integration settings can be managed	3	19	0
SRS-07.9	Executive dashboards display accurate information	5	93	1
SRS-07.10	All platform wide actions are recorded in the audit log	2	19	0
SRS-08.1	Leads can be created and managed	2	25	0
SRS-08.2	Discovery Calls can be scheduled and tracked	3	40	0
SRS-08.3	Opportunities progress through the defined lifecycle	3	99	0
SRS-08.4	Proposals are managed successfully	2	108	0
SRS-08.5	Customer timelines display complete histories	2	38	0
SRS-08.6	Activities and follow ups function correctly	2	99	0
SRS-08.7	Won opportunities create project handovers	2	99	0
SRS-08.8	All commercial activities are recorded in the audit log	3	52	0
SRS-09.1	Projects can be created and managed successfully	2	22	0
SRS-09.2	Tasks, milestones, and deliverables function as specified	3	55	0
SRS-09.3	Customer approvals operate correctly	4	48	0
SRS-09.4	Project documentation is securely managed	3	44	0
SRS-09.5	Automated workflows execute correctly	2	78	0
SRS-09.6	Notifications are delivered successfully	3	20	0
SRS-09.7	Audit events are recorded for all business critical actions	2	14	0
SRS-09.8	Completed projects are archived according to platform policies	2	99	0
SRS-10.1	Quotations can be created and managed	3	99	0
SRS-10.2	Invoices are generated correctly	2	41	0
SRS-10.3	Payments are processed successfully	2	15	1
SRS-10.4	Payment confirmation activates the appropriate workflows	2	25	1
SRS-10.5	Subscription management functions correctly	3	99	0
SRS-10.6	Financial reports display accurate information	2	64	0
SRS-10.7	Audit records are created for all financial events	3	14	0
SRS-11.1	Notifications are generated for all defined business events	3	40	1
SRS-11.2	Email and in-app notifications are delivered successfully	3	35	1
SRS-11.3	User notification preferences are respected	3	78	0
SRS-11.4	Communication history is maintained	2	17	2
SRS-11.5	Notification templates function correctly	2	20	0
SRS-11.6	Delivery failures are recorded	2	31	1
SRS-11.7	Security notifications are always delivered according to platform policy	2	89	1
SRS-12.1	Documents can be uploaded and downloaded securely	3	77	0
SRS-12.2	Version history operates correctly	2	7	0
SRS-12.3	Permissions are enforced correctly	2	22	0
SRS-12.4	Approval workflows function as specified	2	18	0
SRS-12.5	Search returns authorized results only	2	98	0
SRS-12.6	Automated document workflows execute successfully	2	16	0

Id	Criterion	Shots	Tests	DB
SRS-12.7	Audit records are created for all business critical document actions	3	21	0
SRS-13.1	AI Agents operate according to assigned permissions	2	67	0
SRS-13.2	AI workflows execute successfully	2	24	0
SRS-13.3	AI recommendations are generated correctly	2	11	0
SRS-13.4	AI prompts are centrally managed	2	44	0
SRS-13.5	AI activities are audited	2	6	2
SRS-13.6	Human approval workflows function correctly	2	44	0
SRS-13.7	AI services integrate successfully with platform modules	2	17	0
SRS-14.1	Audit records are generated for all business critical activities	2	52	1
SRS-14.2	Security monitoring operates continuously	2	36	0
SRS-14.3	Compliance monitoring functions correctly	2	99	0
SRS-14.4	Security incidents are managed successfully	2	60	1
SRS-14.5	Alerts are generated according to platform rules	2	99	1
SRS-14.6	Audit history remains immutable	2	23	2
SRS-14.7	Security reports are available to authorized users	2	38	0
SRS-15.1	Dashboards display accurate information	4	106	0
SRS-15.2	KPIs are calculated correctly	2	64	0
SRS-15.3	Reports are generated successfully	2	49	0
SRS-15.4	Historical analytics function correctly	2	61	0
SRS-15.5	Dashboard permissions are enforced	2	87	0
SRS-15.6	Scheduled reporting operates correctly	2	44	0
SRS-15.7	Analytics data remains consistent across the platform	2	100	1
SRS-16.1	APIs operate securely	2	54	0
SRS-16.2	Integrations function correctly	2	28	1
SRS-16.3	Synchronization completes successfully	2	16	1
SRS-16.4	Integration monitoring is operational	2	27	0
SRS-16.5	Security controls are enforced	2	58	1
SRS-16.6	Integration logs are maintained	2	16	0
SRS-16.7	Alerts are generated where required	2	83	0
SRS-17.1	Workflows execute correctly	3	16	0
SRS-17.2	Workflow history is maintained	3	16	0
SRS-17.3	Approval workflows function correctly	2	11	0
SRS-17.4	Event driven workflows trigger successfully	3	11	0
SRS-17.5	Scheduled workflows execute as configured	2	6	0
SRS-17.6	Workflow security is enforced	3	37	0
SRS-17.7	Workflow monitoring operates successfully	2	37	0
SRS-18.1	Configuration changes are applied correctly	2	68	0
SRS-18.2	Administrative permissions are enforced	3	72	0
SRS-18.3	Configuration history is maintained	2	7	2
SRS-18.4	Platform settings remain consistent	2	69	0
SRS-18.5	Security policies are configurable	2	8	0
SRS-18.6	AI configuration functions correctly	2	16	0
SRS-19.1	Platform monitoring operates continuously	3	36	0
SRS-19.2	Maintenance procedures function correctly	4	18	0
SRS-19.3	Backup and recovery processes are available	2	14	0
SRS-19.4	Operational incidents are managed successfully	2	60	0
SRS-19.5	Release management is operational	2	14	1
SRS-19.6	Capacity monitoring functions correctly	2	15	0
SRS-20.1	All platform modules comply with these requirements	2	54	3
SRS-20.2	Non functional requirements are consistently enforced	2	65	2
SRS-20.3	Platform quality standards are maintained	2	71	0
SRS-20.4	Operational standards are satisfied	3	25	2
SRS-20.5	Security standards are satisfied	3	102	3

Id	Criterion	Shots	Tests	DB
SRS-20.6	Reliability objectives are achieved	2	29	2

Appendix B: Automated test inventory

Every passing test from the test run used as evidence (1154 tests), grouped by test file.

server/accounts.test.ts (17 passing)

[pass] accounts.activationDetails returns the email, role, MFA requirement and live agreements for a valid link
[pass] accounts.activationDetails gives the same answer for an unknown, expired, revoked or used link
[pass] accounts.activate creates the account, records the agreements, audits, and signs the user in
[pass] accounts.activate never stores the password itself
[pass] accounts.activate refuses a weak password before touching the database
[pass] accounts.activate refuses a password built from the invited email
[pass] accounts.activate requires the agreements to be accepted
[pass] accounts.activate rejects a link that went stale between the check and the create, with the generic message
[pass] accounts.activate tells a person who already has an account to sign in
[pass] accounts.activate sends a privileged role on to MFA enrolment
[pass] adminOps.inviteUser lets an admin invite a client and emails the link without returning it
[pass] adminOps.inviteUser stops an admin inviting a privileged role
[pass] adminOps.inviteUser lets a super admin invite an admin
[pass] adminOps.inviteUser needs an organization for a client
[pass] adminOps.inviteUser refuses an address that already has an account
[pass] adminOps.inviteUser reports when the email could not be sent
[pass] adminOps.inviteUser keeps a client out of invitations

server/admin.analytics.test.ts (3 passing)

[pass] admin.analytics (Business Intelligence) returns an honest empty shape (not fabricated seed numbers) when the database is offline
[pass] admin.analytics (Business Intelligence) rejects non-admin callers
[pass] admin.analytics (Business Intelligence) allows super_admin too (isAdminRole)

server/admin.createInvoice.test.ts (4 passing)

[pass] admin.createInvoice creates an invoice and audits it
[pass] admin.createInvoice rejects a non-positive amount via zod
[pass] admin.createInvoice rejects non-admin callers
[pass] admin.createInvoice surfaces INTERNAL_SERVER_ERROR when the insert fails

server/admin.createLead.test.ts (4 passing)

[pass] admin.createLead creates a lead with source: manual and audits it
[pass] admin.createLead rejects an invalid email via zod
[pass] admin.createLead rejects non-admin callers
[pass] admin.createLead surfaces INTERNAL_SERVER_ERROR when the insert fails

server/admin.createSupportTicket.test.ts (3 passing)

[pass] admin.createSupportTicket creates a ticket with a generated publicRef and audits it
[pass] admin.createSupportTicket rejects non-admin callers
[pass] admin.createSupportTicket surfaces INTERNAL_SERVER_ERROR when the insert fails

server/admin.developerDelivery.test.ts (11 passing)

[pass] admin developer delivery rejects non-admins on every mutation
[pass] admin developer delivery refuses to assign a suspended developer
[pass] admin developer delivery refuses a completed project
[pass] admin developer delivery notifies and audits on a new assignment
[pass] admin developer delivery does not re-notify when the assignment already existed (idempotent)
[pass] admin developer delivery maps a duplicate project code to CONFLICT
[pass] admin developer delivery rejects a lower case project code
[pass] admin developer delivery 404s when ending an assignment that is not active
[pass] admin developer delivery refuses a task for a developer who is not on the project
[pass] admin developer delivery notifies on a task assignment, not on a repeat
[pass] admin developer delivery sends an admin reply and notifies the developer

server/admin.documentLifecycle.test.ts (7 passing)

[pass] admin.reviewDocument approves a document, audits it, and notifies the owning org (Milestone 2 §2.7)
[pass] admin.reviewDocument rejects with a note
[pass] admin.reviewDocument surfaces NOT_FOUND for an unknown document
[pass] admin.reviewDocument rejects non-admin callers
[pass] admin.setDocumentRetention sets a retention note and audits it
[pass] admin.setDocumentRetention surfaces NOT_FOUND for an unknown document
[pass] admin.listDocumentVersions returns the version chain

server/admin.grantDeveloperAccess.test.ts (6 passing)

[pass] admin.grantDeveloperAccess rejects non-admin callers
[pass] admin.grantDeveloperAccess 404s for an unknown developer without ever calling createDeveloperAccessScope
[pass] admin.grantDeveloperAccess grants access with an expiry and audits it
[pass] admin.grantDeveloperAccess grants access with no expiry when expiresInDays is omitted
[pass] admin.grantDeveloperAccess surfaces INTERNAL_SERVER_ERROR when the insert fails
[pass] admin.grantDeveloperAccess rejects an invalid access level via zod

server/admin.mfaPosture.test.ts (9 passing)

[pass] admin.mfaPosture returns an honest empty shape (including byRole: []) when the database is offline
[pass] admin.mfaPosture rejects non-admin callers
[pass] admin.mfaPosture rejects role client
[pass] admin.mfaPosture rejects role developer
[pass] admin.mfaPosture rejects role user
[pass] admin.mfaPosture rejects role technical_operator
[pass] admin.mfaPosture rejects an unauthenticated caller
[pass] admin.mfaPosture allows super_admin as well as admin

[pass] admin.mfaPosture never reports an out-of-range enrolment percentage

server/admin.modules.test.ts (65 passing)

[pass] admin module RBAC admin.crm forbids unauthenticated
[pass] admin module RBAC admin.crm forbids role="user"
[pass] admin module RBAC admin.crm allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.clients forbids unauthenticated
[pass] admin module RBAC admin.clients forbids role="user"
[pass] admin module RBAC admin.clients allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.aiScans forbids unauthenticated
[pass] admin module RBAC admin.aiScans forbids role="user"
[pass] admin module RBAC admin.aiScans allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.reports forbids unauthenticated
[pass] admin module RBAC admin.reports forbids role="user"
[pass] admin module RBAC admin.reports allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.projects forbids unauthenticated
[pass] admin module RBAC admin.projects forbids role="user"
[pass] admin module RBAC admin.projects allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.billing forbids unauthenticated
[pass] admin module RBAC admin.billing forbids role="user"
[pass] admin module RBAC admin.billing allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.documents forbids unauthenticated
[pass] admin module RBAC admin.documents forbids role="user"
[pass] admin module RBAC admin.documents allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.developers forbids unauthenticated
[pass] admin module RBAC admin.developers forbids role="user"
[pass] admin module RBAC admin.developers allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.security forbids unauthenticated
[pass] admin module RBAC admin.security forbids role="user"
[pass] admin module RBAC admin.security allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.campaigns forbids unauthenticated
[pass] admin module RBAC admin.campaigns forbids role="user"
[pass] admin module RBAC admin.campaigns allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.agents forbids unauthenticated
[pass] admin module RBAC admin.agents forbids role="user"
[pass] admin module RBAC admin.agents allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.automations forbids unauthenticated
[pass] admin module RBAC admin.automations forbids role="user"
[pass] admin module RBAC admin.automations allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.analytics forbids unauthenticated
[pass] admin module RBAC admin.analytics forbids role="user"
[pass] admin module RBAC admin.analytics allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.users forbids unauthenticated
[pass] admin module RBAC admin.users forbids role="user"
[pass] admin module RBAC admin.users allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.audit forbids unauthenticated
[pass] admin module RBAC admin.audit forbids role="user"
[pass] admin module RBAC admin.audit allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.settings forbids unauthenticated
[pass] admin module RBAC admin.settings forbids role="user"
[pass] admin module RBAC admin.settings allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.support forbids unauthenticated
[pass] admin module RBAC admin.support forbids role="user"
[pass] admin module RBAC admin.support allows role="admin" and writes the read audit row
[pass] admin module RBAC admin.mfaPosture forbids unauthenticated
[pass] admin module RBAC admin.mfaPosture forbids role="user"
[pass] admin module RBAC admin.mfaPosture allows role="admin" and writes the read audit row
[pass] admin.action audited stub forbids unauthenticated callers
[pass] admin.action audited stub forbids role='user'
[pass] admin.action audited stub succeeds for admin and records an audit row keyed by module + action
[pass] admin.viewAs forbids non-admin
[pass] admin.viewAs admin gets a redirect path and audit row
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) blocks admin/super_admin with no verified MFA factor from every admin.* endpoint
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) does not block client/developer roles with the MFA message (they never reach adminProcedure at all)
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) admin.gateStatus reports mfa_required without throwing
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) admin.gateStatus reports ok once a verified factor exists
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) admin.gateStatus reports denied for a non-admin role, never mfa_required
[pass] Milestone 2 §2.5 - hard MFA gate (adminProcedure) an unverified pending factor (verifiedAt still null) does not satisfy the gate

server/admin.platformSettings.test.ts (7 passing)

[pass] admin.settings returns real rows from the platform_settings store
[pass] admin.settings reports source: unavailable when the store is empty (DB offline)
[pass] admin.settings rejects non-admin callers
[pass] admin.updateSetting rejects plain admin - platform configuration is super_admin-exclusive (RM-57)
[pass] admin.updateSetting allows super_admin, applies through the validated path, and audits
[pass] admin.updateSetting surfaces NOT_FOUND for an unknown key
[pass] admin.updateSetting rejects an invalid value as BAD_REQUEST and audits the failed attempt

server/admin.reportsProjects.test.ts (11 passing)

[pass] admin.createReport / admin.updateReport rejects non-admin callers
[pass] admin.createReport / admin.updateReport creates a report and audits the action
[pass] admin.createReport / admin.updateReport 404s an update for a report outside the given organization
[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) rejects a scan that hasn't finished scoring

[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) 404s when the AI Scan doesn't exist
[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) creates a client_reports row carrying the scan's real score and executive summary
[pass] admin.promoteAiScanToClientReport (AI Scan -> Reports bridge) does not fabricate a summary when reportPayload is corrupted - still creates the report from the score alone
[pass] admin.createProject / admin.updateProject creates a project and audits the action
[pass] admin.createMilestone / admin.updateMilestone (tenant isolation) refuses to attach a milestone to a project belonging to a different organization
[pass] admin.createMilestone / admin.updateMilestone (tenant isolation) creates a milestone once the project's org ownership is verified
[pass] admin.createMilestone / admin.updateMilestone (tenant isolation) refuses to update a milestone under a project outside the given organization

server/admin.retriggerAiScan.test.ts (8 passing)

[pass] admin.retriggerAiScan rejects non-admin callers
[pass] admin.retriggerAiScan 404s for an unknown scan
[pass] admin.retriggerAiScan rejects a scan that is already ready (PRECONDITION_FAILED)
[pass] admin.retriggerAiScan rejects a scan that is already actively scoring (PRECONDITION_FAILED)
[pass] admin.retriggerAiScan rejects a scan with no valid stored answers instead of fabricating some
[pass] admin.retriggerAiScan rejects a scan whose responses parse but contain no answers
[pass] admin.retriggerAiScan retries a failed scan with its real stored answers and audits it
[pass] admin.retriggerAiScan retries a pending scan too (not just failed)

server/admin.srsOps.test.ts (38 passing)

[pass] authority boundaries keeps a client out of every adminOps procedure
[pass] authority boundaries reserves AI governance for the super admin
[pass] authority boundaries lets a technical operator work incidents but not sales data
[pass] denied access is recorded (SRS 8.16) writes one blocked audit row when a signed in user is refused
[pass] denied access is recorded (SRS 8.16) does not write a row when an allowed call succeeds
[pass] opportunities needs a lead or an organization
[pass] opportunities surfaces a refused transition as PRECONDITION_FAILED and audits nothing
[pass] opportunities notifies admins when a deal is won and a handover project exists
[pass] activities and quotations requires a due date on a follow up
[pass] activities and quotations requires something to attach an activity to
[pass] activities and quotations turns a quotation arithmetic error into BAD_REQUEST
[pass] activities and quotations refuses fractional cents at the boundary
[pass] activities and quotations will not reopen a cancelled subscription
[pass] time review demands a reason to reject
[pass] time review tells the developer about the decision
[pass] time review refuses an entry that was already reviewed
[pass] AI governance audits a blocked agent action as a failure
[pass] AI governance will not decide the same execution twice
[pass] incidents, archive and reports does not resolve an incident without a resolution
[pass] incidents, archive and reports alerts admins to a critical incident
[pass] incidents, archive and reports refuses to archive a project that is not eligible
[pass] incidents, archive and reports will not schedule a report in the past
[pass] audit export, search and health exports CSV, defuses a formula in an attacker typed identifier, and audits the export
[pass] audit export, search and health keeps audit search and export away from a technical operator
[pass] audit export, search and health lets a technical operator read platform health but not search documents
[pass] audit export, search and health refuses a one character document search
[pass] audit export, search and health scopes a client document search to the caller's organization, never the query text
[pass] AI Scan expert review keeps a technical operator and a client out of the review actions
[pass] AI Scan expert review will not let the API approve straight from a state the rules forbid
[pass] AI Scan expert review records the approver and does not email the customer on approval
[pass] AI Scan expert review emails the customer a link when a report is published
[pass] AI Scan expert review still publishes when the notification email fails
[pass] AI Scan expert review only regenerates a report that was sent back
[pass] Discovery Call outcomes and task comments demands a follow up date for a follow up outcome before touching the database
[pass] Discovery Call outcomes and task comments records an outcome with the follow up and audits it
[pass] Discovery Call outcomes and task comments refuses an outcome on a cancelled call
[pass] Discovery Call outcomes and task comments will not comment on a task nobody holds
[pass] Discovery Call outcomes and task comments keeps a technical operator out of call outcomes

server/admin.summary.test.ts (6 passing)

[pass] admin.summary RBAC rejects unauthenticated callers
[pass] admin.summary RBAC rejects non-admin authenticated callers
[pass] admin.summary RBAC allows admin callers and writes an audit row
[pass] admin.summary when DB is offline reports honest zeros/empty arrays, never fabricated positive numbers
[pass] admin.liveFeed requires admin and emits a separate audit row
[pass] admin.recentLoginAudit returns [] safely when the database is offline and audits the read

server/admin.superAdmin.test.ts (17 passing)

[pass] admin.listOrganizations allows plain admin (read-only)
[pass] admin.listOrganizations rejects non-admin callers
[pass] admin.createOrganization rejects plain admin - this is a super_admin-exclusive capability (RM-57)
[pass] admin.createOrganization rejects unauthenticated callers
[pass] admin.createOrganization allows super_admin, checks slug uniqueness first, and audits
[pass] admin.createOrganization rejects a duplicate slug with CONFLICT before ever calling createOrganization
[pass] admin.createOrganization rejects an invalid slug shape via zod before touching the database
[pass] admin.updateOrganization rejects plain admin
[pass] admin.updateOrganization allows super_admin and audits
[pass] admin.updateOrganization surfaces NOT_FOUND when the organization doesn't exist
[pass] admin.setUserRole rejects plain admin - role/permission management is super_admin-exclusive (RM-57)
[pass] admin.setUserRole refuses to let a super_admin change their own role
[pass] admin.setUserRole allows super_admin to change another user's role and audits the before/after
[pass] admin.setUserRole surfaces NOT_FOUND for an unknown user without calling setUserRole
[pass] admin.assignUserOrganization rejects plain admin
[pass] admin.assignUserOrganization allows super_admin to link a user to an organization and audits it

[pass] admin.assignUserOrganization allows clearing a user's organization (organizationId: null)

server/admin.webhooks.test.ts (8 passing)

[pass] admin.webhookRegistrations (read) rejects plain admin - registrations carry a signing secret
[pass] admin.webhookRegistrations (read) allows super_admin
[pass] admin.webhookDeliveries (read) allows plain admin
[pass] admin.webhookDeliveries (read) rejects non-admin callers
[pass] admin.createWebhookRegistration rejects plain admin
[pass] admin.createWebhookRegistration rejects a non-https URL
[pass] admin.createWebhookRegistration allows super_admin, persists, and audits
[pass] admin.setWebhookRegistrationEnabled surfaces NOT_FOUND for an unknown id

server/admin.workflows.test.ts (11 passing)

[pass] admin.workflowDefinitions / admin.workflowRuns (read) allows plain admin
[pass] admin.workflowDefinitions / admin.workflowRuns (read) rejects non-admin callers
[pass] admin.createWorkflowDefinition rejects plain admin - platform configuration is super_admin-exclusive (RM-57)
[pass] admin.createWorkflowDefinition allows super_admin and audits
[pass] admin.createWorkflowDefinition requires a cadence and first run for a scheduled workflow
[pass] admin.createWorkflowDefinition stores the cadence and first run for a scheduled workflow
[pass] admin.createWorkflowDefinition rejects an invalid triggerType via zod
[pass] admin.setWorkflowDefinitionEnabled rejects plain admin
[pass] admin.setWorkflowDefinitionEnabled allows super_admin and surfaces NOT_FOUND for an unknown id
[pass] admin.reviewDocument triggers the workflow engine invokes runWorkflowsForTrigger with document_approved on approval
[pass] admin.reviewDocument triggers the workflow engine invokes runWorkflowsForTrigger with document_rejected on rejection

server/aiGovernance.test.ts (6 passing)

[pass] guardAiScanRun registers the defaults, records the attempt and returns the active managed prompt
[pass] guardAiScanRun blocks the run when the agent is disabled or lacks the permission
[pass] guardAiScanRun runs on the default prompt when there is no managed prompt yet
[pass] guardAiScanRun does not take scans down when the registry itself fails
[pass] managed prompt in the scoring call uses the managed text and always appends the language instruction
[pass] managed prompt in the scoring call falls back to the built in text for an empty managed prompt

server/aiScanModel.test.ts (4 passing)

[pass] AI Scan model contract declares exactly the five marketed dimensions
[pass] AI Scan model contract grade bands cover 0..100 with no gaps and no overlap
[pass] AI Scan model contract gradeForScore maps boundaries correctly
[pass] AI Scan model contract tier profile escalates monotonically (free < growth < elite)

server/aiScanReportPdf.test.ts (3 passing)

[pass] renderAiScanReportPdf produces a non-empty PDF buffer with a valid header for each tier
[pass] renderAiScanReportPdf does not throw when optional sections are empty
[pass] renderAiScanReportPdf handles a missing company gracefully

server/aiScans.test.ts (24 passing)

[pass] aiScansRouter.submitLead persists a free-tier lead with source=ai-scan and interest=ai-scan:free
[pass] aiScansRouter.submitLead preserves tier distinction for paid Growth tier
[pass] aiScansRouter.submitLead preserves tier distinction for paid Elite tier
[pass] aiScansRouter.submitLead rejects submissions where the AI Disclaimer was not accepted
[pass] aiScansRouter.submitLead rejects invalid email
[pass] aiScansRouter.submitLead rejects non-empty honeypot field at the schema layer
[pass] aiScansRouter.submitLead does not break when notifyOwner throws
[pass] aiScansRouter.submitLead rate-limits after 6 submissions from the same IP within 1 minute
[pass] aiScansRouter.submitLead propagates a meaningful error when the lead cannot be persisted
[pass] AI Scan questionnaire bank contract is consistent: tier counts match AI_SCAN_TIER_PROFILE
[pass] AI Scan questionnaire bank free tier exposes exactly the configured number of questions
[pass] AI Scan questionnaire bank growth tier is a strict superset of free tier
[pass] AI Scan questionnaire bank elite tier is a strict superset of growth tier
[pass] AI Scan questionnaire bank every question maps to a covered dimension at its tier
[pass] AI Scan questionnaire bank findMissingAnswers reports omissions and is empty when complete
[pass] AI Scan questionnaire bank computeRawDimensionScores averages within 0..100
[pass] aiScansRouter.submitQuestionnaire persists scan + lead, runs scoring engine inline for free tier, returns reportToken
[pass] aiScansRouter.submitQuestionnaire rejects payload missing required answers
[pass] aiScansRouter.submitQuestionnaire rejects unknown question ids to prevent payload pollution
[pass] aiScansRouter.submitQuestionnaire marks scan as failed and notifies owner when engine fails
[pass] aiScansRouter.submitQuestionnaire does not block the response on owner notification failure
[pass] aiScansRouter.submitQuestionnaire holds a scored report for expert review and shows it only once published (BR-016)
[pass] aiScansRouter.submitQuestionnaire getReport throws NOT_FOUND for unknown tokens
[pass] aiScansRouter.submitQuestionnaire getQuestionnaire returns canonical question set for the tier

server/aiScanScoring.test.ts (7 passing)

[pass] scoreAiScan returns a typed report and stamps tier + grade for free tier
[pass] scoreAiScan trims opportunities to the tier cap even if LLM returns more
[pass] scoreAiScan locks dimensions to the tier profile even if LLM returns extra dimensions
[pass] scoreAiScan falls back to deterministic raw scores when LLM omits a dimension
[pass] scoreAiScan returns ok=false (not throw) on LLM transport failure
[pass] scoreAiScan returns ok=false on unparseable LLM response
[pass] scoreAiScan propagates locale into the system prompt

server/apiHardening.test.ts (29 passing)

[pass] RM-86: helmet security headers never advertises the framework via X-Powered-By
[pass] RM-86: helmet security headers sets clickjacking, sniffing and referrer protections
[pass] RM-86: helmet security headers does NOT enforce CSP or HSTS in development
[pass] RM-86: helmet security headers enforces a restrictive CSP and HSTS in production
[pass] RM-86: helmet security headers allows the real font and Supabase asset hosts the client loads from
[pass] RM-86: helmet security headers omits the analytics origin from the CSP when it is not configured

[pass] RM-86: helmet security headers includes the analytics origin when one is configured
[pass] RM-87: explicit CORS policy rejects the '*' wildcard - it cannot be combined with credentials
[pass] RM-87: explicit CORS policy drops malformed origins instead of trusting them
[pass] RM-87: explicit CORS policy normalises to the origin, discarding any path
[pass] RM-87: explicit CORS policy allows requests with no Origin header (same-origin / non-browser)
[pass] RM-87: explicit CORS policy denies every cross-origin request when no allowlist is configured
[pass] RM-87: explicit CORS policy allows only exact allowlist matches
[pass] RM-87: explicit CORS policy omits Access-Control-Allow-Origin for a disallowed origin
[pass] RM-87: explicit CORS policy echoes the origin and allows credentials for an allowed origin
[pass] RM-88: rate limiter allows up to the limit and blocks beyond it
[pass] RM-88: rate limiter counts each caller independently
[pass] RM-88: rate limiter never limits when the caller IP is unknown
[pass] RM-88: rate limiter expires hits once they fall outside the window
[pass] RM-88: rate limiter keeps two limiters isolated even when they share a store
[pass] RM-88: rate limiter defaults to the in-memory store and warns on an unknown value
[pass] RM-89: deliberate session TTL defaults to 12 hours, not the previous one year
[pass] RM-89: deliberate session TTL honours a valid override
[pass] RM-89: deliberate session TTL falls back to the default for a non-numeric or zero value
[pass] RM-89: deliberate session TTL clamps absurd values rather than accepting them
[pass] malformed request URLs answers 400 instead of throwing on an un-decodable path
[pass] malformed request URLs answers 400 for a stray percent sign from any client
[pass] malformed request URLs leaves well-formed paths alone
[pass] malformed request URLs leaves correctly percent-encoded paths alone

server/auditCoverage.test.ts (14 passing)

[pass] audit coverage admin: every mutation audits itself or is on the central list
[pass] audit coverage adminOps: every mutation audits itself or is on the central list
[pass] audit coverage bookingAdmin: every mutation audits itself or is on the central list
[pass] audit coverage clientPortal: every mutation audits itself or is on the central list
[pass] audit coverage developer: every mutation audits itself or is on the central list
[pass] audit coverage ops: every mutation audits itself or is on the central list
[pass] audit coverage privacy: every mutation audits itself or is on the central list
[pass] audit coverage profile: every mutation audits itself or is on the central list
[pass] audit coverage mfa: every mutation audits itself or is on the central list
[pass] audit coverage finds mutations to check, so the scan is not passing on an empty parse
[pass] shouldAuditMutation covers the booking admin router and the listed client actions
[pass] shouldAuditMutation does not audit unrelated paths
[pass] mutation audit middleware records a successful listed mutation with the caller and the path
[pass] mutation audit middleware records nothing when the mutation fails

server/auth.logout.test.ts (1 passing)

[pass] auth.logout clears the session cookie and reports success

server/auth.recordAttempt.test.ts (3 passing)

[pass] auth.recordAttempt accepts 'supabase' as a valid provider (RM-50)
[pass] auth.recordAttempt still accepts every pre-existing provider value
[pass] auth.recordAttempt rejects an unknown provider value

server/bookingAdmin.test.ts (12 passing)

[pass] booking action tokens round-trips and verifies correctly
[pass] booking action tokens rejects a tampered signature
[pass] booking action tokens rejects when the requested action does not match
[pass] bookingAdmin router authz rejects anonymous callers on listAvailabilityRules
[pass] bookingAdmin router authz rejects authenticated non-admin callers
[pass] bookingAdmin router authz allows admin callers
[pass] bookingAdmin input validation rejects rules where end <= start
[pass] bookingAdmin input validation accepts a valid rule and lists it back
[pass] bookingAdmin input validation rejects calendar block with end < start
[pass] bookings.hold rejects a second hold on the same slot with CONFLICT
[pass] bookings.cancelByToken rejects bad signatures
[pass] bookings.cancelByToken accepts a properly signed token

server/bookingReminders.test.ts (7 passing)

[pass] dispatchDueBookingReminders sends a due 24h reminder and marks it sent
[pass] dispatchDueBookingReminders never re-sends a 'confirmation' reminder - only marks it as handled
[pass] dispatchDueBookingReminders suppresses a reminder for a cancelled booking without emailing
[pass] dispatchDueBookingReminders includes the meeting URL only when callType is video
[pass] dispatchDueBookingReminders omits the meeting URL when callType has reverted to phone, even if one is stored
[pass] dispatchDueBookingReminders records a failed send without throwing
[pass] dispatchDueBookingReminders skips a reminder whose booking no longer exists

server/bookings.test.ts (12 passing)

[pass] bookings.create creates a confirmed booking and returns a public reference
[pass] bookings.create rejects honeypot submissions at input validation
[pass] bookings.create rejects slot times in the deep past
[pass] bookings.create rejects malformed emails
[pass] bookings.create requires a telephone number
[pass] bookings.create rejects a placeholder in the telephone field
[pass] bookings.create accepts international telephone formats
[pass] bookings.getByRef returns null for an unknown reference
[pass] bookings.getByRef returns sanitized booking data when reference exists
[pass] bookings.listRecent rejects unauthenticated callers
[pass] bookings.listRecent rejects authenticated non-admin callers
[pass] bookings.listRecent returns recent bookings for admin callers

server/clientNotifications.test.ts (3 passing)

[pass] clientPortal.notifications shows everything when the member has set no preferences
[pass] clientPortal.notifications hides a category this member opted out of, for in app only
[pass] clientPortal.notifications never hides a security notification, even if a preference row says so

server/clientPortal.test.ts (37 passing)

[pass] clientPortal router rejects unauthenticated calls
[pass] clientPortal router rejects users without a client role
[pass] clientPortal router rejects clients without a linked organization
[pass] clientPortal router returns the tenant-scoped dashboard for the logged-in client
[pass] clientPortal router returns the organization record for the logged-in client
[pass] clientPortal router creates a support ticket with a public reference and notifies owner
[pass] clientPortal router sends a client message and writes a notification
[pass] clientPortal router requestReportSignedUrl returns a short-lived URL and audits download
[pass] clientPortal router requestReportSignedUrl rejects when report is not in caller's org
[pass] clientPortal router requestReportSignedUrl rejects with PRECONDITION when pdfKey is missing
[pass] clientPortal router recommendationAction proposal: flips status to in_progress, audits, notifies owner
[pass] clientPortal router recommendationAction discuss: audits + notifies feed but does NOT flip status
[pass] clientPortal router recommendationAction dismiss: flips to dismissed, audits, no owner notify
[pass] clientPortal router recommendationAction rejects when rec is in another tenant
[pass] clientPortal router cancelStrategyCall: cancels a future booking, audits, notifies owner
[pass] clientPortal router cancelStrategyCall: blocks self-cancel inside the 60-min window
[pass] clientPortal router cancelStrategyCall: rejects when booking is in another tenant
[pass] clientPortal router requestInvoiceCheckout: open invoice triggers manual flow + audit + notify
[pass] clientPortal router requestInvoiceCheckout: rejects already-paid invoices
[pass] clientPortal router requestInvoiceCheckout: rejects when invoice belongs to another tenant
[pass] clientPortal router uploadDocument: rejects blocked extensions
[pass] clientPortal router uploadDocument: rejects empty payload
[pass] clientPortal router uploadDocument: persists, audits, notifies
[pass] clientPortal router uploadDocument: passes supersedesDocumentId through to insertClientDocument (Milestone 2 §2.6 versioning)
[pass] clientPortal router uploadDocument: surfaces a version-linking failure as BAD_REQUEST
[pass] clientPortal router markNotificationRead: marks a notification read and surfaces NOT_FOUND for an unknown one (Milestone 2 §2.7)
[pass] clientPortal router archiveNotification: archives a notification (Milestone 2 §2.7)
[pass] clientPortal router requestDocumentDeletion: only the uploader can delete their file
[pass] clientPortal router requestDocumentDeletion: removes own file + audits
[pass] clientPortal router requestDocumentDeletion: DB row is removed even if the storage-object delete fails (best-effort, not a partial-failure error)
[pass] clientPortal router markMessagesRead returns affected-rows count and stays tenant-scoped
[pass] clientPortal router updateDisplayName: persists trimmed name and audits the change
[pass] clientPortal router updateDisplayName: rejects names shorter than 2 chars
[pass] clientPortal router setMfaMethod: enables email MFA and audits the change
[pass] clientPortal router setMfaMethod: rejects unknown methods at the schema layer
[pass] clientPortal router revokeSession: clears the IO SKY cookie and audits the revocation
[pass] clientPortal router surfaces the security center payload with recentLogins array

server/concurrency.test.ts (9 passing)

[pass] RM-113: booking-slot concurrency gives the slot to exactly one of ten simultaneous holders
[pass] RM-113: booking-slot concurrency keeps different slots independent under the same burst
[pass] RM-113: booking-slot concurrency lets an expired hold be taken over rather than blocking the slot forever
[pass] RM-113: booking-slot concurrency does not let two callers take over the same expired hold
[pass] RM-110: latency baseline for hot queries records a baseline for the authentication lookup
[pass] RM-110: latency baseline for hot queries records a baseline for the login lookup
[pass] RM-110: latency baseline for hot queries records a baseline for tenant-scoped listing
[pass] RM-110: latency baseline for hot queries hangs, rather than queues, when a burst exceeds the pool size
[pass] RM-110: latency baseline for hot queries handles a burst of concurrent authentication lookups without collapsing

server/contact-engineering-auth.test.ts (10 passing)

[pass] contact.submit creates a submission, CRM lead, and returns a publicRef
[pass] contact.submit rejects malformed emails
[pass] contact.submit rejects honeypot submissions at the validator boundary
[pass] contact.submit guards listRecent behind admin auth
[pass] engineering.submit creates an application + CRM lead when all acknowledgements are present
[pass] engineering.submit rejects applications missing any acknowledgement
[pass] engineering.submit guards listRecent and setStatus behind admin auth
[pass] auth.recordAttempt appends a login audit row with the requested provider/outcome
[pass] auth.recordAttempt rejects unknown providers and outcomes
[pass] auth.recordAttempt guards audit.listLeads + audit.listLogins behind admin auth

server/cookieSecurity.test.ts (20 passing)

[pass] RM-92: direct connections uses Lax + insecure over plain HTTP
[pass] RM-92: direct connections uses None + Secure over direct HTTPS
[pass] RM-92: behind a TLS-terminating proxy honours X-Forwarded-Proto: https
[pass] RM-92: behind a TLS-terminating proxy handles a comma-separated forwarded chain
[pass] RM-92: behind a TLS-terminating proxy handles the header arriving as an array
[pass] RM-92: behind a TLS-terminating proxy tolerates whitespace and casing in the chain
[pass] RM-92: behind a TLS-terminating proxy stays insecure when the proxy reports plain http
[pass] RM-92: invariants that must hold on every path 'plain http' is always HttpOnly
[pass] RM-92: invariants that must hold on every path 'direct https' is always HttpOnly
[pass] RM-92: invariants that must hold on every path 'proxied https' is always HttpOnly
[pass] RM-92: invariants that must hold on every path 'proxied http' is always HttpOnly
[pass] RM-92: invariants that must hold on every path 'plain http' is scoped to the whole site
[pass] RM-92: invariants that must hold on every path 'direct https' is scoped to the whole site
[pass] RM-92: invariants that must hold on every path 'proxied https' is scoped to the whole site
[pass] RM-92: invariants that must hold on every path 'proxied http' is scoped to the whole site
[pass] RM-92: invariants that must hold on every path 'plain http' never emits SameSite=None without Secure

[pass] RM-92: invariants that must hold on every path 'direct https' never emits SameSite=None without Secure
[pass] RM-92: invariants that must hold on every path 'proxied https' never emits SameSite=None without Secure
[pass] RM-92: invariants that must hold on every path 'proxied http' never emits SameSite=None without Secure
[pass] RM-92: trust-proxy configuration is opt-in rather than always on

server/dbConstraints.test.ts (9 passing)

[pass] RM-108: database constraint enforcement foreign keys declares a substantial number of foreign keys, not a handful
[pass] RM-108: database constraint enforcement foreign keys every foreign key declares explicit ON DELETE behaviour
[pass] RM-108: database constraint enforcement foreign keys rejects an orphaned row at the database layer
[pass] RM-108: database constraint enforcement updatedAt triggers installs the updatedAt trigger on tables that carry the column
[pass] RM-108: database constraint enforcement updatedAt triggers actually bumps updatedAt on write
[pass] RM-108: database constraint enforcement row-level security enables RLS on EVERY public table, not only the tenant-scoped ones
[pass] RM-108: database constraint enforcement row-level security enables RLS on every tenant-scoped table
[pass] RM-108: database constraint enforcement row-level security does not leave an RLS-enabled table with zero policies
[pass] RM-108: database constraint enforcement indexes indexes every foreign key column

server/designLanguage.test.ts (30 passing)

[pass] Pakket 2 - design-language tokens declares .io-surface
[pass] Pakket 2 - design-language tokens declares .io-surface-glass
[pass] Pakket 2 - design-language tokens declares .io-card
[pass] Pakket 2 - design-language tokens declares .io-section
[pass] Pakket 2 - design-language tokens declares .io-empty-state
[pass] Pakket 2 - design-language tokens declares .io-empty-icon
[pass] Pakket 2 - design-language tokens declares .io-icon-chip
[pass] Pakket 2 - design-language tokens declares .io-icon-chip-sm
[pass] Pakket 2 - design-language tokens declares .io-divider
[pass] Pakket 2 - design-language tokens declares .io-divider-vertical
[pass] Pakket 2 - design-language tokens declares .io-pill
[pass] Pakket 2 - design-language tokens declares .io-pill-success
[pass] Pakket 2 - design-language tokens declares .io-pill-danger
[pass] Pakket 2 - design-language tokens declares .io-pill-warn
[pass] Pakket 2 - design-language tokens declares .io-pill-orange
[pass] Pakket 2 - design-language tokens declares .reveal
[pass] Pakket 2 - design-language tokens declares .pulse-orange
[pass] Pakket 2 - design-language tokens declares .glow-orange
[pass] Pakket 2 - design-language tokens declares .lift-on-hover
[pass] Pakket 2 - design-language tokens declares .skeleton
[pass] Pakket 2 - design-language tokens declares .ticker-track
[pass] Pakket 2 - design-language tokens declares .font-display
[pass] Pakket 2 - design-language tokens declares .font-mono
[pass] Pakket 2 - design-language tokens declares .eyebrow
[pass] Pakket 2 - design-language tokens declares .btn-primary
[pass] Pakket 2 - design-language tokens declares .btn-secondary
[pass] Pakket 2 - design-language tokens brand orange variable is the exact #F58A1F specified by the approved design system
[pass] Pakket 2 - design-language tokens brand background is the exact #0D2D2E Deep Teal specified by the approved design system
[pass] Pakket 2 - design-language tokens respects prefers-reduced-motion globally
[pass] Pakket 2 - design-language tokens supports RTL reveal on Arabic locale

server/developer.test.ts (33 passing)

[pass] developer router - gating rejects unauthenticated calls to gateStatus
[pass] developer router - gating returns ok=false/reason=denied for non-developer roles
[pass] developer router - gating blocks dashboard when MFA gate fails
[pass] developer router - gating blocks dashboard when agreements gate fails
[pass] developer router - gating blocks dashboard when access scope is expired
[pass] developer router - gating blocks dashboard when no active assignments exist
[pass] developer router - gating returns the workspace dashboard when every gate passes
[pass] developer router - file signed URL denies download when file does not belong to an assigned project
[pass] developer router - file signed URL returns a signed URL and records an audit row when access is allowed
[pass] developer router - task + submission rejects setTaskStatus when the task is not assigned to the developer
[pass] developer router - task + submission updates status and notifies admin when caller owns the task
[pass] developer router - task + submission blocks submission for an unassigned project
[pass] developer router - task + submission creates a submission, audits, and notifies admin
[pass] developer router - task + submission requires repository+sha when submitting a commit
[pass] developer router - messages + agreements appends a message to the admin thread and notifies admin
[pass] developer router - messages + agreements marks admin messages as read
[pass] developer router - messages + agreements lets a developer sign an agreement even before all gates pass
[pass] developer router - Notification Center (Milestone 2 §2.7) marks a notification read and surfaces NOT_FOUND for an unknown one
[pass] developer router - Notification Center (Milestone 2 §2.7) archives a notification
[pass] developer router - support tickets rejects subjects that are too short
[pass] developer router - support tickets opens a ticket, audits, and notifies the engineering desk
[pass] developer router - access extension rejects extension reasons that are too short
[pass] developer router - access extension creates an access request, audits, and notifies admin
[pass] developer router - Step 2: editable profile + security updateProfile writes patch + audit row and skips notify when availability stays the same
[pass] developer router - Step 2: editable profile + security updateProfile fires notifyOwner when availability changes
[pass] developer router - Step 2: editable profile + security updateProfile is rejected for client, user, and even admin (self-service only)
[pass] developer router - Step 2: editable profile + security setMfaMethodLite is rejected for client, user, and even admin (self-service only)
[pass] developer router - Step 2: editable profile + security getProfileForEdit is rejected for client, user, and even admin (self-service only)
[pass] developer router - Step 2: editable profile + security setMfaMethodLite rejects 'none' when mfaRequired=1 and records a security event
[pass] developer router - Step 2: editable profile + security setMfaMethodLite allows switching to 'email' and writes an audit row
[pass] developer router - Step 2: editable profile + security setMfaMethodLite allows 'none' when mfaRequired=0 and notifies the admin
[pass] developer router - Step 2: editable profile + security listAuditEvents returns the calling developer's audit rows only
[pass] developer router - Step 2: editable profile + security listAuditEvents is rejected for client, user, and even admin (self-service only)

server/email-i18n.test.ts (9 passing)

[pass] email-i18n locale normalisation maps common locale-ish inputs to supported codes
[pass] email-i18n locale normalisation falls back to EN for unknown or empty input
[pass] email-i18n locale normalisation flags only Arabic as RTL
[pass] email-i18n string completeness provides non-empty strings for every locale and email type
[pass] email-i18n string completeness keeps placeholder tokens intact in templated strings
[pass] email-i18n string completeness fill() substitutes tokens and leaves unknown tokens visible
[pass] localised email rendering (console transport) renders Dutch booking subject and RTL Arabic markup
[pass] localised email rendering (console transport) renders contact + devapp confirmations for a non-EN locale
[pass] localised email rendering (console transport) defaults to EN when locale is omitted

server/emailBranding.test.ts (3 passing)

[pass] transactional email branding defines the exact brand ground and accent
[pass] transactional email branding carries no off-brand approximations of the teal or the orange
[pass] transactional email branding routes every template colour through the shared palette

server/emailDeliveryLogging.test.ts (3 passing)

[pass] email delivery logging (Milestone 2 §2.3) logs a 'sent' row for a booking confirmation delivered via the console fallback
[pass] email delivery logging (Milestone 2 §2.3) logs a 'failed' row with the transport error when Resend rejects the send
[pass] email delivery logging (Milestone 2 §2.3) logs contact-confirmation and devapp-ack sends with their own messageType and relatedRef

server/healthRoute.test.ts (14 passing)

[pass] RM-76: liveness (/health) returns 200 with a status payload
[pass] RM-76: liveness (/health) stays 200 even when the database is completely unavailable
[pass] RM-76: liveness (/health) never touches the database at all
[pass] RM-76: liveness (/health) forbids caching so a proxy cannot mask a dead instance
[pass] RM-76: readiness (/health/ready) returns 200 when the database answers
[pass] RM-76: readiness (/health/ready) returns 503 when the database is unreachable
[pass] RM-76: readiness (/health/ready) returns 503 when no database is configured at all
[pass] RM-76: readiness (/health/ready) reports the probe latency
[pass] RM-76: readiness (/health/ready) never leaks a connection string in the error message
[pass] RM-76: version (/health/version) reports the build commit so a deploy or rollback can be confirmed
[pass] RM-76: version (/health/version) says 'unknown' rather than inventing a commit when unset
[pass] RM-76: credential redaction redacts a password embedded in a connection URL
[pass] RM-76: credential redaction redacts a key/value style password
[pass] RM-76: credential redaction leaves an innocuous message untouched

server/i18n.completeness.test.ts (10 passing)

[pass] i18n completeness English has at least 1100 keys
[pass] i18n completeness nl.ts covers every English key
[pass] i18n completeness de.ts covers every English key
[pass] i18n completeness fr.ts covers every English key
[pass] i18n completeness es.ts covers every English key
[pass] i18n completeness it.ts covers every English key
[pass] i18n completeness pt.ts covers every English key
[pass] i18n completeness ar.ts covers every English key
[pass] i18n completeness ja.ts covers every English key
[pass] i18n completeness zh.ts covers every English key

server/i18n.homepage.test.ts (10 passing)

[pass] i18n - homepage key completeness loads a non-empty English dictionary
[pass] i18n - homepage key completeness every t("...") key in Hero.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in GrowthDependency.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in LookBeyond.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in OurStartingPoint.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in DesigningRelationships.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in WhatThatCanBecome.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in WhyIOSKY.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in BuiltForChange.tsx is declared in en.ts
[pass] i18n - homepage key completeness every t("...") key in HomeFinalCta.tsx is declared in en.ts

server/i18n.locale.test.ts (15 passing)

[pass] Pakket 3 - i18n registry registers exactly the 10 active languages
[pass] Pakket 3 - i18n registry Arabic is the only RTL locale
[pass] Pakket 3 - i18n registry each language exposes a BCP47 tag for Intl APIs
[pass] Pakket 3 - translate() returns the localized value when the key exists in the locale
[pass] Pakket 3 - translate() falls back to English when the key is missing in the target locale
[pass] Pakket 3 - translate() returns the raw key as a last-resort fallback
[pass] Pakket 3 - translate() supports {name} placeholder substitution
[pass] Pakket 3 - Chinese locale ZH dictionary contains at least the core navigation keys
[pass] Pakket 3 - Chinese locale every ZH value is non-Latin (catches accidental EN copy-paste)
[pass] Pakket 3 - locale-aware formatters formatNumber respects locale separators
[pass] Pakket 3 - locale-aware formatters formatCurrency emits a recognisable currency symbol
[pass] Pakket 3 - locale-aware formatters formatDate produces locale-specific output
[pass] Pakket 3 - locale-aware formatters formatRelative returns a sensible string
[pass] Pakket 3 - locale-aware formatters formatters never throw on unknown locale (defensive fallback)
[pass] Pakket 3 - dictionary parity EN remains the single source of truth

server/i18n.usedKeys.test.ts (4 passing)

[pass] keys used without a default exist in the dictionary the dictionary has the keys the scan below relies on
[pass] keys used without a default exist in the dictionary detects a single argument call and ignores one with a default
[pass] keys used without a default exist in the dictionary scans the client source
[pass] keys used without a default exist in the dictionary no t("key") call shows a raw key because its entry is missing

server/inputValidationCoverage.test.ts (5 passing)

[pass] RM-91: dangerouslySetInnerHTML surface has no dangerouslySetInnerHTML anywhere in client or server source
[pass] RM-93: zod validation coverage across tRPC procedures finds the expected procedure surface (guards the parser itself)
[pass] RM-93: zod validation coverage across tRPC procedures every procedure that reads `input` declares a validator for it
[pass] RM-93: zod validation coverage across tRPC procedures every declared validator is a zod schema
[pass] RM-93: zod validation coverage across tRPC procedures procedures without a validator genuinely take no input

server/integrations.test.ts (11 passing)

[pass] integration status reports configured only when every required variable is set
[pass] integration status accepts either of two alternative variables
[pass] integration status never includes a secret value in the status
[pass] integration status does not call a provider that is not configured
[pass] integration status reports the mode when the Stripe key is accepted
[pass] integration status reports a rejected key as a failure
[pass] lead evaluation (SRS 14.16) parses a valid answer and rejects malformed ones
[pass] lead evaluation (SRS 14.16) routes through the agent gate, uses the simple model class and records the result
[pass] lead evaluation (SRS 14.16) does not call the model when the agent is blocked
[pass] lead evaluation (SRS 14.16) records nothing when the model answer is unusable
[pass] lead evaluation (SRS 14.16) reports a provider failure instead of throwing

server/llm.test.ts (10 passing)

[pass] invokeLLM (Milestone 2 §2.2) throws a clear config error when no endpoint is configured - no silent fallback to a hardcoded Manus/Forge URL
[pass] invokeLLM (Milestone 2 §2.2) throws a clear config error when no credential is configured
[pass] invokeLLM (Milestone 2 §2.2) sends the configured model/url/key and defaults max_tokens
[pass] invokeLLM (Milestone 2 §2.2) respects an explicit maxTokens override instead of always sending the hardcoded default
[pass] invokeLLM (Milestone 2 §2.2) surfaces a clear rate-limit error on HTTP 429
[pass] invokeLLM (Milestone 2 §2.2) surfaces a clear error for other non-OK responses
[pass] invokeLLM (Milestone 2 §2.2) wraps a network failure in a clear error rather than letting a raw fetch rejection propagate
[pass] invokeLLM (Milestone 2 §2.2) activates from OPENAI_API_KEY alone, defaulting to OpenAI's endpoint
[pass] invokeLLM (Milestone 2 §2.2) lets an explicit LLM_API_URL win over the OpenAI default
[pass] invokeLLM (Milestone 2 §2.2) reports configuration status without performing a call

server/localAuth.errors.test.ts (17 passing)

[pass] POST /api/auth/local/login - missing fields returns 400 with stable code 'missing_fields' when email is empty
[pass] POST /api/auth/local/login - missing fields returns 400 with stable code 'missing_fields' when password is empty
[pass] POST /api/auth/local/login - missing fields returns 400 when body is empty object
[pass] POST /api/auth/local/login - missing fields missing-fields path does NOT touch the database
[pass] POST /api/auth/local/login - unknown email returns 401 with the SAME generic code as wrong-password
[pass] POST /api/auth/local/login - unknown email still runs a bcrypt compare to keep timing constant (anti-enumeration)
[pass] POST /api/auth/local/login - unknown email audits the failed attempt with reason 'invalid_credentials'
[pass] POST /api/auth/local/login - wrong password returns 401 with code 'invalid_credentials' for a real user
[pass] POST /api/auth/local/login - wrong password does NOT mint a session cookie on wrong password
[pass] POST /api/auth/local/login - wrong password audits the failed attempt linked to the real user id
[pass] POST /api/auth/local/login - passwordless account treats user.passwordHash=null exactly like wrong-password (401, no enumeration)
[pass] POST /api/auth/local/login - success path returns 200 with role + next, mints io_sky_session cookie, audits success
[pass] POST /api/auth/local/login - success path admin role redirects to /admin/bookings
[pass] POST /api/auth/local/login - success path developer role redirects to /developer-workspace
[pass] POST /api/auth/local/login - internal error returns 500 with code 'server_error' when the DB lookup throws
[pass] POST /api/auth/local/login: brute force throttle answers 429 after repeated attempts on one account, and records it as blocked
[pass] POST /api/auth/local/login: brute force throttle does not check the password once an account is throttled

server/localAuth.mfa.test.ts (4 passing)

[pass] local sign in with a second factor enrolled issues no session and sends the browser to the challenge
[pass] local sign in with a second factor enrolled records an mfa_required audit row, not a successful sign in
[pass] local sign in with a second factor enrolled refuses the login when the factor lookup fails, rather than assuming there is none
[pass] local sign in without a second factor still signs in with the session cookie

server/mfa.test.ts (14 passing)

[pass] mfa.enrollTotpBegin creates an un-verified factor and returns an otpauth URI
[pass] mfa.enrollTotpBegin replaces an abandoned un-verified factor instead of stacking a new one
[pass] mfa.enrollTotpBegin never discards a verified factor when starting a new enrolment
[pass] mfa.enrollTotpVerify marks the factor verified and returns 10 recovery codes
[pass] mfa.enrollTotpVerify rejects a wrong code, bumps failedAttempts, and audits the failure
[pass] mfa.enrollTotpVerify locks the factor after 5 consecutive failed attempts
[pass] mfa.listFactors / deleteFactor / setPrimaryFactor lists masked factors, refuses cross-user delete, and switches primary
[pass] mfa.regenerateRecoveryCodes replaces the recovery code batch and audits the action
[pass] mfa SMS enrolment dispatches an OTP and stores an unverified SMS factor
[pass] mfa SMS enrolment rejects an invalid phone number with BAD_REQUEST
[pass] mfa SMS enrolment verifies the SMS code, marks the factor verified, issues recovery codes
[pass] mfa SMS enrolment rejects wrong code, bumps failures, locks after MAX attempts
[pass] mfa.redeemRecoveryCode burns a single code and refuses to reuse it
[pass] mfa.redeemRecoveryCode rejects an unknown recovery code with UNAUTHORIZED + audit

server/mfaChallenge.test.ts (14 passing)

[pass] verifyChallengeCode accepts a fresh TOTP code generated from the same secret
[pass] verifyChallengeCode rejects a TOTP code that is plainly wrong
[pass] verifyChallengeCode accepts an SMS code while its expiry is in the future
[pass] verifyChallengeCode rejects an SMS code once it has expired
[pass] verifyChallengeCode rejects when the factor is not verified
[pass] POST /api/mfa/challenge returns 401 challenge_expired when no pending cookie is set
[pass] POST /api/mfa/challenge issues a real session cookie and clears the pending cookie on a valid TOTP code
[pass] POST /api/mfa/challenge returns 401 + bumps the failure counter on a wrong code
[pass] POST /api/mfa/challenge returns 429 when the factor is already locked
[pass] POST /api/mfa/challenge returns 404 when the factor belongs to a different user
[pass] POST /api/mfa/challenge redeems a valid recovery code one-shot and marks it used

[pass] POST /api/mfa/challenge rejects an unrelated recovery code
[pass] GET /api/mfa/challenge/status returns 401 inactive when there is no pending cookie
[pass] GET /api/mfa/challenge/status returns the list of verified factors for the pending user

server/mfaCrypto.test.ts (4 passing)

[pass] envelopeEncrypt / envelopeDecrypt round-trips arbitrary plaintext
[pass] envelopeEncrypt / envelopeDecrypt rejects tampered ciphertext
[pass] hashPhoneNumber / verifyPhoneHash verifies the same phone but rejects a different one
[pass] recovery codes generates 10 codes that match their hashes

server/mfaTotp.test.ts (4 passing)

[pass] TOTP helper generates a base32 secret that can be re-used to verify a token
[pass] TOTP helper rejects a malformed or wrong token
[pass] TOTP helper strips whitespace and dashes from the user-supplied token
[pass] TOTP helper renders an otpauth URI with the IO SKY issuer and the user's email

server/notification.test.ts (7 passing)

[pass] notifyOwner (Milestone 2 §2.2) rejects an empty title/content before touching config or the transport
[pass] notifyOwner (Milestone 2 §2.2) throws a clear config error when OWNER_NOTIFY_EMAIL is unset - no silent Manus-style fallback
[pass] notifyOwner (Milestone 2 §2.2) sends via the shared email transport and returns true on success
[pass] notifyOwner (Milestone 2 §2.2) returns false (does not throw) when the email transport reports failure
[pass] notifyOwner (Milestone 2 §2.2) escapes HTML in title/content so a hostile submission can't inject markup into the owner-alert email
[pass] notifyOwner (Milestone 2 §2.2) posts to Slack when a webhook is configured, without blocking or failing the email path
[pass] notifyOwner (Milestone 2 §2.2) does not call Slack when no webhook is configured

server/notificationCatalogue.test.ts (14 passing)

[pass] Notification Event Catalogue - structure carries all 84 events from the v1.0 catalogue
[pass] Notification Event Catalogue - structure matches the per-family counts in the source document
[pass] Notification Event Catalogue - structure gives every event a unique catalogue id and a unique machine name
[pass] Notification Event Catalogue - structure uses only the nine declared families
[pass] Notification Event Catalogue - structure gives every event the fields routing and delivery depend on
[pass] Notification Event Catalogue - structure resolves every conditional priority to a concrete floor
[pass] Notification Event Catalogue - lookups finds an event by catalogue id
[pass] Notification Event Catalogue - lookups finds an event by machine name
[pass] Notification Event Catalogue - lookups returns undefined rather than throwing for unknown keys
[pass] Notification Event Catalogue - lookups reports the events that require the recipient to act
[pass] Notification Event Catalogue - specification invariants keeps pre-publication AI Scan review events away from the Client
[pass] Notification Event Catalogue - specification invariants declares a published AI Scan event, which is the Client-facing boundary
[pass] Notification Event Catalogue - specification invariants never describes a notification preview containing secrets
[pass] Notification Event Catalogue - specification invariants scopes every deduplication key to whoever receives it

server/notificationDispatcher.test.ts (14 passing)

[pass] emitNotification rejects a name that is not in the catalogue without delivering anything
[pass] emitNotification delivers a repeated occurrence only once
[pass] emitNotification records the catalogue id, priority and a key scoped to event, audience, recipient and occurrence
[pass] emitNotification maps priority onto the in app scale
[pass] emitNotification does not fill the admin bell twice when the caller already did
[pass] emitNotification routes to a client organization with an email when the catalogue asks for one
[pass] emitNotification routes a developer event and sends a mandatory one by email
[pass] emitNotification files a security event under the security category so it cannot be opted out of
[pass] emitNotification never throws into the caller when delivery fails
[pass] emitNotification still delivers when the emission log cannot be written because there is no database
[pass] dispatch policy helpers reads only the leading keyword of the email policy
[pass] dispatch policy helpers maps priorities and families
[pass] dispatch policy helpers builds a bounded dedupe key
[pass] dispatch policy helpers resolves every catalogue event to a routable family and priority

server/notifications.test.ts (6 passing)

[pass] notifyClient writes the in-app row with channel: in_app by default and never calls the email bridge
[pass] notifyClient bridges to email for every org member when channel is in_app_and_email
[pass] notifyClient still writes the in-app row even if the email bridge throws
[pass] notifyDeveloper writes the in-app row and never calls the email bridge by default
[pass] notifyDeveloper bridges to email when channel is in_app_and_email and the developer has an email on file
[pass] notifyDeveloper skips the email bridge silently when the developer has no email on file

server/oauth.redirect.test.ts (5 passing)

[pass] OAuth callback - role-based redirect routes role=developer to /developer-workspace
[pass] OAuth callback - role-based redirect routes role=client (and client_member) to /client-portal
[pass] OAuth callback - role-based redirect routes role=admin to /admin/bookings
[pass] OAuth callback - role-based redirect falls back to the requested returnPath for role=user
[pass] OAuth callback - role-based redirect falls back to / when role is unknown and no returnPath given

server/ops.test.ts (22 passing)

[pass] ops RBAC gating (isOpsRole) allows technical_operator
[pass] ops RBAC gating (isOpsRole) allows admin (additive, not a replacement for adminProcedure elsewhere)
[pass] ops RBAC gating (isOpsRole) allows super_admin
[pass] ops RBAC gating (isOpsRole) rejects client
[pass] ops RBAC gating (isOpsRole) rejects developer
[pass] ops RBAC gating (isOpsRole) rejects unauthenticated callers
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.billing
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.documents
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.crm (leads)
[pass] technical_operator is walled off from customer/financial admin endpoints cannot reach admin.reports
[pass] ops.systemHealth returns an honest empty/unavailable shape when the database is offline
[pass] ops.emailDeliveryLog / ops.securityEvents returns the email delivery log
[pass] ops.emailDeliveryLog / ops.securityEvents returns recent security events

[pass] ops.acknowledgeSecurityEvent acknowledges an event and audits it
[pass] ops.acknowledgeSecurityEvent surfaces NOT_FOUND for an unknown event id
[pass] ops.acknowledgeSecurityEvent rejects non-ops callers
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) blocks technical_operator/admin/super_admin with no verified MFA factor from every ops.* endpoint
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) an unverified (pending) factor does not satisfy the gate - only verifiedAt-set factors count
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) does not affect client/developer roles at all - the gate only applies to admin/super_admin/technical_operator
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) ops.gateStatus reports mfa_required without throwing, so the console can render a calm interstitial
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) ops.gateStatus reports ok once a verified factor exists
[pass] Milestone 2 §2.5 - hard MFA gate (opsProcedure) ops.gateStatus reports denied (not mfa_required) for a non-ops role

server/paymentSync.test.ts (5 passing)

[pass] payment reminder staging is quiet until a week before the due date
[pass] payment reminder staging picks the closest applicable stage
[pass] payment reminder staging compares calendar days, not hours
[pass] branded email shell links the logo to the homepage and carries the same header and footer
[pass] branded email shell escapes message text so a name cannot inject markup

server/platformRules.test.ts (15 passing)

[pass] notification templates (OPD-001) builds the variant id from event, channel, language and version
[pass] notification templates (OPD-001) accepts only the backend derived placeholders
[pass] notification templates (OPD-001) refuses markup in template text
[pass] notification templates (OPD-001) escapes values when rendering html and leaves missing values empty
[pass] notification templates (OPD-001) falls back to English when the preferred language has no template
[pass] document matrix (OPD-003) allows only the listed roles
[pass] document matrix (OPD-003) never shows a type to a client unless it is client visible
[pass] document matrix (OPD-003) is closed for unknown types except for administrators
[pass] technical operator scopes (SRS 15.4) treats expired and revoked grants as inactive
[pass] technical operator scopes (SRS 15.4) does not give the Security Center to an operator by role alone
[pass] technical operator scopes (SRS 15.4) keeps administrators and refuses every other role
[pass] AI model routing (SRS 19.6, 19.25) uses the configured model for each class
[pass] AI model routing (SRS 19.6, 19.25) lets a single LLM_MODEL pin every class, as before routing existed
[pass] AI model routing (SRS 19.6, 19.25) falls back to the defaults and treats an unknown class as complex
[pass] AI model routing (SRS 19.6, 19.25) prices a call only when the model has a configured price

server/policy.test.ts (8 passing)

[pass] session length policy uses the built in default when nothing is set
[pass] session length policy uses the environment value when there is no policy
[pass] session length policy lets the policy win over the environment
[pass] session length policy ignores an out of range value instead of locking everyone out
[pass] session length policy returns to the fallback when the policy is cleared
[pass] password length policy defaults to the platform minimum
[pass] password length policy applies a valid configured minimum
[pass] password length policy refuses a minimum below the safe floor

server/privacy.test.ts (18 passing)

[pass] privacy officer authorisation refuses a Super Admin who holds no grant
[pass] privacy officer authorisation refuses an anonymous caller
[pass] privacy officer authorisation admits a granted user whose role is not privileged
[pass] privacy officer authorisation refuses a granted user who has not cleared MFA
[pass] privacy officer authorisation refuses once a grant is revoked
[pass] identity verification gate refuses to locate data for an unverified subject
[pass] identity verification gate locates data once the subject is verified and records what was searched
[pass] export produces JSON carrying the reference and the located data
[pass] export escapes quotes and commas in CSV rather than shifting columns
[pass] export records every export in the audit history
[pass] staged approval refuses to stage an erasure rather than reporting one as done
[pass] staged approval refuses self-approval of a staged action
[pass] staged approval completes when a different authorised person approves
[pass] staged approval records a rejection as a rejection, not a completion
[pass] staged approval refuses approval when nothing is staged
[pass] request record sets a one month statutory deadline from receipt
[pass] request record normalises the subject email so casing cannot split one person in two
[pass] request record keeps an append-only history of every action on the request

server/productionBundle.test.ts (3 passing)

[pass] production server bundle never statically imports vite
[pass] production server bundle imports no devDependency at module scope
[pass] production server bundle still imports the runtime dependencies it needs

server/profileAvatar.test.ts (8 passing)

[pass] sniffImageType identifies PNG, JPEG and WebP from their leading bytes
[pass] sniffImageType rejects an SVG even though browsers render it
[pass] sniffImageType rejects HTML dressed up with an image extension
[pass] sniffImageType rejects a RIFF container that is not WebP
[pass] sniffImageType rejects a payload too short to identify
[pass] decodeBoundedBase64 decodes a payload within the limit
[pass] decodeBoundedBase64 refuses an oversize payload before allocating it
[pass] decodeBoundedBase64 refuses an empty payload

server/queryPerformance.test.ts (6 passing)

[pass] RM-111: index usage under realistic queries looks up a user by email via an index (the login hot path)
[pass] RM-111: index usage under realistic queries looks up a user by openId via an index (every authenticated request)
[pass] RM-111: index usage under realistic queries filters users by organization via an index (tenant scoping)

[pass] RM-111: index usage under realistic queries filters bookings by status via an index
[pass] RM-111: index usage under realistic queries serves the rate-limit window from its composite index
[pass] RM-111: index usage under realistic queries reports the planner's natural choice for the login lookup

server/rawSqlDates.test.ts (97 passing)

[pass] raw sql date parameters scans a meaningful number of db files
[pass] raw sql date parameters db\accounts.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\aiScans.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\auth.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\bookings.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\clientPortal.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\connection.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\crm.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\developerWorkspace.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\emailDelivery.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\index.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\legal.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\mfa.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\payments.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\platformGovernance.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\platformSettings.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\privacy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\solutions.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\srsDelivery.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\srsExtras.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\srsGovernance.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\srsOps.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\srsSales.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\users.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\webhooks.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db\workflows.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\accounts.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\admin.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\adminOps.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\adminPlatform.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\aiScans.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\bookingAdmin.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\bookings.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\clientPortal.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\contact.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\developer.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\engineering.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\legal.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\mfa.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\ops.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\privacy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\profile.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers\solutions.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\aiScanScoring.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\bookingReminders.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\context.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\cookies.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\corsPolicy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\env.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\healthRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\index.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\llm.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\llmUsage.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\localAuthRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\mfaChallenge.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\mfaChallengeRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\mfaCrypto.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\mfaTotp.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\notification.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\oauth.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\operations.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\policy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\publicRef.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\rateLimiter.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\requestMeta.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\resendWebhookRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\sdk.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\securityHeaders.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\smsSender.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\stagingGate.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\staticServer.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\storageProxy.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\stripe.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\stripeWebhookRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\supabaseAuth.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\supabaseAuthRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\systemRouter.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\trpc.ts passes no bare date variable into a raw sql template

[pass] raw sql date parameters _core\viewAsRoute.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters _core\vite.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters aiGovernance.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters aiScanReportPdf.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters db.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters email-i18n.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters email.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters emailShell.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters integrations.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters leadEvaluation.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters legalDb.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters notificationDispatcher.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters notifications.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters paymentSync.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters routers.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters storage.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters webhookDispatcher.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters workflowEngine.ts passes no bare date variable into a raw sql template
[pass] raw sql date parameters the detector itself flags the bad pattern

server/rbac.authOrigin.test.ts (23 passing)

[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects role=client
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects role=developer
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin adminProcedure rejects role=user
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin clientProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin clientProcedure rejects role=user (no client/admin role)
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin clientProcedure rejects role=client with no organizationId
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin developerProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin developerProcedure rejects role=client
[pass] RBAC is identical regardless of auth origin (RM-55) Manus-origin developerProcedure rejects role=user
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin adminProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin adminProcedure rejects role=client
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin adminProcedure rejects role=developer
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin adminProcedure rejects role=user
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin clientProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin clientProcedure rejects role=user (no client/admin role)
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin clientProcedure rejects role=client with no organizationId
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin developerProcedure rejects unauthenticated
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin developerProcedure rejects role=client
[pass] RBAC is identical regardless of auth origin (RM-55) Supabase-origin developerProcedure rejects role=user
[pass] RBAC is identical regardless of auth origin (RM-55) role gating never inspects openId/authUserId - a Supabase-shaped admin passes the SAME adminProcedure check a Manus-shaped admin would reach for
[pass] RBAC is identical regardless of auth origin (RM-55) RM-57: super_admin passes adminProcedure's role gate exactly like admin does (strict superset, not a separate/weaker tier)
[pass] RBAC is identical regardless of auth origin (RM-55) RM-57: plain admin is rejected by superAdminProcedure (super_admin's exclusive capabilities are NOT available to regular admin)

server/resendWebhook.test.ts (6 passing)

[pass] Resend webhook route (Milestone 2 §2.3) rejects with 500 when RESEND_WEBHOOK_SECRET is not configured - fails closed, not silently
[pass] Resend webhook route (Milestone 2 §2.3) rejects an unsigned/tampered payload with 401
[pass] Resend webhook route (Milestone 2 §2.3) rejects a payload signed with the wrong secret
[pass] Resend webhook route (Milestone 2 §2.3) applies a valid email.delivered event to the matching log row
[pass] Resend webhook route (Milestone 2 §2.3) maps email.bounced and email.complained to the right status
[pass] Resend webhook route (Milestone 2 §2.3) acknowledges but ignores event types it doesn't track (e.g. email.opened)

server/rls.negative.test.ts (18 passing)

[pass] RM-60: RLS negative tests (live Supabase project) client A can read their own org's report
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT read client A's org report (cross-tenant read denied)
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT read client A's org invoice (cross-tenant read denied)
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT read client A's organization row directly
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT update client A's org invoice (cross-tenant update denied)
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT delete client A's org report (cross-tenant delete denied)
[pass] RM-60: RLS negative tests (live Supabase project) client A CANNOT read the admin-only leads table
[pass] RM-60: RLS negative tests (live Supabase project) developer X CANNOT read the admin-only leads table
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) request CANNOT read leads at all
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) request CANNOT read client_reports at all
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) request CANNOT read organizations at all
[pass] RM-60: RLS negative tests (live Supabase project) developer Y CANNOT read developer X's developer_profiles row
[pass] RM-60: RLS negative tests (live Supabase project) developer X can read their OWN developer_profiles row
[pass] RM-60: RLS negative tests (live Supabase project) client A (not a developer) CANNOT read any developer_profiles row
[pass] RM-60: RLS negative tests (live Supabase project) client B CANNOT read client A's mfa_factors (even though none exist, the query must return empty, not error, and must not leak existence)
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) CAN read a PUBLISHED agreement version (deliberate public carve-out)
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) CANNOT read a DRAFT agreement version (carve-out is narrowly scoped, not USING(true))
[pass] RM-60: RLS negative tests (live Supabase project) unauthenticated (anon) CAN read the active legal_documents row itself

server/sessionRevocation.test.ts (8 passing)

[pass] RM-90: server-side session revocation accepts a valid session when nothing has been revoked
[pass] RM-90: server-side session revocation rejects a token issued before the revocation cutoff
[pass] RM-90: server-side session revocation rejects a token issued in the same second as the revocation
[pass] RM-90: server-side session revocation accepts a fresh login issued after a revocation
[pass] RM-90: server-side session revocation rejects a legacy token with no iat claim once a revocation exists

[pass] RM-90: server-side session revocation still accepts a legacy token when the user has never revoked
[pass] RM-89/RM-90: issued-at claim is present on every new session signs an iat claim so revocation has something to compare against
[pass] RM-89/RM-90: issued-at claim is present on every new session mints sessions that expire in hours, not a year

server/solutions.test.ts (9 passing)

[pass] solutionsRouter.recordClick records a click without throwing
[pass] solutionsRouter.recordClick swallows DB errors instead of breaking UX
[pass] solutionsRouter.requestProposal creates lead + proposal + notifies owner
[pass] solutionsRouter.requestProposal rejects invalid email
[pass] solutionsRouter.startDiscovery + saveDiscoveryStep + submitDiscovery issues a token, persists progressive saves, and finalizes submission
[pass] solutionsRouter.startDiscovery + saveDiscoveryStep + submitDiscovery blocks submission without name+email
[pass] solutionsRouter.startDiscovery + saveDiscoveryStep + submitDiscovery rejects unknown discovery token
[pass] solutionsRouter admin listings requires admin role
[pass] solutionsRouter admin listings admins can list

server/srsRules.test.ts (61 passing)

[pass] opportunity lifecycle moves forward, never back
[pass] opportunity lifecycle lets any open stage close, and keeps closed stages terminal
[pass] opportunity lifecycle requires an organization to win and a reason to lose
[pass] proposal and quote lifecycle only sends a draft and only decides a sent document
[pass] proposal and quote lifecycle totals in integer cents and rejects bad lines
[pass] time registration accepts today and a recent day
[pass] time registration rejects the future, the distant past, bad minutes and bad dates
[pass] notification preferences defaults to delivering
[pass] notification preferences honours an opt out
[pass] notification preferences scopes an opt out to its own channel
[pass] notification preferences never lets security notifications be switched off
[pass] alert firing fires at the threshold, not below
[pass] alert firing stays quiet for one window after firing
[pass] configuration validation refuses to edit derived values
[pass] configuration validation validates on/off and integer ranges
[pass] configuration validation rejects empty and oversized free text
[pass] scheduling steps daily and weekly
[pass] scheduling clamps a monthly step to the end of a short month
[pass] AI agent authorisation allows a permitted action and flags approval
[pass] AI agent authorisation blocks an action outside its permissions
[pass] AI agent authorisation blocks a disabled or unknown agent
[pass] project archive policy archives only a completed project with nothing pending
[pass] notification category mapping maps kinds to preference categories
[pass] notification category mapping never files an unknown kind under marketing
[pass] CSV export quotes cells with commas, quotes and line breaks
[pass] CSV export defuses spreadsheet formulas
[pass] CSV export builds a header and rows
[pass] LIKE escaping escapes wildcards and the escape character
[pass] AI Scan report lifecycle (SRS 9.6) has exactly the nine statuses the SRS names
[pass] AI Scan report lifecycle (SRS 9.6) walks the happy path in order
[pass] AI Scan report lifecycle (SRS 9.6) cannot skip review: the engine output is never approved or published directly
[pass] AI Scan report lifecycle (SRS 9.6) sends a report back and through review again
[pass] AI Scan report lifecycle (SRS 9.6) treats archived as terminal and publication as one way
[pass] AI Scan report lifecycle (SRS 9.6) shows the customer only a published report
[pass] AI Scan report lifecycle (SRS 9.6) marks approve, revise, publish and archive as human only
[pass] Discovery Call outcomes needs a follow up date when work is left to do
[pass] Discovery Call outcomes does not require one when the matter is closed
[pass] Discovery Call outcomes rejects a follow up date in the past
[pass] questionnaire drafts expires after the retention window
[pass] compliance evaluation passes everything on a clean platform
[pass] compliance evaluation fails an administrator without a second factor and a missed privacy deadline
[pass] compliance evaluation warns on a slowly growing review backlog and fails it only when large
[pass] compliance evaluation fails when nothing is watching for abuse
[pass] compliance evaluation names the count in the detail so the figure can be checked
[pass] monthly history helpers lists the last n months oldest first, across a year boundary
[pass] monthly history helpers fills missing months with zero and keeps the order
[pass] monthly history helpers knows the capacity metrics
[pass] invitations (SRS 8.7) lets a super admin invite anyone
[pass] invitations (SRS 8.7) lets an admin invite only customers and developers, so a stolen admin cannot mint admins
[pass] invitations (SRS 8.7) lets nobody else invite
[pass] invitations (SRS 8.7) requires MFA for the privileged roles only
[pass] invitations (SRS 8.7) derives the invitation state, with accepted and revoked beating expiry
[pass] password strength accepts a long mixed password
[pass] password strength refuses short, single letter run, letters only, numbers only
[pass] password strength refuses a password that contains the email name
[pass] password strength refuses an oversized password
[pass] password strength explains each refusal in words for the person choosing
[pass] project lifecycle (SRS 15.5) moves forward one stage at a time
[pass] project lifecycle (SRS 15.5) lets a review send work back to in progress and nothing else go backwards
[pass] project lifecycle (SRS 15.5) treats archived as final and rejects unknown stages
[pass] project lifecycle (SRS 15.5) keeps the coarse status older screens read

server/stagingGate.test.ts (11 passing)

[pass] stagingGate - STAGING_MODE=on blocks anonymous GET / with the pre-launch screen
[pass] stagingGate - STAGING_MODE=on does not gate /api/* requests
[pass] stagingGate - STAGING_MODE=on does not gate static assets
[pass] stagingGate - STAGING_MODE=on rejects unlock with wrong password
[pass] stagingGate - STAGING_MODE=on accepts unlock with correct password and sets the cookie

[pass] stagingGate - STAGING_MODE=on lets a request through when carrying a valid staging cookie
[pass] stagingGate - STAGING_MODE=on rejects a tampered staging cookie
[pass] stagingGate - STAGING_MODE=on lets a request through when an authenticated session cookie is present
[pass] stagingGate - STAGING_MODE=on returns Disallow: / from /robots.txt
[pass] stagingGate - STAGING_MODE off does not gate anonymous requests
[pass] stagingGate - STAGING_MODE off returns Allow: / from /robots.txt

server/stripe.test.ts (11 passing)

[pass] verifyStripeSignature accepts a correct, fresh signature
[pass] verifyStripeSignature rejects a wrong secret, a changed body and a stale timestamp
[pass] processStripeEvent: invoices marks an invoice paid once and notifies the client
[pass] processStripeEvent: invoices ignores a redelivered event
[pass] processStripeEvent: invoices does not mark paid when the amount differs from the invoice
[pass] processStripeEvent: invoices does not treat an unpaid completed session as payment
[pass] processStripeEvent: invoices records a failed asynchronous payment and tells the client
[pass] processStripeEvent: invoices ignores events that are not for this platform
[pass] processStripeEvent: AI Scan purchase creates the account invitation only after verified payment
[pass] processStripeEvent: AI Scan purchase grants nothing on a wrong amount
[pass] processStripeEvent: AI Scan purchase does not invite twice for a redelivery

server/supabaseAuth.test.ts (5 passing)

[pass] getSupabaseAdmin throws a clear config error when SUPABASE_URL/SECRET_KEY are unset
[pass] getSupabaseAdmin succeeds once both vars are set
[pass] verifySupabaseAccessToken returns null for a missing token without touching config
[pass] verifySupabaseAccessToken throws a clear config error when SUPABASE_JWKS_URL is unset, rather than silently returning null
[pass] verifySupabaseAccessToken returns null (not a throw) for a malformed token once JWKS is configured

server/viewAs.test.ts (5 passing)

[pass] View-As impersonation token round-trips a signed token and exposes the claim
[pass] View-As impersonation token rejects an empty / missing token
[pass] View-As impersonation token rejects a tampered payload
[pass] View-As impersonation token rejects a token signed with the wrong secret
[pass] View-As impersonation token exposes a stable cookie name

server/webhookDispatcher.test.ts (5 passing)

[pass] dispatchWebhooksForTrigger does nothing when no enabled registrations match the trigger
[pass] dispatchWebhooksForTrigger POSTs to the registered URL and records a successful delivery
[pass] dispatchWebhooksForTrigger signs the payload with HMAC-SHA256 when the registration has a secret
[pass] dispatchWebhooksForTrigger records a failed delivery (not a throw) on a non-2xx response
[pass] dispatchWebhooksForTrigger catches a network error and records a failed delivery with statusCode null

server/workflowCoverage.test.ts (26 passing)

[pass] RM-109: every converted workflow has a test suite CRM / leads pipeline is covered by its suite
[pass] RM-109: every converted workflow has a test suite Billing / invoice creation is covered by its suite
[pass] RM-109: every converted workflow has a test suite Support ticketing is covered by its suite
[pass] RM-109: every converted workflow has a test suite Reports & projects bridge is covered by its suite
[pass] RM-109: every converted workflow has a test suite Executive overview summary is covered by its suite
[pass] RM-109: every converted workflow has a test suite Admin action / audited buttons is covered by its suite
[pass] RM-109: every converted workflow has a test suite Developer access granting is covered by its suite
[pass] RM-109: every converted workflow has a test suite Developer project, task and message delivery is covered by its suite
[pass] RM-109: every converted workflow has a test suite SRS completion (CRM, quotes, governance, incidents, alerts) is covered by its suite
[pass] RM-109: every converted workflow has a test suite Account invitation and activation is covered by its suite
[pass] RM-109: every converted workflow has a test suite SRS business rules (lifecycles, policy, validation) is covered by its suite
[pass] RM-109: every converted workflow has a test suite AI Scan retrigger is covered by its suite
[pass] RM-109: every converted workflow has a test suite Super Admin & role management is covered by its suite
[pass] RM-109: every converted workflow has a test suite Platform configuration store is covered by its suite
[pass] RM-109: every converted workflow has a test suite Business intelligence / analytics is covered by its suite
[pass] RM-109: every converted workflow has a test suite MFA compliance posture is covered by its suite
[pass] RM-109: every converted workflow has a test suite Document lifecycle is covered by its suite
[pass] RM-109: every converted workflow has a test suite Workflow definition engine is covered by its suite
[pass] RM-109: every converted workflow has a test suite Integration & webhook registry is covered by its suite
[pass] RM-109: every converted workflow has a test suite Client portal is covered by its suite
[pass] RM-109: every converted workflow has a test suite Developer portal is covered by its suite
[pass] RM-109: every converted workflow has a test suite Booking engine is covered by its suite
[pass] RM-109: every converted workflow has a test suite Booking administration is covered by its suite
[pass] RM-109: every converted workflow has a test suite Email delivery tracking is covered by its suite
[pass] RM-109: every converted workflow has a test suite each suite actually contains assertions
[pass] RM-109: every converted workflow has a test suite covers every admin router test file that exists

server/workflowEngine.test.ts (5 passing)

[pass] runWorkflowsForTrigger does nothing when no enabled definitions match the trigger
[pass] runWorkflowsForTrigger runs a notify_owner action, substitutes template tokens, and records a succeeded run
[pass] runWorkflowsForTrigger runs an audit_log action and records a succeeded run
[pass] runWorkflowsForTrigger catches a notify_owner failure and records a failed run instead of throwing
[pass] runWorkflowsForTrigger runs every matching enabled definition, not just the first

server/workflowSchedule.test.ts (6 passing)

[pass] runDueScheduledWorkflows does nothing when no workflow is due
[pass] runDueScheduledWorkflows runs each claimed workflow and logs a successful run for it
[pass] runDueScheduledWorkflows records a failure and still runs the next workflow
[pass] runDueScheduledWorkflows hands the claim a monthly rule that clamps to the end of a short month
[pass] fireTrigger runs matching workflows and registered webhooks
[pass] fireTrigger does not throw when workflows or webhooks fail, and still tries the webhooks

client/src/tailwindArbitraryValues.test.ts (2 passing)

[pass] Tailwind arbitrary values finds source files to scan
[pass] Tailwind arbitrary values contains no arbitrary value with a raw space

client/src/components/NotificationBell.test.tsx (14 passing)

[pass] RM-99: unread badge shows the unread count
[pass] RM-99: unread badge counts a notification with an undefined readAt as unread
[pass] RM-99: unread badge hides the badge entirely when everything is read
[pass] RM-99: unread badge stays accessible by name
[pass] RM-99: dropdown behaviour opens on click and lists the notifications
[pass] RM-99: dropdown behaviour renders the notification body when present
[pass] RM-99: dropdown behaviour shows an empty state rather than a blank panel
[pass] RM-99: mark-as-read and archive are wired marks a single notification read
[pass] RM-99: mark-as-read and archive are wired offers mark-read only on unread items
[pass] RM-99: mark-as-read and archive are wired marks every unread item read from the header action
[pass] RM-99: mark-as-read and archive are wired hides 'Mark all read' when nothing is unread
[pass] RM-99: mark-as-read and archive are wired archives a notification
[pass] RM-99: mark-as-read and archive are wired does not mark read when archiving
[pass] RM-99: priority indicator falls back to the normal dot for an unrecognised priority

client/src/components/RouteTransition.test.tsx (4 passing)

[pass] RouteTransition carries no transform and no will-change once settled
[pass] RouteTransition is fully opaque once settled, so content is never left invisible
[pass] RouteTransition settles even if the transition never fires
[pass] RouteTransition renders its children

client/src/lib/industries.test.ts (6 passing)

[pass] searchIndustries returns every canonical option for an empty query
[pass] searchIndustries matches the canonical label directly
[pass] searchIndustries surfaces the canonical category from a Dutch alias
[pass] searchIndustries is case-insensitive and tolerant of punctuation
[pass] searchIndustries never returns a value outside the canonical list
[pass] searchIndustries returns nothing for a query matching no label or alias

client/src/lib/siteImages.test.ts (6 passing)

[pass] dead asset host is referenced nowhere in the client
[pass] no hardcoded image URLs in pages routes every remote image through the registry
[pass] registry derives a sensible env var name for each key
[pass] registry returns null for an unsupplied visual rather than a placeholder URL
[pass] registry labels every key, so a placeholder always names what belongs there
[pass] registry reports the current gap honestly

client/src/pages/Login.test.tsx (12 passing)

[pass] RM-98: Login form rendering renders both credential fields
[pass] RM-98: Login form rendering masks the password by default
[pass] RM-98: Login form rendering sets autocomplete hints so password managers behave
[pass] RM-98: Login form rendering ships a honeypot field that is hidden from autocomplete
[pass] RM-98: Login form validation disables submit until the form is valid
[pass] RM-98: Login form validation keeps submit disabled for a malformed email
[pass] RM-98: Login form validation keeps submit disabled for a password under 8 characters
[pass] RM-98: Login anti-automation gates blocks a submission made immediately after mount
[pass] RM-98: Login anti-automation gates blocks a submission when the honeypot field is filled
[pass] RM-98: Remember-me hydration pre-fills the email from localStorage on mount
[pass] RM-98: Remember-me hydration renders normally when localStorage is unavailable
[pass] RM-98: password visibility toggle reveals and re-masks the password

client/src/_core/hooks/useRouteGuard.test.ts (8 passing)

[pass] roleHome maps every known role to its portal
[pass] roleHome falls back to / for user role and unknown/missing values
[pass] isAdminRole (RM-57) is true for admin and super_admin (strict superset)
[pass] isAdminRole (RM-57) is false for every non-admin role and missing values
[pass] isImpersonatingTarget is true only when impersonation is active AND targets the given role
[pass] isImpersonatingTarget is false for null/undefined user or missing impersonation
[pass] recordAttemptProvider passes through every valid non-manus/credentials provider value
[pass] recordAttemptProvider falls back to credentials for unknown values, including the ones deriveLoginMethod() can actually produce

client/src/pages/admin/sections/_shared/adminModuleState.test.tsx (16 passing)

[pass] RM-100: ModuleStateBoundary state machine shows a loading state while the query is in flight
[pass] RM-100: ModuleStateBoundary state machine renders the happy path when data arrives
[pass] RM-100: ModuleStateBoundary state machine distinguishes 'permission denied' from 'no data'
[pass] RM-100: ModuleStateBoundary state machine treats UNAUTHORIZED the same as FORBIDDEN
[pass] RM-100: ModuleStateBoundary state machine surfaces a genuine failure as an alert, not as an empty state
[pass] RM-100: ModuleStateBoundary state machine falls back to a generic message when the error carries none
[pass] RM-100: ModuleStateBoundary state machine offers retry only when a retry handler was supplied
[pass] RM-100: ModuleStateBoundary state machine shows the connected-but-empty state when isEmpty reports true
[pass] RM-100: ModuleStateBoundary state machine renders nothing at all when data is undefined and there is no error
[pass] RM-100: ModuleStateBoundary state machine does not treat a present-but-falsy payload as missing
[pass] RM-100: DataTable renders headers and rows
[pass] RM-100: DataTable shows an explicit empty label instead of a bare table shell
[pass] RM-100: DataTable honours a caller-supplied empty label
[pass] RM-100: DataTable uses a custom cell renderer when one is provided
[pass] RM-100: StatusPill renders each tone with its label
[pass] RM-100: StatusPill visually separates a failure tone from a success tone

Appendix C: Database schema

The live database has 93 tables. Each is listed with its row count, columns, indexes and foreign keys at capture time.

account_invitations (rows: 4, indexes: 7, foreign keys: 3)

id integer not null, tokenHash character varying not null, email character varying not null, role character varying not null, organizationId integer, invitedByUserId integer, expiresAt timestamp without time zone not null, acceptedAt timestamp without time zone, acceptedUserId integer, revokedAt timestamp without time zone, createdAt timestamp without time zone not null

admin_availability (rows: 0, indexes: 1, foreign keys: 0)

id integer not null, consultationType character varying not null, weekday integer not null, startMinute integer not null, endMinute integer not null, timezone character varying not null, active integer not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

admin_notifications (rows: 20, indexes: 2, foreign keys: 1)

id integer not null, kind character varying not null, title character varying not null, body text, href character varying, priority character varying not null, readAt timestamp without time zone, readByUserId integer, createdAt timestamp without time zone not null

agreement_acceptances (rows: 0, indexes: 3, foreign keys: 3)

id integer not null, userId integer not null, organizationId integer, versionId integer not null, documentKind character varying not null, acceptedAt timestamp without time zone not null, ip character varying, userAgent text, method character varying not null

agreement_versions (rows: 0, indexes: 2, foreign keys: 2)

id integer not null, documentId integer not null, version character varying not null, language character varying not null, bodyMd text not null, bodyHash character varying not null, effectiveFrom timestamp without time zone not null, status USER-DEFINED not null, createdAt timestamp without time zone not null, createdBy integer

ai_agents (rows: 1, indexes: 2, foreign keys: 0)

id integer not null, key character varying not null, name character varying not null, purpose text, status character varying not null, permissionsJson text not null, requiresHumanApproval boolean not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

ai_executions (rows: 2, indexes: 2, foreign keys: 1)

id integer not null, agentKey character varying not null, promptVersion integer, action character varying not null, subjectRef character varying, outcome character varying not null, detail text, approvedByUserId integer, createdAt timestamp without time zone not null

ai_prompt_versions (rows: 2, indexes: 3, foreign keys: 2)

id integer not null, agentKey character varying not null, version integer not null, body text not null, changeNote text, isActive boolean not null, createdByUserId integer, createdAt timestamp without time zone not null

ai_scan_drafts (rows: 3, indexes: 3, foreign keys: 0)

id integer not null, resumeToken character varying not null, tier character varying not null, email character varying, answersJson text not null, stepIndex integer not null, expiresAt timestamp without time zone not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

ai_scan_status_events (rows: 3, indexes: 3, foreign keys: 2)

id integer not null, scanId integer not null, fromStatus character varying, toStatus character varying not null, actorUserId integer, note text, createdAt timestamp without time zone not null

ai_scans (rows: 4, indexes: 6, foreign keys: 3)

id integer not null, reportToken character varying not null, tier USER-DEFINED not null, leadId integer, fullName character varying not null, email character varying not null, company character varying, locale character varying not null, responses text not null, status USER-DEFINED not null, reportPayload text, overallScore integer, reportPdfKey character varying, errorMessage text, utmSource character varying, utmCampaign character varying, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null, scoredAt timestamp without time zone, reportStatus character varying not null, reviewerUserId integer, reviewNote text, approvedByUserId integer, approvedAt timestamp without time zone, publishedAt timestamp without time zone

ai_usage (rows: 0, indexes: 2, foreign keys: 0)

id integer not null, model character varying not null, complexity character varying not null, purpose character varying, promptTokens integer not null, completionTokens integer not null, costMicros integer, createdAt timestamp without time zone not null

alert_rules (rows: 6, indexes: 2, foreign keys: 0)

id integer not null, key character varying not null, title character varying not null, metric character varying not null, threshold integer not null, windowMinutes integer not null, severity character varying not null, enabled boolean not null, lastFiredAt timestamp without time zone, createdAt timestamp without time zone not null

availability_windows (rows: 0, indexes: 1, foreign keys: 0)

id integer not null, consultationType character varying, kind USER-DEFINED not null, startMs bigint not null, endMs bigint not null, reason character varying, createdAt timestamp without time zone not null

booking_answers (rows: 72, indexes: 2, foreign keys: 1)

id integer not null, bookingId integer not null, question character varying not null, answer text not null, createdAt timestamp without time zone not null

booking_audit (rows: 36, indexes: 2, foreign keys: 1)

id integer not null, bookingId integer not null, event character varying not null, detail text, createdAt timestamp without time zone not null

booking_events (rows: 9, indexes: 2, foreign keys: 1)

id integer not null, bookingId integer not null, event character varying not null, actorOpenId character varying, detail text, createdAt timestamp without time zone not null

booking_outcomes (rows: 1, indexes: 3, foreign keys: 2)

id integer not null, bookingId integer not null, outcome character varying not null, notes text, followUpAt timestamp without time zone, recordedByUserId integer, createdAt timestamp without time zone not null

booking_reminders (rows: 19, indexes: 2, foreign keys: 1)

id integer not null, bookingId integer not null, kind USER-DEFINED not null, scheduledForMs bigint not null, sentAt timestamp without time zone, errorDetail text, createdAt timestamp without time zone not null

booking_slots (rows: 6, indexes: 4, foreign keys: 0)

id integer not null, consultationType character varying not null, slotStartMs bigint not null, slotEndMs bigint not null, status USER-DEFINED not null, bookingId integer, holdToken character varying, holdExpiresAtMs bigint, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

bookings (rows: 9, indexes: 3, foreign keys: 0)

id integer not null, publicRef character varying not null, serviceId character varying not null, slotStartMs bigint not null, durationMin integer not null, timezone character varying not null, fullName character varying not null, email character varying not null, company character varying, roleTitle character varying, phone character varying, preparation text, note text, utmSource character varying, utmCampaign character varying, status USER-DEFINED not null, emailSent integer not null, ownerNotified integer not null, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null, callType USER-DEFINED not null, meetingUrl text, locale character varying

calendar_blocks (rows: 0, indexes: 1, foreign keys: 0)

id integer not null, startMs bigint not null, endMs bigint not null, label character varying not null, createdAt timestamp without time zone not null

client_documents (rows: 2, indexes: 4, foreign keys: 3)

id integer not null, organizationId integer not null, name character varying not null, category character varying not null, fileKey character varying not null, sizeBytes integer, mimeType character varying, uploadedByUserId integer, uploadedBy character varying, createdAt timestamp without time zone not null, documentGroupId integer, version integer not null, status USER-DEFINED not null, reviewedByUserId integer, reviewedAt timestamp without time zone, reviewNote text, retentionNote text, documentType character varying

client_invoices (rows: 4, indexes: 4, foreign keys: 1)

id integer not null, organizationId integer not null, number character varying not null, description character varying not null, amountCents integer not null, currency character varying not null, status USER-DEFINED not null, issuedMs bigint not null, dueMs bigint, paidMs bigint, pdfKey character varying, stripeSessionId character varying, stripeInvoiceUrl character varying

client_messages (rows: 15, indexes: 2, foreign keys: 1)

id integer not null, organizationId integer not null, threadKey character varying not null, sender USER-DEFINED not null, senderName character varying, subject character varying, body text not null, readAt bigint, createdAt timestamp without time zone not null

client_notifications (rows: 25, indexes: 2, foreign keys: 1)

id integer not null, organizationId integer not null, kind character varying not null, title character varying not null, body text, href character varying, readAt bigint, createdAt timestamp without time zone not null, priority USER-DEFINED not null, channel USER-DEFINED not null, templateKey character varying, status USER-DEFINED not null

client_project_milestones (rows: 4, indexes: 2, foreign keys: 1)

id integer not null, projectId integer not null, title character varying not null, dueMs bigint, status USER-DEFINED not null, body text

client_projects (rows: 3, indexes: 2, foreign keys: 1)

id integer not null, organizationId integer not null, name character varying not null, phase character varying not null, progress integer not null, startMs bigint, targetMs bigint, status USER-DEFINED not null, summary text, createdAt timestamp without time zone not null, archivedAt timestamp without time zone, lifecycle character varying not null

client_recommendations (rows: 0, indexes: 3, foreign keys: 2)

id integer not null, organizationId integer not null, reportId integer, title character varying not null, category character varying not null, impact USER-DEFINED not null, status USER-DEFINED not null, body text, createdAt timestamp without time zone not null

client_reports (rows: 1, indexes: 3, foreign keys: 1)

id integer not null, organizationId integer not null, publicRef character varying not null, title character varying not null, scanType character varying not null, score integer not null, delta integer not null, summary text, pdfKey character varying, status USER-DEFINED not null, pages integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

client_support_tickets (rows: 1, indexes: 4, foreign keys: 2)

id integer not null, organizationId integer not null, openedByUserId integer, publicRef character varying not null, subject character varying not null, body text not null, category character varying not null, priority USER-DEFINED not null, status USER-DEFINED not null, createdAt timestamp without time zone not null

config_history (rows: 8, indexes: 2, foreign keys: 1)

id integer not null, settingKey character varying not null, oldValue text, newValue text not null, outcome character varying not null, reason text, changedByUserId integer, createdAt timestamp without time zone not null

contact_submissions (rows: 0, indexes: 2, foreign keys: 0)

id integer not null, publicRef character varying not null, fullName character varying not null, email character varying not null, phone character varying, company character varying, industry character varying, size character varying, subject character varying not null, message text not null, status USER-DEFINED not null, emailSent integer not null, ownerNotified integer not null, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

cookie_consents (rows: 19, indexes: 2, foreign keys: 2)

id integer not null, subjectKey character varying not null, userId integer, policyVersionId integer, categoriesJson text not null, decision character varying not null, acceptedAt timestamp without time zone not null, ip character varying, userAgent text

crm_activities (rows: 5, indexes: 4, foreign keys: 4)

id integer not null, kind character varying not null, subject character varying not null, body text, leadId integer, opportunityId integer, organizationId integer, dueAt timestamp without time zone, completedAt timestamp without time zone, createdByUserId integer, createdAt timestamp without time zone not null

crm_opportunities (rows: 4, indexes: 2, foreign keys: 4)

id integer not null, title character varying not null, leadId integer, organizationId integer, stage character varying not null, valueCents bigint not null, currency character varying not null, ownerUserId integer, expectedCloseDate date, lostReason text, handoverClientProjectId integer, closedAt timestamp without time zone, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

crm_proposals (rows: 1, indexes: 2, foreign keys: 2)

id integer not null, opportunityId integer not null, title character varying not null, status character varying not null, amountCents bigint not null, currency character varying not null, validUntil date, body text, sentAt timestamp without time zone, decidedAt timestamp without time zone, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

custom_discovery_sessions (rows: 0, indexes: 3, foreign keys: 1)

id integer not null, token character varying not null, fullName character varying, email character varying, company character varying, phone character varying, needsTypes text, currentSystems text, teamSize character varying, growthStage character varying, complianceTags text, integrations text, timeline character varying, urgency character varying, preferredNext USER-DEFINED, status USER-DEFINED not null, leadId integer, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null, submittedAt timestamp without time zone

deployments (rows: 20, indexes: 2, foreign keys: 0)

id integer not null, commitSha character varying, environment character varying not null, nodeVersion character varying not null, startedAt timestamp without time zone not null

dev_applications (rows: 0, indexes: 2, foreign keys: 0)

id integer not null, publicRef character varying not null, fullName character varying not null, email character varying not null, phone character varying, company character varying, roleTitle character varying, yearsExperience integer, links text, message text, ackNda integer not null, ackConfidentiality integer not null, ackNonSolicitation integer not null, status USER-DEFINED not null, reviewerNote text, ownerNotified integer not null, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_access_requests (rows: 0, indexes: 2, foreign keys: 3)

id integer not null, developerId integer not null, scopeId integer, reason text not null, status USER-DEFINED not null, reviewerNote text, reviewedByUserId integer, reviewedMs bigint, createdAt timestamp without time zone not null

developer_access_scopes (rows: 1, indexes: 2, foreign keys: 2)

id integer not null, developerId integer not null, level USER-DEFINED not null, allowedActions text, allowedRoutes text, startMs bigint not null, expiresMs bigint, status USER-DEFINED not null, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_agreements (rows: 5, indexes: 2, foreign keys: 1)

id integer not null, developerId integer not null, agreementType character varying not null, version character varying not null, status USER-DEFINED not null, signedMs bigint, signedIp character varying, signedUserAgent text, documentKey character varying, createdAt timestamp without time zone not null

developer_audit (rows: 8, indexes: 2, foreign keys: 1)

id integer not null, developerId integer, event character varying not null, detail text, ip character varying, userAgent text, createdAt timestamp without time zone not null

developer_messages (rows: 1, indexes: 2, foreign keys: 1)

id integer not null, developerId integer not null, sender USER-DEFINED not null, senderName character varying, subject character varying, body text not null, readAt bigint, createdAt timestamp without time zone not null

developer_notifications (rows: 5, indexes: 2, foreign keys: 1)

id integer not null, developerId integer not null, kind character varying not null, title character varying not null, body text, href character varying, readAt bigint, createdAt timestamp without time zone not null, priority USER-DEFINED not null, channel USER-DEFINED not null, templateKey character varying, status USER-DEFINED not null

developer_profiles (rows: 1, indexes: 3, foreign keys: 3)

id integer not null, userId integer not null, applicationId integer, fullName character varying not null, country character varying, linkedin character varying, github character varying, portfolio character varying, specialties character varying, yearsExperience integer, availability USER-DEFINED not null, status USER-DEFINED not null, mfaRequired integer not null, approvedMs bigint, approvedByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_project_assignments (rows: 1, indexes: 3, foreign keys: 3)

id integer not null, projectId integer not null, developerId integer not null, assignmentRole USER-DEFINED not null, status USER-DEFINED not null, progress integer not null, startMs bigint, endMs bigint, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_project_files (rows: 0, indexes: 2, foreign keys: 2)

id integer not null, projectId integer not null, name character varying not null, fileKey character varying not null, sizeBytes integer, mimeType character varying, category character varying not null, uploadedByUserId integer, createdAt timestamp without time zone not null

developer_projects (rows: 1, indexes: 2, foreign keys: 1)

id integer not null, code character varying not null, name character varying not null, brief text, track character varying not null, status USER-DEFINED not null, startMs bigint, targetMs bigint, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_security_events (rows: 0, indexes: 3, foreign keys: 2)

id integer not null, developerId integer, kind character varying not null, severity USER-DEFINED not null, message character varying not null, detail text, ip character varying, userAgent text, acknowledgedAt bigint, acknowledgedByUserId integer, createdAt timestamp without time zone not null

developer_submissions (rows: 0, indexes: 3, foreign keys: 3)

id integer not null, projectId integer not null, developerId integer not null, kind USER-DEFINED not null, title character varying not null, body text, fileKey character varying, repository character varying, sha character varying, branch character varying, status USER-DEFINED not null, reviewerNote text, reviewedByUserId integer, reviewedMs bigint, createdAt timestamp without time zone not null

developer_support_tickets (rows: 0, indexes: 3, foreign keys: 1)

id integer not null, developerId integer not null, publicRef character varying not null, subject character varying not null, body text not null, category character varying not null, priority USER-DEFINED not null, status USER-DEFINED not null, createdAt timestamp without time zone not null

developer_task_assignments (rows: 3, indexes: 3, foreign keys: 2)

id integer not null, taskId integer not null, developerId integer not null, status USER-DEFINED not null, createdAt timestamp without time zone not null

developer_task_comments (rows: 3, indexes: 4, foreign keys: 3)

id integer not null, taskId integer not null, developerId integer, authorUserId integer, kind character varying not null, body text not null, createdAt timestamp without time zone not null

developer_tasks (rows: 3, indexes: 3, foreign keys: 2)

id integer not null, projectId integer not null, title character varying not null, body text, status USER-DEFINED not null, priority USER-DEFINED not null, dueMs bigint, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

developer_time_entries (rows: 5, indexes: 3, foreign keys: 4)

id integer not null, developerId integer not null, projectId integer not null, taskId integer, workDate date not null, minutes integer not null, note text, status character varying not null, reviewedByUserId integer, reviewedAt timestamp without time zone, reviewNote text, createdAt timestamp without time zone not null

document_matrix (rows: 11, indexes: 2, foreign keys: 1)

documentType character varying not null, label character varying not null, owningEntity character varying not null, authorizedRoles text not null, versioned boolean not null, approvalRequired boolean not null, retentionDays integer, archiveOnProjectCompletion boolean not null, classification character varying not null, clientVisible boolean not null, provisional boolean not null, updatedByUserId integer, updatedAt timestamp without time zone not null

ecosystem_click_events (rows: 49, indexes: 2, foreign keys: 1)

id integer not null, eventKey character varying not null, source character varying not null, ecosystem character varying, sessionToken character varying, userId integer, ip character varying, userAgent text, payload text, createdAt timestamp without time zone not null

ecosystem_proposal_requests (rows: 0, indexes: 2, foreign keys: 1)

id integer not null, ecosystem USER-DEFINED not null, fullName character varying not null, email character varying not null, company character varying, phone character varying, message text, goals text, source character varying not null, status USER-DEFINED not null, leadId integer, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

email_delivery_log (rows: 29, indexes: 4, foreign keys: 0)

id integer not null, messageType USER-DEFINED not null, transport character varying not null, providerMessageId character varying, recipient character varying not null, subject character varying, relatedRef character varying, status USER-DEFINED not null, errorMessage text, providerResponse text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

incidents (rows: 5, indexes: 2, foreign keys: 2)

id integer not null, category character varying not null, title character varying not null, description text, severity character varying not null, status character varying not null, assignedToUserId integer, resolution text, reportedByUserId integer, closedAt timestamp without time zone, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

leads (rows: 11, indexes: 2, foreign keys: 0)

id integer not null, source character varying not null, sourceId integer, fullName character varying not null, email character varying not null, company character varying, phone character varying, interest character varying, note text, status USER-DEFINED not null, utmSource character varying, utmCampaign character varying, ip character varying, userAgent text, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

legal_acknowledgements (rows: 0, indexes: 2, foreign keys: 2)

id integer not null, userId integer, documentKind character varying not null, versionId integer, context character varying not null, acknowledgedAt timestamp without time zone not null, ip character varying

legal_documents (rows: 0, indexes: 3, foreign keys: 0)

id integer not null, kind character varying not null, slug character varying not null, title character varying not null, jurisdiction character varying, defaultLanguage character varying not null, status USER-DEFINED not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

login_audit (rows: 1143, indexes: 2, foreign keys: 1)

id integer not null, userId integer, identifier character varying, provider character varying not null, outcome character varying not null, reason character varying, ip character varying, userAgent text, createdAt timestamp without time zone not null

mfa_challenges (rows: 0, indexes: 3, foreign keys: 2)

id integer not null, userId integer not null, state character varying not null, purpose USER-DEFINED not null, expectedKind USER-DEFINED not null, factorId integer, failedAttempts integer not null, expiresAt timestamp without time zone not null, consumedAt timestamp without time zone, ip character varying, userAgent text, createdAt timestamp without time zone not null

mfa_factors (rows: 6, indexes: 2, foreign keys: 1)

id integer not null, userId integer not null, kind USER-DEFINED not null, label character varying, secret text not null, phoneHint character varying, verifiedAt timestamp without time zone, primary integer not null, failedAttempts integer not null, lockedUntilMs bigint, createdAt timestamp without time zone not null, lastUsedAt timestamp without time zone

mfa_recovery_codes (rows: 30, indexes: 2, foreign keys: 1)

id integer not null, userId integer not null, codeHash character varying not null, usedAt timestamp without time zone, createdAt timestamp without time zone not null

notification_events (rows: 19, indexes: 4, foreign keys: 0)

id integer not null, eventId character varying not null, eventName character varying not null, audience character varying not null, recipientRef character varying not null, dedupKey character varying not null, priority character varying not null, title character varying not null, emailRequested boolean not null, createdAt timestamp without time zone not null

notification_preferences (rows: 1, indexes: 2, foreign keys: 1)

id integer not null, userId integer not null, category character varying not null, channel character varying not null, enabled boolean not null, updatedAt timestamp without time zone not null

notification_templates (rows: 0, indexes: 3, foreign keys: 1)

id integer not null, eventName character varying not null, channel character varying not null, locale character varying not null, version integer not null, subject character varying not null, body text not null, status character varying not null, createdByUserId integer, createdAt timestamp without time zone not null

operator_scopes (rows: 0, indexes: 3, foreign keys: 2)

id integer not null, userId integer not null, scope character varying not null, expiresAt timestamp without time zone, revokedAt timestamp without time zone, grantedByUserId integer, note character varying, createdAt timestamp without time zone not null

organization_memberships (rows: 2, indexes: 3, foreign keys: 2)

id integer not null, organizationId integer not null, userId integer not null, membershipRole USER-DEFINED not null, createdAt timestamp without time zone not null

organizations (rows: 78, indexes: 2, foreign keys: 0)

id integer not null, slug character varying not null, name character varying not null, legalName character varying, industry character varying, size character varying, country character varying, operationalScore integer not null, accentHex character varying, statusLabel character varying not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

payment_events (rows: 2, indexes: 2, foreign keys: 0)

id integer not null, providerEventId character varying not null, type character varying not null, invoiceId integer, organizationId integer, scanPurchaseId integer, amountCents integer, currency character varying, outcome character varying not null, detail text, createdAt timestamp without time zone not null

platform_settings (rows: 12, indexes: 3, foreign keys: 1)

id integer not null, section character varying not null, key character varying not null, title character varying not null, description text, value text not null, updatedByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

privacy_officer_grants (rows: 0, indexes: 2, foreign keys: 3)

id integer not null, userId integer not null, grantedByUserId integer, reason text not null, grantedAt timestamp without time zone not null, revokedAt timestamp without time zone, revokedByUserId integer, revokedReason text

privacy_request_events (rows: 0, indexes: 2, foreign keys: 2)

id integer not null, requestId integer not null, actorUserId integer, event character varying not null, detail text, ip character varying, userAgent text, createdAt timestamp without time zone not null

privacy_requests (rows: 0, indexes: 5, foreign keys: 3)

id integer not null, publicRef character varying not null, requestType character varying not null, subjectUserId integer, subjectEmail character varying not null, subjectName character varying, receivedAt timestamp without time zone not null, dueAt timestamp without time zone, identityVerificationStatus character varying not null, identityVerificationNote text, identityVerifiedAt timestamp without time zone, identityVerifiedByUserId integer, assignedToUserId integer, affectedSystemsJson text, actionsTakenJson text, status character varying not null, decision text, completedAt timestamp without time zone, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

project_approvals (rows: 2, indexes: 2, foreign keys: 4)

id integer not null, projectId integer not null, milestoneId integer, title character varying not null, description text, status character varying not null, requestedByUserId integer, decidedByUserId integer, decisionNote text, decidedAt timestamp without time zone, createdAt timestamp without time zone not null

project_lifecycle_events (rows: 0, indexes: 3, foreign keys: 2)

id integer not null, projectId integer not null, fromState character varying, toState character varying not null, actorUserId integer, note character varying, createdAt timestamp without time zone not null

quotes (rows: 1, indexes: 2, foreign keys: 3)

id integer not null, publicRef character varying not null, organizationId integer, opportunityId integer, title character varying not null, linesJson text not null, totalCents bigint not null, currency character varying not null, status character varying not null, validUntil date, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

rate_limit_hits (rows: 14, indexes: 3, foreign keys: 0)

id bigint not null, key character varying not null, hitAtMs bigint not null

scan_purchases (rows: 10, indexes: 2, foreign keys: 0)

id integer not null, tier character varying not null, email character varying not null, fullName character varying not null, company character varying, locale character varying not null, amountCents integer not null, currency character varying not null, stripeSessionId character varying, status character varying not null, leadId integer, organizationId integer, createdAt timestamp without time zone not null, paidAt timestamp without time zone

scheduled_reports (rows: 1, indexes: 1, foreign keys: 1)

id integer not null, name character varying not null, reportKind character varying not null, cadence character varying not null, recipientsJson text not null, enabled boolean not null, nextRunAt timestamp without time zone not null, lastRunAt timestamp without time zone, lastStatus character varying, createdByUserId integer, createdAt timestamp without time zone not null

subscriptions (rows: 1, indexes: 2, foreign keys: 1)

id integer not null, organizationId integer not null, plan character varying not null, status character varying not null, amountCents bigint not null, currency character varying not null, billingInterval character varying not null, startedAt timestamp without time zone not null, renewsAt timestamp without time zone, cancelledAt timestamp without time zone, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

timezone_preferences (rows: 9, indexes: 1, foreign keys: 0)

id integer not null, email character varying not null, timezone character varying not null, lastSeenAt timestamp without time zone not null, createdAt timestamp without time zone not null

users (rows: 11, indexes: 5, foreign keys: 2)

id integer not null, openId character varying not null, name text, email character varying, loginMethod character varying, passwordHash character varying, organizationId integer, phone character varying, role USER-DEFINED not null, mfaMethod character varying not null, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null, lastSignedIn timestamp without time zone not null, authUserId uuid, sessionsRevokedAtMs bigint, avatarKey character varying, avatarUpdatedAt timestamp without time zone

webhook_deliveries (rows: 0, indexes: 3, foreign keys: 1)

id integer not null, webhookRegistrationId integer not null, triggerType USER-DEFINED not null, triggerEntityRef character varying, success integer not null, statusCode integer, errorMessage text, requestedAt timestamp without time zone not null

webhook_registrations (rows: 1, indexes: 2, foreign keys: 1)

id integer not null, name character varying not null, url text not null, secret character varying, triggerType USER-DEFINED not null, enabled integer not null, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null

workflow_definitions (rows: 2, indexes: 3, foreign keys: 1)

id integer not null, name character varying not null, triggerType USER-DEFINED not null, actionType USER-DEFINED not null, actionConfig text, enabled integer not null, createdByUserId integer, createdAt timestamp without time zone not null, updatedAt timestamp without time zone not null, scheduleCadence character varying, nextRunAt timestamp without time zone

workflow_runs (rows: 1, indexes: 3, foreign keys: 1)

id integer not null, workflowDefinitionId integer not null, triggerType USER-DEFINED not null, triggerEntityRef character varying, status USER-DEFINED not null, resultMessage text, ranAt timestamp without time zone not null

Appendix D: Procedure inventory

296 typed API procedures, with the access level that guards each one.

Router	Procedure	Access	Kind
accounts	activate	public	mutation
accounts	activationDetails	public	query
admin	action	admin	mutation
admin	agents	admin	query
admin	aiScans	admin	query
admin	analytics	admin	query
admin	assignDeveloperTask	admin	mutation
admin	assignDeveloperToProject	admin	mutation
admin	assignUserOrganization	superAdmin	mutation
admin	audit	admin	query
admin	automations	admin	query
admin	billing	admin	query
admin	campaigns	admin	query
admin	clients	admin	query
admin	createDeveloperProject	admin	mutation
admin	createDeveloperTask	admin	mutation
admin	createInvoice	admin	mutation
admin	createLead	admin	mutation
admin	createMilestone	admin	mutation
admin	createOrganization	superAdmin	mutation
admin	createProject	admin	mutation
admin	createReport	admin	mutation
admin	createSupportTicket	admin	mutation
admin	createWebhookRegistration	superAdmin	mutation
admin	createWorkflowDefinition	superAdmin	mutation
admin	crm	admin	query
admin	developerAssignments	admin	query
admin	developerProjects	admin	query
admin	developers	admin	query
admin	developerTasks	admin	query
admin	documents	admin	query
admin	emailDeliveryFailures	admin	query
admin	emailDeliveryLog	admin	query
admin	endDeveloperAssignment	admin	mutation
admin	gateStatus	protected	query
admin	grantDeveloperAccess	admin	mutation
admin	listDocumentVersions	admin	query
admin	listOrganizations	admin	query
admin	liveFeed	admin	query
admin	mfaPosture	admin	query
adminOps	activatePromptVersion	superAdmin	mutation
adminOps	addPromptVersion	superAdmin	mutation
adminOps	aiAgents	admin	query
adminOps	aiExecutions	admin	query
adminOps	aiPromptVersions	admin	query
adminOps	aiScanHistory	admin	query
adminOps	aiScanReviewQueue	admin	query
adminOps	alertRules	ops	query
adminOps	archiveProject	admin	mutation
adminOps	assignAiScanReviewer	admin	mutation
adminOps	auditExport	admin	mutation
adminOps	auditSearch	admin	query
adminOps	callOutcome	admin	query
adminOps	campaignOverview	admin	query
adminOps	commentOnTask	admin	mutation
adminOps	communicationHistory	admin	query
adminOps	completeActivity	admin	mutation
adminOps	compliance	ops	query

Router	Procedure	Access	Kind
adminOps	configHistory	admin	query
adminOps	createActivity	admin	mutation
adminOps	createIncident	ops	mutation
adminOps	createOpportunity	admin	mutation
adminOps	createProposal	admin	mutation
adminOps	createQuote	admin	mutation
adminOps	createScheduledReport	admin	mutation
adminOps	createSubscription	admin	mutation
adminOps	customerTimeline	admin	query
adminOps	decideAiExecution	admin	mutation
adminOps	deployments	ops	query
adminOps	evaluateAlerts	ops	mutation
adminOps	exportDataset	admin	mutation
adminOps	financialSummary	admin	query
adminOps	followUps	admin	query
adminOps	history	admin	query
adminOps	incidents	ops	query
adminOps	invitations	admin	query
adminOps	inviteUser	admin	mutation
adminOps	markNotificationsRead	admin	mutation
adminOps	moveAiScanReport	admin	mutation
adminOps	moveOpportunity	admin	mutation
adminOps	moveProposal	admin	mutation
adminOps	moveQuote	admin	mutation
adminOps	notifications	admin	query
adminOps	opportunities	admin	query
adminOps	pendingApprovals	admin	query
adminOps	platformHealth	ops	query
adminOps	projectLifecycleHistory	admin	query
adminOps	projectLifecycles	admin	query
adminOps	proposals	admin	query
adminOps	quotes	admin	query
adminOps	recordCallOutcome	admin	mutation
adminOps	regenerateAiScanReport	admin	mutation
adminOps	requestProjectApproval	admin	mutation
adminOps	reviewTimeEntry	admin	mutation
adminOps	revokeInvitation	admin	mutation
adminOps	runAiAgentAction	admin	mutation
adminOps	scheduledReports	admin	query
adminOps	searchDocuments	admin	query
adminOps	setProjectLifecycle	admin	mutation
adminOps	setScheduledReportEnabled	admin	mutation
adminOps	setSubscriptionStatus	admin	mutation
adminOps	subscriptions	admin	query
adminOps	taskComments	admin	query
adminOps	timeEntries	admin	query
adminOps	unreadNotificationCount	admin	query
adminOps	updateAlertRule	superAdmin	mutation
adminOps	updateIncident	ops	mutation
adminOps	upsertAiAgent	superAdmin	mutation
adminPlatform	activateTemplate	superAdmin	mutation
adminPlatform	aiUsage	admin	query
adminPlatform	documentMatrix	admin	query
adminPlatform	evaluateLead	admin	mutation
adminPlatform	grantOperatorScope	superAdmin	mutation
adminPlatform	integrations	admin	query
adminPlatform	leadEvaluations	admin	query
adminPlatform	listTemplates	admin	query
adminPlatform	operatorScopes	admin	query
adminPlatform	previewTemplate	admin	query
adminPlatform	reconcilePayments	superAdmin	mutation
adminPlatform	revokeOperatorScope	superAdmin	mutation
adminPlatform	saveTemplate	superAdmin	mutation

Router	Procedure	Access	Kind
adminPlatform	setDocumentType	admin	mutation
adminPlatform	templateEvents	admin	query
adminPlatform	templatePlaceholders	admin	query
adminPlatform	testIntegration	superAdmin	mutation
adminPlatform	updateDocumentMatrix	superAdmin	mutation
admin	projects	admin	query
admin	promoteAiScanToClientReport	admin	mutation
admin	recentLoginAudit	admin	query
admin	replyToDeveloper	admin	mutation
admin	reports	admin	query
admin	retriggerAiScan	admin	mutation
admin	reviewDocument	admin	mutation
admin	security	admin	query
admin	setDocumentRetention	admin	mutation
admin	settings	admin	query
admin	setUserRole	superAdmin	mutation
admin	setWebhookRegistrationEnabled	superAdmin	mutation
admin	setWorkflowDefinitionEnabled	superAdmin	mutation
admin	summary	admin	query
admin	support	admin	query
admin	updateMilestone	admin	mutation
admin	updateOrganization	superAdmin	mutation
admin	updateProject	admin	mutation
admin	updateReport	admin	mutation
admin	updateSetting	superAdmin	mutation
admin	users	admin	query
admin	viewAs	admin	mutation
admin	webhookDeliveries	admin	query
admin	webhookRegistrations	superAdmin	query
admin	workflowDefinitions	admin	query
admin	workflowRuns	admin	query
aiScans	getQuestionnaire	public	query
aiScans	getReport	public	query
aiScans	getReportPdf	public	mutation
aiScans	loadDraft	public	query
aiScans	saveDraft	public	mutation
aiScans	startPurchase	public	mutation
aiScans	submitLead	public	mutation
aiScans	submitQuestionnaire	public	mutation
bookingAdmin	addAvailabilityWindow	admin	mutation
bookingAdmin	addCalendarBlock	admin	mutation
bookingAdmin	bookingDetail	admin	query
bookingAdmin	cancel	admin	mutation
bookingAdmin	deleteAvailabilityRule	admin	mutation
bookingAdmin	deleteAvailabilityWindow	admin	mutation
bookingAdmin	deleteCalendarBlock	admin	mutation
bookingAdmin	listAvailabilityRules	admin	query
bookingAdmin	listAvailabilityWindows	admin	query
bookingAdmin	listCalendarBlocks	admin	query
bookingAdmin	listRecent	admin	query
bookingAdmin	markNoShow	admin	mutation
bookingAdmin	remindersTick	admin	mutation
bookingAdmin	setCallType	admin	mutation
bookingAdmin	upsertAvailabilityRule	admin	mutation
bookings	cancelByToken	public	mutation
bookings	create	public	mutation
bookings	getByRef	public	query
bookings	hold	public	mutation
bookings	listRecent	admin	query
bookings	listSlots	public	query
bookings	rescheduleByToken	public	mutation
clientPortal	aiScanProgress	client	query
clientPortal	approvals	client	query

Router	Procedure	Access	Kind
clientPortal	archiveNotification	client	mutation
clientPortal	cancelStrategyCall	client	mutation
clientPortal	createTicket	client	mutation
clientPortal	dashboard	client	query
clientPortal	decideApproval	client	mutation
clientPortal	documents	client	query
clientPortal	invoices	client	query
clientPortal	markMessagesRead	client	mutation
clientPortal	markNotificationRead	client	mutation
clientPortal	messages	client	query
clientPortal	notifications	client	query
clientPortal	organization	client	query
clientPortal	projects	client	query
clientPortal	recommendationAction	client	mutation
clientPortal	recommendations	client	query
clientPortal	reports	client	query
clientPortal	requestDocumentDeletion	client	mutation
clientPortal	requestDocumentSignedUrl	client	mutation
clientPortal	requestInvoiceCheckout	client	mutation
clientPortal	requestInvoiceSignedUrl	client	mutation
clientPortal	requestReportSignedUrl	client	mutation
clientPortal	revokeSession	client	mutation
clientPortal	searchDocuments	client	query
clientPortal	security	client	query
clientPortal	sendMessage	client	mutation
clientPortal	setMfaMethod	client	mutation
clientPortal	strategyCalls	client	query
clientPortal	tickets	client	query
clientPortal	updateDisplayName	client	mutation
clientPortal	uploadDocument	client	mutation
contact	listRecent	admin	query
contact	submit	public	mutation
developer	addTaskComment	developerSelf	mutation
developer	archiveNotification	developer	mutation
developer	createSubmission	developer	mutation
developer	createSupportTicket	developer	mutation
developer	dashboard	developer	query
developer	gateStatus	protected	query
developer	getProfileForEdit	developerSelf	query
developer	getProject	developer	query
developer	listAgreements	developer	query
developer	listAuditEvents	developerSelf	query
developer	listFiles	developer	query
developer	listMessages	developer	query
developer	listNotifications	developer	query
developer	listProjects	developer	query
developer	listSubmissions	developer	query
developer	listTasks	developer	query
developer	logTime	developerSelf	mutation
developer	markMessagesRead	developer	mutation
developer	markNotificationRead	developer	mutation
developer	myTimeEntries	developerSelf	query
developer	requestAccessExtension	developer	mutation
developer	requestFileSignedUrl	developer	mutation
developer	sendMessage	developer	mutation
developer	setMfaMethodLite	developerSelf	mutation
developer	setTaskStatus	developer	mutation
developer	signAgreement	protected	mutation
developer	taskComments	developer	query
developer	updateProfile	developerSelf	mutation
engineering	listRecent	admin	query
engineering	setStatus	admin	mutation
engineering	submit	public	mutation

Router	Procedure	Access	Kind
legal	acceptAgreement	protected	mutation
legal	acknowledgeAi	public	mutation
legal	adminCounts	admin	query
legal	getCookieConsent	public	query
legal	getDocument	public	query
legal	listDocuments	public	query
legal	myAcceptances	protected	query
legal	myMissingAcceptances	protected	query
legal	recordCookieConsent	public	mutation
mfa	deleteFactor	protected	mutation
mfa	enrollSmsBegin	protected	mutation
mfa	enrollSmsVerify	protected	mutation
mfa	enrollTotpBegin	protected	mutation
mfa	enrollTotpVerify	protected	mutation
mfa	listFactors	protected	query
mfa	redeemRecoveryCode	protected	mutation
mfa	regenerateRecoveryCodes	protected	mutation
mfa	requestSmsCode	protected	mutation
mfa	setPrimaryFactor	protected	mutation
ops	acknowledgeSecurityEvent	ops	mutation
ops	emailDeliveryLog	ops	query
ops	gateStatus	protected	query
ops	securityEvents	ops	query
ops	systemHealth	ops	query
privacy	approveAction	privacyOfficer	mutation
privacy	create	privacyOfficer	mutation
privacy	export	privacyOfficer	mutation
privacy	get	privacyOfficer	query
privacy	grantOfficer	superAdmin	mutation
privacy	list	privacyOfficer	query
privacy	listOfficers	superAdmin	query
privacy	locate	privacyOfficer	mutation
privacy	prepareAction	privacyOfficer	mutation
privacy	revokeOfficer	superAdmin	mutation
privacy	setIdentityVerification	privacyOfficer	mutation
profile	get	protected	query
profile	notificationPreferences	protected	query
profile	removeAvatar	protected	mutation
profile	setNotificationPreference	protected	mutation
profile	updateDisplayName	protected	mutation
profile	uploadAvatar	protected	mutation
solutions	adminListClicks	admin	query
solutions	adminListDiscoveries	admin	query
solutions	adminListProposals	admin	query
solutions	recordClick	public	mutation
solutions	requestProposal	public	mutation
solutions	saveDiscoveryStep	public	mutation
solutions	startDiscovery	public	mutation
solutions	submitDiscovery	public	mutation

Appendix E: Notification event catalogue

84 notification events with family, priority and email delivery rule.

Id	Event	Family	Priority	Email	Deep link
DC-01	DISCOVERY_CALL_REQUESTED	discovery_calls	P3	IMMEDIATE	Authorised Discovery Call record
DC-02	DISCOVERY_CALL_SCHEDULED	discovery_calls	P3	MANDATORY	Authorised Discovery Call record
DC-03	DISCOVERY_CALL_RESCHEDULED	discovery_calls	P2 when close to original/new	IMMEDIATE	Relevant authorised resource
DC-04	DISCOVERY_CALL_CANCELLED	discovery_calls	P3	IMMEDIATE	Relevant authorised resource
DC-05	DISCOVERY_CALL_UPCOMING_24H	discovery_calls	P3	IMMEDIATE	Discovery Call with intake/
DC-06	DISCOVERY_CALL_UPCOMING_1H	discovery_calls	otherwise P2	IMMEDIATE	prospect context
DC-07	DISCOVERY_CALL_RETRY_DUE	discovery_calls	P2/P3	IMMEDIATE	Relevant authorised resource
DC-08	DISCOVERY_CALL_FOLLOW_UP_DUE	discovery_calls	P2/P3 based on urgency	IMMEDIATE for P2; OPTIONAL for	Relevant authorised resource Discovery Call/prospect record
DC-09	DISCOVERY_CALL_INFORMATION_UPDATED	discovery_calls	P3	OPTIONAL	Relevant authorised resource
DC-10	DISCOVERY_CALL_ACTION_REQUIRED	discovery_calls	P2/P3	IMMEDIATE	Relevant authorised resource
AS-01	AI_SCAN_CREATED	ai_scans	P3	OPTIONAL	Relevant authorised resource
AS-02	AI_SCAN_INFORMATION_REQUIRED	ai_scans	P2	IMMEDIATE	Client Scan input/request view
AS-03	AI_SCAN_SUBMITTED	ai_scans	P3	Client	Relevant authorised resource
AS-04	AI_SCAN_ANALYSIS_EXCEPTION	ai_scans	P1/P2	confirmation IMMEDIATE/	Relevant authorised resource
AS-05	AI_SCAN_READY_FOR_REVIEW	ai_scans	P2	IMMEDIATE	Internal Scan Review Workspace
AS-06	AI_SCAN_REVIEW_ASSIGNED	ai_scans	P2	IMMEDIATE	Assigned Scan Review
AS-07	AI_SCAN_REVIEW_REMINDER	ai_scans	P2	IMMEDIATE	Relevant authorised resource
AS-08	AI_SCAN_CHANGES_REQUIRED	ai_scans	P2	IMMEDIATE	Relevant authorised resource
AS-09	AI_SCAN_REVIEW_APPROVED	ai_scans	P2	IMMEDIATE	Approved Scan / Publish
AS-10	AI_SCAN_PUBLICATION_FAILED	ai_scans	P1/P2	IMMEDIATE	Workspace Relevant authorised resource
AS-11	AI_SCAN_PUBLISHED	ai_scans	P3	IMMEDIATE to	Correct published Client Portal
AS-12	AI_SCAN_DELIVERY_AT_RISK	ai_scans	on delivery P2	Client	report Relevant authorised resource
AS-13	AI_SCAN_DELIVERY_OVERDUE	ai_scans	impact P1/P2	IMMEDIATE	Relevant authorised resource
CA-01	CLIENT_ACCOUNT_CREATED	clients_accounts	P3	IMMEDIATE OPTIONAL	Relevant authorised resource
CA-02	CLIENT_INFORMATION_REQUIRED	clients_accounts	P2/P3	IMMEDIATE to	Relevant authorised resource
CA-03	CLIENT_INFORMATION_SUBMITTED	clients_accounts	P3	Client/delivery communication	Relevant authorised resource
CA-04	CLIENT_MATERIAL_INFORMATION_UPDATED	clients_accounts	P3	OPTIONAL	Relevant authorised resource
CA-05	CLIENT_ACCOUNT_ACTION_REQUIRED	clients_accounts	P2/P3	IMMEDIATE	Relevant authorised resource
CA-06	CLIENT_ACCOUNT_SECURITY_ACTION_REQUIRED	clients_accounts	P1/P2	IMMEDIATE	Relevant authorised resource
PD-01	PROJECT_ASSIGNED	projects_delivery	P3	IMMEDIATE	Relevant authorised resource
PD-02	PROJECT_REASSIGNED	projects_delivery	P3	IMMEDIATE	Relevant authorised resource
PD-03	PROJECT_MILESTONE_UPDATED	projects_delivery	P3	OPTIONAL	Relevant authorised resource
PD-04	PROJECT_DEADLINE_7D	projects_delivery	P3	IMMEDIATE	Relevant authorised resource
PD-05	PROJECT_DEADLINE_3D	projects_delivery	P2	IMMEDIATE	Relevant authorised resource
PD-06	PROJECT_DEADLINE_24H	projects_delivery	P2	IMMEDIATE	Relevant authorised resource
PD-07	PROJECT_DEADLINE_MISSED	projects_delivery	P2	IMMEDIATE	Relevant authorised resource
PD-08	PROJECT_REVIEW_REQUESTED	projects_delivery	P2/P3	IMMEDIATE	Relevant authorised resource
PD-09	PROJECT_REVIEWER_ASSIGNED	projects_delivery	P3 depending on deadline	IMMEDIATE	Relevant authorised resource
PD-10	PROJECT_IMPLEMENTATION_ACTION_REQUIRED	projects_delivery	P2/P3	IMMEDIATE	Relevant authorised resource
PD-11	PROJECT_REVIEW_ACTION_REQUIRED	projects_delivery	P2	IMMEDIATE where deadline/action	Relevant authorised resource
PD-12	PROJECT_BLOCKER_CREATED	projects_delivery	P2; P1 only	IMMEDIATE	Relevant authorised resource
PD-13	PROJECT_BLOCKER_RESOLVED	projects_delivery	if business-critical	OPTIONAL	Relevant authorised resource
PD-14	PROJECT_DEPENDENCY_ACTION_REQUIRED	projects_delivery	P2/P3	IMMEDIATE	Relevant authorised resource
PD-15	PROJECT_CLIENT_INFORMATION_REQUIRED	projects_delivery	P2/P3	IMMEDIATE to	Relevant authorised resource
PD-16	PROJECT_CLIENT_INFORMATION_RECEIVED	projects_delivery	P3	OPTIONAL;	Relevant authorised resource
PD-17	PROJECT_DELIVERY_STATE_CHANGED	projects_delivery	P3 or P2	IMMEDIATE	Relevant authorised resource
PB-01	INVOICE_CREATED_ACTION_REQUIRED	payments_billing	P3	OPTIONAL	Relevant authorised resource
PB-02	PAYMENT_DUE_7D	payments_billing	P3	IMMEDIATE	Relevant authorised resource
PB-03	PAYMENT_DUE_1D	payments_billing	P2/P3	IMMEDIATE	Relevant authorised resource
PB-04	PAYMENT_DUE_TODAY	payments_billing	P2	IMMEDIATE	Relevant authorised resource
PB-05	PAYMENT_OVERDUE	payments_billing	P2	IMMEDIATE	Relevant authorised resource
PB-06	PAYMENT_FAILED	payments_billing	P2	IMMEDIATE	Relevant authorised resource
PB-07	PAYMENT_COMPLETED	payments_billing	P4/P3	Client receipt/	Relevant authorised resource
PB-08	BILLING_ACTION_REQUIRED	payments_billing	P2/P3	IMMEDIATE	Relevant authorised resource
AO-01	AI_OPERATION_FAILED	ai_operations	P2/P1	IMMEDIATE	Relevant authorised resource
AO-02	AI_HUMAN_INTERVENTION_REQUIRED	ai_operations	depending on impact P2	OPTIONAL	Relevant authorised resource
AO-03	AI_PROCESSING_EXCEPTION	ai_operations	P2	IMMEDIATE	Relevant authorised resource
AO-04	AI_OPERATION_THRESHOLD_EXCEEDED	ai_operations	P2/P3 depending		

on threshold

IMMEDIATE
where action

required

Relevant authorised resource

Id	Event	Family	Priority	Email	Deep link
AO-05	AI_SERVICE_UNAVAILABLE	ai_operations	P1/P2	IMMEDIATE	Relevant authorised resource
AO-06	AI_OPERATION_RECOVERED	ai_operations	P3	OPTIONAL	Relevant authorised resource
PI-01	INTEGRATION_DISCONNECTED	platform_integrations	P2	IMMEDIATE	Relevant authorised resource
PI-02	INTEGRATION_AUTH_EXPIRED	platform_integrations	P2	IMMEDIATE	Relevant authorised resource
PI-03	INTEGRATION_FAILURE	platform_integrations	P2/P1	IMMEDIATE	Relevant authorised resource
PI-04	EXTERNAL_SERVICE_UNAVAILABLE	platform_integrations	Impact-	IMMEDIATE	Relevant authorised resource
PI-05	PLATFORM_COMPONENT_ACTION_REQUIRED	platform_integrations	P2	IMMEDIATE	Relevant authorised resource
PI-06	PLATFORM_CONFIGURATION_ACTION_REQUIRE	platform_integrations	P2/P3	IMMEDIATE	Relevant authorised resource
PI-07	PLATFORM_INCIDENT_CRITICAL	platform_integrations	P1	IMMEDIATE	Relevant authorised resource
PI-08	PLATFORM_SERVICE_RECOVERED	platform_integrations	P3	OPTIONAL /	Relevant authorised resource
SA-01	SECURITY_ALERT_CRITICAL	security_access	P1	IMMEDIATE /	Authorised Security Center
SA-02	SECURITY_ACTION_REQUIRED	security_access	P2	IMMEDIATE	Relevant authorised resource
SA-03	PRIVILEGED_ACCESS_GRANTED	security_access	P2/P3	IMMEDIATE	Relevant authorised resource
SA-04	PRIVILEGED_ACCESS_REVOKED	security_access	P2/P3	Context	Relevant authorised resource
SA-05	SIGNIFICANT_PERMISSION_CHANGE	security_access	P2/P3	IMMEDIATE	Relevant authorised resource
SA-06	SECURITY_CENTER_ACTION_REQUIRED	security_access	P2	IMMEDIATE	Relevant authorised resource
SA-07	SECURITY_CONFIGURATION_ACTION_REQUIRED	security_access	P2	IMMEDIATE	Relevant authorised resource
SA-08	SUSPICIOUS_ACCESS_EVENT	security_access	P1/P2	IMMEDIATE	Relevant authorised resource
SA-09	ACCOUNT_SECURITY_ACTION_REQUIRED	security_access	P1/P2	IMMEDIATE	Relevant authorised resource
SA-10	SECURITY_INCIDENT_RESOLVED	security_access	P3	IMMEDIATE	Relevant authorised resource
GS-01	GOVERNANCE_ACTION_REQUIRED	governance_system	P2	IMMEDIATE	Relevant authorised resource
GS-02	PRIVILEGED_ACCESS_OVERSIGHT_REQUIRED	governance_system	P2	IMMEDIATE	Relevant authorised resource
GS-03	ADMINISTRATIVE_CONFIGURATION_OVERSIGHT	governance_system	P2/P3	Context	Relevant authorised resource
GS-04	SYSTEM_GOVERNANCE_ISSUE	governance_system	P2/P1	IMMEDIATE	Relevant authorised resource
GS-05	AUDIT_INTEGRITY_ACTION_REQUIRED	governance_system	P1/P2	IMMEDIATE	Relevant authorised resource
GS-06	GOVERNANCE_INCIDENT_RESOLVED	governance_system	P3	Context dependent	Relevant authorised resource

Appendix F: Database migrations

37 migration files, applied to the live database.

File	Stmts	Summary
0000_slim_santa_claus.sql	100	> statement-breakpoint > statement-breakpoint > statement-breakpoint > statement-breakpoint
0001_futuristic_nekra.sql	121	
0002_updated_at_triggers.sql	19	Milestone 1 (RM-43/44): Postgres replacement for MySQL's `.onUpdateNow()`. Drizzle's
0003_add_auth_user_id.sql	2	Postgres dialect has no equivalent to MySQL's ON UPDATE CURRENT_TIMESTAMP column modifier, so it was dropped from every column definition in drizzle/schema.ts
0004_rls_policies.sql	214	Milestone 1 (RM-48): Row-Level Security policies. ARCHITECTURE NOTE - why this matters even though the Express/tRPC backend already does its own tenant scoping in
0005_auth_users_fk.sql	1	Milestone 1 (RM-50): link public.users.authUserId to Supabase's own auth.users(id). application code (clientProcedure/
0006_super_admin_role.sql	3	Milestone 1 (RM-57, resolved): add the "super_admin" role tier. Client decision (recorded, not invented): super_admin is a new 5th enum value, a strict superset of admin (every admin capability remains
0007_storage_buckets.sql	9	Milestone 2 §2.1: Storage Migration - bucket architecture + storage-layer RLS. Replaces
0008_email_delivery_log.sql	10	Milestone 2 §2.3: Email delivery tracking (delivery log + Resend webhook handling), so email failures are visible instead of silently disappearing. See drizzle/schema.ts's
0009_super_admin_org_management.sql	2	Milestone 2 §2.5 - Organization Management is a super_admin-exclusive capability per email_delivery_log table comment for the full column rationale
0010_technical_operator_role.sql	2	Milestone 2 §2.5: add the "technical_operator" role tier. Unlike super_admin (0006_super_admin_role.sql: a strict superset of admin), technical_operator is a lateral collaboration > statement-breakpoint Milestone 2 §2.5: platform configuration narrower tier: infrastructure
0011_platform_settings.sql	7	
0012_document_lifecycle.sql	10	
0013_workflow_engine.sql	18	> statement-breakpoint > statement-breakpoint > statement-breakpoint Milestone 2 §2.6:
0014_webhook_registry.sql	15	> statement-breakpoint > statement-breakpoint > statement-breakpoint Milestone 2 §2.6: webhook registry RLS, same split as 0013's workflow
0015_notification_infrastructure.sql	12	Milestone 2 §2.7: notification infrastructure schema extension. client_notifications/
0016_session_revocation_and_rate_limit.sql	1	Milestone 3 §3.3 - API hardening and session security. RM-88: shared-state rate limiting.
0017_missing_updated_at_triggers.sql	6	The Milestone 1 limiter (server/_core/rateLimiter.ts) kept its sliding Milestone 3 §3.4 (RM-108) - restore the updatedAt trigger on three tables that were
0018_users_email_index.sql	1	Milestone 3 §3.5 (RM-111) - index users.email. Found by the RM-111 index-usage suite (server/queryPerformance.test.ts): with `enable_seqscan = off`, the planner still produced
0019_booking_slots_unique.sql	2	Milestone 3 §3.5 (RM-113) - enforce one row per bookable slot. CRITICAL: server/db/ a Seq Scan for
0020_user_avatars.sql	8	Profile photos for every role. The client asked for profile completion including a profile photo across Client, Developer, Technical Operator, Admin and Super Admin. There was
0021_privacy_requests.sql	10	Data Subject Rights administration. Implements the record the client specified: date
0022_booking_call_type.sql	4	Discovery Call spec §11 (Call Type - PHONE / VIDEO). PHONE is the authoritative default and the only type the customer-facing flow ever produces. An authorised IO SKY
0023_srs_completion.sql	36	SRS completion: the tables Master SRS v1.1 requires that did not exist. Covers time user can later switch a specific
0024_srs_completion_rls.sql	11	Row Level Security for the tables added in 0023, following 0004's conventions. Supabase exposes every public table to the publishable key over PostgREST, so a table without RLS is readable by anyone who has loaded the site. 0023
0025_ai_scan_report_lifecycle.sql	21	AI Scan report lifecycle (SRS 9.6, BR-009, BR-016). Every report has exactly one of nine
0026_outcomes_comments_drafts.sql	13	Discovery Call outcomes (SRS 14.7), developer task comments and clarification requests (SRS 11.7), and resumable AI Scan questionnaires (SRS 9.7). Idempotent. Every table
0027_notification_events.sql	9	Notification emission log (SRS 17, Functional Specification section 35). Every catalogue gets RLS in this same file, following 0004 and 0024. > statement-breakpoint
0028_workflow_triggers.sql	8	More workflow triggers and scheduled workflows (SRS 23.9, 23.10). New event triggers join the existing five, and a `schedule` trigger runs a definition on a cadence. ALTER
0029_deployments.sql	8	Release tracking (SRS 25.12). Each process start records which build is running, so the TYPE ... ADD VALUE is idempotent with IF NOT
0030_account_invitations.sql	10	Account invitation and activation (SRS 8.7). Registration is invitation only (BR-004). An invitation holds the email, role and organization, and the account does not exist until the invitee completes
0031_privacy_tables_rls.sql	6	Row Level Security for the Data Subject Rights tables (0021). 0021 created these without
0032_payments_routing_templates_matrix.sql	12	Stripe payments, AI usage, notification templates, document matrix, operator scopes.
0033_governance_followups.sql	9	Every new table has row level security enabled and forced with no policy: the backend privileged connection is the only reader, as for the privacy tables (0031). > statement-b Follow ups to 0032, found by the database constraint tests. updatedAt trigger on
0034_project_lifecycle.sql	9	Project lifecycle (SRS 15.5) with an append only stage history. > statement-breakpoint > statement-breakpoint > statement-breakpoint
0035_project_triggers.sql	2	Stage-change notification triggers (SRS 15.16): Fired when a project changes stage and when it
0036_document_type.sql	2	Document matrix enforcement (OPD-003, SRS 18.19 to 18.21): each document may be tagged with its type. > statement-breakpoint

Appendix G: Live database verification

Results of real statements and queries run against the live database for this report.

APPEND ONLY AUDIT TABLES

Statement tried	Result
INSERT a row into login_audit	ALLOWED (rolled back, nothing kept)
UPDATE a row in login_audit	REFUSED: audit table login_audit is append only: UPDATE refused
DELETE a row from login_audit	REFUSED: audit table login_audit is append only: DELETE refused
UPDATE a row in config_history	REFUSED: audit table config_history is append only: UPDATE refused
DELETE a row from ai_executions	REFUSED: audit table ai_executions is append only: DELETE refused
UPDATE a row in notification_events	REFUSED: audit table notification_events is append only: UPDATE refused
UPDATE a row in ai_scan_status_events	REFUSED: audit table ai_scan_status_events is append only: UPDATE refused
DELETE the parent of an audited child (foreign key cascade)	ALLOWED: the child row was removed by the cascade
DELETE the audited child directly	REFUSED: audit table ev_child is append only: DELETE refused

ROW LEVEL SECURITY

93 of 93 public tables have row level security enabled, 92 are forced, with 143 policies.

TABLES WITH THE APPEND ONLY TRIGGER

ai_executions, ai_scan_status_events, ai_usage, booking_audit, config_history, deployments, developer_audit, login_audit, notification_events, payment_events, privacy_request_events, project_lifecycle_events

RECORD COUNTS

leads: 11 bookings: 9 loginAudit: 1143 notificationEvents: 19 incidents: 5

Appendix H: Screenshot index

All 160 screenshots captured from the live application, with the role used and the page.

Scene	Role	Page	Title
pub-home	public	/	Home
pub-intelligence	public	/intelligence	Intelligence
pub-solutions	public	/solutions	Solutions
pub-ai-scan	public	/ai-scan	AI Scan
pub-custom-software	public	/custom-software	Custom Software
pub-about	public	/about	About
pub-contact	public	/contact	Contact
pub-book	public	/book-strategy	Book a Discovery Call
pub-enterprise	public	/enterprise	Enterprise
pub-infrastructure	public	/infrastructure	Infrastructure
pub-security	public	/security	Security
pub-login	public	/login	Sign in
pub-legal-privacy	public	/privacy	Privacy policy
pub-legal-terms	public	/terms	Terms of service
pub-legal-cookies	public	/cookies	Cookie policy
pub-legal-ai	public	/ai-disclaimer	AI disclaimer
pub-legal-dpa	public	/dpa	Data processing agreement
pub-legal-trust	public	/trust	Trust centre
val-contact-empty	public	/contact	Contact form refuses an empty submission
val-contact-email	public	/contact	Contact form rejects an invalid email address
val-login-disabled	public	/login	Sign in stays disabled until the form is valid
auth-wrong-password	public	/login	A wrong password gives one generic message
auth-no-signup	public	/login	The sign in page has no public registration
auth-forgot	public	/login	Password recovery entry point
auth-reset-invalid	public	/reset-password	A reset link that is invalid or expired is refused
auth-anon-admin	public	/login	Anonymous visitor sent to sign in (admin)
auth-anon-client	public	/login	Anonymous visitor sent to sign in (client portal)
auth-anon-dev	public	/login	Anonymous visitor sent to sign in (developer workspace)
act-invalid	public	/activate	An invalid activation link gives one generic message
act-form	public	/activate	Activation page for a valid invitation
act-weak	public	/activate	A weak password is refused with a reason
act-success	client	/client-portal	Activation signs the new user in and routes them to the client portal
cl-dashboard	client	/client-portal	Client portal dashboard after sign in
cl-reports	client	/client-portal/reports	Published reports
cl-ai-scans	client	/client-portal/ai-scans	AI Scan history with the review progress card
cl-recommendations	client	/client-portal/recommendations	Recommendations
cl-strategy-calls	client	/client-portal/strategy-calls	Discovery Calls
cl-projects	client	/client-portal/projects	Project progress and milestones
cl-billing	client	/client-portal/billing	Invoices and billing
cl-documents	client	/client-portal/documents	Document vault
cl-documents-search	client	/client-portal/documents	Document search, scoped to this organization
cl-documents-search-none	client	/client-portal/documents	A search with no match says so
cl-messages	client	/client-portal/messages	Secure messaging
cl-support	client	/client-portal/support	Support tickets
cl-security	client	/client-portal/security	Security centre
cl-account	client	/client-portal/account	Account settings
cl-account-prefs	client	/client-portal/account	Notification preferences, security locked on
cl-bell	client	/client-portal	Notification bell with recent events
cl-approvals-pending	client	/client-portal/approvals	A project phase waiting for the customer's approval
cl-approvals-reject-needs-note	client	/client-portal/approvals	Requesting changes requires saying what to change
cl-approvals-decided	client	/client-portal/approvals	After the customer approves, the decision is recorded
cl-forbidden-admin	client	/client-portal	A client who opens the admin address is sent to their own portal
cl-forbidden-dev	client	/client-portal	A client cannot open the developer workspace
dv-overview	developer	/developer-workspace	Developer workspace after sign in
dv-projects	developer	/developer-workspace/projects	Only the projects assigned to this developer
dv-tasks	developer	/developer-workspace/tasks	Personal task list
dv-task-thread	developer	/developer-workspace/tasks	Progress note, clarification request and the answer on a task
dv-task-ask	developer	/developer-workspace/tasks	Asking for clarification from the task thread

Scene	Role	Page	Title
dv-time	developer	/developer-workspace/time	Time registration with review status
dv-time-form	developer	/developer-workspace/time	Logging time against an assigned project
dv-time-future	developer	/developer-workspace/time	A future date cannot be registered
dv-messages	developer	/developer-workspace/messages	Messages from the engineering desk
dv-files	developer	/developer-workspace/files	Project files
dv-submissions	developer	/developer-workspace/submissions	Deliverable submissions
dv-access-scope	developer	/developer-workspace/access-scope	Access scope and expiry
dv-agreements	developer	/developer-workspace/agreements	Signed agreements
dv-profile	developer	/developer-workspace/profile	Profile and notification preferences
dv-profile-prefs	developer	/developer-workspace/profile	Notification preferences with security locked on
dv-security	developer	/developer-workspace/security	Security centre
dv-support	developer	/developer-workspace/support	Support
dv-bell	developer	/developer-workspace	Notification bell with assignment and task events
dv-forbidden-admin	developer	/developer-workspace	A developer who opens the admin address is refused
dv-forbidden-client	developer	/client-portal	A developer cannot open the client portal
ad-landing	admin	/admin/bookings	Admin portal after sign in and the MFA challenge
ad-overview	admin	/admin	Executive overview, top
ad-overview-2	admin	/admin	Executive overview, compliance, alerts and automation
ad-overview-3	admin	/admin	Executive overview, pipeline, access and system health
ad-bell	admin	/admin	Admin notification bell
ad-crm	admin	/admin/crm	CRM and leads
ad-clients	admin	/admin/clients	Clients
ad-ai-scans	admin	/admin/ai-scans	AI Scans
ad-reports	admin	/admin/reports	Reports
ad-projects	admin	/admin/projects	Projects and ecosystems
ad-strategy-calls	admin	/admin/strategy-calls	Discovery Calls
ad-availability	admin	/admin/booking-availability	Booking availability
ad-billing	admin	/admin/billing	Billing and payments
ad-documents	admin	/admin/documents	Documents and storage
ad-developers	admin	/admin/developers	Developer management
ad-security	admin	/admin/security	Security monitoring
ad-agents	admin	/admin/agents	AI agent registry
ad-automations	admin	/admin/automations	Notifications and automations (workflows and webhooks)
ad-analytics	admin	/admin/analytics	Analytics and insights
ad-users	admin	/admin/users	Users and permissions
ad-audit	admin	/admin/audit	Audit logs
ad-settings	admin	/admin/settings	System settings
ad-support	admin	/admin/support	Support desk
ad-my-security	admin	/admin/my-security	My security (MFA)
ad-delivery-assign	admin	/admin/delivery	Delivery: projects and developer assignment
ad-delivery-assign-form	admin	/admin/delivery	Delivery: assignment and project creation forms
ad-delivery-tasks	admin	/admin/delivery	Delivery: tasks and assignees
ad-delivery-time	admin	/admin/delivery	Delivery: time entries awaiting review
ad-delivery-approvals	admin	/admin/delivery	Delivery: approvals waiting on customers
ad-delivery-messages	admin	/admin/delivery	Delivery: message a developer
ad-sales-pipeline	admin	/admin/sales	Sales: opportunities and the pipeline
ad-sales-proposals	admin	/admin/sales	Sales: proposals
ad-sales-activities	admin	/admin/sales	Sales: activities, follow ups and call outcomes
ad-sales-quotes	admin	/admin/sales	Sales: quotations
ad-sales-subs	admin	/admin/sales	Sales: subscriptions
ad-sales-finance	admin	/admin/sales	Sales: financial summary, twelve month history and exports
ad-sales-timeline	admin	/admin/sales	Sales: customer timeline for the demo organization
ad-gov-scanreview	admin	/admin/governance	Governance: AI Scan review queue
ad-gov-scanreview-history	admin	/admin/governance	Governance: status history of a report (append only)
ad-gov-scanreview-all	admin	/admin/governance	Governance: reports in every status
ad-gov-incidents	admin	/admin/governance	Governance: incident register
ad-gov-alerts	admin	/admin/governance	Governance: alert rules
ad-gov-ai	admin	/admin/governance	Governance: AI agents, prompts and execution history
ad-gov-config	admin	/admin/governance	Governance: configuration change and history
ad-gov-reports	admin	/admin/governance	Governance: scheduled reports
ad-gov-audit	admin	/admin/governance	Governance: audit log search and export
ad-gov-health	admin	/admin/governance	Governance: platform health, capacity and release history
ad-gov-comms	admin	/admin/governance	Governance: communication history

Scene	Role	Page	Title
ad-gov-compliance	admin	/admin/governance	Governance: compliance checks
ad-gov-invites	admin	/admin/governance	Governance: invitations
ad-gov-ai-2	admin	/admin/governance	Governance: agent registration and prompt version forms
ad-gov-audit-blocked	admin	/admin/governance	Governance: audit log filtered to denied access attempts
ad-gov-audit-mfa	admin	/admin/governance	Governance: audit log filtered to MFA challenges
ad-gov-audit-failed	admin	/admin/governance	Governance: audit log filtered to failed sign ins
ad-gov-config-rejected	admin	/admin/governance	Governance: a refused configuration change is recorded
scan-q-start	public	/ai-scan/start	AI Scan questionnaire, first question
scan-q-save	public	/ai-scan/start	Save and continue later gives a link that works for 14 days
scan-q-resumed	public	/ai-scan/start	Opening the link in a fresh browser restores the saved progress
scan-result-review	public	/ai-scan/result/demo1d353fa305fca81a	Generated report held back: awaiting expert review
scan-result-revision	public	/ai-scan/result/demo1181b9c8000000000000000000000000	Report sent back for revision stays hidden
scan-result-published	public	/ai-scan/result/demo8571de655585c38	Published report visible to the customer
scan-result-published-2	public	/ai-scan/result/demo1341f7160ab5a1a	Published report, dimensions and opportunities
scan-result-published-3	public	/ai-scan/result/demo1181ba6ab0000000000000000000000	Published report, roadmap and disclaimers
ad-maint-form	admin	/admin/governance	Setting maintenance mode through the validated settings form
ad-maint-public	public	/about	A visitor sees the maintenance page while it is on
ad-maint-admin-reachable	admin	/admin/governance	The admin portal stays reachable during maintenance
ad-maint-off	public	/about	After switching it off, the site is back
cl-account-prefs-off	client	/client-portal/account	Opting out of a category for in app delivery
ad-plat-templates	admin	/admin/governance	Governance: notification templates, versioned per event, channel and language
ad-plat-matrix	admin	/admin/governance	Governance: document matrix with the eleven document types
ad-plat-scopes	admin	/admin/governance	Governance: Technical Operator scopes with expiry and revocation
ad-plat-aiusage	admin	/admin/governance	Governance: AI model routing, usage and lead evaluation
ad-plat-integrations	admin	/admin/governance	Governance: connected providers and their configured state
ad-plat-integrations-test	admin	/admin/governance	Governance: a Super Admin connection test against Stripe
ad-delivery-lifecycle	admin	/admin/delivery	Delivery: customer project stages from Created to Archived
cl-billing-paid	client	/client-portal/billing	Invoices after a Stripe payment: one is paid, the others are open
pub-stripe-checkout	public	checkout.stripe.com (hosted page)	The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT
pub-home-mobile	public	/	Home at 390 px wide (mobile)
pub-solutions-mobile	public	/solutions	Solutions at 390 px wide (mobile)
pub-aiscan-mobile	public	/ai-scan	AI Scan at 390 px wide (mobile)
pub-menu-mobile	public	/	Navigation menu open at 390 px wide (mobile)
pub-home-tablet	public	/	Home at 768 px wide (tablet)
pub-solutions-tablet	public	/solutions	Solutions at 768 px wide (tablet)
pub-aiscan-tablet	public	/ai-scan	AI Scan at 768 px wide (tablet)
pub-menu-tablet	public	/	Navigation menu open at 768 px wide (tablet)
ad-campaigns	admin	/admin/campaigns	Campaign attribution from real lead data
ad-overview-campaigns	admin	/admin	Executive overview with the live campaign attribution panel

Appendix I: Screenshot contact sheets



pub-home: Home



pub-intelligence: Intelligence



pub-solutions: Solutions



pub-ai-scan: AI Scan

pub-custom-software: Custom Software



pub-about: About

Appendix I: Screenshot contact sheets



pub-contact: Contact



pub-book: Book a Discovery Call



pub-enterprise: Enterprise



pub-infrastructure: Infrastructure



pub-security: Security



pub-login: Sign in

Appendix I: Screenshot contact sheets



pub-legal-privacy: Privacy policy



pub-legal-terms: Terms of service



pub-legal-cookies: Cookie policy



pub-legal-ai: AI disclaimer



pub-legal-dpa: Data processing agreement



pub-legal-trust: Trust centre

Appendix I: Screenshot contact sheets



val-contact-empty: Contact form refuses an empty submission



val-contact-email: Contact form rejects an invalid email address



val-login-disabled: Sign in stays disabled until the form is valid



auth-wrong-password: A wrong password gives one generic message





auth-forgot: Password recovery entry point

Appendix I: Screenshot contact sheets



auth-reset-invalid: A reset link that is invalid or expired is refused



auth-anon-admin: Anonymous visitor sent to sign in (admin)



auth-anon-client: Anonymous visitor sent to sign in (client portal)



auth-anon-dev: Anonymous visitor sent to sign in (developer workspace)



act-invalid: An invalid activation link gives one generic message



act-form: Activation page for a valid invitation

Appendix I: Screenshot contact sheets



act-weak: A weak password is refused with a reason



act-success: Activation signs the new user in and routes them to the client portal



cl-dashboard: Client portal dashboard after sign in



cl-reports: Published reports



cl-ai-scans: AI Scan history with the review progress card



cl-recommendations: Recommendations

Appendix I: Screenshot contact sheets



cl-strategy-calls: Discovery Calls



cl-projects: Project progress and milestones



cl-billing: Invoices and billing



cl-documents: Document vault



cl-documents-search: Document search, scoped to this organization



cl-documents-search-none: A search with no match says so

Appendix I: Screenshot contact sheets



cl-messages: Secure messaging



cl-support: Support tickets



cl-security: Security centre



cl-account: Account settings



cl-account-prefs: Notification preferences, security locked on



cl-bell: Notification bell with recent events

Appendix I: Screenshot contact sheets



cl-approvals-pending: A project phase waiting for the customer's approval



cl-approvals-reject-needs-note: Requesting changes requires saying what to change



cl-approvals-decided: After the customer approves, the decision is recorded



cl-forbidden-admin: A client who opens the admin address is sent to their own portal



cl-forbidden-dev: A client cannot open the developer workspace



dv-overview: Developer workspace after sign in

Appendix I: Screenshot contact sheets



dv-projects: Only the projects assigned to this developer



dv-tasks: Personal task list



dv-task-thread: Progress note, clarification request and the answer on a task



dv-task-ask: Asking for clarification from the task thread



dv-time: Time registration with review status



dv-time-form: Logging time against an assigned project

Appendix I: Screenshot contact sheets



dv-time-future: A future date cannot be registered



dv-messages: Messages from the engineering desk



dv-files: Project files



dv-submissions: Deliverable submissions



dv-access-scope: Access scope and expiry



dv-agreements: Signed agreements

Appendix I: Screenshot contact sheets



dv-profile: Profile and notification preferences



dv-profile-prefs: Notification preferences with security locked on



dv-security: Security centre



dv-support: Support



dv-bell: Notification bell with assignment and task events



dv-forbidden-admin: A developer who opens the admin address is refused

Appendix I: Screenshot contact sheets



dv-forbidden-client: A developer cannot open the client portal



ad-landing: Admin portal after sign in and the MFA challenge

ad-overview: Executive overview, top



ad-overview-2: Executive overview, compliance, alerts and automation

ad-overview-3: Executive overview, pipeline, access and system health

ad-bell: Admin notification bell

Appendix I: Screenshot contact sheets



ad-crm: CRM and leads



ad-clients: Clients



ad-ai-scans: AI Scans



ad-reports: Reports



ad-projects: Projects and ecosystems



ad-strategy-calls: Discovery Calls

Appendix I: Screenshot contact sheets



ad-availability: Booking availability



ad-billing: Billing and payments



ad-documents: Documents and storage



ad-developers: Developer management



ad-security: Security monitoring



ad-agents: AI agent registry

Appendix I: Screenshot contact sheets



ad-automations: Notifications and automations (workflows and webhooks)



ad-analytics: Analytics and insights



ad-users: Users and permissions



ad-audit: Audit logs



ad-settings: System settings



ad-support: Support desk

Appendix I: Screenshot contact sheets



ad-my-security: My security (MFA)



ad-delivery-assign: Delivery: projects and developer assignment



ad-delivery-assign-form: Delivery: assignment and project creation forms



ad-delivery-tasks: Delivery: tasks and assignees



ad-delivery-time: Delivery: time entries awaiting review



ad-delivery-approvals: Delivery: approvals waiting on customers

Appendix I: Screenshot contact sheets



ad-delivery-messages: Delivery: message a developer



ad-sales-pipeline: Sales: opportunities and the pipeline



ad-sales-proposals: Sales: proposals



ad-sales-activities: Sales: activities, follow ups and call outcomes



ad-sales-quotes: Sales: quotations



ad-sales-subs: Sales: subscriptions

Appendix I: Screenshot contact sheets



ad-sales-finance: Sales: financial summary, twelve month history and exports



ad-sales-timeline: Sales: customer timeline for the demo organization



ad-gov-scanreview: Governance: AI Scan review queue



ad-gov-scanreview-history: Governance: status history of a report (append only)



ad-gov-scanreview-all: Governance: reports in every status



ad-gov-incidents: Governance: incident register

Appendix I: Screenshot contact sheets



ad-gov-alerts: Governance: alert rules



ad-gov-ai: Governance: AI agents, prompts and execution history



ad-gov-config: Governance: configuration change and history



ad-gov-reports: Governance: scheduled reports



ad-gov-audit: Governance: audit log search and export



ad-gov-health: Governance: platform health, capacity and release history

Appendix I: Screenshot contact sheets



ad-gov-comms: Governance: communication history



ad-gov-compliance: Governance: compliance checks



ad-gov-invites: Governance: invitations



ad-gov-ai-2: Governance: agent registration and prompt version forms



ad-gov-audit-blocked: Governance: audit log filtered to denied access attempts



ad-gov-audit-mfa: Governance: audit log filtered to MFA challenges

Appendix I: Screenshot contact sheets



ad-gov-audit-failed: Governance: audit log filtered to failed sign ins



ad-gov-config-rejected: Governance: a refused configuration change is recorded



scan-q-start: AI Scan questionnaire, first question



scan-q-save: Save and continue later gives a link that works for 14 days



scan-q-resumed: Opening the link in a fresh browser restores the saved progress



scan-result-review: Generated report held back: awaiting expert review

Appendix I: Screenshot contact sheets



scan-result-revision: Report sent back for revision stays hidden



scan-result-published: Published report visible to the customer



scan-result-published-2: Published report, dimensions and opportunities



scan-result-published-3: Published report, roadmap and disclaimers



ad-maint-form: Setting maintenance mode through the validated settings form



ad-maint-public: A visitor sees the maintenance page while it is on

Appendix I: Screenshot contact sheets



ad-maint-admin-reachable: The admin portal stays reachable during maintenance



ad-maint-off: After switching it off, the site is back



cl-account-prefs-off: Opting out of a category for in app delivery



ad-plat-templates: Governance: notification templates, versioned per event, channel and language



ad-plat-matrix: Governance: document matrix with the eleven document types



ad-plat-scopes: Governance: Technical Operator scopes with expiry and revocation

Appendix I: Screenshot contact sheets



ad-plat-aiusage: Governance: AI model routing, usage and lead evaluation



ad-plat-integrations: Governance: connected providers and their configured state



ad-plat-integrations-test: Governance: a Super Admin connection test against Stripe



ad-delivery-lifecycle: Delivery: customer project stages from Created to Archived



cl-billing-paid: Invoices after a Stripe payment: one is paid, the others are open



pub-stripe-checkout: The Stripe payment page for an AI Scan (test mode), EUR 1,595.00 excluding VAT

Appendix I: Screenshot contact sheets











Appendix I: Screenshot contact sheets



ad-overview-campaigns: Executive overview with the live campaign attribution panel



pub-menu-tablet: Navigation menu open at 768 px wide (tablet)



ad-campaigns: Campaign attribution from real lead data