

Integrating an IMEI (International Mobile Equipment Identity) validation and lookup system

Breakdown of the key points:

1. Hosting the TAC Database

The TAC database, which needs to be uploaded and hosted on the server.

This database will be used to look up phone details based on IMEI numbers.

2. IMEI Validation & LUHN Algorithm

LUHN Algorithm will be used to check if an entered IMEI is valid.

Instead of writing custom logic, an existing npm package (luhn-generator) will be used. (A few sample IMEIs were provided to verify the LUHN validation)

3. IMEI Lookup & Auto-Population

When an IMEI is entered, the system should automatically fetch and display:

- Phone Make
- Phone Model
- Phone Model Name

These fields should be auto-populated and uneditable in the form.

4. Security & Status Checks via APIs

Multiple APIs will be used to check IMEI-related security statuses:

1. Blacklist Check (Separate API)
2. Apple Check (For Find My iPhone, iCloud Lock, etc.)
3. Carrier Lock Check

For Apple devices, additional checks like Find My iPhone and iCloud lock will be performed.

5. Two Main Use Cases

a) BYOD (Bring Your Own Device)

Validations required:

LUHN checksum

Phone Make, Model, and Name

Blacklist status

Carrier Lock status

b) Trade-In Phone

Same checks as BYOD, but if the phone is an Apple device, additional Apple-related API checks are required.

6. API Documentation & Keys

The required APIs and credentials are under "API Manage" on imeicheck.com.

API documentation and keys will be provided for implementation.

Enable / disable access of Agent to Springairns Portal

Whenever a new signup occurs you can get an email notification about it and then your team member can see the details through the admin side of the portal and can give access(enable) to the desired agent. Also we can add disable access as well.

Unless it got enabled the agent would not be able to login.