

Lab 1

1 Create an HTML page to illustrate the use of HTML tags. The page must contain Headings with different font sizes, an ordered list with at least 3 items, an image, 2 hyper links and 2 paragraphs. • The page must have an appropriate background color. • Paragraphs must have non-default font type and color. • Image must be resized

Code:

```
<!DOCTYPE html>
<html>
<head>
  <title>HTML Tags Illustration</title>

  <style>
    body{
      background-color: #dfefff; /* Background color */
      font-family: Arial, sans-serif;
      padding: 20px;
    }

    p{
      font-family: "Courier New", monospace; /* Non-default font */
      color: darkblue; /* Paragraph color */
      font-size: 18px;
    }

    img{
      width: 300px; /* Resized image */
      height: 200px;
      border-radius: 10px;
    }

    a{
      color: green;
      text-decoration: none;
    }

    a:hover{
      color: red;
    }
  </style>
</head>

<body>

  <!-- Headings with different sizes -->
  <h1>Welcome to HTML</h1>
  <h2>Learning HTML Tags</h2>
  <h3>Basic Elements</h3>
  <h4>Formatting Example</h4>

  <!-- Ordered List -->
  <h3>Ordered List Example</h3>
  <ol>
    <li>HTML</li>
    <li>CSS</li>
    <li>JavaScript</li>
  </ol>

  <!-- Paragraphs -->
  <p>
```

HTML stands for HyperText Markup Language. It is used to create webpages and structure web content using different tags.

</p>

<p>

CSS is used to style HTML pages by adding colors, fonts, layouts, and attractive designs.

</p>

<!-- Image -->

<h3>Sample Image</h3>

<!-- Hyperlinks -->

<h3>Useful Links</h3>

Visit Google

Learn HTML at W3Schools

</body>

</html>

2. Write HTML code to create a Time Table for your class.

Code:

SEM-6 TIMETABLE

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8" />

<meta name="viewport" content="width=device-width, initial-scale=1.0" />

<title>Department Time Table</title>

<style>

body{

font-family: Arial, sans-serif;

margin:20px;

color:#000;

}

.top{

text-align:center;

line-height:1.5;

}

.top h2,

.top h3,

.top h4,

.top p{

margin:2px;

}

.info{

display:flex;

justify-content:space-between;

```

        margin-top:10px;
        font-weight:bold;
    }

    table{
        width:100%;
        border-collapse:collapse;
        margin-top:10px;
    }

    th, td{
        border:1px solid #000;
        padding:6px;
        text-align:center;
        vertical-align:middle;
        font-size:13px;
    }

    .small{
        font-size:12px;
    }

    .left{
        text-align:left;
    }

    .break{
        writing-mode:vertical-rl;
        transform:rotate(180deg);
        font-weight:bold;
        letter-spacing:2px;
    }

    .note{
        margin-top:10px;
        font-weight:bold;
    }

    .signature{
        display:flex;
        justify-content:space-between;
        margin-top:40px;
        font-weight:bold;
    }
</style>
</head>

<body>

<div class="top">
    <h3>Sri Dharmasthala Manjunatheshwara College of Engineering & Technology, Dhavalagiri, Dharwad</h3>
    <h3>DEPARTMENT OF INFORMATION SCIENCE AND ENGINEERING</h3>
    <h3>TIME TABLE (EVEN)</h3>
</div>

<div class="info">
    <div>Academic Year : 2025-26</div>
    <div>B1:1-23</div>
</div>

<div class="info">
    <div>SEM : VI</div>
    <div>B2:24-47</div>
</div>

<div class="info">

```

<div></div>
<div>B3:48 Onwards</div>
</div>

<div class="info">
<div></div>
<div>HALL No: 32</div>
</div>

<table>
<tr>
<th>Days</th>
<th>8:00 to 9:00 A.M.</th>
<th>9:00 to 10:00 A.M.</th>
<th>10:00 to 10:30 A.M.</th>
<th>10:30 to 11:30 A.M.</th>
<th>11:30 to 12:30 P.M.</th>
<th>12:30 to 1:30 P.M.</th>
<th>1:30 to 2:00 P.M.</th>
<th>2:30 to 3:30 P.M.</th>
<th>3:30 to 4:30 P.M.</th>
</tr>

<tr>
<td>Mon</td>
<td>-</td>
<td>AM (OE I)
22UISC641</td>
<td rowspan="6" class="break">Break</td>
<td>BDA
22UISC602</td>
<td>CN
22UISC601</td>
<td>ML
22UISC600</td>
<td rowspan="6" class="break">Break</td>
<td>-</td>
<td>-</td>
</tr>

<tr>
<td>Tue</td>
<td>-</td>
<td>AM (OE I)
22UISC641</td>
<td>ML
22UISC600</td>
<td>CN
22UISC601</td>
<td>ADMS
22UISE622</td>
<td>CN LAB / WEB TECH LAB / Minor project-II
22UISL604-B1 / 22UISL603-B2 / 22UISL605-B3
</td>
<td>-</td>
</tr>

<tr>
<td>Wed</td>
<td>-</td>
<td>AM (OE I)
22UISC641</td>
<td>CN LAB / WEB TECH LAB / Minor project-II
22UISL604-B2 / 22UISL603-B3 / 22UISL605-B1
</td>
<td>-</td>
<td>-</td>
<td>Yoga</td>
<td>22UPYK607</td>
</tr>

<tr>
<td>Thu</td>
<td>-</td>
<td>CN
22UISC601</td>

| | |
|--|--|
| ADMS | 22UISE622 |
| BDA | 22UISC602 |
| SM | 22UISE631 |
| CN LAB / WEB TECH LAB / Minor project-II | 22UISL604-B3 / 22UISL603-B1 / 22UISL605-B2 |

| | | | | | | | | |
|-----|----|-----------|----|-----------|------|-----------|----|-----------|
| Fri | SM | 22UISE631 | ML | 22UISC600 | ADMS | 22UISE622 | CN | 22UISC601 |
|-----|----|-----------|----|-----------|------|-----------|----|-----------|

| | | | | | | |
|-----|----|-----------|----|-----------|-----|-----------|
| Sat | SM | 22UISE631 | ML | 22UISC600 | BDA | 22UISC602 |
|-----|----|-----------|----|-----------|-----|-----------|

Note: Time Table will be in force from: 05.02.2026

| Sl.No. | Course Title | Code | Credits | L-T-P-S | Course Instructor |
|--------|--------------|------|---------|---------|-------------------|
|--------|--------------|------|---------|---------|-------------------|

| | | | | | |
|---|------------------|-----------|---|---------|----------------------|
| 1 | Machine Learning | 22UISC600 | 4 | 4-0-0-0 | Prof. Arati S. Nayak |
|---|------------------|-----------|---|---------|----------------------|

| | | | | | |
|---|-------------------|-----------|---|---------|------------------------|
| 2 | Computer Networks | 22UISC601 | 4 | 4-0-0-0 | Dr. Sachidananda Joshi |
|---|-------------------|-----------|---|---------|------------------------|

| |
|---|
| 3 |
|---|

| |
|--|
| <div> <div>Big Data Analytics</div> <div>22UISC602</div> <div>3</div> <div>3-0-0-0</div> <div>Dr. Rajashekarappa</div> </div> |
| <div> <div>4</div> <div>Advanced Database Management System</div> <div>22UISE622</div> <div>3</div> <div>3-0-0-0</div> <div>Dr. Anita Dixit</div> </div> |
| <div> <div>5</div> <div>Storage Management</div> <div>22UISE631</div> <div>3</div> <div>3-0-0-0</div> <div>Dr. Varsha S Jadhav</div> </div> |
| <div> <div>6</div> <div>Agile Methodologies</div> <div>22UIS0641</div> <div>3</div> <div>3-0-0-0</div> <div>Dr. Pushpalatha S. N / Dr. S. S. Biradar</div> </div> |
| <div> <div>7</div> <div>Web Technology Laboratory</div> <div>22UISL603</div> <div>1</div> <div>0-0-2-0</div> <div>Dr. Pushpalatha S. N(I/C) / Dr. S. R. Biradar</div> </div> |
| <div> <div>8</div> <div>Computer Networks Laboratory</div> <div>22UISL604</div> <div>1</div> <div>0-0-2-0</div> <div>Dr. S S Joshi(I/C)/Dr Rajashekarappa</div> </div> |
| <div> <div>9</div> <div>Minor Project-II</div> <div>22UISL605</div> <div>2</div> <div>0-0-4-0</div> <div>Dr. Varsha S. Jadhav</div> </div> |
| <div> <div>10</div> <div>Soft Skills-II</div> <div>22USSK606</div> <div>Audit</div> </div> |

```

        <td>0-0-2-0</td>
        <td class="left">C.I.T.</td>
    </tr>

    <tr>
        <td>11</td>
        <td class="left">Physical Education and Yoga (PE & Y)</td>
        <td>22UPYK607</td>
        <td>Audit</td>
        <td>0-0-2-0</td>
        <td class="left">Prof. Tanveer Ahmed</td>
    </tr>

    <tr>
        <td colspan="3"><b>Total</b></td>
        <td><b>24</b></td>
        <td><b>20-0-12-0</b></td>
        <td></td>
    </tr>
</table>

<div class="signature">
    <div>HEAD OF DEPT.</div>
    <div>DEAN ACADEMIC</div>
    <div>PRINCIPAL</div>
</div>

</body>
</html>

```

LAB 2

1.Create an HTML form to accept Name, Gender (radio button), Branch (dropdown box), CGPA (0.0 to 10.0), Email, Phone Number (10 digits only), Date-of-birth and a Message from a job aspirant. The form must be validated (except message all fields are compulsory and CGPA must be at least 7.0) using JavaScript code and also be properly aligned by applying CSS.

Code:

```

<!DOCTYPE html>
<html>
<head>
    <title>Job Aspirant Form</title>

    <style>
        body{
            font-family: Arial, sans-serif;
            background-color:#e6f2ff;
            display:flex;
            justify-content:center;
            align-items:center;
            min-height:100vh;
        }

        .container{
            width:400px;
            background:white;
            padding:25px;
            border-radius:10px;
            box-shadow:0 0 10px gray;
        }
    </style>

```

```

h2{
  text-align:center;
  color:darkblue;
}

.form-group{
  margin-bottom:15px;
}

label{
  display:block;
  margin-bottom:5px;
  font-weight:bold;
}

input,select,textarea{
  width:100%;
  padding:8px;
  border:1px solid gray;
  border-radius:5px;
}

.gender{
  display:flex;
  gap:15px;
}

.gender input{
  width:auto;
}

button{
  width:100%;
  padding:10px;
  background:darkblue;
  color:white;
  border:none;
  border-radius:5px;
  cursor:pointer;
}

button:hover{
  background:blue;
}
</style>
</head>

<body>

<div class="container">

<h2>Job Aspirant Form</h2>

<form onsubmit="return validateForm()">

<div class="form-group">
<label>Name:</label>
<input type="text" id="name">
</div>

<div class="form-group">
<label>Gender:</label>

<div class="gender">
<input type="radio" name="gender" value="Male"> Male

```



```

<input type="radio" name="gender" value="Female"> Female
</div>

</div>

<div class="form-group">
<label>Branch:</label>

<select id="branch">
<option value="">Select Branch</option>
<option>CSE</option>
<option>ISE</option>
<option>ECE</option>
<option>EEE</option>
</select>

</div>

<div class="form-group">
<label>CGPA:</label>
<input type="number" id="cgpa" step="0.1" min="0" max="10">
</div>

<div class="form-group">
<label>Email:</label>
<input type="email" id="email">
</div>

<div class="form-group">
<label>Phone Number:</label>
<input type="text" id="phone">
</div>

<div class="form-group">
<label>Date of Birth:</label>
<input type="date" id="dob">
</div>

<div class="form-group">
<label>Message (Optional):</label>
<textarea id="message"></textarea>
</div>

<button type="submit">Submit</button>

</form>

</div>

<script>

function validateForm(){

let name=document.getElementById("name").value;
let branch=document.getElementById("branch").value;
let cgpa=document.getElementById("cgpa").value;
let email=document.getElementById("email").value;
let phone=document.getElementById("phone").value;
let dob=document.getElementById("dob").value;

let gender=document.querySelector("input[name='gender']:checked");

if(name==""){
alert("Name is required");
return false;

```

```

}

if(!gender){
alert("Select Gender");
return false;
}

if(branch==""){
alert("Select Branch");
return false;
}

if(cgpa==" || cgpa<7.0){
alert("CGPA must be at least 7.0");
return false;
}

let emailPattern=/^[^ ]+@[^ ]+\.[a-z]{2,3}$/;

if(!email.match(emailPattern)){
alert("Enter valid email");
return false;
}

let phonePattern=/^[0-9]{10}$/;

if(!phone.match(phonePattern)){
alert("Phone number must contain exactly 10 digits");
return false;
}

if(dob==""){
alert("Select Date of Birth");
return false;
}

alert("Form Submitted Successfully");

return true;

}

</script>

</body>
</html>

```

2.Create a form to accept password. Ask the user to re-enter the same password for confirmation. Validate the form using java script code. No field can be blank and both the passwords must be same. • If an input field is blank alert the user and highlight the field. • If the passwords do not match then alert the user, highlight the first field and select the password so that user can delete it one go and re-enter.

Code:

```

<!DOCTYPE html>
<html>
<head>
  <title>Password Validation Form</title>

  <style>
    body{
      font-family: Arial;
      background-color:#e6f2ff;

```

```

        display:flex;
        justify-content:center;
        align-items:center;
        height:100vh;
    }

    .container{
        background:white;
        padding:25px;
        width:350px;
        border-radius:10px;
        box-shadow:0px 0px 10px gray;
    }

    h2{
        text-align:center;
        color:darkblue;
    }

    input{
        width:100%;
        padding:10px;
        margin-top:8px;
        margin-bottom:15px;
        border:1px solid gray;
        border-radius:5px;
    }

    button{
        width:100%;
        padding:10px;
        background:darkblue;
        color:white;
        border:none;
        border-radius:5px;
    }

    .error{
        border:2px solid red;
        background-color:#ffe6e6;
    }

</style>
</head>

<body>

<div class="container">

<h2>Password Confirmation Form</h2>

<form onsubmit="return validateForm()">

<label>Password:</label>
<input type="password" id="pass1">

<label>Confirm Password:</label>
<input type="password" id="pass2">

<button type="submit">Submit</button>

</form>

</div>

<script>

```

```

function validateForm(){

let p1=document.getElementById("pass1");
let p2=document.getElementById("pass2");

p1.classList.remove("error");
p2.classList.remove("error");

if(p1.value==""){
alert("Password field cannot be blank");

p1.classList.add("error");
p1.focus();

return false;
}

if(p2.value==""){
alert("Confirm Password field cannot be blank");

p2.classList.add("error");
p2.focus();

return false;
}

if(p1.value!=p2.value){

alert("Passwords do not match");

p1.classList.add("error");

p1.focus();

p1.select();

return false;
}

alert("Password Matched Successfully");

return true;

}

</script>

</body>
</html>

```

LAB 3

1.Create an HTML form as given in Fig 3.1 to accept order from customers. Based on the value entered for Quantity Total Cost (including Shipping Charges) must be displayed. Items must be shipped for free if the customer orders products worth Rs.1,000/ at least otherwise the shipping charges must be 15% of the order amount. Note: 1. Validation must be done for Payment Mode (one option MUST be selected) 2. Input field next to Total Cost button cannot be blank and should not be editable manually

CODE:

```
<!DOCTYPE html>
<html>

<head>

  <title>Accessories Order Form</title>

  <style>

    body{
      font-family:"Times New Roman";
      font-size:14px;
      margin:20px;
    }

    .title{
      background-color:#8d63c7;
      width:520px;
      text-align:center;
      font-weight:bold;
      padding:4px;
    }

    table{
      border-collapse:collapse;
      width:520px;
      margin-top:10px;
    }

    th,td{
      border:1px solid black;
      text-align:center;
      padding:3px;
    }

    .small{
      width:55px;
    }

    .section{
      font-weight:bold;
      margin-top:20px;
    }

    .address td{
      border:none;
      text-align:left;
      padding:1px;
    }

    input[type=text], select{
      width:150px;
      height:18px;
    }

    .btns{
      margin-top:10px;
    }

  </style>

</head>

<body>
```

```
<form id="orderForm">

<div class="title">
  Accessories Order Form
</div>

<table>

<tr>
  <th>Product Name</th>
  <th>Price</th>
  <th>Quantity</th>
</tr>

<tr>
  <td>Ethernet Cable (2 m.)</td>
  <td>Rs.150</td>
  <td>
    <input type="text" id="q1" class="small" required>
  </td>
</tr>

<tr>
  <td>Router</td>
  <td>Rs.1000</td>
  <td>
    <input type="text" id="q2" class="small" required>
  </td>
</tr>

<tr>
  <td>Adapter</td>
  <td>Rs.280</td>
  <td>
    <input type="text" id="q3" class="small" required>
  </td>
</tr>

</table>

<br>

<button type="button" onclick="totalCost()">
  Total Cost (incl. Shipping Charges)
</button>

<input type="text" id="total" readonly required>

<div class="section">
  Payment Mode
</div>

<br>

<input type="radio" name="pay" required>
Debit Credit Cards

<br>

<input type="radio" name="pay">
UPI (PhonePe/GooglePay BHIM)

<br>

<input type="radio" name="pay">
Net Banking
```

```

<br>

<input type="radio" name="pay">
Cash on Delivery

<div class="section">
  Shipping Address
</div>

<table class="address">

<tr>
  <td>Customer Full Name</td>
  <td>
    <input type="text" id="sname" required>
  </td>
</tr>

<tr>
  <td>Locality</td>
  <td>
    <input type="text" id="slocality" required>
  </td>
</tr>

<tr>
  <td>City</td>
  <td>
    <input type="text" id="scity" required>
  </td>
</tr>

<tr>
  <td>State</td>
  <td>
    <select id="sstate" required>
      <option value="">-- Select your state --</option>
      <option>Maharashtra</option>
      <option>Karnataka</option>
      <option>Tamil Nadu</option>
    </select>
  </td>
</tr>

<tr>
  <td>PIN</td>
  <td>
    <input type="text" id="spin" placeholder="6-digit PIN" required>
  </td>
</tr>

</table>

<div class="section">
  Billing Address
</div>

<br>

<input type="checkbox" id="same" onclick="copyAddress()">
Same as shipping address

<table class="address">

```

```

<tr>
  <td>Customer Full Name</td>
  <td>
    <input type="text" id="bname" required>
  </td>
</tr>

<tr>
  <td>Locality</td>
  <td>
    <input type="text" id="blocality" required>
  </td>
</tr>

<tr>
  <td>City</td>
  <td>
    <input type="text" id="bcity" required>
  </td>
</tr>

<tr>
  <td>State</td>
  <td>
    <select id="bstate" required>
      <option value="">-- Select your state --</option>
      <option>Maharashtra</option>
      <option>Karnataka</option>
      <option>Tamil Nadu</option>
    </select>
  </td>
</tr>

<tr>
  <td>PIN</td>
  <td>
    <input type="text" id="bpin" placeholder="6-digit PIN" required>
  </td>
</tr>

</table>

<div class="btns">

  <button type="button" onclick="submitForm()">
    Submit Order
  </button>

  <button type="reset">
    Clear Order Form
  </button>

</div>

</form>

<script>

function totalCost(){

  let q1 = parseInt(document.getElementById("q1").value) || 0;
  let q2 = parseInt(document.getElementById("q2").value) || 0;
  let q3 = parseInt(document.getElementById("q3").value) || 0;

```



```

let total = (q1 * 150) + (q2 * 1000) + (q3 * 280);

if(total < 1000 && total > 0){

    total = total + (total * 0.15);
}

document.getElementById("total").value = total;
}

function copyAddress(){

    if(document.getElementById("same").checked){

        document.getElementById("bname").value =
            document.getElementById("sname").value;

        document.getElementById("blocality").value =
            document.getElementById("slocality").value;

        document.getElementById("bcity").value =
            document.getElementById("scity").value;

        document.getElementById("bstate").value =
            document.getElementById("sstate").value;

        document.getElementById("bpin").value =
            document.getElementById("spin").value;
    }

    else{

        document.getElementById("bname").value = "";
        document.getElementById("blocality").value = "";
        document.getElementById("bcity").value = "";
        document.getElementById("bstate").value = "";
        document.getElementById("bpin").value = "";
    }
}

function submitForm(){

    let form = document.getElementById("orderForm");

    if(!form.checkValidity()){

        form.reportValidity();
        return;
    }

    let payment = document.getElementsByName("pay");
    let selected = false;

    for(let i=0; i<payment.length; i++){

        if(payment[i].checked){

            selected = true;
        }
    }

    if(selected == false){

        alert("Select Payment Mode");
        return;
    }
}

```

```

    }

    if(document.getElementById("total").value == ""){

        alert("Calculate Total Cost");
        return;
    }

    alert("Order Submitted Successfully");
}

</script>

</body>
</html>

```

LAB 4

1. Write HTML and JavaScript code to change the text color on selecting a radio button as in Fig 1.1

Code:

```

<!DOCTYPE html>
<html>

<head>

    <title>Change Text Color</title>

    <style>

        body{
            font-family:"Times New Roman";
            margin:20px;
        }

        #text{
            font-size:28px;
            font-weight:bold;
            color:purple;
        }

        .author{
            text-align:right;
            font-size:22px;
            margin-top:10px;
        }

        .box{
            border:1px solid lightgray;
            padding:15px;
            width:900px;
        }

        .radio-section{
            margin-top:40px;
        }

        .color-box{
            width:60px;
            height:25px;
            display:inline-block;
            border:4px solid lightgray;

```



```

<title>Text Case Converter</title>

<style>

    body{
        font-family:"Times New Roman";
        margin:30px;
        font-size:20px;
    }

    table{
        border-collapse:collapse;
    }

    td{
        padding:5px;
        font-weight:bold;
    }

    input[type=text]{
        width:250px;
        height:25px;
    }

    .radio{
        margin-left:25px;
        margin-top:10px;
    }

    button{
        margin-left:170px;
        margin-top:10px;
        width:80px;
        font-size:20px;
    }

</style>

</head>

<body>

<form>

<table>

<tr>

    <td>Input Text</td>

    <td>
        <input type="text" id="inputText">
    </td>

</tr>

<tr>

    <td>Result Text</td>

    <td>
        <input type="text" id="resultText" readonly>
    </td>

</tr>

```

[illegible]

3. Write code to demonstrate the creation of a dynamic list using DOM methods.

Code:

```
<!DOCTYPE html>
<html>

<head>

  <title>Dynamic List using DOM</title>

  <style>

    body{
      font-family:"Times New Roman";
```

```

        margin:30px;
        font-size:20px;
    }

    input[type=text]{
        width:220px;
        height:25px;
    }

    button{
        margin-top:10px;
        font-size:18px;
    }

    ul{
        margin-top:20px;
    }

</style>

</head>

<body>

<h2>Dynamic List using DOM Methods</h2>

Enter Item :
<input type="text" id="item">

<br>

<button onclick="addItem()">
    Add Item
</button>

<button onclick="removeItem()">
    Remove Last Item
</button>

<ul id="list">

</ul>

<script>

function addItem(){

    let value =
    document.getElementById("item").value;

    if(value == ""){

        alert("Enter Item");
        return;
    }

    let li =
    document.createElement("li");

    let text =
    document.createTextNode(value);

    li.appendChild(text);

    document.getElementById("list")
    .appendChild(li);

```

```

        document.getElementById("item").value = "";
    }

    function removeItem(){

        let list =
        document.getElementById("list");

        if(list.lastChild){

            list.removeChild(list.lastChild);
        }
    }

</script>

</body>

</html>

```

LAB 5

1. Write HTML and JavaScript code to demonstrate adding event listeners 2 to different HTML elements to handle at least 2 mouse events each.

Code:

```

<!DOCTYPE html>
<html>
<head>

<title>Event Listeners Demo</title>

<style>

body{
font-family:Arial;
text-align:center;
margin-top:100px;
background-color:#f0f8ff;
}

button{
padding:15px;
font-size:18px;
margin-bottom:30px;
cursor:pointer;
}

p{
font-size:24px;
cursor:pointer;
color:black;
}

</style>

</head>

<body>

<!-- BUTTON -->
<button id="question">
What is HTML?

```

```

</button>

<br><br>

<!-- TEXT -->
<p id="text">
Press mouse on this text
</p>

<script>

let btn=document.getElementById("question");

// Mouse enter → show answer
btn.addEventListener("mouseenter",function(){
btn.innerHTML="HTML = HyperText Markup Language";
});

// Mouse leave → show question back
btn.addEventListener("mouseleave",function(){
btn.innerHTML="What is HTML?";
});

let para=document.getElementById("text");

// Mouse press → red
para.addEventListener("mousedown",function(){
para.style.color="red";
});

// Mouse release anywhere → blue (IMPORTANT FIX)
document.addEventListener("mouseup",function(){
para.style.color="blue";
});

</script>

</body>
</html>

```

2. Write code to demonstrate the removal of an event listener. (You should not modify in the above code. New code must be written.)

Code:

```

<!DOCTYPE html>
<html>
<head>

<title>Remove Event Listener</title>

<style>

body{
text-align:center;
font-family:Arial;
margin-top:100px;
}

button{
padding:12px;
}

</style>

```



```

</head>

<body>

<button id="btn">
Hover on me
</button>

<br><br>

<button onclick="removeEvent()">
Remove Listener
</button>

<script>

let b=document.getElementById("btn");

function show(){

b.innerHTML="Mouse Entered";

}

b.addEventListener("mouseenter",show);

function removeEvent(){

b.removeEventListener("mouseenter",show);

alert("Event Listener Removed");

}

</script>

</body>
</html>

```

3. Write HTML and javascript to add rows, on clicking a button, to a railway passenger details table. Each row must have input fields to accept Name, Age and Berth Preference[Lower, Middle, Upper].

Code:

```

<!DOCTYPE html>
<html>
<head>

<title>Railway Passenger Table</title>

<style>

body{
font-family:Arial;
padding:20px;
}

table{
width:100%;
border-collapse:collapse;
}

```

```
th,td{
border:1px solid black;
padding:10px;
text-align:center;
}
```

```
button{
padding:10px;
margin-bottom:20px;
}
```

```
input,select{
width:90%;
padding:5px;
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<h2>Railway Passenger Details</h2>
```

```
<button onclick="addRow()">
Add Passenger
</button>
```

```
<table id="table">
```

```
<tr>
```

```
<th>Name</th>
```

```
<th>Age</th>
```

```
<th>Berth Preference</th>
```

```
</tr>
```

```
</table>
```

```
<script>
```

```
function addRow(){
```

```
let table=document.getElementById("table");
```

```
let row=table.insertRow();
```

```
row.innerHTML=`
```

```
<td>
```

```
<input type="text" placeholder="Enter Name">
</td>
```

```
<td>
```

```
<input type="number" placeholder="Age">
</td>
```

```
<td>
```

```
<select>
```

```
<option>Lower</option>
```

```

<option>Middle</option>

<option>Upper</option>

</select>

</td>

`;

}

</script>

</body>
</html>

```

LAB 7(as per new pdf)

1.Design a web page with 3 equally -wide columns a header and a footer as in fig. Navigation bar must be distinguishable from cut of the page, and on hovering a link its background must change. The page must be responsive on all kinds of devices. i. e, on resizing the browser window the columns must be stacked upon each

Code:

```

<!DOCTYPE html>
<html>
<head>
<title>Responsive 3 Column Layout</title>

<style>

*{
box-sizing:border-box;
margin:0;
padding:0;
font-family:Arial;
}

/* HEADER */
header{
background:#1e3a8a;
color:white;
text-align:center;
padding:20px;
font-size:24px;
}

/* NAVIGATION */
nav{
background:#333;
display:flex;
justify-content:center;
}

nav a{
color:white;
padding:15px 20px;
text-decoration:none;
display:block;
}

nav a:hover{
background:#ff9800;

```

```

color:black;
}

/* MAIN CONTAINER */
.row{
display:flex;
flex-wrap:wrap;
}

/* COLUMNS */
.column{
flex:33.33%;
padding:20px;
min-height:200px;
}

.column:nth-child(1){background:#f1f1f1;}
.column:nth-child(2){background:#e3f2fd;}
.column:nth-child(3){background:#fce4ec;}

/* FOOTER */
footer{
background:#222;
color:white;
text-align:center;
padding:15px;
}

/* RESPONSIVE */
@media screen and (max-width:768px){
.column{
flex:100%;
}
nav{
flex-direction:column;
text-align:center;
}
}

</style>

</head>

<body>

<header>
Responsive Web Page Layout
</header>

<nav>
<a href="#">Home</a>
<a href="#">About</a>
<a href="#">Services</a>
<a href="#">Contact</a>
</nav>

<div class="row">

<div class="column">
<h2>Column 1</h2>
<p>This is first column content.</p>
</div>

<div class="column">
<h2>Column 2</h2>
<p>This is second column content.</p>

```

```

</div>

<div class="column">
<h2>Column 3</h2>
<p>This is third column content.</p>
</div>

</div>

<footer>
© 2026 Responsive Layout Example
</footer>

</body>
</html>

```

2.Modify previous webpage to have a varying width columns(25%,50%,25%)

Code:

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>25-50-25 Layout</title>

<style>
* {
  margin: 0;
  padding: 0;
  box-sizing: border-box;
  font-family: Arial;
}

/* HEADER */
header {
  background: #1b1b1b;
  color: white;
  padding: 15px;
  text-align: center;
}

/* NAVBAR */
nav {
  background: #333;
  display: flex;
  justify-content: center;
}

nav a {
  color: white;
  padding: 14px 20px;
  text-decoration: none;
  transition: 0.3s;
}

nav a:hover {
  background: #ff5722;
  border-radius: 5px;
}

/* ROW */
.row {
  display: flex;
  flex-wrap: wrap;
}

```

```

/* 🔥 CLEARLY VISIBLE COLORS */

/* Left - 25% */
.left {
  flex: 25%;
  padding: 20px;
  background: #ffcc80; /* light orange */
}

/* Middle - 50% */
.middle {
  flex: 50%;
  padding: 20px;
  background: #90caf9; /* light blue */
}

/* Right - 25% */
.right {
  flex: 25%;
  padding: 20px;
  background: #a5d6a7; /* light green */
}

/* FOOTER */
footer {
  background: #1b1b1b;
  color: white;
  text-align: center;
  padding: 10px;
}

/* RESPONSIVE */
@media screen and (max-width: 768px) {
  .left, .middle, .right {
    flex: 100%;
  }
}
</style>
</head>

<body>

<header>
  <h1>25-50-25 Responsive Layout</h1>
</header>

<nav>
  <a href="#">Home</a>
  <a href="#">About</a>
  <a href="#">Services</a>
  <a href="#">Contact</a>
</nav>

<div class="row">
  <div class="left">Left Column (25%)</div>
  <div class="middle">Middle Column (50%)</div>
  <div class="right">Right Column (25%)</div>
</div>

<footer>
  <p>Footer Section</p>
</footer>

</body>
</html>

```

3.with sticky header. On scrolling the page up to the top, the sticky effect must be removed.

Code:

```
<!DOCTYPE html>
<html>
<head>
<title>Sticky Header Example</title>

<style>

body{
margin:0;
font-family:Arial;
}

/* Sticky Header */
header{
position:sticky;
top:0;
background:#1e3a8a;
color:white;
padding:15px;
text-align:center;
font-size:22px;
z-index:1000;
}

/* Navigation (optional) */
nav{
background:#333;
display:flex;
justify-content:center;
}

nav a{
color:white;
padding:12px 18px;
text-decoration:none;
display:block;
}

nav a:hover{
background:orange;
color:black;
}

/* Content */
.content{
padding:20px;
}

.section{
height:400px; /* to enable scrolling */
padding:20px;
margin:10px 0;
background:#f1f1f1;
}

.section:nth-child(even){
background:#e3f2fd;
}

</style>
```

```

</head>

<body>

<header>
Sticky Header Example
</header>

<nav>
<a href="#">Home</a>
<a href="#">About</a>
<a href="#">Services</a>
<a href="#">Contact</a>
</nav>

<div class="content">

<div class="section">Section 1 - Scroll down</div>
<div class="section">Section 2 - Keep scrolling</div>
<div class="section">Section 3 - Sticky header stays at top</div>
<div class="section">Section 4 - Works smoothly</div>

</div>

</body>
</html>

```

LAB 8

1. Write a PHP script to accept the data provided through HTML form created in Lab2 (Q1) and Store it in a table called job_aspirant in a database called recruitment Note:

- If the CGPA is below 7.5 then do not store the data. Instead, display a message saying "Dear aspirant_name, The minimum CGPA must be 7.5!!"

Code:

HTML CODE: save as form.html

```

<!DOCTYPE html>
<html>
<head>
<title>Job Aspirant Form</title>

<style>
body{
    font-family: Arial;
    background: #f4f4f4;
}

.container{
    width: 50%;
    margin: auto;
    background: white;
    padding: 20px;
    margin-top: 30px;
    border-radius: 10px;
    box-shadow: 0px 0px 10px gray;
}

```



```

h2{
  text-align: center;
}

label{
  font-weight: bold;
}

input, select, textarea{
  width: 100%;
  padding: 8px;
  margin: 5px 0 15px 0;
  box-sizing: border-box;
}

/* ✅ FIXED GENDER FIELD */
.radio-group{
  display: flex;
  align-items: center;
  gap: 25px;
  margin-bottom: 15px;
}

.radio-group label{
  display: flex;
  align-items: center;
  gap: 5px;
  font-weight: normal;
}

button{
  background: blue;
  color: white;
  padding: 10px;
  border: none;
  width: 100%;
  cursor: pointer;
}

button:hover{
  background: darkblue;
}
</style>

<script>
function validateForm(){

  let name = document.forms["jobForm"]["name"].value;
  let gender = document.forms["jobForm"]["gender"].value;
  let branch = document.forms["jobForm"]["branch"].value;
  let cgpa = document.forms["jobForm"]["cgpa"].value;
  let email = document.forms["jobForm"]["email"].value;
  let phone = document.forms["jobForm"]["phone"].value;
  let dob = document.forms["jobForm"]["dob"].value;

  if(name=="" || gender=="" || branch=="" || cgpa=="" || email=="" || phone=="" || dob==""){
    alert("All fields except message are required!");
    return false;
  }

  if(cgpa < 7.0 || cgpa > 10.0){
    alert("CGPA must be between 7.0 and 10.0");
    return false;
  }

  if(phone.length != 10){

```

```
        alert("Phone number must be 10 digits");
        return false;
    }

    return true;
}
</script>

</head>

<body>

<div class="container">

<h2>Job Aspirant Form</h2>

<form name="jobForm" action="store.php" method="get" onsubmit="return validateForm()">

    <label>Name:</label>
    <input type="text" name="name">

    <label>Gender:</label>
    <div class="radio-group">

        <label>
            <input type="radio" name="gender" value="Male"> Male
        </label>

        <label>
            <input type="radio" name="gender" value="Female"> Female
        </label>

    </div>

    <label>Branch:</label>
    <select name="branch">
        <option value="">Select</option>
        <option>CSE</option>
        <option>ISE</option>
        <option>ECE</option>
        <option>EEE</option>
        <option>CIVIL</option>
        <option>MECH</option>
    </select>

    <label>CGPA:</label>
    <input type="number" step="0.1" name="cgpa">

    <label>Email:</label>
    <input type="email" name="email">

    <label>Phone Number:</label>
    <input type="text" name="phone">

    <label>Date of Birth:</label>
    <input type="date" name="dob">

    <label>Message (Optional):</label>
    <textarea name="message"></textarea>

    <button type="submit">Submit</button>

</form>

</div>
```

```
</body>
</html>
```

PHP CODE: save as store.php (just make sure in html code u will give the same name of php file what u have saved as)

```
<?php

$name = $_GET['name'];
$gender = $_GET['gender'];
$branch = $_GET['branch'];
$cgpa = $_GET['cgpa'];
$email = $_GET['email'];
$phone = $_GET['phone'];
$dob = $_GET['dob'];
$message = $_GET['message'];

// CGPA check (IMPORTANT REQUIREMENT)
if ($cgpa < 7.5) {
    echo "Dear $name, The minimum CGPA must be 7.5!!";
    exit();
}

// DB connection
$conn = new mysqli("localhost", "root", "", "recruitment");

if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// INSERT QUERY
$sql = "INSERT INTO job_aspirant (name, gender, branch, cgpa, email, phone, dob, message)
VALUES ('$name', '$gender', '$branch', '$cgpa', '$email', '$phone', '$dob', '$message')";

if ($conn->query($sql) === TRUE) {
    echo "Data stored successfully!";
} else {
    echo "Error: " . $conn->error;
}

$conn->close();

?>
```

SQL QUERY TO CREATE TABLE in Database: Recruitment : (create db manually - in that go to sql and paste this query)

```
CREATE TABLE job_aspirant (
    id INT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(100),
    gender VARCHAR(10),
    branch VARCHAR(20),
    cgpa FLOAT,
    email VARCHAR(100),
    phone VARCHAR(15),
    dob DATE,
    message TEXT
);
```

2. Write a PHP script to accept the data through HTML form created in Lab: 2 (Q2) and Store it in a table called credentials in a database called admission. Note:

- password should be stored in an encrypted format

Code:

SQL Query to create table credentials in db admission: (create db manually - in that go to sql and paste this query)

```
CREATE TABLE credentials (  
id INT AUTO_INCREMENT PRIMARY KEY,  
password VARCHAR(255)  
);
```

Html Code: save as pass.html

```
<!DOCTYPE html>  
  
<html>  
  
<head>  
  
<title>Password Validation Form</title>  
  
<style>  
  
body{  
  
font-family: Arial;  
  
background-color: #e6f2ff;  
  
display: flex;  
  
justify-content: center;  
  
align-items: center;  
  
height: 100vh;  
  
}  
  
.container{  
  
background: white;  
  
padding: 25px;  
  
width: 350px;  
  
border-radius: 10px;  
  
box-shadow: 0px 0px 10px gray;  
  
}  
  
h2{  
  
text-align: center;
```

```
color:darkblue;

}

input{

width:100%;

padding:10px;

margin-top:8px;

margin-bottom:15px;

border:1px solid gray;

border-radius:5px;

}

button{

width:100%;

padding:10px;

background:darkblue;

color:white;

border:none;

border-radius:5px;

}

.error{

border:2px solid red;

background-color:#ffe6e6;

}

</style>

</head>

<body>

<div class="container">

<h2>Password Confirmation Form</h2>

<!-- ✅ PHP connected here -->

<form action="pass.php" method="post" onsubmit="return validateForm()">

<label>Password:</label>

<input type="password" id="pass1" name="password">
```

```
<label>Confirm Password:</label>

<input type="password" id="pass2">

<button type="submit">Submit</button>

</form>

</div>

<script>

function validateForm(){

let p1=document.getElementById("pass1");

let p2=document.getElementById("pass2");

p1.classList.remove("error");

p2.classList.remove("error");

if(p1.value==""){

alert("Password field cannot be blank");

p1.classList.add("error");

p1.focus();

return false;

}

if(p2.value==""){

alert("Confirm Password field cannot be blank");

p2.classList.add("error");

p2.focus();

return false;

}

if(p1.value!=p2.value){

alert("Passwords do not match");

p1.classList.add("error");

p1.focus();

p1.select();

return false;

}

alert("Password Matched Successfully");
```

```

return true;

}

</script>

</body>

</html>

```

PHP Code: Save as pass.php

```

<?php

$conn = new mysqli("localhost", "root", "", "admission");

if ($conn->connect_error) {

    die("Connection failed: " . $conn->connect_error);

}

$password = $_POST['password'];

// encrypt password

$hash = password_hash($password, PASSWORD_DEFAULT);

// insert ONLY password

$sql = "INSERT INTO credentials (password) VALUES ('$hash')";

if ($conn->query($sql) === TRUE) {

    echo "Password stored successfully!";

} else {

    echo "Error: " . $conn->error;

}

$conn->close();

?>

```

LAB 9

9.1 Write a PHP script to connect to the database ,execute SELECT query on a table and display all the details present in a table format.

Code:

Note: First create db(student) manually- then go to sql and paste the table creation and then next insertion of values queries one after other)

SQL Queries to create table students and then insert some values:

```

CREATE TABLE students (
    id INT PRIMARY KEY AUTO_INCREMENT,

```

```
    name VARCHAR(50),
    marks INT
);
```

```
INSERT INTO students (name, marks) VALUES
('Ananya', 85),
('Rahul', 72),
('Sneha', 90);
```

PHP Code: save as select.php

```
<?php

// 1. Database connection

$host = "localhost";

$username = "root";

$password = "";

$databse = "student";

$conn = mysqli_connect($host, $username, $password, $database);

// 2. Check connection

if (!$conn) {

    die("Connection failed: " . mysqli_connect_error());

}

// 3. SELECT query

$sql = "SELECT * FROM students";

$result = mysqli_query($conn, $sql);

?>

<!DOCTYPE html>

<html>

<head>

<title>Student Data</title>

<style>

body{

    font-family: Arial;

    background-color: #f2f2f2;

    text-align: center;

}

table{
```



```

margin: auto;

border-collapse: collapse;

width: 50%;

background: white;

}

th, td{

border: 1px solid #333;

padding: 10px;

}

th{

background-color: #4CAF50;

color: white;

}

</style>

</head>

<body>

<h2>Student Records</h2>

<table>

<tr>

<th>ID</th>

<th>Name</th>

<th>Marks</th>

</tr>

<?php

// 4. Display data

if (mysqli_num_rows($result) > 0) {

while ($row = mysqli_fetch_assoc($result)) {

echo "<tr>

<td>".$row['id']. "</td>

<td>".$row['name']. "</td>

<td>".$row['marks']. "</td>

```

```

</tr>";

}

} else {

echo "<tr><td colspan='3'>No records found</td></tr>";

}

// 5. Close connection

mysqli_close($conn);

?>

</table>

</body>

</html>

```

2. Write a PHP script to connect to the MYSQL database and access the table cookie_sales(Sale_ID, Salesman_Name, Sale_Amount, Sale_Date)' and to Display only those rows from the cookie_sales table where the Sale Amount is less than 99 dollars, Print the no of rows fetched. • Change the Salesman_Name to MGR where Sale Amount is 0. Print the no. of rows affected

Code:

SQL queries to create table (cookie_sales): (Note-manually create db (sales) in that go to sql and paste these one after other) at last show db to show updated name:

```

CREATE TABLE cookie_sales (
    Sale_ID INT PRIMARY KEY AUTO_INCREMENT,
    Salesman_Name VARCHAR(50),
    Sale_Amount FLOAT,
    Sale_Date DATE
);

INSERT INTO cookie_sales (Salesman_Name, Sale_Amount, Sale_Date) VALUES
('Amit', 120, '2026-01-10'),
('Ravi', 80, '2026-01-11'),
('Sita', 0, '2026-01-12'),
('John', 50, '2026-01-13');

```

PHP Code: Save as sales.php

```

<?php

// 1. Connection

$conn = mysqli_connect("localhost", "root", "", "salesdb");

if (!$conn) {

die("Connection failed: " . mysqli_connect_error());

}

```

```

// 2. SELECT query (Sale_Amount < 99)

$sql = "SELECT * FROM cookie_sales WHERE Sale_Amount < 99";

$result = mysqli_query($conn, $sql);

echo "<h2>Sales Less Than $99</h2>";

if (mysqli_num_rows($result) > 0) {

echo "<table border='1' cellpadding='10'>

<tr>

<th>Sale ID</th>

<th>Salesman Name</th>

<th>Sale Amount</th>

<th>Sale Date</th>

</tr>";

while ($row = mysqli_fetch_assoc($result)) {

echo "<tr>

<td>".$row['Sale_ID']. "</td>

<td>".$row['Salesman_Name']. "</td>

<td>".$row['Sale_Amount']. "</td>

<td>".$row['Sale_Date']. "</td>

</tr>";

}

echo "</table>";

} else {

echo "No records found.";

}

// Print number of rows fetched

$fetch_rows = mysqli_num_rows($result);

echo "<h3>Rows Fetched: $fetch_rows</h3>";

// 3. UPDATE query (Sale_Amount = 0 → Salesman_Name = MGR)

$update_sql = "UPDATE cookie_sales

SET Salesman_Name = 'MGR'

WHERE Sale_Amount = 0";

```

```

mysqli_query($conn, $update_sql);

// Print rows affected

$affected_rows = mysqli_affected_rows($conn);

echo "<h3>Rows Affected (Updated to MGR): $affected_rows</h3>";

// 4. Close connection

mysqli_close($conn);

?>

```

3. Write HTML code to create a login page (User-ID, Password and a login (submit-type) button). On clicking the login button the PHP script should connect to the database and check if the User-ID exists in the credentials table. If it exists then hash the input password and compare it with the already hashed password in the credentials table. If not a match then print an error message saying “The credentials are wrong” else display a success message saying “The login is successful!”

SQL QUERIES TO CREATE TABLE: Note: Create db (logindb) manually in that go to sql and paste these queries one after other)

```

CREATE TABLE credentials (
user_id VARCHAR(50) PRIMARY KEY,
password VARCHAR(255)
);

```

IMP Note: Now create hash.php and paste this code:

```

<?php
echo password_hash("admin123", PASSWORD_DEFAULT);
?>

```

RUN this file: that is paste this file in wamp64—www and go to url and type localhost/hash.php u will get a hashed password copy and paste it in below sql query:

Now open db in that table credentials: go to sql and put this query:

```

INSERT INTO credentials (user_id, password)
VALUES ('admin', 'PASTE_YOUR_HASH_HERE');

```

HTML CODE for login form: save as login.html

```

<!DOCTYPE html>
<html>
<head>
    <title>Login Page</title>
</head>
<body>

<h2>Login Form</h2>

<form action="login.php" method="POST">
    User ID: <input type="text" name="user_id" required><br><br>

    Password: <input type="password" name="password" required><br><br>

```

```
        <input type="submit" value="Login">
    </form>

</body>
</html>
```

PHP Code: save as login.php

```
<?php

// 1. Connection

$conn = mysqli_connect("localhost", "root", "", "logindb");

if (!$conn) {

    die("Connection failed: " . mysqli_connect_error());

}

// 2. Get form data

$user_id = $_POST['user_id'];

$password = $_POST['password'];

// 3. Check if user exists

$sql = "SELECT * FROM credentials WHERE user_id='$user_id'";

$result = mysqli_query($conn, $sql);

if (mysqli_num_rows($result) > 0) {

    $row = mysqli_fetch_assoc($result);

    // 4. Verify hashed password

    if (password_verify($password, $row['password'])) {

        echo "<h2 style='color:green;'>Login is successful!</h2>";

    } else {

        echo "<h2 style='color:red;'>The credentials are wrong</h2>";

    }

} else {

    echo "<h2 style='color:red;'>The credentials are wrong</h2>";

}

// 5. Close connection

mysqli_close($conn);

?>
```

