

SQLW Day 2

~~SQL~~ Day

1. Select Query

It is used to retrieve data from a SQL database.

" SELECT column, column another...
FROM table name "

2. Query with Constraints (WHERE)

It is used to filter records based on a specific conditions.


- AND / OR
- col-name != 4
- col-name BETWEEN 2000 AND 2010
- col-name ^(sb) IN (1, 2, 6, 8)
- col-name LIKE

3) DISTINCT

Select all the unique char.

4) Aggregate Functions

min(), Max, count(), sum(), Avg()



ve-etc
Trunkelate

SQL Order by

```
SELECT * FROM student
ORDER BY S_Fee ASC,
```

SQL OR || AND

```
SELECT * FROM student
WHERE Fee = 10,000 AND (Paid = cash ||
Paid = online)
```

SQL Insertion

```
Insert Into file Name (columns,
Values)
```

SQL NULL

```
SELECT * FROM student
WHERE Fee is NOT NULL
```

SQL UPDATE

```
UPDATE table_name
SET C1 = V1, C2 = V2...
WHERE condition
```

SQL DELETE

```
DELETE FROM table WHERE condition
```

SQL Aggregate Function

SQL Min(), ~~SQL~~ Max(), Count(),
Sum(), Average.

SQL LIKE

It is used to search for a specified pattern within a column's text data.

Where Like "[a- %]"

SQL IN

It checks if a specified column's value matches any value within the list where country In "Nepal", "India"

SQL BETWEEN

SELECT * From Product
Where Price Between 10 AND 20,

SQL Aliases

It creates alias for a keyword as A.
It is often used to make a column name more readable.

Customers AS C

SQL Joins

It is used to combine multiple table to make a single table as a output.

Inner joint

It will give the common element / id from both table.

Left join

It will return all records from the left table and the matched records from the right table.

Right joint

It will return all records from the left table and the matched records from the right table.

Full joint

Return all records when there is a match in either left or right table.

DBeaver