Network Layer: “data plane” roadmap

- Network layer service
- Networks layer: Internet
- IP Protocol
- IP Addressing
- DHCP
- Network Address Translation (NAT)



Network-layer services and protocols

- transport segment from sending to receiving host
  - sender: encapsulates segments into datagrams, passes to link layer
  - receiver: delivers segments to transport layer protocol
- network layer protocols in *every Internet device*: hosts, routers
- routers:
  - examines header fields in all IP datagrams passing through it
  - moves datagrams from input ports to output ports to transfer datagrams along end-end path



Two key network-layer functions

network-layer functions:

- *forwarding:* move packets from a router's input link to appropriate router output link
  - *routing:* determine route taken by packets from source to destination
    - *routing algorithms*

analogy: taking a trip

- *forwarding:* process of getting through single interchange
  - *routing:* process of planning trip from source to destination

forwarding

routing

Forwarding vs Routing



Destination	NextHop	Interface
12.10.0.1	12.1.1.2	EH1/0/0
12.11.0.1	12.2.2.2	EH2/0/0
12.12.0.1	12.3.3.2	EH3/0/0

Routing Table of A

Network-layer service model

Network Architecture	Service Model	Quality of Service (QoS) Guarantees ?			
		Bandwidth	Loss	Order	Timing
Internet	best effort	none	no	no	no

Internet "best effort" service model

No guarantees on:

i. successful datagram delivery to destination
ii. timing or order of delivery
iii. bandwidth available to end-end flow

Reflections on best-effort service:

- simplicity of mechanism has allowed Internet to be widely deployed adopted
- sufficient provisioning of bandwidth allows performance of real-time applications (e.g., interactive voice, video) to be "good enough" for "most of the time"
- replicated, application-layer distributed services (datacenters, content distribution networks) connecting close to clients' networks, allow services to be provided from multiple locations
- congestion control of "elastic" services helps

It's hard to argue with success of best-effort service model

Network Layer: “data plane” roadmap

- Network layer functions
- Service model
- Networks layer: Internet
- IP Protocol
- IP Addressing
- DHCP
- Network Address Translation (NAT)



Network Layer: Internet

host, router network layer functions:



IP Datagram format



overhead

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead for TCP+IP

IP addressing: introduction

- **IP address:** 32-bit identifier associated with each host or router *interface*
- **interface:** connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)



dotted-decimal IP address notation:

223.1.1.1 = 11011111 00000001 00000001 00000001

223 1 1 1

Subnets

- *What's a subnet ?*
  - device interfaces that can physically reach each other without passing through an intervening router
- IP addresses have structure:
  - subnet part: devices in same subnet have common high order bits
  - host part: remaining low order bits



network consisting of 3 subnets

Subnets

Recipe for defining subnets:

- detach each interface from its host or router, creating "islands" of isolated networks
- each isolated network is called a *subnet*



subnet mask: /24
(high-order 24 bits: subnet part of IP address)

Subnets

- where are the subnets?
- what are the /24 subnet addresses?



IP addressing: CIDR

CIDR: Classless InterDomain Routing (pronounced “cider”)

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address



200.23.16.0/23

Hierarchical Addressing under CIDR



Figure 4.21 ♦ Hierarchical addressing and route aggregation

Exercise: Allocating Addresses to Subnets

- How does the organization with network address 192.168.76.0/23 allocate addresses to two of its subnets A and B?
- Always allocate the larger subnet first (descending order)
- Subnet A
  - Subnet address 192.168.76.0/27
  - First 192.168.76.1
  - Last 192.168.76.30
  - Subnet broadcast 192.168.76.31
- Subnet B - Exercise



Longest prefix matching

longest prefix match

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

	Destination Address Range	Link interface
200.23.16/21	11001000 00010111 00010*** ********	0
200.23.24/24	11001000 00010111 00011000 ********	1
200.23.24/21	11001000 00010111 00011*** ********	2
	otherwise	3

Exercise:

11001000 00010111 00010110 10100001 which interface?

11001000 00010111 00011000 10101010 which interface?

Longest prefix matching

longest prefix match

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** ********	0
11001000 00010111 00011000 ********	1
11001000 00010111 00011*** ********	2
otherwise	3

match!

examples:

11001000 00010111 00010110 10100001 which interface?

11001000 00010111 00011000 10101010 which interface?

Longest prefix matching

longest prefix match

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** ********	0
11001000 00010111 00011000 ********	1
11001000 00010111 00011*** ********	2
otherwise	3

match!

examples:

11001000 00010110 10100001 which interface?

11001000 00010111 00011000 10101010 which interface?

Longest prefix matching

longest prefix match

when looking for forwarding table entry for given destination address, use *longest* address prefix that matches destination address.

Destination Address Range	Link interface
11001000 00010111 00010*** ********	0
11001000 00010111 00011000 ********	1
11001000 00010111 00011*** ********	2
otherwise	3

match!

examples:

11001000 00010111 00010110 10100001 which interface?

11001000 00010111 00011000 10101010 which interface?

IP addresses: how to get one?

That's actually two questions:

1. Q: How does a *host* get IP address within its network (host part of address)?
2. Q: How does a *network* get IP address for itself (network part of address)

How does *host* get IP address?

- hard-coded by sysadmin in config file (e.g., /etc/rc.config in UNIX)
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from as server
  - "plug-and-play"

Network Layer: “data plane” roadmap

- Network layer functions
- Service model
- Networks layer: Internet
- IP Protocol
- IP Addressing
- DHCP
- Network Address Translation (NAT)



DHCP: Dynamic Host Configuration Protocol

goal: host *dynamically* obtains IP address from network server when it "joins" network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected/on)
- support for mobile users who join/leave network

DHCP overview:

- host broadcasts DHCP discover msg [optional]
- DHCP server responds with DHCP offer msg [optional]
- host requests IP address: DHCP request msg
- DHCP server sends address: DHCP ack msg

DHCP client-server scenario



Typically, DHCP server will be co-located in router, serving all subnets to which router is attached

arriving DHCP client needs address in this network

DHCP client-server scenario



The two steps above can be skipped "if a client remembers and wishes to reuse a previously allocated network address" [RFC 2131]

IP addressing: ISP

Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers http://www.icann.org/

- allocates IP addresses, through 5 regional registries (RRs) (who may then allocate to local registries)
- manages DNS root zone, including delegation of individual TLD (.com, .edu , …) management

Q: are there enough 32-bit IP addresses?

- ICANN allocated last chunk of IPv4 addresses to RRs in 2011
- NAT (next) helps IPv4 address space exhaustion
- IPv6 has 128-bit address space

Network Layer: “data plane” roadmap

- Network layer functions
- Service model
- Networks layer: Internet
- IP Protocol
- IP Addressing
- DHCP
- Network Address Translation (NAT)



NAT: network address translation

NAT: all devices in local network share just one IPv4 address as far as outside world is concerned



all datagrams *leaving* local network have *same* source NAT IP address: 138.76.29.7, but *different* source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

- all devices in local network have 32-bit addresses in a “private” IP address space (10/8, 172.16/12, 192.168/16 prefixes) that can only be used in local network
- advantages:
  - just one IP address needed from provider ISP for *all* devices
  - can change addresses of host in local network without notifying outside world
  - can change ISP without changing addresses of devices in local network
  - security: devices inside local net not directly addressable, visible by outside world

NAT: network address translation

2: NAT router changes datagram source address from 10.0.0.1, 3345 to 138.76.29.7, 5001, updates table



3: reply arrives, destination address: 138.76.29.7, 5001