

2] Conversion - we can convert tuple, set, list into dictionary.

i) Converting tuple into dictionary.

eg. tuple1 = (('name', 'ganesh'), ('age', 25))

```
dict1 = dict(tuple1)
```

```
print(dict1)
```

triple

↓ dict

o/p - { "name": "ganesh",
"age": 25 }

2) Converting list (list of tuples) into dictionary.

list1 = [("name", "jamesh"), ("age", 25)]

dict2 = dict(list1)

point (dict+2)

С. И. "Дом"

o/p - { "name": "jyesh",
"age": 25 }

3] Converting set of elements
as key & default values
as dictionary.

set1 = { "num1", "num2", "num3" }

dict3 = { key : 10 for key in
set1 }

print(dict3)

o/p - { "num1" : 10,
"num2" : 10,
"num3" : 10 }

4) Converting range as keys

4 values as default
in dictionary

eg. `range1 = range(1, 6, 1)`

`dict4 = {key: 10 for key in
range1}`

`print(dict4)`

o/p - { 1 : 10
2 : 10
3 : 10
4 : 10
5 : 10 }

3] Aliasing -

`dict1 = { "mobile": "iphone",
"model": "iphone 18" }`

`dict2 = dict1`

`print(dict2)`

dict1 / dict2

`print(id(dict1))`
`print(id(dict2))` } same 

4] Cloning -

`dict4 = { "mobile": "iphone",
 "model": "iphone18" }`

`dict5 = dict4.copy()`

`print(id(dict4))`
`print(id(dict5))` } different 

5] Searching - 'in' operator

`dict7 = { "name": "ganes h",
 "age": 25,
 "roll-no": 51 }`

print("name" in dict7) → True
print("age" in dict7) → True
print("address" in dict7) → False

6] Identity - 'is' operator

dict8 = { "name": "jamesh",
 "age": 25 }

dict9 = dict8

print(dict8 is dict9) → True

dict10 = dict8.copy()

print(dict8 is dict10) → False

7] Emptiness - 'not' operator

eg. dict11 = { }

print(not dict1) → True

dict12 = {"name": "jamesh"}

print(not dict12) → False

dictionary Methods -

1) update - we can add multiple key-value pairs or update existing key-value pair.

eg. dict1 = {"name": "jamesh"}

dict1.update({"age": 25,
"roll-no": 51})

print(dict1)

o/p - { "name": "ganesha",
"age": 25,
"roll.no": 51 }

2) pop(Key) - we provide Key to the pop method & it delete particular pair.

```
dict1 = { "name": "ganesha",  
          "age": 25,  
          "roll.no": 51 ,  
          "address": "pune" }
```

```
dict1.pop("address")
```

```
print(dict1)
```

o/p - { "name": "ganesh",
"age": 25,
"roll-no": 51 }

3] popitem() - It deletes last
key-value pair of dictionary.

dict1 = { "name": "ganesh",
"age": 25,
"roll-no": 51 ,
"address": "pune" }

dict1.popitem()

print(dict1)

o/p - { "name": "ganesh",
"age": 25,

~~f = {~~
"2011-no" : 51 }

4] clear() - It delete all the
pairs & make empty dictionary.

eg. dict1 = { "name" : "gareeb",
 "age" : 25,
 "2011-no" : 51 ,
 "address" : "pune" }

dict1.clear()

print(dict1) → { }