

Built-in functions - list, tuple, set, dictionary.

Built-in functions on dictionary.

1) `len()` - returns count of key-value pairs

eg. `dict1 = { "name": "ganesh",  
              "age": 25 }`

`print(len(dict1))` → 2

2) `min()` - it returns smallest key which is numerical

eg. `dict2 = { 10 : "a",  
              20 : "b",  
              30 : "c" }`

`print(min(dict2))` → 10

3) `max()` - it returns largest

Key which is numeric

eg. dict3 = { 10 : "a",  
20 : "b",  
30 : "c" }

print(max(dict3)) → 30

4) Sum() - it returns addition of all keys which are numeric.

eg. dict4 = { 10 : "a",  
20 : "b",  
30 : "c" }

print(Sum(dict4)) → 60

5) any() - any() returns true if atleast one key is true

eg. dict5 = { 0 : "a",  
0 : "b",  
0 : "c",  
0 : "d" }

False: "d"]

print(any(dict5)) → False

dict6 = { 0 : "a",  
          0 : "b",  
          1 : "c",  
          False : "d" }

print(any(dict6)) → True

6) all() - all() function returns true if all the keys are true

eg. dict7 = { 1 : "a",  
              2 : "b",  
              3 : "c",  
              0 : "d" }

print(all(dict7)) → False

dict8 = { 1 : "a",  
          : "b",  
          3 : "c",  
          }

1 : "d" }

print (all(dict8)) → True

7) sorted() — it returns sorted keys in list.

eg. dict9 = { 40 : "a",  
20 : "b",  
10 : "c" }

print (sorted(dict9))

o/p- [10, 20, 40]

8) reversed() — It returns keys in reversed order, it provides in list.

eg. dict10 = { 10 : "a",  
20 : "b",  
30 : "c" }

