```
from threading import Thread
def display1():          # t1
    print("This is display1")

def display2():          # t2
    print("This is display2")

def display3():
    print("This is display3")

t1 = Thread(target = display1,
            name = "display1")

t2 = Thread(target = display2,
            name = "display2")

t1.start()
t2.start()
```

1min
1min

Parallelly run 1min

#display1() — 1 min
#display2() — 1 min] - 2 min

display3() # mainThread

- Join() - The join method is used to make the main thread wait until the specified thread completes its execution.

Thread 1 - display1() - 4 sec
Thread 2 - display2() - 2 sec
mainThread - display3() & display4()

t1.start()
t1.join()

Sequentially

t2.start()

t2.join()

executing threads

- t1.start()
  t2.start()
  t1.join()
  t2.join()

Both threads execute concurrently

* Printing thread name

By default - MainThread

Thread 1
Thread 2

t1 = Thread(target = display1,
name = "myThread1")

print(t1.name) → myThread1

print(t1.getName()) → myThread1

* Printing current thread name

import threading.

main_thread = threading.current_thread()

print(main_thread.name) → MainThread

print(main_thread.getName()) → MainThread

* To get the name of current running thread.

print(threading.current_thread().name)

Thread Identity numbers.

i) ident - Python Interpreter assigns the unique ID to thread.
— 10 digit.

Built-in functions in multithreading

1. is_alive() - It is used to check wether thread is currently running or not.

if currently running - True
if not currenty running - False

2. enumerate() - It provides list of all the active thradl.

t1. enumeark() X

This is the function of threading module.

```
import threading
threading.enumerate()
```

3. active_count() — provides count of active thread.

```
print(threading.active_count())
```

4. get_ident() — It provides ID of currently running thread

```
print(threading.get_ident())
```