

Console input - output -

Console input/output allows programs to interact with user.

Input - Receives data from the user.

output - Display result to user.

Input accept :- input()

output display :- print()

Output display - print()

The print function displays o/p to the screen/console.

Syntax :- `print(value1, value2, ...,
sep = " ", end = "\n")`

Print (10) $\longrightarrow$ 10

Print (20.1) $\longrightarrow$ 20.1

Print (1+2j) $\longrightarrow$ 1+2j

Print ("Hello ~~world~~") $\longrightarrow$ Hello world

Print (True) $\longrightarrow$

Input accept - input()

num1 = input()

print(num1)

- input() built in function accepts
input as string.

by default - string data type

10 10.1 "hello"
↓ ↓ ↓
"10" "10.1" "hello"
2+3j → "2+3j"

```
num1 = input("Enter First Number:")
```

```
print(num1)
```

input(5) — 10

str1 = "Hello."

~~str~~2 = "world"

str3 = str1 + str2

print(str3) → "Hello world"

num1 = "10"

num2 = "20"

result = "10" + "20"

print(result)

"1020"

Conversion builtin functions.

"10" → 10 int()

10 → "10" str()

10 → 10.0 float()

str → "10"
num1 = input("Enter first NO:")
new_num1 = int(num1) "10" → 10
num2 = input("Enter second NO:")
new_num2 = int(num2) "20" → 20
result = new_num1 + new_num2
print(result) 10 + 20 = 30

num1 = int(input("Enter First No:"))
"10"

num2 = int(input("Enter Second No:"))
"23"

result = num1 + num2

print("Addition of num1 & num2 is:", result)

`num1 = int("10")` → "10" → 10

```
graph LR; A["num1 = int('10')"] --> B["'10'"]; B --> C((10)); C --> A;
```

`num2 = int("20")` → "20" → 20

```
graph LR; D["num2 = int('20')"] --> E["'20'"]; E --> F((20)); F --> D;
```

`result = num1 + num2`
10 + 20 = 30

```
graph LR; G["result = num1 + num2"] --> H["10 + 20 = 30"];
```

`print("result")` → 30

```
graph LR; I["print('result')"] --> J["30"];
```

Formatted output — ① Comma separated

name = "ganeesh"

age = 25

Print("my name is", name, "and age is",
age)



msg	name var	msg	age var
my name is	ganeesh	and age is	25

② f-string method.

name = "ganesh"

age = 25

Print(f ^① my name is {name} and
age is {age} ^②)

df - my name is ganesh and age is 25

fix var fix var

