Unet VS pluggin

How Webview API requests data from extension layer using MessageHandler

Without MessageHandler



In the extension/webview communication, you send a message, but you won't get a response. You listen to messages coming back, making it a disconnected experience.

With MessageHandler



When requesting data with the message handler, it creates a callback function that returns a promise and identifies it with a **requestId.** The message sends this ID with the message command and payload to the extension listener.

Examples

https://www.eliostruyf.com/simplify-communication-visual-studio-code-extension-webview/

> https://github.com/estruyf/vscode-react-webview-template

---

extension.ts

Initialize **var output : any**

disposable → generateTrace

- output = whatever comes out of generateTrace
- In this case, we use mermaid diagram (string)
- **output = mermaid(sequenceResult[0], sequenceResult[1]);**

disposable1 → openWebview

```
let disposable1 = vscode.commands.registerCommand('vscode-react-webview-starter.openWebview', () => {
    const panel = vscode.window.createWebviewPanel(
        'react-webview',
        'React Webview',
        vscode.ViewColumn.One,
        {
            enableScripts: true,
            retainContextWhenHidden: true
        }
    );
```

Open webview panel nothing much

```
    panel.webview.onDidReceiveMessage(message => {
        const { command, requestId, payload } = message;
        var text : String;
        if (command === "GET_DATA") {
            // Do something with the payload
            if (output == undefined) {
                text = "Upload trace.json file first";
            }
            else {
                text = output;
            }
            // Send a response back to the webview
            panel.webview.postMessage({
                command,
                requestId, // The requestId is used to identify the response
                payload: text
            } as MessageHandlerData<string>);
```

each message has a command, requestID, payload (contains data)

when button is pressed (ignore the other 2 for now)



(src/webview/App.tsx)

this one render the html

```
<button onClick={requestData}>
          Get data from extension
        </button>
```

```
const requestData = () => {
    messageHandler.request<string>('GET_DATA').then((msg) => {
      setMessage(msg);
    });
  };
```

this part im not rlly sure how it works i havent study react

```
const [message, setMessage] = React.useState<string>("");
```

back to extension.ts, payload = text

if output == undefined (havent upload trace.json yet)

text = "Upload trace.json file first”



else

text = output