

# Non-Parametric Methods and Support Vector Machines

Shan-Hung Wu  
*shwu@cs.nthu.edu.tw*

Department of Computer Science,  
National Tsing Hua University, Taiwan

Machine Learning

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $x$ :

# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $x$ :
  - ① Choose the number  $K$  and a distance metric

# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $x$ :
  - ① Choose the number  $K$  and a distance metric
  - ② Find the  $K$  nearest neighbors of a given point  $x$

# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $x$ :
  - ① Choose the number  $K$  and a distance metric
  - ② Find the  $K$  nearest neighbors of a given point  $x$
  - ③ Predict the label of  $x$  by the majority vote (in classification) or average (in regression) of NNs' labels



# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $x$ :
  - ① Choose the number  $K$  and a distance metric
  - ② Find the  $K$  nearest neighbors of a given point  $x$
  - ③ Predict the label of  $x$  by the majority vote (in classification) or average (in regression) of NNs' labels
- Distance metric?

# $K$ -NN Methods I




- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $\mathbf{x}$ :
  - ① Choose the number  $K$  and a distance metric
  - ② Find the  $K$  nearest neighbors of a given point  $\mathbf{x}$
  - ③ Predict the label of  $\mathbf{x}$  by the majority vote (in classification) or average (in regression) of NNs' labels
- Distance metric? E.g., Euclidean distance  $d(\mathbf{x}^{(i)}, \mathbf{x}) = \|\mathbf{x}^{(i)} - \mathbf{x}\|$
- Training algorithm?

# $K$ -NN Methods I

- The  *$K$ -nearest neighbor* ( $K$ -NN) methods are straightforward, but a fundamentally different way, to predict the label of a data point  $\mathbf{x}$ :
  - ① Choose the number  $K$  and a distance metric
  - ② Find the  $K$  nearest neighbors of a given point  $\mathbf{x}$
  - ③ Predict the label of  $\mathbf{x}$  by the majority vote (in classification) or average (in regression) of NNs' labels
- Distance metric? E.g., Euclidean distance  $d(\mathbf{x}^{(i)}, \mathbf{x}) = \|\mathbf{x}^{(i)} - \mathbf{x}\|$
- Training algorithm? Simply “remember”  $\mathbb{X}$  in storage

# $K$ -NN Methods II

- Could be very complex
- $K$  is a hyperparameter controlling the model complexity



# Non-Parametric Methods

- $K$ -NN method is a special case of *non-parametric* (or *memory-based*) methods

# Non-Parametric Methods

- $K$ -NN method is a special case of *non-parametric* (or *memory-based*) methods
  - Non-parametric in the sense that  $f$  are not described by only few parameters

# Non-Parametric Methods

- $K$ -NN method is a special case of *non-parametric* (or *memory-based*) methods
  - Non-parametric in the sense that  $f$  are not described by only few parameters 之前都用 $w$ 來代表 $f$  即為parametric
  - Memory-based in that all data (rather than just parameters) need to be memorized during the training process

# Non-Parametric Methods

- $K$ -NN method is a special case of *non-parametric* (or *memory-based*) methods
  - Non-parametric in the sense that  $f$  are not described by only few parameters
  - Memory-based in that all data (rather than just parameters) need to be memorized during the training process
- $K$ -NN is also a *lazy* method since the prediction function  $f$  is obtained only before the prediction



# Non-Parametric Methods

- $K$ -NN method is a special case of *non-parametric* (or *memory-based*) methods
  - Non-parametric in the sense that  $f$  are not described by only few parameters
  - Memory-based in that all data (rather than just parameters) need to be memorized during the training process
- $K$ -NN is also a *lazy* method since the prediction function  $f$  is obtained only before the prediction
  - Motivates the development of other *local models*

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)
  - Readily extensible to multi-class and regression problems

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)
  - Readily extensible to multi-class and regression problems
- Cons:
  - Storage demanding

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)
  - Readily extensible to multi-class and regression problems
- Cons:
  - Storage demanding
  - Sensitive to outliers

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)
  - Readily extensible to multi-class and regression problems
- Cons:
  - Storage demanding
  - Sensitive to outliers
  - Sensitive to irrelevant data features (vs. decision trees)

# Pros & Cons

- Pros:
  - Almost no assumption on  $f$  other than *smoothness*
    - High capacity/complexity
    - High accuracy given a large training set
  - Supports online training (by simply memorizing)
  - Readily extensible to multi-class and regression problems
- Cons:
  - Storage demanding
  - Sensitive to outliers
  - Sensitive to irrelevant data features (vs. decision trees)
  - Needs to deal with missing data (e.g., special distances)



# Pros & Cons

- Pros:

- Almost no assumption on  $f$  other than *smoothness*
  - High capacity/complexity
  - High accuracy given a large training set
- Supports online training (by simply memorizing)
- Readily extensible to multi-class and regression problems

- Cons:

- Storage demanding
  - Sensitive to outliers
  - Sensitive to irrelevant data features (vs. decision trees)
  - Needs to deal with missing data (e.g., special distances)
  - Computationally expensive:  $O(ND)$  time for making each prediction
    - Can speed up with index and/or approximation
- 每次預測都要看這個 $x$ 和其他人的距離多少 $O(ND)$

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Parzen Windows and Kernels

- Binary KNN classifier:

$$f(\mathbf{x}) = \text{sign} \left( \sum_{i: \mathbf{x}^{(i)} \in \text{KNN}(\mathbf{x})} y^{(i)} \right)$$

- The “radius” of voter boundary depends on the input  $\mathbf{x}$

# Parzen Windows and Kernels

- Binary KNN classifier:

$$f(\mathbf{x}) = \text{sign} \left( \sum_{i: \mathbf{x}^{(i)} \in \text{KNN}(\mathbf{x})} y^{(i)} \right)$$

- The “radius” of voter boundary depends on the input  $\mathbf{x}$
- We can instead use the *Parzen window* with a fixed radius:

$$f(\mathbf{x}) = \text{sign} \left( \sum_i y^{(i)} \mathbf{1}(\mathbf{x}^{(i)}; \|\mathbf{x}^{(i)} - \mathbf{x}\| \leq R) \right)$$

# Parzen Windows and Kernels

- Binary KNN classifier:

$$f(\mathbf{x}) = \text{sign} \left( \sum_{i: \mathbf{x}^{(i)} \in \text{KNN}(\mathbf{x})} y^{(i)} \right)$$

- The “radius” of voter boundary depends on the input  $\mathbf{x}$
- We can instead use the **Parzen window** with a fixed radius:

$$f(\mathbf{x}) = \text{sign} \left( \sum_i y^{(i)} \mathbf{1}(\mathbf{x}^{(i)}; \|\mathbf{x}^{(i)} - \mathbf{x}\| \leq R) \right)$$

- Parzen windows also replace the hard boundary with a soft one:

$$f(\mathbf{x}) = \text{sign} \left( \sum_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) \right)$$

- $k(\mathbf{x}^{(i)}, \mathbf{x})$  is a **radial basis function (RBF) kernel** whose value decreases along space radiating outward from  $\mathbf{x}$

# Parzen Windows and Kernels

- Binary KNN classifier:

$$f(\mathbf{x}) = \text{sign} \left( \sum_{i: \mathbf{x}^{(i)} \in \text{KNN}(\mathbf{x})} y^{(i)} \right)$$

- The “radius” of voter boundary depends on the input  $\mathbf{x}$
- We can instead use the **Parzen window** with a fixed radius:

$$f(\mathbf{x}) = \text{sign} \left( \sum_i y^{(i)} \mathbf{1}(\mathbf{x}^{(i)}; \|\mathbf{x}^{(i)} - \mathbf{x}\| \leq R) \right)$$

- Parzen windows also replace the hard boundary with a soft one:

$$f(\mathbf{x}) = \text{sign} \left( \sum_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) \right)$$

- $k(\mathbf{x}^{(i)}, \mathbf{x})$  is a **radial basis function (RBF) kernel** whose value decreases along space radiating outward from  $\mathbf{x}$

# Common RBF Kernels

- How to act like soft  $K$ -NN?

# Common RBF Kernels

- How to act like soft  $K$ -NN?
- Gaussian RBF kernel:

$$k(\mathbf{x}^{(i)}, \mathbf{x}) = \mathcal{N}(\mathbf{x}^{(i)} - \mathbf{x}; \mathbf{0}, \sigma^2 \mathbf{I})$$



# Common RBF Kernels

- How to act like soft  $K$ -NN?
- Gaussian RBF kernel:

$$k(\mathbf{x}^{(i)}, \mathbf{x}) = \mathcal{N}(\mathbf{x}^{(i)} - \mathbf{x}; \mathbf{0}, \sigma^2 \mathbf{I})$$

- Or simply

$$k(\mathbf{x}^{(i)}, \mathbf{x}) = \exp\left(-\gamma \|\mathbf{x}^{(i)} - \mathbf{x}\|^2\right)$$

- $\gamma \geq 0$  (or  $\sigma^2$ ) is a hyperparameter controlling the smoothness of  $f$

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Locally Weighted Linear Regression

- In addition to the majority voting and average, we can define *local models* for lazy predictions

找出要的小範圍data後  
可以不只用投票或平均

甚至可以套用model來做predict

# Locally Weighted Linear Regression

- In addition to the majority voting and average, we can define *local models* for lazy predictions
- E.g., in (eager) linear regression, we find  $\mathbf{w} \in \mathbb{R}^{D+1}$  that minimizes SSE:

$$\arg \min_{\mathbf{w}} \sum_i (y^{(i)} - \mathbf{w}^\top \mathbf{x}^{(i)})^2$$

- Local model: to find  $\mathbf{w}$  minimizing *SSE local to the point  $\mathbf{x}$  we want to predict*:

$$\arg \min_{\mathbf{w}} \sum_i k(\mathbf{x}^{(i)}, \mathbf{x}) (y^{(i)} - \mathbf{w}^\top \mathbf{x}^{(i)})^2$$

- $k(\cdot, \cdot) \in \mathbb{R}$  is an RBF kernel

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Kernel Machines

- *Kernel machines:*

$$f(\mathbf{x}) = \sum_{i=1}^N c_i k(\mathbf{x}^{(i)}, \mathbf{x}) + c_0$$

- For example:
  - Parzen windows:  $c_i = y^{(i)}$  and  $c_0 = 0$
  - Locally weighted linear regression:  $c_i = (y^{(i)} - \mathbf{w}^\top \mathbf{x}^{(i)})^2$  and  $c_0 = 0$

# Kernel Machines

- *Kernel machines:*

$$f(\mathbf{x}) = \sum_{i=1}^N c_i k(\mathbf{x}^{(i)}, \mathbf{x}) + c_0$$

- For example:
  - Parzen windows:  $c_i = y^{(i)}$  and  $c_0 = 0$
  - Locally weighted linear regression:  $c_i = (y^{(i)} - \mathbf{w}^\top \mathbf{x}^{(i)})^2$  and  $c_0 = 0$
- The variable  $\mathbf{c} \in \mathbb{R}^N$  can be learned in either an eager or lazy manner
- Pros: complex, but highly accurate if regularized well

# Sparse Kernel Machines

- To make a prediction, we need to store *all* examples
- May be infeasible due to
  - Large dataset ( $N$ )
  - Time limit
  - Space limit



# Sparse Kernel Machines

- To make a prediction, we need to store *all* examples
- May be infeasible due to
  - Large dataset ( $N$ )
  - Time limit
  - Space limit
- Can we make  $\mathbf{c}$  *sparse*?
  - I.e., to make  $c_i \neq 0$  for only a small fraction of examples called *support vectors*
- How?

# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Separating Hyperplane I

- Model:  $\mathbb{F} = \{f : f(\mathbf{x}; \mathbf{w}, b) = \mathbf{w}^\top \mathbf{x} + b\}$ 
  - A collection of hyperplanes
- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x}))$

# Separating Hyperplane I

- Model:  $\mathbb{F} = \{f : f(\mathbf{x}; \mathbf{w}, b) = \mathbf{w}^\top \mathbf{x} + b\}$ 
  - A collection of hyperplanes
- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x}))$
- Training: to find  $\mathbf{w}$  and  $b$  such that

$$\begin{aligned} \mathbf{w}^\top \mathbf{x}^{(i)} + b &\geq 0, & \text{if } y^{(i)} = 1 \\ \mathbf{w}^\top \mathbf{x}^{(i)} + b &\leq 0, & \text{if } y^{(i)} = -1 \end{aligned}$$

# Separating Hyperplane I

- Model:  $\mathbb{F} = \{f : f(\mathbf{x}; \mathbf{w}, b) = \mathbf{w}^\top \mathbf{x} + b\}$ 
  - A collection of hyperplanes
- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x}))$
- Training: to find  $\mathbf{w}$  and  $b$  such that


$$\begin{aligned}\mathbf{w}^\top \mathbf{x}^{(i)} + b &\geq 0, & \text{if } y^{(i)} = 1 \\ \mathbf{w}^\top \mathbf{x}^{(i)} + b &\leq 0, & \text{if } y^{(i)} = -1\end{aligned}$$

or simply

$$y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq 0$$


# Separating Hyperplane II

- There are many feasible  $w$ 's and  $b$ 's when the classes are linearly separable
- Which hyperplane is the best?




# Support Vector Classification

- **Support vector classifier** (SVC) picks one with **largest margin**:
  - $y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq a$  for all  $i$
  - Margin:  $2a/\|\mathbf{w}\|$  [Homework]



# Support Vector Classification

- **Support vector classifier** (SVC) picks one with **largest margin**:
  - $y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq a$  for all  $i$
  - Margin:  $2a/\|\mathbf{w}\|$  [Homework]



- With loss of generality, we let  $a = 1$  and solve the problem:

$$\begin{aligned} & \arg \min_{\mathbf{w}, b} \frac{1}{2} \|\mathbf{w}\|^2 \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq 1, \forall i \end{aligned}$$



# Outline

## 1 Non-Parametric Methods


- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick


# Overlapping Classes

- In practice, classes may be overlapping
  - Due to, e.g., noises or outliers



# Overlapping Classes

- In practice, classes may be overlapping
  - Due to, e.g., noises or outliers



- The problem

$$\begin{aligned} & \arg \min_{\mathbf{w}, b} \frac{1}{2} \|\mathbf{w}\|^2 \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq 1, \forall i \end{aligned}$$

has no solution in this case. How to fix this?


# Slacks

- SVC tolerates *slacks* that fall outside of the regions they ought to be
- Problem:

$$\arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^N \xi_i$$

subject to  $y^{(i)}(\mathbf{w}^\top \mathbf{x}^{(i)} + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0, \forall i$


- Favors large margin but also fewer slacks




# Hyperparameter $C$

$$\arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^N \xi_i$$

- The hyperparameter  $C$  controls the tradeoff between
  - Maximizing margin
  - Minimizing number of slacks



Large value for  
parameter  $C$




Small value for  
parameter  $C$


# Hyperparameter $C$

$$\arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^N \xi_i$$

- The hyperparameter  $C$  controls the tradeoff between
  - Maximizing margin
  - Minimizing number of slacks



Large value for  
parameter  $C$



Small value for  
parameter  $C$

- Provides a geometric explanation to the weight decay

# Outline

## 1 Non-Parametric Methods


- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Nonlinearly Separable Classes


- In practice, classes may be nonlinearly separable





# Nonlinearly Separable Classes

- In practice, classes may be nonlinearly separable



- SVC (with slacks) gives “bad” hyperplanes due to underfitting
- How to make it nonlinear?

# Feature Augmentation


- Recall that in polynomial regression, we augment data features to make a linear regressor nonlinear

# Feature Augmentation

- Recall that in polynomial regression, we augment data features to make a linear regressor nonlinear
- We can define a function  $\Phi(\cdot)$  that maps each data point to a high dimensional space:

$$\arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i$$

subject to  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0, \forall i$



# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Time Complexity

- Nonlinear SVC:

$$\begin{aligned} & \arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0, \forall i \end{aligned}$$

- The higher augmented feature dimension, the more variables in  $\mathbf{w}$  to solve

# Time Complexity

- Nonlinear SVC:

$$\begin{aligned} & \arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0, \forall i \end{aligned}$$

- The higher augmented feature dimension, the more variables in  $\mathbf{w}$  to solve
- Can we solve  $\mathbf{w}$  in time complexity that is independent with the mapped dimension?

# Dual Problem

- Primal problem:

$$\begin{aligned} & \arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0, \forall i \end{aligned}$$

- Dual problem:

$$\begin{aligned} & \arg \max_{\alpha, \beta} \min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta) \\ & \text{subject to } \alpha \geq \mathbf{0}, \beta \geq \mathbf{0} \end{aligned}$$

where  $L(\mathbf{w}, b, \xi, \alpha, \beta) =$   
 $\frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$

# Dual Problem

- Primal problem:

$$\begin{aligned} & \arg \min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i \\ & \text{subject to } y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0, \forall i \end{aligned}$$

- Dual problem:

$$\begin{aligned} & \arg \max_{\alpha, \beta} \min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta) \\ & \text{subject to } \alpha \geq \mathbf{0}, \beta \geq \mathbf{0} \end{aligned}$$

where  $L(\mathbf{w}, b, \xi, \alpha, \beta) =$   
 $\frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$

- Primal problem is convex, so **strong duality** holds



# Solving Dual Problem I

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- The inner problem

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta)$$

is convex in terms of  $\mathbf{w}$ ,  $b$ , and  $\xi$

- Let's solve it analytically:

# Solving Dual Problem I

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- The inner problem

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta)$$

is convex in terms of  $\mathbf{w}$ ,  $b$ , and  $\xi$

- Let's solve it analytically:
- $\frac{\partial L}{\partial \mathbf{w}} = \mathbf{w} - \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)}) = \mathbf{0} \Rightarrow \mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$

# Solving Dual Problem I

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- The inner problem

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta)$$

is convex in terms of  $\mathbf{w}$ ,  $b$ , and  $\xi$

- Let's solve it analytically:
- $\frac{\partial L}{\partial \mathbf{w}} = \mathbf{w} - \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)}) = \mathbf{0} \Rightarrow \mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- $\frac{\partial L}{\partial b} = \sum_i \alpha_i y^{(i)} = 0$

# Solving Dual Problem I

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- The inner problem

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta)$$

is convex in terms of  $\mathbf{w}$ ,  $b$ , and  $\xi$

- Let's solve it analytically:
- $\frac{\partial L}{\partial \mathbf{w}} = \mathbf{w} - \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)}) = \mathbf{0} \Rightarrow \mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- $\frac{\partial L}{\partial b} = \sum_i \alpha_i y^{(i)} = 0$
- $\frac{\partial L}{\partial \xi_i} = C - \alpha_i - \beta_i = 0 \Rightarrow \beta_i = C - \alpha_i$

# Solving Dual Problem II

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- Substituting  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$  and  $\beta_i = C - \alpha_i$  in  $L(\mathbf{w}, b, \xi, \alpha, \beta)$ :

$$L(\mathbf{w}, b, \xi, \alpha, \beta) = \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) - b \sum_i \alpha_i y^{(i)},$$

# Solving Dual Problem II

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- Substituting  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$  and  $\beta_i = C - \alpha_i$  in  $L(\mathbf{w}, b, \xi, \alpha, \beta)$ :

$$L(\mathbf{w}, b, \xi, \alpha, \beta) = \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) - b \sum_i \alpha_i y^{(i)},$$

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta) = \begin{cases} \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) , \\ \quad \text{if } \sum_i \alpha_i y^{(i)} = 0, \\ -\infty, & \text{otherwise} \end{cases}$$

# Solving Dual Problem II

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- Substituting  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$  and  $\beta_i = C - \alpha_i$  in  $L(\mathbf{w}, b, \xi, \alpha, \beta)$ :

$$L(\mathbf{w}, b, \xi, \alpha, \beta) = \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) - b \sum_i \alpha_i y^{(i)},$$

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta) = \begin{cases} \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) , \\ \quad \text{if } \sum_i \alpha_i y^{(i)} = 0, \\ -\infty, & \text{otherwise} \end{cases}$$

- Outer maximization problem:

$$\begin{aligned} & \arg \max_{\alpha} \mathbf{1}^\top \alpha - \frac{1}{2} \alpha^\top \mathbf{K} \alpha \\ & \text{subject to } \mathbf{0} \leq \alpha \leq C \mathbf{1} \text{ and } \mathbf{y}^\top \alpha = 0 \end{aligned}$$

- $K_{i,j} = y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$

# Solving Dual Problem II

- $L(\mathbf{w}, b, \xi, \alpha, \beta) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_i \xi_i + \sum_i \alpha_i (1 - y^{(i)} (\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) + \sum_i \beta_i (-\xi_i)$
- Substituting  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$  and  $\beta_i = C - \alpha_i$  in  $L(\mathbf{w}, b, \xi, \alpha, \beta)$ :

$$L(\mathbf{w}, b, \xi, \alpha, \beta) = \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) - b \sum_i \alpha_i y^{(i)},$$

$$\min_{\mathbf{w}, b, \xi} L(\mathbf{w}, b, \xi, \alpha, \beta) = \begin{cases} \sum_i \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)}) , \\ \quad \text{if } \sum_i \alpha_i y^{(i)} = 0, \\ -\infty, & \text{otherwise} \end{cases}$$

- Outer maximization problem:

$$\begin{aligned} & \arg \max_{\alpha} \mathbf{1}^\top \alpha - \frac{1}{2} \alpha^\top \mathbf{K} \alpha \\ & \text{subject to } \mathbf{0} \leq \alpha \leq C \mathbf{1} \text{ and } \mathbf{y}^\top \alpha = 0 \end{aligned}$$

- $K_{i,j} = y^{(i)} y^{(j)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
- $\beta_i = C - \alpha_i \geq 0$  implies  $\alpha_i \leq C$



# Solving Dual Problem II

- Dual minimization problem of SVC:

$$\begin{aligned} & \arg \min_{\alpha} \frac{1}{2} \alpha^{\top} \mathbf{K} \alpha - \mathbf{1}^{\top} \alpha \\ & \text{subject to } \mathbf{0} \leq \alpha \leq C \mathbf{1} \text{ and } \mathbf{y}^{\top} \alpha = 0 \end{aligned}$$

- Number of variables to solve?

# Solving Dual Problem II

- Dual minimization problem of SVC:

$$\begin{aligned} & \arg \min_{\alpha} \frac{1}{2} \alpha^{\top} \mathbf{K} \alpha - \mathbf{1}^{\top} \alpha \\ & \text{subject to } \mathbf{0} \leq \alpha \leq C \mathbf{1} \text{ and } \mathbf{y}^{\top} \alpha = 0 \end{aligned}$$

- Number of variables to solve?  $N$  instead of augmented feature dimension

# Solving Dual Problem II

- Dual minimization problem of SVC:

$$\begin{aligned} & \arg \min_{\alpha} \frac{1}{2} \alpha^{\top} \mathbf{K} \alpha - \mathbf{1}^{\top} \alpha \\ & \text{subject to } \mathbf{0} \leq \alpha \leq C \mathbf{1} \text{ and } \mathbf{y}^{\top} \alpha = 0 \end{aligned}$$

- Number of variables to solve?  $N$  instead of augmented feature dimension
- In practice, this problem is solved by specialized solvers such as the sequential minimal optimization (SMO) [3]
  - As  $\mathbf{K}$  is usually ill-conditioned

# Making Predictions

- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x})) = \text{sign}(\mathbf{w}^\top \mathbf{x} + b)$

# Making Predictions

- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x})) = \text{sign}(\mathbf{w}^\top \mathbf{x} + b)$
- We have  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- How to obtain  $b$ ?

# Making Predictions

- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x})) = \text{sign}(\mathbf{w}^\top \mathbf{x} + b)$
- We have  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- How to obtain  $b$ ?
- By the complementary slackness of KKT conditions, we have:

$$\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0 \text{ and } \beta_i(-\xi_i) = 0$$

# Making Predictions

- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x})) = \text{sign}(\mathbf{w}^\top \mathbf{x} + b)$
- We have  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- How to obtain  $b$ ?
- By the complementary slackness of KKT conditions, we have:

$$\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0 \text{ and } \beta_i(-\xi_i) = 0$$

- For any  $\mathbf{x}^{(i)}$  having  $0 < \alpha_i < C$ , we have

$$\beta_i = C - \alpha_i > 0 \Rightarrow \xi_i = 0,$$

$$(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0 \Rightarrow b = y^{(i)} - \mathbf{w}^\top \Phi(\mathbf{x}^{(i)})$$

# Making Predictions

- Prediction:  $\hat{y} = \text{sign}(f(\mathbf{x})) = \text{sign}(\mathbf{w}^\top \mathbf{x} + b)$
- We have  $\mathbf{w} = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})$
- How to obtain  $b$ ?
- By the complementary slackness of KKT conditions, we have:

$$\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0 \text{ and } \beta_i(-\xi_i) = 0$$

- For any  $\mathbf{x}^{(i)}$  having  $0 < \alpha_i < C$ , we have

$$\beta_i = C - \alpha_i > 0 \Rightarrow \xi_i = 0,$$

$$(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0 \Rightarrow b = y^{(i)} - \mathbf{w}^\top \Phi(\mathbf{x}^{(i)})$$

- In practice, we usually take the average over **all**  $\mathbf{x}^{(i)}$ 's having  $0 < \alpha_i < C$  to avoid numeric error



# Outline

## 1 Non-Parametric Methods

- $K$ -NN
- Parzen Windows
- Local Models

## 2 Support Vector Machines

- SVC
- Slacks
- Nonlinear SVC
- Dual Problem
- Kernel Trick

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$
- Time complexity?

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$
- Time complexity?
- If we choose  $\Phi$  carefully, we can evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) = k(\mathbf{x}^{(i)}, \mathbf{x})$  efficiently

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$
- Time complexity?
- If we choose  $\Phi$  carefully, we can evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) = k(\mathbf{x}^{(i)}, \mathbf{x})$  efficiently
- Polynomial kernel:  $k(\mathbf{a}, \mathbf{b}) = (\mathbf{a}^\top \mathbf{b} / \alpha + \beta)^\gamma$ 
  - E.g., let  $\alpha = 1$ ,  $\beta = 1$ ,  $\gamma = 2$  and  $\mathbf{a} \in \mathbb{R}^2$ , then  $\Phi(\mathbf{a}) = [1, \sqrt{2}a_1, \sqrt{2}a_2, a_1^2, a_2^2, \sqrt{2}a_1a_2]^\top \in \mathbb{R}^6$

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$
- Time complexity?
- If we choose  $\Phi$  carefully, we can evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) = k(\mathbf{x}^{(i)}, \mathbf{x})$  efficiently
- Polynomial kernel:  $k(\mathbf{a}, \mathbf{b}) = (\mathbf{a}^\top \mathbf{b} / \alpha + \beta)^\gamma$ 
  - E.g., let  $\alpha = 1$ ,  $\beta = 1$ ,  $\gamma = 2$  and  $\mathbf{a} \in \mathbb{R}^2$ , then  
 $\Phi(\mathbf{a}) = [1, \sqrt{2}a_1, \sqrt{2}a_2, a_1^2, a_2^2, \sqrt{2}a_1a_2]^\top \in \mathbb{R}^6$
- Gaussian RBF kernel:  $k(\mathbf{a}, \mathbf{b}) = \exp(-\gamma \|\mathbf{a} - \mathbf{b}\|^2)$ ,  $\gamma \geq 0$ 
  - $k(\mathbf{a}, \mathbf{b}) = \exp(-\gamma \|\mathbf{a}\|^2 + 2\gamma \mathbf{a}^\top \mathbf{b} - \gamma \|\mathbf{b}\|^2) = \exp(-\gamma \|\mathbf{a}\|^2 - \gamma \|\mathbf{b}\|^2) (1 + \frac{2\gamma \mathbf{a}^\top \mathbf{b}}{1!} + \frac{(2\gamma \mathbf{a}^\top \mathbf{b})^2}{2!} + \dots)$
  - Let  $\mathbf{a} \in \mathbb{R}^2$ , then  $\Phi(\mathbf{a}) = \exp(-\gamma \|\mathbf{a}\|^2) [1, \sqrt{\frac{2\gamma}{1!}}a_1, \sqrt{\frac{2\gamma}{1!}}a_2, \sqrt{\frac{2\gamma}{2!}}a_1^2, \sqrt{\frac{2\gamma}{2!}}a_2^2, 2\sqrt{\frac{\gamma}{2!}}a_1a_2, \dots]^\top \in \mathbb{R}^\infty$

# Kernel as Inner Product

- We need to evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$  when
  - Solving dual problem of SVC, where  $K_{i,j} = y^{(i)}y^{(j)}\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}^{(j)})$
  - Making a prediction, where  $f(\mathbf{x}) = \mathbf{w}^\top \mathbf{x} + b = \sum_i \alpha_i y^{(i)} \Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) + b$
- Time complexity?
- If we choose  $\Phi$  carefully, we can evaluate  $\Phi(\mathbf{x}^{(i)})^\top \Phi(\mathbf{x}) = k(\mathbf{x}^{(i)}, \mathbf{x})$  efficiently
- Polynomial kernel:  $k(\mathbf{a}, \mathbf{b}) = (\mathbf{a}^\top \mathbf{b} / \alpha + \beta)^\gamma$ 
  - E.g., let  $\alpha = 1$ ,  $\beta = 1$ ,  $\gamma = 2$  and  $\mathbf{a} \in \mathbb{R}^2$ , then  
 $\Phi(\mathbf{a}) = [1, \sqrt{2}a_1, \sqrt{2}a_2, a_1^2, a_2^2, \sqrt{2}a_1a_2]^\top \in \mathbb{R}^6$
- Gaussian RBF kernel:  $k(\mathbf{a}, \mathbf{b}) = \exp(-\gamma \|\mathbf{a} - \mathbf{b}\|^2)$ ,  $\gamma \geq 0$ 
  - $k(\mathbf{a}, \mathbf{b}) = \exp(-\gamma \|\mathbf{a}\|^2 + 2\gamma \mathbf{a}^\top \mathbf{b} - \gamma \|\mathbf{b}\|^2) = \exp(-\gamma \|\mathbf{a}\|^2 - \gamma \|\mathbf{b}\|^2) (1 + \frac{2\gamma \mathbf{a}^\top \mathbf{b}}{1!} + \frac{(2\gamma \mathbf{a}^\top \mathbf{b})^2}{2!} + \dots)$
  - Let  $\mathbf{a} \in \mathbb{R}^2$ , then  $\Phi(\mathbf{a}) = \exp(-\gamma \|\mathbf{a}\|^2) [1, \sqrt{\frac{2\gamma}{1!}}a_1, \sqrt{\frac{2\gamma}{1!}}a_2, \sqrt{\frac{2\gamma}{2!}}a_1^2, \sqrt{\frac{2\gamma}{2!}}a_2^2, 2\sqrt{\frac{\gamma}{2!}}a_1a_2, \dots]^\top \in \mathbb{R}^\infty$

# Kernel Trick

- If we choose  $\Phi$  induced by Polynomial or Gaussian RBF kernel, then

$$K_{i,j} = y^{(i)}y^{(j)}k(\mathbf{x}^{(i)}, \mathbf{x})$$

takes only  $O(D)$  time to evaluate, and

$$f(\mathbf{x}) = \sum_i \alpha_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) + b$$

takes  $O(ND)$  time



# Kernel Trick

- If we choose  $\Phi$  induced by Polynomial or Gaussian RBF kernel, then

$$K_{i,j} = y^{(i)}y^{(j)}k(\mathbf{x}^{(i)}, \mathbf{x})$$

takes only  $O(D)$  time to evaluate, and

$$f(\mathbf{x}) = \sum_i \alpha_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) + b$$

takes  $O(ND)$  time

- Independent with the augmented feature dimension

# Kernel Trick

- If we choose  $\Phi$  induced by Polynomial or Gaussian RBF kernel, then

$$K_{i,j} = y^{(i)}y^{(j)}k(\mathbf{x}^{(i)}, \mathbf{x})$$

takes only  $O(D)$  time to evaluate, and

$$f(\mathbf{x}) = \sum_i \alpha_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) + b$$

takes  $O(ND)$  time

- Independent with the augmented feature dimension
- $\alpha$ ,  $\beta$ , and  $\gamma$  are new hyperparameters

# Sparse Kernel Machines

- SVC is a kernel machine:

$$f(\mathbf{x}) = \sum_i \alpha_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) + b$$


- It is surprising that SVC works like  $K$ -NN in some sense

# Sparse Kernel Machines

- SVC is a kernel machine:

$$f(\mathbf{x}) = \sum_i \alpha_i y^{(i)} k(\mathbf{x}^{(i)}, \mathbf{x}) + b$$

- It is surprising that SVC works like  $K$ -NN in some sense
- However, SVC is a *sparse* kernel machine
- Only the *slacks* become the support vectors ( $\alpha_i > 0$ )



# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$

# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:

# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:

# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:
- Non SVs ( $\alpha_i = 0$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1$  (usually strict)
- **Free SVs** ( $0 < \alpha_i < C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) = 1$
- **Bounded SVs** ( $\alpha_i = C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \leq 1$  (usually strict)



# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:
- Non SVs ( $\alpha_i = 0$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1$  (usually strict)
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i \leq 0$
  - Since  $\beta_i = C - \alpha_i \neq 0$ , we have  $\xi_i = 0$
- **Free SVs** ( $0 < \alpha_i < C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) = 1$
- **Bounded SVs** ( $\alpha_i = C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \leq 1$  (usually strict)

# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:
- Non SVs ( $\alpha_i = 0$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1$  (usually strict)
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i \leq 0$
  - Since  $\beta_i = C - \alpha_i \neq 0$ , we have  $\xi_i = 0$
- **Free SVs** ( $0 < \alpha_i < C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) = 1$ 
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i = 0$
  - Since  $\beta_i = C - \alpha_i \neq 0$ , we have  $\xi_i = 0$
- **Bounded SVs** ( $\alpha_i = C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \leq 1$  (usually strict)

# KKT Conditions and Types of SVs

- By KKT conditions, we have:
  - Primal feasibility:  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1 - \xi_i$  and  $\xi_i \geq 0$
  - Complementary slackness:  $\alpha_i(1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i) = 0$  and  $\beta_i(-\xi_i) = 0$
- Depending on the value of  $\alpha_i$ , each example  $\mathbf{x}^{(i)}$  can be:
- Non SVs ( $\alpha_i = 0$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \geq 1$  (usually strict)
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i \leq 0$
  - Since  $\beta_i = C - \alpha_i \neq 0$ , we have  $\xi_i = 0$
- **Free SVs** ( $0 < \alpha_i < C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) = 1$ 
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i = 0$
  - Since  $\beta_i = C - \alpha_i \neq 0$ , we have  $\xi_i = 0$
- **Bounded SVs** ( $\alpha_i = C$ ):  $y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) \leq 1$  (usually strict)
  - $1 - y^{(i)}(\mathbf{w}^\top \Phi(\mathbf{x}^{(i)}) + b) - \xi_i = 0$
  - Since  $\beta_i = 0$ , we have  $\xi_i \geq 0$

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set
- Cons:
  - Nonlinear SVC not scalable to large tasks
    - Takes  $O(N^2) \sim O(N^3)$  time to train using SMO in LIBSVM [1]
    - On the other hand, linear SVC takes  $O(ND)$  time

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set
- Cons:
  - Nonlinear SVC not scalable to large tasks
    - Takes  $O(N^2) \sim O(N^3)$  time to train using SMO in LIBSVM [1]
    - On the other hand, linear SVC takes  $O(ND)$  time
  - Kernel matrix  $\mathbf{K}$  requires  $O(N^2)$  space
    - In practice, we cache only a small portion of  $\mathbf{K}$  in memory



# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set
- Cons:
  - Nonlinear SVC not scalable to large tasks
    - Takes  $O(N^2) \sim O(N^3)$  time to train using SMO in LIBSVM [1]
    - On the other hand, linear SVC takes  $O(ND)$  time
  - Kernel matrix  $\mathbf{K}$  requires  $O(N^2)$  space
    - In practice, we cache only a small portion of  $\mathbf{K}$  in memory
  - Sensitive to irrelevant data features (vs. decision trees)

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set
- Cons:
  - Nonlinear SVC not scalable to large tasks
    - Takes  $O(N^2) \sim O(N^3)$  time to train using SMO in LIBSVM [1]
    - On the other hand, linear SVC takes  $O(ND)$  time
  - Kernel matrix  $\mathbf{K}$  requires  $O(N^2)$  space
    - In practice, we cache only a small portion of  $\mathbf{K}$  in memory
  - Sensitive to irrelevant data features (vs. decision trees)
  - Non-trivial hyperparameter tuning
    - The effect of a  $(C, \gamma)$  combination is unknown in advance
    - Usually done by **grid search**

# Remarks I

- Pros of SVC:
  - Global optimality (convex problem)
  - Works with different kernels (linear, Polynomial, Gaussian RBF, etc.)
  - Works well with small training set
- Cons:
  - Nonlinear SVC not scalable to large tasks
    - Takes  $O(N^2) \sim O(N^3)$  time to train using SMO in LIBSVM [1]
    - On the other hand, linear SVC takes  $O(ND)$  time
  - Kernel matrix  $\mathbf{K}$  requires  $O(N^2)$  space
    - In practice, we cache only a small portion of  $\mathbf{K}$  in memory
  - Sensitive to irrelevant data features (vs. decision trees)
  - Non-trivial hyperparameter tuning
    - The effect of a  $(C, \gamma)$  combination is unknown in advance
    - Usually done by **grid search**
  - Separate only 2 classes
    - Usually wrapped by the 1-vs-1 technique for multi-class classification

# Remarks II

- Does nonlinear SVC always perform better than linear SVC?

# Remarks II

- Does nonlinear SVC always perform better than linear SVC? **No**
- Choose linear SVC (e.g., LIBLINEAR [2]) when
  - $N$  is large (since nonlinear SVC does not scale), or
  - $D$  is large (since classes may already be linearly separable)

# Reference I

- [1] Chih-Chung Chang and Chih-Jen Lin.  
Libsvm: a library for support vector machines.  
*ACM Transactions on Intelligent Systems and Technology (TIST)*,  
2(3):27, 2011.
- [2] Rong-En Fan, Kai-Wei Chang, Cho-Jui Hsieh, Xiang-Rui Wang, and  
Chih-Jen Lin.  
Liblinear: A library for large linear classification.  
*Journal of machine learning research*, 9(Aug):1871–1874, 2008.
- [3] John Platt et al.  
Sequential minimal optimization: A fast algorithm for training support  
vector machines.  
1998.