

PsychSync - System Architecture & Technical Documentation

Table of Contents

1. [Project Overview](#)
2. [System Architecture](#)
3. [Technology Stack](#)
4. [Database Design](#)
5. [API Architecture](#)
6. [Frontend Architecture](#)
7. [Security Architecture](#)
8. [Deployment Architecture](#)
9. [Performance Considerations](#)
10. [Scalability Plan](#)

Project Overview

PsychSync is a comprehensive team psychology and optimization platform that helps organizations build high-performing teams through personality assessments, behavioral analysis, and AI-driven recommendations.

Core Features


- **Team Management:** Create, manage, and organize teams
- **Assessment Center:** Multiple personality frameworks (MBTI, Big Five, DISC, etc.)
- **Team Optimizer:** AI-powered team composition recommendations
- **Analytics Dashboard:** Performance metrics and behavioral insights
- **Predictive Analytics:** Team velocity and compatibility predictions


Business Value

- Reduce team formation time by 60%
- Improve team productivity by 35%
- Decrease team conflict incidents by 45%
- Enhance employee satisfaction and retention

System Architecture

High-Level Architecture





Microservices Architecture

Core Services

1. Authentication Service

- JWT token management
- OAuth integration
- User session management
- Role-based access control

2. User Management Service

- User profiles and preferences
- Organization management
- Team membership tracking

3. Assessment Service

- Assessment framework management
- Question bank administration
- Response collection and validation
- Scoring algorithms

4. Team Management Service

- Team CRUD operations
- Member assignment and roles
- Team hierarchy management

5. Analytics Service

- Data aggregation and processing
- Report generation
- Metrics calculation
- Trend analysis

6. AI/ML Service

- Personality analysis algorithms
- Team optimization recommendations
- Predictive modeling
- Behavioral pattern recognition

7. Notification Service

- Email notifications
- Push notifications
- In-app notifications
- Communication templates

Technology Stack

Frontend

yaml

Framework: React 18+

Language: TypeScript/JavaScript ES6+

State Management: Context API + useReducer

Routing: React Router v6

Styling: Tailwind CSS

Charts: Recharts/Chart.js

Icons: Heroicons/Lucide React

Build Tool: Vite/Create React App

Testing: Jest + React Testing Library

Backend

yaml

API Framework: FastAPI (Python) / Express.js (Node.js)

Authentication: JWT + OAuth 2.0

Database ORM: SQLAlchemy (Python) / Prisma (Node.js)

Validation: Pydantic (Python) / Joi (Node.js)

Documentation: OpenAPI/Swagger

Testing: pytest (Python) / Jest (Node.js)

Database

yaml

Primary Database: PostgreSQL 14+

Cache: Redis 6+

Search Engine: Elasticsearch 7+

Time Series: InfluxDB (for analytics)

AI/ML Stack

yaml

Framework: TensorFlow 2.x / PyTorch

Libraries: scikit-learn, pandas, numpy

NLP: spaCy, NLTK

Model Serving: TensorFlow Serving / MLflow

DevOps & Infrastructure

yaml

Containerization: Docker + Docker Compose

Orchestration: Kubernetes

Cloud Provider: AWS / Google Cloud / Azure

CI/CD: GitHub Actions / GitLab CI

Monitoring: Prometheus + Grafana

Logging: ELK Stack (Elasticsearch, Logstash, Kibana)

API Gateway: Kong / AWS API Gateway

Database Design

Core Entities

sql

-- Users and Organizations

```
CREATE TABLE organizations (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  name VARCHAR(255) NOT NULL,  
  domain VARCHAR(100),  
  settings JSONB,  
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

```
CREATE TABLE users (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  organization_id UUID REFERENCES organizations(id),  
  email VARCHAR(255) UNIQUE NOT NULL,  
  password_hash VARCHAR(255),  
  first_name VARCHAR(100),  
  last_name VARCHAR(100),  
  role VARCHAR(50) DEFAULT 'member',  
  is_active BOOLEAN DEFAULT true,  
  last_login TIMESTAMP,  
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

-- Teams

```
CREATE TABLE teams (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  organization_id UUID REFERENCES organizations(id),  
  name VARCHAR(255) NOT NULL,  
  description TEXT,  
  team_type VARCHAR(50),  
  status VARCHAR(50) DEFAULT 'active',  
  created_by UUID REFERENCES users(id),  
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

```
CREATE TABLE team_members (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  team_id UUID REFERENCES teams(id),  
  user_id UUID REFERENCES users(id),  
  role VARCHAR(50) DEFAULT 'member',  
  joined_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  UNIQUE(team_id, user_id)  
);
```

-- Assessment Framework

```
CREATE TABLE assessment_frameworks (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  name VARCHAR(255) NOT NULL,  
  description TEXT,  
  version VARCHAR(20),  
  question_count INTEGER,  
  estimated_duration INTEGER, -- in minutes  
  is_active BOOLEAN DEFAULT true,  
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

```
CREATE TABLE assessment_questions (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  framework_id UUID REFERENCES assessment_frameworks(id),  
  question_text TEXT NOT NULL,  
  question_type VARCHAR(50), -- likert, multiple_choice, binary  
  options JSONB, -- for multiple choice questions  
  category VARCHAR(100),  
  order_index INTEGER,  
  is_active BOOLEAN DEFAULT true  
);
```

```
CREATE TABLE assessments (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  user_id UUID REFERENCES users(id),  
  framework_id UUID REFERENCES assessment_frameworks(id),  
  status VARCHAR(50) DEFAULT 'in_progress',  
  started_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  completed_at TIMESTAMP,  
  results JSONB,  
  raw_scores JSONB  
);
```

```
CREATE TABLE assessment_responses (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  assessment_id UUID REFERENCES assessments(id),  
  question_id UUID REFERENCES assessment_questions(id),  
  response_value TEXT,  
  response_score INTEGER,  
  answered_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

-- Analytics and Insights

```
CREATE TABLE team_analytics (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  team_id UUID REFERENCES teams(id),
```

```

metric_type VARCHAR(100),
metric_value DECIMAL(10,4),
calculation_date DATE,
metadata JSONB,
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
);

CREATE TABLE team_insights (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  team_id UUID REFERENCES teams(id),
  insight_type VARCHAR(100),
  insight_data JSONB,
  confidence_score DECIMAL(3,2),
  generated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
);

```

Indexes and Performance Optimization

```

sql

-- User and authentication indexes
CREATE INDEX idx_users_email ON users(email);
CREATE INDEX idx_users_org_role ON users(organization_id, role);
CREATE INDEX idx_users_active ON users(is_active);

-- Team and membership indexes
CREATE INDEX idx_teams_org ON teams(organization_id);
CREATE INDEX idx_team_members_team ON team_members(team_id);
CREATE INDEX idx_team_members_user ON team_members(user_id);

-- Assessment indexes
CREATE INDEX idx_assessments_user ON assessments(user_id);
CREATE INDEX idx_assessments_framework ON assessments(framework_id);
CREATE INDEX idx_assessments_status ON assessments(status);
CREATE INDEX idx_assessment_responses_assessment ON assessment_responses(assessment_id);

-- Analytics indexes
CREATE INDEX idx_team_analytics_team_date ON team_analytics(team_id, calculation_date);
CREATE INDEX idx_team_insights_team_type ON team_insights(team_id, insight_type);

```

API Architecture

RESTful API Design

Base URL Structure

Production: <https://api.psychsync.com/v1>
Staging: <https://staging-api.psychsync.com/v1>
Development: <http://localhost:8000/v1>

Authentication Endpoints

yaml

POST /auth/login
POST /auth/register
POST /auth/refresh
POST /auth/logout
GET /auth/me
POST /auth/forgot-password
POST /auth/reset-password

User Management Endpoints

yaml

GET /users
GET /users/{user_id}
PUT /users/{user_id}
DELETE /users/{user_id}
GET /users/{user_id}/assessments
GET /users/{user_id}/teams

Team Management Endpoints

yaml

GET /teams
POST /teams
GET /teams/{team_id}
PUT /teams/{team_id}
DELETE /teams/{team_id}
GET /teams/{team_id}/members
POST /teams/{team_id}/members
DELETE /teams/{team_id}/members/{user_id}
GET /teams/{team_id}/analytics
GET /teams/{team_id}/insights
POST /teams/{team_id}/optimize

Assessment Endpoints

yaml

```
GET /assessments/frameworks
GET /assessments/frameworks/{framework_id}
GET /assessments/frameworks/{framework_id}/questions
POST /assessments
GET /assessments/{assessment_id}
PUT /assessments/{assessment_id}
POST /assessments/{assessment_id}/responses
GET /assessments/{assessment_id}/results
```

Analytics Endpoints

yaml

```
GET /analytics/dashboard
GET /analytics/teams/{team_id}
GET /analytics/organization
GET /analytics/behavioral-trends
GET /analytics/performance-metrics
```

API Response Format

json

```
{
  "success": true,
  "data": {
    // Actual response data
  },
  "message": "Operation completed successfully",
  "timestamp": "2024-01-15T10:30:00Z",
  "request_id": "req_123456789"
}
```

Error Response Format


json

```
{  
  "success": false,  
  "error": {  
    "code": "VALIDATION_ERROR",  
    "message": "The provided data is invalid",  
    "details": {  
      "field": "email",  
      "reason": "Invalid email format"  
    }  
  },  
  "timestamp": "2024-01-15T10:30:00Z",  
  "request_id": "req_123456789"  
}
```

Frontend Architecture

Component Structure

```
src/
├── components/
│   ├── Auth/
│   │   ├── Login.tsx
│   │   ├── Register.tsx
│   │   ├── ForgotPassword.tsx
│   │   └── ProtectedRoute.tsx
│   ├── Dashboard/
│   │   ├── Dashboard.tsx
│   │   ├── DashboardCard.tsx
│   │   ├── MetricsOverview.tsx
│   │   └── QuickActions.tsx
│   ├── Teams/
│   │   ├── TeamList.tsx
│   │   ├── TeamCard.tsx
│   │   ├── TeamDetail.tsx
│   │   ├── CreateTeam.tsx
│   │   ├── TeamMembers.tsx
│   │   └── TeamOptimization.tsx
│   ├── Assessments/
│   │   ├── AssessmentCenter.tsx
│   │   ├── AssessmentList.tsx
│   │   ├── TakeAssessment.tsx
│   │   ├── AssessmentResults.tsx
│   │   └── AssessmentComparison.tsx
│   ├── Analytics/
│   │   ├── Analytics.tsx
│   │   ├── TeamAnalytics.tsx
│   │   ├── BehavioralTrends.tsx
│   │   └── PerformanceCharts.tsx
│   ├── Layout/
│   │   ├── Header.tsx
│   │   ├── Sidebar.tsx
│   │   ├── Footer.tsx
│   │   └── Layout.tsx
│   └── UI/
│       ├── Button.tsx
│       ├── Modal.tsx
│       ├── LoadingSpinner.tsx
│       ├── NotificationContainer.tsx
│       └── FormElements.tsx
├── contexts/
│   ├── AuthContext.tsx
│   ├── TeamContext.tsx
│   ├── NotificationContext.tsx
│   └── ThemeContext.tsx
```



State Management Architecture



```
// Global State Structure
```

```
interface AppState {  
  auth: {  
    user: User | null;  
    isAuthenticated: boolean;  
    isLoading: boolean;  
    error: string | null;  
  };  
  teams: {  
    teams: Team[];  
    currentTeam: Team | null;  
    loading: boolean;  
    error: string | null;  
  };  
  assessments: {  
    assessments: Assessment[];  
    frameworks: AssessmentFramework[];  
    loading: boolean;  
    error: string | null;  
  };  
  notifications: {  
    notifications: Notification[];  
  };  
  ui: {  
    sidebarOpen: boolean;  
    theme: 'light' | 'dark';  
    loading: boolean;  
  };  
}
```

Security Architecture

Authentication & Authorization

1. JWT Tokens

- Access tokens (15 minutes expiry)
- Refresh tokens (7 days expiry)
- Secure HTTP-only cookies

2. Role-Based Access Control (RBAC)

```
typescript
```

```
enum UserRole {  
    SUPER_ADMIN = 'super_admin',  
    ORG_ADMIN = 'org_admin',  
    TEAM_LEAD = 'team_lead',  
    MEMBER = 'member'  
}  
  
interface Permission {  
    resource: string;  
    action: string;  
    conditions?: Record<string, any>;  
}
```

3. Data Encryption

- TLS 1.3 for data in transit
- AES-256 for data at rest
- bcrypt for password hashing

Security Measures

1. Input Validation

- Schema validation on all API endpoints
- XSS protection
- SQL injection prevention

2. Rate Limiting

- API endpoint rate limiting
- Authentication attempt limiting
- DDoS protection

3. Audit Logging

- User action tracking
- Data access logging
- Security event monitoring

Deployment Architecture

Environment Configuration

Development

yaml

Database: PostgreSQL (local)
Cache: Redis (local)
API: FastAPI dev server
Frontend: React dev server with HMR
Monitoring: Local logging only

Staging

yaml

Infrastructure: Docker containers
Database: PostgreSQL (managed service)
Cache: Redis (managed service)
Load Balancer: NGINX
SSL: Let's Encrypt
Monitoring: Basic metrics

Production

yaml

Infrastructure: Kubernetes cluster
Database: PostgreSQL cluster with read replicas
Cache: Redis cluster
CDN: CloudFlare/AWS CloudFront
Load Balancer: AWS ALB / GCP Load Balancer
SSL: Commercial certificate
Monitoring: Full observability stack

CI/CD Pipeline

yaml

GitHub Actions workflow

name: PsychSync CI/CD

on:

push:

branches: [main, develop]

pull_request:

branches: [main]

jobs:

test:

runs-on: ubuntu-latest

steps:

- **name:** Checkout code
- **name:** Setup Node.js
- **name:** Install dependencies
- **name:** Run linting
- **name:** Run tests
- **name:** Generate coverage report

security:

runs-on: ubuntu-latest

steps:

- **name:** Security audit
- **name:** Dependency vulnerability scan
- **name:** SAST analysis

build:

needs: [test, security]

runs-on: ubuntu-latest

steps:

- **name:** Build Docker images
- **name:** Push to registry

deploy:

needs: build

runs-on: ubuntu-latest

if: github.ref == 'refs/heads/main'

steps:

- **name:** Deploy to staging
- **name:** Run integration tests
- **name:** Deploy to production
- **name:** Health check

Performance Considerations

Backend Optimization

1. Database Optimization

- Query optimization with proper indexing
- Connection pooling
- Read replicas for analytics queries
- Query result caching

2. API Performance

- Response compression (gzip)
- HTTP/2 support
- Pagination for large datasets
- Async processing for heavy operations

3. Caching Strategy

- Redis for session and application cache
- CDN for static assets
- API response caching
- Database query result caching

Frontend Optimization

1. Bundle Optimization

- Code splitting by routes
- Tree shaking for unused code
- Lazy loading of components
- Webpack bundle analysis

2. Performance Monitoring

- Core Web Vitals tracking
- Performance budget enforcement
- Real User Monitoring (RUM)
- Synthetic monitoring

Scalability Plan

Horizontal Scaling

1. Microservices Decomposition

- Service separation by domain
- Independent deployment pipelines

- Service mesh for communication
- Circuit breakers for resilience

2. Database Scaling

- Read replicas for query distribution
- Sharding strategy for large datasets
- Connection pooling optimization
- Query performance monitoring

3. Auto-scaling Configuration

```
yaml

# Kubernetes HPA configuration
apiVersion: autoscaling/v2
kind: HorizontalPodAutoscaler
metadata:
  name: psychsync-api-hpa
spec:
  scaleTargetRef:
    apiVersion: apps/v1
    kind: Deployment
    name: psychsync-api
  minReplicas: 3
  maxReplicas: 50
  metrics:
    - type: Resource
      resource:
        name: cpu
        target:
          type: Utilization
          averageUtilization: 70
    - type: Resource
      resource:
        name: memory
        target:
          type: Utilization
          averageUtilization: 80
```

Performance Targets

- **API Response Time:** < 200ms (95th percentile)
- **Page Load Time:** < 2 seconds (initial load)
- **Database Query Time:** < 50ms (average)
- **Availability:** 99.9% uptime

- **Concurrent Users:** 10,000+
- **Throughput:** 1,000 requests/second