

Ex. No.: 5

Date: 13.2.25

System Calls Programming

Aim: To experiment system calls using fork(), execlp() and pid() functions.

Algorithm:

1. **Start**
 - Include the required header files (stdio.h and stdlib.h).
2. **Variable Declaration**
 - Declare an integer variable pid to hold the process ID.
3. **Create a Process**
 - Call the fork() function to create a new process. Store the return value in the pid variable:
 - If fork() returns:
 - -1: Forking failed (child process not created).
 - 0: Process is the child process.
 - Positive integer: Process is the parent process.
4. **Print Statement Executed Twice**
 - Print the statement:

```
scss
Copy code
THIS LINE EXECUTED TWICE
```

(This line is executed by both parent and child processes after fork()).

5. **Check for Process Creation Failure**
 - If pid == -1:
 - Print:

Copy code
CHILD PROCESS NOT CREATED
 - Exit the program using exit(0).
6. **Child Process Execution**
 - If pid == 0 (child process):
 - Print:
 - Process ID of the child process using getpid().
 - Parent process ID of the child process using getppid().
7. **Parent Process Execution**
 - If pid > 0 (parent process):
 - Print:
 - Process ID of the parent process using getpid().
 - Parent's parent process ID using getppid().
8. **Final Print Statement**
 - Print the statement:

objectivec

Copy code
IT CAN BE EXECUTED TWICE

(This line is executed by both parent and child processes).

9. End

Program:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
int main ()
{
    int pid;
    pid = fork();
    printf("\n This line executed twice");
    if (pid == -1)
    {
        printf("\n Child process not created\n");
        exit(0);
    }
    if (pid == 0)
    {
        printf("\n I am child process and my id is\n", getpid());
        printf("\n The Child parent process id is %d\n", getppid());
    }
    else
    {

```



```

printf("\n I am parent process and my id is %.d\n", get pid());
printf("\n The parents parent process ID is %.d\n", get ppid());
}
printf("\n It can be executed Twice");
printf("\n")
}

```

Output:

This line executed twice
 I am parent process and my id is 1644
 The parents parent process ID is 1509.
 It can be executed twice.
 This line executed twice.
 This line executed twice
 I am child process and my id is 1645
 The child parent process ID is 1644.
 It can be executed twice.

Result:

Thus the program is executed using fork(), execp() and pid() functions.

✓
S. H.