


COPPER TUBE IN- LINE CONNECTORS



				Dowell's						
mm²	øΑ	øC	J	CAT. No.	SYB-95	SYD-20A	SYE-150A	SYT-102 R	STD PKG	
1.5	1.6	3.2	15	EH-453					200	
2.5	2.4	4.0	15	EH-454					200	
4.0	3.1	4.8	15	CB-3	SYA-427	200				
4.6	3.5	5.5	15	EH-455		200				
6.0	3.8	5.5	15	CB-4						
10	4.5	6.2	20	EH-460	JBR-1				200	
16	5.4	7.1	20	CB-6	JBR-2				200	
25	6.8	8.8	32	CB-24	JBR-3				100	
35	8.2	10.6	36	CB-25	JBR-4				100	
50	9.5	12.4	40	CB-26	JBR-5			HY-267	100	
70	11.2	14.7	40	CB-51	JBR-6			HY-268	50	
95	13.5	17.4	45	CB-52	JBR-9	JDR-9	JER-7	HY-269	50	
120	15.0	19.4	45	CB-53		JDR-10	JER-8	HY-270	30	
150	16.5	21.2	55	CB-54		JDR-11	JER-9	HY-271	20	
185	18.5	23.5	65	CB-55		JDR-12	JER-10	HY-272	20	
240	21.0	26.5	80	CB-56		JDR-14	JER-11	HY-273	10	
300	23.5	30.0	85	CB-57		JDR-15	JER-12	HY-274	10	
400	26.8	34.8	90	CB-58			JER-13	HY-275	5	
500	30.0	39.0	100	CB-59			JER-14	JEM-279	5	
630	35.0	45.0	110	CB-61			JER-15	JEM-280	5	

COPPER REDUCER TERMINALS





		Dowell's RECOMMENDED TOOLS & DIES						DIES							
MM ²	øΑ	øС	øD	D-1	В	K	G-H	J	CAT. No.	SYB-	SYD-	SYT-	SYE-	0.77.400.5	STD
										95	20A	150A	150 B	SYT-102 R	PKG
2.5	2.5	4.7	3.8	3.3	6	4	10	20	WPC-7	LINE (CONNE	CTERS			200
4.0	2.8	4.7	3.8	3.3	6	4	10	20	WPC-16	SYA-427	SYT-17	SYT-2			200
6.0	3.1	4.7	3.8	3.3	6	4	10	20	WPC-18						200
10	3.8	5.5	3.8	3.3	9	4	10	23	WPC-20						200
10	4.4	6.2	3.8	3.3	9	4	10	23	WPC-22	JBR-1					200
16	5.3	7.1	3.8	3.3	13	4	13	30	WPC-2	JBR-2					200
25	7.0	9.0	6.0	5.5	12	5	15	32	WPC-25	JBR-3					100
35	8.0	10.0	7.5	6.5	12	5	20	37	WPC-4	JBR-4					100
50	9.2	11.2	7.5	6.5	16	5	20	41	WPC-26	JBR-6					100
70	11.3	13.8	7.5	6.5	18	5	20	43	WPC-27	JBR-7				HY-267	50
95	12.8	15.6	11.5	10.5	20	6	25	51	WPC-29	JBR-9				HY-268	50
120	14.8	17.8	11.5	10.5	22	6	32	60	WPC-35	JBR-10			JEA-120	HY-269	30
150	16.0	19.6	11.5	10.5	26	6	32	64	WPC-37		JDR-11	JER-11	JEA-150	HY-270	20
185	18.0	22.0	11.5	10.5	32	6	32	70	WPC-38		JDR-12	JER-12	JEA-185	HY-271	20
225	20.0	26.0	15.6	14.0	38	8	32	78	WPC-39		JDR-14	JER-14	JEA-240	HY-272	10
240	21.2	26.0	15.6	14.0	38	8	32	78	WPC-43		JDR-14	JER-14	JEA-240	HY-272	10
300	24.0	28.7	16.0	15.0	42	8	42	92	WPC-45		JDR-15	JER-15	JEA-300	HY-273	10
400	27.0	33.2	15.6	14.0	46	12	32	90	WPC-101			JER-17	JEA-400	HY-274	5

MATERIAL -EC GRADE COPPER IS -191

TOLERANCE=± 5%




COPPER TUBE IN - LINE CONNECTORS

CONNECTORS FOR SOLDERLESS CRIMPING TO COPPER CONDUCTORS. COMPACT ALUMINIUM XLPE CABLE

	MM ²	øΑ	øС	J	Dowell's CAT. No.	Retail Packing Nos.
	1.5	1.8	3.7	12	CB-41	100
	2.5	2.4	4.0	15	EH-454	100
	4.0	3.1	4.8	15	CB-3	100
	6.0	3.8	5.5	15	CB-4	100
	10	4.5	6.2	20	EH-460	100
	10	5.4	7.1	20	CB-6	100
5	20	6.0	7.7	22	CB-47	100
3	25	6.8	8.8	32	CB-24	100
X	35	8.2	10.6	36	CB-25	100
¥N.						
5	50	9.5	12.4	40	CB-26	100
A H	70	11.2	14.7	40	CB-51	50
2	95	13.5	17.4	45	CB-52	50
A L						
IAN	120	15.0	19.4	45	CB-53	30
X	150	16.5	21.2	55	CB-54	20
Z Z	185	18.5	23.5	65	CB-55	20
ESIC						
E D	240	21.0	26.5	80	CB-56	10
Ξ	300	23.5	30.0	85	CB-57	10
	400	26.8	34.8	90	CB-58	5
EN L						
	500	30.0	39.0	100	CB-59	5
YAI	550	31.7	41.4	100	CB-60	5
AD.	630	35.0	45.0	110	CB-61	5
O ENSURE ADVANCEMENT IN THE DESIGN OR MANUFACTURE OF ANY PRODUC.						
ENS	800	39.0	50.6	150	CB-42	5
2	1000	43.0	56.2	170	CB-43	4








LUGS SYSTEM



COPPER TUBE IN-LINE CONNECTORS







ΜM²	øΑ	øС	J	Dowell's CAT. No.	RECOMM TOOLS	STD PKG
1.5	1.6	3.2	15	EH-453	SYA-427	200
2.5	2.4	4.0	15	EH-454	SYT-17	200
4.6	3.5	5.5	15	EH-455	SYT-2	200


COPPER INSULATED IN-LINE CONNECTORS

EH-465

SYI-1210/SYT-1546

200







27 15

5.5 5.6 7.2