

Amazon Machine Image (AMI)

Ubuntu Server 24.04 LTS (HVM), SSD Volume Type
ami-0e86e20dae9224db8 (64-bit (x86)) / ami-096ea6a12ea24a797 (64-bit (Arm))
Virtualization: hvm ENA enabled: true Root device type: ebs

Description

Ubuntu Server 24.04 LTS (HVM), EBS General Purpose (SSD) Volume Type. Support available from Canonical (<http://www.ubuntu.com/cloud/services>).

Architecture: 64-bit (x86) **AMI ID**: ami-0e86e20dae9224db8 **Verified provider**

Instance type: t2.medium
Family: t2 2 vCPU 4 GiB Memory Current generation: true
On-Demand Linux base pricing: 0.0464 USD per Hour
On-Demand RHEL base pricing: 0.0752 USD per Hour
On-Demand Windows base pricing: 0.0644 USD per Hour
On-Demand SUSE base pricing: 0.1464 USD per Hour

Summary

Number of instances: 1

Software Image (AMI): Canonical, Ubuntu, 24.04, amd64...
Virtual server type (instance type): t2.medium
Firewall (security group): New security group
Storage (volumes): 1 volume(s) - 8 GiB

Free tier: In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 750 hours of public IPv4 address usage per month.

Launch instance

Step 2: After creating the instance click on Connect the instance and navigate to SSH Client.

Instances (1) Info

Last updated less than a minute ago

Connect

Instance state ▾







Actions ▾

Launch instances ▾

Find Instance by attribute or tag (case-sensitive)

All states ▾

< 1 > ⚙

<input type="checkbox"/>	Name  ▾	Instance ID	Instance state ▾	Instance type ▾	Status check	Alarm status	Availability Zone ▾	Public IP
<input type="checkbox"/>	Exp4	i-04a49a928f6d2dbf1	 Running  	t2.medium	 Initializing	View alarms 	us-east-1d	ec2-52-91-240-34.compute-1.amazonaws.com

```
Microsoft Windows [Version 10.0.22000.2057]
(c) Microsoft Corporation. All rights reserved.

C:\Users\ACER\Downloads>ssh -i "exp4key.pem" ubuntu@ec2-52-91-240-34.compute-1.amazonaws.com
The authenticity of host 'ec2-52-91-240-34.compute-1.amazonaws.com (52.91.240.34)' can't be established.
ECDSA key fingerprint is SHA256:hQXGxhM3JrUApDQWobOui+rTZu/uzA7hY4Hs9p58oLM.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added 'ec2-52-91-240-34.compute-1.amazonaws.com,52.91.240.34' (ECDSA) to the list of known hosts.
Welcome to Ubuntu 24.04 LTS (GNU/Linux 6.8.0-1012-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:        https://ubuntu.com/pro

System information as of Sat Sep 21 10:54:46 UTC 2024

System load:  0.08          Processes:            115
Usage of /:   22.7% of 6.71GB Users logged in:       0
Memory usage: 6%           IPv4 address for enX0: 172.31.87.78
Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status
```

Step 4: Run the below commands to install and setup Docker.

```
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo apt-key add
- curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo tee
```

```
/etc/apt/trusted.gpg.d/docker.gpg > /dev/null
```

```
sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu  
$(lsb_release -cs) stable"
```

```
9AcZ58Em+1WsVnAXdUR//bMmhyr8wL/G1Y01V3JEJTRdxsSxdYa4deGBBY/Adpsw  
24jxh0JR+1sJpqIUeb999+R8euDhRHG9eF07DRu6weatUJ6suupoDTRWtr/4yGqe  
dKxv3qQhNLsnaAzqW/1nA3iUB4k7kCaKZxhdhDbClf9P37qaRW467BLCVO/coL3y  
Vm50dwdrNtKpMBh3ZpbB1uJvgi9mXtyBOMJ3v8RZeDzFiG8HdCtg9RvIt/AIFoHR  
H3S+U79NT6i0KPzLImDfs8T7R1pyuMc4Ufs8gggyg9v3Ae6cN3eQyxcK3w0cbBwsh  
/nQNFsA6uu+9H7NhbehBMhYnpNZyrHzCmzyXkauwRAqoCbGCNyKTRwsur9gS41TQ  
M8ssD1jFhe0Jf3h0DnkKU+HKjvMRO11DK7zdmLdNzA1cvTZ/nCC9KPj1z8QC47S  
xx+dTZSx40NAhwbs/LN3PoKtn8LPjY9NP9uDwI+TWYquS2U+KHDrBDLsgozDbs/O  
jCxcPdzNmXpWQHEtHU7649OXHP7UeNST1mCUC5qdank0V1iejF6/CfTFU4MfcrG  
YT90qFF93M3v01BbxP+EIY2/9tiIPbrd  
=0YYh  
-----END PGP PUBLIC KEY BLOCK-----  
ubuntu@ip-172-31-87-78:~$ /etc/apt/trusted.gpg.d/docker.gpg > /dev/null  
-bash: /etc/apt/trusted.gpg.d/docker.gpg: No such file or directory  
ubuntu@ip-172-31-87-78:~$ sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu $(lsb_release -cs) stable"  
Repository: 'deb [arch=amd64] https://download.docker.com/linux/ubuntu noble stable'  
Description:  
Archive for codename: noble components: stable  
More info: https://download.docker.com/linux/ubuntu  
Adding repository.  
Press [ENTER] to continue or Ctrl-c to cancel.  
Adding deb entry to /etc/apt/sources.list.d/archive_uri-https_download_docker_com_linux_ubuntu-noble.list  
Adding disabled deb-src entry to /etc/apt/sources.list.d/archive_uri-https_download_docker_com_linux_ubuntu-noble.list  
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease  
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease [126 kB]  
Get:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease [126 kB]  
Get:4 http://security.ubuntu.com/ubuntu noble-security InRelease [126 kB]  
Get:5 https://download.docker.com/linux/ubuntu noble InRelease [48.8 kB]  
Get:6 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe amd64 Packages [15.0 MB]  
Get:7 https://download.docker.com/linux/ubuntu noble/stable amd64 Packages [15.3 kB]  
Get:8 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/universe Translation-en [5982 kB]
```

```
sudo apt-get update sudo apt-get install -y docker-ce
```

```

W: https://download.docker.com/linux/ubuntu/dists/noble/InRelease: Key is stored in legacy trusted.gpg keyring (/etc/apt/trusted.gpg), see the DEPRECATION section in apt-key(8) for detail:
ubuntu@ip-172-31-87-78:~$ sudo apt-get update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu noble InRelease
Hit:5 http://security.ubuntu.com/ubuntu noble-security InRelease
Reading package lists... Done
W: https://download.docker.com/linux/ubuntu/dists/noble/InRelease: Key is stored in legacy trusted.gpg keyring (/etc/apt/trusted.gpg), see the DEPRECATION section in apt-key(8) for detail:
ubuntu@ip-172-31-87-78:~$ sudo apt-get install -y docker-ce
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  containerd.io docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras docker-compose-plugin libltdl7 libslirp0 pigz slirp4netns
Suggested packages:
  aufs-tools cgroupfs-mount | cgroup-lite
The following NEW packages will be installed:
  containerd.io docker-buildx-plugin docker-ce docker-ce-cli docker-ce-rootless-extras docker-compose-plugin libltdl7 libslirp0 pigz slirp4netns
0 upgraded, 10 newly installed, 0 to remove and 139 not upgraded.
Need to get 123 MB of archives.
After this operation, 442 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 libltdl7 2.4.7-7build1 amd64 123 kB

```

```

Unpacking docker-ce (5:27.3.1-1~ubuntu.24.04~noble) ...
Selecting previously unselected package docker-ce-rootless-extras.
Preparing to unpack .../5-docker-ce-rootless-extras_5%3a27.3.1-1~ubuntu.24.04~noble_amd64.deb ...
Unpacking docker-ce-rootless-extras (5:27.3.1-1~ubuntu.24.04~noble) ...
Selecting previously unselected package docker-compose-plugin.
Preparing to unpack .../6-docker-compose-plugin_2.29.7-1~ubuntu.24.04~noble_amd64.deb ...
Unpacking docker-compose-plugin (2.29.7-1~ubuntu.24.04~noble) ...
Selecting previously unselected package libltdl7:amd64.
Preparing to unpack .../7-libltdl7_2.4.7-7build1_amd64.deb ...
Unpacking libltdl7:amd64 (2.4.7-7build1) ...
Selecting previously unselected package libslirp0:amd64.
Preparing to unpack .../8-libslirp0_4.7.0-1ubuntu3_amd64.deb ...
Unpacking libslirp0:amd64 (4.7.0-1ubuntu3) ...
Selecting previously unselected package slirp4netns.
Preparing to unpack .../9-slirp4netns_1.2.1-1build2_amd64.deb ...
Unpacking slirp4netns (1.2.1-1build2) ...
Setting up docker-buildx-plugin (0.17.1-1~ubuntu.24.04~noble) ...
Setting up containerd.io (1.7.22-1) ...
Created symlink /etc/systemd/system/multi-user.target.wants/containerd.service → /usr/lib/systemd/system/containerd.service.
Setting up docker-compose-plugin (2.29.7-1~ubuntu.24.04~noble) ...
Setting up libltdl7:amd64 (2.4.7-7build1) ...
Setting up docker-ce-cli (5:27.3.1-1~ubuntu.24.04~noble) ...
Setting up libslirp0:amd64 (4.7.0-1ubuntu3) ...
Setting up pigz (2.8-1) ...
Setting up docker-ce-rootless-extras (5:27.3.1-1~ubuntu.24.04~noble) ...
Setting up slirp4netns (1.2.1-1build2) ...
Setting up docker-ce (5:27.3.1-1~ubuntu.24.04~noble) ...
Created symlink /etc/systemd/system/multi-user.target.wants/docker.service → /usr/lib/systemd/system/docker.service.
Created symlink /etc/systemd/system/sockets.target.wants/docker.socket → /usr/lib/systemd/system/docker.socket.
Processing triggers for man-db (2.12.0-4build2) ...
Processing triggers for libc-bin (2.39-0ubuntu8.2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.

```

```

sudo mkdir -p /etc/docker cat <<EOF | sudo
tee /etc/docker/daemon.json
{
  "exec-opts":["native.cgroupdriver=systemd"]
}
EOF

```

```

ubuntu@ip-172-31-87-78:~$ sudo mkdir -p /etc/docker
ubuntu@ip-172-31-87-78:~$ cat <<EOF | sudo tee /etc/docker/daemon.json
> {
>   "exec-opts":["native.cgroupdriver=systemd"]
> }
> EOF
{
  "exec-opts":["native.cgroupdriver=systemd"]
}
ubuntu@ip-172-31-87-78:~$

```

```

sudo systemctl enable docker sudo
systemctl daemon-reload sudo
systemctl restart docker

```

```
ubuntu@ip-172-31-87-78:~$ sudo systemctl enable docker
Synchronizing state of docker.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable docker
ubuntu@ip-172-31-87-78:~$ sudo systemctl daemon-reload
ubuntu@ip-172-31-87-78:~$ sudo systemctl restart docker
```

Step 5: Run the below command to install Kubernetes. **curl -fsSL**

https://pkgs.k8s.io/core:/stable:/v1.31/deb/Release.key | sudo gpg --dearmor -o /etc/apt/keyrings/kubernetes-apt-keyring.gpg

echo 'deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg]

https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /' | sudo tee

/etc/apt/sources.list.d/kubernetes.list

```
ubuntu@ip-172-31-87-78:~$ sudo systemctl restart docker
ubuntu@ip-172-31-87-78:~$ curl -fsSL https://pkgs.k8s.io/core:/stable:/v1.31/deb/Release.key | sudo gpg --dearmor -o /etc/apt/keyrings/kubernetes-apt-keyring.gpg
ubuntu@ip-172-31-87-78:~$ echo 'deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg] https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /' | sudo tee /etc/apt/sources.list.d/kubernetes.list
deb [signed-by=/etc/apt/keyrings/kubernetes-apt-keyring.gpg] https://pkgs.k8s.io/core:/stable:/v1.31/deb/ /
ubuntu@ip-172-31-87-78:~$
```

sudo

apt-get update

sudo apt-get install -y kubelet kubeadm kubectl

sudo apt-mark hold kubelet kubeadm kubectl

```
ubuntu@ip-172-31-87-78:~$ sudo apt-get update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 https://download.docker.com/linux/ubuntu noble InRelease
Get:5 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb InRelease [1186 B]
Hit:6 http://security.ubuntu.com/ubuntu noble-security InRelease
Get:7 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb Packages [4865 B]
Fetched 6051 B in 1s (30.5 kB/s)
Reading package lists... Done
W: https://download.docker.com/linux/ubuntu/dists/noble/InRelease: Key is stored in legacy trusted.gpg keyring (/etc/apt/trusted.gpg), s
ubuntu@ip-172-31-87-78:~$ sudo apt-get install -y kubelet kubeadm kubectl
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  conntrack cri-tools kubernetes-cni
The following NEW packages will be installed:
  conntrack cri-tools kubeadm kubectl kubernetes-cni
0 upgraded, 6 newly installed, 0 to remove and 139 not upgraded.
Need to get 87.4 MB of archives.
After this operation, 314 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 conntrack amd64 1:1.4.8-1ubuntu1 [37.9 kB]
Get:2 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb cri-tools 1.31.1-1.1 [15.7 MB]
Get:3 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubeadm 1.31.1-1.1 [11.4 MB]
Get:4 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubectl 1.31.1-1.1 [11.2 MB]
Get:5 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubernetes-cni 1.5.1-1.1 [33.9 MB]
Get:6 https://prod-cdn.packages.k8s.io/repositories/iscv/kubernetes:/core:/stable:/v1.31/deb kubelet 1.31.1-1.1 [15.2 MB]
Fetched 87.4 MB in 1s (87.2 MB/s)
Selecting previously unselected package conntrack.
(Reading database ... 68007 files and directories currently installed.)
Preparing to unpack .../0-conntrack_1:1.4.8-1ubuntu1_amd64.deb ...
Unpacking conntrack (1:1.4.8-1ubuntu1) ...
Selecting previously unselected package cri-tools.
Preparing to unpack .../1-cri-tools_1.31.1-1.1_amd64.deb ...
Unpacking cri-tools (1.31.1-1.1) ...
Selecting previously unselected package kubeadm.
Preparing to unpack .../2-kubeadm_1.31.1-1.1_amd64.deb ...
Unpacking kubeadm (1.31.1-1.1) ...
Selecting previously unselected package kubectl.
Preparing to unpack .../3-kubectl_1.31.1-1.1_amd64.deb ...
Unpacking kubectl (1.31.1-1.1) ...
Selecting previously unselected package kubernetes-cni.
Preparing to unpack .../4-kubernetes-cni_1.5.1-1.1_amd64.deb ...
Unpacking kubernetes-cni (1.5.1-1.1) ...
Setting up conntrack (1:1.4.8-1ubuntu1) ...
Setting up cri-tools (1.31.1-1.1) ...
Setting up kubernetes-cni (1.5.1-1.1) ...
Setting up kubeadm (1.31.1-1.1) ...
Setting up kubectl (1.31.1-1.1) ...
Setting up kubelet (1.31.1-1.1) ...
```

```

Get:6 https://prod-cdn.packages.k8s.io/repositories/1sv:/kubernetes:/core:/stable:/v1.31/deb kubelet 1.
Fetched 87.4 MB in 1s (87.2 MB/s)
Selecting previously unselected package conntrack.
(Reading database ... 68007 files and directories currently installed.)
Preparing to unpack .../0-conntrack_1%3a1.4.8-1ubuntu1_amd64.deb ...
Unpacking conntrack (1:1.4.8-1ubuntu1) ...
Selecting previously unselected package cri-tools.
Preparing to unpack .../1-cri-tools_1.31.1-1.1_amd64.deb ...
Unpacking cri-tools (1.31.1-1.1) ...
Selecting previously unselected package kubeadm.
Preparing to unpack .../2-kubeadm_1.31.1-1.1_amd64.deb ...
Unpacking kubeadm (1.31.1-1.1) ...
Selecting previously unselected package kubect1.
Preparing to unpack .../3-kubect1_1.31.1-1.1_amd64.deb ...
Unpacking kubect1 (1.31.1-1.1) ...
Selecting previously unselected package kubernetes-cni.
Preparing to unpack .../4-kubernetes-cni_1.5.1-1.1_amd64.deb ...
Unpacking kubernetes-cni (1.5.1-1.1) ...
Selecting previously unselected package kubelet.
Preparing to unpack .../5-kubelet_1.31.1-1.1_amd64.deb ...
Unpacking kubelet (1.31.1-1.1) ...
Setting up conntrack (1:1.4.8-1ubuntu1) ...
Setting up kubect1 (1.31.1-1.1) ...
Setting up cri-tools (1.31.1-1.1) ...
Setting up kubernetes-cni (1.5.1-1.1) ...
Setting up kubeadm (1.31.1-1.1) ...
Setting up kubelet (1.31.1-1.1) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-87-78:~$ sudo apt-mark hold kubelet kubeadm kubect1
kubelet set on hold.
kubeadm set on hold.
kubect1 set on hold.
ubuntu@ip-172-31-87-78:~$

```

sudo

systemctl enable --now kubelet

sudo kubeadm init --pod-network-cidr=10.244.0.0/16

```

ubuntu@ip-172-31-87-78:~$ sudo systemctl enable --now kubelet
ubuntu@ip-172-31-87-78:~$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16
[init] Using Kubernetes version: v1.31.0
[preflight] Running pre-flight checks
W0921 11:48:52.282513 4743 checks.go:1080] [preflight] WARNING: Couldn't create the interface used for talking to the container runtime: failed to create new CRI runtime service: validate service connection:
validate CRI v1 runtime API for endpoint "unix:///var/run/containerd/containerd.sock": rpc error: code = Unimplemented desc = unknown service runtime.v1.RuntimeService
[WARNING FileExisting-socat]: socat not found in system path
[preflight] Pulling images required for setting up a Kubernetes cluster
[preflight] This might take a minute or two, depending on the speed of your internet connection
[preflight] You can also perform this action beforehand using 'kubeadm config images pull'
error execution phase preflight: [preflight] Some fatal errors occurred:
failed to create new CRI runtime service: validate service connection: validate CRI v1 runtime API for endpoint "unix:///var/run/containerd/containerd.sock": rpc error: code = Unimplemented desc = unknown service runtime.v1.RuntimeService[preflight] If you know what you are doing, you can make a check non-fatal with '--ignore-preflight-errors=...'
To see the stack trace of this error execute with --v=5 or higher
ubuntu@ip-172-31-87-78:~$

```

Now We have got an error.

So we have to perform some additional commands as follow.

sudo apt-get install -y containerd

```

to see the stack trace of this error execute with --v3 or higher
ubuntu@ip-172-31-87-78:~$ sudo apt-get install -y containerd
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following packages were automatically installed and are no longer required:
  docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras docker-compose-plugin libltdl7 libslirp0 pigz slirp4netns
Use 'sudo apt autoremove' to remove them.
The following additional packages will be installed:
  runc
The following packages will be REMOVED:
  containerd.io docker-ce
The following NEW packages will be installed:
  containerd runc
0 upgraded, 2 newly installed, 2 to remove and 139 not upgraded.
Need to get 47.2 MB of archives.
After this operation, 53.1 MB disk space will be freed.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 runc amd64 1.1.12-0ubuntu3.1 [8599 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble-updates/main amd64 containerd amd64 1.7.12-0ubuntu4.1 [38.6 MB]
Fetched 47.2 MB in 1s (88.2 MB/s)
(Reading database ... 68064 files and directories currently installed.)
Removing docker-ce (5:27.3.1-1~ubuntu.24.04~noble) ...
Removing containerd.io (1.7.22-1) ...
Selecting previously unselected package runc.
(Reading database ... 68044 files and directories currently installed.)
Preparing to unpack .../runc_1.1.12-0ubuntu3.1_amd64.deb ...
Unpacking runc (1.1.12-0ubuntu3.1) ...
Selecting previously unselected package containerd.
Preparing to unpack .../containerd_1.7.12-0ubuntu4.1_amd64.deb ...
Unpacking containerd (1.7.12-0ubuntu4.1) ...
Setting up runc (1.1.12-0ubuntu3.1) ...
Setting up containerd (1.7.12-0ubuntu4.1) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-87-78:~$

```

sudo mkdir -p /etc/containerd

sudo containerd config default | sudo tee /etc/containerd/config.toml

```

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-87-78:~$ sudo mkdir -p /etc/containerd
ubuntu@ip-172-31-87-78:~$ sudo containerd config default | sudo tee /etc/containerd/config.toml
ubuntu@ip-172-31-87-78:~$ sudo mkdir -p /etc/containerd
ubuntu@ip-172-31-87-78:~$ sudo containerd config default | sudo tee /etc/containerd/config.toml
disabled_plugins = []
imports = []
oom_score = 0
plugin_dir = ""
required_plugins = []
root = "/var/lib/containerd"
state = "/run/containerd"
temp = ""
version = 2

[cgroup]
  path = ""

[debug]
  address = ""
  format = ""
  gid = 0
  level = ""
  uid = 0

[grpc]
  address = "/run/containerd/containerd.sock"
  gid = 0
  max_recv_message_size = 16777216
  max_send_message_size = 16777216
  tcp_address = ""
  tcp_tls_ca = ""
  tcp_tls_cert = ""
  tcp_tls_key = ""
  uid = 0

```

... sudo systemctl restart

containerd sudo systemctl

enable containerd

sudo systemctl status containerd

```

ubuntu@ip-172-31-87-78:~$ sudo systemctl restart containerd
ubuntu@ip-172-31-87-78:~$ sudo systemctl enable containerd
ubuntu@ip-172-31-87-78:~$ sudo systemctl status containerd
● containerd.service - containerd container runtime
   Loaded: loaded (/usr/lib/systemd/system/containerd.service; enabled; preset: enabled)
   Active: active (running) since Sat 2024-09-21 12:48:02 UTC; 2min 6s ago
     Docs: https://containerd.io
   Main PID: 7830 (containerd)
    Tasks: 7
   Memory: 13.2M (peak: 14.0M)
      CPU: 295ms
   CGroup: /system.slice/containerd.service
           └─7830 /usr/bin/containerd

Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603681825Z" level=info msg="Start subscribing containerd event"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603713219Z" level=info msg="serving... address=/run/containerd/containerd.sock.ttrpc"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603720772Z" level=info msg="Start recovering state"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603745293Z" level=info msg="serving... address=/run/containerd/containerd.sock"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603770644Z" level=info msg="Start event monitor"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603779762Z" level=info msg="Start snapshots syncer"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603787308Z" level=info msg="Start cni network conf syncer for default"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603795250Z" level=info msg="Start streaming server"
Sep 21 12:48:02 ip-172-31-87-78 containerd[7830]: time="2024-09-21T12:48:02.603847770Z" level=info msg="containerd successfully booted in 0.027952s"
Sep 21 12:48:02 ip-172-31-87-78 systemd[1]: Started containerd.service - containerd container runtime.
ubuntu@ip-172-31-87-78:~$

```

sudo apt-get install -y socat

```

ubuntu@ip-172-31-87-78:~$ sudo apt-get install -y socat
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following packages were automatically installed and are no longer required:
  docker-buildx-plugin docker-ce-cli docker-ce-rootless-extras docker-compose-plugin libltdl7 libslirp0 pigz slirp4netns
Use 'sudo apt autoremove' to remove them.
The following NEW packages will be installed:
  socat
0 upgraded, 1 newly installed, 0 to remove and 139 not upgraded.
Need to get 374 kB of archives.
After this operation, 1649 kB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu noble/main amd64 socat amd64 1.8.0.0-4build3 [374 kB]
Fetched 374 kB in 0s (13.2 MB/s)
Selecting previously unselected package socat.
(Reading database ... 68108 files and directories currently installed.)
Preparing to unpack .../socat_1.8.0.0-4build3_amd64.deb ...
Unpacking socat (1.8.0.0-4build3) ...
Setting up socat (1.8.0.0-4build3) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-87-78:~$

```

Step 6: Initialize the Kubecluster

sudo kubeadm init --pod-network-cidr=10.244.0.0/16

```

ubuntu@ip-172-31-87-78:~$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16
[init] Using Kubernetes version: v1.31.0
[preflight] Running pre-flight checks
[preflight] Pulling images required for setting up a Kubernetes cluster
[preflight] This might take a minute or two, depending on the speed of your internet connection
[preflight] You can also perform this action beforehand using 'kubeadm config images pull'
W0921 12:58:06.057654 8434 checks.go:846] detected that the sandbox image "registry.k8s.io/pause:3.8" of the container runtime is inconsistent with that used by kubeadm.It is recommended to use "registry.k8s.io/pause:3.10" as the CRI sandbox image.
[certs] Using certificateDir folder "/etc/kubernetes/pki"
[certs] Generating "ca" certificate and key
[certs] Generating "apiserver" certificate and key
[certs] apiserver serving cert is signed for DNS names [ip-172-31-87-78 kubernetes kubernetes.default kubernetes.default.svc kubernetes.default.svc.cluster.local] and IPs [10.96.0.1 172.31.87.78]
[certs] Generating "apiserver-kubelet-client" certificate and key
[certs] Generating "front-proxy-ca" certificate and key
[certs] Generating "front-proxy-client" certificate and key
[certs] Generating "etcd/ca" certificate and key
[certs] Generating "etcd/server" certificate and key
[certs] etcd/server serving cert is signed for DNS names [ip-172-31-87-78 localhost] and IPs [172.31.87.78 127.0.0.1 ::1]
[certs] Generating "etcd/peer" certificate and key
[certs] etcd/peer serving cert is signed for DNS names [ip-172-31-87-78 localhost] and IPs [172.31.87.78 127.0.0.1 ::1]
[certs] Generating "etcd/healthcheck-client" certificate and key
[certs] Generating "apiserver-etcd-client" certificate and key
[certs] Generating "sa" key and public key
[kubeconfig] Using kubeconfig folder "/etc/kubernetes"
[kubeconfig] Writing "admin.conf" kubeconfig file
[kubeconfig] Writing "super-admin.conf" kubeconfig file
[kubeconfig] Writing "kubelet.conf" kubeconfig file
[kubeconfig] Writing "controller-manager.conf" kubeconfig file
[kubeconfig] Writing "scheduler.conf" kubeconfig file
[etcd] Creating static Pod manifest for local etcd in "/etc/kubernetes/manifests"
[control-plane] Using manifest folder "/etc/kubernetes/manifests"
[control-plane] Creating static Pod manifest for "kube-apiserver"
[control-plane] Creating static Pod manifest for "kube-controller-manager"
[control-plane] Creating static Pod manifest for "kube-scheduler"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"

```



```
[mark-control-plane] Marking the node ip-172-31-87-78 as control-plane by adding the taints [node-role.kubernetes.io/control-plane:NoSchedule]
[bootstrap-token] Using token: ut4opm.bfe28j57nfncds8m
[bootstrap-token] Configuring bootstrap tokens, cluster-info ConfigMap, RBAC Roles
[bootstrap-token] Configured RBAC rules to allow Node Bootstrap tokens to get nodes
[bootstrap-token] Configured RBAC rules to allow Node Bootstrap tokens to post CSRs in order for nodes to get long term certificate credentials
[bootstrap-token] Configured RBAC rules to allow the csrapprover controller automatically approve CSRs from a Node Bootstrap Token
[bootstrap-token] Configured RBAC rules to allow certificate rotation for all node client certificates in the cluster
[bootstrap-token] Creating the "cluster-info" ConfigMap in the "kube-public" namespace
[kubelet-finalize] Updating "/etc/kubernetes/kubelet.conf" to point to a rotatable kubelet client certificate and key
[addons] Applied essential addon: CoreDNS
[addons] Applied essential addon: kube-proxy
```

Your Kubernetes control-plane has initialized successfully!

To start using your cluster, you need to run the following as a regular user:

```
mkdir -p $HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

Alternatively, if you are the root user, you can run:

```
export KUBECONFIG=/etc/kubernetes/admin.conf
```

You should now deploy a pod network to the cluster.

Run "kubectl apply -f [podnetwork].yaml" with one of the options listed at:
<https://kubernetes.io/docs/concepts/cluster-administration/addons/>

Then you can join any number of worker nodes by running the following on each as root:

```
kubeadm join 172.31.87.78:6443 --token ut4opm.bfe28j57nfncds8m \
--discovery-token-ca-cert-hash sha256:be2108f5129c3aac922280e2219dcace14c20204be972d8823eacc59bf6528e6
ubuntu@ip-172-31-87-78:~$
```

Copy the mkdir and chown commands from the top and execute them. mkdir
-p \$HOME/.kube
sudo cp -i /etc/kubernetes/admin.conf \$HOME/.kube/config sudo
chown \$(id -u):\$(id -g) \$HOME/.kube/config

```
--discovery-token-ca-cert-hash sha256:be2108f5129c3aac922280e2219dcace14c20204be972d8823eacc59bf6528e6
ubuntu@ip-172-31-87-78:~$ mkdir -p $HOME/.kube
ubuntu@ip-172-31-87-78:~$ sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config
ubuntu@ip-172-31-87-78:~$ sudo chown $(id -u):$(id -g) $HOME/.kube/config
ubuntu@ip-172-31-87-78:~$
```

Add a common networking plugin called flannel as mentioned in the code.

kubectl apply -f <https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml>

```
ubuntu@ip-172-31-87-78:~$ kubectl apply -f https://raw.githubusercontent.com/coreos/flannel/master/Documentation/kube-flannel.yml
namespace/kube-flannel created
clusterrole.rbac.authorization.k8s.io/flannel created
clusterrolebinding.rbac.authorization.k8s.io/flannel created
serviceaccount/flannel created
configmap/kube-flannel-cfg created
daemonset.apps/kube-flannel-ds created
ubuntu@ip-172-31-87-78:~$
```



```

serviceaccount/flannel created
configmap/kube-flannel-cfg created
daemonset.apps/kube-flannel-ds created
ubuntu@ip-172-31-87-78:~$ kubectl apply -f https://k8s.io/examples/application/deployment.yaml
deployment.apps/nginx-deployment created
ubuntu@ip-172-31-87-78:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-2nwj8    0/1     Pending   0           6m54s
nginx-deployment-d556bf558-vbnn6    0/1     Pending   0           6m54s
ubuntu@ip-172-31-87-78:~$ POD_NAME=$(kubectl get pods -i app=nginx -o jsonpath="{.items[0].metadata.name}")
error: unknown shorthand flag: 'i' in -i
See 'kubectl get --help' for usage.
ubuntu@ip-172-31-87-78:~$ POD_NAME=$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}")
ubuntu@ip-172-31-87-78:~$ kubectl port-forward $POD_NAME 8080:80
error: unable to forward port because pod is not running. Current status=Pending
ubuntu@ip-172-31-87-78:~$ kubectl taint nodes --all node-role.kubernetes.io/control-plane-node/ip-172-31-20-171 untainted
error: at least one taint update is required
ubuntu@ip-172-31-87-78:~$ kubectl get nodes
NAME                                STATUS   ROLES    AGE   VERSION
ip-172-31-87-78                    Ready    control-plane   63m   v1.31.1
ubuntu@ip-172-31-87-78:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-2nwj8    0/1     Pending   0           41m
nginx-deployment-d556bf558-vbnn6    0/1     Pending   0           41m
ubuntu@ip-172-31-87-78:~$ POD_NAME=$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}")
ubuntu@ip-172-31-87-78:~$ kubectl port-forward $POD_NAME 8080:80
error: unable to forward port because pod is not running. Current status=Pending
ubuntu@ip-172-31-87-78:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-2nwj8    0/1     Pending   0           52m
nginx-deployment-d556bf558-vbnn6    0/1     Pending   0           52m
ubuntu@ip-172-31-87-78:~$
Broadcast message from root@ip-172-31-87-78 (Sat 2024-09-21 14:22:30 UTC):

The system will power off now!

Connection to ec2-52-91-240-34.compute-1.amazonaws.com closed by remote host.
Connection to ec2-52-91-240-34.compute-1.amazonaws.com closed.

C:\Users\ACER\Downloads>ssh -i "exp4key.pem" ubuntu@ec2-52-91-240-34.compute-1.amazonaws.com
ssh: connect to host ec2-52-91-240-34.compute-1.amazonaws.com port 22: Connection timed out

C:\Users\ACER\Downloads>ssh -i "exp4key.pem" ubuntu@172.31.87.78
ssh: connect to host 172.31.87.78 port 22: Connection timed out

C:\Users\ACER\Downloads>echo komal
komal

```

Step 7: Now that the cluster is up and running, we can deploy our nginx server on this cluster. Apply this deployment file using this command to create a deployment `kubectl apply -f https://k8s.io/examples/application/deployment.yaml`

```

daemonset.apps/kube-flannel-ds created
ubuntu@ip-172-31-87-78:~$ kubectl apply -f https://k8s.io/examples/application/deployment.yaml
deployment.apps/nginx-deployment created
ubuntu@ip-172-31-87-78:~$

```

kubectl get pods

```

deployment.apps/nginx-deployment created
ubuntu@ip-172-31-87-78:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-2nwj8    0/1     Pending   0           6m54s
nginx-deployment-d556bf558-vbnn6    0/1     Pending   0           6m54s
ubuntu@ip-172-31-87-78:~$

```

POD_NAME=\$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}") `kubectl port-forward $POD_NAME 8080:80`

```

ubuntu@ip-172-31-87-78:~$ kubectl port-forward $POD_NAME 8080:80
error: unable to forward port because pod is not running. Current status=Pending
ubuntu@ip-172-31-87-78:~$

```

Note : We have faced an error as pod status is pending so make it running run below commands then again run above 2 commands.

kubectl taint nodes --all node-role.kubernetes.io/control-plane-node/ip-172-31-20-171 untainted

kubectl get nodes

```

ubuntu@ip-172-31-87-78:~$ kubectl taint nodes --all node-role.kubernetes.io/control-plane-node/ip-172-31-20-171 untainted
error: at least one taint update is required
ubuntu@ip-172-31-87-78:~$ kubectl get nodes
NAME                                STATUS   ROLES    AGE   VERSION
ip-172-31-87-78                    Ready    control-plane   63m   v1.31.1
ubuntu@ip-172-31-87-78:~$

```

kubectl get pods

```
ubuntu@ip-172-31-87-78:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-2nwj8    0/1     Pending   0           41m
nginx-deployment-d556bf558-vbnn6    0/1     Pending   0           41m
ubuntu@ip-172-31-87-78:~$
```

POD_NAME=\$(kubectl get pods -l app=nginx -o jsonpath="{.items[0].metadata.name}") kubectl port-forward \$POD_NAME 8080:80

```
ubuntu@ip-172-31-20-171:~$ kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-d556bf558-vz8rv    1/1     Running   0           3m4s
nginx-deployment-d556bf558-wz5wc    1/1     Running   0           3m4s
```

Step 8: Verify your deployment

Open up a new terminal and ssh to your EC2 instance.

Then, use this curl command to check if the Nginx server is running. **curl**

--head http://127.0.0.1:8080

```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\Users\bhush\one drive 2\OneDrive\Desktop\New folder (4)> ssh -i "Master_Ec2_Key.pem" ubuntu@ec2-54-196-129-215.compute-1.amazonaws.com
Welcome to Ubuntu 24.04 LTS (GNU/Linux 6.8.0-1012-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Sun Sep 15 07:58:53 UTC 2024

System load:  0.15          Processes:            152
Usage of /:   55.3% of 6.71GB Users logged in:        1
Memory usage: 20%          IPv4 address for enX0: 172.31.20.171
Swap usage:   0%

 * Ubuntu Pro delivers the most comprehensive open source security and
 * compliance features.
 *
https://ubuntu.com/aws/pro
```

```
ubuntu@ip-172-31-20-171:~$ curl --head http://127.0.0.1:8080
HTTP/1.1 200 OK
Server: nginx/1.14.2
Date: Sun, 15 Sep 2024 07:59:03 GMT
Content-Type: text/html
Content-Length: 612
Last-Modified: Tue, 04 Dec 2018 14:44:49 GMT
Connection: keep-alive
ETag: "5c0692e1-264"
Accept-Ranges: bytes
ubuntu@ip-172-31-20-171:~$
```

If the response is 200 OK and you can see the Nginx server name, your deployment was successful. We have successfully deployed our Nginx server on our EC2 instance.

Conclusion: In this experiment, we successfully installed Kubernetes on an EC2 instance and deployed an Nginx server using Kubectl commands. During the process, we encountered two main errors: the Kubernetes pod was initially in a pending state, which was resolved by removing the controlplane taint using **kubectl taint nodes --all**, and we also faced an issue with the missing **containerd** runtime, which was fixed by installing and starting containerd. We used a **t2.medium EC2 instance with 2 CPUs** to meet the necessary resource requirements for the Kubernetes setup and deployment.