



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

Experiment No. 9
Implement Non-Restoring algorithm using c-programming
Name: Vinith Shetty
Roll Number: 55
Date of Performance:
Date of Submission:

**Aim** - To implement Non-Restoring division algorithm using c-programming.

### Objective -

1. To understand the working of Non-Restoring division algorithm.
2. To understand how to implement Non-Restoring division algorithm using c-programming.


### Theory:

In each cycle content of the register, A is first shifted and then the divisor is added or subtracted with the content of register A depending upon the sign of A. In this, there is no need of restoring, but if the remainder is negative then there is a need of restoring the remainder. This is the faster algorithm of division.



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science



Perform  $8 \div 3$  by non-restoring division technique.

	A Register	Q Register	
Initially	0 0 0 0	1 0 0 0	
Shift	0 0 0 1	0 0 0 □	
Subtract	1 1 1 0		
Set Q <sub>0</sub>	① 1 1 1 0	0 0 0 0	First Cycle
Shift	1 1 1 0	0 0 0 □	
Add	0 0 0 1		
Set Q <sub>0</sub>	① 1 1 1 1	0 0 0 0	Second Cycle
Shift	1 1 1 1	0 0 0 □	
Add	0 0 0 1		
Set Q <sub>0</sub>	① 1 1 1 1	0 0 0 1	Third Cycle
Shift	0 0 0 1	0 0 1 □	
Subtract	1 1 1 0		
Set Q <sub>0</sub>	① 1 1 1 1	0 0 1 0	Fourth Cycle
Add	1 1 1 1		Quotient
	0 0 0 1		
	0 0 0 1		Remainder



Program -

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int dec_bin(int, int []);
```

```
int twos(int [], int []);
```

```
int left(int [], int []);
```

```
int add(int [], int []);
```

```
int main()
```

```
{
```

```
    int a, b, m[4]={0,0,0,0}, q[4]={0,0,0,0}, acc[4]={0,0,0,0}, m2[4], i, n=4;
```

```
    printf("Enter the Dividend: ");
```

```
    scanf("%d", &a);
```

```
    printf("Enter the Divisor: ");
```

```
    scanf("%d", &b);
```

```
    dec_bin(a, q);
```

```
    dec_bin(b, m);
```

```
    twos(m, m2);
```

```
    printf("\nA\tQ\tComments\n");
```

```
    for(i=3; i>=0; i--)
```

```
    {
```

```
        printf("%d", acc[i]);
```

```
    }
```

```
    printf("\t");
```

```
    for(i=3; i>=0; i--)
```

```
    {
```

```
        printf("%d", q[i]);
```

```
    }
```

```
    printf("\tStart\n");
```

```
    while(n>0)
```

```
    {
```

```
        left(acc, q);
```

```
        for(i=3; i>=0; i--)
```

```
        {
```

```
            printf("%d", acc[i]);
```



```
}
printf("\t");
for(i=3; i>=1; i--)
{
    printf("%d", q[i]);
}
printf("_\tLeft Shift A,Q\n");
add(acc, m2);
for(i=3; i>=0; i--)
{
    printf("%d", acc[i]);
}
printf("\t");
for(i=3; i>=1; i--)
{
    printf("%d", q[i]);
}
printf("_\tA=A-M\n");
if(acc[3]==0)
{
    q[0]=1;
    for(i=3; i>=0; i--)
    {
        printf("%d", acc[i]);
    }
    printf("\t");
    for(i=3; i>=0; i--)
    {
        printf("%d", q[i]);
    }
    printf("\tQo=1\n");
}
else
{
    q[0]=0;
    add(acc, m);
    for(i=3; i>=0; i--)
    {
        printf("%d", acc[i]);
    }
}
```



```
    }
    printf("\t");
    for(i=3; i>=0; i--)
    {
        printf("%d", q[i]);
    }
    printf("\tQo=0; A=A+M\n");
}
n--;
}
printf("\nQuotient = ");
for(i=3; i>=0; i--)
{
    printf("%d", q[i]);
}
printf("\tRemainder = ");
for(i=3; i>=0; i--)
{
    printf("%d", acc[i]);
}
printf("\n");
return 0;
}
```

```
int dec_bin(int d, int m[])
{
    int b=0, i=0;
    for(i=0; i<4; i++)
    {
        m[i]=d%2;
        d=d/2;
    }
    return 0;
}
```

```
int twos(int m[], int m2[])
{
    int i, m1[4];
    for(i=0; i<4; i++)
```



```
{
    if(m[i]==0)
    {
        m1[i]=1;
    }
    else
    {
        m1[i]=0;
    }
}
for(i=0; i<4; i++)
{
    m2[i]=m1[i];
}
if(m2[0]==0)
{
    m2[0]=1;
}
else
{
    m2[0]=0;
    if(m2[1]==0)
    {
        m2[1]=1;
    }
    else
    {
        m2[1]=0;
        if(m2[2]==0)
        {
            m2[2]=1;
        }
        else
        {
            m2[2]=0;
            if(m2[3]==0)
            {
                m2[3]=1;
            }
        }
    }
}
```



```
        else
        {
            m2[3]=0;
        }
    }
}
return 0;
}

int left(int acc[], int q[])
{
    int i;
    for(i=3; i>0; i--)
    {
        acc[i]=acc[i-1];
    }
    acc[0]=q[3];
    for(i=3; i>0; i--)
    {
        q[i]=q[i-1];
    }
}

int add(int acc[], int m[])
{
    int i, carry=0;
    for(i=0; i<4; i++)
    {
        if(acc[i]+m[i]+carry==0)
        {
            acc[i]=0;
            carry=0;
        }
        else if(acc[i]+m[i]+carry==1)
        {
            acc[i]=1;
            carry=0;
        }
    }
}
```



```
else if(acc[i]+m[i]+carry==2)
{
    acc[i]=0;
    carry=1;
}
else if(acc[i]+m[i]+carry==3)
{
    acc[i]=1;
    carry=1;
}
}
return 0;
}
```

### Output:

Enter the Dividend: 10

Enter the Divisor: 2

A	Q	Comments
0000	1010	Start
0001	010_	Left Shift A,Q
1111	010_	A=A-M
0001	0100	Qo=0; A=A+M
0010	100_	Left Shift A,Q
0000	100_	A=A-M
0000	1001	Qo=1
0001	001_	Left Shift A,Q
1111	001_	A=A-M
0001	0010	Qo=0; A=A+M
0010	010_	Left Shift A,Q
0000	010_	A=A-M
0000	0101	Qo=1

Quotient = 0101      Remainder = 0000





### **Conclusion -**

The Non-Restoring Division Algorithm represents a significant improvement over the Restoring Division Algorithm, offering a more efficient approach to perform integer division in computer arithmetic. Its primary advantage lies in reducing the number of iterations and operations required to produce the quotient and remainder when dividing binary numbers. the Non-Restoring Division Algorithm stands as a significant advancement in the realm of computer arithmetic, providing a more efficient and faster means of performing integer division. Its application in processor design and digital circuitry showcases its relevance in optimizing computational efficiency.