



Experiment No. 7
Implement Booth's algorithm using c-programming
Name: Vinith Shetty
Roll Number: 55
Date of Performance:
Date of Submission:

Aim: To implement Booth's algorithm using c-programming.

Objective -


1. To understand the working of Booths algorithm.
2. To understand how to implement Booth's algorithm using c-programming.

Theory:

Booth's algorithm is a multiplication algorithm that multiplies two signed binary numbers in 2's complement notation. Booth used desk calculators that were faster at shifting than adding and created the algorithm to increase their speed.

The algorithm works as per the following conditions :

1. If Q_n and Q_{-1} are same i.e. 00 or 11 perform arithmetic shift by 1 bit.
2. If $Q_n Q_{-1} = 10$ do $A = A - B$ and perform arithmetic shift by 1 bit.
3. If $Q_n Q_{-1} = 01$ do $A = A + B$ and perform arithmetic shift by 1 bit.



Multiplicand (B) ← 0 1 0 1 (5), Multiplier (Q) ← 0 1 0 0 (4)				
Steps	A	Q	Q-1	Operation
	0 0 0 0	0 1 0 0	0	Initial
Step 1 :	0 0 0 0	0 0 1 0	0	Shift right
Step 2 :	0 0 0 0	0 0 0 1	0	Shift right
Step 3 :	1 0 1 1	0 0 0 1	0	A ← A - B
	1 1 0 1	1 0 0 0	1	Shift right
Step 4 :	0 0 1 0	1 0 0 0	1	A ← A + B
	0 0 0 1	0 1 0 0	0	Shift right
Result	0 0 0 1 0 1 0 0 = +20			



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Program:

```
#include <math.h>
```

```
int a = 0, b = 0, c = 0, a1 = 0, b1 = 0, com[5] = { 1, 0, 0, 0, 0};  
int anum[5] = {0}, anumcp[5] = {0}, bnum[5] = {0};  
int acomp[5] = {0}, bcomp[5] = {0}, pro[5] = {0}, res[5] = {0};
```

```
void binary(){  
    a1 = fabs(a);  
    b1 = fabs(b);  
    int r, r2, i, temp;  
    for (i = 0; i < 5; i++){  
        r = a1 % 2;  
        a1 = a1 / 2;  
        r2 = b1 % 2;  
        b1 = b1 / 2;  
        anum[i] = r;  
        anumcp[i] = r;  
        bnum[i] = r2;  
        if(r2 == 0){  
            bcomp[i] = 1;  
        }  
        if(r == 0){  
            acomp[i] = 1;  
        }  
    }  
}
```

```
c = 0;  
for ( i = 0; i < 5; i++){  
    res[i] = com[i] + bcomp[i] + c;  
    if(res[i] >= 2){  
        c = 1;  
    }  
    else  
        c = 0;  
    res[i] = res[i] % 2;  
}  
for (i = 4; i >= 0; i--){  
    bcomp[i] = res[i];
```



```
}

if (a < 0){
    c = 0;
    for (i = 4; i >= 0; i--){
        res[i] = 0;
    }
    for ( i = 0; i < 5; i++){
        res[i] = com[i] + acomp[i] + c;
        if (res[i] >= 2){
            c = 1;
        }
        else
            c = 0;
        res[i] = res[i] % 2;
    }
    for (i = 4; i >= 0; i--){
        anum[i] = res[i];
        anumcp[i] = res[i];
    }
}

if(b < 0){
    for (i = 0; i < 5; i++){
        temp = bnum[i];
        bnum[i] = bcomp[i];
        bcomp[i] = temp;
    }
}

void add(int num[]){
    int i;
    c = 0;
    for ( i = 0; i < 5; i++){
        res[i] = pro[i] + num[i] + c;
        if (res[i] >= 2){
            c = 1;
        }
        else{
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
c = 0;
}
res[i] = res[i] % 2;
}
for (i = 4; i >= 0; i--){
    pro[i] = res[i];
    printf("%d", pro[i]);
}
printf(":");
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}

void arshift(){
    int temp = pro[4], temp2 = pro[0], i;
    for (i = 1; i < 5 ; i++){
        pro[i-1] = pro[i];
    }
    pro[4] = temp;
    for (i = 1; i < 5 ; i++){
        anumcp[i-1] = anumcp[i];
    }
    anumcp[4] = temp2;
    printf("\nAR-SHIFT: ");
    for (i = 4; i >= 0; i--){
        printf("%d", pro[i]);
    }
    printf(":");
    for(i = 4; i >= 0; i--){
        printf("%d", anumcp[i]);
    }
}

void main(){
    int i, q = 0;
    printf("\t\tBOOTH'S MULTIPLICATION ALGORITHM");
    printf("\nEnter two numbers to multiply: ");
    printf("\nBoth must be less than 16");
    //simulating for two numbers each below 16
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
do{
    printf("\nEnter A: ");
    scanf("%d",&a);
    printf("Enter B: ");
    scanf("%d", &b);
}while(a >=16 || b >=16);

printf("\nExpected product = %d", a * b);
binary();
printf("\n\nBinary Equivalents are: ");
printf("\nA = ");
for (i = 4; i >= 0; i--){
    printf("%d", anum[i]);
}
printf("\nB = ");
for (i = 4; i >= 0; i--){
    printf("%d", bnum[i]);
}
printf("\nB'+ 1 = ");
for (i = 4; i >= 0; i--){
    printf("%d", bcomp[i]);
}
printf("\n\n");
for (i = 0; i < 5; i++){
    if (anum[i] == q){
        printf("\n-->");
        arshift();
        q = anum[i];
    }
    else if(anum[i] == 1 && q == 0){
        printf("\n-->");
        printf("\nSUB B: ");
        add(bcomp);
        arshift();
        q = anum[i];
    }
    else{
        printf("\n-->");
        printf("\nADD B: ");
    }
}
```



```
        add(bnum);
        arshift();
        q = anum[i];
    }
}

printf("\nProduct is = ");
for (i = 4; i >= 0; i--){
    printf("%d", pro[i]);
}
for (i = 4; i >= 0; i--){
    printf("%d", anumcp[i]);
}
}
```

Output:

OUTPUT:-

BOOTH'S MULTIPLICATION ALGORITHM

Enter two numbers to multiply:

Both must be less than 16

Enter A: 10

Enter B: 2

Expected product = 20

Binary Equivalentents are:

A = 01010

B = 00010

B' + 1 = 11110

-->

AR-SHIFT: 00000:00101

-->

SUB B: 11110:00101

AR-SHIFT: 11111:00010

-->

ADD B: 00001:00010

AR-SHIFT: 00000:10001

-->

SUB B: 11110:10001

AR-SHIFT: 11111:01000



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

-->

ADD B: 00001:01000

AR-SHIFT: 00000:10100

Product is = 0000010100

Conclusion –

Booth's algorithm, a multiplication algorithm designed to efficiently multiply signed binary numbers, has proven to be a significant advancement in computer arithmetic. Its capacity to perform multiplication using a more streamlined process by reducing the number of additions and operations required showcases its relevance in optimizing computational efficiency. Booth's algorithm stands as a valuable contribution to computer arithmetic, offering an efficient method for multiplying binary numbers.