



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Name:	Vinith Shetty
Roll No:	52
Class/Sem:	TE/V
Experiment No.:	8
Title:	Implementation of any one clustering algorithm using languages like JAVA/ Python.
Date of Performance:	
Date of Submission:	
Marks:	
Sign of Faculty:	



Aim: To Study and Implement K-Means algorithm

Objective:- Understand the working of K-Means algorithm and its implementation using python.

Theory:

In statistics and machine learning, k-means clustering is a method of cluster analysis which aims to partition n observations into k clusters in which each observation belongs to the cluster with the nearest mean.

Input

K:-number of clusters

D:- data set containing n objects

Output

A set of k clusters

Given k , the k-means algorithm is implemented in 5 steps:


Step 1: Arbitrarily choose k objects from D as the initial cluster centers.

Step 2: Find the distance from each object in the dataset with respect to cluster centers

Step 3: Assign each object to the cluster with the nearest seed point based on the mean value of the objects in the cluster.

Step 4: Update the cluster means i.e calculate the mean value of the objects for each cluster.

Step 5: Repeat the procedure, until there is no change in meaning.



Example: $d = \{2,4,10,12,3,20,30,11,25\}$ $k = 2$

1. Randomly assign mean $m_1=3$ and $m_2 = 4$

Therefore, $k_1 = \{2,3\}$ Therefore, $k_1 = \{4,10,12,20,30,11,25\}$

2. Randomly assign mean $m_1=2.5$ and $m_2 =$

16 Therefore, $k_1 = \{2,3,4\}$ Therefore,

$k_1 = \{4,10,12,20,30,11,25\}$

3. Randomly assign mean $m_1=3$ and $m_2 = 18$



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Therefore, $k1 = \{2,3,4,10\}$ Therefore, $k1 = \{12,20,30,11,25\}$

4. Randomly assign mean $m1=7$ and $m2 = 25$

Therefore, $k1 = \{2,3,4,10,11,12\}$ Therefore, $k1$

=

$\{20,30,25\}$

5. Randomly assign mean $m1=7$ and $m2 = 25$ Therefore, we stop as we are getting same mean values.

6. Therefore, Final clusters are: $k1 = \{2,3,4,10,11,12\}$ Therefore, $k1 = \{20,30,25\}$

CODE:

```
import pandas as pd
```

```
import seaborn as sns
```

```
import matplotlib.pyplot as plt
```

```
from sklearn.model_selection import train_test_split
```

```
from sklearn.cluster import KMeans
```

```
from sklearn.metrics import silhouette_score, classification_report
```

```
from sklearn.datasets import load_iris
```

```
from sklearn.impute import SimpleImputer
```

```
# Load the Iris dataset (or replace it with your  
dataset) iris = load_iris()
```

```
X = iris.data # Features
```

```
y = iris.target # Target labels (optional, if you're doing comparison)
```

```
# Split the data into training and test sets
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=42)
```

```
# Initialize and train the K-Means model
```

```
kmeans_model = KMeans(n_clusters=len(set(y)), random_state=42)
```



```
kmeans_model.fit(X_train)
```

```
# Predict the cluster labels on the test set
```

```
y_pred = kmeans_model.predict(X_test)
```

```
# Evaluate the model using Silhouette Score (common for  
clustering) sil_score = silhouette_score(X_test, y_pred)
```

```
print(f'Silhouette Score: {sil_score}')
```

```
# Optionally, compare predicted clusters with true labels using a classification report
```

```
print(f'Classification Report (with original labels):\n{classification_report(y_test, y_pred)}')
```

```
# Plotting the clusters (optional, useful for visualizing 2D data)
```

```
plt.scatter(X_test[:, 0], X_test[:, 1], c=y_pred, cmap='viridis')
```

```
plt.title('K-Means Clusters')
```


```
plt.show()
```

OUTPUT:

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/kmeans.py:1416: FutureWarning: The default value of 'n_init' will change from 10 to 'auto' in 1.4. Set the value of 'n_init' explicitly to suppress the warning
  super()._check_params_vs_input(X, default_n_init=10)
Silhouette Score: 0.5798300174405277
Classification Report (with original labels):
      precision    recall  f1-score   support

     0       0.00      0.00      0.00        19
     1       0.00      0.00      0.00        13
     2       0.19      0.23      0.21        13

 accuracy          0.06          0.08          0.07          45
 macro avg          0.06          0.08          0.07          45
 weighted avg          0.05          0.07          0.06          45
```





CONCLUSION:

What types of data preprocessing are necessary before applying the K-Means algorithm?

Before applying the K-Means algorithm, key data preprocessing steps include:

- 1. Scaling: Normalize or standardize features, as K-Means is sensitive to scale.**
- 2. Handling Missing Values: Impute or remove missing data, since K-Means does not handle them directly.**
- 3. Outlier Treatment: Address outliers as they can distort cluster formation.**
- 4. Dimensionality Reduction: Use PCA or similar techniques if the data has many features to improve clustering performance and reduce noise.**
- 5. Encoding Categorical Data: Convert categorical variables to numeric using one-hot encoding or label encoding.**