

# Recommender Systems

Machine Learning (AIM 5002-41)

Joon Hee Choi  
Sungkyunkwan University

# Problem formulation

## Example: Predicting movie ratings

User rates movies using zero to five stars



$n_u$  = no. users

$n_m$  = no. movies

$r(i, j) = 1$  if user  $j$  has  
rated movie  $i$

$y^{(i,j)}$  = rating given by  
user  $j$  to movie  $i$   
(defined only if  
 $r(i, j) = 1$ )

0, ..., 5

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?

# Content-based recommendations

# Content-based recommender systems

	Movie	Alice (1) $\theta^{(1)}$	Bob (2) $\theta^{(2)}$	Carol (3) $\theta^{(3)}$	Dave (4) $\theta^{(4)}$
$\mathbf{x}^{(1)}$	Love at last	5	5	0	0
$\mathbf{x}^{(2)}$	Romance forever	5	?	?	0
$\mathbf{x}^{(3)}$	Cute puppies of love	?	4	0	?
$\mathbf{x}^{(4)}$	Nonstop car chases	0	0	5	4
$\mathbf{x}^{(5)}$	Swords vs. karate	0	0	5	?

For each user  $j$ , learn a parameter  $\theta^{(j)} \in \mathbb{R}^3$ . Predict user  $j$  as rating movie  $i$  with  $(\theta^{(j)})^T x^{(i)}$  stars.

$$\mathbf{x}^{(3)} = \begin{bmatrix} 1 \\ 0.99 \\ 0 \end{bmatrix} \leftrightarrow \boldsymbol{\theta}^{(1)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix} \Rightarrow (\boldsymbol{\theta}^{(1)})^T \mathbf{x}^{(3)} = 4.95$$

## Problem formulation

$r(i, j) = 1$  if user  $j$  has rated movie  $i$  (0 otherwise)

$y^{(i,j)}$  = rating by user  $j$  on movie  $i$  (if defined)

$\theta^{(j)}$  = parameter vector for user  $j$

$x^{(i)}$  = feature vector for movie  $i$

For user  $j$ , movie  $i$ , predicted rating:  $(\theta^{(j)})^T (x^{(i)})$

$m^{(j)}$  = no. of movies rated by user  $j$

To learn  $\theta^{(j)}$ :

$$\min_{\theta^{(j)}} \frac{1}{2m^{(j)}} \sum_{i:r(i,j)=1} \left( (\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2m^{(j)}} \sum_{k=1}^n (\theta_k^{(j)})^2$$

## Optimization objective:

To learn  $\theta^{(j)}$  (parameter for user  $j$ ):

$$\min_{\theta^{(j)}} \frac{1}{2} \sum_{i:r(i,j)=1} \left( (\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{k=1}^n (\theta_k^{(j)})^2$$

To learn  $\theta^{(1)}, \theta^{(2)}, \dots, \theta^{(n_u)}$ :

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left( (\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

## Optimization algorithm:

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \underbrace{\frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} \left( (\theta^{(j)})^T x^{(i)} - y^{(i,j)} \right)^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2}_{J(\theta^{(1)}, \dots, \theta^{(n_u)})}$$

## Gradient descent update:

$$\begin{aligned} \theta_k^{(j)} &:= \theta_k^{(j)} - \alpha \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} \quad (\text{for } k = 0) \\ \theta_k^{(j)} &:= \theta_k^{(j)} - \alpha \underbrace{\left( \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} + \lambda \theta_k^{(j)} \right)}_{\frac{\partial}{\partial \theta_k^{(j)}} J(\theta^{(1)}, \dots, \theta^{(n_u)})} \quad (\text{for } k \neq 0) \end{aligned}$$



# Collaborative filtering

# Problem motivation

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	$x_1$ (romance)	$x_2$ (action)
Love at last	5	5	0	0	0.9	0
Romance forever	5	?	?	0	1.0	0.01
Cute puppies of love	?	4	0	?	0.99	0
Nonstop car chases	0	0	5	4	0.1	1.0
Swords vs. karate	0	0	5	?	0	0.9

# Problem motivation

						$x_0 = 1$		$\mathbf{x}^{(1)} = \begin{bmatrix} 1 \\ 1.0 \\ 0.0 \end{bmatrix}$
Movie		Alice (1) $\theta^{(1)}$	Bob (2) $\theta^{(2)}$	Carol (3) $\theta^{(3)}$	Dave (4) $\theta^{(4)}$	$x_1$ (romance)	$x_2$ (action)	
$\mathbf{x}^{(1)}$	Love at last	5	5	0	0	? $\rightarrow 1.0$	? $\rightarrow 0.0$	
$\mathbf{x}^{(2)}$	Romance forever	5	?	?	0	?	?	
$\mathbf{x}^{(3)}$	Cute puppies of love	?	4	0	?	?	?	
$\mathbf{x}^{(4)}$	Nonstop car chases	0	0	5	4	?	?	
$\mathbf{x}^{(5)}$	Swords vs. karate	0	0	5	?	?	?	

$$\theta^{(1)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}, \theta^{(2)} = \begin{bmatrix} 0 \\ 5 \\ 0 \end{bmatrix}, \theta^{(3)} = \begin{bmatrix} 0 \\ 0 \\ 5 \end{bmatrix}, \theta^{(4)} = \begin{bmatrix} 0 \\ 0 \\ 5 \end{bmatrix}$$

$$(\theta^{(1)})^T \mathbf{x}^{(1)} \approx 5$$

$$(\theta^{(2)})^T \mathbf{x}^{(1)} \approx 5$$

$$(\theta^{(3)})^T \mathbf{x}^{(1)} \approx 0$$

$$(\theta^{(4)})^T \mathbf{x}^{(1)} \approx 0$$

# Optimization algorithm

Given  $\theta^{(1)}, \dots, \theta^{(n_u)}$ , to learn  $x^{(i)}$ :

$$\min_{x^{(i)}} \frac{1}{2} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{k=1}^n (x_k^{(i)})^2$$

Given  $\theta^{(1)}, \dots, \theta^{(n_u)}$ , to learn  $x^{(1)}, \dots, x^{(n_m)}$ :

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

# Collaborative filtering

Given  $x^{(1)}, \dots, x^{(n_m)}$  (and movie ratings),  
can estimate  $\theta^{(1)}, \dots, \theta^{(n_u)}$

Given  $\theta^{(1)}, \dots, \theta^{(n_u)}$ ,  
can estimate  $x^{(1)}, \dots, x^{(n_m)}$

$$\boldsymbol{\theta} \rightarrow \mathbf{x} \rightarrow \boldsymbol{\theta} \rightarrow \mathbf{x} \rightarrow \boldsymbol{\theta} \rightarrow \mathbf{x} \rightarrow \dots$$

# Collaborative filtering algorithm

## Collaborative filtering optimization objective

Given  $x^{(1)}, \dots, x^{(n_m)}$ , estimate  $\theta^{(1)}, \dots, \theta^{(n_u)}$ :

$$\min_{\theta^{(1)}, \dots, \theta^{(n_u)}} \frac{1}{2} \sum_{j=1}^{n_u} \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

Given  $\theta^{(1)}, \dots, \theta^{(n_u)}$ , estimate  $x^{(1)}, \dots, x^{(n_m)}$ :

$$\min_{x^{(1)}, \dots, x^{(n_m)}} \frac{1}{2} \sum_{i=1}^{n_m} \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2$$

Minimizing  $x^{(1)}, \dots, x^{(n_m)}$  and  $\theta^{(1)}, \dots, \theta^{(n_u)}$  simultaneously:

$$J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}) = \frac{1}{2} \sum_{(i,j):r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$
$$\min_{\substack{x^{(1)}, \dots, x^{(n_m)} \\ \theta^{(1)}, \dots, \theta^{(n_u)}}} J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$$

## Collaborative filtering algorithm

1. Initialize  $x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)}$  to small random values.
2. Minimize  $J(x^{(1)}, \dots, x^{(n_m)}, \theta^{(1)}, \dots, \theta^{(n_u)})$  using gradient descent (or an advanced optimization algorithm). E.g. for every  $j = 1, \dots, n_u, i = 1, \dots, n_m$  :

$$x_k^{(i)} := x_k^{(i)} - \alpha \left( \sum_{j:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) \theta_k^{(j)} + \lambda x_k^{(i)} \right)$$
$$\theta_k^{(j)} := \theta_k^{(j)} - \alpha \left( \sum_{i:r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)}) x_k^{(i)} + \lambda \theta_k^{(j)} \right)$$

3. For a user with parameters  $\theta$  and a movie with (learned) features  $x$ , predict a star rating of  $\theta^T x$ .



# Vectorization:


## Low rank matrix factorization

# Collaborative filtering

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)
Love at last	5	5	0	0
Romance forever	5	?	?	0
Cute puppies of love	?	4	0	?
Nonstop car chases	0	0	5	4
Swords vs. karate	0	0	5	?

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

$y^{(i,j)}$



# Collaborative filtering

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 \\ 5 & ? & ? & 0 \\ ? & 4 & 0 & ? \\ 0 & 0 & 5 & 4 \\ 0 & 0 & 5 & 0 \end{bmatrix}$$

Predicted ratings:

$$\begin{bmatrix} (\theta^{(1)})^T(x^{(1)}) & (\theta^{(2)})^T(x^{(1)}) & \dots & (\theta^{(n_u)})^T(x^{(1)}) \\ (\theta^{(1)})^T(x^{(2)}) & (\theta^{(2)})^T(x^{(2)}) & \dots & (\theta^{(n_u)})^T(x^{(2)}) \\ \vdots & \vdots & \vdots & \vdots \\ (\theta^{(1)})^T(x^{(n_m)}) & (\theta^{(2)})^T(x^{(n_m)}) & \dots & (\theta^{(n_u)})^T(x^{(n_m)}) \end{bmatrix}$$

$X\Theta^T$



$$X = \begin{bmatrix} - & (x^{(1)})^T & - \\ & \vdots & \\ - & (x^{(n_m)})^T & - \end{bmatrix}$$

$$\Theta = \begin{bmatrix} - & (\theta^{(1)})^T & - \\ & \vdots & \\ - & (\theta^{(n_u)})^T & - \end{bmatrix}$$

→ Low rank matrix factorization

## Finding related movies

For each product  $i$ , we learn a feature vector  $x^{(i)} \in \mathbb{R}^n$ .

→  $x_1 = \text{romance}$ ,  $x_2 = \text{action}$ ,  $x_3 = \text{comedy}$ ,  $x_4 = \dots$

How to find movies  $j$  related to movie  $i$ ?

Small  $\|x^{(i)} - x^{(j)}\| \rightarrow$  movies  $j$  and  $i$  are "similar"

5 most similar movies to movie  $i$ :

Find the 5 movies  $j$  with the smallest  $\|x^{(i)} - x^{(j)}\|$ .

Implementational detail:  
Mean normalization

# Users who have not rated any movies

Movie	Alice (1)	Bob (2)	Carol (3)	Dave (4)	Eve (5)
Love at last	5	5	0	0	?
Romance forever	5	?	?	0	?
Cute puppies of love	?	4	0	?	?
Nonstop car chases	0	0	5	4	?
Swords vs. karate	0	0	5	?	?

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix}$$

$$\min_{\substack{x^{(1)}, \dots, x^{(n_m)} \\ \theta^{(1)}, \dots, \theta^{(n_u)}}} \frac{1}{2} \sum_{(i,j): r(i,j)=1} ((\theta^{(j)})^T x^{(i)} - y^{(i,j)})^2 + \frac{\lambda}{2} \sum_{i=1}^{n_m} \sum_{k=1}^n (x_k^{(i)})^2 + \frac{\lambda}{2} \sum_{j=1}^{n_u} \sum_{k=1}^n (\theta_k^{(j)})^2$$

## Mean Normalization:

$$Y = \begin{bmatrix} 5 & 5 & 0 & 0 & ? \\ 5 & ? & ? & 0 & ? \\ ? & 4 & 0 & ? & ? \\ 0 & 0 & 5 & 4 & ? \\ 0 & 0 & 5 & 0 & ? \end{bmatrix} \quad \mu = \begin{bmatrix} 2.5 \\ 2.5 \\ 2 \\ 2.25 \\ 1.25 \end{bmatrix} \rightarrow Y = \begin{bmatrix} 2.5 & 2.5 & -2.5 & -2.5 & ? \\ 2.5 & ? & ? & -2.5 & ? \\ ? & 2 & -2 & ? & ? \\ -2.25 & -2.25 & 2.75 & 1.75 & ? \\ -1.25 & -1.25 & 3.75 & -1.25 & ? \end{bmatrix}$$

For user  $j$ , on movie  $i$  predict:

$$\rightarrow (\theta^{(j)})^T (x^{(i)}) + \mu_i$$

Learn  $\theta^{(j)}, x^{(i)}$

User 5 (Eve):

$$\theta^{(5)} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

$$\underbrace{(\theta^{(5)})^T (x^{(i)})}_{=0} + \mu_i$$