Q1) Adam is working in an IT company. He has been given a task to reduce the load of a system by killing some of the processes running in the LINUX operating system. Which commands will he use to complete the given task with the help of the following operation?

- Kill Processes by name
- Kill a process based on the process name
- Kill a single process at a time with the given process ID

Q2) Write a program for process creation using C

- Orphan Process
- Zombie Process

Q3) Create the process using fork 0 system call

- Child Process creation
- Parent Process creation
- PPID and PID

```
labex:project/ $ mkdir os_practical_4
labex:project/ $ cd os_practical_4
labex:os_practical_4/ $ touch fork.c
labex:os_practical_4/ $ touch orphan.c
labex:os_practical_4/ $ touch zomie.c
labex:os_practical_4/ $ nano fork.c
labex:os_practical_4/ $ nano orphan,c
labex:os_practical_4/ $ nano orphan.c
labex:os_practical_4/ $ nano zombie.c
labex:os_practical_4/ $ gcc fork.c -o fork
labex:os_practical_4/ $ gcc orphan.c -o orphan
labex:os_practical_4/ $ gcc zombie.c -o zombie
labex:os_practical_4/ $ ./fork
Parent Process:
  PID = 8821
  Child PID = 8822
Child Process:
  PID = 8822
  Parent PID = 1
labex:os_practical_4/ $ ./orphan
Parent Process:
  PID = 8858
  Exiting parent...
labex:os_practical_4/ $ Child Process (Orphan):
  PID = 8859
  Parent PID (now 1 or init) = 1

labex:os_practical_4/ $ ps aux | grep orphan
labex:os_practical_4/ $ ./zombie
Parent Process:
  PID = 9071
  Sleeping for 30 seconds (check with 'ps aux | grep zombie' in another terminal)
Child Process (Zombie):
  PID = 9072
  Exiting child...

  Parent exiting...
labex:os_practical_4/ $
labex:os_practical_4/ $ ps aux | grep zombie
labex       9191  0.0  0.0   3464  1660 pts/13   S+   23:51   0:00 grep --color=auto --exclude-dir=.bzr --exclude-dir=CVS --exclude-dir=.git --exclude-dir=.hg
 --exclude-dir=.svn --exclude-dir=.idea --exclude-dir=.tox zombie
labex:os_practical_4/ $
```