# Advances in Robotics (AIR 2017)

3<sup>rd</sup> International Conference of Robotics Society of India June 28-July 2, 2017 Indian Institute of Technology Delhi, New Delhi, India



# Robotic cloth manipulation for clothing assistance task using Dynamic Movement Primitives

Ravi P. Joshi<sup>a</sup>, Nishanth Koganti<sup>a,b</sup>, and Tomohiro Shibata<sup>a</sup>

 $^a$  Graduate School of Life Science and Systems Engineering, Kyushu Institute of Technology, Kitakyushu, Japan

 $^b$ Graduate School of Information Science, Nara Institute of Science and Technology, Nara, Japan

June 29, 2017





## Outline

- 1 Introduction
- 2 Related Works
- 3 Dynamic Movement Primitives
- 4 Setup and Experiment
- **5** Experiments and Results
- 6 Discussion and Conclusion
- 7 Future work

### Introduction

- Clothing assistance is a basic and important assistance activity in the daily life of the elderly and disabled people
- Need of robotic clothing assistance is growing



## Major challenges involved

- Close interaction of the robot with non-rigid clothing article
- Safe human-robot interaction
- Estimation of human-cloth relationship

Ravi P. Joshi AIR 2017 1 / 10

### Related Works

# Towner et al.<sup>1</sup>, Manipulating clothing article by dual-arm robot

- Used Hidden Markov Model for tracking
- Triangulated mesh model for simulating clothing article
- Highly depends on simulated contour information.



# Tamei $et \ al.^2$ , Clothing assistance with dual-arm robot

- Used Reinforcement learning (RL)
- Topology coordinates for human and cloth extremities relationship
- Via-point trajectory with minimum jerk criterion



<sup>&</sup>lt;sup>1</sup>Marco Cusumano-Towner et al. "Bringing clothing into desired configurations with limited perception". In: *Robotics and Automation (ICRA)*, 2011 IEEE International Conference on. IEEE. 2011, pp. 3893–3900.

<sup>&</sup>lt;sup>2</sup>Tomoya Tamei et al. "Reinforcement learning of clothing assistance with a dual-arm robot". In: *Humanoid Robots (Humanoids), 2011 11th IEEE-RAS International Conference on.* IEEE. 2011, pp. 733–738.

# Dynamic Movement Primitives (DMP)

### DMP in a nutshell

- It is used for generating a control signal to guide the real system<sup>3</sup>
- It can represent *nonlinear* motion with a set of differential equations

The system is defined as

$$\ddot{y} = \alpha_y(\beta_y(g-y) - \dot{y}) + f$$

where:

- $\bullet$  y is system state and g is goal state
- $\alpha$  and  $\beta$  are gain terms
- $\bullet$  f is nonlinear function defined over time

f is a function of canonical system, denoted by x as  $\dot{x} = -\alpha_x x$ 

Ravi P. Joshi AIR 2017 3 / 10

<sup>&</sup>lt;sup>3</sup>Stefan Schaal. "Dynamic movement primitives-a framework for motor control in humans and humanoid robotics". In: Adaptive Motion of Animals and Machines. Springer, 2006, pp. 261–280.

# Forcing function f

$$f$$
 is defined as 
$$f(x,g) = \frac{\sum_{i=1}^{N} \psi_i w_i}{\sum_{i=1}^{N} \psi_i} x(g - y_0)$$

where:

- $y_0$  is the initial state of the system
- $w_i$  is a weighting for a given basis function  $\psi_i$
- $\psi_i = \exp\left(-h_i(x-c_i)^2\right)$  is Gaussian with mean  $c_i$  and variance  $h_i$

## Imitating a desired path

The desired forcing term f which affects the system acceleration, is written as  $\mathbf{f}_d = \ddot{\mathbf{y}}_d - \alpha_v(\beta_v(q - \mathbf{y}) - \dot{\mathbf{y}})$ 

where

•  $\mathbf{y}_d$  is desired trajectory, given by  $\ddot{\mathbf{y}}_d = \frac{\partial}{\partial t}\dot{\mathbf{y}}_d = \frac{\partial}{\partial t}\frac{\partial}{\partial t}\mathbf{y}_d$ 

Choose the weights over the basis functions i.e., minimize<sup>4</sup>

$$\sum_{t} \psi_{i}(t) \left[ f_{d}(t) - w_{i} \left\{ x(t) (q - y_{0}) \right\} \right]^{2}$$

Ravi P. Joshi

AIR 2017

<sup>&</sup>lt;sup>4</sup>Stefan Schaal, Christopher G Atkeson, and Sethu Vijayakumar. "Scalable techniques from nonparametric statistics for real time robot learning". In: *Applied Intelligence* 17.1 (2002), pp. 49–60.


# Workflow of Robotic cloth manipulation task

# Teaching Phase A demonstration is performed by moving the

A demonstration is performed by moving the Baxter arms in the appropriate trajectory


### Learn Trajectory

Baxter Left Arm Trajectory



Recorded trajectory is parameterized by DMP

### DMP Generalization



Arms posture of the mannequin is changed.


Accordingly goal parameter of DMP is modified

#### Testing Phase





DMP can accommodate any posture by changing goal parameter

# Setup



# Experiments and Results





Old & modified posture of mannequin


Left arm trajectories of Baxter Robot

Video Demonstration

# Accuracy measurement

Angle of Inclination measures the bending of arms w.r.t. horizontal line in two-dimensional space





Ravi P. Joshi AIR 2017 8 / 10

## Discussion and Conclusion

- Robotic clothing assistance is challenging since it requires cooperative manipulation
- Clothing article inherits non-rigid and highly deformable properties
- Result shows that DMPs are able to generalize the movement trajectory
- DMP should incorporate orientation information as well

### Future work

- Make approach more robust by using combination of visual and force information
- Need for designing an adaptive controller
  - For real-time tracking of mannequin
  - To adapt various failure scenarios

# Acknowledgments

This work was supported in part by the Grant-in-Aid for Scientific Research from Japan Society for the Promotion of Science (No. 16H01749).

Ravi P. Joshi AIR 2017 10 / 10

### References



Bishop, Christopher M. Pattern Recognition and Machine Learning. Springer, 2006.



Cusumano-Towner, Marco et al. "Bringing clothing into desired configurations with limited perception". In: Robotics and Automation (ICRA), 2011 IEEE International Conference on. IEEE. 2011, pp. 3893-3900.



Fitzgerald, Cliff. "Developing baxter". In: Technologies for Practical Robot Applications (TePRA), 2013 IEEE International Conference on. IEEE. 2013, pp. 1-6.



Ijspeert, AJ, J Nakanishi, and S Schaal. "Learning control policies for movement imitation and movement recognition". In: Neural information processing system. Vol. 15, 2003, pp. 1547-1554.



Ijspeert, Auke Jan, Jun Nakanishi, and Stefan Schaal. "Movement imitation with nonlinear dynamical systems in humanoid robots". In: Robotics and Automation, 2002. Proceedings. ICRA'02. IEEE International Conference on. Vol. 2. IEEE. 2002, pp. 1398-1403.



Schaal, Stefan. "Dynamic movement primitives-a framework for motor control in humans and humanoid robotics". In: Adaptive Motion of Animals and Machines. Springer, 2006, pp. 261– 280.



Schaal, Stefan, Christopher G Atkeson, and Sethu Vijayakumar. "Scalable techniques from non-parametric statistics for real time robot learning". In: Applied Intelligence 17.1 (2002), pp. 49–60.



Tamei, Tomoya et al. "Reinforcement learning of clothing assistance with a dual-arm robot". In: Humanoid Robots (Humanoids), 2011 11th IEEE-RAS International Conference on. IEEE. 2011, pp. 733-738.

Ravi P. Joshi AIR 2017 10 / 10

# Thanks for your attention!

Any questions?

www.ravijoshi.xyz

Ravi P. Joshi AIR 2017 10 / 10