



Computational Thinking

Prof. Madhavan Mukund

Department of Computer Science
Chennai Mathematical Institute

Prof. G. Venkatesh

Indian Institute of Technology Madras

Mr. Omkar Joshi

Course Instructor
IITM Online Degree Programme



Computational Thinking

Tutorial on pseudocode for recursion
and Depth First Search (DFS)

Content

- Recursion
- Pseudocode for factorial (iterative process)
- Pseudocode for factorial (recursive procedure)
- Depth First Search (DFS)

Recursion

- Recursion is a process in which a procedure calls itself.
- All problems can not be solved using recursion.
- Only those problems which have a base condition can be solved using recursion.
- Recursion simplifies the pseudocode.

Pseudocode to find the factorial of a number

Procedure factorial (n)

 fact = 1

 while (n > 0) {

 fact = fact * n

 n = n - 1

 }

 return (fact)

End factorial

Pseudocode to find the factorial of a number

Procedure factorial (n)

fact = 1

while (n > 0) {

fact = fact * n

n = n - 1

}

return (fact)

End factorial



Recursion

Procedure factorial (n)

if (n == 0) {

return (1)

}

else {

return (n * factorial (n - 1))

}

End factorial

Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (n)

```
    if (n == 0) {  
        return (1)  
    }  
    else {  
        return (n * factorial (n - 1))  
    }
```

End factorial

Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (5)

 if (5 == 0) {

 return (1)

 }

 else {

 return (5 * factorial (5 - 1))

 }

End factorial

Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Procedure factorial (2)

```
if (2 == 0) {  
    return (1)  
}  
else {  
    return (2 * factorial (2 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (2)

```
if (2 == 0) {  
    return (1)  
}  
else {  
    return (2 * factorial (2 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (1)

```
if (1 == 0) {  
    return (1)  
}  
else {  
    return (1 * factorial (1 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (2)

```
if (2 == 0) {  
    return (1)  
}  
else {  
    return (2 * factorial (2 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (1)

```
if (1 == 0) {  
    return (1)  
}  
else {  
    return (1 * factorial (1 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Procedure factorial (0)

```
if (0 == 0) {  
    return (1)  
}  
else {  
    return (0 * factorial (0 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (2)

```
if (2 == 0) {  
    return (1)  
}  
else {  
    return (2 * factorial (2 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (1)

```
if (1 == 0) {  
    return (1)  
}  
else {  
    return (1 * 1)  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * factorial (3 - 1))  
}
```

End factorial

Procedure factorial (2)

```
if (2 == 0) {  
    return (1)  
}  
else {  
    return (2 * 1)  
}
```

End factorial

Pseudocode to find the factorial using recursion (n = 5)

Procedure factorial (5)

```
if (5 == 0) {  
    return (1)  
}  
else {  
    return (5 * factorial (5 - 1))  
}
```

End factorial

Procedure factorial (4)

```
if (4 == 0) {  
    return (1)  
}  
else {  
    return (4 * factorial (4 - 1))  
}
```

End factorial

Procedure factorial (3)

```
if (3 == 0) {  
    return (1)  
}  
else {  
    return (3 * 2)  
}
```

End factorial

Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (5)

```
    if (5 == 0) {  
        return (1)  
    }  
    else {  
        return (5 * factorial (5 - 1))  
    }  
}
```

End factorial

Procedure factorial (4)

```
    if (4 == 0) {  
        return (1)  
    }  
    else {  
        return (4 * 6)  
    }  
}
```

End factorial


Pseudocode to find the factorial using recursion ($n = 5$)

Procedure factorial (5)

```
    if (5 == 0) {  
        return (1)  
    }  
    else {  
        return (5 * 24)  
    }
```

End factorial


Depth First Search (DFS)



Input graph

Starting vertex = 1

Depth First Search (DFS)




Input graph

Current vertex = 1

①

Depth First Search (DFS)




Input graph

Current vertex = 1

Neighbour = 2, 4

①


Depth First Search (DFS)




Input graph

Current vertex = 2

Neighbour = 3, 5




Depth First Search (DFS)




Input graph

Current vertex = 1

Neighbour = No




Depth First Search (DFS)




Input graph

Current vertex = 5

Neighbour = 4




Depth First Search (DFS)




Input graph

Current vertex = 4


Neighbour = No



Depth First Search (DFS)



Input graph



Output DFS tree