public\assets\editor\clike.js

```
CodeMirror.defineMode("clike", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit,Ð     statementIndentUnit =
parserConfig.statementIndentUnit || indentUnit,Ð     dontAlignCalls =
parserConfig.dontAlignCalls,Ð     keywords = parserConfig.keywords || {},Ð
      builtin = parserConfig.builtin || {},Ð     blockKeywords =
parserConfig.blockKeywords || {},Ð     atoms = parserConfig.atoms || {},Ð
hooks = parserConfig.hooks || {},Ð     multiLineStrings =
parserConfig.multiLineStrings;Ð var isOperatorChar = /[+\-*&%=<>!?|\/]/;Ð var
curPunc;Ð function tokenBase(stream, state) {Ð   var ch = stream.next();Ð
if (hooks[ch]) {Ð     var result = hooks[ch](stream, state);Ð     if (result !
== false) return result;Ð   }Ð   if (ch == '"' || ch == "'") {Ð
state.tokenize = tokenString(ch);Ð     return state.tokenize(stream, state);Ð
    }Ð   if (/[\[\]{}\(\),;\:\.]/.test(ch)) {Ð     curPunc = ch;Ð     return
null;Ð   }Ð   if (/\d/.test(ch)) {Ð     stream.eatWhile(/[\w\.]/);Ð
return "number";Ð   }Ð   if (ch == "/") {Ð     if (stream.eat("*")) {Ð
state.tokenize = tokenComment;Ð       return tokenComment(stream, state);Ð
      }Ð     if (stream.eat("/")) {Ð       stream.skipToEnd();Ð       return
"comment";Ð     }Ð   }Ð   if (isOperatorChar.test(ch)) {Ð
stream.eatWhile(isOperatorChar);Ð     return "operator";Ð   }Ð
stream.eatWhile(/[\w\$_]/);Ð   var cur = stream.current();Ð   if
(keywords.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "keyword";Ð   }Ð   if (builtin.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "builtin";Ð   }Ð   if (atoms.propertyIsEnumerable(cur)) return "atom";Ð
    return "variable";Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, next, end = false;Ð
while ((next = stream.next()) != null) {Ð       if (next == quote && !
escaped) {end = true; break;}Ð       escaped = !escaped && next == "\\";Ð
      }Ð     if (end || !(escaped || multiLineStrings))Ð       state.tokenize
= null;Ð     return "string";Ð   };Ð }Ð function tokenComment(stream, state) {Ð
    var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if (ch ==
"/" && maybeEnd) {Ð       state.tokenize = null;Ð       break;Ð     }Ð
maybeEnd = (ch == "*");Ð   }Ð   return "comment";Ð }Ð function
Context(indented, column, type, align, prev) {Ð   this.indented = indented;Ð
    this.column = column;Ð   this.type = type;Ð   this.align = align;Ð
this.prev = prev;Ð }Ð function pushContext(state, col, type) {Ð   var indent
= state.indented;Ð   if (state.context && state.context.type == "statement")Ð
      indent = state.context.indented;Ð   return state.context = new
Context(indent, col, type, null, state.context);Ð }Ð function
popContext(state) {Ð   var t = state.context.type;Ð   if (t == ")" || t ==
"]" || t == "}")Ð     state.indented = state.context.indented;Ð   return
state.context = state.context.prev;Ð }Ð // InterfaceÐ return {Ð   startState:
function(basecolumn) {Ð     return {Ð       tokenize: null,Ð       context:
new Context((basecolumn || 0) - indentUnit, 0, "top", false),Ð
indented: 0,Ð       startOfLine: trueÐ     };Ð   },Ð   token:
function(stream, state) {Ð     var ctx = state.context;Ð     if
(stream.sol()) {Ð       if (ctx.align == null) ctx.align = false;Ð
state.indented = stream.indentation();Ð       state.startOfLine = true;Ð     }Ð
      if (stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style
= (state.tokenize || tokenBase)(stream, state);Ð     if (style == "comment"
|| style == "meta") return style;Ð     if (ctx.align == null) ctx.align =
true;Ð     if ((curPunc == ";" || curPunc == ":" || curPunc == ",") &&
ctx.type == "statement") popContext(state);Ð     else if (curPunc == "{")
pushContext(state, stream.column(), "}");Ð     else if (curPunc == "[")
pushContext(state, stream.column(), "]");Ð     else if (curPunc == "(")
pushContext(state, stream.column(), ")");Ð     else if (curPunc == "}") {Ð
        while (ctx.type == "statement") ctx = popContext(state);Ð       if
(ctx.type == "}") ctx = popContext(state);Ð
```

```
                                                    while (ctx.type ==
"statement") ctx = popContext(state);Ð     }Ð     else if (curPunc ==
ctx.type) popContext(state);Ð     else if (((ctx.type == "}" || ctx.type ==
"top") && curPunc != ';') || (ctx.type == "statement" && curPunc ==
"newstatement"))Ð       pushContext(state, stream.column(), "statement");Ð
      state.startOfLine = false;Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.tokenize != tokenBase &&
state.tokenize != null) return CodeMirror.Pass;Ð     var ctx = state.context,
firstChar = textAfter && textAfter.charAt(0);Ð     if (ctx.type ==
"statement" && firstChar == "}") ctx = ctx.prev;Ð     var closing = firstChar
== ctx.type;Ð     if (ctx.type == "statement") return ctx.indented +
(firstChar == "{" ? 0 : statementIndentUnit);Ð     else if (dontAlignCalls &&
ctx.type == ")" && !closing) return ctx.indented + statementIndentUnit;Ð
else if (ctx.align) return ctx.column + (closing ? 0 : 1);Ð     else return
ctx.indented + (closing ? 0 : indentUnit);Ð   },Ð   electricChars: "{}"Ð };Ð});Ð
(function() {Ð function words(str) {Ð   var obj = {}, words = str.split(" ");Ð
    for (var i = 0; i < words.length; ++i) obj[words[i]] = true;Ð   return
obj;Ð }Ð var cKeywords = "auto if break int case long char register continue
return default short do sizeof " +Ð   "double static else struct entry switch
extern typedef float union for unsigned " +Ð   "goto while enum void const
signed volatile";Ð function cppHook(stream, state) {Ð   if (!
state.startOfLine) return false;Ð   for (;;) {Ð     if (stream.skipTo("\\")) {Ð
        stream.next();Ð       if (stream.eol()) {Ð         state.tokenize =
cppHook;Ð         break;Ð       }Ð     } else {Ð       stream.skipToEnd();Ð
        state.tokenize = null;Ð       break;Ð     }Ð   }Ð   return "meta";Ð }Ð
  // C#-style strings where "" escapes a quote.Ð function
tokenAtString(stream, state) {Ð   var next;Ð   while ((next = stream.next()) !
= null) {Ð     if (next == '"' && !stream.eat('"')) {Ð       state.tokenize =
null;Ð       break;Ð     }Ð   }Ð   return "string";Ð }Ð function mimes(ms,
mode) {Ð   for (var i = 0; i < ms.length; ++i) CodeMirror.defineMIME(ms[i],
mode);Ð }Ð mimes(["text/x-csrc", "text/x-c", "text/x-chdr"], {Ð   name:
"clike",Ð   keywords: words(cKeywords),Ð   blockKeywords: words("case do else
for if switch while struct"),Ð   atoms: words("null"),Ð   hooks: {"#":
cppHook}Ð });Ð mimes(["text/x-c++src", "text/x-c++hdr"], {Ð   name: "clike",Ð
    keywords: words(cKeywords + " asm dynamic_cast namespace reinterpret_cast
try bool explicit new " +Ð                    "static_cast typeid catch
operator template typename class friend private " +Ð                   "this
using const_cast inline public throw virtual delete mutable protected " +Ð
                    "wchar_t"),Ð   blockKeywords: words("catch class do else
finally for if struct switch try while"),Ð   atoms: words("true false null"),Ð
    hooks: {"#": cppHook}Ð });Ð CodeMirror.defineMIME("text/x-java", {Ð
name: "clike",Ð   keywords: words("abstract assert boolean break byte case
catch char class const continue default " +Ð                    "do double
else enum extends final finally float for goto if implements import " +Ð
                    "instanceof int interface long native new package private
protected public " +Ð                    "return short static strictfp super
switch synchronized this throw throws transient " +Ð                   "try
void volatile while"),Ð   blockKeywords: words("catch class do else finally
for if switch try while"),Ð   atoms: words("true false null"),Ð   hooks: {Ð
      "@": function(stream) {Ð       stream.eatWhile(/[\w\$_]/);Ð
return "meta";Ð     }Ð   }Ð });Ð CodeMirror.defineMIME("text/x-csharp", {Ð
name: "clike",Ð   keywords: words("abstract as base break case catch checked
class const continue" +Ð                    " default delegate do else enum
event explicit extern finally fixed for" +Ð                    " foreach goto
if implicit in interface internal is lock namespace new" +Ð
" operator out override params private protected public readonly ref return
sealed" +Ð                    " sizeof stackalloc static struct switch this
throw try typeof unchecked" +Ð                    " unsafe using virtual void
volatile while add alias ascending descending dynamic from get" +Ð
                    " global group into join let orderby partial remove
select set value var yield"),Ð
```

```
                                  blockKeywords: words("catch class do else
finally for foreach if struct switch try while"),Ð   builtin: words("Boolean
Byte Char DateTime DateTimeOffset Decimal Double" +Ð                   " Guid
Int16 Int32 Int64 Object SByte Single String TimeSpan UInt16 UInt32" +Ð
                    " UInt64 bool byte char decimal double short int long
object"  +Ð                   " sbyte float string ushort uint ulong"),Ð
atoms: words("true false null"),Ð   hooks: {Ð     "@": function(stream,
state) {Ð       if (stream.eat('"')) {Ð         state.tokenize =
tokenAtString;Ð         return tokenAtString(stream, state);Ð       }Ð
stream.eatWhile(/[\w\$_]/);Ð       return "meta";Ð     }Ð   }Ð });Ð
CodeMirror.defineMIME("text/x-scala", {Ð   name: "clike",Ð   keywords: words(Ð
      /* scala */Ð     "abstract case catch class def do else extends false
final finally for forSome if " +Ð     "implicit import lazy match new null
object override package private protected return " +Ð     "sealed super this
throw trait try trye type val var while with yield _ : = => <- <: " +Ð
"<% >: # @ " +Ð     /* package scala */Ð     "assert assume require print
println printf readLine readBoolean readByte readShort " +Ð     "readChar
readInt readLong readFloat readDouble " +Ð     "AnyVal App Application Array
BufferedIterator BigDecimal BigInt Char Console Either " +Ð     "Enumeration
Equiv Error Exception Fractional Function IndexedSeq Integral Iterable " +Ð
      "Iterator List Map Numeric Nil NotNull Option Ordered Ordering
PartialFunction PartialOrdering " +Ð     "Product Proxy Range Responder Seq
Serializable Set Specializable Stream StringBuilder " +Ð     "StringContext
Symbol Throwable Traversable TraversableOnce Tuple Unit Vector :: #:: " +Ð
      /* package java.lang */Ð     "Boolean Byte Character CharSequence Class
ClassLoader Cloneable Comparable " +Ð     "Compiler Double Exception Float
Integer Long Math Number Object Package Pair Process " +Ð     "Runtime
Runnable SecurityManager Short StackTraceElement StrictMath String " +Ð
"StringBuffer System Thread ThreadGroup ThreadLocal Throwable Triple Void"Ð
    ),Ð   blockKeywords: words("catch class do else finally for forSome if
match switch try while"),Ð   atoms: words("true false null"),Ð   hooks: {Ð
      "@": function(stream) {Ð       stream.eatWhile(/[\w\$_]/);Ð
return "meta";Ð     }Ð   }Ð });Ð});Ð
```

public\assets\editor\codemirror.js

```
// CodeMirror version 3.12Ð/Ð/ CodeMirror is the only global var we claimÐ
window.CodeMirror = (function() {Ð "use strict";Ð // BROWSER SNIFFINGÐ //
Crude, but necessary to handle a number of hard-to-feature-detectÐ // bugs
and behavior differences.Ð var gecko = /gecko\/\d/i.test(navigator.userAgent);Ð
  var ie = /MSIE \d/.test(navigator.userAgent);Ð var ie_lt8 = ie &&
(document.documentMode == null || document.documentMode < 8);Ð var ie_lt9 =
ie && (document.documentMode == null || document.documentMode < 9);Ð var
webkit = /WebKit\//.test(navigator.userAgent);Ð var qtwebkit = webkit && /Qt\/
\d+\.\d+/.test(navigator.userAgent);Ð var chrome = /
Chrome\//.test(navigator.userAgent);Ð var opera = /
Opera\//.test(navigator.userAgent);Ð var safari = /Apple
Computer/.test(navigator.vendor);Ð var khtml = /
KHTML\//.test(navigator.userAgent);Ð var mac_geLion = /Mac OS X 1\d\D([7-9]|
\d\d)\D/.test(navigator.userAgent);Ð var mac_geMountainLion = /Mac OS X
1\d\D([8-9]|\d\d)\D/.test(navigator.userAgent);Ð var phantom = /
PhantomJS/.test(navigator.userAgent);Ð var ios = /
AppleWebKit/.test(navigator.userAgent) && /Mobile\/
\w+/.test(navigator.userAgent);Ð // This is woefully incomplete. Suggestions
for alternative methods welcome.Ð var mobile = ios || /Android|webOS|
BlackBerry|Opera Mini|Opera Mobi|IEMobile/i.test(navigator.userAgent);Ð var
mac = ios || /Mac/.test(navigator.platform);Ð var windows = /windows/
i.test(navigator.platform);Ð var opera_version = opera &&
navigator.userAgent.match(/Version\/(\d*\.\d*)/);Ð if (opera_version)
opera_version = Number(opera_version[1]);Ð // Some browsers use the wrong
event properties to signal cmd/ctrl on OS XÐ var flipCtrlCmd = mac &&
(qtwebkit || opera && (opera_version == null || opera_version < 12.11));Ð var
captureMiddleClick = gecko || (ie && !ie_lt9);Ð // Optimize some code when
these features are not usedÐ var sawReadOnlySpans = false, sawCollapsedSpans
= false;Ð // CONSTRUCTORÐ function CodeMirror(place, options) {Ð   if (!(this
instanceof CodeMirror)) return new CodeMirror(place, options);Ð
this.options = options = options || {};Ð   // Determine effective options
based on given values and defaults.Ð   for (var opt in defaults) if (!
options.hasOwnProperty(opt) && defaults.hasOwnProperty(opt))Ð
options[opt] = defaults[opt];Ð   setGuttersForLineNumbers(options);Ð   var
docStart = typeof options.value == "string" ? 0 : options.value.first;Ð   var
display = this.display = makeDisplay(place, docStart);Ð
display.wrapper.CodeMirror = this;Ð   updateGutters(this);Ð   if
(options.autofocus && !mobile) focusInput(this);Ð   this.state = {keyMaps: [],Ð
                  overlays: [],Ð                  modeGen: 0,Ð
overwrite: false, focused: false,Ð                  suppressEdits: false,
pasteIncoming: false,Ð                  draggingText: false,Ð
highlight: new Delayed()};Ð   themeChanged(this);Ð   if (options.lineWrapping)Ð
      this.display.wrapper.className += " CodeMirror-wrap";Ð   var doc =
options.value;Ð   if (typeof doc == "string") doc = new Doc(options.value,
options.mode);Ð   operation(this, attachDoc)(this, doc);Ð   // Override magic
textarea content restore that IE sometimes doesÐ   // on our hidden textarea
on reloadÐ   if (ie) setTimeout(bind(resetInput, this, true), 20);Ð
registerEventHandlers(this);Ð   // IE throws unspecified error in certain
cases, whenÐ   // trying to access activeElement before onloadÐ   var
hasFocus; try { hasFocus = (document.activeElement == display.input); }
catch(e) { }Ð   if (hasFocus || (options.autofocus && !mobile))
setTimeout(bind(onFocus, this), 20);Ð   else onBlur(this);Ð   operation(this,
function() {Ð     for (var opt in optionHandlers)Ð       if
(optionHandlers.propertyIsEnumerable(opt))Ð         optionHandlers[opt](this,
options[opt], Init);Ð     for (var i = 0; i < initHooks.length; ++i)
initHooks[i](this);Ð   })();Ð }Ð // DISPLAY CONSTRUCTORÐ function
makeDisplay(place, docStart) {Ð   var d = {};Ð   var input = d.input =
elt("textarea", null, null, "position: absolute; padding: 0; width: 1px;
height: 1em; outline: none; font-size: 4px;");Ð
```

```
                                                    if (webkit)
input.style.width = "1000px";Ð   else input.setAttribute("wrap", "off");Ð
    // if border: 0; -- iOS fails to open keyboard (issue #1287)Ð   if (ios)
input.style.border = "1px solid black";Ð   input.setAttribute("autocorrect",
"off"); input.setAttribute("autocapitalize", "off");Ð   // Wraps and hides
input textareaÐ   d.inputDiv = elt("div", [input], null, "overflow: hidden;
position: relative; width: 3px; height: 0px;");Ð   // The actual fake
scrollbars.Ð   d.scrollbarH = elt("div", [elt("div", null, null, "height:
1px")], "CodeMirror-hscrollbar");Ð   d.scrollbarV = elt("div", [elt("div",
null, null, "width: 1px")], "CodeMirror-vscrollbar");Ð   d.scrollbarFiller =
elt("div", null, "CodeMirror-scrollbar-filler");Ð   // DIVs containing the
selection and the actual codeÐ   d.lineDiv = elt("div");Ð   d.selectionDiv =
elt("div", null, null, "position: relative; z-index: 1");Ð   // Blinky
cursor, and element used to ensure cursor fits at the end of a lineÐ
d.cursor = elt("div", "\u00a0", "CodeMirror-cursor");Ð   // Secondary cursor,
shown when on a 'jump' in bi-directional textÐ   d.otherCursor = elt("div",
"\u00a0", "CodeMirror-cursor CodeMirror-secondarycursor");Ð   // Used to
measure text sizeÐ   d.measure = elt("div", null, "CodeMirror-measure");Ð
    // Wraps everything that needs to exist inside the vertically-padded
coordinate systemÐ   d.lineSpace = elt("div", [d.measure, d.selectionDiv,
d.lineDiv, d.cursor, d.otherCursor],Ð                        null, "position:
relative; outline: none");Ð   // Moved around its parent to cover visible viewÐ
    d.mover = elt("div", [elt("div", [d.lineSpace], "CodeMirror-lines")],
null, "position: relative");Ð   // Set to the height of the text, causes
scrollingÐ   d.sizer = elt("div", [d.mover], "CodeMirror-sizer");Ð   // D is
needed because behavior of elts with overflow: auto and padding is
inconsistent across browsersÐ   d.heightForcer = elt("div", null, null,
"position: absolute; height: " + scrollerCutOff + "px; width: 1px;");Ð   //
Will contain the gutters, if anyÐ   d.gutters = elt("div", null, "CodeMirror-
gutters");Ð   d.lineGutter = null;Ð   // Helper element to properly size the
gutter backgroundsÐ   var scrollerInner = elt("div", [d.sizer,
d.heightForcer, d.gutters], null, "position: relative; min-height: 100%");Ð
    // Provides scrollingÐ   d.scroller = elt("div", [scrollerInner],
"CodeMirror-scroll");Ð   d.scroller.setAttribute("tabIndex", "-1");Ð   // The
element in which the editor lives.Ð   d.wrapper = elt("div", [d.inputDiv,
d.scrollbarH, d.scrollbarV,Ð                             d.scrollbarFiller,
d.scroller], "CodeMirror");Ð   // Work around IE7 z-index bugÐ   if (ie_lt8)
{ d.gutters.style.zIndex = -1; d.scroller.style.paddingRight = 0; }Ð   if
(place.appendChild) place.appendChild(d.wrapper); else place(d.wrapper);Ð
    // Needed to hide big blue blinking cursor on Mobile SafariÐ   if (ios)
input.style.width = "0px";Ð   if (!webkit) d.scroller.draggable = true;Ð   //
Needed to handle Tab key in KHTMLÐ   if (khtml) { d.inputDiv.style.height =
"1px"; d.inputDiv.style.position = "absolute"; }Ð   // Need to set a minimum
width to see the scrollbar on IE7 (but must not set it on IE8).Ð   else if
(ie_lt8) d.scrollbarH.style.minWidth = d.scrollbarV.style.minWidth = "18px";Ð
    // Current visible range (may be bigger than the view window).Ð
d.viewOffset = d.lastSizeC = 0;Ð   d.showingFrom = d.showingTo = docStart;Ð
    // Used to only resize the line number gutter when necessary (whenÐ   //
the amount of lines crosses a boundary that makes its width change)Ð
d.lineNumWidth = d.lineNumInnerWidth = d.lineNumChars = null;Ð   // See
readInput and resetInputÐ   d.prevInput = "";Ð   // Set to true when a non-
horizontal-scrolling widget is added. AsÐ   // an optimization, widget
aligning is skipped when d is false.Ð   d.alignWidgets = false;Ð   // Flag
that indicates whether we currently expect input to appearÐ   // (after some
event like 'keypress' or 'input') and are pollingÐ   // intensively.Ð
d.pollingFast = false;Ð   // Self-resetting timeout for the pollerÐ   d.poll
= new Delayed();Ð   d.cachedCharWidth = d.cachedTextHeight = null;Ð
d.measureLineCache = [];Ð   d.measureLineCachePos = 0;Ð   // Tracks when
resetInput has punted to just putting a shortÐ   // string instead of the
(large) selection.Ð
```

```
                    d.inaccurateSelection = false;Ð   // Tracks the maximum
line length so that the horizontal scrollbarÐ   // can be kept static when
scrolling.Ð   d.maxLine = null;Ð   d.maxLineLength = 0;Ð   d.maxLineChanged =
false;Ð   // Used for measuring wheel scrolling granularityÐ   d.wheelDX =
d.wheelDY = d.wheelStartX = d.wheelStartY = null;Ð   return d;Ð }Ð // STATE
UPDATESÐ // Used to get the editor into a consistent state again when options
change.Ð function loadMode(cm) {Ð   cm.doc.mode =
CodeMirror.getMode(cm.options, cm.doc.modeOption);Ð
cm.doc.iter(function(line) {Ð     if (line.stateAfter) line.stateAfter = null;Ð
      if (line.styles) line.styles = null;Ð   });Ð   cm.doc.frontier =
cm.doc.first;Ð   startWorker(cm, 100);Ð   cm.state.modeGen++;Ð   if
(cm.curOp) regChange(cm);Ð }Ð function wrappingChanged(cm) {Ð   if
(cm.options.lineWrapping) {Ð     cm.display.wrapper.className += " CodeMirror-
wrap";Ð     cm.display.sizer.style.minWidth = "";Ð   } else {Ð
cm.display.wrapper.className = cm.display.wrapper.className.replace(" 
CodeMirror-wrap", "");Ð     computeMaxLength(cm);Ð   }Ð
estimateLineHeights(cm);Ð   regChange(cm);Ð   clearCaches(cm);Ð
setTimeout(function(){updateScrollbars(cm.display, cm.doc.height);}, 100);Ð }Ð
  function estimateHeight(cm) {Ð   var th = textHeight(cm.display), wrapping
= cm.options.lineWrapping;Ð   var perLine = wrapping && Math.max(5,
cm.display.scroller.clientWidth / charWidth(cm.display) - 3);Ð   return
function(line) {Ð     if (lineIsHidden(cm.doc, line))Ð       return 0;Ð
else if (wrapping)Ð       return (Math.ceil(line.text.length / perLine) || 1)
* th;Ð     elseÐ       return th;Ð   };Ð }Ð function estimateLineHeights(cm) {Ð
    var doc = cm.doc, est = estimateHeight(cm);Ð   doc.iter(function(line) {Ð
      var estHeight = est(line);Ð     if (estHeight != line.height)
updateLineHeight(line, estHeight);Ð   });Ð }Ð function keyMapChanged(cm) {Ð
var style = keyMap[cm.options.keyMap].style;Ð   cm.display.wrapper.className
= cm.display.wrapper.className.replace(/\s*cm-keymap-\S+/g, "") +Ð
(style ? " cm-keymap-" + style : "");Ð }Ð function themeChanged(cm) {Ð
cm.display.wrapper.className = cm.display.wrapper.className.replace(/\s*cm-s-
\S+/g, "") +Ð     cm.options.theme.replace(/(^|\s)\s*/g, " cm-s-");Ð
clearCaches(cm);Ð }Ð function guttersChanged(cm) {Ð   updateGutters(cm);Ð
regChange(cm);Ð }Ð function updateGutters(cm) {Ð   var gutters =
cm.display.gutters, specs = cm.options.gutters;Ð   removeChildren(gutters);Ð
    for (var i = 0; i < specs.length; ++i) {Ð     var gutterClass = specs[i];Ð
      var gElt = gutters.appendChild(elt("div", null, "CodeMirror-gutter " +
gutterClass));Ð     if (gutterClass == "CodeMirror-linenumbers") {Ð
cm.display.lineGutter = gElt;Ð       gElt.style.width =
(cm.display.lineNumWidth || 1) + "px";Ð     }Ð   }Ð   gutters.style.display =
i ? "" : "none";Ð }Ð function lineLength(doc, line) {Ð   if (line.height ==
0) return 0;Ð   var len = line.text.length, merged, cur = line;Ð   while
(merged = collapsedSpanAtStart(cur)) {Ð     var found = merged.find();Ð
cur = getLine(doc, found.from.line);Ð     len += found.from.ch - found.to.ch;Ð
    }Ð   cur = line;Ð   while (merged = collapsedSpanAtEnd(cur)) {Ð     var
found = merged.find();Ð     len -= cur.text.length - found.from.ch;Ð     cur
= getLine(doc, found.to.line);Ð     len += cur.text.length - found.to.ch;Ð   }Ð
    return len;Ð }Ð function computeMaxLength(cm) {Ð   var d = cm.display,
doc = cm.doc;Ð   d.maxLine = getLine(doc, doc.first);Ð   d.maxLineLength =
lineLength(doc, d.maxLine);Ð   d.maxLineChanged = true;Ð
doc.iter(function(line) {Ð     var len = lineLength(doc, line);Ð     if (len
> d.maxLineLength) {Ð       d.maxLineLength = len;Ð       d.maxLine = line;Ð
      }Ð   });Ð }Ð // Make sure the gutters options contains the elementÐ //
"CodeMirror-linenumbers" when the lineNumbers option is true.Ð function
setGuttersForLineNumbers(options) {Ð   var found = false;Ð   for (var i = 0;
i < options.gutters.length; ++i) {Ð     if (options.gutters[i] == "CodeMirror-
linenumbers") {Ð       if (options.lineNumbers) found = true;Ð       else
options.gutters.splice(i--, 1);Ð     }Ð   }Ð   if (!found &&
options.lineNumbers)Ð     options.gutters.push("CodeMirror-linenumbers");Ð }Ð
  // SCROLLBARSÐ
```

```
                Ð // Re-synchronize the fake scrollbars with the actual size
of theÐ // content. Optionally force a scrollTop.Ð function
updateScrollbars(d /* display */, docHeight) {Ð   var totalHeight = docHeight
+ paddingVert(d);Ð   d.sizer.style.minHeight = d.heightForcer.style.top =
totalHeight + "px";Ð   var scrollHeight = Math.max(totalHeight,
d.scroller.scrollHeight);Ð   var needsH = d.scroller.scrollWidth >
d.scroller.clientWidth;Ð   var needsV = scrollHeight >
d.scroller.clientHeight;Ð   if (needsV) {Ð     d.scrollbarV.style.display =
"block";Ð     d.scrollbarV.style.bottom = needsH ? scrollbarWidth(d.measure)
+ "px" : "0";Ð     d.scrollbarV.firstChild.style.height =Ð
(scrollHeight - d.scroller.clientHeight + d.scrollbarV.clientHeight) + "px";Ð
    } else d.scrollbarV.style.display = "";Ð   if (needsH) {Ð
d.scrollbarH.style.display = "block";Ð     d.scrollbarH.style.right =
needsV ? scrollbarWidth(d.measure) + "px" : "0";Ð
d.scrollbarH.firstChild.style.width =Ð       (d.scroller.scrollWidth -
d.scroller.clientWidth + d.scrollbarH.clientWidth) + "px";Ð   } else
d.scrollbarH.style.display = "";Ð   if (needsH && needsV) {Ð
d.scrollbarFiller.style.display = "block";Ð
d.scrollbarFiller.style.height = d.scrollbarFiller.style.width =
scrollbarWidth(d.measure) + "px";Ð   } else d.scrollbarFiller.style.display =
"";Ð   if (mac_geLion && scrollbarWidth(d.measure) === 0)Ð
d.scrollbarV.style.minWidth = d.scrollbarH.style.minHeight =
mac_geMountainLion ? "18px" : "12px";Ð }Ð function visibleLines(display, doc,
viewPort) {Ð   var top = display.scroller.scrollTop, height =
display.wrapper.clientHeight;Ð   if (typeof viewPort == "number") top =
viewPort;Ð   else if (viewPort) {top = viewPort.top; height = viewPort.bottom
- viewPort.top;}Ð   top = Math.floor(top - paddingTop(display));Ð   var
bottom = Math.ceil(top + height);Ð   return {from: lineAtHeight(doc, top),
to: lineAtHeight(doc, bottom)};Ð }Ð // LINE NUMBERSÐ function
alignHorizontally(cm) {Ð   var display = cm.display;Ð   if (!
display.alignWidgets && (!display.gutters.firstChild || !
cm.options.fixedGutter)) return;Ð   var comp = compensateForHScroll(display)
- display.scroller.scrollLeft + cm.doc.scrollLeft;Ð   var gutterW =
display.gutters.offsetWidth, l = comp + "px";Ð   for (var n =
display.lineDiv.firstChild; n; n = n.nextSibling) if (n.alignable) {Ð     for
(var i = 0, a = n.alignable; i < a.length; ++i) a[i].style.left = l;Ð   }Ð
if (cm.options.fixedGutter)Ð     display.gutters.style.left = (comp +
gutterW) + "px";Ð }Ð function maybeUpdateLineNumberWidth(cm) {Ð   if (!
cm.options.lineNumbers) return false;Ð   var doc = cm.doc, last =
lineNumberFor(cm.options, doc.first + doc.size - 1), display = cm.display;Ð
if (last.length != display.lineNumChars) {Ð     var test =
display.measure.appendChild(elt("div", [elt("div", last)],Ð
                                            "CodeMirror-linenumber
CodeMirror-gutter-elt"));Ð     var innerW = test.firstChild.offsetWidth,
padding = test.offsetWidth - innerW;Ð     display.lineGutter.style.width = "";Ð
      display.lineNumInnerWidth = Math.max(innerW,
display.lineGutter.offsetWidth - padding);Ð     display.lineNumWidth =
display.lineNumInnerWidth + padding;Ð     display.lineNumChars =
display.lineNumInnerWidth ? last.length : -1;Ð
display.lineGutter.style.width = display.lineNumWidth + "px";Ð     return
true;Ð   }Ð   return false;Ð }Ð function lineNumberFor(options, i) {Ð
return String(options.lineNumberFormatter(i + options.firstLineNumber));Ð }Ð
function compensateForHScroll(display) {Ð   return
getRect(display.scroller).left - getRect(display.sizer).left;Ð }Ð // DISPLAY
DRAWINGÐ function updateDisplay(cm, changes, viewPort) {Ð   var oldFrom =
cm.display.showingFrom, oldTo = cm.display.showingTo, updated;Ð   var visible
= visibleLines(cm.display, cm.doc, viewPort);Ð   for (;;) {Ð     if
(updateDisplayInner(cm, changes, visible)) {Ð       updated = true;Ð
signalLater(cm, "update", cm);Ð       if (cm.display.showingFrom != oldFrom
|| cm.display.showingTo != oldTo)Ð
```

signalLater(cm, "viewportChange", cm, cm.display.showingFrom, cm.display.showingTo);Ð } else break;Ð updateSelection(cm);Ð updateScrollbars(cm.display, cm.doc.height);Ð // Clip forced viewport to actual scrollable areaÐ if (viewPort)Ð viewPort = Math.min(cm.display.scroller.scrollHeight - cm.display.scroller.clientHeight,Ð typeof viewPort == "number" ? viewPort : viewPort.top);Ð visible = visibleLines(cm.display, cm.doc, viewPort);Ð if (visible.from >= cm.display.showingFrom && visible.to <= cm.display.showingTo)Ð break;Ð changes = [];Ð }Ð return updated;Ð }Ð // Uses a set of changes plus the current scroll position toÐ // determine which DOM updates have to be made, and makes theÐ // updates.Ð function updateDisplayInner(cm, changes, visible) {Ð var display = cm.display, doc = cm.doc;Ð if (!display.wrapper.clientWidth) {Ð display.showingFrom = display.showingTo = doc.first;Ð display.viewOffset = 0;Ð return;Ð }Ð // Bail out if the visible area is already rendered and nothing changed.Ð if (changes.length == 0 &&Ð visible.from > display.showingFrom && visible.to < display.showingTo)Ð return;Ð if (maybeUpdateLineNumberWidth(cm))Ð changes = [{from: doc.first, to: doc.first + doc.size}];Ð var gutterW = display.sizer.style.marginLeft = display.gutters.offsetWidth + "px";Ð display.scrollbarH.style.left = cm.options.fixedGutter ? gutterW : "0";Ð // Used to determine which lines need their line numbers updatedÐ var positionsChangedFrom = Infinity;Ð if (cm.options.lineNumbers)Ð for (var i = 0; i < changes.length; ++i)Ð if (changes[i].diff) { positionsChangedFrom = changes[i].from; break; }Ð var end = doc.first + doc.size;Ð var from = Math.max(visible.from - cm.options.viewportMargin, doc.first);Ð var to = Math.min(end, visible.to + cm.options.viewportMargin);Ð if (display.showingFrom < from && from - display.showingFrom < 20) from = Math.max(doc.first, display.showingFrom);Ð if (display.showingTo > to && display.showingTo - to < 20) to = Math.min(end, display.showingTo);Ð if (sawCollapsedSpans) {Ð from = lineNo(visualLine(doc, getLine(doc, from)));Ð while (to < end && lineIsHidden(doc, getLine(doc, to))) ++to;Ð }Ð // Create a range of theoretically intact lines, and punch holesÐ // in that using the change info.Ð var intact = [{from: Math.max(display.showingFrom, doc.first),Ð to: Math.min(display.showingTo, end)}];Ð if (intact[0].from >= intact[0].to) intact = [];Ð else intact = computeIntact(intact, changes);Ð // When merged lines are present, we might have to reduce theÐ // intact ranges because changes in continued fragments of theÐ // intact lines do require the lines to be redrawn.Ð if (sawCollapsedSpans)Ð for (var i = 0; i < intact.length; ++i) {Ð var range = intact[i], merged;Ð while (merged = collapsedSpanAtEnd(getLine(doc, range.to - 1))) {Ð var newTo = merged.find().from.line;Ð if (newTo > range.from) range.to = newTo;Ð else { intact.splice(i--, 1); break; }Ð }Ð }Ð // Clip off the parts that won't be visibleÐ var intactLines = 0;Ð for (var i = 0; i < intact.length; ++i) {Ð var range = intact[i];Ð if (range.from < from) range.from = from;Ð if (range.to > to) range.to = to;Ð if (range.from >= range.to) intact.splice(i--, 1);Ð else intactLines += range.to - range.from;Ð }Ð if (intactLines == to - from && from == display.showingFrom && to == display.showingTo) {Ð updateViewOffset(cm);Ð return;Ð }Ð intact.sort(function(a, b) {return a.from - b.from;});Ð // Avoid crashing on IE's "unspecified error" when in iframesÐ try {Ð var focused = document.activeElement;Ð } catch(e) {}Ð if (intactLines < (to - from) * .7) display.lineDiv.style.display = "none";Ð patchDisplay(cm, from, to, intact, positionsChangedFrom);Ð display.lineDiv.style.display = "";Ð if (focused && document.activeElement != focused && focused.offsetHeight) focused.focus();Ð var different = from != display.showingFrom || to != display.showingTo ||Ð display.lastSizeC != display.wrapper.clientHeight;Ð

```
                                    // This is just a bogus formula that detects
when the editor isÐ   // resized or the font size changes.Ð   if (different)
display.lastSizeC = display.wrapper.clientHeight;Ð   display.showingFrom =
from; display.showingTo = to;Ð   startWorker(cm, 100);Ð   var prevBottom =
display.lineDiv.offsetTop;Ð   for (var node = display.lineDiv.firstChild,
height; node; node = node.nextSibling) if (node.lineObj) {Ð     if (ie_lt8) {Ð
        var bot = node.offsetTop + node.offsetHeight;Ð       height = bot -
prevBottom;Ð       prevBottom = bot;Ð     } else {Ð       var box =
getRect(node);Ð       height = box.bottom - box.top;Ð     }Ð     var diff =
node.lineObj.height - height;Ð     if (height < 2) height =
textHeight(display);Ð     if (diff > .001 || diff < -.001) {Ð
updateLineHeight(node.lineObj, height);Ð       var widgets =
node.lineObj.widgets;Ð       if (widgets) for (var i = 0; i < widgets.length;
++i)Ð         widgets[i].height = widgets[i].node.offsetHeight;Ð     }Ð   }Ð
    updateViewOffset(cm);Ð   return true;Ð }Ð function updateViewOffset(cm) {Ð
    var off = cm.display.viewOffset = heightAtLine(cm, getLine(cm.doc,
cm.display.showingFrom));Ð   // Position the mover div to align with the
current virtual scroll positionÐ   cm.display.mover.style.top = off + "px";Ð }Ð
  function computeIntact(intact, changes) {Ð   for (var i = 0, l =
changes.length || 0; i < l; ++i) {Ð     var change = changes[i], intact2 =
[], diff = change.diff || 0;Ð     for (var j = 0, l2 = intact.length; j < l2;
++j) {Ð       var range = intact[j];Ð       if (change.to <= range.from &&
change.diff) {Ð         intact2.push({from: range.from + diff, to: range.to +
diff});Ð       } else if (change.to <= range.from || change.from >= range.to)
{Ð         intact2.push(range);Ð       } else {Ð         if (change.from >
range.from)Ð           intact2.push({from: range.from, to: change.from});Ð
          if (change.to < range.to)Ð           intact2.push({from: change.to
+ diff, to: range.to + diff});Ð       }Ð     }Ð     intact = intact2;Ð   }Ð
return intact;Ð }Ð function getDimensions(cm) {Ð   var d = cm.display, left =
{}, width = {};Ð   for (var n = d.gutters.firstChild, i = 0; n; n =
n.nextSibling, ++i) {Ð     left[cm.options.gutters[i]] = n.offsetLeft;Ð
width[cm.options.gutters[i]] = n.offsetWidth;Ð   }Ð   return {fixedPos:
compensateForHScroll(d),Ð           gutterTotalWidth: d.gutters.offsetWidth,Ð
            gutterLeft: left,Ð           gutterWidth: width,Ð
wrapperWidth: d.wrapper.clientWidth};Ð }Ð function patchDisplay(cm, from, to,
intact, updateNumbersFrom) {Ð   var dims = getDimensions(cm);Ð   var display
= cm.display, lineNumbers = cm.options.lineNumbers;Ð   if (!intact.length &&
(!webkit || !cm.display.currentWheelTarget))Ð
removeChildren(display.lineDiv);Ð   var container = display.lineDiv, cur =
container.firstChild;Ð   function rm(node) {Ð     var next = node.nextSibling;Ð
      if (webkit && mac && cm.display.currentWheelTarget == node) {Ð
node.style.display = "none";Ð       node.lineObj = null;Ð     } else {Ð
node.parentNode.removeChild(node);Ð     }Ð     return next;Ð   }Ð   var
nextIntact = intact.shift(), lineN = from;Ð   cm.doc.iter(from, to,
function(line) {Ð     if (nextIntact && nextIntact.to == lineN) nextIntact =
intact.shift();Ð     if (lineIsHidden(cm.doc, line)) {Ð       if
(line.height != 0) updateLineHeight(line, 0);Ð       if (line.widgets &&
cur.previousSibling) for (var i = 0; i < line.widgets.length; ++i)Ð
if (line.widgets[i].showIfHidden) {Ð           var prev = cur.previousSibling;Ð
            if (/pre/i.test(prev.nodeName)) {Ð             var wrap =
elt("div", null, null, "position: relative");Ð
prev.parentNode.replaceChild(wrap, prev);Ð             wrap.appendChild(prev);Ð
              prev = wrap;Ð           }Ð           var wnode =
prev.appendChild(elt("div", [line.widgets[i].node], "CodeMirror-linewidget"));Ð
            positionLineWidget(line.widgets[i], wnode, prev, dims);Ð         }Ð
      } else if (nextIntact && nextIntact.from <= lineN && nextIntact.to >
lineN) {Ð       // This line is intact. Skip to the actual node. Update itsÐ
        // line number if needed.Ð       while (cur.lineObj != line) cur =
rm(cur);Ð       if (lineNumbers && updateNumbersFrom <= lineN &&
cur.lineNumber)Ð
```

```
                          setTextContent(cur.lineNumber,
lineNumberFor(cm.options, lineN));Ð       cur = cur.nextSibling;Ð     } else {Ð
        // For lines with widgets, make an attempt to find and reuseÐ
        // the existing element, so that widgets aren't needlesslyÐ       //
removed and re-inserted into the domÐ       if (line.widgets) for (var j = 0,
search = cur, reuse; search && j < 20; ++j, search = search.nextSibling)Ð
          if (search.lineObj == line && /div/i.test(search.nodeName)) { reuse
= search; break; }Ð       // This line needs to be generated.Ð       var
lineNode = buildLineElement(cm, line, lineN, dims, reuse);Ð       if
(lineNode != reuse) {Ð         container.insertBefore(lineNode, cur);Ð
        } else {Ð         while (cur != reuse) cur = rm(cur);Ð         cur =
cur.nextSibling;Ð       }Ð       lineNode.lineObj = line;Ð     }Ð     ++lineN;Ð
    });Ð   while (cur) cur = rm(cur);Ð }Ð function buildLineElement(cm, line,
lineNo, dims, reuse) {Ð   var lineElement = lineContent(cm, line);Ð   var
markers = line.gutterMarkers, display = cm.display, wrap;Ð   if (!
cm.options.lineNumbers && !markers && !line.bgClass && !line.wrapClass && !
line.widgets)Ð     return lineElement;Ð   // Lines with gutter elements,
widgets or a background class needÐ   // to be wrapped again, and have the
extra elements added to theÐ   // wrapper divÐ   if (reuse) {Ð
reuse.alignable = null;Ð     var isOk = true, widgetsSeen = 0;Ð     for (var
n = reuse.firstChild, next; n; n = next) {Ð       next = n.nextSibling;Ð
        if (!/\bCodeMirror-linewidget\b/.test(n.className)) {Ð
reuse.removeChild(n);Ð       } else {Ð         for (var i = 0, first = true;
i < line.widgets.length; ++i) {Ð           var widget = line.widgets[i],
isFirst = false;Ð           if (!widget.above) { isFirst = first; first =
false; }Ð           if (widget.node == n.firstChild) {Ð
positionLineWidget(widget, n, reuse, dims);Ð             ++widgetsSeen;Ð
              if (isFirst) reuse.insertBefore(lineElement, n);Ð
break;Ð           }Ð         }Ð         if (i == line.widgets.length) { isOk
= false; break; }Ð       }Ð     }Ð     if (isOk && widgetsSeen ==
line.widgets.length) {Ð       wrap = reuse;Ð       reuse.className =
line.wrapClass || "";Ð     }Ð   }Ð   if (!wrap) {Ð     wrap = elt("div",
null, line.wrapClass, "position: relative");Ð
wrap.appendChild(lineElement);Ð   }Ð   // Kludge to make sure the styled
element lies behind the selection (by z-index)Ð   if (line.bgClass)Ð
wrap.insertBefore(elt("div", null, line.bgClass + " CodeMirror-
linebackground"), wrap.firstChild);Ð   if (cm.options.lineNumbers || markers)
{Ð     var gutterWrap = wrap.insertBefore(elt("div", null, null, "position:
absolute; left: " +Ð
(cm.options.fixedGutter ? dims.fixedPos : -dims.gutterTotalWidth) + "px"),Ð
                                          wrap.firstChild);Ð     if
(cm.options.fixedGutter) (wrap.alignable || (wrap.alignable =
[])).push(gutterWrap);Ð     if (cm.options.lineNumbers && (!markers || !
markers["CodeMirror-linenumbers"]))Ð       wrap.lineNumber =
gutterWrap.appendChild(Ð         elt("div", lineNumberFor(cm.options, lineNo),Ð
              "CodeMirror-linenumber CodeMirror-gutter-elt",Ð
"left: " + dims.gutterLeft["CodeMirror-linenumbers"] + "px; width: "Ð
              + display.lineNumInnerWidth + "px"));Ð     if (markers)Ð
for (var k = 0; k < cm.options.gutters.length; ++k) {Ð         var id =
cm.options.gutters[k], found = markers.hasOwnProperty(id) && markers[id];Ð
          if (found)Ð           gutterWrap.appendChild(elt("div", [found],
"CodeMirror-gutter-elt", "left: " +Ð
dims.gutterLeft[id] + "px; width: " + dims.gutterWidth[id] + "px"));Ð       }Ð
    }Ð   if (ie_lt8) wrap.style.zIndex = 2;Ð   if (line.widgets && wrap !=
reuse) for (var i = 0, ws = line.widgets; i < ws.length; ++i) {Ð     var
widget = ws[i], node = elt("div", [widget.node], "CodeMirror-linewidget");Ð
      positionLineWidget(widget, node, wrap, dims);Ð     if (widget.above)Ð
        wrap.insertBefore(node, cm.options.lineNumbers && line.height != 0 ?
gutterWrap : lineElement);Ð     elseÐ       wrap.appendChild(node);Ð
signalLater(widget, "redraw");Ð
```

```
                                    }Ð   return wrap;Ð }Ð function
positionLineWidget(widget, node, wrap, dims) {Ð   if (widget.noHScroll) {Ð
      (wrap.alignable || (wrap.alignable = [])).push(node);Ð     var width =
dims.wrapperWidth;Ð     node.style.left = dims.fixedPos + "px";Ð     if (!
widget.coverGutter) {Ð       width -= dims.gutterTotalWidth;Ð
node.style.paddingLeft = dims.gutterTotalWidth + "px";Ð     }Ð
node.style.width = width + "px";Ð   }Ð   if (widget.coverGutter) {Ð
node.style.zIndex = 5;Ð     node.style.position = "relative";Ð     if (!
widget.noHScroll) node.style.marginLeft = -dims.gutterTotalWidth + "px";Ð   }Ð
  }Ð // SELECTION / CURSORÐ function updateSelection(cm) {Ð   var display =
cm.display;Ð   var collapsed = posEq(cm.doc.sel.from, cm.doc.sel.to);Ð   if
(collapsed || cm.options.showCursorWhenSelecting)Ð
updateSelectionCursor(cm);Ð   elseÐ     display.cursor.style.display =
display.otherCursor.style.display = "none";Ð   if (!collapsed)Ð
updateSelectionRange(cm);Ð   elseÐ     display.selectionDiv.style.display =
"none";Ð   // Move the hidden textarea near the cursor to prevent scrolling
artifactsÐ   if (cm.options.moveInputWithCursor) {Ð     var headPos =
cursorCoords(cm, cm.doc.sel.head, "div");Ð     var wrapOff =
getRect(display.wrapper), lineOff = getRect(display.lineDiv);Ð
display.inputDiv.style.top = Math.max(0,
Math.min(display.wrapper.clientHeight - 10,Ð
                                                          headPos.top +
lineOff.top - wrapOff.top)) + "px";Ð     display.inputDiv.style.left =
Math.max(0, Math.min(display.wrapper.clientWidth - 10,Ð
                                                           headPos.left +
lineOff.left - wrapOff.left)) + "px";Ð   }Ð }Ð // No selection, plain cursorÐ
function updateSelectionCursor(cm) {Ð   var display = cm.display, pos =
cursorCoords(cm, cm.doc.sel.head, "div");Ð   display.cursor.style.left =
pos.left + "px";Ð   display.cursor.style.top = pos.top + "px";Ð
display.cursor.style.height = Math.max(0, pos.bottom - pos.top) *
cm.options.cursorHeight + "px";Ð   display.cursor.style.display = "";Ð   if
(pos.other) {Ð     display.otherCursor.style.display = "";Ð
display.otherCursor.style.left = pos.other.left + "px";Ð
display.otherCursor.style.top = pos.other.top + "px";Ð
display.otherCursor.style.height = (pos.other.bottom - pos.other.top) * .85 +
"px";Ð   } else { display.otherCursor.style.display = "none"; }Ð }Ð //
Highlight selectionÐ function updateSelectionRange(cm) {Ð   var display =
cm.display, doc = cm.doc, sel = cm.doc.sel;Ð   var fragment =
document.createDocumentFragment();Ð   var clientWidth =
display.lineSpace.offsetWidth, pl = paddingLeft(cm.display);Ð   function
add(left, top, width, bottom) {Ð     if (top < 0) top = 0;Ð
fragment.appendChild(elt("div", null, "CodeMirror-selected", "position:
absolute; left: " + left +Ð                                "px; top: " + top +
"px; width: " + (width == null ? clientWidth - left : width) +Ð
                               "px; height: " + (bottom - top) + "px"));Ð   }Ð
    function drawForLine(line, fromArg, toArg, retTop) {Ð     var lineObj =
getLine(doc, line);Ð     var lineLen = lineObj.text.length, rVal = retTop ?
Infinity : -Infinity;Ð     function coords(ch) {Ð       return charCoords(cm,
Pos(line, ch), "div", lineObj);Ð     }Ð
iterateBidiSections(getOrder(lineObj), fromArg || 0, toArg == null ?
lineLen : toArg, function(from, to, dir) {Ð       var leftPos = coords(from),
rightPos, left, right;Ð       if (from == to) {Ð         rightPos = leftPos;Ð
          left = right = leftPos.left;Ð       } else {Ð         rightPos =
coords(to - 1);Ð         if (dir == "rtl") { var tmp = leftPos; leftPos =
rightPos; rightPos = tmp; }Ð         left = leftPos.left;Ð         right =
rightPos.right;Ð       }Ð       if (rightPos.top - leftPos.top > 3) { //
Different lines, draw top partÐ         add(left, leftPos.top, null,
leftPos.bottom);Ð         left = pl;Ð         if (leftPos.bottom <
rightPos.top) add(left, leftPos.bottom, null, rightPos.top);Ð       }Ð
if (toArg == null && to == lineLen) right = clientWidth;Ð
```

```
                                                                if (fromArg
== null && from == 0) left = pl;Ð       rVal = retTop ?
Math.min(rightPos.top, rVal) : Math.max(rightPos.bottom, rVal);Ð       if
(left < pl + 1) left = pl;Ð       add(left, rightPos.top, right - left,
rightPos.bottom);Ð     });Ð     return rVal;Ð   }Ð   if (sel.from.line ==
sel.to.line) {Ð     drawForLine(sel.from.line, sel.from.ch, sel.to.ch);Ð   }
else {Ð     var fromObj = getLine(doc, sel.from.line);Ð     var cur =
fromObj, merged, path = [sel.from.line, sel.from.ch], singleLine;Ð     while
(merged = collapsedSpanAtEnd(cur)) {Ð       var found = merged.find();Ð
path.push(found.from.ch, found.to.line, found.to.ch);Ð       if
(found.to.line == sel.to.line) {Ð         path.push(sel.to.ch);Ð
singleLine = true;Ð         break;Ð       }Ð       cur = getLine(doc,
found.to.line);Ð     }Ð     // This is a single, merged lineÐ     if
(singleLine) {Ð       for (var i = 0; i < path.length; i += 3)Ð
drawForLine(path[i], path[i+1], path[i+2]);Ð     } else {Ð       var
middleTop, middleBot, toObj = getLine(doc, sel.to.line);Ð       if
(sel.from.ch)Ð         // Draw the first line of selection.Ð
middleTop = drawForLine(sel.from.line, sel.from.ch, null, false);Ð       elseÐ
          // Simply include it in the middle block.Ð         middleTop =
heightAtLine(cm, fromObj) - display.viewOffset;Ð       if (!sel.to.ch)Ð
          middleBot = heightAtLine(cm, toObj) - display.viewOffset;Ð
elseÐ         middleBot = drawForLine(sel.to.line,
collapsedSpanAtStart(toObj) ? null : 0, sel.to.ch, true);Ð       if
(middleTop < middleBot) add(pl, middleTop, null, middleBot);Ð     }Ð   }Ð
removeChildrenAndAdd(display.selectionDiv, fragment);Ð
display.selectionDiv.style.display = "";Ð }Ð // Cursor-blinkingÐ function
restartBlink(cm) {Ð   if (!cm.state.focused) return;Ð   var display =
cm.display;Ð   clearInterval(display.blinker);Ð   var on = true;Ð
display.cursor.style.visibility = display.otherCursor.style.visibility = "";Ð
    display.blinker = setInterval(function() {Ð
display.cursor.style.visibility = display.otherCursor.style.visibility = (on
= !on) ? "" : "hidden";Ð   }, cm.options.cursorBlinkRate);Ð }Ð // HIGHLIGHT
WORKERÐ function startWorker(cm, time) {Ð   if (cm.doc.mode.startState &&
cm.doc.frontier < cm.display.showingTo)Ð     cm.state.highlight.set(time,
bind(highlightWorker, cm));Ð }Ð function highlightWorker(cm) {Ð   var doc =
cm.doc;Ð   if (doc.frontier < doc.first) doc.frontier = doc.first;Ð   if
(doc.frontier >= cm.display.showingTo) return;Ð   var end = +new Date +
cm.options.workTime;Ð   var state = copyState(doc.mode, getStateBefore(cm,
doc.frontier));Ð   var changed = [], prevChange;Ð   doc.iter(doc.frontier,
Math.min(doc.first + doc.size, cm.display.showingTo + 500), function(line) {Ð
      if (doc.frontier >= cm.display.showingFrom) { // VisibleÐ       var
oldStyles = line.styles;Ð       line.styles = highlightLine(cm, line, state);Ð
        var ischange = !oldStyles || oldStyles.length != line.styles.length;Ð
        for (var i = 0; !ischange && i < oldStyles.length; ++i) ischange =
oldStyles[i] != line.styles[i];Ð       if (ischange) {Ð         if
(prevChange && prevChange.end == doc.frontier) prevChange.end++;Ð
else changed.push(prevChange = {start: doc.frontier, end: doc.frontier + 1});Ð
        }Ð       line.stateAfter = copyState(doc.mode, state);Ð     } else {Ð
        processLine(cm, line, state);Ð       line.stateAfter = doc.frontier %
5 == 0 ? copyState(doc.mode, state) : null;Ð     }Ð     ++doc.frontier;Ð
if (+new Date > end) {Ð       startWorker(cm, cm.options.workDelay);Ð
return true;Ð     }Ð   });Ð   if (changed.length)Ð     operation(cm,
function() {Ð       for (var i = 0; i < changed.length; ++i)Ð
regChange(this, changed[i].start, changed[i].end);Ð     })();Ð }Ð // Finds
the line to start with when starting a parse. Tries toÐ // find a line with a
stateAfter, so that it can start with aÐ // valid state. If that fails, it
returns the line with theÐ // smallest indentation, which tends to need the
least context toÐ // parse correctly.Ð function findStartLine(cm, n) {Ð   var
minindent, minline, doc = cm.doc;Ð   for (var search = n, lim = n - 100;
search > lim; --search) {Ð
```

```
                                if (search <= doc.first) return doc.first;Ð
      var line = getLine(doc, search - 1);Ð     if (line.stateAfter) return
search;Ð     var indented = countColumn(line.text, null, cm.options.tabSize);Ð
      if (minline == null || minindent > indented) {Ð       minline = search
- 1;Ð       minindent = indented;Ð     }Ð   }Ð   return minline;Ð }Ð function
getStateBefore(cm, n) {Ð   var doc = cm.doc, display = cm.display;Ð     if (!
doc.mode.startState) return true;Ð   var pos = findStartLine(cm, n), state =
pos > doc.first && getLine(doc, pos-1).stateAfter;Ð   if (!state) state =
startState(doc.mode);Ð   else state = copyState(doc.mode, state);Ð
doc.iter(pos, n, function(line) {Ð     processLine(cm, line, state);Ð     var
save = pos == n - 1 || pos % 5 == 0 || pos >= display.showingFrom && pos <
display.showingTo;Ð     line.stateAfter = save ? copyState(doc.mode, state) :
null;Ð     ++pos;Ð   });Ð   return state;Ð }Ð // POSITION MEASUREMENTÐ
function paddingTop(display) {return display.lineSpace.offsetTop;}Ð function
paddingVert(display) {return display.mover.offsetHeight -
display.lineSpace.offsetHeight;}Ð function paddingLeft(display) {Ð   var e =
removeChildrenAndAdd(display.measure, elt("pre", null, null, "text-align:
left")).appendChild(elt("span", "x"));Ð   return e.offsetLeft;Ð }Ð function
measureChar(cm, line, ch, data) {Ð   var dir = -1;Ð   data = data ||
measureLine(cm, line);Ð   for (var pos = ch;; pos += dir) {Ð     var r =
data[pos];Ð     if (r) break;Ð     if (dir < 0 && pos == 0) dir = 1;Ð   }Ð
return {left: pos < ch ? r.right : r.left,Ð           right: pos > ch ?
r.left : r.right,Ð           top: r.top, bottom: r.bottom};Ð }Ð function
findCachedMeasurement(cm, line) {Ð   var cache = cm.display.measureLineCache;Ð
    for (var i = 0; i < cache.length; ++i) {Ð     var memo = cache[i];Ð
if (memo.text == line.text && memo.markedSpans == line.markedSpans &&Ð
          cm.display.scroller.clientWidth == memo.width &&Ð
memo.classes == line.textClass + "|" + line.bgClass + "|" + line.wrapClass)Ð
        return memo.measure;Ð   }Ð }Ð function measureLine(cm, line) {Ð   //
First look in the cacheÐ   var measure = findCachedMeasurement(cm, line);Ð
if (!measure) {Ð     // Failing that, recompute and store result in cacheÐ
      measure = measureLineInner(cm, line);Ð     var cache =
cm.display.measureLineCache;Ð     var memo = {text: line.text, width:
cm.display.scroller.clientWidth,Ð                 markedSpans:
line.markedSpans, measure: measure,Ð                 classes: line.textClass
+ "|" + line.bgClass + "|" + line.wrapClass};Ð     if (cache.length == 16)
cache[++cm.display.measureLineCachePos % 16] = memo;Ð     else
cache.push(memo);Ð   }Ð   return measure;Ð }Ð function measureLineInner(cm,
line) {Ð   var display = cm.display, measure = emptyArray(line.text.length);Ð
    var pre = lineContent(cm, line, measure);Ð   // IE does not cache element
positions of inline elements betweenÐ   // calls to getBoundingClientRect.
This makes the loop below,Ð   // which gathers the positions of all the
characters on the line,Ð   // do an amount of layout work quadratic to the
number ofÐ   // characters. When line wrapping is off, we try to improve
thingsÐ   // by first subdividing the line into a bunch of inline blocks, soÐ
    // that IE can reuse most of the layout information from cachesÐ   // for
those blocks. This does interfere with line wrapping, so itÐ   // doesn't
work when wrapping is on, but in that case theÐ   // situation is slightly
better, since IE does cache line-wrappingÐ   // information and only
recomputes per-line.Ð   if (ie && !ie_lt8 && !cm.options.lineWrapping &&
pre.childNodes.length > 100) {Ð     var fragment =
document.createDocumentFragment();Ð     var chunk = 10, n =
pre.childNodes.length;Ð     for (var i = 0, chunks = Math.ceil(n / chunk); i
< chunks; ++i) {Ð       var wrap = elt("div", null, null, "display: inline-
block");Ð       for (var j = 0; j < chunk && n; ++j) {Ð
wrap.appendChild(pre.firstChild);Ð         --n;Ð       }Ð
fragment.appendChild(wrap);Ð     }Ð     pre.appendChild(fragment);Ð   }Ð
removeChildrenAndAdd(display.measure, pre);Ð   var outer =
getRect(display.lineDiv);Ð   var vranges = [], data =
emptyArray(line.text.length), maxBot = pre.offsetHeight;Ð
```

```
                                                                    // Work around an
IE7/8 bug where it will sometimes have randomlyÐ   // replaced our pre with a
clone at this point.Ð   if (ie_lt9 && display.measure.first != pre)Ð
removeChildrenAndAdd(display.measure, pre);Ð   for (var i = 0, cur; i <
measure.length; ++i) if (cur = measure[i]) {Ð     var size = getRect(cur);Ð
      var top = Math.max(0, size.top - outer.top), bot = Math.min(size.bottom
- outer.top, maxBot);Ð     for (var j = 0; j < vranges.length; j += 2) {Ð
        var rtop = vranges[j], rbot = vranges[j+1];Ð       if (rtop > bot ||
rbot < top) continue;Ð       if (rtop <= top && rbot >= bot ||Ð           top
<= rtop && bot >= rbot ||Ð           Math.min(bot, rbot) - Math.max(top,
rtop) >= (bot - top) >> 1) {Ð         vranges[j] = Math.min(top, rtop);Ð
          vranges[j+1] = Math.max(bot, rbot);Ð         break;Ð       }Ð     }Ð
      if (j == vranges.length) vranges.push(top, bot);Ð     var right =
size.right;Ð     if (cur.measureRight) right = getRect(cur.measureRight).left;Ð
      data[i] = {left: size.left - outer.left, right: right - outer.left,
top: j};Ð   }Ð   for (var i = 0, cur; i < data.length; ++i) if (cur =
data[i]) {Ð     var vr = cur.top;Ð     cur.top = vranges[vr]; cur.bottom =
vranges[vr+1];Ð   }Ð   return data;Ð }Ð function measureLineWidth(cm, line) {Ð
    var hasBadSpan = false;Ð   if (line.markedSpans) for (var i = 0; i <
line.markedSpans; ++i) {Ð     var sp = line.markedSpans[i];Ð     if
(sp.collapsed && (sp.to == null || sp.to == line.text.length)) hasBadSpan =
true;Ð   }Ð   var cached = !hasBadSpan && findCachedMeasurement(cm, line);Ð
if (cached) return measureChar(cm, line, line.text.length, cached).right;Ð
var pre = lineContent(cm, line);Ð   var end =
pre.appendChild(zeroWidthElement(cm.display.measure));Ð
removeChildrenAndAdd(cm.display.measure, pre);Ð   return getRect(end).right -
getRect(cm.display.lineDiv).left;Ð }Ð function clearCaches(cm) {Ð
cm.display.measureLineCache.length = cm.display.measureLineCachePos = 0;Ð
cm.display.cachedCharWidth = cm.display.cachedTextHeight = null;Ð   if (!
cm.options.lineWrapping) cm.display.maxLineChanged = true;Ð
cm.display.lineNumChars = null;Ð }Ð // Context is one of "line",
"div" (display.lineDiv), "local"/null (editor), or "page"Ð function
intoCoordSystem(cm, lineObj, rect, context) {Ð   if (lineObj.widgets) for
(var i = 0; i < lineObj.widgets.length; ++i) if (lineObj.widgets[i].above) {Ð
      var size = widgetHeight(lineObj.widgets[i]);Ð     rect.top += size;
rect.bottom += size;Ð   }Ð   if (context == "line") return rect;Ð   if (!
context) context = "local";Ð   var yOff = heightAtLine(cm, lineObj);Ð   if
(context != "local") yOff -= cm.display.viewOffset;Ð   if (context == "page")
{Ð     var lOff = getRect(cm.display.lineSpace);Ð     yOff += lOff.top +
(window.pageYOffset || (document.documentElement || document.body).scrollTop);Ð
      var xOff = lOff.left + (window.pageXOffset || (document.documentElement
|| document.body).scrollLeft);Ð     rect.left += xOff; rect.right += xOff;Ð
    }Ð   rect.top += yOff; rect.bottom += yOff;Ð   return rect;Ð }Ð //
Context may be "window", "page", "div", or "local"/nullÐ // Result is in
"div" coordsÐ function fromCoordSystem(cm, coords, context) {Ð   if (context
== "div") return coords;Ð   var left = coords.left, top = coords.top;Ð   if
(context == "page") {Ð     left -= window.pageXOffset ||
(document.documentElement || document.body).scrollLeft;Ð     top -=
window.pageYOffset || (document.documentElement || document.body).scrollTop;Ð
    }Ð   var lineSpaceBox = getRect(cm.display.lineSpace);Ð   left -=
lineSpaceBox.left;Ð   top -= lineSpaceBox.top;Ð   if (context == "local" || !
context) {Ð     var editorBox = getRect(cm.display.wrapper);Ð     left +=
editorBox.left;Ð     top += editorBox.top;Ð   }Ð   return {left: left, top:
top};Ð }Ð function charCoords(cm, pos, context, lineObj) {Ð   if (!lineObj)
lineObj = getLine(cm.doc, pos.line);Ð   return intoCoordSystem(cm, lineObj,
measureChar(cm, lineObj, pos.ch), context);Ð }Ð function cursorCoords(cm,
pos, context, lineObj, measurement) {Ð   lineObj = lineObj || getLine(cm.doc,
pos.line);Ð   if (!measurement) measurement = measureLine(cm, lineObj);Ð
function get(ch, right) {Ð     var m = measureChar(cm, lineObj, ch,
measurement);Ð
```

```
                    if (right) m.left = m.right; else m.right = m.left;Ð
return intoCoordSystem(cm, lineObj, m, context);Ð   }Ð   var order =
getOrder(lineObj), ch = pos.ch;Ð   if (!order) return get(ch);Ð   var main,
other, linedir = order[0].level;Ð   for (var i = 0; i < order.length; ++i) {Ð
      var part = order[i], rtl = part.level % 2, nb, here;Ð     if (part.from
< ch && part.to > ch) return get(ch, rtl);Ð     var left = rtl ? part.to :
part.from, right = rtl ? part.from : part.to;Ð     if (left == ch) {Ð
        // IE returns bogus offsets and widths for edges where theÐ       //
direction flips, but only for the side with the lowerÐ       // level. So we
try to use the side with the higher level.Ð       if (i && part.level < (nb =
order[i-1]).level) here = get(nb.level % 2 ? nb.from : nb.to - 1, true);Ð
        else here = get(rtl && part.from != part.to ? ch - 1 : ch);Ð       if
(rtl == linedir) main = here; else other = here;Ð     } else if (right == ch)
{Ð       var nb = i < order.length - 1 && order[i+1];Ð       if (!rtl && nb
&& nb.from == nb.to) continue;Ð       if (nb && part.level < nb.level) here =
get(nb.level % 2 ? nb.to - 1 : nb.from);Ð       else here = get(rtl ? ch : ch
- 1, true);Ð       if (rtl == linedir) main = here; else other = here;Ð     }Ð
    }Ð   if (linedir && !ch) other = get(order[0].to - 1);Ð   if (!main)
return other;Ð   if (other) main.other = other;Ð   return main;Ð }Ð function
PosMaybeOutside(line, ch, outside) {Ð   var pos = new Pos(line, ch);Ð   if
(outside) pos.outside = true;Ð   return pos;Ð }Ð // Coords must be lineSpace-
localÐ function coordsChar(cm, x, y) {Ð   var doc = cm.doc;Ð   y +=
cm.display.viewOffset;Ð   if (y < 0) return PosMaybeOutside(doc.first, 0,
true);Ð   var lineNo = lineAtHeight(doc, y), last = doc.first + doc.size - 1;Ð
    if (lineNo > last)Ð     return PosMaybeOutside(doc.first + doc.size - 1,
getLine(doc, last).text.length, true);Ð   if (x < 0) x = 0;Ð   for (;;) {Ð
      var lineObj = getLine(doc, lineNo);Ð     var found =
coordsCharInner(cm, lineObj, lineNo, x, y);Ð     var merged =
collapsedSpanAtEnd(lineObj);Ð     var mergedPos = merged && merged.find();Ð
      if (merged && found.ch >= mergedPos.from.ch)Ð       lineNo =
mergedPos.to.line;Ð     elseÐ       return found;Ð   }Ð }Ð function
coordsCharInner(cm, lineObj, lineNo, x, y) {Ð   var innerOff = y -
heightAtLine(cm, lineObj);Ð   var wrongLine = false, adjust = 2 *
cm.display.wrapper.clientWidth;Ð   var measurement = measureLine(cm, lineObj);Ð
    function getX(ch) {Ð     var sp = cursorCoords(cm, Pos(lineNo, ch),
"line",Ð                           lineObj, measurement);Ð     wrongLine =
true;Ð     if (innerOff > sp.bottom) return sp.left - adjust;Ð     else if
(innerOff < sp.top) return sp.left + adjust;Ð     else wrongLine = false;Ð
      return sp.left;Ð   }Ð   var bidi = getOrder(lineObj), dist =
lineObj.text.length;Ð   var from = lineLeft(lineObj), to = lineRight(lineObj);Ð
    var fromX = getX(from), fromOutside = wrongLine, toX = getX(to),
toOutside = wrongLine;Ð   if (x > toX) return PosMaybeOutside(lineNo, to,
toOutside);Ð   // Do a binary search between these bounds.Ð   for (;;) {Ð
if (bidi ? to == from || to == moveVisually(lineObj, from, 1) : to - from <=
1) {Ð       var after = x - fromX < toX - x, ch = after ? from : to;Ð
while (isExtendingChar.test(lineObj.text.charAt(ch))) ++ch;Ð       var pos =
PosMaybeOutside(lineNo, ch, after ? fromOutside : toOutside);Ð
pos.after = after;Ð       return pos;Ð     }Ð     var step = Math.ceil(dist /
2), middle = from + step;Ð     if (bidi) {Ð       middle = from;Ð       for
(var i = 0; i < step; ++i) middle = moveVisually(lineObj, middle, 1);Ð     }Ð
      var middleX = getX(middle);Ð     if (middleX > x) {to = middle; toX =
middleX; if (toOutside = wrongLine) toX += 1000; dist = step;}Ð     else
{from = middle; fromX = middleX; fromOutside = wrongLine; dist -= step;}Ð   }Ð
  }Ð var measureText;Ð function textHeight(display) {Ð   if
(display.cachedTextHeight != null) return display.cachedTextHeight;Ð   if
(measureText == null) {Ð     measureText = elt("pre");Ð     // Measure a
bunch of lines, for browsers that computeÐ     // fractional heights.Ð
for (var i = 0; i < 49; ++i) {Ð
measureText.appendChild(document.createTextNode("x"));Ð
measureText.appendChild(elt("br"));Ð
```

```
                                        }Ð
measureText.appendChild(document.createTextNode("x"));Ð   }Ð
removeChildrenAndAdd(display.measure, measureText);Ð   var height =
measureText.offsetHeight / 50;Ð   if (height > 3) display.cachedTextHeight =
height;Ð   removeChildren(display.measure);Ð   return height || 1;Ð }Ð
function charWidth(display) {Ð   if (display.cachedCharWidth != null) return
display.cachedCharWidth;Ð   var anchor = elt("span", "x");Ð   var pre =
elt("pre", [anchor]);Ð   removeChildrenAndAdd(display.measure, pre);Ð   var
width = anchor.offsetWidth;Ð   if (width > 2) display.cachedCharWidth = width;Ð
    return width || 10;Ð }Ð // OPERATIONSÐ // Operations are used to wrap
changes in such a way that eachÐ // change won't have to update the cursor
and display (which wouldÐ // be awkward, slow, and error-prone), but instead
updates areÐ // batched and then all combined and executed at once.Ð var
nextOpId = 0;Ð function startOperation(cm) {Ð   cm.curOp = {Ð     // An array
of ranges of lines that have to be updated. SeeÐ     // updateDisplay.Ð
changes: [],Ð     updateInput: null,Ð     userSelChange: null,Ð
textChanged: null,Ð     selectionChanged: false,Ð     cursorActivity: false,Ð
      updateMaxLine: false,Ð     updateScrollPos: false,Ð     id: ++nextOpIdÐ
    };Ð   if (!delayedCallbackDepth++) delayedCallbacks = [];Ð }Ð function
endOperation(cm) {Ð   var op = cm.curOp, doc = cm.doc, display = cm.display;Ð
    cm.curOp = null;Ð   if (op.updateMaxLine) computeMaxLength(cm);Ð   if
(display.maxLineChanged && !cm.options.lineWrapping && display.maxLine) {Ð
      var width = measureLineWidth(cm, display.maxLine);Ð
display.sizer.style.minWidth = Math.max(0, width + 3 + scrollerCutOff) + "px";Ð
      display.maxLineChanged = false;Ð     var maxScrollLeft = Math.max(0,
display.sizer.offsetLeft + display.sizer.offsetWidth -
display.scroller.clientWidth);Ð     if (maxScrollLeft < doc.scrollLeft && !
op.updateScrollPos)Ð       setScrollLeft(cm,
Math.min(display.scroller.scrollLeft, maxScrollLeft), true);Ð   }Ð   var
newScrollPos, updated;Ð   if (op.updateScrollPos) {Ð     newScrollPos =
op.updateScrollPos;Ð   } else if (op.selectionChanged &&
display.scroller.clientHeight) { // don't rescroll if not visibleÐ     var
coords = cursorCoords(cm, doc.sel.head);Ð     newScrollPos =
calculateScrollPos(cm, coords.left, coords.top, coords.left, coords.bottom);Ð
    }Ð   if (op.changes.length || newScrollPos && newScrollPos.scrollTop !=
null) {Ð     updated = updateDisplay(cm, op.changes, newScrollPos &&
newScrollPos.scrollTop);Ð     if (cm.display.scroller.offsetHeight)
cm.doc.scrollTop = cm.display.scroller.scrollTop;Ð   }Ð   if (!updated &&
op.selectionChanged) updateSelection(cm);Ð   if (op.updateScrollPos) {Ð
display.scroller.scrollTop = display.scrollbarV.scrollTop = doc.scrollTop =
newScrollPos.scrollTop;Ð     display.scroller.scrollLeft =
display.scrollbarH.scrollLeft = doc.scrollLeft = newScrollPos.scrollLeft;Ð
      alignHorizontally(cm);Ð     if (op.scrollToPos)Ð
scrollPosIntoView(cm, clipPos(cm.doc, op.scrollToPos), op.scrollToPosMargin);Ð
    } else if (newScrollPos) {Ð     scrollCursorIntoView(cm);Ð   }Ð   if
(op.selectionChanged) restartBlink(cm);Ð   if (cm.state.focused &&
op.updateInput)Ð     resetInput(cm, op.userSelChange);Ð   var hidden =
op.maybeHiddenMarkers, unhidden = op.maybeUnhiddenMarkers;Ð   if (hidden) for
(var i = 0; i < hidden.length; ++i)Ð     if (!hidden[i].lines.length)
signal(hidden[i], "hide");Ð   if (unhidden) for (var i = 0; i <
unhidden.length; ++i)Ð     if (unhidden[i].lines.length) signal(unhidden[i],
"unhide");Ð   var delayed;Ð   if (!--delayedCallbackDepth) {Ð     delayed =
delayedCallbacks;Ð     delayedCallbacks = null;Ð   }Ð   if (op.textChanged)Ð
      signal(cm, "change", cm, op.textChanged);Ð   if (op.cursorActivity)
signal(cm, "cursorActivity", cm);Ð   if (delayed) for (var i = 0; i <
delayed.length; ++i) delayed[i]();Ð }Ð // Wraps a function in an operation.
Returns the wrapped function.Ð function operation(cm1, f) {Ð   return
function() {Ð     var cm = cm1 || this, withOp = !cm.curOp;Ð     if (withOp)
startOperation(cm);Ð     try { var result = f.apply(cm, arguments); }Ð
finally { if (withOp) endOperation(cm); }Ð
```

```
                                                return result;Ð   };Ð }Ð
function docOperation(f) {Ð   return function() {Ð     var withOp = this.cm
&& !this.cm.curOp, result;Ð     if (withOp) startOperation(this.cm);Ð     try
{ result = f.apply(this, arguments); }Ð     finally { if (withOp)
endOperation(this.cm); }Ð     return result;Ð   };Ð }Ð function runInOp(cm,
f) {Ð   var withOp = !cm.curOp, result;Ð   if (withOp) startOperation(cm);Ð
try { result = f(); }Ð   finally { if (withOp) endOperation(cm); }Ð   return
result;Ð }Ð function regChange(cm, from, to, lendiff) {Ð   if (from == null)
from = cm.doc.first;Ð   if (to == null) to = cm.doc.first + cm.doc.size;Ð
cm.curOp.changes.push({from: from, to: to, diff: lendiff});Ð }Ð // INPUT
HANDLINGÐ function slowPoll(cm) {Ð   if (cm.display.pollingFast) return;Ð
cm.display.poll.set(cm.options.pollInterval, function() {Ð     readInput(cm);Ð
      if (cm.state.focused) slowPoll(cm);Ð   });Ð }Ð function fastPoll(cm) {Ð
    var missed = false;Ð   cm.display.pollingFast = true;Ð   function p() {Ð
      var changed = readInput(cm);Ð     if (!changed && !missed) {missed =
true; cm.display.poll.set(60, p);}Ð     else {cm.display.pollingFast = false;
slowPoll(cm);}Ð   }Ð   cm.display.poll.set(20, p);Ð }Ð // prevInput is a hack
to work with IME. If we reset the textareaÐ // on every change, that breaks
IME. So we look for changesÐ // compared to the previous content instead.
(Modern browsers haveÐ // events that indicate IME taking place, but these
are not widelyÐ // supported or compatible enough yet to rely on.)Ð function
readInput(cm) {Ð   var input = cm.display.input, prevInput =
cm.display.prevInput, doc = cm.doc, sel = doc.sel;Ð   if (!cm.state.focused
|| hasSelection(input) || isReadOnly(cm)) return false;Ð   var text =
input.value;Ð   if (text == prevInput && posEq(sel.from, sel.to)) return
false;Ð   if (ie && !ie_lt9 && cm.display.inputHasSelection === text) {Ð
resetInput(cm, true);Ð     return false;Ð   }Ð   var withOp = !cm.curOp;Ð
if (withOp) startOperation(cm);Ð   sel.shift = false;Ð   var same = 0, l =
Math.min(prevInput.length, text.length);Ð   while (same < l &&
prevInput.charCodeAt(same) == text.charCodeAt(same)) ++same;Ð   var from =
sel.from, to = sel.to;Ð   if (same < prevInput.length)Ð     from =
Pos(from.line, from.ch - (prevInput.length - same));Ð   else if
(cm.state.overwrite && posEq(from, to) && !cm.state.pasteIncoming)Ð     to =
Pos(to.line, Math.min(getLine(doc, to.line).text.length, to.ch + (text.length
- same)));Ð   var updateInput = cm.curOp.updateInput;Ð   makeChange(cm.doc,
{from: from, to: to, text: splitLines(text.slice(same)),Ð
                        origin: cm.state.pasteIncoming ? "paste" : "+input"},
"end");Ð   cm.curOp.updateInput = updateInput;Ð   if (text.length > 1000 ||
text.indexOf("\n") > -1) input.value = cm.display.prevInput = "";Ð   else
cm.display.prevInput = text;Ð   if (withOp) endOperation(cm);Ð
cm.state.pasteIncoming = false;Ð   return true;Ð }Ð function resetInput(cm,
user) {Ð   var minimal, selected, doc = cm.doc;Ð   if (!posEq(doc.sel.from,
doc.sel.to)) {Ð     cm.display.prevInput = "";Ð     minimal = hasCopyEvent &&Ð
        (doc.sel.to.line - doc.sel.from.line > 100 || (selected =
cm.getSelection()).length > 1000);Ð     var content = minimal ? "-" :
selected || cm.getSelection();Ð     cm.display.input.value = content;Ð     if
(cm.state.focused) selectInput(cm.display.input);Ð     if (ie && !ie_lt9)
cm.display.inputHasSelection = content;Ð   } else if (user) {Ð
cm.display.prevInput = cm.display.input.value = "";Ð     if (ie && !ie_lt9)
cm.display.inputHasSelection = null;Ð   }Ð   cm.display.inaccurateSelection =
minimal;Ð }Ð function focusInput(cm) {Ð   if (cm.options.readOnly !=
"nocursor" && (!mobile || document.activeElement != cm.display.input))Ð
cm.display.input.focus();Ð }Ð function isReadOnly(cm) {Ð   return
cm.options.readOnly || cm.doc.cantEdit;Ð }Ð // EVENT HANDLERSÐ function
registerEventHandlers(cm) {Ð   var d = cm.display;Ð   on(d.scroller,
"mousedown", operation(cm, onMouseDown));Ð   if (ie)Ð     on(d.scroller,
"dblclick", operation(cm, function(e) {Ð       var pos = posFromMouse(cm, e);Ð
        if (!pos || clickInGutter(cm, e) || eventInWidget(cm.display, e))
return;Ð       e_preventDefault(e);Ð       var word =
findWordAt(getLine(cm.doc, pos.line).text, pos);Ð
```

```
extendSelection(cm.doc, word.from, word.to);Ð     }));Ð   elseÐ
on(d.scroller, "dblclick", e_preventDefault);Ð   on(d.lineSpace,
"selectstart", function(e) {Ð     if (!eventInWidget(d, e))
e_preventDefault(e);Ð   });Ð   // Gecko browsers fire contextmenu *after*
opening the menu, atÐ   // which point we can't mess with it anymore. Context
menu isÐ   // handled in onMouseDown for Gecko.Ð   if (!captureMiddleClick)
on(d.scroller, "contextmenu", function(e) {onContextMenu(cm, e);});Ð
on(d.scroller, "scroll", function() {Ð     if (d.scroller.clientHeight) {Ð
        setScrollTop(cm, d.scroller.scrollTop);Ð       setScrollLeft(cm,
d.scroller.scrollLeft, true);Ð       signal(cm, "scroll", cm);Ð     }Ð   });Ð
    on(d.scrollbarV, "scroll", function() {Ð     if (d.scroller.clientHeight)
setScrollTop(cm, d.scrollbarV.scrollTop);Ð   });Ð   on(d.scrollbarH,
"scroll", function() {Ð     if (d.scroller.clientHeight) setScrollLeft(cm,
d.scrollbarH.scrollLeft);Ð   });Ð   on(d.scroller, "mousewheel", function(e)
{onScrollWheel(cm, e);});Ð   on(d.scroller, "DOMMouseScroll", function(e)
{onScrollWheel(cm, e);});Ð   function reFocus() { if (cm.state.focused)
setTimeout(bind(focusInput, cm), 0); }Ð   on(d.scrollbarH, "mousedown",
reFocus);Ð   on(d.scrollbarV, "mousedown", reFocus);Ð   // Prevent wrapper
from ever scrollingÐ   on(d.wrapper, "scroll", function()
{ d.wrapper.scrollTop = d.wrapper.scrollLeft = 0; });Ð   function onResize() {Ð
      // Might be a text scaling operation, clear size caches.Ð
d.cachedCharWidth = d.cachedTextHeight = null;Ð     clearCaches(cm);Ð
runInOp(cm, bind(regChange, cm));Ð   }Ð   on(window, "resize", onResize);Ð
    // Above handler holds on to the editor and its data structures.Ð   //
Here we poll to unregister it when the editor is no longer inÐ   // the
document, so that it can be garbage-collected.Ð   function unregister() {Ð
      for (var p = d.wrapper.parentNode; p && p != document.body; p =
p.parentNode) {}Ð     if (p) setTimeout(unregister, 5000);Ð     else
off(window, "resize", onResize);Ð   }Ð   setTimeout(unregister, 5000);Ð
on(d.input, "keyup", operation(cm, function(e) {Ð     if
(cm.options.onKeyEvent && cm.options.onKeyEvent(cm, addStop(e))) return;Ð
if (e.keyCode == 16) cm.doc.sel.shift = false;Ð   }));Ð   on(d.input,
"input", bind(fastPoll, cm));Ð   on(d.input, "keydown", operation(cm,
onKeyDown));Ð   on(d.input, "keypress", operation(cm, onKeyPress));Ð
on(d.input, "focus", bind(onFocus, cm));Ð   on(d.input, "blur", bind(onBlur,
cm));Ð   function drag_(e) {Ð     if (cm.options.onDragEvent &&
cm.options.onDragEvent(cm, addStop(e))) return;Ð     e_stop(e);Ð   }Ð   if
(cm.options.dragDrop) {Ð     on(d.scroller, "dragstart", function(e)
{onDragStart(cm, e);});Ð     on(d.scroller, "dragenter", drag_);Ð
on(d.scroller, "dragover", drag_);Ð     on(d.scroller, "drop", operation(cm,
onDrop));Ð   }Ð   on(d.scroller, "paste", function(e){Ð     if
(eventInWidget(d, e)) return;Ð     focusInput(cm);Ð     fastPoll(cm);Ð   });Ð
    on(d.input, "paste", function() {Ð     cm.state.pasteIncoming = true;Ð
      fastPoll(cm);Ð   });Ð   function prepareCopy() {Ð     if
(d.inaccurateSelection) {Ð       d.prevInput = "";Ð
d.inaccurateSelection = false;Ð       d.input.value = cm.getSelection();Ð
        selectInput(d.input);Ð     }Ð   }Ð   on(d.input, "cut", prepareCopy);Ð
    on(d.input, "copy", prepareCopy);Ð   // Needed to handle Tab key in KHTMLÐ
    if (khtml) on(d.sizer, "mouseup", function() {Ð       if
(document.activeElement == d.input) d.input.blur();Ð       focusInput(cm);Ð
    });Ð }Ð function eventInWidget(display, e) {Ð   for (var n = e_target(e);
n != display.wrapper; n = n.parentNode) {Ð     if (!n) return true;Ð     if (/
\bCodeMirror-(?:line)?widget\b/.test(n.className) ||Ð         n.parentNode ==
display.sizer && n != display.mover) return true;Ð   }Ð }Ð function
posFromMouse(cm, e, liberal) {Ð   var display = cm.display;Ð   if (!liberal) {Ð
      var target = e_target(e);Ð     if (target == display.scrollbarH ||
target == display.scrollbarH.firstChild ||Ð         target ==
display.scrollbarV || target == display.scrollbarV.firstChild ||Ð
target == display.scrollbarFiller) return null;Ð
```

```
                                                    }Ð   var x, y, space =
getRect(display.lineSpace);Ð   // Fails unpredictably on IE[67] when mouse is
dragged around quickly.Ð   try { x = e.clientX; y = e.clientY; } catch (e)
{ return null; }Ð   return coordsChar(cm, x - space.left, y - space.top);Ð }Ð
var lastClick, lastDoubleClick;Ð function onMouseDown(e) {Ð   var cm = this,
display = cm.display, doc = cm.doc, sel = doc.sel;Ð   sel.shift = e.shiftKey;Ð
    if (eventInWidget(display, e)) {Ð     if (!webkit) {Ð
display.scroller.draggable = false;Ð       setTimeout(function()
{display.scroller.draggable = true;}, 100);Ð     }Ð     return;Ð   }Ð   if
(clickInGutter(cm, e)) return;Ð   var start = posFromMouse(cm, e);Ð   switch
(e_button(e)) {Ð   case 3:Ð     if (captureMiddleClick)
onContextMenu.call(cm, cm, e);Ð     return;Ð   case 2:Ð     if (start)
extendSelection(cm.doc, start);Ð     setTimeout(bind(focusInput, cm), 20);Ð
      e_preventDefault(e);Ð     return;Ð   }Ð   // For button 1, if it was
clicked inside the editorÐ   // (posFromMouse returning non-null), we have to
adjust theÐ   // selection.Ð   if (!start) {if (e_target(e) ==
display.scroller) e_preventDefault(e); return;}Ð   if (!cm.state.focused)
onFocus(cm);Ð   var now = +new Date, type = "single";Ð   if (lastDoubleClick
&& lastDoubleClick.time > now - 400 && posEq(lastDoubleClick.pos, start)) {Ð
      type = "triple";Ð     e_preventDefault(e);Ð
setTimeout(bind(focusInput, cm), 20);Ð     selectLine(cm, start.line);Ð   }
else if (lastClick && lastClick.time > now - 400 && posEq(lastClick.pos,
start)) {Ð     type = "double";Ð     lastDoubleClick = {time: now, pos:
start};Ð     e_preventDefault(e);Ð     var word = findWordAt(getLine(doc,
start.line).text, start);Ð     extendSelection(cm.doc, word.from, word.to);Ð
    } else { lastClick = {time: now, pos: start}; }Ð   var last = start;Ð
if (cm.options.dragDrop && dragAndDrop && !isReadOnly(cm) && !posEq(sel.from,
sel.to) &&Ð       !posLess(start, sel.from) && !posLess(sel.to, start) &&
type == "single") {Ð     var dragEnd = operation(cm, function(e2) {Ð       if
(webkit) display.scroller.draggable = false;Ð       cm.state.draggingText =
false;Ð       off(document, "mouseup", dragEnd);Ð       off(display.scroller,
"drop", dragEnd);Ð       if (Math.abs(e.clientX - e2.clientX) +
Math.abs(e.clientY - e2.clientY) < 10) {Ð         e_preventDefault(e2);Ð
           extendSelection(cm.doc, start);Ð         focusInput(cm);Ð       }Ð
      });Ð     // Let the drag handler handle this.Ð     if (webkit)
display.scroller.draggable = true;Ð     cm.state.draggingText = dragEnd;Ð
      // IE's approach to draggableÐ     if (display.scroller.dragDrop)
display.scroller.dragDrop();Ð     on(document, "mouseup", dragEnd);Ð
on(display.scroller, "drop", dragEnd);Ð     return;Ð   }Ð
e_preventDefault(e);Ð   if (type == "single") extendSelection(cm.doc,
clipPos(doc, start));Ð   var startstart = sel.from, startend = sel.to,
lastPos = start;Ð   function doSelect(cur) {Ð     if (posEq(lastPos, cur))
return;Ð     lastPos = cur;Ð     if (type == "single") {Ð
extendSelection(cm.doc, clipPos(doc, start), cur);Ð       return;Ð     }Ð
startstart = clipPos(doc, startstart);Ð     startend = clipPos(doc, startend);Ð
      if (type == "double") {Ð       var word = findWordAt(getLine(doc,
cur.line).text, cur);Ð       if (posLess(cur, startstart))
extendSelection(cm.doc, word.from, startend);Ð       else
extendSelection(cm.doc, startstart, word.to);Ð     } else if (type ==
"triple") {Ð       if (posLess(cur, startstart)) extendSelection(cm.doc,
startend, clipPos(doc, Pos(cur.line, 0)));Ð       else
extendSelection(cm.doc, startstart, clipPos(doc, Pos(cur.line + 1, 0)));Ð
      }Ð   }Ð   var editorSize = getRect(display.wrapper);Ð   // Used to
ensure timeout re-tries don't fire when another extendÐ   // happened in the
meantime (clearTimeout isn't reliable -- atÐ   // least on Chrome, the
timeouts still happen even when cleared,Ð   // if the clear happens after
their scheduled firing time).Ð   var counter = 0;Ð   function extend(e) {Ð
      var curCount = ++counter;Ð     var cur = posFromMouse(cm, e, true);Ð
      if (!cur) return;Ð     if (!posEq(cur, last)) {Ð       if (!
cm.state.focused) onFocus(cm);Ð
```

```
                                        last = cur;Ð       doSelect(cur);Ð
        var visible = visibleLines(display, doc);Ð       if (cur.line >=
visible.to || cur.line < visible.from)Ð         setTimeout(operation(cm,
function(){if (counter == curCount) extend(e);}), 150);Ð     } else {Ð
var outside = e.clientY < editorSize.top ? -20 : e.clientY >
editorSize.bottom ? 20 : 0;Ð       if (outside) setTimeout(operation(cm,
function() {Ð         if (counter != curCount) return;Ð
display.scroller.scrollTop += outside;Ð         extend(e);Ð       }), 50);Ð
      }Ð   }Ð   function done(e) {Ð     counter = Infinity;Ð     var cur =
posFromMouse(cm, e);Ð     if (cur) doSelect(cur);Ð     e_preventDefault(e);Ð
      focusInput(cm);Ð     off(document, "mousemove", move);Ð
off(document, "mouseup", up);Ð   }Ð   var move = operation(cm, function(e) {Ð
      if (!ie && !e_button(e)) done(e);Ð     else extend(e);Ð   });Ð   var up
= operation(cm, done);Ð   on(document, "mousemove", move);Ð   on(document,
"mouseup", up);Ð }Ð function onDrop(e) {Ð   var cm = this;Ð   if
(eventInWidget(cm.display, e) || (cm.options.onDragEvent &&
cm.options.onDragEvent(cm, addStop(e))))Ð     return;Ð   e_preventDefault(e);Ð
    var pos = posFromMouse(cm, e, true), files = e.dataTransfer.files;Ð   if
(!pos || isReadOnly(cm)) return;Ð   if (files && files.length &&
window.FileReader && window.File) {Ð     var n = files.length, text =
Array(n), read = 0;Ð     var loadFile = function(file, i) {Ð       var reader
= new FileReader;Ð       reader.onload = function() {Ð         text[i] =
reader.result;Ð         if (++read == n) {Ð           pos = clipPos(cm.doc,
pos);Ð           makeChange(cm.doc, {from: pos, to: pos, text:
splitLines(text.join("\n")), origin: "paste"}, "around");Ð         }Ð       };Ð
        reader.readAsText(file);Ð     };Ð     for (var i = 0; i < n; ++i)
loadFile(files[i], i);Ð   } else {Ð     // Don't do a replace if the drop
happened inside of the selected text.Ð     if (cm.state.draggingText && !
(posLess(pos, cm.doc.sel.from) || posLess(cm.doc.sel.to, pos))) {Ð
cm.state.draggingText(e);Ð       // Ensure the editor is re-focusedÐ
setTimeout(bind(focusInput, cm), 20);Ð       return;Ð     }Ð     try {Ð
var text = e.dataTransfer.getData("Text");Ð       if (text) {Ð         var
curFrom = cm.doc.sel.from, curTo = cm.doc.sel.to;Ð
setSelection(cm.doc, pos, pos);Ð         if (cm.state.draggingText)
replaceRange(cm.doc, "", curFrom, curTo, "paste");Ð
cm.replaceSelection(text, null, "paste");Ð         focusInput(cm);Ð
onFocus(cm);Ð       }Ð     }Ð     catch(e){}Ð   }Ð }Ð function
clickInGutter(cm, e) {Ð   var display = cm.display;Ð   try { var mX =
e.clientX, mY = e.clientY; }Ð   catch(e) { return false; }Ð   if (mX >=
Math.floor(getRect(display.gutters).right)) return false;Ð
e_preventDefault(e);Ð   if (!hasHandler(cm, "gutterClick")) return true;Ð
var lineBox = getRect(display.lineDiv);Ð   if (mY > lineBox.bottom) return
true;Ð   mY -= lineBox.top - display.viewOffset;Ð   for (var i = 0; i <
cm.options.gutters.length; ++i) {Ð     var g = display.gutters.childNodes[i];Ð
      if (g && getRect(g).right >= mX) {Ð       var line =
lineAtHeight(cm.doc, mY);Ð       var gutter = cm.options.gutters[i];Ð
signalLater(cm, "gutterClick", cm, line, gutter, e);Ð       break;Ð     }Ð   }Ð
    return true;Ð }Ð function onDragStart(cm, e) {Ð   if (ie && !
cm.state.draggingText) { e_stop(e); return; }Ð   if
(eventInWidget(cm.display, e)) return;Ð   var txt = cm.getSelection();Ð
e.dataTransfer.setData("Text", txt);Ð   // Use dummy image instead of default
browsers image.Ð   // Recent Safari (~6.0.2) have a tendency to segfault when
this happens, so we don't do it there.Ð   if (e.dataTransfer.setDragImage) {Ð
      var img = elt("img", null, null, "position: fixed; left: 0; top: 0;");Ð
      if (opera) {Ð       img.width = img.height = 1;Ð
cm.display.wrapper.appendChild(img);Ð       // Force a relayout, or Opera
won't use our image for some obscure reasonÐ       img._top = img.offsetTop;Ð
      }Ð     if (safari) {Ð       if (cm.display.dragImg) {Ð         img =
cm.display.dragImg;Ð       } else {Ð         cm.display.dragImg = img;Ð
          img.src = "";Ð
```

```
cm.display.wrapper.appendChild(img);Ð       }Ð     }Ð
e.dataTransfer.setDragImage(img, 0, 0);Ð     if (opera)
img.parentNode.removeChild(img);Ð   }Ð }Ð function setScrollTop(cm, val) {Ð
if (Math.abs(cm.doc.scrollTop - val) < 2) return;Ð   cm.doc.scrollTop = val;Ð
    if (!gecko) updateDisplay(cm, [], val);Ð   if
(cm.display.scroller.scrollTop != val) cm.display.scroller.scrollTop = val;Ð
    if (cm.display.scrollbarV.scrollTop != val)
cm.display.scrollbarV.scrollTop = val;Ð   if (gecko) updateDisplay(cm, []);Ð }Ð
  function setScrollLeft(cm, val, isScroller) {Ð   if (isScroller ? val ==
cm.doc.scrollLeft : Math.abs(cm.doc.scrollLeft - val) < 2) return;Ð   val =
Math.min(val, cm.display.scroller.scrollWidth -
cm.display.scroller.clientWidth);Ð   cm.doc.scrollLeft = val;Ð
alignHorizontally(cm);Ð   if (cm.display.scroller.scrollLeft != val)
cm.display.scroller.scrollLeft = val;Ð   if
(cm.display.scrollbarH.scrollLeft != val) cm.display.scrollbarH.scrollLeft =
val;Ð }Ð // Since the delta values reported on mouse wheel events areÐ //
unstandardized between browsers and even browser versions, andÐ // generally
horribly unpredictable, this code starts by measuringÐ // the scroll effect
that the first few mouse wheel events have,Ð // and, from that, detects the
way it can convert deltas to pixelÐ // offsets afterwards.Ð //Ð // The reason
we want to know the amount a wheel event will scrollÐ // is that it gives us
a chance to update the display before theÐ // actual scrolling happens,
reducing flickering.Ð var wheelSamples = 0, wheelPixelsPerUnit = null;Ð //
Fill in a browser-detected starting value on browsers where weÐ // know one.
These don't have to be accurate -- the result of themÐ // being wrong would
just be a slight flicker on the first wheelÐ // scroll (if it is large
enough).Ð if (ie) wheelPixelsPerUnit = -.53;Ð else if (gecko)
wheelPixelsPerUnit = 15;Ð else if (chrome) wheelPixelsPerUnit = -.7;Ð else if
(safari) wheelPixelsPerUnit = -1/3;Ð function onScrollWheel(cm, e) {Ð   var
dx = e.wheelDeltaX, dy = e.wheelDeltaY;Ð   if (dx == null && e.detail &&
e.axis == e.HORIZONTAL_AXIS) dx = e.detail;Ð   if (dy == null && e.detail &&
e.axis == e.VERTICAL_AXIS) dy = e.detail;Ð   else if (dy == null) dy =
e.wheelDelta;Ð   var display = cm.display, scroll = display.scroller;Ð   //
Quit if there's nothing to scroll hereÐ   if (!(dx && scroll.scrollWidth >
scroll.clientWidth ||Ð         dy && scroll.scrollHeight >
scroll.clientHeight)) return;Ð   // Webkit browsers on OS X abort momentum
scrolls when the targetÐ   // of the scroll event is removed from the
scrollable element.Ð   // This hack (see related code in patchDisplay) makes
sure theÐ   // element is kept around.Ð   if (dy && mac && webkit) {Ð     for
(var cur = e.target; cur != scroll; cur = cur.parentNode) {Ð       if
(cur.lineObj) {Ð         cm.display.currentWheelTarget = cur;Ð         break;Ð
        }Ð     }Ð   }Ð   // On some browsers, horizontal scrolling will cause
redraws toÐ   // happen before the gutter has been realigned, causing it toÐ
    // wriggle around in a most unseemly way. When we have anÐ   // estimated
pixels/delta value, we just handle horizontalÐ   // scrolling entirely here.
It'll be slightly off from native, butÐ   // better than glitching out.Ð   if
(dx && !gecko && !opera && wheelPixelsPerUnit != null) {Ð     if (dy)Ð
setScrollTop(cm, Math.max(0, Math.min(scroll.scrollTop + dy *
wheelPixelsPerUnit, scroll.scrollHeight - scroll.clientHeight)));Ð
setScrollLeft(cm, Math.max(0, Math.min(scroll.scrollLeft + dx *
wheelPixelsPerUnit, scroll.scrollWidth - scroll.clientWidth)));Ð
e_preventDefault(e);Ð     display.wheelStartX = null; // Abort measurement,
if in progressÐ     return;Ð   }Ð   if (dy && wheelPixelsPerUnit != null) {Ð
      var pixels = dy * wheelPixelsPerUnit;Ð     var top = cm.doc.scrollTop,
bot = top + display.wrapper.clientHeight;Ð     if (pixels < 0) top =
Math.max(0, top + pixels - 50);Ð     else bot = Math.min(cm.doc.height, bot +
pixels + 50);Ð     updateDisplay(cm, [], {top: top, bottom: bot});Ð   }Ð   if
(wheelSamples < 20) {Ð     if (display.wheelStartX == null) {Ð
display.wheelStartX = scroll.scrollLeft; display.wheelStartY =
scroll.scrollTop;Ð
```

```
                        display.wheelDX = dx; display.wheelDY = dy;Ð
setTimeout(function() {Ð         if (display.wheelStartX == null) return;Ð
          var movedX = scroll.scrollLeft - display.wheelStartX;Ð         var
movedY = scroll.scrollTop - display.wheelStartY;Ð         var sample =
(movedY && display.wheelDY && movedY / display.wheelDY) ||Ð           (movedX
&& display.wheelDX && movedX / display.wheelDX);Ð         display.wheelStartX
= display.wheelStartY = null;Ð         if (!sample) return;Ð
wheelPixelsPerUnit = (wheelPixelsPerUnit * wheelSamples + sample) /
(wheelSamples + 1);Ð         ++wheelSamples;Ð       }, 200);Ð     } else {Ð
        display.wheelDX += dx; display.wheelDY += dy;Ð     }Ð   }Ð }Ð
function doHandleBinding(cm, bound, dropShift) {Ð   if (typeof bound ==
"string") {Ð     bound = commands[bound];Ð     if (!bound) return false;Ð   }Ð
    // Ensure previous input has been read, so that the handler sees aÐ   //
consistent view of the documentÐ   if (cm.display.pollingFast &&
readInput(cm)) cm.display.pollingFast = false;Ð   var doc = cm.doc, prevShift
= doc.sel.shift, done = false;Ð   try {Ð     if (isReadOnly(cm))
cm.state.suppressEdits = true;Ð     if (dropShift) doc.sel.shift = false;Ð
      done = bound(cm) != Pass;Ð   } finally {Ð     doc.sel.shift = prevShift;Ð
      cm.state.suppressEdits = false;Ð   }Ð   return done;Ð }Ð function
allKeyMaps(cm) {Ð   var maps = cm.state.keyMaps.slice(0);Ð   if
(cm.options.extraKeys) maps.push(cm.options.extraKeys);Ð
maps.push(cm.options.keyMap);Ð   return maps;Ð }Ð var maybeTransition;Ð
function handleKeyBinding(cm, e) {Ð   // Handle auto keymap transitionsÐ
var startMap = getKeyMap(cm.options.keyMap), next = startMap.auto;Ð
clearTimeout(maybeTransition);Ð   if (next && !isModifierKey(e))
maybeTransition = setTimeout(function() {Ð     if
(getKeyMap(cm.options.keyMap) == startMap)Ð       cm.options.keyMap =
(next.call ? next.call(null, cm) : next);Ð   }, 50);Ð   var name = keyName(e,
true), handled = false;Ð   if (!name) return false;Ð   var keymaps =
allKeyMaps(cm);Ð   if (e.shiftKey) {Ð     // First try to resolve full name
(including 'Shift-'). FailingÐ     // that, see if there is a cursor-motion
command (starting withÐ     // 'go') bound to the keyname without 'Shift-'.Ð
      handled = lookupKey("Shift-" + name, keymaps, function(b) {return
doHandleBinding(cm, b, true);})Ð            || lookupKey(name, keymaps,
function(b) {Ð                 if (typeof b == "string" && /^go[A-
Z]/.test(b)) return doHandleBinding(cm, b);Ð               });Ð   } else {Ð
      handled = lookupKey(name, keymaps, function(b) { return
doHandleBinding(cm, b); });Ð   }Ð   if (handled == "stop") handled = false;Ð
    if (handled) {Ð     e_preventDefault(e);Ð     restartBlink(cm);Ð     if
(ie_lt9) { e.oldKeyCode = e.keyCode; e.keyCode = 0; }Ð   }Ð   return handled;Ð
  }Ð function handleCharBinding(cm, e, ch) {Ð   var handled = lookupKey("'" +
ch + "'", allKeyMaps(cm),Ð                             function(b) { return
doHandleBinding(cm, b, true); });Ð   if (handled) {Ð     e_preventDefault(e);Ð
      restartBlink(cm);Ð   }Ð   return handled;Ð }Ð var lastStoppedKey = null;Ð
  function onKeyDown(e) {Ð   var cm = this;Ð   if (!cm.state.focused)
onFocus(cm);Ð   if (ie && e.keyCode == 27) { e.returnValue = false; }Ð   if
(cm.options.onKeyEvent && cm.options.onKeyEvent(cm, addStop(e))) return;Ð
var code = e.keyCode;Ð   // IE does strange things with escape.Ð
cm.doc.sel.shift = code == 16 || e.shiftKey;Ð   // First give onKeyEvent
option a chance to handle this.Ð   var handled = handleKeyBinding(cm, e);Ð
if (opera) {Ð     lastStoppedKey = handled ? code : null;Ð     // Opera has
no cut event... we try to at least catch the key comboÐ     if (!handled &&
code == 88 && !hasCopyEvent && (mac ? e.metaKey : e.ctrlKey))Ð
cm.replaceSelection("");Ð   }Ð }Ð function onKeyPress(e) {Ð   var cm = this;Ð
    if (cm.options.onKeyEvent && cm.options.onKeyEvent(cm, addStop(e)))
return;Ð   var keyCode = e.keyCode, charCode = e.charCode;Ð   if (opera &&
keyCode == lastStoppedKey) {lastStoppedKey = null; e_preventDefault(e);
return;}Ð   if (((opera && (!e.which || e.which < 10)) || khtml) &&
handleKeyBinding(cm, e)) return;Ð   var ch = String.fromCharCode(charCode ==
null ? keyCode : charCode);Ð
```

```
                                if (this.options.electricChars &&
this.doc.mode.electricChars &&Ð       this.options.smartIndent && !
isReadOnly(this) &&Ð       this.doc.mode.electricChars.indexOf(ch) > -1)Ð
setTimeout(operation(cm, function() {indentLine(cm, cm.doc.sel.to.line,
"smart");}), 75);Ð   if (handleCharBinding(cm, e, ch)) return;Ð   if (ie && !
ie_lt9) cm.display.inputHasSelection = null;Ð   fastPoll(cm);Ð }Ð function
onFocus(cm) {Ð   if (cm.options.readOnly == "nocursor") return;Ð   if (!
cm.state.focused) {Ð     signal(cm, "focus", cm);Ð     cm.state.focused =
true;Ð     if (cm.display.wrapper.className.search(/\bCodeMirror-focused\b/)
== -1)Ð       cm.display.wrapper.className += " CodeMirror-focused";Ð
resetInput(cm, true);Ð   }Ð   slowPoll(cm);Ð   restartBlink(cm);Ð }Ð function
onBlur(cm) {Ð   if (cm.state.focused) {Ð     signal(cm, "blur", cm);Ð
cm.state.focused = false;Ð     cm.display.wrapper.className =
cm.display.wrapper.className.replace(" CodeMirror-focused", "");Ð   }Ð
clearInterval(cm.display.blinker);Ð   setTimeout(function() {if (!
cm.state.focused) cm.doc.sel.shift = false;}, 150);Ð }Ð var
detectingSelectAll;Ð function onContextMenu(cm, e) {Ð   var display =
cm.display, sel = cm.doc.sel;Ð   if (eventInWidget(display, e)) return;Ð
var pos = posFromMouse(cm, e), scrollPos = display.scroller.scrollTop;Ð   if
(!pos || opera) return; // Opera is difficult.Ð   if (posEq(sel.from, sel.to)
|| posLess(pos, sel.from) || !posLess(pos, sel.to))Ð     operation(cm,
setSelection)(cm.doc, pos, pos);Ð   var oldCSS = display.input.style.cssText;Ð
    display.inputDiv.style.position = "absolute";Ð
display.input.style.cssText = "position: fixed; width: 30px; height: 30px;
top: " + (e.clientY - 5) +Ð     "px; left: " + (e.clientX - 5) + "px; z-
index: 1000; background: white; outline: none;" +Ð     "border-width: 0;
outline: none; overflow: hidden; opacity: .05; -ms-opacity: .05; filter:
alpha(opacity=5);";Ð   focusInput(cm);Ð   resetInput(cm, true);Ð   // Adds
"Select all" to context menu in FFÐ   if (posEq(sel.from, sel.to))
display.input.value = display.prevInput = " ";Ð   function rehide() {Ð
display.inputDiv.style.position = "relative";Ð
display.input.style.cssText = oldCSS;Ð     if (ie_lt9)
display.scrollbarV.scrollTop = display.scroller.scrollTop = scrollPos;Ð
slowPoll(cm);Ð     // Try to detect the user choosing select-allÐ     if
(display.input.selectionStart != null && (!ie || ie_lt9)) {Ð
clearTimeout(detectingSelectAll);Ð       var extval = display.input.value = "
" + (posEq(sel.from, sel.to) ? "" : display.input.value), i = 0;Ð
display.prevInput = " ";Ð       display.input.selectionStart = 1;
display.input.selectionEnd = extval.length;Ð       var poll = function(){Ð
          if (display.prevInput == " " && display.input.selectionStart == 0)Ð
            operation(cm, commands.selectAll)(cm);Ð         else if (i++ <
10) detectingSelectAll = setTimeout(poll, 500);Ð         else resetInput(cm);Ð
        };Ð       detectingSelectAll = setTimeout(poll, 200);Ð     }Ð   }Ð
if (captureMiddleClick) {Ð     e_stop(e);Ð     var mouseup = function() {Ð
        off(window, "mouseup", mouseup);Ð       setTimeout(rehide, 20);Ð
      };Ð     on(window, "mouseup", mouseup);Ð   } else {Ð
setTimeout(rehide, 50);Ð   }Ð }Ð // UPDATINGÐ function changeEnd(change) {Ð
if (!change.text) return change.to;Ð   return Pos(change.from.line +
change.text.length - 1,Ð              lst(change.text).length +
(change.text.length == 1 ? change.from.ch : 0));Ð }Ð // Make sure a position
will be valid after the given change.Ð function clipPostChange(doc, change,
pos) {Ð   if (!posLess(change.from, pos)) return clipPos(doc, pos);Ð   var
diff = (change.text.length - 1) - (change.to.line - change.from.line);Ð   if
(pos.line > change.to.line + diff) {Ð     var preLine = pos.line - diff,
lastLine = doc.first + doc.size - 1;Ð     if (preLine > lastLine) return
Pos(lastLine, getLine(doc, lastLine).text.length);Ð     return clipToLen(pos,
getLine(doc, preLine).text.length);Ð   }Ð   if (pos.line == change.to.line +
diff)Ð     return clipToLen(pos, lst(change.text).length +
(change.text.length == 1 ? change.from.ch : 0) +Ð
getLine(doc, change.to.line).text.length - change.to.ch);Ð
```

```
                                                                var inside =
pos.line - change.from.line;Ð   return clipToLen(pos,
change.text[inside].length + (inside ? 0 : change.from.ch));Ð }Ð // Hint can
be null|"end"|"start"|"around"|{anchor,head}Ð function
computeSelAfterChange(doc, change, hint) {Ð   if (hint && typeof hint ==
"object") // Assumed to be {anchor, head} objectÐ     return {anchor:
clipPostChange(doc, change, hint.anchor),Ð             head:
clipPostChange(doc, change, hint.head)};Ð   if (hint == "start") return
{anchor: change.from, head: change.from};Ð   var end = changeEnd(change);Ð
if (hint == "around") return {anchor: change.from, head: end};Ð   if (hint ==
"end") return {anchor: end, head: end};Ð   // hint is null, leave the
selection alone as much as possibleÐ   var adjustPos = function(pos) {Ð
if (posLess(pos, change.from)) return pos;Ð     if (!posLess(change.to, pos))
return end;Ð     var line = pos.line + change.text.length - (change.to.line -
change.from.line) - 1, ch = pos.ch;Ð     if (pos.line == change.to.line) ch
+= end.ch - change.to.ch;Ð     return Pos(line, ch);Ð   };Ð   return {anchor:
adjustPos(doc.sel.anchor), head: adjustPos(doc.sel.head)};Ð }Ð function
filterChange(doc, change) {Ð   var obj = {Ð     canceled: false,Ð     from:
change.from,Ð     to: change.to,Ð     text: change.text,Ð     origin:
change.origin,Ð     update: function(from, to, text, origin) {Ð       if
(from) this.from = clipPos(doc, from);Ð       if (to) this.to = clipPos(doc,
to);Ð       if (text) this.text = text;Ð       if (origin !== undefined)
this.origin = origin;Ð     },Ð     cancel: function() { this.canceled =
true; }Ð   };Ð   signal(doc, "beforeChange", doc, obj);Ð   if (doc.cm)
signal(doc.cm, "beforeChange", doc.cm, obj);Ð   if (obj.canceled) return null;Ð
    return {from: obj.from, to: obj.to, text: obj.text, origin: obj.origin};Ð
  }Ð // Replace the range from from to to by the strings in replacement.Ð //
change is a {from, to, text [, origin]} objectÐ function makeChange(doc,
change, selUpdate, ignoreReadOnly) {Ð   if (doc.cm) {Ð     if (!doc.cm.curOp)
return operation(doc.cm, makeChange)(doc, change, selUpdate, ignoreReadOnly);Ð
      if (doc.cm.state.suppressEdits) return;Ð   }Ð   if (hasHandler(doc,
"beforeChange") || doc.cm && hasHandler(doc.cm, "beforeChange")) {Ð
change = filterChange(doc, change);Ð     if (!change) return;Ð   }Ð   //
Possibly split or suppress the update based on the presenceÐ   // of read-
only spans in its range.Ð   var split = sawReadOnlySpans && !ignoreReadOnly
&& removeReadOnlyRanges(doc, change.from, change.to);Ð   if (split) {Ð
for (var i = split.length - 1; i >= 1; --i)Ð       makeChangeNoReadonly(doc,
{from: split[i].from, to: split[i].to, text: [""]});Ð     if (split.length)Ð
        makeChangeNoReadonly(doc, {from: split[0].from, to: split[0].to,
text: change.text}, selUpdate);Ð   } else {Ð     makeChangeNoReadonly(doc,
change, selUpdate);Ð   }Ð }Ð function makeChangeNoReadonly(doc, change,
selUpdate) {Ð   var selAfter = computeSelAfterChange(doc, change, selUpdate);Ð
    addToHistory(doc, change, selAfter, doc.cm ? doc.cm.curOp.id : NaN);Ð
makeChangeSingleDoc(doc, change, selAfter, stretchSpansOverChange(doc,
change));Ð   var rebased = [];Ð   linkedDocs(doc, function(doc, sharedHist) {Ð
      if (!sharedHist && indexOf(rebased, doc.history) == -1) {Ð
rebaseHist(doc.history, change);Ð       rebased.push(doc.history);Ð     }Ð
      makeChangeSingleDoc(doc, change, null, stretchSpansOverChange(doc,
change));Ð   });Ð }Ð function makeChangeFromHistory(doc, type) {Ð   if
(doc.cm && doc.cm.state.suppressEdits) return;Ð   var hist = doc.history;Ð
var event = (type == "undo" ? hist.done : hist.undone).pop();Ð   if (!event)
return;Ð   hist.dirtyCounter += type == "undo" ? -1 : 1;Ð   var anti =
{changes: [], anchorBefore: event.anchorAfter, headBefore: event.headAfter,Ð
                 anchorAfter: event.anchorBefore, headAfter: event.headBefore};Ð
    (type == "undo" ? hist.undone : hist.done).push(anti);Ð   for (var i =
event.changes.length - 1; i >= 0; --i) {Ð     var change = event.changes[i];Ð
      change.origin = type;Ð
anti.changes.push(historyChangeFromChange(doc, change));Ð     var after = i ?
computeSelAfterChange(doc, change, null)Ð                   : {anchor:
event.anchorBefore, head: event.headBefore};Ð
```

```
                                                    makeChangeSingleDoc(doc,
change, after, mergeOldSpans(doc, change));Ð     var rebased = [];Ð
linkedDocs(doc, function(doc, sharedHist) {Ð       if (!sharedHist &&
indexOf(rebased, doc.history) == -1) {Ð         rebaseHist(doc.history,
change);Ð         rebased.push(doc.history);Ð       }Ð
makeChangeSingleDoc(doc, change, null, mergeOldSpans(doc, change));Ð     });Ð
    }Ð }Ð function shiftDoc(doc, distance) {Ð   function shiftPos(pos)
{return Pos(pos.line + distance, pos.ch);}Ð   doc.first += distance;Ð   if
(doc.cm) regChange(doc.cm, doc.first, doc.first, distance);Ð   doc.sel.head =
shiftPos(doc.sel.head); doc.sel.anchor = shiftPos(doc.sel.anchor);Ð
doc.sel.from = shiftPos(doc.sel.from); doc.sel.to = shiftPos(doc.sel.to);Ð }Ð
function makeChangeSingleDoc(doc, change, selAfter, spans) {Ð   if (doc.cm
&& !doc.cm.curOp)Ð     return operation(doc.cm, makeChangeSingleDoc)(doc,
change, selAfter, spans);Ð   if (change.to.line < doc.first) {Ð
shiftDoc(doc, change.text.length - 1 - (change.to.line - change.from.line));Ð
      return;Ð   }Ð   if (change.from.line > doc.lastLine()) return;Ð   //
Clip the change to the size of this docÐ   if (change.from.line < doc.first) {Ð
      var shift = change.text.length - 1 - (doc.first - change.from.line);Ð
      shiftDoc(doc, shift);Ð     change = {from: Pos(doc.first, 0), to:
Pos(change.to.line + shift, change.to.ch),Ð               text:
[lst(change.text)], origin: change.origin};Ð   }Ð   var last = doc.lastLine();Ð
    if (change.to.line > last) {Ð     change = {from: change.from, to:
Pos(last, getLine(doc, last).text.length),Ð               text:
[change.text[0]], origin: change.origin};Ð   }Ð   change.removed =
getBetween(doc, change.from, change.to);Ð   if (!selAfter) selAfter =
computeSelAfterChange(doc, change, null);Ð   if (doc.cm)
makeChangeSingleDocInEditor(doc.cm, change, spans, selAfter);Ð   else
updateDoc(doc, change, spans, selAfter);Ð }Ð function
makeChangeSingleDocInEditor(cm, change, spans, selAfter) {Ð   var doc =
cm.doc, display = cm.display, from = change.from, to = change.to;Ð   var
recomputeMaxLength = false, checkWidthStart = from.line;Ð   if (!
cm.options.lineWrapping) {Ð     checkWidthStart = lineNo(visualLine(doc,
getLine(doc, from.line)));Ð     doc.iter(checkWidthStart, to.line + 1,
function(line) {Ð       if (line == display.maxLine) {Ð
recomputeMaxLength = true;Ð         return true;Ð       }Ð     });Ð   }Ð   if
(!posLess(doc.sel.head, change.from) && !posLess(change.to, doc.sel.head))Ð
      cm.curOp.cursorActivity = true;Ð   updateDoc(doc, change, spans,
selAfter, estimateHeight(cm));Ð   if (!cm.options.lineWrapping) {Ð
doc.iter(checkWidthStart, from.line + change.text.length, function(line) {Ð
        var len = lineLength(doc, line);Ð       if (len >
display.maxLineLength) {Ð         display.maxLine = line;Ð
display.maxLineLength = len;Ð         display.maxLineChanged = true;Ð
recomputeMaxLength = false;Ð       }Ð     });Ð     if (recomputeMaxLength)
cm.curOp.updateMaxLine = true;Ð   }Ð   // Adjust frontier, schedule workerÐ
doc.frontier = Math.min(doc.frontier, from.line);Ð   startWorker(cm, 400);Ð
var lendiff = change.text.length - (to.line - from.line) - 1;Ð   // Remember
that these lines changed, for updating the displayÐ   regChange(cm,
from.line, to.line + 1, lendiff);Ð   if (hasHandler(cm, "change")) {Ð     var
changeObj = {from: from, to: to,Ð                       text: change.text,Ð
                      removed: change.removed,Ð                      origin:
change.origin};Ð     if (cm.curOp.textChanged) {Ð       for (var cur =
cm.curOp.textChanged; cur.next; cur = cur.next) {}Ð       cur.next =
changeObj;Ð     } else cm.curOp.textChanged = changeObj;Ð   }Ð }Ð function
replaceRange(doc, code, from, to, origin) {Ð   if (!to) to = from;Ð   if
(posLess(to, from)) { var tmp = to; to = from; from = tmp; }Ð   if (typeof
code == "string") code = splitLines(code);Ð   makeChange(doc, {from: from,
to: to, text: code, origin: origin}, null);Ð }Ð // POSITION OBJECTÐ function
Pos(line, ch) {Ð   if (!(this instanceof Pos)) return new Pos(line, ch);Ð
this.line = line; this.ch = ch;Ð }Ð CodeMirror.Pos = Pos;Ð function posEq(a,
b) {return a.line == b.line && a.ch == b.ch;}Ð
```

```
                                                function posLess(a, b) {return
a.line < b.line || (a.line == b.line && a.ch < b.ch);}Ð function copyPos(x)
{return Pos(x.line, x.ch);}Ð // SELECTIONÐ function clipLine(doc, n) {return
Math.max(doc.first, Math.min(n, doc.first + doc.size - 1));}Ð function
clipPos(doc, pos) {Ð   if (pos.line < doc.first) return Pos(doc.first, 0);Ð
var last = doc.first + doc.size - 1;Ð   if (pos.line > last) return Pos(last,
getLine(doc, last).text.length);Ð   return clipToLen(pos, getLine(doc,
pos.line).text.length);Ð }Ð function clipToLen(pos, linelen) {Ð   var ch =
pos.ch;Ð   if (ch == null || ch > linelen) return Pos(pos.line, linelen);Ð
else if (ch < 0) return Pos(pos.line, 0);Ð   else return pos;Ð }Ð function
isLine(doc, l) {return l >= doc.first && l < doc.first + doc.size;}Ð // If
shift is held, this will move the selection anchor. Otherwise,Ð // it'll set
the whole selection.Ð function extendSelection(doc, pos, other, bias) {Ð   if
(doc.sel.shift || doc.sel.extend) {Ð     var anchor = doc.sel.anchor;Ð     if
(other) {Ð       var posBefore = posLess(pos, anchor);Ð       if (posBefore !
= posLess(other, anchor)) {Ð         anchor = pos;Ð         pos = other;Ð
        } else if (posBefore != posLess(pos, other)) {Ð         pos = other;Ð
        }Ð     }Ð     setSelection(doc, anchor, pos, bias);Ð   } else {Ð
setSelection(doc, pos, other || pos, bias);Ð   }Ð   if (doc.cm)
doc.cm.curOp.userSelChange = true;Ð }Ð function filterSelectionChange(doc,
anchor, head) {Ð   var obj = {anchor: anchor, head: head};Ð   signal(doc,
"beforeSelectionChange", doc, obj);Ð   if (doc.cm) signal(doc.cm,
"beforeSelectionChange", doc.cm, obj);Ð   obj.anchor = clipPos(doc,
obj.anchor); obj.head = clipPos(doc, obj.head);Ð   return obj;Ð }Ð // Update
the selection. Last two args are only used byÐ // updateDoc, since they have
to be expressed in the lineÐ // numbers before the update.Ð function
setSelection(doc, anchor, head, bias, checkAtomic) {Ð   if (!checkAtomic &&
hasHandler(doc, "beforeSelectionChange") || doc.cm && hasHandler(doc.cm,
"beforeSelectionChange")) {Ð     var filtered = filterSelectionChange(doc,
anchor, head);Ð     head = filtered.head;Ð     anchor = filtered.anchor;Ð   }Ð
    var sel = doc.sel;Ð   sel.goalColumn = null;Ð   // Skip over atomic spans.Ð
    if (checkAtomic || !posEq(anchor, sel.anchor))Ð     anchor =
skipAtomic(doc, anchor, bias, checkAtomic != "push");Ð   if (checkAtomic || !
posEq(head, sel.head))Ð     head = skipAtomic(doc, head, bias, checkAtomic !=
"push");Ð   if (posEq(sel.anchor, anchor) && posEq(sel.head, head)) return;Ð
    sel.anchor = anchor; sel.head = head;Ð   var inv = posLess(head, anchor);Ð
    sel.from = inv ? head : anchor;Ð   sel.to = inv ? anchor : head;Ð   if
(doc.cm)Ð     doc.cm.curOp.updateInput = doc.cm.curOp.selectionChanged =Ð
        doc.cm.curOp.cursorActivity = true;Ð   signalLater(doc,
"cursorActivity", doc);Ð }Ð function reCheckSelection(cm) {Ð
setSelection(cm.doc, cm.doc.sel.from, cm.doc.sel.to, null, "push");Ð }Ð
function skipAtomic(doc, pos, bias, mayClear) {Ð   var flipped = false,
curPos = pos;Ð   var dir = bias || 1;Ð   doc.cantEdit = false;Ð   search: for
(;;) {Ð     var line = getLine(doc, curPos.line);Ð     if (line.markedSpans) {Ð
        for (var i = 0; i < line.markedSpans.length; ++i) {Ð         var sp =
line.markedSpans[i], m = sp.marker;Ð         if ((sp.from == null ||
(m.inclusiveLeft ? sp.from <= curPos.ch : sp.from < curPos.ch)) &&Ð
              (sp.to == null || (m.inclusiveRight ? sp.to >= curPos.ch :
sp.to > curPos.ch))) {Ð           if (mayClear) {Ð             signal(m,
"beforeCursorEnter");Ð             if (m.explicitlyCleared) {Ð
if (!line.markedSpans) break;Ð               else {--i; continue;}Ð
              }Ð           }Ð           if (!m.atomic) continue;Ð
var newPos = m.find()[dir < 0 ? "from" : "to"];Ð           if (posEq(newPos,
curPos)) {Ð             newPos.ch += dir;Ð             if (newPos.ch < 0) {Ð
                if (newPos.line > doc.first) newPos = clipPos(doc,
Pos(newPos.line - 1));Ð               else newPos = null;Ð             } else
if (newPos.ch > line.text.length) {Ð               if (newPos.line <
doc.first + doc.size - 1) newPos = Pos(newPos.line + 1, 0);Ð
else newPos = null;Ð             }Ð             if (!newPos) {Ð
if (flipped) {Ð
```

```
                                // Driven in a corner -- no valid cursor
position found at allÐ                 // -- try again *with* clearing, if we
didn't alreadyÐ                 if (!mayClear) return skipAtomic(doc, pos,
bias, true);Ð                 // Otherwise, turn off editing until further
notice, and return the start of the docÐ                 doc.cantEdit = true;Ð
                  return Pos(doc.first, 0);Ð                 }Ð
flipped = true; newPos = pos; dir = -dir;Ð             }Ð           }Ð
            curPos = newPos;Ð           continue search;Ð         }Ð       }Ð
      }Ð     return curPos;Ð   }Ð }Ð // SCROLLINGÐ function
scrollCursorIntoView(cm) {Ð   var coords = scrollPosIntoView(cm,
cm.doc.sel.head);Ð   if (!cm.state.focused) return;Ð   var display =
cm.display, box = getRect(display.sizer), doScroll = null, pTop =
paddingTop(cm.display);Ð   if (coords.top + pTop + box.top < 0) doScroll =
true;Ð   else if (coords.bottom + pTop + box.top > (window.innerHeight ||
document.documentElement.clientHeight)) doScroll = false;Ð   if (doScroll !=
null && !phantom) {Ð     var hidden = display.cursor.style.display == "none";Ð
      if (hidden) {Ð       display.cursor.style.display = "";Ð
display.cursor.style.left = coords.left + "px";Ð
display.cursor.style.top = (coords.top - display.viewOffset) + "px";Ð     }Ð
      display.cursor.scrollIntoView(doScroll);Ð     if (hidden)
display.cursor.style.display = "none";Ð   }Ð }Ð function
scrollPosIntoView(cm, pos, margin) {Ð   if (margin == null) margin = 0;Ð
for (;;) {Ð     var changed = false, coords = cursorCoords(cm, pos);Ð     var
scrollPos = calculateScrollPos(cm, coords.left, coords.top - margin,
coords.left, coords.bottom + margin);Ð     var startTop = cm.doc.scrollTop,
startLeft = cm.doc.scrollLeft;Ð     if (scrollPos.scrollTop != null) {Ð
setScrollTop(cm, scrollPos.scrollTop);Ð       if (Math.abs(cm.doc.scrollTop -
startTop) > 1) changed = true;Ð     }Ð     if (scrollPos.scrollLeft != null) {Ð
        setScrollLeft(cm, scrollPos.scrollLeft);Ð       if
(Math.abs(cm.doc.scrollLeft - startLeft) > 1) changed = true;Ð     }Ð     if
(!changed) return coords;Ð   }Ð }Ð function scrollIntoView(cm, x1, y1, x2,
y2) {Ð   var scrollPos = calculateScrollPos(cm, x1, y1, x2, y2);Ð   if
(scrollPos.scrollTop != null) setScrollTop(cm, scrollPos.scrollTop);Ð   if
(scrollPos.scrollLeft != null) setScrollLeft(cm, scrollPos.scrollLeft);Ð }Ð
function calculateScrollPos(cm, x1, y1, x2, y2) {Ð   var display =
cm.display, pt = paddingTop(display);Ð   y1 += pt; y2 += pt;Ð   if (y1 < 0)
y1 = 0;Ð   var screen = display.scroller.clientHeight - scrollerCutOff,
screentop = display.scroller.scrollTop, result = {};Ð   var docBottom =
cm.doc.height + paddingVert(display);Ð   var atTop = y1 < pt + 10, atBottom =
y2 + pt > docBottom - 10;Ð   if (y1 < screentop) {Ð     result.scrollTop =
atTop ? 0 : y1;Ð   } else if (y2 > screentop + screen) {Ð     var newTop =
Math.min(y1, (atBottom ? docBottom : y2) - screen);Ð     if (newTop !=
screentop) result.scrollTop = newTop;Ð   }Ð   var screenw =
display.scroller.clientWidth - scrollerCutOff, screenleft =
display.scroller.scrollLeft;Ð   x1 += display.gutters.offsetWidth; x2 +=
display.gutters.offsetWidth;Ð   var gutterw = display.gutters.offsetWidth;Ð
var atLeft = x1 < gutterw + 10;Ð   if (x1 < screenleft + gutterw || atLeft) {Ð
      if (atLeft) x1 = 0;Ð     result.scrollLeft = Math.max(0, x1 - 10 -
gutterw);Ð   } else if (x2 > screenw + screenleft - 3) {Ð
result.scrollLeft = x2 + 10 - screenw;Ð   }Ð   return result;Ð }Ð function
updateScrollPos(cm, left, top) {Ð   cm.curOp.updateScrollPos = {scrollLeft:
left == null ? cm.doc.scrollLeft : left,Ð
scrollTop: top == null ? cm.doc.scrollTop : top};Ð }Ð function
addToScrollPos(cm, left, top) {Ð   var pos = cm.curOp.updateScrollPos ||
(cm.curOp.updateScrollPos = {scrollLeft: cm.doc.scrollLeft, scrollTop:
cm.doc.scrollTop});Ð   var scroll = cm.display.scroller;Ð   pos.scrollTop =
Math.max(0, Math.min(scroll.scrollHeight - scroll.clientHeight, pos.scrollTop
+ top));Ð   pos.scrollLeft = Math.max(0, Math.min(scroll.scrollWidth -
scroll.clientWidth, pos.scrollLeft + left));Ð }Ð // API UTILITIESÐ function
indentLine(cm, n, how, aggressive) {Ð
```

```
                                        var doc = cm.doc;Ð   if (!how) how =
"add";Ð   if (how == "smart") {Ð     if (!cm.doc.mode.indent) how = "prev";Ð
      else var state = getStateBefore(cm, n);Ð   }Ð   var tabSize =
cm.options.tabSize;Ð   var line = getLine(doc, n), curSpace =
countColumn(line.text, null, tabSize);Ð   var curSpaceString =
line.text.match(/^\s*/)[0], indentation;Ð   if (how == "smart") {Ð
indentation = cm.doc.mode.indent(state,
line.text.slice(curSpaceString.length), line.text);Ð     if (indentation ==
Pass) {Ð       if (!aggressive) return;Ð       how = "prev";Ð     }Ð   }Ð
if (how == "prev") {Ð     if (n > doc.first) indentation =
countColumn(getLine(doc, n-1).text, null, tabSize);Ð     else indentation = 0;Ð
    } else if (how == "add") {Ð     indentation = curSpace +
cm.options.indentUnit;Ð   } else if (how == "subtract") {Ð     indentation =
curSpace - cm.options.indentUnit;Ð   }Ð   indentation = Math.max(0,
indentation);Ð   var indentString = "", pos = 0;Ð   if
(cm.options.indentWithTabs)Ð     for (var i = Math.floor(indentation /
tabSize); i; --i) {pos += tabSize; indentString += "\t";}Ð   if (pos <
indentation) indentString += spaceStr(indentation - pos);Ð   if
(indentString != curSpaceString)Ð     replaceRange(cm.doc, indentString,
Pos(n, 0), Pos(n, curSpaceString.length), "+input");Ð   line.stateAfter =
null;Ð }Ð function changeLine(cm, handle, op) {Ð   var no = handle, line =
handle, doc = cm.doc;Ð   if (typeof handle == "number") line = getLine(doc,
clipLine(doc, handle));Ð   else no = lineNo(handle);Ð   if (no == null)
return null;Ð   if (op(line, no)) regChange(cm, no, no + 1);Ð   else return
null;Ð   return line;Ð }Ð function findPosH(doc, pos, dir, unit, visually) {Ð
    var line = pos.line, ch = pos.ch;Ð   var lineObj = getLine(doc, line);Ð
var possible = true;Ð   function findNextLine() {Ð     var l = line + dir;Ð
      if (l < doc.first || l >= doc.first + doc.size) return (possible =
false);Ð     line = l;Ð     return lineObj = getLine(doc, l);Ð   }Ð
function moveOnce(boundToLine) {Ð     var next = (visually ? moveVisually :
moveLogically)(lineObj, ch, dir, true);Ð     if (next == null) {Ð       if (!
boundToLine && findNextLine()) {Ð         if (visually) ch = (dir < 0 ?
lineRight : lineLeft)(lineObj);Ð         else ch = dir < 0 ?
lineObj.text.length : 0;Ð       } else return (possible = false);Ð     } else
ch = next;Ð     return true;Ð   }Ð   if (unit == "char") moveOnce();Ð   else
if (unit == "column") moveOnce(true);Ð   else if (unit == "word" || unit ==
"group") {Ð     var sawType = null, group = unit == "group";Ð     for (var
first = true;; first = false) {Ð       if (dir < 0 && !moveOnce(!first))
break;Ð       var cur = lineObj.text.charAt(ch) || "\n";Ð       var type =
isWordChar(cur) ? "w"Ð         : !group ? nullÐ         : /\s/.test(cur) ?
nullÐ         : "p";Ð       if (sawType && sawType != type) {Ð         if
(dir < 0) {dir = 1; moveOnce();}Ð         break;Ð       }Ð       if (type)
sawType = type;Ð       if (dir > 0 && !moveOnce(!first)) break;Ð     }Ð   }Ð
    var result = skipAtomic(doc, Pos(line, ch), dir, true);Ð   if (!possible)
result.hitSide = true;Ð   return result;Ð }Ð function findPosV(cm, pos, dir,
unit) {Ð   var doc = cm.doc, x = pos.left, y;Ð   if (unit == "page") {Ð
var pageSize = Math.min(cm.display.wrapper.clientHeight, window.innerHeight
|| document.documentElement.clientHeight);Ð     y = pos.top + dir * (pageSize
- (dir < 0 ? 1.5 : .5) * textHeight(cm.display));Ð   } else if (unit ==
"line") {Ð     y = dir > 0 ? pos.bottom + 3 : pos.top - 3;Ð   }Ð   for (;;) {Ð
      var target = coordsChar(cm, x, y);Ð     if (!target.outside) break;Ð
      if (dir < 0 ? y <= 0 : y >= doc.height) { target.hitSide = true;
break; }Ð     y += dir * 5;Ð   }Ð   return target;Ð }Ð function
findWordAt(line, pos) {Ð   var start = pos.ch, end = pos.ch;Ð   if (line) {Ð
      if (pos.after === false || end == line.length) --start; else ++end;Ð
      var startChar = line.charAt(start);Ð     var check =
isWordChar(startChar) ? isWordCharÐ       : /\s/.test(startChar) ?
function(ch) {return /\s/.test(ch);}Ð       : function(ch) {return !/
\s/.test(ch) && !isWordChar(ch);};Ð     while (start > 0 &&
check(line.charAt(start - 1))) --start;Ð
```

```
                                                while (end < line.length &&
check(line.charAt(end))) ++end;Ð   }Ð   return {from: Pos(pos.line, start),
to: Pos(pos.line, end)};Ð }Ð function selectLine(cm, line) {Ð
extendSelection(cm.doc, Pos(line, 0), clipPos(cm.doc, Pos(line + 1, 0)));Ð }Ð
  // PROTOTYPEÐ // The publicly visible API. Note that operation(null, f)
meansÐ // 'wrap f in an operation, performed on its `this` parameter'Ð
CodeMirror.prototype = {Ð   focus: function(){window.focus();
focusInput(this); onFocus(this); fastPoll(this);},Ð   setOption:
function(option, value) {Ð     var options = this.options, old =
options[option];Ð     if (options[option] == value && option != "mode")
return;Ð     options[option] = value;Ð     if
(optionHandlers.hasOwnProperty(option))Ð       operation(this,
optionHandlers[option])(this, value, old);Ð   },Ð   getOption:
function(option) {return this.options[option];},Ð   getDoc: function()
{return this.doc;},Ð   addKeyMap: function(map, bottom) {Ð
this.state.keyMaps[bottom ? "push" : "unshift"](map);Ð   },Ð   removeKeyMap:
function(map) {Ð     var maps = this.state.keyMaps;Ð     for (var i = 0; i <
maps.length; ++i)Ð       if ((typeof map == "string" ? maps[i].name :
maps[i]) == map) {Ð         maps.splice(i, 1);Ð         return true;Ð       }Ð
    },Ð   addOverlay: operation(null, function(spec, options) {Ð     var mode
= spec.token ? spec : CodeMirror.getMode(this.options, spec);Ð     if
(mode.startState) throw new Error("Overlays may not be stateful.");Ð
this.state.overlays.push({mode: mode, modeSpec: spec, opaque: options &&
options.opaque});Ð     this.state.modeGen++;Ð     regChange(this);Ð   }),Ð
removeOverlay: operation(null, function(spec) {Ð     var overlays =
this.state.overlays;Ð     for (var i = 0; i < overlays.length; ++i) {Ð
if (overlays[i].modeSpec == spec) {Ð         overlays.splice(i, 1);Ð
this.state.modeGen++;Ð         regChange(this);Ð         return;Ð       }Ð
      }Ð   }),Ð   indentLine: operation(null, function(n, dir, aggressive) {Ð
      if (typeof dir != "string") {Ð       if (dir == null) dir =
this.options.smartIndent ? "smart" : "prev";Ð       else dir = dir ? "add" :
"subtract";Ð     }Ð     if (isLine(this.doc, n)) indentLine(this, n, dir,
aggressive);Ð   }),Ð   indentSelection: operation(null, function(how) {Ð
var sel = this.doc.sel;Ð     if (posEq(sel.from, sel.to)) return
indentLine(this, sel.from.line, how);Ð     var e = sel.to.line - (sel.to.ch ?
0 : 1);Ð     for (var i = sel.from.line; i <= e; ++i) indentLine(this, i,
how);Ð   }),Ð   // Fetch the parser token for a given character. Useful for
hacksÐ   // that want to inspect the mode state (say, for completion).Ð
getTokenAt: function(pos) {Ð     var doc = this.doc;Ð     pos = clipPos(doc,
pos);Ð     var state = getStateBefore(this, pos.line), mode = this.doc.mode;Ð
      var line = getLine(doc, pos.line);Ð     var stream = new
StringStream(line.text, this.options.tabSize);Ð     while (stream.pos <
pos.ch && !stream.eol()) {Ð       stream.start = stream.pos;Ð       var style
= mode.token(stream, state);Ð     }Ð     return {start: stream.start,Ð
              end: stream.pos,Ð              string: stream.current(),Ð
              className: style || null, // Deprecated, use 'type' insteadÐ
              type: style || null,Ð             state: state};Ð   },Ð
getStateAfter: function(line) {Ð     var doc = this.doc;Ð     line =
clipLine(doc, line == null ? doc.first + doc.size - 1: line);Ð     return
getStateBefore(this, line + 1);Ð   },Ð   cursorCoords: function(start, mode) {Ð
      var pos, sel = this.doc.sel;Ð     if (start == null) pos = sel.head;Ð
      else if (typeof start == "object") pos = clipPos(this.doc, start);Ð
else pos = start ? sel.from : sel.to;Ð     return cursorCoords(this, pos,
mode || "page");Ð   },Ð   charCoords: function(pos, mode) {Ð     return
charCoords(this, clipPos(this.doc, pos), mode || "page");Ð   },Ð
coordsChar: function(coords, mode) {Ð     coords = fromCoordSystem(this,
coords, mode || "page");Ð     return coordsChar(this, coords.left,
coords.top);Ð   },Ð   defaultTextHeight: function() { return
textHeight(this.display); },Ð   defaultCharWidth: function() { return
charWidth(this.display); },Ð
```

```
                            Ð   setGutterMarker: operation(null,
function(line, gutterID, value) {Ð     return changeLine(this, line,
function(line) {Ð       var markers = line.gutterMarkers ||
(line.gutterMarkers = {});Ð       markers[gutterID] = value;Ð       if (!
value && isEmpty(markers)) line.gutterMarkers = null;Ð       return true;Ð
      });Ð   }),Ð   clearGutter: operation(null, function(gutterID) {Ð
var cm = this, doc = cm.doc, i = doc.first;Ð     doc.iter(function(line) {Ð
        if (line.gutterMarkers && line.gutterMarkers[gutterID]) {Ð
line.gutterMarkers[gutterID] = null;Ð         regChange(cm, i, i + 1);Ð
          if (isEmpty(line.gutterMarkers)) line.gutterMarkers = null;Ð       }Ð
        ++i;Ð     });Ð   }),Ð   addLineClass: operation(null,
function(handle, where, cls) {Ð     return changeLine(this, handle,
function(line) {Ð       var prop = where == "text" ? "textClass" : where ==
"background" ? "bgClass" : "wrapClass";Ð       if (!line[prop]) line[prop] =
cls;Ð       else if (new RegExp("\\b" + cls + "\\b").test(line[prop])) return
false;Ð       else line[prop] += " " + cls;Ð       return true;Ð     });Ð
    }),Ð   removeLineClass: operation(null, function(handle, where, cls) {Ð
      return changeLine(this, handle, function(line) {Ð       var prop =
where == "text" ? "textClass" : where == "background" ? "bgClass" :
"wrapClass";Ð       var cur = line[prop];Ð       if (!cur) return false;Ð
        else if (cls == null) line[prop] = null;Ð       else {Ð         var
upd = cur.replace(new RegExp("^" + cls + "\\b\\s*|\\s*\\b" + cls + "\\b"),
"");Ð         if (upd == cur) return false;Ð         line[prop] = upd || null;Ð
        }Ð       return true;Ð     });Ð   }),Ð   addLineWidget:
operation(null, function(handle, node, options) {Ð     return
addLineWidget(this, handle, node, options);Ð   }),Ð   removeLineWidget:
function(widget) { widget.clear(); },Ð   lineInfo: function(line) {Ð     if
(typeof line == "number") {Ð       if (!isLine(this.doc, line)) return null;Ð
        var n = line;Ð       line = getLine(this.doc, line);Ð       if (!
line) return null;Ð     } else {Ð       var n = lineNo(line);Ð       if (n ==
null) return null;Ð     }Ð     return {line: n, handle: line, text:
line.text, gutterMarkers: line.gutterMarkers,Ð             textClass:
line.textClass, bgClass: line.bgClass, wrapClass: line.wrapClass,Ð
              widgets: line.widgets};Ð   },Ð   getViewport: function()
{ return {from: this.display.showingFrom, to: this.display.showingTo};},Ð
addWidget: function(pos, node, scroll, vert, horiz) {Ð     var display =
this.display;Ð     pos = cursorCoords(this, clipPos(this.doc, pos));Ð     var
top = pos.bottom, left = pos.left;Ð     node.style.position = "absolute";Ð
      display.sizer.appendChild(node);Ð     if (vert == "over") {Ð       top
= pos.top;Ð     } else if (vert == "above" || vert == "near") {Ð       var
vspace = Math.max(display.wrapper.clientHeight, this.doc.height),Ð
hspace = Math.max(display.sizer.clientWidth, display.lineSpace.clientWidth);Ð
        // Default to positioning above (if specified and possible);
otherwise default to positioning belowÐ       if ((vert == 'above' ||
pos.bottom + node.offsetHeight > vspace) && pos.top > node.offsetHeight)Ð
          top = pos.top - node.offsetHeight;Ð       else if (pos.bottom +
node.offsetHeight <= vspace)Ð         top = pos.bottom;Ð       if (left +
node.offsetWidth > hspace)Ð         left = hspace - node.offsetWidth;Ð     }Ð
      node.style.top = (top + paddingTop(display)) + "px";Ð
node.style.left = node.style.right = "";Ð     if (horiz == "right") {Ð
left = display.sizer.clientWidth - node.offsetWidth;Ð       node.style.right
= "0px";Ð     } else {Ð       if (horiz == "left") left = 0;Ð       else if
(horiz == "middle") left = (display.sizer.clientWidth - node.offsetWidth) / 2;Ð
        node.style.left = left + "px";Ð     }Ð     if (scroll)Ð
scrollIntoView(this, left, top, left + node.offsetWidth, top +
node.offsetHeight);Ð   },Ð   triggerOnKeyDown: operation(null, onKeyDown),Ð
execCommand: function(cmd) {return commands[cmd](this);},Ð   findPosH:
function(from, amount, unit, visually) {Ð     var dir = 1;Ð     if (amount <
0) { dir = -1; amount = -amount; }Ð     for (var i = 0, cur =
clipPos(this.doc, from); i < amount; ++i) {Ð
```

```
                                                    cur = findPosH(this.doc,
cur, dir, unit, visually);Ð       if (cur.hitSide) break;Ð     }Ð     return
cur;Ð   },Ð   moveH: operation(null, function(dir, unit) {Ð     var sel =
this.doc.sel, pos;Ð     if (sel.shift || sel.extend || posEq(sel.from,
sel.to))Ð       pos = findPosH(this.doc, sel.head, dir, unit,
this.options.rtlMoveVisually);Ð     elseÐ       pos = dir < 0 ? sel.from :
sel.to;Ð     extendSelection(this.doc, pos, pos, dir);Ð   }),Ð   deleteH:
operation(null, function(dir, unit) {Ð     var sel = this.doc.sel;Ð     if (!
posEq(sel.from, sel.to)) replaceRange(this.doc, "", sel.from, sel.to,
"+delete");Ð     else replaceRange(this.doc, "", sel.from, findPosH(this.doc,
sel.head, dir, unit, false), "+delete");Ð     this.curOp.userSelChange = true;Ð
    }),Ð   findPosV: function(from, amount, unit, goalColumn) {Ð     var dir
= 1, x = goalColumn;Ð     if (amount < 0) { dir = -1; amount = -amount; }Ð
      for (var i = 0, cur = clipPos(this.doc, from); i < amount; ++i) {Ð
        var coords = cursorCoords(this, cur, "div");Ð       if (x == null) x
= coords.left;Ð       else coords.left = x;Ð       cur = findPosV(this,
coords, dir, unit);Ð       if (cur.hitSide) break;Ð     }Ð     return cur;Ð
    },Ð   moveV: operation(null, function(dir, unit) {Ð     var sel =
this.doc.sel;Ð     var pos = cursorCoords(this, sel.head, "div");Ð     if
(sel.goalColumn != null) pos.left = sel.goalColumn;Ð     var target =
findPosV(this, pos, dir, unit);Ð     if (unit == "page") addToScrollPos(this,
0, charCoords(this, target, "div").top - pos.top);Ð
extendSelection(this.doc, target, target, dir);Ð     sel.goalColumn =
pos.left;Ð   }),Ð   toggleOverwrite: function() {Ð     if
(this.state.overwrite = !this.state.overwrite)Ð
this.display.cursor.className += " CodeMirror-overwrite";Ð     elseÐ
this.display.cursor.className = this.display.cursor.className.replace("
CodeMirror-overwrite", "");Ð   },Ð   hasFocus: function() { return
this.state.focused; },Ð   scrollTo: operation(null, function(x, y) {Ð
updateScrollPos(this, x, y);Ð   }),Ð   getScrollInfo: function() {Ð     var
scroller = this.display.scroller, co = scrollerCutOff;Ð     return {left:
scroller.scrollLeft, top: scroller.scrollTop,Ð              height:
scroller.scrollHeight - co, width: scroller.scrollWidth - co,Ð
clientHeight: scroller.clientHeight - co, clientWidth: scroller.clientWidth -
co};Ð   },Ð   scrollIntoView: operation(null, function(pos, margin) {Ð     if
(typeof pos == "number") pos = Pos(pos, 0);Ð     if (!margin) margin = 0;Ð
      var coords = pos;Ð     if (!pos || pos.line != null) {Ð
this.curOp.scrollToPos = pos ? clipPos(this.doc, pos) : this.doc.sel.head;Ð
        this.curOp.scrollToPosMargin = margin;Ð       coords =
cursorCoords(this, this.curOp.scrollToPos);Ð     }Ð     var sPos =
calculateScrollPos(this, coords.left, coords.top - margin, coords.right,
coords.bottom + margin);Ð     updateScrollPos(this, sPos.scrollLeft,
sPos.scrollTop);Ð   }),Ð   setSize: function(width, height) {Ð     function
interpret(val) {Ð       return typeof val == "number" || /^\d+
$/.test(String(val)) ? val + "px" : val;Ð     }Ð     if (width != null)
this.display.wrapper.style.width = interpret(width);Ð     if (height != null)
this.display.wrapper.style.height = interpret(height);Ð     this.refresh();Ð
    },Ð   on: function(type, f) {on(this, type, f);},Ð   off: function(type,
f) {off(this, type, f);},Ð   operation: function(f){return runInOp(this, f);},Ð
    refresh: operation(null, function() {Ð     clearCaches(this);Ð
updateScrollPos(this, this.doc.scrollLeft, this.doc.scrollTop);Ð
regChange(this);Ð   }),Ð   swapDoc: operation(null, function(doc) {Ð     var
old = this.doc;Ð     old.cm = null;Ð     attachDoc(this, doc);Ð
clearCaches(this);Ð     resetInput(this, true);Ð     updateScrollPos(this,
doc.scrollLeft, doc.scrollTop);Ð     return old;Ð   }),Ð   getInputField:
function(){return this.display.input;},Ð   getWrapperElement: function()
{return this.display.wrapper;},Ð   getScrollerElement: function(){return
this.display.scroller;},Ð   getGutterElement: function(){return
this.display.gutters;}Ð };Ð // OPTION DEFAULTSÐ var optionHandlers =
CodeMirror.optionHandlers = {};Ð
```

```
                                Ð // The default configuration options.Ð var
defaults = CodeMirror.defaults = {};Ð function option(name, deflt, handle,
notOnInit) {Ð   CodeMirror.defaults[name] = deflt;Ð   if (handle)
optionHandlers[name] =Ð     notOnInit ? function(cm, val, old) {if (old !=
Init) handle(cm, val, old);} : handle;Ð }Ð var Init = CodeMirror.Init =
{toString: function(){return "CodeMirror.Init";}};Ð // These two are, on
init, called from the constructor because theyÐ // have to be initialized
before the editor can start at all.Ð option("value", "", function(cm, val) {Ð
    cm.setValue(val);Ð }, true);Ð option("mode", null, function(cm, val) {Ð
cm.doc.modeOption = val;Ð   loadMode(cm);Ð }, true);Ð option("indentUnit", 2,
loadMode, true);Ð option("indentWithTabs", false);Ð option("smartIndent",
true);Ð option("tabSize", 4, function(cm) {Ð   loadMode(cm);Ð
clearCaches(cm);Ð   regChange(cm);Ð }, true);Ð option("electricChars", true);Ð
  option("rtlMoveVisually", !windows);Ð option("theme", "default",
function(cm) {Ð   themeChanged(cm);Ð   guttersChanged(cm);Ð }, true);Ð
option("keyMap", "default", keyMapChanged);Ð option("extraKeys", null);Ð
option("onKeyEvent", null);Ð option("onDragEvent", null);Ð
option("lineWrapping", false, wrappingChanged, true);Ð option("gutters", [],
function(cm) {Ð   setGuttersForLineNumbers(cm.options);Ð   guttersChanged(cm);Ð
  }, true);Ð option("fixedGutter", true, function(cm, val) {Ð
cm.display.gutters.style.left = val ? compensateForHScroll(cm.display) +
"px" : "0";Ð   cm.refresh();Ð }, true);Ð option("lineNumbers", false,
function(cm) {Ð   setGuttersForLineNumbers(cm.options);Ð   guttersChanged(cm);Ð
  }, true);Ð option("firstLineNumber", 1, guttersChanged, true);Ð
option("lineNumberFormatter", function(integer) {return integer;},
guttersChanged, true);Ð option("showCursorWhenSelecting", false,
updateSelection, true);Ð option("readOnly", false, function(cm, val) {Ð   if
(val == "nocursor") {onBlur(cm); cm.display.input.blur();}Ð   else if (!val)
resetInput(cm, true);Ð });Ð option("dragDrop", true);Ð
option("cursorBlinkRate", 530);Ð option("cursorHeight", 1);Ð
option("workTime", 100);Ð option("workDelay", 100);Ð option("flattenSpans",
true);Ð option("pollInterval", 100);Ð option("undoDepth", 40, function(cm,
val){cm.doc.history.undoDepth = val;});Ð option("historyEventDelay", 500);Ð
option("viewportMargin", 10, function(cm){cm.refresh();}, true);Ð
option("maxHighlightLength", 10000, function(cm){loadMode(cm);
cm.refresh();}, true);Ð option("moveInputWithCursor", true, function(cm, val)
{Ð   if (!val) cm.display.inputDiv.style.top = cm.display.inputDiv.style.left
= 0;Ð });Ð option("tabindex", null, function(cm, val) {Ð
cm.display.input.tabIndex = val || "";Ð });Ð option("autofocus", null);Ð //
MODE DEFINITION AND QUERYINGÐ // Known modes, by name and by MIMEÐ var modes
= CodeMirror.modes = {}, mimeModes = CodeMirror.mimeModes = {};Ð
CodeMirror.defineMode = function(name, mode) {Ð   if (!
CodeMirror.defaults.mode && name != "null") CodeMirror.defaults.mode = name;Ð
    if (arguments.length > 2) {Ð     mode.dependencies = [];Ð     for (var i
= 2; i < arguments.length; ++i) mode.dependencies.push(arguments[i]);Ð   }Ð
modes[name] = mode;Ð };Ð CodeMirror.defineMIME = function(mime, spec) {Ð
mimeModes[mime] = spec;Ð };Ð CodeMirror.resolveMode = function(spec) {Ð   if
(typeof spec == "string" && mimeModes.hasOwnProperty(spec))Ð     spec =
mimeModes[spec];Ð   else if (typeof spec == "string" && /^[\w\-]+\/[\w\-]+\
+xml$/.test(spec))Ð     return CodeMirror.resolveMode("application/xml");Ð
if (typeof spec == "string") return {name: spec};Ð   else return spec ||
{name: "null"};Ð };Ð CodeMirror.getMode = function(options, spec) {Ð   spec =
CodeMirror.resolveMode(spec);Ð   var mfactory = modes[spec.name];Ð   if (!
mfactory) return CodeMirror.getMode(options, "text/plain");Ð   var modeObj =
mfactory(options, spec);Ð   if (modeExtensions.hasOwnProperty(spec.name)) {Ð
      var exts = modeExtensions[spec.name];Ð     for (var prop in exts) {Ð
        if (!exts.hasOwnProperty(prop)) continue;Ð       if
(modeObj.hasOwnProperty(prop)) modeObj["_" + prop] = modeObj[prop];Ð
modeObj[prop] = exts[prop];Ð     }Ð   }Ð   modeObj.name = spec.name;Ð
return modeObj;Ð
```

```
                 };Ð CodeMirror.defineMode("null", function() {Ð   return
{token: function(stream) {stream.skipToEnd();}};Ð });Ð
CodeMirror.defineMIME("text/plain", "null");Ð var modeExtensions =
CodeMirror.modeExtensions = {};Ð CodeMirror.extendMode = function(mode,
properties) {Ð   var exts = modeExtensions.hasOwnProperty(mode) ?
modeExtensions[mode] : (modeExtensions[mode] = {});Ð   copyObj(properties,
exts);Ð };Ð // EXTENSIONSÐ CodeMirror.defineExtension = function(name, func) {Ð
    CodeMirror.prototype[name] = func;Ð };Ð CodeMirror.defineDocExtension =
function(name, func) {Ð   Doc.prototype[name] = func;Ð };Ð
CodeMirror.defineOption = option;Ð var initHooks = [];Ð
CodeMirror.defineInitHook = function(f) {initHooks.push(f);};Ð // MODE STATE
HANDLINGÐ // Utility functions for working with state. Exported because modesÐ
  // sometimes need to do this.Ð function copyState(mode, state) {Ð   if
(state === true) return state;Ð   if (mode.copyState) return
mode.copyState(state);Ð   var nstate = {};Ð   for (var n in state) {Ð     var
val = state[n];Ð     if (val instanceof Array) val = val.concat([]);Ð
nstate[n] = val;Ð   }Ð   return nstate;Ð }Ð CodeMirror.copyState = copyState;Ð
  function startState(mode, a1, a2) {Ð   return mode.startState ?
mode.startState(a1, a2) : true;Ð }Ð CodeMirror.startState = startState;Ð
CodeMirror.innerMode = function(mode, state) {Ð   while (mode.innerMode) {Ð
      var info = mode.innerMode(state);Ð     state = info.state;Ð     mode =
info.mode;Ð   }Ð   return info || {mode: mode, state: state};Ð };Ð //
STANDARD COMMANDSÐ var commands = CodeMirror.commands = {Ð   selectAll:
function(cm) {cm.setSelection(Pos(cm.firstLine(), 0), Pos(cm.lastLine()));},Ð
    killLine: function(cm) {Ð     var from = cm.getCursor(true), to =
cm.getCursor(false), sel = !posEq(from, to);Ð     if (!sel &&
cm.getLine(from.line).length == from.ch)Ð       cm.replaceRange("", from,
Pos(from.line + 1, 0), "+delete");Ð     else cm.replaceRange("", from, sel ?
to : Pos(from.line), "+delete");Ð   },Ð   deleteLine: function(cm) {Ð     var
l = cm.getCursor().line;Ð     cm.replaceRange("", Pos(l, 0), Pos(l),
"+delete");Ð   },Ð   undo: function(cm) {cm.undo();},Ð   redo: function(cm)
{cm.redo();},Ð   goDocStart: function(cm)
{cm.extendSelection(Pos(cm.firstLine(), 0));},Ð   goDocEnd: function(cm)
{cm.extendSelection(Pos(cm.lastLine()));},Ð   goLineStart: function(cm) {Ð
      cm.extendSelection(lineStart(cm, cm.getCursor().line));Ð   },Ð
goLineStartSmart: function(cm) {Ð     var cur = cm.getCursor(), start =
lineStart(cm, cur.line);Ð     var line = cm.getLineHandle(start.line);Ð
var order = getOrder(line);Ð     if (!order || order[0].level == 0) {Ð
var firstNonWS = Math.max(0, line.text.search(/\S/));Ð       var inWS =
cur.line == start.line && cur.ch <= firstNonWS && cur.ch;Ð
cm.extendSelection(Pos(start.line, inWS ? 0 : firstNonWS));Ð     } else
cm.extendSelection(start);Ð   },Ð   goLineEnd: function(cm) {Ð
cm.extendSelection(lineEnd(cm, cm.getCursor().line));Ð   },Ð   goLineRight:
function(cm) {Ð     var top = cm.charCoords(cm.getCursor(), "div").top + 5;Ð
      cm.extendSelection(cm.coordsChar({left: cm.display.lineDiv.offsetWidth
+ 100, top: top}, "div"));Ð   },Ð   goLineLeft: function(cm) {Ð     var top =
cm.charCoords(cm.getCursor(), "div").top + 5;Ð
cm.extendSelection(cm.coordsChar({left: 0, top: top}, "div"));Ð   },Ð
goLineUp: function(cm) {cm.moveV(-1, "line");},Ð   goLineDown: function(cm)
{cm.moveV(1, "line");},Ð   goPageUp: function(cm) {cm.moveV(-1, "page");},Ð
goPageDown: function(cm) {cm.moveV(1, "page");},Ð   goCharLeft: function(cm)
{cm.moveH(-1, "char");},Ð   goCharRight: function(cm) {cm.moveH(1, "char");},Ð
    goColumnLeft: function(cm) {cm.moveH(-1, "column");},Ð   goColumnRight:
function(cm) {cm.moveH(1, "column");},Ð   goWordLeft: function(cm)
{cm.moveH(-1, "word");},Ð   goGroupRight: function(cm) {cm.moveH(1,
"group");},Ð   goGroupLeft: function(cm) {cm.moveH(-1, "group");},Ð
goWordRight: function(cm) {cm.moveH(1, "word");},Ð   delCharBefore:
function(cm) {cm.deleteH(-1, "char");},Ð   delCharAfter: function(cm)
{cm.deleteH(1, "char");},Ð   delWordBefore: function(cm) {cm.deleteH(-1,
"word");},Ð
```

```
              delWordAfter: function(cm) {cm.deleteH(1, "word");},Ð
delGroupBefore: function(cm) {cm.deleteH(-1, "group");},Ð   delGroupAfter:
function(cm) {cm.deleteH(1, "group");},Ð   indentAuto: function(cm)
{cm.indentSelection("smart");},Ð   indentMore: function(cm)
{cm.indentSelection("add");},Ð   indentLess: function(cm)
{cm.indentSelection("subtract");},Ð   insertTab: function(cm)
{cm.replaceSelection("\t", "end", "+input");},Ð   defaultTab: function(cm) {Ð
      if (cm.somethingSelected()) cm.indentSelection("add");Ð     else
cm.replaceSelection("\t", "end", "+input");Ð   },Ð   transposeChars:
function(cm) {Ð     var cur = cm.getCursor(), line = cm.getLine(cur.line);Ð
      if (cur.ch > 0 && cur.ch < line.length - 1)Ð
cm.replaceRange(line.charAt(cur.ch) + line.charAt(cur.ch - 1),Ð
                        Pos(cur.line, cur.ch - 1), Pos(cur.line, cur.ch + 1));Ð
    },Ð   newlineAndIndent: function(cm) {Ð     operation(cm, function() {Ð
        cm.replaceSelection("\n", "end", "+input");Ð
cm.indentLine(cm.getCursor().line, null, true);Ð     })();Ð   },Ð
toggleOverwrite: function(cm) {cm.toggleOverwrite();}Ð };Ð // STANDARD KEYMAPSÐ
  var keyMap = CodeMirror.keyMap = {};Ð keyMap.basic = {Ð   "Left":
"goCharLeft", "Right": "goCharRight", "Up": "goLineUp", "Down": "goLineDown",Ð
    "End": "goLineEnd", "Home": "goLineStartSmart", "PageUp": "goPageUp",
"PageDown": "goPageDown",Ð   "Delete": "delCharAfter", "Backspace":
"delCharBefore", "Tab": "defaultTab", "Shift-Tab": "indentAuto",Ð   "Enter":
"newlineAndIndent", "Insert": "toggleOverwrite"Ð };Ð // Note that the save
and find-related commands aren't defined byÐ // default. Unknown commands are
simply ignored.Ð keyMap.pcDefault = {Ð   "Ctrl-A": "selectAll", "Ctrl-D":
"deleteLine", "Ctrl-Z": "undo", "Shift-Ctrl-Z": "redo", "Ctrl-Y": "redo",Ð
"Ctrl-Home": "goDocStart", "Alt-Up": "goDocStart", "Ctrl-End": "goDocEnd",
"Ctrl-Down": "goDocEnd",Ð   "Ctrl-Left": "goGroupLeft", "Ctrl-Right":
"goGroupRight", "Alt-Left": "goLineStart", "Alt-Right": "goLineEnd",Ð   "Ctrl-
Backspace": "delGroupBefore", "Ctrl-Delete": "delGroupAfter", "Ctrl-S":
"save", "Ctrl-F": "find",Ð   "Ctrl-G": "findNext", "Shift-Ctrl-G":
"findPrev", "Shift-Ctrl-F": "replace", "Shift-Ctrl-R": "replaceAll",Ð   "Ctrl-
[": "indentLess", "Ctrl-]": "indentMore",Ð   fallthrough: "basic"Ð };Ð
keyMap.macDefault = {Ð   "Cmd-A": "selectAll", "Cmd-D": "deleteLine", "Cmd-
Z": "undo", "Shift-Cmd-Z": "redo", "Cmd-Y": "redo",Ð   "Cmd-Up":
"goDocStart", "Cmd-End": "goDocEnd", "Cmd-Down": "goDocEnd", "Alt-Left":
"goGroupLeft",Ð   "Alt-Right": "goGroupRight", "Cmd-Left": "goLineStart",
"Cmd-Right": "goLineEnd", "Alt-Backspace": "delGroupBefore",Ð   "Ctrl-Alt-
Backspace": "delGroupAfter", "Alt-Delete": "delGroupAfter", "Cmd-S": "save",
"Cmd-F": "find",Ð   "Cmd-G": "findNext", "Shift-Cmd-G": "findPrev", "Cmd-Alt-
F": "replace", "Shift-Cmd-Alt-F": "replaceAll",Ð   "Cmd-[": "indentLess",
"Cmd-]": "indentMore",Ð   fallthrough: ["basic", "emacsy"]Ð };Ð
keyMap["default"] = mac ? keyMap.macDefault : keyMap.pcDefault;Ð
keyMap.emacsy = {Ð   "Ctrl-F": "goCharRight", "Ctrl-B": "goCharLeft", "Ctrl-
P": "goLineUp", "Ctrl-N": "goLineDown",Ð   "Alt-F": "goWordRight", "Alt-B":
"goWordLeft", "Ctrl-A": "goLineStart", "Ctrl-E": "goLineEnd",Ð   "Ctrl-V":
"goPageDown", "Shift-Ctrl-V": "goPageUp", "Ctrl-D": "delCharAfter", "Ctrl-H":
"delCharBefore",Ð   "Alt-D": "delWordAfter", "Alt-Backspace":
"delWordBefore", "Ctrl-K": "killLine", "Ctrl-T": "transposeChars"Ð };Ð //
KEYMAP DISPATCHÐ function getKeyMap(val) {Ð   if (typeof val == "string")
return keyMap[val];Ð   else return val;Ð }Ð function lookupKey(name, maps,
handle) {Ð   function lookup(map) {Ð     map = getKeyMap(map);Ð     var found
= map[name];Ð     if (found === false) return "stop";Ð     if (found != null
&& handle(found)) return true;Ð     if (map.nofallthrough) return "stop";Ð
      var fallthrough = map.fallthrough;Ð     if (fallthrough == null) return
false;Ð     if (Object.prototype.toString.call(fallthrough) != "[object
Array]")Ð       return lookup(fallthrough);Ð     for (var i = 0, e =
fallthrough.length; i < e; ++i) {Ð       var done = lookup(fallthrough[i]);Ð
        if (done) return done;Ð     }Ð     return false;Ð   }Ð   for (var i =
0; i < maps.length; ++i) {Ð
```

```
                                var done = lookup(maps[i]);Ð     if (done)
return done;Ð   }Ð }Ð function isModifierKey(event) {Ð   var name =
keyNames[event.keyCode];Ð   return name == "Ctrl" || name == "Alt" || name ==
"Shift" || name == "Mod";Ð }Ð function keyName(event, noShift) {Ð   if (opera
&& event.keyCode == 34 && event["char"]) return false;Ð   var name =
keyNames[event.keyCode];Ð   if (name == null || event.altGraphKey) return
false;Ð   if (event.altKey) name = "Alt-" + name;Ð   if (flipCtrlCmd ?
event.metaKey : event.ctrlKey) name = "Ctrl-" + name;Ð   if (flipCtrlCmd ?
event.ctrlKey : event.metaKey) name = "Cmd-" + name;Ð   if (!noShift &&
event.shiftKey) name = "Shift-" + name;Ð   return name;Ð }Ð
CodeMirror.lookupKey = lookupKey;Ð CodeMirror.isModifierKey = isModifierKey;Ð
CodeMirror.keyName = keyName;Ð // FROMTEXTAREAÐ CodeMirror.fromTextArea =
function(textarea, options) {Ð   if (!options) options = {};Ð   options.value
= textarea.value;Ð   if (!options.tabindex && textarea.tabindex)Ð
options.tabindex = textarea.tabindex;Ð   if (!options.placeholder &&
textarea.placeholder)Ð     options.placeholder = textarea.placeholder;Ð   //
Set autofocus to true if this textarea is focused, or if it hasÐ   //
autofocus and no other element is focused.Ð   if (options.autofocus == null) {Ð
      var hasFocus = document.body;Ð     // doc.activeElement occasionally
throws on IEÐ     try { hasFocus = document.activeElement; } catch(e) {}Ð
options.autofocus = hasFocus == textarea ||Ð
textarea.getAttribute("autofocus") != null && hasFocus == document.body;Ð   }Ð
    function save() {textarea.value = cm.getValue();}Ð   if (textarea.form) {Ð
      on(textarea.form, "submit", save);Ð     // Deplorable hack to make the
submit method do the right thing.Ð     if (!options.leaveSubmitMethodAlone) {Ð
        var form = textarea.form, realSubmit = form.submit;Ð       try {Ð
          var wrappedSubmit = form.submit = function() {Ð           save();Ð
            form.submit = realSubmit;Ð           form.submit();Ð
form.submit = wrappedSubmit;Ð         };Ð       } catch(e) {}Ð     }Ð   }Ð
textarea.style.display = "none";Ð   var cm = CodeMirror(function(node) {Ð
textarea.parentNode.insertBefore(node, textarea.nextSibling);Ð   }, options);Ð
    cm.save = save;Ð   cm.getTextArea = function() { return textarea; };Ð
cm.toTextArea = function() {Ð     save();Ð
textarea.parentNode.removeChild(cm.getWrapperElement());Ð
textarea.style.display = "";Ð     if (textarea.form) {Ð
off(textarea.form, "submit", save);Ð       if (typeof textarea.form.submit ==
"function")Ð         textarea.form.submit = realSubmit;Ð     }Ð   };Ð
return cm;Ð };Ð // STRING STREAMÐ // Fed to the mode parsers, provides helper
functions to makeÐ // parsers more succinct.Ð // The character stream used by
a mode's parser.Ð function StringStream(string, tabSize) {Ð   this.pos =
this.start = 0;Ð   this.string = string;Ð   this.tabSize = tabSize || 8;Ð
this.lastColumnPos = this.lastColumnValue = 0;Ð }Ð StringStream.prototype = {Ð
    eol: function() {return this.pos >= this.string.length;},Ð   sol:
function() {return this.pos == 0;},Ð   peek: function() {return
this.string.charAt(this.pos) || undefined;},Ð   next: function() {Ð     if
(this.pos < this.string.length)Ð       return this.string.charAt(this.pos++);Ð
    },Ð   eat: function(match) {Ð     var ch = this.string.charAt(this.pos);Ð
      if (typeof match == "string") var ok = ch == match;Ð     else var ok =
ch && (match.test ? match.test(ch) : match(ch));Ð     if (ok) {++this.pos;
return ch;}Ð   },Ð   eatWhile: function(match) {Ð     var start = this.pos;Ð
      while (this.eat(match)){}Ð     return this.pos > start;Ð   },Ð
eatSpace: function() {Ð     var start = this.pos;Ð     while (/
[\s\u00a0]/.test(this.string.charAt(this.pos))) ++this.pos;Ð     return
this.pos > start;Ð   },Ð   skipToEnd: function() {this.pos =
this.string.length;},Ð   skipTo: function(ch) {Ð     var found =
this.string.indexOf(ch, this.pos);Ð     if (found > -1) {this.pos = found;
return true;}Ð   },Ð   backUp: function(n) {this.pos -= n;},Ð   column:
function() {Ð     if (this.lastColumnPos < this.start) {Ð
this.lastColumnValue = countColumn(this.string, this.start, this.tabSize,
this.lastColumnPos, this.lastColumnValue);Ð
```

```
                                                    this.lastColumnPos =
this.start;Ð     }Ð     return this.lastColumnValue;Ð   },Ð   indentation:
function() {return countColumn(this.string, null, this.tabSize);},Ð   match:
function(pattern, consume, caseInsensitive) {Ð     if (typeof pattern ==
"string") {Ð       var cased = function(str) {return caseInsensitive ?
str.toLowerCase() : str;};Ð       var substr = this.string.substr(this.pos,
pattern.length);Ð       if (cased(substr) == cased(pattern)) {Ð         if
(consume !== false) this.pos += pattern.length;Ð         return true;Ð       }Ð
      } else {Ð       var match = this.string.slice(this.pos).match(pattern);Ð
        if (match && match.index > 0) return null;Ð       if (match &&
consume !== false) this.pos += match[0].length;Ð       return match;Ð     }Ð
    },Ð   current: function(){return this.string.slice(this.start, this.pos);}Ð
  };Ð CodeMirror.StringStream = StringStream;Ð // TEXTMARKERSÐ function
TextMarker(doc, type) {Ð   this.lines = [];Ð   this.type = type;Ð   this.doc
= doc;Ð }Ð CodeMirror.TextMarker = TextMarker;Ð TextMarker.prototype.clear =
function() {Ð   if (this.explicitlyCleared) return;Ð   var cm = this.doc.cm,
withOp = cm && !cm.curOp;Ð   if (withOp) startOperation(cm);Ð   var min =
null, max = null;Ð   for (var i = 0; i < this.lines.length; ++i) {Ð     var
line = this.lines[i];Ð     var span = getMarkedSpanFor(line.markedSpans,
this);Ð     if (span.to != null) max = lineNo(line);Ð     line.markedSpans =
removeMarkedSpan(line.markedSpans, span);Ð     if (span.from != null)Ð
min = lineNo(line);Ð     else if (this.collapsed && !lineIsHidden(this.doc,
line) && cm)Ð       updateLineHeight(line, textHeight(cm.display));Ð   }Ð
if (cm && this.collapsed && !cm.options.lineWrapping) for (var i = 0; i <
this.lines.length; ++i) {Ð     var visual = visualLine(cm.doc,
this.lines[i]), len = lineLength(cm.doc, visual);Ð     if (len >
cm.display.maxLineLength) {Ð       cm.display.maxLine = visual;Ð
cm.display.maxLineLength = len;Ð       cm.display.maxLineChanged = true;Ð
      }Ð   }Ð   if (min != null && cm) regChange(cm, min, max + 1);Ð
this.lines.length = 0;Ð   this.explicitlyCleared = true;Ð   if
(this.collapsed && this.doc.cantEdit) {Ð     this.doc.cantEdit = false;Ð
if (cm) reCheckSelection(cm);Ð   }Ð   if (withOp) endOperation(cm);Ð
signalLater(this, "clear");Ð };Ð TextMarker.prototype.find = function() {Ð
var from, to;Ð   for (var i = 0; i < this.lines.length; ++i) {Ð     var line
= this.lines[i];Ð     var span = getMarkedSpanFor(line.markedSpans, this);Ð
      if (span.from != null || span.to != null) {Ð       var found =
lineNo(line);Ð       if (span.from != null) from = Pos(found, span.from);Ð
        if (span.to != null) to = Pos(found, span.to);Ð     }Ð   }Ð   if
(this.type == "bookmark") return from;Ð   return from && {from: from, to: to};Ð
  };Ð TextMarker.prototype.getOptions = function(copyWidget) {Ð   var repl =
this.replacedWith;Ð   return {className: this.className,Ð
inclusiveLeft: this.inclusiveLeft, inclusiveRight: this.inclusiveRight,Ð
            atomic: this.atomic,Ð           collapsed: this.collapsed,Ð
            replacedWith: copyWidget ? repl && repl.cloneNode(true) : repl,Ð
            readOnly: this.readOnly,Ð           startStyle: this.startStyle,
endStyle: this.endStyle};Ð };Ð TextMarker.prototype.attachLine =
function(line) {Ð   if (!this.lines.length && this.doc.cm) {Ð     var op =
this.doc.cm.curOp;Ð     if (!op.maybeHiddenMarkers ||
indexOf(op.maybeHiddenMarkers, this) == -1)Ð       (op.maybeUnhiddenMarkers
|| (op.maybeUnhiddenMarkers = [])).push(this);Ð   }Ð   this.lines.push(line);Ð
  };Ð TextMarker.prototype.detachLine = function(line) {Ð
this.lines.splice(indexOf(this.lines, line), 1);Ð   if (!this.lines.length &&
this.doc.cm) {Ð     var op = this.doc.cm.curOp;Ð     (op.maybeHiddenMarkers
|| (op.maybeHiddenMarkers = [])).push(this);Ð   }Ð };Ð function markText(doc,
from, to, options, type) {Ð   if (options && options.shared) return
markTextShared(doc, from, to, options, type);Ð   if (doc.cm && !doc.cm.curOp)
return operation(doc.cm, markText)(doc, from, to, options, type);Ð   var
marker = new TextMarker(doc, type);Ð   if (type == "range" && !posLess(from,
to)) return marker;Ð   if (options) copyObj(options, marker);Ð   if
(marker.replacedWith) {Ð
```

```
                                marker.collapsed = true;Ð
marker.replacedWith = elt("span", [marker.replacedWith], "CodeMirror-widget");Ð
    }Ð   if (marker.collapsed) sawCollapsedSpans = true;Ð   if
(marker.addToHistory)Ð     addToHistory(doc, {from: from, to: to, origin:
"markText"},Ð                   {head: doc.sel.head, anchor: doc.sel.anchor},
NaN);Ð   var curLine = from.line, size = 0, collapsedAtStart, collapsedAtEnd,
cm = doc.cm, updateMaxLine;Ð   doc.iter(curLine, to.line + 1, function(line) {Ð
      if (cm && marker.collapsed && !cm.options.lineWrapping &&
visualLine(doc, line) == cm.display.maxLine)Ð       updateMaxLine = true;Ð
      var span = {from: null, to: null, marker: marker};Ð     size +=
line.text.length;Ð     if (curLine == from.line) {span.from = from.ch; size -
= from.ch;}Ð     if (curLine == to.line) {span.to = to.ch; size -=
line.text.length - to.ch;}Ð     if (marker.collapsed) {Ð       if (curLine ==
to.line) collapsedAtEnd = collapsedSpanAt(line, to.ch);Ð       if (curLine ==
from.line) collapsedAtStart = collapsedSpanAt(line, from.ch);Ð       else
updateLineHeight(line, 0);Ð     }Ð     addMarkedSpan(line, span);Ð     +
+curLine;Ð   });Ð   if (marker.collapsed) doc.iter(from.line, to.line + 1,
function(line) {Ð     if (lineIsHidden(doc, line)) updateLineHeight(line, 0);Ð
    });Ð   if (marker.clearOnEnter) on(marker, "beforeCursorEnter",
function() { marker.clear(); });Ð   if (marker.readOnly) {Ð
sawReadOnlySpans = true;Ð     if (doc.history.done.length ||
doc.history.undone.length)Ð       doc.clearHistory();Ð   }Ð   if
(marker.collapsed) {Ð     if (collapsedAtStart != collapsedAtEnd)Ð
throw new Error("Inserting collapsed marker overlapping an existing one");Ð
      marker.size = size;Ð     marker.atomic = true;Ð   }Ð   if (cm) {Ð
if (updateMaxLine) cm.curOp.updateMaxLine = true;Ð     if (marker.className
|| marker.startStyle || marker.endStyle || marker.collapsed)Ð
regChange(cm, from.line, to.line + 1);Ð     if (marker.atomic)
reCheckSelection(cm);Ð   }Ð   return marker;Ð }Ð // SHARED TEXTMARKERSÐ
function SharedTextMarker(markers, primary) {Ð   this.markers = markers;Ð
this.primary = primary;Ð   for (var i = 0, me = this; i < markers.length; +
+i) {Ð     markers[i].parent = this;Ð     on(markers[i], "clear", function()
{me.clear();});Ð   }Ð }Ð CodeMirror.SharedTextMarker = SharedTextMarker;Ð
SharedTextMarker.prototype.clear = function() {Ð   if
(this.explicitlyCleared) return;Ð   this.explicitlyCleared = true;Ð   for
(var i = 0; i < this.markers.length; ++i)Ð     this.markers[i].clear();Ð
signalLater(this, "clear");Ð };Ð SharedTextMarker.prototype.find = function()
{Ð   return this.primary.find();Ð };Ð SharedTextMarker.prototype.getOptions =
function(copyWidget) {Ð   var inner = this.primary.getOptions(copyWidget);Ð
inner.shared = true;Ð   return inner;Ð };Ð function markTextShared(doc, from,
to, options, type) {Ð   options = copyObj(options);Ð   options.shared = false;Ð
    var markers = [markText(doc, from, to, options, type)], primary =
markers[0];Ð   var widget = options.replacedWith;Ð   linkedDocs(doc,
function(doc) {Ð     if (widget) options.replacedWith =
widget.cloneNode(true);Ð     markers.push(markText(doc, clipPos(doc, from),
clipPos(doc, to), options, type));Ð     for (var i = 0; i <
doc.linked.length; ++i)Ð       if (doc.linked[i].isParent) return;Ð
primary = lst(markers);Ð   });Ð   return new SharedTextMarker(markers,
primary);Ð }Ð // TEXTMARKER SPANSÐ function getMarkedSpanFor(spans, marker) {Ð
    if (spans) for (var i = 0; i < spans.length; ++i) {Ð     var span =
spans[i];Ð     if (span.marker == marker) return span;Ð   }Ð }Ð function
removeMarkedSpan(spans, span) {Ð   for (var r, i = 0; i < spans.length; ++i)Ð
      if (spans[i] != span) (r || (r = [])).push(spans[i]);Ð   return r;Ð }Ð
function addMarkedSpan(line, span) {Ð   line.markedSpans = line.markedSpans ?
line.markedSpans.concat([span]) : [span];Ð   span.marker.attachLine(line);Ð }Ð
  function markedSpansBefore(old, startCh, isInsert) {Ð   if (old) for (var i
= 0, nw; i < old.length; ++i) {Ð     var span = old[i], marker = span.marker;Ð
      var startsBefore = span.from == null || (marker.inclusiveLeft ?
span.from <= startCh : span.from < startCh);Ð     if (startsBefore ||
marker.type == "bookmark" && span.from == startCh && (!isInsert || !
span.marker.insertLeft)) {Ð
```

```
                                    var endsAfter = span.to == null ||
(marker.inclusiveRight ? span.to >= startCh : span.to > startCh);Ð       (nw
|| (nw = [])).push({from: span.from,Ð                                  to:
endsAfter ? null : span.to,Ð                                marker: marker});Ð
      }Ð   }Ð   return nw;Ð }Ð function markedSpansAfter(old, endCh,
isInsert) {Ð   if (old) for (var i = 0, nw; i < old.length; ++i) {Ð     var
span = old[i], marker = span.marker;Ð     var endsAfter = span.to == null ||
(marker.inclusiveRight ? span.to >= endCh : span.to > endCh);Ð     if
(endsAfter || marker.type == "bookmark" && span.from == endCh && (!isInsert
|| span.marker.insertLeft)) {Ð       var startsBefore = span.from == null ||
(marker.inclusiveLeft ? span.from <= endCh : span.from < endCh);Ð       (nw
|| (nw = [])).push({from: startsBefore ? null : span.from - endCh,Ð
                                    to: span.to == null ? null : span.to - endCh,Ð
                                    marker: marker});Ð     }Ð   }Ð   return nw;Ð }Ð
  function stretchSpansOverChange(doc, change) {Ð   var oldFirst =
isLine(doc, change.from.line) && getLine(doc, change.from.line).markedSpans;Ð
    var oldLast = isLine(doc, change.to.line) && getLine(doc,
change.to.line).markedSpans;Ð   if (!oldFirst && !oldLast) return null;Ð
var startCh = change.from.ch, endCh = change.to.ch, isInsert =
posEq(change.from, change.to);Ð   // Get the spans that 'stick out' on both
sidesÐ   var first = markedSpansBefore(oldFirst, startCh, isInsert);Ð   var
last = markedSpansAfter(oldLast, endCh, isInsert);Ð   // Next, merge those
two endsÐ   var sameLine = change.text.length == 1, offset =
lst(change.text).length + (sameLine ? startCh : 0);Ð   if (first) {Ð     //
Fix up .to properties of firstÐ     for (var i = 0; i < first.length; ++i) {Ð
        var span = first[i];Ð       if (span.to == null) {Ð         var found
= getMarkedSpanFor(last, span.marker);Ð         if (!found) span.to = startCh;Ð
          else if (sameLine) span.to = found.to == null ? null : found.to +
offset;Ð       }Ð     }Ð   }Ð   if (last) {Ð     // Fix up .from in last (or
move them into first in case of sameLine)Ð     for (var i = 0; i <
last.length; ++i) {Ð       var span = last[i];Ð       if (span.to != null)
span.to += offset;Ð       if (span.from == null) {Ð         var found =
getMarkedSpanFor(first, span.marker);Ð         if (!found) {Ð
span.from = offset;Ð           if (sameLine) (first || (first =
[])).push(span);Ð         }Ð       } else {Ð         span.from += offset;Ð
          if (sameLine) (first || (first = [])).push(span);Ð       }Ð     }Ð
    }Ð   var newMarkers = [first];Ð   if (!sameLine) {Ð     // Fill gap with
whole-line-spansÐ     var gap = change.text.length - 2, gapMarkers;Ð     if
(gap > 0 && first)Ð       for (var i = 0; i < first.length; ++i)Ð         if
(first[i].to == null)Ð           (gapMarkers || (gapMarkers =
[])).push({from: null, to: null, marker: first[i].marker});Ð     for (var i =
0; i < gap; ++i)Ð       newMarkers.push(gapMarkers);Ð
newMarkers.push(last);Ð   }Ð   return newMarkers;Ð }Ð function
mergeOldSpans(doc, change) {Ð   var old = getOldSpans(doc, change);Ð   var
stretched = stretchSpansOverChange(doc, change);Ð   if (!old) return
stretched;Ð   if (!stretched) return old;Ð   for (var i = 0; i < old.length; +
+i) {Ð     var oldCur = old[i], stretchCur = stretched[i];Ð     if (oldCur &&
stretchCur) {Ð       spans: for (var j = 0; j < stretchCur.length; ++j) {Ð
          var span = stretchCur[j];Ð         for (var k = 0; k <
oldCur.length; ++k)Ð           if (oldCur[k].marker == span.marker) continue
spans;Ð         oldCur.push(span);Ð       }Ð     } else if (stretchCur) {Ð
        old[i] = stretchCur;Ð     }Ð   }Ð   return old;Ð }Ð function
removeReadOnlyRanges(doc, from, to) {Ð   var markers = null;Ð
doc.iter(from.line, to.line + 1, function(line) {Ð     if (line.markedSpans)
for (var i = 0; i < line.markedSpans.length; ++i) {Ð       var mark =
line.markedSpans[i].marker;Ð       if (mark.readOnly && (!markers ||
indexOf(markers, mark) == -1))Ð         (markers || (markers =
[])).push(mark);Ð     }Ð   });Ð   if (!markers) return null;Ð   var parts =
[{from: from, to: to}];Ð   for (var i = 0; i < markers.length; ++i) {Ð
var mk = markers[i], m = mk.find();Ð
```

```
                                        for (var j = 0; j < parts.length; +
+j) {Ð       var p = parts[j];Ð       if (posLess(p.to, m.from) ||
posLess(m.to, p.from)) continue;Ð       var newParts = [j, 1];Ð       if
(posLess(p.from, m.from) || !mk.inclusiveLeft && posEq(p.from, m.from))Ð
          newParts.push({from: p.from, to: m.from});Ð       if (posLess(m.to,
p.to) || !mk.inclusiveRight && posEq(p.to, m.to))Ð
newParts.push({from: m.to, to: p.to});Ð       parts.splice.apply(parts,
newParts);Ð       j += newParts.length - 1;Ð     }Ð   }Ð   return parts;Ð }Ð
function collapsedSpanAt(line, ch) {Ð   var sps = sawCollapsedSpans &&
line.markedSpans, found;Ð   if (sps) for (var sp, i = 0; i < sps.length; ++i)
{Ð     sp = sps[i];Ð     if (!sp.marker.collapsed) continue;Ð     if
((sp.from == null || sp.from < ch) &&Ð         (sp.to == null || sp.to > ch)
&&Ð         (!found || found.width < sp.marker.width))Ð       found =
sp.marker;Ð   }Ð   return found;Ð }Ð function collapsedSpanAtStart(line)
{ return collapsedSpanAt(line, -1); }Ð function collapsedSpanAtEnd(line)
{ return collapsedSpanAt(line, line.text.length + 1); }Ð function
visualLine(doc, line) {Ð   var merged;Ð   while (merged =
collapsedSpanAtStart(line))Ð     line = getLine(doc, merged.find().from.line);Ð
    return line;Ð }Ð function lineIsHidden(doc, line) {Ð   var sps =
sawCollapsedSpans && line.markedSpans;Ð   if (sps) for (var sp, i = 0; i <
sps.length; ++i) {Ð     sp = sps[i];Ð     if (!sp.marker.collapsed) continue;Ð
      if (sp.from == null) return true;Ð     if (sp.from == 0 &&
sp.marker.inclusiveLeft && lineIsHiddenInner(doc, line, sp))Ð       return
true;Ð   }Ð }Ð function lineIsHiddenInner(doc, line, span) {Ð   if (span.to
== null) {Ð     var end = span.marker.find().to, endLine = getLine(doc,
end.line);Ð     return lineIsHiddenInner(doc, endLine,
getMarkedSpanFor(endLine.markedSpans, span.marker));Ð   }Ð   if
(span.marker.inclusiveRight && span.to == line.text.length)Ð     return true;Ð
    for (var sp, i = 0; i < line.markedSpans.length; ++i) {Ð     sp =
line.markedSpans[i];Ð     if (sp.marker.collapsed && sp.from == span.to &&Ð
          (sp.marker.inclusiveLeft || span.marker.inclusiveRight) &&Ð
lineIsHiddenInner(doc, line, sp)) return true;Ð   }Ð }Ð function
detachMarkedSpans(line) {Ð   var spans = line.markedSpans;Ð   if (!spans)
return;Ð   for (var i = 0; i < spans.length; ++i)Ð
spans[i].marker.detachLine(line);Ð   line.markedSpans = null;Ð }Ð function
attachMarkedSpans(line, spans) {Ð   if (!spans) return;Ð   for (var i = 0; i
< spans.length; ++i)Ð     spans[i].marker.attachLine(line);Ð
line.markedSpans = spans;Ð }Ð // LINE WIDGETSÐ var LineWidget =
CodeMirror.LineWidget = function(cm, node, options) {Ð   for (var opt in
options) if (options.hasOwnProperty(opt))Ð     this[opt] = options[opt];Ð
this.cm = cm;Ð   this.node = node;Ð };Ð function widgetOperation(f) {Ð
return function() {Ð     var withOp = !this.cm.curOp;Ð     if (withOp)
startOperation(this.cm);Ð     try {var result = f.apply(this, arguments);}Ð
      finally {if (withOp) endOperation(this.cm);}Ð     return result;Ð   };Ð
  }Ð LineWidget.prototype.clear = widgetOperation(function() {Ð   var ws =
this.line.widgets, no = lineNo(this.line);Ð   if (no == null || !ws) return;Ð
    for (var i = 0; i < ws.length; ++i) if (ws[i] == this) ws.splice(i--, 1);Ð
    if (!ws.length) this.line.widgets = null;Ð   updateLineHeight(this.line,
Math.max(0, this.line.height - widgetHeight(this)));Ð   regChange(this.cm,
no, no + 1);Ð });Ð LineWidget.prototype.changed = widgetOperation(function() {Ð
    var oldH = this.height;Ð   this.height = null;Ð   var diff =
widgetHeight(this) - oldH;Ð   if (!diff) return;Ð
updateLineHeight(this.line, this.line.height + diff);Ð   var no =
lineNo(this.line);Ð   regChange(this.cm, no, no + 1);Ð });Ð function
widgetHeight(widget) {Ð   if (widget.height != null) return widget.height;Ð
if (!widget.node.parentNode || widget.node.parentNode.nodeType != 1)Ð
removeChildrenAndAdd(widget.cm.display.measure, elt("div", [widget.node],
null, "position: relative"));Ð   return widget.height =
widget.node.offsetHeight;Ð }Ð function addLineWidget(cm, handle, node,
options) {Ð
```

```
              var widget = new LineWidget(cm, node, options);Ð   if
(widget.noHScroll) cm.display.alignWidgets = true;Ð   changeLine(cm, handle,
function(line) {Ð     (line.widgets || (line.widgets = [])).push(widget);Ð
      widget.line = line;Ð     if (!lineIsHidden(cm.doc, line) ||
widget.showIfHidden) {Ð       var aboveVisible = heightAtLine(cm, line) <
cm.display.scroller.scrollTop;Ð       updateLineHeight(line, line.height +
widgetHeight(widget));Ð       if (aboveVisible) addToScrollPos(cm, 0,
widget.height);Ð     }Ð     return true;Ð   });Ð   return widget;Ð }Ð // LINE
DATA STRUCTUREÐ // Line objects. These hold state related to a line, includingÐ
  // highlighting info (the styles array).Ð function makeLine(text,
markedSpans, estimateHeight) {Ð   var line = {text: text};Ð
attachMarkedSpans(line, markedSpans);Ð   line.height = estimateHeight ?
estimateHeight(line) : 1;Ð   return line;Ð }Ð function updateLine(line, text,
markedSpans, estimateHeight) {Ð   line.text = text;Ð   if (line.stateAfter)
line.stateAfter = null;Ð   if (line.styles) line.styles = null;Ð   if
(line.order != null) line.order = null;Ð   detachMarkedSpans(line);Ð
attachMarkedSpans(line, markedSpans);Ð   var estHeight = estimateHeight ?
estimateHeight(line) : 1;Ð   if (estHeight != line.height)
updateLineHeight(line, estHeight);Ð }Ð function cleanUpLine(line) {Ð
line.parent = null;Ð   detachMarkedSpans(line);Ð }Ð // Run the given mode's
parser over a line, update the stylesÐ // array, which contains alternating
fragments of text and CSSÐ // classes.Ð function runMode(cm, text, mode,
state, f) {Ð   var flattenSpans = mode.flattenSpans;Ð   if (flattenSpans ==
null) flattenSpans = cm.options.flattenSpans;Ð   var curText = "", curStyle =
null;Ð   var stream = new StringStream(text, cm.options.tabSize), style;Ð
if (text == "" && mode.blankLine) mode.blankLine(state);Ð   while (!
stream.eol()) {Ð     if (stream.pos > cm.options.maxHighlightLength) {Ð
flattenSpans = false;Ð       // Webkit seems to refuse to render text nodes
longer than 57444 charactersÐ       stream.pos = Math.min(text.length,
stream.start + 50000);Ð       style = null;Ð     } else {Ð       style =
mode.token(stream, state);Ð     }Ð     var substr = stream.current();Ð
stream.start = stream.pos;Ð     if (!flattenSpans || curStyle != style) {Ð
        if (curText) f(curText, curStyle);Ð       curText = substr; curStyle
= style;Ð     } else curText = curText + substr;Ð   }Ð   if (curText)
f(curText, curStyle);Ð }Ð function highlightLine(cm, line, state) {Ð   // A
styles array always starts with a number identifying theÐ   // mode/overlays
that it is based on (for easy invalidation).Ð   var st = [cm.state.modeGen];Ð
    // Compute the base array of stylesÐ   runMode(cm, line.text,
cm.doc.mode, state, function(txt, style) {st.push(txt, style);});Ð   // Run
overlays, adjust style array.Ð   for (var o = 0; o <
cm.state.overlays.length; ++o) {Ð     var overlay = cm.state.overlays[o], i =
1;Ð     runMode(cm, line.text, overlay.mode, true, function(txt, style) {Ð
        var start = i, len = txt.length;Ð       // Ensure there's a token end
at the current position, and that i points at itÐ       while (len) {Ð
          var cur = st[i], len_ = cur.length;Ð         if (len_ <= len) {Ð
            len -= len_;Ð         } else {Ð           st.splice(i, 1,
cur.slice(0, len), st[i+1], cur.slice(len));Ð           len = 0;Ð         }Ð
          i += 2;Ð       }Ð       if (!style) return;Ð       if
(overlay.opaque) {Ð         st.splice(start, i - start, txt, style);Ð
i = start + 2;Ð       } else {Ð         for (; start < i; start += 2) {Ð
            var cur = st[start+1];Ð           st[start+1] = cur ? cur + " " +
style : style;Ð         }Ð       }Ð     });Ð   }Ð   return st;Ð }Ð function
getLineStyles(cm, line) {Ð   if (!line.styles || line.styles[0] !=
cm.state.modeGen)Ð     line.styles = highlightLine(cm, line, line.stateAfter
= getStateBefore(cm, lineNo(line)));Ð   return line.styles;Ð }Ð //
Lightweight form of highlight -- proceed over this line andÐ // update state,
but don't save a style array.Ð function processLine(cm, line, state) {Ð   var
mode = cm.doc.mode;Ð   var stream = new StringStream(line.text,
cm.options.tabSize);Ð   if (line.text == "" && mode.blankLine)
mode.blankLine(state);Ð
```

```
                            while (!stream.eol() && stream.pos <=
cm.options.maxHighlightLength) {Ð     mode.token(stream, state);Ð
stream.start = stream.pos;Ð   }Ð }Ð var styleToClassCache = {};Ð function
styleToClass(style) {Ð   if (!style) return null;Ð   return
styleToClassCache[style] ||Ð     (styleToClassCache[style] = "cm-" +
style.replace(/ +/g, " cm-"));Ð }Ð function lineContent(cm, realLine,
measure) {Ð   var merged, line = realLine, lineBefore, sawBefore, simple =
true;Ð   while (merged = collapsedSpanAtStart(line)) {Ð     simple = false;Ð
      line = getLine(cm.doc, merged.find().from.line);Ð     if (!lineBefore)
lineBefore = line;Ð   }Ð   var builder = {pre: elt("pre"), col: 0, pos: 0,
display: !measure,Ð                  measure: null, addedOne: false, cm: cm};Ð
    if (line.textClass) builder.pre.className = line.textClass;Ð   do {Ð
builder.measure = line == realLine && measure;Ð     builder.pos = 0;Ð
builder.addToken = builder.measure ? buildTokenMeasure : buildToken;Ð     if
((ie || webkit) && cm.getOption("lineWrapping"))Ð       builder.addToken =
buildTokenSplitSpaces(builder.addToken);Ð     if (measure && sawBefore &&
line != realLine && !builder.addedOne) {Ð       measure[0] =
builder.pre.appendChild(zeroWidthElement(cm.display.measure));Ð
builder.addedOne = true;Ð     }Ð     var next = insertLineContent(line,
builder, getLineStyles(cm, line));Ð     sawBefore = line == lineBefore;Ð
if (next) {Ð       line = getLine(cm.doc, next.to.line);Ð       simple =
false;Ð     }Ð   } while (next);Ð   if (measure && !builder.addedOne)Ð
measure[0] = builder.pre.appendChild(simple ? elt("span", "\u00a0") :
zeroWidthElement(cm.display.measure));Ð   if (!builder.pre.firstChild && !
lineIsHidden(cm.doc, realLine))Ð
builder.pre.appendChild(document.createTextNode("\u00a0"));Ð   var order;Ð
    // Work around problem with the reported dimensions of single-charÐ   //
direction spans on IE (issue #1129). See also the comment inÐ   //
cursorCoords.Ð   if (measure && ie && (order = getOrder(line))) {Ð     var l
= order.length - 1;Ð     if (order[l].from == order[l].to) --l;Ð     var last
= order[l], prev = order[l - 1];Ð     if (last.from + 1 == last.to && prev &&
last.level < prev.level) {Ð       var span = measure[builder.pos - 1];Ð
if (span) span.parentNode.insertBefore(span.measureRight =
zeroWidthElement(cm.display.measure),Ð
                                                span.nextSibling);Ð     }Ð   }Ð
    signal(cm, "renderLine", cm, realLine, builder.pre);Ð   return
builder.pre;Ð }Ð var tokenSpecialChars = /[\t\u0000-
\u0019\u00ad\u200b\u2028\u2029\uFEFF]/g;Ð function buildToken(builder, text,
style, startStyle, endStyle) {Ð   if (!text) return;Ð   if (!
tokenSpecialChars.test(text)) {Ð     builder.col += text.length;Ð     var
content = document.createTextNode(text);Ð   } else {Ð     var content =
document.createDocumentFragment(), pos = 0;Ð     while (true) {Ð
tokenSpecialChars.lastIndex = pos;Ð       var m =
tokenSpecialChars.exec(text);Ð       var skipped = m ? m.index - pos :
text.length - pos;Ð       if (skipped) {Ð
content.appendChild(document.createTextNode(text.slice(pos, pos + skipped)));Ð
          builder.col += skipped;Ð       }Ð       if (!m) break;Ð       pos
+= skipped + 1;Ð       if (m[0] == "\t") {Ð         var tabSize =
builder.cm.options.tabSize, tabWidth = tabSize - builder.col % tabSize;Ð
          content.appendChild(elt("span", spaceStr(tabWidth), "cm-tab"));Ð
          builder.col += tabWidth;Ð       } else {Ð         var token =
elt("span", "\u2022", "cm-invalidchar");Ð         token.title = "\\u" +
m[0].charCodeAt(0).toString(16);Ð         content.appendChild(token);Ð
          builder.col += 1;Ð       }Ð     }Ð   }Ð   if (style || startStyle
|| endStyle || builder.measure) {Ð     var fullStyle = style || "";Ð     if
(startStyle) fullStyle += startStyle;Ð     if (endStyle) fullStyle +=
endStyle;Ð     return builder.pre.appendChild(elt("span", [content],
fullStyle));Ð   }Ð   builder.pre.appendChild(content);Ð }Ð function
buildTokenMeasure(builder, text, style, startStyle, endStyle) {Ð   var
wrapping = builder.cm.options.lineWrapping;Ð
```

```
                                                for (var i = 0; i <
text.length; ++i) {Ð     var ch = text.charAt(i), start = i == 0;Ð     if (ch
>= "\ud800" && ch < "\udbff" && i < text.length - 1) {Ð       ch =
text.slice(i, i + 2);Ð       ++i;Ð     } else if (i && wrapping &&Ð
                  spanAffectsWrapping.test(text.slice(i - 1, i + 1))) {Ð
builder.pre.appendChild(elt("wbr"));Ð     }Ð     var span =
builder.measure[builder.pos] =Ð       buildToken(builder, ch, style,Ð
                    start && startStyle, i == text.length - 1 && endStyle);Ð
      // In IE single-space nodes wrap differently than spacesÐ     //
embedded in larger text nodes, except when set toÐ     // white-space: normal
(issue #1268).Ð     if (ie && wrapping && ch == " " && i && !/
\s/.test(text.charAt(i - 1)) &&Ð         i < text.length - 1 && !/
\s/.test(text.charAt(i + 1)))Ð       span.style.whiteSpace = "normal";Ð
builder.pos += ch.length;Ð   }Ð   if (text.length) builder.addedOne = true;Ð }Ð
  function buildTokenSplitSpaces(inner) {Ð   function split(old) {Ð     var
out = " ";Ð     for (var i = 0; i < old.length - 2; ++i) out += i % 2 ? " " :
"\u00a0";Ð     out += " ";Ð     return out;Ð   }Ð   return function(builder,
text, style, startStyle, endStyle) {Ð     return inner(builder,
text.replace(/ {3,}/, split), style, startStyle, endStyle);Ð   };Ð }Ð
function buildCollapsedSpan(builder, size, widget) {Ð   if (widget) {Ð     if
(!builder.display) widget = widget.cloneNode(true);Ð
builder.pre.appendChild(widget);Ð     if (builder.measure && size) {Ð
builder.measure[builder.pos] = widget;Ð       builder.addedOne = true;Ð     }Ð
    }Ð   builder.pos += size;Ð }Ð // Outputs a number of spans to make up a
line, taking highlightingÐ // and marked text into account.Ð function
insertLineContent(line, builder, styles) {Ð   var spans = line.markedSpans;Ð
    if (!spans) {Ð     for (var i = 1; i < styles.length; i+=2)Ð
builder.addToken(builder, styles[i], styleToClass(styles[i+1]));Ð     return;Ð
    }Ð   var allText = line.text, len = allText.length;Ð   var pos = 0, i =
1, text = "", style;Ð   var nextChange = 0, spanStyle, spanEndStyle,
spanStartStyle, collapsed;Ð   for (;;) {Ð     if (nextChange == pos) { //
Update current marker setÐ       spanStyle = spanEndStyle = spanStartStyle =
"";Ð       collapsed = null; nextChange = Infinity;Ð       var foundBookmark
= null;Ð       for (var j = 0; j < spans.length; ++j) {Ð         var sp =
spans[j], m = sp.marker;Ð         if (sp.from <= pos && (sp.to == null ||
sp.to > pos)) {Ð           if (sp.to != null && nextChange > sp.to)
{ nextChange = sp.to; spanEndStyle = ""; }Ð           if (m.className)
spanStyle += " " + m.className;Ð           if (m.startStyle && sp.from ==
pos) spanStartStyle += " " + m.startStyle;Ð           if (m.endStyle && sp.to
== nextChange) spanEndStyle += " " + m.endStyle;Ð           if (m.collapsed
&& (!collapsed || collapsed.marker.width < m.width))Ð             collapsed =
sp;Ð         } else if (sp.from > pos && nextChange > sp.from) {Ð
nextChange = sp.from;Ð         }Ð         if (m.type == "bookmark" && sp.from
== pos && m.replacedWith)Ð           foundBookmark = m.replacedWith;Ð       }Ð
        if (collapsed && (collapsed.from || 0) == pos) {Ð
buildCollapsedSpan(builder, (collapsed.to == null ? len : collapsed.to) - pos,Ð
                             collapsed.from != null &&
collapsed.marker.replacedWith);Ð         if (collapsed.to == null) return
collapsed.marker.find();Ð       }Ð       if (foundBookmark && !collapsed)
buildCollapsedSpan(builder, 0, foundBookmark);Ð     }Ð     if (pos >= len)
break;Ð     var upto = Math.min(len, nextChange);Ð     while (true) {Ð
if (text) {Ð         var end = pos + text.length;Ð         if (!collapsed) {Ð
            var tokenText = end > upto ? text.slice(0, upto - pos) : text;Ð
            builder.addToken(builder, tokenText, style ? style + spanStyle :
spanStyle,Ð                              spanStartStyle, pos + tokenText.length
== nextChange ? spanEndStyle : "");Ð         }Ð         if (end >= upto)
{text = text.slice(upto - pos); pos = upto; break;}Ð         pos = end;Ð
          spanStartStyle = "";Ð       }Ð       text = styles[i++]; style =
styleToClass(styles[i++]);Ð     }Ð   }Ð }Ð // DOCUMENT DATA STRUCTUREÐ
function updateDoc(doc, change, markedSpans, selAfter, estimateHeight) {Ð
```

```
function spansFor(n) {return markedSpans ? markedSpans[n] : null;}Ð
function update(line, text, spans) {Ð     updateLine(line, text, spans,
estimateHeight);Ð     signalLater(line, "change", line, change);Ð   }Ð   var
from = change.from, to = change.to, text = change.text;Ð   var firstLine =
getLine(doc, from.line), lastLine = getLine(doc, to.line);Ð   var lastText =
lst(text), lastSpans = spansFor(text.length - 1), nlines = to.line -
from.line;Ð   // First adjust the line structureÐ   if (from.ch == 0 && to.ch
== 0 && lastText == "") {Ð     // This is a whole-line replace. Treated
specially to makeÐ     // sure line objects move the way they are supposed to.Ð
      for (var i = 0, e = text.length - 1, added = []; i < e; ++i)Ð
added.push(makeLine(text[i], spansFor(i), estimateHeight));Ð
update(lastLine, lastLine.text, lastSpans);Ð     if (nlines)
doc.remove(from.line, nlines);Ð     if (added.length) doc.insert(from.line,
added);Ð   } else if (firstLine == lastLine) {Ð     if (text.length == 1) {Ð
        update(firstLine, firstLine.text.slice(0, from.ch) + lastText +
firstLine.text.slice(to.ch), lastSpans);Ð     } else {Ð       for (var added
= [], i = 1, e = text.length - 1; i < e; ++i)Ð
added.push(makeLine(text[i], spansFor(i), estimateHeight));Ð
added.push(makeLine(lastText + firstLine.text.slice(to.ch), lastSpans,
estimateHeight));Ð       update(firstLine, firstLine.text.slice(0, from.ch) +
text[0], spansFor(0));Ð       doc.insert(from.line + 1, added);Ð     }Ð   }
else if (text.length == 1) {Ð     update(firstLine, firstLine.text.slice(0,
from.ch) + text[0] + lastLine.text.slice(to.ch), spansFor(0));Ð
doc.remove(from.line + 1, nlines);Ð   } else {Ð     update(firstLine,
firstLine.text.slice(0, from.ch) + text[0], spansFor(0));Ð
update(lastLine, lastText + lastLine.text.slice(to.ch), lastSpans);Ð     for
(var i = 1, e = text.length - 1, added = []; i < e; ++i)Ð
added.push(makeLine(text[i], spansFor(i), estimateHeight));Ð     if (nlines >
1) doc.remove(from.line + 1, nlines - 1);Ð     doc.insert(from.line + 1,
added);Ð   }Ð   signalLater(doc, "change", doc, change);Ð   setSelection(doc,
selAfter.anchor, selAfter.head, null, true);Ð }Ð function LeafChunk(lines) {Ð
    this.lines = lines;Ð   this.parent = null;Ð   for (var i = 0, e =
lines.length, height = 0; i < e; ++i) {Ð     lines[i].parent = this;Ð
height += lines[i].height;Ð   }Ð   this.height = height;Ð }Ð
LeafChunk.prototype = {Ð   chunkSize: function() { return
this.lines.length; },Ð   removeInner: function(at, n) {Ð     for (var i = at,
e = at + n; i < e; ++i) {Ð       var line = this.lines[i];Ð       this.height
-= line.height;Ð       cleanUpLine(line);Ð       signalLater(line, "delete");Ð
      }Ð     this.lines.splice(at, n);Ð   },Ð   collapse: function(lines) {Ð
      lines.splice.apply(lines, [lines.length, 0].concat(this.lines));Ð   },Ð
    insertInner: function(at, lines, height) {Ð     this.height += height;Ð
      this.lines = this.lines.slice(0,
at).concat(lines).concat(this.lines.slice(at));Ð     for (var i = 0, e =
lines.length; i < e; ++i) lines[i].parent = this;Ð   },Ð   iterN:
function(at, n, op) {Ð     for (var e = at + n; at < e; ++at)Ð       if
(op(this.lines[at])) return true;Ð   }Ð };Ð function BranchChunk(children) {Ð
    this.children = children;Ð   var size = 0, height = 0;Ð   for (var i = 0,
e = children.length; i < e; ++i) {Ð     var ch = children[i];Ð     size +=
ch.chunkSize(); height += ch.height;Ð     ch.parent = this;Ð   }Ð   this.size
= size;Ð   this.height = height;Ð   this.parent = null;Ð }Ð
BranchChunk.prototype = {Ð   chunkSize: function() { return this.size; },Ð
removeInner: function(at, n) {Ð     this.size -= n;Ð     for (var i = 0; i <
this.children.length; ++i) {Ð       var child = this.children[i], sz =
child.chunkSize();Ð       if (at < sz) {Ð         var rm = Math.min(n, sz -
at), oldHeight = child.height;Ð         child.removeInner(at, rm);Ð
this.height -= oldHeight - child.height;Ð         if (sz == rm)
{ this.children.splice(i--, 1); child.parent = null; }Ð         if ((n -= rm)
== 0) break;Ð         at = 0;Ð       } else at -= sz;Ð     }Ð     if
(this.size - n < 25) {Ð
```

```
                                var lines = [];Ð       this.collapse(lines);Ð
        this.children = [new LeafChunk(lines)];Ð
this.children[0].parent = this;Ð     }Ð   },Ð   collapse: function(lines) {Ð
      for (var i = 0, e = this.children.length; i < e; ++i)
this.children[i].collapse(lines);Ð   },Ð   insertInner: function(at, lines,
height) {Ð     this.size += lines.length;Ð     this.height += height;Ð
for (var i = 0, e = this.children.length; i < e; ++i) {Ð       var child =
this.children[i], sz = child.chunkSize();Ð       if (at <= sz) {Ð
child.insertInner(at, lines, height);Ð         if (child.lines &&
child.lines.length > 50) {Ð           while (child.lines.length > 50) {Ð
              var spilled = child.lines.splice(child.lines.length - 25, 25);Ð
              var newleaf = new LeafChunk(spilled);Ð             child.height
-= newleaf.height;Ð             this.children.splice(i + 1, 0, newleaf);Ð
              newleaf.parent = this;Ð           }Ð
this.maybeSpill();Ð         }Ð         break;Ð       }Ð       at -= sz;Ð     }Ð
    },Ð   maybeSpill: function() {Ð     if (this.children.length <= 10)
return;Ð     var me = this;Ð     do {Ð       var spilled =
me.children.splice(me.children.length - 5, 5);Ð       var sibling = new
BranchChunk(spilled);Ð       if (!me.parent) { // Become the parent nodeÐ
          var copy = new BranchChunk(me.children);Ð         copy.parent = me;Ð
          me.children = [copy, sibling];Ð         me = copy;Ð       } else {Ð
          me.size -= sibling.size;Ð         me.height -= sibling.height;Ð
          var myIndex = indexOf(me.parent.children, me);Ð
me.parent.children.splice(myIndex + 1, 0, sibling);Ð       }Ð
sibling.parent = me.parent;Ð     } while (me.children.length > 10);Ð
me.parent.maybeSpill();Ð   },Ð   iterN: function(at, n, op) {Ð     for (var i
= 0, e = this.children.length; i < e; ++i) {Ð       var child =
this.children[i], sz = child.chunkSize();Ð       if (at < sz) {Ð         var
used = Math.min(n, sz - at);Ð         if (child.iterN(at, used, op)) return
true;Ð         if ((n -= used) == 0) break;Ð         at = 0;Ð       } else at
-= sz;Ð     }Ð   }Ð };Ð var nextDocId = 0;Ð var Doc = CodeMirror.Doc =
function(text, mode, firstLine) {Ð   if (!(this instanceof Doc)) return new
Doc(text, mode, firstLine);Ð   if (firstLine == null) firstLine = 0;Ð
BranchChunk.call(this, [new LeafChunk([makeLine("", null)])]);Ð   this.first
= firstLine;Ð   this.scrollTop = this.scrollLeft = 0;Ð   this.cantEdit =
false;Ð   this.history = makeHistory();Ð   this.frontier = firstLine;Ð   var
start = Pos(firstLine, 0);Ð   this.sel = {from: start, to: start, head:
start, anchor: start, shift: false, extend: false, goalColumn: null};Ð
this.id = ++nextDocId;Ð   this.modeOption = mode;Ð   if (typeof text ==
"string") text = splitLines(text);Ð   updateDoc(this, {from: start, to:
start, text: text}, null, {head: start, anchor: start});Ð };Ð Doc.prototype =
createObj(BranchChunk.prototype, {Ð   iter: function(from, to, op) {Ð     if
(op) this.iterN(from - this.first, to - from, op);Ð     else
this.iterN(this.first, this.first + this.size, from);Ð   },Ð   insert:
function(at, lines) {Ð     var height = 0;Ð     for (var i = 0, e =
lines.length; i < e; ++i) height += lines[i].height;Ð     this.insertInner(at
- this.first, lines, height);Ð   },Ð   remove: function(at, n)
{ this.removeInner(at - this.first, n); },Ð   getValue: function(lineSep) {Ð
      var lines = getLines(this, this.first, this.first + this.size);Ð     if
(lineSep === false) return lines;Ð     return lines.join(lineSep || "\n");Ð
    },Ð   setValue: function(code) {Ð     var top = Pos(this.first, 0), last
= this.first + this.size - 1;Ð     makeChange(this, {from: top, to: Pos(last,
getLine(this, last).text.length),Ð                       text:
splitLines(code), origin: "setValue"},Ð                 {head: top, anchor:
top}, true);Ð   },Ð   replaceRange: function(code, from, to, origin) {Ð
from = clipPos(this, from);Ð     to = to ? clipPos(this, to) : from;Ð
replaceRange(this, code, from, to, origin);Ð   },Ð   getRange: function(from,
to, lineSep) {Ð     var lines = getBetween(this, clipPos(this, from),
clipPos(this, to));Ð     if (lineSep === false) return lines;Ð     return
lines.join(lineSep || "\n");Ð
```

```
                                  },Ð   getLine: function(line) {var l =
this.getLineHandle(line); return l && l.text;},Ð   setLine: function(line,
text) {Ð     if (isLine(this, line))Ð       replaceRange(this, text,
Pos(line, 0), clipPos(this, Pos(line)));Ð   },Ð   removeLine: function(line) {Ð
      if (line) replaceRange(this, "", clipPos(this, Pos(line - 1)),
clipPos(this, Pos(line)));Ð     else replaceRange(this, "", Pos(0, 0),
clipPos(this, Pos(1, 0)));Ð   },Ð   getLineHandle: function(line) {if
(isLine(this, line)) return getLine(this, line);},Ð   getLineNumber:
function(line) {return lineNo(line);},Ð   lineCount: function() {return
this.size;},Ð   firstLine: function() {return this.first;},Ð   lastLine:
function() {return this.first + this.size - 1;},Ð   clipPos: function(pos)
{return clipPos(this, pos);},Ð   getCursor: function(start) {Ð     var sel =
this.sel, pos;Ð     if (start == null || start == "head") pos = sel.head;Ð
      else if (start == "anchor") pos = sel.anchor;Ð     else if (start ==
"end" || start === false) pos = sel.to;Ð     else pos = sel.from;Ð     return
copyPos(pos);Ð   },Ð   somethingSelected: function() {return !
posEq(this.sel.head, this.sel.anchor);},Ð   setCursor:
docOperation(function(line, ch, extend) {Ð     var pos = clipPos(this, typeof
line == "number" ? Pos(line, ch || 0) : line);Ð     if (extend)
extendSelection(this, pos);Ð     else setSelection(this, pos, pos);Ð   }),Ð
setSelection: docOperation(function(anchor, head) {Ð     setSelection(this,
clipPos(this, anchor), clipPos(this, head || anchor));Ð   }),Ð
extendSelection: docOperation(function(from, to) {Ð     extendSelection(this,
clipPos(this, from), to && clipPos(this, to));Ð   }),Ð   getSelection:
function(lineSep) {return this.getRange(this.sel.from, this.sel.to,
lineSep);},Ð   replaceSelection: function(code, collapse, origin) {Ð
makeChange(this, {from: this.sel.from, to: this.sel.to, text:
splitLines(code), origin: origin}, collapse || "around");Ð   },Ð   undo:
docOperation(function() {makeChangeFromHistory(this, "undo");}),Ð   redo:
docOperation(function() {makeChangeFromHistory(this, "redo");}),Ð
setExtending: function(val) {this.sel.extend = val;},Ð   historySize:
function() {Ð     var hist = this.history;Ð     return {undo:
hist.done.length, redo: hist.undone.length};Ð   },Ð   clearHistory:
function() {this.history = makeHistory();},Ð   markClean: function() {Ð
this.history.dirtyCounter = 0;Ð     this.history.lastOp =
this.history.lastOrigin = null;Ð   },Ð   isClean: function () {return
this.history.dirtyCounter == 0;},Ð   getHistory: function() {Ð     return
{done: copyHistoryArray(this.history.done),Ð             undone:
copyHistoryArray(this.history.undone)};Ð   },Ð   setHistory:
function(histData) {Ð     var hist = this.history = makeHistory();Ð
hist.done = histData.done.slice(0);Ð     hist.undone =
histData.undone.slice(0);Ð   },Ð   markText: function(from, to, options) {Ð
      return markText(this, clipPos(this, from), clipPos(this, to), options,
"range");Ð   },Ð   setBookmark: function(pos, options) {Ð     var realOpts =
{replacedWith: options && (options.nodeType == null ? options.widget :
options),Ð                     insertLeft: options && options.insertLeft};Ð
      pos = clipPos(this, pos);Ð     return markText(this, pos, pos,
realOpts, "bookmark");Ð   },Ð   findMarksAt: function(pos) {Ð     pos =
clipPos(this, pos);Ð     var markers = [], spans = getLine(this,
pos.line).markedSpans;Ð     if (spans) for (var i = 0; i < spans.length; ++i)
{Ð       var span = spans[i];Ð       if ((span.from == null || span.from <=
pos.ch) &&Ð           (span.to == null || span.to >= pos.ch))Ð
markers.push(span.marker.parent || span.marker);Ð     }Ð     return markers;Ð
    },Ð   getAllMarks: function() {Ð     var markers = [];Ð
this.iter(function(line) {Ð       var sps = line.markedSpans;Ð       if (sps)
for (var i = 0; i < sps.length; ++i)Ð         if (sps[i].from != null)
markers.push(sps[i].marker);Ð     });Ð     return markers;Ð   },Ð
posFromIndex: function(off) {Ð     var ch, lineNo = this.first;Ð
this.iter(function(line) {Ð       var sz = line.text.length + 1;Ð       if
(sz > off) { ch = off; return true; }Ð
```

```
                                                off -= sz;Ð       ++lineNo;Ð
      });Ð     return clipPos(this, Pos(lineNo, ch));Ð   },Ð   indexFromPos:
function (coords) {Ð     coords = clipPos(this, coords);Ð     var index =
coords.ch;Ð     if (coords.line < this.first || coords.ch < 0) return 0;Ð
this.iter(this.first, coords.line, function (line) {Ð       index +=
line.text.length + 1;Ð     });Ð     return index;Ð   },Ð   copy:
function(copyHistory) {Ð     var doc = new Doc(getLines(this, this.first,
this.first + this.size), this.modeOption, this.first);Ð     doc.scrollTop =
this.scrollTop; doc.scrollLeft = this.scrollLeft;Ð     doc.sel = {from:
this.sel.from, to: this.sel.to, head: this.sel.head, anchor: this.sel.anchor,Ð
                  shift: this.sel.shift, extend: false, goalColumn:
this.sel.goalColumn};Ð     if (copyHistory) {Ð       doc.history.undoDepth =
this.history.undoDepth;Ð       doc.setHistory(this.getHistory());Ð     }Ð
return doc;Ð   },Ð   linkedDoc: function(options) {Ð     if (!options)
options = {};Ð     var from = this.first, to = this.first + this.size;Ð
if (options.from != null && options.from > from) from = options.from;Ð     if
(options.to != null && options.to < to) to = options.to;Ð     var copy = new
Doc(getLines(this, from, to), options.mode || this.modeOption, from);Ð     if
(options.sharedHist) copy.history = this.history;Ð     (this.linked ||
(this.linked = [])).push({doc: copy, sharedHist: options.sharedHist});Ð
copy.linked = [{doc: this, isParent: true, sharedHist: options.sharedHist}];Ð
      return copy;Ð   },Ð   unlinkDoc: function(other) {Ð     if (other
instanceof CodeMirror) other = other.doc;Ð     if (this.linked) for (var i =
0; i < this.linked.length; ++i) {Ð       var link = this.linked[i];Ð       if
(link.doc != other) continue;Ð       this.linked.splice(i, 1);Ð
other.unlinkDoc(this);Ð       break;Ð     }Ð     // If the histories were
shared, split them againÐ     if (other.history == this.history) {Ð       var
splitIds = [other.id];Ð       linkedDocs(other, function(doc)
{splitIds.push(doc.id);}, true);Ð       other.history = makeHistory();Ð
other.history.done = copyHistoryArray(this.history.done, splitIds);Ð
other.history.undone = copyHistoryArray(this.history.undone, splitIds);Ð     }Ð
    },Ð   iterLinkedDocs: function(f) {linkedDocs(this, f);},Ð   getMode:
function() {return this.mode;},Ð   getEditor: function() {return this.cm;}Ð
  });Ð Doc.prototype.eachLine = Doc.prototype.iter;Ð // The Doc methods that
should be available on CodeMirror instancesÐ var dontDelegate = "iter insert
remove copy getEditor".split(" ");Ð for (var prop in Doc.prototype) if
(Doc.prototype.hasOwnProperty(prop) && indexOf(dontDelegate, prop) < 0)Ð
CodeMirror.prototype[prop] = (function(method) {Ð     return function()
{return method.apply(this.doc, arguments);};Ð   })(Doc.prototype[prop]);Ð
function linkedDocs(doc, f, sharedHistOnly) {Ð   function propagate(doc,
skip, sharedHist) {Ð     if (doc.linked) for (var i = 0; i <
doc.linked.length; ++i) {Ð       var rel = doc.linked[i];Ð       if (rel.doc
== skip) continue;Ð       var shared = sharedHist && rel.sharedHist;Ð
if (sharedHistOnly && !shared) continue;Ð       f(rel.doc, shared);Ð
propagate(rel.doc, doc, shared);Ð     }Ð   }Ð   propagate(doc, null, true);Ð }Ð
  function attachDoc(cm, doc) {Ð   if (doc.cm) throw new Error("This document
is already in use.");Ð   cm.doc = doc;Ð   doc.cm = cm;Ð
estimateLineHeights(cm);Ð   loadMode(cm);Ð   if (!cm.options.lineWrapping)
computeMaxLength(cm);Ð   cm.options.mode = doc.modeOption;Ð   regChange(cm);Ð
  }Ð // LINE UTILITIESÐ function getLine(chunk, n) {Ð   n -= chunk.first;Ð
while (!chunk.lines) {Ð     for (var i = 0;; ++i) {Ð       var child =
chunk.children[i], sz = child.chunkSize();Ð       if (n < sz) { chunk =
child; break; }Ð       n -= sz;Ð     }Ð   }Ð   return chunk.lines[n];Ð }Ð
function getBetween(doc, start, end) {Ð   var out = [], n = start.line;Ð
doc.iter(start.line, end.line + 1, function(line) {Ð     var text = line.text;Ð
      if (n == end.line) text = text.slice(0, end.ch);Ð     if (n ==
start.line) text = text.slice(start.ch);Ð     out.push(text);Ð     ++n;Ð   });Ð
    return out;Ð }Ð function getLines(doc, from, to) {Ð   var out = [];Ð
doc.iter(from, to, function(line) { out.push(line.text); });Ð   return out;Ð }Ð
  function updateLineHeight(line, height) {Ð
```

```
                                                var diff = height -
line.height;Ð   for (var n = line; n; n = n.parent) n.height += diff;Ð }Ð
function lineNo(line) {Ð   if (line.parent == null) return null;Ð   var cur =
line.parent, no = indexOf(cur.lines, line);Ð   for (var chunk = cur.parent;
chunk; cur = chunk, chunk = chunk.parent) {Ð     for (var i = 0;; ++i) {Ð
        if (chunk.children[i] == cur) break;Ð       no +=
chunk.children[i].chunkSize();Ð     }Ð   }Ð   return no + cur.first;Ð }Ð
function lineAtHeight(chunk, h) {Ð   var n = chunk.first;Ð   outer: do {Ð
for (var i = 0, e = chunk.children.length; i < e; ++i) {Ð       var child =
chunk.children[i], ch = child.height;Ð       if (h < ch) { chunk = child;
continue outer; }Ð       h -= ch;Ð       n += child.chunkSize();Ð     }Ð
return n;Ð   } while (!chunk.lines);Ð   for (var i = 0, e =
chunk.lines.length; i < e; ++i) {Ð     var line = chunk.lines[i], lh =
line.height;Ð     if (h < lh) break;Ð     h -= lh;Ð   }Ð   return n + i;Ð }Ð
function heightAtLine(cm, lineObj) {Ð   lineObj = visualLine(cm.doc, lineObj);Ð
    var h = 0, chunk = lineObj.parent;Ð   for (var i = 0; i <
chunk.lines.length; ++i) {Ð     var line = chunk.lines[i];Ð     if (line ==
lineObj) break;Ð     else h += line.height;Ð   }Ð   for (var p =
chunk.parent; p; chunk = p, p = chunk.parent) {Ð     for (var i = 0; i <
p.children.length; ++i) {Ð       var cur = p.children[i];Ð       if (cur ==
chunk) break;Ð       else h += cur.height;Ð     }Ð   }Ð   return h;Ð }Ð
function getOrder(line) {Ð   var order = line.order;Ð   if (order == null)
order = line.order = bidiOrdering(line.text);Ð   return order;Ð }Ð // HISTORYÐ
  function makeHistory() {Ð   return {Ð     // Arrays of history events.
Doing something adds an event toÐ     // done and clears undo. Undoing moves
events from done toÐ     // undone, redoing moves them in the other direction.Ð
      done: [], undone: [], undoDepth: Infinity,Ð     // Used to track when
changes can be merged into a single undoÐ     // eventÐ     lastTime: 0,
lastOp: null, lastOrigin: null,Ð     // Used by the isClean() methodÐ
dirtyCounter: 0Ð   };Ð }Ð function attachLocalSpans(doc, change, from, to) {Ð
    var existing = change["spans_" + doc.id], n = 0;Ð
doc.iter(Math.max(doc.first, from), Math.min(doc.first + doc.size, to),
function(line) {Ð     if (line.markedSpans)Ð       (existing || (existing =
change["spans_" + doc.id] = {}))[n] = line.markedSpans;Ð     ++n;Ð   });Ð }Ð
function historyChangeFromChange(doc, change) {Ð   var histChange = {from:
change.from, to: changeEnd(change), text: getBetween(doc, change.from,
change.to)};Ð   attachLocalSpans(doc, histChange, change.from.line,
change.to.line + 1);Ð   linkedDocs(doc, function(doc) {attachLocalSpans(doc,
histChange, change.from.line, change.to.line + 1);}, true);Ð   return
histChange;Ð }Ð function addToHistory(doc, change, selAfter, opId) {Ð   var
hist = doc.history;Ð   hist.undone.length = 0;Ð   var time = +new Date, cur =
lst(hist.done);Ð   if (cur &&Ð       (hist.lastOp == opId ||Ð
hist.lastOrigin == change.origin && change.origin &&Ð
((change.origin.charAt(0) == "+" && doc.cm && hist.lastTime > time -
doc.cm.options.historyEventDelay) ||Ð         change.origin.charAt(0) ==
"*"))) {Ð     // Merge this change into the last eventÐ     var last =
lst(cur.changes);Ð     if (posEq(change.from, change.to) &&
posEq(change.from, last.to)) {Ð       // Optimized case for simple insertion
-- don't want to addÐ       // new changesets for every character typedÐ
        last.to = changeEnd(change);Ð     } else {Ð       // Add new sub-eventÐ
        cur.changes.push(historyChangeFromChange(doc, change));Ð     }Ð
cur.anchorAfter = selAfter.anchor; cur.headAfter = selAfter.head;Ð   } else {Ð
      // Can not be merged, start a new event.Ð     cur = {changes:
[historyChangeFromChange(doc, change)],Ð            anchorBefore:
doc.sel.anchor, headBefore: doc.sel.head,Ð            anchorAfter:
selAfter.anchor, headAfter: selAfter.head};Ð     hist.done.push(cur);Ð
while (hist.done.length > hist.undoDepth)Ð       hist.done.shift();Ð     if
(hist.dirtyCounter < 0)Ð       // The user has made a change after undoing
past the last clean state.Ð       // We can never get back to a clean state
now until markClean() is called.Ð
```

```
                                        hist.dirtyCounter = NaN;Ð     elseÐ
        hist.dirtyCounter++;Ð   }Ð   hist.lastTime = time;Ð   hist.lastOp =
opId;Ð   hist.lastOrigin = change.origin;Ð }Ð function
removeClearedSpans(spans) {Ð   if (!spans) return null;Ð   for (var i = 0,
out; i < spans.length; ++i) {Ð     if (spans[i].marker.explicitlyCleared)
{ if (!out) out = spans.slice(0, i); }Ð     else if (out) out.push(spans[i]);Ð
    }Ð   return !out ? spans : out.length ? out : null;Ð }Ð function
getOldSpans(doc, change) {Ð   var found = change["spans_" + doc.id];Ð   if (!
found) return null;Ð   for (var i = 0, nw = []; i < change.text.length; ++i)Ð
      nw.push(removeClearedSpans(found[i]));Ð   return nw;Ð }Ð // Used both
to provide a JSON-safe object in .getHistory, and, whenÐ // detaching a
document, to split the history in twoÐ function copyHistoryArray(events,
newGroup) {Ð   for (var i = 0, copy = []; i < events.length; ++i) {Ð     var
event = events[i], changes = event.changes, newChanges = [];Ð
copy.push({changes: newChanges, anchorBefore: event.anchorBefore, headBefore:
event.headBefore,Ð                anchorAfter: event.anchorAfter, headAfter:
event.headAfter});Ð     for (var j = 0; j < changes.length; ++j) {Ð       var
change = changes[j], m;Ð       newChanges.push({from: change.from, to:
change.to, text: change.text});Ð       if (newGroup) for (var prop in change)
if (m = prop.match(/^spans_(\d+)$/)) {Ð         if (indexOf(newGroup,
Number(m[1])) > -1) {Ð           lst(newChanges)[prop] = change[prop];Ð
            delete change[prop];Ð         }Ð       }Ð     }Ð   }Ð   return
copy;Ð }Ð // Rebasing/resetting history to deal with externally-sourced
changesÐ function rebaseHistSel(pos, from, to, diff) {Ð   if (to < pos.line) {Ð
      pos.line += diff;Ð   } else if (from < pos.line) {Ð     pos.line = from;Ð
      pos.ch = 0;Ð   }Ð }Ð // Tries to rebase an array of history events
given a change in theÐ // document. If the change touches the same lines as
the event, theÐ // event, and everything 'behind' it, is discarded. If the
change isÐ // before the event, the event's positions are updated. Uses aÐ //
copy-on-write scheme for the positions, to avoid having toÐ // reallocate
them all on every rebase, but also avoid problems withÐ // shared position
objects being unsafely updated.Ð function rebaseHistArray(array, from, to,
diff) {Ð   for (var i = 0; i < array.length; ++i) {Ð     var sub = array[i],
ok = true;Ð     for (var j = 0; j < sub.changes.length; ++j) {Ð       var cur
= sub.changes[j];Ð       if (!sub.copied) { cur.from = copyPos(cur.from);
cur.to = copyPos(cur.to); }Ð       if (to < cur.from.line) {Ð
cur.from.line += diff;Ð         cur.to.line += diff;Ð       } else if (from
<= cur.to.line) {Ð         ok = false;Ð         break;Ð       }Ð     }Ð
if (!sub.copied) {Ð       sub.anchorBefore = copyPos(sub.anchorBefore);
sub.headBefore = copyPos(sub.headBefore);Ð       sub.anchorAfter =
copyPos(sub.anchorAfter); sub.readAfter = copyPos(sub.headAfter);Ð
sub.copied = true;Ð     }Ð     if (!ok) {Ð       array.splice(0, i + 1);Ð
        i = 0;Ð     } else {Ð       rebaseHistSel(sub.anchorBefore);
rebaseHistSel(sub.headBefore);Ð       rebaseHistSel(sub.anchorAfter);
rebaseHistSel(sub.headAfter);Ð     }Ð   }Ð }Ð function rebaseHist(hist,
change) {Ð   var from = change.from.line, to = change.to.line, diff =
change.text.length - (to - from) - 1;Ð   rebaseHistArray(hist.done, from, to,
diff);Ð   rebaseHistArray(hist.undone, from, to, diff);Ð }Ð // EVENT OPERATORSÐ
  function stopMethod() {e_stop(this);}Ð // Ensure an event has a stop method.Ð
  function addStop(event) {Ð   if (!event.stop) event.stop = stopMethod;Ð
return event;Ð }Ð function e_preventDefault(e) {Ð   if (e.preventDefault)
e.preventDefault();Ð   else e.returnValue = false;Ð }Ð function
e_stopPropagation(e) {Ð   if (e.stopPropagation) e.stopPropagation();Ð   else
e.cancelBubble = true;Ð }Ð function e_stop(e) {e_preventDefault(e);
e_stopPropagation(e);}Ð CodeMirror.e_stop = e_stop;Ð
CodeMirror.e_preventDefault = e_preventDefault;Ð CodeMirror.e_stopPropagation
= e_stopPropagation;Ð function e_target(e) {return e.target || e.srcElement;}Ð
  function e_button(e) {Ð   var b = e.which;Ð   if (b == null) {Ð     if
(e.button & 1) b = 1;Ð     else if (e.button & 2) b = 3;Ð     else if
(e.button & 4) b = 2;Ð
```

```
                          }Ð   if (mac && e.ctrlKey && b == 1) b = 3;Ð
return b;Ð }Ð // EVENT HANDLINGÐ function on(emitter, type, f) {Ð   if
(emitter.addEventListener)Ð     emitter.addEventListener(type, f, false);Ð
else if (emitter.attachEvent)Ð     emitter.attachEvent("on" + type, f);Ð
else {Ð     var map = emitter._handlers || (emitter._handlers = {});Ð     var
arr = map[type] || (map[type] = []);Ð     arr.push(f);Ð   }Ð }Ð function
off(emitter, type, f) {Ð   if (emitter.removeEventListener)Ð
emitter.removeEventListener(type, f, false);Ð   else if (emitter.detachEvent)Ð
      emitter.detachEvent("on" + type, f);Ð   else {Ð     var arr =
emitter._handlers && emitter._handlers[type];Ð     if (!arr) return;Ð     for
(var i = 0; i < arr.length; ++i)Ð       if (arr[i] == f) { arr.splice(i, 1);
break; }Ð   }Ð }Ð function signal(emitter, type /*, values...*/) {Ð   var arr
= emitter._handlers && emitter._handlers[type];Ð   if (!arr) return;Ð   var
args = Array.prototype.slice.call(arguments, 2);Ð   for (var i = 0; i <
arr.length; ++i) arr[i].apply(null, args);Ð }Ð var delayedCallbacks,
delayedCallbackDepth = 0;Ð function signalLater(emitter, type /*,
values...*/) {Ð   var arr = emitter._handlers && emitter._handlers[type];Ð
if (!arr) return;Ð   var args = Array.prototype.slice.call(arguments, 2);Ð
if (!delayedCallbacks) {Ð     ++delayedCallbackDepth;Ð     delayedCallbacks =
[];Ð     setTimeout(fireDelayed, 0);Ð   }Ð   function bnd(f) {return
function(){f.apply(null, args);};};Ð   for (var i = 0; i < arr.length; ++i)Ð
      delayedCallbacks.push(bnd(arr[i]));Ð }Ð function fireDelayed() {Ð   --
delayedCallbackDepth;Ð   var delayed = delayedCallbacks;Ð   delayedCallbacks
= null;Ð   for (var i = 0; i < delayed.length; ++i) delayed[i]();Ð }Ð
function hasHandler(emitter, type) {Ð   var arr = emitter._handlers &&
emitter._handlers[type];Ð   return arr && arr.length > 0;Ð }Ð CodeMirror.on =
on; CodeMirror.off = off; CodeMirror.signal = signal;Ð // MISC UTILITIESÐ //
Number of pixels added to scroller and sizer to hide scrollbarÐ var
scrollerCutOff = 30;Ð // Returned or thrown by various protocols to signal
'I'm notÐ // handling this'.Ð var Pass = CodeMirror.Pass = {toString:
function(){return "CodeMirror.Pass";}};Ð function Delayed() {this.id = null;}Ð
  Delayed.prototype = {set: function(ms, f) {clearTimeout(this.id); this.id =
setTimeout(f, ms);}};Ð // Counts the column offset in a string, taking tabs
into account.Ð // Used mostly to find indentation.Ð function
countColumn(string, end, tabSize, startIndex, startValue) {Ð   if (end ==
null) {Ð     end = string.search(/[^\s\u00a0]/);Ð     if (end == -1) end =
string.length;Ð   }Ð   for (var i = startIndex || 0, n = startValue || 0; i <
end; ++i) {Ð     if (string.charAt(i) == "\t") n += tabSize - (n % tabSize);Ð
      else ++n;Ð   }Ð   return n;Ð }Ð CodeMirror.countColumn = countColumn;Ð
var spaceStrs = [""];Ð function spaceStr(n) {Ð   while (spaceStrs.length <= n)Ð
      spaceStrs.push(lst(spaceStrs) + " ");Ð   return spaceStrs[n];Ð }Ð
function lst(arr) { return arr[arr.length-1]; }Ð function selectInput(node) {Ð
    if (ios) { // Mobile Safari apparently has a bug where select() is broken.Ð
      node.selectionStart = 0;Ð     node.selectionEnd = node.value.length;Ð
    } else node.select();Ð }Ð function indexOf(collection, elt) {Ð   if
(collection.indexOf) return collection.indexOf(elt);Ð   for (var i = 0, e =
collection.length; i < e; ++i)Ð     if (collection[i] == elt) return i;Ð
return -1;Ð }Ð function createObj(base, props) {Ð   function Obj() {}Ð
Obj.prototype = base;Ð   var inst = new Obj();Ð   if (props) copyObj(props,
inst);Ð   return inst;Ð }Ð function copyObj(obj, target) {Ð   if (!target)
target = {};Ð   for (var prop in obj) if (obj.hasOwnProperty(prop))
target[prop] = obj[prop];Ð   return target;Ð }Ð function emptyArray(size) {Ð
    for (var a = [], i = 0; i < size; ++i) a.push(undefined);Ð   return a;Ð }Ð
  function bind(f) {Ð   var args = Array.prototype.slice.call(arguments, 1);Ð
    return function(){return f.apply(null, args);};Ð }Ð var
nonASCIISingleCaseWordChar = /[\u3040-\u309f\u30a0-\u30ff\u3400-\u4db5\u4e00-
\u9fcc]/;Ð function isWordChar(ch) {Ð   return /\w/.test(ch) || ch > "\x80" &&Ð
      (ch.toUpperCase() != ch.toLowerCase() ||
nonASCIISingleCaseWordChar.test(ch));Ð }Ð function isEmpty(obj) {Ð   for (var
n in obj) if (obj.hasOwnProperty(n) && obj[n]) return false;Ð
```

```
                                                                return true;Ð
  }Ð var isExtendingChar = /[\u0300-\u036F\u0483-\u0487\u0488-\u0489\u0591-
\u05BD\u05BF\u05C1-\u05C2\u05C4-\u05C5\u05C7\u0610-\u061A\u064B-
\u065F\u0670\u06D6-\u06DC\u06DF-\u06E4\u06E7-\u06E8\u06EA-\u06ED\uA66F\uA670-
\uA672\uA674-\uA67D\uA69F\udc00-\udfff]/;Ð // DOM UTILITIESÐ function
elt(tag, content, className, style) {Ð   var e = document.createElement(tag);Ð
    if (className) e.className = className;Ð   if (style) e.style.cssText =
style;Ð   if (typeof content == "string") setTextContent(e, content);Ð   else
if (content) for (var i = 0; i < content.length; ++i)
e.appendChild(content[i]);Ð   return e;Ð }Ð function removeChildren(e) {Ð
for (var count = e.childNodes.length; count > 0; --count)Ð
e.removeChild(e.firstChild);Ð   return e;Ð }Ð function
removeChildrenAndAdd(parent, e) {Ð   return
removeChildren(parent).appendChild(e);Ð }Ð function setTextContent(e, str) {Ð
    if (ie_lt9) {Ð     e.innerHTML = "";Ð
e.appendChild(document.createTextNode(str));Ð   } else e.textContent = str;Ð }Ð
  function getRect(node) {Ð   return node.getBoundingClientRect();Ð }Ð
CodeMirror.replaceGetRect = function(f) { getRect = f; };Ð // FEATURE
DETECTIONÐ // Detect drag-and-dropÐ var dragAndDrop = function() {Ð   //
There is *some* kind of drag-and-drop support in IE6-8, but IÐ   // couldn't
get it to work yet.Ð   if (ie_lt9) return false;Ð   var div = elt('div');Ð
return "draggable" in div || "dragDrop" in div;Ð }();Ð // For a reason I have
yet to figure out, some browsers disallowÐ // word wrapping between certain
characters *only* if a new inlineÐ // element is started between them. This
makes it hard to reliablyÐ // measure the position of things, since that
requires inserting anÐ // extra span. This terribly fragile set of regexps
matches theÐ // character combinations that suffer from this phenomenon on theÐ
  // various browsers.Ð var spanAffectsWrapping = /^$/; // Won't match any
two-character stringÐ if (gecko) spanAffectsWrapping = /$'/;Ð else if (safari
&& !/Version\/([6-9]|\d\d)\b/.test(navigator.userAgent)) spanAffectsWrapping
= /\-[^ \-?]|\?[^ !'\"\),.\-\/:;\?\]\}]/;Ð else if (webkit)
spanAffectsWrapping = /[~!#%&*)=+}\]|\"\.>,:;][({[<]|-[^\-?\.]|\?[\w~`@#$%
\^&*(_=+{[|><]/;Ð var knownScrollbarWidth;Ð function scrollbarWidth(measure) {Ð
    if (knownScrollbarWidth != null) return knownScrollbarWidth;Ð   var test
= elt("div", null, null, "width: 50px; height: 50px; overflow-x: scroll");Ð
removeChildrenAndAdd(measure, test);Ð   if (test.offsetWidth)Ð
knownScrollbarWidth = test.offsetHeight - test.clientHeight;Ð   return
knownScrollbarWidth || 0;Ð }Ð var zwspSupported;Ð function
zeroWidthElement(measure) {Ð   if (zwspSupported == null) {Ð     var test =
elt("span", "\u200b");Ð     removeChildrenAndAdd(measure, elt("span", [test,
document.createTextNode("x")]));Ð     if (measure.firstChild.offsetHeight !=
0)Ð       zwspSupported = test.offsetWidth <= 1 && test.offsetHeight > 2 && !
ie_lt8;Ð   }Ð   if (zwspSupported) return elt("span", "\u200b");Ð   else
return elt("span", "\u00a0", null, "display: inline-block; width: 1px; margin-
right: -1px");Ð }Ð // See if "".split is the broken IE version, if so,
provide anÐ // alternative way to split lines.Ð var splitLines =
"\n\nb".split(/\n/).length != 3 ? function(string) {Ð   var pos = 0, result =
[], l = string.length;Ð   while (pos <= l) {Ð     var nl =
string.indexOf("\n", pos);Ð     if (nl == -1) nl = string.length;Ð     var
line = string.slice(pos, string.charAt(nl - 1) == "\r" ? nl - 1 : nl);Ð
var rt = line.indexOf("\r");Ð     if (rt != -1) {Ð
result.push(line.slice(0, rt));Ð       pos += rt + 1;Ð     } else {Ð
result.push(line);Ð       pos = nl + 1;Ð     }Ð   }Ð   return result;Ð } :
function(string){return string.split(/\r\n?|\n/);};Ð CodeMirror.splitLines =
splitLines;Ð var hasSelection = window.getSelection ? function(te) {Ð   try
{ return te.selectionStart != te.selectionEnd; }Ð   catch(e) { return false; }Ð
  } : function(te) {Ð   try {var range =
te.ownerDocument.selection.createRange();}Ð   catch(e) {}Ð   if (!range ||
range.parentElement() != te) return false;Ð   return
range.compareEndPoints("StartToEnd", range) != 0;Ð
```

```
                                                    };Ð var hasCopyEvent =
(function() {Ð   var e = elt("div");Ð   if ("oncopy" in e) return true;Ð
e.setAttribute("oncopy", "return;");Ð   return typeof e.oncopy == 'function';Ð
  })();Ð // KEY NAMINGÐ var keyNames = {3: "Enter", 8: "Backspace", 9: "Tab",
13: "Enter", 16: "Shift", 17: "Ctrl", 18: "Alt",Ð                  19:
"Pause", 20: "CapsLock", 27: "Esc", 32: "Space", 33: "PageUp", 34:
"PageDown", 35: "End",Ð                 36: "Home", 37: "Left", 38: "Up", 39:
"Right", 40: "Down", 44: "PrintScrn", 45: "Insert",Ð                 46:
"Delete", 59: ";", 91: "Mod", 92: "Mod", 93: "Mod", 109: "-", 107: "=", 127:
"Delete",Ð                 186: ";", 187: "=", 188: ",", 189: "-", 190: ".",
191: "/", 192: "`", 219: "[", 220: "\\",Ð                 221: "]", 222: "'",
63276: "PageUp", 63277: "PageDown", 63275: "End", 63273: "Home",Ð
                  63234: "Left", 63232: "Up", 63235: "Right", 63233: "Down",
63302: "Insert", 63272: "Delete"};Ð CodeMirror.keyNames = keyNames;Ð
(function() {Ð   // Number keysÐ   for (var i = 0; i < 10; i++) keyNames[i +
48] = String(i);Ð   // Alphabetic keysÐ   for (var i = 65; i <= 90; i++)
keyNames[i] = String.fromCharCode(i);Ð   // Function keysÐ   for (var i = 1;
i <= 12; i++) keyNames[i + 111] = keyNames[i + 63235] = "F" + i;Ð })();Ð //
BIDI HELPERSÐ function iterateBidiSections(order, from, to, f) {Ð   if (!
order) return f(from, to, "ltr");Ð   for (var i = 0; i < order.length; ++i) {Ð
      var part = order[i];Ð     if (part.from < to && part.to > from || from
== to && part.to == from)Ð       f(Math.max(part.from, from),
Math.min(part.to, to), part.level == 1 ? "rtl" : "ltr");Ð   }Ð }Ð function
bidiLeft(part) { return part.level % 2 ? part.to : part.from; }Ð function
bidiRight(part) { return part.level % 2 ? part.from : part.to; }Ð function
lineLeft(line) { var order = getOrder(line); return order ?
bidiLeft(order[0]) : 0; }Ð function lineRight(line) {Ð   var order =
getOrder(line);Ð   if (!order) return line.text.length;Ð   return
bidiRight(lst(order));Ð }Ð function lineStart(cm, lineN) {Ð   var line =
getLine(cm.doc, lineN);Ð   var visual = visualLine(cm.doc, line);Ð   if
(visual != line) lineN = lineNo(visual);Ð   var order = getOrder(visual);Ð
var ch = !order ? 0 : order[0].level % 2 ? lineRight(visual) :
lineLeft(visual);Ð   return Pos(lineN, ch);Ð }Ð function lineEnd(cm, lineN) {Ð
    var merged, line;Ð   while (merged = collapsedSpanAtEnd(line =
getLine(cm.doc, lineN)))Ð     lineN = merged.find().to.line;Ð   var order =
getOrder(line);Ð   var ch = !order ? line.text.length : order[0].level % 2 ?
lineLeft(line) : lineRight(line);Ð   return Pos(lineN, ch);Ð }Ð // This is
somewhat involved. It is needed in order to moveÐ // 'visually' through bi-
directional text -- i.e., pressing leftÐ // should make the cursor go left,
even when in RTL text. TheÐ // tricky part is the 'jumps', where RTL and LTR
text touch eachÐ // other. This often requires the cursor offset to move more
thanÐ // one unit, in order to visually move one unit.Ð function
moveVisually(line, start, dir, byUnit) {Ð   var bidi = getOrder(line);Ð   if
(!bidi) return moveLogically(line, start, dir, byUnit);Ð   var moveOneUnit =
byUnit ? function(pos, dir) {Ð     do pos += dir;Ð     while (pos > 0 &&
isExtendingChar.test(line.text.charAt(pos)));Ð     return pos;Ð   } :
function(pos, dir) { return pos + dir; };Ð   var linedir = bidi[0].level;Ð
for (var i = 0; i < bidi.length; ++i) {Ð     var part = bidi[i], sticky =
part.level % 2 == linedir;Ð     if ((part.from < start && part.to > start) ||Ð
          (sticky && (part.from == start || part.to == start))) break;Ð   }Ð
    var target = moveOneUnit(start, part.level % 2 ? -dir : dir);Ð   while
(target != null) {Ð     if (part.level % 2 == linedir) {Ð       if (target <
part.from || target > part.to) {Ð         part = bidi[i += dir];Ð
target = part && (dir > 0 == part.level % 2 ? moveOneUnit(part.to, -1) :
moveOneUnit(part.from, 1));Ð       } else break;Ð     } else {Ð       if
(target == bidiLeft(part)) {Ð         part = bidi[--i];Ð         target =
part && bidiRight(part);Ð       } else if (target == bidiRight(part)) {Ð
          part = bidi[++i];Ð         target = part && bidiLeft(part);Ð
        } else break;Ð     }Ð   }Ð   return target < 0 || target >
line.text.length ? null : target;Ð
```

```
                                    }Ð function moveLogically(line, start,
dir, byUnit) {Ð   var target = start + dir;Ð   if (byUnit) while (target > 0
&& isExtendingChar.test(line.text.charAt(target))) target += dir;Ð   return
target < 0 || target > line.text.length ? null : target;Ð }Ð // Bidirectional
ordering algorithmÐ // See http://unicode.org/reports/tr9/tr9-13.html for the
algorithmÐ // that this (partially) implements.Ð // One-char codes used for
character types:Ð // L (L):   Left-to-RightÐ // R (R):   Right-to-LeftÐ // r
(AL):  Right-to-Left ArabicÐ // 1 (EN):  European NumberÐ // + (ES):
European Number SeparatorÐ // % (ET):  European Number TerminatorÐ // n
(AN):  Arabic NumberÐ // , (CS):  Common Number SeparatorÐ // m (NSM): Non-
Spacing MarkÐ // b (BN):  Boundary NeutralÐ // s (B):   Paragraph SeparatorÐ
  // t (S):   Segment SeparatorÐ // w (WS):  WhitespaceÐ // N (ON):  Other
NeutralsÐ // Returns null if characters are ordered as they appearÐ // (left-
to-right), or an array of sections ({from, to, level}Ð // objects) in the
order in which they occur visually.Ð var bidiOrdering = (function() {Ð   //
Character types for codepoints 0 to 0xffÐ   var lowTypes =
"bbbbbbbbbtstwsbbbbbbbbbbbbbbssstwNN%%%NNNNNN,N,N1111111111NNNNNNNLLLLLLLLLLL
LLLLLLLLLLLLLLNNNNNNLLLLLLLLLLLLLLLLLLLLLLLLLLLLNNNNbbbbbbsbbbbbbbbbbbbbbbbbbb
bbbbb,N%%%%NNNNLNNNNN%
%11NLNNN1LNNNNNLLLLLLLLLLLLLLLLLLLLLLLLNLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLNLLLLLLL";Ð
    // Character types for codepoints 0x600 to 0x6ffÐ   var arabicTypes = "rrr
rrrrrrrrr,rNNmmmmmmrrrrrrr
```

```
          for (var j = i; j < end; ++j) types[j] = replace;Ð         i = end
- 1;Ð       }Ð     }Ð     // W7. Search backwards from each instance of a
European numberÐ     // until the first strong type (R, L, or sor) is found.
If an L isÐ     // found, then change the type of the European number to L.Ð
      for (var i = 0, cur = outerType; i < len; ++i) {Ð       var type =
types[i];Ð       if (cur == "L" && type == "1") types[i] = "L";Ð       else
if (isStrong.test(type)) cur = type;Ð     }Ð     // N1. A sequence of
neutrals takes the direction of theÐ     // surrounding strong text if the
text on both sides has the sameÐ     // direction. European and Arabic
numbers act as if they were R inÐ     // terms of their influence on
neutrals. Start-of-level-run (sor)Ð     // and end-of-level-run (eor) are
used at level run boundaries.Ð     // N2. Any remaining neutrals take the
embedding direction.Ð     for (var i = 0; i < len; ++i) {Ð       if
(isNeutral.test(types[i])) {Ð         for (var end = i + 1; end < len &&
isNeutral.test(types[end]); ++end) {}Ð         var before = (i ? types[i-1] :
outerType) == "L";Ð         var after = (end < len - 1 ? types[end] :
outerType) == "L";Ð         var replace = before || after ? "L" : "R";Ð
          for (var j = i; j < end; ++j) types[j] = replace;Ð         i = end
- 1;Ð       }Ð     }Ð     // Here we depart from the documented algorithm, in
order to avoidÐ     // building up an actual levels array. Since there are
only threeÐ     // levels (0, 1, 2) in an implementation that doesn't takeÐ
      // explicit embedding into account, we can build up the order onÐ
      // the fly, without following the level-based algorithm.Ð     var order
= [], m;Ð     for (var i = 0; i < len;) {Ð       if
(countsAsLeft.test(types[i])) {Ð         var start = i;Ð         for (++i; i
< len && countsAsLeft.test(types[i]); ++i) {}Ð         order.push({from:
start, to: i, level: 0});Ð       } else {Ð         var pos = i, at =
order.length;Ð         for (++i; i < len && types[i] != "L"; ++i) {}Ð
for (var j = pos; j < i;) {Ð           if (countsAsNum.test(types[j])) {Ð
              if (pos < j) order.splice(at, 0, {from: pos, to: j, level: 1});Ð
              var nstart = j;Ð             for (++j; j < i &&
countsAsNum.test(types[j]); ++j) {}Ð             order.splice(at, 0, {from:
nstart, to: j, level: 2});Ð             pos = j;Ð           } else ++j;Ð
          }Ð         if (pos < i) order.splice(at, 0, {from: pos, to: i,
level: 1});Ð       }Ð     }Ð     if (order[0].level == 1 && (m = str.match(/
^\s+/))) {Ð       order[0].from = m[0].length;Ð       order.unshift({from: 0,
to: m[0].length, level: 0});Ð     }Ð     if (lst(order).level == 1 && (m =
str.match(/\s+$/))) {Ð       lst(order).to -= m[0].length;Ð
order.push({from: len - m[0].length, to: len, level: 0});Ð     }Ð     if
(order[0].level != lst(order).level)Ð       order.push({from: len, to: len,
level: order[0].level});Ð     return order;Ð   };Ð })();Ð // THE ENDÐ
CodeMirror.version = "3.12";Ð return CodeMirror;Ð})();Ð
```

public\assets\editor\css.js

```
CodeMirror.defineMode("css", function(config) {Ð return
CodeMirror.getMode(config, "text/css");Þ});ÐodeMirror.defineMode("css-base",
function(config, parserConfig) {Ð "use strict";Ð var indentUnit =
config.indentUnit,Ð     hooks = parserConfig.hooks || {},Ð     atMediaTypes =
parserConfig.atMediaTypes || {},Ð     atMediaFeatures =
parserConfig.atMediaFeatures || {},Ð     propertyKeywords =
parserConfig.propertyKeywords || {},Ð     colorKeywords =
parserConfig.colorKeywords || {},Ð     valueKeywords =
parserConfig.valueKeywords || {},Ð     allowNested = !!
parserConfig.allowNested,Ð     type = null;Ð function ret(style, tp) { type =
tp; return style; }Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (hooks[ch]) {Ð     // result[0] is style and result[1]
is typeÐ     var result = hooks[ch](stream, state);Ð     if (result !==
false) return result;Ð   }Ð   if (ch == "@") {stream.eatWhile(/[\w\\\-]/);
return ret("def", stream.current());}Ð   else if (ch == "=") ret(null,
"compare");Ð   else if ((ch == "~" || ch == "|") && stream.eat("=")) return
ret(null, "compare");Ð   else if (ch == "\"" || ch == "'") {Ð
state.tokenize = tokenString(ch);Ð     return state.tokenize(stream, state);Ð
    }Ð   else if (ch == "#") {Ð     stream.eatWhile(/[\w\\\-]/);Ð     return
ret("atom", "hash");Ð   }Ð   else if (ch == "!") {Ð     stream.match(/
^\s*\w*/);Ð     return ret("keyword", "important");Ð   }Ð   else if (/
\d/.test(ch)) {Ð     stream.eatWhile(/[\w.%]/);Ð     return ret("number",
"unit");Ð   }Ð   else if (ch === "-") {Ð     if (/\d/.test(stream.peek())) {Ð
        stream.eatWhile(/[\w.%]/);Ð       return ret("number", "unit");Ð
      } else if (stream.match(/^[^-]+-/)) {Ð       return ret("meta", "meta");Ð
      }Ð   }Ð   else if (/[,+>*\/]/.test(ch)) {Ð     return ret(null, "select-
op");Ð   }Ð   else if (ch == "." && stream.match(/^-?[_a-z][_a-z0-9-]*/i)) {Ð
      return ret("qualifier", "qualifier");Ð   }Ð   else if (ch == ":") {Ð
      return ret("operator", ch);Ð   }Ð   else if (/[;{}\[\]\(\)]/.test(ch)) {Ð
      return ret(null, ch);Ð   }Ð   else if (ch == "u" &&
stream.match("rl(")) {Ð     stream.backUp(1);Ð     state.tokenize =
tokenParenthesized;Ð     return ret("property", "variable");Ð   }Ð   else {Ð
      stream.eatWhile(/[\w\\\-]/);Ð     return ret("property", "variable");Ð
    }Ð }Ð function tokenString(quote, nonInclusive) {Ð   return
function(stream, state) {Ð     var escaped = false, ch;Ð     while ((ch =
stream.next()) != null) {Ð       if (ch == quote && !escaped)Ð         break;Ð
        escaped = !escaped && ch == "\\";Ð     }Ð     if (!escaped) {Ð
if (nonInclusive) stream.backUp(1);Ð       state.tokenize = tokenBase;Ð     }Ð
      return ret("string", "string");Ð   };Ð }Ð function
tokenParenthesized(stream, state) {Ð   stream.next(); // Must be '('Ð   if (!
stream.match(/\s*[\"\']/, false))Ð     state.tokenize = tokenString(")",
true);Ð   elseÐ     state.tokenize = tokenBase;Ð   return ret(null, "(");Ð }Ð
return {Ð   startState: function(base) {Ð     return {tokenize: tokenBase,Ð
              baseIndent: base || 0,Ð             stack: []};Ð   },Ð   token:
function(stream, state) {Ð     // Use these terms when applicable (see http://
www.xanthir.com/blog/b4E50)Ð     //Ð     // rule** or **ruleset:Ð     // A
selector + braces combo, or an at-rule.Ð     //Ð     // declaration block:Ð
      // A sequence of declarations.Ð     //Ð     // declaration:Ð     // A
property + colon + value combo.Ð     //Ð     // property value:Ð     // The
entire value of a property.Ð     //Ð     // component value:Ð     // A single
piece of a property value. Like the 5px inÐ     // text-shadow: 0 0 5px
blue;. Can also refer to things that areÐ     // multiple terms, like the 1-4
terms that make up the background-sizeÐ     // portion of the background
shorthand.Ð     //Ð     // term:Ð     // The basic unit of author-facing CSS,
like a single number (5),Ð     // dimension (5px), string ("foo"), or
function. Officially definedÐ     //  by the CSS 2.1 grammar (look for the
'term' production)Ð     //Ð     //Ð     // simple selector:Ð     // A single
atomic selector, like a type selector, an attr selector, aÐ     // class
selector, etc.Ð
```

```
                    //Ð     // compound selector:Ð     // One or more simple
selectors without a combinator. div.example isÐ     // compound, div
> .example is not.Ð     //Ð     // complex selector:Ð     // One or more
compound selectors chained with combinators.Ð     //Ð     // combinator:Ð
      // The parts of selectors that express relationships. There are fourÐ
      // currently - the space (descendant combinator), the greater-thanÐ
      // bracket (child combinator), the plus sign (next sibling combinator),Ð
      // and the tilda (following sibling combinator).Ð     //Ð     //
sequence of selectors:Ð     // One or more of the named type of selector
chained with commas.Ð     state.tokenize = state.tokenize || tokenBase;Ð
if (state.tokenize == tokenBase && stream.eatSpace()) return null;Ð     var
style = state.tokenize(stream, state);Ð     if (style && typeof style !=
"string") style = ret(style[0], style[1]);Ð     // Changing style returned
based on contextÐ     var context = state.stack[state.stack.length-1];Ð
if (style == "variable") {Ð       if (type == "variable-definition")
state.stack.push("propertyValue");Ð       return "variable-2";Ð     } else if
(style == "property") {Ð       if (context == "propertyValue"){Ð         if
(valueKeywords[stream.current()]) {Ð           style = "string-2";Ð         }
else if (colorKeywords[stream.current()]) {Ð           style = "keyword";Ð
          } else {Ð           style = "variable-2";Ð         }Ð       } else
if (context == "rule") {Ð         if (!propertyKeywords[stream.current()]) {Ð
            style += " error";Ð         }Ð       } else if (context ==
"block") {Ð         // if a value is present in both property, value, or
color, the orderÐ         // of preference is property -> color -> valueÐ
          if (propertyKeywords[stream.current()]) {Ð           style =
"property";Ð         } else if (colorKeywords[stream.current()]) {Ð
style = "keyword";Ð         } else if (valueKeywords[stream.current()]) {Ð
            style = "string-2";Ð         } else {Ð           style = "tag";Ð
          }Ð       } else if (!context || context == "@media{") {Ð
style = "tag";Ð       } else if (context == "@media") {Ð         if
(atMediaTypes[stream.current()]) {Ð           style = "attribute"; // Known
attributeÐ         } else if (/^(only|not)$/i.test(stream.current())) {Ð
            style = "keyword";Ð         } else if
(stream.current().toLowerCase() == "and") {Ð           style = "error"; //
"and" is only allowed in @mediaTypeÐ         } else if
(atMediaFeatures[stream.current()]) {Ð           style = "error"; // Known
property, should be in @mediaType(Ð         } else {Ð           // Unknown,
expecting keyword or attribute, assuming attributeÐ           style =
"attribute error";Ð         }Ð       } else if (context == "@mediaType") {Ð
          if (atMediaTypes[stream.current()]) {Ð           style =
"attribute";Ð         } else if (stream.current().toLowerCase() == "and") {Ð
            style = "operator";Ð         } else if (/^(only|not)$/
i.test(stream.current())) {Ð           style = "error"; // Only allowed in
@mediaÐ         } else if (atMediaFeatures[stream.current()]) {Ð
style = "error"; // Known property, should be in parenthesesÐ         } else {Ð
            // Unknown attribute or property, but expecting property (precededÐ
            // by "and"). Should be in parenthesesÐ           style = "error";Ð
          }Ð       } else if (context == "@mediaType(") {Ð         if
(propertyKeywords[stream.current()]) {Ð           // do nothing, remains
"property"Ð         } else if (atMediaTypes[stream.current()]) {Ð
style = "error"; // Known property, should be in parenthesesÐ         } else
if (stream.current().toLowerCase() == "and") {Ð           style = "operator";Ð
          } else if (/^(only|not)$/i.test(stream.current())) {Ð
style = "error"; // Only allowed in @mediaÐ         } else {Ð           style
+= " error";Ð         }Ð       } else {Ð         style = "error";Ð       }Ð
      } else if (style == "atom") {Ð       if(!context || context ==
"@media{" || context == "block") {Ð         style = "builtin";Ð       } else
if (context == "propertyValue") {Ð         if (!/^#([0-9a-fA-f]{3}|[0-9a-fA-f]
{6})$/.test(stream.current())) {Ð           style += " error";Ð         }Ð
        } else {Ð
```

style = "error";Ð }Ð } else if (context == "@media" && type == "{") {Ð style = "error";Ð }Ð // Push/pop context stackÐ if (type == "{") {Ð if (context == "@media" || context == "@mediaType") {Ð state.stack.pop();Ð state.stack[state.stack.length-1] = "@media{";Ð }Ð else {Ð var newContext = allowNested ? "block" : "rule";Ð state.stack.push(newContext);Ð }Ð }Ð else if (type == "}") {Ð var lastState = state.stack[state.stack.length - 1];Ð if (lastState == "interpolation") style = "operator";Ð state.stack.pop();Ð if (context == "propertyValue") state.stack.pop();Ð }Ð else if (type == "interpolation") state.stack.push("interpolation");Ð else if (type == "@media") state.stack.push("@media");Ð else if (context == "@media" && /\b(keyword|attribute)\b/.test(style))Ð state.stack.push("@mediaType");Ð else if (context == "@mediaType" && stream.current() == ",") state.stack.pop();Ð else if (context == "@mediaType" && type == "(") state.stack.push("@mediaType(");Ð else if (context == "@mediaType(" && type == ")") state.stack.pop();Ð else if ((context == "rule" || context == "block") && type == ":") state.stack.push("propertyValue");Ð else if (context == "propertyValue" && type == ";") state.stack.pop();Ð return style;Ð },Ð indent: function(state, textAfter) {Ð var n = state.stack.length;Ð if (/^\}/.test(textAfter))Ð n -= state.stack[state.stack.length-1] == "propertyValue" ? 2 : 1;Ð return state.baseIndent + n * indentUnit;Ð },Ð electricChars: "}"Ð };Ð});Ð(function() {Ð function keySet(array) {Ð var keys = {};Ð for (var i = 0; i < array.length; ++i) {Ð keys[array[i]] = true;Ð }Ð return keys;Ð }Ð var atMediaTypes = keySet([Ð "all", "aural", "braille", "handheld", "print", "projection", "screen",Ð "tty", "tv", "embossed"Ð]);Ð var atMediaFeatures = keySet([Ð "width", "min-width", "max-width", "height", "min-height", "max-height",Ð "device-width", "min-device-width", "max-device-width", "device-height",Ð "min-device-height", "max-device-height", "aspect-ratio",Ð "min-aspect-ratio", "max-aspect-ratio", "device-aspect-ratio",Ð "min-device-aspect-ratio", "max-device-aspect-ratio", "color", "min-color",Ð "max-color", "color-index", "min-color-index", "max-color-index",Ð "monochrome", "min-monochrome", "max-monochrome", "resolution",Ð "min-resolution", "max-resolution", "scan", "grid"Ð]);Ð var propertyKeywords = keySet([Ð "align-content", "align-items", "align-self", "alignment-adjust",Ð "alignment-baseline", "anchor-point", "animation", "animation-delay",Ð "animation-direction", "animation-duration", "animation-iteration-count",Ð "animation-name", "animation-play-state", "animation-timing-function",Ð "appearance", "azimuth", "backface-visibility", "background",Ð "background-attachment", "background-clip", "background-color",Ð "background-image", "background-origin", "background-position",Ð "background-repeat", "background-size", "baseline-shift", "binding",Ð "bleed", "bookmark-label", "bookmark-level", "bookmark-state",Ð "bookmark-target", "border", "border-bottom", "border-bottom-color",Ð "border-bottom-left-radius", "border-bottom-right-radius",Ð "border-bottom-style", "border-bottom-width", "border-collapse",Ð "border-color", "border-image", "border-image-outset",Ð "border-image-repeat", "border-image-slice", "border-image-source",Ð "border-image-width", "border-left", "border-left-color",Ð "border-left-style", "border-left-width", "border-radius", "border-right",Ð "border-right-color", "border-right-style", "border-right-width",Ð "border-spacing", "border-style", "border-top", "border-top-color",Ð "border-top-left-radius", "border-top-right-radius", "border-top-style",Ð "border-top-width", "border-width", "bottom", "box-decoration-break",Ð "box-shadow", "box-sizing", "break-after", "break-before", "break-inside",Ð "caption-side", "clear", "clip", "color", "color-profile", "column-count",Ð "column-fill", "column-gap", "column-rule", "column-rule-color",Ð "column-rule-style", "column-rule-width", "column-span", "column-width",Ð "columns", "content", "counter-increment", "counter-reset", "crop", "cue",Ð

"cue-after", "cue-before", "cursor", "direction", "display",Ð "dominant-baseline", "drop-initial-after-adjust",Ð "drop-initial-after-align", "drop-initial-before-adjust",Ð "drop-initial-before-align", "drop-initial-size", "drop-initial-value",Ð "elevation", "empty-cells", "fit", "fit-position", "flex", "flex-basis",Ð "flex-direction", "flex-flow", "flex-grow", "flex-shrink", "flex-wrap",Ð "float", "float-offset", "font", "font-feature-settings", "font-family",Ð "font-kerning", "font-language-override", "font-size", "font-size-adjust",Ð "font-stretch", "font-style", "font-synthesis", "font-variant",Ð "font-variant-alternates", "font-variant-caps", "font-variant-east-asian",Ð "font-variant-ligatures", "font-variant-numeric", "font-variant-position",Ð "font-weight", "grid-cell", "grid-column", "grid-column-align",Ð "grid-column-sizing", "grid-column-span", "grid-columns", "grid-flow",Ð "grid-row", "grid-row-align", "grid-row-sizing", "grid-row-span",Ð "grid-rows", "grid-template", "hanging-punctuation", "height", "hyphens",Ð "icon", "image-orientation", "image-rendering", "image-resolution",Ð "inline-box-align", "justify-content", "left", "letter-spacing",Ð "line-break", "line-height", "line-stacking", "line-stacking-ruby",Ð "line-stacking-shift", "line-stacking-strategy", "list-style",Ð "list-style-image", "list-style-position", "list-style-type", "margin",Ð "margin-bottom", "margin-left", "margin-right", "margin-top",Ð "marker-offset", "marks", "marquee-direction", "marquee-loop",Ð "marquee-play-count", "marquee-speed", "marquee-style", "max-height",Ð "max-width", "min-height", "min-width", "move-to", "nav-down", "nav-index",Ð "nav-left", "nav-right", "nav-up", "opacity", "order", "orphans", "outline",Ð "outline-color", "outline-offset", "outline-style", "outline-width",Ð "overflow", "overflow-style", "overflow-wrap", "overflow-x", "overflow-y",Ð "padding", "padding-bottom", "padding-left", "padding-right", "padding-top",Ð "page", "page-break-after", "page-break-before", "page-break-inside",Ð "page-policy", "pause", "pause-after", "pause-before", "perspective",Ð "perspective-origin", "pitch", "pitch-range", "play-during", "position",Ð "presentation-level", "punctuation-trim", "quotes", "rendering-intent",Ð "resize", "rest", "rest-after", "rest-before", "richness", "right",Ð "rotation", "rotation-point", "ruby-align", "ruby-overhang",Ð "ruby-position", "ruby-span", "size", "speak", "speak-as", "speak-header",Ð "speak-numeral", "speak-punctuation", "speech-rate", "stress", "string-set",Ð "tab-size", "table-layout", "target", "target-name", "target-new",Ð "target-position", "text-align", "text-align-last", "text-decoration",Ð "text-decoration-color", "text-decoration-line", "text-decoration-skip",Ð "text-decoration-style", "text-emphasis", "text-emphasis-color",Ð "text-emphasis-position", "text-emphasis-style", "text-height",Ð "text-indent", "text-justify", "text-outline", "text-shadow",Ð "text-space-collapse", "text-transform", "text-underline-position",Ð "text-wrap", "top", "transform", "transform-origin", "transform-style",Ð "transition", "transition-delay", "transition-duration",Ð "transition-property", "transition-timing-function", "unicode-bidi",Ð "vertical-align", "visibility", "voice-balance", "voice-duration",Ð "voice-family", "voice-pitch", "voice-range", "voice-rate", "voice-stress",Ð "voice-volume", "volume", "white-space", "widows", "width", "word-break",Ð "word-spacing", "word-wrap", "z-index"Ð];Ð var colorKeywords = keySet([Ð "black", "silver", "gray", "white", "maroon", "red", "purple", "fuchsia",Ð "green", "lime", "olive", "yellow", "navy", "blue", "teal", "aqua"Ð];Ð var valueKeywords = keySet([Ð "above", "absolute", "activeborder", "activecaption", "afar",Ð "after-white-space", "ahead", "alias", "all", "all-scroll", "alternate",Ð "always", "amharic", "amharic-abegede", "antialiased", "appworkspace",Ð "arabic-indic", "armenian", "asterisks", "auto", "avoid", "background",Ð "backwards", "baseline", "below", "bidi-override", "binary", "bengali",Ð "blink", "block", "block-axis", "bold", "bolder", "border", "border-box",Ð "both", "bottom", "break-all", "break-word", "button", "button-bevel",Ð "buttonface", "buttonhighlight", "buttonshadow", "buttontext", "cambodian",Ð

"capitalize", "caps-lock-indicator", "caption", "captiontext", "caret",Ð "cell", "center", "checkbox", "circle", "cjk-earthly-branch",Ð "cjk-heavenly-stem", "cjk-ideographic", "clear", "clip", "close-quote",Ð "col-resize", "collapse", "compact", "condensed", "contain", "content",Ð "content-box", "context-menu", "continuous", "copy", "cover", "crop",Ð "cross", "crosshair", "currentcolor", "cursive", "dashed", "decimal",Ð "decimal-leading-zero", "default", "default-button", "destination-atop",Ð "destination-in", "destination-out", "destination-over", "devanagari",Ð "disc", "discard", "document", "dot-dash", "dot-dot-dash", "dotted",Ð "double", "down", "e-resize", "ease", "ease-in", "ease-in-out", "ease-out",Ð "element", "ellipsis", "embed", "end", "ethiopic", "ethiopic-abegede",Ð "ethiopic-abegede-am-et", "ethiopic-abegede-gez", "ethiopic-abegede-ti-er",Ð "ethiopic-abegede-ti-et", "ethiopic-halehame-aa-er",Ð "ethiopic-halehame-aa-et", "ethiopic-halehame-am-et",Ð "ethiopic-halehame-gez", "ethiopic-halehame-om-et",Ð "ethiopic-halehame-sid-et", "ethiopic-halehame-so-et",Ð "ethiopic-halehame-ti-er", "ethiopic-halehame-ti-et",Ð "ethiopic-halehame-tig", "ew-resize", "expanded", "extra-condensed",Ð "extra-expanded", "fantasy", "fast", "fill", "fixed", "flat", "footnotes",Ð "forwards", "from", "geometricPrecision", "georgian", "graytext", "groove",Ð "gujarati", "gurmukhi", "hand", "hangul", "hangul-consonant", "hebrew",Ð "help", "hidden", "hide", "higher", "highlight", "highlighttext",Ð "hiragana", "hiragana-iroha", "horizontal", "hsl", "hsla", "icon", "ignore",Ð "inactiveborder", "inactivecaption", "inactivecaptiontext", "infinite",Ð "infobackground", "infotext", "inherit", "initial", "inline", "inline-axis",Ð "inline-block", "inline-table", "inset", "inside", "intrinsic", "invert",Ð "italic", "justify", "kannada", "katakana", "katakana-iroha", "khmer",Ð "landscape", "lao", "large", "larger", "left", "level", "lighter",Ð "line-through", "linear", "lines", "list-item", "listbox", "listitem",Ð "local", "logical", "loud", "lower", "lower-alpha", "lower-armenian",Ð "lower-greek", "lower-hexadecimal", "lower-latin", "lower-norwegian",Ð "lower-roman", "lowercase", "ltr", "malayalam", "match",Ð "media-controls-background", "media-current-time-display",Ð "media-fullscreen-button", "media-mute-button", "media-play-button",Ð "media-return-to-realtime-button", "media-rewind-button",Ð "media-seek-back-button", "media-seek-forward-button", "media-slider",Ð "media-sliderthumb", "media-time-remaining-display", "media-volume-slider",Ð "media-volume-slider-container", "media-volume-sliderthumb", "medium",Ð "menu", "menulist", "menulist-button", "menulist-text",Ð "menulist-textfield", "menutext", "message-box", "middle", "min-intrinsic",Ð "mix", "mongolian", "monospace", "move", "multiple", "myanmar", "n-resize",Ð "narrower", "ne-resize", "nesw-resize", "no-close-quote", "no-drop",Ð "no-open-quote", "no-repeat", "none", "normal", "not-allowed", "nowrap",Ð "ns-resize", "nw-resize", "nwse-resize", "oblique", "octal", "open-quote",Ð "optimizeLegibility", "optimizeSpeed", "oriya", "oromo", "outset",Ð "outside", "overlay", "overline", "padding", "padding-box", "painted",Ð "paused", "persian", "plus-darker", "plus-lighter", "pointer", "portrait",Ð "pre", "pre-line", "pre-wrap", "preserve-3d", "progress", "push-button",Ð "radio", "read-only", "read-write", "read-write-plaintext-only", "relative",Ð "repeat", "repeat-x", "repeat-y", "reset", "reverse", "rgb", "rgba",Ð "ridge", "right", "round", "row-resize", "rtl", "run-in", "running",Ð "s-resize", "sans-serif", "scroll", "scrollbar", "se-resize", "searchfield",Ð "searchfield-cancel-button", "searchfield-decoration",Ð "searchfield-results-button", "searchfield-results-decoration",Ð "semi-condensed", "semi-expanded", "separate", "serif", "show", "sidama",Ð "single", "skip-white-space", "slide", "slider-horizontal",Ð "slider-vertical", "sliderthumb-horizontal", "sliderthumb-vertical", "slow",Ð "small", "small-caps", "small-caption", "smaller", "solid", "somali",Ð "source-atop", "source-in", "source-out", "source-over", "space", "square",Ð "square-button", "start", "static", "status-bar", "stretch", "stroke",Ð

"sub", "subpixel-antialiased", "super", "sw-resize", "table",Ð "table-caption", "table-cell", "table-column", "table-column-group",Ð "table-footer-group", "table-header-group", "table-row", "table-row-group",Ð "telugu", "text", "text-bottom", "text-top", "textarea", "textfield", "thai",Ð "thick", "thin", "threeddarkshadow", "threedface", "threedhighlight",Ð "threedlightshadow", "threedshadow", "tibetan", "tigre", "tigrinya-er",Ð "tigrinya-er-abegede", "tigrinya-et", "tigrinya-et-abegede", "to", "top",Ð "transparent", "ultra-condensed", "ultra-expanded", "underline", "up",Ð "upper-alpha", "upper-armenian", "upper-greek", "upper-hexadecimal",Ð "upper-latin", "upper-norwegian", "upper-roman", "uppercase", "urdu", "url",Ð "vertical", "vertical-text", "visible", "visibleFill", "visiblePainted",Ð "visibleStroke", "visual", "w-resize", "wait", "wave", "white", "wider",Ð "window", "windowframe", "windowtext", "x-large", "x-small", "xor",Ð "xx-large", "xx-small"Ð]);Ð function tokenCComment(stream, state) {Ð var maybeEnd = false, ch;Ð while ((ch = stream.next()) != null) {Ð if (maybeEnd && ch == "/") {Ð state.tokenize = null;Ð break;Ð }Ð maybeEnd = (ch == "*");Ð }Ð return ["comment", "comment"];Ð }Ð CodeMirror.defineMIME("text/css", {Ð atMediaTypes: atMediaTypes,Ð atMediaFeatures: atMediaFeatures,Ð propertyKeywords: propertyKeywords,Ð colorKeywords: colorKeywords,Ð valueKeywords: valueKeywords,Ð hooks: {Ð "<": function(stream, state) {Ð function tokenSGMLComment(stream, state) {Ð var dashes = 0, ch;Ð while ((ch = stream.next()) != null) {Ð if (dashes >= 2 && ch == ">") {Ð state.tokenize = null;Ð break;Ð }Ð dashes = (ch == "-") ? dashes + 1 : 0;Ð }Ð return ["comment", "comment"];Ð }Ð if (stream.eat("!")) {Ð state.tokenize = tokenSGMLComment;Ð return tokenSGMLComment(stream, state);Ð }Ð },Ð "/": function(stream, state) {Ð if (stream.eat("*")) {Ð state.tokenize = tokenCComment;Ð return tokenCComment(stream, state);Ð }Ð return false;Ð }Ð },Ð name: "css-base"Ð });Ð CodeMirror.defineMIME("text/x-scss", {Ð atMediaTypes: atMediaTypes,Ð atMediaFeatures: atMediaFeatures,Ð propertyKeywords: propertyKeywords,Ð colorKeywords: colorKeywords,Ð valueKeywords: valueKeywords,Ð allowNested: true,Ð hooks: {Ð "$": function(stream) {Ð stream.match(/^[\w-]+/);Ð if (stream.peek() == ":") {Ð return ["variable", "variable-definition"];Ð }Ð return ["variable", "variable"];Ð },Ð "/": function(stream, state) {Ð if (stream.eat("/")) {Ð stream.skipToEnd();Ð return ["comment", "comment"];Ð } else if (stream.eat("*")) {Ð state.tokenize = tokenCComment;Ð return tokenCComment(stream, state);Ð } else {Ð return ["operator", "operator"];Ð }Ð },Ð "#": function(stream) {Ð if (stream.eat("{")) {Ð return ["operator", "interpolation"];Ð } else {Ð stream.eatWhile(/[\w\\\-]/);Ð return ["atom", "hash"];Ð }Ð }Ð },Ð name: "css-base"Ð });Ð})();Ð

public\assets\editor\htmlmixed.js

```
CodeMirror.defineMode("htmlmixed", function(config, parserConfig) {Ð var
htmlMode = CodeMirror.getMode(config, {name: "xml", htmlMode: true});Ð var
cssMode = CodeMirror.getMode(config, "css");Ð var scriptTypes = [],
scriptTypesConf = parserConfig && parserConfig.scriptTypes;Ð
scriptTypes.push({matches: /^(?:text|application)\/(?:x-)?(?:java|
ecma)script$|^$/i,Ð                    mode: CodeMirror.getMode(config,
"javascript")});Ð if (scriptTypesConf) for (var i = 0; i <
scriptTypesConf.length; ++i) {Ð   var conf = scriptTypesConf[i];Ð
scriptTypes.push({matches: conf.matches, mode: conf.mode &&
CodeMirror.getMode(config, conf.mode)});Ð }Ð scriptTypes.push({matches: /./,Ð
                     mode: CodeMirror.getMode(config, "text/plain")});Ð
function html(stream, state) {Ð   var tagName = state.htmlState.tagName;Ð
var style = htmlMode.token(stream, state.htmlState);Ð   if (tagName ==
"script" && /\btag\b/.test(style) && stream.current() == ">") {Ð     //
Script block: mode to change to depends on type attributeÐ     var scriptType
= stream.string.slice(Math.max(0, stream.pos - 100), stream.pos).match(/
\btype\s*=\s*("[^"]+"|'[^']+'|\S+)[^<]*$/i);Ð     scriptType = scriptType ?
scriptType[1] : "";Ð     if (scriptType && /
[\"\']/.test(scriptType.charAt(0))) scriptType = scriptType.slice(1,
scriptType.length - 1);Ð     for (var i = 0; i < scriptTypes.length; ++i) {Ð
        var tp = scriptTypes[i];Ð       if (typeof tp.matches == "string" ?
scriptType == tp.matches : tp.matches.test(scriptType)) {Ð         if
(tp.mode) {Ð           state.token = script;Ð           state.localMode =
tp.mode;Ð           state.localState = tp.mode.startState &&
tp.mode.startState(htmlMode.indent(state.htmlState, ""));Ð         }Ð
break;Ð       }Ð     }Ð   } else if (tagName == "style" && /
\btag\b/.test(style) && stream.current() == ">") {Ð     state.token = css;Ð
      state.localMode = cssMode;Ð     state.localState =
cssMode.startState(htmlMode.indent(state.htmlState, ""));Ð   }Ð   return
style;Ð }Ð function maybeBackup(stream, pat, style) {Ð   var cur =
stream.current();Ð   var close = cur.search(pat), m;Ð   if (close > -1)
stream.backUp(cur.length - close);Ð   else if (m = cur.match(/<\/?$/)) {Ð
stream.backUp(cur.length);Ð     if (!stream.match(pat, false))
stream.match(cur[0]);Ð   }Ð   return style;Ð }Ð function script(stream,
state) {Ð   if (stream.match(/^<\/\s*script\s*>/i, false)) {Ð     state.token
= html;Ð     state.localState = state.localMode = null;Ð     return
html(stream, state);Ð   }Ð   return maybeBackup(stream, /<\/\s*script\s*>/,Ð
                       state.localMode.token(stream, state.localState));Ð }Ð
function css(stream, state) {Ð   if (stream.match(/^<\/\s*style\s*>/i,
false)) {Ð     state.token = html;Ð     state.localState = state.localMode =
null;Ð     return html(stream, state);Ð   }Ð   return maybeBackup(stream, /<\/
\s*style\s*>/,Ð                       cssMode.token(stream, state.localState));Ð
  }Ð return {Ð   startState: function() {Ð     var state =
htmlMode.startState();Ð     return {token: html, localMode: null, localState:
null, htmlState: state};Ð   },Ð   copyState: function(state) {Ð     if
(state.localState)Ð       var local = CodeMirror.copyState(state.localMode,
state.localState);Ð     return {token: state.token, localMode:
state.localMode, localState: local,Ð             htmlState:
CodeMirror.copyState(htmlMode, state.htmlState)};Ð   },Ð   token:
function(stream, state) {Ð     return state.token(stream, state);Ð   },Ð
indent: function(state, textAfter) {Ð     if (!state.localMode || /
^\s*<\//.test(textAfter))Ð       return htmlMode.indent(state.htmlState,
textAfter);Ð     else if (state.localMode.indent)Ð       return
state.localMode.indent(state.localState, textAfter);Ð     elseÐ       return
CodeMirror.Pass;Ð   },Ð   electricChars: "/{}:",Ð   innerMode:
function(state) {Ð     return {state: state.localState || state.htmlState,
mode: state.localMode || htmlMode};Ð   }Ð };Ð, "xml", "javascript", "css");Ð
CodeMirror.defineMIME("text/html", "htmlmixed");Ð
```

public\assets\editor\javascript.js

```
// TODO actually recognize syntax of TypeScript constructsÐ
CodeMirror.defineMode("javascript", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit;Ð var jsonMode = parserConfig.json;Ð var isTS
= parserConfig.typescript;Ð // TokenizerÐ var keywords = function(){Ð
function kw(type) {return {type: type, style: "keyword"};}Ð   var A =
kw("keyword a"), B = kw("keyword b"), C = kw("keyword c");Ð   var operator =
kw("operator"), atom = {type: "atom", style: "atom"};Ð   var jsKeywords = {Ð
      "if": kw("if"), "while": A, "with": A, "else": B, "do": B, "try": B,
"finally": B,Ð     "return": C, "break": C, "continue": C, "new": C,
"delete": C, "throw": C,Ð     "var": kw("var"), "const": kw("var"), "let":
kw("var"),Ð     "function": kw("function"), "catch": kw("catch"),Ð     "for":
kw("for"), "switch": kw("switch"), "case": kw("case"), "default":
kw("default"),Ð     "in": operator, "typeof": operator, "instanceof":
operator,Ð     "true": atom, "false": atom, "null": atom, "undefined": atom,
"NaN": atom, "Infinity": atom,Ð     "this": kw("this")Ð   };Ð   // Extend the
'normal' keywords with the TypeScript language extensionsÐ   if (isTS) {Ð
var type = {type: "variable", style: "variable-3"};Ð     var tsKeywords = {Ð
        // object-like thingsÐ       "interface": kw("interface"),Ð
"class": kw("class"),Ð       "extends": kw("extends"),Ð       "constructor":
kw("constructor"),Ð       // scope modifiersÐ       "public": kw("public"),Ð
        "private": kw("private"),Ð       "protected": kw("protected"),Ð
"static": kw("static"),Ð       "super": kw("super"),Ð       // typesÐ
"string": type, "number": type, "bool": type, "any": typeÐ     };Ð     for
(var attr in tsKeywords) {Ð       jsKeywords[attr] = tsKeywords[attr];Ð     }Ð
    }Ð   return jsKeywords;Ð }();Ð var isOperatorChar = /[+\-*&%=<>!?|~^]/;Ð
function chain(stream, state, f) {Ð   state.tokenize = f;Ð   return f(stream,
state);Ð }Ð function nextUntilUnescaped(stream, end) {Ð   var escaped =
false, next;Ð   while ((next = stream.next()) != null) {Ð     if (next == end
&& !escaped)Ð       return false;Ð     escaped = !escaped && next == "\\";Ð
    }Ð   return escaped;Ð }Ð // Used as scratch variables to communicate
multiple values withoutÐ // consing up tons of objects.Ð var type, content;Ð
function ret(tp, style, cont) {Ð   type = tp; content = cont;Ð   return style;Ð
  }Ð function jsTokenBase(stream, state) {Ð   var ch = stream.next();Ð   if
(ch == '"' || ch == "'")Ð     return chain(stream, state, jsTokenString(ch));Ð
    else if (/[\[\]{}\(\),;\:\.]/.test(ch))Ð     return ret(ch);Ð   else if
(ch == "0" && stream.eat(/x/i)) {Ð     stream.eatWhile(/[\da-f]/i);Ð
return ret("number", "number");Ð   }Ð   else if (/\d/.test(ch) || ch == "-"
&& stream.eat(/\d/)) {Ð     stream.match(/^\d*(?:\.\d*)?(?:[eE][+\-]?\d+)?/);Ð
      return ret("number", "number");Ð   }Ð   else if (ch == "/") {Ð     if
(stream.eat("*")) {Ð       return chain(stream, state, jsTokenComment);Ð     }Ð
      else if (stream.eat("/")) {Ð       stream.skipToEnd();Ð       return
ret("comment", "comment");Ð     }Ð     else if (state.lastType == "operator"
|| state.lastType == "keyword c" ||Ð              /
^[\[{}\(,;:]$/.test(state.lastType)) {Ð       nextUntilUnescaped(stream, "/");Ð
        stream.eatWhile(/[gimy]/); // 'y' is "sticky" option in MozillaÐ
        return ret("regexp", "string-2");Ð     }Ð     else {Ð
stream.eatWhile(isOperatorChar);Ð       return ret("operator", null,
stream.current());Ð     }Ð   }Ð   else if (ch == "#") {Ð
stream.skipToEnd();Ð     return ret("error", "error");Ð   }Ð   else if
(isOperatorChar.test(ch)) {Ð     stream.eatWhile(isOperatorChar);Ð     return
ret("operator", null, stream.current());Ð   }Ð   else {Ð     stream.eatWhile(/
[\w\$_]/);Ð     var word = stream.current(), known =
keywords.propertyIsEnumerable(word) && keywords[word];Ð     return (known &&
state.lastType != ".") ? ret(known.type, known.style, word) :Ð
                     ret("variable", "variable", word);Ð   }Ð }Ð function
jsTokenString(quote) {Ð   return function(stream, state) {Ð     if (!
nextUntilUnescaped(stream, quote))Ð       state.tokenize = jsTokenBase;Ð
return ret("string", "string");Ð   };Ð }Ð function jsTokenComment(stream,
state) {Ð
```

```
            var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if
(ch == "/" && maybeEnd) {Ð       state.tokenize = jsTokenBase;Ð       break;Ð
      }Ð     maybeEnd = (ch == "*");Ð   }Ð   return ret("comment", "comment");Ð
  }Ð // ParserÐ var atomicTypes = {"atom": true, "number": true, "variable":
true, "string": true, "regexp": true, "this": true};Ð function
JSLexical(indented, column, type, align, prev, info) {Ð   this.indented =
indented;Ð   this.column = column;Ð   this.type = type;Ð   this.prev = prev;Ð
    this.info = info;Ð   if (align != null) this.align = align;Ð }Ð function
inScope(state, varname) {Ð   for (var v = state.localVars; v; v = v.next)Ð
      if (v.name == varname) return true;Ð }Ð function parseJS(state, style,
type, content, stream) {Ð   var cc = state.cc;Ð   // Communicate our context
to the combinators.Ð   // (Less wasteful than consing up a hundred closures
on every call.)Ð   cx.state = state; cx.stream = stream; cx.marked = null,
cx.cc = cc;Ð   if (!state.lexical.hasOwnProperty("align"))Ð
state.lexical.align = true;Ð   while(true) {Ð     var combinator =
cc.length ? cc.pop() : jsonMode ? expression : statement;Ð     if
(combinator(type, content)) {Ð       while(cc.length && cc[cc.length - 1].lex)Ð
          cc.pop()();Ð       if (cx.marked) return cx.marked;Ð       if (type
== "variable" && inScope(state, content)) return "variable-2";Ð       return
style;Ð     }Ð   }Ð }Ð // Combinator utilsÐ var cx = {state: null, column:
null, marked: null, cc: null};Ð function pass() {Ð   for (var i =
arguments.length - 1; i >= 0; i--) cx.cc.push(arguments[i]);Ð }Ð function
cont() {Ð   pass.apply(null, arguments);Ð   return true;Ð }Ð function
register(varname) {Ð   function inList(list) {Ð     for (var v = list; v; v =
v.next)Ð       if (v.name == varname) return true;Ð     return false;Ð   }Ð
var state = cx.state;Ð   if (state.context) {Ð     cx.marked = "def";Ð     if
(inList(state.localVars)) return;Ð     state.localVars = {name: varname,
next: state.localVars};Ð   } else {Ð     if (inList(state.globalVars)) return;Ð
      state.globalVars = {name: varname, next: state.globalVars};Ð   }Ð }Ð //
CombinatorsÐ var defaultVars = {name: "this", next: {name: "arguments"}};Ð
function pushcontext() {Ð   cx.state.context = {prev: cx.state.context, vars:
cx.state.localVars};Ð   cx.state.localVars = defaultVars;Ð }Ð function
popcontext() {Ð   cx.state.localVars = cx.state.context.vars;Ð
cx.state.context = cx.state.context.prev;Ð }Ð function pushlex(type, info) {Ð
    var result = function() {Ð     var state = cx.state;Ð     state.lexical =
new JSLexical(state.indented, cx.stream.column(), type, null, state.lexical,
info);Ð   };Ð   result.lex = true;Ð   return result;Ð }Ð function poplex() {Ð
    var state = cx.state;Ð   if (state.lexical.prev) {Ð     if
(state.lexical.type == ")")Ð       state.indented = state.lexical.indented;Ð
      state.lexical = state.lexical.prev;Ð   }Ð }Ð poplex.lex = true;Ð
function expect(wanted) {Ð   return function(type) {Ð     if (type == wanted)
return cont();Ð     else if (wanted == ";") return pass();Ð     else return
cont(arguments.callee);Ð   };Ð }Ð function statement(type) {Ð   if (type ==
"var") return cont(pushlex("vardef"), vardef1, expect(";"), poplex);Ð   if
(type == "keyword a") return cont(pushlex("form"), expression, statement,
poplex);Ð   if (type == "keyword b") return cont(pushlex("form"), statement,
poplex);Ð   if (type == "{") return cont(pushlex("}"), block, poplex);Ð   if
(type == ";") return cont();Ð   if (type == "if") return
cont(pushlex("form"), expression, statement, poplex,
maybeelse(cx.state.indented));Ð   if (type == "function") return
cont(functiondef);Ð   if (type == "for") return cont(pushlex("form"),
expect("("), pushlex(")"), forspec1, expect(")"),Ð
                                  poplex, statement, poplex);Ð   if (type
== "variable") return cont(pushlex("stat"), maybelabel);Ð   if (type ==
"switch") return cont(pushlex("form"), expression, pushlex("}", "switch"),
expect("{"),Ð                                         block, poplex, poplex);Ð
    if (type == "case") return cont(expression, expect(":"));Ð   if (type ==
"default") return cont(expect(":"));Ð   if (type == "catch") return
cont(pushlex("form"), pushcontext, expect("("), funarg, expect(")"),Ð
                                       statement, poplex, popcontext);Ð
```

```
return pass(pushlex("stat"), expression, expect(";"), poplex);Ð }Ð function
expression(type) {Ð   return expressionInner(type, maybeoperatorComma);Ð }Ð
function expressionNoComma(type) {Ð   return expressionInner(type,
maybeoperatorNoComma);Ð }Ð function expressionInner(type, maybeop) {Ð   if
(atomicTypes.hasOwnProperty(type)) return cont(maybeop);Ð   if (type ==
"function") return cont(functiondef);Ð   if (type == "keyword c") return
cont(maybeexpression);Ð   if (type == "(") return cont(pushlex(")"),
maybeexpression, expect(")"), poplex, maybeop);Ð   if (type == "operator")
return cont(expression);Ð   if (type == "[") return cont(pushlex("]"),
commasep(expressionNoComma, "]"), poplex, maybeop);Ð   if (type == "{")
return cont(pushlex("}"), commasep(objprop, "}"), poplex, maybeop);Ð   return
cont();Ð }Ð function maybeexpression(type) {Ð   if (type.match(/[;\}\)\],]/))
return pass();Ð   return pass(expression);Ð }Ð function
maybeoperatorComma(type, value) {Ð   if (type == ",") return cont(expression);Ð
    return maybeoperatorNoComma(type, value, maybeoperatorComma);Ð }Ð
function maybeoperatorNoComma(type, value, me) {Ð   if (!me) me =
maybeoperatorNoComma;Ð   if (type == "operator") {Ð     if (/\+\
+|--/.test(value)) return cont(me);Ð     if (value == "?") return
cont(expression, expect(":"), expression);Ð     return cont(expression);Ð   }Ð
    if (type == ";") return;Ð   if (type == "(") return cont(pushlex(")",
"call"), commasep(expressionNoComma, ")"), poplex, me);Ð   if (type == ".")
return cont(property, me);Ð   if (type == "[") return cont(pushlex("]"),
expression, expect("]"), poplex, me);Ð }Ð function maybelabel(type) {Ð   if
(type == ":") return cont(poplex, statement);Ð   return
pass(maybeoperatorComma, expect(";"), poplex);Ð }Ð function property(type) {Ð
    if (type == "variable") {cx.marked = "property"; return cont();}Ð }Ð
function objprop(type, value) {Ð   if (type == "variable") {Ð     cx.marked =
"property";Ð     if (value == "get" || value == "set") return
cont(getterSetter);Ð   } else if (type == "number" || type == "string") {Ð
      cx.marked = type + " property";Ð   }Ð   if
(atomicTypes.hasOwnProperty(type)) return cont(expect(":"),
expressionNoComma);Ð }Ð function getterSetter(type) {Ð   if (type == ":")
return cont(expression);Ð   if (type != "variable") return cont(expect(":"),
expression);Ð   cx.marked = "property";Ð   return cont(functiondef);Ð }Ð
function commasep(what, end) {Ð   function proceed(type) {Ð     if (type ==
",") {Ð       var lex = cx.state.lexical;Ð       if (lex.info == "call")
lex.pos = (lex.pos || 0) + 1;Ð       return cont(what, proceed);Ð     }Ð
if (type == end) return cont();Ð     return cont(expect(end));Ð   }Ð   return
function(type) {Ð     if (type == end) return cont();Ð     else return
pass(what, proceed);Ð   };Ð }Ð function block(type) {Ð   if (type == "}")
return cont();Ð   return pass(statement, block);Ð }Ð function maybetype(type)
{Ð   if (type == ":") return cont(typedef);Ð   return pass();Ð }Ð function
typedef(type) {Ð   if (type == "variable"){cx.marked = "variable-3"; return
cont();}Ð   return pass();Ð }Ð function vardef1(type, value) {Ð   if (type ==
"variable") {Ð     register(value);Ð     return isTS ? cont(maybetype,
vardef2) : cont(vardef2);Ð   }Ð   return pass();Ð }Ð function vardef2(type,
value) {Ð   if (value == "=") return cont(expressionNoComma, vardef2);Ð   if
(type == ",") return cont(vardef1);Ð }Ð function maybeelse(indent) {Ð
return function(type, value) {Ð     if (type == "keyword b" && value ==
"else") {Ð       cx.state.lexical = new JSLexical(indent, 0, "form", null,
cx.state.lexical);Ð       return cont(statement, poplex);Ð     }Ð     return
pass();Ð   };Ð }Ð function forspec1(type) {Ð   if (type == "var") return
cont(vardef1, expect(";"), forspec2);Ð   if (type == ";") return
cont(forspec2);Ð   if (type == "variable") return cont(formaybein);Ð   return
pass(expression, expect(";"), forspec2);Ð }Ð function formaybein(_type,
value) {Ð   if (value == "in") return cont(expression);Ð   return
cont(maybeoperatorComma, forspec2);Ð }Ð function forspec2(type, value) {Ð
if (type == ";") return cont(forspec3);Ð   if (value == "in") return
cont(expression);Ð
```

```
                    return pass(expression, expect(";"), forspec3);Ð }Ð
function forspec3(type) {Ð   if (type != ")") cont(expression);Ð }Ð function
functiondef(type, value) {Ð   if (type == "variable") {register(value);
return cont(functiondef);}Ð   if (type == "(") return cont(pushlex(")"),
pushcontext, commasep(funarg, ")"), poplex, statement, popcontext);Ð }Ð
function funarg(type, value) {Ð   if (type == "variable") {register(value);
return isTS ? cont(maybetype) : cont();}Ð }Ð // InterfaceÐ return {Ð
startState: function(basecolumn) {Ð     return {Ð       tokenize: jsTokenBase,Ð
        lastType: null,Ð       cc: [],Ð       lexical: new
JSLexical((basecolumn || 0) - indentUnit, 0, "block", false),Ð
localVars: parserConfig.localVars,Ð       globalVars: parserConfig.globalVars,Ð
        context: parserConfig.localVars && {vars: parserConfig.localVars},Ð
        indented: 0Ð     };Ð   },Ð   token: function(stream, state) {Ð     if
(stream.sol()) {Ð       if (!state.lexical.hasOwnProperty("align"))Ð
state.lexical.align = false;Ð       state.indented = stream.indentation();Ð
      }Ð     if (state.tokenize != jsTokenComment && stream.eatSpace())
return null;Ð     var style = state.tokenize(stream, state);Ð     if (type ==
"comment") return style;Ð     state.lastType = type == "operator" && (content
== "++" || content == "--") ? "incdec" : type;Ð     return parseJS(state,
style, type, content, stream);Ð   },Ð   indent: function(state, textAfter) {Ð
      if (state.tokenize == jsTokenComment) return CodeMirror.Pass;Ð     if
(state.tokenize != jsTokenBase) return 0;Ð     var firstChar = textAfter &&
textAfter.charAt(0), lexical = state.lexical;Ð     if (lexical.type == "stat"
&& firstChar == "}") lexical = lexical.prev;Ð     var type = lexical.type,
closing = firstChar == type;Ð     if (parserConfig.statementIndent != null) {Ð
        if (type == ")" && lexical.prev && lexical.prev.type == "stat")
lexical = lexical.prev;Ð       if (lexical.type == "stat") return
lexical.indented + parserConfig.statementIndent;Ð     }Ð     if (type ==
"vardef") return lexical.indented + (state.lastType == "operator" ||
state.lastType == "," ? 4 : 0);Ð     else if (type == "form" && firstChar ==
"{") return lexical.indented;Ð     else if (type == "form") return
lexical.indented + indentUnit;Ð     else if (type == "stat")Ð       return
lexical.indented + (state.lastType == "operator" || state.lastType == "," ?
indentUnit : 0);Ð     else if (lexical.info == "switch" && !closing)Ð
return lexical.indented + (/^(?:case|default)\b/.test(textAfter) ?
indentUnit : 2 * indentUnit);Ð     else if (lexical.align) return
lexical.column + (closing ? 0 : 1);Ð     else return lexical.indented +
(closing ? 0 : indentUnit);Ð   },Ð   electricChars: ":{}",Ð   jsonMode:
jsonModeÐ };Ð});ÐodeMirror.defineMIME("text/javascript", "javascript");Ð
CodeMirror.defineMIME("text/ecmascript", "javascript");Ð
CodeMirror.defineMIME("application/javascript", "javascript");Ð
CodeMirror.defineMIME("application/ecmascript", "javascript");Ð
CodeMirror.defineMIME("application/json", {name: "javascript", json: true});Ð
CodeMirror.defineMIME("text/typescript", { name: "javascript", typescript:
true });ÐodeMirror.defineMIME("application/typescript", { name: "javascript",
typescript: true });Ð
```

public\assets\editor\matchbrackets.js

```
(function() {Ð var ie_lt8 = /MSIE \d/.test(navigator.userAgent) &&Ð
(document.documentMode == null || document.documentMode < 8);Ð var Pos =
CodeMirror.Pos;Ð var matching = {"(": ")>", ")": "(<", "[": "]>", "]": "[<",
"{": "}>", "}": "{<"};Ð function findMatchingBracket(cm) {Ð   var maxScanLen
= cm.state._matchBrackets.maxScanLineLength || 10000;Ð   var cur =
cm.getCursor(), line = cm.getLineHandle(cur.line), pos = cur.ch - 1;Ð   var
match = (pos >= 0 && matching[line.text.charAt(pos)]) ||
matching[line.text.charAt(++pos)];Ð   if (!match) return null;Ð   var forward
= match.charAt(1) == ">", d = forward ? 1 : -1;Ð   var style =
cm.getTokenAt(Pos(cur.line, pos + 1)).type;Ð   var stack =
[line.text.charAt(pos)], re = /[(){}[\]]/;Ð   function scan(line, lineNo,
start) {Ð     if (!line.text) return;Ð     var pos = forward ? 0 :
line.text.length - 1, end = forward ? line.text.length : -1;Ð     if
(line.text.length > maxScanLen) return null;Ð     var checkTokenStyles =
line.text.length < 1000;Ð     if (start != null) pos = start + d;Ð     for (;
pos != end; pos += d) {Ð       var ch = line.text.charAt(pos);Ð       if
(re.test(ch) && (!checkTokenStyles || cm.getTokenAt(Pos(lineNo, pos +
1)).type == style)) {Ð         var match = matching[ch];Ð         if
(match.charAt(1) == ">" == forward) stack.push(ch);Ð         else if
(stack.pop() != match.charAt(0)) return {pos: pos, match: false};Ð
else if (!stack.length) return {pos: pos, match: true};Ð       }Ð     }Ð   }Ð
    for (var i = cur.line, found, e = forward ? Math.min(i + 100,
cm.lineCount()) : Math.max(-1, i - 100); i != e; i+=d) {Ð     if (i ==
cur.line) found = scan(line, i, pos);Ð     else found =
scan(cm.getLineHandle(i), i);Ð     if (found) break;Ð   }Ð   return {from:
Pos(cur.line, pos), to: found && Pos(i, found.pos), match: found &&
found.match};Ð }Ð function matchBrackets(cm, autoclear) {Ð   // Disable brace
matching in long lines, since it'll cause hugely slow updatesÐ   var
maxHighlightLen = cm.state._matchBrackets.maxHighlightLineLength || 1000;Ð
var found = findMatchingBracket(cm);Ð   if (!found ||
cm.getLine(found.from.line).length > maxHighlightLen ||Ð      found.to &&
cm.getLine(found.to.line).length > maxHighlightLen)Ð     return;Ð   var style
= found.match ? "CodeMirror-matchingbracket" : "CodeMirror-
nonmatchingbracket";Ð   var one = cm.markText(found.from,
Pos(found.from.line, found.from.ch + 1), {className: style});Ð   var two =
found.to && cm.markText(found.to, Pos(found.to.line, found.to.ch + 1),
{className: style});Ð   // Kludge to work around the IE bug from issue #1193,
where textÐ   // input stops going to the textare whever this fires.Ð   if
(ie_lt8 && cm.state.focused) cm.display.input.focus();Ð   var clear =
function() {Ð     cm.operation(function() { one.clear(); two &&
two.clear(); });Ð   };Ð   if (autoclear) setTimeout(clear, 800);Ð   else
return clear;Ð }Ð var currentlyHighlighted = null;Ð function
doMatchBrackets(cm) {Ð   cm.operation(function() {Ð     if
(currentlyHighlighted) {currentlyHighlighted(); currentlyHighlighted = null;}Ð
      if (!cm.somethingSelected()) currentlyHighlighted = matchBrackets(cm,
false);Ð   });Ð }Ð CodeMirror.defineOption("matchBrackets", false,
function(cm, val, old) {Ð   if (old && old != CodeMirror.Init)Ð
cm.off("cursorActivity", doMatchBrackets);Ð   if (val) {Ð
cm.state._matchBrackets = typeof val == "object" ? val : {};Ð
cm.on("cursorActivity", doMatchBrackets);Ð   }Ð });Ð
CodeMirror.defineExtension("matchBrackets", function() {matchBrackets(this,
true);});Ð CodeMirror.defineExtension("findMatchingBracket", function()
{return findMatchingBracket(this);});Ð})();Ð
```

public\assets\editor\xml.js

```
CodeMirror.defineMode("xml", function(config, parserConfig) {Ð var indentUnit
= config.indentUnit;Ð var multilineTagIndentFactor =
parserConfig.multilineTagIndentFactor || 1;Ð var Kludges =
parserConfig.htmlMode ? {Ð   autoSelfClosers: {'area': true, 'base': true,
'br': true, 'col': true, 'command': true,Ð                     'embed': true,
'frame': true, 'hr': true, 'img': true, 'input': true,Ð
'keygen': true, 'link': true, 'meta': true, 'param': true, 'source': true,Ð
                      'track': true, 'wbr': true},Ð   implicitlyClosed:
{'dd': true, 'li': true, 'optgroup': true, 'option': true, 'p': true,Ð
                       'rp': true, 'rt': true, 'tbody': true, 'td': true,
'tfoot': true,Ð                      'th': true, 'tr': true},Ð
contextGrabbers: {Ð     'dd': {'dd': true, 'dt': true},Ð     'dt': {'dd':
true, 'dt': true},Ð     'li': {'li': true},Ð     'option': {'option': true,
'optgroup': true},Ð     'optgroup': {'optgroup': true},Ð     'p': {'address':
true, 'article': true, 'aside': true, 'blockquote': true, 'dir': true,Ð
            'div': true, 'dl': true, 'fieldset': true, 'footer': true,
'form': true,Ð           'h1': true, 'h2': true, 'h3': true, 'h4': true,
'h5': true, 'h6': true,Ð           'header': true, 'hgroup': true, 'hr':
true, 'menu': true, 'nav': true, 'ol': true,Ð           'p': true, 'pre':
true, 'section': true, 'table': true, 'ul': true},Ð     'rp': {'rp': true,
'rt': true},Ð     'rt': {'rp': true, 'rt': true},Ð     'tbody': {'tbody':
true, 'tfoot': true},Ð     'td': {'td': true, 'th': true},Ð     'tfoot':
{'tbody': true},Ð     'th': {'td': true, 'th': true},Ð     'thead': {'tbody':
true, 'tfoot': true},Ð     'tr': {'tr': true}Ð   },Ð   doNotIndent: {"pre":
true},Ð   allowUnquoted: true,Ð   allowMissing: trueÐ } : {Ð
autoSelfClosers: {},Ð   implicitlyClosed: {},Ð   contextGrabbers: {},Ð
doNotIndent: {},Ð   allowUnquoted: false,Ð   allowMissing: falseÐ };Ð var
alignCDATA = parserConfig.alignCDATA;Ð // Return variables for tokenizersÐ
var tagName, type;Ð function inText(stream, state) {Ð   function
chain(parser) {Ð     state.tokenize = parser;Ð     return parser(stream,
state);Ð   }Ð   var ch = stream.next();Ð   if (ch == "<") {Ð     if
(stream.eat("!")) {Ð       if (stream.eat("[")) {Ð         if
(stream.match("CDATA")) return chain(inBlock("atom", "]]>"));Ð         else
return null;Ð       }Ð       else if (stream.match("--")) return
chain(inBlock("comment", "-->"));Ð       else if (stream.match("DOCTYPE",
true, true)) {Ð         stream.eatWhile(/[\w\._\-]/);Ð         return
chain(doctype(1));Ð       }Ð       else return null;Ð     }Ð     else if
(stream.eat("?")) {Ð       stream.eatWhile(/[\w\._\-]/);Ð
state.tokenize = inBlock("meta", "?>");Ð       return "meta";Ð     }Ð
else {Ð       var isClose = stream.eat("/");Ð       tagName = "";Ð       var
c;Ð       while ((c = stream.eat(/[^\s\u00a0=<>\"\'\/?]/))) tagName += c;Ð
        if (!tagName) return "error";Ð       type = isClose ? "closeTag" :
"openTag";Ð       state.tokenize = inTag;Ð       return "tag";Ð     }Ð   }Ð
else if (ch == "&") {Ð     var ok;Ð     if (stream.eat("#")) {Ð       if
(stream.eat("x")) {Ð         ok = stream.eatWhile(/[a-fA-F\d]/) &&
stream.eat(";");Ð       } else {Ð         ok = stream.eatWhile(/[\d]/) &&
stream.eat(";");Ð       }Ð     } else {Ð       ok = stream.eatWhile(/[\w\.
\-:]/) && stream.eat(";");Ð     }Ð     return ok ? "atom" : "error";Ð   }Ð
else {Ð     stream.eatWhile(/[^&<]/);Ð     return null;Ð   }Ð }Ð function
inTag(stream, state) {Ð   var ch = stream.next();Ð   if (ch == ">" || (ch ==
"/" && stream.eat(">"))) {Ð     state.tokenize = inText;Ð     type = ch ==
">" ? "endTag" : "selfcloseTag";Ð     return "tag";Ð   }Ð   else if (ch ==
"=") {Ð     type = "equals";Ð     return null;Ð   }Ð   else if (/
[\'\"]/.test(ch)) {Ð     state.tokenize = inAttribute(ch);Ð     return
state.tokenize(stream, state);Ð   }Ð   else {Ð     stream.eatWhile(/
[^\s\u00a0=<>\"\']/);Ð     return "word";Ð   }Ð }Ð function
inAttribute(quote) {Ð   return function(stream, state) {Ð     while (!
stream.eol()) {Ð       if (stream.next() == quote) {Ð         state.tokenize
= inTag;Ð
```

```
                  break;Ð       }Ð     }Ð     return "string";Ð   };Ð }Ð
function inBlock(style, terminator) {Ð   return function(stream, state) {Ð
      while (!stream.eol()) {Ð       if (stream.match(terminator)) {Ð
state.tokenize = inText;Ð         break;Ð       }Ð       stream.next();Ð     }Ð
      return style;Ð   };Ð }Ð function doctype(depth) {Ð   return
function(stream, state) {Ð     var ch;Ð     while ((ch = stream.next()) !=
null) {Ð       if (ch == "<") {Ð         state.tokenize = doctype(depth + 1);Ð
          return state.tokenize(stream, state);Ð       } else if (ch == ">") {Ð
          if (depth == 1) {Ð           state.tokenize = inText;Ð
break;Ð         } else {Ð           state.tokenize = doctype(depth - 1);Ð
            return state.tokenize(stream, state);Ð         }Ð       }Ð     }Ð
      return "meta";Ð   };Ð }Ð var curState, curStream, setStyle;Ð function
pass() {Ð   for (var i = arguments.length - 1; i >= 0; i--)
curState.cc.push(arguments[i]);Ð }Ð function cont() {Ð   pass.apply(null,
arguments);Ð   return true;Ð }Ð function pushContext(tagName, startOfLine) {Ð
    var noIndent = Kludges.doNotIndent.hasOwnProperty(tagName) ||
(curState.context && curState.context.noIndent);Ð   curState.context = {Ð
prev: curState.context,Ð     tagName: tagName,Ð     indent: curState.indented,Ð
      startOfLine: startOfLine,Ð     noIndent: noIndentÐ   };Ð }Ð function
popContext() {Ð   if (curState.context) curState.context =
curState.context.prev;Ð }Ð function element(type) {Ð   if (type == "openTag")
{Ð     curState.tagName = tagName;Ð     curState.tagStart =
curStream.column();Ð     return cont(attributes,
endtag(curState.startOfLine));Ð   } else if (type == "closeTag") {Ð     var
err = false;Ð     if (curState.context) {Ð       if
(curState.context.tagName != tagName) {Ð         if (Kludges.implicitlyClosed.
hasOwnProperty(curState.context.tagName.toLowerCase())) {Ð
popContext();Ð         }Ð         err = !curState.context ||
curState.context.tagName != tagName;Ð       }Ð     } else {Ð       err = true;Ð
      }Ð     if (err) setStyle = "error";Ð     return cont(endclosetag(err));Ð
    }Ð   return cont();Ð }Ð function endtag(startOfLine) {Ð   return
function(type) {Ð     var tagName = curState.tagName;Ð     curState.tagName =
curState.tagStart = null;Ð     if (type == "selfcloseTag" ||Ð         (type
== "endTag" &&
Kludges.autoSelfClosers.hasOwnProperty(tagName.toLowerCase()))) {Ð
maybePopContext(tagName.toLowerCase());Ð       return cont();Ð     }Ð     if
(type == "endTag") {Ð       maybePopContext(tagName.toLowerCase());Ð
pushContext(tagName, startOfLine);Ð       return cont();Ð     }Ð     return
cont();Ð   };Ð }Ð function endclosetag(err) {Ð   return function(type) {Ð
if (err) setStyle = "error";Ð     if (type == "endTag") { popContext();
return cont(); }Ð     setStyle = "error";Ð     return cont(arguments.callee);Ð
    };Ð }Ð function maybePopContext(nextTagName) {Ð   var parentTagName;Ð
while (true) {Ð     if (!curState.context) {Ð       return;Ð     }Ð
parentTagName = curState.context.tagName.toLowerCase();Ð     if (!
Kludges.contextGrabbers.hasOwnProperty(parentTagName) ||Ð         !
Kludges.contextGrabbers[parentTagName].hasOwnProperty(nextTagName)) {Ð
return;Ð     }Ð     popContext();Ð   }Ð }Ð function attributes(type) {Ð   if
(type == "word") {setStyle = "attribute"; return cont(attribute, attributes);}Ð
    if (type == "endTag" || type == "selfcloseTag") return pass();Ð
setStyle = "error";Ð   return cont(attributes);Ð }Ð function attribute(type) {Ð
    if (type == "equals") return cont(attvalue, attributes);Ð   if (!
Kludges.allowMissing) setStyle = "error";Ð   else if (type == "word")
setStyle = "attribute";Ð   return (type == "endTag" || type ==
"selfcloseTag") ? pass() : cont();Ð }Ð function attvalue(type) {Ð   if (type
== "string") return cont(attvaluemaybe);Ð   if (type == "word" &&
Kludges.allowUnquoted) {setStyle = "string"; return cont();}Ð   setStyle =
"error";Ð   return (type == "endTag" || type == "selfCloseTag") ? pass() :
cont();Ð }Ð function attvaluemaybe(type) {Ð   if (type == "string") return
cont(attvaluemaybe);Ð   else return pass();Ð }Ð return {Ð   startState:
function() {Ð
```

```
                  return {tokenize: inText, cc: [], indented: 0, startOfLine:
true, tagName: null, tagStart: null, context: null};Ð   },Ð   token:
function(stream, state) {Ð     if (!state.tagName && stream.sol()) {Ð
state.startOfLine = true;Ð       state.indented = stream.indentation();Ð     }Ð
      if (stream.eatSpace()) return null;Ð     setStyle = type = tagName =
null;Ð     var style = state.tokenize(stream, state);Ð     state.type = type;Ð
      if ((style || type) && style != "comment") {Ð       curState = state;
curStream = stream;Ð       while (true) {Ð         var comb = state.cc.pop()
|| element;Ð         if (comb(type || style)) break;Ð       }Ð     }Ð
state.startOfLine = false;Ð     return setStyle || style;Ð   },Ð   indent:
function(state, textAfter, fullLine) {Ð     var context = state.context;Ð
if ((state.tokenize != inTag && state.tokenize != inText) ||Ð         context
&& context.noIndent)Ð       return fullLine ? fullLine.match(/^(\s*)/)
[0].length : 0;Ð     if (state.tagName) return state.tagStart + indentUnit *
multilineTagIndentFactor;Ð     if (alignCDATA && /<!
\[CDATA\[/.test(textAfter)) return 0;Ð     if (context && /
^<\//.test(textAfter))Ð       context = context.prev;Ð     while (context && !
context.startOfLine)Ð       context = context.prev;Ð     if (context) return
context.indent + indentUnit;Ð     else return 0;Ð   },Ð   electricChars: "/",Ð
    configuration: parserConfig.htmlMode ? "html" : "xml"Ð };Ð });Ð
CodeMirror.defineMIME("text/xml", "xml");ÐodeMirror.defineMIME("application/
xml", "xml");Ðif (!CodeMirror.mimeModes.hasOwnProperty("text/html"))Ð
CodeMirror.defineMIME("text/html", {name: "xml", htmlMode: true});Ð
```

public\assets\frontend\js\bootstrap.js

```
/*!Ð* Bootstrap v3.0.3 (http://getbootstrap.com)Ð* Copyright 2013 Twitter,
Inc.Ð* Licensed under http://www.apache.org/licenses/LICENSE-2.0Ð*/Ðif (typeof
jQuery === "undefined") { throw new Error("Bootstrap requires jQuery") }ÐØ*
============================================================================Ð*
Bootstrap: transition.js v3.0.3Ð* http://getbootstrap.com/javascript/
#transitionsÐ*
============================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
============================================================================ */Ð
+function ($) { "use strict";Ð // CSS TRANSITION SUPPORT (Shoutout: http://
www.modernizr.com/)Ð //
==============================================================Ð function
transitionEnd() {Ð   var el = document.createElement('bootstrap')Ð   var
transEndEventNames = {Ð     'WebkitTransition' : 'webkitTransitionEnd'Ð   ,
'MozTransition'    : 'transitionend'Ð   , 'OTransition'      :
'oTransitionEnd otransitionend'Ð   , 'transition'       : 'transitionend'Ð   }Ð
    for (var name in transEndEventNames) {Ð     if (el.style[name] !==
undefined) {Ð       return { end: transEndEventNames[name] }Ð     }Ð   }Ð }Ð
  // http://blog.alexmaccaw.com/css-transitionsÐ $.fn.emulateTransitionEnd =
function (duration) {Ð   var called = false, $el = thisÐ
$(this).one($.support.transition.end, function () { called = true })Ð   var
callback = function () { if (!called)
$($el).trigger($.support.transition.end) }Ð   setTimeout(callback, duration)Ð
    return thisÐ }Ð $(function () {Ð   $.support.transition = transitionEnd()Ð
  })ÐØ(jQuery);ØÐ*
============================================================================Ð*
Bootstrap: alert.js v3.0.3Ð* http://getbootstrap.com/javascript/#alertsÐ*
============================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
============================================================================ */Ð
+function ($) { "use strict";Ð // ALERT CLASS DEFINITIONÐ //
======================Ð var dismiss = '[data-dismiss="alert"]'Ð var Alert   =
function (el) {Ð   $(el).on('click', dismiss, this.close)Ð }Ð
Alert.prototype.close = function (e) {Ð   var $this    = $(this)Ð   var
selector = $this.attr('data-target')Ð   if (!selector) {Ð     selector =
$this.attr('href')Ð     selector = selector && selector.replace(/.*(?
=#[^\s]*$)/, '') // strip for ie7Ð   }Ð   var $parent = $(selector)Ð   if (e)
e.preventDefault()Ð   if (!$parent.length) {Ð     $parent =
$this.hasClass('alert') ? $this : $this.parent()Ð   }Ð   $parent.trigger(e =
$.Event('close.bs.alert'))Ð   if (e.isDefaultPrevented()) returnÐ
$parent.removeClass('in')Ð   function removeElement() {Ð
$parent.trigger('closed.bs.alert').remove()Ð   }Ð   $.support.transition &&
$parent.hasClass('fade') ?Ð     $parentÐ       .one($.support.transition.end,
removeElement)Ð       .emulateTransitionEnd(150) :Ð     removeElement()Ð }Ð
  // ALERT PLUGIN DEFINITIONÐ
```

```
                                // ========================Ð var old = $.fn.alertÐ
  $.fn.alert = function (option) {Ð   return this.each(function () {Ð     var
$this = $(this)Ð     var data  = $this.data('bs.alert')Ð     if (!data)
$this.data('bs.alert', (data = new Alert(this)))Ð     if (typeof option ==
'string') data[option].call($this)Ð   })Ð }Ð $.fn.alert.Constructor = AlertÐ
  // ALERT NO CONFLICTÐ // =================Ð $.fn.alert.noConflict =
function () {Ð   $.fn.alert = oldÐ   return thisÐ }Ð // ALERT DATA-APIÐ //
==============Ð $(document).on('click.bs.alert.data-api', dismiss,
Alert.prototype.close)Ð }(jQuery);Ð*
============================================================================Ð*
Bootstrap: button.js v3.0.3Ð* http://getbootstrap.com/javascript/#buttonsÐ*
============================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
============================================================================ */Ð
+function ($) { "use strict";Ð // BUTTON PUBLIC CLASS DEFINITIONÐ //
==============================Ð var Button = function (element, options) {Ð
this.$element = $(element)Ð   this.options  = $.extend({}, Button.DEFAULTS,
options)Ð }Ð Button.DEFAULTS = {Ð   loadingText: 'loading...'Ð }Ð
Button.prototype.setState = function (state) {Ð   var d    = 'disabled'Ð
var $el  = this.$elementÐ   var val  = $el.is('input') ? 'val' : 'html'Ð
var data = $el.data()Ð   state = state + 'Text'Ð   if (!data.resetText)
$el.data('resetText', $el[val]())Ð   $el[val](data[state] ||
this.options[state])Ð   // push to event loop to allow forms to submitÐ
setTimeout(function () {Ð     state == 'loadingText' ?Ð
$el.addClass(d).attr(d, d) :Ð       $el.removeClass(d).removeAttr(d);Ð   }, 0)Ð
  }Ð Button.prototype.toggle = function () {Ð   var $parent = this.
$element.closest('[data-toggle="buttons"]')Ð   var changed = trueÐ   if
($parent.length) {Ð     var $input = this.$element.find('input')Ð     if
($input.prop('type') === 'radio') {Ð       // see if clicking on current oneÐ
        if ($input.prop('checked') && this.$element.hasClass('active'))Ð
          changed = falseÐ       elseÐ
$parent.find('.active').removeClass('active')Ð     }Ð     if (changed)
$input.prop('checked', !this.$element.hasClass('active')).trigger('change')Ð
    }Ð   if (changed) this.$element.toggleClass('active')Ð }Ð // BUTTON
PLUGIN DEFINITIONÐ // ========================Ð var old = $.fn.buttonÐ
$.fn.button = function (option) {Ð   return this.each(function () {Ð     var
$this   = $(this)Ð     var data    = $this.data('bs.button')Ð     var options
= typeof option == 'object' && optionÐ     if (!data) $this.data('bs.button',
(data = new Button(this, options)))Ð     if (option == 'toggle') data.toggle()Ð
      else if (option) data.setState(option)Ð   })Ð }Ð
$.fn.button.Constructor = ButtonÐ // BUTTON NO CONFLICTÐ // ==================Ð
  $.fn.button.noConflict = function () {Ð   $.fn.button = oldÐ   return thisÐ
  }Ð // BUTTON DATA-APIÐ // ================Ð
$(document).on('click.bs.button.data-api', '[data-toggle^=button]', function
(e) {Ð   var $btn = $(e.target)Ð   if (!$btn.hasClass('btn')) $btn =
$btn.closest('.btn')Ð   $btn.button('toggle')Ð   e.preventDefault()Ð })Ð }
(jQuery);Ð*
============================================================================Ð*
Bootstrap: carousel.js v3.0.3Ð* http://getbootstrap.com/javascript/#carouselÐ
* ===========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð
```

```
             * You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
============================================================================ */Ð
+function ($) { "use strict";Ð // CAROUSEL CLASS DEFINITIONÐ //
========================Ð var Carousel = function (element, options) {Ð
this.$element    = $(element)Ð   this.$indicators = this.
$element.find('.carousel-indicators')Ð   this.options     = optionsÐ
this.paused      =Ð   this.sliding     =Ð   this.interval    =Ð   this.
$active     =Ð   this.$items      = nullÐ   this.options.pause == 'hover' &&
this.$elementÐ     .on('mouseenter', $.proxy(this.pause, this))Ð
      .on('mouseleave', $.proxy(this.cycle, this))Ð }Ð Carousel.DEFAULTS = {Ð
    interval: 5000Ð , pause: 'hover'Ð , wrap: trueÐ }Ð
Carousel.prototype.cycle =  function (e) {Ð   e || (this.paused = false)Ð
this.interval && clearInterval(this.interval)Ð   this.options.intervalÐ
&& !this.pausedÐ     && (this.interval = setInterval($.proxy(this.next,
this), this.options.interval))Ð   return thisÐ }Ð
Carousel.prototype.getActiveIndex = function () {Ð   this.$active = this.
$element.find('.item.active')Ð   this.$items  = this.
$active.parent().children()Ð   return this.$items.index(this.$active)Ð }Ð
Carousel.prototype.to = function (pos) {Ð   var that        = thisÐ   var
activeIndex = this.getActiveIndex()Ð   if (pos > (this.$items.length - 1) ||
pos < 0) returnÐ   if (this.sliding)       return this.
$element.one('slid.bs.carousel', function () { that.to(pos) })Ð   if
(activeIndex == pos) return this.pause().cycle()Ð   return this.slide(pos >
activeIndex ? 'next' : 'prev', $(this.$items[pos]))Ð }Ð
Carousel.prototype.pause = function (e) {Ð   e || (this.paused = true)Ð   if
(this.$element.find('.next, .prev').length && $.support.transition.end) {Ð
      this.$element.trigger($.support.transition.end)Ð     this.cycle(true)Ð
    }Ð   this.interval = clearInterval(this.interval)Ð   return thisÐ }Ð
Carousel.prototype.next = function () {Ð   if (this.sliding) returnÐ   return
this.slide('next')Ð }Ð Carousel.prototype.prev = function () {Ð   if
(this.sliding) returnÐ   return this.slide('prev')Ð }Ð
Carousel.prototype.slide = function (type, next) {Ð   var $active   = this.
$element.find('.item.active')Ð   var $next     = next || $active[type]()Ð
var isCycling = this.intervalÐ   var direction = type == 'next' ? 'left' :
'right'Ð   var fallback  = type == 'next' ? 'first' : 'last'Ð   var that
= thisÐ   if (!$next.length) {Ð     if (!this.options.wrap) returnÐ     $next
= this.$element.find('.item')[fallback]()Ð   }Ð   this.sliding = trueÐ
isCycling && this.pause()Ð   var e = $.Event('slide.bs.carousel',
{ relatedTarget: $next[0], direction: direction })Ð   if
($next.hasClass('active')) returnÐ   if (this.$indicators.length) {Ð     this.
$indicators.find('.active').removeClass('active')Ð     this.
$element.one('slid.bs.carousel', function () {Ð       var $nextIndicator =
$(that.$indicators.children()[that.getActiveIndex()])Ð       $nextIndicator
&& $nextIndicator.addClass('active')Ð     })Ð   }Ð   if ($.support.transition
&& this.$element.hasClass('slide')) {Ð     this.$element.trigger(e)Ð     if
(e.isDefaultPrevented()) returnÐ     $next.addClass(type)Ð
$next[0].offsetWidth // force reflowÐ     $active.addClass(direction)Ð
$next.addClass(direction)Ð     $activeÐ       .one($.support.transition.end,
function () {Ð         $next.removeClass([type, direction].join('
')).addClass('active')Ð         $active.removeClass(['active',
direction].join(' '))Ð         that.sliding = falseÐ
setTimeout(function () { that.$element.trigger('slid.bs.carousel') }, 0)Ð
        })Ð       .emulateTransitionEnd(600)Ð   } else {Ð     this.
$element.trigger(e)Ð     if (e.isDefaultPrevented()) returnÐ
$active.removeClass('active')Ð
```

```
                                    $next.addClass('active')Ð     this.sliding
= falseÐ     this.$element.trigger('slid.bs.carousel')Ð   }Ð   isCycling &&
this.cycle()Ð   return thisÐ }Ð // CAROUSEL PLUGIN DEFINITIONÐ //
==========================Ð var old = $.fn.carouselÐ $.fn.carousel = function
(option) {Ð   return this.each(function () {Ð     var $this   = $(this)Ð
var data    = $this.data('bs.carousel')Ð     var options = $.extend({},
Carousel.DEFAULTS, $this.data(), typeof option == 'object' && option)Ð
var action  = typeof option == 'string' ? option : options.slideÐ     if (!
data) $this.data('bs.carousel', (data = new Carousel(this, options)))Ð     if
(typeof option == 'number') data.to(option)Ð     else if (action) data[action]
()Ð     else if (options.interval) data.pause().cycle()Ð   })Ð }Ð
$.fn.carousel.Constructor = CarouselÐ // CAROUSEL NO CONFLICTÐ //
====================Ð $.fn.carousel.noConflict = function () {Ð
$.fn.carousel = oldÐ   return thisÐ }Ð // CAROUSEL DATA-APIÐ //
=================Ð $(document).on('click.bs.carousel.data-api', '[data-
slide], [data-slide-to]', function (e) {Ð   var $this   = $(this), hrefÐ
var $target = $($this.attr('data-target') || (href = $this.attr('href')) &&
href.replace(/.*(?=#[^\s]+$)/, '')) //strip for ie7Ð   var options =
$.extend({}, $target.data(), $this.data())Ð   var slideIndex =
$this.attr('data-slide-to')Ð   if (slideIndex) options.interval = falseÐ
$target.carousel(options)Ð   if (slideIndex = $this.attr('data-slide-to')) {Ð
      $target.data('bs.carousel').to(slideIndex)Ð   }Ð   e.preventDefault()Ð
  })Ð $(window).on('load', function () {Ð   $('[data-
ride="carousel"]').each(function () {Ð     var $carousel = $(this)Ð
$carousel.carousel($carousel.data())Ð   })Ð })Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: collapse.js v3.0.3Ð* http://getbootstrap.com/javascript/#collapseÐ
* ========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
======================================================================== */Ð
+function ($) { "use strict";Ð // COLLAPSE PUBLIC CLASS DEFINITIONÐ //
==================================Ð var Collapse = function (element, options) {Ð
    this.$element      = $(element)Ð   this.options       = $.extend({},
Collapse.DEFAULTS, options)Ð   this.transitioning = nullÐ   if
(this.options.parent) this.$parent = $(this.options.parent)Ð   if
(this.options.toggle) this.toggle()Ð }Ð Collapse.DEFAULTS = {Ð   toggle: trueÐ
  }Ð Collapse.prototype.dimension = function () {Ð   var hasWidth = this.
$element.hasClass('width')Ð   return hasWidth ? 'width' : 'height'Ð }Ð
Collapse.prototype.show = function () {Ð   if (this.transitioning || this.
$element.hasClass('in')) returnÐ   var startEvent =
$.Event('show.bs.collapse')Ð   this.$element.trigger(startEvent)Ð   if
(startEvent.isDefaultPrevented()) returnÐ   var actives = this.$parent &&
this.$parent.find('> .panel > .in')Ð   if (actives && actives.length) {Ð
var hasData = actives.data('bs.collapse')Ð     if (hasData &&
hasData.transitioning) returnÐ     actives.collapse('hide')Ð     hasData ||
actives.data('bs.collapse', null)Ð   }Ð   var dimension = this.dimension()Ð
this.$elementÐ     .removeClass('collapse')Ð     .addClass('collapsing')Ð
[dimension](0)Ð   this.transitioning = 1Ð   var complete = function () {Ð
this.$elementÐ       .removeClass('collapsing')Ð       .addClass('in')Ð
[dimension]('auto')Ð     this.transitioning = 0Ð     this.
$element.trigger('shown.bs.collapse')Ð   }Ð   if (!$.support.transition)
return complete.call(this)Ð   var scrollSize = $.camelCase(['scroll',
dimension].join('-'))Ð
```

```
                    Ð   this.$elementÐ     .one($.support.transition.end,
$.proxy(complete, this))Ð     .emulateTransitionEnd(350)Ð     [dimension]
(this.$element[0][scrollSize])Ð }Ð Collapse.prototype.hide = function () {Ð
if (this.transitioning || !this.$element.hasClass('in')) returnÐ   var
startEvent = $.Event('hide.bs.collapse')Ð   this.$element.trigger(startEvent)Ð
    if (startEvent.isDefaultPrevented()) returnÐ   var dimension =
this.dimension()Ð   this.$elementÐ     [dimension](this.$element[dimension]())Ð
      [0].offsetHeightÐ   this.$elementÐ     .addClass('collapsing')Ð
      .removeClass('collapse')Ð     .removeClass('in')Ð   this.transitioning
= 1Ð   var complete = function () {Ð     this.transitioning = 0Ð     this.
$elementÐ       .trigger('hidden.bs.collapse')Ð
        .removeClass('collapsing')Ð       .addClass('collapse')Ð   }Ð   if (!
$.support.transition) return complete.call(this)Ð   this.$elementÐ
[dimension](0)Ð     .one($.support.transition.end, $.proxy(complete, this))Ð
      .emulateTransitionEnd(350)Ð }Ð Collapse.prototype.toggle = function () {Ð
    this[this.$element.hasClass('in') ? 'hide' : 'show']()Ð }Ð // COLLAPSE
PLUGIN DEFINITIONÐ // ==========================Ð var old = $.fn.collapseÐ
$.fn.collapse = function (option) {Ð   return this.each(function () {Ð
var $this   = $(this)Ð     var data    = $this.data('bs.collapse')Ð     var
options = $.extend({}, Collapse.DEFAULTS, $this.data(), typeof option ==
'object' && option)Ð     if (!data) $this.data('bs.collapse', (data = new
Collapse(this, options)))Ð     if (typeof option == 'string') data[option]()Ð
    })Ð }Ð $.fn.collapse.Constructor = CollapseÐ // COLLAPSE NO CONFLICTÐ //
====================Ð $.fn.collapse.noConflict = function () {Ð
$.fn.collapse = oldÐ   return thisÐ }Ð // COLLAPSE DATA-APIÐ //
=================Ð $(document).on('click.bs.collapse.data-api', '[data-
toggle=collapse]', function (e) {Ð   var $this   = $(this), hrefÐ   var
target  = $this.attr('data-target')Ð       || e.preventDefault()Ð       ||
(href = $this.attr('href')) && href.replace(/.*(?=#[^\s]+$)/, '') //strip for
ie7Ð   var $target = $(target)Ð   var data    = $target.data('bs.collapse')Ð
    var option  = data ? 'toggle' : $this.data()Ð   var parent  =
$this.attr('data-parent')Ð   var $parent = parent && $(parent)Ð   if (!data
|| !data.transitioning) {Ð     if ($parent) $parent.find('[data-
toggle=collapse][data-parent="' + parent +
'"]').not($this).addClass('collapsed')Ð     $this[$target.hasClass('in') ?
'addClass' : 'removeClass']('collapsed')Ð   }Ð   $target.collapse(option)Ð }))Ð
(jQuery);Ð*
==========================================================================Ð*
Bootstrap: dropdown.js v3.0.3Ð* http://getbootstrap.com/javascript/#dropdownsÐ
* ==========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
========================================================================== */Ð
+function ($) { "use strict";Ð // DROPDOWN CLASS DEFINITIONÐ //
==========================Ð var backdrop = '.dropdown-backdrop'Ð var toggle
= '[data-toggle=dropdown]'Ð var Dropdown = function (element) {Ð
$(element).on('click.bs.dropdown', this.toggle)Ð }Ð Dropdown.prototype.toggle
= function (e) {Ð   var $this = $(this)Ð   if
($this.is('.disabled, :disabled')) returnÐ   var $parent  = getParent($this)Ð
    var isActive = $parent.hasClass('open')Ð   clearMenus()Ð   if (!isActive)
{Ð     if ('ontouchstart' in document.documentElement && !
$parent.closest('.navbar-nav').length) {Ð       // if mobile we use a
backdrop because click events don't delegateÐ       $('<div class="dropdown-
backdrop"/>').insertAfter($(this)).on('click', clearMenus)Ð
```

```
                                                                    }Ð
$parent.trigger(e = $.Event('show.bs.dropdown'))Ð     if
(e.isDefaultPrevented()) returnÐ     $parentÐ       .toggleClass('open')Ð
        .trigger('shown.bs.dropdown')Ð     $this.focus()Ð   }Ð   return falseÐ
  }Ð Dropdown.prototype.keydown = function (e) {Ð   if (!/(38|40|
27)/.test(e.keyCode)) returnÐ   var $this = $(this)Ð   e.preventDefault()Ð
e.stopPropagation()Ð   if ($this.is('.disabled, :disabled')) returnÐ   var
$parent  = getParent($this)Ð   var isActive = $parent.hasClass('open')Ð   if
(!isActive || (isActive && e.keyCode == 27)) {Ð     if (e.which == 27)
$parent.find(toggle).focus()Ð     return $this.click()Ð   }Ð   var $items =
$('[role=menu] li:not(.divider):visible a', $parent)Ð   if (!$items.length)
returnÐ   var index = $items.index($items.filter(':focus'))Ð   if (e.keyCode
== 38 && index > 0)                 index--                        // upÐ
if (e.keyCode == 40 && index < $items.length - 1) index+
+                        // downÐ   if (!
~index)                                       index=0Ð
$items.eq(index).focus()Ð }Ð function clearMenus() {Ð   $(backdrop).remove()Ð
    $(toggle).each(function (e) {Ð     var $parent = getParent($(this))Ð
if (!$parent.hasClass('open')) returnÐ     $parent.trigger(e =
$.Event('hide.bs.dropdown'))Ð     if (e.isDefaultPrevented()) returnÐ
$parent.removeClass('open').trigger('hidden.bs.dropdown')Ð   })Ð }Ð function
getParent($this) {Ð   var selector = $this.attr('data-target')Ð   if (!
selector) {Ð     selector = $this.attr('href')Ð     selector = selector && /
#/.test(selector) && selector.replace(/.*(?=#[^\s]*$)/, '') //strip for ie7Ð
    }Ð   var $parent = selector && $(selector)Ð   return $parent &&
$parent.length ? $parent : $this.parent()Ð }Ð // DROPDOWN PLUGIN DEFINITIONÐ
  // ==========================Ð var old = $.fn.dropdownÐ $.fn.dropdown =
function (option) {Ð   return this.each(function () {Ð     var $this = $(this)Ð
      var data  = $this.data('bs.dropdown')Ð     if (!data)
$this.data('bs.dropdown', (data = new Dropdown(this)))Ð     if (typeof option
== 'string') data[option].call($this)Ð   })Ð }Ð $.fn.dropdown.Constructor =
DropdownÐ // DROPDOWN NO CONFLICTÐ // ====================Ð
$.fn.dropdown.noConflict = function () {Ð   $.fn.dropdown = oldÐ   return thisÐ
  }Ð // APPLY TO STANDARD DROPDOWN ELEMENTSÐ //
===================================Ð $(document)Ð
    .on('click.bs.dropdown.data-api', clearMenus)Ð
    .on('click.bs.dropdown.data-api', '.dropdown form', function (e)
{ e.stopPropagation() })Ð   .on('click.bs.dropdown.data-api'  , toggle,
Dropdown.prototype.toggle)Ð   .on('keydown.bs.dropdown.data-api', toggle + ',
[role=menu]' , Dropdown.prototype.keydown)Ð}(jQuery);Ð*
============================================================================Ð*
Bootstrap: modal.js v3.0.3Ð* http://getbootstrap.com/javascript/#modalsÐ*
============================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
============================================================================ */Ð
+function ($) { "use strict";Ð // MODAL CLASS DEFINITIONÐ //
======================Ð var Modal = function (element, options) {Ð
this.options   = optionsÐ   this.$element  = $(element)Ð   this.$backdrop =Ð
    this.isShown   = nullÐ   if (this.options.remote) this.
$element.load(this.options.remote)Ð }Ð Modal.DEFAULTS = {Ð     backdrop: trueÐ
    , keyboard: trueÐ   , show: trueÐ }Ð Modal.prototype.toggle = function
(_relatedTarget) {Ð   return this[!this.isShown ? 'show' : 'hide']
(_relatedTarget)Ð
```

```
                  }Ð Modal.prototype.show = function (_relatedTarget) {Ð
var that = thisÐ   var e    = $.Event('show.bs.modal', { relatedTarget:
_relatedTarget })Ð   this.$element.trigger(e)Ð   if (this.isShown ||
e.isDefaultPrevented()) returnÐ   this.isShown = trueÐ   this.escape()Ð
this.$element.on('click.dismiss.modal', '[data-dismiss="modal"]',
$.proxy(this.hide, this))Ð   this.backdrop(function () {Ð     var transition
= $.support.transition && that.$element.hasClass('fade')Ð     if (!that.
$element.parent().length) {Ð       that.$element.appendTo(document.body) //
don't move modals dom positionÐ     }Ð     that.$element.show()Ð     if
(transition) {Ð       that.$element[0].offsetWidth // force reflowÐ     }Ð
      that.$elementÐ       .addClass('in')Ð       .attr('aria-hidden', false)Ð
      that.enforceFocus()Ð     var e = $.Event('shown.bs.modal',
{ relatedTarget: _relatedTarget })Ð     transition ?Ð       that.
$element.find('.modal-dialog') // wait for modal to slide inÐ
          .one($.support.transition.end, function () {Ð           that.
$element.focus().trigger(e)Ð         })Ð         .emulateTransitionEnd(300) :Ð
        that.$element.focus().trigger(e)Ð   })Ð }Ð Modal.prototype.hide =
function (e) {Ð   if (e) e.preventDefault()Ð   e = $.Event('hide.bs.modal')Ð
    this.$element.trigger(e)Ð   if (!this.isShown || e.isDefaultPrevented())
returnÐ   this.isShown = falseÐ   this.escape()Ð
$(document).off('focusin.bs.modal')Ð   this.$elementÐ     .removeClass('in')Ð
      .attr('aria-hidden', true)Ð     .off('click.dismiss.modal')Ð
$.support.transition && this.$element.hasClass('fade') ?Ð     this.$elementÐ
        .one($.support.transition.end, $.proxy(this.hideModal, this))Ð
        .emulateTransitionEnd(300) :Ð     this.hideModal()Ð }Ð
Modal.prototype.enforceFocus = function () {Ð   $(document)Ð
      .off('focusin.bs.modal') // guard against infinite focus loopÐ
      .on('focusin.bs.modal', $.proxy(function (e) {Ð       if (this.
$element[0] !== e.target && !this.$element.has(e.target).length) {Ð
this.$element.focus()Ð       }Ð     }, this))Ð }Ð Modal.prototype.escape =
function () {Ð   if (this.isShown && this.options.keyboard) {Ð     this.
$element.on('keyup.dismiss.bs.modal', $.proxy(function (e) {Ð       e.which
== 27 && this.hide()Ð     }, this))Ð   } else if (!this.isShown) {Ð     this.
$element.off('keyup.dismiss.bs.modal')Ð   }Ð }Ð Modal.prototype.hideModal =
function () {Ð   var that = thisÐ   this.$element.hide()Ð
this.backdrop(function () {Ð     that.removeBackdrop()Ð     that.
$element.trigger('hidden.bs.modal')Ð   })Ð }Ð Modal.prototype.removeBackdrop
= function () {Ð   this.$backdrop && this.$backdrop.remove()Ð   this.
$backdrop = nullÐ }Ð Modal.prototype.backdrop = function (callback) {Ð   var
that    = thisÐ   var animate = this.$element.hasClass('fade') ? 'fade' : ''Ð
    if (this.isShown && this.options.backdrop) {Ð     var doAnimate =
$.support.transition && animateÐ     this.$backdrop = $('<div class="modal-
backdrop ' + animate + '" />')Ð       .appendTo(document.body)Ð     this.
$element.on('click.dismiss.modal', $.proxy(function (e) {Ð       if
(e.target !== e.currentTarget) returnÐ       this.options.backdrop == 'static'Ð
          ? this.$element[0].focus.call(this.$element[0])Ð         :
this.hide.call(this)Ð     }, this))Ð     if (doAnimate) this.
$backdrop[0].offsetWidth // force reflowÐ     this.$backdrop.addClass('in')Ð
      if (!callback) returnÐ     doAnimate ?Ð       this.$backdropÐ
          .one($.support.transition.end, callback)Ð
          .emulateTransitionEnd(150) :Ð       callback()Ð   } else if (!
this.isShown && this.$backdrop) {Ð     this.$backdrop.removeClass('in')Ð
$.support.transition && this.$element.hasClass('fade')?Ð       this.$backdropÐ
          .one($.support.transition.end, callback)Ð
          .emulateTransitionEnd(150) :Ð       callback()Ð   } else if
(callback) {Ð     callback()Ð   }Ð }Ð // MODAL PLUGIN DEFINITIONÐ //
=======================Ð var old = $.fn.modalÐ $.fn.modal = function (option,
_relatedTarget) {Ð   return this.each(function () {Ð     var $this   = $(this)Ð
      var data    = $this.data('bs.modal')Ð     var options = $.extend({},
Modal.DEFAULTS, $this.data(), typeof option == 'object' && option)Ð
```

```
                                                                    Ð     if (!
data) $this.data('bs.modal', (data = new Modal(this, options)))Ð     if
(typeof option == 'string') data[option](_relatedTarget)Ð     else if
(options.show) data.show(_relatedTarget)Ð   })Ð }Ð $.fn.modal.Constructor =
ModalÐ // MODAL NO CONFLICTÐ // =================Ð $.fn.modal.noConflict =
function () {Ð   $.fn.modal = oldÐ   return thisÐ }Ð // MODAL DATA-APIÐ //
==============Ð $(document).on('click.bs.modal.data-api', '[data-
toggle="modal"]', function (e) {Ð   var $this   = $(this)Ð   var href    =
$this.attr('href')Ð   var $target = $($this.attr('data-target') || (href &&
href.replace(/.*(?=#[^\s]+$)/, '''))) //strip for ie7Ð   var option  =
$target.data('modal') ? 'toggle' : $.extend({ remote: !/#/.test(href) &&
href }, $target.data(), $this.data())Ð   e.preventDefault()Ð   $targetÐ
      .modal(option, this)Ð     .one('hide', function () {Ð
$this.is(':visible') && $this.focus()Ð     })Ð })Ð $(document)Ð
    .on('show.bs.modal',  '.modal', function ()
{ $(document.body).addClass('modal-open') })Ð   .on('hidden.bs.modal',
'.modal', function () { $(document.body).removeClass('modal-open') })Ð }
(jQuery);Ð*
================================================================================Ð*
Bootstrap: tooltip.js v3.0.3Ð* http://getbootstrap.com/javascript/#tooltipÐ*
Inspired by the original jQuery.tipsy by Jason FrameÐ*
================================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
================================================================================ */Ð
+function ($) { "use strict";Ð // TOOLTIP PUBLIC CLASS DEFINITIONÐ //
================================Ð var Tooltip = function (element, options) {Ð
    this.type       =Ð   this.options    =Ð   this.enabled    =Ð
this.timeout    =Ð   this.hoverState =Ð   this.$element   = nullÐ
this.init('tooltip', element, options)Ð }Ð Tooltip.DEFAULTS = {Ð   animation:
trueÐ , placement: 'top'Ð , selector: falseÐ , template: '<div
class="tooltip"><div class="tooltip-arrow"></div><div class="tooltip-inner"></
div></div>'Ð , trigger: 'hover focus'Ð , title: ''Ð , delay: 0Ð , html: falseÐ
  , container: falseÐ }Ð Tooltip.prototype.init = function (type, element,
options) {Ð   this.enabled  = trueÐ   this.type     = typeÐ   this.$element =
$(element)Ð   this.options  = this.getOptions(options)Ð   var triggers =
this.options.trigger.split(' ')Ð   for (var i = triggers.length; i--;) {Ð
var trigger = triggers[i]Ð     if (trigger == 'click') {Ð       this.
$element.on('click.' + this.type, this.options.selector, $.proxy(this.toggle,
this))Ð     } else if (trigger != 'manual') {Ð       var eventIn  = trigger
== 'hover' ? 'mouseenter' : 'focus'Ð       var eventOut = trigger ==
'hover' ? 'mouseleave' : 'blur'Ð       this.$element.on(eventIn  + '.' +
this.type, this.options.selector, $.proxy(this.enter, this))Ð       this.
$element.on(eventOut + '.' + this.type, this.options.selector,
$.proxy(this.leave, this))Ð     }Ð   }Ð   this.options.selector ?Ð
(this._options = $.extend({}, this.options, { trigger: 'manual', selector:
'' })) :Ð     this.fixTitle()Ð }Ð Tooltip.prototype.getDefaults = function ()
{Ð   return Tooltip.DEFAULTSÐ }Ð Tooltip.prototype.getOptions = function
(options) {Ð   options = $.extend({}, this.getDefaults(), this.
$element.data(), options)Ð   if (options.delay && typeof options.delay ==
'number') {Ð     options.delay = {Ð       show: options.delayÐ     , hide:
options.delayÐ     }Ð   }Ð   return optionsÐ }Ð
Tooltip.prototype.getDelegateOptions = function () {Ð   var options  = {}Ð
var defaults = this.getDefaults()Ð
```

```
                                Ð   this._options && $.each(this._options,
function (key, value) {Ð     if (defaults[key] != value) options[key] = valueÐ
    })Ð   return optionsÐ }Ð Tooltip.prototype.enter = function (obj) {Ð
var self = obj instanceof this.constructor ?Ð     obj : $(obj.currentTarget)
[this.type](this.getDelegateOptions()).data('bs.' + this.type)Ð
clearTimeout(self.timeout)Ð   self.hoverState = 'in'Ð   if (!
self.options.delay || !self.options.delay.show) return self.show()Ð
self.timeout = setTimeout(function () {Ð     if (self.hoverState == 'in')
self.show()Ð   }, self.options.delay.show)Ð }Ð Tooltip.prototype.leave =
function (obj) {Ð   var self = obj instanceof this.constructor ?Ð     obj :
$(obj.currentTarget)[this.type](this.getDelegateOptions()).data('bs.' +
this.type)Ð   clearTimeout(self.timeout)Ð   self.hoverState = 'out'Ð   if (!
self.options.delay || !self.options.delay.hide) return self.hide()Ð
self.timeout = setTimeout(function () {Ð     if (self.hoverState == 'out')
self.hide()Ð   }, self.options.delay.hide)Ð }Ð Tooltip.prototype.show =
function () {Ð   var e = $.Event('show.bs.'+ this.type)Ð   if
(this.hasContent() && this.enabled) {Ð     this.$element.trigger(e)Ð     if
(e.isDefaultPrevented()) returnÐ     var $tip = this.tip()Ð
this.setContent()Ð     if (this.options.animation) $tip.addClass('fade')Ð
var placement = typeof this.options.placement == 'function' ?Ð
this.options.placement.call(this, $tip[0], this.$element[0]) :Ð
this.options.placementÐ     var autoToken = /\s?auto?\s?/iÐ     var autoPlace
= autoToken.test(placement)Ð     if (autoPlace) placement =
placement.replace(autoToken, '') || 'top'Ð     $tipÐ       .detach()Ð
        .css({ top: 0, left: 0, display: 'block' })Ð
        .addClass(placement)Ð     this.options.container ?
$tip.appendTo(this.options.container) : $tip.insertAfter(this.$element)Ð
var pos          = this.getPosition()Ð     var actualWidth  =
$tip[0].offsetWidthÐ     var actualHeight = $tip[0].offsetHeightÐ     if
(autoPlace) {Ð       var $parent = this.$element.parent()Ð       var
orgPlacement = placementÐ       var docScroll    =
document.documentElement.scrollTop || document.body.scrollTopÐ       var
parentWidth  = this.options.container == 'body' ? window.innerWidth  :
$parent.outerWidth()Ð       var parentHeight = this.options.container ==
'body' ? window.innerHeight : $parent.outerHeight()Ð       var parentLeft   =
this.options.container == 'body' ? 0 : $parent.offset().leftÐ       placement
= placement == 'bottom' && pos.top   + pos.height  + actualHeight - docScroll
> parentHeight  ? 'top'    :Ð                  placement == 'top'    &&
pos.top   - docScroll   - actualHeight < 0                          ?
'bottom' :Ð                   placement == 'right'  && pos.right +
actualWidth > parentWidth                              ? 'left'   :Ð
                    placement == 'left'   && pos.left  - actualWidth <
parentLeft                                ? 'right'  :Ð
placementÐ       $tipÐ         .removeClass(orgPlacement)Ð
          .addClass(placement)Ð     }Ð     var calculatedOffset =
this.getCalculatedOffset(placement, pos, actualWidth, actualHeight)Ð
this.applyPlacement(calculatedOffset, placement)Ð     this.
$element.trigger('shown.bs.' + this.type)Ð   }Ð }Ð
Tooltip.prototype.applyPlacement = function(offset, placement) {Ð   var
replaceÐ   var $tip   = this.tip()Ð   var width  = $tip[0].offsetWidthÐ   var
height = $tip[0].offsetHeightÐ   // manually read margins because
getBoundingClientRect includes differenceÐ   var marginTop =
parseInt($tip.css('margin-top'), 10)Ð   var marginLeft =
parseInt($tip.css('margin-left'), 10)Ð   // we must check for NaN for ie 8/9Ð
    if (isNaN(marginTop))  marginTop  = 0Ð   if (isNaN(marginLeft))
marginLeft = 0Ð   offset.top  = offset.top  + marginTopÐ   offset.left =
offset.left + marginLeftÐ   $tipÐ     .offset(offset)Ð     .addClass('in')Ð
    // check to see if placing tip in new offset caused the tip to resize
itselfÐ   var actualWidth  = $tip[0].offsetWidthÐ   var actualHeight =
$tip[0].offsetHeightÐ
```

```
                    Ð   if (placement == 'top' && actualHeight != height) {Ð
      replace = trueÐ     offset.top = offset.top + height - actualHeightÐ   }Ð
    if (/bottom|top/.test(placement)) {Ð     var delta = 0Ð     if
(offset.left < 0) {Ð       delta       = offset.left * -2Ð       offset.left
= 0Ð       $tip.offset(offset)Ð       actualWidth  = $tip[0].offsetWidthÐ
        actualHeight = $tip[0].offsetHeightÐ     }Ð
this.replaceArrow(delta - width + actualWidth, actualWidth, 'left')Ð   } else
{Ð     this.replaceArrow(actualHeight - height, actualHeight, 'top')Ð   }Ð
if (replace) $tip.offset(offset)Ð }Ð Tooltip.prototype.replaceArrow =
function(delta, dimension, position) {Ð   this.arrow().css(position, delta ?
(50 * (1 - delta / dimension) + "%") : '')Ð }Ð Tooltip.prototype.setContent =
function () {Ð   var $tip  = this.tip()Ð   var title = this.getTitle()Ð
$tip.find('.tooltip-inner')[this.options.html ? 'html' : 'text'](title)Ð
$tip.removeClass('fade in top bottom left right')Ð }Ð Tooltip.prototype.hide
= function () {Ð   var that = thisÐ   var $tip = this.tip()Ð   var e    =
$.Event('hide.bs.' + this.type)Ð   function complete() {Ð     if
(that.hoverState != 'in') $tip.detach()Ð   }Ð   this.$element.trigger(e)Ð
if (e.isDefaultPrevented()) returnÐ   $tip.removeClass('in')Ð
$.support.transition && this.$tip.hasClass('fade') ?Ð     $tipÐ
        .one($.support.transition.end, complete)Ð
        .emulateTransitionEnd(150) :Ð     complete()Ð   this.
$element.trigger('hidden.bs.' + this.type)Ð   return thisÐ }Ð
Tooltip.prototype.fixTitle = function () {Ð   var $e = this.$elementÐ   if
($e.attr('title') || typeof($e.attr('data-original-title')) != 'string') {Ð
      $e.attr('data-original-title', $e.attr('title') || '').attr('title', '')Ð
    }Ð }Ð Tooltip.prototype.hasContent = function () {Ð   return
this.getTitle()Ð }Ð Tooltip.prototype.getPosition = function () {Ð   var el =
this.$element[0]Ð   return $.extend({}, (typeof el.getBoundingClientRect ==
'function') ? el.getBoundingClientRect() : {Ð     width: el.offsetWidthÐ   ,
height: el.offsetHeightÐ   }, this.$element.offset())Ð }Ð
Tooltip.prototype.getCalculatedOffset = function (placement, pos,
actualWidth, actualHeight) {Ð   return placement == 'bottom' ? { top: pos.top
+ pos.height,   left: pos.left + pos.width / 2 - actualWidth / 2  } :Ð
           placement == 'top'    ? { top: pos.top - actualHeight, left:
pos.left + pos.width / 2 - actualWidth / 2  } :Ð          placement ==
'left'   ? { top: pos.top + pos.height / 2 - actualHeight / 2, left: pos.left
- actualWidth } :Ð       /* placement == 'right' */ { top: pos.top +
pos.height / 2 - actualHeight / 2, left: pos.left + pos.width   }Ð }Ð
Tooltip.prototype.getTitle = function () {Ð   var titleÐ   var $e = this.
$elementÐ   var o  = this.optionsÐ   title = $e.attr('data-original-title')Ð
      || (typeof o.title == 'function' ? o.title.call($e[0]) :  o.title)Ð
return titleÐ }Ð Tooltip.prototype.tip = function () {Ð   return this.$tip =
this.$tip || $(this.options.template)Ð }Ð Tooltip.prototype.arrow = function
() {Ð   return this.$arrow = this.$arrow || this.tip().find('.tooltip-arrow')Ð
  }Ð Tooltip.prototype.validate = function () {Ð   if (!this.
$element[0].parentNode) {Ð     this.hide()Ð     this.$element = nullÐ
this.options  = nullÐ   }Ð }Ð Tooltip.prototype.enable = function () {Ð
this.enabled = trueÐ }Ð Tooltip.prototype.disable = function () {Ð
this.enabled = falseÐ }Ð Tooltip.prototype.toggleEnabled = function () {Ð
this.enabled = !this.enabledÐ }Ð Tooltip.prototype.toggle = function (e) {Ð
var self = e ? $(e.currentTarget)[this.type]
(this.getDelegateOptions()).data('bs.' + this.type) : thisÐ
self.tip().hasClass('in') ? self.leave(self) : self.enter(self)Ð }Ð
Tooltip.prototype.destroy = function () {Ð   this.hide().$element.off('.' +
this.type).removeData('bs.' + this.type)Ð }Ð // TOOLTIP PLUGIN DEFINITIONÐ //
========================Ð var old = $.fn.tooltipÐ $.fn.tooltip = function
(option) {Ð   return this.each(function () {Ð     var $this   = $(this)Ð
var data    = $this.data('bs.tooltip')Ð     var options = typeof option ==
'object' && optionÐ     if (!data) $this.data('bs.tooltip', (data = new
Tooltip(this, options)))Ð
```

```
                                if (typeof option == 'string') data[option]()Ð
    })Ð }Ð $.fn.tooltip.Constructor = TooltipÐ // TOOLTIP NO CONFLICTÐ //
===================Ð $.fn.tooltip.noConflict = function () {Ð   $.fn.tooltip
= oldÐ   return thisÐ }Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: popover.js v3.0.3Ð* http://getbootstrap.com/javascript/#popoversÐ*
========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
======================================================================== */Ð
+function ($) { "use strict";Ð // POPOVER PUBLIC CLASS DEFINITIONÐ //
================================Ð var Popover = function (element, options) {Ð
    this.init('popover', element, options)Ð }Ð if (!$.fn.tooltip) throw new
Error('Popover requires tooltip.js')Ð Popover.DEFAULTS = $.extend({} ,
$.fn.tooltip.Constructor.DEFAULTS, {Ð   placement: 'right'Ð , trigger: 'click'Ð
  , content: ''Ð , template: '<div class="popover"><div class="arrow"></
div><h3 class="popover-title"></h3><div class="popover-content"></div></div>'Ð
  })Ð // NOTE: POPOVER EXTENDS tooltip.jsÐ // ================================Ð
  Popover.prototype = $.extend({}, $.fn.tooltip.Constructor.prototype)Ð
Popover.prototype.constructor = PopoverÐ Popover.prototype.getDefaults =
function () {Ð   return Popover.DEFAULTSÐ }Ð Popover.prototype.setContent =
function () {Ð   var $tip    = this.tip()Ð   var title   = this.getTitle()Ð
var content = this.getContent()Ð   $tip.find('.popover-title')
[this.options.html ? 'html' : 'text'](title)Ð   $tip.find('.popover-content')
[this.options.html ? 'html' : 'text'](content)Ð   $tip.removeClass('fade top
bottom left right in')Ð   // IE8 doesn't accept hiding via the `:empty`
pseudo selector, we have to doÐ   // this manually by checking the contents.Ð
    if (!$tip.find('.popover-title').html()) $tip.find('.popover-
title').hide()Ð }Ð Popover.prototype.hasContent = function () {Ð   return
this.getTitle() || this.getContent()Ð }Ð Popover.prototype.getContent =
function () {Ð   var $e = this.$elementÐ   var o  = this.optionsÐ   return
$e.attr('data-content')Ð     || (typeof o.content == 'function' ?Ð
o.content.call($e[0]) :Ð           o.content)Ð }Ð Popover.prototype.arrow =
function () {Ð   return this.$arrow = this.$arrow || this.tip().find('.arrow')Ð
  }Ð Popover.prototype.tip = function () {Ð   if (!this.$tip) this.$tip =
$(this.options.template)Ð   return this.$tipÐ }Ð // POPOVER PLUGIN DEFINITIONÐ
  // ==========================Ð var old = $.fn.popoverÐ $.fn.popover =
function (option) {Ð   return this.each(function () {Ð     var $this   =
$(this)Ð     var data    = $this.data('bs.popover')Ð     var options = typeof
option == 'object' && optionÐ     if (!data) $this.data('bs.popover', (data =
new Popover(this, options)))Ð     if (typeof option == 'string') data[option]
()Ð   })Ð }Ð $.fn.popover.Constructor = PopoverÐ // POPOVER NO CONFLICTÐ //
===================Ð $.fn.popover.noConflict = function () {Ð   $.fn.popover
= oldÐ   return thisÐ }Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: scrollspy.js v3.0.3Ð* http://getbootstrap.com/javascript/#scrollspyÐ
 * ========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð
```

```
                    * See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
========================================================================== */Ð
+function ($) { "use strict";Ð // SCROLLSPY CLASS DEFINITIONÐ //
==========================Ð function ScrollSpy(element, options) {Ð   var hrefÐ
    var process  = $.proxy(this.process, this)Ð   this.$element       =
$(element).is('body') ? $(window) : $(element)Ð   this.$body          =
$('body')Ð   this.$scrollElement = this.$element.on('scroll.bs.scroll-
spy.data-api', process)Ð   this.options        = $.extend({},
ScrollSpy.DEFAULTS, options)Ð   this.selector       = (this.options.targetÐ
      || ((href = $(element).attr('href')) && href.replace(/.*(?=#[^\s]+$)/,
'')) //strip for ie7Ð     || '') + ' .nav li > a'Ð   this.offsets        =
$([])Ð   this.targets        = $([])Ð   this.activeTarget   = nullÐ
this.refresh()Ð   this.process()Ð }Ð ScrollSpy.DEFAULTS = {Ð   offset: 10Ð }Ð
ScrollSpy.prototype.refresh = function () {Ð   var offsetMethod = this.
$element[0] == window ? 'offset' : 'position'Ð   this.offsets = $([])Ð
this.targets = $([])Ð   var self     = thisÐ   var $targets = this.$bodyÐ
      .find(this.selector)Ð     .map(function () {Ð       var $el   = $(this)Ð
        var href  = $el.data('target') || $el.attr('href')Ð       var $href
= /^#\w/.test(href) && $(href)Ð       return ($hrefÐ         && $href.lengthÐ
          && [[ $href[offsetMethod]().top + (!$.isWindow(self.
$scrollElement.get(0)) && self.$scrollElement.scrollTop()), href ]]) || nullÐ
      })Ð     .sort(function (a, b) { return a[0] - b[0] })Ð
      .each(function () {Ð       self.offsets.push(this[0])Ð
self.targets.push(this[1])Ð     })Ð }Ð ScrollSpy.prototype.process = function
() {Ð   var scrollTop    = this.$scrollElement.scrollTop() +
this.options.offsetÐ   var scrollHeight = this.$scrollElement[0].scrollHeight
|| this.$body[0].scrollHeightÐ   var maxScroll    = scrollHeight - this.
$scrollElement.height()Ð   var offsets      = this.offsetsÐ   var
targets      = this.targetsÐ   var activeTarget = this.activeTargetÐ   var iÐ
    if (scrollTop >= maxScroll) {Ð     return activeTarget != (i =
targets.last()[0]) && this.activate(i)Ð   }Ð   for (i = offsets.length; i--;)
{Ð     activeTarget != targets[i]Ð       && scrollTop >= offsets[i]Ð       &&
(!offsets[i + 1] || scrollTop <= offsets[i + 1])Ð       &&
this.activate( targets[i] )Ð   }Ð }Ð ScrollSpy.prototype.activate = function
(target) {Ð   this.activeTarget = targetÐ   $(this.selector)Ð
      .parents('.active')Ð     .removeClass('active')Ð   var selector =
this.selectorÐ     + '[data-target="' + target + '"],'Ð     + this.selector +
'[href="' + target + '"]'Ð   var active = $(selector)Ð     .parents('li')Ð
      .addClass('active')Ð   if (active.parent('.dropdown-menu').length)  {Ð
      active = activeÐ       .closest('li.dropdown')Ð
        .addClass('active')Ð   }Ð   active.trigger('activate.bs.scrollspy')Ð }Ð
  // SCROLLSPY PLUGIN DEFINITIONÐ // ===========================Ð var old =
$.fn.scrollspyÐ $.fn.scrollspy = function (option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.scrollspy')Ð     var options = typeof option == 'object' &&
optionÐ     if (!data) $this.data('bs.scrollspy', (data = new ScrollSpy(this,
options)))Ð     if (typeof option == 'string') data[option]()Ð   })Ð }Ð
$.fn.scrollspy.Constructor = ScrollSpyÐ // SCROLLSPY NO CONFLICTÐ //
=====================Ð $.fn.scrollspy.noConflict = function () {Ð
$.fn.scrollspy = oldÐ   return thisÐ }Ð // SCROLLSPY DATA-APIÐ //
==================Ð $(window).on('load', function () {Ð   $('[data-
spy="scroll"]').each(function () {Ð     var $spy = $(this)Ð
$spy.scrollspy($spy.data())Ð   })Ð })Ð(jQuery);Ð*
============================================================================Ð*
Bootstrap: tab.js v3.0.3Ð* http://getbootstrap.com/javascript/#tabsÐ*
============================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð
```

```
             * You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
========================================================================== */Ð
+function ($) { "use strict";Ð // TAB CLASS DEFINITIONÐ //
====================Ð var Tab = function (element) {Ð   this.element =
$(element)Ð }Ð Tab.prototype.show = function () {Ð   var $this    =
this.elementÐ   var $ul      = $this.closest('ul:not(.dropdown-menu)')Ð   var
selector = $this.data('target')Ð   if (!selector) {Ð     selector =
$this.attr('href')Ð     selector = selector && selector.replace(/.*(?
=#[^\s]*$)/, '') //strip for ie7Ð   }Ð   if
($this.parent('li').hasClass('active')) returnÐ   var previous =
$ul.find('.active:last a')[0]Ð   var e        = $.Event('show.bs.tab', {Ð
relatedTarget: previousÐ   })Ð   $this.trigger(e)Ð   if
(e.isDefaultPrevented()) returnÐ   var $target = $(selector)Ð
this.activate($this.parent('li'), $ul)Ð   this.activate($target,
$target.parent(), function () {Ð     $this.trigger({Ð       type:
'shown.bs.tab'Ð     , relatedTarget: previousÐ     })Ð   })Ð }Ð
Tab.prototype.activate = function (element, container, callback) {Ð   var
$active    = container.find('> .active')Ð   var transition = callbackÐ     &&
$.support.transitionÐ     && $active.hasClass('fade')Ð   function next() {Ð
      $activeÐ       .removeClass('active')Ð       .find('> .dropdown-menu
> .active')Ð       .removeClass('active')Ð     element.addClass('active')Ð
      if (transition) {Ð       element[0].offsetWidth // reflow for transitionÐ
        element.addClass('in')Ð     } else {Ð
element.removeClass('fade')Ð     }Ð     if (element.parent('.dropdown-menu'))
{Ð       element.closest('li.dropdown').addClass('active')Ð     }Ð
callback && callback()Ð   }Ð   transition ?Ð     $activeÐ
        .one($.support.transition.end, next)Ð
        .emulateTransitionEnd(150) :Ð     next()Ð   $active.removeClass('in')Ð
  }Ð // TAB PLUGIN DEFINITIONÐ // ====================Ð var old = $.fn.tabÐ
$.fn.tab = function ( option ) {Ð   return this.each(function () {Ð     var
$this = $(this)Ð     var data  = $this.data('bs.tab')Ð     if (!data)
$this.data('bs.tab', (data = new Tab(this)))Ð     if (typeof option ==
'string') data[option]()Ð   })Ð }Ð $.fn.tab.Constructor = TabÐ // TAB NO
CONFLICTÐ // ===============Ð $.fn.tab.noConflict = function () {Ð   $.fn.tab
= oldÐ   return thisÐ }Ð // TAB DATA-APIÐ // ============Ð
$(document).on('click.bs.tab.data-api', '[data-toggle="tab"], [data-
toggle="pill"]', function (e) {Ð   e.preventDefault()Ð   $(this).tab('show')Ð
  })Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: affix.js v3.0.3Ð* http://getbootstrap.com/javascript/#affixÐ*
========================================================================Ð*
Copyright 2013 Twitter, Inc.Ð*Ð* Licensed under the Apache License, Version
2.0 (the "License");Ð* you may not use this file except in compliance with
the License.Ð* You may obtain a copy of the License atÐ*Ð* http://
www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or
agreed to in writing, softwareÐ* distributed under the License is distributed
on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express or implied.Ð* See the License for the specific language governing
permissions andÐ* limitations under the License.Ð*
========================================================================== */Ð
+function ($) { "use strict";Ð // AFFIX CLASS DEFINITIONÐ //
======================Ð var Affix = function (element, options) {Ð
this.options = $.extend({}, Affix.DEFAULTS, options)Ð   this.$window =
$(window)Ð     .on('scroll.bs.affix.data-api', $.proxy(this.checkPosition,
this))Ð
```

```
            .on('click.bs.affix.data-api',
$.proxy(this.checkPositionWithEventLoop, this))Ð   this.$element = $(element)Ð
    this.affixed  =Ð   this.unpin    = nullÐ   this.checkPosition()Ð }Ð
Affix.RESET = 'affix affix-top affix-bottom'Ð Affix.DEFAULTS = {Ð   offset: 0Ð
  }Ð Affix.prototype.checkPositionWithEventLoop = function () {Ð
setTimeout($.proxy(this.checkPosition, this), 1)Ð }Ð
Affix.prototype.checkPosition = function () {Ð   if (!this.
$element.is(':visible')) returnÐ   var scrollHeight = $(document).height()Ð
var scrollTop    = this.$window.scrollTop()Ð   var position     = this.
$element.offset()Ð   var offset       = this.options.offsetÐ   var
offsetTop    = offset.topÐ   var offsetBottom = offset.bottomÐ   if (typeof
offset != 'object')         offsetBottom = offsetTop = offsetÐ   if (typeof
offsetTop == 'function')    offsetTop    = offset.top()Ð   if (typeof
offsetBottom == 'function') offsetBottom = offset.bottom()Ð   var affix =
this.unpin   != null && (scrollTop + this.unpin <= position.top) ? false :Ð
                offsetBottom != null && (position.top + this.
$element.height() >= scrollHeight - offsetBottom) ? 'bottom' :Ð
offsetTop    != null && (scrollTop <= offsetTop) ? 'top' : falseÐ   if
(this.affixed === affix) returnÐ   if (this.unpin) this.$element.css('top',
'')Ð   this.affixed = affixÐ   this.unpin   = affix == 'bottom' ?
position.top - scrollTop : nullÐ   this.
$element.removeClass(Affix.RESET).addClass('affix' + (affix ? '-' + affix :
''))Ð   if (affix == 'bottom') {Ð     this.$element.offset({ top:
document.body.offsetHeight - offsetBottom - this.$element.height() })Ð   }Ð }Ð
  // AFFIX PLUGIN DEFINITIONÐ // ======================Ð var old = $.fn.affixÐ
  $.fn.affix = function (option) {Ð   return this.each(function () {Ð     var
$this   = $(this)Ð     var data    = $this.data('bs.affix')Ð     var options
= typeof option == 'object' && optionÐ     if (!data) $this.data('bs.affix',
(data = new Affix(this, options)))Ð     if (typeof option == 'string')
data[option]()Ð   })Ð }Ð $.fn.affix.Constructor = AffixÐ // AFFIX NO CONFLICTÐ
  // ================Ð $.fn.affix.noConflict = function () {Ð   $.fn.affix =
oldÐ   return thisÐ }Ð // AFFIX DATA-APIÐ // =============Ð
$(window).on('load', function () {Ð   $('[data-spy="affix"]').each(function
() {Ð     var $spy = $(this)Ð     var data = $spy.data()Ð     data.offset =
data.offset || {}Ð     if (data.offsetBottom) data.offset.bottom =
data.offsetBottomÐ     if (data.offsetTop)    data.offset.top    =
data.offsetTopÐ     $spy.affix(data)Ð   })Ð })Ð}(jQuery);Ð
```

public\assets\frontend\js\forms.js

```
//  ==========================================================================Ð/•
Theme Name: Lumen - Multi-purpose Bootstrap TemplateÐ/•F†VÖR U$“¢//•
Description: This javascript file for Fiesta.Ð/•fW'6–öã¢  ã//” WF†÷#¢
Responsive ExpertÐ/” WF†÷" U$“¢ ‡GG ¢ò÷F†VÖVf÷&W7BææWB÷W6W"÷&W7 öç6—fVW‡ W'G≠/•
Tags:Ð/  ==========================================================================Ð
(function() {Ð'W6R 7G&–7B#½gVæ7F–öâ f Æ–F FUöVÖ –Â†VÖ –Â’—½   f " &Vr Ò õâ…´ Ð
Za-z0-9_\-\.])+\@([A-Za-z0-9_\-\.])+\.([A-Za-z]{2,4})$/;Ð   &WGW&â
reg.test(email);ÐÝB†Fö7VÖVçB’ç&V G’†gVæ7F–öâ†R’ ™½$('#contact-
submit').click(function(e) {™–Rç &WfVçDFVf VÇB,™½6öçF 7E÷7V&Ö—B,™½);™Ð
$('input:text, textarea').keyup(function(e) {™’B‡F†—2’ç&VÖ÷fT6Æ 72,vW'&÷"r™½);™Ð
$('#contact-error').hide();™$('#contact-loading').hide();™Þ('#contact-
success').hide();™$('#contact-failed').hide();™Þ('#rsvp-error').hide();™Þ('#rsvp-
loading').hide();™$('#rsvp-success').hide();™Þ('#rsvp-failed').hide();÷Ð“½òò
Contact form validationÐgVæ7F–öâ 6öçF 7E÷7V&Ö—B,•™$('#contact-error').hide();™Ð
var submit_flag = 'yes';™var contact_name = $('#contact-name').val();™Ð
if( contact_name ==='')™™™{ÐÐif(submit_flag == 'yes™™™™){ÐÐB,r66öçF 7BÖæ ÖRr’æfö7W2,™™™™½Ð
$('#contact-name').addClass('error');™™submit_flag = 'no™™™}Ðar contact_email
=$('#contact-email').val();™if(contact_email ==''™™™™){ÐÐif(submit_flag == 'yes™™™™){Ð
$('#contact-email').focus();™™™™}Þ('#contact-email').addClass('error');™™Ð
submit_flag = 'no';™™™}Ðif(!validate_email(contact_email)™™™™{ÐÐif(submit_flag ==
'yes')™™™™™{ÐB,r66öçF 7BÖVÖ –Âr’æfö7W2,™™™™½Þ('#contact-email').addClass('error');™™Ð
submit_flag = 'no';™™™}Ðar contact_phone = $('#contact-phone').val();™Ð
if( contact_phone ==='')™™™™™Ð{Ðif(submit_flag == 'yes™™™™™™){ÐÐB,r66öçF 7B× †öæRr’æfö7W2,™™™™½Ð
$('#contact-phone').addClass('error');™™submit_flag = 'no™™™}Ðar contact_msg =
$('#contact-msg').val();™if( contact_msg ==='' || contact_msg== 'Your Message
*')™™™™™Ð{Ðif(submit_flag == 'yes™™™™™™){ÐÐB,r66öçF 7BÖ×6rr’æfö7W2,™™™™½Þ('#contact-
msg').addClass('error');™™submit_flag = 'no™™™}Ðif(submit_flag != 'yes')™™™{•
$('#contact-error').show().html('Please review the above details filled');™™™}Ð
else™™™™{ÐB,r66öçF 7BÖW'&÷"r’æ†–FR,™½B,r66öçF 7B×7V66W72r’æ†–FR,™½B,r66öçF 7BÐ
failed').hide();™™™™™™
```

public\assets\frontend\js\jquery.flexslider.js

```
/*Ð* jQuery FlexSlider v2.2.2Ð* Copyright 2012 WooThemesÐ* Contributing
Author: Tyler SmithÐ*/ÐÐ(function ($) {Ð //FlexSlider: Object InstanceÐ
$.flexslider = function(el, options) {Ð   var slider = $(el);Ð   // making
variables publicÐ   slider.vars = $.extend({}, $.flexslider.defaults,
options);Ð   var namespace = slider.vars.namespace,Ð       msGesture =
window.navigator && window.navigator.msPointerEnabled && window.MSGesture,Ð
        touch = (( "ontouchstart" in window ) || msGesture ||
window.DocumentTouch && document instanceof DocumentTouch) &&
slider.vars.touch,Ð       // depricating this idea, as devices are being
released with both of these eventsÐ       //eventType = (touch) ?
"touchend" : "click",Ð       eventType = "click touchend MSPointerUp",Ð
watchedEvent = "",Ð       watchedEventClearTimer,Ð       vertical =
slider.vars.direction === "vertical",Ð       reverse = slider.vars.reverse,Ð
        carousel = (slider.vars.itemWidth > 0),Ð       fade =
slider.vars.animation === "fade",Ð       asNav = slider.vars.asNavFor !== "",Ð
        methods = {},Ð       focused = true;Ð   // Store a reference to the
slider objectÐ   $.data(el, "flexslider", slider);Ð   // Private slider
methodsÐ   methods = {Ð     init: function() {Ð       slider.animating =
false;Ð       // Get current slide and make sure it is a numberÐ
slider.currentSlide = parseInt( ( slider.vars.startAt ? slider.vars.startAt :
0), 10 );Ð       if ( isNaN( slider.currentSlide ) ) slider.currentSlide = 0;Ð
        slider.animatingTo = slider.currentSlide;Ð       slider.atEnd =
(slider.currentSlide === 0 || slider.currentSlide === slider.last);Ð
slider.containerSelector =
slider.vars.selector.substr(0,slider.vars.selector.search(' '));Ð
slider.slides = $(slider.vars.selector, slider);Ð       slider.container =
$(slider.containerSelector, slider);Ð       slider.count =
slider.slides.length;Ð       // SYNC:Ð       slider.syncExists =
$(slider.vars.sync).length > 0;Ð       // SLIDE:Ð       if
(slider.vars.animation === "slide") slider.vars.animation = "swing";Ð
slider.prop = (vertical) ? "top" : "marginLeft";Ð       slider.args = {};Ð
        // SLIDESHOW:Ð       slider.manualPause = false;Ð
slider.stopped = false;Ð       //PAUSE WHEN INVISIBLEÐ       slider.started =
false;Ð       slider.startTimeout = null;Ð       // TOUCH/USECSS:Ð
slider.transitions = !slider.vars.video && !fade && slider.vars.useCSS &&
(function() {Ð         var obj = document.createElement('div'),Ð
props = ['perspectiveProperty', 'WebkitPerspective', 'MozPerspective',
'OPerspective', 'msPerspective'];Ð         for (var i in props) {Ð
if ( obj.style[ props[i] ] !== undefined ) {Ð             slider.pfx =
props[i].replace('Perspective','').toLowerCase();Ð             slider.prop =
"-" + slider.pfx + "-transform";Ð             return true;Ð           }Ð
          }Ð         return false;Ð       }());Ð       // CONTROLSCONTAINER:Ð
        if (slider.vars.controlsContainer !== "") slider.controlsContainer =
$(slider.vars.controlsContainer).length > 0 &&
$(slider.vars.controlsContainer);Ð       // MANUAL:Ð       if
(slider.vars.manualControls !== "") slider.manualControls =
$(slider.vars.manualControls).length > 0 && $(slider.vars.manualControls);Ð
        // RANDOMIZE:Ð       if (slider.vars.randomize) {Ð
slider.slides.sort(function() { return (Math.round(Math.random())-0.5); });Ð
          slider.container.empty().append(slider.slides);Ð       }Ð
slider.doMath();Ð       // INITÐ       slider.setup("init");Ð       //
CONTROLNAV:Ð       if (slider.vars.controlNav) methods.controlNav.setup();Ð
        // DIRECTIONNAV:Ð       if (slider.vars.directionNav)
methods.directionNav.setup();Ð       // KEYBOARD:Ð       if
(slider.vars.keyboard && ($(slider.containerSelector).length === 1 ||
slider.vars.multipleKeyboard)) {Ð         $(document).bind('keyup',
function(event) {Ð           var keycode = event.keyCode;Ð           if (!
slider.animating && (keycode === 39 || keycode === 37)) {Ð             var
target = (keycode === 39) ? slider.getTarget('next') :Ð
```

```
                            (keycode === 37) ? slider.getTarget('prev') :
false;Ð              slider.flexAnimate(target, slider.vars.pauseOnAction);Ð
            }Ð         });Ð       }Ð       // MOUSEWHEEL:Ð       if
(slider.vars.mousewheel) {Ð         slider.bind('mousewheel', function(event,
delta, deltaX, deltaY) {Ð           event.preventDefault();Ð           var
target = (delta < 0) ? slider.getTarget('next') : slider.getTarget('prev');Ð
            slider.flexAnimate(target, slider.vars.pauseOnAction);Ð
          });Ð       }Ð       // PAUSEPLAYÐ       if (slider.vars.pausePlay)
methods.pausePlay.setup();Ð       //PAUSE WHEN INVISIBLEÐ       if
(slider.vars.slideshow && slider.vars.pauseInvisible)
methods.pauseInvisible.init();Ð       // SLIDSESHOWÐ       if
(slider.vars.slideshow) {Ð         if (slider.vars.pauseOnHover) {Ð
slider.hover(function() {Ð             if (!slider.manualPlay && !
slider.manualPause) slider.pause();Ð           }, function() {Ð
if (!slider.manualPause && !slider.manualPlay && !slider.stopped)
slider.play();Ð           });Ð         }Ð         // initialize animationÐ
          //If we're visible, or we don't use PageVisibility APIÐ         if(!
slider.vars.pauseInvisible || !methods.pauseInvisible.isHidden()) {Ð
            (slider.vars.initDelay > 0) ? slider.startTimeout =
setTimeout(slider.play, slider.vars.initDelay) : slider.play();Ð         }Ð
        }Ð       // ASNAV:Ð       if (asNav) methods.asNav.setup();Ð       //
TOUCHÐ       if (touch && slider.vars.touch) methods.touch();Ð       //
FADE&&SMOOTHHEIGHT || SLIDE:Ð       if (!fade || (fade &&
slider.vars.smoothHeight)) $(window).bind("resize orientationchange focus",
methods.resize);Ð       slider.find("img").attr("draggable", "false");Ð
        // API: start() CallbackÐ       setTimeout(function(){Ð
slider.vars.start(slider);Ð       }, 200);Ð     },Ð     asNav: {Ð
setup: function() {Ð         slider.asNav = true;Ð         slider.animatingTo
= Math.floor(slider.currentSlide/slider.move);Ð         slider.currentItem =
slider.currentSlide;Ð         slider.slides.removeClass(namespace + "active-
slide").eq(slider.currentItem).addClass(namespace + "active-slide");Ð
if(!msGesture){Ð             slider.slides.on(eventType, function(e){Ð
                e.preventDefault();Ð               var $slide = $(this),Ð
                    target = $slide.index();Ð               var posFromLeft =
$slide.offset().left - $(slider).scrollLeft(); // Find position of slide
relative to left of slider containerÐ               if( posFromLeft <= 0 &&
$slide.hasClass( namespace + 'active-slide' ) ) {Ð
slider.flexAnimate(slider.getTarget("prev"), true);Ð               } else if
(!$(slider.vars.asNavFor).data('flexslider').animating && !
$slide.hasClass(namespace + "active-slide")) {Ð
slider.direction = (slider.currentItem < target) ? "next" : "prev";Ð
                  slider.flexAnimate(target, slider.vars.pauseOnAction,
false, true, true);Ð               }Ð             });Ð         }else{Ð
              el._slider = slider;Ð             slider.slides.each(function ()
{Ð                 var that = this;Ð                 that._gesture = new
MSGesture();Ð                 that._gesture.target = that;Ð
that.addEventListener("MSPointerDown", function (e){Ð
e.preventDefault();Ð                     if(e.currentTarget._gesture)Ð
                          e.currentTarget._gesture.addPointer(e.pointerId);Ð
                  }, false);Ð
that.addEventListener("MSGestureTap", function (e){Ð
e.preventDefault();Ð                     var $slide = $(this),Ð
                          target = $slide.index();Ð                     if (!
$(slider.vars.asNavFor).data('flexslider').animating && !
$slide.hasClass('active')) {Ð                         slider.direction =
(slider.currentItem < target) ? "next" : "prev";Ð
slider.flexAnimate(target, slider.vars.pauseOnAction, false, true, true);Ð
                      }Ð                 });Ð             });Ð         }Ð
        }Ð
```

```
                },Ð     controlNav: {Ð       setup: function() {Ð         if (!
slider.manualControls) {Ð           methods.controlNav.setupPaging();Ð
          } else { // MANUALCONTROLS:Ð
methods.controlNav.setupManual();Ð         }Ð       },Ð       setupPaging:
function() {Ð         var type = (slider.vars.controlNav === "thumbnails") ?
'control-thumbs' : 'control-paging',Ð             j = 1,Ð             item,Ð
              slide;Ð         slider.controlNavScaffold = $('<ol class="'+
namespace + 'control-nav ' + namespace + type + '"></ol>');Ð         if
(slider.pagingCount > 1) {Ð           for (var i = 0; i < slider.pagingCount;
i++) {Ð             slide = slider.slides.eq(i);Ð             item =
(slider.vars.controlNav === "thumbnails") ? '<img src="' + slide.attr( 'data-
thumb' ) + '"/>' : '<a>' + j + '</a>';Ð             if ( 'thumbnails' ===
slider.vars.controlNav && true === slider.vars.thumbCaptions ) {Ð
                var captn = slide.attr( 'data-thumbcaption' );Ð
if ( '' != captn && undefined != captn ) item += '<span class="' + namespace
+ 'caption">' + captn + '</span>';Ð             }Ð
slider.controlNavScaffold.append('<li>' + item + '</li>');Ð             j++;Ð
            }Ð         }Ð         // CONTROLSCONTAINER:Ð
(slider.controlsContainer) ?
$(slider.controlsContainer).append(slider.controlNavScaffold) :
slider.append(slider.controlNavScaffold);Ð         methods.controlNav.set();Ð
          methods.controlNav.active();Ð
slider.controlNavScaffold.delegate('a, img', eventType, function(event) {Ð
            event.preventDefault();Ð           if (watchedEvent === "" ||
watchedEvent === event.type) {Ð             var $this = $(this),Ð
                  target = slider.controlNav.index($this);Ð             if (!
$this.hasClass(namespace + 'active')) {Ð               slider.direction =
(target > slider.currentSlide) ? "next" : "prev";Ð
slider.flexAnimate(target, slider.vars.pauseOnAction);Ð             }Ð
            }Ð           // setup flags to prevent event duplicationÐ
            if (watchedEvent === "") {Ð             watchedEvent = event.type;Ð
            }Ð           methods.setToClearWatchedEvent();Ð         });Ð
        },Ð       setupManual: function() {Ð         slider.controlNav =
slider.manualControls;Ð         methods.controlNav.active();Ð
slider.controlNav.bind(eventType, function(event) {Ð
event.preventDefault();Ð           if (watchedEvent === "" || watchedEvent
=== event.type) {Ð             var $this = $(this),Ð                target =
slider.controlNav.index($this);Ð             if (!$this.hasClass(namespace +
'active')) {Ð               (target > slider.currentSlide) ? slider.direction
= "next" : slider.direction = "prev";Ð
slider.flexAnimate(target, slider.vars.pauseOnAction);Ð             }Ð
            }Ð           // setup flags to prevent event duplicationÐ
            if (watchedEvent === "") {Ð             watchedEvent = event.type;Ð
            }Ð           methods.setToClearWatchedEvent();Ð         });Ð
        },Ð       set: function() {Ð         var selector =
(slider.vars.controlNav === "thumbnails") ? 'img' : 'a';Ð
slider.controlNav = $('.' + namespace + 'control-nav li ' + selector,
(slider.controlsContainer) ? slider.controlsContainer : slider);Ð       },Ð
        active: function() {Ð         slider.controlNav.removeClass(namespace
+ "active").eq(slider.animatingTo).addClass(namespace + "active");Ð       },Ð
        update: function(action, pos) {Ð         if (slider.pagingCount > 1
&& action === "add") {Ð
slider.controlNavScaffold.append($('<li><a>' + slider.count + '</a></li>'));Ð
          } else if (slider.pagingCount === 1) {Ð
slider.controlNavScaffold.find('li').remove();Ð         } else {Ð
slider.controlNav.eq(pos).closest('li').remove();Ð         }Ð
methods.controlNav.set();Ð         (slider.pagingCount > 1 &&
slider.pagingCount !== slider.controlNav.length) ? slider.update(pos,
action) : methods.controlNav.active();Ð       }Ð     },Ð     directionNav: {Ð
        setup: function() {Ð
```

```
                                    var directionNavScaffold = $('<ul
class="' + namespace + 'direction-nav"><li><a class="' + namespace + 'prev"
href="#">' + slider.vars.prevText + '</a></li><li><a class="' + namespace +
'next" href="#">' + slider.vars.nextText + '</a></li></ul>');Ð         //
CONTROLSCONTAINER:Ð         if (slider.controlsContainer) {Ð
$(slider.controlsContainer).append(directionNavScaffold);Ð
slider.directionNav = $('.' + namespace + 'direction-nav li a',
slider.controlsContainer);Ð         } else {Ð
slider.append(directionNavScaffold);Ð           slider.directionNav = $('.' +
namespace + 'direction-nav li a', slider);Ð         }Ð
methods.directionNav.update();Ð         slider.directionNav.bind(eventType,
function(event) {Ð           event.preventDefault();Ð           var target;Ð
            if (watchedEvent === "" || watchedEvent === event.type) {Ð
              target = ($(this).hasClass(namespace + 'next')) ?
slider.getTarget('next') : slider.getTarget('prev');Ð
slider.flexAnimate(target, slider.vars.pauseOnAction);Ð           }Ð
            // setup flags to prevent event duplicationÐ           if
(watchedEvent === "") {Ð             watchedEvent = event.type;Ð           }Ð
            methods.setToClearWatchedEvent();Ð         });Ð       },Ð
update: function() {Ð         var disabledClass = namespace + 'disabled';Ð
          if (slider.pagingCount === 1) {Ð
slider.directionNav.addClass(disabledClass).attr('tabindex', '-1');Ð
          } else if (!slider.vars.animationLoop) {Ð           if
(slider.animatingTo === 0) {Ð
slider.directionNav.removeClass(disabledClass).filter('.' + namespace +
"prev").addClass(disabledClass).attr('tabindex', '-1');Ð           } else if
(slider.animatingTo === slider.last) {Ð
slider.directionNav.removeClass(disabledClass).filter('.' + namespace +
"next").addClass(disabledClass).attr('tabindex', '-1');Ð           } else {Ð

slider.directionNav.removeClass(disabledClass).removeAttr('tabindex');Ð
            }Ð         } else {Ð
slider.directionNav.removeClass(disabledClass).removeAttr('tabindex');Ð
          }Ð       }Ð     },Ð     pausePlay: {Ð       setup: function() {Ð
          var pausePlayScaffold = $('<div class="' + namespace +
'pauseplay"><a></a></div>');Ð         // CONTROLSCONTAINER:Ð         if
(slider.controlsContainer) {Ð
slider.controlsContainer.append(pausePlayScaffold);Ð
slider.pausePlay = $('.' + namespace + 'pauseplay a',
slider.controlsContainer);Ð         } else {Ð
slider.append(pausePlayScaffold);Ð           slider.pausePlay = $('.' +
namespace + 'pauseplay a', slider);Ð         }Ð
methods.pausePlay.update((slider.vars.slideshow) ? namespace + 'pause' :
namespace + 'play');Ð         slider.pausePlay.bind(eventType,
function(event) {Ð           event.preventDefault();Ð           if
(watchedEvent === "" || watchedEvent === event.type) {Ð             if
($(this).hasClass(namespace + 'pause')) {Ð               slider.manualPause =
true;Ð               slider.manualPlay = false;Ð               slider.pause();Ð
              } else {Ð               slider.manualPause = false;Ð
                slider.manualPlay = true;Ð               slider.play();Ð
              }Ð           }Ð           // setup flags to prevent event
duplicationÐ           if (watchedEvent === "") {Ð             watchedEvent =
event.type;Ð           }Ð           methods.setToClearWatchedEvent();Ð
          });Ð       },Ð       update: function(state) {Ð         (state ===
"play") ? slider.pausePlay.removeClass(namespace +
'pause').addClass(namespace + 'play').html(slider.vars.playText) :
slider.pausePlay.removeClass(namespace + 'play').addClass(namespace +
'pause').html(slider.vars.pauseText);Ð       }Ð     },Ð     touch: function()
{Ð       var startX,Ð         startY,Ð         offset,Ð         cwidth,Ð
          dx,Ð
```

```
                        startT,Ð         scrolling = false,Ð         localX =
0,Ð         localY = 0,Ð         accDx = 0;Ð       if(!msGesture){Ð
el.addEventListener('touchstart', onTouchStart, false);Ð           function
onTouchStart(e) {Ð             if (slider.animating) {Ð
e.preventDefault();Ð             } else if
( ( window.navigator.msPointerEnabled ) || e.touches.length === 1 ) {Ð
                slider.pause();Ð               // CAROUSEL:Ð
cwidth = (vertical) ? slider.h : slider. w;Ð               startT =
Number(new Date());Ð               // CAROUSEL:Ð               // Local vars
for X and Y points.Ð               localX = e.touches[0].pageX;Ð
                localY = e.touches[0].pageY;Ð               offset =
(carousel && reverse && slider.animatingTo === slider.last) ? 0 :Ð
                        (carousel && reverse) ? slider.limit -
(((slider.itemW + slider.vars.itemMargin) * slider.move) *
slider.animatingTo) :Ð                        (carousel &&
slider.currentSlide === slider.last) ? slider.limit :Ð
(carousel) ? ((slider.itemW + slider.vars.itemMargin) * slider.move) *
slider.currentSlide :Ð                        (reverse) ? (slider.last -
slider.currentSlide + slider.cloneOffset) * cwidth : (slider.currentSlide +
slider.cloneOffset) * cwidth;Ð               startX = (vertical) ? localY :
localX;Ð               startY = (vertical) ? localX : localY;Ð
el.addEventListener('touchmove', onTouchMove, false);Ð
el.addEventListener('touchend', onTouchEnd, false);Ð             }Ð
            }Ð           function onTouchMove(e) {Ð             // Local vars
for X and Y points.Ð             localX = e.touches[0].pageX;Ð
localY = e.touches[0].pageY;Ð             dx = (vertical) ? startX - localY :
startX - localX;Ð             scrolling = (vertical) ? (Math.abs(dx) <
Math.abs(localX - startY)) : (Math.abs(dx) < Math.abs(localY - startY));Ð
              var fxms = 500;Ð             if ( ! scrolling || Number( new
Date() ) - startT > fxms ) {Ð               e.preventDefault();Ð
                if (!fade && slider.transitions) {Ð                 if (!
slider.vars.animationLoop) {Ð                   dx = dx/((slider.currentSlide
=== 0 && dx < 0 || slider.currentSlide === slider.last && dx > 0) ?
(Math.abs(dx)/cwidth+2) : 1);Ð                 }Ð
slider.setProps(offset + dx, "setTouch");Ð               }Ð             }Ð
            }Ð           function onTouchEnd(e) {Ð             // finish the
touch by undoing the touch sessionÐ
el.removeEventListener('touchmove', onTouchMove, false);Ð             if
(slider.animatingTo === slider.currentSlide && !scrolling && !(dx === null)) {Ð
                var updateDx = (reverse) ? -dx : dx,Ð
target = (updateDx > 0) ? slider.getTarget('next') : slider.getTarget('prev');Ð
                if (slider.canAdvance(target) && (Number(new Date()) - startT
< 550 && Math.abs(updateDx) > 50 || Math.abs(updateDx) > cwidth/2)) {Ð
                  slider.flexAnimate(target, slider.vars.pauseOnAction);Ð
                } else {Ð                 if (!fade)
slider.flexAnimate(slider.currentSlide, slider.vars.pauseOnAction, true);Ð
                }Ð             }Ð
el.removeEventListener('touchend', onTouchEnd, false);Ð             startX =
null;Ð             startY = null;Ð             dx = null;Ð             offset
= null;Ð             }Ð       }else{Ð           el.style.msTouchAction = "none";Ð
            el._gesture = new MSGesture();Ð           el._gesture.target = el;Ð
            el.addEventListener("MSPointerDown", onMSPointerDown, false);Ð
            el._slider = slider;Ð
el.addEventListener("MSGestureChange", onMSGestureChange, false);Ð
el.addEventListener("MSGestureEnd", onMSGestureEnd, false);Ð
function onMSPointerDown(e){Ð               e.stopPropagation();Ð
                if (slider.animating) {Ð                   e.preventDefault();Ð
                }else{Ð                   slider.pause();Ð
el._gesture.addPointer(e.pointerId);Ð                   accDx = 0;Ð
                     cwidth = (vertical) ? slider.h : slider. w;Ð
```

```
                    startT = Number(new Date());Ð                    //
CAROUSEL:Ð                    offset = (carousel && reverse &&
slider.animatingTo === slider.last) ? 0 :Ð                        (carousel &&
reverse) ? slider.limit - (((slider.itemW + slider.vars.itemMargin) *
slider.move) * slider.animatingTo) :Ð                            (carousel &&
slider.currentSlide === slider.last) ? slider.limit :Ð
                                (carousel) ? ((slider.itemW +
slider.vars.itemMargin) * slider.move) * slider.currentSlide :Ð
                                   (reverse) ? (slider.last -
slider.currentSlide + slider.cloneOffset) * cwidth : (slider.currentSlide +
slider.cloneOffset) * cwidth;Ð               }Ð           }Ð
function onMSGestureChange(e) {Ð               e.stopPropagation();Ð
                var slider = e.target._slider;Ð               if(!slider){Ð
                    return;Ð               }Ð               var transX = -
e.translationX,Ð                    transY = -e.translationY;Ð               //
Accumulate translations.Ð                accdx = accDx + ((vertical) ?
transY : transX);Ð               dx = accDx;Ð               scrolling =
(vertical) ? (Math.abs(accDx) < Math.abs(-transX)) : (Math.abs(accDx) <
Math.abs(-transY));Ð               if(e.detail === e.MSGESTURE_FLAG_INERTIA){Ð
                    setImmediate(function (){Ð
el._gesture.stop();Ð                  });Ð                  return;Ð
                }Ð               if (!scrolling || Number(new Date()) -
startT > 500) {Ð                  e.preventDefault();Ð                  if
(!fade && slider.transitions) {Ð                        if (!
slider.vars.animationLoop) {Ð                          dx = accDx /
((slider.currentSlide === 0 && accDx < 0 || slider.currentSlide ===
slider.last && accDx > 0) ? (Math.abs(accDx) / cwidth + 2) : 1);Ð
                        }Ð                        slider.setProps(offset + dx,
"setTouch");Ð                    }Ð               }Ð           }Ð
function onMSGestureEnd(e) {Ð               e.stopPropagation();Ð
                var slider = e.target._slider;Ð               if(!slider){Ð
                    return;Ð               }Ð               if
(slider.animatingTo === slider.currentSlide && !scrolling && !(dx === null)) {Ð
                    var updateDx = (reverse) ? -dx : dx,Ð
                        target = (updateDx > 0) ? slider.getTarget('next') :
slider.getTarget('prev');Ð                  if (slider.canAdvance(target) &&
(Number(new Date()) - startT < 550 && Math.abs(updateDx) > 50 ||
Math.abs(updateDx) > cwidth/2)) {Ð
slider.flexAnimate(target, slider.vars.pauseOnAction);Ð                  }
else {Ð                        if (!fade)
slider.flexAnimate(slider.currentSlide, slider.vars.pauseOnAction, true);Ð
                    }Ð               }Ð               startX = null;Ð
                startY = null;Ð               dx = null;Ð
offset = null;Ð               accDx = 0;Ð           }Ð       }Ð     },Ð
resize: function() {Ð       if (!slider.animating && slider.is(':visible')) {Ð
          if (!carousel) slider.doMath();Ð         if (fade) {Ð           //
SMOOTH HEIGHT:Ð           methods.smoothHeight();Ð         } else if
(carousel) { //CAROUSEL:Ð           slider.slides.width(slider.computedW);Ð
            slider.update(slider.pagingCount);Ð           slider.setProps();Ð
          }Ð         else if (vertical) { //VERTICAL:Ð
slider.viewport.height(slider.h);Ð           slider.setProps(slider.h,
"setTotal");Ð         } else {Ð           // SMOOTH HEIGHT:Ð           if
(slider.vars.smoothHeight) methods.smoothHeight();Ð
slider.newSlides.width(slider.computedW);Ð
slider.setProps(slider.computedW, "setTotal");Ð         }Ð       }Ð     },Ð
      smoothHeight: function(dur) {Ð       if (!vertical || fade) {Ð
var $obj = (fade) ? slider : slider.viewport;Ð         (dur) ?
$obj.animate({"height": slider.slides.eq(slider.animatingTo).height()},
dur) : $obj.height(slider.slides.eq(slider.animatingTo).height());Ð
```

```
                                                                    }Ð
      },Ð     sync: function(action) {Ð       var $obj =
$(slider.vars.sync).data("flexslider"),Ð           target =
slider.animatingTo;Ð       switch (action) {Ð         case "animate":
$obj.flexAnimate(target, slider.vars.pauseOnAction, false, true); break;Ð
          case "play": if (!$obj.playing && !$obj.asNav) { $obj.play(); }
break;Ð         case "pause": $obj.pause(); break;Ð       }Ð     },Ð
uniqueID: function($clone) {Ð       $clone.find( '[id]' ).each(function() {Ð
          var $this = $(this);Ð         $this.attr( 'id', $this.attr( 'id' )
+ '_clone' );Ð       });Ð       return $clone;Ð     },Ð     pauseInvisible: {Ð
        visProp: null,Ð       init: function() {Ð         var prefixes =
['webkit','moz','ms','o'];Ð         if ('hidden' in document) return 'hidden';Ð
          for (var i = 0; i < prefixes.length; i++) {Ð           if
((prefixes[i] + 'Hidden') in document)Ð
methods.pauseInvisible.visProp = prefixes[i] + 'Hidden';Ð         }Ð
if (methods.pauseInvisible.visProp) {Ð           var evtname =
methods.pauseInvisible.visProp.replace(/[H|h]idden/,'') + 'visibilitychange';Ð
            document.addEventListener(evtname, function() {Ð             if
(methods.pauseInvisible.isHidden()) {Ð               if(slider.startTimeout)
clearTimeout(slider.startTimeout); //If clock is ticking, stop timer and
prevent from starting while invisibleÐ               else slider.pause(); //
Or just pauseÐ             }Ð             else {Ð
if(slider.started) slider.play(); //Initiated before, just playÐ
                else (slider.vars.initDelay > 0) ? setTimeout(slider.play,
slider.vars.initDelay) : slider.play(); //Didn't init before: simply init or
wait for itÐ             }Ð           });Ð         }Ð       },Ð
isHidden: function() {Ð         return
document[methods.pauseInvisible.visProp] || false;Ð       }Ð     },Ð
setToClearWatchedEvent: function() {Ð
clearTimeout(watchedEventClearTimer);Ð       watchedEventClearTimer =
setTimeout(function() {Ð         watchedEvent = "";Ð       }, 3000);Ð     }Ð
    };Ð   // public methodsÐ   slider.flexAnimate = function(target, pause,
override, withSync, fromNav) {Ð     if (!slider.vars.animationLoop && target !
== slider.currentSlide) {Ð       slider.direction = (target >
slider.currentSlide) ? "next" : "prev";Ð     }Ð     if (asNav &&
slider.pagingCount === 1) slider.direction = (slider.currentItem < target) ?
"next" : "prev";Ð     if (!slider.animating && (slider.canAdvance(target,
fromNav) || override) && slider.is(":visible")) {Ð       if (asNav &&
withSync) {Ð         var master = $(slider.vars.asNavFor).data('flexslider');Ð
          slider.atEnd = target === 0 || target === slider.count - 1;Ð
          master.flexAnimate(target, true, false, true, fromNav);Ð
slider.direction = (slider.currentItem < target) ? "next" : "prev";Ð
master.direction = slider.direction;Ð         if (Math.ceil((target + 1)/
slider.visible) - 1 !== slider.currentSlide && target !== 0) {Ð
slider.currentItem = target;Ð           slider.slides.removeClass(namespace +
"active-slide").eq(target).addClass(namespace + "active-slide");Ð
target = Math.floor(target/slider.visible);Ð         } else {Ð
slider.currentItem = target;Ð           slider.slides.removeClass(namespace +
"active-slide").eq(target).addClass(namespace + "active-slide");Ð
return false;Ð         }Ð       }Ð       slider.animating = true;Ð
slider.animatingTo = target;Ð       // SLIDESHOW:Ð       if (pause)
slider.pause();Ð       // API: before() animation CallbackÐ
slider.vars.before(slider);Ð       // SYNC:Ð       if (slider.syncExists && !
fromNav) methods.sync("animate");Ð       // CONTROLNAVÐ       if
(slider.vars.controlNav) methods.controlNav.active();Ð       // !CAROUSEL:Ð
        // CANDIDATE: slide active class (for add/remove slide)Ð       if (!
carousel) slider.slides.removeClass(namespace + 'active-
slide').eq(target).addClass(namespace + 'active-slide');Ð       // INFINITE
LOOP:Ð       // CANDIDATE: atEndÐ       slider.atEnd = target === 0 || target
=== slider.last;Ð
```

```
                Ð       // DIRECTIONNAV:Ð       if (slider.vars.directionNav)
methods.directionNav.update();Ð       if (target === slider.last) {Ð
          // API: end() of cycle CallbackÐ         slider.vars.end(slider);Ð
          // SLIDESHOW && !INFINITE LOOP:Ð         if (!
slider.vars.animationLoop) slider.pause();Ð       }Ð       // SLIDE:Ð
if (!fade) {Ð         var dimension = (vertical) ?
slider.slides.filter(':first').height() : slider.computedW,Ð
margin, slideString, calcNext;Ð         // INFINITE LOOP / REVERSE:Ð
if (carousel) {Ð           //margin = (slider.vars.itemWidth > slider.w) ?
slider.vars.itemMargin * 2 : slider.vars.itemMargin;Ð           margin =
slider.vars.itemMargin;Ð           calcNext = ((slider.itemW + margin) *
slider.move) * slider.animatingTo;Ð           slideString = (calcNext >
slider.limit && slider.visible !== 1) ? slider.limit : calcNext;Ð         }
else if (slider.currentSlide === 0 && target === slider.count - 1 &&
slider.vars.animationLoop && slider.direction !== "next") {Ð
slideString = (reverse) ? (slider.count + slider.cloneOffset) * dimension : 0;Ð
          } else if (slider.currentSlide === slider.last && target === 0 &&
slider.vars.animationLoop && slider.direction !== "prev") {Ð
slideString = (reverse) ? 0 : (slider.count + 1) * dimension;Ð         } else
{Ð           slideString = (reverse) ? ((slider.count - 1) - target +
slider.cloneOffset) * dimension : (target + slider.cloneOffset) * dimension;Ð
          }Ð         slider.setProps(slideString, "",
slider.vars.animationSpeed);Ð         if (slider.transitions) {Ð           if
(!slider.vars.animationLoop || !slider.atEnd) {Ð             slider.animating
= false;Ð             slider.currentSlide = slider.animatingTo;Ð           }Ð
            slider.container.unbind("webkitTransitionEnd transitionend");Ð
            slider.container.bind("webkitTransitionEnd transitionend",
function() {Ð             slider.wrapup(dimension);Ð           });Ð         }
else {Ð           slider.container.animate(slider.args,
slider.vars.animationSpeed, slider.vars.easing, function(){Ð
slider.wrapup(dimension);Ð           });Ð         }Ð       } else { // FADE:Ð
          if (!touch) {Ð           //
slider.slides.eq(slider.currentSlide).fadeOut(slider.vars.animationSpeed,
slider.vars.easing);Ð           //
slider.slides.eq(target).fadeIn(slider.vars.animationSpeed,
slider.vars.easing, slider.wrapup);Ð
slider.slides.eq(slider.currentSlide).css({"zIndex": 1}).animate({"opacity":
0}, slider.vars.animationSpeed, slider.vars.easing);Ð
slider.slides.eq(target).css({"zIndex": 2}).animate({"opacity": 1},
slider.vars.animationSpeed, slider.vars.easing, slider.wrapup);Ð         }
else {Ð           slider.slides.eq(slider.currentSlide).css({ "opacity": 0,
"zIndex": 1 });Ð           slider.slides.eq(target).css({ "opacity": 1,
"zIndex": 2 });Ð           slider.wrapup(dimension);Ð         }Ð       }Ð
        // SMOOTH HEIGHT:Ð       if (slider.vars.smoothHeight)
methods.smoothHeight(slider.vars.animationSpeed);Ð     }Ð   };Ð
slider.wrapup = function(dimension) {Ð     // SLIDE:Ð     if (!fade && !
carousel) {Ð       if (slider.currentSlide === 0 && slider.animatingTo ===
slider.last && slider.vars.animationLoop) {Ð
slider.setProps(dimension, "jumpEnd");Ð       } else if (slider.currentSlide
=== slider.last && slider.animatingTo === 0 && slider.vars.animationLoop) {Ð
          slider.setProps(dimension, "jumpStart");Ð       }Ð     }Ð
slider.animating = false;Ð     slider.currentSlide = slider.animatingTo;Ð
      // API: after() animation CallbackÐ     slider.vars.after(slider);Ð   };Ð
    // SLIDESHOW:Ð   slider.animateSlides = function() {Ð     if (!
slider.animating && focused ) slider.flexAnimate(slider.getTarget("next"));Ð
    };Ð   // SLIDESHOW:Ð   slider.pause = function() {Ð
clearInterval(slider.animatedSlides);Ð     slider.animatedSlides = null;Ð
slider.playing = false;Ð     // PAUSEPLAY:Ð     if (slider.vars.pausePlay)
methods.pausePlay.update("play");Ð     // SYNC:Ð     if (slider.syncExists)
methods.sync("pause");Ð
```

```
                        };Ð   // SLIDESHOW:Ð   slider.play = function() {Ð
      if (slider.playing) clearInterval(slider.animatedSlides);Ð
slider.animatedSlides = slider.animatedSlides ||
setInterval(slider.animateSlides, slider.vars.slideshowSpeed);Ð
slider.started = slider.playing = true;Ð     // PAUSEPLAY:Ð     if
(slider.vars.pausePlay) methods.pausePlay.update("pause");Ð     // SYNC:Ð
if (slider.syncExists) methods.sync("play");Ð   };Ð   // STOP:Ð   slider.stop
= function () {Ð     slider.pause();Ð     slider.stopped = true;Ð   };Ð
slider.canAdvance = function(target, fromNav) {Ð     // ASNAV:Ð     var last
= (asNav) ? slider.pagingCount - 1 : slider.last;Ð     return (fromNav) ?
true :Ð            (asNav && slider.currentItem === slider.count - 1 &&
target === 0 && slider.direction === "prev") ? true :Ð            (asNav &&
slider.currentItem === 0 && target === slider.pagingCount - 1 &&
slider.direction !== "next") ? false :Ð            (target ===
slider.currentSlide && !asNav) ? false :Ð
(slider.vars.animationLoop) ? true :Ð            (slider.atEnd &&
slider.currentSlide === 0 && target === last && slider.direction !==
"next") ? false :Ð            (slider.atEnd && slider.currentSlide === last
&& target === 0 && slider.direction === "next") ? false :Ð            true;Ð
    };Ð   slider.getTarget = function(dir) {Ð     slider.direction = dir;Ð
      if (dir === "next") {Ð       return (slider.currentSlide ===
slider.last) ? 0 : slider.currentSlide + 1;Ð     } else {Ð       return
(slider.currentSlide === 0) ? slider.last : slider.currentSlide - 1;Ð     }Ð
    };Ð   // SLIDE:Ð   slider.setProps = function(pos, special, dur) {Ð
var target = (function() {Ð       var posCheck = (pos) ? pos : ((slider.itemW
+ slider.vars.itemMargin) * slider.move) * slider.animatingTo,Ð
posCalc = (function() {Ð             if (carousel) {Ð               return
(special === "setTouch") ? pos :Ð                     (reverse &&
slider.animatingTo === slider.last) ? 0 :Ð                     (reverse) ?
slider.limit - (((slider.itemW + slider.vars.itemMargin) * slider.move) *
slider.animatingTo) :Ð                     (slider.animatingTo ===
slider.last) ? slider.limit : posCheck;Ð             } else {Ð
switch (special) {Ð                 case "setTotal": return (reverse) ?
((slider.count - 1) - slider.currentSlide + slider.cloneOffset) * pos :
(slider.currentSlide + slider.cloneOffset) * pos;Ð                 case
"setTouch": return (reverse) ? pos : pos;Ð                 case "jumpEnd":
return (reverse) ? pos : slider.count * pos;Ð                 case
"jumpStart": return (reverse) ? slider.count * pos : pos;Ð
default: return pos;Ð               }Ð             }Ð           }());Ð
            return (posCalc * -1) + "px";Ð         }());Ð     if
(slider.transitions) {Ð       target = (vertical) ? "translate3d(0," + target
+ ",0)" : "translate3d(" + target + ",0,0)";Ð       dur = (dur !==
undefined) ? (dur/1000) + "s" : "0s";Ð       slider.container.css("-" +
slider.pfx + "-transition-duration", dur);Ð
slider.container.css("transition-duration", dur);Ð     }Ð
slider.args[slider.prop] = target;Ð     if (slider.transitions || dur ===
undefined) slider.container.css(slider.args);Ð
slider.container.css('transform',target);Ð   };Ð   slider.setup =
function(type) {Ð     // SLIDE:Ð     if (!fade) {Ð       var sliderOffset,
arr;Ð       if (type === "init") {Ð         slider.viewport = $('<div
class="' + namespace + 'viewport"></div>').css({"overflow": "hidden",
"position": "relative"}).appendTo(slider).append(slider.container);Ð
          // INFINITE LOOP:Ð         slider.cloneCount = 0;Ð
slider.cloneOffset = 0;Ð         // REVERSE:Ð         if (reverse) {Ð
            arr = $.makeArray(slider.slides).reverse();Ð
slider.slides = $(arr);Ð
slider.container.empty().append(slider.slides);Ð         }Ð       }Ð       //
INFINITE LOOP && !CAROUSEL:Ð       if (slider.vars.animationLoop && !
carousel) {Ð         slider.cloneCount = 2;Ð         slider.cloneOffset = 1;Ð
          // clear out old clonesÐ
```

```
                                        if (type !== "init")
slider.container.find('.clone').remove();Ð         // slider.container.append(
slider.slides.first().clone().addClass('clone').attr('aria-hidden',
'true')).prepend(slider.slides.last().clone().addClass('clone').attr('aria-
hidden', 'true'));Ð
methods.uniqueID( slider.slides.first().clone().addClass('clone').attr('aria-
hidden', 'true') ).appendTo( slider.container );Ð
methods.uniqueID( slider.slides.last().clone().addClass('clone').attr('aria-
hidden', 'true') ).prependTo( slider.container );Ð       }Ð
slider.newSlides = $(slider.vars.selector, slider);Ð       sliderOffset =
(reverse) ? slider.count - 1 - slider.currentSlide + slider.cloneOffset :
slider.currentSlide + slider.cloneOffset;Ð       // VERTICAL:Ð       if
(vertical && !carousel) {Ð         slider.container.height((slider.count +
slider.cloneCount) * 200 + "%").css("position", "absolute").width("100%");Ð
          setTimeout(function(){Ð           slider.newSlides.css({"display":
"block"});Ð           slider.doMath();Ð
slider.viewport.height(slider.h);Ð           slider.setProps(sliderOffset *
slider.h, "init");Ð         }, (type === "init") ? 100 : 0);Ð       } else {Ð
          slider.container.width((slider.count + slider.cloneCount) * 200 +
"%");Ð         slider.setProps(sliderOffset * slider.computedW, "init");Ð
          setTimeout(function(){Ð           slider.doMath();Ð
slider.newSlides.css({"width": slider.computedW, "float": "left", "display":
"block"});Ð           // SMOOTH HEIGHT:Ð           if
(slider.vars.smoothHeight) methods.smoothHeight();Ð         }, (type ===
"init") ? 100 : 0);Ð       }Ð     } else { // FADE:Ð
slider.slides.css({"width": "100%", "float": "left", "marginRight": "-100%",
"position": "relative"});Ð       if (type === "init") {Ð         if (!touch) {Ð
            //
slider.slides.eq(slider.currentSlide).fadeIn(slider.vars.animationSpeed,
slider.vars.easing);Ð           slider.slides.css({ "opacity": 0, "display":
"block", "zIndex": 1 }).eq(slider.currentSlide).css({"zIndex":
2}).animate({"opacity": 1},slider.vars.animationSpeed,slider.vars.easing);Ð
          } else {Ð           slider.slides.css({ "opacity": 0, "display":
"block", "webkitTransition": "opacity " + slider.vars.animationSpeed / 1000 +
"s ease", "zIndex": 1 }).eq(slider.currentSlide).css({ "opacity": 1,
"zIndex": 2});Ð         }Ð       }Ð       // SMOOTH HEIGHT:Ð       if
(slider.vars.smoothHeight) methods.smoothHeight();Ð     }Ð     // !CAROUSEL:Ð
      // CANDIDATE: active slideÐ     if (!carousel)
slider.slides.removeClass(namespace + "active-
slide").eq(slider.currentSlide).addClass(namespace + "active-slide");Ð     //
FlexSlider: init() CallbackÐ     slider.vars.init(slider);Ð   };Ð
slider.doMath = function() {Ð     var slide = slider.slides.first(),Ð
slideMargin = slider.vars.itemMargin,Ð         minItems =
slider.vars.minItems,Ð         maxItems = slider.vars.maxItems;Ð     slider.w
= (slider.viewport===undefined) ? slider.width() : slider.viewport.width();Ð
      slider.h = slide.height();Ð     slider.boxPadding = slide.outerWidth()
- slide.width();Ð     // CAROUSEL:Ð     if (carousel) {Ð       slider.itemT =
slider.vars.itemWidth + slideMargin;Ð       slider.minW = (minItems) ?
minItems * slider.itemT : slider.w;Ð       slider.maxW = (maxItems) ?
(maxItems * slider.itemT) - slideMargin : slider.w;Ð       slider.itemW =
(slider.minW > slider.w) ? (slider.w - (slideMargin * (minItems - 1)))/
minItems :Ð                       (slider.maxW < slider.w) ? (slider.w -
(slideMargin * (maxItems - 1)))/maxItems :Ð
(slider.vars.itemWidth > slider.w) ? slider.w : slider.vars.itemWidth;Ð
slider.visible = Math.floor(slider.w/(slider.itemW));Ð       slider.move =
(slider.vars.move > 0 && slider.vars.move < slider.visible ) ?
slider.vars.move : slider.visible;Ð       slider.pagingCount =
Math.ceil(((slider.count - slider.visible)/slider.move) + 1);Ð
slider.last =  slider.pagingCount - 1;Ð       slider.limit =
(slider.pagingCount === 1) ? 0 :Ð
```

(slider.vars.itemWidth > slider.w) ? (slider.itemW * (slider.count - 1)) + (slideMargin * (slider.count - 1)) : ((slider.itemW + slideMargin) * slider.count) - slider.w - slideMargin;Ð } else {Ð slider.itemW = slider.w;Ð slider.pagingCount = slider.count;Ð slider.last = slider.count - 1;Ð }Ð slider.computedW = slider.itemW - slider.boxPadding;Ð };Ð slider.update = function(pos, action) {Ð slider.doMath();Ð // update currentSlide and slider.animatingTo if necessaryÐ if (!carousel) {Ð if (pos < slider.currentSlide) {Ð slider.currentSlide += 1;Ð } else if (pos <= slider.currentSlide && pos !== 0) {Ð slider.currentSlide -= 1;Ð }Ð slider.animatingTo = slider.currentSlide;Ð }Ð // update controlNavÐ if (slider.vars.controlNav && !slider.manualControls) {Ð if ((action === "add" && !carousel) || slider.pagingCount > slider.controlNav.length) {Ð methods.controlNav.update("add");Ð } else if ((action === "remove" && !carousel) || slider.pagingCount < slider.controlNav.length) {Ð if (carousel && slider.currentSlide > slider.last) {Ð slider.currentSlide -= 1;Ð slider.animatingTo -= 1;Ð }Ð methods.controlNav.update("remove", slider.last);Ð }Ð }Ð // update directionNavÐ if (slider.vars.directionNav) methods.directionNav.update();Ð };Ð slider.addSlide = function(obj, pos) {Ð var $obj = $(obj);Ð slider.count += 1;Ð slider.last = slider.count - 1;Ð // append new slideÐ if (vertical && reverse) {Ð (pos !== undefined) ? slider.slides.eq(slider.count - pos).after($obj) : slider.container.prepend($obj);Ð } else {Ð (pos !== undefined) ? slider.slides.eq(pos).before($obj) : slider.container.append($obj);Ð }Ð // update currentSlide, animatingTo, controlNav, and directionNavÐ slider.update(pos, "add");Ð // update slider.slidesÐ slider.slides = $(slider.vars.selector + ':not(.clone)', slider);Ð // re-setup the slider to accomdate new slideÐ slider.setup();Ð //FlexSlider: added() CallbackÐ slider.vars.added(slider);Ð };Ð slider.removeSlide = function(obj) {Ð var pos = (isNaN(obj)) ? slider.slides.index($(obj)) : obj;Ð // update countÐ slider.count -= 1;Ð slider.last = slider.count - 1;Ð // remove slideÐ if (isNaN(obj)) {Ð $(obj, slider.slides).remove();Ð } else {Ð (vertical && reverse) ? slider.slides.eq(slider.last).remove() : slider.slides.eq(obj).remove();Ð }Ð // update currentSlide, animatingTo, controlNav, and directionNavÐ slider.doMath();Ð slider.update(pos, "remove");Ð // update slider.slidesÐ slider.slides = $(slider.vars.selector + ':not(.clone)', slider);Ð // re-setup the slider to accomdate new slideÐ slider.setup();Ð // FlexSlider: removed() CallbackÐ slider.vars.removed(slider);Ð };Ð //FlexSlider: InitializeÐ methods.init();Ð };Ð // Ensure the slider isn't focussed if the window loses focus.Ð $(window).blur(function (e) {Ð focused = false;Ð }).focus(function (e) {Ð focused = true;Ð });Ð //FlexSlider: Default SettingsÐ $.flexslider.defaults = {Ð namespace: "flex-", // {NEW} String: Prefix string attached to the class of every element generated by the pluginÐ selector: ".slides > li", //{NEW} Selector: Must match a simple pattern. '{container} > {slide}' -- Ignore pattern at your own perilÐ animation: "fade", //String: Select your animation type, "fade" or "slide"Ð easing: "swing", //{NEW} String: Determines the easing method used in jQuery transitions. jQuery easing plugin is supported!Ð direction: "horizontal", //String: Select the sliding direction, "horizontal" or "vertical"Ð reverse: false, // {NEW} Boolean: Reverse the animation directionÐ animationLoop: true, //Boolean: Should the animation loop? If false, directionNav will received "disable" classes at either endÐ smoothHeight: false, //{NEW} Boolean: Allow height of the slider to animate smoothly in horizontal modeÐ

```
                                startAt: 0,                     //Integer: The
slide that the slider should start on. Array notation (0 = first slide)Ð
slideshow: true,                //Boolean: Animate slider automaticallyÐ
slideshowSpeed:5000,           //Integer: Set the speed of the slideshow
cycling, in millisecondsÐ   animationSpeed:1000,            //Integer: Set
the speed of animations, in millisecondsÐ   initDelay: 0,                   //
{NEW} Integer: Set an initialization delay, in millisecondsÐ   randomize:
false,               //Boolean: Randomize slide orderÐ   thumbCaptions:
false,           //Boolean: Whether or not to put captions on thumbnails when
using the "thumbnails" controlNav.Ð   // Usability featuresÐ   pauseOnAction:
true,            //Boolean: Pause the slideshow when interacting with control
elements, highly recommended.Ð   pauseOnHover: false,            //Boolean:
Pause the slideshow when hovering over slider, then resume when no longer
hoveringÐ   pauseInvisible: true,   ™//{NEW} Boolean: Pause the slideshow when
tab is invisible, resume when visible. Provides better UX, lower CPU usage.Ð
    useCSS: true,                   //{NEW} Boolean: Slider will use CSS3
transitions if availableÐ   touch: true,                    //{NEW} Boolean:
Allow touch swipe navigation of the slider on touch-enabled devicesÐ   video:
false,                    //{NEW} Boolean: If using video in the slider, will
prevent CSS3 3D Transforms to avoid graphical glitchesÐ   // Primary ControlsÐ
    controlNav: true,               //Boolean: Create navigation for paging
control of each clide? Note: Leave true for manualControls usageÐ
directionNav: false,             //Boolean: Create navigation for previous/
next navigation? (true/false)Ð   prevText: "",           //String: Set the
text for the "previous" directionNav itemÐ   nextText: "",               //
String: Set the text for the "next" directionNav itemÐ   // Secondary
NavigationÐ   keyboard: true,                 //Boolean: Allow slider
navigating via keyboard left/right keysÐ   multipleKeyboard: false,        //
{NEW} Boolean: Allow keyboard navigation to affect multiple sliders. Default
behavior cuts out keyboard navigation with more than one slider present.Ð
mousewheel: false,              //{UPDATED} Boolean: Requires
jquery.mousewheel.js (https://github.com/brandonaaron/jquery-mousewheel) -
Allows slider navigating via mousewheelÐ   pausePlay: false,               //
Boolean: Create pause/play dynamic elementÐ   pauseText:
"Pause",             //String: Set the text for the "pause" pausePlay itemÐ
playText: "Play",               //String: Set the text for the "play"
pausePlay itemÐ   // Special propertiesÐ   controlsContainer: "",          //
{UPDATED} jQuery Object/Selector: Declare which container the navigation
elements should be appended too. Default container is the FlexSlider element.
Example use would be $(".flexslider-container"). Property is ignored if given
element is not found.Ð   manualControls: "",             //{UPDATED} jQuery
Object/Selector: Declare custom control navigation. Examples would be
$(".flex-control-nav li") or "#tabs-nav li img", etc. The number of elements
in your controlNav should match the number of slides/tabs.Ð   sync:
"",                       //{NEW} Selector: Mirror the actions performed on
this slider with another slider. Use with care.Ð   asNavFor:
"",                    //{NEW} Selector: Internal property exposed for turning
the slider into a thumbnail navigation for another sliderÐ   // Carousel
OptionsÐ   itemWidth: 0,                   //{NEW} Integer: Box-model width
of individual carousel items, including horizontal borders and padding.Ð
itemMargin: 0,                  //{NEW} Integer: Margin between carousel
items.Ð   minItems: 1,                    //{NEW} Integer: Minimum number of
carousel items that should be visible. Items will resize fluidly when below
this.Ð   maxItems: 0,                    //{NEW} Integer: Maxmimum number of
carousel items that should be visible. Items will resize fluidly when above
this limit.Ð   move: 0,                        //{NEW} Integer: Number of
carousel items that should move on animation. If 0, slider will move all
visible items.Ð   allowOneSlide: true,           //{NEW} Boolean: Whether or
not to allow a slider comprised of a single slideÐ   // Callback APIÐ
start: function(){},            //Callback: function(slider) - Fires when the
slider loads the first slideÐ
```

```
                                before: function(){},           //Callback:
function(slider) - Fires asynchronously with each slider animationÐ   after:
function(){},            //Callback: function(slider) - Fires after each
slider animation completesÐ   end: function(){},              //Callback:
function(slider) - Fires when the slider reaches the last slide (asynchronous)Ð
    added: function(){},            //{NEW} Callback: function(slider) -
Fires after a slide is addedÐ   removed: function(){},           //{NEW}
Callback: function(slider) - Fires after a slide is removedÐ   init:
function() {}             //{NEW} Callback: function(slider) - Fires after
the slider is initially setupÐ };Ð //FlexSlider: Plugin FunctionÐ
$.fn.flexslider = function(options) {Ð   if (options === undefined) options =
{};Ð   if (typeof options === "object") {Ð     return this.each(function() {Ð
        var $this = $(this),Ð           selector = (options.selector) ?
options.selector : ".slides > li",Ð           $slides = $this.find(selector);Ð
      if ( ( $slides.length === 1 && options.allowOneSlide === true ) ||
$slides.length === 0 ) {Ð         $slides.fadeIn(400);Ð         if
(options.start) options.start($this);Ð       } else if
($this.data('flexslider') === undefined) {Ð         new $.flexslider(this,
options);Ð       }Ð     });Ð   } else {Ð     // Helper strings to quickly
perform functions on the sliderÐ     var $slider = $(this).data('flexslider');Ð
      switch (options) {Ð       case "play": $slider.play(); break;Ð
case "pause": $slider.pause(); break;Ð       case "stop": $slider.stop();
break;Ð       case "next": $slider.flexAnimate($slider.getTarget("next"),
true); break;Ð       case "prev":Ð       case "previous":
$slider.flexAnimate($slider.getTarget("prev"), true); break;Ð       default:
if (typeof options === "number") $slider.flexAnimate(options, true);Ð     }Ð
    }Ð };Ð})(jQuery);Ð
```

public\assets\frontend\js\jquery.isotope.js

```
/**Ð* Isotope v1.5.25Ð* An exquisite jQuery plugin for magical layoutsÐ*
http://isotope.metafizzy.coÐ*Ð* Commercial use requires one-time purchase of
a commercial licenseÐ* http://isotope.metafizzy.co/docs/license.htmlÐ*Ð* Non-
commercial use is licensed under the MIT LicenseÐ*Ð* Copyright 2013 MetafizzyÐ
*/Ø*jshint asi: true, browser: true, curly: true, eqeqeq: true, forin: false,
immed: false, newcap: true, noempty: true, strict: true, undef: true */Ø
*global jQuery: false */Øfunction( window, $, undefined ){Ð 'use strict';Ð //
get global varsÐ var document = window.document;Ð var Modernizr =
window.Modernizr;Ð // helper functionÐ var capitalize = function( str ) {Ð
return str.charAt(0).toUpperCase() + str.slice(1);Ð };Ð //
========================= getStyleProperty by kangax
==============================Ð // http://perfectionkills.com/feature-
testing-css-properties/Ð var prefixes = 'Moz Webkit O Ms'.split(' ');Ð var
getStyleProperty = function( propName ) {Ð   var style =
document.documentElement.style,Ð       prefixed;Ð   // test standard property
firstÐ   if ( typeof style[propName] === 'string' ) {Ð     return propName;Ð
    }Ð   // capitalizeÐ   propName = capitalize( propName );Ð   // test
vendor specific propertiesÐ   for ( var i=0, len = prefixes.length; i < len;
i++ ) {Ð     prefixed = prefixes[i] + propName;Ð     if ( typeof
style[ prefixed ] === 'string' ) {Ð       return prefixed;Ð     }Ð   }Ð };Ð
var transformProp = getStyleProperty('transform'),Ð     transitionProp =
getStyleProperty('transitionProperty');Ð // =========================
miniModernizr ===============================Ð // <3<3<3 and thanks to Faruk
and Paul for doing the heavy liftingÐ /*!Ð  * Modernizr v1.6ish:
miniModernizr for IsotopeÐ  * http://www.modernizr.comÐ  *Ð  * Developed by:Ð
   * - Faruk Ates  http://farukat.es/Ð  * - Paul Irish  http://paulirish.com/Ð
   *Ð  * Copyright (c) 2009-2010Ð  * Dual-licensed under the BSD or MIT
licenses.Ð  * http://www.modernizr.com/license/Ð  */Ð /*Ð  * This version
whittles down the script just to check support forÐ  * CSS transitions,
transforms, and 3D transforms.Ð */Ð var tests = {Ð   csstransforms:
function() {Ð     return !!transformProp;Ð   },Ð   csstransforms3d:
function() {Ð     var test = !!getStyleProperty('perspective');Ð     //
double check for Chrome's false positiveÐ     if ( test ) {Ð       var
vendorCSSPrefixes = ' -o- -moz- -ms- -webkit- -khtml- '.split(' '),Ð
            mediaQuery = '@media (' + vendorCSSPrefixes.join('transform-3d),
(') + 'modernizr)',Ð           $style = $('<style>' + mediaQuery +
'{#modernizr{height:3px}}' + '</style>')Ð
                        .appendTo('head'),Ð           $div = $('<div
id="modernizr" />').appendTo('html');Ð       test = $div.height() === 3;Ð
        $div.remove();Ð       $style.remove();Ð     }Ð     return test;Ð   },Ð
    csstransitions: function() {Ð     return !!transitionProp;Ð   }Ð };Ð var
testName;Ð if ( Modernizr ) {Ð   // if there's a previous Modernzir, check if
there are necessary testsÐ   for ( testName in tests) {Ð     if ( !
Modernizr.hasOwnProperty( testName ) ) {Ð       // if test hasn't been run,
use addTest to run itÐ       Modernizr.addTest( testName, tests[ testName ] );Ð
      }Ð   }Ð } else {Ð   // or create new mini Modernizr that just has the 3
testsÐ   Modernizr = window.Modernizr = {Ð     _version : '1.6ish:
miniModernizr for Isotope'Ð   };Ð   var classes = ' ';Ð   var result;Ð   //
Run through testsÐ   for ( testName in tests) {Ð     result =
tests[ testName ]();Ð     Modernizr[ testName ] = result;Ð     classes += ' '
+ ( result ?  '' : 'no-' ) + testName;Ð   }Ð   // Add the new classes to the
<html> element.Ð   $('html').addClass( classes );Ð }Ð //
========================= isoTransform ==============================Ð /**Ð
*  provides hooks for .css({ scale: value, translate: [x, y] })Ð  *
Progressively enhanced CSS transformsÐ  *  Uses hardware accelerated 3D
transforms for SafariÐ  *  or falls back to 2D transforms.Ð  */Ð if
( Modernizr.csstransforms ) {Ð       // i.e. transformFnNotations.scale(0.5)
>> 'scale3d( 0.5, 0.5, 1)'Ð   var transformFnNotations =
Modernizr.csstransforms3d ?Ð
```

```
                                    { // 3D transform functionsÐ
translate : function ( position ) {Ð         return 'translate3d(' +
position[0] + 'px, ' + position[1] + 'px, 0) ';Ð       },Ð       scale :
function ( scale ) {Ð         return 'scale3d(' + scale + ', ' + scale + ',
1) ';Ð       }Ð     } :Ð     { // 2D transform functionsÐ       translate :
function ( position ) {Ð         return 'translate(' + position[0] + 'px, ' +
position[1] + 'px) ';Ð       },Ð       scale : function ( scale ) {Ð
return 'scale(' + scale + ') ';Ð       }Ð     }Ð   ;Ð   var setIsoTransform =
function ( elem, name, value ) {Ð         // unpack current transform dataÐ
      var data =  $.data( elem, 'isoTransform' ) || {},Ð         newData = {},Ð
          fnName,Ð         transformObj = {},Ð         transformValue;Ð
      // i.e. newData.scale = 0.5Ð     newData[ name ] = value;Ð     //
extend new value over current dataÐ     $.extend( data, newData );Ð     for
( fnName in data ) {Ð       transformValue = data[ fnName ];Ð
transformObj[ fnName ] = transformFnNotations[ fnName ]( transformValue );Ð
      }Ð     // get proper orderÐ     // ideally, we could loop through this
give an array, but since we only haveÐ     // a couple transforms we're
keeping track of, we'll do it like soÐ     var translateFn =
transformObj.translate || '',Ð         scaleFn = transformObj.scale || '',Ð
          // sorting so translate always comes firstÐ         valueFns =
translateFn + scaleFn;Ð     // set data back in elemÐ     $.data( elem,
'isoTransform', data );Ð     // set name to vendor specific propertyÐ
elem.style[ transformProp ] = valueFns;Ð   };Ð   // ====================
scale ===================Ð   $.cssNumber.scale = true;Ð   $.cssHooks.scale = {Ð
      set: function( elem, value ) {Ð       // uncomment this bit if you want
to properly parse stringsÐ       // if ( typeof value === 'string' ) {Ð
        //   value = parseFloat( value );Ð       // }Ð
setIsoTransform( elem, 'scale', value );Ð     },Ð     get: function( elem,
computed ) {Ð       var transform = $.data( elem, 'isoTransform' );Ð
return transform && transform.scale ? transform.scale : 1;Ð     }Ð   };Ð
$.fx.step.scale = function( fx ) {Ð     $.cssHooks.scale.set( fx.elem,
fx.now+fx.unit );Ð   };Ð   // ==================== translate
===================Ð   $.cssNumber.translate = true;Ð   $.cssHooks.translate
= {Ð     set: function( elem, value ) {Ð       // uncomment this bit if you
want to properly parse stringsÐ       // if ( typeof value === 'string' ) {Ð
        //   value = value.split(' ');Ð       // }Ð       //Ð       // var i,
val;Ð       // for ( i = 0; i < 2; i++ ) {Ð       //   val = value[i];Ð
        //   if ( typeof val === 'string' ) {Ð       //     val =
parseInt( val );Ð       //   }Ð       // }Ð       setIsoTransform( elem,
'translate', value );Ð     },Ð     get: function( elem, computed ) {Ð
var transform = $.data( elem, 'isoTransform' );Ð       return transform &&
transform.translate ? transform.translate : [ 0, 0 ];Ð     }Ð   };Ð }Ð //
========================= get transition-end event
================================Ð var transitionEndEvent, transitionDurProp;Ð
if ( Modernizr.csstransitions ) {Ð   transitionEndEvent = {Ð
WebkitTransitionProperty: 'webkitTransitionEnd',  // webkitÐ
MozTransitionProperty: 'transitionend',Ð     OTransitionProperty:
'oTransitionEnd otransitionend',Ð     transitionProperty: 'transitionend'Ð   }
[ transitionProp ];Ð   transitionDurProp =
getStyleProperty('transitionDuration');Ð }Ð // =========================
smartresize ================================Ð /*Ð  * smartresize: debounced
resize event for jQueryÐ  *Ð  * latest version and complete README available
on Github:Ð  * https://github.com/louisremi/jquery.smartresize.jsÐ  *Ð  *
Copyright 2011 @louis_remiÐ  * Licensed under the MIT license.Ð  */Ð var
$event = $.event,Ð     dispatchMethod = $.event.handle ? 'handle' :
'dispatch',Ð     resizeTimeout;Ð $event.special.smartresize = {Ð   setup:
function() {Ð     $(this).bind( "resize",
$event.special.smartresize.handler );Ð   },Ð   teardown: function() {Ð
$(this).unbind( "resize", $event.special.smartresize.handler );Ð   },Ð
handler: function( event, execAsap ) {Ð
```

```
                                                // Save the contextÐ     var
context = this,Ð         args = arguments;Ð     // set correct event typeÐ
      event.type = "smartresize";Ð     if ( resizeTimeout )
{ clearTimeout( resizeTimeout ); }Ð     resizeTimeout = setTimeout(function()
{Ð       $event[ dispatchMethod ].apply( context, args );Ð     }, execAsap
=== "execAsap"? 0 : 100 );Ð   }Ð };Ð $.fn.smartresize = function( fn ) {Ð
return fn ? this.bind( "smartresize", fn ) : this.trigger( "smartresize",
["execAsap"] );Ð };Ð/ ========================= Isotope
================================Ð // our "Widget" object constructorÐ
$.Isotope = function( options, element, callback ){Ð   this.element =
$( element );Ð   this._create( options );Ð   this._init( callback );Ð };Ð //
styles of container element we want to keep track ofÐ var isoContainerStyles
= [ 'width', 'height' ];Ð var $window = $(window);Ð $.Isotope.settings = {Ð
resizable: true,Ð   layoutMode : 'masonry',Ð   containerClass : 'isotope',Ð
itemClass : 'isotope-item',Ð   hiddenClass : 'isotope-hidden',Ð
hiddenStyle: { opacity: 0, scale: 0.001 },Ð   visibleStyle: { opacity: 1,
scale: 1 },Ð   containerStyle: {Ð     position: 'relative',Ð     overflow:
'hidden'Ð   },Ð   animationEngine: 'best-available',Ð   animationOptions: {Ð
      queue: false,Ð     duration: 800Ð   },Ð   sortBy : 'original-order',Ð
sortAscending : true,Ð   resizesContainer : true,Ð   transformsEnabled: true,Ð
    itemPositionDataEnabled: falseÐ };Ð $.Isotope.prototype = {Ð   // sets up
widgetÐ   _create : function( options ) {Ð     this.options = $.extend( {},
$.Isotope.settings, options );Ð     this.styleQueue = [];Ð     this.elemCount
= 0;Ð     // get original styles in case we re-apply them in .destroy()Ð
var elemStyle = this.element[0].style;Ð     this.originalStyle = {};Ð     //
keep track of container stylesÐ     var containerStyles =
isoContainerStyles.slice(0);Ð     for ( var prop in
this.options.containerStyle ) {Ð       containerStyles.push( prop );Ð     }Ð
      for ( var i=0, len = containerStyles.length; i < len; i++ ) {Ð
prop = containerStyles[i];Ð       this.originalStyle[ prop ] =
elemStyle[ prop ] || '';Ð     }Ð     // apply container style from optionsÐ
      this.element.css( this.options.containerStyle );Ð
this._updateAnimationEngine();Ð     this._updateUsingTransforms();Ð     //
sortingÐ     var originalOrderSorter = {Ð       'original-order' :
function( $elem, instance ) {Ð         instance.elemCount ++;Ð         return
instance.elemCount;Ð       },Ð       random : function() {Ð         return
Math.random();Ð       }Ð     };Ð     this.options.getSortData =
$.extend( this.options.getSortData, originalOrderSorter );Ð     // need to
get atomsÐ     this.reloadItems();Ð     // get top left position of where the
bricks should beÐ     this.offset = {Ð       left:
parseInt( ( this.element.css('padding-left') || 0 ), 10 ),Ð       top:
parseInt( ( this.element.css('padding-top') || 0 ), 10 )Ð     };Ð     // add
isotope class first time aroundÐ     var instance = this;Ð
setTimeout( function() {Ð
instance.element.addClass( instance.options.containerClass );Ð     }, 0 );Ð
      // bind resize methodÐ     if ( this.options.resizable ) {Ð
$window.bind( 'smartresize.isotope', function() {Ð         instance.resize();Ð
        });Ð     }Ð     // dismiss all click events from hidden eventsÐ
this.element.delegate( '.' + this.options.hiddenClass, 'click', function(){Ð
        return false;Ð     });Ð   },Ð   _getAtoms : function( $elems ) {Ð
var selector = this.options.itemSelector,Ð         // filter & findÐ
$atoms = selector ?
$elems.filter( selector ).add( $elems.find( selector ) ) : $elems,Ð
          // base style for atomsÐ         atomStyle = { position:
'absolute' };Ð     // filter out text nodesÐ     $atoms =
$atoms.filter( function( i, atom ) {Ð       return atom.nodeType === 1;Ð
      });Ð     if ( this.usingTransforms ) {Ð       atomStyle.left = 0;Ð
        atomStyle.top = 0;Ð     }Ð
$atoms.css( atomStyle ).addClass( this.options.itemClass );Ð
this.updateSortData( $atoms, true );Ð
```

```
                                    Ð     return $atoms;Ð   },Ð   // _init
fires when your instance is first createdÐ   // (from the constructor above),
and when youÐ   // attempt to initialize the widget again (by the bridge)Ð
    // after it has already been initialized.Ð   _init : function( callback )
{Ð     this.$filteredAtoms = this._filter( this.$allAtoms );Ð
this._sort();Ð     this.reLayout( callback );Ð   },Ð   option :
function( opts ){Ð     // change options AFTER initialization:Ð     //
signature: $('#foo').bar({ cool:false });Ð     if ( $.isPlainObject( opts ) ){Ð
        this.options = $.extend( true, this.options, opts );Ð       //
trigger _updateOptionName if it existsÐ       var updateOptionFn;Ð       for
( var optionName in opts ) {Ð         updateOptionFn = '_update' +
capitalize( optionName );Ð         if ( this[ updateOptionFn ] ) {Ð
this[ updateOptionFn ]();Ð         }Ð       }Ð     }Ð   },Ð   //
====================== updaters ====================== //Ð   // kind of like
settersÐ   _updateAnimationEngine : function() {Ð     var animationEngine =
this.options.animationEngine.toLowerCase().replace( /[ _\-]/g, '');Ð     var
isUsingJQueryAnimation;Ð     // set applyStyleFnNameÐ     switch
( animationEngine ) {Ð       case 'css' :Ð       case 'none' :Ð
isUsingJQueryAnimation = false;Ð         break;Ð       case 'jquery' :Ð
          isUsingJQueryAnimation = true;Ð         break;Ð       default : //
best availableÐ         isUsingJQueryAnimation = !Modernizr.csstransitions;Ð
      }Ð     this.isUsingJQueryAnimation = isUsingJQueryAnimation;Ð
this._updateUsingTransforms();Ð   },Ð   _updateTransformsEnabled : function()
{Ð     this._updateUsingTransforms();Ð   },Ð   _updateUsingTransforms :
function() {Ð     var usingTransforms = this.usingTransforms =
this.options.transformsEnabled &&Ð       Modernizr.csstransforms &&
Modernizr.csstransitions && !this.isUsingJQueryAnimation;Ð     // prevent
scales when transforms are disabledÐ     if ( !usingTransforms ) {Ð
delete this.options.hiddenStyle.scale;Ð       delete
this.options.visibleStyle.scale;Ð     }Ð     this.getPositionStyles =
usingTransforms ? this._translate : this._positionAbs;Ð   },Ð   //
====================== Filtering ======================Ð   _filter :
function( $atoms ) {Ð     var filter = this.options.filter === '' ? '*' :
this.options.filter;Ð     if ( !filter ) {Ð       return $atoms;Ð     }Ð
var hiddenClass    = this.options.hiddenClass,Ð         hiddenSelector = '.'
+ hiddenClass,Ð         $hiddenAtoms   = $atoms.filter( hiddenSelector ),Ð
          $atomsToShow   = $hiddenAtoms;Ð     if ( filter !== '*' ) {Ð
$atomsToShow = $hiddenAtoms.filter( filter );Ð       var $atomsToHide =
$atoms.not( hiddenSelector ).not( filter ).addClass( hiddenClass );Ð
this.styleQueue.push({ $el: $atomsToHide, style: this.options.hiddenStyle });Ð
      }Ð     this.styleQueue.push({ $el: $atomsToShow, style:
this.options.visibleStyle });Ð     $atomsToShow.removeClass( hiddenClass );Ð
      return $atoms.filter( filter );Ð   },Ð   // ======================
Sorting ======================Ð   updateSortData : function( $atoms,
isIncrementingElemCount ) {Ð     var instance = this,Ð         getSortData =
this.options.getSortData,Ð         $this, sortData;Ð
$atoms.each(function(){Ð       $this = $(this);Ð       sortData = {};Ð
        // get value for sort data based on fn( $elem ) passed inÐ       for
( var key in getSortData ) {Ð         if ( !isIncrementingElemCount && key
=== 'original-order' ) {Ð           // keep original order originalÐ
            sortData[ key ] = $.data( this, 'isotope-sort-data' )[ key ];Ð
          } else {Ð           sortData[ key ] = getSortData[ key ]( $this,
instance );Ð         }Ð       }Ð       // apply sort data to elementÐ
$.data( this, 'isotope-sort-data', sortData );Ð     });Ð   },Ð   // used on
all the filtered atomsÐ   _sort : function() {Ð     var sortBy =
this.options.sortBy,Ð         getSorter = this._getSorter,Ð         sortDir =
this.options.sortAscending ? 1 : -1,Ð         sortFn = function( alpha,
beta ) {Ð           var a = getSorter( alpha, sortBy ),Ð               b =
getSorter( beta, sortBy );Ð           // fall back to original order if data
matchesÐ
```

```
                    if ( a === b && sortBy !== 'original-order') {Ð
               a = getSorter( alpha, 'original-order' );Ð              b =
getSorter( beta, 'original-order' );Ð           }Ð           return ( ( a >
b ) ? 1 : ( a < b ) ? -1 : 0 ) * sortDir;Ð         };Ð     this.
$filteredAtoms.sort( sortFn );Ð   },Ð   _getSorter : function( elem, sortBy )
{Ð     return $.data( elem, 'isotope-sort-data' )[ sortBy ];Ð   },Ð   //
====================== Layout Helpers ======================Ð   _translate :
function( x, y ) {Ð     return { translate : [ x, y ] };Ð   },Ð
_positionAbs : function( x, y ) {Ð     return { left: x, top: y };Ð   },Ð
_pushPosition : function( $elem, x, y ) {Ð     x = Math.round( x +
this.offset.left );Ð     y = Math.round( y + this.offset.top );Ð     var
position = this.getPositionStyles( x, y );Ð     this.styleQueue.push({ $el:
$elem, style: position });Ð     if ( this.options.itemPositionDataEnabled ) {Ð
        $elem.data('isotope-item-position', {x: x, y: y} );Ð     }Ð   },Ð
    // ====================== General Layout ======================Ð   //
used on collection of atoms (should be filtered, and sorted before )Ð   //
accepts atoms-to-be-laid-out to start withÐ   layout : function( $elems,
callback ) {Ð     var layoutMode = this.options.layoutMode;Ð     // layout
logicÐ     this[ '_' +  layoutMode + 'Layout' ]( $elems );Ð     // set the
size of the containerÐ     if ( this.options.resizesContainer ) {Ð       var
containerStyle = this[ '_' +  layoutMode + 'GetContainerSize' ]();Ð
this.styleQueue.push({ $el: this.element, style: containerStyle });Ð     }Ð
      this._processStyleQueue( $elems, callback );Ð     this.isLaidOut = true;Ð
    },Ð   _processStyleQueue : function( $elems, callback ) {Ð     // are we
animating the layout arrangement?Ð     // use plugin-ish syntax for css or
animateÐ     var styleFn = !this.isLaidOut ? 'css' : (Ð
this.isUsingJQueryAnimation ? 'animate' : 'css'Ð         ),Ð         animOpts
= this.options.animationOptions,Ð         onLayout = this.options.onLayout,Ð
          objStyleFn, processor,Ð         triggerCallbackNow, callbackFn;Ð
      // default styleQueue processor, may be overwritten down belowÐ
processor = function( i, obj ) {Ð       obj.$el[ styleFn ]( obj.style,
animOpts );Ð     };Ð     if ( this._isInserting &&
this.isUsingJQueryAnimation ) {Ð       // if using styleQueue to insert itemsÐ
        processor = function( i, obj ) {Ð         // only animate if it not
being insertedÐ         objStyleFn = obj.$el.hasClass('no-transition') ?
'css' : styleFn;Ð         obj.$el[ objStyleFn ]( obj.style, animOpts );Ð
        };Ð     } else if ( callback || onLayout || animOpts.complete ) {Ð
        // has callbackÐ       var isCallbackTriggered = false,Ð           //
array of possible callbacks to triggerÐ           callbacks = [ callback,
onLayout, animOpts.complete ],Ð           instance = this;Ð
triggerCallbackNow = true;Ð       // trigger callback only onceÐ
callbackFn = function() {Ð         if ( isCallbackTriggered ) {Ð
return;Ð         }Ð         var hollaback;Ð         for (var i=0, len =
callbacks.length; i < len; i++) {Ð           hollaback = callbacks[i];Ð
            if ( typeof hollaback === 'function' ) {Ð
hollaback.call( instance.element, $elems, instance );Ð           }Ð         }Ð
          isCallbackTriggered = true;Ð       };Ð       if
( this.isUsingJQueryAnimation && styleFn === 'animate' ) {Ð         // add
callback to animation optionsÐ         animOpts.complete = callbackFn;Ð
          triggerCallbackNow = false;Ð       } else if
( Modernizr.csstransitions ) {Ð         // detect if first item has transitionÐ
          var i = 0,Ð             firstItem = this.styleQueue[0],Ð
              testElem = firstItem && firstItem.$el,Ð             styleObj;Ð
          // get first non-empty jQ objectÐ         while ( !testElem || !
testElem.length ) {Ð           styleObj = this.styleQueue[ i++ ];Ð
            // HACK: sometimes styleQueue[i] is undefinedÐ           if ( !
styleObj ) {Ð             return;Ð           }Ð           testElem = styleObj.
$el;Ð         }Ð         // get transition duration of the first element in
that objectÐ         // yeah, this is inexactÐ         var duration =
parseFloat( getComputedStyle( testElem[0] )[ transitionDurProp ] );Ð
```

```
if ( duration > 0 ) {Ð           processor = function( i, obj ) {Ð
              obj.$el[ styleFn ]( obj.style, animOpts )Ð               //
trigger callback at transition endÐ               .one( transitionEndEvent,
callbackFn );Ð           };Ð           triggerCallbackNow = false;Ð         }Ð
        }Ð     }Ð     // process styleQueueÐ     $.each( this.styleQueue,
processor );Ð     if ( triggerCallbackNow ) {Ð       callbackFn();Ð     }Ð
      // clear out queue for next timeÐ     this.styleQueue = [];Ð   },Ð
resize : function() {Ð     if ( this[ '_' + this.options.layoutMode +
'ResizeChanged' ]() ) {Ð       this.reLayout();Ð     }Ð   },Ð   reLayout :
function( callback ) {Ð     this[ '_' +  this.options.layoutMode + 'Reset' ]
();Ð     this.layout( this.$filteredAtoms, callback );Ð   },Ð   //
====================== Convenience methods ======================Ð   //
====================== Adding items ======================Ð   // adds a
jQuery object of items to a isotope containerÐ   addItems :
function( $content, callback ) {Ð     var $newAtoms =
this._getAtoms( $content );Ð     // add new atoms to atoms poolsÐ     this.
$allAtoms = this.$allAtoms.add( $newAtoms );Ð     if ( callback ) {Ð
callback( $newAtoms );Ð     }Ð   },Ð   // convienence method for adding
elements properly to any layoutÐ   // positions items, hides them, then
animates them back in <--- very sezzyÐ   insert : function( $content,
callback ) {Ð     // position itemsÐ     this.element.append( $content );Ð
      var instance = this;Ð     this.addItems( $content,
function( $newAtoms ) {Ð       var $newFilteredAtoms =
instance._filter( $newAtoms );Ð
instance._addHideAppended( $newFilteredAtoms );Ð       instance._sort();Ð
        instance.reLayout();Ð
instance._revealAppended( $newFilteredAtoms, callback );Ð     });Ð   },Ð   //
convienence method for working with Infinite ScrollÐ   appended :
function( $content, callback ) {Ð     var instance = this;Ð
this.addItems( $content, function( $newAtoms ) {Ð
instance._addHideAppended( $newAtoms );Ð       instance.layout( $newAtoms );Ð
        instance._revealAppended( $newAtoms, callback );Ð     });Ð   },Ð   //
adds new atoms, then hides them before positioningÐ   _addHideAppended :
function( $newAtoms ) {Ð     this.$filteredAtoms = this.
$filteredAtoms.add( $newAtoms );Ð     $newAtoms.addClass('no-transition');Ð
      this._isInserting = true;Ð     // apply hidden stylesÐ
this.styleQueue.push({ $el: $newAtoms, style: this.options.hiddenStyle });Ð
    },Ð   // sets visible style on new atomsÐ   _revealAppended :
function( $newAtoms, callback ) {Ð     var instance = this;Ð     // apply
visible style after a secÐ     setTimeout( function() {Ð       // enable
animationÐ       $newAtoms.removeClass('no-transition');Ð       // reveal
newly inserted filtered elementsÐ       instance.styleQueue.push({ $el:
$newAtoms, style: instance.options.visibleStyle });Ð
instance._isInserting = false;Ð       instance._processStyleQueue( $newAtoms,
callback );Ð     }, 10 );Ð   },Ð   // gathers all atomsÐ   reloadItems :
function() {Ð     this.$allAtoms = this._getAtoms( this.element.children() );Ð
    },Ð   // removes elements from Isotope widgetÐ   remove:
function( $content, callback ) {Ð     // remove elements immediately from
Isotope instanceÐ     this.$allAtoms = this.$allAtoms.not( $content );Ð
this.$filteredAtoms = this.$filteredAtoms.not( $content );Ð     // remove()
as a callback, for after transition / animationÐ     var instance = this;Ð
      var removeContent = function() {Ð       $content.remove();Ð       if
( callback ) {Ð         callback.call( instance.element );Ð       }Ð     };Ð
      if ( $content.filter( ':not(.' + this.options.hiddenClass +
')' ).length ) {Ð       // if any non-hidden content needs to be removedÐ
        this.styleQueue.push({ $el: $content, style:
this.options.hiddenStyle });Ð       this._sort();Ð
this.reLayout( removeContent );Ð     } else {Ð       // remove it nowÐ
removeContent();Ð
```

```
                    }Ð   },Ð   shuffle : function( callback ) {Ð
this.updateSortData( this.$allAtoms );Ð     this.options.sortBy = 'random';Ð
      this._sort();Ð     this.reLayout( callback );Ð   },Ð   // destroys
widget, returns elements and container back (close) to original styleÐ
destroy : function() {Ð     var usingTransforms = this.usingTransforms;Ð
var options = this.options;Ð     this.$allAtomsÐ
        .removeClass( options.hiddenClass + ' ' + options.itemClass )Ð
        .each(function(){Ð         var style = this.style;Ð
style.position = '';Ð         style.top = '';Ð         style.left = '';Ð
          style.opacity = '';Ð         if ( usingTransforms ) {Ð
style[ transformProp ] = '';Ð         }Ð       });Ð     // re-apply saved
container stylesÐ     var elemStyle = this.element[0].style;Ð     for ( var
prop in this.originalStyle ) {Ð       elemStyle[ prop ] =
this.originalStyle[ prop ];Ð     }Ð     this.elementÐ
        .unbind('.isotope')Ð       .undelegate( '.' + options.hiddenClass,
'click' )Ð       .removeClass( options.containerClass )Ð
        .removeData('isotope');Ð     $window.unbind('.isotope');Ð   },Ð   //
====================== LAYOUTS ======================Ð   // calculates number
of rows or columnsÐ   // requires columnWidth or rowHeight to be set on
namespaced objectÐ   // i.e. this.masonry.columnWidth = 200Ð   _getSegments :
function( isRows ) {Ð     var namespace = this.options.layoutMode,Ð
measure  = isRows ? 'rowHeight' : 'columnWidth',Ð         size     = isRows ?
'height' : 'width',Ð         segmentsName = isRows ? 'rows' : 'cols',Ð
          containerSize = this.element[ size ](),Ð         segments,Ð
                    // i.e. options.masonry && options.masonry.columnWidthÐ
          segmentSize = this.options[ namespace ] && this.options[ namespace ]
[ measure ] ||Ð                   // or use the size of the first item, i.e.
outerWidthÐ                   this.$filteredAtoms[ 'outer' +
capitalize(size) ](true) ||Ð                   // if there's no items, use
size of containerÐ                   containerSize;Ð     segments =
Math.floor( containerSize / segmentSize );Ð     segments =
Math.max( segments, 1 );Ð     // i.e. this.masonry.cols = ....Ð
this[ namespace ][ segmentsName ] = segments;Ð     // i.e.
this.masonry.columnWidth = ...Ð     this[ namespace ][ measure ] =
segmentSize;Ð   },Ð   _checkIfSegmentsChanged : function( isRows ) {Ð     var
namespace = this.options.layoutMode,Ð         segmentsName = isRows ?
'rows' : 'cols',Ð         prevSegments = this[ namespace ][ segmentsName ];Ð
      // update cols/rowsÐ     this._getSegments( isRows );Ð     // return if
updated cols/rows is not equal to previousÐ     return ( this[ namespace ]
[ segmentsName ] !== prevSegments );Ð   },Ð   // ======================
Masonry ======================Ð   _masonryReset : function() {Ð     // layout-
specific propsÐ     this.masonry = {};Ð     // FIXME shouldn't have to call
this againÐ     this._getSegments();Ð     var i = this.masonry.cols;Ð
this.masonry.colYs = [];Ð     while (i--) {Ð
this.masonry.colYs.push( 0 );Ð     }Ð   },Ð   _masonryLayout :
function( $elems ) {Ð     var instance = this,Ð         props =
instance.masonry;Ð     $elems.each(function(){Ð       var $this  = $(this),Ð
            //how many columns does this brick spanÐ           colSpan =
Math.ceil( $this.outerWidth(true) / props.columnWidth );Ð       colSpan =
Math.min( colSpan, props.cols );Ð       if ( colSpan === 1 ) {Ð         // if
brick spans only one column, just like singleModeÐ
instance._masonryPlaceBrick( $this, props.colYs );Ð       } else {Ð
          // brick spans more than one columnÐ         // how many different
places could this brick fit horizontallyÐ         var groupCount = props.cols
+ 1 - colSpan,Ð             groupY = [],Ð             groupColY,Ð
i;Ð         // for each group potential horizontal positionÐ         for
( i=0; i < groupCount; i++ ) {Ð           // make an array of colY values for
that one groupÐ           groupColY = props.colYs.slice( i, i+colSpan );Ð
            // and get the max value of the arrayÐ           groupY[i] =
Math.max.apply( Math, groupColY );Ð
```

```
                                        }Ð
instance._masonryPlaceBrick( $this, groupY );Ð       }Ð     });Ð   },Ð   //
worker method that places brick in the columnSetÐ   //   with the the minYÐ
_masonryPlaceBrick : function( $brick, setY ) {Ð     // get the minimum Y
value from the columnsÐ     var minimumY = Math.min.apply( Math, setY ),Ð
          shortCol = 0;Ð     // Find index of short column, the first from
the leftÐ     for (var i=0, len = setY.length; i < len; i++) {Ð       if
( setY[i] === minimumY ) {Ð         shortCol = i;Ð         break;Ð       }Ð
      }Ð     // position the brickÐ     var x = this.masonry.columnWidth *
shortCol,Ð         y = minimumY;Ð     this._pushPosition( $brick, x, y );Ð
      // apply setHeight to necessary columnsÐ     var setHeight = minimumY +
$brick.outerHeight(true),Ð         setSpan = this.masonry.cols + 1 - len;Ð
      for ( i=0; i < setSpan; i++ ) {Ð       this.masonry.colYs[ shortCol +
i ] = setHeight;Ð     }Ð   },Ð   _masonryGetContainerSize : function() {Ð
var containerHeight = Math.max.apply( Math, this.masonry.colYs );Ð     return
{ height: containerHeight };Ð   },Ð   _masonryResizeChanged : function() {Ð
      return this._checkIfSegmentsChanged();Ð   },Ð   //
====================== fitRows ======================Ð   _fitRowsReset :
function() {Ð     this.fitRows = {Ð       x : 0,Ð       y : 0,Ð
height : 0Ð     };Ð   },Ð   _fitRowsLayout : function( $elems ) {Ð     var
instance = this,Ð         containerWidth = this.element.width(),Ð
props = this.fitRows;Ð     $elems.each( function() {Ð       var $this =
$(this),Ð           atomW = $this.outerWidth(true),Ð           atomH =
$this.outerHeight(true);Ð       if ( props.x !== 0 && atomW + props.x >
containerWidth ) {Ð         // if this element cannot fit in the current rowÐ
          props.x = 0;Ð         props.y = props.height;Ð       }Ð       //
position the atomÐ       instance._pushPosition( $this, props.x, props.y );Ð
        props.height = Math.max( props.y + atomH, props.height );Ð
props.x += atomW;Ð     });Ð   },Ð   _fitRowsGetContainerSize : function () {Ð
      return { height : this.fitRows.height };Ð   },Ð
_fitRowsResizeChanged : function() {Ð     return true;Ð   },Ð   //
====================== cellsByRow ======================Ð
_cellsByRowReset : function() {Ð     this.cellsByRow = {Ð       index : 0Ð
      };Ð     // get this.cellsByRow.columnWidthÐ     this._getSegments();Ð
      // get this.cellsByRow.rowHeightÐ     this._getSegments(true);Ð   },Ð
_cellsByRowLayout : function( $elems ) {Ð     var instance = this,Ð
props = this.cellsByRow;Ð     $elems.each( function(){Ð       var $this =
$(this),Ð           col = props.index % props.cols,Ð           row =
Math.floor( props.index / props.cols ),Ð           x = ( col + 0.5 ) *
props.columnWidth - $this.outerWidth(true) / 2,Ð           y = ( row + 0.5 )
* props.rowHeight - $this.outerHeight(true) / 2;Ð
instance._pushPosition( $this, x, y );Ð       props.index ++;Ð     });Ð   },Ð
    _cellsByRowGetContainerSize : function() {Ð     return { height :
Math.ceil( this.$filteredAtoms.length / this.cellsByRow.cols ) *
this.cellsByRow.rowHeight + this.offset.top };Ð   },Ð
_cellsByRowResizeChanged : function() {Ð     return
this._checkIfSegmentsChanged();Ð   },Ð   // ======================
straightDown ======================Ð   _straightDownReset : function() {Ð
this.straightDown = {Ð       y : 0Ð     };Ð   },Ð   _straightDownLayout :
function( $elems ) {Ð     var instance = this;Ð     $elems.each( function( i )
{Ð       var $this = $(this);Ð       instance._pushPosition( $this, 0,
instance.straightDown.y );Ð       instance.straightDown.y +=
$this.outerHeight(true);Ð     });Ð   },Ð   _straightDownGetContainerSize :
function() {Ð     return { height : this.straightDown.y };Ð   },Ð
_straightDownResizeChanged : function() {Ð     return true;Ð   },Ð   //
====================== masonryHorizontal ======================Ð
_masonryHorizontalReset : function() {Ð     // layout-specific propsÐ
this.masonryHorizontal = {};Ð     // FIXME shouldn't have to call this againÐ
      this._getSegments( true );Ð     var i = this.masonryHorizontal.rows;Ð
      this.masonryHorizontal.rowXs = [];Ð
```

```
                                                while (i--) {Ð
this.masonryHorizontal.rowXs.push( 0 );Ð     }Ð   },Ð
_masonryHorizontalLayout : function( $elems ) {Ð     var instance = this,Ð
          props = instance.masonryHorizontal;Ð     $elems.each(function(){Ð
        var $this  = $(this),Ð           //how many rows does this brick spanÐ
            rowSpan = Math.ceil( $this.outerHeight(true) / props.rowHeight );Ð
        rowSpan = Math.min( rowSpan, props.rows );Ð       if ( rowSpan ===
1 ) {Ð         // if brick spans only one column, just like singleModeÐ
          instance._masonryHorizontalPlaceBrick( $this, props.rowXs );Ð
        } else {Ð         // brick spans more than one rowÐ         // how
many different places could this brick fit horizontallyÐ         var
groupCount = props.rows + 1 - rowSpan,Ð             groupX = [],Ð
groupRowX, i;Ð         // for each group potential horizontal positionÐ
          for ( i=0; i < groupCount; i++ ) {Ð           // make an array of
colY values for that one groupÐ           groupRowX = props.rowXs.slice( i,
i+rowSpan );Ð           // and get the max value of the arrayÐ
groupX[i] = Math.max.apply( Math, groupRowX );Ð         }Ð
instance._masonryHorizontalPlaceBrick( $this, groupX );Ð       }Ð     });Ð
    },Ð   _masonryHorizontalPlaceBrick : function( $brick, setX ) {Ð     //
get the minimum Y value from the columnsÐ     var minimumX  =
Math.min.apply( Math, setX ),Ð         smallRow  = 0;Ð     // Find index of
smallest row, the first from the topÐ     for (var i=0, len = setX.length; i
< len; i++) {Ð       if ( setX[i] === minimumX ) {Ð         smallRow = i;Ð
          break;Ð       }Ð     }Ð     // position the brickÐ     var x =
minimumX,Ð         y = this.masonryHorizontal.rowHeight * smallRow;Ð
this._pushPosition( $brick, x, y );Ð     // apply setHeight to necessary
columnsÐ     var setWidth = minimumX + $brick.outerWidth(true),Ð
setSpan = this.masonryHorizontal.rows + 1 - len;Ð     for ( i=0; i < setSpan;
i++ ) {Ð       this.masonryHorizontal.rowXs[ smallRow + i ] = setWidth;Ð     }Ð
    },Ð   _masonryHorizontalGetContainerSize : function() {Ð     var
containerWidth = Math.max.apply( Math, this.masonryHorizontal.rowXs );Ð
return { width: containerWidth };Ð   },Ð   _masonryHorizontalResizeChanged :
function() {Ð     return this._checkIfSegmentsChanged(true);Ð   },Ð   //
===================== fitColumns =====================Ð
_fitColumnsReset : function() {Ð     this.fitColumns = {Ð       x : 0,Ð
y : 0,Ð       width : 0Ð     };Ð   },Ð   _fitColumnsLayout :
function( $elems ) {Ð     var instance = this,Ð         containerHeight =
this.element.height(),Ð         props = this.fitColumns;Ð
$elems.each( function() {Ð       var $this = $(this),Ð           atomW =
$this.outerWidth(true),Ð           atomH = $this.outerHeight(true);Ð       if
( props.y !== 0 && atomH + props.y > containerHeight ) {Ð         // if this
element cannot fit in the current columnÐ         props.x = props.width;Ð
          props.y = 0;Ð       }Ð       // position the atomÐ
instance._pushPosition( $this, props.x, props.y );Ð       props.width =
Math.max( props.x + atomW, props.width );Ð       props.y += atomH;Ð     });Ð
    },Ð   _fitColumnsGetContainerSize : function () {Ð     return { width :
this.fitColumns.width };Ð   },Ð   _fitColumnsResizeChanged : function() {Ð
      return true;Ð   },Ð   // ===================== cellsByColumn
=====================Ð   _cellsByColumnReset : function() {Ð
this.cellsByColumn = {Ð       index : 0Ð     };Ð     // get
this.cellsByColumn.columnWidthÐ     this._getSegments();Ð     // get
this.cellsByColumn.rowHeightÐ     this._getSegments(true);Ð   },Ð
_cellsByColumnLayout : function( $elems ) {Ð     var instance = this,Ð
          props = this.cellsByColumn;Ð     $elems.each( function(){Ð
var $this = $(this),Ð           col = Math.floor( props.index / props.rows ),Ð
            row = props.index % props.rows,Ð           x = ( col + 0.5 ) *
props.columnWidth - $this.outerWidth(true) / 2,Ð           y = ( row + 0.5 )
* props.rowHeight - $this.outerHeight(true) / 2;Ð
instance._pushPosition( $this, x, y );Ð       props.index ++;Ð     });Ð   },Ð
    _cellsByColumnGetContainerSize : function() {Ð
```

```
                                                        return { width :
Math.ceil( this.$filteredAtoms.length / this.cellsByColumn.rows ) *
this.cellsByColumn.columnWidth };Ð   },Ð   _cellsByColumnResizeChanged :
function() {Ð     return this._checkIfSegmentsChanged(true);Ð   },Ð   //
====================== straightAcross ======================Ð
_straightAcrossReset : function() {Ð     this.straightAcross = {Ð       x : 0Ð
      };Ð   },Ð   _straightAcrossLayout : function( $elems ) {Ð     var
instance = this;Ð     $elems.each( function( i ){Ð       var $this = $(this);Ð
        instance._pushPosition( $this, instance.straightAcross.x, 0 );Ð
instance.straightAcross.x += $this.outerWidth(true);Ð     });Ð   },Ð
_straightAcrossGetContainerSize : function() {Ð     return { width :
this.straightAcross.x };Ð   },Ð   _straightAcrossResizeChanged : function() {Ð
      return true;Ð   }Ð };Ð // ======================== imagesLoaded Plugin
================================Ð /*!Ð  * jQuery imagesLoaded plugin v1.1.0Ð
* http://github.com/desandro/imagesloadedÐ  *Ð  * MIT License. by Paul Irish
et al.Ð  */Ð // $('#my-container').imagesLoaded(myFunction)Ð // orÐ //
$('img').imagesLoaded(myFunction)Ð // execute a callback when all images have
loaded.Ð // needed because .load() doesn't work on cached imagesÐ // callback
function gets image collection as argumentÐ //  `this` is the containerÐ
$.fn.imagesLoaded = function( callback ) {Ð   var $this = this,Ð
$images = $this.find('img').add( $this.filter('img') ),Ð       len =
$images.length,Ð       blank = '',Ð       loaded =
[];Ð   function triggerCallback() {Ð     callback.call( $this, $images );Ð   }Ð
    function imgLoaded( event ) {Ð     var img = event.target;Ð     if
( img.src !== blank && $.inArray( img, loaded ) === -1 ){Ð
loaded.push( img );Ð       if ( --len <= 0 ){Ð
setTimeout( triggerCallback );Ð         $images.unbind( '.imagesLoaded',
imgLoaded );Ð       }Ð     }Ð   }Ð   // if no images, trigger immediatelyÐ
if ( !len ) {Ð     triggerCallback();Ð   }Ð
$images.bind( 'load.imagesLoaded error.imagesLoaded',
imgLoaded ).each( function() {Ð     // cached images don't fire load
sometimes, so we reset src.Ð     var src = this.src;Ð     // webkit hack from
http://groups.google.com/group/jquery-dev/browse_thread/thread/
eee6ab7b2da50e1fÐ     // data uri bypasses webkit log warning (thx doug jones)Ð
      this.src = blank;Ð     this.src = src;Ð   });Ð   return $this;Ð };Ð //
helper function for logging errorsÐ // $.error breaks jQuery chainingÐ var
logError = function( message ) {Ð   if ( window.console ) {Ð
window.console.error( message );Ð   }Ð };Ð // ======================  Plugin
bridge  ================================Ð // leverages data method to either
create or return $.Isotope constructorÐ // A bit from jQuery UIÐ //   https://
github.com/jquery/jquery-ui/blob/master/ui/jquery.ui.widget.jsÐ // A bit from
jcarouselÐ //   https://github.com/jsor/jcarousel/blob/master/lib/
jquery.jcarousel.jsÐ $.fn.isotope = function( options, callback ) {Ð   if
( typeof options === 'string' ) {Ð     // call methodÐ     var args =
Array.prototype.slice.call( arguments, 1 );Ð     this.each(function(){Ð
var instance = $.data( this, 'isotope' );Ð       if ( !instance ) {Ð
logError( "cannot call methods on isotope prior to initialization; " +Ð
              "attempted to call method '" + options + "'" );Ð         return;Ð
        }Ð       if ( !$.isFunction( instance[options] ) || options.charAt(0)
=== "_" ) {Ð         logError( "no such method '" + options + "' for isotope
instance" );Ð         return;Ð       }Ð       // apply methodÐ
instance[ options ].apply( instance, args );Ð     });Ð   } else {Ð
this.each(function() {Ð       var instance = $.data( this, 'isotope' );Ð
        if ( instance ) {Ð         // apply options & initÐ
instance.option( options );Ð         instance._init( callback );Ð       }
else {Ð         // initialize new instanceÐ         $.data( this, 'isotope',
new $.Isotope( options, this, callback ) );Ð       }Ð     });Ð   }Ð   //
return jQuery objectÐ   // so plugin methods do not have toÐ   return this;Ð
  };Ð
```

```
})( window, jQuery );
```

public\assets\frontend\js\jquery.magnific-popup.js

/*! Magnific Popup - v0.9.9 - 2013-12-27Ð http://dimsemenov.com/plugins/
magnific-popup/Ð Copyright (c) 2013 Dmitry Semenov; */Ð(function($) {Ð
>>core/Ð**Ð* Ð* Magnific Popup Core JS fileÐ* Ð*/Ð**Ð* Private static
constantsÐ*/Ðvar CLOSE_EVENT = 'Close',Ð$Tdõ$Uô4Äõ4UôUdTåB Ò t&Vf÷&T6Æ÷6Rrí
AFTER_CLOSE_EVENT = 'AfterClose',Ð$Tdõ$Uô TäEôUdTåB Ò t&Vf÷&T VæBrí
MARKUP_PARSE_EVENT = 'MarkupParse',Ðõ TåôUdTåB Ò t÷ Vârí4„ ätUôUdTåB Ò
'Change',Ðå2 Ò vÖg ríUdTåEôå2 Ò râr ² å2í$T E•ô4Ä 52 Ò vÖg ×&V G’rí
REMOVING_CLASS = 'mfp-removing',Ð $UdTåEô4Äõ4Uô4Ä 52 Ò vÖg × &WfVçBÖ6Æ÷6RsÐ**Ð
* Private vars Ð*/Ðvar mfp, // As we have only one instance of MagnificPopup
object, we define it locally to not to use 'this'ÐÖ væ–f–5 ÷ W Ò gVæ7F–öâ,—·Òí
_isJQ = !!(window.jQuery),Ð÷ &We7F GW2í÷v–æF÷r Ò B‡v–æF÷r’íö&öG’íöFö7VÖVçBí
_prevContentType,Ð÷w& 6Æ 76W2íö7W'% ÷ W G— SÐ**Ð* Private functionsÐ*/Ðvar
_mfpOn = function(name, f) {Ðmfp.ev.on(NS + name + EVENT_NS, f);ÐíövWDVÂ Ò
function(className, appendTo, html, raw) {Ðvar el =
document.createElement('div');Ðel.className = 'mfp-'+className;Ðif(html) {Ð
el.innerHTML = html;Ð}Ðif(!raw) {ÐVÂ Ò B†VÂ™½–b† VæEFò’™½el.appendTo(appendTo);Ð
™™¥ else if(appendTo) {Ð VæEFòæ VæD6†–ÆB†VÂ™½Ðreturn el;ÐíöÖg G&–vvW" Ò
function(e, data) {Ðmfp.ev.triggerHandler(NS + e, data);Ðif(mfp.st.callbacks) {Ð
™’òò 6öçfW'G2 &Ög WfVçDæ ÖR" Fò &WfVçDæ ÖR" 6 ÆÆ& 6² æB G&–vvW'2 —B –b —Bw2
presentÐ–R Ò Ræ6† $ Bƒ ’çFôÆ÷vW$6 6R,’ ² Rç6Æ–6Rƒ ™½–b†Ög ç7Bæ6 ÆÆ& 6·5¶UÒ’™½
mfp.st.callbacks[e].apply(mfp, $.isArray(data) ? data : [data]);Ð™¥ÐÍ
_getCloseBtn = function(type) {Ðif(type !== _currPopupType || !
mfp.currTemplate.closeBtn) {Ð–Ög æ7W'%FV× Æ FRæ6Æ÷6T'Fâ Ò
$(mfp.st.closeMarkup.replace('%title%', mfp.st.tClose));Ð•ö7W'% ÷ W G— R Ò
type;Ð™Ðreturn mfp.currTemplate.closeBtn;ÐÍòò –æ—F– Æ—¦R Ö væ–f–2 ÷ W öæÇ’
when called at least onceÐö6†V6´–ç7F æ6R Ò gVæ7F–öâ,’ ™½if(!
$.magnificPopup.instance) {Ð–Ög Ò æWr Ö væ–f–5 ÷ W ,™½Ög æ–æ—B,™½
$.magnificPopup.instance = mfp;Ð™ÐÍòò 552 G& ç6—F–öâ FWFV7F–öâÂ ‡GG ¢òð
stackoverflow.com/questions/7264899/detect-css-transitions-using-javascript-
and-without-modernizrÐ7W ÷'G5G& ç6—F–öç2 Ò gVæ7F–öâ,’ ™½var s =
document.createElement('p').style, // 's' for style. better to create an
element if body yet to existÐ—b Ò ²v×2rÂtòrÂtÖ÷¢rÂuvV&¶—BuÓ² òò wbr f÷" fVæFÐ-
if(s['transition'] !== undefined) {Ð—&WGW&â G'VS™™Ðwhile(v.length) {Ð
if(v.pop() + 'Transition' in s) {Ð™return true;ÐÐreturn false;ÐÍÐ**Ð* Public
functionsÐ*/ÐmagnificPopup.prototype = {Ð6öç7G'V7F÷#¢ Ö væ–f–5 ÷ W ÐÒ¢´ ¢
Initializes Magnific Popup plugin. Ð ¢ F†—2 gVæ7F–öâ —2 G&–vvW&VB öæÇ’ öæ6R
when $.fn.magnificPopup or $.magnificPopup is executedÐ ¢ý–æ—C¢ gVæ7F–öâ,’ ™½
var appVersion = navigator.appVersion;Ðmfp.isIE7 = appVersion.indexOf("MSIE
7.") !== -1; Ðmfp.isIE8 = appVersion.indexOf("MSIE 8.") !== -1;Ðmfp.isLowIE =
mfp.isIE7 || mfp.isIE8;Ðmfp.isAndroid = (/android/gi).test(appVersion);Ð
mfp.isIOS = (/iphone|ipad|ipod/gi).test(appVersion);Ðmfp.supportsTransition =
supportsTransitions();Ð// We disable fixed positioned lightbox on devices that
don't handle it nicely.Ð// If you know a better way of detecting this - let me
know.Ðmfp.probablyMobile = (mfp.isAndroid || mfp.isIOS || /(Opera Mini)|Kindle|
webOS|BlackBerry|(Opera Mobi)|(Windows Phone)|IEMobile/
i.test(navigator.userAgent));Ð_document = $(document);Ðmfp.popupsCache = {};ÐÍÒ
**Ð ¢ ÷ Vç2 ÷ W’ ¢   & Ò F F ¶FW67&— F–öåÝ ¢ý÷ Vã¢ gVæ7F–öâ†F F ’ Ðif(!
_body) {Ð•ö&öG’ Ò B†Fö7VÖVçBæ&öG’™Ðvar i;Ðif(data.isObj === false) {Ð™Ðòò 6öçfW'B
jQuery collection to array to avoid conflicts laterÐ–Ög æ—FV×2 Ò
data.items.toArray();Ð–Ög æ–æFW, Ò ™½f " —FV×2 Ò F F æ—FV×2item;Ð÷"†’ Ò ² ’ Â
items.length; i++) {Ðitem = items[i];Ðif(item.parsed)™Ð—FVÒ Ò —FVÒæVÂ³™™Ò½Ð
if(item === data.el[0]) {Ð–Ög æ–æFW, Ò™½'&V™™½Ð else {ÐÖg æ—FV×2 Ò
$.isArray(data.items) ? data.items : [data.items];Ð–Ög æ–æFW, Ò F F æ–æFW, ÇÂ ½
™ÐÐ// if popup is already opened - we just update the contentÐif(mfp.isOpen) {Ð
mfp.updateItemHTML();Ð—&WGW&â½Ðmfp.types = [];Ð wrapClasses = '';Ðif(data.mainEl
&& data.mainEl.length) {Ð–Ög æWb Ò F F æÖ –äVÂæW ƒ ™½ else {ÐÖg æWb Ò öFö7VÖVçC½
™ÐÐif(data.key) {Ð–b, Ög ç ÷ W 46 6†U¶F F æ¶W•Ò’™½mfp.popupsCache[data.key] = {};Ð
™™¥Ög æ7W'%FV× Æ FR Ò Ög ç ÷ W 46 6†U¶F F æ¶W•Ò½ else {ÐÖg æ7W'%FV× Æ FR Ò ·Ò½Ð
mfp.st = $.extend(true, {}, $.magnificPopup.defaults, data); Ð

™

mfp.fixedContentPos = mfp.st.fixedContentPos === 'auto' ? !
mfp.probablyMobile : mfp.st.fixedContentPos;™if(mfp.st.modal) {™Ð
mfp.st.closeOnContentClick = false;™–Ög ç7Bæ6Æ÷6Töä&t6Æ–6² Ò f Ç6S½
mfp.st.showCloseBtn = false;™–Ög ç7BæVæ &ÆTW66 T¶W' Ò f Ç6S½™™Ð/ Building markupÐ
™// main containers are created only once™™if(!mfp.bgOverlay) {™™Ðòò F &² ÷fW&Æ™•
mfp.bgOverlay = _getEl('bg').on('click'+EVENT_NS, function() {™™mfp.close();™™Ð½
mfp.wrap = _getEl('wrap').attr('tabindex', -1).on('click'+EVENT_NS,
function(e) {™™if(mfp._checkIfClose(e.target)) {™™ÐÖg æ6Æ÷6R,™™½™™Ð½Ög æ6öçF –æW" Ò
_getEl('container', mfp.wrap);™™™™mfp.contentContainer = _getEl('content');™Ð
if(mfp.st.preloader) {™–Ög ç &VÆö FW" Ò övWDVÂ,w &VÆö FW"rÂ Ög æ6öçF –æW"Â
mfp.st.tLoading);™™™Ð/ Initializing modules™™var modules =
$.magnificPopup.modules;™™for(i = 0; i < modules.length; i++) {™™Ðf " â Ò
modules[i];™–â Ò âæ6† $ Bƒ 'çFõW W$6 6R,' ² âç6Æ–6Rƒ ™½Ög ²v–æ—Br¶åÒæ6 ÆÂ†Ög "½
™™™™™™mfpTrigger('BeforeOpen');™™™™™™if(mfp.st.showCloseBtn) {™™Ðòò 6Æ÷6R 'WGFÖí–b,
mfp.st.closeBtnInside) {™™mfp.wrap.append(_getCloseBtn());™™Ð VÇ6R™™½
_mfpOn(MARKUP_PARSE_EVENT, function(e, template, values, item) {™™•
values.close_replaceWith = _getCloseBtn(item.type);™™™™}™™™™™™

™—Ò VÇ6R™½windowStyles.overflow = '™™Ý
$('html').css(windowStyles);Ð™}Ðdocument.off('keyup' + EVENT_NS + ' focusin' +
EVENT_NS);Ðmfp.ev.off(EVENT_NS);ÐÐ// clean up DOM elements that aren't removeÐÐ
mfp.wrap.attr('class', 'mfp-wrap').removeAttr('style');Ð
mfp.bgOverlay.attr('class', 'mfp-bg');Ðmfp.container.attr('class', 'mfp-
container');Ð// remove close button from target elementÐif(mfp.st.showCloseBtn
&&Ð(!mfp.st.closeBtnInside || mfp.currTemplate[mfp.currItem.type] === true)) {Ð
if(mfp.currTemplate.closeBtn)Ð™mfp.currTemplate.closeBtn.detach();ÐÐ
if(mfp._lastFocusedEl) {Ð'B†Ög åöÆ 7Dfö7W6VDVÂ'æfö7W2,"² òò WB F " fö7W2 & ™½Ð
mfp.currItem = null;™mfp.content = null;™Ðmfp.currTemplate = null;™Ðmfp.prevHeight
= 0;Ð_mfpTrigger(AFTER_CLOSE_EVENT);÷ÒÍW F FU6—¦S¢ gVæ7F–öâ‡v–ä†V–v‡B' Ð
if(mfp.isIOS) {Ð'òò f—†W2 "õ2 æ b & '2 ‡GG 3¢òöv—F‡V"æ6öÒöF–×6VÖVæ÷bôÖ væ–f–2Ð
Popup/issues/2Ð—f " ¦ööÔÆWfVÂ Ò Fö7VÖVçBæFö7VÖVçDVÆVÖVçBæ6Æ–VçEv–GF, ò
window.innerWidth;Ð—f " †V–v‡B Ò v–æF÷ræ–ææW$†V–v‡B ¢ ¦ööÔÆWfVÂ½
mfp.wrap.css('height', height);Ð–Ög çt, Ò †V–v‡C½ else {ÐÖg çt, Ò v–ä†V–v‡B ÇÂ
_window.height();Ð™ÐÐ// Fixes #84: popup incorrectly positioned with
position:relative on bodyÐif(!mfp.fixedContentPos) {ÐÖg çw& æ772,v†V–v‡BrÂ
mfp.wH);ÐÐÐ_mfpTrigger('Resize');ÐÐÍò¢' ¢ 6WB 6öçFVçB öb ÷ W & 6VB öâ 7W'&VçB
indexÐ ¢ýW F FT—FVÖ…DÒÃ¢ gVæ7F–öâ,' ½var item = mfp.items[mfp.index];ÐÐ// Detach
and perform modificationsÐmfp.contentContainer.detach();ÐÐif(mfp.content)Ð
mfp.content.detach();Ðif(!item.parsed) {Ð—FVÒ Ò Ög ç '6TVÂ, Ög æ–æFW, ™ÐÐvar
type = item.type;Ð_mfpTrigger('BeforeChange', [mfp.currItem ?
mfp.currItem.type : '', type]);Ð// BeforeChange event works like so:Ð//
_mfpOn('BeforeChange', function(e, prevType, newType) { });ÐÐmfp.currItem =
item;ÐÐif(!mfp.currTemplate[type]) {Ðf " Ö &·W Ò Ög ç7E·G— UÒ ò
mfp.st[type].markup : false;Ð'òò ÆÆ÷w2 Fò ÖöF–g' Ö &·W•
_mfpTrigger('FirstMarkupParse', markup);Ð––b†Ö &·W '™½mfp.currTemplate[type] =
$(markup);Ð—Ò VÇ6R™½// if there is no markup found we just define that template
is parsedÐ™mfp.currTemplate[type] = true;™™ÐÐif(_prevContentType &&
_prevContentType !== item.type) {Ð•
mfp.container.removeClass('mfp-'+_prevContentType+'-holder');Ð™Ðvar newContent
= mfp['get' + type.charAt(0).toUpperCase() + type.slice(1)](item,
mfp.currTemplate[type]);Ðmfp.appendContent(newContent, type);ÐÐitem.preloaded =
true;Ð_mfpTrigger(CHANGE_EVENT, item);™ÐprevContentType = item.type;™Ð// Append
container back after its content changedÐ
mfp.container.prepend(mfp.contentContainer);Ð_mfpTrigger('AfterChange');÷ÒÍò¢'
* Set HTML content of popupÐ ¢ý VæD6öçFVçC¢ gVæ7F–öâ†æWt6öçFVçBÂ G— R' ½
mfp.content = newContent;ÐÐif(newContent) {Ð–b†Ög ç7Bç6†÷t6Æ÷6T'Fâ bb
mfp.st.closeBtnInside &&Ð™mfp.currTemplate[type] === true)™{Ð// if there is no
markup, we just append close button element insideÐ™if(!mfp.content.find('.mfp-
close').length) {Ð™–Ög æ6öçFVçBæ VæB…övWD6Æ÷6T'Fâ,™™½Ò VÇ6R™½mfp.content =
newContent;Ð—} else ™ÐÖg æ6öçFVçB Ò rS™ÐÐmfpTrigger(BEFORE_APPEND_EVENT);™Ð
mfp.container.addClass('mfp-'+type+'-holder');Ð
mfp.contentContainer.append(mfp.content);ÐÒÍò¢' ¢ 7&V FW2 Ö væ–f–2 ÷ W F F
object based on given dataÐ ¢   & Ò ¶–çGÒ –æFW, –æFW, öb —FVÒ Fò '6] ¢ý
parseEl: function(index) {Ðvar item = mfp.items[index];™ÐG— ™½if(item.tagName) {Ð
item = { el: $(item) };Ð} else {ÐG— R Ò —FVÒçG— S½—FVÒ Ò ² F F ¢ —FVÒÂ 7&3¢
item.src };ÐÐif(item.el) {Ðf " G— W2 Ò Ög çG— W™½òò 6†V6² f÷" vÖg ÕE• Rr 6Æ 7™
for(var i = 0; i < types.length; i++) {Ð™
if(item.el.hasClass('mfp-'+types[i])) {Ð™—G— R Ò G— W5¶™Ö½'&V™™ÐÐ—FVÒç7&2 Ò
item.el.attr('data-mfp-src');Ð––b, —FVÒç7&2'™½item.src = item.el.attr('href');™ÐÐ
item.type = type || mfp.st.type || 'inline';Ðitem.index = index;™Ðitem.parsed =
true;Ðmfp.items[index] = item;™ÐmfpTrigger('ElementParse', item);ÐÐreturn
mfp.items[index];ÐÒÍò¢' ¢ –æ—F– Æ—¦W2 6–æVÆR ÷ W ÷"   w&÷W öb ÷ W ™ ¢ý
addGroup: function(el, options) {Ðvar eHandler = function(e) {ÐRæÖg VÂ Ò F†—3½
mfp._openClick(e, el, options);Ð}™ÐÐif(!options) {Ð÷ F–öç2 Ò ·Ö½™ÐÐvar eName =
'click.magnificPopup';Ðoptions.mainEl = el;™Ðif(options.items) {Ð÷ F–öç2æ—4ö&¢ Ò
true;Ð–VÂæöfb†Tæ ÖR'æöâ†Tæ ÖRÂ T† æFÆW"™½ else {Ð÷ F–öç2æ—4ö&¢ Ò f Ç6S½
if(options.delegate) {Ð™el.off(eName).on(eName, options.delegate , eHandler);™÷Ò
else {Ð

™™options.items = el™Ðel.off(eName).on(eName, eHandler)™™ÐÍö÷ Vä6Æ–6³¢
function(e, el, options) {Ðvar midClick = options.midClick !== undefined ?
options.midClick : $.magnificPopup.defaults.midClick;Ðif(!midClick &&
(e.which === 2 || e.ctrlKey || e.metaKey)) {Ð–&WGW&â™™Ðvar disableOn =
options.disableOn !== undefined ? options.disableOn :
$.magnificPopup.defaults.disableOn;Ðif(disableOn) ™Ð–b,Bæ–4gVæ7F–öâ†F–6 &ÆTöâ''
{Ð™if(!disableOn.call(mfp))™™Ð&WGW&â G'VS½Ð VÇ6R ² òò VÇ6R –Bw2 çVÖ&W™
if(_window.width() < disableOn) {Ð™–&WGW&â G'VS½™™™Ðif(e.type) ™Ð
e.preventDefault();Ð'òò F†–2 v–ÆÂ &WfVçB ÷ W g&öÒ 6Æ÷6–ær –b VÆVÖVçB –2
inside and popup is already openedÐ––b†Ög æ–4÷ Vâ'½e.stopPropagation()™™™ÐÐ
options.el = $(e.mfpEl);Ðif(options.delegate) ™Ð÷ F–öç2æ–FV×2 Ò
el.find(options.delegate);Ð™™Ðmfp.open(options)÷ÐÍò¢' ¢ W F FW2 FW‡B öâ &VÆö FW-
' ¢ýW F FU7F GW3¢ gVæ7F–öâ‡7F GW2Â FW‡B' ™Ðif(mfp.preloader) ™Ð–b…÷ &We7F GW2
== status) {Ð™mfp.container.removeClass('mfp-s-'+_prevStatus)™™™Ð–b, FW‡B bb
status === 'loading') {Ð™text = mfp.st.tLoading™™™Ðf " F F Ò½status: status™™Ð
text: textÐ–Ö½òò ÆÆ÷w2 Fò ÖöF–g' 7F GW÷öÖg G&–vvW",uW F FU7F GW2rÂ F F Ð½
status = data.status;Ð–FW‡B Ò F F çFW‡Ð½Ög ç &VÆö FW"æ‡FÖÂ‡FW‡BÐ½
mfp.preloader.find('a').on('click', function(e) {Ð™e.stopImmediatePropagation();Ð
™–ÒÐ½Ög æ6öçF –æW"æ FD6Æ 72,vÖg ×2Òr·7F GW2½÷ &We7F GW2 Ò 7F GW½ÐÐò-
™"Private" helpers that aren't private at allÐ¢ýòò 6†V6² Fò 6Æ÷6R ÷ W ÷" æ÷M
'òò 'F &vWB" –2 â VÆVÖVçB F† B v 2 6Æ–6¶VÖö6†V6´–d6Æ÷6S¢ gVæ7F–öâ‡F &vWB' ™Ð
if($(target).hasClass(PREVENT_CLOSE_CLASS)) {Ð–&WGW&â™™Ðvar closeOnContent =
mfp.st.closeOnContentClick;Ðvar closeOnBg = mfp.st.closeOnBgClick™™Ð
if(closeOnContent && closeOnBg) {Ð–&WGW&â G'VS½ else ™™Ðòò vR 6Æ÷6R F†R ÷ W –b
click is on close button or on preloader. Or if there is no content.Ð––b,
mfp.content || $(target).hasClass('mfp-close') || (mfp.preloader && target
=== mfp.preloader[0])) {Ð™return true™™™Ðòò –b 6Æ–6² –2 ÷WG6–FR F†R 6öçFVÇM
if((target !== mfp.content[0] && !$.contains(mfp.content[0], target))) {Ð™
if(closeOnBg) {Ð™'òò Æ 7B 6†V6²Â –b F†R 6Æ–6¶VB VÆVÖVçB –2 –â DôÒÂ †–â 6 6R –Bw2
removed onclick)Ð™––b, Bæ6öçF –ç2†Fö7VÖVçBÂ F &vWB' ™½return true™™™ÐÐ VÇ6R
if(closeOnContent) {Ð™return true™™™Ðreturn false÷ÐÍö FD6Æ 75FôÔe ¢
function(cName) {Ðmfp.bgOverlay.addClass(cName);Ðmfp.wrap.addClass(cName)÷ÐÍ
_removeClassFromMFP: function(cName) {Ðthis.bgOverlay.removeClass(cName);Ð
mfp.wrap.removeClass(cName);ÐÒÍö† 567&öÆÄ& #¢ gVæ7F–öâ‡v–ä†V–v‡B' ™½return
((mfp.isIE7 ? _document.height() : document.body.scrollHeight) > (winHeight
|| _window.height()));ÐÒÍ÷6WDfö7W3¢ gVæ7F–öâ,' ™½(mfp.st.focus ?
mfp.content.find(mfp.st.focus).eq(0) : mfp.wrap).focus();ÐÒÍööäfö7W4–ã¢
function(e) {Ðif(e.target !== mfp.wrap[0] && !$.contains(mfp.wrap[0],
e.target)) {Ð–Ög å÷6WDfö7W2,™½&WGW&â f Ç6S½ÒÍ÷ '6TÖ &·W ¢ gVæ7F–öâ‡FV× Æ FRÂ
values, item) {Ðvar arr;Ðif(item.data) {ÐÐf ÇVW2 Ò BæW‡FVæB†–FVÒæF F Â f ÇVW2™½Ð
_mfpTrigger(MARKUP_PARSE_EVENT, [template, values, item]);Ð™$.each(values,
function(key, value) {Ð––b‡f ÇVR ÓÓÒ VæFVf–æVB ÇÂ f ÇVR ÓÓÒ f Ç6R'™½return true;Ð
™™¥ '" Ò ¶W'ç7 Æ–B,uòr™½–b† '"æÆVæwF, â '™™½var el = template.find(EVENT_NS +
'-'+arr[0]);Ð™if(el.length > 0)™™™Ðf " GG" Ò '%³™™™Ó½–b† GG" ÓÓÒ w&W Æ 6Uv–F,r™™™½
if(el[0] !== value[0]) {Ð™™™–VÂç&W Æ 6Uv–F,‡f ÇVR™™™½Ð VÇ6R –b† GG" ÓÓÒ v–Örr™™™½
if(el.is('img')) {Ð™™™–VÂæ GG",w7&2rÂ f ÇVR™™™½ else {™™™ÐVÂç&W Æ 6Uv–F,, sÆ–Ör
src="'+value+'" class="' + el.attr('class') + '" />');Ð™™™ÐÐ VÇ6R™™™½
el.attr(arr[1], value);Ð™™™ÐÐ VÇ6R™™™½template.find(EVENT_NS +
'-'+key).html(value);Ð™™™Ó})÷ÐÍövWE67&öÆÆ& %6–¦S¢ gVæ7F–öâ,' ™½// thx David™™Ð
if(mfp.scrollbarSize === undefined) {Ð™–f " 67&öÆÄF–b Ò
document.createElement("div");Ð™–67&öÆÄF–bæ–B Ò &Ög ×6&Ò™½
scrollDiv.style.cssText = 'width: 99px; height: 99px; overflow: scroll;
position: absolute; top: -9999px;';Ð–Fö7VÖVçBæ&öG'æ VæD6†–ÆB‡67&öÆÄF–b™½
mfp.scrollbarSize = scrollDiv.offsetWidth - scrollDiv.clientWidth;Ð™•
document.body.removeChild(scrollDiv);Ð™™™Ðeturn mfp.scrollbarSize÷™™™Ð; /*
MagnificPopup core prototype end */Ð**Ð* Public static functionsÐ*/Ð
$.magnificPopup = {Ð–ç7F æ6S¢ çVÆÂÍ &÷Fó¢ Ö væ–f–5 ÷ W ç &÷F÷G– RÍÖöGVÆW3¢ µÒÐ
open: function(options, index) {Ð_checkInstance()™™™Ðif(!options) ™™™Ð÷ F–öç2 Ò ·Ö½
else {Ð–÷ F–öç2 Ò BæW‡FVæB‡G'VRÂ ·ÒÂ ÷ F–öç2™™™ÐÐoptions.isObj = true;Ð
options.index = index || 0;Ð

™return this.instance.open(options);ÐÍ6Æ÷6S¢
function() {Ðreturn $.magnificPopup.instance &&
$.magnificPopup.instance.close();ÐÒÍ&Vv–7FW$ÖöGVÆS¢ gVæ7F–öâ†æ ÖRÂ ÖöGVÆR’ ™ ½
if(module.options) {Ð’BæÖ væ–f–5 ÷ W æFVf VÇG5¶æ ÖUÒ Ò ÖöGVÆRæ÷ F–öç3½Ð
$.extend(this.proto, module.proto);™this.modules.push(name);ÐÍFVf VÇG3¢ ² Ð//
Info about options is in docs:Ð// http://dimsemenov.com/plugins/magnific-popup/
documentation.html#optionsÐdisableOn: 0,Ðkey: nullÐmidClick: falseÐmainClass:
'',Ðpreloader: trueÐfocus: '', // CSS selector of input to focus after popup
is openedÐcloseOnContentClick: falseÐcloseOnBgClick: trueÐcloseBtnInside:
true, ÐshowCloseBtn: trueÐenableEscapeKey: trueÐmodal: falseÐalignTop: false,Ð
removalDelay: 0,ÐprependTo: null,ÐfixedContentPos: 'auto',ÐfixedBgPos: 'auto'ÐÐ
overflowY: 'auto',ÐcloseMarkup: '<button title="%title%" type="button"
class="mfp-close">×</button>',ÐtClose: 'Close (Esc)'ÐÐLoading:
'Loading...'ÐÝ;Ð.fn.magnificPopup = function(options) {Ðö6†V6´–ç7F æ6R,“Ðf "
jqEl = $(this);Ðòò vR 6 ÆÂ 6öÖR ’ ÖWF†öB öb f–'7B & Ò –2 7G&–æ}–b
(typeof options === "string") {Ðif(options === 'open') {Ðf " –FV×2ÍitemOpts =
_isJQ ? jqEl.data('magnificPopup') : jqEl[0].magnificPopup,Ð™index =
parseInt(arguments[1], 10) || 0;Ð––b†–FVÔ÷ G2æ–FV×2’½items =
itemOpts.items[index];Ð–Ò VÇ6R½items = jqEl,Ðf(itemOpts.delegate)™{Ð–FV×2 Ò
items.find(itemOpts.delegate);Ð }Ðitems = items.eq(index);ÐÐ
mfp._openClick({mfpEl:items}, jqEl, itemOpts);Ð} else {Ð–b†Ög æ–4÷ Vä•
mfp[options].apply(mfp, Array.prototype.slice.call(arguments, 1));ÐÐÒ VÇ6R ½//
clone options objÐoptions = $.extend(true, {}, options);Ð™Ð* As Zepto doesn't
support .data() method for objects Ð * and it works only in normal browserÐ*
we assign "options" object directly to the DOM element. FTW!Ð */Ðf(_isJQ) {Ð
jqEl.data('magnificPopup', options);Ð} else {Ð§ VÅ³ ÒæÖ væ–f–5 ÷ W Ò ÷ F–öç3½Ð
mfp.addGroup(jqEl, options);ÐÝ&WGW&â § VÃ½;Ð/Quick benchmarkÐ*Ðar start =
performance.now(),Ð’Í&÷VæG2 Ò Ðor(i = 0; i < rounds; i++) {ÐÐ
console.log('Test #1:', performance.now() - start);Ðtart = performance.now();Ð
for(i = 0; i < rounds; i++) {ÐÐonsole.log('Test #2:', performance.now() -
start);Ð/Ð*>>core*/Ð*>>inline*/Ðar INLINE_NS = 'inline',Ðö†–FFVä6Æ 72Í
_inlinePlaceholder, ÐöÆ 7D–æÆ–æTVÆVÖVçBÍ÷ WD–æÆ–æTVÆVÖVçG4& 6² Ò gVæ7F–öâ,’ ™ ½
if(_lastInlineElement) {Ð•ö–æÆ–æU Æ 6V†öÆFW"æ gFW", öÆ 7D–æÆ–æTVÆVÖVçBæ FD6Æ 72€
_hiddenClass)).detach();Ð•öÆ 7D–æÆ–æTVÆVÖVçB Ò çVÆÃ½ÐÐ
$.magnificPopup.registerModule(INLINE_NS, {Ð÷ F–öç3¢ ½hiddenClass: 'hide', //
will be appended with `mfp-` prefixÐmarkup: '',ÐNotFound: 'Content not found'ÐÍ
proto: {ÐinitInline: function() {ÐÖg çG– W2ç W6,„”äÄ”äUôå2Ð½
_mfpOn(CLOSE_EVENT+'.'+INLINE_NS, function() {Ð™_putInlineElementsBack();Ð½ÐÐ
getInline: function(item, template) {Ð•÷ WD–æÆ–æTVÆVÖVçG4& 6²,Ð½–b†–FVÒç7&2’ ™ ½
var inlineSt = mfp.st.inline,Ð™–VÂ Ò B†–FVÒç7&Ð½f(el.length)Ð{Ðòò –b F &vWB
element has parent - we replace it with placeholder and put it back after
popup is closedÐ™–f " &VçB Ò VÅ³ Òç &VçDæöFS½–b‡ &VçB bb &VçBçF tæ ÖR™ ½
if(!_inlinePlaceholder) {Ð™•ö†–FFVä6Æ 72 Ò –æÆ–æU7Bæ†–FFVä6Æ 7S½
_inlinePlaceholder = _getEl(_hiddenClass);Ð™•ö†–FFVä6Æ 72 Ò vÖg Òrµö†–FFVä6Æ 7S½Ð
™// replace target inline element with placeholderÐlastInlineElement =
el.after(_inlinePlaceholder).detach().removeClass(_hiddenClass);ÐÐ–Ý
mfp.updateStatus('ready');Ð™} else {ÐÖg çW F FU7F GW2,vW'&÷"rÂ
inlineSt.tNotFound);Ð™–VÂ Ò B,sÆF–câ™½Ðtem.inlineElement = el,Ðeturn elÐÐ
mfp.updateStatus('ready');Ð–Ög å÷ '6TÕ &·W ‡FV× Æ FRÂ ·ÒÂ –FVÒ½&WGW&â
template;Ð}Ð);Ð*>>inline*/Ð*>>ajax*/Ðar AJAX_NS = 'ajax',Ðö ¦ „7W"Í
_removeAjaxCursor = function() {Ðif(_ajaxCur) {Ðö&öG’ç&VÖ÷fT6Æ 72…ö ¦ „7W"½ÐÍ
_destroyAjaxRequest = function() {Ð_removeAjaxCursor();Ðf(mfp.req) {Ð
mfp.req.abort();Ð}ÐÐ.magnificPopup.registerModule(AJAX_NS, {Ð÷ F–öç3¢ ½
settings: null,Ðcursor: 'mfp-ajax-cur',ÐError: '<a href="%url%">The content</
a> could not be loaded.'ÐÍÐ &÷Fó¢ ½initAjax: function() {Ð
mfp.types.push(AJAX_NS);Ð•ö ¦ „7W" Ò Ög ç7Bæ ¦ ,æ7W'6÷Ð½
_mfpOn(CLOSE_EVENT+'.'+AJAX_NS, _destroyAjaxRequest);Ð•öÖg öâ,t&Vf÷&T6† ævRâr ²
AJAX_NS, _destroyAjaxRequest);Ð},ÐetAjax: function(item) {ÐÐ–b…ö ¦ „7W™•
_body.addClass(_ajaxCur);Ð–Ög çW F FU7F GW2,vÆö F–ærrÐ½f " ÷ G2 Ò BæW‡FVæB‡½
url: item.src,Ð

```
success: function(data, textStatus, jqXHR) {f " FV×
data:data, xhr:jqXHR½öÖg G&–vvW",u  '6T ¦ ,rÂ FV×½
mfp.appendContent( $(temp.data), AJAX_NS );––FVÒæf–æ–6†VB Ò G'VS½
_removeAjaxCursor();–Ög å÷6WDfö7W2½6WEF–ÖV÷WB†gVæ7F–öâ,
mfp.wrap.addClass(READY_CLASS);–ÒÂ  ½Ög çW F FU7F GW2,w&V G’½
_mfpTrigger('AjaxContentAdded');},error: function() {÷&VÖ÷fT ¦ „7W'6÷",½
item.finished = item.loadError = true;–Ög çW F FU7F GW2,vW'&÷"rÂ
mfp.st.ajax.tError.replace('%url%', item.src));}ÒÂ Ög ç7Bæ ¦ ,ç6WGF–æw2½
mfp.req = $.ajax(opts);–&WGW&â rS½);/*>>ajax*/*>>image*/var _imgInterval,
_getTitle = function(item) {if(item.data && item.data.title !== undefined)
return item.data.title;var src = mfp.st.image.titleSrc;if(src) {
if($.isFunction(src)) {return src.call(mfp, item);Ò VÇ6R –b†–FVÒæVÂ’½return
item.el.attr(src) || '';};return '';};mfp.magnificPopup.registerModule('image',
{÷ F–öç3¢ ½markup: '<div class="mfp-figure">'+’sÆF–b 6Æ 73Ò&Ög Ö6Æ÷6R#ãÂöF–câr½
’sÆf–wW&Sar½'<div class="mfp-img"></div>'+<figcaption>'+sÆF–b 6Æ 73Ò&Ög
bottom-bar">'+'<div class="mfp-title"></div>'+<div class="mfp-counter">
</div>'+’sÂöF–car½</figcaption>'+ÂÂöf–wW&Sar½</div>’çrsor: 'mfp-zoom-out-
cur',titleSrc: 'title',verticalFit: true,Error: '<a href="%url%">The image</
a> could not be loaded.'Ò &÷Fó¢ ½initImage: function() {f " –Öu7B Ò
mfp.st.image,ns = '.image÷Ög çG– W2ç W6,,v–Ö vRr½öÖg öâ„õ TåâUdTåB¶ç2Â
function() {if(mfp.currItem.type === 'image' && imgSt.cursor) {
_body.addClass(imgSt.cursor);}½öÖg öâ„4Äõ4UôUdTåB¶ç2Â gVæ7F–öâ,’½
if(imgSt.cursor) {•ö&öG’ç&VÖ÷fT6Æ 72†–Öu7Bæ7W'6÷½window.off('resize' +
EVENT_NS);–Ò½öÖg öâ,u&W6–¦Rr¶ç2Â Ög ç&W6–¦T–Ö vR½–b†Ög æ–4Æ÷t”R’½
_mfpOn('AfterChange', mfp.resizeImage);},resizeImage: function() {f " –FVÒ Ò
mfp.currItem;––b, –FVÒ ÇÂ  –FVÒæ–Ör’ &WGW&½–b†Ög ç7Bæ–Ö vRçfW'F–6 Äf–B’½var
decr = 0;// fix box-sizing in ie7/8if(mfp.isLowIE) {FV7" Ò
parseInt(item.img.css('padding-top'), 10) + parseInt(item.img.css('padding-
bottom'),10);}item.img.css('max-height', mfp.wH-decr);},onImageHasSize:
function(item) {––b†–FVÒæ–Ör’½item.hasSize = true;if(_imgInterval) {
clearInterval(_imgInterval);}item.isCheckingImgSize = false;
_mfpTrigger('ImageHasSize', item);if(item.imgHidden) {–b†Ög æ6öçFVçB•
mfp.content.removeClass('mfp-loading');•–FVÒæ–Öt†–FFVâ Ò f ÇöB½/*
Function that loops until the image has size to display elements that rely on
it asap*/findImageSize: function(item) {f " 6÷VçFW" Ò ’img = item.img[0],
mfpSetInterval = function(delay) {––b…ö–Öt–çFW'f Â’½
clearInterval(_imgInterval);–Ÿòò FV6VÆW& F–ær –çFW'f Â F† B 6†V6·2 f÷" 6–¦R öb
an image•ö–Öt–çFW'f Â Ò 6WD–çFW'f Â†gVæ7F–öâ,’½if(img.naturalWidth > 0) {
mfp._onImageHasSize(item);’–&WGW&a½if(counter > 200) {
clearInterval(_imgInterval);}counter++;if(counter === 3) {Ög 6WD–çFW'f Âƒ  “½
} else if(counter === 40) {Ög 6WD–çFW'f ÂƒS  ½ else if(counter === 100) {
mfpSetInterval(500);}ÒÂ FVÆ  ½÷Ög 6WD–çFW'f Âƒ ½};getImage: function(item,
template) {–f " wV &B Ò DI// image load complete handleronLoadComplete =
function() {––b†–FVÒ’½if (item.img[0].complete) {–FVÒæ–Öræöfb,ræÖg Æö FW’½
if(item === mfp.currItem){’mfp._onImageHasSize(item);mfp.updateStatus('ready');
–Ÿ–FVÒæ† 56–¦R Ò G’VS½–FVÒæÆö FVB Ò GDVS½öÖg G&–vvW",t–Ö vTÆö D6ö× ÆWFR’½
else {’ò–b –Ö vR 6ö× ÆWFR 6†V6² f –Ç2 #  F–ÖW2 ƒ#  6V2’Â vR  77VÖR F† B
there was an error.’–wV &B’½–b†wV &B Â # ’½setTimeout(onLoadComplete,100);
else {’onLoadError();};// image error handleronLoadError = function() {
if(item) {’item.img.off('.mfploader');if(item === mfp.currItem){
mfp._onImageHasSize(item);’–Ög çW F FU7F GW2,vW'&÷"rÂ
imgSt.tError.replace('%url%', item.src) );}item.hasSize = true;item.loaded =
true;’item.loadError = true;};imgSt = mfp.st.image;f " VÂ Ò
template.find('.mfp-img');––b†VÂæÆVæwF,’½var img =
document.createElement('img');’img.className = 'mfp-img';item.img =
$(img).on('load.mfploader', onLoadComplete).on('error.mfploader',
onLoadError);’img.src = item.src;// without clone() "error" event is not
firing when IMG is replaced by new IMG// TODO: find a way to avoid such
cloning’if(el.is('img')) {–FVÒæ–Ör Ò –FVÒæ–Öræ6ÆöæR½img = item.img[0],
if(img.naturalWidth > 0) {
```

™™––FVÒæ† 56–¦R Ò G'VS½ else if(!img.width)™™{•Ð
item.hasSize = false;ÐÐÖg å÷ '6TÖ &·W ‡FV× Æ FRÂ½title: _getTitle(item),Ð
img_replaceWith: item.imgÐ–ÒÂ –FVÒÐ½Ög ç&W6–¦T–Ö vR,Ð½–b†–FVÒæ† 56–¦R’™™½
if(_imgInterval) clearInterval(_imgInterval);Ð™if(item.loadError)™™{Ð
template.addClass('mfp-loading');Ð™–Ög çW F FU7F GW2,vW'&÷"rÂ
imgSt.tError.replace('%url%', item.src));Ð™} else™™{ÐFV× Æ FRç&VÖ÷fT6Æ 72,vÖg Ð
loading');Ð™–Ög çW F FU7F GW2,w&V G’™™½Ðeturn templateÐ
mfp.updateStatus('loading');Ð––FVÒæÆö F–ær Ò G'VÐ½–b, –FVÒæ† 56–¦R’™™½
item.imgHidden = true;Ð™template.addClass('mfp-loading');Ð
mfp.findImageSize(item);Ð–Ò–&WGW&â FV× Æ FS½Ð);Ð*>>image*/Ð*>>zoom*/Ðar
hasMozTransform,ÐvWD† 4Ö÷¥G& ç6f÷&Ò Ò gVæ7F–öâ,’ ½if(hasMozTransform ===
undefined) {Ð–† 4Ö÷¥G& ç6f÷&Ò Ò Fö7VÖVçBæ7&V FTVÆVÖVçB,w r’ç7G–ÆRäÖ÷¥G& ç6f÷&Ò
== undefined;Ð}Ðeturn hasMozTransform;ÐÐ.magnificPopup.registerModule('zoom',
{Ð÷ F–öç3¢ ½enabled: false,Ðasing: 'ease-in-out',Ðuration: 300,Ðpener:
function(element) {Ð–&WGW&â VÆVÖVçBæ–2,v–Örr’ ò VÆVÖVçB ¢ VÆVÖVçBæf–æB,v–Örr™½Ð
–ÒÐ &÷Fó¢ ÐinitZoom: function() {Ðf " ¦öö0Ö7B Ò Ög ç7Bç¦öö0Ö7ns = '.zoom™™½mage,Ð
if(!zoomSt.enabled || !mfp.supportsTransition) {Ð™returnÐÐf " GW& F–öâ Ò
zoomSt.duration,Ð™getElToAnimate = function(image)™™{Ðf " æWt–Ör Ò
image.clone().removeAttr('style').removeAttr('class').addClass('mfp-animated-
image'),Ð™™™transition = 'all '+(zoomSt.duration/1000)+'s ' + zoomSt.easing,Ð
cssObj = {Ð™™– ÷6–F–öã¢ vf–†™™VBrÌ¤–æFWƒ¢ “™™™™ÍÆVgC¢™™™ÍF÷ ¢™™™Ír×vV&¶–BÖr·EÒ Ò 774ö&¥²rÐ
visibility': 'hidden'Ð™™™},Ð = 'transitioÐ™;Ð74ö&¥²r×vV&¶–BÒr·EÒ Ò 774ö&¥²rÐ
moz-'+t] = cssObj['-o-'+t] = cssObj[t] = transition;Ð™–æWt–Ö ræ772†774ö&¢™™½&WGW&â
newImg;Ð™™™},ÐhowMainContent = function()™™{ÐÖg æ6öçFVçBæ772,wf–6–&–Æ–G’rÂ
'visible');Ð™™™},ÐpenTimeout,ÐanimatedImg;Ð™™™•ÐÖg öâ,t'V–ÆD6öçG&öÇ2r¶ç2Â gVæ7F–öâ,’™™½
if(mfp._allowZoom()) {Ð™–6ÆV %F–ÖV÷WB†÷ VåF–ÖV÷WÐ™™½Ög æ6öçFVçBæ772,wf–6–&–Æ–G’rÂ
'hidden');Ð™’òò & 6–6 ÆÇ’Â ÆÂ 6öFR &VÆ÷r FöW2 –2 6ÆöæW2 W†–7F–ær –Ö vRÂ WG2 –â
on top of the current one and animated itÐ™™™–Ö vR Ò Ög åövWD–FVÕFõ¦öö0Ö™™½–b,
image) {Ð™™showMainContent();ÐeturÐ™™™ æ–Ö FVD–Ör Ò vWDVÅFô æ–Ö FR†–Ö vR™™™•
animatedImg.css(mfp._getOffset());Ð™–Ög çw& æ VæB† æ–Ö FVD–ÖÐ™™½÷ VåF–ÖV÷WB
= setTimeout(function() {Ð™™™animatedImg.css(mfp._getOffset(true));Ð
openTimeout = setTimeout(function() {Ð™™™–6†÷tÖ –ä6öçFVçÐ,™™½6WEF–ÖV÷WB†gVæ7F–öâ,™™™½
animatedImg.remove();Ð™™™™™image = animatedImg = null;Ð
_mfpTrigger('ZoomAnimationEnded');Ð™™™–ÒÂ b“² òò fö–B &Æ–æ² v†Vâ 7v–F6†–ær
images Ð™™™}, duration); // this timeout equals animation duratÐ™™nÐÂ b“² òò ''
adding this timeout we avoid short glitch at the beginning of animationÐ™™’òò
Lots of timeouts...Ð™™}Ð™™½öÖg öâ„$TdõÖ$UÖ4Äõ4UÖUdÅB¶ç2Â gVæ7F–öâ,’™™½
if(mfp._allowZoom()) {Ð™–6ÆV %F–ÖV÷WB†÷ VåF–ÖV÷WÐ™™½Ög ç7Bç&VÖ÷f ÄFVÆ ’ Ò
duration;Ð™––b, –Ö vR™™™½image = mfp._getItemToZoom();Ðf(!image) {Ð&WGW&â½Ð
animatedImg = getElToAnimate(image);Ð™™™™ æ–Ö FVD–Ö ræ772, Ög åövWDöfg6WB‡G'VR’™™™½
mfp.wrap.append(animatedImg);Ð™–Ög æ6öçFVçBæ772,wf–6–&–Æ–G’rÂ v†–FFVâ™™™½
setTimeout(function() {Ð™™™animatedImg.css(mfp._getOffset()™™™);ÐÂ bÐ½ÐÐ½
_mfpOn(CLOSE_EVENT+ns, function() {Ð™™if(mfp._allowZoom())™™™{Ð6†÷tÖ –ä6öçFVçB,™™½
if(animatedImg) {Ð™™™animatedImg.remove();Ð™™™–Ö vR Ò çVÆÆ½Ö ™™½ÐallowZoom:
function() {Ð–&WGW&â Ög æ7W'$–FVÒçG– R ÓÓÒ v–Ö vRS½ÐgetItemToZoom: function()
{Ð––b†Ög æ7W'$–FVÒæ† 56–¦R’™™½return mfp.currItem.img;Ð VÇ6R™™½return false;ÐÐÐ/
Get element postion relative to viewportÐ_getOffset: function(isLarge) {Ðf " VÃ½
if(isLarge) {Ð™el = mfp.currItem.img;Ð VÇ6R™™½el =
mfp.st.zoom.opener(mfp.currItem.el || mfp.currItem);ÐÐ™™™f " öfg6WB Ò VÂæöfg6WB,™™½
var paddingTop = parseInt(el.css('padding-top'),10);Ð–f " FF–æt&÷GFöÒ Ò
parseInt(el.css('padding-bottom'),10);Ð–öfg6WBçF÷ ÓÒ , B‡v–æF÷r’ç67&öÆÅF÷ ,’ Ò
paddingTop);Ð’™™™ æ–Ö F–ær ÆVgB ² F÷ ² v–GF,ö†V–v‡B Æöö·2 vÆ–F6‡’ –â f–&Vf÷,Â
but perfect in Chrome. And vice-versa.Ð™’™™™¢™™™f " ö&¢ Ò™™½width: el.width(),Ð/ fix
Zepto height+padding issueÐ™™™height: (_isJQ ? el.innerHeight() :
el[0].offsetHeight) - paddingBottom - paddingTopÐ–™™½òò ’ † FR Fò Fò F†–2Â 'WB
there is no another optionÐ––b, vWD† 4Ö÷¥G& ç6f÷&Ò,’ ’™™½obj['-moz-transform'] =
obj['transform'] = 'translate(' + offset.left + 'px,' + offset.top + 'px)';Ð–Ò
else {Ð™obj.left = offset.left;Ðbj.top = offset.top;Ð&WGW&â ö&¢Ð);Ð*>>zoom*/Ð
>>iframe/ÐÐar IFRAME_NS = 'iframe',ÐöV× G• vR Ò ròö &÷WC¦&Æ æ²rÐ
_fixIframeBugs = function(isShowing) {Ð

™if(mfp.currTemplate[IFRAME_NS]) {Ðf " VÂ
= mfp.currTemplate[IFRAME_NS].find('iframe');Ð--b†VÂæÆVæwF,' ™// reset src
after the popup is closed to avoid "video keeps playing after popup is
closed" bugÐ™if(!isShowing)™ÐVÅ³ Òç7&2 Ò öV× G• VÐ½Ð/ IE8 black screen bug fIXÐ
if(mfp.isIE8) {Ð™–VÂæ772,vF–7 Æ 'rÂ –56†÷v–ær ò v&Æö6²r ¢ væöæRr™½ÐÓÐ
$.magnificPopup.registerModule(IFRAME_NS, {Ð÷ F–öç3¢ ™½markup: '<div class="mfp-
iframe-scaler">'+Ð™'sÆF–b 6Æ 73Ò&Ög Ö6Æ÷6R#ãÂöF–car½sÆ–g& ÖR 6Æ 73Ò&Ög Ö–g& ÖR"
src="//about:blank" frameborder="0" allowfullscreen></iframe>'+Ð™' Ð,Ð
srcAction: 'iframe_src',Ð// we don't care and support only one default type of
URL by defaultÐpatterns: {Ð–÷WGV&S¢™½index: 'youtube.com',™Ðid: 'v=',™Ðsrc: '//
www.youtube.com/embed/%id%?autoplay=1'Ð–ÒÍf–ÖVó¢™½index: 'vimeo.com/',™Ðid: '/',Ð
src: '//player.vimeo.com/video/%id%?autoplay=1'Ð–ÒÍvÖ 3¢™½index: '//
maps.google.',Ð™src: '%id%&output=embed™½ÐÐ &÷Fó¢ ™½initIframe: function() {Ð
mfp.types.push(IFRAME_NS);Ð•öÖg öâ,t&Vf÷&T6† ævRrÂ gVæ7F–öâ†RÂ &WeG– RÂ
newType) {Ð™if(prevType !== newType)™Ð–b‡ &WeG– R ÓÓÒ ”e$ ÔUôå2™½
_fixIframeBugs(); // iframe if removedÐ™–Ò VÇ6R –b†æWuG– R ÓÓÒ ”e$ ÔUôå2™½
_fixIframeBugs(true); // iframe is showingÐ™–Ò}// else™Ðòò –g& ÖR 6÷W&6R –2
switched, don't do anythingÐ™/™}ÒÐ½öÖg öâ„4Äõ4UôUdTåB ² râr ² ”e$ ÔUôå2Â
function() {Ð™_fixIframeBugs()÷Ð™½ÐgetIframe: function(item, template) {Ðf "
embedSrc = item.src;Ð–f " –g& ÖU7B Ò Ög ç7Bæ–g& ÖS½ÐæV 6,†–g& ÖU7Bç GFW&ç2Â
function() {Ð™if(embedSrc.indexOf(this.index) > -1)™Ð–b‡F†–2æ–B™½if(typeof
this.id === 'string') {Ð™–VÖ&VE7&2 Ò
embedSrc.substr(embedSrc.lastIndexOf(this.id)+this.id.length,
embedSrc.length);Ð™} else™ÐVÖ&VE7&2 Ò F†–2æ–Bæ6 ÆÂ, F†–2Â VÖ&VE7&2™½ÐÓVÖ&VE7&2
= this.src.replace('%id%', embedSrc);Ð™–&WGW&â f Ç6S² òò '&V™½Ð™½f " F F ö&¢
= {};Ð--b†–g& ÖU7Bç7&4 7F–öâ'™½dataObj[iframeSt.srcAction] = embedSrc;Ð
mfp._parseMarkup(template, dataObj, item);Ð–Ög çW F FU7F GW2,w&V G'rÐ½&WGW&â
template;Ð}½);Ð*>>iframe*/Ð*>>gallery*/Ð**Ð* Get looped index depending on
number of slidesÐ*/Ðvar _getLoopedId = function(index) {Ðvar numSlides =
mfp.items.length;Ðif(index > numSlides - 1) {Ð&WGW&â –æFW, Ò çVÕ6Æ–FW3½ else
if(index < 0) {Ð–&WGW&â çVÕ6Æ–FW2 ² –æFW™½Ðeturn index;ÐÍ÷&W Æ 6T7W'%F÷F Â Ò
function(text, curr, total) {Ðreturn text.replace(/%curr%/gi, curr +
1).replace(/%total%/gi, total);ÐÓÐ$.magnificPopup.registerModule('gallery', {Ð
options: {Ðenabled: false,Ðarrowmarkup: '<button title="%title%" type="button"
class="mfp-arrow mfp-arrow-%dir%"></button>',Ðpreload: [0,2],Ð
navigateByImgClick: true,Ðarrows: true,ÐÐPrev: 'Previous (Left arrow key)',Ð
tNext: 'Next (Right arrow key)',ÐtCounter: '%curr% of %total%'ÐÐ &÷Fó¢ ™½
initGallery: function() {Ð–f " u7B Ò Ög ç7Bæv ÆÆW'™Ðns = '.mfp-gallery',Ð
supportsFastClick = Boolean($.fn.mfpFastClick);Ð–Ög æF–&V7F–öâ Ò G'VS² òò G'VR
- next, false - prevÐ•–b, u7B ÇÂ u7BæVæ &ÆVB ' &WGW&â f Ç6Ð½÷w& 6Æ 76W2 ³Ò r
mfp-gallery';Ð•öÖg öâ„õ TåôUdTåB¶ç2Â gVæ7F–öâ,'™½if(gSt.navigateByImgClick)™{Ð
mfp.wrap.on('click'+ns, '.mfp-img', function() {Ð™™if(mfp.items.length > 1) {Ð
mfp.next();Ð™–&WGW&â f çoS½ÐÐ½Ðdocument.on('keydown'+ns, function(e)™{Ð–b
(e.keyCode === 37) {Ð™mfp.prev()÷Ð VÇ6R –b †Ræ¶W”6öFR ÓÓÒ 3'™½mfp.next()÷Ð);Ð
™–ÒÐ½öÖg öâ,uW F FU7F GW2r¶ç2Â gVæ7F–öâ†RÂ F F '™½if(data.text)™ÐF F çFW‡B Ò
_replaceCurrTotal(data.text, mfp.currItem.index, mfp.items.length);Ð™}ÐÐ½
_mfpOn(MARKUP_PARSE_EVENT+ns, function(e, element, values, item) {Ð™var l =
mfp.items.length;Ð™values.counter = l > 1 ? _replaceCurrTotal(gSt.tCounter,
item.index, l) : '';Ð–ÒÐ½öÖg öâ,t'V–ÆD6öçG&öÇ2r ² ç2Â gVæ7F–öâ,'™½
if(mfp.items.length > 1 && gSt.arrows && !mfp.arrowLeft) {Ð™–f " Ö &·W Ò
gSt.arrowMarkup,Ð™™arrowLeft = mfp.arrowLeft = $(markup.replace(/%title%/gi,
gSt.tPrev).replace(/%dir%/gi, 'left')).addClass(PREVENT_CLOSE_CLASS),™•™
arrowRight = mfp.arrowRight = $(markup.replace(/%title%/gi,
gSt.tNext).replace(/%dir%/gi, 'right')).addClass(PREVENT_CLOSE_CLASS);Ð™–f "
eName = supportsFastClick ? 'mfpFastClick' : 'click';Ð™– '&÷tÆVgE¶Tæ ÖUÐ
(function() {Ð™™mfp.prev()÷Ð™™1™Ð&÷u&–v‡E¶Tæ ÖUÒ†gVæ7F–öâ,™½mfp.next()÷Ð™™1™Ðò
Polyfill for :before and :after (adds elements with classes mfp-a and mfp-b)Ð™•
if(mfp.isIE7) {Ð™™_getEl('b', arrowLeft[0], false, true);Ð_getEl('a',
arrowLeft[0], false, true);Ð™™_getEl('b', arrowRight[0], false, true);Ð
_getEl('a', arrowRight[0], false, true);Ð

™™™

™ns = '.'+eName;Ðò 2 ¦W Fòæ§2 FöW6âwB † fR â V 7’ v ’
to add custom events (like jQuery), so we implement it in this wayÐ
$.fn.mfpFastClick = function(callback) {Ðreturn $(this).each(function() {Ðif "
elem = $(this),Ð™lock;Ðb, 7W ÷'G5F÷V6, ’Ð½var timeout,Ð7F 'E,Í7F 'E’Í
pointerMoved,Ð™— ö–ÇBÍçVÕ ö–çFWÐ3½elem.on('touchstart' + ns, function(e)™{Ð
pointerMoved = false;Ð™–çVÕ ö–çFW'2 ÒÐ™½ ö–çB Ò Ræ÷&–v–æ ÄWfVçB ò
e.originalEvent.touches[0] : e.touches[0];Ð™—7F 'E, Ò ö–çBæ6Æ–VçE/™½7F 'E’ Ò
point.clientY;Ð™•÷v–æF÷ræöâ,wF÷V6†Ö÷fRr¶ç2Â gVæ7F–öâ†R™½point =
e.originalEvent ? e.originalEvent.touches : e.touches;Ð™numPointers =
point.length;Ð™point = point[0];Ðif (Math.abs(point.clientX - startX) > 10™||Ð
Math.abs(point.clientY - startY) > 10) {Ð™— ö–çFW$Ö÷fVB Ò G™VS½Væ&–æEF÷V6„Ö÷fR,“½
™™™}ÐÒ’æöâ,wF÷V6†VæBr¶ç2Â gVæ7F–öâ†R™½unbindTouchMove();Ðif(pointerMoved ||
numPointers > 1) {Ð™—&WGW&a½Ðlock = true;Ð.preventDefault();Ð
clearTimeout(timeout);Ð™timeout = setTimeout(function() {ÐÆö6² Ò f ÇÖS½,
ghostClickDelay);Ð™callback();Ð ½ÐÐÐVÆVÒæöâ,v6Æ–6²r ² ç2Â gVæ7F–öâ,’ ™½if(!
lock) {Ð™–6 ÆÆ& 6²,™½Ò ½);ÐÍÐBæfâæFW7G&÷”Ög f 7D6Æ–6² Ò gVæ7F–öâ,’ ™½
$(this).off('touchstart' + ns + ' click' + ns);Ðif(supportsTouch)
_window.off('touchmove'+ns+' touchend'+ns);ÐÓ½)();Ð*>>fastclick*/Ð
_checkInstance(); })(window.jQuery || window.Zepto);

public\assets\frontend\js\map-settings.js

```
//  ======================================================================Ð/•
Theme Name: Lumen - Multi-purpose Bootstrap TemplateÐ/•F†VÖR U$“¢ ‡GG ¢òð
themeforest.net/user/responsiveexpertsÐ/”FW67&— F–öã¢ F†—2 ¦ f 67&— B f–ÆR —2
using as a settings file. This file includes the sub scripts for the
javascripts used in this template.Ð/•fW'6–öã¢  ã//” WF†÷#¢ &W7 öç6—fR W‡ W'G≠/•
Author URI: http://themeforest.net/user/responsiveexpertsÐ/•F w3⁄//
======================================================================Ð/•D $ÄR
OF CONTENTSÐ/’ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÝ//’   â Ö   6WGF–æwÐ/
======================================================================Ð
(function() {Ð'W6R 7G&–7B#½òò ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒ    Ö   6WGF–æw2
----------------------ÐÒòò
------------------------------------------------------------ÐÒòò v†Vâ F†R v–æF÷r
has finished loading create our google map belowÐ
google.maps.event.addDomListener(window, 'load', init);ÐgVæ7F–öâ –æ—B,’ ™//
Basic options for a simple Google MapÐ// For more options see: https://
developers.google.com/maps/documentation/javascript/reference#MapOptionsÐvar
mapOptions = {Ð’òò †÷r ¦öö0VB –â –÷R v çB F†R Ö   Fò 7F 'B  B † Çv —2 &W V—&VÐ•
zoom: 11,Ð—67&öÆÇv†VVÃ¢ f Ç6ÐÍòò F†R Æ F—GVFR  æB Æöæv—GVFR Fò 6VçFW" F†R Ö
(always required)Ð–6VçFW#¢ æWr vöövÆRæÖ  2äÆ DÆærƒC ãcs  Â Ós2ã“C  ’Â òò æWr
YorkÐ’òò †÷r –÷R v÷VÆB Æ–¶R Fò 7G–ÆR F†R Ö  ã’òò F†—2 —2 v†W&R –÷R v÷VÆB   7FR
any style found on Snazzy Maps.Ð—7G–ÆW3Ð{"stylers":[{"saturation":-100},
{"gamma":0.8},{"lightness":4},{"visibility":"on"}]},
{"featureType":"landscape.natural","stylers":[{"visibility":"on"},
{"color":"#5dff00"},{"gamma":4.97},{"lightness":-5},{"saturation":100}]}]}ÐÐ/
Get the HTML DOM element that will contain your map Ð// We are using a div
with id="map" seen below in the <body>Ðvar mapElement =
document.getElementById('map');Ð// Create the Google Map using our element and
options defined aboveÐvar map = new google.maps.Map(mapElement, mapOptions);ÐÐ/
Let's also add a marker while we're at itÐvar marker = new google.maps.Marker({Ð
position: new google.maps.LatLng(40.6700, -73.9400),Ð–Ö  ¢ Ö ™ÏF—FÆS¢ tÇVÖVâ }
™});Ð})(jQuery);Ð
```

public\assets\frontend\js\settings.js

```
//  ==========================================================================Ð/•
Theme Name: Lumen - Multi-purpose Bootstrap TemplateÐ/•F†VÖR U$“¢ ‡GG ¢òð
themeforest.net/user/responsiveexpertsÐ/”FW67&— F–öã¢ F†—2 ¦ f 67&— B f–ÆR —2
using as a settings file. This file includes the sub scripts for the
javascripts used in this template.Ð/•fW'6–öã¢  ã//” WF†÷#¢ &W7 öç6—fR W‡ W'G≠/•
Author URI: http://themeforest.net/user/responsiveexpertsÐ/•F w3≠/
==========================================================================Ð/•D $ÄR
OF CONTENTSÐ/’ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÝ/’   â  &VÆö FW≠/’  "â fÆW‡6Æ–FW≠/
03. Adding fixed position to headerÐ/’  Bâ ÖVçR FövvÆ]/’  Râ  ÷  W//’  bâ
Scroll To TopÐ/’  râ 67&öÆÂ Fò F÷Ð/
==========================================================================Ð
(function() {Ð'W6R 7G&–7B#½òò ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒ   â  &VÆö FW"
----------------------ÐÒòò
-------------------------------------------------------------Ð
$(window).load(function() {™$("#loader").fadeOut();™Ð
$("#mask").delay(1000).fadeOut("slow");ÐÒ“½òò ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒ  "â
Flexslider -------------------ÐÒòò
-------------------------------------------------------------Ð™•
$(window).load(function() {™  $('#banner-slider').flexslider({™Ð æ–Ö F–öã¢
"fade",™Ð–6öçG&öÄæ c¢ G'V™Í6Æ–FW6†÷u7 VVC£S  ™Í æ–Ö F–öå7 VVC£   ™ÍF—&V7F–öäæ c¢
true™  });™Ð $('#testimonial-slider').flexslider({™Ð æ–Ö F–öã¢ '6Æ–FR™Í
controlNav: true,™—6Æ–FW6†÷u7 VVC£c  ™Í æ–Ö F–öå7 VVC£#  ™ÍF—&V7F–öäæ c¢ G'V]
™  });™Ð});ÐÒòò ÒÒÒÒÒÒÒÒÒÒ  2â  FF–ær f—†VB  ÷6—F–öâ Fò †V FW" ÒÒÒÒÒÒÒÒÒÒ’òò
-------------------------------------------------------------Ð
$(document).scroll(function() {™if ($(document).scrollTop() >= 1) {™Ð
$('.header-area').addClass('navbar-fixed-top');™} else {™Ð $('.header-
area').removeClass('navbar-fixed-top');™}ÐÒ“½òò ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒ  Bâ ÖVçR
Toggle --------------------ÐÒòò
-------------------------------------------------------------ÐB, "çFövrÐ
navi" ).click(function() {™$( ".menu-main" ).toggle();™ÐÒ“½òò
-------------------- 05. pop up ---------------------ÐÒòò
-------------------------------------------------------------Ð
$(document).ready(function() {Ð       $('.yellow-solid').magnificPopup({Ð
          delegate: '.srch',Ð         type: 'image',Ð         tLoading:
'Loading image',Ð         mainClass: 'mfp-img-mobile',Ð         gallery: {Ð
            enabled: true,Ð           navigateByImgClick: true,Ð
preload: [0,1] // Will preload 0 - before current, and 1 after the current
imageÐ         },Ð         image: {Ð           tError: '<a href="%url%">The
image #%curr%</a> could not be loaded.',Ð           titleSrc: function(item) {Ð
             // return item.el.attr('title') + '<small>by Marsel Van Oosten</
small>';Ð           }Ð         }Ð       });Ð     });Ð  òò ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒ
06. Scroll To Top ------------------ÐÒòò
-------------------------------------------------------------ÐB†gVæ7F–öâ,’ ½
$(document).on("scroll", onScroll);™™Ð
$('a[href*=#]:not([href=#])').click(function() {™’B,ræÖVçRÖÖ –â
li').removeClass('active');™’B‡F†—2’ç  &VçB,’æ FD6Æ 72,v 7F—fRr™½–b
(location.pathname.replace(/^\//, '') == this.pathname.replace(/^\//, '') ||
location.hostname == this.hostname) {™™var target = $(this.hash);™™Ðarget =
target.length ? target : $('[name=' + this.hash.slice(1) + ']');™™if
(target.length) {™™’B,v‡FÖÂÆ&öG’r’æ æ–Ö FR‡½™™™scrollTop: target.offset().top™™ÐÂ
100);™™—&WGW&â f ÇöS½™™™
```

•

```
$(window).scroll(function() {Ðif ($(this).scrollTop() >= 50) {        // If
page is scrolled more than 50pxÐ’B,r7&WGW&â×Fò×F÷ r’æf FT–âƒ#  “²    òò f FR –â
the arrowÐ} else {ÐB,r7&WGW&â×Fò×F÷ r’æf FT÷WBƒ#  “²   òò VÇ6R f FR ÷WB F†R
arrowÐ}Ð“½B,r7&WGW&â×Fò×F÷ r’æ6Æ–6²†gVæ7F–öâ,’ ²      òò v†Vâ  '&÷r —2 6Æ–6¶VÐ
$('body,html').animate({Ð—67&öÆÅF÷  ¢                        òò 67&öÆÂ Fò F÷
of bodyÐ}, 500)÷Ð“½})(jQuery);Ð
```

public\assets\js\bootstrap.js

```
/*!Ð* Bootstrap v3.3.6 (http://getbootstrap.com)Ð* Copyright 2011-2015
Twitter, Inc.Ð* Licensed under the MIT licenseÐ*/Ðif (typeof jQuery ===
'undefined') {Ð throw new Error('Bootstrap\'s JavaScript requires jQuery')ÐÐ
+function ($) {Ð 'use strict';Ð var version = $.fn.jquery.split(' ')
[0].split('.')Ð if ((version[0] < 2 && version[1] < 9) || (version[0] == 1 &&
version[1] == 9 && version[2] < 1) || (version[0] > 2)) {Ð   throw new
Error('Bootstrap\'s JavaScript requires jQuery version 1.9.1 or higher, but
lower than version 3')Ð }ÐÐ(jQuery);Ð*
========================================================================Ð*
Bootstrap: transition.js v3.3.6Ð* http://getbootstrap.com/javascript/
#transitionsÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
======================================================================== */Ð
+function ($) {Ð 'use strict';Ð // CSS TRANSITION SUPPORT (Shoutout: http://
www.modernizr.com/)Ð //
================================================================Ð function
transitionEnd() {Ð   var el = document.createElement('bootstrap')Ð   var
transEndEventNames = {Ð     WebkitTransition : 'webkitTransitionEnd',Ð
MozTransition    : 'transitionend',Ð     OTransition      : 'oTransitionEnd
otransitionend',Ð     transition       : 'transitionend'Ð   }Ð   for (var
name in transEndEventNames) {Ð     if (el.style[name] !== undefined) {Ð
return { end: transEndEventNames[name] }Ð     }Ð   }Ð   return false //
explicit for ie8 (  ._.)Ð }Ð // http://blog.alexmaccaw.com/css-transitionsÐ
$.fn.emulateTransitionEnd = function (duration) {Ð   var called = falseÐ
var $el = thisÐ   $(this).one('bsTransitionEnd', function () { called =
true })Ð   var callback = function () { if (!called)
$($el).trigger($.support.transition.end) }Ð   setTimeout(callback, duration)Ð
    return thisÐ }Ð $(function () {Ð   $.support.transition = transitionEnd()Ð
    if (!$.support.transition) returnÐ   $.event.special.bsTransitionEnd = {Ð
      bindType: $.support.transition.end,Ð     delegateType:
$.support.transition.end,Ð     handle: function (e) {Ð       if
($(e.target).is(this)) return e.handleObj.handler.apply(this, arguments)Ð
      }Ð   }Ð })ÐÐ(jQuery);Ð*
========================================================================Ð*
Bootstrap: alert.js v3.3.6Ð* http://getbootstrap.com/javascript/#alertsÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
======================================================================== */Ð
+function ($) {Ð 'use strict';Ð // ALERT CLASS DEFINITIONÐ //
=======================Ð var dismiss = '[data-dismiss="alert"]'Ð var Alert   =
function (el) {Ð   $(el).on('click', dismiss, this.close)Ð }Ð Alert.VERSION =
'3.3.6'Ð Alert.TRANSITION_DURATION = 150Ð Alert.prototype.close = function
(e) {Ð   var $this    = $(this)Ð   var selector = $this.attr('data-target')Ð
    if (!selector) {Ð     selector = $this.attr('href')Ð     selector =
selector && selector.replace(/.*(?=#[^\s]*$)/, '') // strip for ie7Ð   }Ð
var $parent = $(selector)Ð   if (e) e.preventDefault()Ð   if (!
$parent.length) {Ð     $parent = $this.closest('.alert')Ð   }Ð
$parent.trigger(e = $.Event('close.bs.alert'))Ð   if (e.isDefaultPrevented())
returnÐ   $parent.removeClass('in')Ð   function removeElement() {Ð     //
detach from parent, fire event then clean up dataÐ
$parent.detach().trigger('closed.bs.alert').remove()Ð   }Ð
$.support.transition && $parent.hasClass('fade') ?Ð     $parentÐ
        .one('bsTransitionEnd', removeElement)Ð
        .emulateTransitionEnd(Alert.TRANSITION_DURATION) :Ð
removeElement()Ð }Ð // ALERT PLUGIN DEFINITIONÐ // =======================Ð
function Plugin(option) {Ð
```

```
                              return this.each(function () {Ð     var $this =
$(this)Ð     var data  = $this.data('bs.alert')Ð     if (!data)
$this.data('bs.alert', (data = new Alert(this)))Ð     if (typeof option ==
'string') data[option].call($this)Ð   })Ð }Ð var old = $.fn.alertÐ
$.fn.alert             = PluginÐ $.fn.alert.Constructor = AlertÐ // ALERT NO
CONFLICTÐ // ==================Ð $.fn.alert.noConflict = function () {Ð
$.fn.alert = oldÐ   return thisÐ }Ð // ALERT DATA-APIÐ // ===============Ð
$(document).on('click.bs.alert.data-api', dismiss, Alert.prototype.close)Ð
(jQuery);Ð*
============================================================================Ð*
Bootstrap: button.js v3.3.6Ð* http://getbootstrap.com/javascript/#buttonsÐ*
============================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
============================================================================ */Ð
+function ($) {Ð 'use strict';Ð // BUTTON PUBLIC CLASS DEFINITIONÐ //
==============================Ð var Button = function (element, options) {Ð
this.$element  = $(element)Ð   this.options   = $.extend({}, Button.DEFAULTS,
options)Ð   this.isLoading = falseÐ }Ð Button.VERSION  = '3.3.6'Ð
Button.DEFAULTS = {Ð   loadingText: 'loading...'Ð }Ð
Button.prototype.setState = function (state) {Ð   var d    = 'disabled'Ð
var $el  = this.$elementÐ   var val  = $el.is('input') ? 'val' : 'html'Ð
var data = $el.data()Ð   state += 'Text'Ð   if (data.resetText == null)
$el.data('resetText', $el[val]())Ð   // push to event loop to allow forms to
submitÐ   setTimeout($.proxy(function () {Ð     $el[val](data[state] ==
null ? this.options[state] : data[state])Ð     if (state == 'loadingText') {Ð
        this.isLoading = trueÐ       $el.addClass(d).attr(d, d)Ð     } else
if (this.isLoading) {Ð       this.isLoading = falseÐ
$el.removeClass(d).removeAttr(d)Ð     }Ð   }, this), 0)Ð }Ð
Button.prototype.toggle = function () {Ð   var changed = trueÐ   var $parent
= this.$element.closest('[data-toggle="buttons"]')Ð   if ($parent.length) {Ð
      var $input = this.$element.find('input')Ð     if ($input.prop('type')
== 'radio') {Ð       if ($input.prop('checked')) changed = falseÐ
$parent.find('.active').removeClass('active')Ð       this.
$element.addClass('active')Ð     } else if ($input.prop('type') ==
'checkbox') {Ð       if (($input.prop('checked')) !== this.
$element.hasClass('active')) changed = falseÐ       this.
$element.toggleClass('active')Ð     }Ð     $input.prop('checked', this.
$element.hasClass('active'))Ð     if (changed) $input.trigger('change')Ð   }
else {Ð     this.$element.attr('aria-pressed', !this.
$element.hasClass('active'))Ð     this.$element.toggleClass('active')Ð   }Ð }Ð
  // BUTTON PLUGIN DEFINITIONÐ // ========================Ð function
Plugin(option) {Ð   return this.each(function () {Ð     var $this   = $(this)Ð
      var data    = $this.data('bs.button')Ð     var options = typeof option
== 'object' && optionÐ     if (!data) $this.data('bs.button', (data = new
Button(this, options)))Ð     if (option == 'toggle') data.toggle()Ð     else
if (option) data.setState(option)Ð   })Ð }Ð var old = $.fn.buttonÐ
$.fn.button             = PluginÐ $.fn.button.Constructor = ButtonÐ // BUTTON
NO CONFLICTÐ // ==================Ð $.fn.button.noConflict = function () {Ð
$.fn.button = oldÐ   return thisÐ }Ð // BUTTON DATA-APIÐ // ===============Ð
$(document)Ð   .on('click.bs.button.data-api', '[data-toggle^="button"]',
function (e) {Ð     var $btn = $(e.target)Ð     if (!$btn.hasClass('btn'))
$btn = $btn.closest('.btn')Ð     Plugin.call($btn, 'toggle')Ð     if (!
($(e.target).is('input[type="radio"]') ||
$(e.target).is('input[type="checkbox"]'))) e.preventDefault()Ð   })Ð
    .on('focus.bs.button.data-api blur.bs.button.data-api', '[data-
toggle^="button"]', function (e) {Ð
$(e.target).closest('.btn').toggleClass('focus', /^focus(in)?$/.test(e.type))Ð
    })Ð(jQuery);Ð*
============================================================================Ð
```

```
                                                                        *
Bootstrap: carousel.js v3.3.6Ð* http://getbootstrap.com/javascript/#carouselÐ
* ========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
========================================================================== */Ð
+function ($) {Ð 'use strict';Ð // CAROUSEL CLASS DEFINITIONÐ //
==========================Ð var Carousel = function (element, options) {Ð
this.$element    = $(element)Ð   this.$indicators = this.
$element.find('.carousel-indicators')Ð   this.options     = optionsÐ
this.paused      = nullÐ   this.sliding     = nullÐ   this.interval    = nullÐ
    this.$active     = nullÐ   this.$items      = nullÐ
this.options.keyboard && this.$element.on('keydown.bs.carousel',
$.proxy(this.keydown, this))Ð   this.options.pause == 'hover' && !
('ontouchstart' in document.documentElement) && this.$elementÐ
      .on('mouseenter.bs.carousel', $.proxy(this.pause, this))Ð
      .on('mouseleave.bs.carousel', $.proxy(this.cycle, this))Ð }Ð
Carousel.VERSION  = '3.3.6'Ð Carousel.TRANSITION_DURATION = 600Ð
Carousel.DEFAULTS = {Ð   interval: 5000,Ð   pause: 'hover',Ð   wrap: true,Ð
keyboard: trueÐ }Ð Carousel.prototype.keydown = function (e) {Ð   if (/input|
textarea/i.test(e.target.tagName)) returnÐ   switch (e.which) {Ð     case 37:
this.prev(); breakÐ     case 39: this.next(); breakÐ     default: returnÐ   }Ð
    e.preventDefault()Ð }Ð Carousel.prototype.cycle = function (e) {Ð   e ||
(this.paused = false)Ð   this.interval && clearInterval(this.interval)Ð
this.options.intervalÐ     && !this.pausedÐ     && (this.interval =
setInterval($.proxy(this.next, this), this.options.interval))Ð   return thisÐ
  }Ð Carousel.prototype.getItemIndex = function (item) {Ð   this.$items =
item.parent().children('.item')Ð   return this.$items.index(item || this.
$active)Ð }Ð Carousel.prototype.getItemForDirection = function (direction,
active) {Ð   var activeIndex = this.getItemIndex(active)Ð   var willWrap =
(direction == 'prev' && activeIndex === 0)Ð                || (direction ==
'next' && activeIndex == (this.$items.length - 1))Ð   if (willWrap && !
this.options.wrap) return activeÐ   var delta = direction == 'prev' ? -1 : 1Ð
    var itemIndex = (activeIndex + delta) % this.$items.lengthÐ   return this.
$items.eq(itemIndex)Ð }Ð Carousel.prototype.to = function (pos) {Ð   var
that        = thisÐ   var activeIndex = this.getItemIndex(this.$active = this.
$element.find('.item.active'))Ð   if (pos > (this.$items.length - 1) || pos <
0) returnÐ   if (this.sliding)       return this.
$element.one('slid.bs.carousel', function () { that.to(pos) }) // yes, "slid"Ð
    if (activeIndex == pos) return this.pause().cycle()Ð   return
this.slide(pos > activeIndex ? 'next' : 'prev', this.$items.eq(pos))Ð }Ð
Carousel.prototype.pause = function (e) {Ð   e || (this.paused = true)Ð   if
(this.$element.find('.next, .prev').length && $.support.transition) {Ð
this.$element.trigger($.support.transition.end)Ð     this.cycle(true)Ð   }Ð
this.interval = clearInterval(this.interval)Ð   return thisÐ }Ð
Carousel.prototype.next = function () {Ð   if (this.sliding) returnÐ   return
this.slide('next')Ð }Ð Carousel.prototype.prev = function () {Ð   if
(this.sliding) returnÐ   return this.slide('prev')Ð }Ð
Carousel.prototype.slide = function (type, next) {Ð   var $active   = this.
$element.find('.item.active')Ð   var $next     = next ||
this.getItemForDirection(type, $active)Ð   var isCycling = this.intervalÐ
var direction = type == 'next' ? 'left' : 'right'Ð   var that      = thisÐ
if ($next.hasClass('active')) return (this.sliding = false)Ð   var
relatedTarget = $next[0]Ð   var slideEvent = $.Event('slide.bs.carousel', {Ð
      relatedTarget: relatedTarget,Ð     direction: directionÐ   })Ð   this.
$element.trigger(slideEvent)Ð   if (slideEvent.isDefaultPrevented()) returnÐ
    this.sliding = trueÐ   isCycling && this.pause()Ð   if (this.
$indicators.length) {Ð     this.
$indicators.find('.active').removeClass('active')Ð     var $nextIndicator =
$(this.$indicators.children()[this.getItemIndex($next)])Ð
```

```
                                                                $nextIndicator
&& $nextIndicator.addClass('active')Ð   }Ð   var slidEvent =
$.Event('slid.bs.carousel', { relatedTarget: relatedTarget, direction:
direction }) // yes, "slid"Ð   if ($.support.transition && this.
$element.hasClass('slide')) {Ð     $next.addClass(type)Ð
$next[0].offsetWidth // force reflowÐ     $active.addClass(direction)Ð
$next.addClass(direction)Ð     $activeÐ       .one('bsTransitionEnd',
function () {Ð         $next.removeClass([type, direction].join('
')).addClass('active')Ð         $active.removeClass(['active',
direction].join(' '))Ð         that.sliding = falseÐ
setTimeout(function () {Ð           that.$element.trigger(slidEvent)Ð
          }, 0)Ð       })Ð
        .emulateTransitionEnd(Carousel.TRANSITION_DURATION)Ð   } else {Ð
$active.removeClass('active')Ð     $next.addClass('active')Ð     this.sliding
= falseÐ     this.$element.trigger(slidEvent)Ð   }Ð   isCycling &&
this.cycle()Ð   return thisÐ }Ð // CAROUSEL PLUGIN DEFINITIONÐ //
==========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.carousel')Ð     var options = $.extend({}, Carousel.DEFAULTS,
$this.data(), typeof option == 'object' && option)Ð     var action  = typeof
option == 'string' ? option : options.slideÐ     if (!data)
$this.data('bs.carousel', (data = new Carousel(this, options)))Ð     if
(typeof option == 'number') data.to(option)Ð     else if (action) data[action]
()Ð     else if (options.interval) data.pause().cycle()Ð   })Ð }Ð var old =
$.fn.carouselÐ $.fn.carousel             = PluginÐ $.fn.carousel.Constructor
= CarouselÐ // CAROUSEL NO CONFLICTÐ // ====================Ð
$.fn.carousel.noConflict = function () {Ð   $.fn.carousel = oldÐ   return thisÐ
  }Ð // CAROUSEL DATA-APIÐ // =================Ð var clickHandler = function
(e) {Ð   var hrefÐ   var $this   = $(this)Ð   var $target =
$($this.attr('data-target') || (href = $this.attr('href')) &&
href.replace(/.*(?=#[^\s]+$)/, '')) // strip for ie7Ð   if (!
$target.hasClass('carousel')) returnÐ   var options = $.extend({},
$target.data(), $this.data())Ð   var slideIndex = $this.attr('data-slide-to')Ð
    if (slideIndex) options.interval = falseÐ   Plugin.call($target, options)Ð
    if (slideIndex) {Ð     $target.data('bs.carousel').to(slideIndex)Ð   }Ð
e.preventDefault()Ð }Ð $(document)Ð   .on('click.bs.carousel.data-api',
'[data-slide]', clickHandler)Ð   .on('click.bs.carousel.data-api', '[data-
slide-to]', clickHandler)Ð $(window).on('load', function () {Ð   $('[data-
ride="carousel"]').each(function () {Ð     var $carousel = $(this)Ð
Plugin.call($carousel, $carousel.data())Ð   })Ð })Ð}(jQuery);Ð*
============================================================================Ð*
Bootstrap: collapse.js v3.3.6Ð* http://getbootstrap.com/javascript/#collapseÐ
* ============================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
============================================================================ */Ð
+function ($) {Ð 'use strict';Ð // COLLAPSE PUBLIC CLASS DEFINITIONÐ //
================================Ð var Collapse = function (element, options) {Ð
    this.$element      = $(element)Ð   this.options       = $.extend({},
Collapse.DEFAULTS, options)Ð   this.$trigger      = $('[data-
toggle="collapse"][href="#' + element.id + '"],' +Ð
'[data-toggle="collapse"][data-target="#' + element.id + '"]')Ð
this.transitioning = nullÐ   if (this.options.parent) {Ð     this.$parent =
this.getParent()Ð   } else {Ð     this.addAriaAndCollapsedClass(this.
$element, this.$trigger)Ð   }Ð   if (this.options.toggle) this.toggle()Ð }Ð
Collapse.VERSION  = '3.3.6'Ð Collapse.TRANSITION_DURATION = 350Ð
Collapse.DEFAULTS = {Ð   toggle: trueÐ }Ð Collapse.prototype.dimension =
function () {Ð   var hasWidth = this.$element.hasClass('width')Ð   return
hasWidth ? 'width' : 'height'Ð }Ð Collapse.prototype.show = function () {Ð
if (this.transitioning || this.$element.hasClass('in')) returnÐ
```

```
                                                                Ð   var
activesDataÐ   var actives = this.$parent && this.
$parent.children('.panel').children('.in, .collapsing')Ð   if (actives &&
actives.length) {Ð     activesData = actives.data('bs.collapse')Ð     if
(activesData && activesData.transitioning) returnÐ   }Ð   var startEvent =
$.Event('show.bs.collapse')Ð   this.$element.trigger(startEvent)Ð   if
(startEvent.isDefaultPrevented()) returnÐ   if (actives && actives.length) {Ð
      Plugin.call(actives, 'hide')Ð     activesData ||
actives.data('bs.collapse', null)Ð   }Ð   var dimension = this.dimension()Ð
this.$elementÐ     .removeClass('collapse')Ð     .addClass('collapsing')
[dimension](0)Ð     .attr('aria-expanded', true)Ð   this.$triggerÐ
      .removeClass('collapsed')Ð     .attr('aria-expanded', true)Ð
this.transitioning = 1Ð   var complete = function () {Ð     this.$elementÐ
        .removeClass('collapsing')Ð       .addClass('collapse in')[dimension]
('')Ð     this.transitioning = 0Ð     this.$elementÐ
        .trigger('shown.bs.collapse')Ð   }Ð   if (!$.support.transition)
return complete.call(this)Ð   var scrollSize = $.camelCase(['scroll',
dimension].join('-'))Ð   this.$elementÐ     .one('bsTransitionEnd',
$.proxy(complete, this))Ð
      .emulateTransitionEnd(Collapse.TRANSITION_DURATION)[dimension](this.
$element[0][scrollSize])Ð }Ð Collapse.prototype.hide = function () {Ð   if
(this.transitioning || !this.$element.hasClass('in')) returnÐ   var
startEvent = $.Event('hide.bs.collapse')Ð   this.$element.trigger(startEvent)Ð
    if (startEvent.isDefaultPrevented()) returnÐ   var dimension =
this.dimension()Ð   this.$element[dimension](this.$element[dimension]())
[0].offsetHeightÐ   this.$elementÐ     .addClass('collapsing')Ð
      .removeClass('collapse in')Ð     .attr('aria-expanded', false)Ð   this.
$triggerÐ     .addClass('collapsed')Ð     .attr('aria-expanded', false)Ð
this.transitioning = 1Ð   var complete = function () {Ð
this.transitioning = 0Ð     this.$elementÐ       .removeClass('collapsing')Ð
        .addClass('collapse')Ð       .trigger('hidden.bs.collapse')Ð   }Ð
if (!$.support.transition) return complete.call(this)Ð   this.$elementÐ
[dimension](0)Ð     .one('bsTransitionEnd', $.proxy(complete, this))Ð
      .emulateTransitionEnd(Collapse.TRANSITION_DURATION)Ð }Ð
Collapse.prototype.toggle = function () {Ð   this[this.
$element.hasClass('in') ? 'hide' : 'show']()Ð }Ð Collapse.prototype.getParent
= function () {Ð   return $(this.options.parent)Ð     .find('[data-
toggle="collapse"][data-parent="' + this.options.parent + '"]')Ð
      .each($.proxy(function (i, element) {Ð       var $element = $(element)Ð
        this.addAriaAndCollapsedClass(getTargetFromTrigger($element),
$element)Ð     }, this))Ð     .end()Ð }Ð
Collapse.prototype.addAriaAndCollapsedClass = function ($element, $trigger) {Ð
    var isOpen = $element.hasClass('in')Ð   $element.attr('aria-expanded',
isOpen)Ð   $triggerÐ     .toggleClass('collapsed', !isOpen)Ð     .attr('aria-
expanded', isOpen)Ð }Ð function getTargetFromTrigger($trigger) {Ð   var hrefÐ
    var target = $trigger.attr('data-target')Ð     || (href =
$trigger.attr('href')) && href.replace(/.*(?=#[^\s]+$)/, '') // strip for ie7Ð
    return $(target)Ð }Ð // COLLAPSE PLUGIN DEFINITIONÐ //
==========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.collapse')Ð     var options = $.extend({}, Collapse.DEFAULTS,
$this.data(), typeof option == 'object' && option)Ð     if (!data &&
options.toggle && /show|hide/.test(option)) options.toggle = falseÐ     if (!
data) $this.data('bs.collapse', (data = new Collapse(this, options)))Ð     if
(typeof option == 'string') data[option]()Ð   })Ð }Ð var old = $.fn.collapseÐ
$.fn.collapse             = PluginÐ $.fn.collapse.Constructor = CollapseÐ //
COLLAPSE NO CONFLICTÐ // ====================Ð $.fn.collapse.noConflict =
function () {Ð   $.fn.collapse = oldÐ   return thisÐ }Ð // COLLAPSE DATA-APIÐ
  // =================Ð $(document).on('click.bs.collapse.data-api', '[data-
toggle="collapse"]', function (e) {Ð
```

```
                                        var $this   = $(this)Ð   if (!
$this.attr('data-target')) e.preventDefault()Ð   var $target =
getTargetFromTrigger($this)Ð   var data    = $target.data('bs.collapse')Ð
var option  = data ? 'toggle' : $this.data()Ð   Plugin.call($target, option)Ð
  })Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: dropdown.js v3.3.6Ð* http://getbootstrap.com/javascript/#dropdownsÐ
* ========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
========================================================================= */Ð
+function ($) {Ð 'use strict';Ð // DROPDOWN CLASS DEFINITIONÐ //
=========================Ð var backdrop = '.dropdown-backdrop'Ð var toggle
= '[data-toggle="dropdown"]'Ð var Dropdown = function (element) {Ð
$(element).on('click.bs.dropdown', this.toggle)Ð }Ð Dropdown.VERSION = '3.3.6'Ð
  function getParent($this) {Ð   var selector = $this.attr('data-target')Ð
if (!selector) {Ð     selector = $this.attr('href')Ð     selector = selector
&& /#[A-Za-z]/.test(selector) && selector.replace(/.*(?=#[^\s]*$)/, '') //
strip for ie7Ð   }Ð   var $parent = selector && $(selector)Ð   return $parent
&& $parent.length ? $parent : $this.parent()Ð }Ð function clearMenus(e) {Ð
if (e && e.which === 3) returnÐ   $(backdrop).remove()Ð
$(toggle).each(function () {Ð     var $this         = $(this)Ð     var
$parent       = getParent($this)Ð     var relatedTarget = { relatedTarget:
this }Ð     if (!$parent.hasClass('open')) returnÐ     if (e && e.type ==
'click' && /input|textarea/i.test(e.target.tagName) && $.contains($parent[0],
e.target)) returnÐ     $parent.trigger(e = $.Event('hide.bs.dropdown',
relatedTarget))Ð     if (e.isDefaultPrevented()) returnÐ     $this.attr('aria-
expanded', 'false')Ð
$parent.removeClass('open').trigger($.Event('hidden.bs.dropdown',
relatedTarget))Ð   })Ð }Ð Dropdown.prototype.toggle = function (e) {Ð   var
$this = $(this)Ð   if ($this.is('.disabled, :disabled')) returnÐ   var
$parent  = getParent($this)Ð   var isActive = $parent.hasClass('open')Ð
clearMenus()Ð   if (!isActive) {Ð     if ('ontouchstart' in
document.documentElement && !$parent.closest('.navbar-nav').length) {Ð
        // if mobile we use a backdrop because click events don't delegateÐ
        $(document.createElement('div'))Ð         .addClass('dropdown-
backdrop')Ð         .insertAfter($(this))Ð         .on('click', clearMenus)Ð
      }Ð     var relatedTarget = { relatedTarget: this }Ð
$parent.trigger(e = $.Event('show.bs.dropdown', relatedTarget))Ð     if
(e.isDefaultPrevented()) returnÐ     $thisÐ       .trigger('focus')Ð
        .attr('aria-expanded', 'true')Ð     $parentÐ
        .toggleClass('open')Ð       .trigger($.Event('shown.bs.dropdown',
relatedTarget))Ð   }Ð   return falseÐ }Ð Dropdown.prototype.keydown =
function (e) {Ð   if (!/(38|40|27|32)/.test(e.which) || /input|textarea/
i.test(e.target.tagName)) returnÐ   var $this = $(this)Ð   e.preventDefault()Ð
    e.stopPropagation()Ð   if ($this.is('.disabled, :disabled')) returnÐ
var $parent  = getParent($this)Ð   var isActive = $parent.hasClass('open')Ð
if (!isActive && e.which != 27 || isActive && e.which == 27) {Ð     if
(e.which == 27) $parent.find(toggle).trigger('focus')Ð     return
$this.trigger('click')Ð   }Ð   var desc = ' li:not(.disabled):visible a'Ð
var $items = $parent.find('.dropdown-menu' + desc)Ð   if (!$items.length)
returnÐ   var index = $items.index(e.target)Ð   if (e.which == 38 && index >
0)                 index--         // upÐ   if (e.which == 40 && index <
$items.length - 1) index++         // downÐ   if (!
~index)                                         index = 0Ð
$items.eq(index).trigger('focus')Ð }Ð // DROPDOWN PLUGIN DEFINITIONÐ //
=========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this = $(this)Ð     var data  =
$this.data('bs.dropdown')Ð     if (!data) $this.data('bs.dropdown', (data =
new Dropdown(this)))Ð
```

```
                            if (typeof option == 'string')
data[option].call($this)Ð   })Ð }Ð var old = $.fn.dropdownÐ
$.fn.dropdown             = PluginÐ $.fn.dropdown.Constructor = DropdownÐ //
DROPDOWN NO CONFLICTÐ // ====================Ð $.fn.dropdown.noConflict =
function () {Ð   $.fn.dropdown = oldÐ   return thisÐ }Ð // APPLY TO STANDARD
DROPDOWN ELEMENTSÐ // ===================================Ð $(document)Ð
    .on('click.bs.dropdown.data-api', clearMenus)Ð
    .on('click.bs.dropdown.data-api', '.dropdown form', function (e)
{ e.stopPropagation() })Ð   .on('click.bs.dropdown.data-api', toggle,
Dropdown.prototype.toggle)Ð   .on('keydown.bs.dropdown.data-api', toggle,
Dropdown.prototype.keydown)Ð   .on('keydown.bs.dropdown.data-api', '.dropdown-
menu', Dropdown.prototype.keydown)Ð }(jQuery);Ð*
========================================================================Ð*
Bootstrap: modal.js v3.3.6Ð* http://getbootstrap.com/javascript/#modalsÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
========================================================================== */Ð
+function ($) {Ð 'use strict';Ð // MODAL CLASS DEFINITIONÐ //
======================Ð var Modal = function (element, options) {Ð
this.options             = optionsÐ   this.$body               =
$(document.body)Ð   this.$element            = $(element)Ð   this.
$dialog             = this.$element.find('.modal-dialog')Ð   this.
$backdrop           = nullÐ   this.isShown             = nullÐ
this.originalBodyPad     = nullÐ   this.scrollbarWidth      = 0Ð
this.ignoreBackdropClick = falseÐ   if (this.options.remote) {Ð     this.
$elementÐ       .find('.modal-content')Ð       .load(this.options.remote,
$.proxy(function () {Ð         this.$element.trigger('loaded.bs.modal')Ð
        }, this))Ð   }Ð }Ð Modal.VERSION  = '3.3.6'Ð
Modal.TRANSITION_DURATION = 300Ð Modal.BACKDROP_TRANSITION_DURATION = 150Ð
Modal.DEFAULTS = {Ð   backdrop: true,Ð   keyboard: true,Ð   show: trueÐ }Ð
Modal.prototype.toggle = function (_relatedTarget) {Ð   return this.isShown ?
this.hide() : this.show(_relatedTarget)Ð }Ð Modal.prototype.show = function
(_relatedTarget) {Ð   var that = thisÐ   var e    = $.Event('show.bs.modal',
{ relatedTarget: _relatedTarget })Ð   this.$element.trigger(e)Ð   if
(this.isShown || e.isDefaultPrevented()) returnÐ   this.isShown = trueÐ
this.checkScrollbar()Ð   this.setScrollbar()Ð   this.$body.addClass('modal-
open')Ð   this.escape()Ð   this.resize()Ð   this.
$element.on('click.dismiss.bs.modal', '[data-dismiss="modal"]',
$.proxy(this.hide, this))Ð   this.$dialog.on('mousedown.dismiss.bs.modal',
function () {Ð     that.$element.one('mouseup.dismiss.bs.modal', function (e)
{Ð       if ($(e.target).is(that.$element)) that.ignoreBackdropClick = trueÐ
      })Ð   })Ð   this.backdrop(function () {Ð     var transition =
$.support.transition && that.$element.hasClass('fade')Ð     if (!that.
$element.parent().length) {Ð       that.$element.appendTo(that.$body) //
don't move modals dom positionÐ     }Ð     that.$elementÐ       .show()Ð
        .scrollTop(0)Ð     that.adjustDialog()Ð     if (transition) {Ð
that.$element[0].offsetWidth // force reflowÐ     }Ð     that.
$element.addClass('in')Ð     that.enforceFocus()Ð     var e =
$.Event('shown.bs.modal', { relatedTarget: _relatedTarget })Ð     transition ?Ð
        that.$dialog // wait for modal to slide inÐ
          .one('bsTransitionEnd', function () {Ð           that.
$element.trigger('focus').trigger(e)Ð         })Ð
          .emulateTransitionEnd(Modal.TRANSITION_DURATION) :Ð       that.
$element.trigger('focus').trigger(e)Ð   })Ð }Ð Modal.prototype.hide =
function (e) {Ð   if (e) e.preventDefault()Ð   e = $.Event('hide.bs.modal')Ð
    this.$element.trigger(e)Ð   if (!this.isShown || e.isDefaultPrevented())
returnÐ   this.isShown = falseÐ   this.escape()Ð   this.resize()Ð
$(document).off('focusin.bs.modal')Ð   this.$elementÐ     .removeClass('in')Ð
      .off('click.dismiss.bs.modal')Ð
```

```
                                                .off('mouseup.dismiss.bs.modal')Ð
this.$dialog.off('mousedown.dismiss.bs.modal')Ð   $.support.transition &&
this.$element.hasClass('fade') ?Ð     this.$elementÐ
        .one('bsTransitionEnd', $.proxy(this.hideModal, this))Ð
        .emulateTransitionEnd(Modal.TRANSITION_DURATION) :Ð
this.hideModal()Ð }Ð Modal.prototype.enforceFocus = function () {Ð
$(document)Ð     .off('focusin.bs.modal') // guard against infinite focus loopÐ
      .on('focusin.bs.modal', $.proxy(function (e) {Ð       if (this.
$element[0] !== e.target && !this.$element.has(e.target).length) {Ð
this.$element.trigger('focus')Ð       }Ð     }, this))Ð }Ð
Modal.prototype.escape = function () {Ð   if (this.isShown &&
this.options.keyboard) {Ð     this.$element.on('keydown.dismiss.bs.modal',
$.proxy(function (e) {Ð       e.which == 27 && this.hide()Ð     }, this))Ð
    } else if (!this.isShown) {Ð     this.
$element.off('keydown.dismiss.bs.modal')Ð   }Ð }Ð Modal.prototype.resize =
function () {Ð   if (this.isShown) {Ð     $(window).on('resize.bs.modal',
$.proxy(this.handleUpdate, this))Ð   } else {Ð
$(window).off('resize.bs.modal')Ð   }Ð }Ð Modal.prototype.hideModal =
function () {Ð   var that = thisÐ   this.$element.hide()Ð
this.backdrop(function () {Ð     that.$body.removeClass('modal-open')Ð
that.resetAdjustments()Ð     that.resetScrollbar()Ð     that.
$element.trigger('hidden.bs.modal')Ð   })Ð }Ð Modal.prototype.removeBackdrop
= function () {Ð   this.$backdrop && this.$backdrop.remove()Ð   this.
$backdrop = nullÐ }Ð Modal.prototype.backdrop = function (callback) {Ð   var
that = thisÐ   var animate = this.$element.hasClass('fade') ? 'fade' : ''Ð
if (this.isShown && this.options.backdrop) {Ð     var doAnimate =
$.support.transition && animateÐ     this.$backdrop =
$(document.createElement('div'))Ð       .addClass('modal-backdrop ' + animate)Ð
        .appendTo(this.$body)Ð     this.$element.on('click.dismiss.bs.modal',
$.proxy(function (e) {Ð       if (this.ignoreBackdropClick) {Ð
this.ignoreBackdropClick = falseÐ         returnÐ       }Ð       if
(e.target !== e.currentTarget) returnÐ       this.options.backdrop == 'static'Ð
          ? this.$element[0].focus()Ð         : this.hide()Ð     }, this))Ð
      if (doAnimate) this.$backdrop[0].offsetWidth // force reflowÐ     this.
$backdrop.addClass('in')Ð     if (!callback) returnÐ     doAnimate ?Ð
this.$backdropÐ         .one('bsTransitionEnd', callback)Ð
          .emulateTransitionEnd(Modal.BACKDROP_TRANSITION_DURATION) :Ð
callback()Ð   } else if (!this.isShown && this.$backdrop) {Ð     this.
$backdrop.removeClass('in')Ð     var callbackRemove = function () {Ð
that.removeBackdrop()Ð       callback && callback()Ð     }Ð
$.support.transition && this.$element.hasClass('fade') ?Ð       this.$backdropÐ
          .one('bsTransitionEnd', callbackRemove)Ð
          .emulateTransitionEnd(Modal.BACKDROP_TRANSITION_DURATION) :Ð
callbackRemove()Ð   } else if (callback) {Ð     callback()Ð   }Ð }Ð // these
following methods are used to handle overflowing modalsÐ
Modal.prototype.handleUpdate = function () {Ð   this.adjustDialog()Ð }Ð
Modal.prototype.adjustDialog = function () {Ð   var modalIsOverflowing = this.
$element[0].scrollHeight > document.documentElement.clientHeightÐ   this.
$element.css({Ð     paddingLeft:  !this.bodyIsOverflowing &&
modalIsOverflowing ? this.scrollbarWidth : '',Ð     paddingRight:
this.bodyIsOverflowing && !modalIsOverflowing ? this.scrollbarWidth : ''Ð   })Ð
  }Ð Modal.prototype.resetAdjustments = function () {Ð   this.$element.css({Ð
      paddingLeft: '',Ð     paddingRight: ''Ð   })Ð }Ð
Modal.prototype.checkScrollbar = function () {Ð   var fullWindowWidth =
window.innerWidthÐ   if (!fullWindowWidth) { // workaround for missing
window.innerWidth in IE8Ð     var documentElementRect =
document.documentElement.getBoundingClientRect()Ð     fullWindowWidth =
documentElementRect.right - Math.abs(documentElementRect.left)Ð   }Ð
this.bodyIsOverflowing = document.body.clientWidth < fullWindowWidthÐ
this.scrollbarWidth = this.measureScrollbar()Ð
```

```
                                                    }Ð
Modal.prototype.setScrollbar = function () {Ð   var bodyPad = parseInt((this.
$body.css('padding-right') || 0), 10)Ð   this.originalBodyPad =
document.body.style.paddingRight || ''Ð   if (this.bodyIsOverflowing) this.
$body.css('padding-right', bodyPad + this.scrollbarWidth)Ð }Ð
Modal.prototype.resetScrollbar = function () {Ð   this.$body.css('padding-
right', this.originalBodyPad)Ð }Ð Modal.prototype.measureScrollbar = function
() { // thx walshÐ   var scrollDiv = document.createElement('div')Ð
scrollDiv.className = 'modal-scrollbar-measure'Ð   this.
$body.append(scrollDiv)Ð   var scrollbarWidth = scrollDiv.offsetWidth -
scrollDiv.clientWidthÐ   this.$body[0].removeChild(scrollDiv)Ð   return
scrollbarWidthÐ }Ð // MODAL PLUGIN DEFINITIONÐ // =======================Ð
function Plugin(option, _relatedTarget) {Ð   return this.each(function () {Ð
      var $this   = $(this)Ð     var data    = $this.data('bs.modal')Ð
var options = $.extend({}, Modal.DEFAULTS, $this.data(), typeof option ==
'object' && option)Ð     if (!data) $this.data('bs.modal', (data = new
Modal(this, options)))Ð     if (typeof option == 'string') data[option]
(_relatedTarget)Ð     else if (options.show) data.show(_relatedTarget)Ð   })Ð
  }Ð var old = $.fn.modalÐ $.fn.modal             = PluginÐ
$.fn.modal.Constructor = ModalÐ // MODAL NO CONFLICTÐ // =================Ð
$.fn.modal.noConflict = function () {Ð   $.fn.modal = oldÐ   return thisÐ }Ð
  // MODAL DATA-APIÐ // ==============Ð $(document).on('click.bs.modal.data-
api', '[data-toggle="modal"]', function (e) {Ð   var $this   = $(this)Ð   var
href    = $this.attr('href')Ð   var $target = $($this.attr('data-target') ||
(href && href.replace(/.*(?=#[^\s]+$)/, ''))) // strip for ie7Ð   var option
= $target.data('bs.modal') ? 'toggle' : $.extend({ remote: !/#/.test(href) &&
href }, $target.data(), $this.data())Ð   if ($this.is('a')) e.preventDefault()Ð
    $target.one('show.bs.modal', function (showEvent) {Ð     if
(showEvent.isDefaultPrevented()) return // only register focus restorer if
modal will actually get shownÐ     $target.one('hidden.bs.modal', function ()
{Ð       $this.is(':visible') && $this.trigger('focus')Ð     })Ð   })Ð
Plugin.call($target, option, this)Ð })Ð(jQuery);Ø*
========================================================================Ð*
Bootstrap: tooltip.js v3.3.6Ð* http://getbootstrap.com/javascript/#tooltipÐ*
Inspired by the original jQuery.tipsy by Jason FrameÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
======================================================================== */Ð
+function ($) {Ð 'use strict';Ð // TOOLTIP PUBLIC CLASS DEFINITIONÐ //
================================Ð var Tooltip = function (element, options) {Ð
    this.type       = nullÐ   this.options    = nullÐ   this.enabled    = nullÐ
    this.timeout    = nullÐ   this.hoverState = nullÐ   this.$element   = nullÐ
    this.inState    = nullÐ   this.init('tooltip', element, options)Ð }Ð
Tooltip.VERSION  = '3.3.6'Ð Tooltip.TRANSITION_DURATION = 150Ð
Tooltip.DEFAULTS = {Ð   animation: true,Ð   placement: 'top',Ð   selector:
false,Ð   template: '<div class="tooltip" role="tooltip"><div class="tooltip-
arrow"></div><div class="tooltip-inner"></div></div>',Ð   trigger: 'hover
focus',Ð   title: '',Ð   delay: 0,Ð   html: false,Ð   container: false,Ð
viewport: {Ð     selector: 'body',Ð     padding: 0Ð   }Ð }Ð
Tooltip.prototype.init = function (type, element, options) {Ð
this.enabled   = trueÐ   this.type      = typeÐ   this.$element  = $(element)Ð
    this.options   = this.getOptions(options)Ð   this.$viewport =
this.options.viewport && $($.isFunction(this.options.viewport) ?
this.options.viewport.call(this, this.$element) :
(this.options.viewport.selector || this.options.viewport))Ð   this.inState
= { click: false, hover: false, focus: false }Ð   if (this.$element[0]
instanceof document.constructor && !this.options.selector) {Ð     throw new
Error('`selector` option must be specified when initializing ' + this.type +
' on the window.document object!')Ð
```

```
                                        }Ð   var triggers =
this.options.trigger.split(' ')Ð   for (var i = triggers.length; i--;) {Ð
var trigger = triggers[i]Ð     if (trigger == 'click') {Ð       this.
$element.on('click.' + this.type, this.options.selector, $.proxy(this.toggle,
this))Ð     } else if (trigger != 'manual') {Ð       var eventIn  = trigger
== 'hover' ? 'mouseenter' : 'focusin'Ð       var eventOut = trigger ==
'hover' ? 'mouseleave' : 'focusout'Ð       this.$element.on(eventIn  + '.' +
this.type, this.options.selector, $.proxy(this.enter, this))Ð       this.
$element.on(eventOut + '.' + this.type, this.options.selector,
$.proxy(this.leave, this))Ð     }Ð   }Ð   this.options.selector ?Ð
(this._options = $.extend({}, this.options, { trigger: 'manual', selector:
'' })) :Ð     this.fixTitle()Ð }Ð Tooltip.prototype.getDefaults = function ()
{Ð   return Tooltip.DEFAULTSÐ }Ð Tooltip.prototype.getOptions = function
(options) {Ð   options = $.extend({}, this.getDefaults(), this.
$element.data(), options)Ð   if (options.delay && typeof options.delay ==
'number') {Ð     options.delay = {Ð       show: options.delay,Ð       hide:
options.delayÐ     }Ð   }Ð   return optionsÐ }Ð
Tooltip.prototype.getDelegateOptions = function () {Ð   var options  = {}Ð
var defaults = this.getDefaults()Ð   this._options && $.each(this._options,
function (key, value) {Ð     if (defaults[key] != value) options[key] = valueÐ
    })Ð   return optionsÐ }Ð Tooltip.prototype.enter = function (obj) {Ð
var self = obj instanceof this.constructor ?Ð     obj :
$(obj.currentTarget).data('bs.' + this.type)Ð   if (!self) {Ð     self = new
this.constructor(obj.currentTarget, this.getDelegateOptions())Ð
$(obj.currentTarget).data('bs.' + this.type, self)Ð   }Ð   if (obj instanceof
$.Event) {Ð     self.inState[obj.type == 'focusin' ? 'focus' : 'hover'] = trueÐ
    }Ð   if (self.tip().hasClass('in') || self.hoverState == 'in') {Ð
self.hoverState = 'in'Ð     returnÐ   }Ð   clearTimeout(self.timeout)Ð
self.hoverState = 'in'Ð   if (!self.options.delay || !
self.options.delay.show) return self.show()Ð   self.timeout =
setTimeout(function () {Ð     if (self.hoverState == 'in') self.show()Ð   },
self.options.delay.show)Ð }Ð Tooltip.prototype.isInStateTrue = function () {Ð
    for (var key in this.inState) {Ð     if (this.inState[key]) return trueÐ
    }Ð   return falseÐ }Ð Tooltip.prototype.leave = function (obj) {Ð   var
self = obj instanceof this.constructor ?Ð     obj :
$(obj.currentTarget).data('bs.' + this.type)Ð   if (!self) {Ð     self = new
this.constructor(obj.currentTarget, this.getDelegateOptions())Ð
$(obj.currentTarget).data('bs.' + this.type, self)Ð   }Ð   if (obj instanceof
$.Event) {Ð     self.inState[obj.type == 'focusout' ? 'focus' : 'hover'] =
falseÐ   }Ð   if (self.isInStateTrue()) returnÐ   clearTimeout(self.timeout)Ð
    self.hoverState = 'out'Ð   if (!self.options.delay || !
self.options.delay.hide) return self.hide()Ð   self.timeout =
setTimeout(function () {Ð     if (self.hoverState == 'out') self.hide()Ð   },
self.options.delay.hide)Ð }Ð Tooltip.prototype.show = function () {Ð   var e
= $.Event('show.bs.' + this.type)Ð   if (this.hasContent() && this.enabled) {Ð
      this.$element.trigger(e)Ð     var inDom = $.contains(this.
$element[0].ownerDocument.documentElement, this.$element[0])Ð     if
(e.isDefaultPrevented() || !inDom) returnÐ     var that = thisÐ     var $tip
= this.tip()Ð     var tipId = this.getUID(this.type)Ð     this.setContent()Ð
      $tip.attr('id', tipId)Ð     this.$element.attr('aria-describedby',
tipId)Ð     if (this.options.animation) $tip.addClass('fade')Ð     var
placement = typeof this.options.placement == 'function' ?Ð
this.options.placement.call(this, $tip[0], this.$element[0]) :Ð
this.options.placementÐ     var autoToken = /\s?auto?\s?/iÐ     var autoPlace
= autoToken.test(placement)Ð     if (autoPlace) placement =
placement.replace(autoToken, '') || 'top'Ð     $tipÐ       .detach()Ð
        .css({ top: 0, left: 0, display: 'block' })Ð
        .addClass(placement)Ð       .data('bs.' + this.type, this)Ð
this.options.container ? $tip.appendTo(this.options.container) :
$tip.insertAfter(this.$element)Ð
```

```
                                        this.$element.trigger('inserted.bs.' +
this.type)Ð     var pos          = this.getPosition()Ð     var actualWidth  =
$tip[0].offsetWidthÐ     var actualHeight = $tip[0].offsetHeightÐ     if
(autoPlace) {Ð       var orgPlacement = placementÐ       var viewportDim =
this.getPosition(this.$viewport)Ð       placement = placement == 'bottom' &&
pos.bottom + actualHeight > viewportDim.bottom ? 'top'    :Ð
                     placement == 'top'    && pos.top    - actualHeight <
viewportDim.top    ? 'bottom' :Ð                    placement == 'right'  &&
pos.right  + actualWidth  > viewportDim.width  ? 'left'   :Ð
                     placement == 'left'   && pos.left   - actualWidth  <
viewportDim.left   ? 'right'  :Ð                    placementÐ       $tipÐ
          .removeClass(orgPlacement)Ð         .addClass(placement)Ð     }Ð
      var calculatedOffset = this.getCalculatedOffset(placement, pos,
actualWidth, actualHeight)Ð     this.applyPlacement(calculatedOffset,
placement)Ð     var complete = function () {Ð       var prevHoverState =
that.hoverStateÐ       that.$element.trigger('shown.bs.' + that.type)Ð
that.hoverState = nullÐ       if (prevHoverState == 'out') that.leave(that)Ð
      }Ð     $.support.transition && this.$tip.hasClass('fade') ?Ð       $tipÐ
          .one('bsTransitionEnd', complete)Ð
          .emulateTransitionEnd(Tooltip.TRANSITION_DURATION) :Ð
complete()Ð   }Ð }Ð Tooltip.prototype.applyPlacement = function (offset,
placement) {Ð   var $tip   = this.tip()Ð   var width  = $tip[0].offsetWidthÐ
    var height = $tip[0].offsetHeightÐ   // manually read margins because
getBoundingClientRect includes differenceÐ   var marginTop =
parseInt($tip.css('margin-top'), 10)Ð   var marginLeft =
parseInt($tip.css('margin-left'), 10)Ð   // we must check for NaN for ie 8/9Ð
    if (isNaN(marginTop))  marginTop  = 0Ð   if (isNaN(marginLeft))
marginLeft = 0Ð   offset.top  += marginTopÐ   offset.left += marginLeftÐ   //
$.fn.offset doesn't round pixel valuesÐ   // so we use setOffset directly
with our own function B-0Ð   $.offset.setOffset($tip[0], $.extend({Ð
using: function (props) {Ð       $tip.css({Ð         top:
Math.round(props.top),Ð         left: Math.round(props.left)Ð       })Ð     }Ð
    }, offset), 0)Ð   $tip.addClass('in')Ð   // check to see if placing tip
in new offset caused the tip to resize itselfÐ   var actualWidth  =
$tip[0].offsetWidthÐ   var actualHeight = $tip[0].offsetHeightÐ   if
(placement == 'top' && actualHeight != height) {Ð     offset.top = offset.top
+ height - actualHeightÐ   }Ð   var delta =
this.getViewportAdjustedDelta(placement, offset, actualWidth, actualHeight)Ð
    if (delta.left) offset.left += delta.leftÐ   else offset.top += delta.topÐ
    var isVertical          = /top|bottom/.test(placement)Ð   var
arrowDelta          = isVertical ? delta.left * 2 - width + actualWidth :
delta.top * 2 - height + actualHeightÐ   var arrowOffsetPosition =
isVertical ? 'offsetWidth' : 'offsetHeight'Ð   $tip.offset(offset)Ð
this.replaceArrow(arrowDelta, $tip[0][arrowOffsetPosition], isVertical)Ð }Ð
Tooltip.prototype.replaceArrow = function (delta, dimension, isVertical) {Ð
this.arrow()Ð     .css(isVertical ? 'left' : 'top', 50 * (1 - delta /
dimension) + '%')Ð     .css(isVertical ? 'top' : 'left', '')Ð }Ð
Tooltip.prototype.setContent = function () {Ð   var $tip  = this.tip()Ð   var
title = this.getTitle()Ð   $tip.find('.tooltip-inner')[this.options.html ?
'html' : 'text'](title)Ð   $tip.removeClass('fade in top bottom left right')Ð
  }Ð Tooltip.prototype.hide = function (callback) {Ð   var that = thisÐ   var
$tip = $(this.$tip)Ð   var e    = $.Event('hide.bs.' + this.type)Ð   function
complete() {Ð     if (that.hoverState != 'in') $tip.detach()Ð     that.
$elementÐ       .removeAttr('aria-describedby')Ð       .trigger('hidden.bs.'
+ that.type)Ð     callback && callback()Ð   }Ð   this.$element.trigger(e)Ð
if (e.isDefaultPrevented()) returnÐ   $tip.removeClass('in')Ð
$.support.transition && $tip.hasClass('fade') ?Ð     $tipÐ
        .one('bsTransitionEnd', complete)Ð
        .emulateTransitionEnd(Tooltip.TRANSITION_DURATION) :Ð     complete()Ð
    this.hoverState = nullÐ
```

```
                          Ð   return thisÐ }Ð Tooltip.prototype.fixTitle =
function () {Ð   var $e = this.$elementÐ   if ($e.attr('title') || typeof
$e.attr('data-original-title') != 'string') {Ð     $e.attr('data-original-
title', $e.attr('title') || '').attr('title', '')Ð   }Ð }Ð
Tooltip.prototype.hasContent = function () {Ð   return this.getTitle()Ð }Ð
Tooltip.prototype.getPosition = function ($element) {Ð   $element   =
$element || this.$elementÐ   var el     = $element[0]Ð   var isBody =
el.tagName == 'BODY'Ð   var elRect    = el.getBoundingClientRect()Ð   if
(elRect.width == null) {Ð     // width and height are missing in IE8, so
compute them manually; see https://github.com/twbs/bootstrap/issues/14093Ð
      elRect = $.extend({}, elRect, { width: elRect.right - elRect.left,
height: elRect.bottom - elRect.top })Ð   }Ð   var elOffset  = isBody ? { top:
0, left: 0 } : $element.offset()Ð   var scroll    = { scroll: isBody ?
document.documentElement.scrollTop || document.body.scrollTop :
$element.scrollTop() }Ð   var outerDims = isBody ? { width:
$(window).width(), height: $(window).height() } : nullÐ   return $.extend({},
elRect, scroll, outerDims, elOffset)Ð }Ð
Tooltip.prototype.getCalculatedOffset = function (placement, pos,
actualWidth, actualHeight) {Ð   return placement == 'bottom' ? { top: pos.top
+ pos.height,   left: pos.left + pos.width / 2 - actualWidth / 2 } :Ð
           placement == 'top'    ? { top: pos.top - actualHeight, left:
pos.left + pos.width / 2 - actualWidth / 2 } :Ð          placement ==
'left'   ? { top: pos.top + pos.height / 2 - actualHeight / 2, left: pos.left
- actualWidth } :Ð       /* placement == 'right' */ { top: pos.top +
pos.height / 2 - actualHeight / 2, left: pos.left + pos.width }Ð }Ð
Tooltip.prototype.getViewportAdjustedDelta = function (placement, pos,
actualWidth, actualHeight) {Ð   var delta = { top: 0, left: 0 }Ð   if (!this.
$viewport) return deltaÐ   var viewportPadding = this.options.viewport &&
this.options.viewport.padding || 0Ð   var viewportDimensions =
this.getPosition(this.$viewport)Ð   if (/right|left/.test(placement)) {Ð
var topEdgeOffset    = pos.top - viewportPadding - viewportDimensions.scrollÐ
      var bottomEdgeOffset = pos.top + viewportPadding -
viewportDimensions.scroll + actualHeightÐ     if (topEdgeOffset <
viewportDimensions.top) { // top overflowÐ       delta.top =
viewportDimensions.top - topEdgeOffsetÐ     } else if (bottomEdgeOffset >
viewportDimensions.top + viewportDimensions.height) { // bottom overflowÐ
        delta.top = viewportDimensions.top + viewportDimensions.height -
bottomEdgeOffsetÐ     }Ð   } else {Ð     var leftEdgeOffset  = pos.left -
viewportPaddingÐ     var rightEdgeOffset = pos.left + viewportPadding +
actualWidthÐ     if (leftEdgeOffset < viewportDimensions.left) { // left
overflowÐ       delta.left = viewportDimensions.left - leftEdgeOffsetÐ     }
else if (rightEdgeOffset > viewportDimensions.right) { // right overflowÐ
        delta.left = viewportDimensions.left + viewportDimensions.width -
rightEdgeOffsetÐ     }Ð   }Ð   return deltaÐ }Ð Tooltip.prototype.getTitle =
function () {Ð   var titleÐ   var $e = this.$elementÐ   var o  = this.optionsÐ
    title = $e.attr('data-original-title')Ð     || (typeof o.title ==
'function' ? o.title.call($e[0]) :  o.title)Ð   return titleÐ }Ð
Tooltip.prototype.getUID = function (prefix) {Ð   do prefix +=
~~(Math.random() * 1000000)Ð   while (document.getElementById(prefix))Ð
return prefixÐ }Ð Tooltip.prototype.tip = function () {Ð   if (!this.$tip) {Ð
      this.$tip = $(this.options.template)Ð     if (this.$tip.length != 1) {Ð
        throw new Error(this.type + ' `template` option must consist of
exactly 1 top-level element!')Ð     }Ð   }Ð   return this.$tipÐ }Ð
Tooltip.prototype.arrow = function () {Ð   return (this.$arrow = this.$arrow
|| this.tip().find('.tooltip-arrow'))Ð }Ð Tooltip.prototype.enable = function
() {Ð   this.enabled = trueÐ }Ð Tooltip.prototype.disable = function () {Ð
this.enabled = falseÐ }Ð Tooltip.prototype.toggleEnabled = function () {Ð
this.enabled = !this.enabledÐ }Ð Tooltip.prototype.toggle = function (e) {Ð
var self = thisÐ   if (e) {Ð     self = $(e.currentTarget).data('bs.' +
this.type)Ð
```

```
                if (!self) {Ð       self = new
this.constructor(e.currentTarget, this.getDelegateOptions())Ð
$(e.currentTarget).data('bs.' + this.type, self)Ð     }Ð   }Ð   if (e) {Ð
self.inState.click = !self.inState.clickÐ     if (self.isInStateTrue())
self.enter(self)Ð     else self.leave(self)Ð   } else {Ð
self.tip().hasClass('in') ? self.leave(self) : self.enter(self)Ð   }Ð }Ð
Tooltip.prototype.destroy = function () {Ð   var that = thisÐ
clearTimeout(this.timeout)Ð   this.hide(function () {Ð     that.
$element.off('.' + that.type).removeData('bs.' + that.type)Ð     if (that.
$tip) {Ð       that.$tip.detach()Ð     }Ð     that.$tip = nullÐ     that.
$arrow = nullÐ     that.$viewport = nullÐ   })Ð }Ð // TOOLTIP PLUGIN
DEFINITIONÐ // ========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.tooltip')Ð     var options = typeof option == 'object' &&
optionÐ     if (!data && /destroy|hide/.test(option)) returnÐ     if (!data)
$this.data('bs.tooltip', (data = new Tooltip(this, options)))Ð     if (typeof
option == 'string') data[option]()Ð   })Ð }Ð var old = $.fn.tooltipÐ
$.fn.tooltip             = PluginÐ $.fn.tooltip.Constructor = TooltipÐ //
TOOLTIP NO CONFLICTÐ // ===================Ð $.fn.tooltip.noConflict =
function () {Ð   $.fn.tooltip = oldÐ   return thisÐ }}Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: popover.js v3.3.6Ð* http://getbootstrap.com/javascript/#popoversÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
========================================================================= */Ð
+function ($) {Ð 'use strict';Ð // POPOVER PUBLIC CLASS DEFINITIONÐ //
================================Ð var Popover = function (element, options) {Ð
    this.init('popover', element, options)Ð }Ð if (!$.fn.tooltip) throw new
Error('Popover requires tooltip.js')Ð Popover.VERSION  = '3.3.6'Ð
Popover.DEFAULTS = $.extend({}, $.fn.tooltip.Constructor.DEFAULTS, {Ð
placement: 'right',Ð   trigger: 'click',Ð   content: '',Ð   template: '<div
class="popover" role="tooltip"><div class="arrow"></div><h3 class="popover-
title"></h3><div class="popover-content"></div></div>'Ð })Ð // NOTE: POPOVER
EXTENDS tooltip.jsÐ // ================================Ð Popover.prototype =
$.extend({}, $.fn.tooltip.Constructor.prototype)Ð
Popover.prototype.constructor = PopoverÐ Popover.prototype.getDefaults =
function () {Ð   return Popover.DEFAULTSÐ }Ð Popover.prototype.setContent =
function () {Ð   var $tip    = this.tip()Ð   var title   = this.getTitle()Ð
var content = this.getContent()Ð   $tip.find('.popover-title')
[this.options.html ? 'html' : 'text'](title)Ð   $tip.find('.popover-
content').children().detach().end()[ // we use append for html objects to
maintain js eventsÐ     this.options.html ? (typeof content == 'string' ?
'html' : 'append') : 'text'Ð   ](content)Ð   $tip.removeClass('fade top
bottom left right in')Ð   // IE8 doesn't accept hiding via the `:empty`
pseudo selector, we have to doÐ   // this manually by checking the contents.Ð
    if (!$tip.find('.popover-title').html()) $tip.find('.popover-
title').hide()Ð }Ð Popover.prototype.hasContent = function () {Ð   return
this.getTitle() || this.getContent()Ð }Ð Popover.prototype.getContent =
function () {Ð   var $e = this.$elementÐ   var o  = this.optionsÐ   return
$e.attr('data-content')Ð     || (typeof o.content == 'function' ?Ð
o.content.call($e[0]) :Ð           o.content)Ð }Ð Popover.prototype.arrow =
function () {Ð   return (this.$arrow = this.$arrow ||
this.tip().find('.arrow'))Ð }Ð // POPOVER PLUGIN DEFINITIONÐ //
========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.popover')Ð     var options = typeof option == 'object' &&
optionÐ     if (!data && /destroy|hide/.test(option)) returnÐ     if (!data)
$this.data('bs.popover', (data = new Popover(this, options)))Ð     if (typeof
option == 'string') data[option]()Ð
```

```
                                        })Ð }Ð var old = $.fn.popoverÐ
$.fn.popover             = PluginÐ $.fn.popover.Constructor = PopoverÐ //
POPOVER NO CONFLICTÐ // ===================Ð $.fn.popover.noConflict =
function () {Ð   $.fn.popover = oldÐ   return thisÐ }Ð(jQuery);Ð*
========================================================================Ð*
Bootstrap: scrollspy.js v3.3.6Ð* http://getbootstrap.com/javascript/#scrollspyÐ
 * ========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
======================================================================== */Ð
+function ($) {Ð 'use strict';Ð // SCROLLSPY CLASS DEFINITIONÐ //
==========================Ð function ScrollSpy(element, options) {Ð   this.
$body          = $(document.body)Ð   this.$scrollElement =
$(element).is(document.body) ? $(window) : $(element)Ð   this.options
= $.extend({}, ScrollSpy.DEFAULTS, options)Ð   this.selector       =
(this.options.target || '') + ' .nav li > a'Ð   this.offsets        = []Ð
this.targets        = []Ð   this.activeTarget   = nullÐ   this.scrollHeight
= 0Ð   this.$scrollElement.on('scroll.bs.scrollspy', $.proxy(this.process,
this))Ð   this.refresh()Ð   this.process()Ð }Ð ScrollSpy.VERSION  = '3.3.6'Ð
ScrollSpy.DEFAULTS = {Ð   offset: 10Ð }Ð ScrollSpy.prototype.getScrollHeight
= function () {Ð   return this.$scrollElement[0].scrollHeight ||
Math.max(this.$body[0].scrollHeight, document.documentElement.scrollHeight)Ð }Ð
  ScrollSpy.prototype.refresh = function () {Ð   var that          = thisÐ
var offsetMethod  = 'offset'Ð   var offsetBase    = 0Ð   this.offsets      =
[]Ð   this.targets      = []Ð   this.scrollHeight = this.getScrollHeight()Ð
if (!$.isWindow(this.$scrollElement[0])) {Ð     offsetMethod = 'position'Ð
      offsetBase   = this.$scrollElement.scrollTop()Ð   }Ð   this.$bodyÐ
      .find(this.selector)Ð     .map(function () {Ð       var $el   = $(this)Ð
        var href  = $el.data('target') || $el.attr('href')Ð       var $href
= /^#./.test(href) && $(href)Ð       return ($hrefÐ         && $href.lengthÐ
          && $href.is(':visible')Ð         && [[$href[offsetMethod]().top +
offsetBase, href]]) || nullÐ     })Ð     .sort(function (a, b) { return a[0]
- b[0] })Ð     .each(function () {Ð       that.offsets.push(this[0])Ð
that.targets.push(this[1])Ð     })Ð }Ð ScrollSpy.prototype.process = function
() {Ð   var scrollTop    = this.$scrollElement.scrollTop() +
this.options.offsetÐ   var scrollHeight = this.getScrollHeight()Ð   var
maxScroll    = this.options.offset + scrollHeight - this.
$scrollElement.height()Ð   var offsets      = this.offsetsÐ   var
targets      = this.targetsÐ   var activeTarget = this.activeTargetÐ   var iÐ
    if (this.scrollHeight != scrollHeight) {Ð     this.refresh()Ð   }Ð   if
(scrollTop >= maxScroll) {Ð     return activeTarget != (i =
targets[targets.length - 1]) && this.activate(i)Ð   }Ð   if (activeTarget &&
scrollTop < offsets[0]) {Ð     this.activeTarget = nullÐ     return
this.clear()Ð   }Ð   for (i = offsets.length; i--;) {Ð     activeTarget !=
targets[i]Ð       && scrollTop >= offsets[i]Ð       && (offsets[i + 1] ===
undefined || scrollTop < offsets[i + 1])Ð       && this.activate(targets[i])Ð
    }Ð }Ð ScrollSpy.prototype.activate = function (target) {Ð
this.activeTarget = targetÐ   this.clear()Ð   var selector = this.selector +Ð
      '[data-target="' + target + '"],' +Ð     this.selector + '[href="' +
target + '"]'Ð   var active = $(selector)Ð     .parents('li')Ð
      .addClass('active')Ð   if (active.parent('.dropdown-menu').length) {Ð
      active = activeÐ       .closest('li.dropdown')Ð
        .addClass('active')Ð   }Ð   active.trigger('activate.bs.scrollspy')Ð }Ð
  ScrollSpy.prototype.clear = function () {Ð   $(this.selector)Ð
      .parentsUntil(this.options.target, '.active')Ð
      .removeClass('active')Ð }Ð // SCROLLSPY PLUGIN DEFINITIONÐ //
===========================Ð function Plugin(option) {Ð   return
this.each(function () {Ð     var $this   = $(this)Ð     var data    =
$this.data('bs.scrollspy')Ð     var options = typeof option == 'object' &&
optionÐ
```

```
      Ð     if (!data) $this.data('bs.scrollspy', (data = new ScrollSpy(this,
options)))Ð     if (typeof option == 'string') data[option]()Ð   })Ð }Ð var
old = $.fn.scrollspyÐ $.fn.scrollspy             = PluginÐ
$.fn.scrollspy.Constructor = ScrollSpyÐ // SCROLLSPY NO CONFLICTÐ //
=====================Ð $.fn.scrollspy.noConflict = function () {Ð
$.fn.scrollspy = oldÐ   return thisÐ }Ð // SCROLLSPY DATA-APIÐ //
===================Ð $(window).on('load.bs.scrollspy.data-api', function () {Ð
    $('[data-spy="scroll"]').each(function () {Ð     var $spy = $(this)Ð
Plugin.call($spy, $spy.data())Ð   })Ð })Ð }(jQuery);Ð*
========================================================================Ð*
Bootstrap: tab.js v3.3.6Ð* http://getbootstrap.com/javascript/#tabsÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
========================================================================= */Ð
+function ($) {Ð 'use strict';Ð // TAB CLASS DEFINITIONÐ //
====================Ð var Tab = function (element) {Ð   // jscs:disable
requireDollarBeforejQueryAssignmentÐ   this.element = $(element)Ð   //
jscs:enable requireDollarBeforejQueryAssignmentÐ }Ð Tab.VERSION = '3.3.6'Ð
Tab.TRANSITION_DURATION = 150Ð Tab.prototype.show = function () {Ð   var
$this    = this.elementÐ   var $ul      = $this.closest('ul:not(.dropdown-
menu)')Ð   var selector = $this.data('target')Ð   if (!selector) {Ð
selector = $this.attr('href')Ð     selector = selector &&
selector.replace(/.*(?=#[^\s]*$)/, '') // strip for ie7Ð   }Ð   if
($this.parent('li').hasClass('active')) returnÐ   var $previous =
$ul.find('.active:last a')Ð   var hideEvent = $.Event('hide.bs.tab', {Ð
relatedTarget: $this[0]Ð   })Ð   var showEvent = $.Event('show.bs.tab', {Ð
      relatedTarget: $previous[0]Ð   })Ð   $previous.trigger(hideEvent)Ð
$this.trigger(showEvent)Ð   if (showEvent.isDefaultPrevented() ||
hideEvent.isDefaultPrevented()) returnÐ   var $target = $(selector)Ð
this.activate($this.closest('li'), $ul)Ð   this.activate($target,
$target.parent(), function () {Ð     $previous.trigger({Ð       type:
'hidden.bs.tab',Ð       relatedTarget: $this[0]Ð     })Ð     $this.trigger({Ð
        type: 'shown.bs.tab',Ð       relatedTarget: $previous[0]Ð     })Ð   })Ð
  }Ð Tab.prototype.activate = function (element, container, callback) {Ð
var $active    = container.find('> .active')Ð   var transition = callbackÐ
      && $.support.transitionÐ     && ($active.length &&
$active.hasClass('fade') || !!container.find('> .fade').length)Ð   function
next() {Ð     $activeÐ       .removeClass('active')Ð       .find('> .dropdown-
menu > .active')Ð         .removeClass('active')Ð       .end()Ð
        .find('[data-toggle="tab"]')Ð         .attr('aria-expanded', false)Ð
      elementÐ       .addClass('active')Ð       .find('[data-toggle="tab"]')Ð
          .attr('aria-expanded', true)Ð     if (transition) {Ð
element[0].offsetWidth // reflow for transitionÐ       element.addClass('in')Ð
      } else {Ð       element.removeClass('fade')Ð     }Ð     if
(element.parent('.dropdown-menu').length) {Ð       elementÐ
          .closest('li.dropdown')Ð           .addClass('active')Ð
          .end()Ð         .find('[data-toggle="tab"]')Ð           .attr('aria-
expanded', true)Ð     }Ð     callback && callback()Ð   }Ð   $active.length &&
transition ?Ð     $activeÐ       .one('bsTransitionEnd', next)Ð
        .emulateTransitionEnd(Tab.TRANSITION_DURATION) :Ð     next()Ð
$active.removeClass('in')Ð }Ð // TAB PLUGIN DEFINITIONÐ //
=====================Ð function Plugin(option) {Ð   return this.each(function
() {Ð     var $this = $(this)Ð     var data  = $this.data('bs.tab')Ð     if (!
data) $this.data('bs.tab', (data = new Tab(this)))Ð     if (typeof option ==
'string') data[option]()Ð   })Ð }Ð var old = $.fn.tabÐ $.fn.tab             =
PluginÐ $.fn.tab.Constructor = TabÐ // TAB NO CONFLICTÐ // ===============Ð
$.fn.tab.noConflict = function () {Ð   $.fn.tab = oldÐ   return thisÐ }Ð //
TAB DATA-APIÐ // ============Ð var clickHandler = function (e) {Ð
e.preventDefault()Ð
```

```
                        Plugin.call($(this), 'show')Ð }Ð $(document)Ð
    .on('click.bs.tab.data-api', '[data-toggle="tab"]', clickHandler)Ð
    .on('click.bs.tab.data-api', '[data-toggle="pill"]', clickHandler)Ð
(jQuery);Ð*
========================================================================Ð*
Bootstrap: affix.js v3.3.6Ð* http://getbootstrap.com/javascript/#affixÐ*
========================================================================Ð*
Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/
twbs/bootstrap/blob/master/LICENSE)Ð*
======================================================================== */Ð
+function ($) {Ð 'use strict';Ð // AFFIX CLASS DEFINITIONÐ //
======================Ð var Affix = function (element, options) {Ð
this.options = $.extend({}, Affix.DEFAULTS, options)Ð   this.$target =
$(this.options.target)Ð     .on('scroll.bs.affix.data-api',
$.proxy(this.checkPosition, this))Ð     .on('click.bs.affix.data-api',
$.proxy(this.checkPositionWithEventLoop, this))Ð   this.$element     =
$(element)Ð   this.affixed      = nullÐ   this.unpin        = nullÐ
this.pinnedOffset = nullÐ   this.checkPosition()Ð }Ð Affix.VERSION  = '3.3.6'Ð
  Affix.RESET    = 'affix affix-top affix-bottom'Ð Affix.DEFAULTS = {Ð
offset: 0,Ð   target: windowÐ }Ð Affix.prototype.getState = function
(scrollHeight, height, offsetTop, offsetBottom) {Ð   var scrollTop    = this.
$target.scrollTop()Ð   var position     = this.$element.offset()Ð   var
targetHeight = this.$target.height()Ð   if (offsetTop != null && this.affixed
== 'top') return scrollTop < offsetTop ? 'top' : falseÐ   if (this.affixed ==
'bottom') {Ð     if (offsetTop != null) return (scrollTop + this.unpin <=
position.top) ? false : 'bottom'Ð     return (scrollTop + targetHeight <=
scrollHeight - offsetBottom) ? false : 'bottom'Ð   }Ð   var initializing   =
this.affixed == nullÐ   var colliderTop    = initializing ? scrollTop :
position.topÐ   var colliderHeight = initializing ? targetHeight : heightÐ
if (offsetTop != null && scrollTop <= offsetTop) return 'top'Ð   if
(offsetBottom != null && (colliderTop + colliderHeight >= scrollHeight -
offsetBottom)) return 'bottom'Ð   return falseÐ }Ð
Affix.prototype.getPinnedOffset = function () {Ð   if (this.pinnedOffset)
return this.pinnedOffsetÐ   this.
$element.removeClass(Affix.RESET).addClass('affix')Ð   var scrollTop = this.
$target.scrollTop()Ð   var position  = this.$element.offset()Ð   return
(this.pinnedOffset = position.top - scrollTop)Ð }Ð
Affix.prototype.checkPositionWithEventLoop = function () {Ð
setTimeout($.proxy(this.checkPosition, this), 1)Ð }Ð
Affix.prototype.checkPosition = function () {Ð   if (!this.
$element.is(':visible')) returnÐ   var height       = this.$element.height()Ð
    var offset       = this.options.offsetÐ   var offsetTop    = offset.topÐ
    var offsetBottom = offset.bottomÐ   var scrollHeight =
Math.max($(document).height(), $(document.body).height())Ð   if (typeof
offset != 'object')         offsetBottom = offsetTop = offsetÐ   if (typeof
offsetTop == 'function')    offsetTop    = offset.top(this.$element)Ð   if
(typeof offsetBottom == 'function') offsetBottom = offset.bottom(this.
$element)Ð   var affix = this.getState(scrollHeight, height, offsetTop,
offsetBottom)Ð   if (this.affixed != affix) {Ð     if (this.unpin != null)
this.$element.css('top', '')Ð     var affixType = 'affix' + (affix ? '-' +
affix : '')Ð     var e         = $.Event(affixType + '.bs.affix')Ð     this.
$element.trigger(e)Ð     if (e.isDefaultPrevented()) returnÐ     this.affixed
= affixÐ     this.unpin = affix == 'bottom' ? this.getPinnedOffset() : nullÐ
      this.$elementÐ       .removeClass(Affix.RESET)Ð
        .addClass(affixType)Ð       .trigger(affixType.replace('affix',
'affixed') + '.bs.affix')Ð   }Ð   if (affix == 'bottom') {Ð     this.
$element.offset({Ð       top: scrollHeight - height - offsetBottomÐ     })Ð
    }Ð }Ð // AFFIX PLUGIN DEFINITIONÐ // ======================Ð function
Plugin(option) {Ð   return this.each(function () {Ð     var $this   = $(this)Ð
      var data    = $this.data('bs.affix')Ð
```

```
                                                    var options = typeof option
== 'object' && optionÐ     if (!data) $this.data('bs.affix', (data = new
Affix(this, options)))Ð     if (typeof option == 'string') data[option]()Ð
    })Ð }Ð var old = $.fn.affixÐ $.fn.affix             = PluginÐ
$.fn.affix.Constructor = AffixÐ // AFFIX NO CONFLICTÐ // =================Ð
$.fn.affix.noConflict = function () {Ð   $.fn.affix = oldÐ   return thisÐ }Ð
  // AFFIX DATA-APIÐ // ==============Ð $(window).on('load', function () {Ð
$('[data-spy="affix"]').each(function () {Ð     var $spy = $(this)Ð     var
data = $spy.data()Ð     data.offset = data.offset || {}Ð     if
(data.offsetBottom != null) data.offset.bottom = data.offsetBottomÐ     if
(data.offsetTop    != null) data.offset.top    = data.offsetTopÐ
Plugin.call($spy, data)Ð   })Ð })Ð }(jQuery);Ð
```

public\assets\js\customize.js

```
$(document).ready(function() {    const customizeOptions = $('#customize-
options');    const selectedElementInfo = $('#selected-element-info');    let
selectedElement = null;                          const customizableOptions =
[        { name: 'backgroundColor', label: 'Background Color', type:
'color' },        { name: 'color', label: 'Text Color', type: 'color' },
        { name: 'fontFamily', label: 'Font Family', type: 'select', options:
['Arial', 'Helvetica', 'Times New Roman', 'Courier'] },        { name:
'fontSize', label: 'Font Size', type: 'range', min: 12, max: 24, step: 1 },
        { name: 'padding', label: 'Padding', type: 'text' },        { name:
'margin', label: 'Margin', type: 'text' }    ];          // Listen for
messages from the iframe    window.addEventListener('message',
function(event) {    console.log('Received message:', event.data);  // Add
this line for debugging    if (event.data.type === 'elementClicked') {
selectedElement = event.data;        updateSelectedElementInfo();
populateCustomizationOptions();    } else if (event.data.type ===
'previewLoaded') {        console.log('Preview loaded');    }});
function updateSelectedElementInfo() {            console.log('Updating
selected element info:', selectedElement);        selectedElementInfo.html(`
            <p><strong>Selected Element:</strong> ${selectedElement.selector}
</p>            <p><strong>Element Type:</strong>
${selectedElement.elementType}</p>        `);    }         function
populateCustomizationOptions() {          console.log('Populating options
for:', selectedElement);                   customizeOptions.empty();
customizableOptions.forEach(option => {            let inputHtml;
let currentValue = selectedElement.styles[option.name] || '';
            if (option.type === 'color') {                inputHtml = `<input
type="color" id="${option.name}" name="${option.name}"
value="${currentValue}">`;            } else if (option.type === 'select') {
                inputHtml = `<select id="${option.name}"
name="${option.name}">                    ${option.options.map(opt =>
`<option value="${opt}" ${currentValue === opt ? 'selected' : ''}>${opt}</
option>`).join('')}                </select>`;            } else if
(option.type === 'range') {                inputHtml = `<input type="range"
id="${option.name}" name="${option.name}" min="${option.min}"
max="${option.max}" step="${option.step}" value="${currentValue ||
option.min}">                             <span id="${option.name}-
value">${currentValue || option.min}</span>`;            } else {
                inputHtml = `<input type="text" id="${option.name}"
name="${option.name}" value="${currentValue}">`;            }
            customizeOptions.append(`                <div class="form-group">
                    <label for="${option.name}">${option.label}</label>
                    ${inputHtml}                </div>            `);
        });                    attachOptionChangeListeners();    }
function attachOptionChangeListeners() {        customizeOptions.find('input,
select').on('change', function() {            const property =
$(this).attr('name');            const value = $(this).val();
updateIframeStyle(selectedElement.selector, property, value);
            // Update the range value display if it's a range input
            if ($(this).attr('type') === 'range') {
$(`#${property}-value`).text(value);            }        });    }
function updateIframeStyle(selector, property, value) {        const iframe =
document.getElementById('live-preview');
iframe.contentWindow.postMessage({            type: 'updateStyle',
selector: selector,            property: property,            value: value
        }, '*');    }         // Handle save changes    $('#save-
changes').on('click', function() {        const iframe =
document.getElementById('live-preview');
iframe.contentWindow.postMessage({            type: 'saveStyles'        },
'*');
```

```
});});
```

public\assets\js\demo\chartjs-demo.js

```
$(function () {Đ   var lineData = {Đ       labels: ["January", "February",
"March", "April", "May", "June", "July"],Đ       datasets: [Đ           {Đ
                label: "Example dataset",Đ               fillColor:
"rgba(220,220,220,0.5)",Đ               strokeColor: "rgba(220,220,220,1)",Đ
                pointColor: "rgba(220,220,220,1)",Đ
pointStrokeColor: "#fff",Đ               pointHighlightFill: "#fff",Đ
                pointHighlightStroke: "rgba(220,220,220,1)",Đ
data: [65, 59, 80, 81, 56, 55, 40]Đ           },Đ           {Đ
label: "Example dataset",Đ               fillColor: "rgba(26,179,148,0.5)",Đ
                strokeColor: "rgba(26,179,148,0.7)",Đ
pointColor: "rgba(26,179,148,1)",Đ               pointStrokeColor: "#fff",Đ
                pointHighlightFill: "#fff",Đ
pointHighlightStroke: "rgba(26,179,148,1)",Đ               data: [28, 48, 40,
19, 86, 27, 90]Đ           }Đ       ]Đ   };Đ   var lineOptions = {Đ
scaleShowGridLines: true,Đ       scaleGridLineColor: "rgba(0,0,0,.05)",Đ
        scaleGridLineWidth: 1,Đ       bezierCurve: true,Đ
bezierCurveTension: 0.4,Đ       pointDot: true,Đ       pointDotRadius: 4,Đ
        pointDotStrokeWidth: 1,Đ       pointHitDetectionRadius: 20,Đ
datasetStroke: true,Đ       datasetStrokeWidth: 2,Đ       datasetFill: true,Đ
        responsive: true,Đ   };Đ   var ctx =
document.getElementById("lineChart").getContext("2d");Đ   var myNewChart =
new Chart(ctx).Line(lineData, lineOptions);Đ   var barData = {Đ       labels:
["January", "February", "March", "April", "May", "June", "July"],Đ
datasets: [Đ           {Đ               label: "My First dataset",Đ
                fillColor: "rgba(220,220,220,0.5)",Đ
strokeColor: "rgba(220,220,220,0.8)",Đ               highlightFill:
"rgba(220,220,220,0.75)",Đ               highlightStroke:
"rgba(220,220,220,1)",Đ               data: [65, 59, 80, 81, 56, 55, 40]Đ
            },Đ           {Đ               label: "My Second dataset",Đ
                fillColor: "rgba(26,179,148,0.5)",Đ
strokeColor: "rgba(26,179,148,0.8)",Đ               highlightFill:
"rgba(26,179,148,0.75)",Đ               highlightStroke: "rgba(26,179,148,1)",Đ
                data: [28, 48, 40, 19, 86, 27, 90]Đ           }Đ       ]Đ   };Đ
    var barOptions = {Đ       scaleBeginAtZero: true,Đ
scaleShowGridLines: true,Đ       scaleGridLineColor: "rgba(0,0,0,.05)",Đ
        scaleGridLineWidth: 1,Đ       barShowStroke: true,Đ
barStrokeWidth: 2,Đ       barValueSpacing: 5,Đ       barDatasetSpacing: 1,Đ
        responsive: trueĐ   }Đ   var ctx =
document.getElementById("barChart").getContext("2d");Đ   var myNewChart = new
Chart(ctx).Bar(barData, barOptions);Đ   var polarData = [Đ       {Đ
value: 300,Đ           color: "#a3e1d4",Đ           highlight: "#1ab394",Đ
            label: "App"Đ       },Đ       {Đ           value: 140,Đ
color: "#dedede",Đ           highlight: "#1ab394",Đ           label:
"Software"Đ       },Đ       {Đ           value: 200,Đ           color:
"#b5b8cf",Đ           highlight: "#1ab394",Đ           label: "Laptop"Đ
        }Đ   ];Đ   var polarOptions = {Đ       scaleShowLabelBackdrop: true,Đ
        scaleBackdropColor: "rgba(255,255,255,0.75)",Đ
scaleBeginAtZero: true,Đ       scaleBackdropPaddingY: 1,Đ
scaleBackdropPaddingX: 1,Đ       scaleShowLine: true,Đ
segmentShowStroke: true,Đ       segmentStrokeColor: "#fff",Đ
segmentStrokeWidth: 2,Đ       animationSteps: 100,Đ       animationEasing:
"easeOutBounce",Đ       animateRotate: true,Đ       animateScale: false,Đ
        responsive: true,Đ   };Đ   var ctx =
document.getElementById("polarChart").getContext("2d");Đ   var myNewChart =
new Chart(ctx).PolarArea(polarData, polarOptions);Đ   var doughnutData = [Đ
        {Đ           value: 300,Đ           color: "#a3e1d4",Đ
highlight: "#1ab394",Đ           label: "App"Đ       },Đ       {Đ
value: 50,Đ           color: "#dedede",Đ           highlight: "#1ab394",Đ
            label: "Software"Đ
```

```
                                        },Ð       {Ð           value: 100,Ð
            color: "#b5b8cf",Ð           highlight: "#1ab394",Ð
label: "Laptop"Ð       }Ð   ];Ð   var doughnutOptions = {Ð
segmentShowStroke: true,Ð       segmentStrokeColor: "#fff",Ð
segmentStrokeWidth: 2,Ð       percentageInnerCutout: 45, // This is 0 for Pie
chartsÐ       animationSteps: 100,Ð       animationEasing: "easeOutBounce",Ð
        animateRotate: true,Ð       animateScale: false,Ð       responsive:
true,Ð   };Ð   var ctx =
document.getElementById("doughnutChart").getContext("2d");Ð   var myNewChart
= new Chart(ctx).Doughnut(doughnutData, doughnutOptions);Ð   var radarData = {Ð
        labels: ["Eating", "Drinking", "Sleeping", "Designing", "Coding",
"Cycling", "Running"],Ð       datasets: [Ð           {Ð               label:
"My First dataset",Ð               fillColor: "rgba(220,220,220,0.2)",Ð
                strokeColor: "rgba(220,220,220,1)",Ð
pointColor: "rgba(220,220,220,1)",Ð               pointStrokeColor: "#fff",Ð
                pointHighlightFill: "#fff",Ð
pointHighlightStroke: "rgba(220,220,220,1)",Ð               data: [65, 59,
90, 81, 56, 55, 40]Ð           },Ð           {Ð               label: "My
Second dataset",Ð               fillColor: "rgba(26,179,148,0.2)",Ð
                strokeColor: "rgba(26,179,148,1)",Ð               pointColor:
"rgba(26,179,148,1)",Ð               pointStrokeColor: "#fff",Ð
pointHighlightFill: "#fff",Ð               pointHighlightStroke:
"rgba(151,187,205,1)",Ð               data: [28, 48, 40, 19, 96, 27, 100]Ð
            }Ð       ]Ð   };Ð   var radarOptions = {Ð       scaleShowLine:
true,Ð       angleShowLineOut: true,Ð       scaleShowLabels: false,Ð
scaleBeginAtZero: true,Ð       angleLineColor: "rgba(0,0,0,.1)",Ð
angleLineWidth: 1,Ð       pointLabelFontFamily: "'Arial'",Ð
pointLabelFontStyle: "normal",Ð       pointLabelFontSize: 10,Ð
pointLabelFontColor: "#666",Ð       pointDot: true,Ð       pointDotRadius: 3,Ð
        pointDotStrokeWidth: 1,Ð       pointHitDetectionRadius: 20,Ð
datasetStroke: true,Ð       datasetStrokeWidth: 2,Ð       datasetFill: true,Ð
        responsive: true,Ð   }Ð   var ctx =
document.getElementById("radarChart").getContext("2d");Ð   var myNewChart =
new Chart(ctx).Radar(radarData, radarOptions);Ð});
```

public\assets\js\demo\dashboard-demo.js

```
$(function() {Ð   Morris.Area({Ð       element: 'morris-area-chart',Ð
data: [{Ð           period: '2010 Q1',Ð           iphone: 2666,Ð
ipad: null,Ð           itouch: 2647Ð       }, {Ð           period: '2010 Q2',Ð
            iphone: 2778,Ð           ipad: 2294,Ð           itouch: 2441Ð
        }, {Ð           period: '2010 Q3',Ð           iphone: 4912,Ð
            ipad: 1969,Ð           itouch: 2501Ð       }, {Ð
period: '2010 Q4',Ð           iphone: 3767,Ð           ipad: 3597,Ð
itouch: 5689Ð       }, {Ð           period: '2011 Q1',Ð           iphone:
6810,Ð           ipad: 1914,Ð           itouch: 2293Ð       }, {Ð
period: '2011 Q2',Ð           iphone: 5670,Ð           ipad: 4293,Ð
itouch: 1881Ð       }, {Ð           period: '2011 Q3',Ð           iphone:
4820,Ð           ipad: 3795,Ð           itouch: 1588Ð       }, {Ð
period: '2011 Q4',Ð           iphone: 15073,Ð           ipad: 5967,Ð
            itouch: 5175Ð       }, {Ð           period: '2012 Q1',Ð
iphone: 10687,Ð           ipad: 4460,Ð           itouch: 2028Ð       }, {Ð
            period: '2012 Q2',Ð           iphone: 8432,Ð           ipad: 5713,Ð
            itouch: 1791Ð       }],Ð       xkey: 'period',Ð       ykeys:
['iphone', 'ipad', 'itouch'],Ð       labels: ['iPhone', 'iPad', 'iPod Touch'],Ð
        pointSize: 2,Ð       hideHover: 'auto',Ð       resize: trueÐ   });Ð
Morris.Donut({Ð       element: 'morris-donut-chart',Ð       data: [{Ð
            label: "Download Sales",Ð           value: 12Ð       }, {Ð
            label: "In-Store Sales",Ð           value: 30Ð       }, {Ð
            label: "Mail-Order Sales",Ð           value: 20Ð       }],Ð
resize: trueÐ   });Ð   Morris.Bar({Ð       element: 'morris-bar-chart',Ð
        data: [{Ð           y: '2006',Ð           a: 100,Ð           b: 90Ð
        }, {Ð           y: '2007',Ð           a: 75,Ð           b: 65Ð
        }, {Ð           y: '2008',Ð           a: 50,Ð           b: 40Ð
        }, {Ð           y: '2009',Ð           a: 75,Ð           b: 65Ð
        }, {Ð           y: '2010',Ð           a: 50,Ð           b: 40Ð
        }, {Ð           y: '2011',Ð           a: 75,Ð           b: 65Ð
        }, {Ð           y: '2012',Ð           a: 100,Ð           b: 90Ð
        }],Ð       xkey: 'y',Ð       ykeys: ['a', 'b'],Ð       labels:
['Series A', 'Series B'],Ð       hideHover: 'auto',Ð       resize: trueÐ   });Ð
});Ð
```

public\assets\js\demo\flot-demo2.js

```
//Flot Pie Chart DevicesÐ$(function() {Ð   var data = [{Ð       label:
"iPhone",Ð       data: 21,Ð       color: "#d3d3d3",Ð   }, {Ð       label:
"Samsung",Ð       data: 3,Ð       color: "#bababa",Ð   }, {Ð       label:
"Windows",Ð       data: 15,Ð       color: "#79d2c0",Ð   }, {Ð       label:
"Blackberry",Ð       data: 52,Ð       color: "#1ab394",Ð   }];Ð   var plotObj
= $.plot($("#flot-pie-chart-devices"), data, {Ð       series: {Ð
pie: {Ð                show: trueÐ           }Ð       },Ð       grid: {Ð
            hoverable: trueÐ       },Ð       tooltip: true,Ð
tooltipOpts: {Ð           content: "%p.0%, %s", // show percentages, rounding
to 2 decimal placesÐ           shifts: {Ð                x: 20,Ð
y: 0Ð           },Ð           defaultTheme: falseÐ       }Ð   });Ð});Ð/Flot
Pie Chart BrowsersÐ$(function() {Ð   var data = [{Ð       label: "Chrome",Ð
        data: 21,Ð       color: "#d3d3d3",Ð   }, {Ð       label: "Firefox",Ð
        data: 3,Ð       color: "#bababa",Ð   }, {Ð       label: "IE",Ð
data: 15,Ð       color: "#79d2c0",Ð   }, {Ð       label: "Safari",Ð
data: 52,Ð       color: "#1ab394",Ð   }];Ð   var plotObj = $.plot($("#flot-
pie-chart-browsers"), data, {Ð       series: {Ð           pie: {Ð
                show: trueÐ           }Ð       },Ð       grid: {Ð
hoverable: trueÐ       },Ð       tooltip: true,Ð       tooltipOpts: {Ð
            content: "%p.0%, %s", // show percentages, rounding to 2 decimal
placesÐ           shifts: {Ð                x: 20,Ð                y: 0Ð
            },Ð           defaultTheme: falseÐ       }Ð   });Ð});Ð/Flot Pie
Chart SourcesÐ$(function() {Ð   var data = [{Ð       label: "Client 1",Ð
data: 21,Ð       color: "#d3d3d3",Ð   }, {Ð       label: "Client 2",Ð
data: 3,Ð       color: "#bababa",Ð   }, {Ð       label: "Client 3",Ð
data: 15,Ð       color: "#79d2c0",Ð   }, {Ð       label: "Client 4",Ð
data: 52,Ð       color: "#1ab394",Ð   }];Ð   var plotObj = $.plot($("#flot-
pie-chart-sources"), data, {Ð       series: {Ð           pie: {Ð
                show: trueÐ           }Ð       },Ð       grid: {Ð
hoverable: trueÐ       },Ð       tooltip: true,Ð       tooltipOpts: {Ð
            content: "%p.0%, %s", // show percentages, rounding to 2 decimal
placesÐ           shifts: {Ð                x: 20,Ð                y: 0Ð
            },Ð           defaultTheme: falseÐ       }Ð   });Ð});Ð/Flot Pie
Chart CarriersÐ$(function() {Ð   var data = [{Ð       label: "Carriers 1",Ð
        data: 21,Ð       color: "#d3d3d3",Ð   }, {Ð       label: "Carriers 2",Ð
        data: 3,Ð       color: "#bababa",Ð   }, {Ð       label: "Carriers 3",Ð
        data: 15,Ð       color: "#79d2c0",Ð   }, {Ð       label: "Carriers 4",Ð
        data: 52,Ð       color: "#1ab394",Ð   }];Ð   var plotObj =
$.plot($("#flot-pie-chart-carriers"), data, {Ð       series: {Ð
pie: {Ð                show: trueÐ           }Ð       },Ð       grid: {Ð
            hoverable: trueÐ       },Ð       tooltip: true,Ð
tooltipOpts: {Ð           content: "%p.0%, %s", // show percentages, rounding
to 2 decimal placesÐ           shifts: {Ð                x: 20,Ð
y: 0Ð           },Ð           defaultTheme: falseÐ       }Ð   });Ð});Ð/Flot
Pie Chart GenderÐ$(function() {Ð   var data = [{Ð       label: "Male",Ð
data: 50,Ð       color: "#d3d3d3",Ð   },{Ð       label: "Female",Ð
data: 50,Ð       color: "#1ab394",Ð   }];Ð   var plotObj = $.plot($("#flot-
pie-chart-gender"), data, {Ð       series: {Ð           pie: {Ð
show: trueÐ           }Ð       },Ð       grid: {Ð           hoverable: trueÐ
        },Ð       tooltip: true,Ð       tooltipOpts: {Ð           content:
"%p.0%, %s", // show percentages, rounding to 2 decimal placesÐ
shifts: {Ð                x: 20,Ð                y: 0Ð           },Ð
defaultTheme: falseÐ       }Ð   });Ð});Ð/Flot Pie Chart Age groupsÐ$(function()
{Ð   var data = [{Ð       label: "18/24",Ð       data: 21,Ð       color:
"#d3d3d3",Ð   }, {Ð       label: "24/34",Ð       data: 3,Ð       color:
"#bababa",Ð   }, {Ð       label: "35/44",Ð       data: 15,Ð       color:
"#79d2c0",Ð   }, {Ð       label: "45/54",Ð       data: 37,Ð       color:
"#1ab394",Ð   }, {Ð       label: ">55",Ð       data: 15,Ð       color:
"#79d2c0",Ð
```

```
              }];Ð   var plotObj = $.plot($("#flot-pie-chart-age-groups"),
data, {Ð       series: {Ð           pie: {Ð               show: trueÐ
            }Ð       },Ð       grid: {Ð           hoverable: trueÐ       },Ð
        tooltip: true,Ð       tooltipOpts: {Ð           content: "%p.0%,
%s", // show percentages, rounding to 2 decimal placesÐ           shifts: {Ð
                x: 20,Ð               y: 0Ð           },Ð
defaultTheme: falseÐ       }Ð   });Ð});ÐÐ/Flot Pie Chart Spending powerÐ
$(function() {Ð   var data = [{Ð       label: "High",Ð       data: 20,Ð
color: "#d3d3d3",Ð   }, {Ð       label: "Medium",Ð       data: 40,Ð
color: "#1ab394",Ð   }, {Ð       label: "Low",Ð       data: 40,Ð       color:
"#79d2c0",Ð   }];Ð   var plotObj = $.plot($("#flot-pie-chart-spending-
power"), data, {Ð       series: {Ð           pie: {Ð               show: trueÐ
            }Ð       },Ð       grid: {Ð           hoverable: trueÐ       },Ð
        tooltip: true,Ð       tooltipOpts: {Ð           content: "%p.0%,
%s", // show percentages, rounding to 2 decimal placesÐ           shifts: {Ð
                x: 20,Ð               y: 0Ð           },Ð
defaultTheme: falseÐ       }Ð   });Ð});ÐÐ/Flot Pie Chart User typeÐ$(function() {Ð
    var data = [{Ð       label: "Business",Ð       data: 60,Ð       color:
"#1ab394",Ð   }, {Ð       label: "Private",Ð       data: 40,Ð       color:
"#79d2c0",Ð   }];Ð   var plotObj = $.plot($("#flot-pie-chart-user-type"),
data, {Ð       series: {Ð           pie: {Ð               show: trueÐ
            }Ð       },Ð       grid: {Ð           hoverable: trueÐ       },Ð
        tooltip: true,Ð       tooltipOpts: {Ð           content: "%p.0%,
%s", // show percentages, rounding to 2 decimal placesÐ           shifts: {Ð
                x: 20,Ð               y: 0Ð           },Ð
defaultTheme: falseÐ       }Ð   });Ð});ÐÐ/Flot Pie Chart InterestÐ$(function() {Ð
    var data = [{Ð       label: "Auto",Ð       data: 21,Ð       color:
"#d3d3d3",Ð   }, {Ð       label: "Sports",Ð       data: 3,Ð       color:
"#bababa",Ð   }, {Ð       label: "Health",Ð       data: 15,Ð       color:
"#79d2c0",Ð   }, {Ð       label: "Education",Ð       data: 37,Ð       color:
"#1ab394",Ð   }, {Ð       label: "Other",Ð       data: 15,Ð       color:
"#79d2c0",Ð   }];Ð   var plotObj = $.plot($("#flot-pie-chart-interest"),
data, {Ð       series: {Ð           pie: {Ð               show: trueÐ
            }Ð       },Ð       grid: {Ð           hoverable: trueÐ       },Ð
        tooltip: true,Ð       tooltipOpts: {Ð           content: "%p.0%,
%s", // show percentages, rounding to 2 decimal placesÐ           shifts: {Ð
                x: 20,Ð               y: 0Ð           },Ð
defaultTheme: falseÐ       }Ð   });Ð});Ð
```

public\assets\js\demo\morris-demo.js

```
$(function() {Ð   Morris.Line({Ð       element: 'morris-one-line-chart',Ð
            data: [Ð               { year: '2008', value: 5 },Ð
{ year: '2009', value: 10 },Ð               { year: '2010', value: 8 },Ð
                { year: '2011', value: 22 },Ð               { year: '2012',
value: 8 },Ð               { year: '2014', value: 10 },Ð
{ year: '2015', value: 5 }Ð           ],Ð       xkey: 'year',Ð       ykeys:
['value'],Ð       resize: true,Ð       lineWidth:4,Ð       labels: ['Value'],Ð
        lineColors: ['#1ab394'],Ð       pointSize:5,Ð   });Ð   Morris.Area({Ð
        element: 'morris-area-chart',Ð       data: [{ period: '2010 Q1',
iphone: 2666, ipad: null, itouch: 2647 },Ð           { period: '2010 Q2',
iphone: 2778, ipad: 2294, itouch: 2441 },Ð           { period: '2010 Q3',
iphone: 4912, ipad: 1969, itouch: 2501 },Ð           { period: '2010 Q4',
iphone: 3767, ipad: 3597, itouch: 5689 },Ð           { period: '2011 Q1',
iphone: 6810, ipad: 1914, itouch: 2293 },Ð           { period: '2011 Q2',
iphone: 5670, ipad: 4293, itouch: 1881 },Ð           { period: '2011 Q3',
iphone: 4820, ipad: 3795, itouch: 1588 },Ð           { period: '2011 Q4',
iphone: 15073, ipad: 5967, itouch: 5175 },Ð           { period: '2012 Q1',
iphone: 10687, ipad: 4460, itouch: 2028 },Ð           { period: '2012 Q2',
iphone: 8432, ipad: 5713, itouch: 1791 } ],Ð       xkey: 'period',Ð
ykeys: ['iphone', 'ipad', 'itouch'],Ð       labels: ['iPhone', 'iPad', 'iPod
Touch'],Ð       pointSize: 2,Ð       hideHover: 'auto',Ð       resize: true,Ð
        lineColors: ['#87d6c6', '#54cdb4','#1ab394'],Ð       lineWidth:2,Ð
        pointSize:1,Ð   });Ð   Morris.Donut({Ð       element: 'morris-donut-
chart',Ð       data: [{ label: "Download Sales", value: 12 },Ð
{ label: "In-Store Sales", value: 30 },Ð           { label: "Mail-Order
Sales", value: 20 } ],Ð       resize: true,Ð       colors: ['#87d6c6',
'#54cdb4','#1ab394'],Ð   });Ð   Morris.Bar({Ð       element: 'morris-bar-
chart',Ð       data: [{ y: '2006', a: 60, b: 50 },Ð           { y: '2007', a:
75, b: 65 },Ð           { y: '2008', a: 50, b: 40 },Ð           { y: '2009',
a: 75, b: 65 },Ð           { y: '2010', a: 50, b: 40 },Ð           { y:
'2011', a: 75, b: 65 },Ð           { y: '2012', a: 100, b: 90 } ],Ð
xkey: 'y',Ð       ykeys: ['a', 'b'],Ð       labels: ['Series A', 'Series B'],Ð
        hideHover: 'auto',Ð       resize: true,Ð       barColors: ['#1ab394',
'#cacaca'],Ð   });Ð   Morris.Line({Ð       element: 'morris-line-chart',Ð
        data: [{ y: '2006', a: 100, b: 90 },Ð           { y: '2007', a: 75,
b: 65 },Ð           { y: '2008', a: 50, b: 40 },Ð           { y: '2009', a:
75, b: 65 },Ð           { y: '2010', a: 50, b: 40 },Ð           { y: '2011',
a: 75, b: 65 },Ð           { y: '2012', a: 100, b: 90 } ],Ð       xkey: 'y',Ð
        ykeys: ['a', 'b'],Ð       labels: ['Series A', 'Series B'],Ð
hideHover: 'auto',Ð       resize: true,Ð       lineColors:
['#54cdb4','#1ab394'],Ð   });Ð});Ð
```

public\assets\js\demo\peity-demo.js

```
$(function() {Ð   $("span.pie").peity("pie", {Ð       fill: ['#1ab394',
'#d7d7d7', '#ffffff']Ð   })Ð   $(".line").peity("line",{Ð       fill:
'#1ab394',Ð       stroke:'#169c81',Ð   })Ð   $(".bar").peity("bar", {Ð
fill: ["#1ab394", "#d7d7d7"]Ð   })Ð   $(".bar_dashboard").peity("bar", {Ð
        fill: ["#1ab394", "#d7d7d7"],Ð       width:100Ð   })Ð   var
updatingChart = $(".updating-chart").peity("line", { fill:
'#1ab394',stroke:'#169c81', width: 64 })Ð   setInterval(function() {Ð
var random = Math.round(Math.random() * 10)Ð       var values =
updatingChart.text().split(",")Ð       values.shift()Ð
values.push(random)Ð       updatingChartÐ           .text(values.join(","))Ð
            .change()Ð   }, 1000);Ð});Ð
```

public\assets\js\demo\rickshaw-demo.js

```
$(function() {Ð   var graph = new Rickshaw.Graph( {Ð       element:
document.querySelector("#chart"),Ð       series: [{Ð           color:
'#1ab394',Ð           data: [Ð               { x: 0, y: 40 },Ð
{ x: 1, y: 49 },Ð               { x: 2, y: 38 },Ð               { x: 3, y:
30 },Ð               { x: 4, y: 32 } ]Ð       }]Ð   });Ð   graph.render();Ð
var graph2 = new Rickshaw.Graph( {Ð       element:
document.querySelector("#rickshaw_multi"),Ð       renderer: 'area',Ð
stroke: true,Ð       series: [ {Ð           data: [ { x: 0, y: 40 }, { x: 1,
y: 49 }, { x: 2, y: 38 }, { x: 3, y: 20 }, { x: 4, y: 16 } ],Ð
color: '#1ab394',Ð           stroke: '#17997f'Ð       }, {Ð           data:
[ { x: 0, y: 22 }, { x: 1, y: 25 }, { x: 2, y: 38 }, { x: 3, y: 44 }, { x: 4,
y: 46 } ],Ð           color: '#eeeeee',Ð           stroke: '#d7d7d7'Ð
        } ]Ð   } );Ð   graph2.renderer.unstack = true;Ð   graph2.render();Ð
var graph3 = new Rickshaw.Graph({Ð       element:
document.querySelector("#rickshaw_line"),Ð       renderer: 'line',Ð
series: [ {Ð           data: [ { x: 0, y: 40 }, { x: 1, y: 49 }, { x: 2, y:
38 }, { x: 3, y: 30 }, { x: 4, y: 32 } ],Ð           color: '#1ab394'Ð
        } ]Ð   } );Ð   graph3.render();Ð   var graph4 = new Rickshaw.Graph({Ð
        element: document.querySelector("#rickshaw_multi_line"),Ð
renderer: 'line',Ð       series: [{Ð           data: [ { x: 0, y: 40 }, { x:
1, y: 49 }, { x: 2, y: 38 }, { x: 3, y: 30 }, { x: 4, y: 32 } ],Ð
color: '#1ab394'Ð       }, {Ð           data: [ { x: 0, y: 20 }, { x: 1, y:
24 }, { x: 2, y: 19 }, { x: 3, y: 15 }, { x: 4, y: 16 } ],Ð           color:
'#d7d7d7'Ð       }]Ð   });Ð   graph4.render();Ð   var graph5 = new
Rickshaw.Graph( {Ð       element: document.querySelector("#rickshaw_bars"),Ð
        renderer: 'bar',Ð       series: [ {Ð           data: [ { x: 0, y:
40 }, { x: 1, y: 49 }, { x: 2, y: 38 }, { x: 3, y: 30 }, { x: 4, y: 32 } ],Ð
            color: '#1ab394'Ð       } ]Ð   } );Ð   graph5.render();Ð   var
graph6 = new Rickshaw.Graph( {Ð       element:
document.querySelector("#rickshaw_bars_stacked"),Ð       renderer: 'bar',Ð
        series: [Ð           {Ð               data: [ { x: 0, y: 40 }, { x:
1, y: 49 }, { x: 2, y: 38 }, { x: 3, y: 30 }, { x: 4, y: 32 } ],Ð
                color: '#1ab394'Ð           }, {Ð               data: [ { x:
0, y: 20 }, { x: 1, y: 24 }, { x: 2, y: 19 }, { x: 3, y: 15 }, { x: 4, y:
16 } ],Ð               color: '#d7d7d7'Ð           } ]Ð   } );Ð
graph6.render();Ð   var graph7 = new Rickshaw.Graph( {Ð       element:
document.querySelector("#rickshaw_scatterplot"),Ð       renderer:
'scatterplot',Ð       stroke: true,Ð       padding: { top: 0.05, left: 0.05,
right: 0.05 },Ð       series: [ {Ð           data: [ { x: 0, y: 15 },Ð
                { x: 1, y: 18 },Ð               { x: 2, y: 10 },Ð
                { x: 3, y: 12 },Ð               { x: 4, y: 15 },Ð
                { x: 5, y: 24 },Ð               { x: 6, y: 28 },Ð
                { x: 7, y: 31 },Ð               { x: 8, y: 22 },Ð
                { x: 9, y: 18 },Ð               { x: 10, y: 16 }Ð           ],Ð
            color: '#1ab394'Ð       } ]Ð   } );Ð   graph7.render();Ð});
```

public\assets\js\demo\sparkline-demo.js

```
$(function () {Ð   $("#sparkline1").sparkline([34, 43, 43, 35, 44, 32, 44,
52, 25], {Ð       type: 'line',Ð       lineColor: '#17997f',Ð
fillColor: '#1ab394',Ð   });Ð   $("#sparkline2").sparkline([5, 6, 7, 2, 0,
-4, -2, 4], {Ð       type: 'bar',Ð       barColor: '#1ab394',Ð
negBarColor: '#c6c6c6'});Ð   $("#sparkline3").sparkline([1, 1, 2], {Ð
type: 'pie',Ð       sliceColors: ['#1ab394', '#b3b3b3', '#e4f0fb']});Ð
$("#sparkline4").sparkline([34, 43, 43, 35, 44, 32, 15, 22, 46, 33, 86, 54,
73, 53, 12, 53, 23, 65, 23, 63, 53, 42, 34, 56, 76, 15, 54, 23, 44], {Ð
type: 'line',Ð       lineColor: '#17997f',Ð       fillColor: '#ffffff',Ð   });Ð
    $("#sparkline5").sparkline([1, 1, 0, 1, -1, -1, 1, -1, 0, 0, 1, 1], {Ð
        type: 'tristate',Ð       posBarColor: '#1ab394',Ð       negBarColor:
'#bfbfbf'});Ð   $("#sparkline6").sparkline([4, 6, 7, 7, 4, 3, 2, 1, 4, 4, 5,
6, 3, 4, 5, 8, 7, 6, 9, 3, 2, 4, 1, 5, 6, 4, 3, 7, ], {Ð       type:
'discrete',Ð       lineColor: '#1ab394'});Ð   $("#sparkline7").sparkline([52,
12, 44], {Ð       type: 'pie',Ð       height: '150px',Ð       sliceColors:
['#1ab394', '#b3b3b3', '#e4f0fb']});Ð   $("#sparkline8").sparkline([5, 6, 7,
2, 0, 4, 2, 4, 5, 7, 2, 4, 12, 14, 4, 2, 14, 12, 7], {Ð       type: 'bar',Ð
        barWidth: 8,Ð       height: '150px',Ð       barColor: '#1ab394',Ð
        negBarColor: '#c6c6c6'});Ð   $("#sparkline9").sparkline([34, 43, 43,
35, 44, 32, 15, 22, 46, 33, 86, 54, 73, 53, 12, 53, 23, 65, 23, 63, 53, 42,
34, 56, 76, 15, 54, 23, 44], {Ð       type: 'line',Ð       lineWidth: 1,Ð
        height: '150px',Ð       lineColor: '#17997f',Ð       fillColor:
'#ffffff',Ð   });Ð});Ð
```

public\assets\js\iframe-content.js

```
document.addEventListener('DOMContentLoaded', function() {    function
sendMessageToParent(message) {        window.parent.postMessage(message, '*');
    }         document.body.addEventListener('click', function(event) {
        event.preventDefault();        var element = event.target;        var
selector = generateSelector(element);        var styles =
getComputedStyle(element);
sendMessageToParent({            type: 'elementClicked',            selector:
selector,            elementType: element.tagName.toLowerCase(),
styles: {                backgroundColor: styles.backgroundColor,
                color: styles.color,                fontFamily:
styles.fontFamily,                fontSize: styles.fontSize,
padding: styles.padding,                margin: styles.margin            }
        });    });           function generateSelector(element) {        //
This is a simple implementation. You might want to create a more robust
selector generation.        if (element.id) {            return '#' +
element.id;        } else if (element.className) {            return '.' +
element.className.split(' ')[0];        } else {            return
element.tagName.toLowerCase();        }    }
window.addEventListener('message', function(event) {        if
(event.data.type === 'updateStyle') {            var elements =
document.querySelectorAll(event.data.selector);
elements.forEach(function(element) {
element.style[event.data.property] = event.data.value;            });
        } else if (event.data.type === 'saveStyles') {            //
Implement saving logic here            console.log('Saving styles');        }
else if (event.data.type === 'iframeLoaded') {            console.log('Iframe
loaded message received');        }    });
sendMessageToParent({ type: 'previewLoaded' });});
```

public\assets\js\inspinia.js

```
/*Ð*Ð*   INSPINIA - Responsive Admin ThemeÐ*   version 2.4Ð*Ð*/Ð
$(document).ready(function () {Ð   // Add body-small class if window less
than 768pxÐ   if ($(this).width() < 769) {Ð       $('body').addClass('body-
small')Ð   } else {Ð       $('body').removeClass('body-small')Ð   }Ð   //
MetsiMenuÐ   $('#side-menu').metisMenu();Ð   // Collapse ibox functionÐ
$('.collapse-link').click(function () {Ð       var ibox =
$(this).closest('div.ibox');Ð       var button = $(this).find('i');Ð
var content = ibox.find('div.ibox-content');Ð       content.slideToggle(200);Ð
        button.toggleClass('fa-chevron-up').toggleClass('fa-chevron-down');Ð
        ibox.toggleClass('').toggleClass('border-bottom');Ð
setTimeout(function () {Ð           ibox.resize();Ð
ibox.find('[id^=map-]').resize();Ð       }, 50);Ð   });Ð   // Close ibox
functionÐ   $('.close-link').click(function () {Ð       var content =
$(this).closest('div.ibox');Ð       content.remove();Ð   });Ð   // Fullscreen
ibox functionÐ   $('.fullscreen-link').click(function () {Ð       var ibox =
$(this).closest('div.ibox');Ð       var button = $(this).find('i');Ð
$('body').toggleClass('fullscreen-ibox-mode');Ð       button.toggleClass('fa-
expand').toggleClass('fa-compress');Ð       ibox.toggleClass('fullscreen');Ð
        setTimeout(function () {Ð           $(window).trigger('resize');Ð
        }, 100);Ð   });Ð   // Close menu in canvas modeÐ   $('.close-canvas-
menu').click(function () {Ð       $("body").toggleClass("mini-navbar");Ð
        SmoothlyMenu();Ð   });Ð   // Run menu of canvasÐ   $('body.canvas-
menu .sidebar-collapse').slimScroll({Ð       height: '100%',Ð
railOpacity: 0.9Ð   });Ð   // Open close right sidebarÐ   $('.right-sidebar-
toggle').click(function () {Ð       $('#right-sidebar').toggleClass('sidebar-
open');Ð   });Ð   // Initialize slimscroll for right sidebarÐ   $('.sidebar-
container').slimScroll({Ð       height: '100%',Ð       railOpacity: 0.4,Ð
        wheelStep: 10Ð   });Ð   // Open close small chatÐ   $('.open-small-
chat').click(function () {Ð       $(this).children().toggleClass('fa-
comments').toggleClass('fa-remove');Ð       $('.small-chat-
box').toggleClass('active');Ð   });Ð   // Initialize slimscroll for small chatÐ
    $('.small-chat-box .content').slimScroll({Ð       height: '234px',Ð
railOpacity: 0.4Ð   });Ð   // Small todo handlerÐ   $('.check-
link').click(function () {Ð       var button = $(this).find('i');Ð       var
label = $(this).next('span');Ð       button.toggleClass('fa-check-
square').toggleClass('fa-square-o');Ð       label.toggleClass('todo-
completed');Ð       return false;Ð   });Ð   // Append config box / Only for
demo purposeÐ   // Uncomment on server mode to enable XHR callsÐ   //
$.get("skin-config.html", function (data) {Ð   //    if (!
$('body').hasClass('no-skin-config'))Ð   //        $('body').append(data);Ð
    //});Ð   // Minimalize menuÐ   $('.navbar-minimalize').click(function () {Ð
        $("body").toggleClass("mini-navbar");Ð       SmoothlyMenu();Ð   });Ð
    // Tooltips demoÐ   $('.tooltip-demo').tooltip({Ð       selector: "[data-
toggle=tooltip]",Ð       container: "body"Ð   });Ð   // Move modal to bodyÐ
    // Fix Bootstrap backdrop issu with animation.cssÐ
$('.modal').appendTo("body");Ð   // Full height of sidebarÐ   function
fix_height() {Ð       var heightWithoutNavbar = $("body > #wrapper").height()
- 61;Ð       $(".sidebard-panel").css("min-height", heightWithoutNavbar +
"px");Ð       var navbarHeigh = $('nav.navbar-default').height();Ð       var
wrapperHeigh = $('#page-wrapper').height();Ð       if (navbarHeigh >
wrapperHeigh) {Ð           $('#page-wrapper').css("min-height", navbarHeigh +
"px");Ð       }Ð       if (navbarHeigh < wrapperHeigh) {Ð           $('#page-
wrapper').css("min-height", $(window).height() + "px");Ð       }Ð       if
($('body').hasClass('fixed-nav')) {Ð           if (navbarHeigh >
wrapperHeigh) {Ð               $('#page-wrapper').css("min-height",
navbarHeigh - 60 + "px");Ð           } else {Ð               $('#page-
wrapper').css("min-height", $(window).height() - 60 + "px");Ð           }Ð
        }Ð   }Ð   fix_height();Ð   // Fixed SidebarÐ   $(window).bind("load",
function () {Ð
```

```
                    if ($("body").hasClass('fixed-sidebar')) {Ð
$('.sidebar-collapse').slimScroll({Ð                height: '100%',Ð
                railOpacity: 0.9Ð            });Ð       }Ð   });Ð   // Move
right sidebar top after scrollÐ   $(window).scroll(function () {Ð       if
($(window).scrollTop() > 0 && !$('body').hasClass('fixed-nav')) {Ð
$('#right-sidebar').addClass('sidebar-top');Ð       } else {Ð
$('#right-sidebar').removeClass('sidebar-top');Ð       }Ð   });Ð
$(window).bind("load resize scroll", function () {Ð       if (!
$("body").hasClass('body-small')) {Ð           fix_height();Ð       }Ð   });Ð
    $("[data-toggle=popover]")Ð       .popover();Ð   // Add slimscroll to
elementÐ   $('.full-height-scroll').slimscroll({Ð       height: '100%'Ð   })Ð
});Ð// Minimalize menu when screen is less than 768pxÐ$(window).bind("resize",
function () {Ð   if ($(this).width() < 769) {Ð       $('body').addClass('body-
small')Ð   } else {Ð       $('body').removeClass('body-small')Ð   }Ð});Ð// 
Local Storage functionsÐ// Set proper body class and plugins based on user
configurationÐ$(document).ready(function () {Ð   if (localStorageSupport) {Ð
        var collapse = localStorage.getItem("collapse_menu");Ð       var
fixedsidebar = localStorage.getItem("fixedsidebar");Ð       var fixednavbar =
localStorage.getItem("fixednavbar");Ð       var boxedlayout =
localStorage.getItem("boxedlayout");Ð       var fixedfooter =
localStorage.getItem("fixedfooter");Ð       var body = $('body');Ð       if
(fixedsidebar == 'on') {Ð           body.addClass('fixed-sidebar');Ð
            $('.sidebar-collapse').slimScroll({Ð                height: '100%',Ð
                railOpacity: 0.9Ð            });Ð       }Ð       if (collapse
== 'on') {Ð           if (body.hasClass('fixed-sidebar')) {Ð               if
(!body.hasClass('body-small')) {Ð                   body.addClass('mini-
navbar');Ð               }Ð           } else {Ð               if (!
body.hasClass('body-small')) {Ð                   body.addClass('mini-
navbar');Ð               }Ð           }Ð       }Ð       if (fixednavbar ==
'on') {Ð           $(".navbar-static-top").removeClass('navbar-static-
top').addClass('navbar-fixed-top');Ð           body.addClass('fixed-nav');Ð
        }Ð       if (boxedlayout == 'on') {Ð           body.addClass('boxed-
layout');Ð       }Ð       if (fixedfooter == 'on') {Ð
$(".footer").addClass('fixed');Ð       }Ð   }Ð});Ð// check if browser support
HTML5 local storageÐfunction localStorageSupport() {Ð   return
(('localStorage' in window) && window['localStorage'] !== null)}ÐÐ// For demo
purpose - animation css scriptÐfunction animationHover(element, animation) {Ð
    element = $(element);Ð   element.hover(Ð       function () {Ð
element.addClass('animated ' + animation);Ð       },Ð       function () {Ð
            //wait for animation to finish before removing classesÐ
window.setTimeout(function () {Ð               element.removeClass('animated
' + animation);Ð           }, 2000);Ð       });}ÐÐfunction SmoothlyMenu() {Ð
if (!$('body').hasClass('mini-navbar') || $('body').hasClass('body-small')) {Ð
        // Hide menu in order to smoothly turn on when maximize menuÐ
$('#side-menu').hide();Ð       // For smoothly turn on menuÐ       setTimeout(Ð
            function () {Ð               $('#side-menu').fadeIn(400);Ð
            }, 200);Ð   } else if ($('body').hasClass('fixed-sidebar')) {Ð
        $('#side-menu').hide();Ð       setTimeout(Ð           function () {Ð
                $('#side-menu').fadeIn(400);Ð           }, 100);Ð   } else {Ð
        // Remove all inline style from jquery fadeIn function to reset menu
stateÐ       $('#side-menu').removeAttr('style');Ð   }}ÐÐ// Dragable panelsÐ
function WinMove() {Ð   var element = "[class*=col]";Ð   var handle = ".ibox-
title";Ð   var connect = "[class*=col]";Ð   $(element).sortable(Ð       {Ð
            handle: handle,Ð           connectWith: connect,Ð
tolerance: 'pointer',Ð           forcePlaceholderSize: true,Ð
opacity: 0.8Ð       })Ð       .disableSelection();}ÐÐ
```

public\assets\js\plugins\bootstrap-markdown\bootstrap-markdown.js

```
/* ======================================================Ð* bootstrap-
markdown.js v2.9.0Ð* http://github.com/toopay/bootstrap-markdownÐ*
======================================================Ð* Copyright 2013-2015
Taufan AdityaÐ*Ð* Licensed under the Apache License, Version 2.0 (the
"License");Ð* you may not use this file except in compliance with the License.Ð
 * You may obtain a copy of the License atÐ*Ð* http://www.apache.org/licenses/
LICENSE-2.0Ð*Ð* Unless required by applicable law or agreed to in writing,
softwareÐ* distributed under the License is distributed on an "AS IS" BASIS,Ð
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.Ð*
See the License for the specific language governing permissions andÐ*
limitations under the License.Ð*
============================================================== */Ð
(function(factory){Ð   if (typeof define === "function" && define.amd) {Ð
        //RequireJSÐ       define(["jquery"], factory);Ð   } else if (typeof
exports === 'object') {Ð       //Backbone.jsÐ
factory(require('jquery'));Ð   } else {Ð       //Jquery pluginÐ
factory(jQuery);Ð   }Ð}(function($){Ð "use strict"; // jshint ;_;Ð /* MARKDOWN
CLASS DEFINITIONÐ  * ========================== */Ð var Markdown = function
(element, options) {Ð   // @TODO : remove this BC on next major releaseÐ   //
@see : https://github.com/toopay/bootstrap-markdown/issues/109Ð   var opts =
['autofocus', 'savable', 'hideable', 'width', Ð     'height', 'resize',
'iconlibrary', 'language', Ð     'footer', 'fullscreen', 'hiddenButtons',
'disabledButtons'];Ð   $.each(opts,function(_, opt){Ð     if (typeof
$(element).data(opt) !== 'undefined') {Ð       options = typeof options ==
'object' ? options : {}Ð       options[opt] = $(element).data(opt)Ð     }Ð
    });Ð   // End BCÐ   // Class PropertiesÐ   this.$ns           =
'bootstrap-markdown';Ð   this.$element      = $(element);Ð   this.
$editable     = {el:null, type:null,attrKeys:[], attrValues:[], content:null};Ð
    this.$options      = $.extend(true, {}, $.fn.markdown.defaults, options,
this.$element.data('options'));Ð   this.$oldContent   = null;Ð   this.
$isPreview    = false;Ð   this.$isFullscreen = false;Ð   this.$editor       =
null;Ð   this.$textarea     = null;Ð   this.$handler      = [];Ð   this.
$callback     = [];Ð   this.$nextTab      = [];Ð   this.showEditor();Ð };Ð
Markdown.prototype = {Ð   constructor: MarkdownÐ , __alterButtons:
function(name,alter) {Ð     var handler = this.$handler, isAll = (name ==
'all'),that = this;Ð     $.each(handler,function(k,v) {Ð       var halt =
true;Ð       if (isAll) {Ð         halt = false;Ð       } else {Ð
halt = v.indexOf(name) < 0;Ð       }Ð       if (halt === false) {Ð
alter(that.$editor.find('button[data-handler="'+v+'"]'));Ð       }Ð     });Ð
    }Ð , __buildButtons: function(buttonsArray, container) {Ð     var i,Ð
         ns = this.$ns,Ð         handler = this.$handler,Ð         callback
= this.$callback;Ð     for (i=0;i<buttonsArray.length;i++) {Ð       // Build
each group containerÐ       var y, btnGroups = buttonsArray[i];Ð       for
(y=0;y<btnGroups.length;y++) {Ð         // Build each button groupÐ
var z,Ð             buttons = btnGroups[y].data,Ð
btnGroupContainer = $('<div/>', {Ð                                    'class':
'btn-group'Ð                                 });Ð         for
(z=0;z<buttons.length;z++) {Ð           var button = buttons[z],Ð
                buttonContainer, buttonIconContainer,Ð
buttonHandler = ns+'-'+button.name,Ð                buttonIcon =
this.__getIcon(button.icon),Ð               btnText = button.btnText ?
button.btnText : '',Ð               btnClass = button.btnClass ?
button.btnClass : 'btn',Ð               tabIndex = button.tabIndex ?
button.tabIndex : '-1',Ð               hotkey = typeof button.hotkey !==
'undefined' ? button.hotkey : '',Ð               hotkeyCaption = typeof
jQuery.hotkeys !== 'undefined' && hotkey !== '' ? ' ('+hotkey+')' : '';Ð
            // Construct the button objectÐ           buttonContainer =
$('<button></button>');Ð           buttonContainer.text(' ' +
this.__localize(btnText)).addClass('btn-default btn-sm').addClass(btnClass);Ð
```

```
            if(btnClass.match(/btn\-(primary|success|info|warning|danger|
link)/)){Ð                buttonContainer.removeClass('btn-default');Ð
            }Ð            buttonContainer.attr({Ð                'type':
'button',Ð                'title': this.__localize(button.title) +
hotkeyCaption,Ð                'tabindex': tabIndex,Ð                'data-
provider': ns,Ð                'data-handler': buttonHandler,Ð
'data-hotkey': hotkeyÐ            });Ð            if (button.toggle === true){Ð
              buttonContainer.attr('data-toggle', 'button');Ð            }Ð
            buttonIconContainer = $('<span/>');Ð
buttonIconContainer.addClass(buttonIcon);Ð
buttonIconContainer.prependTo(buttonContainer);Ð            // Attach the
button objectÐ            btnGroupContainer.append(buttonContainer);Ð
            // Register handler and callbackÐ
handler.push(buttonHandler);Ð            callback.push(button.callback);Ð
          }Ð         // Attach the button group into container domÐ
container.append(btnGroupContainer);Ð        }Ð     }Ð     return container;Ð
    }Ð , __setListener: function() {Ð     // Set size and resizable PropertiesÐ
      var hasRows = typeof this.$textarea.attr('rows') !== 'undefined',Ð
          maxRows = this.$textarea.val().split("\n").length > 5 ? this.
$textarea.val().split("\n").length : '5',Ð         rowsVal = hasRows ? this.
$textarea.attr('rows') : maxRows;Ð     this.$textarea.attr('rows',rowsVal);Ð
      if (this.$options.resize) {Ð       this.$textarea.css('resize',this.
$options.resize);Ð     }Ð     this.$textareaÐ       .on('focus',
$.proxy(this.focus, this))Ð       .on('keypress', $.proxy(this.keypress,
this))Ð       .on('keyup',    $.proxy(this.keyup, this))Ð
        .on('change',   $.proxy(this.change, this))Ð       .on('select',
$.proxy(this.select, this));Ð     if (this.eventSupported('keydown')) {Ð
        this.$textarea.on('keydown', $.proxy(this.keydown, this));Ð     }Ð
      // Re-attach markdown dataÐ     this.$textarea.data('markdown',this);Ð
    }Ð , __handle: function(e) {Ð     var target = $(e.currentTarget),Ð
          handler = this.$handler,Ð         callback = this.$callback,Ð
          handlerName = target.attr('data-handler'),Ð         callbackIndex =
handler.indexOf(handlerName),Ð         callbackHandler =
callback[callbackIndex];Ð     // Trigger the focusinÐ
$(e.currentTarget).focus();Ð     callbackHandler(this);Ð     // Trigger
onChange for each button handleÐ     this.change(this);Ð     // Unless it was
the save handler,Ð     // focusin the textareaÐ     if
(handlerName.indexOf('cmdSave') < 0) {Ð       this.$textarea.focus();Ð     }Ð
      e.preventDefault();Ð   }Ð , __localize: function(string) {Ð     var
messages = $.fn.markdown.messages,Ð         language = this.$options.language;Ð
      if (Ð       typeof messages !== 'undefined' &&Ð       typeof
messages[language] !== 'undefined' &&Ð       typeof messages[language]
[string] !== 'undefined'Ð     ) {Ð       return messages[language][string];Ð
      }Ð     return string;Ð   }Ð , __getIcon: function(src) {Ð   return
typeof src == 'object' ? src[this.$options.iconlibrary] : src;Ð }Ð ,
setFullscreen: function(mode) {Ð   var $editor = this.$editor,Ð
$textarea = this.$textarea;Ð   if (mode === true) {Ð     $editor.addClass('md-
fullscreen-mode');Ð     $('body').addClass('md-nooverflow');Ð     this.
$options.onFullscreen(this);Ð   } else {Ð     $editor.removeClass('md-
fullscreen-mode');Ð     $('body').removeClass('md-nooverflow');Ð     if (this.
$isPreview == true) this.hidePreview().showPreview()Ð   }Ð   this.
$isFullscreen = mode;Ð   $textarea.focus();Ð }Ð , showEditor: function() {Ð
      var instance = this,Ð         textarea,Ð         ns = this.$ns,Ð
          container = this.$element,Ð         originalHeigth =
container.css('height'),Ð         originalWidth = container.css('width'),Ð
          editable = this.$editable,Ð         handler = this.$handler,Ð
          callback = this.$callback,Ð         options = this.$options,Ð
          editor = $( '<div/>', {Ð                     'class': 'md-editor',Ð
                      click: function() {Ð
```

instance.focus();Ð }Ð });Ð // Prepare the editorÐ if (this.$editor === null) {Ð // Create the panelÐ var editorHeader = $(' ', {Ð 'class': 'md-header btn-toolbar'Ð });Ð // Merge the main & additional button groups togetherÐ var allBtnGroups = [];Ð if (options.buttons.length > 0) allBtnGroups = allBtnGroups.concat(options.buttons[0]);Ð if (options.additionalButtons.length > 0) {Ð // iterate the additional button groupsÐ $.each(options.additionalButtons[0], function(idx, buttonGroup){Ð Ð // see if the group name of the addional group matches an existing groupÐ var matchingGroups = $.grep(allBtnGroups, function(allButtonGroup, allIdx){Ð return allButtonGroup.name === buttonGroup.name;Ð });Ð // if it matches add the addional buttons to that group, if not just add it to the all buttons groupÐ if(matchingGroups.length > 0) {Ð matchingGroups[0].data = matchingGroups[0].data.concat(buttonGroup.data);Ð } else {Ð allBtnGroups.push(options.additionalButtons[0][idx]);Ð }Ð });Ð } Ð // Reduce and/or reorder the button groupsÐ if (options.reorderButtonGroups.length > 0) {Ð allBtnGroups = allBtnGroupsÐ .filter(function(btnGroup) {Ð return options.reorderButtonGroups.indexOf(btnGroup.name) > -1;Ð })Ð .sort(function(a, b) {Ð if (options.reorderButtonGroups.indexOf(a.name) < options.reorderButtonGroups.indexOf(b.name)) return -1;Ð if (options.reorderButtonGroups.indexOf(a.name) > options.reorderButtonGroups.indexOf(b.name)) return 1;Ð return 0;Ð });Ð }Ð // Build the buttonsÐ if (allBtnGroups.length > 0) {Ð editorHeader = this.__buildButtons([allBtnGroups], editorHeader);Ð }Ð if (options.fullscreen.enable) {Ð editorHeader.append(' <a class="md-control md-control-fullscreen" href="#"></a> ').on('click', '.md-control-fullscreen', function(e) {Ð e.preventDefault();Ð instance.setFullscreen(true);Ð });Ð }Ð editor.append(editorHeader);Ð // Wrap the textareaÐ if (container.is('textarea')) {Ð container.before(editor);Ð textarea = container;Ð textarea.addClass('md-input');Ð editor.append(textarea);Ð } else {Ð var rawContent = (typeof toMarkdown == 'function') ? toMarkdown(container.html()) : container.html(),Ð currentContent = $.trim(rawContent);Ð // This is some arbitrary content that could be editedÐ textarea = $('<textarea/>', {Ð 'class': 'md-input',Ð 'val' : currentContentÐ });Ð editor.append(textarea);Ð // Save the editableÐ editable.el = container;Ð editable.type = container.prop('tagName').toLowerCase();Ð editable.content = container.html();Ð $(container[0].attributes).each(function(){Ð editable.attrKeys.push(this.nodeName);Ð editable.attrValues.push(this.nodeValue);Ð });Ð // Set editor to blocked the original containerÐ container.replaceWith(editor);Ð }Ð var editorFooter = $(' ', {Ð 'class': 'md-footer'Ð }),Ð createFooter = false,Ð footer = '';Ð // Create the footer if savableÐ if (options.savable) {Ð createFooter = true;Ð var saveHandler = 'cmdSave';Ð // Register handler and callbackÐ handler.push(saveHandler);Ð callback.push(options.onSave);Ð editorFooter.append('<button class="btn btn-success" data-provider="'Ð + nsÐ

```
                                                                    + '" data-
handler="'Ð                                 + saveHandlerÐ
                                + '"><i class="icon icon-white icon-ok"></i> 'Ð
                                + this.__localize('Save')Ð
                                + '</button>');Ð       }Ð       footer = typeof
options.footer === 'function' ? options.footer(this) : options.footer;Ð
if ($.trim(footer) !== '') {Ð         createFooter = true;Ð
editorFooter.append(footer);Ð       }Ð       if (createFooter)
editor.append(editorFooter);Ð       // Set widthÐ       if (options.width &&
options.width !== 'inherit') {Ð         if (jQuery.isNumeric(options.width)) {Ð
            editor.css('display', 'table');Ð           textarea.css('width',
options.width + 'px');Ð         } else {Ð
editor.addClass(options.width);Ð         }Ð       }Ð       // Set heightÐ
        if (options.height && options.height !== 'inherit') {Ð         if
(jQuery.isNumeric(options.height)) {Ð           var height = options.height;Ð
            if (editorHeader) height = Math.max(0, height -
editorHeader.outerHeight());Ð           if (editorFooter) height =
Math.max(0, height - editorFooter.outerHeight());Ð
textarea.css('height', height + 'px');Ð         } else {Ð
editor.addClass(options.height);Ð         }Ð       }Ð       // ReferenceÐ
        this.$editor     = editor;Ð       this.$textarea   = textarea;Ð
this.$editable   = editable;Ð       this.$oldContent = this.getContent();Ð
        this.__setListener();Ð       // Set editor attributes, data short-
hand API and listenerÐ       this.$editor.attr('id',(new Date()).getTime());Ð
        this.$editor.on('click', '[data-provider="bootstrap-markdown"]',
$.proxy(this.__handle, this));Ð       if (this.$element.is(':disabled') ||
this.$element.is('[readonly]')) {Ð         this.$editor.addClass('md-editor-
disabled');Ð         this.disableButtons('all');Ð       }Ð       if
(this.eventSupported('keydown') && typeof jQuery.hotkeys === 'object') {Ð
          editorHeader.find('[data-provider="bootstrap-
markdown"]').each(function() {Ð           var $button = $(this),Ð
                hotkey = $button.attr('data-hotkey');Ð           if
(hotkey.toLowerCase() !== '') {Ð             textarea.bind('keydown', hotkey,
function() {Ð               $button.trigger('click');Ð               return
false;Ð             });Ð           }Ð         });Ð       }Ð       if
(options.initialstate === 'preview') {Ð         this.showPreview();Ð       }
else if (options.initialstate === 'fullscreen' && options.fullscreen.enable) {Ð
          this.setFullscreen(true);Ð       }Ð     } else {Ð       this.
$editor.show();Ð     }Ð     if (options.autofocus) {Ð       this.
$textarea.focus();Ð       this.$editor.addClass('active');Ð     }Ð     if
(options.fullscreen.enable && options.fullscreen !== false) {Ð       this.
$editor.append('<div class="md-fullscreen-controls">'Ð
+ '<a href="#" class="exit-fullscreen" title="Exit fullscreen"><span class="'
+ this.__getIcon(options.fullscreen.icons.fullscreenOff) + '">'Ð
                        + '</span></a>'Ð                        + '</div>');Ð
        this.$editor.on('click', '.exit-fullscreen', function(e) {Ð
e.preventDefault();Ð         instance.setFullscreen(false);Ð       });Ð     }Ð
      // hide hidden buttons from optionsÐ
this.hideButtons(options.hiddenButtons);Ð     // disable disabled buttons
from optionsÐ     this.disableButtons(options.disabledButtons);Ð     //
Trigger the onShow hookÐ     options.onShow(this);Ð     return this;Ð   }Ð ,
parseContent: function(val) {Ð     var content;Ð     // parse with supported
markdown parserÐ     var val = val || this.$textarea.val();Ð     if (this.
$options.parser) {Ð       content = this.$options.parser(val);Ð     } else if
(typeof markdown == 'object') {Ð       content = markdown.toHTML(val);Ð     }
else if (typeof marked == 'function') {Ð       content = marked(val);Ð     }
else {Ð       content = val;Ð     }Ð     return content;Ð   }Ð , showPreview:
function() {Ð     var options = this.$options,Ð         container = this.
$textarea,Ð         afterContainer = container.next(),Ð
replacementContainer = $('<div/>',{'class':'md-preview','data-
provider':'markdown-preview'}),Ð
```

```
                                        content,Ð         callbackContent;Ð
      if (this.$isPreview == true) {Ð       // Avoid sequenced element
creation on missused scenarioÐ       // @see https://github.com/toopay/
bootstrap-markdown/issues/170Ð       return this;Ð     }Ð     Ð     // Give
flag that tell the editor enter preview modeÐ     this.$isPreview = true;Ð
      // Disable all buttonsÐ
this.disableButtons('all').enableButtons('cmdPreview');Ð     // Try to get
the content from callbackÐ     callbackContent = options.onPreview(this);Ð
      // Set the content based from the callback content if string otherwise
parse value from textareaÐ     content = typeof callbackContent == 'string' ?
callbackContent : this.parseContent();Ð     // Build preview elementÐ
replacementContainer.html(content);Ð     if (afterContainer &&
afterContainer.attr('class') == 'md-footer') {Ð       // If there is footer
element, insert the preview container before itÐ
replacementContainer.insertBefore(afterContainer);Ð     } else {Ð       //
Otherwise, just append it after textareaÐ
container.parent().append(replacementContainer);Ð     }Ð     // Set the
preview element dimensionsÐ     replacementContainer.css({Ð       width:
container.outerWidth() + 'px',Ð       height: container.outerHeight() + 'px'Ð
      });Ð     if (this.$options.resize) {Ð
replacementContainer.css('resize',this.$options.resize);Ð     }Ð     // Hide
the last-active textareaÐ     container.hide();Ð     // Attach the editor
instancesÐ     replacementContainer.data('markdown',this);Ð     if (this.
$element.is(':disabled') || this.$element.is('[readonly]')) {Ð       this.
$editor.addClass('md-editor-disabled');Ð       this.disableButtons('all');Ð
      }Ð     return this;Ð   }Ð , hidePreview: function() {Ð     // Give flag
that tell the editor quit preview modeÐ     this.$isPreview = false;Ð     //
Obtain the preview containerÐ     var container = this.$editor.find('div[data-
provider="markdown-preview"]');Ð     // Remove the preview containerÐ
container.remove();Ð     // Enable all buttonsÐ     this.enableButtons('all');Ð
      // Disable configured disabled buttonsÐ     this.disableButtons(this.
$options.disabledButtons);Ð     // Back to the editorÐ     this.
$textarea.show();Ð     this.__setListener();Ð     return this;Ð   }Ð ,
isDirty: function() {Ð     return this.$oldContent != this.getContent();Ð   }Ð
  , getContent: function() {Ð     return this.$textarea.val();Ð   }Ð ,
setContent: function(content) {Ð     this.$textarea.val(content);Ð     return
this;Ð   }Ð , findSelection: function(chunk) {Ð   var content =
this.getContent(), startChunkPosition;Ð   if (startChunkPosition =
content.indexOf(chunk), startChunkPosition >= 0 && chunk.length > 0) {Ð
var oldSelection = this.getSelection(), selection;Ð
this.setSelection(startChunkPosition,startChunkPosition+chunk.length);Ð
selection = this.getSelection();Ð
this.setSelection(oldSelection.start,oldSelection.end);Ð     return selection;Ð
    } else {Ð     return null;Ð   }Ð }Ð , getSelection: function() {Ð     var
e = this.$textarea[0];Ð     return (Ð         ('selectionStart' in e &&
function() {Ð             var l = e.selectionEnd - e.selectionStart;Ð
              return { start: e.selectionStart, end: e.selectionEnd, length:
l, text: e.value.substr(e.selectionStart, l) };Ð         }) ||Ð         /*
browser not supported */Ð         function() {Ð           return null;Ð
          }Ð     )();Ð   }Ð , setSelection: function(start,end) {Ð     var e
= this.$textarea[0];Ð     return (Ð         ('selectionStart' in e &&
function() {Ð             e.selectionStart = start;Ð
e.selectionEnd = end;Ð             return;Ð         }) ||Ð         /* browser
not supported */Ð         function() {Ð           return null;Ð         }Ð
      )();Ð   }Ð , replaceSelection: function(text) {Ð     var e = this.
$textarea[0];Ð     return (Ð         ('selectionStart' in e && function() {Ð
              e.value = e.value.substr(0, e.selectionStart) + text +
e.value.substr(e.selectionEnd, e.value.length);Ð             // Set cursor to
the last replacement endÐ             e.selectionStart = e.value.length;Ð
              return this;Ð
```

```
                                    }) ||Ð         /* browser not supported */Ð
          function() {Ð             e.value += text;Ð             return
jQuery(e);Ð         }Ð     )();Ð   }Ð , getNextTab: function() {Ð     //
Shift the nextTabÐ     if (this.$nextTab.length === 0) {Ð       return null;Ð
      } else {Ð       var nextTab, tab = this.$nextTab.shift();Ð       if
(typeof tab == 'function') {Ð         nextTab = tab();Ð       } else if
(typeof tab == 'object' && tab.length > 0) {Ð         nextTab = tab;Ð       }Ð
        return nextTab;Ð     }Ð   }Ð , setNextTab: function(start,end) {Ð
      // Push new selection into nextTab collectionsÐ     if (typeof start ==
'string') {Ð       var that = this;Ð       this.$nextTab.push(function(){Ð
          return that.findSelection(start);Ð       });Ð     } else if (typeof
start == 'number' && typeof end == 'number') {Ð       var oldSelection =
this.getSelection();Ð       this.setSelection(start,end);Ð       this.
$nextTab.push(this.getSelection());Ð
this.setSelection(oldSelection.start,oldSelection.end);Ð     }Ð     return;Ð
    }Ð , __parseButtonNameParam: function (names) {Ð     return typeof names
== 'string' ?Ð                     names.split(' ') :Ð
names;Ð   }Ð , enableButtons: function(name) {Ð     var buttons =
this.__parseButtonNameParam(name),Ð       that = this;Ð     $.each(buttons,
function(i, v) {Ð       that.__alterButtons(buttons[i], function (el) {Ð
          el.removeAttr('disabled');Ð       });Ð     });Ð     return this;Ð
    }Ð , disableButtons: function(name) {Ð     var buttons =
this.__parseButtonNameParam(name),Ð       that = this;Ð     $.each(buttons,
function(i, v) {Ð       that.__alterButtons(buttons[i], function (el) {Ð
          el.attr('disabled','disabled');Ð       });Ð     });Ð     return
this;Ð   }Ð , hideButtons: function(name) {Ð     var buttons =
this.__parseButtonNameParam(name),Ð       that = this;Ð     $.each(buttons,
function(i, v) {Ð       that.__alterButtons(buttons[i], function (el) {Ð
          el.addClass('hidden');Ð       });Ð     });Ð     return this;Ð   }Ð
  , showButtons: function(name) {Ð     var buttons =
this.__parseButtonNameParam(name),Ð       that = this;Ð     $.each(buttons,
function(i, v) {Ð       that.__alterButtons(buttons[i], function (el) {Ð
          el.removeClass('hidden');Ð       });Ð     });Ð     return this;Ð   }Ð
  , eventSupported: function(eventName) {Ð     var isSupported = eventName in
this.$element;Ð     if (!isSupported) {Ð       this.
$element.setAttribute(eventName, 'return;');Ð       isSupported = typeof this.
$element[eventName] === 'function';Ð     }Ð     return isSupported;Ð   }Ð ,
keyup: function (e) {Ð     var blocked = false;Ð     switch(e.keyCode) {Ð
        case 40: // down arrowÐ       case 38: // up arrowÐ       case 16: //
shiftÐ       case 17: // ctrlÐ       case 18: // altÐ         break;Ð
case 9: // tabÐ         var nextTab;Ð         if (nextTab =
this.getNextTab(),nextTab !== null) {Ð           // Get the nextTab if existsÐ
            var that = this;Ð           setTimeout(function(){Ð
that.setSelection(nextTab.start,nextTab.end);Ð           },500);Ð
blocked = true;Ð         } else {Ð           // The next tab memory contains
nothing...Ð           // check the cursor position to determine tab actionÐ
            var cursor = this.getSelection();Ð           if (cursor.start ==
cursor.end && cursor.end == this.getContent().length) {Ð             // The
cursor already reach the end of the contentÐ             blocked = false;Ð
            } else {Ð             // Put the cursor to the endÐ
this.setSelection(this.getContent().length,this.getContent().length);Ð
              blocked = true;Ð           }Ð         }Ð         break;Ð
case 13: // enterÐ         blocked = false;Ð         break;Ð       case
27: // escapeÐ         if (this.$isFullscreen) this.setFullscreen(false);Ð
          blocked = false;Ð         break;Ð       default:Ð         blocked =
false;Ð     }Ð     if (blocked) {Ð       e.stopPropagation();Ð
e.preventDefault();Ð     }Ð     this.$options.onChange(this);Ð   }Ð , change:
function(e) {Ð     this.$options.onChange(this);Ð     return this;Ð   }Ð ,
select: function (e) {Ð     this.$options.onSelect(this);Ð     return this;Ð
    }Ð
```

```
        , focus: function (e) {Ð     var options = this.$options,Ð
isHideable = options.hideable,Ð         editor = this.$editor;Ð
editor.addClass('active');Ð     // Blur other markdown(s)Ð
$(document).find('.md-editor').each(function(){Ð       if
($(this).attr('id') !== editor.attr('id')) {Ð         var attachedMarkdown;Ð
          if (attachedMarkdown = $(this).find('textarea').data('markdown'),Ð
              attachedMarkdown === null) {Ð             attachedMarkdown =
$(this).find('div[data-provider="markdown-preview"]').data('markdown');Ð
          }Ð         if (attachedMarkdown) {Ð
attachedMarkdown.blur();Ð         }Ð       }Ð     });Ð     // Trigger the
onFocus hookÐ     options.onFocus(this);Ð     return this;Ð   }Ð , blur:
function (e) {Ð     var options = this.$options,Ð         isHideable =
options.hideable,Ð         editor = this.$editor,Ð         editable = this.
$editable;Ð     if (editor.hasClass('active') || this.
$element.parent().length === 0) {Ð       editor.removeClass('active');Ð
if (isHideable) {Ð         // Check for editable elementsÐ         if
(editable.el !== null) {Ð           // Build the original elementÐ
var oldElement = $('<'+editable.type+'/>'),Ð               content =
this.getContent(),Ð               currentContent = this.parseContent(content);Ð
            $(editable.attrKeys).each(function(k,v) {Ð
oldElement.attr(editable.attrKeys[k],editable.attrValues[k]);Ð           });Ð
            // Get the editor contentÐ
oldElement.html(currentContent);Ð           editor.replaceWith(oldElement);Ð
          } else {Ð           editor.hide();Ð         }Ð       }Ð       //
Trigger the onBlur hookÐ       options.onBlur(this);Ð     }Ð     return this;Ð
    }Ð };Ð/* MARKDOWN PLUGIN DEFINITIONÐ * ========================== */Ð var
old = $.fn.markdown;Ð $.fn.markdown = function (option) {Ð   return
this.each(function () {Ð     var $this = $(this)Ð       , data =
$this.data('markdown')Ð       , options = typeof option == 'object' && option;Ð
      if (!data) $this.data('markdown', (data = new Markdown(this, options)))Ð
    })Ð };Ð $.fn.markdown.messages = {};Ð $.fn.markdown.defaults = {Ð   /*
Editor Properties */Ð   autofocus: false,Ð   hideable: false,Ð   savable:
false,Ð   width: 'inherit',Ð   height: 'inherit',Ð   resize: 'none',Ð
iconlibrary: 'glyph',Ð   language: 'en',Ð   initialstate: 'editor',Ð
parser: null,Ð   /* Buttons Properties */Ð   buttons: [Ð     [{Ð       name:
'groupFont',Ð       data: [{Ð         name: 'cmdBold',Ð         hotkey:
'Ctrl+B',Ð         title: 'Bold',Ð         icon: { glyph: 'glyphicon
glyphicon-bold', fa: 'fa fa-bold', 'fa-3': 'icon-bold' },Ð         callback:
function(e){Ð           // Give/remove ** surround the selectionÐ
var chunk, cursor, selected = e.getSelection(), content = e.getContent();Ð
            if (selected.length === 0) {Ð             // Give extra wordÐ
              chunk = e.__localize('strong text');Ð           } else {Ð
              chunk = selected.text;Ð           }Ð           // transform
selection and set the cursor into chunked textÐ           if
(content.substr(selected.start-2,2) === '**'Ð               &&
content.substr(selected.end,2) === '**' ) {Ð
e.setSelection(selected.start-2,selected.end+2);Ð
e.replaceSelection(chunk);Ð             cursor = selected.start-2;Ð
            } else {Ð             e.replaceSelection('**'+chunk+'**');Ð
              cursor = selected.start+2;Ð           }Ð           // Set the
cursorÐ           e.setSelection(cursor,cursor+chunk.length);Ð         }Ð
        },{Ð         name: 'cmdItalic',Ð         title: 'Italic',Ð
hotkey: 'Ctrl+I',Ð         icon: { glyph: 'glyphicon glyphicon-italic', fa:
'fa fa-italic', 'fa-3': 'icon-italic' },Ð         callback: function(e){Ð
            // Give/remove * surround the selectionÐ           var chunk,
cursor, selected = e.getSelection(), content = e.getContent();Ð           if
(selected.length === 0) {Ð             // Give extra wordÐ             chunk
= e.__localize('emphasized text');Ð           } else {Ð             chunk =
selected.text;Ð           }Ð           // transform selection and set the
cursor into chunked textÐ
```

```
                                    if (content.substr(selected.start-1,1)
=== '_'Ð                && content.substr(selected.end,1) === '_' ) {Ð
              e.setSelection(selected.start-1,selected.end+1);Ð
e.replaceSelection(chunk);Ð             cursor = selected.start-1;Ð
            } else {Ð             e.replaceSelection('_'+chunk+'_');Ð
              cursor = selected.start+1;Ð           }Ð           // Set the
cursorÐ           e.setSelection(cursor,cursor+chunk.length);Ð         }Ð
        },{Ð         name: 'cmdHeading',Ð         title: 'Heading',Ð
hotkey: 'Ctrl+H',Ð         icon: { glyph: 'glyphicon glyphicon-header', fa:
'fa fa-header', 'fa-3': 'icon-font' },Ð         callback: function(e){Ð
            // Append/remove ### surround the selectionÐ           var chunk,
cursor, selected = e.getSelection(), content = e.getContent(), pointer,
prevChar;Ð           if (selected.length === 0) {Ð             // Give extra
wordÐ             chunk = e.__localize('heading text');Ð           } else {Ð
              chunk = selected.text + '\n';Ð           }Ð           //
transform selection and set the cursor into chunked textÐ           if
((pointer = 4, content.substr(selected.start-pointer,pointer) === '### ')Ð
                || (pointer = 3, content.substr(selected.start-
pointer,pointer) === '###')) {Ð             e.setSelection(selected.start-
pointer,selected.end);Ð             e.replaceSelection(chunk);Ð
cursor = selected.start-pointer;Ð           } else if (selected.start > 0 &&
(prevChar = content.substr(selected.start-1,1), !!prevChar && prevChar !=
'\n')) {Ð             e.replaceSelection('\n\n### '+chunk);Ð
cursor = selected.start+6;Ð           } else {Ð             // Empty string
before elementÐ             e.replaceSelection('### '+chunk);Ð
cursor = selected.start+4;Ð           }Ð           // Set the cursorÐ
            e.setSelection(cursor,cursor+chunk.length);Ð         }Ð       }]Ð
      },{Ð       name: 'groupLink',Ð       data: [{Ð         name: 'cmdUrl',Ð
          title: 'URL/Link',Ð         hotkey: 'Ctrl+L',Ð         icon:
{ glyph: 'glyphicon glyphicon-link', fa: 'fa fa-link', 'fa-3': 'icon-link' },Ð
          callback: function(e){Ð           // Give [] surround the selection
and prepend the linkÐ           var chunk, cursor, selected =
e.getSelection(), content = e.getContent(), link;Ð           if
(selected.length === 0) {Ð             // Give extra wordÐ             chunk
= e.__localize('enter link description here');Ð           } else {Ð
              chunk = selected.text;Ð           }Ð           link =
prompt(e.__localize('Insert Hyperlink'),'http://');Ð           var urlRegex =
new RegExp('^((http|https://|(mailto:)|(//))[a-z0-9]', 'i');Ð           if
(link !== null && link !== '' && link !== 'http://' && urlRegex.test(link)) {Ð
              var sanitizedLink = $('<div>'+link+'</div>').text();Ð
              // transform selection and set the cursor into chunked textÐ
              e.replaceSelection('['+chunk+']('+sanitizedLink+')');Ð
              cursor = selected.start+1;Ð             // Set the cursorÐ
              e.setSelection(cursor,cursor+chunk.length);Ð           }Ð
          }Ð       },{Ð         name: 'cmdImage',Ð         title: 'Image',Ð
          hotkey: 'Ctrl+G',Ð         icon: { glyph: 'glyphicon glyphicon-
picture', fa: 'fa fa-picture-o', 'fa-3': 'icon-picture' },Ð         callback:
function(e){Ð           // Give ![] surround the selection and prepend the
image linkÐ           var chunk, cursor, selected = e.getSelection(), content
= e.getContent(), link;Ð           if (selected.length === 0) {Ð
              // Give extra wordÐ             chunk = e.__localize('enter
image description here');Ð           } else {Ð             chunk =
selected.text;Ð           }Ð           link = prompt(e.__localize('Insert
Image Hyperlink'),'http://');Ð           var urlRegex = new RegExp('^((http|
https://|(//))[a-z0-9]', 'i');Ð           if (link !== null && link !== ''
&& link !== 'http://' && urlRegex.test(link)) {Ð             var
sanitizedLink = $('<div>'+link+'</div>').text();Ð             // transform
selection and set the cursor into chunked textÐ
e.replaceSelection('!['+chunk+']('+sanitizedLink+' "'+e.__localize('enter
image title here')+'")');Ð
```

```
                                        cursor = selected.start+2;Ð
              // Set the next tabÐ
e.setNextTab(e.__localize('enter image title here'));Ð             // Set the
cursorÐ             e.setSelection(cursor,cursor+chunk.length);Ð           }Ð
          }Ð       }]Ð     },{Ð       name: 'groupMisc',Ð       data: [{Ð
          name: 'cmdList',Ð         hotkey: 'Ctrl+U',Ð         title:
'Unordered List',Ð         icon: { glyph: 'glyphicon glyphicon-list', fa: 'fa
fa-list', 'fa-3': 'icon-list-ul' },Ð         callback: function(e){Ð
            // Prepend/Give - surround the selectionÐ           var chunk,
cursor, selected = e.getSelection(), content = e.getContent();Ð           //
transform selection and set the cursor into chunked textÐ           if
(selected.length === 0) {Ð             // Give extra wordÐ             chunk
= e.__localize('list text here');Ð             e.replaceSelection('- '+chunk);Ð
              // Set the cursorÐ             cursor = selected.start+2;Ð
            } else {Ð             if (selected.text.indexOf('\n') < 0) {Ð
                chunk = selected.text;Ð               e.replaceSelection('-
'+chunk);Ð               // Set the cursorÐ               cursor =
selected.start+2;Ð             } else {Ð             var list = [];Ð
                list = selected.text.split('\n');Ð               chunk =
list[0];Ð               $.each(list,function(k,v) {Ð                 list[k]
= '- '+v;Ð               });Ð
e.replaceSelection('\n\n'+list.join('\n'));Ð               // Set the cursorÐ
                cursor = selected.start+4;Ð             }Ð           }Ð
            // Set the cursorÐ
e.setSelection(cursor,cursor+chunk.length);Ð         }Ð       },Ð       {Ð
          name: 'cmdListO',Ð         hotkey: 'Ctrl+O',Ð         title:
'Ordered List',Ð         icon: { glyph: 'glyphicon glyphicon-th-list', fa:
'fa fa-list-ol', 'fa-3': 'icon-list-ol' },Ð         callback: function(e) {Ð
            // Prepend/Give - surround the selectionÐ           var chunk,
cursor, selected = e.getSelection(), content = e.getContent();Ð           //
transform selection and set the cursor into chunked textÐ           if
(selected.length === 0) {Ð             // Give extra wordÐ             chunk
= e.__localize('list text here');Ð             e.replaceSelection('1.
'+chunk);Ð             // Set the cursorÐ             cursor =
selected.start+3;Ð           } else {Ð             if
(selected.text.indexOf('\n') < 0) {Ð               chunk = selected.text;Ð
                e.replaceSelection('1. '+chunk);Ð               // Set the
cursorÐ               cursor = selected.start+3;Ð             } else {Ð
                var list = [];Ð               list =
selected.text.split('\n');Ð               chunk = list[0];Ð
$.each(list,function(k,v) {Ð                 list[k] = '1. '+v;Ð
                });Ð               e.replaceSelection('\n\n'+list.join('\n'));Ð
                // Set the cursorÐ               cursor = selected.start+5;Ð
              }Ð           }Ð           // Set the cursorÐ
e.setSelection(cursor,cursor+chunk.length);Ð         }Ð       },Ð       {Ð
          name: 'cmdCode',Ð         hotkey: 'Ctrl+K',Ð         title: 'Code',Ð
          icon: { glyph: 'glyphicon glyphicon-asterisk', fa: 'fa fa-code',
'fa-3': 'icon-code' },Ð         callback: function(e) {Ð           // Give/
remove ** surround the selectionÐ           var chunk, cursor, selected =
e.getSelection(), content = e.getContent();Ð           if (selected.length
=== 0) {Ð             // Give extra wordÐ             chunk =
e.__localize('code text here');Ð           } else {Ð             chunk =
selected.text;Ð           }Ð           // transform selection and set the
cursor into chunked textÐ           if (content.substr(selected.start-4,4)
=== '```\n'Ð               && content.substr(selected.end,4) === '\n```') {Ð
              e.setSelection(selected.start-4, selected.end+4);Ð
e.replaceSelection(chunk);Ð             cursor = selected.start-4;Ð
            } else if (content.substr(selected.start-1,1) === '`'Ð
                && content.substr(selected.end,1) === '`') {Ð
e.setSelection(selected.start-1,selected.end+1);Ð
```

```
e.replaceSelection(chunk);Ð             cursor = selected.start-1;Ð
            } else if (content.indexOf('\n') > -1) {Ð
e.replaceSelection('```\n'+chunk+'\n```');Ð             cursor =
selected.start+4;Ð           } else {Ð
e.replaceSelection('`'+chunk+'`');Ð             cursor = selected.start+1;Ð
            }Ð           // Set the cursorÐ
e.setSelection(cursor,cursor+chunk.length);Ð         }Ð       },Ð       {Ð
          name: 'cmdQuote',Ð         hotkey: 'Ctrl+Q',Ð         title:
'Quote',Ð         icon: { glyph: 'glyphicon glyphicon-comment', fa: 'fa fa-
quote-left', 'fa-3': 'icon-quote-left' },Ð         callback: function(e) {Ð
            // Prepend/Give - surround the selectionÐ           var chunk,
cursor, selected = e.getSelection(), content = e.getContent();Ð           //
transform selection and set the cursor into chunked textÐ           if
(selected.length === 0) {Ð             // Give extra wordÐ             chunk
= e.__localize('quote here');Ð             e.replaceSelection('> '+chunk);Ð
              // Set the cursorÐ             cursor = selected.start+2;Ð
            } else {Ð             if (selected.text.indexOf('\n') < 0) {Ð
                chunk = selected.text;Ð               e.replaceSelection('>
'+chunk);Ð               // Set the cursorÐ               cursor =
selected.start+2;Ð             } else {Ð               var list = [];Ð
                list = selected.text.split('\n');Ð               chunk =
list[0];Ð               $.each(list,function(k,v) {Ð                 list[k]
= '> '+v;Ð               });Ð
e.replaceSelection('\n\n'+list.join('\n'));Ð               // Set the cursorÐ
                cursor = selected.start+4;Ð             }Ð           }Ð
            // Set the cursorÐ
e.setSelection(cursor,cursor+chunk.length);Ð         }Ð       }]Ð     },{Ð
        name: 'groupUtil',Ð       data: [{Ð         name: 'cmdPreview',Ð
          toggle: true,Ð         hotkey: 'Ctrl+P',Ð         title: 'Preview',Ð
          btnText: 'Preview',Ð         btnClass: 'btn btn-primary btn-sm',Ð
          icon: { glyph: 'glyphicon glyphicon-search', fa: 'fa fa-search',
'fa-3': 'icon-search' },Ð         callback: function(e){Ð           // Check
the preview mode and toggle based on this flagÐ           var isPreview = e.
$isPreview,content;Ð           if (isPreview === false) {Ð             //
Give flag that tell the editor enter preview modeÐ
e.showPreview();Ð           } else {Ð             e.hidePreview();Ð
            }Ð         }Ð       }]Ð     }]Ð   ],Ð   additionalButtons:[], //
Place to hook more buttons by codeÐ   reorderButtonGroups:[],Ð
hiddenButtons:[], // Default hidden buttonsÐ   disabledButtons:[], // Default
disabled buttonsÐ   footer: '',Ð   fullscreen: {Ð     enable: true,Ð
icons: {Ð       fullscreenOn: {Ð         fa: 'fa fa-expand',Ð         glyph:
'glyphicon glyphicon-fullscreen',Ð         'fa-3': 'icon-resize-full'Ð
        },Ð       fullscreenOff: {Ð         fa: 'fa fa-compress',Ð
glyph: 'glyphicon glyphicon-fullscreen',Ð         'fa-3': 'icon-resize-small'Ð
        }Ð     }Ð   },Ð   /* Events hook */Ð   onShow: function (e) {},Ð
onPreview: function (e) {},Ð   onSave: function (e) {},Ð   onBlur: function
(e) {},Ð   onFocus: function (e) {},Ð   onChange: function(e) {},Ð
onFullscreen: function(e) {},Ð   onSelect: function (e) {}Ð };Ð
$.fn.markdown.Constructor = Markdown;Ð/* MARKDOWN NO CONFLICTÐ *
==================== */Ð $.fn.markdown.noConflict = function () {Ð
$.fn.markdown = old;Ð   return this;Ð };Ð /* MARKDOWN GLOBAL FUNCTION & DATA-
APIÐ * ==================================== */Ð var initMarkdown =
function(el) {Ð   var $this = el;Ð   if ($this.data('markdown')) {Ð
$this.data('markdown').showEditor();Ð     return;Ð   }Ð   $this.markdown()Ð };Ð
  var blurNonFocused = function(e) {Ð   var $activeElement =
$(document.activeElement);Ð   // Blur eventÐ   $(document).find('.md-
editor').each(function(){Ð     var $this             = $(this),Ð
focused          = $activeElement.closest('.md-editor')[0] === this,Ð
attachedMarkdown = $this.find('textarea').data('markdown') ||Ð
```

```
                              $this.find('div[data-provider="markdown-
preview"]').data('markdown');Ð     if (attachedMarkdown && !focused) {Ð
attachedMarkdown.blur();Ð     }Ð   })Ð };Ð $(document)Ð
    .on('click.markdown.data-api', '[data-provide="markdown-editable"]',
function (e) {Ð     initMarkdown($(this));Ð     e.preventDefault();Ð   })Ð
    .on('click focusin', function (e) {Ð     blurNonFocused(e);Ð   })Ð
    .ready(function(){Ð     $('textarea[data-
provide="markdown"]').each(function(){Ð       initMarkdown($(this));Ð     })Ð
    });Ð}));Ð
```

public\assets\js\plugins\bootstrap-markdown\markdown.js

```
// Released under MIT licenseØ/ Copyright (c) 2009-2010 Dominic BaggottØ/
Copyright (c) 2009-2010 Ash BerlinØ/ Copyright (c) 2011 Christoph Dorn
<christoph@christophdorn.com> (http://www.christophdorn.com)Ð
(function( expose ) {Ð   /**Ð    *  class MarkdownÐ    *Ð    *  Markdown
processing in Javascript done right. We have very particular viewsÐ    *  on
what constitutes 'right' which include:Ð    *Ð    *  - produces well-formed
HTML (this means that em and strong nesting isÐ    *    important)Ð    *Ð
*  - has an intermediate representation to allow processing of parsed data (WeÐ
     *    in fact have two, both as [JsonML]: a markdown tree and an HTML
tree).Ð    *Ð    *  - is easily extensible to add new dialects without having
to rewrite theÐ    *    entire parsing mechanicsÐ    *Ð    *  - has a good
test suiteÐ    *Ð    *  This implementation fulfills all of these (except
that the test suite couldÐ    *  do with expanding to automatically run all
the fixtures from other MarkdownÐ    *  implementations.)Ð    *Ð    *  #####
Intermediate RepresentationÐ    *Ð    *  *TODO* Talk about this :) Its
JsonML, but document the node names we use.Ð    *Ð    *  [JsonML]: http://
jsonml.org/ "JSON Markup Language"Ð    **/Ð   var Markdown = expose.Markdown
= function Markdown(dialect) {Ð       switch (typeof dialect) {Ð
case "undefined":Ð               this.dialect = Markdown.dialects.Gruber;Ð
                break;Ð           case "object":Ð               this.dialect
= dialect;Ð               break;Ð           default:Ð               if
(dialect in Markdown.dialects) {Ð                    this.dialect =
Markdown.dialects[dialect];Ð               }Ð               else {Ð
                    throw new Error("Unknown Markdown dialect '" +
String(dialect) + "'");Ð               }Ð               break;Ð       }Ð
        this.em_state = [];Ð       this.strong_state = [];Ð
this.debug_indent = "";Ð   };Ð   /**Ð    *  parse( markdown, [dialect] ) ->
JsonMLÐ    *  - markdown (String): markdown string to parseÐ    *  - dialect
(String | Dialect): the dialect to use, defaults to gruberÐ    *Ð    *  Parse
`markdown` and return a markdown document as a Markdown.JsonML tree.Ð    **/Ð
    expose.parse = function( source, dialect ) {Ð       // dialect will
default if undefinedÐ       var md = new Markdown( dialect );Ð       return
md.toTree( source );Ð   };Ð   /**Ð    *  toHTML( markdown, [dialect]  ) ->
StringÐ    *  toHTML( md_tree ) -> StringÐ    *  - markdown (String):
markdown string to parseÐ    *  - md_tree (Markdown.JsonML): parsed markdown
treeÐ    *Ð    *  Take markdown (either as a string or as a JsonML tree) and
run it throughÐ    *  [[toHTMLTree]] then turn it into a well-formated HTML
fragment.Ð    **/Ð   expose.toHTML = function toHTML( source , dialect ,
options ) {Ð       var input = expose.toHTMLTree( source , dialect ,
options );Ð       return expose.renderJsonML( input );Ð   };Ð   /**Ð    *
toHTMLTree( markdown, [dialect] ) -> JsonMLÐ    *  toHTMLTree( md_tree ) ->
JsonMLÐ    *  - markdown (String): markdown string to parseÐ    *  - dialect
(String | Dialect): the dialect to use, defaults to gruberÐ    *  - md_tree
(Markdown.JsonML): parsed markdown treeÐ    *Ð    *  Turn markdown into HTML,
represented as a JsonML tree. If a string is givenÐ    *  to this function,
it is first parsed into a markdown tree by callingÐ    *  [[parse]].Ð    **/Ð
    expose.toHTMLTree = function toHTMLTree( input, dialect , options ) {Ð
        // convert string input to an MD treeÐ       if ( typeof input
===="string" ) input = this.parse( input, dialect );Ð       // Now convert the
MD tree to an HTML treeÐ       // remove references from the treeÐ       var
attrs = extract_attr( input ),Ð           refs = {};Ð       if ( attrs &&
attrs.references ) {Ð           refs = attrs.references;Ð       }Ð       var
html = convert_tree_to_html( input, refs , options );Ð
merge_text_nodes( html );Ð       return html;Ð   };Ø/ For Spidermonkey based
enginesÐ   function mk_block_toSource() {Ð       return "Markdown.mk_block( "
+Ð           uneval(this.toString()) +Ð           ", " +Ð
uneval(this.trailing) +Ð           ", " +Ð           uneval(this.lineNumber) +Ð
            " )";Ð   }Ø/ nodeÐ   function mk_block_inspect() {Ð       var
util = require('util');Ð
```

```
                                return "Markdown.mk_block( " +Ð
util.inspect(this.toString()) +Ð           ", " +Ð
util.inspect(this.trailing) +Ð           ", " +Ð
util.inspect(this.lineNumber) +Ð           " )";Ð   }Ð   var mk_block =
Markdown.mk_block = function(block, trail, line) {Ð       // Be helpful for
default case in tests.Ð       if ( arguments.length == 1 ) trail = "\n\n";Ð
        var s = new String(block);Ð       s.trailing = trail;Ð       // To
make it clear its not just a stringÐ       s.inspect = mk_block_inspect;Ð
        s.toSource = mk_block_toSource;Ð       if (line != undefined)Ð
            s.lineNumber = line;Ð       return s;Ð   };Ð   function
count_lines( str ) {Ð       var n = 0, i = -1;Ð       while ( ( i =
str.indexOf('\n', i+1) ) !== -1) n++;Ð       return n;Ð   }Ð/ Internal -
split source into rough blocksÐ   Markdown.prototype.split_blocks = function
splitBlocks( input, startLine ) {Ð       // [\s\S] matches _anything_
(newline or space)Ð       var re = /([\s\S]+?)($|\n(?:\s*\n|$)+)/g,Ð
            blocks = [],Ð           m;Ð       var line_no = 1;Ð       if
( ( m = /^(\s*\n)/.exec(input) ) != null ) {Ð           // skip (but count)
leading blank linesÐ           line_no += count_lines( m[0] );Ð
re.lastIndex = m[0].length;Ð       }Ð       while ( ( m = re.exec(input) ) !
== null ) {Ð           blocks.push( mk_block( m[1], m[2], line_no ) );Ð
            line_no += count_lines( m[0] );Ð       }Ð       return blocks;Ð
    };Ð   /**Ð    *  Markdown#processBlock( block, next ) -> undefined |
[ JsonML, ... ]Ð    *  - block (String): the block to processÐ    *  - next
(Array): the following blocksÐ    *Ð    * Process `block` and return an array
of JsonML nodes representing `block`.Ð    *Ð    * It does this by asking each
block level function in the dialect to processÐ    * the block until one can.
Succesful handling is indicated by returning anÐ    * array (with zero or
more JsonML nodes), failure by a false value.Ð    *Ð    * Blocks handlers are
responsible for calling [[Markdown#processInline]]Ð    * themselves as
appropriate.Ð    *Ð    * If the blocks were split incorrectly or adjacent
blocks need collapsing youÐ    * can adjust `next` in place using shift/
splice etc.Ð    *Ð    * If any of this default behaviour is not right for the
dialect, you canÐ    * define a `__call__` method on the dialect that will
get invoked to handleÐ    * the block processing.Ð    */Ð
Markdown.prototype.processBlock = function processBlock( block, next ) {Ð
        var cbs = this.dialect.block,Ð           ord = cbs.__order__;Ð
if ( "__call__" in cbs ) {Ð           return cbs.__call__.call(this, block,
next);Ð       }Ð       for ( var i = 0; i < ord.length; i++ ) {Ð           //
D:this.debug( "Testing", ord[i] );Ð           var res =
cbs[ ord[i] ].call( this, block, next );Ð           if ( res ) {Ð
                //D:this.debug("  matched");Ð               if ( !
isArray(res) || ( res.length > 0 && !( isArray(res[0]) ) ) )Ð
                    this.debug(ord[i], "didn't return a proper array");Ð
                //D:this.debug( "" );Ð               return res;Ð           }Ð
        }Ð       // Uhoh! no match! Should we throw an error?Ð       return
[];Ð   };Ð   Markdown.prototype.processInline = function
processInline( block ) {Ð       return
this.dialect.inline.__call__.call( this, String( block ) );Ð   };Ð   /**Ð
*  Markdown#toTree( source ) -> JsonMLÐ    *  - source (String): markdown
source to parseÐ    *Ð    *  Parse `source` into a JsonML tree representing
the markdown document.Ð    **/Ð/ custom_tree means set this.tree to
`custom_tree` and restore old value on returnÐ   Markdown.prototype.toTree =
function toTree( source, custom_root ) {Ð       var blocks = source
instanceof Array ? source : this.split_blocks( source );Ð       // Make tree
a member variable so its easier to mess with in extensionsÐ       var
old_tree = this.tree;Ð       try {Ð           this.tree = custom_root ||
this.tree || [ "markdown" ];Ð           blocks:Ð               while
( blocks.length ) {Ð                   var b =
this.processBlock( blocks.shift(), blocks );Ð                   // Reference
blocks and the like won't return any contentÐ
```

```
                                                                if ( !
b.length ) continue blocks;Ð
this.tree.push.apply( this.tree, b );Ð                }Ð           return
this.tree;Ð       }Ð       finally {Ð           if ( custom_root ) {Ð
                this.tree = old_tree;Ð           }Ð       }Ð   };Ð// Noop by
defaultÐ   Markdown.prototype.debug = function () {Ð       var args =
Array.prototype.slice.call( arguments);Ð
args.unshift(this.debug_indent);Ð       if (typeof print !== "undefined")Ð
            print.apply( print, args );Ð       if (typeof console !==
"undefined" && typeof console.log !== "undefined")Ð
console.log.apply( null, args );Ð   }Ð
Markdown.prototype.loop_re_over_block = function( re, block, cb ) {Ð       //
Dont use /g regexps with thisÐ       var m,Ð           b = block.valueOf();Ð
        while ( b.length && (m = re.exec(b) ) != null) {Ð           b =
b.substr( m[0].length );Ð           cb.call(this, m);Ð       }Ð       return
b;Ð   };Ð   /**Ð    * Markdown.dialectsÐ    *Ð    * Namespace of built-in
dialects.Ð    **/Ð   Markdown.dialects = {};Ð   /**Ð    *
Markdown.dialects.GruberÐ    *Ð    * The default dialect that follows the
rules set out by John Gruber'sÐ    * markdown.pl as closely as possible. Well
actually we follow the behaviour ofÐ    * that script which in some places is
not exactly what the syntax web pageÐ    * says.Ð    **/Ð
Markdown.dialects.Gruber = {Ð       block: {Ð           atxHeader: function
atxHeader( block, next ) {Ð               var m = block.match( /
^(#{1,6})\s*(.*?)\s*#*\s*(?:\n|$)/ );Ð               if ( !m ) return
undefined;Ð               var header = [ "header", { level: m[ 1 ].length } ];Ð
                Array.prototype.push.apply(header,
this.processInline(m[ 2 ]));Ð               if ( m[0].length < block.length )Ð
                    next.unshift( mk_block( block.substr( m[0].length ),
block.trailing, block.lineNumber + 2 ) );Ð               return [ header ];Ð
            },Ð           setextHeader: function setextHeader( block, next ) {Ð
                var m = block.match( /^(.*)\n([-=])\2\2+(?:\n|$)/ );Ð
                if ( !m ) return undefined;Ð               var level =
( m[ 2 ] === "=" ) ? 1 : 2;Ð               var header = [ "header", { level :
level }, m[ 1 ] ];Ð               if ( m[0].length < block.length )Ð
                    next.unshift( mk_block( block.substr( m[0].length ),
block.trailing, block.lineNumber + 2 ) );Ð               return [ header ];Ð
            },Ð           code: function code( block, next ) {Ð
                // |    FooÐ               // |barÐ               // should
be a code block followed by a paragraph. FunÐ               //Ð
                // There might also be adjacent code block to merge.Ð
                var ret = [],Ð                   re = /^(?: {0,3}\t| {4})
(.*)\n?/,Ð                   lines;Ð               // 4 spaces + contentÐ
                if ( !block.match( re ) ) return undefined;Ð
block_search:Ð                   do {Ð                       // Now pull out
the rest of the linesÐ                       var b = this.loop_re_over_block(Ð
                            re, block.valueOf(), function( m )
{ ret.push( m[1] ); } );Ð                       if (b.length) {Ð
                            // Case alluded to in first comment. push it back
on as a new blockÐ                               next.unshift( mk_block(b,
block.trailing) );Ð                               break block_search;Ð
                        }Ð                       else if (next.length) {Ð
                            // Check the next block - it might be code tooÐ
                            if ( !next[0].match( re ) ) break block_search;Ð
                            // Pull how how many blanks lines follow - minus
two to account for .joinÐ                           ret.push
( block.trailing.replace(/[^\n]/g, '').substring(2) );Ð
                            block = next.shift();Ð                       }Ð
                        else {Ð                           break block_search;Ð
                        }Ð                   } while (true);Ð
return [ [ "code_block", ret.join("\n") ] ];Ð
```

```
                                                        },Ð
horizRule: function horizRule( block, next ) {Ð                // this needs
to find any hr in the block to handle abutting blocksÐ              var m =
block.match( /^(?:([\s\S]*?)\n)?[ \t]*([-_*])(?:[ \t]*\2){2,}[ \t]*(?:
\n([\s\S]*))?$/ );Ð                if ( !m ) {Ð                    return
undefined;Ð               }Ð               var jsonml = [ [ "hr" ] ];Ð
                // if there's a leading abutting block, process itÐ
                if ( m[ 1 ] ) {Ð
jsonml.unshift.apply( jsonml, this.processBlock( m[ 1 ], [] ) );Ð
                }Ð               // if there's a trailing abutting block,
stick it into nextÐ               if ( m[ 3 ] ) {Ð
next.unshift( mk_block( m[ 3 ] ) );Ð               }Ð               return
jsonml;Ð           },Ð           // There are two types of lists. Tight and
loose. Tight lists have no whitespaceÐ           // between the items (and
result in text just in the <li>) and loose lists,Ð           // which have an
empty line between list items, resulting in (one or more)Ð           //
paragraphs inside the <li>.Ð           //Ð           // There are all sorts
weird edge cases about the original markdown.pl'sÐ           // handling of
lists:Ð           //Ð           // * Nested lists are supposed to be indented
by four chars per level. ButÐ           //   if they aren't, you can get a
nested list by indenting by less thanÐ           //   four so long as the
indent doesn't match an indent of an existing listÐ           //   item in
the 'nest stack'.Ð           //Ð           // * The type of the list (bullet
or number) is controlled just by theÐ           //    first item at the
indent. Subsequent changes are ignored unless theyÐ           //    are for
nested listsÐ           //Ð           lists: (function( ) {Ð               //
Use a closure to hide a few variables.Ð               var any_list = "[*+-]|\
\d+\\.",Ð                   bullet_list = /[*+-]/,Ð
number_list = /\d+\./,Ð               // Capture leading indent as it matters
for determining nested lists.Ð                   is_list_re = new
RegExp( "^( {0,3})(" + any_list + ")[ \t]+" ),Ð                   indent_re =
"(?: {0,3}\\t| {4})";Ð               // TODO: Cache this regexp for certain
depths.Ð               // Create a regexp suitable for matching an li for a
given stack depthÐ               function regex_for_depth( depth ) {Ð
                    return new RegExp(Ð                        // m[1] =
indent, m[2] = list_typeÐ                        "(?:^(" + indent_re + "{0," +
depth + "} {0,3})(" + any_list + ")\\s+)|" +Ð                           //
m[3] = contÐ                        "(^" + indent_re + "{0," + (depth-1) + "}
[ ]{0,4})"Ð                   );Ð               }Ð               function
expand_tab( input ) {Ð                    return input.replace( / {0,3}\t/g,
"    " );Ð               }Ð               // Add inline content `inline` to
`li`. inline comes from processInlineÐ               // so is an array of
contentÐ               function add(li, loose, inline, nl) {Ð
                    if (loose) {Ð
li.push( [ "para" ].concat(inline) );Ð                        return;Ð
                    }Ð                    // Hmmm, should this be any block
level element or just paras?Ð                    var add_to = li[li.length -1]
instanceof Array && li[li.length - 1][0] == "para"Ð                        ?
li[li.length -1]Ð                        : li;Ð                    // If there
is already some content in this list, add the new line inÐ
if (nl && li.length > 1) inline.unshift(nl);Ð                    for (var i=0;
i < inline.length; i++) {Ð                        var what = inline[i],Ð
                        is_str = typeof what == "string";Ð
                        if (is_str && add_to.length > 1 && typeof
add_to[add_to.length-1] == "string" ) {Ð
add_to[ add_to.length-1 ] += what;Ð                        }Ð
                        else {Ð                        add_to.push( what );Ð
                        }Ð                    }Ð               }Ð
                // contained means have an indent greater than the current
one. OnÐ
```

```
                        // *every* line in the blockÐ                function
get_contained_blocks( depth, blocks ) {Ð                    var re = new
RegExp( "^(" + indent_re + "{" + depth + "}.*?\\n?)*$" ),Ð
                         replace = new RegExp("^" + indent_re + "{" + depth +
"}", "gm"),Ð                        ret = [];Ð                     while
( blocks.length > 0 ) {Ð                        if ( re.exec( blocks[0] ) ) {Ð
                             var b = blocks.shift(),Ð
                             // Now remove that indentÐ
                                 x = b.replace( replace, "");Ð
                             ret.push( mk_block( x, b.trailing,
b.lineNumber ) );Ð                        }Ð                        break;Ð
                    }Ð                    return ret;Ð                }Ð
                  // passed to stack.forEach to turn list items up the stack
into parasÐ                function paragraphify(s, i, stack) {Ð
                    var list = s.list;Ð                    var last_li =
list[list.length-1];Ð                    if (last_li[1] instanceof Array &&
last_li[1][0] == "para") {Ð                        return;Ð                    }Ð
                    if (i+1 == stack.length) {Ð                        // Last
stack frameÐ                        // Keep the same array, but replace the
contentsÐ
last_li.push( ["para"].concat( last_li.splice(1) ) );Ð                    }Ð
                    else {Ð                        var sublist = last_li.pop();Ð
                        last_li.push( ["para"].concat( last_li.splice(1) ),
sublist );Ð                    }Ð                }Ð                // The
matcher functionÐ                return function( block, next ) {Ð
                    var m = block.match( is_list_re );Ð                    if
( !m ) return undefined;Ð                    function make_list( m ) {Ð
                        var list = bullet_list.exec( m[2] )Ð
                            ? ["bulletlist"]Ð                        :
["numberlist"];Ð                        stack.push( { list: list, indent:
m[1] } );Ð                        return list;Ð                    }Ð
                    var stack = [], // Stack of lists for nesting.Ð
                        list = make_list( m ),Ð                        last_li,Ð
                        loose = false,Ð                        ret =
[ stack[0].list ],Ð                        i;Ð                    // Loop to
search over block looking for inner block elements and loose listsÐ
                    loose_search:Ð                        while( true ) {Ð
                             // Split into lines preserving new lines at end
of lineÐ                        var lines = block.split( /(?=\n)/ );Ð
                             // We have to grab all lines for a li and call
processInline on themÐ                        // once as there are some
inline things that can span lines.Ð                        var
li_accumulate = "";Ð                        // Loop over the lines in this
block looking for tight lists.Ð                        tight_search:Ð
                                 for (var line_no=0; line_no < lines.length;
line_no++) {Ð                        var nl = "",Ð
                                     l = lines[line_no].replace(/^\n/,
function(n) { nl = n; return ""; });Ð                        //
TODO: really should cache thisÐ                        var line_re
= regex_for_depth( stack.length );Ð                        m =
l.match( line_re );Ð                        //print( "line:",
uneval(l), "\nline match:", uneval(m) );Ð
                                     // We have a list itemÐ
                                     if ( m[1] !== undefined ) {Ð
                                         // Process the previous list item, if
anyÐ                                         if ( li_accumulate.length ) {Ð
                                             add( last_li, loose,
this.processInline( li_accumulate ), nl );Ð
                                             // Loose mode will have been
dealt with. Reset itÐ
```

```
                                                                    loose = false;Ð
                                                li_accumulate = "";Ð
                                            }Ð
                                            m[1] = expand_tab( m[1] );Ð
                                            var wanted_depth =
Math.floor(m[1].length/4)+1;Ð                                                   //
print( "want:", wanted_depth, "stack:", stack.length);Ð
                                            if ( wanted_depth > stack.length ) {Ð
                                                // Deep enough for a nested list
outrightÐ                                               //print ( "new nested
list" );Ð                                               list = make_list( m );Ð
                                                last_li.push( list );Ð
                                                last_li = list[1] =
[ "listitem" ];Ð                                           }Ð
                                            else {Ð
                                                // We aren't deep enough to be
strictly a new level. This isÐ                                                  //
where Md.pl goes nuts. If the indent matches a level in theÐ
                                                // stack, put it there, else put
it one deeper then theÐ                                         //
wanted_depth deserves.Ð                                         var found =
false;Ð                                                   for (i = 0; i <
stack.length; i++) {Ð                                                   if
( stack[ i ].indent != m[1] ) continue;Ð
                                                    list = stack[ i ].list;Ð
                                                    stack.splice( i+1 );Ð
                                                    found = true;Ð
                                                    break;Ð
                                                }Ð
                                                if (!found) {Ð
                                                    //print("not found. l:",
uneval(l));Ð                                                wanted_depth++;Ð
                                                    if (wanted_depth <=
stack.length) {Ð
stack.splice(wanted_depth);Ð
                                                        //print("Desired depth
now", wanted_depth, "stack:", stack.length);Ð
                                                        list =
stack[wanted_depth-1].list;Ð
                                                        //print("list:",
uneval(list) );Ð                                                    }Ð
                                                    else {Ð
                                                        //print ("made new stack
for messy indent");Ð                                                    list =
make_list(m);Ð
last_li.push(list);Ð                                                    }Ð
                                                }Ð
                                                //print( uneval(list), "last",
list === stack[stack.length-1].list );Ð
                                                last_li = [ "listitem" ];Ð
                                                list.push(last_li);Ð
                                            } // end depth of shenegainsÐ
                                            nl = "";Ð
                                        }Ð                                      //
Add contentÐ                                        if (l.length > m[0].length) {Ð
                                            li_accumulate += nl +
l.substr( m[0].length );Ð                                           }Ð
                                    } // tight_searchÐ
if ( li_accumulate.length ) {Ð                                   add( last_li,
loose, this.processInline( li_accumulate ), nl );Ð
```

```
                                // Loose mode will have been dealt with.
Reset itÐ                               loose = false;Ð
                                li_accumulate = "";Ð
                            }Ð                          // Look at the next
block - we might have a loose list. Or an extraÐ                          //
paragraph for the current liÐ                           var contained =
get_contained_blocks( stack.length, next );Ð                          //
Deal with code blocks or properly nested listsÐ                           if
(contained.length > 0) {Ð                               // Make sure all
listitems up the stack are paragraphsÐ
forEach( stack, paragraphify, this);Ð
last_li.push.apply( last_li, this.toTree( contained, [] ) );Ð
                            }Ð                          var next_block =
next[0] && next[0].valueOf() || "";Ð                          if
( next_block.match(is_list_re) || next_block.match( /^ / ) ) {Ð
                                block = next.shift();Ð
                                // Check for an HR following a list: features/
lists/hr_abuttingÐ                              var hr =
this.dialect.block.horizRule( block, next );Ð
if (hr) {Ð                                      ret.push.apply(ret, hr);Ð
                                    break;Ð                               }Ð
                                // Make sure all listitems up the stack are
paragraphsÐ                               forEach( stack, paragraphify, this);Ð
                                loose = true;Ð
continue loose_search;Ð                          }Ð
                            break;Ð                      } // loose_searchÐ
                    return ret;Ð              };Ð           })(),Ð
blockquote: function blockquote( block, next ) {Ð               if ( !
block.match( /^>/m ) )Ð                   return undefined;Ð
var jsonml = [];Ð               // separate out the leading abutting block,
if anyÐ               if ( block[ 0 ] != ">" ) {Ð                  var lines
= block.split( /\n/ ),Ð                       prev = [];Ð
                    // keep shifting lines until you find a crotchetÐ
                    while ( lines.length && lines[ 0 ][ 0 ] != ">" ) {Ð
                        prev.push( lines.shift() );Ð                  }Ð
                    // reassemble!Ð                     block =
lines.join( "\n" );Ð                   jsonml.push.apply( jsonml,
this.processBlock( prev.join( "\n" ), [] ) );Ð               }Ð
                // if the next block is also a blockquote merge it inÐ
                while ( next.length && next[ 0 ][ 0 ] == ">" ) {Ð
                    var b = next.shift();Ð                   block = new
String(block + block.trailing + b);Ð                   block.trailing =
b.trailing;Ð               }Ð               // Strip off the leading "> " and
re-process as a block.Ð               var input = block.replace( /^> ?/gm,
'' ),Ð                   old_tree = this.tree;Ð
jsonml.push( this.toTree( input, [ "blockquote" ] ) );Ð               return
jsonml;Ð           },Ð           referenceDefn: function
referenceDefn( block, next) {Ð               var re = /^\s*\[(.*?)\]:\s*(\S+)
(?:\s+(?:(['"])(.*?)\3|\((.*?)\)))?\n?/;Ð               // interesting
matches are [ , ref_id, url, , title, title ]Ð               if ( !
block.match(re) )Ð                   return undefined;Ð               // make
an attribute node if it doesn't existÐ               if ( !
extract_attr( this.tree ) ) {Ð                   this.tree.splice( 1, 0, {} );Ð
                }Ð               var attrs = extract_attr( this.tree );Ð
                // make a references hash if it doesn't existÐ
if ( attrs.references === undefined ) {Ð                   attrs.references =
{};Ð               }Ð               var b = this.loop_re_over_block(re,
block, function( m ) {Ð                   if ( m[2] && m[2][0] == '<' && m[2]
[m[2].length-1] == '>' )Ð
```

```
                                                    m[2] = m[2].substring( 1,
m[2].length - 1 );Ð                    var ref =
attrs.references[ m[1].toLowerCase() ] = {Ð                        href: m[2]Ð
                    };Ð                  if (m[4] !== undefined)Ð
                        ref.title = m[4];Ð                  else if (m[5] !
== undefined)Ð                      ref.title = m[5];Ð              } );Ð
                if (b.length)Ð                  next.unshift( mk_block( b,
block.trailing ) );Ð              return [];Ð           },Ð           para:
function para( block, next ) {Ð              // everything's a para!Ð
                return [ ["para"].concat( this.processInline( block ) ) ];Ð
            }Ð       }Ð   };Ð   Markdown.dialects.Gruber.inline = {Ð
__oneElement__: function oneElement( text, patterns_or_re, previous_nodes ) {Ð
            var m,Ð               res,Ð               lastIndex = 0;Ð
            patterns_or_re = patterns_or_re ||
this.dialect.inline.__patterns__;Ð           var re = new RegExp( "([\\s\
\S]*?)(" + (patterns_or_re.source || patterns_or_re) + ")" );Ð           m =
re.exec( text );Ð           if (!m) {Ð               // Just boring textÐ
                return [ text.length, text ];Ð           }Ð           else if
( m[1] ) {Ð               // Some un-interesting text matched. Return that
firstÐ               return [ m[1].length, m[1] ];Ð           }Ð
var res;Ð           if ( m[2] in this.dialect.inline ) {Ð               res =
this.dialect.inline[ m[2] ].call(Ð                   this,Ð
text.substr( m.index ), m, previous_nodes || [] );Ð           }Ð           //
Default for now to make dev easier. just slurp special and output it.Ð
            res = res || [ m[2].length, m[2] ];Ð           return res;Ð
        },Ð       __call__: function inline( text, patterns ) {Ð
var out = [],Ð               res;Ð           function add(x) {Ð
                //D:self.debug("  adding output", uneval(x));Ð
if (typeof x == "string" && typeof out[out.length-1] == "string")Ð
                    out[ out.length-1 ] += x;Ð               elseÐ
                    out.push(x);Ð           }Ð           while ( text.length
> 0 ) {Ð               res = this.dialect.inline.__oneElement__.call(this,
text, patterns, out );Ð               text = text.substr( res.shift() );Ð
                forEach(res, add )Ð           }Ð           return out;Ð
        },Ð       // These characters are intersting elsewhere, so have rules
for them so thatÐ       // chunks of plain text blocks don't include themÐ
        "]": function () {},Ð       "}": function () {},Ð       "\\":
function escaped( text ) {Ð           // [ length of input processed, node/
children to add... ]Ð           // Only esacape: \ ` * _ { } [ ] ( ) # * +
- . !Ð           if ( text.match( /^\\[\\`\*_{}\[\]()#\+.!\-]/ ) )Ð
                return [ 2, text[1] ];Ð           elseÐ           // Not an
esacpeÐ               return [ 1, "\\" ];Ð       },Ð       "![": function
image( text ) {Ð           // Unlike images, alt text is plain text only. no
other elements areÐ           // allowed in thereÐ           // ![Alt text](/
path/to/img.jpg "Optional title")Ð           //      1          2
3       4         <--- capturesÐ           var m = text.match( /^!\[(.*?)\]
[ \t]*\([ \t]*(\S*)(?:[ \t]+(["'])(.*?)\3)?[ \t]*\)/ );Ð           if ( m ) {Ð
                if ( m[2] && m[2][0] == '<' && m[2][m[2].length-1] == '>' )Ð
                    m[2] = m[2].substring( 1, m[2].length - 1 );Ð
                m[2] = this.dialect.inline.__call__.call( this, m[2], /\\/ )
[0];Ð               var attrs = { alt: m[1], href: m[2] || "" };Ð
                if ( m[4] !== undefined)Ð                   attrs.title =
m[4];Ð               return [ m[0].length, [ "img", attrs ] ];Ð           }Ð
            // ![Alt text][id]Ð           m = text.match( /^!\[(.*?)\]
[ \t]*\[(.*?)\]/ );Ð           if ( m ) {Ð               // We can't check if
the reference is known here as it likely wont beÐ               // found till
after. Check it in md tree->hmtl tree conversionÐ               return
[ m[0].length, [ "img_ref", { alt: m[1], ref: m[2].toLowerCase(), original:
m[0] } ] ];Ð           }Ð           // Just consume the '!['Ð
return [ 2, "![" ];Ð
```

```
                            },Ð       "[": function link( text ) {Ð
var orig = String(text);Ð           // Inline content is possible inside
`link text`Ð           var res =
Markdown.DialectHelpers.inline_until_char.call( this, text.substr(1), ']' );Ð
            // No closing ']' found. Just consume the [Ð           if ( !
res ) return [ 1, '[' ];Ð           var consumed = 1 + res[ 0 ],Ð
                children = res[ 1 ],Ð               link,Ð
attrs;Ð           // At this point the first [...] has been parsed. See what
follows to findÐ           // out which kind of link we are (reference or
direct url)Ð           text = text.substr( consumed );Ð           // [link
text](/path/to/img.jpg "Optional title")Ð           //
1            2       3         <--- capturesÐ           // This will capture
up to the last paren in the block. We then pullÐ           // back based on
if there a matching ones in the urlÐ           //    ([here](/url/(test))Ð
            // The parens have to be balancedÐ           var m = text.match( /
^\s*\([ \t]*(\S+)(?:[ \t]+(["']])(.*?)\2)?[ \t]*\)/ );Ð           if ( m ) {Ð
                var url = m[1];Ð               consumed += m[0].length;Ð
                if ( url && url[0] == '<' && url[url.length-1] == '>' )Ð
                    url = url.substring( 1, url.length - 1 );Ð
                // If there is a title we don't have to worry about parens in
the urlÐ               if ( !m[3] ) {Ð                   var open_parens =
1; // One open that isn't in the captureÐ                   for (var len = 0;
len < url.length; len++) {Ð                       switch ( url[len] ) {Ð
                            case '(':Ð
open_parens++;Ð                                   break;Ð
                            case ')':Ð                                if ( --
open_parens == 0) {Ð                                   consumed -= url.length
- len;Ð                                   url = url.substring(0, len);Ð
                                }Ð                                   break;Ð
                        }Ð                   }Ð               }Ð
                // Process escapes onlyÐ               url =
this.dialect.inline.__call__.call( this, url, /\\/ )[0];Ð               attrs
= { href: url || "" };Ð               if ( m[3] !== undefined)Ð
                    attrs.title = m[3];Ð               link = [ "link",
attrs ].concat( children );Ð               return [ consumed, link ];Ð
            }Ð           // [Alt text][id]Ð           // [Alt text] [id]Ð
            m = text.match( /^\s*\[(.*?)\]/ );Ð           if ( m ) {Ð
                consumed += m[ 0 ].length;Ð               // [links][] uses
links as its referenceÐ               attrs = { ref: ( m[ 1 ] ||
String(children) ).toLowerCase(),  original: orig.substr( 0, consumed ) };Ð
                link = [ "link_ref", attrs ].concat( children );Ð
                // We can't check if the reference is known here as it likely
wont beÐ               // found till after. Check it in md tree->hmtl tree
conversion.Ð               // Store the original so that conversion can
revert if the ref isn't found.Ð               return [ consumed, link ];Ð
            }Ð           // [id]Ð           // Only if id is plain (no
formatting.)Ð           if ( children.length == 1 && typeof children[0] ==
"string" ) {Ð               attrs = { ref: children[0].toLowerCase(),
original: orig.substr( 0, consumed ) };Ð               link = [ "link_ref",
attrs, children[0] ];Ð               return [ consumed, link ];Ð           }Ð
            // Just consume the '['Ð           return [ 1, "[" ];Ð       },Ð
        "<": function autoLink( text ) {Ð           var m;Ð           if
( ( m = text.match( /^<(?:((https?|ftp|mailto):[^>]+)|(.*?@.*?\.[a-zA-
Z]+))>/ ) ) != null ) {Ð               if ( m[3] ) {Ð
return [ m[0].length, [ "link", { href: "mailto:" + m[3] }, m[3] ] ];Ð
                }Ð               else if ( m[2] == "mailto" ) {Ð
                    return [ m[0].length, [ "link", { href: m[1] },
m[1].substr("mailto:".length ) ] ];Ð               }Ð               elseÐ
                    return [ m[0].length, [ "link", { href: m[1] }, m[1] ] ];Ð
            }Ð
```

```
            Ð           return [ 1, "<" ];Ð       },Ð       "`": function
inlineCode( text ) {Ð           // Inline code block. as many backticks as
you like to start itÐ           // Always skip over the opening ticks.Ð
            var m = text.match( /(`+)(([\s\S]*?)\1)/ );Ð           if ( m &&
m[2] )Ð               return [ m[1].length + m[2].length, [ "inlinecode",
m[3] ] ];Ð           else {Ð               // TODO: No matching end code
found - warn!Ð               return [ 1, "`" ];Ð           }Ð       },Ð
"  \n": function lineBreak( text ) {Ð           return [ 3, [ "linebreak" ] ];Ð
        }Ð   };Ð// Meta Helper/generator method for em and strong handlingÐ
function strong_em( tag, md ) {Ð       var state_slot = tag + "_state",Ð
            other_slot = tag == "strong" ? "em_state" : "strong_state";Ð
        function CloseTag(len) {Ð           this.len_after = len;Ð
this.name = "close_" + md;Ð       }Ð       return function ( text,
orig_match ) {Ð           if (this[state_slot][0] == md) {Ð               //
Most recent em is of this typeÐ               //D:this.debug("closing", md);Ð
                this[state_slot].shift();Ð               // "Consume"
everything to go back to the recrusion in the else-block belowÐ
return[ text.length, new CloseTag(text.length-md.length) ];Ð           }Ð
            else {Ð               // Store a clone of the em/strong statesÐ
                var other = this[other_slot].slice(),Ð
state = this[state_slot].slice();Ð               this[state_slot].unshift(md);Ð
                //D:this.debug_indent += "  ";Ð               // RecurseÐ
                var res = this.processInline( text.substr( md.length ) );Ð
                //D:this.debug_indent = this.debug_indent.substr(2);Ð
                var last = res[res.length - 1];Ð               //
D:this.debug("processInline from", tag + ": ", uneval( res ) );Ð
                var check = this[state_slot].shift();Ð               if (last
instanceof CloseTag) {Ð                   res.pop();Ð                   // We
matched! Huzzah.Ð                   var consumed = text.length -
last.len_after;Ð                   return [ consumed, [ tag ].concat(res) ];Ð
                }Ð               else {Ð                   // Restore the
state of the other kind. We might have mistakenly closed it.Ð
                    this[other_slot] = other;Ð
this[state_slot] = state;Ð                   // We can't reuse the processed
result as it could have wrong parsing contexts in it.Ð
return [ md.length, md ];Ð               }Ð           }Ð       }; // End
returned functionÐ   }Ð   Markdown.dialects.Gruber.inline["**"] =
strong_em("strong", "**");Ð   Markdown.dialects.Gruber.inline["__"] =
strong_em("strong", "__");Ð   Markdown.dialects.Gruber.inline["*"]  =
strong_em("em", "*");Ð   Markdown.dialects.Gruber.inline["_"]  =
strong_em("em", "_");Ð// Build default order from insertion order.Ð
Markdown.buildBlockOrder = function(d) {Ð       var ord = [];Ð       for
( var i in d ) {Ð           if ( i == "__order__" || i == "__call__" )
continue;Ð           ord.push( i );Ð       }Ð       d.__order__ = ord;Ð   };Ð
// Build patterns for inline matcherÐ   Markdown.buildInlinePatterns =
function(d) {Ð       var patterns = [];Ð       for ( var i in d ) {Ð
            // __foo__ is reserved and not a patternÐ           if
( i.match( /^__.*__$/) ) continue;Ð           var l = i.replace( /([\\.*+?|
()\[\]{}])/g, "\\$1" )Ð               .replace( /\n/, "\\n" );Ð
patterns.push( i.length == 1 ? l : "(?:" + l + ")" );Ð       }Ð
patterns = patterns.join("|");Ð       d.__patterns__ = patterns;Ð       //
print("patterns:", uneval( patterns ) );Ð       var fn = d.__call__;Ð
d.__call__ = function(text, pattern) {Ð           if (pattern != undefined) {Ð
                return fn.call(this, text, pattern);Ð           }Ð
elseÐ           {Ð               return fn.call(this, text, patterns);Ð
            }Ð       };Ð   };Ð   Markdown.DialectHelpers = {};Ð
Markdown.DialectHelpers.inline_until_char = function( text, want ) {Ð
var consumed = 0,Ð           nodes = [];Ð       while ( true ) {Ð
if ( text[ consumed ] == want ) {Ð               // Found the character we
were looking forÐ
```

```
                                consumed++;Ð                return [ consumed,
nodes ];Ð           }Ð           if ( consumed >= text.length ) {Ð
              // No closing char found. Abort.Ð                return null;Ð
            }Ð           var res =
this.dialect.inline.__oneElement__.call(this, text.substr( consumed ) );Ð
            consumed += res[ 0 ];Ð           // Add any returned nodes.Ð
            nodes.push.apply( nodes, res.slice( 1 ) );Ð       }Ð   }Ð// Helper
function to make sub-classing a dialect easierÐ   Markdown.subclassDialect =
function( d ) {Ð       function Block() {}Ð       Block.prototype = d.block;Ð
        function Inline() {}Ð       Inline.prototype = d.inline;Ð
return { block: new Block(), inline: new Inline() };Ð   };Ð
Markdown.buildBlockOrder ( Markdown.dialects.Gruber.block );Ð
Markdown.buildInlinePatterns( Markdown.dialects.Gruber.inline );Ð
Markdown.dialects.Maruku =
Markdown.subclassDialect( Markdown.dialects.Gruber );Ð
Markdown.dialects.Maruku.processMetaHash = function
processMetaHash( meta_string ) {Ð       var meta =
split_meta_hash( meta_string ),Ð           attr = {};Ð       for ( var i = 0;
i < meta.length; ++i ) {Ð           // id: #fooÐ           if ( /
^#/.test( meta[ i ] ) ) {Ð               attr.id = meta[ i ].substring( 1 );Ð
            }Ð           // class: .fooÐ           else if ( /
^\./.test( meta[ i ] ) ) {Ð               // if class already exists, append
the new oneÐ               if ( attr['class'] ) {Ð
attr['class'] = attr['class'] + meta[ i ].replace( /./, " " );Ð
                }Ð               else {Ð                   attr['class'] =
meta[ i ].substring( 1 );Ð               }Ð           }Ð           //
attribute: foo=barÐ           else if ( /\=/.test( meta[ i ] ) ) {Ð
                var s = meta[ i ].split( /\=/ );Ð
attr[ s[ 0 ] ] = s[ 1 ];Ð           }Ð       }Ð       return attr;Ð   }Ð
function split_meta_hash( meta_string ) {Ð       var meta =
meta_string.split( "" ),Ð           parts = [ "" ],Ð           in_quotes =
false;Ð       while ( meta.length ) {Ð           var letter = meta.shift();Ð
            switch ( letter ) {Ð               case " " :Ð
                    // if we're in a quoted section, keep itÐ
                    if ( in_quotes ) {Ð
parts[ parts.length - 1 ] += letter;Ð                   }Ð
                    // otherwise make a new partÐ                   else {Ð
                        parts.push( "" );Ð                   }Ð
                    break;Ð               case "'" :Ð               case '"' :Ð
                    // reverse the quotes and move straight onÐ
                    in_quotes = !in_quotes;Ð                   break;Ð
                case "\\" :Ð                   // shift off the next letter
to be used straight away.Ð                   // it was escaped so we'll keep
it whatever it isÐ                   letter = meta.shift();Ð
default :Ð                   parts[ parts.length - 1 ] += letter;Ð
                    break;Ð           }Ð       }Ð       return parts;Ð   }Ð
Markdown.dialects.Maruku.block.document_meta = function document_meta( block,
next ) {Ð       // we're only interested in the first blockÐ       if
( block.lineNumber > 1 ) return undefined;Ð       // document_meta blocks
consist of one or more lines of `Key: Value\n`Ð       if ( ! block.match( /
^(?:\w+:.*\n)*\w+:.*$/ ) ) return undefined;Ð       // make an attribute node
if it doesn't existÐ       if ( !extract_attr( this.tree ) ) {Ð
this.tree.splice( 1, 0, {} );Ð       }Ð       var pairs = block.split( /\n/ );Ð
        for ( p in pairs ) {Ð           var m = pairs[ p ].match( /(\w+):
\s*(.*)$/ ),Ð               key = m[ 1 ].toLowerCase(),Ð               value
= m[ 2 ];Ð           this.tree[ 1 ][ key ] = value;Ð       }Ð       //
document_meta produces no content!Ð       return [];Ð   };Ð
Markdown.dialects.Maruku.block.block_meta = function block_meta( block,
next ) {Ð       // check if the last line of the block is an meta hashÐ
var m = block.match( /(^|\n) {0,3}\{:\s*((?:\\\}|[^\}])*)\s*\}$/ );Ð
```

```
                                                                    if
( !m ) return undefined;Ð       // process the meta hashÐ       var attr =
this.dialect.processMetaHash( m[ 2 ] );Ð       var hash;Ð       // if we
matched ^ then we need to apply meta to the previous blockÐ       if ( m[ 1 ]
=== "" ) {Ð           var node = this.tree[ this.tree.length - 1 ];Ð
            hash = extract_attr( node );Ð           // if the node is a
string (rather than JsonML), bailÐ           if ( typeof node === "string" )
return undefined;Ð           // create the attribute hash if it doesn't existÐ
            if ( !hash ) {Ð               hash = {};Ð
node.splice( 1, 0, hash );Ð           }Ð           // add the attributes inÐ
            for ( a in attr ) {Ð               hash[ a ] = attr[ a ];Ð
            }Ð           // return nothing so the meta hash is removedÐ
            return [];Ð       }Ð       // pull the meta hash off the block
and process what's leftÐ       var b = block.replace( /\n.*$/, "" ),Ð
            result = this.processBlock( b, [] );Ð       // get or make the
attributes hashÐ       hash = extract_attr( result[ 0 ] );Ð       if ( !
hash ) {Ð           hash = {};Ð           result[ 0 ].splice( 1, 0, hash );Ð
        }Ð       // attach the attributes to the blockÐ       for ( a in
attr ) {Ð           hash[ a ] = attr[ a ];Ð       }Ð       return result;Ð
    };Ð   Markdown.dialects.Maruku.block.definition_list = function
definition_list( block, next ) {Ð       // one or more terms followed by one
or more definitions, in a single blockÐ       var tight = /^((?:[^\s:].*\n)+):
\s+([\s\S]+)$/,Ð           list = [ "dl" ],Ð           i;Ð       // see if
we're dealing with a tight or loose blockÐ       if ( ( m =
block.match( tight ) ) ) {Ð           // pull subsequent tight DL blocks out
of `next`Ð           var blocks = [ block ];Ð           while ( next.length
&& tight.exec( next[ 0 ] ) ) {Ð               blocks.push( next.shift() );Ð
            }Ð           for ( var b = 0; b < blocks.length; ++b ) {Ð
                var m = blocks[ b ].match( tight ),Ð                   terms
= m[ 1 ].replace( /\n$/, "" ).split( /\n/ ),Ð                   defns =
m[ 2 ].split( /\n:\s+/ );Ð               // print( uneval( m ) );Ð
                for ( i = 0; i < terms.length; ++i ) {Ð
list.push( [ "dt", terms[ i ] ] );Ð               }Ð               for ( i =
0; i < defns.length; ++i ) {Ð                   // run inline processing over
the definitionÐ
list.push( [ "dd" ].concat( this.processInline( defns[ i ].replace( /
(\n)\s+/, "$1" ) ) ) );Ð               }Ð           }Ð       }Ð       else {Ð
            return undefined;Ð       }Ð       return [ list ];Ð   };Ð
Markdown.dialects.Maruku.inline[ "{:" ] = function inline_meta( text,
matches, out ) {Ð       if ( !out.length ) {Ð           return [ 2, "{:" ];Ð
        }Ð       // get the preceeding elementÐ       var before =
out[ out.length - 1 ];Ð       if ( typeof before === "string" ) {Ð
return [ 2, "{:" ];Ð       }Ð       // match a meta hashÐ       var m =
text.match( /^\{:\s*((?:\\\}|[^\}])*)\s*\}/ );Ð       // no match, false alarmÐ
        if ( !m ) {Ð           return [ 2, "{:" ];Ð       }Ð       // attach
the attributes to the preceeding elementÐ       var meta =
this.dialect.processMetaHash( m[ 1 ] ),Ð           attr =
extract_attr( before );Ð       if ( !attr ) {Ð           attr = {};Ð
            before.splice( 1, 0, attr );Ð       }Ð       for ( var k in
meta ) {Ð           attr[ k ] = meta[ k ];Ð       }Ð       // cut out the
string and replace it with nothingÐ       return [ m[ 0 ].length, "" ];Ð   };Ð
    Markdown.buildBlockOrder ( Markdown.dialects.Maruku.block );Ð
Markdown.buildInlinePatterns( Markdown.dialects.Maruku.inline );Ð   var
isArray = Array.isArray || function(obj) {Ð           return
Object.prototype.toString.call(obj) == '[object Array]';Ð       };Ð   var
forEach;Ø/ Don't mess with Array.prototype. Its not friendlyÐ   if
( Array.prototype.forEach ) {Ð       forEach = function( arr, cb, thisp ) {Ð
            return arr.forEach( cb, thisp );Ð       };Ð   }Ð   else {Ð
forEach = function(arr, cb, thisp) {Ð           for (var i = 0; i <
arr.length; i++) {Ð
```

```
                                    cb.call(thisp || arr, arr[i], i, arr);Ð
            }Ð       }Ð   }Ð   function extract_attr( jsonml ) {Ð
return isArray(jsonml)Ð       && jsonml.length > 1Ð       && typeof
jsonml[ 1 ] === "object"Ð       && !( isArray(jsonml[ 1 ]) )Ð           ?
jsonml[ 1 ]Ð           : undefined;Ð   }Ð   /**Ð    *  renderJsonML( jsonml[,
options] ) -> StringÐ    *  - jsonml (Array): JsonML array to render to XMLÐ
     *  - options (Object): optionsÐ    *Ð    *  Converts the given JsonML
into well-formed XML.Ð    *Ð    *  The options currently understood are:Ð    *Ð
     *  - root (Boolean): wether or not the root node should be included in
theÐ    *    output, or just its children. The default `false` is to not
include theÐ    *    root itself.Ð    */Ð   expose.renderJsonML =
function( jsonml, options ) {Ð       options = options || {};Ð       //
include the root element in the rendered output?Ð       options.root =
options.root || false;Ð       var content = [];Ð       if ( options.root ) {Ð
            content.push( render_tree( jsonml ) );Ð       }Ð       else {Ð
            jsonml.shift(); // get rid of the tagÐ           if
( jsonml.length && typeof jsonml[ 0 ] === "object" && !( jsonml[ 0 ]
instanceof Array ) ) {Ð               jsonml.shift(); // get rid of the
attributesÐ           }Ð           while ( jsonml.length ) {Ð
content.push( render_tree( jsonml.shift() ) );Ð           }Ð       }Ð
return content.join( "\n\n" );Ð   };Ð   function escapeHTML( text ) {Ð
return text.replace( /&/g, "&amp;" )Ð           .replace( /</g, "&lt;" )Ð
            .replace( />/g, "&gt;" )Ð           .replace( /"/g, "&quot;" )Ð
            .replace( /'/g, "&#39;" );Ð   }Ð   function render_tree( jsonml )
{Ð       // basic caseÐ       if ( typeof jsonml === "string" ) {Ð
return escapeHTML( jsonml );Ð       }Ð       var tag = jsonml.shift(),Ð
            attributes = {},Ð           content = [];Ð       if
( jsonml.length && typeof jsonml[ 0 ] === "object" && !( jsonml[ 0 ]
instanceof Array ) ) {Ð           attributes = jsonml.shift();Ð       }Ð
        while ( jsonml.length ) {Ð
content.push( arguments.callee( jsonml.shift() ) );Ð       }Ð       var
tag_attrs = "";Ð       for ( var a in attributes ) {Ð           tag_attrs +=
" " + a + '="' + escapeHTML( attributes[ a ] ) + '"';Ð       }Ð       // be
careful about adding whitespace here for inline elementsÐ       if ( tag ==
"img" || tag == "br" || tag == "hr" ) {Ð           return "<"+ tag +
tag_attrs + "/>";Ð       }Ð       else {Ð           return "<"+ tag +
tag_attrs + ">" + content.join( "" ) + "</" + tag + ">";Ð       }Ð   }Ð
function convert_tree_to_html( tree, references, options ) {Ð       var i;Ð
        options = options || {};Ð       // shallow cloneÐ       var jsonml =
tree.slice( 0 );Ð       if (typeof options.preprocessTreeNode === "function")
{Ð           jsonml = options.preprocessTreeNode(jsonml, references);Ð       }Ð
        // Clone attributes if they existÐ       var attrs =
extract_attr( jsonml );Ð       if ( attrs ) {Ð           jsonml[ 1 ] = {};Ð
            for ( i in attrs ) {Ð               jsonml[ 1 ][ i ] = attrs[ i ];Ð
            }Ð           attrs = jsonml[ 1 ];Ð       }Ð       // basic caseÐ
        if ( typeof jsonml === "string" ) {Ð           return jsonml;Ð       }Ð
        // convert this nodeÐ       switch ( jsonml[ 0 ] ) {Ð           case
"header":Ð               jsonml[ 0 ] = "h" + jsonml[ 1 ].level;Ð
                delete jsonml[ 1 ].level;Ð               break;Ð
case "bulletlist":Ð               jsonml[ 0 ] = "ul";Ð               break;Ð
            case "numberlist":Ð               jsonml[ 0 ] = "ol";Ð
                break;Ð           case "listitem":Ð               jsonml[ 0 ]
= "li";Ð               break;Ð           case "para":Ð
jsonml[ 0 ] = "p";Ð               break;Ð           case "markdown":Ð
                jsonml[ 0 ] = "html";Ð               if ( attrs ) delete
attrs.references;Ð               break;Ð           case "code_block":Ð
                jsonml[ 0 ] = "pre";Ð               i = attrs ? 2 : 1;Ð
                var code = [ "code" ];Ð               code.push.apply( code,
jsonml.splice( i ) );Ð               jsonml[ i ] = code;Ð               break;Ð
            case "inlinecode":Ð
```

```
                                                jsonml[ 0 ] = "code";Ð
                break;Ð           case "img":Ð                jsonml[ 1 ].src
= jsonml[ 1 ].href;Ð               delete jsonml[ 1 ].href;Ð
break;Ð           case "linebreak":Ð               jsonml[ 0 ] = "br";Ð
                break;Ð           case "link":Ð                jsonml[ 0 ] =
"a";Ð               break;Ð           case "link_ref":Ð
jsonml[ 0 ] = "a";Ð               // grab this ref and clean up the attribute
nodeÐ               var ref = references[ attrs.ref ];Ð               // if
the reference exists, make the linkÐ               if ( ref ) {Ð
                    delete attrs.ref;Ð                    // add in the href
and title, if presentÐ                    attrs.href = ref.href;Ð
                    if ( ref.title ) {Ð                    attrs.title =
ref.title;Ð                    }Ð                    // get rid of the unneeded
original textÐ                    delete attrs.original;Ð               }Ð
                // the reference doesn't exist, so revert to plain textÐ
                else {Ð                    return attrs.original;Ð
                }Ð               break;Ð           case "img_ref":Ð
                jsonml[ 0 ] = "img";Ð               // grab this ref and
clean up the attribute nodeÐ               var ref = references[ attrs.ref ];Ð
                // if the reference exists, make the linkÐ               if
( ref ) {Ð                    delete attrs.ref;Ð                    // add in
the href and title, if presentÐ                    attrs.src = ref.href;Ð
                    if ( ref.title ) {Ð                    attrs.title =
ref.title;Ð                    }Ð                    // get rid of the unneeded
original textÐ                    delete attrs.original;Ð               }Ð
                // the reference doesn't exist, so revert to plain textÐ
                else {Ð                    return attrs.original;Ð
                }Ð               break;Ð       }Ð       // convert all the
childrenÐ       i = 1;Ð       // deal with the attribute node, if it existsÐ
        if ( attrs ) {Ð           // if there are keys, skip over itÐ
            for ( var key in jsonml[ 1 ] ) {Ð               i = 2;Ð
            }Ð           // if there aren't, remove itÐ           if ( i ===
1 ) {Ð               jsonml.splice( i, 1 );Ð           }Ð       }Ð       for
( ; i < jsonml.length; ++i ) {Ð           jsonml[ i ] =
arguments.callee( jsonml[ i ], references, options );Ð       }Ð       return
jsonml;Ð   }Ø/ merges adjacent text nodes into a single nodeÐ   function
merge_text_nodes( jsonml ) {Ð       // skip the tag name and attribute hashÐ
        var i = extract_attr( jsonml ) ? 2 : 1;Ð       while ( i <
jsonml.length ) {Ð           // if it's a string check the next item tooÐ
            if ( typeof jsonml[ i ] === "string" ) {Ð               if ( i +
1 < jsonml.length && typeof jsonml[ i + 1 ] === "string" ) {Ð
                    // merge the second string into the first and remove itÐ
                    jsonml[ i ] += jsonml.splice( i + 1, 1 )[ 0 ];Ð
                }Ð               else {Ð                    ++i;Ð
                }Ð           }Ð           // if it's not a string recurseÐ
            else {Ð               arguments.callee( jsonml[ i ] );Ð
                ++i;Ð           }Ð       }Ð   }Ð )( (function() {Ð   if
( typeof exports === "undefined" ) {Ð       window.markdown = {};Ð
return window.markdown;Ð   }Ð   else {Ð       return exports;Ð   }Ð )() );
```

public\assets\js\plugins\chosen\chosen.jquery.js

```
/*!ÐChosen, a Select Box Enhancer for jQuery and PrototypeÐby Patrick Filler
for Harvest, http://getharvest.comÐVersion 1.1.0ÐFull source at https://
github.com/harvesthq/chosenÐCopyright (c) 2011 Harvest http://getharvest.comÐ
MIT License, https://github.com/harvesthq/chosen/blob/master/LICENSE.mdÐThis
file is generated by `grunt build`, do not edit it by hand.Ð*/Ð(function() {Ð
    var $, AbstractChosen, Chosen, SelectParser, _ref,Ð       __hasProp =
{}.hasOwnProperty,Ð       __extends = function(child, parent) { for (var key
in parent) { if (__hasProp.call(parent, key)) child[key] = parent[key]; }
function ctor() { this.constructor = child; } ctor.prototype =
parent.prototype; child.prototype = new ctor(); child.__super__ =
parent.prototype; return child; };Ð   SelectParser = (function() {Ð
function SelectParser() {Ð           this.options_index = 0;Ð
this.parsed = [];Ð       }Ð       SelectParser.prototype.add_node =
function(child) {Ð           if (child.nodeName.toUpperCase() === "OPTGROUP")
{Ð               return this.add_group(child);Ð           } else {Ð
                return this.add_option(child);Ð           }Ð       };Ð
SelectParser.prototype.add_group = function(group) {Ð           var
group_position, option, _i, _len, _ref, _results;Ð           group_position =
this.parsed.length;Ð           this.parsed.push({Ð               array_index:
group_position,Ð               group: true,Ð               label:
this.escapeExpression(group.label),Ð               children: 0,Ð
                disabled: group.disabledÐ           });Ð           _ref =
group.childNodes;Ð           _results = [];Ð           for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð               option = _ref[_i];Ð
                _results.push(this.add_option(option, group_position,
group.disabled));Ð           }Ð           return _results;Ð       };Ð
SelectParser.prototype.add_option = function(option, group_position,
group_disabled) {Ð           if (option.nodeName.toUpperCase() === "OPTION") {Ð
                if (option.text !== "") {Ð                    if
(group_position != null) {Ð
this.parsed[group_position].children += 1;Ð                    }Ð
                    this.parsed.push({Ð                        array_index:
this.parsed.length,Ð                        options_index: this.options_index,Ð
                        value: option.value,Ð                        text:
option.text,Ð                        html: option.innerHTML,Ð
                        selected: option.selected,Ð
disabled: group_disabled === true ? group_disabled : option.disabled,Ð
                        group_array_index: group_position,Ð
                        classes: option.className,Ð
style: option.style.cssTextÐ                    });Ð               } else {Ð
                    this.parsed.push({Ð                        array_index:
this.parsed.length,Ð                        options_index: this.options_index,Ð
                        empty: trueÐ                    });Ð               }Ð
                return this.options_index += 1;Ð           }Ð       };Ð
SelectParser.prototype.escapeExpression = function(text) {Ð           var
map, unsafe_chars;Ð           if ((text == null) || text === false) {Ð
                return "";Ð           }Ð           if (!/
[\&\<\>\"\'\`]/.test(text)) {Ð               return text;Ð           }Ð
            map = {Ð               "<": "&lt;",Ð               ">": "&gt;",Ð
                '"': "&quot;",Ð               "'": "&#x27;",Ð
"`": "&#x60;"Ð           };Ð           unsafe_chars = /&(?!\w+;)|[\<\>\"\'\`]/
g;Ð           return text.replace(unsafe_chars, function(chr) {Ð
                return map[chr] || "&amp;";Ð           });Ð       };Ð
return SelectParser;Ð   })();Ð   SelectParser.select_to_array =
function(select) {Ð       var child, parser, _i, _len, _ref;Ð       parser =
new SelectParser();Ð       _ref = select.childNodes;Ð       for (_i = 0, _len
= _ref.length; _i < _len; _i++) {Ð           child = _ref[_i];Ð
parser.add_node(child);Ð       }Ð       return parser.parsed;Ð   };Ð
AbstractChosen = (function() {Ð
```

```
                                        function AbstractChosen(form_field,
options) {Ð           this.form_field = form_field;Ð           this.options =
options != null ? options : {};Ð           if (!
AbstractChosen.browser_is_supported()) {Ð               return;Ð           }Ð
            this.is_multiple = this.form_field.multiple;Ð
this.set_default_text();Ð           this.set_default_values();Ð
this.setup();Ð           this.set_up_html();Ð
this.register_observers();Ð       }Ð
AbstractChosen.prototype.set_default_values = function() {Ð           var
_this = this;Ð           this.click_test_action = function(evt) {Ð
                return _this.test_active_click(evt);Ð           };Ð
this.activate_action = function(evt) {Ð               return
_this.activate_field(evt);Ð           };Ð           this.active_field = false;Ð
            this.mouse_on_container = false;Ð           this.results_showing
= false;Ð           this.result_highlighted = null;Ð
this.allow_single_deselect = (this.options.allow_single_deselect != null) &&
(this.form_field.options[0] != null) && this.form_field.options[0].text ===
"" ? this.options.allow_single_deselect : false;Ð
this.disable_search_threshold = this.options.disable_search_threshold || 0;Ð
            this.disable_search = this.options.disable_search || false;Ð
            this.enable_split_word_search =
this.options.enable_split_word_search != null ?
this.options.enable_split_word_search : true;Ð           this.group_search =
this.options.group_search != null ? this.options.group_search : true;Ð
            this.search_contains = this.options.search_contains || false;Ð
            this.single_backstroke_delete =
this.options.single_backstroke_delete != null ?
this.options.single_backstroke_delete : true;Ð
this.max_selected_options = this.options.max_selected_options || Infinity;Ð
            this.inherit_select_classes = this.options.inherit_select_classes
|| false;Ð           this.display_selected_options =
this.options.display_selected_options != null ?
this.options.display_selected_options : true;Ð           return
this.display_disabled_options = this.options.display_disabled_options !=
null ? this.options.display_disabled_options : true;Ð       };Ð
AbstractChosen.prototype.set_default_text = function() {Ð           if
(this.form_field.getAttribute("data-placeholder")) {Ð
this.default_text = this.form_field.getAttribute("data-placeholder");Ð
            } else if (this.is_multiple) {Ð               this.default_text =
this.options.placeholder_text_multiple || this.options.placeholder_text ||
AbstractChosen.default_multiple_text;Ð           } else {Ð
this.default_text = this.options.placeholder_text_single ||
this.options.placeholder_text || AbstractChosen.default_single_text;Ð
            }Ð           return this.results_none_found =
this.form_field.getAttribute("data-no_results_text") ||
this.options.no_results_text || AbstractChosen.default_no_result_text;Ð
        };Ð       AbstractChosen.prototype.mouse_enter = function() {Ð
            return this.mouse_on_container = true;Ð       };Ð
AbstractChosen.prototype.mouse_leave = function() {Ð           return
this.mouse_on_container = false;Ð       };Ð
AbstractChosen.prototype.input_focus = function(evt) {Ð           var _this =
this;Ð           if (this.is_multiple) {Ð               if (!
this.active_field) {Ð                   return setTimeout((function() {Ð
                        return _this.container_mousedown();Ð
                    }), 50);Ð               }Ð           } else {Ð
                if (!this.active_field) {Ð                   return
this.activate_field();Ð               }Ð           }Ð       };Ð
AbstractChosen.prototype.input_blur = function(evt) {Ð           var _this =
this;Ð           if (!this.mouse_on_container) {Ð
this.active_field = false;Ð
```

```
                                        return setTimeout((function() {Ð
                    return _this.blur_test();Ð                }), 100);Ð
            }Ð       };Ð       AbstractChosen.prototype.results_option_build
= function(options) {Ð           var content, data, _i, _len, _ref;Ð
            content = '';Ð           _ref = this.results_data;Ð           for
(_i = 0, _len = _ref.length; _i < _len; _i++) {Ð                data =
_ref[_i];Ð               if (data.group) {Ð                    content +=
this.result_add_group(data);Ð               } else {Ð
content += this.result_add_option(data);Ð               }Ð               if
(options != null ? options.first : void 0) {Ð                    if
(data.selected && this.is_multiple) {Ð
this.choice_build(data);Ð                   } else if (data.selected && !
this.is_multiple) {Ð
this.single_set_selected_text(data.text);Ð                   }Ð
                }Ð           }Ð           return content;Ð       };Ð
AbstractChosen.prototype.result_add_option = function(option) {Ð
var classes, option_el;Ð           if (!option.search_match) {Ð
return '';Ð           }Ð           if (!
this.include_option_in_results(option)) {Ð                return '';Ð
            }Ð           classes = [];Ð           if (!option.disabled && !
(option.selected && this.is_multiple)) {Ð                classes.push("active-
result");Ð           }Ð           if (option.disabled && !(option.selected &&
this.is_multiple)) {Ð                classes.push("disabled-result");Ð
            }Ð           if (option.selected) {Ð
classes.push("result-selected");Ð           }Ð           if
(option.group_array_index != null) {Ð                classes.push("group-
option");Ð           }Ð           if (option.classes !== "") {Ð
classes.push(option.classes);Ð           }Ð           option_el =
document.createElement("li");Ð           option_el.className = classes.join("
");Ð           option_el.style.cssText = option.style;Ð
option_el.setAttribute("data-option-array-index", option.array_index);Ð
            option_el.innerHTML = option.search_text;Ð           return
this.outerHTML(option_el);Ð       };Ð
AbstractChosen.prototype.result_add_group = function(group) {Ð           var
group_el;Ð           if (!(group.search_match || group.group_match)) {Ð
                return '';Ð           }Ð           if (!(group.active_options
> 0)) {Ð                return '';Ð           }Ð           group_el =
document.createElement("li");Ð           group_el.className = "group-result";Ð
            group_el.innerHTML = group.search_text;Ð           return
this.outerHTML(group_el);Ð       };Ð
AbstractChosen.prototype.results_update_field = function() {Ð
this.set_default_text();Ð           if (!this.is_multiple) {Ð
this.results_reset_cleanup();Ð           }Ð
this.result_clear_highlight();Ð           this.results_build();Ð           if
(this.results_showing) {Ð                return this.winnow_results();Ð
            }Ð       };Ð
AbstractChosen.prototype.reset_single_select_options = function() {Ð
            var result, _i, _len, _ref, _results;Ð           _ref =
this.results_data;Ð           _results = [];Ð           for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                result = _ref[_i];Ð
                if (result.selected) {Ð
_results.push(result.selected = false);Ð                } else {Ð
                    _results.push(void 0);Ð                }Ð           }Ð
            return _results;Ð       };Ð
AbstractChosen.prototype.results_toggle = function() {Ð           if
(this.results_showing) {Ð                return this.results_hide();Ð
            } else {Ð                return this.results_show();Ð           }Ð
        };Ð       AbstractChosen.prototype.results_search = function(evt) {Ð
            if (this.results_showing) {Ð                return
this.winnow_results();Ð
```

```
                                    } else {Ð                return
this.results_show();Ð           }Ð       };Ð
AbstractChosen.prototype.winnow_results = function() {Ð           var
escapedSearchText, option, regex, regexAnchor, results, results_group,
searchText, startpos, text, zregex, _i, _len, _ref;Ð
this.no_results_clear();Ð           results = 0;Ð           searchText =
this.get_search_text();Ð           escapedSearchText = searchText.replace(/[-
[\]{}()*+?.,\\^$|#\s]/g, "\\$&");Ð           regexAnchor =
this.search_contains ? "" : "^";Ð           regex = new RegExp(regexAnchor +
escapedSearchText, 'i');Ð           zregex = new RegExp(escapedSearchText,
'i');Ð           _ref = this.results_data;Ð           for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð               option = _ref[_i];Ð
                option.search_match = false;Ð               results_group =
null;Ð               if (this.include_option_in_results(option)) {Ð
                    if (option.group) {Ð
option.group_match = false;Ð                        option.active_options = 0;Ð
                    }Ð                   if ((option.group_array_index !=
null) && this.results_data[option.group_array_index]) {Ð
                        results_group =
this.results_data[option.group_array_index];Ð                        if
(results_group.active_options === 0 && results_group.search_match) {Ð
                            results += 1;Ð                        }Ð
                        results_group.active_options += 1;Ð
                    }Ð                   if (!(option.group && !
this.group_search)) {Ð                        option.search_text =
option.group ? option.label : option.html;Ð
option.search_match = this.search_string_match(option.search_text, regex);Ð
                        if (option.search_match && !option.group) {Ð
                            results += 1;Ð                        }Ð
                        if (option.search_match) {Ð
if (searchText.length) {Ð                               startpos =
option.search_text.search(zregex);Ð                               text =
option.search_text.substr(0, startpos + searchText.length) + '</em>' +
option.search_text.substr(startpos + searchText.length);Ð
                                option.search_text = text.substr(0, startpos)
+ '<em>' + text.substr(startpos);Ð                           }Ð
                            if (results_group != null) {Ð
                                results_group.group_match = true;Ð
                            }Ð                       } else if
((option.group_array_index != null) &&
this.results_data[option.group_array_index].search_match) {Ð
                            option.search_match = true;Ð
                        }Ð                   }Ð               }Ð           }Ð
            this.result_clear_highlight();Ð           if (results < 1 &&
searchText.length) {Ð               this.update_results_content("");Ð
                return this.no_results(searchText);Ð           } else {Ð
                this.update_results_content(this.results_option_build());Ð
                return this.winnow_results_set_highlight();Ð           }Ð
        };Ð       AbstractChosen.prototype.search_string_match =
function(search_string, regex) {Ð           var part, parts, _i, _len;Ð
            if (regex.test(search_string)) {Ð               return true;Ð
            } else if (this.enable_split_word_search &&
(search_string.indexOf(" ") >= 0 || search_string.indexOf("[") === 0)) {Ð
                parts = search_string.replace(/\[|\]/g, "").split(" ");Ð
                if (parts.length) {Ð                   for (_i = 0, _len =
parts.length; _i < _len; _i++) {Ð                       part = parts[_i];Ð
                        if (regex.test(part)) {Ð
return true;Ð                       }Ð                   }Ð               }Ð
            }Ð       };Ð       AbstractChosen.prototype.choices_count =
function() {Ð
```

```
                        var option, _i, _len, _ref;Ð           if
(this.selected_option_count != null) {Ð               return
this.selected_option_count;Ð           }Ð
this.selected_option_count = 0;Ð           _ref = this.form_field.options;Ð
            for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                option = _ref[_i];Ð               if (option.selected) {Ð
                    this.selected_option_count += 1;Ð               }Ð
            }Ð           return this.selected_option_count;Ð       };Ð
AbstractChosen.prototype.choices_click = function(evt) {Ð
evt.preventDefault();Ð           if (!(this.results_showing ||
this.is_disabled)) {Ð               return this.results_show();Ð           }Ð
        };Ð       AbstractChosen.prototype.keyup_checker = function(evt) {Ð
            var stroke, _ref;Ð           stroke = (_ref = evt.which) !=
null ? _ref : evt.keyCode;Ð           this.search_field_scale();Ð
switch (stroke) {Ð               case 8:Ð                   if
(this.is_multiple && this.backstroke_length < 1 && this.choices_count() > 0) {Ð
                        return this.keydown_backstroke();Ð
                    } else if (!this.pending_backstroke) {Ð
                        this.result_clear_highlight();Ð
return this.results_search();Ð                   }Ð                   break;Ð
                case 13:Ð                   evt.preventDefault();Ð
                    if (this.results_showing) {Ð                       return
this.result_select(evt);Ð                   }Ð                   break;Ð
                case 27:Ð                   if (this.results_showing) {Ð
                        this.results_hide();Ð                   }Ð
                    return true;Ð               case 9:Ð               case
38:Ð               case 40:Ð               case 16:Ð               case 91:Ð
                case 17:Ð                   break;Ð               default:Ð
                    return this.results_search();Ð           }Ð       };Ð
        AbstractChosen.prototype.clipboard_event_checker = function(evt) {Ð
            var _this = this;Ð           return setTimeout((function() {Ð
                return _this.results_search();Ð           }), 50);Ð       };Ð
        AbstractChosen.prototype.container_width = function() {Ð           if
(this.options.width != null) {Ð               return this.options.width;Ð
            } else {Ð               return "" + this.form_field.offsetWidth +
"px";Ð           }Ð       };Ð
AbstractChosen.prototype.include_option_in_results = function(option) {Ð
            if (this.is_multiple && (!this.display_selected_options &&
option.selected)) {Ð               return false;Ð           }Ð           if (!
this.display_disabled_options && option.disabled) {Ð               return
false;Ð           }Ð           if (option.empty) {Ð               return
false;Ð           }Ð           return true;Ð       };Ð
AbstractChosen.prototype.search_results_touchstart = function(evt) {Ð
            this.touch_started = true;Ð           return
this.search_results_mouseover(evt);Ð       };Ð
AbstractChosen.prototype.search_results_touchmove = function(evt) {Ð
            this.touch_started = false;Ð           return
this.search_results_mouseout(evt);Ð       };Ð
AbstractChosen.prototype.search_results_touchend = function(evt) {Ð
if (this.touch_started) {Ð               return
this.search_results_mouseup(evt);Ð           }Ð       };Ð
AbstractChosen.prototype.outerHTML = function(element) {Ð           var tmp;Ð
            if (element.outerHTML) {Ð               return element.outerHTML;Ð
            }Ð           tmp = document.createElement("div");Ð
tmp.appendChild(element);Ð           return tmp.innerHTML;Ð       };Ð
AbstractChosen.browser_is_supported = function() {Ð           if
(window.navigator.appName === "Microsoft Internet Explorer") {Ð
return document.documentMode >= 8;Ð           }Ð           if (/iP(od|hone)/
i.test(window.navigator.userAgent)) {Ð               return false;Ð
            }Ð
```

```
                        if (/Android/i.test(window.navigator.userAgent)) {Ð
                if (/Mobile/i.test(window.navigator.userAgent)) {Ð
                    return false;Ð                }Ð            }Ð
return true;Ð        };Ð        AbstractChosen.default_multiple_text = "Select
Some Options";Ð        AbstractChosen.default_single_text = "Select an Option";Ð
        AbstractChosen.default_no_result_text = "No results match";Ð
return AbstractChosen;Ð   })();Ð   $ = jQuery;Ð   $.fn.extend({Ð
chosen: function(options) {Ð            if (!
AbstractChosen.browser_is_supported()) {Ð                return this;Ð
            }Ð            return this.each(function(input_field) {Ð
                var $this, chosen;Ð                $this = $(this);Ð
                chosen = $this.data('chosen');Ð                if (options ===
'destroy' && chosen) {Ð                    chosen.destroy();Ð                }
else if (!chosen) {Ð                    $this.data('chosen', new Chosen(this,
options));Ð                }Ð            });Ð        }Ð   });Ð   Chosen =
(function(_super) {Ð        __extends(Chosen, _super);Ð        function
Chosen() {Ð            _ref = Chosen.__super__.constructor.apply(this,
arguments);Ð            return _ref;Ð        }Ð        Chosen.prototype.setup =
function() {Ð            this.form_field_jq = $(this.form_field);Ð
this.current_selectedIndex = this.form_field.selectedIndex;Ð            return
this.is_rtl = this.form_field_jq.hasClass("chosen-rtl");Ð        };Ð
Chosen.prototype.set_up_html = function() {Ð            var container_classes,
container_props;Ð            container_classes = ["chosen-container"];Ð
            container_classes.push("chosen-container-" + (this.is_multiple ?
"multi" : "single"));Ð            if (this.inherit_select_classes &&
this.form_field.className) {Ð
container_classes.push(this.form_field.className);Ð            }Ð            if
(this.is_rtl) {Ð                container_classes.push("chosen-rtl");Ð
            }Ð            container_props = {Ð                'class':
container_classes.join(' '),Ð                'style': "width: " +
(this.container_width()) + ";",Ð                'title': this.form_field.titleÐ
            };Ð            if (this.form_field.id.length) {Ð
container_props.id = this.form_field.id.replace(/[^\w]/g, '_') + "_chosen";Ð
            }Ð            this.container = $("<div />", container_props);Ð
            if (this.is_multiple) {Ð                this.container.html('<ul
class="chosen-choices"><li class="search-field"><input type="text" value="' +
this.default_text + '" class="default" autocomplete="off"
style="width:25px;" /></li></ul><div class="chosen-drop"><ul class="chosen-
results"></ul></div>');Ð            } else {Ð
this.container.html('<a class="chosen-single chosen-default"
tabindex="-1"><span>' + this.default_text + '</span><div><b></b></div></
a><div class="chosen-drop"><div class="chosen-search"><input type="text"
autocomplete="off" /></div><ul class="chosen-results"></ul></div>');Ð
            }Ð            this.form_field_jq.hide().after(this.container);Ð
            this.dropdown = this.container.find('div.chosen-drop').first();Ð
            this.search_field = this.container.find('input').first();Ð
            this.search_results = this.container.find('ul.chosen-
results').first();Ð            this.search_field_scale();Ð
this.search_no_results = this.container.find('li.no-results').first();Ð
            if (this.is_multiple) {Ð                this.search_choices =
this.container.find('ul.chosen-choices').first();Ð
this.search_container = this.container.find('li.search-field').first();Ð
            } else {Ð                this.search_container =
this.container.find('div.chosen-search').first();Ð
this.selected_item = this.container.find('.chosen-single').first();Ð
            }Ð            this.results_build();Ð
this.set_tab_index();Ð            this.set_label_behavior();Ð            return
this.form_field_jq.trigger("chosen:ready", {Ð                chosen: thisÐ
            });Ð        };Ð        Chosen.prototype.register_observers =
function() {Ð
```

```
                        var _this = this;Ð
this.container.bind('mousedown.chosen', function(evt) {Ð
_this.container_mousedown(evt);Ð           });Ð
this.container.bind('mouseup.chosen', function(evt) {Ð
_this.container_mouseup(evt);Ð           });Ð
this.container.bind('mouseenter.chosen', function(evt) {Ð
_this.mouse_enter(evt);Ð           });Ð
this.container.bind('mouseleave.chosen', function(evt) {Ð
_this.mouse_leave(evt);Ð           });Ð
this.search_results.bind('mouseup.chosen', function(evt) {Ð
_this.search_results_mouseup(evt);Ð           });Ð
this.search_results.bind('mouseover.chosen', function(evt) {Ð
_this.search_results_mouseover(evt);Ð           });Ð
this.search_results.bind('mouseout.chosen', function(evt) {Ð
_this.search_results_mouseout(evt);Ð           });Ð
this.search_results.bind('mousewheel.chosen DOMMouseScroll.chosen',
function(evt) {Ð               _this.search_results_mousewheel(evt);Ð
            });Ð           this.search_results.bind('touchstart.chosen',
function(evt) {Ð               _this.search_results_touchstart(evt);Ð
            });Ð           this.search_results.bind('touchmove.chosen',
function(evt) {Ð               _this.search_results_touchmove(evt);Ð
            });Ð           this.search_results.bind('touchend.chosen',
function(evt) {Ð               _this.search_results_touchend(evt);Ð
            });Ð           this.form_field_jq.bind("chosen:updated.chosen",
function(evt) {Ð               _this.results_update_field(evt);Ð           });Ð
            this.form_field_jq.bind("chosen:activate.chosen", function(evt) {Ð
                _this.activate_field(evt);Ð           });Ð
this.form_field_jq.bind("chosen:open.chosen", function(evt) {Ð
_this.container_mousedown(evt);Ð           });Ð
this.form_field_jq.bind("chosen:close.chosen", function(evt) {Ð
_this.input_blur(evt);Ð           });Ð
this.search_field.bind('blur.chosen', function(evt) {Ð
_this.input_blur(evt);Ð           });Ð
this.search_field.bind('keyup.chosen', function(evt) {Ð
_this.keyup_checker(evt);Ð           });Ð
this.search_field.bind('keydown.chosen', function(evt) {Ð
_this.keydown_checker(evt);Ð           });Ð
this.search_field.bind('focus.chosen', function(evt) {Ð
_this.input_focus(evt);Ð           });Ð
this.search_field.bind('cut.chosen', function(evt) {Ð
_this.clipboard_event_checker(evt);Ð           });Ð
this.search_field.bind('paste.chosen', function(evt) {Ð
_this.clipboard_event_checker(evt);Ð           });Ð           if
(this.is_multiple) {Ð               return
this.search_choices.bind('click.chosen', function(evt) {Ð
_this.choices_click(evt);Ð               });Ð           } else {Ð
                return this.container.bind('click.chosen', function(evt) {Ð
                    evt.preventDefault();Ð               });Ð           }Ð
        };Ð       Chosen.prototype.destroy = function() {Ð
$(this.container[0].ownerDocument).unbind("click.chosen",
this.click_test_action);Ð           if (this.search_field[0].tabIndex) {Ð
                this.form_field_jq[0].tabIndex =
this.search_field[0].tabIndex;Ð           }Ð
this.container.remove();Ð           this.form_field_jq.removeData('chosen');Ð
            return this.form_field_jq.show();Ð       };Ð
Chosen.prototype.search_field_disabled = function() {Ð
this.is_disabled = this.form_field_jq[0].disabled;Ð           if
(this.is_disabled) {Ð               this.container.addClass('chosen-
disabled');Ð               this.search_field[0].disabled = true;Ð
                if (!this.is_multiple) {Ð
```

```
this.selected_item.unbind("focus.chosen", this.activate_action);Ð
                }Ð               return this.close_field();Ð           } else
{Ð                this.removeClass('chosen-disabled');Ð
                this.search_field[0].disabled = false;Ð               if (!
this.is_multiple) {Ð                    return
this.selected_item.bind("focus.chosen", this.activate_action);Ð
                }Ð           }Ð       };Ð
Chosen.prototype.container_mousedown = function(evt) {Ð           if (!
this.is_disabled) {Ð               if (evt && evt.type === "mousedown" && !
this.results_showing) {Ð                    evt.preventDefault();Ð
                }Ð               if (!((evt != null) &&
($(evt.target)).hasClass("search-choice-close"))) {Ð                  if (!
this.active_field) {Ð                        if (this.is_multiple) {Ð
                          this.search_field.val("");Ð
                        }Ð
$(this.container[0].ownerDocument).bind('click.chosen',
this.click_test_action);Ð                        this.results_show();Ð
                    } else if (!this.is_multiple && evt && (($(evt.target)[0]
=== this.selected_item[0]) || $(evt.target).parents("a.chosen-
single").length)) {Ð                        evt.preventDefault();Ð
                        this.results_toggle();Ð                  }Ð
                    return this.activate_field();Ð               }Ð
            }Ð       };Ð       Chosen.prototype.container_mouseup =
function(evt) {Ð           if (evt.target.nodeName === "ABBR" && !
this.is_disabled) {Ð               return this.results_reset(evt);Ð
            }Ð       };Ð       Chosen.prototype.search_results_mousewheel =
function(evt) {Ð           var delta;Ð           if (evt.originalEvent) {Ð
                delta = -evt.originalEvent.wheelDelta ||
evt.originalEvent.detail;Ð           }Ð           if (delta != null) {Ð
                evt.preventDefault();Ð               if (evt.type ===
'DOMMouseScroll') {Ð                    delta = delta * 40;Ð               }Ð
                return this.search_results.scrollTop(delta +
this.search_results.scrollTop());Ð           }Ð       };Ð
Chosen.prototype.blur_test = function(evt) {Ð           if (!
this.active_field && this.container.hasClass("chosen-container-active")) {Ð
                return this.close_field();Ð           }Ð       };Ð
Chosen.prototype.close_field = function() {Ð
$(this.container[0].ownerDocument).unbind("click.chosen",
this.click_test_action);Ð           this.active_field = false;Ð
this.results_hide();Ð           this.container.removeClass("chosen-container-
active");Ð           this.clear_backstroke();Ð
this.show_search_field_default();Ð           return this.search_field_scale();Ð
        };Ð       Chosen.prototype.activate_field = function() {Ð
this.container.addClass("chosen-container-active");Ð
this.active_field = true;Ð
this.search_field.val(this.search_field.val());Ð           return
this.search_field.focus();Ð       };Ð
Chosen.prototype.test_active_click = function(evt) {Ð           var
active_container;Ð           active_container =
$(evt.target).closest('.chosen-container');Ð           if
(active_container.length && this.container[0] === active_container[0]) {Ð
                return this.active_field = true;Ð           } else {Ð
                return this.close_field();Ð           }Ð       };Ð
Chosen.prototype.results_build = function() {Ð           this.parsing = true;Ð
            this.selected_option_count = null;Ð           this.results_data =
SelectParser.select_to_array(this.form_field);Ð           if
(this.is_multiple) {Ð               this.search_choices.find("li.search-
choice").remove();Ð           } else if (!this.is_multiple) {Ð
this.single_set_selected_text();Ð
```

```
                                                    if (this.disable_search ||
this.form_field.options.length <= this.disable_search_threshold) {Ð
                    this.search_field[0].readOnly = true;Ð
this.container.addClass("chosen-container-single-nosearch");Ð               }
else {Ð                    this.search_field[0].readOnly = false;Ð
                    this.container.removeClass("chosen-container-single-
nosearch");Ð               }Ð           }Ð
this.update_results_content(this.results_option_build({Ð               first:
trueÐ           }));Ð           this.search_field_disabled();Ð
this.show_search_field_default();Ð           this.search_field_scale();Ð
            return this.parsing = false;Ð       };Ð
Chosen.prototype.result_do_highlight = function(el) {Ð           var
high_bottom, high_top, maxHeight, visible_bottom, visible_top;Ð           if
(el.length) {Ð               this.result_clear_highlight();Ð
this.result_highlight = el;Ð
this.result_highlight.addClass("highlighted");Ð               maxHeight =
parseInt(this.search_results.css("maxHeight"), 10);Ð
visible_top = this.search_results.scrollTop();Ð               visible_bottom
= maxHeight + visible_top;Ð               high_top =
this.result_highlight.position().top + this.search_results.scrollTop();Ð
                high_bottom = high_top + this.result_highlight.outerHeight();Ð
                if (high_bottom >= visible_bottom) {Ð
return this.search_results.scrollTop((high_bottom - maxHeight) > 0 ?
high_bottom - maxHeight : 0);Ð               } else if (high_top <
visible_top) {Ð                    return
this.search_results.scrollTop(high_top);Ð               }Ð           }Ð
        };Ð       Chosen.prototype.result_clear_highlight = function() {Ð
            if (this.result_highlight) {Ð
this.result_highlight.removeClass("highlighted");Ð           }Ð
return this.result_highlight = null;Ð       };Ð
Chosen.prototype.results_show = function() {Ð           if (this.is_multiple
&& this.max_selected_options <= this.choices_count()) {Ð
this.form_field_jq.trigger("chosen:maxselected", {Ð                  chosen:
thisÐ               });Ð               return false;Ð           }Ð
this.container.addClass("chosen-with-drop");Ð           this.results_showing
= true;Ð           this.search_field.focus();Ð
this.search_field.val(this.search_field.val());Ð
this.winnow_results();Ð           return
this.form_field_jq.trigger("chosen:showing_dropdown", {Ð
chosen: thisÐ           });Ð       };Ð
Chosen.prototype.update_results_content = function(content) {Ð
return this.search_results.html(content);Ð       };Ð
Chosen.prototype.results_hide = function() {Ð           if
(this.results_showing) {Ð               this.result_clear_highlight();Ð
                this.container.removeClass("chosen-with-drop");Ð
                this.form_field_jq.trigger("chosen:hiding_dropdown", {Ð
                    chosen: thisÐ               });Ð           }Ð
return this.results_showing = false;Ð       };Ð
Chosen.prototype.set_tab_index = function(el) {Ð           var ti;Ð
if (this.form_field.tabIndex) {Ð               ti = this.form_field.tabIndex;Ð
                this.form_field.tabIndex = -1;Ð               return
this.search_field[0].tabIndex = ti;Ð           }Ð       };Ð
Chosen.prototype.set_label_behavior = function() {Ð           var _this =
this;Ð           this.form_field_label = this.form_field_jq.parents("label");Ð
            if (!this.form_field_label.length && this.form_field.id.length) {Ð
                this.form_field_label = $("label[for='" + this.form_field.id
+ "']");Ð           }Ð           if (this.form_field_label.length > 0) {Ð
                return this.form_field_label.bind('click.chosen',
function(evt) {Ð                   if (_this.is_multiple) {Ð
                        return _this.container_mousedown(evt);Ð
```

```
                    } else {Ð                        return
_this.activate_field();Ð                  }Ð              });Ð           }Ð
        };Ð       Chosen.prototype.show_search_field_default = function() {Ð
            if (this.is_multiple && this.choices_count() < 1 && !
this.active_field) {Ð               this.search_field.val(this.default_text);Ð
                return this.search_field.addClass("default");Ð           }
else {Ð               this.search_field.val("");Ð               return
this.search_field.removeClass("default");Ð           }Ð       };Ð
Chosen.prototype.search_results_mouseup = function(evt) {Ð           var
target;Ð           target = $(evt.target).hasClass("active-result") ?
$(evt.target) : $(evt.target).parents(".active-result").first();Ð
if (target.length) {Ð               this.result_highlight = target;Ð
                this.result_select(evt);Ð               return
this.search_field.focus();Ð           }Ð       };Ð
Chosen.prototype.search_results_mouseover = function(evt) {Ð           var
target;Ð           target = $(evt.target).hasClass("active-result") ?
$(evt.target) : $(evt.target).parents(".active-result").first();Ð
if (target) {Ð               return this.result_do_highlight(target);Ð
            }Ð       };Ð       Chosen.prototype.search_results_mouseout =
function(evt) {Ð           if ($(evt.target).hasClass("active-result" ||
$(evt.target).parents('.active-result').first())) {Ð               return
this.result_clear_highlight();Ð           }Ð       };Ð
Chosen.prototype.choice_build = function(item) {Ð           var choice,
close_link,Ð               _this = this;Ð           choice = $('<li />', {Ð
                "class": "search-choice"Ð           }).html("<span>" +
item.html + "</span>");Ð           if (item.disabled) {Ð
choice.addClass('search-choice-disabled');Ð           } else {Ð
close_link = $('<a />', {Ð                   "class": 'search-choice-close',Ð
                    'data-option-array-index': item.array_indexÐ
                });Ð               close_link.bind('click.chosen',
function(evt) {Ð                   return
_this.choice_destroy_link_click(evt);Ð               });Ð
choice.append(close_link);Ð           }Ð           return
this.search_container.before(choice);Ð       };Ð
Chosen.prototype.choice_destroy_link_click = function(evt) {Ð
evt.preventDefault();Ð           evt.stopPropagation();Ð           if (!
this.is_disabled) {Ð               return this.choice_destroy($(evt.target));Ð
            }Ð       };Ð       Chosen.prototype.choice_destroy =
function(link) {Ð           if
(this.result_deselect(link[0].getAttribute("data-option-array-index"))) {Ð
                this.show_search_field_default();Ð               if
(this.is_multiple && this.choices_count() > 0 &&
this.search_field.val().length < 1) {Ð                   this.results_hide();Ð
                }Ð               link.parents('li').first().remove();Ð
                return this.search_field_scale();Ð           }Ð       };Ð
        Chosen.prototype.results_reset = function() {Ð
this.reset_single_select_options();Ð
this.form_field.options[0].selected = true;Ð
this.single_set_selected_text();Ð           this.show_search_field_default();Ð
            this.results_reset_cleanup();Ð
this.form_field_jq.trigger("change");Ð           if (this.active_field) {Ð
                return this.results_hide();Ð           }Ð       };Ð
Chosen.prototype.results_reset_cleanup = function() {Ð
this.current_selectedIndex = this.form_field.selectedIndex;Ð           return
this.selected_item.find("abbr").remove();Ð       };Ð
Chosen.prototype.result_select = function(evt) {Ð           var high, item;Ð
            if (this.result_highlight) {Ð               high =
this.result_highlight;Ð               this.result_clear_highlight();Ð
                if (this.is_multiple && this.max_selected_options <=
this.choices_count()) {Ð
```

```
this.form_field_jq.trigger("chosen:maxselected", {Ð
chosen: thisÐ                    });Ð                    return false;Ð
                }Ð                if (this.is_multiple) {Ð
high.removeClass("active-result");Ð                } else {Ð
this.reset_single_select_options();Ð                }Ð                item =
this.results_data[high[0].getAttribute("data-option-array-index")];Ð
                item.selected = true;Ð
this.form_field.options[item.options_index].selected = true;Ð
this.selected_option_count = null;Ð                if (this.is_multiple) {Ð
                    this.choice_build(item);Ð                } else {Ð
                    this.single_set_selected_text(item.text);Ð                }Ð
                if (!((evt.metaKey || evt.ctrlKey) && this.is_multiple)) {Ð
                    this.results_hide();Ð                }Ð
this.search_field.val("");Ð                if (this.is_multiple ||
this.form_field.selectedIndex !== this.current_selectedIndex) {Ð
                    this.form_field_jq.trigger("change", {Ð
                        'selected':
this.form_field.options[item.options_index].valueÐ                    });Ð
                }Ð                this.current_selectedIndex =
this.form_field.selectedIndex;Ð                return
this.search_field_scale();Ð            }Ð        };Ð
Chosen.prototype.single_set_selected_text = function(text) {Ð            if
(text == null) {Ð                text = this.default_text;Ð            }Ð
            if (text === this.default_text) {Ð
this.selected_item.addClass("chosen-default");Ð            } else {Ð
                this.single_deselect_control_build();Ð
this.selected_item.removeClass("chosen-default");Ð            }Ð
return this.selected_item.find("span").text(text);Ð        };Ð
Chosen.prototype.result_deselect = function(pos) {Ð            var result_data;Ð
            result_data = this.results_data[pos];Ð            if (!
this.form_field.options[result_data.options_index].disabled) {Ð
result_data.selected = false;Ð
this.form_field.options[result_data.options_index].selected = false;Ð
                this.selected_option_count = null;Ð
this.result_clear_highlight();Ð                if (this.results_showing) {Ð
                    this.winnow_results();Ð                }Ð
this.form_field_jq.trigger("change", {Ð                    deselected:
this.form_field.options[result_data.options_index].valueÐ                });Ð
                this.search_field_scale();Ð                return true;Ð
            } else {Ð                return false;Ð            }Ð        };Ð
        Chosen.prototype.single_deselect_control_build = function() {Ð
            if (!this.allow_single_deselect) {Ð                return;Ð
            }Ð            if (!this.selected_item.find("abbr").length) {Ð
                this.selected_item.find("span").first().after("<abbr
class=\"search-choice-close\"></abbr>");Ð            }Ð            return
this.selected_item.addClass("chosen-single-with-deselect");Ð        };Ð
Chosen.prototype.get_search_text = function() {Ð            if
(this.search_field.val() === this.default_text) {Ð                return "";Ð
            } else {Ð                return $('<div/
>').text($.trim(this.search_field.val())).html();Ð            }Ð        };Ð
        Chosen.prototype.winnow_results_set_highlight = function() {Ð
            var do_high, selected_results;Ð            selected_results = !
this.is_multiple ? this.search_results.find(".result-selected.active-
result") : [];Ð            do_high = selected_results.length ?
selected_results.first() : this.search_results.find(".active-result").first();Ð
            if (do_high != null) {Ð                return
this.result_do_highlight(do_high);Ð            }Ð        };Ð
Chosen.prototype.no_results = function(terms) {Ð            var
no_results_html;Ð
```

```
                            no_results_html = $('<li class="no-results">' +
this.results_none_found + ' "<span></span>"</li>');Ð
no_results_html.find("span").first().html(terms);Ð
this.search_results.append(no_results_html);Ð           return
this.form_field_jq.trigger("chosen:no_results", {Ð               chosen: thisÐ
            });Ð       };Ð       Chosen.prototype.no_results_clear =
function() {Ð           return this.search_results.find(".no-
results").remove();Ð       };Ð       Chosen.prototype.keydown_arrow =
function() {Ð           var next_sib;Ð           if (this.results_showing &&
this.result_highlight) {Ð               next_sib =
this.result_highlight.nextAll("li.active-result").first();Ð               if
(next_sib) {Ð                   return this.result_do_highlight(next_sib);Ð
                }Ð           } else {Ð               return
this.results_show();Ð           }Ð       };Ð
Chosen.prototype.keyup_arrow = function() {Ð           var prev_sibs;Ð
            if (!this.results_showing && !this.is_multiple) {Ð
return this.results_show();Ð           } else if (this.result_highlight) {Ð
                prev_sibs = this.result_highlight.prevAll("li.active-result");Ð
                if (prev_sibs.length) {Ð                   return
this.result_do_highlight(prev_sibs.first());Ð               } else {Ð
                    if (this.choices_count() > 0) {Ð
this.results_hide();Ð                   }Ð                   return
this.result_clear_highlight();Ð               }Ð           }Ð       };Ð
Chosen.prototype.keydown_backstroke = function() {Ð           var
next_available_destroy;Ð           if (this.pending_backstroke) {Ð

this.choice_destroy(this.pending_backstroke.find("a").first());Ð
                return this.clear_backstroke();Ð           } else {Ð
                next_available_destroy =
this.search_container.siblings("li.search-choice").last();Ð               if
(next_available_destroy.length && !next_available_destroy.hasClass("search-
choice-disabled")) {Ð                   this.pending_backstroke =
next_available_destroy;Ð                   if (this.single_backstroke_delete)
{Ð                       return this.keydown_backstroke();Ð
                    } else {Ð                       return
this.pending_backstroke.addClass("search-choice-focus");Ð                   }Ð
                }Ð           }Ð       };Ð
Chosen.prototype.clear_backstroke = function() {Ð           if
(this.pending_backstroke) {Ð
this.pending_backstroke.removeClass("search-choice-focus");Ð           }Ð
            return this.pending_backstroke = null;Ð       };Ð
Chosen.prototype.keydown_checker = function(evt) {Ð           var stroke,
_ref1;Ð           stroke = (_ref1 = evt.which) != null ? _ref1 : evt.keyCode;Ð
            this.search_field_scale();Ð           if (stroke !== 8 &&
this.pending_backstroke) {Ð               this.clear_backstroke();Ð
            }Ð           switch (stroke) {Ð               case 8:Ð
                    this.backstroke_length = this.search_field.val().length;Ð
                    break;Ð               case 9:Ð                   if
(this.results_showing && !this.is_multiple) {Ð
this.result_select(evt);Ð                   }Ð
this.mouse_on_container = false;Ð                   break;Ð
case 13:Ð                   evt.preventDefault();Ð                   break;Ð
                case 38:Ð                   evt.preventDefault();Ð
                    this.keyup_arrow();Ð                   break;Ð
                case 40:Ð                   evt.preventDefault();Ð
                    this.keydown_arrow();Ð                   break;Ð
            }Ð       };Ð       Chosen.prototype.search_field_scale =
function() {Ð           var div, f_width, h, style, style_block, styles, w,
_i, _len;Ð           if (this.is_multiple) {Ð               h = 0;Ð
                w = 0;Ð
```

```
                                        style_block = "position:absolute; left:
-1000px; top: -1000px; display:none;";Ð               styles = ['font-size',
'font-style', 'font-weight', 'font-family', 'line-height', 'text-transform',
'letter-spacing'];Ð               for (_i = 0, _len = styles.length; _i <
_len; _i++) {Ð                  style = styles[_i];Ð
style_block += style + ":" + this.search_field.css(style) + ";";Ð
                }Ð               div = $('<div />', {Ð
'style': style_blockÐ                 });Ð
div.text(this.search_field.val());Ð               $('body').append(div);Ð
                w = div.width() + 25;Ð               div.remove();Ð
                f_width = this.container.outerWidth();Ð               if (w >
f_width - 10) {Ð                   w = f_width - 10;Ð               }Ð
                return this.search_field.css({Ð                   'width': w
+ 'px'Ð               });Ð           }Ð       };Ð       return Chosen;Ð   })
(AbstractChosen);Ð}).call(this);Ð
```

public\assets\js\plugins\clockpicker\clockpicker.js

/*!Ð* ClockPicker v{package.version} (http://weareoutman.github.io/
clockpicker/)Ð* Copyright 2014 Wang Shenwei.Ð* Licensed under MIT (https://
github.com/weareoutman/clockpicker/blob/gh-pages/LICENSE)Ð*/™Ð(function(){™Ðf "
$ = window.jQuery,™Ð$win = $(window),™Ðdoc = $(document),™Ðbody;™ÐÒò 6 â ’ W6R
inline svg ?™Ðf " 7ftå2 Ò v‡GG ¢ò÷wwrçs2æ÷&ró#   ÷7frrÍsvgSupported =
'SVGAngle' in window && (function(){™Ð–f " 7W ÷'FVBÍel =
document.createElement('div');™Ð–VÂæ–ææW$…DÔÂ Ò sÇ7fróâS½7W ÷'FVB Ò
(el.firstChild && el.firstChild.namespaceURI) == svgNS;™Ð–VÂæ–ææW$…DÔÂ Ò r™½
return supported;™Ð})()™ÐÒò 6 â ’ W6R G& ç6—F–öâ ¥f " G& ç6—F–öå7W ÷'FVB Ò
(function(){™Ðvar style = document.createElement('div').style;™Ðeturn
'transition' in style ||™Ð’uvV&¶–EG& ç6—F–öâr –â 7G–ÆR ÇÍtÖ÷¥G& ç6—F–öâr –â
style ||™Ð’v×5G& ç6—F–öâr –â 7G–ÆR ÇÍtõG& ç6—F–öâr –â 7G–ÆSÒ’,“™Ðòò Æ—7FVâ F÷V6,
events in touch screen device, instead of mouse events in desktop.™Ðf "
touchSupported = 'ontouchstart' in window,™ÐmousedownEvent = 'mousedown' +
(touchSupported ? ' touchstart' : ''),™ÐmousemoveEvent =
'mousemove.clockpicker' + (touchSupported ? ' touchmove.clockpicker' : ''),™Ð
mouseupEvent = 'mouseup.clockpicker' + (touchSupported ? '
touchend.clockpicker' : '');™ÐÒò f–'& FR F†R FWf–6R –b 7W ÷'FVÍf " f–'& FR Ò
navigator.vibrate ? 'vibrate' : navigator.webkitVibrate ? 'webkitVibrate' :
null;™ÐgVæ7F–öâ 7&V FU7ftVÆVÖVçB†æ ÖR’ ™½return document.createElementNS(svgNS,
name);™Ð™ÐgVæ7F–öâ ÆV F–æu¦W&ò†çVÒ’ ™½return (num < 10 ? '0' : '') + num;™ÐÒò vWB
a unique id™Ðf " –D6÷VçFW" Ò ½gVæ7F–öâ Væ— VT–B‡ &Vf–,’ ™½var id = ++idCounter
+ '';™Ðreturn prefix ? prefix + id : id;™ÐÒò 6Æö6² 6–¦]f " F– Å& F—W2 Ò   Í
outerRadius = 80,™Ð// innerRadius = 80 on 12 hour clock™ÐinnerRadius = 54,™Ð
tickRadius = 13,™Ðdiameter = dialRadius * 2,™Ðuration = transitionSupported ?
350 : 1;™ÐÒò ÷ ÷fW" FV× Æ F]f " G Â Ò ™½'<div class="popover clockpicker-
popover">',™Ð’sÆF–b 6Æ 73Ò& '&÷r#ãÂöF–câÍsÆF–b 6Æ 73Ò' ÷ ÷fW"×F–FÆR#âÍ'<span
class="clockpicker-span-hours text-primary">',™Ð' : ™Ð,™Ð<span
class="clockpicker-span-minutes">',™Ð'<span class="clockpicker-span-am-
pm">',™Ð’sÂöF–câÍsÆF–b 6Æ 73Ò' ÷ ÷fW"Ö6öçFVçB#âÍ'<div
class="clockpicker-plate">',™Ð’sÆF–b 6Æ 73Ò&6Æö6· –6¶W"Ö6 çf 2#ãÂöF–câÍsÆF–b
class="clockpicker-dial clockpicker-hours"> ',™Ð’sÆF–b 6Æ 73Ò&6Æö6· –6¶W"™Ð
dial clockpicker-minutes clockpicker-dial-out"> ',™Ð' ™,™Ð<span
class="clockpicker-am-pm-block">',™Ð'™,™ÐÂöF–câÍ ™Ðæ¦ö–â,rr“™Ðòò
ClockPickerÐgVæ7F–öâ 6Æö6µ –6¶W"†VÆVÖVçBÂ ÷ F–öç2’ ™½var popover = $(tpl),™Ð Æ FR
= popover.find('.clockpicker-plate'),™Ð–†÷W'5f–Wr Ò ÷ ÷fW"æf–æB,ræ6Æö6· –6¶W"™Ð
hours'),™Ð–Ö–çWFW5f–Wr Ò ÷ ÷fW"æf–æB,ræ6Æö6· –6¶W"ÖÖ–çWFW2r™Í Õ Ô&Æö6² Ò
popover.find('.clockpicker-am-pm-block'),™Ð––4–ç WB Ò VÆVÖVçBç &÷ ,wF tæ ÖRr’
=== 'INPUT',™Ð––ç WB Ò —4–ç WB ò VÆVÖVçB ¢ VÆVÖVçBæf–æB,v–ç WBr™Í FFöâ Ò
element.find('.input-group-addon'),™Ð–6VÆb Ò F†—2ÍF–ÖW™Ð½this.id = uniqueId('cp');™Ð
this.element = element;™Ðthis.options = options;™Ðhis.isAppended = false;™Ð
this.isShown = false;™Ðthis.currentView = 'hours';™Ðhis.isInput = isInput;™Ð
this.input = input;™Ðthis.addon = addon;™Ðhis.popover = popover;™Ðhis.plate =
plate;™Ðthis.hoursView = hoursView;™Ðhis.minutesView = minutesView;™Ð
this.amPmBlock = amPmBlock;™Ðthis.spanHours = popover.find('.clockpicker-span-
hours');™Ðthis.spanMinutes = popover.find('.clockpicker-span-minutes');™Ð
this.spanAmPm = popover.find('.clockpicker-span-am-pm');™Ðthis.amOrPm = "PM";™Ð/
Setup for for 12 hour clock if option is selected™Ðif (options.twelvehour) {™Ð
var amPmButtonsTemplate = [' ',™Ð'<button
type="button" class="btn btn-sm btn-default clockpicker-button clockpicker-am-
button">',™Ð'AM</button>™,™Ð<button type="button" class="btn btn-sm btn-default
clockpicker-button clockpicker-pm-button">',™Ð'PM</button>™,™Ð '].join('');™Ð
var amPmButtons = $(amPmButtonsTemplate);™Ð’òö Õ Ô'WGFöç2æ VæEFò‡ Æ FR™½òòòð
Not working b/c they are not shown when this runs™Ð’òòB,v6Æö6· –6¶W"Ö ÒÖ'WGFöâr•
™’òò æöâ,&6Æ–6²"Â gVæ7F–öâ,’™½òò 6VÆbæ Ô÷% Ò Ò $ Ò™#½òò
$('.clockpicker-span-am-pm').empty().append('AM');™Ð’òò Ò™½òò ™’òð
$('clockpicker-pm-button')™Ð’òò æöâ,&6Æ–6²"Â gVæ7F–öâ,’™½òò
self.amOrPm = "PM";™Ð’òò B,ræ6Æö6· –6¶W"×7 âÖ ÒÐ
pm').empty().append('PM');Ð

™'òò Ò™½B,sÆ'WGFöâ G— SÒ&'WGFöâ" 6Æ 73Ò&'Fâ 'Fâ×6Ò
btn-default clockpicker-button am-button">' + "AM" + '</button>')™.on("click",
function() {™—6VÆbæ Ô÷% Ò Ò $ Ò#½B,ræ6Æö6· –6¶W"×7 âÖ ÒÐ
pm').empty().append('AM');™}).appendTo(this.amPmBlock);™,sÆ'WGFöâ
type="button" class="btn btn-sm btn-default clockpicker-button pm-button">' +
"PM" + '</button>')™.on("click", function()™{Ð6VÆbæ Ô÷% Ò Ò u Ò™½
$('.clockpicker-span-am-pm').empty().append('PM');™}).appendTo(this.amPmBlock);™
™™Ðif (! options.autoclose) ™{Ðòò –b WFö6Æ÷6R —2 æ÷B 6WGFVBÂ VæB 'WGFÖ1
$('<button type="button" class="btn btn-sm btn-default btn-block clockpicker-
button">' + options.donetext + '</button>')™.click($.proxy(this.done, this))™
™™.appendTo(popover);™™// Placement and arrow align - make sure they make sense.™
if ((options.placement === 'top' || options.placement === 'bottom') &&
(options.align === 'top' || options.align === 'bottom')) options.align =
'left';™if ((options.placement === 'left' || options.placement === 'right') &&
(options.align === 'left' || options.align === 'right')) options.align =
'top';™popover.addClass(options.placement);™popover.addClass('clockpicker-
align-' + options.align);™this.spanHours.click($.proxy(this.toggleView, this,
'hours'));™this.spanMinutes.click($.proxy(this.toggleView, this, 'minutes'));™™
™// Show or toggle™input.on('focus.clockpicker click.clockpicker',
$.proxy(this.show, this));™addon.on('click.clockpicker', $.proxy(this.toggle,
this));™// Build tick™var tickTpl = $(' ');™
i, tick, radian, radius;™// Hours view™if (options.twelvehour) ™{Ðf÷" †' Ò ² ' Â
13; i += 1) {™tick = tickTpl.clone();™radian = i / 6 * Math.PI;™radius =
outerRadius;™tick.css('font-size', '120%');™tick.css({ÐÆVgC¢ F– Å& F—W2 ²
Math.sin(radian) * radius - tickRadius,™—F÷ ¢ F– Å& F—W2 Ò Ö F,æ6÷2‡& F– â' ¢
radius - tickRadius™});™tick.html(i === 0 ? '00' : i);™hoursView.append(tick);™
tick.on(mousedownEvent, mousedown);™—} else ™{Ðf÷" †' Ò ² ' Â #C² ' ³Ò '™½tick
= tickTpl.clone();™radian = i / 6 * Math.PI;™var inner = i > 0 && i < 13;™radius
= inner ? innerRadius : outerRadius;™tick.css({ÐÆVgC¢ F– Å& F—W2 ²
Math.sin(radian) * radius - tickRadius,™—F÷ ¢ F– Å& F—W2 Ò Ö F,æ6÷2‡& F– â' ¢
radius - tickRadius™});™if (inner) ™{ÐF–6²æ772,vföçB×6—¦RrÂ s # Rr ™½™™tick.html(i
=== 0 ? '00' : i);™hoursView.append(tick);™tick.on(mousedownEvent, mousedown);™™™
™// Minutes view™for (i = 0; i < 60; i += 5) {ÐF–6² Ò F–6µG Âæ6ÆöæR,™½& F– â Ò
i / 30 * Math.PI;™—F–6²æ772‡½™™left: dialRadius + Math.sin(radian) * outerRadius
- tickRadius,™top: dialRadius - Math.cos(radian) * outerRadius - tickRadius™™½
tick.css('font-size', '120%');™—F–6²æ‡FÖÂ†ÆV F–æu¦W&ò†''™½
minutesView.append(tick);™—F–6²æöâ†Ö÷W6VF÷väWfVçBÂ Ö÷W6VF÷vâ™™™

™™™if ((space || moved) && x
=== dx && y === dy) {Ð™—6VÆbç6WD† æB‡,Â ™™™½Ðif (self.currentView === 'hours') {™™™Ð
self.toggleView('minutes', duration / 2);Ð™} else™™™{Ð–b †÷ F–öç2æ WFö6Æ÷6R™™™½
self.minutesView.addClass('clockpicker-dial-out');Ð™™™setTimeout(function(){™™™™Ð
self.done();Ð™™™}, duration / 2);™™™™½Ðplate.prepend(canvas);Ð™™Ð// Reset cursor style of
bodyÐ™clearTimeout(movingTimer);™™™Ðbody.removeClass('clockpicker-moving');Ð™™Ð//
Unbind mousemove eventÐ™$doc.off(mousemoveEvent);™™™½Ðif (svgSupported) {™™™Ðòò G& r
clock hands and othersÐ™—f " 6 çf 2 Ò ÷ ÷fW"æf–æB,ræ6Æö6· –6¶W"Ö6 çf 2r™™™Ïsvg =
createSvgElement('svg');Ð™—7frç6WD GG&–'WFR,v6Æ 72rÂ v6Æö6· –6¶W"×7frr™™½
svg.setAttribute('width', diameter);Ð™—7frç6WD GG&–'WFR,v†V–v‡BrÂ F– ÖWFW"™™½f "
g = createSvgElement('g');Ð™–rç6WD GG&–'WFR,wG& ç6f÷&ÒrÂ wG& ç6Æ FR,r ²
dialRadius + ',' + dialRadius + ')');Ð™—f " &V &–ær Ò 7&V FU7ftVÆVÖVçB,v6—&6ÆRr™™½
bearing.setAttribute('class', 'clockpicker-canvas-bearing');Ð™•
bearing.setAttribute('cx', 0);Ð™–&V &–ærç6WD GG&–'WFR,v7’rÂ ™™½
bearing.setAttribute('r', 2);Ð™—f " † æB Ò 7&V FU7ftVÆVÖVçB,vÆ–æRr™™½
hand.setAttribute('x1', 0);Ð™–† æBç6WD GG&–'WFR,w“ rÂ ™™½f " &r Ò
createSvgElement('circle');Ð™–&rç6WD GG&–'WFR,v6Æ 72rÂ v6Æö6· –6¶W"Ö6 çf 2Ö&rr™™½
bg.setAttribute('r', tickRadius);Ð™—f " fr Ò 7&V FU7ftVÆVÖVçB,v6—&6ÆRr™™½
fg.setAttribute('class', 'clockpicker-canvas-fg');Ð™–frç6WD GG&–'WFR,w"rÂ 2ãR™™½
g.appendChild(hand);Ð™–ræ VæD6†–ÆB†&r™™½ræ VæD6†–ÆB†fr™™½
g.appendChild(bearing);Ð™—7fræ VæD6†–ÆB†r™™½6 çf 2æ VæB‡7frÐ™½F†—2æ† æB Ò † æÇ™½
this.bg = bg;Ð™—F†—2æfr Ò f™½F†—2æ&V &–ær Ò &V &–æ™™½F†—2ær Ò ™™½F†—2æ6 çf 2 Ò
canvas;™™™ÐÐraiseCallback(this.options.init);™™™ÐgVæ7F–öâ
raiseCallback(callbackFunction) {Ðif (callbackFunction && typeof
callbackFunction === "function") {Ð–6 ÆÆ& 6´gVæ7F–öâ,™™™½Ðòò FVf VÇB ÷ F–öç™
ClockPicker.DEFAULTS = {Ð'default': '',   // default time, 'now' or
'13:14' e.g.Ðfromnow: 0,   // set default time to * milliseconds from
now (using with default = 'now')Ðplacement: 'bottom', // clock popover
placementÐalign: 'left',   // popover arrow alignÐdonetext: '[Œb ',   // done
button textÐautoclose: false,   // auto close when minute is selectedÐ
twelvehour: false, // change to 12 hour AM/PM clock from 24 hourÐvibrate:
true   // vibrate the device when dragging clock handÐÓ™™½Ðòò 6†÷r ÷" †–FR
popoverÐ™™™6Æö6µ –6¶W"ç &÷F÷G— RçFövvÆR Ò gVæ7F–öâ,™™™½this[this.isShown ? 'hide' :
'show']();™™™ÐÓ™™½Ðòò 6WB ÷ ÷fW" ÷6—F–öÍ6Æö6µ –6¶W"ç &÷F÷G— RæÆö6 FR Ò gVæ7F–öâ,™™™½
var element = this.element,Ð™— ÷ ÷fW" Ò F†—2ç ÷ ÷fW™™™Íöfg6WB Ò VÆVÖVçBæöfg6WB,™™™Í
width = element.outerWidth(),Ð™–†V–v‡B Ò VÆVÖVçBæ÷WFW$†V–v‡B,™™™Í Æ 6VÖVçB Ò
this.options.placement,Ð™– Æ–vâ Ò F†—2æ÷ F–öç2æ Æ–vâ™™™Í7G–ÆW2 Ò ·™™™Ö™™™Í6VÆb Ò F†—Ð™½
popover.show();Ð™// Place the popoverÐswitch (placement) {™™™Ð6 6R v&÷GFöÒ™™™
styles.top = offset.top + height;Ð™break;™™™Ð 6R w&–v‡BS™™™styles.left = offset.left
+ width;Ð™break;™™™Ð 6R wF÷ S™™™styles.top = offset.top - popover.outerHeight();™™™Ð
break;™™™Ð–6 6R vÆVgBS™™™styles.left = offset.left - popover.outerWidth();™™™™™™Ðbreak;™™™Ð//
Align the popover arrowÐswitch (align) {™™™Ð6 6R vÆVgBS™™™styles.left = offset.left;™™™Ð
break;™™™Ð–6 6R w&–v‡BS™™™styles.left = offset.left + width - popover.outerWidth();™™™Ð
break;™™™Ð–6 6R wF÷ S™™™styles.top = offset.top;™™™™™™Ðbreak;™™™Ð 6R v&÷GFöÒS™™™styles.top =
offset.top + height - popover.outerHeight();™™™™™™Ðbreak;™™™™™™Ðpopover.css(styles);™™™™™™ÐÐòò
Show popoverÐ™™™6Æö6µ –6¶W"ç &÷F÷G— Rç6†÷r Ò gVæ7F–öâ†R—™™™½// Not show again™™™Ð
(this.isShown) {™™™Ð—&WGW&™™™™™™

™—f " F &vWB Ò B†RçF &vWB™½–b ‡F &vWBæ6Æ÷6W7B‡6VÆbç ÷ ÷fW"'æÆVæwF,
=== 0 &&Ð™—F &vWBæ6Æ÷6W7B‡6VÆbæ FFöâ'æÆVæwF, ÓÓÒ ™Ðm
target.closest(self.input).length === 0) {Ð™self.hide();Ð/// Hide when ESC is
pressedÐ$doc.on('keyup.clockpicker.' + this.id, function(e){Ð–b †Ræ¶W"6öFR ÓÓÒ
27) {Ð™self.hide();ÐraiseCallback(this.options.afterShow);ÐÒòò †–FR ÷ ÷fW•
ClockPicker.prototype.hide = function(){Ð
raiseCallback(this.options.beforeHide);Ðthis.isShown = falseÐ// Unbinding
events on documentÐ$doc.off('click.clockpicker.' + this.id + '
focusin.clockpicker.' + this.id);Ð$doc.off('keyup.clockpicker.' + this.id);Ð
this.popover.hide();ÐraiseCallback(this.options.afterHide);ÐÒòò FövvÆR Fò
hours or minutes viewÐ6Æö6µ –6¶W"ç &÷F÷G— RçFövvÆUf–Wr Ò gVæ7F–öâ‡f–WrÂ FVÆ '—½
var raiseAfterHourSelect = false;Ðif (view === 'minutes' &&
$(this.hoursView).css("visibility") === "visible") {Ð•
raiseCallback(this.options.beforeHourSelect);Ð—& —6T gFW$†÷W%6VÆV7B Ò G'VS½Ðvar
isHours = view === 'hours',Ð–æW‡Ef–Wr Ò —4†÷W'2 ò F†—2æ†÷W'5f–Wr ¢
this.minutesView,Ð–†–FUf–Wr Ò —4†÷W'2 ò F†—2æÖ–çWFW5f–Wr ¢ F†—2æ†÷W'5f–WÐ½
this.currentView = view;Ðthis.spanHours.toggleClass('text-primary', isHours);Ð
this.spanMinutes.toggleClass('text-primary', ! isHours);Ð// Let's make
transitionsÐhideView.addClass('clockpicker-dial-out');Ð
nextView.css('visibility', 'visible').removeClass('clockpicker-dial-out');Ð//
Reset clock handÐthis.resetClock(delay);Ð// After transitions endedÐ
clearTimeout(this.toggleViewTimer);Ðthis.toggleViewTimer =
setTimeout(function(){Ð–†–FUf–Wræ772,wf—6–&–Æ—G'rÂ v†–FFVâr™½, duration);Ðif
(raiseAfterHourSelect) {Ð—& —6T6 ÆÆ& 6²‡F†—2æ÷ F–öç2æ gFW$†÷W%6VÆV7B™½ÓÒòò
Reset clock handÐ6Æö6µ –6¶W"ç &÷F÷G— Rç&W6WD6Æö6² Ò gVæ7F–öâ†FVÆ '—½var view =
this.currentView,Ð—f ÇVR Ò F†—5·f–WuÒÍ—4†÷W'2 Ò f–Wr ÓÓÒ v†÷W'2™ÍVæ—B Ò
Math.PI / (isHours ? 6 : 30),Ð—& F– â Ò f ÇVR ¢ Væ—Ð™Í& F—W2 Ò —4†÷W'2 bb f ÇVR
> 0 && value < 13 ? innerRadius : outerRadius,Ð—, Ò Ö F,ç6–â‡& F– â' ¢ & F—W2™Í'
= - Math.cos(radian) * radius,Ð—6VÆb Ò F†—3½f (svgSupported && delay) {Ð
self.canvas.addClass('clockpicker-canvas-out');Ð—6WEF–ÖV÷WB†gVæ7F–öâ,™½
self.canvas.removeClass('clockpicker-canvas-out');Ð™self.setHand(x, y);ÐÂ
delay);Ð} else {ÐF†—2ç6WD† æB‡,Â '™½ÓÒòò 6WB 6Æö6² † æB Fò ‡,Â '•
ClockPicker.prototype.setHand = function(x, y, roundBy5, dragging){Ðvar radian
= Math.atan2(x, - y),Ð—–4†÷W'2 Ò F†—2æ7W'&VçEf–Wr ÓÓÒ v†÷W'2™ÍVæ—B Ò Ö F,å ' ò
(isHours || roundBy5 ? 6 : 30),Ð—¢ Ò Ö F,ç7 'B‡, ¢ , ² ' ¢ '™Í÷ F–öç2 Ò
this.options,Ð––ææW" Ò —4†÷W'2 bb ¢ Â †÷WFW%& F—W2 ² –ææW%& F—W2' ò ™Í& F—W2 Ò
inner ? innerRadius : outerRadius,Ð—f ÇVS½–b †÷ F–öç2çGvVÇfV†÷W"'™½radius =
outerRadius;ÐÐÝ// Radian should in range [0, 2PI]Ðif (radian < 0) {Ð& F– â Ò
Math.PI * 2 + radian;ÐÐÐ// Get the round valueÐvalue = Math.round(radian / unit);Ð
™// Get the round radianÐradian = value * unitÐÐ// Correct the hours or minutesÐ
if (options.twelvehour) {Ð––b †—4†÷W'2'™½if (value === 0)™½Ð ÇVR Ò ™½Ò VÇ6R™½
if (roundBy5) {Ð™—f ÇVR £Ò™½Ðif (value === 60)™½Ð ÇVR Ò™½Ð else ™Ð–b
(isHours) {Ð™if (value === 12)™½Ð ÇVR Ò™½Ðvalue = inner ? (value === 0 ? 12 :
value) : value === 0 ? 0 : value + 12;Ð—Ò VÇ6R™½if (roundBy5)™½Ð ÇVR £Ò™½Ðif
(value === 60) {Ð™—f ÇVR Ò™½Ð// Once hours or minutes changed, vibrate the
deviceÐif (this[this.currentView] !== value) {Ð–b ‡f–'& FR bb
this.options.vibrate) {Ð™// Do not vibrate too frequentlyÐif (!
this.vibrateTimer) {Ð™–æ f–v F÷%·f–'& FUÒƒ ™½F†—2çf–'& FUF–ÖW" Ò
setTimeout($.proxy(function(){Ð™this.vibrateTimer = nullÐÂ F†—2'Â ™½Ð
this[this.currentView] = value;Ðthis[isHours ? 'spanHours' :
'spanMinutes'].html(leadingZero(value));Ð// If svg is not supported, just add
an active class to the tickÐif (! svgSupported) {ÐF†—5¶—4†÷W'2 ò v†÷W'5f–Wrr ¢
'minutesView'].find('.clockpicker-tick').each(function(){Ð™var tick = $(this);Ð
tick.toggleClass('active', value === + tick.html());Ð—Ò™½&WGW&a½Ð// Place clock
hand at the top when draggingÐif (dragging || (! isHours && value % 5)) {Ð
this.g.insertBefore(this.hand, this.bearing);Ð—F†—2æræ–ç6W'D&Vf÷&R‡F†—2æ&rÂ
this.fg);Ð—F†—2æ&rç6WD GG&–'WFR,v6Æ 72rÂ v6Æö6· –6¶W"Ö6 çf 2Ö&r 6Æö6· –6¶W"Ð
canvas-bg-trans');Ð} else {Ðòò ÷" Æ 6R —B B F†R &÷GFÒÝ
this.g.insertBefore(this.hand, this.bg);Ð—F†—2æræ–ç6W'D&Vf÷&R‡F†—2æfrÂ F†—2æ&r™½
this.bg.setAttribute('class', 'clockpicker-canvas-bg');Ð

™™™

public\assets\js\plugins\codemirror\mode\apl\apl.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("apl", function() {Ð var builtInOps = {Ð   ".":
"innerProduct",Ð   "\\": "scan",Ð   "/": "reduce",Ð   "#?": "reduce1Axis",Ð
"#@": "scan1Axis",Ð "¨": "each",Ð   "#c": "power"Ð};Ð var builtInFuncs = {Ð
"+": ["conjugate", "add"],Ð   "" ": ["negate", "subtract"],Ð "×": ["signOf",
"multiply"],Ð   "÷": ["reciprocal", "divide"],Ð   "# ": ["ceiling",
"greaterOf"],Ð   "# ": ["floor", "lesserOf"],Ð ""#": ["absolute", "residue"],Ð
    "#s": ["indexGenerate", "indexOf"],Ð "?": ["roll", "deal"],Ð   ""Æ":
["exponentiate", "toThePowerOf"],Ð   "#_": ["naturalLog", "logToTheBase"],Ð
"%Ë": ["piTimes", "circularFuncs"],Ð "!": ["factorial", "binomial"],Ð   "#9":
["matrixInverse", "matrixDivide"],Ð   "<": [null, "lessThan"],Ð   ""d": [null,
"lessThanOrEqual"],Ð   "=": [null, "equals"],Ð   ">": [null, "greaterThan"],Ð
    ""e": [null, "greaterThanOrEqual"],Ð ""`": [null, "notEqual"],Ð ""a":
["depth", "match"],Ð   ""b": [null, "notMatch"],Ð "" ": ["enlist",
"membership"],Ð   "#w": [null, "find"],Ð ""*": ["unique", "union"],Ð ""(": [null, "intersection"],Ð   ""<": ["not", "without"],Ð ""(": [null, "or"],Ð
""'": [null, "and"],Ð "#q": [null, "nor"],Ð "#r": [null, "nand"],Ð "#t":
["shapeOf", "reshape"],Ð   ",": ["ravel", "catenate"],Ð   "#j": [null,
"firstAxisCatenate"],Ð   "#=": ["reverse", "rotate"],Ð ""–": ["axis1Reverse",
"axis1Rotate"],Ð   "#I": ["transpose", null],Ð "!‘": ["first", "take"],Ð "!“":
[null, "drop"],Ð   "",": ["enclose", "partitionWithAxis"],Ð ""ƒ": ["diclose",
"pick"],Ð   "#7": [null, "index"],Ð "#K": ["gradeUp", null],Ð "#R":
["gradeDown", null],Ð   ""¤": ["encode", null],Ð ""¥": ["decode", null],Ð "#U":
["format", "formatByExample"],Ð   "#N": ["execute", null],Ð ""£": ["stop",
"left"],Ð   ""¢": ["pass", "right"]Ð};Ð var isOperator = /[\.\/#?#@¨#¯/];Ð var
isNiladic = /#l/;Ð var isFunction = /[\+" ×÷# # "##s\?¯Æ#_%ÊÆ#9ewd=>/e*/;Ð var
isComment = /[#]#].*$Ð;Ð var stringEater = function(type) {Ð   var prev;Ð
prev = false;Ð   return function(c) {Ð     prev = c;Ð     if (c === type) {Ð
        return prev === "\\";Ð     }Ð     return true;Ð   };Ð };Ð return {Ð
startState: function() {Ð     return {Ð       prev: false,Ð       func: false,Ð
        op: false,Ð       string: false,Ð       escape: false Ð     };Ð   },Ð
    token: function(stream, state) {Ð     var ch, funcName, word;Ð     if
(stream.eatSpace()) {Ð       return null;Ð     }Ð     ch = stream.next();Ð
      if (ch === '"' || ch === "'") {Ð       stream.eatWhile(stringEater(ch));Ð
        stream.next();Ð       state.prev = true;Ð       return "string";Ð
      }Ð     if (/[\[{\(]/.test(ch)) {Ð       state.prev = false;Ð
return null;Ð     }Ð     if (/[\]}\)]/.test(ch)) {Ð       state.prev = true;Ð
        return null;Ð     }Ð     if (isNiladic.test(ch)) {Ð       state.prev
= false;Ð       return "niladic";Ð     }Ð     if (/[¯\d]/.test(ch)) {Ð
if (state.func) {Ð         state.func = false;Ð         state.prev = false;Ð
        } else {Ð         state.prev = true;Ð       }Ð       stream.eatWhile(/
[\w\.]/);Ð       return "number";Ð     }Ð     if (isOperator.test(ch)) {Ð
        return "operator apl-" + builtInOps[ch];Ð     }Ð     if
(isArrow.test(ch)) {Ð       return "apl-arrow";Ð     }Ð     if
(isFunction.test(ch)) {Ð       funcName = "apl-";Ð       if
(builtInFuncs[ch] != null) {Ð         if (state.prev) {Ð           funcName
+= builtInFuncs[ch][1];Ð         } else {Ð           funcName +=
builtInFuncs[ch][0];Ð         }Ð       }Ð       state.func = true;Ð
state.prev = false;Ð       return "function " + funcName;Ð     }Ð     if
(isComment.test(ch)) {Ð       stream.skipToEnd();Ð       return "comment";Ð
      }Ð     if (ch === "" " && stream.peek() === ".") {Ð     stream.next();Ð
        return "function jot-dot";Ð     }Ð     stream.eatWhile(/[\w\$_]/);Ð
      word = stream.current();Ð     state.prev = true;Ð     return "keyword";Ð
    }Ð
```

```
};Ð));ÐodeMirror.defineMIME("text/apl", "apl");Ð));Ð
```

public\assets\js\plugins\codemirror\mode\asterisk\asterisk.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð*Ð* ======================
==============================================================Ð*Ð*
Filename:  mode/asterisk/asterisk.js Ð*Ð*    Description:  CodeMirror mode for
Asterisk dialplan Ð*Ð*        Created:  05/17/2012 09:20:25 PM Ð*
Revision:  none Ð*Ð*         Author:  Stas Kobzar (stas@modulis.ca), Ð*
Company:  Modulis.ca Inc. Ð*Ð* ================================================
=====================================Ð*/Ð function(mod) {Ð if (typeof exports
== "object" && typeof module == "object") // CommonJS Ð   mod(require("../../
lib/codemirror"));Ð else if (typeof define == "function" && define.amd) // AMD Ð
    define(["../../lib/codemirror"], mod);Ð else // Plain browser env Ð
mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("asterisk", function() {Ð var atoms    = ["exten",
"same", "include","ignorepat","switch"],Ð     dpcmd    = ["#include","#exec"],Ð
      apps     = [Ð                  "addqueuemember","adsiprog","aelsub","agen
tlogin","agentmonitoroutgoing","agi",Ð
"alarmreceiver","amd","answer","authenticate","background","backgrounddetect",Ð

"bridge","busy","callcompletioncancel","callcompletionrequest","celgenuserevent",Ð

"changemonitor","chanisavail","channelredirect","chanspy","clearhash","confbridge",Ð

"congestion","continuewhile","controlplayback","dahdiacceptr2call","dahdibarge",Ð

"dahdiras","dahdiscan","dahdisendcallreroutingfacility","dahdisendkeypadfacility",Ð

"datetime","dbdel","dbdeltree","deadagi","dial","dictate","directory","disa",Ð

"dumpchan","eagi","echo","endwhile","exec","execif","execiftime","exitwhile","extenspy",Ð

"externalivr","festival","flash","followme","forkcdr","getcpeid","gosub","gosubif",Ð

"goto","gotoif","gotoiftime","hangup","iax2provision","ices","importvar","incomplete",Ð

"ivrdemo","jabberjoin","jabberleave","jabbersend","jabbersendgroup","jabberstatus",Ð

"jack","log","macro","macroexclusive","macroexit","macroif","mailboxexists","meetme",Ð

"meetmeadmin","meetmechanneladmin","meetmecount","milliwatt","minivmaccmess","minivmdelete

"minivmgreet","minivmmwi","minivmnotify","minivmrecord","mixmonitor","monitor","morsecode"

"mp3player","mset","musiconhold","nbscat","nocdr","noop","odbc","odbc","odbcfinish",Ð

"originate","ospauth","ospfinish","osplookup","ospnext","page","park","parkandannounce",Ð

"parkedcall","pausemonitor","pausequeuemember","pickup","pickupchan","playback","playtones

"privacymanager","proceeding","progress","queue","queuelog","raiseexception","read","reade

"readfile","receivefax","receivefax","receivefax","record","removequeuemember",Ð

"resetcdr","retrydial","return","ringing","sayalpha","saycountedadj","saycountednoun",Ð

"saycountpl","saydigits","saynumber","sayphonetic","sayunixtime","senddtmf","sendfax",Ð

"sendfax","sendfax","sendimage","sendtext","sendurl","set","setamaflags",Ð

"setcallerpres","setmusiconhold","sipaddheader","sipdtmfmode","sipremoveheader","skel",Ð
```

```
"slastation","slatrunk","sms","softhangup","speechactivategrammar","speechbackground",Ð

"speechcreate","speechdeactivategrammar","speechdestroy","speechloadgrammar","speechproces

"speechstart","speechunloadgrammar","stackpop","startmusiconhold","stopmixmonitor","stopmo

"stopmusiconhold","stopplaytones","system","testclient","testserver","transfer","tryexec",

"trysystem","unpausemonitor","unpausequeuemember","userevent","verbose","vmauthenticate",Ð

"vmsayname","voicemail","voicemailmain","wait","waitexten","waitfornoise","waitforring",Ð

"waitforsilence","waitmusiconhold","waituntil","while","zapateller"Ð
                  ];Ð function basicToken(stream,state){Ð   var cur = '';Ð
var ch  = '';Ð   ch = stream.next();Ð   // commentÐ   if(ch == ";") {Ð
stream.skipToEnd();Ð     return "comment";Ð   }Ð   // contextÐ   if(ch ==
'[') {Ð     stream.skipTo(']');Ð     stream.eat(']');Ð     return "header";Ð
    }Ð   // stringÐ   if(ch == '"') {Ð     stream.skipTo('"');Ð     return
"string";Ð   }Ð   if(ch == "'") {Ð     stream.skipTo("'");Ð     return
"string-2";Ð   }Ð   // dialplan commandsÐ   if(ch == '#') {Ð
stream.eatWhile(/\w/);Ð     cur = stream.current();Ð
if(dpcmd.indexOf(cur) !== -1) {Ð       stream.skipToEnd();Ð       return
"strong";Ð     }Ð   }Ð   // application argsÐ   if(ch == '$'){Ð     var ch1 =
stream.peek();Ð     if(ch1 == '{'){Ð       stream.skipTo('}');Ð
stream.eat('}');Ð       return "variable-3";Ð     }Ð   }Ð   // extensionÐ
stream.eatWhile(/\w/);Ð   cur = stream.current();Ð   if(atoms.indexOf(cur) !
== -1) {Ð     state.extenStart = true;Ð     switch(cur) {Ð       case 'same':
state.extenSame = true; break;Ð       case 'include':Ð       case 'switch':Ð
        case 'ignorepat':Ð         state.extenInclude = true;break;Ð
default:break;Ð     }Ð     return "atom";Ð   }Ð }Ð return {Ð   startState:
function() {Ð     return {Ð       extenStart: false,Ð       extenSame:  false,Ð
        extenInclude: false,Ð       extenExten: false,Ð       extenPriority:
false,Ð       extenApplication: falseÐ     };Ð   },Ð   token:
function(stream, state) {Ð     var cur = '';Ð     var ch  = '';Ð
if(stream.eatSpace()) return null;Ð     // extension startedÐ
if(state.extenStart){Ð       stream.eatWhile(/[^\s]/);Ð       cur =
stream.current();Ð       if(/^=>?$/.test(cur)){Ð         state.extenExten =
true;Ð         state.extenStart = false;Ð         return "strong";Ð       }
else {Ð         state.extenStart = false;Ð         stream.skipToEnd();Ð
          return "error";Ð       }Ð     } else if(state.extenExten) {Ð
        // set exten and priorityÐ       state.extenExten = false;Ð
state.extenPriority = true;Ð       stream.eatWhile(/[^,]/);Ð
if(state.extenInclude) {Ð         stream.skipToEnd();Ð
state.extenPriority = false;Ð         state.extenInclude = false;Ð       }Ð
        if(state.extenSame) {Ð         state.extenPriority = false;Ð
state.extenSame = false;Ð         state.extenApplication = true;Ð       }Ð
        return "tag";Ð     } else if(state.extenPriority) {Ð
state.extenPriority = false;Ð       state.extenApplication = true;Ð       ch
= stream.next(); // get commaÐ       if(state.extenSame) return null;Ð
stream.eatWhile(/[^,]/);Ð       return "number";Ð     } else
if(state.extenApplication) {Ð       stream.eatWhile(/,/);Ð       cur =
stream.current();Ð       if(cur === ',') return null;Ð       stream.eatWhile(/
\w/);Ð       cur = stream.current().toLowerCase();Ð
state.extenApplication = false;Ð       if(apps.indexOf(cur) !== -1){Ð
return "def strong";Ð       }Ð     } else{Ð       return
basicToken(stream,state);Ð     }Ð     return null;Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("text/x-asterisk", "asterisk");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\clike\clike.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("clike", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit,Ð     statementIndentUnit =
parserConfig.statementIndentUnit || indentUnit,Ð     dontAlignCalls =
parserConfig.dontAlignCalls,Ð     keywords = parserConfig.keywords || {},Ð
      builtin = parserConfig.builtin || {},Ð     blockKeywords =
parserConfig.blockKeywords || {},Ð     atoms = parserConfig.atoms || {},Ð
hooks = parserConfig.hooks || {},Ð     multiLineStrings =
parserConfig.multiLineStrings,Ð     indentStatements =
parserConfig.indentStatements !== false;Ð var isOperatorChar = /[+\-*&%=<>!?|
\/]/;Ð var curPunc;Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (hooks[ch]) {Ð     var result = hooks[ch](stream, state);Ð
      if (result !== false) return result;Ð   }Ð   if (ch == '"' || ch ==
"'") {Ð     state.tokenize = tokenString(ch);Ð     return
state.tokenize(stream, state);Ð   }Ð   if (/[\[\]{}\(\),;\:\.]/.test(ch)) {Ð
      curPunc = ch;Ð     return null;Ð   }Ð   if (/\d/.test(ch)) {Ð
stream.eatWhile(/[\w\.]/);Ð     return "number";Ð   }Ð   if (ch == "/") {Ð
      if (stream.eat("*")) {Ð       state.tokenize = tokenComment;Ð
return tokenComment(stream, state);Ð     }Ð     if (stream.eat("/")) {Ð
stream.skipToEnd();Ð       return "comment";Ð     }Ð   }Ð   if
(isOperatorChar.test(ch)) {Ð     stream.eatWhile(isOperatorChar);Ð     return
"operator";Ð   }Ð   stream.eatWhile(/[\w\$_\xa1-\uffff]/);Ð   var cur =
stream.current();Ð   if (keywords.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "keyword";Ð   }Ð   if (builtin.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "builtin";Ð   }Ð   if (atoms.propertyIsEnumerable(cur)) return "atom";Ð
    return "variable";Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, next, end = false;Ð
while ((next = stream.next()) != null) {Ð       if (next == quote && !
escaped) {end = true; break;}Ð       escaped = !escaped && next == "\\";Ð
      }Ð     if (end || !(escaped || multiLineStrings))Ð       state.tokenize
= null;Ð     return "string";Ð   };Ð }Ð function tokenComment(stream, state) {Ð
    var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if (ch ==
"/" && maybeEnd) {Ð       state.tokenize = null;Ð       break;Ð     }Ð
maybeEnd = (ch == "*");Ð   }Ð   return "comment";Ð }Ð function
Context(indented, column, type, align, prev) {Ð   this.indented = indented;Ð
    this.column = column;Ð   this.type = type;Ð   this.align = align;Ð
this.prev = prev;Ð }Ð function pushContext(state, col, type) {Ð   var indent
= state.indented;Ð   if (state.context && state.context.type == "statement")Ð
      indent = state.context.indented;Ð   return state.context = new
Context(indent, col, type, null, state.context);Ð }Ð function
popContext(state) {Ð   var t = state.context.type;Ð   if (t == ")" || t ==
"]" || t == "}")Ð     state.indented = state.context.indented;Ð   return
state.context = state.context.prev;Ð }Ð // Interface Ð return {Ð   startState:
function(basecolumn) {Ð     return {Ð       tokenize: null,Ð       context:
new Context((basecolumn || 0) - indentUnit, 0, "top", false),Ð
indented: 0,Ð       startOfLine: true Ð     };Ð   },Ð   token:
function(stream, state) {Ð     var ctx = state.context;Ð     if
(stream.sol()) {Ð       if (ctx.align == null) ctx.align = false;Ð
state.indented = stream.indentation();Ð       state.startOfLine = true;Ð     }Ð
      if (stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style
= (state.tokenize || tokenBase)(stream, state);Ð     if (style == "comment"
|| style == "meta") return style;Ð
```

```
                                        if (ctx.align == null) ctx.align =
true;Ð     if ((curPunc == ";" || curPunc == ":" || curPunc == ",") &&
ctx.type == "statement") popContext(state);Ð     else if (curPunc == "{")
pushContext(state, stream.column(), "}");Ð     else if (curPunc == "[")
pushContext(state, stream.column(), "]");Ð     else if (curPunc == "(")
pushContext(state, stream.column(), ")");Ð     else if (curPunc == "}") {Ð
        while (ctx.type == "statement") ctx = popContext(state);Ð       if
(ctx.type == "}") ctx = popContext(state);Ð       while (ctx.type ==
"statement") ctx = popContext(state);Ð     }Ð     else if (curPunc ==
ctx.type) popContext(state);Ð     else if (indentStatements &&Ð
(((ctx.type == "}" || ctx.type == "top") && curPunc != ';') ||Ð
(ctx.type == "statement" && curPunc == "newstatement")))Ð
pushContext(state, stream.column(), "statement");Ð     state.startOfLine =
false;Ð     return style;Ð   },Ð   indent: function(state, textAfter) {Ð
if (state.tokenize != tokenBase && state.tokenize != null) return
CodeMirror.Pass;Ð     var ctx = state.context, firstChar = textAfter &&
textAfter.charAt(0);Ð     if (ctx.type == "statement" && firstChar == "}")
ctx = ctx.prev;Ð     var closing = firstChar == ctx.type;Ð     if (ctx.type
== "statement") return ctx.indented + (firstChar == "{" ? 0 :
statementIndentUnit);Ð     else if (ctx.align && (!dontAlignCalls ||
ctx.type != ")")) return ctx.column + (closing ? 0 : 1);Ð     else if
(ctx.type == ")" && !closing) return ctx.indented + statementIndentUnit;Ð
else return ctx.indented + (closing ? 0 : indentUnit);Ð   },Ð
electricChars: "{}",Ð   blockCommentStart: "/*",Ð   blockCommentEnd: "*/",Ð
lineComment: "//",Ð   fold: "brace"Ð };Ð);Ð function words(str) {Ð   var obj
= {}, words = str.split(" ");Ð   for (var i = 0; i < words.length; ++i)
obj[words[i]] = true;Ð   return obj;Ð }Ð var cKeywords = "auto if break int
case long char register continue return default short do sizeof " +Ð
"double static else struct entry switch extern typedef float union for
unsigned " +Ð   "goto while enum void const signed volatile";Ð function
cppHook(stream, state) {Ð   if (!state.startOfLine) return false;Ð   for (;;)
{Ð     if (stream.skipTo("\\")) {Ð       stream.next();Ð       if
(stream.eol()) {Ð         state.tokenize = cppHook;Ð         break;Ð       }Ð
      } else {Ð       stream.skipToEnd();Ð       state.tokenize = null;Ð
        break;Ð     }Ð   }Ð   return "meta";Ð }Ð function
cpp11StringHook(stream, state) {Ð   stream.backUp(1);Ð   // Raw strings.Ð
if (stream.match(/(R|u8R|uR|UR|LR)/)) {Ð     var match = stream.match(/"([^\s\
\()]{0,16})\(/);Ð     if (!match) {Ð       return false;Ð     }Ð
state.cpp11RawStringDelim = match[1];Ð     state.tokenize = tokenRawString;Ð
      return tokenRawString(stream, state);Ð   }Ð   // Unicode strings/chars.Ð
    if (stream.match(/(u8|u|U|L)/)) {Ð     if (stream.match(/["']/, /* eat */
false)) {Ð       return "string";Ð     }Ð     return false;Ð   }Ð   // Ignore
this hook.Ð   stream.next();Ð   return false;Ð }Ð // C#-style strings where
"" escapes a quote.Ð function tokenAtString(stream, state) {Ð   var next;Ð
while ((next = stream.next()) != null) {Ð     if (next == '"' && !
stream.eat('"')) {Ð       state.tokenize = null;Ð       break;Ð     }Ð   }Ð
return "string";Ð }Ð // C++11 raw string literal is
<prefix>"<delim>( anything )<delim>", whereÐ // <delim> can be a string up to
16 characters long.Ð function tokenRawString(stream, state) {Ð   // Escape
characters that have special regex meanings.Ð   var delim =
state.cpp11RawStringDelim.replace(/[^\w\s]/g, '\\$&');Ð   var match =
stream.match(new RegExp(".*?\\)" + delim + '"'));Ð   if (match)Ð
state.tokenize = null;Ð   elseÐ     stream.skipToEnd();Ð   return "string";Ð }Ð
  function def(mimes, mode) {Ð   if (typeof mimes == "string") mimes =
[mimes];Ð   var words = [];Ð   function add(obj) {Ð     if (obj) for (var
prop in obj) if (obj.hasOwnProperty(prop))Ð       words.push(prop);Ð   }Ð
add(mode.keywords);Ð   add(mode.builtin);Ð   add(mode.atoms);Ð   if
(words.length) {Ð     mode.helperType = mimes[0];Ð
CodeMirror.registerHelper("hintWords", mimes[0], words);Ð   }Ð   for (var i =
0; i < mimes.length; ++i)Ð
```

```
                                CodeMirror.defineMIME(mimes[i], mode);Ð }Ð
def(["text/x-csrc", "text/x-c", "text/x-chdr"], {Ð   name: "clike",Ð
keywords: words(cKeywords),Ð   blockKeywords: words("case do else for if
switch while struct"),Ð   atoms: words("null"),Ð   hooks: {"#": cppHook},Ð
modeProps: {fold: ["brace", "include"]}Ð });Ð def(["text/x-c++src", "text/x-c+
+hdr"], {Ð   name: "clike",Ð   keywords: words(cKeywords + " asm dynamic_cast
namespace reinterpret_cast try bool explicit new " +Ð
"static_cast typeid catch operator template typename class friend private " +Ð
                    "this using const_cast inline public throw virtual delete
mutable protected " +Ð                   "wchar_t alignas alignof constexpr
decltype nullptr noexcept thread_local final " +Ð
"static_assert override"),Ð   blockKeywords: words("catch class do else
finally for if struct switch try while"),Ð   atoms: words("true false null"),Ð
    hooks: {Ð     "#": cppHook,Ð     "u": cpp11StringHook,Ð     "U":
cpp11StringHook,Ð     "L": cpp11StringHook,Ð     "R": cpp11StringHookÐ   },Ð
    modeProps: {fold: ["brace", "include"]}Ð });Ð def("text/x-java", {Ð
name: "clike",Ð   keywords: words("abstract assert boolean break byte case
catch char class const continue default " +Ð                   "do double
else enum extends final finally float for goto if implements import " +Ð
                    "instanceof int interface long native new package private
protected public " +Ð                   "return short static strictfp super
switch synchronized this throw throws transient " +Ð                   "try
void volatile while"),Ð   blockKeywords: words("catch class do else finally
for if switch try while"),Ð   atoms: words("true false null"),Ð   hooks: {Ð
      "@": function(stream) {Ð       stream.eatWhile(/[\w\$_]/);Ð
return "meta";Ð     }Ð   },Ð   modeProps: {fold: ["brace", "import"]}Ð });Ð
def("text/x-csharp", {Ð   name: "clike",Ð   keywords: words("abstract as base
break case catch checked class const continue" +Ð                   " default
delegate do else enum event explicit extern finally fixed for" +Ð
                    " foreach goto if implicit in interface internal is lock
namespace new" +Ð                   " operator out override params private
protected public readonly ref return sealed" +Ð                   " sizeof
stackalloc static struct switch this throw try typeof unchecked" +Ð
                    " unsafe using virtual void volatile while add alias
ascending descending dynamic from get" +Ð                   " global group
into join let orderby partial remove select set value var yield"),Ð
blockKeywords: words("catch class do else finally for foreach if struct
switch try while"),Ð   builtin: words("Boolean Byte Char DateTime
DateTimeOffset Decimal Double" +Ð                   " Guid Int16 Int32 Int64
Object SByte Single String TimeSpan UInt16 UInt32" +Ð                   "
UInt64 bool byte char decimal double short int long object"  +Ð
                    " sbyte float string ushort uint ulong"),Ð   atoms:
words("true false null"),Ð   hooks: {Ð     "@": function(stream, state) {Ð
        if (stream.eat('"')) {Ð         state.tokenize = tokenAtString;Ð
          return tokenAtString(stream, state);Ð       }Ð
stream.eatWhile(/[\w\$_]/);Ð       return "meta";Ð     }Ð   }Ð });Ð function
tokenTripleString(stream, state) {Ð   var escaped = false;Ð   while (!
stream.eol()) {Ð     if (!escaped && stream.match('""')) {Ð
state.tokenize = null;Ð       break;Ð     }Ð     escaped = stream.next() != "\
\" && !escaped;Ð   }Ð   return "string";Ð }Ð def("text/x-scala", {Ð   name:
"clike",Ð   keywords: words(Ð     /* scala */Ð     "abstract case catch class
def do else extends false final finally for forSome if " +Ð     "implicit
import lazy match new null object override package private protected return "
+Ð     "sealed super this throw trait try trye type val var while with yield
_ : = => <- <: " +Ð     "<% >: # @ " +Ð     /* package scala */Ð     "assert
assume require print println printf readLine readBoolean readByte readShort "
+Ð     "readChar readInt readLong readFloat readDouble " +Ð     "AnyVal App
Application Array BufferedIterator BigDecimal BigInt Char Console Either " +Ð
      "Enumeration Equiv Error Exception Fractional Function IndexedSeq
Integral Iterable " +Ð
```

"Iterator List Map Numeric Nil NotNull Option Ordered Ordering PartialFunction PartialOrdering " +Ð "Product Proxy Range Responder Seq Serializable Set Specializable Stream StringBuilder " +Ð "StringContext Symbol Throwable Traversable TraversableOnce Tuple Unit Vector :: #:: " +Ð /* package java.lang */Ð "Boolean Byte Character CharSequence Class ClassLoader Cloneable Comparable " +Ð "Compiler Double Exception Float Integer Long Math Number Object Package Pair Process " +Ð "Runtime Runnable SecurityManager Short StackTraceElement StrictMath String " +Ð "StringBuffer System Thread ThreadGroup ThreadLocal Throwable Triple Void"Ð),Ð multiLineStrings: true,Ð blockKeywords: words("catch class do else finally for forSome if match switch try while"),Ð atoms: words("true false null"),Ð indentStatements: false,Ð hooks: {Ð "@": function(stream) {Ð stream.eatWhile(/[\w\$_]/);Ð return "meta";Ð },Ð '"': function(stream, state) {Ð if (!stream.match('"""')) return false;Ð state.tokenize = tokenTripleString;Ð return state.tokenize(stream, state);Ð }Ð }Ð });Ð def(["x-shader/x-vertex", "x-shader/x-fragment"], {Ð name: "clike",Ð keywords: words("float int bool void " +Ð "vec2 vec3 vec4 ivec2 ivec3 ivec4 bvec2 bvec3 bvec4 " +Ð "mat2 mat3 mat4 " +Ð "sampler1D sampler2D sampler3D samplerCube " +Ð "sampler1DShadow sampler2DShadow" +Ð "const attribute uniform varying " +Ð "break continue discard return " +Ð "for while do if else struct " +Ð "in out inout"),Ð blockKeywords: words("for while do if else struct"),Ð builtin: words("radians degrees sin cos tan asin acos atan " +Ð "pow exp log exp2 sqrt inversesqrt " +Ð "abs sign floor ceil fract mod min max clamp mix step smootstep " +Ð "length distance dot cross normalize ftransform faceforward " +Ð "reflect refract matrixCompMult " +Ð "lessThan lessThanEqual greaterThan greaterThanEqual " +Ð "equal notEqual any all not " +Ð "texture1D texture1DProj texture1DLod texture1DProjLod " +Ð "texture2D texture2DProj texture2DLod texture2DProjLod " +Ð "texture3D texture3DProj texture3DLod texture3DProjLod " +Ð "textureCube textureCubeLod " +Ð "shadow1D shadow2D shadow1DProj shadow2DProj " +Ð "shadow1DLod shadow2DLod shadow1DProjLod shadow2DProjLod " +Ð "dFdx dFdy fwidth " +Ð "noise1 noise2 noise3 noise4"),Ð atoms: words("true false " +Ð "gl_FragColor gl_SecondaryColor gl_Normal gl_Vertex " +Ð "gl_MultiTexCoord0 gl_MultiTexCoord1 gl_MultiTexCoord2 gl_MultiTexCoord3 " +Ð "gl_MultiTexCoord4 gl_MultiTexCoord5 gl_MultiTexCoord6 gl_MultiTexCoord7 " +Ð "gl_FogCoord " +Ð "gl_Position gl_PointSize gl_ClipVertex " +Ð "gl_FrontColor gl_BackColor gl_FrontSecondaryColor gl_BackSecondaryColor " +Ð "gl_TexCoord gl_FogFragCoord " +Ð "gl_FragCoord gl_FrontFacing " +Ð "gl_FragColor gl_FragData gl_FragDepth " +Ð "gl_ModelViewMatrix gl_ProjectionMatrix gl_ModelViewProjectionMatrix " +Ð "gl_TextureMatrix gl_NormalMatrix gl_ModelViewMatrixInverse " +Ð "gl_ProjectionMatrixInverse gl_ModelViewProjectionMatrixInverse " +Ð "gl_TexureMatrixTranspose gl_ModelViewMatrixInverseTranspose " +Ð "gl_ProjectionMatrixInverseTranspose " +Ð "gl_ModelViewProjectionMatrixInverseTranspose " +Ð "gl_TextureMatrixInverseTranspose " +Ð "gl_NormalScale gl_DepthRange gl_ClipPlane " +Ð "gl_Point gl_FrontMaterial gl_BackMaterial gl_LightSource gl_LightModel " +Ð "gl_FrontLightModelProduct gl_BackLightModelProduct " +Ð "gl_TextureColor gl_EyePlaneS gl_EyePlaneT gl_EyePlaneR gl_EyePlaneQ " +Ð "gl_FogParameters " +Ð "gl_MaxLights gl_MaxClipPlanes gl_MaxTextureUnits gl_MaxTextureCoords " +Ð

```
"gl_MaxVertexAttribs gl_MaxVertexUniformComponents gl_MaxVaryingFloats " +Ð
                "gl_MaxVertexTextureImageUnits gl_MaxTextureImageUnits " +Ð
                "gl_MaxFragmentUniformComponents
gl_MaxCombineTextureImageUnits " +Ð              "gl_MaxDrawBuffers"),Ð
hooks: {"#": cppHook},Ð   modeProps: {fold: ["brace", "include"]}Ð });Ð
def("text/x-nesc", {Ð   name: "clike",Ð   keywords: words(cKeywords + "as
atomic async call command component components configuration event generic " +Ð
                    "implementation includes interface module new norace
nx_struct nx_union post provides " +Ð                  "signal task uses
abstract extends"),Ð   blockKeywords: words("case do else for if switch while
struct"),Ð   atoms: words("null"),Ð   hooks: {"#": cppHook},Ð   modeProps:
{fold: ["brace", "include"]}Ð });Ð
});Ð
```

public\assets\js\plugins\codemirror\mode\cobol\cobol.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð**Ð* Author: Gautam MehtaÐ
* Branched from CodeMirror's Scheme modeÐ*/Ð(function(mod) {Ð if (typeof
exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("cobol", function () {Ð var BUILTIN = "builtin",
COMMENT = "comment", STRING = "string",Ð     ATOM = "atom", NUMBER =
"number", KEYWORD = "keyword", MODTAG = "header",Ð     COBOLLINENUM = "def",
PERIOD = "link";Ð function makeKeywords(str) {Ð   var obj = {}, words =
str.split(" ");Ð   for (var i = 0; i < words.length; ++i) obj[words[i]] =
true;Ð   return obj;Ð }Ð var atoms = makeKeywords("TRUE FALSE ZEROES ZEROS
ZERO SPACES SPACE LOW-VALUE LOW-VALUES ");Ð var keywords = makeKeywords(Ð
"ACCEPT ACCESS ACQUIRE ADD ADDRESS " +Ð     "ADVANCING AFTER ALIAS ALL
ALPHABET " +Ð     "ALPHABETIC ALPHABETIC-LOWER ALPHABETIC-UPPER ALPHANUMERIC
ALPHANUMERIC-EDITED " +Ð     "ALSO ALTER ALTERNATE AND ANY " +Ð     "ARE AREA
AREAS ARITHMETIC ASCENDING " +Ð     "ASSIGN AT ATTRIBUTE AUTHOR AUTO " +Ð
"AUTO-SKIP AUTOMATIC B-AND B-EXOR B-LESS " +Ð     "B-NOT B-OR BACKGROUND-
COLOR BACKGROUND-COLOUR BEEP " +Ð     "BEFORE BELL BINARY BIT BITS " +Ð
"BLANK BLINK BLOCK BOOLEAN BOTTOM " +Ð     "BY CALL CANCEL CD CF " +Ð     "CH
CHARACTER CHARACTERS CLASS CLOCK-UNITS " +Ð     "CLOSE COBOL CODE CODE-SET
COL " +Ð     "COLLATING COLUMN COMMA COMMIT COMMITMENT " +Ð     "COMMON
COMMUNICATION COMP COMP-0 COMP-1 " +Ð     "COMP-2 COMP-3 COMP-4 COMP-5 COMP-6
" +Ð     "COMP-7 COMP-8 COMP-9 COMPUTATIONAL COMPUTATIONAL-0 " +Ð
"COMPUTATIONAL-1 COMPUTATIONAL-2 COMPUTATIONAL-3 COMPUTATIONAL-4
COMPUTATIONAL-5 " +Ð     "COMPUTATIONAL-6 COMPUTATIONAL-7 COMPUTATIONAL-8
COMPUTATIONAL-9 COMPUTE " +Ð     "CONFIGURATION CONNECT CONSOLE CONTAINED
CONTAINS " +Ð     "CONTENT CONTINUE CONTROL CONTROL-AREA CONTROLS " +Ð
"CONVERTING COPY CORR CORRESPONDING COUNT " +Ð     "CRT CRT-UNDER CURRENCY
CURRENT CURSOR " +Ð     "DATA DATE DATE-COMPILED DATE-WRITTEN DAY " +Ð
"DAY-OF-WEEK DB DB-ACCESS-CONTROL-KEY DB-DATA-NAME DB-EXCEPTION " +Ð     "DB-
FORMAT-NAME DB-RECORD-NAME DB-SET-NAME DB-STATUS DBCS " +Ð     "DBCS-EDITED
DE DEBUG-CONTENTS DEBUG-ITEM DEBUG-LINE " +Ð     "DEBUG-NAME DEBUG-SUB-1
DEBUG-SUB-2 DEBUG-SUB-3 DEBUGGING " +Ð     "DECIMAL-POINT DECLARATIVES
DEFAULT DELETE DELIMITED " +Ð     "DELIMITER DEPENDING DESCENDING DESCRIBED
DESTINATION " +Ð     "DETAIL DISABLE DISCONNECT DISPLAY DISPLAY-1 " +Ð
"DISPLAY-2 DISPLAY-3 DISPLAY-4 DISPLAY-5 DISPLAY-6 " +Ð     "DISPLAY-7
DISPLAY-8 DISPLAY-9 DIVIDE DIVISION " +Ð     "DOWN DROP DUPLICATE DUPLICATES
DYNAMIC " +Ð     "EBCDIC EGI EJECT ELSE EMI " +Ð     "EMPTY EMPTY-CHECK
ENABLE END END. END-ACCEPT END-ACCEPT. " +Ð     "END-ADD END-CALL END-COMPUTE
END-DELETE END-DISPLAY " +Ð     "END-DIVIDE END-EVALUATE END-IF END-INVOKE
END-MULTIPLY " +Ð     "END-OF-PAGE END-PERFORM END-READ END-RECEIVE END-
RETURN " +Ð     "END-REWRITE END-SEARCH END-START END-STRING END-SUBTRACT " +Ð
      "END-UNSTRING END-WRITE END-XML ENTER ENTRY " +Ð     "ENVIRONMENT EOP
EQUAL EQUALS ERASE " +Ð     "ERROR ESI EVALUATE EVERY EXCEEDS " +Ð
"EXCEPTION EXCLUSIVE EXIT EXTEND EXTERNAL " +Ð     "EXTERNALLY-DESCRIBED-KEY
FD FETCH FILE FILE-CONTROL " +Ð     "FILE-STREAM FILES FILLER FINAL FIND " +Ð
      "FINISH FIRST FOOTING FOR FOREGROUND-COLOR " +Ð     "FOREGROUND-COLOUR
FORMAT FREE FROM FULL " +Ð     "FUNCTION GENERATE GET GIVING GLOBAL " +Ð
"GO GOBACK GREATER GROUP HEADING " +Ð     "HIGH-VALUE HIGH-VALUES HIGHLIGHT I-
O I-O-CONTROL " +Ð     "ID IDENTIFICATION IF IN INDEX " +Ð     "INDEX-1
INDEX-2 INDEX-3 INDEX-4 INDEX-5 " +Ð     "INDEX-6 INDEX-7 INDEX-8 INDEX-9
INDEXED " +Ð     "INDIC INDICATE INDICATOR INDICATORS INITIAL " +Ð
"INITIALIZE INITIATE INPUT INPUT-OUTPUT INSPECT " +Ð     "INSTALLATION INTO
INVALID INVOKE IS " +Ð     "JUST JUSTIFIED KANJI KEEP KEY " +Ð     "LABEL
LAST LD LEADING LEFT " +Ð     "LEFT-JUSTIFY LENGTH LENGTH-CHECK LESS LIBRARY
" +Ð     "LIKE LIMIT LIMITS LINAGE LINAGE-COUNTER " +Ð     "LINE LINE-COUNTER
LINES LINKAGE LOCAL-STORAGE " +Ð
```

```
                                        "LOCALE LOCALLY LOCK " +Ð     "MEMBER
MEMORY MERGE MESSAGE METACLASS " +Ð     "MODE MODIFIED MODIFY MODULES MOVE " +Ð
      "MULTIPLE MULTIPLY NATIONAL NATIVE NEGATIVE " +Ð     "NEXT NO NO-ECHO
NONE NOT " +Ð     "NULL NULL-KEY-MAP NULL-MAP NULLS NUMBER " +Ð     "NUMERIC
NUMERIC-EDITED OBJECT OBJECT-COMPUTER OCCURS " +Ð     "OF OFF OMITTED ON ONLY
" +Ð     "OPEN OPTIONAL OR ORDER ORGANIZATION " +Ð     "OTHER OUTPUT OVERFLOW
OWNER PACKED-DECIMAL " +Ð     "PADDING PAGE PAGE-COUNTER PARSE PERFORM " +Ð
      "PF PH PIC PICTURE PLUS " +Ð     "POINTER POSITION POSITIVE PREFIX
PRESENT " +Ð     "PRINTING PRIOR PROCEDURE PROCEDURE-POINTER PROCEDURES " +Ð
      "PROCEED PROCESS PROCESSING PROGRAM PROGRAM-ID " +Ð     "PROMPT
PROTECTED PURGE QUEUE QUOTE " +Ð     "QUOTES RANDOM RD READ READY " +Ð
"REALM RECEIVE RECONNECT RECORD RECORD-NAME " +Ð     "RECORDS RECURSIVE
REDEFINES REEL REFERENCE " +Ð     "REFERENCE-MONITOR REFERENCES RELATION
RELATIVE RELEASE " +Ð     "REMAINDER REMOVAL RENAMES REPEATED REPLACE " +Ð
      "REPLACING REPORT REPORTING REPORTS REPOSITORY " +Ð     "REQUIRED RERUN
RESERVE RESET RETAINING " +Ð     "RETRIEVAL RETURN RETURN-CODE RETURNING
REVERSE-VIDEO " +Ð     "REVERSED REWIND REWRITE RF RH " +Ð     "RIGHT RIGHT-
JUSTIFY ROLLBACK ROLLING ROUNDED " +Ð     "RUN SAME SCREEN SD SEARCH " +Ð
"SECTION SECURE SECURITY SEGMENT SEGMENT-LIMIT " +Ð     "SELECT SEND SENTENCE
SEPARATE SEQUENCE " +Ð     "SEQUENTIAL SET SHARED SIGN SIZE " +Ð     "SKIP1
SKIP2 SKIP3 SORT SORT-MERGE " +Ð     "SORT-RETURN SOURCE SOURCE-COMPUTER
SPACE-FILL " +Ð     "SPECIAL-NAMES STANDARD STANDARD-1 STANDARD-2 " +Ð
"START STARTING STATUS STOP STORE " +Ð     "STRING SUB-QUEUE-1 SUB-QUEUE-2
SUB-QUEUE-3 SUB-SCHEMA " +Ð     "SUBFILE SUBSTITUTE SUBTRACT SUM SUPPRESS " +Ð
      "SYMBOLIC SYNC SYNCHRONIZED SYSIN SYSOUT " +Ð     "TABLE TALLYING TAPE
TENANT TERMINAL " +Ð     "TERMINATE TEST TEXT THAN THEN " +Ð     "THROUGH
THRU TIME TIMES TITLE " +Ð     "TO TOP TRAILING TRAILING-SIGN TRANSACTION " +Ð
      "TYPE TYPEDEF UNDERLINE UNEQUAL UNIT " +Ð     "UNSTRING UNTIL UP UPDATE
UPON " +Ð     "USAGE USAGE-MODE USE USING VALID " +Ð     "VALIDATE VALUE
VALUES VARYING VLR " +Ð     "WAIT WHEN WHEN-COMPILED WITH WITHIN " +Ð
"WORDS WORKING-STORAGE WRITE XML XML-CODE " +Ð     "XML-EVENT XML-NTEXT XML-
TEXT ZERO ZERO-FILL " );Ð var builtins = makeKeywords("- * ** / + < <= = > >=
");Ð var tests = {Ð   digit: /\d/,Ð   digit_or_colon: /[\d:]/,Ð   hex: /[0-9a-
f]/i,Ð   sign: /[+-]/,Ð   exponent: /e/i,Ð   keyword_char: /[^\s\(\[\;\)\]]/,Ð
    symbol: /[\w*+\-]/Ð };Ð function isNumber(ch, stream){Ð   // hexÐ   if
( ch === '0' && stream.eat(/x/i) ) {Ð     stream.eatWhile(tests.hex);Ð
return true;Ð   }Ð   // leading signÐ   if ( ( ch == '+' || ch == '-' ) &&
( tests.digit.test(stream.peek()) ) ) {Ð     stream.eat(tests.sign);Ð     ch
= stream.next();Ð   }Ð   if ( tests.digit.test(ch) ) {Ð     stream.eat(ch);Ð
      stream.eatWhile(tests.digit);Ð     if ( '.' == stream.peek()) {Ð
stream.eat('.');Ð       stream.eatWhile(tests.digit);Ð     }Ð     if
( stream.eat(tests.exponent) ) {Ð       stream.eat(tests.sign);Ð
stream.eatWhile(tests.digit);Ð     }Ð     return true;Ð   }Ð   return false;Ð
  }Ð return {Ð   startState: function () {Ð     return {Ð       indentStack:
null,Ð       indentation: 0,Ð       mode: falseÐ     };Ð   },Ð   token:
function (stream, state) {Ð     if (state.indentStack == null &&
stream.sol()) {Ð       // update indentation, but only if indentStack is emptyÐ
        state.indentation = 6 ; //stream.indentation();Ð     }Ð     // skip
spacesÐ     if (stream.eatSpace()) {Ð       return null;Ð     }Ð     var
returnType = null;Ð     switch(state.mode){Ð     case "string": // multi-line
string parsing modeÐ       var next = false;Ð       while ((next =
stream.next()) != null) {Ð         if (next == "\"" || next == "\'") {Ð
            state.mode = false;Ð           break;Ð         }Ð       }Ð
returnType = STRING; // continue on in string modeÐ       break;Ð
default: // default parsing modeÐ       var ch = stream.next();Ð       var
col = stream.column();Ð       if (col >= 0 && col <= 5) {Ð         returnType
= COBOLLINENUM;Ð       } else if (col >= 72 && col <= 79) {Ð
stream.skipToEnd();Ð         returnType = MODTAG;Ð       } else if (ch == "*"
&& col == 6) { // commentÐ         stream.skipToEnd(); // rest of the line is
a commentÐ
```

```
                    returnType = COMMENT;Ð       } else if (ch == "\"" || ch
== "\'") {Ð         state.mode = "string";Ð         returnType = STRING;Ð
        } else if (ch == "'" && !
( tests.digit_or_colon.test(stream.peek()) )) {Ð         returnType = ATOM;Ð
        } else if (ch == ".") {Ð         returnType = PERIOD;Ð       } else
if (isNumber(ch,stream)){Ð         returnType = NUMBER;Ð       } else {Ð
          if (stream.current().match(tests.symbol)) {Ð           while (col <
71) {Ð             if (stream.eat(tests.symbol) === undefined) {Ð
                break;Ð             } else {Ð               col++;Ð
              }Ð           }Ð         }Ð         if (keywords &&
keywords.propertyIsEnumerable(stream.current().toUpperCase())) {Ð
returnType = KEYWORD;Ð         } else if (builtins &&
builtins.propertyIsEnumerable(stream.current().toUpperCase())) {Ð
returnType = BUILTIN;Ð         } else if (atoms &&
atoms.propertyIsEnumerable(stream.current().toUpperCase())) {Ð
returnType = ATOM;Ð         } else returnType = null;Ð       }Ð     }Ð
return returnType;Ð   },Ð   indent: function (state) {Ð     if
(state.indentStack == null) return state.indentation;Ð     return
state.indentStack.indent;Ð   }Ð };Ð});ÐCodeMirror.defineMIME("text/x-cobol",
"cobol");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\coffeescript\coffeescript.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð**Ð* Link to the
project's GitHub page:Ð* https://github.com/pickhardt/coffeescript-codemirror-
modeÐ*/Ð function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð })
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("coffeescript",
function(conf) {Ð var ERRORCLASS = "error";Ð function wordRegexp(words) {Ð
return new RegExp("^((" + words.join(")|(") + "))\\b");Ð }Ð var operators = /
^(?:->|=>|\+[+=]?|-[\-=]?|\*[\*=]?|\/[\/=]?|[=!]=|<[><]?=?|>>?=?|%=?|&=?|\|=?|
\^=?|\~|!|\?|(or|and|\|\||&&|\?)=)/;Ð var delimiters = /^(?:[()\[\]{},:`=;]|\.
\.?\.?)/;Ð var identifiers = /^[_A-Za-z$][_A-Za-z$0-9]*/;Ð var properties = /
^(@|this\.)[_A-Za-z$][_A-Za-z$0-9]*/;Ð var wordOperators = wordRegexp(["and",
"or", "not",Ð                                    "is", "isnt", "in",Ð
                                  "instanceof", "typeof"]);Ð var
indentKeywords = ["for", "while", "loop", "if", "unless", "else",Ð
                          "switch", "try", "catch", "finally", "class"];Ð var
commonKeywords = ["break", "by", "continue", "debugger", "delete",Ð
                          "do", "in", "of", "new", "return", "then",Ð
                          "this", "@", "throw", "when", "until", "extends"];Ð
var keywords = wordRegexp(indentKeywords.concat(commonKeywords));Ð
indentKeywords = wordRegexp(indentKeywords);Ð var stringPrefixes = /^('{3}|
\"{3}|['\"])/;Ð var regexPrefixes = /^(\/{3}|\/)/;Ð var commonConstants =
["Infinity", "NaN", "undefined", "null", "true", "false", "on", "off", "yes",
"no"];Ð var constants = wordRegexp(commonConstants);Ð // TokenizersÐ function
tokenBase(stream, state) {Ð   // Handle scope changesÐ   if (stream.sol()) {Ð
      if (state.scope.align === null) state.scope.align = false;Ð     var
scopeOffset = state.scope.offset;Ð     if (stream.eatSpace()) {Ð       var
lineOffset = stream.indentation();Ð       if (lineOffset > scopeOffset &&
state.scope.type == "coffee") {Ð         return "indent";Ð       } else if
(lineOffset < scopeOffset) {Ð         return "dedent";Ð       }Ð       return
null;Ð     } else {Ð       if (scopeOffset > 0) {Ð         dedent(stream,
state);Ð       }Ð     }Ð   }Ð   if (stream.eatSpace()) {Ð     return null;Ð
    }Ð   var ch = stream.peek();Ð   // Handle docco title comment (single
line)Ð   if (stream.match("####")) {Ð     stream.skipToEnd();Ð     return
"comment";Ð   }Ð   // Handle multi line commentsÐ   if (stream.match("###")) {Ð
      state.tokenize = longComment;Ð     return state.tokenize(stream, state);Ð
    }Ð   // Single line commentÐ   if (ch === "#") {Ð     stream.skipToEnd();Ð
      return "comment";Ð   }Ð   // Handle number literalsÐ   if
(stream.match(/^-?[0-9\.]/, false)) {Ð     var floatLiteral = false;Ð     //
FloatsÐ     if (stream.match(/^-?\d*\.\d+(e[\+\-]?\d+)?/i)) {Ð
floatLiteral = true;Ð     }Ð     if (stream.match(/^-?\d+\.\d*/)) {Ð
floatLiteral = true;Ð     }Ð     if (stream.match(/^-?\.\d+/)) {Ð
floatLiteral = true;Ð     }Ð     if (floatLiteral) {Ð       // prevent from
getting extra . on 1..Ð       if (stream.peek() == ".){Ð
stream.backUp(1);Ð       }Ð       return "number";Ð     }Ð     // IntegersÐ
      var intLiteral = false;Ð     // HexÐ     if (stream.match(/^-?0x[0-9a-
f]+/i)) {Ð       intLiteral = true;Ð     }Ð     // DecimalÐ     if
(stream.match(/^-?[1-9]\d*(e[\+\-]?\d+)?/)) {Ð       intLiteral = true;Ð     }Ð
      // Zero by itself with no other piece of number.Ð     if (stream.match(/
^-?0(?![\dx])/i)) {Ð       intLiteral = true;Ð     }Ð     if (intLiteral) {Ð
        return "number";Ð     }Ð   }Ð   // Handle stringsÐ   if
(stream.match(stringPrefixes)) {Ð     state.tokenize =
tokenFactory(stream.current(), false, "string");Ð     return
state.tokenize(stream, state);Ð   }Ð   // Handle regex literalsÐ   if
(stream.match(regexPrefixes)) {Ð     if (stream.current() != "/" ||
stream.match(/^.*\//, false)) { // prevent highlight of divisionÐ
state.tokenize = tokenFactory(stream.current(), true, "string-2");Ð
```

return state.tokenize(stream, state);Ð } else {Ð stream.backUp(1);Ð }Ð }Ð // Handle operators and delimitersÐ if (stream.match(operators) || stream.match(wordOperators)) {Ð return "operator";Ð }Ð if (stream.match(delimiters)) {Ð return "punctuation";Ð }Ð if (stream.match(constants)) {Ð return "atom";Ð }Ð if (stream.match(keywords)) {Ð return "keyword";Ð }Ð if (stream.match(identifiers)) {Ð return "variable";Ð }Ð if (stream.match(properties)) {Ð return "property";Ð }Ð // Handle non-detected itemsÐ stream.next();Ð return ERRORCLASS;Ð }Ð function tokenFactory(delimiter, singleline, outclass) {Ð return function(stream, state) {Ð while (!stream.eol()) {Ð stream.eatWhile(/[^'"\/\\]/);Ð if (stream.eat("\\")) {Ð stream.next();Ð if (singleline && stream.eol()) {Ð return outclass;Ð }Ð } else if (stream.match(delimiter)) {Ð state.tokenize = tokenBase;Ð return outclass;Ð } else {Ð stream.eat(/['"\/]/);Ð }Ð }Ð if (singleline) {Ð if (conf.mode.singleLineStringErrors) {Ð outclass = ERRORCLASS;Ð } else {Ð state.tokenize = tokenBase;Ð }Ð }Ð return outclass;Ð };Ð }Ð function longComment(stream, state) {Ð while (!stream.eol()) {Ð stream.eatWhile(/[^#]/);Ð if (stream.match("###")) {Ð state.tokenize = tokenBase;Ð break;Ð }Ð stream.eatWhile("#");Ð }Ð return "comment";Ð }Ð function indent(stream, state, type) {Ð type = type || "coffee";Ð var offset = 0, align = false, alignOffset = null;Ð for (var scope = state.scope; scope; scope = scope.prev) {Ð if (scope.type === "coffee" || scope.type == "}") {Ð offset = scope.offset + conf.indentUnit;Ð break;Ð }Ð }Ð if (type !== "coffee") {Ð align = null;Ð alignOffset = stream.column() + stream.current().length;Ð } else if (state.scope.align) {Ð state.scope.align = false;Ð }Ð state.scope = {Ð offset: offset,Ð type: type,Ð prev: state.scope,Ð align: align,Ð alignOffset: alignOffsetÐ };Ð }Ð function dedent(stream, state) {Ð if (!state.scope.prev) return;Ð if (state.scope.type === "coffee") {Ð var _indent = stream.indentation();Ð var matched = false;Ð for (var scope = state.scope; scope; scope = scope.prev) {Ð if (_indent === scope.offset) {Ð matched = true;Ð break;Ð }Ð }Ð if (!matched) {Ð return true;Ð }Ð while (state.scope.prev && state.scope.offset !== _indent) {Ð state.scope = state.scope.prev;Ð }Ð return false;Ð } else {Ð state.scope = state.scope.prev;Ð return false;Ð }Ð }Ð function tokenLexer(stream, state) {Ð var style = state.tokenize(stream, state);Ð var current = stream.current();Ð // Handle "." connected identifiersÐ if (current === ".") {Ð style = state.tokenize(stream, state);Ð current = stream.current();Ð if (/^\.[\w$]+$/.test(current)) {Ð return "variable";Ð } else {Ð return ERRORCLASS;Ð }Ð }Ð // Handle scope changes.Ð if (current === "return") {Ð state.dedent = true;Ð }Ð if (((current === "->" || current === "=>") &&Ð !state.lambda &&Ð !stream.peek())Ð || style === "indent") {Ð indent(stream, state);Ð }Ð var delimiter_index = "[({".indexOf(current);Ð if (delimiter_index !== -1) {Ð indent(stream, state, "])}".slice(delimiter_index, delimiter_index+1));Ð }Ð if (indentKeywords.exec(current)){Ð indent(stream, state);Ð }Ð if (current == "then"){Ð dedent(stream, state);Ð }Ð if (style === "dedent") {Ð if (dedent(stream, state)) {Ð return ERRORCLASS;Ð }Ð }Ð delimiter_index = "])}".indexOf(current);Ð if (delimiter_index !== -1) {Ð while (state.scope.type == "coffee" && state.scope.prev)Ð state.scope = state.scope.prev;Ð if (state.scope.type == current)Ð state.scope = state.scope.prev;Ð }Ð if (state.dedent && stream.eol()) {Ð if (state.scope.type == "coffee" && state.scope.prev)Ð state.scope = state.scope.prev;Ð state.dedent = false;Ð }Ð return style;Ð

```
        }Ð var external = {Ð   startState: function(basecolumn) {Ð     return
{Ð       tokenize: tokenBase,Ð       scope: {offset:basecolumn || 0,
type:"coffee", prev: null, align: false},Ð       lastToken: null,Ð
lambda: false,Ð       dedent: 0Ð     };Ð   },Ð   token: function(stream,
state) {Ð     var fillAlign = state.scope.align === null && state.scope;Ð
if (fillAlign && stream.sol()) fillAlign.align = false;Ð     var style =
tokenLexer(stream, state);Ð     if (fillAlign && style && style != "comment")
fillAlign.align = true;Ð     state.lastToken = {style:style, content:
stream.current()};Ð     if (stream.eol() && stream.lambda) {Ð
state.lambda = false;Ð     }Ð     return style;Ð   },Ð   indent:
function(state, text) {Ð     if (state.tokenize != tokenBase) return 0;Ð
var scope = state.scope;Ð     var closer = text &&
"])}".indexOf(text.charAt(0)) > -1;Ð     if (closer) while (scope.type ==
"coffee" && scope.prev) scope = scope.prev;Ð     var closes = closer &&
scope.type === text.charAt(0);Ð     if (scope.align)Ð       return
scope.alignOffset - (closes ? 1 : 0);Ð     elseÐ       return (closes ?
scope.prev : scope).offset;Ð   },Ð   lineComment: "#",Ð   fold: "indent"Ð };Ð
return external;Þ);ÐodeMirror.defineMIME("text/x-coffeescript",
"coffeescript");Þ);Ð
```

public\assets\js\plugins\codemirror\mode\commonlisp\commonlisp.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("commonlisp", function (config) {Ð var assumeBody = /
^with|^def|^do|^prog|case$|^cond$|bind$|when$|unless$/;Ð var numLiteral = /
^(?:[+\-]?(?:\d+|\d*\.\d+)(?:[efd][+\-]?\d+)?|[+\-]?\d+(?:\/[+\-]?\d+)?|#b[+
\-]?[01]+|#o[+\-]?[0-7]+|#x[+\-]?[\da-f]+)/;Ð var symbol = /
[^\s'`,@()\[\]";]/;Ð var type;Ð function readSym(stream) {Ð   var ch;Ð
while (ch = stream.next()) {Ð     if (ch == "\\") stream.next();Ð     else if
(!symbol.test(ch)) { stream.backUp(1); break; }Ð   }Ð   return
stream.current();Ð }Ð function base(stream, state) {Ð   if
(stream.eatSpace()) {type = "ws"; return null;}Ð   if
(stream.match(numLiteral)) return "number";Ð   var ch = stream.next();Ð   if
(ch == "\\") ch = stream.next();Ð   if (ch == '"') return (state.tokenize =
inString)(stream, state);Ð   else if (ch == "(") { type = "open"; return
"bracket"; }Ð   else if (ch == ")" || ch == "]") { type = "close"; return
"bracket"; }Ð   else if (ch == ";") { stream.skipToEnd(); type = "ws"; return
"comment"; }Ð   else if (/['`,@]/.test(ch)) return null;Ð   else if (ch ==
"|") {Ð     if (stream.skipTo("|")) { stream.next(); return "symbol"; }Ð
else { stream.skipToEnd(); return "error"; }Ð   } else if (ch == "#") {Ð
var ch = stream.next();Ð     if (ch == "[") { type = "open"; return
"bracket"; }Ð     else if (/[+\-=\.']/.test(ch)) return null;Ð     else if (/
\d/.test(ch) && stream.match(/^\d*#/)) return null;Ð     else if (ch == "|")
return (state.tokenize = inComment)(stream, state);Ð     else if (ch == ":")
{ readSym(stream); return "meta"; }Ð     else return "error";Ð   } else {Ð
      var name = readSym(stream);Ð     if (name == ".") return null;Ð
type = "symbol";Ð     if (name == "nil" || name == "t") return "atom";Ð
if (name.charAt(0) == ":") return "keyword";Ð     if (name.charAt(0) == "&")
return "variable-2";Ð     return "variable";Ð   }Ð }Ð function
inString(stream, state) {Ð   var escaped = false, next;Ð   while (next =
stream.next()) {Ð     if (next == '"' && !escaped) { state.tokenize = base;
break; }Ð     escaped = !escaped && next == "\\";Ð   }Ð   return "string";Ð }Ð
  function inComment(stream, state) {Ð   var next, last;Ð   while (next =
stream.next()) {Ð     if (next == "#" && last == "|") { state.tokenize =
base; break; }Ð     last = next;Ð   }Ð   type = "ws";Ð   return "comment";Ð }Ð
  return {Ð   startState: function () {Ð     return {ctx: {prev: null, start:
0, indentTo: 0}, tokenize: base};Ð   },Ð   token: function (stream, state) {Ð
      if (stream.sol() && typeof state.ctx.indentTo != "number")Ð
state.ctx.indentTo = state.ctx.start + 1;Ð     type = null;Ð     var style =
state.tokenize(stream, state);Ð     if (type != "ws") {Ð       if
(state.ctx.indentTo == null) {Ð         if (type == "symbol" &&
assumeBody.test(stream.current()))Ð           state.ctx.indentTo =
state.ctx.start + config.indentUnit;Ð         elseÐ
state.ctx.indentTo = "next";Ð       } else if (state.ctx.indentTo == "next") {Ð
          state.ctx.indentTo = stream.column();Ð       }Ð     }Ð     if (type
== "open") state.ctx = {prev: state.ctx, start: stream.column(), indentTo:
null};Ð     else if (type == "close") state.ctx = state.ctx.prev || state.ctx;Ð
      return style;Ð   },Ð   indent: function (state, _textAfter) {Ð     var
i = state.ctx.indentTo;Ð     return typeof i == "number" ? i :
state.ctx.start + 1;Ð   },Ð   lineComment: ";;",Ð   blockCommentStart: "#|",Ð
    blockCommentEnd: "|#"Ð };Ð });ÐodeMirror.defineMIME("text/x-common-lisp",
"commonlisp");Ð });Ð
```

public\assets\js\plugins\codemirror\mode\css\css.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("css", function(config, parserConfig) {Ð if (!
parserConfig.propertyKeywords) parserConfig = CodeMirror.resolveMode("text/
css");Ð var indentUnit = config.indentUnit,Ð     tokenHooks =
parserConfig.tokenHooks,Ð     mediaTypes = parserConfig.mediaTypes || {},Ð
      mediaFeatures = parserConfig.mediaFeatures || {},Ð     propertyKeywords
= parserConfig.propertyKeywords || {},Ð     nonStandardPropertyKeywords =
parserConfig.nonStandardPropertyKeywords || {},Ð     colorKeywords =
parserConfig.colorKeywords || {},Ð     valueKeywords =
parserConfig.valueKeywords || {},Ð     fontProperties =
parserConfig.fontProperties || {},Ð     allowNested =
parserConfig.allowNested;Ð var type, override;Ð function ret(style, tp)
{ type = tp; return style; }Ð // TokenizersÐ function tokenBase(stream,
state) {Ð   var ch = stream.next();Ð   if (tokenHooks[ch]) {Ð     var result
= tokenHooks[ch](stream, state);Ð     if (result !== false) return result;Ð
    }Ð   if (ch == "@") {Ð     stream.eatWhile(/[\w\\\-]/);Ð     return
ret("def", stream.current());Ð   } else if (ch == "=" || (ch == "~" || ch ==
"|") && stream.eat("=")) {Ð     return ret(null, "compare");Ð   } else if (ch
== "\"" || ch == "'") {Ð     state.tokenize = tokenString(ch);Ð     return
state.tokenize(stream, state);Ð   } else if (ch == "#") {Ð
stream.eatWhile(/[\w\\\-]/);Ð     return ret("atom", "hash");Ð   } else if
(ch == "!") {Ð     stream.match(/^\s*\w*/);Ð     return ret("keyword",
"important");Ð   } else if (/\d/.test(ch) || ch == "." && stream.eat(/\d/)) {Ð
      stream.eatWhile(/[\w.%]/);Ð     return ret("number", "unit");Ð   } else
if (ch === "-") {Ð     if (/[\d.]/.test(stream.peek())) {Ð
stream.eatWhile(/[\w.%]/);Ð       return ret("number", "unit");Ð     } else
if (stream.match(/^\w+-/)) {Ð       return ret("meta", "meta");Ð     }Ð   }
else if (/[,+>*\/]/.test(ch)) {Ð     return ret(null, "select-op");Ð   } else
if (ch == "." && stream.match(/^-?[_a-z][_a-z0-9-]*/i)) {Ð     return
ret("qualifier", "qualifier");Ð   } else if (/[:;{}\[\]\(\)]/.test(ch)) {Ð
      return ret(null, ch);Ð   } else if (ch == "u" && stream.match("rl(")) {Ð
      stream.backUp(1);Ð     state.tokenize = tokenParenthesized;Ð     return
ret("property", "word");Ð   } else if (/[\w\\\-]/.test(ch)) {Ð
stream.eatWhile(/[\w\\\-]/);Ð     return ret("property", "word");Ð   } else {Ð
      return ret(null, null);Ð   }Ð }Ð function tokenString(quote) {Ð
return function(stream, state) {Ð     var escaped = false, ch;Ð     while
((ch = stream.next()) != null) {Ð       if (ch == quote && !escaped) {Ð
          if (quote == ")") stream.backUp(1);Ð         break;Ð       }Ð
escaped = !escaped && ch == "\\";Ð     }Ð     if (ch == quote || !escaped &&
quote != ")") state.tokenize = null;Ð     return ret("string", "string");Ð
    };Ð }Ð function tokenParenthesized(stream, state) {Ð   stream.next(); //
Must be '('Ð   if (!stream.match(/\s*[\"\')]/, false))Ð     state.tokenize =
tokenString(")");Ð   elseÐ     state.tokenize = null;Ð   return ret(null,
"(");Ð }Ð // Context managementÐ function Context(type, indent, prev) {Ð
this.type = type;Ð   this.indent = indent;Ð   this.prev = prev;Ð }Ð function
pushContext(state, stream, type) {Ð   state.context = new Context(type,
stream.indentation() + indentUnit, state.context);Ð   return type;Ð }Ð
function popContext(state) {Ð   state.context = state.context.prev;Ð   return
state.context.type;Ð }Ð function pass(type, stream, state) {Ð   return
states[state.context.type](type, stream, state);Ð }Ð function
popAndPass(type, stream, state, n) {Ð   for (var i = n || 1; i > 0; i--)Ð
state.context = state.context.prev;Ð   return pass(type, stream, state);Ð }Ð
  // ParserÐ function wordAsValue(stream) {Ð   var word =
stream.current().toLowerCase();Ð
```

```
                                    if (valueKeywords.hasOwnProperty(word))Ð
      override = "atom";Ð   else if (colorKeywords.hasOwnProperty(word))Ð
override = "keyword";Ð   elseÐ     override = "variable";Ð }Ð var states = {};Ð
  states.top = function(type, stream, state) {Ð   if (type == "{") {Ð
return pushContext(state, stream, "block");Ð   } else if (type == "}" &&
state.context.prev) {Ð     return popContext(state);Ð   } else if (type ==
"@media") {Ð     return pushContext(state, stream, "media");Ð   } else if
(type == "@font-face") {Ð     return "font_face_before";Ð   } else if (/^@(-
(moz|ms|o|webkit)-)?keyframes$/.test(type)) {Ð     return "keyframes";Ð   }
else if (type && type.charAt(0) == "@") {Ð     return pushContext(state,
stream, "at");Ð   } else if (type == "hash") {Ð     override = "builtin";Ð
    } else if (type == "word") {Ð     override = "tag";Ð   } else if (type ==
"variable-definition") {Ð     return "maybeprop";Ð   } else if (type ==
"interpolation") {Ð     return pushContext(state, stream, "interpolation");Ð
    } else if (type == ":") {Ð     return "pseudo";Ð   } else if (allowNested
&& type == "(") {Ð     return pushContext(state, stream, "parens");Ð   }Ð
return state.context.type;Ð };Ð states.block = function(type, stream, state) {Ð
    if (type == "word") {Ð     var word = stream.current().toLowerCase();Ð
      if (propertyKeywords.hasOwnProperty(word)) {Ð       override =
"property";Ð       return "maybeprop";Ð     } else if
(nonStandardPropertyKeywords.hasOwnProperty(word)) {Ð       override =
"string-2";Ð       return "maybeprop";Ð     } else if (allowNested) {Ð
override = stream.match(/^\s*:/, false) ? "property" : "tag";Ð       return
"block";Ð     } else {Ð       override += " error";Ð       return "maybeprop";Ð
      }Ð   } else if (type == "meta") {Ð     return "block";Ð   } else if (!
allowNested && (type == "hash" || type == "qualifier")) {Ð     override =
"error";Ð     return "block";Ð   } else {Ð     return states.top(type,
stream, state);Ð   }Ð };Ð states.maybeprop = function(type, stream, state) {Ð
    if (type == ":") return pushContext(state, stream, "prop");Ð   return
pass(type, stream, state);Ð };Ð states.prop = function(type, stream, state) {Ð
    if (type == ";") return popContext(state);Ð   if (type == "{" &&
allowNested) return pushContext(state, stream, "propBlock");Ð   if (type ==
"}" || type == "{") return popAndPass(type, stream, state);Ð   if (type ==
"(") return pushContext(state, stream, "parens");Ð   if (type == "hash" && !/
^#([0-9a-fA-f]{3}|[0-9a-fA-f]{6})$/.test(stream.current())) {Ð     override
+= " error";Ð   } else if (type == "word") {Ð     wordAsValue(stream);Ð   }
else if (type == "interpolation") {Ð     return pushContext(state, stream,
"interpolation");Ð   }Ð   return "prop";Ð };Ð states.propBlock =
function(type, _stream, state) {Ð   if (type == "}") return popContext(state);Ð
    if (type == "word") { override = "property"; return "maybeprop"; }Ð
return state.context.type;Ð };Ð states.parens = function(type, stream, state)
{Ð   if (type == "{" || type == "}") return popAndPass(type, stream, state);Ð
    if (type == ")") return popContext(state);Ð   if (type == "(") return
pushContext(state, stream, "parens");Ð   if (type == "word")
wordAsValue(stream);Ð   return "parens";Ð };Ð states.pseudo = function(type,
stream, state) {Ð   if (type == "word") {Ð     override = "variable-3";Ð
return state.context.type;Ð   }Ð   return pass(type, stream, state);Ð };Ð
states.media = function(type, stream, state) {Ð   if (type == "(") return
pushContext(state, stream, "media_parens");Ð   if (type == "}") return
popAndPass(type, stream, state);Ð   if (type == "{") return popContext(state)
&& pushContext(state, stream, allowNested ? "block" : "top");Ð   if (type ==
"word") {Ð     var word = stream.current().toLowerCase();Ð     if (word ==
"only" || word == "not" || word == "and")Ð       override = "keyword";Ð
else if (mediaTypes.hasOwnProperty(word))Ð       override = "attribute";Ð
else if (mediaFeatures.hasOwnProperty(word))Ð       override = "property";Ð
      elseÐ       override = "error";Ð   }Ð   return state.context.type;Ð };Ð
states.media_parens = function(type, stream, state) {Ð   if (type == ")")
return popContext(state);Ð   if (type == "{" || type == "}") return
popAndPass(type, stream, state, 2);Ð   return states.media(type, stream,
state);Ð
```

```
         };Ð states.font_face_before = function(type, stream, state) {Ð   if
(type == "{")Ð     return pushContext(state, stream, "font_face");Ð   return
pass(type, stream, state);Ð };Ð states.font_face = function(type, stream,
state) {Ð   if (type == "}") return popContext(state);Ð   if (type == "word")
{Ð     if (!fontProperties.hasOwnProperty(stream.current().toLowerCase()))Ð
        override = "error";Ð     elseÐ       override = "property";Ð
return "maybeprop";Ð   }Ð   return "font_face";Ð };Ð states.keyframes =
function(type, stream, state) {Ð   if (type == "word") { override =
"variable"; return "keyframes"; }Ð   if (type == "{") return
pushContext(state, stream, "top");Ð   return pass(type, stream, state);Ð };Ð
states.at = function(type, stream, state) {Ð   if (type == ";") return
popContext(state);Ð   if (type == "{" || type == "}") return popAndPass(type,
stream, state);Ð   if (type == "word") override = "tag";Ð   else if (type ==
"hash") override = "builtin";Ð   return "at";Ð };Ð states.interpolation =
function(type, stream, state) {Ð   if (type == "}") return popContext(state);Ð
    if (type == "{" || type == ";") return popAndPass(type, stream, state);Ð
    if (type != "variable") override = "error";Ð   return "interpolation";Ð };Ð
  return {Ð   startState: function(base) {Ð     return {tokenize: null,Ð
              state: "top",Ð             context: new Context("top", base ||
0, null)};Ð   },Ð   token: function(stream, state) {Ð     if (!state.tokenize
&& stream.eatSpace()) return null;Ð     var style = (state.tokenize ||
tokenBase)(stream, state);Ð     if (style && typeof style == "object") {Ð
        type = style[1];Ð       style = style[0];Ð     }Ð     override =
style;Ð     state.state = states[state.state](type, stream, state);Ð
return override;Ð   },Ð   indent: function(state, textAfter) {Ð     var cx =
state.context, ch = textAfter && textAfter.charAt(0);Ð     var indent =
cx.indent;Ð     if (cx.type == "prop" && (ch == "}" || ch == ")")) cx =
cx.prev;Ð     if (cx.prev &&Ð         (ch == "}" && (cx.type == "block" ||
cx.type == "top" || cx.type == "interpolation" || cx.type == "font_face") ||Ð
           ch == ")" && (cx.type == "parens" || cx.type == "media_parens") ||Ð
           ch == "{" && (cx.type == "at" || cx.type == "media"))) {Ð
indent = cx.indent - indentUnit;Ð       cx = cx.prev;Ð     }Ð     return
indent;Ð   },Ð   electricChars: "}",Ð   blockCommentStart: "/*",Ð
blockCommentEnd: "*/",Ð   fold: "brace"Ð };Ð });Ð function keySet(array) {Ð
var keys = {};Ð   for (var i = 0; i < array.length; ++i) {Ð
keys[array[i]] = true;Ð   }Ð   return keys;Ð }Ð var mediaTypes_ = [Ð   "all",
"aural", "braille", "handheld", "print", "projection", "screen",Ð   "tty",
"tv", "embossed"Ð ], mediaTypes = keySet(mediaTypes_);Ð var mediaFeatures_ = [Ð
    "width", "min-width", "max-width", "height", "min-height", "max-height",Ð
    "device-width", "min-device-width", "max-device-width", "device-height",Ð
    "min-device-height", "max-device-height", "aspect-ratio",Ð   "min-aspect-
ratio", "max-aspect-ratio", "device-aspect-ratio",Ð   "min-device-aspect-
ratio", "max-device-aspect-ratio", "color", "min-color",Ð   "max-color",
"color-index", "min-color-index", "max-color-index",Ð   "monochrome", "min-
monochrome", "max-monochrome", "resolution",Ð   "min-resolution", "max-
resolution", "scan", "grid"Ð ], mediaFeatures = keySet(mediaFeatures_);Ð var
propertyKeywords_ = [Ð   "align-content", "align-items", "align-self",
"alignment-adjust",Ð   "alignment-baseline", "anchor-point", "animation",
"animation-delay",Ð   "animation-direction", "animation-duration", "animation-
fill-mode",Ð   "animation-iteration-count", "animation-name", "animation-play-
state",Ð   "animation-timing-function", "appearance", "azimuth", "backface-
visibility",Ð   "background", "background-attachment", "background-clip",
"background-color",Ð   "background-image", "background-origin", "background-
position",Ð   "background-repeat", "background-size", "baseline-shift",
"binding",Ð   "bleed", "bookmark-label", "bookmark-level", "bookmark-state",Ð
    "bookmark-target", "border", "border-bottom", "border-bottom-color",Ð
"border-bottom-left-radius", "border-bottom-right-radius",Ð   "border-bottom-
style", "border-bottom-width", "border-collapse",Ð   "border-color", "border-
image", "border-image-outset",Ð   "border-image-repeat", "border-image-
slice", "border-image-source",Ð
```

"border-image-width", "border-left",
"border-left-color",Ð "border-left-style", "border-left-width", "border-radius", "border-right",Ð "border-right-color", "border-right-style", "border-right-width",Ð "border-spacing", "border-style", "border-top", "border-top-color",Ð "border-top-left-radius", "border-top-right-radius", "border-top-style",Ð "border-top-width", "border-width", "bottom", "box-decoration-break",Ð "box-shadow", "box-sizing", "break-after", "break-before", "break-inside",Ð "caption-side", "clear", "clip", "color", "color-profile", "column-count",Ð "column-fill", "column-gap", "column-rule", "column-rule-color",Ð "column-rule-style", "column-rule-width", "column-span", "column-width",Ð "columns", "content", "counter-increment", "counter-reset", "crop", "cue",Ð "cue-after", "cue-before", "cursor", "direction", "display",Ð "dominant-baseline", "drop-initial-after-adjust",Ð "drop-initial-after-align", "drop-initial-before-adjust",Ð "drop-initial-before-align", "drop-initial-size", "drop-initial-value",Ð "elevation", "empty-cells", "fit", "fit-position", "flex", "flex-basis",Ð "flex-direction", "flex-flow", "flex-grow", "flex-shrink", "flex-wrap",Ð "float", "float-offset", "flow-from", "flow-into", "font", "font-feature-settings",Ð "font-family", "font-kerning", "font-language-override", "font-size", "font-size-adjust",Ð "font-stretch", "font-style", "font-synthesis", "font-variant",Ð
"font-variant-alternates", "font-variant-caps", "font-variant-east-asian",Ð
"font-variant-ligatures", "font-variant-numeric", "font-variant-position",Ð
"font-weight", "grid", "grid-area", "grid-auto-columns", "grid-auto-flow",Ð
"grid-auto-position", "grid-auto-rows", "grid-column", "grid-column-end",Ð
"grid-column-start", "grid-row", "grid-row-end", "grid-row-start",Ð
"grid-template", "grid-template-areas", "grid-template-columns",Ð "grid-template-rows", "hanging-punctuation", "height", "hyphens",Ð "icon", "image-orientation", "image-rendering", "image-resolution",Ð "inline-box-align", "justify-content", "left", "letter-spacing",Ð "line-break", "line-height", "line-stacking", "line-stacking-ruby",Ð "line-stacking-shift", "line-stacking-strategy", "list-style",Ð "list-style-image", "list-style-position", "list-style-type", "margin",Ð "margin-bottom", "margin-left", "margin-right", "margin-top",Ð "marker-offset", "marks", "marquee-direction", "marquee-loop",Ð "marquee-play-count", "marquee-speed", "marquee-style", "max-height",Ð "max-width", "min-height", "min-width", "move-to", "nav-down", "nav-index",Ð "nav-left", "nav-right", "nav-up", "object-fit", "object-position",Ð "opacity", "order", "orphans", "outline",Ð
"outline-color", "outline-offset", "outline-style", "outline-width",Ð
"overflow", "overflow-style", "overflow-wrap", "overflow-x", "overflow-y",Ð
"padding", "padding-bottom", "padding-left", "padding-right", "padding-top",Ð
"page", "page-break-after", "page-break-before", "page-break-inside",Ð
"page-policy", "pause", "pause-after", "pause-before", "perspective",Ð
"perspective-origin", "pitch", "pitch-range", "play-during", "position",Ð
"presentation-level", "punctuation-trim", "quotes", "region-break-after",Ð
"region-break-before", "region-break-inside", "region-fragment",Ð
"rendering-intent", "resize", "rest", "rest-after", "rest-before", "richness",Ð
"right", "rotation", "rotation-point", "ruby-align", "ruby-overhang",Ð
"ruby-position", "ruby-span", "shape-image-threshold", "shape-inside", "shape-margin",Ð "shape-outside", "size", "speak", "speak-as", "speak-header",Ð
"speak-numeral", "speak-punctuation", "speech-rate", "stress", "string-set",Ð
"tab-size", "table-layout", "target", "target-name", "target-new",Ð
"target-position", "text-align", "text-align-last", "text-decoration",Ð
"text-decoration-color", "text-decoration-line", "text-decoration-skip",Ð
"text-decoration-style", "text-emphasis", "text-emphasis-color",Ð "text-emphasis-position", "text-emphasis-style", "text-height",Ð "text-indent", "text-justify", "text-outline", "text-overflow", "text-shadow",Ð "text-size-adjust", "text-space-collapse", "text-transform", "text-underline-position",Ð
"text-wrap", "top", "transform", "transform-origin", "transform-style",Ð
"transition", "transition-delay", "transition-duration",Ð "transition-property", "transition-timing-function", "unicode-bidi",Ð

"vertical-align",
"visibility", "voice-balance", "voice-duration",Ð "voice-family", "voice-
pitch", "voice-range", "voice-rate", "voice-stress",Ð "voice-volume",
"volume", "white-space", "widows", "width", "word-break",Ð "word-spacing",
"word-wrap", "z-index",Ð // SVG-specificÐ "clip-path", "clip-rule",
"mask", "enable-background", "filter", "flood-color",Ð "flood-opacity",
"lighting-color", "stop-color", "stop-opacity", "pointer-events",Ð "color-
interpolation", "color-interpolation-filters",Ð "color-rendering", "fill",
"fill-opacity", "fill-rule", "image-rendering",Ð "marker", "marker-end",
"marker-mid", "marker-start", "shape-rendering", "stroke",Ð "stroke-
dasharray", "stroke-dashoffset", "stroke-linecap", "stroke-linejoin",Ð
"stroke-miterlimit", "stroke-opacity", "stroke-width", "text-rendering",Ð
"baseline-shift", "dominant-baseline", "glyph-orientation-horizontal",Ð
"glyph-orientation-vertical", "text-anchor", "writing-mode"Ð],
propertyKeywords = keySet(propertyKeywords_);Ð var
nonStandardPropertyKeywords_ = [Ð "scrollbar-arrow-color", "scrollbar-base-
color", "scrollbar-dark-shadow-color",Ð "scrollbar-face-color", "scrollbar-
highlight-color", "scrollbar-shadow-color",Ð "scrollbar-3d-light-color",
"scrollbar-track-color", "shape-inside",Ð "searchfield-cancel-button",
"searchfield-decoration", "searchfield-results-button",Ð "searchfield-
results-decoration", "zoom"Ð], nonStandardPropertyKeywords =
keySet(nonStandardPropertyKeywords_);Ð var colorKeywords_ = [Ð "aliceblue",
"antiquewhite", "aqua", "aquamarine", "azure", "beige",Ð "bisque", "black",
"blanchedalmond", "blue", "blueviolet", "brown",Ð "burlywood", "cadetblue",
"chartreuse", "chocolate", "coral", "cornflowerblue",Ð "cornsilk",
"crimson", "cyan", "darkblue", "darkcyan", "darkgoldenrod",Ð "darkgray",
"darkgreen", "darkkhaki", "darkmagenta", "darkolivegreen",Ð "darkorange",
"darkorchid", "darkred", "darksalmon", "darkseagreen",Ð "darkslateblue",
"darkslategray", "darkturquoise", "darkviolet",Ð "deeppink", "deepskyblue",
"dimgray", "dodgerblue", "firebrick",Ð "floralwhite", "forestgreen",
"fuchsia", "gainsboro", "ghostwhite",Ð "gold", "goldenrod", "gray", "grey",
"green", "greenyellow", "honeydew",Ð "hotpink", "indianred", "indigo",
"ivory", "khaki", "lavender",Ð "lavenderblush", "lawngreen",
"lemonchiffon", "lightblue", "lightcoral",Ð "lightcyan",
"lightgoldenrodyellow", "lightgray", "lightgreen", "lightpink",Ð
"lightsalmon", "lightseagreen", "lightskyblue", "lightslategray",Ð
"lightsteelblue", "lightyellow", "lime", "limegreen", "linen", "magenta",Ð
"maroon", "mediumaquamarine", "mediumblue", "mediumorchid", "mediumpurple",Ð
"mediumseagreen", "mediumslateblue", "mediumspringgreen",
"mediumturquoise",Ð "mediumvioletred", "midnightblue", "mintcream",
"mistyrose", "moccasin",Ð "navajowhite", "navy", "oldlace", "olive",
"olivedrab", "orange", "orangered",Ð "orchid", "palegoldenrod",
"palegreen", "paleturquoise", "palevioletred",Ð "papayawhip", "peachpuff",
"peru", "pink", "plum", "powderblue",Ð "purple", "rebeccapurple", "red",
"rosybrown", "royalblue", "saddlebrown",Ð "salmon", "sandybrown",
"seagreen", "seashell", "sienna", "silver", "skyblue",Ð "slateblue",
"slategray", "snow", "springgreen", "steelblue", "tan",Ð "teal", "thistle",
"tomato", "turquoise", "violet", "wheat", "white",Ð "whitesmoke", "yellow",
"yellowgreen"Ð], colorKeywords = keySet(colorKeywords_);Ð var valueKeywords_
= [Ð "above", "absolute", "activeborder", "activecaption", "afar",Ð
"after-white-space", "ahead", "alias", "all", "all-scroll", "alternate",Ð
"always", "amharic", "amharic-abegede", "antialiased", "appworkspace",Ð
"arabic-indic", "armenian", "asterisks", "auto", "avoid", "avoid-column",
"avoid-page",Ð "avoid-region", "background", "backwards", "baseline",
"below", "bidi-override", "binary",Ð "bengali", "blink", "block", "block-
axis", "bold", "bolder", "border", "border-box",Ð "both", "bottom",
"break", "break-all", "break-word", "button", "button-bevel",Ð
"buttonface", "buttonhighlight", "buttonshadow", "buttontext", "cambodian",Ð
"capitalize", "caps-lock-indicator", "caption", "captiontext", "caret",Ð
"cell", "center", "checkbox", "circle", "cjk-earthly-branch",Ð

"cjk-heavenly-stem", "cjk-ideographic", "clear", "clip", "close-quote",Ð "col-resize", "collapse", "column", "compact", "condensed", "contain", "content",Ð "content-box", "context-menu", "continuous", "copy", "cover", "crop",Ð "cross", "crosshair", "currentcolor", "cursive", "dashed", "decimal",Ð "decimal-leading-zero", "default", "default-button", "destination-atop",Ð "destination-in", "destination-out", "destination-over", "devanagari",Ð "disc", "discard", "document", "dot-dash", "dot-dot-dash", "dotted",Ð "double", "down", "e-resize", "ease", "ease-in", "ease-in-out", "ease-out",Ð "element", "ellipse", "ellipsis", "embed", "end", "ethiopic", "ethiopic-abegede",Ð "ethiopic-abegede-am-et", "ethiopic-abegede-gez", "ethiopic-abegede-ti-er",Ð "ethiopic-abegede-ti-et", "ethiopic-halehame-aa-er",Ð "ethiopic-halehame-aa-et", "ethiopic-halehame-am-et",Ð "ethiopic-halehame-gez", "ethiopic-halehame-om-et",Ð "ethiopic-halehame-sid-et", "ethiopic-halehame-so-et",Ð "ethiopic-halehame-ti-er", "ethiopic-halehame-ti-et",Ð "ethiopic-halehame-tig", "ew-resize", "expanded", "extra-condensed",Ð "extra-expanded", "fantasy", "fast", "fill", "fixed", "flat", "footnotes",Ð "forwards", "from", "geometricPrecision", "georgian", "graytext", "groove",Ð "gujarati", "gurmukhi", "hand", "hangul", "hangul-consonant", "hebrew",Ð "help", "hidden", "hide", "higher", "highlight", "highlighttext",Ð "hiragana", "hiragana-iroha", "horizontal", "hsl", "hsla", "icon", "ignore",Ð "inactiveborder", "inactivecaption", "inactivecaptiontext", "infinite",Ð "infobackground", "infotext", "inherit", "initial", "inline", "inline-axis",Ð "inline-block", "inline-table", "inset", "inside", "intrinsic", "invert",Ð "italic", "justify", "kannada", "katakana", "katakana-iroha", "keep-all", "khmer",Ð "landscape", "lao", "large", "larger", "left", "level", "lighter",Ð "line-through", "linear", "lines", "list-item", "listbox", "listitem",Ð "local", "logical", "loud", "lower", "lower-alpha", "lower-armenian",Ð "lower-greek", "lower-hexadecimal", "lower-latin", "lower-norwegian",Ð "lower-roman", "lowercase", "ltr", "malayalam", "match",Ð "media-controls-background", "media-current-time-display",Ð "media-fullscreen-button", "media-mute-button", "media-play-button",Ð "media-return-to-realtime-button", "media-rewind-button",Ð "media-seek-back-button", "media-seek-forward-button", "media-slider",Ð "media-sliderthumb", "media-time-remaining-display", "media-volume-slider",Ð "media-volume-slider-container", "media-volume-sliderthumb", "medium",Ð "menu", "menulist", "menulist-button", "menulist-text",Ð "menulist-textfield", "menutext", "message-box", "middle", "min-intrinsic",Ð "mix", "mongolian", "monospace", "move", "multiple", "myanmar", "n-resize",Ð "narrower", "ne-resize", "nesw-resize", "no-close-quote", "no-drop",Ð "no-open-quote", "no-repeat", "none", "normal", "not-allowed", "nowrap",Ð "ns-resize", "nw-resize", "nwse-resize", "oblique", "octal", "open-quote",Ð "optimizeLegibility", "optimizeSpeed", "oriya", "oromo", "outset",Ð "outside", "outside-shape", "overlay", "overline", "padding", "padding-box",Ð "painted", "page", "paused", "persian", "plus-darker", "plus-lighter", "pointer",Ð "polygon", "portrait", "pre", "pre-line", "pre-wrap", "preserve-3d", "progress", "push-button",Ð "radio", "read-only", "read-write", "read-write-plaintext-only", "rectangle", "region",Ð "relative", "repeat", "repeat-x", "repeat-y", "reset", "reverse", "rgb", "rgba",Ð "ridge", "right", "round", "row-resize", "rtl", "run-in", "running",Ð "s-resize", "sans-serif", "scroll", "scrollbar", "se-resize", "searchfield",Ð "searchfield-cancel-button", "searchfield-decoration",Ð "searchfield-results-button", "searchfield-results-decoration",Ð "semi-condensed", "semi-expanded", "separate", "serif", "show", "sidama",Ð "single", "skip-white-space", "slide", "slider-horizontal",Ð "slider-vertical", "sliderthumb-horizontal", "sliderthumb-vertical", "slow",Ð "small", "small-caps", "small-caption", "smaller", "solid", "somali",Ð "source-atop", "source-in", "source-out", "source-over", "space", "square",Ð "square-button", "start", "static", "status-bar", "stretch", "stroke",Ð "sub", "subpixel-antialiased", "super", "sw-resize", "table",Ð

```
                                                    "table-caption", "table-
cell", "table-column", "table-column-group",Ð   "table-footer-group", "table-
header-group", "table-row", "table-row-group",Ð   "telugu", "text", "text-
bottom", "text-top", "textarea", "textfield", "thai",Ð   "thick", "thin",
"threeddarkshadow", "threedface", "threedhighlight",Ð   "threedlightshadow",
"threedshadow", "tibetan", "tigre", "tigrinya-er",Ð   "tigrinya-er-abegede",
"tigrinya-et", "tigrinya-et-abegede", "to", "top",Ð   "transparent", "ultra-
condensed", "ultra-expanded", "underline", "up",Ð   "upper-alpha", "upper-
armenian", "upper-greek", "upper-hexadecimal",Ð   "upper-latin", "upper-
norwegian", "upper-roman", "uppercase", "urdu", "url",Ð   "vertical",
"vertical-text", "visible", "visibleFill", "visiblePainted",Ð
"visibleStroke", "visual", "w-resize", "wait", "wave", "wider",Ð   "window",
"windowframe", "windowtext", "x-large", "x-small", "xor",Ð   "xx-large", "xx-
small"Ð ], valueKeywords = keySet(valueKeywords_);Ð var fontProperties_ = [Ð
    "font-family", "src", "unicode-range", "font-variant", "font-feature-
settings",Ð   "font-stretch", "font-weight", "font-style"Ð ], fontProperties
= keySet(fontProperties_);Ð var allWords =
mediaTypes_.concat(mediaFeatures_).concat(propertyKeywords_)Ð
    .concat(nonStandardPropertyKeywords_).concat(colorKeywords_).concat(valueKeywords_);Ð
  CodeMirror.registerHelper("hintWords", "css", allWords);Ð function
tokenCComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while ((ch =
stream.next()) != null) {Ð     if (maybeEnd && ch == "/") {Ð
state.tokenize = null;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð
    return ["comment", "comment"];Ð }Ð function tokenSGMLComment(stream,
state) {Ð   if (stream.skipTo("-->")) {Ð     stream.match("-->");Ð
state.tokenize = null;Ð   } else {Ð     stream.skipToEnd();Ð   }Ð   return
["comment", "comment"];Ð }Ð CodeMirror.defineMIME("text/css", {Ð
mediaTypes: mediaTypes,Ð   mediaFeatures: mediaFeatures,Ð   propertyKeywords:
propertyKeywords,Ð   nonStandardPropertyKeywords: nonStandardPropertyKeywords,Ð
    colorKeywords: colorKeywords,Ð   valueKeywords: valueKeywords,Ð
fontProperties: fontProperties,Ð   tokenHooks: {Ð     "<": function(stream,
state) {Ð       if (!stream.match("!--")) return false;Ð       state.tokenize
= tokenSGMLComment;Ð       return tokenSGMLComment(stream, state);Ð     },Ð
      "/": function(stream, state) {Ð       if (!stream.eat("*")) return
false;Ð       state.tokenize = tokenCComment;Ð       return
tokenCComment(stream, state);Ð     }Ð   },Ð   name: "css"Ð });Ð
CodeMirror.defineMIME("text/x-scss", {Ð   mediaTypes: mediaTypes,Ð
mediaFeatures: mediaFeatures,Ð   propertyKeywords: propertyKeywords,Ð
nonStandardPropertyKeywords: nonStandardPropertyKeywords,Ð   colorKeywords:
colorKeywords,Ð   valueKeywords: valueKeywords,Ð   fontProperties:
fontProperties,Ð   allowNested: true,Ð   tokenHooks: {Ð     "/":
function(stream, state) {Ð       if (stream.eat("/")) {Ð
stream.skipToEnd();Ð         return ["comment", "comment"];Ð       } else if
(stream.eat("*")) {Ð         state.tokenize = tokenCComment;Ð         return
tokenCComment(stream, state);Ð       } else {Ð         return ["operator",
"operator"];Ð       }Ð     },Ð     ":": function(stream) {Ð       if
(stream.match(/\s*\{/))Ð         return [null, "{"];Ð       return false;Ð
      },Ð     "$": function(stream) {Ð       stream.match(/^[\w-]+/);Ð
if (stream.match(/^\s*:/, false))Ð         return ["variable-2", "variable-
definition"];Ð       return ["variable-2", "variable"];Ð     },Ð     "#":
function(stream) {Ð       if (!stream.eat("{")) return false;Ð       return
[null, "interpolation"];Ð     }Ð   },Ð   name: "css",Ð   helperType: "scss"Ð
  });Ð CodeMirror.defineMIME("text/x-less", {Ð   mediaTypes: mediaTypes,Ð
mediaFeatures: mediaFeatures,Ð   propertyKeywords: propertyKeywords,Ð
nonStandardPropertyKeywords: nonStandardPropertyKeywords,Ð   colorKeywords:
colorKeywords,Ð   valueKeywords: valueKeywords,Ð   fontProperties:
fontProperties,Ð   allowNested: true,Ð   tokenHooks: {Ð     "/":
function(stream, state) {Ð       if (stream.eat("/")) {Ð
stream.skipToEnd();Ð         return ["comment", "comment"];Ð       } else if
(stream.eat("*")) {Ð
```

```
                              state.tokenize = tokenCComment;Ð         return
tokenCComment(stream, state);Ð       } else {Ð         return ["operator",
"operator"];Ð       }Ð     },Ð     "@": function(stream) {Ð       if
(stream.match(/^(charset|document|font-face|import|(-(moz|ms|o|webkit)-)?
keyframes|media|namespace|page|supports)\b/, false)) return false;Ð
stream.eatWhile(/[\w\\\-]/);Ð       if (stream.match(/^\s*:/, false))Ð
          return ["variable-2", "variable-definition"];Ð       return
["variable-2", "variable"];Ð     },Ð     "&": function() {Ð       return
["atom", "atom"];Ð     }Ð   },Ð   name: "css",Ð   helperType: "less"Ð });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\css\less_test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð "use
strict";Ð var mode = CodeMirror.getMode({indentUnit: 2}, "text/x-less");Ð
function MT(name) { test.mode(name, mode,
Array.prototype.slice.call(arguments, 1), "less"); }Ð MT("variable",Ð
"[variable-2 @base]: [atom #f04615];",Ð    "[qualifier .class] {",Ð
"  [property width]: [variable percentage]([number 0.5]); [comment // returns
`50%`]",Ð    "  [property color]: [variable saturate]([variable-2 @base],
[number 5%]);",Ð    "}");Ð MT("amp",Ð    "[qualifier .child],
[qualifier .sibling] {",Ð    "  [qualifier .parent] [atom &] {",Ð
"    [property color]: [keyword black];",Ð    "  }",Ð    "  [atom &] + [atom
&] {",Ð    "    [property color]: [keyword red];",Ð    "  }",Ð    "}");Ð
MT("mixin",Ð    "[qualifier .mixin] ([variable dark]; [variable-2 @color]) {",Ð
     "  [property color]: [variable darken]([variable-2 @color], [number
10%]);",Ð    "}",Ð    "[qualifier .mixin] ([variable light]; [variable-2
@color]) {",Ð    "  [property color]: [variable lighten]([variable-2 @color],
[number 10%]);",Ð    "}",Ð    "[qualifier .mixin] ([variable-2 @_];
[variable-2 @color]) {",Ð    "  [property display]: [atom block];",Ð    "}",Ð
     "[variable-2 @switch]: [variable light];",Ð    "[qualifier .class] {",Ð
     "  [qualifier .mixin]([variable-2 @switch]; [atom #888]);",Ð    "}");Ð
MT("nest",Ð    "[qualifier .one] {",Ð    "  [def @media] ([property width]:
[number 400px]) {",Ð    "    [property font-size]: [number 1.2em];",Ð
"    [def @media] [attribute print] [keyword and] [property color] {",Ð
"      [property color]: [keyword blue];",Ð    "    }",Ð    "  }",Ð    "}");Ð})
();Ð
```

public\assets\js\plugins\codemirror\mode\css\scss_test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ðfunction() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "text/x-scss");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1), "scss"); }Ð
MT('url_with_quotation',Ð   "[tag foo] { [property background]:[atom url]
([string test.jpg]) }");Ð MT('url_with_double_quotes',Ð   "[tag foo]
{ [property background]:[atom url]([string \"test.jpg\"]) }");Ð
MT('url_with_single_quotes',Ð   "[tag foo] { [property background]:[atom url]
([string \'test.jpg\']) }");Ð MT('string',Ð   "[def @import] [string
\"compass/css3\"]");Ð MT('important_keyword',Ð   "[tag foo] { [property
background]:[atom url]([string \'test.jpg\']) [keyword !important] }");Ð
MT('variable',Ð   "[variable-2 $blue]:[atom #333]");Ð
MT('variable_as_attribute',Ð   "[tag foo] { [property color]:[variable-2
$blue] }");Ð MT('numbers',Ð   "[tag foo] { [property padding]:[number 10px]
[number 10] [number 10em] [number 8in] }");Ð MT('number_percentage',Ð   "[tag
foo] { [property width]:[number 80%] }");Ð MT('selector',Ð   "[builtin #hello]
[qualifier .world]{}");Ð MT('singleline_comment',Ð   "[comment // this is a
comment]");Ð MT('multiline_comment',Ð   "[comment /*foobar*/]");Ð
MT('attribute_with_hyphen',Ð   "[tag foo] { [property font-size]:[number
10px] }");Ð MT('string_after_attribute',Ð   "[tag foo] { [property content]:
[string \"::\"] }");Ð MT('directives',Ð   "[def @include]
[qualifier .mixin]");Ð MT('basic_structure',Ð   "[tag p] { [property
background]:[keyword red]; }");Ð MT('nested_structure',Ð   "[tag p] { [tag a]
{ [property color]:[keyword red]; } }");Ð MT('mixin',Ð   "[def @mixin] [tag
table-base] {}");Ð MT('number_without_semicolon',Ð   "[tag p] {[property
width]:[number 12]}",Ð   "[tag a] {[property color]:[keyword red];}");Ð
MT('atom_in_nested_block',Ð   "[tag p] { [tag a] { [property color]:[atom
#000]; } }");Ð MT('interpolation_in_property',Ð   "[tag foo] { #{[variable-2
$hello]}:[number 2]; }");Ð MT('interpolation_in_selector',Ð   "[tag
foo]#{[variable-2 $hello]} { [property color]:[atom #000]; }");Ð
MT('interpolation_error',Ð   "[tag foo]#{[error foo]} { [property color]:
[atom #000]; }");Ð MT("divide_operator",Ð   "[tag foo] { [property width]:
[number 4] [operator /] [number 2] }");Ð
MT('nested_structure_with_id_selector',Ð   "[tag p] { [builtin #hello]
{ [property color]:[keyword red]; } }");Ð MT('indent_mixin',Ð    "[def
@mixin] [tag container] (",Ð    "  [variable-2 $a]: [number 10],",Ð
"  [variable-2 $b]: [number 10])",Ð    "{}");Ð MT('indent_nested',Ð    "[tag
foo] {",Ð    "  [tag bar] {",Ð    "  }",Ð    "}");Ð MT('indent_parentheses',Ð
     "[tag foo] {",Ð    "  [property color]: [variable darken]([variable-2
$blue],",Ð    "    [number 9%]);",Ð    "}");Ð MT('indent_vardef',Ð
"[variable-2 $name]:",Ð    "  [string 'val'];",Ð    "[tag tag] {",Ð
"  [tag inner] {",Ð    "    [property margin]: [number 3px];",Ð    "  }",Ð
"});Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\css\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "css");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð //
Error, because "foobarhello" is neither a known type or property, butÐ //
property was expected (after "and"), and it should be in parenthese.Ð
MT("atMediaUnknownType",Ð    "[def @media] [attribute screen] [keyword and]
[error foobarhello] { }");Ð // Soft error, because "foobarhello" is not a
known property or type.Ð MT("atMediaUnknownProperty",Ð    "[def @media]
[attribute screen] [keyword and] ([error foobarhello]) { }");Ð // Make sure
nesting works with media queriesÐ MT("atMediaMaxWidthNested",Ð    "[def
@media] [attribute screen] [keyword and] ([property max-width]: [number
25px]) { [tag foo] { } }");Ð MT("tagSelector",Ð    "[tag foo] { }");Ð
MT("classSelector",Ð    "[qualifier .foo-bar_hello] { }");Ð MT("idSelector",Ð
     "[builtin #foo] { [error #foo] }");Ð MT("tagSelectorUnclosed",Ð    "[tag
foo] { [property margin]: [number 0] } [tag bar] { }");Ð
MT("tagStringNoQuotes",Ð    "[tag foo] { [property font-family]: [variable
hello] [variable world]; }");Ð MT("tagStringDouble",Ð    "[tag foo]
{ [property font-family]: [string \"hello world\"]; }");Ð
MT("tagStringSingle",Ð    "[tag foo] { [property font-family]: [string 'hello
world']; }");Ð MT("tagColorKeyword",Ð    "[tag foo] {",Ð    "  [property
color]: [keyword black];",Ð    "  [property color]: [keyword navy];",Ð
"  [property color]: [keyword yellow];",Ð    "}");Ð MT("tagColorHex3",Ð
"[tag foo] { [property background]: [atom #fff]; }");Ð MT("tagColorHex6",Ð
"[tag foo] { [property background]: [atom #ffffff]; }");Ð MT("tagColorHex4",Ð
     "[tag foo] { [property background]: [atom&error #ffff]; }");Ð
MT("tagColorHexInvalid",Ð    "[tag foo] { [property background]: [atom&error
#ffg]; }");Ð MT("tagNegativeNumber",Ð    "[tag foo] { [property margin]:
[number -5px]; }");Ð MT("tagPositiveNumber",Ð    "[tag foo] { [property
padding]: [number 5px]; }");Ð MT("tagVendor",Ð    "[tag foo] { [meta -foo-]
[property box-sizing]: [meta -foo-][atom border-box]; }");Ð
MT("tagBogusProperty",Ð    "[tag foo] { [property&error barhelloworld]:
[number 0]; }");Ð MT("tagTwoProperties",Ð    "[tag foo] { [property margin]:
[number 0]; [property padding]: [number 0]; }");Ð MT("tagTwoPropertiesURL",Ð
     "[tag foo] { [property background]: [atom url]([string //example.com/
foo.png]); [property padding]: [number 0]; }");Ð MT("commentSGML",Ð
"[comment <!--comment-->]");Ð MT("commentSGML2",Ð    "[comment <!--comment]",Ð
     "[comment -->] [tag div] {}");Ð MT("indent_tagSelector",Ð    "[tag
strong], [tag em] {",Ð    "  [property background]: [atom rgba](",Ð
"    [number 255], [number 255], [number 0], [number .2]",Ð    "  );",Ð
"}");Ð MT("indent_atMedia",Ð    "[def @media] {",Ð    "  [tag foo] {",Ð
"    [property color]:",Ð    "      [keyword yellow];",Ð    "  }",Ð    "}");Ð
MT("indent_comma",Ð    "[tag foo] {",Ð    "  [property font-family]:
[variable verdana],",Ð    "    [atom sans-serif];",Ð    "}");Ð
MT("indent_parentheses",Ð    "[tag foo]:[variable-3 before] {",Ð
"  [property background]: [atom url](",Ð    "[string     blahblah]",Ð
"[string     etc]",Ð    "[string   ]) [keyword !important];",Ð    "}");Ð
MT("font_face",Ð    "[def @font-face] {",Ð    "  [property font-family]:
[string 'myfont'];",Ð    "  [error nonsense]: [string 'abc'];",Ð
"  [property src]: [atom url]([string http://blah]),",Ð    "    [atom url]
([string http://foo]);",Ð    "}");Ð MT("empty_url",Ð    "[def @import] [tag
url]() [tag screen];");Ð MT("parens",Ð    "[qualifier .foo] {",Ð
"  [property background-image]: [variable fade]([atom #000], [number 20%]);",Ð
     "  [property border-image]: [variable linear-gradient](",Ð    "    [atom
to] [atom bottom],",Ð    "    [variable fade]([atom #000], [number 20%])
[number 0%],",Ð    "    [variable fade]([atom #000], [number 20%]) [number
100%]",Ð    "  );",Ð    "}");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\cypher\cypher.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ By the Neo4j Team and
contributors. Ð/ https://github.com/neo4j-contrib/CodeMirror Ð(function(mod) {Ð
if (typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
  var wordRegexp = function(words) {Ð   return new RegExp("^(?:" +
words.join("|") + ")$", "i");Ð };Ð CodeMirror.defineMode("cypher",
function(config) {Ð   var tokenBase = function(stream/*, state*/) {Ð     var
ch = stream.next(), curPunc = null;Ð     if (ch === "\"" || ch === "'") {Ð
        stream.match(/.+?["']/);Ð       return "string";Ð     }Ð     if (/
[{}\(\),\.;\[\]]/.test(ch)) {Ð       curPunc = ch;Ð       return "node";Ð
      } else if (ch === "/" && stream.eat("/")) {Ð       stream.skipToEnd();Ð
        return "comment";Ð     } else if (operatorChars.test(ch)) {Ð
stream.eatWhile(operatorChars);Ð       return null;Ð     } else {Ð
stream.eatWhile(/[_\w\d]/);Ð       if (stream.eat(":")) {Ð
stream.eatWhile(/[\w\d_\-]/);Ð         return "atom";Ð       }Ð       var
word = stream.current();Ð       if (funcs.test(word)) return "builtin";Ð
        if (preds.test(word)) return "def";Ð       if (keywords.test(word))
return "keyword";Ð       return "variable";Ð     }Ð   };Ð   var pushContext =
function(state, type, col) {Ð     return state.context = {Ð       prev:
state.context,Ð       indent: state.indent,Ð       col: col,Ð       type: typeÐ
      };Ð   };Ð   var popContext = function(state) {Ð     state.indent =
state.context.indent;Ð     return state.context = state.context.prev;Ð   };Ð
    var indentUnit = config.indentUnit;Ð   var curPunc;Ð   var funcs =
wordRegexp(["abs", "acos", "allShortestPaths", "asin", "atan", "atan2",
"avg", "ceil", "coalesce", "collect", "cos", "cot", "count", "degrees", "e",
"endnode", "exp", "extract", "filter", "floor", "haversin", "head", "id",
"labels", "last", "left", "length", "log", "log10", "lower", "ltrim", "max",
"min", "node", "nodes", "percentileCont", "percentileDisc", "pi", "radians",
"rand", "range", "reduce", "rel", "relationship", "relationships", "replace",
"right", "round", "rtrim", "shortestPath", "sign", "sin", "split", "sqrt",
"startnode", "stdev", "stdevp", "str", "substring", "sum", "tail", "tan",
"timestamp", "toFloat", "toInt", "trim", "type", "upper"]);Ð   var preds =
wordRegexp(["all", "and", "any", "has", "in", "none", "not", "or", "single",
"xor"]);Ð   var keywords = wordRegexp(["as", "asc", "ascending", "assert",
"by", "case", "commit", "constraint", "create", "csv", "cypher", "delete",
"desc", "descending", "distinct", "drop", "else", "end", "false",
"fieldterminator", "foreach", "from", "headers", "in", "index", "is",
"limit", "load", "match", "merge", "null", "on", "optional", "order",
"periodic", "remove", "return", "scan", "set", "skip", "start", "then",
"true", "union", "unique", "unwind", "using", "when", "where", "with"]);Ð
var operatorChars = /[*+\-<>=&|~%^]/;Ð   return {Ð     startState: function(/
*base*/) {Ð       return {Ð         tokenize: tokenBase,Ð         context:
null,Ð         indent: 0,Ð         col: 0Ð       };Ð     },Ð     token:
function(stream, state) {Ð       if (stream.sol()) {Ð         if
(state.context && (state.context.align == null)) {Ð
state.context.align = false;Ð         }Ð         state.indent =
stream.indentation();Ð       }Ð       if (stream.eatSpace()) {Ð
return null;Ð       }Ð       var style = state.tokenize(stream, state);Ð
        if (style !== "comment" && state.context && (state.context.align ==
null) && state.context.type !== "pattern") {Ð         state.context.align =
true;Ð       }Ð       if (curPunc === "(") {Ð         pushContext(state, ")",
stream.column());Ð       } else if (curPunc === "[") {Ð
pushContext(state, "]", stream.column());Ð       } else if (curPunc === "{") {Ð
          pushContext(state, "}", stream.column());Ð       } else if (/
[\]\}\)]/.test(curPunc)) {Ð         while (state.context &&
state.context.type === "pattern") {Ð
```

```
                                                popContext(state);Ð         }Ð
          if (state.context && curPunc === state.context.type) {Ð
popContext(state);Ð         }Ð       } else if (curPunc === "." &&
state.context && state.context.type === "pattern") {Ð
popContext(state);Ð       } else if (/atom|string|variable/.test(style) &&
state.context) {Ð         if (/[\}\]]/.test(state.context.type)) {Ð
pushContext(state, "pattern", stream.column());Ð         } else if
(state.context.type === "pattern" && !state.context.align) {Ð
state.context.align = true;Ð           state.context.col = stream.column();Ð
          }Ð       }Ð       return style;Ð     },Ð     indent:
function(state, textAfter) {Ð       var firstChar = textAfter &&
textAfter.charAt(0);Ð       var context = state.context;Ð       if (/
[\]\}]/.test(firstChar)) {Ð         while (context && context.type ===
"pattern") {Ð           context = context.prev;Ð         }Ð       }Ð
var closing = context && firstChar === context.type;Ð       if (!context)
return 0;Ð       if (context.type === "keywords") return
CodeMirror.commands.newlineAndIndent;Ð       if (context.align) return
context.col + (closing ? 0 : 1);Ð       return context.indent + (closing ?
0 : indentUnit);Ð     }Ð   };Ð });Ð CodeMirror.modeExtensions["cypher"] = {Ð
    autoFormatLineBreaks: function(text) {Ð     var i, lines,
reProcessedPortion;Ð     var lines = text.split("\n");Ð     var
reProcessedPortion = /\s+\b(return|where|order by|match|with|skip|limit|
create|delete|set)\b\s/g;Ð     for (var i = 0; i < lines.length; i++)Ð
lines[i] = lines[i].replace(reProcessedPortion, " \n$1 ").trim();Ð     return
lines.join("\n");Ð   }Ð };Ð CodeMirror.defineMIME("application/x-cypher-
query", "cypher");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\d\d.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("d", function(config, parserConfig) {Ð var indentUnit =
config.indentUnit,Ð     statementIndentUnit =
parserConfig.statementIndentUnit || indentUnit,Ð     keywords =
parserConfig.keywords || {},Ð     builtin = parserConfig.builtin || {},Ð
blockKeywords = parserConfig.blockKeywords || {},Ð     atoms =
parserConfig.atoms || {},Ð     hooks = parserConfig.hooks || {},Ð
multiLineStrings = parserConfig.multiLineStrings;Ð var isOperatorChar = /[+\-
*&%=<>!?|\/]/;Ð var curPunc;Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (hooks[ch]) {Ð     var result = hooks[ch](stream, state);Ð
      if (result !== false) return result;Ð   }Ð   if (ch == '"' || ch == "'"
|| ch == "`") {Ð     state.tokenize = tokenString(ch);Ð     return
state.tokenize(stream, state);Ð   }Ð   if (/[\[\]{}\(\),;\:\.]/.test(ch)) {Ð
      curPunc = ch;Ð     return null;Ð   }Ð   if (/\d/.test(ch)) {Ð
stream.eatWhile(/[\w\.]/);Ð     return "number";Ð   }Ð   if (ch == "/") {Ð
      if (stream.eat("+")) {Ð       state.tokenize = tokenComment;Ð
return tokenNestedComment(stream, state);Ð     }Ð     if (stream.eat("*")) {Ð
        state.tokenize = tokenComment;Ð       return tokenComment(stream,
state);Ð     }Ð     if (stream.eat("/")) {Ð       stream.skipToEnd();Ð
return "comment";Ð     }Ð   }Ð   if (isOperatorChar.test(ch)) {Ð
stream.eatWhile(isOperatorChar);Ð     return "operator";Ð   }Ð
stream.eatWhile(/[\w\$_\xa1-\uffff]/);Ð   var cur = stream.current();Ð   if
(keywords.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "keyword";Ð   }Ð   if (builtin.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "builtin";Ð   }Ð   if (atoms.propertyIsEnumerable(cur)) return "atom";Ð
    return "variable";Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, next, end = false;Ð
while ((next = stream.next()) != null) {Ð       if (next == quote && !
escaped) {end = true; break;}Ð       escaped = !escaped && next == "\\";Ð
      }Ð     if (end || !(escaped || multiLineStrings))Ð       state.tokenize
= null;Ð     return "string";Ð   };Ð }Ð function tokenComment(stream, state) {Ð
    var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if (ch ==
"/" && maybeEnd) {Ð       state.tokenize = null;Ð       break;Ð     }Ð
maybeEnd = (ch == "*");Ð   }Ð   return "comment";Ð }Ð function
tokenNestedComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while (ch
= stream.next()) {Ð     if (ch == "/" && maybeEnd) {Ð       state.tokenize =
null;Ð       break;Ð     }Ð     maybeEnd = (ch == "+");Ð   }Ð   return
"comment";Ð }Ð function Context(indented, column, type, align, prev) {Ð
this.indented = indented;Ð   this.column = column;Ð   this.type = type;Ð
this.align = align;Ð   this.prev = prev;Ð }Ð function pushContext(state, col,
type) {Ð   var indent = state.indented;Ð   if (state.context &&
state.context.type == "statement")Ð     indent = state.context.indented;Ð
return state.context = new Context(indent, col, type, null, state.context);Ð }Ð
  function popContext(state) {Ð   var t = state.context.type;Ð   if (t == ")"
|| t == "]" || t == "}")Ð     state.indented = state.context.indented;Ð
return state.context = state.context.prev;Ð }Ð // Interface Ð return {Ð
startState: function(basecolumn) {Ð     return {Ð       tokenize: null,Ð
        context: new Context((basecolumn || 0) - indentUnit, 0, "top", false),Ð
        indented: 0,Ð       startOfLine: true Ð     };Ð   },Ð   token:
function(stream, state) {Ð     var ctx = state.context;Ð     if
(stream.sol()) {Ð       if (ctx.align == null) ctx.align = false;Ð
state.indented = stream.indentation();Ð
```

```
                                                    state.startOfLine = true;Ð     }Ð
      if (stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style
= (state.tokenize || tokenBase)(stream, state);Ð     if (style == "comment"
|| style == "meta") return style;Ð     if (ctx.align == null) ctx.align =
true;Ð     if ((curPunc == ";" || curPunc == ":" || curPunc == ",") &&
ctx.type == "statement") popContext(state);Ð     else if (curPunc == "{")
pushContext(state, stream.column(), "}");Ð     else if (curPunc == "[")
pushContext(state, stream.column(), "]");Ð     else if (curPunc == "(")
pushContext(state, stream.column(), ")");Ð     else if (curPunc == "}") {Ð
        while (ctx.type == "statement") ctx = popContext(state);Ð       if
(ctx.type == "}") ctx = popContext(state);Ð       while (ctx.type ==
"statement") ctx = popContext(state);Ð     }Ð     else if (curPunc ==
ctx.type) popContext(state);Ð     else if (((ctx.type == "}" || ctx.type ==
"top") && curPunc != ';') || (ctx.type == "statement" && curPunc ==
"newstatement"))Ð       pushContext(state, stream.column(), "statement");Ð
      state.startOfLine = false;Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.tokenize != tokenBase &&
state.tokenize != null) return CodeMirror.Pass;Ð     var ctx = state.context,
firstChar = textAfter && textAfter.charAt(0);Ð     if (ctx.type ==
"statement" && firstChar == "}") ctx = ctx.prev;Ð     var closing = firstChar
== ctx.type;Ð     if (ctx.type == "statement") return ctx.indented +
(firstChar == "{" ? 0 : statementIndentUnit);Ð     else if (ctx.align) return
ctx.column + (closing ? 0 : 1);Ð     else return ctx.indented + (closing ?
0 : indentUnit);Ð   },Ð   electricChars: "{}"Ð };Ð});Ð function words(str) {Ð
    var obj = {}, words = str.split(" ");Ð   for (var i = 0; i <
words.length; ++i) obj[words[i]] = true;Ð   return obj;Ð }Ð var blockKeywords
= "body catch class do else enum for foreach foreach_reverse if in interface
mixin " +Ð                     "out scope struct switch try union unittest
version while with";Ð CodeMirror.defineMIME("text/x-d", {Ð   name: "d",Ð
keywords: words("abstract alias align asm assert auto break case cast cdouble
cent cfloat const continue " +Ð                    "debug default delegate
delete deprecated export extern final finally function goto immutable " +Ð
                    "import inout invariant is lazy macro module new nothrow
override package pragma private " +Ð                   "protected public pure
ref return shared short static super synchronized template this " +Ð
                    "throw typedef typeid typeof volatile __FILE__ __LINE__
__gshared __traits __vector __parameters " +Ð
blockKeywords),Ð   blockKeywords: words(blockKeywords),Ð   builtin:
words("bool byte char creal dchar double float idouble ifloat int ireal long
real short ubyte " +Ð                  "ucent uint ulong ushort wchar wstring
void size_t sizediff_t"),Ð   atoms: words("exit failure success true false
null"),Ð   hooks: {Ð     "@": function(stream, _state) {Ð
stream.eatWhile(/[\w\$_]/);Ð       return "meta";Ð     }Ð   }Ð });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\diff\diff.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("diff", function() {Ð var TOKEN_NAMES = {Ð   '+':
'positive',Ð   '-': 'negative',Ð   '@': 'meta'Ð };Ð return {Ð   token:
function(stream) {Ð     var tw_pos = stream.string.search(/[\t ]+?$/);Ð
if (!stream.sol() || tw_pos === 0) {Ð       stream.skipToEnd();Ð       return
("error " + (Ð         TOKEN_NAMES[stream.string.charAt(0)] || '')).replace(/
$/, '');Ð     }Ð     var token_name = TOKEN_NAMES[stream.peek()] ||
stream.skipToEnd();Ð     if (tw_pos === -1) {Ð       stream.skipToEnd();Ð
      } else {Ð       stream.pos = tw_pos;Ð     }Ð     return token_name;Ð   }Ð
  };Ð});ÐodeMirror.defineMIME("text/x-diff", "diff");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\django\django.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../htmlmixed/htmlmixed"),Ð
        require("../../addon/mode/overlay"));Ð else if (typeof define ==
"function" && define.amd) // AMD Ð   define(["../../lib/codemirror", "../
htmlmixed/htmlmixed",Ð           "../../addon/mode/overlay"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
  CodeMirror.defineMode("django:inner", function() {Ð   var keywords =
["block", "endblock", "for", "endfor", "in", "true", "false",Ð
                    "loop", "none", "self", "super", "if", "endif", "as",
"not", "and",Ð                    "else", "import", "with", "endwith",
"without", "context", "ifequal", "endifequal",Ð
"ifnotequal", "endifnotequal", "extends", "include", "load", "length",
"comment",Ð                   "endcomment", "empty"];Ð   keywords = new
RegExp("^((" + keywords.join(")|(") + "))\\b");Ð   function tokenBase
(stream, state) {Ð     stream.eatWhile(/[^\{]/);Ð     var ch = stream.next();Ð
      if (ch == "{") {Ð       if (ch = stream.eat(/\{|%|#/)) {Ð
state.tokenize = inTag(ch);Ð         return "tag";Ð       }Ð     }Ð   }Ð
function inTag (close) {Ð     if (close == "{") {Ð       close = "}";Ð     }Ð
      return function (stream, state) {Ð       var ch = stream.next();Ð
if ((ch == close) && stream.eat("}")) {Ð         state.tokenize = tokenBase;Ð
          return "tag";Ð       }Ð       if (stream.match(keywords)) {Ð
          return "keyword";Ð       }Ð       return close == "#" ? "comment" :
"string";Ð     };Ð   }Ð   return {Ð     startState: function () {Ð
return {tokenize: tokenBase};Ð     },Ð     token: function (stream, state) {Ð
        return state.tokenize(stream, state);Ð     }Ð   };Ð });Ð
CodeMirror.defineMode("django", function(config) {Ð   var htmlBase =
CodeMirror.getMode(config, "text/html");Ð   var djangoInner =
CodeMirror.getMode(config, "django:inner");Ð   return
CodeMirror.overlayMode(htmlBase, djangoInner);Ð });Ð
CodeMirror.defineMIME("text/x-django", "django");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\dtd\dtd.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð*Ð DTD mode Ð Ported to
CodeMirror by Peter Kroon <plakroon@gmail.com> Ð Report bugs/issues here:
https://github.com/codemirror/CodeMirror/issues Ð GitHub: @peterkroon Ð/Ð
(function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð})
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("dtd",
function(config) {Ð var indentUnit = config.indentUnit, type;Ð function
ret(style, tp) {type = tp; return style;}Ð function tokenBase(stream, state) {Ð
    var ch = stream.next();Ð   if (ch == "<" && stream.eat("!") ) {Ð     if
(stream.eatWhile(/[\-]/)) {Ð       state.tokenize = tokenSGMLComment;Ð
return tokenSGMLComment(stream, state);Ð     } else if (stream.eatWhile(/
[\w]/)) return ret("keyword", "doindent");Ð   } else if (ch == "<" &&
stream.eat("?")) { //xml declaration Ð     state.tokenize = inBlock("meta", "?
>");Ð     return ret("meta", ch);Ð   } else if (ch == "#" && stream.eatWhile(/
[\w]/)) return ret("atom", "tag");Ð   else if (ch == "|") return
ret("keyword", "seperator");Ð   else if (ch.match(/[\(\)\[\]\-\.,\+\?>]/))
return ret(null, ch);//if(ch === ">") return ret(null, "endtag"); else Ð
else if (ch.match(/[\[\]]/)) return ret("rule", ch);Ð   else if (ch == "\""
|| ch == "'") {Ð     state.tokenize = tokenString(ch);Ð     return
state.tokenize(stream, state);Ð   } else if (stream.eatWhile(/[a-zA-Z\?\+
\d]/)) {Ð     var sc = stream.current();Ð
if( sc.substr(sc.length-1,sc.length).match(/\?|\+/) !==
null )stream.backUp(1);Ð     return ret("tag", "tag");Ð   } else if (ch ==
"%" || ch == "*" ) return ret("number", "number");Ð   else {Ð
stream.eatWhile(/[\w\\\-_%.{,]/);Ð     return ret(null, null);Ð   }Ð }Ð
function tokenSGMLComment(stream, state) {Ð   var dashes = 0, ch;Ð   while
((ch = stream.next()) != null) {Ð     if (dashes >= 2 && ch == ">") {Ð
state.tokenize = tokenBase;Ð       break;Ð     }Ð     dashes = (ch == "-") ?
dashes + 1 : 0;Ð   }Ð   return ret("comment", "comment");Ð }Ð function
tokenString(quote) {Ð   return function(stream, state) {Ð     var escaped =
false, ch;Ð     while ((ch = stream.next()) != null) {Ð       if (ch == quote
&& !escaped) {Ð         state.tokenize = tokenBase;Ð         break;Ð       }Ð
        escaped = !escaped && ch == "\\";Ð     }Ð     return ret("string",
"tag");Ð   };Ð }Ð function inBlock(style, terminator) {Ð   return
function(stream, state) {Ð     while (!stream.eol()) {Ð       if
(stream.match(terminator)) {Ð         state.tokenize = tokenBase;Ð
break;Ð       }Ð       stream.next();Ð     }Ð     return style;Ð   };Ð }Ð
return {Ð   startState: function(base) {Ð     return {tokenize: tokenBase,Ð
              baseIndent: base || 0,Ð             stack: []};Ð   },Ð   token:
function(stream, state) {Ð     if (stream.eatSpace()) return null;Ð     var
style = state.tokenize(stream, state);Ð     var context =
state.stack[state.stack.length-1];Ð     if (stream.current() == "[" || type
=== "doindent" || type == "[") state.stack.push("rule");Ð     else if (type
=== "endtag") state.stack[state.stack.length-1] = "endtag";Ð     else if
(stream.current() == "]" || type == "]" || (type == ">" && context ==
"rule")) state.stack.pop();Ð     else if (type == "[") state.stack.push("[");Ð
      return style;Ð   },Ð   indent: function(state, textAfter) {Ð     var n
= state.stack.length;Ð     if( textAfter.match(/\]\s+|\]/) )n=n-1;Ð     else
if(textAfter.substr(textAfter.length-1, textAfter.length) === ">"){Ð
if(textAfter.substr(0,1) === "<")n;Ð       else if( type == "doindent" &&
textAfter.length > 1 )n;Ð       else if( type == "doindent")n--;Ð       else
if( type == ">" && textAfter.length > 1)n;Ð       else if( type == "tag" &&
textAfter !== ">")n;Ð       else if( type == "tag" &&
state.stack[state.stack.length-1] == "rule")n--;Ð       else if( type ==
"tag")n++;Ð       else if( textAfter === ">" &&
state.stack[state.stack.length-1] == "rule" && type === ">")n--;Ð
```

```
                                                                    else
if( textAfter === ">" && state.stack[state.stack.length-1] == "rule")n;Ð
        else if( textAfter.substr(0,1) !== "<" && textAfter.substr(0,1) ===
">" )n=n-1;Ð       else if( textAfter === ">")n;Ð       else n=n-1;Ð       //
over rule them allÐ       if(type == null || type == "]")n--;Ð     }Ð
return state.baseIndent + n * indentUnit;Ð   },Ð   electricChars: "]>"Ð };Ð});Ð
CodeMirror.defineMIME("application/xml-dtd", "dtd");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\dylan\dylan.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("dylan", function(_config) {Ð // WordsÐ var words = {Ð
    // Words that introduce unnamed definitions like "define interface"Ð
unnamedDefinition: ["interface"],Ð   // Words that introduce simple named
definitions like "define library"Ð   namedDefinition: ["module", "library",
"macro",Ð                     "C-struct", "C-union",Ð                     "C-
function", "C-callable-wrapper"Ð                     ],Ð   // Words that
introduce type definitions like "define class".Ð   // These are also
parameterized like "define method" and areÐ   // appended to
otherParameterizedDefinitionWordsÐ   typeParameterizedDefinition: ["class",
"C-subtype", "C-mapped-subtype"],Ð   // Words that introduce trickier
definitions like "define method".Ð   // These require special definitions to
be added to startExpressionsÐ   otherParameterizedDefinition: ["method",
"function",Ð                                  "C-variable", "C-address"Ð
                                 ],Ð   // Words that introduce module
constant definitions.Ð   // These must also be simple definitions and areÐ
    // appended to otherSimpleDefinitionWordsÐ   constantSimpleDefinition:
["constant"],Ð   // Words that introduce module variable definitions.Ð   //
These must also be simple definitions and areÐ   // appended to
otherSimpleDefinitionWordsÐ   variableSimpleDefinition: ["variable"],Ð   //
Other words that introduce simple definitionsÐ   // (without implicit bodies).Ð
    otherSimpleDefinition: ["generic", "domain",Ð
"C-pointer-type",Ð                          "table"Ð
                         ],Ð   // Words that begin statements with implicit
bodies.Ð   statement: ["if", "block", "begin", "method", "case",Ð
                "for", "select", "when", "unless", "until",Ð
"while", "iterate", "profiling", "dynamic-bind"Ð              ],Ð   //
Patterns that act as separators in compound statements.Ð   // This may
include any general pattern that must be indentedÐ   // specially.Ð
separator: ["finally", "exception", "cleanup", "else",Ð
"elseif", "afterwards"Ð              ],Ð   // Keywords that do not require
special indentation handling,Ð   // but which should be highlightedÐ   other:
["above", "below", "by", "from", "handler", "in",Ð           "instance",
"let", "local", "otherwise", "slot",Ð           "subclass", "then", "to",
"keyed-by", "virtual"Ð          ],Ð   // Condition signaling function callsÐ
    signalingCalls: ["signal", "error", "cerror",Ð
"break", "check-type", "abort"Ð                    ]Ð };Ð
words["otherDefinition"] =Ð   words["unnamedDefinition"]Ð
    .concat(words["namedDefinition"])Ð
    .concat(words["otherParameterizedDefinition"]);Ð words["definition"] =Ð
words["typeParameterizedDefinition"]Ð   .concat(words["otherDefinition"]);Ð
words["parameterizedDefinition"] =Ð   words["typeParameterizedDefinition"]Ð
    .concat(words["otherParameterizedDefinition"]);Ð
words["simpleDefinition"] =Ð   words["constantSimpleDefinition"]Ð
    .concat(words["variableSimpleDefinition"])Ð
    .concat(words["otherSimpleDefinition"]);Ð words["keyword"] =Ð
words["statement"]Ð   .concat(words["separator"])Ð   .concat(words["other"]);Ð
  // PatternsÐ var symbolPattern = "[-_a-zA-Z?!*@<>$%]+";Ð var symbol = new
RegExp("^" + symbolPattern);Ð var patterns = {Ð   // Symbols with special
syntaxÐ   symbolKeyword: symbolPattern + ":",Ð   symbolClass: "<" +
symbolPattern + ">",Ð   symbolGlobal: "\\*" + symbolPattern + "\\*",Ð
symbolConstant: "\\$" + symbolPatternÐ };Ð var patternStyles = {Ð
symbolKeyword: "atom",Ð   symbolClass: "tag",Ð   symbolGlobal: "variable-2",Ð
    symbolConstant: "variable-3"Ð
```

```
                                    };Ð // Compile all patterns to regular
expressionsÐ for (var patternName in patterns)Ð   if
(patterns.hasOwnProperty(patternName))Ð     patterns[patternName] = new
RegExp("^" + patterns[patternName]);Ð // Names beginning "with-" and
"without-" are commonlyÐ // used as statement macroÐ patterns["keyword"] = [/
^with(?:out)?-[-_a-zA-Z?!*@<>$%]+/];Ð var styles = {};Ð styles["keyword"] =
"keyword";Ð styles["definition"] = "def";Ð styles["simpleDefinition"] = "def";Ð
  styles["signalingCalls"] = "builtin";Ð // protected words lookup tableÐ var
wordLookup = {};Ð var styleLookup = {};Ð [Ð   "keyword",Ð   "definition",Ð
"simpleDefinition",Ð   "signalingCalls"Ð ].forEach(function(type) {Ð
words[type].forEach(function(word) {Ð     wordLookup[word] = type;Ð
styleLookup[word] = styles[type];Ð   });Ð });Ð function chain(stream, state,
f) {Ð   state.tokenize = f;Ð   return f(stream, state);Ð }Ð var type, content;Ð
  function ret(_type, style, _content) {Ð   type = _type;Ð   content =
_content;Ð   return style;Ð }Ð function tokenBase(stream, state) {Ð   //
StringÐ   var ch = stream.peek();Ð   if (ch == "'" || ch == '"') {Ð
stream.next();Ð     return chain(stream, state, tokenString(ch, "string",
"string"));Ð   }Ð   // CommentÐ   else if (ch == "/") {Ð     stream.next();Ð
      if (stream.eat("*")) {Ð       return chain(stream, state, tokenComment);Ð
      } else if (stream.eat("/")) {Ð       stream.skipToEnd();Ð       return
ret("comment", "comment");Ð     } else {Ð       stream.skipTo(" ");Ð
return ret("operator", "operator");Ð     }Ð   }Ð   // DecimalÐ   else if (/
\d/.test(ch)) {Ð     stream.match(/^\d*(?:\.\d*)?(?:e[+\-]?\d+)?/);Ð
return ret("number", "number");Ð   }Ð   // HashÐ   else if (ch == "#") {Ð
stream.next();Ð     // Symbol with string syntaxÐ     ch = stream.peek();Ð
      if (ch == '"') {Ð       stream.next();Ð       return chain(stream,
state, tokenString('"', "symbol", "string-2"));Ð     }Ð     // Binary numberÐ
      else if (ch == "b") {Ð       stream.next();Ð       stream.eatWhile(/
[01]/);Ð       return ret("number", "number");Ð     }Ð     // Hex numberÐ
else if (ch == "x") {Ð       stream.next();Ð       stream.eatWhile(/[\da-f]/
i);Ð       return ret("number", "number");Ð     }Ð     // Octal numberÐ
else if (ch == "o") {Ð       stream.next();Ð       stream.eatWhile(/[0-7]/);Ð
        return ret("number", "number");Ð     }Ð     // Hash symbolÐ     else {Ð
        stream.eatWhile(/[-a-zA-Z]/);Ð       return ret("hash", "keyword");Ð
      }Ð   } else if (stream.match("end")) {Ð     return ret("end",
"keyword");Ð   }Ð   for (var name in patterns) {Ð     if
(patterns.hasOwnProperty(name)) {Ð       var pattern = patterns[name];Ð
if ((pattern instanceof Array && pattern.some(function(p) {Ð         return
stream.match(p);Ð       })) || stream.match(pattern))Ð         return
ret(name, patternStyles[name], stream.current());Ð     }Ð   }Ð   if
(stream.match("define")) {Ð     return ret("definition", "def");Ð   } else {Ð
      stream.eatWhile(/[\w\-]/);Ð     // KeywordÐ     if
(wordLookup[stream.current()]) {Ð       return
ret(wordLookup[stream.current()], styleLookup[stream.current()],
stream.current());Ð     } else if (stream.current().match(symbol)) {Ð
return ret("variable", "variable");Ð     } else {Ð       stream.next();Ð
        return ret("other", "variable-2");Ð     }Ð   }Ð }Ð function
tokenComment(stream, state) {Ð   var maybeEnd = false,Ð   ch;Ð   while ((ch =
stream.next())) {Ð     if (ch == "/" && maybeEnd) {Ð       state.tokenize =
tokenBase;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð   return
ret("comment", "comment");Ð }Ð function tokenString(quote, type, style) {Ð
return function(stream, state) {Ð     var next, end = false;Ð     while
((next = stream.next()) != null) {Ð       if (next == quote) {Ð         end =
true;Ð         break;Ð       }Ð     }Ð     if (end)Ð       state.tokenize =
tokenBase;Ð     return ret(type, style);Ð   };Ð }Ð // InterfaceÐ return {Ð
startState: function() {Ð     return {Ð       tokenize: tokenBase,Ð
currentIndent: 0Ð     };Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace())Ð       return null;Ð     var style =
state.tokenize(stream, state);Ð     return style;Ð   },Ð   blockCommentStart:
"/*",Ð
```

```
        blockCommentEnd: "*/"Ð };Þ);ÐodeMirror.defineMIME("text/x-dylan",
"dylan");Þ);Ð
```

public\assets\js\plugins\codemirror\mode\eiffel\eiffel.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("eiffel", function() {Ð function wordObj(words) {Ð
var o = {};Ð   for (var i = 0, e = words.length; i < e; ++i) o[words[i]] =
true;Ð   return o;Ð }Ð var keywords = wordObj([Ð   'note',Ð   'across',Ð
'when',Ð   'variant',Ð   'until',Ð   'unique',Ð   'undefine',Ð   'then',Ð
'strip',Ð   'select',Ð   'retry',Ð   'rescue',Ð   'require',Ð   'rename',Ð
'reference',Ð   'redefine',Ð   'prefix',Ð   'once',Ð   'old',Ð   'obsolete',Ð
    'loop',Ð   'local',Ð   'like',Ð   'is',Ð   'inspect',Ð   'infix',Ð
'include',Ð   'if',Ð   'frozen',Ð   'from',Ð   'external',Ð   'export',Ð
'ensure',Ð   'end',Ð   'elseif',Ð   'else',Ð   'do',Ð   'creation',Ð
'create',Ð   'check',Ð   'alias',Ð   'agent',Ð   'separate',Ð   'invariant',Ð
    'inherit',Ð   'indexing',Ð   'feature',Ð   'expanded',Ð   'deferred',Ð
'class',Ð   'Void',Ð   'True',Ð   'Result',Ð   'Precursor',Ð   'False',Ð
'Current',Ð   'create',Ð   'attached',Ð   'detachable',Ð   'as',Ð   'and',Ð
'implies',Ð   'not',Ð   'or'Ð ]);Ð var operators = wordObj([":=", "and
then","and", "or","<<",">>"]);Ð var curPunc;Ð function chain(newtok, stream,
state) {Ð   state.tokenize.push(newtok);Ð   return newtok(stream, state);Ð }Ð
function tokenBase(stream, state) {Ð   curPunc = null;Ð   if
(stream.eatSpace()) return null;Ð   var ch = stream.next();Ð   if (ch == '"'||
ch == "'") {Ð     return chain(readQuoted(ch, "string"), stream, state);Ð   }
else if (ch == "-"&&stream.eat("-")) {Ð     stream.skipToEnd();Ð     return
"comment";Ð   } else if (ch == ":"&&stream.eat("=")) {Ð     return "operator";Ð
    } else if (/[0-9]/.test(ch)) {Ð     stream.eatWhile(/[xXbBCc0-9\.]/);Ð
      stream.eat(/[\?\!]/);Ð     return "ident";Ð   } else if (/[a-zA-
Z_0-9]/.test(ch)) {Ð     stream.eatWhile(/[a-zA-Z_0-9]/);Ð     stream.eat(/[\?
\!]/);Ð     return "ident";Ð   } else if (/[=+\-\/*^%<>~]/.test(ch)) {Ð
stream.eatWhile(/[=+\-\/*^%<>~]/);Ð     return "operator";Ð   } else {Ð
return null;Ð   }Ð }Ð function readQuoted(quote, style,  unescaped) {Ð
return function(stream, state) {Ð     var escaped = false, ch;Ð     while
((ch = stream.next()) != null) {Ð       if (ch == quote && (unescaped || !
escaped)) {Ð         state.tokenize.pop();Ð         break;Ð       }Ð
escaped = !escaped && ch == "%";Ð     }Ð     return style;Ð   };Ð }Ð return {Ð
    startState: function() {Ð     return {tokenize: [tokenBase]};Ð   },Ð
token: function(stream, state) {Ð     var style =
state.tokenize[state.tokenize.length-1](stream, state);Ð     if (style ==
"ident") {Ð       var word = stream.current();Ð       style =
keywords.propertyIsEnumerable(stream.current()) ? "keyword"Ð         :
operators.propertyIsEnumerable(stream.current()) ? "operator"Ð         : /^[A-
Z][A-Z_0-9]*$/g.test(word) ? "tag"Ð         : /^0[bB][0-1]+$/g.test(word) ?
"number"Ð         : /^0[cC][0-7]+$/g.test(word) ? "number"Ð         : /^0[xX]
[a-fA-F0-9]+$/g.test(word) ? "number"Ð         : /^([0-9]+\.[0-9]*)|([0-9]*\.
[0-9]+)$/g.test(word) ? "number"Ð         : /^[0-9]+$/g.test(word) ? "number"Ð
          : "variable";Ð     }Ð     return style;Ð   },Ð   lineComment: "--"Ð
  };Ð });ÐodeMirror.defineMIME("text/x-eiffel", "eiffel");Ð });Ð
```

public\assets\js\plugins\codemirror\mode\erlang\erlang.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and othersØ/ Distributed
under an MIT license: http://codemirror.net/LICENSEØ*jshint unused:true,
eqnull:true, curly:true, bitwise:true */Ø*jshint undef:true, latedef:true,
trailing:true */Ø*global CodeMirror:true */Ø/ erlang mode.Ø/ tokenizer ->
token types -> CodeMirror stylesØ/ tokenizer maintains a parse stackØ/
indenter uses the parse stackØ/ TODO indenter:Ø/   bit syntaxØ/   old guard/
bif/conversion clashes (e.g. "float/1")Ø/   type/spec/opaqueØfunction(mod) {Ø
if (typeof exports == "object" && typeof module == "object") // CommonJSØ
mod(require("../../lib/codemirror"));Ø else if (typeof define == "function"
&& define.amd) // AMDØ   define(["../../lib/codemirror"], mod);Ø else //
Plain browser envØ   mod(CodeMirror);Ø})(function(CodeMirror) {Ø"use strict";Ø
CodeMirror.defineMIME("text/x-erlang", "erlang");Ø
CodeMirror.defineMode("erlang", function(cmCfg) {Ø "use strict";Ø
//////////////////////////////////////////////////////////////////////////Ø
// constantsØ var typeWords = [Ø   "-type", "-spec", "-export_type", "-
opaque"];Ø var keywordWords = [Ø
"after","begin","catch","case","cond","end","fun","if",Ø
"let","of","query","receive","try","when"];Ø var separatorRE    = /[\->,;]/;Ø
var separatorWords = [Ø   "->",";",","];Ø var operatorAtomWords = [Ø
"and","andalso","band","bnot","bor","bsl","bsr","bxor",Ø
"div","not","or","orelse","rem","xor"];Ø var operatorSymbolRE    = /[\+\-\*\/
<>=\|:!]/;Ø var operatorSymbolWords = [Ø
"=","+","-","*","/",">",">=","<","=<","=:=","==","=/=","/=","||","<-","!"];Ø
var openParenRE    = /[<\(\[\{]/;Ø var openParenWords = [Ø
"<<","(","[","{"];Ø var closeParenRE    = /[>\)\]\}]/;Ø var closeParenWords =
[Ø   "}","]",")",">>"];Ø var guardWords = [Ø
"is_atom","is_binary","is_bitstring","is_boolean","is_float",Ø
"is_function","is_integer","is_list","is_number","is_pid",Ø
"is_port","is_record","is_reference","is_tuple",Ø
"atom","binary","bitstring","boolean","function","integer","list",Ø
"number","pid","port","record","reference","tuple"];Ø var bifWords = [Ø
"abs","adler32","adler32_combine","alive","apply","atom_to_binary",Ø
"atom_to_list","binary_to_atom","binary_to_existing_atom",Ø
"binary_to_list","binary_to_term","bit_size","bitstring_to_list",Ø
"byte_size","check_process_code","contact_binary","crc32",Ø
"crc32_combine","date","decode_packet","delete_module",Ø
"disconnect_node","element","erase","exit","float","float_to_list",Ø
"garbage_collect","get","get_keys","group_leader","halt","hd",Ø
"integer_to_list","internal_bif","iolist_size","iolist_to_binary",Ø
"is_alive","is_atom","is_binary","is_bitstring","is_boolean",Ø
"is_float","is_function","is_integer","is_list","is_number","is_pid",Ø
"is_port","is_process_alive","is_record","is_reference","is_tuple",Ø
"length","link","list_to_atom","list_to_binary","list_to_bitstring",Ø
"list_to_existing_atom","list_to_float","list_to_integer",Ø
"list_to_pid","list_to_tuple","load_module","make_ref","module_loaded",Ø
"monitor_node","node","node_link","node_unlink","nodes","notalive",Ø
"now","open_port","pid_to_list","port_close","port_command",Ø
"port_connect","port_control","pre_loaded","process_flag",Ø
"process_info","processes","purge_module","put","register",Ø
"registered","round","self","setelement","size","spawn","spawn_link",Ø
"spawn_monitor","spawn_opt","split_binary","statistics",Ø
"term_to_binary","time","throw","tl","trunc","tuple_size",Ø
"tuple_to_list","unlink","unregister","whereis"];Ø/ upper case: [A-Z] [Ø-Þ]
[À-Ö]Ø/ lower case: [a-z] [ß-ö] [ø-ÿ]Ø var anumRE       = /[\w@Ø-ÞÀ-Öß-öø-ÿ]/;Ø
  var escapesRE    =Ø   /[0-7]{1,3}|[bdefnrstv\\"']|\^[a-zA-Z]|x[0-9a-zA-Z]
{2}|x{[0-9a-zA-Z]+}/;Ø
//////////////////////////////////////////////////////////////////////////Ø
// tokenizerØ function tokenizer(stream,state) {Ø   // in multi-line stringØ
    if (state.in_string) {Ø
```

```
                                  state.in_string = (!doubleQuote(stream));Ð
      return rval(state,stream,"string");Ð   }Ð   // in multi-line atomÐ   if
(state.in_atom) {Ð     state.in_atom = (!singleQuote(stream));Ð     return
rval(state,stream,"atom");Ð   }Ð   // whitespaceÐ   if (stream.eatSpace()) {Ð
      return rval(state,stream,"whitespace");Ð   }Ð   // attributes and type
specsÐ   if (!peekToken(state) &&Ð       stream.match(/-\s*[a-zß-öø-ÿ][\wØ-ÞÀ-
Öß-öø-ÿ]*/)) {Ð     if (is_member(stream.current(),typeWords)) {Ð
return rval(state,stream,"type");Ð     }else{Ð       return
rval(state,stream,"attribute");Ð     }Ð   }Ð   var ch = stream.next();Ð   //
commentÐ   if (ch == '%') {Ð     stream.skipToEnd();Ð     return
rval(state,stream,"comment");Ð   }Ð   // colonÐ   if (ch == ":") {Ð
return rval(state,stream,"colon");Ð   }Ð   // macroÐ   if (ch == '?') {Ð
stream.eatSpace();Ð     stream.eatWhile(anumRE);Ð     return
rval(state,stream,"macro");Ð   }Ð   // recordÐ   if (ch == "#") {Ð
stream.eatSpace();Ð     stream.eatWhile(anumRE);Ð     return
rval(state,stream,"record");Ð   }Ð   // dollar escapeÐ   if (ch == "$") {Ð
      if (stream.next() == "\\" && !stream.match(escapesRE)) {Ð       return
rval(state,stream,"error");Ð     }Ð     return rval(state,stream,"number");Ð
    }Ð   // dotÐ   if (ch == ".") {Ð     return rval(state,stream,"dot");Ð   }Ð
    // quoted atomÐ   if (ch == '\'') {Ð     if (!(state.in_atom = (!
singleQuote(stream)))) {Ð       if (stream.match(/\s*\/\s*[0-9]/,false)) {Ð
          stream.match(/\s*\/\s*[0-9]/,true);Ð         return
rval(state,stream,"fun");      // 'f'/0 style funÐ       }Ð       if
(stream.match(/\s*\(/,false) || stream.match(/\s*:/,false)) {Ð         return
rval(state,stream,"function");Ð       }Ð     }Ð     return
rval(state,stream,"atom");Ð   }Ð   // stringÐ   if (ch == '"') {Ð
state.in_string = (!doubleQuote(stream));Ð     return
rval(state,stream,"string");Ð   }Ð   // variableÐ   if (/[A-Z_Ø-ÞÀ-
Ö]/.test(ch)) {Ð     stream.eatWhile(anumRE);Ð     return
rval(state,stream,"variable");Ð   }Ð   // atom/keyword/BIF/functionÐ   if (/
[a-z_ß-öø-ÿ]/.test(ch)) {Ð     stream.eatWhile(anumRE);Ð     if
(stream.match(/\s*\/\s*[0-9]/,false)) {Ð       stream.match(/\s*\/
\s*[0-9]/,true);Ð       return rval(state,stream,"fun");      // f/0 style funÐ
      }Ð     var w = stream.current();Ð     if (is_member(w,keywordWords)) {Ð
        return rval(state,stream,"keyword");Ð     }else if
(is_member(w,operatorAtomWords)) {Ð       return
rval(state,stream,"operator");Ð     }else if (stream.match(/\s*\(/,false)) {Ð
        // 'put' and 'erlang:put' are bifs, 'foo:put' is notÐ       if
(is_member(w,bifWords) &&Ð           ((peekToken(state).token != ":") ||Ð
             (peekToken(state,2).token == "erlang"))) {Ð         return
rval(state,stream,"builtin");Ð       }else if (is_member(w,guardWords)) {Ð
          return rval(state,stream,"guard");Ð       }else{Ð         return
rval(state,stream,"function");Ð       }Ð     }else if
(is_member(w,operatorAtomWords)) {Ð       return
rval(state,stream,"operator");Ð     }else if (lookahead(stream) == ":") {Ð
        if (w == "erlang") {Ð         return rval(state,stream,"builtin");Ð
        } else {Ð         return rval(state,stream,"function");Ð       }Ð
      }else if (is_member(w,["true","false"])) {Ð       return
rval(state,stream,"boolean");Ð     }else if (is_member(w,["true","false"])) {Ð
        return rval(state,stream,"boolean");Ð     }else{Ð       return
rval(state,stream,"atom");Ð     }Ð   }Ð   // numberÐ   var digitRE      = /
[0-9]/;Ð   var radixRE      = /[0-9a-zA-Z]/;         // 36#zZ style intÐ   if
(digitRE.test(ch)) {Ð     stream.eatWhile(digitRE);Ð     if (stream.eat('#'))
{                 // 36#aZ  style integerÐ       if (!
stream.eatWhile(radixRE)) {Ð
stream.backUp(1);                 //"36#" - syntax errorÐ       }Ð     } else
if (stream.eat('.')) {       // floatÐ       if (!stream.eatWhile(digitRE)) {Ð
          stream.backUp(1);        // "3." - probably end of functionÐ
        } else {Ð         if (stream.eat(/[eE]/)) {        // float with
exponentÐ
```

```
                    if (stream.eat(/[-+]/)) {Ð             if (!
stream.eatWhile(digitRE)) {Ð               stream.backUp(2);            //
"2e-" - syntax errorÐ             }Ð           } else {Ð             if (!
stream.eatWhile(digitRE)) {Ð               stream.backUp(1);            //
"2e" - syntax errorÐ             }Ð           }Ð         }Ð       }Ð     }Ð
      return rval(state,stream,"number");   // normal integerÐ   }Ð   // open
parensÐ   if (nongreedy(stream,openParenRE,openParenWords)) {Ð     return
rval(state,stream,"open_paren");Ð   }Ð   // close parensÐ   if
(nongreedy(stream,closeParenRE,closeParenWords)) {Ð     return
rval(state,stream,"close_paren");Ð   }Ð   // separatorsÐ   if
(greedy(stream,separatorRE,separatorWords)) {Ð     return
rval(state,stream,"separator");Ð   }Ð   // operatorsÐ   if
(greedy(stream,operatorSymbolRE,operatorSymbolWords)) {Ð     return
rval(state,stream,"operator");Ð   }Ð   return rval(state,stream,null);Ð }Ð
//////////////////////////////////////////////////////////////////////////Ð
// utilitiesÐ function nongreedy(stream,re,words) {Ð   if
(stream.current().length == 1 && re.test(stream.current())) {Ð
stream.backUp(1);Ð     while (re.test(stream.peek())) {Ð       stream.next();Ð
        if (is_member(stream.current(),words)) {Ð         return true;Ð
        }Ð     }Ð     stream.backUp(stream.current().length-1);Ð   }Ð
return false;Ð }Ð function greedy(stream,re,words) {Ð   if
(stream.current().length == 1 && re.test(stream.current())) {Ð     while
(re.test(stream.peek())) {Ð       stream.next();Ð     }Ð     while (0 <
stream.current().length) {Ð       if (is_member(stream.current(),words)) {Ð
          return true;Ð       }else{Ð         stream.backUp(1);Ð       }Ð
      }Ð     stream.next();Ð   }Ð   return false;Ð }Ð function
doubleQuote(stream) {Ð   return quote(stream, '"', '\\');Ð }Ð function
singleQuote(stream) {Ð   return quote(stream,'\'','\\');Ð }Ð function
quote(stream,quoteChar,escapeChar) {Ð   while (!stream.eol()) {Ð     var ch =
stream.next();Ð     if (ch == quoteChar) {Ð       return true;Ð     }else if
(ch == escapeChar) {Ð       stream.next();Ð     }Ð   }Ð   return false;Ð }Ð
function lookahead(stream) {Ð   var m = stream.match(/([\n\s]+|
%[^\n]*\n)*(.)/,false);Ð   return m ? m.pop() : "";Ð }Ð function
is_member(element,list) {Ð   return (-1 < list.indexOf(element));Ð }Ð
function rval(state,stream,type) {Ð   // parse stackÐ
pushToken(state,realToken(type,stream));Ð   // map erlang token type to
CodeMirror style classÐ   //     erlang             -> CodeMirror tagÐ
switch (type) {Ð     case "atom":        return "atom";Ð     case
"attribute":   return "attribute";Ð     case "boolean":     return "atom";Ð
      case "builtin":     return "builtin";Ð     case "close_paren": return
null;Ð     case "colon":       return null;Ð     case "comment":     return
"comment";Ð     case "dot":         return null;Ð     case "error":
return "error";Ð     case "fun":         return "meta";Ð     case
"function":    return "tag";Ð     case "guard":       return "property";Ð
case "keyword":     return "keyword";Ð     case "macro":       return
"variable-2";Ð     case "number":      return "number";Ð     case
"open_paren":  return null;Ð     case "operator":    return "operator";Ð
case "record":      return "bracket";Ð     case "separator":   return null;Ð
      case "string":      return "string";Ð     case "type":        return
"def";Ð     case "variable":    return "variable";Ð     default:
return null;Ð   }Ð }Ð function aToken(tok,col,ind,typ) {Ð   return {token:
tok,Ð           column: col,Ð           indent: ind,Ð           type:   typ};Ð
  }Ð function realToken(type,stream) {Ð   return aToken(stream.current(),Ð
                  stream.column(),Ð                stream.indentation(),Ð
                  type);Ð }Ð function fakeToken(type) {Ð   return
aToken(type,0,0,type);Ð }Ð function peekToken(state,depth) {Ð   var len =
state.tokenStack.length;Ð   var dep = (depth ? depth : 1);Ð   if (len < dep) {Ð
      return false;Ð   }else{Ð     return state.tokenStack[len-dep];Ð   }Ð }Ð
function pushToken(state,token) {Ð   if (!(token.type == "comment" ||
token.type == "whitespace")) {Ð
```

```
                                    state.tokenStack =
maybe_drop_pre(state.tokenStack,token);Ð     state.tokenStack =
maybe_drop_post(state.tokenStack);Ð   }Ð }Ð function maybe_drop_pre(s,token) {Ð
    var last = s.length-1;Ð   if (0 < last && s[last].type === "record" &&
token.type === "dot") {Ð     s.pop();Ð   }else if (0 < last && s[last].type
=== "group") {Ð     s.pop();Ð     s.push(token);Ð   }else{Ð     s.push(token);Ð
    }Ð   return s;Ð }Ð function maybe_drop_post(s) {Ð   var last = s.length-1;Ð
    if (s[last].type === "dot") {Ð     return [];Ð   }Ð   if (s[last].type
=== "fun" && s[last-1].token === "fun") {Ð     return s.slice(0,last-1);Ð   }Ð
    switch (s[s.length-1].token) {Ð     case "}":    return d(s,{g:["{"]});Ð
      case "]":    return d(s,{i:["["]});Ð     case ")":    return d(s,{i:
["("]});Ð     case ">>":   return d(s,{i:["<<"]});Ð     case "end":  return
d(s,{i:["begin","case","fun","if","receive","try"]});Ð     case ",":
return d(s,{e:["begin","try","when","->",Ð
",","(","[","{","<<"]});Ð     case "->":   return d(s,{r:["when"],Ð
                                m:["try","if","case","receive"]});Ð     case
";":    return d(s,{E:["case","fun","if","receive","try","when"]});Ð     case
"catch":return d(s,{e:["try"]});Ð     case "of":   return d(s,{e:["case"]});Ð
      case "after":return d(s,{e:["receive","try"]});Ð     default:
return s;Ð   }Ð }Ð function d(stack,tt) {Ð   // stack is a stack of Token
objects.Ð   // tt is an object; {type:tokens}Ð   // type is a char, tokens is
a list of token strings.Ð   // The function returns (possibly truncated)
stack.Ð   // It will descend the stack, looking for a Token such that
Token.tokenÐ   //  is a member of tokens. If it does not find that, it will
normally (butÐ   //  see "E" below) return stack. If it does find a match, it
will removeÐ   //  all the Tokens between the top and the matched Token.Ð
    // If type is "m", that is all it does.Ð   // If type is "i", it will
also remove the matched Token and the top Token.Ð   // If type is "g", like
"i", but add a fake "group" token at the top.Ð   // If type is "r", it will
remove the matched Token, but not the top Token.Ð   // If type is "e", it
will keep the matched Token but not the top Token.Ð   // If type is "E", it
behaves as for type "e", except if there is no match,Ð   //  in which case it
will return an empty stack.Ð   for (var type in tt) {Ð     var len =
stack.length-1;Ð     var tokens = tt[type];Ð     for (var i = len-1; -1 < i ;
i--) {Ð       if (is_member(stack[i].token,tokens)) {Ð         var ss =
stack.slice(0,i);Ð         switch (type) {Ð             case "m": return
ss.concat(stack[i]).concat(stack[len]);Ð             case "r": return
ss.concat(stack[len]);Ð             case "i": return ss;Ð             case
"g": return ss.concat(fakeToken("group"));Ð             case "E": return
ss.concat(stack[i]);Ð             case "e": return ss.concat(stack[i]);Ð
          }Ð       }Ð     }Ð   }Ð   return (type == "E" ? [] : stack);Ð }Ð
//////////////////////////////////////////////////////////////////////////Ð
// indenterÐ function indenter(state,textAfter) {Ð   var t;Ð   var unit =
cmCfg.indentUnit;Ð   var wordAfter = wordafter(textAfter);Ð   var currT =
peekToken(state,1);Ð   var prevT = peekToken(state,2);Ð   if (state.in_string
|| state.in_atom) {Ð     return CodeMirror.Pass;Ð   }else if (!prevT) {Ð
return 0;Ð   }else if (currT.token == "when") {Ð     return currT.column+unit;Ð
    }else if (wordAfter === "when" && prevT.type === "function") {Ð
return prevT.indent+unit;Ð   }else if (wordAfter === "(" && currT.token ===
"fun") {Ð     return  currT.column+3;Ð   }else if (wordAfter === "catch" &&
(t = getToken(state,["try"]))) {Ð     return t.column;Ð   }else if
(is_member(wordAfter,["end","after","of"])) {Ð     t = getToken(state,
["begin","case","fun","if","receive","try"]);Ð     return t ? t.column :
CodeMirror.Pass;Ð   }else if (is_member(wordAfter,closeParenWords)) {Ð     t
= getToken(state,openParenWords);Ð     return t ? t.column : CodeMirror.Pass;Ð
    }else if (is_member(currT.token,[",","|","||"]) ||Ð
is_member(wordAfter,[",","|","||"])) {Ð     t = postcommaToken(state);Ð
return t ? t.column+t.token.length : unit;Ð   }else if (currT.token == "->") {Ð
      if (is_member(prevT.token, ["receive","case","if","try"])) {Ð
return prevT.column+unit+unit;Ð
```

```
                                    }else{Ð       return prevT.column+unit;Ð
      }Ð   }else if (is_member(currT.token,openParenWords)) {Ð     return
currT.column+currT.token.length;Ð   }else{Ð     t = defaultToken(state);Ð
return truthy(t) ? t.column+unit : 0;Ð   }Ð }Ð function wordafter(str) {Ð
var m = str.match(/,|[a-z]+|\}|\]|\)|>>|\|+|\(/);Ð   return truthy(m) &&
(m.index === 0) ? m[0] : "";Ð }Ð function postcommaToken(state) {Ð   var objs
= state.tokenStack.slice(0,-1);Ð   var i = getTokenIndex(objs,"type",
["open_paren"]);Ð   return truthy(objs[i]) ? objs[i] : false;Ð }Ð function
defaultToken(state) {Ð   var objs = state.tokenStack;Ð   var stop =
getTokenIndex(objs,"type",["open_paren","separator","keyword"]);Ð   var oper
= getTokenIndex(objs,"type",["operator"]);Ð   if (truthy(stop) &&
truthy(oper) && stop < oper) {Ð     return objs[stop+1];Ð   } else if
(truthy(stop)) {Ð     return objs[stop];Ð   } else {Ð     return false;Ð   }Ð
  }Ð function getToken(state,tokens) {Ð   var objs = state.tokenStack;Ð   var
i = getTokenIndex(objs,"token",tokens);Ð   return truthy(objs[i]) ? objs[i] :
false;Ð }Ð function getTokenIndex(objs,propname,propvals) {Ð   for (var i =
objs.length-1; -1 < i ; i--) {Ð     if (is_member(objs[i]
[propname],propvals)) {Ð       return i;Ð     }Ð   }Ð   return false;Ð }Ð
function truthy(x) {Ð   return (x !== false) && (x != null);Ð }Ð
////////////////////////////////////////////////////////////////////////////Ð
// this object defines the modeÐ return {Ð   startState:Ð     function() {Ð
        return {tokenStack: [],Ð               in_string:  false,Ð
                in_atom:    false};Ð     },Ð   token:Ð     function(stream,
state) {Ð       return tokenizer(stream, state);Ð     },Ð   indent:Ð
function(state, textAfter) {Ð       return indenter(state,textAfter);Ð     },Ð
    lineComment: "%"Ð };Ð});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\fortran\fortran.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("fortran", function() {Ð function words(array) {Ð   var
keys = {};Ð   for (var i = 0; i < array.length; ++i) {Ð     keys[array[i]] =
true;Ð   }Ð   return keys;Ð }Ð var keywords = words([Ð
"abstract", "accept", "allocatable", "allocate",Ð                 "array",
"assign", "asynchronous", "backspace",Ð                 "bind", "block",
"byte", "call", "case",Ð                 "class", "close", "common",
"contains",Ð                 "continue", "cycle", "data", "deallocate",Ð
                  "decode", "deferred", "dimension", "do",Ð
"elemental", "else", "encode", "end",Ð                 "endif", "entry",
"enumerator", "equivalence",Ð                 "exit", "external",
"extrinsic", "final",Ð                 "forall", "format", "function",
"generic",Ð                 "go", "goto", "if", "implicit", "import",
"include",Ð                 "inquire", "intent", "interface", "intrinsic",Ð
                  "module", "namelist", "non_intrinsic",Ð
"non_overridable", "none", "nopass",Ð                 "nullify", "open",
"optional", "options",Ð                 "parameter", "pass", "pause",
"pointer",Ð                 "print", "private", "program", "protected",Ð
                  "public", "pure", "read", "recursive", "result",Ð
                  "return", "rewind", "save", "select", "sequence",Ð
                  "stop", "subroutine", "target", "then", "to", "type",Ð
                  "use", "value", "volatile", "where", "while",Ð
                  "write"]);Ð var builtins = words(["abort", "abs", "access",
"achar", "acos",Ð                         "adjustl", "adjustr", "aimag",
"aint", "alarm",Ð                         "all", "allocated", "alog", "amax",
"amin",Ð                         "amod", "and", "anint", "any", "asin",Ð
                         "associated", "atan", "besj", "besjn", "besy",Ð
                         "besyn", "bit_size", "btest", "cabs", "ccos",Ð
                         "ceiling", "cexp", "char", "chdir", "chmod",Ð
                         "clog", "cmplx", "command_argument_count",Ð
                         "complex", "conjg", "cos", "cosh", "count",Ð
                         "cpu_time", "cshift", "csin", "csqrt", "ctime",Ð
                         "c_funloc", "c_loc", "c_associated", "c_null_ptr",Ð
                         "c_null_funptr", "c_f_pointer", "c_null_char",Ð
                         "c_alert", "c_backspace", "c_form_feed",Ð
                         "c_new_line", "c_carriage_return",Ð
                         "c_horizontal_tab", "c_vertical_tab", "dabs",Ð
                         "dacos", "dasin", "datan", "date_and_time",Ð
                         "dbesj", "dbesj", "dbesjn", "dbesy", "dbesy",Ð
                         "dbesyn", "dble", "dcos", "dcosh", "ddim", "derf",Ð
                         "derfc", "dexp", "digits", "dim", "dint", "dlog",Ð
                         "dlog", "dmax", "dmin", "dmod", "dnint",Ð
                         "dot_product", "dprod", "dsign", "dsinh",Ð
                         "dsin", "dsqrt", "dtanh", "dtan", "dtime",Ð
                         "eoshift", "epsilon", "erf", "erfc", "etime",Ð
                         "exit", "exp", "exponent", "extends_type_of",Ð
                         "fdate", "fget", "fgetc", "float", "floor",Ð
                         "flush", "fnum", "fputc", "fput", "fraction",Ð
                         "fseek", "fstat", "ftell", "gerror", "getarg",Ð
                         "get_command", "get_command_argument",Ð
                         "get_environment_variable", "getcwd",Ð
                         "getenv", "getgid", "getlog", "getpid",Ð
                         "getuid", "gmtime", "hostnm", "huge", "iabs",Ð
                         "iachar", "iand", "iargc", "ibclr", "ibits",Ð
```

```
                            "ibset", "ichar", "idate", "idim", "idint",Ð
                            "idnint", "ieor", "ierrno", "ifix", "imag",Ð
                            "imagpart", "index", "int", "ior", "irand",Ð
                            "isatty", "ishft", "ishftc", "isign",Ð
                            "iso_c_binding", "is_iostat_end", "is_iostat_eor",Ð
                            "itime", "kill", "kind", "lbound", "len",
"len_trim",Ð                          "lge", "lgt", "link", "lle", "llt",
"lnblnk", "loc",Ð                          "log", "logical", "long", "lshift",
"lstat", "ltime",Ð                          "matmul", "max", "maxexponent",
"maxloc", "maxval",Ð                          "mclock", "merge", "move_alloc",
"min", "minexponent",Ð                          "minloc", "minval", "mod",
"modulo", "mvbits",Ð                          "nearest", "new_line", "nint",
"not", "or", "pack",Ð                          "perror", "precision",
"present", "product", "radix",Ð                          "rand",
"random_number", "random_seed", "range",Ð                          "real",
"realpart", "rename", "repeat", "reshape",Ð
"rrspacing", "rshift", "same_type_as", "scale",Ð
"scan", "second", "selected_int_kind",Ð
"selected_real_kind", "set_exponent", "shape",Ð
"short", "sign", "signal", "sinh", "sin", "sleep",Ð
"sngl", "spacing", "spread", "sqrt", "srand", "stat",Ð
                            "sum", "symlnk", "system", "system_clock", "tan",Ð
                            "tanh", "time", "tiny", "transfer", "transpose",Ð
                            "trim", "ttynam", "ubound", "umask", "unlink",Ð
                            "unpack", "verify", "xor", "zabs", "zcos", "zexp",Ð
                            "zlog", "zsin", "zsqrt"]);Ð   var dataTypes =
words(["c_bool", "c_char", "c_double", "c_double_complex",Ð
                      "c_float", "c_float_complex", "c_funptr", "c_int",Ð
                      "c_int16_t", "c_int32_t", "c_int64_t", "c_int8_t",Ð
                      "c_int_fast16_t", "c_int_fast32_t", "c_int_fast64_t",Ð
                      "c_int_fast8_t", "c_int_least16_t", "c_int_least32_t",Ð
                      "c_int_least64_t", "c_int_least8_t", "c_intmax_t",Ð
                      "c_intptr_t", "c_long", "c_long_double",Ð
                      "c_long_double_complex", "c_long_long", "c_ptr",Ð
                      "c_short", "c_signed_char", "c_size_t", "character",Ð
                      "complex", "double", "integer", "logical", "real"]);Ð
var isOperatorChar = /[+\-*&=<>\/\:]/;Ð var litOperator = new
RegExp("(\.and\.|\.or\.|\.eq\.|\.lt\.|\.le\.|\.gt\.|\.ge\.|\.ne\.|\.not\.|
\.eqv\.|\.neqv\.)", "i");Ð function tokenBase(stream, state) {Ð   if
(stream.match(litOperator)){Ð       return 'operator';Ð   }Ð   var ch =
stream.next();Ð   if (ch == "!") {Ð     stream.skipToEnd();Ð     return
"comment";Ð   }Ð   if (ch == '"' || ch == "'") {Ð     state.tokenize =
tokenString(ch);Ð     return state.tokenize(stream, state);Ð   }Ð   if (/
[\[\]\(\),]/.test(ch)) {Ð     return null;Ð   }Ð   if (/\d/.test(ch)) {Ð
stream.eatWhile(/[\w\.]/);Ð     return "number";Ð   }Ð   if
(isOperatorChar.test(ch)) {Ð     stream.eatWhile(isOperatorChar);Ð     return
"operator";Ð   }Ð   stream.eatWhile(/[\w\$_]/);Ð   var word =
stream.current().toLowerCase();Ð   if (keywords.hasOwnProperty(word)){Ð
            return 'keyword';Ð   }Ð   if (builtins.hasOwnProperty(word) ||
dataTypes.hasOwnProperty(word)) {Ð           return 'builtin';Ð   }Ð   return
"variable";Ð }Ð function tokenString(quote) {Ð   return function(stream,
state) {Ð     var escaped = false, next, end = false;Ð     while ((next =
stream.next()) != null) {Ð       if (next == quote && !escaped) {Ð
end = true;Ð           break;Ð       }Ð       escaped = !escaped && next == "\
\";Ð     }Ð     if (end || !escaped) state.tokenize = null;Ð     return
"string";Ð   };Ð }Ð // InterfaceÐ return {Ð   startState: function() {Ð
return {tokenize: null};Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     var style = (state.tokenize ||
tokenBase)(stream, state);Ð
```

```
                                if (style == "comment" || style == "meta")
return style;Ð     return style;Ð   }Ð };Þ});ÐodeMirror.defineMIME("text/x-
fortran", "fortran");Þ});Ð
```

public\assets\js\plugins\codemirror\mode\gas\gas.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("gas", function(_config, parserConfig) {Ð 'use strict';Ð
  // If an architecture is specified, its initialization function may Ð //
populate this array with custom parsing functions which will be Ð // tried in
the event that the standard functions do not find a match.Ð var custom = [];Ð
  // The symbol used to start a line comment changes based on the target Ð //
architecture.Ð // If no architecture is pased in "parserConfig" then only
multiline Ð // comments will have syntax support.Ð var lineCommentStartSymbol
= "";Ð // These directives are architecture independent.Ð // Machine specific
directives should go in their respective Ð // architecture initialization
function.Ð // Reference:Ð // http://sourceware.org/binutils/docs/as/Pseudo-
Ops.html#Pseudo-Ops Ð var directives = {Ð   ".abort" : "builtin",Ð
".align" : "builtin",Ð   ".altmacro" : "builtin",Ð   ".ascii" : "builtin",Ð
".asciz" : "builtin",Ð   ".balign" : "builtin",Ð   ".balignw" : "builtin",Ð
".balignl" : "builtin",Ð   ".bundle_align_mode" : "builtin",Ð
".bundle_lock" : "builtin",Ð   ".bundle_unlock" : "builtin",Ð   ".byte" :
"builtin",Ð   ".cfi_startproc" : "builtin",Ð   ".comm" : "builtin",Ð
".data" : "builtin",Ð   ".def" : "builtin",Ð   ".desc" : "builtin",Ð
".dim" : "builtin",Ð   ".double" : "builtin",Ð   ".eject" : "builtin",Ð
".else" : "builtin",Ð   ".elseif" : "builtin",Ð   ".end" : "builtin",Ð
".endef" : "builtin",Ð   ".endfunc" : "builtin",Ð   ".endif" : "builtin",Ð
".equ" : "builtin",Ð   ".equiv" : "builtin",Ð   ".eqv" : "builtin",Ð
".err" : "builtin",Ð   ".error" : "builtin",Ð   ".exitm" : "builtin",Ð
".extern" : "builtin",Ð   ".fail" : "builtin",Ð   ".file" : "builtin",Ð
".fill" : "builtin",Ð   ".float" : "builtin",Ð   ".func" : "builtin",Ð
".global" : "builtin",Ð   ".gnu_attribute" : "builtin",Ð   ".hidden" :
"builtin",Ð   ".hword" : "builtin",Ð   ".ident" : "builtin",Ð   ".if" :
"builtin",Ð   ".incbin" : "builtin",Ð   ".include" : "builtin",Ð   ".int" :
"builtin",Ð   ".internal" : "builtin",Ð   ".irp" : "builtin",Ð   ".irpc" :
"builtin",Ð   ".lcomm" : "builtin",Ð   ".lflags" : "builtin",Ð   ".line" :
"builtin",Ð   ".linkonce" : "builtin",Ð   ".list" : "builtin",Ð   ".ln" :
"builtin",Ð   ".loc" : "builtin",Ð   ".loc_mark_labels" : "builtin",Ð
".local" : "builtin",Ð   ".long" : "builtin",Ð   ".macro" : "builtin",Ð
".mri" : "builtin",Ð   ".noaltmacro" : "builtin",Ð   ".nolist" : "builtin",Ð
    ".octa" : "builtin",Ð   ".offset" : "builtin",Ð   ".org" : "builtin",Ð
".p2align" : "builtin",Ð   ".popsection" : "builtin",Ð   ".previous" :
"builtin",Ð   ".print" : "builtin",Ð   ".protected" : "builtin",Ð
".psize" : "builtin",Ð   ".purgem" : "builtin",Ð   ".pushsection" : "builtin",Ð
    ".quad" : "builtin",Ð   ".reloc" : "builtin",Ð   ".rept" : "builtin",Ð
".sbttl" : "builtin",Ð   ".scl" : "builtin",Ð   ".section" : "builtin",Ð
".set" : "builtin",Ð   ".short" : "builtin",Ð   ".single" : "builtin",Ð
".size" : "builtin",Ð   ".skip" : "builtin",Ð   ".sleb128" : "builtin",Ð
".space" : "builtin",Ð   ".stab" : "builtin",Ð   ".string" : "builtin",Ð
".struct" : "builtin",Ð   ".subsection" : "builtin",Ð   ".symver" : "builtin",Ð
    ".tag" : "builtin",Ð   ".text" : "builtin",Ð   ".title" : "builtin",Ð
".type" : "builtin",Ð   ".uleb128" : "builtin",Ð   ".val" : "builtin",Ð
".version" : "builtin",Ð   ".vtable_entry" : "builtin",Ð
".vtable_inherit" : "builtin",Ð   ".warning" : "builtin",Ð   ".weak" :
"builtin",Ð   ".weakref" : "builtin",Ð   ".word" : "builtin" Ð };Ð var
registers = {};Ð function x86(_parserConfig) {Ð   lineCommentStartSymbol =
"#";Ð   registers.ax  = "variable";Ð   registers.eax = "variable-2";Ð
registers.rax = "variable-3";Ð   registers.bx  = "variable";Ð   registers.ebx
= "variable-2";Ð   registers.rbx = "variable-3";Ð   registers.cx  =
"variable";Ð
```

```
                registers.ecx = "variable-2";Ð   registers.rcx = "variable-3";Ð
    registers.dx  = "variable";Ð   registers.edx = "variable-2";Ð
registers.rdx = "variable-3";Ð   registers.si  = "variable";Ð   registers.esi
= "variable-2";Ð   registers.rsi = "variable-3";Ð   registers.di  =
"variable";Ð   registers.edi = "variable-2";Ð   registers.rdi = "variable-3";Ð
    registers.sp  = "variable";Ð   registers.esp = "variable-2";Ð
registers.rsp = "variable-3";Ð   registers.bp  = "variable";Ð   registers.ebp
= "variable-2";Ð   registers.rbp = "variable-3";Ð   registers.ip  =
"variable";Ð   registers.eip = "variable-2";Ð   registers.rip = "variable-3";Ð
    registers.cs  = "keyword";Ð   registers.ds  = "keyword";Ð   registers.ss
= "keyword";Ð   registers.es  = "keyword";Ð   registers.fs  = "keyword";Ð
registers.gs  = "keyword";Ð }Ð function armv6(_parserConfig) {Ð   //
Reference:Ð   // http://infocenter.arm.com/help/topic/com.arm.doc.qrc0001l/
QRC0001_UAL.pdfÐ   // http://infocenter.arm.com/help/topic/
com.arm.doc.ddi0301h/DDI0301H_arm1176jzfs_r0p7_trm.pdfÐ
lineCommentStartSymbol = "@";Ð   directives.syntax = "builtin";Ð
registers.r0  = "variable";Ð   registers.r1  = "variable";Ð   registers.r2  =
"variable";Ð   registers.r3  = "variable";Ð   registers.r4  = "variable";Ð
registers.r5  = "variable";Ð   registers.r6  = "variable";Ð   registers.r7  =
"variable";Ð   registers.r8  = "variable";Ð   registers.r9  = "variable";Ð
registers.r10 = "variable";Ð   registers.r11 = "variable";Ð   registers.r12 =
"variable";Ð   registers.sp  = "variable-2";Ð   registers.lr  = "variable-2";Ð
    registers.pc  = "variable-2";Ð   registers.r13 = registers.sp;Ð
registers.r14 = registers.lr;Ð   registers.r15 = registers.pc;Ð
custom.push(function(ch, stream) {Ð     if (ch === '#') {Ð
stream.eatWhile(/\w/);Ð       return "number";Ð     }Ð   });Ð }Ð var arch =
(parserConfig.architecture || "x86").toLowerCase();Ð if (arch === "x86") {Ð
x86(parserConfig);Ð } else if (arch === "arm" || arch === "armv6") {Ð
armv6(parserConfig);Ð }Ð function nextUntilUnescaped(stream, end) {Ð   var
escaped = false, next;Ð   while ((next = stream.next()) != null) {Ð     if
(next === end && !escaped) {Ð       return false;Ð     }Ð     escaped = !
escaped && next === "\\";Ð   }Ð   return escaped;Ð }Ð function
clikeComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while ((ch =
stream.next()) != null) {Ð     if (ch === "/" && maybeEnd) {Ð
state.tokenize = null;Ð       break;Ð     }Ð     maybeEnd = (ch === "*");Ð   }Ð
    return "comment";Ð }Ð return {Ð   startState: function() {Ð     return {Ð
        tokenize: nullÐ     };Ð   },Ð   token: function(stream, state) {Ð
if (state.tokenize) {Ð       return state.tokenize(stream, state);Ð     }Ð
      if (stream.eatSpace()) {Ð       return null;Ð     }Ð     var style,
cur, ch = stream.next();Ð     if (ch === "/") {Ð       if (stream.eat("*")) {Ð
          state.tokenize = clikeComment;Ð         return clikeComment(stream,
state);Ð       }Ð     }Ð     if (ch === lineCommentStartSymbol) {Ð
stream.skipToEnd();Ð       return "comment";Ð     }Ð     if (ch === '"') {Ð
        nextUntilUnescaped(stream, '"');Ð       return "string";Ð     }Ð
if (ch === '.') {Ð       stream.eatWhile(/\w/);Ð       cur =
stream.current().toLowerCase();Ð       style = directives[cur];Ð       return
style || null;Ð     }Ð     if (ch === '=') {Ð       stream.eatWhile(/\w/);Ð
        return "tag";Ð     }Ð     if (ch === '{') {Ð       return "braket";Ð
      }Ð     if (ch === '}') {Ð       return "braket";Ð     }Ð     if (/
\d/.test(ch)) {Ð       if (ch === "0" && stream.eat("x")) {Ð
stream.eatWhile(/[0-9a-fA-F]/);Ð         return "number";Ð       }Ð
stream.eatWhile(/\d/);Ð       return "number";Ð     }Ð     if (/\w/.test(ch))
{Ð       stream.eatWhile(/\w/);Ð       if (stream.eat(":")) {Ð         return
'tag';Ð       }Ð       cur = stream.current().toLowerCase();Ð       style =
registers[cur];Ð       return style || null;Ð     }Ð     for (var i = 0; i <
custom.length; i++) {Ð       style = custom[i](ch, stream, state);Ð       if
(style) {Ð         return style;Ð       }Ð     }Ð   },Ð   lineComment:
lineCommentStartSymbol,Ð   blockCommentStart: "/*",Ð   blockCommentEnd: "*/"Ð
  };Ð});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\gfm\gfm.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../markdown/markdown"),
require("../../addon/mode/overlay"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror", "../markdown/
markdown", "../../addon/mode/overlay"], mod);Ð else // Plain browser env Ð
mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("gfm", function(config, modeConfig) {Ð var codeDepth =
0;Ð function blankLine(state) {Ð   state.code = false;Ð   return null;Ð }Ð
var gfmOverlay = {Ð   startState: function() {Ð     return {Ð       code:
false,Ð       codeBlock: false,Ð       ateSpace: false Ð     };Ð   },Ð
copyState: function(s) {Ð     return {Ð       code: s.code,Ð       codeBlock:
s.codeBlock,Ð       ateSpace: s.ateSpace Ð     };Ð   },Ð   token:
function(stream, state) {Ð     state.combineTokens = null;Ð     // Hack to
prevent formatting override inside code blocks (block and inline) Ð     if
(state.codeBlock) {Ð       if (stream.match(/^```/)) {Ð
state.codeBlock = false;Ð         return null;Ð       }Ð
stream.skipToEnd();Ð       return null;Ð     }Ð     if (stream.sol()) {Ð
        state.code = false;Ð     }Ð     if (stream.sol() && stream.match(/
^```/)) {Ð       stream.skipToEnd();Ð       state.codeBlock = true;Ð
return null;Ð     }Ð     // If this block is changed, it may need to be
updated in Markdown mode Ð     if (stream.peek() === '`') {Ð
stream.next();Ð       var before = stream.pos;Ð       stream.eatWhile('`');Ð
        var difference = 1 + stream.pos - before;Ð       if (!state.code) {Ð
          codeDepth = difference;Ð         state.code = true;Ð       } else {Ð
          if (difference === codeDepth) { // Must be exact Ð
state.code = false;Ð         }Ð       }Ð       return null;Ð     } else if
(state.code) {Ð       stream.next();Ð       return null;Ð     }Ð     // Check
if space. If so, links can be formatted later on Ð     if (stream.eatSpace()) {Ð
        state.ateSpace = true;Ð       return null;Ð     }Ð     if
(stream.sol() || state.ateSpace) {Ð       state.ateSpace = false;Ð
if(stream.match(/^(?:[a-zA-Z0-9\-_]+\/)?(?:[a-zA-Z0-9\-_]+@)?(?:[a-f0-9]
{7,40}\b)/)) {Ð         // User/Project@SHA Ð         // User@SHA Ð         //
SHA Ð         state.combineTokens = true;Ð         return "link";Ð       }
else if (stream.match(/^(?:[a-zA-Z0-9\-_]+\/)?(?:[a-zA-Z0-9\-_]+)?#[0-9]+
\b/)) {Ð         // User/Project#Num Ð         // User#Num Ð         // #Num Ð
          state.combineTokens = true;Ð         return "link";Ð       }Ð     }Ð
      if (stream.match(/^((?:[a-z][\w-]+:(?:\/{1,3}|[a-z0-9%])|www\d{0,3}[.]|
[a-z0-9.\-]+[.][a-z]{2,4}\/)(?:[^\s()<>]|\([^\s()<>]*\))+(?:\([^\s()<>]*\)|
[^\s`*!()\[\]{};:'".,<>?«»“”‘’]))/i) &&Ð
stream.string.slice(stream.start - 2, stream.start) != "](") {Ð       // URLs Ð
        // Taken from http://daringfireball.net/2010/07/
improved_regex_for_matching_urls Ð       // And then (issue #1160) simplified
to make it not crash the Chrome Regexp engine Ð       state.combineTokens =
true;Ð       return "link";Ð     }Ð     stream.next();Ð     return null;Ð   },Ð
    blankLine: blankLine Ð };Ð var markdownConfig = {Ð
underscoresBreakWords: false,Ð   taskLists: true,Ð   fencedCodeBlocks: true Ð
  };Ð for (var attr in modeConfig) {Ð   markdownConfig[attr] =
modeConfig[attr];Ð }Ð markdownConfig.name = "markdown";Ð
CodeMirror.defineMIME("gfmBase", markdownConfig);Ð return
CodeMirror.overlayMode(CodeMirror.getMode(config, "gfmBase"), gfmOverlay);Ð,
"markdown");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\gfm\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ðfunction() {Ð var mode =
CodeMirror.getMode({tabSize: 4}, "gfm");Ð function MT(name) { test.mode(name,
mode, Array.prototype.slice.call(arguments, 1)); }Ð var
modeHighlightFormatting = CodeMirror.getMode({tabSize: 4}, {name: "gfm",
highlightFormatting: true});Ð function FT(name) { test.mode(name,
modeHighlightFormatting, Array.prototype.slice.call(arguments, 1)); }Ð
FT("codeBackticks",Ð    "[comment&formatting&formatting-code `][comment foo]
[comment&formatting&formatting-code `]");Ð FT("doubleBackticks",Ð
"[comment&formatting&formatting-code ``][comment foo ` bar]
[comment&formatting&formatting-code ``]");Ð FT("codeBlock",Ð
"[comment&formatting&formatting-code-block ```css]",Ð    "[tag foo]",Ð
"[comment&formatting&formatting-code-block ```]");Ð FT("taskList",Ð
"[variable-2&formatting&formatting-list&formatting-list-ul - ]
[meta&formatting&formatting-task [ ]]][variable-2  foo]",Ð
"[variable-2&formatting&formatting-list&formatting-list-ul - ]
[property&formatting&formatting-task [x]]][variable-2  foo]");Ð
MT("emInWordAsterisk",Ð    "foo[em *bar*]hello");Ð MT("emInWordUnderscore",Ð
     "foo_bar_hello");Ð MT("emStrongUnderscore",Ð    "[strong __][em&strong
_foo__][em _] bar");Ð MT("fencedCodeBlocks",Ð    "[comment ```]",Ð
"[comment foo]",Ð    "",Ð    "[comment ```]",Ð    "bar");Ð
MT("fencedCodeBlockModeSwitching",Ð    "[comment ```javascript]",Ð
"[variable foo]",Ð    "",Ð    "[comment ```]",Ð    "bar");Ð
MT("taskListAsterisk",Ð    "[variable-2 * []] foo]", // Invalid; must have
space or x between []Ð    "[variable-2 * [ ]]bar]", // Invalid; must have
space after ]Ð    "[variable-2 * [x]]hello]", // Invalid; must have space
after ]Ð    "[variable-2 * ][meta [ ]]][variable-2  [world]]]", // Valid;
tests reference style linksÐ    "    [variable-3 * ][property [x]]]
[variable-3  foo]"); // Valid; can be nestedÐ MT("taskListPlus",Ð
"[variable-2 + []] foo]", // Invalid; must have space or x between []Ð
"[variable-2 + [ ]]bar]", // Invalid; must have space after ]Ð
"[variable-2 + [x]]hello]", // Invalid; must have space after ]Ð
"[variable-2 + ][meta [ ]]][variable-2  [world]]]", // Valid; tests reference
style linksÐ    "    [variable-3 + ][property [x]]][variable-3  foo]"); //
Valid; can be nestedÐ MT("taskListDash",Ð    "[variable-2 - []] foo]", //
Invalid; must have space or x between []Ð    "[variable-2 - [ ]]bar]", //
Invalid; must have space after ]Ð    "[variable-2 - [x]]hello]", // Invalid;
must have space after ]Ð    "[variable-2 - ][meta [ ]]][variable-2
[world]]]", // Valid; tests reference style linksÐ    "    [variable-3 - ]
[property [x]]][variable-3  foo]"); // Valid; can be nestedÐ
MT("taskListNumber",Ð    "[variable-2 1. []] foo]", // Invalid; must have
space or x between []Ð    "[variable-2 2. [ ]]bar]", // Invalid; must have
space after ]Ð    "[variable-2 3. [x]]hello]", // Invalid; must have space
after ]Ð    "[variable-2 4. ][meta [ ]]][variable-2  [world]]]", // Valid;
tests reference style linksÐ    "    [variable-3 1. ][property [x]]]
[variable-3  foo]"); // Valid; can be nestedÐ MT("SHA",Ð    "foo [link
be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2] bar");Ð MT("SHAEmphasis",Ð    "[em
*foo ][em&link be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2][em *]");Ð
MT("shortSHA",Ð    "foo [link be6a8cc] bar");Ð MT("tooShortSHA",Ð    "foo
be6a8c bar");Ð MT("longSHA",Ð    "foo
be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd22 bar");Ð MT("badSHA",Ð    "foo
be6a8cc1c1ecfe9489fb51e4869af15a13fc2cg2 bar");Ð MT("userSHA",Ð    "foo [link
bar@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2] hello");Ð MT("userSHAEmphasis",Ð
     "[em *foo ][em&link bar@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2][em
*]");Ð MT("userProjectSHA",Ð    "foo [link bar/
hello@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2] world");Ð
MT("userProjectSHAEmphasis",Ð    "[em *foo ][em&link bar/
hello@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2][em *]");Ð MT("num",Ð    "foo
[link #1] bar");Ð
```

```
                Ð MT("numEmphasis",Ð    "[em *foo ][em&link #1][em *]");Ð
MT("badNum",Ð    "foo #1bar hello");Ð MT("userNum",Ð    "foo [link bar#1]
hello");Ð MT("userNumEmphasis",Ð    "[em *foo ][em&link bar#1][em *]");Ð
MT("userProjectNum",Ð    "foo [link bar/hello#1] world");Ð
MT("userProjectNumEmphasis",Ð    "[em *foo ][em&link bar/hello#1][em *]");Ð
MT("vanillaLink",Ð    "foo [link http://www.example.com/] bar");Ð
MT("vanillaLinkPunctuation",Ð    "foo [link http://www.example.com/]. bar");Ð
MT("vanillaLinkExtension",Ð    "foo [link http://www.example.com/index.html]
bar");Ð MT("vanillaLinkEmphasis",Ð    "foo [em *][em&link http://
www.example.com/index.html][em *] bar");Ð MT("notALink",Ð    "[comment
```css]",Ð    "[tag foo] {[property color]:[keyword black];}",Ð    "[comment
```][link http://www.example.com/]");Ð MT("notALink",Ð    "[comment ``foo
`bar` http://www.example.com/``] hello");Ð MT("notALink",Ð   "[comment
`foo]",Ð    "[link http://www.example.com/]",Ð    "[comment `foo]",Ð   "",Ð
     "[link http://www.example.com/]");Ð MT("headerCodeBlockGithub",Ð
"[header&header-1 # heading]",Ð   "",Ð   "[comment ```]",Ð   "[comment
code]",Ð   "[comment ```]",Ð   "",Ð   "Commit: [link
be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2]",Ð   "Issue: [link #1]",Ð
"Link: [link http://www.example.com/]");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\go\go.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("go", function(config) {Ð var indentUnit =
config.indentUnit;Ð var keywords = {Ð   "break":true, "case":true,
"chan":true, "const":true, "continue":true,Ð   "default":true, "defer":true,
"else":true, "fallthrough":true, "for":true,Ð   "func":true, "go":true,
"goto":true, "if":true, "import":true,Ð   "interface":true, "map":true,
"package":true, "range":true, "return":true,Ð   "select":true, "struct":true,
"switch":true, "type":true, "var":true,Ð   "bool":true, "byte":true,
"complex64":true, "complex128":true,Ð   "float32":true, "float64":true,
"int8":true, "int16":true, "int32":true,Ð   "int64":true, "string":true,
"uint8":true, "uint16":true, "uint32":true,Ð   "uint64":true, "int":true,
"uint":true, "uintptr":true Ð };Ð var atoms = {Ð   "true":true, "false":true,
"iota":true, "nil":true, "append":true,Ð   "cap":true, "close":true,
"complex":true, "copy":true, "imag":true,Ð   "len":true, "make":true,
"new":true, "panic":true, "print":true,Ð   "println":true, "real":true,
"recover":true Ð };Ð var isOperatorChar = /[+\-*&^%:=<>!|\/]/;Ð var curPunc;Ð
function tokenBase(stream, state) {Ð   var ch = stream.next();Ð   if (ch ==
'"' || ch == "'" || ch == "`") {Ð     state.tokenize = tokenString(ch);Ð
return state.tokenize(stream, state);Ð   }Ð   if (/[\d\.]/.test(ch)) {Ð
if (ch == ".") {Ð       stream.match(/^[0-9]+([eE][\-+]?[0-9]+)?/);Ð     }
else if (ch == "0") {Ð       stream.match(/^[xX][0-9a-fA-F]+/) ||
stream.match(/^0[0-7]+/);Ð     } else {Ð       stream.match(/^[0-9]*\.?
[0-9]*([eE][\-+]?[0-9]+)?/);Ð     }Ð     return "number";Ð   }Ð   if (/[\[\]
{}\(\),;\:\.]/.test(ch)) {Ð     curPunc = ch;Ð     return null;Ð   }Ð   if
(ch == "/") {Ð     if (stream.eat("*")) {Ð       state.tokenize =
tokenComment;Ð       return tokenComment(stream, state);Ð     }Ð     if
(stream.eat("/")) {Ð       stream.skipToEnd();Ð       return "comment";Ð     }Ð
    }Ð   if (isOperatorChar.test(ch)) {Ð     stream.eatWhile(isOperatorChar);Ð
      return "operator";Ð   }Ð   stream.eatWhile(/[\w\$_\xa1-\uffff]/);Ð
var cur = stream.current();Ð   if (keywords.propertyIsEnumerable(cur)) {Ð
if (cur == "case" || cur == "default") curPunc = "case";Ð     return
"keyword";Ð   }Ð   if (atoms.propertyIsEnumerable(cur)) return "atom";Ð
return "variable";Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, next, end = false;Ð
while ((next = stream.next()) != null) {Ð       if (next == quote && !
escaped) {end = true; break;}Ð       escaped = !escaped && next == "\\";Ð
      }Ð     if (end || !(escaped || quote == "`"))Ð       state.tokenize =
tokenBase;Ð     return "string";Ð   };Ð }Ð function tokenComment(stream,
state) {Ð   var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if
(ch == "/" && maybeEnd) {Ð       state.tokenize = tokenBase;Ð       break;Ð
      }Ð     maybeEnd = (ch == "*");Ð   }Ð   return "comment";Ð }Ð function
Context(indented, column, type, align, prev) {Ð   this.indented = indented;Ð
    this.column = column;Ð   this.type = type;Ð   this.align = align;Ð
this.prev = prev;Ð }Ð function pushContext(state, col, type) {Ð   return
state.context = new Context(state.indented, col, type, null, state.context);Ð
  }Ð function popContext(state) {Ð   var t = state.context.type;Ð   if (t ==
")" || t == "]" || t == "}")Ð     state.indented = state.context.indented;Ð
return state.context = state.context.prev;Ð }Ð // Interface Ð return {Ð
startState: function(basecolumn) {Ð     return {Ð       tokenize: null,Ð
        context: new Context((basecolumn || 0) - indentUnit, 0, "top", false),Ð
        indented: 0,Ð       startOfLine: true Ð     };Ð   },Ð   token:
function(stream, state) {Ð     var ctx = state.context;Ð     if
(stream.sol()) {Ð       if (ctx.align == null) ctx.align = false;Ð
state.indented = stream.indentation();Ð
```

```
                                                    state.startOfLine = true;Ð
        if (ctx.type == "case") ctx.type = "}";Ð     }Ð     if
(stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style =
(state.tokenize || tokenBase)(stream, state);Ð     if (style == "comment")
return style;Ð     if (ctx.align == null) ctx.align = true;Ð     if (curPunc
== "{") pushContext(state, stream.column(), "}");Ð     else if (curPunc ==
"[") pushContext(state, stream.column(), "]");Ð     else if (curPunc == "(")
pushContext(state, stream.column(), ")");Ð     else if (curPunc == "case")
ctx.type = "case";Ð     else if (curPunc == "}" && ctx.type == "}") ctx =
popContext(state);Ð     else if (curPunc == ctx.type) popContext(state);Ð
state.startOfLine = false;Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.tokenize != tokenBase &&
state.tokenize != null) return 0;Ð     var ctx = state.context, firstChar =
textAfter && textAfter.charAt(0);Ð     if (ctx.type == "case" && /^(?:case|
default)\b/.test(textAfter)) {Ð       state.context.type = "}";Ð       return
ctx.indented;Ð     }Ð     var closing = firstChar == ctx.type;Ð     if
(ctx.align) return ctx.column + (closing ? 0 : 1);Ð     else return
ctx.indented + (closing ? 0 : indentUnit);Ð   },Ð   electricChars: "{}):",Ð
fold: "brace",Ð   blockCommentStart: "/*",Ð   blockCommentEnd: "*/",Ð
lineComment: "//"Ð };Ð});ÐodeMirror.defineMIME("text/x-go", "go");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\groovy\groovy.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("groovy", function(config) {Ð function words(str) {Ð
var obj = {}, words = str.split(" ");Ð   for (var i = 0; i < words.length; +
+i) obj[words[i]] = true;Ð   return obj;Ð }Ð var keywords = words(Ð
"abstract as assert boolean break byte case catch char class const continue
def default " +Ð   "do double else enum extends final finally float for goto
if implements import in " +Ð   "instanceof int interface long native new
package private protected public return " +Ð   "short static strictfp super
switch synchronized threadsafe throw throws transient " +Ð   "try void
volatile while");Ð var blockKeywords = words("catch class do else finally for
if switch try while enum interface def");Ð var atoms = words("null true false
this");Ð var curPunc;Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (ch == '"' || ch == "'") {Ð     return startString(ch,
stream, state);Ð   }Ð   if (/[\[\]{}\(\),;\:\.]/.test(ch)) {Ð     curPunc =
ch;Ð     return null;Ð   }Ð   if (/\d/.test(ch)) {Ð     stream.eatWhile(/
[\w\.]/);Ð     if (stream.eat(/eE/)) { stream.eat(/\+\-/); stream.eatWhile(/
\d/); }Ð     return "number";Ð   }Ð   if (ch == "/") {Ð     if
(stream.eat("*")) {Ð       state.tokenize.push(tokenComment);Ð       return
tokenComment(stream, state);Ð     }Ð     if (stream.eat("/")) {Ð
stream.skipToEnd();Ð       return "comment";Ð     }Ð     if
(expectExpression(state.lastToken)) {Ð       return startString(ch, stream,
state);Ð     }Ð   }Ð   if (ch == "-" && stream.eat(">")) {Ð     curPunc = "-
>";Ð     return null;Ð   }Ð   if (/[+\-*&%=<>!?|\/~]/.test(ch)) {Ð
stream.eatWhile(/[+\-*&%=<>|~]/);Ð     return "operator";Ð   }Ð
stream.eatWhile(/[\w\$_]/);Ð   if (ch == "@") { stream.eatWhile(/[\w\$_\.]/);
return "meta"; }Ð   if (state.lastToken == ".") return "property";Ð   if
(stream.eat(":")) { curPunc = "proplabel"; return "property"; }Ð   var cur =
stream.current();Ð   if (atoms.propertyIsEnumerable(cur)) { return "atom"; }Ð
    if (keywords.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "keyword";Ð   }Ð   return "variable";Ð }Ð tokenBase.isBase = true;Ð
function startString(quote, stream, state) {Ð   var tripleQuoted = false;Ð
if (quote != "/" && stream.eat(quote)) {Ð     if (stream.eat(quote))
tripleQuoted = true;Ð     else return "string";Ð   }Ð   function t(stream,
state) {Ð     var escaped = false, next, end = !tripleQuoted;Ð     while
((next = stream.next()) != null) {Ð       if (next == quote && !escaped) {Ð
          if (!tripleQuoted) { break; }Ð         if (stream.match(quote +
quote)) { end = true; break; }Ð       }Ð       if (quote == '"' && next ==
"$" && !escaped && stream.eat("{")) {Ð
state.tokenize.push(tokenBaseUntilBrace());Ð         return "string";Ð       }Ð
        escaped = !escaped && next == "\\";Ð     }Ð     if (end)
state.tokenize.pop();Ð     return "string";Ð   }Ð   state.tokenize.push(t);Ð
    return t(stream, state);Ð }Ð function tokenBaseUntilBrace() {Ð   var
depth = 1;Ð   function t(stream, state) {Ð     if (stream.peek() == "}") {Ð
        depth--;Ð       if (depth == 0) {Ð         state.tokenize.pop();Ð
          return state.tokenize[state.tokenize.length-1](stream, state);Ð
        }Ð     } else if (stream.peek() == "{") {Ð       depth++;Ð     }Ð
return tokenBase(stream, state);Ð   }Ð   t.isBase = true;Ð   return t;Ð }Ð
function tokenComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while
(ch = stream.next()) {Ð     if (ch == "/" && maybeEnd) {Ð
state.tokenize.pop();Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð
    return "comment";Ð }Ð function expectExpression(last) {Ð   return !last
|| last == "operator" || last == "->" || /[\.\[\{\(,;:]/.test(last) ||Ð
last == "newstatement" || last == "keyword" || last == "proplabel";Ð
```

```
                                                                    }Ð
function Context(indented, column, type, align, prev) {Ð   this.indented =
indented;Ð   this.column = column;Ð   this.type = type;Ð   this.align = align;Ð
    this.prev = prev;Ð }Ð function pushContext(state, col, type) {Ð   return
state.context = new Context(state.indented, col, type, null, state.context);Ð
  }Ð function popContext(state) {Ð   var t = state.context.type;Ð   if (t ==
")" || t == "]" || t == "}")Ð     state.indented = state.context.indented;Ð
return state.context = state.context.prev;Ð }Ð // InterfaceÐ return {Ð
startState: function(basecolumn) {Ð     return {Ð       tokenize: [tokenBase],Ð
        context: new Context((basecolumn || 0) - config.indentUnit, 0, "top",
false),Ð       indented: 0,Ð       startOfLine: true,Ð       lastToken: nullÐ
      };Ð   },Ð   token: function(stream, state) {Ð     var ctx =
state.context;Ð     if (stream.sol()) {Ð       if (ctx.align == null)
ctx.align = false;Ð       state.indented = stream.indentation();Ð
state.startOfLine = true;Ð       // Automatic semicolon insertionÐ       if
(ctx.type == "statement" && !expectExpression(state.lastToken)) {Ð
popContext(state); ctx = state.context;Ð       }Ð     }Ð     if
(stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style =
state.tokenize[state.tokenize.length-1](stream, state);Ð     if (style ==
"comment") return style;Ð     if (ctx.align == null) ctx.align = true;Ð
if ((curPunc == ";" || curPunc == ":") && ctx.type == "statement")
popContext(state);Ð     // Handle indentation for {x -> \n ... }Ð     else if
(curPunc == "->" && ctx.type == "statement" && ctx.prev.type == "}") {Ð
popContext(state);Ð       state.context.align = false;Ð     }Ð     else if
(curPunc == "{") pushContext(state, stream.column(), "}");Ð     else if
(curPunc == "[") pushContext(state, stream.column(), "]");Ð     else if
(curPunc == "(") pushContext(state, stream.column(), ")");Ð     else if
(curPunc == "}") {Ð       while (ctx.type == "statement") ctx =
popContext(state);Ð       if (ctx.type == "}") ctx = popContext(state);Ð
        while (ctx.type == "statement") ctx = popContext(state);Ð     }Ð
else if (curPunc == ctx.type) popContext(state);Ð     else if (ctx.type ==
"}" || ctx.type == "top" || (ctx.type == "statement" && curPunc ==
"newstatement"))Ð       pushContext(state, stream.column(), "statement");Ð
      state.startOfLine = false;Ð     state.lastToken = curPunc || style;Ð
      return style;Ð   },Ð   indent: function(state, textAfter) {Ð     if (!
state.tokenize[state.tokenize.length-1].isBase) return 0;Ð     var firstChar
= textAfter && textAfter.charAt(0), ctx = state.context;Ð     if (ctx.type ==
"statement" && !expectExpression(state.lastToken)) ctx = ctx.prev;Ð     var
closing = firstChar == ctx.type;Ð     if (ctx.type == "statement") return
ctx.indented + (firstChar == "{" ? 0 : config.indentUnit);Ð     else if
(ctx.align) return ctx.column + (closing ? 0 : 1);Ð     else return
ctx.indented + (closing ? 0 : config.indentUnit);Ð   },Ð   electricChars:
"{}",Ð   fold: "brace"Ð };Ð});ÐodeMirror.defineMIME("text/x-groovy", "groovy");Ð
});Ð
```

public\assets\js\plugins\codemirror\mode\haml\haml.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../htmlmixed/htmlmixed"),
require("../ruby/ruby"));Ð else if (typeof define == "function" &&
define.amd) // AMD Ð   define(["../../lib/codemirror", "../htmlmixed/
htmlmixed", "../ruby/ruby"], mod);Ð else // Plain browser env Ð
mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð // full haml mode.
This handled embeded ruby and html fragments too Ð
CodeMirror.defineMode("haml", function(config) {Ð   var htmlMode =
CodeMirror.getMode(config, {name: "htmlmixed"});Ð   var rubyMode =
CodeMirror.getMode(config, "ruby");Ð   function rubyInQuote(endQuote) {Ð
return function(stream, state) {Ð       var ch = stream.peek();Ð       if (ch
== endQuote && state.rubyState.tokenize.length == 1) {Ð         // step out
of ruby context as it seems to complete processing all the braces Ð
stream.next();Ð         state.tokenize = html;Ð         return
"closeAttributeTag";Ð       } else {Ð         return ruby(stream, state);Ð
        }Ð     };Ð   }Ð   function ruby(stream, state) {Ð     if
(stream.match("-#")) {Ð       stream.skipToEnd();Ð       return "comment";Ð
      }Ð     return rubyMode.token(stream, state.rubyState);Ð   }Ð   function
html(stream, state) {Ð     var ch = stream.peek();Ð     // handle haml
declarations. All declarations that cant be handled here Ð     // will be
passed to html mode Ð     if (state.previousToken.style == "comment" ) {Ð
        if (state.indented > state.previousToken.indented) {Ð
stream.skipToEnd();Ð         return "commentLine";Ð       }Ð     }Ð     if
(state.startOfLine) {Ð       if (ch == "!" && stream.match("!!")) {Ð
stream.skipToEnd();Ð         return "tag";Ð       } else if (stream.match(/
^%[\w:#\.]+=/)) {Ð         state.tokenize = ruby;Ð         return "hamlTag";Ð
        } else if (stream.match(/^%[\w:]+/)) {Ð         return "hamlTag";Ð
        } else if (ch == "/" ) {Ð         stream.skipToEnd();Ð         return
"comment";Ð       }Ð     }Ð     if (state.startOfLine ||
state.previousToken.style == "hamlTag") {Ð       if ( ch == "#" || ch == ".")
{Ð         stream.match(/[\w-#\.]*/);Ð         return "hamlAttribute";Ð
        }Ð     }Ð     // donot handle --> as valid ruby, make it HTML close
comment instead Ð     if (state.startOfLine && !stream.match("-->", false) &&
(ch == "=" || ch == "-" )) {Ð       state.tokenize = ruby;Ð       return
state.tokenize(stream, state);Ð     }Ð     if (state.previousToken.style ==
"hamlTag" ||Ð         state.previousToken.style == "closeAttributeTag" ||Ð
          state.previousToken.style == "hamlAttribute") {Ð       if (ch ==
"(") {Ð         state.tokenize = rubyInQuote(")");Ð         return
state.tokenize(stream, state);Ð       } else if (ch == "{") {Ð
state.tokenize = rubyInQuote("}");Ð         return state.tokenize(stream,
state);Ð       }Ð     }Ð     return htmlMode.token(stream, state.htmlState);Ð
    }Ð   return {Ð     // default to html mode Ð     startState: function() {Ð
        var htmlState = htmlMode.startState();Ð       var rubyState =
rubyMode.startState();Ð       return {Ð         htmlState: htmlState,Ð
          rubyState: rubyState,Ð         indented: 0,Ð         previousToken:
{ style: null, indented: 0},Ð         tokenize: html Ð       };Ð     },Ð
copyState: function(state) {Ð       return {Ð         htmlState :
CodeMirror.copyState(htmlMode, state.htmlState),Ð         rubyState:
CodeMirror.copyState(rubyMode, state.rubyState),Ð         indented:
state.indented,Ð         previousToken: state.previousToken,Ð
tokenize: state.tokenize Ð       };Ð     },Ð     token: function(stream,
state) {Ð       if (stream.sol()) {Ð         state.indented =
stream.indentation();Ð         state.startOfLine = true;Ð       }Ð       if
(stream.eatSpace()) return null;Ð       var style = state.tokenize(stream,
state);Ð       state.startOfLine = false;Ð       // dont record comment line
as we only want to measure comment line with Ð       // the opening comment
block Ð
```

```
             if (style && style != "commentLine") {Ð
state.previousToken = { style: style, indented: state.indented };Ð       }Ð
        // if current state is ruby and the previous token is not `,` reset
theÐ       // tokenize to htmlÐ       if (stream.eol() && state.tokenize ==
ruby) {Ð         stream.backUp(1);Ð         var ch = stream.peek();Ð
stream.next();Ð         if (ch && ch != ",") {Ð           state.tokenize =
html;Ð         }Ð       }Ð       // reprocess some of the specific style tag
when finish setting previousTokenÐ       if (style == "hamlTag") {Ð
style = "tag";Ð       } else if (style == "commentLine") {Ð         style =
"comment";Ð       } else if (style == "hamlAttribute") {Ð         style =
"attribute";Ð       } else if (style == "closeAttributeTag") {Ð         style
= null;Ð       }Ð       return style;Ð     }Ð   };Ð }, "htmlmixed", "ruby");Ð
CodeMirror.defineMIME("text/x-haml", "haml");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\haml\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({tabSize: 4, indentUnit: 2}, "haml");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð //
Requires at least one media queryÐ MT("elementName",Ð    "[tag %h1] Hey
There");Ð MT("oneElementPerLine",Ð    "[tag %h1] Hey There %h2");Ð
MT("idSelector",Ð    "[tag %h1][attribute #test] Hey There");Ð
MT("classSelector",Ð    "[tag %h1][attribute .hello] Hey There");Ð
MT("docType",Ð    "[tag !!! XML]");Ð MT("comment",Ð    "[comment / Hello
WORLD]");Ð MT("notComment",Ð    "[tag %h1] This is not a / comment ");Ð
MT("attributes",Ð    "[tag %a]([variable title][operator =][string \"test\"])
{[atom :title] [operator =>] [string \"test\"]}");Ð MT("htmlCode",Ð
"[tag&bracket <][tag h1][tag&bracket >]Title[tag&bracket </][tag h1]
[tag&bracket >]");Ð MT("rubyBlock",Ð    "[operator =][variable-2 @item]");Ð
MT("selectorRubyBlock",Ð    "[tag %a.selector=] [variable-2 @item]");Ð
MT("nestedRubyBlock",Ð     "[tag %a]",Ð     "   [operator =][variable puts]
[string \"test\"]");Ð MT("multilinePlaintext",Ð     "[tag %p]",Ð     "
Hello,",Ð     "  World");Ð MT("multilineRuby",Ð     "[tag %p]",Ð
"  [comment -# this is a comment]",Ð     "     [comment and this is a comment
too]",Ð     "  Date/Time",Ð     "  [operator -] [variable now] [operator =]
[tag DateTime][operator .][property now]",Ð     "  [tag %strong=] [variable
now]",Ð     "  [operator -] [keyword if] [variable now] [operator >] [tag
DateTime][operator .][property parse]([string \"December 31, 2006\"])",Ð
"     [operator =][string \"Happy\"]",Ð     "     [operator =][string
\"Belated\"]",Ð     "     [operator =][string \"Birthday\"]");Ð
MT("multilineComment",Ð     "[comment /]",Ð     "  [comment Multiline]",Ð
"  [comment Comment]");Ð MT("hamlComment",Ð    "[comment -# this is a
comment]");Ð MT("multilineHamlComment",Ð    "[comment -# this is a comment]",Ð
     "   [comment and this is a comment too]");Ð MT("multilineHTMLComment",Ð
    "[comment <!--]",Ð   "  [comment what a comment]",Ð   "  [comment -->]");Ð
  MT("hamlAfterRubyTag",Ð   "[attribute .block]",Ð   "  [tag %strong=]
[variable now]",Ð   "  [attribute .test]",Ð   "     [operator =][variable
now]",Ð   "  [attribute .right]");Ð MT("stretchedRuby",Ð    "[operator =]
[variable puts] [string \"Hello\"],",Ð    "   [string \"World\"]");Ð
MT("interpolationInHashAttribute",Ð    //"[tag %div]{[atom :id] [operator =>]
[string \"#{][variable test][string }_#{][variable ting][string }\"]} test");Ð
     "[tag %div]{[atom :id] [operator =>] [string \"#{][variable test]
[string }_#{][variable ting][string }\"]} test");Ð
MT("interpolationInHTMLAttribute",Ð    "[tag %div]([variable title][operator
=][string \"#{][variable test][string }_#{][variable ting]()[string }\"])
Test");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\haskell\haskell.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("haskell", function(_config, modeConfig) {Ð function
switchState(source, setState, f) {Ð   setState(f);Ð   return f(source,
setState);Ð }Ð // These should all be Unicode extended, as per the Haskell
2010 report Ð var smallRE = /[a-z_]/;Ð var largeRE = /[A-Z]/;Ð var digitRE = /
\d/;Ð var hexitRE = /[0-9A-Fa-f]/;Ð var octitRE = /[0-7]/;Ð var idRE = /[a-
z_A-Z0-9'\xa1-\uffff]/;Ð var symbolRE = /[-!#$%&*+.\/<=>?@\\^|~:]/;Ð var
specialRE = /[(),;[\]`{}]/;Ð var whiteCharRE = /[ \t\v\f]/; // newlines are
handled in tokenizer Ð function normal(source, setState) {Ð   if
(source.eatWhile(whiteCharRE)) {Ð     return null;Ð   }Ð   var ch =
source.next();Ð   if (specialRE.test(ch)) {Ð     if (ch == '{' &&
source.eat('-')) {Ð       var t = "comment";Ð       if (source.eat('#')) {Ð
          t = "meta";Ð       }Ð       return switchState(source, setState,
ncomment(t, 1));Ð     }Ð     return null;Ð   }Ð   if (ch == '\'') {Ð     if
(source.eat('\\')) {Ð       source.next();  // should handle other escapes
hereÐ     }Ð     else {Ð       source.next();Ð     }Ð     if
(source.eat('\'')) {Ð       return "string";Ð     }Ð     return "error";Ð   }Ð
    if (ch == '"') {Ð     return switchState(source, setState, stringLiteral);Ð
    }Ð   if (largeRE.test(ch)) {Ð     source.eatWhile(idRE);Ð     if
(source.eat('.')) {Ð       return "qualifier";Ð     }Ð     return
"variable-2";Ð   }Ð   if (smallRE.test(ch)) {Ð     source.eatWhile(idRE);Ð
      return "variable";Ð   }Ð   if (digitRE.test(ch)) {Ð     if (ch == '0') {Ð
        if (source.eat(/[xX]/)) {Ð         source.eatWhile(hexitRE); //
should require at least 1Ð         return "integer";Ð       }Ð       if
(source.eat(/[oO]/)) {Ð         source.eatWhile(octitRE); // should require
at least 1Ð         return "number";Ð       }Ð     }Ð
source.eatWhile(digitRE);Ð     var t = "number";Ð     if (source.match(/^\.
\d+/)) {Ð       t = "number";Ð     }Ð     if (source.eat(/[eE]/)) {Ð       t
= "number";Ð       source.eat(/[-+]/);Ð       source.eatWhile(digitRE); //
should require at least 1Ð     }Ð     return t;Ð   }Ð   if (ch == "." &&
source.eat("."))Ð     return "keyword";Ð   if (symbolRE.test(ch)) {Ð     if
(ch == '-' && source.eat(/-/)) {Ð       source.eatWhile(/-/);Ð       if (!
source.eat(symbolRE)) {Ð         source.skipToEnd();Ð         return
"comment";Ð       }Ð     }Ð     var t = "variable";Ð     if (ch == ':') {Ð
        t = "variable-2";Ð     }Ð     source.eatWhile(symbolRE);Ð     return
t;Ð   }Ð   return "error";Ð }Ð function ncomment(type, nest) {Ð   if (nest ==
0) {Ð     return normal;Ð   }Ð   return function(source, setState) {Ð     var
currNest = nest;Ð     while (!source.eol()) {Ð       var ch = source.next();Ð
        if (ch == '{' && source.eat('-')) {Ð         ++currNest;Ð       }Ð
        else if (ch == '-' && source.eat('}')) {Ð         --currNest;Ð
          if (currNest == 0) {Ð           setState(normal);Ð           return
type;Ð         }Ð       }Ð     }Ð     setState(ncomment(type, currNest));Ð
      return type;Ð   };Ð }Ð function stringLiteral(source, setState) {Ð
while (!source.eol()) {Ð     var ch = source.next();Ð     if (ch == '"') {Ð
        setState(normal);Ð       return "string";Ð     }Ð     if (ch == '\\')
{Ð       if (source.eol() || source.eat(whiteCharRE)) {Ð
setState(stringGap);Ð         return "string";Ð       }Ð       if
(source.eat('&')) {Ð       }Ð       else {Ð         source.next(); // should
handle other escapes hereÐ       }Ð     }Ð   }Ð   setState(normal);Ð   return
"error";Ð }Ð function stringGap(source, setState) {Ð   if (source.eat('\\')) {Ð
      return switchState(source, setState, stringLiteral);Ð   }Ð
source.next();Ð   setState(normal);Ð   return "error";Ð }Ð var wellKnownWords
= (function() {Ð   var wkw = {};Ð   function setType(t) {Ð     return
function () {Ð
```

```
                    for (var i = 0; i < arguments.length; i++)Ð
wkw[arguments[i]] = t;Ð     };Ð   }Ð   setType("keyword")(Ð     "case",
"class", "data", "default", "deriving", "do", "else", "foreign",Ð     "if",
"import", "in", "infix", "infixl", "infixr", "instance", "let",Ð
"module", "newtype", "of", "then", "type", "where", "_");Ð
setType("keyword")(Ð     "\.\.", ":", "::", "=", "\\", "\"", "<-", "->", "@",
"~", "=>");Ð   setType("builtin")(Ð     "!!", "$!", "$", "&&", "+", "++",
"-", ".", "/", "/=", "<", "<=", "=<<",Ð     "==", ">", ">=", ">>", ">>=",
"^", "^^", "||", "*", "**");Ð   setType("builtin")(Ð     "Bool", "Bounded",
"Char", "Double", "EQ", "Either", "Enum", "Eq",Ð     "False", "FilePath",
"Float", "Floating", "Fractional", "Functor", "GT",Ð     "IO", "IOError",
"Int", "Integer", "Integral", "Just", "LT", "Left",Ð     "Maybe", "Monad",
"Nothing", "Num", "Ord", "Ordering", "Rational", "Read",Ð     "ReadS",
"Real", "RealFloat", "RealFrac", "Right", "Show", "ShowS",Ð     "String",
"True");Ð   setType("builtin")(Ð     "abs", "acos", "acosh", "all", "and",
"any", "appendFile", "asTypeOf",Ð     "asin", "asinh", "atan", "atan2",
"atanh", "break", "catch", "ceiling",Ð     "compare", "concat", "concatMap",
"const", "cos", "cosh", "curry",Ð     "cycle", "decodeFloat", "div",
"divMod", "drop", "dropWhile", "either",Ð     "elem", "encodeFloat",
"enumFrom", "enumFromThen", "enumFromThenTo",Ð     "enumFromTo", "error",
"even", "exp", "exponent", "fail", "filter",Ð     "flip", "floatDigits",
"floatRadix", "floatRange", "floor", "fmap",Ð     "foldl", "foldl1", "foldr",
"foldr1", "fromEnum", "fromInteger",Ð     "fromIntegral", "fromRational",
"fst", "gcd", "getChar", "getContents",Ð     "getLine", "head", "id", "init",
"interact", "ioError", "isDenormalized",Ð     "isIEEE", "isInfinite",
"isNaN", "isNegativeZero", "iterate", "last",Ð     "lcm", "length", "lex",
"lines", "log", "logBase", "lookup", "map",Ð     "mapM", "mapM_", "max",
"maxBound", "maximum", "maybe", "min", "minBound",Ð     "minimum", "mod",
"negate", "not", "notElem", "null", "odd", "or",Ð     "otherwise", "pi",
"pred", "print", "product", "properFraction",Ð     "putChar", "putStr",
"putStrLn", "quot", "quotRem", "read", "readFile",Ð     "readIO", "readList",
"readLn", "readParen", "reads", "readsPrec",Ð     "realToFrac", "recip",
"rem", "repeat", "replicate", "return", "reverse",Ð     "round",
"scaleFloat", "scanl", "scanl1", "scanr", "scanr1", "seq",Ð     "sequence",
"sequence_", "show", "showChar", "showList", "showParen",Ð     "showString",
"shows", "showsPrec", "significand", "signum", "sin",Ð     "sinh", "snd",
"span", "splitAt", "sqrt", "subtract", "succ", "sum",Ð     "tail", "take",
"takeWhile", "tan", "tanh", "toEnum", "toInteger",Ð     "toRational",
"truncate", "uncurry", "undefined", "unlines", "until",Ð     "unwords",
"unzip", "unzip3", "userError", "words", "writeFile", "zip",Ð     "zip3",
"zipWith", "zipWith3");Ð   var override = modeConfig.overrideKeywords;Ð   if
(override) for (var word in override) if (override.hasOwnProperty(word))Ð
wkw[word] = override[word];Ð   return wkw;Ð })();Ð return {Ð   startState:
function ()  { return { f: normal }; },Ð   copyState:  function (s) { return
{ f: s.f }; },Ð   token: function(stream, state) {Ð     var t =
state.f(stream, function(s) { state.f = s; });Ð     var w = stream.current();Ð
      return wellKnownWords.hasOwnProperty(w) ? wellKnownWords[w] : t;Ð   },Ð
    blockCommentStart: "{-",Ð   blockCommentEnd: "-}",Ð   lineComment: "--"Ð
  };Ð});ÐodeMirror.defineMIME("text/x-haskell", "haskell");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\haxe\haxe.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("haxe", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit;Ð // TokenizerÐ var keywords = function(){Ð
function kw(type) {return {type: type, style: "keyword"};}Ð   var A =
kw("keyword a"), B = kw("keyword b"), C = kw("keyword c");Ð   var operator =
kw("operator"), atom = {type: "atom", style: "atom"}, attribute =
{type:"attribute", style: "attribute"};Ð var type = kw("typedef");Ð   return {Ð
      "if": A, "while": A, "else": B, "do": B, "try": B,Ð     "return": C,
"break": C, "continue": C, "new": C, "throw": C,Ð     "var": kw("var"),
"inline":attribute, "static": attribute, "using":kw("import"),Ð   "public":
attribute, "private": attribute, "cast": kw("cast"), "import": kw("import"),
"macro": kw("macro"),Ð     "function": kw("function"), "catch": kw("catch"),
"untyped": kw("untyped"), "callback": kw("cb"),Ð     "for": kw("for"),
"switch": kw("switch"), "case": kw("case"), "default": kw("default"),Ð
"in": operator, "never": kw("property_access"), "trace":kw("trace"),Ð
"class": type, "abstract":type, "enum":type, "interface":type,
"typedef":type, "extends":type, "implements":type, "dynamic":type,Ð
"true": atom, "false": atom, "null": atomÐ   };Ð }();Ð var isOperatorChar = /
[+\-*&%=<>!?|]/;Ð function chain(stream, state, f) {Ð   state.tokenize = f;Ð
    return f(stream, state);Ð }Ð function nextUntilUnescaped(stream, end) {Ð
    var escaped = false, next;Ð   while ((next = stream.next()) != null) {Ð
      if (next == end && !escaped)Ð       return false;Ð     escaped = !
escaped && next == "\\";Ð   }Ð   return escaped;Ð }Ð // Used as scratch
variables to communicate multiple values without Ð // consing up tons of
objects.Ð var type, content;Ð function ret(tp, style, cont) {Ð   type = tp;
content = cont;Ð   return style;Ð }Ð function haxeTokenBase(stream, state) {Ð
    var ch = stream.next();Ð   if (ch == '"' || ch == "'")Ð     return
chain(stream, state, haxeTokenString(ch));Ð   else if (/[\[\]{}\(\),;\:
\.]/.test(ch))Ð     return ret(ch);Ð   else if (ch == "0" && stream.eat(/x/
i)) {Ð     stream.eatWhile(/[\da-f]/i);Ð     return ret("number", "number");Ð
    }Ð   else if (/\d/.test(ch) || ch == "-" && stream.eat(/\d/)) {Ð
stream.match(/^\d*(?:\.\d*)?(?:[eE][+\-]?\d+)?/);Ð     return ret("number",
"number");Ð   }Ð   else if (state.reAllowed && (ch == "~" && stream.eat(/
\//))) {Ð     nextUntilUnescaped(stream, "/");Ð     stream.eatWhile(/
[gimsu]/);Ð     return ret("regexp", "string-2");Ð   }Ð   else if (ch == "/")
{Ð     if (stream.eat("*")) {Ð       return chain(stream, state,
haxeTokenComment);Ð     }Ð     else if (stream.eat("/")) {Ð
stream.skipToEnd();Ð       return ret("comment", "comment");Ð     }Ð     else
{Ð       stream.eatWhile(isOperatorChar);Ð       return ret("operator", null,
stream.current());Ð     }Ð   }Ð   else if (ch == "#") {Ð
stream.skipToEnd();Ð       return ret("conditional", "meta");Ð   }Ð   else if
(ch == "@") {Ð     stream.eat(/:/);Ð     stream.eatWhile(/[\w_]/);Ð
return ret ("metadata", "meta");Ð   }Ð   else if (isOperatorChar.test(ch)) {Ð
      stream.eatWhile(isOperatorChar);Ð     return ret("operator", null,
stream.current());Ð   }Ð   else {Ð   var word;Ð   if(/[A-Z]/.test(ch))Ð   {Ð
      stream.eatWhile(/[\w_<>]/);Ð     word = stream.current();Ð     return
ret("type", "variable-3", word);Ð   }Ð   elseÐ   {Ð       stream.eatWhile(/
[\w_]/);Ð       var word = stream.current(), known =
keywords.propertyIsEnumerable(word) && keywords[word];Ð       return (known
&& state.kwAllowed) ? ret(known.type, known.style, word) :Ð
                        ret("variable", "variable", word);Ð   }Ð   }Ð }Ð
function haxeTokenString(quote) {Ð   return function(stream, state) {Ð     if
(!nextUntilUnescaped(stream, quote))Ð       state.tokenize = haxeTokenBase;Ð
      return ret("string", "string");Ð
```

```
                                        };Ð }Ð function
haxeTokenComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while (ch =
stream.next()) {Ð     if (ch == "/" && maybeEnd) {Ð       state.tokenize =
haxeTokenBase;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð
return ret("comment", "comment");Ð }Ð // ParserÐ var atomicTypes = {"atom":
true, "number": true, "variable": true, "string": true, "regexp": true};Ð
function HaxeLexical(indented, column, type, align, prev, info) {Ð
this.indented = indented;Ð   this.column = column;Ð   this.type = type;Ð
this.prev = prev;Ð   this.info = info;Ð   if (align != null) this.align =
align;Ð }Ð function inScope(state, varname) {Ð   for (var v =
state.localVars; v; v = v.next)Ð     if (v.name == varname) return true;Ð }Ð
function parseHaxe(state, style, type, content, stream) {Ð   var cc =
state.cc;Ð   // Communicate our context to the combinators.Ð   // (Less
wasteful than consing up a hundred closures on every call.)Ð   cx.state =
state; cx.stream = stream; cx.marked = null, cx.cc = cc;Ð   if (!
state.lexical.hasOwnProperty("align"))Ð     state.lexical.align = true;Ð
while(true) {Ð     var combinator = cc.length ? cc.pop() : statement;Ð     if
(combinator(type, content)) {Ð       while(cc.length && cc[cc.length - 1].lex)Ð
          cc.pop()();Ð       if (cx.marked) return cx.marked;Ð       if (type
== "variable" && inScope(state, content)) return "variable-2";Ð   if (type ==
"variable" && imported(state, content)) return "variable-3";Ð       return
style;Ð     }Ð   }Ð }Ð function imported(state, typename)Ð {Ð if (/[a-
z]/.test(typename.charAt(0)))Ð   return false;Ð var len =
state.importedtypes.length;Ð for (var i = 0; i<len; i++)Ð
if(state.importedtypes[i]==typename) return true;Ð }Ð function
registerimport(importname) {Ð var state = cx.state;Ð for (var t =
state.importedtypes; t; t = t.next)Ð   if(t.name == importname) return;Ð
state.importedtypes = { name: importname, next: state.importedtypes };Ð }Ð //
Combinator utilsÐ var cx = {state: null, column: null, marked: null, cc:
null};Ð function pass() {Ð   for (var i = arguments.length - 1; i >= 0; i--)
cx.cc.push(arguments[i]);Ð }Ð function cont() {Ð   pass.apply(null,
arguments);Ð   return true;Ð }Ð function register(varname) {Ð   var state =
cx.state;Ð   if (state.context) {Ð     cx.marked = "def";Ð     for (var v =
state.localVars; v; v = v.next)Ð       if (v.name == varname) return;Ð
state.localVars = {name: varname, next: state.localVars};Ð   }Ð }Ð //
CombinatorsÐ var defaultVars = {name: "this", next: null};Ð function
pushcontext() {Ð   if (!cx.state.context) cx.state.localVars = defaultVars;Ð
    cx.state.context = {prev: cx.state.context, vars: cx.state.localVars};Ð }Ð
  function popcontext() {Ð   cx.state.localVars = cx.state.context.vars;Ð
cx.state.context = cx.state.context.prev;Ð }Ð function pushlex(type, info) {Ð
    var result = function() {Ð     var state = cx.state;Ð     state.lexical =
new HaxeLexical(state.indented, cx.stream.column(), type, null,
state.lexical, info);Ð   };Ð   result.lex = true;Ð   return result;Ð }Ð
function poplex() {Ð   var state = cx.state;Ð   if (state.lexical.prev) {Ð
      if (state.lexical.type == ")")Ð       state.indented =
state.lexical.indented;Ð     state.lexical = state.lexical.prev;Ð   }Ð }Ð
poplex.lex = true;Ð function expect(wanted) {Ð   function f(type) {Ð     if
(type == wanted) return cont();Ð     else if (wanted == ";") return pass();Ð
      else return cont(f);Ð   };Ð   return f;Ð }Ð function statement(type) {Ð
    if (type == "@") return cont(metadef);Ð   if (type == "var") return
cont(pushlex("vardef"), vardef1, expect(";"), poplex);Ð   if (type ==
"keyword a") return cont(pushlex("form"), expression, statement, poplex);Ð
if (type == "keyword b") return cont(pushlex("form"), statement, poplex);Ð
if (type == "{") return cont(pushlex("}"), pushcontext, block, poplex,
popcontext);Ð   if (type == ";") return cont();Ð   if (type == "attribute")
return cont(maybeattribute);Ð   if (type == "function") return
cont(functiondef);Ð   if (type == "for") return cont(pushlex("form"),
expect("("), pushlex(")"), forspec1, expect(")"),Ð
                                        poplex, statement, poplex);Ð   if (type
== "variable") return cont(pushlex("stat"), maybelabel);Ð
```

```
                                                            if (type ==
"switch") return cont(pushlex("form"), expression, pushlex("}", "switch"),
expect("{"),Ð                                          block, poplex, poplex);Ð
    if (type == "case") return cont(expression, expect(":"));Ð   if (type ==
"default") return cont(expect(":"));Ð   if (type == "catch") return
cont(pushlex("form"), pushcontext, expect("("), funarg, expect(")"),Ð
                                        statement, poplex, popcontext);Ð   if
(type == "import") return cont(importdef, expect(";"));Ð   if (type ==
"typedef") return cont(typedef);Ð   return pass(pushlex("stat"), expression,
expect(";"), poplex);Ð }Ð function expression(type) {Ð   if
(atomicTypes.hasOwnProperty(type)) return cont(maybeoperator);Ð   if (type ==
"function") return cont(functiondef);Ð   if (type == "keyword c") return
cont(maybeexpression);Ð   if (type == "(") return cont(pushlex(")"),
maybeexpression, expect(")"), poplex, maybeoperator);Ð   if (type ==
"operator") return cont(expression);Ð   if (type == "[") return
cont(pushlex("]"), commasep(expression, "]"), poplex, maybeoperator);Ð   if
(type == "{") return cont(pushlex("}"), commasep(objprop, "}"), poplex,
maybeoperator);Ð   return cont();Ð }Ð function maybeexpression(type) {Ð   if
(type.match(/[;\}\)\],]/)) return pass();Ð   return pass(expression);Ð }Ð
function maybeoperator(type, value) {Ð   if (type == "operator" && /\+\
+|--/.test(value)) return cont(maybeoperator);Ð   if (type == "operator" ||
type == ":") return cont(expression);Ð   if (type == ";") return;Ð   if (type
== "(") return cont(pushlex(")"), commasep(expression, ")"), poplex,
maybeoperator);Ð   if (type == ".") return cont(property, maybeoperator);Ð
if (type == "[") return cont(pushlex("]"), expression, expect("]"), poplex,
maybeoperator);Ð }Ð function maybeattribute(type) {Ð   if (type ==
"attribute") return cont(maybeattribute);Ð   if (type == "function") return
cont(functiondef);Ð   if (type == "var") return cont(vardef1);Ð }Ð function
metadef(type) {Ð   if(type == ":") return cont(metadef);Ð   if(type ==
"variable") return cont(metadef);Ð   if(type == "(") return
cont(pushlex(")"), commasep(metaargs, ")"), poplex, statement);Ð }Ð function
metaargs(type) {Ð   if(type == "variable") return cont();Ð }Ð function
importdef (type, value) {Ð if(type == "variable" && /[A-
Z]/.test(value.charAt(0))) { registerimport(value); return cont(); }Ð else
if(type == "variable" || type == "property" || type == "." || value == "*")
return cont(importdef);Ð }Ð function typedef (type, value)Ð {Ð if(type ==
"variable" && /[A-Z]/.test(value.charAt(0))) { registerimport(value); return
cont(); }Ð else if (type == "type" && /[A-Z]/.test(value.charAt(0))) { return
cont(); }Ð }Ð function maybelabel(type) {Ð   if (type == ":") return
cont(poplex, statement);Ð   return pass(maybeoperator, expect(";"), poplex);Ð
  }Ð function property(type) {Ð   if (type == "variable") {cx.marked =
"property"; return cont();}Ð }Ð function objprop(type) {Ð   if (type ==
"variable") cx.marked = "property";Ð   if (atomicTypes.hasOwnProperty(type))
return cont(expect(":"), expression);Ð }Ð function commasep(what, end) {Ð
function proceed(type) {Ð     if (type == ",") return cont(what, proceed);Ð
      if (type == end) return cont();Ð     return cont(expect(end));Ð   }Ð
return function(type) {Ð     if (type == end) return cont();Ð     else return
pass(what, proceed);Ð   };Ð }Ð function block(type) {Ð   if (type == "}")
return cont();Ð   return pass(statement, block);Ð }Ð function vardef1(type,
value) {Ð   if (type == "variable"){register(value); return cont(typeuse,
vardef2);}Ð   return cont();Ð }Ð function vardef2(type, value) {Ð   if (value
== "=") return cont(expression, vardef2);Ð   if (type == ",") return
cont(vardef1);Ð }Ð function forspec1(type, value) {Ð if (type == "variable") {Ð
    register(value);Ð }Ð return cont(pushlex(")"), pushcontext, forin,
expression, poplex, statement, popcontext);Ð }Ð function forin(_type, value) {Ð
    if (value == "in") return cont();Ð }Ð function functiondef(type, value) {Ð
    if (type == "variable") {register(value); return cont(functiondef);}Ð
if (value == "new") return cont(functiondef);Ð   if (type == "(") return
cont(pushlex(")"), pushcontext, commasep(funarg, ")"), poplex, typeuse,
statement, popcontext);Ð
```

```
                          }Ð function typeuse(type) {Ð   if(type == ":")
return cont(typestring);Ð }Ð function typestring(type) {Ð   if(type ==
"type") return cont();Ð   if(type == "variable") return cont();Ð   if(type ==
"{") return cont(pushlex("}"), commasep(typeprop, "}"), poplex);Ð }Ð function
typeprop(type) {Ð   if(type == "variable") return cont(typeuse);Ð }Ð function
funarg(type, value) {Ð   if (type == "variable") {register(value); return
cont(typeuse);}Ð }Ð // InterfaceÐ return {Ð   startState:
function(basecolumn) {Ð   var defaulttypes = ["Int", "Float", "String",
"Void", "Std", "Bool", "Dynamic", "Array"];Ð     return {Ð       tokenize:
haxeTokenBase,Ð       reAllowed: true,Ð       kwAllowed: true,Ð       cc: [],Ð
        lexical: new HaxeLexical((basecolumn || 0) - indentUnit, 0, "block",
false),Ð       localVars: parserConfig.localVars,Ð   importedtypes:
defaulttypes,Ð       context: parserConfig.localVars && {vars:
parserConfig.localVars},Ð       indented: 0Ð     };Ð   },Ð   token:
function(stream, state) {Ð     if (stream.sol()) {Ð       if (!
state.lexical.hasOwnProperty("align"))Ð         state.lexical.align = false;Ð
        state.indented = stream.indentation();Ð     }Ð     if
(stream.eatSpace()) return null;Ð     var style = state.tokenize(stream,
state);Ð     if (type == "comment") return style;Ð     state.reAllowed = !!
(type == "operator" || type == "keyword c" || type.match(/^[\[{}\(,;:]$/));Ð
      state.kwAllowed = type != '.';Ð     return parseHaxe(state, style,
type, content, stream);Ð   },Ð   indent: function(state, textAfter) {Ð     if
(state.tokenize != haxeTokenBase) return 0;Ð     var firstChar = textAfter &&
textAfter.charAt(0), lexical = state.lexical;Ð     if (lexical.type == "stat"
&& firstChar == "}") lexical = lexical.prev;Ð     var type = lexical.type,
closing = firstChar == type;Ð     if (type == "vardef") return
lexical.indented + 4;Ð     else if (type == "form" && firstChar == "{")
return lexical.indented;Ð     else if (type == "stat" || type == "form")
return lexical.indented + indentUnit;Ð     else if (lexical.info == "switch"
&& !closing)Ð       return lexical.indented + (/^(?:case|
default)\b/.test(textAfter) ? indentUnit : 2 * indentUnit);Ð     else if
(lexical.align) return lexical.column + (closing ? 0 : 1);Ð     else return
lexical.indented + (closing ? 0 : indentUnit);Ð   },Ð   electricChars: "{}",Ð
    blockCommentStart: "/*",Ð   blockCommentEnd: "*/",Ð   lineComment: "//"Ð
  };Þ);ÐodeMirror.defineMIME("text/x-haxe", "haxe");Ð
CodeMirror.defineMode("hxml", function () {Ð return {Ð   startState: function
() {Ð     return {Ð       define: false,Ð       inString: falseÐ     };Ð   },Ð
    token: function (stream, state) {Ð     var ch = stream.peek();Ð     var
sol = stream.sol();Ð     ///* comments */Ð     if (ch == "#") {Ð
stream.skipToEnd();Ð       return "comment";Ð     }Ð     if (sol && ch ==
"-") {Ð       var style = "variable-2";Ð       stream.eat(/-/);Ð       if
(stream.peek() == "-") {Ð         stream.eat(/-/);Ð         style = "keyword
a";Ð       }Ð       if (stream.peek() == "D") {Ð         stream.eat(/[D]/);Ð
          style = "keyword c";Ð         state.define = true;Ð       }Ð
stream.eatWhile(/[A-Z]/i);Ð       return style;Ð     }Ð     var ch =
stream.peek();Ð     if (state.inString == false && ch == "'") {Ð
state.inString = true;Ð       ch = stream.next();Ð     }Ð     if
(state.inString == true) {Ð       if (stream.skipTo("'")) {Ð       } else {Ð
          stream.skipToEnd();Ð       }Ð       if (stream.peek() == "'") {Ð
          stream.next();Ð         state.inString = false;Ð       }Ð
return "string";Ð     }Ð     stream.next();Ð     return null;Ð   },Ð
lineComment: "#"Ð };Þ);ÐodeMirror.defineMIME("text/x-hxml", "hxml");Þ);Ð
```

public\assets\js\plugins\codemirror\mode\htmlembedded\htmlembedded.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../htmlmixed/htmlmixed"));Ð
else if (typeof define == "function" && define.amd) // AMD Ð   define(["../../
lib/codemirror", "../htmlmixed/htmlmixed"], mod);Ð else // Plain browser env Ð
    mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("htmlembedded", function(config, parserConfig) {Ð //
config settings Ð var scriptStartRegex = parserConfig.scriptStartRegex || /^<%/
i,Ð     scriptEndRegex = parserConfig.scriptEndRegex || /^%>/i;Ð //inner modes Ð
  var scriptingMode, htmlMixedMode;Ð //tokenizer when in html mode Ð function
htmlDispatch(stream, state) {Ð     if (stream.match(scriptStartRegex, false))
{Ð         state.token=scriptingDispatch;Ð         return
scriptingMode.token(stream, state.scriptState);Ð         }Ð     elseÐ
return htmlMixedMode.token(stream, state.htmlState);Ð   }Ð //tokenizer when
in scripting mode Ð function scriptingDispatch(stream, state) {Ð     if
(stream.match(scriptEndRegex, false))  {Ð         state.token=htmlDispatch;Ð
          return htmlMixedMode.token(stream, state.htmlState);Ð        }Ð
elseÐ         return scriptingMode.token(stream, state.scriptState);Ð        }Ð
  return {Ð   startState: function() {Ð     scriptingMode = scriptingMode ||
CodeMirror.getMode(config, parserConfig.scriptingModeSpec);Ð
htmlMixedMode = htmlMixedMode || CodeMirror.getMode(config, "htmlmixed");Ð
      return {Ð         token :  parserConfig.startOpen ? scriptingDispatch :
htmlDispatch,Ð         htmlState : CodeMirror.startState(htmlMixedMode),Ð
          scriptState : CodeMirror.startState(scriptingMode)Ð     };Ð   },Ð
token: function(stream, state) {Ð     return state.token(stream, state);Ð   },Ð
    indent: function(state, textAfter) {Ð     if (state.token == htmlDispatch)Ð
        return htmlMixedMode.indent(state.htmlState, textAfter);Ð     else if
(scriptingMode.indent)Ð       return scriptingMode.indent(state.scriptState,
textAfter);Ð   },Ð   copyState: function(state) {Ð     return {Ð      token :
state.token,Ð      htmlState : CodeMirror.copyState(htmlMixedMode,
state.htmlState),Ð      scriptState : CodeMirror.copyState(scriptingMode,
state.scriptState)Ð     };Ð   },Ð   innerMode: function(state) {Ð     if
(state.token == scriptingDispatch) return {state: state.scriptState, mode:
scriptingMode};Ð     else return {state: state.htmlState, mode:
htmlMixedMode};Ð   }Ð };Ð, "htmlmixed");ÐodeMirror.defineMIME("application/x-
ejs", { name: "htmlembedded", scriptingModeSpec:"javascript"});Ð
CodeMirror.defineMIME("application/x-aspx", { name: "htmlembedded",
scriptingModeSpec:"text/x-csharp"});ÐodeMirror.defineMIME("application/x-
jsp", { name: "htmlembedded", scriptingModeSpec:"text/x-java"});Ð
CodeMirror.defineMIME("application/x-erb", { name: "htmlembedded",
scriptingModeSpec:"ruby"});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\htmlmixed\htmlmixed.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../xml/xml"), require("../
javascript/javascript"), require("../css/css"));Ð else if (typeof define ==
"function" && define.amd) // AMD Ð   define(["../../lib/codemirror", "../xml/
xml", "../javascript/javascript", "../css/css"], mod);Ð else // Plain browser
env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("htmlmixed", function(config, parserConfig) {Ð var
htmlMode = CodeMirror.getMode(config, {name: "xml",Ð
                                          htmlMode: true,Ð
                                          multilineTagIndentFactor:
parserConfig.multilineTagIndentFactor,Ð
                                          multilineTagIndentPastTag:
parserConfig.multilineTagIndentPastTag});Ð var cssMode =
CodeMirror.getMode(config, "css");Ð var scriptTypes = [], scriptTypesConf =
parserConfig && parserConfig.scriptTypes;Ð scriptTypes.push({matches: /
^(?:text|application)\/(?:x-)?(?:java|ecma)script$|^$/i,Ð
mode: CodeMirror.getMode(config, "javascript")});Ð if (scriptTypesConf) for
(var i = 0; i < scriptTypesConf.length; ++i) {Ð   var conf =
scriptTypesConf[i];Ð   scriptTypes.push({matches: conf.matches, mode:
conf.mode && CodeMirror.getMode(config, conf.mode)});Ð }Ð
scriptTypes.push({matches: /./,Ð                    mode:
CodeMirror.getMode(config, "text/plain")});Ð function html(stream, state) {Ð
    var tagName = state.htmlState.tagName;Ð   if (tagName) tagName =
tagName.toLowerCase();Ð   var style = htmlMode.token(stream, state.htmlState);Ð
    if (tagName == "script" && /\btag\b/.test(style) && stream.current() ==
">") {Ð     // Script block: mode to change to depends on type attribute Ð
var scriptType = stream.string.slice(Math.max(0, stream.pos - 100),
stream.pos).match(/\btype\s*=\s*("[^"]+"|'[^']+'|\S+)[^<]*$/i);Ð
scriptType = scriptType ? scriptType[1] : "";Ð     if (scriptType && /
[\"\']/.test(scriptType.charAt(0))) scriptType = scriptType.slice(1,
scriptType.length - 1);Ð     for (var i = 0; i < scriptTypes.length; ++i) {Ð
        var tp = scriptTypes[i];Ð       if (typeof tp.matches == "string" ?
scriptType == tp.matches : tp.matches.test(scriptType)) {Ð         if
(tp.mode) {Ð           state.token = script;Ð           state.localMode =
tp.mode;Ð           state.localState = tp.mode.startState &&
tp.mode.startState(htmlMode.indent(state.htmlState, ""));Ð         }Ð
break;Ð       }Ð     }Ð   } else if (tagName == "style" && /
\btag\b/.test(style) && stream.current() == ">") {Ð     state.token = css;Ð
      state.localMode = cssMode;Ð     state.localState =
cssMode.startState(htmlMode.indent(state.htmlState, ""));Ð   }Ð   return
style;Ð }Ð function maybeBackup(stream, pat, style) {Ð   var cur =
stream.current();Ð   var close = cur.search(pat), m;Ð   if (close > -1)
stream.backUp(cur.length - close);Ð   else if (m = cur.match(/<\/?$/)) {Ð
stream.backUp(cur.length);Ð     if (!stream.match(pat, false))
stream.match(cur);Ð   }Ð   return style;Ð }Ð function script(stream, state) {Ð
    if (stream.match(/^<\/\s*script\s*>/i, false)) {Ð     state.token = html;Ð
      state.localState = state.localMode = null;Ð     return html(stream,
state);Ð   }Ð   return maybeBackup(stream, /<\/\s*script\s*>/,Ð
                       state.localMode.token(stream, state.localState));Ð }Ð
function css(stream, state) {Ð   if (stream.match(/^<\/\s*style\s*>/i,
false)) {Ð     state.token = html;Ð     state.localState = state.localMode =
null;Ð     return html(stream, state);Ð   }Ð   return maybeBackup(stream, /<\/
\s*style\s*>/,Ð                       cssMode.token(stream, state.localState));Ð
  }Ð return {Ð   startState: function() {Ð     var state =
htmlMode.startState();Ð     return {token: html, localMode: null, localState:
null, htmlState: state};Ð   },Ð   copyState: function(state) {Ð     if
(state.localState)Ð
```

```
                          var local = CodeMirror.copyState(state.localMode,
state.localState);Ð     return {token: state.token, localMode:
state.localMode, localState: local,Ð             htmlState:
CodeMirror.copyState(htmlMode, state.htmlState)};Ð   },Ð   token:
function(stream, state) {Ð     return state.token(stream, state);Ð   },Ð
indent: function(state, textAfter) {Ð     if (!state.localMode || /
^\s*<\//.test(textAfter))Ð       return htmlMode.indent(state.htmlState,
textAfter);Ð     else if (state.localMode.indent)Ð       return
state.localMode.indent(state.localState, textAfter);Ð     elseÐ       return
CodeMirror.Pass;Ð   },Ð   innerMode: function(state) {Ð     return {state:
state.localState || state.htmlState, mode: state.localMode || htmlMode};Ð   }Ð
  };Ð, "xml", "javascript", "css");ÐodeMirror.defineMIME("text/html",
"htmlmixed");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\http\http.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("http", function() {Ð function failFirstLine(stream,
state) {Ð   stream.skipToEnd();Ð   state.cur = header;Ð   return "error";Ð }Ð
function start(stream, state) {Ð   if (stream.match(/^HTTP\/\d\.\d/)) {Ð
state.cur = responseStatusCode;Ð     return "keyword";Ð   } else if
(stream.match(/^[A-Z]+/) && /[ \t]/.test(stream.peek())) {Ð     state.cur =
requestPath;Ð     return "keyword";Ð   } else {Ð     return
failFirstLine(stream, state);Ð   }Ð }Ð function responseStatusCode(stream,
state) {Ð   var code = stream.match(/^\d+/);Ð   if (!code) return
failFirstLine(stream, state);Ð   state.cur = responseStatusText;Ð   var
status = Number(code[0]);Ð   if (status >= 100 && status < 200) {Ð     return
"positive informational";Ð   } else if (status >= 200 && status < 300) {Ð
return "positive success";Ð   } else if (status >= 300 && status < 400) {Ð
      return "positive redirect";Ð   } else if (status >= 400 && status <
500) {Ð     return "negative client-error";Ð   } else if (status >= 500 &&
status < 600) {Ð     return "negative server-error";Ð   } else {Ð     return
"error";Ð   }Ð }Ð function responseStatusText(stream, state) {Ð
stream.skipToEnd();Ð   state.cur = header;Ð   return null;Ð }Ð function
requestPath(stream, state) {Ð   stream.eatWhile(/\S/);Ð   state.cur =
requestProtocol;Ð   return "string-2";Ð }Ð function requestProtocol(stream,
state) {Ð   if (stream.match(/^HTTP\/\d\.\d$/)) {Ð     state.cur = header;Ð
      return "keyword";Ð   } else {Ð     return failFirstLine(stream, state);Ð
    }Ð }Ð function header(stream) {Ð   if (stream.sol() && !stream.eat(/
[ \t]/)) {Ð     if (stream.match(/^.*?:/)) {Ð       return "atom";Ð     }
else {Ð       stream.skipToEnd();Ð       return "error";Ð     }Ð   } else {Ð
      stream.skipToEnd();Ð     return "string";Ð   }Ð }Ð function
body(stream) {Ð   stream.skipToEnd();Ð   return null;Ð }Ð return {Ð   token:
function(stream, state) {Ð     var cur = state.cur;Ð     if (cur != header &&
cur != body && stream.eatSpace()) return null;Ð     return cur(stream, state);Ð
    },Ð   blankLine: function(state) {Ð     state.cur = body;Ð   },Ð
startState: function() {Ð     return {cur: start};Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("message/http", "http");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\jade\jade.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../javascript/javascript"),
require("../css/css"), require("../htmlmixed/htmlmixed"));Ð else if (typeof
define == "function" && define.amd) // AMD Ð   define(["../../lib/codemirror",
"../javascript/javascript", "../css/css", "../htmlmixed/htmlmixed"], mod);Ð
else // Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð use
strict";Ð CodeMirror.defineMode('jade', function (config) {Ð // token types Ð
var KEYWORD = 'keyword';Ð var DOCTYPE = 'meta';Ð var ID = 'builtin';Ð var
CLASS = 'qualifier';Ð var ATTRS_NEST = {Ð   '{': '}',Ð   '(': ')',Ð   '[': ']'Ð
  };Ð var jsMode = CodeMirror.getMode(config, 'javascript');Ð function
State() {Ð   this.javaScriptLine = false;Ð   this.javaScriptLineExcludesColon
= false;Ð   this.javaScriptArguments = false;Ð
this.javaScriptArgumentsDepth = 0;Ð   this.isInterpolating = false;Ð
this.interpolationNesting = 0;Ð   this.jsState = jsMode.startState();Ð
this.restOfLine = '';Ð   this.isIncludeFiltered = false;Ð   this.isEach =
false;Ð   this.lastTag = '';Ð   this.scriptType = '';Ð   // Attributes Mode Ð
    this.isAttrs = false;Ð   this.attrsNest = [];Ð   this.inAttributeName =
true;Ð   this.attributeIsType = false;Ð   this.attrValue = '';Ð   // Indented
Mode Ð   this.indentOf = Infinity;Ð   this.indentToken = '';Ð   this.innerMode
= null;Ð   this.innerState = null;Ð   this.innerModeForLine = false;Ð }Ð /**Ð
   * Safely copy a state Ð  *Ð  * @return {State}Ð  */Ð State.prototype.copy =
function () {Ð   var res = new State();Ð   res.javaScriptLine =
this.javaScriptLine;Ð   res.javaScriptLineExcludesColon =
this.javaScriptLineExcludesColon;Ð   res.javaScriptArguments =
this.javaScriptArguments;Ð   res.javaScriptArgumentsDepth =
this.javaScriptArgumentsDepth;Ð   res.isInterpolating = this.isInterpolating;Ð
    res.interpolationNesting = this.intpolationNesting;Ð   res.jsState =
CodeMirror.copyState(jsMode, this.jsState);Ð   res.innerMode = this.innerMode;Ð
    if (this.innerMode && this.innerState) {Ð     res.innerState =
CodeMirror.copyState(this.innerMode, this.innerState);Ð   }Ð   res.restOfLine
= this.restOfLine;Ð   res.isIncludeFiltered = this.isIncludeFiltered;Ð
res.isEach = this.isEach;Ð   res.lastTag = this.lastTag;Ð   res.scriptType =
this.scriptType;Ð   res.isAttrs = this.isAttrs;Ð   res.attrsNest =
this.attrsNest.slice();Ð   res.inAttributeName = this.inAttributeName;Ð
res.attributeIsType = this.attributeIsType;Ð   res.attrValue = this.attrValue;Ð
    res.indentOf = this.indentOf;Ð   res.indentToken = this.indentToken;Ð
res.innerModeForLine = this.innerModeForLine;Ð   return res;Ð };Ð function
javaScript(stream, state) {Ð   if (stream.sol()) {Ð     // if javaScriptLine
was set at end of line, ignore it Ð     state.javaScriptLine = false;Ð
state.javaScriptLineExcludesColon = false;Ð   }Ð   if (state.javaScriptLine) {Ð
      if (state.javaScriptLineExcludesColon && stream.peek() === ':') {Ð
        state.javaScriptLine = false;Ð
state.javaScriptLineExcludesColon = false;Ð       return;Ð     }Ð     var tok
= jsMode.token(stream, state.jsState);Ð     if (stream.eol())
state.javaScriptLine = false;Ð     return tok || true;Ð   }Ð }Ð function
javaScriptArguments(stream, state) {Ð   if (state.javaScriptArguments) {Ð
if (state.javaScriptArgumentsDepth === 0 && stream.peek() !== '(') {Ð
state.javaScriptArguments = false;Ð       return;Ð     }Ð     if
(stream.peek() === '(') {Ð       state.javaScriptArgumentsDepth++;Ð     }
else if (stream.peek() === ')') {Ð       state.javaScriptArgumentsDepth--;Ð
      }Ð     if (state.javaScriptArgumentsDepth === 0) {Ð
state.javaScriptArguments = false;Ð       return;Ð     }Ð     var tok =
jsMode.token(stream, state.jsState);Ð     return tok || true;Ð   }Ð }Ð
function yieldStatement(stream) {Ð   if (stream.match(/^yield\b/)) {Ð
return 'keyword';Ð   }Ð }Ð function doctype(stream) {Ð   if (stream.match(/
^(?:doctype) *([^\n]+)?/)) {Ð       return DOCTYPE;Ð   }Ð }Ð function
interpolation(stream, state) {Ð
```

```
                                    if (stream.match('#{')) {Ð
state.isInterpolating = true;Ð     state.interpolationNesting = 0;Ð
return 'punctuation';Ð   }Ð }Ð function interpolationContinued(stream, state)
{Ð   if (state.isInterpolating) {Ð     if (stream.peek() === '}') {Ð
state.interpolationNesting--;Ð       if (state.interpolationNesting < 0) {Ð
          stream.next();Ð         state.isInterpolating = false;Ð
return 'puncutation';Ð       }Ð     } else if (stream.peek() === '{') {Ð
        state.interpolationNesting++;Ð     }Ð     return jsMode.token(stream,
state.jsState) || true;Ð   }Ð }Ð function caseStatement(stream, state) {Ð
if (stream.match(/^case\b/)) {Ð     state.javaScriptLine = true;Ð     return
KEYWORD;Ð   }Ð }Ð function when(stream, state) {Ð   if (stream.match(/
^when\b/)) {Ð     state.javaScriptLine = true;Ð
state.javaScriptLineExcludesColon = true;Ð     return KEYWORD;Ð   }Ð }Ð
function defaultStatement(stream) {Ð   if (stream.match(/^default\b/)) {Ð
return KEYWORD;Ð   }Ð }Ð function extendsStatement(stream, state) {Ð   if
(stream.match(/^extends?\b/)) {Ð     state.restOfLine = 'string';Ð     return
KEYWORD;Ð   }Ð }Ð function append(stream, state) {Ð   if (stream.match(/
^append\b/)) {Ð     state.restOfLine = 'variable';Ð     return KEYWORD;Ð   }Ð
  }Ð function prepend(stream, state) {Ð   if (stream.match(/^prepend\b/)) {Ð
      state.restOfLine = 'variable';Ð     return KEYWORD;Ð   }Ð }Ð function
block(stream, state) {Ð   if (stream.match(/^block\b *(?:(prepend|
append)\b)?/)) {Ð     state.restOfLine = 'variable';Ð     return KEYWORD;Ð   }Ð
  }Ð function include(stream, state) {Ð   if (stream.match(/^include\b/)) {Ð
      state.restOfLine = 'string';Ð     return KEYWORD;Ð   }Ð }Ð function
includeFiltered(stream, state) {Ð   if (stream.match(/^include:([a-zA-
Z0-9\-]+)/, false) && stream.match('include')) {Ð     state.isIncludeFiltered
= true;Ð     return KEYWORD;Ð   }Ð }Ð function
includeFilteredContinued(stream, state) {Ð   if (state.isIncludeFiltered) {Ð
      var tok = filter(stream, state);Ð     state.isIncludeFiltered = false;Ð
      state.restOfLine = 'string';Ð     return tok;Ð   }Ð }Ð function
mixin(stream, state) {Ð   if (stream.match(/^mixin\b/)) {Ð
state.javaScriptLine = true;Ð     return KEYWORD;Ð   }Ð }Ð function
call(stream, state) {Ð   if (stream.match(/^\+([-\w]+)/)) {Ð     if (!
stream.match(/^\( *[-\w]+ *=/, false)) {Ð       state.javaScriptArguments =
true;Ð       state.javaScriptArgumentsDepth = 0;Ð     }Ð     return
'variable';Ð   }Ð   if (stream.match(/^\+#{/, false)) {Ð     stream.next();Ð
      state.mixinCallAfter = true;Ð     return interpolation(stream, state);Ð
    }Ð }Ð function callArguments(stream, state) {Ð   if
(state.mixinCallAfter) {Ð     state.mixinCallAfter = false;Ð     if (!
stream.match(/^\( *[-\w]+ *=/, false)) {Ð       state.javaScriptArguments =
true;Ð       state.javaScriptArgumentsDepth = 0;Ð     }Ð     return true;Ð   }Ð
  }Ð function conditional(stream, state) {Ð   if (stream.match(/^(if|unless|
else if|else)\b/)) {Ð     state.javaScriptLine = true;Ð     return KEYWORD;Ð
    }Ð }Ð function each(stream, state) {Ð   if (stream.match(/^(- *)?(each|
for)\b/)) {Ð     state.isEach = true;Ð     return KEYWORD;Ð   }Ð }Ð function
eachContinued(stream, state) {Ð   if (state.isEach) {Ð     if (stream.match(/
^ in\b/)) {Ð       state.javaScriptLine = true;Ð       state.isEach = false;Ð
        return KEYWORD;Ð     } else if (stream.sol() || stream.eol()) {Ð
        state.isEach = false;Ð     } else if (stream.next()) {Ð       while (!
stream.match(/^ in\b/, false) && stream.next());Ð       return 'variable';Ð
      }Ð   }Ð }Ð function whileStatement(stream, state) {Ð   if
(stream.match(/^while\b/)) {Ð     state.javaScriptLine = true;Ð     return
KEYWORD;Ð   }Ð }Ð function tag(stream, state) {Ð   var captures;Ð   if
(captures = stream.match(/^(\w(?:[-:\w]*\w)?)\/?/)) {Ð     state.lastTag =
captures[1].toLowerCase();Ð     if (state.lastTag === 'script') {Ð
state.scriptType = 'application/javascript';Ð     }Ð     return 'tag';Ð   }Ð }Ð
  function filter(stream, state) {Ð   if (stream.match(/^:([\w\-]+)/)) {Ð
var innerMode;Ð     if (config && config.innerModes) {Ð       innerMode =
config.innerModes(stream.current().substring(1));Ð     }Ð     if (!innerMode)
{Ð
```

```
        innerMode = stream.current().substring(1);Ð     }Ð     if (typeof
innerMode === 'string') {Ð       innerMode = CodeMirror.getMode(config,
innerMode);Ð     }Ð     setInnerMode(stream, state, innerMode);Ð     return
'atom';Ð   }Ð }Ð function code(stream, state) {Ð   if (stream.match(/^(!?
=|-)/)) {Ð     state.javaScriptLine = true;Ð     return 'punctuation';Ð   }Ð }Ð
  function id(stream) {Ð   if (stream.match(/^#([\w-]+)/)) {Ð     return ID;Ð
    }Ð }Ð function className(stream) {Ð   if (stream.match(/^\.([\w-]+)/)) {Ð
      return CLASS;Ð   }Ð }Ð function attrs(stream, state) {Ð   if
(stream.peek() == '(') {Ð     stream.next();Ð     state.isAttrs = true;Ð
state.attrsNest = [];Ð     state.inAttributeName = true;Ð     state.attrValue
= '';Ð     state.attributeIsType = false;Ð     return 'punctuation';Ð   }Ð }Ð
function attrsContinued(stream, state) {Ð   if (state.isAttrs) {Ð     if
(ATTRS_NEST[stream.peek()]) {Ð
state.attrsNest.push(ATTRS_NEST[stream.peek()]);Ð     }Ð     if
(state.attrsNest[state.attrsNest.length - 1] === stream.peek()) {Ð
state.attrsNest.pop();Ð     } else  if (stream.eat(')')) {Ð
state.isAttrs = false;Ð       return 'punctuation';Ð     }Ð     if
(state.inAttributeName && stream.match(/^[^=,\)!]+/)) {Ð       if
(stream.peek() === '=' || stream.peek() === '!') {Ð
state.inAttributeName = false;Ð         state.jsState = jsMode.startState();Ð
          if (state.lastTag === 'script' &&
stream.current().trim().toLowerCase() === 'type') {Ð
state.attributeIsType = true;Ð         } else {Ð
state.attributeIsType = false;Ð         }Ð       }Ð       return 'attribute';Ð
      }Ð     var tok = jsMode.token(stream, state.jsState);Ð     if
(state.attributeIsType && tok === 'string') {Ð       state.scriptType =
stream.current().toString();Ð     }Ð     if (state.attrsNest.length === 0 &&
(tok === 'string' || tok === 'variable' || tok === 'keyword')) {Ð       try {Ð
          Function('', 'var x ' + state.attrValue.replace(/,\s*$/,
'').replace(/^!/, ''));Ð         state.inAttributeName = true;Ð
state.attrValue = '';Ð         stream.backUp(stream.current().length);Ð
          return attrsContinued(stream, state);Ð       } catch (ex) {Ð
          //not the end of an attributeÐ       }Ð     }Ð     state.attrValue
+= stream.current();Ð     return tok || true;Ð   }Ð }Ð function
attributesBlock(stream, state) {Ð   if (stream.match(/^&attributes\b/)) {Ð
      state.javaScriptArguments = true;Ð     state.javaScriptArgumentsDepth =
0;Ð     return 'keyword';Ð   }Ð }Ð function indent(stream) {Ð   if
(stream.sol() && stream.eatSpace()) {Ð     return 'indent';Ð   }Ð }Ð function
comment(stream, state) {Ð   if (stream.match(/^ *\/\/(-)?([^\n]*)/)) {Ð
state.indentOf = stream.indentation();Ð     state.indentToken = 'comment';Ð
      return 'comment';Ð   }Ð }Ð function colon(stream) {Ð   if
(stream.match(/^: */)) {Ð     return 'colon';Ð   }Ð }Ð function text(stream,
state) {Ð   if (stream.match(/^(?:\| ?| )([^\n]+)/)) {Ð     return 'string';Ð
    }Ð   if (stream.match(/^(<[^\n]*)/, false)) {Ð     // html stringÐ
setInnerMode(stream, state, 'htmlmixed');Ð     state.innerModeForLine = true;Ð
      return innerMode(stream, state, true);Ð   }Ð }Ð function dot(stream,
state) {Ð   if (stream.eat('.')) {Ð     var innerMode = null;Ð     if
(state.lastTag === 'script' &&
state.scriptType.toLowerCase().indexOf('javascript') != -1) {Ð
innerMode = state.scriptType.toLowerCase().replace(/"|'/g, '');Ð     } else
if (state.lastTag === 'style') {Ð       innerMode = 'css';Ð     }Ð
setInnerMode(stream, state, innerMode);Ð     return 'dot';Ð   }Ð }Ð function
fail(stream) {Ð   stream.next();Ð   return null;Ð }Ð function
setInnerMode(stream, state, mode) {Ð   mode = CodeMirror.mimeModes[mode] ||
mode;Ð   mode = config.innerModes ? config.innerModes(mode) || mode : mode;Ð
    mode = CodeMirror.mimeModes[mode] || mode;Ð   mode =
CodeMirror.getMode(config, mode);Ð   state.indentOf = stream.indentation();Ð
    if (mode && mode.name !== 'null') {Ð     state.innerMode = mode;Ð   }
else {Ð     state.indentToken = 'string';Ð   }Ð }Ð function innerMode(stream,
state, force) {Ð
```

```
                    if (stream.indentation() > state.indentOf ||
(state.innerModeForLine && !stream.sol()) || force) {Ð     if
(state.innerMode) {Ð       if (!state.innerState) {Ð         state.innerState
= state.innerMode.startState ?
state.innerMode.startState(stream.indentation()) : {};Ð       }Ð       return
stream.hideFirstChars(state.indentOf + 2, function () {Ð         return
state.innerMode.token(stream, state.innerState) || true;Ð       });Ð     }
else {Ð       stream.skipToEnd();Ð       return state.indentToken;Ð     }Ð
    } else if (stream.sol()) {Ð     state.indentOf = Infinity;Ð
state.indentToken = null;Ð     state.innerMode = null;Ð     state.innerState
= null;Ð   }Ð }Ð function restOfLine(stream, state) {Ð   if (stream.sol()) {Ð
      // if restOfLine was set at end of line, ignore itÐ
state.restOfLine = '';Ð   }Ð   if (state.restOfLine) {Ð
stream.skipToEnd();Ð     var tok = state.restOfLine;Ð     state.restOfLine =
'';Ð     return tok;Ð   }Ð }Ð function startState() {Ð   return new State();Ð
  }Ð function copyState(state) {Ð   return state.copy();Ð }Ð /**Ð  * Get the
next token in the streamÐ  *Ð  * @param {Stream} streamÐ  * @param {State}
stateÐ  */Ð function nextToken(stream, state) {Ð   var tok =
innerMode(stream, state)Ð     || restOfLine(stream, state)Ð     ||
interpolationContinued(stream, state)Ð     ||
includeFilteredContinued(stream, state)Ð     || eachContinued(stream, state)Ð
      || attrsContinued(stream, state)Ð     || javaScript(stream, state)Ð
|| javaScriptArguments(stream, state)Ð     || callArguments(stream, state)Ð
      || yieldStatement(stream, state)Ð     || doctype(stream, state)Ð     ||
interpolation(stream, state)Ð     || caseStatement(stream, state)Ð     ||
when(stream, state)Ð     || defaultStatement(stream, state)Ð     ||
extendsStatement(stream, state)Ð     || append(stream, state)Ð     ||
prepend(stream, state)Ð     || block(stream, state)Ð     || include(stream,
state)Ð     || includeFiltered(stream, state)Ð     || mixin(stream, state)Ð
      || call(stream, state)Ð     || conditional(stream, state)Ð     ||
each(stream, state)Ð     || whileStatement(stream, state)Ð     || tag(stream,
state)Ð     || filter(stream, state)Ð     || code(stream, state)Ð     ||
id(stream, state)Ð     || className(stream, state)Ð     || attrs(stream,
state)Ð     || attributesBlock(stream, state)Ð     || indent(stream, state)Ð
      || text(stream, state)Ð     || comment(stream, state)Ð     ||
colon(stream, state)Ð     || dot(stream, state)Ð     || fail(stream, state);Ð
    return tok === true ? null : tok;Ð }Ð return {Ð   startState: startState,Ð
    copyState: copyState,Ð   token: nextTokenÐ };Ð});Ð
CodeMirror.defineMIME('text/x-jade', 'jade');Ð});Ð
```

public\assets\js\plugins\codemirror\mode\javascript\javascript.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and othersÐ// Distributed
under an MIT license: http://codemirror.net/LICENSEÐ// TODO actually recognize
syntax of TypeScript constructsÐfunction(mod) {Ð if (typeof exports ==
"object" && typeof module == "object") // CommonJSÐ   mod(require("../../lib/
codemirror"));Ð else if (typeof define == "function" && define.amd) // AMDÐ
define(["../../lib/codemirror"], mod);Ð else // Plain browser envÐ
mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("javascript", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit;Ð var statementIndent =
parserConfig.statementIndent;Ð var jsonldMode = parserConfig.jsonld;Ð var
jsonMode = parserConfig.json || jsonldMode;Ð var isTS =
parserConfig.typescript;Ð var wordRE = parserConfig.wordCharacters || /[\w$
\xa1-\uffff]/;Ð // TokenizerÐ var keywords = function(){Ð   function kw(type)
{return {type: type, style: "keyword"};}Ð   var A = kw("keyword a"), B =
kw("keyword b"), C = kw("keyword c");Ð   var operator = kw("operator"), atom
= {type: "atom", style: "atom"};Ð   var jsKeywords = {Ð     "if": kw("if"),
"while": A, "with": A, "else": B, "do": B, "try": B, "finally": B,Ð
"return": C, "break": C, "continue": C, "new": C, "delete": C, "throw": C,
"debugger": C,Ð     "var": kw("var"), "const": kw("var"), "let": kw("var"),Ð
      "function": kw("function"), "catch": kw("catch"),Ð     "for":
kw("for"), "switch": kw("switch"), "case": kw("case"), "default":
kw("default"),Ð     "in": operator, "typeof": operator, "instanceof":
operator,Ð     "true": atom, "false": atom, "null": atom, "undefined": atom,
"NaN": atom, "Infinity": atom,Ð     "this": kw("this"), "module":
kw("module"), "class": kw("class"), "super": kw("atom"),Ð     "yield": C,
"export": kw("export"), "import": kw("import"), "extends": CÐ   };Ð   //
Extend the 'normal' keywords with the TypeScript language extensionsÐ   if
(isTS) {Ð     var type = {type: "variable", style: "variable-3"};Ð     var
tsKeywords = {Ð       // object-like thingsÐ       "interface":
kw("interface"),Ð       "extends": kw("extends"),Ð       "constructor":
kw("constructor"),Ð       // scope modifiersÐ       "public": kw("public"),Ð
        "private": kw("private"),Ð       "protected": kw("protected"),Ð
"static": kw("static"),Ð       // typesÐ       "string": type, "number":
type, "bool": type, "any": typeÐ     };Ð     for (var attr in tsKeywords) {Ð
        jsKeywords[attr] = tsKeywords[attr];Ð     }Ð   }Ð   return jsKeywords;Ð
  }();Ð var isOperatorChar = /[+\-*&%=<>!?|~^]/;Ð var isJsonldKeyword = /
^@(context|id|value|language|type|container|list|set|reverse|index|base|vocab|
graph)"/;Ð function readRegexp(stream) {Ð   var escaped = false, next, inSet
= false;Ð   while ((next = stream.next()) != null) {Ð     if (!escaped) {Ð
        if (next == "/" && !inSet) return;Ð       if (next == "[") inSet =
true;Ð       else if (inSet && next == "]") inSet = false;Ð     }Ð
escaped = !escaped && next == "\\";Ð   }Ð }Ð // Used as scratch variables to
communicate multiple values withoutÐ // consing up tons of objects.Ð var
type, content;Ð function ret(tp, style, cont) {Ð   type = tp; content = cont;Ð
    return style;Ð }Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (ch == '"' || ch == "'") {Ð     state.tokenize =
tokenString(ch);Ð     return state.tokenize(stream, state);Ð   } else if (ch
== "." && stream.match(/^\d+(?:[eE][+\-]?\d+)?/)) {Ð     return ret("number",
"number");Ð   } else if (ch == "." && stream.match("..")) {Ð     return
ret("spread", "meta");Ð   } else if (/[\[\]{}\(\),;\:\.]/.test(ch)) {Ð
return ret(ch);Ð   } else if (ch == "=" && stream.eat(">")) {Ð     return
ret("=>", "operator");Ð   } else if (ch == "0" && stream.eat(/x/i)) {Ð
stream.eatWhile(/[\da-f]/i);Ð     return ret("number", "number");Ð   } else
if (/\d/.test(ch)) {Ð     stream.match(/^\d*(?:\.\d*)?(?:[eE][+\-]?\d+)?/);Ð
      return ret("number", "number");Ð   } else if (ch == "/") {Ð     if
(stream.eat("*")) {Ð       state.tokenize = tokenComment;Ð       return
tokenComment(stream, state);Ð     } else if (stream.eat("/")) {Ð
stream.skipToEnd();Ð       return ret("comment", "comment");Ð     } else if
(state.lastType == "operator" || state.lastType == "keyword c" ||Ð
```

```
                state.lastType == "sof" || /
^[\[{}\(,;:]$/.test(state.lastType)) {Ð       readRegexp(stream);Ð
stream.eatWhile(/[gimy]/); // 'y' is "sticky" option in MozillaÐ       return
ret("regexp", "string-2");Ð     } else {Ð
stream.eatWhile(isOperatorChar);Ð       return ret("operator", "operator",
stream.current());Ð     }Ð   } else if (ch == "`") {Ð     state.tokenize =
tokenQuasi;Ð     return tokenQuasi(stream, state);Ð   } else if (ch == "#") {Ð
      stream.skipToEnd();Ð     return ret("error", "error");Ð   } else if
(isOperatorChar.test(ch)) {Ð     stream.eatWhile(isOperatorChar);Ð     return
ret("operator", "operator", stream.current());Ð   } else if (wordRE.test(ch))
{Ð     stream.eatWhile(wordRE);Ð     var word = stream.current(), known =
keywords.propertyIsEnumerable(word) && keywords[word];Ð     return (known &&
state.lastType != ".") ? ret(known.type, known.style, word) :Ð
                      ret("variable", "variable", word);Ð   }Ð }Ð function
tokenString(quote) {Ð   return function(stream, state) {Ð     var escaped =
false, next;Ð     if (jsonldMode && stream.peek() == "@" &&
stream.match(isJsonldKeyword)){Ð       state.tokenize = tokenBase;Ð
return ret("jsonld-keyword", "meta");Ð     }Ð     while ((next =
stream.next()) != null) {Ð       if (next == quote && !escaped) break;Ð
escaped = !escaped && next == "\\";Ð     }Ð     if (!escaped) state.tokenize
= tokenBase;Ð     return ret("string", "string");Ð   };Ð }Ð function
tokenComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while (ch =
stream.next()) {Ð     if (ch == "/" && maybeEnd) {Ð       state.tokenize =
tokenBase;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð   return
ret("comment", "comment");Ð }Ð function tokenQuasi(stream, state) {Ð   var
escaped = false, next;Ð   while ((next = stream.next()) != null) {Ð     if (!
escaped && (next == "`" || next == "$" && stream.eat("{"))) {Ð
state.tokenize = tokenBase;Ð       break;Ð     }Ð     escaped = !escaped &&
next == "\\";Ð   }Ð   return ret("quasi", "string-2", stream.current());Ð }Ð
var brackets = "([{}])";Ð // This is a crude lookahead trick to try and
notice that we'reÐ // parsing the argument patterns for a fat-arrow function
before weÐ // actually hit the arrow token. It only works if the arrow is onÐ
  // the same line as the arguments and there's no strange noiseÐ //
(comments) in between. Fallback is to only notice when we hit theÐ // arrow,
and not declare the arguments as locals for the arrowÐ // body.Ð function
findFatArrow(stream, state) {Ð   if (state.fatArrowAt) state.fatArrowAt =
null;Ð   var arrow = stream.string.indexOf("=>", stream.start);Ð   if (arrow
< 0) return;Ð   var depth = 0, sawSomething = false;Ð   for (var pos = arrow
- 1; pos >= 0; --pos) {Ð     var ch = stream.string.charAt(pos);Ð     var
bracket = brackets.indexOf(ch);Ð     if (bracket >= 0 && bracket < 3) {Ð
        if (!depth) { ++pos; break; }Ð       if (--depth == 0) break;Ð     }
else if (bracket >= 3 && bracket < 6) {Ð       ++depth;Ð     } else if
(wordRE.test(ch)) {Ð       sawSomething = true;Ð     } else if (sawSomething
&& !depth) {Ð       ++pos;Ð       break;Ð     }Ð   }Ð   if (sawSomething && !
depth) state.fatArrowAt = pos;Ð }Ð // ParserÐ var atomicTypes = {"atom":
true, "number": true, "variable": true, "string": true, "regexp": true,
"this": true, "jsonld-keyword": true};Ð function JSLexical(indented, column,
type, align, prev, info) {Ð   this.indented = indented;Ð   this.column =
column;Ð   this.type = type;Ð   this.prev = prev;Ð   this.info = info;Ð   if
(align != null) this.align = align;Ð }Ð function inScope(state, varname) {Ð
for (var v = state.localVars; v; v = v.next)Ð     if (v.name == varname)
return true;Ð   for (var cx = state.context; cx; cx = cx.prev) {Ð     for
(var v = cx.vars; v; v = v.next)Ð       if (v.name == varname) return true;Ð
    }Ð }Ð function parseJS(state, style, type, content, stream) {Ð   var cc =
state.cc;Ð   // Communicate our context to the combinators.Ð   // (Less
wasteful than consing up a hundred closures on every call.)Ð   cx.state =
state; cx.stream = stream; cx.marked = null, cx.cc = cc; cx.style = style;Ð
if (!state.lexical.hasOwnProperty("align"))Ð     state.lexical.align = true;Ð
    while(true) {Ð
```

var combinator = cc.length ? cc.pop() : jsonMode ? expression : statement;Ð if (combinator(type, content)) {Ð while(cc.length && cc[cc.length - 1].lex)Ð cc.pop()();Ð if (cx.marked) return cx.marked;Ð if (type == "variable" && inScope(state, content)) return "variable-2";Ð return style;Ð }Ð }Ð }Ð // Combinator utilsÐ var cx = {state: null, column: null, marked: null, cc: null};Ð function pass() {Ð for (var i = arguments.length - 1; i >= 0; i--) cx.cc.push(arguments[i]);Ð }Ð function cont() {Ð pass.apply(null, arguments);Ð return true;Ð }Ð function register(varname) {Ð function inList(list) {Ð for (var v = list; v; v = v.next)Ð if (v.name == varname) return true;Ð return false;Ð }Ð var state = cx.state;Ð if (state.context) {Ð cx.marked = "def";Ð if (inList(state.localVars)) return;Ð state.localVars = {name: varname, next: state.localVars};Ð } else {Ð if (inList(state.globalVars)) return;Ð if (parserConfig.globalVars)Ð state.globalVars = {name: varname, next: state.globalVars};Ð }Ð }Ð // CombinatorsÐ var defaultVars = {name: "this", next: {name: "arguments"}};Ð function pushcontext() {Ð cx.state.context = {prev: cx.state.context, vars: cx.state.localVars};Ð cx.state.localVars = defaultVars;Ð }Ð function popcontext() {Ð cx.state.localVars = cx.state.context.vars;Ð cx.state.context = cx.state.context.prev;Ð }Ð function pushlex(type, info) {Ð var result = function() {Ð var state = cx.state, indent = state.indented;Ð if (state.lexical.type == "stat") indent = state.lexical.indented;Ð else for (var outer = state.lexical; outer && outer.type == ")" && outer.align; outer = outer.prev)Ð indent = outer.indented;Ð state.lexical = new JSLexical(indent, cx.stream.column(), type, null, state.lexical, info);Ð };Ð result.lex = true;Ð return result;Ð }Ð function poplex() {Ð var state = cx.state;Ð if (state.lexical.prev) {Ð if (state.lexical.type == ")")Ð state.indented = state.lexical.indented;Ð state.lexical = state.lexical.prev;Ð }Ð }Ð poplex.lex = true;Ð function expect(wanted) {Ð function exp(type) {Ð if (type == wanted) return cont();Ð else if (wanted == ";") return pass();Ð else return cont(exp);Ð };Ð return exp;Ð }Ð function statement(type, value) {Ð if (type == "var") return cont(pushlex("vardef", value.length), vardef, expect(";"), poplex);Ð if (type == "keyword a") return cont(pushlex("form"), expression, statement, poplex);Ð if (type == "keyword b") return cont(pushlex("form"), statement, poplex);Ð if (type == "{") return cont(pushlex("}"), block, poplex);Ð if (type == ";") return cont();Ð if (type == "if") {Ð if (cx.state.lexical.info == "else" && cx.state.cc[cx.state.cc.length - 1] == poplex)Ð cx.state.cc.pop()();Ð return cont(pushlex("form"), expression, statement, poplex, maybeelse);Ð }Ð if (type == "function") return cont(functiondef);Ð if (type == "for") return cont(pushlex("form"), forspec, statement, poplex);Ð if (type == "variable") return cont(pushlex("stat"), maybelabel);Ð if (type == "switch") return cont(pushlex("form"), expression, pushlex("}", "switch"), expect("{"),Ð block, poplex, poplex);Ð if (type == "case") return cont(expression, expect(":"));Ð if (type == "default") return cont(expect(":"));Ð if (type == "catch") return cont(pushlex("form"), pushcontext, expect("("), funarg, expect(")"),Ð statement, poplex, popcontext);Ð if (type == "module") return cont(pushlex("form"), pushcontext, afterModule, popcontext, poplex);Ð if (type == "class") return cont(pushlex("form"), className, poplex);Ð if (type == "export") return cont(pushlex("form"), afterExport, poplex);Ð if (type == "import") return cont(pushlex("form"), afterImport, poplex);Ð return pass(pushlex("stat"), expression, expect(";"), poplex);Ð }Ð function expression(type) {Ð return expressionInner(type, false);Ð }Ð function expressionNoComma(type) {Ð return expressionInner(type, true);Ð }Ð function expressionInner(type, noComma) {Ð if (cx.state.fatArrowAt == cx.stream.start) {Ð var body = noComma ? arrowBodyNoComma : arrowBody;Ð

```
                                                if (type == "(") return
cont(pushcontext, pushlex(")"), commasep(pattern, ")"), poplex, expect("=>"),
body, popcontext);Ð     else if (type == "variable") return pass(pushcontext,
pattern, expect("=>"), body, popcontext);Ð   }Ð   var maybeop = noComma ?
maybeoperatorNoComma : maybeoperatorComma;Ð   if
(atomicTypes.hasOwnProperty(type)) return cont(maybeop);Ð   if (type ==
"function") return cont(functiondef, maybeop);Ð   if (type == "keyword c")
return cont(noComma ? maybeexpressionNoComma : maybeexpression);Ð   if (type
== "(") return cont(pushlex(")"), maybeexpression, comprehension,
expect(")"), poplex, maybeop);Ð   if (type == "operator" || type == "spread")
return cont(noComma ? expressionNoComma : expression);Ð   if (type == "[")
return cont(pushlex("]"), arrayLiteral, poplex, maybeop);Ð   if (type == "{")
return contCommasep(objprop, "}", null, maybeop);Ð   if (type == "quasi")
{ return pass(quasi, maybeop); }Ð   return cont();Ð }Ð function
maybeexpression(type) {Ð   if (type.match(/[;\}\)\],]/)) return pass();Ð
return pass(expression);Ð }Ð function maybeexpressionNoComma(type) {Ð   if
(type.match(/[;\}\)\],]/)) return pass();Ð   return pass(expressionNoComma);Ð
  }Ð function maybeoperatorComma(type, value) {Ð   if (type == ",") return
cont(expression);Ð   return maybeoperatorNoComma(type, value, false);Ð }Ð
function maybeoperatorNoComma(type, value, noComma) {Ð   var me = noComma ==
false ? maybeoperatorComma : maybeoperatorNoComma;Ð   var expr = noComma ==
false ? expression : expressionNoComma;Ð   if (type == "=>") return
cont(pushcontext, noComma ? arrowBodyNoComma : arrowBody, popcontext);Ð   if
(type == "operator") {Ð     if (/\+\+|--/.test(value)) return cont(me);Ð
if (value == "?") return cont(expression, expect(":"), expr);Ð     return
cont(expr);Ð   }Ð   if (type == "quasi") { return pass(quasi, me); }Ð   if
(type == ";") return;Ð   if (type == "(") return
contCommasep(expressionNoComma, ")", "call", me);Ð   if (type == ".") return
cont(property, me);Ð   if (type == "[") return cont(pushlex("]"),
maybeexpression, expect("]"), poplex, me);Ð }Ð function quasi(type, value) {Ð
    if (type != "quasi") return pass();Ð   if (value.slice(value.length - 2) !
= "${") return cont(quasi);Ð   return cont(expression, continueQuasi);Ð }Ð
function continueQuasi(type) {Ð   if (type == "}") {Ð     cx.marked =
"string-2";Ð     cx.state.tokenize = tokenQuasi;Ð     return cont(quasi);Ð   }Ð
  }Ð function arrowBody(type) {Ð   findFatArrow(cx.stream, cx.state);Ð
return pass(type == "{" ? statement : expression);Ð }Ð function
arrowBodyNoComma(type) {Ð   findFatArrow(cx.stream, cx.state);Ð   return
pass(type == "{" ? statement : expressionNoComma);Ð }Ð function
maybelabel(type) {Ð   if (type == ":") return cont(poplex, statement);Ð
return pass(maybeoperatorComma, expect(";"), poplex);Ð }Ð function
property(type) {Ð   if (type == "variable") {cx.marked = "property"; return
cont();}Ð }Ð function objprop(type, value) {Ð   if (type == "variable" ||
cx.style == "keyword") {Ð     cx.marked = "property";Ð     if (value == "get"
|| value == "set") return cont(getterSetter);Ð     return cont(afterprop);Ð
    } else if (type == "number" || type == "string") {Ð     cx.marked =
jsonldMode ? "property" : (cx.style + " property");Ð     return
cont(afterprop);Ð   } else if (type == "jsonld-keyword") {Ð     return
cont(afterprop);Ð   } else if (type == "[") {Ð     return cont(expression,
expect("]"), afterprop);Ð   }Ð }Ð function getterSetter(type) {Ð   if (type !
= "variable") return pass(afterprop);Ð   cx.marked = "property";Ð   return
cont(functiondef);Ð }Ð function afterprop(type) {Ð   if (type == ":") return
cont(expressionNoComma);Ð   if (type == "(") return pass(functiondef);Ð }Ð
function commasep(what, end) {Ð   function proceed(type) {Ð     if (type ==
",") {Ð       var lex = cx.state.lexical;Ð       if (lex.info == "call")
lex.pos = (lex.pos || 0) + 1;Ð       return cont(what, proceed);Ð     }Ð
if (type == end) return cont();Ð     return cont(expect(end));Ð   }Ð   return
function(type) {Ð     if (type == end) return cont();Ð     return pass(what,
proceed);Ð   };Ð }Ð function contCommasep(what, end, info) {Ð   for (var i =
3; i < arguments.length; i++)Ð     cx.cc.push(arguments[i]);Ð   return
cont(pushlex(end, info), commasep(what, end), poplex);Ð
```

```
                                                        }Ð function
block(type) {Ð   if (type == "}") return cont();Ð   return pass(statement,
block);Ð }Ð function maybetype(type) {Ð   if (isTS && type == ":") return
cont(typedef);Ð }Ð function typedef(type) {Ð   if (type == "variable")
{cx.marked = "variable-3"; return cont();}Ð }Ð function vardef() {Ð   return
pass(pattern, maybetype, maybeAssign, vardefCont);Ð }Ð function pattern(type,
value) {Ð   if (type == "variable") { register(value); return cont(); }Ð   if
(type == "[") return contCommasep(pattern, "]");Ð   if (type == "{") return
contCommasep(proppattern, "}");Ð }Ð function proppattern(type, value) {Ð   if
(type == "variable" && !cx.stream.match(/^\s*:/, false)) {Ð
register(value);Ð     return cont(maybeAssign);Ð   }Ð   if (type ==
"variable") cx.marked = "property";Ð   return cont(expect(":"), pattern,
maybeAssign);Ð }Ð function maybeAssign(_type, value) {Ð   if (value == "=")
return cont(expressionNoComma);Ð }Ð function vardefCont(type) {Ð   if (type
== ",") return cont(vardef);Ð }Ð function maybeelse(type, value) {Ð   if
(type == "keyword b" && value == "else") return cont(pushlex("form", "else"),
statement, poplex);Ð }Ð function forspec(type) {Ð   if (type == "(") return
cont(pushlex(")"), forspec1, expect(")"), poplex);Ð }Ð function
forspec1(type) {Ð   if (type == "var") return cont(vardef, expect(";"),
forspec2);Ð   if (type == ";") return cont(forspec2);Ð   if (type ==
"variable") return cont(formaybeinof);Ð   return pass(expression,
expect(";"), forspec2);Ð }Ð function formaybeinof(_type, value) {Ð   if
(value == "in" || value == "of") { cx.marked = "keyword"; return
cont(expression); }Ð   return cont(maybeoperatorComma, forspec2);Ð }Ð
function forspec2(type, value) {Ð   if (type == ";") return cont(forspec3);Ð
    if (value == "in" || value == "of") { cx.marked = "keyword"; return
cont(expression); }Ð   return pass(expression, expect(";"), forspec3);Ð }Ð
function forspec3(type) {Ð   if (type != ")") cont(expression);Ð }Ð function
functiondef(type, value) {Ð   if (value == "*") {cx.marked = "keyword";
return cont(functiondef);}Ð   if (type == "variable") {register(value);
return cont(functiondef);}Ð   if (type == "(") return cont(pushcontext,
pushlex(")"), commasep(funarg, ")"), poplex, statement, popcontext);Ð }Ð
function funarg(type) {Ð   if (type == "spread") return cont(funarg);Ð
return pass(pattern, maybetype);Ð }Ð function className(type, value) {Ð   if
(type == "variable") {register(value); return cont(classNameAfter);}Ð }Ð
function classNameAfter(type, value) {Ð   if (value == "extends") return
cont(expression, classNameAfter);Ð   if (type == "{") return
cont(pushlex("}"), classBody, poplex);Ð }Ð function classBody(type, value) {Ð
    if (type == "variable" || cx.style == "keyword") {Ð     cx.marked =
"property";Ð     if (value == "get" || value == "set") return
cont(classGetterSetter, functiondef, classBody);Ð     return
cont(functiondef, classBody);Ð   }Ð   if (value == "*") {Ð     cx.marked =
"keyword";Ð     return cont(classBody);Ð   }Ð   if (type == ";") return
cont(classBody);Ð   if (type == "}") return cont();Ð }Ð function
classGetterSetter(type) {Ð   if (type != "variable") return pass();Ð
cx.marked = "property";Ð   return cont();Ð }Ð function afterModule(type,
value) {Ð   if (type == "string") return cont(statement);Ð   if (type ==
"variable") { register(value); return cont(maybeFrom); }Ð }Ð function
afterExport(_type, value) {Ð   if (value == "*") { cx.marked = "keyword";
return cont(maybeFrom, expect(";")); }Ð   if (value == "default") { cx.marked
= "keyword"; return cont(expression, expect(";")); }Ð   return
pass(statement);Ð }Ð function afterImport(type) {Ð   if (type == "string")
return cont();Ð   return pass(importSpec, maybeFrom);Ð }Ð function
importSpec(type, value) {Ð   if (type == "{") return contCommasep(importSpec,
"}");Ð   if (type == "variable") register(value);Ð   return cont();Ð }Ð
function maybeFrom(_type, value) {Ð   if (value == "from") { cx.marked =
"keyword"; return cont(expression); }Ð }Ð function arrayLiteral(type) {Ð   if
(type == "]") return cont();Ð   return pass(expressionNoComma,
maybeArrayComprehension);Ð }Ð function maybeArrayComprehension(type) {Ð   if
(type == "for") return pass(comprehension, expect("]"));Ð
```

```
                                                                if (type == ",")
return cont(commasep(maybeexpressionNoComma, "]"));Ð   return
pass(commasep(expressionNoComma, "]"));Ð }Ð function comprehension(type) {Ð
if (type == "for") return cont(forspec, comprehension);Ð   if (type == "if")
return cont(expression, comprehension);Ð }Ð // InterfaceÐ return {Ð
startState: function(basecolumn) {Ð     var state = {Ð       tokenize:
tokenBase,Ð       lastType: "sof",Ð       cc: [],Ð       lexical: new
JSLexical((basecolumn || 0) - indentUnit, 0, "block", false),Ð
localVars: parserConfig.localVars,Ð       context: parserConfig.localVars &&
{vars: parserConfig.localVars},Ð       indented: 0Ð     };Ð     if
(parserConfig.globalVars && typeof parserConfig.globalVars == "object")Ð
        state.globalVars = parserConfig.globalVars;Ð     return state;Ð   },Ð
    token: function(stream, state) {Ð     if (stream.sol()) {Ð       if (!
state.lexical.hasOwnProperty("align"))Ð         state.lexical.align = false;Ð
        state.indented = stream.indentation();Ð       findFatArrow(stream,
state);Ð     }Ð     if (state.tokenize != tokenComment && stream.eatSpace())
return null;Ð     var style = state.tokenize(stream, state);Ð     if (type ==
"comment") return style;Ð     state.lastType = type == "operator" && (content
== "++" || content == "--") ? "incdec" : type;Ð     return parseJS(state,
style, type, content, stream);Ð   },Ð   indent: function(state, textAfter) {Ð
      if (state.tokenize == tokenComment) return CodeMirror.Pass;Ð     if
(state.tokenize != tokenBase) return 0;Ð     var firstChar = textAfter &&
textAfter.charAt(0), lexical = state.lexical;Ð     // Kludge to prevent
'maybelse' from blocking lexical scope popsÐ     if (!/
^\s*else\b/.test(textAfter)) for (var i = state.cc.length - 1; i >= 0; --i) {Ð
        var c = state.cc[i];Ð       if (c == poplex) lexical = lexical.prev;Ð
        else if (c != maybeelse) break;Ð     }Ð     if (lexical.type ==
"stat" && firstChar == "}") lexical = lexical.prev;Ð     if (statementIndent
&& lexical.type == ")" && lexical.prev.type == "stat")Ð       lexical =
lexical.prev;Ð     var type = lexical.type, closing = firstChar == type;Ð
if (type == "vardef") return lexical.indented + (state.lastType == "operator"
|| state.lastType == "," ? lexical.info + 1 : 0);Ð     else if (type ==
"form" && firstChar == "{") return lexical.indented;Ð     else if (type ==
"form") return lexical.indented + indentUnit;Ð     else if (type == "stat")Ð
        return lexical.indented + (state.lastType == "operator" ||
state.lastType == "," ? statementIndent || indentUnit : 0);Ð     else if
(lexical.info == "switch" && !closing && parserConfig.doubleIndentSwitch !=
false)Ð       return lexical.indented + (/^(?:case|
default)\b/.test(textAfter) ? indentUnit : 2 * indentUnit);Ð     else if
(lexical.align) return lexical.column + (closing ? 0 : 1);Ð     else return
lexical.indented + (closing ? 0 : indentUnit);Ð   },Ð   electricInput: /
^\s*(?:case .*?:|default:|\{|\})$/,Ð   blockCommentStart: jsonMode ? null : "/
*",Ð   blockCommentEnd: jsonMode ? null : "*/",Ð   lineComment: jsonMode ?
null : "//",Ð   fold: "brace",Ð   helperType: jsonMode ? "json" :
"javascript",Ð   jsonldMode: jsonldMode,Ð   jsonMode: jsonModeÐ };Ð});Ð
CodeMirror.registerHelper("wordChars", "javascript", /[\w$]/);Ð
CodeMirror.defineMIME("text/javascript", "javascript");Ð
CodeMirror.defineMIME("text/ecmascript", "javascript");Ð
CodeMirror.defineMIME("application/javascript", "javascript");Ð
CodeMirror.defineMIME("application/x-javascript", "javascript");Ð
CodeMirror.defineMIME("application/ecmascript", "javascript");Ð
CodeMirror.defineMIME("application/json", {name: "javascript", json: true});Ð
CodeMirror.defineMIME("application/x-json", {name: "javascript", json: true});Ð
CodeMirror.defineMIME("application/ld+json", {name: "javascript", jsonld:
true});ÐodeMirror.defineMIME("text/typescript", { name: "javascript",
typescript: true });ÐodeMirror.defineMIME("application/typescript", { name:
"javascript", typescript: true });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\javascript\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ðfunction() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "javascript");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT("locals",Ð    "[keyword function] [variable foo]([def a], [def b])
{ [keyword var] [def c] [operator =] [number 10]; [keyword return]
[variable-2 a] [operator +] [variable-2 c] [operator +] [variable d]; }");Ð
MT("comma-and-binop",Ð    "[keyword function](){ [keyword var] [def x]
[operator =] [number 1] [operator +] [number 2], [def y]; }");Ð
MT("destructuring",Ð    "([keyword function]([def a], [[[def b], [def c] ]])
{",Ð    "  [keyword let] {[def d], [property foo]: [def c][operator =][number
10], [def x]} [operator =] [variable foo]([variable-2 a]);",Ð
"  [[[variable-2 c], [variable y] ]] [operator =] [variable-2 c];",Ð    "})
();");Ð MT("class_body",Ð    "[keyword class] [variable Foo] {",Ð
"  [property constructor]() {}",Ð    "  [property sayName]() {",Ð
"    [keyword return] [string-2 `foo${][variable foo][string-2 }oo`];",Ð
"  }",Ð    "}");Ð MT("class",Ð    "[keyword class] [variable Point] [keyword
extends] [variable SuperThing] {",Ð    "  [property get] [property prop]()
{ [keyword return] [number 24]; }",Ð    "  [property constructor]([def x],
[def y]) {",Ð    "    [keyword super]([string 'something']);",Ð
"    [keyword this].[property x] [operator =] [variable-2 x];",Ð    "  }",Ð
     "}");Ð MT("module",Ð    "[keyword module] [string 'foo'] {",Ð
"  [keyword export] [keyword let] [def x] [operator =] [number 42];",Ð
"  [keyword export] [keyword *] [keyword from] [string 'somewhere'];",Ð
"}");Ð MT("import",Ð    "[keyword function] [variable foo]() {",Ð
"  [keyword import] [def $] [keyword from] [string 'jquery'];",Ð
"  [keyword module] [def crypto] [keyword from] [string 'crypto'];",Ð
"  [keyword import] { [def encrypt], [def decrypt] } [keyword from] [string
'crypto'];",Ð    "}");Ð MT("const",Ð    "[keyword function] [variable f]() {",Ð
     "  [keyword const] [[ [def a], [def b] ]] [operator =] [[ [number 1],
[number 2] ]];",Ð    "}");Ð MT("for/of",Ð    "[keyword for]([keyword let]
[variable of] [keyword of] [variable something]) {}");Ð MT("generator",Ð
"[keyword function*] [variable repeat]([def n]) {",Ð    "  [keyword for]
([keyword var] [def i] [operator =] [number 0]; [variable-2 i] [operator <]
[variable-2 n]; [operator ++][variable-2 i])",Ð    "    [keyword yield]
[variable-2 i];",Ð    "}");Ð MT("fatArrow",Ð    "[variable array].[property
filter]([def a] [operator =>] [variable-2 a] [operator +] [number 1]);",Ð
"[variable a];", // No longer in scopeÐ    "[keyword let] [variable f]
[operator =] ([[ [def a], [def b] ]], [def c]) [operator =>] [variable-2 a]
[operator +] [variable-2 c];",Ð    "[variable c];");Ð MT("spread",Ð
"[keyword function] [variable f]([def a], [meta ...][def b]) {",Ð
"  [variable something]([variable-2 a], [meta ...][variable-2 b]);",Ð    "}");Ð
  MT("comprehension",Ð    "[keyword function] [variable f]() {",Ð
"  [[([variable x] [operator +] [number 1]) [keyword for] ([keyword var] [def
x] [keyword in] [variable y]) [keyword if] [variable pred]([variable-2
x]) ]];",Ð    "  ([variable u] [keyword for] ([keyword var] [def u] [keyword
of] [variable generateValues]()) [keyword if] ([variable-2 u].[property
color] [operator ===] [string 'blue']));",Ð    "}");Ð MT("quasi",Ð
"[variable re][string-2 `fofdlakj${][variable x] [operator +] ([variable re]
[string-2 `foo`]) [operator +] [number 1][string-2 }fdsa`] [operator +]
[number 2]");Ð MT("quasi_no_function",Ð    "[variable x] [operator =]
[string-2 `fofdlakj${][variable x] [operator +] [string-2 `foo`] [operator +]
[number 1][string-2 }fdsa`] [operator +] [number 2]");Ð MT("indent_statement",Ð
     "[keyword var] [variable x] [operator =] [number 10]",Ð    "[variable x]
[operator +=] [variable y] [operator +]",Ð    "  [atom Infinity]",Ð
"[keyword debugger];");Ð MT("indent_if",Ð    "[keyword if] ([number 1])",Ð
"  [keyword break];",Ð    "[keyword else] [keyword if] ([number 2])",Ð
"  [keyword continue];",Ð    "[keyword else]",Ð    "  [number 10];",Ð
"[keyword if] ([number 1]) {",Ð
```

```
                                    "  [keyword break];",Ð    "} [keyword
else] [keyword if] ([number 2]) {",Ð    "  [keyword continue];",Ð    "}
[keyword else] {",Ð    "  [number 10];",Ð    "});Ð MT("indent_for",Ð
"[keyword for] ([keyword var] [variable i] [operator =] [number 0];",Ð
"     [variable i] [operator <] [number 100];",Ð    "     [variable i]
[operator ++])",Ð    "  [variable doSomething([variable i]);",Ð    "[keyword
debugger];");Ð MT("indent_c_style",Ð    "[keyword function] [variable foo]()",Ð
     "{",Ð    "  [keyword debugger];",Ð    "});Ð MT("indent_else",Ð
"[keyword for] (;;)",Ð    "  [keyword if] ([variable foo])",Ð
"    [keyword if] ([variable bar])",Ð    "      [number 1];",Ð
"    [keyword else]",Ð    "      [number 2];",Ð    "  [keyword else]",Ð
"    [number 3];");Ð MT("indent_funarg",Ð    "[variable foo]([number 10000],",Ð
     "    [keyword function]([def a]) {",Ð    "  [keyword debugger];",Ð
"};");Ð MT("indent_below_if",Ð    "[keyword for] (;;)",Ð    "  [keyword if]
([variable foo])",Ð    "    [number 1];",Ð    "[number 2];");Ð
MT("multilinestring",Ð    "[keyword var] [variable x] [operator =] [string
'foo\\]",Ð    "[string bar'];");Ð MT("scary_regexp",Ð    "[string-2 /
foo[[/]]bar/];");Ð MT("indent_strange_array",Ð    "[keyword var] [variable x]
[operator =] [[",Ð    "  [number 1],,",Ð    "  [number 2],",Ð    "]];",Ð
"[number 10];");Ð var jsonld_mode = CodeMirror.getMode(Ð   {indentUnit: 2},Ð
    {name: "javascript", jsonld: true}Ð );Ð function LD(name) {Ð
test.mode(name, jsonld_mode, Array.prototype.slice.call(arguments, 1));Ð }Ð
LD("json_ld_keywords",Ð   '{',Ð   '  [meta "@context"]: {',Ð   '    [meta
"@base"]: [string "http://example.com"],',Ð   '    [meta "@vocab"]: [string
"http://xmlns.com/foaf/0.1/"],',Ð   '    [property "likesFlavor"]: {',Ð
'      [meta "@container"]: [meta "@list"]',Ð   '      [meta "@reverse"]:
[string "@beFavoriteOf"]',Ð   '    },',Ð   '    [property "nick"]: { [meta
"@container"]: [meta "@set"] },',Ð   '    [property "nick"]: { [meta
"@container"]: [meta "@index"] }',Ð   '  },',Ð   '  [meta "@graph"]: [[ {',Ð
    '    [meta "@id"]: [string "http://dbpedia.org/resource/John_Lennon"],',Ð
    '    [property "name"]: [string "John Lennon"],',Ð   '    [property
"modified"]: {',Ð   '      [meta "@value"]: [string
"2010-05-29T14:17:39+02:00"],',Ð   '      [meta "@type"]: [string "http://
www.w3.org/2001/XMLSchema#dateTime"]',Ð   '    }',Ð   '  } ]]',Ð   '}');Ð
LD("json_ld_fake",Ð   '{',Ð   '  [property "@fake"]: [string "@fake"],',Ð
'  [property "@contextual"]: [string "@identifier"],',Ð   '  [property
"user@domain.com"]: [string "@graphical"],',Ð   '  [property "@ID"]: [string
"@@ID"]',Ð   '}');Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\jinja2\jinja2.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
  CodeMirror.defineMode("jinja2", function() {Ð   var keywords = ["and",
"as", "block", "endblock", "by", "cycle", "debug", "else", "elif",Ð
"extends", "filter", "endfilter", "firstof", "for",Ð     "endfor", "if",
"endif", "ifchanged", "endifchanged",Ð     "ifequal", "endifequal",
"ifnotequal",Ð     "endifnotequal", "in", "include", "load", "not", "now",
"or",Ð     "parsed", "regroup", "reversed", "spaceless",Ð     "endspaceless",
"ssi", "templatetag", "openblock",Ð     "closeblock", "openvariable",
"closevariable",Ð     "openbrace", "closebrace", "opencomment",Ð
"closecomment", "widthratio", "url", "with", "endwith",Ð
"get_current_language", "trans", "endtrans", "noop", "blocktrans",Ð
"endblocktrans", "get_available_languages",Ð     "get_current_language_bidi",
"plural"],Ð   operator = /^[+\-*&%=<>!?|~^]/,Ð   sign = /^[:\[\(\{]/,Ð   atom
= ["true", "false"],Ð   number = /^(\d[+\-\*\/])?\d+(\.\d+)?/;Ð   keywords =
new RegExp("((" + keywords.join(")|(") + "))\\b");Ð   atom = new RegExp("(("
+ atom.join(")|(") + "))\\b");Ð   function tokenBase (stream, state) {Ð
var ch = stream.peek();Ð     //CommentÐ     if (state.incomment) {Ð       if(!
stream.skipTo("#}")) {Ð         stream.skipToEnd();Ð       } else {Ð
stream.eatWhile(/\#|}/);Ð         state.incomment = false;Ð       }Ð
return "comment";Ð     //TagÐ     } else if (state.intag) {Ð       //After
operatorÐ       if(state.operator) {Ð         state.operator = false;Ð
          if(stream.match(atom)) {Ð           return "atom";Ð         }Ð
          if(stream.match(number)) {Ð           return "number";Ð         }Ð
        }Ð       //After signÐ       if(state.sign) {Ð         state.sign =
false;Ð         if(stream.match(atom)) {Ð           return "atom";Ð         }Ð
          if(stream.match(number)) {Ð           return "number";Ð         }Ð
        }Ð       if(state.instring) {Ð         if(ch == state.instring) {Ð
            state.instring = false;Ð         }Ð         stream.next();Ð
          return "string";Ð       } else if(ch == "'" || ch == '"') {Ð
          state.instring = ch;Ð         stream.next();Ð         return
"string";Ð       } else if(stream.match(state.intag + "}") || stream.eat("-")
&& stream.match(state.intag + "}")) {Ð         state.intag = false;Ð
return "tag";Ð       } else if(stream.match(operator)) {Ð
state.operator = true;Ð         return "operator";Ð       } else
if(stream.match(sign)) {Ð         state.sign = true;Ð       } else {Ð
if(stream.eat(" ") || stream.sol()) {Ð           if(stream.match(keywords)) {Ð
              return "keyword";Ð           }Ð
if(stream.match(atom)) {Ð             return "atom";Ð           }Ð
if(stream.match(number)) {Ð             return "number";Ð           }Ð
            if(stream.sol()) {Ð             stream.next();Ð           }Ð
          } else {Ð           stream.next();Ð         }Ð       }Ð
return "variable";Ð     } else if (stream.eat("{")) {Ð       if (ch =
stream.eat("#")) {Ð         state.incomment = true;Ð         if(!
stream.skipTo("#}")) {Ð           stream.skipToEnd();Ð         } else {Ð
            stream.eatWhile(/\#|}/);Ð           state.incomment = false;Ð
          }Ð         return "comment";Ð       //Open tagÐ       } else if (ch
= stream.eat(/\{|%/)) {Ð         //Cache close tagÐ         state.intag = ch;Ð
          if(ch == "{") {Ð           state.intag = "}";Ð         }Ð
stream.eat("-");Ð         return "tag";Ð       }Ð     }Ð     stream.next();Ð
    };Ð   return {Ð     startState: function () {Ð       return {tokenize:
tokenBase};Ð     },Ð     token: function (stream, state) {Ð       return
state.tokenize(stream, state);Ð     }Ð   };Ð });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\julia\julia.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("julia", function(_conf, parserConf) {Ð var ERRORCLASS
= 'error';Ð function wordRegexp(words) {Ð   return new RegExp("^((" +
words.join(")|(") + "))\\b");Ð }Ð var operators = parserConf.operators || /
^\.?[|&^\\%*+\-<>!=\/]=?|\?|~|:|\$|\.[<>]|<<=?|>>>?=?|\.[<>=]=|->?|\/\/|
\bin\b/;Ð var delimiters = parserConf.delimiters || /^[;,()[\]{}]/;Ð var
identifiers = parserConf.identifiers|| /^[_A-Za-z\u00A1-\uFFFF][_A-Za-
z0-9\u00A1-\uFFFF]*!*/;Ð var blockOpeners = ["begin", "function", "type",
"immutable", "let", "macro", "for", "while", "quote", "if", "else", "elseif",
"try", "finally", "catch", "do"];Ð var blockClosers = ["end", "else",
"elseif", "catch", "finally"];Ð var keywordList = ['if', 'else', 'elseif',
'while', 'for', 'begin', 'let', 'end', 'do', 'try', 'catch', 'finally',
'return', 'break', 'continue', 'global', 'local', 'const', 'export',
'import', 'importall', 'using', 'function', 'macro', 'module', 'baremodule',
'type', 'immutable', 'quote', 'typealias', 'abstract', 'bitstype', 'ccall'];Ð
var builtinList = ['true', 'false', 'enumerate', 'open', 'close', 'nothing',
'NaN', 'Inf', 'print', 'println', 'Int', 'Int8', 'Uint8', 'Int16', 'Uint16',
'Int32', 'Uint32', 'Int64', 'Uint64', 'Int128', 'Uint128', 'Bool', 'Char',
'Float16', 'Float32', 'Float64', 'Array', 'Vector', 'Matrix', 'String',
'UTF8String', 'ASCIIString', 'error', 'warn', 'info', '@printf'];Ð //var
stringPrefixes = new RegExp("^[br]?('|\")")Ð var stringPrefixes = /^(`|'|"{3}|
([br]?"))/;Ð var keywords = wordRegexp(keywordList);Ð var builtins =
wordRegexp(builtinList);Ð var openers = wordRegexp(blockOpeners);Ð var
closers = wordRegexp(blockClosers);Ð var macro = /^@[_A-Za-z][_A-Za-z0-9]*/;Ð
var symbol = /^:[_A-Za-z][_A-Za-z0-9]*/;Ð var indentInfo = null;Ð function
in_array(state) {Ð   var ch = cur_scope(state);Ð   if(ch=="[" || ch=="{") {Ð
      return true;Ð   }Ð   else {Ð     return false;Ð   }Ð }Ð function
cur_scope(state) {Ð   if(state.scopes.length==0) {Ð     return null;Ð   }Ð
return state.scopes[state.scopes.length - 1];Ð }Ð // tokenizersÐ function
tokenBase(stream, state) {Ð   // Handle scope changesÐ   var leaving_expr =
state.leaving_expr;Ð   if(stream.sol()) {Ð     leaving_expr = false;Ð   }Ð
state.leaving_expr = false;Ð   if(leaving_expr) {Ð     if(stream.match(/
^'+/)) {Ð       return 'operator';Ð     }Ð   }Ð   if(stream.match(/^\.
{2,3}/)) {Ð     return 'operator';Ð   }Ð   if (stream.eatSpace()) {Ð
return null;Ð   }Ð   var ch = stream.peek();Ð   // Handle CommentsÐ   if (ch
=== '#') {Ð       stream.skipToEnd();Ð       return 'comment';Ð   }Ð
if(ch=='[') {Ð     state.scopes.push("[");Ð   }Ð   if(ch=='{') {Ð
state.scopes.push("{");Ð   }Ð   var scope=cur_scope(state);Ð   if(scope=='['
&& ch==']') {Ð     state.scopes.pop();Ð     state.leaving_expr=true;Ð   }Ð
if(scope=='{' && ch=='}') {Ð     state.scopes.pop();Ð
state.leaving_expr=true;Ð   }Ð   if(ch==')') {Ð     state.leaving_expr =
true;Ð   }Ð   var match;Ð   if(!in_array(state) &&
(match=stream.match(openers, false))) {Ð     state.scopes.push(match);Ð   }Ð
    if(!in_array(state) && stream.match(closers, false)) {Ð
state.scopes.pop();Ð   }Ð   if(in_array(state)) {Ð     if(stream.match(/
^end/)) {Ð       return 'number';Ð     }Ð   }Ð   if(stream.match(/^=>/)) {Ð
      return 'operator';Ð   }Ð   // Handle Number LiteralsÐ   if
(stream.match(/^[0-9\.]/, false)) {Ð     var imMatcher = RegExp(/^im\b/);Ð
      var floatLiteral = false;Ð     // FloatsÐ     if (stream.match(/^\d*\.
(?!\.)\d+([ef][\+\-]?\d+)?/i)) { floatLiteral = true; }Ð     if
(stream.match(/^\d+\.(?!\.)\d*/)) { floatLiteral = true; }Ð     if
(stream.match(/^\.\d+/)) { floatLiteral = true; }Ð     if (floatLiteral) {Ð
          // Float literals may be "imaginary"Ð
stream.match(imMatcher);Ð
```

```
                                    state.leaving_expr = true;Ð         return
'number';Ð     }Ð     // IntegersÐ     var intLiteral = false;Ð     // HexÐ
      if (stream.match(/^0x[0-9a-f]+/i)) { intLiteral = true; }Ð     // BinaryÐ
      if (stream.match(/^0b[01]+/i)) { intLiteral = true; }Ð     // OctalÐ
      if (stream.match(/^0o[0-7]+/i)) { intLiteral = true; }Ð     // DecimalÐ
      if (stream.match(/^[1-9]\d*(e[\+\-]?\d+)?/)) {Ð         intLiteral =
true;Ð     }Ð     // Zero by itself with no other piece of number.Ð     if
(stream.match(/^0(?![\dx])/i)) { intLiteral = true; }Ð     if (intLiteral) {Ð
          // Integer literals may be "long"Ð         stream.match(imMatcher);Ð
          state.leaving_expr = true;Ð         return 'number';Ð     }Ð   }Ð
if(stream.match(/^(::)|(<:)/)) {Ð     return 'operator';Ð   }Ð   // Handle
symbolsÐ   if(!leaving_expr && stream.match(symbol)) {Ð     return 'string';Ð
    }Ð   // Handle operators and DelimitersÐ   if (stream.match(operators)) {Ð
      return 'operator';Ð   }Ð   // Handle StringsÐ   if
(stream.match(stringPrefixes)) {Ð     state.tokenize =
tokenStringFactory(stream.current());Ð     return state.tokenize(stream,
state);Ð   }Ð   if (stream.match(macro)) {Ð     return 'meta';Ð   }Ð   if
(stream.match(delimiters)) {Ð     return null;Ð   }Ð   if
(stream.match(keywords)) {Ð     return 'keyword';Ð   }Ð   if
(stream.match(builtins)) {Ð     return 'builtin';Ð   }Ð   if
(stream.match(identifiers)) {Ð     state.leaving_expr=true;Ð     return
'variable';Ð   }Ð   // Handle non-detected itemsÐ   stream.next();Ð   return
ERRORCLASS;Ð }Ð function tokenStringFactory(delimiter) {Ð   while
('rub'.indexOf(delimiter.charAt(0).toLowerCase()) >= 0) {Ð     delimiter =
delimiter.substr(1);Ð   }Ð   var singleline = delimiter.length == 1;Ð   var
OUTCLASS = 'string';Ð   function tokenString(stream, state) {Ð     while (!
stream.eol()) {Ð       stream.eatWhile(/[^'"\\]/);Ð       if (stream.eat('\
\')) {Ð           stream.next();Ð           if (singleline && stream.eol()) {Ð
              return OUTCLASS;Ð           }Ð       } else if
(stream.match(delimiter)) {Ð           state.tokenize = tokenBase;Ð
return OUTCLASS;Ð       } else {Ð           stream.eat(/['"]/);Ð       }Ð
      }Ð     if (singleline) {Ð       if (parserConf.singleLineStringErrors) {Ð
            return ERRORCLASS;Ð       } else {Ð           state.tokenize =
tokenBase;Ð       }Ð     }Ð     return OUTCLASS;Ð   }Ð   tokenString.isString
= true;Ð   return tokenString;Ð }Ð function tokenLexer(stream, state) {Ð
indentInfo = null;Ð   var style = state.tokenize(stream, state);Ð   var
current = stream.current();Ð   // Handle '.' connected identifiersÐ   if
(current === '.') {Ð     style = stream.match(identifiers, false) ? null :
ERRORCLASS;Ð     if (style === null && state.lastStyle === 'meta') {Ð
          // Apply 'meta' style to '.' connected identifiers whenÐ         //
appropriate.Ð       style = 'meta';Ð     }Ð     return style;Ð   }Ð   return
style;Ð }Ð var external = {Ð   startState: function() {Ð     return {Ð
tokenize: tokenBase,Ð       scopes: [],Ð       leaving_expr: falseÐ     };Ð
    },Ð   token: function(stream, state) {Ð     var style =
tokenLexer(stream, state);Ð     state.lastStyle = style;Ð     return style;Ð
    },Ð   indent: function(state, textAfter) {Ð     var delta = 0;Ð
if(textAfter=="end" || textAfter=="]" || textAfter=="}" || textAfter=="else"
|| textAfter=="elseif" || textAfter=="catch" || textAfter=="finally") {Ð
        delta = -1;Ð     }Ð     return (state.scopes.length + delta) * 4;Ð
    },Ð   lineComment: "#",Ð   fold: "indent",Ð   electricChars: "edlsifyh]}"Ð
  };Ð return external;Ð});ÐodeMirror.defineMIME("text/x-julia", "julia");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\kotlin\kotlin.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("kotlin", function (config, parserConfig) {Ð function
words(str) {Ð   var obj = {}, words = str.split(" ");Ð   for (var i = 0; i <
words.length; ++i) obj[words[i]] = true;Ð   return obj;Ð }Ð var
multiLineStrings = parserConfig.multiLineStrings;Ð var keywords = words(Ð
          "package continue return object while break class data trait throw
super" +Ð         " when type this else This try val var fun for is in if do
as true false null get set");Ð var softKeywords = words("import" +Ð     "
where by get set abstract enum open annotation override private public
internal" +Ð     " protected catch out vararg inline finally final ref");Ð
var blockKeywords = words("catch class do else finally for if where try while
enum");Ð var atoms = words("null true false this");Ð var curPunc;Ð function
tokenBase(stream, state) {Ð   var ch = stream.next();Ð   if (ch == '"' || ch
== "'") {Ð     return startString(ch, stream, state);Ð   }Ð   // Wildcard
import w/o trailing semicolon (import smth.*)Ð   if (ch == "." &&
stream.eat("*")) {Ð     return "word";Ð   }Ð   if (/[\[\]{}\(\),;\:
\.]/.test(ch)) {Ð     curPunc = ch;Ð     return null;Ð   }Ð   if (/
\d/.test(ch)) {Ð     if (stream.eat(/eE/)) {Ð       stream.eat(/\+\-/);Ð
        stream.eatWhile(/\d/);Ð     }Ð     return "number";Ð   }Ð   if (ch ==
"/") {Ð     if (stream.eat("*")) {Ð       state.tokenize.push(tokenComment);Ð
        return tokenComment(stream, state);Ð     }Ð     if (stream.eat("/")) {Ð
        stream.skipToEnd();Ð       return "comment";Ð     }Ð     if
(expectExpression(state.lastToken)) {Ð       return startString(ch, stream,
state);Ð     }Ð   }Ð   // CommentedÐ   if (ch == "-" && stream.eat(">")) {Ð
      curPunc = "->";Ð     return null;Ð   }Ð   if (/[\-+*&%=<>!?|\/
~]/.test(ch)) {Ð     stream.eatWhile(/[\-+*&%=<>|~]/);Ð     return "operator";Ð
    }Ð   stream.eatWhile(/[\w\$_]/);Ð   var cur = stream.current();Ð   if
(atoms.propertyIsEnumerable(cur)) {Ð     return "atom";Ð   }Ð   if
(softKeywords.propertyIsEnumerable(cur)) {Ð     if
(blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "softKeyword";Ð   }Ð   if (keywords.propertyIsEnumerable(cur)) {Ð
if (blockKeywords.propertyIsEnumerable(cur)) curPunc = "newstatement";Ð
return "keyword";Ð   }Ð   return "word";Ð }Ð tokenBase.isBase = true;Ð
function startString(quote, stream, state) {Ð   var tripleQuoted = false;Ð
if (quote != "/" && stream.eat(quote)) {Ð     if (stream.eat(quote))
tripleQuoted = true;Ð     else return "string";Ð   }Ð   function t(stream,
state) {Ð     var escaped = false, next, end = !tripleQuoted;Ð     while
((next = stream.next()) != null) {Ð       if (next == quote && !escaped) {Ð
          if (!tripleQuoted) {Ð           break;Ð         }Ð         if
(stream.match(quote + quote)) {Ð           end = true;Ð           break;Ð
          }Ð       }Ð       if (quote == '"' && next == "$" && !escaped &&
stream.eat("{")) {Ð         state.tokenize.push(tokenBaseUntilBrace());Ð
          return "string";Ð       }Ð       if (next == "$" && !escaped && !
stream.eat(" ")) {Ð         state.tokenize.push(tokenBaseUntilSpace());Ð
          return "string";Ð       }Ð       escaped = !escaped && next == "\\";Ð
      }Ð     if (multiLineStrings)Ð       state.tokenize.push(t);Ð     if
(end) state.tokenize.pop();Ð     return "string";Ð   }Ð
state.tokenize.push(t);Ð   return t(stream, state);Ð }Ð function
tokenBaseUntilBrace() {Ð   var depth = 1;Ð   function t(stream, state) {Ð
if (stream.peek() == "}") {Ð       depth--;Ð       if (depth == 0) {Ð
state.tokenize.pop();Ð         return state.tokenize[state.tokenize.length -
1](stream, state);Ð       }Ð     } else if (stream.peek() == "{") {Ð
depth++;Ð     }Ð     return tokenBase(stream, state);Ð   }Ð   t.isBase = true;Ð
    return t;Ð
```

```
                }Ð function tokenBaseUntilSpace() {Ð   function t(stream,
state) {Ð     if (stream.eat(/[\w]/)) {Ð       var isWord = stream.eatWhile(/
[\w]/);Ð       if (isWord) {Ð         state.tokenize.pop();Ð         return
"word";Ð       }Ð     }Ð     state.tokenize.pop();Ð     return "string";Ð   }Ð
    t.isBase = true;Ð   return t;Ð }Ð function tokenComment(stream, state) {Ð
    var maybeEnd = false, ch;Ð   while (ch = stream.next()) {Ð     if (ch ==
"/" && maybeEnd) {Ð       state.tokenize.pop();Ð       break;Ð     }Ð
maybeEnd = (ch == "*");Ð   }Ð   return "comment";Ð }Ð function
expectExpression(last) {Ð   return !last || last == "operator" || last == "-
>" || /[\.\[\{\(,;:]/.test(last) ||Ð       last == "newstatement" || last ==
"keyword" || last == "proplabel";Ð }Ð function Context(indented, column,
type, align, prev) {Ð   this.indented = indented;Ð   this.column = column;Ð
this.type = type;Ð   this.align = align;Ð   this.prev = prev;Ð }Ð function
pushContext(state, col, type) {Ð   return state.context = new
Context(state.indented, col, type, null, state.context);Ð }Ð function
popContext(state) {Ð   var t = state.context.type;Ð   if (t == ")" || t ==
"]" || t == "}")Ð     state.indented = state.context.indented;Ð   return
state.context = state.context.prev;Ð }Ð // InterfaceÐ return {Ð   startState:
function (basecolumn) {Ð     return {Ð       tokenize: [tokenBase],Ð
context: new Context((basecolumn || 0) - config.indentUnit, 0, "top", false),Ð
        indented: 0,Ð       startOfLine: true,Ð       lastToken: nullÐ     };Ð
    },Ð   token: function (stream, state) {Ð     var ctx = state.context;Ð
      if (stream.sol()) {Ð       if (ctx.align == null) ctx.align = false;Ð
        state.indented = stream.indentation();Ð       state.startOfLine =
true;Ð       // Automatic semicolon insertionÐ       if (ctx.type ==
"statement" && !expectExpression(state.lastToken)) {Ð
popContext(state);Ð         ctx = state.context;Ð       }Ð     }Ð     if
(stream.eatSpace()) return null;Ð     curPunc = null;Ð     var style =
state.tokenize[state.tokenize.length - 1](stream, state);Ð     if (style ==
"comment") return style;Ð     if (ctx.align == null) ctx.align = true;Ð
if ((curPunc == ";" || curPunc == ":") && ctx.type == "statement")
popContext(state);Ð     // Handle indentation for {x -> \n ... }Ð     else if
(curPunc == "->" && ctx.type == "statement" && ctx.prev.type == "}") {Ð
popContext(state);Ð       state.context.align = false;Ð     }Ð     else if
(curPunc == "{") pushContext(state, stream.column(), "}");Ð     else if
(curPunc == "[") pushContext(state, stream.column(), "]");Ð     else if
(curPunc == "(") pushContext(state, stream.column(), ")");Ð     else if
(curPunc == "}") {Ð       while (ctx.type == "statement") ctx =
popContext(state);Ð       if (ctx.type == "}") ctx = popContext(state);Ð
        while (ctx.type == "statement") ctx = popContext(state);Ð     }Ð
else if (curPunc == ctx.type) popContext(state);Ð     else if (ctx.type ==
"}" || ctx.type == "top" || (ctx.type == "statement" && curPunc ==
"newstatement"))Ð       pushContext(state, stream.column(), "statement");Ð
      state.startOfLine = false;Ð     state.lastToken = curPunc || style;Ð
      return style;Ð   },Ð   indent: function (state, textAfter) {Ð     if (!
state.tokenize[state.tokenize.length - 1].isBase) return 0;Ð     var
firstChar = textAfter && textAfter.charAt(0), ctx = state.context;Ð     if
(ctx.type == "statement" && !expectExpression(state.lastToken)) ctx =
ctx.prev;Ð     var closing = firstChar == ctx.type;Ð     if (ctx.type ==
"statement") {Ð       return ctx.indented + (firstChar == "{" ? 0 :
config.indentUnit);Ð     }Ð     else if (ctx.align) return ctx.column +
(closing ? 0 : 1);Ð     else return ctx.indented + (closing ? 0 :
config.indentUnit);Ð   },Ð   electricChars: "{}"Ð };Ð});Ð
CodeMirror.defineMIME("text/x-kotlin", "kotlin");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\livescript\livescript.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð**Ð* Link to the
project's GitHub page:Ð* https://github.com/duralog/CodeMirror Ð*/Ð
(function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð})
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode('livescript',
function(){Ð   var tokenBase = function(stream, state) {Ð     var next_rule =
state.next || "start";Ð     if (next_rule) {Ð       state.next = state.next;Ð
        var nr = Rules[next_rule];Ð       if (nr.splice) {Ð         for (var
i$ = 0; i$ < nr.length; ++i$) {Ð           var r = nr[i$], m;Ð           if
(r.regex && (m = stream.match(r.regex))) {Ð             state.next = r.next
|| state.next;Ð             return r.token;Ð           }Ð         }Ð
stream.next();Ð         return 'error';Ð       }Ð       if (stream.match(r =
Rules[next_rule])) {Ð         if (r.regex && stream.match(r.regex)) {Ð
            state.next = r.next;Ð           return r.token;Ð         } else {Ð
            stream.next();Ð           return 'error';Ð         }Ð       }Ð
      }Ð     stream.next();Ð     return 'error';Ð   };Ð   var external = {Ð
      startState: function(){Ð       return {Ð         next: 'start',Ð
          lastToken: nullÐ       };Ð     },Ð     token: function(stream,
state){Ð       while (stream.pos == stream.start)Ð         var style =
tokenBase(stream, state);Ð       state.lastToken = {Ð         style: style,Ð
          indent: stream.indentation(),Ð         content: stream.current()Ð
        };Ð       return style.replace(/\./g, ' ');Ð     },Ð     indent:
function(state){Ð       var indentation = state.lastToken.indent;Ð       if
(state.lastToken.content.match(indenter)) {Ð         indentation += 2;Ð
        }Ð       return indentation;Ð     }Ð   };Ð   return external;Ð });Ð
var identifier = '(?![\\d\\s])[$\\w\\xAA-\\uFFDC](?:(?!\\s)[$\\w\\xAA-\
\uFFDC]|-[A-Za-z])*';Ð var indenter = RegExp('(?:[({[=:]|[-~]>|\\b(?:e(?:lse|
xport)|d(?:o|efault)|t(?:ry|hen)|finally|import(?:\\s*all)?|const|var|let|new|
catch(?:\\s*' + identifier + ')?))\\s*$');Ð var keywordend = '(?![$\\w]|-[A-
Za-z]|\\s*:(?![:=]))';Ð var stringfill = {Ð   token: 'string',Ð   regex: '.+'Ð
  };Ð var Rules = {Ð   start: [Ð     {Ð       token: 'comment.doc',Ð
regex: '/\\*',Ð       next: 'comment'Ð     }, {Ð       token: 'comment',Ð
        regex: '#.*'Ð     }, {Ð       token: 'keyword',Ð       regex:
'(?:t(?:h(?:is|row|en)|ry|ypeof!?)|c(?:on(?:tinue|st)|a(?:se|tch)|lass)|
i(?:n(?:stanceof)?|mp(?:ort(?:\\s+all)?|lements)|[fs])|d(?:e(?:fault|lete|
bugger)|o)|f(?:or(?:\\s+own)?|inally|unction)|s(?:uper|witch)|e(?:lse|
x(?:tends|port)|val)|a(?:nd|rguments)|n(?:ew|ot)|un(?:less|til)|w(?:hile|ith)|
o[fr]|return|break|let|var|loop)' + keywordend Ð     }, {Ð       token:
'constant.language',Ð       regex: '(?:true|false|yes|no|on|off|null|void|
undefined)' + keywordend Ð     }, {Ð       token: 'invalid.illegal',Ð
regex: '(?:p(?:ackage|r(?:ivate|otected)|ublic)|i(?:mplements|nterface)|enum|
static|yield)' + keywordend Ð     }, {Ð       token: 'language.support.class',Ð
        regex: '(?:R(?:e(?:gExp|ferenceError)|angeError)|S(?:tring|
yntaxError)|E(?:rror|valError)|Array|Boolean|Date|Function|Number|Object|
TypeError|URIError)' + keywordend Ð     }, {Ð       token:
'language.support.function',Ð       regex: '(?:is(?:NaN|Finite)|parse(?:Int|
Float)|Math|JSON|(?:en|de)codeURI(?:Component)?)' + keywordend Ð     }, {Ð
        token: 'variable.language',Ð       regex: '(?:t(?:hat|il|o)|f(?:rom|
allthrough)|it|by|e)' + keywordend Ð     }, {Ð       token: 'identifier',Ð
        regex: identifier + '\\s*:(?![:=])'Ð     }, {Ð       token:
'variable',Ð       regex: identifier Ð     }, {Ð       token:
'keyword.operator',Ð       regex: '(?:\\.{3}|\\s+\\?)'Ð     }, {Ð
token: 'keyword.variable',Ð       regex: '(?:@+|::|\\.\\.)',Ð       next:
'key'Ð     }, {Ð       token: 'keyword.operator',Ð       regex: '\\.\\s*',Ð
        next: 'key'Ð     }, {Ð       token: 'string',Ð       regex: '\\\\\
\S[^\\s,;)}\\]]*'Ð
```

```
                        }, {Ð       token: 'string.doc',Ð       regex:
'\'\'\'',Ð       next: 'qdoc'Ð     }, {Ð       token: 'string.doc',Ð
regex: '"""',Ð       next: 'qqdoc'Ð     }, {Ð       token: 'string',Ð
regex: '\'',Ð       next: 'qstring'Ð     }, {Ð       token: 'string',Ð
regex: '"',Ð       next: 'qqstring'Ð     }, {Ð       token: 'string',Ð
regex: '`',Ð       next: 'js'Ð     }, {Ð       token: 'string',Ð       regex:
'<\\[',Ð       next: 'words'Ð     }, {Ð       token: 'string.regex',Ð
regex: '//',Ð       next: 'heregex'Ð     }, {Ð       token: 'string.regex',Ð
        regex: '\\/(?:[^[\\/\\n\\\\]*(?:(?:\\\\.|\\[[^\\]\\n\\\\]*(?:\\\\.[^\
\]\\n\\\\]*)*\\])[^[\\/\\n\\\\]*)*)\\/[gimy$]{0,4}',Ð       next: 'key'Ð
      }, {Ð       token: 'constant.numeric',Ð       regex: '(?:0x[\\da-fA-F][\
\da-fA-F_]*|(?:[2-9]|[12]\\d|3[0-6])r[\\da-zA-Z][\\da-zA-Z_]*|(?:\\d[\\d_]*(?:
\\.\\d[\\d_]*)?|\\.\\d[\\d_]*)(?:e[+-]?\\d[\\d_]*)?[\\w$]*)'Ð     }, {Ð
token: 'lparen',Ð       regex: '[({[]'Ð     }, {Ð       token: 'rparen',Ð
        regex: '[)}\\]]',Ð       next: 'key'Ð     }, {Ð       token:
'keyword.operator',Ð       regex: '\\S+'Ð     }, {Ð       token: 'text',Ð
        regex: '\\s+'Ð     }Ð   ],Ð   heregex: [Ð     {Ð       token:
'string.regex',Ð       regex: '.*?//[gimy$?]{0,4}',Ð       next: 'start'Ð
      }, {Ð       token: 'string.regex',Ð       regex: '\\s*#{'Ð     }, {Ð
        token: 'comment.regex',Ð       regex: '\\s+(?:#.*)?'Ð     }, {Ð
token: 'string.regex',Ð       regex: '\\S+'Ð     }Ð   ],Ð   key: [Ð     {Ð
        token: 'keyword.operator',Ð       regex: '[.?@!]+'Ð     }, {Ð
token: 'identifier',Ð       regex: identifier,Ð       next: 'start'Ð     }, {Ð
        token: 'text',Ð       regex: '',Ð       next: 'start'Ð     }Ð   ],Ð
comment: [Ð     {Ð       token: 'comment.doc',Ð       regex: '.*?\\*/',Ð
        next: 'start'Ð     }, {Ð       token: 'comment.doc',Ð       regex: '.
+'Ð     }Ð   ],Ð   qdoc: [Ð     {Ð       token: 'string',Ð       regex:
".*?''''",Ð       next: 'key'Ð     }, stringfillÐ   ],Ð   qqdoc: [Ð     {Ð
        token: 'string',Ð       regex: '.*?"""',Ð       next: 'key'Ð     },
stringfillÐ   ],Ð   qstring: [Ð     {Ð       token: 'string',Ð       regex:
'[^\\\\\\']*(?:\\\\.[^\\\\\\']*)*\'',Ð       next: 'key'Ð     }, stringfillÐ
    ],Ð   qqstring: [Ð     {Ð       token: 'string',Ð       regex: '[^\\\
\"]*(?:\\\\.[^\\\\\"]*)*"',Ð       next: 'key'Ð     }, stringfillÐ   ],Ð   js:
[Ð     {Ð       token: 'string',Ð       regex: '[^\\\\`]*(?:\\\\.[^\\\
\`]*)*`',Ð       next: 'key'Ð     }, stringfillÐ   ],Ð   words: [Ð     {Ð
        token: 'string',Ð       regex: '.*?\\]>',Ð       next: 'key'Ð     },
stringfillÐ   ]Ð };Ð for (var idx in Rules) {Ð   var r = Rules[idx];Ð   if
(r.splice) {Ð     for (var i = 0, len = r.length; i < len; ++i) {Ð       var
rr = r[i];Ð       if (typeof rr.regex === 'string') {Ð         Rules[idx]
[i].regex = new RegExp('^' + rr.regex);Ð       }Ð     }Ð   } else if (typeof
rr.regex === 'string') {Ð     Rules[idx].regex = new RegExp('^' + r.regex);Ð
    }Ð }Ð CodeMirror.defineMIME('text/x-livescript', 'livescript');Ð});Ð
```

public\assets\js\plugins\codemirror\mode\lua\lua.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ LUA mode. Ported to
CodeMirror 2 from Franciszek Wawrzak's Ð/ CodeMirror 1 mode. Ð/ highlights
keywords, strings, comments (no leveling supported! ("[==[")), tokens, basic
indenting Ð(function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð })
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("lua",
function(config, parserConfig) {Ð var indentUnit = config.indentUnit;Ð
function prefixRE(words) {Ð   return new RegExp("^(?:" + words.join("|") +
")", "i");Ð }Ð function wordRE(words) {Ð   return new RegExp("^(?:" +
words.join("|") + ")$", "i");Ð }Ð var specials = wordRE(parserConfig.specials
|| []);Ð // long list of standard functions from lua manual Ð var builtins =
wordRE([Ð   "_G","_VERSION","assert","collectgarbage","dofile","error","getfen
v","getmetatable","ipairs","load",Ð   "loadfile","loadstring","module","next",
"pairs","pcall","print","rawequal","rawget","rawset","require",Ð   "select","s
etfenv","setmetatable","tonumber","tostring","type","unpack","xpcall",Ð   "cor
outine.create","coroutine.resume","coroutine.running","coroutine.status","coro
utine.wrap","coroutine.yield",Ð   "debug.debug","debug.getfenv","debug.gethook
","debug.getinfo","debug.getlocal","debug.getmetatable",Ð   "debug.getregistry
","debug.getupvalue","debug.setfenv","debug.sethook","debug.setlocal","debug.s
etmetatable",Ð   "debug.setupvalue","debug.traceback",Ð
"close","flush","lines","read","seek","setvbuf","write",Ð   "io.close","io.flu
sh","io.input","io.lines","io.open","io.output","io.popen","io.read","io.stder
r","io.stdin",Ð   "io.stdout","io.tmpfile","io.type","io.write",Ð   "math.abs"
,"math.acos","math.asin","math.atan","math.atan2","math.ceil","math.cos","math
.cosh","math.deg",Ð   "math.exp","math.floor","math.fmod","math.frexp","math.h
uge","math.ldexp","math.log","math.log10","math.max",Ð   "math.min","math.modf
","math.pi","math.pow","math.rad","math.random","math.randomseed","math.sin","
math.sinh",Ð   "math.sqrt","math.tan","math.tanh",Ð   "os.clock","os.date","os
.difftime","os.execute","os.exit","os.getenv","os.remove","os.rename","os.setl
ocale",Ð   "os.time","os.tmpname",Ð   "package.cpath","package.loaded","packag
e.loaders","package.loadlib","package.path","package.preload",Ð
"package.seeall",Ð   "string.byte","string.char","string.dump","string.find","
string.format","string.gmatch","string.gsub",Ð   "string.len","string.lower","
string.match","string.rep","string.reverse","string.sub","string.upper",Ð
"table.concat","table.insert","table.maxn","table.remove","table.sort"Ð ]);Ð
var keywords =
wordRE(["and","break","elseif","false","nil","not","or","return",Ð
                        "true","function", "end", "if", "then", "else", "do",Ð
                        "while", "repeat", "until", "for", "in", "local" ]);Ð
  var indentTokens = wordRE(["function", "if","repeat","do", "\\(", "{"]);Ð
var dedentTokens = wordRE(["end", "until", "\\)", "}"]);Ð var dedentPartial =
prefixRE(["end", "until", "\\)", "}", "else", "elseif"]);Ð function
readBracket(stream) {Ð   var level = 0;Ð   while (stream.eat("=")) ++level;Ð
    stream.eat("[");Ð   return level;Ð }Ð function normal(stream, state) {Ð
var ch = stream.next();Ð   if (ch == "-" && stream.eat("-")) {Ð     if
(stream.eat("[") && stream.eat("["))Ð       return (state.cur =
bracketed(readBracket(stream), "comment"))(stream, state);Ð
stream.skipToEnd();Ð     return "comment";Ð   }Ð   if (ch == "\"" || ch ==
"'")Ð     return (state.cur = string(ch))(stream, state);Ð   if (ch == "["
&& /[\[=]/.test(stream.peek()))Ð     return (state.cur =
bracketed(readBracket(stream), "string"))(stream, state);Ð   if (/
\d/.test(ch)) {Ð     stream.eatWhile(/[\w.%]/);Ð     return "number";Ð   }Ð
if (/[\w_]/.test(ch)) {Ð     stream.eatWhile(/[\w\\\-_.]/);Ð     return
"variable";Ð   }Ð   return null;Ð }Ð function bracketed(level, style) {Ð
return function(stream, state) {Ð     var curlev = null, ch;Ð     while ((ch
= stream.next()) != null) {Ð
```

```
                                    if (curlev == null) {if (ch == "]") curlev
= 0;}Ð       else if (ch == "=") ++curlev;Ð       else if (ch == "]" &&
curlev == level) { state.cur = normal; break; }Ð       else curlev = null;Ð
      }Ð     return style;Ð   };Ð }Ð function string(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, ch;Ð     while ((ch =
stream.next()) != null) {Ð       if (ch == quote && !escaped) break;Ð
escaped = !escaped && ch == "\\";Ð     }Ð     if (!escaped) state.cur =
normal;Ð     return "string";Ð   };Ð }Ð return {Ð   startState:
function(basecol) {Ð     return {basecol: basecol || 0, indentDepth: 0, cur:
normal};Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     var style = state.cur(stream, state);Ð
      var word = stream.current();Ð     if (style == "variable") {Ð       if
(keywords.test(word)) style = "keyword";Ð       else if (builtins.test(word))
style = "builtin";Ð       else if (specials.test(word)) style = "variable-2";Ð
      }Ð     if ((style != "comment") && (style != "string")){Ð       if
(indentTokens.test(word)) ++state.indentDepth;Ð       else if
(dedentTokens.test(word)) --state.indentDepth;Ð     }Ð     return style;Ð   },Ð
    indent: function(state, textAfter) {Ð     var closing =
dedentPartial.test(textAfter);Ð     return state.basecol + indentUnit *
(state.indentDepth - (closing ? 1 : 0));Ð   },Ð   lineComment: "--",Ð
blockCommentStart: "--[[",Ð   blockCommentEnd: "]]"Ð };Ð});Ð
CodeMirror.defineMIME("text/x-lua", "lua");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\markdown\markdown.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror", require("../xml/xml")));Ð else if (typeof
define == "function" && define.amd) // AMD Ð   define(["../../lib/codemirror",
"../xml/xml"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð })
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("markdown",
function(cmCfg, modeCfg) {Ð var htmlFound =
CodeMirror.modes.hasOwnProperty("xml");Ð var htmlMode =
CodeMirror.getMode(cmCfg, htmlFound ? {name: "xml", htmlMode: true} : "text/
plain");Ð var aliases = {Ð   html: "htmlmixed",Ð   js: "javascript",Ð   json:
"application/json",Ð   c: "text/x-csrc",Ð   "c++": "text/x-c++src",Ð   java:
"text/x-java",Ð   csharp: "text/x-csharp",Ð   "c#": "text/x-csharp",Ð
scala: "text/x-scala"Ð };Ð var getMode = (function () {Ð   var i, modes = {},
mimes = {}, mime;Ð   var list = [];Ð   for (var m in CodeMirror.modes)Ð
if (CodeMirror.modes.propertyIsEnumerable(m)) list.push(m);Ð   for (i = 0; i
< list.length; i++) {Ð     modes[list[i]] = list[i];Ð   }Ð   var mimesList =
[];Ð   for (var m in CodeMirror.mimeModes)Ð     if
(CodeMirror.mimeModes.propertyIsEnumerable(m))Ð       mimesList.push({mime:
m, mode: CodeMirror.mimeModes[m]});Ð   for (i = 0; i < mimesList.length; i++)
{Ð     mime = mimesList[i].mime;Ð     mimes[mime] = mimesList[i].mime;Ð   }Ð
    for (var a in aliases) {Ð     if (aliases[a] in modes || aliases[a] in
mimes)Ð       modes[a] = aliases[a];Ð   }Ð   return function (lang) {Ð
return modes[lang] ? CodeMirror.getMode(cmCfg, modes[lang]) : null;Ð   };Ð }
());Ð // Should characters that affect highlighting be highlighted separate?Ð
  // Does not include characters that will be output (such as `1.` and `-`
for lists)Ð if (modeCfg.highlightFormatting === undefined)Ð
modeCfg.highlightFormatting = false;Ð // Maximum number of nested
blockquotes. Set to 0 for infinite nesting.Ð // Excess `>` will emit `error`
token.Ð if (modeCfg.maxBlockquoteDepth === undefined)Ð
modeCfg.maxBlockquoteDepth = 0;Ð // Should underscores in words open/close em/
strong?Ð if (modeCfg.underscoresBreakWords === undefined)Ð
modeCfg.underscoresBreakWords = true;Ð // Turn on fenced code blocks? ("```"
to start/end)Ð if (modeCfg.fencedCodeBlocks === undefined)
modeCfg.fencedCodeBlocks = false;Ð // Turn on task lists? ("- [ ] " and "-
[x] ")Ð if (modeCfg.taskLists === undefined) modeCfg.taskLists = false;Ð var
codeDepth = 0;Ð var header   = 'header'Ð ,   code     = 'comment'Ð ,
quote    = 'quote'Ð ,   list1    = 'variable-2'Ð ,   list2    = 'variable-3'Ð
  ,   list3    = 'keyword'Ð ,   hr       = 'hr'Ð ,   image    = 'tag'Ð ,
formatting = 'formatting'Ð ,   linkinline = 'link'Ð ,   linkemail = 'link'Ð
  ,   linktext = 'link'Ð ,   linkhref = 'string'Ð ,   em       = 'em'Ð ,
strong   = 'strong';Ð var hrRE = /^([*\-=_])(?:\s*\1){2,}\s*$/Ð ,   ulRE = /
^[*\-+]\s+/Ð ,   olRE = /^[0-9]+\.\s+/Ð ,   taskListRE = /^\[(x| )\](?
=\s)/ // Must follow ulRE or olRE Ð ,   atxHeaderRE = /^#+/Ð ,
setextHeaderRE = /^(?:\={1,}|-{1,})$/Ð ,   textRE = /^[^#!\[\]*_\\<>` "'(]+/;Ð
  function switchInline(stream, state, f) {Ð   state.f = state.inline = f;Ð
return f(stream, state);Ð }Ð function switchBlock(stream, state, f) {Ð
state.f = state.block = f;Ð   return f(stream, state);Ð }Ð // BlocksÐ
function blankLine(state) {Ð   // Reset linkTitle stateÐ   state.linkTitle =
false;Ð   // Reset EM stateÐ   state.em = false;Ð   // Reset STRONG stateÐ
state.strong = false;Ð   // Reset state.quoteÐ   state.quote = 0;Ð   if (!
htmlFound && state.f == htmlBlock) {Ð     state.f = inlineNormal;Ð
state.block = blockNormal;Ð   }Ð   // Reset state.trailingSpaceÐ
state.trailingSpace = 0;Ð   state.trailingSpaceNewLine = false;Ð   // Mark
this line as blankÐ   state.thisLineHasContent = false;Ð   return null;Ð }Ð
function blockNormal(stream, state) {Ð   var sol = stream.sol();Ð   var
prevLineIsList = (state.list !== false);Ð   if (state.list !== false &&
state.indentationDiff >= 0) { // Continued listÐ     if
(state.indentationDiff < 4) { // Only adjust indentation if *not* a code blockÐ
```

```
        state.indentation -= state.indentationDiff;Ð     }Ð     state.list =
null;Ð   } else if (state.list !== false && state.indentation > 0) {Ð
state.list = null;Ð     state.listDepth = Math.floor(state.indentation / 4);Ð
    } else if (state.list !== false) { // No longer a listÐ     state.list =
false;Ð     state.listDepth = 0;Ð   }Ð   var match = null;Ð   if
(state.indentationDiff >= 4) {Ð     state.indentation -= 4;Ð
stream.skipToEnd();Ð     return code;Ð   } else if (stream.eatSpace()) {Ð
return null;Ð   } else if (match = stream.match(atxHeaderRE)) {Ð
state.header = match[0].length <= 6 ? match[0].length : 6;Ð     if
(modeCfg.highlightFormatting) state.formatting = "header";Ð     state.f =
state.inline;Ð     return getType(state);Ð   } else if
(state.prevLineHasContent && (match = stream.match(setextHeaderRE))) {Ð
state.header = match[0].charAt(0) == '=' ? 1 : 2;Ð     if
(modeCfg.highlightFormatting) state.formatting = "header";Ð     state.f =
state.inline;Ð     return getType(state);Ð   } else if (stream.eat('>')) {Ð
      state.indentation++;Ð     state.quote = sol ? 1 : state.quote + 1;Ð
if (modeCfg.highlightFormatting) state.formatting = "quote";Ð
stream.eatSpace();Ð     return getType(state);Ð   } else if (stream.peek()
=== '[') {Ð     return switchInline(stream, state, footnoteLink);Ð   } else
if (stream.match(hrRE, true)) {Ð     return hr;Ð   } else if ((!
state.prevLineHasContent || prevLineIsList) && (stream.match(ulRE, false) ||
stream.match(olRE, false))) {Ð     var listType = null;Ð     if
(stream.match(ulRE, true)) {Ð       listType = 'ul';Ð     } else {Ð
stream.match(olRE, true);Ð       listType = 'ol';Ð     }Ð
state.indentation += 4;Ð     state.list = true;Ð     state.listDepth++;Ð
if (modeCfg.taskLists && stream.match(taskListRE, false)) {Ð
state.taskList = true;Ð     }Ð     state.f = state.inline;Ð     if
(modeCfg.highlightFormatting) state.formatting = ["list", "list-" + listType];Ð
      return getType(state);Ð   } else if (modeCfg.fencedCodeBlocks &&
stream.match(/^```([\w+#]*)/, true)) {Ð     // try switching modeÐ
state.localMode = getMode(RegExp.$1);Ð     if (state.localMode)
state.localState = state.localMode.startState();Ð     switchBlock(stream,
state, local);Ð     if (modeCfg.highlightFormatting) state.formatting = "code-
block";Ð     state.code = true;Ð     return getType(state);Ð   }Ð   return
switchInline(stream, state, state.inline);Ð }Ð function htmlBlock(stream,
state) {Ð   var style = htmlMode.token(stream, state.htmlState);Ð   if
((htmlFound && state.htmlState.tagStart === null && !state.htmlState.context)
||Ð       (state.md_inside && stream.current().indexOf(">") > -1)) {Ð
state.f = inlineNormal;Ð     state.block = blockNormal;Ð     state.htmlState
= null;Ð   }Ð   return style;Ð }Ð function local(stream, state) {Ð   if
(stream.sol() && stream.match(/^```/, true)) {Ð     state.localMode =
state.localState = null;Ð     state.f = inlineNormal;Ð     state.block =
blockNormal;Ð     if (modeCfg.highlightFormatting) state.formatting = "code-
block";Ð     state.code = true;Ð     var returnType = getType(state);Ð
state.code = false;Ð     return returnType;Ð   } else if (state.localMode) {Ð
      return state.localMode.token(stream, state.localState);Ð   } else {Ð
      stream.skipToEnd();Ð     return code;Ð   }Ð }Ð // InlineÐ function
getType(state) {Ð   var styles = [];Ð   if (state.formatting) {Ð
styles.push(formatting);Ð     if (typeof state.formatting === "string")
state.formatting = [state.formatting];Ð     for (var i = 0; i <
state.formatting.length; i++) {Ð       styles.push(formatting + "-" +
state.formatting[i]);Ð       if (state.formatting[i] === "header") {Ð
styles.push(formatting + "-" + state.formatting[i] + "-" + state.header);Ð
        }Ð       // Add `formatting-quote` and `formatting-quote-#` for
blockquotesÐ       // Add `error` instead if the maximum blockquote nesting
depth is passedÐ       if (state.formatting[i] === "quote") {Ð         if (!
modeCfg.maxBlockquoteDepth || modeCfg.maxBlockquoteDepth >= state.quote) {Ð
            styles.push(formatting + "-" + state.formatting[i] + "-" +
state.quote);Ð
```

```
                        } else {Ð           styles.push("error");Ð         }Ð
        }Ð     }Ð   }Ð   if (state.taskOpen) {Ð     styles.push("meta");Ð
return styles.length ? styles.join(' ') : null;Ð   }Ð   if (state.taskClosed)
{Ð     styles.push("property");Ð     return styles.length ? styles.join('
') : null;Ð   }Ð   if (state.linkHref) {Ð     styles.push(linkhref);Ð
return styles.length ? styles.join(' ') : null;Ð   }Ð   if (state.strong)
{ styles.push(strong); }Ð   if (state.em) { styles.push(em); }Ð   if
(state.linkText) { styles.push(linktext); }Ð   if (state.code)
{ styles.push(code); }Ð   if (state.header) { styles.push(header);
styles.push(header + "-" + state.header); }Ð   if (state.quote) {Ð
styles.push(quote);Ð     // Add `quote-#` where the maximum for `#` is
modeCfg.maxBlockquoteDepthÐ     if (!modeCfg.maxBlockquoteDepth ||
modeCfg.maxBlockquoteDepth >= state.quote) {Ð       styles.push(quote + "-" +
state.quote);Ð     } else {Ð       styles.push(quote + "-" +
modeCfg.maxBlockquoteDepth);Ð     }Ð   }Ð   if (state.list !== false) {Ð
var listMod = (state.listDepth - 1) % 3;Ð     if (!listMod) {Ð
styles.push(list1);Ð     } else if (listMod === 1) {Ð
styles.push(list2);Ð     } else {Ð       styles.push(list3);Ð     }Ð   }Ð
if (state.trailingSpaceNewLine) {Ð     styles.push("trailing-space-new-line");Ð
    } else if (state.trailingSpace) {Ð     styles.push("trailing-space-" +
(state.trailingSpace % 2 ? "a" : "b"));Ð   }Ð   return styles.length ?
styles.join(' ') : null;Ð }Ð function handleText(stream, state) {Ð   if
(stream.match(textRE, true)) {Ð     return getType(state);Ð   }Ð   return
undefined;Ð }Ð function inlineNormal(stream, state) {Ð   var style =
state.text(stream, state);Ð   if (typeof style !== 'undefined')Ð     return
style;Ð   if (state.list) { // List marker (*, +, -, 1., etc)Ð     state.list
= null;Ð     return getType(state);Ð   }Ð   if (state.taskList) {Ð     var
taskOpen = stream.match(taskListRE, true)[1] !== "x";Ð     if (taskOpen)
state.taskOpen = true;Ð     else state.taskClosed = true;Ð     if
(modeCfg.highlightFormatting) state.formatting = "task";Ð     state.taskList
= false;Ð     return getType(state);Ð   }Ð   state.taskOpen = false;Ð
state.taskClosed = false;Ð   if (state.header && stream.match(/^#+$/, true)) {Ð
      if (modeCfg.highlightFormatting) state.formatting = "header";Ð
return getType(state);Ð   }Ð   // Get sol() value now, before character is
consumedÐ   var sol = stream.sol();Ð   var ch = stream.next();Ð   if (ch ===
'\\') {Ð     stream.next();Ð     if (modeCfg.highlightFormatting) {Ð
var type = getType(state);Ð       return type ? type + " formatting-escape" :
"formatting-escape";Ð     }Ð   }Ð   // Matches link titles present on next
lineÐ   if (state.linkTitle) {Ð     state.linkTitle = false;Ð     var matchCh
= ch;Ð     if (ch === '(') {Ð       matchCh = ')';Ð     }Ð     matchCh =
(matchCh+'').replace(/([.?*+^$[\]\\(){}|-])/g, "\\$1");Ð     var regex = '^\
\s*(?:[^' + matchCh + '\\\\]+|\\\\\\\\|\\\\.)' + matchCh;Ð     if
(stream.match(new RegExp(regex), true)) {Ð       return linkhref;Ð     }Ð   }Ð
    // If this block is changed, it may need to be updated in GFM modeÐ   if
(ch === '`') {Ð     var previousFormatting = state.formatting;Ð     if
(modeCfg.highlightFormatting) state.formatting = "code";Ð     var t =
getType(state);Ð     var before = stream.pos;Ð     stream.eatWhile('`');Ð
var difference = 1 + stream.pos - before;Ð     if (!state.code) {Ð
codeDepth = difference;Ð       state.code = true;Ð       return
getType(state);Ð     } else {Ð       if (difference === codeDepth) { // Must
be exactÐ         state.code = false;Ð         return t;Ð       }Ð
state.formatting = previousFormatting;Ð       return getType(state);Ð     }Ð
    } else if (state.code) {Ð     return getType(state);Ð   }Ð   if (ch ===
'!' && stream.match(/\[[^\]]*\] ?(?:\(|\[)/, false)) {Ð     stream.match(/
\[[^\]]*\]/);Ð     state.inline = state.f = linkHref;Ð     return image;Ð   }Ð
    if (ch === '[' && stream.match(/.*\](\(| ?\[)/, false)) {Ð
state.linkText = true;Ð     if (modeCfg.highlightFormatting) state.formatting
= "link";Ð     return getType(state);Ð   }Ð   if (ch === ']' &&
state.linkText) {Ð     if (modeCfg.highlightFormatting) state.formatting =
"link";Ð
```

```
            var type = getType(state);Ð     state.linkText = false;Ð
state.inline = state.f = linkHref;Ð     return type;Ð   }Ð   if (ch === '<'
&& stream.match(/^(https?|ftps?):\/\/(?:[^\\>]|\\.)+>/, false)) {Ð
state.f = state.inline = linkInline;Ð     if (modeCfg.highlightFormatting)
state.formatting = "link";Ð     var type = getType(state);Ð     if (type){Ð
        type += " ";Ð     } else {Ð       type = "";Ð     }Ð     return type
+ linkinline;Ð   }Ð   if (ch === '<' && stream.match(/^[^> \\]+@(?:[^\\>]|\
\.)+>/, false)) {Ð     state.f = state.inline = linkInline;Ð     if
(modeCfg.highlightFormatting) state.formatting = "link";Ð     var type =
getType(state);Ð     if (type){Ð       type += " ";Ð     } else {Ð       type
= "";Ð     }Ð     return type + linkemail;Ð   }Ð   if (ch === '<' &&
stream.match(/^\w/, false)) {Ð     if (stream.string.indexOf(">") != -1) {Ð
        var atts = stream.string.substring(1,stream.string.indexOf(">"));Ð
        if (/markdown\s*=\s*('|"){0,1}1('|"){0,1}/.test(atts)) {Ð
state.md_inside = true;Ð       }Ð     }Ð     stream.backUp(1);Ð
state.htmlState = CodeMirror.startState(htmlMode);Ð     return
switchBlock(stream, state, htmlBlock);Ð   }Ð   if (ch === '<' &&
stream.match(/^\/\w*?>/)) {Ð     state.md_inside = false;Ð     return "tag";Ð
    }Ð   var ignoreUnderscore = false;Ð   if (!modeCfg.underscoresBreakWords)
{Ð     if (ch === '_' && stream.peek() !== '_' && stream.match(/(\w)/,
false)) {Ð       var prevPos = stream.pos - 2;Ð       if (prevPos >= 0) {Ð
          var prevCh = stream.string.charAt(prevPos);Ð         if (prevCh !==
'_' && prevCh.match(/(\w)/, false)) {Ð           ignoreUnderscore = true;Ð
          }Ð       }Ð     }Ð   }Ð   if (ch === '*' || (ch === '_' && !
ignoreUnderscore)) {Ð     if (sol && stream.peek() === ' ') {Ð       // Do
nothing, surrounded by newline and spaceÐ     } else if (state.strong === ch
&& stream.eat(ch)) { // Remove STRONGÐ       if (modeCfg.highlightFormatting)
state.formatting = "strong";Ð       var t = getType(state);Ð
state.strong = false;Ð       return t;Ð     } else if (!state.strong &&
stream.eat(ch)) { // Add STRONGÐ       state.strong = ch;Ð       if
(modeCfg.highlightFormatting) state.formatting = "strong";Ð       return
getType(state);Ð     } else if (state.em === ch) { // Remove EMÐ       if
(modeCfg.highlightFormatting) state.formatting = "em";Ð       var t =
getType(state);Ð       state.em = false;Ð       return t;Ð     } else if (!
state.em) { // Add EMÐ       state.em = ch;Ð       if
(modeCfg.highlightFormatting) state.formatting = "em";Ð       return
getType(state);Ð     }Ð   } else if (ch === ' ') {Ð     if (stream.eat('*')
|| stream.eat('_')) { // Probably surrounded by spacesÐ       if
(stream.peek() === ' ') { // Surrounded by spaces, ignoreÐ         return
getType(state);Ð       } else { // Not surrounded by spaces, back up pointerÐ
          stream.backUp(1);Ð       }Ð     }Ð   }Ð   if (ch === ' ') {Ð     if
(stream.match(/ +$/, false)) {Ð       state.trailingSpace++;Ð     } else if
(state.trailingSpace) {Ð       state.trailingSpaceNewLine = true;Ð     }Ð   }Ð
    return getType(state);Ð }Ð function linkInline(stream, state) {Ð   var ch
= stream.next();Ð   if (ch === ">") {Ð     state.f = state.inline =
inlineNormal;Ð     if (modeCfg.highlightFormatting) state.formatting = "link";Ð
      var type = getType(state);Ð     if (type){Ð       type += " ";Ð     }
else {Ð       type = "";Ð     }Ð     return type + linkinline;Ð   }Ð
stream.match(/^[^>]+/, true);Ð   return linkinline;Ð }Ð function
linkHref(stream, state) {Ð   // Check if space, and return NULL if so (to
avoid marking the space)Ð   if(stream.eatSpace()){Ð     return null;Ð   }Ð
var ch = stream.next();Ð   if (ch === '(' || ch === '[') {Ð     state.f =
state.inline = getLinkHrefInside(ch === "(" ? ")" : "]");Ð     if
(modeCfg.highlightFormatting) state.formatting = "link-string";Ð
state.linkHref = true;Ð     return getType(state);Ð   }Ð   return 'error';Ð }Ð
  function getLinkHrefInside(endChar) {Ð   return function(stream, state) {Ð
      var ch = stream.next();Ð     if (ch === endChar) {Ð       state.f =
state.inline = inlineNormal;Ð       if (modeCfg.highlightFormatting)
state.formatting = "link-string";Ð       var returnState = getType(state);Ð
        state.linkHref = false;Ð
```

```
                                        return returnState;Ð     }Ð     if
(stream.match(inlineRE(endChar), true)) {Ð       stream.backUp(1);Ð     }Ð
      state.linkHref = true;Ð     return getType(state);Ð   };Ð }Ð function
footnoteLink(stream, state) {Ð   if (stream.match(/^[^\]]*\]:/, false)) {Ð
      state.f = footnoteLinkInside;Ð     stream.next(); // Consume [Ð     if
(modeCfg.highlightFormatting) state.formatting = "link";Ð     state.linkText
= true;Ð     return getType(state);Ð   }Ð   return switchInline(stream,
state, inlineNormal);Ð }Ð function footnoteLinkInside(stream, state) {Ð   if
(stream.match(/^\]:/, true)) {Ð     state.f = state.inline = footnoteUrl;Ð
      if (modeCfg.highlightFormatting) state.formatting = "link";Ð     var
returnType = getType(state);Ð     state.linkText = false;Ð     return
returnType;Ð   }Ð   stream.match(/^[^\]]+/, true);Ð   return linktext;Ð }Ð
function footnoteUrl(stream, state) {Ð   // Check if space, and return NULL
if so (to avoid marking the space)Ð   if(stream.eatSpace()){Ð     return null;Ð
    }Ð   // Match URLÐ   stream.match(/^[^\s]+/, true);Ð   // Check for link
titleÐ   if (stream.peek() === undefined) { // End of line, set flag to check
next lineÐ     state.linkTitle = true;Ð   } else { // More content on line,
check if link titleÐ     stream.match(/^(?:\s+(?:"(?:[^"\\]|\\\\|\\.)+"|'(?:
[^'\\]|\\\\|\\.)+'|\((?:[^)\\]|\\\\|\\.)+\)))?/, true);Ð   }Ð   state.f =
state.inline = inlineNormal;Ð   return linkhref;Ð }Ð var savedInlineRE = [];Ð
function inlineRE(endChar) {Ð   if (!savedInlineRE[endChar]) {Ð     // Escape
endChar for RegExp (taken from http://stackoverflow.com/a/494122/526741)Ð
endChar = (endChar+'').replace(/([.?*+^$[\]\\(){}|-])/g, "\\$1");Ð     //
Match any non-endChar, escaped character, as well as the closingÐ     //
endChar.Ð     savedInlineRE[endChar] = new RegExp('^(?:[^\\\\]|\\\\.)*?(' +
endChar + ')');Ð   }Ð   return savedInlineRE[endChar];Ð }Ð var mode = {Ð
startState: function() {Ð     return {Ð       f: blockNormal,Ð
prevLineHasContent: false,Ð       thisLineHasContent: false,Ð       block:
blockNormal,Ð       htmlState: null,Ð       indentation: 0,Ð       inline:
inlineNormal,Ð       text: handleText,Ð       formatting: false,Ð
linkText: false,Ð       linkHref: false,Ð       linkTitle: false,Ð       em:
false,Ð       strong: false,Ð       header: 0,Ð       taskList: false,Ð
list: false,Ð       listDepth: 0,Ð       quote: 0,Ð       trailingSpace: 0,Ð
        trailingSpaceNewLine: falseÐ     };Ð   },Ð   copyState: function(s) {Ð
      return {Ð       f: s.f,Ð       prevLineHasContent: s.prevLineHasContent,Ð
        thisLineHasContent: s.thisLineHasContent,Ð       block: s.block,Ð
        htmlState: s.htmlState && CodeMirror.copyState(htmlMode, s.htmlState),Ð
        indentation: s.indentation,Ð       localMode: s.localMode,Ð
localState: s.localMode ? CodeMirror.copyState(s.localMode, s.localState) :
null,Ð       inline: s.inline,Ð       text: s.text,Ð       formatting: false,Ð
        linkTitle: s.linkTitle,Ð       em: s.em,Ð       strong: s.strong,Ð
        header: s.header,Ð       taskList: s.taskList,Ð       list: s.list,Ð
        listDepth: s.listDepth,Ð       quote: s.quote,Ð       trailingSpace:
s.trailingSpace,Ð       trailingSpaceNewLine: s.trailingSpaceNewLine,Ð
md_inside: s.md_insideÐ     };Ð   },Ð   token: function(stream, state) {Ð
      // Reset state.formattingÐ     state.formatting = false;Ð     if
(stream.sol()) {Ð       var forceBlankLine = !!state.header;Ð       // Reset
state.headerÐ       state.header = 0;Ð       if (stream.match(/^\s*$/, true)
|| forceBlankLine) {Ð         state.prevLineHasContent = false;Ð
blankLine(state);Ð         return forceBlankLine ? this.token(stream,
state) : null;Ð       } else {Ð         state.prevLineHasContent =
state.thisLineHasContent;Ð         state.thisLineHasContent = true;Ð       }Ð
        // Reset state.taskListÐ       state.taskList = false;Ð       //
Reset state.codeÐ       state.code = false;Ð       // Reset
state.trailingSpaceÐ       state.trailingSpace = 0;Ð
state.trailingSpaceNewLine = false;Ð       state.f = state.block;Ð       var
indentation = stream.match(/^\s*/, true)[0].replace(/\t/g, '    ').length;Ð
        var difference = Math.floor((indentation - state.indentation) / 4) *
4;Ð       if (difference > 4) difference = 4;Ð       var adjustedIndentation
= state.indentation + difference;Ð
```

```
                                        state.indentationDiff =
adjustedIndentation - state.indentation;Ð       state.indentation =
adjustedIndentation;Ð       if (indentation > 0) return null;Ð     }Ð     var
result = state.f(stream, state);Ð     if (stream.start == stream.pos) return
this.token(stream, state);Ð     else return result;Ð   },Ð   innerMode:
function(state) {Ð     if (state.block == htmlBlock) return {state:
state.htmlState, mode: htmlMode};Ð     if (state.localState) return {state:
state.localState, mode: state.localMode};Ð     return {state: state, mode:
mode};Ð   },Ð   blankLine: blankLine,Ð   getType: getType,Ð   fold: "markdown"Ð
  };Ð return mode;Ð, "xml");ÐodeMirror.defineMIME("text/x-markdown",
"markdown");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\markdown\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ðfunction() {Ð var mode =
CodeMirror.getMode({tabSize: 4}, "markdown");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð var
modeHighlightFormatting = CodeMirror.getMode({tabSize: 4}, {name: "markdown",
highlightFormatting: true});Ð function FT(name) { test.mode(name,
modeHighlightFormatting, Array.prototype.slice.call(arguments, 1)); }Ð
FT("formatting_emAsterisk",Ð    "[em&formatting&formatting-em *][em foo]
[em&formatting&formatting-em *]");Ð FT("formatting_emUnderscore",Ð
"[em&formatting&formatting-em _][em foo][em&formatting&formatting-em _]");Ð
FT("formatting_strongAsterisk",Ð    "[strong&formatting&formatting-strong **]
[strong foo][strong&formatting&formatting-strong **]");Ð
FT("formatting_strongUnderscore",Ð    "[strong&formatting&formatting-strong
__][strong foo][strong&formatting&formatting-strong __]");Ð
FT("formatting_codeBackticks",Ð    "[comment&formatting&formatting-code `]
[comment foo][comment&formatting&formatting-code `]");Ð
FT("formatting_doubleBackticks",Ð    "[comment&formatting&formatting-code ``]
[comment foo ` bar][comment&formatting&formatting-code ``]");Ð
FT("formatting_atxHeader",Ð    "[header&header-1&formatting&formatting-
header&formatting-header-1 #][header&header-1  foo # bar ]
[header&header-1&formatting&formatting-header&formatting-header-1 #]");Ð
FT("formatting_setextHeader",Ð    "foo",Ð
"[header&header-1&formatting&formatting-header&formatting-header-1 =]");Ð
FT("formatting_blockquote",Ð    "[quote&quote-1&formatting&formatting-
quote&formatting-quote-1 > ][quote&quote-1 foo]");Ð FT("formatting_list",Ð
"[variable-2&formatting&formatting-list&formatting-list-ul - ][variable-2
foo]");Ð FT("formatting_list",Ð    "[variable-2&formatting&formatting-
list&formatting-list-ol 1. ][variable-2 foo]");Ð FT("formatting_link",Ð
"[link&formatting&formatting-link [][link foo][link&formatting&formatting-
link ]]][string&formatting&formatting-link-string (][string http://
example.com/][string&formatting&formatting-link-string )]");Ð
FT("formatting_linkReference",Ð    "[link&formatting&formatting-link [][link
foo][link&formatting&formatting-link ]]][string&formatting&formatting-link-
string [][string bar][string&formatting&formatting-link-string ]]]",Ð
"[link&formatting&formatting-link [][link bar][link&formatting&formatting-
link ]]:] [string http://example.com/]");Ð FT("formatting_linkWeb",Ð
"[link&formatting&formatting-link <][link http://example.com/]
[link&formatting&formatting-link >]");Ð FT("formatting_linkEmail",Ð
"[link&formatting&formatting-link <][link user@example.com]
[link&formatting&formatting-link >]");Ð FT("formatting_escape",Ð
"[formatting-escape \\*]");Ð MT("plainText",Ð    "foo");Ð // Don't style
single trailing spaceÐ MT("trailingSpace1",Ð    "foo ");Ð // Two or more
trailing spaces should be styled with line break characterÐ
MT("trailingSpace2",Ð    "foo[trailing-space-a  ][trailing-space-new-
line  ]");Ð MT("trailingSpace3",Ð    "foo[trailing-space-a  ][trailing-space-
b  ][trailing-space-new-line  ]");Ð MT("trailingSpace4",Ð    "foo[trailing-
space-a  ][trailing-space-b  ][trailing-space-a  ][trailing-space-new-
line  ]");Ð // Code blocks using 4 spaces (regardless of CodeMirror.tabSize
value)Ð MT("codeBlocksUsing4Spaces",Ð    "    [comment foo]");Ð // Code
blocks using 4 spaces with internal indentationÐ
MT("codeBlocksUsing4SpacesIndentation",Ð    "    [comment bar]",Ð
"        [comment hello]",Ð    "            [comment world]",Ð
"    [comment foo]",Ð    "bar");Ð // Code blocks using 4 spaces with internal
indentationÐ MT("codeBlocksUsing4SpacesIndentation",Ð    " foo",Ð
"    [comment bar]",Ð    "        [comment hello]",Ð    "    [comment
world]");Ð // Code blocks should end even after extra indented linesÐ
MT("codeBlocksWithTrailingIndentedLine",Ð    "    [comment foo]",Ð
"        [comment bar]",Ð    "    [comment baz]",Ð    "    ",Ð    "hello");Ð
  // Code blocks using 1 tab (regardless of CodeMirror.indentWithTabs value)Ð
```

MT("codeBlocksUsing1Tab",Ð "\t[comment foo]");Ð // Inline code using backticksÐ MT("inlineCodeUsingBackticks",Ð "foo [comment `bar`]");Ð // Block code using single backtick (shouldn't work)Ð MT("blockCodeSingleBacktick",Ð "[comment `]",Ð "foo",Ð "[comment `]");Ð // Unclosed backticksÐ // Instead of simply marking as CODE, it would be nice to have anÐ // incomplete flag for CODE, that is styled slightly different.Ð MT("unclosedBackticks",Ð "foo [comment `bar]");Ð // Per documentation: "To include a literal backtick character within aÐ // code span, you can use multiple backticks as the opening and closingÐ // delimiters"Ð MT("doubleBackticks",Ð "[comment ``foo ` bar``]");Ð // Tests based on DingusÐ // http://daringfireball.net/projects/markdown/dingusÐ //Ð // Multiple backticks within an inline code blockÐ MT("consecutiveBackticks",Ð "[comment `foo```bar`]");Ð // Multiple backticks within an inline code block with a second code blockÐ MT("consecutiveBackticks",Ð "[comment `foo```bar`] hello [comment `world`]");Ð // Unclosed with several different groups of backticksÐ MT("unclosedBackticks",Ð "[comment ``foo ``` bar` hello]");Ð // Closed with several different groups of backticksÐ MT("closedBackticks",Ð "[comment ``foo ``` bar` hello``] world");Ð // atx headersÐ // http://daringfireball.net/projects/markdown/syntax#headerÐ MT("atxH1",Ð "[header&header-1 # foo]");Ð MT("atxH2",Ð "[header&header-2 ## foo]");Ð MT("atxH3",Ð "[header&header-3 ### foo]");Ð MT("atxH4",Ð "[header&header-4 #### foo]");Ð MT("atxH5",Ð "[header&header-5 ##### foo]");Ð MT("atxH6",Ð "[header&header-6 ###### foo]");Ð // H6 - 7x '#' should still be H6, per DingusÐ // http://daringfireball.net/projects/markdown/dingusÐ MT("atxH6NotH7",Ð "[header&header-6 ####### foo]");Ð // Inline styles should be parsed inside headersÐ MT("atxH1inline",Ð "[header&header-1 # foo][header&header-1&em *bar*]");Ð // Setext headers - H1, H2Ð // Per documentation, "Any number of underlining =’s or -’s will work."Ð // http://daringfireball.net/projects/markdown/syntax#headerÐ // Ideally, the text would be marked as `header` as well, but this isÐ // not really feasible at the moment. So, instead, we're testing againstÐ // what works today, to avoid any regressions.Ð //Ð // Check if single underlining = worksÐ MT("setextH1",Ð "foo",Ð "[header&header-1 =]");Ð // Check if 3+ ='s workÐ MT("setextH1",Ð "foo",Ð "[header&header-1 ===]");Ð // Check if single underlining - worksÐ MT("setextH2",Ð "foo",Ð "[header&header-2 -]");Ð // Check if 3+ -'s workÐ MT("setextH2",Ð "foo",Ð "[header&header-2 ---]");Ð // Single-line blockquote with trailing spaceÐ MT("blockquoteSpace",Ð "[quote&quote-1 > foo]");Ð // Single-line blockquoteÐ MT("blockquoteNoSpace",Ð "[quote&quote-1 >foo]");Ð // No blank line before blockquoteÐ MT("blockquoteNoBlankLine",Ð "foo",Ð "[quote&quote-1 > bar]");Ð // Nested blockquoteÐ MT("blockquoteSpace",Ð "[quote&quote-1 > foo]",Ð "[quote&quote-1 >][quote&quote-2 > foo]",Ð "[quote&quote-1 >][quote&quote-2 >][quote&quote-3 > foo]");Ð // Single-line blockquote followed by normal paragraphÐ MT("blockquoteThenParagraph",Ð "[quote&quote-1 >foo]",Ð "",Ð "bar");Ð // Multi-line blockquote (lazy mode)Ð MT("multiBlockquoteLazy",Ð "[quote&quote-1 >foo]",Ð "[quote&quote-1 bar]");Ð // Multi-line blockquote followed by normal paragraph (lazy mode)Ð MT("multiBlockquoteLazyThenParagraph",Ð "[quote&quote-1 >foo]",Ð "[quote&quote-1 bar]",Ð "",Ð "hello");Ð // Multi-line blockquote (non-lazy mode)Ð MT("multiBlockquote",Ð "[quote&quote-1 >foo]",Ð "[quote&quote-1 >bar]");Ð // Multi-line blockquote followed by normal paragraph (non-lazy mode)Ð MT("multiBlockquoteThenParagraph",Ð "[quote&quote-1 >foo]",Ð "[quote&quote-1 >bar]",Ð "",Ð "hello");Ð // Check list typesÐ MT("listAsterisk",Ð "foo",Ð "bar",Ð "",Ð "[variable-2 * foo]",Ð "[variable-2 * bar]");Ð MT("listPlus",Ð "foo",Ð "bar",Ð "",Ð "[variable-2 + foo]",Ð "[variable-2 + bar]");Ð MT("listDash",Ð "foo",Ð "bar",Ð

```
                "",Ð    "[variable-2 - foo]",Ð    "[variable-2 - bar]");Ð
MT("listNumber",Ð    "foo",Ð    "bar",Ð    "",Ð    "[variable-2 1. foo]",Ð
"[variable-2 2. bar]");Ð // Lists require a preceding blank line (per Dingus)Ð
  MT("listBogus",Ð    "foo",Ð    "1. bar",Ð    "2. hello");Ð // List after
headerÐ MT("listAfterHeader",Ð    "[header&header-1 # foo]",Ð    "[variable-2
- bar]");Ð // Formatting in lists (*)Ð MT("listAsteriskFormatting",Ð
"[variable-2 * ][variable-2&em *foo*][variable-2  bar]",Ð    "[variable-2 * ]
[variable-2&strong **foo**][variable-2  bar]",Ð    "[variable-2 * ]
[variable-2&strong **][variable-2&em&strong *foo**][variable-2&em *]
[variable-2  bar]",Ð    "[variable-2 * ][variable-2&comment `foo`]
[variable-2  bar]");Ð // Formatting in lists (+)Ð MT("listPlusFormatting",Ð
     "[variable-2 + ][variable-2&em *foo*][variable-2  bar]",Ð
"[variable-2 + ][variable-2&strong **foo**][variable-2  bar]",Ð
"[variable-2 + ][variable-2&strong **][variable-2&em&strong *foo**]
[variable-2&em *][variable-2  bar]",Ð    "[variable-2 + ][variable-2&comment
`foo`][variable-2  bar]");Ð // Formatting in lists (-)Ð
MT("listDashFormatting",Ð    "[variable-2 - ][variable-2&em *foo*]
[variable-2  bar]",Ð    "[variable-2 - ][variable-2&strong **foo**]
[variable-2  bar]",Ð    "[variable-2 - ][variable-2&strong **]
[variable-2&em&strong *foo**][variable-2&em *][variable-2  bar]",Ð
"[variable-2 - ][variable-2&comment `foo`][variable-2  bar]");Ð // Formatting
in lists (1.)Ð MT("listNumberFormatting",Ð    "[variable-2 1. ][variable-2&em
*foo*][variable-2  bar]",Ð    "[variable-2 2. ][variable-2&strong **foo**]
[variable-2  bar]",Ð    "[variable-2 3. ][variable-2&strong **]
[variable-2&em&strong *foo**][variable-2&em *][variable-2  bar]",Ð
"[variable-2 4. ][variable-2&comment `foo`][variable-2  bar]");Ð // Paragraph
listsÐ MT("listParagraph",Ð    "[variable-2 * foo]",Ð    "",Ð    "[variable-2
* bar]");Ð // Multi-paragraph listsÐ //Ð // 4 spacesÐ MT("listMultiParagraph",Ð
     "[variable-2 * foo]",Ð    "",Ð    "[variable-2 * bar]",Ð    "",Ð
"    [variable-2 hello]");Ð // 4 spaces, extra blank lines (should still be
list, per Dingus)Ð MT("listMultiParagraphExtra",Ð    "[variable-2 * foo]",Ð
     "",Ð    "[variable-2 * bar]",Ð    "",Ð    "",Ð    "    [variable-2
hello]");Ð // 4 spaces, plus 1 space (should still be list, per Dingus)Ð
MT("listMultiParagraphExtraSpace",Ð    "[variable-2 * foo]",Ð    "",Ð
"[variable-2 * bar]",Ð    "",Ð    "     [variable-2 hello]",Ð    "",Ð
"    [variable-2 world]");Ð // 1 tabÐ MT("listTab",Ð    "[variable-2 * foo]",Ð
     "",Ð    "[variable-2 * bar]",Ð    "",Ð    "\t[variable-2 hello]");Ð //
No indentÐ MT("listNoIndent",Ð    "[variable-2 * foo]",Ð    "",Ð
"[variable-2 * bar]",Ð    "",Ð    "hello");Ð // BlockquoteÐ MT("blockquote",Ð
     "[variable-2 * foo]",Ð    "",Ð    "[variable-2 * bar]",Ð    "",Ð
"    [variable-2&quote&quote-1 > hello]");Ð // Code blockÐ
MT("blockquoteCode",Ð    "[variable-2 * foo]",Ð    "",Ð    "[variable-2 *
bar]",Ð    "",Ð    "        [comment > hello]",Ð    "",Ð    "    [variable-2
world]");Ð // Code block followed by textÐ MT("blockquoteCodeText",Ð
"[variable-2 * foo]",Ð    "",Ð    "    [variable-2 bar]",Ð    "",Ð
"        [comment hello]",Ð    "",Ð    "    [variable-2 world]");Ð // Nested
listÐ MT("listAsteriskNested",Ð    "[variable-2 * foo]",Ð    "",Ð
"    [variable-3 * bar]");Ð MT("listPlusNested",Ð    "[variable-2 + foo]",Ð
     "",Ð    "    [variable-3 + bar]");Ð MT("listDashNested",Ð
"[variable-2 - foo]",Ð    "",Ð    "    [variable-3 - bar]");Ð
MT("listNumberNested",Ð    "[variable-2 1. foo]",Ð    "",Ð
"    [variable-3 2. bar]");Ð MT("listMixed",Ð    "[variable-2 * foo]",Ð    "",Ð
     "    [variable-3 + bar]",Ð    "",Ð    "        [keyword - hello]",Ð
"",Ð    "            [variable-2 1. world]");Ð MT("listBlockquote",Ð
"[variable-2 * foo]",Ð    "",Ð    "    [variable-3 + bar]",Ð    "",Ð
"        [quote&quote-1&variable-3 > hello]");Ð MT("listCode",Ð
"[variable-2 * foo]",Ð    "",Ð    "    [variable-3 + bar]",Ð    "",Ð
"            [comment hello]");Ð // Code with internal indentationÐ
MT("listCodeIndentation",Ð    "[variable-2 * foo]",Ð    "",Ð
"        [comment bar]",Ð
```

```
                              "            [comment hello]",Ð
"                 [comment world]",Ð    "        [comment foo]",Ð
"    [variable-2 bar]");Ð // List nesting edge casesÐ MT("listNested",Ð
"[variable-2 * foo]",Ð   "",Ð   "    [variable-3 * bar]",Ð   "",Ð
"       [variable-2 hello]"Ð );Ð MT("listNested",Ð   "[variable-2 * foo]",Ð
"",Ð   "    [variable-3 * bar]",Ð   "",Ð   "      [variable-3 * foo]"Ð );Ð //
Code followed by textÐ MT("listCodeText",Ð    "[variable-2 * foo]",Ð    "",Ð
     "        [comment bar]",Ð    "",Ð    "hello");Ð // Following tests
directly from official Markdown documentationÐ // http://daringfireball.net/
projects/markdown/syntax#hrÐ MT("hrSpace",Ð    "[hr * * *]");Ð MT("hr",Ð
"[hr ***]");Ð MT("hrLong",Ð    "[hr *****]");Ð MT("hrSpaceDash",Ð    "[hr - -
-]");Ð MT("hrDashLong",Ð    "[hr ----------------------------------------]");Ð
  // Inline link with titleÐ MT("linkTitle",Ð    "[link [[foo]][string
(http://example.com/ \"bar\")] hello");Ð // Inline link without titleÐ
MT("linkNoTitle",Ð    "[link [[foo]][string (http://example.com/)] bar");Ð
  // Inline link with imageÐ MT("linkImage",Ð    "[link [[][tag ![[foo]]]
[string (http://example.com/)][link ]]][string (http://example.com/)] bar");Ð
  // Inline link with EmÐ MT("linkEm",Ð    "[link [[][link&em *foo*][link ]]]
[string (http://example.com/)] bar");Ð // Inline link with StrongÐ
MT("linkStrong",Ð    "[link [[][link&strong **foo**][link ]]][string (http://
example.com/)] bar");Ð // Inline link with EmStrongÐ MT("linkEmStrong",Ð
"[link [[][link&strong **][link&em&strong *foo**][link&em *][link ]]][string
(http://example.com/)] bar");Ð // Image with titleÐ MT("imageTitle",Ð
"[tag ![[foo]]][string (http://example.com/ \"bar\")] hello");Ð // Image
without titleÐ MT("imageNoTitle",Ð    "[tag ![[foo]]][string (http://
example.com/)] bar");Ð // Image with asterisksÐ MT("imageAsterisks",Ð
"[tag ![[*foo*]]][string (http://example.com/)] bar");Ð // Not a link. Should
be normal text due to square brackets being usedÐ // regularly in text,
especially in quoted material, and no space is allowedÐ // between square
brackets and parentheses (per Dingus).Ð MT("notALink",Ð    "[[foo]] (bar)");Ð
  // Reference-style linksÐ MT("linkReference",Ð    "[link [[foo]]][string
[[bar]]] hello");Ð // Reference-style links with EmÐ MT("linkReferenceEm",Ð
     "[link [[][link&em *foo*][link ]]][string [[bar]]] hello");Ð //
Reference-style links with StrongÐ MT("linkReferenceStrong",Ð    "[link [[]
[link&strong **foo**][link ]]][string [[bar]]] hello");Ð // Reference-style
links with EmStrongÐ MT("linkReferenceEmStrong",Ð    "[link [[][link&strong
**][link&em&strong *foo**][link&em *][link ]]][string [[bar]]] hello");Ð //
Reference-style links with optional space separator (per docuentation)Ð //
"You can optionally use a space to separate the sets of brackets"Ð
MT("linkReferenceSpace",Ð    "[link [[foo]] [string [[bar]]] hello");Ð //
Should only allow a single space ("...use *a* space...")Ð
MT("linkReferenceDoubleSpace",Ð    "[[foo]]  [[bar]] hello");Ð // Reference-
style links with implicit link nameÐ MT("linkImplicit",Ð    "[link [[foo]]]
[string [[]]] hello");Ð // @todo It would be nice if, at some point, the
document was actuallyÐ // checked to see if the referenced link existsÐ //
Link label, for reference-style links (taken from documentation)Ð
MT("labelNoTitle",Ð    "[link [[foo]]:] [string http://example.com/]");Ð
MT("labelIndented",Ð    "   [link [[foo]]:] [string http://example.com/]");Ð
MT("labelSpaceTitle",Ð    "[link [[foo bar]]:] [string http://example.com/
\"hello\"]");Ð MT("labelDoubleTitle",Ð    "[link [[foo bar]]:] [string http://
example.com/ \"hello\"] \"world\"");Ð MT("labelTitleDoubleQuotes",Ð    "[link
[[foo]]:] [string http://example.com/  \"bar\"]");Ð
MT("labelTitleSingleQuotes",Ð    "[link [[foo]]:] [string http://
example.com/  'bar']");Ð MT("labelTitleParenthese",Ð    "[link [[foo]]:]
[string http://example.com/  (bar)]");Ð MT("labelTitleInvalid",Ð    "[link
[[foo]]:] [string http://example.com/] bar");Ð MT("labelLinkAngleBrackets",Ð
     "[link [[foo]]:] [string <http://example.com/>  \"bar\"]");Ð
MT("labelTitleNextDoubleQuotes",Ð    "[link [[foo]]:] [string http://
example.com/]",Ð    "[string \"bar\"] hello");Ð
MT("labelTitleNextSingleQuotes",Ð
```

```
                                        "[link [[foo]]:] [string http://
example.com/]",Ð    "[string 'bar'] hello");Ð MT("labelTitleNextParenthese",Ð
     "[link [[foo]]:] [string http://example.com/]",Ð    "[string (bar)]
hello");Ð MT("labelTitleNextMixed",Ð    "[link [[foo]]:] [string http://
example.com/]",Ð    "(bar\" hello");Ð MT("linkWeb",Ð    "[link <http://
example.com/>] foo");Ð MT("linkWebDouble",Ð    "[link <http://example.com/>]
foo [link <http://example.com/>]");Ð MT("linkEmail",Ð    "[link
<user@example.com>] foo");Ð MT("linkEmailDouble",Ð    "[link
<user@example.com>] foo [link <user@example.com>]");Ð MT("emAsterisk",Ð
"[em *foo*] bar");Ð MT("emUnderscore",Ð    "[em _foo_] bar");Ð
MT("emInWordAsterisk",Ð    "foo[em *bar*]hello");Ð MT("emInWordUnderscore",Ð
     "foo[em _bar_]hello");Ð // Per documentation: "...surround an * or _
with spaces, it'll beÐ // treated as a literal asterisk or underscore."Ð
MT("emEscapedBySpaceIn",Ð    "foo [em _bar _ hello_] world");Ð
MT("emEscapedBySpaceOut",Ð    "foo _ bar[em _hello_]world");Ð
MT("emEscapedByNewline",Ð    "foo",Ð    "_ bar[em _hello_]world");Ð //
Unclosed emphasis charactersÐ // Instead of simply marking as EM / STRONG, it
would be nice to have anÐ // incomplete flag for EM and STRONG, that is
styled slightly different.Ð MT("emIncompleteAsterisk",Ð    "foo [em *bar]");Ð
MT("emIncompleteUnderscore",Ð    "foo [em _bar]");Ð MT("strongAsterisk",Ð
"[strong **foo**] bar");Ð MT("strongUnderscore",Ð    "[strong __foo__] bar");Ð
  MT("emStrongAsterisk",Ð    "[em *foo][em&strong **bar*][strong hello**]
world");Ð MT("emStrongUnderscore",Ð    "[em _foo][em&strong __bar_][strong
hello__] world");Ð // "...same character must be used to open and close an
emphasis span.""Ð MT("emStrongMixed",Ð    "[em _foo][em&strong **bar*hello__
world]");Ð MT("emStrongMixed",Ð    "[em *foo][em&strong __bar_hello**
world]");Ð // These characters should be escaped:Ð // \   backslashÐ // `
backtickÐ // *   asteriskÐ // _   underscoreÐ // {}  curly bracesÐ // []
square bracketsÐ // ()  parenthesesÐ // #   hash markÐ // +   plus signÐ //
-   minus sign (hyphen)Ð // .   dotÐ // !   exclamation markÐ
MT("escapeBacktick",Ð    "foo \\`bar\\`");Ð MT("doubleEscapeBacktick",Ð
"foo \\\\[comment `bar\\\\`]");Ð MT("escapeAsterisk",Ð    "foo \\*bar\\*");Ð
MT("doubleEscapeAsterisk",Ð    "foo \\\\[em *bar\\\\*]");Ð
MT("escapeUnderscore",Ð    "foo \\_bar\\_");Ð MT("doubleEscapeUnderscore",Ð
     "foo \\\\[em _bar\\\\_]");Ð MT("escapeHash",Ð    "\\# foo");Ð
MT("doubleEscapeHash",Ð    "\\\\# foo");Ð MT("escapeNewline",Ð    "\\",Ð
"[em *foo*]");Ð // Tests to make sure GFM-specific things aren't getting
throughÐ MT("taskList",Ð    "[variable-2 * [ ]] bar]");Ð
MT("fencedCodeBlocks",Ð    "[comment ```]",Ð    "foo",Ð    "[comment ```]");Ð
  // Tests that require XML modeÐ MT("xmlMode",Ð    "[tag&bracket <][tag div]
[tag&bracket >]",Ð    "*foo*",Ð    "[tag&bracket <][tag http://github.com]
[tag&bracket />]",Ð    "[tag&bracket </][tag div][tag&bracket >]",Ð    "[link
<http://github.com/>]");Ð MT("xmlModeWithMarkdownInside",Ð    "[tag&bracket <]
[tag div] [attribute markdown]=[string 1][tag&bracket >]",Ð    "[em *foo*]",Ð
     "[link <http://github.com/>]",Ð    "[tag </div>]",Ð    "[link <http://
github.com/>]",Ð    "[tag&bracket <][tag div][tag&bracket >]",Ð
"[tag&bracket </][tag div][tag&bracket >]");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\meta.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../lib/codemirror"));Ð else if (typeof define == "function" &&
define.amd) // AMD Ð   define(["../lib/codemirror"], mod);Ð else // Plain
browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.modeInfo = [Ð   {name: "APL", mime: "text/apl", mode: "apl", ext:
["dyalog", "apl"]},Ð   {name: "Asterisk", mime: "text/x-asterisk", mode:
"asterisk"},Ð   {name: "C", mime: "text/x-csrc", mode: "clike", ext: ["c",
"h"]},Ð   {name: "C++", mime: "text/x-c++src", mode: "clike", ext: ["cpp", "c+
+", "hpp", "h++"]},Ð   {name: "Cobol", mime: "text/x-cobol", mode: "cobol",
ext: ["cob", "cpy"]},Ð   {name: "C#", mime: "text/x-csharp", mode: "clike",
ext: ["cs"]},Ð   {name: "Clojure", mime: "text/x-clojure", mode: "clojure",
ext: ["clj"]},Ð   {name: "CoffeeScript", mime: "text/x-coffeescript", mode:
"coffeescript", ext: ["coffee"]},Ð   {name: "Common Lisp", mime: "text/x-
common-lisp", mode: "commonlisp", ext: ["cl", "lisp", "el"]},Ð   {name:
"Cypher", mime: "application/x-cypher-query", mode: "cypher"},Ð   {name:
"Cython", mime: "text/x-cython", mode: "python", ext: ["pyx", "pxd", "pxi"]},Ð
    {name: "CSS", mime: "text/css", mode: "css", ext: ["css"]},Ð   {name:
"CQL", mime: "text/x-cassandra", mode: "sql", ext: ["cql"]},Ð   {name: "D",
mime: "text/x-d", mode: "d", ext: ["d"]},Ð   {name: "diff", mime: "text/x-
diff", mode: "diff", ext: ["diff", "patch"]},Ð   {name: "DTD", mime:
"application/xml-dtd", mode: "dtd", ext: ["dtd"]},Ð   {name: "Dylan", mime:
"text/x-dylan", mode: "dylan", ext: ["dylan", "dyl", "intr"]},Ð   {name:
"ECL", mime: "text/x-ecl", mode: "ecl", ext: ["ecl"]},Ð   {name: "Eiffel",
mime: "text/x-eiffel", mode: "eiffel", ext: ["e"]},Ð   {name: "Embedded
Javascript", mime: "application/x-ejs", mode: "htmlembedded", ext: ["ejs"]},Ð
    {name: "Erlang", mime: "text/x-erlang", mode: "erlang", ext: ["erl"]},Ð
{name: "Fortran", mime: "text/x-fortran", mode: "fortran", ext: ["f", "for",
"f77", "f90"]},Ð   {name: "F#", mime: "text/x-fsharp", mode: "mllike", ext:
["fs"]},Ð   {name: "Gas", mime: "text/x-gas", mode: "gas", ext: ["s"]},Ð
{name: "Gherkin", mime: "text/x-feature", mode: "gherkin", ext: ["feature"]},Ð
    {name: "GitHub Flavored Markdown", mime: "text/x-gfm", mode: "gfm"},Ð
{name: "Go", mime: "text/x-go", mode: "go", ext: ["go"]},Ð   {name: "Groovy",
mime: "text/x-groovy", mode: "groovy", ext: ["groovy"]},Ð   {name: "HAML",
mime: "text/x-haml", mode: "haml", ext: ["haml"]},Ð   {name: "Haskell", mime:
"text/x-haskell", mode: "haskell", ext: ["hs"]},Ð   {name: "Haxe", mime:
"text/x-haxe", mode: "haxe", ext: ["hx"]},Ð   {name: "HXML", mime: "text/x-
hxml", mode: "haxe", ext: ["hxml"]},Ð   {name: "ASP.NET", mime: "application/
x-aspx", mode: "htmlembedded", ext: ["aspx"]},Ð   {name: "HTML", mime: "text/
html", mode: "htmlmixed", ext: ["html", "htm"]},Ð   {name: "HTTP", mime:
"message/http", mode: "http"},Ð   {name: "Jade", mime: "text/x-jade", mode:
"jade", ext: ["jade"]},Ð   {name: "Java", mime: "text/x-java", mode: "clike",
ext: ["java"]},Ð   {name: "Java Server Pages", mime: "application/x-jsp",
mode: "htmlembedded", ext: ["jsp"]},Ð   {name: "JavaScript", mimes: ["text/
javascript", "text/ecmascript", "application/javascript", "application/x-
javascript", "application/ecmascript"],Ð    mode: "javascript", ext: ["js"]},Ð
    {name: "JSON", mimes: ["application/json", "application/x-json"], mode:
"javascript", ext: ["json", "map"]},Ð   {name: "JSON-LD", mime: "application/
ld+json", mode: "javascript"},Ð   {name: "Jinja2", mime: "null", mode:
"jinja2"},Ð   {name: "Julia", mime: "text/x-julia", mode: "julia", ext:
["jl"]},Ð   {name: "Kotlin", mime: "text/x-kotlin", mode: "kotlin", ext:
["kt"]},Ð   {name: "LESS", mime: "text/x-less", mode: "css", ext: ["less"]},Ð
    {name: "LiveScript", mime: "text/x-livescript", mode: "livescript", ext:
["ls"]},Ð   {name: "Lua", mime: "text/x-lua", mode: "lua", ext: ["lua"]},Ð
{name: "Markdown (GitHub-flavour)", mime: "text/x-markdown", mode:
"markdown", ext: ["markdown", "md", "mkd"]},Ð   {name: "mIRC", mime: "text/
mirc", mode: "mirc"},Ð   {name: "MariaDB SQL", mime: "text/x-mariadb", mode:
"sql"},Ð
```

{name: "Modelica", mime: "text/x-modelica", mode: "modelica", ext: ["mo"]},Ð {name: "MS SQL", mime: "text/x-mssql", mode: "sql"},Ð {name: "MySQL", mime: "text/x-mysql", mode: "sql"},Ð {name: "Nginx", mime: "text/x-nginx-conf", mode: "nginx"},Ð {name: "NTriples", mime: "text/n-triples", mode: "ntriples", ext: ["nt"]},Ð {name: "OCaml", mime: "text/x-ocaml", mode: "mllike", ext: ["ml", "mli", "mll", "mly"]},Ð {name: "Octave", mime: "text/x-octave", mode: "octave", ext: ["m"]},Ð {name: "Pascal", mime: "text/x-pascal", mode: "pascal", ext: ["p", "pas"]},Ð {name: "PEG.js", mime: "null", mode: "pegjs"},Ð {name: "Perl", mime: "text/x-perl", mode: "perl", ext: ["pl", "pm"]},Ð {name: "PHP", mime: "application/x-httpd-php", mode: "php", ext: ["php", "php3", "php4", "php5", "phtml"]},Ð {name: "Pig", mime: "text/x-pig", mode: "pig"},Ð {name: "Plain Text", mime: "text/plain", mode: "null", ext: ["txt", "text", "conf", "def", "list", "log"]},Ð {name: "PLSQL", mime: "text/x-plsql", mode: "sql"},Ð {name: "Properties files", mime: "text/x-properties", mode: "properties", ext: ["properties", "ini", "in"]},Ð {name: "Python", mime: "text/x-python", mode: "python", ext: ["py", "pyw"]},Ð {name: "Puppet", mime: "text/x-puppet", mode: "puppet", ext: ["pp"]},Ð {name: "Q", mime: "text/x-q", mode: "q", ext: ["q"]},Ð {name: "R", mime: "text/x-rsrc", mode: "r", ext: ["r"]},Ð {name: "reStructuredText", mime: "text/x-rst", mode: "rst", ext: ["rst"]},Ð {name: "Ruby", mime: "text/x-ruby", mode: "ruby", ext: ["rb"]},Ð {name: "Rust", mime: "text/x-rustsrc", mode: "rust", ext: ["rs"]},Ð {name: "Sass", mime: "text/x-sass", mode: "sass", ext: ["sass"]},Ð {name: "Scala", mime: "text/x-scala", mode: "clike", ext: ["scala"]},Ð {name: "Scheme", mime: "text/x-scheme", mode: "scheme", ext: ["scm", "ss"]},Ð {name: "SCSS", mime: "text/x-scss", mode: "css", ext: ["scss"]},Ð {name: "Shell", mime: "text/x-sh", mode: "shell", ext: ["sh", "ksh", "bash"]},Ð {name: "Sieve", mime: "application/sieve", mode: "sieve"},Ð {name: "Slim", mimes: ["text/x-slim", "application/x-slim"], mode: "slim"},Ð {name: "Smalltalk", mime: "text/x-stsrc", mode: "smalltalk", ext: ["st"]},Ð {name: "Smarty", mime: "text/x-smarty", mode: "smarty", ext: ["tpl"]},Ð {name: "SmartyMixed", mime: "text/x-smarty", mode: "smartymixed"},Ð {name: "Solr", mime: "text/x-solr", mode: "solr"},Ð {name: "SPARQL", mime: "application/x-sparql-query", mode: "sparql", ext: ["sparql"]},Ð {name: "SQL", mime: "text/x-sql", mode: "sql", ext: ["sql"]},Ð {name: "MariaDB", mime: "text/x-mariadb", mode: "sql"},Ð {name: "sTeX", mime: "text/x-stex", mode: "stex"},Ð {name: "LaTeX", mime: "text/x-latex", mode: "stex", ext: ["text", "ltx"]},Ð {name: "SystemVerilog", mime: "text/x-systemverilog", mode: "verilog", ext: ["v"]},Ð {name: "Tcl", mime: "text/x-tcl", mode: "tcl", ext: ["tcl"]},Ð {name: "Textile", mime: "text/x-textile", mode: "textile"},Ð {name: "TiddlyWiki ", mime: "text/x-tiddlywiki", mode: "tiddlywiki"},Ð {name: "Tiki wiki", mime: "text/tiki", mode: "tiki"},Ð {name: "TOML", mime: "text/x-toml", mode: "toml"},Ð {name: "Tornado", mime: "text/x-tornado", mode: "tornado"},Ð {name: "Turtle", mime: "text/turtle", mode: "turtle", ext: ["ttl"]},Ð {name: "TypeScript", mime: "application/typescript", mode: "javascript", ext: ["ts"]},Ð {name: "VB.NET", mime: "text/x-vb", mode: "vb", ext: ["vb"]},Ð {name: "VBScript", mime: "text/vbscript", mode: "vbscript"},Ð {name: "Velocity", mime: "text/velocity", mode: "velocity", ext: ["vtl"]},Ð {name: "Verilog", mime: "text/x-verilog", mode: "verilog", ext: ["v"]},Ð {name: "XML", mimes: ["application/xml", "text/xml"], mode: "xml", ext: ["xml", "xsl", "xsd"]},Ð {name: "XQuery", mime: "application/xquery", mode: "xquery", ext: ["xy", "xquery"]},Ð {name: "YAML", mime: "text/x-yaml", mode: "yaml", ext: ["yaml"]},Ð {name: "Z80", mime: "text/x-z80", mode: "z80", ext: ["z80"]}Ð];Ð // Ensure all modes have a mime property for backwards compatibilityÐ for (var i = 0; i < CodeMirror.modeInfo.length; i++) {Ð var info = CodeMirror.modeInfo[i];Ð if (info.mimes) info.mime = info.mimes[0];Ð }Ð CodeMirror.findModeByMIME = function(mime) {Ð for (var i = 0; i < CodeMirror.modeInfo.length; i++) {Ð var info = CodeMirror.modeInfo[i];Ð if (info.mime == mime) return info;Ð if (info.mimes) for (var j = 0; j < info.mimes.length; j++)Ð

```
                                                                if
(info.mimes[j] == mime) return info;Ð   }Ð };Ð CodeMirror.findModeByExtension
= function(ext) {Ð   for (var i = 0; i < CodeMirror.modeInfo.length; i++) {Ð
      var info = CodeMirror.modeInfo[i];Ð     if (info.ext) for (var j = 0; j
< info.ext.length; j++)Ð       if (info.ext[j] == ext) return info;Ð   }Ð };Ð
});Ð
```

public\assets\js\plugins\codemirror\mode\mirc\mirc.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ mIRC mode by
Ford_Lawnmower :: Based on Velocity mode by Steve O'Hara Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMIME("text/mirc", "mirc");Ð CodeMirror.defineMode("mirc",
function() {Ð function parseWords(str) {Ð   var obj = {}, words = str.split("
");Ð   for (var i = 0; i < words.length; ++i) obj[words[i]] = true;Ð   return
obj;Ð }Ð var specials = parseWords("$! $$ $& $? $+ $abook $abs $active
$activecid " +Ð                          "$activewid $address $addtok $agent
$agentname $agentstat $agentver " +Ð                          "$alias $and
$anick $ansi2mirc $aop $appactive $appstate $asc $asctime " +Ð
                            "$asin $atan $avoice $away $awaymsg $awaytime
$banmask $base $bfind " +Ð                          "$binoff $biton $bnick
$bvar $bytes $calc $cb $cd $ceil $chan $chanmodes " +Ð
                            "$chantypes $chat $chr $cid $clevel $click
$cmdbox $cmdline $cnick $color " +Ð                          "$com $comcall
$comchan $comerr $compact $compress $comval $cos $count " +Ð
                            "$cr $crc $creq $crlf $ctime $ctimer $ctrlenter
$date $day $daylight " +Ð                          "$dbuh $dbuw $dccignore
$dccport $dde $ddename $debug $decode $decompress " +Ð
                            "$deltok $devent $dialog $did $didreg $didtok
$didwm $disk $dlevel $dll " +Ð                          "$dllcall $dname
$dns $duration $ebeeps $editbox $emailaddr $encode $error " +Ð
                            "$eval $event $exist $feof $ferr $fgetc $file
$filename $filtered $finddir " +Ð                          "$finddirn
$findfile $findfilen $findtok $fline $floor $fopen $fread $fserve " +Ð
                            "$fulladdress $fulldate $fullname $fullscreen
$get $getdir $getdot $gettok $gmt " +Ð                          "$group
$halted $hash $height $hfind $hget $highlight $hnick $hotline " +Ð
                            "$hotlinepos $ial $ialchan $ibl $idle $iel
$ifmatch $ignore $iif $iil " +Ð                          "$inelipse $ini
$inmidi $inpaste $inpoly $input $inrect $inroundrect " +Ð
                            "$insong $instok $int $inwave $ip $isalias $isbit
$isdde $isdir $isfile " +Ð                          "$isid $islower $istok
$isupper $keychar $keyrpt $keyval $knick $lactive " +Ð
                            "$lactivecid $lactivewid $left $len $level $lf
$line $lines $link $lock " +Ð                          "$lock $locked $log
$logstamp $logstampfmt $longfn $longip $lower $ltimer " +Ð
                            "$maddress $mask $matchkey $matchtok $md5 $me
$menu $menubar $menucontext " +Ð                          "$menutype $mid
$middir $mircdir $mircexe $mircini $mklogfn $mnick $mode " +Ð
                            "$modefirst $modelast $modespl $mouse $msfile
$network $newnick $nick $nofile " +Ð                          "$nopath $noqt
$not $notags $notify $null $numeric $numok $oline $onpoly " +Ð
                            "$opnick $or $ord $os $passivedcc $pic $play
$pnick $port $portable $portfree " +Ð                          "$pos $prefix
$prop $protect $puttok $qt $query $rand $r $rawmsg $read $readomo " +Ð
                            "$readn $regex $regml $regsub $regsubex $remove
$remtok $replace $replacex " +Ð                          "$reptok $result
$rgb $right $round $scid $scon $script $scriptdir $scriptline " +Ð
                            "$sdir $send $server $serverip $sfile $sha1
$shortfn $show $signal $sin " +Ð                          "$site $sline
$snick $snicks $snotify $sock $sockbr $sockerr $sockname " +Ð
                            "$sorttok $sound $sqrt $ssl $sreq $sslready
$status $strip $str $stripped " +Ð                          "$syle $submenu
$switchbar $tan $target $ticks $time $timer $timestamp " +Ð
```

```
                              "$timestampfmt $timezone $tip $titlebar $toolbar
$treebar $trust $ulevel " +Ð                          "$ulist $upper $uptime
$url $usermode $v1 $v2 $var $vcmd $vcmdstat $vcmdver " +Ð
                              "$version $vnick $vol $wid $width $wildsite
$wildtok $window $wrap $xor");Ð var keywords = parseWords("abook ajinvite
alias aline ame amsg anick aop auser autojoin avoice " +Ð
                              "away background ban bcopy beep bread break
breplace bset btrunc bunset bwrite " +Ð                           "channel
clear clearall cline clipboard close cnick color comclose comopen " +Ð
                              "comreg continue copy creq ctcpreply ctcps dcc
dccserver dde ddeserver " +Ð                          "debug dec describe
dialog did didtok disable disconnect dlevel dline dll " +Ð
                              "dns dqwindow drawcopy drawdot drawfill drawline
drawpic drawrect drawreplace " +Ð                           "drawrot drawsave
drawscroll drawtext ebeeps echo editbox emailaddr enable " +Ð
                              "events exit fclose filter findtext finger
firewall flash flist flood flush " +Ð                           "flushini
font fopen fseek fsend fserve fullname fwrite ghide gload gmove " +Ð
                              "gopts goto gplay gpoint gqreq groups gshow gsize
gstop gtalk gunload hadd " +Ð                           "halt haltdef hdec
hdel help hfree hinc hload hmake hop hsave ial ialclear " +Ð
                              "ialmark identd if ignore iline inc invite iuser
join kick linesep links list " +Ð                           "load loadbuf
localinfo log mdi me menubar mkdir mnick mode msg nick noop notice " +Ð
                              "notify omsg onotice part partall pdcc perform
play playctrl pop protect pvoice " +Ð                           "qme qmsg
query queryn quit raw reload remini remote remove rename renwin " +Ð
                              "reseterror resetidle return rlevel rline rmdir
run ruser save savebuf saveini " +Ð                           "say scid scon
server set showmirc signam sline sockaccept sockclose socklist " +Ð
                              "socklisten sockmark sockopen sockpause sockread
sockrename sockudp sockwrite " +Ð                           "sound speak
splay sreq strip switchbar timer timestamp titlebar tnick tokenize " +Ð
                              "toolbar topic tray treebar ulist unload unset
unsetall updatenl url uwho " +Ð                           "var vcadd vcmd
vcrem vol while whois window winhelp write writeint if isalnum " +Ð
                              "isalpha isaop isavoice isban ischan ishop
isignore isin isincs isletter islower " +Ð
"isnotify isnum ison isop isprotect isreg isupper isvoice iswm iswmcs " +Ð
                              "elseif else goto menu nicklist status title icon
size option text edit " +Ð                           "button check radio box
scroll list combo link tab item");Ð var functions = parseWords("if elseif
else and not or eq ne in ni for foreach while switch");Ð var isOperatorChar
= /[+\-*&%=<>!?^\/\|]/;Ð function chain(stream, state, f) {Ð   state.tokenize
= f;Ð   return f(stream, state);Ð }Ð function tokenBase(stream, state) {Ð
var beforeParams = state.beforeParams;Ð   state.beforeParams = false;Ð   var
ch = stream.next();Ð   if (/[\[\]{}\(\),\.]/.test(ch)) {Ð     if (ch == "("
&& beforeParams) state.inParams = true;Ð     else if (ch == ")")
state.inParams = false;Ð     return null;Ð   }Ð   else if (/\d/.test(ch)) {Ð
      stream.eatWhile(/[\w\.]/);Ð     return "number";Ð   }Ð   else if (ch ==
"\\") {Ð     stream.eat("\\");Ð     stream.eat(/./);Ð     return "number";Ð
    }Ð   else if (ch == "/" && stream.eat("*")) {Ð     return chain(stream,
state, tokenComment);Ð   }Ð   else if (ch == ";" && stream.match(/ *\( *\(/))
{Ð     return chain(stream, state, tokenUnparsed);Ð   }Ð   else if (ch == ";"
&& !state.inParams) {Ð     stream.skipToEnd();Ð     return "comment";Ð   }Ð
else if (ch == '"') {Ð     stream.eat(/"/);Ð     return "keyword";Ð   }Ð
else if (ch == "$") {Ð     stream.eatWhile(/[$_a-z0-9A-Z\.:]/);Ð     if
(specials && specials.propertyIsEnumerable(stream.current().toLowerCase())) {Ð
        return "keyword";Ð
```

```
                                }Ð     else {Ð       state.beforeParams = true;Ð
        return "builtin";Ð     }Ð   }Ð   else if (ch == "%") {Ð
stream.eatWhile(/[^,^\s^\(^\)]/);Ð     state.beforeParams = true;Ð     return
"string";Ð   }Ð   else if (isOperatorChar.test(ch)) {Ð
stream.eatWhile(isOperatorChar);Ð     return "operator";Ð   }Ð   else {Ð
stream.eatWhile(/[\w\$_{}]/);Ð     var word = stream.current().toLowerCase();Ð
      if (keywords && keywords.propertyIsEnumerable(word))Ð       return
"keyword";Ð     if (functions && functions.propertyIsEnumerable(word)) {Ð
        state.beforeParams = true;Ð       return "keyword";Ð     }Ð
return null;Ð   }Ð }Ð function tokenComment(stream, state) {Ð   var maybeEnd
= false, ch;Ð   while (ch = stream.next()) {Ð     if (ch == "/" && maybeEnd) {Ð
        state.tokenize = tokenBase;Ð       break;Ð     }Ð     maybeEnd = (ch
== "*");Ð   }Ð   return "comment";Ð }Ð function tokenUnparsed(stream, state) {Ð
    var maybeEnd = 0, ch;Ð   while (ch = stream.next()) {Ð     if (ch == ";"
&& maybeEnd == 2) {Ð       state.tokenize = tokenBase;Ð       break;Ð     }Ð
      if (ch == ")")Ð       maybeEnd++;Ð     else if (ch != " ")Ð
maybeEnd = 0;Ð   }Ð   return "meta";Ð }Ð return {Ð   startState: function() {Ð
      return {Ð       tokenize: tokenBase,Ð       beforeParams: false,Ð
inParams: falseÐ     };Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     return state.tokenize(stream, state);Ð
    }Ð };Ð});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\mllike\mllike.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode('mllike', function(_config, parserConfig) {Ð var words
= {Ð   'let': 'keyword',Ð   'rec': 'keyword',Ð   'in': 'keyword',Ð   'of':
'keyword',Ð   'and': 'keyword',Ð   'if': 'keyword',Ð   'then': 'keyword',Ð
'else': 'keyword',Ð   'for': 'keyword',Ð   'to': 'keyword',Ð   'while':
'keyword',Ð   'do': 'keyword',Ð   'done': 'keyword',Ð   'fun': 'keyword',Ð
'function': 'keyword',Ð   'val': 'keyword',Ð   'type': 'keyword',Ð
'mutable': 'keyword',Ð   'match': 'keyword',Ð   'with': 'keyword',Ð   'try':
'keyword',Ð   'open': 'builtin',Ð   'ignore': 'builtin',Ð   'begin':
'keyword',Ð   'end': 'keyword'Ð };Ð var extraWords = parserConfig.extraWords
|| {};Ð for (var prop in extraWords) {Ð   if
(extraWords.hasOwnProperty(prop)) {Ð     words[prop] =
parserConfig.extraWords[prop];Ð   }Ð }Ð function tokenBase(stream, state) {Ð
    var ch = stream.next();Ð   if (ch === '"') {Ð     state.tokenize =
tokenString;Ð     return state.tokenize(stream, state);Ð   }Ð   if (ch ===
'(') {Ð     if (stream.eat('*')) {Ð       state.commentLevel++;Ð
state.tokenize = tokenComment;Ð       return state.tokenize(stream, state);Ð
      }Ð   }Ð   if (ch === '~') {Ð     stream.eatWhile(/\w/);Ð     return
'variable-2';Ð   }Ð   if (ch === '`') {Ð     stream.eatWhile(/\w/);Ð
return 'quote';Ð   }Ð   if (ch === '/' && parserConfig.slashComments &&
stream.eat('/')) {Ð     stream.skipToEnd();Ð     return 'comment';Ð   }Ð   if
(/\d/.test(ch)) {Ð     stream.eatWhile(/[\d]/);Ð     if (stream.eat('.')) {Ð
        stream.eatWhile(/[\d]/);Ð     }Ð     return 'number';Ð   }Ð   if ( /[+
\-*&%=<>!?|]/.test(ch)) {Ð     return 'operator';Ð   }Ð   stream.eatWhile(/
\w/);Ð   var cur = stream.current();Ð   return words[cur] || 'variable';Ð }Ð
function tokenString(stream, state) {Ð   var next, end = false, escaped =
false;Ð   while ((next = stream.next()) != null) {Ð     if (next === '"' && !
escaped) {Ð       end = true;Ð       break;Ð     }Ð     escaped = !escaped &&
next === '\\';Ð   }Ð   if (end && !escaped) {Ð     state.tokenize = tokenBase;Ð
    }Ð   return 'string';Ð };Ð function tokenComment(stream, state) {Ð   var
prev, next;Ð   while(state.commentLevel > 0 && (next = stream.next()) !=
null) {Ð     if (prev === '(' && next === '*') state.commentLevel++;Ð     if
(prev === '*' && next === ')') state.commentLevel--;Ð     prev = next;Ð   }Ð
    if (state.commentLevel <= 0) {Ð     state.tokenize = tokenBase;Ð   }Ð
return 'comment';Ð }Ð return {Ð   startState: function() {return {tokenize:
tokenBase, commentLevel: 0};},Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     return state.tokenize(stream, state);Ð
    },Ð   blockCommentStart: "(*",Ð   blockCommentEnd: "*)",Ð   lineComment:
parserConfig.slashComments ? "//" : nullÐ };Ð });ÐodeMirror.defineMIME('text/x-
ocaml', {Ð name: 'mllike',Ð extraWords: {Ð   'succ': 'keyword',Ð   'trace':
'builtin',Ð   'exit': 'builtin',Ð   'print_string': 'builtin',Ð
'print_endline': 'builtin',Ð   'true': 'atom',Ð   'false': 'atom',Ð
'raise': 'keyword'Ð }Ð });ÐodeMirror.defineMIME('text/x-fsharp', {Ð name:
'mllike',Ð extraWords: {Ð   'abstract': 'keyword',Ð   'as': 'keyword',Ð
'assert': 'keyword',Ð   'base': 'keyword',Ð   'class': 'keyword',Ð
'default': 'keyword',Ð   'delegate': 'keyword',Ð   'downcast': 'keyword',Ð
'downto': 'keyword',Ð   'elif': 'keyword',Ð   'exception': 'keyword',Ð
'extern': 'keyword',Ð   'finally': 'keyword',Ð   'global': 'keyword',Ð
'inherit': 'keyword',Ð   'inline': 'keyword',Ð   'interface': 'keyword',Ð
'internal': 'keyword',Ð   'lazy': 'keyword',Ð   'let!': 'keyword',Ð
'member' : 'keyword',Ð   'module': 'keyword',Ð   'namespace': 'keyword',Ð
'new': 'keyword',Ð   'null': 'keyword',Ð   'override': 'keyword',Ð
'private': 'keyword',Ð   'public': 'keyword',Ð   'return': 'keyword',Ð
'return!': 'keyword',Ð
```

'select': 'keyword',Ð 'static': 'keyword',Ð 'struct': 'keyword',Ð 'upcast': 'keyword',Ð 'use': 'keyword',Ð 'use!': 'keyword',Ð 'val': 'keyword',Ð 'when': 'keyword',Ð 'yield': 'keyword',Ð 'yield!': 'keyword',Ð 'List': 'builtin',Ð 'Seq': 'builtin',Ð 'Map': 'builtin',Ð 'Set': 'builtin',Ð 'int': 'builtin',Ð 'string': 'builtin',Ð 'raise': 'builtin',Ð 'failwith': 'builtin',Ð 'not': 'builtin',Ð 'true': 'builtin',Ð 'false': 'builtin'Ð },Ð slashComments: trueÐ});Ð});Ð

public\assets\js\plugins\codemirror\mode\modelica\modelica.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and othersÐ// Distributed
under an MIT license: http://codemirror.net/LICENSEÐ// Modelica support for
CodeMirror, copyright (c) by Lennart OchelÐfunction(mod) {Ð if (typeof
exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})ÐÐfunction(CodeMirror) {Ð "use strict";Ð
  CodeMirror.defineMode("modelica", function(config, parserConfig) {Ð   var
indentUnit = config.indentUnit;Ð   var keywords = parserConfig.keywords || {};Ð
    var builtin = parserConfig.builtin || {};Ð   var atoms =
parserConfig.atoms || {};Ð   var isSingleOperatorChar = /[;=\(:\),{}.*<>+\-\/
^\[\]]/;Ð   var isDoubleOperatorChar = /(:=|<=|>=|==|<>|\.\+|\.\-|\.\*|\.\/|\.
\^)/;Ð   var isDigit = /[0-9]/;Ð   var isNonDigit = /[_a-zA-Z]/;Ð   function
tokenLineComment(stream, state) {Ð     stream.skipToEnd();Ð
state.tokenize = null;Ð     return "comment";Ð   }Ð   function
tokenBlockComment(stream, state) {Ð     var maybeEnd = false, ch;Ð     while
(ch = stream.next()) {Ð       if (maybeEnd && ch == "/") {Ð
state.tokenize = null;Ð         break;Ð       }Ð       maybeEnd = (ch == "*");Ð
      }Ð     return "comment";Ð   }Ð   function tokenString(stream, state) {Ð
      var escaped = false, ch;Ð     while ((ch = stream.next()) != null) {Ð
        if (ch == '"' && !escaped) {Ð         state.tokenize = null;Ð
state.sol = false;Ð         break;Ð       }Ð       escaped = !escaped && ch
== "\\";Ð     }Ð     return "string";Ð   }Ð   function tokenIdent(stream,
state) {Ð     stream.eatWhile(isDigit);Ð     while (stream.eat(isDigit) ||
stream.eat(isNonDigit)) { }Ð     var cur = stream.current();Ð
if(state.sol && (cur == "package" || cur == "model" || cur == "when" || cur
== "connector")) state.level++;Ð     else if(state.sol && cur == "end" &&
state.level > 0) state.level--;Ð     state.tokenize = null;Ð     state.sol =
false;Ð     if (keywords.propertyIsEnumerable(cur)) return "keyword";Ð
else if (builtin.propertyIsEnumerable(cur)) return "builtin";Ð     else if
(atoms.propertyIsEnumerable(cur)) return "atom";Ð     else return "variable";Ð
    }Ð   function tokenQIdent(stream, state) {Ð     while (stream.eat(/
[^']/)) { }Ð     state.tokenize = null;Ð     state.sol = false;Ð
if(stream.eat("'"))Ð       return "variable";Ð     elseÐ       return "error";Ð
    }Ð   function tokenUnsignedNuber(stream, state) {Ð
stream.eatWhile(isDigit);Ð     if (stream.eat('.')) {Ð
stream.eatWhile(isDigit);Ð     }Ð     if (stream.eat('e') || stream.eat('E'))
{Ð       if (!stream.eat('-'))Ð         stream.eat('+');Ð
stream.eatWhile(isDigit);Ð     }Ð     state.tokenize = null;Ð     state.sol =
false;Ð     return "number";Ð   }Ð   // InterfaceÐ   return {Ð
startState: function() {Ð       return {Ð         tokenize: null,Ð
level: 0,Ð         sol: trueÐ       };Ð     },Ð     token: function(stream,
state) {Ð       if(state.tokenize != null) {Ð         return
state.tokenize(stream, state);Ð       }Ð       if(stream.sol()) {Ð
state.sol = true;Ð       }Ð       // WHITESPACEÐ       if(stream.eatSpace()) {Ð
          state.tokenize = null;Ð         return null;Ð       }Ð       var ch
= stream.next();Ð       // LINECOMMENTÐ       if(ch == '/' &&
stream.eat('/')) {Ð         state.tokenize = tokenLineComment;Ð       }Ð
        // BLOCKCOMMENTÐ       else if(ch == '/' && stream.eat('*')) {Ð
          state.tokenize = tokenBlockComment;Ð       }Ð       // TWO SYMBOL
TOKENSÐ       else if(isDoubleOperatorChar.test(ch+stream.peek())) {Ð
stream.next();Ð         state.tokenize = null;Ð         return "operator";Ð
        }Ð       // SINGLE SYMBOL TOKENSÐ       else
if(isSingleOperatorChar.test(ch)) {Ð         state.tokenize = null;Ð
return "operator";Ð       }Ð       // IDENTÐ       else
if(isNonDigit.test(ch)) {Ð         state.tokenize = tokenIdent;Ð       }Ð
        // Q-IDENTÐ       else if(ch == "'" && stream.peek() &&
stream.peek() != "'") {Ð         state.tokenize = tokenQIdent;Ð       }Ð
        // STRINGÐ
```

```
                        else if(ch == '"') {Ð         state.tokenize =
tokenString;Ð       }Ð       // UNSIGNED_NUBERÐ       else
if(isDigit.test(ch)) {Ð         state.tokenize = tokenUnsignedNuber;Ð       }Ð
        // ERRORÐ       else {Ð         state.tokenize = null;Ð
return "error";Ð       }Ð       return state.tokenize(stream, state);Ð     },Ð
      indent: function(state, textAfter) {Ð       if (state.tokenize != null)
return CodeMirror.Pass;Ð       var level = state.level;Ð       if(/
(algorithm)/.test(textAfter)) level--;Ð       if(/
(equation)/.test(textAfter)) level--;Ð       if(/(initial
algorithm)/.test(textAfter)) level--;Ð       if(/(initial
equation)/.test(textAfter)) level--;Ð       if(/(end)/.test(textAfter))
level--;Ð       if(level > 0)Ð         return indentUnit*level;Ð       elseÐ
          return 0;Ð     },Ð     blockCommentStart: "/*",Ð
blockCommentEnd: "*/",Ð     lineComment: "//"Ð   };Ð });Ð function words(str)
{Ð   var obj = {}, words = str.split(" ");Ð   for (var i=0; i<words.length; +
+i)Ð     obj[words[i]] = true;Ð   return obj;Ð }Ð var modelicaKeywords =
"algorithm and annotation assert block break class connect connector constant
constrainedby der discrete each else elseif elsewhen encapsulated end
enumeration equation expandable extends external false final flow for
function if import impure in initial inner input loop model not operator or
outer output package parameter partial protected public pure record redeclare
replaceable return stream then true type when while within";Ð var
modelicaBuiltin = "abs acos actualStream asin atan atan2 cardinality ceil cos
cosh delay div edge exp floor getInstanceName homotopy inStream integer log
log10 mod pre reinit rem semiLinear sign sin sinh spatialDistribution sqrt
tan tanh";Ð var modelicaAtoms = "Real Boolean Integer String";Ð function
def(mimes, mode) {Ð   if (typeof mimes == "string")Ð     mimes = [mimes];Ð
var words = [];Ð   function add(obj) {Ð     if (obj)Ð       for (var prop in
obj)Ð         if (obj.hasOwnProperty(prop))Ð           words.push(prop);Ð   }Ð
    add(mode.keywords);Ð   add(mode.builtin);Ð   add(mode.atoms);Ð   if
(words.length) {Ð     mode.helperType = mimes[0];Ð
CodeMirror.registerHelper("hintWords", mimes[0], words);Ð   }Ð   for (var
i=0; i<mimes.length; ++i)Ð     CodeMirror.defineMIME(mimes[i], mode);Ð }Ð
def(["text/x-modelica"], {Ð   name: "modelica",Ð   keywords:
words(modelicaKeywords),Ð   builtin: words(modelicaBuiltin),Ð   atoms:
words(modelicaAtoms)Ð });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\ntriples\ntriples.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð
*************************************************************Ð This script
provides syntax highlighting support for Ð the Ntriples format. Ð Ntriples
format specification: Ð     http://www.w3.org/TR/rdf-testcases/#ntriples Ð
*************************************************************/Ð*Ð   The
following expression defines the defined ASF grammar transitions. Ð
pre_subject ->Ð       {Ð       ( writing_subject_uri | writing_bnode_uri )Ð
            -> pre_predicateÐ               -> writing_predicate_uriÐ
                    -> pre_objectÐ                        ->
writing_object_uri | writing_object_bnode |Ð                          (Ð
                            writing_object_literalÐ
                                -> writing_literal_lang | writing_literal_typeÐ
                            )Ð                            -> post_objectÐ
                                -> BEGINÐ        } otherwise {Ð            ->
ERRORÐ        }Ð/Ð function(mod) {Ð if (typeof exports == "object" && typeof
module == "object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð
else if (typeof define == "function" && define.amd) // AMD Ð   define(["../../
lib/codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð})
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("ntriples",
function() {Ð var Location = {Ð   PRE_SUBJECT         : 0,Ð
WRITING_SUB_URI     : 1,Ð   WRITING_BNODE_URI   : 2,Ð   PRE_PRED           :
3,Ð   WRITING_PRED_URI    : 4,Ð   PRE_OBJ             : 5,Ð
WRITING_OBJ_URI     : 6,Ð   WRITING_OBJ_BNODE   : 7,Ð   WRITING_OBJ_LITERAL :
8,Ð   WRITING_LIT_LANG    : 9,Ð   WRITING_LIT_TYPE    : 10,Ð
POST_OBJ            : 11,Ð   ERROR               : 12Ð };Ð function
transitState(currState, c) {Ð   var currLocation = currState.location;Ð   var
ret;Ð   // Opening.Ð   if     (currLocation == Location.PRE_SUBJECT && c ==
'<') ret = Location.WRITING_SUB_URI;Ð   else if(currLocation ==
Location.PRE_SUBJECT && c == '_') ret = Location.WRITING_BNODE_URI;Ð   else
if(currLocation == Location.PRE_PRED    && c == '<') ret =
Location.WRITING_PRED_URI;Ð   else if(currLocation == Location.PRE_OBJ     &&
c == '<') ret = Location.WRITING_OBJ_URI;Ð   else if(currLocation ==
Location.PRE_OBJ     && c == '_') ret = Location.WRITING_OBJ_BNODE;Ð   else
if(currLocation == Location.PRE_OBJ     && c == '"') ret =
Location.WRITING_OBJ_LITERAL;Ð   // Closing.Ð   else if(currLocation ==
Location.WRITING_SUB_URI     && c == '>') ret = Location.PRE_PRED;Ð   else
if(currLocation == Location.WRITING_BNODE_URI   && c == ' ') ret =
Location.PRE_PRED;Ð   else if(currLocation == Location.WRITING_PRED_URI    &&
c == '>') ret = Location.PRE_OBJ;Ð   else if(currLocation ==
Location.WRITING_OBJ_URI     && c == '>') ret = Location.POST_OBJ;Ð   else
if(currLocation == Location.WRITING_OBJ_BNODE   && c == ' ') ret =
Location.POST_OBJ;Ð   else if(currLocation == Location.WRITING_OBJ_LITERAL &&
c == '"') ret = Location.POST_OBJ;Ð   else if(currLocation ==
Location.WRITING_LIT_LANG && c == ' ') ret = Location.POST_OBJ;Ð   else
if(currLocation == Location.WRITING_LIT_TYPE && c == '>') ret =
Location.POST_OBJ;Ð   // Closing typed and language literal.Ð   else
if(currLocation == Location.WRITING_OBJ_LITERAL && c == '@') ret =
Location.WRITING_LIT_LANG;Ð   else if(currLocation ==
Location.WRITING_OBJ_LITERAL && c == '^') ret = Location.WRITING_LIT_TYPE;Ð
    // Spaces.Ð   else if( c == ' ' &&Ð            (Ð
currLocation == Location.PRE_SUBJECT ||Ð              currLocation ==
Location.PRE_PRED    ||Ð              currLocation == Location.PRE_OBJ     ||Ð
               currLocation == Location.POST_OBJ Ð            )Ð          )
ret = currLocation;Ð   // Reset.Ð   else if(currLocation == Location.POST_OBJ
&& c == '.') ret = Location.PRE_SUBJECT;Ð   // ErrorÐ   else ret =
Location.ERROR;Ð   currState.location=ret;Ð }Ð return {Ð   startState:
function() {Ð      return {Ð          location : Location.PRE_SUBJECT,Ð
           uris     : [],Ð
```

```
                                    anchors  : [],Ð          bnodes   : [],Ð
           langs    : [],Ð          types    : []Ð      };Ð   },Ð   token:
function(stream, state) {Ð     var ch = stream.next();Ð     if(ch == '<') {Ð
         transitState(state, ch);Ð        var parsedURI = '';Ð
stream.eatWhile( function(c) { if( c != '#' && c != '>' ) { parsedURI += c;
return true; } return false;} );Ð        state.uris.push(parsedURI);Ð
if( stream.match('#', false) ) return 'variable';Ð        stream.next();Ð
         transitState(state, '>');Ð        return 'variable';Ð     }Ð
if(ch == '#') {Ð       var parsedAnchor = '';Ð
stream.eatWhile(function(c) { if(c != '>' && c != ' ') { parsedAnchor+= c;
return true; } return false;});Ð       state.anchors.push(parsedAnchor);Ð
        return 'variable-2';Ð     }Ð     if(ch == '>') {Ð
transitState(state, '>');Ð         return 'variable';Ð     }Ð     if(ch ==
'_') {Ð         transitState(state, ch);Ð         var parsedBNode = '';Ð
          stream.eatWhile(function(c) { if( c != ' ' ) { parsedBNode += c;
return true; } return false;});Ð         state.bnodes.push(parsedBNode);Ð
          stream.next();Ð         transitState(state, ' ');Ð         return
'builtin';Ð     }Ð     if(ch == '"') {Ð         transitState(state, ch);Ð
          stream.eatWhile( function(c) { return c != '"'; } );Ð
stream.next();Ð         if( stream.peek() != '@' && stream.peek() != '^' ) {Ð
               transitState(state, '"');Ð         }Ð         return 'string';Ð
      }Ð     if( ch == '@' ) {Ð         transitState(state, '@');Ð
var parsedLang = '';Ð         stream.eatWhile(function(c) { if( c != ' ' )
{ parsedLang += c; return true; } return false;});Ð
state.langs.push(parsedLang);Ð         stream.next();Ð
transitState(state, ' ');Ð         return 'string-2';Ð     }Ð     if( ch ==
'^' ) {Ð         stream.next();Ð         transitState(state, '^');Ð
var parsedType = '';Ð         stream.eatWhile(function(c) { if( c != '>' )
{ parsedType += c; return true; } return false;} );Ð
state.types.push(parsedType);Ð         stream.next();Ð
transitState(state, '>');Ð         return 'variable';Ð     }Ð     if( ch == '
' ) {Ð         transitState(state, ch);Ð     }Ð     if( ch == '.' ) {Ð
          transitState(state, ch);Ð     }Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("text/n-triples", "ntriples");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\octave\octave.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others/ Distributed
under an MIT license: http://codemirror.net/LICENSE(function(mod) { if
(typeof exports == "object" && typeof module == "object") // CommonJS
mod(require("../../lib/codemirror")); else if (typeof define == "function"
&& define.amd) // AMD   define(["../../lib/codemirror"], mod); else //
Plain browser env   mod(CodeMirror);})(function(CodeMirror) {"use strict";
CodeMirror.defineMode("octave", function() { function wordRegexp(words) {
return new RegExp("^(" + words.join("|") + ")\\b"); }var
singleOperators = new RegExp("^[\\+\\-\\*/&|\\^~<>!@'\\]");var
singleDelimiters = new RegExp('^[\\(\\[\\{\\},:=;]');var doubleOperators =
new RegExp("^((==)|(~=)|(<=)|(>=)|(<<)|(>>)|(\\.[\\+\\-\\*/\\^\\]))");var
doubleDelimiters = new RegExp("^((!=)|(\\+=)|(\\-=)|(\\*=)|(/=)|(&=)|(\\|=)|(\
\^=))");var tripleDelimiters = new RegExp("^((>>=)|(<<=))");var
expressionEnd = new RegExp("^[\\]\\)]");var identifiers = new RegExp("^[_A-
Za-z\xa1-\uffff][_A-Za-z0-9\xa1-\uffff]*");var builtins = wordRegexp([
'error', 'eval', 'function', 'abs', 'acos', 'atan', 'asin', 'cos',   'cosh',
'exp', 'log', 'prod', 'sum', 'log10', 'max', 'min', 'sign', 'sin', 'sinh',
'sqrt', 'tan', 'reshape', 'break', 'zeros', 'default', 'margin', 'round',
'ones',   'rand', 'syn', 'ceil', 'floor', 'size', 'clear', 'zeros', 'eye',
'mean', 'std', 'cov',   'det', 'eig', 'inv', 'norm', 'rank', 'trace',
'expm', 'logm', 'sqrtm', 'linspace', 'plot',   'title', 'xlabel', 'ylabel',
'legend', 'text', 'grid', 'meshgrid', 'mesh', 'num2str',   'fft', 'ifft',
'arrayfun', 'cellfun', 'input', 'fliplr', 'flipud', 'ismember' ]);var
keywords = wordRegexp([   'return', 'case', 'switch', 'else', 'elseif',
'end', 'endif', 'endfunction',   'if', 'otherwise', 'do', 'for', 'while',
'try', 'catch', 'classdef', 'properties', 'events',   'methods', 'global',
'persistent', 'endfor', 'endwhile', 'printf', 'sprintf', 'disp', 'until',
'continue', 'pkg' ]);// tokenizersfunction tokenTranspose(stream, state)
{   if (!stream.sol() && stream.peek() === '\'') {     stream.next();
state.tokenize = tokenBase;     return 'operator';   }   state.tokenize =
tokenBase;   return tokenBase(stream, state); }function
tokenComment(stream, state) {   if (stream.match(/^.*%}/)) {
state.tokenize = tokenBase;     return 'comment';   };
stream.skipToEnd();   return 'comment'; }function tokenBase(stream,
state) {   // whitespaces   if (stream.eatSpace()) return null;   //
Handle one line Comments   if (stream.match('%{')){     state.tokenize =
tokenComment;     stream.skipToEnd();     return 'comment';   }   if
(stream.match(/^[%#]/)){     stream.skipToEnd();     return 'comment';   }
    // Handle Number Literals   if (stream.match(/^[0-9\.+-]/, false)) {
      if (stream.match(/^[+-]?0x[0-9a-fA-F]+[ij]?/)) {       stream.tokenize
= tokenBase;       return 'number'; };     if (stream.match(/^[+-]?\d*\.
\d+([EeDd][+-]?\d+)?[ij]?/)) { return 'number'; };     if (stream.match(/
^[+-]?\d+([EeDd][+-]?\d+)?[ij]?/)) { return 'number'; };   }   if
(stream.match(wordRegexp(['nan','NaN','inf','Inf']))) { return 'number'; };
    // Handle Strings   if (stream.match(/^"([^"]|("")*"/)) { return
'string'; } ;   if (stream.match(/^'([^']|('')*'/)) { return 'string'; } ;
    // Handle words   if (stream.match(keywords)) { return 'keyword'; } ;
if (stream.match(builtins)) { return 'builtin'; } ;   if
(stream.match(identifiers)) { return 'variable'; } ;   if
(stream.match(singleOperators) || stream.match(doubleOperators)) { return
'operator'; };   if (stream.match(singleDelimiters) ||
stream.match(doubleDelimiters) || stream.match(tripleDelimiters)) { return
null; };   if (stream.match(expressionEnd)) {     state.tokenize =
tokenTranspose;     return null;   };   // Handle non-detected items
stream.next();   return 'error'; };return {   startState: function() {
      return {       tokenize: tokenBase     };   },   token:
function(stream, state) {     var style = state.tokenize(stream, state);
      if (style === 'number' || style === 'variable'){       state.tokenize
= tokenTranspose;
```

```
                        }Ð     return style;Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("text/x-octave", "octave");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\pascal\pascal.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("pascal", function() {Ð function words(str) {Ð   var
obj = {}, words = str.split(" ");Ð   for (var i = 0; i < words.length; ++i)
obj[words[i]] = true;Ð   return obj;Ð }Ð var keywords = words("and array
begin case const div do downto else end file for forward integer " +Ð
                       "boolean char function goto if in label mod nil not of
or packed procedure " +Ð                       "program record repeat set
string then to type until var while with");Ð var atoms = {"null": true};Ð var
isOperatorChar = /[+\-*&%=<>!?|\/]/;Ð function tokenBase(stream, state) {Ð
var ch = stream.next();Ð   if (ch == "#" && state.startOfLine) {Ð
stream.skipToEnd();Ð     return "meta";Ð   }Ð   if (ch == '"' || ch == "'") {Ð
      state.tokenize = tokenString(ch);Ð     return state.tokenize(stream,
state);Ð   }Ð   if (ch == "(" && stream.eat("*")) {Ð     state.tokenize =
tokenComment;Ð     return tokenComment(stream, state);Ð   }Ð   if (/[\[\]
{}\(\),;\:\.]/.test(ch)) {Ð     return null;Ð   }Ð   if (/\d/.test(ch)) {Ð
      stream.eatWhile(/[\w\.]/);Ð     return "number";Ð   }Ð   if (ch == "/")
{Ð     if (stream.eat("/")) {Ð       stream.skipToEnd();Ð       return
"comment";Ð     }Ð   }Ð   if (isOperatorChar.test(ch)) {Ð
stream.eatWhile(isOperatorChar);Ð     return "operator";Ð   }Ð
stream.eatWhile(/[\w\$_]/);Ð   var cur = stream.current();Ð   if
(keywords.propertyIsEnumerable(cur)) return "keyword";Ð   if
(atoms.propertyIsEnumerable(cur)) return "atom";Ð   return "variable";Ð }Ð
function tokenString(quote) {Ð   return function(stream, state) {Ð     var
escaped = false, next, end = false;Ð     while ((next = stream.next()) !=
null) {Ð       if (next == quote && !escaped) {end = true; break;}Ð
escaped = !escaped && next == "\\";Ð     }Ð     if (end || !escaped)
state.tokenize = null;Ð     return "string";Ð   };Ð }Ð function
tokenComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while (ch =
stream.next()) {Ð     if (ch == ")" && maybeEnd) {Ð       state.tokenize =
null;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð   }Ð   return
"comment";Ð }Ð // Interface Ð return {Ð   startState: function() {Ð     return
{tokenize: null};Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     var style = (state.tokenize ||
tokenBase)(stream, state);Ð     if (style == "comment" || style == "meta")
return style;Ð     return style;Ð   },Ð   electricChars: "{}"Ð };Ð });Ð
CodeMirror.defineMIME("text/x-pascal", "pascal");Ð });Ð
```

public\assets\js\plugins\codemirror\mode\pegjs\pegjs.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../javascript/javascript"));Ð
else if (typeof define == "function" && define.amd) // AMD Ð   define(["../../
lib/codemirror", "../javascript/javascript"], mod);Ð else // Plain browser env Ð
    mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("pegjs", function (config) {Ð var jsMode =
CodeMirror.getMode(config, "javascript");Ð function identifier(stream) {Ð
return stream.match(/^[a-zA-Z_][a-zA-Z0-9_]*/);Ð }Ð return {Ð   startState:
function () {Ð     return {Ð       inString: false,Ð       stringType: null,Ð
        inComment: false,Ð       inChracterClass: false,Ð       braced: 0,Ð
        lhs: true,Ð       localState: nullÐ     };Ð   },Ð   token: function
(stream, state) {Ð     if (stream)Ð     //check for state changesÐ     if (!
state.inString && !state.inComment && ((stream.peek() == '"') ||
(stream.peek() == "'"))) {Ð       state.stringType = stream.peek();Ð
stream.next(); // Skip quoteÐ       state.inString = true; // Update stateÐ
      }Ð     if (!state.inString && !state.inComment && stream.match(/^\/
\*/)) {Ð       state.inComment = true;Ð     }Ð     //return stateÐ     if
(state.inString) {Ð       while (state.inString && !stream.eol()) {Ð
if (stream.peek() === state.stringType) {Ð           stream.next(); // Skip
quoteÐ           state.inString = false; // Clear flagÐ         } else if
(stream.peek() === '\\') {Ð           stream.next();Ð           stream.next();Ð
          } else {Ð           stream.match(/^.[^\\\"\']*/);Ð         }Ð
        }Ð       return state.lhs ? "property string" : "string"; // Token
styleÐ     } else if (state.inComment) {Ð       while (state.inComment && !
stream.eol()) {Ð         if (stream.match(/\*\//)) {Ð
state.inComment = false; // Clear flagÐ         } else {Ð
stream.match(/^.[^\*]*/);Ð         }Ð       }Ð       return "comment";Ð     }
else if (state.inChracterClass) {Ð         while (state.inChracterClass && !
stream.eol()) {Ð           if (!(stream.match(/^[^\]\\]+/) || stream.match(/^\
\./))) {Ð             state.inChracterClass = false;Ð           }Ð         }Ð
      } else if (stream.peek() === '[') {Ð       stream.next();Ð
state.inChracterClass = true;Ð       return 'bracket';Ð     } else if
(stream.match(/^\/\//)) {Ð       stream.skipToEnd();Ð       return "comment";Ð
      } else if (state.braced || stream.peek() === '{') {Ð       if
(state.localState === null) {Ð         state.localState = jsMode.startState();Ð
        }Ð       var token = jsMode.token(stream, state.localState);Ð
var text = stream.current();Ð       if (!token) {Ð         for (var i = 0; i
< text.length; i++) {Ð           if (text[i] === '{') {Ð
state.braced++;Ð           } else if (text[i] === '}') {Ð
state.braced--;Ð           }Ð         };Ð       }Ð       return token;Ð     }
else if (identifier(stream)) {Ð       if (stream.peek() === ':') {Ð
return 'variable';Ð       }Ð       return 'variable-2';Ð     } else if (['[',
']', '(', ')'].indexOf(stream.peek()) != -1) {Ð       stream.next();Ð
return 'bracket';Ð     } else if (!stream.eatSpace()) {Ð       stream.next();Ð
      }Ð     return null;Ð   }Ð };Ð, "javascript");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\perl\perl.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ CodeMirror2 mode/perl/
perl.js (text/x-perl) beta 0.10 (2011-11-08) Ð/ This is a part of CodeMirror
from https://github.com/sabaca/CodeMirror_mode_perl (mail@sabaca.com) Ð
(function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð})
(function(CodeMirror) {Ð"use strict";Ð CodeMirror.defineMode("perl",function(){Ð
        // http://perldoc.perl.org Ð       var
PERL={                                          //   null - magic touch Ð
                                                        //   1 - keyword Ð
                                                        //   2 - def Ð
                                                        //   3 - atom Ð
                                                        //   4 - operator Ð
                                                        //   5 - variable-2
(predefined) Ð                                                     //
[x,y] - x=1,2,3; y=must be defined if x{...}Ð
                                                //      PERL operators Ð
                '->'                            :   4,Ð              '+
+'                              :   4,Ð
'--'                              :   4,Ð
'**'                              :   4,Ð
                                                        //   ! ~ \ and unary
+ and -Ð                '=~'                            :   4,Ð
'!~'                              :   4,Ð
'*'                               :   4,Ð
'/'                               :   4,Ð
'%'                               :   4,Ð
'x'                               :   4,Ð
'+'                               :   4,Ð
'-'                               :   4,Ð
'.'                               :   4,Ð
'<<'                              :   4,Ð
'>>'                              :   4,Ð
                                                        //   named unary
operators Ð                '<'                           :   4,Ð
                '>'                             :   4,Ð
'<='                              :   4,Ð
'>='                              :   4,Ð
'lt'                              :   4,Ð
'gt'                              :   4,Ð
'le'                              :   4,Ð
'ge'                              :   4,Ð
'=='                              :   4,Ð               '!
='                              :   4,Ð
'<=>'                             :   4,Ð
'eq'                              :   4,Ð
'ne'                              :   4,Ð
'cmp'                             :   4,Ð
'~~'                              :   4,Ð
'&'                               :   4,Ð
'|'                               :   4,Ð
'^'                               :   4,Ð
'&&'                              :   4,Ð
'||'                              :   4,Ð
'//'                              :   4,Ð
'..'                              :   4,Ð
'...'                             :   4,Ð
```

```
'?'                             :   4,Ð
':'                             :   4,Ð
'='                             :   4,Ð
'+='                            :   4,Ð               '-
='                            :   4,Ð
'*='                            :   4,  //   etc. ???Ð
','                             :   4,Ð
'=>'                            :   4,Ð
'::'                            :   4,Ð
                                                          //   list operators
(rightward)Ð               'not'                             :   4,Ð
                'and'                           :   4,Ð
'or'                            :   4,Ð
'xor'                           :   4,Ð
                                                //      PERL predefined
variables (I know, what this is a paranoid idea, but may be needed for
people, who learn PERL, and for me as well, ...and may be for you?;)Ð
                'BEGIN'                         :   [5,1],Ð
'END'                           :   [5,1],Ð
'PRINT'                         :   [5,1],Ð
'PRINTF'                        :   [5,1],Ð
'GETC'                          :   [5,1],Ð
'READ'                          :   [5,1],Ð
'READLINE'                      :   [5,1],Ð
'DESTROY'                       :   [5,1],Ð
'TIE'                           :   [5,1],Ð
'TIEHANDLE'                     :   [5,1],Ð
'UNTIE'                         :   [5,1],Ð
'STDIN'                         :    5,Ð
'STDIN_TOP'                     :    5,Ð
'STDOUT'                        :    5,Ð
'STDOUT_TOP'                    :    5,Ð
'STDERR'                        :    5,Ð
'STDERR_TOP'                    :    5,Ð
'$ARG'                          :    5,Ð
'$_'                            :    5,Ð
'@ARG'                          :    5,Ð
'@_'                            :    5,Ð
'$LIST_SEPARATOR'               :    5,Ð
'$"'                            :    5,Ð
'$PROCESS_ID'                   :    5,Ð
'$PID'                          :    5,Ð               '$
$'                            :    5,Ð
'$REAL_GROUP_ID'                :    5,Ð
'$GID'                          :    5,Ð
'$('                            :    5,Ð
'$EFFECTIVE_GROUP_ID'           :    5,Ð
'$EGID'                         :    5,Ð
'$)'                            :    5,Ð
'$PROGRAM_NAME'                 :    5,Ð
'$0'                            :    5,Ð
'$SUBSCRIPT_SEPARATOR'          :    5,Ð
'$SUBSEP'                       :    5,Ð
'$;'                            :    5,Ð
'$REAL_USER_ID'                 :    5,Ð
'$UID'                          :    5,Ð
'$<'                            :    5,Ð
'$EFFECTIVE_USER_ID'            :    5,Ð
'$EUID'                         :    5,Ð
```

```
'$>'                            :    5,Ð
'$a'                            :    5,Ð
'$b'                            :    5,Ð
'$COMPILING'                    :    5,Ð
'$^C'                           :    5,Ð
'$DEBUGGING'                    :    5,Ð
'$^D'                           :    5,Ð
'${^ENCODING}'                  :    5,Ð
'$ENV'                          :    5,Ð
'%ENV'                          :    5,Ð
'$SYSTEM_FD_MAX'                :    5,Ð
'$^F'                           :    5,Ð
'@F'                            :    5,Ð
'${^GLOBAL_PHASE}'              :    5,Ð
'$^H'                           :    5,Ð
'%^H'                           :    5,Ð
'@INC'                          :    5,Ð
'%INC'                          :    5,Ð
'$INPLACE_EDIT'                 :    5,Ð
'$^I'                           :    5,Ð
'$^M'                           :    5,Ð
'$OSNAME'                       :    5,Ð
'$^O'                           :    5,Ð
'${^OPEN}'                      :    5,Ð
'$PERLDB'                       :    5,Ð
'$^P'                           :    5,Ð
'$SIG'                          :    5,Ð
'%SIG'                          :    5,Ð
'$BASETIME'                     :    5,Ð
'$^T'                           :    5,Ð
'${^TAINT}'                     :    5,Ð
'${^UNICODE}'                   :    5,Ð
'${^UTF8CACHE}'                 :    5,Ð
'${^UTF8LOCALE}'                :    5,Ð
'$PERL_VERSION'                 :    5,Ð
'$^V'                           :    5,Ð
'${^WIN32_SLOPPY_STAT}'         :    5,Ð
'$EXECUTABLE_NAME'              :    5,Ð
'$^X'                           :    5,Ð
'$1'                            :    5, // - regexp $1, $2...Ð
'$MATCH'                        :    5,Ð
'$&'                            :    5,Ð
'${^MATCH}'                     :    5,Ð
'$PREMATCH'                     :    5,Ð
'$`'                            :    5,Ð
'${^PREMATCH}'                  :    5,Ð
'$POSTMATCH'                    :    5,Ð
"$'"                            :    5,Ð
'${^POSTMATCH}'                 :    5,Ð
'$LAST_PAREN_MATCH'             :    5,Ð                '$
+'                            :    5,Ð
'$LAST_SUBMATCH_RESULT'         :    5,Ð
'$^N'                           :    5,Ð
'@LAST_MATCH_END'               :    5,Ð
'@+'                            :    5,Ð
'%LAST_PAREN_MATCH'             :    5,Ð                '%
+'                            :    5,Ð
'@LAST_MATCH_START'             :    5,Ð
'@-'                            :    5,Ð
```

```
'%LAST_MATCH_START'             :    5,Ð
'%-'                            :    5,Ð
'$LAST_REGEXP_CODE_RESULT'      :    5,Ð
'$^R'                           :    5,Ð
'${^RE_DEBUG_FLAGS}'            :    5,Ð
'${^RE_TRIE_MAXBUF}'            :    5,Ð
'$ARGV'                         :    5,Ð
'@ARGV'                         :    5,Ð
'ARGV'                          :    5,Ð
'ARGVOUT'                       :    5,Ð
'$OUTPUT_FIELD_SEPARATOR'       :    5,Ð
'$OFS'                          :    5,Ð
'$,'                            :    5,Ð
'$INPUT_LINE_NUMBER'            :    5,Ð
'$NR'                           :    5,Ð
'$.'                            :    5,Ð
'$INPUT_RECORD_SEPARATOR'       :    5,Ð
'$RS'                           :    5,Ð
'$/'                            :    5,Ð
'$OUTPUT_RECORD_SEPARATOR'      :    5,Ð
'$ORS'                          :    5,Ð                '$\
\'                            :    5,Ð
'$OUTPUT_AUTOFLUSH'             :    5,Ð
'$|'                            :    5,Ð
'$ACCUMULATOR'                  :    5,Ð
'$^A'                           :    5,Ð
'$FORMAT_FORMFEED'              :    5,Ð
'$^L'                           :    5,Ð
'$FORMAT_PAGE_NUMBER'           :    5,Ð                '$
%'                            :    5,Ð
'$FORMAT_LINES_LEFT'            :    5,Ð
'$-'                            :    5,Ð
'$FORMAT_LINE_BREAK_CHARACTERS' :    5,Ð
'$:'                            :    5,Ð
'$FORMAT_LINES_PER_PAGE'        :    5,Ð
'$='                            :    5,Ð
'$FORMAT_TOP_NAME'              :    5,Ð
'$^'                            :    5,Ð
'$FORMAT_NAME'                  :    5,Ð
'$~'                            :    5,Ð
'${^CHILD_ERROR_NATIVE}'        :    5,Ð
'$EXTENDED_OS_ERROR'            :    5,Ð
'$^E'                           :    5,Ð
'$EXCEPTIONS_BEING_CAUGHT'      :    5,Ð
'$^S'                           :    5,Ð
'$WARNING'                      :    5,Ð
'$^W'                           :    5,Ð
'${^WARNING_BITS}'              :    5,Ð
'$OS_ERROR'                     :    5,Ð
'$ERRNO'                        :    5,Ð
'$!'                            :    5,Ð
'%OS_ERROR'                     :    5,Ð
'%ERRNO'                        :    5,Ð
'%!'                            :    5,Ð
'$CHILD_ERROR'                  :    5,Ð
'$?'                            :    5,Ð
'$EVAL_ERROR'                   :    5,Ð
'$@'                            :    5,Ð
'$OFMT'                         :    5,Ð
```

```
'$#'                            :    5,Ð
'$*'                            :    5,Ð
'$ARRAY_BASE'                   :    5,Ð
'$['                            :    5,Ð
'$OLD_PERL_VERSION'             :    5,Ð
'$]'                            :    5,Ð
                                                //      PERL blocksÐ
                'if'                            :[1,1],Ð
elsif                           :[1,1],Ð
'else'                          :[1,1],Ð
'while'                         :[1,1],Ð
unless                          :[1,1],Ð
'for'                           :[1,1],Ð
foreach                         :[1,1],Ð
                                                //      PERL functionsÐ
                'abs'                           :1,     // - absolute value
functionÐ               accept                          :1,     // - accept
an incoming socket connectÐ
alarm                           :1,     // - schedule a SIGALRMÐ
                'atan2'                         :1,     // - arctangent of Y/
X in the range -PI to PIÐ
bind                            :1,     // - binds an address to a socketÐ
                binmode                         :1,     // - prepare binary
files for I/OÐ               bless                           :1,     // -
create an objectÐ               bootstrap                       :1,     //Ð
                'break'                         :1,     // - break out of a
"given" blockÐ               caller                          :1,     // - get
context of the current subroutine callÐ
chdir                           :1,     // - change your current working
directoryÐ               chmod                           :1,     // - changes
the permissions on a list of filesÐ
chomp                           :1,     // - remove a trailing record
separator from a stringÐ
chop                            :1,     // - remove the last character from a
stringÐ               chown                           :1,     // - change the
owership on a list of filesÐ
chr                             :1,     // - get character this number
representsÐ               chroot                          :1,     // - make
directory new root for path lookupsÐ
close                           :1,     // - close file (or pipe or socket)
handleÐ               closedir                        :1,     // - close
directory handleÐ               connect                         :1,     // -
connect to a remote socketÐ               'continue'                      :
[1,1], // - optional trailing block in a while or foreachÐ
'cos'                           :1,     // - cosine functionÐ
crypt                           :1,     // - one-way passwd-style encryptionÐ
                dbmclose                        :1,     // - breaks binding
on a tied dbm fileÐ               dbmopen                         :1,     //
- create binding on a tied dbm fileÐ
'default'                       :1,     //Ð
defined                         :1,     // - test whether a value, variable,
or function is definedÐ
'delete'                        :1,     // - deletes a value from a hashÐ
                die                             :1,     // - raise an
exception or bail outÐ
'do'                            :1,     // - turn a BLOCK into a TERMÐ
                dump                            :1,     // - create an
immediate core dumpÐ               each                            :1,     //
- retrieve the next key/value pair from a hashÐ
```

endgrent :1, // - be done using group fileÐ
endhostent :1, // - be done using hosts fileÐ
endnetent :1, // - be done using networks fileÐ
endprotoent :1, // - be done using protocols fileÐ
endpwent :1, // - be done using passwd fileÐ
endservent :1, // - be done using services fileÐ
eof :1, // - test a filehandle for its endÐ
'eval' :1, // - catch exceptions or compile and run codeÐ
'exec' :1, // - abandon this program to run anotherÐ
exists :1, // - test whether a hash key is presentÐ
exit :1, // - terminate this programÐ
'exp' :1, // - raise I to a powerÐ
fcntl :1, // - file control system callÐ
fileno :1, // - return file descriptor from filehandleÐ
flock :1, // - lock an entire file with an advisory lockÐ
fork :1, // - create a new process just like this oneÐ
format :1, // - declare a picture format with use by the write() functionÐ
formline :1, // - internal function used for formatsÐ
getc :1, // - get the next character from the filehandleÐ
getgrent :1, // - get next group recordÐ
getgrgid :1, // - get group record given group user IDÐ
getgrnam :1, // - get group record given group nameÐ
gethostbyaddr :1, // - get host record given its addressÐ
gethostbyname :1, // - get host record given nameÐ
gethostent :1, // - get next hosts recordÐ
getlogin :1, // - return who logged in at this ttyÐ
getnetbyaddr :1, // - get network record given its addressÐ
getnetbyname :1, // - get networks record given nameÐ
getnetent :1, // - get next networks recordÐ
getpeername :1, // - find the other end of a socket connectionÐ
getpgrp :1, // - get process groupÐ
getppid :1, // - get parent process IDÐ
getpriority :1, // - get current nice valueÐ
getprotobyname :1, // - get protocol record given nameÐ
getprotobynumber :1, // - get protocol record numeric protocolÐ
getprotoent :1, // - get next protocols recordÐ
getpwent :1, // - get next passwd recordÐ
getpwnam :1, // - get passwd record given user login nameÐ
getpwuid :1, // - get passwd record given user IDÐ
getservbyname :1, // - get services record given its nameÐ
getservbyport :1, // - get services record given numeric portÐ
getservent :1, // - get next services recordÐ
getsockname :1, // - retrieve the sockaddr for a given socketÐ

getsockopt :1, // - get socket options on a given
socketÐ given :1, //Ð
glob :1, // - expand filenames
using wildcardsÐ gmtime :1, // -
convert UNIX time into record or string using Greenwich timeÐ
'goto' :1, // - create spaghetti codeÐ
grep :1, // - locate elements
in a list test true against a given criterionÐ
hex :1, // - convert a string to a
hexadecimal numberÐ 'import' :1, //
- patch a module's namespace into your ownÐ
index :1, // - find a substring within a stringÐ
'int' :1, // - get the integer
portion of a numberÐ ioctl :1, //
- system-dependent device control system callÐ
'join' :1, // - join a list into a string using
a separatorÐ keys :1, // -
retrieve list of indices from a hashÐ
kill :1, // - send a signal to a process or
process groupÐ last :1, // -
exit a block prematurelyÐ
lc :1, // - return lower-case version of a
stringÐ lcfirst :1, // - return a
string with just the next letter in lower caseÐ
length :1, // - return the number of bytes in a
stringÐ 'link' :1, // - create a
hard link in the filesytemÐ
listen :1, // - register your socket as a serverÐ
local : 2, // - create a
temporary value for a global variable (dynamic scoping)Ð
localtime :1, // - convert UNIX time into record or
string using local timeÐ
lock :1, // - get a thread lock on a variable,
subroutine, or methodÐ
'log' :1, // - retrieve the natural logarithm
for a numberÐ lstat :1, // - stat
a symbolic linkÐ m :null, // -
match a string with a regular expression patternÐ
map :1, // - apply a change to a list to get
back a new list with the changesÐ
mkdir :1, // - create a directoryÐ
msgctl :1, // - SysV IPC message
control operationsÐ msgget :1, //
- get SysV IPC message queueÐ
msgrcv :1, // - receive a SysV IPC message from
a message queueÐ msgsnd :1, // -
send a SysV IPC message to a message queueÐ
my : 2, // - declare and assign a local
variable (lexical scoping)Ð
'new' :1, //Ð
next :1, // - iterate a block prematurelyÐ
no :1, // - unimport some
module symbols or semantics at compile timeÐ
oct :1, // - convert a string to an octal
numberÐ open :1, // - open a
file, pipe, or descriptorÐ
opendir :1, // - open a directoryÐ
ord :1, // - find a character's numeric
representationÐ

```
                                our                                 : 2,    // -
declare and assign a package variable (lexical scoping)Ð
pack                            :1,     // - convert a list into a binary
representationÐ                 'package'                           :1,     // -
declare a separate global namespaceÐ
pipe                            :1,     // - open a pair of connected
filehandlesÐ                pop                                 :1,     // -
remove the last element from an array and return itÐ
pos                             :1,     // - find or set the offset for the
last/next m//g searchÐ
print                           :1,     // - output a list to a filehandleÐ
                printf                          :1,     // - output a
formatted list to a filehandleÐ
prototype                       :1,     // - get the prototype (if any) of a
subroutineÐ                push                                :1,     // - append
one or more elements to an arrayÐ
q                               :null,  // - singly quote a stringÐ
                qq                              :null,  // - doubly quote a
stringÐ                qr                              :null,  // - Compile
patternÐ                quotemeta                       :null,  // - quote
regular expression magic charactersÐ
qw                              :null,  // - quote a list of wordsÐ
                qx                              :null,  // - backquote quote
a stringÐ                rand                            :1,     // - retrieve
the next pseudorandom numberÐ
read                            :1,     // - fixed-length buffered input from
a filehandleÐ                readdir                         :1,     // - get
a directory from a directory handleÐ
readline                        :1,     // - fetch a record from a fileÐ
                readlink                        :1,     // - determine where
a symbolic link is pointingÐ
readpipe                        :1,     // - execute a system command and
collect standard outputÐ
recv                            :1,     // - receive a message over a SocketÐ
                redo                            :1,     // - start this loop
iteration over againÐ
ref                             :1,     // - find out the type of thing being
referencedÐ                rename                          :1,     // - change
a filenameÐ                require                         :1,     // - load
in external functions from a library at runtimeÐ
reset                           :1,     // - clear all variables of a given
nameÐ                'return'                        :1,     // - get out of a
function earlyÐ                reverse                         :1,     // -
flip a string or a listÐ
rewinddir                       :1,     // - reset directory handleÐ
                rindex                          :1,     // - right-to-left
substring searchÐ                rmdir                           :1,     // -
remove a directoryÐ                s                               :null,  //
- replace a pattern with a stringÐ
say                             :1,     // - print with newlineÐ
                scalar                          :1,     // - force a scalar
contextÐ                seek                            :1,     // -
reposition file pointer for random-access I/OÐ
seekdir                         :1,     // - reposition directory pointerÐ
                select                          :1,     // - reset default
output or do I/O multiplexingÐ
semctl                          :1,     // - SysV semaphore control operationsÐ
                semget                          :1,     // - get set of SysV
semaphoresÐ                semop                           :1,     // - SysV
semaphore operationsÐ
```

send :1, // - send a message over a socketÐ
setgrent :1, // - prepare group
file for useÐ sethostent :1, // -
prepare hosts file for useÐ
setnetent :1, // - prepare networks file for useÐ
setpgrp :1, // - set the process
group of a processÐ setpriority :1, //
- set a process's nice valueÐ
setprotoent :1, // - prepare protocols file for useÐ
setpwent :1, // - prepare passwd
file for useÐ setservent :1, // -
prepare services file for useÐ
setsockopt :1, // - set some socket optionsÐ
shift :1, // - remove the first
element of an array, and return itÐ
shmctl :1, // - SysV shared memory operationsÐ
shmget :1, // - get SysV shared
memory segment identifierÐ
shmread :1, // - read SysV shared memoryÐ
shmwrite :1, // - write SysV
shared memoryÐ shutdown :1, // -
close down just half of a socket connectionÐ
'sin' :1, // - return the sine of a numberÐ
sleep :1, // - block for some
number of secondsÐ socket :1, // -
create a socketÐ socketpair :1, // -
create a pair of socketsÐ
'sort' :1, // - sort a list of valuesÐ
splice :1, // - add or remove
elements anywhere in an arrayÐ
'split' :1, // - split up a string using a regexp
delimiterÐ sprintf :1, // -
formatted print into a stringÐ
'sqrt' :1, // - square root functionÐ
srand :1, // - seed the random
number generatorÐ stat :1, // -
get a file's status informationÐ
state :1, // - declare and assign a state
variable (persistent lexical scoping)Ð
study :1, // - optimize input data for repeated
searchesÐ 'sub' :1, // - declare
a subroutine, possibly anonymouslyÐ
'substr' :1, // - get or alter a portion of a
stirngÐ symlink :1, // - create a
symbolic link to a fileÐ
syscall :1, // - execute an arbitrary system callÐ
sysopen :1, // - open a file,
pipe, or descriptorÐ sysread :1, //
- fixed-length unbuffered input from a filehandleÐ
sysseek :1, // - position I/O pointer on handle
used with sysread and syswriteÐ
system :1, // - run a separate programÐ
syswrite :1, // - fixed-length
unbuffered output to a filehandleÐ
tell :1, // - get current seekpointer on a
filehandleÐ telldir :1, // - get
current seekpointer on a directory handleÐ
tie :1, // - bind a variable to an object
classÐ

```
                    tied                            :1,     // - get a
reference to the object underlying a tied variableÐ
time                            :1,     // - return number of seconds since
1970Ð               times                           :1,     // - return
elapsed time for self and child processesÐ
tr                              :null,  // - transliterate a stringÐ
               truncate                        :1,     // - shorten a fileÐ
               uc                              :1,     // - return upper-
case version of a stringÐ
ucfirst                         :1,     // - return a string with just the
next letter in upper caseÐ
umask                           :1,     // - set file creation mode maskÐ
               undef                           :1,     // - remove a
variable or function definitionÐ
unlink                          :1,     // - remove one link to a fileÐ
               unpack                          :1,     // - convert binary
structure into normal perl variablesÐ
unshift                         :1,     // - prepend more elements to the
beginning of a listÐ               untie                           :1,     //
- break a tie binding to a variableÐ
use                             :1,     // - load in a module at compile timeÐ
               utime                           :1,     // - set a file's
last access and modify timesÐ
values                          :1,     // - return a list of the values in a
hashÐ               vec                             :1,     // - test or set
particular bits in a stringÐ
wait                            :1,     // - wait for any child process to dieÐ
               waitpid                         :1,     // - wait for a
particular child process to dieÐ
wantarray                       :1,     // - get void vs scalar vs list
context of current subroutine callÐ
warn                            :1,     // - print debugging infoÐ
               when                            :1,     //Ð
write                           :1,     // - print a picture recordÐ
               y                               :null}; // - transliterate a
stringÐ       var RXstyle="string-2";Ð       var RXmodifiers=/
[gosexim acplud]/;              // NOTE: "m", "s", "y" and "tr" need to
correct real modifiers for each regexp typeÐ       function
tokenChain(stream,state,chain,style,tail){     // NOTE: chain.length > 2 is
not working now (it's for s[...][...]geos;)Ð               state.chain=null;
                                //
           12   3tailÐ               state.style=null;Ð
state.tail=null;Ð               state.tokenize=function(stream,state){Ð
                        var e=false,c,i=0;Ð
while(c=stream.next()){Ð                                if(c===chain[i]&&!e){Ð
                                        if(chain[++i]!==undefined){Ð
                                                state.chain=chain[i];Ð
                                                state.style=style;Ð
                                                state.tail=tail;}Ð
                                        else if(tail)Ð
                                                stream.eatWhile(tail);Ð
                                        state.tokenize=tokenPerl;Ð
                                        return style;}Ð
                                e=!e&&c=="\\";}Ð                      return
style;};Ð                       return state.tokenize(stream,state);}Ð       function
tokenSOMETHING(stream,state,string){Ð
state.tokenize=function(stream,state){Ð
if(stream.string==string)Ð
state.tokenize=tokenPerl;Ð                      stream.skipToEnd();Ð
                        return "string";};Ð
```

```
                                                        return
state.tokenize(stream,state);}Ð       function tokenPerl(stream,state){Ð
                if(stream.eatSpace())Ð                        return null;Ð
                if(state.chain)Ð                      return
tokenChain(stream,state,state.chain,state.style,state.tail);Ð
if(stream.match(/^\-?[\d\.]/,false))Ð                        if(stream.match(/
^(\-?(\d*\.\d+(e[+-]?\d+)?|\d+\.\d*)|0x[\da-fA-F]+|0b[01]+|\d+(e[+-]?\d+)?)/))Ð
                                return 'number';Ð
if(stream.match(/^<<(?=\w)/)){                  // NOTE: <<SOMETHING\n...
\nSOMETHING\nÐ                        stream.eatWhile(/\w/);Ð
                        return
tokenSOMETHING(stream,state,stream.current().substr(2));}Ð
if(stream.sol()&&stream.match(/^\=item(?!\w)/)){// NOTE: \n=item...\n=cut\nÐ
                        return tokenSOMETHING(stream,state,'=cut');}Ð
                var ch=stream.next();Ð               if(ch=='"'||ch=="'")
{                         // NOTE: ' or " or <<'SOMETHING'\n...
\nSOMETHING\n or <<"SOMETHING"\n...\nSOMETHING\nÐ
if(prefix(stream, 3)=="<<"+ch){Ð                              var
p=stream.pos;Ð                                stream.eatWhile(/\w/);Ð
                                var n=stream.current().substr(1);Ð
                                if(n&&stream.eat(ch))Ð
                                        return tokenSOMETHING(stream,state,n);Ð
                                stream.pos=p;}Ð                       return
tokenChain(stream,state,[ch],"string");}Ð               if(ch=="q"){Ð
                        var c=look(stream, -2);Ð                       if(!
(c&&/\w/.test(c))){Ð                                    c=look(stream, 0);Ð
                                if(c=="x"){Ð
                                        c=look(stream, 1);Ð
                                        if(c=="("){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[")"],RXstyle,RXmodifiers);}Ð
                                        if(c=="["){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["]"],RXstyle,RXmodifiers);}Ð
                                        if(c=="{"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["}"],RXstyle,RXmodifiers);}Ð
                                        if(c=="<"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[">"],RXstyle,RXmodifiers);}Ð
                                        if(/[\^'"!~\/]/.test(c)){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[stream.eat(c)],RXstyle,RXmodifiers);}}Ð
                                else if(c=="q"){Ð
                                        c=look(stream, 1);Ð
                                        if(c=="("){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[")"],"string");}Ð
                                        if(c=="["){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["]"],"string");}Ð
                                        if(c=="{"){Ð
                                                eatSuffix(stream, 2);Ð
```

```
                                                        return
tokenChain(stream,state,["}"],"string");}Ð
                                        if(c=="<"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[">"],"string");}Ð
                                        if(/[\^'"!~\/]/.test(c)){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[stream.eat(c)],"string");}}Ð
                                else if(c=="w"){Ð
                                        c=look(stream, 1);Ð
                                        if(c=="("){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[")"],"bracket");}Ð
                                        if(c=="["){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["]"],"bracket");}Ð
                                        if(c=="{"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["}"],"bracket");}Ð
                                        if(c=="<"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[">"],"bracket");}Ð
                                        if(/[\^'"!~\/]/.test(c)){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[stream.eat(c)],"bracket");}}Ð
                                else if(c=="r"){Ð
                                        c=look(stream, 1);Ð
                                        if(c=="("){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[")"],RXstyle,RXmodifiers);}Ð
                                        if(c=="["){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["]"],RXstyle,RXmodifiers);}Ð
                                        if(c=="{"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,["}"],RXstyle,RXmodifiers);}Ð
                                        if(c=="<"){Ð
                                                eatSuffix(stream, 2);Ð
                                                return
tokenChain(stream,state,[">"],RXstyle,RXmodifiers);}Ð
                                        if(/[\^'"!~\/]/.test(c)){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[stream.eat(c)],RXstyle,RXmodifiers);}}Ð
                                else if(/[\^'"!~\/(\[{<]/.test(c)){Ð
                                        if(c=="("){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[")"],"string");}Ð
```

```
                                        if(c=="["){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,["]"],"string");}Ð
                                        if(c=="{"){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,["}"],"string");}Ð
                                        if(c=="<"){Ð
                                                eatSuffix(stream, 1);Ð
                                                return
tokenChain(stream,state,[">"],"string");}Ð
                                        if(/[\^'"!~\/]/.test(c)){Ð
                                                return
tokenChain(stream,state,[stream.eat(c)],"string");}}}}Ð
if(ch=="m"){Ð                        var c=look(stream, -2);Ð
                        if(!(c&&/\w/.test(c))){Ð
                                c=stream.eat(/[(\[{<\^'"!~\/]/);Ð
                                if(c){Ð
if(/[\^'"!~\/]/.test(c)){Ð
return tokenChain(stream,state,[c],RXstyle,RXmodifiers);}Ð
                                        if(c=="("){Ð
                                                return
tokenChain(stream,state,[")"],RXstyle,RXmodifiers);}Ð
                                        if(c=="["){Ð
                                                return
tokenChain(stream,state,["]"],RXstyle,RXmodifiers);}Ð
                                        if(c=="{"){Ð
                                                return
tokenChain(stream,state,["}"],RXstyle,RXmodifiers);}Ð
                                        if(c=="<"){Ð
                                                return
tokenChain(stream,state,[">"],RXstyle,RXmodifiers);}}}}Ð
if(ch=="s"){Ð                        var c=/[\/>\]})\w]/.test(look(stream,
-2));Ð                          if(!c){Ð
c=stream.eat(/[(\[{<\^'"!~\/]/);Ð                                if(c){Ð
                                        if(c==")Ð
                                                return
tokenChain(stream,state,["]","]"],RXstyle,RXmodifiers);Ð
                                        if(c=="{")Ð
                                                return
tokenChain(stream,state,["}","}"],RXstyle,RXmodifiers);Ð
                                        if(c=="<")Ð
                                                return
tokenChain(stream,state,[">",">"],RXstyle,RXmodifiers);Ð
                                        if(c=="(")Ð
                                                return
tokenChain(stream,state,[")",")"],RXstyle,RXmodifiers);Ð
                                        return tokenChain(stream,state,
[c,c],RXstyle,RXmodifiers);}}}Ð                 if(ch=="y"){Ð
                        var c=/[\/>\]})\w]/.test(look(stream, -2));Ð
                        if(!c){Ð                                c=stream.eat(/
[(\[{<\^'"!~\/]/);Ð                                if(c){Ð
                                        if(c=="[")Ð
                                                return
tokenChain(stream,state,["]","]"],RXstyle,RXmodifiers);Ð
                                        if(c=="{")Ð
                                                return
tokenChain(stream,state,["}","}"],RXstyle,RXmodifiers);Ð
```

```
                                        if(c=="<")Ð
                                                return
tokenChain(stream,state,[">",">"],RXstyle,RXmodifiers);Ð
                                        if(c=="(")Ð
                                                return
tokenChain(stream,state,[")",")"],RXstyle,RXmodifiers);Ð
                                        return tokenChain(stream,state,
[c,c],RXstyle,RXmodifiers);}}}Ð               if(ch=="t"){Ð
                        var c=/[\/>\]})\w]/.test(look(stream, -2));Ð
                        if(!c){Ð
c=stream.eat("r");if(c){Ð                               c=stream.eat(/
[(\[{<\^'"!~\/]/);Ð                               if(c){Ð
                                        if(c=="[")Ð
                                                return
tokenChain(stream,state,["]","]"],RXstyle,RXmodifiers);Ð
                                        if(c=="{")Ð
                                                return
tokenChain(stream,state,["}","}"],RXstyle,RXmodifiers);Ð
                                        if(c=="<")Ð
                                                return
tokenChain(stream,state,[">",">"],RXstyle,RXmodifiers);Ð
                                        if(c=="(")Ð
                                                return
tokenChain(stream,state,[")",")"],RXstyle,RXmodifiers);Ð
                                        return tokenChain(stream,state,
[c,c],RXstyle,RXmodifiers);}}}}Ð               if(ch=="`"){Ð
                        return tokenChain(stream,state,[ch],"variable-2");}Ð
                if(ch=="/"){Ð                       if(!/
~\s*$/.test(prefix(stream)))Ð                                   return "operator";Ð
                        elseÐ                                   return
tokenChain(stream,state,[ch],RXstyle,RXmodifiers);}Ð                   if(ch=="$")
{Ð                       var p=stream.pos;Ð
if(stream.eatWhile(/\d/)||stream.eat("{")&&stream.eatWhile(/
\d/)&&stream.eat("}"))Ð                                 return "variable-2";Ð
                        elseÐ                                   stream.pos=p;}Ð
                if(/[$@%]/.test(ch)){Ð                       var p=stream.pos;Ð
                        if(stream.eat("^")&&stream.eat(/[A-Z]/)||!/[@$
%&]/.test(look(stream, -2))&&stream.eat(/[=|\\\-#?@;:&`~\^!\[\]*'"$+.,\/
<>()]/)){Ð                               var c=stream.current();Ð
                                if(PERL[c])Ð
                                        return "variable-2";}Ð
                        stream.pos=p;}Ð                 if(/[$@%&]/.test(ch)){Ð
                        if(stream.eatWhile(/[\w$\[\]]/)||
stream.eat("{")&&stream.eatWhile(/[\w$\[\]]/)&&stream.eat("}")){Ð
                                var c=stream.current();Ð
                                if(PERL[c])Ð
                                        return "variable-2";Ð
                                elseÐ
return "variable";}}Ð                   if(ch=="#"){Ð
if(look(stream, -2)!="$"){Ð                                     stream.skipToEnd();Ð
                                return "comment";}}Ð                   if(/[:+\-
\^*$&%@=<>!?|\/~\.]/.test(ch)){Ð                        var p=stream.pos;Ð
                        stream.eatWhile(/[:+\-\^*$&%@=<>!?|\/~\.]/);Ð
                        if(PERL[stream.current()])Ð
                                return "operator";Ð                       elseÐ
                                stream.pos=p;}Ð                 if(ch=="_"){Ð
                        if(stream.pos==1){Ð
if(suffix(stream, 6)=="_END__"){Ð
return tokenChain(stream,state,['\0'],"comment");}Ð
```

```
                                else if(suffix(stream, 7)=="_DATA__"){Ð
                                        return tokenChain(stream,state,
['\0'],"variable-2");}Ð                                 else if(suffix(stream,
7)=="_C__"){Ð                                   return
tokenChain(stream,state,['\0'],"string");}}}Ð               if(/\w/.test(ch)){Ð
                        var p=stream.pos;Ð
if(look(stream, -2)=="{"&&(look(stream, 0)=="}"||stream.eatWhile(/
\w/)&&look(stream, 0)=="}"))Ð                               return "string";Ð
                        elseÐ                               stream.pos=p;}Ð
                if(/[A-Z]/.test(ch)){Ð                       var
l=look(stream, -2);Ð                        var p=stream.pos;Ð
                        stream.eatWhile(/[A-Z_]/);Ð                     if(/
[\da-z]/.test(look(stream, 0))){Ð                              stream.pos=p;}Ð
                        else{Ð                               var
c=PERL[stream.current()];Ð                             if(!c)Ð
                                        return "meta";Ð
                                if(c[1])Ð
                                        c=c[0];Ð
                                if(l!=":"){Ð
                                        if(c==1)Ð
                                                return "keyword";Ð
                                        else if(c==2)Ð
                                                return "def";Ð
                                        else if(c==3)Ð
                                                return "atom";Ð
                                        else if(c==4)Ð
                                                return "operator";Ð
                                        else if(c==5)Ð
                                                return "variable-2";Ð
                                        elseÐ
                                                return "meta";}Ð
                                elseÐ
return "meta";}}Ð               if(/[a-zA-Z_]/.test(ch)){Ð
                        var l=look(stream, -2);Ð
stream.eatWhile(/\w/);Ð                     var c=PERL[stream.current()];Ð
                        if(!c)Ð                                 return "meta";Ð
                        if(c[1])Ð                                 c=c[0];Ð
                        if(l!=":"){Ð                                 if(c==1)Ð
                                        return "keyword";Ð
                                else if(c==2)Ð
                                        return "def";Ð
                                else if(c==3)Ð
                                        return "atom";Ð
                                else if(c==4)Ð
                                        return "operator";Ð
                                else if(c==5)Ð
                                        return "variable-2";Ð
                                elseÐ
return "meta";}Ð                        elseÐ
return "meta";}Ð                return null;}Ð       return{Ð
startState:function(){Ð                     return{Ð
                                tokenize:tokenPerl,Ð
                                chain:null,Ð
style:null,Ð                            tail:null};},Ð
token:function(stream,state){Ð                          return (state.tokenize||
tokenPerl)(stream,state);}Ð                 };});Ð
CodeMirror.registerHelper("wordChars", "perl", /[\w$]/);Ð
CodeMirror.defineMIME("text/x-perl", "perl");Ð/ it's like "peek", but need
for look-ahead or look-behind if index < 0Ð
```

```
function look(stream, c){Ð return
stream.string.charAt(stream.pos+(c||0));}ÐÐ// return a part of prefix of
current stream from current positionÐfunction prefix(stream, c){Ð if(c){Ð
var x=stream.pos-c;Ð   return stream.string.substr((x>=0?x:0),c);}Ð else{Ð
return stream.string.substr(0,stream.pos-1);Ð }}ÐÐ// return a part of suffix of
current stream from current positionÐfunction suffix(stream, c){Ð var
y=stream.string.length;Ð var x=y-stream.pos+1;Ð return
stream.string.substr(stream.pos,(c&&c<y?c:x));}ÐÐ// eating and vomiting a part
of stream from current positionÐfunction eatSuffix(stream, c){Ð var
x=stream.pos+c;Ð var y;Ð if(x<=0)Ð   stream.pos=0;Ð else
if(x>=(y=stream.string.length-1))Ð   stream.pos=y;Ð elseÐ   stream.pos=x;}}ÐÐ);Ð
```

public\assets\js\plugins\codemirror\mode\php\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "php");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT('simple_test',Ð    '[meta <?php] ' +Ð    '[keyword echo] [string "aaa"]; '
+Ð    '[meta ?>]');Ð MT('variable_interpolation_non_alphanumeric',Ð    '[meta
<?php]',Ð    '[keyword echo] [string "aaa$~$!$@$#$$$%$^$&$*$($)$.$<$>$/$\\$}$\
\\"$:$;$?$|$[[$]]$+$=aaa"]',Ð    '[meta ?>]');Ð
MT('variable_interpolation_digits',Ð    '[meta <?php]',Ð    '[keyword echo]
[string "aaa$1$2$3$4$5$6$7$8$9$0aaa"]',Ð    '[meta ?>]');Ð
MT('variable_interpolation_simple_syntax_1',Ð    '[meta <?php]',Ð
'[keyword echo] [string "aaa][variable-2 $aaa][string .aaa"];',Ð    '[meta ?
>]');Ð MT('variable_interpolation_simple_syntax_2',Ð    '[meta <?php]',Ð
'[keyword echo] [string "][variable-2 $aaaa][[','[number 2]',         ']]
[string aa"];',Ð    '[keyword echo] [string "][variable-2 $aaaa][[','[number
2345]',      ']][string aa"];',Ð    '[keyword echo] [string "][variable-2
$aaaa][[','[number 2.3]',       ']][string aa"];',Ð    '[keyword echo]
[string "][variable-2 $aaaa][[','[variable aaaaa]',   ']][string aa"];',Ð
'[keyword echo] [string "][variable-2 $aaaa][[','[variable-2 $aaaaa]',']]
[string aa"];',Ð    '[keyword echo] [string "1aaa][variable-2 $aaaa]
[[','[number 2]',         ']][string aa"];',Ð    '[keyword echo] [string "aaa]
[variable-2 $aaaa][[','[number 2345]',      ']][string aa"];',Ð    '[keyword
echo] [string "aaa][variable-2 $aaaa][[','[number 2.3]',       ']][string
aa"];',Ð    '[keyword echo] [string "aaa][variable-2 $aaaa][[','[variable
aaaaa]',   ']][string aa"];',Ð    '[keyword echo] [string "aaa][variable-2
$aaaa][[','[variable-2 $aaaaa]',']][string aa"];',Ð    '[meta ?>]');Ð
MT('variable_interpolation_simple_syntax_3',Ð    '[meta <?php]',Ð
'[keyword echo] [string "aaa][variable-2 $aaaa]->[variable aaaaa]
[string .aaaaaa"];',Ð    '[keyword echo] [string "aaa][variable-2 $aaaa]
[string ->][variable-2 $aaaaa][string .aaaaaa"];',Ð    '[keyword echo]
[string "aaa][variable-2 $aaaa]->[variable aaaaa][string [[2]].aaaaaa"];',Ð
     '[keyword echo] [string "aaa][variable-2 $aaaa]->[variable aaaaa][string
->aaaa2.aaaaaa"];',Ð    '[meta ?>]');Ð MT('variable_interpolation_escaping',Ð
     '[meta <?php] [comment /* Escaping */]',Ð    '[keyword echo] [string
"aaa\\$aaaa->aaa.aaa"];',Ð    '[keyword echo] [string "aaa\\
$aaaa[[2]]aaa.aaa"];',Ð    '[keyword echo] [string "aaa\\
$aaaa[[asd]]aaa.aaa"];',Ð    '[keyword echo] [string "aaa{\\$aaaa-
>aaa.aaa"];',Ð    '[keyword echo] [string "aaa{\\$aaaa[[2]]aaa.aaa"];',Ð
'[keyword echo] [string "aaa{\\aaaaa[[asd]]aaa.aaa"];',Ð    '[keyword echo]
[string "aaa\\${aaaa->aaa.aaa"];',Ð    '[keyword echo] [string "aaa\\
${aaaa[[2]]aaa.aaa"];',Ð    '[keyword echo] [string "aaa\\
${aaaa[[asd]]aaa.aaa"];',Ð    '[meta ?>]');Ð
MT('variable_interpolation_complex_syntax_1',Ð    '[meta <?php]',Ð
'[keyword echo] [string "aaa][variable-2 $]{[variable aaaa]}[string -
>aaa.aaa"];',Ð    '[keyword echo] [string "aaa][variable-2 $]{[variable-2
$aaaa]}[string ->aaa.aaa"];',Ð    '[keyword echo] [string "aaa][variable-2 $]
{[variable-2 $aaaa][[','  [number 42]',']]}[string ->aaa.aaa"];',Ð
'[keyword echo] [string "aaa][variable-2 $]{[variable aaaa][meta ?>]aaaaaa');Ð
  MT('variable_interpolation_complex_syntax_2',Ð    '[meta <?php] [comment /*
Monsters */]',Ð    '[keyword echo] [string "][variable-2 $]{[variable aaa]
[comment /*}?>} $aaa<?php } */]}[string ->aaa.aaa"];',Ð    '[keyword echo]
[string "][variable-2 $]{[variable aaa][comment /*}?>*/][[','  [string "aaa]
[variable-2 $aaa][string {}][variable-2 $]{[variable aaa]}[string "]','']]}
[string ->aaa.aaa"];',Ð    '[keyword echo] [string "][variable-2 $]{[variable
aaa][comment /*} } $aaa } */]}[string ->aaa.aaa"];');Ð function
build_recursive_monsters(nt, t, n){Ð   var monsters = [t];Ð   for (var i = 1;
i <= n; ++i)Ð     monsters[i] = nt.join(monsters[i - 1]);Ð   return monsters;Ð
  }Ð var m1 = build_recursive_monsters(Ð   ['[string "][variable-2 $]
{[variable aaa] [operator +] ', '}[string "]'],Ð
```

```
                                                        '[comment /* }?>} */]
[string "aaa][variable-2 $aaa][string .aaa"]',Ð   10Ð );Ð
MT('variable_interpolation_complex_syntax_3_1',Ð    '[meta <?php] [comment /*
Recursive monsters */]',Ð    '[keyword echo] ' + m1[4] + ';',Ð    '[keyword
echo] ' + m1[7] + ';',Ð    '[keyword echo] ' + m1[8] + ';',Ð    '[keyword
echo] ' + m1[5] + ';',Ð    '[keyword echo] ' + m1[1] + ';',Ð    '[keyword
echo] ' + m1[6] + ';',Ð    '[keyword echo] ' + m1[9] + ';',Ð    '[keyword
echo] ' + m1[0] + ';',Ð    '[keyword echo] ' + m1[10] + ';',Ð    '[keyword
echo] ' + m1[2] + ';',Ð    '[keyword echo] ' + m1[3] + ';',Ð    '[keyword
echo] [string "end"];',Ð    '[meta ?>]');Ð var m2 = build_recursive_monsters(Ð
    ['[string "a][variable-2 $]{[variable aaa] [operator +] ', ' [operator +]
', '}[string .a"]'],Ð   '[comment /* }?>{{ */] [string "a?>}{{aa][variable-2
$aaa][string .a}a?>a"]',Ð   5Ð );Ð
MT('variable_interpolation_complex_syntax_3_2',Ð    '[meta <?php] [comment /*
Recursive monsters 2 */]',Ð    '[keyword echo] ' + m2[0] + ';',Ð    '[keyword
echo] ' + m2[1] + ';',Ð    '[keyword echo] ' + m2[5] + ';',Ð    '[keyword
echo] ' + m2[4] + ';',Ð    '[keyword echo] ' + m2[2] + ';',Ð    '[keyword
echo] ' + m2[3] + ';',Ð    '[keyword echo] [string "end"];',Ð    '[meta ?>]');Ð
  function build_recursive_monsters_2(mf1, mf2, nt, t, n){Ð   var monsters =
[t];Ð   for (var i = 1; i <= n; ++i)Ð     monsters[i] = nt[0] + mf1[i - 1] +
nt[1] + mf2[i - 1] + nt[2] + monsters[i - 1] + nt[3];Ð   return monsters;Ð }Ð
var m3 = build_recursive_monsters_2(Ð   m1,Ð   m2,Ð   ['[string "a]
[variable-2 $]{[variable aaa] [operator +] ', ' [operator +] ', ' [operator
+] ', '}[string .a"]'],Ð   '[comment /* }?>{{ */] [string "a?>}{{aa]
[variable-2 $aaa][string .a}a?>a"]',Ð   4Ð );Ð
MT('variable_interpolation_complex_syntax_3_3',Ð    '[meta <?php] [comment /*
Recursive monsters 2 */]',Ð    '[keyword echo] ' + m3[4] + ';',Ð    '[keyword
echo] ' + m3[0] + ';',Ð    '[keyword echo] ' + m3[3] + ';',Ð    '[keyword
echo] ' + m3[1] + ';',Ð    '[keyword echo] ' + m3[2] + ';',Ð    '[keyword
echo] [string "end"];',Ð    '[meta ?>]');Ð
MT("variable_interpolation_heredoc",Ð    "[meta <?php]",Ð    "[string
<<<here]",Ð    "[string doc ][variable-2 $]{[variable yay]}[string more]",Ð
     "[string here]; [comment // normal]");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\pig\pig.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others/ Distributed
under an MIT license: http://codemirror.net/LICENSE*      Pig Latin Mode
for CodeMirror 2*      @author Prasanth Jayachandran*      @link   https://
github.com/prasanthj/pig-codemirror-2*  This implementation is adapted from
PL/SQL mode in CodeMirror 2.*/function(mod) { if (typeof exports ==
"object" && typeof module == "object") // CommonJS   mod(require("../../lib/
codemirror"));  else if (typeof define == "function" && define.amd) // AMD
define(["../../lib/codemirror"], mod);  else // Plain browser env
mod(CodeMirror);})(function(CodeMirror) {"use strict";
CodeMirror.defineMode("pig", function(_config, parserConfig) { var keywords
= parserConfig.keywords,  builtins = parserConfig.builtins,  types =
parserConfig.types,  multiLineStrings = parserConfig.multiLineStrings;  var
isOperatorChar = /[*+\-%<>=&?:\/!|]/;  function chain(stream, state, f) {
state.tokenize = f;   return f(stream, state);  }  var type;  function
ret(tp, style) {   type = tp;   return style;  }  function
tokenComment(stream, state) {   var isEnd = false;   var ch;   while(ch =
stream.next()) {     if(ch == "/" && isEnd) {       state.tokenize =
tokenBase;       break;     }     isEnd = (ch == "*");   }   return
ret("comment", "comment");  }  function tokenString(quote) {   return
function(stream, state) {     var escaped = false, next, end = false;
while((next = stream.next()) != null) {       if (next == quote && !escaped)
{         end = true; break;       }       escaped = !escaped && next == "\
\";     }     if (end || !(escaped || multiLineStrings))
state.tokenize = tokenBase;     return ret("string", "error");   };  }
function tokenBase(stream, state) {   var ch = stream.next();   // is a
start of string?   if (ch == '"' || ch == "'")     return chain(stream,
state, tokenString(ch));   // is it one of the special chars   else if(/
[\[\]{}\(\),;\.]/.test(ch))     return ret(ch);   // is it a number?
else if(/\d/.test(ch)) {     stream.eatWhile(/[\w\.]/);     return
ret("number", "number");   }   // multi line comment or operator   else if
(ch == "/") {     if (stream.eat("*")) {       return chain(stream, state,
tokenComment);     }     else {       stream.eatWhile(isOperatorChar);
        return ret("operator", "operator");     }   }   // single line
comment or operator   else if (ch=="-") {     if(stream.eat("-")){
stream.skipToEnd();       return ret("comment", "comment");     }     else
{       stream.eatWhile(isOperatorChar);       return ret("operator",
"operator");     }   }   // is it an operator   else if
(isOperatorChar.test(ch)) {     stream.eatWhile(isOperatorChar);     return
ret("operator", "operator");   }   else {     // get the while word
stream.eatWhile(/[\w\$_]/);     // is it one of the listed keywords?     if
(keywords && keywords.propertyIsEnumerable(stream.current().toUpperCase())) {
        if (stream.eat(")") || stream.eat(".")) {         //keywords can be
used as variables like flatten(group), group.$0 etc..       }       else {
          return ("keyword", "keyword");       }     }     // is it one of
the builtin functions?     if (builtins &&
builtins.propertyIsEnumerable(stream.current().toUpperCase()))     {
return ("keyword", "variable-2");     }     // is it one of the listed
types?     if (types &&
types.propertyIsEnumerable(stream.current().toUpperCase()))       return
("keyword", "variable-3");     // default is a 'variable'     return
ret("variable", "pig-word");   }  }  // Interface  return {   startState:
function() {     return {       tokenize: tokenBase,       startOfLine:
true     };   },   token: function(stream, state) {
if(stream.eatSpace()) return null;     var style = state.tokenize(stream,
state);     return style;   }  };});function() {  function keywords(str) {
    var obj = {}, words = str.split(" ");   for (var i = 0; i <
words.length; ++i) obj[words[i]] = true;   return obj;  }  // builtin funcs
taken from trunk revision 1303237  var pBuiltins = "ABS ACOS ARITY ASIN ATAN
AVG BAGSIZE BINSTORAGE BLOOM BUILDBLOOM CBRT CEIL "
```

```
                                                        + "CONCAT COR COS COSH
COUNT COUNT_STAR COV CONSTANTSIZE CUBEDIMENSIONS DIFF DISTINCT DOUBLEABS "Ð
+ "DOUBLEAVG DOUBLEBASE DOUBLEMAX DOUBLEMIN DOUBLEROUND DOUBLESUM EXP FLOOR
FLOATABS FLOATAVG "Ð   + "FLOATMAX FLOATMIN FLOATROUND FLOATSUM
GENERICINVOKER INDEXOF INTABS INTAVG INTMAX INTMIN "Ð   + "INTSUM
INVOKEFORDOUBLE INVOKEFORFLOAT INVOKEFORINT INVOKEFORLONG INVOKEFORSTRING
INVOKER "Ð   + "ISEMPTY JSONLOADER JSONMETADATA JSONSTORAGE LAST_INDEX_OF
LCFIRST LOG LOG10 LOWER LONGABS "Ð   + "LONGAVG LONGMAX LONGMIN LONGSUM MAX
MIN MAPSIZE MONITOREDUDF NONDETERMINISTIC OUTPUTSCHEMA  "Ð   + "PIGSTORAGE
PIGSTREAMING RANDOM REGEX_EXTRACT REGEX_EXTRACT_ALL REPLACE ROUND SIN SINH
SIZE "Ð   + "SQRT STRSPLIT SUBSTRING SUM STRINGCONCAT STRINGMAX STRINGMIN
STRINGSIZE TAN TANH TOBAG "Ð   + "TOKENIZE TOMAP TOP TOTUPLE TRIM TEXTLOADER
TUPLESIZE UCFIRST UPPER UTF8STORAGECONVERTER ";Ð // taken from QueryLexer.gÐ
var pKeywords = "VOID IMPORT RETURNS DEFINE LOAD FILTER FOREACH ORDER CUBE
DISTINCT COGROUP "Ð   + "JOIN CROSS UNION SPLIT INTO IF OTHERWISE ALL AS BY
USING INNER OUTER ONSCHEMA PARALLEL "Ð   + "PARTITION GROUP AND OR NOT
GENERATE FLATTEN ASC DESC IS STREAM THROUGH STORE MAPREDUCE "Ð   + "SHIP
CACHE INPUT OUTPUT STDERROR STDIN STDOUT LIMIT SAMPLE LEFT RIGHT FULL EQ GT
LT GTE LTE "Ð   + "NEQ MATCHES TRUE FALSE DUMP";Ð // data typesÐ var pTypes =
"BOOLEAN INT LONG FLOAT DOUBLE CHARARRAY BYTEARRAY BAG TUPLE MAP ";Ð
CodeMirror.defineMIME("text/x-pig", {Ð   name: "pig",Ð   builtins:
keywords(pBuiltins),Ð   keywords: keywords(pKeywords),Ð   types:
keywords(pTypes)Ð });Ð CodeMirror.registerHelper("hintWords", "pig",
(pBuiltins + pTypes + pKeywords).split(" "));Ð});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\properties\properties.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("properties", function() {Ð return {Ð   token:
function(stream, state) {Ð     var sol = stream.sol() || state.afterSection;Ð
      var eol = stream.eol();Ð     state.afterSection = false;Ð     if (sol) {Ð
        if (state.nextMultiline) {Ð         state.inMultiline = true;Ð
          state.nextMultiline = false;Ð       } else {Ð
state.position = "def";Ð       }Ð     }Ð     if (eol && !
state.nextMultiline) {Ð       state.inMultiline = false;Ð
state.position = "def";Ð     }Ð     if (sol) {Ð
while(stream.eatSpace());Ð     }Ð     var ch = stream.next();Ð     if (sol &&
(ch === "#" || ch === "!" || ch === ";")) {Ð       state.position = "comment";Ð
        stream.skipToEnd();Ð       return "comment";Ð     } else if (sol &&
ch === "[") {Ð       state.afterSection = true;Ð       stream.skipTo("]");
stream.eat("]");Ð       return "header";Ð     } else if (ch === "=" || ch ===
":") {Ð       state.position = "quote";Ð       return null;Ð     } else if
(ch === "\\" && state.position === "quote") {Ð       if (stream.next() !==
"u") {    // u = Unicode sequence \u1234 Ð         // Multiline value Ð
state.nextMultiline = true;Ð       }Ð     }Ð     return state.position;Ð   },Ð
    startState: function() {Ð     return {Ð       position : "def",       //
Current position, "def", "quote" or "comment" Ð       nextMultiline :
false,  // Is the next line multiline value Ð       inMultiline : false,    //
Is the current line a multiline value Ð       afterSection : false    // Did
we just open a section Ð     };Ð   }Ð };Ð });Ð CodeMirror.defineMIME("text/x-
properties", "properties");Ð CodeMirror.defineMIME("text/x-ini", "properties");Ð
});Ð
```

public\assets\js\plugins\codemirror\mode\puppet\puppet.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("puppet", function () {Ð // Stores the words from the
define method Ð var words = {};Ð // Taken, mostly, from the Puppet official
variable standards regex Ð var variable_regex = /({)?([a-z][a-z0-9_]*)?((::[a-
z][a-z0-9_]*)*::)?[a-zA-Z0-9_]+(})?/;Ð // Takes a string of words separated
by spaces and adds them as Ð // keys with the value of the first argument
'style' Ð function define(style, string) {Ð   var split = string.split(' ');Ð
    for (var i = 0; i < split.length; i++) {Ð     words[split[i]] = style;Ð
    }Ð }Ð // Takes commonly known puppet types/words and classifies them to a
style Ð define('keyword', 'class define site node include import inherits');Ð
define('keyword', 'case if else in and elsif default or');Ð define('atom',
'false true running present absent file directory undef');Ð define('builtin',
'action augeas burst chain computer cron destination dport exec ' +Ð   'file
filebucket group host icmp iniface interface jump k5login limit log_level ' +Ð
    'log_prefix macauthorization mailalias maillist mcx mount nagios_command
' +Ð   'nagios_contact nagios_contactgroup nagios_host nagios_hostdependency
' +Ð   'nagios_hostescalation nagios_hostextinfo nagios_hostgroup
nagios_service ' +Ð   'nagios_servicedependency nagios_serviceescalation
nagios_serviceextinfo ' +Ð   'nagios_servicegroup nagios_timeperiod name
notify outiface package proto reject ' +Ð   'resources router schedule
scheduled_task selboolean selmodule service source ' +Ð   'sport
ssh_authorized_key sshkey stage state table tidy todest toports tosource ' +Ð
    'user vlan yumrepo zfs zone zpool');Ð // After finding a start of a
string ('|") this function attempts to find the end;Ð // If a variable is
encountered along the way, we display it differently when it Ð // is
encapsulated in a double-quoted string.Ð function tokenString(stream, state) {Ð
    var current, prev, found_var = false;Ð   while (!stream.eol() && (current
= stream.next()) != state.pending) {Ð     if (current === '$' && prev != '\\'
&& state.pending == '"') {Ð       found_var = true;Ð       break;Ð     }Ð
prev = current;Ð   }Ð   if (found_var) {Ð     stream.backUp(1);Ð   }Ð   if
(current == state.pending) {Ð     state.continueString = false;Ð   } else {Ð
      state.continueString = true;Ð   }Ð   return "string";Ð }Ð // Main
function Ð function tokenize(stream, state) {Ð   // Matches one whole word Ð
var word = stream.match(/[\w]+/, false);Ð   // Matches attributes (i.e.
ensure => present ; 'ensure' would be matched)Ð   var attribute =
stream.match(/(\s+)?\w+\s+=>.*/, false);Ð   // Matches non-builtin resource
declarations Ð   // (i.e. "apache::vhost {" or "mycustomclasss {" would be
matched)Ð   var resource = stream.match(/(\s+)?[\w:_]+(\s+)?{/, false);Ð   //
Matches virtual and exported resources (i.e. @@user { ; and the like)Ð   var
special_resource = stream.match(/(\s+)?[@]{1,2}[\w:_]+(\s+)?{/, false);Ð   //
Finally advance the stream Ð   var ch = stream.next();Ð   // Have we found a
variable?Ð   if (ch === '$') {Ð     if (stream.match(variable_regex)) {Ð
        // If so, and its in a string, assign it a different color Ð
return state.continueString ? 'variable-2' : 'variable';Ð     }Ð     //
Otherwise return an invalid variable Ð     return "error";Ð   }Ð   // Should
we still be looking for the end of a string?Ð   if (state.continueString) {Ð
      // If so, go through the loop again Ð     stream.backUp(1);Ð     return
tokenString(stream, state);Ð   }Ð   // Are we in a definition (class, node,
define)?Ð   if (state.inDefinition) {Ð     // If so, return def (i.e. for
'class myclass {' ; 'myclass' would be matched)Ð     if (stream.match(/(\s+)?
[\w:_]+(\s+)?/)) {Ð       return 'def';Ð     }Ð     // Match the rest it the
next time around Ð     stream.match(/\s+{/);Ð     state.inDefinition = false;Ð
    }Ð   // Are we in an 'include' statement?Ð   if (state.inInclude) {Ð
      // Match and return the included class Ð
```

```
                                                    stream.match(/(\s+)?
\S+(\s+)?/);Ð     state.inInclude = false;Ð     return 'def';Ð   }Ð   // Do
we just have a function on our hands?Ð   // In 'ensure_resource("myclass")',
'ensure_resource' is matchedÐ   if (stream.match(/(\s+)?\w+\(/)) {Ð
stream.backUp(1);Ð     return 'def';Ð   }Ð   // Have we matched the prior
attribute regex?Ð   if (attribute) {Ð     stream.match(/(\s+)?\w+/);Ð
return 'tag';Ð   }Ð   // Do we have Puppet specific words?Ð   if (word &&
words.hasOwnProperty(word)) {Ð     // Negates the initial next()Ð
stream.backUp(1);Ð     // Acutally move the streamÐ     stream.match(/[\w]+/);Ð
      // We want to process these words differentlyÐ     // do to the
importance they have in PuppetÐ     if (stream.match(/\s+\S+\s+{/, false)) {Ð
        state.inDefinition = true;Ð     }Ð     if (word == 'include') {Ð
        state.inInclude = true;Ð     }Ð     // Returns their value as state
in the prior define methodsÐ     return words[word];Ð   }Ð   // Is there a
match on a reference?Ð   if (/(\s+)?[A-Z]/.test(word)) {Ð     // Negate the
next()Ð     stream.backUp(1);Ð     // Match the full referenceÐ
stream.match(/(\s+)?[A-Z][\w:_]+/);Ð     return 'def';Ð   }Ð   // Have we
matched the prior resource regex?Ð   if (resource) {Ð     stream.match(/(\s+)?
[\w:_]+/);Ð     return 'def';Ð   }Ð   // Have we matched the prior
special_resource regex?Ð   if (special_resource) {Ð     stream.match(/(\s+)?
[@]{1,2}/);Ð     return 'special';Ð   }Ð   // Match all the comments. All of
them.Ð   if (ch == "#") {Ð     stream.skipToEnd();Ð     return "comment";Ð   }Ð
    // Have we found a string?Ð   if (ch == "'" || ch == '"') {Ð     // Store
the type (single or double)Ð     state.pending = ch;Ð     // Perform the
looping function to find the endÐ     return tokenString(stream, state);Ð   }Ð
    // Match all the bracketsÐ   if (ch == '{' || ch == '}') {Ð     return
'bracket';Ð   }Ð   // Match characters that we are going to assumeÐ   // are
trying to be regexÐ   if (ch == '/') {Ð     stream.match(/.*?\//);Ð
return 'variable-3';Ð   }Ð   // Match all the numbersÐ   if (ch.match(/
[0-9]/)) {Ð     stream.eatWhile(/[0-9]+/);Ð     return 'number';Ð   }Ð   //
Match the '=' and '=>' operatorsÐ   if (ch == '=') {Ð     if (stream.peek()
== '>') {Ð         stream.next();Ð     }Ð     return "operator";Ð   }Ð   //
Keep advancing through all the restÐ   stream.eatWhile(/[\w-]/);Ð   // Return
a blank line for everything elseÐ   return null;Ð }Ð // Start it allÐ return {Ð
    startState: function () {Ð     var state = {};Ð     state.inDefinition =
false;Ð     state.inInclude = false;Ð     state.continueString = false;Ð
state.pending = false;Ð     return state;Ð   },Ð   token: function (stream,
state) {Ð     // Strip the spaces, but regex will account for them eitherwayÐ
      if (stream.eatSpace()) return null;Ð     // Go through the main processÐ
      return tokenize(stream, state);Ð   }Ð };Ð});ÐodeMirror.defineMIME("text/
x-puppet", "puppet");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\python\python.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
  function wordRegexp(words) {Ð   return new RegExp("^((" + words.join(")|(")
+ "))\\b");Ð }Ð var wordOperators = wordRegexp(["and", "or", "not", "is"]);Ð
var commonKeywords = ["as", "assert", "break", "class", "continue",Ð
                        "def", "del", "elif", "else", "except", "finally",Ð
                        "for", "from", "global", "if", "import",Ð
                        "lambda", "pass", "raise", "return",Ð
                        "try", "while", "with", "yield", "in"];Ð var
commonBuiltins = ["abs", "all", "any", "bin", "bool", "bytearray",
"callable", "chr",Ð                       "classmethod", "compile",
"complex", "delattr", "dict", "dir", "divmod",Ð
"enumerate", "eval", "filter", "float", "format", "frozenset",Ð
                        "getattr", "globals", "hasattr", "hash", "help",
"hex", "id",Ð                         "input", "int", "isinstance",
"issubclass", "iter", "len",Ð                         "list", "locals", "map",
"max", "memoryview", "min", "next",Ð                       "object", "oct",
"open", "ord", "pow", "property", "range",Ð                       "repr",
"reversed", "round", "set", "setattr", "slice",Ð
"sorted", "staticmethod", "str", "sum", "super", "tuple",Ð
                        "type", "vars", "zip", "__import__", "NotImplemented",Ð
                        "Ellipsis", "__debug__"];Ð var py2 = {builtins:
["apply", "basestring", "buffer", "cmp", "coerce", "execfile",Ð
                        "file", "intern", "long", "raw_input", "reduce",
"reload",Ð                         "unichr", "unicode", "xrange", "False",
"True", "None"],Ð            keywords: ["exec", "print"]};Ð var py3 =
{builtins: ["ascii", "bytes", "exec", "print"],Ð            keywords:
["nonlocal", "False", "True", "None"]};Ð
CodeMirror.registerHelper("hintWords", "python",
commonKeywords.concat(commonBuiltins));Ð function top(state) {Ð   return
state.scopes[state.scopes.length - 1];Ð }Ð CodeMirror.defineMode("python",
function(conf, parserConf) {Ð   var ERRORCLASS = "error";Ð   var
singleDelimiters = parserConf.singleDelimiters || new RegExp("^[\\(\\)\\[\\]\
\{\\}@,:`=;\\.]");Ð   var doubleOperators = parserConf.doubleOperators || new
RegExp("^((==)|(!=)|(<=)|(>=)|(<>)|(<<)|(>>)|(//)|(\\*\\*))");Ð   var
doubleDelimiters = parserConf.doubleDelimiters || new RegExp("^((\\+=)|(\\-=)|
(\\*=)|(%=)|(/=)|(&=)|(\\|=)|(\\^=))");Ð   var tripleDelimiters =
parserConf.tripleDelimiters || new RegExp("^((//=)|(>>=)|(<<=)|(\\*\\*=))");Ð
    if (parserConf.version && parseInt(parserConf.version, 10) == 3){Ð
        // since http://legacy.python.org/dev/peps/pep-0465/ @ is also an
operatorÐ       var singleOperators = parserConf.singleOperators || new
RegExp("^[\\+\\-\\*/%&|\\^~<>!@]");Ð       var identifiers =
parserConf.identifiers|| new RegExp("^[_A-Za-z\u00A1-\uFFFF][_A-Za-z0-9\u00A1-
\uFFFF]*");Ð   } else {Ð       var singleOperators =
parserConf.singleOperators || new RegExp("^[\\+\\-\\*/%&|\\^~<>!]");Ð
var identifiers = parserConf.identifiers|| new RegExp("^[_A-Za-z][_A-Za-
z0-9]*");Ð   }Ð   var hangingIndent = parserConf.hangingIndent ||
conf.indentUnit;Ð   var myKeywords = commonKeywords, myBuiltins =
commonBuiltins;Ð   if(parserConf.extra_keywords != undefined){Ð
myKeywords = myKeywords.concat(parserConf.extra_keywords);Ð   }Ð
if(parserConf.extra_builtins != undefined){Ð     myBuiltins =
myBuiltins.concat(parserConf.extra_builtins);Ð   }Ð   if (parserConf.version
&& parseInt(parserConf.version, 10) == 3) {Ð     myKeywords =
myKeywords.concat(py3.keywords);Ð     myBuiltins =
myBuiltins.concat(py3.builtins);Ð
```

```
                                        var stringPrefixes = new
RegExp("^(([rb]|(br))?('{3}|\"{3}|['\"]))", "i");Ð   } else {Ð     myKeywords
= myKeywords.concat(py2.keywords);Ð     myBuiltins =
myBuiltins.concat(py2.builtins);Ð     var stringPrefixes = new
RegExp("^(([rub]|(ur)|(br))?('{3}|\"{3}|['\"]))", "i");Ð   }Ð   var keywords
= wordRegexp(myKeywords);Ð   var builtins = wordRegexp(myBuiltins);Ð   //
tokenizersÐ   function tokenBase(stream, state) {Ð     // Handle scope changesÐ
      if (stream.sol() && top(state).type == "py") {Ð       var scopeOffset =
top(state).offset;Ð       if (stream.eatSpace()) {Ð         var lineOffset =
stream.indentation();Ð         if (lineOffset > scopeOffset)Ð
pushScope(stream, state, "py");Ð         else if (lineOffset < scopeOffset &&
dedent(stream, state))Ð           state.errorToken = true;Ð         return
null;Ð       } else {Ð         var style = tokenBaseInner(stream, state);Ð
          if (scopeOffset > 0 && dedent(stream, state))Ð           style += "
" + ERRORCLASS;Ð         return style;Ð       }Ð     }Ð     return
tokenBaseInner(stream, state);Ð   }Ð   function tokenBaseInner(stream, state)
{Ð     if (stream.eatSpace()) return null;Ð     var ch = stream.peek();Ð
      // Handle CommentsÐ     if (ch == "#") {Ð       stream.skipToEnd();Ð
        return "comment";Ð     }Ð     // Handle Number LiteralsÐ     if
(stream.match(/^[0-9\.]/, false)) {Ð       var floatLiteral = false;Ð
        // FloatsÐ       if (stream.match(/^\d*\.\d+(e[\+\-]?\d+)?/i))
{ floatLiteral = true; }Ð       if (stream.match(/^\d+\.\d*/)) { floatLiteral
= true; }Ð       if (stream.match(/^\.\d+/)) { floatLiteral = true; }Ð
if (floatLiteral) {Ð         // Float literals may be "imaginary"Ð
stream.eat(/J/i);Ð         return "number";Ð       }Ð       // IntegersÐ
        var intLiteral = false;Ð       // HexÐ       if (stream.match(/
^0x[0-9a-f]+/i)) intLiteral = true;Ð       // BinaryÐ       if (stream.match(/
^0b[01]+/i)) intLiteral = true;Ð       // OctalÐ       if (stream.match(/
^0o[0-7]+/i)) intLiteral = true;Ð       // DecimalÐ       if (stream.match(/
^[1-9]\d*(e[\+\-]?\d+)?/)) {Ð         // Decimal literals may be "imaginary"Ð
          stream.eat(/J/i);Ð         // TODO - Can you have imaginary longs?Ð
          intLiteral = true;Ð       }Ð       // Zero by itself with no other
piece of number.Ð       if (stream.match(/^0(?![\dx])/i)) intLiteral = true;Ð
        if (intLiteral) {Ð         // Integer literals may be "long"Ð
stream.eat(/L/i);Ð         return "number";Ð       }Ð     }Ð     // Handle
StringsÐ     if (stream.match(stringPrefixes)) {Ð       state.tokenize =
tokenStringFactory(stream.current());Ð       return state.tokenize(stream,
state);Ð     }Ð     // Handle operators and DelimitersÐ     if
(stream.match(tripleDelimiters) || stream.match(doubleDelimiters))Ð
return null;Ð     if (stream.match(doubleOperators)Ð         ||
stream.match(singleOperators)Ð         || stream.match(wordOperators))Ð
return "operator";Ð     if (stream.match(singleDelimiters))Ð       return
null;Ð     if (stream.match(keywords))Ð       return "keyword";Ð     if
(stream.match(builtins))Ð       return "builtin";Ð     if (stream.match(/
^(self|cls)\b/))Ð       return "variable-2";Ð     if
(stream.match(identifiers)) {Ð       if (state.lastToken == "def" ||
state.lastToken == "class")Ð         return "def";Ð       return "variable";Ð
      }Ð     // Handle non-detected itemsÐ     stream.next();Ð     return
ERRORCLASS;Ð   }Ð   function tokenStringFactory(delimiter) {Ð     while
("rub".indexOf(delimiter.charAt(0).toLowerCase()) >= 0)Ð       delimiter =
delimiter.substr(1);Ð     var singleline = delimiter.length == 1;Ð     var
OUTCLASS = "string";Ð     function tokenString(stream, state) {Ð       while
(!stream.eol()) {Ð         stream.eatWhile(/[^'"\\]/);Ð         if
(stream.eat("\\")) {Ð           stream.next();Ð           if (singleline &&
stream.eol())Ð             return OUTCLASS;Ð         } else if
(stream.match(delimiter)) {Ð           state.tokenize = tokenBase;Ð
return OUTCLASS;Ð         } else {Ð           stream.eat(/['"]/);Ð         }Ð
        }Ð       if (singleline) {Ð         if
(parserConf.singleLineStringErrors)Ð           return ERRORCLASS;Ð
elseÐ
```

```
                state.tokenize = tokenBase;Ð       }Ð       return OUTCLASS;Ð
      }Ð     tokenString.isString = true;Ð     return tokenString;Ð   }Ð
function pushScope(stream, state, type) {Ð     var offset = 0, align = null;Ð
      if (type == "py") {Ð       while (top(state).type != "py")Ð
state.scopes.pop();Ð     }Ð     offset = top(state).offset + (type == "py" ?
conf.indentUnit : hangingIndent);Ð     if (type != "py" && !stream.match(/
^(\s|#.*)*$/, false))Ð       align = stream.column() + 1;Ð
state.scopes.push({offset: offset, type: type, align: align});Ð   }Ð
function dedent(stream, state) {Ð     var indented = stream.indentation();Ð
      while (top(state).offset > indented) {Ð       if (top(state).type !=
"py") return true;Ð       state.scopes.pop();Ð     }Ð     return
top(state).offset != indented;Ð   }Ð   function tokenLexer(stream, state) {Ð
      var style = state.tokenize(stream, state);Ð     var current =
stream.current();Ð     // Handle '.' connected identifiersÐ     if (current
== ".") {Ð       style = stream.match(identifiers, false) ? null : ERRORCLASS;Ð
        if (style == null && state.lastStyle == "meta") {Ð         // Apply
'meta' style to '.' connected identifiers whenÐ         // appropriate.Ð
          style = "meta";Ð       }Ð       return style;Ð     }Ð     // Handle
decoratorsÐ     if (current == "@"){Ð       if(parserConf.version &&
parseInt(parserConf.version, 10) == 3){Ð           return
stream.match(identifiers, false) ? "meta" : "operator";Ð       } else {Ð
            return stream.match(identifiers, false) ? "meta" : ERRORCLASS;Ð
        }Ð     }Ð     if ((style == "variable" || style == "builtin")Ð
          && state.lastStyle == "meta")Ð       style = "meta";Ð     // Handle
scope changes.Ð     if (current == "pass" || current == "return")Ð
state.dedent += 1;Ð     if (current == "lambda") state.lambda = true;Ð     if
(current == ":" && !state.lambda && top(state).type == "py")Ð
pushScope(stream, state, "py");Ð     var delimiter_index = current.length ==
1 ? "[({".indexOf(current) : -1;Ð     if (delimiter_index != -1)Ð
pushScope(stream, state, "])}".slice(delimiter_index, delimiter_index+1));Ð
      delimiter_index = "])}".indexOf(current);Ð     if (delimiter_index !=
-1) {Ð       if (top(state).type == current) state.scopes.pop();Ð       else
return ERRORCLASS;Ð     }Ð     if (state.dedent > 0 && stream.eol() &&
top(state).type == "py") {Ð       if (state.scopes.length > 1)
state.scopes.pop();Ð       state.dedent -= 1;Ð     }Ð     return style;Ð   }Ð
    var external = {Ð     startState: function(basecolumn) {Ð       return {Ð
          tokenize: tokenBase,Ð         scopes: [{offset: basecolumn || 0,
type: "py", align: null}],Ð         lastStyle: null,Ð         lastToken: null,Ð
          lambda: false,Ð         dedent: 0Ð       };Ð     },Ð     token:
function(stream, state) {Ð       var addErr = state.errorToken;Ð       if
(addErr) state.errorToken = false;Ð       var style = tokenLexer(stream,
state);Ð       state.lastStyle = style;Ð       var current = stream.current();Ð
        if (current && style)Ð         state.lastToken = current;Ð       if
(stream.eol() && state.lambda)Ð         state.lambda = false;Ð       return
addErr ? style + " " + ERRORCLASS : style;Ð     },Ð     indent:
function(state, textAfter) {Ð       if (state.tokenize != tokenBase)Ð
return state.tokenize.isString ? CodeMirror.Pass : 0;Ð       var scope =
top(state);Ð       var closing = textAfter && textAfter.charAt(0) ==
scope.type;Ð       if (scope.align != null)Ð         return scope.align -
(closing ? 1 : 0);Ð       else if (closing && state.scopes.length > 1)Ð
          return state.scopes[state.scopes.length - 2].offset;Ð       elseÐ
          return scope.offset;Ð     },Ð     lineComment: "#",Ð     fold:
"indent"Ð   };Ð   return external;Ð });Ð CodeMirror.defineMIME("text/x-
python", "python");Ð var words = function(str) { return str.split(" "); };Ð
CodeMirror.defineMIME("text/x-cython", {Ð   name: "python",Ð
extra_keywords: words("by cdef cimport cpdef ctypedef enum except"+Ð
                          "extern gil include nogil property public"+Ð
                          "readonly struct union DEF IF ELIF ELSE")Ð });Ð});Ð
```

public\assets\js\plugins\codemirror\mode\r\r.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("r", function(config) {Ð function wordObj(str) {Ð   var
words = str.split(" "), res = {};Ð   for (var i = 0; i < words.length; ++i)
res[words[i]] = true;Ð   return res;Ð }Ð var atoms = wordObj("NULL NA Inf NaN
NA_integer_ NA_real_ NA_complex_ NA_character_");Ð var builtins =
wordObj("list quote bquote eval return call parse deparse");Ð var keywords =
wordObj("if else repeat while function for in next break");Ð var
blockkeywords = wordObj("if else repeat while function for");Ð var opChars = /
[+\-*\/^<>=!&|~$:]/;Ð var curPunc;Ð function tokenBase(stream, state) {Ð
curPunc = null;Ð   var ch = stream.next();Ð   if (ch == "#") {Ð
stream.skipToEnd();Ð     return "comment";Ð   } else if (ch == "0" &&
stream.eat("x")) {Ð     stream.eatWhile(/[\da-f]/i);Ð     return "number";Ð
    } else if (ch == "." && stream.eat(/\d/)) {Ð     stream.match(/\d*(?:e[+
\-]?\d+)?/);Ð     return "number";Ð   } else if (/\d/.test(ch)) {Ð
stream.match(/\d*(?:\.\d+)?(?:e[+\-]\d+)?L?/);Ð     return "number";Ð   }
else if (ch == "'" || ch == '"') {Ð     state.tokenize = tokenString(ch);Ð
      return "string";Ð   } else if (ch == "." && stream.match(/.[.\d]+/)) {Ð
      return "keyword";Ð   } else if (/[\w\.]/.test(ch) && ch != "_") {Ð
stream.eatWhile(/[\w\.]/);Ð     var word = stream.current();Ð     if
(atoms.propertyIsEnumerable(word)) return "atom";Ð     if
(keywords.propertyIsEnumerable(word)) {Ð       // Block keywords start new
blocks, except 'else if', which only starts Ð       // one new block for the
'if', no block for the 'else'.Ð       if
(blockkeywords.propertyIsEnumerable(word) && Ð           !stream.match(/
\s*if(\s+|$)/, false))Ð         curPunc = "block";Ð       return "keyword";Ð
      }Ð     if (builtins.propertyIsEnumerable(word)) return "builtin";Ð
return "variable";Ð   } else if (ch == "%") {Ð     if (stream.skipTo("%"))
stream.next();Ð     return "variable-2";Ð   } else if (ch == "<" &&
stream.eat("-")) {Ð     return "arrow";Ð   } else if (ch == "=" &&
state.ctx.argList) {Ð     return "arg-is";Ð   } else if (opChars.test(ch)) {Ð
      if (ch == "$") return "dollar";Ð     stream.eatWhile(opChars);Ð
return "operator";Ð   } else if (/[\(\){}\[\];]/.test(ch)) {Ð     curPunc =
ch;Ð     if (ch == ";") return "semi";Ð     return null;Ð   } else {Ð
return null;Ð   }Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     if (stream.eat("\\")) {Ð       var ch =
stream.next();Ð       if (ch == "x") stream.match(/^[a-f0-9]{2}/i);Ð
else if ((ch == "u" || ch == "U") && stream.eat("{") && stream.skipTo("}"))
stream.next();Ð       else if (ch == "u") stream.match(/^[a-f0-9]{4}/i);Ð
        else if (ch == "U") stream.match(/^[a-f0-9]{8}/i);Ð       else if (/
[0-7]/.test(ch)) stream.match(/^[0-7]{1,2}/);Ð       return "string-2";Ð
      } else {Ð       var next;Ð       while ((next = stream.next()) != null)
{Ð         if (next == quote) { state.tokenize = tokenBase; break; }Ð
if (next == "\\") { stream.backUp(1); break; }Ð       }Ð       return
"string";Ð     }Ð   };Ð }Ð function push(state, type, stream) {Ð   state.ctx
= {type: type,Ð                indent: state.indent,Ð                align:
null,Ð                column: stream.column(),Ð                prev:
state.ctx};Ð }Ð function pop(state) {Ð   state.indent = state.ctx.indent;Ð
state.ctx = state.ctx.prev;Ð }Ð return {Ð   startState: function() {Ð
return {tokenize: tokenBase,Ð             ctx: {type: "top",Ð
                    indent: -config.indentUnit,Ð                    align:
false},Ð             indent: 0,Ð             afterIdent: false};Ð   },Ð
token: function(stream, state) {Ð     if (stream.sol()) {Ð       if
(state.ctx.align == null) state.ctx.align = false;Ð       state.indent =
stream.indentation();Ð
```

```
                            }Ð     if (stream.eatSpace()) return null;Ð
var style = state.tokenize(stream, state);Ð     if (style != "comment" &&
state.ctx.align == null) state.ctx.align = true;Ð     var ctype =
state.ctx.type;Ð     if ((curPunc == ";" || curPunc == "{" || curPunc == "}")
&& ctype == "block") pop(state);Ð     if (curPunc == "{") push(state, "}",
stream);Ð     else if (curPunc == "(") {Ð       push(state, ")", stream);Ð
        if (state.afterIdent) state.ctx.argList = true;Ð     }Ð     else if
(curPunc == "[") push(state, "]", stream);Ð     else if (curPunc == "block")
push(state, "block", stream);Ð     else if (curPunc == ctype) pop(state);Ð
      state.afterIdent = style == "variable" || style == "keyword";Ð
return style;Ð   },Ð   indent: function(state, textAfter) {Ð     if
(state.tokenize != tokenBase) return 0;Ð     var firstChar = textAfter &&
textAfter.charAt(0), ctx = state.ctx,Ð         closing = firstChar ==
ctx.type;Ð     if (ctx.type == "block") return ctx.indent + (firstChar ==
"{" ? 0 : config.indentUnit);Ð     else if (ctx.align) return ctx.column +
(closing ? 0 : 1);Ð     else return ctx.indent + (closing ? 0 :
config.indentUnit);Ð   },Ð   lineComment: "#"Ð };Ð});Ð
CodeMirror.defineMIME("text/x-rsrc", "r");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\rpm\rpm.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("rpm-changes", function() {Ð var headerSeperator = /^-+
$/;Ð var headerLine = /^(Mon|Tue|Wed|Thu|Fri|Sat|Sun) (Jan|Feb|Mar|Apr|May|
Jun|Jul|Aug|Sep|Oct|Nov|Dec)  ?\d{1,2} \d{2}:\d{2}(:\d{2})? [A-Z]{3,4} \d{4}
- /;Ð var simpleEmail = /^[\w+.-]+@[\w.-]+/;Ð return {Ð   token:
function(stream) {Ð     if (stream.sol()) {Ð       if
(stream.match(headerSeperator)) { return 'tag'; }Ð       if
(stream.match(headerLine)) { return 'tag'; }Ð     }Ð     if
(stream.match(simpleEmail)) { return 'string'; }Ð     stream.next();Ð
return null;Ð   }Ð };Ð });Ð CodeMirror.defineMIME("text/x-rpm-changes", "rpm-
changes");Ð// Quick and dirty spec file highlighting Ð CodeMirror.defineMode("rpm-
spec", function() {Ð var arch = /^(i386|i586|i686|x86_64|ppc64|ppc|ia64|s390x|
s390|sparc64|sparcv9|sparc|noarch|alphaev6|alpha|hppa|mipsel)/;Ð var preamble
= /^(Name|Version|Release|License|Summary|Url|Group|Source|BuildArch|
BuildRequires|BuildRoot|AutoReqProv|Provides|Requires(\(\w+\))?|Obsoletes|
Conflicts|Recommends|Source\d*|Patch\d*|ExclusiveArch|NoSource|Supplements):/;Ð
  var section = /^%(debug_package|package|description|prep|build|install|
files|clean|changelog|preinstall|preun|postinstall|postun|pre|post|triggerin|
triggerun|pretrans|posttrans|verifyscript|check|triggerpostun|triggerprein|
trigger)/;Ð var control_flow_complex = /^%(ifnarch|ifarch|if)/; // rpm
control flow macros Ð var control_flow_simple = /^%(else|endif)/; // rpm
control flow macros Ð var operators = /^(\!|\?|\<\=|\<|\>\=|\>|\=\=|\&\&|\|
\|)/; // operators in control flow macros Ð return {Ð   startState: function
() {Ð       return {Ð         controlFlow: false,Ð         macroParameters:
false,Ð         section: false Ð       };Ð   },Ð   token: function (stream,
state) {Ð     var ch = stream.peek();Ð     if (ch == "#")
{ stream.skipToEnd(); return "comment"; }Ð     if (stream.sol()) {Ð       if
(stream.match(preamble)) { return "preamble"; }Ð       if
(stream.match(section)) { return "section"; }Ð     }Ð     if (stream.match(/^\
$\w+/)) { return "def"; } // Variables like '$RPM_BUILD_ROOT'Ð     if
(stream.match(/^\$\{\w+\}/)) { return "def"; } // Variables like
'${RPM_BUILD_ROOT}'Ð     if (stream.match(control_flow_simple)) { return
"keyword"; }Ð     if (stream.match(control_flow_complex)) {Ð
state.controlFlow = true;Ð       return "keyword";Ð     }Ð     if
(state.controlFlow) {Ð       if (stream.match(operators)) { return
"operator"; }Ð       if (stream.match(/^(\d+)/)) { return "number"; }Ð
if (stream.eol()) { state.controlFlow = false; }Ð     }Ð     if
(stream.match(arch)) { return "number"; }Ð     // Macros like '%make_install'
or '%attr(0775,root,root)'Ð     if (stream.match(/^%[\w]+/)) {Ð       if
(stream.match(/^\(/)) { state.macroParameters = true; }Ð       return "macro";Ð
      }Ð     if (state.macroParameters) {Ð       if (stream.match(/^\d+/))
{ return "number";}Ð       if (stream.match(/^\)/)) {Ð
state.macroParameters = false;Ð         return "macro";Ð       }Ð     }Ð
if (stream.match(/^%\{\??[\w \-]+\}/)) { return "macro"; } // Macros like
'%{defined fedora}'Ð     //TODO: Include bash script sub-parser (CodeMirror
supports that) Ð     stream.next();Ð     return null;Ð   }Ð };Ð });Ð
CodeMirror.defineMIME("text/x-rpm-spec", "rpm-spec");Ð });Ð
```

public\assets\js\plugins\codemirror\mode\rst\rst.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../python/python"), require("../
stex/stex"), require("../../addon/mode/overlay"));Ð else if (typeof define ==
"function" && define.amd) // AMD Ð   define(["../../lib/codemirror", "../
python/python", "../stex/stex", "../../addon/mode/overlay"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode('rst', function (config, options) {Ð var rx_strong = /
^\*\*[^\*\s](?:[^\*]*[^\*\s])?\*\*/;Ð var rx_emphasis = /^\*[^\*\s](?:
[^\*]*[^\*\s])?\*/;Ð var rx_literal = /^``[^`\s](?:[^`]*[^`\s])``/;Ð var
rx_number = /^(?:[\d]+(?:[\.,]\d+)*)/;Ð var rx_positive = /^(?:\s\+[\d]+(?:
[\.,]\d+)*)/;Ð var rx_negative = /^(?:\s\-[\d]+(?:[\.,]\d+)*)/;Ð var
rx_uri_protocol = "[Hh][Tt][Tt][Pp][Ss]?://";Ð var rx_uri_domain = "(?:[\\d\
\w.-]+)\\.(?:\\w{2,6})";Ð var rx_uri_path = "(?:/[\\d\\w\\#\\%\\&\\-\\.\\,\\/\
\:\\=\\?\\~]+)*";Ð var rx_uri = new RegExp("^" + rx_uri_protocol +
rx_uri_domain + rx_uri_path);Ð var overlay = {Ð   token: function (stream) {Ð
      if (stream.match(rx_strong) && stream.match (/\W+|$/, false))Ð
return 'strong';Ð     if (stream.match(rx_emphasis) && stream.match (/\W+|$/,
false))Ð       return 'em';Ð     if (stream.match(rx_literal) && stream.match
(/\W+|$/, false))Ð       return 'string-2';Ð     if (stream.match(rx_number))Ð
        return 'number';Ð     if (stream.match(rx_positive))Ð       return
'positive';Ð     if (stream.match(rx_negative))Ð       return 'negative';Ð
      if (stream.match(rx_uri))Ð       return 'link';Ð     while
(stream.next() != null) {Ð       if (stream.match(rx_strong, false)) break;Ð
        if (stream.match(rx_emphasis, false)) break;Ð       if
(stream.match(rx_literal, false)) break;Ð       if (stream.match(rx_number,
false)) break;Ð       if (stream.match(rx_positive, false)) break;Ð       if
(stream.match(rx_negative, false)) break;Ð       if (stream.match(rx_uri,
false)) break;Ð     }Ð     return null;Ð   }Ð };Ð var mode =
CodeMirror.getMode(Ð   config, options.backdrop || 'rst-base'Ð );Ð return
CodeMirror.overlayMode(mode, overlay, true); // combined Ð, 'python', 'stex');Ð
////////////////////////////////////////////////////////////////////////////Ð
////////////////////////////////////////////////////////////////////////////Ð
ÐodeMirror.defineMode('rst-base', function (config) {Ð
  ///////////////////////////////////////////////////////////////////////Ð
  ///////////////////////////////////////////////////////////////////////Ð
  function format(string) {Ð   var args =
Array.prototype.slice.call(arguments, 1);Ð   return string.replace(/{(\d+)}/
g, function (match, n) {Ð     return typeof args[n] != 'undefined' ?
args[n] : match;Ð   });Ð }Ð
  ///////////////////////////////////////////////////////////////////////Ð
  ///////////////////////////////////////////////////////////////////////Ð
  var mode_python = CodeMirror.getMode(config, 'python');Ð var mode_stex =
CodeMirror.getMode(config, 'stex');Ð
  ///////////////////////////////////////////////////////////////////////Ð
  ///////////////////////////////////////////////////////////////////////Ð
  var SEPA = "\\s+";Ð var TAIL = "(?:\\s*|\\W|$)",Ð rx_TAIL = new
RegExp(format('^{0}', TAIL));Ð var NAME =Ð   "(?:[^\\W\\d_](?:[\\w!\"#$%&'()\
\*\\+,\\-\\.\/:;<=>\\?]*[^\\W_])?)",Ð rx_NAME = new RegExp(format('^{0}',
NAME));Ð var NAME_WWS =Ð   "(?:[^\\W\\d_](?:[\\w\\s!\"#$%&'()\\*\\+,\\-\\.
\/:;<=>\\?]*[^\\W_])?)";Ð var REF_NAME = format('(?:{0}|`{1}`)', NAME,
NAME_WWS);Ð var TEXT1 = "(?:[^\\s\\|](?:[^\\|]*[^\\s\\|])?)";Ð var TEXT2 =
"(?:[^\\`]+)",Ð rx_TEXT2 = new RegExp(format('^{0}', TEXT2));Ð var rx_section
= new RegExp(Ð   "^([!'#$%&\"()*+,-./:;<=>?@\\[\\\\\\]^_`{|}~])\\1{3,}\\s*$");Ð
  var rx_explicit = new RegExp(Ð   format('^\\.\\.{0}', SEPA));Ð var rx_link
= new RegExp(Ð   format('^_{0}:{1}|^__:{1}', REF_NAME, TAIL));Ð var
rx_directive = new RegExp(Ð   format('^{0}::{1}', REF_NAME, TAIL));Ð var
rx_substitution = new RegExp(Ð
```

```
                                    format('^\\|{0}\\|{1}{2}::{3}', TEXT1, SEPA,
REF_NAME, TAIL));Ð var rx_footnote = new RegExp(Ð   format('^\\[(?:\\d+|#{0}?|
\\*)]{1}', REF_NAME, TAIL));Ð var rx_citation = new RegExp(Ð   format('^\
\[{0}\\]{1}', REF_NAME, TAIL));Ð var rx_substitution_ref = new RegExp(Ð
format('^\\|{0}\\|', TEXT1));Ð var rx_footnote_ref = new RegExp(Ð   format('^\
\[(?:\\d+|#{0}?|\\*)]_', REF_NAME));Ð var rx_citation_ref = new RegExp(Ð
format('^\\[{0}\\]_', REF_NAME));Ð var rx_link_ref1 = new RegExp(Ð
format('^{0}__?', REF_NAME));Ð var rx_link_ref2 = new RegExp(Ð   format('^`{0}
`_', TEXT2));Ð var rx_role_pre = new RegExp(Ð   format('^:{0}:`{1}`{2}',
NAME, TEXT2, TAIL));Ð var rx_role_suf = new RegExp(Ð   format('^`{1}`:{0}:
{2}', NAME, TEXT2, TAIL));Ð var rx_role = new RegExp(Ð   format('^:{0}:{1}',
NAME, TAIL));Ð var rx_directive_name = new RegExp(format('^{0}', REF_NAME));Ð
var rx_directive_tail = new RegExp(format('^::{0}', TAIL));Ð var
rx_substitution_text = new RegExp(format('^\\|{0}\\|', TEXT1));Ð var
rx_substitution_sepa = new RegExp(format('^{0}', SEPA));Ð var
rx_substitution_name = new RegExp(format('^{0}', REF_NAME));Ð var
rx_substitution_tail = new RegExp(format('^::{0}', TAIL));Ð var rx_link_head
= new RegExp("^_");Ð var rx_link_name = new RegExp(format('^{0}|_',
REF_NAME));Ð var rx_link_tail = new RegExp(format('^:{0}', TAIL));Ð var
rx_verbatim = new RegExp('^::\\s*$');Ð var rx_examples = new RegExp('^\
\s+(?:>>>|In \\[\\d+\\]:)\\s');Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  function to_normal(stream, state) {Ð   var token = null;Ð   if
(stream.sol() && stream.match(rx_examples, false)) {Ð     change(state,
to_mode, {Ð       mode: mode_python, local: CodeMirror.startState(mode_python)Ð
      });Ð   } else if (stream.sol() && stream.match(rx_explicit)) {Ð
change(state, to_explicit);Ð     token = 'meta';Ð   } else if (stream.sol()
&& stream.match(rx_section)) {Ð     change(state, to_normal);Ð     token =
'header';Ð   } else if (phase(state) == rx_role_pre ||Ð
stream.match(rx_role_pre, false)) {Ð     switch (stage(state)) {Ð     case 0:Ð
        change(state, to_normal, context(rx_role_pre, 1));Ð
stream.match(/^:/);Ð       token = 'meta';Ð       break;Ð     case 1:Ð
change(state, to_normal, context(rx_role_pre, 2));Ð
stream.match(rx_NAME);Ð       token = 'keyword';Ð       if
(stream.current().match(/^(?:math|latex)/)) {Ð         state.tmp_stex = true;Ð
        }Ð       break;Ð     case 2:Ð       change(state, to_normal,
context(rx_role_pre, 3));Ð       stream.match(/^:`/);Ð       token = 'meta';Ð
        break;Ð     case 3:Ð       if (state.tmp_stex) {Ð
state.tmp_stex = undefined; state.tmp = {Ð           mode: mode_stex, local:
CodeMirror.startState(mode_stex)Ð         };Ð       }Ð       if (state.tmp) {Ð
          if (stream.peek() == '`') {Ð           change(state, to_normal,
context(rx_role_pre, 4));Ð           state.tmp = undefined;Ð           break;Ð
          }Ð         token = state.tmp.mode.token(stream, state.tmp.local);Ð
          break;Ð       }Ð       change(state, to_normal,
context(rx_role_pre, 4));Ð       stream.match(rx_TEXT2);Ð       token =
'string';Ð       break;Ð     case 4:Ð       change(state, to_normal,
context(rx_role_pre, 5));Ð       stream.match(/^`/);Ð       token = 'meta';Ð
        break;Ð     case 5:Ð       change(state, to_normal,
context(rx_role_pre, 6));Ð       stream.match(rx_TAIL);Ð       break;Ð
default:Ð       change(state, to_normal);Ð     }Ð   } else if (phase(state)
== rx_role_suf ||Ð              stream.match(rx_role_suf, false)) {Ð
switch (stage(state)) {Ð     case 0:Ð       change(state, to_normal,
context(rx_role_suf, 1));Ð       stream.match(/^`/);Ð       token = 'meta';Ð
        break;Ð     case 1:Ð       change(state, to_normal,
context(rx_role_suf, 2));Ð       stream.match(rx_TEXT2);Ð       token =
'string';Ð       break;Ð     case 2:Ð       change(state, to_normal,
context(rx_role_suf, 3));Ð       stream.match(/^`:/);Ð       token = 'meta';Ð
        break;Ð     case 3:Ð       change(state, to_normal,
context(rx_role_suf, 4));Ð
```

```
                                    stream.match(rx_NAME);Ð       token =
'keyword';Ð       break;Ð     case 4:Ð       change(state, to_normal,
context(rx_role_suf, 5));Ð       stream.match(/^:/);Ð       token = 'meta';Ð
        break;Ð     case 5:Ð       change(state, to_normal,
context(rx_role_suf, 6));Ð       stream.match(rx_TAIL);Ð       break;Ð
default:Ð       change(state, to_normal);Ð     }Ð   } else if (phase(state)
== rx_role || stream.match(rx_role, false)) {Ð     switch (stage(state)) {Ð
      case 0:Ð       change(state, to_normal, context(rx_role, 1));Ð
stream.match(/^:/);Ð       token = 'meta';Ð       break;Ð     case 1:Ð
change(state, to_normal, context(rx_role, 2));Ð       stream.match(rx_NAME);Ð
        token = 'keyword';Ð       break;Ð     case 2:Ð       change(state,
to_normal, context(rx_role, 3));Ð       stream.match(/^:/);Ð       token =
'meta';Ð       break;Ð     case 3:Ð       change(state, to_normal,
context(rx_role, 4));Ð       stream.match(rx_TAIL);Ð       break;Ð
default:Ð       change(state, to_normal);Ð     }Ð   } else if (phase(state)
== rx_substitution_ref ||Ð              stream.match(rx_substitution_ref,
false)) {Ð     switch (stage(state)) {Ð     case 0:Ð       change(state,
to_normal, context(rx_substitution_ref, 1));Ð
stream.match(rx_substitution_text);Ð       token = 'variable-2';Ð       break;Ð
      case 1:Ð       change(state, to_normal, context(rx_substitution_ref,
2));Ð       if (stream.match(/^_?_?/)) token = 'link';Ð       break;Ð
default:Ð       change(state, to_normal);Ð     }Ð   } else if
(stream.match(rx_footnote_ref)) {Ð     change(state, to_normal);Ð     token =
'quote';Ð   } else if (stream.match(rx_citation_ref)) {Ð     change(state,
to_normal);Ð     token = 'quote';Ð   } else if (stream.match(rx_link_ref1)) {Ð
      change(state, to_normal);Ð     if (!stream.peek() ||
stream.peek().match(/^\W$/)) {Ð       token = 'link';Ð     }Ð   } else if
(phase(state) == rx_link_ref2 ||Ð              stream.match(rx_link_ref2,
false)) {Ð     switch (stage(state)) {Ð     case 0:Ð       if (!stream.peek()
|| stream.peek().match(/^\W$/)) {Ð         change(state, to_normal,
context(rx_link_ref2, 1));Ð       } else {Ð
stream.match(rx_link_ref2);Ð       }Ð       break;Ð     case 1:Ð
change(state, to_normal, context(rx_link_ref2, 2));Ð       stream.match(/^`/);Ð
        token = 'link';Ð       break;Ð     case 2:Ð       change(state,
to_normal, context(rx_link_ref2, 3));Ð       stream.match(rx_TEXT2);Ð
break;Ð     case 3:Ð       change(state, to_normal, context(rx_link_ref2, 4));Ð
        stream.match(/^`_/);Ð       token = 'link';Ð       break;Ð
default:Ð       change(state, to_normal);Ð     }Ð   } else if
(stream.match(rx_verbatim)) {Ð     change(state, to_verbatim);Ð   }Ð   else {Ð
      if (stream.next()) change(state, to_normal);Ð   }Ð   return token;Ð }Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  function to_explicit(stream, state) {Ð   var token = null;Ð   if
(phase(state) == rx_substitution ||Ð       stream.match(rx_substitution,
false)) {Ð     switch (stage(state)) {Ð     case 0:Ð       change(state,
to_explicit, context(rx_substitution, 1));Ð
stream.match(rx_substitution_text);Ð       token = 'variable-2';Ð       break;Ð
      case 1:Ð       change(state, to_explicit, context(rx_substitution, 2));Ð
        stream.match(rx_substitution_sepa);Ð       break;Ð     case 2:Ð
change(state, to_explicit, context(rx_substitution, 3));Ð
stream.match(rx_substitution_name);Ð       token = 'keyword';Ð       break;Ð
      case 3:Ð       change(state, to_explicit, context(rx_substitution, 4));Ð
        stream.match(rx_substitution_tail);Ð       token = 'meta';Ð
break;Ð     default:Ð       change(state, to_normal);Ð     }Ð   } else if
(phase(state) == rx_directive ||Ð              stream.match(rx_directive,
false)) {Ð     switch (stage(state)) {Ð     case 0:Ð       change(state,
to_explicit, context(rx_directive, 1));Ð
stream.match(rx_directive_name);Ð       token = 'keyword';Ð       if
(stream.current().match(/^(?:math|latex)/))Ð         state.tmp_stex = true;Ð
        else if (stream.current().match(/^python/))Ð
```

```
                                                                state.tmp_py =
true;Ð       break;Ð     case 1:Ð       change(state, to_explicit,
context(rx_directive, 2));Ð       stream.match(rx_directive_tail);Ð
token = 'meta';Ð       if (stream.match(/^latex\s*$/) || state.tmp_stex) {Ð
          state.tmp_stex = undefined; change(state, to_mode, {Ð
mode: mode_stex, local: CodeMirror.startState(mode_stex)Ð         });Ð       }Ð
        break;Ð     case 2:Ð       change(state, to_explicit,
context(rx_directive, 3));Ð       if (stream.match(/^python\s*$/) ||
state.tmp_py) {Ð         state.tmp_py = undefined; change(state, to_mode, {Ð
            mode: mode_python, local: CodeMirror.startState(mode_python)Ð
          });Ð       }Ð       break;Ð     default:Ð       change(state,
to_normal);Ð     }Ð   } else if (phase(state) == rx_link ||
stream.match(rx_link, false)) {Ð     switch (stage(state)) {Ð     case 0:Ð
        change(state, to_explicit, context(rx_link, 1));Ð
stream.match(rx_link_head);Ð       stream.match(rx_link_name);Ð       token =
'link';Ð       break;Ð     case 1:Ð       change(state, to_explicit,
context(rx_link, 2));Ð       stream.match(rx_link_tail);Ð       token =
'meta';Ð       break;Ð     default:Ð       change(state, to_normal);Ð     }Ð
    } else if (stream.match(rx_footnote)) {Ð     change(state, to_normal);Ð
      token = 'quote';Ð   } else if (stream.match(rx_citation)) {Ð
change(state, to_normal);Ð     token = 'quote';Ð   }Ð   else {Ð
stream.eatSpace();Ð     if (stream.eol()) {Ð       change(state, to_normal);Ð
      } else {Ð       stream.skipToEnd();Ð       change(state, to_comment);Ð
        token = 'comment';Ð     }Ð   }Ð   return token;Ð }Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  function to_comment(stream, state) {Ð   return as_block(stream, state,
'comment');Ð }Ð function to_verbatim(stream, state) {Ð   return
as_block(stream, state, 'meta');Ð }Ð function as_block(stream, state, token) {Ð
    if (stream.eol() || stream.eatSpace()) {Ð     stream.skipToEnd();Ð
return token;Ð   } else {Ð     change(state, to_normal);Ð     return null;Ð
    }Ð }Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  function to_mode(stream, state) {Ð   if (state.ctx.mode && state.ctx.local)
{Ð     if (stream.sol()) {Ð       if (!stream.eatSpace()) change(state,
to_normal);Ð       return null;Ð     }Ð     return
state.ctx.mode.token(stream, state.ctx.local);Ð   }Ð   change(state,
to_normal);Ð   return null;Ð }Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  function context(phase, stage, mode, local) {Ð   return {phase: phase,
stage: stage, mode: mode, local: local};Ð }Ð function change(state, tok, ctx)
{Ð   state.tok = tok;Ð   state.ctx = ctx || {};Ð }Ð function stage(state) {Ð
    return state.ctx.stage || 0;Ð }Ð function phase(state) {Ð   return
state.ctx.phase;Ð }Ð
  ////////////////////////////////////////////////////////////////////////Ð
  ////////////////////////////////////////////////////////////////////////Ð
  return {Ð   startState: function () {Ð     return {tok: to_normal, ctx:
context(undefined, 0)};Ð   },Ð   copyState: function (state) {Ð     var ctx =
state.ctx, tmp = state.tmp;Ð     if (ctx.local)Ð       ctx = {mode: ctx.mode,
local: CodeMirror.copyState(ctx.mode, ctx.local)};Ð     if (tmp)Ð       tmp =
{mode: tmp.mode, local: CodeMirror.copyState(tmp.mode, tmp.local)};Ð
return {tok: state.tok, ctx: ctx, tmp: tmp};Ð   },Ð   innerMode: function
(state) {Ð     return state.tmp      ? {state: state.tmp.local, mode:
state.tmp.mode}Ð     : state.ctx.mode ? {state: state.ctx.local, mode:
state.ctx.mode}Ð     : null;Ð   },Ð   token: function (stream, state) {Ð
return state.tok(stream, state);Ð   }Ð };Ð, 'python', 'stex');Ð
////////////////////////////////////////////////////////////////////////////Ð
////////////////////////////////////////////////////////////////////////////Ð
```

```
ÐodeMirror.defineMIME('text/x-rst', 'rst');Ð
////////////////////////////////////////////////////////////////////////////Ð
////////////////////////////////////////////////////////////////////////////Ð
Ð});Ð
```

public\assets\js\plugins\codemirror\mode\ruby\ruby.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("ruby", function(config) {Ð function wordObj(words) {Ð
    var o = {};Ð   for (var i = 0, e = words.length; i < e; ++i) o[words[i]]
= true;Ð   return o;Ð }Ð var keywords = wordObj([Ð   "alias", "and", "BEGIN",
"begin", "break", "case", "class", "def", "defined?", "do", "else",Ð
"elsif", "END", "end", "ensure", "false", "for", "if", "in", "module",
"next", "not", "or",Ð   "redo", "rescue", "retry", "return", "self", "super",
"then", "true", "undef", "unless",Ð   "until", "when", "while", "yield",
"nil", "raise", "throw", "catch", "fail", "loop", "callcc",Ð   "caller",
"lambda", "proc", "public", "protected", "private", "require", "load",Ð
"require_relative", "extend", "autoload", "__END__", "__FILE__", "__LINE__",
"__dir__"Ð ]);Ð var indentWords = wordObj(["def", "class", "case", "for",
"while", "module", "then",Ð                              "catch", "loop",
"proc", "begin"]);Ð var dedentWords = wordObj(["end", "until"]);Ð var
matching = {"[": "]", "{": "}", "(": ")"};Ð var curPunc;Ð function
chain(newtok, stream, state) {Ð   state.tokenize.push(newtok);Ð   return
newtok(stream, state);Ð }Ð function tokenBase(stream, state) {Ð   curPunc =
null;Ð   if (stream.sol() && stream.match("=begin") && stream.eol()) {Ð
state.tokenize.push(readBlockComment);Ð     return "comment";Ð   }Ð   if
(stream.eatSpace()) return null;Ð   var ch = stream.next(), m;Ð   if (ch ==
"`" || ch == "'" || ch == '"') {Ð     return chain(readQuoted(ch, "string",
ch == '"' || ch == "`"), stream, state);Ð   } else if (ch == "/") {Ð     var
currentIndex = stream.current().length;Ð     if (stream.skipTo("/")) {Ð
var search_till = stream.current().length;Ð
stream.backUp(stream.current().length - currentIndex);Ð       var balance =
0;  // balance brackets Ð       while (stream.current().length < search_till) {Ð
          var chchr = stream.next();Ð         if (chchr == "(") balance += 1;Ð
          else if (chchr == ")") balance -= 1;Ð         if (balance < 0)
break;Ð       }Ð       stream.backUp(stream.current().length - currentIndex);Ð
        if (balance == 0)Ð         return chain(readQuoted(ch, "string-2",
true), stream, state);Ð     }Ð     return "operator";Ð   } else if (ch ==
"%") {Ð     var style = "string", embed = true;Ð     if (stream.eat("s"))
style = "atom";Ð     else if (stream.eat(/[WQ]/)) style = "string";Ð     else
if (stream.eat(/[r]/)) style = "string-2";Ð     else if (stream.eat(/[wxq]/))
{ style = "string"; embed = false; }Ð     var delim = stream.eat(/[^\w\s=]/);Ð
      if (!delim) return "operator";Ð     if
(matching.propertyIsEnumerable(delim)) delim = matching[delim];Ð     return
chain(readQuoted(delim, style, embed, true), stream, state);Ð   } else if (ch
== "#") {Ð     stream.skipToEnd();Ð     return "comment";Ð   } else if (ch ==
"<" && (m = stream.match(/^<-?[\`\"\']?([a-zA-Z_?]\w*)[\`\"\']?(?:;|$)))) {Ð
      return chain(readHereDoc(m[1]), stream, state);Ð   } else if (ch ==
"0") {Ð     if (stream.eat("x")) stream.eatWhile(/[\da-fA-F]/);Ð     else if
(stream.eat("b")) stream.eatWhile(/[01]/);Ð     else stream.eatWhile(/[0-7]/);Ð
      return "number";Ð   } else if (/\d/.test(ch)) {Ð     stream.match(/
^[\d_]*(?:\.[\d_]+)?(?:[eE][+\-]?[\d_]+)?/);Ð     return "number";Ð   } else
if (ch == "?") {Ð     while (stream.match(/^\\[CM]-/)) {}Ð     if
(stream.eat("\\")) stream.eatWhile(/\w/);Ð     else stream.next();Ð
return "string";Ð   } else if (ch == ":") {Ð     if (stream.eat("'")) return
chain(readQuoted("'", "atom", false), stream, state);Ð     if
(stream.eat('"')) return chain(readQuoted('"', "atom", true), stream, state);Ð
      // :> :>> :< :<< are valid symbols Ð     if (stream.eat(/[\<\>]/)) {Ð
        stream.eat(/[\<\>]/);Ð       return "atom";Ð     }Ð     // :
+ :- :/ :* :| :& :! are valid symbols Ð     if (stream.eat(/[\+\-\*\/\&\|\:
\!]/)) {Ð
```

```
                return "atom";Ð     }Ð     // Symbols can't start by a digitÐ
      if (stream.eat(/[a-zA-Z$@_\xa1-\uffff]/)) {Ð       stream.eatWhile(/[\w$
\xa1-\uffff]/);Ð       // Only one ? ! = is allowed and only as the last
characterÐ       stream.eat(/[\?\!\=]/);Ð       return "atom";Ð     }Ð
return "operator";Ð   } else if (ch == "@" && stream.match(/^@?[a-zA-Z_\xa1-
\uffff]/)) {Ð     stream.eat("@");Ð     stream.eatWhile(/[\w\xa1-\uffff]/);Ð
      return "variable-2";Ð   } else if (ch == "$") {Ð     if (stream.eat(/[a-
zA-Z_]/)) {Ð       stream.eatWhile(/[\w]/);Ð     } else if (stream.eat(/\d/))
{Ð       stream.eat(/\d/);Ð     } else {Ð       stream.next(); // Must be a
special global like $: or $!Ð     }Ð     return "variable-3";Ð   } else if (/
[a-zA-Z_\xa1-\uffff]/.test(ch)) {Ð     stream.eatWhile(/[\w\xa1-\uffff]/);Ð
      stream.eat(/[\?\!]/);Ð     if (stream.eat(":")) return "atom";Ð
return "ident";Ð   } else if (ch == "|" && (state.varList || state.lastTok ==
"{" || state.lastTok == "do")) {Ð     curPunc = "|";Ð     return null;Ð   }
else if (/[\(\)\[\]{}\\;]/.test(ch)) {Ð     curPunc = ch;Ð     return null;Ð
    } else if (ch == "-" && stream.eat(">")) {Ð     return "arrow";Ð   } else
if (/[=+\-\/*:\.^%<>~|]/.test(ch)) {Ð     var more = stream.eatWhile(/[=+\-\/
*:\.^%<>~|]/);Ð     if (ch == "." && !more) curPunc = ".";Ð     return
"operator";Ð   } else {Ð     return null;Ð   }Ð }Ð function
tokenBaseUntilBrace(depth) {Ð   if (!depth) depth = 1;Ð   return
function(stream, state) {Ð     if (stream.peek() == "}") {Ð       if (depth
== 1) {Ð         state.tokenize.pop();Ð         return
state.tokenize[state.tokenize.length-1](stream, state);Ð       } else {Ð
          state.tokenize[state.tokenize.length - 1] =
tokenBaseUntilBrace(depth - 1);Ð       }Ð     } else if (stream.peek() ==
"{") {Ð       state.tokenize[state.tokenize.length - 1] =
tokenBaseUntilBrace(depth + 1);Ð     }Ð     return tokenBase(stream, state);Ð
    };Ð }Ð function tokenBaseOnce() {Ð   var alreadyCalled = false;Ð   return
function(stream, state) {Ð     if (alreadyCalled) {Ð
state.tokenize.pop();Ð       return state.tokenize[state.tokenize.length-1]
(stream, state);Ð     }Ð     alreadyCalled = true;Ð     return
tokenBase(stream, state);Ð   };Ð }Ð function readQuoted(quote, style, embed,
unescaped) {Ð   return function(stream, state) {Ð     var escaped = false, ch;Ð
      if (state.context.type === 'read-quoted-paused') {Ð       state.context
= state.context.prev;Ð       stream.eat("}");Ð     }Ð     while ((ch =
stream.next()) != null) {Ð       if (ch == quote && (unescaped || !escaped)) {Ð
          state.tokenize.pop();Ð         break;Ð       }Ð       if (embed &&
ch == "#" && !escaped) {Ð         if (stream.eat("{")) {Ð           if (quote
== "}") {Ð             state.context = {prev: state.context, type: 'read-
quoted-paused'};Ð           }Ð
state.tokenize.push(tokenBaseUntilBrace());Ð           break;Ð         } else
if (/[@\$]/.test(stream.peek())) {Ð
state.tokenize.push(tokenBaseOnce());Ð           break;Ð         }Ð       }Ð
         escaped = !escaped && ch == "\\";Ð     }Ð     return style;Ð   };Ð }Ð
function readHereDoc(phrase) {Ð   return function(stream, state) {Ð     if
(stream.match(phrase)) state.tokenize.pop();Ð     else stream.skipToEnd();Ð
      return "string";Ð   };Ð }Ð function readBlockComment(stream, state) {Ð
    if (stream.sol() && stream.match("=end") && stream.eol())Ð
state.tokenize.pop();Ð   stream.skipToEnd();Ð   return "comment";Ð }Ð return {Ð
    startState: function() {Ð     return {tokenize: [tokenBase],Ð
indented: 0,Ð             context: {type: "top", indented: -
config.indentUnit},Ð             continuedLine: false,Ð             lastTok:
null,Ð             varList: false};Ð   },Ð   token: function(stream, state) {Ð
      if (stream.sol()) state.indented = stream.indentation();Ð     var style
= state.tokenize[state.tokenize.length-1](stream, state), kwtype;Ð     var
thisTok = curPunc;Ð     if (style == "ident") {Ð       var word =
stream.current();Ð       style = state.lastTok == "." ? "property"Ð         :
keywords.propertyIsEnumerable(stream.current()) ? "keyword"Ð         : /^[A-
Z]/.test(word) ? "tag"Ð         : (state.lastTok == "def" || state.lastTok ==
"class" || state.varList) ? "def"Ð
```

```
                                            : "variable";Ð       if (style ==
"keyword") {Ð         thisTok = word;Ð         if
(indentWords.propertyIsEnumerable(word)) kwtype = "indent";Ð         else if
(dedentWords.propertyIsEnumerable(word)) kwtype = "dedent";Ð         else if
((word == "if" || word == "unless") && stream.column() ==
stream.indentation())Ð           kwtype = "indent";Ð         else if (word ==
"do" && state.context.indented < state.indented)Ð           kwtype = "indent";Ð
        }Ð     }Ð     if (curPunc || (style && style != "comment"))
state.lastTok = thisTok;Ð     if (curPunc == "|") state.varList = !
state.varList;Ð     if (kwtype == "indent" || /[\(\[\{]/.test(curPunc))Ð
        state.context = {prev: state.context, type: curPunc || style,
indented: state.indented};Ð     else if ((kwtype == "dedent" || /
[\)\]\}]/.test(curPunc)) && state.context.prev)Ð       state.context =
state.context.prev;Ð     if (stream.eol())Ð       state.continuedLine =
(curPunc == "\\" || style == "operator");Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if
(state.tokenize[state.tokenize.length-1] != tokenBase) return 0;Ð     var
firstChar = textAfter && textAfter.charAt(0);Ð     var ct = state.context;Ð
      var closing = ct.type == matching[firstChar] ||Ð       ct.type ==
"keyword" && /^(?:end|until|else|elsif|when|rescue)\b/.test(textAfter);Ð
return ct.indented + (closing ? 0 : config.indentUnit) +Ð
(state.continuedLine ? config.indentUnit : 0);Ð   },Ð   electricChars: "}
de", // enD and rescuEÐ   lineComment: "#"Ð };Þ);ÐodeMirror.defineMIME("text/
x-ruby", "ruby");Þ);Ð
```

public\assets\js\plugins\codemirror\mode\ruby\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "ruby");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT("divide_equal_operator",Ð    "[variable bar] [operator /=] [variable
foo]");Ð MT("divide_equal_operator_no_spacing",Ð    "[variable foo][operator /
=][number 42]");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\rust\rust.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("rust", function() {Ð var indentUnit = 4, altIndentUnit
= 2;Ð var valKeywords = {Ð   "if": "if-style", "while": "if-style", "loop":
"else-style", "else": "else-style",Ð   "do": "else-style", "ret": "else-
style", "fail": "else-style",Ð   "break": "atom", "cont": "atom", "const":
"let", "resource": "fn",Ð   "let": "let", "fn": "fn", "for": "for", "alt":
"alt", "iface": "iface",Ð   "impl": "impl", "type": "type", "enum": "enum",
"mod": "mod",Ð   "as": "op", "true": "atom", "false": "atom", "assert": "op",
"check": "op",Ð   "claim": "op", "native": "ignore", "unsafe": "ignore",
"import": "else-style",Ð   "export": "else-style", "copy": "op", "log": "op",
"log_err": "op",Ð   "use": "op", "bind": "op", "self": "atom", "struct":
"enum"Ð };Ð var typeKeywords = function() {Ð   var keywords = {"fn": "fn",
"block": "fn", "obj": "obj"};Ð   var atoms = "bool uint int i8 i16 i32 i64 u8
u16 u32 u64 float f32 f64 str char".split(" ");Ð   for (var i = 0, e =
atoms.length; i < e; ++i) keywords[atoms[i]] = "atom";Ð   return keywords;Ð }
();Ð var operatorChar = /[+\-*&%=<>!?|\.@]/;Ð // TokenizerÐ // Used as
scratch variable to communicate multiple values without Ð // consing up tons
of objects.Ð var tcat, content;Ð function r(tc, style) {Ð   tcat = tc;Ð
return style;Ð }Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (ch == '"') {Ð     state.tokenize = tokenString;Ð
return state.tokenize(stream, state);Ð   }Ð   if (ch == "'") {Ð     tcat =
"atom";Ð     if (stream.eat("\\")) {Ð       if (stream.skipTo("'"))
{ stream.next(); return "string"; }Ð       else { return "error"; }Ð     }
else {Ð       stream.next();Ð       return stream.eat("'") ? "string" :
"error";Ð     }Ð   }Ð   if (ch == "/") {Ð     if (stream.eat("/"))
{ stream.skipToEnd(); return "comment"; }Ð     if (stream.eat("*")) {Ð
state.tokenize = tokenComment(1);Ð       return state.tokenize(stream, state);Ð
      }Ð   }Ð   if (ch == "#") {Ð     if (stream.eat("[")) { tcat = "open-
attr"; return null; }Ð     stream.eatWhile(/\w/);Ð     return r("macro",
"meta");Ð   }Ð   if (ch == ":" && stream.match(":<")) {Ð     return r("op",
null);Ð   }Ð   if (ch.match(/\d/) || (ch == "." && stream.eat(/\d/))) {Ð
var flp = false;Ð     if (!stream.match(/^x[\da-f]+/i) && !stream.match(/
^b[01]+/)) {Ð       stream.eatWhile(/\d/);Ð       if (stream.eat(".")) { flp
= true; stream.eatWhile(/\d/); }Ð       if (stream.match(/^e[+\-]?\d+/i))
{ flp = true; }Ð     }Ð     if (flp) stream.match(/^f(?:32|64)/);Ð     else
stream.match(/^[ui](?:8|16|32|64)/);Ð     return r("atom", "number");Ð   }Ð
if (ch.match(/[()\[\]{}:;,]/)) return r(ch, null);Ð   if (ch == "-" &&
stream.eat(">")) return r("->", null);Ð   if (ch.match(operatorChar)) {Ð
stream.eatWhile(operatorChar);Ð     return r("op", null);Ð   }Ð
stream.eatWhile(/\w/);Ð   content = stream.current();Ð   if (stream.match(/^::
\w/)) {Ð     stream.backUp(1);Ð     return r("prefix", "variable-2");Ð   }Ð
if (state.keywords.propertyIsEnumerable(content))Ð     return
r(state.keywords[content], content.match(/true|false/) ? "atom" : "keyword");Ð
    return r("name", "variable");Ð }Ð function tokenString(stream, state) {Ð
    var ch, escaped = false;Ð   while (ch = stream.next()) {Ð     if (ch ==
'"' && !escaped) {Ð       state.tokenize = tokenBase;Ð       return r("atom",
"string");Ð     }Ð     escaped = !escaped && ch == "\\";Ð   }Ð   // Hack to
not confuse the parser when a string is split in Ð   // pieces.Ð   return
r("op", "string");Ð }Ð function tokenComment(depth) {Ð   return
function(stream, state) {Ð     var lastCh = null, ch;Ð     while (ch =
stream.next()) {Ð       if (ch == "/" && lastCh == "*") {Ð         if (depth
== 1) {Ð           state.tokenize = tokenBase;Ð           break;Ð         }
else {Ð           state.tokenize = tokenComment(depth - 1);Ð           return
state.tokenize(stream, state);Ð
```

```
                                        }Ð       }Ð       if (ch == "*" &&
lastCh == "/") {Ð         state.tokenize = tokenComment(depth + 1);Ð
return state.tokenize(stream, state);Ð       }Ð       lastCh = ch;Ð     }Ð
      return "comment";Ð   };Ð }Ð // ParserÐ var cx = {state: null, stream:
null, marked: null, cc: null};Ð function pass() {Ð   for (var i =
arguments.length - 1; i >= 0; i--) cx.cc.push(arguments[i]);Ð }Ð function
cont() {Ð   pass.apply(null, arguments);Ð   return true;Ð }Ð function
pushlex(type, info) {Ð   var result = function() {Ð     var state = cx.state;Ð
      state.lexical = {indented: state.indented, column: cx.stream.column(),Ð
                        type: type, prev: state.lexical, info: info};Ð   };Ð
result.lex = true;Ð   return result;Ð }Ð function poplex() {Ð   var state =
cx.state;Ð   if (state.lexical.prev) {Ð     if (state.lexical.type == ")")Ð
        state.indented = state.lexical.indented;Ð     state.lexical =
state.lexical.prev;Ð   }Ð }Ð function typecx() { cx.state.keywords =
typeKeywords; }Ð function valcx() { cx.state.keywords = valKeywords; }Ð
poplex.lex = typecx.lex = valcx.lex = true;Ð function commasep(comb, end) {Ð
    function more(type) {Ð     if (type == ",") return cont(comb, more);Ð
if (type == end) return cont();Ð     return cont(more);Ð   }Ð   return
function(type) {Ð     if (type == end) return cont();Ð     return pass(comb,
more);Ð   };Ð }Ð function stat_of(comb, tag) {Ð   return cont(pushlex("stat",
tag), comb, poplex, block);Ð }Ð function block(type) {Ð   if (type == "}")
return cont();Ð   if (type == "let") return stat_of(letdef1, "let");Ð   if
(type == "fn") return stat_of(fndef);Ð   if (type == "type") return
cont(pushlex("stat"), tydef, endstatement, poplex, block);Ð   if (type ==
"enum") return stat_of(enumdef);Ð   if (type == "mod") return stat_of(mod);Ð
    if (type == "iface") return stat_of(iface);Ð   if (type == "impl") return
stat_of(impl);Ð   if (type == "open-attr") return cont(pushlex("]"),
commasep(expression, "]"), poplex);Ð   if (type == "ignore" || type.match(/
[\]\);,]/)) return cont(block);Ð   return pass(pushlex("stat"), expression,
poplex, endstatement, block);Ð }Ð function endstatement(type) {Ð   if (type
== ";") return cont();Ð   return pass();Ð }Ð function expression(type) {Ð
if (type == "atom" || type == "name") return cont(maybeop);Ð   if (type ==
"{") return cont(pushlex("}"), exprbrace, poplex);Ð   if (type.match(/
[\[\(]/)) return matchBrackets(type, expression);Ð   if (type.match(/
[\]\)\};,]/)) return pass();Ð   if (type == "if-style") return
cont(expression, expression);Ð   if (type == "else-style" || type == "op")
return cont(expression);Ð   if (type == "for") return cont(pattern,
maybetype, inop, expression, expression);Ð   if (type == "alt") return
cont(expression, altbody);Ð   if (type == "fn") return cont(fndef);Ð   if
(type == "macro") return cont(macro);Ð   return cont();Ð }Ð function
maybeop(type) {Ð   if (content == ".") return cont(maybeprop);Ð   if (content
== "::<"){return cont(typarams, maybeop);}Ð   if (type == "op" || content ==
":") return cont(expression);Ð   if (type == "(" || type == "[") return
matchBrackets(type, expression);Ð   return pass();Ð }Ð function maybeprop() {Ð
    if (content.match(/^\w+$/)) {cx.marked = "variable"; return
cont(maybeop);}Ð   return pass(expression);Ð }Ð function exprbrace(type) {Ð
if (type == "op") {Ð     if (content == "|") return cont(blockvars, poplex,
pushlex("}", "block"), block);Ð     if (content == "||") return cont(poplex,
pushlex("}", "block"), block);Ð   }Ð   if (content == "mutable" ||
(content.match(/^\w+$/) && cx.stream.peek() == ":"Ð
                                  && !cx.stream.match("::", false)))Ð
return pass(record_of(expression));Ð   return pass(block);Ð }Ð function
record_of(comb) {Ð   function ro(type) {Ð     if (content == "mutable" ||
content == "with") {cx.marked = "keyword"; return cont(ro);}Ð     if
(content.match(/^\w*$/)) {cx.marked = "variable"; return cont(ro);}Ð     if
(type == ":") return cont(comb, ro);Ð     if (type == "}") return cont();Ð
      return cont(ro);Ð   }Ð   return ro;Ð }Ð function blockvars(type) {Ð
if (type == "name") {cx.marked = "def"; return cont(blockvars);}Ð   if (type
== "op" && content == "|") return cont();Ð   return cont(blockvars);Ð }Ð
function letdef1(type) {Ð
```

```
                            if (type.match(/[\]\)\};]/)) return cont();Ð   if
(content == "=") return cont(expression, letdef2);Ð   if (type == ",") return
cont(letdef1);Ð   return pass(pattern, maybetype, letdef1);Ð }Ð function
letdef2(type) {Ð   if (type.match(/[\]\)\};,]/)) return pass(letdef1);Ð
else return pass(expression, letdef2);Ð }Ð function maybetype(type) {Ð   if
(type == ":") return cont(typecx, rtype, valcx);Ð   return pass();Ð }Ð
function inop(type) {Ð   if (type == "name" && content == "in") {cx.marked =
"keyword"; return cont();}Ð   return pass();Ð }Ð function fndef(type) {Ð   if
(content == "@" || content == "~") {cx.marked = "keyword"; return
cont(fndef);}Ð   if (type == "name") {cx.marked = "def"; return cont(fndef);}Ð
    if (content == "<") return cont(typarams, fndef);Ð   if (type == "{")
return pass(expression);Ð   if (type == "(") return cont(pushlex(")"),
commasep(argdef, ")"), poplex, fndef);Ð   if (type == "->") return
cont(typecx, rtype, valcx, fndef);Ð   if (type == ";") return cont();Ð
return cont(fndef);Ð }Ð function tydef(type) {Ð   if (type == "name")
{cx.marked = "def"; return cont(tydef);}Ð   if (content == "<") return
cont(typarams, tydef);Ð   if (content == "=") return cont(typecx, rtype,
valcx);Ð   return cont(tydef);Ð }Ð function enumdef(type) {Ð   if (type ==
"name") {cx.marked = "def"; return cont(enumdef);}Ð   if (content == "<")
return cont(typarams, enumdef);Ð   if (content == "=") return cont(typecx,
rtype, valcx, endstatement);Ð   if (type == "{") return cont(pushlex("}"),
typecx, enumblock, valcx, poplex);Ð   return cont(enumdef);Ð }Ð function
enumblock(type) {Ð   if (type == "}") return cont();Ð   if (type == "(")
return cont(pushlex(")"), commasep(rtype, ")"), poplex, enumblock);Ð   if
(content.match(/^\w+$/)) cx.marked = "def";Ð   return cont(enumblock);Ð }Ð
function mod(type) {Ð   if (type == "name") {cx.marked = "def"; return
cont(mod);}Ð   if (type == "{") return cont(pushlex("}"), block, poplex);Ð
return pass();Ð }Ð function iface(type) {Ð   if (type == "name") {cx.marked =
"def"; return cont(iface);}Ð   if (content == "<") return cont(typarams,
iface);Ð   if (type == "{") return cont(pushlex("}"), block, poplex);Ð
return pass();Ð }Ð function impl(type) {Ð   if (content == "<") return
cont(typarams, impl);Ð   if (content == "of" || content == "for") {cx.marked
= "keyword"; return cont(rtype, impl);}Ð   if (type == "name") {cx.marked =
"def"; return cont(impl);}Ð   if (type == "{") return cont(pushlex("}"),
block, poplex);Ð   return pass();Ð }Ð function typarams() {Ð   if (content ==
">") return cont();Ð   if (content == ",") return cont(typarams);Ð   if
(content == ":") return cont(rtype, typarams);Ð   return pass(rtype,
typarams);Ð }Ð function argdef(type) {Ð   if (type == "name") {cx.marked =
"def"; return cont(argdef);}Ð   if (type == ":") return cont(typecx, rtype,
valcx);Ð   return pass();Ð }Ð function rtype(type) {Ð   if (type == "name")
{cx.marked = "variable-3"; return cont(rtypemaybeparam); }Ð   if (content ==
"mutable") {cx.marked = "keyword"; return cont(rtype);}Ð   if (type ==
"atom") return cont(rtypemaybeparam);Ð   if (type == "op" || type == "obj")
return cont(rtype);Ð   if (type == "fn") return cont(fntype);Ð   if (type ==
"{") return cont(pushlex("{"), record_of(rtype), poplex);Ð   return
matchBrackets(type, rtype);Ð }Ð function rtypemaybeparam() {Ð   if (content
== "<") return cont(typarams);Ð   return pass();Ð }Ð function fntype(type) {Ð
    if (type == "(") return cont(pushlex("("), commasep(rtype, ")"), poplex,
fntype);Ð   if (type == "->") return cont(rtype);Ð   return pass();Ð }Ð
function pattern(type) {Ð   if (type == "name") {cx.marked = "def"; return
cont(patternmaybeop);}Ð   if (type == "atom") return cont(patternmaybeop);Ð
if (type == "op") return cont(pattern);Ð   if (type.match(/[\]\)\};,]/))
return pass();Ð   return matchBrackets(type, pattern);Ð }Ð function
patternmaybeop(type) {Ð   if (type == "op" && content == ".") return cont();Ð
    if (content == "to") {cx.marked = "keyword"; return cont(pattern);}Ð
else return pass();Ð }Ð function altbody(type) {Ð   if (type == "{") return
cont(pushlex("}", "alt"), altblock1, poplex);Ð   return pass();Ð }Ð function
altblock1(type) {Ð   if (type == "}") return cont();Ð   if (type == "|")
return cont(altblock1);Ð   if (content == "when") {cx.marked = "keyword";
return cont(expression, altblock2);}Ð
```

```
                                        if (type.match(/[\]\);,]/)) return
cont(altblock1);Ð   return pass(pattern, altblock2);Ð }Ð function
altblock2(type) {Ð   if (type == "{") return cont(pushlex("}", "alt"), block,
poplex, altblock1);Ð   else return pass(altblock1);Ð }Ð function macro(type) {Ð
    if (type.match(/[\[\(\{]/)) return matchBrackets(type, expression);Ð
return pass();Ð }Ð function matchBrackets(type, comb) {Ð   if (type == "[")
return cont(pushlex("]"), commasep(comb, "]"), poplex);Ð   if (type == "(")
return cont(pushlex(")"), commasep(comb, ")"), poplex);Ð   if (type == "{")
return cont(pushlex("}"), commasep(comb, "}"), poplex);Ð   return cont();Ð }Ð
function parse(state, stream, style) {Ð   var cc = state.cc;Ð   //
Communicate our context to the combinators.Ð   // (Less wasteful than consing
up a hundred closures on every call.)Ð   cx.state = state; cx.stream =
stream; cx.marked = null, cx.cc = cc;Ð   while (true) {Ð     var combinator =
cc.length ? cc.pop() : block;Ð     if (combinator(tcat)) {Ð
while(cc.length && cc[cc.length - 1].lex)Ð         cc.pop()();Ð       return
cx.marked || style;Ð     }Ð   }Ð }Ð return {Ð   startState: function() {Ð
return {Ð       tokenize: tokenBase,Ð       cc: [],Ð       lexical:
{indented: -indentUnit, column: 0, type: "top", align: false},Ð
keywords: valKeywords,Ð       indented: 0Ð     };Ð   },Ð   token:
function(stream, state) {Ð     if (stream.sol()) {Ð       if (!
state.lexical.hasOwnProperty("align"))Ð         state.lexical.align = false;Ð
        state.indented = stream.indentation();Ð     }Ð     if
(stream.eatSpace()) return null;Ð     tcat = content = null;Ð     var style =
state.tokenize(stream, state);Ð     if (style == "comment") return style;Ð
      if (!state.lexical.hasOwnProperty("align"))Ð       state.lexical.align
= true;Ð     if (tcat == "prefix") return style;Ð     if (!content) content =
stream.current();Ð     return parse(state, stream, style);Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.tokenize != tokenBase) return 0;Ð
      var firstChar = textAfter && textAfter.charAt(0), lexical =
state.lexical,Ð         type = lexical.type, closing = firstChar == type;Ð
      if (type == "stat") return lexical.indented + indentUnit;Ð     if
(lexical.align) return lexical.column + (closing ? 0 : 1);Ð     return
lexical.indented + (closing ? 0 : (lexical.info == "alt" ? altIndentUnit :
indentUnit));Ð   },Ð   electricChars: "{}",Ð   blockCommentStart: "/*",Ð
blockCommentEnd: "*/",Ð   lineComment: "//",Ð   fold: "brace"Ð };Ð});Ð
CodeMirror.defineMIME("text/x-rustsrc", "rust");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\sass\sass.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("sass", function(config) {Ð function tokenRegexp(words)
{Ð   return new RegExp("^" + words.join("|"));Ð }Ð var keywords = ["true",
"false", "null", "auto"];Ð var keywordsRegexp = new RegExp("^" +
keywords.join("|"));Ð var operators = ["\\(", "\\)", "=", ">", "<", "==",
">=", "<=", "\\+", "-", "\\!=", "/", "\\*", "%", "and", "or", "not"];Ð var
opRegexp = tokenRegexp(operators);Ð var pseudoElementsRegexp = /^::?[\w\-]+/;Ð
  function urlTokens(stream, state) {Ð   var ch = stream.peek();Ð   if (ch
=== ")") {Ð     stream.next();Ð     state.tokenizer = tokenBase;Ð     return
"operator";Ð   } else if (ch === "(") {Ð     stream.next();Ð
stream.eatSpace();Ð     return "operator";Ð   } else if (ch === "'" || ch ===
'"') {Ð     state.tokenizer = buildStringTokenizer(stream.next());Ð
return "string";Ð   } else {Ð     state.tokenizer = buildStringTokenizer(")",
false);Ð     return "string";Ð   }Ð }Ð function comment(indentation,
multiLine) {Ð   return function(stream, state) {Ð     if (stream.sol() &&
stream.indentation() <= indentation) {Ð       state.tokenizer = tokenBase;Ð
        return tokenBase(stream, state);Ð     }Ð     if (multiLine &&
stream.skipTo("*/")) {Ð       stream.next();Ð       stream.next();Ð
state.tokenizer = tokenBase;Ð     } else {Ð       stream.next();Ð     }Ð
return "comment";Ð   };Ð }Ð function buildStringTokenizer(quote, greedy) {Ð
if(greedy == null) { greedy = true; }Ð   function stringTokenizer(stream,
state) {Ð     var nextChar = stream.next();Ð     var peekChar = stream.peek();Ð
      var previousChar = stream.string.charAt(stream.pos-2);Ð     var
endingString = ((nextChar !== "\\" && peekChar === quote) || (nextChar ===
quote && previousChar !== "\\"));Ð     if (endingString) {Ð       if
(nextChar !== quote && greedy) { stream.next(); }Ð       state.tokenizer =
tokenBase;Ð       return "string";Ð     } else if (nextChar === "#" &&
peekChar === "{") {Ð       state.tokenizer =
buildInterpolationTokenizer(stringTokenizer);Ð       stream.next();Ð
return "operator";Ð     } else {Ð       return "string";Ð     }Ð   }Ð
return stringTokenizer;Ð }Ð function
buildInterpolationTokenizer(currentTokenizer) {Ð   return function(stream,
state) {Ð     if (stream.peek() === "}") {Ð       stream.next();Ð
state.tokenizer = currentTokenizer;Ð       return "operator";Ð     } else {Ð
        return tokenBase(stream, state);Ð     }Ð   };Ð }Ð function
indent(state) {Ð   if (state.indentCount == 0) {Ð     state.indentCount++;Ð
      var lastScopeOffset = state.scopes[0].offset;Ð     var currentOffset =
lastScopeOffset + config.indentUnit;Ð
state.scopes.unshift({ offset:currentOffset });Ð   }Ð }Ð function
dedent(state) {Ð   if (state.scopes.length == 1) return;Ð
state.scopes.shift();Ð }Ð function tokenBase(stream, state) {Ð   var ch =
stream.peek();Ð   // Comment Ð   if (stream.match("/*")) {Ð
state.tokenizer = comment(stream.indentation(), true);Ð     return
state.tokenizer(stream, state);Ð   }Ð   if (stream.match("//")) {Ð
state.tokenizer = comment(stream.indentation(), false);Ð     return
state.tokenizer(stream, state);Ð   }Ð   // Interpolation Ð   if
(stream.match("#{")) {Ð     state.tokenizer =
buildInterpolationTokenizer(tokenBase);Ð     return "operator";Ð   }Ð   if
(ch === ".") {Ð     stream.next();Ð     // Match class selectors Ð     if
(stream.match(/^[\w-]+/)) {Ð       indent(state);Ð       return "atom";Ð
      } else if (stream.peek() === "#") {Ð       indent(state);Ð       return
"atom";Ð     } else {Ð       return "operator";Ð     }Ð   }Ð   if (ch ===
"#") {Ð     stream.next();Ð     // Hex numbers Ð     if (stream.match(/[0-9a-
fA-F]{6}|[0-9a-fA-F]{3}/))Ð
```

```
                                    return "number";Ð     // ID selectorsÐ
if (stream.match(/^[\w-]+/)) {Ð       indent(state);Ð       return "atom";Ð
      }Ð     if (stream.peek() === "#") {Ð       indent(state);Ð       return
"atom";Ð     }Ð   }Ð   // NumbersÐ   if (stream.match(/^-?[0-9\.]+/))Ð
return "number";Ð   // UnitsÐ   if (stream.match(/^(px|em|in)\b/))Ð
return "unit";Ð   if (stream.match(keywordsRegexp))Ð     return "keyword";Ð
if (stream.match(/^url/) && stream.peek() === "(") {Ð     state.tokenizer =
urlTokens;Ð     return "atom";Ð   }Ð   // VariablesÐ   if (ch === "$") {Ð
stream.next();Ð     stream.eatWhile(/[\w-]/);Ð     if (stream.peek() === ":")
{Ð       stream.next();Ð       return "variable-2";Ð     } else {Ð
return "variable-3";Ð     }Ð   }Ð   if (ch === "!") {Ð     stream.next();Ð
      return stream.match(/^[\w]+/) ? "keyword": "operator";Ð   }Ð   if (ch
=== "=") {Ð     stream.next();Ð     // Match shortcut mixin definitionÐ
if (stream.match(/^[\w-]+/)) {Ð       indent(state);Ð       return "meta";Ð
      } else {Ð       return "operator";Ð     }Ð   }Ð   if (ch === "+") {Ð
      stream.next();Ð     // Match shortcut mixin definitionÐ     if
(stream.match(/^[\w-]+/))Ð       return "variable-3";Ð     elseÐ       return
"operator";Ð   }Ð   // Indent DirectivesÐ   if (stream.match(/^@(else if|if|
media|else|for|each|while|mixin|function)/)) {Ð     indent(state);Ð
return "meta";Ð   }Ð   // Other DirectivesÐ   if (ch === "@") {Ð
stream.next();Ð     stream.eatWhile(/[\w-]/);Ð     return "meta";Ð   }Ð   //
StringsÐ   if (ch === '"' || ch === "'") {Ð     stream.next();Ð
state.tokenizer = buildStringTokenizer(ch);Ð     return "string";Ð   }Ð   //
Pseudo element selectorsÐ   if (ch == ":" &&
stream.match(pseudoElementsRegexp))Ð     return "keyword";Ð   // atomsÐ   if
(stream.eatWhile(/[\w-&]/)) {Ð     // matches a property definitionÐ     if
(stream.peek() === ":" && !stream.match(pseudoElementsRegexp, false))Ð
return "property";Ð     elseÐ       return "atom";Ð   }Ð   if
(stream.match(opRegexp))Ð     return "operator";Ð   // If we haven't returned
by now, we move 1 characterÐ   // and return an errorÐ   stream.next();Ð
return null;Ð }Ð function tokenLexer(stream, state) {Ð   if (stream.sol())
state.indentCount = 0;Ð   var style = state.tokenizer(stream, state);Ð   var
current = stream.current();Ð   if (current === "@return")Ð     dedent(state);Ð
    if (style === "atom")Ð     indent(state);Ð   if (style !== null) {Ð
var startOfToken = stream.pos - current.length;Ð     var withCurrentIndent =
startOfToken + (config.indentUnit * state.indentCount);Ð     var newScopes =
[];Ð     for (var i = 0; i < state.scopes.length; i++) {Ð       var scope =
state.scopes[i];Ð       if (scope.offset <= withCurrentIndent)Ð
newScopes.push(scope);Ð     }Ð     state.scopes = newScopes;Ð   }Ð   return
style;Ð }Ð return {Ð   startState: function() {Ð     return {Ð
tokenizer: tokenBase,Ð       scopes: [{offset: 0, type: "sass"}],Ð
indentCount: 0,Ð       definedVars: [],Ð       definedMixins: []Ð     };Ð   },Ð
    token: function(stream, state) {Ð     var style = tokenLexer(stream,
state);Ð     state.lastToken = { style: style, content: stream.current() };Ð
      return style;Ð   },Ð   indent: function(state) {Ð     return
state.scopes[0].offset;Ð   }Ð };Ð});ÐodeMirror.defineMIME("text/x-sass",
"sass");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\shell\shell.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode('shell', function() {Ð var words = {};Ð function
define(style, string) {Ð   var split = string.split(' ');Ð   for(var i = 0; i
< split.length; i++) {Ð     words[split[i]] = style;Ð   }Ð };Ð // AtomsÐ
define('atom', 'true false');Ð // KeywordsÐ define('keyword', 'if then do
else elif while until for in esac fi fin ' +Ð   'fil done exit set unset
export function');Ð // CommandsÐ define('builtin', 'ab awk bash beep cat cc
cd chown chmod chroot clear cp ' +Ð   'curl cut diff echo find gawk gcc get
git grep kill killall ln ls make ' +Ð   'mkdir openssl mv nc node npm ping ps
restart rm rmdir sed service sh ' +Ð   'shopt shred source sort sleep ssh
start stop su sudo tee telnet top ' +Ð   'touch vi vim wall wc wget who write
yes zsh');Ð function tokenBase(stream, state) {Ð   if (stream.eatSpace())
return null;Ð   var sol = stream.sol();Ð   var ch = stream.next();Ð   if (ch
=== '\\') {Ð     stream.next();Ð     return null;Ð   }Ð   if (ch === '\'' ||
ch === '"' || ch === '`') {Ð     state.tokens.unshift(tokenString(ch));Ð
return tokenize(stream, state);Ð   }Ð   if (ch === '#') {Ð     if (sol &&
stream.eat('!')) {Ð       stream.skipToEnd();Ð       return 'meta'; //
'comment'?Ð     }Ð     stream.skipToEnd();Ð     return 'comment';Ð   }Ð   if
(ch === '$') {Ð     state.tokens.unshift(tokenDollar);Ð     return
tokenize(stream, state);Ð   }Ð   if (ch === '+' || ch === '=') {Ð     return
'operator';Ð   }Ð   if (ch === '-') {Ð     stream.eat('-');Ð
stream.eatWhile(/\w/);Ð     return 'attribute';Ð   }Ð   if (/\d/.test(ch)) {Ð
      stream.eatWhile(/\d/);Ð     if(stream.eol() || !/
\w/.test(stream.peek())) {Ð       return 'number';Ð     }Ð   }Ð
stream.eatWhile(/[\w-]/);Ð   var cur = stream.current();Ð   if (stream.peek()
=== '=' && /\w+/.test(cur)) return 'def';Ð   return
words.hasOwnProperty(cur) ? words[cur] : null;Ð }Ð function
tokenString(quote) {Ð   return function(stream, state) {Ð     var next, end =
false, escaped = false;Ð     while ((next = stream.next()) != null) {Ð
if (next === quote && !escaped) {Ð         end = true;Ð         break;Ð
        }Ð       if (next === '$' && !escaped && quote !== '\'') {Ð
escaped = true;Ð         stream.backUp(1);Ð
state.tokens.unshift(tokenDollar);Ð         break;Ð       }Ð       escaped = !
escaped && next === '\\';Ð     }Ð     if (end || !escaped) {Ð
state.tokens.shift();Ð     }Ð     return (quote === '`' || quote === ')' ?
'quote' : 'string');Ð   };Ð };Ð var tokenDollar = function(stream, state) {Ð
    if (state.tokens.length > 1) stream.eat('$');Ð   var ch = stream.next(),
hungry = /\w/;Ð   if (ch === '{') hungry = /[^}]/;Ð   if (ch === '(') {Ð
state.tokens[0] = tokenString(')');Ð     return tokenize(stream, state);Ð   }Ð
    if (!/\d/.test(ch)) {Ð     stream.eatWhile(hungry);Ð     stream.eat('}');Ð
    }Ð   state.tokens.shift();Ð   return 'def';Ð };Ð function
tokenize(stream, state) {Ð   return (state.tokens[0] || tokenBase) (stream,
state);Ð };Ð return {Ð   startState: function() {return {tokens:[]};},Ð
token: function(stream, state) {Ð     return tokenize(stream, state);Ð   },Ð
    lineComment: '#'Ð };Ð});ÐodeMirror.defineMIME('text/x-sh', 'shell');Ð});Ð
```

public\assets\js\plugins\codemirror\mode\shell\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({}, "shell");Ð function MT(name) { test.mode(name, mode,
Array.prototype.slice.call(arguments, 1)); }Ð MT("var",Ð    "text [def $var]
text");Ð MT("varBraces",Ð    "text[def ${var}]text");Ð MT("varVar",Ð    "text
[def $a$b] text");Ð MT("varBracesVarBraces",Ð    "text[def ${a}${b}]text");Ð
MT("singleQuotedVar",Ð    "[string 'text $var text']");Ð
MT("singleQuotedVarBraces",Ð    "[string 'text ${var} text']");Ð
MT("doubleQuotedVar",Ð    '[string "text ][def $var][string  text"]');Ð
MT("doubleQuotedVarBraces",Ð    '[string "text][def ${var}][string text"]');Ð
MT("doubleQuotedVarPunct",Ð    '[string "text ][def $@][string  text"]');Ð
MT("doubleQuotedVarVar",Ð    '[string "][def $a$b][string "]');Ð
MT("doubleQuotedVarBracesVarBraces",Ð    '[string "][def ${a}${b}][string
"]');Ð MT("notAString",Ð    "text\\'text");Ð MT("escapes",Ð    "outside\\'\\
\"\\`\\\\[string \"inside\\`\\'\\\"\\\\`\\$notAVar\"]outside\\$\
\(notASubShell\\)");Ð MT("subshell",Ð    "[builtin echo] [quote $(whoami)] s
log, stardate [quote `date`].");Ð MT("doubleQuotedSubshell",Ð    "[builtin
echo] [string \"][quote $(whoami)][string 's log, stardate `date`.\"]");Ð
MT("hashbang",Ð    "[meta #!/bin/bash]");Ð MT("comment",Ð    "text [comment #
Blurb]");Ð MT("numbers",Ð    "[number 0] [number 1] [number 2]");Ð
MT("keywords",Ð    "[keyword while] [atom true]; [keyword do]",Ð
"  [builtin sleep] [number 3]",Ð    "[keyword done]");Ð MT("options",Ð
"[builtin ls] [attribute -l] [attribute --human-readable]");Ð MT("operator",Ð
     "[def var][operator =]value");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\sieve\sieve.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("sieve", function(config) {Ð function words(str) {Ð
var obj = {}, words = str.split(" ");Ð   for (var i = 0; i < words.length; +
+i) obj[words[i]] = true;Ð   return obj;Ð }Ð var keywords = words("if elsif
else stop require");Ð var atoms = words("true false not");Ð var indentUnit =
config.indentUnit;Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (ch == "/" && stream.eat("*")) {Ð     state.tokenize =
tokenCComment;Ð     return tokenCComment(stream, state);Ð   }Ð   if (ch ===
'#') {Ð     stream.skipToEnd();Ð     return "comment";Ð   }Ð   if (ch ==
"\"") {Ð     state.tokenize = tokenString(ch);Ð     return
state.tokenize(stream, state);Ð   }Ð   if (ch == "(") {Ð
state._indent.push("(");Ð     // add virtual angel wings so that editor
behaves...Ð     // ...more sane incase of broken brackets Ð
state._indent.push("{");Ð     return null;Ð   }Ð   if (ch === "{") {Ð
state._indent.push("{");Ð     return null;Ð   }Ð   if (ch == ")")  {Ð
state._indent.pop();Ð     state._indent.pop();Ð   }Ð   if (ch === "}") {Ð
state._indent.pop();Ð     return null;Ð   }Ð   if (ch == ",")Ð     return
null;Ð   if (ch == ";")Ð     return null;Ð   if (/[{}\(\),;]/.test(ch))Ð
return null;Ð   // 1*DIGIT "K" / "M" / "G"Ð   if (/\d/.test(ch)) {Ð
stream.eatWhile(/[\d]/);Ð     stream.eat(/[KkMmGg]/);Ð     return "number";Ð
    }Ð   // ":" (ALPHA / "_") *(ALPHA / DIGIT / "_")Ð   if (ch == ":") {Ð
stream.eatWhile(/[a-zA-Z_]/);Ð     stream.eatWhile(/[a-zA-Z0-9_]/);Ð
return "operator";Ð   }Ð   stream.eatWhile(/\w/);Ð   var cur =
stream.current();Ð   // "text:" *(SP / HTAB) (hash-comment / CRLF)Ð   //
*(multiline-literal / multiline-dotstart)Ð   // "." CRLFÐ   if ((cur ==
"text") && stream.eat(":"))Ð   {Ð     state.tokenize = tokenMultiLineString;Ð
      return "string";Ð   }Ð   if (keywords.propertyIsEnumerable(cur))Ð
return "keyword";Ð   if (atoms.propertyIsEnumerable(cur))Ð     return "atom";Ð
    return null;Ð }Ð function tokenMultiLineString(stream, state)Ð {Ð
state._multiLineString = true;Ð   // the first line is special it may contain
a commentÐ   if (!stream.sol()) {Ð     stream.eatSpace();Ð     if
(stream.peek() == "#") {Ð       stream.skipToEnd();Ð       return "comment";Ð
      }Ð     stream.skipToEnd();Ð     return "string";Ð   }Ð   if
((stream.next() == ".")  && (stream.eol()))Ð   {Ð     state._multiLineString
= false;Ð     state.tokenize = tokenBase;Ð   }Ð   return "string";Ð }Ð
function tokenCComment(stream, state) {Ð   var maybeEnd = false, ch;Ð   while
((ch = stream.next()) != null) {Ð     if (maybeEnd && ch == "/") {Ð
state.tokenize = tokenBase;Ð       break;Ð     }Ð     maybeEnd = (ch == "*");Ð
    }Ð   return "comment";Ð }Ð function tokenString(quote) {Ð   return
function(stream, state) {Ð     var escaped = false, ch;Ð     while ((ch =
stream.next()) != null) {Ð       if (ch == quote && !escaped)Ð         break;Ð
        escaped = !escaped && ch == "\\";Ð     }Ð     if (!escaped)
state.tokenize = tokenBase;Ð     return "string";Ð   };Ð }Ð return {Ð
startState: function(base) {Ð     return {tokenize: tokenBase,Ð
baseIndent: base || 0,Ð             _indent: []};Ð   },Ð   token:
function(stream, state) {Ð     if (stream.eatSpace())Ð       return null;Ð
      return (state.tokenize || tokenBase)(stream, state);;Ð   },Ð   indent:
function(state, _textAfter) {Ð     var length = state._indent.length;Ð     if
(_textAfter && (_textAfter[0] == "}"))Ð       length--;Ð     if (length <0)Ð
        length = 0;Ð     return length * indentUnit;Ð   },Ð   electricChars:
"}"Ð };Ð});ÐodeMirror.defineMIME("application/sieve", "sieve");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\slim\slim.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð// Slim Highlighting for
CodeMirror copyright (c) HicknHack Software Gmbh Ð(function(mod) {Ð if (typeof
exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../htmlmixed/htmlmixed"),
require("../ruby/ruby"));Ð else if (typeof define == "function" &&
define.amd) // AMD Ð   define(["../../lib/codemirror", "../htmlmixed/
htmlmixed", "../ruby/ruby"], mod);Ð else // Plain browser env Ð
mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("slim", function(config) {Ð   var htmlMode =
CodeMirror.getMode(config, {name: "htmlmixed"});Ð   var rubyMode =
CodeMirror.getMode(config, "ruby");Ð   var modes = { html: htmlMode, ruby:
rubyMode };Ð   var embedded = {Ð     ruby: "ruby",Ð     javascript:
"javascript",Ð     css: "text/css",Ð     sass: "text/x-sass",Ð     scss:
"text/x-scss",Ð     less: "text/x-less",Ð     styl: "text/x-styl", // no
highlighting so farÐ     coffee: "coffeescript",Ð     asciidoc: "text/x-
asciidoc",Ð     markdown: "text/x-markdown",Ð     textile: "text/x-
textile", // no highlighting so farÐ     creole: "text/x-creole", // no
highlighting so farÐ     wiki: "text/x-wiki", // no highlighting so farÐ
mediawiki: "text/x-mediawiki", // no highlighting so farÐ     rdoc: "text/x-
rdoc", // no highlighting so farÐ     builder: "text/x-builder", // no
highlighting so farÐ     nokogiri: "text/x-nokogiri", // no highlighting so
farÐ     erb: "application/x-erb"Ð   };Ð   var embeddedRegexp = function(map){Ð
      var arr = [];Ð     for(var key in map) arr.push(key);Ð     return new
RegExp("^("+arr.join('|')+"):");Ð   }(embedded);Ð   var styleMap = {Ð
"commentLine": "comment",Ð     "slimSwitch": "operator special",Ð
"slimTag": "tag",Ð     "slimId": "attribute def",Ð     "slimClass":
"attribute qualifier",Ð     "slimAttribute": "attribute",Ð     "slimSubmode":
"keyword special",Ð     "closeAttributeTag": null,Ð     "slimDoctype": null,Ð
      "lineContinuation": nullÐ   };Ð   var closing = {Ð     "{": "}",Ð
"[": "]",Ð     "(": ")"Ð   };Ð   var nameStartChar = "_a-zA-Z\xC0-\xD6\xD8-
\xF6\xF8-\u02FF\u0370-\u037D\u037F-\u1FFF\u200C-\u200D\u2070-\u218F\u2C00-
\u2FEF\u3001-\uD7FF\uF900-\uFDCF\uFDF0-\uFFFD";Ð   var nameChar =
nameStartChar + "\\-0-9\xB7\u0300-\u036F\u203F-\u2040";Ð   var nameRegexp =
new RegExp("^[:"+nameStartChar+"](?::["+nameChar+"]|["+nameChar+"]*)");Ð
var attributeNameRegexp = new RegExp("^[:"+nameStartChar+"][:\
\."+nameChar+"]*(?=\\s*=)");Ð   var wrappedAttributeNameRegexp = new
RegExp("^[:"+nameStartChar+"][:\\."+nameChar+"]*");Ð   var classNameRegexp = /
^\.-?[_a-zA-Z]+[\w\-]*/;Ð   var classIdRegexp = /^#[_a-zA-Z]+[\w\-]*/;Ð
function backup(pos, tokenize, style) {Ð     var restore = function(stream,
state) {Ð       state.tokenize = tokenize;Ð       if (stream.pos < pos) {Ð
          stream.pos = pos;Ð         return style;Ð       }Ð       return
state.tokenize(stream, state);Ð     };Ð     return function(stream, state) {Ð
        state.tokenize = restore;Ð       return tokenize(stream, state);Ð
      };Ð   }Ð   function maybeBackup(stream, state, pat, offset, style) {Ð
      var cur = stream.current();Ð     var idx = cur.search(pat);Ð     if
(idx > -1) {Ð       state.tokenize = backup(stream.pos, state.tokenize,
style);Ð       stream.backUp(cur.length - idx - offset);Ð     }Ð     return
style;Ð   }Ð   function continueLine(state, column) {Ð     state.stack = {Ð
        parent: state.stack,Ð       style: "continuation",Ð       indented:
column,Ð       tokenize: state.lineÐ     };Ð     state.line = state.tokenize;Ð
    }Ð   function finishContinue(state) {Ð     if (state.line ==
state.tokenize) {Ð       state.line = state.stack.tokenize;Ð
state.stack = state.stack.parent;Ð     }Ð   }Ð   function
lineContinuable(column, tokenize) {Ð     return function(stream, state) {Ð
        finishContinue(state);Ð       if (stream.match(/^\\$/)) {Ð
continueLine(state, column);Ð         return "lineContinuation";Ð       }Ð
        var style = tokenize(stream, state);Ð       if (stream.eol() &&
stream.current().match(/(?:^|[^\\])(?:\\\\)*\\$/)) {Ð
```

```
stream.backUp(1);Ð       }Ð       return style;Ð     };Ð   }Ð   function
commaContinuable(column, tokenize) {Ð     return function(stream, state) {Ð
        finishContinue(state);Ð       var style = tokenize(stream, state);Ð
        if (stream.eol() && stream.current().match(/,$/)) {Ð
continueLine(state, column);Ð       }Ð       return style;Ð     };Ð   }Ð
function rubyInQuote(endQuote, tokenize) {Ð     // TODO: add multi line
supportÐ     return function(stream, state) {Ð       var ch = stream.peek();Ð
        if (ch == endQuote && state.rubyState.tokenize.length == 1) {Ð
          // step out of ruby context as it seems to complete processing all
the bracesÐ         stream.next();Ð         state.tokenize = tokenize;Ð
          return "closeAttributeTag";Ð       } else {Ð         return
ruby(stream, state);Ð       }Ð     };Ð   }Ð   function
startRubySplat(tokenize) {Ð     var rubyState;Ð     var runSplat =
function(stream, state) {Ð       if (state.rubyState.tokenize.length == 1 && !
state.rubyState.context.prev) {Ð         stream.backUp(1);Ð         if
(stream.eatSpace()) {Ð           state.rubyState = rubyState;Ð
state.tokenize = tokenize;Ð           return tokenize(stream, state);Ð
          }Ð         stream.next();Ð       }Ð       return ruby(stream,
state);Ð     };Ð     return function(stream, state) {Ð       rubyState =
state.rubyState;Ð       state.rubyState = rubyMode.startState();Ð
state.tokenize = runSplat;Ð       return ruby(stream, state);Ð     };Ð   }Ð
function ruby(stream, state) {Ð     return rubyMode.token(stream,
state.rubyState);Ð   }Ð   function htmlLine(stream, state) {Ð     if
(stream.match(/^\\$/)) {Ð       return "lineContinuation";Ð     }Ð     return
html(stream, state);Ð   }Ð   function html(stream, state) {Ð     if
(stream.match(/^#\{/)) {Ð       state.tokenize = rubyInQuote("}",
state.tokenize);Ð       return null;Ð     }Ð     return maybeBackup(stream,
state, /[^\\]#\{/, 1, htmlMode.token(stream, state.htmlState));Ð   }Ð
function startHtmlLine(lastTokenize) {Ð     return function(stream, state) {Ð
        var style = htmlLine(stream, state);Ð       if (stream.eol())
state.tokenize = lastTokenize;Ð       return style;Ð     };Ð   }Ð   function
startHtmlMode(stream, state, offset) {Ð     state.stack = {Ð       parent:
state.stack,Ð       style: "html",Ð       indented: stream.column() +
offset, // pipe + spaceÐ       tokenize: state.lineÐ     };Ð     state.line =
state.tokenize = html;Ð     return null;Ð   }Ð   function comment(stream,
state) {Ð     stream.skipToEnd();Ð     return state.stack.style;Ð   }Ð
function commentMode(stream, state) {Ð     state.stack = {Ð       parent:
state.stack,Ð       style: "comment",Ð       indented: state.indented + 1,Ð
        tokenize: state.lineÐ     };Ð     state.line = comment;Ð     return
comment(stream, state);Ð   }Ð   function attributeWrapper(stream, state) {Ð
      if (stream.eat(state.stack.endQuote)) {Ð       state.line =
state.stack.line;Ð       state.tokenize = state.stack.tokenize;Ð
state.stack = state.stack.parent;Ð       return null;Ð     }Ð     if
(stream.match(wrappedAttributeNameRegexp)) {Ð       state.tokenize =
attributeWrapperAssign;Ð       return "slimAttribute";Ð     }Ð
stream.next();Ð     return null;Ð   }Ð   function
attributeWrapperAssign(stream, state) {Ð     if (stream.match(/^==?/)) {Ð
        state.tokenize = attributeWrapperValue;Ð       return null;Ð     }Ð
      return attributeWrapper(stream, state);Ð   }Ð   function
attributeWrapperValue(stream, state) {Ð     var ch = stream.peek();Ð     if
(ch == '"' || ch == "\'") {Ð       state.tokenize = readQuoted(ch, "string",
true, false, attributeWrapper);Ð       stream.next();Ð       return
state.tokenize(stream, state);Ð     }Ð     if (ch == '[') {Ð       return
startRubySplat(attributeWrapper)(stream, state);Ð     }Ð     if
(stream.match(/^(true|false|nil)\b/)) {Ð       state.tokenize =
attributeWrapper;Ð       return "keyword";Ð     }Ð     return
startRubySplat(attributeWrapper)(stream, state);Ð   }Ð   function
startAttributeWrapperMode(state, endQuote, tokenize) {Ð     state.stack = {Ð
        parent: state.stack,Ð
```

```
                                    style: "wrapper",Ð       indented:
state.indented + 1,Ð       tokenize: tokenize,Ð       line: state.line,Ð
        endQuote: endQuoteÐ     };Ð     state.line = state.tokenize =
attributeWrapper;Ð     return null;Ð   }Ð   function sub(stream, state) {Ð
      if (stream.match(/^#\{/)) {Ð       state.tokenize = rubyInQuote("}",
state.tokenize);Ð       return null;Ð     }Ð     var subStream = new
CodeMirror.StringStream(stream.string.slice(state.stack.indented),
stream.tabSize);Ð     subStream.pos = stream.pos - state.stack.indented;Ð
subStream.start = stream.start - state.stack.indented;Ð
subStream.lastColumnPos = stream.lastColumnPos - state.stack.indented;Ð
subStream.lastColumnValue = stream.lastColumnValue - state.stack.indented;Ð
      var style = state.subMode.token(subStream, state.subState);Ð
stream.pos = subStream.pos + state.stack.indented;Ð     return style;Ð   }Ð
function firstSub(stream, state) {Ð     state.stack.indented =
stream.column();Ð     state.line = state.tokenize = sub;Ð     return
state.tokenize(stream, state);Ð   }Ð   function createMode(mode) {Ð     var
query = embedded[mode];Ð     var spec = CodeMirror.mimeModes[query];Ð     if
(spec) {Ð       return CodeMirror.getMode(config, spec);Ð     }Ð     var
factory = CodeMirror.modes[query];Ð     if (factory) {Ð       return
factory(config, {name: query});Ð     }Ð     return CodeMirror.getMode(config,
"null");Ð   }Ð   function getMode(mode) {Ð     if (!
modes.hasOwnProperty(mode)) {Ð       return modes[mode] = createMode(mode);Ð
      }Ð     return modes[mode];Ð   }Ð   function startSubMode(mode, state) {Ð
      var subMode = getMode(mode);Ð     var subState = subMode.startState &&
subMode.startState();Ð     state.subMode = subMode;Ð     state.subState =
subState;Ð     state.stack = {Ð       parent: state.stack,Ð       style:
"sub",Ð       indented: state.indented + 1,Ð       tokenize: state.lineÐ
      };Ð     state.line = state.tokenize = firstSub;Ð     return
"slimSubmode";Ð   }Ð   function doctypeLine(stream, _state) {Ð
stream.skipToEnd();Ð     return "slimDoctype";Ð   }Ð   function
startLine(stream, state) {Ð     var ch = stream.peek();Ð     if (ch == '<') {Ð
        return (state.tokenize = startHtmlLine(state.tokenize))(stream,
state);Ð     }Ð     if (stream.match(/^[|']/)) {Ð       return
startHtmlMode(stream, state, 1);Ð     }Ð     if (stream.match(/^\/(!|
\[\w+])?/)) {Ð       return commentMode(stream, state);Ð     }Ð     if
(stream.match(/^(-|==?[<>]?)/)) {Ð       state.tokenize =
lineContinuable(stream.column(), commaContinuable(stream.column(), ruby));Ð
        return "slimSwitch";Ð     }Ð     if (stream.match(/^doctype\b/)) {Ð
        state.tokenize = doctypeLine;Ð       return "keyword";Ð     }Ð
var m = stream.match(embeddedRegexp);Ð     if (m) {Ð       return
startSubMode(m[1], state);Ð     }Ð     return slimTag(stream, state);Ð   }Ð
function slim(stream, state) {Ð     if (state.startOfLine) {Ð       return
startLine(stream, state);Ð     }Ð     return slimTag(stream, state);Ð   }Ð
function slimTag(stream, state) {Ð     if (stream.eat('*')) {Ð
state.tokenize = startRubySplat(slimTagExtras);Ð       return null;Ð     }Ð
      if (stream.match(nameRegexp)) {Ð       state.tokenize = slimTagExtras;Ð
        return "slimTag";Ð     }Ð     return slimClass(stream, state);Ð   }Ð
    function slimTagExtras(stream, state) {Ð     if (stream.match(/^(<>?|
><?)/)) {Ð       state.tokenize = slimClass;Ð       return null;Ð     }Ð
return slimClass(stream, state);Ð   }Ð   function slimClass(stream, state) {Ð
      if (stream.match(classIdRegexp)) {Ð       state.tokenize = slimClass;Ð
        return "slimId";Ð     }Ð     if (stream.match(classNameRegexp)) {Ð
        state.tokenize = slimClass;Ð       return "slimClass";Ð     }Ð
return slimAttribute(stream, state);Ð   }Ð   function slimAttribute(stream,
state) {Ð     if (stream.match(/^([\[\{\(])/)) {Ð       return
startAttributeWrapperMode(state, closing[RegExp.$1], slimAttribute);Ð     }Ð
      if (stream.match(attributeNameRegexp)) {Ð       state.tokenize =
slimAttributeAssign;Ð       return "slimAttribute";Ð     }Ð     if
(stream.peek() == '*') {Ð       stream.next();Ð       state.tokenize =
startRubySplat(slimContent);Ð
```

```
                                    return null;Ð     }Ð     return
slimContent(stream, state);Ð   }Ð   function slimAttributeAssign(stream,
state) {Ð     if (stream.match(/^==?/)) {Ð       state.tokenize =
slimAttributeValue;Ð       return null;Ð     }Ð     // should never happen,
because of forward lookupÐ     return slimAttribute(stream, state);Ð   }Ð
function slimAttributeValue(stream, state) {Ð     var ch = stream.peek();Ð
      if (ch == '"' || ch == "\'") {Ð       state.tokenize = readQuoted(ch,
"string", true, false, slimAttribute);Ð       stream.next();Ð       return
state.tokenize(stream, state);Ð     }Ð     if (ch == '[') {Ð       return
startRubySplat(slimAttribute)(stream, state);Ð     }Ð     if (ch == ':') {Ð
        return startRubySplat(slimAttributeSymbols)(stream, state);Ð     }Ð
      if (stream.match(/^(true|false|nil)\b/)) {Ð       state.tokenize =
slimAttribute;Ð       return "keyword";Ð     }Ð     return
startRubySplat(slimAttribute)(stream, state);Ð   }Ð   function
slimAttributeSymbols(stream, state) {Ð     stream.backUp(1);Ð     if
(stream.match(/^[^\s],(?=:)/)) {Ð       state.tokenize =
startRubySplat(slimAttributeSymbols);Ð       return null;Ð     }Ð
stream.next();Ð     return slimAttribute(stream, state);Ð   }Ð   function
readQuoted(quote, style, embed, unescaped, nextTokenize) {Ð     return
function(stream, state) {Ð       finishContinue(state);Ð       var fresh =
stream.current().length == 0;Ð       if (stream.match(/^\\$/, fresh)) {Ð
          if (!fresh) return style;Ð         continueLine(state,
state.indented);Ð         return "lineContinuation";Ð       }Ð       if
(stream.match(/^#\{/, fresh)) {Ð         if (!fresh) return style;Ð
state.tokenize = rubyInQuote("}", state.tokenize);Ð         return null;Ð
        }Ð       var escaped = false, ch;Ð       while ((ch = stream.next()) !
= null) {Ð         if (ch == quote && (unescaped || !escaped)) {Ð
state.tokenize = nextTokenize;Ð           break;Ð         }Ð         if
(embed && ch == "#" && !escaped) {Ð           if (stream.eat("{")) {Ð
              stream.backUp(2);Ð             break;Ð           }Ð         }Ð
          escaped = !escaped && ch == "\\";Ð       }Ð       if (stream.eol()
&& escaped) {Ð         stream.backUp(1);Ð       }Ð       return style;Ð     };Ð
    }Ð   function slimContent(stream, state) {Ð     if (stream.match(/^==?/))
{Ð       state.tokenize = ruby;Ð       return "slimSwitch";Ð     }Ð     if
(stream.match(/^\/$/)) { // tag close hintÐ       state.tokenize = slim;Ð
        return null;Ð     }Ð     if (stream.match(/^:/)) { // inline tagÐ
        state.tokenize = slimTag;Ð       return "slimSwitch";Ð     }Ð
startHtmlMode(stream, state, 0);Ð     return state.tokenize(stream, state);Ð
    }Ð   var mode = {Ð     // default to html modeÐ     startState:
function() {Ð       var htmlState = htmlMode.startState();Ð       var
rubyState = rubyMode.startState();Ð       return {Ð         htmlState:
htmlState,Ð         rubyState: rubyState,Ð         stack: null,Ð
last: null,Ð         tokenize: slim,Ð         line: slim,Ð         indented: 0Ð
        };Ð     },Ð     copyState: function(state) {Ð       return {Ð
htmlState : CodeMirror.copyState(htmlMode, state.htmlState),Ð
rubyState: CodeMirror.copyState(rubyMode, state.rubyState),Ð         subMode:
state.subMode,Ð         subState: state.subMode &&
CodeMirror.copyState(state.subMode, state.subState),Ð         stack:
state.stack,Ð         last: state.last,Ð         tokenize: state.tokenize,Ð
          line: state.lineÐ       };Ð     },Ð     token: function(stream,
state) {Ð       if (stream.sol()) {Ð         state.indented =
stream.indentation();Ð         state.startOfLine = true;Ð
state.tokenize = state.line;Ð         while (state.stack &&
state.stack.indented > state.indented && state.last != "slimSubmode") {Ð
            state.line = state.tokenize = state.stack.tokenize;Ð
state.stack = state.stack.parent;Ð           state.subMode = null;Ð
state.subState = null;Ð         }Ð       }Ð       if (stream.eatSpace())
return null;Ð       var style = state.tokenize(stream, state);Ð
state.startOfLine = false;Ð       if (style) state.last = style;Ð
return styleMap.hasOwnProperty(style) ? styleMap[style] : style;Ð
```

```
                                                                    },Ð
blankLine: function(state) {Ð       if (state.subMode &&
state.subMode.blankLine) {Ð         return
state.subMode.blankLine(state.subState);Ð       }Ð     },Ð     innerMode:
function(state) {Ð       if (state.subMode) return {state: state.subState,
mode: state.subMode};Ð       return {state: state, mode: mode};Ð     }Ð     //
indent: function(state) {Ð     //  return state.indented;Ð     //}Ð   };Ð
return mode;Ð }, "htmlmixed", "ruby");Ð CodeMirror.defineMIME("text/x-slim",
"slim");Ð CodeMirror.defineMIME("application/x-slim", "slim");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\slim\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ Slim Highlighting for
CodeMirror copyright (c) HicknHack Software Gmbh Ð function() {Ð var mode =
CodeMirror.getMode({tabSize: 4, indentUnit: 2}, "slim");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð //
Requires at least one media queryÐ MT("elementName",Ð    "[tag h1] Hey
There");Ð MT("oneElementPerLine",Ð    "[tag h1] Hey There .h2");Ð
MT("idShortcut",Ð    "[attribute&def #test] Hey There");Ð
MT("tagWithIdShortcuts",Ð    "[tag h1][attribute&def #test] Hey There");Ð
MT("classShortcut",Ð    "[attribute&qualifier .hello] Hey There");Ð
MT("tagWithIdAndClassShortcuts",Ð    "[tag h1][attribute&def #test]
[attribute&qualifier .hello] Hey There");Ð MT("docType",Ð    "[keyword
doctype] xml");Ð MT("comment",Ð    "[comment / Hello WORLD]");Ð
MT("notComment",Ð    "[tag h1] This is not a / comment ");Ð MT("attributes",Ð
     "[tag a]([attribute title]=[string \"test\"]) [attribute href]=[string
\"link\"]}");Ð MT("multiLineAttributes",Ð    "[tag a]([attribute
title]=[string \"test\"]",Ð    "  ) [attribute href]=[string \"link\"]}");Ð
MT("htmlCode",Ð    "[tag&bracket <][tag h1][tag&bracket >]Title[tag&bracket
</][tag h1][tag&bracket >]");Ð MT("rubyBlock",Ð    "[operator&special =]
[variable-2 @item]");Ð MT("selectorRubyBlock",Ð    "[tag a]
[attribute&qualifier .test][operator&special =] [variable-2 @item]");Ð
MT("nestedRubyBlock",Ð     "[tag a]",Ð     "  [operator&special =][variable
puts] [string \"test\"]");Ð MT("multilinePlaintext",Ð     "[tag p]",Ð     "
| Hello,",Ð     "    World");Ð MT("multilineRuby",Ð     "[tag p]",Ð
"  [comment /# this is a comment]",Ð     "     [comment and this is a comment
too]",Ð     "  | Date/Time",Ð     "  [operator&special -] [variable now]
[operator =] [tag DateTime][operator .][property now]",Ð     "  [tag strong]
[operator&special =] [variable now]",Ð     "  [operator&special -] [keyword
if] [variable now] [operator >] [tag DateTime][operator .][property parse]
([string \"December 31, 2006\"])",Ð     "     [operator&special =][string
\"Happy\"]",Ð     "     [operator&special =][string \"Belated\"]",Ð
"     [operator&special =][string \"Birthday\"]");Ð MT("multilineComment",Ð
      "[comment /]",Ð     "  [comment Multiline]",Ð     "  [comment
Comment]");Ð MT("hamlAfterRubyTag",Ð   "[attribute&qualifier .block]",Ð
"  [tag strong][operator&special =] [variable now]",Ð
"  [attribute&qualifier .test]",Ð   "     [operator&special =][variable now]",Ð
    "  [attribute&qualifier .right]");Ð MT("stretchedRuby",Ð
"[operator&special =] [variable puts] [string \"Hello\"],",Ð    "   [string
\"World\"]");Ð MT("interpolationInHashAttribute",Ð    "[tag div]{[attribute
id] = [string \"]#{[variable test]}[string _]#{[variable ting]}[string \"]}
test");Ð MT("interpolationInHTMLAttribute",Ð    "[tag div]([attribute
title]=[string \"]#{[variable test]}[string _]#{[variable ting]()}[string
\"]) Test");Ð })();Ð
```

public\assets\js\plugins\codemirror\mode\smalltalk\smalltalk.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode('smalltalk', function(config) {Ð var specialChars = /[+
\-\/\\*~<>=@%|&?!.,:;^]/;Ð var keywords = /true|false|nil|self|super|
thisContext/;Ð var Context = function(tokenizer, parent) {Ð   this.next =
tokenizer;Ð   this.parent = parent;Ð };Ð var Token = function(name, context,
eos) {Ð   this.name = name;Ð   this.context = context;Ð   this.eos = eos;Ð };Ð
  var State = function() {Ð   this.context = new Context(next, null);Ð
this.expectVariable = true;Ð   this.indentation = 0;Ð
this.userIndentationDelta = 0;Ð };Ð State.prototype.userIndent =
function(indentation) {Ð   this.userIndentationDelta = indentation > 0 ?
(indentation / config.indentUnit - this.indentation) : 0;Ð };Ð var next =
function(stream, context, state) {Ð   var token = new Token(null, context,
false);Ð   var aChar = stream.next();Ð   if (aChar === '"') {Ð     token =
nextComment(stream, new Context(nextComment, context));Ð   } else if (aChar
=== '\'') {Ð     token = nextString(stream, new Context(nextString, context));Ð
    } else if (aChar === '#') {Ð     if (stream.peek() === '\'') {Ð
stream.next();Ð       token = nextSymbol(stream, new Context(nextSymbol,
context));Ð     } else {Ð       if (stream.eatWhile(/[^\s.{}\[\]()]/))Ð
          token.name = 'string-2';Ð       elseÐ         token.name = 'meta';Ð
      }Ð   } else if (aChar === '$') {Ð     if (stream.next() === '<') {Ð
        stream.eatWhile(/[^\s>]/);Ð       stream.next();Ð     }Ð
token.name = 'string-2';Ð   } else if (aChar === '|' && state.expectVariable)
{Ð     token.context = new Context(nextTemporaries, context);Ð   } else if (/
[\[\]{}()]/.test(aChar)) {Ð     token.name = 'bracket';Ð     token.eos = /
[\[{(]/.test(aChar);Ð     if (aChar === '[') {Ð       state.indentation++;Ð
      } else if (aChar === ']') {Ð       state.indentation = Math.max(0,
state.indentation - 1);Ð     }Ð   } else if (specialChars.test(aChar)) {Ð
stream.eatWhile(specialChars);Ð     token.name = 'operator';Ð     token.eos =
aChar !== ';'; // ; cascaded message expression Ð   } else if (/
\d/.test(aChar)) {Ð     stream.eatWhile(/[\w\d]/);Ð     token.name = 'number';Ð
    } else if (/[\w_]/.test(aChar)) {Ð     stream.eatWhile(/[\w\d_]/);Ð
token.name = state.expectVariable ? (keywords.test(stream.current()) ?
'keyword' : 'variable') : null;Ð   } else {Ð     token.eos =
state.expectVariable;Ð   }Ð   return token;Ð };Ð var nextComment =
function(stream, context) {Ð   stream.eatWhile(/[^"]/);Ð   return new
Token('comment', stream.eat('"') ? context.parent : context, true);Ð };Ð var
nextString = function(stream, context) {Ð   stream.eatWhile(/[^']/);Ð
return new Token('string', stream.eat('\'') ? context.parent : context,
false);Ð };Ð var nextSymbol = function(stream, context) {Ð   stream.eatWhile(/
[^']/);Ð   return new Token('string-2', stream.eat('\'') ? context.parent :
context, false);Ð };Ð var nextTemporaries = function(stream, context) {Ð
var token = new Token(null, context, false);Ð   var aChar = stream.next();Ð
if (aChar === '|') {Ð     token.context = context.parent;Ð     token.eos =
true;Ð   } else {Ð     stream.eatWhile(/[^|]/);Ð     token.name = 'variable';Ð
    }Ð   return token;Ð };Ð return {Ð   startState: function() {Ð     return
new State;Ð   },Ð   token: function(stream, state) {Ð
state.userIndent(stream.indentation());Ð     if (stream.eatSpace()) {Ð
return null;Ð     }Ð     var token = state.context.next(stream,
state.context, state);Ð     state.context = token.context;Ð
state.expectVariable = token.eos;Ð     return token.name;Ð   },Ð   blankLine:
function(state) {Ð     state.userIndent(0);Ð   },Ð   indent: function(state,
textAfter) {Ð     var i = state.context.next === next && textAfter &&
textAfter.charAt(0) === ']' ? -1 : state.userIndentationDelta;Ð     return
(state.indentation + i) * config.indentUnit;Ð
```

```
                                                    },Ð   electricChars: ']'Ð };Ð
});ÐodeMirror.defineMIME('text/x-stsrc', {name: 'smalltalk'});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\smarty\smarty.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/**Ð* Smarty 2 and 3 mode.Ð
*/Ð(function(mod) {Ð if (typeof exports == "object" && typeof module ==
"object") // CommonJS Ð   mod(require("../../lib/codemirror"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror"], mod);Ð else // Plain browser env Ð   mod(CodeMirror);Ð})
(function(CodeMirror) {Ð "use strict";Ð CodeMirror.defineMode("smarty",
function(config) {Ð "use strict";Ð // our default settings; check to see if
they're overriddenÐ var settings = {Ð   rightDelimiter: '}',Ð
leftDelimiter: '{',Ð   smartyVersion: 2 // for backward compatibilityÐ };Ð if
(config.hasOwnProperty("leftDelimiter")) {Ð   settings.leftDelimiter =
config.leftDelimiter;Ð }Ð if (config.hasOwnProperty("rightDelimiter")) {Ð
settings.rightDelimiter = config.rightDelimiter;Ð }Ð if
(config.hasOwnProperty("smartyVersion") && config.smartyVersion === 3) {Ð
settings.smartyVersion = 3;Ð }Ð var keyFunctions = ["debug", "extends",
"function", "include", "literal"];Ð var last;Ð var regs = {Ð
operatorChars: /[+\-*&%=<>!?]/,Ð   validIdentifier: /[a-zA-Z0-9_]/,Ð
stringChar: /['"]/Ð };Ð var helpers = {Ð   cont: function(style, lastType) {Ð
      last = lastType;Ð     return style;Ð   },Ð   chain: function(stream,
state, parser) {Ð     state.tokenize = parser;Ð     return parser(stream,
state);Ð   }Ð };Ð // our various parsersÐ var parsers = {Ð   // the main
tokenizerÐ   tokenizer: function(stream, state) {Ð     if
(stream.match(settings.leftDelimiter, true)) {Ð       if (stream.eat("*")) {Ð
          return helpers.chain(stream, state, parsers.inBlock("comment", "*"
+ settings.rightDelimiter));Ð       } else {Ð         // Smarty 3 allows
{ and } surrounded by whitespace to NOT slip into Smarty modeÐ
state.depth++;Ð         var isEol = stream.eol();Ð         var
isFollowedByWhitespace = /\s/.test(stream.peek());Ð         if
(settings.smartyVersion === 3 && settings.leftDelimiter === "{" && (isEol ||
isFollowedByWhitespace)) {Ð           state.depth--;Ð           return null;Ð
          } else {Ð           state.tokenize = parsers.smarty;Ð
last = "startTag";Ð           return "tag";Ð         }Ð       }Ð     } else {Ð
        stream.next();Ð       return null;Ð     }Ð   },Ð   // parsing Smarty
contentÐ   smarty: function(stream, state) {Ð     if
(stream.match(settings.rightDelimiter, true)) {Ð       if
(settings.smartyVersion === 3) {Ð         state.depth--;Ð         if
(state.depth <= 0) {Ð           state.tokenize = parsers.tokenizer;Ð         }Ð
        } else {Ð         state.tokenize = parsers.tokenizer;Ð       }Ð
return helpers.cont("tag", null);Ð     }Ð     if
(stream.match(settings.leftDelimiter, true)) {Ð       state.depth++;Ð
return helpers.cont("tag", "startTag");Ð     }Ð     var ch = stream.next();Ð
      if (ch == "$") {Ð       stream.eatWhile(regs.validIdentifier);Ð
return helpers.cont("variable-2", "variable");Ð     } else if (ch == "|") {Ð
        return helpers.cont("operator", "pipe");Ð     } else if (ch == ".") {Ð
        return helpers.cont("operator", "property");Ð     } else if
(regs.stringChar.test(ch)) {Ð       state.tokenize = parsers.inAttribute(ch);Ð
        return helpers.cont("string", "string");Ð     } else if
(regs.operatorChars.test(ch)) {Ð       stream.eatWhile(regs.operatorChars);Ð
        return helpers.cont("operator", "operator");Ð     } else if (ch ==
"[" || ch == "]") {Ð       return helpers.cont("bracket", "bracket");Ð     }
else if (ch == "(" || ch == ")") {Ð       return helpers.cont("bracket",
"operator");Ð     } else if (/\d/.test(ch)) {Ð       stream.eatWhile(/\d/);Ð
        return helpers.cont("number", "number");Ð     } else {Ð       if
(state.last == "variable") {Ð         if (ch == "@") {Ð
stream.eatWhile(regs.validIdentifier);Ð           return
helpers.cont("property", "property");Ð         } else if (ch == "|") {Ð
            stream.eatWhile(regs.validIdentifier);Ð           return
helpers.cont("qualifier", "modifier");Ð         }Ð       } else if
(state.last == "pipe") {Ð
```

```
                                    stream.eatWhile(regs.validIdentifier);Ð
          return helpers.cont("qualifier", "modifier");Ð       } else if
(state.last == "whitespace") {Ð         stream.eatWhile(regs.validIdentifier);Ð
          return helpers.cont("attribute", "modifier");Ð       } if
(state.last == "property") {Ð         stream.eatWhile(regs.validIdentifier);Ð
          return helpers.cont("property", null);Ð       } else if (/
\s/.test(ch)) {Ð         last = "whitespace";Ð         return null;Ð       }Ð
        var str = "";Ð       if (ch != "/") {Ð         str += ch;Ð       }Ð
        var c = null;Ð       while (c = stream.eat(regs.validIdentifier)) {Ð
          str += c;Ð       }Ð       for (var i=0, j=keyFunctions.length; i<j;
i++) {Ð         if (keyFunctions[i] == str) {Ð           return
helpers.cont("keyword", "keyword");Ð         }Ð       }Ð       if (/
\s/.test(ch)) {Ð         return null;Ð       }Ð       return
helpers.cont("tag", "tag");Ð     }Ð   },Ð   inAttribute: function(quote) {Ð
      return function(stream, state) {Ð       var prevChar = null;Ð       var
currChar = null;Ð       while (!stream.eol()) {Ð         currChar =
stream.peek();Ð         if (stream.next() == quote && prevChar !== '\\') {Ð
            state.tokenize = parsers.smarty;Ð           break;Ð         }Ð
          prevChar = currChar;Ð       }Ð       return "string";Ð     };Ð   },Ð
    inBlock: function(style, terminator) {Ð     return function(stream,
state) {Ð       while (!stream.eol()) {Ð         if
(stream.match(terminator)) {Ð           state.tokenize = parsers.tokenizer;Ð
            break;Ð         }Ð         stream.next();Ð       }Ð       return
style;Ð     };Ð   }Ð };Ð // the public API for CodeMirrorÐ return {Ð
startState: function() {Ð     return {Ð       tokenize: parsers.tokenizer,Ð
        mode: "smarty",Ð       last: null,Ð       depth: 0Ð     };Ð   },Ð
token: function(stream, state) {Ð     var style = state.tokenize(stream,
state);Ð     state.last = last;Ð     return style;Ð   },Ð   electricChars: ""Ð
  };Ð});ÐodeMirror.defineMIME("text/x-smarty", "smarty");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\smartymixed\smartymixed.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/**Ð @file smartymixed.js Ð
@brief Smarty Mixed Codemirror mode (Smarty + Mixed HTML) Ð @author Ruslan
Osmanov <rrosmanov at gmail dot com> Ð @version 3.0 Ð @date 05.07.2013 Ð/Ð/
Warning: Don't base other modes on this one. This here is a Ð// terrible way to
write a mixed mode. Ð(function(mod) {Ð if (typeof exports == "object" && typeof
module == "object") // CommonJS Ð   mod(require("../../lib/codemirror"),
require("../htmlmixed/htmlmixed"), require("../smarty/smarty"));Ð else if
(typeof define == "function" && define.amd) // AMD Ð   define(["../../lib/
codemirror", "../htmlmixed/htmlmixed", "../smarty/smarty"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("smartymixed", function(config) {Ð var htmlMixedMode =
CodeMirror.getMode(config, "htmlmixed");Ð var smartyMode =
CodeMirror.getMode(config, "smarty");Ð var settings = {Ð   rightDelimiter:
'}',Ð   leftDelimiter: '{'Ð };Ð if (config.hasOwnProperty("leftDelimiter")) {Ð
    settings.leftDelimiter = config.leftDelimiter;Ð }Ð if
(config.hasOwnProperty("rightDelimiter")) {Ð   settings.rightDelimiter =
config.rightDelimiter;Ð }Ð function reEsc(str) { return str.replace(/[^\s\w]/
g, "\\$&"); }Ð var reLeft = reEsc(settings.leftDelimiter), reRight =
reEsc(settings.rightDelimiter);Ð var regs = {Ð   smartyComment: new
RegExp("^" + reRight + "\\*"),Ð   literalOpen: new RegExp(reLeft + "literal"
+ reRight),Ð   literalClose: new RegExp(reLeft + "\/literal" + reRight),Ð
hasLeftDelimeter: new RegExp(".*" + reLeft),Ð   htmlHasLeftDelimeter: new
RegExp("[^<>]*" + reLeft)Ð };Ð var helpers = {Ð   chain: function(stream,
state, parser) {Ð     state.tokenize = parser;Ð     return parser(stream,
state);Ð   },Ð   cleanChain: function(stream, state, parser) {Ð
state.tokenize = null;Ð     state.localState = null;Ð     state.localMode =
null;Ð     return (typeof parser == "string") ? (parser ? parser : null) :
parser(stream, state);Ð   },Ð   maybeBackup: function(stream, pat, style) {Ð
      var cur = stream.current();Ð     var close = cur.search(pat),Ð     m;Ð
      if (close > - 1) stream.backUp(cur.length - close);Ð     else if (m =
cur.match(/<\/?$/)) {Ð       stream.backUp(cur.length);Ð       if (!
stream.match(pat, false)) stream.match(cur[0]);Ð     }Ð     return style;Ð   }Ð
  };Ð var parsers = {Ð   html: function(stream, state) {Ð     var htmlTagName
= state.htmlMixedState.htmlState.context &&
state.htmlMixedState.htmlState.context.tagNameÐ       ?
state.htmlMixedState.htmlState.context.tagNameÐ       : null;Ð     if (!
state.inLiteral && stream.match(regs.htmlHasLeftDelimeter, false) &&
htmlTagName === null) {Ð       state.tokenize = parsers.smarty;Ð
state.localMode = smartyMode;Ð       state.localState =
smartyMode.startState(htmlMixedMode.indent(state.htmlMixedState, ""));Ð
return helpers.maybeBackup(stream, settings.leftDelimiter,
smartyMode.token(stream, state.localState));Ð     } else if (!state.inLiteral
&& stream.match(settings.leftDelimiter, false)) {Ð       state.tokenize =
parsers.smarty;Ð       state.localMode = smartyMode;Ð       state.localState
= smartyMode.startState(htmlMixedMode.indent(state.htmlMixedState, ""));Ð
        return helpers.maybeBackup(stream, settings.leftDelimiter,
smartyMode.token(stream, state.localState));Ð     }Ð     return
htmlMixedMode.token(stream, state.htmlMixedState);Ð   },Ð   smarty:
function(stream, state) {Ð     if (stream.match(settings.leftDelimiter,
false)) {Ð       if (stream.match(regs.smartyComment, false)) {Ð
return helpers.chain(stream, state, parsers.inBlock("comment", "*" +
settings.rightDelimiter));Ð       }Ð     } else if
(stream.match(settings.rightDelimiter, false)) {Ð
stream.eat(settings.rightDelimiter);Ð       state.tokenize = parsers.html;Ð
        state.localMode = htmlMixedMode;Ð       state.localState =
state.htmlMixedState;Ð
```

```
                              return "tag";Ð     }Ð     return
helpers.maybeBackup(stream, settings.rightDelimiter, smartyMode.token(stream,
state.localState));Ð   },Ð   inBlock: function(style, terminator) {Ð
return function(stream, state) {Ð       while (!stream.eol()) {Ð         if
(stream.match(terminator)) {Ð           helpers.cleanChain(stream, state, "");Ð
            break;Ð         }Ð         stream.next();Ð       }Ð       return
style;Ð     };Ð   }Ð };Ð return {Ð   startState: function() {Ð     var state
= htmlMixedMode.startState();Ð     return {Ð       token: parsers.html,Ð
        localMode: null,Ð       localState: null,Ð       htmlMixedState:
state,Ð       tokenize: null,Ð       inLiteral: falseÐ     };Ð   },Ð
copyState: function(state) {Ð     var local = null, tok = (state.tokenize ||
state.token);Ð     if (state.localState) {Ð       local =
CodeMirror.copyState((tok != parsers.html ? smartyMode : htmlMixedMode),
state.localState);Ð     }Ð     return {Ð       token: state.token,Ð
tokenize: state.tokenize,Ð       localMode: state.localMode,Ð
localState: local,Ð       htmlMixedState: CodeMirror.copyState(htmlMixedMode,
state.htmlMixedState),Ð       inLiteral: state.inLiteralÐ     };Ð   },Ð
token: function(stream, state) {Ð     if
(stream.match(settings.leftDelimiter, false)) {Ð       if (!state.inLiteral
&& stream.match(regs.literalOpen, true)) {Ð         state.inLiteral = true;Ð
          return "keyword";Ð       } else if (state.inLiteral &&
stream.match(regs.literalClose, true)) {Ð         state.inLiteral = false;Ð
          return "keyword";Ð       }Ð     }Ð     if (state.inLiteral &&
state.localState != state.htmlMixedState) {Ð       state.tokenize =
parsers.html;Ð       state.localMode = htmlMixedMode;Ð       state.localState
= state.htmlMixedState;Ð     }Ð     var style = (state.tokenize ||
state.token)(stream, state);Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.localMode == smartyModeÐ
|| (state.inLiteral && !state.localMode)Ð        ||
regs.hasLeftDelimeter.test(textAfter)) {Ð       return CodeMirror.Pass;Ð     }Ð
      return htmlMixedMode.indent(state.htmlMixedState, textAfter);Ð   },Ð
innerMode: function(state) {Ð     return {Ð       state: state.localState ||
state.htmlMixedState,Ð       mode: state.localMode || htmlMixedModeÐ     };Ð
    }Ð };Ð, "htmlmixed", "smarty");ÐodeMirror.defineMIME("text/x-smarty",
"smartymixed");Ð/ vim: et ts=2 sts=2 sw=2Ð});Ð
```

public\assets\js\plugins\codemirror\mode\solr\solr.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("solr", function() {Ð "use strict";Ð var isStringChar
= /[^\s\|\!\+\-\*\?\~\^\&\:\(\)\[\]\{\}\^\"\\]/;Ð var isOperatorChar = /[\|\!\
+\-\*\?\~\^\&]/;Ð var isOperatorString = /^(OR|AND|NOT|TO)$/i;Ð function
isNumber(word) {Ð   return parseFloat(word, 10).toString() === word;Ð }Ð
function tokenString(quote) {Ð   return function(stream, state) {Ð     var
escaped = false, next;Ð     while ((next = stream.next()) != null) {Ð
if (next == quote && !escaped) break;Ð       escaped = !escaped && next == "\
\";Ð     }Ð     if (!escaped) state.tokenize = tokenBase;Ð     return
"string";Ð   };Ð }Ð function tokenOperator(operator) {Ð   return
function(stream, state) {Ð     var style = "operator";Ð     if (operator ==
"+")Ð       style += " positive";Ð     else if (operator == "-")Ð       style
+= " negative";Ð     else if (operator == "|")Ð       stream.eat(/\|/);Ð
else if (operator == "&")Ð       stream.eat(/\&/);Ð     else if (operator ==
"^")Ð       style += " boost";Ð     state.tokenize = tokenBase;Ð     return
style;Ð   };Ð }Ð function tokenWord(ch) {Ð   return function(stream, state) {Ð
      var word = ch;Ð     while ((ch = stream.peek()) &&
ch.match(isStringChar) != null) {Ð       word += stream.next();Ð     }Ð
state.tokenize = tokenBase;Ð     if (isOperatorString.test(word))Ð
return "operator";Ð     else if (isNumber(word))Ð       return "number";Ð
else if (stream.peek() == ":")Ð       return "field";Ð     elseÐ       return
"string";Ð   };Ð }Ð function tokenBase(stream, state) {Ð   var ch =
stream.next();Ð   if (ch == '"')Ð     state.tokenize = tokenString(ch);Ð
else if (isOperatorChar.test(ch))Ð     state.tokenize = tokenOperator(ch);Ð
else if (isStringChar.test(ch))Ð     state.tokenize = tokenWord(ch);Ð
return (state.tokenize != tokenBase) ? state.tokenize(stream, state) : null;Ð
  }Ð return {Ð   startState: function() {Ð     return {Ð       tokenize:
tokenBase Ð     };Ð   },Ð   token: function(stream, state) {Ð     if
(stream.eatSpace()) return null;Ð     return state.tokenize(stream, state);Ð
    }Ð };Ð});Ð odeMirror.defineMIME("text/x-solr", "solr");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\sparql\sparql.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("sparql", function(config) {Ð var indentUnit =
config.indentUnit;Ð var curPunc;Ð function wordRegexp(words) {Ð   return new
RegExp("^(?:" + words.join("|") + ")$", "i");Ð }Ð var ops =
wordRegexp(["str", "lang", "langmatches", "datatype", "bound", "sameterm",
"isiri", "isuri",Ð                        "isblank", "isliteral", "a"]);Ð var
keywords = wordRegexp(["base", "prefix", "select", "distinct", "reduced",
"construct", "describe",Ð                              "ask", "from", "named",
"where", "order", "limit", "offset", "filter", "optional",Ð
                              "graph", "by", "asc", "desc", "as", "having",
"undef", "values", "group",Ð                              "minus", "in", "not",
"service", "silent", "using", "insert", "delete", "union",Ð
                              "data", "copy", "to", "move", "add", "create",
"drop", "clear", "load"]);Ð var operatorChars = /[*+\-<>=&|]/;Ð function
tokenBase(stream, state) {Ð   var ch = stream.next();Ð   curPunc = null;Ð
if (ch == "$" || ch == "?") {Ð     stream.match(/^[\w\d]*/);Ð     return
"variable-2";Ð   }Ð   else if (ch == "<" && !stream.match(/^[\s\u00a0=]/,
false)) {Ð     stream.match(/^[^\s\u00a0>]*>?/);Ð     return "atom";Ð   }Ð
else if (ch == "\"" || ch == "'") {Ð     state.tokenize = tokenLiteral(ch);Ð
      return state.tokenize(stream, state);Ð   }Ð   else if (/[{}\(\),\.;
\[\]]/.test(ch)) {Ð     curPunc = ch;Ð     return null;Ð   }Ð   else if (ch
== "#") {Ð     stream.skipToEnd();Ð     return "comment";Ð   }Ð   else if
(operatorChars.test(ch)) {Ð     stream.eatWhile(operatorChars);Ð     return
null;Ð   }Ð   else if (ch == ":") {Ð     stream.eatWhile(/[\w\d\._\-]/);Ð
return "atom";Ð   }Ð   else {Ð     stream.eatWhile(/[_\w\d]/);Ð     if
(stream.eat(":")) {Ð       stream.eatWhile(/[\w\d_\-]/);Ð       return "atom";Ð
      }Ð     var word = stream.current();Ð     if (ops.test(word))Ð
return null;Ð     else if (keywords.test(word))Ð       return "keyword";Ð
elseÐ       return "variable";Ð   }Ð }Ð function tokenLiteral(quote) {Ð
return function(stream, state) {Ð     var escaped = false, ch;Ð     while
((ch = stream.next()) != null) {Ð       if (ch == quote && !escaped) {Ð
          state.tokenize = tokenBase;Ð         break;Ð       }Ð       escaped
= !escaped && ch == "\\";Ð     }Ð     return "string";Ð   };Ð }Ð function
pushContext(state, type, col) {Ð   state.context = {prev: state.context,
indent: state.indent, col: col, type: type};Ð }Ð function popContext(state) {Ð
    state.indent = state.context.indent;Ð   state.context =
state.context.prev;Ð }Ð return {Ð   startState: function() {Ð     return
{tokenize: tokenBase,Ð             context: null,Ð             indent: 0,Ð
              col: 0};Ð   },Ð   token: function(stream, state) {Ð     if
(stream.sol()) {Ð       if (state.context && state.context.align == null)
state.context.align = false;Ð       state.indent = stream.indentation();Ð
      }Ð     if (stream.eatSpace()) return null;Ð     var style =
state.tokenize(stream, state);Ð     if (style != "comment" && state.context
&& state.context.align == null && state.context.type != "pattern") {Ð
state.context.align = true;Ð     }Ð     if (curPunc == "(")
pushContext(state, ")", stream.column());Ð     else if (curPunc == "[")
pushContext(state, "]", stream.column());Ð     else if (curPunc == "{")
pushContext(state, "}", stream.column());Ð     else if (/
[\]\}\)]/.test(curPunc)) {Ð       while (state.context && state.context.type
== "pattern") popContext(state);Ð       if (state.context && curPunc ==
state.context.type) popContext(state);Ð     }Ð     else if (curPunc == "." &&
state.context && state.context.type == "pattern") popContext(state);Ð
else if (/atom|string|variable/.test(style) && state.context) {Ð       if (/
[\}\]]/.test(state.context.type))Ð
```

```
                                                pushContext(state, "pattern",
stream.column());Ð       else if (state.context.type == "pattern" && !
state.context.align) {Ð         state.context.align = true;Ð
state.context.col = stream.column();Ð       }Ð     }Ð     return style;Ð   },Ð
    indent: function(state, textAfter) {Ð     var firstChar = textAfter &&
textAfter.charAt(0);Ð     var context = state.context;Ð     if (/
[\]\}]/.test(firstChar))Ð       while (context && context.type == "pattern")
context = context.prev;Ð     var closing = context && firstChar ==
context.type;Ð     if (!context)Ð       return 0;Ð     else if (context.type
== "pattern")Ð       return context.col;Ð     else if (context.align)Ð
return context.col + (closing ? 0 : 1);Ð     elseÐ       return
context.indent + (closing ? 0 : indentUnit);Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("application/x-sparql-query", "sparql");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\stex\stex.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others/ Distributed
under an MIT license: http://codemirror.net/LICENSE/* Author: Constantin
Jucovschi (c.jucovschi@jacobs-university.de)* Licence: MIT*/(function(mod) {
  if (typeof exports == "object" && typeof module == "object") // CommonJS
mod(require("../../lib/codemirror"));  else if (typeof define == "function"
&& define.amd) // AMD   define(["../../lib/codemirror"], mod);  else //
Plain browser env   mod(CodeMirror);})(function(CodeMirror) {  "use strict";
CodeMirror.defineMode("stex", function() {   "use strict";   function
pushCommand(state, command) {       state.cmdState.push(command);   }
function peekCommand(state) {       if (state.cmdState.length > 0) {
            return state.cmdState[state.cmdState.length - 1];       } else {
            return null;       }   }   function popCommand(state) {
var plug = state.cmdState.pop();       if (plug) {
plug.closeBracket();       }   }   // returns the non-default plugin
closest to the end of the list   function getMostPowerful(state) {
var context = state.cmdState;       for (var i = context.length - 1; i >= 0;
i--) {           var plug = context[i];           if (plug.name ==
"DEFAULT") {               continue;           }           return plug;
        }       return { styleIdentifier: function() { return null; } };   }
    function addPluginPattern(pluginName, cmdStyle, styles) {       return
function () {           this.name = pluginName;           this.bracketNo =
0;           this.style = cmdStyle;           this.styles = styles;
            this.argument = null;   // \begin and \end have arguments that
follow. These are stored in the plugin           this.styleIdentifier =
function() {               return this.styles[this.bracketNo - 1] || null;
            };           this.openBracket = function() {
this.bracketNo++;               return "bracket";           };
this.closeBracket = function() {};       };   }   var plugins = {};
plugins["importmodule"] = addPluginPattern("importmodule", "tag", ["string",
"builtin"]);   plugins["documentclass"] = addPluginPattern("documentclass",
"tag", [""], "atom"]);   plugins["usepackage"] =
addPluginPattern("usepackage", "tag", ["atom"]);   plugins["begin"] =
addPluginPattern("begin", "tag", ["atom"]);   plugins["end"] =
addPluginPattern("end", "tag", ["atom"]);   plugins["DEFAULT"] = function ()
{       this.name = "DEFAULT";       this.style = "tag";
this.styleIdentifier = this.openBracket = this.closeBracket = function() {};
    };   function setState(state, f) {       state.f = f;   }   // called
when in a normal (no environment) context   function normal(source, state) {
        var plug;       // Do we look like '\command' ?  If so, attempt to
apply the plugin 'command'       if (source.match(/^\\[a-zA-Z@]+/)) {
            var cmdName = source.current().slice(1);           plug =
plugins[cmdName] || plugins["DEFAULT"];           plug = new plug();
            pushCommand(state, plug);           setState(state, beginParams);
            return plug.style;       }       // escape characters       if
(source.match(/^\\[$&%#{}_]/)) {         return "tag";       }       //
white space control characters       if (source.match(/^\\[,;!\/\\]/)) {
          return "tag";       }       // find if we're starting various
math modes       if (source.match("\\[")) {           setState(state,
function(source, state){ return inMathMode(source, state, "\\]"); });
            return "keyword";       }       if (source.match("$$")) {
            setState(state, function(source, state){ return
inMathMode(source, state, "$$"); });           return "keyword";       }
        if (source.match("$")) {           setState(state, function(source,
state){ return inMathMode(source, state, "$"); });           return
"keyword";       }       var ch = source.next();       if (ch == "%") {
            // special case: % at end of its own line; stay in same state
            if (!source.eol()) {             setState(state, inCComment);
            }           return "comment";       }       else if (ch == '}'
|| ch == ']') {
```

```
                            plug = peekCommand(state);Ð           if (plug) {Ð
                plug.closeBracket(ch);Ð               setState(state,
beginParams);Ð           } else {Ð               return "error";Ð           }Ð
            return "bracket";Ð       } else if (ch == '{' || ch == '[') {Ð
            plug = plugins["DEFAULT"];Ð           plug = new plug();Ð
            pushCommand(state, plug);Ð           return "bracket";Ð       }Ð
        else if (/\d/.test(ch)) {Ð           source.eatWhile(/[\w.%]/);Ð
            return "atom";Ð       }Ð       else {Ð           source.eatWhile(/
[\w\-_]/);Ð           plug = getMostPowerful(state);Ð           if (plug.name
== 'begin') {Ð               plug.argument = source.current();Ð           }Ð
            return plug.styleIdentifier();Ð       }Ð   }Ð   function
inCComment(source, state) {Ð       source.skipToEnd();Ð       setState(state,
normal);Ð       return "comment";Ð   }Ð   function inMathMode(source, state,
endModeSeq) {Ð       if (source.eatSpace()) {Ð           return null;Ð       }Ð
        if (source.match(endModeSeq)) {Ð           setState(state, normal);Ð
            return "keyword";Ð       }Ð       if (source.match(/^\\[a-zA-
Z@]+/)) {Ð           return "tag";Ð       }Ð       if (source.match(/^[a-zA-
Z]+/)) {Ð           return "variable-2";Ð       }Ð       // escape charactersÐ
        if (source.match(/^\\[$&%#{}_]/)) {Ð         return "tag";Ð       }Ð
        // white space control charactersÐ       if (source.match(/^\\[,;!
\/]/)) {Ð         return "tag";Ð       }Ð       // special math-mode
charactersÐ       if (source.match(/^[\^_&]/)) {Ð         return "tag";Ð
        }Ð       // non-special charactersÐ       if (source.match(/^[+\-<>|=,
\/@!*:;'"`~#?]/)) {Ð           return null;Ð       }Ð       if (source.match(/
^(\d+\.\d*|\d*\.\d+|\d+)/)) {Ð         return "number";Ð       }Ð       var
ch = source.next();Ð       if (ch == "{" || ch == "}" || ch == "[" || ch ==
"]" || ch == "(" || ch == ")") {Ð           return "bracket";Ð       }Ð
        // eat comments here, because inCComment returns us to normal state!Ð
        if (ch == "%") {Ð           if (!source.eol()) {Ð
source.skipToEnd();Ð           }Ð           return "comment";Ð       }Ð
return "error";Ð   }Ð   function beginParams(source, state) {Ð       var ch =
source.peek(), lastPlug;Ð       if (ch == '{' || ch == '[') {Ð
lastPlug = peekCommand(state);Ð           lastPlug.openBracket(ch);Ð
            source.eat(ch);Ð           setState(state, normal);Ð
return "bracket";Ð       }Ð       if (/[ \t\r]/.test(ch)) {Ð
source.eat(ch);Ð           return null;Ð       }Ð       setState(state,
normal);Ð       popCommand(state);Ð       return normal(source, state);Ð   }Ð
    return {Ð       startState: function() {Ð           return {Ð
                cmdState: [],Ð               f: normalÐ           };Ð       },Ð
        copyState: function(s) {Ð           return {Ð               cmdState:
s.cmdState.slice(),Ð               f: s.fÐ           };Ð       },Ð
token: function(stream, state) {Ð           return state.f(stream, state);Ð
        },Ð       lineComment: "%"Ð   };Ð});ÐodeMirror.defineMIME("text/x-
stex", "stex");ÐodeMirror.defineMIME("text/x-latex", "stex");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\stex\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({tabSize: 4}, "stex");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT("word",Ð    "foo");Ð MT("twoWords",Ð    "foo bar");Ð MT("beginEndDocument",Ð
     "[tag \\begin][bracket {][atom document][bracket }]",Ð    "[tag \\end]
[bracket {][atom document][bracket }]");Ð MT("beginEndEquation",Ð    "[tag \
\begin][bracket {][atom equation][bracket }]",Ð    "  E=mc^2",Ð    "[tag \
\end][bracket {][atom equation][bracket }]");Ð MT("beginModule",Ð    "[tag \
\begin][bracket {][atom module][bracket }[[]]]");Ð MT("beginModuleId",Ð
"[tag \\begin][bracket {][atom module][bracket }[[]id=bbt-size[bracket ]]]");Ð
  MT("importModule",Ð    "[tag \\importmodule][bracket [[][string b-b-t]
[bracket ]]{][builtin b-b-t][bracket }]");Ð MT("importModulePath",Ð    "[tag \
\importmodule][bracket [[][tag \\KWARCslides][bracket {][string dmath/en/
cardinality][bracket }]]{][builtin card][bracket }]");Ð MT("psForPDF",Ð
"[tag \\PSforPDF][bracket [[][atom 1][bracket ]]{]#1[bracket }]");Ð
MT("comment",Ð    "[comment % foo]");Ð MT("tagComment",Ð    "[tag \\item]
[comment % bar]");Ð MT("commentTag",Ð    " [comment % \\item]");Ð
MT("commentLineBreak",Ð    "[comment %]",Ð    "foo");Ð MT("tagErrorCurly",Ð
     "[tag \\begin][error }][bracket {]");Ð MT("tagErrorSquare",Ð    "[tag \
\item][error ]]][bracket {]");Ð MT("commentCurly",Ð    "[comment % }]");Ð
MT("tagHash",Ð    "the [tag \\#] key");Ð MT("tagNumber",Ð    "a [tag \\$]
[atom 5] stetson");Ð MT("tagPercent",Ð    "[atom 100][tag \\%] beef");Ð
MT("tagAmpersand",Ð    "L [tag \\&] N");Ð MT("tagUnderscore",Ð    "foo[tag \
\_]bar");Ð MT("tagBracketOpen",Ð    "[tag \\emph][bracket {][tag \\{]
[bracket }]");Ð MT("tagBracketClose",Ð    "[tag \\emph][bracket {][tag \\}]
[bracket }]");Ð MT("tagLetterNumber",Ð    "section [tag \\S][atom 1]");Ð
MT("textTagNumber",Ð    "para [tag \\P][atom 2]");Ð MT("thinspace",Ð
"x[tag \\,]y");Ð MT("thickspace",Ð    "x[tag \\;]y");Ð MT("negativeThinspace",Ð
     "x[tag \\!]y");Ð MT("periodNotSentence",Ð    "J.\\ L.\\ is");Ð
MT("periodSentence",Ð    "X[tag \\@]. The");Ð MT("italicCorrection",Ð
"[bracket {][tag \\em] If[tag \\/][bracket }] I");Ð MT("tagBracket",Ð
"[tag \\newcommand][bracket {][tag \\pop][bracket }]");Ð
MT("inlineMathTagFollowedByNumber",Ð    "[keyword $][tag \\pi][number 2]
[keyword $]");Ð MT("inlineMath",Ð    "[keyword $][number 3][variable-2 x][tag
^][number 2.45]-[tag \\sqrt][bracket {][tag \\$\\alpha][bracket }] = [number
2][keyword $] other text");Ð MT("displayMath",Ð    "More [keyword $
$]\t[variable-2 S][tag ^][variable-2 n][tag \\sum] [variable-2 i][keyword $$]
other text");Ð MT("mathWithComment",Ð    "[keyword $][variable-2 x] [comment
% $]",Ð    "[variable-2 y][keyword $] other text");Ð MT("lineBreakArgument",Ð
    "[tag \\\\][bracket [[][atom 1cm][bracket ]]]");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\tcl\tcl.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð// tcl mode by
Ford_Lawnmower :: Based on Velocity mode by Steve O'Hara Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("tcl", function() {Ð function parseWords(str) {Ð   var
obj = {}, words = str.split(" ");Ð   for (var i = 0; i < words.length; ++i)
obj[words[i]] = true;Ð   return obj;Ð }Ð var keywords = parseWords("Tcl safe
after append array auto_execok auto_import auto_load " +Ð       "auto_mkindex
auto_mkindex_old auto_qualify auto_reset bgerror " +Ð       "binary break
catch cd close concat continue dde eof encoding error " +Ð       "eval exec
exit expr fblocked fconfigure fcopy file fileevent filename " +Ð
"filename flush for foreach format gets glob global history http if " +Ð
        "incr info interp join lappend lindex linsert list llength load
lrange " +Ð       "lreplace lsearch lset lsort memory msgcat namespace open
package parray " +Ð       "pid pkg::create pkg_mkIndex proc puts pwd
re_syntax read regex regexp " +Ð       "registry regsub rename resource
return scan seek set socket source split " +Ð       "string subst switch
tcl_endOfWord tcl_findLibrary tcl_startOfNextWord " +Ð
"tcl_wordBreakAfter tcl_startOfPreviousWord tcl_wordBreakBefore tcltest " +Ð
        "tclvars tell time trace unknown unset update uplevel upvar variable
" +Ð   "vwait");Ð   var functions = parseWords("if elseif else and not or eq
ne in ni for foreach while switch");Ð   var isOperatorChar = /[+\-*&%=<>!?^\/
\|]/;Ð   function chain(stream, state, f) {Ð     state.tokenize = f;Ð
return f(stream, state);Ð   }Ð   function tokenBase(stream, state) {Ð     var
beforeParams = state.beforeParams;Ð     state.beforeParams = false;Ð     var
ch = stream.next();Ð     if ((ch == '"' || ch == "'") && state.inParams)Ð
        return chain(stream, state, tokenString(ch));Ð     else if (/[\[\]
{}\(\),;\.]/.test(ch)) {Ð       if (ch == "(" && beforeParams) state.inParams
= true;Ð       else if (ch == ")") state.inParams = false;Ð         return
null;Ð     }Ð     else if (/\d/.test(ch)) {Ð       stream.eatWhile(/[\w\.]/);Ð
        return "number";Ð     }Ð     else if (ch == "#" && stream.eat("*")) {Ð
        return chain(stream, state, tokenComment);Ð     }Ð     else if (ch ==
"#" && stream.match(/ *\[ *\[/)) {Ð       return chain(stream, state,
tokenUnparsed);Ð     }Ð     else if (ch == "#" && stream.eat("#")) {Ð
stream.skipToEnd();Ð       return "comment";Ð     }Ð     else if (ch == '"') {Ð
        stream.skipTo(/"/);Ð       return "comment";Ð     }Ð     else if (ch
== "$") {Ð       stream.eatWhile(/[$_a-z0-9A-Z\.{:]/);Ð
stream.eatWhile(/}/);Ð       state.beforeParams = true;Ð       return
"builtin";Ð     }Ð     else if (isOperatorChar.test(ch)) {Ð
stream.eatWhile(isOperatorChar);Ð       return "comment";Ð     }Ð     else {Ð
        stream.eatWhile(/[\w\$_{}\xa1-\uffff]/);Ð       var word =
stream.current().toLowerCase();Ð       if (keywords &&
keywords.propertyIsEnumerable(word))Ð         return "keyword";Ð       if
(functions && functions.propertyIsEnumerable(word)) {Ð
state.beforeParams = true;Ð         return "keyword";Ð       }Ð       return
null;Ð     }Ð   }Ð   function tokenString(quote) {Ð     return
function(stream, state) {Ð     var escaped = false, next, end = false;Ð
while ((next = stream.next()) != null) {Ð       if (next == quote && !
escaped) {Ð         end = true;Ð         break;Ð       }Ð       escaped = !
escaped && next == "\\";Ð     }Ð     if (end) state.tokenize = tokenBase;Ð
        return "string";Ð     };Ð   }Ð   function tokenComment(stream, state)
{Ð     var maybeEnd = false, ch;Ð     while (ch = stream.next()) {Ð       if
(ch == "#" && maybeEnd) {Ð         state.tokenize = tokenBase;Ð         break;Ð
        }Ð       maybeEnd = (ch == "*");Ð     }Ð     return "comment";Ð   }Ð
    function tokenUnparsed(stream, state) {Ð     var maybeEnd = 0, ch;Ð
while (ch = stream.next()) {Ð
```

```
                                    if (ch == "#" && maybeEnd == 2) {Ð
          state.tokenize = tokenBase;Ð         break;Ð       }Ð       if (ch
== "]")Ð         maybeEnd++;Ð       else if (ch != " ")Ð         maybeEnd = 0;Ð
      }Ð     return "meta";Ð   }Ð   return {Ð     startState: function() {Ð
        return {Ð         tokenize: tokenBase,Ð         beforeParams: false,Ð
          inParams: falseÐ       };Ð     },Ð     token: function(stream,
state) {Ð       if (stream.eatSpace()) return null;Ð       return
state.tokenize(stream, state);Ð     }Ð   };Ð});ÐodeMirror.defineMIME("text/x-
tcl", "tcl");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\textile\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ðfunction() {Ð var mode =
CodeMirror.getMode({tabSize: 4}, 'textile');Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT('simpleParagraphs',Ð     'Some text.',Ð     '',Ð     'Some more text.');Ð /
*Ð  * Phrase ModifiersÐ  */Ð MT('em',Ð     'foo [em _bar_]');Ð MT('emBoogus',Ð
      'code_mirror');Ð MT('strong',Ð     'foo [strong *bar*]');Ð
MT('strongBogus',Ð     '3 * 3 = 9');Ð MT('italic',Ð     'foo [em __bar__]');Ð
MT('italicBogus',Ð     'code__mirror');Ð MT('bold',Ð     'foo [strong
**bar**]');Ð MT('boldBogus',Ð     '3 ** 3 = 27');Ð MT('simpleLink',Ð
'[link "CodeMirror":http://codemirror.net]');Ð MT('referenceLink',Ð
'[link "CodeMirror":code_mirror]',Ð     'Normal Text.',Ð     '[link
[[code_mirror]]http://codemirror.net]');Ð MT('footCite',Ð     'foo
bar[qualifier [[1]]]');Ð MT('footCiteBogus',Ð     'foo bar[[1a2]]');Ð
MT('special-characters',Ð         'Registered [tag (r)], ' +Ð
'Trademark [tag (tm)], and ' +Ð         'Copyright [tag (c)] 2008');Ð
MT('cite',Ð     "A book is [keyword ??The Count of Monte Cristo??] by
Dumas.");Ð MT('additionAndDeletion',Ð     'The news networks declared
[negative -Al Gore-] ' +Ð       '[positive +George W. Bush+] the winner in
Florida.');Ð MT('subAndSup',Ð     'f(x, n) = log [builtin ~4~] x [builtin
^n^]');Ð MT('spanAndCode',Ð     'A [quote %span element%] and [atom @code
element@]');Ð MT('spanBogus',Ð     'Percentage 25% is not a span.');Ð
MT('citeBogus',Ð     'Question? is not a citation.');Ð MT('codeBogus',Ð
'user@example.com');Ð MT('subBogus',Ð     '~username');Ð MT('supBogus',Ð
'foo ^ bar');Ð MT('deletionBogus',Ð     '3 - 3 = 0');Ð MT('additionBogus',Ð
      '3 + 3 = 6');Ð MT('image',Ð     'An image: [string !http://
www.example.com/image.png!]');Ð MT('imageWithAltText',Ð     'An image:
[string !http://www.example.com/image.png (Alt Text)!]');Ð MT('imageWithUrl',Ð
      'An image: [string !http://www.example.com/image.png!:http://
www.example.com/]');Ð /*Ð  * HeadersÐ  */Ð MT('h1',Ð     '[header&header-1
h1. foo]');Ð MT('h2',Ð     '[header&header-2 h2. foo]');Ð MT('h3',Ð
'[header&header-3 h3. foo]');Ð MT('h4',Ð     '[header&header-4 h4. foo]');Ð
MT('h5',Ð     '[header&header-5 h5. foo]');Ð MT('h6',Ð     '[header&header-6
h6. foo]');Ð MT('h7Bogus',Ð     'h7. foo');Ð MT('multipleHeaders',Ð
'[header&header-1 h1. Heading 1]',Ð     '',Ð     'Some text.',Ð     '',Ð
'[header&header-2 h2. Heading 2]',Ð     '',Ð     'More text.');Ð
MT('h1inline',Ð     '[header&header-1 h1. foo ][header&header-1&em _bar_]
[header&header-1  baz]');Ð /*Ð  * ListsÐ  */Ð MT('ul',Ð     'foo',Ð     'bar',Ð
      '',Ð     '[variable-2 * foo]',Ð     '[variable-2 * bar]');Ð
MT('ulNoBlank',Ð     'foo',Ð     'bar',Ð     '[variable-2 * foo]',Ð
'[variable-2 * bar]');Ð MT('ol',Ð     'foo',Ð     'bar',Ð     '',Ð
'[variable-2 # foo]',Ð     '[variable-2 # bar]');Ð MT('olNoBlank',Ð     'foo',Ð
      'bar',Ð     '[variable-2 # foo]',Ð     '[variable-2 # bar]');Ð
MT('ulFormatting',Ð     '[variable-2 * ][variable-2&em _foo_][variable-2
bar]',Ð     '[variable-2 * ][variable-2&strong *][variable-2&em&strong
_foo_]' +Ð       '[variable-2&strong *][variable-2  bar]',Ð     '[variable-2
* ][variable-2&strong *foo*][variable-2 bar]');Ð MT('olFormatting',Ð
'[variable-2 # ][variable-2&em _foo_][variable-2 bar]',Ð     '[variable-2 # ]
[variable-2&strong *][variable-2&em&strong _foo_]' +Ð
'[variable-2&strong *][variable-2  bar]',Ð     '[variable-2 # ]
[variable-2&strong *foo*][variable-2 bar]');Ð MT('ulNested',Ð
'[variable-2 * foo]',Ð     '[variable-3 ** bar]',Ð     '[keyword *** bar]',Ð
      '[variable-2 **** bar]',Ð     '[variable-3 ** bar]');Ð MT('olNested',Ð
      '[variable-2 # foo]',Ð     '[variable-3 ## bar]',Ð     '[keyword ###
bar]',Ð     '[variable-2 #### bar]',Ð     '[variable-3 ## bar]');Ð
MT('ulNestedWithOl',Ð     '[variable-2 * foo]',Ð     '[variable-3 ## bar]',Ð
      '[keyword *** bar]',Ð     '[variable-2 #### bar]',Ð     '[variable-3 **
bar]');Ð MT('olNestedWithUl',Ð     '[variable-2 # foo]',Ð     '[variable-3 **
bar]',Ð
```

```
            '[keyword ### bar]',Ð     '[variable-2 **** bar]',Ð
'[variable-3 ## bar]');Ð MT('definitionList',Ð     '[number - coffee := Hot ]
[number&em _and_][number  black]',Ð     '',Ð     'Normal text.');Ð
MT('definitionListSpan',Ð     '[number - coffee :=]',Ð     '',Ð     '[number
Hot ][number&em _and_][number  black =:]',Ð     '',Ð     'Normal text.');Ð
MT('boo',Ð     '[number - dog := woof woof]',Ð     '[number - cat := meow
meow]',Ð     '[number - whale :=]',Ð     '[number Whale noises.]',Ð     '',Ð
      '[number Also, ][number&em _splashing_][number . =:]');Ð /*Ð  *
AttributesÐ  */Ð MT('divWithAttribute',Ð     '[punctuation div]
[punctuation&attribute (#my-id)][punctuation . foo bar]');Ð
MT('divWithAttributeAnd2emRightPadding',Ð     '[punctuation div]
[punctuation&attribute (#my-id)(([punctuation . foo bar]');Ð
MT('divWithClassAndId',Ð     '[punctuation div][punctuation&attribute (my-
class#my-id)][punctuation . foo bar]');Ð MT('paragraphWithCss',Ð
'p[attribute {color:red;}]. foo bar');Ð MT('paragraphNestedStyles',Ð     'p.
[strong *foo ][strong&em _bar_][strong *]');Ð MT('paragraphWithLanguage',Ð
      'p[attribute [[fr]]]. Parlez-vous français?');Ð MT('paragraphLeftAlign',Ð
      'p[attribute <]. Left');Ð MT('paragraphRightAlign',Ð     'p[attribute
>]. Right');Ð MT('paragraphRightAlign',Ð     'p[attribute =]. Center');Ð
MT('paragraphJustified',Ð     'p[attribute <>]. Justified');Ð
MT('paragraphWithLeftIndent1em',Ð     'p[attribute (]. Left');Ð
MT('paragraphWithRightIndent1em',Ð     'p[attribute )]. Right');Ð
MT('paragraphWithLeftIndent2em',Ð     'p[attribute ((]. Left');Ð
MT('paragraphWithRightIndent2em',Ð     'p[attribute ))]. Right');Ð
MT('paragraphWithLeftIndent3emRightIndent2em',Ð     'p[attribute ((())].
Right');Ð MT('divFormatting',Ð     '[punctuation div. ][punctuation&strong
*foo ]' +Ð       '[punctuation&strong&em _bar_][punctuation&strong *]');Ð
MT('phraseModifierAttributes',Ð     'p[attribute (my-class)]. This is a
paragraph that has a class and' +Ð     ' this [em _][em&attribute (#special-
phrase)][em emphasized phrase_]' +Ð     ' has an id.');Ð MT('linkWithClass',Ð
      '[link "(my-class). This is a link with class":http://redcloth.org]');Ð
  /*Ð  * LayoutsÐ  */Ð MT('paragraphLayouts',Ð     'p. This is one
paragraph.',Ð     '',Ð     'p. This is another.');Ð MT('div',Ð
'[punctuation div. foo bar]');Ð MT('pre',Ð     '[operator pre. Text]');Ð
MT('bq.',Ð     '[bracket bq. foo bar]',Ð     '',Ð     'Normal text.');Ð
MT('footnote',Ð     '[variable fn123. foo ][variable&strong *bar*]');Ð /*Ð  *
Spanning LayoutsÐ  */Ð MT('bq..ThenParagraph',Ð     '[bracket bq.. foo bar]',Ð
      '',Ð     '[bracket More quote.]',Ð     'p. Normal Text');Ð
MT('bq..ThenH1',Ð     '[bracket bq.. foo bar]',Ð     '',Ð     '[bracket More
quote.]',Ð     '[header&header-1 h1. Header Text]');Ð MT('bc..ThenParagraph',Ð
      '[atom bc.. # Some ruby code]',Ð     '[atom obj = {foo: :bar}]',Ð
'[atom puts obj]',Ð     '',Ð     '[atom obj[[:love]] = "*love*"]',Ð
'[atom puts obj.love.upcase]',Ð     '',Ð     'p. Normal text.');Ð
MT('fn1..ThenParagraph',Ð     '[variable fn1.. foo bar]',Ð     '',Ð
'[variable More.]',Ð     'p. Normal Text');Ð MT('pre..ThenParagraph',Ð
'[operator pre.. foo bar]',Ð     '',Ð     '[operator More.]',Ð     'p. Normal
Text');Ð /*Ð  * TablesÐ  */Ð MT('table',Ð     '[variable-3&operator |_. name |
_. age|]',Ð     '[variable-3 |][variable-3&strong *Walter*][variable-3 |   5
|]',Ð     '[variable-3 |Florence|   6  |]',Ð     '',Ð     'p. Normal text.');Ð
  MT('tableWithAttributes',Ð     '[variable-3&operator |_. name |_. age|]',Ð
      '[variable-3 |][variable-3&attribute /2.][variable-3  Jim |]',Ð
'[variable-3 |][variable-3&attribute \\2{color: red}.][variable-3  Sam |]');Ð
  /*Ð  * HTMLÐ  */Ð MT('html',Ð     '[comment <div id="wrapper">]',Ð
'[comment <section id="introduction">]',Ð     '',Ð     '[header&header-1 h1.
Welcome]',Ð     '',Ð     '[variable-2 * Item one]',Ð     '[variable-2 * Item
two]',Ð     '',Ð     '[comment <a href="http://example.com">Example</a>]',Ð
      '',Ð     '[comment </section>]',Ð     '[comment </div>]');Ð
MT('inlineHtml',Ð     'I can use HTML directly in my [comment <span
class="youbetcha">Textile</span>].');Ð /*Ð  * No-TextileÐ  */Ð MT('notextile',Ð
    '[string-2 notextile. *No* formatting]');Ð
```

```
                                                Ð MT('notextileInline',Ð
'Use [string-2 ==*asterisks*==] for [strong *strong*] text.');Ð
MT('notextileWithPre',Ð     '[operator pre. *No* formatting]');Ð
MT('notextileWithSpanningPre',Ð     '[operator pre.. *No* formatting]',Ð
'',Ð     '[operator *No* formatting]');Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\textile\textile.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == 'object' && typeof module == 'object') { // CommonJS Ð
mod(require('../../lib/codemirror'));Ð } else if (typeof define == 'function'
&& define.amd) { // AMD Ð   define(['../../lib/codemirror'], mod);Ð } else
{ // Plain browser env Ð   mod(CodeMirror);Ð }Ð})(function(CodeMirror) {Ð use
strict';Ð var TOKEN_STYLES = {Ð addition: 'positive',Ð attributes: 'attribute',Ð
  bold: 'strong',Ð cite: 'keyword',Ð code: 'atom',Ð definitionList: 'number',Ð
  deletion: 'negative',Ð div: 'punctuation',Ð em: 'em',Ð footnote: 'variable',Ð
  footCite: 'qualifier',Ð header: 'header',Ð html: 'comment',Ð image:
'string',Ð italic: 'em',Ð link: 'link',Ð linkDefinition: 'link',Ð list1:
'variable-2',Ð list2: 'variable-3',Ð list3: 'keyword',Ð notextile: 'string-2',Ð
  pre: 'operator',Ð p: 'property',Ð quote: 'bracket',Ð span: 'quote',Ð
specialChar: 'tag',Ð strong: 'strong',Ð sub: 'builtin',Ð sup: 'builtin',Ð
table: 'variable-3',Ð tableHeading: 'operator'Ð};Ð function
Parser(regExpFactory, state, stream) {Ð this.regExpFactory = regExpFactory;Ð
this.state = state;Ð this.stream = stream;Ð this.styles = TOKEN_STYLES;Ð
this.state.specialChar = null;ÐÐ Parser.prototype.eat = function(name) {Ð
return this.stream.match(this.regExpFactory.pattern(name), true);Ð};Ð
Parser.prototype.check = function(name) {Ð return
this.stream.match(this.regExpFactory.pattern(name), false);Ð};Ð
Parser.prototype.setModeForNextToken = function(mode) {Ð return
this.state.mode = mode;Ð};Ð Parser.prototype.execMode = function(newMode) {Ð
return this.setModeForNextToken(newMode).call(this);Ð};Ð
Parser.prototype.startNewLine = function() {Ð
this.setModeForNextToken(Modes.newLayout);Ð this.state.tableHeading = false;Ð
if (this.state.layoutType === 'definitionList' && this.state.spanningLayout) {Ð
    if (this.check('definitionListEnd')) {Ð     this.state.spanningLayout =
false;Ð   }Ð }Ð};Ð Parser.prototype.nextToken = function() {Ð return
this.state.mode.call(this);Ð};Ð Parser.prototype.styleFor = function(token) {Ð
if (this.styles.hasOwnProperty(token)) {Ð   return this.styles[token];Ð }Ð
throw 'unknown token';Ð};Ð Parser.prototype.handlePhraseModifier = function(ch) {Ð
  if (ch === '_') {Ð   if (this.stream.eat('_')) {Ð     return
this.togglePhraseModifier('italic', /^.*__/);Ð   }Ð   return
this.togglePhraseModifier('em', /^.*_/);Ð }Ð if (ch === '*') {Ð   if
(this.stream.eat('*')) {Ð     return this.togglePhraseModifier('bold', /
^.*\*\*/);Ð   }Ð   return this.togglePhraseModifier('strong', /^.*\*/);Ð }Ð
if (ch === '[') {Ð   if (this.stream.match(/\d+\]/)) {Ð
this.state.footCite = true;Ð   }Ð   return this.tokenStyles();Ð }Ð if (ch ===
'(') {Ð   if (this.stream.match('r)')) {Ð     this.state.specialChar = 'r';Ð
    } else if (this.stream.match('tm)')) {Ð     this.state.specialChar = 'tm';Ð
    } else if (this.stream.match('c)')) {Ð     this.state.specialChar = 'c';Ð
    }Ð   return this.tokenStyles();Ð }Ð if (ch === '<') {Ð   if
(this.stream.match(/(\w+)[^>]+>[^<]+<\/\1>/)) {Ð     return
this.tokenStylesWith(this.styleFor('html'));Ð   }Ð }Ð if (ch === '?' &&
this.stream.eat('?')) {Ð   return this.togglePhraseModifier('cite', /^.*\?
\?/);Ð }Ð if (ch === '=' && this.stream.eat('=')) {Ð   return
this.togglePhraseModifier('notextile', /^.*==/);Ð }Ð if (ch === '-') {Ð
return this.togglePhraseModifier('deletion', /^.*-/);Ð }Ð if (ch === '+') {Ð
    return this.togglePhraseModifier('addition', /^.*\+/);Ð }Ð if (ch ===
'~') {Ð   return this.togglePhraseModifier('sub', /^.*~/);Ð }Ð if (ch ===
'^') {Ð   return this.togglePhraseModifier('sup', /^.*\^/);Ð }Ð if (ch ===
'%') {Ð   return this.togglePhraseModifier('span', /^.*%/);Ð }Ð if (ch ===
'@') {Ð   return this.togglePhraseModifier('code', /^.*@/);Ð }Ð if (ch ===
'!') {Ð   var type = this.togglePhraseModifier('image', /^.*(?:\([^\)]+
\))?!/);Ð   this.stream.match(/^:\S+/); // optional Url portion Ð   return
type;Ð }Ð return this.tokenStyles();Ð};Ð Parser.prototype.togglePhraseModifier =
function(phraseModifier, closeRE) {Ð if (this.state[phraseModifier]) { //
remove phrase modifier Ð
```

```
                            var type = this.tokenStyles();Ð
this.state[phraseModifier] = false;Ð   return type;Ð }Ð if
(this.stream.match(closeRE, false)) { // add phrase modifierÐ
this.state[phraseModifier] = true;Ð
this.setModeForNextToken(Modes.attributes);Ð }Ð return this.tokenStyles();Ð};Ð
Parser.prototype.tokenStyles = function() {Ð var disabled =
this.textileDisabled(),Ð     styles = [];Ð if (disabled) return disabled;Ð if
(this.state.layoutType) {Ð
styles.push(this.styleFor(this.state.layoutType));Ð }Ð styles =
styles.concat(this.activeStyles('addition', 'bold', 'cite', 'code',Ð
'deletion', 'em', 'footCite', 'image', 'italic', 'link', 'span',
'specialChar', 'strong',Ð     'sub', 'sup', 'table', 'tableHeading'));Ð if
(this.state.layoutType === 'header') {Ð   styles.push(this.styleFor('header')
+ '-' + this.state.header);Ð }Ð return styles.length ? styles.join(' ') :
null;Ð};ÐParser.prototype.textileDisabled = function() {Ð var type =
this.state.layoutType;Ð switch(type) {Ð   case 'notextile':Ð   case 'code':Ð
    case 'pre':Ð     return this.styleFor(type);Ð   default:Ð     if
(this.state.notextile) {Ð       return this.styleFor('notextile') + (type ?
(' ' + this.styleFor(type)) : '');Ð     }Ð     return null;Ð }Ð};Ð
Parser.prototype.tokenStylesWith = function(extraStyles) {Ð var disabled =
this.textileDisabled(),Ð     type;Ð if (disabled) return disabled;Ð type =
this.tokenStyles();Ð if(extraStyles) {Ð   return type ? (type + ' ' +
extraStyles) : extraStyles;Ð }Ð return type;Ð};ÐParser.prototype.activeStyles =
function() {Ð var styles = [],Ð     i;Ð for (i = 0; i < arguments.length; +
+i) {Ð   if (this.state[arguments[i]]) {Ð
styles.push(this.styleFor(arguments[i]));Ð   }Ð }Ð return styles;Ð};Ð
Parser.prototype.blankLine = function() {Ð var spanningLayout =
this.state.spanningLayout,Ð     type = this.state.layoutType,Ð     key;Ð for
(key in this.state) {Ð   if (this.state.hasOwnProperty(key)) {Ð     delete
this.state[key];Ð   }Ð }Ð this.setModeForNextToken(Modes.newLayout);Ð if
(spanningLayout) {Ð   this.state.layoutType = type;Ð
this.state.spanningLayout = true;Ð }Ð};ÐFunction RegExpFactory() {Ð this.cache
= {};Ð this.single = {Ð   bc: 'bc',Ð   bq: 'bq',Ð   definitionList: /-
[^(?::=)]+:=+/,Ð   definitionListEnd: /.*=:\s*$/,Ð   div: 'div',Ð
drawTable: /\|.*\|/,Ð   foot: /fn\d+/,Ð   header: /h[1-6]/,Ð   html: /\s*<(?:
\/)?(\w+)(?:[^>]+)?>(?:[^<]+<\/\1>)?/,Ð   link: /["]+":\S/,Ð
linkDefinition: /\[[^\s\]]+\]\S+/,Ð   list: /(?:#+|\*+)/,Ð   notextile:
'notextile',Ð   para: 'p',Ð   pre: 'pre',Ð   table: 'table',Ð
tableCellAttributes: /[/\\]\d+/,Ð   tableHeading: /\|_\./,Ð   tableText: /
["_\*\[\(\?\+~\^%@|-]+/,Ð   text: /["_=\*\[\(<\?\+~\^%@-]+/Ð };Ð
this.attributes = {Ð   align: /(?:<>|<|>|=)/,Ð   selector: /\([^\(][^\)]+\)/,Ð
    lang: /\[[^\[\]]+\]/,Ð   pad: /(?:\(+|\)+){1,2}/,Ð   css: /\{[^\}]+\}/Ð };Ð
}ÐRegExpFactory.prototype.pattern = function(name) {Ð return (this.cache[name]
|| this.createRe(name));Ð};ÐRegExpFactory.prototype.createRe = function(name) {Ð
  switch (name) {Ð   case 'drawTable':Ð     return this.makeRe('^',
this.single.drawTable, '$');Ð   case 'html':Ð     return this.makeRe('^',
this.single.html, '(?:', this.single.html, ')*', '$');Ð   case
'linkDefinition':Ð     return this.makeRe('^', this.single.linkDefinition,
'$');Ð   case 'listLayout':Ð     return this.makeRe('^', this.single.list,
this.pattern('allAttributes'), '*\\s+');Ð   case 'tableCellAttributes':Ð
return this.makeRe('^', this.choiceRe(this.single.tableCellAttributes,Ð
          this.pattern('allAttributes')), '+\\.');Ð   case 'type':Ð
return this.makeRe('^', this.pattern('allTypes'));Ð   case 'typeLayout':Ð
return this.makeRe('^', this.pattern('allTypes'),
this.pattern('allAttributes'),Ð         '*\\.\\.?', '(\\s+|$)');Ð   case
'attributes':Ð     return this.makeRe('^', this.pattern('allAttributes'),
'+');Ð   case 'allTypes':Ð     return this.choiceRe(this.single.div,
this.single.foot,Ð         this.single.header, this.single.bc, this.single.bq,Ð
          this.single.notextile, this.single.pre, this.single.table,Ð
this.single.para);Ð
```

```
                  Ð   case 'allAttributes':Ð     return
this.choiceRe(this.attributes.selector, this.attributes.css,Ð
this.attributes.lang, this.attributes.align, this.attributes.pad);Ð   default:Ð
      return this.makeRe('^', this.single[name]);Ð }Ð};Ð
RegExpFactory.prototype.makeRe = function() {Ð var pattern = '',Ð     i,Ð
arg;Ð for (i = 0; i < arguments.length; ++i) {Ð   arg = arguments[i];Ð
pattern += (typeof arg === 'string') ? arg : arg.source;Ð }Ð return new
RegExp(pattern);Ð};Ð RegExpFactory.prototype.choiceRe = function() {Ð var parts
= [arguments[0]],Ð     i;Ð for (i = 1; i < arguments.length; ++i) {Ð
parts[i * 2 - 1] = '|';Ð   parts[i * 2] = arguments[i];Ð }Ð
parts.unshift('(?:');Ð parts.push(')');Ð return this.makeRe.apply(this,
parts);Ð};Ð var Modes = {Ð newLayout: function() {Ð   if
(this.check('typeLayout')) {Ð     this.state.spanningLayout = false;Ð
return this.execMode(Modes.blockType);Ð   }Ð   if (!this.textileDisabled()) {Ð
      if (this.check('listLayout')) {Ð       return this.execMode(Modes.list);Ð
      } else if (this.check('drawTable')) {Ð       return
this.execMode(Modes.table);Ð     } else if (this.check('linkDefinition')) {Ð
        return this.execMode(Modes.linkDefinition);Ð     } else if
(this.check('definitionList')) {Ð       return
this.execMode(Modes.definitionList);Ð     } else if (this.check('html')) {Ð
        return this.execMode(Modes.html);Ð     }Ð   }Ð   return
this.execMode(Modes.text);Ð },Ð blockType: function() {Ð   var match,Ð
type;Ð   this.state.layoutType = null;Ð   if (match = this.eat('type')) {Ð
      type = match[0];Ð   } else {Ð     return this.execMode(Modes.text);Ð   }Ð
    if(match = type.match(this.regExpFactory.pattern('header'))) {Ð
this.state.layoutType = 'header';Ð     this.state.header = parseInt(match[0]
[1]);Ð   } else if (type.match(this.regExpFactory.pattern('bq'))) {Ð
this.state.layoutType = 'quote';Ð   } else if
(type.match(this.regExpFactory.pattern('bc'))) {Ð     this.state.layoutType =
'code';Ð   } else if (type.match(this.regExpFactory.pattern('foot'))) {Ð
this.state.layoutType = 'footnote';Ð   } else if
(type.match(this.regExpFactory.pattern('notextile'))) {Ð
this.state.layoutType = 'notextile';Ð   } else if
(type.match(this.regExpFactory.pattern('pre'))) {Ð     this.state.layoutType
= 'pre';Ð   } else if (type.match(this.regExpFactory.pattern('div'))) {Ð
this.state.layoutType = 'div';Ð   } else if
(type.match(this.regExpFactory.pattern('table'))) {Ð
this.state.layoutType = 'table';Ð   }Ð
this.setModeForNextToken(Modes.attributes);Ð   return this.tokenStyles();Ð },Ð
  text: function() {Ð   if (this.eat('text')) {Ð     return
this.tokenStyles();Ð   }Ð   var ch = this.stream.next();Ð   if (ch === '"') {Ð
      return this.execMode(Modes.link);Ð   }Ð   return
this.handlePhraseModifier(ch);Ð },Ð attributes: function() {Ð
this.setModeForNextToken(Modes.layoutLength);Ð   if (this.eat('attributes')) {Ð
      return this.tokenStylesWith(this.styleFor('attributes'));Ð   }Ð
return this.tokenStyles();Ð },Ð layoutLength: function() {Ð   if
(this.stream.eat('.') && this.stream.eat('.')) {Ð
this.state.spanningLayout = true;Ð   }Ð
this.setModeForNextToken(Modes.text);Ð   return this.tokenStyles();Ð },Ð
list: function() {Ð   var match = this.eat('list'),Ð       listMod;Ð
this.state.listDepth = match[0].length;Ð   listMod = (this.state.listDepth -
1) % 3;Ð   if (!listMod) {Ð     this.state.layoutType = 'list1';Ð   } else if
(listMod === 1) {Ð     this.state.layoutType = 'list2';Ð   } else {Ð
this.state.layoutType = 'list3';Ð   }Ð
this.setModeForNextToken(Modes.attributes);Ð   return this.tokenStyles();Ð },Ð
  link: function() {Ð   this.setModeForNextToken(Modes.text);Ð   if
(this.eat('link')) {Ð     this.stream.match(/\S+/);Ð     return
this.tokenStylesWith(this.styleFor('link'));Ð   }Ð   return
this.tokenStyles();Ð },Ð linkDefinition: function() {Ð
this.stream.skipToEnd();Ð
```

```
                              return
this.tokenStylesWith(this.styleFor('linkDefinition'));Ð },Ð definitionList:
function() {Ð   this.eat('definitionList');Ð   this.state.layoutType =
'definitionList';Ð   if (this.stream.match(/\s*$/)) {Ð
this.state.spanningLayout = true;Ð   } else {Ð
this.setModeForNextToken(Modes.attributes);Ð   }Ð   return this.tokenStyles();Ð
  },Ð html: function() {Ð   this.stream.skipToEnd();Ð   return
this.tokenStylesWith(this.styleFor('html'));Ð },Ð table: function() {Ð
this.state.layoutType = 'table';Ð   return this.execMode(Modes.tableCell);Ð },Ð
  tableCell: function() {Ð   if (this.eat('tableHeading')) {Ð
this.state.tableHeading = true;Ð   } else {Ð     this.stream.eat('|');Ð   }Ð
    this.setModeForNextToken(Modes.tableCellAttributes);Ð   return
this.tokenStyles();Ð },Ð tableCellAttributes: function() {Ð
this.setModeForNextToken(Modes.tableText);Ð   if
(this.eat('tableCellAttributes')) {Ð     return
this.tokenStylesWith(this.styleFor('attributes'));Ð   }Ð   return
this.tokenStyles();Ð },Ð tableText: function() {Ð   if
(this.eat('tableText')) {Ð     return this.tokenStyles();Ð   }Ð   if
(this.stream.peek() === '|') { // end of cellÐ
this.setModeForNextToken(Modes.tableCell);Ð     return this.tokenStyles();Ð
    }Ð   return this.handlePhraseModifier(this.stream.next());Ð }};Ð
CodeMirror.defineMode('textile', function() {Ð var regExpFactory = new
RegExpFactory();Ð return {Ð   startState: function() {Ð     return { mode:
Modes.newLayout };Ð   },Ð   token: function(stream, state) {Ð     var parser
= new Parser(regExpFactory, state, stream);Ð     if (stream.sol())
{ parser.startNewLine(); }Ð     return parser.nextToken();Ð   },Ð
blankLine: function(state) {Ð     new Parser(regExpFactory,
state).blankLine();Ð   }Ð };});ÐodeMirror.defineMIME('text/x-textile',
'textile');});Ð
```

public\assets\js\plugins\codemirror\mode\tiddlywiki\tiddlywiki.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others/ Distributed
under an MIT license: http://codemirror.net/LICENSE***   |''Name''|
tiddlywiki.js|   |''Description''|Enables TiddlyWikiy syntax highlighting
using CodeMirror|   |''Author''|PMario|   |''Version''|0.1.7|
|''Status''|''stable''|   |''Source''|[[GitHub|https://github.com/pmario/
CodeMirror2/blob/tw-syntax/mode/tiddlywiki]]|   |''Documentation''|http://
codemirror.tiddlyspace.com/|   |''License''|[[MIT License|http://
www.opensource.org/licenses/mit-license.php]]|   |''CoreVersion''|2.5.0|
|''Requires''|codemirror.js|   |''Keywords''|syntax highlighting color code
mirror codemirror|   ! Info   CoreVersion parameter is needed for
TiddlyWiki only!**//{{{function(mod) { if (typeof exports == "object" &&
typeof module == "object") // CommonJS   mod(require("../../lib/
codemirror"));  else if (typeof define == "function" && define.amd) // AMD
define(["../../lib/codemirror"], mod);  else // Plain browser env
mod(CodeMirror);})(function(CodeMirror) {"use strict";
CodeMirror.defineMode("tiddlywiki", function () {  // Tokenizer var
textwords = {};  var keywords = function () {   function kw(type) {
return { type: type, style: "macro"};   }   return {     "allTags":
kw('allTags'), "closeAll": kw('closeAll'), "list": kw('list'),
"newJournal": kw('newJournal'), "newTiddler": kw('newTiddler'),
"permaview": kw('permaview'), "saveChanges": kw('saveChanges'),
"search": kw('search'), "slider": kw('slider'),   "tabs": kw('tabs'),
"tag": kw('tag'), "tagging": kw('tagging'),       "tags": kw('tags'),
"tiddler": kw('tiddler'), "timeline": kw('timeline'),     "today":
kw('today'), "version": kw('version'),   "option": kw('option'),     "with":
kw('with'),     "filter": kw('filter')   };  }();  var isSpaceName = /
[\w_\-]/i,  reHR = /^\-\-\-\-+$/,                                  // <hr>
reWikiCommentStart = /^\/\*\*\*$/,            // /***  reWikiCommentStop = /
^\*\*\*\/$/,             // ***/  reBlockQuote = /^<<<$/,  reJsCodeStart = /
^\/\/\{\{\{$/,                       // //{{{ js block start  reJsCodeStop = /
^\/\/\}\}\}$/,                        // //}}} js stop  reXmlCodeStart = /
^<!--\{\{\{-->$/,           // xml block start  reXmlCodeStop = /^<!--\}\}\}--
>$/,            // xml stop  reCodeBlockStart = /
^\{\{\{$/,                        // {{{ TW text div block start
reCodeBlockStop = /^\}\}\}$/,                  // }}} TW text stop
reUntilCodeStop = /.*?\}\}\}/;  function chain(stream, state, f) {
state.tokenize = f;   return f(stream, state);  }  // Used as scratch
variables to communicate multiple values without  // consing up tons of
objects.  var type, content;  function ret(tp, style, cont) {   type = tp;
    content = cont;   return style;  }  function jsTokenBase(stream, state) {
    var sol = stream.sol(), ch;   state.block = false;        // indicates
the start of a code block.   ch = stream.peek();         // don't eat, to
make matching simpler   // check start of  blocks   if (sol && /[<\/
\*{}\-]/.test(ch)) {     if (stream.match(reCodeBlockStart)) {
state.block = true;       return chain(stream, state, twTokenCode);     }
      if (stream.match(reBlockQuote)) {       return ret('quote', 'quote');
      }     if (stream.match(reWikiCommentStart) ||
stream.match(reWikiCommentStop)) {       return ret('code', 'comment');
      }     if (stream.match(reJsCodeStart) || stream.match(reJsCodeStop) ||
stream.match(reXmlCodeStart) || stream.match(reXmlCodeStop)) {       return
ret('code', 'comment');     }     if (stream.match(reHR)) {       return
ret('hr', 'hr');     }   } // sol   ch = stream.next();   if (sol && /[\/
\*!#;:>|]/.test(ch)) {     if (ch == "!") { // tw header
stream.skipToEnd();       return ret("header", "header");     }     if (ch
== "*") { // tw list       stream.eatWhile('*');       return ret("list",
"comment");     }     if (ch == "#") { // tw numbered list
stream.eatWhile('#');       return ret("list", "comment");     }     if
(ch == ";") { // definition list, term       stream.eatWhile(';');
return ret("list", "comment");
```

}Ð if (ch == ":") { // definition list, descriptionÐ stream.eatWhile(':');Ð return ret("list", "comment");Ð }Ð if (ch == ">") { // single line quoteÐ stream.eatWhile(">");Ð return ret("quote", "quote");Ð }Ð if (ch == '|') {Ð return ret('table', 'header');Ð }Ð }Ð if (ch == '{' && stream.match(/\{\{/)) {Ð return chain(stream, state, twTokenCode);Ð }Ð // rudimentary html:// file:// link matching. TW knows much more ...Ð if (/[hf]/i.test(ch)) {Ð if (/[ti]/i.test(stream.peek()) && stream.match(/\b(ttps?|tp|ile):\/\/[\-A-Z0-9+&@#\/%?=~_|$!:,.;]*[A-Z0-9+&@#\/%=~_|$]/i)) {Ð return ret("link", "link");Ð }Ð }Ð // just a little string indicator, don't want to have the whole string coveredÐ if (ch == '"') {Ð return ret('string', 'string');Ð }Ð if (ch == '~') { // _no_ CamelCase indicator should be boldÐ return ret('text', 'brace');Ð }Ð if (/[\[\]]/.test(ch)) { // check for [[..]]Ð if (stream.peek() == ch) {Ð stream.next();Ð return ret('brace', 'brace');Ð }Ð }Ð if (ch == "@") { // check for space link. TODO fix @@...@@ highlightingÐ stream.eatWhile(isSpaceName);Ð return ret("link", "link");Ð }Ð if (/\d/.test(ch)) { // numbersÐ stream.eatWhile(/\d/);Ð return ret("number", "number");Ð }Ð if (ch == "/") { // tw invisible commentÐ if (stream.eat("%")) {Ð return chain(stream, state, twTokenComment);Ð }Ð else if (stream.eat("/")) { //Ð return chain(stream, state, twTokenEm);Ð }Ð }Ð if (ch == "_") { // tw underlineÐ if (stream.eat("_")) {Ð return chain(stream, state, twTokenUnderline);Ð }Ð }Ð // strikethrough and mdash handlingÐ if (ch == "-") {Ð if (stream.eat("-")) {Ð // if strikethrough looks ugly, change CSS.Ð if (stream.peek() != ' ')Ð return chain(stream, state, twTokenStrike);Ð // mdashÐ if (stream.peek() == ' ')Ð return ret('text', 'brace');Ð }Ð }Ð if (ch == "'") { // tw boldÐ if (stream.eat("'")) {Ð return chain(stream, state, twTokenStrong);Ð }Ð }Ð if (ch == "<") { // tw macroÐ if (stream.eat("<")) {Ð return chain(stream, state, twTokenMacro);Ð }Ð }Ð else {Ð return ret(ch);Ð }Ð // core macro handlingÐ stream.eatWhile(/[\w\$_]/);Ð var word = stream.current(),Ð known = textwords.propertyIsEnumerable(word) && textwords[word];Ð return known ? ret(known.type, known.style, word) : ret("text", null, word);Ð } // jsTokenBase()Ð // tw invisible commentÐ function twTokenComment(stream, state) {Ð var maybeEnd = false,Ð ch;Ð while (ch = stream.next()) {Ð if (ch == "/" && maybeEnd) {Ð state.tokenize = jsTokenBase;Ð break;Ð }Ð maybeEnd = (ch == "%");Ð }Ð return ret("comment", "comment");Ð }Ð // tw strong / boldÐ function twTokenStrong(stream, state) {Ð var maybeEnd = false,Ð ch;Ð while (ch = stream.next()) {Ð if (ch == "'" && maybeEnd) {Ð state.tokenize = jsTokenBase;Ð break;Ð }Ð maybeEnd = (ch == "'");Ð }Ð return ret("text", "strong");Ð }Ð // tw codeÐ function twTokenCode(stream, state) {Ð var ch, sb = state.block;Ð if (sb && stream.current()) {Ð return ret("code", "comment");Ð }Ð if (!sb && stream.match(reUntilCodeStop)) {Ð state.tokenize = jsTokenBase;Ð return ret("code", "comment");Ð }Ð if (sb && stream.sol() && stream.match(reCodeBlockStop)) {Ð state.tokenize = jsTokenBase;Ð return ret("code", "comment");Ð }Ð ch = stream.next();Ð return (sb) ? ret("code", "comment") : ret("code", "comment");Ð }Ð // tw em / italicÐ function twTokenEm(stream, state) {Ð var maybeEnd = false,Ð ch;Ð while (ch = stream.next()) {Ð if (ch == "/" && maybeEnd) {Ð state.tokenize = jsTokenBase;Ð break;Ð }Ð maybeEnd = (ch == "/");Ð }Ð return ret("text", "em");Ð }Ð // tw underlined textÐ function twTokenUnderline(stream, state) {Ð var maybeEnd = false,Ð ch;Ð while (ch = stream.next()) {Ð if (ch == "_" && maybeEnd) {Ð state.tokenize = jsTokenBase;Ð break;Ð }Ð maybeEnd = (ch == "_");Ð }Ð return ret("text", "underlined");Ð }Ð // tw strike through text looks uglyÐ // change CSS if neededÐ function twTokenStrike(stream, state) {Ð var maybeEnd = false, ch;Ð

```
                              Ð   while (ch = stream.next()) {Ð     if (ch ==
"-" && maybeEnd) {Ð       state.tokenize = jsTokenBase;Ð       break;Ð     }Ð
      maybeEnd = (ch == "-");Ð   }Ð   return ret("text", "strikethrough");Ð }Ð
  // macroÐ function twTokenMacro(stream, state) {Ð   var ch, word, known;Ð
if (stream.current() == '<<') {Ð     return ret('brace', 'macro');Ð   }Ð   ch
= stream.next();Ð   if (!ch) {Ð     state.tokenize = jsTokenBase;Ð     return
ret(ch);Ð   }Ð   if (ch == ">") {Ð     if (stream.peek() == '>') {Ð
stream.next();Ð       state.tokenize = jsTokenBase;Ð       return
ret("brace", "macro");Ð     }Ð   }Ð   stream.eatWhile(/[\w\$_]/);Ð   word =
stream.current();Ð   known = keywords.propertyIsEnumerable(word) &&
keywords[word];Ð   if (known) {Ð     return ret(known.type, known.style,
word);Ð   }Ð   else {Ð     return ret("macro", null, word);Ð   }Ð }Ð //
InterfaceÐ return {Ð   startState: function () {Ð     return {Ð
tokenize: jsTokenBase,Ð       indented: 0,Ð       level: 0Ð     };Ð   },Ð
token: function (stream, state) {Ð     if (stream.eatSpace()) return null;Ð
      var style = state.tokenize(stream, state);Ð     return style;Ð   },Ð
electricChars: ""Ð };Ð});ÐodeMirror.defineMIME("text/x-tiddlywiki",
"tiddlywiki");Ð});Ð/}}}Ð
```

public\assets\js\plugins\codemirror\mode\tiki\tiki.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode('tiki', function(config) {Ð function inBlock(style,
terminator, returnTokenizer) {Ð   return function(stream, state) {Ð     while
(!stream.eol()) {Ð       if (stream.match(terminator)) {Ð
state.tokenize = inText;Ð         break;Ð       }Ð       stream.next();Ð     }Ð
      if (returnTokenizer) state.tokenize = returnTokenizer;Ð     return
style;Ð   };Ð }Ð function inLine(style) {Ð   return function(stream, state) {Ð
      while(!stream.eol()) {Ð       stream.next();Ð     }Ð     state.tokenize
= inText;Ð     return style;Ð   };Ð }Ð function inText(stream, state) {Ð
function chain(parser) {Ð     state.tokenize = parser;Ð     return
parser(stream, state);Ð   }Ð   var sol = stream.sol();Ð   var ch =
stream.next();Ð   //non start of line Ð   switch (ch) { //switch is generally
much faster than if, so it is used here Ð   case "{": //plugin Ð
stream.eat("/");Ð     stream.eatSpace();Ð     var tagName = "";Ð     var c;Ð
      while ((c = stream.eat(/[^\s\u00a0=\"\'\/?(}]/))) tagName += c;Ð
state.tokenize = inPlugin;Ð     return "tag";Ð     break;Ð   case "_": //bold Ð
      if (stream.eat("_")) {Ð       return chain(inBlock("strong", "__",
inText));Ð     }Ð     break;Ð   case "'": //italics Ð     if (stream.eat("'"))
{Ð       // Italic text Ð       return chain(inBlock("em", "''", inText));Ð
      }Ð     break;Ð   case "(":// Wiki Link Ð     if (stream.eat("(")) {Ð
        return chain(inBlock("variable-2", "))", inText));Ð     }Ð     break;Ð
    case "[":// Weblink Ð     return chain(inBlock("variable-3", "]", inText));Ð
      break;Ð   case "|": //table Ð     if (stream.eat("|")) {Ð       return
chain(inBlock("comment", "||"));Ð     }Ð     break;Ð   case "-":Ð     if
(stream.eat("=")) {//titleBar Ð       return chain(inBlock("header string",
"=-", inText));Ð     } else if (stream.eat("-")) {//deleted Ð       return
chain(inBlock("error tw-deleted", "--", inText));Ð     }Ð     break;Ð   case
"=": //underline Ð     if (stream.match("==")) {Ð       return
chain(inBlock("tw-underline", "===", inText));Ð     }Ð     break;Ð   case ":":Ð
      if (stream.eat(":")) {Ð       return chain(inBlock("comment", "::"));Ð
      }Ð     break;Ð   case "^": //box Ð     return chain(inBlock("tw-box",
"^"));Ð     break;Ð   case "~": //np Ð     if (stream.match("np~")) {Ð
return chain(inBlock("meta", "~/np~"));Ð     }Ð     break;Ð   }Ð   //start of
line types Ð   if (sol) {Ð     switch (ch) {Ð     case "!": //header at start
of line Ð       if (stream.match('!!!!!')) {Ð         return
chain(inLine("header string"));Ð       } else if (stream.match('!!!!')) {Ð
          return chain(inLine("header string"));Ð       } else if
(stream.match('!!!')) {Ð         return chain(inLine("header string"));Ð
        } else if (stream.match('!!')) {Ð         return chain(inLine("header
string"));Ð       } else {Ð         return chain(inLine("header string"));Ð
        }Ð       break;Ð     case "*": //unordered list line item, or <li />
at start of line Ð     case "#": //ordered list line item, or <li /> at start
of line Ð     case "+": //ordered list line item, or <li /> at start of line Ð
        return chain(inLine("tw-listitem bracket"));Ð       break;Ð     }Ð   }Ð
    //stream.eatWhile(/[&{]/); was eating up plugins, turned off to act less
like html and more like tiki Ð   return null;Ð }Ð var indentUnit =
config.indentUnit;Ð // Return variables for tokenizers Ð var pluginName, type;Ð
  function inPlugin(stream, state) {Ð   var ch = stream.next();Ð   var peek =
stream.peek();Ð   if (ch == "}") {Ð     state.tokenize = inText;Ð     //type
= ch == ")" ? "endPlugin" : "selfclosePlugin"; inPlugin Ð     return "tag";Ð
    } else if (ch == "(" || ch == ")") {Ð     return "bracket";Ð   } else if
(ch == "=") {Ð     type = "equals";Ð     if (peek == ">") {Ð       ch =
stream.next();Ð       peek = stream.peek();Ð     }Ð     //here we detect
values directly after equal character with no quotes Ð
```

```
                                                            if (!/
[\'\"]/.test(peek)) {Ð       state.tokenize = inAttributeNoQuote();Ð     }Ð
      //end detect valuesÐ     return "operator";Ð   } else if (/
[\'\"]/.test(ch)) {Ð     state.tokenize = inAttribute(ch);Ð     return
state.tokenize(stream, state);Ð   } else {Ð     stream.eatWhile(/
[^\s\u00a0=\"\'\/?]/);Ð     return "keyword";Ð   }Ð }Ð function
inAttribute(quote) {Ð   return function(stream, state) {Ð     while (!
stream.eol()) {Ð       if (stream.next() == quote) {Ð         state.tokenize
= inPlugin;Ð         break;Ð       }Ð     }Ð     return "string";Ð   };Ð }Ð
function inAttributeNoQuote() {Ð   return function(stream, state) {Ð
while (!stream.eol()) {Ð       var ch = stream.next();Ð       var peek =
stream.peek();Ð       if (ch == " " || ch == "," || /[ )}]/.test(peek)) {Ð
      state.tokenize = inPlugin;Ð     break;Ð   }Ð }Ð return "string";Ð};Ð
                      }Ð var curState, setStyle;Ð function pass() {Ð for (var i =
arguments.length - 1; i >= 0; i--) curState.cc.push(arguments[i]);Ð}Ð function
cont() {Ð pass.apply(null, arguments);Ð return true;Ð}Ð function
pushContext(pluginName, startOfLine) {Ð var noIndent = curState.context &&
curState.context.noIndent;Ð curState.context = {Ð   prev: curState.context,Ð
    pluginName: pluginName,Ð   indent: curState.indented,Ð   startOfLine:
startOfLine,Ð   noIndent: noIndentÐ };Ð}Ð function popContext() {Ð if
(curState.context) curState.context = curState.context.prev;Ð}Ð function
element(type) {Ð if (type == "openPlugin") {curState.pluginName = pluginName;
return cont(attributes, endplugin(curState.startOfLine));}Ð else if (type ==
"closePlugin") {Ð   var err = false;Ð   if (curState.context) {Ð     err =
curState.context.pluginName != pluginName;Ð     popContext();Ð   } else {Ð
      err = true;Ð   }Ð   if (err) setStyle = "error";Ð   return
cont(endcloseplugin(err));Ð }Ð else if (type == "string") {Ð   if (!
curState.context || curState.context.name != "!cdata") pushContext("!cdata");Ð
    if (curState.tokenize == inText) popContext();Ð   return cont();Ð }Ð else
return cont();Ð}Ð function endplugin(startOfLine) {Ð return function(type) {Ð
if (Ð     type == "selfclosePlugin" ||Ð       type == "endPlugin"Ð   )Ð
return cont();Ð   if (type == "endPlugin") {pushContext(curState.pluginName,
startOfLine); return cont();}Ð   return cont();Ð };Ð}Ð function
endcloseplugin(err) {Ð return function(type) {Ð   if (err) setStyle = "error";Ð
    if (type == "endPlugin") return cont();Ð   return pass();Ð };Ð}Ð function
attributes(type) {Ð if (type == "keyword") {setStyle = "attribute"; return
cont(attributes);}Ð if (type == "equals") return cont(attvalue, attributes);Ð
return pass();Ð}Ð function attvalue(type) {Ð if (type == "keyword") {setStyle =
"string"; return cont();}Ð if (type == "string") return cont(attvaluemaybe);Ð
return pass();Ð}Ð function attvaluemaybe(type) {Ð if (type == "string") return
cont(attvaluemaybe);Ð else return pass();Ð}Ð return {Ð startState: function() {Ð
    return {tokenize: inText, cc: [], indented: 0, startOfLine: true,
pluginName: null, context: null};Ð },Ð token: function(stream, state) {Ð   if
(stream.sol()) {Ð     state.startOfLine = true;Ð     state.indented =
stream.indentation();Ð   }Ð   if (stream.eatSpace()) return null;Ð   setStyle
= type = pluginName = null;Ð   var style = state.tokenize(stream, state);Ð
if ((style || type) && style != "comment") {Ð     curState = state;Ð
while (true) {Ð       var comb = state.cc.pop() || element;Ð       if
(comb(type || style)) break;Ð     }Ð   }Ð   state.startOfLine = false;Ð
return setStyle || style;Ð },Ð indent: function(state, textAfter) {Ð   var
context = state.context;Ð   if (context && context.noIndent) return 0;Ð   if
(context && /^{\//.test(textAfter))Ð       context = context.prev;Ð
while (context && !context.startOfLine)Ð         context = context.prev;Ð
        if (context) return context.indent + indentUnit;Ð       else return 0;Ð
       },Ð   electricChars: "/"Ð };Ð});ÐodeMirror.defineMIME("text/tiki",
"tiki");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\toml\toml.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("toml", function () {Ð return {Ð   startState: function
() {Ð     return {Ð       inString: false,Ð       stringType: "",Ð       lhs:
true,Ð       inArray: 0Ð     };Ð   },Ð   token: function (stream, state) {Ð
      //check for state changes Ð     if (!state.inString && ((stream.peek()
== '"') || (stream.peek() == "'"))) {Ð       state.stringType = stream.peek();Ð
        stream.next(); // Skip quote Ð       state.inString = true; // Update
state Ð     }Ð     if (stream.sol() && state.inArray === 0) {Ð       state.lhs
= true;Ð     }Ð     //return state Ð     if (state.inString) {Ð       while
(state.inString && !stream.eol()) {Ð         if (stream.peek() ===
state.stringType) {Ð           stream.next(); // Skip quote Ð
state.inString = false; // Clear flag Ð         } else if (stream.peek() === '\
\') {Ð           stream.next();Ð           stream.next();Ð         } else {Ð
            stream.match(/^.[^\\\"\']*/);Ð         }Ð       }Ð       return
state.lhs ? "property string" : "string"; // Token style Ð     } else if
(state.inArray && stream.peek() === ']') {Ð       stream.next();Ð
state.inArray--;Ð       return 'bracket';Ð     } else if (state.lhs &&
stream.peek() === '[' && stream.skipTo(']')) {Ð       stream.next();//skip
closing ]Ð       // array of objects has an extra open & close []Ð       if
(stream.peek() === ']') stream.next();Ð       return "atom";Ð     } else if
(stream.peek() === "#") {Ð       stream.skipToEnd();Ð       return "comment";Ð
      } else if (stream.eatSpace()) {Ð       return null;Ð     } else if
(state.lhs && stream.eatWhile(function (c) { return c != '=' && c != ' '; }))
{Ð       return "property";Ð     } else if (state.lhs && stream.peek() ===
"=") {Ð       stream.next();Ð       state.lhs = false;Ð       return null;Ð
      } else if (!state.lhs && stream.match(/^\d\d\d\d[\d\-\:\.T]*Z/)) {Ð
        return 'atom'; //date Ð     } else if (!state.lhs &&
(stream.match('true') || stream.match('false'))) {Ð       return 'atom';Ð
      } else if (!state.lhs && stream.peek() === '[') {Ð       state.inArray+
+;Ð       stream.next();Ð       return 'bracket';Ð     } else if (!state.lhs
&& stream.match(/^\-?\d+(?:\.\d+)?/)) {Ð       return 'number';Ð     } else
if (!stream.eatSpace()) {Ð       stream.next();Ð     }Ð     return null;Ð   }Ð
  };Ð );Ð CodeMirror.defineMIME('text/x-toml', 'toml');Ð );Ð
```

public\assets\js\plugins\codemirror\mode\tornado\tornado.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"), require("../htmlmixed/htmlmixed"),Ð
        require("../../addon/mode/overlay"));Ð else if (typeof define ==
"function" && define.amd) // AMD Ð   define(["../../lib/codemirror", "../
htmlmixed/htmlmixed",Ð           "../../addon/mode/overlay"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
  CodeMirror.defineMode("tornado:inner", function() {Ð   var keywords =
["and","as","assert","autoescape","block","break","class","comment","context",Ð

"continue","datetime","def","del","elif","else","end","escape","except",Ð

"exec","extends","false","finally","for","from","global","if","import","in",Ð

"include","is","json_encode","lambda","length","linkify","load","module",Ð

"none","not","or","pass","print","put","raise","raw","return","self","set",Ð

"squeeze","super","true","try","url_escape","while","with","without","xhtml_escape","yield
    keywords = new RegExp("^((" + keywords.join(")|(") + "))\\b");Ð
function tokenBase (stream, state) {Ð     stream.eatWhile(/[^\{]/);Ð     var
ch = stream.next();Ð     if (ch == "{") {Ð       if (ch = stream.eat(/\{|%|
#/)) {Ð         state.tokenize = inTag(ch);Ð         return "tag";Ð       }Ð
      }Ð   }Ð   function inTag (close) {Ð     if (close == "{") {Ð
close = "}";Ð     }Ð     return function (stream, state) {Ð       var ch =
stream.next();Ð       if ((ch == close) && stream.eat("}")) {Ð
state.tokenize = tokenBase;Ð         return "tag";Ð       }Ð       if
(stream.match(keywords)) {Ð         return "keyword";Ð       }Ð       return
close == "#" ? "comment" : "string";Ð     };Ð   }Ð   return {Ð
startState: function () {Ð       return {tokenize: tokenBase};Ð     },Ð
token: function (stream, state) {Ð       return state.tokenize(stream, state);Ð
      }Ð   };Ð });Ð CodeMirror.defineMode("tornado", function(config) {Ð
var htmlBase = CodeMirror.getMode(config, "text/html");Ð   var tornadoInner =
CodeMirror.getMode(config, "tornado:inner");Ð   return
CodeMirror.overlayMode(htmlBase, tornadoInner);Ð });Ð
CodeMirror.defineMIME("text/x-tornado", "tornado");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\turtle\turtle.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("turtle", function(config) {Ð var indentUnit =
config.indentUnit;Ð var curPunc;Ð function wordRegexp(words) {Ð   return new
RegExp("^(?:" + words.join("|") + ")$", "i");Ð }Ð var ops = wordRegexp([]);Ð
var keywords = wordRegexp(["@prefix", "@base", "a"]);Ð var operatorChars = /
[*+\-<>=&|]/;Ð function tokenBase(stream, state) {Ð   var ch = stream.next();Ð
    curPunc = null;Ð   if (ch == "<" && !stream.match(/^[\s\u00a0=]/, false))
{Ð     stream.match(/^[^\s\u00a0>]*>?/);Ð     return "atom";Ð   }Ð   else if
(ch == "\"" || ch == "'") {Ð     state.tokenize = tokenLiteral(ch);Ð
return state.tokenize(stream, state);Ð   }Ð   else if (/[{}\(\),\.;
\[\]]/.test(ch)) {Ð     curPunc = ch;Ð     return null;Ð   }Ð   else if (ch
== "#") {Ð     stream.skipToEnd();Ð     return "comment";Ð   }Ð   else if
(operatorChars.test(ch)) {Ð     stream.eatWhile(operatorChars);Ð     return
null;Ð   }Ð   else if (ch == ":") {Ð         return "operator";Ð       } else
{Ð     stream.eatWhile(/[_\w\d]/);Ð     if(stream.peek() == ":") {Ð
return "variable-3";Ð     } else {Ð            var word = stream.current();Ð
             if(keywords.test(word)) {Ð                        return "meta";Ð
             }Ð            if(ch >= "A" && ch <= "Z") {Ð
return "comment";Ð                } else {Ð                        return
"keyword";Ð                }Ð     }Ð     var word = stream.current();Ð     if
(ops.test(word))Ð       return null;Ð     else if (keywords.test(word))Ð
        return "meta";Ð     elseÐ       return "variable";Ð   }Ð }Ð function
tokenLiteral(quote) {Ð   return function(stream, state) {Ð     var escaped =
false, ch;Ð     while ((ch = stream.next()) != null) {Ð       if (ch == quote
&& !escaped) {Ð         state.tokenize = tokenBase;Ð         break;Ð       }Ð
        escaped = !escaped && ch == "\\";Ð     }Ð     return "string";Ð   };Ð
  }Ð function pushContext(state, type, col) {Ð   state.context = {prev:
state.context, indent: state.indent, col: col, type: type};Ð }Ð function
popContext(state) {Ð   state.indent = state.context.indent;Ð   state.context
= state.context.prev;Ð }Ð return {Ð   startState: function() {Ð     return
{tokenize: tokenBase,Ð             context: null,Ð             indent: 0,Ð
              col: 0};Ð   },Ð   token: function(stream, state) {Ð     if
(stream.sol()) {Ð       if (state.context && state.context.align == null)
state.context.align = false;Ð       state.indent = stream.indentation();Ð
      }Ð     if (stream.eatSpace()) return null;Ð     var style =
state.tokenize(stream, state);Ð     if (style != "comment" && state.context
&& state.context.align == null && state.context.type != "pattern") {Ð
state.context.align = true;Ð     }Ð     if (curPunc == "(")
pushContext(state, ")", stream.column());Ð     else if (curPunc == "[")
pushContext(state, "]", stream.column());Ð     else if (curPunc == "{")
pushContext(state, "}", stream.column());Ð     else if (/
[\]\}\)]/.test(curPunc)) {Ð       while (state.context && state.context.type
== "pattern") popContext(state);Ð       if (state.context && curPunc ==
state.context.type) popContext(state);Ð     }Ð     else if (curPunc == "." &&
state.context && state.context.type == "pattern") popContext(state);Ð
else if (/atom|string|variable/.test(style) && state.context) {Ð       if (/
[\}\]]/.test(state.context.type))Ð         pushContext(state, "pattern",
stream.column());Ð       else if (state.context.type == "pattern" && !
state.context.align) {Ð         state.context.align = true;Ð
state.context.col = stream.column();Ð       }Ð     }Ð     return style;Ð   },Ð
    indent: function(state, textAfter) {Ð     var firstChar = textAfter &&
textAfter.charAt(0);Ð     var context = state.context;Ð     if (/
[\]\}]/.test(firstChar))Ð       while (context && context.type == "pattern")
context = context.prev;Ð
```

```
                        Ð     var closing = context && firstChar ==
context.type;Ð     if (!context)Ð       return 0;Ð     else if (context.type
== "pattern")Ð       return context.col;Ð     else if (context.align)Ð
return context.col + (closing ? 0 : 1);Ð     elseÐ       return
context.indent + (closing ? 0 : indentUnit);Ð   }Ð };Ð});Ð
CodeMirror.defineMIME("text/turtle", "turtle");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\vb\vb.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("vb", function(conf, parserConf) {Ð   var ERRORCLASS =
'error';Ð   function wordRegexp(words) {Ð       return new RegExp("^((" +
words.join(")|(") + "))\\b", "i");Ð   }Ð   var singleOperators = new
RegExp("^[\\+\\-\\*/%&\\\\|\\^~<>!]");Ð   var singleDelimiters = new
RegExp('^[\\(\\)\\[\\]\\{\\}@,:`=;\\.]');Ð   var doubleOperators = new
RegExp("^((==)|(<>)|(<=)|(>=)|(<>)|(<<)|(>>)|(//)|(\\*\\*))");Ð   var
doubleDelimiters = new RegExp("^((\\+=)|(\\-=)|(\\*=)|(%=)|(/=)|(&=)|(\\|=)|(\
\^=))");Ð   var tripleDelimiters = new RegExp("^((//=)|(>>=)|(<<=)|(\\*\
\*=))");Ð   var identifiers = new RegExp("^[_A-Za-z][_A-Za-z0-9]*");Ð   var
openingKeywords = ['class','module',
'sub','enum','select','while','if','function',  'get','set','property',
'try'];Ð   var middleKeywords = ['else','elseif','case', 'catch'];Ð   var
endKeywords = ['next','loop'];Ð   var wordOperators = wordRegexp(['and',
'or', 'not', 'xor', 'in']);Ð   var commonkeywords = ['as', 'dim', 'break',
'continue','optional', 'then',  'until',Ð                          'goto',
'byval','byref','new','handles','property', 'return',Ð
                          'const','private', 'protected', 'friend', 'public',
'shared', 'static', 'true','false'];Ð   var commontypes =
['integer','string','double','decimal','boolean','short','char',
'float','single'];Ð   var keywords = wordRegexp(commonkeywords);Ð   var types
= wordRegexp(commontypes);Ð   var stringPrefixes = '"';Ð   var opening =
wordRegexp(openingKeywords);Ð   var middle = wordRegexp(middleKeywords);Ð
var closing = wordRegexp(endKeywords);Ð   var doubleClosing =
wordRegexp(['end']);Ð   var doOpening = wordRegexp(['do']);Ð   var indentInfo
= null;Ð   function indent(_stream, state) {Ð     state.currentIndent++;Ð   }Ð
    function dedent(_stream, state) {Ð     state.currentIndent--;Ð   }Ð   //
tokenizers Ð   function tokenBase(stream, state) {Ð       if
(stream.eatSpace()) {Ð           return null;Ð       }Ð       var ch =
stream.peek();Ð       // Handle CommentsÐ       if (ch === "'") {Ð
stream.skipToEnd();Ð           return 'comment';Ð       }Ð       // Handle
Number LiteralsÐ       if (stream.match(/^((&H)|(&O))?[0-9\.a-f]/i, false)) {Ð
            var floatLiteral = false;Ð           // FloatsÐ           if
(stream.match(/^\d*\.\d+F?/i)) { floatLiteral = true; }Ð           else if
(stream.match(/^\d+\.\d*F?/)) { floatLiteral = true; }Ð           else if
(stream.match(/^\.\d+F?/)) { floatLiteral = true; }Ð           if
(floatLiteral) {Ð               // Float literals may be "imaginary"Ð
                stream.eat(/J/i);Ð               return 'number';Ð           }Ð
            // IntegersÐ           var intLiteral = false;Ð           // HexÐ
            if (stream.match(/^&H[0-9a-f]+/i)) { intLiteral = true; }Ð
            // OctalÐ           else if (stream.match(/^&O[0-7]+/i))
{ intLiteral = true; }Ð           // DecimalÐ           else if
(stream.match(/^[1-9]\d*F?/)) {Ð               // Decimal literals may be
"imaginary"Ð               stream.eat(/J/i);Ð               // TODO - Can you
have imaginary longs?Ð               intLiteral = true;Ð           }Ð
            // Zero by itself with no other piece of number.Ð           else
if (stream.match(/^0(?![\dx])/i)) { intLiteral = true; }Ð           if
(intLiteral) {Ð               // Integer literals may be "long"Ð
                stream.eat(/L/i);Ð               return 'number';Ð           }Ð
        }Ð       // Handle StringsÐ       if (stream.match(stringPrefixes)) {Ð
            state.tokenize = tokenStringFactory(stream.current());Ð
return state.tokenize(stream, state);Ð       }Ð       // Handle operators and
DelimitersÐ       if (stream.match(tripleDelimiters) ||
stream.match(doubleDelimiters)) {Ð
```

```
                                                return null;Ð       }Ð       if
(stream.match(doubleOperators)Ð           || stream.match(singleOperators)Ð
            || stream.match(wordOperators)) {Ð           return 'operator';Ð
        }Ð       if (stream.match(singleDelimiters)) {Ð           return null;Ð
        }Ð       if (stream.match(doOpening)) {Ð
indent(stream,state);Ð           state.doInCurrentLine = true;Ð
return 'keyword';Ð       }Ð       if (stream.match(opening)) {Ð           if
(! state.doInCurrentLine)Ð             indent(stream,state);Ð           elseÐ
              state.doInCurrentLine = false;Ð           return 'keyword';Ð
        }Ð       if (stream.match(middle)) {Ð           return 'keyword';Ð
        }Ð       if (stream.match(doubleClosing)) {Ð
dedent(stream,state);Ð           dedent(stream,state);Ð           return
'keyword';Ð       }Ð       if (stream.match(closing)) {Ð
dedent(stream,state);Ð           return 'keyword';Ð       }Ð       if
(stream.match(types)) {Ð           return 'keyword';Ð       }Ð       if
(stream.match(keywords)) {Ð           return 'keyword';Ð       }Ð       if
(stream.match(identifiers)) {Ð           return 'variable';Ð       }Ð
        // Handle non-detected itemsÐ       stream.next();Ð       return
ERRORCLASS;Ð   }Ð   function tokenStringFactory(delimiter) {Ð       var
singleline = delimiter.length == 1;Ð       var OUTCLASS = 'string';Ð
return function(stream, state) {Ð           while (!stream.eol()) {Ð
                stream.eatWhile(/[^'"]/);Ð               if
(stream.match(delimiter)) {Ð                   state.tokenize = tokenBase;Ð
                    return OUTCLASS;Ð               } else {Ð
                    stream.eat(/['"]/);Ð               }Ð           }Ð
            if (singleline) {Ð               if
(parserConf.singleLineStringErrors) {Ð                   return ERRORCLASS;Ð
                } else {Ð                   state.tokenize = tokenBase;Ð
                }Ð           }Ð           return OUTCLASS;Ð       };Ð   }Ð
function tokenLexer(stream, state) {Ð       var style =
state.tokenize(stream, state);Ð       var current = stream.current();Ð
        // Handle '.' connected identifiersÐ       if (current === '.') {Ð
            style = state.tokenize(stream, state);Ð           current =
stream.current();Ð           if (style === 'variable') {Ð
return 'variable';Ð           } else {Ð               return ERRORCLASS;Ð
            }Ð       }Ð       var delimiter_index = '[({'.indexOf(current);Ð
        if (delimiter_index !== -1) {Ð           indent(stream, state );Ð
        }Ð       if (indentInfo === 'dedent') {Ð           if (dedent(stream,
state)) {Ð               return ERRORCLASS;Ð           }Ð       }Ð
delimiter_index = '])}'.indexOf(current);Ð       if (delimiter_index !== -1) {Ð
            if (dedent(stream, state)) {Ð               return ERRORCLASS;Ð
            }Ð       }Ð       return style;Ð   }Ð   var external = {Ð
electricChars:"dDpPtTfFeE ",Ð       startState: function() {Ð
return {Ð             tokenize: tokenBase,Ð             lastToken: null,Ð
              currentIndent: 0,Ð             nextLineIndent: 0,Ð
doInCurrentLine: falseÐ         };Ð       },Ð       token: function(stream,
state) {Ð           if (stream.sol()) {Ð             state.currentIndent +=
state.nextLineIndent;Ð             state.nextLineIndent = 0;Ð
state.doInCurrentLine = 0;Ð           }Ð           var style =
tokenLexer(stream, state);Ð           state.lastToken = {style:style,
content: stream.current()};Ð           return style;Ð       },Ð       indent:
function(state, textAfter) {Ð           var trueText = textAfter.replace(/
^\s+|\s+$/g, '') ;Ð           if (trueText.match(closing) ||
trueText.match(doubleClosing) || trueText.match(middle)) return
conf.indentUnit*(state.currentIndent-1);Ð           if(state.currentIndent <
0) return 0;Ð           return state.currentIndent * conf.indentUnit;Ð       }Ð
    };Ð   return external;Ð});ÐodeMirror.defineMIME("text/x-vb", "vb");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\vbscript\vbscript.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð* For extra ASP classic
objects, initialize CodeMirror instance with this option: Ð   isASP: true Ð E.G.: Ð
    var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
        lineNumbers: true,Ð       isASP: trueÐ     });Ð /Ð (function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("vbscript", function(conf, parserConf) {Ð   var
ERRORCLASS = 'error';Ð   function wordRegexp(words) {Ð       return new
RegExp("^((" + words.join(")|(") + "))\\b", "i");Ð   }Ð   var singleOperators
= new RegExp("^[\\+\\-\\*/&\\\\\\^<>=]");Ð   var doubleOperators = new
RegExp("^((<>)|(<=)|(>=))");Ð   var singleDelimiters = new RegExp('^[\\.,]');Ð
    var brakets = new RegExp('^[\\(\\)]');Ð   var identifiers = new
RegExp("^[A-Za-z][_A-Za-z0-9]*");Ð   var openingKeywords =
['class','sub','select','while','if','function', 'property', 'with', 'for'];Ð
    var middleKeywords = ['else','elseif','case'];Ð   var endKeywords =
['next','loop','wend'];Ð   var wordOperators = wordRegexp(['and', 'or',
'not', 'xor', 'is', 'mod', 'eqv', 'imp']);Ð   var commonkeywords = ['dim',
'redim', 'then',  'until', 'randomize',Ð
'byval','byref','new','property', 'exit', 'in',Ð
'const','private', 'public',Ð                          'get','set','let',
'stop', 'on error resume next', 'on error goto 0', 'option explicit', 'call',
'me'];Ð   //This list was from: http://msdn.microsoft.com/en-us/library/
f8tbc79x(v=vs.84).aspx Ð   var atomWords = ['true', 'false', 'nothing',
'empty', 'null'];Ð   //This list was from: http://msdn.microsoft.com/en-us/
library/3ca8tfek(v=vs.84).aspx Ð   var builtinFuncsWords = ['abs', 'array',
'asc', 'atn', 'cbool', 'cbyte', 'ccur', 'cdate', 'cdbl', 'chr', 'cint',
'clng', 'cos', 'csng', 'cstr', 'date', 'dateadd', 'datediff', 'datepart',Ð
                        'dateserial', 'datevalue', 'day', 'escape', 'eval',
'execute', 'exp', 'filter', 'formatcurrency', 'formatdatetime',
'formatnumber', 'formatpercent', 'getlocale', 'getobject',Ð
                        'getref', 'hex', 'hour', 'inputbox', 'instr',
'instrrev', 'int', 'fix', 'isarray', 'isdate', 'isempty', 'isnull',
'isnumeric', 'isobject', 'join', 'lbound', 'lcase', 'left',Ð
                        'len', 'loadpicture', 'log', 'ltrim', 'rtrim',
'trim', 'maths', 'mid', 'minute', 'month', 'monthname', 'msgbox', 'now',
'oct', 'replace', 'rgb', 'right', 'rnd', 'round',Ð
'scriptengine', 'scriptenginebuildversion', 'scriptenginemajorversion',
'scriptengineminorversion', 'second', 'setlocale', 'sgn', 'sin', 'space',
'split', 'sqr', 'strcomp',Ð                       'string', 'strreverse',
'tan', 'time', 'timer', 'timeserial', 'timevalue', 'typename', 'ubound',
'ucase', 'unescape', 'vartype', 'weekday', 'weekdayname', 'year'];Ð   //This
list was from: http://msdn.microsoft.com/en-us/library/ydz4cfk3(v=vs.84).aspx Ð
    var builtinConsts = ['vbBlack', 'vbRed', 'vbGreen', 'vbYellow', 'vbBlue',
'vbMagenta', 'vbCyan', 'vbWhite', 'vbBinaryCompare', 'vbTextCompare',Ð
                         'vbSunday', 'vbMonday', 'vbTuesday', 'vbWednesday',
'vbThursday', 'vbFriday', 'vbSaturday', 'vbUseSystemDayOfWeek',
'vbFirstJan1', 'vbFirstFourDays', 'vbFirstFullWeek',Ð
'vbGeneralDate', 'vbLongDate', 'vbShortDate', 'vbLongTime', 'vbShortTime',
'vbObjectError',Ð                       'vbOKOnly', 'vbOKCancel',
'vbAbortRetryIgnore', 'vbYesNoCancel', 'vbYesNo', 'vbRetryCancel',
'vbCritical', 'vbQuestion', 'vbExclamation', 'vbInformation',
'vbDefaultButton1', 'vbDefaultButton2',Ð
'vbDefaultButton3', 'vbDefaultButton4', 'vbApplicationModal',
'vbSystemModal', 'vbOK', 'vbCancel', 'vbAbort', 'vbRetry', 'vbIgnore',
'vbYes', 'vbNo',Ð                       'vbCr', 'VbCrLf', 'vbFormFeed',
'vbLf', 'vbNewLine', 'vbNullChar', 'vbNullString', 'vbTab', 'vbVerticalTab',
```

'vbUseDefault', 'vbTrue', 'vbFalse',Ð 'vbEmpty', 'vbNull', 'vbInteger', 'vbLong', 'vbSingle', 'vbDouble', 'vbCurrency', 'vbDate', 'vbString', 'vbObject', 'vbError', 'vbBoolean', 'vbVariant', 'vbDataObject', 'vbDecimal', 'vbByte', 'vbArray'];Ð //This list was from: http://msdn.microsoft.com/en-us/library/hkc375ea(v=vs.84).aspxÐ var builtinObjsWords = ['WScript', 'err', 'debug', 'RegExp'];Ð var knownProperties = ['description', 'firstindex', 'global', 'helpcontext', 'helpfile', 'ignorecase', 'length', 'number', 'pattern', 'source', 'value', 'count'];Ð var knownMethods = ['clear', 'execute', 'raise', 'replace', 'test', 'write', 'writeline', 'close', 'open', 'state', 'eof', 'update', 'addnew', 'end', 'createobject', 'quit'];Ð var aspBuiltinObjsWords = ['server', 'response', 'request', 'session', 'application'];Ð var aspKnownProperties = ['buffer', 'cachecontrol', 'charset', 'contenttype', 'expires', 'expiresabsolute', 'isclientconnected', 'pics', 'status', // responseÐ 'clientcertificate', 'cookies', 'form', 'querystring', 'servervariables', 'totalbytes', //requestÐ 'contents', 'staticobjects', //applicationÐ 'codepage', 'lcid', 'sessionid', 'timeout', // sessionÐ 'scripttimeout']; //serverÐ var aspKnownMethods = ['addheader', 'appendtolog', 'binarywrite', 'end', 'flush', 'redirect', //responseÐ 'binaryread', //requestÐ 'remove', 'removeall', 'lock', 'unlock', // applicationÐ 'abandon', //sessionÐ 'getlasterror', 'htmlencode', 'mappath', 'transfer', 'urlencode']; //serverÐ var knownWords = knownMethods.concat(knownProperties);Ð builtinObjsWords = builtinObjsWords.concat(builtinConsts);Ð if (conf.isASP){Ð builtinObjsWords = builtinObjsWords.concat(aspBuiltinObjsWords);Ð knownWords = knownWords.concat(aspKnownMethods, aspKnownProperties);Ð };Ð var keywords = wordRegexp(commonkeywords);Ð var atoms = wordRegexp(atomWords);Ð var builtinFuncs = wordRegexp(builtinFuncsWords);Ð var builtinObjs = wordRegexp(builtinObjsWords);Ð var known = wordRegexp(knownWords);Ð var stringPrefixes = '"';Ð var opening = wordRegexp(openingKeywords);Ð var middle = wordRegexp(middleKeywords);Ð var closing = wordRegexp(endKeywords);Ð var doubleClosing = wordRegexp(['end']);Ð var doOpening = wordRegexp(['do']);Ð var noIndentWords = wordRegexp(['on error resume next', 'exit']);Ð var comment = wordRegexp(['rem']);Ð function indent(_stream, state) {Ð state.currentIndent++;Ð }Ð function dedent(_stream, state) {Ð state.currentIndent--;Ð }Ð // tokenizersÐ function tokenBase(stream, state) {Ð if (stream.eatSpace()) {Ð return 'space';Ð //return null;Ð }Ð var ch = stream.peek();Ð // Handle CommentsÐ if (ch === "'") {Ð stream.skipToEnd();Ð return 'comment';Ð }Ð if (stream.match(comment)){Ð stream.skipToEnd();Ð return 'comment';Ð }Ð // Handle Number LiteralsÐ if (stream.match(/^((&H)|(&O))?[0-9\.]/i, false) && !stream.match(/^((&H)|(&O))?[0-9\.]+[a-z_]/i, false)) {Ð var floatLiteral = false;Ð // FloatsÐ if (stream.match(/^\d*\.\d+/i)) { floatLiteral = true; }Ð else if (stream.match(/^\d+\.\d*/)) { floatLiteral = true; }Ð else if (stream.match(/^\.\d+/)) { floatLiteral = true; }Ð if (floatLiteral) {Ð // Float literals may be "imaginary"Ð stream.eat(/J/i);Ð return 'number';Ð }Ð // IntegersÐ var intLiteral = false;Ð // HexÐ if (stream.match(/^&H[0-9a-f]+/i)) { intLiteral = true; }Ð // OctalÐ else if (stream.match(/^&O[0-7]+/i)) { intLiteral = true; }Ð // DecimalÐ else if (stream.match(/^[1-9]\d*F?/)) {Ð // Decimal literals may be "imaginary"Ð stream.eat(/J/i);Ð // TODO - Can you have imaginary longs?Ð

```
                                    intLiteral = true;Ð           }Ð
            // Zero by itself with no other piece of number.Ð           else
if (stream.match(/^0(?![\dx])/i)) { intLiteral = true; }Ð          if
(intLiteral) {Ð               // Integer literals may be "long"Ð
                stream.eat(/L/i);Ð               return 'number';Ð           }Ð
        }Ð       // Handle StringsÐ       if (stream.match(stringPrefixes)) {Ð
            state.tokenize = tokenStringFactory(stream.current());Ð
return state.tokenize(stream, state);Ð       }Ð       // Handle operators and
DelimitersÐ       if (stream.match(doubleOperators)Ð           ||
stream.match(singleOperators)Ð           || stream.match(wordOperators)) {Ð
            return 'operator';Ð       }Ð       if
(stream.match(singleDelimiters)) {Ð           return null;Ð       }Ð       if
(stream.match(brakets)) {Ð           return "bracket";Ð       }Ð       if
(stream.match(noIndentWords)) {Ð           state.doInCurrentLine = true;Ð
            return 'keyword';Ð       }Ð       if (stream.match(doOpening)) {Ð
            indent(stream,state);Ð           state.doInCurrentLine = true;Ð
            return 'keyword';Ð       }Ð       if (stream.match(opening)) {Ð
            if (! state.doInCurrentLine)Ð             indent(stream,state);Ð
            elseÐ             state.doInCurrentLine = false;Ð
return 'keyword';Ð       }Ð       if (stream.match(middle)) {Ð
return 'keyword';Ð       }Ð       if (stream.match(doubleClosing)) {Ð
            dedent(stream,state);Ð           dedent(stream,state);Ð
return 'keyword';Ð       }Ð       if (stream.match(closing)) {Ð           if
(! state.doInCurrentLine)Ð             dedent(stream,state);Ð           elseÐ
              state.doInCurrentLine = false;Ð           return 'keyword';Ð
        }Ð       if (stream.match(keywords)) {Ð           return 'keyword';Ð
        }Ð       if (stream.match(atoms)) {Ð           return 'atom';Ð       }Ð
        if (stream.match(known)) {Ð           return 'variable-2';Ð       }Ð
        if (stream.match(builtinFuncs)) {Ð           return 'builtin';Ð
        }Ð       if (stream.match(builtinObjs)){Ð           return
'variable-2';Ð       }Ð       if (stream.match(identifiers)) {Ð
return 'variable';Ð       }Ð       // Handle non-detected itemsÐ
stream.next();Ð       return ERRORCLASS;Ð   }Ð   function
tokenStringFactory(delimiter) {Ð       var singleline = delimiter.length == 1;Ð
        var OUTCLASS = 'string';Ð       return function(stream, state) {Ð
            while (!stream.eol()) {Ð               stream.eatWhile(/[^'"]/);Ð
                if (stream.match(delimiter)) {Ð
state.tokenize = tokenBase;Ð                   return OUTCLASS;Ð
                } else {Ð                   stream.eat(/['"]/);Ð
                }Ð           }Ð           if (singleline) {Ð           if
(parserConf.singleLineStringErrors) {Ð                   return ERRORCLASS;Ð
                } else {Ð                   state.tokenize = tokenBase;Ð
                }Ð           }Ð           return OUTCLASS;Ð       };Ð   }Ð
function tokenLexer(stream, state) {Ð       var style =
state.tokenize(stream, state);Ð       var current = stream.current();Ð
        // Handle '.' connected identifiersÐ       if (current === '.') {Ð
            style = state.tokenize(stream, state);Ð           current =
stream.current();Ð           if (style && (style.substr(0, 8) === 'variable'
|| style==='builtin' || style==='keyword')){//||
knownWords.indexOf(current.substring(1)) > -1) {Ð           if (style ===
'builtin' || style === 'keyword') style='variable';Ð           if
(knownWords.indexOf(current.substr(1)) > -1) style='variable-2';Ð
                return style;Ð           } else {Ð           return
ERRORCLASS;Ð           }Ð       }Ð       return style;Ð   }Ð   var external =
{Ð       electricChars:"dDpPtTfFeE ",Ð       startState: function() {Ð
            return {Ð           tokenize: tokenBase,Ð
lastToken: null,Ð           currentIndent: 0,Ð           nextLineIndent:
0,Ð           doInCurrentLine: false,Ð           ignoreKeyword: falseÐ
          };Ð       },Ð       token: function(stream, state) {Ð           if
(stream.sol()) {Ð
```

```
                                state.currentIndent += state.nextLineIndent;Ð
              state.nextLineIndent = 0;Ð             state.doInCurrentLine =
0;Ð           }Ð           var style = tokenLexer(stream, state);Ð
state.lastToken = {style:style, content: stream.current()};Ð           if
(style=='space') style=null;Ð           return style;Ð       },Ð
indent: function(state, textAfter) {Ð           var trueText =
textAfter.replace(/^\s+|\s+$/g, '') ;Ð           if (trueText.match(closing)
|| trueText.match(doubleClosing) || trueText.match(middle)) return
conf.indentUnit*(state.currentIndent-1);Ð           if(state.currentIndent <
0) return 0;Ð           return state.currentIndent * conf.indentUnit;Ð       }Ð
    };Ð   return external;Ð});ÐodeMirror.defineMIME("text/vbscript",
"vbscript");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\velocity\velocity.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("velocity", function() {Ð   function parseWords(str) {Ð
        var obj = {}, words = str.split(" ");Ð       for (var i = 0; i <
words.length; ++i) obj[words[i]] = true;Ð       return obj;Ð   }Ð   var
keywords = parseWords("#end #else #break #stop #[[ #]] " +Ð
                              "#{end} #{else} #{break} #{stop}");Ð   var
functions = parseWords("#if #elseif #foreach #set #include #parse #macro
#define #evaluate " +Ð                              "#{if} #{elseif}
#{foreach} #{set} #{include} #{parse} #{macro} #{define} #{evaluate}");Ð
var specials = parseWords("$foreach.count $foreach.hasNext $foreach.first
$foreach.last $foreach.topmost $foreach.parent.count $foreach.parent.hasNext
$foreach.parent.first $foreach.parent.last $foreach.parent $velocityCount $!
bodyContent $bodyContent");Ð   var isOperatorChar = /[+\-*&%=<>!?:\/|]/;Ð
function chain(stream, state, f) {Ð       state.tokenize = f;Ð       return
f(stream, state);Ð   }Ð   function tokenBase(stream, state) {Ð       var
beforeParams = state.beforeParams;Ð       state.beforeParams = false;Ð
var ch = stream.next();Ð       // start of unparsed string?Ð       if ((ch ==
"'") && state.inParams) {Ð           state.lastTokenWasBuiltin = false;Ð
            return chain(stream, state, tokenString(ch));Ð       }Ð       //
start of parsed string?Ð       else if ((ch == '"')) {Ð
state.lastTokenWasBuiltin = false;Ð           if (state.inString) {Ð
                state.inString = false;Ð               return "string";Ð
            }Ð           else if (state.inParams)Ð               return
chain(stream, state, tokenString(ch));Ð       }Ð       // is it one of the
special signs []{}().,;? Seperator?Ð       else if (/[\[\]{}\(\),;
\.]/.test(ch)) {Ð           if (ch == "(" && beforeParams)Ð
state.inParams = true;Ð           else if (ch == ")") {Ð
state.inParams = false;Ð               state.lastTokenWasBuiltin = true;Ð
            }Ð           return null;Ð       }Ð       // start of a number
value?Ð       else if (/\d/.test(ch)) {Ð           state.lastTokenWasBuiltin
= false;Ð           stream.eatWhile(/[\w\.]/);Ð           return "number";Ð
        }Ð       // multi line comment?Ð       else if (ch == "#" &&
stream.eat("*")) {Ð           state.lastTokenWasBuiltin = false;Ð
return chain(stream, state, tokenComment);Ð       }Ð       // unparsed
content?Ð       else if (ch == "#" && stream.match(/ *\[ *\[/)) {Ð
state.lastTokenWasBuiltin = false;Ð           return chain(stream, state,
tokenUnparsed);Ð       }Ð       // single line comment?Ð       else if (ch ==
"#" && stream.eat("#")) {Ð           state.lastTokenWasBuiltin = false;Ð
            stream.skipToEnd();Ð           return "comment";Ð       }Ð
        // variable?Ð       else if (ch == "$") {Ð           stream.eatWhile(/
[\w\d\$_\.{}]/);Ð           // is it one of the specials?Ð           if
(specials && specials.propertyIsEnumerable(stream.current())) {Ð
                return "keyword";Ð           }Ð           else {Ð
                state.lastTokenWasBuiltin = true;Ð
state.beforeParams = true;Ð               return "builtin";Ð           }Ð
        }Ð       // is it a operator?Ð       else if
(isOperatorChar.test(ch)) {Ð           state.lastTokenWasBuiltin = false;Ð
            stream.eatWhile(isOperatorChar);Ð           return "operator";Ð
        }Ð       else {Ð           // get the whole wordÐ
stream.eatWhile(/[\w\$_{}@]/);Ð           var word = stream.current();Ð
            // is it one of the listed keywords?Ð           if (keywords &&
keywords.propertyIsEnumerable(word))Ð               return "keyword";Ð
            // is it one of the listed functions?Ð           if (functions &&
functions.propertyIsEnumerable(word) ||Ð
```

```
(stream.current().match(/^#@?[a-z0-9_]+ *$/i) && stream.peek()=="(") &&Ð
                    !(functions &&
functions.propertyIsEnumerable(word.toLowerCase()))) {Ð
state.beforeParams = true;Ð              state.lastTokenWasBuiltin = false;Ð
                return "keyword";Ð          }Ð          if (state.inString)
{Ð               state.lastTokenWasBuiltin = false;Ð              return
"string";Ð          }Ð          if (stream.pos > word.length &&
stream.string.charAt(stream.pos-word.length-1)=="." &&
state.lastTokenWasBuiltin)Ð              return "builtin";Ð          //
default: just a "word"Ð          state.lastTokenWasBuiltin = false;Ð
            return null;Ð       }Ð   }Ð   function tokenString(quote) {Ð
        return function(stream, state) {Ð          var escaped = false,
next, end = false;Ð          while ((next = stream.next()) != null) {Ð
                if ((next == quote) && !escaped) {Ð                  end =
true;Ð                    break;Ð              }Ð              if
(quote=='"' && stream.peek() == '$' && !escaped) {Ð
state.inString = true;Ð                  end = true;Ð
break;Ð              }Ð              escaped = !escaped && next == "\\";Ð
            }Ð          if (end) state.tokenize = tokenBase;Ð
return "string";Ð       };Ð   }Ð   function tokenComment(stream, state) {Ð
        var maybeEnd = false, ch;Ð       while (ch = stream.next()) {Ð
            if (ch == "#" && maybeEnd) {Ð              state.tokenize =
tokenBase;Ð              break;Ð          }Ð          maybeEnd = (ch ==
"*");Ð       }Ð       return "comment";Ð   }Ð   function
tokenUnparsed(stream, state) {Ð       var maybeEnd = 0, ch;Ð       while (ch
= stream.next()) {Ð          if (ch == "#" && maybeEnd == 2) {Ð
                state.tokenize = tokenBase;Ð              break;Ð          }Ð
            if (ch == "]")Ð              maybeEnd++;Ð          else if (ch !
= " ")Ð              maybeEnd = 0;Ð       }Ð       return "meta";Ð   }Ð   //
InterfaceÐ   return {Ð       startState: function() {Ð          return {Ð
                tokenize: tokenBase,Ð              beforeParams: false,Ð
                inParams: false,Ð              inString: false,Ð
                lastTokenWasBuiltin: falseÐ          };Ð       },Ð
token: function(stream, state) {Ð          if (stream.eatSpace()) return
null;Ð          return state.tokenize(stream, state);Ð       },Ð
blockCommentStart: "#*",Ð       blockCommentEnd: "*#",Ð       lineComment:
"##",Ð       fold: "velocity"Ð   };Ð});ÐodeMirror.defineMIME("text/velocity",
"velocity");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\verilog\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({indentUnit: 4}, "verilog");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT("binary_literals",Ð    "[number 1'b0]",Ð    "[number 1'b1]",Ð    "[number
1'bx]",Ð    "[number 1'bz]",Ð    "[number 1'bX]",Ð    "[number 1'bZ]",Ð
"[number 1'B0]",Ð    "[number 1'B1]",Ð    "[number 1'Bx]",Ð    "[number
1'Bz]",Ð    "[number 1'BX]",Ð    "[number 1'BZ]",Ð    "[number 1'b0]",Ð
"[number 1'b1]",Ð    "[number 2'b01]",Ð    "[number 2'bxz]",Ð    "[number
2'b11]",Ð    "[number 2'b10]",Ð    "[number 2'b1Z]",Ð    "[number
12'b0101_0101_0101]",Ð    "[number 1'b 0]",Ð    "[number 'b0101]"Ð );Ð
MT("octal_literals",Ð    "[number 3'o7]",Ð    "[number 3'O7]",Ð    "[number
3'so7]",Ð    "[number 3'SO7]"Ð );Ð MT("decimal_literals",Ð    "[number 0]",Ð
     "[number 1]",Ð    "[number 7]",Ð    "[number 123_456]",Ð    "[number
'd33]",Ð    "[number 8'd255]",Ð    "[number 8'D255]",Ð    "[number 8'sd255]",Ð
     "[number 8'SD255]",Ð    "[number 32'd123]",Ð    "[number 32 'd123]",Ð
"[number 32 'd 123]"Ð );Ð MT("hex_literals",Ð    "[number 4'h0]",Ð
"[number 4'ha]",Ð    "[number 4'hF]",Ð    "[number 4'hx]",Ð    "[number
4'hz]",Ð    "[number 4'hX]",Ð    "[number 4'hZ]",Ð    "[number 32'hdc78]",Ð
     "[number 32'hDC78]",Ð    "[number 32 'hDC78]",Ð    "[number 32'h DC78]",Ð
     "[number 32 'h DC78]",Ð    "[number 32'h44x7]",Ð    "[number 32'hFFF?]"Ð
  );Ð MT("real_number_literals",Ð    "[number 1.2]",Ð    "[number 0.1]",Ð
"[number 2394.26331]",Ð    "[number 1.2E12]",Ð    "[number 1.2e12]",Ð
"[number 1.30e-2]",Ð    "[number 0.1e-0]",Ð    "[number 23E10]",Ð    "[number
29E-2]",Ð    "[number 236.123_763_e-12]"Ð );Ð MT("operators",Ð    "[meta ^]"Ð
  );Ð MT("keywords",Ð    "[keyword logic]",Ð    "[keyword logic] [variable
foo]",Ð    "[keyword reg] [variable abc]"Ð );Ð MT("variables",Ð    "[variable
_leading_underscore]",Ð    "[variable _if]",Ð    "[number 12] [variable foo]",Ð
     "[variable foo] [number 14]"Ð );Ð MT("tick_defines",Ð    "[def `FOO]",Ð
     "[def `foo]",Ð    "[def `FOO_bar]"Ð );Ð MT("system_calls",Ð    "[meta
$display]",Ð    "[meta $vpi_printf]"Ð );Ð MT("line_comment", "[comment //
Hello world]");Ð // Alignment testsÐ MT("align_port_map_style1",Ð    /**Ð
* mod mod(.a(a),Ð     *         .b(b)Ð     *         );Ð     */Ð    "[variable
mod] [variable mod][bracket (].[variable a][bracket (][variable a]
[bracket )],",Ð    "        .[variable b][bracket (][variable b][bracket )]",Ð
     "       [bracket )];",Ð    ""Ð );Ð MT("align_port_map_style2",Ð    /**Ð
      * mod mod(Ð     *     .a(a),Ð     *     .b(b)Ð     * );Ð     */Ð
"[variable mod] [variable mod][bracket (]",Ð    "    .[variable a][bracket (]
[variable a][bracket )],",Ð    "    .[variable b][bracket (][variable b]
[bracket )]",Ð    "[bracket )];",Ð    ""Ð );Ð // Indentation testsÐ
MT("indent_single_statement_if",Ð     "[keyword if] [bracket (][variable foo]
[bracket )]",Ð     "    [keyword break];",Ð     ""Ð );Ð
MT("no_indent_after_single_line_if",Ð     "[keyword if] [bracket (][variable
foo][bracket )] [keyword break];",Ð     ""Ð );Ð
MT("indent_after_if_begin_same_line",Ð     "[keyword if] [bracket (][variable
foo][bracket )] [keyword begin]",Ð     "    [keyword break];",Ð
"    [keyword break];",Ð     "[keyword end]",Ð     ""Ð );Ð
MT("indent_after_if_begin_next_line",Ð     "[keyword if] [bracket (][variable
foo][bracket )]",Ð     "    [keyword begin]",Ð     "        [keyword break];",Ð
      "        [keyword break];",Ð     "    [keyword end]",Ð     ""Ð );Ð
MT("indent_single_statement_if_else",Ð     "[keyword if] [bracket (][variable
foo][bracket )]",Ð     "    [keyword break];",Ð     "[keyword else]",Ð
"    [keyword break];",Ð     ""Ð );Ð MT("indent_if_else_begin_same_line",Ð
      "[keyword if] [bracket (][variable foo][bracket )] [keyword begin]",Ð
      "    [keyword break];",Ð     "    [keyword break];",Ð     "[keyword
end] [keyword else] [keyword begin]",Ð     "    [keyword break];",Ð
"    [keyword break];",Ð     "[keyword end]",Ð     ""Ð );Ð
MT("indent_if_else_begin_next_line",Ð     "[keyword if] [bracket (][variable
foo][bracket )]",Ð
```

```
                        "    [keyword begin]",Ð     "        [keyword break];",Ð
      "        [keyword break];",Ð     "    [keyword end]",Ð     "[keyword
else]",Ð     "    [keyword begin]",Ð     "        [keyword break];",Ð
"        [keyword break];",Ð     "    [keyword end]",Ð     ""Ð );Ð
MT("indent_if_nested_without_begin",Ð     "[keyword if] [bracket (][variable
foo][bracket )]",Ð     "    [keyword if] [bracket (][variable foo]
[bracket )]",Ð     "        [keyword if] [bracket (][variable foo]
[bracket )]",Ð     "            [keyword break];",Ð     ""Ð );Ð
MT("indent_case",Ð     "[keyword case] [bracket (][variable state]
[bracket )]",Ð     "    [variable FOO]:",Ð     "        [keyword break];",Ð
      "    [variable BAR]:",Ð     "        [keyword break];",Ð     "[keyword
endcase]",Ð     ""Ð );Ð MT("unindent_after_end_with_preceding_text",Ð
"[keyword begin]",Ð     "    [keyword break]; [keyword end]",Ð     ""Ð );Ð
MT("export_function_one_line_does_not_indent",Ð    "[keyword export] [string
\"DPI-C\"] [keyword function] [variable helloFromSV];",Ð    ""Ð );Ð
MT("export_task_one_line_does_not_indent",Ð    "[keyword export] [string
\"DPI-C\"] [keyword task] [variable helloFromSV];",Ð    ""Ð );Ð
MT("export_function_two_lines_indents_properly",Ð   "[keyword export]",Ð
"    [string \"DPI-C\"] [keyword function] [variable helloFromSV];",Ð   ""Ð );Ð
  MT("export_task_two_lines_indents_properly",Ð   "[keyword export]",Ð
"    [string \"DPI-C\"] [keyword task] [variable helloFromSV];",Ð   ""Ð );Ð
MT("import_function_one_line_does_not_indent",Ð   "[keyword import] [string
\"DPI-C\"] [keyword function] [variable helloFromC];",Ð   ""Ð );Ð
MT("import_task_one_line_does_not_indent",Ð   "[keyword import] [string \"DPI-
C\"] [keyword task] [variable helloFromC];",Ð   ""Ð );Ð
MT("import_package_single_line_does_not_indent",Ð   "[keyword import]
[variable p]::[variable x];",Ð   "[keyword import] [variable p]::[variable
y];",Ð   ""Ð );Ð MT("covergoup_with_function_indents_properly",Ð   "[keyword
covergroup] [variable cg] [keyword with] [keyword function] [variable sample]
[bracket (][keyword bit] [variable b][bracket )];",Ð   "    [variable c] :
[keyword coverpoint] [variable c];",Ð   "[keyword endgroup]: [variable cg]",Ð
    ""Ð );Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\verilog\verilog.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJSÐ
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMDÐ   define(["../../lib/codemirror"], mod);Ð else //
Plain browser envÐ   mod(CodeMirror);Ð})(function(CodeMirror) {Ð"use strict";Ð
CodeMirror.defineMode("verilog", function(config, parserConfig) {Ð var
indentUnit = config.indentUnit,Ð     statementIndentUnit =
parserConfig.statementIndentUnit || indentUnit,Ð     dontAlignCalls =
parserConfig.dontAlignCalls,Ð     noIndentKeywords =
parserConfig.noIndentKeywords || [],Ð     multiLineStrings =
parserConfig.multiLineStrings;Ð function words(str) {Ð   var obj = {}, words
= str.split(" ");Ð   for (var i = 0; i < words.length; ++i) obj[words[i]] =
true;Ð   return obj;Ð }Ð /**Ð  * Keywords from IEEE 1800-2012Ð  */Ð var
keywords = words(Ð   "accept_on alias always always_comb always_ff
always_latch and assert assign assume automatic before begin bind " +Ð
"bins binsof bit break buf bufif0 bufif1 byte case casex casez cell chandle
checker class clocking cmos config " +Ð   "const constraint context continue
cover covergroup coverpoint cross deassign default defparam design disable " +Ð
    "dist do edge else end endcase endchecker endclass endclocking endconfig
endfunction endgenerate endgroup " +Ð   "endinterface endmodule endpackage
endprimitive endprogram endproperty endspecify endsequence endtable endtask "
+Ð   "enum event eventually expect export extends extern final first_match
for force foreach forever fork forkjoin " +Ð   "function generate genvar
global highz0 highz1 if iff ifnone ignore_bins illegal_bins implements
implies import " +Ð   "incdir include initial inout input inside instance int
integer interconnect interface intersect join join_any " +Ð   "join_none
large let liblist library local localparam logic longint macromodule matches
medium modport module " +Ð   "nand negedge nettype new nexttime nmos nor
noshowcancelled not notif0 notif1 null or output package packed " +Ð
"parameter pmos posedge primitive priority program property protected pull0
pull1 pulldown pullup " +Ð   "pulsestyle_ondetect pulsestyle_onevent pure
rand randc randcase randsequence rcmos real realtime ref reg " +Ð
"reject_on release repeat restrict return rnmos rpmos rtran rtranif0 rtranif1
s_always s_eventually s_nexttime " +Ð   "s_until s_until_with scalared
sequence shortint shortreal showcancelled signed small soft solve specify " +Ð
    "specparam static string strong strong0 strong1 struct super supply0
supply1 sync_accept_on sync_reject_on " +Ð   "table tagged task this
throughout time timeprecision timeunit tran tranif0 tranif1 tri tri0 tri1
triand trior " +Ð   "trireg type typedef union unique unique0 unsigned until
until_with untyped use uwire var vectored virtual void " +Ð   "wait
wait_order wand weak weak0 weak1 while wildcard wire with within wor xnor
xor");Ð /** Operators from IEEE 1800-2012Ð    unary_operator ::=Ð      + | -
| ! | ~ | & | ~& | | | ~| | ^ | ~^ | ^~Ð    binary_operator ::=Ð      + | - |
* | / | % | == | != | === | !== | ==? | !=? | && | || | **Ð      | < | <= | >
| >= | & | | | ^ | ^~ | ~^ | >> | << | >>> | <<<Ð      | -> | <->Ð
inc_or_dec_operator ::= ++ | --Ð    unary_module_path_operator ::=Ð      ! |
~ | & | ~& | | | ~| | ^ | ~^ | ^~Ð    binary_module_path_operator ::=Ð
== | != | && | || | & | | | ^ | ^~ | ~^Ð */Ð var isOperatorChar = /[\+\-\*\/!
~&|^%=?:]/;Ð var isBracketChar = /[\[\]{}()]/;Ð var unsignedNumber = /
\d[0-9_]*/;Ð var decimalLiteral = /\d*\s*'s?d\s*\d[0-9_]*/i;Ð var
binaryLiteral = /\d*\s*'s?b\s*[xz01][xz01_]*/i;Ð var octLiteral = /\d*\s*'s?
o\s*[xz0-7][xz0-7_]*/i;Ð var hexLiteral = /\d*\s*'s?h\s*[0-9a-fxz?][0-9a-fxz?
_]*/i;Ð var realLiteral = /(\d[\d_]*(\.\d[\d_]*)?E-?[\d_]+)|(\d[\d_]*\.
\d[\d_]*)/i;Ð var closingBracketOrWord = /^((\w+)|[)}\]])/;Ð var
closingBracket = /[)}\]]/;Ð var curPunc;Ð var curKeyword;Ð // Block openings
which are closed by a matching keyword in the form of ("end" + keyword)Ð //
E.g. "task" => "endtask"Ð var blockKeywords = words(Ð   "case checker class
clocking config function generate interface module package" +Ð
```

"primitive program property specify sequence table task"Ð);Ð // Opening/closing pairsÐ var openClose = {};Ð for (var keyword in blockKeywords) {Ð openClose[keyword] = "end" + keyword;Ð }Ð openClose["begin"] = "end";Ð openClose["casex"] = "endcase";Ð openClose["casez"] = "endcase";Ð openClose["do"] = "while";Ð openClose["fork"] = "join;join_any;join_none";Ð openClose["covergroup"] = "endgroup";Ð for (var i in noIndentKeywords) {Ð var keyword = noIndentKeywords[i];Ð if (openClose[keyword]) {Ð openClose[keyword] = undefined;Ð }Ð }Ð // Keywords which open statements that are ended with a semi-colonÐ var statementKeywords = words("always always_comb always_ff always_latch assert assign assume else export for foreach forever if import initial repeat while");Ð function tokenBase(stream, state) {Ð var ch = stream.peek();Ð if (/[,;:\.]/.test(ch)) {Ð curPunc = stream.next();Ð return null;Ð }Ð if (isBracketChar.test(ch)) {Ð curPunc = stream.next();Ð return "bracket";Ð }Ð // Macros (tick-defines)Ð if (ch == '`') {Ð stream.next();Ð if (stream.eatWhile(/[\w\$_]/)) {Ð return "def";Ð } else {Ð return null;Ð }Ð }Ð // System callsÐ if (ch == '$') {Ð stream.next();Ð if (stream.eatWhile(/[\w\$_]/)) {Ð return "meta";Ð } else {Ð return null;Ð }Ð }Ð // Time literalsÐ if (ch == '#') {Ð stream.next();Ð stream.eatWhile(/[\d_.]/);Ð return "def";Ð }Ð // StringsÐ if (ch == '"') {Ð stream.next();Ð state.tokenize = tokenString(ch);Ð return state.tokenize(stream, state);Ð }Ð // CommentsÐ if (ch == "/") {Ð stream.next();Ð if (stream.eat("*")) {Ð state.tokenize = tokenComment;Ð return tokenComment(stream, state);Ð }Ð if (stream.eat("/")) {Ð stream.skipToEnd();Ð return "comment";Ð }Ð stream.backUp(1);Ð }Ð // Numeric literalsÐ if (stream.match(realLiteral) ||Ð stream.match(decimalLiteral) ||Ð stream.match(binaryLiteral) ||Ð stream.match(octLiteral) ||Ð stream.match(hexLiteral) ||Ð stream.match(unsignedNumber) ||Ð stream.match(realLiteral)) {Ð return "number";Ð }Ð // OperatorsÐ if (stream.eatWhile(isOperatorChar)) {Ð return "meta";Ð }Ð // Keywords / plain variablesÐ if (stream.eatWhile(/[\w\$_]/)) {Ð var cur = stream.current();Ð if (keywords[cur]) {Ð if (openClose[cur]) {Ð curPunc = "newblock";Ð }Ð if (statementKeywords[cur]) {Ð curPunc = "newstatement";Ð }Ð curKeyword = cur;Ð return "keyword";Ð }Ð return "variable";Ð }Ð stream.next();Ð return null;Ð }Ð function tokenString(quote) {Ð return function(stream, state) {Ð var escaped = false, next, end = false;Ð while ((next = stream.next()) != null) {Ð if (next == quote && !escaped) {end = true; break;}Ð escaped = !escaped && next == "\\";Ð }Ð if (end || !(escaped || multiLineStrings))Ð state.tokenize = tokenBase;Ð return "string";Ð };Ð }Ð function tokenComment(stream, state) {Ð var maybeEnd = false, ch;Ð while (ch = stream.next()) {Ð if (ch == "/" && maybeEnd) {Ð state.tokenize = tokenBase;Ð break;Ð }Ð maybeEnd = (ch == "*");Ð }Ð return "comment";Ð }Ð function Context(indented, column, type, align, prev) {Ð this.indented = indented;Ð this.column = column;Ð this.type = type;Ð this.align = align;Ð this.prev = prev;Ð }Ð function pushContext(state, col, type) {Ð var indent = state.indented;Ð var c = new Context(indent, col, type, null, state.context);Ð return state.context = c;Ð }Ð function popContext(state) {Ð var t = state.context.type;Ð if (t == ")" || t == "]" || t == "}") {Ð state.indented = state.context.indented;Ð }Ð return state.context = state.context.prev;Ð }Ð function isClosing(text, contextClosing) {Ð if (text == contextClosing) {Ð return true;Ð } else {Ð // contextClosing may be mulitple keywords separated by ;Ð var closingKeywords = contextClosing.split(";");Ð for (var i in closingKeywords) {Ð if (text == closingKeywords[i]) {Ð return true;Ð }Ð }Ð return false;Ð }Ð }Ð function buildElectricInputRegEx() {Ð

```
                                // Reindentation should occur on any bracket
char: {}()[]Ð   // or on a match of any of the block closing keywords, atÐ
    // the end of a lineÐ   var allClosings = [];Ð   for (var i in openClose)
{Ð     if (openClose[i]) {Ð       var closings = openClose[i].split(";");Ð
        for (var j in closings) {Ð         allClosings.push(closings[j]);Ð
        }Ð     }Ð   }Ð   var re = new RegExp("[{}()\\[\\]]|(" +
allClosings.join("|") + ")$");Ð   return re;Ð }Ð // InterfaceÐ return {Ð   //
Regex to force current line to reindentÐ   electricInput:
buildElectricInputRegEx(),Ð   startState: function(basecolumn) {Ð     return {Ð
        tokenize: null,Ð       context: new Context((basecolumn || 0) -
indentUnit, 0, "top", false),Ð       indented: 0,Ð       startOfLine: trueÐ
      };Ð   },Ð   token: function(stream, state) {Ð     var ctx =
state.context;Ð     if (stream.sol()) {Ð       if (ctx.align == null)
ctx.align = false;Ð       state.indented = stream.indentation();Ð
state.startOfLine = true;Ð     }Ð     if (stream.eatSpace()) return null;Ð
      curPunc = null;Ð     curKeyword = null;Ð     var style =
(state.tokenize || tokenBase)(stream, state);Ð     if (style == "comment" ||
style == "meta" || style == "variable") return style;Ð     if (ctx.align ==
null) ctx.align = true;Ð     if (curPunc == ctx.type) {Ð
popContext(state);Ð     }Ð     else if ((curPunc == ";" && ctx.type ==
"statement") ||Ð              (ctx.type && isClosing(curKeyword, ctx.type))) {Ð
        ctx = popContext(state);Ð       while (ctx && ctx.type ==
"statement") ctx = popContext(state);Ð     }Ð     else if (curPunc == "{")
{ pushContext(state, stream.column(), "}"); }Ð     else if (curPunc == "[")
{ pushContext(state, stream.column(), "]"); }Ð     else if (curPunc == "(")
{ pushContext(state, stream.column(), ")"); }Ð     else if (ctx && ctx.type
== "endcase" && curPunc == ":") { pushContext(state, stream.column(),
"statement"); }Ð     else if (curPunc == "newstatement") {Ð
pushContext(state, stream.column(), "statement");Ð     } else if (curPunc ==
"newblock") {Ð       if (curKeyword == "function" && ctx && (ctx.type ==
"statement" || ctx.type == "endgroup")) {Ð         // The 'function' keyword
can appear in some other contexts where it actually does notÐ         //
indicate a function (import/export DPI and covergroup definitions).Ð
          // Do nothing in this caseÐ       } else if (curKeyword == "task"
&& ctx && ctx.type == "statement") {Ð         // Same thing for taskÐ       }
else {Ð         var close = openClose[curKeyword];Ð
pushContext(state, stream.column(), close);Ð       }Ð     }Ð
state.startOfLine = false;Ð     return style;Ð   },Ð   indent:
function(state, textAfter) {Ð     if (state.tokenize != tokenBase &&
state.tokenize != null) return CodeMirror.Pass;Ð     var ctx = state.context,
firstChar = textAfter && textAfter.charAt(0);Ð     if (ctx.type ==
"statement" && firstChar == "}") ctx = ctx.prev;Ð     var closing = false;Ð
      var possibleClosing = textAfter.match(closingBracketOrWord);Ð     if
(possibleClosing) {Ð       closing = isClosing(possibleClosing[0], ctx.type);Ð
      }Ð     if (ctx.type == "statement") return ctx.indented + (firstChar ==
"{" ? 0 : statementIndentUnit);Ð     else if (closingBracket.test(ctx.type)
&& ctx.align && !dontAlignCalls) return ctx.column + (closing ? 0 : 1);Ð
else if (ctx.type == ")" && !closing) return ctx.indented +
statementIndentUnit;Ð     else return ctx.indented + (closing ? 0 :
indentUnit);Ð   },Ð   blockCommentStart: "/*",Ð   blockCommentEnd: "*/",Ð
lineComment: "//"Ð };Þ});ÐodeMirror.defineMIME("text/x-verilog", {Ð name:
"verilog"Þ});ÐodeMirror.defineMIME("text/x-systemverilog", {Ð name:
"systemverilog"Þ});Þ});Ð
```

public\assets\js\plugins\codemirror\mode\xml\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function() {Ð var mode =
CodeMirror.getMode({indentUnit: 2}, "xml"), mname = "xml";Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1), mname); }Ð
MT("matching",Ð    "[tag&bracket <][tag top][tag&bracket >]",Ð    "  text",Ð
     "  [tag&bracket <][tag inner][tag&bracket />]",Ð    "[tag&bracket </]
[tag top][tag&bracket >]");Ð MT("nonmatching",Ð    "[tag&bracket <][tag top]
[tag&bracket >]",Ð    "  [tag&bracket <][tag inner][tag&bracket />]",Ð
"  [tag&bracket </][tag&error tip][tag&bracket&error >]");Ð MT("doctype",Ð
"[meta <!doctype foobar>]",Ð    "[tag&bracket <][tag top][tag&bracket />]");Ð
MT("cdata",Ð    "[tag&bracket <][tag top][tag&bracket >]",Ð    "  [atom <!
[CDATA[foo]",Ð    "[atom barbazguh]]]]>]",Ð    "[tag&bracket </][tag top]
[tag&bracket >]");Ð // HTML testsÐ mode = CodeMirror.getMode({indentUnit: 2},
"text/html");Ð MT("selfclose",Ð    "[tag&bracket <][tag html][tag&bracket >]",Ð
     "  [tag&bracket <][tag link] [attribute rel]=[string stylesheet]
[attribute href]=[string \"/foobar\"][tag&bracket >]",Ð    "[tag&bracket </]
[tag html][tag&bracket >]");Ð MT("list",Ð    "[tag&bracket <][tag ol]
[tag&bracket >]",Ð    "  [tag&bracket <][tag li][tag&bracket >]one",Ð
"  [tag&bracket <][tag li][tag&bracket >]two",Ð    "[tag&bracket </][tag ol]
[tag&bracket >]");Ð MT("valueless",Ð    "[tag&bracket <][tag input]
[attribute type]=[string checkbox] [attribute checked][tag&bracket />]");Ð
MT("pThenArticle",Ð    "[tag&bracket <][tag p][tag&bracket >]",Ð    "  foo",Ð
     "[tag&bracket <][tag article][tag&bracket >]bar");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\xml\xml.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð })(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("xml", function(config, parserConfig) {Ð var indentUnit
= config.indentUnit;Ð var multilineTagIndentFactor =
parserConfig.multilineTagIndentFactor || 1;Ð var multilineTagIndentPastTag =
parserConfig.multilineTagIndentPastTag;Ð if (multilineTagIndentPastTag ==
null) multilineTagIndentPastTag = true;Ð var Kludges =
parserConfig.htmlMode ? {Ð   autoSelfClosers: {'area': true, 'base': true,
'br': true, 'col': true, 'command': true,Ð                    'embed': true,
'frame': true, 'hr': true, 'img': true, 'input': true,Ð
'keygen': true, 'link': true, 'meta': true, 'param': true, 'source': true,Ð
                      'track': true, 'wbr': true, 'menuitem': true},Ð
implicitlyClosed: {'dd': true, 'li': true, 'optgroup': true, 'option': true,
'p': true,Ð                      'rp': true, 'rt': true, 'tbody': true, 'td':
true, 'tfoot': true,Ð                          'th': true, 'tr': true},Ð
contextGrabbers: {Ð     'dd': {'dd': true, 'dt': true},Ð     'dt': {'dd':
true, 'dt': true},Ð     'li': {'li': true},Ð     'option': {'option': true,
'optgroup': true},Ð     'optgroup': {'optgroup': true},Ð     'p': {'address':
true, 'article': true, 'aside': true, 'blockquote': true, 'dir': true,Ð
            'div': true, 'dl': true, 'fieldset': true, 'footer': true,
'form': true,Ð           'h1': true, 'h2': true, 'h3': true, 'h4': true,
'h5': true, 'h6': true,Ð           'header': true, 'hgroup': true, 'hr':
true, 'menu': true, 'nav': true, 'ol': true,Ð           'p': true, 'pre':
true, 'section': true, 'table': true, 'ul': true},Ð     'rp': {'rp': true,
'rt': true},Ð     'rt': {'rp': true, 'rt': true},Ð     'tbody': {'tbody':
true, 'tfoot': true},Ð     'td': {'td': true, 'th': true},Ð     'tfoot':
{'tbody': true},Ð     'th': {'td': true, 'th': true},Ð     'thead': {'tbody':
true, 'tfoot': true},Ð     'tr': {'tr': true}Ð   },Ð   doNotIndent: {"pre":
true},Ð   allowUnquoted: true,Ð   allowMissing: true,Ð   caseFold: true Ð } : {Ð
    autoSelfClosers: {},Ð   implicitlyClosed: {},Ð   contextGrabbers: {},Ð
doNotIndent: {},Ð   allowUnquoted: false,Ð   allowMissing: false,Ð
caseFold: false Ð };Ð var alignCDATA = parserConfig.alignCDATA;Ð // Return
variables for tokenizers Ð var type, setStyle;Ð function inText(stream, state)
{Ð   function chain(parser) {Ð     state.tokenize = parser;Ð     return
parser(stream, state);Ð   }Ð   var ch = stream.next();Ð   if (ch == "<") {Ð
      if (stream.eat("!")) {Ð       if (stream.eat("[")) {Ð         if
(stream.match("CDATA[")) return chain(inBlock("atom", "]]>"));Ð         else
return null;Ð       } else if (stream.match("--")) {Ð         return
chain(inBlock("comment", "-->"));Ð       } else if (stream.match("DOCTYPE",
true, true)) {Ð         stream.eatWhile(/[\w\._\-]/);Ð         return
chain(doctype(1));Ð       } else {Ð         return null;Ð       }Ð     } else
if (stream.eat("?")) {Ð       stream.eatWhile(/[\w\._\-]/);Ð
state.tokenize = inBlock("meta", "?>");Ð       return "meta";Ð     } else {Ð
        type = stream.eat("/") ? "closeTag" : "openTag";Ð
state.tokenize = inTag;Ð       return "tag bracket";Ð     }Ð   } else if (ch
== "&") {Ð     var ok;Ð     if (stream.eat("#")) {Ð       if
(stream.eat("x")) {Ð         ok = stream.eatWhile(/[a-fA-F\d]/) &&
stream.eat(";");Ð       } else {Ð         ok = stream.eatWhile(/[\d]/) &&
stream.eat(";");Ð       }Ð     } else {Ð       ok = stream.eatWhile(/[\w\.
\-:]/) && stream.eat(";");Ð     }Ð     return ok ? "atom" : "error";Ð   }
else {Ð     stream.eatWhile(/[^&<]/);Ð     return null;Ð   }Ð }Ð function
inTag(stream, state) {Ð   var ch = stream.next();Ð   if (ch == ">" || (ch ==
"/" && stream.eat(">"))) {Ð     state.tokenize = inText;Ð     type = ch ==
">" ? "endTag" : "selfcloseTag";Ð     return "tag bracket";Ð   } else if (ch
== "=") {Ð
```

```
                type = "equals";Ð     return null;Ð   } else if (ch == "<") {Ð
      state.tokenize = inText;Ð     state.state = baseState;Ð
state.tagName = state.tagStart = null;Ð     var next = state.tokenize(stream,
state);Ð     return next ? next + " tag error" : "tag error";Ð   } else if (/
[\'\"]/.test(ch)) {Ð     state.tokenize = inAttribute(ch);Ð
state.stringStartCol = stream.column();Ð     return state.tokenize(stream,
state);Ð   } else {Ð     stream.match(/
^[^\s\u00a0=<>\"\']*[^\s\u00a0=<>\"\'\/]/);Ð     return "word";Ð   }Ð }Ð
function inAttribute(quote) {Ð   var closure = function(stream, state) {Ð
while (!stream.eol()) {Ð       if (stream.next() == quote) {Ð
state.tokenize = inTag;Ð         break;Ð       }Ð     }Ð     return "string";Ð
    };Ð   closure.isInAttribute = true;Ð   return closure;Ð }Ð function
inBlock(style, terminator) {Ð   return function(stream, state) {Ð     while (!
stream.eol()) {Ð       if (stream.match(terminator)) {Ð
state.tokenize = inText;Ð         break;Ð       }Ð       stream.next();Ð     }Ð
      return style;Ð   };Ð }Ð function doctype(depth) {Ð   return
function(stream, state) {Ð     var ch;Ð     while ((ch = stream.next()) !=
null) {Ð       if (ch == "<") {Ð         state.tokenize = doctype(depth + 1);Ð
          return state.tokenize(stream, state);Ð       } else if (ch == ">") {Ð
          if (depth == 1) {Ð           state.tokenize = inText;Ð
break;Ð         } else {Ð           state.tokenize = doctype(depth - 1);Ð
            return state.tokenize(stream, state);Ð         }Ð       }Ð     }Ð
      return "meta";Ð   };Ð }Ð function Context(state, tagName, startOfLine) {Ð
    this.prev = state.context;Ð   this.tagName = tagName;Ð   this.indent =
state.indented;Ð   this.startOfLine = startOfLine;Ð   if
(Kludges.doNotIndent.hasOwnProperty(tagName) || (state.context &&
state.context.noIndent))Ð     this.noIndent = true;Ð }Ð function
popContext(state) {Ð   if (state.context) state.context = state.context.prev;Ð
  }Ð function maybePopContext(state, nextTagName) {Ð   var parentTagName;Ð
while (true) {Ð     if (!state.context) {Ð       return;Ð     }Ð
parentTagName = state.context.tagName;Ð     if (!
Kludges.contextGrabbers.hasOwnProperty(parentTagName) ||Ð         !
Kludges.contextGrabbers[parentTagName].hasOwnProperty(nextTagName)) {Ð
return;Ð     }Ð     popContext(state);Ð   }Ð }Ð function baseState(type,
stream, state) {Ð   if (type == "openTag") {Ð     state.tagStart =
stream.column();Ð     return tagNameState;Ð   } else if (type == "closeTag") {Ð
      return closeTagNameState;Ð   } else {Ð     return baseState;Ð   }Ð }Ð
function tagNameState(type, stream, state) {Ð   if (type == "word") {Ð
state.tagName = stream.current();Ð     setStyle = "tag";Ð     return
attrState;Ð   } else {Ð     setStyle = "error";Ð     return tagNameState;Ð   }Ð
  }Ð function closeTagNameState(type, stream, state) {Ð   if (type == "word")
{Ð     var tagName = stream.current();Ð     if (state.context &&
state.context.tagName != tagName &&Ð
Kludges.implicitlyClosed.hasOwnProperty(state.context.tagName))Ð
popContext(state);Ð     if (state.context && state.context.tagName ==
tagName) {Ð       setStyle = "tag";Ð       return closeState;Ð     } else {Ð
        setStyle = "tag error";Ð       return closeStateErr;Ð     }Ð   } else
{Ð     setStyle = "error";Ð     return closeStateErr;Ð   }Ð }Ð function
closeState(type, _stream, state) {Ð   if (type != "endTag") {Ð     setStyle =
"error";Ð     return closeState;Ð   }Ð   popContext(state);Ð   return
baseState;Ð }Ð function closeStateErr(type, stream, state) {Ð   setStyle =
"error";Ð   return closeState(type, stream, state);Ð }Ð function
attrState(type, _stream, state) {Ð   if (type == "word") {Ð     setStyle =
"attribute";Ð     return attrEqState;Ð   } else if (type == "endTag" || type
== "selfcloseTag") {Ð     var tagName = state.tagName, tagStart =
state.tagStart;Ð     state.tagName = state.tagStart = null;Ð     if (type ==
"selfcloseTag" ||Ð         Kludges.autoSelfClosers.hasOwnProperty(tagName)) {Ð
        maybePopContext(state, tagName);Ð     } else {Ð
maybePopContext(state, tagName);Ð       state.context = new Context(state,
tagName, tagStart == state.indented);Ð
```

```
                                                }Ð     return baseState;Ð   }Ð
setStyle = "error";Ð   return attrState;Ð }Ð function attrEqState(type,
stream, state) {Ð   if (type == "equals") return attrValueState;Ð   if (!
Kludges.allowMissing) setStyle = "error";Ð   return attrState(type, stream,
state);Ð }Ð function attrValueState(type, stream, state) {Ð   if (type ==
"string") return attrContinuedState;Ð   if (type == "word" &&
Kludges.allowUnquoted) {setStyle = "string"; return attrState;}Ð   setStyle =
"error";Ð   return attrState(type, stream, state);Ð }Ð function
attrContinuedState(type, stream, state) {Ð   if (type == "string") return
attrContinuedState;Ð   return attrState(type, stream, state);Ð }Ð return {Ð
startState: function() {Ð     return {tokenize: inText,Ð             state:
baseState,Ð             indented: 0,Ð             tagName: null, tagStart:
null,Ð             context: null};Ð   },Ð   token: function(stream, state) {Ð
      if (!state.tagName && stream.sol())Ð       state.indented =
stream.indentation();Ð     if (stream.eatSpace()) return null;Ð     type =
null;Ð     var style = state.tokenize(stream, state);Ð     if ((style ||
type) && style != "comment") {Ð       setStyle = null;Ð       state.state =
state.state(type || style, stream, state);Ð       if (setStyle)Ð
style = setStyle == "error" ? style + " error" : setStyle;Ð     }Ð     return
style;Ð   },Ð   indent: function(state, textAfter, fullLine) {Ð     var
context = state.context;Ð     // Indent multi-line strings (e.g. css).Ð
if (state.tokenize.isInAttribute) {Ð       if (state.tagStart ==
state.indented)Ð         return state.stringStartCol + 1;Ð       elseÐ
          return state.indented + indentUnit;Ð     }Ð     if (context &&
context.noIndent) return CodeMirror.Pass;Ð     if (state.tokenize != inTag &&
state.tokenize != inText)Ð       return fullLine ? fullLine.match(/^(\s*)/)
[0].length : 0;Ð     // Indent the starts of attribute names.Ð     if
(state.tagName) {Ð       if (multilineTagIndentPastTag)Ð         return
state.tagStart + state.tagName.length + 2;Ð       elseÐ         return
state.tagStart + indentUnit * multilineTagIndentFactor;Ð     }Ð     if
(alignCDATA && /<!\[CDATA\[/.test(textAfter)) return 0;Ð     var tagAfter =
textAfter && /^<(\/)?([\w_:\.-]*)/.exec(textAfter);Ð     if (tagAfter &&
tagAfter[1]) { // Closing tag spottedÐ       while (context) {Ð         if
(context.tagName == tagAfter[2]) {Ð           context = context.prev;Ð
            break;Ð         } else if
(Kludges.implicitlyClosed.hasOwnProperty(context.tagName)) {Ð
context = context.prev;Ð         } else {Ð           break;Ð         }Ð
        }Ð     } else if (tagAfter) { // Opening tag spottedÐ       while
(context) {Ð         var grabbers = Kludges.contextGrabbers[context.tagName];Ð
          if (grabbers && grabbers.hasOwnProperty(tagAfter[2]))Ð
context = context.prev;Ð         elseÐ           break;Ð       }Ð     }Ð
while (context && !context.startOfLine)Ð       context = context.prev;Ð
if (context) return context.indent + indentUnit;Ð     else return 0;Ð   },Ð
electricInput: /<\/[\s\w:]+>$/,Ð   blockCommentStart: "<!--",Ð
blockCommentEnd: "-->",Ð   configuration: parserConfig.htmlMode ? "html" :
"xml",Ð   helperType: parserConfig.htmlMode ? "html" : "xml"Ð };Ð});Ð
CodeMirror.defineMIME("text/xml", "xml");ÐodeMirror.defineMIME("application/
xml", "xml");Ð if (!CodeMirror.mimeModes.hasOwnProperty("text/html"))Ð
CodeMirror.defineMIME("text/html", {name: "xml", htmlMode: true});Ð});Ð
```

public\assets\js\plugins\codemirror\mode\xquery\test.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð/ Don't take these too
seriously -- the expected results appear to be Ð/ based on the results of
actual runs without any serious manual Ð/ verification. If a change you made
causes them to fail, the test is Ð/ as likely to wrong as the code. Ð function()
{Ð var mode = CodeMirror.getMode({tabSize: 4}, "xquery");Ð function MT(name)
{ test.mode(name, mode, Array.prototype.slice.call(arguments, 1)); }Ð
MT("eviltest",Ð    "[keyword xquery] [keyword version] [variable &quot;1]
[keyword .][atom 0][keyword -][variable ml&quot;][def&variable ;]
[comment (: this is       : a          \"comment\" :)]",Ð    "      [keyword
let] [variable $let] [keyword :=] [variable &lt;x] [variable attr][keyword =]
[variable &quot;value&quot;&gt;&quot;test&quot;&lt;func&gt]
[def&variable ;function]() [variable $var] {[keyword function]()} {[variable
$var]}[variable &lt;][keyword /][variable func&gt;&lt;][keyword /][variable
x&gt;]",Ð    "      [keyword let] [variable $joe][keyword :=][atom 1]",Ð
"      [keyword return] [keyword element] [variable element] {",Ð
"          [keyword attribute] [variable attribute] { [atom 1] },",Ð
"          [keyword element] [variable test] { [variable
&#39;a&#39;] },           [keyword attribute] [variable foo] { [variable
&quot;bar&quot;] },",Ð    "          [def&variable fn:doc]()[[ [variable foo]
[keyword /][variable @bar] [keyword eq] [variable $let] ]],",Ð
"          [keyword //][variable x] }                [comment (: a more
'evil' test :)]",Ð    "      [comment (: Modified Blakeley example (: with
nested comment :) ... :)]",Ð    "      [keyword declare] [keyword private]
[keyword function] [def&variable local:declare]() {()}[variable ;]",Ð
"      [keyword declare] [keyword private] [keyword function] [def&variable
local:private]() {()}[variable ;]",Ð    "      [keyword declare] [keyword
private] [keyword function] [def&variable local:function]() {()}[variable ;]",Ð
     "      [keyword declare] [keyword private] [keyword function]
[def&variable local:local]() {()}[variable ;]",Ð    "      [keyword let]
[variable $let] [keyword :=] [variable &lt;let&gt;let] [variable $let]
[keyword :=] [variable &quot;let&quot;&lt;][keyword /let][variable &gt;]",Ð
     "      [keyword return] [keyword element] [variable element] {",Ð
"          [keyword attribute] [variable attribute] { [keyword try]
{ [def&variable xdmp:version]() } [keyword catch]([variable $e])
{ [def&variable xdmp:log]([variable $e]) } },",Ð    "          [keyword
attribute] [variable fn:doc] { [variable &quot;bar&quot;] [variable castable]
[keyword as] [atom xs:string] },",Ð    "          [keyword element] [variable
text] { [keyword text] { [variable &quot;text&quot;] } },",Ð
"          [def&variable fn:doc]()[[ [qualifier child::][variable eq]
[keyword /]([variable @bar] [keyword |] [qualifier attribute::][variable
attribute]) [keyword eq] [variable $let] ]],",Ð    "          [keyword //]
[variable fn:doc]",Ð    "      }");Ð MT("testEmptySequenceKeyword",Ð
"[string \"foo\"] [keyword instance] [keyword of] [keyword empty-sequence]
()");Ð MT("testMultiAttr",Ð    "[tag <p ][attribute a1]=[string \"foo\"]
[attribute a2]=[string \"bar\"][tag >][variable hello] [variable world][tag </
p>]");Ð MT("test namespaced variable",Ð    "[keyword declare] [keyword
namespace] [variable e] [keyword =] [string \"http://example.com/ANamespace\"]
[variable ;declare] [keyword variable] [variable
$e:exampleComThisVarIsNotRecognized] [keyword as] [keyword element]([keyword
*]) [variable external;]");Ð MT("test EQName variable",Ð    "[keyword
declare] [keyword variable] [variable $\"http://www.example.com/ns/my\":var]
[keyword :=] [atom 12][variable ;]",Ð    "[tag <out>]{[variable $\"http://
www.example.com/ns/my\":var]}[tag </out>]");Ð MT("test EQName function",Ð
"[keyword declare] [keyword function] [def&variable \"http://www.example.com/
ns/my\":fn] ([variable $a] [keyword as] [atom xs:integer]) [keyword as] [atom
xs:integer] {",Ð    "   [variable $a] [keyword +] [atom 2]",Ð    "}
[variable ;]",Ð    "[tag <out>]{[def&variable \"http://www.example.com/ns/
my\":fn]([atom 12])}[tag </out>]");Ð
```

```
                                    Ð MT("test EQName function with single
quotes",Ð    "[keyword declare] [keyword function] [def&variable 'http://
www.example.com/ns/my':fn] ([variable $a] [keyword as] [atom xs:integer])
[keyword as] [atom xs:integer] {",Ð    "   [variable $a] [keyword +] [atom
2]",Ð    "}[variable ;]",Ð    "[tag <out>]{[def&variable 'http://
www.example.com/ns/my':fn]([atom 12])}[tag </out>]");Ð
MT("testProcessingInstructions",Ð    "[def&variable data]([comment&meta <?
target content?>]) [keyword instance] [keyword of] [atom xs:string]");Ð
MT("testQuoteEscapeDouble",Ð    "[keyword let] [variable $rootfolder]
[keyword :=] [string \"c:\\builds\\winnt\\HEAD\\qa\\scripts\\\"]",Ð
"[keyword let] [variable $keysfolder] [keyword :=] [def&variable concat]
([variable $rootfolder], [string \"keys\\\"])");Ð})();Ð
```

public\assets\js\plugins\codemirror\mode\xquery\xquery.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ðuse strict";Ð
CodeMirror.defineMode("xquery", function() {Ð // The keywords object is set
to the result of this self executing Ð // function. Each keyword is a property
of the keywords object whose Ð // value is {type: atype, style: astyle} Ð var
keywords = function(){Ð   // conveinence functions used to build keywords
object Ð   function kw(type) {return {type: type, style: "keyword"};}Ð   var A
= kw("keyword a")Ð     , B = kw("keyword b")Ð     , C = kw("keyword c")Ð
      , operator = kw("operator")Ð     , atom = {type: "atom", style: "atom"}Ð
      , punctuation = {type: "punctuation", style: null}Ð     , qualifier =
{type: "axis_specifier", style: "qualifier"};Ð   // kwObj is what is return
from this function at the end Ð   var kwObj = {Ð     'if': A, 'switch': A,
'while': A, 'for': A,Ð     'else': B, 'then': B, 'try': B, 'finally': B,
'catch': B,Ð     'element': C, 'attribute': C, 'let': C, 'implements': C,
'import': C, 'module': C, 'namespace': C,Ð     'return': C, 'super': C,
'this': C, 'throws': C, 'where': C, 'private': C,Ð     ',': punctuation,Ð
'null': atom, 'fn:false()': atom, 'fn:true()': atom Ð   };Ð   // a list of
'basic' keywords. For each add a property to kwObj with the value of Ð   //
{type: basic[i], style: "keyword"} e.g. 'after' --> {type: "after", style:
"keyword"} Ð   var basic = ['after','ancestor','ancestor-or-
self','and','as','ascending','assert','attribute','before',Ð   'by','case','ca
st','child','comment','declare','default','define','descendant','descendant-
or-self',Ð   'descending','document','document-
node','element','else','eq','every','except','external','following',Ð
'following-
sibling','follows','for','function','if','import','in','instance','intersect','item',Ð

'let','module','namespace','node','node','of','only','or','order','parent','precedes','pre
    'preceding-sibling','processing-
instruction','ref','return','returns','satisfies','schema','schema-element',Ð

'self','some','sortby','stable','text','then','to','treat','typeswitch','union','variable'
    'xquery', 'empty-sequence'];Ð   for(var i=0, l=basic.length; i < l; i++)
{ kwObj[basic[i]] = kw(basic[i]);};Ð   // a list of types. For each add a
property to kwObj with the value of Ð   // {type: "atom", style: "atom"} Ð
var types = ['xs:string', 'xs:float', 'xs:decimal', 'xs:double',
'xs:integer', 'xs:boolean', 'xs:date', 'xs:dateTime',Ð   'xs:time',
'xs:duration', 'xs:dayTimeDuration', 'xs:time', 'xs:yearMonthDuration',
'numeric', 'xs:hexBinary',Ð   'xs:base64Binary', 'xs:anyURI', 'xs:QName',
'xs:byte','xs:boolean','xs:anyURI','xf:yearMonthDuration'];Ð   for(var i=0,
l=types.length; i < l; i++) { kwObj[types[i]] = atom;};Ð   // each operator
will add a property to kwObj with value of {type: "operator", style:
"keyword"} Ð   var operators = ['eq', 'ne', 'lt', 'le', 'gt', 'ge', ':=', '=',
'>', '>=', '<', '<=', '.', '|', '?', 'and', 'or', 'div', 'idiv', 'mod', '*',
'/', '+', '-'];Ð   for(var i=0, l=operators.length; i < l; i++)
{ kwObj[operators[i]] = operator;};Ð   // each axis_specifiers will add a
property to kwObj with value of {type: "axis_specifier", style: "qualifier"} Ð
    var axis_specifiers = ["self::", "attribute::", "child::",
"descendant::", "descendant-or-self::", "parent::",Ð   "ancestor::",
"ancestor-or-self::", "following::", "preceding::", "following-sibling::",
"preceding-sibling::"];Ð   for(var i=0, l=axis_specifiers.length; i < l; i++)
{ kwObj[axis_specifiers[i]] = qualifier; };Ð   return kwObj;Ð }();Ð // Used
as scratch variables to communicate multiple values without Ð // consing up
tons of objects.Ð var type, content;Ð function ret(tp, style, cont) {Ð   type
= tp; content = cont;Ð
```

```
                        return style;Ð }Ð function chain(stream, state, f) {Ð
    state.tokenize = f;Ð   return f(stream, state);Ð }Ð // the primary mode
tokenizerÐ function tokenBase(stream, state) {Ð   var ch = stream.next(),Ð
        mightBeFunction = false,Ð       isEQName = isEQNameAhead(stream);Ð
    // an XML tag (if not in some sub, chained tokenizer)Ð   if (ch == "<") {Ð
      if(stream.match("!--", true))Ð       return chain(stream, state,
tokenXMLComment);Ð     if(stream.match("![CDATA", false)) {Ð
state.tokenize = tokenCDATA;Ð       return ret("tag", "tag");Ð     }Ð
if(stream.match("?", false)) {Ð       return chain(stream, state,
tokenPreProcessing);Ð     }Ð     var isclose = stream.eat("/");Ð
stream.eatSpace();Ð     var tagName = "", c;Ð     while ((c = stream.eat(/
[^\s\u00a0=<>\"\'\/?]/))) tagName += c;Ð     return chain(stream, state,
tokenTag(tagName, isclose));Ð   }Ð   // start code blockÐ   else if(ch ==
"{") {Ð     pushStateStack(state,{ type: "codeblock"});Ð     return ret("",
null);Ð   }Ð   // end code blockÐ   else if(ch == "}") {Ð
popStateStack(state);Ð     return ret("", null);Ð   }Ð   // if we're in an
XML blockÐ   else if(isInXmlBlock(state)) {Ð     if(ch == ">")Ð       return
ret("tag", "tag");Ð     else if(ch == "/" && stream.eat(">")) {Ð
popStateStack(state);Ð       return ret("tag", "tag");Ð     }Ð     elseÐ
        return ret("word", "variable");Ð   }Ð   // if a numberÐ   else if (/
\d/.test(ch)) {Ð     stream.match(/^\d*(?:\.\d*)?(?:E[+\-]?\d+)?/);Ð
return ret("number", "atom");Ð   }Ð   // comment startÐ   else if (ch === "("
&& stream.eat(":")) {Ð     pushStateStack(state, { type: "comment"});Ð
return chain(stream, state, tokenComment);Ð   }Ð   // quoted stringÐ   else
if (  !isEQName && (ch === '"' || ch === "'"))Ð     return chain(stream,
state, tokenString(ch));Ð   // variableÐ   else if(ch === "$") {Ð     return
chain(stream, state, tokenVariable);Ð   }Ð   // assignmentÐ   else if(ch
===":" && stream.eat("=")) {Ð     return ret("operator", "keyword");Ð   }Ð
    // open parenÐ   else if(ch === "(") {Ð     pushStateStack(state, { type:
"paren"});Ð     return ret("", null);Ð   }Ð   // close parenÐ   else if(ch
=== ")") {Ð     popStateStack(state);Ð     return ret("", null);Ð   }Ð   //
open parenÐ   else if(ch === "[") {Ð     pushStateStack(state, { type:
"bracket"});Ð     return ret("", null);Ð   }Ð   // close parenÐ   else if(ch
=== "]") {Ð     popStateStack(state);Ð     return ret("", null);Ð   }Ð   else
{Ð     var known = keywords.propertyIsEnumerable(ch) && keywords[ch];Ð     //
if there's a EQName ahead, consume the rest of the string portion, it's
likely a functionÐ     if(isEQName && ch === '\"') while(stream.next() !==
'"'){}Ð     if(isEQName && ch === '\'') while(stream.next() !== '\'){}Ð
      // gobble up a word if the character is not knownÐ     if(!known)
stream.eatWhile(/[\w\$_-]/);Ð     // gobble a colon in the case that is a lib
func type call fn:docÐ     var foundColon = stream.eat(":");Ð     // if
there's not a second colon, gobble another word. Otherwise, it's probably an
axis specifierÐ     // which should get matched as a keywordÐ     if(!
stream.eat(":") && foundColon) {Ð       stream.eatWhile(/[\w\$_-]/);Ð     }Ð
      // if the next non whitespace character is an open paren, this is
probably a function (if not a keyword of other sort)Ð     if(stream.match(/
^[ \t]*\(/, false)) {Ð       mightBeFunction = true;Ð     }Ð     // is the
word a keyword?Ð     var word = stream.current();Ð     known =
keywords.propertyIsEnumerable(word) && keywords[word];Ð     // if we think
it's a function call but not yet known,Ð     // set style to variable for now
for lack of something betterÐ     if(mightBeFunction && !known) known =
{type: "function_call", style: "variable def"};Ð     // if the previous word
was element, attribute, axis specifier, this word should be the name of thatÐ
      if(isInXmlConstructor(state)) {Ð       popStateStack(state);Ð
return ret("word", "variable", word);Ð     }Ð     // as previously checked,
if the word is element,attribute, axis specifier, call it an "xmlconstructor"
andÐ     // push the stack so we know to look for it on the next wordÐ
if(word == "element" || word == "attribute" || known.type ==
"axis_specifier") pushStateStack(state, {type: "xmlconstructor"});Ð     // if
the word is known, return the details of that else just call this a generic
'word'Ð
```

```
            return known ? ret(known.type, known.style, word) :Ð
                      ret("word", "variable", word);Ð   }Ð }Ð // handle
comments, including nestedÐ function tokenComment(stream, state) {Ð   var
maybeEnd = false, maybeNested = false, nestedCount = 0, ch;Ð   while (ch =
stream.next()) {Ð     if (ch == ")" && maybeEnd) {Ð       if(nestedCount > 0)Ð
          nestedCount--;Ð       else {Ð         popStateStack(state);Ð
          break;Ð       }Ð     }Ð     else if(ch == ":" && maybeNested) {Ð
        nestedCount++;Ð     }Ð     maybeEnd = (ch == ":");Ð     maybeNested =
(ch == "(");Ð   }Ð   return ret("comment", "comment");Ð }Ð // tokenizer for
string literalsÐ // optionally pass a tokenizer function to set
state.tokenize back to when finishedÐ function tokenString(quote, f) {Ð
return function(stream, state) {Ð     var ch;Ð     if(isInString(state) &&
stream.current() == quote) {Ð       popStateStack(state);Ð       if(f)
state.tokenize = f;Ð       return ret("string", "string");Ð     }Ð
pushStateStack(state, { type: "string", name: quote, tokenize:
tokenString(quote, f) });Ð     // if we're in a string and in an XML block,
allow an embedded code blockÐ     if(stream.match("{", false) &&
isInXmlAttributeBlock(state)) {Ð       state.tokenize = tokenBase;Ð
return ret("string", "string");Ð     }Ð     while (ch = stream.next()) {Ð
        if (ch ==  quote) {Ð         popStateStack(state);Ð         if(f)
state.tokenize = f;Ð         break;Ð       }Ð       else {Ð         // if
we're in a string and in an XML block, allow an embedded code block in an
attributeÐ         if(stream.match("{", false) &&
isInXmlAttributeBlock(state)) {Ð           state.tokenize = tokenBase;Ð
            return ret("string", "string");Ð         }Ð       }Ð     }Ð
return ret("string", "string");Ð   };Ð }Ð // tokenizer for variablesÐ
function tokenVariable(stream, state) {Ð   var isVariableChar = /[\w\$_-]/;Ð
    // a variable may start with a quoted EQName so if the next character is
quote, consume to the next quoteÐ   if(stream.eat("\"")) {Ð
while(stream.next() !== '\"'){};Ð     stream.eat(":");Ð   } else {Ð
stream.eatWhile(isVariableChar);Ð     if(!stream.match(":=", false))
stream.eat(":");Ð   }Ð   stream.eatWhile(isVariableChar);Ð   state.tokenize =
tokenBase;Ð   return ret("variable", "variable");Ð }Ð // tokenizer for XML
tagsÐ function tokenTag(name, isclose) {Ð   return function(stream, state) {Ð
      stream.eatSpace();Ð     if(isclose && stream.eat(">")) {Ð
popStateStack(state);Ð       state.tokenize = tokenBase;Ð       return
ret("tag", "tag");Ð     }Ð     // self closing tag without attributes?Ð
if(!stream.eat("/"))Ð       pushStateStack(state, { type: "tag", name: name,
tokenize: tokenBase});Ð     if(!stream.eat(">")) {Ð       state.tokenize =
tokenAttribute;Ð       return ret("tag", "tag");Ð     }Ð     else {Ð
state.tokenize = tokenBase;Ð     }Ð     return ret("tag", "tag");Ð   };Ð }Ð
  // tokenizer for XML attributesÐ function tokenAttribute(stream, state) {Ð
    var ch = stream.next();Ð   if(ch == "/" && stream.eat(">")) {Ð
if(isInXmlAttributeBlock(state)) popStateStack(state);Ð
if(isInXmlBlock(state)) popStateStack(state);Ð     return ret("tag", "tag");Ð
    }Ð   if(ch == ">") {Ð     if(isInXmlAttributeBlock(state))
popStateStack(state);Ð     return ret("tag", "tag");Ð   }Ð   if(ch == "=")Ð
      return ret("", null);Ð   // quoted stringÐ   if (ch == '"' || ch == "'")Ð
      return chain(stream, state, tokenString(ch, tokenAttribute));Ð   if(!
isInXmlAttributeBlock(state))Ð     pushStateStack(state, { type: "attribute",
tokenize: tokenAttribute});Ð   stream.eat(/[a-zA-Z_:]/);Ð   stream.eatWhile(/
[-a-zA-Z0-9_:.]/);Ð   stream.eatSpace();Ð   // the case where the attribute
has not value and the tag was closedÐ   if(stream.match(">", false) ||
stream.match("/", false)) {Ð     popStateStack(state);Ð     state.tokenize =
tokenBase;Ð   }Ð   return ret("attribute", "attribute");Ð }Ð // handle
comments, including nestedÐ function tokenXMLComment(stream, state) {Ð   var
ch;Ð   while (ch = stream.next()) {Ð     if (ch == "-" && stream.match("->",
true)) {Ð       state.tokenize = tokenBase;Ð       return ret("comment",
"comment");Ð     }Ð   }Ð }Ð // handle CDATAÐ function tokenCDATA(stream,
state) {Ð
```

```
            var ch;Ð   while (ch = stream.next()) {Ð     if (ch == "]" &&
stream.match("]", true)) {Ð       state.tokenize = tokenBase;Ð       return
ret("comment", "comment");Ð     }Ð   }Ð }Ð // handle preprocessing
instructionsÐ function tokenPreProcessing(stream, state) {Ð   var ch;Ð
while (ch = stream.next()) {Ð     if (ch == "?" && stream.match(">", true)) {Ð
        state.tokenize = tokenBase;Ð       return ret("comment", "comment
meta");Ð     }Ð   }Ð }Ð // functions to test the current context of the stateÐ
  function isInXmlBlock(state) { return isIn(state, "tag"); }Ð function
isInXmlAttributeBlock(state) { return isIn(state, "attribute"); }Ð function
isInXmlConstructor(state) { return isIn(state, "xmlconstructor"); }Ð function
isInString(state) { return isIn(state, "string"); }Ð function
isEQNameAhead(stream) {Ð   // assume we've already eaten a quote (")Ð
if(stream.current() === '"')Ð     return stream.match(/^[^\"]+\"\:/, false);Ð
    else if(stream.current() === '\'')Ð     return stream.match(/^[^\"]+
\'\:/, false);Ð   elseÐ     return false;Ð }Ð function isIn(state, type) {Ð
return (state.stack.length && state.stack[state.stack.length - 1].type ==
type);Ð }Ð function pushStateStack(state, newState) {Ð
state.stack.push(newState);Ð }Ð function popStateStack(state) {Ð
state.stack.pop();Ð   var reinstateTokenize = state.stack.length &&
state.stack[state.stack.length-1].tokenize;Ð   state.tokenize =
reinstateTokenize || tokenBase;Ð }Ð // the interface for the mode APIÐ return
{Ð   startState: function() {Ð     return {Ð       tokenize: tokenBase,Ð
        cc: [],Ð       stack: []Ð     };Ð   },Ð   token: function(stream,
state) {Ð     if (stream.eatSpace()) return null;Ð     var style =
state.tokenize(stream, state);Ð     return style;Ð   },Ð   blockCommentStart:
"(:",Ð   blockCommentEnd: ":)"Ð };Ð});ÐodeMirror.defineMIME("application/
xquery", "xquery");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\yaml\yaml.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð/ Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode("yaml", function() {Ð var cons = ['true', 'false',
'on', 'off', 'yes', 'no'];Ð var keywordRegex = new RegExp("\
\b(("+cons.join(")|(")+"))$", 'i');Ð return {Ð   token: function(stream,
state) {Ð     var ch = stream.peek();Ð     var esc = state.escaped;Ð
state.escaped = false;Ð     /* comments */Ð     if (ch == "#" && (stream.pos
== 0 || /\s/.test(stream.string.charAt(stream.pos - 1)))) {Ð
stream.skipToEnd(); return "comment";Ð     }Ð     if (state.literal &&
stream.indentation() > state.keyCol) {Ð       stream.skipToEnd(); return
"string";Ð     } else if (state.literal) { state.literal = false; }Ð     if
(stream.sol()) {Ð       state.keyCol = 0;Ð       state.pair = false;Ð
state.pairStart = false;Ð       /* document start */Ð
if(stream.match(/---/)) { return "def"; }Ð       /* document end */Ð       if
(stream.match(/\.\.\./)) { return "def"; }Ð       /* array list item */Ð
        if (stream.match(/\s*-\s+/)) { return 'meta'; }Ð     }Ð     /* inline
pairs/lists */Ð     if (stream.match(/^(\{|\}|\[|\])/)) {Ð       if (ch ==
'{')Ð         state.inlinePairs++;Ð       else if (ch == '}')Ð
state.inlinePairs--;Ð       else if (ch == '[')Ð         state.inlineList++;Ð
        elseÐ         state.inlineList--;Ð       return 'meta';Ð     }Ð     /
* list seperator */Ð     if (state.inlineList > 0 && !esc && ch == ',') {Ð
        stream.next();Ð       return 'meta';Ð     }Ð     /* pairs seperator */Ð
      if (state.inlinePairs > 0 && !esc && ch == ',') {Ð       state.keyCol =
0;Ð       state.pair = false;Ð       state.pairStart = false;Ð
stream.next();Ð       return 'meta';Ð     }Ð     /* start of value of a pair
*/Ð     if (state.pairStart) {Ð       /* block literals */Ð       if
(stream.match(/^\s*(\||\>)\s*/)) { state.literal = true; return 'meta'; };Ð
        /* references */Ð       if (stream.match(/^\s*(\&|\*)[a-z0-9\._-]+\b/
i)) { return 'variable-2'; }Ð       /* numbers */Ð       if
(state.inlinePairs == 0 && stream.match(/^\s*-?[0-9\.\,]+\s?$/)) { return
'number'; }Ð       if (state.inlinePairs > 0 && stream.match(/^\s*-?[0-9\.\,]+
\s?(?=(,|}))/)) { return 'number'; }Ð       /* keywords */Ð       if
(stream.match(keywordRegex)) { return 'keyword'; }Ð     }Ð     /* pairs
(associative arrays) -> key */Ð     if (!state.pair && stream.match(/^\s*(?:[,
\[\]{}&*!|>'"%@`][^\s'":]|[^,\[\]{}#&*!|>'"%@`])[^#]*?(?=\s*:($|\s))/)) {Ð
        state.pair = true;Ð       state.keyCol = stream.indentation();Ð
return "atom";Ð     }Ð     if (state.pair && stream.match(/^:\s*/))
{ state.pairStart = true; return 'meta'; }Ð     /* nothing found, continue */Ð
      state.pairStart = false;Ð     state.escaped = (ch == '\\');Ð
stream.next();Ð     return null;Ð   },Ð   startState: function() {Ð
return {Ð       pair: false,Ð       pairStart: false,Ð       keyCol: 0,Ð
        inlinePairs: 0,Ð       inlineList: 0,Ð       literal: false,Ð
escaped: false Ð     };Ð   }Ð };Ð});ÐodeMirror.defineMIME("text/x-yaml",
"yaml");Ð});Ð
```

public\assets\js\plugins\codemirror\mode\z80\z80.js

```
// CodeMirror, copyright (c) by Marijn Haverbeke and others Ð// Distributed
under an MIT license: http://codemirror.net/LICENSE Ð(function(mod) {Ð if
(typeof exports == "object" && typeof module == "object") // CommonJS Ð
mod(require("../../lib/codemirror"));Ð else if (typeof define == "function"
&& define.amd) // AMD Ð   define(["../../lib/codemirror"], mod);Ð else //
Plain browser env Ð   mod(CodeMirror);Ð})(function(CodeMirror) {Ð "use strict";Ð
CodeMirror.defineMode('z80', function() {Ð var keywords1 = /^(exx?|(ld|cp|in)
([di]r?)?|pop|push|ad[cd]|cpl|daa|dec|inc|neg|sbc|sub|and|bit|[cs]cf|x?or|res|
set|r[lr]c?a?|r[lr]d|s[lr]a|srl|djnz|nop|rst|[de]i|halt|im|ot[di]r|
out[di]?)\b/i;Ð var keywords2 = /^(call|j[pr]|ret[in]?)\b/i;Ð var keywords3
= /^b_?(call|jump)\b/i;Ð var variables1 = /^(af?|bc?|c|de?|e|hl?|l|i[xy]?|r|
sp)\b/i;Ð var variables2 = /^(n?[zc]|p[oe]?|m)\b/i;Ð var errors = /^([hl][xy]|
i[xy][hl]|slia|sll)\b/i;Ð var numbers = /^([\da-f]+h|[0-7]+o|[01]+b|\d+)\b/i;Ð
  return {Ð   startState: function() {Ð     return {context: 0};Ð   },Ð
token: function(stream, state) {Ð     if (!stream.column())Ð
state.context = 0;Ð     if (stream.eatSpace())Ð       return null;Ð     var w;Ð
      if (stream.eatWhile(/\w/)) {Ð       w = stream.current();Ð       if
(stream.indentation()) {Ð         if (state.context == 1 &&
variables1.test(w))Ð           return 'variable-2';Ð         if
(state.context == 2 && variables2.test(w))Ð           return 'variable-3';Ð
          if (keywords1.test(w)) {Ð           state.context = 1;Ð
return 'keyword';Ð         } else if (keywords2.test(w)) {Ð
state.context = 2;Ð           return 'keyword';Ð         } else if
(keywords3.test(w)) {Ð           state.context = 3;Ð           return
'keyword';Ð         }Ð         if (errors.test(w))Ð           return 'error';Ð
        } else if (numbers.test(w)) {Ð         return 'number';Ð       } else
{Ð         return null;Ð       }Ð     } else if (stream.eat(';')) {Ð
stream.skipToEnd();Ð       return 'comment';Ð     } else if (stream.eat('"'))
{Ð       while (w = stream.next()) {Ð         if (w == '"')Ð           break;Ð
          if (w == '\\')Ð           stream.next();Ð       }Ð       return
'string';Ð     } else if (stream.eat('\'')) {Ð       if (stream.match(/\
\?.'/))Ð         return 'number';Ð     } else if (stream.eat('.') ||
stream.sol() && stream.eat('#')) {Ð       state.context = 4;Ð       if
(stream.eatWhile(/\w/))Ð         return 'def';Ð     } else if
(stream.eat('$')) {Ð       if (stream.eatWhile(/[\da-f]/i))Ð         return
'number';Ð     } else if (stream.eat('%')) {Ð       if (stream.eatWhile(/
[01]/))Ð         return 'number';Ð     } else {Ð       stream.next();Ð     }Ð
      return null;Ð   }Ð };Ð});ÐCodeMirror.defineMIME("text/x-z80", "z80");Ð});Ð
```

public\assets\js\plugins\datapicker\bootstrap-datepicker.js

/* ==========Ð* bootstrap-datepicker.jsÐ* Repo: https://github.com/eternicode/bootstrap-datepicker/Ð* Demo: http://eternicode.github.io/bootstrap-datepicker/Ð* Docs: http://bootstrap-datepicker.readthedocs.org/Ð* Forked from http://www.eyecon.ro/bootstrap-datepickerÐ* ==========Ð* Started by Stefan Petre; improvements by Andrew Rowls + contributorsÐ*Ð* Licensed under the Apache License, Version 2.0 (the "License");Ð* you may not use this file except in compliance with the License.Ð* You may obtain a copy of the License atÐ*Ð* http://www.apache.org/licenses/LICENSE-2.0Ð*Ð* Unless required by applicable law or agreed to in writing, softwareÐ* distributed under the License is distributed on an "AS IS" BASIS,Ð* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.Ð* See the License for the specific language governing permissions andÐ* limitations under the License.Ð * ========== */Ðfunction($, undefined){Ðf " Gv–æF÷r Ò B‡v–æF÷r“ÐgVæ7F–öâ UD4F FR,—™return new Date(Date.UTC.apply(Date, arguments));ÐÝgVæ7F–öâ UD5FöF ’,—™var today = new Date();Ðreturn UTCDate(today.getFullYear(), today.getMonth(), today.getDate());Ð—ÝgVæ7F–öâ Æ– 2†ÖWF†öB—™return function(){Ð&WGW&â F†–5¶ÖWF†öEÒæ Ç’‡F†–2Â arguments);Ð}¬Ðf " F FT '& ’ Ò †gVæ7F–öâ,—™var extras = {ÐvWC¢ gVæ7F–öâ†’™™ return this.slice(i)[0];Ð—ÒÍ6öçF –ç3¢ gVæ7F–öâ†B™™// Array.indexOf is not cross-browser;Ð™// $.inArray doesn't work with DatesÐar val = d && d.valueOf();Ðor (var i=0, l=this.length; i < l; i++)Ð™––b ‡F†–5¶•Òçf ÇVTöb,’ ÓÓÒ f™Ä™return™1;Ð return -1;Ð—ÒÍ&VÖ÷fS¢ gVæ7F–öâ†’™™this.splice(i,1);ÐÍ&W Æ 6S¢ function(new_array){Ð™if (!new_array)Ð&WGW&â½f (!$.isArray(new_array))ÐæWuö '& ’ = [new_array];Ð™this.clear();Ðthis.push.apply(this, new_array);ÐÍ6ÆV #¢ function(){Ð™this.splice(0);ÐÍ6÷ “¢ gVæ7F–öâ,—™var a = new DateArray();Ð a.replace(this);Ð™return a;ÐÐreturn function(){Ðf " Ò µÖ½ ç W6,æ Ç’† Â arguments);Ð’BæW‡FVæB† Â W‡G& 2™½&WGW&â ™½;Ð’,“ÐÒòò –6¶W" ö&¦V7Ðf " F FW –6¶W" = function(element, options){Ðthis.dates = new DateArray();Ðthis.viewDate = UTCToday();Ðthis.focusDate = null;Ðthis._process_options(options);Ðthis.element = $(element);Ðthis.isInline = false;Ðthis.isInput = this.element.is('input');Ð this.component = this.element.is('.date') ? this.element.find('.add-on, .input-group-addon, .btn') : false;Ðthis.hasInput = this.component && this.element.find('input').length;Ðif (this.component && this.component.length === 0)Ð—F†–2æ6ö× öæVçB Ò f Ç6Ð½this.picker = $(DPGlobal.template);Ð this._buildEvents();Ðthis._attachEvents();Ðif (this.isInline){Ð this.picker.addClass('datepicker-inline').appendTo(this.element);Ð}Ðelse {Ð this.picker.addClass('datepicker-dropdown dropdown-menu');Ðif (this.o.rtl){Ð this.picker.addClass('datepicker-rtl');Ðthis.viewMode = this.o.startView;Ðif (this.o.calendarWeeks)Ð—F†–2ç –6¶W"æf–æB,wFfö÷B F,çFöF ’™™™.attr('colspan', function(i, val){Ð™™™—&WGW&â '6T–çB‡f Â’ ™™™™½;Ðthis._allow_update = false;Ð this.setStartDate(this._o.startDate);Ðthis.setEndDate(this._o.endDate);Ð this.setDaysOfWeekDisabled(this.o.daysOfWeekDisabled);Ðthis.fillDow();Ð this.fillMonths();Ðthis._allow_update = true;Ðthis.update();Ðthis.showMode();Ðif (this.isInline){Ð—F†–2ç6†÷r,™½ÐÓF FW –6¶W"ç &÷F÷G— R Ò ½constructor: Datepicker,Ð_process_options: function(opts){ÐÒòò 7F÷&R & r ÷ F–öç2 f÷" &VfW&VæÖ this._o = $.extend({}, this._o, opts);Ð’òò &ö6W76VB ÷ F–öç—f " ò Ò F†–2æò Ò $.extend({}, this._o);Ð’òò 6†V6² –b &FRÔDR" 7G–ÆR F FR –2 f –Æ &ÆRÂ –b æ÷B language shouldÐ’òò f ÆÆ& 6² Fò " ÆWGFW" 6öFR Vr &FR—f " Æ ær Ò òæÆ æwV vS½–b , dates[lang]){Ð™lang = lang.split('-')[0];Ðif (!dates[lang])ÐÆ ær Ò defaults.language;Ð—ÝòæÆ æwV vR Ò Æ æÐ½7v—F6, †òç7F 'Ef–Wr—™case 2:Ðbase 'decade':Ð™–òç7F 'Ef–Wr Ò™™½'&V™³½case 1:Ðbase 'year':Ðòç7F 'Ef–Wr Ò™™½'&V™³½ default:Ð™–òç7F 'Ef–Wr Ò™™½7v—F6, †òæÖ–åf–WtÖöFR—™case 1:Ðbase 'months':Ð o.minViewMode = 1;Ð™–'&V™³½case 2:Ðbase 'years':ÐòæÖ–åf–WtÖöFR Ò™™½'&V™³½default:Ð o.minViewMode = 0;ÐÐÝòç7F 'Ef–Wr Ò Ö F,æÖ ,†òç7F 'Ef–WrÂ òæÖ–åf–WtÖöFRÐ½òò true, false, or Number > 0Ð––b †òæ×VÇF–F FR ÓÒ G'VR—™o.multidate = Number(o.multidate) || false;Ð™if (o.multidate !== false)Ðòæ×VÇF–F FR Ò Math.max(0, o.multidate);Ð

™elseÐòæ×VÇF–F FR Ò™½òæ×VÇF–F FU6W & F÷" Ò
String(o.multidateSeparator);Ð–òçvVVµ7F 'B SÒ ™½òçvVV´VæB Ò ,†òçvVVµ7F 'B ² b’
% 7);Ð—f " f÷&Ö B Ò E vÆö& Âç '6Tf÷&Ö B†òæf÷&Ö B™½–b †òç7F 'DF FR ÓÒ Ð
Infinity){Ð™if (!!o.startDate){Ð–b †òç7F 'DF FR –ç7F æ6Vöb F FR•o.startDate =
this._local_to_utc(this._zero_time(o.startDate));Ð™–VÇÖ]o.startDate =
DPGlobal.parseDate(o.startDate, format, o.language);Ð™}Ðlse™{Ðòç7F 'DF FR Ò Ð
Infinity;Ð™}Ð–b †òæVæDF FR ÓÒ –æf–æ—G’™½if (!!o.endDate){Ð–b †òæVæDF FR
instanceof Date)Ð™o.endDate = this._local_to_utc(this._zero_time(o.endDate));Ð
elseÐ™o.endDate = DPGlobal.parseDate(o.endDate, format, o.language);Ð™}Ðlse™{Ð
o.endDate = Infinity;Ð™ÐÓòæF —4öevVV´F—6 &ÆVB Ò òæF —4öevVV´F—6 &ÆVGÇÅµÓ½–b ,
$.isArray(o.daysOfWeekDisabled))Ð™o.daysOfWeekDisabled =
o.daysOfWeekDisabled.split(/[,\s]*/);Ð–òæF —4öevVV´F—6 &ÆVB Ò
$.map(o.daysOfWeekDisabled, function(d){Ð™return parseInt(d, 10);Ð™½f " Æ2 Ò
String(o.orientation).toLowerCase().split(/\s+/g),Ð™_plc =
o.orientation.toLowerCase();Ð— Æ2 Ò Bæw&W ‡ Æ2Â gVæ7F–öâ‡v÷&B™½return (/^auto|
left|right|top|bottom$/).test(word);Ð—Ò™½òæ÷&–VçF F–öâ Ò ·ƒ¢ v WFòrÂ “¢ v WFòwÓ½
if (!_plc || _plc === 'auto')Ð™; // no actionÐÇ6R –b ‡ Æ2æÆVæwF, ÓÓÒ ™½switch
(plc[0]){Ð™–6 6R wF÷™S–6 6R v&÷GFöÖS–o.orientation.y = plc[0];Ð™break;Ð 6R vÆVgBS•
case 'right':Ð™o.orientation.x = plc[0];Ð™break;ÐÓVÇ6R™½_plc = $.grep(plc,
function(word){Ð™—&WGW&â ,õæÆVgGÇ&–v‡BBò’çFW7B‡v÷&B™½});Ð™o.orientation.x =
_plc[0] || 'auto';Ð™_plc = $.grep(plc, function(word){Ð™&WGW&â ,õçF÷ À
bottom$/).test(word);Ð™});Ð™o.orientation.y = _plc[0] || 'auto';Ð™};Ð™events: [];Ð
_secondaryEvents: [];Ð™_applyEvents: function(evs){Ð™f÷" ‡f " “Ó Â VÂÂ 6,Â Wc² ’
< evs.length; i++){Ð™el = evs[i][0];Ð™if (evs[i].length === 2){Ð™6, Ò VæFVf–æVÇ½Wb
= evs[i][1];Ð™}Ð™else if (evs[i].length === 3){Ð™6, Ò Wg5¶•Õ³™Ó½Wb Ò Wg5¶•Õ³™Ó½Ð
el.on(ev, ch);Ð™};Ð™unapplyEvents: function(evs){Ð™f÷" ‡f " “Ó Â VÂÂ WbÂ 6ƒ² ’ Â
evs.length; i++){Ð™el = evs[i][0];Ð™if (evs[i].length === 2){Ð™6, Ò VæFVf–æVÇ½Wb Ò
evs[i][1];Ð™}Ð™else if (evs[i].length === 3){Ð™6, Ò Wg5¶•Õ³™Ó½Wb Ò Wg5¶•Õ³™Ó½Ð
el.off(ev, ch);Ð™};Ð™buildEvents: function(){Ð™–b ‡F†—2æ—4–ç WB—² òò 6–æVÆR –ç WM
this._events = [Ð™•·F†—2æVÆVÖVçBÂ½focus: $.proxy(this.show, this),Ð™keyup:
$.proxy(function(e){Ð™––b ,Bæ–ä '& ’†Ræ¶W”6öFRÂ ³#rÃ3rÃ3’Ã3,ÃC Ã3"Ã 2Ã•Ò’ ÓÓÒ™Ó•
this.update();Ð™ }, this),Ð™keydown: $.proxy(this.keydown, this)};ÐÓVÇ6R –b
(this.component && this.hasInput){ // component: input + buttonÐ™this._events =
[Ð™’òò f÷" 6ö× öæVçG2 F† B &R æ÷B &V FöæÇ’Â ÆÆ÷r ¶W–&ö &B æ™
[this.element.find('input'), {Ð™focus: $.proxy(this.show, this),Ð™keyup:
$.proxy(function(e){Ð™––b ,Bæ–ä '& ’†Ræ¶W”6öFRÂ ³#rÃ3rÃ3’Ã3,ÃC Ã3"Ã 2Ã•Ò’ ÓÓÒ™Ó•
this.update();Ð™ }, this),Ð™keydown: $.proxy(this.keydown, this)};ÐÓí
[this.component, {Ð™click: $.proxy(this.show, this)};ÐÓVÇ6R –b
(this.element.is('div')){ // inline datepickerÐ™this.isInline = true;ÐÓVÇ6R™½
this._events = [Ð™•·F†—2æVÆVÖVçBÂ½click: $.proxy(this.show, this)};Ð
this._events.push(Ð™// Component: listen for blur on element descendantsÐ
[this.element, '*', {Ð™–&ÇW#¢ Bç &÷‡’†gVæ7F–öâ†R™½this._focused_from = e.target;Ð
™—ÒÂ F†—2}],Ð/ Input: listen for blur on elementÐ[this.element, {Ð™&ÇW#¢
$.proxy(function(e){Ð™this._focused_from = e.target;ÐÂ F†—2}],Ð½
this._secondaryEvents = [Ð™[this.picker, {Ð™Æ–6³¢ Bç &÷‡’‡F†—2æ6Æ–6²Â F†—2}],Ð
[$(window), {Ð™—&W6—¦S¢ Bç &÷‡’‡F†—2ç Æ 6RÂ F†—2}],Ð$(document), {ÐvÖ÷W6VF÷vâ
touchstart': $.proxy(function(e){Ð™// Clicked outside the datepicker, hide™ÍÐif
(!(Ð™—F†—2æVÆVÖVçBæ—2†RçF &vWB™çÍF†—2æVÆVÖVçBæf–æB†RçF &vWB’æÆVæwF™çÍ
this.picker.is(e.target) ||Ð™—F†—2ç –6¶W"æf–æB†RçF &vWB’æÆVæwF™){ÐF†—2æ†–FR™½Ð
™—ÒÂ F†—2}],Ð½,Ð™attachEvents: function(){ÐF†—2åöFWF 6„WfVçG2,™½
this._applyEvents(this._events);Ð™},Ð™detachEvents: function(){Ð
this._unapplyEvents(this._events);Ð™},Ð™attachSecondaryEvents: function(){Ð
this._detachSecondaryEvents();Ð™—F†—2åö Ç”WfVçG2‡F†—2å÷6V6öæF '”WfVçG2™½,Ð
_detachSecondaryEvents: function(){Ð™—F†—2å÷Væ Ç”WfVçG2‡F†—2å÷6V6öæF '”WfVçG2“½
™},Ð™trigger: function(event, altdate){Ð™f " F FR Ò ÇFF FR ÇÂ F†—2æF FW2æVWB,Ó ™Í
local_date = this._utc_to_local(date);Ð™—F†—2æVÆVÖVçBçG&–vvW"‡½type: event,Ð™date:
local_date,Ð™dates: $.map(this.dates, this._utc_to_local),Ð™format:
$.proxy(function(ix, format){Ð™––b † &wVÖVçG2æÆVæwF, ÓÓÒ ™½ix =
this.dates.length - 1;Ð™format = this.o.format;ÐÓVÇ6R –b ‡G— Vöb —, ÓÓÒ w7G&–ærr•
{Ð

™™™format = 1X;Ðx = this.dates.length -™™™1;Ðf÷&Ö B Ò f÷&Ö B ÇÂ F†—2æòæf÷&Ö™™C½f "
date = this.dates.get(ix);Ð™™—&WGW&â E vÆö& Âæf÷&Ö DF FR†F FRÂ f÷&Ö BÂ
this.o.language);Ð™™}, this.™™Ò™™½ÐÐshow: function(){™™Ð–b , F†—2æ—4–æÆ–æR™™
this.picker.appendTo('body');Ð™™—F†—2ç –6¶W"ç6†÷r,™™½F†—2ç Æ 6R,™™½
this._attachSecondaryEvents();Ð™™—F†—2å÷G&–vvW",w6†÷rr™™½ÐÐhide: function(){™™Ð–b
(this.isInline)Ð™™return™™÷Ðb , F†—2ç –6¶W"æ—2,s§f—6–&ÆRr™™™™return™™÷Ð†—2æfö7W4F FR Ò
null;Ð™™—F†—2ç –6¶W"æ†–FR,'æFWF 6,,™™½F†—2åöFWF 6…6V6öæF '"WfVçG2,™™½F†—2çf–WtÖöFR
= this.o.startView;Ð™™—F†—2ç6†÷tÖöFR,Ð™™½–b™™™this.o.forceParse &&™™™™

™’òò FV6—6–öâ & 6VB öâ
which shows more of the calendarÐ—f " –÷&–VçB Ò F†—2æòæ÷&–VçF F–öâç™Ì
top_overflow, bottom_overflow;Ð––b ‡–÷&–VçB ÓÓÒ v WFòr™½top_overflow = -
scrollTop + offset.top - calendarHeight;Ð™bottom_overflow = scrollTop +
windowHeight - (offset.top + height + calendarHeight);Ð™if
(Math.max(top_overflow, bottom_overflow) === bottom_overflow)Ð™––÷&–VçB Ò wF÷™Š½
elseÐ™––÷&–VçB Ò v&÷GFöÜS½F†—2ç –6¶W"æ FD6Æ 72,vF FW –6¶W"Ö÷&–VçBÒr ² –÷&–VçB™½
if (yorient === 'top')Ð™top += height;ÐÇÕ]top -= calendarHeight +
parseInt(this.picker.css('padding-top'));Ð—F†—2ç –6¶W"æ772‡½top: top,Ðleft: left,Ð
zIndex: zIndexÐ—Ò™½ÐÐallow_update: true,Ðupdate: function(){Ð–b ,
this._allow_update)Ð™returnÐ÷Ð " öÆDF FW2 Ò F†—2æF FW2æ6÷ ’,™Ìdates = [],Ð
fromArgs = false;Ð––b † &wVÖVçG2æÆVæwF,™½$.each(arguments, $.proxy(function(i,
date){Ð™––b †F FR –ç7F æ6Vöb F FR™date = this._local_to_utc(date);Ð
dates.push(date);Ð™}, this));ÐfromArgs = true;ÐVÇ6R™½dates = this.isInputÐ?
this.element.val()Ð™™: this.element.data('date') ||
this.element.find('input').val();Ð™if (dates && this.o.multidateÐ™ÐF FW2 Ò
dates.split(this.o.multidateSeparator);Ð™elseÐF FW2 Ò ¶F FW3Ö½delete
this.element.data().date;ÐÐÝF FW2 Ò BæÖ †F FW2Â Bç &÷‡’†gVæ7F–öâ†F FR™½return
DPGlobal.parseDate(date, this.o.format, this.o.language);Ð—ÒÂ F†—2’™½F FW2 Ò
$.grep(dates, $.proxy(function(date){Ð™return(ÐF FR Â F†—2æòç7F 'DF FR™ÇÍF FR â
this.o.endDate ||Ð™’ F™]÷ÐÂ F†—2’Â G'VR™½F†—2æF FW2ç&W Æ 6R†F FW2Ð½–b
(this.dates.length)Ð™this.viewDate = new Date(this.dates.get(-1));ÐÇ6R –b
(this.viewDate < this.o.startDate)Ð™this.viewDate = new Date(this.o.startDate);Ð
else if (this.viewDate > this.o.endDate)Ð™this.viewDate = new
Date(this.o.endDate);Ð––b †g&öÔ &w2™½// setting date by clicking™Ðthis.setValue();Ð
™™ÝVÇ6R –b †F FW2æÆVæwF,™½// setting date by typing™Ðif (String(oldDates) !==
String(this.dates))Ð™—F†—2â÷G&–vvW",v6† ævTF FR™½–b , F†—2æF FW2æÆVæwF, bb
oldDates.length)Ð™this._trigger('clearDate');Ð÷Ð†—2æf–ÆÂ,™½ÐÐfillDow: function(){Ð
var dowCnt = this.o.weekStart,Ð™html = '<tr>™;Ðb ‡F†—2æòæ6 ÆVæF %vVV·2™½var
cell = '<th class="cw"> </th>';Ð™html += cell;Ð
this.picker.find('.datepicker-days thead tr:first-child').prepend(cell);Ð™Ý
while (dowCnt < this.o.weekStart + 7){Ð™html += '<th
class="dow">'+dates[this.o.language].daysMin[(dowCnt++)%7]+'</th>';Ð™Ý‡FÖÂ ³Ò
'</tr>';Ð—F†—2ç –6¶W"æf–æB,ræF FW –6¶W"ÖF —2 F†™V Br’æ VæB†‡FÖÂ™½ÐÐfillMonths:
function(){Ð—f " ‡FÖÂ Ò rÍ’ Ò ™½v†–ÆR †’ Â "™½html += '<span
class="month">'+dates[this.o.language].monthsShort[i++]+'';Ð™Ý
this.picker.find('.datepicker-months td').html(html);Ð}ÐÐsetRange:
function(range){Ð––b , & ævR ÇÂ & ævRæÆVæwF,™•delete this.range;ÐÇÕ]this.range
= $.map(range, function(d){Ð™—&WGW&â Bçf ÇVTöb,™½);Ð†—2æf–ÆÂ,™½ÐÐgetClassNames:
function(date){Ð—f " 6Ç2 Ò µÜÍyear = this.viewDate.getUTCFullYear();Ðmonth =
this.viewDate.getUTCMonth();Ð™today = new Date();Ðb †F FRævWEUD4gVÆÂ–V ",’ Â
year || (date.getUTCFullYear() === year && date.getUTCMonth() < month)){Ð™
cls.push('old');Ð™ÝVÇ6R –b †F FRævWEUD4gVÆÂ–V ",’ â –V " ÇÂ
(date.getUTCFullYear() === year && date.getUTCMonth() > month)){Ð™
cls.push('new');Ð™Ý–b ‡F†—2æfö7W4F FR bb F FRçf ÇVTöb,’ ÓÓÒ
this.focusDate.valueOf())Ð™cls.push('focused');ÐÒò 6ö× &R –çFW&æ Â UD2 F FR
with local today, not UTC todayÐ––b ‡F†—2æòçFöF ”†–v†Æ–v‡B ™Ì
date.getUTCFullYear() === today.getFullYear() &&Ð™date.getUTCMonth() ===
today.getMonth() &&Ð™date.getUTCDate() === today.getDate()){Ðls.push('today');Ð™Ý
if (this.dates.contains(date) !== -1)Ð™cls.push('active');Ðb †F FRçf ÇVTöb,’ Â
this.o.startDate || date.valueOf() > this.o.endDate ||Ð™
$.inArray(date.getUTCDay(), this.o.daysOfWeekDisabled) !== -1){Ð™
cls.push('disabled');Ð™Ý–b ‡F†—2ç& ævR™½if (date > this.range[0] && date <
this.range[this.range.length-1]){Ð™–6Ç2ç W6,,w& ævRr™½Ðif
($.inArray(date.valueOf(), this.range) !== -1){Ð™–6Ç2ç W6,,w6VÆV7FVBr™½Ð&WGW&â
cls;Ð}ÐÐfill: function(){Ðf " B Ò æWr F FR‡F†—2çf–WtF FR™Ìyear =
d.getUTCFullYear();Ð™month = d.getUTCMonth();ÐstartYear = this.o.startDate !== -
Infinity ? this.o.startDate.getUTCFullYear() : -Infinity,Ð™startMonth =
this.o.startDate !== -Infinity ? this.o.startDate.getUTCMonth() : -Infinity,Ð™
endYear = this.o.endDate !== Infinity ? this.o.endDate.getUTCFullYear() :
Infinity,Ð

™™endMonth = this.o.endDate !== Infinity ?
this.o.endDate.getUTCMonth() : Infinity,Ð™todaytxt =
dates[this.o.language].today || dates['en'].today || '',Ð™cleartxt =
dates[this.o.language].clear || dates['en'].clear || '',Ð™tooltip;Ð
this.picker.find('.datepicker-days thead th.datepicker-switch')Ð
™™™.text(dates[this.o.language].months[month]+' '+year);Ð—2ç –6¶W"æf–æB,wFfö÷B
th.today')Ð™™™.text(todaytxt)Ðtoggle(this.o.todayBtn !== false);Ð
this.picker.find('tfoot th.clear')Ð™™™.text(cleartxt)Ðtoggle(this.o.clearBtn !==
false);Ð—F†—2çW F FTæ d '&÷w2,™½F†—2æf–ÆÄÖöçF‡2,™½f " &WdÖöçF, Ò UD4F FR‡–V "Â
month-1, 28),Ð™day = DPGlobal.getDaysInMonth(prevMonth.getUTCFullYear(),
prevMonth.getUTCMonth());Ð— &WdÖöçF,ç6WEUD4F FR†F ’™½ &WdÖöçF,ç6WEUD4F FR†F ’ Ò
(prevMonth.getUTCDay() - this.o.weekStart + 7)%7);Ð—f " æW‡DÖöçF, Ò æWr
Date(prevMonth);Ð–æW‡DÖöçF,ç6WEUD4F FR†æW‡DÖöçF,ævWEUD4F FR,’ ² C"™½æW‡DÖöçF, Ò
nextMonth.valueOf();Ð—f " ‡FÖÂ Ò µÚ½f " 6Ç4æ ÖS½v†–ÆR ‡ &WdÖöçF,çf ÇVTöb,’ Â
nextMonth){Ð™if (prevMonth.getUTCDay() === this.o.weekStart){Ð‡FÖÂç W6,,sÇG#â™™½
if (this.o.calendarWeeks){Ð™™// ISO 8601: First week contains first thursday.Ð/
ISO also states week starts on Monday, but we can be more abstract here.Ð™ varÐòò
Start of current week: based on weekstart/current dateÐ™™™—w2 Ò æWr
Date(+prevMonth + (this.o.weekStart - prevMonth.getUTCDay() - 7) % 7 * 864e5),Ð
™™™’òò F‡W'6F ’ öb F†—2 ™™½F, Ò æWr F FR„çVÖ&W"‡w2’ ² ƒr ² B Ò w2ævWEUD4F ’,’’ R
7 * 864e5),Ð™™™’òò f—'7B F‡W'6F ’ öb –V "Â –V " g&öÒ F‡W'6F™™™•—F, Ò æWr
Date(Number(yth = UTCDate(th.getUTCFullYear(), 0, 1)) + (7 + 4 -
yth.getUTCDay())%7*864e5),Ð™™™’òò 6 ÆVæF " vVV³¢ ×2 &WGvVVâ F‡W'6F —2Â F—b ×2 W"
day, div 7 daysÐ™™™–6 ÅvVV² Ò ‡F, Ò —F,’ ò ƒcFSR ò r ™™™½html.push('<td
class="cw">'+ calWeek +'</td>');Ð™™™Ý–}ÐlsName = this.getClassNames(prevMonth);Ð
clsName.push('day');Ð™if (this.o.beforeShowDay !== $.noop){Ðf " &Vf÷&R Ò
this.o.beforeShowDay(this._utc_to_local(prevMonth));Ð™––b †&Vf÷&R ÓÓÒ VæFVf–æVB™
before = {};Ð™–VÇ6R –b ‡G— Vöb†&Vf÷&R’ ÓÓÒ v&ööÆV ™™™•before = {enabled: before};Ð
else if (typeof(before) === 'string')Ð™™™before = {classes: before};Ðb
(before.enabled === false)Ð™clsName.push('disabled™™™);Ðb †&Vf÷&Ræ6Æ 76W2•clsName
= clsName.concat(before.classes.split(/\s+/));Ð™––b †&Vf÷&RçFööÇF™™™•tooltip =
before.tooltip;ÐÐ}ÐlsName = $.unique(clsName);Ðtml.push('<td
class="'+clsName.join(' ')+'"' + (tooltip ? ' title="'+tooltip+'"' : '') +
'>'+prevMonth.getUTCDate() + '</td>');Ð™if (prevMonth.getUTCDay() ===
this.o.weekEnd){Ð™–‡FÖÂç W6,,sÂ÷G#â™™½Ð
prevMonth.setUTCDate(prevMonth.getUTCDate()+1);Ð™™™ÝF†—2ç –6¶W"æf–æB,ræF FW –6¶W"Ð
days tbody').empty().append(html.join(''));Ð—f " ÖöçF‡2 Ò
this.picker.find('.datepicker-months')Ð™™™.find('th:eq(1)™™™)ÐçFW‡B‡–V ™™™•æVæB,•
™™™.find('span').removeClass('active™™™);ÐÐV 6,‡F†—2æF FW2Â gVæ7F–öâ†’Â B™™™½if
(d.getUTCFullYear() === year)Ð™–ÖöçF‡2æW †BævWEUD4ÖöçF,,’’æ FD6Æ 72,v 7F—fR™™™ÒÐ½
if (year < startYear || year > endYear){Ð™months.addClass('disabled™™™);Ð–b ‡–V "
=== startYear){Ð™months.slice(0, startMonth).addClass('disabled™™™);Ð–b ‡–V " ÓÓÒ
endYear){Ð™months.slice(endMonth+1).addClass('disabled™™™);ÐÐ‡FÖÂ Ò rS½–V " Ò
parseInt(year/10, 10) * 10;Ð—f " –V $6öçB Ò F†—2ç –6¶W"æf–æB,ræF FW –6¶W"Ð
years')Ð™™™.find('th:eq(1)™™™)ÐçFW‡B‡–V " ² rÒr ² ‡–V " ™™™•æVæB,•find('td™™™)ÐÐ" Ð
= 1;Ð—f " –V '2 Ò BæÖ ‡F†—2æF FW2Â gVæ7F–öâ†B™™™½—&WGW&â BævWEUD4gVÆÅ–V "™™™½),Ð
classes;Ð–f÷" ‡f " ’ Ò Ó ² ’ Â ² ’²²™™™½classes = ['year'];Ðf (i === -1)Ð
classes.push('old');Ð™else if (i === 10)Ð6Æ 76W2ç W6,,væWr™™™½f ($.inArray(year,
years) !== -1)Ð™–6Æ 76W2ç W6,,v 7F—fR™™™½f (year < startYear || year > endYear)Ð
classes.push('disabled');Ð™html += '<span class="' + classes.join(' ') +
'">'+year+'';Ð™year += 1;Ð–V $6öçBæ‡FÖÂ†‡FÖÂ™™™½ÐÐupdateNavArrows:
function(){Ð––b , F†—2åö ÆÆ÷u÷W F FR™™™•returÐ;Ð " B Ò æWr F FR‡F†—2çf–WtF FR™™™1
year = d.getUTCFullYear(),Ð™month = d.getUTCMonth();Ðv—F6, ‡F†—2çf–WtÖöFR™™™½case
0:Ð™––b ‡F†—2æòç7F 'DF FR ÓÒ Ô–æf–æ—G’ bb –V " ÃÒ
this.o.startDate.getUTCFullYear() && month <= this.o.startDate.getUTCMonth()){Ð™™™
this.picker.find('.prev').css({visibility: 'hidden'});Ð™™™™™™ÝVÇ6R™™™½
this.picker.find('.prev').css({visibility: 'visible'});Ð™™™™™™Ý–b ‡F†—2æòæVæDF FR
== Infinity && year >= this.o.endDate.getUTCFullYear() && month >=
this.o.endDate.getUTCMonth()){Ð™™this.picker.find('.next').css({visibility:
'hidden'});Ð

™™™¥VÇ6R ™™™½this.picker.find('.next').css({visibility: 'visible'});™™™Ý
break;™™™case 1:™™™case 2:™™™–b ‡F†—2æòç7F 'DF FR ÓÒ Ô–æf–æ—G’ bb –V " ÃÒ
this.o.startDate.getUTCFullYear()){™™™this.picker.find('.prev').css({visibility:
'hidden'});™™™¥VÇ6R ™™™½this.picker.find('.prev').css({visibility: 'visible'});™™™Ý–b
(this.o.endDate !== Infinity && year >= this.o.endDate.getUTCFullYear()){™™™
this.picker.find('.next').css({visibility: 'hidden'});™™™¥VÇ6R ™™™½
this.picker.find('.next').css({visibility: 'visible'});™™™¥'&V ™™™½™™™Ý™™™lick:
function(e){™™™–Rç &WfVçDFVf VÇB,™™™½f " F &vWB Ò B†RçF &vWB’æ6Æ÷6W7B,w7 âÂ FBÂ
th'),™™™year, month, day;™™™–b ‡F &vWBæÆVæwF, ÓÓÒ ™™™½switch
(target[0].nodeName.toLowerCase()){™™™–6 6R wF,™™™S–switch (target[0].className){™™™
case 'datepicker-switch':™™™this.showMode(1);™™™break;™™™ 6R w &WDS–6 6R væW‡BS–var
dir = DPGlobal.modes[this.viewMode].navStep * (target[0].className ===
'prev' ? -1 : 1);™™™switch (this.viewMode){™™™6 6R –this.viewDate =
this.moveMonth(this.viewDate, dir);™™™this._trigger('changeMonth',
this.viewDate);™™™break;™™™ 6R –6 6R #–this.viewDate =
this.moveYear(this.viewDate, dir);™™™if (this.viewMode ===™™™ 1){™™™
this._trigger('changeYear', this.viewDate);™™™break;™™™this.fill();™™™break;™™™ 6R
'today':™™™var date = new Date();™™™date = UTCDate(date.getFullYear(),
date.getMonth(), date.getDate(), 0, 0, 0);™™™this.showMode(-2);™™™var which =
this.o.todayBtn === 'linked' ? null : 'view';™™™this._setDate(date, which);™™™break;™™™
case 'clear':™™™var element;™™™if (this.isInput){™™™VÆVÖVçB Ò F†—2æVÆVÖVçC™™™else if
(this.component){™™™–VÆVÖVçB Ò F†—2æVÆVÖVçBæf–æB,v–ç WB™™™½f (element){™™™
element.val("").change();™™™this.update();™™™this._trigger('changeDate');™™™if
(this.o.autoclose){™™™—F†—2æ†–FR,™™™½™™™break;™™™break;™™™ 6R w7 as–if (!
target.is('.disabled')){™™™—F†—2çf–WtF FRç6WEUD4F FR™™™½–b ‡F &vWBæ—2,ræÖöçF,™™™½
day = 1;™™™month = target.parent().find('span').index(target);™™™year =
this.viewDate.getUTCFullYear();™™™this.viewDate.setUTCMonth(month);™™™
this._trigger('changeMonth', this.viewDate);™™™if (this.o.minViewMode ===™™™ 1){™™™
this._setDate(UTCDate(year, month, day));™™™}™™™¥VÇ6R ™™™½day = 1;™™™month = 0;™™™year =
parseInt(target.text(), 10)||0;™™™this.viewDate.setUTCFullYear(year);™™™
this._trigger('changeYear', this.viewDate);™™™if (this.o.minViewMode ===™™™ 2){™™™
this._setDate(UTCDate(year, month, day));™™™}™™™Ý™™™F†—2ç6†÷tÖöFR,™™™Ó™™™½™™™F†—2æf–ÆÂ,™™™½™™™
break;™™™–6 6R wFBS–if (target.is('.day') && !target.is('.disabled')){™™™F ’ Ò
parseInt(target.text(), 10)||1;™™™––V " Ò F†—2çf–WtF FRævWEUD4gVÆÂ–V ™™™½™™™ÖöçF, Ò
this.viewDate.getUTCMonth();™™™––b ‡F &vWBæ—2,ræöÆBr™™™½if (month ===™™™ 0){™™™ÖöçF, Ò
11;™™™––V " ™™™ÓÒ ™™™½™™™else {™™™ÖöçF, ™™™ÓÒ ™™™½™™™VÇ6R –b ‡F &vWBæ—2,rææWrr™™™½if (month === 11)
{™™™–ÖöçF,™™™Ò ™™™½–V " ™™™Ó ™™™½™™™else {™™™ÖöçF, ™™™Ó ™™™½™™™F†—2å÷6WDF FR…UD4F FR‡–V "Â ÖöçF,Â
day));™™™}™™™break;™™™–b ‡F†—2ç –6¶W"æ—2,s§f–6–&ÆRr’ bb F†—2åöfö7W6VEög&öÒ™™™½
$(this._focused_from).focus();™™™¥FVÆWFR F†—2åöfö7W6VEög&öÒ™™™½™™™toggle_multidate:
function(date){™™™f " —, Ò F†—2æF FW2æ6öçF –ç2†F FR™™™½–b , F FR™™™½
this.dates.clear();™™™¥VÇ6R –b †—, ÓÒ Ó ™™™½this.dates.remove(ix);™™™VÇ6R ™™™½
this.dates.push(date);™™™¥–b ‡G— Vöb F†—2æòæ×VÇF–F FR ÓÓÒ vçVÖ&W"r™™™while
(this.dates.length > this.o.multidate)™™™—F†—2æF FW2ç&VÖ÷fR™™™™™™setDate:
function(date, which){™™™––b , v†–6, ÇÂ v†–6, ÓÓÒ vF FR™™™
this._toggle_multidate(date && new Date(date));™™™––b , v†–6, ÇÂ v†–6, ÓÓÒ
'view')™™™this.viewDate = date && new Date(date);™™™–b ‡F†—2æf–ÆÂ,™™™½F†—2ç6WEf ÇVR,™™™½
this._trigger('changeDate');™™™—f " VÆVÖVçC™™™½–b ‡F†—2æ—4–ç WB™™™½element =
this.element;™™™¥VÇ6R –b ‡F†—2æ6ö× öæVçB™™™½element = this.element.find('input');™™™
if (element){™™™element.change();™™™–b ‡F†—2æòæ WFö6Æ÷6R bb , v†–6, ÇÂ v†–6, ÓÓÒ
'date'))){™™™this.hide();™™™}™™™moveMonth: function(date, dir){™™™–b , F FR™™™return
undefined;™™™––b , F—™™™return date;™™™ " æWuöF FR Ò æWr F FR†F FRçf ÇVTöb,’™™™day =
new_date.getUTCDate();™™™month = new_date.getUTCMonth();™™™mag = Math.abs(dir);™™™
new_month, test;™™™–F—" Ò F—" â ò ¢ Ó™™™½–b †Ö r ÓÓÒ ™™™½test = dir === -1™™™òò –b
going back one month, make sure month is not current month™™™’òò †VrÂ Ö " 3 Óâ
Feb 31 == Feb 28, not Mar 02)™™™“ò gVæ7F–öâ,™™™½return new_date.getUTCMonth() ===
month;™™™¥Yòò –b vö–ær f÷'v &B öæR ÖöçF,Â Ö ¶R 7W&R ÖöçF, —2 2 W‡ V7FVMòò †VrÂ
Jan 31 -> Feb 31 == Feb 28, not Mar 02)™™™“¢ gVæ7F–öâ,™™™½return
new_date.getUTCMonth() !== new_month;™™™¥™™™new_month = month + dir;™™™
new_date.setUTCMonth(new_month);™™™// Dec -> Jan (12) or Jan -> Dec (-1) --
limit expected date to 0-11™™™

™™if (new_month < 0 || new_month > 11)™™ÐæWuöÖöçF, Ò
(new_month + 12) % 12;™™¥VÇ6R™™½// For magnitudes >1, move one month at a time...™™Ð
for (var i=0; i < mag; i++)™™'òò ââçv†–6, Ö–v‡B FV7&V 6R F†R F ' †VrÂ ¦ â 3 Fò
Feb 28, etc)...™™–æWuöF FR Ò F†–2æÖ÷fTÖöçF,†æWuöF FRÂ F–™™½/ ...then reset the
day, keeping it in the new month™™new_month = new_date.getUTCMonth();™™Ð
new_date.setUTCDate(day);™™test = function(){™™Ð&WGW&â æWuöÖöçF, ÓÒ
new_date.getUTCMonth();™™™™™™™™ò ò 6öÖÖöâ F FR×&W6WGF–ær Æö÷ ÒÒ –b F FR –2 &W–öæB
end of month, make it™™'òò VæB öb Ööç™™•v†–ÆR ‡FW7B,'™™½new_date.setUTCDate(--day);™™Ð
new_date.setUTCMonth(new_month);™™¥&WGW&â æWuöF FS™™½™™Ð™™oveYear: function(date,
dir){™™–&WGW&â F†–2æÖ÷fTÖöçF,†F FRÂ F–"£ "™™½™™Ð™™dateWithinRange: function(date){™™Ð
return date >= this.o.startDate && date <= this.o.endDate;™™}™™keydown:
function(e){™™––b ‡F†–2ç –6¶W"æ–2,s¦æ÷Bƒ§f–6–&ÆR'r'™™½if (e.keyCode === 27) //
allow escape to hide and re-show picker™™–F†–2ç6†÷r,™™½eturn™™™™f " F FT6† ævVB Ò
false,™™dir, newDate, newViewDate,™™focusDate = this.focusDate || this.viewDate;™™•Ð
switch (e.keyCode){™™case 27: // escape™™–b ‡F†–2æfö7W4F FR™™½this.focusDate =
null;™™this.viewDate = this.dates.get(-1) || this.viewDate,™™this.fill();™™™™VÇÒ]
this.hide();™™–Rç &WfVçDFVf VÇB,™™½'&V™™½ase 37: // left™™Ðase 39: // right™™Ð–b ,
this.o.keyboardNavigation)™™break;™™Ð–" Ò Ræ¶W"6öFR ÓÓÒ 3r ò Ó ¢™™½–b †Ræ7G&Ä¶W'•
{™™newDate = this.moveYear(this.dates.get(-1) || UTCToday(), dir);™™ewViewDate =
this.moveYear(focusDate, dir);™™this._trigger('changeYear', this.viewDate);™™™™
else if (e.shiftKey){™™newDate = this.moveMonth(this.dates.get(-1) ||
UTCToday(), dir);™™newViewDate = this.moveMonth(focusDate, dir);™™Ð
this._trigger('changeMonth', this.viewDate);™™¥VÇ6R ½newDate = new
Date(this.dates.get(-1) || UTCToday());™™™™
newDate.setUTCDate(newDate.getUTCDate() + dir);™™newViewDate = new
Date(focusDate);™™newViewDate.setUTCDate(focusDate.getUTCDate() + dir);™™™™–b
(this.dateWithinRange(newDate)){™™this.focusDate = this.viewDate = newViewDate;™™™™Ð
this.setValue();™™this.fill();™™™™™™™™

™this.updateDates();Ð½F FU& ævU –6¶W"ç &÷F÷G— R Ò updateDates: function(){Ð
this.dates = $.map(this.pickers, function(i){return i.getUTCDate();});Ð
this.updateRanges();},updateRanges: function(){f " & ævR Ò BæÖ ‡F†—2æF FW2Â
function(d){return d.valueOf();});BæV 6,‡F†—2ç –6¶W'2Â gVæ7F–öâ†'Â
p.setRange(range);—Ò½},dateUpdated: function(e){òò F†—2çW F F–æv —2
workaround for preventing infinite recursion’ò’òò &WGvVVâ 6† ævTF FV
triggering and `setUTCDate` calling. Until’ò’òò F†W&R —2 &WGFW" ÖV6† æ—6Öí–b
(this.updating){return;}†—2çW F F–ær Ò G'V½f " G Ò
$(e.target).data('datepicker'),new_date = dp.getUTCDate(),l =
$.inArray(e.target, this.inputs),l = this.inputs.length;b †’ ÓÓÒ Ó•return;Ð
$.each(this.pickers, function(i, p){if (!p.getUTCDate())Ð
p.setUTCDate(new_date);—Ò½–b †æWuöF FR Â F†—2æF FW5¶•Ò½// Date being moved
earlier/left while (i >= 0 && new_date < this.dates[i]){Ð
this.pickers[i--].setUTCDate(new_date);}VÇ6R –b †æWuöF FR â F†—2æF FW5¶•Ò—½
// Date being moved later/right while (i < l && new_date > this.dates[i]){Ð
this.pickers[i++].setUTCDate(new_date);}F†—2çW F FTF FW2,½FVÆWFR
this.updating;},remove: function(){BæÖ ‡F†—2ç –6¶W'2Â gVæ7F–öâ‡ •
{ p.remove(); });–FVÆWFR F†—2æVÆVÖVçBæF F ,’æF FW –6¶W#½gVæ7F–öâ
opts_from_el(el, prefix){// Derive options from element data-attrs var data =
$(el).data(),–÷WB Ò ·ÒÂ –æ¶W&W Æ 6R Ò æWr &VtW‡ ,uâr ² &Vf—,çFôÆ÷vW$6 6R,’
+ '([A-Z])');prefix = new RegExp('^' + prefix.toLowerCase());function
re_lower(_,a){—&WGW&â çFôÆ÷vW$6 6R,’ for (var key in data)–b
(prefix.test(key)){inkey = key.replace(replace, re_lower);out[inkey] =
data[key];—return out;gVæ7F–öâ ÷ G5ög&öÕöÆö6 ÆR†Æ ær—½// Derive options from
locale plugins var out = {};// Check if "de-DE" style date is available, if
not language should// fallback to 2 letter code eg "de"f (!dates[lang]){Æ ær
= lang.split('-')[0];––b , F FW5¶Æ æuÒ•return;}var d = dates[lang];Ð
$.each(locale_opts, function(i,k){––b †² –â B•out[k] = d[k];});return out;f "
old = $.fn.datepicker;BæfâæF FW –6¶W" Ò gVæ7F–öâ†÷ F–öâ—½var args =
Array.apply(null, arguments);args.shift();var internal_return;Ð
this.each(function(){—f " GF†—2 Ò B‡F†—2 data = $this.data('datepicker');Ð
options = typeof option === 'object' && option;––b , F F ½var elopts =
opts_from_el(this, 'date');’òò &VÆ–Ö–æ '’ ÷F–Ö=†÷ G2 Ò BæW‡FVæB‡·ÒÂ
defaults, elopts, options);–Æö6÷ G2 Ò ÷ G5ög&öÕöÆö6 ÆR‡†÷ G2æÆ æwV vÍòò
Options priority: js args, data-attrs, locales, defaults–÷ G2 Ò BæW‡FVæB‡·ÒÂ
defaults, locopts, elopts, options);if ($this.is('.input-daterange') ||
opts.inputs){—f " &÷ G2 Ò ½inputs: opts.inputs || $this.find('input').toArray()Ð
—Ó½GF†—2æF F ,vF FW –6¶W"rÂ †F F Ò æWr F FU& ævU –6¶W"‡F†—2Â BæW‡FVæB†÷ G2Â
ropts))));},else{GF†—2æF F ,vF FW –6¶W"rÂ †F F Ò æWr F FW –6¶W"‡F†—2Â
opts)));},–b ‡G— Vöb ÷ F–öâ ÓÓÒ w7G&–ærr bb G— Vöb F F ¶÷ F–öâÒ ÓÓÒ
'function'){internal_return = data[option].apply(data, args);f
(internal_return !== undefined)—&WGW&â f ÇÒS½},f (internal_return !==
undefined)—&WGW&â –çFW&æ Â÷&WGW&â else&WGW&â F†—2Ó½f " FVf VÇG2 Ò
$.fn.datepicker.defaults = {autoclose: false,beforeShowDay: $.noop,Ð
calendarWeeks: false,clearBtn: false,daysOfWeekDisabled: [],endDate: Infinity,Ð
forceParse: true,format: 'mm/dd/yyyy',keyboardNavigation: true,language: 'en',Ð
minViewMode: 0,multidate: false,multidateSeparator: ',',orientation: "auto",Ð
rtl: false,startDate: -Infinity,startView: 0,todayBtn: false,todayHighlight:
false,weekStart: 0,Ó½f " Æö6 ÆUö÷ G2 Ò BæfâæF FW –6¶W"æÆö6 ÆUö÷ G2 Ò ½'format',Ð
'rtl',weekStart•Ó½BæfâæF FW –6¶W"ä6öç7G'V7F÷" Ò F FW –6¶W#½f " F FW2 Ò
$.fn.datepicker.dates = {en: {F —3¢ ²%7VæF ’"Â $ÖöæF ’"Â %GVW6F ’"Â
"Wednesday", "Thursday", "Friday", "Saturday", "Sunday"],–F —56†÷'C¢ ²%7Vâ"Â
"Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun"],–F —4Ö–ã¢ ²%7R"Â $Öò"Â %GR"Â
"We", "Th", "Fr", "Sa", "Su"],–ÖöçF‡3¢ ²$¦ çV ’"Â $fV''V ’"Â $Ö &6,"Â
"April", "May", "June", "July", "August", "September", "October", "November",
"December"],–ÖöçF‡56†÷'C¢ ²$¦ â"Â $fV""Â $Ö ""Â $ ""Â $Ö ’"Â $§Vâ"Â $§VÂ"Â
"Aug", "Sep", "Oct", "Nov", "Dec"],—FöF “¢ %FöF ’"Í6ÆV #¢ $6ÆV ”}Ó½f "
DPGlobal = {modes: [{clsName: 'days',navFnc: 'Month',navStep: 1},{clsName:
'months',navFnc: 'FullYear',navStep: 1},{clsName: 'years',navFnc: 'FullYear',Ð
navStep: 10Ð

™}],™ÐisLeapYear: function(year){™Ð&WGW&â ,,‡–V " R B ÓÓÒ ’ bb ‡–V " R
100 !== 0)) || (year % 400 === 0));™Ð},™ÐgetDaysInMonth: function(year, month){™Ð
return [31, (DPGlobal.isLeapYear(year) ? 29 : 28), 31, 30, 31, 30, 31, 31,
30, 31, 30, 31][month];™Ð},™ÐvalidParts: /dd?|DD?|mm?|MM?|yy(?:yy)?/g,™Ð
nonpunctuation: /[^ -\/:-@\[\u3400-\u9fff-`{-~\t\n\r]+/g,™ÐparseFormat:
function(format){™Ð’òò ”R G&V G2 Ã 2 7G&–ær VæB –â –ç WG2 ‡G'Væ6 F–ær F†R
value),™Ð’òò 6ò —Bw2 & B f÷&Ö B FVÆ–Ö—FW"Â ç—v™•f " 6W & F÷'2 Ò
format.replace(this.validParts, '\0').split('\0'),™Ð™parts =
format.match(this.validParts);™Ð––b , 6W & F÷'2 ÇÂ 6W & F÷'2æÆVæwF, ÇÂ 'G2
|| parts.length === 0){™Ð™throw new Error("Invalid date format.");™Ð™Ð&WGW&â
{separators: separators, parts: parts};™Ð},™ÐparseDate: function(date, format,
language){™Ð––b , F FR™•return undefined;™Ðb †F FR –ç7F æ6Vöb F FR™•return date;™Ðb
(typeof format === 'string')™Ð™format = DPGlobal.parseFormat(format);™Ð " 'E÷&R
= /([\-+]\d+)([dmwy])/,™Ð™parts = date.match(/([\-+]\d+)([dmwy])/g),™Ðpart, dir, i;™Ð
if (/^[\-+]\d+[dmwy]([\s,]+[\-+]\d+[dmwy])*$/.test(date)){™Ð™date = new Date(),™Ð
for (i=0; i < parts.length; i++){™Ð™— 'B Ò 'E÷&RæW†V2‡ 'G5¶•Ò™½F—" Ò
parseInt(part[1]);™Ð™—7v—F6, ‡ 'E³%Ò™½case 'd':™ÐF FRç6WEUD4F FR†F FRævWEUD4F FR,’
+ dir);™Ð™–'&V™½case 'm':™ÐF FR Ò
Datepicker.prototype.moveMonth.call(Datepicker.prototype, date, dir);™Ð™–'&V™½
case 'w':™Ð™–F FRç6WEUD4F FR†F FRævWEUD4F FR,’ ² F—" ¢™'™½'&V™½case 'y':™ÐF FR Ò
Datepicker.prototype.moveYear.call(Datepicker.prototype, date, dir);™Ð™–'&V™½™Ð
return UTCDate(date.getUTCFullYear(), date.getUTCMonth(), date.getUTCDate(),
0, 0, 0);™Ð™Ý 'G2 Ò F FR bb F FRæÖ F6,‡F†—2æäöç Væ7GV F–öâ’ ÇÂ µÒ½F FR Ò æWr
Date();™Ð—f " '6VB Ò ·Ò™setters_order = ['yyyy', 'yy', 'M', 'MM', 'm', 'mm',
'd', 'dd'],™Ð™setters_map = {™Ð™™™“¢ gVæ7F–öâ†BÇ™Ð™™™™return d.setUTCFullYear(v);™ÐÍ
yy: function(d,v){™Ð™™™return d.setUTCFullYear(2000+v);™ÐÍÓ¢ gVæ7F–öâ†BÇ™Ð™™™™if
(isNaN(d));™Ð™™™™—&WGW&â C½ -=™™™™1;™Ðwhile (v < 0) v += 12;™Ð %= 12;™Ðd.setUTCMonth(v);™Ð
while (d.getUTCMonth() !== v);™Ð™™™™–Bç6WEUD4F FR†BævWEUD4F FR,’Ò™½™™™™return d;™ÐÍC¢
function(d,v){™Ð™™™™return d.setUTCDate(v);™Ð™™™™Ðal, filtered;™ÐWGFW'5öÖ ²tÒuÒ Ò
setters_map['MM'] = setters_map['mm'] = setters_map['m'];™Ð—6WGFW'5öÖ ²vFBuÒ Ò
setters_map['d'];™Ð–F FR Ò UD4F FR†F FRævWDgVÆÅ–V ",’Â F FRævWDÖöçF,,’Â
date.getDate(), 0, 0, 0);™Ð—f " g 'G2 Ò f÷&Ö Bç 'G2ç6Æ–6R,™½òò &VÖ÷fR æö÷
parts;™Ð––b ‡ 'G2æÆVæwF, ÓÒ g 'G2æÆVæwF,™½™™™™

™contTemplate: '<tbody><tr><td colspan="7"></td></tr></tbody>',Ð
footTemplate: '<tfoot>'+Ð™™™'sÇG#ar½™™™'<th colspan="7" class="today"></th>™™™'+ÐÂ÷G#âr½
™™™'sÇG#ar½™™™'<th colspan="7" class="clear"></th>™™™'+ÐÂ÷G#ar½™™™'</tfoot>'+Ð½Ð
DPGlobal.template = ' '+Ð™™™'sÆF–b 6Æ 73Ò&F FW –6¶W"Ð
days">'+Ð™™™'<table class=" table-condensed">™™™'+ÐE vÆö& Âæ†V EFV× Æ™™™'FR½sÇF&öG“ãÂð
tbody>'+Ð™™™"E vÆö& Âæfö÷EFV× Æ™™™'FR½</table>™™™'+ÐÂöF–Car½sÆF–b 6Æ 73Ò&F FW –6¶W"Ð
months">'+Ð™™™'<table class="table-condensed">™™™'+ÐE vÆö& Âæ†V EFV× Æ™™™'FR½
DPGlobal.contTemplate+Ð™™™"E vÆö& Âæfö÷EFV× Æ™™™'FR½</table>™™™'+ÐÂöF–Car½sÆF–b
class="datepicker-years">'+Ð™™™'<table class="table-condensed">™™™'+Ð
DPGlobal.headTemplate+Ð™™™"E vÆö& Âæ6öçEFV× Æ™™™"E vÆö& Âæfö÷EFV× Æ™™™'FR½</table>'+Ð
™™™'sÂöF–Car½™™™'</divÐBæÐâæF FW –6¶W"äE vÆö& Â Ò E vÆö& ÃÐòò¢ D DU ”4´U" äò
CONFLICTÐ¢ ÓÓÓÓÓÓÓÓÓÓÓÓÓÓÓÓÓÓÒ ¢ÐBæfâæF FW –6¶W"æâô6öæfÆ–7B Ò gVæ7F–öâ,–½
$.fn.datepicker = old;Ðreturn this;ÓÐòò¢ D DU ”4´U" D D Ô ‘¢
================== */ÐB†Fö7VÖVçB’æöâ™'focus.datepicker.data-api
click.datepicker.data-api',Ð'[data-provide="datepicker"]',Ðunction(e){Ðf "
$this = $(this);Ð––b ,GF†–2æF F ,vF FW –6¶W"r™'return;Ðç &WfVçDFVf VÇB,™½òò
component click requires us to explicitly show itÐ’GF†–2æF FW –6¶W",w6†÷rr™½Ð½
$(function(){Ð$('[data-provide="datepicker-inline"]').datepicker();Ð“Ð
(window.jQuery));Ð

public\assets\js\plugins\daterangepicker\daterangepicker.js

```
/**Ð @version: 1.3.21Ð @author: Dan Grossman http://www.dangrossman.info/Ð
@copyright: Copyright (c) 2012-2015 Dan Grossman. All rights reserved.Ð
@license: Licensed under the MIT license. See http://www.opensource.org/
licenses/mit-license.phpÐ @website: https://www.improvely.com/Ð/Ð
(function(root, factory) {Ð if (typeof define === 'function' && define.amd) {Ð
    define(['moment', 'jquery', 'exports'], function(momentjs, $, exports) {Ð
      root.daterangepicker = factory(root, exports, momentjs, $);Ð   });Ð }
else if (typeof exports !== 'undefined') {Ð   var momentjs =
require('moment');Ð   var jQuery;Ð   try {Ð     jQuery = require('jquery');Ð
    } catch (err) {Ð     jQuery = window.jQuery;Ð     if (!jQuery) throw new
Error('jQuery dependency not found');Ð   }Ð   factory(root, exports,
momentjs, jQuery);Ð // Finally, as a browser global.Ð } else {Ð
root.daterangepicker = factory(root, {}, root.moment, (root.jQuery ||
root.Zepto || root.ender || root.$));Ð }}Ð(this, function(root,
daterangepicker, moment, $) {Ð   var DateRangePicker = function (element,
options, cb) {Ð       // by default, the daterangepicker element is placed at
the bottom of HTML bodyÐ       this.parentEl = 'body';Ð       //element that
triggered the date range pickerÐ       this.element = $(element);Ð       //
tracks visible stateÐ       this.isShowing = false;Ð       //create the
picker HTML objectÐ       var DRPTemplate = '<div class="daterangepicker
dropdown-menu">' +Ð                '<div class="calendar first left"></div>' +Ð
                 '<div class="calendar second right"></div>' +Ð
'<div class="ranges">' +Ð                  '<div class="range_inputs">' +Ð
                     '<div class="daterangepicker_start_input">' +Ð
                       '<label for="daterangepicker_start"></label>' +Ð
                       '<input class="input-mini" type="text"
name="daterangepicker_start" value="" />' +Ð                    '</div>' +Ð
                     '<div class="daterangepicker_end_input">' +Ð
                       '<label for="daterangepicker_end"></label>' +Ð
                       '<input class="input-mini" type="text"
name="daterangepicker_end" value="" />' +Ð                    '</div>' +Ð
                     '<button class="applyBtn" disabled="disabled"></
button> ' +Ð                    '<button class="cancelBtn"></button>' +Ð
                   '</div>' +Ð                '</div>' +Ð              '</div>';Ð
        //custom optionsÐ       if (typeof options !== 'object' || options
=== null)Ð           options = {};Ð       this.parentEl = (typeof options ===
'object' && options.parentEl && $(options.parentEl).length) ?
$(options.parentEl) : $(this.parentEl);Ð       this.container =
$(DRPTemplate).appendTo(this.parentEl);Ð       this.setOptions(options, cb);Ð
        //event listenersÐ       this.container.find('.calendar')Ð
            .on('click.daterangepicker', '.prev', $.proxy(this.clickPrev,
this))Ð           .on('click.daterangepicker', '.next',
$.proxy(this.clickNext, this))Ð           .on('click.daterangepicker',
'td.available', $.proxy(this.clickDate, this))Ð
            .on('mouseenter.daterangepicker', 'td.available',
$.proxy(this.hoverDate, this))Ð           .on('mouseleave.daterangepicker',
'td.available', $.proxy(this.updateFormInputs, this))Ð
            .on('change.daterangepicker', 'select.yearselect',
$.proxy(this.updateMonthYear, this))Ð           .on('change.daterangepicker',
'select.monthselect', $.proxy(this.updateMonthYear, this))Ð
            .on('change.daterangepicker',
'select.hourselect,select.minuteselect,select.secondselect,select.ampmselect',
$.proxy(this.updateTime, this));Ð       this.container.find('.ranges')Ð
            .on('click.daterangepicker', 'button.applyBtn',
$.proxy(this.clickApply, this))Ð           .on('click.daterangepicker',
'button.cancelBtn', $.proxy(this.clickCancel, this))Ð
            .on('click.daterangepicker',
'.daterangepicker_start_input,.daterangepicker_end_input',
$.proxy(this.showCalendars, this))Ð
```

```
                                                .on('change.daterangepicker',
'.daterangepicker_start_input,.daterangepicker_end_input',
$.proxy(this.inputsChanged, this))Ð            .on('keydown.daterangepicker',
'.daterangepicker_start_input,.daterangepicker_end_input',
$.proxy(this.inputsKeydown, this))Ð            .on('click.daterangepicker',
'li', $.proxy(this.clickRange, this))Ð
            .on('mouseenter.daterangepicker', 'li', $.proxy(this.enterRange,
this))Ð           .on('mouseleave.daterangepicker', 'li',
$.proxy(this.updateFormInputs, this));Ð       if (this.element.is('input')) {Ð
            this.element.on({Ð               'click.daterangepicker':
$.proxy(this.show, this),Ð               'focus.daterangepicker':
$.proxy(this.show, this),Ð               'keyup.daterangepicker':
$.proxy(this.updateFromControl, this),Ð
'keydown.daterangepicker': $.proxy(this.keydown, this)Ð           });Ð
        } else {Ð           this.element.on('click.daterangepicker',
$.proxy(this.toggle, this));Ð       }Ð   };Ð   DateRangePicker.prototype = {Ð
        constructor: DateRangePicker,Ð       setOptions: function(options,
callback) {Ð           this.startDate = moment().startOf('day');Ð
this.endDate = moment().endOf('day');Ð           this.timeZone =
moment().utcOffset();Ð           this.minDate = false;Ð
this.maxDate = false;Ð           this.dateLimit = false;Ð
this.showDropdowns = false;Ð           this.showWeekNumbers = false;Ð
            this.timePicker = false;Ð           this.timePickerSeconds =
false;Ð           this.timePickerIncrement = 30;Ð
this.timePicker12Hour = true;Ð           this.singleDatePicker = false;Ð
            this.ranges = {};Ð           this.opens = 'right';Ð           if
(this.element.hasClass('pull-right'))Ð               this.opens = 'left';Ð
            this.drops = 'down';Ð           if
(this.element.hasClass('dropup'))Ð               this.drops = 'up';Ð
            this.buttonClasses = ['btn', 'btn-small btn-sm'];Ð
this.applyClass = 'btn-success';Ð           this.cancelClass = 'btn-default';Ð
            this.format = 'MM/DD/YYYY';Ð           this.separator = ' - ';Ð
            this.locale = {Ð               applyLabel: 'Apply',Ð
                cancelLabel: 'Cancel',Ð               fromLabel: 'From',Ð
                toLabel: 'To',Ð               weekLabel: 'W',Ð
customRangeLabel: 'Custom Range',Ð               daysOfWeek:
moment.weekdaysMin(),Ð               monthNames: moment.monthsShort(),Ð
                firstDay: moment.localeData()._week.dowÐ           };Ð
            this.cb = function () { };Ð           if (typeof options.format
=== 'string')Ð               this.format = options.format;Ð           if
(typeof options.separator === 'string')Ð               this.separator =
options.separator;Ð           if (typeof options.startDate === 'string')Ð
                this.startDate = moment(options.startDate, this.format);Ð
            if (typeof options.endDate === 'string')Ð
this.endDate = moment(options.endDate, this.format);Ð           if (typeof
options.minDate === 'string')Ð               this.minDate =
moment(options.minDate, this.format);Ð           if (typeof options.maxDate
=== 'string')Ð               this.maxDate = moment(options.maxDate,
this.format);Ð           if (typeof options.startDate === 'object')Ð
                this.startDate = moment(options.startDate);Ð           if
(typeof options.endDate === 'object')Ð               this.endDate =
moment(options.endDate);Ð           if (typeof options.minDate === 'object')Ð
                this.minDate = moment(options.minDate);Ð           if (typeof
options.maxDate === 'object')Ð               this.maxDate =
moment(options.maxDate);Ð           if (typeof options.applyClass ===
'string')Ð               this.applyClass = options.applyClass;Ð           if
(typeof options.cancelClass === 'string')Ð               this.cancelClass =
options.cancelClass;Ð           if (typeof options.dateLimit === 'object')Ð
                this.dateLimit = options.dateLimit;Ð           if (typeof
options.locale === 'object') {Ð
```

```
                              Ð               if (typeof
options.locale.daysOfWeek === 'object') {Ð                    // Create a copy
of daysOfWeek to avoid modification of originalÐ                    // options
object for reusability in multiple daterangepicker instancesÐ
                    this.locale.daysOfWeek =
options.locale.daysOfWeek.slice();Ð               }Ð               if (typeof
options.locale.monthNames === 'object') {Ð
this.locale.monthNames = options.locale.monthNames.slice();Ð               }Ð
                if (typeof options.locale.firstDay === 'number') {Ð
                  this.locale.firstDay = options.locale.firstDay;Ð
                }Ð               if (typeof options.locale.applyLabel ===
'string') {Ð                 this.locale.applyLabel =
options.locale.applyLabel;Ð               }Ð               if (typeof
options.locale.cancelLabel === 'string') {Ð
this.locale.cancelLabel = options.locale.cancelLabel;Ð               }Ð
                if (typeof options.locale.fromLabel === 'string') {Ð
                  this.locale.fromLabel = options.locale.fromLabel;Ð
                }Ð               if (typeof options.locale.toLabel ===
'string') {Ð                 this.locale.toLabel = options.locale.toLabel;Ð
                }Ð               if (typeof options.locale.weekLabel ===
'string') {Ð                 this.locale.weekLabel = options.locale.weekLabel;Ð
                }Ð               if (typeof options.locale.customRangeLabel
=== 'string') {Ð                 this.locale.customRangeLabel =
options.locale.customRangeLabel;Ð               }Ð           }Ð           if
(typeof options.opens === 'string')Ð               this.opens = options.opens;Ð
            if (typeof options.drops === 'string')Ð               this.drops
= options.drops;Ð           if (typeof options.showWeekNumbers === 'boolean')
{Ð               this.showWeekNumbers = options.showWeekNumbers;Ð           }Ð
            if (typeof options.buttonClasses === 'string') {Ð
this.buttonClasses = [options.buttonClasses];Ð           }Ð           if
(typeof options.buttonClasses === 'object') {Ð
this.buttonClasses = options.buttonClasses;Ð           }Ð           if
(typeof options.showDropdowns === 'boolean') {Ð
this.showDropdowns = options.showDropdowns;Ð           }Ð           if
(typeof options.singleDatePicker === 'boolean') {Ð
this.singleDatePicker = options.singleDatePicker;Ð               if
(this.singleDatePicker) {Ð                   this.endDate =
this.startDate.clone();Ð               }Ð           }Ð           if (typeof
options.timePicker === 'boolean') {Ð               this.timePicker =
options.timePicker;Ð           }Ð           if (typeof
options.timePickerSeconds === 'boolean') {Ð
this.timePickerSeconds = options.timePickerSeconds;Ð           }Ð
if (typeof options.timePickerIncrement === 'number') {Ð
this.timePickerIncrement = options.timePickerIncrement;Ð           }Ð
            if (typeof options.timePicker12Hour === 'boolean') {Ð
                this.timePicker12Hour = options.timePicker12Hour;Ð           }Ð
            // update day names order to firstDayÐ           if
(this.locale.firstDay != 0) {Ð               var iterator =
this.locale.firstDay;Ð               while (iterator > 0) {Ð

this.locale.daysOfWeek.push(this.locale.daysOfWeek.shift());Ð
                    iterator--;Ð               }Ð           }Ð           var
start, end, range;Ð           //if no start/end dates set, check if an input
element contains initial valuesÐ           if (typeof options.startDate ===
'undefined' && typeof options.endDate === 'undefined') {Ð               if
($(this.element).is('input[type=text]')) {Ð                   var val =
$(this.element).val(),Ð                       split =
val.split(this.separator);Ð                   start = end = null;Ð
                    if (split.length == 2) {Ð                       start =
moment(split[0], this.format);Ð
```

```
                                                        end = moment(split[1],
this.format);Ð                    } else if (this.singleDatePicker && val !==
"") {Ð                        start = moment(val, this.format);Ð
                        end = moment(val, this.format);Ð                    }Ð
                    if (start !== null && end !== null) {Ð
                        this.startDate = start;Ð
this.endDate = end;Ð                    }Ð              }Ð           }Ð
            // bind the time zone used to build the calendar to either the
timeZone passed in through the options or the zone of the startDate (which
will be the local time zone by default)Ð           if (typeof
options.timeZone === 'string' || typeof options.timeZone === 'number') {Ð
            ––b ‡G— Vöb ÷ F–öç2çF–ÖU¦öæR ÓÓÒ w7G&–ærr bb G— Vöb ÖöÖVçBçG¢  ÓÒ
'undefined') {Ð           ™this.timeZone =
moment.tz.zone(options.timeZone).parse(new Date) * -1;’òò öfg6WB —2  ÷6—F—fR
if the timezone is behind UTC and negative if it is ahead.Ð           —Ò VÇ6R ½
            ™this.timeZone = options.timeZone;Ð          —Ý
this.startDate.utcOffset(this.timeZone);Ð
this.endDate.utcOffset(this.timeZone);Ð           } else {Ð
this.timeZone = moment(this.startDate).utcOffset();Ð           }Ð
if (typeof options.ranges === 'object') {Ð               for (range in
options.ranges) {Ð                    if (typeof options.ranges[range][0] ===
'string')Ð                        start = moment(options.ranges[range][0],
this.format);Ð                    elseÐ                        start =
moment(options.ranges[range][0]);Ð                    if (typeof
options.ranges[range][1] === 'string')Ð                        end =
moment(options.ranges[range][1], this.format);Ð                    elseÐ
                        end = moment(options.ranges[range][1]);Ð
                    // If we have a min/max date set, bound this rangeÐ
                    // to it, but only if it would otherwise fallÐ
                    // outside of the min/max.Ð                    if
(this.minDate && start.isBefore(this.minDate))Ð                        start =
moment(this.minDate);Ð                    if (this.maxDate &&
end.isAfter(this.maxDate))Ð                        end = moment(this.maxDate);Ð
                    // If the end of the range is before the minimum (if min
is set) ORÐ                    // the start of the range is after the max
(also if set) don't display thisÐ                    // range option.Ð
                    if ((this.minDate && end.isBefore(this.minDate)) ||
(this.maxDate && start.isAfter(this.maxDate))) {Ð
continue;Ð                    }Ð                    this.ranges[range] =
[start, end];Ð                }Ð                var list = '<ul>';Ð
                for (range in this.ranges) {Ð                    list +=
'<li>' + range + '</li>';Ð                }Ð                list += '<li>' +
this.locale.customRangeLabel + '</li>';Ð                list += '</ul>';Ð
                this.container.find('.ranges ul').remove();Ð
this.container.find('.ranges').prepend(list);Ð           }Ð           if
(typeof callback === 'function') {Ð                this.cb = callback;Ð
            }Ð           if (!this.timePicker) {Ð
this.startDate = this.startDate.startOf('day');Ð                this.endDate =
this.endDate.endOf('day');Ð           }Ð           if (this.singleDatePicker)
{Ð                this.opens = 'right';Ð
this.container.addClass('single');Ð
this.container.find('.calendar.right').show();Ð
this.container.find('.calendar.left').hide();Ð                if (!
this.timePicker) {Ð                    this.container.find('.ranges').hide();Ð
                } else {Ð                    this.container.find('.ranges .date
rangepicker_start_input, .ranges .daterangepicker_end_input').hide();Ð
                }Ð                if (!
this.container.find('.calendar.right').hasClass('single'))Ð
this.container.find('.calendar.right').addClass('single');Ð           } else {Ð
                this.container.removeClass('single');Ð
```

```
this.container.find('.calendar.right').removeClass('single');Ð
this.container.find('.ranges').show();Ð           }Ð
this.oldStartDate = this.startDate.clone();Ð           this.oldEndDate =
this.endDate.clone();Ð           this.oldChosenLabel = this.chosenLabel;Ð
            this.leftCalendar = {Ð               month:
moment([this.startDate.year(), this.startDate.month(), 1,
this.startDate.hour(), this.startDate.minute(), this.startDate.second()]),Ð
                calendar: []Ð           };Ð           this.rightCalendar = {Ð
                month: moment([this.endDate.year(), this.endDate.month(), 1,
this.endDate.hour(), this.endDate.minute(), this.endDate.second()]),Ð
                calendar: []Ð           };Ð           if (this.opens ==
'right' || this.opens == 'center') {Ð               //swap calendar positionsÐ
                var first = this.container.find('.calendar.first');Ð
                var second = this.container.find('.calendar.second');Ð
                if (second.hasClass('single')) {Ð
second.removeClass('single');Ð                    first.addClass('single');Ð
                }Ð               first.removeClass('left').addClass('right');Ð
                second.removeClass('right').addClass('left');Ð
if (this.singleDatePicker) {Ð                   first.show();Ð
                    second.hide();Ð               }Ð           }Ð
if (typeof options.ranges === 'undefined' && !this.singleDatePicker) {Ð
                this.container.addClass('show-calendar');Ð           }Ð
            this.container.removeClass('opensleft
opensright').addClass('opens' + this.opens);Ð           this.updateView();Ð
            this.updateCalendars();Ð           //apply CSS classes and labels
to buttonsÐ           var c = this.container;Ð
$.each(this.buttonClasses, function (idx, val) {Ð
c.find('button').addClass(val);Ð           });Ð
this.container.find('.daterangepicker_start_input
label').html(this.locale.fromLabel);Ð
this.container.find('.daterangepicker_end_input
label').html(this.locale.toLabel);Ð           if (this.applyClass.length)Ð
                this.container.find('.applyBtn').addClass(this.applyClass);Ð
            if (this.cancelClass.length)Ð
this.container.find('.cancelBtn').addClass(this.cancelClass);Ð
this.container.find('.applyBtn').html(this.locale.applyLabel);Ð
this.container.find('.cancelBtn').html(this.locale.cancelLabel);Ð       },Ð
        setStartDate: function(startDate) {Ð           if (typeof startDate
=== 'string')Ð               this.startDate = moment(startDate,
this.format).utcOffset(this.timeZone);Ð           if (typeof startDate ===
'object')Ð               this.startDate = moment(startDate);Ð           if (!
this.timePicker)Ð               this.startDate =
this.startDate.startOf('day');Ð           this.oldStartDate =
this.startDate.clone();Ð           this.updateView();Ð
this.updateCalendars();Ð           this.updateInputText();Ð       },Ð
setEndDate: function(endDate) {Ð           if (typeof endDate === 'string')Ð
                this.endDate = moment(endDate,
this.format).utcOffset(this.timeZone);Ð           if (typeof endDate ===
'object')Ð               this.endDate = moment(endDate);Ð           if (!
this.timePicker)Ð               this.endDate = this.endDate.endOf('day');Ð
            this.oldEndDate = this.endDate.clone();Ð
this.updateView();Ð           this.updateCalendars();Ð
this.updateInputText();Ð       },Ð       updateView: function () {Ð
this.leftCalendar.month.month(this.startDate.month()).year(this.startDate.year
()).hour(this.startDate.hour()).minute(this.startDate.minute());Ð           th
is.rightCalendar.month.month(this.endDate.month()).year(this.endDate.year()).h
our(this.endDate.hour()).minute(this.endDate.minute());Ð
this.updateFormInputs();Ð       },Ð       updateFormInputs: function () {Ð

this.container.find('input[name=daterangepicker_start]').val(this.startDate.format(this.fo
```

```
this.container.find('input[name=daterangepicker_end]').val(this.endDate.format(this.format
Ð           if (this.startDate.isSame(this.endDate) ||
this.startDate.isBefore(this.endDate)) {Ð
this.container.find('button.applyBtn').removeAttr('disabled');Ð           }
else {Ð               this.container.find('button.applyBtn').attr('disabled',
'disabled');Ð           }Ð       },Ð       updateFromControl: function () {Ð
            if (!this.element.is('input')) return;Ð           if (!
this.element.val().length) return;Ð           var dateString =
this.element.val().split(this.separator),Ð               start = null,Ð
                end = null;Ð           if(dateString.length === 2) {Ð
                start = moment(dateString[0],
this.format).utcOffset(this.timeZone);Ð               end =
moment(dateString[1], this.format).utcOffset(this.timeZone);Ð           }Ð
            if (this.singleDatePicker || start === null || end === null) {Ð
                start = moment(this.element.val(),
this.format).utcOffset(this.timeZone);Ð               end = start;Ð
            }Ð           if (end.isBefore(start)) return;Ð
this.oldStartDate = this.startDate.clone();Ð           this.oldEndDate =
this.endDate.clone();Ð           this.startDate = start;Ð
this.endDate = end;Ð           if (!this.startDate.isSame(this.oldStartDate)
|| !this.endDate.isSame(this.oldEndDate))Ð               this.notify();Ð
            this.updateCalendars();Ð       },Ð       Ð       keydown:
function (e) {Ð           //hide on tab or enterÐ       --b ,†Ræ¶W”6öFR ÓÓÒ ’’
|| (e.keyCode === 13)) {Ð       ™this.hide();Ð      —Ý       },Ð
notify: function () {Ð           this.updateView();Ð
this.cb(this.startDate, this.endDate, this.chosenLabel);Ð       },Ð
move: function () {Ð           var parentOffset = { top: 0, left: 0 },Ð
            –6öçF –æW%F÷ ½           var parentRightEdge = $(window).width();Ð
            if (!this.parentEl.is('body')) {Ð               parentOffset = {Ð
                    top: this.parentEl.offset().top -
this.parentEl.scrollTop(),Ð                    left:
this.parentEl.offset().left - this.parentEl.scrollLeft()Ð               };Ð
                parentRightEdge = this.parentEl[0].clientWidth +
this.parentEl.offset().left;Ð           }Ð           Ð           if
(this.drops == 'up')Ð           –6öçF –æW%F÷  Ò F†—2æVÆVÖVçBæöfg6WB,’çF÷  Ò
this.container.outerHeight() - parentOffset.top;Ð           elseÐ           •
containerTop = this.element.offset().top + this.element.outerHeight() -
parentOffset.top;Ð           this.container[this.drops == 'up' ? 'addClass' :
'removeClass']('dropup');Ð           if (this.opens == 'left') {Ð
                this.container.css({Ð                    top: containerTop,Ð
                    right: parentRightEdge - this.element.offset().left -
this.element.outerWidth(),Ð                    left: 'auto'Ð               });Ð
                if (this.container.offset().left < 0) {Ð
this.container.css({Ð                        right: 'auto',Ð
                        left: 9Ð                    });Ð               }Ð
            } else if (this.opens == 'center') {Ð
this.container.css({Ð                    top: containerTop,Ð
left: this.element.offset().left - parentOffset.left +
this.element.outerWidth() / 2Ð                        -
this.container.outerWidth() / 2,Ð                    right: 'auto'Ð
                });Ð               if (this.container.offset().left < 0) {Ð
                    this.container.css({Ð                        right: 'auto',Ð
                        left: 9Ð                    });Ð               }Ð
            } else {Ð               this.container.css({Ð
top: containerTop,Ð                    left: this.element.offset().left -
parentOffset.left,Ð                    right: 'auto'Ð               });Ð
                if (this.container.offset().left +
this.container.outerWidth() > $(window).width()) {Ð
```

```
this.container.css({Ð                        left: 'auto',Ð
                        right: 0Ð                    });Ð              }Ð
            }Ð       },Ð       toggle: function (e) {Ð           if
(this.element.hasClass('active')) {Ð               this.hide();Ð           }
else {Ð               this.show();Ð           }Ð       },Ð       show:
function (e) {Ð           if (this.isShowing) return;Ð
this.element.addClass('active');Ð           this.container.show();Ð
this.move();Ð           // Create a click proxy that is private to this
instance of datepicker, for unbindingÐ           this._outsideClickProxy =
$.proxy(function (e) { this.outsideClick(e); }, this);Ð           // Bind
global datepicker mousedown for hiding andÐ           $(document)Ð
              .on('mousedown.daterangepicker', this._outsideClickProxy)Ð
              // also support mobile devicesÐ
              .on('touchend.daterangepicker', this._outsideClickProxy)Ð
              // also explicitly play nice with Bootstrap dropdowns, which
stopPropagation when clicking themÐ             .on('click.daterangepicker',
'[data-toggle=dropdown]', this._outsideClickProxy)Ð             // and also
close when focus changes to outside the picker (eg. tabbing between controls)Ð
              .on('focusin.daterangepicker', this._outsideClickProxy);Ð
            this.isShowing = true;Ð
this.element.trigger('show.daterangepicker', this);Ð       },Ð
outsideClick: function (e) {Ð           var target = $(e.target);Ð
            // if the page is clicked anywhere except within the
daterangerpicker/buttonÐ           // itself then call this.hide()Ð
if (Ð               // ie modal dialog fixÐ               e.type == "focusin"
||Ð               target.closest(this.element).length ||Ð
target.closest(this.container).length ||Ð
target.closest('.calendar-date').lengthÐ               ) return;Ð
this.hide();Ð       },Ð       hide: function (e) {Ð           if (!
this.isShowing) return;Ð           $(document)Ð
              .off('.daterangepicker');Ð
this.element.removeClass('active');Ð           this.container.hide();Ð
            if (!this.startDate.isSame(this.oldStartDate) || !
this.endDate.isSame(this.oldEndDate))Ð               this.notify();Ð
            this.oldStartDate = this.startDate.clone();Ð
this.oldEndDate = this.endDate.clone();Ð           this.isShowing = false;Ð
            this.element.trigger('hide.daterangepicker', this);Ð       },Ð
        enterRange: function (e) {Ð           // mouse pointer has entered a
range labelÐ           var label = e.target.innerHTML;Ð           if (label
== this.locale.customRangeLabel) {Ð               this.updateView();Ð
            } else {Ð               var dates = this.ranges[label];Ð

this.container.find('input[name=daterangepicker_start]').val(dates[0].format(this.format))

this.container.find('input[name=daterangepicker_end]').val(dates[1].format(this.format));Ð
            }Ð       },Ð       showCalendars: function() {Ð
this.container.addClass('show-calendar');Ð           this.move();Ð
this.element.trigger('showCalendar.daterangepicker', this);Ð       },Ð
hideCalendars: function() {Ð           this.container.removeClass('show-
calendar');Ð           this.element.trigger('hideCalendar.daterangepicker',
this);Ð       },Ð       // when a date is typed into the start to end date
textboxesÐ       inputsChanged: function (e) {Ð           var el =
$(e.target);Ð           var date = moment(el.val(), this.format);Ð
if (!date.isValid()) return;Ð           var startDate, endDate;Ð           if
(el.attr('name') === 'daterangepicker_start') {Ð               startDate =
(false !== this.minDate && date.isBefore(this.minDate)) ? this.minDate : date;Ð
                endDate = this.endDate;Ð           } else {Ð
startDate = this.startDate;Ð               endDate = (false !== this.maxDate
&& date.isAfter(this.maxDate)) ? this.maxDate : date;Ð
```

```
                                                                    }Ð
this.setCustomDates(startDate, endDate);Ð       },Ð       inputsKeydown:
function(e) {Ð           if (e.keyCode === 13) {Ð
this.inputsChanged(e);Ð               this.notify();Ð           }Ð       },Ð
        updateInputText: function() {Ð           if (this.element.is('input')
&& !this.singleDatePicker) {Ð
this.element.val(this.startDate.format(this.format) + this.separator +
this.endDate.format(this.format));Ð
this.element.trigger('change');Ð           } else if
(this.element.is('input')) {Ð
this.element.val(this.endDate.format(this.format));Ð
this.element.trigger('change');Ð           }Ð       },Ð       clickRange:
function (e) {Ð           var label = e.target.innerHTML;Ð
this.chosenLabel = label;Ð           if (label ==
this.locale.customRangeLabel) {Ð               this.showCalendars();Ð
            } else {Ð               var dates = this.ranges[label];Ð
                this.startDate = dates[0];Ð               this.endDate =
dates[1];Ð               if (!this.timePicker) {Ð
this.startDate.startOf('day');Ð                   this.endDate.endOf('day');Ð
                }Ð               this.leftCalendar.month.month(this.startDate.
month()).year(this.startDate.year()).hour(this.startDate.hour()).minute(this.s
tartDate.minute());Ð               this.rightCalendar.month.month(this.endDate
.month()).year(this.endDate.year()).hour(this.endDate.hour()).minute(this.endD
ate.minute());Ð               this.updateCalendars();Ð
this.updateInputText();Ð               this.hideCalendars();Ð
this.hide();Ð               this.element.trigger('apply.daterangepicker',
this);Ð           }Ð       },Ð       clickPrev: function (e) {Ð           var
cal = $(e.target).parents('.calendar');Ð           if (cal.hasClass('left')) {Ð
                this.leftCalendar.month.subtract(1, 'month');Ð           }
else {Ð               this.rightCalendar.month.subtract(1, 'month');Ð
            }Ð           this.updateCalendars();Ð       },Ð       clickNext:
function (e) {Ð           var cal = $(e.target).parents('.calendar');Ð
            if (cal.hasClass('left')) {Ð
this.leftCalendar.month.add(1, 'month');Ð           } else {Ð
this.rightCalendar.month.add(1, 'month');Ð           }Ð
this.updateCalendars();Ð       },Ð       hoverDate: function (e) {Ð
var title = $(e.target).attr('data-title');Ð           var row =
title.substr(1, 1);Ð           var col = title.substr(3, 1);Ð           var
cal = $(e.target).parents('.calendar');Ð           if (cal.hasClass('left')) {Ð

this.container.find('input[name=daterangepicker_start]').val(this.leftCalendar.calendar[ro
[col].format(this.format));Ð           } else {Ð               this.container.
find('input[name=daterangepicker_end]').val(this.rightCalendar.calendar[row]
[col].format(this.format));Ð           }Ð       },Ð       setCustomDates:
function(startDate, endDate) {Ð           this.chosenLabel =
this.locale.customRangeLabel;Ð           if (startDate.isAfter(endDate)) {Ð
                var difference = this.endDate.diff(this.startDate);Ð
                endDate = moment(startDate).add(difference, 'ms');Ð
                if (this.maxDate && endDate.isAfter(this.maxDate)) {Ð
                  endDate = this.maxDate.clone();Ð               }Ð
            }Ð           this.startDate = startDate;Ð           this.endDate
= endDate;Ð           this.updateView();Ð           this.updateCalendars();Ð
        },Ð       clickDate: function (e) {Ð           var title =
$(e.target).attr('data-title');Ð           var row = title.substr(1, 1);Ð
            var col = title.substr(3, 1);Ð           var cal =
$(e.target).parents('.calendar');Ð           var startDate, endDate;Ð
            if (cal.hasClass('left')) {Ð               startDate =
this.leftCalendar.calendar[row][col];Ð               endDate = this.endDate;Ð
                if (typeof this.dateLimit === 'object') {Ð
var maxDate = moment(startDate).add(this.dateLimit).startOf('day');Ð
```

```
                    if (endDate.isAfter(maxDate)) {Ð
endDate = maxDate;Ð                    }Ð                }Ð            } else {Ð
                startDate = this.startDate;Ð                endDate =
this.rightCalendar.calendar[row][col];Ð                if (typeof
this.dateLimit === 'object') {Ð                var minDate =
moment(endDate).subtract(this.dateLimit).startOf('day');Ð
if (startDate.isBefore(minDate)) {Ð                        startDate = minDate;Ð
                    }Ð                }Ð            }Ð            if
(this.singleDatePicker && cal.hasClass('left')) {Ð                endDate =
startDate.clone();Ð            } else if (this.singleDatePicker &&
cal.hasClass('right')) {Ð                startDate = endDate.clone();Ð
            }Ð            cal.find('td').removeClass('active');Ð
$(e.target).addClass('active');Ð            this.setCustomDates(startDate,
endDate);Ð            if (!this.timePicker)Ð
endDate.endOf('day');Ð            if (this.singleDatePicker && !
this.timePicker)Ð                this.clickApply();Ð        },Ð
clickApply: function (e) {Ð            this.updateInputText();Ð
this.hide();Ð            this.element.trigger('apply.daterangepicker', this);Ð
        },Ð        clickCancel: function (e) {Ð            this.startDate =
this.oldStartDate;Ð            this.endDate = this.oldEndDate;Ð
this.chosenLabel = this.oldChosenLabel;Ð            this.updateView();Ð
            this.updateCalendars();Ð            this.hide();Ð
this.element.trigger('cancel.daterangepicker', this);Ð        },Ð
updateMonthYear: function (e) {Ð            var isLeft =
$(e.target).closest('.calendar').hasClass('left'),Ð                leftOrRight
= isLeft ? 'left' : 'right',Ð                cal =
this.container.find('.calendar.'+leftOrRight);Ð            // Month must be
Number for new moment versionsÐ            var month =
parseInt(cal.find('.monthselect').val(), 10);Ð            var year =
cal.find('.yearselect').val();Ð            if (!isLeft && !
this.singleDatePicker) {Ð                if (year < this.startDate.year() ||
(year == this.startDate.year() && month < this.startDate.month())) {Ð
                    month = this.startDate.month();Ð                year =
this.startDate.year();Ð                }Ð            }Ð            if
(this.minDate) {Ð                if (year < this.minDate.year() || (year ==
this.minDate.year() && month < this.minDate.month())) {Ð
month = this.minDate.month();Ð                year = this.minDate.year();Ð
                }Ð            }Ð            if (this.maxDate) {Ð
if (year > this.maxDate.year() || (year == this.maxDate.year() && month >
this.maxDate.month())) {Ð                month = this.maxDate.month();Ð
                    year = this.maxDate.year();Ð                }Ð            }Ð
            this[leftOrRight+'Calendar'].month.month(month).year(year);Ð
            this.updateCalendars();Ð        },Ð        updateTime: function(e) {Ð
            var cal = $(e.target).closest('.calendar'),Ð                isLeft
= cal.hasClass('left');Ð            var hour =
parseInt(cal.find('.hourselect').val(), 10);Ð            var minute =
parseInt(cal.find('.minuteselect').val(), 10);Ð            var second = 0;Ð
            if (this.timePickerSeconds) {Ð                second =
parseInt(cal.find('.secondselect').val(), 10);Ð            }Ð            if
(this.timePicker12Hour) {Ð                var ampm =
cal.find('.ampmselect').val();Ð                if (ampm === 'PM' && hour < 12)Ð
                    hour += 12;Ð                if (ampm === 'AM' && hour ===
12)Ð                    hour = 0;Ð            }Ð            if (isLeft) {Ð
                var start = this.startDate.clone();Ð
start.hour(hour);Ð                start.minute(minute);Ð
start.second(second);Ð                this.startDate = start;Ð
this.leftCalendar.month.hour(hour).minute(minute).second(second);Ð
                if (this.singleDatePicker)Ð                    this.endDate =
start.clone();Ð
```

```
                        } else {Ð                var end =
this.endDate.clone();Ð                end.hour(hour);Ð
end.minute(minute);Ð                end.second(second);Ð
this.endDate = end;Ð                if (this.singleDatePicker)Ð
                    this.startDate = end.clone();Ð
this.rightCalendar.month.hour(hour).minute(minute).second(second);Ð
            }Ð           this.updateView();Ð           this.updateCalendars();Ð
        },Ð       updateCalendars: function () {Ð
this.leftCalendar.calendar =
this.buildCalendar(this.leftCalendar.month.month(),
this.leftCalendar.month.year(), this.leftCalendar.month.hour(),
this.leftCalendar.month.minute(), this.leftCalendar.month.second(), 'left');Ð
            this.rightCalendar.calendar =
this.buildCalendar(this.rightCalendar.month.month(),
this.rightCalendar.month.year(), this.rightCalendar.month.hour(),
this.rightCalendar.month.minute(), this.rightCalendar.month.second(),
'right');Ð           this.container.find('.calendar.left').empty().html(this.r
enderCalendar(this.leftCalendar.calendar, this.startDate, this.minDate,
this.maxDate, 'left'));Ð           this.container.find('.calendar.right').empt
y().html(this.renderCalendar(this.rightCalendar.calendar, this.endDate,
this.singleDatePicker ? this.minDate : this.startDate, this.maxDate,
'right'));Ð           this.container.find('.ranges li').removeClass('active');Ð
            var customRange = true;Ð           var i = 0;Ð           for (var
range in this.ranges) {Ð                if (this.timePicker) {Ð
                    if (this.startDate.isSame(this.ranges[range][0]) &&
this.endDate.isSame(this.ranges[range][1])) {Ð
customRange = false;Ð                        this.chosenLabel =
this.container.find('.ranges li:eq(' + i + ')')Ð
                            .addClass('active').html();Ð                    }Ð
                } else {Ð                    //ignore times when comparing
dates if time picker is not enabledÐ                    if
(this.startDate.format('YYYY-MM-DD') == this.ranges[range][0].format('YYYY-MM-
DD') && this.endDate.format('YYYY-MM-DD') == this.ranges[range]
[1].format('YYYY-MM-DD')) {Ð                        customRange = false;Ð
                        this.chosenLabel = this.container.find('.ranges
li:eq(' + i + ')')Ð                            .addClass('active').html();Ð
                    }Ð               }Ð               i++;Ð           }Ð
            if (customRange) {Ð               this.chosenLabel =
this.container.find('.ranges li:last').addClass('active').html();Ð
                this.showCalendars();Ð           }Ð       },Ð
buildCalendar: function (month, year, hour, minute, second, side) {Ð
            var daysInMonth = moment([year, month]).daysInMonth();Ð
var firstDay = moment([year, month, 1]);Ð           var lastDay =
moment([year, month, daysInMonth]);Ð           var lastMonth =
moment(firstDay).subtract(1, 'month').month();Ð           var lastYear =
moment(firstDay).subtract(1, 'month').year();Ð           var daysInLastMonth
= moment([lastYear, lastMonth]).daysInMonth();Ð           var dayOfWeek =
firstDay.day();Ð           var i;Ð           //initialize a 6 rows x 7
columns array for the calendarÐ           var calendar = [];Ð
calendar.firstDay = firstDay;Ð           calendar.lastDay = lastDay;Ð
            for (i = 0; i < 6; i++) {Ð               calendar[i] = [];Ð
            }Ð           //populate the calendar with date objectsÐ
var startDay = daysInLastMonth - dayOfWeek + this.locale.firstDay + 1;Ð
            if (startDay > daysInLastMonth)Ð               startDay -= 7;Ð
            if (dayOfWeek == this.locale.firstDay)Ð               startDay =
daysInLastMonth - 6;Ð           var curDate = moment([lastYear, lastMonth,
startDay, 12, minute, second]).utcOffset(this.timeZone);Ð           var col,
row;Ð           for (i = 0, col = 0, row = 0; i < 42; i++, col++, curDate =
moment(curDate).add(24, 'hour')) {Ð               if (i > 0 && col % 7 === 0)
{Ð
```

```
                    col = 0;Ð                    row++;Ð                }Ð
                calendar[row][col] = curDate.clone().hour(hour);Ð
                curDate.hour(12);Ð                if (this.minDate &&
calendar[row][col].format('YYYY-MM-DD') == this.minDate.format('YYYY-MM-DD')
&& calendar[row][col].isBefore(this.minDate) && side == 'left') {Ð
                    calendar[row][col] = this.minDate.clone();Ð
                }Ð                if (this.maxDate && calendar[row]
[col].format('YYYY-MM-DD') == this.maxDate.format('YYYY-MM-DD') &&
calendar[row][col].isAfter(this.maxDate) && side == 'right') {Ð
                    calendar[row][col] = this.maxDate.clone();Ð
                }Ð            }Ð            return calendar;Ð        },Ð
renderDropdowns: function (selected, minDate, maxDate) {Ð            var
currentMonth = selected.month();Ð            var currentYear = selected.year();Ð
            var maxYear = (maxDate && maxDate.year()) || (currentYear + 5);Ð
            var minYear = (minDate && minDate.year()) || (currentYear - 50);Ð
            var monthHtml = '<select class="monthselect">';Ð            var
inMinYear = currentYear == minYear;Ð            var inMaxYear = currentYear ==
maxYear;Ð            for (var m = 0; m < 12; m++) {Ð                if ((!
inMinYear || m >= minDate.month()) && (!inMaxYear || m <= maxDate.month())) {Ð
                    monthHtml += "<option value='" + m + "'" +Ð
                        (m === currentMonth ? " selected='selected'" : "") +Ð
                        ">" + this.locale.monthNames[m] + "</option>";Ð
                }Ð            }Ð            monthHtml += "</select>";Ð
            var yearHtml = '<select class="yearselect">';Ð            for (var
y = minYear; y <= maxYear; y++) {Ð                yearHtml += '<option
value="' + y + '"' +Ð                    (y === currentYear ? '
selected="selected"' : '') +Ð                    '>' + y + '</option>';Ð
            }Ð            yearHtml += '</select>';Ð            return monthHtml
+ yearHtml;Ð        },Ð        renderCalendar: function (calendar, selected,
minDate, maxDate, side) {Ð            var html = '<div class="calendar-date">';Ð
            html += '<table class="table-condensed">';Ð            html +=
'<thead>';Ð            html += '<tr>';Ð            // add empty cell for week
numberÐ            if (this.showWeekNumbers)Ð                html += '<th></
th>';Ð            if (!minDate || minDate.isBefore(calendar.firstDay)) {Ð
                html += '<th class="prev available"><i class="fa fa-arrow-
left icon icon-arrow-left glyphicon glyphicon-arrow-left"></i></th>';Ð
            } else {Ð                html += '<th></th>';Ð            }Ð
            var dateHtml = this.locale.monthNames[calendar[1][1].month()] +
calendar[1][1].format(" YYYY");Ð            if (this.showDropdowns) {Ð
                dateHtml = this.renderDropdowns(calendar[1][1], minDate,
maxDate);Ð            }Ð            html += '<th colspan="5" class="month">' +
dateHtml + '</th>';Ð            if (!maxDate ||
maxDate.isAfter(calendar.lastDay)) {Ð                html += '<th class="next
available"><i class="fa fa-arrow-right icon icon-arrow-right glyphicon
glyphicon-arrow-right"></i></th>';Ð            } else {Ð                html +=
'<th></th>';Ð            }Ð            html += '</tr>';Ð            html +=
'<tr>';Ð            // add week number labelÐ            if
(this.showWeekNumbers)Ð                html += '<th class="week">' +
this.locale.weekLabel + '</th>';Ð            $.each(this.locale.daysOfWeek,
function (index, dayOfWeek) {Ð                html += '<th>' + dayOfWeek + '</
th>';Ð            });Ð            html += '</tr>';Ð            html += '</
thead>';Ð            html += '<tbody>';Ð            for (var row = 0; row < 6;
row++) {Ð                html += '<tr>';Ð                // add week numberÐ
                if (this.showWeekNumbers)Ð                html += '<td
class="week">' + calendar[row][0].week() + '</td>';Ð                for (var
col = 0; col < 7; col++) {Ð                var cname = 'available ';Ð
                    cname += (calendar[row][col].month() == calendar[1]
[1].month()) ? '' : 'off';Ð                if ((minDate && calendar[row]
[col].isBefore(minDate, 'day')) || (maxDate && calendar[row]
[col].isAfter(maxDate, 'day'))) {Ð
```

```
                                                        cname = ' off
disabled ';Ð                    } else if (calendar[row][col].format('YYYY-MM-
DD') == selected.format('YYYY-MM-DD')) {Ð                        cname += '
active ';Ð                      if (calendar[row][col].format('YYYY-MM-DD')
== this.startDate.format('YYYY-MM-DD')) {Ð                          cname +=
' start-date ';Ð                        }Ð                        if
(calendar[row][col].format('YYYY-MM-DD') == this.endDate.format('YYYY-MM-
DD')) {Ð                          cname += ' end-date ';Ð
                        }Ð                  } else if (calendar[row][col] >=
this.startDate && calendar[row][col] <= this.endDate) {Ð
                        cname += ' in-range ';Ð                      if
(calendar[row][col].isSame(this.startDate)) { cname += ' start-date '; }Ð
                        if (calendar[row][col].isSame(this.endDate)) { cname
+= ' end-date '; }Ð                    }Ð                    var title = 'r' +
row + 'c' + col;Ð                    html += '<td class="' + cname.replace(/
\s+/g, ' ').replace(/^\s?(.*?)\s?$/, '$1') + '" data-title="' + title + '">'
+ calendar[row][col].date() + '</td>';Ð                }Ð                html
+= '</tr>';Ð            }Ð            html += '</tbody>';Ð            html += '</
table>';Ð            html += '</div>';Ð            var i;Ð            if
(this.timePicker) {Ð                html += '<div class="calendar-time">';Ð
                html += '<select class="hourselect">';Ð                //
Disallow selections before the minDate or after the maxDateÐ
var min_hour = 0;Ð                var max_hour = 23;Ð                if
(minDate && (side == 'left' || this.singleDatePicker) &&
selected.format('YYYY-MM-DD') == minDate.format('YYYY-MM-DD')) {Ð
                    min_hour = minDate.hour();Ð                    if
(selected.hour() < min_hour)Ð                        selected.hour(min_hour);Ð
                    if (this.timePicker12Hour && min_hour >= 12 &&
selected.hour() >= 12)Ð                        min_hour -= 12;Ð
                    if (this.timePicker12Hour && min_hour == 12)Ð
                        min_hour = 1;Ð                }Ð                if
(maxDate && (side == 'right' || this.singleDatePicker) &&
selected.format('YYYY-MM-DD') == maxDate.format('YYYY-MM-DD')) {Ð
                    max_hour = maxDate.hour();Ð                    if
(selected.hour() > max_hour)Ð                        selected.hour(max_hour);Ð
                    if (this.timePicker12Hour && max_hour >= 12 &&
selected.hour() >= 12)Ð                        max_hour -= 12;Ð                }Ð
                var start = 0;Ð                var end = 23;Ð
var selected_hour = selected.hour();Ð                if
(this.timePicker12Hour) {Ð                    start = 1;Ð
end = 12;Ð                    if (selected_hour >= 12)Ð
selected_hour -= 12;Ð                    if (selected_hour === 0)Ð
                        selected_hour = 12;Ð                }Ð
for (i = start; i <= end; i++) {Ð                    if (i == selected_hour) {Ð
                        html += '<option value="' + i + '"
selected="selected">' + i + '</option>';Ð                    } else if (i <
min_hour || i > max_hour) {Ð                        html += '<option value="'
+ i + '" disabled="disabled" class="disabled">' + i + '</option>';Ð
                    } else {Ð                        html += '<option value="'
+ i + '">' + i + '</option>';Ð                    }Ð                }Ð
                html += '</select> : ';Ð                html += '<select
class="minuteselect">';Ð                // Disallow selections before the
minDate or after the maxDateÐ                var min_minute = 0;Ð
                var max_minute = 59;Ð                if (minDate && (side ==
'left' || this.singleDatePicker) && selected.format('YYYY-MM-DD h A') ==
minDate.format('YYYY-MM-DD h A')) {Ð                    min_minute =
minDate.minute();Ð                    if (selected.minute() < min_minute)Ð
                        selected.minute(min_minute);Ð                }Ð
                if (maxDate && (side == 'right' || this.singleDatePicker) &&
selected.format('YYYY-MM-DD h A') == maxDate.format('YYYY-MM-DD h A')) {Ð
```

```
                    max_minute = maxDate.minute();Ð                    if
(selected.minute() > max_minute)Ð
selected.minute(max_minute);Ð              }Ð               for (i = 0; i <
60; i += this.timePickerIncrement) {Ð                    var num = i;Ð
                    if (num < 10)Ð                     num = '0' + num;Ð
                    if (i == selected.minute()) {Ð                        html
+= '<option value="' + i + '" selected="selected">' + num + '</option>';Ð
                    } else if (i < min_minute || i > max_minute) {Ð
                        html += '<option value="' + i + '"
disabled="disabled" class="disabled">' + num + '</option>';Ð
                    } else {Ð                      html += '<option value="'
+ i + '">' + num + '</option>';Ð                    }Ð              }Ð
                html += '</select> ';Ð                if
(this.timePickerSeconds) {Ð                   html += ': <select
class="secondselect">';Ð                  for (i = 0; i < 60; i +=
this.timePickerIncrement) {Ð                    var num = i;Ð
                        if (num < 10)Ð                           num = '0' +
num;Ð                        if (i == selected.second()) {Ð
                        html += '<option value="' + i + '"
selected="selected">' + num + '</option>';Ð                       } else {Ð
                        html += '<option value="' + i + '">' + num + '</
option>';Ð                     }Ð                   }Ð
html += '</select>';Ð               }Ð                if
(this.timePicker12Hour) {Ð                    html += '<select
class="ampmselect">';Ð                  // Disallow selection before the
minDate or after the maxDateÐ                    var am_html = '';Ð
                    var pm_html = '';Ð                    if (minDate && (side
== 'left' || this.singleDatePicker) && selected.format('YYYY-MM-DD') ==
minDate.format('YYYY-MM-DD') && minDate.hour() >= 12) {Ð
                        am_html = ' disabled="disabled" class="disabled"';Ð
                    }Ð                   if (maxDate && (side == 'right' ||
this.singleDatePicker) && selected.format('YYYY-MM-DD') ==
maxDate.format('YYYY-MM-DD') && maxDate.hour() < 12) {Ð
pm_html = ' disabled="disabled" class="disabled"';Ð                    }Ð
                    if (selected.hour() >= 12) {Ð                      html
+= '<option value="AM"' + am_html + '>AM</option><option value="PM"
selected="selected"' + pm_html + '>PM</option>';Ð                  } else {Ð
                        html += '<option value="AM" selected="selected"' +
am_html + '>AM</option><option value="PM"' + pm_html + '>PM</option>';Ð
                    }Ð                   html += '</select>';Ð               }Ð
                html += '</div>';Ð           }Ð           return html;Ð
        },Ð       remove: function() {Ð           this.container.remove();Ð
            this.element.off('.daterangepicker');Ð
this.element.removeData('daterangepicker');Ð       }Ð   };Ð
$.fn.daterangepicker = function (options, cb) {Ð       this.each(function () {Ð
            var el = $(this);Ð           if (el.data('daterangepicker'))Ð
                el.data('daterangepicker').remove();Ð
el.data('daterangepicker', new DateRangePicker(el, options, cb));Ð       });Ð
        return this;Ð   };Ð}));Ð
```

public\assets\js\plugins\diff_match_patch\javascript\diff_match_patch.js

```
(function(){function diff_match_patch(){this.Diff_Timeout=1;this.Diff_EditCost
=4;this.Match_Threshold=0.5;this.Match_Distance=1E3;this.Patch_DeleteThreshold
=0.5;this.Patch_Margin=4;this.Match_MaxBits=32}Ð
diff_match_patch.prototype.diff_main=function(a,b,c,d){"undefined"==typeof
d&&(d=0>=this.Diff_Timeout?Number.MAX_VALUE:(new
Date).getTime()+1E3*this.Diff_Timeout);if(null==a||null==b)throw Error("Null
input. (diff_main)");if(a==b)return a?[[0,a]]:[];"undefined"==typeof c&&(c=!
0);var
e=c,f=this.diff_commonPrefix(a,b);c=a.substring(0,f);a=a.substring(f);b=b.substring(f);var
f=this.diff_commonSuffix(a,b),g=a.substring(a.length-
f);a=a.substring(0,a.length-f);b=b.substring(0,b.length-
f);a=this.diff_compute_(a,Ð
b,e,d);c&&a.unshift([0,c]);g&&a.push([0,g]);this.diff_cleanupMerge(a);return
a};Ðdiff_match_patch.prototype.diff_compute_=function(a,b,c,d){if(!
a)return[[1,b]];if(!b)return[[-1,a]];var e=a.length>b.length?
a:b,f=a.length>b.length?b:a,g=e.indexOf(f);return-1!=g?
(c=[[1,e.substring(0,g)],[0,f],
[1,e.substring(g+f.length)]],a.length>b.length&&(c[0][0]=c[2]
[0]=-1),c):1==f.length?[[-1,a],[1,b]]:(e=this.diff_halfMatch_(a,b))?(f=e[0],a=
e[1],g=e[2],b=e[3],e=e[4],f=this.diff_main(f,g,c,d),c=this.diff_main(a,b,c,d),
f.concat([[0,e]],c)):c&&100<a.length&&100<b.length?this.diff_lineMode_(a,b,Ð
d):this.diff_bisect_(a,b,d)};Ð
diff_match_patch.prototype.diff_lineMode_=function(a,b,c){var
d=this.diff_linesToChars_(a,b);a=d.chars1;b=d.chars2;d=d.lineArray;a=this.diff_main(a,b,!
1,c);this.diff_charsToLines_(a,d);this.diff_cleanupSemantic(a);a.push([0,""]);for(var
e=d=b=0,f="",g="";b<a.length;){switch(a[b][0]){case 1:e++;g+=a[b]
[1];break;case -1:d++;f+=a[b][1];break;case 0:if(1<=d&&1<=e){a.splice(b-d-
e,d+e);b=b-d-e;d=this.diff_main(f,g,!
1,c);for(e=d.length-1;0<=e;e--)a.splice(b,0,d[e]);b+=d.length}d=e=0;g=f=""}b+
+}a.pop();return a};Ðdiff_match_patch.prototype.diff_bisect_=function(a,b,c)
{for(var
d=a.length,e=b.length,f=Math.ceil((d+e)/2),g=f,h=2*f,j=Array(h),i=Array(h),k=0;k<h;k+
+)j[k]=-1,i[k]=-1;j[g+1]=0;i[g+1]=0;for(var k=d-e,q=0!
=k%2,r=0,t=0,p=0,w=0,v=0;v<f&&!((new Date).getTime()>c);v++){for(var n=-
v+r;n<=v-t;n+=2){var l=g+n,m;m=n==-v||n!=v&&j[l-1]<j[l+1]?
j[l+1]:j[l-1]+1;for(var s=m-n;m<d&&s<e&&a.charAt(m)==b.charAt(s);)m++,s+
+;j[l]=m;if(m>d)t+=2;else if(s>e)r+=2;else if(q&&(l=g+k-n,0<=l&&l<h&&-1!
=i[l])){var u=d-i[l];if(m>=Ð)return this.diff_bisectSplit_(a,b,m,s,c)}}for(n=-
v+p;n<=v-w;n+=2){l=g+n;u=n==-v||n!=v&&i[l-1]<i[l+1]?i[l+1]:i[l-1]+1;for(m=u-
n;u<d&&m<e&&a.charAt(d-u-1)==b.charAt(e-m-1);)u++,m++;i[l]=u;if(u>d)w+=2;else
if(m>e)p+=2;else if(!q&&(l=g+k-n,0<=l&&(l<h&&-1!=j[l])&&(m=j[l],s=g+m-l,u=d-
u,m>=u)))return this.diff_bisectSplit_(a,b,m,s,c)}}return[[-1,a],[1,b]]};Ð
diff_match_patch.prototype.diff_bisectSplit_=function(a,b,c,d,e){var
f=a.substring(0,c),g=b.substring(0,d);a=a.substring(c);b=b.substring(d);f=this.diff_main(f
1,e);e=this.diff_main(a,b,!1,e);return f.concat(e)};Ð
diff_match_patch.prototype.diff_linesToChars_=function(a,b){function c(a)
{for(var b="",c=0,f=-1,g=d.length;f<a.length-1;)
{f=a.indexOf("\n",c);-1==f&&(f=a.length-1);var r=a.substring(c,f+1),c=f+1;
(e.hasOwnProperty?e.hasOwnProperty(r):void 0!==e[r])?
b+=String.fromCharCode(e[r]):(b+=String.fromCharCode(g),e[r]=g,d[g++]=r)}
return b}var d=[],e={};d[0]="";var
f=c(a),g=c(b);return{chars1:f,chars2:g,lineArray:d}};Ð
diff_match_patch.prototype.diff_charsToLines_=function(a,b){for(var
c=0;c<a.length;c++){for(var d=a[c][1],e=[],f=0;f<d.length;f+
+)e[f]=b[d.charCodeAt(f)];a[c]
[1]=e.join("")}};diff_match_patch.prototype.diff_commonPrefix=function(a,b)
{if(!a||!b||a.charAt(0)!=b.charAt(0))return 0;for(var
c=0,d=Math.min(a.length,b.length),e=d,f=0;c<e;)a.substring(f,e)==b.substring(f,e)?
```

```
f=c=e:d=e,e=Math.floor((d-c)/2+c);return e};Ð
diff_match_patch.prototype.diff_commonSuffix=function(a,b){if(!a||!b||
a.charAt(a.length-1)!=b.charAt(b.length-1))return 0;for(var
c=0,d=Math.min(a.length,b.length),e=d,f=0;c<e;)a.substring(a.length-
e,a.length-f)==b.substring(b.length-e,b.length-f)?f=c=e:d=e,e=Math.floor((d-
c)/2+c);return e};Ðdiff_match_patch.prototype.diff_commonOverlap_=function(a,b)
{var c=a.length,d=b.length;if(0==c||0==d)return 0;c>d?a=a.substring(c-
d):c<d&&(b=b.substring(0,c));c=Math.min(c,d);if(a==b)return c;for(var
d=0,e=1;;){var f=a.substring(c-e),f=b.indexOf(f);if(-1==f)return
d;e+=f;if(0==f||a.substring(c-e)==b.substring(0,e))d=e,e++}};Ð
diff_match_patch.prototype.diff_halfMatch_=function(a,b){function c(a,b,c)
{for(var d=a.substring(c,c+Math.floor(a.length/4)),e=-1,g="",h,j,n,l;-1!
=(e=b.indexOf(d,e+1));){var m=f.diff_commonPrefix(a.substring(c),b.substring(e
)),s=f.diff_commonSuffix(a.substring(0,c),b.substring(0,e));g.length<s+m&&(g=b
.substring(e-s,e)+b.substring(e,e+m),h=a.substring(0,c-
s),j=a.substring(c+m),n=b.substring(0,e-s),l=b.substring(e+m))}return
2*g.length>=a.length?[h,j,n,l,g]:null}if(0>=this.Diff_Timeout)return null;Ðvar
d=a.length>b.length?a:b,e=a.length>b.length?b:a;if(4>d.length||
2*e.length<d.length)return null;var
f=this,g=c(d,e,Math.ceil(d.length/4)),d=c(d,e,Math.ceil(d.length/2)),h;if(!
g&&!d)return null;h=d?g?g[4].length>d[4].length?g:d:d:g;var
j;a.length>b.length?(g=h[0],d=h[1],e=h[2],j=h[3]):
(e=h[0],j=h[1],g=h[2],d=h[3]);h=h[4];return[g,d,e,j,h]};Ð
diff_match_patch.prototype.diff_cleanupSemantic=function(a){for(var b=!
1,c=[],d=0,e=null,f=0,g=0,h=0,j=0,i=0;f<a.length;)0==a[f][0]?(c[d+
+]=f,g=j,h=i,i=j=0,e=a[f][1]):(1==a[f][0]?j+=a[f][1].length:i+=a[f]
[1].length,e&&(e.length<=Math.max(g,h)&&e.length<=Math.max(j,i))&&(a.splice(c[d-1],0,
[-1,e]),a[c[d-1]+1][0]=1,d--,d--,f=0<d?c[d-1]:-1,i=j=h=g=0,e=null,b=!0)),f+
+;b&&this.diff_cleanupMerge(a);this.diff_cleanupSemanticLossless(a);for(f=1;f<a.length;)
{if(-1==a[f-1][0]&&1==a[f][0]){b=a[f-1][1];c=a[f][1];Ð
d=this.diff_commonOverlap_(b,c);e=this.diff_commonOverlap_(c,b);if(d>=e)
{if(d>=b.length/2||d>=c.length/2)a.splice(f,0,[0,c.substring(0,d)]),a[f-1]
[1]=b.substring(0,b.length-d),a[f+1][1]=c.substring(d),f++}else
if(e>=b.length/2||e>=c.length/2)a.splice(f,0,[0,b.substring(0,e)]),a[f-1]
[0]=1,a[f-1][1]=c.substring(0,c.length-e),a[f+1][0]=-1,a[f+1]
[1]=b.substring(e),f++;f++}f++}};Ð
diff_match_patch.prototype.diff_cleanupSemanticLossless=function(a){function
b(a,b){if(!a||!b)return 6;var c=a.charAt(a.length-1),d=b.charAt(0),e=c.match(d
iff_match_patch.nonAlphaNumericRegex_),f=d.match(diff_match_patch.nonAlphaNume
ricRegex_),g=e&&c.match(diff_match_patch.whitespaceRegex_),h=f&&d.match(diff_m
atch_patch.whitespaceRegex_),c=g&&c.match(diff_match_patch.linebreakRegex_),d=
h&&d.match(diff_match_patch.linebreakRegex_),i=c&&a.match(diff_match_patch.bla
nklineEndRegex_),j=d&&b.match(diff_match_patch.blanklineStartRegex_);Ðreturn
i||j?5:c||d?4:e&&!g&&h?3:g||h?2:e||f?1:0}for(var c=1;c<a.length-1;)
{if(0==a[c-1][0]&&0==a[c+1][0]){var d=a[c-1][1],e=a[c][1],f=a[c+1]
[1],g=this.diff_commonSuffix(d,e);if(g)var h=e.substring(e.length-
g),d=d.substring(0,d.length-g),e=h+e.substring(0,e.length-g),f=h+f;for(var
g=d,h=e,j=f,i=b(d,e)+b(e,f);e.charAt(0)===f.charAt(0);){var
d=d+e.charAt(0),e=e.substring(1)+f.charAt(0),f=f.substring(1),k=b(d,e)+b(e,f);k>=i&&(i=k,g
a[c-1][1]!=g&&(g?a[c-1][1]=g:(a.splice(c-1,1),c--),a[c][1]=Ð,j?a[c+1][1]=j:
(a.splice(c+1,1),c--))}c++}};diff_match_patch.nonAlphaNumericRegex_=/[^a-zA-
Z0-9]/;diff_match_patch.whitespaceRegex_=/
\s/;diff_match_patch.linebreakRegex_=/
[\r\n]/;diff_match_patch.blanklineEndRegex_=/\n\r?
\n$/;diff_match_patch.blanklineStartRegex_=/^\r?\n\r?\n/;Ð
diff_match_patch.prototype.diff_cleanupEfficiency=function(a){for(var b=!
1,c=[],d=0,e=null,f=0,g=!1,h=!1,j=!1,i=!1;f<a.length;){if(0==a[f][0])a[f]
[1].length<this.Diff_EditCost&&(j||i)?(c[d++]=f,g=j,h=i,e=a[f][1]):
(d=0,e=null),j=i=!1;else if(-1==a[f][0]?i=!0:j=!0,e&&(g&&h&&j&&i||
e.length<this.Diff_EditCost/2&&3==g+h+j+i))a.splice(c[d-1],0,
[-1,e]),a[c[d-1]+1][0]=1,d--,e=null,g&&h?(j=i=!0,d=0):(d--,f=0<d?
```

```
c[d-1]:-1,j=i=!1),b=!0;f++}b&&this.diff_cleanupMerge(a)};Ð
diff_match_patch.prototype.diff_cleanupMerge=function(a)
{a.push([0,""]);for(var b=0,c=0,d=0,e="",f="",g;b<a.length;)switch(a[b][0])
{case 1:d++;f+=a[b][1];b++;break;case -1:c++;e+=a[b][1];b++;break;case
0:1<c+d?(0!==c&&0!==d&&(g=this.diff_commonPrefix(f,e),0!==g&&(0<b-c-d&&0==a[b-
c-d-1][0]?a[b-c-d-1][1]+=f.substring(0,g):(a.splice(0,0,
[0,f.substring(0,g)]),b+
+),f=f.substring(g),e=e.substring(g)),g=this.diff_commonSuffix(f,e),0!
==g&&(a[b][1]=f.substring(f.length-g)+a[b][1],f=f.substring(0,f.length-Ð
g),e=e.substring(0,e.length-g))),0===c?a.splice(b-d,c+d,[1,f]):0===d?
a.splice(b-c,c+d,[-1,e]):a.splice(b-c-d,c+d,[-1,e],[1,f]),b=b-c-d+(c?1:0)+(d?
1:0)+1):0!==b&&0==a[b-1][0]?(a[b-1][1]+=a[b][1],a.splice(b,1)):b+
+,c=d=0,f=e=""}""===a[a.length-1][1]&&a.pop();c=!
1;for(b=1;b<a.length-1;)0==a[b-1][0]&&0==a[b+1][0]&&(a[b][1].substring(a[b]
[1].length-a[b-1][1].length)==a[b-1][1]?(a[b][1]=a[b-1][1]+a[b]
[1].substring(0,a[b][1].length-a[b-1][1].length),a[b+1][1]=a[b-1][1]+a[b+1]
[1],a.splice(b-1,1),c=!0):a[b][1].substring(0,Ða[b+1][1].length)==a[b+1]
[1]&&(a[b-1][1]+=a[b+1][1],a[b][1]=a[b][1].substring(a[b+1][1].length)+a[b+1]
[1],a.splice(b+1,1),c=!0)),b+
+;c&&this.diff_cleanupMerge(a)};diff_match_patch.prototype.diff_xIndex=function(a,b)
{var c=0,d=0,e=0,f=0,g;for(g=0;g<a.length;g++){1!==a[g][0]&&(c+=a[g]
[1].length);-1!==a[g][0]&&(d+=a[g][1].length);if(c>b)break;e=c;f=d}return
a.length!=g&&-1===a[g][0]?f:f+(b-e)};Ð
diff_match_patch.prototype.diff_prettyHtml=function(a){for(var b=[],c=/&/g,d=/
</g,e=/>/g,f=/\n/g,g=0;g<a.length;g++){var h=a[g][0],j=a[g]
[1],j=j.replace(c,"&amp;").replace(d,"&lt;").replace(e,"&gt;").replace(f,"&para;<br>");swi
{case 1:b[g]='<ins style="background:#e6ffe6;">'+j+"</ins>";break;case
-1:b[g]='<del style="background:#ffe6e6;">'+j+"</del>";break;case
0:b[g]="<span>"+j+"</span>"}}return b.join("")};Ð
diff_match_patch.prototype.diff_text1=function(a){for(var
b=[],c=0;c<a.length;c++)1!==a[c][0]&&(b[c]=a[c][1]);return
b.join("")};diff_match_patch.prototype.diff_text2=function(a){for(var
b=[],c=0;c<a.length;c++)-1!==a[c][0]&&(b[c]=a[c][1]);return
b.join("")};diff_match_patch.prototype.diff_levenshtein=function(a){for(var
b=0,c=0,d=0,e=0;e<a.length;e++){var f=a[e][0],g=a[e][1];switch(f){case
1:c+=g.length;break;case -1:d+=g.length;break;case 0:b+=Math.max(c,d),d=c=0}}
return b+=Math.max(c,d)};Ðdiff_match_patch.prototype.diff_toDelta=function(a)
{for(var b=[],c=0;c<a.length;c++)switch(a[c][0]){case
1:b[c]="+"+encodeURI(a[c][1]);break;case -1:b[c]="-"+a[c]
[1].length;break;case 0:b[c]="="+a[c][1].length}return b.join("\t").replace(/
%20/g," ")};Ðdiff_match_patch.prototype.diff_fromDelta=function(a,b){for(var
c=[],d=0,e=0,f=b.split(/\t/g),g=0;g<f.length;g++){var
h=f[g].substring(1);switch(f[g].charAt(0)){case "+":try{c[d+
+]=[1,decodeURI(h)]}catch(j){throw Error("Illegal escape in diff_fromDelta:
"+h);}break;case "-":case "=":var i=parseInt(h,10);if(isNaN(i)||0>i)throw
Error("Invalid number in diff_fromDelta:
"+h);h=a.substring(e,e+=i);"="==f[g].charAt(0)?c[d++]=[0,h]:c[d+
+]=[-1,h];break;default:if(f[g])throw Error("Invalid diff operation in
diff_fromDelta: "+Ðf[g]);}}if(e!=a.length)throw Error("Delta length ("+e+")
does not equal source text length ("+a.length+").");return
c};diff_match_patch.prototype.match_main=function(a,b,c){if(null==a||null==b||
null==c)throw Error("Null input.
(match_main)");c=Math.max(0,Math.min(c,a.length));return a==b?0:a.length?
a.substring(c,c+b.length)==b?c:this.match_bitap_(a,b,c):-1};Ð
diff_match_patch.prototype.match_bitap_=function(a,b,c){function d(a,d){var
e=a/b.length,g=Math.abs(c-d);return!f.Match_Distance?g?1:e:e+g/
f.Match_Distance}if(b.length>this.Match_MaxBits)throw Error("Pattern too long
for this browser.");var
e=this.match_alphabet_(b),f=this,g=this.Match_Threshold,h=a.indexOf(b,c);-1!
=h&&(g=Math.min(d(0,h),g),h=a.lastIndexOf(b,c+b.length),-1!
=h&&(g=Math.min(d(0,h),g)));for(var
```

```
j=1<<b.length-1,h=-1,i,k,q=b.length+a.length,r,t=0;t<b.length;t++)
{i=0;for(k=q;i<k;)d(t,c+k)<=g?i=k:q=k,k=Math.floor((q-
i)/2+i);q=k;i=Math.max(1,c-k+1);var
p=Math.min(c+k,a.length)+b.length;k=Array(p+2);for(k[p+1]=(1<<t)-1;p>=i;p--)
{var w=e[a.charAt(p-1)];k[p]=0===t?(k[p+1]<<1|1)&w:(k[p+1]<<1|1)&w|((r[p+1]|
r[p])<<1|1)|
r[p+1];if(k[p]&j&&(w=d(t,p-1),w<=g))if(g=w,h=p-1,h>c)i=Math.max(1,2*c-h);else
break}if(d(t+1,c)>g)break;r=k}return h};
diff_match_patch.prototype.match_alphabet_=function(a){for(var
b={},c=0;c<a.length;c++)b[a.charAt(c)]=0;for(c=0;c<a.length;c+
+)b[a.charAt(c)]|=1<<a.length-c-1;return b};
diff_match_patch.prototype.patch_addContext_=function(a,b){if(0!=b.length)
{for(var c=b.substring(a.start2,a.start2+a.length1),d=0;b.indexOf(c)!
=b.lastIndexOf(c)&&c.length<this.Match_MaxBits-this.Patch_Margin-
this.Patch_Margin;)d+=this.Patch_Margin,c=b.substring(a.start2-
d,a.start2+a.length1+d);d+=this.Patch_Margin;(c=b.substring(a.start2-
d,a.start2))&&a.diffs.unshift([0,c]);
(d=b.substring(a.start2+a.length1,a.start2+a.length1+d))&&a.diffs.push([0,d]);a.start1-
=c.length;a.start2-=c.length;a.length1+=
c.length+d.length;a.length2+=c.length+d.length}};
diff_match_patch.prototype.patch_make=function(a,b,c){var
d;if("string"==typeof a&&"string"==typeof b&&"undefined"==typeof
c)d=a,b=this.diff_main(d,b,!
0),2<b.length&&(this.diff_cleanupSemantic(b),this.diff_cleanupEfficiency(b));else
if(a&&"object"==typeof a&&"undefined"==typeof b&&"undefined"==typeof
c)b=a,d=this.diff_text1(b);else if("string"==typeof a&&b&&"object"==typeof
b&&"undefined"==typeof c)d=a;else if("string"==typeof a&&"string"==typeof
b&&c&&"object"==typeof c)d=a,b=c;else throw Error("Unknown call format to
patch_make.");if(0===b.length)return[];c=[];a=new
diff_match_patch.patch_obj;for(var e=0,f=0,g=0,h=d,j=0;j<b.length;j++){var
i=b[j][0],k=b[j][1];!e&&0!==i&&(a.start1=f,a.start2=g);switch(i){case
1:a.diffs[e+
+]=b[j];a.length2+=k.length;d=d.substring(0,g)+k+d.substring(g);break;case
-1:a.length1+=k.length;a.diffs[e+
+]=b[j];d=d.substring(0,g)+d.substring(g+k.length);break;case
0:k.length<=2*this.Patch_Margin&&e&&b.length!=j+1?(a.diffs[e+
+]=b[j],a.length1+=k.length,a.length2+=k.length):k.length>=2*this.Patch_Margin&&
e&&(this.patch_addContext_(a,h),c.push(a),a=new
diff_match_patch.patch_obj,e=0,h=d,f=g)}1!==i&&(f+=k.length);-1!
==i&&(g+=k.length)}e&&(this.patch_addContext_(a,h),c.push(a));return
c};diff_match_patch.prototype.patch_deepCopy=function(a){for(var
b=[],c=0;c<a.length;c++){var d=a[c],e=new
diff_match_patch.patch_obj;e.diffs=[];for(var f=0;f<d.diffs.length;f+
+)e.diffs[f]=d.diffs[f].slice();e.start1=d.start1;e.start2=d.start2;e.length1=d.length1;e.
return b};diff_match_patch.prototype.patch_apply=function(a,b)
{if(0==a.length)return[b,[]];a=this.patch_deepCopy(a);var
c=this.patch_addPadding(a);b=c+b+c;this.patch_splitMax(a);for(var
d=0,e=[],f=0;f<a.length;f++){var
g=a[f].start2+d,h=this.diff_text1(a[f].diffs),j,i=-1;if(h.length>this.Match_MaxBits)
{if(j=this.match_main(b,h.substring(0,this.Match_MaxBits),g),-1!
=j&&(i=this.match_main(b,h.substring(h.length-this.Match_MaxBits),g+h.length-
this.Match_MaxBits),-1==i||j>=i))j=-1}else j=this.match_main(b,h,g);
if(-1==j)e[f]=!1,d-=a[f].length2-a[f].length1;else if(e[f]=!0,d=j-g,g=-1==i?
b.substring(j,j+h.length):b.substring(j,i+this.Match_MaxBits),h==g)b=b.substring(0,j)+this
if(g=this.diff_main(h,g,!
1),h.length>this.Match_MaxBits&&this.diff_levenshtein(g)/
h.length>this.Patch_DeleteThreshold)e[f]=!
1;else{this.diff_cleanupSemanticLossless(g);for(var
h=0,k,i=0;i<a[f].diffs.length;i++){var q=a[f].diffs[i];0!
==q[0]&&(k=this.diff_xIndex(g,h));1===q[0]?b=b.substring(0,
```

```
j+k)+q[1]+b.substring(j+k):-1===q[0]&&(b=b.substring(0,j+k)+b.substring(j+this.diff_xIndex
==q[0]&&(h+=q[1].length)}}}b=b.substring(c.length,b.length-
c.length);return[b,e]};Ðdiff_match_patch.prototype.patch_addPadding=function(a)
{for(var b=this.Patch_Margin,c="",d=1;d<=b;d+
+)c+=String.fromCharCode(d);for(d=0;d<a.length;d+
+)a[d].start1+=b,a[d].start2+=b;var d=a[0],e=d.diffs;if(0==e.length||0!=e[0]
[0])e.unshift([0,c]),d.start1-=b,d.start2-=b,d.length1+=b,d.length2+=b;else
if(b>e[0][1].length){var f=b-e[0][1].length;e[0][1]=c.substring(e[0]
[1].length)+e[0][1];d.start1-=f;d.start2-=f;d.length1+=f;d.length2+=f}
d=a[a.length-1];e=d.diffs;0==e.length||0!=e[e.length-1][0]?(e.push([0,Ð
c]),d.length1+=b,d.length2+=b):b>e[e.length-1][1].length&&(f=b-e[e.length-1]
[1].length,e[e.length-1]
[1]+=c.substring(0,f),d.length1+=f,d.length2+=f);return c};Ð
diff_match_patch.prototype.patch_splitMax=function(a){for(var
b=this.Match_MaxBits,c=0;c<a.length;c++)if(!(a[c].length1<=b)){var
d=a[c];a.splice(c--,1);for(var e=d.start1,f=d.start2,g="";0!==d.diffs.length;)
{var h=new diff_match_patch.patch_obj,j=!0;h.start1=e-g.length;h.start2=f-
g.length;""!==g&&(h.length1=h.length2=g.length,h.diffs.push([0,g]));for(;0!
==d.diffs.length&&h.length1<b-this.Patch_Margin;){var g=d.diffs[0]
[0],i=d.diffs[0][1];1===g?
(h.length2+=i.length,f+=i.length,h.diffs.push(d.diffs.shift()),Ðj=!
1):-1===g&&1==h.diffs.length&&0==h.diffs[0][0]&&i.length>2*b?
(h.length1+=i.length,e+=i.length,j=!1,h.diffs.push([g,i]),d.diffs.shift()):
(i=i.substring(0,b-h.length1-
this.Patch_Margin),h.length1+=i.length,e+=i.length,0===g?
(h.length2+=i.length,f+=i.length):j=!1,h.diffs.push([g,i]),i==d.diffs[0][1]?
d.diffs.shift():d.diffs[0][1]=d.diffs[0][1].substring(i.length))}
g=this.diff_text2(h.diffs);g=g.substring(g.length-
this.Patch_Margin);i=this.diff_text1(d.diffs).substring(0,this.Patch_Margin);""!
==i&&Ðh.length1+=i.length,h.length2+=i.length,0!
==h.diffs.length&&0===h.diffs[h.diffs.length-1][0]?h.diffs[h.diffs.length-1]
[1]+=i:h.diffs.push([0,i]));j||a.splice(+
+c,0,h)}}};diff_match_patch.prototype.patch_toText=function(a){for(var
b=[],c=0;c<a.length;c++)b[c]=a[c];return b.join("")};Ð
diff_match_patch.prototype.patch_fromText=function(a){var b=[];if(!a)return
b;a=a.split("\n");for(var c=0,d=/^@@ -(\d+),?(\d*) \+(\d+),?(\d*)
@@$/;c<a.length;){var e=a[c].match(d);if(!e)throw Error("Invalid patch
string: "+a[c]);var f=new
diff_match_patch.patch_obj;b.push(f);f.start1=parseInt(e[1],10);""===e[2]?
(f.start1--,f.length1=1):"0"==e[2]?f.length1=0:
(f.start1--,f.length1=parseInt(e[2],10));f.start2=parseInt(e[3],10);""===e[4]?
(f.start2--,f.length2=1):"0"==e[4]?f.length2=0:(f.start2--,f.length2=Ð
parseInt(e[4],10));for(c++;c<a.length;){e=a[c].charAt(0);try{var
g=decodeURI(a[c].substring(1))}catch(h){throw Error("Illegal escape in
patch_fromText: "+g);}if("-"==e)f.diffs.push([-1,g]);else
if("+"==e)f.diffs.push([1,g]);else if(" "==e)f.diffs.push([0,g]);else
if("@"==e)break;else if(""!==e)throw Error('Invalid patch mode "'+e+'" in:
'+g);c++}}return b};diff_match_patch.patch_obj=function()
{this.diffs=[];this.start2=this.start1=null;this.length2=this.length1=0};Ð
diff_match_patch.patch_obj.prototype.toString=function(){var
a,b;a=0===this.length1?this.start1+",0":1==this.length1?
this.start1+1:this.start1+1+","+this.length1;b=0===this.length2?
this.start2+",0":1==this.length2?
this.start2+1:this.start2+1+","+this.length2;a=["@@ -"+a+" +"+b+" @@\n"];var
c;for(b=0;b<this.diffs.length;b++){switch(this.diffs[b][0]){case
1:c="+";break;case -1:c="-";break;case 0:c=" "}
a[b+1]=c+encodeURI(this.diffs[b][1])+"\n"}return a.join("").replace(/%20/g,"
")};Ðthis.diff_match_patch=diff_match_patch;this.DIFF_DELETE=-1;this.DIFF_INSER
T=1;this.DIFF_EQUAL=0;})()Ð
```

public\assets\js\plugins\dropzone\dropzone.js

```
Ð(function(){Ð   /**Ð    * Require the module at `name`.Ð    *Ð    * @param
{String} nameÐ    * @return {Object} exportsÐ    * @api publicÐ    */Ð
function require(name) {Ð       var module = require.modules[name];Ð       if
(!module) throw new Error('failed to require "' + name + '"');Ð       if (!
('exports' in module) && typeof module.definition === 'function') {Ð
            module.client = module.component = true;Ð
module.definition.call(this, module.exports = {}, module);Ð           delete
module.definition;Ð       }Ð       return module.exports;Ð   }Ð   /**Ð    *
Registered modules.Ð    */Ð   require.modules = {};Ð   /**Ð    * Register
module at `name` with callback `definition`.Ð    *Ð    * @param {String} nameÐ
     * @param {Function} definitionÐ    * @api privateÐ    */Ð
require.register = function (name, definition) {Ð       require.modules[name]
= {Ð           definition: definitionÐ       };Ð   };Ð   /**Ð    * Define a
module's exports immediately with `exports`.Ð    *Ð    * @param {String} nameÐ
     * @param {Generic} exportsÐ    * @api privateÐ    */Ð   require.define =
function (name, exports) {Ð       require.modules[name] = {Ð
exports: exportsÐ       };Ð   };Ð
require.register("component~emitter@1.1.2", function (exports, module) {Ð
        /**Ð        * Expose `Emitter`.Ð        */Ð       module.exports =
Emitter;Ð       /**Ð        * Initialize a new `Emitter`.Ð        *Ð        *
@api publicÐ        */Ð       function Emitter(obj) {Ð           if (obj)
return mixin(obj);Ð       };Ð       /**Ð        * Mixin the emitter
properties.Ð        *Ð        * @param {Object} objÐ        * @return {Object}Ð
         * @api privateÐ        */Ð       function mixin(obj) {Ð
for (var key in Emitter.prototype) {Ð               obj[key] =
Emitter.prototype[key];Ð           }Ð           return obj;Ð       }Ð       /
**Ð        * Listen on the given `event` with `fn`.Ð        *Ð        *
@param {String} eventÐ        * @param {Function} fnÐ        * @return
{Emitter}Ð        * @api publicÐ        */Ð       Emitter.prototype.on =Ð
            Emitter.prototype.addEventListener = function(event, fn){Ð
                this._callbacks = this._callbacks || {};Ð
(this._callbacks[event] = this._callbacks[event] || [])Ð
                    .push(fn);Ð               return this;Ð           };Ð
        /**Ð        * Adds an `event` listener that will be invoked a singleÐ
         * time then automatically removed.Ð        *Ð        * @param
{String} eventÐ        * @param {Function} fnÐ        * @return {Emitter}Ð
         * @api publicÐ        */Ð       Emitter.prototype.once =
function(event, fn){Ð           var self = this;Ð           this._callbacks =
this._callbacks || {};Ð           function on() {Ð
self.off(event, on);Ð               fn.apply(this, arguments);Ð           }Ð
            on.fn = fn;Ð           this.on(event, on);Ð           return this;Ð
        };Ð       /**Ð        * Remove the given callback for `event` or allÐ
         * registered callbacks.Ð        *Ð        * @param {String} eventÐ
         * @param {Function} fnÐ        * @return {Emitter}Ð        * @api
publicÐ        */Ð       Emitter.prototype.off =Ð
Emitter.prototype.removeListener =Ð
Emitter.prototype.removeAllListeners =Ð
Emitter.prototype.removeEventListener = function(event, fn){Ð
                        this._callbacks = this._callbacks || {};Ð
                        // allÐ                        if (0 ==
arguments.length) {Ð                            this._callbacks = {};Ð
                            return this;Ð                        }Ð
                        // specific eventÐ                        var
callbacks = this._callbacks[event];Ð                        if (!callbacks)
return this;Ð                        // remove all handlersÐ
                        if (1 == arguments.length) {Ð
                            delete this._callbacks[event];Ð
                            return this;Ð                        }Ð
                        // remove specific handlerÐ
```

var cb;Ð for (var i = 0; i < callbacks.length; i++) {Ð cb = callbacks[i];Ð if (cb === fn || cb.fn === fn) {Ð callbacks.splice(i, 1);Ð break;Ð }Ð }Ð return this;Ð };Ð /**Ð * Emit `event` with the given args.Ð *Ð * @param {String} eventÐ * @param {Mixed} ...Ð * @return {Emitter}Ð */Ð Emitter.prototype.emit = function(event){Ð this._callbacks = this._callbacks || {};Ð var args = [].slice.call(arguments, 1)Ð , callbacks = this._callbacks[event];Ð if (callbacks) {Ð callbacks = callbacks.slice(0);Ð for (var i = 0, len = callbacks.length; i < len; ++i) {Ð callbacks[i].apply(this, args);Ð }Ð }Ð return this;Ð };Ð /**Ð * Return array of callbacks for `event`.Ð *Ð * @param {String} eventÐ * @return {Array}Ð * @api publicÐ */Ð Emitter.prototype.listeners = function(event){Ð this._callbacks = this._callbacks || {};Ð return this._callbacks[event] || [];Ð };Ð /**Ð * Check if this emitter has `event` handlers.Ð *Ð * @param {String} eventÐ * @return {Boolean}Ð * @api publicÐ */Ð Emitter.prototype.hasListeners = function(event){Ð return !! this.listeners(event).length;Ð };Ð });Ð require.register("dropzone", function (exports, module) {Ð /**Ð * Exposing dropzoneÐ */Ð module.exports = require("dropzone/lib/dropzone.js");Ð });Ð require.register("dropzone/lib/dropzone.js", function (exports, module) {Ð /*Ð *Ð * More info at www.dropzonejs.comÐ *Ð * Copyright (c) 2012, Matias MenoÐ *Ð * Permission is hereby granted, free of charge, to any person obtaining a copyÐ * of this software and associated documentation files (the "Software"), to dealÐ * in the Software without restriction, including without limitation the rightsÐ * to use, copy, modify, merge, publish, distribute, sublicense, and/or sellÐ * copies of the Software, and to permit persons to whom the Software isÐ * furnished to do so, subject to the following conditions:Ð *Ð * The above copyright notice and this permission notice shall be included inÐ * all copies or substantial portions of the Software.Ð *Ð * THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS ORÐ * IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,Ð * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THEÐ * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHERÐ * LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,Ð * OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS INÐ * THE SOFTWARE.Ð *Ð */Ð (function() {Ð var Dropzone, Em, camelize, contentLoaded, detectVerticalSquash, drawImageIOSFix, noop, without,Ð __hasProp = {}.hasOwnProperty,Ð __extends = function(child, parent) { for (var key in parent) { if (__hasProp.call(parent, key)) child[key] = parent[key]; } function ctor() { this.constructor = child; } ctor.prototype = parent.prototype; child.prototype = new ctor(); child.__super__ = parent.prototype; return child; },Ð __slice = [].slice;Ð Em = typeof Emitter ! == "undefined" && Emitter !== null ? Emitter : require("component~emitter@1.1.2");Ð noop = function() {};Ð Dropzone = (function(_super) {Ð var extend;Ð __extends(Dropzone, _super);Ð /*Ð This is a list of all available events you can register on a dropzone object.Ð You can register an event handler like this:Ð dropzone.on("dragEnter", function() { });Ð

```
                                                                    */Ð
                Dropzone.prototype.events = ["drop", "dragstart", "dragend",
"dragenter", "dragover", "dragleave", "addedfile", "removedfile",
"thumbnail", "error", "errormultiple", "processing", "processingmultiple",
"uploadprogress", "totaluploadprogress", "sending", "sendingmultiple",
"success", "successmultiple", "canceled", "canceledmultiple", "complete",
"completemultiple", "reset", "maxfilesexceeded", "maxfilesreached"];Ð
                Dropzone.prototype.defaultOptions = {Ð                    url:
null,Ð                    method: "post",Ð                    withCredentials:
false,Ð                     parallelUploads: 2,Ð
uploadMultiple: false,Ð                    maxFilesize: 256,Ð
                    paramName: "file",Ð
createImageThumbnails: true,Ð                    maxThumbnailFilesize: 10,Ð
                    thumbnailWidth: 100,Ð                    thumbnailHeight:
100,Ð                    maxFiles: null,Ð                    params: {},Ð
                    clickable: true,Ð                    ignoreHiddenFiles:
true,Ð                     acceptedFiles: null,Ð
acceptedMimeTypes: null,Ð                    autoProcessQueue: true,Ð
                    autoQueue: true,Ð                    addRemoveLinks: false,Ð
                    previewsContainer: null,Ð
dictDefaultMessage: "Drop files here to upload",Ð
dictFallbackMessage: "Your browser does not support drag'n'drop file
uploads.",Ð                    dictFallbackText: "Please use the fallback form
below to upload your files like in the olden days.",Ð
dictFileTooBig: "File is too big ({{filesize}}MiB). Max filesize:
{{maxFilesize}}MiB.",Ð                    dictInvalidFileType: "You can't
upload files of this type.",Ð                    dictResponseError: "Server
responded with {{statusCode}} code.",Ð                    dictCancelUpload:
"Cancel upload",Ð                    dictCancelUploadConfirmation: "Are you
sure you want to cancel this upload?",Ð                    dictRemoveFile:
"Remove file",Ð                    dictRemoveFileConfirmation: null,Ð
                    dictMaxFilesExceeded: "You can not upload any more
files.",Ð                    accept: function(file, done) {Ð
                        return done();Ð                    },Ð
                    init: function() {Ð                    return noop;Ð
                    },Ð                    forceFallback: false,Ð
                    fallback: function() {Ð                    var child,
messageElement, span, _i, _len, _ref;Ð
this.element.className = "" + this.element.className + " dz-browser-not-
supported";Ð                    _ref =
this.element.getElementsByTagName("div");Ð                    for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð                    child =
_ref[_i];Ð                    if (/(^| )dz-
message($| )/.test(child.className)) {Ð
messageElement = child;Ð                    child.className = "dz-
message";Ð                    continue;Ð
                            }Ð                    }Ð
if (!messageElement) {Ð                    messageElement =
Dropzone.createElement("<div class=\"dz-message\"><span></span></div>");Ð
                            this.element.appendChild(messageElement);Ð
                        }Ð                    span =
messageElement.getElementsByTagName("span")[0];Ð                    if
(span) {Ð                    span.textContent =
this.options.dictFallbackMessage;Ð                    }Ð
                        return
this.element.appendChild(this.getFallbackForm());Ð                    },Ð
                    resize: function(file) {Ð                    var info,
srcRatio, trgRatio;Ð                    info = {Ð
                            srcX: 0,Ð                    srcY: 0,Ð
                            srcWidth: file.width,Ð
```

```
srcHeight: file.heightÐ                        };Ð
srcRatio = file.width / file.height;Ð                        trgRatio =
this.options.thumbnailWidth / this.options.thumbnailHeight;Ð
                        if (file.height < this.options.thumbnailHeight ||
file.width < this.options.thumbnailWidth) {Ð
info.trgHeight = info.srcHeight;Ð                            info.trgWidth =
info.srcWidth;Ð                        } else {Ð                            if
(srcRatio > trgRatio) {Ð                                info.srcHeight =
file.height;Ð                              info.srcWidth = info.srcHeight *
trgRatio;Ð                            } else {Ð
info.srcWidth = file.width;Ð                                info.srcHeight =
info.srcWidth / trgRatio;Ð                              }Ð
                        }Ð                        info.srcX = (file.width -
info.srcWidth) / 2;Ð                        info.srcY = (file.height -
info.srcHeight) / 2;Ð                        return info;Ð                    },Ð
                    /*Ð                        Those functions register
themselves to the events on init and handle allÐ                    the user
interface specific stuff. Overwriting them won't break the uploadÐ
                     but can break the way it's displayed.Ð
                     You can overwrite them if you don't like the default
behavior. If you justÐ                    want to add an additional event
handler, register it on the dropzone objectÐ                    and don't
overwrite those options.Ð                        */Ð                    drop:
function(e) {Ð                        return this.element.classList.remove("dz-
drag-hover");Ð                    },Ð                    dragstart: noop,Ð
                    dragend: function(e) {Ð                        return
this.element.classList.remove("dz-drag-hover");Ð                    },Ð
                    dragenter: function(e) {Ð                        return
this.element.classList.add("dz-drag-hover");Ð                    },Ð
                    dragover: function(e) {Ð                        return
this.element.classList.add("dz-drag-hover");Ð                    },Ð
                    dragleave: function(e) {Ð                        return
this.element.classList.remove("dz-drag-hover");Ð                    },Ð
                    paste: noop,Ð                    reset: function() {Ð
                        return this.element.classList.remove("dz-started");Ð
                    },Ð                    addedfile: function(file) {Ð
                        var node, removeFileEvent, removeLink, _i, _j, _k,
_len, _len1, _len2, _ref, _ref1, _ref2, _results;Ð                        if
(this.element === this.previewsContainer) {Ð
this.element.classList.add("dz-started");Ð                        }Ð
                        file.previewElement =
Dropzone.createElement(this.options.previewTemplate.trim());Ð
                        file.previewTemplate = file.previewElement;Ð

this.previewsContainer.appendChild(file.previewElement);Ð
                        _ref = file.previewElement.querySelectorAll("[data-dz-
name]");Ð                        for (_i = 0, _len = _ref.length; _i < _len;
_i++) {Ð                            node = _ref[_i];Ð
                            node.textContent = file.name;Ð
                        }Ð                        _ref1 =
file.previewElement.querySelectorAll("[data-dz-size]");Ð
                        for (_j = 0, _len1 = _ref1.length; _j < _len1; _j++) {Ð
                            node = _ref1[_j];Ð
node.innerHTML = this.filesize(file.size);Ð                        }Ð
                        if (this.options.addRemoveLinks) {Ð
                            file._removeLink = Dropzone.createElement("<a
class=\"dz-remove\" href=\"javascript:undefined;\" data-dz-remove>" +
this.options.dictRemoveFile + "</a>");Ð
file.previewElement.appendChild(file._removeLink);Ð
```

```
                                                                                    }Ð
                        removeFileEvent = (function(_this) {Ð
                            return function(e) {Ð
                                e.preventDefault();Ð
                                e.stopPropagation();Ð
                                if (file.status === Dropzone.UPLOADING) {Ð
                                    return
Dropzone.confirm(_this.options.dictCancelUploadConfirmation, function() {Ð
                                        return _this.removeFile(file);Ð
                                    });Ð                                } else
{Ð                                   if
(_this.options.dictRemoveFileConfirmation) {Ð
                                        return
Dropzone.confirm(_this.options.dictRemoveFileConfirmation, function() {Ð
                                            return _this.removeFile(file);Ð
                                        });Ð
                                    } else {Ð
                                        return _this.removeFile(file);Ð
                                    }Ð                                  }Ð
                            };Ð                        })(this);Ð
                        _ref2 = file.previewElement.querySelectorAll("[data-
dz-remove]");Ð                          _results = [];Ð
for (_k = 0, _len2 = _ref2.length; _k < _len2; _k++) {Ð
                            removeLink = _ref2[_k];Ð

_results.push(removeLink.addEventListener("click", removeFileEvent));Ð
                        }Ð                        return _results;Ð
                    },Ð                    removedfile: function(file) {Ð
                        var _ref;Ð                        if ((_ref =
file.previewElement) != null) {Ð
_ref.parentNode.removeChild(file.previewElement);Ð                        }Ð
                        return this._updateMaxFilesReachedClass();Ð
                    },Ð                    thumbnail: function(file, dataUrl) {Ð
                        var thumbnailElement, _i, _len, _ref, _results;Ð
                        file.previewElement.classList.remove("dz-file-
preview");Ð                        file.previewElement.classList.add("dz-image-
preview");Ð                        _ref =
file.previewElement.querySelectorAll("[data-dz-thumbnail]");Ð
                        _results = [];Ð                        for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð
thumbnailElement = _ref[_i];Ð                            thumbnailElement.alt
= file.name;Ð                            _results.push(thumbnailElement.src =
dataUrl);Ð                        }Ð                        return _results;Ð
                    },Ð                    error: function(file, message) {Ð
                        var node, _i, _len, _ref, _results;Ð
                        file.previewElement.classList.add("dz-error");Ð
                        if (typeof message !== "String" && message.error) {Ð
                            message = message.error;Ð                        }Ð
                        _ref = file.previewElement.querySelectorAll("[data-dz-
errormessage]");Ð                        _results = [];Ð
for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                            node = _ref[_i];Ð
_results.push(node.textContent = message);Ð                        }Ð
                        return _results;Ð                    },Ð
                    errormultiple: noop,Ð                    processing:
function(file) {Ð                        file.previewElement.classList.add("dz-
processing");Ð                        if (file._removeLink) {Ð
                            return file._removeLink.textContent =
this.options.dictCancelUpload;Ð                        }Ð                    },Ð
                    processingmultiple: noop,Ð
```

```
uploadprogress: function(file, progress, bytesSent) {Ð
var node, _i, _len, _ref, _results;Ð                        _ref =
file.previewElement.querySelectorAll("[data-dz-uploadprogress]");Ð
                        _results = [];Ð                       for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð                           node =
_ref[_i];Ð                            _results.push(node.style.width = "" +
progress + "%");Ð                        }Ð                       return
_results;Ð                    },Ð                   totaluploadprogress: noop,Ð
                    sending: noop,Ð                   sendingmultiple: noop,Ð
                    success: function(file) {Ð                       return
file.previewElement.classList.add("dz-success");Ð                     },Ð
                    successmultiple: noop,Ð                   canceled:
function(file) {Ð                       return this.emit("error", file,
"Upload canceled.");Ð                   },Ð
canceledmultiple: noop,Ð                   complete: function(file) {Ð
                        if (file._removeLink) {Ð
return file._removeLink.textContent = this.options.dictRemoveFile;Ð
                        }Ð                   },Ð
completemultiple: noop,Ð                   maxfilesexceeded: noop,Ð
                    maxfilesreached: noop,Ð
previewTemplate: "<div class=\"dz-preview dz-file-preview\">\n  <div
class=\"dz-details\">\n    <div class=\"dz-filename\"><span data-dz-name></
span></div>\n    <div class=\"dz-size\" data-dz-size></div>\n    <img data-dz-
thumbnail />\n  </div>\n  <div class=\"dz-progress\"><span class=\"dz-
upload\" data-dz-uploadprogress></span></div>\n  <div class=\"dz-success-
mark\"><span>' </span></div>\n  <div class=\"dz-error-mark\"><span>' </span></
div>\n  <div class=\"dz-error-message\"><span data-dz-errormessage></span></
div>\n</div>"Ð                 };Ð                extend = function() {Ð
                    var key, object, objects, target, val, _i, _len;Ð
                    target = arguments[0], objects = 2 <= arguments.length ?
__slice.call(arguments, 1) : [];Ð                   for (_i = 0, _len =
objects.length; _i < _len; _i++) {Ð                       object =
objects[_i];Ð                       for (key in object) {Ð
                        val = object[key];Ð
target[key] = val;Ð                       }Ð                   }Ð
                    return target;Ð                 };Ð                function
Dropzone(element, options) {Ð                   var elementOptions, fallback,
_ref;Ð                   this.element = element;Ð
this.version = Dropzone.version;Ð
this.defaultOptions.previewTemplate =
this.defaultOptions.previewTemplate.replace(/\n*/g, "");Ð
this.clickableElements = [];Ð                   this.listeners = [];Ð
                    this.files = [];Ð                   if (typeof
this.element === "string") {Ð                   this.element =
document.querySelector(this.element);Ð                   }Ð
if (!(this.element && (this.element.nodeType != null))) {Ð
                        throw new Error("Invalid dropzone element.");Ð
                    }Ð                   if (this.element.dropzone) {Ð
                        throw new Error("Dropzone already attached.");Ð
                    }Ð                   Dropzone.instances.push(this);Ð
                    this.element.dropzone = this;Ð
elementOptions = (_ref = Dropzone.optionsForElement(this.element)) != null ?
_ref : {};Ð                   this.options = extend({}, this.defaultOptions,
elementOptions, options != null ? options : {});Ð                   if
(this.options.forceFallback || !Dropzone.isBrowserSupported()) {Ð
                        return this.options.fallback.call(this);Ð
                    }Ð                   if (this.options.url == null) {Ð
                        this.options.url =
this.element.getAttribute("action");Ð
```

```
                                                    }Ð
if (!this.options.url) {Ð                       throw new Error("No URL
provided.");Ð                   }Ð                    if
(this.options.acceptedFiles && this.options.acceptedMimeTypes) {Ð
                        throw new Error("You can't provide both
'acceptedFiles' and 'acceptedMimeTypes'. 'acceptedMimeTypes' is deprecated.");Ð
                    }Ð                  if (this.options.acceptedMimeTypes) {Ð
                        this.options.acceptedFiles =
this.options.acceptedMimeTypes;Ð                        delete
this.options.acceptedMimeTypes;Ð                      }Ð
this.options.method = this.options.method.toUpperCase();Ð
if ((fallback = this.getExistingFallback()) && fallback.parentNode) {Ð
                        fallback.parentNode.removeChild(fallback);Ð
                    }Ð                  if (this.options.previewsContainer) {Ð
                        this.previewsContainer =
Dropzone.getElement(this.options.previewsContainer, "previewsContainer");Ð
                    } else {Ð                       this.previewsContainer =
this.element;Ð                   }Ð                    if
(this.options.clickable) {Ð                       if (this.options.clickable
=== true) {Ð                          this.clickableElements =
[this.element];Ð                      } else {Ð
this.clickableElements = Dropzone.getElements(this.options.clickable,
"clickable");Ð                      }Ð                   }Ð
                    this.init();Ð               }Ð
Dropzone.prototype.getAcceptedFiles = function() {Ð                   var
file, _i, _len, _ref, _results;Ð                   _ref = this.files;Ð
                    _results = [];Ð                   for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                       file = _ref[_i];Ð
                        if (file.accepted) {Ð
_results.push(file);Ð                       }Ð                   }Ð
                    return _results;Ð               };Ð
Dropzone.prototype.getRejectedFiles = function() {Ð                   var
file, _i, _len, _ref, _results;Ð                   _ref = this.files;Ð
                    _results = [];Ð                   for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                       file = _ref[_i];Ð
                        if (!file.accepted) {Ð
_results.push(file);Ð                       }Ð                   }Ð
                    return _results;Ð               };Ð
Dropzone.prototype.getFilesWithStatus = function(status) {Ð
var file, _i, _len, _ref, _results;Ð                   _ref = this.files;Ð
                    _results = [];Ð                   for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                       file = _ref[_i];Ð
                        if (file.status === status) {Ð
                            _results.push(file);Ð                       }Ð
                    }Ð                  return _results;Ð               };Ð
                Dropzone.prototype.getQueuedFiles = function() {Ð
                    return this.getFilesWithStatus(Dropzone.QUEUED);Ð
                };Ð               Dropzone.prototype.getUploadingFiles =
function() {Ð                   return
this.getFilesWithStatus(Dropzone.UPLOADING);Ð               };Ð
Dropzone.prototype.getActiveFiles = function() {Ð                   var file,
_i, _len, _ref, _results;Ð                   _ref = this.files;Ð
                    _results = [];Ð                   for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                       file = _ref[_i];Ð
                        if (file.status === Dropzone.UPLOADING || file.status
=== Dropzone.QUEUED) {Ð                           _results.push(file);Ð
                        }Ð                   }Ð                   return
_results;Ð               };Ð               Dropzone.prototype.init =
function() {Ð                   var eventName, noPropagation,
setupHiddenFileInput, _i, _len, _ref, _ref1;Ð
```

```
                                                                if
(this.element.tagName === "form") {Ð
this.element.setAttribute("enctype", "multipart/form-data");Ð
                    }Ð                    if
(this.element.classList.contains("dropzone") && !
this.element.querySelector(".dz-message")) {Ð
this.element.appendChild(Dropzone.createElement("<div class=\"dz-default dz-
message\"><span>" + this.options.dictDefaultMessage + "</span></div>"));Ð
                    }Ð                    if (this.clickableElements.length) {Ð
                        setupHiddenFileInput = (function(_this) {Ð
                            return function() {Ð
                                if (_this.hiddenFileInput) {Ð

document.body.removeChild(_this.hiddenFileInput);Ð
                                }Ð
_this.hiddenFileInput = document.createElement("input");Ð
                                _this.hiddenFileInput.setAttribute("type",
"file");Ð                               if ((_this.options.maxFiles == null)
|| _this.options.maxFiles > 1) {Ð
_this.hiddenFileInput.setAttribute("multiple", "multiple");Ð
                                }Ð
_this.hiddenFileInput.className = "dz-hidden-input";Ð
                                if (_this.options.acceptedFiles != null) {Ð

_this.hiddenFileInput.setAttribute("accept", _this.options.acceptedFiles);Ð
                                }Ð
_this.hiddenFileInput.style.visibility = "hidden";Ð
                                _this.hiddenFileInput.style.position =
"absolute";Ð                                _this.hiddenFileInput.style.top =
"0";Ð                                _this.hiddenFileInput.style.left = "0";Ð
                                _this.hiddenFileInput.style.height = "0";Ð
                                _this.hiddenFileInput.style.width = "0";Ð

document.body.appendChild(_this.hiddenFileInput);Ð
                                return
_this.hiddenFileInput.addEventListener("change", function() {Ð
                                    var file, files, _i, _len;Ð
                                    files = _this.hiddenFileInput.files;Ð
                                    if (files.length) {Ð
                                        for (_i = 0, _len = files.length; _i
< _len; _i++) {Ð                                    file = files[_i];Ð
                                            _this.addFile(file);Ð
                                        }Ð                                  }Ð
                                    return setupHiddenFileInput();Ð
                                });Ð                            };Ð
                        })(this);Ð
setupHiddenFileInput();Ð                    }Ð                    this.URL =
(_ref = window.URL) != null ? _ref : window.webkitURL;Ð
_ref1 = this.events;Ð                   for (_i = 0, _len = _ref1.length; _i
< _len; _i++) {Ð                       eventName = _ref1[_i];Ð
                        this.on(eventName, this.options[eventName]);Ð
                    }Ð                    this.on("uploadprogress",
(function(_this) {Ð                         return function() {Ð
                            return _this.updateTotalUploadProgress();Ð
                        };Ð                    })(this));Ð
this.on("removedfile", (function(_this) {Ð                        return
function() {Ð                           return
_this.updateTotalUploadProgress();Ð                        };Ð
                    })(this));Ð                    this.on("canceled",
(function(_this) {Ð
```

```
                                        return function(file) {Ð
                            return _this.emit("complete", file);Ð
                        };Ð                    })(this));Ð
this.on("complete", (function(_this) {Ð                        return
function(file) {Ð                            if
(_this.getUploadingFiles().length === 0 && _this.getQueuedFiles().length ===
0) {Ð                                return setTimeout((function() {Ð
                                    return _this.emit("queuecomplete");Ð
                                }), 0);Ð                            }Ð
                        };Ð                    })(this));Ð
noPropagation = function(e) {Ð                        e.stopPropagation();Ð
                        if (e.preventDefault) {Ð
return e.preventDefault();Ð                        } else {Ð
                            return e.returnValue = false;Ð
                        }Ð                    };Ð
this.listeners = [Ð                        {Ð
element: this.element,Ð                            events: {Ð
                                "dragstart": (function(_this) {Ð
                                    return function(e) {Ð
                                        return _this.emit("dragstart", e);Ð
                                    };Ð                                })
(this),Ð                                "dragenter": (function(_this) {Ð
                                    return function(e) {Ð
                                        noPropagation(e);Ð
                                        return _this.emit("dragenter", e);Ð
                                    };Ð                                })
(this),Ð                                "dragover": (function(_this) {Ð
                                    return function(e) {Ð
                                        var efct;Ð
                                        try {Ð
                                            efct =
e.dataTransfer.effectAllowed;Ð                                    } catch
(_error) {}Ð                                    e.dataTransfer.dropEffect
= 'move' === efct || 'linkMove' === efct ? 'move' : 'copy';Ð
                                        noPropagation(e);Ð
                                        return _this.emit("dragover", e);Ð
                                    };Ð                                })
(this),Ð                                "dragleave": (function(_this) {Ð
                                    return function(e) {Ð
                                        return _this.emit("dragleave", e);Ð
                                    };Ð                                })
(this),Ð                                "drop": (function(_this) {Ð
                                    return function(e) {Ð
                                        noPropagation(e);Ð
                                        return _this.drop(e);Ð
                                    };Ð                                })
(this),Ð                                "dragend": (function(_this) {Ð
                                    return function(e) {Ð
                                        return _this.emit("dragend", e);Ð
                                    };Ð                                })(this)Ð
                            }Ð                        }Ð                    ];Ð
                    this.clickableElements.forEach((function(_this) {Ð
                        return function(clickableElement) {Ð
                            return _this.listeners.push({Ð
                                element: clickableElement,Ð
                                events: {Ð
"click": function(evt) {Ð                                    if
((clickableElement !== _this.element) || (evt.target === _this.element ||
Dropzone.elementInside(evt.target, _this.element.querySelector(".dz-
message")))) {Ð
```

```
                                                        return
_this.hiddenFileInput.click();Ð                                        }Ð
                                    }Ð                                }Ð
                              });Ð                        };Ð
                    })(this));Ð                     this.enable();Ð
                    return this.options.init.call(this);Ð              };Ð
                Dropzone.prototype.destroy = function() {Ð
var _ref;Ð                    this.disable();Ð
this.removeAllFiles(true);Ð                    if ((_ref =
this.hiddenFileInput) != null ? _ref.parentNode : void 0) {Ð

this.hiddenFileInput.parentNode.removeChild(this.hiddenFileInput);Ð
                        this.hiddenFileInput = null;Ð                  }Ð
                    delete this.element.dropzone;Ð                  return
Dropzone.instances.splice(Dropzone.instances.indexOf(this), 1);Ð
                };Ð
Dropzone.prototype.updateTotalUploadProgress = function() {Ð
                    var activeFiles, file, totalBytes, totalBytesSent,
totalUploadProgress, _i, _len, _ref;Ð                  totalBytesSent = 0;Ð
                    totalBytes = 0;Ð                  activeFiles =
this.getActiveFiles();Ð                  if (activeFiles.length) {Ð
                        _ref = this.getActiveFiles();Ð
for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                              file = _ref[_i];Ð
totalBytesSent += file.upload.bytesSent;Ð
totalBytes += file.upload.total;Ð                      }Ð
                        totalUploadProgress = 100 * totalBytesSent /
totalBytes;Ð                  } else {Ð
totalUploadProgress = 100;Ð                    }Ð                  return
this.emit("totaluploadprogress", totalUploadProgress, totalBytes,
totalBytesSent);Ð                };Ð
Dropzone.prototype.getFallbackForm = function() {Ð                  var
existingFallback, fields, fieldsString, form;Ð                  if
(existingFallback = this.getExistingFallback()) {Ð
return existingFallback;Ð                  }Ð                  fieldsString
= "<div class=\"dz-fallback\">";Ð                  if
(this.options.dictFallbackText) {Ð                      fieldsString +=
"<p>" + this.options.dictFallbackText + "</p>";Ð                  }Ð
                    fieldsString += "<input type=\"file\" name=\"" +
this.options.paramName + (this.options.uploadMultiple ? "[]" : "") + "\" " +
(this.options.uploadMultiple ? 'multiple="multiple"' : void 0) + " /><input
type=\"submit\" value=\"Upload!\"></div>";Ð                  fields =
Dropzone.createElement(fieldsString);Ð                  if
(this.element.tagName !== "FORM") {Ð                    form =
Dropzone.createElement("<form action=\"" + this.options.url + "\"
enctype=\"multipart/form-data\" method=\"" + this.options.method + "\"></
form>");Ð                      form.appendChild(fields);Ð
                    } else {Ð
this.element.setAttribute("enctype", "multipart/form-data");Ð
                        this.element.setAttribute("method",
this.options.method);Ð                  }Ð                  return form !=
null ? form : fields;Ð                };Ð
Dropzone.prototype.getExistingFallback = function() {Ð                  var
fallback, getFallback, tagName, _i, _len, _ref;Ð
getFallback = function(elements) {Ð                      var el, _i, _len;Ð
                        for (_i = 0, _len = elements.length; _i < _len; _i++)
{Ð                          el = elements[_i];Ð                          if
(/(^| )fallback($| )/.test(el.className)) {Ð
return el;Ð                          }Ð                      }Ð
                    };Ð
```

```
                                        _ref = ["div", "form"];Ð
                    for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                        tagName = _ref[_i];Ð                        if
(fallback = getFallback(this.element.getElementsByTagName(tagName))) {Ð
                            return fallback;Ð                        }Ð
                    }Ð                };Ð
Dropzone.prototype.setupEventListeners = function() {Ð                    var
elementListeners, event, listener, _i, _len, _ref, _results;Ð
                    _ref = this.listeners;Ð                    _results = [];Ð
                    for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                        elementListeners = _ref[_i];Ð
_results.push((function() {Ð                            var _ref1, _results1;Ð
                            _ref1 = elementListeners.events;Ð
                            _results1 = [];Ð                            for
(event in _ref1) {Ð                                listener = _ref1[event];Ð

_results1.push(elementListeners.element.addEventListener(event, listener,
false));Ð                            }Ð                            return
_results1;Ð                        })());Ð                        }Ð
                    return _results;Ð                };Ð
Dropzone.prototype.removeEventListeners = function() {Ð                    var
elementListeners, event, listener, _i, _len, _ref, _results;Ð
                    _ref = this.listeners;Ð                    _results = [];Ð
                    for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                        elementListeners = _ref[_i];Ð
_results.push((function() {Ð                            var _ref1, _results1;Ð
                            _ref1 = elementListeners.events;Ð
                            _results1 = [];Ð                            for
(event in _ref1) {Ð                                listener = _ref1[event];Ð

_results1.push(elementListeners.element.removeEventListener(event, listener,
false));Ð                            }Ð                            return
_results1;Ð                        })());Ð                        }Ð
                    return _results;Ð                };Ð
Dropzone.prototype.disable = function() {Ð                    var file, _i,
_len, _ref, _results;Ð
this.clickableElements.forEach(function(element) {Ð
return element.classList.remove("dz-clickable");Ð                    });Ð
                    this.removeEventListeners();Ð                    _ref =
this.files;Ð                    _results = [];Ð                    for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð                        file = _ref[_i];Ð
                        _results.push(this.cancelUpload(file));Ð
                    }Ð                    return _results;Ð                };Ð
                Dropzone.prototype.enable = function() {Ð
this.clickableElements.forEach(function(element) {Ð
return element.classList.add("dz-clickable");Ð                    });Ð
                    return this.setupEventListeners();Ð                };Ð
                Dropzone.prototype.filesize = function(size) {Ð
                    var string;Ð                    if (size >= 1024 * 1024 *
1024 * 1024 / 10) {Ð                        size = size / (1024 * 1024 * 1024
* 1024 / 10);Ð                        string = "TiB";Ð                    }
else if (size >= 1024 * 1024 * 1024 / 10) {Ð                        size =
size / (1024 * 1024 * 1024 / 10);Ð                        string = "GiB";Ð
                    } else if (size >= 1024 * 1024 / 10) {Ð
                        size = size / (1024 * 1024 / 10);Ð
                        string = "MiB";Ð                    } else if (size >=
1024 / 10) {Ð                        size = size / (1024 / 10);Ð
                        string = "KiB";Ð                    } else {Ð
                        size = size * 10;Ð                        string = "b";Ð
                    }Ð
```

```
                                        return "<strong>" +
(Math.round(size) / 10) + "</strong> " + string;Ð              };Ð
                Dropzone.prototype._updateMaxFilesReachedClass = function() {Ð
                    if ((this.options.maxFiles != null) &&
this.getAcceptedFiles().length >= this.options.maxFiles) {Ð
                        if (this.getAcceptedFiles().length ===
this.options.maxFiles) {Ð
this.emit('maxfilesreached', this.files);Ð                      }Ð
                        return this.element.classList.add("dz-max-files-
reached");Ð                  } else {Ð                    return
this.element.classList.remove("dz-max-files-reached");Ð                  }Ð
                };Ð              Dropzone.prototype.drop = function(e) {Ð
                    var files, items;Ð                  if (!e.dataTransfer)
{Ð                         return;Ð                  }Ð
this.emit("drop", e);Ð                  files = e.dataTransfer.files;Ð
                    if (files.length) {Ð                      items =
e.dataTransfer.items;Ð                      if (items && items.length &&
(items[0].webkitGetAsEntry != null)) {Ð
this._addFilesFromItems(items);Ð                      } else {Ð
                            this.handleFiles(files);Ð                      }Ð
                    }Ð              };Ð
Dropzone.prototype.paste = function(e) {Ð                  var items, _ref;Ð
                    if ((e != null ? (_ref = e.clipboardData) != null ?
_ref.items : void 0 : void 0) == null) {Ð                      return;Ð
                    }Ð                  this.emit("paste", e);Ð
                    items = e.clipboardData.items;Ð                  if
(items.length) {Ð                      return this._addFilesFromItems(items);Ð
                    }Ð              };Ð
Dropzone.prototype.handleFiles = function(files) {Ð                  var
file, _i, _len, _results;Ð                  _results = [];Ð
                    for (_i = 0, _len = files.length; _i < _len; _i++) {Ð
                        file = files[_i];Ð
_results.push(this.addFile(file));Ð                  }Ð
return _results;Ð              };Ð
Dropzone.prototype._addFilesFromItems = function(items) {Ð
var entry, item, _i, _len, _results;Ð                  _results = [];Ð
                    for (_i = 0, _len = items.length; _i < _len; _i++) {Ð
                        item = items[_i];Ð                      if
((item.webkitGetAsEntry != null) && (entry = item.webkitGetAsEntry())) {Ð
                            if (entry.isFile) {Ð
                                _results.push(this.addFile(item.getAsFile()));Ð
                            } else if (entry.isDirectory) {Ð

_results.push(this._addFilesFromDirectory(entry, entry.name));Ð
                            } else {Ð
_results.push(void 0);Ð                          }Ð                      }
else if (item.getAsFile != null) {Ð                          if ((item.kind
== null) || item.kind === "file") {Ð
_results.push(this.addFile(item.getAsFile()));Ð                          }
else {Ð                              _results.push(void 0);Ð
                            }Ð                      } else {Ð
                            _results.push(void 0);Ð                      }Ð
                    }Ð                  return _results;Ð              };Ð
                Dropzone.prototype._addFilesFromDirectory =
function(directory, path) {Ð                  var dirReader, entriesReader;Ð
                    dirReader = directory.createReader();Ð
entriesReader = (function(_this) {Ð                      return
function(entries) {Ð                          var entry, _i, _len;Ð
                            for (_i = 0, _len = entries.length; _i < _len; _i+
+) {Ð
```

```
                                    entry = entries[_i];Ð
                                if (entry.isFile) {Ð
                                    entry.file(function(file) {Ð
                                        if (_this.options.ignoreHiddenFiles
&& file.name.substring(0, 1) === '.') {Ð
                                            return;Ð
                                        }Ð
                                        file.fullPath = "" + path + "/" +
file.name;Ð                                     return _this.addFile(file);Ð
                                    });Ð                                } else
if (entry.isDirectory) {Ð
_this._addFilesFromDirectory(entry, "" + path + "/" + entry.name);Ð
                                }Ð                              }Ð
                            };Ð                   })(this);Ð
return dirReader.readEntries(entriesReader, function(error) {Ð
                            return typeof console !== "undefined" && console !==
null ? typeof console.log === "function" ? console.log(error) : void 0 : void
0;Ð                      });Ð               };Ð
Dropzone.prototype.accept = function(file, done) {Ð                   if
(file.size > this.options.maxFilesize * 1024 * 1024) {Ð
return done(this.options.dictFileTooBig.replace("{{filesize}}",
Math.round(file.size / 1024 / 10.24) / 100).replace("{{maxFilesize}}",
this.options.maxFilesize));Ð                   } else if (!
Dropzone.isValidFile(file, this.options.acceptedFiles)) {Ð
                            return done(this.options.dictInvalidFileType);Ð
                        } else if ((this.options.maxFiles != null) &&
this.getAcceptedFiles().length >= this.options.maxFiles) {Ð

done(this.options.dictMaxFilesExceeded.replace("{{maxFiles}}",
this.options.maxFiles));Ð                       return
this.emit("maxfilesexceeded", file);Ð                   } else {Ð
                            return this.options.accept.call(this, file, done);Ð
                        }Ð               };Ð
Dropzone.prototype.addFile = function(file) {Ð                   file.upload
= {Ð                        progress: 0,Ð                       total:
file.size,Ð                         bytesSent: 0Ð                   };Ð
                        this.files.push(file);Ð                   file.status =
Dropzone.ADDED;Ð                    this.emit("addedfile", file);Ð
                        this._enqueueThumbnail(file);Ð                   return
this.accept(file, (function(_this) {Ð                       return
function(error) {Ð                            if (error) {Ð
                                file.accepted = false;Ð
                                _this._errorProcessing([file], error);Ð
                            } else {Ð
file.accepted = true;Ð                                if
(_this.options.autoQueue) {Ð
_this.enqueueFile(file);Ð                                   }Ð
                            }Ð                           return
_this._updateMaxFilesReachedClass();Ð                       };Ð
                        })(this));Ð               };Ð
Dropzone.prototype.enqueueFiles = function(files) {Ð                   var
file, _i, _len;Ð                    for (_i = 0, _len = files.length; _i <
_len; _i++) {Ð                      file = files[_i];Ð
this.enqueueFile(file);Ð                  }Ð                   return null;Ð
                };Ð               Dropzone.prototype.enqueueFile =
function(file) {Ð                   if (file.status === Dropzone.ADDED &&
file.accepted === true) {Ð                          file.status =
Dropzone.QUEUED;Ð                       if (this.options.autoProcessQueue) {Ð
                            return setTimeout(((function(_this) {Ð
                                return function() {Ð
```

```
                                    return _this.processQueue();Ð
                                };Ð                                })(this)), 0);Ð
                        }Ð                    } else {Ð
throw new Error("This file can't be queued because it has already been
processed or was rejected.");Ð                    }Ð                };Ð
                Dropzone.prototype._thumbnailQueue = [];Ð
Dropzone.prototype._processingThumbnail = false;Ð
Dropzone.prototype._enqueueThumbnail = function(file) {Ð                    if
(this.options.createImageThumbnails && file.type.match(/image.*/) &&
file.size <= this.options.maxThumbnailFilesize * 1024 * 1024) {Ð
                        this._thumbnailQueue.push(file);Ð
                        return setTimeout(((function(_this) {Ð
                            return function() {Ð
                                return _this._processThumbnailQueue();Ð
                            };Ð                        })(this)), 0);Ð
                    }Ð                };Ð
Dropzone.prototype._processThumbnailQueue = function() {Ð
if (this._processingThumbnail || this._thumbnailQueue.length === 0) {Ð
                        return;Ð                    }Ð
this._processingThumbnail = true;Ð                    return
this.createThumbnail(this._thumbnailQueue.shift(), (function(_this) {Ð
                        return function() {Ð
_this._processingThumbnail = false;Ð                            return
_this._processThumbnailQueue();Ð                        };Ð
                    })(this));Ð                };Ð
Dropzone.prototype.removeFile = function(file) {Ð                    if
(file.status === Dropzone.UPLOADING) {Ð
this.cancelUpload(file);Ð                    }Ð                    this.files =
without(this.files, file);Ð                    this.emit("removedfile", file);Ð
                    if (this.files.length === 0) {Ð
return this.emit("reset");Ð                    }Ð                };Ð
                Dropzone.prototype.removeAllFiles =
function(cancelIfNecessary) {Ð                    var file, _i, _len, _ref;Ð
                    if (cancelIfNecessary == null) {Ð
cancelIfNecessary = false;Ð                    }Ð                    _ref =
this.files.slice();Ð                    for (_i = 0, _len = _ref.length; _i <
_len; _i++) {Ð                        file = _ref[_i];Ð
if (file.status !== Dropzone.UPLOADING || cancelIfNecessary) {Ð
                            this.removeFile(file);Ð                        }Ð
                    }Ð                    return null;Ð                };Ð
                Dropzone.prototype.createThumbnail = function(file, callback)
{Ð                    var fileReader;Ð                    fileReader = new
FileReader;Ð                    fileReader.onload = (function(_this) {Ð
                        return function() {Ð                            var
img;Ð                            img = document.createElement("img");Ð
                            img.onload = function() {Ð
                                var canvas, ctx, resizeInfo, thumbnail, _ref,
_ref1, _ref2, _ref3;Ð                                file.width = img.width;Ð
                                file.height = img.height;Ð
                                resizeInfo = _this.options.resize.call(_this,
file);Ð                                if (resizeInfo.trgWidth == null) {Ð
                                    resizeInfo.trgWidth =
_this.options.thumbnailWidth;Ð                                }Ð
                                if (resizeInfo.trgHeight == null) {Ð
                                    resizeInfo.trgHeight =
_this.options.thumbnailHeight;Ð                                }Ð
                                canvas = document.createElement("canvas");Ð
                                ctx = canvas.getContext("2d");Ð
                                canvas.width = resizeInfo.trgWidth;Ð
```

```
                                canvas.height = resizeInfo.trgHeight;Ð
                                drawImageIOSFix(ctx, img, (_ref =
resizeInfo.srcX) != null ? _ref : 0, (_ref1 = resizeInfo.srcY) != null ?
_ref1 : 0, resizeInfo.srcWidth, resizeInfo.srcHeight, (_ref2 =
resizeInfo.trgX) != null ? _ref2 : 0, (_ref3 = resizeInfo.trgY) != null ?
_ref3 : 0, resizeInfo.trgWidth, resizeInfo.trgHeight);Ð
                                thumbnail = canvas.toDataURL("image/png");Ð
                                _this.emit("thumbnail", file, thumbnail);Ð
                                if (callback != null) {Ð
                                    return callback();Ð
                                }Ð                          };Ð
                            return img.src = fileReader.result;Ð
                        };Ð                   })(this);Ð
return fileReader.readAsDataURL(file);Ð               };Ð
Dropzone.prototype.processQueue = function() {Ð                    var i,
parallelUploads, processingLength, queuedFiles;Ð
parallelUploads = this.options.parallelUploads;Ð
processingLength = this.getUploadingFiles().length;Ð                  i =
processingLength;Ð                   if (processingLength >= parallelUploads)
{Ð                       return;Ð                   }Ð
queuedFiles = this.getQueuedFiles();Ð                    if (!
(queuedFiles.length > 0)) {Ð                      return;Ð
                    }Ð                   if (this.options.uploadMultiple) {Ð
                        return this.processFiles(queuedFiles.slice(0,
parallelUploads - processingLength));Ð                   } else {Ð
                        while (i < parallelUploads) {Ð
                            if (!queuedFiles.length) {Ð
                                return;Ð                          }Ð
                            this.processFile(queuedFiles.shift());Ð
                            i++;Ð                        }Ð                  }Ð
                };Ð               Dropzone.prototype.processFile =
function(file) {Ð                   return this.processFiles([file]);Ð
                };Ð               Dropzone.prototype.processFiles =
function(files) {Ð                   var file, _i, _len;Ð
for (_i = 0, _len = files.length; _i < _len; _i++) {Ð
file = files[_i];Ð                       file.processing = true;Ð
                        file.status = Dropzone.UPLOADING;Ð
                        this.emit("processing", file);Ð                  }Ð
                    if (this.options.uploadMultiple) {Ð
this.emit("processingmultiple", files);Ð                   }Ð
                    return this.uploadFiles(files);Ð              };Ð
                Dropzone.prototype._getFilesWithXhr = function(xhr) {Ð
                    var file, files;Ð                   return files =
(function() {Ð                         var _i, _len, _ref, _results;Ð
                        _ref = this.files;Ð                       _results =
[];Ð                      for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
                            file = _ref[_i];Ð                         if
(file.xhr === xhr) {Ð                              _results.push(file);Ð
                            }Ð                         }Ð
return _results;Ð                    }).call(this);Ð              };Ð
                Dropzone.prototype.cancelUpload = function(file) {Ð
                    var groupedFile, groupedFiles, _i, _j, _len, _len1, _ref;Ð
                    if (file.status === Dropzone.UPLOADING) {Ð
                        groupedFiles = this._getFilesWithXhr(file.xhr);Ð
                        for (_i = 0, _len = groupedFiles.length; _i < _len;
_i++) {Ð                            groupedFile = groupedFiles[_i];Ð
                            groupedFile.status = Dropzone.CANCELED;Ð
                        }Ð                       file.xhr.abort();Ð
                        for (_j = 0, _len1 = groupedFiles.length; _j < _len1;
_j++) {Ð
```

```
                                    groupedFile = groupedFiles[_j];Ð
                                this.emit("canceled", groupedFile);Ð
                            }Ð                          if
(this.options.uploadMultiple) {Ð
this.emit("canceledmultiple", groupedFiles);Ð                          }Ð
                        } else if ((_ref = file.status) === Dropzone.ADDED ||
_ref === Dropzone.QUEUED) {Ð                          file.status =
Dropzone.CANCELED;Ð                          this.emit("canceled", file);Ð
                            if (this.options.uploadMultiple) {Ð
                                this.emit("canceledmultiple", [file]);Ð
                            }Ð                    }Ð                    if
(this.options.autoProcessQueue) {Ð                          return
this.processQueue();Ð                    }Ð                    };Ð
Dropzone.prototype.uploadFile = function(file) {Ð                    return
this.uploadFiles([file]);Ð                    };Ð
Dropzone.prototype.uploadFiles = function(files) {Ð                    var
file, formData, handleError, headerName, headerValue, headers, input,
inputName, inputType, key, option, progressObj, response, updateProgress,
value, xhr, _i, _j, _k, _l, _len, _len1, _len2, _len3, _len4, _m, _ref,
_ref1, _ref2, _ref3, _ref4;Ð                    xhr = new XMLHttpRequest();Ð
                        for (_i = 0, _len = files.length; _i < _len; _i++) {Ð
                            file = files[_i];Ð                          file.xhr =
xhr;Ð                            }Ð                    xhr.open(this.options.method,
this.options.url, true);Ð                    xhr.withCredentials = !!
this.options.withCredentials;Ð                    response = null;Ð
                        handleError = (function(_this) {Ð
return function() {Ð                    var _j, _len1, _results;Ð
                                _results = [];Ð                    for (_j
= 0, _len1 = files.length; _j < _len1; _j++) {Ð
file = files[_j];Ð
_results.push(_this._errorProcessing(files, response ||
_this.options.dictResponseError.replace("{{statusCode}}", xhr.status), xhr));Ð
                                }Ð                    return _results;Ð
                            };Ð                    })(this);Ð
updateProgress = (function(_this) {Ð                    return function(e)
{Ð                    var allFilesFinished, progress, _j, _k, _l,
_len1, _len2, _len3, _results;Ð                    if (e != null) {Ð
                                    progress = 100 * e.loaded / e.total;Ð
                                    for (_j = 0, _len1 = files.length; _j <
_len1; _j++) {Ð                    file = files[_j];Ð
                                        file.upload = {Ð
                                            progress: progress,Ð
                                            total: e.total,Ð
                                            bytesSent: e.loadedÐ
                                        };Ð                    }Ð
                                } else {Ð
allFilesFinished = true;Ð                    progress = 100;Ð
                                    for (_k = 0, _len2 = files.length; _k <
_len2; _k++) {Ð                    file = files[_k];Ð
                                        if (!(file.upload.progress === 100 &&
file.upload.bytesSent === file.upload.total)) {Ð
                                            allFilesFinished = false;Ð
                                        }Ð
file.upload.progress = progress;Ð
file.upload.bytesSent = file.upload.total;Ð                    }Ð
                                    if (allFilesFinished) {Ð
                                        return;Ð                    }Ð
                                }Ð                    _results = [];Ð
                                for (_l = 0, _len3 = files.length; _l < _len3; _l+
+) {Ð
```

```
                                    file = files[_l];Ð
                                _results.push(_this.emit("uploadprogress",
file, progress, file.upload.bytesSent));Ð                          }Ð
                            return _results;Ð                      };Ð
                        })(this);Ð                  xhr.onload =
(function(_this) {Ð                       return function(e) {Ð
                            var _ref;Ð                            if
(files[0].status === Dropzone.CANCELED) {Ð
return;Ð                            }Ð                          if
(xhr.readyState !== 4) {Ð                                return;Ð
                            }Ð                           response =
xhr.responseText;Ð                          if
(xhr.getResponseHeader("content-type") && ~xhr.getResponseHeader("content-
type").indexOf("application/json")) {Ð                              try {Ð
                                    response = JSON.parse(response);Ð
                                } catch (_error) {Ð
                                    e = _error;Ð
                                    response = "Invalid JSON response from
server.";Ð                                }Ð                          }Ð
                            updateProgress();Ð                          if (!
((200 <= (_ref = xhr.status) && _ref < 300))) {Ð
                                return handleError();Ð
                            } else {Ð                              return
_this._finished(files, response, e);Ð                          }Ð
                        };Ð                  })(this);Ð
xhr.onerror = (function(_this) {Ð                       return function() {Ð
                            if (files[0].status === Dropzone.CANCELED) {Ð
                                return;Ð                          }Ð
                            return handleError();Ð                      };Ð
                        })(this);Ð                  progressObj = (_ref =
xhr.upload) != null ? _ref : xhr;Ð                  progressObj.onprogress =
updateProgress;Ð                    headers = {Ð
"Accept": "application/json",Ð                      "Cache-Control": "no-
cache",Ð                        "X-Requested-With": "XMLHttpRequest"Ð
                        };Ð                  if (this.options.headers) {Ð
                            extend(headers, this.options.headers);Ð
                        }Ð                  for (headerName in headers) {Ð
                            headerValue = headers[headerName];Ð
                            xhr.setRequestHeader(headerName, headerValue);Ð
                        }Ð                  formData = new FormData();Ð
                        if (this.options.params) {Ð                     _ref1 =
this.options.params;Ð                       for (key in _ref1) {Ð
                            value = _ref1[key];Ð
formData.append(key, value);Ð                       }Ð                  }Ð
                        for (_j = 0, _len1 = files.length; _j < _len1; _j++) {Ð
                            file = files[_j];Ð
this.emit("sending", file, xhr, formData);Ð                   }Ð
                        if (this.options.uploadMultiple) {Ð
this.emit("sendingmultiple", files, xhr, formData);Ð                  }Ð
                        if (this.element.tagName === "FORM") {Ð
                            _ref2 = this.element.querySelectorAll("input,
textarea, select, button");Ð                      for (_k = 0, _len2 =
_ref2.length; _k < _len2; _k++) {Ð                          input =
_ref2[_k];Ð                           inputName = input.getAttribute("name");Ð
                            inputType = input.getAttribute("type");Ð
                            if (input.tagName === "SELECT" &&
input.hasAttribute("multiple")) {Ð                                _ref3 =
input.options;Ð                             for (_l = 0, _len3 =
_ref3.length; _l < _len3; _l++) {Ð                                  option =
_ref3[_l];Ð
```

```
                                                if (option.selected) {Ð
                                            formData.append(inputName,
option.value);Ð                                         }Ð
                                  }Ð                              } else if (!
inputType || ((_ref4 = inputType.toLowerCase()) !== "checkbox" && _ref4 !==
"radio") || input.checked) {Ð
formData.append(inputName, input.value);Ð                                 }Ð
                          }Ð                    }Ð                     for (_m =
0, _len4 = files.length; _m < _len4; _m++) {Ð                             file =
files[_m];Ð                        formData.append("" + this.options.paramName
+ (this.options.uploadMultiple ? "[]" : ""), file, file.name);Ð
                      }Ð                     return xhr.send(formData);Ð
                  };Ð                Dropzone.prototype._finished =
function(files, responseText, e) {Ð                     var file, _i, _len;Ð
                      for (_i = 0, _len = files.length; _i < _len; _i++) {Ð
                          file = files[_i];Ð                        file.status
= Dropzone.SUCCESS;Ð                          this.emit("success", file,
responseText, e);Ð                        this.emit("complete", file);Ð
                      }Ð                      if (this.options.uploadMultiple) {Ð
                          this.emit("successmultiple", files, responseText, e);Ð
                          this.emit("completemultiple", files);Ð
                      }Ð                      if (this.options.autoProcessQueue) {Ð
                          return this.processQueue();Ð                    }Ð
                  };Ð                Dropzone.prototype._errorProcessing =
function(files, message, xhr) {Ð                     var file, _i, _len;Ð
                      for (_i = 0, _len = files.length; _i < _len; _i++) {Ð
                          file = files[_i];Ð                        file.status
= Dropzone.ERROR;Ð                        this.emit("error", file, message,
xhr);Ð                        this.emit("complete", file);Ð                    }Ð
                      if (this.options.uploadMultiple) {Ð
this.emit("errormultiple", files, message, xhr);Ð
this.emit("completemultiple", files);Ð                    }Ð
if (this.options.autoProcessQueue) {Ð                        return
this.processQueue();Ð                    }Ð                    };Ð
return Dropzone;Ð            })(Em);Ð            Dropzone.version = "3.8.7";Ð
            Dropzone.options = {};Ð            Dropzone.optionsForElement =
function(element) {Ð                if (element.getAttribute("id")) {Ð
                      return
Dropzone.options[camelize(element.getAttribute("id"))];Ð                } else
{Ð                    return void 0;Ð                }Ð            };Ð
Dropzone.instances = [];Ð            Dropzone.forElement = function(element) {Ð
                if (typeof element === "string") {Ð                    element
= document.querySelectorSelector(element);Ð                }Ð                if
((element != null ? element.dropzone : void 0) == null) {Ð
throw new Error("No Dropzone found for given element. This is probably
because you're trying to access it before Dropzone had the time to
initialize. Use the `init` option to setup any additional observers on your
Dropzone.");Ð                }Ð                return element.dropzone;Ð
            };Ð            Dropzone.autoDiscover = true;Ð
Dropzone.discover = function() {Ð                var checkElements, dropzone,
dropzones, _i, _len, _results;Ð                if (document.querySelectorAll) {Ð
                      dropzones = document.querySelectorAll(".dropzone");Ð
                  } else {Ð                    dropzones = [];Ð
                      checkElements = function(elements) {Ð
                          var el, _i, _len, _results;Ð
_results = [];Ð                          for (_i = 0, _len = elements.length; _i
< _len; _i++) {Ð                          el = elements[_i];Ð
                              if (/(^| )dropzone($| )/.test(el.className)) {Ð
                                  _results.push(dropzones.push(el));Ð
                              } else {Ð
```

```
_results.push(void 0);Ð                          }Ð                      }Ð
                        return _results;Ð                  };Ð
                    checkElements(document.getElementsByTagName("div"));Ð
                    checkElements(document.getElementsByTagName("form"));Ð
                }Ð               _results = [];Ð               for (_i = 0,
_len = dropzones.length; _i < _len; _i++) {Ð                  dropzone =
dropzones[_i];Ð                   if (Dropzone.optionsForElement(dropzone) !
== false) {Ð                       _results.push(new Dropzone(dropzone));Ð
                    } else {Ð                      _results.push(void 0);Ð
                    }Ð               }Ð               return _results;Ð
            };Ð           Dropzone.blacklistedBrowsers = [/
opera.*Macintosh.*version\/12/i];Ð           Dropzone.isBrowserSupported =
function() {Ð               var capableBrowser, regex, _i, _len, _ref;Ð
                capableBrowser = true;Ð               if (window.File &&
window.FileReader && window.FileList && window.Blob && window.FormData &&
document.querySelector) {Ð                   if (!("classList" in
document.createElement("a"))) {Ð                       capableBrowser = false;Ð
                    } else {Ð                      _ref =
Dropzone.blacklistedBrowsers;Ð                       for (_i = 0, _len =
_ref.length; _i < _len; _i++) {Ð                           regex = _ref[_i];Ð
                            if (regex.test(navigator.userAgent)) {Ð
                                capableBrowser = false;Ð
                                continue;Ð                              }Ð
                        }Ð                   }Ð               } else {Ð
                    capableBrowser = false;Ð               }Ð
return capableBrowser;Ð           };Ð           without = function(list,
rejectedItem) {Ð               var item, _i, _len, _results;Ð
_results = [];Ð               for (_i = 0, _len = list.length; _i < _len; _i+
+) {Ð                    item = list[_i];Ð                    if (item !==
rejectedItem) {Ð                        _results.push(item);Ð
                    }Ð               }Ð               return _results;Ð
            };Ð           camelize = function(str) {Ð               return
str.replace(/[\-_](\w)/g, function(match) {Ð                   return
match.charAt(1).toUpperCase();Ð               });Ð           };Ð
Dropzone.createElement = function(string) {Ð               var div;Ð
                div = document.createElement("div");Ð
div.innerHTML = string;Ð               return div.childNodes[0];Ð           };Ð
            Dropzone.elementInside = function(element, container) {Ð
                if (element === container) {Ð                   return true;Ð
                }Ð               while (element = element.parentNode) {Ð
                    if (element === container) {Ð
return true;Ð                    }Ð               }Ð               return
false;Ð           };Ð           Dropzone.getElement = function(el, name) {Ð
                var element;Ð               if (typeof el === "string") {Ð
                    element = document.querySelector(el);Ð               }
else if (el.nodeType != null) {Ð                   element = el;Ð
                }Ð               if (element == null) {Ð
throw new Error("Invalid `" + name + "` option provided. Please provide a CSS
selector or a plain HTML element.");Ð               }Ð               return
element;Ð           };Ð           Dropzone.getElements = function(els, name) {Ð
                var e, el, elements, _i, _j, _len, _len1, _ref;Ð
                if (els instanceof Array) {Ð                   elements = [];Ð
                    try {Ð                       for (_i = 0, _len =
els.length; _i < _len; _i++) {Ð                           el = els[_i];Ð
                            elements.push(this.getElement(el, name));Ð
                        }Ð                   } catch (_error) {Ð
                        e = _error;Ð                       elements = null;Ð
                    }Ð               } else if (typeof els === "string") {Ð
                    elements = [];Ð
```

```
                                                    _ref =
document.querySelectorAll(els);Ð                  for (_j = 0, _len1 =
_ref.length; _j < _len1; _j++) {Ð                     el = _ref[_j];Ð
                        elements.push(el);Ð                  }Ð
                } else if (els.nodeType != null) {Ð
elements = [els];Ð                }Ð                if (!((elements != null) &&
elements.length)) {Ð                    throw new Error("Invalid `" + name +
"` option provided. Please provide a CSS selector, a plain HTML element or a
list of those.");Ð                }Ð                return elements;Ð
            };Ð           Dropzone.confirm = function(question, accepted,
rejected) {Ð                if (window.confirm(question)) {Ð
return accepted();Ð                } else if (rejected != null) {Ð
                    return rejected();Ð                }Ð           };Ð
            Dropzone.isValidFile = function(file, acceptedFiles) {Ð
                var baseMimeType, mimeType, validType, _i, _len;Ð
                if (!acceptedFiles) {Ð                    return true;Ð
                }Ð                acceptedFiles = acceptedFiles.split(",");Ð
                mimeType = file.type;Ð                baseMimeType =
mimeType.replace(/\/.*$/, "");Ð                for (_i = 0, _len =
acceptedFiles.length; _i < _len; _i++) {Ð                    validType =
acceptedFiles[_i];Ð                    validType = validType.trim();Ð
                    if (validType.charAt(0) === ".") {Ð
if (file.name.toLowerCase().indexOf(validType.toLowerCase(), file.name.length
- validType.length) !== -1) {Ð                        return true;Ð
                        }Ð                    } else if (/\/
\*$/.test(validType)) {Ð                      if (baseMimeType ===
validType.replace(/\/.*$/, "")) {Ð                            return true;Ð
                        }Ð                    } else {Ð
if (mimeType === validType) {Ð                        return true;Ð
                        }Ð                    }Ð                }Ð
                return false;Ð           };Ð           if (typeof jQuery !==
"undefined" && jQuery != null) {Ð                jQuery.fn.dropzone =
function(options) {Ð                    return this.each(function() {Ð
                        return new Dropzone(this, options);Ð
                    });Ð                };Ð           }Ð           if (typeof
module != "undefined" && module != null) {Ð                module.exports =
Dropzone;Ð           } else {Ð                window.Dropzone = Dropzone;Ð
            }Ð           Dropzone.ADDED = "added";Ð           Dropzone.QUEUED
= "queued";Ð           Dropzone.ACCEPTED = Dropzone.QUEUED;Ð
Dropzone.UPLOADING = "uploading";Ð           Dropzone.PROCESSING =
Dropzone.UPLOADING;Ð           Dropzone.CANCELED = "canceled";Ð
Dropzone.ERROR = "error";Ð           Dropzone.SUCCESS = "success";Ð
            /*Ð            Bugfix for iOS 6 and 7Ð            Source: http://
stackoverflow.com/questions/11929099/html5-canvas-drawimage-ratio-bug-iosÐ
             based on the work of https://github.com/stomita/ios-imagefile-
megapixelÐ            */Ð           detectVerticalSquash = function(img) {Ð
                var alpha, canvas, ctx, data, ey, ih, iw, py, ratio, sy;Ð
                iw = img.naturalWidth;Ð                ih = img.naturalHeight;Ð
                canvas = document.createElement("canvas");Ð
canvas.width = 1;Ð                canvas.height = ih;Ð                ctx =
canvas.getContext("2d");Ð                ctx.drawImage(img, 0, 0);Ð
                data = ctx.getImageData(0, 0, 1, ih).data;Ð                sy
= 0;Ð                ey = ih;Ð                py = ih;Ð                while (py
> sy) {Ð                    alpha = data[(py - 1) * 4 + 3];Ð
if (alpha === 0) {Ð                        ey = py;Ð                    } else {Ð
                        sy = py;Ð                    }Ð                    py =
(ey + sy) >> 1;Ð                }Ð                ratio = py / ih;Ð
                if (ratio === 0) {Ð                    return 1;Ð
                } else {Ð                    return ratio;Ð                }Ð
            };Ð
```

```
              Ð           drawImageIOSFix = function(ctx, img, sx, sy, sw,
sh, dx, dy, dw, dh) {Ð               var vertSquashRatio;Ð
vertSquashRatio = detectVerticalSquash(img);Ð               return
ctx.drawImage(img, sx, sy, sw, sh, dx, dy, dw, dh / vertSquashRatio);Ð
            };Ð           /*Ð            * contentloaded.jsÐ            *Ð
             * Author: Diego Perini (diego.perini at gmail.com)Ð            *
Summary: cross-browser wrapper for DOMContentLoadedÐ            * Updated:
20101020Ð            * License: MITÐ            * Version: 1.2Ð            *Ð
             * URL:Ð            * http://javascript.nwbox.com/ContentLoaded/Ð
             * http://javascript.nwbox.com/ContentLoaded/MIT-LICENSEÐ
             */Ð           contentLoaded = function(win, fn) {Ð
var add, doc, done, init, poll, pre, rem, root, top;Ð               done =
false;Ð               top = true;Ð               doc = win.document;Ð
                root = doc.documentElement;Ð               add =
(doc.addEventListener ? "addEventListener" : "attachEvent");Ð
rem = (doc.addEventListener ? "removeEventListener" : "detachEvent");Ð
                pre = (doc.addEventListener ? "" : "on");Ð               init
= function(e) {Ð                    if (e.type === "readystatechange" &&
doc.readyState !== "complete") {Ð                        return;Ð
                    }Ð                    (e.type === "load" ? win : doc)[rem]
(pre + e.type, init, false);Ð                    if (!done && (done = true)) {Ð
                        return fn.call(win, e.type || e);Ð                    }Ð
                };Ð               poll = function() {Ð               var
e;Ð                    try {Ð                        root.doScroll("left");Ð
                    } catch (_error) {Ð                        e = _error;Ð
                        setTimeout(poll, 50);Ð                        return;Ð
                    }Ð                    return init("poll");Ð
                };Ð               if (doc.readyState !== "complete") {Ð
                    if (doc.createEventObject && root.doScroll) {Ð
                        try {Ð                        top = !
win.frameElement;Ð                    } catch (_error) {}Ð
                        if (top) {Ð                        poll();Ð
                        }Ð                    }Ð                    doc[add]
(pre + "DOMContentLoaded", init, false);Ð                    doc[add](pre +
"readystatechange", init, false);Ð                    return win[add](pre +
"load", init, false);Ð               }Ð           };Ð
Dropzone._autoDiscoverFunction = function() {Ð               if
(Dropzone.autoDiscover) {Ð                    return Dropzone.discover();Ð
                }Ð           };Ð           contentLoaded(window,
Dropzone._autoDiscoverFunction);Ð       }).call(this);Ð   });Ð   if (typeof
exports == "object") {Ð       module.exports = require("dropzone");Ð   } else
if (typeof define == "function" && define.amd) {Ð       define([], function()
{ return require("dropzone"); });Ð   } else {Ð       this["Dropzone"] =
require("dropzone");Ð   }Ð})()Ð
```

public\assets\js\plugins\easypiechart\easypiechart.js

```
/**!Ð* easyPieChartÐ* Lightweight plugin to render simple, animated and
retina optimized pie chartsÐ*Ð* @licenseÐ* @author Robert Fleischmann
<rendro87@gmail.com> (http://robert-fleischmann.de)Ð* @version 2.1.5Ð**/Ð
(function(root, factory) {Ð   if(typeof exports === 'object') {Ð
module.exports = factory();Ð   }Ð   else if(typeof define === 'function' &&
define.amd) {Ð       define([], factory);Ð   }Ð   else {Ð
root['EasyPieChart'] = factory();Ð   }Ð}(this, function() {Ð   /**Ð    *
Renderer to render the chart on a canvas objectÐ    * @param {DOMElement}
el      DOM element to host the canvas (root of the plugin)Ð    * @param
{object}     options options object of the pluginÐ    */Ð   var
CanvasRenderer = function(el, options) {Ð       var cachedBackground;Ð
var canvas = document.createElement('canvas');Ð       el.appendChild(canvas);Ð
        if (typeof(G_vmlCanvasManager) !== 'undefined') {Ð
G_vmlCanvasManager.initElement(canvas);Ð       }Ð       var ctx =
canvas.getContext('2d');Ð       canvas.width = canvas.height = options.size;Ð
        // canvas on retina devicesÐ       var scaleBy = 1;Ð       if
(window.devicePixelRatio > 1) {Ð           scaleBy = window.devicePixelRatio;Ð
            canvas.style.width = canvas.style.height = [options.size,
'px'].join('');Ð           canvas.width = canvas.height = options.size *
scaleBy;Ð           ctx.scale(scaleBy, scaleBy);Ð       }Ð       // move 0,0
coordinates to the centerÐ       ctx.translate(options.size / 2,
options.size / 2);Ð       // rotate canvas -90degÐ       ctx.rotate((-1 / 2 +
options.rotate / 180) * Math.PI);Ð       var radius = (options.size -
options.lineWidth) / 2;Ð       if (options.scaleColor && options.scaleLength)
{Ð           radius -= options.scaleLength + 2; // 2 is the distance between
scale and barÐ       }Ð       // IE polyfill for DateÐ       Date.now =
Date.now || function() {Ð           return +(new Date());Ð       };Ð       /**Ð
         * Draw a circle around the center of the canvasÐ        * @param
{strong} color     Valid CSS color stringÐ        * @param {number} lineWidth
Width of the line in pxÐ        * @param {number} percent   Percentage to
draw (float between -1 and 1)Ð        */Ð       var drawCircle =
function(color, lineWidth, percent) {Ð           percent =
Math.min(Math.max(-1, percent || 0), 1);Ð           var isNegative = percent
<= 0 ? true : false;Ð           ctx.beginPath();Ð           ctx.arc(0, 0,
radius, 0, Math.PI * 2 * percent, isNegative);Ð           ctx.strokeStyle =
color;Ð           ctx.lineWidth = lineWidth;Ð           ctx.stroke();Ð
        };Ð       /**Ð        * Draw the scale of the chartÐ        */Ð
var drawScale = function() {Ð           var offset;Ð           var length;Ð
            ctx.lineWidth = 1;Ð           ctx.fillStyle = options.scaleColor;Ð
            ctx.save();Ð           for (var i = 24; i > 0; --i) {Ð
                if (i % 6 === 0) {Ð                    length =
options.scaleLength;Ð                    offset = 0;Ð               } else {Ð
                    length = options.scaleLength * 0.6;Ð
offset = options.scaleLength - length;Ð               }Ð
ctx.fillRect(-options.size/2 + offset, 0, length, 1);Ð
ctx.rotate(Math.PI / 12);Ð           }Ð           ctx.restore();Ð       };Ð
        /**Ð        * Request animation frame wrapper with polyfillÐ        *
@return {function} Request animation frame method or timeout fallbackÐ
*/Ð       var reqAnimationFrame = (function() {Ð           return
window.requestAnimationFrame ||Ð
window.webkitRequestAnimationFrame ||Ð
window.mozRequestAnimationFrame ||Ð               function(callback) {Ð
                    window.setTimeout(callback, 1000 / 60);Ð               };Ð
        }());Ð       /**Ð        * Draw the background of the plugin
including the scale and the trackÐ        */Ð       var drawBackground =
function() {Ð           if(options.scaleColor) drawScale();Ð
if(options.trackColor) drawCircle(options.trackColor, options.lineWidth, 1);Ð
        };Ð       /**Ð        * Canvas accessorÐ        */Ð
this.getCanvas = function() {Ð
```

```
                                        return canvas;Ð       };Ð       /**Ð
         * Canvas 2D context 'ctx' accessorÐ        */Ð       this.getCtx =
function() {Ð           return ctx;Ð       };Ð       /**Ð        * Clear the
complete canvasÐ        */Ð       this.clear = function() {Ð
ctx.clearRect(options.size / -2, options.size / -2, options.size,
options.size);Ð       };Ð       /**Ð        * Draw the complete chartÐ
* @param {number} percent Percent shown by the chart between -100 and 100Ð
         */Ð       this.draw = function(percent) {Ð           // do we need
to render a backgroundÐ           if (!!options.scaleColor || !!
options.trackColor) {Ð               // getImageData and putImageData are
supportedÐ               if (ctx.getImageData && ctx.putImageData) {Ð
                    if (!cachedBackground) {Ð
drawBackground();Ð                        cachedBackground =
ctx.getImageData(0, 0, options.size * scaleBy, options.size * scaleBy);Ð
                    } else {Ð
ctx.putImageData(cachedBackground, 0, 0);Ð                    }Ð
                } else {Ð                    this.clear();Ð
drawBackground();Ð                }Ð           } else {Ð
this.clear();Ð           }Ð           ctx.lineCap = options.lineCap;Ð
            // if barcolor is a function execute it and pass the percent as a
valueÐ           var color;Ð           if (typeof(options.barColor) ===
'function') {Ð               color = options.barColor(percent);Ð           }
else {Ð               color = options.barColor;Ð           }Ð           //
draw barÐ           drawCircle(color, options.lineWidth, percent / 100);Ð
        }.bind(this);Ð       /**Ð        * Animate from some percent to some
other percentageÐ        * @param {number} from Starting percentageÐ        *
@param {number} to   Final percentageÐ        */Ð       this.animate =
function(from, to) {Ð           var startTime = Date.now();Ð
options.onStart(from, to);Ð           var animation = function() {Ð
                var process = Math.min(Date.now() - startTime,
options.animate.duration);Ð               var currentValue =
options.easing(this, process, from, to - from, options.animate.duration);Ð
                this.draw(currentValue);Ð               options.onStep(from,
to, currentValue);Ð               if (process >= options.animate.duration) {Ð
                    options.onStop(from, to);Ð               } else {Ð
                    reqAnimationFrame(animation);Ð               }Ð
            }.bind(this);Ð           reqAnimationFrame(animation);Ð
        }.bind(this);Ð   };Ð   var EasyPieChart = function(el, opts) {Ð
var defaultOptions = {Ð           barColor: '#ef1e25',Ð           trackColor:
'#f9f9f9',Ð           scaleColor: '#dfe0e0',Ð           scaleLength: 5,Ð
            lineCap: 'round',Ð           lineWidth: 3,Ð           size: 110,Ð
            rotate: 0,Ð           animate: {Ð               duration: 1000,Ð
                enabled: trueÐ           },Ð           easing: function (x,
t, b, c, d) { // more can be found here: http://gsgd.co.uk/sandbox/jquery/
easing/Ð               t = t / (d/2);Ð               if (t < 1) {Ð
                    return c / 2 * t * t + b;Ð               }Ð
return -c/2 * ((--t)*(t-2) - 1) + b;Ð           },Ð           onStart:
function(from, to) {Ð               return;Ð           },Ð           onStep:
function(from, to, currentValue) {Ð               return;Ð           },Ð
            onStop: function(from, to) {Ð               return;Ð           }Ð
        };Ð       // detect present rendererÐ       if
(typeof(CanvasRenderer) !== 'undefined') {Ð           defaultOptions.renderer
= CanvasRenderer;Ð       } else if (typeof(SVGRenderer) !== 'undefined') {Ð
            defaultOptions.renderer = SVGRenderer;Ð       } else {Ð
throw new Error('Please load either the SVG- or the CanvasRenderer');Ð       }Ð
        var options = {};Ð       var currentValue = 0;Ð       /**Ð        *
Initialize the plugin by creating the options object and initialize renderingÐ
         */Ð       var init = function() {Ð           this.el = el;Ð
            this.options = options;Ð           // merge user options into
default optionsÐ
```

```
                            for (var i in defaultOptions) {Ð                if
(defaultOptions.hasOwnProperty(i)) {Ð                    options[i] = opts &&
typeof(opts[i]) !== 'undefined' ? opts[i] : defaultOptions[i];Ð
                    if (typeof(options[i]) === 'function') {Ð
                        options[i] = options[i].bind(this);Ð
                    }Ð               }Ð           }Ð           // check for
jQuery easingÐ           if (typeof(options.easing) === 'string' &&
typeof(jQuery) !== 'undefined' &&
jQuery.isFunction(jQuery.easing[options.easing])) {Ð
options.easing = jQuery.easing[options.easing];Ð           } else {Ð
                options.easing = defaultOptions.easing;Ð           }Ð
            // process earlier animate option to avoid bc breaksÐ
if (typeof(options.animate) === 'number') {Ð               options.animate = {Ð
                    duration: options.animate,Ð                    enabled:
trueÐ                };Ð           }Ð           if (typeof(options.animate)
=== 'boolean' && !options.animate) {Ð               options.animate = {Ð
                    duration: 1000,Ð                   enabled:
options.animateÐ               };Ð           }Ð           // create rendererÐ
            this.renderer = new options.renderer(el, options);Ð           //
initial drawÐ           this.renderer.draw(currentValue);Ð           //
initial updateÐ           if (el.dataset && el.dataset.percent) {Ð
                this.update(parseFloat(el.dataset.percent));Ð           }
else if (el.getAttribute && el.getAttribute('data-percent')) {Ð
this.update(parseFloat(el.getAttribute('data-percent')));Ð           }Ð
        }.bind(this);Ð       /**Ð        * Update the value of the chartÐ
         * @param  {number} newValue Number between 0 and 100Ð        *
@return {object}          Instance of the plugin for method chainingÐ
*/Ð       this.update = function(newValue) {Ð           newValue =
parseFloat(newValue);Ð           if (options.animate.enabled) {Ð
                this.renderer.animate(currentValue, newValue);Ð           }
else {Ð               this.renderer.draw(newValue);Ð           }Ð
currentValue = newValue;Ð           return this;Ð       }.bind(this);Ð       /
**Ð        * Disable animationÐ        * @return {object} Instance of the
plugin for method chainingÐ        */Ð       this.disableAnimation =
function() {Ð           options.animate.enabled = false;Ð           return
this;Ð       };Ð       /**Ð        * Enable animationÐ        * @return
{object} Instance of the plugin for method chainingÐ        */Ð
this.enableAnimation = function() {Ð           options.animate.enabled = true;Ð
            return this;Ð       };Ð       init();Ð   };Ð   return
EasyPieChart;Ð}));Ð
```

public\assets\js\plugins\easypiechart\jquery.easypiechart.js

```
/**!Ð* easyPieChartÐ* Lightweight plugin to render simple, animated and
retina optimized pie chartsÐ*Ð* @licenseÐ* @author Robert Fleischmann
<rendro87@gmail.com> (http://robert-fleischmann.de)Ð* @version 2.1.5Ð**/Ð
(function(root, factory) {Ð   if(typeof exports === 'object') {Ð
module.exports = factory(require('jquery'));Ð   }Ð   else if(typeof define
=== 'function' && define.amd) {Ð       define(['jquery'], factory);Ð   }Ð
else {Ð       factory(root.jQuery);Ð   }Ð}(this, function($) {Ð   /**Ð    *
Renderer to render the chart on a canvas objectÐ    * @param {DOMElement}
el      DOM element to host the canvas (root of the plugin)Ð    * @param
{object}     options options object of the pluginÐ    */Ð   var
CanvasRenderer = function(el, options) {Ð       var cachedBackground;Ð
var canvas = document.createElement('canvas');Ð       el.appendChild(canvas);Ð
        if (typeof(G_vmlCanvasManager) !== 'undefined') {Ð
G_vmlCanvasManager.initElement(canvas);Ð       }Ð       var ctx =
canvas.getContext('2d');Ð       canvas.width = canvas.height = options.size;Ð
        // canvas on retina devicesÐ       var scaleBy = 1;Ð       if
(window.devicePixelRatio > 1) {Ð           scaleBy = window.devicePixelRatio;Ð
            canvas.style.width = canvas.style.height = [options.size,
'px'].join('');Ð           canvas.width = canvas.height = options.size *
scaleBy;Ð           ctx.scale(scaleBy, scaleBy);Ð       }Ð       // move 0,0
coordinates to the centerÐ       ctx.translate(options.size / 2,
options.size / 2);Ð       // rotate canvas -90degÐ       ctx.rotate((-1 / 2 +
options.rotate / 180) * Math.PI);Ð       var radius = (options.size -
options.lineWidth) / 2;Ð       if (options.scaleColor && options.scaleLength)
{Ð           radius -= options.scaleLength + 2; // 2 is the distance between
scale and barÐ       }Ð       // IE polyfill for DateÐ       Date.now =
Date.now || function() {Ð           return +(new Date());Ð       };Ð       /**Ð
         * Draw a circle around the center of the canvasÐ        * @param
{strong} color     Valid CSS color stringÐ        * @param {number} lineWidth
Width of the line in pxÐ        * @param {number} percent   Percentage to
draw (float between -1 and 1)Ð        */Ð       var drawCircle =
function(color, lineWidth, percent) {Ð           percent =
Math.min(Math.max(-1, percent || 0), 1);Ð           var isNegative = percent
<= 0 ? true : false;Ð           ctx.beginPath();Ð           ctx.arc(0, 0,
radius, 0, Math.PI * 2 * percent, isNegative);Ð           ctx.strokeStyle =
color;Ð           ctx.lineWidth = lineWidth;Ð           ctx.stroke();Ð
        };Ð       /**Ð        * Draw the scale of the chartÐ        */Ð
var drawScale = function() {Ð           var offset;Ð           var length;Ð
            ctx.lineWidth = 1;Ð           ctx.fillStyle = options.scaleColor;Ð
            ctx.save();Ð           for (var i = 24; i > 0; --i) {Ð
                if (i % 6 === 0) {Ð                   length =
options.scaleLength;Ð                   offset = 0;Ð               } else {Ð
                    length = options.scaleLength * 0.6;Ð
offset = options.scaleLength - length;Ð               }Ð
ctx.fillRect(-options.size/2 + offset, 0, length, 1);Ð
ctx.rotate(Math.PI / 12);Ð           }Ð           ctx.restore();Ð       };Ð
        /**Ð        * Request animation frame wrapper with polyfillÐ        *
@return {function} Request animation frame method or timeout fallbackÐ
*/Ð       var reqAnimationFrame = (function() {Ð           return
window.requestAnimationFrame ||Ð
window.webkitRequestAnimationFrame ||Ð
window.mozRequestAnimationFrame ||Ð               function(callback) {Ð
                    window.setTimeout(callback, 1000 / 60);Ð               };Ð
        }());Ð       /**Ð        * Draw the background of the plugin
including the scale and the trackÐ        */Ð       var drawBackground =
function() {Ð           if(options.scaleColor) drawScale();Ð
if(options.trackColor) drawCircle(options.trackColor, options.lineWidth, 1);Ð
        };Ð       /**Ð        * Canvas accessorÐ        */Ð
this.getCanvas = function() {Ð
```

```
                                        return canvas;Ð       };Ð       /**Ð
         * Canvas 2D context 'ctx' accessorÐ        */Ð       this.getCtx =
function() {Ð           return ctx;Ð       };Ð       /**Ð        * Clear the
complete canvasÐ        */Ð       this.clear = function() {Ð
ctx.clearRect(options.size / -2, options.size / -2, options.size,
options.size);Ð       };Ð       /**Ð        * Draw the complete chartÐ
* @param {number} percent Percent shown by the chart between -100 and 100Ð
         */Ð       this.draw = function(percent) {Ð           // do we need
to render a backgroundÐ           if (!!options.scaleColor || !!
options.trackColor) {Ð               // getImageData and putImageData are
supportedÐ               if (ctx.getImageData && ctx.putImageData) {Ð
                    if (!cachedBackground) {Ð
drawBackground();Ð                        cachedBackground =
ctx.getImageData(0, 0, options.size * scaleBy, options.size * scaleBy);Ð
                    } else {Ð
ctx.putImageData(cachedBackground, 0, 0);Ð                    }Ð
                } else {Ð                    this.clear();Ð
drawBackground();Ð                }Ð           } else {Ð
this.clear();Ð           }Ð           ctx.lineCap = options.lineCap;Ð
            // if barcolor is a function execute it and pass the percent as a
valueÐ           var color;Ð           if (typeof(options.barColor) ===
'function') {Ð               color = options.barColor(percent);Ð           }
else {Ð               color = options.barColor;Ð           }Ð           //
draw barÐ           drawCircle(color, options.lineWidth, percent / 100);Ð
        }.bind(this);Ð       /**Ð        * Animate from some percent to some
other percentageÐ        * @param {number} from Starting percentageÐ        *
@param {number} to   Final percentageÐ        */Ð       this.animate =
function(from, to) {Ð           var startTime = Date.now();Ð
options.onStart(from, to);Ð           var animation = function() {Ð
                var process = Math.min(Date.now() - startTime,
options.animate.duration);Ð               var currentValue =
options.easing(this, process, from, to - from, options.animate.duration);Ð
                this.draw(currentValue);Ð               options.onStep(from,
to, currentValue);Ð               if (process >= options.animate.duration) {Ð
                    options.onStop(from, to);Ð               } else {Ð
                    reqAnimationFrame(animation);Ð               }Ð
            }.bind(this);Ð           reqAnimationFrame(animation);Ð
        }.bind(this);Ð   };Ð   var EasyPieChart = function(el, opts) {Ð
var defaultOptions = {Ð           barColor: '#ef1e25',Ð           trackColor:
'#f9f9f9',Ð           scaleColor: '#dfe0e0',Ð           scaleLength: 5,Ð
            lineCap: 'round',Ð           lineWidth: 3,Ð           size: 110,Ð
            rotate: 0,Ð           animate: {Ð               duration: 1000,Ð
                enabled: trueÐ           },Ð           easing: function (x,
t, b, c, d) { // more can be found here: http://gsgd.co.uk/sandbox/jquery/
easing/Ð               t = t / (d/2);Ð               if (t < 1) {Ð
                    return c / 2 * t * t + b;Ð               }Ð
return -c/2 * ((--t)*(t-2) - 1) + b;Ð           },Ð           onStart:
function(from, to) {Ð               return;Ð           },Ð           onStep:
function(from, to, currentValue) {Ð               return;Ð           },Ð
            onStop: function(from, to) {Ð               return;Ð           }Ð
        };Ð       // detect present rendererÐ       if
(typeof(CanvasRenderer) !== 'undefined') {Ð           defaultOptions.renderer
= CanvasRenderer;Ð       } else if (typeof(SVGRenderer) !== 'undefined') {Ð
            defaultOptions.renderer = SVGRenderer;Ð       } else {Ð
throw new Error('Please load either the SVG- or the CanvasRenderer');Ð       }Ð
        var options = {};Ð       var currentValue = 0;Ð       /**Ð        *
Initialize the plugin by creating the options object and initialize renderingÐ
         */Ð       var init = function() {Ð           this.el = el;Ð
            this.options = options;Ð           // merge user options into
default optionsÐ
```

```
                            for (var i in defaultOptions) {Ð                if
(defaultOptions.hasOwnProperty(i)) {Ð                   options[i] = opts &&
typeof(opts[i]) !== 'undefined' ? opts[i] : defaultOptions[i];Ð
                    if (typeof(options[i]) === 'function') {Ð
                        options[i] = options[i].bind(this);Ð
                    }Ð               }Ð           }Ð           // check for
jQuery easingÐ           if (typeof(options.easing) === 'string' &&
typeof(jQuery) !== 'undefined' &&
jQuery.isFunction(jQuery.easing[options.easing])) {Ð
options.easing = jQuery.easing[options.easing];Ð           } else {Ð
                options.easing = defaultOptions.easing;Ð           }Ð
            // process earlier animate option to avoid bc breaksÐ
if (typeof(options.animate) === 'number') {Ð               options.animate = {Ð
                    duration: options.animate,Ð                    enabled:
trueÐ                };Ð           }Ð           if (typeof(options.animate)
=== 'boolean' && !options.animate) {Ð               options.animate = {Ð
                    duration: 1000,Ð                   enabled:
options.animateÐ               };Ð           }Ð           // create rendererÐ
            this.renderer = new options.renderer(el, options);Ð           //
initial drawÐ           this.renderer.draw(currentValue);Ð           //
initial updateÐ           if (el.dataset && el.dataset.percent) {Ð
                this.update(parseFloat(el.dataset.percent));Ð           }
else if (el.getAttribute && el.getAttribute('data-percent')) {Ð
this.update(parseFloat(el.getAttribute('data-percent')));Ð           }Ð
        }.bind(this);Ð       /**Ð        * Update the value of the chartÐ
         * @param  {number} newValue Number between 0 and 100Ð        *
@return {object}          Instance of the plugin for method chainingÐ
*/Ð       this.update = function(newValue) {Ð           newValue =
parseFloat(newValue);Ð           if (options.animate.enabled) {Ð
                this.renderer.animate(currentValue, newValue);Ð           }
else {Ð               this.renderer.draw(newValue);Ð           }Ð
currentValue = newValue;Ð           return this;Ð       }.bind(this);Ð       /
**Ð        * Disable animationÐ        * @return {object} Instance of the
plugin for method chainingÐ        */Ð       this.disableAnimation =
function() {Ð           options.animate.enabled = false;Ð           return
this;Ð       };Ð       /**Ð        * Enable animationÐ        * @return
{object} Instance of the plugin for method chainingÐ        */Ð
this.enableAnimation = function() {Ð           options.animate.enabled = true;Ð
            return this;Ð       };Ð       init();Ð   };Ð   $.fn.easyPieChart
= function(options) {Ð       return this.each(function() {Ð           var
instanceOptions;Ð           if (!$.data(this, 'easyPieChart')) {Ð
                instanceOptions = $.extend({}, options, $(this).data());Ð
                $.data(this, 'easyPieChart', new EasyPieChart(this,
instanceOptions));Ð           }Ð       });Ð   };Ð       }));Ð
```

public\assets\js\plugins\flot\curvedLines.js

/* The MIT LicenseÐCopyright (c) 2011 by Michael Zinsmaier and nergal.devÐ Copyright (c) 2012 by Thomas RitouÐPermission is hereby granted, free of charge, to any person obtaining a copyÐof this software and associated documentation files (the "Software"), to dealÐin the Software without restriction, including without limitation the rightsÐto use, copy, modify, merge, publish, distribute, sublicense, and/or sellÐcopies of the Software, and to permit persons to whom the Software isÐfurnished to do so, subject to the following conditions:ÐThe above copyright notice and this permission notice shall be included inÐall copies or substantial portions of the Software.ÐTHE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS ORÐIMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,ÐFITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THEÐAUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHERÐLIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,ÐOUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS INÐTHE SOFTWARE.Ð*/Ð*Ð _____Ðwhat it is:Ð _____ÐcurvedLines is a plugin for flot, that tries to display lines in a smoother way.ÐThe plugin is based on nergal.dev's work https://code.google.com/p/flot/issues/detail?id=226Ðand further extended with a mode that forces the min/max points of the curves to be on theÐpoints. Both modes are achieved through adding of more data pointsÐ => 1) with large data sets you may get troubleÐ=> 2) if you want to display the points too, you have to plot them as 2nd data series over the linesÐ&& 3) consecutive x data points are not allowed to have the same valueÐThis is version 0.5 of curvedLines so it will probably not work in every case. However Ð the basic form of use descirbed next works (:ÐFeel free to further improve the codeÐ_____Ðhow to use it:Ð _____Ðvar d1 = [[5,5],[7,3], [9,12]];Ðvar options = { series: { curvedLines: { active: true }}};Ð $.plot($("#placeholder"), [{data = d1, lines: { show: true}, curvedLines: {apply: true}}], options);Ð _____Ðoptions:Ð _____Ðactive: bool true => plugin can be usedÐapply: bool true => series will be drawn as curved lineÐfit: bool true => forces the max,mins of the curve to be on the datapointsÐcurvePointFactor int defines how many "virtual" points are used per "real" data point toÐemulate the curvedLines (points total = real points * curvePointFactor)ÐfitPointDist: int defines the x axis distance of the additional two points that are usedÐto enforce the min max condition.Ð+ line options (since v0.5 curved lines use flots line implementation for drawingÐ=> line options like fill, show ... are supported out of the box)Ð*/Ð*Ð* v0.1 initial commitÐ* v0.15 negative values should work now (outcommented a negative -> 0 hook hope it does no harm)Ð* v0.2 added fill option (thanks to monemihir) and multi axis support (thanks to soewono effendi)Ð* v0.3 improved saddle handling and added basic handling of DatesÐ* v0.4 rewritten fill option (thomas ritou) mostly from original flot code (now fill between points rather than to graph bottom), corrected fill Opacity bugÐ* v0.5 rewritten instead of implementing a own draw function CurvedLines is now based on the processDatapoints flot hook (credits go to thomas ritou).Ð* ™ This change breakes existing code however CurvedLines are now just many tiny straight lines to flot and therefore all flot lines options (like gradient fill,Ð* ’ 6† F÷r’ &R æ÷r 7W ÷'FVB ÷WB öb F†R &÷•* v0.6 flot 0.8 compatibility and some bug fixesÐ*/Ðfunction($) {Ð var options = {Ð series : {Ð curvedLines : {Ð active : false,Ð apply: false,Ð fit : false,Ð curvePointFactor : 20,Ð fitPointDist : undefinedÐ }Ð }Ð

```
            };Ð   function init(plot) {Ð
plot.hooks.processOptions.push(processOptions);Ð       //if the plugin is
active register processDatapoints methodÐ       function processOptions(plot,
options) {Ð           if (options.series.curvedLines.active) {Ð
plot.hooks.processDatapoints.unshift(processDatapoints);Ð           }Ð       }Ð
        //only if the plugin is activeÐ       function
processDatapoints(plot, series, datapoints) {Ð           var nrPoints =
datapoints.points.length / datapoints.pointsize;Ð           var EPSILON =
0.5; //pretty large epsilon but saveÐ           if (series.curvedLines.apply
== true && series.originSeries === undefined && nrPoints > (1 + EPSILON)) {Ð
                if (series.lines.fill) {Ð                   var pointsTop =
calculateCurvePoints(datapoints, series.curvedLines, 1)Ð
                        ,pointsBottom = calculateCurvePoints(datapoints,
series.curvedLines, 2); //flot makes sure for us that we've got a second y
point if fill is true !Ð                   //Merge top and bottom curveÐ
                    datapoints.pointsize = 3;Ð
datapoints.points = [];Ð                   var j = 0;Ð                   var
k = 0;Ð                   var i = 0;Ð                   var ps = 2;Ð
                    while (i < pointsTop.length || j < pointsBottom.length) {Ð
                        if (pointsTop[i] == pointsBottom[j]) {Ð
                            datapoints.points[k] = pointsTop[i];Ð
                            datapoints.points[k + 1] = pointsTop[i + 1];Ð
                            datapoints.points[k + 2] = pointsBottom[j + 1];Ð
                            j += ps;Ð                           i += ps;Ð
                        } else if (pointsTop[i] < pointsBottom[j]) {Ð
                            datapoints.points[k] = pointsTop[i];Ð
                            datapoints.points[k + 1] = pointsTop[i + 1];Ð
                            datapoints.points[k + 2] = k > 0 ?
datapoints.points[k-1] : null;Ð                           i += ps;Ð
                        } else {Ð
datapoints.points[k] = pointsBottom[j];Ð
datapoints.points[k + 1] = k > 1 ? datapoints.points[k-2] : null;Ð
                            datapoints.points[k + 2] = pointsBottom[j + 1];Ð
                            j += ps;Ð                       }Ð
                        k += 3;Ð                   }Ð               } else if
(series.lines.lineWidth > 0) {Ð                   datapoints.points =
calculateCurvePoints(datapoints, series.curvedLines, 1);Ð
datapoints.pointsize = 2;Ð               }Ð           }Ð       }Ð       //no
real idea whats going on here code mainly from https://code.google.com/p/flot/
issues/detail?id=226Ð       //if fit option is selected additional datapoints
get inserted before the curve calculations in nergal.dev s code.Ð
function calculateCurvePoints(datapoints, curvedLinesOptions, yPos) {Ð
            var points = datapoints.points, ps = datapoints.pointsize;Ð
            var num = curvedLinesOptions.curvePointFactor * (points.length /
ps);Ð           var xdata = new Array;Ð           var ydata = new Array;Ð
            var curX = -1;Ð           var curY = -1;Ð           var j = 0;Ð
            if (curvedLinesOptions.fit) {Ð               //insert a point
before and after the "real" data point to force the lineÐ               //to
have a max,min at the data point.Ð               var fpDist;Ð
if(typeof curvedLinesOptions.fitPointDist == 'undefined') {Ð
                    //estimate itÐ                   var minX = points[0];Ð
                    var maxX = points[points.length-ps];Ð
fpDist = (maxX - minX) / (500 * 100); //x range / (estimated pixel length of
placeholder * factor)Ð               } else {Ð                   //use user
defined valueÐ                   fpDist = curvedLinesOptions.fitPointDist;Ð
                }Ð               for (var i = 0; i < points.length; i += ps) {Ð
                    var frontX;Ð                   var backX;Ð
                    curX = i;Ð                   curY = i + yPos;Ð
                    //add point X sÐ                   frontX = points[curX]
- fpDist;Ð
```

```
                            backX = points[curX] + fpDist;Ð
                    var factor = 2;Ð                    while (frontX ==
points[curX] || backX == points[curX]) {Ð                        //inside the
ulpÐ                        frontX = points[curX] - (fpDist * factor);Ð
                        backX = points[curX] + (fpDist * factor);Ð
                        factor++;Ð                    }Ð                    //
add curve pointsÐ                    xdata[j] = frontX;Ð
ydata[j] = points[curY];Ð                    j++;Ð                    xdata[j]
= points[curX];Ð                    ydata[j] = points[curY];Ð
                    j++;Ð                    xdata[j] = backX;Ð
                    ydata[j] = points[curY];Ð                    j++;Ð
                }Ð            } else {Ð                //just use the datapointsÐ
                for (var i = 0; i < points.length; i += ps) {Ð
                    curX = i;Ð                    curY = i + yPos;Ð
                    xdata[j] = points[curX];Ð                    ydata[j] =
points[curY];Ð                    j++;Ð                    }Ð            }Ð
            var n = xdata.length;Ð            var y2 = new Array();Ð
var delta = new Array();Ð            y2[0] = 0;Ð            y2[n - 1] = 0;Ð
            delta[0] = 0;Ð            for (var i = 1; i < n - 1; ++i) {Ð
                var d = (xdata[i + 1] - xdata[i - 1]);Ð                if (d
== 0) {Ð                    //point before current point and after current
point need some space in betweenÐ                    return [];Ð
                }Ð                var s = (xdata[i] - xdata[i - 1]) / d;Ð
                var p = s * y2[i - 1] + 2;Ð                y2[i] = (s - 1) / p;Ð
                delta[i] = (ydata[i + 1] - ydata[i]) / (xdata[i + 1] -
xdata[i]) - (ydata[i] - ydata[i - 1]) / (xdata[i] - xdata[i - 1]);Ð
                delta[i] = (6 * delta[i] / (xdata[i + 1] - xdata[i - 1]) - s
* delta[i - 1]) / p;Ð            }Ð            for (var j = n - 2; j >= 0; --j)
{Ð                y2[j] = y2[j] * y2[j + 1] + delta[j];Ð            }Ð
            //   xmax  - xmin  / #pointsÐ            var step = (xdata[n - 1]
- xdata[0]) / (num - 1);Ð            var xnew = new Array;Ð            var ynew
= new Array;Ð            var result = new Array;Ð            xnew[0] = xdata[0];Ð
            ynew[0] = ydata[0];Ð            result.push(xnew[0]);Ð
result.push(ynew[0]);Ð            for ( j = 1; j < num; ++j) {Ð
                //new x point (sampling point for the created curve)Ð
                xnew[j] = xnew[0] + j * step;Ð                var max = n - 1;Ð
                var min = 0;Ð                while (max - min > 1) {Ð
                    var k = Math.round((max + min) / 2);Ð
if (xdata[k] > xnew[j]) {Ð                        max = k;Ð
                    } else {Ð                        min = k;Ð
                    }Ð                }Ð                //found point one to
the left and one to the right of generated new pointÐ                var h =
(xdata[max] - xdata[min]);Ð                if (h == 0) {Ð                    //
similar to above two points from original x data need some space between themÐ
                    return [];Ð                }Ð                var a =
(xdata[max] - xnew[j]) / h;Ð                var b = (xnew[j] - xdata[min]) / h;Ð
                ynew[j] = a * ydata[min] + b * ydata[max] + ((a * a * a - a)
* y2[min] + (b * b * b - b) * y2[max]) * (h * h) / 6;Ð
result.push(xnew[j]);Ð                result.push(ynew[j]);Ð            }Ð
            return result;Ð        }Ð    }//end initÐ    $.plot.plugins.push({Ð
        init : init,Ð        options : options,Ð        name : 'curvedLines',Ð
        version : '0.5'Ð    });Ð})(jQuery);Ð
```

public\assets\js\plugins\flot\jquery.flot.pie.js

/* Flot plugin for rendering pie charts.Ðopyright (c) 2007-2014 IOLA and Ole Laursen.Ðicensed under the MIT license.Ðhe plugin assumes that each series has a single data value, and that eachÐalue is a positive integer or zero. Negative numbers don't make sense for aÐie chart, and have unpredictable results. The values do NOT need to beÐassed in as percentages; the plugin will calculate the total and per-sliceÐercentages internally.Ð Created by Brian MedendorpÐ Updated with contributions from btburnett3, Anthony Aragues and Xavi IvarsÐhe plugin supports these options:Ð6W&-W3¢ ™pie: ™Ð6†÷s¢ G'VRð falseÐ—& F—W3¢ Ó f÷" W&6VçF vR öb gVÆÇ6—¦RÂ ÷"   7 V6-f-VB —†VÂ ÆVæwF,Â ÷" 'auto'Ð--ææW%& F—W3¢ Ó f÷" W&6VçF vR öb gVÆÇ6—¦R ÷"   7 V6-f-VB —†VÂ length, for creating a donut effectÐ—7F 'D ævÆS¢ Ó" f 7F÷" öb ' W6VB f÷" starting angle (in radians) i.e 3/2 starts at the top, 0 and 2 have the resultÐ—F-ÇC¢ Ó f÷" W&6VçF vR Fò F-ÇB F†R -RÂ v†W&R —2 æò F-ÇBÂ æB —2 completely flat (nothing will show)Ð-öfg6WC¢™ ™top: integer value to move the pie up or downÐ™left: integer value to move the pie left or right, or 'autoÐ™ stroke: {Ð™color: any hexidecimal color value (other formats may or may not work, so best to stick with something like '#FFF')Ð™width: integer pixel width of the strokeÐ—Ó†Æ &VÃ¢™ ™show: true/false, or 'autoÐ™formatter: a user-defined function that modifies the text/style of the label textÐ™radius: 0-1 for percentage of fullsize, or a specified pixel lengthÐ™background:™ ™Ð6öÆ÷#¢ ç' hexidecimal color value (other formats may or may not work, so best to stick with something like '#000')Ð™-÷ 6—G"¢ ™Ó},Ðhreshold: 0-1 for the percentage value at which to hide labels (if they're too small)Ð™Ó†6öÖ&-æS¢™ ™threshold: 0-1 for the percentage value at which to combine slices (if they're too small)Ð™ color: any hexidecimal color value (other formats may or may not work, so best to stick with something like '#CCC'), if null, the plugin will automatically use the color of the first slice to be combinedÐ™label: any text value of what the combined slice should be labeledÐ™Ý†-v†Æ-v‡C¢™ ™opacity: 0-1Ð More detail and specific examples can be found in the included HTML file.Ð/Ð (function($) {ÐÒòò Ö †-×VÒ &VG& r GFV× G2 v†Vâ f—GF-ær Æ &VÇ2 v—F†-â F†R Æ÷Ð var REDRAW_ATTEMPTS = 10;ÐÒòò f 7F÷" '' v†-6, Fò 6‡&-æ² F†R -R v†Vâ f—GF-ær labels within the plotÐf " TE uõ4…$"ä² Ò ã"SÐgVæ7F-öâ -æ—B‡ Æ÷B' Ðvar canvas = null,Ð™—F &vWB Ò çVÆÂÍ÷ F-öç2 Ò çVÆÂÍÖ …& F—W2 Ò çVÆÂÍ6VçFW$ÆVgB Ò çVÆÂÍ centerTop = null,Ð™— &ö6W76VB Ò f Ç6RÍ7G, Ò çVÆÐ½/ interactive variableÐÐvar highlights = [];Ð™// add hook to determine if pie plugin in enabled, and then perform necessary operationsÐplot.hooks.processOptions.push(function(plot, options) {Ð™--b †÷ F-öç2ç6W&-W2ç -Rç6†÷r'Ð™options.grid.show = falseÐ™Ð/ set labels.showÐ™if (options.series.pie.label.show == "auto")™{Ð-b (options.legend.show) {Ð™™options.series.pie.label.show = false;Ð™ VÇ6R™ ™ options.series.pie.label.show = true;Ð™ Ð}ÐÐ/ set radiusÐif (options.series.pie.radius == "auto") {Ð™--b †÷ F-öç2ç6W&-W2ç -RæÆ &VÂç6†÷r™™™ options.series.pie.radius = 3/4;Ð™—Ò VÇ6R™ ™options.series.pie.radius = 1;ÐÐ/ ensure sane tiltÐ™if (options.series.pie.tilt > 1)™{Ð÷ F-öç2ç6W&-W2ç -RçF-ÇB Ò ½ ™™} else if (options.series.pie.tilt < 0)™{Ð÷ F-öç2ç6W&-W2ç -RçF-ÇB Ò™™™ ½Ð)™ÐÐ plot.hooks.bindEvents.push(function(plot, eventHolder) {Ð—f " ÷ F-öç2 Ò plot.getOptions();Ð--b †÷ F-öç2ç6W&-W2ç -Rç6†÷r'™ ™if (options.grid.hoverable)™{Ð eventHolder.unbind("mousemove").mousemove(onMouseMove);Ð™™™Ðif (options.grid.clickable) {Ð™-WfVçD†öÆFW"çVæ&-æB,&6Æ-6²"'æ6Æ-6²†öä6Æ-6™™™ ½Ð)™ÐÐ plot.hooks.processDatapoints.push(function(plot, series, data, datapoints) {Ð• var options = plot.getOptions();Ð--b †÷ F-öç2ç6W&-W2ç -Rç6†÷r'™ ™ processDatapoints(plot, series, data, datapoints);Ð™Ý)™ÐÐ plot.hooks.drawOverlay.push(function(plot, octx) {Ð—f " ÷ F-öç2 Ò plot.getOptions();Ð--b †÷ F-öç2ç6W&-W2ç -Rç6†÷r'™ ™drawOverlay(plot, octx);Ð™Ý)™ÐÐ plot.hooks.draw.push(function(plot, newCtx) {Ð—f " ÷ F-öç2 Ò Æ÷BævWD÷ F-öç2,™ ½ if (options.series.pie.show) {Ð™draw(plot, newCtx);Ð™Ý)™ÐÐunction processDatapoints(plot, series, datapoints) {Ð--b , &ö6W76VB™ {Ðprocessed = true;Ð canvas = plot.getCanvas();Ð™target = $(canvas).parent();Ð™options = plot.getOptions();Ð™plot.setData(combine(plot.getData()));Ð™Ý)™ÐÐunction combine(data) {Ð

Ð—f " F÷F Â Ò ™Ícombined = 0;™ÐumCombined = 0;™Ðolor =
options.series.pie.combine.color,™newdata = [];™Ðòò f—, W F†R & r F F g&öÒ
Flot, ensuring the data is numericÐ–f÷" ‡f " ’ Ò ² ’ Â F F æÆVæwFƒ² ²¶’’™½var
value = data[i].data;™// If the data is an array, we'll assume that it's a
standardÐ™// Flot x-y pair, and are concerned only with the second valuÐ.™Ð/
Note how we use the original array, rather than creating aÐ™// new one; this is
more efficient and preserves any extra dataÐ™// that the user may have stored
in higher indexes.™if ($.isArray(value) && value.length == 1) {Ð ™value =
value[0];™™™}™Ðif ($.isArray(value))™™™{™™™Ðòò W V—f ÆVçB Fò Bæ—4çVÖW&–2,’ 'WB
compatible with jQuery < 1.7™™™–b , —4æ â‡ '6TfÆö B‡f ÇVU³ Ò’’ bb
isFinite(value[1])) {™™™value[1] = +value[1];™™™Ð VÇ6R™™™½value[1] =™™™0;™™™Ð else if (!
isNaN(parseFloat(value)) && isFinite(value)) {™™™–f ÇVR Ò ³ Â ·f ÇVÜÜ™™™½ else™™™{™™™Ð
value = [1, 0];™™™}™™™Ðata[i].data = [value];™™™™™™Ðòò 7VÒ W ÆÂ F†R 6Æ–6W2Â 6ò vR 6 â
calculate percentages for eachÐ–f÷" ‡f " ’ Ò ² ’ Â F F æÆVæwFƒ² ²¶’’™½total +=
data[i].data[0][1];™™™™™™

™Ð¥–b ‡ Æ÷Bç6WE6W&–W2 bb Æ÷Bæ–ç6W'DÆVvVæB’™½
plot.setSeries(slices);Ð™plot.insertLegend(™Ð™Ýòò vRw&R 7GV ÆÇ’ FöæR B F†–2
point, just defining internal functions at this pointÐ–gVæ7F–öâ 6ÆV ",’™½
ctx.clearRect(0, 0, canvasWidth, canvasHeight);Ð™
target.children().filter(".pieLabel, .pieLabelBackground").remove();™Ð¥gVæ7F–öâ
drawShadow() {Ð™var shadowLeft = options.series.pie.shadow.left;™Ðar shadowTop =
options.series.pie.shadow.top;Ð™var edge = 10;™Ðar alpha =
options.series.pie.shadow.alpha;Ð™var radius = options.series.pie.radius > 1 ?
options.series.pie.radius : maxRadius * options.series.pie.radius;Ð™if (radius
>= canvasWidth / 2 - shadowLeft || radius * options.series.pie.tilt >=
canvasHeight / 2 - shadowTop || radius <= edge) {Ð™–&WGW&ã¹// shadow would be
outside canvas, so don't draw itÐ™}™Ðctx.save();™Ð
ctx.translate(shadowLeft,shadowTop);Ð™ctx.globalAlpha = alpha;™Ðctx.fillStyle =
"#000";Ð™// center and rotate to starting positiÐ™Ð
ctx.translate(centerLeft,centerTop);Ð™ctx.scale(1, options.series.pie.tilt);™Ð/
radius -= edge;Ð™for (var i = 1; i <= edge; i++) {™Ð7G,æ&Vv–å F,’™½7G,æ &2ƒ Â Â
radius, 0, Math.PI * 2, false);Ð™–7G,æf–ÆÂ™½& F–W2 ÓÒ™Ð™Ðctx.restore();™Ð™Ð
function drawPie() {Ð™var startAngle = Math.PI * options.series.pie.startAngle;™Ð
var radius = options.series.pie.radius > 1 ? options.series.pie.radius :
maxRadius * options.series.pie.radius;Ð™// center and rotate to starting
positionÐ™ctx.save();™Ðctx.translate(centerLeft,centerTop);™Ðctx.scale(1,
options.series.pie.tilt);Ð™//ctx.rotate(startAngle); // start at top; -- This
doesn't work properly in OperaÐ™// draw sliceÐ™™Ðctx.save();™Ðar currentAngle =
startAngle;Ð™for (var i = 0; i < slices.length; ++i) {™Ð6Æ–6W5¶•Òç7F 'D æv‡R Ò
currentAngle;Ð™–G& u6Æ–6R‡6Æ–6W5¶•Òæ æv‡RÂ 6Æ–6W5¶•Òæ6öÆ÷"Â G'VR™½™Ðctx.restore();™Ð
™// draw slice outlineÐ™™Ðif (options.series.pie.stroke.width > 0) {™Ð7G,ç6 fR,’™½
ctx.lineWidth = options.series.pie.stroke.width;Ð™–7W'&VçD æv‡R Ò 7F 'D æv‡S½f÷"
(var i = 0; i < slices.length; ++i) {Ð™™drawSlice(slices[i].angle,
options.series.pie.stroke.color, false);Ð™™¥7G,ç&W7F÷&R,™Ð™Ð/ draw donut holeÐ™
drawDonutHole(ctx);Ð™ctx.restore();™Ð/ Draw the labels, returning true if they
fit within the plotÐ™if (options.series.pie.label.show) {™Ð&WGW&â G& tÆ &VÇ2,’™½
else return true;Ð™function drawSlice(angle, color, fill) {™Ð–b † æv‡R ÃÒ ÇÂ
isNaN(angle)) {Ð™return false;™Ð–b †f–ÆÂ™½™Ðctx.fillStyle = color;™Ð VÇ6R™½
ctx.strokeStyle = color;Ð™™ctx.lineJoin = "round;™Ð™Ð7G,æ&Vv–å F,’™½–b
(Math.abs(angle - Math.PI * 2) > 0.000000001) {Ð™™ctx.moveTo(0, 0); // Center of
the pieÐ™™–Ýòö7G,æ &2ƒ Â Â & F–W2Â Â æv‡RÂ f Ç6R“² òò F†–2 FöW6âwB v÷&²
properly in OperaÐ™–7G,æ &2ƒ Â Â & F–W2Æ7W'&VçD æv‡RÂ 7W'&VçD æv‡R ² æv‡R ò "Â
false);Ð™–7G,æ &2ƒ Â Â & F–W2Æ7W'&VçD æv‡R ² æv‡R ò "Â 7W'&VçD æv‡R ² æv‡RÂ
false);Ð™–7G,æ6Æ÷6U F,’™½òö7G,ç&÷F FR† æv‡R“² òò F†–2 FöW6âwB v÷&² &÷ W&Ç’ –â
OperaÐ™–7W'&VçD æv‡R ³Ò æv‡S½–b †f–ÆÂ™½ctx.fill();™Ð VÇ6R™½ctx.stroke();™Ð™Ð
function drawLabels() {Ð™–f " 7W'&VçD æv‡R Ò 7F 'D æv‡S½f " & F–W2 Ò
options.series.pie.label.radius > 1 ? options.series.pie.label.radius :
maxRadius * options.series.pie.label.radius;Ð™–f÷" ‡f " ’ Ò ² ’ Â
slices.length; ++i) {Ð™™if (slices[i].percent >=
options.series.pie.label.threshold * 100) {Ð™™––b , G& tÆ &VÂ‡6Æ–6W5¶•ÒÂ
currentAngle, i)) {Ð™™return false;™Ð™™currentAngle += slices[i].angle;™Ð™Ð&WGW&â
true;Ð™–gVæ7F–öâ G& tÆ &VÂ‡6Æ–6RÂ 7F 'D æv‡RÂ –æFW,™Ð™½if (slice.data[0][1] == 0)
{Ð™™–&WGW&â G™Ð™™S½™Ð/ format label textÐ™™Ðar lf = options.legend.labelFormatter,
text, plf = options.series.pie.label.formatter;Ð™™if (lf) {™ÐFW‡B Ò
lf(slice.label, slice);Ð™™} else {™ÐFW‡B Ò 6Æ–6RæÆ &™Ð™™A½™Ðif (plf) {™ÐFW‡B Ò Æb‡FW‡BÂ
slice);™Ð™™}™Ðar halfAngle = ((startAngle + slice.angle) + startAngle) / 2;™Ðar x =
centerLeft + Math.round(Math.cos(halfAngle) * radius);Ð™™var y = centerTop +
Math.round(Math.sin(halfAngle) * radius) * options.series.pie.tilt;Ð™™var html =
"<span class='pieLabel' id='pieLabel" + index + "'
style='position:absolute;top:" + y + "px;left:" + x + "px;'>" + text + "</
span>";Ð™™target.append(html);™Ðar label = target.children("#pieLabel" + index);™Ð
var labelTop = (y - label.height() / 2);Ð™™var labelLeft = (x - label.width() /
2);Ð™™label.css("top", labelTop);™Ðlabel.css("left", labelLeft);™Ð/ check to make
sure that the label is not outside the canvasÐ™™if (0 - labelTop > 0 || 0 -
labelLeft > 0 || canvasHeight - (labelTop + label.height()) < 0 ||
canvasWidth - (labelLeft + label.width()) < 0) {Ð

™™™™—&WGW&â f ÇÐS½Ðf
(options.series.pie.label.background.opacity != 0) {Ð™™™’òò WB –â F†R G& ç7 &VçB
background separately to avoid blended labels and label boxesÐ™™™—f " 2 Ò
options.series.pie.label.background.color;Ð™™™––b †2 ÓÒ çVÆÂ™™™™½c = slice.color;Ð™™™
var pos = "top:" + labelTop + "px;left:" + labelLeft + "px;";Ð™™™’B,#ÆF—b
class='pieLabelBackground' style='position:absolute;width:" + label.width() +
"px;height:" + label.height() + "px;" + pos + "background-color:" + c + ";'></
div>")Ð™™™™.css("opacity", options.series.pie.label.background.opacity)Ð
™™™™™.insertBefore(labelÐ™™™);Ð™™™return true;Ð™™™ òò VæB –æF—f–GV Â Æ &VÂ gVæ7F™™™ // end
drawLabels functionÐ™™™—Ò òò VæB G& u –R gVæ7F–™™™ // end draw functionÐ™™™// Placed
here because it needs to be accessed from multiple locationsÐ™™™function
drawDonutHole(layer) {Ð™™™––b †÷ F–öç2ç6W&–W2ç –Ræ–ææW%& F—W2 â ’Ð™™™// subtract
the centerÐ™™™layer.save();Ð™™™var innerRadius = options.series.pie.innerRadius > 1 ?
options.series.pie.innerRadius : maxRadius * options.series.pie.innerRadius;Ð™™™
layer.globalCompositeOperation = "destination-out"; // this does not work
with excanvas, but it will fall back to using the stroke colorÐ™™™
layer.beginPath();Ð™™™layer.fillStyle = options.series.pie.stroke.color;Ð™™™
layer.arc(0, 0, innerRadius, 0, Math.PI * 2, false);Ð™™™layer.fill();Ð™™™
layer.closePath();Ð™™™layer.restore();Ð™™™// add inner strokeÐ™™™layer.save();Ð™™™
layer.beginPath();Ð™™™layer.strokeStyle = options.series.pie.stroke.color;Ð™™™
layer.arc(0, 0, innerRadius, 0, Math.PI * 2, false);Ð™™™layer.stroke();Ð™™™
layer.closePath();Ð™™™layer.restore();Ð™™™// TODO: add extra shadow inside hole (with
a mask) if the pie is tilted.Ð™™™™™Ð™™™// -- Additional Interactive related functions
--Ð™™™function isPointInPoly(poly, pt) {Ðf÷"‡f " 2 Ò f Ç6RÂ ’ Ò Ó Â Â Ò
poly.length, j = l - 1; ++i < l; j = i)Ð™™™((poly[i][1] <= pt[1] && pt[1] <
poly[j][1]) || (poly[j][1] <= pt[1] && pt[1]< poly[i][1]))Ð™™™&& (pt[0] < (poly[j]
[0] - poly[i][0]) * (pt[1] - poly[i][1]) / (poly[j][1] - poly[i][1]) + poly[i]
[0])Ð™™™&& (c = !c);Ð™™™&WGW&â 3™™™™™Ð™™™function findNearbySlice(mouseX, mouseY) {Ð™™™f "
slices = plot.getData(),Ð™™™options = plot.getOptions();Ð™™™radius =
options.series.pie.radius > 1 ? options.series.pie.radius : maxRadius *
options.series.pie.radius,Ð™™™x, y;Ð™™™f÷" ‡f " ’ Ò ² ’ Â 6Æ–6W2æÆVæwFƒ² ²¶’’Ð™™™½var s
= slices[i];Ð™™™if (s.pie.show)Ð™™™{Ð™™™7G,ç6 fR,™™™½7G,æ&Vv–â F,™™™½7G,æÖ÷fUFòƒ Â “² òò
Center of the pieÐ™™™’òö7G,ç66 ÆRƒ Â ÷ F–öç2ç6W&–W2ç –RçF–ÇB“¹// this actually
seems to break everything when here.Ð™™™–7G,æ &2ƒ Â Â & F—W2Â 2ç7F 'D ævÆRÂ
s.startAngle + s.angle / 2, false);Ð™™™–7G,æ &2ƒ Â Â & F—W2Â 2ç7F 'D ævÆR ²
s.angle / 2, s.startAngle + s.angle, false);Ð™™™–7G,æ6Æ÷6U F,™™™½, Ò Ö÷W6U, Ò
centerLeft;Ð™™™—’ Ò Ö÷W6U’ Ò 6VçFW%FÐ™™™½–b †7G,æ—5 ö–çD–â F,™™™½if
(ctx.isPointInPath(mouseX - centerLeft, mouseY - centerTop)) {Ð™™™–7G,ç&W7F÷&R,™™™½
return {Ð™™™datapoint: [s.percent, s.data],Ð™™™™™

™™—f " , Ò †–v†Æ–v‡G5¶•Ó½–b †,æ WFò ÓÒ WfVçFæ ÖR bb
(item && h.series == item.series)) {Ð™unhighlight(h.series);Ð™Ò òò †–v†Æ–v‡B F†R
sliceÐ––b †—FVÒ’™½highlight(item.series, eventname);Ð™Ò òò G&–vvW" ç’ †÷fW" &–æB
eventsÐ—f " ÷2 Ò ² vUƒ¢ Rç vU,Â vU“¢ Rç vU’ Ó½F &vWBçG&–vvW"†WfVçFæ ÖRÂ
[pos, item]);Ð™Ò function highlight(s, auto) {Ð™Ò öö–b ‡G— Vöb 2 ÓÒ &çVÖ&W""’™½òùs =
series[s];Ð™’ òÐ™¥f " ’ Ò –æFW„öd†–v†Æ–v‡B‡2Ð™½–b †’ ÓÒ Ó ’™½
highlights.push({ series: s, auto: auto });Ð™plot.triggerRedrawOverlay();Ð™ VÇ6R
if (!auto) {Ð™highlights[i].auto = false;Ð™Ò function unhighlight(s) {Ð™–b ‡2 ÓÒ
null) {Ð™highlights = [];Ð™plot.triggerRedrawOverlay();Ð™Ò öö–b ‡G— Vöb 2 ÓÒ
"number") {Ð™’ òùs = series[s];Ð™¥f " ’ Ò –æFW„öd†–v†Æ–v‡B‡2Ð™½–b †’ Ò Ó ’™½
highlights.splice(i, 1);Ð™plot.triggerRedrawOverlay();Ð™Ò function
indexOfHighlight(s) {Ð™–f÷" ‡f " ’ Ò ² ’ Â †–v†Æ–v‡G2æÆVæwFƒ² ²¶’’™½var h =
highlights[i];Ð™if (h.series == s);Ð™&WGW&â™½&WGW&â Ó™½Ð™Ò function
drawOverlay(plot, octx) {Ð™—f " ÷ F–öç2 Ò Æ÷BævWD÷ F–öç2,Ð™½f " & F—W2 Ò
options.series.pie.radius > 1 ? options.series.pie.radius : maxRadius *
options.series.pie.radius;Ð™–ö7G,ç6 fR,™½ö7G,çG& ç6Æ FR†6VçFW$ÆVgBÂ 6VçFW%F÷ ™½
octx.scale(1, options.series.pie.tilt);Ð™–f÷" ‡f " ’ Ò ² ’ Â †–v†Æ–v‡G2æÆVæwFƒ²
++i) {Ð™drawHighlight(highlights[i].series);Ð™&G& tFöçWD†öÆR†ö7G,Ð™½ö7G,ç&W7F÷&R,Ð™½
function drawHighlight(series) {Ð™if (series.angle <= 0 || isNaN(series.angle))
{Ð™—&WGW&Ð™½Ð/octx.fillStyle =
parseColor(options.series.pie.highlight.color).scale(null, null, null,
options.series.pie.highlight.opacity).toString();Ð™octx.fillStyle = "rgba(255,
255, 255, " + options.series.pie.highlight.opacity + ")"; // this is
temporary until we have access to parseColorÐ™octx.beginPath();Ð™if
(Math.abs(series.angle - Math.PI * 2) > 0.000000001) {Ð™–ö7G,æÖ÷fUFòƒ Â “² òò
Center of the pieÐ™}Ð™octx.arc(0, 0, radius, series.startAngle, series.startAngle
+ series.angle / 2, false);Ð™octx.arc(0, 0, radius, series.startAngle +
series.angle / 2, series.startAngle + series.angle, false);Ð™octx.closePath();Ð™
octx.fill();Ð™—}Ð™ òò VæB –æ—B ‡ ÇVv–â &öG’Ð™òò FVf–æR –R 7 V6–f–2 ÷ F–öç2 æB
their default valuesÐ™f " ÷ F–öç2 Ò ™½series: {Ð™ –S¢™½show: false,Ð™radius:
"auto",’òò 7GV Â & F—W2 öb F†R f—6–&ÆR –R †& 6VB öâ gVÆÂ 6 Æ7VÆ FVB & F—W2
if <=1, or hard pixel value)Ð™innerRadius: 0, /* for donut ™/Ð™startAngle: 3/2,Ð™
tilt: 1,Ð™shadow: {Ð™ÆVgC¢ RÉ// shadow left offset™Ð™÷ ¢ RÉ// shadow top offset™Ð™
alpha: 0.02’òò 6† F÷r Ç †™™™™™},Ð™offset: {Ð™F÷ ¢™™™ÍÆVgC¢ & WFÓ™™™},Ð™stroke: {Ð™6öÆ÷#¢
"#fff",Ð™—v–GFƒ¢™™™},Ð™label: {Ð™6†÷s¢ & WFÓ™™™Íf÷&Ö GFW#¢ gVæ7F–öâ†Æ &VÂÂ 6Æ–6R™™½
return "<div style='font-size:x-small;text-align:center;padding:2px;color:" +
slice.color + ";'>" + label + "<br/>" + Math.round(slice.percent) + "% ";Ð
™™—ÒÉ// formatter function™Ð™ F—W3¢ É// radius at which to place the labels
(based on full calculated radius if <=1, or hard pixel value)Ð™–& 6¶w&÷VæC¢™™™½
color: null,Ð™™™opacity: ™™™™™

public\assets\js\plugins\flot\jquery.flot.spline.js

```
/**Ð* Flot plugin that provides spline interpolation for line graphsÐ*
author: Alex Bardas < alex.bardas@gmail.com >Ð* modified by: Avi Kohn https://
github.com/AMKohnÐ* based on the spline interpolation described at:Ð*™ http://
scaledinnovation.com/analytics/splines/aboutSplines.htmlÐ*Ð* Example usage:
(add in plot options series object)Ð*™for linespline:Ð™–6W&–W3¢ ½™™..*Ð™lines: {Ð
 *™™–6†÷s¢ f Çõ™™};*Ð™splines: {Ð™–6†÷s¢ G'VRÍ™–FVç6–öã¢ ,Â †fÆö B &WGvVVâ    æB
1, defaults to 0.5),Ð*™™–Æ–æUv–GFƒ¢ ' †çVÖ&W"Â FVf VÇG2 Fò "*Í™–f–ÆÃ¢ ¢ †fÆö B
between 0 .. 1 or false, as in flot documentation)Ð*™™}*Ð™..*Ð–Ý™areaspline:Ð™•
series: {Ð*™™..*Ð™lines: {Ð™–6†÷s¢ G'VRÍ™–Æ–æUv–GFƒ¢  Â †Æ–æR G& v–ær v–ÆÂ æ÷B
execute)Ð*™™–f–ÆÃ¢ ,Â †fÆö B &WGvVVâ   ââ  Â  2 –â fÆ÷B Fö7VÖVçF F–öã™'ââÍ™}*Ð™
splines: {Ð*™™–6†÷s¢ G'VRÍ™–FVç6–öã¢  ãR †fÆö B &WGvVVâ    æB *™™};*Ð™..*Ð–Ý™Ð*/Ð
(function($) {Ð   'use strict'Ð   /**Ð    * @param {Number} x0, y0, x1, y1:
coordinates of the end (knot) points of the segmentÐ    * @param {Number} x2,
y2: the next knot (not connected, but needed to calculate p2)Ð    * @param
{Number} tension: control how far the control points spreadÐ    * @return
{Array}: p1 -> control point, from x1 back toward x0Ð    * ™™_ " Óâ F†R æW‡B
control point, returned to become the next segment's p1Ð    *Ð    * @api
privateÐ    */Ð   function getControlPoints(x0, y0, x1, y1, x2, y2, tension) {Ð
        var pow = Math.pow,Ð           sqrt = Math.sqrt,Ð           d01, d12,
fa, fb, p1x, p1y, p2x, p2y;Ð       //  Scaling factors: distances from this
knot to the previous and following knots.Ð       d01 = sqrt(pow(x1 - x0, 2) +
pow(y1 - y0, 2));Ð       d12 = sqrt(pow(x2 - x1, 2) + pow(y2 - y1, 2));Ð
        fa = tension * d01 / (d01 + d12);Ð       fb = tension - fa;Ð
p1x = x1 + fa * (x0 - x2);Ð       p1y = y1 + fa * (y0 - y2);Ð       p2x = x1
- fb * (x0 - x2);Ð       p2y = y1 - fb * (y0 - y2);Ð       return [p1x, p1y,
p2x, p2y];Ð   }Ð   var line = [];Ð   function drawLine(points, ctx, height,
fill, seriesColor) {Ð       var c = $.color.parse(seriesColor);Ð       c.a =
typeof fill == "number" ? fill : .3;Ð       c.normalize();Ð       c =
c.toString();Ð       ctx.beginPath();Ð       ctx.moveTo(points[0][0],
points[0][1]);Ð       var plength = points.length;Ð       for (var i = 0; i <
plength; i++) {Ð           ctx[points[i][3]].apply(ctx, points[i][2]);Ð
        }Ð       ctx.stroke();Ð       ctx.lineWidth = 0;Ð
ctx.lineTo(points[plength - 1][0], height);Ð       ctx.lineTo(points[0][0],
height);Ð       ctx.closePath();Ð       if (fill !== false) {Ð
ctx.fillStyle = c;Ð           ctx.fill();Ð       }Ð   }Ð   /**Ð    * @param
{Object} ctx: canvas contextÐ    * @param {String} type: accepted strings:
'bezier' or 'quadratic' (defaults to quadratic)Ð    * @param {Array} points:
2 points for which to draw the interpolationÐ    * @param {Array} cpoints:
control points for those segment pointsÐ    *Ð    * @api privateÐ    */Ð
function queue(ctx, type, points, cpoints) {Ð       if (type === void 0 ||
(type !== 'bezier' && type !== 'quadratic')) {Ð           type = 'quadratic';Ð
        }Ð       type = type + 'CurveTo';Ð       if (line.length == 0)
line.push([points[0], points[1], cpoints.concat(points.slice(2)), type]);Ð
        else if (type == "quadraticCurveTo" && points.length == 2) {Ð
            cpoints = cpoints.slice(0, 2).concat(points);Ð
line.push([points[0], points[1], cpoints, type]);Ð       }Ð       else
line.push([points[2], points[3], cpoints.concat(points.slice(2)), type]);Ð   }Ð
    /**Ð    * @param {Object} plotÐ    * @param {Object} ctx: canvas contextÐ
     * @param {Object} seriesÐ    *Ð    * @api privateÐ    */Ð   function
drawSpline(plot, ctx, series) {Ð       // Not interested if spline is not
requestedÐ       if (series.splines.show !== true) {Ð           return;Ð
        }Ð       var cp = [],Ð       // array of control pointsÐ
tension = series.splines.tension || 0.5,Ð           idx, x, y, points =
series.datapoints.points,Ð           ps = series.datapoints.pointsize,Ð
            plotOffset = plot.getPlotOffset(),Ð           len = points.length,Ð
            pts = [];Ð       line = [];Ð       // Cannot display a linespline/
areaspline if there are less than 3 pointsÐ       if (len / ps < 4) {Ð
            $.extend(series.lines, series.splines);Ð           return;Ð
        }Ð
```

```
         Ð       for (idx = 0; idx < len; idx += ps) {Ð           x =
points[idx];Ð           y = points[idx + 1];Ð           if (x == null || x <
series.xaxis.min || x > series.xaxis.max || y < series.yaxis.min || y >
series.yaxis.max) {Ð               continue;Ð           }Ð
pts.push(series.xaxis.p2c(x) + plotOffset.left, series.yaxis.p2c(y) +
plotOffset.top);Ð       }Ð       len = pts.length;Ð       // Draw an open
curve, not connected at the endsÐ       for (idx = 0; idx < len - 2; idx +=
2) {Ð           cp = cp.concat(getControlPoints.apply(this, pts.slice(idx,
idx + 6).concat([tension])));Ð       }Ð       ctx.save();Ð
ctx.strokeStyle = series.color;Ð       ctx.lineWidth =
series.splines.lineWidth;Ð       queue(ctx, 'quadratic', pts.slice(0, 4),
cp.slice(0, 2));Ð       for (idx = 2; idx < len - 3; idx += 2) {Ð
queue(ctx, 'bezier', pts.slice(idx, idx + 4), cp.slice(2 * idx - 2, 2 * idx +
2));Ð       }Ð       queue(ctx, 'quadratic', pts.slice(len - 2, len), [cp[2 *
len - 10], cp[2 * len - 9], pts[len - 4], pts[len - 3]]);Ð
drawLine(line, ctx, plot.height() + 10, series.splines.fill, series.color);Ð
        ctx.restore();Ð   }Ð   $.plot.plugins.push({Ð       init:
function(plot) {Ð           plot.hooks.drawSeries.push(drawSpline);Ð       },Ð
        options: {Ð           series: {Ð               splines: {Ð
                    show: false,Ð                    lineWidth: 2,Ð
                    tension: 0.5,Ð                    fill: falseÐ
                }Ð           }Ð       },Ð       name: 'spline',Ð
version: '0.8.2'Ð   });Ð})(jQuery);Ð
```

public\assets\js\plugins\flot\jquery.flot.symbol.js

/* Flot plugin that adds some extra symbols for plotting points.Ðcopyright (c) 2007-2014 IOLA and Ole Laursen.Ðlicensed under the MIT license.Ðthe symbols are accessed as strings through the standard symbol options:Ð6W&–W3¢ ½points: {Ð symbol: "square" // or "diamond", "triangle", "cross"Ð}ÐÐ/*Ð function ($) {Ð function processRawData(plot, series, datapoints) {Ð // we normalize the area of each symbol so it is approximately theÐ // same as a circle of the given radiusÐ var handlers = {Ð square: function (ctx, x, y, radius, shadow) {Ð // pi * r^2 = (2s)^2 => s = r * sqrt(pi)/2Ð var size = radius * Math.sqrt(Math.PI) / 2;Ð ctx.rect(x - size, y - size, size + size, size + size);Ð },Ð diamond: function (ctx, x, y, radius, shadow) {Ð // pi * r^2 = 2s^2 => s = r * sqrt(pi/2)Ð var size = radius * Math.sqrt(Math.PI / 2);Ð ctx.moveTo(x - size, y);Ð ctx.lineTo(x, y - size);Ð ctx.lineTo(x + size, y);Ð ctx.lineTo(x, y + size);Ð ctx.lineTo(x - size, y);Ð },Ð triangle: function (ctx, x, y, radius, shadow) {Ð // pi * r^2 = 1/2 * s^2 * sin (pi / 3) => s = r * sqrt(2 * pi / sin(pi / 3))Ð var size = radius * Math.sqrt(2 * Math.PI / Math.sin(Math.PI / 3));Ð var height = size * Math.sin(Math.PI / 3);Ð ctx.moveTo(x - size/2, y + height/2);Ð ctx.lineTo(x + size/2, y + height/2);Ð if (!shadow) {Ð ctx.lineTo(x, y - height/2);Ð ctx.lineTo(x - size/2, y + height/2);Ð }Ð },Ð cross: function (ctx, x, y, radius, shadow) {Ð // pi * r^2 = (2s)^2 => s = r * sqrt(pi)/2Ð var size = radius * Math.sqrt(Math.PI) / 2;Ð ctx.moveTo(x - size, y - size);Ð ctx.lineTo(x + size, y + size);Ð ctx.moveTo(x - size, y + size);Ð ctx.lineTo(x + size, y - size);Ð }Ð };Ð var s = series.points.symbol;Ð if (handlers[s])Ð series.points.symbol = handlers[s];Ð }Ð Ð function init(plot) {Ð plot.hooks.processDatapoints.push(processRawData);Ð }Ð Ð $.plot.plugins.push({Ð init: init,Ð name: 'symbols',Ð version: '1.0'Ð });Ð})(jQuery);Ð

public\assets\js\plugins\flot\jquery.flot.time.js

/* Pretty handling of time axes.Ðopyright (c) 2007-2014 IOLA and Ole Laursen.Ð
Licensed under the MIT license.Ðet axis.mode to "time" to enable. See the
section "Time series data" inÐPI.txt for details.Ð/Ðfunction($) {Ðf " ÷ F–öç2
= {™xaxis: ™ÐF–ÖW¦öæS¢ çVÆÂÉ’òò &'&÷w6W"" f÷" Æö6 Â Fò F†R 6Æ–VçB ÷" F–ÖW¦öæR
for timezone-js™Ð—F–ÖVf÷&Ö C¢ çVÆÂÉ// format string to use™ÐvVÇfT†÷W$6Æö6³¢
false,’òò " ÷" #B F–ÖR –â F–ÖR ÖöF™–ÖöçF„æ ÖW3¢ çVÆÉ// list of names of month™$Ð
—ÓÐòò &÷VæB Fò æV &'’ Æ÷vW" ×VÇF— ÆR öb & 6ÐgVæ7F–öâ fÆö÷$–ä& 6R†âÂ & 6R’ ™
return base * Math.floor(n / base);ÐÓòò &WGW&ç2 7G&–ær v—F, F†R F FR B
formatted according to fmt.Ðòò 7V'6WB öb F†R ÷ Vâ w&÷W w2 7G&gF–ÖR f÷&Ö B —2
supported.ÐgVæ7F–öâ f÷&Ö DF FR†BÂ f×BÂ ÖöçF„æ ÖW2Â F ”æ ÖW2’ ™if (typeof
d.strftime == "function") {™—&WGW&â Bç7G&gF–ÖR†f×B™ÐÐvar leftPad = function(n,
pad) {™–â Ò "" ² ™½ B Ò "" ² ‡ B ÓÒ çVÆÂ ò # " ¢ B™½&WGW&â âæÆVæwF, ÓÒ ò
pad + n : n;™}™Ðvar r = [];™Ðvar escape = false;™Ðvar hours = d.getHours();™Ðvar isAM
= hours < 12;™if (monthNames == null) {™ÐÖöçF„æ ÖW2 Ò ²$¦ â"Â $fV""Â $Ö ""Â
"Apr", "May", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec"];™Ðif (dayNames
== null) {™–F ”æ ÖW2 Ò ²%7Vâ"Â $Ööâ"Â %GVR"Â %vVB"Â %F‡R"Â $g&’"Â %6 B%Ó™Ðvar
hours12;™if (hours > 12) {™Ð†÷W'3 " Ò †÷W'2 Ò #½ else if (hours == 0) {™Ð†÷W'3 "
= 12;™} else {™Ð†÷W'3 " Ò †÷W'™Ðfor (var i = 0; i < fmt.length; ++i) {™Ðf " 2 Ò
fmt.charAt(i);™––b †W66 R’™½switch (c)™™™Ð6 6R v s¢ 2 Ò "" ²
dayNames[d.getDay()]; break;™–6 6R v"s¢ 2 Ò "" ² ÖöçF„æ ÖW5¶BævWDÖöçF,,•Ó²
break;™–6 6R vBs¢ 2 Ò ÆVgE B†BævWDF FR,’“² '&V™™½6 6R vRs¢ 2 Ò
leftPad(d.getDate(), " "); break;™–6 6R v,s©// For back-compat with 0.7; remove
in 1.0™–6 6R t,s¢ 2 Ò ÆVgE B††÷W'2“² '&V™™½6 6R t’s¢ 2 Ò ÆVgE B††÷W'3 "“²
break;™–6 6R vÂs¢ 2 Ò ÆVgE B††÷W'3 "Â " "“² '&V™™½6 6R vÒs¢ 2 Ò
leftPad(d.getMonth() + 1); break;™–6 6R tÒs¢ 2 Ò ÆVgE B†BævWDÖ–çWFW2,’“² '&V ³½
™™’òò V 'FW'2 æ÷B –â ÷ Vâ w&÷W w2 7G&gF–ÖR 7 V6–f–6 F™™í6 6R w™s™c = "" +
(Math.floor(d.getMonth() / 3) + 1); break;™–6 6R u2s¢ 2 Ò
leftPad(d.getSeconds()); break;™–6 6R w’s¢ 2 Ò ÆVgE B†BævWDgVÆÅ–V ",’ R “²
break;™–6 6R u’s¢ 2 Ò "" ² BævWDgVÆÅ–V ",“² '&V™™½6 6R w s¢ 2 Ò †—4 Ò’ ò ,"" ²
"am") : ("" + "pm"); break;™–6 6R u s¢ 2 Ò †—4 Ò’ ò ,"" ² $ Ò"’ ¢ ,"" ² % Ò"“²
break;™–6 6R wrs¢ 2 Ò "" ² BævWDF ’,“² '&V™™½™Ð.push(c);™Ðscape = false;™Ð VÇ6R™™½
if (c == "%") {™–W66 R Ò G'VS½ else™™Ð"ç W6,†2 ™™™Ðreturn r.join("");™ÐÓòò Fò
have a consistent view of time-based data independent of which time™Ðòò ¦öæR
the client happens to be in we need a date-like object independent™Ðòò öb F–ÖR
zones. This is done through a wrapper that only calls the UTC™Ðòò fW'6–öç2 öb
the accessor methods.ÐgVæ7F–öâ Ö ¶UWF5w& W"†B’ ™function
addProxyMethod(sourceObj, sourceMethod, targetObj, targetMethod) {™•
sourceObj[sourceMethod] = function() {™™return
targetObj[targetMethod].apply(targetObj, arguments);™—Ó½™™Ðvar utc = {™ÐF FS¢™™™™Ð
™// support strftime, if found™™if (d.strftime != undefined) {™Ð
addProxyMethod(utc, "strftime", d, "strftime");™™™™™™™™™™™™™™™™™™™™™™™™addProxyMethod(utc,
"getTime", d, "getTime");™™™™™™™™™™™™™™™™™™™™™™™™addProxyMethod(utc, "setTime", d, "setTime");™™™™™™™™™™™™™™™™™™™

Ðf " & 6U7 V2 Ò ™½[1, "second"], [2, "second"], [5, "second"], [10, "second"],™Ð[30, "second"],™Ð1, "minute"], [2, "minute"], [5, "minute"], [10, "minute"],™Ð[30, "minute"],™Ð1, "hour"], [2, "hour"], [4, "hour"],™Ð8, "hour"], [12, "hour"],™Ð[1, "day"], [2, "day"], [3, "day"],™Ð0.25, "month"], [0.5, "month"], [1, "month"],™Ð[2, "month"]•ÓÐòò vR FöâwB ¶æ÷r v†–6, f &– çB‡2’ vRvÆÂ need yet, but generating both isÐòò 6†V Ðf " 7 V4ÖöçF‡2 Ò & 6U7 V2æ6öæ6 B…µ³2Â "month"], [6, "month"],™Ð[1, "year"]])÷Ð " 7 V5 V 'FW'2 Ò & 6U7 V2æ6öæ6 B…µ³ Â "quarter"], [2, "quarter"],™Ð[1, "year"]])ÐgVæ7F–öâ –æ–B‡ Æ÷B’ ™½ plot.hooks.processOptions.push(function (plot, options) {™Ð• $.each(plot.getAxes(), function(axisName, axis) {™Ðvar opts = axis.options;™Ðif (opts.mode == "time") {™Ð– †–2çF–6´vVæW& F÷" Ò gVæ7F–öâ† †–2™Ð½var ticks = [];™Ð var d = dateGenerator(axis.min, opts);™Ðvar minSize =™Ð0;™Ð// make quarter use a possibility if quarters are™Ð// mentioned in either of these optiÐns™Ðvar spec = (opts.tickSize && opts.tickSize[1] ===™Ð'' V 'FW"™Ð'' Çí†÷ G2æÖ–åF–6µ6–¦R bb opts.minTickSize[1] ===™Ð'' V 'FW"™Ð'' ò 7 V5 V 'FW'2 ¢ 7 V4ÖöçÐ‡3½f (opts.minTickSize != null) {™Ð––b ‡G– Vöb ÷ G2çF–6µ6–¦R ÓÒ &çVÖ&W"™Ð½minSize = opts.tickSize;™Ð—Ò VÇ6R ½minSize = opts.minTickSize[0] * timeUnitSize[opts.minTickSize[1]];™Ð™Ðfor (var i = 0; i < spec.length - 1; ++i) {™Ð––b † †–2æFVÇF Â ‡7 V5¶•Õ³ Ò ¢ F–ÕUVæ–E6–¦U·7 V5¶•Õ³™Ð™Ð’ ² 7 V5¶’ ² Õ³ Ò ¢ timeUnitSize[spec[i + 1][1]]) / 2™Ð&& spec[i][0] * timeUnitSize[spec[i][1]] >= minSize) {™Ðbreak;™Ðvar size = spec[i][0];™Ðvar unit = spec[i][1];™Ð// special-case the possibility of several years™Ðif (unit == "year"™Ð {™Ðòò –b v–fVâ minTickSize in years, just use it,™Ð’òò Vç7W&–ær F† B –Bw2 â –çF™ÐVW––b (opts.minTickSize != null && opts.minTickSize[1] == "year") {™Ðsize = Math.floor(opts.minTickSize[0]);™Ð—Ò VÇ™ÐR ½var magn = Math.pow(10, Math.floor(Math.log(axis.delta / timeUnitSize.year) / Math.LN10));™Ðvar norm = (axis.delta / timeUnitSize.year) / magn;™Ðif (norm < 1.5) {™Ð6–¦R™Ò Ò ½ else if (norm < 3) {™Ð—6–¦R™Ò #½ else if (norm < 7.5) {™Ð6–¦R™Ò S½ else {™Ð6–¦R™Ò ÓÐ ½™Ðsize *= magn;™Ð™Ðòò Ö–æ–×VÒ 6–¦R f÷" –V '2 ™Ð2 ––b ‡6–¦R Â ™½size = ™Ð1;™Ð axis.tickSize = opts.tickSize || [size, unit];™Ðvar tickSize = axis.tickSize[0];™Ð unit = axis.tickSize[1];™Ðvar step = tickSize * timeUnitSize[unit];™Ðif (unit == "second") {™Ð–Bç6WE6V6öæG2†fÆö÷$–ä& 6R†BævWE6V6öæG2,’Â F–6µ6–¦R™Ð½ else if (unit == "minute") {™Ð–Bç6WDÖ–çWFW2†fÆö÷$–ä& 6R†BævWDÖ–çWFW2,’Â F–6µ6–¦R™Ð½ else if (unit == "hour") {™Ð–Bç6WD†÷W'2†fÆö÷$–ä& 6R†BævWD†÷W'2,’Â F–6µ6–¦R™Ð½ else if (unit == "month") {™Ð–Bç6WDÖöçF,†fÆö÷$–ä& 6R†BævWDÖöçF,,’Â F–6µ6–¦R™Ð½ else if (unit == "quarter") {™Ð–Bç6WDÖöçF,ƒ2 ¢ fÆö÷$–ä& 6R†BævWDÖöçF,,’ Ò 21™Ð tickSize));™Ð} else if (unit == "year") {™Ð d.setFullYear(floorInBase(d.getFullYear(), tickSize));™Ð™Ð}™Ð// reset smaller components™Ðd.setMilliseconds(™Ð0);™Ðif (step >= timeUnitSize.minute) {™Ð d.setSeconds(0);™Ð}™Ðif (step >= timeUnitSize.hour) {™ÐBç6WDÖ–çWFW2/™Ð½™Ðif (step >= timeUnitSize.day) {™Ð–Bç6WD†÷W'2/™Ð½™Ðif (step >= timeUnitSize.day * 4) {™Ð d.setDate(1);™Ð}™Ðif (step >= timeUnitSize.month * 2) {™Ð d.setMonth(floorInBase(d.getMonth(), 3));™Ð}™Ðif (step >= timeUnitSize.quarter * 2) {™Ð–Bç6WDÖöçF,†fÆö÷$–ä& 6R†BævWDÖöçF,,’Â Ò ™½™Ðif (step >= timeUnitSize.year) {™Ð d.setMonth(0);™Ð™Ð}™Ðvar carry =™Ð0;™Ðvar v = Number.NaN;™Ðvar prev;™Ð™Ð{™Ð &Wb Ò C½b Ò d.getTime();™Ð—F–6·2ç W6,™Ð™Ð½–b ‡Væ–B ÓÒ &ÖöçF," ÇÂ Væ–B ÓÒ ' V 'FW"™Ð½if (tickSize < 1) {™Ð’òò &–B 6ö× Æ–6 FVB Ò vRvÆÂ F–f–FR™Ð F†]òò ÖöçF,÷ V 'FW" W but we need to take™Ð’òò 6 &R öb g& 7F–öç2 6ò vR FöâwB VæB W™Ð–ìòò F†R Ö–FFÆR öb a day™Ð–Bç6WDF FR™Ð½f " 7F 'B Ò BævWEF–ÕR™Ð½Bç6WDÖöçF,†BævWDÖöçF,,™Ð½(unit == "quarter" ? 3 : 1));™Ð—f " VæB Ò BævWEF–ÕR™Ð½Bç6WEF–ÕR‡b ² 6 ''’ ¢ timeUnitSize.hour + (end - start) * tickSize);™Ð–6 ''’ Ò BævWD†÷W'2™Ð½ d.setHours(0);™Ð} else {™ÐBç6WDÖöçF,†BævWDÖöçF,,™Ð½tickSize * (unit == "quarter" ? 3 : 1));™Ð}™ÐVÇ6R –b ‡Væ–B ÓÒ '–V "™Ð½™Ð d.setFullYear(d.getFullYear() + tickSize);™Ð—Ò VÇ6R ½d.setTime(v + step);™Ð while (v < axis.max && v != prev);™Ðreturn ticks;™Ð™Ð½ †–2çF–6´f÷&Ö GFW" Ò function (v, axis) {™Ðvar d = dateGenerator(v, axis.options);™Ð// first check global format™Ðif (opts.timeformat != null) {™Ð&WGW&â f÷&Ö DF FR†BÂ opts.timeformat, opts.monthNames, opts.dayNames);™Ð™Ð}™Ð// possibly use quarters if quarters are mentioned in™Ð// any of these places™Ðvar useQuarters = (axis.options.tickSize &&™Ð

™™™™axis.options.tickSize[1] == "quarter") ||Ð
(axis.options.minTickSize &&Ð™™™™axis.options.minTickSize[1] == "quarter") {Ð™™™™var t =
axis.tickSize[0] * timeUnitSize[axis.tickSize[1]];Ð™™™™var span = axis.max -
axis.min;Ð™™™™var suffix = (opts.twelveHourClock) ? " %p" : "";Ð™™™™var hourCode =
(opts.twelveHourClock) ? "%I" : "%H";Ð™™™™var fmt;Ð™™™™if (t < timeUnitSize.minute) {Ð
fmt = hourCode + ":%M:%S" + suffix;Ð™™™™} else if (t < timeUnitSize.day) {Ð–b ‡7 â
< 2 * timeUnitSize.day) {Ð™™™™fmt = hourCode + ":%M" + suffix;Ð™™™™VÇÖR ½fmt = "%b %d
" + hourCode + ":%M" + suffix;Ð™™™™Ý else if (t < timeUnitSize.month) {Ðf×B Ò "V"
%d";Ð™™™™} else if ((useQuarters && t < timeUnitSize.quarter) ||Ð™™™™, W6U V 'FW'2 bb B
< timeUnitSize.year)) {Ð™™™™––b ‡7 â Â F–ÖUVæ—E6—¦Rç–V ™™™™½fmt = "%b %d";Ð™™™™VÇÖR ½fmt
= "%b %Y";Ð™™™™Ý else if (useQuarters && t < timeUnitSize.year) {Ð–b ‡7 â Â
timeUnitSize.year) {Ð™™™™fmt = "Q%q";Ð™™™™VÇÖR ½fmt = "Q%q %Y";Ð™™™™Ý else {Ðf×B Ò "UÐ#½Ð
var rt = formatDate(d, fmt, opts.monthNames, opts.dayNames);Ð™™™™return rt;Ð™™™™½Ò“½
™™™™});Ð™™™™Bç Æ÷Bç ÇVv–ç2ç W6,‡½init: init,Ðoptions: options,Ðname: 'time',Ðversion:
'1.0'ÐÒ“ÐÒòò F–ÖRÖ †—2 7W ÷'B W6VB Fò &R –â fÆ÷B 6÷&RÂ v†–6, W‡ ÷6VB F†]òò
formatDate function on the plot object. Various plugins dependÐòò öâ F†R
function, so we need to re-expose it here.ÐBç Æ÷Bæf÷&Ö DF FR Ò f÷&Ö DF FS½
$.plot.dateGenerator = dateGenerator;Ð})(jQuery);Ð

public\assets\js\plugins\iCheck\icheck.min.js

```
/*! iCheck v1.0.2 by Damir Sultanov, http://git.io/arlzeA, MIT Licensed */Ð
(function(f){function A(a,b,d){var c=a[0],g=/er/.test(d)?_indeterminate:/
bl/.test(d)?n:k,e=d==_update?
{checked:c[k],disabled:c[n],indeterminate:"true"==a.attr(_indeterminate)||"false"==a.attr(
^(ch|di|in)/.test(d)&&!e)x(a,g);else if(/^(un|en|de)/.test(d)&&e)q(a,g);else
if(d==_update)for(var f in e)e[f]?x(a,f,!0):q(a,f,!0);else if(!b||"toggle"==d)
{if(!b)a[_callback]("ifClicked");e?c[_type]!==r&&q(a,g):x(a,g)}}function
x(a,b,d){var c=a[0],g=a.parent(),e=b==k,u=b==_indeterminate,Ð   v=b==n,s=u?
_determinate:e?y:"enabled",F=l(a,s+t(c[_type])),B=l(a,b+t(c[_type]));if(!0!
==c[b]){if(!d&&b==k&&c[_type]==r&&c.name){var
w=a.closest("form"),p='input[name="'+c.name+'"]',p=w.length?
w.find(p):f(p);p.each(function(){this!==c&&f(this).data(m)&&q(f(this),b)})}u?
(c[b]=!0,c[k]&&q(a,k,"force")):(d||(c[b]=!
0),e&&c[_indeterminate]&&q(a,_indeterminate,!1));D(a,e,b,d)}
c[n]&&l(a,_cursor,!0)&&g.find("."+C).css(_cursor,"default");g[_add](B||
l(a,b)||"");g.attr("role")&&!u&&g.attr("aria-"+(v?n:k),"true");Ð   g[_remove]
(F||l(a,s)||"")}function q(a,b,d){var
c=a[0],g=a.parent(),e=b==k,f=b==_indeterminate,m=b==n,s=f?_determinate:e?
y:"enabled",q=l(a,s+t(c[_type])),r=l(a,b+t(c[_type]));if(!1!==c[b]){if(f||!
d||"force"==d)c[b]=!1;D(a,e,s,d)}!c[n]&&l(a,_cursor,!
0)&&g.find("."+C).css(_cursor,"pointer");g[_remove](r||
l(a,b)||"");g.attr("role")&&!f&&g.attr("aria-"+(m?n:k),"false");g[_add](q||
l(a,s)||"")}function E(a,b){if(a.data(m))
{a.parent().html(a.attr("style",a.data(m).s||""));if(b)a[_callback]
(b);a.off(".i").unwrap();Ð
f(_label+'[for="'+a[0].id+'"]').add(a.closest(_label)).off(".i")}}function
l(a,b,f){if(a.data(m))return a.data(m).o[b+(f?"":"Class")]}function t(a)
{return a.charAt(0).toUpperCase()+a.slice(1)}function D(a,b,f,c){if(!c)
{if(b)a[_callback]("ifToggled");a[_callback]("ifChanged")[_callback]
("if"+t(f))}}var m="iCheck",C=m+"-helper",r="radio",k="checked",y="un"+k,n="di
sabled";_determinate="determinate";_indeterminate="in"+_determinate;_update="u
pdate";_type="type";_click="click";_touch="touchbegin.i touchend.i";Ð   _add="
addClass";_remove="removeClass";_callback="trigger";_label="label";_cursor="cu
rsor";_mobile=/ipad|iphone|ipod|android|blackberry|windows phone|opera mini|
silk/i.test(navigator.userAgent);f.fn[m]=function(a,b){var
d='input[type="checkbox"], input[type="'+r+'"]',c=f(),g=function(a)
{a.each(function(){var a=f(this);c=a.is(d)?c.add(a):c.add(a.find(d))})};if(/
^(check|uncheck|toggle|indeterminate|determinate|disable|enable|update|
destroy)$/i.test(a))return a=a.toLowerCase(),g(this),c.each(function(){var c=Ð
        f(this);"destroy"==a?E(c,"ifDestroyed"):A(c,!
0,a);f.isFunction(b)&&b()});if("object"!=typeof a&&a)return this;var
e=f.extend({checkedClass:k,disabledClass:n,indeterminateClass:_indeterminate,labelHover:!
0},a),l=e.handle,v=e.hoverClass||"hover",s=e.focusClass||"focus",t=e.activeClass||"active"
e.labelHover,w=e.labelHoverClass||"hover",p=(""+e.increaseArea).replace("%","")|
0;if("checkbox"==l||
l==r)d='input[type="'+l+'"]';-50>p&&(p=-50);g(this);return c.each(function()
{var a=f(this);E(a);var c=this,Ð       b=c.id,g=-p+"%",d=100+2*p+"%",d={positi
on:"absolute",top:g,left:g,display:"block",width:d,height:d,margin:0,padding:0
,background:"#fff",border:0,opacity:0},g=_mobile?
{position:"absolute",visibility:"hidden"}:p?d:
{position:"absolute",opacity:0},l="checkbox"==c[_type]?
e.checkboxClass||"icheckbox":e.radioClass||"i"+r,z=f(_label+'[for="'+b+'"]').add(a.closest
e.aria,y=m+"-"+Math.random().toString(36).substr(2,6),h='<div class="'+l+'"
'+(u?'role="'+c[_type]+'" ':"");u&&z.each(function(){h+=Ð       'aria-
labelledby="';this.id?h+=this.id:(this.id=y,h+=y);h+='"'});h=a.wrap(h+"/>")
[_callback]("ifCreated").parent().append(e.insert);d=f('<ins class="'+C+'"/
>').css(d).appendTo(h);a.data(m,
{o:e,s:a.attr("style")}).css(g);e.inheritClass&&h[_add]
(c.className||"");e.inheritID&&b&&h.attr("id",m+"-"+b);"static"==h.css("position")&&h.css(
```

0,_update);if(z.length)z.on(_click+".i mouseover.i mouseout.i
"+_touch,function(b){var d=b[_type],e=f(this);if(!c[n]){if(d==_click)
{if(f(b.target).is("a"))return;Ð   A(a,!1,!0)}else B&&(/ut|nd/.test(d)?
(h[_remove](v),e[_remove](w)):(h[_add](v),e[_add]
(w)));if(_mobile)b.stopPropagation();else return!1}});a.on(_click+".i focus.i
blur.i keyup.i keydown.i keypress.i",function(b){var
d=b[_type];b=b.keyCode;if(d==_click)return!1;if("keydown"==d&&32==b)return
c[_type]==r&&c[k]||(c[k]?q(a,k):x(a,k)),!1;if("keyup"==d&&c[_type]==r)!
c[k]&&x(a,k);else if(/us|ur/.test(d))h["blur"==d?_remove:_add]
(s)});d.on(_click+" mousedown mouseup mouseover mouseout "+_touch,function(b)
{var d=Ð   b[_type],e=/wn|up/.test(d)?t:v;if(!c[n]){if(d==_click)A(a,!1,!
0);else{if(/wn|er|in/.test(d))h[_add](e);else h[_remove](e+"
"+t);if(z.length&&B&&e==v)z[/ut|nd/.test(d)?_remove:_add](w)}
if(_mobile)b.stopPropagation();else return!1}})})}})(window.jQuery||
window.Zepto);Ð

public\assets\js\plugins\ionRangeSlider\ion.rangeSlider.min.js

```
þÿ// Ion.RangeSlider | version 1.9.1 | https://github.com/IonDen/ion.rangeSliderÐ
(function(c,ea,$,M){var aa=0,s,S=function(){var c=M.userAgent,a=/msie\s\d+/
i;return 0<c.search(a)&&(c=a.exec(c).toString(),c=c.split(" ")[1],9>c)?!0:!1}
(),X="ontouchstart"in $||0<M.msMaxTouchPoints,N=function(c){"Number"!==typeof
c&&(c=parseFloat(c));return isNaN(c)?null:c},H={init:function(fa){return
this.each(function(){var
a=c.extend({min:null,max:null,from:null,to:null,type:"single",step:null,prefix:"",postfix:
1,hideMinMax:!1,hideFromTo:!1,prettify:!0,disable:!1,values:null,Ð
onChange:null,onLoad:null,onFinish:null},fa),e=c(this),n=this,I=!1,g=null;if(!
e.data("isActive")){e.data("isActive",!
0);this.pluginCount=aa+=1;e.prop("value")&&(g=e.prop("value").split(";"));"single"===a.typ
g&&1<g.length?("number"!==typeof a.min?a.min=parseFloat(g[0]):"number"!
==typeof a.from&&(a.from=parseFloat(g[0])),"number"!==typeof
a.max&&(a.max=parseFloat(g[1]))):g&&1===g.length&&"number"!==typeof
a.from&&(a.from=parseFloat(g[0])):"double"===a.type&&(g&&1<g.length?("number"!
==typeof a.min?Ð.min=parseFloat(g[0]):"number"!==typeof
a.from&&(a.from=parseFloat(g[0])),"number"!==typeof a.max?
a.max=parseFloat(g[1]):"number"!==typeof
a.to&&(a.to=parseFloat(g[1]))):g&&1===g.length&&("number"!==typeof a.min?
a.min=parseFloat(g[0]):"number"!==typeof
a.from&&(a.from=parseFloat(g[0]))));"number"===typeof
e.data("min")&&(a.min=parseFloat(e.data("min")));"number"===typeof
e.data("max")&&(a.max=parseFloat(e.data("max")));"number"===typeof
e.data("from")&&(a.from=parseFloat(e.data("from")));"number"===Ðtypeof e.data("
to")&&(a.to=parseFloat(e.data("to")));e.data("step")&&(a.step=parseFloat(e.dat
a("step")));e.data("type")&&(a.type=e.data("type"));e.data("prefix")&&(a.prefi
x=e.data("prefix"));e.data("postfix")&&(a.postfix=e.data("postfix"));e.data("m
axpostfix")&&(a.maxPostfix=e.data("maxpostfix"));e.data("hasgrid")&&(a.hasGrid
=e.data("hasgrid"));e.data("hideminmax")&&(a.hideMinMax=e.data("hideminmax"));
e.data("hidefromto")&&(a.hideFromTo=e.data("hidefromto"));e.data("prettify")&&
(a.prettify=e.data("prettify"));Ð.data("disable")&&(a.disable=e.data("disable"
));e.data("values")&&(a.values=e.data("values").split(","));a.min=N(a.min);a.m
in||0===a.min||(a.min=10);a.max=N(a.max);a.max||0===a.max||
(a.max=100);"[object Array]"!==Object.prototype.toString.call(a.values)&&(a.va
lues=null);a.values&&0<a.values.length&&(a.min=0,a.max=a.values.length-1,a.ste
p=1,I=!0);a.from=N(a.from);a.from||0===a.from||
(a.from=a.min);a.to=N(a.to);a.to||0===a.to||
(a.to=a.max);a.step=N(a.step);a.step||(a.step=1);a.from<a.min&&(a.from=Ð.min);
a.from>a.max&&(a.from=a.min);a.to<a.min&&(a.to=a.max);a.to>a.max&&(a.to=a.max)
;"double"===a.type&&(a.from>a.to&&(a.from=a.to),a.to<a.from&&(a.to=a.from));va
r z=function(b){b=b.toString();a.prettify&&(b=b.replace(/(\d{1,3}(?=(?:
\d\d\d)+(?!\d)))/g,"$1 "));return b},g='<span class="irs"
id="irs-'+this.pluginCount+'"></
span>';e[0].style.display="none";e.before(g);var
p=e.prev(),J=c(ea.body),T=c($),q,C,D,A,B,w,x,m,t,r,H,M,v=!1,y=!1,E=!
0,f={},U=0,O=0,P=0,l=0,F=0,G=0,V=0,Q=0,R=0,Y=0,u=0;parseInt(a.step,Ð10)!
==parseFloat(a.step)&&(u=a.step.toString().split(".")
[1],u=Math.pow(10,u.length));this.updateData=function(b){E=!0;a=c.extend(a,b);
p.find("*").off();T.off("mouseup.irs"+n.pluginCount);J.off("mouseup.irs"+n.plu
ginCount);J.off("mousemove.irs"+n.pluginCount);p.html("");ba()};this.removeSli
der=function(){p.find("*").off();T.off("mouseup.irs"+n.pluginCount);J.off("mou
seup.irs"+n.pluginCount);J.off("mousemove.irs"+n.pluginCount);p.html("").remov
e();e.data("isActive",!1);e.show()};var ba=function(){p.html('<span
class="irs"><span class="irs-line"><span class="irs-line-left"></span><span
class="irs-line-mid"></span><span class="irs-line-right"></span></span><span
class="irs-min">0</span><span class="irs-max">1</span><span class="irs-
from">0</span><span class="irs-to">0</span><span class="irs-single">0</span></
span><span class="irs-grid"></span>');Ð=p.find(".irs");C=q.find(".irs-
min");D=q.find(".irs-max");A=q.find(".irs-from");B=q.find(".irs-
```

```
to");w=q.find(".irs-single");M=p.find(".irs-grid");a.hideFromTo&&(A[0].style.v
isibility="hidden",B[0].style.visibility="hidden",w[0].style.visibility="hidde
n");a.hideFromTo||(A[0].style.visibility="visible",B[0].style.visibility="visi
ble",w[0].style.visibility="visible");a.hideMinMax&&(C[0].style.visibility="hi
dden",D[0].style.visibility="hidden",P=O=0);a.hideMinMax||
(C[0].style.visibility="visible",D[0].style.visibility=Ðvisible",a.values?(C.h
tml(a.prefix+a.values[0]+a.postfix),D.html(a.prefix+a.values[a.values.length-1
]+a.maxPostfix+a.postfix)):(C.html(a.prefix+z(a.min)+a.postfix),D.html(a.prefi
x+z(a.max)+a.maxPostfix+a.postfix)),O=C.outerWidth(),P=D.outerWidth());ga()},g
a=function(){if("single"===a.type){if(q.append('<span class="irs-slider
single"></span>'),x=q.find(".single"),x.on("mousedown",function(a)
{a.preventDefault();a.stopPropagation();K(a,c(this),null);y=v=!
0;s=n.pluginCount;S&&c("*").prop("unselectable",Ð
0)}),X)x.on("touchstart",function(a)
{a.preventDefault();a.stopPropagation();K(a.originalEvent.touches[0],c(this),null);y=v=!
0;s=n.pluginCount})}else"double"===a.type&&(q.append('<span class="irs-
diapason"></span><span class="irs-slider from"></span><span class="irs-slider
to"></span>'),m=q.find(".from"),t=q.find(".to"),H=q.find(".irs-
diapason"),L(),m.on("mousedown",function(a)
{a.preventDefault();a.stopPropagation();c(this).addClass("last");t.removeClass("last");K(a
0;s=n.pluginCount;Ð&&c("*").prop("unselectable",!
0)}),t.on("mousedown",function(a){a.preventDefault();a.stopPropagation();c(thi
s).addClass("last");m.removeClass("last");K(a,c(this),"to");y=v=!
0;s=n.pluginCount;S&&c("*").prop("unselectable",!
0)}),X&&(m.on("touchstart",function(a){a.preventDefault();a.stopPropagation();
c(this).addClass("last");t.removeClass("last");K(a.originalEvent.touches[0],c(
this),"from");y=v=!0;s=n.pluginCount}),t.on("touchstart",function(a)
{a.preventDefault();a.stopPropagation();c(this).addClass("last");Ð
m.removeClass("last");K(a.originalEvent.touches[0],c(this),"to");y=v=!
0;s=n.pluginCount})),a.to===a.max&&m.addClass("last"));J.on("mouseup.irs"+n.pluginCount,fu
{s===n.pluginCount&&v&&(v=y=!
1,r.removeAttr("id"),r=null,"double"===a.type&&L(),Z(),S&&c("*").prop("unselectable",!
1))});J.on("mousemove.irs"+n.pluginCount,function(a)
{v&&(U=a.pageX,W())});p.on("mousedown",function()
{s=n.pluginCount});p.on("mouseup",function(b){if(s===n.pluginCount&&!v&&!
a.disable){b=b.pageX;E=!1;b-=p.offset().left;Ðar d=f.fromX+(f.toX-
f.fromX)/2;Q=0;V=q.width()-G;R=q.width()-G;"single"===a.type?
(r=x,r.attr("id","irs-active-slider"),W(b)):"double"===a.type&&(r=b<=d?
m:t,r.attr("id","irs-active-
slider"),W(b),L());r.removeAttr("id");r=null}});X&&(T.on("touchend",function()
{v&&(v=y=!
1,r.removeAttr("id"),r=null,"double"===a.type&&L(),Z())}),T.on("touchmove",function(a)
{v&&(U=a.originalEvent.touches[0].pageX,W())}));ca();ha();a.hasGrid&&ia();a.disable?
(p.addClass("irs-disabled"),p.append('<span class="irs-disable-mask"></
span>')):Ðp.removeClass("irs-disabled"),p.find(".irs-disable-
mask").remove())},ca=function(){l=q.width();G=x?x.width():m.width();F=l-
G},K=function(b,d,h){ca();E=!1;r=d;r.attr("id","irs-active-
slider");d=r.offset().left;Y=d+(b.pageX-d)-
r.position().left;"single"===a.type?V=q.width()-
G:"double"===a.type&&("from"===h?(Q=0,R=parseInt(t.css("left"),10)):
(Q=parseInt(m.css("left"),10),R=q.width()-G))},L=function(){var
a=m.width(),d=c.data(m[0],"x")||parseInt(m[0].style.left,10)||
m.position().left,h=(c.data(t[0],Ðx")||parseInt(t[0].style.left,10)||
t.position().left)-
d;H[0].style.left=d+a/2+"px";H[0].style.width=h+"px"},W=function(b){var d=U-
Y,d=b?b:U-Y;"single"===a.type?(0>d&&(d=0),d>V&&(d=V)):"double"===a.type&&(d<Q&
&(d=Q),d>R&&(d=R),L());c.data(r[0],"x",d);Z();b=Math.round(d);r[0].style.left=
b+"px"},Z=function(){var b={input:e,slider:p,min:a.min,max:a.max,fromNumber:0,
toNumber:0,fromPers:0,toPers:0,fromX:0,fromX_pure:0,toX:0,toX_pure:0},d=a.max-
a.min,h;"single"===a.type?(b.fromX=c.data(x[0],"x")||parseInt(x[0].style.left,Ð
```

```
10)||x.position().left,b.fromPers=b.fromX/
F*100,h=d/100*b.fromPers+a.min,b.fromNumber=Math.round(h/
a.step)*a.step,b.fromNumber<a.min&&(b.fromNumber=a.min),b.fromNumber>a.max&&(b.fromNumber=
u),I&&(b.fromValue=a.values[b.fromNumber])):"double"===a.type&&(b.fromX=c.data(m[0],"x")||
parseInt(m[0].style.left,10)||m.position().left,b.fromPers=b.fromX/
F*100,h=d/100*b.fromPers+a.min,b.fromNumber=Math.round(h/
a.step)*a.step,b.fromNumber<a.min&&(b.fromNumber=Ð
a.min),b.toX=c.data(t[0],"x")||parseInt(t[0].style.left,10)||
t.position().left,b.toPers=b.toX/
F*100,d=d/100*b.toPers+a.min,b.toNumber=Math.round(d/
a.step)*a.step,b.toNumber>a.max&&(b.toNumber=a.max),u&&(b.fromNumber=parseInt(b.fromNumber
u,b.toNumber=parseInt(b.toNumber*u,10)/
u),I&&(b.fromValue=a.values[b.fromNumber],b.toValue=a.values[b.toNumber]));f=b;da()},ha=fu
{var
b={input:e,slider:p,min:a.min,max:a.max,fromNumber:a.from,toNumber:a.to,fromPers:0,toPers:
toX_pure:0},d=a.max-a.min;"single"===a.type?(b.fromPers=0!==d?(b.fromNumber-
a.min)/
d*100:0,b.fromX_pure=F/100*b.fromPers,b.fromX=Math.round(b.fromX_pure),x[0].style.left=b.f
==d?(b.fromNumber-a.min)/
d*100:0,b.fromX_pure=F/100*b.fromPers,b.fromX=Math.round(b.fromX_pure),m[0].style.left=b.f
==d?(b.toNumber-a.min)/
d*100:1,b.toX_pure=F/100*b.toPers,b.toX=Math.round(b.toX_pure),t[0].style.left=Ð
b.toX+"px",c.data(t[0],"x",b.toX_pure),L());f=b;da()},da=function(){var
b,d,h,c,g,k;k=G/2;h="";"single"===a.type?(h=f.fromNumber===a.max?
a.maxPostfix:"",A[0].style.display="none",B[0].style.display="none",h=I?
a.prefix+a.values[f.fromNumber]+h+a.postfix:a.prefix+z(f.fromNumber)+h+a.postfix,w.html(h)
g/2+k,0>k&&(k=0),k>l-g&&(k=l-g),w[0].style.left=k+"px",a.hideMinMax||
a.hideFromTo||(C[0].style.display=k<O?"none":"block",D[0].style.display=k+g>l-
P?"none":"block"),e.attr("value",Ð
parseFloat(f.fromNumber))):"double"===a.type&&(h=f.toNumber===a.max?
a.maxPostfix:"",I?
(b=a.prefix+a.values[f.fromNumber]+a.postfix,d=a.prefix+a.values[f.toNumber]+h+a.postfix,h
==f.toNumber?a.prefix+a.values[f.fromNumber]+" \u2014
"+a.prefix+a.values[f.toNumber]+h+a.postfix:a.prefix+a.values[f.fromNumber]+h+a.postfix):
(b=a.prefix+z(f.fromNumber)+a.postfix,d=a.prefix+z(f.toNumber)+h+a.postfix,h=f.fromNumber!
==f.toNumber?a.prefix+z(f.fromNumber)+" \u2014
"+a.prefix+z(f.toNumber)+h+a.postfix:Ð
a.prefix+z(f.fromNumber)+h+a.postfix),A.html(b),B.html(d),w.html(h),b=A.outerWidth(),d=f.f
b/2+k,0>d&&(d=0),d>l-b&&(d=l-
b),A[0].style.left=d+"px",h=B.outerWidth(),c=f.toX-h/2+k,0>c&&(c=0),c>l-
h&&(c=l-h),B[0].style.left=c+"px",g=w.outerWidth(),k=f.fromX+(f.toX-
f.fromX)/2-g/2+k,0>k&&(k=0),k>l-g&&(k=l-g),w[0].style.left=k+"px",d+b<c?
(w[0].style.display="none",A[0].style.display="block",B[0].style.display="block"):
(w[0].style.display="block",A[0].style.display="none",B[0].style.display="none"),a.hideMin
a.hideFromTo||(C[0].style.display=k<O||
d<O?"none":"block",D[0].style.display=k+g>l-P||c+h>l-
P?"none":"block"),e.attr("value",parseFloat(f.fromNumber)+";"+parseFloat(f.toNumber)));ja(
{"function"!==typeof a.onFinish||y||E||a.onFinish.call(this,f);"function"!
==typeof a.onChange||E||a.onChange.call(this,f);"function"===typeof
a.onLoad&&!y&&E&&(a.onLoad.call(this,f),E=!1)},ia=function(){p.addClass("irs-
with-grid");var
b,d="",c=0,c=0,e="";for(b=0;20>=b;b+=1)c=Math.floor(l/20*b),c>=l&&(c=Ð
l-1),e+='<span class="irs-grid-pol small" style="left: '+c+'px;"></
span>';for(b=0;4>=b;b+=1)c=Math.floor(l/4*b),c>=l&&(c=l-1),e+='<span
class="irs-grid-pol" style="left: '+c+'px;"></span>',u?(d=a.min+(a.max-
a.min)/4*b,d=d/a.step*a.step,d=parseInt(d*u,10)/u):(d=Math.round(a.min+(a.max-
a.min)/4*b),d=Math.round(d/a.step)*a.step,d=z(d)),I&&(a.hideMinMax?
(d=Math.round(a.min+(a.max-a.min)/4*b),d=Math.round(d/a.step)*a.step,d=0===b||
4===b?a.values[d]:""):d=""),0===b?e+='<span class="irs-grid-text"
style="left: '+Ð
```

```
                c+'px; text-align: left;">'+d+"</span>":4===b?(c-
=100,e+='<span class="irs-grid-text" style="left: '+c+'px; text-align:
right;">'+d+"</span>"):(c-=50,e+='<span class="irs-grid-text" style="left:
'+c+'px;">'+d+"</span>");M.html(e)};ba()}})},update:function(c){return
this.each(function(){this.updateData(c)})},remove:function(){return
this.each(function(){this.removeSlider()})}};c.fn.ionRangeSlider=function(s)
{if(H[s])return
H[s].apply(this,Array.prototype.slice.call(arguments,1));if("object"!==typeof
s&&s)c.error("Method "+s+" does not exist for jQuery.ionRangeSlider");else
return H.init.apply(this,arguments)}})(jQuery,document,window,navigator);
```

public\assets\js\plugins\jeditable\jquery.jeditable.js

```
/*Ð* Jeditable - jQuery in place edit pluginÐ*Ð* Copyright (c) 2006-2009 Mika
Tuupola, Dylan VerheulÐ*Ð* Licensed under the MIT license:Ð*   http://
www.opensource.org/licenses/mit-license.phpÐ*Ð* Project home:Ð*   http://
www.appelsiini.net/projects/jeditableÐ*Ð* Based on editable by Dylan Verheul
<dylan_at_dyve.net>:Ð*    http://www.dyve.net/jquery/?editableÐ*Ð*/Ð**Ð*
Version 1.7.1Ð*Ð* ** means there is basic unit tests for this parameter.Ð*Ð*
@name  JeditableÐ* @type  jQueryÐ* @param String  target             (POST)
URL or function to send edited content to **Ð* @param Hash
options            additional optionsÐ* @param String  options[method]
method to use to send edited content (POST or PUT) **Ð* @param Function
options[callback] Function to run after submitting edited content **Ð* @param
String  options[name]      POST parameter name of edited contentÐ* @param
String  options[id]        POST parameter name of edited div idÐ* @param
Hash    options[submitdata] Extra parameters to send when submitting edited
content.Ð* @param String  options[type]      text, textarea or select (or any
3rd party input type) **Ð* @param Integer options[rows]      number of rows
if using textarea **Ð* @param Integer options[cols]      number of columns if
using textarea **Ð* @param Mixed   options[height]    'auto', 'none' or
height in pixels **Ð* @param Mixed   options[width]     'auto', 'none' or
width in pixels **Ð* @param String  options[loadurl]   URL to fetch input
content before editing **Ð* @param String  options[loadtype]  Request type
for load url. Should be GET or POST.Ð* @param String  options[loadtext]  Text
to display while loading external content.Ð* @param Mixed
options[loaddata]  Extra parameters to pass when fetching content before
editing.Ð* @param Mixed   options[data]      Or content given as paramameter.
String or function.**Ð* @param String  options[indicator] indicator html to
show when savingÐ* @param String  options[tooltip]   optional tooltip text
via title attribute **Ð* @param String  options[event]     jQuery event such
as 'click' of 'dblclick' **Ð* @param String  options[submit]    submit button
value, empty means no button **Ð* @param String  options[cancel]    cancel
button value, empty means no button **Ð* @param String  options[cssclass]
CSS class to apply to input form. 'inherit' to copy from parent. **Ð* @param
String  options[style]     Style to apply to input form 'inherit' to copy
from parent. **Ð* @param String  options[select]    true or false, when true
text is highlighted ??Ð* @param String  options[placeholder] Placeholder text
or html to insert when element is empty. **Ð* @param String
options[onblur]    'cancel', 'submit', 'ignore' or function ??Ð*Ð* @param
Function options[onsubmit] function(settings, original) { ... } called before
submitÐ* @param Function options[onreset]  function(settings, original)
{ ... } called before resetÐ* @param Function options[onerror]
function(settings, original, xhr) { ... } called on errorÐ*Ð* @param Hash
options[ajaxoptions]  jQuery Ajax options. See docs.jquery.com.Ð*Ð*/Ð
(function($) {Ð   $.fn.editable = function(target, options) {Ð       if
('disable' == target) {Ð           $(this).data('disabled.editable', true);Ð
            return;Ð       }Ð       if ('enable' == target) {Ð
$(this).data('disabled.editable', false);Ð           return;Ð       }Ð
if ('destroy' == target) {Ð           $(this)Ð
                .unbind($(this).data('event.editable'))Ð
                .removeData('disabled.editable')Ð
                .removeData('event.editable');Ð           return;Ð       }Ð
        var settings = $.extend({}, $.fn.editable.defaults, {target:target},
options);Ð       /* setup some functions */Ð       var plugin   =
$.editable.types[settings.type].plugin || function() { };Ð       var submit
= $.editable.types[settings.type].submit || function() { };Ð       var
buttons  = $.editable.types[settings.type].buttonsÐ           ||
$.editable.types['defaults'].buttons;Ð       var content  =
$.editable.types[settings.type].contentÐ           ||
$.editable.types['defaults'].content;Ð       var element  =
$.editable.types[settings.type].elementÐ
```

```
                                                    ||
$.editable.types['defaults'].element;Ð       var reset    =
$.editable.types[settings.type].resetÐ           ||
$.editable.types['defaults'].reset;Ð       var callback = settings.callback
|| function() { };Ð       var onedit   = settings.onedit   || function() { };Ð
        var onsubmit = settings.onsubmit || function() { };Ð       var
onreset  = settings.onreset  || function() { };Ð       var onerror  =
settings.onerror  || reset;Ð       /* show tooltip */Ð       if
(settings.tooltip) {Ð           $(this).attr('title', settings.tooltip);Ð
        }Ð       settings.autowidth  = 'auto' == settings.width;Ð
settings.autoheight = 'auto' == settings.height;Ð       return
this.each(function() {Ð           /* save this to self because this changes
when scope changes */Ð           var self = this;Ð           /* inlined block
elements lose their width and height after first edit */Ð           /* save
them for later use as workaround */Ð           var savedwidth  =
$(self).width();Ð           var savedheight = $(self).height();Ð           /*
save so it can be later used by $.editable('destroy') */Ð
$(this).data('event.editable', settings.event);Ð           /* if element is
empty add something clickable (if requested) */Ð           if (!
$.trim($(this).html())) {Ð               $(this).html(settings.placeholder);Ð
            }Ð           $(this).bind(settings.event, function(e) {Ð
                /* abort if disabled for this element */Ð               if
(true === $(this).data('disabled.editable')) {Ð                    return;Ð
                }Ð               /* prevent throwing an exeption if edit
field is clicked again */Ð               if (self.editing) {Ð
                    return;Ð               }Ð               /* abort if
onedit hook returns false */Ð               if (false === onedit.apply(this,
[settings, self])) {Ð                    return;Ð               }Ð
                /* prevent default action and bubbling */Ð
e.preventDefault();Ð               e.stopPropagation();Ð               /*
remove tooltip */Ð               if (settings.tooltip) {Ð
$(self).removeAttr('title');Ð               }Ð               /* figure out
how wide and tall we are, saved width and height */Ð               /* are
workaround for http://dev.jquery.com/ticket/2190 */Ð               if (0 ==
$(self).width()) {Ð                    //$(self).css('visibility', 'hidden');Ð
                    settings.width  = savedwidth;Ð
settings.height = savedheight;Ð               } else {Ð                    if
(settings.width != 'none') {Ð                        settings.width =Ð
                            settings.autowidth ? $(self).width()  :
settings.width;Ð                    }Ð                    if (settings.height !
= 'none') {Ð                        settings.height =Ð
                            settings.autoheight ? $(self).height() :
settings.height;Ð                    }Ð               }Ð               //
$(this).css('visibility', '');Ð               /* remove placeholder text,
replace is here because of IE */Ð               if
($(this).html().toLowerCase().replace(/(;|")/g, '') ==Ð
settings.placeholder.toLowerCase().replace(/(;|")/g, '')) {Ð
                    $(this).html('');Ð               }Ð
self.editing    = true;Ð               self.revert     = $(self).html();Ð
                $(self).html('');Ð               /* create the form object */Ð
                var form = $('<form />');Ð               /* apply css or
style or both */Ð               if (settings.cssclass) {Ð
if ('inherit' == settings.cssclass) {Ð
form.attr('class', $(self).attr('class'));Ð                    } else {Ð
                        form.attr('class', settings.cssclass);Ð
                    }Ð               }Ð               if (settings.style) {Ð
                    if ('inherit' == settings.style) {Ð
form.attr('style', $(self).attr('style'));Ð                        /* IE needs
the second line or display wont be inherited */Ð
form.css('display', $(self).css('display'));Ð
```

```
                                                                    } else {Ð
                        form.attr('style', settings.style);Ð
                    }Ð               }Ð               /* add main input
element to form and store it in input */Ð               var input =
element.apply(form, [settings, self]);Ð               /* set input content
via POST, GET, given data or existing value */Ð               var
input_content;Ð               if (settings.loadurl) {Ð                 var
t = setTimeout(function() {Ð                      input.disabled = true;Ð
                        content.apply(form, [settings.loadtext, settings,
self]);Ð                    }, 100);Ð                 var loaddata = {};Ð
                    loaddata[settings.id] = self.id;Ð                 if
($.isFunction(settings.loaddata)) {Ð                      $.extend(loaddata,
settings.loaddata.apply(self, [self.revert, settings]));Ð                 }
else {Ð                      $.extend(loaddata, settings.loaddata);Ð
                    }Ð                  $.ajax({Ð
type : settings.loadtype,Ð                      url  : settings.loadurl,Ð
                        data : loaddata,Ð                      async : false,Ð
                        success: function(result) {Ð
                            window.clearTimeout(t);Ð
                            input_content = result;Ð
                            input.disabled = false;Ð                      }Ð
                    });Ð               } else if (settings.data) {Ð
                    input_content = settings.data;Ð                 if
($.isFunction(settings.data)) {Ð                      input_content =
settings.data.apply(self, [self.revert, settings]);Ð                 }Ð
                } else {Ð                  input_content = self.revert;Ð
                }Ð               content.apply(form, [input_content,
settings, self]);Ð               input.attr('name', settings.name);Ð
                /* add buttons to the form */Ð
buttons.apply(form, [settings, self]);Ð               /* add created form to
self */Ð               $(self).append(form);Ð               /* attach 3rd
party plugin if requested */Ð               plugin.apply(form, [settings,
self]);Ð               /* focus to first visible form element */Ð
                $(':input:visible:enabled:first', form).focus();Ð
                /* highlight input contents when requested */Ð
if (settings.select) {Ð                  input.select();Ð               }Ð
                /* discard changes if pressing esc */Ð
input.keydown(function(e) {Ð                  if (e.keyCode == 27) {Ð
                        e.preventDefault();Ð                      //
self.reset();Ð                      reset.apply(form, [settings, self]);Ð
                    }Ð               });Ð               /* discard, submit or
nothing with changes when clicking outside */Ð               /* do nothing is
usable when navigating with tab */Ð               var t;Ð               if
('cancel' == settings.onblur) {Ð                  input.blur(function(e) {Ð
                        /* prevent canceling if submit was clicked */Ð
                        t = setTimeout(function() {Ð
                            reset.apply(form, [settings, self]);Ð
                        }, 500);Ð                  });Ð               } else
if ('submit' == settings.onblur) {Ð                  input.blur(function(e) {Ð
                        /* prevent double submit if submit was clicked */Ð
                        t = setTimeout(function() {Ð
                            form.submit();Ð                      }, 200);Ð
                    });Ð               } else if
($.isFunction(settings.onblur)) {Ð                  input.blur(function(e) {Ð
                        settings.onblur.apply(self, [input.val(), settings]);Ð
                    });Ð               } else {Ð
input.blur(function(e) {Ð                      /* TODO: maybe something here
*/Ð                  });Ð               }Ð
form.submit(function(e) {Ð                  if (t) {Ð
clearTimeout(t);Ð
```

```
                                    }Ð                    /* do no submit */Ð
                    e.preventDefault();Ð                    /* call before
submit hook. */Ð                  /* if it returns false abort submitting */Ð
                    if (false !== onsubmit.apply(form, [settings, self])) {Ð
                        /* custom inputs call before submit hook. */Ð
                        /* if it returns false abort submitting */Ð
                        if (false !== submit.apply(form, [settings, self])) {Ð
                            /* check if given target is function */Ð
                            if ($.isFunction(settings.target)) {Ð
                                var str = settings.target.apply(self,
[input.val(), settings]);Ð                              $(self).html(str);Ð
                                self.editing = false;Ð
                                callback.apply(self, [self.innerHTML,
settings]);Ð                            /* TODO: this is not dry */Ð
                                if (!$.trim($(self).html())) {Ð
                                    $(self).html(settings.placeholder);Ð
                                }Ð                          } else {Ð
                                /* add edited content and id of edited
element to POST */Ð                                var submitdata = {};Ð
                                submitdata[settings.name] = input.val();Ð
                                submitdata[settings.id] = self.id;Ð
                                /* add extra data to be POST:ed */Ð
                                if ($.isFunction(settings.submitdata)) {Ð
                                    $.extend(submitdata,
settings.submitdata.apply(self, [self.revert, settings]));Ð
                                } else {Ð
$.extend(submitdata, settings.submitdata);Ð                                }Ð
                                /* quick and dirty PUT support */Ð
                                if ('PUT' == settings.method) {Ð
                                    submitdata['_method'] = 'put';Ð
                                }Ð                                /* show the
saving indicator */Ð
$(self).html(settings.indicator);Ð                                /* defaults
for ajaxoptions */Ð                               var ajaxoptions = {Ð
                                    type    : 'POST',Ð
                                    data    : submitdata,Ð
                                    dataType: 'html',Ð
                                    url     : settings.target,Ð
                                    success : function(result, status) {Ð
                                        if (ajaxoptions.dataType == 'html') {Ð
                                            $(self).html(result);Ð
                                        }Ð
                                        self.editing = false;Ð
                                        callback.apply(self, [result,
settings]);Ð                                        if (!
$.trim($(self).html())) {Ð
$(self).html(settings.placeholder);Ð                                        }Ð
                                    },Ð
error   : function(xhr, status, error) {Ð
                                        onerror.apply(form, [settings, self,
xhr]);Ð                                  }Ð                              };Ð
                                /* override with what is given in
settings.ajaxoptions */Ð                                $.extend(ajaxoptions,
settings.ajaxoptions);Ð                                $.ajax(ajaxoptions);Ð
                        }Ð                        }Ð                  }Ð
                    /* show tooltip again */Ð
$(self).attr('title', settings.tooltip);Ð                  return false;Ð
                });Ð           });Ð           /* privileged methods */Ð
            this.reset = function(form) {Ð               /* prevent calling
reset twice when blurring */Ð
```

```
                                        if (this.editing) {Ð
                    /* before reset hook, if it returns false abort reseting
*/Ð                   if (false !== onreset.apply(form, [settings, self])) {Ð
                        $(self).html(self.revert);Ð
self.editing   = false;Ð                        if (!$.trim($(self).html())) {Ð
                            $(self).html(settings.placeholder);Ð
                        }Ð                      /* show tooltip again */Ð
                        if (settings.tooltip) {Ð
$(self).attr('title', settings.tooltip);Ð                          }Ð
                    }Ð              }Ð          };Ð       });Ð   };Ð
$.editable = {Ð       types: {Ð           defaults: {Ð
element : function(settings, original) {Ð                    var input =
$('<input type="hidden"></input>');Ð                   $(this).append(input);Ð
                    return(input);Ð              },Ð               content :
function(string, settings, original) {Ð                    $(':input:first',
this).val(string);Ð              },Ð               reset :
function(settings, original) {Ð                    original.reset(this);Ð
                },Ð              buttons : function(settings, original) {Ð
                    var form = this;Ð                   if (settings.submit) {Ð
                        /* if given html string use that */Ð
                        if (settings.submit.match(/>$/)) {Ð
                            var submit = $(settings.submit).click(function() {Ð
                                if (submit.attr("type") != "submit") {Ð
                                    form.submit();Ð
                                }Ð                          });Ð
                            /* otherwise use button with given string as text
*/Ð                       } else {Ð                           var submit =
$('<button type="submit" />');Ð
submit.html(settings.submit);Ð                        }Ð
$(this).append(submit);Ð                    }Ð                    if
(settings.cancel) {Ð                        /* if given html string use that */Ð
                        if (settings.cancel.match(/>$/)) {Ð
                            var cancel = $(settings.cancel);Ð
                            /* otherwise use button with given string as text
*/Ð                       } else {Ð                           var cancel =
$('<button type="cancel" />');Ð
cancel.html(settings.cancel);Ð                        }Ð
$(this).append(cancel);Ð
$(cancel).click(function(event) {Ð                          //
original.reset();Ð                          if
($.isFunction($.editable.types[settings.type].reset)) {Ð
                                var reset =
$.editable.types[settings.type].reset;Ð                           } else {Ð
                                var reset =
$.editable.types['defaults'].reset;Ð                          }Ð
                            reset.apply(form, [settings, original]);Ð
                            return false;Ð                      });Ð
                    }Ð              }Ð          },Ð          text: {Ð
                element : function(settings, original) {Ð
var input = $('<input />');Ð                   if (settings.width  != 'none')
{ input.width(settings.width);  }Ð                   if (settings.height !=
'none') { input.height(settings.height); }Ð                    /* https://
bugzilla.mozilla.org/show_bug.cgi?id=236791 */Ð                    //
input[0].setAttribute('autocomplete','off');Ð
input.attr('autocomplete','off');Ð                   $(this).append(input);Ð
                    return(input);Ð              }Ð          },Ð
textarea: {Ð              element : function(settings, original) {Ð
                    var textarea = $('<textarea />');Ð                   if
(settings.rows) {Ð                      textarea.attr('rows', settings.rows);Ð
                    } else if (settings.height != "none") {Ð
```

```
                        textarea.height(settings.height);Ð                    }Ð
                    if (settings.cols) {Ð
textarea.attr('cols', settings.cols);Ð                    } else if
(settings.width != "none") {Ð
textarea.width(settings.width);Ð                    }Ð
$(this).append(textarea);Ð                    return(textarea);Ð
                }Ð           },Ð           select: {Ð               element :
function(settings, original) {Ð                    var select = $('<select /
>');Ð                    $(this).append(select);Ð
return(select);Ð                },Ð               content : function(data,
settings, original) {Ð                    /* If it is string assume it is
json. */Ð                    if (String == data.constructor) {Ð
                        eval ('var json = ' + data);Ð                    }
else {Ð                        /* Otherwise assume it is a hash already. */Ð
                        var json = data;Ð                    }Ð
                    for (var key in json) {Ð                        if (!
json.hasOwnProperty(key)) {Ð                        continue;Ð
                        }Ð                    if ('selected' == key) {Ð
                            continue;Ð                        }Ð
                        var option = $('<option /
>').val(key).append(json[key]);Ð                        $('select',
this).append(option);Ð                    }Ð                        /* Loop option
again to set selected. IE needed this... */Ð                        $('select',
this).children().each(function() {Ð                        if ($(this).val()
== json['selected'] ||Ð                        $(this).text() ==
$.trim(original.revert)) {Ð
$(this).attr('selected', 'selected');Ð                        }Ð
                    });Ð                }Ð            }Ð        },Ð        /* Add
new input type */Ð        addInputType: function(name, input) {Ð
$.editable.types[name] = input;Ð        }Ð    };Ð    // publicly accessible
defaultsÐ    $.fn.editable.defaults = {Ð        name        : 'value',Ð
id          : 'id',Ð        type        : 'text',Ð        width       : 'auto',Ð
        height      : 'auto',Ð        event       : 'click.editable',Ð
onblur      : 'cancel',Ð        loadtype    : 'GET',Ð        loadtext    :
'Loading...',Ð        placeholder: 'Click to edit',Ð        loaddata    : {},Ð
        submitdata : {},Ð        ajaxoptions: {}Ð    };Ð})(jQuery);
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-ar.js

```
;(function($){Ð**Ð* jqGrid Arabic TranslationÐ* Ð* http://trirand.com/blog/ Ð
* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/
licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid =
$.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "b¦3bÆJdB ³ Ò Ò ³™Ò 9dFI {2}",Ð
emptyrecords: "dF' ™Ò¢Ò¢ÒÒ¢ÒÒ¢ÒÒ
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-bg.js

```
;(function($){Ð**Ð* jqGrid Bulgarian Translation Ð* Tony Tomov
tony@trirand.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "{0} - {1} CäB {2} ™Ð
Ct0CÔ8Da„8è™Ð "At0D™ÐCÄ4<:."B,ÐD â ³ Ò–ÒÍÓV³&Ò, ¢ ™caption: "B$JD™ACÄ4C™AÂÔ0CÄ5D 8",Ð
Reset: "A„7DÄ8DaBC[{Íoper:'eq', text:"D 0C$=Câ'ÒÇ² ÷ W#¢væRrÂ FW‡C¢$@C 7C´8Dt=Câ'ÒÇ² ÷ W#¢
text:"Cô>-CÄ0C´:Câ'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢$?CâÔ<C ;C¤> C„;C‚Ò'ÒÇ² ÷ W#¢vwBrÂ FW‡C¢$?CâÔ3Cä;Dô
C4>C´OCÄ> C„;C, Ò'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢$7C ?CäGC$0 D 'ÒÇ² ÷ W#¢v&ârÂ FW‡C¢$=CR 7C ?CäGC$0 D
{ oper:'ni', text:"CÔ5 D 5 CÔ0CÄ8D 0 C"'ÒÇ² ÷ W#¢vWrrÂ FW‡C¢$7C 2D¤@D„2C  A"},{ oper:'en',
{ oper:'cn', text:"D JCDJD 6C 'ÒÇ² ÷ W#¢væ2rÂ FW‡C¢$=CR AD¤4D¤@Cd0"},{ oper:'nu', text:'CR
{ oper:'nn', text:'CÔ5 CR åTÄÂwÕÔÍw&÷W ÷ 3¢ ¹{ op: "AND", text: " A, " ÒÉ
{ op: "OR",  text: "A„ A, ™oper:™andTitle : "AÔ0D$8D™eCet7C™tle0Ct1CÄ@™ÔÔ™BBAC™™AD$>CBäCÄAD$BC
addCaption: "AÔ>C™edi™CapÄ™AÔ„Ð "B ™ÐDÔ™mÐC„O"At0CÄ8D„8Í,ÐA™7DÄ™eCB:Í"At0Ä™2DÄ@C„"Í
"AD0CÔ=C„BCRbÄ™es ?D"AÔÄ™ÔÔ5CÔÄ0CÄ™ÄÄ™tD:JD™Ä@Ä™gD0{™Ä™W ™D&™VCÄ$CÔÄ™Ä™Ä™$CÄ™D™2D™J™CÄ™BC™RC™ÇÔ™"
minValue:"D BCä9CÔ>D™BÔ$™fD$™D™0$™Ä™$>CÔ™CÄ™D™BÄ™Ä™Ä™=D™<™C™8™C™8™Ä™=™Ä™8™4™Ä™8™Ä™2™C™4™Ä™
C$0C™-™CÄ™C&R4™CÄ™2C"ÍC„4CT= URL. A„7C„AC¤0C$0™Ðæ5FV™C™@™VÐC¢:Ð 5v™CÄ™Ä™5™Ä™8™Ä™ 0™Ä™5;™Ä™0)™C$0™
D BCä™W™FÔÖB!&,Ð ¢ $ CäBD 5C™-™W$™ÐÄ™C™FV™60 D$™ÐD™1BÄ™05C™Ä™Ä™5™W™A™C™Ä™C™Ä™2™Ä™8™Ä™7™6™C™6™DBC76C?
bClose: "A±ÒÍ™ÐÄ@C™eaption: "A™mÐ@C„2D0=CR™7D$™Ðm™tC´8A™7™8™0™C™9™-™C™Ä™8™7™C™6™A?",Ð
edittext: " ",Ðedittitle: "B 5™ÐÄ™E™t0"C„™Ðd™C™i™l™t0™ÄÐ™C™d™C™E™0™Ä™5 ™C™Ô™7™C™Ð 7C ?C„A",Ð
deltitle: "A„7D$™Ðea™2C™h™CRt8Ct1D™ÐÄ™eÄ™7™t™1C„A",ÐB$JD™ACT™CRh™ext™C„A(™Ð'"Í
refreshtitle: "Aä1™Ä™1™C™8™C™ap0™C™AC™Ä™C™4™Ä™2™t5™C™AÄ™C™Ä™C™5™C™e™W™C™t5D™5™W™5™e™t™C™1™D "Ä™@™Ä™3C´5CB 8Ct1
col : {Ðcaption: "A„™7D™5™D™8™t™C¤™A™b™C™ÐÄ™eÐ: "AÒ™ÍW™8™B™2™Ð¢ ™errcap : "A4™0™H™C¤™0™"™AÔOCÄ0 Cô>D >
url C 4™D™5™CÄ™Ä™ds: "AÔOCÄ™0™1™0™C™8™DAÄ™7™CD™5™Ä™6™@™Ä™5™Ä™W™C™Ä™B™Ä™8™Ä™9™D$2C  =C  8CÄ5CÔ0D$0!"•
{thousandsSeparator: " ", defaultValue: '0'},Ðnumber : {decimalSeparator:".",
thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},Ðcurrency :
{decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "",
suffix:" C´2.", defaultValue: '0.00™ÐaÐe : {™ÐF ”æ ÖW3¢  ™"AÔ5CB"Â $ Cä=", "A$B", "B @", "
"AÔ5D""Â ™$AÔ™ÐC™5D´O", "Aô>CÔ5CD5C™=Ó¡ÍÓ¡F„Â$™Ðw™a™C™8™B™O™Ä™2$™ÂD$™DC™2", "™BÄ™D$™2™Ä™@™D$™C™2"™Â™$AÄ™CB
"A 2C2"Â $!CT?", "Aä:™DBÓÄ™D$™0™Dä™2", "™BD5C$™ÐÄ40D 8", "AÄ0D B", "A ?D™8™Ó™1"Ä ™ ™ C 9", "Bä=C,"Â $
["","","","","],Ð•3¢ gVæ7F–öâ †¢’™½if(j==7 || j==8 || j== 27 || j== 28) {Ð&WGW&â
'CÄ8™™™Ðeturn ['C$8', 'D 8', 'D$8'][Math.min((j - 1)™%™Í™0™&™2™}™ÇÐ™DC¢ u’ÓÒÖBr™Í
newformat: 'd/m/Y',Ð™—  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÕÖ™ÍÍÖ 6·2 ¢ ™ISO8601Long:"Y-m-d
H:i:s",Ð™ISO8601Short:"Y-m-d™™™,Ðhort™Date: "n/j/Y™™,ÐongDate: "l, F d, Y™™™,Ð
FullDateTime: "l, F d, Y g:i:s A",Ð™MonthDay: "F d™™™,ÐhortTime: "g:i A™™™,Ð
LongTime: "g:i:s A",Ð™SortableDateTime: "Y-m-d\\TH:i:s™™™,Ð
UniversalSortableDateTime: "Y-m-d H:i:sO",Ð™YearMonth: "F, Y™™™,Ð™™™Í
reformatAfterEdit : falseÐ},Ð™aseLinkUrl: '',Ð™howAction: '',Ðarget: '',Ð
checkbox : {disabled:true},ÐidName : 'id™™™,Ð});Ð})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-bg1251.js

```
;(function($){Ð**Ð* jqGrid Bulgarian Translation Ð* Tony Tomov
tony@trirand.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "{0} - {1} ÿýÿý {2}™ÐrecordsÐ: "ÿýÿýÿýÿý
ÿýÿýÿý™ÿýÿýÿýÿý"™Ð ÿýÿý™ÿýÿýÿýÿýÿýÿýÐ {0}-{1}™Ð™caption: "ÿýÿý™ÿýÿýÿýÿýÿýÿýÿýÿýÐ",
Reset: "ÿýÿý™ÿýÿýÿýÿýÿýÿýÐ", Ðr:'eq', text:'ÿýÿýÿýÿýÿý'}, { oper:'ne', text:'ÿýÿýÿýÿýÿýÿýÿýÿýÿý'}
text:'ÿýÿý-ÿýÿýÿýÿýÿý'}, { oper:'le', text:'ÿýÿý-ÿýÿýÿýÿýÿý ÿýÿýÿý='},{ oper:'gt', text:'ÿ
text:'ÿýÿý-ÿýÿýÿýÿýÿýÿý ÿýÿýÿý ='}, { oper:'bw', text:'ÿýÿýÿýÿýÿýÿýÿý ÿý'},{ oper:'bn', te
text:'ÿýÿý ÿýÿýÿýÿýÿýÿý ÿý'},{ oper:'ni', text:'ÿýÿý ÿýÿý ÿýÿýÿýÿýÿýÿý ÿý'},{ oper:'ew', t
text:'ÿýÿý ÿýÿýÿýÿýÿýÿýÿýÿýÿý ÿý'},,{ oper:'cn', text:'ÿýÿýÿýÿýÿýÿýÿýÿý™ÿýW}÷ 3¢ ™oper:'nc', tex
{ op: "AND", text: " ÿý " },—² ÷ ¢ $õ""Â  FW‡C¢ /ÿßÿßÿß
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-cat.js

```
;(function($){Ð**Ð* jqGrid Catalan TranslationÐ* Traducció jqGrid en Catatà
per Faserline, S.L.Ð* http://www.faserline.comÐ* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "Mostrant {0} - {1} de {2}",Ð
emptyrecords: "Sense registres que mostrar",™loadtext: "Carregant...",™Ðgtext :
"Pàgina {0} de {1}"ÐÒÍ6V &6, ¢ ™caption: "Cerca...",™Ðind: "Cercar",™Ðreset:
"Buidar",Ð    öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢&W V Â'ÒÇ² ÷ W#¢væRrÂ FW‡C¢&æ÷B
equal"},{ oper:'lt', text:"less"},{ oper:'le', text:"less or equal"},
{ oper:'gt', text:"greater"},{ oper:'ge', text:"greater or equal"},
{ oper:'bw', text:"begins with"},{ oper:'bn', text:"does not begin with"},
{ oper:'in', text:"is in"},{ oper:'ni', text:"is not in"},{ oper:'ew',
text:"ends with"},{ oper:'en', text:"does not end with"},{ oper:'cn',
text:"contains"},{ oper:'nc', text:"does not contain"},{ oper:'nu', text:'is
null'},{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹{ op: "AND", text:
"tot" },—² ÷ ¢ $õ""Â  FW‡C¢ ' V Ç6WföÂ" Ù],™ÐperandTitle : "Click to select
search operation.",™ÐresetTitle : "Reset Search Value"ÒÍVF—B ¢ ™ÐaddCaption:
"Afegir registre",™ÐeditCaption: "Modificar registre",™ÐSubmit: "Guardar",™Ð
bCancel: "Cancelar",™ÐbClose: "Tancar",™ÐsaveData: "Les dades han canviat.
Guardar canvis?",™ÐbYes : "Yes",™ÐNo : "No",™ÐExit : "Cancel",™Ðmsg: {™Ð
required:"Camp obligatori",™    number:"Introdueixi un nombre",™Ð
minValue:"El valor ha de ser major o igual que ",™    maxValue:"El valor ha de
ser menor o igual a ",™    email: "no és una direcció de correu vàlida",™Ð
integer: "Introdueixi un valor enter",™–F FS¢ $–çG&öGVV—†' Væ  F F  6÷'&V7F  ™Í
url: "no és una URL vàlida. Prefix requerit ('http://' or 'https://')",™Ð•
nodefined : " is not defined!",™–æ÷f ÇVR ¢ " &WGW&â f ÇVR —2 &W V—&VB ™Í
customarray : "Custom function should return array!",™–7W7FöÖf6†V6² ¢ $7W7FöÒ
function should be present in case of custom checking!"™}ÐÍf–Wr ¢ ™caption:
"Veure registre",™ÐbClose: "Tancar"ÒÍFVÂ ¢ ™caption: "Eliminar",™Ðmsg: "¿Desitja
eliminar els registres seleccionats?",™ÐbSubmit: "Eliminar",™ÐCancel: "Cancelar"Ð
—ÒÍæ b ¢ ™edittext: " ",™Ðdittitle: "Modificar fila seleccionada",™Ðddtext:" ",™Ð
addtitle: "Agregar nova fila",™Ðdeltext: " ",™Ðeltitle: "Eliminar fila
seleccionada",™Ðsearchtext: " ",™Ðearchtitle: "Cercar informació",™Ðefreshtext:
"",™Ðrefreshtitle: "Refrescar taula",™Ðlertcap: "Avís",™Ðlerttext: "Seleccioni
una fila",™Ðviewtext: " ",™Ðiewtitle: "Veure fila seleccionada"ÒÍ/ setcolumns
moduleÐ6öÂ ¢ ™caption: "Mostrar/ocultar columnes",™ÐSubmit: "Enviar",™ÐCancel:
"Cancelar"•ÒÍW'&÷'2 ¢ ™errcap : "Error",™Ðourl : "No s'ha especificat una URL",™Ð
norecords: "No hi ha dades per processar",™Ðmodel : "Les columnes de noms són
diferents de les columnes del model"ÐÒÍf÷&Ö GFW" ¢ ™integer :
{thousandsSeparator: ".", defaultValue: '0'},™Ðnumber : {decimalSeparator:",",
thousandsSeparator: ".", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency :
{decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0,00'},™Ðdate : {™ÐF ”æ ÖW3¢  ™½"Dg", "Dl", "Dt", "Dc",
"Dj", "Dv", "Ds",™™"Diumenge", "Dilluns", "Dimarts", "Dimecres", "Dijous",
"Divendres", "Dissabte"™•ÒÍÖöçF„æ ÖW3¢™½"Gen", "Febr", "Març", "Abr", "Maig",
"Juny", "Jul", "Ag", "Set", "Oct", "Nov", "Des",™™"Gener", "Febrer", "Març",
"Abril", "Maig", "Juny", "Juliol", "Agost", "Setembre", "Octubre",
"Novembre", "Desembre"™•ÒÍ Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%ÒÍ3¢ gVæ7F–öâ †¢' ·&WGW&â
j < 11 || j > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] :
'th'},™–7&6f÷&Ö C¢ u'ÖÒÖBr™ÍæWvf÷&Ö C¢ vBÖÒÕ'r™Í  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒÍ
masks : {™        ISO8601Long:"Y-m-d H:i:s",™       ISO8601Short:"Y-m-d",™
™        ShortDate: "n/j/Y",™       LongDate: "l, F d, Y",™
FullDateTime: "l, F d, Y g:i:s A",™        MonthDay: "F d",™       ShortTime:
"g:i A",™        LongTime: "g:i:s A",™       SortableDateTime: "Y-m-d\\TH:i:s",™
™        UniversalSortableDateTime: "Y-m-d H:i:sO",™       YearMonth: "F, Y"™
™    },™   reformatAfterEdit : false™,™ÐaseLinkUrl: '',™ÐhowAction: 'show',™
target: '',™    6†V6¶&÷, ¢ ¶F—6 &ÆVC§G'VWÒ™idName : 'id'™});™})(jQuery);™
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-cn.js

```
;(function($){Ð**Ð* jqGrid Chinese TranslationÐ* T–UaQT yanhonglei@gmail.comÐ
http://www.kafeitu.me Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð   defaults : {Ð
        recordtext: "{0} - {1}\u3000Qq {2} ga", // Qq[WÐmfÝQh%ÒzrusÐ "eàepcnf>y:",Ð
        loadtext: "‹ûSÖN-...",Ð pgtext : " {0} Qq {1} ~u"Ð},Ð   search : {Ð
        caption: "d }"...",Ð   Find: "gåb~",Ð   Reset: "‘Í•n",Ð   odata:
[{ oper:'eq', text:'{INŽ\u3000\u3000'},{ oper:'ne', text:'N {I\u3000\u3000'},
{ oper:'lt', text:'\ NŽ\u3000\u3000'},{ oper:'le', text:'\ NŽ{INŽ'},{ oper:'gt', text:'Y'N
\u3000\u3000'},{ oper:'ge', text:'Y'NŽ{INŽ'},{ oper:'bw', text:'_ YËNŽ'},{ oper:'bn', text
NŽ'},{ oper:'in', text:'\^NŽ\u3000\u3000'},{ oper:'ni', text:'N \^NŽ'},{ oper:'ew', text:'
NŽ'},{ oper:'en', text:'N ~Óg_NŽ'},{ oper:'cn', text:'S T+\u3000\u3000'},{ oper:'nc', text
T+'},{ oper:'nu', text:'N [XW('},{ oper:'nn', text:'[XW(}ÐÐ},ÐOps: [ { op:
"AND", text: "b@g " },    { op: "OR",  text: "NÚNope}ÐÐ},ÐÐitle : "Click to
select search operation.",ÐresetTitle : "Reset Search Value"Ð  },Ð   edit : {Ð
        addCaption: "mûR ‹°_U",ÐeditCaption: "• •‘‹°_U",ÐSubmit: "cÐN¤",Ð
bCancel: "SÖmˆ",Ð   bClose: "Qs•í",Ð   saveData: "epcn]òe9SØÝYÐ&T&OÝ[XÝ",Ð,Ð
bNo : "T&",Ð     bExit : "SÖmˆ",Ð   msg: {Ð           required:"kd[Wkµ_Å— ",Ð
number:"‹÷•“Qeg eHep[WÝ",ÐValue:"•“P<_Å˜{Y'NŽ{INŽaXÝ",ÐalueÐ:"•“P<_Å˜{\ NŽ{INŽ ",Ð
email: "•ÙN f/g eHv„e-mailWÝ",ÐÐ",Ðer: "‹÷•“Qeg eHetepÐ",ÐÐe: "‹÷•“Qeg eHeö•ôÝ",Ð:
"eàeH•QW@0 RM• _Å˜{N: ('http://' b  'http://'ÐÐ,Ð " g*[šNIÿ ",Ð   novalue :
" — ‰••ÔVÞP<ÿ ",Ðustomarray : "•ê[šNIQýep— ‰••ÔVÞmfÝÿeÐ",Ð: "_Å˜{g •ê[šNIQýep]!ÐÐ
    view : {Ð       caption: "gåw ‹°_U",ÐClose: "Qs•í"Ð},Ð   del : {Ð
caption: "R –d",Ð   msg: "R –db@• ‹°bÜÿ",ÐÐ: "R –d",Ð   bCancel: "SÖmˆ"Ð},Ð
nav : {Ð       edittext: "",Ð       edittitle: "• •‘b@• ‹°aÜÿ",ÐÐext:"",Ð
addtitle: "mûR e°‹°_Ud",ÐÐtext: "",Ð       deltitle: "R –db@• ‹°sÜÿ",ÐÐhtext: "",Ð
        searchtitle: "gåb~",Ð   refreshtext: "",Ð       refreshtitle: "R7e°ˆhh<",Ð
        alertcap: "lèa ",Ð   alerttext: "‹÷• bé‹°_UÝ",ÐÐwtext: "",Ð
viewtitle: "gåw b@",Ð‹°_UÝÐ : {Ð       caption: "• béR ",Ð bSubmit: "xn[š",Ð
bCancel: "SÖmˆ"Ð},Ð   errors : {Ð       errcap : "• ‹ï",Ð   nourl : "l¡g ‹¾•nurl",Ð
        norecords: "l¡g ‰•Y t m„ÊlU",ÐcolNames TŒ colModel ••^}ÑÐ{Iÿ "Ð
formatter : {Ð       integer : {thousandsSeparator: ",", defaultValue: '0'},Ð
        number : {decimalSeparator:".", thousandsSeparator: ",",
decimalPlaces: 2, defaultValue: '0.00'},Ð       currency :
{decimalSeparator:".", thousandsSeparator: ",", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0.00'},Ð       date : {Ð           dayNames:   [Ð
                "eå", "N ", "NŒ", "N ", "VÛ", "N"", "Qm",Ð "f g eå", "f g N ", "f g NŒ", "
VÛ", "f g N"", "f g Qm"],Ð           monthNames: [Ð               "N ", "NŒ", "N ",
"VÛ", "N"", "Qm", "N ", "Qk", "N]", "SA", "SAN ", "SANŒ",Ð "NŒg ", "N g ", "VÛg ", "N"g ",
g ", "Qkg ", "N]g ", "SAg ", "SAN]gÐ", "SANŒg "ÐmPm : ["am","pm","N SH","N SH"],Ð
            S: function (j) {return j < 11 || j > 13 ? ['st', 'nd', 'rd',
'th'][Math.min((j - 1) % 10, 3)] : 'th';},Ð           srcformat: 'Y-m-d',Ð
            newformat: 'Y-m-d',Ð           parseRe : /[#%\\\/:_;.,\t\s-]/,Ð
            masks : {Ð               // see http://php.net/manual/en/
function.date.php for PHP format used in jqGridÐ               // and see
http://docs.jquery.com/UI/Datepicker/formatDateÐ               // and https://
github.com/jquery/globalize#dates for alternative formats used frequentlyÐ
                // one can find on https://github.com/jquery/globalize/tree/
master/lib/cultures manyÐ               // information about date, time,
numbers and currency formats used in different countriesÐ               //
one should just convert the information in PHP formatÐ
ISO8601Long:"Y-m-d H:i:s",Ð               ISO8601Short:"Y-m-d",Ð
                // short date:Ð               //    n - Numeric
representation of a month, without leading zerosÐ               //    j - Day
of the month without leading zerosÐ               //    Y - A full numeric
representation of a year, 4 digitsÐ               // example: 3/1/2012 which
means 1 March 2012Ð               ShortDate: "n/j/Y", // in jQuery UI
Datepicker: "M/d/yyyy"Ð               // long date:Ð               //    l -
A full textual representation of the day of the weekÐ
```

```
                                                                    //    F -
A full textual representation of a monthÐ               //    d - Day of the
month, 2 digits with leading zerosÐ              //    Y - A full numeric
representation of a year, 4 digitsÐ              LongDate: "l, F d, Y", //
in jQuery UI Datepicker: "dddd, MMMM dd, yyyy"Ð               // long date
with long time:Ð               //    l - A full textual representation of the
day of the weekÐ               //    F - A full textual representation of a
monthÐ               //    d - Day of the month, 2 digits with leading zerosÐ
                //    Y - A full numeric representation of a year, 4 digitsÐ
                //    g - 12-hour format of an hour without leading zerosÐ
                //    i - Minutes with leading zerosÐ               //    s -
Seconds, with leading zerosÐ               //    A - Uppercase Ante meridiem
and Post meridiem (AM or PM)Ð               FullDateTime: "l, F d, Y g:i:s
A", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy h:mm:ss tt"Ð
                // month day:Ð               //    F - A full textual
representation of a monthÐ               //    d - Day of the month, 2 digits
with leading zerosÐ               MonthDay: "F d", // in jQuery UI
Datepicker: "MMMM dd"Ð               // short time (without seconds)Ð
                //    g - 12-hour format of an hour without leading zerosÐ
                //    i - Minutes with leading zerosÐ               //    A -
Uppercase Ante meridiem and Post meridiem (AM or PM)Ð
ShortTime: "g:i A", // in jQuery UI Datepicker: "h:mm tt"Ð               //
long time (with seconds)Ð               //    g - 12-hour format of an hour
without leading zerosÐ               //    i - Minutes with leading zerosÐ
                //    s - Seconds, with leading zerosÐ               //    A
- Uppercase Ante meridiem and Post meridiem (AM or PM)Ð
LongTime: "g:i:s A", // in jQuery UI Datepicker: "h:mm:ss tt"Ð
SortableDateTime: "Y-m-d\\TH:i:s",Ð               UniversalSortableDateTime:
"Y-m-d H:i:sO",Ð               // month with yearÐ               //    Y - A
full numeric representation of a year, 4 digitsÐ               //    F - A
full textual representation of a monthÐ               YearMonth: "F, Y" // in
jQuery UI Datepicker: "MMMM, yyyy"Ð           },Ð
reformatAfterEdit : falseÐ       },Ð       baseLinkUrl: '',Ð
showAction: '',Ð       target: '',Ð       checkbox : {disabled:true},Ð
idName : 'id'Ð   }});})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-cs.js

;(function($){Ð**Ð* jqGrid Czech TranslationÐ* Pavel Jirak
pavel.jirak@jipas.czÐ* doplnil Thomas Wagner xwagne01@stud.fit.vutbr.czÐ*
http://trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™
recordtext: "Zobrazeno {0} - {1} z {2} záznam ò"Í V× G—&V6÷&G3¢ $æVæ ÆW¦Vç'
žádné záznamy",Ðloadtext: "Na Þ×N ÒââÂ™ÐÍtext : "Strana {0} z {1}"ÐÍ6V &6, ¢ ™
caption: "Vyhledávám...",ÐFind: "Hledat",™Ðreset: "Reset",Ð öF F ¢
[{ oper:'eq', text:"rovno"},{ oper:'ne', text:"nerovno"},{ oper:'lt',
text:"menší"},{ oper:'le', text:"menší nebo rovno"},{ oper:'gt', text:"v ·I®Ò'ÒÀ
{ oper:'ge', text:"v ·I®Ò æV&ò &÷fæò'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢'¦ íná s"},
{ oper:'bn', text:"neza ÞÖî 2'ÒÇ² ÷ W#¢v–ârÂ FW‡C¢&¦R b'ÒÇ² ÷ W#¢væ'rÂ
text:"není v"},{ oper:'ew', text:"kon ÞÒ 2'ÒÇ² ÷ W#¢vVârÂ FW‡C¢&æV¶öá í s"},
{ oper:'cn', text:"obsahuje"},{ oper:'nc', text:"neobsahuje"},{ oper:'nu',
text:'is null'},{ oper:'nn', text:'is not null'}],Ð   w&÷W ÷ 3¢ ¹{ op: "AND",
text: "všech" },—² ÷ ¢ $õ""Â FW‡C¢ &á kterého z" }™ÒÍerandTitle : "Click to
select search operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ™
addCaption: "P ––F B ® ¦æ Ò™ÍeditCaption: "Editace záznamu",ÐSubmit: "Uložit",™Ð
bCancel: "Storno",ÐbClose: "Zav ž×™ÍaveData: "Data byla zm ¶á na! Uložit zm ¶Ç"ò"Í
bYes : "Ano",ÐbNo : "Ne",™ÐExit : "Zrušit",™Ðmsg: "Ð   required:"Pole je
vyžadováno",Ð   number:"Prosím, vložte validní Þ×6Æ™"Í minValue:"hodnota
musí být v ·I®Ò æYâ æV&ò &÷fî ™Í   maxValue:"hodnota musí být menší než nebo
rovná ",Ð   email: "není validní e-mail",™Ð   integer: "Prosím, vložte celé
 Þ×6Æò™ÍF FS¢ % &÷>ÖÒÂ fÆùçFR f Æ–FîÒ F GVÒ™ÍW&Ã¢ &æVîÒ Æ Fæ÷R U$Ââ g™æ F÷n â
prefix ('http://' or 'https://')",Ð–æöFVf–æVB ¢ " æVîÒ FVf–æ÷n â ™Íæ÷f ÇVR ¢ "
je vyžadována návratová hodnota!",Ð–7W7FöÖ '& ' ¢ $7W7FöÒ gVæ7F–öâ Ñ lá vrátit
pole!",Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ gVæ7F–öâ '' Ñ la být p ž×FöÖæ b Yípad ² 7W7FöÒ
checking!"Ð]ÐÍf–Wr ¢ ½   6 F–öã¢ %¦ö'& ¦—B ® ¦æ Ò"Í $6Æ÷6S¢ %¦ aYí±ÒÍ
del : {Ðcaption: "Smazat",™Ðmsg: "Smazat vybraný(é) záznam(y)?",ÐSubmit:
"Smazat",ÐbCancel: "Storno"ÐÍæ b ¢ ™edittext: " ",™Ðedittitle: "Editovat vybraný
 ž FV²™ÍaddtextÐ:" ",™Ðaddtitle: "P ––F B æ÷oÒ Yádek",™ÐÍtext: " ",™Ðdeltitle: "Smazat
vybraný záznam ",Ðsearchtext: " ",™Ðsearchtitle: "Najít záznamy",™Ðrefreshtext: "",™Ð
refreshtitle: "Obnovit tabulku",Ðalertcap: "Varování",™Ðalerttext: "Prosím,
vyberte ž FV²™Íviewtext: "",™Ðviewtitle: "Zobrazit vybraný ž FV²ÍÍ6öÂ ¢ ™
caption: "Zobrazit/Skrýt sloupce",ÐbSubmit: "Uložit",™ÐCancel: "Storno"ÐÍ
errors : {Ðerrcap : "Chyba",™Ðurl : "Není nastavena url",™Ðrecords: "Žádné
záznamy ke zpracování",Ðmodel : "Délka colNames <> colModel!"ÐÍf÷&Ö GFW" ¢ ™
integer : {thousandsSeparator: " ", defaultValue: '0'},Ðnumber :
{decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2,
defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator: "
", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : {™Ð
dayNames: [™Ð"Ne", "Po", "Út", "St", " ÇB"Â % "Â %ÖÖ"™ÍÍed ¶ÆR"Â % öæA lí",
"Úterý", "St –VF "Â ! tvrtek", "Pátek", "Sobota™ÐÍÖöçF„æ ÖW3¢™½"™Led", "Úno",
"B –R"Â $GV""Â $·a ", " ÆW""Â ! vc", "Srp", "Zá '"Â !Xíj", "Lis™", "Prosinec",Ð
"Únor", "B –W¦Vâ"Â $GV&Vâ"Â $·a ten", " ÆW'fVâ"Â ! ervenec", "Srpen", "Zá žÒ"Â
" ŽÖ¦Vâ"Â $Æ—7F÷ B"Â % &÷6–æV2•™ÍÍ Õ Ò ¢ ²&Fò"Â&öB"Â$DÒ"Â$ôB%™ÍÍ3¢ gVæ7F–öâ †¢'
{return j < 11 || j > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10,
3)] : 'th'},Ð—7&6f÷&Ö C¢ u'ÖÒÖBr™ÍæWvf÷&Ö C¢ vBöÒõ'™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÀ
\t\s-]/,Ð–Ö 6·2 ¢™½   ISO8601Long:"Y-m-d H:i:s",™Ð   ISO8601Short:"Y-m-
d",Ð   ShortDate: "n/j/Y",™Ð   LongDate: "l, F d, Y",™Ð
FullDateTime: "l, F d, Y g:i:s A",Ð   MonthDay: "F d",™Ð   ShortTime:
"g:i A",Ð   LongTime: "g:i:s A",™Ð   SortableDateTime: "Y-m-d\\TH:i:s",Ð
™   UniversalSortableDateTime: "Y-m-d H:i:sO",™Ð   YearMonth: "F, Y"Ð
™   },™Ð   reformatAfterEdit : false™Ð,™ÐbaseLinkUrl: '',™ÐshowAction: '',Ð
target: '',Ð   6†V6¶&÷, ¢ ¶F—6 &ÆVC§G'VWÒ™idName : 'id'™Ð});Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-da.js

;(function($){Ð**Ð* jqGrid Danish TranslationÐ* Aesiras A/SÐ* http://
www.aesiras.dkÐ* Dual licensed under the MIT and GPL licenses:Ð* http://
www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/
gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext:
"Vis {0} - {1} of {2}",Ð V× G–&V6÷&G3¢ $–ævVâ Æ–æ¦W" gVæFWB"Í loadtext:
"Henter...",™Ðpgtext : "Side {0} af {1}"™ÐÍ6V &6, ¢ ½ 6 F–öã¢ %?†râââ"Í
Find: "Find",Ð &W6WC¢ $çVÇ7F–Â"Í öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢&Æ–r'ÒÀ
{ oper:'ne', text:"forskellige fra"},{ oper:'lt', text:"mindre"},{ oper:'le',
text:"mindre eller lig"},{ oper:'gt', text:"større"},{ oper:'ge',
text:"større eller lig"},{ oper:'bw', text:"begynder med"},{ oper:'bn',
text:"begynder ikke med"},{ oper:'in', text:"findes i"},{ oper:'ni',
text:"findes ikke i"},{ oper:'ew', text:"ender med"},{ oper:'en', text:"ender
ikke med"},{ oper:'cn', text:"indeholder"},{ oper:'nc', text:"indeholder
ikke"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð
groupOps: [–² ÷ ¢ $ äB"Â FW‡C¢ & ÆÂ" ÒÉ{ op: "OR", text: "any" }•ÒÍ
operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search
Value"ÐÒÍVF–B ¢ ½ FD6 F–öã¢ %F–Æo†¢"Í VF–D6 F–öã¢ %&WB"Í %7V&Ö–C¢
"Send",Ð $6 æ6VÃ¢ $ æçVÆÆW""™ÍbClose: "Luk",™ÐaveData: "Data er ændret. Gem
data?",™ÐbYes : "Ja",™ÐNo : "Nej",™ÐExit : "Fortryd",Ð ×6s¢ ½
required:"Felt er nødvendigt",Ð çVÖ&W#¢$–æGF 7B fVæÆ–w7B WB f Æ–GB F Â"Í
' Ö–åf ÇVS¢'ng&F' 6¶ Â ng&R 7O‡'&R VæB VÆÆW" Æ–r ÖVB"Í
maxValue:"værdi skal være mindre end eller lig med",Ð VÖ –Ã¢ &W" –¶¶R
en gyldig email",Ð –çFVvW#¢ $–æGF 7B fVæÆ–w7B WB w–ÆF–wB †VÇF Â"™Í–F FS¢
"Indtast venligst en gyldig datoværdi",™Ð–W&Ã¢ &W" Vw–ÆF–r U$Ââ &Vf–, Ö ævÆW"
('http://' or 'https://')",™Ð–æöFVf–æVB ¢ " W" –¶¶R FVf–æW&WB ™™Íæ÷f ÇVR ¢ "
returværdi kræves!",™Ð–7W7FöÖ '& ' ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &WGW&â '& ' ™™Í
customfcheck : "Custom function should be present in case of custom checking!"Ð
™}ÒÍf–Wr ¢ ½ 6 F–öã¢ %f–2 Æ–æ¦R"Í $6Æ÷6S¢ $ÇV²–ÒÍFVÂ ¢ ½ 6 F–öã¢
"Slet",Ð ×6s¢ %6ÆWB f ÆwFR Æ–æ¦R‡"“ò"Í %7V&Ö–C¢ %6ÆWB"Í $6 æ6VÃ¢
"Fortryd"ÐÒÍæ b ¢ ™½edittext: " ",Ð VF–GF–FÆS¢ %&VF–vW" f ÆwFR Æ–æ¦R"™Í
addtext:" ",Ð FGF–FÆS¢ %F–Æo†¢ ç' Æ–æ¦R"Í FVÇFW‡C¢ " "Í FVÇF–FÆS¢
"Slet valgte linje",Ð 6V &6‡FW‡C¢ " "Í 6V &6‡F–FÆS¢ $f–æB Æ–æ¦W""Í
refreshtext: "",Ð &Vg&W6‡F–FÆS¢ $–æFÎg2 –vVâ"Í ÆW'F6 ¢ $ Gf '6VÂ"Í
alerttext: "Vælg venligst linje",™Ðviewtext: "",™Ðiewtitle: "Vis valgte linje"™ÐÍ
col : {Ð 6 F–öã¢ %f–2÷6¶§VÂ ¶öÆöææW""Í %7V&Ö–C¢ $÷ F FW&R"Í $6 æ6VÃ¢
"Fortryd"ÐÒÍW'&÷'2 ¢ ™½errcap : "Fejl",™Ðourl : "Ingen url valgt",™Ðorecords:
"Ingen linjer at behandle",Ð ÖöFVÂ ¢ &6öÄæ ÖW2 ör 6öÄÖöFVÃ † " –¶¶R 6 ÖÖR
længde!"ÐÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: " ", defaultValue: '0'},™Ð
number : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2,
defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: "
", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0,00'},™Ðdate : {™Ð
dayNames: [™™"Søn", "Man", "Tir", "Ons", "Tor", "Fre", "Lør™™™",™ÐSøndag",
"Mandag", "Tirsdag", "Onsdag", "Torsdag", "Fredag", "Lørdag"™Ð•™™ÍÖöçF„æ ÖW3¢ ½
™™"Jan", "Feb", "Mar", "Apr", "Maj", "Jun", "Jul", "Aug", "Sep", "Okt", "Nov",
"Dec",™Ð™"Januar", "Februar", "Marts", "April", "Maj", "Juni", "Juli", "August",
"September", "Oktober", "November", "December"™Ð•™™ÍÕ Ò ¢ ²""Â""Â""Â"%™™Í3¢
function (j) {return '.'},™Ð–7&6f÷&Ö C¢ u'ÖÒÖBr™ÍæWvf÷&Ö C¢ vBöÒõ'™™Í '6U&R ¢ õ²2P
\\\/:_;.,\t\s-]/,™Ð–Ö 6·2 ¢'½ •4ó‚fc Æöæs¢%'ÖÒÖB ƒ¦“§2"Í
ISO8601Short:"Y-m-d",Ð 6†÷'DF FS¢ &¢öâõ'"Í ÆöætF FS¢ &Â
d. F Y",Ð gVÆÄF FUF–ÖS¢ &Â B b ' s¦“§2"Í ÖöçF„F “¢ &Bâ
F",Ð 6†÷'EF–ÖS¢ $s¦'"Í ÆöæuF–ÖS¢ $s¦“§2"Í
SortableDateTime: "Y-m-d\\TH:i:s",Ð Væ–fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %'ÖÒÐ
d H:i:sO",Ð –V $ÖöçF‚f¢ $b '' ™ ÒÍ &Vf÷&Ö D gFW$VF–B ¢
falseÐ},™ÐaseLinkUrl: '',™ÐhowAction: '',Ð F &vWC¢ rrÍ 6†V6¶&÷, ¢
{disabled:true},™ÐidName : 'id–™});Ð/ DAÐ})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-de.js

;(function($){Ð**Ð* jqGrid German TranslationÐ* Version 1.0.0 (developed for jQuery Grid 3.3.1)Ð* Olaf Klöppel opensource@blue-hit.deÐ* http://blue-hit.de/ Ð*Ð* Updated for jqGrid 3.8Ð* Andreas FlackÐ* http://www.contentcontrol-berlin.deÐ*Ð* Updated for jQuery 4.4Ð* Oleg Kiriljuk oleg.kiriljuk@ok-soft-gmbh.comÐ* the format corresponds now the format fromÐ* https://github.com/jquery/globalize/blob/master/lib/cultures/globalize.culture.de.jsÐ*Ð* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™ recordtext: "Zeige {0} - {1} von {2}",™Ðemptyrecords: "Keine Datensätze vorhanden",™Ðloadtext: "Lädt...",™Ðpgtext : "Seite {0} von {1}"™ÐÍ6V &6, ¢ ™ caption: "Suche...",™ÐFind: "Suchen",™Ðreset: "Zurücksetzen",™Ðdata: [{ oper:'eq', text:"gleich"},{ oper:'ne', text:"ungleich"},{ oper:'lt', text:"kleiner"},{ oper:'le', text:"kleiner gleich"},{ oper:'gt', text:"größer"},{ oper:'ge', text:"größer gleich"},{ oper:'bw', text:"beginnt mit"},{ oper:'bn', text:"beginnt nicht mit"},{ oper:'in', text:"ist in"},{ oper:'ni', text:"ist nicht in"},{ oper:'ew', text:"endet mit"},{ oper:'en', text:"endet nicht mit"},{ oper:'cn', text:"enthält"},{ oper:'nc', text:"enthält nicht"},{ oper:'nu', text:"ist Null" }, { oper:'nn', text:"ist nicht Null" }],™Ðgroupops: [{ op: "AND", text: "alle" },{ op: "OR", text: "mindestens eine" }],™Ðoperandtitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™addCaption: "Datensatz hinzufügen",™ÐeditCaption: "Datensatz bearbeiten",™ÐbSubmit: "Speichern",™ÐCancel: "Abbrechen",™ÐClose: "Schließen",™ÐsaveData: "Daten wurden geändert! Änderungen speichern?",™ÐbYes : "ja",™ÐNo : "nein",™ÐbExit : "abbrechen",™Ðmsg: {™Ð&W V—&VC¢$fVÆB —7B W&f÷&FW&Æ–6,™ÍçVÖ&W#¢ "Bitte geben Sie eine Zahl ein",™Ð–Ö–åf ÇVS¢%vW'B ×W72 w/möW" öFW" vÆV–6, 6V–âÂ als ",™Ð–Ö …f ÇVS¢%vW'B ×W72 ¶ÆV–æW" öFW" vÆV–6, 6V–âÂ Ç2 ™ÍVÖ –Ã¢ &—7B ¶V–æR gültige E-Mail-Adresse",™Ð––çFVvW#¢ $&—GFR vV&Vâ 6–R V–æR v ç§¦ †Â V–â™ÍF FS¢ "Bitte geben Sie ein gültiges Datum ein",™Ð—W&Ã¢ &—7B ¶V–æR •ÆÇF–vR U$Ââ .Ff—, muss eingegeben werden ('http://' oder 'https://')",™Ð–æöFVf–æVB ¢ " —7B æ–6‡B definiert!",™Ð–æ÷f ÇVR ¢ " /Æ6¶v &WvW'B —7B W&f÷&FW&Æ–6, ™Í7W7FöÖ '& ’ ¢ "Benutzerdefinierte Funktion sollte ein Array zurückgeben!",™Ð–7W7FöÖf6†V6² ¢ "Benutzerdefinierte Funktion sollte im Falle der benutzerdefinierten Überprüfung vorhanden sein!"™}ÒÍf–Wr ¢ ™caption: "Datensatz anzeigen",™ÐClose: "Schließen"ÐÒÍFVÂ ¢ ™caption: "Löschen",™Ðmsg: "Ausgewählte Datensätze löschen?",™Ðbsubmit: "Löschen",™ÐbCancel: "Abbrechen"™ÐÍæ b ¢ ™edittext: " ",™Ðedittitle: "Ausgewählte Zeile editieren",™Ðaddtext:" ",™Ðaddtitle: "Neue Zeile einfügen",™Ðdeltext: " ",™Ðdeltitle: "Ausgewählte Zeile löschen",™Ðsearchtext: " ",™Ðsearchtitle: "Datensatz suchen",™Ðrefreshtext: "",™Ðrefreshtitle: "Tabelle neu laden",™Ðalertcap: "Warnung",™Ðalerttext: "Bitte Zeile auswählen",™Ðviewtext: "",™Ðviewtitle: "Ausgewählte Zeile anzeigen"ÐÒÍ6öÂ ¢ ™caption: "Spalten auswählen",™Ðbsubmit: "Speichern",™ÐbCancel: "Abbrechen"™ÐÍW'&÷'2 ¢ ™errcap : "Fehler",™Ðnourl : "Keine URL angegeben",™Ðnorecords: "Keine Datensätze zu bearbeiten",™Ðmodel : "colNames und colModel sind unterschiedlich lang!"ÐÒÍf÷&Ö GFW" ¢ ™ integer : {thousandsSeparator: ".", defaultValue: '0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "", suffix:" €", defaultValue: '0,00'},™Ðdate : {™Ðdaynames: [™™"So", "Mo", "Di", "Mi", "Do", "Fr", "Sa™™™,™ÐSonntag", "Montag", "Dienstag", "Mittwoch", "Donnerstag", "Freitag", "Samstag"™Ð•™ÍÖöçF„æ ÖW3¢ ½ ™™"Jan", "Feb", "Mar", "Apr", "Mai", "Jun", "Jul", "Aug", "Sep", "Okt", "Nov", "Dez",™™"Januar", "Februar", "März", "April", "Mai", "Juni", "Juli", "August", "September", "Oktober", "November", "Dezember"™Ð•™Í Õ Ò ¢ ²""Â""Â""Â"%™Í3¢ function () {return '.';}, // one can also use 'er' instead of '.' but one have to use additional word like 'der' or 'den' before™—7&6f÷&Ö C¢ u’ÖÒÖBr™Í newformat: 'd.m.Y',™— '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÖÍÖ 6·2 ¢™½// see http://php.net/manual/en/function.date.php for PHP format used in jqGrid™// and see http://docs.jquery.com/UI/Datepicker/formatDate™// and https://github.com/jquery/globalize#dates for alternative formats used frequentlyÐ

™™ISO8601Long: "Y-m-d H:i:s",Ð™ISO8601Short: "Y-m-d",Ø™™Ø/ short date™™Ø/   d - Day of the month, 2 digits with leading zerosÐ™//   m - Numeric representation of a month, with leading zerosÐ™//   Y - A full numeric representation of a year, 4 digitsÐ™™Ø/ ShortDate: "d.m.Y",’òò –â ¥ VW'’ T’ F FW –6¶W#¢ &FBäÔÒÒç——’™™// long date™™Ø/ l - A full textual representation of the day of the weekÐ™//   j - Day of the month without leading zerosÐ™//   F - A full textual representation of a monthÐ™™//   Y - A full numeric representation of a year, 4 digitsÐ™™Ø/ LongDate: "l, j. F Y", // in jQuery UI Datepicker: "dddd, d. MMMM yyyy"Ð™// long date with long time:Ð™//   l - A full textual representation of the day of the week™™Ø/   j - Day of the month without leading zerosÐ™//   F - A full textual representation of a monthÐ™//   Y - A full numeric representation of a year, 4 digitsÐ™™Ø/   H - 24-hour format of an hour with leading zerosÐ™//   i - Minutes with leading zerosÐ™//   s - Seconds, with leading zeros™™Ø/ FullDateTime: "l, j. F Y H:i:s", // in jQuery UI Datepicker: "dddd, d. MMMM yyyy HH:mm:ss"Ð™// month day™™Ø/   d - Day of the month, 2 digits with leading zerosÐ™//   F - A full textual representation of a monthÐ™MonthDay: "d F", // in jQuery UI Datepicker: "dd MMMM"Ð™// short time (without seconds)™™Ø/   H - 24-hour format of an hour with leading zerosÐ™//   i - Minutes with leading zeros™™Ø/ ShortTime: "H:i", // in jQuery UI Datepicker: "HH:mm"Ð™// long time (with seconds)™™Ø/   H - 24-hour format of an hour with leading zerosÐ™//   i - Minutes with leading zeros™™Ø/ s - Seconds, with leading zerosÐ™LongTime: "H:i:s", // in jQuery UI Datepicker: "HH:mm:ss"Ð™SortableDateTime: "Y-m-d\\TH:i:s",™™Ø/ UniversalSortableDateTime: "Y-m-d H:i:sO",Ð™// month with year™™Ø/   F - A full textual representation of a monthÐ™™//   Y - A full numeric representation of a year, 4 digits™™Ø/ YearMonth: "F Y" // in jQuery UI Datepicker: "MMMM yyyy"Ð—Ùí&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ],™™Ø baseLinkUrl: '',™™Ø showAction: '',™™Ø target: '',™™Ø checkbox : {disabled:true},™™Ø idName : 'id'™™Ø});™™Ø})(jQuery);™™Ø

public\assets\js\plugins\jqGrid\i18n\grid.locale-dk.js

;(function($){Ð**Ð* jqGrid Danish TranslationÐ* Kaare Rasmussen kjs@jasonic.dkÐ
 * http://jasonic.dk/blog Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/$.jgrid = {ÐFVf VÇG2 ¢ ™recordtext: "View {0} - {1} of
{2}",Ð   V× G—&V6÷&G3¢ $æò &V6÷&G2 Fò f–Wr"Íloadtext: "Loading...",™Ðgtext :
"Page {0} of {1}"ÐÒÍ6V &6, ¢ ½   6 F–öã¢ %?†râââ"Í   f–æC¢ $f–æB"Í
Reset: "Nulstil",Ð   öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢vW V ÂwÒÇ² ÷ W#¢væRrÂ
text:'not equal'},{ oper:'lt', text:'less'},{ oper:'le', text:'less or
equal'},{ oper:'gt', text:'greater'},{ oper:'ge', text:'greater or equal'},
{ oper:'bw', text:'begins with'},{ oper:'bn', text:'does not begin with'},
{ oper:'in', text:'is in'},{ oper:'ni', text:'is not in'},{ oper:'ew',
text:'ends with'},{ oper:'en', text:'does not end with'},{ oper:'cn',
text:'contains'},{ oper:'nc', text:'does not contain'},{ oper:'nu', text:'is
null'},{ oper:'nn', text:'is not null'}],Ð   w&÷W ÷ 3¢ ¹{ op: "AND", text:
"all" },—² ÷ ¢ $õ""Â FW‡C¢ & ç'" Ù],™ÐperandTitle : "Click to select search
operation.",™ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½   FD6 F–öã¢
"Tilføj",Ð   VF—D6 F–öã¢ %&WB"Í   %7V&Ö—C¢ %6VæB"Í $6 æ6VÃ¢ $ æçVÆÆW""Í"
bClose: "Luk",™ÐsaveData: "Data has been changed! Save changes?",™ÐYes : "Yes",™Ð
bNo : "No",™ÐbExit : "Cancel",Ð   ×6s¢ ½   &W V—&VC¢$fVÇB W" ï†GfVæF–wB"Í
'   çVÖ&W#¢$–æGF 7B fVæÆ–w7B WB f Æ–GB F Â"Í   Ö–åf ÇVS¢'ng&F' 6¶ Â
være større end eller lig med",Ð   Ö …f ÇVS¢'ng&F' 6¶ Â ng&R Ö–æG&R VæB
eller lig med",Ð   VÖ –Ã¢ &W" –¶¶R Vâ f Æ–B VÖ –Â"Í   –çFVvW#¢
"Indtast venligst et validt heltalt",™–F FS¢ $–æGF 7B fVæÆ–w7B Vâ f Æ–B
datoværdi",™–W&Ã¢ &—2 æ÷B   f Æ–B U$Ââ &Vf—, &W V—&VB ,v‡GG ¢òòr ÷"
'https://')",™Ð–æöFVf–æVB ¢ " —2 æ÷B FVf–æVB ™Íæ÷f ÇVR ¢ " &WGW&â f ÇVR —2
required!",™Ð–7W7FöÖ '& ' ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &WGW&â '& ' ™Í
customfcheck : "Custom function should be present in case of custom checking!"Ð
™}ÐÍf–Wr ¢ ½   6 F–öã¢ %f–Wr &V6÷&B"Í $6Æ÷6S¢ $6Æ÷6R—ÒÍFVÂ ¢ ½
caption: "Slet",Ð   ×6s¢ %6ÆWB f ÆwFR .f¶¶R‡"“ò"Í   %7V&Ö—C¢ %6ÆWB"Í
bCancel: "Annuller"ÐÒÍæ b ¢ ™edittext: " ",Ð   VF—GF—FÆS¢ %&VF–vW" f ÆwFR
række",™Ðaddtext:" ",Ð   FGF—FÆS¢ %F–Æo†¢ ç' .f¶¶R"Í   FVÇFW‡C¢ " "Í
deltitle: "Slet valgte række",Ð   6V &6‡FW‡C¢ " "Í   6V &6‡F—FÆS¢ $f–æB
poster",Ð   &Vg&W6‡FW‡C¢ ""Í   &Vg&W6‡F—FÆS¢ $–æFÎg2 –vVâ"Í   ÆW'F6 ¢
"Advarsel",Ð   ÆW'GFW‡C¢ %nfÆr fVæÆ–w7B .f¶¶R"Íviewtext: "",™Ðiewtitle: "View
selected row"ÐÒÍ6öÂ ¢ ½   6 F–öã¢ %f—2÷6¶§VÂ ¶öÆöææW""Í   %7V&Ö—C¢ %6VæB"Í
' $6 æ6VÃ¢ $ æçVÆÆW"—ÒÍW'&÷'2 ¢ ™errcap : "Fejl",™Ðourl : "Ingel url valgt",™Ð
norecords: "Ingen poster at behandle",Ð   ÖöFVÂ ¢ &6öÄæ ÖW2 ör 6öÄÖöFVÂ † "
ikke samme længde!"ÐÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: " ",
defaultValue: '0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: " ",
decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",",
thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0,00'},™Ðdate : {™ÐF "æ ÖW3¢ ™½"Søn", "Man", "Tirs", "Ons",
"Tors", "Fre", "Lør",™™"Søndag", "Mandag", "Tirsdag", "Onsdag", "Torsdag",
"Fredag", "Lørdag"™•™ÍÖöçF„æ ÖW3¢™™½"Jan", "Feb", "Mar", "Apr", "Maj", "Jun",
"Jul", "Aug", "Sep", "Okt", "Nov", "Dec",™™"Januar", "Februar", "Marts",
"April", "Maj", "Juni", "Juli", "August", "September", "Oktober", "November",
"December"™•™Í Õ Ò ¢ ²""Â""Â""Â"%™Íí3¢ gVæ7F–öâ †¢' ·&WGW&â râw™Íí7&6f÷&Ö C¢ u'ÖÒÐ
d',™–æWvf÷&Ö C¢ vBöÖõ'™Íí '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒ™ÍÖ 6·2 ¢'½
ISO8601Long:"Y-m-d H:i:s",Ð   •4óƒc 6†÷'C¢%'ÖÒÖB"Í
ShortDate: "j/n/Y",Ð   ÆöætF FS¢ &Â Bâ b '"Í   gVÆÄF FUF–ÖS¢
"l d F Y G:i:s",Ð   ÖöçF„F “¢ &Bâ b"Í   6†÷'EF–ÖS¢ $s¦'"Í
'   ÆöæuF–ÖS¢ $s¦“§2"Í   6÷'F &ÆTF FUF–ÖS¢ %'ÖÒÖEÅÅDƒ¦“§2"Í
'   Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %'ÖÒÖB ƒ¦“§4ò"Í   –V $ÖöçFƒ¢
"F Y"Ð   ÒÍ   &Vf÷&Ö D gFW$VF—B ¢ f Ç6™],™ÐaseLinkUrl: '',™ÐhowAction:
'',Ð   F &vWC¢ rrÍ   6†V6¶&÷, ¢ ¶F—6 &ÆVC§G'VWÒ™idName : 'id—Ð;Ð/ DKÐ})
(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-el.js

```
;(function($){Ð**Ð* jqGrid Greek (el) TranslationÐ* Alex CicovicÐ* http://
www.alexcicovic.comÐ* Dual licensed under the MIT and GPL licenses:Ð* http://
www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/
gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ½recordtext:
"View {0} - {1} of {2}",Ð    V× G—&V6÷&G3¢ $æò &V6÷&G2 Fò f–Wr"Íloadtext:
":cÌ< ÄpgÃçxâãâ"ÍPage {0} of {1}"ÐÍ6V &6, ¢ ½    6  F–öã¢ #‘;Ó±;c®<Cf<ãc¢.#"¿ÓÁ;SÃ;r"Í
’    &W6WC¢ #•< ±;ÓãF<c<¢¬"¿Ð÷ W#¢vW rÂ FW‡C¢vW V ÂwÒÇ² ÷ W#¢væRrÂ FW‡C¢væ÷B
equal'},{ oper:'lt', text:'less'},{ oper:'le', text:'less or equal'},
{ oper:'gt', text:'greater'},{ oper:'ge', text:'greater or equal'},
{ oper:'bw', text:'begins with'},{ oper:'bn', text:'does not begin with'},
{ oper:'in', text:'is in'},{ oper:'ni', text:'is not in'},{ oper:'ew',
text:'ends with'},{ oper:'en', text:'does not end with'},{ oper:'cn',
text:'contains'},{ oper:'nc', text:'does not contain'},{ oper:'nu', text:'is
null'},{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹{ op: "AND", text:
"all" },—² ÷ ¢ $õ""Â  FW‡C¢ & ç'" Ù]™ÐperandTitle : "Click to select search
operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½     FD6  F–öã¢ #•;“Ã; ³<“³:â •;3³
’    VF—D6  F–öã¢ #•<’µ;ãµ%7V¢ÖÃ¢ó±#9$³Ä3Á¢ÃÄ¢ÃÅ¢Ð#Í™ÐÂ¹oÃ;Ð"9Ã¢aÃ¢Ð¢aÃ¿",Ð
"Data has been changed! Save changes?",ÐbYes : "Yes",ÐNo : "No",ÐExit :
"Cancel",Ð    ×6s¢ ½        &W V—&VC¢#¤;ò À;S´:ó¿ ;¢V¢ÖÃW#¢#±<ò±À;S:óÁ¿sÃÇò¹Íµ<C±;’ ¼<Ã½;ò
minValue:"9r Ä;“¼:â À< -< µ;’ Ö;…fµçVÃ¢#¹ <Ãµ;Ã®;²ÍÁ¢ÇÀ;S¹:¢Ö¹<Ã¢ #Ó<;²¹¼$Í;²ÁÌÓÃµ< RÖÖâ–Ã
:Ó³;£Å< ·",ÐçFVvW#¢ #¤;ò À;S´W¢Â¢;¢—²sµ<B±;’f¼ÃÃÐ;U$Â¢£-&Vf÷“¿&WÂV÷&WÃ¸ ;Ã¿<ÓÂ",Ð
('http://' or 'https://')",Ð–æöFVf–æVB ¢ " —2 æ÷B FVf–æVB ™Íæ÷f ÇVR ¢ " &WGW&â
value is required!",Ð–7W7FöÖ '& ’ ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &WGW&â  '& ’ ™Í
customfcheck : "Custom function should be present in case of custom checking!"Ð
™]ÐÍf–Wr ¢ ½    6  F–öã¢ %f–Wr &V6÷&B"Í    $6Æ÷6S¢ $6Æ÷6R—ÒÍFVÂ ¢ ½
caption: "9C¹; ³<×6s¢®#”;“±;3Á; Æ%ãVÄÖ—¢¢;SÀ;“»"¿Ã¢ÇÃ¢ÇÃ¢ÒÍ#¢¢ÒÂ<b±¢Ð¢eÓ¹ÍÍext:
" ",Ð    VF—GF—FÆS¢ #•< ™ãdÍ¹text:Ã:ó±Ð;SÀ;“¢;FÆS¢;Ó•<”Ãµ;3²<V¢ãW¢®¢Ó¹Í""µ;3³< ±<c®<""Í
deltitle: "9C¹;’³< ±6V®&6$ÃW‡¢¢S¹;ÃÍ;Ó·<6Vµ&6‡—ÆS®<#"ÍÓÁ;SÃ&Vg&W6‡FW‡¢¢Î"ÓÍÍ
’    &Vg&W6‡F—FÆS¢ #‘;Ó±;Ó-<ÃÃ;F6 :Ó½# ²;¿²Ì¿Æ®®G,Ð‡C¢ #";S½™vÓÊwSÃxR:µ"™Ð³-;ãµ;’ µ;3³< ±
viewtitle: "View selected row"ÐÒÍ6öÂ ¢ ½    6  F–öã¢ #•;ÃÆ:Ã½;“Ã%7VÃÖ¹¢¢Ì#ÃÃ¢SÍ;r £<C·;³Î;
’    $6 æ6VÃ¢ #±ÒÍÃ¹&¿"Ð ¢ ½errcap : ":3ÃcÃ»lÃ±"ÐCµ;Ò -<s™;óréçórds: "9Cµ;SÒ™ÃÃ;ÓÃ;Ç;ÇÃS;Ò<
model : "8c½;“Ã;óÂ ; Á;“¸;ÃÌ<" ÀÒ$f÷ÓÍ;ÒFWÃÃ® ÒW2®ÃÃÓÖFVÂthousandsSeparator:
" ", defaultValue: '0'},Ðnumber : {decimalSeparator:".", thousandsSeparator: "
", decimalPlaces: 2, defaultValue: '0.00'},Ðcurrency : {decimalSeparator:".",
thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0.00'},Ðdate : ™ÐF ”æ ÖW3¢  ™½"9£Å< "Â #”;SÅ", ":CÁ;’"Â™#¤9£Å<,¹":°µÃÂÂ##;
":CÁ:óÄ;r"Â #¤;SÄ:ÃÃ¢Ó¢¢ÇF„æ ÖWÃÃ™Ó¢9“±;Ò"Â<#‡<S²;SÅ:ãÃÃ<#£ÃÃ#;#±Á¿"Ð9Ã±;’"Â #";óÅ;Ò"Â #™
"9Cµ;¢9Í±;Ó¿<S¬< ¹;óÂ", ":cµ;#Á;óÅ:ÃÁ;“¿<""Â #œ:ÃÃ<ÓÍ;ÕÂÒ,¢"9#À;Â"Â#¼;ÃÃ#3ÒÃÂ#œÃ%ÒÃ #™;
function (j) {return j == 1 || j > 1 ? [';ruÕ´Ö F,æÖ–â,†¢ Ò  ’ R   Â 2•Ò ¢ rwÓÍ
srcformat: 'Y-m-d',Ð–æWvf÷&Ö C¢ vBöÒõ’™Í  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇÇ2ÕÒ™ÍÖ 6·2 ¢ ½
’            •4óƒc  Æöæs¢%’ÖÒÖB ƒ¦“§2"Í            •4óƒc  6†÷'C¢%’ÖÒÖB"Í
’            6†÷'DF FS¢ &âö¢õ’"Í            ÆöætF FS¢ &ÂÂ b BÂ ’"Í
FullDateTime: "l, F d, Y g:i:s A",Ð            ÖöçF„F “¢ $b B"Í
ShortTime: "g:i A",Ð            ÆöæuF–ÖS¢ &s¦“§2  "Í
SortableDateTime: "Y-m-d\\TH:i:s",Ð            Væ–fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÐ
d H:i:sO",Ð            –V $ÖöçFƒ¢ $bÂ ’´        ÒÍ        &Vf÷&Ö D gFW$VF—B ¢
falseÐ}™Ð,ÐaseLinkUrl: '',ÐhowAction: '',Ð   F &vWC¢ rrÍ    6†V6¶&÷, ¢
{disabled:true},ÐidName : 'id'Ð});Ð})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-en.js

;(function($){Ð**Ð* jqGrid English TranslationÐ* Tony Tomov tony@trirand.comÐ
* http://trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½
recordtext: "View {0} - {1} of {2}",™Ðemptyrecords: "No records to view"™Ð
loadtext: "Loading...",™Ðpgtext : "Page {0} of {1}"™ÐÍ6V &6, ¢ ™½caption:
"Search...",™ÐFind: "Find"™Ðreset: "Reset"™Ðdata: [{ oper:'eq', text:'equal'},
{ oper:'ne', text:'not equal'},{ oper:'lt', text:'less'},{ oper:'le',
text:'less or equal'},{ oper:'gt', text:'greater'},{ oper:'ge', text:'greater
or equal'},{ oper:'bw', text:'begins with'},{ oper:'bn', text:'does not begin
with'},{ oper:'in', text:'is in'},{ oper:'ni', text:'is not in'},{ oper:'ew',
text:'ends with'},{ oper:'en', text:'does not end with'},{ oper:'cn',
text:'contains'},{ oper:'nc', text:'does not contain'},{ oper:'nu', text:'is
null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [{ op: "AND", text:
"all" },{ op: "OR", text: "any" }],™ÐoperandTitle : "Click to select search
operation.",™ÐresetTitle : "Reset Search Value"™ÐÍVF—B ¢ ™½addCaption: "Add
Record",™ÐeditCaption: "Edit Record"™ÐSubmit: "Submit"™ÐCancel: "Cancel"™Ð
bClose: "Close",™ÐsaveData: "Data has been changed! Save changes?"™ÐYes : "Yes"™Ð
bNo : "No",™ÐbExit : "Cancel"™Ðmsg: ™Ð&W V—&VC¢$f–VÆB —2 &W V—&VB™Í
number:"Please, enter valid number",™Ð–Ö–åf ÇVS¢'f ÇVR ×W7B &R w&V FW" F† â ÷"
equal to ",™Ð–Ö …f ÇVS¢'f ÇVR ×W7B &R ÆW72 F† â ÷" W V Â FÒ™ÍVÖ –Ã¢ &—2 æ÷B
valid e-mail",™Ð––çFVvW#¢ % ÆV 6RÂ VçFW" f Æ–B –çFVvW" f ÇVR™ÍF FS¢ % ÆV 6RÂ
enter valid date value",™Ð—W&Ã¢ &—2 æ÷B f Æ–B U$Ââ &Vf—, &W V—&VB ,v‡GG ¢òòr
or 'https://')",™Ð–æöFVf–æVB ¢ " —2 æ÷B FVf–æVB ™Íæ÷f ÇVR ¢ " &WGW&â f ÇVR —2
required!",™Ð–7W7FöÖ '& ’ ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &WGW&â '& ’ ™Í
customfcheck : "Custom function should be present in case of custom checking!"™Ð•
™}ÐÍf–Wr ¢ ™½caption: "View Record"™ÐClose: "Close"™ÐÍFVÂ ¢ ™½caption: "Delete",™Ð
msg: "Delete selected record(s)?",™ÐbSubmit: "Delete"™ÐCancel: "Cancel"™ÐÍæ b ¢ ™½
edittext: "",™Ðedittitle: "Edit selected row",™Ðaddtext:"",™Ðaddtitle: "Add new
row",™Ðdeltext: ""™Ðdeltitle: "Delete selected row",™Ðsearchtext: ""™Ðsearchtitle:
"Find records",™Ðrefreshtext: ""™Ðrefreshtitle: "Reload Grid",™Ðalertcap:
"Warning",™Ðalerttext: "Please, select row",™Ðviewtext: ""™Ðviewtitle: "View
selected row"™ÐÍ6öÂ ¢ ™½caption: "Select columns",™ÐSubmit: "Ok"™ÐCancel:
"Cancel"™ÐÍW'&÷'2 ¢ ™½errcap : "Error",™Ðourl : "No url is set",™Ðorecords: "No
records to process",™Ðmodel : "Length of colNames <> colModel!"™ÐÍf÷&Ö GFW" ¢ ™½
integer : {thousandsSeparator: ",", defaultValue: '0'},™Ðnumber :
{decimalSeparator:".", thousandsSeparator: ",", decimalPlaces: 2,
defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator:
",", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : ™Ð
dayNames: [™Ð"Sun", "Mon", "Tue", "Wed", "Thr", "Fri", "Sat™™™Ð"Sunday",
"Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday"™Ð•™Í
monthNames: [™Ð"Jan", "Feb", "Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep",
"Oct", "Nov", "Dec",™Ð"January", "February", "March", "April", "May", "June",
"July", "August", "September", "October", "November", "December"™Ð•™™ Õ Ò ¢
["am","pm","AM","PM"],™Ð•3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â ÇÂ ¢ â 2 ò ²w7BrÂ væBrÂ
'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th';},™Ð—7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢
'n/j/Y',™Ð— '6U&R ¢ õ²2UÂÂÂó¥ó²âÂÇEÇ2ÕÒÒ™ÍÖ 6·2 ¢™™½// see http://php.net/manual/
en/function.date.php for PHP format used in jqGrid™Ð// and see http://
docs.jquery.com/UI/Datepicker/formatDate™Ð// and https://github.com/jquery/
globalize#dates for alternative formats used frequently™Ð// one can find on
https://github.com/jquery/globalize/tree/master/lib/cultures many™Ð//
information about date, time, numbers and currency formats used in different
countries™Ð// one should just convert the information in PHP format™Ð
ISO8601Long:"Y-m-d H:i:s",™ÐISO8601Short:"Y-m-d"™™™Ð/ short date™™™Ð/ n -
Numeric representation of a month, without leading zeros™Ð// j - Day of the
month without leading zeros™Ð// Y - A full numeric representation of a year,
4 digits™Ð// example: 3/1/2012 which means 1 March 2012™™™ÐshortDate: "n/j/Y", //
in jQuery UI Datepicker: "M/d/yyyy"™Ð// long date™™™Ð/ l - A full textual
representation of the day of the week™Ð

™™//   F - A full textual representation of a monthÐ™//   d - Day of the month, 2 digits with leading zerosØ™Ø/   Y - A full numeric representation of a year, 4 digitsÐ™LongDate: "l, F d, Y", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy"Ð™// long date with long time:Ø™Ø/ l - A full textual representation of the day of the weekÐ™//   F - A full textual representation of a monthÐ™//   d - Day of the month, 2 digits with leading zerosÐ™//   Y - A full numeric representation of a year, 4 digitsØ™Ø/ g - 12-hour format of an hour without leading zerosÐ™//   i - Minutes with leading zerosÐ™//   s - Seconds, with leading zerosØ™Ø/   A - Uppercase Ante meridiem and Post meridiem (AM or PM)Ð™FullDateTime: "l, F d, Y g:i:s A", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy h:mm:ss tt"Ð™// month day:Ø™Ø/   F - A full textual representation of a monthÐ™//   d - Day of the month, 2 digits with leading zerosÐ™MonthDay: "F d", // in jQuery UI Datepicker: "MMMM ddØ™Ø/ short time (without seconds)Ð™//   g - 12-hour format of an hour without leading zerosÐ™//   i - Minutes with leading zerosØ™Ø/   A - Uppercase Ante meridiem and Post meridiem (AM or PM)Ð™ShortTime: "g:i A", // in jQuery UI Datepicker: "h:mm tt"Ð™// long time (with seconds)Ø™Ø/   g - 12-hour format of an hour without leading zerosÐ™//   i - Minutes with leading zerosØ™Ø/   s - Seconds, with leading zerosÐ™//   A - Uppercase Ante meridiem and Post meridiem (AM or PM)Ð™LongTime: "g:i:s A", // in jQuery UI Datepicker: "h:mm:ss tt"Ð™SortableDateTime: "Y-m-d\\TH:i:s",Ø™ØUniversalSortableDateTime: "Y-m-d H:i:sO",Ð™// month with yearØ™Ø/   Y - A full numeric representation of a year, 4 digitsÐ™//   F - A full textual representation of a monthØ™ØYearMonth: "F, Y" // in jQuery UI Datepicker: "MMMM, yyyy"Ð—ÙÍ&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ},Ð baseLinkUrl: '',Ø™showAction: '',Ø™target: '',Ø™checkbox : {disabled:true},Ø™idName : 'id'Ð™});Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-es.js

```
;(function($){Ð**Ð* jqGrid Spanish TranslationÐ* Traduccion jqGrid en Español
por Yamil BrachoÐ* Traduccion corregida y ampliada por Faserline, S.L. Ð*
http://www.faserline.comÐ* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½
recordtext: "Mostrando {0} - {1} de {2}",Ð    V× G—&V6÷&G3¢ %6–â &Vv—7G&÷2  VR
mostrar",™Ðloadtext: "Cargando...",™Ðpgtext : "Página {0} de {1}"™ÐÍ6V &6, ¢ ½
caption: "Búsqueda...",Ð    f–æC¢ $'W66 ""Í    &W6WC¢ $Æ–× – ""Í    öF F ¢
[{ oper:'eq', text:"igual "},{ oper:'ne', text:"no igual a"},{ oper:'lt',
text:"menor que"},{ oper:'le', text:"menor o igual que"},{ oper:'gt',
text:"mayor que"},{ oper:'ge', text:"mayor o igual a"},{ oper:'bw',
text:"empiece por"},{ oper:'bn', text:"no empiece por"},{ oper:'in',
text:"está en"},{ oper:'ni', text:"no está en"},{ oper:'ew', text:"termina
por"},{ oper:'en', text:"no termina por"},{ oper:'cn', text:"contiene"},
{ oper:'nc', text:"no contiene"},{ oper:'nu', text:'is null'},{ oper:'nn',
text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹{ op: "AND", text: "todo" },—² ÷ ¢ $õ""Â
text: "cualquier" }•ÒÍoperandTitle : "Click to select search operation.",™Ð
resetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ½     FD6  F–öã¢ $ w&Vv " &Vv—7G&ò"Í
’    VF—D6  F–öã¢ $ÖöF–f–6 " &Vv—7G&ò"Í    %7V&Ö—C¢ $wV &F ""Í    $6 æ6VÃ¢
"Cancelar",™ÐbClose: "Cerrar",™ÐaveData: "Se han modificado los datos, ¿guardar
cambios?",™ÐbYes : "Si",™ÐNo : "No",™ÐExit : "Cancelar",Ð   ×6s¢ ½
required:"Campo obligatorio",Ð        çVÖ&W#¢$–çG&öGW¦6  Vâ ï¦ÖW&ò"Í
minValue:"El valor debe ser mayor o igual a ",Ð        Ö …f ÇVS¢$VÂ f Æ÷" FV&R
ser menor o igual a ",Ð        VÖ –Ã¢ &æò W2 Væ  F—&V66Ÿ6â FR 6÷'&Vò n Æ–F "Í
’        –çFVvW#¢ $–çG&öGW¦6  Vâ f Æ÷" VçFW&ò"™Í–F FS¢ $–çG&öGW¦  Væ  fV6†
correcta ",™Ð—W&Ã¢ &æò W2 Væ  U$Â n Æ–F â  &Vf–¦ò &W VW&–Fò ,v‡GG ¢òòr ÷"
'https://')",™Ð–æöFVf–æVB ¢ " æò W7N  FVf–æ–Fòâ™Íæ÷f ÇVR ¢ " f Æ÷" FR &WF÷&æò W2
requerido.",™Ð–7W7FöÖ '& ’ ¢ $Æ  gVæ6Ÿ6â  W'6öæ Æ—¦ F  FV&R FWföÇfW" Vâ  '& ’â™Í
customfcheck : "La función personalizada debe estar presente en el caso de
validación personalizada."™ÐÒÍf–Wr ¢ ½    6  F–öã¢ $6öç7VÇF " &Vv—7G&ò"Í
bClose: "Cerrar"ÐÒÍFVÂ ¢ ½    6  F–öã¢ $VÆ–Ö–æ ""Í    ×6s¢ +ôFW6V  VÆ–Ö–æ "
los registros seleccionados?",Ð    %7V&Ö—C¢ $VÆ–Ö–æ ""Í    $6 æ6VÃ¢ $6 æ6VÆ "-
—ÒÍæ b ¢ ™½edittext: " ",Ð   VF—GF—FÆS¢ $ÖöF–f–6 " f–Æ  6VÆV66–öæ F "™Íaddtext:"
",Ð     FGF—FÆS¢ $ w&Vv " çVWf  f–Æ "Í    FVÇFW‡C¢ " "Í    FVÇF—FÆS¢ $VÆ–Ö–æ "
fila seleccionada",Ð    6V &6‡FW‡C¢ " "Í    6V &6‡F—FÆS¢ $'W66 " –æf÷&Ö 6Ÿ6â"Í
’    &Vg&W6‡FW‡C¢ ""Í    &Vg&W6‡F—FÆS¢ %&V6 &v " F F÷2"Í     ÆW'F6  ¢ $ f—6ò"Í
’     ÆW'GFW‡C¢ %6VÆV66–öæR Væ  f–Æ "™Íviewtext: "",™Ðviewtitle: "Ver fila
seleccionada"ÐÒÍ6öÂ ¢ ½    6  F–öã¢ $Ö÷7G& "öö7VÇF " 6öÇVÖæ 2"Í    %7V&Ö—C¢
"Enviar",Ð    $6 æ6VÃ¢ $6 æ6VÆ "™ÐÍW'&÷'2 ¢ ™½errcap : "Error",™Ðourl : "No se
ha especificado una URL",™Ðnorecords: "No hay datos para procesar",Ð   ÖöFVÂ ¢
"Las columnas de nombres son diferentes de las columnas de modelo"ÐÒÍ
formatter : {™Ðinteger : {thousandsSeparator: ".", defaultValue: '0'},™Ðumber :
{decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2,
defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator:
".", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0,00'},™Ðdate : {™Ð
dayNames:   [™™"Do", "Lu", "Ma", "Mi", "Ju", "Vi", "Sa™™™",ÐDomingo", "Lunes",
"Martes", "Miercoles", "Jueves", "Viernes", "Sabado"™™•ÒÍÖöçF„æ ÖW3¢™™½"Ene",
"Feb", "Mar", "Abr", "May", "Jun", "Jul", "Ago", "Sep", "Oct", "Nov", "Dic",Ð
™™"Enero", "Febrero", "Marzo", "Abril", "Mayo", "Junio", "Julio", "Agosto",
"Septiembre", "Octubre", "Noviembre", "Diciembre"™™•ÒÍ Õ Ò ¢
["am","pm","AM","PM"],™™•3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â    ÇÂ ¢ â  2 ò ²w7BrÂ væBrÂ
'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™—7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢
'd-m-Y',™—  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒ™ÍÖ 6·2 ¢’½           •4ƒc  ÆöæS¢%’ÖÒÐ
d H:i:s",Ð            •4ƒc  6†÷'C¢%’ÖÒÖB"Í           6†÷'DF FS¢ &âö¢õ’"Í
’            ÆöætF FS¢ &ÂÂ b BÂ ’"Í            gVÆÄF FUF–ÖS¢ &ÂÂ b BÂ ’ s¦“§2
A",Ð            ÖöçF„F “¢ $b B"Í            6†÷'EF–ÖS¢ &s¦’  "Í
LongTime: "g:i:s A",Ð            6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÖEÅÅDƒ¦“§2"Í
UniversalSortableDateTime: "Y-m-d H:i:sO",Ð            –V $ÖöçFƒ¢ $bÂ ’-
’        ÒÍ
```

’ &Vf÷&Ö D gFW$VF—B ¢ f Ç6™}™Ð baseLinkUrl: ''™Ð hideAction: '',Ð
’ F &vWC¢ rrÍ 6†V6¶&÷, ¢ ¶F—6 &ÆVC§G'VWÖ™idName : 'id™Ð});Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-fa.js

```
;(function ($) {Ð**Ð* jqGrid Persian TranslationÐ* Dual licensed under the
MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/ÐÐBæ¦w&–B Ò Bæ¦w&–B ÇÂ ·Ó½
$.extend($.jgrid,{Ð       defaults: {Ð           recordtext: "dfEbv(cB ³ Ò Ò ³ Ò 'c"
{2}",Ð           emptyrecords: "c ©d†1böÌ lÆ'd *ldfHbòÍ",Ð          loadtext: "b†'c  c&'c J...",Ð
pgtext: "cVAbÖG {0} bv2 {1}",ÐÐ       search: {Ð           caption: "bÆ3b¦,d,âââ"Í
            Find: "d¦'d *dr Gbr"Í Reset: "bv2 dfH",Ð     odata: [{ oper:'eq',
text:"b†1bv(c 'ÒÇ² ÷ W#¢væRrÂ FW‡C¢&Fbr (c 'b†1"},{ oper:'lt', text:"b†G"},{ oper:'le', te
{ oper:'gt', text:"bv2"},{ oper:'ge', text:"b†2c  b¦1"},{ oper:'bw', text:"cF1d†9 b†'"},
{ oper:'bn', text:"cF1d†9 df4d†/ b†'"},{ oper:'in', text:"df(bv4bò'ÒÇ² ÷ W#¢væ'rÂ FW‡C¢&9c
{ oper:'ew', text:"bv*dV'dR (br'ÒÇ² ÷ W#¢vVârÂ FW‡C¢&*dV'dR FcFHbò (br'ÒÇ² ÷ W#¢v6ârÂ FW‡C
{ oper:'nc', text:"df(bv4bò -bvHlÂ'ÒÇ² ÷ W#¢vçRrÂ FW‡C¢v–2 çVÆÂwÒÇ² ÷ W#¢væârÂ FW‡C¢v–2 æ÷
null'}],Ð           groupOps: [{Ð               op: "AND",Ð
text: "j–D"Ð        },Ð           {Ð               op: "OR",Ð
text: "dV,dVHc'-    }],Ð–÷ W& æEF–FÆR ¢ $6Æ–6² Fò 6VÆV7B 6V &6, ÷ W& F–öââ™Í
resetTitle : "Reset Search Value"Ð       },Ð       edit: {Ð
addCaption: "bv6bvAdr ©c /db ¢¦HCØ¦",Ð  editCaption: "d†Jc 'd¦4 c ©d†bÖbÍ",Ð  bSubmit: "b¶(b¢"Í
            bCancel: "bvFcV1bvA",Ð  bClose: "b†3b¦F",Ð     saveData: "böÌb¦' b¦9lÆÌc  ©c /
            bYes: "b†Ddr"Í       bNo: "bæÌc "Í       bExit: "bvFcV1bvA",Ð
msg: {Ð               required: "d JdF/dv' b†'d¦/ bæ*dVhugercFHdF7d,Ð c–/bò Hc–*b†1 d†'c
                minValue: "dVBbö'c  Hbv1bò 4böG b†'dmÆxV¢2ce:b¦dVBbò'dV3HbvHbò(4böG b†'d¦/
                email: "gæ3b¢ 'dF©b¦1d†Fd¦© d†'cintegerdr"EF7db†1d¦©Jc6/bò5bÖJbÒ Hbv1bò ©d
                date: "dF7d ' d¦© b¦'c Jbâ Ec–b†1 dbvÌdØ jbFd¢2"5bÖÌbÒ FdVÌ b†'cF/. gæÌcF
'https://')",Ð               nodefined: " b¦9c Ìd  FcF/dr "Í  novalue: " dVBbö'c  (c  cF*l
bv3b¢ "Í           customarray: "b¦'b†9 cFEbr (bvÌbò Ed&/bvsbmfbÌdck/bvHb¦bvb†bÖFcF"dÐ E
b†'lÆ/ c67d†F b†' hf©bÆFjò /dF,Ð b†'dr /bvÌbWc ¢Ð'cFÌbò -   caption: "dfEbvÌcB 1j–Hc /",Ð
            bClose: "b†3b¦F"Ð },Ð       del: {Ð           caption: "bÖ0d "Í
            msg: "bv2 bÖ0d  c&JdfG dv'lÂ dfbmfbæ"bÖ0dböG dV7dV&bÆc6td¦/bv'Ícv'dB-
        },Ð       nav: {Ð           edittext: " ",Ð           edittitle: "d†Jc 'd¦4 c /d¦A
cF/dr"Í       addtext: " ",Ð           addtitle: "bvAc&HböF c /d¦AdbÆ'dx¦",Ð
",Ð           deltitle: "bÖ0d  1bö(d  GbvJ bvEbÌbvxtcF/dr",Ð
searchtitle: "bÆ3b¦,d†J c /d¦AÆ¢Ð eshtext: "",Ð           refreshtitle: "b†'c&Jbv(d¢ EbÆ/bò
            alertcap: "bv.cv'c "Í    alerttext: "dF7d ' d¦© c /d¦A bvEbtext( j–Fd¦/",Ð
"",Ð           viewtitle: "dfEbvÌcB 1j–Hc /",Ø dv'lÂ cdF*bÆb, 4böG"Ð  caption:
"dfEbvJcBö9böE dfEbvbmfbÌ¦Hb¶(b¢"Í       bCancel: "bvFcV1bvA",ÐÐ
errors: {Ð           errcap: "bæ7br"Í       nourl: "dvJhb "böl1c6J b¦Fc†JdR FcF/dr 'c6*",Ð
norecords: "dvJhb 1j–Hc /d¢ (c mdelc ¢bvÆdB EbvÆdc¢*dfFcdy",ÐÐV-bvDd  3b¦Hdb GbvJ dV/dB Ed
formatter: {Ð           integer: {Ð               thousandsSeparator: " ",Ð
                defaultValue: "0"Ð           },Ð           number: {Ð
                decimalSeparator: ".",Ð               thousandsSeparator: " ",Ð
                decimalPlaces: 2,Ð               defaultValue: "0.00"Ð
            },Ð           currency: {Ð               decimalSeparator: ".",Ð
                thousandsSeparator: " ",Ð               decimalPlaces: 2,Ð
                prefix: "",Ð               suffix: "",Ð
defaultValue: "0"Ð           },Ð           date: {Ð               dayNames:
["d¦©", "böH", "c6G", "hfGbv1", "gæFbÂ"Â &,dV9", "cFFb,"Â &Jj–4df(dr"Â &/d†4df(dr"Â &3dr 4
monthNames: ["Jan", "Feb", "Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep",
"Oct", "Nov", "Dec", "i†'dfHd¦G", "d Hc Jdr"Â &Ebv1c2"Â &"d†1d¦D", "dVG", "i†HbfF", "i†Hbf
                AmPm: ["b,æ8", "b,æ8", "d"æ8", "d"æ8"],Ð   S: function (b) {Ð
                return b < 11 || b > 13 ? ["st", "nd", "rd", "th"]
[Math.min((b - 1) % 10, 3)] : "th"Ð               },Ð
srcformat: "Y-m-d",Ð               newformat: "d/m/Y",Ð™parseRe : /[#%\\/:_;.,
\t\s-]/,Ð           masks: {Ð               ISO8601Long: "Y-m-d
H:i:s",Ð               ISO8601Short: "Y-m-d",Ð
ShortDate: "n/j/Y",Ð               LongDate: "l, F d, Y",Ð
                FullDateTime: "l, F d, Y g:i:s A",Ð
MonthDay: "F d",Ð               ShortTime: "g:i A",Ð
LongTime: "g:i:s A",Ð               SortableDateTime: "Y-m-d\\TH:i:s",Ð
                UniversalSortableDateTime: "Y-m-d H:i:sO",Ð
```

```
                    YearMonth: "F, Y"Ð                },Ð
reformatAfterEdit: falseÐ           },Ð           baseLinkUrl: "",Ð
showAction: "dfEbvJcB"Í    target: "",Ð           checkbox: {Ð
disabled: trueÐ           },Ð           idName: "id"Ð       }Ð   });Ð})
(jQuery);
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-fi.js

```
;(function($){Ð**Ð* jqGrid (fi) Finnish TranslationÐ* Jukka Inkeri  awot.fi
2010-05-19Ð* Alex Grönholm  alex.gronholm@nextday.fi  2011-05-18Ð* http://
awot.fiÐ* Dual licensed under the MIT and GPL licenses:Ð* http://
www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/
gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG3¢ ™½recordtext:
"Rivit {0} - {1} / {2}",Ð    V× G—&V6÷&G3¢ $V’ âf VÖÃ·—FWGBf VÖÃ·f’f VÖÃ²"Í™
loadtext: "Haetaan...",Ð™pgtext: "Sivu {0} / {1}"—ÐÍ6V &6ƒ¢ ½    6  F–öã¢
"Etsi...",Ð    f–æC¢ $WG6’"Í    &W6WC¢ %G–†¦VæâF VÖÃ²"Í    öF F ¢
[{ oper:'eq', text:"on"},{ oper:'ne', text:"ei ole"},{ oper:'lt',
text:"pienempi"},{ oper:'le', text:"pienempi tai yht&auml;suuri"},
{ oper:'gt', text:"suurempi"},{ oper:'ge', text:"suurempi tai
yht&auml;suuri"},{ oper:'bw', text:"alkaa"},{ oper:'bn', text:"ei ala"},
{ oper:'in', text:"joukossa"},{ oper:'ni', text:"ei joukossa"},{ oper:'ew',
text:"loppuu"},{ oper:'en', text:"ei lopu"},{ oper:'cn',
text:"sis&auml;lt&auml;&auml;"},{ oper:'nc', text:"ei sis&auml;ll&auml;"},
{ oper:'nu', text:"on tyhj&auml;"},{ oper:'nn', text:"ei ole tyhj&auml;"},
{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹
{ op: "AND", text: "kaikki" }, { op: "OR", text: "mik&auml; tahansa" }•ÒÍ™
operandTitle : "Click to select search operation.",Ð™resetTitle : "Reset Search
Value"™ÐÍVF—C¢ ½     FD6  F–öã¢ %WW6’ &—f’"Í    VF—D6  F–öã¢ $×Vö¶¶
rivi&auml;",Ð    %7V&Ö—C¢ $ô²"Í    $6 æ6VÃ¢ % W'R"Í™bClose: "Sulje",Ð™aveData:
"Tietoja muutettu! Tallennetaanko?",Ð™bYes: "Kyll&auml;",Ð™No: "Ei",Ð™Exit:
"Peru",Ð    ×6s¢ ½        &W V—&VC¢ '  ¶öÆÆ–æVâ"Í        çVÖ&W#¢ $ ææ
kelvollinen nro",Ð        Ö–åf ÇVS¢ & 'föâ öÇF f  7WW&V× ’ F ’ –‡Bf VÖÃ·7WW&’
kuin ",Ð        Ö …f ÇVS¢ & 'föâ öÇF f   –VæV× ’ F ’ –‡Bf VÖÃ·7WW&’ ·V–â "Í
’        VÖ –Ã¢ &V’ öÆR ¶VÇföÆÆ–æVâ 2f VÖÃ· ÷7F–÷6ö—FR"Í        –çFVvW#¢ $ ææ
kelvollinen kokonaisluku",Ð™–F FS¢ $ ææ  ¶VÇföÆÆ–æVâ  fÒ™ÍW&Ã¢ $V’ öÆR
kelvollinen linkki(URL). Alku oltava ('http://' tai 'https://')",Ð™–æöFVf–æVC¢ "
ei ole m&auml;&auml;ritelty!",Ð™–æ÷f ÇVS¢ "   ÇWV 'fò f  F—F  â ™Í7W7FöÖ '& “¢
"Oman funktion tulee palauttaa jono!",Ð™–7W7FöÖf6†V6³¢ $öÖ  gVæ·F–ò öâ
m&auml;&auml;ritelt&auml;v&auml; r&auml;&auml;t&auml;l&ouml;ity&auml;
tarkastusta varten!"Ð™ÐÍf–Ws¢ ½    6  F–öã¢ $âf VÖÃ·—Bf VÖÃ² &—f’"Í    $6Æ÷6S¢
"Sulje"ÐÒÍFVÃ¢ ½    6  F–öã¢ % ö—7F "Í    ×6s¢ % ö—7F  f Æ—GWB &—f—Cò"Í
bSubmit: "Poista",Ð    $6 æ6VÃ¢ % W'R—ÒÍæ c¢ ™½edittext: "",Ð   VF—GF—FÆS¢
"Muokkaa valittua rivi&auml;",Ð™addtext: "",Ð    FGF—FÆS¢ %WW6’ &—f’"Í
deltext: "",Ð    FVÇF—FÆS¢ % ö—7F  f Æ—GGR &—f’"Í    6V &6‡FW‡C¢ ""Í
searchtitle: "Etsi tietoja",Ð    &Vg&W6‡FW‡C¢ ""Í    &Vg&W6‡F—FÆS¢ $Æ F
uudelleen",Ð     ÆW'F6  ¢ %f &ö—GW2"Í     ÆW'GFW‡C¢ %f Æ—G6R &—f’"Í™viewtext:
"",Ð™viewtitle: "N&auml;yta valitut rivit"—ÐÍ6öÃ¢ ½    6  F–öã¢ %f Æ—G6R
sarakkeet",Ð    %7V&Ö—C¢ $ô²"Í    $6 æ6VÃ¢ % W'R—ÐÍW'&÷'2 ¢ ™½errcap: "Virhe",Ð
nourl: "URL on asettamatta",Ð™norecords: "Ei muokattavia tietoja",Ð   ÖöFVÃ¢
"Pituus colNames <> colModel!"ÐÒÍf÷&Ö GFW#¢ ™½integer: {thousandsSeparator: "",
defaultValue: '0'},Ð™number: {decimalSeparator:",", thousandsSeparator: "",
decimalPlaces: 2, defaultValue: '0,00'},Ð™currency: {decimalSeparator:",",
thousandsSeparator: "", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0,00'},Ð™date: {Ð™F ”æ ÖW3¢  ™½"Su", "Ma", "Ti", "Ke", "To", "Pe",
"La",Ð™"Sunnuntai", "Maanantai", "Tiistai", "Keskiviikko", "Torstai",
"Perjantai", "Lauantai"Ð™•ÐÍÖöçF„æ ÖW3¢™½"Tam", "Hel", "Maa", "Huh", "Tou",
"Kes", "Hei", "Elo", "Syy", "Lok", "Mar", "Jou",Ð™"Tammikuu", "Helmikuu",
"Maaliskuu", "Huhtikuu", "Toukokuu", "Kes&auml;kuu", "Hein&auml;kuu",
"Elokuu", "Syyskuu", "Lokakuu", "Marraskuu", "Joulukuu"Ð™•ÐÍ Õ Ó¢
["am","pm","AM","PM"],Ð™•3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â    ÇÂ ¢ â  2 ò ²w7BrÂ væBrÂ
'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},Ð™—7&6f÷&Ö C¢ u’ÖÒÖBr™ÍæWvf÷&Ö C¢
'd.m.Y',Ð™—  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒ™ÍÖ 6·3¢’½           •4ó‚ƒc  Æöæs¢%’ÖÒÖB
H:i:s",Ð            •4ó‚ƒc  6†÷'C¢%’ÖÒÖB"Í            6†÷'DF FS¢ &BæÒå’"Í
’            ÆöætF FS¢ &ÂÂ b BÂ ’"Í            gVÆÄF FUF–ÖS¢ &ÂÂ b BÂ ’ s¦“§2
A",Ð            ÖöçF„F “¢ $b B"Í            6†÷'EF–ÖS¢ &s¦’  "Í
LongTime: "g:i:s A",Ð            6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÖEÅÅD‚ƒ¦“§2"Í
UniversalSortableDateTime: "Y-m-d H:i:sO",Ð
```

’ –V $ÖöçFƒ¢ $bÂ ’-
’ ÒÍ &Vf÷&Ö D gFW$VF—B ¢ f Ç6™]}™ÐaseLinkUrl: ''™ÐhowAction: '',Ð
’ F &vWC¢ rrÍ 6†V6¶&÷ƒ¢ ¶F—6 &ÆVC§G'VWÒÍidName: 'id—Ý);Ð/ FIÐ)(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-fr.js

;(function($){Ð**Ð* jqGrid French TranslationÐ* Tony Tomov tony@trirand.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½ recordtext: "Enregistrements {0} - {1} sur {2}",™Ðemptyrecords: "Aucun enregistrement à afficher",™Ðloadtext: "Chargement...",™Ðpgtext : "Page {0} sur {1}"ÐÒÍ6V &6, ¢ ™½caption: "Recherche...",™Ðind: "Chercher",™Ðreset: "Réinitialiser",™Ðodata: [{ oper:'eq', text:"égal"},{ oper:'ne', text:"différent"},{ oper:'lt', text:"inférieur"},{ oper:'le', text:"inférieur ou égal"},{ oper:'gt', text:"supérieur"},{ oper:'ge', text:"supérieur ou égal"},{ oper:'bw', text:"commence par"},{ oper:'bn', text:"ne commence pas par"},{ oper:'in', text:"est dans"},{ oper:'ni', text:"n'est pas dans"}, { oper:'ew', text:"finit par"},{ oper:'en', text:"ne finit pas par"}, { oper:'cn', text:"contient"},{ oper:'nc', text:"ne contient pas"}, { oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [• { op: "AND", text: "tous" },—² ÷ ¢ $õ""Â FW‡C¢ & R Öö–ç2 Vâ" Ù],™Ð operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™½addCaption: "Ajouter",™ÐditCaption: "Editer",™ÐSubmit: "Valider",™ÐbCancel: "Annuler",™ÐClose: "Fermer",™ÐaveData: "Les données ont changé ! Enregistrer les modifications ?",™ÐbYes: "Oui",™ÐNo: "Non",™ÐExit: "Annuler",™Ðmsg: {™Ð&W V—&VC¢ $6† × ö&Æ–v Fö—&R™ÍçVÖ&W#¢ %6 —6—76W¢ Vâ æöÖ'&R correct",™Ð–Ö–åf ÇVS¢ $Æ f ÆWW" Fö—B §G&R 7W —&–WW&R ÷R –v ÆR ™ÍÖ …f ÇVS¢ $Æ valeur doit être inférieure ou égale à",™Ð–VÖ –Ã¢ &âvW7B   2 Vâ VÖ –Â 6÷'&V7B™Í integer: "Saisissez un entier correct",™Ð—W&Ã¢ &âvW7B   2 VæR G&W76R 6÷'&V7FRâ Préfixe requis ('http://' or 'https://')",™Ð–æöFVf–æVB ¢ " âvW7B   2 N–f–æ' ™Í novalue : " la valeur de retour est requise!",™Ð–7W7FöÖ '& ' ¢ %VæR föæ7F–öâ personnalisée devrait retourner un tableau (array)!",™Ð–7W7FöÖf6†V6² ¢ %VæR fonction personnalisée devrait être présente dans le cas d'une vérification personnalisée!"™ÐÒÍf–Wr ¢ ™½caption: "Voir les enregistrement",™ÐClose: "Fermer"Ð —ÒÍFVÂ ¢ ™½caption: "Supprimer",™Ðmsg: "Supprimer les enregistrements sélectionnés ?",™ÐbSubmit: "Supprimer",™ÐCancel: "Annuler"™ÐÍæ b ¢ ™½edittext: " ",™Ð edittitle: "Editer la ligne sélectionnée",™Ðaddtext:" ",™Ðaddtitle: "Ajouter une ligne",™Ðdeltext: " ",™Ðdeltitle: "Supprimer la ligne sélectionnée",™Ðsearchtext: " ",™Ðsearchtitle: "Chercher un enregistrement",™Ðrefreshtext: "",™Ðrefreshtitle: "Recharger le tableau",™Ðalertcap: "Avertissement",™Ðalerttext: "Veuillez sélectionner une ligne",™Ðviewtext: "",™Ðviewtitle: "Afficher la ligne sélectionnée"ÐÒÍ6öÂ ¢ ™½caption: "Afficher/Masquer les colonnes",™ÐSubmit: "Valider",™ÐbCancel: "Annuler"™ÐÍW'&÷'2 ¢ ™½errcap : "Erreur",™Ðourl : "Aucune adresse n'est paramétrée",™Ðnorecords: "Aucun enregistrement à traiter",™Ðmodel : "Nombre de titres (colNames) <> Nombre de données (colModel)!"ÐÒÍf÷&Ö GFW" ¢ ™½ integer : {thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0,00'},™Ðdate : {™Ð dayNames: [™™"Dim", "Lun", "Mar", "Mer", "Jeu", "Ven", "Sam™™",™ÐDimanche", "Lundi", "Mardi", "Mercredi", "Jeudi", "Vendredi", "Samedi"™Ð•™ÍÖöçF„æ ÖW3¢ ½ ™™"Jan", "Fév", "Mar", "Avr", "Mai", "Jui", "Jul", "Aou", "Sep", "Oct", "Nov", "Déc",™™"Janvier", "Février", "Mars", "Avril", "Mai", "Juin", "Juillet", "Aout", "Septembre", "Octobre", "Novembre", "Décembre"™Ð•™Í Õ Ò ¢ ["am","pm","AM","PM"],™Ð•3¢ gVæ7F–öâ †¢' ·&WGW&â ¢ ÓÒ ò vW"r ¢ vRs·™Í srcformat: 'Y-m-d',™Ð–æWvf÷&Ö C¢ vBöÒõ'™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÖ™ÍÖ 6·2 ¢™½ ISO8601Long:"Y-m-d H:i:s",™ÐISO8601Short:"Y-m-d™™",™ÐshortDate: "n/j/Y™™",™ÐlongDate: "l, F d, Y",™ÐFullDateTime: "l, F d, Y g:i:s A™™",™ÐmonthDay: "F d™™",™ÐshortTime: "g:i A",™ÐLongTime: "g:i:s A™™",™ÐsortableDateTime: "Y-m-d\\TH:i:s™™",™Ð UniversalSortableDateTime: "Y-m-d H:i:sO",™ÐYearMonth: "F, Y™™"™™Í reformatAfterEdit : false™Ð},™ÐbaseLinkUrl: '',™ÐshowAction: '',™Ðarget: '',™Ð checkbox : {disabled:true},™ÐidName : 'id™Ð});™Ð})(jQuery);™Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-gl.js

```
;(function($){Ð**Ð* jqGrid Galician TranslationÐ* Translated by Jorge
Barreiro <yortx.barry@gmail.com>Ð* Dual licensed under the MIT and GPL
licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://
www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð
defaults : {Ðrecordtext: "Amosando {0} - {1} de {2}",Ð   V× G—&V6÷&G3¢ %6Vâ
rexistros que amosar",Ðloadtext: "Cargando...",Ðgtext : "Páxina {0} de {1}"ÐÍ
search : {Ð    6  F–öã¢ $/§7 VVF ââá"Í     f–æC¢ $'W66 ""Í     &W6WC¢ $Æ–×  ""Í
'     öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢&–wV Â 'ÒÇ² ÷ W#¢væRrÂ FW‡C¢&F–fW&VçFR  'ÒÀ
{ oper:'lt', text:"menor que"},{ oper:'le', text:"menor ou igual que"},
{ oper:'gt', text:"maior que"},{ oper:'ge', text:"maior ou igual a"},
{ oper:'bw', text:"empece por"},{ oper:'bn', text:"non empece por"},
{ oper:'in', text:"está en"},{ oper:'ni', text:"non está en"},{ oper:'ew',
text:"termina por"},{ oper:'en', text:"non termina por"},{ oper:'cn',
text:"contén"},{ oper:'nc', text:"non contén"},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹{ op: "AND", text: "todo" },•
{ op: "OR",  text: "calquera" }•ÒÍoperandTitle : "Click to select search
operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½     FD6  F–öã¢
"Engadir rexistro",Ð    VF—D6  F–öã¢ $ÖöF–f–6 " &W†—7G&ò"Í    %7V&Ö—C¢
"Gardar",Ð    $6 æ6VÃ¢ $6 æ6VÆ ""ÍbClose: "Pechar",ÐaveData: "Modificáronse os
datos, quere gardar os cambios?",ÐbYes : "Si",ÐNo : "Non",ÐExit : "Cancelar",Ð
'    ×6s¢ ½        &W V—&VC¢$6 × ò ö'&–v F÷&–ò"Í        çVÖ&W#¢$–çG&öGW¦  Vâ
número",Ð        Ö–åf ÇVS¢$ò f Æ÷" FV&R 6W" Ö –÷" ÷R –wV Â   "Í
maxValue:"O valor debe ser menor ou igual a ",Ð        VÖ –Ã¢ &æöâ ' Vâ
enderezo de correo válido",Ð        –çFVvW#¢ $–çG&öGW¦  Vâ f Æ÷" VçFV—&ò"Í•
date: "Introduza unha data correcta ",Ð—W&Ã¢ &æöâ ' Væ†  U$Â n Æ–F â  &Vf—†ò
requerido ('http://' ou 'https://')",Ð–æöFVf–æVB ¢ " æöâ W7N  FVf–æ–FòâÍ
novalue : " o valor de retorno é obrigatorio.",Ð–7W7FöÖ '& ' ¢ $  gVæ6Ÿ6â
persoalizada debe devolver un array.",Ð–7W7FöÖf6†V6² ¢ $  gVæ6Ÿ6â  W'6ö Æ—¦ F
debe estar presente no caso de ter validación persoalizada."Ð}ÐÍf–Wr ¢ ½
caption: "Consultar rexistro",Ð    $6Æ÷6S¢ % V6† "—ÒÍFVÂ ¢ ½    6  F–öã¢
"Eliminar",Ð    ×6s¢ $FW6W†  VÆ–Ö–æ " ÷2 &W†—7G&÷2 6VÆV66–öæ F÷3ò"Í
bSubmit: "Eliminar",Ð    $6 æ6VÃ¢ $6 æ6VÆ "—ÒÍæ b ¢ ½edittext: " ",Ð
edittitle: "Modificar a fila seleccionada",Ðaddtext:" ",Ð    FGF—FÆS¢ $Væv F—"
unha nova fila",Ð    FVÇFW‡C¢ " "Í    FVÇF—FÆS¢ $VÆ–Ö–æ "   f–Æ  6VÆV66–öæ F "Í
'    6V &6‡FW‡C¢ " "Í    6V &6‡F—FÆS¢ $'W66 " –æf÷&Ö 6Ÿ6â"Í    &Vg&W6‡FW‡C¢ ""Í
'    &Vg&W6‡F—FÆS¢ %&V6 &v " F F÷2"Í     ÆW'F6  ¢ $ f—6ò"Í     ÆW'GFW‡C¢
"Seleccione unha fila",Ðviewtext: "",Ðiewtitle: "Ver fila seleccionada"ÐÍ6öÂ ¢
{Ð    6  F–öã¢ $Ö÷7G& "öö7VÇF " 6öÇVÖæ 2"Í    %7V&Ö—C¢ $Vçf– ""Í    $6 æ6VÃ¢
"Cancelar"•ÒÍW'&÷'2 ¢ ½errcap : "Erro",Ðourl : "Non especificou unha URL",Ð
norecords: "Non hai datos para procesar",Ð    ÖöFVÂ ¢ $ 2 6öÇVÖæ 2 FR æöÖW2
son diferentes das columnas de modelo"ÐÒÍf÷&Ö GFW" ¢ ½integer :
{thousandsSeparator: ".", defaultValue: '0'},Ðnumber : {decimalSeparator:",",
thousandsSeparator: ".", decimalPlaces: 2, defaultValue: '0,00'},Ðcurrency :
{decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0,00'},Ðdate : {ÐF ”æ ÖW3¢  ½"Do", "Lu", "Ma", "Me",
"Xo", "Ve", "Sa",Ð"Domingo", "Luns", "Martes", "Mércoles", "Xoves", "Vernes",
"Sábado"Ð•ÍÖöçF„æ ÖW3¢½"Xan", "Feb", "Mar", "Abr", "Mai", "Xuñ", "Xul",
"Ago", "Set", "Out", "Nov", "Dec",Ð"Xaneiro", "Febreiro", "Marzo", "Abril",
"Maio", "Xuño", "Xullo", "Agosto", "Setembro", "Outubro", "Novembro",
"Decembro"Ð•Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%ÍÍ3¢ gVæ7F–öâ †¢' ·&WGW&â ¢ Â    ÇÂ ¢
> 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},Ð—7&6f÷&Ö C¢
'Y-m-d',Ð–æWvf÷&Ö C¢ vBÖÒÕ'ÍÍ  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÍÖ 6·2 ¢ ½
'            •4óƒc  Æöæs¢%'ÖÒÖB ƒ¦“§2"Í            •4óƒc  6†÷'C¢%'ÖÒÖB"Í
'            6†÷'DF FS¢ &âö¢õ'"Í            ÆöætF FS¢ &ÂÂ b BÂ '"Í
FullDateTime: "l, F d, Y g:i:s A",Ð            ÖöçF„F “¢ $b B"Í
ShortTime: "g:i A",Ð            ÆöæuF–ÖS¢ &s¦“§2  "Í
SortableDateTime: "Y-m-d\\TH:i:s",Ð            Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %'ÖÒÐ
d H:i:sO",Ð            –V $ÖöçFƒ¢ $bÂ ''        ÒÍ        &Vf÷&Ö D gFW$VF—B ¢
falseÐ
```

™},™ÐaseLinkUrl: '',™ÐhowAction: '',Ð F &vWC¢ rrÍ 6†V6¶&÷, ¢
{disabled:true},™ÐidName : 'id'™});Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-he.js

```
;(function($){Ð**Ð* jqGrid Hebrew TranslationÐ* Shuki Shukrun
shukrun.shuki@gmail.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the
MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "]åæ]•Ò {0} - {1} ™ÐÐ]ÚÚ¢Ò]ÚÚÐ "] Ù]ò è^•Õ]åÕ^
]ÅÕ™ÐÐ]ÚÚ¢Ò]ÚÚÐ "]…Õ^%ßgtext:Ð "]5ã {0} ]åÕ™ÐÚ {6} ™Ð ™caption: "]å×^ÐÐind",Ð]Üä^/"Í
Reset: "]Ð™]ÐÐÚ¢ÒÐ [{ oper:'eq', text:"^•Õ]UÔ"},{ oper:'ne', text:"]ÅÐ ^•Õ]UÔ"},{ oper:'lt'
text:"^uØ]ò'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢%ç]…ß ] Õ ^•Õ]UÔ"},{ oper:'gt', text:"]%Ó]UÜ"},{ oper:'ge'
^•Õ]UÔ"},{ oper:'bw', text:"]åê]uÙ]Â Ñ"},{ oper:'bn', text:"]ÅÐ ]åê]uÙ]Â Ñ"},{ oper:'in',
{ oper:'ni', text:"]ÅÐ ^ Þ^eÐ ] 'ÒÇ² ÷ W#¢vWrrÂ FW‡C¢%Þ^ ê]•Ù]Ò Ñ"},{ oper:'en', text:"]ÅÐ
{ oper:'cn', text:"]åÛ]•Ü"},{ oper:'nc', text:"]ÅÐ ]åÛ]•Ü"},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],ÐgroupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ %Ô]µÜ" },—² ÷ ¢
"OR",  text: "] ×]2 ÞÞ]ÚÚ¢ÒÐ,ÐdTitle : "Click to select search operation."™Ð
resetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™addCaption: "]EÕÐdÃ¢Ò]ÚÚÐ]B"Í^%Ê]UÚ ^…é]UÞ]B"
bSubmit: "^•ÜÐ]ÚÚ¢Ò]ÚÚÐ"Ó¢ÂÜÍse: "^™ÐÐ]ÚÚ¢Ò]ÚÚÐ"Ó¢ÂÜÍ"
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-hr.js

;(function($){Ð**Ð* jqGrid Croatian TranslationÐ* Version 1.0.1 (developed for jQuery Grid 4.4)Ð* msajko@gmail.comÐ* Ð* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð defaults : {™Ðrecordtext: "Pregled {0} - {1} od {2}",™Ðemptyrecords: "Nema zapisa",™Ðloadtext: "U Ö–F f Òââ™Ðpgtext : "Stranica {0} od {1}"™ÐÍ6V &6, ¢ ™½ caption: "Traži...",™ÐFind: "Pretraživanje",™Ðreset: "Poništi",™Ðdata: [{ oper:'eq', text:"jednak"},{ oper:'ne', text:"nije identi Ö â'ÒÇ² ÷ W#¢vÇBrÂ text:"manje"},{ oper:'le', text:"manje ili identi Öæò'ÒÇ² ÷ W#¢vwBrÂ text:"ve vR'ÒÇ² ÷ W#¢vvRrÂ FW‡C¢'fQ e ili identi Öæò'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢' ñ inje sa"},{ oper:'bn', text:"ne po Ö–æ¦R 6 'ÒÇ² ÷ W#¢v–ârÂ FW‡C¢&¦R R'ÒÀ { oper:'ni', text:"nije u"},{ oper:'ew', text:"završava sa"},{ oper:'en', text:"ne završava sa"},{ oper:'cn', text:"sadrži"},{ oper:'nc', text:"ne sadrži"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™Ð groupOps: [—² ÷ ¢ $'"Â FW‡C¢ '7fR" ÒÉ{ op: "ILI", text: "bilo koji" }•™ÍÍ operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™½addCaption: "Dodaj zapis",™ÐeditCaption: "Promijeni zapis",™Ð bSubmit: "Preuzmi",™ÐbCancel: "Odustani",™ÐClose: "Zatvri",™ÐsaveData: "Podaci su promijenjeni! Preuzmi promijene?",™ÐbYes : "Da",™ÐNo : "Ne",™ÐExit : "Odustani",™Ð msg: {™Ð—&W V—&VC¢% öÆ¦R ¦R ö& fW¦æò™ÍçVÖ&W#¢$ÖöÆ–ÒÂ VæW6—FR —7 & f â '&ö¢™Í minValue:"Vrijednost mora biti ve v –Æ' –FVçF' na™"ÖÐ…f ÇVS¢%g&–¦VFæ÷7B Ö÷& biti manja ili identi Öæ ™ÍVÖ –Ã¢ &æV—7 & f â RÖÖ –Â™Í–çFVvW#¢ $ÖöÆ–ÒÂ Væ¦WF' ispravan cijeli broj (integer)",™Ð–F FS¢ $ÖöÆ–ÒÂ Væ¦WF' —7 & f â F GVÒ ™ÍW&Ã¢ "neispravan URL. Prefiks je obavezan ('http://' or 'https://')",™Ð–æöFVf–æVB ¢ " nije definiran!",™Ð–æ÷f ÇVR ¢ " ¦ ‡F¦Wf â öF F ² ¦R ö& fW¦ â ™Í7W7FöÖ '& ' ¢ "Opcionalna funkcija trebala bi bili polje (array)!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ function should be present in case of custom checking!"™ÐÍf–Wr ¢ ™½caption: "Otvori zapis",™ÐbClose: "Zatvori"™ÐÍFVÂ ¢ ™½caption: "Obriši",™Ðsg: "Obriši ozna ÖVâ ¦ —2 –Æ' f™¦R æ¦–ƒò™ÍÐSubmit: "Obriši",™ÐCancel: "Odustani"™ÐÍæ b ¢ ™½ edittext: "",™Ðedittitle: "Promijeni obilježeni red",™Ðaddtext: "",™Ðaddtitle: "Dodaj novi red",™Ðdeltext: "",™Ðdeltitle: "Obriši obilježeni red",™Ðsearchtext: "",™Ð searchtitle: "Potraži zapise",™Ðrefreshtext: "",™Ðrefreshtitle: "Ponovo preuzmi podatke",™Ðalertcap: "Upozorenje",™Ðalerttext: "Molim, odaberi red",™Ðviewtext: "",™Ð viewtitle: "Pregled obilježenog reda"ÐÒÍ6öÂ ¢ ™½caption: "Obilježi kolonu",™Ð bSubmit: "Uredu",™ÐbCancel: "Odustani"™ÐÍW'&÷'2 ¢ ™½errcap : "Greška",™Ðourl : "Nedostaje URL",™Ðnorecords: "Bez zapisa za obradu",™Ðmodel : "colNames i colModel imaju razli Ö—GR GVÆ¦–çR—ÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: ".", defaultValue: '0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0,00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™½"Ned", "Pon", "Uto", "Sri", " ÆWB"Â % WB"Â %7V"™™Í"Nedjelja", "Ponedjeljak", "Utorak", "Srijeda", " ÆWGg'F ²"Â % WF ²"Â %7V&÷F™•™ÍÖöçF„æ ÖW3¢™½"Sij", "Velj", "Ožu", "Tra", "Svi", "Lip", "Srp", "Kol", "Ruj", "Lis", "Stu", "Pro",™™"Sije Ö æ¢"Â %fVÆ¦ a", "Ožujak", "Travanj", "Svibanj", "Lipanj", "Srpanj", "Kolovoz", "Rujan", "Listopad", "Studeni", "Prosinac"™•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–öâ (j) {return ''},™Ð–7&6f÷&Ö C¢ u'ÖÒÖB™ÍæWvf÷&Ö C¢ vBæÒå'â™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÀ \t\s-]/,™Ð–Ö 6·2 ¢™½// see http://php.net/manual/en/function.date.php for PHP format used in jqGrid™™// and see http://docs.jquery.com/UI/Datepicker/formatDate™™// and https://github.com/jquery/globalize#dates for alternative formats used frequently™™ISO8601Long: "Y-m-d H:i:s™™,™ÐISO8601Short: "Y-m-d™™,™Ð/ short date:™™//   d - Day of the month, 2 digits with leading zeros™™Ð/   m - Numeric representation of a month, with leading zeros™™//   Y - A full numeric representation of a year, 4 digits™™ShortDate: "d.m.Y.",'òò –â ¥ VW'' T' Datepicker: "dd.mm.yy."™™// long date:™™Ð/   l - A full textual representation of the day of the week™™//   j - Day of the month without leading zeros™™Ð/   F - A full textual representation of a month™™//   Y - A full numeric representation of a year, 4 digits™™LongDate: "l, j. F Y", // in jQuery UI Datepicker: "dddd, d. MMMM yyyy"Ð

™™// long date with long time:Ð™™Ð/   l - A full textual representation of the day of the weekÐ™™//   j - Day of the month without leading zerosÐ™™//   F - A full textual representation of a monthÐ™™Ð/   Y - A full numeric representation of a year, 4 digitsÐ™™//   H - 24-hour format of an hour with leading zerosÐ™™//   i - Minutes with leading zerosÐ™™Ð/   s - Seconds, with leading zerosÐ™™FullDateTime: "l, j. F Y H:i:s", // in jQuery UI Datepicker: "dddd, d. MMMM yyyy HH:mm:ss"Ð™™// month day:Ð™™Ð/   d - Day of the month, 2 digits with leading zerosÐ™™//   F - A full textual representation of a monthÐ™™MonthDay: "d F", // in jQuery UI Datepicker: "dd MMMM"Ð™™Ð/ short time (without seconds)Ð™™//   H - 24-hour format of an hour with leading zerosÐ™™Ð/   i - Minutes with leading zerosÐ™™ShortTime: "H:i", // in jQuery UI Datepicker: "HH:mm"Ð™™// long time (with seconds):Ð™™Ð/   H - 24-hour format of an hour with leading zerosÐ™™//   i - Minutes with leading zerosÐ™™Ð/   s - Seconds, with leading zerosÐ™™LongTime: "H:i:s", // in jQuery UI Datepicker: "HH:mm:ss"Ð™™Ð SortableDateTime: "Y-m-d\\TH:i:s",Ð™™UniversalSortableDateTime: "Y-m-d H:i:sO",Ð™™// month with yearÐ™™Ð/   F - A full textual representation of a monthÐ™™Ð/   Y - A full numeric representation of a year, 4 digitsÐ™™YearMonth: "F Y" // in jQuery UI Datepicker: "MMMM yyyy"Ð—Ùí&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ]Ð™™Ð,baseLinkUrl: '',Ð showAction: '',Ð™™target: '',Ðheckbox : {disabled:true},ÐidName : 'id'Ð—Ý);Ð)Ð (jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-hr1250.js

```
;(function($){Ð**Ð* jqGrid Croatian Translation (charset windows-1250)Ð*
Version 1.0.1 (developed for jQuery Grid 4.4)Ð* msajko@gmail.comÐ* Ð* Dual
licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/
mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid ||
{};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "Pregled {0} - {1} od {2}",™Ð
emptyrecords: "Nema zapisa",™Ðloadtext: "Uÿýitavam...™ÐpgÐtext : "Stranica {0} od
{1}"ÐÒÍ6V &6, ¢ ™caption: "Traÿýi...™ÍÐfind: "Pretraÿýivanje™ÐresÐet: "Poniÿýti™",Ð
odata : [{ oper:'eq', text:'jednak'}, { oper:'ne', text:'nije identiÿýan'},
{ oper:'lt', text:'manje'}, { oper:'le', text:'manje ili identiÿýno'},
{ oper:'gt', text:'veÿýe'},{ oper:'ge', text:'veÿýe ili identiÿýno'}, { oper:'bw',
text:'poÿýinje sa'},{ oper:'bn', text:'ne poÿýinje sa '},{ oper:'in', text:'je
u'},{ oper:'ni', text:'nije u'},{ oper:'ew', text:'zavrÿýava sa'},{ oper:'en',
text:'ne zavrÿýava sa'},{ oper:'cn', text:'sadrÿýi'},{ oper:'nc', text:'ne
sadrÿýi'},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}™,Ð
groupOps: [—² ÷ ¢ $’"Â FW‡C¢ '7fR" ÒÉ{ op: "ILI",  text: "bilo koji" }•ÒÍ
operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search
Value"ÐÒÍVF—B ¢ ™ÐaddCaption: "Dodaj zapis",™ÐeditCaption: "Promijeni zapis",™Ð
bSubmit: "Preuzmi",™ÐbCancel: "Odustani",™ÐClose: "Zatvri",™ÐsaveData: "Podaci su
promijenjeni! Preuzmi promijene?",™ÐbYes : "Da",™ÐNo : "Ne",™ÐExit : "Odustani",™Ð
msg: {™—&W V—&VC¢% öÆ¦R ¦R ö& fW¦æò™ÍçVÖ&W#¢$ÖöÆ–ÒÂ VæW6—FR —7 & f â '&ö¢™Í
minValue:"Vrijednost mora biti veÿýa ili identiÿýna™–Ö,™Ðf ÇVS¢%g&–¦VFæ÷7B Ö÷&
biti manja ili identiÿýna™,™ÐÖ –Ã¢ &æV—7 & f â RÖÖ –Â™Í–çFVvW#¢ $ÖöÆ–ÒÂ Væ¦WF’
ispravan cijeli broj (integer)",™Ð–F FS¢ $ÖöÆ–ÒÂ Væ¦WF’ —7 & f â F GVÒ ™ÍW&Ã¢
"neispravan URL. Prefiks je obavezan ('http://' or 'https://')",™Ð–æöFVf–æVB ¢ "
nije definiran!",™Ð–æ÷f ÇVR ¢ " ¦ ‡F¦Wf â  öF F ² ¦R ö& fW¦ â ™Í7W7FöÖ '& ’ ¢
"Opcionalna funkcija trebala bi bili polje (array)!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ
function should be present in case of custom checking!"™ÐÍf–Wr ¢ ™caption:
"Otvori zapis",™ÐbClose: "Zatvori"™ÐÍFVÂ ¢ ™caption: "Obriÿýim™,™Ð: "Obriÿýi oznaÿýen
zapis ili viÿýe njih?"™,™ÐbSubmit: "Obriÿýi™ÐbCancel: "Odustani"™ÐÍæ b ¢ ™ÐedittextÐ:
"",™Ðedittitle: "Promijeni obiljeÿýeni red™,™Ðtext: ""™,™Ðaddtitle: "Dodaj novi
red",™Ðdeltext: ""™,™Ðdeltitle: "Obriÿýi obiljeÿýeni red™,™Ðsearchtext: ""™,™Ðsearchtitle:
"Potraÿýi zapise"™,™Ðrefreshtext: ""™,™Ðrefreshtitle: "Ponovo preuzmi podatke",™Ð
alertcap: "Upozorenje",™Ðalerttext: "Molim, odaberi red",™Ðviewtext: "",™Ð
viewtitle: "Pregled obiljeÿýenog reda™ÐÒ6öÂ ¢ ™caption: "Obiljeÿýi kolonu™",Ð
bSubmit: "Uredu",™ÐbCancel: "Odustani"™ÐÍW'&÷'2 ¢ ™ÐerrcapÐ : "Greÿýka™,™Ðurl :
"Nedostaje URL",™Ðnorecords: "Bez zapisa za obradu",™Ðmodel : "colNames i
colModel imaju razliÿýitu duljinu™ÐÍf÷&Ö GFW" ¢ ™Ðinteger :
{thousandsSeparator: ".", defaultValue: '0'},™Ðnumber : {decimalSeparator:",",
thousandsSeparator: ".", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency :
{decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0,00'},™Ðdate : {™ÐF ”æ ÖW3¢  ™½"Ned", "Pon", "Uto",
"Sri", "ÿýet", "Pet", "Sub™™™,™ÐNedjelja", "Ponedjeljak", "Utorak", "Srijeda",
"ÿýetvrtak", "Petak", "Subota™™™ÍÖöçF„æ ÖW3¢™½"Sij", "Velj", "Oÿýu", "Tra", "Svi",
"Lip", "Srp", "Kol", "Ruj", "Lis", "Stu", "Pro",™™"Sijeÿýanj", "Veljaÿýa", "Oÿýujak",
"Travanj", "Svibanj", "Lipanj", "Srpanj", "Kolovoz", "Rujan", "Listopad",
"Studeni", "Prosinac"™•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–öâ †¢’ ·&WGW&â
''},™—7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢ vBæÒå’â™Í  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒ™Í
masks : {™// see http://php.net/manual/en/function.date.php for PHP format
used in jqGrid™™™// and see http://docs.jquery.com/UI/Datepicker/formatDate™™™Ð/
and https://github.com/jquery/globalize#dates for alternative formats used
frequently™™™ISO8601Long: "Y-m-d H:i:s™™™,™™™ÐISO8601Short: "Y-m-d™™™,™™™Ð/ short date:Ð
™™™//    d - Day of the month, 2 digits with leading zeros™™™Ð/    m - Numeric
representation of a month, with leading zeros™™™//    Y - A full numeric
representation of a year, 4 digits™™™ShortDate: "d.m.Y.",’òò –â ¥ VW'’ T’
Datepicker: "dd.mm.yy."™™™// long date:™™™Ð/    l - A full textual representation
of the day of the week™™™//    j - Day of the month without leading zeros™™™Ð/    F
- A full textual representation of a month™™™//    Y - A full numeric
representation of a year, 4 digits™™™LongDate: "l, j. F Y", // in jQuery UI
Datepicker: "dddd, d. MMMM yyyy"Ð
```

™™// long date with long time:Ð™™Ð/   l - A full textual representation of the day of the weekÐ™™//   j - Day of the month without leading zerosÐ™™//   F - A full textual representation of a monthÐ™™Ð/   Y - A full numeric representation of a year, 4 digitsÐ™™//   H - 24-hour format of an hour with leading zerosÐ™™//   i - Minutes with leading zerosÐ™™Ð/   s - Seconds, with leading zerosÐ™™FullDateTime: "l, j. F Y H:i:s", // in jQuery UI Datepicker: "dddd, d. MMMM yyyy HH:mm:ss"Ð™™// month day:Ð™™Ð/   d - Day of the month, 2 digits with leading zerosÐ™™//   F - A full textual representation of a monthÐ™™MonthDay: "d F", // in jQuery UI Datepicker: "dd MMMM"Ð™™Ð/ short time (without seconds)Ð™™//   H - 24-hour format of an hour with leading zerosÐ™™Ð/   i - Minutes with leading zerosÐ™™ShortTime: "H:i", // in jQuery UI Datepicker: "HH:mm"Ð™™// long time (with seconds):Ð™™Ð/   H - 24-hour format of an hour with leading zerosÐ™™//   i - Minutes with leading zerosÐ™™Ð/   s - Seconds, with leading zerosÐ™™LongTime: "H:i:s", // in jQuery UI Datepicker: "HH:mm:ss"Ð™™Ð SortableDateTime: "Y-m-d\\TH:i:s",Ð™™UniversalSortableDateTime: "Y-m-d H:i:sO",Ð™™// month with yearÐ™™Ð/   F - A full textual representation of a monthÐ™™Ð/   Y - A full numeric representation of a year, 4 digitsÐ™™YearMonth: "F Y" // in jQuery UI Datepicker: "MMMM yyyy"Ð—Ùí&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ]Ð™™Ð,baseLinkUrl: '',Ð showAction: '',Ð™™target: '',Ðheckbox : {disabled:true},ÐidName : 'id'Ð—Ý);Ð)Ð (jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-hu.js

;(function($){Ð*Ð* jqGrid Hungarian TranslationÐ* '7¦–vWG’ N Ò
udx6bs@freemail.huÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "Oldal {0} - {1} / {2}",™Ð
emptyrecords: "Nincs találat",™Ðloadtext: "Betöltés...",™Ðgtext : "Oldal {0} /
{1}"ÐÒÍ6V &6, ¢ ™½caption: "Keresés...",™Ðind: "Keres",™Ðeset: "Alapértelmezett",™Ð
odata: [{ oper:'eq', text:"egyenl 'ÒÇ² ÷ W#¢væRrÂ FW‡C¢&æVÒ Vw–VæÁQ"},
{ oper:'lt', text:"kevesebb"},{ oper:'le', text:"kevesebb vagy egyenl 'ÒÀ
{ oper:'gt', text:"nagyobb"},{ oper:'ge', text:"nagyobb vagy egyenl 'ÒÀ
{ oper:'bw', text:"ezzel kezd F–²'ÒÇ² ÷ W#¢v&ârÂ FW‡C¢&æVÒ W§¦VÂ ¶W¦AQdik"},
{ oper:'in', text:"tartalmaz"},{ oper:'ni', text:"nem tartalmaz"},
{ oper:'ew', text:"végz F–²'ÒÇ² ÷ W#¢vVârÂ FW‡C¢&æVÒ n–w¦Qdik"},{ oper:'cn',
text:"tartalmaz"},{ oper:'nc', text:"nem tartalmaz"},{ oper:'nu', text:'is
null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [—² ÷ ¢ $ äB"Â FW‡C¢
"all" },—² ÷ ¢ $õ""Â FW‡C¢ & ç’" Ù],™ÐperandTitle : "Click to select search
operation.",™ÐresetTitle : "Reset Search Value"™ÐÍVF—B ¢ ™½addCaption: "Új tétel",™Ð
editCaption: "Tétel szerkesztése",™ÐbSubmit: "Mentés",™ÐCancel: "Mégse",™ÐClose:
"Bezárás",™ÐsaveData: "A tétel megváltozott! Tétel mentése?",™ÐYes : "Igen",™Ð
bNo : "Nem",™ÐbExit : "Mégse",™Ðsg: "{Ð&W V—&VC¢$¿gFVÆW¡Q meZ™–çVÕ&W#¢$¾—& Æ²Â
adjon meg egy helyes számot",™Ð–Ö–åf ÇVS¢$æ w–ö&" f w’ Vw–VæÁQnek kell lenni mint
",™Ð–Ö …f ÇVS¢$¶—6V&" f w’ Vw–VæÁQnek kell lennie mint™"™ÐÐ –Ã¢ &†–. 2 VÖ –Æ>ÖÒ™Í
integer: "Kérjük adjon meg egy helyes egész számot",™Ð–F FS¢ $¾—& Æ² F¦öâ ÖVr
egy helyes dátumot",™Ð—W&Ã¢ &æVÒ †VÇ–W2 >ÖÒâ VÁQtag kötelez ,v‡GG ¢òòr f w’
'https://')",™Ð–æöFVf–æVB ¢ " æVÒ FVf–æž ÇB ™Íæ÷f ÇVR ¢ " f—77¦ N—.—6’ —'N–²
kötelez ™Í7W7FöÖ '& ’ ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &WGW&â '& ’ ™Í
customfcheck : "Custom function should be present in case of custom checking!"™•
™}ÐÍf–Wr ¢ ™½caption: "Tétel megtekintése",™ÐClose: "Bezárás"™ÐÍFVÂ ¢ ™½caption:
"Törlés",™Ðmsg: "Kiválaztott tétel(ek) törlése?",™ÐSubmit: "Törlés",™ÐCancel:
"Mégse"ÐÒÍæ b ¢ ™½edittext: "",™Ðdittitle: "Tétel szerkesztése",™Ðddtext:"",™Ð
addtitle: "Új tétel hozzáadása",™Ðdeltext: "",™Ðeltitle: "Tétel törlése",™Ð
searchtext: "",™Ðsearchtitle: "Keresés",™Ðefreshtext: "",™Ðefreshtitle:
"Frissítés",™Ðalertcap: "Figyelmeztetés",™Ðalerttext: "Kérem válasszon tételt.",™Ð
viewtext: "",™Ðviewtitle: "Tétel megtekintése"™ÐÍ6öÂ ¢ ™½caption: "Oszlopok
kiválasztása",™ÐbSubmit: "Ok",™ÐCancel: "Mégse"™ÐÍW'&÷'2 ¢ ™½errcap : "Hiba",™Ð
nourl : "Nincs URL beállítva",™Ðnorecords: "Nincs feldolgozásra váró tétel",™Ð
model : "colNames és colModel hossza nem egyenl —ÒÍf÷&Ö GFW" ¢ ™½integer :
{thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:",",
thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency :
{decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0,00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™½"Va", "Hé", "Ke",
"Sze", "Csü", "Pé", "Szo",™™"Vasárnap", "Hétf "Â $¶VFB"Â %7¦W&F "Â $7?ÇÖg'Of²"Â
"Péntek", "Szombat"™•™ÍÖöçF„æ ÖW3¢™™½"Jan", "Feb", "Már", "Ápr", "Máj", "Jún",
"Júl", "Aug", "Szep", "Okt", "Nov", "Dec",™™"Január", "Február", "Március",
"Április", "Május", "Június", "Július", "Augusztus", "Szeptember", "Október",
"November", "December"™•™Í Ö Ò ¢ ²&FR"Â&GR"Â$DR"Â$ER%™Í3¢ gVæ7F–öâ †¢’ ·&WGW&â
'.-ik';},™—7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢ u’öÒöB™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒ™Í
masks : {™™ISO8601Long:"Y-m-d H:i:s™™,™ÐISO8601Short:"Y-m-d™™,™ÐhortDate: "Y/j/n™™,™Ð
LongDate: "Y. F hó d., l",™™FullDateTime: "l, F d, Y g:i:s A™™,™ÐonthDay: "F d™™,™Ð
ShortTime: "a g:i",™™LongTime: "a g:i:s™™,™ÐortableDateTime: "Y-m-d\\TH:i:s™™,™Ð
UniversalSortableDateTime: "Y-m-d H:i:sO",™™YearMonth: "Y, F"™™ÐÍ
reformatAfterEdit : false™Ð},™™ÐaseLinkUrl: '',™™ÐhowAction: '',™™Ðarget: '',™Ð
checkbox : {disabled:true},™ÐidName : 'id'™Ð});™Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-id.js


```
;(function($){Ð**Ð* jqGrid English TranslationÐ* Tony Tomov tony@trirand.comÐ
* http://trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð.jgrid = $.jgrid || {};Ð.extend($.jgrid,{ÐFVf VÇG2 ¢ ™
recordtext: "Data {0} - {1} dari {2}",™Ðemptyrecords: "Tidak ada data",™Ð
loadtext: "Memuat...",™Ðpgtext : "Halaman {0} dari {1}"—ÐÍ6V &6, ¢ ™caption:
"Pencarian",™ÐFind: "Cari !",™Ðreset: "Segarkan",™Ðdata: [{ oper:'eq', text:"sama
dengan"},{ oper:'ne', text:"tidak sama dengan"},{ oper:'lt', text:"kurang
dari"},{ oper:'le', text:"kurang dari atau sama dengan"},{ oper:'gt',
text:"lebih besar"},{ oper:'ge', text:"lebih besar atau sama dengan"},
{ oper:'bw', text:"dimulai dengan"},{ oper:'bn', text:"tidak dimulai dengan"},
{ oper:'in', text:"di dalam"},{ oper:'ni', text:"tidak di dalam"},
{ oper:'ew', text:"diakhiri dengan"},{ oper:'en', text:"tidak diakhiri
dengan"},{ oper:'cn', text:"mengandung"},{ oper:'nc', text:"tidak
mengandung"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™Ð
groupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ & ÆÂ" ÒÉ{ op: "OR",  text: "any" }•™Í
operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search
Value"ÐÒÍVF—B ¢ ™ÐaddCaption: "Tambah Data",™ÐeditCaption: "Sunting Data",™Ð
bSubmit: "Submit",™ÐbCancel: "Tutup",™ÐClose: "Tutup",™ÐsaveData: "Data telah
berubah! Simpan perubahan?",™ÐbYes : "Ya",™ÐNo : "Tidak",™ÐExit : "Tutup",™Ðmsg: {™Ð
required:"kolom wajib diisi",™Ð–çVÖ&W#¢&† ç–  æöÖW" – ær F— W&&öÆV†¶ â™Í
minValue:"kolom harus lebih besar dari atau sama dengan",™Ð–Ö …f ÇVS¢&¶öÆöÒ
harus lebih kecil atau sama dengan",™Ð–VÖ –Ã¢ & Æ Ö B RÖÖ –Â F–F ² f Æ–B™Í
integer: "hanya nilai integer yang diperbolehkan",™Ð–F FS¢ &æ–Æ ’ F æVv Â F–F ²
valid",™Ð—W&Ã¢ $'V¶ â U$Â – ær f Æ–Bâ † &   wVæ ¶ â ,v‡GG ¢òòr ÷" v‡GG 3¢òòr’™Í
nodefined : " belum didefinisikan!",™Ð–æ÷f ÇVR ¢ " &WGW&â f ÇVR —2 &W V—&VB ™Í
customarray : "Custom function should return array!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ
function should be present in case of custom checking!"™ÐÍf–Wr ¢ ™ÐcaptionÍ
"Menampilkan data",™ÐbClose: "Tutup"—ÐÍFVÂ ¢ ™ÐcaptionÍ "Hapus",™Ðmsg: "Hapus data
terpilih?",™ÐbSubmit: "Hapus",™ÐbCancel: "Batalkan"—ÐÍæ b ¢ ™Ðedittext: "",™Ð
edittitle: "Sunting data terpilih",™Ðaddtext:"",™Ðaddtitle: "Tambah baris baru",™Ð
deltext: "",™Ðdeltitle: "Hapus baris terpilih",™Ðsearchtext: "",™Ðsearchtitle:
"Temukan data",™Ðrefreshtext: "",™Ðrefreshtitle: "Segarkan Grid",™Ðalertcap:
"Warning",™Ðalerttext: "Harap pilih baris",™Ðviewtext: "",™Ðviewtitle: "Tampilkan
baris terpilih"—ÐÒÍ6öÂ ¢ ™Ðcaption: "Pilih Kolom",™ÐSubmit: "Ok",™ÐCancel: "Batal"Ð
—ÒÍW'&÷'2 ¢ ™Ðerrcap : "Error",™Ðourl : "Tidak ada url yang diset",™Ðorecords:
"Tidak ada data untuk diproses",™Ðmodel : "Lebar dari colNames <> colModel!"—ÐÍ
formatter : {™Ðinteger : {thousandsSeparator: ".", defaultValue: '0'},™Ðnumber :
{decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2,
defaultValue: '0'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: ".",
decimalPlaces: 2, prefix: "Rp. ", suffix:"", defaultValue: '0'},™Ðdate : {™Ð
dayNames:   [™™"Ming", "Sen", "Sel", "Rab", "Kam", "Jum", "Sab"™™,™™Minggu",
"Senin", "Selasa", "Rabu", "Kamis", "Jumat", "Sabtu"™™•™ÍÖöçF„æ ÖW3¢™™½"Jan",
"Feb", "Mar", "Apr", "Mei", "Jun", "Jul", "Agu", "Sep", "Okt", "Nov", "Des",Ð
™™"Januari", "Februari", "Maret", "April", "Mei", "Juni", "Juli", "Agustus",
"September", "Oktober", "November", "Desember"™•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í
S: function (j) {return j < 11 || j > 13 ? ['st', 'nd', 'rd', 'th']
[Math.min((j - 1) % 10, 3)] : 'th';},™—7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢ vâö¢õ’™Í
parseRe : /[#%\\\/:_;.,\t\s-]/,™–Ö 6·2 ¢™½// see http://php.net/manual/en/
function.date.php for PHP format used in jqGrid™// and see http://
docs.jquery.com/UI/Datepicker/formatDate™// and https://github.com/jquery/
globalize#dates for alternative formats used frequently™// one can find on
https://github.com/jquery/globalize/tree/master/lib/cultures many™//
information about date, time, numbers and currency formats used in different
countries™// one should just convert the information in PHP format™
ISO8601Long:"Y-m-d H:i:s",™ISO8601Short:"Y-m-d",™/ short date™/    n -
Numeric representation of a month, without leading zeros™//    j - Day of the
month without leading zeros™//    Y - A full numeric representation of a year,
4 digits™
```

™™// example: 3/1/2012 which means 1 March 2012™™ÐshortDate: "n/j/Y", // in jQuery UI Datepicker: "M/d/yyyy"™™// long date:™™Ð/   l - A full textual representation of the day of the week™™//   F - A full textual representation of a month™™//   d - Day of the month, 2 digits with leading zeros™™Ð/   Y - A full numeric representation of a year, 4 digits™™LongDate: "l, F d, Y", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy"™™// long date with long time:™™Ð/ l - A full textual representation of the day of the week™™//   F - A full textual representation of a month™™//   d - Day of the month, 2 digits with leading zeros™™//   Y - A full numeric representation of a year, 4 digits™™Ð/ g - 12-hour format of an hour without leading zeros™™//   i - Minutes with leading zeros™™//   s - Seconds, with leading zeros™™Ð/   A - Uppercase Ante meridiem and Post meridiem (AM or PM)™™FullDateTime: "l, F d, Y g:i:s A", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy h:mm:ss tt"™™// month day:™™Ð/   F - A full textual representation of a month™™//   d - Day of the month, 2 digits with leading zeros™™MonthDay: "F d", // in jQuery UI Datepicker: "MMMM dd"™™Ð/ short time (without seconds)™™//   g - 12-hour format of an hour without leading zeros™™//   i - Minutes with leading zeros™™Ð/   A - Uppercase Ante meridiem and Post meridiem (AM or PM)™™ShortTime: "g:i A", // in jQuery UI Datepicker: "h:mm tt"™™// long time (with seconds):™™Ð/   g - 12-hour format of an hour without leading zeros™™//   i - Minutes with leading zeros™™Ð/   s - Seconds, with leading zeros™™//   A - Uppercase Ante meridiem and Post meridiem (AM or PM)™™LongTime: "g:i:s A", // in jQuery UI Datepicker: "h:mm:ss tt"™™SortableDateTime: "Y-m-d\\TH:i:s",™™UniversalSortableDateTime: "Y-m-d H:i:sO",™™// month with year™™Ð/   Y - A full numeric representation of a year, 4 digits™™//   F - A full textual representation of a month™™YearMonth: "F, Y" // in jQuery UI Datepicker: "MMMM, yyyy"™™—Ùí&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ}™™Ð baseLinkUrl: '',™™showAction: '',™™target: '',™™checkbox : {disabled:true},™™idName : 'id'™™Ý});™™})(jQuery);™™Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-is.js

;(function($){Ð**Ð* jqGrid Icelandic TranslationÐ* jtm@hi.is Univercity of IcelandÐ* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "Skoða {0} - {1} af {2}",Ð V× G–&V6÷&G3¢ $Væv " ng'6ÇW""Í™loadtext: "Hleður...",™Ðpgtext : "Síða {0} af {1}"™ÐÍ6V &6, ¢ ½ 6 F–öã¢ $ÆV–F ââá"Í Find: "Leita",Ð &W6WC¢ $VæGW'6WF¦ "Í öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢'6 Ö og"},{ oper:'ne', text:"ekki sama og"},{ oper:'lt', text:"minna en"}, { oper:'le', text:"minna eða jafnt og"},{ oper:'gt', text:"stærra en"}, { oper:'ge', text:"stærra eða jafnt og"},{ oper:'bw', text:"byrjar á"}, { oper:'bn', text:"byrjar ekki á"},{ oper:'in', text:"er í"},{ oper:'ni', text:"er ekki í"},{ oper:'ew', text:"endar á"},{ oper:'en', text:"endar ekki á"},{ oper:'cn', text:"inniheldur"},{ oper:'nc', text:"inniheldur ekki"}, { oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð w&÷W ÷ 3¢ ¹ { op: "AND", text: "allt" },–² ÷ ¢ $õ""Â FW‡C¢ &_ " Ù]™ÐperandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"™ÐÍVF–B ¢ ½ addCaption: "Bæta við færslu",Ð VF–D6 F–öã¢ $'&W–F ng'6ÇR"Í %7V&Ö–C¢ "Vista",Ð $6 æ6VÃ¢ $ŽgGF fŸ "™ÍbClose: "Loka"™ÐaveData: "Gögn hafa breyst! Vista breytingar?",™ÐbYes : "Já"™ÐNo : "Nei"™ÐExit : "Hætta við",Ð ×6s¢ ½ ’ &W V–&VC¢%&V–GW" W" æ _ 7–æÆVwW""Í çVÖ&W#¢%f–ç6 ÖÆVv 6WGGR inn tölu",Ð Ö–åf ÇVS¢&v–ÆF’ fW/ W" fW& ÖV–& Vâ _ ¦ fçB ör "Í ’ Ö …f ÇVS¢&v–ÆF’ fW/ W" fW& Ö–ææ Vâ _ ¦ fçB ör "Í VÖ –Ã¢ "er ekki löglegt email",Ð –çFVvW#¢ %f–ç6 ÖÆVv 6WGGR –æâ OfÇR"Í–F FS¢ "Vinsamlega setti inn dagsetningu",™–W&Ã¢ &W" V¶¶’ ÏfvÆVwB U$Ââ f çF " ('http://' eða 'https://')",™–æöFVf–æVB ¢ " W" V¶¶’ 6¶–Æw&V–çB ™Íæ÷f ÇVR ¢ " skilagildi nauðsynlegt!",™–7W7FöÖ '& ’ ¢ $f ÆÂ 6¶ Â 6¶–Æ g–Æ¶’ ™Í customfcheck : "Fall skal vera skilgreint!"™}ÐÍf–Wr ¢ ½ 6 F–öã¢ %6¶ÿ færslu",Ð $6Æ÷6S¢ $Æö¶ –ÒÍFVÂ ¢ ½ 6 F–öã¢ $WŸ "Í ×6s¢ $WŸ ofÆGVÒ færslum ?",Ð %7V&Ö–C¢ $WŸ "Í $6 æ6VÃ¢ $ŽgGF fŸ –ÒÍæ b ¢ ™½edittext: " ",Ð ’ VF–GF–FÆS¢ $'&W–F ng'6ÇR"™Íaddtext:" ",Ð FGF–FÆS¢ $ïÒ ng'6Æ "Í deltext: " ",Ð FVÇF–FÆS¢ $WŸ ng'6ÇR"Í 6V &6‡FW‡C¢ " "Í 6V &6‡F–FÆS¢ "Leita",Ð &Vg&W6‡FW‡C¢ ""Í &Vg&W6‡F–FÆS¢ $VæGW&†Æ "Í ÆW'F6 ¢ "Viðvörun",Ð ÆW'GFW‡C¢ %f–ç6 ÖÆVv fVÆGR ng'6ÇR"™Íviewtext: ""™Ðiewtitle: "Skoða valda færslu"ÐÒÍ6öÂ ¢ ½ 6 F–öã¢ %?Öæ ò fVÆ N Æ¶ "Í %7V&Ö–C¢ "Vista",Ð $6 æ6VÃ¢ $ŽgGF fŸ)ÐÍW'&÷'2 ¢ ™½errcap : "Villa"™Ðourl : "Vantar slóð",™Ðnorecords: "Engar færslur valdar",Ð ÖöFVÂ ¢ $ÆVævB 6öÄæ ÖW2 Ãâ colModel!"ÐÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™½"Sun", "Mán", "Þri", "Mið", "Fim", "Fös", "Lau",™™"Sunnudagur", "Mánudagur", "Þriðjudagur", "Miðvikudagur", "Fimmtudagur", "Föstudagur", "Laugardagur"Ð•™ÍÖöçF„æ ÖW3¢™½"Jan", "Feb", "Mar", "Apr", "Maí", "Jún", "Júl", "Ágú", "Sep", "Oct", "Nóv", "Des",™™"Janúar", "Febrúar", "Mars", "Apríl", "Maí", "Júný", "Júlý", "Ágúst", "September", "Október", "Nóvember", "Desember"™•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–öâ (j) {return j < 11 || j > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™–7&6f÷&Ö C¢ u’ÖÒÖB™ÍæWvf÷&Ö C¢ vBöÒõ’™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÀ \t\s-]/,™–Ö 6·2 ¢’½ •4óƒc ÆöæS¢%’ÖÒÖB ƒ¦“§2"Í ISO8601Short:"Y-m-d",Ð 6†÷'DF FS¢ &âö¢õ’"Í ÆöætF FS¢ &ÂÂ F d, Y",Ð gVÆÄF FUF–ÖS¢ &ÂÂ b BÂ ’ s¦“§2 "Í ÖöçF„F “¢ "F d",Ð 6†÷'EF–ÖS¢ &s¦’ "Í ÆöæuF–ÖS¢ &s¦“§2 "Í ’ 6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÖEÅÅDƒ¦“§2"Í UniversalSortableDateTime: "Y-m-d H:i:sO",Ð –V $ÖöçFƒ¢ $bÂ ’- ’ ÒÍ &Vf÷&Ö D gFW$VF–B ¢ f Ç6™]},™ÐaseLinkUrl: '',™ÐhowAction: '',Ð ’ F &vWC¢ rrÍ 6†V6¶&÷, ¢ ¶F–6 &ÆVC§G'VWÒ™ÍidName : 'id'™Ð});Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-ja.js

```
;(function($){Ð**Ð* jqGrid Japanese TranslationÐ* OKADA Yoshitada
okada.dev@sth.jpÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ½recordtext: "{2} \u4EF6\u4E2D {0} - {1}
\u3092\u8868\u793A ",Ð    V× G—&V6÷&G3¢ %ÇSƒƒc…ÇSs“4 ÇS3 S•ÇS3 „%ÇS3 T5ÇS3 #5ÇP
30FC\u30C9\u304C\u3042\u308A\u307E\u305B\u3093",Ðloadtext:
"\u8aad\u307f\u8fbc\u307f\u4e2d...",Ðpgtext : "{1} \u30DA\u30FC\u30B8\u4E2D
{0} \u30DA\u30FC\u30B8\u76EE "ÐÒÍ6V &6, ¢ ½    6  F–öã¢ %ÇSc“ 5ÇSvC#"âââ"Í
Find: "\u691c\u7d22",Ð    &W6WC¢ %ÇS3 V ÇS3 &%ÇS3 35ÇS3 3,"Í    öF F ¢
[{ oper:'eq', text:"\u6B21\u306B\u7B49\u3057\u3044"}, { oper:'ne',
text:"\u6B21\u306B\u7B49\u3057\u304F\u306A\u3044"},Ð           { oper:'lt',
text:"\u6B21\u3088\u308A\u5C0F\u3055\u3044"}, { oper:'le',
text:"\u6B21\u306B\u7B49\u3057\u3044\u304B\u5C0F\u3055\u3044"},Ð
{ oper:'gt', text:"\u6B21\u3088\u308A\u5927\u304D\u3044"}, { oper:'ge',
text:"\u6B21\u306B\u7B49\u3057\u3044\u304B\u5927\u304D\u3044"},Ð
{ oper:'bw', text:"\u6B21\u3067\u59CB\u307E\u308B"}, { oper:'bn',
text:"\u6B21\u3067\u59CB\u307E\u3089\u306A\u3044"},Ð           { oper:'in',
text:"\u6B21\u306B\u542B\u307E\u308C\u308B"}, { oper:'ni',
text:"\u6B21\u306B\u542B\u307E\u308C\u306A\u3044"},Ð           { oper:'ew',
text:"\u6B21\u3067\u7D42\u308F\u308B"}, { oper:'en',
text:"\u6B21\u3067\u7D42\u308F\u3089\u306A\u3044"},Ð           { oper:'cn',
text:"\u6B21\u3092\u542B\u3080"}, { oper:'nc',
text:"\u6B21\u3092\u542B\u307E\u306A\u3044"},Ð—² ÷ W#¢vçRrÂ FW‡C¢v—2 çVÆÂwÒÀ
{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ·½               op: "AND",Ð
                text: "\u3059\u3079\u3066\u306E"Ð           },Ð           {Ð
                op: "OR",Ð               text:
"\u3044\u305A\u308C\u304B\u306E"Ð           }],ÐoperandTitle : "Click to
select search operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½
addCaption: "\u30ec\u30b3\u30fc\u30c9\u8ffd\u52a0",Ð    VF—D6  F–öã¢
"\u30ec\u30b3\u30fc\u30c9\u7de8\u96c6",Ð    %7V&Ö—C¢ %ÇS“   ÇSFfS "Í
bCancel: "\u30ad\u30e3\u30f3\u30bb\u30eb",Ð ™bClose: "\u9589\u3058\u308b",Ð
      saveData:
"\u30C7\u30FC\u30BF\u304C\u5909\u66F4\u3055\u308C\u3066\u3044\u307E\u3059\u3002\u4FDD\u5B5
      bYes: "\u306F\u3044",Ð     bNo: "\u3044\u3044\u3048",Ð     bExit:
"\u30AD\u30E3\u30F3\u30BB\u30EB",Ð    ×6s¢ ½
required:"\u3053\u306e\u9805\u76ee\u306f\u5fc5\u9808\u3067\u3059\u3002",Ð
'
number:"\u6b63\u3057\u3044\u6570\u5024\u3092\u5165\u529b\u3057\u3066\u4e0b\u3055\u3044\u30
'
minValue:"\u6b21\u306e\u5024\u4ee5\u4e0a\u3067\u5165\u529b\u3057\u3066\u4e0b\u3055\u3044\u
'
maxValue:"\u6b21\u306e\u5024\u4ee5\u4e0b\u3067\u5165\u529b\u3057\u3066\u4e0b\u3055\u3044\u
'        VÖ –Ã¢ &RÐ
mail\u304c\u6b63\u3057\u304f\u3042\u308a\u307e\u305b\u3093\u3002",Ð
integer:
"\u6b63\u3057\u3044\u6574\u6570\u5024\u3092\u5165\u529b\u3057\u3066\u4e0b\u3055\u3044\u300
    ™–F FS¢
"\u6b63\u3057\u3044\u5024\u3092\u5165\u529b\u3057\u3066\u4e0b\u3055\u3044\u3002",Ð
          url:
"\u306F\u6709\u52B9\u306AURL\u3067\u306F\u3042\u308A\u307E\u305B\u3093\u3002\20\u30D7\u30E
('http://' \u307E\u305F\u306F 'https://')",Ð         nodefined: "
\u304C\u5B9A\u7FA9\u3055\u308C\u3066\u3044\u307E\u305B\u3093",Ð
novalue: " \u623B\u308A\u5024\u304C\u5FC5\u8981\u3067\u3059",Ð
customarray:
"\u30AB\u30B9\u30BF\u30E0\u95A2\u6570\u306F\u914D\u5217\u3092\u8FD4\u3059\u5FC5\u8981\u304
          customfcheck:
"\u30AB\u30B9\u30BF\u30E0\u691C\u8A3C\u306B\u306F\u30AB\u30B9\u30BF\u30E0\u95A2\u6570\u304
™}Ð
```

—ÒÍf–Wr ¢ ½ caption: "\u30EC\u30B3\u30FC\u30C9\u3092\u8868\u793A",Ð
bClose: "\u9589\u3058\u308B"ÐÒÍFVÂ ¢ ½ 6 F–öã¢ %ÇSS#F ÇS“ccB"Í ×6s¢ %ÇS•
078\u629e\u3057\u305f\u30ec\u30b3\u30fc\u30c9\u3092\u524a\u9664\u3057\u307e\u3
059\u304b\uff1f",Ð %7V&Ö—C¢ %ÇSS#F ÇS“ccB"Í $6 æ6VÃ¢
"\u30ad\u30e3\u30f3\u30bb\u30eb"ÐÒÍæ b ¢ ½ –VF—GFW‡C¢ " "Í VF—GF—FÆS¢
"\u9078\u629e\u3057\u305f\u884c\u3092\u7de8\u96c6",Ð addtext:" ",Ð
addtitle: "\u884c\u3092\u65b0\u898f\u8ffd\u52a0",Ð FVÇFW‡C¢ " "Í
deltitle: "\u9078\u629e\u3057\u305f\u884c\u3092\u524a\u9664",Ð 6V &6‡FW‡C¢
" ",Ð 6V &6‡F—FÆS¢ %ÇS3 V5ÇS3 #5ÇS3 f5ÇS3 3•ÇSc“ 5ÇSvC#""Í &Vg&W6‡FW‡C¢
"",Ð &Vg&W6‡F—FÆS¢ %ÇS3 # ÇS3 V ÇS3 35ÇS3 3•ÇS3 “%ÇS3 V ÇS3 VEÇS3 f5ÇS3 3’"Í
’ ÆW'F6 ¢ %ÇS†#ceÇSSCF "Í ÆW'GFW‡C¢
"\u884c\u3092\u9078\u629e\u3057\u3066\u4e0b\u3055\u3044\u3002",Ð
viewtext: "",Ð viewtitle:
"\u9078\u629E\u3057\u305F\u884C\u3092\u8868\u793A"ÐÒÍ6öÂ ¢ ½ 6 F–öã¢
"\u5217\u3092\u8868\u793a\uff0f\u96a0\u3059",Ð %7V&Ö—C¢ %ÇS“ ÇSFfS "Í
bCancel: "\u30ad\u30e3\u30f3\u30bb\u30eb"ÐÒÍW'&÷'2 ¢ ™errcap :
"\u30a8\u30e9\u30fc",Ðnourl :
"URL\u304c\u8a2d\u5b9a\u3055\u308c\u3066\u3044\u307e\u305b\u3093\u3002",Ð
norecords:
"\u51e6\u7406\u5bfe\u8c61\u306e\u30ec\u30b3\u30fc\u30c9\u304c\u3042\u308a\u307e\u305b\u309
’ ÖöFVÂ ¢
"colNames\u306e\u9577\u3055\u304ccolModel\u3068\u4e00\u81f4\u3057\u307e\u305b\u3093\u3002"
—ÒÍf÷&Ö GFW" ¢ ½ integer: {Ð thousandsSeparator: ",",Ð
defaultValue: '0'Ð },Ð number: {Ð
decimalSeparator: ".",Ð thousandsSeparator: ",",Ð
decimalPlaces: 2,Ð defaultValue: '0.00'Ð
},Ð currency: {Ð decimalSeparator: ".",Ð
thousandsSeparator: ",",Ð decimalPlaces: 0,Ð
prefix: "",Ð suffix: "",Ð
defaultValue: '0'Ð },Ðdate : {ÐF ”æ ÖW3¢ ™½"\u65e5", "\u6708",
"\u706b", "\u6c34", "\u6728", "\u91d1", "\u571f",Ð™"\u65e5", "\u6708",
"\u706b", "\u6c34", "\u6728", "\u91d1", "\u571f"Ð•ÒÍÖöçF„æ ÖW3¢™½"1", "2", "3",
"4", "5", "6", "7", "8", "9", "10", "11", "12",Ð™"1\u6708", "2\u6708",
"3\u6708", "4\u6708", "5\u6708", "6\u6708", "7\u6708", "8\u6708", "9\u6708",
"10\u6708", "11\u6708", "12\u6708"Ð•ÒÍ Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%ÒÍ3¢ gVæ7F–öâ
(j) { return "\u756a\u76ee"; },Ð—7&6f÷&Ö C¢ u’ÖÒÖBÍæWvf÷&Ö C¢ vBöÒõ’Í
parseRe : /[#%\\\/:_;.,\t\s-]/,Ð–Ö 6·2 ¢’½ •4ófc ÆöæS¢%’ÖÒÖB ƒ¦“§2"Í
’ •4ófc 6†÷'C¢%’ÖÒÖB"Í 6†÷'DF FS¢ &âö¢õ’"Í
LongDate: "l, F d, Y",Ð gVÆÄF FUF–ÖS¢ &ÂÂ b BÂ ’ s¦“§2 "Í
’ ÖöçF„F “¢ $b B"Í 6†÷'EF–ÖS¢ &s¦’ "Í
LongTime: "g:i:s A",Ð 6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÖEÅÅDƒ¦“§2"Í
UniversalSortableDateTime: "Y-m-d H:i:sO",Ð –V $ÖöçFƒ¢ $bÂ ’-
’ ÒÍ &Vf÷&Ö D gFW$VF—B ¢ f Ç6™}™,ÐaseLinkUrl: ''™ÐhowAction: '',Ð
’ F &vWC¢ rrÍ 6†V6¶&÷, ¢ ¶F—6 &ÆVC§G'VWÒÍidName : 'id–™);™})(jQery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-kr.js

```
;(function($){Ð**Ð* jqGrid English TranslationÐ* Tony Tomov tony@trirand.comÐ
* http://trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½
recordtext: "¼ô®0 {0} - {1} / {2}™½ÐÐrecords: "Ô\ÂÜÕòaÕ‰ÇxtÅÆÅ¡ÐÊÊÐ¡gÐ"xtÐ: "Ó˜ÇtÉÀ
{0} / {1}"ÐÒÍ6V &6, ¢ ™½caption: "¬€ÀÉ™FinÐ "Ì>Ð®Ð¡eÐ: "Í™ÐÐÐTä;Ð[{ oper:'eq',
text:"¬ ²ä"},{ oper:'ne', text:"¬ ÉÀ ÅJ²ä"},{ oper:'lt', text:"Ç‘²ä"},{ oper:'le', text:"Ç
{ oper:'gt', text:"Ðl²ä"},{ oper:'ge', text:"Ðl¬p°˜ ¬ ²ä"},{ oper:'bw', text:"¸\ ÂÜÇ‘Õ\²ä"
{ oper:'bn', text:"¸\ ÂÜÇ‘ÕXÉÀ ÅJ²″²ä"},{ oper:'in', text:"°´ÅÐ Çˆ²ä"},{ oper:'ni', text:"
{ oper:'ew', text:"¸\ °]°œ²ä"},{ oper:'en', text:"¸\ °]°˜ÉÀ ÅJ²″²ä"},{ oper:'cn', text:"°´
{ oper:'nc', text:"°´ÅÐ ÈtÇ¬ÕXÉÀ ÅJ²″²ä"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'
not null'}],™groupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ ,€KØ " ÒÉ{ op: "OR",  text: ™Ç„ÇX" }•ÒÍ
operandTitle : "Click to select search operation.",™resetTitle : "Reset Search
Value"ÐÒÍVF—B ¢ ™½addCaption: "Õ‰™ÉÍ¡tCaption: "Õ‰™ÂSÜbmÐ: "È™ÁÇ¡ÐÐel: "ÍÉÁŒ",Ð
bClose: "²ë®0ä¡ÐData: "Ç•¸Ì¬™b¼Ás½: ÅÈÂÞÐ²ä!"ÈÐÞÉÕÅÅ¡Ð ÂÚÉÅÐÙ?™™Ð&W V—&VC¢-™L!•VÛªœx[,‹.B
number:"Ç Ö¨Õ™Ù-Ù¨ÐÐ¹ÇVÇ¢,%Ó¡™ÉÚÁ²Æ″ÇÇÐ¢,xÁœ™ZÁ¥Ô VÇ¢Ç,B,™ÁÚÇÉ¥Ô¥Ô¢,¥B¥ÉÚÃ¥Ô¼¥x¥Ç¡xÐÁÍÚŒ•Ê¡
Æ″™¡Ð&Ã¢ ,t  r j•UŒœ  T¬t  U$Ìx[,‹.Bâ ³Œz\Ùì]™—æÚÉÚÇÉÚÐ ¢T¡™V›™•æ¥VÇÚÚT¥ÚÚ¥Á¥™ÉŠÐ¡ÚÐ ³¢Ù
²ä!™¡ÐW7FöÖ '& ' ¢ , Ìjœy™•ÐW7FÚÚf6¡Ð6Ã ¢L$ÐWÁFöÒWÚÐÐ7Ð→öâ.B¡™ÚÁÉB &R  &W6VçB –â
case of custom checking!"Ð¡ÐÍf–Wr ¢ ™½caption: "Õ‰™ÈÚÚÚsÇÐ "²ÒÉÚÚÐ ¢ ™½caption: "À-
È ™™Ðg: "Á ÐÝ™bSÕ‰ÚÚtÀ-ÈÀÒÕÕÂÂ¡ÐÂ¡²È®ÍÒÁÇÉÐ ¢ ™½edittext: ""™Ðdittitle: "Á ÐÝ´  Õ‰ Ó¸ÉÑ",Ð
addtext:"",™Ðaddtitle: "Õ‰™ÂÚÇ¡ÐÐ: ""™Ðeltitle: "Á ÐÝseÕ‰hÈÇ¡ÐÐ",Ð™Ð
searchtitle: "Õ‰ ™®6ÍÇÐhtext: ""™Ðefreshtitle: "-ø¯alÜ¡tÂÀ¡",Ð¬™½alertÐtext: "Õ‰ÇD Á ÐÝÕXÁ8
Æ″™¡ÐewtÐext: ""™Ðiewtitle: "Á ÐÝÍ6ÖÕ‰¢È™ÐÐapÐion: "ÂÔÇÐSÁÐÐÍÕXÁ8™™Ð&ÐÐel: "ÍÒÁŒ"Ð
errors : {™Ðerrcap : "Æ$ÐÚÚrÐ : "Á$È ´ ™ÐÐÐÇÐÐ¡ÐÐÐ¡²È¡ã™ÕÐÐÐÕ‰Ç¡ÐÐÐ
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-lt.js

```
;(function($){Ð**Ð* jqGrid Lithuanian TranslationÐ* aur1mas aur1mas@devnet.ltÐ
* http://aur1mas.devnet.ltÐ* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™
recordtext: "Perži ·&–Ö  ³ Ò Ò ³ Ò ™¢ ³'Ò™Ëemptyrecords: " ç& ¡s n™WoadÍext:
"Kraunama...",Ðpgtext : "Puslapis {0} iš {1}™ÒÍ6V &6, ¢ ™caption: "Paieška...",Ð
Find: "Ieškoti",ÐReset: "Atstatyti",Ðdata: [{ oper:'eq', text:"lygu"},
{ oper:'ne', text:"nelygu"},{ oper:'lt', text:"mažiau"},{ oper:'le',
text:"mažiau arba lygu"},{ oper:'gt', text:"daugiau"},{ oper:'ge',
text:"daugiau arba lygu"},{ oper:'bw', text:"prasideda"},{ oper:'bn',
text:"neprasideda"},{ oper:'in', text:"reikšm r —& 'ÒÇ² ÷ W#¢væ’rÂ
text:"reikšm w2 á ra"},{ oper:'ew', text:"baigiasi"},{ oper:'en',
text:"nesibaigia"},{ oper:'cn', text:"yra sudarytas"},{ oper:'nc', text:"n w&
sudarytas"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð
groupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ 'f—6’" ÒÉ{ op: "OR",  text: "bet kuris" }•ÒÍ
operandTitle : "Click to select search operation.",ÐresetTitle : "Reset Search
Value"ÐÒÍVF—B ¢ ™addCaption: "Sukurti  ÷& ™ed¡ÍÐCaption: "Redaguoti  ÷& ™ ",Ð
bSubmit: "Išsaugoti",ÐbCancel: "Atšaukti",ÐbClose: "Uždaryti",ÐbSaveData:
"Duomenys buvo pakeisti! Išsaugoti pakeitimus?",ÐbYes : "Taip",ÐbNo : "Ne",Ð
bExit : "Atšaukti",Ðmsg: "Ð&W V—&VC¢% &—f ÆöÖ 2 Æ V¶ 2™ÍçVÖ&W#¢!.veskite tinkam R
numer ò™ÍÖ–åf ÇVS¢'&V–¹¦Ñ  turi b ·F’ F–FW6á  arba lygÛ …¦ÐÇVS¢'&V–¹¦Ñ  turi b ·F’
mažesn r  &&  Ç–v’™ÍVÖ –Ã¢ &æWFV—6–æv 2 VÂâ  §Fò  G&W6 2™Í–çFVvW#¢ !.veskite
teising R 7fV–± j ò 6¶™´FiF2¢Í!.veskite teising R ™—W&Ã¢Ð&&Æöv 2  G&W6 2â
Nepamirškite prid wF’ ,v‡GG ¢òòr  &&  v‡GG 3¢òòr’™ÍæöFVf–æVB ¢ " á ra apibr yçF™• "Í
novalue : " turi b ·F’ w& æ–æ Ö  ¶ö¶–  æ÷'2 &V–¹¦Ñ ™"–7W7FöÖ '& ’ ¢ $7W7FöÒ bÖ¦
turi gr Yæ–çF’ Ö 7—a ™"–7W7FöÖf6†V6² ¢ $7W7FöÒ bÖ¦  Akr wAs b ·F’ 7V·W'F Â  &–Y¢
bandant j R æ VF÷F’™}ÒÍf–Wr ¢ ™caption: "Perži ·! ti  ÷&™SW2Íie: "Uždaryti"ÐÍ
del : {Ðcaption: "Ištrinti",Ðmsg: "Ištrinti pažym wGW2 /rašus(-™ÐÍÍÍit:
"Ištrinti",ÐbCancel: "Atšaukti"ÒÍæ b ¢ ™edittext: "",Ðdittitle: "Redaguoti
pažym wA  eilutaddÍext:"",Ðddtitle: "Prid wF’ æ V¡  eilutdeltext: "",Ðeltitle:
"Ištrinti pažym wA  eilutsearchtext: "",Ðearchtitle: "Rasti  ÷& §W2™"Í
refreshtext: "",Ðrefreshtitle: "Perkrauti lentel ™ÍÍertcap: " ç7  jimas",Ð
alerttext: "Pasirinkite eilut ’™Íiewtext: "",Ðiewtitle: "Perži ·! ti pasirinkt R
eilut –ÒÍ6öÂ ¢ ™caption: "Pasirinkti stulpelius",ÐSubmit: "Gerai",ÐCancel:
"Atšaukti"ÐÒÍW'&÷'2 ¢ ™errcap : "Klaida",Ðourl : "Url reikšm r GW&’ !kti
perduota",Ðnorecords: "N w&  /raš 2Â ·W&—V÷2 !kt 2 v Æ–Ö  ™eoÍÍ’"Í"colNames
skai Ö—W2 Ãâ 6öÄÖöFVÂ 6¶ ’ iu÷ÒÍÐ÷&Ö GFW" ¢ ™integer : {thousandsSeparator:
"", defaultValue: '0'},Ðnumber : {decimalSeparator:",", thousandsSeparator:
"", decimalPlaces: 2, defaultValue: '0.00'},Ðcurrency : {decimalSeparator:",",
thousandsSeparator: "", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0.00'},Ðdate : {ÐF ”æ ÖW3¢  ™"Sek", "Pir", "Ant", "Tre", "Ket",
"Pen", "Šeš",Ð™"Sekmadienis", "Pirmadienis", "Antradienis", "Tre Ö– F–Væ—2"Â
"Ketvirtadienis", "Penktadienis", "Šeštadienis"Ð•ÒÍÖöçF„æ ÖW3¢™"Sau", "Vas",
"Kov", "Bal", "Geg", "Bir", "Lie", "Rugj", "Rugs", "Spa", "Lap", "Gru",Ð
™"Sausis", "Vasaris", "Kovas", "Balandis", "Geguž r"Â $&—)æVÆ—2"Â $Æ–W  "Â
"Rugpj ·F—2"Â %'Vw1 jis", "Spalis", "Lapkritis", "GruodisÒÍ Õ Ò ¢
["am","pm","AM","PM"],Ð•3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â    ÇÂ ¢ â  2 ò ²w7BrÂ væBrÂ
'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},Ð—7&6f÷&Ö C¢ u’ÖÒÖBrÍæWvf÷&Ö C¢
'd/m/Y',Ð—  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒÍÖ 6·2 ¢™½ISO8601Long:"Y-m-d H:i:s",Ð
ISO8601Short:"Y-m-d",Ð™ShortDate: "n/j/Y",ÐLongDate: "l, F d, Y",ÐFullDateTime:
"l, F d, Y g:i:s A",Ð™MonthDay: "F d",ÐShortTime: "g:i A",ÐLongTime: "g:i:s A",Ð
SortableDateTime: "Y-m-d\\TH:i:s",Ð™UniversalSortableDateTime: "Y-m-d H:i:sO",Ð
YearMonth: "F, Y"Ð—ÒÍ&Vf÷&Ö D gFW$VF—B ¢ f Çó},ÐbaseLinkUrl: '',ÐshowAction: '',Ð
target: '',Ðcheckbox : {disabled:true},ÐidName : 'id'—});Ð})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-mne.js

;(function($){Ð**Ð* jqGrid Montenegrian TranslationÐ* Bild Studio info@bild-studio.netÐ* http://www.bild-studio.comÐ* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð defaults : {™Ðrecordtext: "Pregled {0} - {1} od {2}",™Ðemptyrecords: "Ne postoji nijedan zapis",™Ðloadtext: "U Ö—F—f æ¦RââÃ™Ðpgtext : "Strana {0} od {1}"—ÐÍ search : {™Ðcaption: "Traženje...",™Ðind: "Traži",™Ðreset: "Resetuj",™Ðdata: [{ oper:'eq', text:"jednako"},{ oper:'ne', text:"nije jednako"},{ oper:'lt', text:"manje"},{ oper:'le', text:"manje ili jednako"},{ oper:'gt', text:"ve vR'ÒÀ { oper:'ge', text:"ve vR –Æ' ¦VFæ ¶ò'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢' ñ inje sa"}, { oper:'bn', text:"ne po Ö–æ¦R 6 'ÒÇ² ÷ W#¢v–ârÂ FW‡C¢&¦R R'ÒÇ² ÷ W#¢væ'rÂ text:"nije u"},{ oper:'ew', text:"završava sa"},{ oper:'en', text:"ne završava sa"},{ oper:'cn', text:"sadrži"},{ oper:'nc', text:"ne sadrži"}, { oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [• { op: "AND", text: "sva" },—² ÷ ¢ $õ""Â FW‡C¢ &&–Æò ¶ö¦R" Ù]™ÐperandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"—ÐÍVF—B ¢ {™ÐaddCaption: "Dodaj zapis",™ÐeditCaption: "Izmjeni zapis",™ÐSubmit: "Pošalji",™Ð bCancel: "Odustani",™ÐbClose: "Zatvori",™ÐaveData: "Podatak je izmjenjen! Sa ×Wf ¢ izmjene?",™ÐbYes : "Da",™ÐNo : "Ne",™ÐExit : "Odustani",™Ðsg: "™Ð&W V—&VC¢% öÆ¦R ¦R obavezno",™Ð–çVÖ&W#¢%VæW6—FR —7 & f â '&ö¢™ÍÖ–åf ÇVS¢'g&–¦VFæ÷7B Ö÷& &—F' fQ a od ili jednaka sa ",™Ð–Ö …f ÇVS¢'g&–¦VFæ÷7B Ö÷& &—F' Ö æ¦ –Æ' ¦VFæ ¶ 6 ™Í email: "nije ispravna email adresa, nije valjda da ne umiješ ukucati mail!?",™Ð• integer: "Ne zajebaji se unesi cjelobrojnu vrijednost ",™Ð–F FS¢ %VæW6—FR ispravan datum",™Ð—W&Ã¢ &æ–¦R —7 & f â U$Ââ ÷G&V& â ¦R &Vf–·2 ,v‡GG ¢òòr ÷" 'https://')",™Ð–æöFVf–æVB ¢ " æ–¦R FVf–æ—6 â ™Íæ÷f ÇVR ¢ " ¦ ‡F¦Wf æ ¦R povratna vrijednost!",™Ð–7W7FöÖ '& ' ¢ % &–Æ vñ ena funkcija treba da vrati niz™Ð,Ð customfcheck : "Prilago Væ gVæ¶6–¦ G&V& F 'VFR &—7WF æ R 6ÇQ aju prilago VæR &÷f¦W&R™ÐÍf–Wr ¢ ™caption: "Pogledaj zapis",™ÐClose: "Zatvori"—ÐÍ del : {™Ðcaption: "Izbrisi",™Ðsg: "Izbrisi izabran(e) zapise(e)?",™ÐSubmit: "Izbriši",™ÐbCancel: "Odbaci"—ÐÍæ b ¢ ™edittext: "",™Ðdittitle: "Izmjeni izabrani red",™Ðaddtext:"",™Ðddtitle: "Dodaj novi red",™Ðeltext: "",™Ðeltitle: "Izbriši izabran red",™Ðsearchtext: "",™Ðearchtitle: "Na ' ¦ —6RF™Íefreshtext: "",™Ð refreshtitle: "Ponovo u Ö—F ¢ öF F¶R™Íalertcap: "Upozorenje",™Ðalerttext: "Izaberite red",™Ðviewtext: "",™Ðiewtitle: "Pogledaj izabrani red"—ÐÍ6öÂ ¢ ™ caption: "Izaberi kolone",™ÐbSubmit: "OK",™ÐCancel: "Odbaci"—ÐÍW'&÷'2 ¢ ™errcap : "Greška",™Ðnourl : "Nije postavljen URL",™Ðorecords: "Nema zapisa za obradu",™Ð model : "Dužina modela colNames <> colModel!"—ÐÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™™"Ned", "Pon", "Uto", "Sre", " ÆWB"Â % WB"Â %7V"™Í"Nedelja", "Ponedeljak", "Utorak", "Srijeda", " ÆWGg'F ²"Â % WF ²"Â %7V&÷F™•™ÍÖöçF„æ ÖW3¢™™"Jan", "Feb", "Mar", "Apr", "Maj", "Jun", "Jul", "Avg", "Sep", "Okt", "Nov", "Dec",™™"Januar", "Februar", "Mart", "April", "Maj", "Jun", "Jul", "Avgust", "Septembar", "Oktobar", "Novembar", "Decembar"™•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–öâ †¢' ·&WGW&â ¢ Â   ÇÂ ¢ > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™Ð—7&6f÷&Ö C¢ 'Y-m-d',™Ð–æWvf÷&Ö C¢ vBöÒõ'™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒ™ÍÖ 6·2 ¢™™ ISO8601Long:"Y-m-d H:i:s",™™ISO8601Short:"Y-m-d",™™ÐhortDate: "n/j/Y",™™ÐongDate: "l, F d, Y",™™FullDateTime: "l, F d, Y g:i:s A",™™ÐonthDay: "F d",™™ÐhortTime: "g:i A",™™LongTime: "g:i:s A",™™ÐortableDateTime: "Y-m-d\\TH:i:s",™™Ð UniversalSortableDateTime: "Y-m-d H:i:sO",™™YearMonth: "F, Y"™™ÐÍ reformatAfterEdit : false™Ð},™™ÐaseLinkUrl: '',™™ÐhowAction: '',™™Ðarget: '',™™Ð checkbox : {disabled:true},™™ÐidName : 'id—™Ð});™Ð})(jQuery);™Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-nl.js

```
(function(a) {Ð a.jgrid = a.jgrid || {};Ð a.extend(a.jgrid,{Ð       defaults:Ð
        {Ð           recordtext: "regels {0} - {1} van {2}",Ð
emptyrecords: "Geen data gevonden.",Ð           loadtext: "laden...",Ð
            pgtext: "pagina  {0}  van {1}"Ð       },Ð       search:Ð       {Ð
            caption: "Zoeken...",Ð           Find: "Zoek",Ð           Reset:
"Herstellen",Ð           odata: [{ oper:'eq', text:"gelijk aan"},{ oper:'ne',
text:"niet gelijk aan"},{ oper:'lt', text:"kleiner dan"},{ oper:'le',
text:"kleiner dan of gelijk aan"},{ oper:'gt', text:"groter dan"},
{ oper:'ge', text:"groter dan of gelijk aan"},{ oper:'bw', text:"begint met"},
{ oper:'bn', text:"begint niet met"},{ oper:'in', text:"is in"},{ oper:'ni',
text:"is niet in"},{ oper:'ew', text:"eindigd met"},{ oper:'en',
text:"eindigd niet met"},{ oper:'cn', text:"bevat"},{ oper:'nc', text:"bevat
niet"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð
            groupOps: [{ op: "AND", text: "alle" }, { op: "OR", text: "een
van de"}],Ð–÷ W& æEF–FÆR ¢ $6Æ–6² Fò 6VÆV7B 6V &6, ÷ W& F–öââ™Í&W6WEF–FÆR ¢
"Reset Search Value"Ð       },Ð       edit:Ð       {Ð           addCaption:
"Nieuw",Ð           editCaption: "Bewerken",Ð           bSubmit: "Opslaan",Ð
            bCancel: "Annuleren",Ð           bClose: "Sluiten",Ð
saveData: "Er is data aangepast! Wijzigingen opslaan?",Ð           bYes: "Ja",Ð
            bNo: "Nee",Ð           bExit: "Sluiten",Ð           msg:Ð
            {Ð               required: "Veld is verplicht",Ð
number: "Voer a.u.b. geldig nummer in",Ð               minValue: "Waarde moet
groter of gelijk zijn aan ",Ð               maxValue: "Waarde moet kleiner of
gelijks zijn aan",Ð               email: "is geen geldig e-mailadres",Ð
                integer: "Voer a.u.b. een geldig getal in",Ð
date: "Voer a.u.b. een geldige waarde in",Ð               url: "is geen
geldige URL. Prefix is verplicht ('http://' or 'https://')",Ð
nodefined : " is not defined!",Ð               novalue : " return value is
required!",Ð               customarray : "Custom function should return
array!",Ð               customfcheck : "Custom function should be present in
case of custom checking!"Ð           }Ð       },Ð       view:Ð       {Ð
            caption: "Tonen",Ð           bClose: "Sluiten"Ð       },Ð
del:Ð       {Ð           caption: "Verwijderen",Ð           msg: "Verwijder
geselecteerde regel(s)?",Ð           bSubmit: "Verwijderen",Ð
bCancel: "Annuleren"Ð       },Ð       nav:Ð       {Ð           edittext: "",Ð
            edittitle: "Bewerken",Ð           addtext: "",Ð
addtitle: "Nieuw",Ð           deltext: "",Ð           deltitle: "Verwijderen",Ð
            searchtext: "",Ð           searchtitle: "Zoeken",Ð
refreshtext: "",Ð           refreshtitle: "Vernieuwen",Ð           alertcap:
"Waarschuwing",Ð           alerttext: "Selecteer a.u.b. een regel",Ð
            viewtext: "",Ð           viewtitle: "Openen"Ð       },Ð       col:Ð
        {Ð           caption: "Tonen/verbergen kolommen",Ð           bSubmit:
"OK",Ð           bCancel: "Annuleren"Ð       },Ð       errors:Ð       {Ð
            errcap: "Fout",Ð           nourl: "Er is geen URL gedefinieerd",Ð
            norecords: "Geen data om te verwerken",Ð           model: "Lengte
van 'colNames' is niet gelijk aan 'colModel'!"Ð       },Ð       formatter:Ð
        {Ð           integer:Ð           {Ð               thousandsSeparator:
".",Ð               defaultValue: "0"Ð           },Ð           number:Ð
            {Ð               decimalSeparator: ",",Ð
thousandsSeparator: ".",Ð               decimalPlaces: 2,Ð
defaultValue: "0.00"Ð           },Ð           currency:Ð           {Ð
                decimalSeparator: ",",Ð               thousandsSeparator: ".",Ð
                decimalPlaces: 2,Ð               prefix: "EUR ",Ð
                suffix: "",Ð               defaultValue: "0.00"Ð           },Ð
            date:Ð           {Ð               dayNames: ["Zo", "Ma", "Di",
"Wo", "Do", "Vr", "Za", "Zondag", "Maandag", "Dinsdag", "Woensdag",
"Donderdag", "Vrijdag", "Zaterdag"],Ð               monthNames: ["Jan",
"Feb", "Maa", "Apr", "Mei", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec",
"Januari", "Februari", "Maart", "April", "Mei", "Juni", "Juli", "Augustus",
```

```
"September", "October", "November", "December"],Đ                AmPm: ["am",
"pm", "AM", "PM"],Đ                S: function(b) {Đ                    return
b < 11 || b > 13 ? ["st", "nd", "rd", "th"][Math.min((b - 1) % 10, 3)] : "th"Đ
                },Đ                srcformat: "Y-m-d",Đ
newformat: "d/m/Y",Đ™parseRe : /[#%\\\/:_;.,\t\s-]/,Đ             masks:Đ
                {Đ                    ISO8601Long: "Y-m-d H:i:s",Đ
                    ISO8601Short: "Y-m-d",Đ                   ShortDate: "n/j/
Y",Đ                    LongDate: "l, F d, Y",Đ
FullDateTime: "l d F Y G:i:s",Đ                    MonthDay: "d F",Đ
                    ShortTime: "G:i",Đ                    LongTime: "G:i:s",Đ
                    SortableDateTime: "Y-m-d\\TH:i:s",Đ
UniversalSortableDateTime: "Y-m-d H:i:sO",Đ                   YearMonth: "F,
Y"Đ                },Đ                reformatAfterEdit: falseĐ           },Đ
            baseLinkUrl: "",Đ            showAction: "",Đ           target: "",Đ
            checkbox:Đ           {Đ                disabled: trueĐ           },Đ
            idName: "id"Đ       }Đ   });Đ})(jQuery);
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-pl.js

```
;(function($){Ð**Ð* jqGrid Polish TranslationÐ*   V¶ 7¢ 66† " ÇV¶ 7¤ g&VWG&VRç Í
 * http://FreeTree.plÐ*Ð* Updated names, abbreviations, currency and date/
time formats for Polish norms (also corresponding with CLDR v21.0.1 -->
http://cldr.unicode.org/index) Ð* Tomasz P –7¦V² G V7¦V´ vÖ –Âæ6öŸ http://
tpeczek.blogspot.com; http://tpeczek.codeplex.comÐ*Ð* Dual licensed under the
MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "Poka Â ³ Ò Ò ³ Ò ¢ ³'Ò"Í
emptyrecords: "Brak rekordów do pokazania",™loadtext: "   F÷v æ–RââÃ™ÍÍtext :
"Strona {0} z {1}"ÐÒÍ6V &6, ¢ ™½caption: "Wyszukiwanie...",™Ðind: "Szukaj",™Ð
Reset: "Czy ±™ÖÐÐata: [{ oper:'eq', text:"dok & Fæ–R'ÒÇ² ÷ W#¢væRrÂ FW‡C¢'/1|ne
od"},{ oper:'lt', text:"mniejsze od"},{ oper:'le', text:"mniejsze lub równe"},
{ oper:'gt', text:"wi –·7¦R öB'ÒÇ² ÷ W#¢vvRrÂ FW‡C¢'v' ksze lub równe"},
{ oper:'bw', text:"zaczyna si ' öB'ÒÇ² ÷ W#¢v&ârÂ FW‡C¢&æ–R ¦ 7§–æ  6'  od"},
{ oper:'in', text:"jest w"},{ oper:'ni', text:"nie jest w"},{ oper:'ew',
text:"ko F7§' 6'  na"},{ oper:'en', text:"nie ko F7§' 6'  na"},{ oper:'cn',
text:"zawiera"},{ oper:'nc', text:"nie zawiera"},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],™groupOps: [–² ÷ ¢ $ äB"Â FW‡C¢ &÷& ¢" ÒÉ
{ op: "OR",  text: "lub" }•ÒÍoperandTitle : "Click to select search
operation.",™resetTitle : "Reset Search Value"ÐÍVF–B ¢ ™½addCaption: "Dodaj
rekord",™ÐeditCaption: "Edytuj rekord",™ÐSubmit: "Zapisz",™ÐCancel: "Anuluj",™Ð
bClose: "Zamknij",™ÐsaveData: "Dane zosta '' ¦Ö–Væ–öæR  ¦  –6   zmianyÐÍÍeÐ:
"Tak",™ÐbNo: "Nie",™ÐExit: "Anuluj",™Ðsg: {™Ð&W V–&VC¢ % öÆR ¦W7B w–Ö v æR™ÍçVÖ&W#¢
"Prosz ' w –6   poprawn R Æ–7¦Ö–ÃÐÇVS¢ 'v 'Fñ[ r ×W6' ''  wi –·7¦  ÇV" /7™æ  öB"Í
maxValue: "warto ±  musi by r Öæ–V§7¦  ÇV" /7væ ™ÖÐÖÍ–Ã¢ &æ–R ¦W7B  ÷ & vç–Ò
adresem e-mail",™––çFVvW#¢ % &÷7¦  wpisa r  ÷ & vá  lieÐbFS¢Í% &÷7¦  podaj
poprawn R F A™–WÐÃ¢ &¦W7B æ–WqBa ¶6–w–Ò  G&W6VÒ U$Ââ   Ö' taj o prefiksie
('http://' lub 'https://')",™–æöFVf–æVC¢ " æ–W¦FVf–æ–÷v æR ™Íæ÷f ÇVS¢ "
wymagana jest warto ±  zwracana™"–7W7FöÖ '& "¢ $gVæ¶6¦  æ–W7F æF &F÷v   ÷v–ææ
zwraca r F &Æ–1 ™"–7W7FöÖf6†V6³¢ $gVæ¶6¦  æ–W7F æF &F÷v   ÷v–ææ  ''  obecna w
przypadku niestandardowego sprawdzania!"™}ÐÍf–Wr ¢ ™½caption: "Poka Â &V¶÷&™"Í
bClose: "Zamknij"ÐÒÍFVÂ ¢ ™½caption: "Usu B™Íg: "Czy usun Q  wybrany rekord(y)?",Ð
bSubmit: "Usu B™ÍÐCancel: "Anuluj"ÐÍæ b ¢ ™½edittext: "",™Ðdittitle: "Edytuj
wybrany wiersz",™Ðaddtext: "",™Ðddtitle: "Dodaj nowy wiersz",™Ðeltext: "",™Ð
deltitle: "Usu B w–'& ç' v–W'7¢™Íearchtext: "",™Ðearchtitle: "Wyszukaj rekord",™Ð
refreshtext: "",™Ðrefreshtitle: "Prze & GV¢™Íertcap: "Uwaga",™Ðlerttext: "Prosz '
wybra r v–W'7¢™Íviewtext: "",™Ðiewtitle: "Poka Â w–'& ç' v–W'7ÐÍ6öÂ ¢ ™½caption:
"Poka ÂõV·'–¢ ¶öÇVÖç'™ÍSubmit: "Zatwierd ™ÍCancel: "Anuluj"ÐÍW'&÷'2 ¢ ™½errcap:
"B ! ™ÍÐrl: "Brak adresu url",™Ðorecords: "Brak danych",™Ðodel : "D 'Vvñ[ r 6öÄæ ÖW2
<> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: " ", defaultValue:
'0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces:
2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",",
thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:" z ""Â
defaultValue: '0,00'},™Ðdate : {™ÐF "æ ÖW3¢  ™½"niedz.", "pon.", "wt.", " ·"â"Â
"czw.", "pt.", "sob.",™Ð™"niedziela", "poniedzia &V²"Â 'wF÷&V²"Â ![roda",
"czwartek", "pi WFV²"Â '6ö&÷F™•ÖÍÖöçF„æ ÖW3¢™½"sty", "lut", "mar", "kwi",
"maj", "cze", "lip", "sie", "wrz", "pa ¢"Â &Æ–2"Â &w'R™Í"stycze B"Â &ÇWG'"Â
"marzec", "kwiecie B"Â &Ö ¢"Â &7¦W'v–V2"Â &Æ– –V2"Â '6–W' –QD", "wrzesie B"Â
"pa ¦G¦–W&æ–²"Â &Æ–7F÷  B"Â &w'VG¦–QD]ÐÐÕ Ò ¢ ²""Â""Â"%™Íí3¢ gVæ7F–öâ †¢'
{return '';},™–7&6f÷&Ö C¢ u'ÖÒÖBr™ÍæWvf÷&Ö C¢ vBæÒå'™Íí  '6U&R ¢ õ²2UÅÅÂó¥ó²âÀ
\t\s-]/,™–Ö 6·2 ¢™½ISO8601Long: "Y-m-d H:i:s™",™ÐSO8601Short: "Y-m-d™",™ÐhortDate:
"d.m.y",™Ð™LongDate: "l, j F Y™",™ÐullDateTime: "l, j F Y H:i:s™",™ÐonthDay: "j F™",Ð
ShortTime: "H:i",™Ð™LongTime: "H:i:s™",™ÐortableDateTime: "Y-m-d\\TH:i:s™",Ð
UniversalSortableDateTime: "Y-m-d H:i:sO",™Ð™YearMonth: "F Y™"–™Í
reformatAfterEdit : falseÐ},™ÐaseLinkUrl: '',™ÐhowAction: '',™Ðarget: '',™Ð
checkbox : {disabled:true},™ÐidName : 'id'–™});Ð})(jQuery);
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-pt-br.js

;(function($){Ð**Ð* jqGrid Brazilian-Portuguese TranslationÐ* Sergio Righi sergio.righi@gmail.comÐ* http://curve.com.brÐ* Ð* Updated by Jonnas FoniniÐ* http://fonini.netÐ*Ð*Ð* Updated by Fabio Ferreira da Silva fabio_ferreiradasilva@yahoo.com.brÐ* Ð*Ð* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð defaults : {Ðrecordtext: "Ver {0} - {1} de {2}",Ð V× G—&V6÷&G3¢ $æVæ‡VÒ registro para visualizar",Ðloadtext: "Carregando...",Ðpgtext : "Página {0} de {1}"ÐÒÍ6V &6, ¢ ½ 6 F–öã¢ % &ö7W& "âââ"Í f–æC¢ % &ö7W& ""Í &W6WC¢ "Resetar",Ð öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢&–wV Â'ÒÇ² ÷ W#¢væRrÂ text:"diferente"},{ oper:'lt', text:"menor"},{ oper:'le', text:"menor ou igual"},{ oper:'gt', text:"maior"},{ oper:'ge', text:"maior ou igual"}, { oper:'bw', text:"inicia com"},{ oper:'bn', text:"não inicia com"}, { oper:'in', text:"está em"},{ oper:'ni', text:"não está em"},{ oper:'ew', text:"termina com"},{ oper:'en', text:"não termina com"},{ oper:'cn', text:"contém"},{ oper:'nc', text:"não contém"},{ oper:'nu', text:"nulo"}, { oper:'nn', text:"não nulo"}],Ð w&÷W ÷ 3¢ ¹{ op: "AND", text: "todos" }, { op: "OR", text: "qualquer um" }•ÒÍoperandTitle : "Click to select search operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½ FD6 F–öã¢ "Incluir",Ð VF—D6 F–öã¢ $ ÇFW& ""Í %7V&Ö—C¢ $Vçf– ""Í $6 æ6VÃ¢ "Cancelar",ÐbClose: "Fechar",ÐsaveData: "Os dados foram alterados! Salvar alterações?",ÐbYes : "Sim",ÐNo : "Não",ÐExit : "Cancelar",Ð ×6s¢ ½ required:"Campo obrigatório",Ð çVÖ&W#¢% ÷" f f÷"Â –æf÷&ÖR VÒ ï¦ÖW&ò válido",Ð Ö–åf ÇVS¢'f Æ÷" FWfR 6W" –wV Â ÷R Ö –÷" VR "Í maxValue:"valor deve ser menor ou igual a",Ð VÖ –Ã¢ &W7FR RÖÖ –Â î6ò ’ válido",Ð –çFVvW#¢ % ÷" f f÷"Â –æf÷&ÖR VÒ f Æ÷" –çFV—&ò"Í–F FS¢ % ÷" favor, informe uma data válida",Ð—W&Ã¢ &î6ò ’ VÖ U$Â n Æ–F â &Vf—†ò obrigatório ('http://' or 'https://')",Ð–æöFVf–æVB ¢ " î6ò W7N FVf–æ–Fò ™Í novalue : " um valor de retorno é obrigatório!",Ð–7W7FöÖ '& ’ ¢ $gVî~6ò customizada deve retornar um array!",Ð–7W7FöÖf6†V6² ¢ $gVî~6ò 7W7FöÖ—¦ F FWfR estar presente em caso de validação customizada!"ÐÒÍf–Wr ¢ ½ 6 F–öã¢ %fW" Registro",Ð $6Æ÷6S¢ $fV6† "—ÒÍFVÂ ¢ ½ caption: "Apagar",Ð ×6s¢ $ v " registro(s) selecionado(s)?",Ð %7V&Ö—C¢ $ v ""Í $6 æ6VÃ¢ $6 æ6VÆ "—ÒÍ nav : {Ðedittext: " ",Ð VF—GF—FÆS¢ $ ÇFW& " &Vv—7G&ò 6VÆV6–öæ Fò"Íaddtext:" ",Ð FGF—FÆS¢ $–æ6ÇV—" æ÷fò &Vv—7G&ò"Í FVÇFW‡C¢ " "Í FVÇF—FÆS¢ "Apagar registro selecionado",Ð 6V &6‡FW‡C¢ " "Í 6V &6‡F—FÆS¢ % &ö7W& " registros",Ð &Vg&W6‡FW‡C¢ ""Í &Vg&W6‡F—FÆS¢ %&V6 '&Vv æFò F &VÆ "Í alertcap: "Aviso",Ð ÆW'GFW‡C¢ % ÷" f f÷"Â 6VÆV6–öæR VÒ &Vv—7G&ò"Íviewtext: "",Ðviewtitle: "Ver linha selecionada"ÐÍ6öÂ ¢ ½ 6 F–öã¢ $Ö÷7G& "ôW66öæFW" Colunas",Ð %7V&Ö—C¢ $Vçf– ""Í $6 æ6VÃ¢ $6 æ6VÆ "—ÒÍW'&÷'2 ¢ ™errcap : "Erro",Ðnourl : "Nenhuma URL definida",Ðorecords: "Sem registros para exibir",Ð ’ ÖöFVÂ ¢ $6ö× &–ÖVçFò FR 6öÄæ ÖW2 Ãâ 6öÄÖöFVÂ —ÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: " ", defaultValue: '0'},Ðnumber : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0,00'},Ðcurrency : {decimalSeparator:",", thousandsSeparator: ".", decimalPlaces: 2, prefix: "R$ ", suffix:"", defaultValue: '0,00'},Ðdate : {ÐF ”æ ÖW3¢ ™½"Dom", "Seg", "Ter", "Qua", "Qui", "Sex", "Sáb",Ð™"Domingo", "Segunda", "Terça", "Quarta", "Quinta", "Sexta", "Sábado"Ð•™ÍÖöçF„æ ÖW3¢™½"Jan", "Fev", "Mar", "Abr", "Mai", "Jun", "Jul", "Ago", "Set", "Out", "Nov", "Dez",Ð™"Janeiro", "Fevereiro", "Março", "Abril", "Maio", "Junho", "Julho", "Agosto", "Setembro", "Outubro", "Novembro", "Dezembro"Ð•™Í Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–öâ †¢’ ·&WGW&â j < 11 || j > 13 ? ['º', 'º', 'º', 'º'][Math.min((j - 1) % 10, 3)] : 'º'},Ð• srcformat: 'Y-m-d',Ð–æWvf÷&Ö C¢ vBöÒõ’™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒ™ÍÖ 6·2 ¢ ½ ’ •4óƒc Æöæs¢%’ÖÒÖB ƒ¦“§2"Í •4óƒc 6†÷'C¢%’ÖÒÖB"Í ’ 6†÷'DF FS¢ &âö¢õ’"Í ÆöætF FS¢ &ÂÂ b BÂ ’"Í FullDateTime: "l, F d, Y g:i:s A",Ð ÖöçF„F “¢ $b B"Í ShortTime: "g:i A",Ð ÆöæuF–ÖS¢ &s¦“§2 "Í SortableDateTime: "Y-m-d\\TH:i:s",Ð Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÐ d H:i:sO",Ð

’ –V $ÖöçFƒ¢ $bÂ ’‘ ÒÍ &Vf÷&Ö D gFW$VF—B ¢
falseÐ}™Ð,ÐbaseLinkUrl: ''™Ð,ÐshowAction: '',Ð F &vWC¢ rrÍ 6†V6¶&÷, ¢
{disabled:true},ÐidName : 'id'—Ð);Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-pt.js

;(function($){Ð**Ð* jqGrid Portuguese TranslationÐ Traduÿýÿýo da jqGrid em Portugues por Frederico Carvalho, http://www.eyeviewdesign.ptÐ* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð $.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "View {0} - {1} of {2}",Ð emptyrecords: "No records to view",Ðloadtext: "A carregar...",™Ðgtext : "Página {0} de {1}"ÐÒÍ6V &6, ¢ ½ 6 F–öã¢ $'W66 âââ"Í f–æC¢ % &ö7W& ""Í Reset: "Limpar",Ð öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢vW V ÂwÒÇ² ÷ W#¢væRrÂ FW‡C¢væ÷B equal'},{ oper:'lt', text:'less'},{ oper:'le', text:'less or equal'}, { oper:'gt', text:'greater'},{ oper:'ge', text:'greater or equal'}, { oper:'bw', text:'begins with'},{ oper:'bn', text:'does not begin with'}, { oper:'in', text:'is in'},{ oper:'ni', text:'is not in'},{ oper:'ew', text:'ends with'},{ oper:'en', text:'does not end with'},{ oper:'cn', text:'contains'},{ oper:'nc', text:'does not contain'},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð w&÷W ÷ 3¢ ¹{ op: "AND", text: "all" },—² ÷ ¢ $õ""Â FW‡C¢ & ç'" Ù]™ÐperandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ½ FD6 F–öã¢ "Adicionar Registo",Ð VF—D6 F–öã¢ $ÖöF–f–6 " &Vv—7Fò"Í %7V&Ö—C¢ "Submeter",Ð $6 æ6VÃ¢ $6 æ6VÆ ""™ÐbClose: "Fechar"™ÐaveData: "Data has been changed! Save changes?",™ÐbYes : "Yes"™ÐNo : "No"™ÐExit : "Cancel",Ð ×6s¢ ½ ' &W V—&VC¢$6 × ò ö'&–v Oÿ×&–ò"Í çVÖ&W#¢% ÷" f f÷"Â –çG&öGW¦ VÒ numero",Ð Ö–åf ÇVS¢$ò f Æ÷" FWfR 6W" Ö –÷" ÷R –wV Â VR"Í maxValue:"O valor deve ser menor ou igual a",Ð VÖ –Ã¢ $ïÿÖò ÿÒ VÒ VæFW&_ÿÖò de email vÿýlido",Ð –çFVvW#¢ % ÷" f f÷"Â –çG&öGW¦ VÒ çVÖW&ò –çFV—&ò"™Í• url: "is not a valid URL. Prefix required ('http://' or 'https://')",™Ð• nodefined : " is not defined!",™Ð–æ÷f ÇVR ¢ " &WGW&â f ÇVR —2 &W V—&VB ™™Í customarray : "Custom function should return array!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ function should be present in case of custom checking!"™ÐÍf–Wr ¢ ½ caption: "View Record",Ð $6Æ÷6S¢ $6Æ÷6R—ÒÍFVÂ ¢ ½ 6 F–öã¢ $VÆ–Ö–æ ""Í ' ×6s¢ $FW6V¦ VÆ–Ö–æ " ò‡2' &Vv—7Fò‡2' 6VÆV66–öæ Fò‡2"ò"Í %7V&Ö—C¢ "Eliminar",Ð $6 æ6VÃ¢ $6 æ6VÆ "—ÒÍæ b ¢ ™½edittext: " ",Ð VF—GF—FÆS¢ "Modificar registo seleccionado",™Ðaddtext:" ",Ð FGF—FÆS¢ $ F–6–öæ " æ÷fò registo",Ð FVÇFW‡C¢ " "Í FVÇF—FÆS¢ $VÆ–Ö–æ " &Vv—7Fò 6VÆV66–öæ Fò"Í searchtext: " ",Ð 6V &6‡F—FÆS¢ % &ö7W& ""Í &Vg&W6‡FW‡C¢ ""Í refreshtitle: "Actualizar",Ð ÆW'F6 ¢ $ f—6ò"Í ÆW'GFW‡C¢ % ÷" f f÷"Â seleccione um registo",™Ðviewtext: "",™Ðiewtitle: "View selected row"ÐÍ6öÂ ¢ ½ ' 6 F–öã¢ $Ö÷7G& "ôö7VÇF " 6öÇVæ 2"Í %7V&Ö—C¢ $Vçf– ""Í $6 æ6VÃ¢ "Cancelar"•ÒÍW'&÷'2 ¢ ™½errcap : "Erro"™Ðourl : "Nÿýo especificou um url™",Ð norecords: "Nÿýo existem dados para processar",Ð ÖöFVÂ ¢ %F Ö æ†ò Fò 6öÄæ ÖW2 <> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : {™ÐF "æ ÖW3¢ ™½"Dom", "Seg", "Ter", "Qua", "Qui", "Sex", "Sab",™™"Domingo", "Segunda-Feira", "Terÿýa-Feira", "Quarta-Feira", "Quinta-Feira", "Sexta-Feira", "Sÿýbado™™™ÐÍÖöçF„æ ÖW3¢™™½"Jan", "Fev", "Mar", "Abr", "Mai", "Jun", "Jul", "Ago", "Set", "Out", "Nov", "Dez",™™"Janeiro", "Fevereiro", "Marÿýo", "Abril", "Maio", "Junho", "Julho", "Agosto", "Setembro", "Outubro", "Novembro", "Dezembro"™•™™ÍÖ Ö Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™™Í3¢ gVæ7F–öâ (j) {return j < 11 || j > 13 ? ['ÿý', 'ÿý', 'ÿý', 'ÿý'][Math.min((j - 1) % 10, 3)] : 'ÿý'™,™Ð&6f÷&Ö C¢ u'ÖÖÖB™™ÍæWvf÷&Ö C¢ vBöÒÖ'™™Í '6U&R ¢ ö²2UÅÅÂó¥ó²âÅÇEÇ2ÖÒÖ™™Í masks : {Ð •4óƒc Æöæs¢%'ÖÒÖB ƒ¦"§2"Í •4óƒc 6†÷'C¢%'ÖÒÐ d",Ð 6†÷'DF FS¢ &âö¢ö'"Í ÆöætF FS¢ &ÂÂ b BÂ '"Í ' gVÆÄF FUF–ÖS¢ &ÂÂ b BÂ ' s¦"§2 "Í ÖöçF„F "¢ $b B"Í ' 6†÷'EF–ÖS¢ &s¦' "Í ÆöæuF–ÖS¢ &s¦"§2 "Í SortableDateTime: "Y-m-d\\TH:i:s",Ð Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %'ÖÒÐ d H:i:sO",Ð –V $ÖöçFƒ¢ $bÂ '™ ÒÍ &Vf÷&Ö D gFW$VF—B ¢ falseÐ}™Ð,™ÐaseLinkUrl: '',™ÐhowAction: '',Ð F &vWC¢ rrÍ 6†V6¶&÷, ¢ {disabled:true},Ð

™idName : 'id'¶);Þ)(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-ro.js

;(function($){Ð**Ð* jqGrid Romanian TranslationÐ* Alexandru Emil Lupu contact@alecslupu.roÐ* http://www.alecslupu.ro/ Ð* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð $.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "Vizualizare {0} - {1} din {2}",™Ð emptyrecords: "Nu exist 2 æç&Vv—7G! ri de vizualizat",™Ðadtext: "Înc 7&6 &Rââã™"Í pgtext : "Pagina {0} din {1}"ÐÒÍ6V &6, ¢ ™caption: "Caut 2ãã™Í"Ind: "Caut 2™"Í Reset: "Resetare",™Ðodata: [{ oper:'eq', text:"egal"},{ oper:'ne', text:"diferit"},{ oper:'lt', text:"mai mic"},{ oper:'le', text:"mai mic sau egal"},{ oper:'gt', text:"mai mare"},{ oper:'ge', text:"mai mare sau egal"}, { oper:'bw', text:"începe cu"},{ oper:'bn', text:"nu începe cu"},{ oper:'in', text:"se g 76R te în"},{ oper:'ni', text:"nu se g 76R te în"},{ oper:'ew', text:"se termin 2 7R'ÒÇ² ÷ W#¢vVârÂ FW‡C¢&çR 6R FW&Ö–á cu"},{ oper:'cn', text:"con!¶–æR'ÒÀ { oper:'nc', text:""},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ 'Fö FR" ÒÉ{ op: "OR", text: "oricare" }•ÒÍ™ÐoperandTitle : "Click to select search operation.",™ÐesetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™ÐaddCaption: "Ad 7Vv &R æç&Vv—7G& &™"ÍÐeditCaption: "Modificare înregistrare",™ÐbSubmit: "Salveaz 2™"ÍÐCancel: "Anulare",™ÐClose: "Închide",™ÐsaveData: "Informa!¶––ÆR R f÷7B ÖöF–f–6 FR 6 Çf i modific 7&™ÆSò"Í bYes : "Da",™ÐbNo : "Nu",™ÐExit : "Anulare",™Ðsg: {™Ð&W V—&VC¢$>&× VÂ W7FR obligatoriu",™Ð–çVÖ&W#¢%a rug 6Ò –çG&öGV6R i un num 7"™ÐFÖÆãB"™ÍÇVS¢'f Æö &V trebuie sa fie mai mare sau egal 2 7R™ÍÖ …f ÇVS¢'f Æö &V G&V'V–R 6 f–R Ö ’ mic 2 6 R Vv Á cu™"™ÐÖ –Ã¢ &çR W7FR ò G&W1 de e-mail valid™–2™ÍÇVvW#¢ %a rug 6Ò introduce!¶’ Vâ çVÑ r valid™"™ÐFÐFS¢ %a rug 6Ò 1 introduce!¶’ ò F A™—W&Ãd$2™Í este un URL valid. Prefixul este necesar('http://' or 'https://')",™Ð• nodefined : " is not defined!",™Ð–æ÷f ÇVR ¢ " &WGW&â f ÇVR —2 &W V—&VB ™Í customarray : "Custom function should return array!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ function should be present in case of custom checking!"™Ð}™ÐÍf–Wr ¢ ™caption: "Vizualizare înregistrare",™ÐbClose: "Închidere"™ÐÍFVÂ ¢ ™caption: "!‡FVvW&™Ís g: "!‡FW&vR i înregistrarea (înregistr 7&–ÆR’ 6VÆV7F ™ÐSubmit: "!‡FW&vR™"ÍÐCancel: "Anulare"™ÐÒÍæ b ¢ ™ÐedittextÐ: "",™Ðdittitle: "Modific 2 .&æGVÂ 6VÆV7F B™"Í addtext:"",™Ðaddtitle: "Adaug 2 .&æB æ÷R™"ÍÐeltext: "",™Ðeltitle: "!‡FW&vR .&æGVÂ selectat",™Ðsearchtext: "",™Ðearchtitle: "C 7WF &R æç&Vv—7G! ™"ÍÐeshtext: "",™Ð refreshtitle: "Reîncarcare Grid",™Ðalertcap: "Avertisment",™Ðlerttext: "V 2 'Vq m s 2 selecta!¶’ Vâ .&æB™"ÍÐiewtext: "",™Ðiewtitle: "Vizualizeaz 2 .&æGVÂ 6VÆV7F—™"ÍÐ col : {™Ðcaption: "Arat 2ô 67VæFR 6öÆö æVÆR™"ÍÐubmit: "Salveaz 2™"ÍÐCancel: "Anulare"™Ð —ÒÍW'&÷'2 ¢ ™Ðerrcap : "Eroare",™Ðourl : "Niciun url nu este setat",™Ðorecords: "Nu sunt înregistr 7&’ FR &ö6W6 B™"ÍÐodel : "Lungimea colNames <> colModel!"™ÐÍ formatter : {™Ðinteger : {thousandsSeparator: " ", defaultValue: '0'},™Ðumber : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0,00'},™Ðcurrency : {decimalSeparator:",", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0,00'},™Ðdate : {™Ð dayNames: [™Ð™"Dum", "Lun", "Mar", "Mie", "Joi", "Vin", "Sâm™™"™ÐDuminic 2"Â "Luni", "Mar!¶’"Â $Ö–W&7W&’"Â $¦ö’"Â %f–æW&’"Â %>&Ö!™ÐÖöçF„æ ÖW3¢™½"Ian", "Feb", "Mar", "Apr", "Mai", "Iun", "Iul", "Aug", "Sep", "Oct", "Noi", "Dec",™Ð ™™"Ianuarie", "Februarie", "Martie", "Aprilie", "Mai", "Iunie", "Iulie", "August", "Septembrie", "Octombrie", "Noiembrie", "Decembrie"™Ð•ÒÍ Õ Ò ¢ ["am","pm","AM","PM"],™Ð’™’ †W&R —2 &ö&ÆVÒ –â &öÖ æ– ã¢™"™Ù/"m7B Ò &–×VÂ ò primaÐ’ &æB Ò Â Fö–ÆV ò F÷™Ð’ 7&B Ò Â G&V–ÆV ò G&V–™’ GF, Ò Â G'VÆV ò A patraÐ’ WF, Ò Â 6–æ6–ÆV ò 6–æ6V™’ gF, Ò Â aselea / A !™’6™WF, Ò Â !– FVÆV ò aptéaÐâãã™’ ¢™ý3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â ÇÂ ¢ â 2 ò ²w7BrÂ 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™Ð–7&6f÷&Ö C¢ u’ÖÒÖBr™Í newformat: 'd/m/Y',™Ð— '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒ™ÍÖ 6·2 ¢™½ISO8601Long:"Y-m-d H:i:s",™ÐISO8601Short:"Y-m-d™™",™ÐhortDate: "n/j/Y™™",™ÐongDate: "l, F d, Y™™",™Ð FullDateTime: "l, F d, Y g:i:s A",™ÐMonthDay: "F d™™",™ÐhortTime: "g:i A™™",™Ð LongTime: "g:i:s A",™ÐSortableDateTime: "Y-m-d\\TH:i:s™™",™Ð UniversalSortableDateTime: "Y-m-d H:i:sO",™ÐYearMonth: "F, Y™"™Ð—™"ÍÐ reformatAfterEdit : false™Ð},™ÐaseLinkUrl: '',™ÐhowAction: '',™Ðarget: '',™Ð checkbox : {disabled:true},Ð

™idName : 'id'¶ÐÐ);Ð)(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-ru.js

```
;(function($){Ð**Ð* jqGrid Russian Translation v1.0 02.07.2009 (based on
translation by Alexey Kanaev v1.1 21.01.2009, http://softcore.com.ru)Ð*
Sergey Dyagovchenko™Ð* http://d.sumy.ua™Ð* Dual licensed under the MIT and GPL
licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://
www.gnu.org/licenses/gpl.html™Ð*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð
defaults : {™Ðrecordtext: "Aô@CäACÄ>D$@ {0}™emptyrecord: "™,Ð5D™loadtext: "™,Ð7C¤Ð.<Cä
pgtext : "B BD â ³ Ò ™ÐÍ6Ý Ò6, ¢ ™caption: "Aô>C™ÐÐ™Ð;™Ð™Ð™Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-sk.js

;(function($){Ð**Ð* jqGrid Slovak TranslationÐ* Milan CibulkaÐ* http://
trirand.com/blog/ Ð* Dual licensed under the MIT and GPL licenses:Ð* http://
www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/
gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext:
"Zobrazených {0} - {1} z {2} záznamov",Ð V× G—&V6÷&G3¢ $æV&öÆ’ î ¦FVî’
žiadne záznamy",Ðloadtext: "Na Þ×N Òâ‚â™Ðgtext : "Strana {0} z {1}"ÐÍ6V &6, ¢ ™
caption: "Vyh æ N f Òâ‚â™Ðind: "H æ F™Ðreset:"Reset",Ð öF F ¢ ·² ÷ W#¢vW rÂ
text:"rovná sa"},{ oper:'ne', text:"nerovná sa"},{ oper:'lt', text:"menšie"},
{ oper:'le', text:"menšie alebo rovnajúce sa"},{ oper:'gt', text:"vä Ù¦–R'ÒÀ
{ oper:'ge', text:"vä Ù¦–R ÆV&ò &÷fæ ¯¦6R 6 'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢'¦ ína s"},
{ oper:'bn', text:"neza ÞÖæ 2'ÒÇ² ÷ W#¢v–ârÂ FW‡C¢&¦R b'ÒÇ² ÷ W#¢væ’rÂ
text:"nie je v"},{ oper:'ew', text:"kon ÞÒ 2'ÒÇ² ÷ W#¢vVârÂ FW‡C¢&æV¶öá í s"},
{ oper:'cn', text:"obahuje"},{ oper:'nc', text:"neobsahuje"},{ oper:'nu',
text:'is null'},{ oper:'nn', text:'is not null'}],Ð w&÷W ÷ 3¢ ¹{ op: "AND",
text: "všetkých" },—² ÷ ¢ $ö""Â FW‡C¢ &æ–V·F÷.–†ò ¢" Ù]™ÐperandTitle : "Click
to select search operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ™
addCaption: "Prida R ® ¦æ Ò™ÍeditCaption: "Editácia záznamov",™ÐSubmit: "Uloži R™"Í
bCancel: "Storno",™ÐbClose: "Zavrie R™ÍaveData: "Údaje boli zmenené! Uloži R
zmeny?",™ÐbYes : "Ano",™ÐNo : "Nie",™ÐExit : "Zruši R™Íg: "™Ð required:"Pole je
požadované",™ number:"Prosím, vložte valídne Þ×6Æ™"Í minValue:"hodnota
musí bý R nA šia ako alebo rovná™",Ð maxValue:"hodnota musí bý R ÖVé¦– ¶ò
alebo rovná ",™ email: "nie je valídny e-mail",Ð integer: "Prosím, vložte
celé Þ×6Æò™ÍF FS¢ % &÷>ÖÒÂ fÆùçFR f ÎÖFç’ N GVÒ™ÍW&Ã¢ &æ–R ¦R Æ Fæ÷R U$Ââ
Požadovaný prefix ('http://' alebo 'https://')",™–æöFVf–æVB ¢ " æ–R ¦R
definovaný!",™–æ÷f ÇVR ¢ " ¦R g™æ F÷f î î g& F÷n †öFæ÷F ™Í7W7FöÖ '& ’ ¢
"Custom function mala vráti R öÆR ™Í7W7FöÖf6†V6² ¢ $7W7FöÒ gVæ7F–öâ '’ Ö Æ ''e
prítomná v prípade custom checking!"™ÐÍf–Wr ¢ ½ 6 F–öã¢ %¦ö'& ¦’e záznam",Ð
’ $6Æ÷6S¢ %¦ g&–QeÖÐFVÂ ¢ ™caption: "Zmaza R™Íg: "Zmaza R g–'& ïÒŽ’’
záznam(y)?",™ÐbSubmit: "Zmaza R™ÍCancel: "Storno"ÐÍæ b ¢ ™edittext: " "™Ð
edittitle: "Editova R g–'& ïÒ &– Fö²™Íddtext:" "™Ðaddtitle: "Prida R æ÷oÒ &– FV™"Í
deltext: " ",™Ðdeltitle: "Zmaza R g–'& ïÒ ® ¦æ Ò™"Íearchtext: " "™Ðsearchtitle:
"Nájs R ® ¦æ ×’™Íefreshtext: ""™Ðrefreshtitle: "Obnovi R F 'Q>™"Íalertcap:
"Varovanie",™Ðalerttext: "Prosím, vyberte riadok",™Ðviewtext: ""™Ðviewtitle:
"Zobrazi R g–'& ïÒ &– Fö²ÒÍ6öÂ ¢ ™caption: "Zobrazit/Skrý R 7A:pÒ™"Íubmit:
"Uloži R™ÍCancel: "Storno"ÐÍW'&÷'2 ¢ ™errcap : "Chyba",™Ðourl : "Nie je
nastavená url",™Ðnorecords: "Žiadne záznamy k spracovaniu",™Ðmodel : "D ©æ¶
colNames <> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: " ",
defaultValue: '0'},™Ðnumber : {decimalSeparator:".", thousandsSeparator: " ",
decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".",
thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0.00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™™½"Ne", "Po", "Ut", "St", "Št",
"Pi", "So",™™"Nedela", "Pondelok", "Utorok", "Streda", "Štvrtok", "Piatek",
"Sobota"™•™ÍÖöçF„æ ÖW3¢™™½"Jan", "Feb", "Mar", "Apr", "Máj", "Jún", "Júl",
"Aug", "Sep", "Okt", "Nov", "Dec",™™"Január", "Február", "Marec", "Apríl",
"Máj", "Jún", "Júl", "August", "September", "Október", "November", "December"Ð
™•™Í Õ Ò ¢ ²&Fò"Â&öB"Â$DÒ"Â$ôB%™Í3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â ÇÂ ¢ â 2 ò
['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™—7&6f÷&Ö C¢ u’ÖÒÐ
d',™–æWvf÷&Ö C¢ vBöÒõ’™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇÇ2ÕÒ™ÍÖ 6·2 ¢™½
ISO8601Long:"Y-m-d H:i:s",™ ISO8601Short:"Y-m-d",™ ShortDate: "n/
j/Y",™ LongDate: "l, F d, Y",™ FullDateTime: "l, F d, Y g:i:s A",Ð
™ MonthDay: "F d",™ ShortTime: "g:i A",™ LongTime: "g:i:s
A",™ SortableDateTime: "Y-m-d\\TH:i:s",™Ð
UniversalSortableDateTime: "Y-m-d H:i:sO",™ YearMonth: "F, Y™Ð },™Ð
reformatAfterEdit : false™Ð},™ÐbaseLinkUrl: ''™ÐshowAction: '',Ð F &vWC¢ rrÍ
checkbox : {disabled:true},™ÐidName : 'id—™});™Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-sr-latin.js

;(function($){Ð**Ð* jqGrid Serbian latin TranslationÐ* Bild Studio info@bild-studio.netÐ* http://www.bild-studio.comÐ* Dual licensed under the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð defaults : {™Ðrecordtext: "Pregled {0} - {1} od {2}",™Ðemptyrecords: "Ne postoji nijedan zapis",™Ðloadtext: "U Ö–F f æ¦XR™Ðpgtext : "Strana {0} od {1}"–ÒÍ6V &6, ¢ ™½ caption: "Traženje...",™ÐFind: "Traži",™Ðreset: "Resetuj",™Ðdata: [{ oper:'eq', text:"jednako"},{ oper:'ne', text:"nije jednako"},{ oper:'lt', text:"manje"}, { oper:'le', text:"manje ili jednako"},{ oper:'gt', text:"ve vR'ÒÇ² ÷ W#¢vvRrÂ text:"ve vR –Æ' ¦VFæ ¶ò'ÒÇ² ÷ W#¢v'rrÂ FW‡C¢' ñ inje sa"},{ oper:'bn', text:"ne po Ö–æ¦R 6 'ÒÇ² ÷ W#¢v–ârÂ FW‡C¢&¦R R'ÒÇ² ÷ W#¢væ'rÂ FW‡C¢&æ–¦R R'ÒÀ { oper:'ew', text:"završava sa"},{ oper:'en', text:"ne završava sa"}, { oper:'cn', text:"sadrži"},{ oper:'nc', text:"ne sadrži"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],™ÐgroupOps: [—² ÷ ¢ $ äB"Â text: "sva" },—² ÷ ¢ $õ""Â FW‡C¢ &&–Æò ¶ö¦R" Ù]™ÐperandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search Value"–ÒÍVF—B ¢ ™½ addCaption: "Dodaj zapis",™ÐeditCaption: "Izmeni zapis",™ÐSubmit: "Pošalji",™Ð bCancel: "Odustani",™ÐbClose: "Zatvori",™ÐaveData: "Podatak je izmenjen! Sa ×Wf ¢ izmene?",™ÐbYes : "Da",™ÐNo : "Ne",™ÐExit : "Odustani",™Ðmsg: {™Ð&W V—&VC¢ % öÆ¦R ¦R obavezno",™Ð–çVÖ&W#¢ %VæW6—FR —7 & f â '&ö¢™ÍÖ–åf ÇVS¢ 'g&VFæ÷7B Ö÷& &—F' fQ a od ili jednaka sa ",™Ð–Ö …f ÇVS¢ 'g&VFæ÷7B Ö÷& &—F' Ö æ¦ –Æ' ¦VFæ ¶ 6 ™Í email: "nije ispravna email adresa, nije valjda da ne umeš ukucati mail!?",™Ð• integer: "Unesi celobrojnu vrednost ",™Ð–F FS¢ %VæW6—FR —7 & f â F GVÒ™ÍW&Ã¢ "nije ispravan URL. Potreban je prefiks ('http://' or 'https://')",™Ð• nodefined : " nije definisan!",™Ð–æ÷f ÇVR ¢ " ¦ ‡FWf æ ¦R ÷g& Fæ g&VFæ÷7B ™Í customarray : "Prilago Væ gVæ¶6–¦ G&V& F g& F' æ—¢ ™Í7W7FöÖf6†V6² ¢ "Prilago Væ gVæ¶6–¦ G&V& F 'VFR &—7WF æ R 6ÇQ aju prilago VæR &÷fW™ÐÍ- view : {™Ðcaption: "Pogledaj zapis",™ÐClose: "Zatvori"–ÒÍFVÂ ¢ ™½caption: "Izbrisi",™Ðmsg: "Izbrisi izabran(e) zapise(e)?",™ÐSubmit: "Izbriši",™ÐCancel: "Odbaci"ÐÒÍæ b ¢ ™½edittext: "",™Ðdittitle: "Izmeni izabrani red",™Ðaddtext:"",™Ð addtitle: "Dodaj novi red",™Ðdeltext: "",™Ðeltitle: "Izbriši izabran red",™Ð searchtext: "",™Ðsearchtitle: "Na ' ¦ —6R™Íefreshtext: "",™Ðefreshtitle: "Ponovo u Ö—F ¢ öF F¶R™Íalertcap: "Upozorenje",™Ðalerttext: "Izaberite red",™Ð viewtext: "",™Ðviewtitle: "Pogledaj izabrani red"–ÒÍ6öÂ ¢ ™½caption: "Izaberi kolone",™ÐbSubmit: "OK",™ÐCancel: "Odbaci"–ÒÍW'&÷'2 ¢ ™½errcap : "Greška",™Ðourl : "Nije postavljen URL",™Ðnorecords: "Nema zapisa za obradu",™Ðodel : "Dužina modela colNames <> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™½integer : {thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency : {decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"", defaultValue: '0.00'},™Ðdate : {™ÐF ”æ ÖW3¢ ™½"Ned", "Pon", "Uto", "Sre", " ÆWB"Â "Pet", "Sub",™Ð™"Nedelja", "Ponedeljak", "Utorak", "Srijeda", " ÆWGg'F ²"Â "Petak", "Subota"™Ð•ÒÍÖöçF„æ ÖW3¢™½"Jan", "Feb", "Mar", "Apr", "Maj", "Jun", "Jul", "Avg", "Sep", "Okt", "Nov", "Dec",™Ð™"Januar", "Februar", "Mart", "April", "Maj", "Jun", "Jul", "Avgust", "Septembar", "Oktobar", "Novembar", "Decembar"™Ð•ÒÍ Õ Ò ¢ ²& Ò"Â' Ò"Â$ Ò"Â% Ò%™Í3¢ gVæ7F–ôâ †¢' ·&WGW&â ¢ Â ÇÂ ¢ > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™Ð—7&6f÷&Ö C¢ 'Y-m-d',™Ð–æWvf÷&Ö C¢ vBöÒõ'™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒ™ÍÖ 6·2 ¢™½ ISO8601Long:"Y-m-d H:i:s",™ÐISO8601Short:"Y-m-d™™Ð,ShortDate: "n/j/Y™™Ð,LongDate: "l, F d, Y",™ÐFullDateTime: "l, F d, Y g:i:s A™™Ð,MonthDay: "F d™™Ð,ShortTime: "g:i A",™ÐLongTime: "g:i:s A™™Ð,SortableDateTime: "Y-m-d\\TH:i:s™™Ð UniversalSortableDateTime: "Y-m-d H:i:sO",™ÐYearMonth: "F, Y"™ÐÍ reformatAfterEdit : false™Ð},™ÐaseLinkUrl: ''™Ð,ShowAction: ''™Ð,arget: ''™Ð checkbox : {disabled:true},™ÐidName : 'id–™});™Ð})(jQuery);Ð

public\assets\js\plugins\jqGrid\i18n\grid.locale-sr.js

```
þÿ;(function($){ÐÐ* jqGrid Serbian TranslationÐ* A ;CT:D 0CÔ4C @ AÄ8C´>C$0Db„ ÆV·6 æF " Ö–
aleksandar.milovac@gmail.comÐ* http://trirand.com/blog/Ð* Dual licensed under
the MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ
 * http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™½recordtext: "Aô@CT3C´5CB ³ Ò ÙempÙ>CB ³ÙÒ"Í"AÔ5 Cô>D BCäXC
CtÔ0Ò0Ò0Ò
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-sv.js

```
;(function($){Ð**Ð* jqGrid Swedish TranslationÐ* Harald Normann
harald.normann@wts.se, harald.normann@gmail.comÐ* http://
www.worldteamsoftware.com Ð* Dual licensed under the MIT and GPL licenses:Ð*
http://www.opensource.org/licenses/mit-license.phpÐ* http://www.gnu.org/
licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™
recordtext: "Visar {0} - {1} av {2}",Ðemptyrecords: "Det finns inga poster att
visa",Ðloadtext: "Laddar...",Ðpgtext : "Sida {0} av {1}"ÐÍ6V &6, ¢ ™caption:
"Sök Poster - Ange sökvillkor",ÐFind: "Sök",Ðreset: "Nollställ Villkor",Ðdata:
[{ oper:'eq', text:"lika"},{ oper:'ne', text:"ej lika"},{ oper:'lt',
text:"mindre"},{ oper:'le', text:"mindre eller lika"},{ oper:'gt',
text:"större"},{ oper:'ge', text:"större eller lika"},{ oper:'bw',
text:"börjar med"},{ oper:'bn', text:"börjar inte med"},{ oper:'in',
text:"tillhör"},{ oper:'ni', text:"tillhör inte"},{ oper:'ew', text:"slutar
med"},{ oper:'en', text:"slutar inte med"},{ oper:'cn', text:"innehåller"},
{ oper:'nc', text:"innehåller inte"},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],ÐgroupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ & ÆÆ " ÒÉ
{ op: "OR",  text: "eller" }•ÒÍoperandTitle : "Click to select search
operation.",ÐresetTitle : "Reset Search Value"ÐÍVF—B ¢ ™addCaption: "Ny Post",Ð
editCaption: "Redigera Post",ÐbSubmit: "Spara",ÐCancel: "Avbryt",ÐClose:
"Stäng",ÐsaveData: "Data har ändrats! Spara förändringar?",ÐYes : "Ja",ÐNo :
"Nej",ÐbExit : "Avbryt",Ðmsg: {Ð       &W V—&VC¢$nFÇFWB G" ö&Æ–v F÷&—6·B"Í
’        çVÖ&W#¢%nFÆ¢ ¶÷'&V·B çVÖÖW""Í        Ö–åf ÇVS¢'nG&FWB ÞW7FR f &
större än eller lika med",Ð        Ö …f ÇVS¢'nG&FWB ÞW7FR f &  Ö–æG&R Fâ VÆÆW"
lika med",Ð        VÖ –Ã¢ .G" –çFR ¶÷'&V·B R× ÷7B  G&W72"Í        –çFVvW#¢
"Var god ange korrekt heltal",Ð        F FS¢ %f " vöB  ævR ¶÷'&V·B F GVÒ"Í
’        W&Ã¢ .G" –çFR Vâ ¶÷'&V·B U$Ââ  &Vf—, ÞW7FR  ævW2 ,v‡GG ¢òòr ÷"
'https://')",Ð        æöFVf–æVB ¢ " G" –çFR FVf–æ–W& B "Í        æ÷f ÇVR ¢ "
returvärde måste anges!",Ð        7W7FöÖ '& ’ ¢ $7W7FöÒ gVæ·F–öâ ÞW7FR
returnera en vektor!",Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ gVæ·F–öâ ÞW7FR f–ææ 2 öÒ 7W7FöÒ
kontroll sker!"ÐÍf–Wr ¢ ™caption: "Visa Post",ÐClose: "Stäng"ÐÍFVÂ ¢ ™
caption: "Radera",Ðmsg: "Radera markerad(e) post(er)?",ÐSubmit: "Radera",Ð
bCancel: "Avbryt"ÐÒÍæ b ¢ ™edittext: "",Ðedittitle: "Redigera markerad rad",Ð
addtext:"",Ðaddtitle: "Skapa ny post",Ðdeltext: "",Ðdeltitle: "Radera markerad
rad",Ðsearchtext: "",Ðsearchtitle: "Sök poster",Ðrefreshtext: "",Ðrefreshtitle:
"Uppdatera data",Ðalertcap: "Varning",Ðalerttext: "Ingen rad är markerad",Ð
viewtext: "",Ðviewtitle: "Visa markerad rad"ÐÍ6öÂ ¢ ™caption: "Välj Kolumner",Ð
bSubmit: "OK",ÐbCancel: "Avbryt"ÐÍW'&÷'2 ¢ ™errcap : "Fel",Ðourl : "URL
saknas",Ðnorecords: "Det finns inga poster att bearbeta",Ðmodel : "Antal
colNames <> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: " ",
defaultValue: '0'},Ðnumber : {decimalSeparator:",", thousandsSeparator: " ",
decimalPlaces: 2, defaultValue: '0,00'},Ðcurrency : {decimalSeparator:",",
thousandsSeparator: " ", decimalPlaces: 2, prefix: "", suffix:"Kr",
defaultValue: '0,00'},Ðdate : {ÐF ”æ ÖW3¢  ™½"Sön", "Mån", "Tis", "Ons", "Tor",
"Fre", "Lör",Ð™"Söndag", "Måndag", "Tisdag", "Onsdag", "Torsdag", "Fredag",
"Lördag"Ð•ÒÍÖöçF„æ ÖW3¢™½"Jan", "Feb", "Mar", "Apr", "Maj", "Jun", "Jul",
"Aug", "Sep", "Okt", "Nov", "Dec",Ð™"Januari", "Februari", "Mars", "April",
"Maj", "Juni", "Juli", "Augusti", "September", "Oktober", "November",
"December"Ð•ÒÍ Õ Ò ¢ ²&fÒ"Â&VÒ"Â$dÒ"Â$TÒ%ÒÍ3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â    ÇÂ ¢
> 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},Ð—7&6f÷&Ö C¢
'Y-m-d',Ð–æWvf÷&Ö C¢ u’ÖÖÖBÍ  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÖÖÍÖ 6·2 ¢ ½
’            •4óƒc  Æöæs¢%’ÖÖÖB ƒ¦“§2"Í            •4óƒc  6†÷'C¢%’ÖÖÖB"Í
’            6†÷'DF FS¢  &âö¢õ’"Í            ÆöætF FS¢ &ÂÂ b BÂ ’"Í
FullDateTime: "l, F d, Y g:i:s A",Ð            ÖöçF„F “¢ $b B"Í
ShortTime: "g:i A",Ð            ÆöæuF–ÖS¢ &s¦“§2  "Í
SortableDateTime: "Y-m-d\\TH:i:s",Ð            Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %’ÖÖÐ
d H:i:sO",Ð            –V $ÖöçFƒ¢ $bÂ ’™—ÒÍ&Vf÷&Ö D gFW$VF—B ¢ f Çõ],Ð
baseLinkUrl: '',ÐshowAction: '',Ðarget: '',Ðheckbox : {disabled:true},ÐidName :
'id'ÐÝ});Ð})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-th.js

```
;(function($){Ð**Ð* jqGrid Thai TranslationÐ* Kittituch Manakul
m.kittituch@Gmail.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the
MIT and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ½recordtext: "ä *áN  {0} - {1}™ãÞ¼ÐÍ¿ÐÍ¿ÐÍ¿
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-tr.js

```
;(function($){Ð**Ð* jqGrid Turkish TranslationÐ* Erhan Gündo ö â
(erhan@trposta.net)Ð* http://blog.zakkum.comÐ* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ½recordtext: "{0}-{1} listeleniyor. Toplam:{2}",Ð
’    V× G—&V6÷&G3¢ $¶ ‘1t bulunamad™lÖÍdtext: "Yükleniyor...",™Ðgtext : "{0}/
{1}. Sayfa"ÐÒÍ6V &6, ¢ ½    6  F–öã¢ $ & Ö ââ"Í    f–æC¢ $'VÂ"Í    &W6WC¢
"Temizle",’    ’    öF F ¢ ·² ÷ W#¢vW rÂ FW‡C¢&Q_it"},{ oper:'ne', text:"e ö—B
de ö–Â'ÒÇ² ÷ W#¢vÇBrÂ FW‡C¢&F †   ¢'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢&F †   ¢ fW–  Q_it"},
{ oper:'gt', text:"daha fazla"},{ oper:'ge', text:"daha fazla veya e ö—B'ÒÀ
{ oper:'bw', text:"ile ba öÆ – â'ÒÇ² ÷ W#¢v&ârÂ FW‡C¢&–ÆR & _lamayan"},
{ oper:'in', text:"içinde"},{ oper:'ni', text:"içinde de ö–Â'ÒÇ² ÷ W#¢vWrrÂ
text:"ile biten"},{ oper:'en', text:"ile bitmeyen"},{ oper:'cn',
text:"içeren"},{ oper:'nc', text:"içermeyen"},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],Ð    w&÷W ÷ 3¢ ¹{ op: "VE", text: "tüm" },•
{ op: "VEYA",  text: "herhangi" }],™ÐoperandTitle : "Click to select search
operation.",™ÐresetTitle : "Reset Search Value"™ÐÍVF—B ¢ ½     FD6  F–öã¢ $¶ ‘1t
Ekle",Ð    VF—D6  F–öã¢ $¶ ‘1t Düzenle",Ð  %7V&Ö—C¢ $•fæFW""Í    $6 æ6VÃ¢
"   F Â™™ÐClose: "Kapat",™ÐaveData: "Veriler de ö’_ti! Kay  B VF–Ç6–â™™ÐÝÒÍ:
"Evet",™ÐbNo : "Hay  ™™ÐÍxit : "   F Â"Í  ×6s¢ ½        &W V—&VC¢$ Æ â vW&V¶Æ’"Í
’        çVÖ&W#¢$ÏÇFfVâ &—" çVÖ &  v—&–æ—¢"Í        Ö–åf ÇVS¢&v—&–ÆVâ FQ er
daha büyük ya da buna e ö—B öÆÖ Á1d’ ""Í    Ö …f ÇVS¢&v—&–ÆVâ FQ er daha küçük
ya da buna e ö—B öÆÖ Á1d’ ""Í    VÖ –Ã¢ &v^vW&Æ’ &—" R× ÷7F   G&W6’ FQ ildir",Ð
’        –çFVvW#¢ $ÏÇFfVâ &—" F ×6 ‘1 giriniz™™ÐW&Ã¢ $v^vW&Æ’ &—" U$Â FQ il.
('http://' or 'https://') ön eki gerekli.",™Ð–æöFVf–æVB ¢ " —2 æ÷B FVf–æVB ™™Í
novalue : " return value is required!",™Ð–7W7FöÖ '& ’ ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB
return array!",™Ð–7W7FöÖf6†V6² ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &R  &W6VçB –â 6 6R öb
custom checking!"™]ÐÍf–Wr ¢ ½    6  F–öã¢ $¶ ‘1t Görüntüle",Ð  $6Æ÷6S¢ $¶   B-
—ÒÍFVÂ ¢ ½    6  F–öã¢ %6–Â"Í    ×6s¢ %6^v–ÆVâ ¶ ‘1tlar silinsin mi?",Ð
bSubmit: "Sil",Ð    $6 æ6VÃ¢ !0ptaÒÍæ b ¢ ™™edittext: " ",Ð   VF—GF—FÆS¢
"Seçili sat  !1 düzenlead™™Ðtext:" ",Ð    FGF—FÆS¢ %–Væ’ 6 A1r ekle",Ð  FVÇFW‡C¢
" ",Ð    FVÇF—FÆS¢ %6^v–Æ’ 6 A1r   6’Â"Í 6V &6‡FW‡C¢ " "Í    6V &6‡F—FÆS¢
"Kay  FÆ !1 bul",Ð &Vg&W6‡FW‡C¢ ""Í    &Vg&W6‡F—FÆS¢ %F &Æ÷—R –Væ–ÆR"Í
alertcap: "Uyar  "Í    ÆW'GFW‡C¢ $ÏÇFfVâ &—" 6 A1r seçiniz™™ÐÍewtext: "",™Ð
viewtitle: "Seçilen sat  !1 görüntüÒÍÐöÂ ¢ ½    6  F–öã¢ %?ÇGVæÆ !1 göster/
gizle",Ð    %7V&Ö—C¢ $•fæFW""Í    $6 æ6VÃ¢ !0ptaÒÍW'&÷'2 ¢ ™™errcap : "Hata",™Ð
nourl : "Bir url yap  Æ æA1r  ÆÖnÑteòÍÍds: "  _lem yap  Æ 6 ² &—" ¶ ‘1t yok",Ð
model : "colNames uzunlu ÷R Ãâ 6öÄÖöFVÂ—ÒÍf÷&Ö GFW" ¢ ™™integer :
{thousandsSeparator: " ", defaultValue: '0'},™Ðnumber : {decimalSeparator:".",
thousandsSeparator: " ", decimalPlaces: 2, defaultValue: '0.00'},™Ðcurrency :
{decimalSeparator:".", thousandsSeparator: " ", decimalPlaces: 2, prefix: "",
suffix:"", defaultValue: '0.00'},™Ðdate : {™ÐF ”æ ÖW3¢  ™™½"Paz", "Pts", "Sal",
"Çar", "Per", "Cum", "Cts",™™"Pazar", "Pazartesi", "Sal  "Â ,v !_amba", "Per öVÖ&R"Â
"Cuma", "Cumartesi™™•ÒÍÖöçF„æ ÖW3¢™™½"Oca", " çV""Â $Ö ""Â $æ—2"Â $Ö ’"Â $† ¢"Â
"Tem", "A ÷R"Â $W–Â"Â $V¶’"Â $¶ 2"Â $ & ™™™"Ocak", " çV& B"Â $Ö 'B"Â $æ—6 â"Â
"May  2"Â $† ¦—& â"Â %FVÖ×W¢"Â $  ustos", "Eylül", "Ekim", "Kas  Ò"Â $ &™™•™™Ðik™Ð
AmPm : ["am","pm","AM","PM"],™™Ð•3¢ gVæ7F–öâ †¢’ ·&WGW&â ¢ Â    ÇÂ ¢ â  2 ò
['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10, 3)] : 'th'},™Ð—7&6f÷&Ö C¢ u’ÖÒÐ
d',™Ð–æWvf÷&Ö C¢ vBöÒõ’™™Í  '6U&R ¢ õ²2UÅÅÂó¥ó²âÅÇEÇ2ÕÒÒ™™ÍÖ 6·2 ¢’½
ISO8601Long:"Y-m-d H:i:s",™Ð            •4óƒc  6†÷'C¢%’ÖÒÖB"Í
ShortDate: "n/j/Y",™Ð            ÆöætF FS¢ &ÂÂ b BÂ ’"Í
FullDateTime: "l, F d, Y g:i:s A",™Ð            ÖöçF„F “¢ $b B"Í
ShortTime: "g:i A",™Ð            ÆöæuF–ÖS¢ &s¦“§2  "Í
SortableDateTime: "Y-m-d\\TH:i:s",™Ð            Væ—fW'6 Å6÷'F &ÆTF FUF–ÖS¢ %’ÖÒÐ
d H:i:sO",™Ð            –V $ÖöçFƒ¢ $bÂ ’™        ÒÍ        &Vf÷&Ö D gFW$VF—B ¢
falseÐ},™ÐbaseLinkUrl: '',™ÐshowAction: '',™Ð   F &vWC¢ rrÍ    6†V6¶&÷, ¢
{disabled:true},™ÐidName : 'id'™Ð});Ð})(jQuery);Ð
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-tw.js

```
;(function($){Ð**Ð* jqGrid Chinese (Taiwan) Translation for v4.2Ð* linquizeÐ*
https://github.com/linquize/jqGridÐ* Dual licensed under the MIT and GPL
licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://
www.gnu.org/licenses/gpl.htmlÐ* Ð*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð
defaults : {Ðrecordtext: "{0} - {1} Qq {2}™ÐemptyÐrecords: "l™ÐloÐdÐtexÐt,Ð "• QeÑ-...",Ð
pgtext : " {0} Qq {1}—ÒÍ¶ÐV &6, ¢ ™Ðcaption: "d \ ™ÐFinÐd "d™ÐReÐsÐet: "’ÐÐdÐata:
[{ oper:'eq', text:"{Ie¼ "},{ oper:'ne', text:"N {Ie¼ "},{ oper:'lt', text:"\ e¼ "},
{ oper:'le', text:"\ e¼{Ie¼ "},{ oper:'gt', text:"Y'e¼ "},{ oper:'ge', text:"Y'e¼{Ie¼ "},
{ oper:'bw', text:"•‹YËe¼ "},{ oper:'bn', text:"N •‹YËe¼ "},{ oper:'in', text:"W(QvN- "},
{ oper:'ni', text:"N W(QvN- "},{ oper:'ew', text:"}Pg_e¼ "},{ oper:'en', text:"N }Pg_e¼ "}
{ oper:'cn', text:"S T+ "},{ oper:'nc', text:"N S T+ "},{ oper:'nu', text:'is null'},
{ oper:'nn', text:'is not null'}],ÐgroupOps: [—² ÷ ¢ $ äB"Â FW‡C¢ &$ p’" ÒÉ{ op:
"OR",  text: "NûN "™ÐpÐÍandTitle : "Click to select search operation.",Ð
resetTitle : "Reset Search Value"ÐÒÍVF—B ¢ ™ÐaddCaption: "e™ÐÐÐÍtÐÐÐ
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-ua.js

```
;(function($){Ð**Ð* jqGrid Ukrainian Translation v1.0 02.07.2009Ð* Sergey
DyagovchenkoÐ* http://d.sumy.uaÐ* Dual licensed under the MIT and GPL
licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ* http://
www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð$.extend($.jgrid,{Ð
defaults : {Ðrecordtext: "Aô5D 5C4;Dô4 {0}'- {1}GC&V6¼Ó¢ $ CT<Ct0D8D VC" 4C´O Cô5D
"At0C$ÐÐÔBÐ6CT=CÔOBCä@,Ð{0}-ÒÉ6V³&Ô, ¢ ½   caption: "Aô>D„CC¢âÂÍ: "At=C 9D$8",Ð
Reset: "B :C„4Ó¢ÂÔ"[Ð oper:'eq', text:"D VC$=Câ'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢$=CR @Ed2CÔ>"},
{ oper:'lt', text:"CÄ5CÔHCR'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢$<CT=D„5 C 1Câ @Ed2CÔ5"},{ oper:'gt', text
{ oper:'ge', text:"C VC´LD„5 C 1Câ @Ed2CÔ5"},{ oper:'bw', text:"Cô>Dt8CÔ0EDBDÄADò 7"},{ op
{ oper:'in', text:"Ct=C ECä4C„BDÄADò 2"},{ oper:'ni', text:"CÔ5 Ct=C ECä4C„BDÄADò 2"},{ op
{ oper:'en', text:"CÔ5 Ct0C¤VCÔGD4TD$LD O CÔ0"},{ oper:'cn', text:"CÄVD BC„BDÂ'ÒÇ² ÷ W#¢væ
{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}],Ð   groupOps: [•
{ op: "AND", text: "C$ACR" ÒÉ{ op: "OR",  text: "C-ÉCW&-ÐÉFCÐR ¢]$ÐÆ-6² Fò
select search operation.",Ð&W6WEF—FÆR ¢ %&W6WB 6V &6, f ÇVR—ÒÍVF—B ¢ ½
addCaption: "AD>CD0DÐ$ÐÍCÔ0ÐÔ"Í"At<Ed=CÔ0Ô„BÔ0m7C:?CÄÄ1CÐ@ÐÔ0ÐÔ0$0Ô;Ð"A$VÐÐ<Ed=C "Í
"At0C¤Ô„BÔ0„Ô"Í"AD> CD0CÔ™ÐÔ„EsC:CÔB$ÐÔ0™ÐÔ"ÐÔ0™ÐÔ„ÐÔ0™ÐÔ„ÐÔ0™ÐÔ„
```

public\assets\js\plugins\jqGrid\i18n\grid.locale-vi.js

;(function($){Ð**Ð* jqGrid Vietnamese TranslationÐ* Lê Æ æ, Aing
dungtdc@gmail.comÐ* http://trirand.com/blog/ Ð* Dual licensed under the MIT
and GPL licenses:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*
http://www.gnu.org/licenses/gpl.htmlÐ*/Ð$.jgrid = $.jgrid || {};Ð
$.extend($.jgrid,{ÐFVf VÇG2 ¢ ™recordtext: "View {0} - {1} of {2}"™,Ð
emptyrecords: "Không có d ï li Çu™,Ðtext: " æ r áê Aîò Æ™ÐgRââ"Í "Trang
{0} trong t Õng s Ñ {1}™,Ð &6, ¢ ™caption: "Tìm ki ¿m..™,Ðtd: "Tìm"™,Ðreset: "Kh ßi
t ¡o l ¡ûdaÐa: [{ oper:'eq', text:"b ±ng"},{ oper:'ne', text:"không b ±ng"},
{ oper:'lt', text:"bé h â'ÒÇ² ÷ W#¢vÆRrÂ FW‡C¢&.' •¡n ho ·c b ±ng"},{ oper:'gt',
text:"l Ûn h â'ÒÇ² ÷ W#¢vvRrÂ FW‡C¢&Áí¶â •¡n ho ·c b ±ng"},{ oper:'bw', text:"b ¯t êwR
{ oper:'bn', text:"không b ¯t êwR aí¶''ÒÇ² ÷ W#¢v–ârÂ FW‡C¢'G&öær'ÒÇ² ÷ W#¢væ'rÂ
text:"không n ±m trong"},{ oper:'ew', text:"k ¿t thúc v Ûi"},{ oper:'en',
text:"không k ¿t thúc v Ûi"},{ oper:'cn', text:"ch éa"},{ oper:'nc', text:"không
ch éa"},{ oper:'nu', text:'is null'},{ oper:'nn', text:'is not null'}]™,Ð
groupOps: [—² ÷ ¢ %l "Â FW‡C¢ 'AêWB 1ê2" ÒÉ{ op: "HO ¶C", text: "b ¥t k ó" }•ÒÍ
operandTitle : "Click to select search operation.",™ÐresetTitle : "Reset Search
Value"ÐÒÍVF—B ¢ ™ÐaddCaption: "Thêm b £n ghi™,ÐeditCaption: "S ía b £n ghi™,ÐsubmitÐ
"G íi™,ÐcancelÐ: "H çy ™,ÐbtnÐ: " 6æ™,ÐsaveData: "D ï li Çu 2 F† ’ Õi! Có l R F† ’ Õi
không?",™ÐbYes : "Có"™,ÐNo : "Không"™,ÐExit : "H çy ™,Ð{Ð&W V—&VC¢%G!° Ýng d ï li Çu
b ¯t bu Ùc Có™,ÐÇ&W#¢$Ž7’ i Án ¡æÖ–ÂÍ ÇÝS¢&vž G!ì² •ê6’ Áí¶â •¡n ho ·™•b ±ng v Ûi ",Ð
maxValue:"giá tr Ë ph £i bé h â †ñëV2VÖë–Ãæ¢"&¶•Fær •ê6’ Î Ñí—B VÖ –Â™•úng",Ð
integer: "Hãy ‘ì â úng s Ñ nguyên™,ÐS¢Ð$Ž7’ i Án ¡æ æ~ ’ ™ÐŽWæÃ¢Í&¶•Fær •ê6’
là URL. Kh ßi êwR !ê÷B 'Qí–2 Î ,v‡GG ¢òòr †ñëv2 v™,ÐGæöBÝÖÖæVBÍ¢ " 6•°a ° ãc ì¶æ,
ngh – ™Íæ÷f ÇVR ¢ " vž G!ì² G!ê2 aì !ê÷B 'Qí™,Ð27W7FöÖ ?æ "Í¢ $Ž Ò î¡â G!ê2 aì Ñí—B
m £ng!™,ÐW7FöÖf6†V6² ¢ $7W7FöÒ gVæ7F–öâ 6†÷VÆB &R &W6VçB –â 6 6R öb 7W7FöÒ
checking!™,ÐÒÍf–Wr ¢ ™caption: "Xem b £n ghi™,ÐclosebÐ: " 6æÒÍFVÂ ¢ ™caption:
"Xóa",™Ðmsg: "Xóa b £n ghi 2 6•ÐÔÃÒ™Íít: "Xóa",™ÐCancel: "H çy—ÒÍÄ"™Ð ¢ ™
edittext: "",™Ðedittitle: "S ía dòng 2 ™ÐÔÃ™Íxt:"",™Ðaddtitle: "Thêm m Ûi 1 dòng™",Ð
deltext: "",™Ðdeltitle: "Xóa dòng 2 6•™ÐÔÃ™Íchtext: "",™Ðsearchtitle: "Tìm b £n
ghi",™Ðrefreshtext: "",™Ðrefreshtitle: "N ¡p l ¡i ™ÐleÍ¶'™Íp: "C £nh báo™,ÐerrtextÐ:
"Hãy ch Ín m Ùt dòng™,Ðtext: "",™Ðviewtitle: "Xem dòng 2 6•™ÐÔÃÖÂ ¢ ™caption:
"Ch Ín c ™,ÐbSubmit: "OK"™,ÐCancel: "H çy—ÒÍÜ"™Ð÷'2 ¢ ™errcap : "L ×™,ÐnoÐrl :
"không url ° ãc™,ÐnorecwBrds: "Không có b £n ghi ì2™,ÐmodeÍÒ™Í"Chi Áu dài c ça
colNames <> colModel!"ÐÒÍf÷&Ö GFW" ¢ ™integer : {thousandsSeparator: ".",
defaultValue: '0'},™Ðnumber : {decimalSeparator:",", thousandsSeparator: ".",
decimalPlaces: 2, defaultValue: '0'},™Ðcurrency : {decimalSeparator:",",
thousandsSeparator: ".", decimalPlaces: 2, prefix: "", suffix:"",
defaultValue: '0'},™Ðdate : {™ÐF ”æ ÖW3¢ ™™"CN", "T2", "T3", "T4", "T5", "T6",
"T7",™™"Ch ç nh -t", "Th é hai", "Th é ba", "Th é t "Â %F•î’ á m", "™™Ðé sáu", "Th é b £y
monthNames: [™™"Th1", "Th2", "Th3", "Th4", "Th5", "Th6", "Th7", "Th8", "Th9",
"Th10", "Th11", "Th12",™™"Tháng m Ùt", "Tháng hai", "Tháng ba", "Tháng t "Â %FŽ ær
n 6Ò"Â %FŽ ær > R"Â %FŽ ær !ê7’"Â %FŽ ær N Ò"Â %FŽ ær 6ŽÖâ"Â %FŽ ær Ñ° Ýi", "Tháng
m íÖ’ Ñí—B"Â %FŽ ær Ñ™•™Ý Ñ™Ò™Ð ²'> ær"Â&6†‘ì R"Â%< är"Â$4„™•™ÐÒ™Væ7F–öâ †¢’
{return j < 11 || j > 13 ? ['st', 'nd', 'rd', 'th'][Math.min((j - 1) % 10,
3)] : 'th';},™—7&6f÷&Ö C¢ u’ÖÒÖBr™ÍæWvf÷&Ö C¢ vâö¢õ’™Í '6U&R ¢ õ²2UÅÅÂó¥ó²âÀ
\t\s-]/,™–Ö 6·2 ¢™™// see http://php.net/manual/en/function.date.php for PHP
format used in jqGrid™™// and see http://docs.jquery.com/UI/Datepicker/
formatDate™™// and https://github.com/jquery/globalize#dates for alternative
formats used frequently™™// one can find on https://github.com/jquery/globalize/
tree/master/lib/cultures many™™// information about date, time, numbers and
currency formats used in different countries™™// one should just convert the
information in PHP format™™ISO8601Long:"Y-m-d H:i:s"™,™ÐSO8601Short:"Y-m-d"™™,Ð/
short date:™™// n - Numeric representation of a month, without leading zeros™™// j - Day of the month without leading zeros™™,Ð/ Y - A full numeric
representation of a year, 4 digits™™// example: 3/1/2012 which means 1 March
2012™™ShortDate: "n/j/Y", // in jQuery UI Datepicker: "M/d/yyyy"™™,Ð/ long date:™™// l - A full textual representation of the day of the week™™,Ð/ F - A
full textual representation of a month™™// d - Day of the month, 2 digits
with leading zeros™

™™//   Y - A full numeric representation of a year, 4 digitsÐ™™
LongDate: "l, F d, Y", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy"Ð™™//
long date with long time:Ð™™//   l - A full textual representation of the day
of the weekÐ™™//   F - A full textual representation of a monthÐ™™//   d - Day of
the month, 2 digits with leading zerosÐ™™//   Y - A full numeric representation
of a year, 4 digitsÐ™™//   g - 12-hour format of an hour without leading zerosÐ
™™//   i - Minutes with leading zerosÐ™™//   s - Seconds, with leading zerosÐ
™™//   A - Uppercase Ante meridiem and Post meridiem (AM or PM)Ð™™FullDateTime:
"l, F d, Y g:i:s A", // in jQuery UI Datepicker: "dddd, MMMM dd, yyyy h:mm:ss
tt"Ð™™// month day:Ð™™//   F - A full textual representation of a monthÐ™™//   d -
Day of the month, 2 digits with leading zerosÐ™™MonthDay: "F d", // in jQuery UI
Datepicker: "MMMM dd"Ð™™// short time (without seconds)Ð™™//   g - 12-hour format
of an hour without leading zerosÐ™™//   i - Minutes with leading zerosÐ™™//   A -
Uppercase Ante meridiem and Post meridiem (AM or PM)Ð™™ShortTime: "g:i A", // in
jQuery UI Datepicker: "h:mm tt"Ð™™// long time (with seconds)Ð™™//   g - 12-hour
format of an hour without leading zerosÐ™™//   i - Minutes with leading zerosÐ
™™//   s - Seconds, with leading zerosÐ™™//   A - Uppercase Ante meridiem and
Post meridiem (AM or PM)Ð™™LongTime: "g:i:s A", // in jQuery UI Datepicker:
"h:mm:ss tt"Ð™™SortableDateTime: "Y-m-d\\TH:i:s",Ð™™UniversalSortableDateTime: "Y-m-
d H:i:sO",Ð™™// month with yearÐ™™//   Y - A full numeric representation of a
year, 4 digitsÐ™™//   F - A full textual representation of a monthÐ™™YearMonth:
"F, Y" // in jQuery UI Datepicker: "MMMM, yyyy"Ð™™Ò¿&Vf÷&Ö D gFW$VF—B ¢ f ÇÖ]Ð™™
baseLinkUrl: '',Ð™™showAction: '',Ð™™target: '',Ð™™checkbox : {disabled:true},Ð™™idName :
'id'Ð™™});Ð™™})(jQuery);Ð™™

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-af.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.af={closeText:"Selekteer",prevText:"Vorige",nextText:"Volg
ende",currentText:"Vandag",monthNames:
["Januarie","Februarie","Maart","April","Mei","Junie","Julie","Augustus","September","Okto
["Jan","Feb","Mrt","Apr","Mei","Jun","Jul","Aug","Sep","Okt","Nov","Des"],dayNames:
["Sondag","Maandag","Dinsdag","Woensdag","Donderdag","Vrydag","Saterdag"],dayNamesShort:
["Son","Maa","Din","Woe","Don","Vry","Sat"],dayNamesMin:
["So","Ma","Di","Wo","Do","Vr","Sa"],weekHeader:"Wk",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.af)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ar-DZ.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t)
{t.datepicker.regional["ar-
DZ"]={closeText:"bV:dF'd""Ç &WeFW‡C¢"b7ƒ43¶'dF3bv(d""ÆæW‡EFW‡C¢&'dF*bvDd¢b7ƒ4S²"Æ7W'&VçEFW
["bÆ'dfAd¢"Â&Ad¦Ac J","dV'c 3","b6Ac JdB"Â&EbvJ","bÆHbvF","bÆHd¦Dd¦)","b6Hb¢"Â&3b†*dV(c "Â
["1","2","3","4","5","6","7","8","9","10","11","12"],dayNames:
["bvDb6-bò"Â&'dF'b¶Fd¦F","bvDb¶Dbv+bv!","bvDb61b†9bv!","bvDbæEd¦3","bvDbÆEc–)","bvDc6(b¢%Ò
["bvDb6-bò"Â&'dF'b¶Fd¦F","bvDb¶Dbv+bv!","bvDb61b†9bv!","bvDbæEd¦3","bvDbÆEc–)","bvDc6(b¢%Ò
0,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["ar-DZ"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ar.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(t){t.
datepicker.regional.ar={closeText:"bV:dF'd""Ç &WeFW‡C¢"b7ƒ43¶'dF3bv(d""ÆæW‡EFW‡C¢&'dF*bvDd
ntText:"bvDd¦HdR"ÆÖöçF„æ ÖW3¥²&CbvFd†F bvDb¶'dfJ","cF(bv7","b&0bv1","dfJc6'db"Â&EbvJd,"Â&-
bvDb6HdB%ÒÆÖöçF„æ ÖW56†÷'C
["1","2","3","4","5","6","7","8","9","10","11","12"],dayNames:
["bvDb6-bò"Â&'dF'b¶Fd¦F","bvDb¶Dbv+bv!","bvDb61b†9bv!","bvDbæEd¦3","bvDbÆEc–)","bvDc6(b¢%Ò
["bÒ"Â&F","b²"Â&1","bâ"Â&,","c2%ÒÇvVV´†V FW#¢&#c6(d†9",dateFormat:"dd/mm/yy",firstDay:6,is
0,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.ar)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-az.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(t){t.
datepicker.regional.az={closeText:"Ba öÆ "Ç &WeFW‡C¢"b7ƒ43´vW&’"ÆæW‡EFW‡C¢!0r%–Æ’b0
x3E;",currentText:"Bugün",monthNames:
["Yanvar","Fevral","Mart","Aprel","May","  —Vâ"Â!0yul","Avqust","Sentyabr","Oktyabr","Noya
["Yan","Fev","Mar","Apr","May","  —Vâ"Â!0yul","Avq","Sen","Okt","Noy","Dek"],dayNames:
["Bazar","Bazar ert%—6’"Â,rYr òYnb%’  •_am  "Â,rYr òYnb%’"Â$?ÆÒY
ax ö Ñ1","Cüm%’"Â!^%–æ"Y"],dayNamesShort:["B","Be","Ça","Ç","Ca","C"," â%ÒÆF ”æ ÖW4Ö–ã
["B","B","Ç","B "Â,r"Â$2"Â!^"],weekHeader:"Hf",dateFormat:"dd.mm.yy",firstDay:1,isRTL:!
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.az)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-be.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.be={closeText:"At0DtKCÔVDdL",prevText:"&larr;AÔ0CôOD â"ÆæW‡EFW‡C¢$ C A
rentText:"B QCÔLCÔO",monthNames:["B BD44Ct5CÔL","A´ND$K","B 0C¤0C$VC¢"Â$ D 0D 0C$VC¢"Â$"D
["B BD2"Â$ DäB","B 0C¢"Â$ D 0","B$@C "Â$'DÔ@","A´VCò"Â$ CÔV","A$5D "Â$ C A","A´VD "Â$!DÄ="
["CÔOCD7CT;Dò"Â$?C =Dô4Ct5C´0C¢"Â$0EäBCä@C :","D 5D 0CD0","Dt0DdLC$5D "Â$?DôBCÔVDd0","D CC
["AÔ4","Aô=","A ^","B @","BtF","AôB","B 1"],weekHeader:"B$4",dateFormat:"dd.mm.yy",firstDa
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.be)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-bg.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.bg={closeText:"Ct0D$2Cä@C,"Ç &WeFW‡C¢"b7ƒ43´=C 7C 4",nextText:"CÔ0Cô@C
igText:"&#x3E;&#x3E;",currentText:"CD=CTA",monthNames:
["Bô=D40D 8","BD5C$@D40D 8","AÄ0D B","A ?D 8C²"Â$ C 9","Bä=C,"Â$.C´8","A 2C4CD B","B 5CôBC
["Bô=D2"Â$$CT2","AÄ0D "Â$ Cô@","AÄ0C’"Â$.CÔ8","Bä;C,"Â$ C$3","B 5Cò"Â$ C¤B","AÔ>C""Â$ CT:"
["AÔ5CD5C´O","Aô>CÔ5CD5C´=C„:","A$BCä@CÔ8C¢"Â$!D OCD0","Bt5D$2D¤@D$JC¢"Â$ CTBD¤:","B JC >D
["AÔ5","Aô>","A$B","B @","Bt5","Aô5","B J"],weekHeader:"Wk",dateFormat:"dd.mm.yy",firstDay
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.bg)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-bs.min.js

/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.bs={closeText:"Zatvori",prevText:"<",nextText:">
",currentText:"Danas",monthNames:
["Januar","Februar","Mart","April","Maj","Juni","Juli","August","Septembar","Oktobar","Nov
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","Aug","Sep","Okt","Nov","Dec"],dayNames:
["Nedelja","Ponedeljak","Utorak","Srijeda"," ÆWGg'F ²"Â% WF ²"Â%7V&÷F %ÒÆF ”æ ÖW56†÷'C
["Ned","Pon","Uto","Sri"," ÆWB"Â% WB"Â%7V"%ÒÆF ”æ ÖW4Ö–ã
["Ne","Po","Ut","Sr"," ÆR"Â% R"Â%7R%ÒÇvVV´†V FW#¢%v²"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ—5%
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.bs)});

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ca.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.ca={closeText:"Tanca",prevText:"Anterior",nextText:"Següen
t",currentText:"Avui",monthNames:
["gener","febrer","març","abril","maig","juny","juliol","agost","setembre","octubre","nove
["gen","feb","març","abr","maig","juny","jul","ag","set","oct","nov","des"],dayNames:
["diumenge","dilluns","dimarts","dimecres","dijous","divendres","dissabte"],dayNamesShort:
["dg","dl","dt","dc","dj","dv","ds"],dayNamesMin:
["dg","dl","dt","dc","dj","dv","ds"],weekHeader:"Set",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.ca)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-cs.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.cs={closeText:"Zav ž×B"Ç &WeFW‡C¢"b7ƒ43´AYíve",nextText:"Pozd °
ji&#x3E;",currentText:"Nyní",monthNames:
["leden","únor","b –W¦Vâ"Â&GV&Vâ"Â&·a ten"," ÖW'fVâ"Â! ervenec","srpen","zá žÒ"Â!Yíjen","l
["led","úno","b –R"Â&GV""Â&·a "," ÖW""Â! vc","srp","zá ’"Â!Yíj","lis","pro"],dayNames:
["ned ¶ÆR"Â' öæA lí","úterý","st –VF "Â! tvrtek","pátek","sobota"],dayNamesShort:
["ne","po","út","st"," ×B"Â'  "Â'6ò%ÒÆF ”æ ÖW4Ö–ã
["ne","po","út","st"," ×B"Â'  "Â'6ò%ÒÇvVV´†V FW#¢%OÖB"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ—5
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.cs)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-cy-GB.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17 http://jqueryui.com Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["cy-
GB"]={closeText:"Done",prevText:"Prev",nextText:"Next",currentText:"Today",monthNames:
["Ionawr","Chwefror","Mawrth","Ebrill","Mai","Mehefin","Gorffennaf","Awst","Medi","Hydref"
["Ion","Chw","Maw","Ebr","Mai","Meh","Gor","Aws","Med","Hyd","Tac","Rha"],dayNames:
["Dydd Sul","Dydd Llun","Dydd Mawrth","Dydd Mercher","Dydd Iau","Dydd
Gwener","Dydd Sadwrn"],dayNamesShort:
["Sul","Llu","Maw","Mer","Iau","Gwe","Sad"],dayNamesMin:
["Su","Ll","Ma","Me","Ia","Gw","Sa"],weekHeader:"Wy",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["cy-GB"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-da.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.da={closeText:"Luk",prevText:"&#x3C;Forrige",nextText:"Næs
te&#x3E;",currentText:"Idag",monthNames:
["Januar","Februar","Marts","April","Maj","Juni","Juli","August","September","Oktober","No
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","Aug","Sep","Okt","Nov","Dec"],dayNames:
["Søndag","Mandag","Tirsdag","Onsdag","Torsdag","Fredag","Lørdag"],dayNamesShort:
["Søn","Man","Tir","Ons","Tor","Fre","Lør"],dayNamesMin:
["Sø","Ma","Ti","On","To","Fr","Lø"],weekHeader:"Uge",dateFormat:"dd-mm-
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.da)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-de.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.de={closeText:"Schließen",prevText:"&#x3C;Zurück",nextText
:"Vor&#x3E;",currentText:"Heute",monthNames:
["Januar","Februar","März","April","Mai","Juni","Juli","August","September","Oktober","Nov
["Jan","Feb","Mär","Apr","Mai","Jun","Jul","Aug","Sep","Okt","Nov","Dez"],dayNames:
["Sonntag","Montag","Dienstag","Mittwoch","Donnerstag","Freitag","Samstag"],dayNamesShort:
["So","Mo","Di","Mi","Do","Fr","Sa"],dayNamesMin:
["So","Mo","Di","Mi","Do","Fr","Sa"],weekHeader:"KW",dateFormat:"dd.mm.yy",firstDay:1,isRT
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.de)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-el.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t)
{t.datepicker.regional.el={closeText:"9£»;S¯<3¹;Ã¿",prevText:": Á;ó·;3¿<Ó¼;S½;óÂ",nextText
9Ã®;Ó±<""ÆÖöçF„æ ÖW3¥²#™; ½;óÅ:ÃÁ;“¿<""Â#¦;S²< ¿<S¬< ¹;óÂ","9Ã¬< Ä;“¿<""Â#’< Á:ó»;“¿<""Â#œ
["9“±;Ò"Â#¦;S²","9Ã±< "Â#’< Á","9Ã±;’"Â#™;óÅ;Ò"Â#™;óÅ;²"Â#’<S³",":3µ< "Â#Ÿ;£Ä","9Ó¿;R"Â#”;
["9£Å< ¹; º:â"Â#”;SÅ<C-< ±",":CÁ:óÄ;r"Â#¤;SÄ:ÃÁ<C·",": -;ÃÀ<C·",": ±< ±<3º;SÅ:â"Â#£:Ã²;#±<
["9£Å","9Cµ",":CÁ",":Cµ",": µ",": ±",":3±"],weekHeader:"9S²;B"ÆF FTf÷&Ö C¢&FBöÖÒ÷—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.el)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-AU.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["en-
AU"]={closeText:"Done",prevText:"Prev",nextText:"Next",currentText:"Today",monthNames:
["January","February","March","April","May","June","July","August","September","October","
["Jan","Feb","Mar","Apr","May","Jun","Jul","Aug","Sep","Oct","Nov","Dec"],dayNames:
["Sunday","Monday","Tuesday","Wednesday","Thursday","Friday","Saturday"],dayNamesShort:
["Sun","Mon","Tue","Wed","Thu","Fri","Sat"],dayNamesMin:
["Su","Mo","Tu","We","Th","Fr","Sa"],weekHeader:"Wk",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["en-AU"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-GB.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["en-
GB"]={closeText:"Done",prevText:"Prev",nextText:"Next",currentText:"Today",monthNames:
["January","February","March","April","May","June","July","August","September","October","
["Jan","Feb","Mar","Apr","May","Jun","Jul","Aug","Sep","Oct","Nov","Dec"],dayNames:
["Sunday","Monday","Tuesday","Wednesday","Thursday","Friday","Saturday"],dayNamesShort:
["Sun","Mon","Tue","Wed","Thu","Fri","Sat"],dayNamesMin:
["Su","Mo","Tu","We","Th","Fr","Sa"],weekHeader:"Wk",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["en-GB"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-NZ.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17 * http://jqueryui.com * Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["en-
NZ"]={closeText:"Done",prevText:"Prev",nextText:"Next",currentText:"Today",monthNames:
["January","February","March","April","May","June","July","August","September","October","
["Jan","Feb","Mar","Apr","May","Jun","Jul","Aug","Sep","Oct","Nov","Dec"],dayNames:
["Sunday","Monday","Tuesday","Wednesday","Thursday","Friday","Saturday"],dayNamesShort:
["Sun","Mon","Tue","Wed","Thu","Fri","Sat"],dayNamesMin:
["Su","Mo","Tu","We","Th","Fr","Sa"],weekHeader:"Wk",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["en-NZ"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-eo.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.eo={closeText:"Fermi",prevText:"&#x3C;Anta",nextText:"Sekv
&#x3E;",currentText:"Nuna",monthNames:
["Januaro","Februaro","Marto","Aprilo","Majo","Junio","Julio","A ÖwW7Fò"Â%6W FVÖ'&ò"Â$ö·Fö
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","A Ör"Â%6W "Â$ö·B"Â$æ÷b"Â$FV2%ÒÆF ”æ ÖW3
["Diman –ò"Â$ÇVæFò"Â$Ö &Fò"Â$ÖW&·&VFò"Â!4a ÖFò"Â%fVæG&VFò"Â%6 & Fò%ÒÆF ”æ ÖW56†÷'C
["Dim","Lun","Mar","Mer"," F m","Ven","Sab"],dayNamesMin:
["Di","Lu","Ma","Me"," F "Â%fR"Â%6 %ÒÇvVV´†V FW#¢%6""ÆF FTf÷&Ö C¢&FBöÖÒð
yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.eo)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-es.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.es={closeText:"Cerrar",prevText:"&#x3C;Ant",nextText:"Sig&
#x3E;",currentText:"Hoy",monthNames:
["enero","febrero","marzo","abril","mayo","junio","julio","agosto","septiembre","octubre",
["ene","feb","mar","abr","may","jun","jul","ogo","sep","oct","nov","dic"],dayNames:
["domingo","lunes","martes","miércoles","jueves","viernes","sábado"],dayNamesShort:
["dom","lun","mar","mié","juv","vie","sáb"],dayNamesMin:
["D","L","M","X","J","V","S"],weekHeader:"Sm",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.es)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-et.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.et={closeText:"Sulge",prevText:"Eelnev",nextText:"Järgnev"
,currentText:"Täna",monthNames:
["Jaanuar","Veebruar","Märts","Aprill","Mai","Juuni","Juuli","August","September","Oktoobe
["Jaan","Veebr","Märts","Apr","Mai","Juuni","Juuli","Aug","Sept","Okt","Nov","Dets"],dayNa
["Pühapäev","Esmaspäev","Teisipäev","Kolmapäev","Neljapäev","Reede","Laupäev"],dayNamesSho
["Pühap","Esmasp","Teisip","Kolmap","Neljap","Reede","Laup"],dayNamesMin:
["P","E","T","K","N","R","L"],weekHeader:"näd",dateFormat:"dd.mm.yy",firstDay:1,isRTL:!
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.et)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-eu.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.eu={closeText:"Egina",prevText:"&#x3C;Aur",nextText:"Hur&#
x3E;",currentText:"Gaur",monthNames:
["urtarrila","otsaila","martxoa","apirila","maiatza","ekaina","uztaila","abuztua","iraila"
["urt.","ots.","mar.","api.","mai.","eka.","uzt.","abu.","ira.","urr.","aza.","abe."],dayN
["igandea","astelehena","asteartea","asteazkena","osteguna","ostirala","larunbata"],dayNam
["ig.","al.","ar.","az.","og.","ol.","lr."],dayNamesMin:
["ig","al","ar","az","og","ol","lr"],weekHeader:"As",dateFormat:"yy-mm-
dd",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.eu)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fa.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.fa={closeText:"b†3b¦F",prevText:"&#x3C;d&(dFÌ",nextText:"b†9böÌ&#x3E;"
ntText:"bvEc Hc""ÆÖöçF„æ ÖW3¥²&Ac Hc /d¦F","bv1böJb†GcF*","bæ1bö'bò"Â&*d¦1","dV1bö'bò"Â&4d
["1","2","3","4","5","6","7","8","9","10","11","12"],dayNames:
["d¦©cFFb†G","böHcFFb†G","c6G  cFFb†G","hfGbv1cFFb†G","gæFbÆ4df(dr"Â&,dV9dr"Â&4df(dr%ÒÆF ”
["lÂ"Â&/","c2"Â&†","gâ"Â&,","cB%ÒÇvVV´†V FW#¢&Gd "ÆF FTf÷&Ö C¢'—’öÖÒöFB"Æf—'7DF “£bÆ—5%DÃ¢
0,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.fa)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fi.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t){t.
datepicker.regional.fi={closeText:"Sulje",prevText:"&#xAB;Edellinen",nextText:
"Seuraava&#xBB;",currentText:"Tänään",monthNames:["Tammikuu","Helmikuu","Maali
skuu","Huhtikuu","Toukokuu","Kesäkuu","Heinäkuu","Elokuu","Syyskuu","Lokakuu",
"Marraskuu","Joulukuu"],monthNamesShort:
["Tammi","Helmi","Maalis","Huhti","Touko","Kesä","Heinä","Elo","Syys","Loka","Marras","Jou
["Su","Ma","Ti","Ke","To","Pe","La"],dayNames:
["Sunnuntai","Maanantai","Tiistai","Keskiviikko","Torstai","Perjantai","Lauantai"],dayName
["Su","Ma","Ti","Ke","To","Pe","La"],weekHeader:"Vk",dateFormat:"d.m.yy",firstDay:1,isRTL:
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.fi)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fo.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(t)
{t.datepicker.regional.fo={closeText:"Lat
aftur",prevText:"&#x3C;Fyrra",nextText:"Næsta&#x3E;",currentText:"Í
dag",monthNames:
["Januar","Februar","Mars","Apríl","Mei","Juni","Juli","August","September","Oktober","Nov
["Jan","Feb","Mar","Apr","Mei","Jun","Jul","Aug","Sep","Okt","Nov","Des"],dayNames:
["Sunnudagur","Mánadagur","Týsdagur","Mikudagur","Hósdagur","Fríggjadagur","Leyardagur"],d
["Sun","Mán","Týs","Mik","Hós","Frí","Ley"],dayNamesMin:
["Su","Má","Tý","Mi","Hó","Fr","Le"],weekHeader:"Vk",dateFormat:"dd-mm-
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.fo)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr-CA.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17 http://jqueryui.com Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["fr-
CA"]={closeText:"Fermer",prevText:"Précédent",nextText:"Suivant",currentText:"Aujourd'hui"
["janvier","février","mars","avril","mai","juin","juillet","août","septembre","octobre","n
["janv.","févr.","mars","avril","mai","juin","juil.","août","sept.","oct.","nov.","déc."],
["dimanche","lundi","mardi","mercredi","jeudi","vendredi","samedi"],dayNamesShort:
["dim.","lun.","mar.","mer.","jeu.","ven.","sam."],dayNamesMin:
["D","L","M","M","J","V","S"],weekHeader:"Sem.",dateFormat:"yy-mm-
dd",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["fr-CA"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr-CH.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17 http://jqueryui.com Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t)
{t.datepicker.regional["fr-
CH"]={closeText:"Fermer",prevText:"&#x3C;Préc",nextText:"Suiv&#x3E;",currentText:"Courant"
["janvier","février","mars","avril","mai","juin","juillet","août","septembre","octobre","n
["janv.","févr.","mars","avril","mai","juin","juil.","août","sept.","oct.","nov.","déc."],
["dimanche","lundi","mardi","mercredi","jeudi","vendredi","samedi"],dayNamesShort:
["dim.","lun.","mar.","mer.","jeu.","ven.","sam."],dayNamesMin:
["D","L","M","M","J","V","S"],weekHeader:"Sm",dateFormat:"dd.mm.yy",firstDay:1,isRTL:!
1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional["fr-CH"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.fr={closeText:"Fermer",prevText:"Précédent",nextText:"Suiv
ant",currentText:"Aujourd'hui",monthNames:
["janvier","février","mars","avril","mai","juin","juillet","août","septembre","octobre","n
["janv.","févr.","mars","avril","mai","juin","juil.","août","sept.","oct.","nov.","déc."],
["dimanche","lundi","mardi","mercredi","jeudi","vendredi","samedi"],dayNamesShort:
["dim.","lun.","mar.","mer.","jeu.","ven.","sam."],dayNamesMin:
["D","L","M","M","J","V","S"],weekHeader:"Sem.",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.fr)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-gl.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(t){t.
datepicker.regional.gl={closeText:"Pechar",prevText:"&#x3C;Ant",nextText:"Seg&
#x3E;",currentText:"Hoxe",monthNames:
["Xaneiro","Febreiro","Marzo","Abril","Maio","Xuño","Xullo","Agosto","Setembro","Outubro",
["Xan","Feb","Mar","Abr","Mai","Xuñ","Xul","Ago","Set","Out","Nov","Dec"],dayNames:
["Domingo","Luns","Martes","Mércores","Xoves","Venres","Sábado"],dayNamesShort:
["Dom","Lun","Mar","Mér","Xov","Ven","Sáb"],dayNamesMin:
["Do","Lu","Ma","Mé","Xo","Ve","Sá"],weekHeader:"Sm",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.gl)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-he.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(t){t.
datepicker.regional.he={closeText:"^ Ò]Uè",prevText:"&#x3C;]Eç]UÓ]Ò"ÆæW‡EFW‡C¢%Ô] Þ&#x3E;"
ntText:"]EÙ]UÝ",monthNames:["]•à]UÐ^,"Â%ä] è]UÐ^,"Â%Þ^…å","] ä^…Ù]Â"Â%Þ] Ù","]•Õ^ Ù","]•Õ]
["]•à]R"Â%ä] è","]åè^R"Â%Ð^Eè","]åÐ]'"Â%Ù]Uà]'"Â%Ù]UÜ]'"Â%Ð]UÒ","^ ä],"Â%Ð]Uç","^ Õ] "Â%Ó^
["^…Ð^•Õ]ò"Â%é^ Ù","^•Ü]•é]'"Â%è] Ù^%Ù","]uÞ]•é]'"Â%é]•é]'"Â%é] ê"],dayNamesShort:["] r"Â%
["] r"Â%Ñ'","]"r"Â%Ó'","]Br"Â%Õ'","^•Ñ^¢%ÒÇvVV´†V FW#¢%v²"ÆF FTf÷&Ö C¢&FBöÖÒð
yy",firstDay:0,isRTL:!0,showMonthAfterYear:!
1,yearSuffix:""},t.datepicker.setDefaults(t.datepicker.regional.he)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hi.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.hi={closeText:"’É ’b"Ç &WeFW‡C¢)*“ù “)>",nextText:"•Y “)>",currentText
nthNames:["’É(“Y0”  "Â)+“ 5“ @","’é>“ M’¢"Â) ’©M“ G“""Â).•,"Â) ”)(","’ÉB“)>•,"Â) ‘y8”Ù$ ",
["’É(","’¹0","’é>“ M’¢"Â) ’©M“ G“""Â).•,"Â) ”)(","’ÉB“)>•,"Â) ‘r"Â)8“ù$","•Y ”Ù ","’‰5","’
["“ 5“ù5“é0","“‰K’é5“é0","’é ‘y2“Y>“ "Â),” '“Y>“ "Â) ” 0” 5“é0","“iA’YM“ 5“é0","“i(“ù5“é0"
["“ 5“ò"Â)8”¹.","’é ‘y2","’ÉA’r"Â) ” 0” "Â)6”  ”Ù0","“i(“ò%ÒÇvVV´†V FW#¢)9’¹M’I>",dateForm
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.hi)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hr.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.hr={closeText:"Zatvori",prevText:"&#x3C;",nextText:"&#x3E;
",currentText:"Danas",monthNames:
["Sije Ö æ¢"Â%fVÆ¦  a","Ožujak","Travanj","Svibanj","Lipanj","Srpanj","Kolovoz","Rujan","L
["Sij","Velj","Ožu","Tra","Svi","Lip","Srp","Kol","Ruj","Lis","Stu","Pro"],dayNames:
["Nedjelja","Ponedjeljak","Utorak","Srijeda"," ÆWGg'F ²"Â% WF ²"Â%7V&÷F %ÒÆF ”æ ÖW56†÷'C
["Ned","Pon","Uto","Sri"," ÆWB"Â% WB"Â%7V"%ÒÆF ”æ ÖW4Ö–ã
["Ne","Po","Ut","Sr"," ÆR"Â% R"Â%7R%ÒÇvVV´†V FW#¢%F¦R"ÆF FTf÷&Ö C¢&FBæÖÒç—’â"Æf—'7DF “£ Æ—
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.hr)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hu.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.hu={closeText:"bezár",prevText:"vissza",nextText:"el  &R"Æ7P
rrentText:"ma",monthNames:["Január","Február","Március","Április","Május","Jún
ius","Július","Augusztus","Szeptember","Október","November","December"],monthN
amesShort:
["Jan","Feb","Már","Ápr","Máj","Jún","Júl","Aug","Szep","Okt","Nov","Dec"],dayNames:
["Vasárnap","Hétf  "Â$¶VFB"Â%7¦W&F "Â$7?ÇOg'Of²"Â% –çFV²"Â%7¦öÖ& B%ÒÆF ”æ ÖW56†÷'C
["Vas","Hét","Ked","Sze","Csü","Pén","Szo"],dayNamesMin:
["V","H","K","Sze","Cs","P","Szo"],weekHeader:"Hét",dateFormat:"yy.mm.dd.",firstDay:1,isRT
1,showMonthAfterYear:!
0,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.hu)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hy.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.hy={closeText:"U5aVõeVÂ"Ç &WeFW‡C¢"b7ƒ43µFV m.",nextText:"T aW²âb7ƒ4S²
rentText:"S uWÕ…X "ÆÖöçF„æ ÖW3¥²%@W…,We~V €","U5eWõ€WåaX "Â%DV €Wò"Â%1W¥€Vµl","TEaWUkWÒ"Â%
["T xX%vWâ"Â%SVU•X "Â%DV €Wò"Â%1W¥€","TEaWUkWÒ"Â%@W…,WekWÒ"Â%@W…,VÂ"Â%UV5}","TÕeW¢"Â%@W…o"
["VõkX aVõk","VUoW…,WuaV%iV²"Â%eX eXEwV bV•k","W•xX eXEwV bV•k","W kWecWuaV%iV²"Â%xX%€V%aV
["VõkX "Â%eX o","VU€XB"Â%yX „","W vV2"Â%xX%€V""Â%wV%i"],weekHeader:"Tu2Tò"ÆF FTf÷&Ö C¢&FBæ
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.hy)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-id.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.id={closeText:"Tutup",prevText:"&#x3C;mundur",nextText:"ma
ju&#x3E;",currentText:"hari ini",monthNames:
["Januari","Februari","Maret","April","Mei","Juni","Juli","Agustus","September","Oktober",
["Jan","Feb","Mar","Apr","Mei","Jun","Jul","Agus","Sep","Okt","Nop","Des"],dayNames:
["Minggu","Senin","Selasa","Rabu","Kamis","Jumat","Sabtu"],dayNamesShort:
["Min","Sen","Sel","Rab","kam","Jum","Sab"],dayNamesMin:
["Mg","Sn","Sl","Rb","Km","jm","Sb"],weekHeader:"Mg",dateFormat:"dd/mm/
yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.id)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-is.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.is={closeText:"Loka",prevText:"&#x3C;
Fyrri",nextText:"Næsti &#x3E;",currentText:"Í dag",monthNames:
["Janúar","Febrúar","Mars","Apríl","Maí","Júní","Júlí","Ágúst","September","Október","Nóve
["Jan","Feb","Mar","Apr","Maí","Jún","Júl","Ágú","Sep","Okt","Nóv","Des"],dayNames:
["Sunnudagur","Mánudagur","Þriðjudagur","Miðvikudagur","Fimmtudagur","Föstudagur","Laugard
["Sun","Mán","Þri","Mið","Fim","Fös","Lau"],dayNamesMin:
["Su","Má","Þr","Mi","Fi","Fö","La"],weekHeader:"Vika",dateFormat:"dd.mm.yy",firstDay:0,is
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.is)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-it.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.it={closeText:"Chiudi",prevText:"&#x3C;Prec",nextText:"Suc
c&#x3E;",currentText:"Oggi",monthNames:["Gennaio","Febbraio","Marzo","Aprile",
"Maggio","Giugno","Luglio","Agosto","Settembre","Ottobre","Novembre","Dicembre
"],monthNamesShort:
["Gen","Feb","Mar","Apr","Mag","Giu","Lug","Ago","Set","Ott","Nov","Dic"],dayNames:
["Domenica","Lunedì","Martedì","Mercoledì","Giovedì","Venerdì","Sabato"],dayNamesShort:
["Dom","Lun","Mar","Mer","Gio","Ven","Sab"],dayNamesMin:
["Do","Lu","Ma","Me","Gi","Ve","Sa"],weekHeader:"Sm",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.it)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ja.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.ja={closeText:"•‰0X0‹",prevText:"&#x3C;RM",nextText:"k!
&#x3E;",currentText:"NÊeå",monthNames:["1g ","2g ","3g ","4g ","5g ","6g ","7g ","8g ","9g
g ","11g ","12g "],monthNamesShort:["1g ","2g ","3g ","4g ","5g ","6g ","7g ","8g ","9g ",
g ","12g "],dayNames:["eåfÜeå","g fÜeå","pkfÜeå","l4fÜeå","g(fÜeå","’ÑfÜeå","W fÜeå"],dayN
["eå","g ","pk","l4","g(","‘Ñ","W "],dayNamesMin:
["eå","g ","pk","l4","g(","‘Ñ","W "],weekHeader:"•1",dateFormat:"yy/mm/dd",firstDay:0,isRT
1,showMonthAfterYear:!
0,yearSuffix:"^t"},e.datepicker.setDefaults(e.datepicker.regional.ja)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ka.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */Þ(function(e)
{e.datepicker.regional.ka={closeText:" Ó Ð î ã à Õ Ð",prevText:"&#x3c;  ì Ø Ü Ð",nextText:
&#x3e;",currentText:" Ó æ Ô á",monthNames:
[" Ø Ð Ü Õ Ð à Ø"," × Ô Ñ Ô à Õ Ð Ú Ø"," Û Ð à â Ø"," Ð Þ à Ø Ú Ø"," Û Ð Ø á Ø"," Ø Õ Ü Ø
[" Ø Ð Ü"," × Ô Ñ"," Û Ð à"," Ð Þ à"," Û Ð Ø"," Ø Õ Ü"," Ø Õ Ú"," Ð Ò Õ"," á Ô å"," Ý å â"
[" Ù Õ Ø à Ð"," Ý à è Ð Ñ Ð × Ø"," á Ð Û è Ð Ñ Ð × Ø"," Ý × î è Ð Ñ Ð × Ø"," î ã × è Ð Ñ Ð
[" Ù Õ"," Ý à è"," á Ð Û"," Ý × î"," î ã ×"," Þ Ð à"," è Ð Ñ"],weekHeader:" Ù Õ Ø à Ð",dat
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ka)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-kk.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.kk={closeText:"Ad0C C",prevText:"&#x3C;A ;CDKJ4“D²"ÆæW‡EFW‡C¢$ CT;CTAE
ntText:"A ¯C4VCÒ"ÆÖöçF„æ ÖW3¥²$šC £D$0D "Â$ I´?C =","AÔ0D4@D´7","B ÙD4VD "Â$ C <D´@","AÄ0D
["I¤0J2"Â$ I´?","AÔ0D2"Â$!M”C","AÄ0CÂ"Â$ C C","B„VC²"Â$"C <","I¤KD "Â$šC 7","I¤0D "Â$ CT;"
["Ad5C¤ACT=C V","AD¯C”ACT=C V","B 5C”ACT=C V","B ÙD ACT=C V","A 5C”ACT=C V","Ad±CÄ0","B 5C
["Ad:","ADA","B A","B @","A A","Ad<","B ="],weekHeader:"AÔ5",dateFormat:"dd.mm.yy",firstDa
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.kk)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-km.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.km={closeText:" ′ Ò œ ¾   š ½ …",prevText:" ˜ » “",nextText:" ” “ Ò
 “ Á Ç",monthNames:[" ˜ € š ¶"," € » ˜ Ò — È"," ˜ ¸ “ ¶"," ˜ Á Ÿ ¶"," § Ÿ — ¶"," ˜ · • » “
[" ˜ € š ¶"," € » ˜ Ò — È"," ˜ ¸ “ ¶"," ˜ Á Ÿ ¶"," § Ÿ — ¶"," ˜ · • » “ ¶"," € € Ò € Š ¶",
[" ¢ ¶ ′ · • Ò ™"," … “ Ò ′"," ¢ „ Ò ‚ ¶ š"," – » ′"," – Ò š   Ÿ Ò ” • · Í"," Ÿ » € Ò š","
[" ¢ ¶"," …"," ¢"," – »"," – Ò š  "," Ÿ »"," Ÿ Å"],weekHeader:" Ÿ ” Ò Š ¶   Í",dateFormat:
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.km)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ko.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.ko={closeText:"²ë®0",prevText:"ÇtÈ ²ì",nextText:"²äÇL²ì",currentTex
²˜",monthNames:["1ÆÔ","2ÆÔ","3ÆÔ","4ÆÔ","5ÆÔ","6ÆÔ","7ÆÔ","8ÆÔ","9ÆÔ","10ÆÔ","11ÆÔ","12
ÆÔ"],monthNamesShort:["1ÆÔ","2ÆÔ","3ÆÔ","4ÆÔ","5ÆÔ","6ÆÔ","7ÆÔ","8ÆÔ","9ÆÔ","10ÆÔ","11ÆÔ",
ÆÔ"],dayNames:["Ç|Æ”Ç|","ÆÔÆ”Ç|","ÖTÆ”Ç|","Â Æ”Ç|","º©Æ”Ç|","® Æ”Ç|","Ñ Æ”Ç|"],dayNamesSho
["Ç|","ÆÔ","ÖT","Â ","º©","® ","Ñ "],dayNamesMin:
["Ç|","ÆÔ","ÖT","Â ","º©","® ","Ñ "],weekHeader:"Wk",dateFormat:"yy-mm-
dd",firstDay:0,isRTL:!1,showMonthAfterYear:!
0,yearSuffix:"±D"},e.datepicker.setDefaults(e.datepicker.regional.ko)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ky.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.ky={closeText:"Ad0C CD2"Ç &WeFW‡C¢"b7ƒ63´ D4@",nextText:"A¤8C’b7ƒ6S²"Æ
ntText:"A ¯C4¯CÒ"ÆÖöçF„æ ÖW3¥²$/CÔ2C @DÂ"Â$$CT2D 0C´L","AÄ0D B","A ?D 5C´L","AÄ0C’"Â$ Dä=D
["Bô=C""Â$$CT2","AÄ0D "Â$ Cô@","AÄ0C’"Â$ Dä=","A„NC²"Â$ C$3","B 5CÒ"Â$ C¤B","AÔ>Dò"Â$ CT:"
["Cd5C¤HCT<C 8","CD¯C”HN”<C ¯","D„5C”HCT<C 8","D„0D HCT<C 8","C 5C”HCT<C 8","CdCCÄ0","C„HC
["Ad:","ADH","B„H","B„@","A H","Ad<","A„H"],weekHeader:"AdCCÂ"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ky)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lb.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.lb={closeText:"Fäerdeg",prevText:"Zréck",nextText:"Weider"
,currentText:"Haut",monthNames:
["Januar","Februar","Mäerz","Abrëll","Mee","Juni","Juli","August","September","Oktober","N
["Jan","Feb","Mäe","Abr","Mee","Jun","Jul","Aug","Sep","Okt","Nov","Dez"],dayNames:
["Sonndeg","Méindeg","Dënschdeg","Mëttwoch","Donneschdeg","Freideg","Samschdeg"],dayNamesS
["Son","Méi","Dën","Mët","Don","Fre","Sam"],dayNamesMin:
["So","Mé","Dë","Më","Do","Fr","Sa"],weekHeader:"W",dateFormat:"dd.mm.yy",firstDay:1,isRTL
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.lb)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lt.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.lt={closeText:"Uždaryti",prevText:"&#x3C;Atgal",nextText:"
Pirmyn&#x3E;",currentText:"Šiandien",monthNames:
["Sausis","Vasaris","Kovas","Balandis","Geguž r"Â$&—)æVÆ—2"Â$Æ–W  "Â%'Vw ¡ktis","Rugs v¦—2
["Sau","Vas","Kov","Bal","Geg","Bir","Lie","Rugp","Rugs","Spa","Lap","Gru"],dayNames:
["sekmadienis","pirmadienis","antradienis","tre Ö– F–Væ—2"Â&¶WGf—'F F–Væ—2"Â' Væ·F F–Væ—2"
["sek","pir","ant","tre","ket","pen","šeš"],dayNamesMin:
["Se","Pr","An","Tr","Ke","Pe","Še"],weekHeader:"SAV",dateFormat:"yy-mm-
dd",firstDay:1,isRTL:!1,showMonthAfterYear:!
0,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.lt)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lv.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.lv={closeText:"Aizv 7'B"Ç &WeFW‡C¢$–W "â"ÆæW‡EFW‡C¢$á k.",cur
rentText:"Šodien",monthNames:["Janv  &—2"Â$fV''Q ris","Marts","Apr ¶Æ—2"Â$Ö –§2"Â$¡k
nijs","J ¶Æ–§2"Â$ VwW7G2"Â%6W FVÖ'&—2"Â$ö·Fö'&—2"Â$æ÷fVÖ'&—2"Â$FV6VÖ'&—2%ÒÆÖöçF€
NamesShort:
["Jan","Feb","Mar","Apr","Mai","J ¶â"Â$¡kl","Aug","Sep","Okt","Nov","Dec"],dayNames:
["sv 7FF–Væ "Â' —&ÖF–Væ "Â&÷G&F–Væ "Â'G&Y¦F–Væ "Â&6WGW'FF–Væ "Â' –V·FF–Væ "Â'6W7FF–Væ %ÒÆF
["svt","prm","otr","tre","ctr","pkt","sst"],dayNamesMin:
["Sv","Pr","Ot","Tr","Ct","Pk","Ss"],weekHeader:"Ned.",dateFormat:"dd.mm.yy",firstDay:1,is
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.lv)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-mk.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.mk={closeText:"At0D$2Cä@C,"Ç &WeFW‡C¢"b7ƒ43²"ÆæW‡EFW‡C¢"b7ƒ4S²"Æ7W'&P
ntText:"AD5CÔ5D "ÆÖöçF„æ ÖW3¥²$ C =D40D 8","BD5C$@D40D 8","AÄ0D B","A ?D 8C²"Â$ C X","@„CC
["@„0CÒ"Â$$CT2","AÄ0D "Â$ Cô@","AÄ0E,"Â$ D4=","@„CC²"Â$ C$3","B 5Cò"Â$ C¤B","AÔ>CR"Â$ CT:"
["AÔ5CD5C´0","Aô>CÔ5CD5C´=C„:","A$BCä@CÔ8C¢"Â$!D 5CD0","Bt5D$2D BCä:","Aô5D$>C¢"Â$!C 1CäBC
["AÔ5","Aô>","A$B","B @","Bt5","Aô5","B 0"],weekHeader:"B 5CB"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.mk)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ml.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.ml={closeText:"Óm0Óò"Ç &WeFW‡C¢-.Ô (ÔÝ(ÒMMÒMF",nextText:"Þ] Ô $ÔÝ$Ò
",currentText:"Þ}(ÔÝ(ÔÒ"ÆÖöçF„æ ÖW3
["ÑÍ(Ô 5Ó ?","Ò½FÒÍMÓ AÓ]0Óò"Â-.Óí0ÔÒ Ý ÔÝ ÔÒ"Â- Ò-MÓ ?Ó-M  ","ÒíGÒýM","ÑÍBÒ=M  ","ÑÍBÓ-H"
["ÑÍ(Ô "Â-+Ôm,ÔÒ"Â-.Óí0ÔÒ Ò"Â- Ò-MÓ ?","ÒíGÒýM","ÑÍBÒ=M  ","ÑÍBÓ->","Þm ","Ó•FÒ-M","Ñ- ÔÝ
["Ñí>Òý0ÔÒ Ò"Â-$Óý ÔÝ Ó=M  ","Ñ-JÓ]MÓR"Â-,Ô 'Ò•M  ","Ó]MÒý>ÓM ","Ó]FÓ=MÓ=?","Óm(Óò%ÒÆF ”æ
["Ñí>","ÒM?","Ñ-J","ÒÍA","Ó]MÒý>","Ó]F","Ób%ÒÇvVV´†V FW#¢- ",dateFormat:"dd/mm/yy",firstDa
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ml)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ms.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.ms={closeText:"Tutup",prevText:"&#x3C;Sebelum",nextText:"S
elepas&#x3E;",currentText:"hari ini",monthNames:
["Januari","Februari","Mac","April","Mei","Jun","Julai","Ogos","September","Oktober","Nove
["Jan","Feb","Mac","Apr","Mei","Jun","Jul","Ogo","Sep","Okt","Nov","Dis"],dayNames:
["Ahad","Isnin","Selasa","Rabu","Khamis","Jumaat","Sabtu"],dayNamesShort:
["Aha","Isn","Sel","Rab","kha","Jum","Sab"],dayNamesMin:
["Ah","Is","Se","Ra","Kh","Ju","Sa"],weekHeader:"Mg",dateFormat:"dd/mm/
yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ms)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nb.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.nb={closeText:"Lukk",prevText:"&#xAB;Forrige",nextText:"Ne
ste&#xBB;",currentText:"I dag",monthNames:
["januar","februar","mars","april","mai","juni","juli","august","september","oktober","nov
["jan","feb","mar","apr","mai","jun","jul","aug","sep","okt","nov","des"],dayNamesShort:
["søn","man","tir","ons","tor","fre","lør"],dayNames:
["søndag","mandag","tirsdag","onsdag","torsdag","fredag","lørdag"],dayNamesMin:
["sø","ma","ti","on","to","fr","lø"],weekHeader:"Uke",dateFormat:"dd.mm.yy",firstDay:1,isR
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.nb)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nl-BE.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17™ http://jqueryui.com™ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */™jQuery(function(e)
{e.datepicker.regional["nl-
BE"]={closeText:"Sluiten",prevText:"!•",nextText:"!’",currentText:"Vandaag",monthNames:
["januari","februari","maart","april","mei","juni","juli","augustus","september","oktober"
["jan","feb","mrt","apr","mei","jun","jul","aug","sep","okt","nov","dec"],dayNames:
["zondag","maandag","dinsdag","woensdag","donderdag","vrijdag","zaterdag"],dayNamesShort:
["zon","maa","din","woe","don","vri","zat"],dayNamesMin:
["zo","ma","di","wo","do","vr","za"],weekHeader:"Wk",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional["nl-BE"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nl.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.nl={closeText:"Sluiten",prevText:"!•",nextText:"!’",currentTex
t:"Vandaag",monthNames:
["januari","februari","maart","april","mei","juni","juli","augustus","september","oktober"
["jan","feb","mrt","apr","mei","jun","jul","aug","sep","okt","nov","dec"],dayNames:
["zondag","maandag","dinsdag","woensdag","donderdag","vrijdag","zaterdag"],dayNamesShort:
["zon","maa","din","woe","don","vri","zat"],dayNamesMin:
["zo","ma","di","wo","do","vr","za"],weekHeader:"Wk",dateFormat:"dd-mm-
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.nl)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nn.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.nn={closeText:"Lukk",prevText:"&#xAB;Førre",nextText:"Nest
e&#xBB;",currentText:"I dag",monthNames:
["januar","februar","mars","april","mai","juni","juli","august","september","oktober","nov
["jan","feb","mar","apr","mai","jun","jul","aug","sep","okt","nov","des"],dayNamesShort:
["sun","mån","tys","ons","tor","fre","lau"],dayNames:
["sundag","måndag","tysdag","onsdag","torsdag","fredag","laurdag"],dayNamesMin:
["su","må","ty","on","to","fr","la"],weekHeader:"Veke",dateFormat:"dd.mm.yy",firstDay:1,is
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.nn)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-no.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.no={closeText:"Lukk",prevText:"&#xAB;Forrige",nextText:"Ne
ste&#xBB;",currentText:"I dag",monthNames:
["januar","februar","mars","april","mai","juni","juli","august","september","oktober","nov
["jan","feb","mar","apr","mai","jun","jul","aug","sep","okt","nov","des"],dayNamesShort:
["søn","man","tir","ons","tor","fre","lør"],dayNames:
["søndag","mandag","tirsdag","onsdag","torsdag","fredag","lørdag"],dayNamesMin:
["sø","ma","ti","on","to","fr","lø"],weekHeader:"Uke",dateFormat:"dd.mm.yy",firstDay:1,isR
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.no)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pl.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.pl={closeText:"Zamknij",prevText:"&#x3C;Poprzedni",nextTex
t:"Nast — ç’b7ƒ4S²"Æ7W'&VçEFW‡C¢$G¦‘[",monthNames:
["Stycze B"Â$ÇWG’"Â$Ö '¦V2"Â$·v–V6–QD","Maj","Czerwiec","Lipiec","Sierpie B"Â%w'¦W6–QD","P
["Sty","Lu","Mar","Kw","Maj","Cze","Lip","Sie","Wrz","Pa","Lis","Gru"],dayNames:
["Niedziela","Poniedzia &V²"Â%wF÷&V²"Â!Zroda","Czwartek","Pi WFV²"Â%6ö&÷F %ÒÆF ”æ ÖW56†÷'C
["Nie","Pn","Wt"," §""Â$7§r"Â% B"Â%6ò%ÒÆF ”æ ÖW4Ö–ã
["N","Pn","Wt"," §""Â$7¢"Â% B"Â%6ò%ÒÇvVV´†V FW#¢%G–G¢"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ—5
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.pl)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pt-BR.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17 http://jqueryui.com Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e)
{e.datepicker.regional["pt-
BR"]={closeText:"Fechar",prevText:"&#x3C;Anterior",nextText:"Próximo&#x3E;",currentText:"H
["Janeiro","Fevereiro","Março","Abril","Maio","Junho","Julho","Agosto","Setembro","Outubro
["Jan","Fev","Mar","Abr","Mai","Jun","Jul","Ago","Set","Out","Nov","Dez"],dayNames:
["Domingo","Segunda-feira","Terça-feira","Quarta-feira","Quinta-feira","Sexta-
feira","Sábado"],dayNamesShort:
["Dom","Seg","Ter","Qua","Qui","Sex","Sáb"],dayNamesMin:
["Dom","Seg","Ter","Qua","Qui","Sex","Sáb"],weekHeader:"Sm",dateFormat:"dd/mm/
yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional["pt-BR"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pt.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.pt={closeText:"Fechar",prevText:"Anterior",nextText:"Segui
nte",currentText:"Hoje",monthNames:
["Janeiro","Fevereiro","Março","Abril","Maio","Junho","Julho","Agosto","Setembro","Outubro
["Jan","Fev","Mar","Abr","Mai","Jun","Jul","Ago","Set","Out","Nov","Dez"],dayNames:
["Domingo","Segunda-feira","Terça-feira","Quarta-feira","Quinta-feira","Sexta-
feira","Sábado"],dayNamesShort:
["Dom","Seg","Ter","Qua","Qui","Sex","Sáb"],dayNamesMin:
["Dom","Seg","Ter","Qua","Qui","Sex","Sáb"],weekHeader:"Sem",dateFormat:"dd/
mm/yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.pt)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-rm.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17* http://jqueryui.com* Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */jQuery(function(e){e.
datepicker.regional.rm={closeText:"Serrar",prevText:"&#x3C;Suandant",nextText:
"Precedent&#x3E;",currentText:"Actual",monthNames:
["Schaner","Favrer","Mars","Avrigl","Matg","Zercladur","Fanadur","Avust","Settember","Octo
["Scha","Fev","Mar","Avr","Matg","Zer","Fan","Avu","Sett","Oct","Nov","Dec"],dayNames:
["Dumengia","Glindesdi","Mardi","Mesemna","Gievgia","Venderdi","Sonda"],dayNamesShort:
["Dum","Gli","Mar","Mes","Gie","Ven","Som"],dayNamesMin:
["Du","Gl","Ma","Me","Gi","Ve","So"],weekHeader:"emna",dateFormat:"dd/mm/
yy",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.rm)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ro.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional.ro={closeText:"Închide",prevText:"&#xAB; Luna
precedent 2"ÆæW‡EFW‡C¢$ÇVæ  W&Ñ toare &#xBB;",currentText:"Azi",monthNames:["Ianu
arie","Februarie","Martie","Aprilie","Mai","Iunie","Iulie","August","Septembri
e","Octombrie","Noiembrie","Decembrie"],monthNamesShort:
["Ian","Feb","Mar","Apr","Mai","Iun","Iul","Aug","Sep","Oct","Nov","Dec"],dayNames:
["Duminic 2"Â$ÇVæ’"Â$Ö !ci","Miercuri","Joi","Vineri","Sâmb 7A "],dayNamesShort:
["Dum","Lun","Mar","Mie","Joi","Vin","Sâm"],dayNamesMin:
["Du","Lu","Ma","Mi","Jo","Vi","Sâ"],weekHeader:"S 7 B"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ—
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ro)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ru.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.ru={closeText:"At0C¤@D´BDÂ"Ç &WeFW‡C¢"b7ƒ43´ D 5CB"ÆæW‡EFW‡C¢$!C´5CBb7
ntText:"B 5C4>CD=Dò"ÆÖöçF„æ ÖW3¥²$/CÔ2C @DÂ"Â$$CT2D 0C´L","AÄ0D B","A ?D 5C´L","AÄ0C’"Â$ D
["Bô=C""Â$$CT2","AÄ0D "Â$ Cô@","AÄ0C’"Â$ Dä=","A„NC²"Â$ C$3","B 5CÒ"Â$ C¤B","AÔ>Dò"Â$ CT:"
["C$>D :D 5D 5CÔLCR"Â$?Cä=CT4CT;DÄ=C„:","C$BCä@CÔ8C¢"Â$AD 5CD0","Dt5D$2CT@C2"Â$?DôBCÔ8Dd0"
["A$A","Aô=","A$B","B @","BtB","AôB","B 1"],weekHeader:"AÔ5CB"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ru)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sk.min.js

/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.sk={closeText:"Zavrie R"Ç &WeFW‡C¢"b7ƒ43µ &VF6Ž G¦ ¯¦6’"ÆæW€
tText:"Nasledujúci>",currentText:"Dnes",monthNames:
["január","február","marec","apríl","máj","jún","júl","august","september","október","nove
["Jan","Feb","Mar","Apr","Máj","Jún","Júl","Aug","Sep","Okt","Nov","Dec"],dayNames:
["nede æ "Â' öæFVÆö²"Â'WF÷&ö²"Â'7G&VF "Â)§Gg'Fö²"Â' – Fö²"Â'6ö&÷F %ÒÆF ”æ ÖW56†÷'C
["Ned","Pon","Uto","Str","Štv","Pia","Sob"],dayNamesMin:
["Ne","Po","Ut","St","Št","Pia","So"],weekHeader:"Ty",dateFormat:"dd.mm.yy",firstDay:1,isR
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.sk)});

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sl.min.js

/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.sl={closeText:"Zapri",prevText:"<Prejšnji",nextText:"
Naslednji>",currentText:"Trenutni",monthNames:
["Januar","Februar","Marec","April","Maj","Junij","Julij","Avgust","September","Oktober","
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","Avg","Sep","Okt","Nov","Dec"],dayNames:
["Nedelja","Ponedeljek","Torek","Sreda"," ÆWG'FV²"Â% WFV²"Â%6ö&÷F %ÒÆF ”æ ÖW56†÷'C
["Ned","Pon","Tor","Sre"," ÆWB"Â% WB"Â%6ö"%ÒÆF ”æ ÖW4Ö–ã
["Ne","Po","To","Sr"," ÆR"Â% R"Â%6ò%ÒÇvVV´†V FW#¢%FVFVâ"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.sl)});

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sq.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.sq={closeText:"mbylle",prevText:"&#x3C;mbrapa",nextText:"P
ërpara&#x3E;",currentText:"sot",monthNames:
["Janar","Shkurt","Mars","Prill","Maj","Qershor","Korrik","Gusht","Shtator","Tetor","Nënto
["Jan","Shk","Mar","Pri","Maj","Qer","Kor","Gus","Sht","Tet","Nën","Dhj"],dayNames:
["E Diel","E Hënë","E Martë","E Mërkurë","E Enjte","E Premte","E
Shtune"],dayNamesShort:["Di","Hë","Ma","Më","En","Pr","Sh"],dayNamesMin:
["Di","Hë","Ma","Më","En","Pr","Sh"],weekHeader:"Ja",dateFormat:"dd.mm.yy",firstDay:1,isRT
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.sq)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sr-SR.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional["sr-
SR"]={closeText:"Zatvori",prevText:"&#x3C;",nextText:"&#x3E;",currentText:"Danas",monthNam
["Januar","Februar","Mart","April","Maj","Jun","Jul","Avgust","Septembar","Oktobar","Novem
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","Avg","Sep","Okt","Nov","Dec"],dayNames:
["Nedelja","Ponedeljak","Utorak","Sreda"," ÆWGg'F ²"Â% WF ²"Â%7V&÷F %ÒÆF ”æ ÖW56†÷'C
["Ned","Pon","Uto","Sre"," ÆWB"Â% WB"Â%7V"%ÒÆF ”æ ÖW4Ö–ã
["Ne","Po","Ut","Sr"," ÆR"Â% R"Â%7R%ÒÇvVV´†V FW#¢%6VB"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7DF “£ Æ—5
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional["sr-SR"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sr.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.sr={closeText:"At0D$2Cä@C,"Ç &WeFW‡C¢"b7ƒ43²"ÆæW‡EFW‡C¢"b7ƒ4S²"Æ7W'&P
ntText:"AD0CÔ0D "ÆÖöçF„æ ÖW3¥²$ C =D40D "Â$$CT1D CC @","AÄ0D B","A ?D 8C²"Â$ C X","@„CCÒ"Â
["@„0CÒ"Â$$CT1","AÄ0D "Â$ Cô@","AÄ0E,"Â$ D4=","@„CC²"Â$ C$3","B 5Cò"Â$ C¤B","AÔ>C""Â$ CTF"
["AÔ5CD5E”0","Aô>CÔ5CD5E”0C¢"Â$#D$>D 0C¢"Â$!D 5CD0","Bt5D$2D BC :","Aô5D$0C¢"Â$!D41CäBC %Ò
["AÔ5","Aô>","B4B","B @","Bt5","Aô5","B C"],weekHeader:"B 5CB"ÆF FTf÷&Ö C¢&FBæÖÒç—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.sr)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sv.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.sv={closeText:"Stäng",prevText:"&#xAB;Förra",nextText:"Näs
ta&#xBB;",currentText:"Idag",monthNames:
["Januari","Februari","Mars","April","Maj","Juni","Juli","Augusti","September","Oktober","
["Jan","Feb","Mar","Apr","Maj","Jun","Jul","Aug","Sep","Okt","Nov","Dec"],dayNamesShort:
["Sön","Mån","Tis","Ons","Tor","Fre","Lör"],dayNames:
["Söndag","Måndag","Tisdag","Onsdag","Torsdag","Fredag","Lördag"],dayNamesMin:
["Sö","Må","Ti","On","To","Fr","Lö"],weekHeader:"Ve",dateFormat:"yy-mm-
dd",firstDay:1,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.sv)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ta.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.ta={closeText:"ºëÂ¹ûÁ",prevText:"ºëÁº›Íº›Èºû¤¼ "ÆæW‡EFW‡C¢+…¹ûÁºKÍºK¤¼
nthNames:["ºKÈ","º ë¾¹«¿","º«™¼Û•¼ ©»ò"Â+š»û¤¼Û¤»û°¼,"Â+µ¼‹•»ëš»ò"Â+†º›¿","¸kŸ»ò"Â+†»[£»ò"Â
["ºKÈ","º ë¾¹«¿","º«™¼Ò"Â+š»û¤¼Ò"Â+µ¼‹•»â"Â+†º›¿","¸kŸ»ò"Â+†»R"Â+ª¼ º","¹ ª¼Ò"Â+•»ë°¼Ò"Â+®»
["¹ë¾ºû¿» Í» Á¹[Í¹[¿»K®¼,"Â+¤»û™¼Û•¹ûÍ¹[¿»K®¼,"Â+š¼kµ¼Ûµ»ë¯¼Û•¼Û•»û´ºëÈ","º«ÁºK©¼Û•»û´ºëÈ"
["¹ë¾","ºK¿","¹«Æ","º«Á",»[¿",»[Æ","¹¢%ÒÇvVV´†V FW#¢$ CR"ÆF FTf÷&Ö C¢&FBöÖÒ÷—'"Æf—'7DF “
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.ta)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-th.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.th={closeText:"á¾4áB"Ç &WeFW‡C¢"b7„ #²b7„  ¾"äž-á’"ÆæW‡EFW‡C¢. ã  äN &
#xBB;",currentText:"â~1áž ã^I",monthNames:
["â  â>2àN!","à 8â  ã. ã  áŽL","â 5áž2àN!","ä !âž2â. ","áî$âž ã. â "Â.!ãN ãŽ ã."á’"Â. â> à
["â î .","à î .","â 5.àBâ"Â.@â î".","ááî .","â 4.â"â"Â. .àBâ"Â.*.àBâ"Â. .â"â"Â. .àBâ"Â. .â
["âÞ2á~4á^"äÂ"Â. ã  á~#äÂ"Â.-ã  àN2â2"Â. ãŽ ","áî$â¾1â® áN5","âŽ8à #äÂ"Â.@â®2â>L"],dayName
["âÞ2.","à,â"Â.-.","ááâ"Â. âBâ"Â.(.","â¢â%ÒÆF ”æ ÖW4Ö–ã
["âÞ2.","à,â"Â.-.","ááâ"Â. âBâ"Â.(.","â¢â%ÒÇvVV´†V FW#¢%v²"ÆF FTf÷&Ö C¢&FBöÖÒð
yy",firstDay:0,isRTL:!1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.th)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-tj.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞQuery(function(e){e.
datepicker.regional.tj={closeText:"A„4Cä<C "Ç &WeFW‡C¢"b7ƒ63´šC DCâ"ÆæW‡EFW‡C¢$ CTH&#x3e;"
ntText:"A„<D ïCr"ÆÖöçF„æ ÖW3¥²$/CÔ2C @","BD5C$@C ;","AÄ0D B","A ?D 5C²"Â$ C 9","A„NCÒ"Â$ D
["Bô=C""Â$$CT2","AÄ0D "Â$ Cô@","AÄ0C’"Â$ Dä=","A„NC²"Â$ C$3","B 5CÒ"Â$ C¤B","AÔ>Dò"Â$ CT:"
["Dô:D„0CÔ1CR"Â$4D4HC =C 5","D 5D„0CÔ1CR"Â$GCä@D„0CÔ1CR"Â$?C =KtHC =C 5","KtCCÄJC "Â$HC =C
["Bô:","ADH","B H","BtH","AôH","Kd<","B„="],weekHeader:"BTD",dateFormat:"dd.mm.yy",firstDa
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.tj)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-tr.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.tr={closeText:"kapat",prevText:"&#x3C;geri",nextText:"iler
i&#x3e",currentText:"bugün",monthNames:
["Ocak"," çV& B"Â$Ö 'B"Â$æ–6 â"Â$Ö ‘1s","Haziran","Temmuz","A ÷W7F÷2"Â$W–ÏÆÂ"Â$V¶–Ò"Â$¶ 11
["Oca"," çV""Â$Ö ""Â$æ–2"Â$Ö ’"Â$† ¢"Â%FVÒ"Â$  u","Eyl","Eki","Kas","Ara"],dayNames:
["Pazar","Pazartesi","Sal  "Â,v !_amba","Per öVÖ&R"Â$7VÖ "Â$7VÖ 'FW6’%ÒÆF ”æ ÖW56†÷'C
["Pz","Pt","Sa","Ça","Pe","Cu","Ct"],dayNamesMin:
["Pz","Pt","Sa","Ça","Pe","Cu","Ct"],weekHeader:"Hf",dateFormat:"dd.mm.yy",firstDay:1,isRT
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.tr)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-uk.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.
datepicker.regional.uk={closeText:"At0C¤@C„BC,"Ç &WeFW‡C¢"b7ƒ43²"ÆæW‡EFW‡C¢"b7ƒ4S²"Æ7W'&P
ntText:"B LCä3Cä4CÔV",monthNames:["B VDt5CÔL","A´ND$8C’"Â$ CT@CT7CT=DÂ"Â$ C$VD$5CÔL","B$@C
["B VDr"Â$ DäB","A 5D "Â$ C$V","B$@C "Â$'CT@","A´8Cò"Â$!CT@","A$5D "Â$ Cä2","A´8D "Â$ D C"
["CÔ5CDVC´O","Cô>CÔ5CDVC´>C¢"Â$2Ed2D$>D >C¢"Â$ACT@CT4C "Â$GCTBC$5D "Â$?’DôBCÔ8DdO","D CC >
["AÔ4","Aô=","A$B","B @","BtB","AôB","B 1"],weekHeader:"B$8Cb"ÆF FTf÷&Ö C¢&FBöÖÒ÷—’"Æf—'7D
1,showMonthAfterYear:!
1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.uk)});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-vi.min.js

/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014 jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e){e.datepicker.regional.vi={closeText:" 6ær"Ç &WeFW‡C¢"b7ƒ43µG!° Ûc",nextText:"Ti ¿p>",currentText:"Hôm nay",monthNames:["Tháng M Ùt","Tháng Hai","Tháng Ba","Tháng T "Â%FŽ ær á m","Tháng Sáu","Tháng B £y","Tháng Tám","Tháng Chín","Tháng M íÖ’"Â%FŽ ær Ñ° Ýi M Ùt","Tháng M íÖ’ † ’%ÒÆÖöçF„æ ÖW56†÷'C¥²%FŽ ær 1","Tháng 2","Tháng 3","Tháng 4","Tháng 5","Tháng 6","Tháng 7","Tháng 8","Tháng 9","Tháng 10","Tháng 11","Tháng 12"],dayNames:["Ch ç Nh -t","Th é Hai","Th é Ba","Th é T "Â%F•î’ á m","Th é Sáu","Th é B £y"],dayNamesShort:["CN","T2","T3","T4","T5","T6","T7"],dayNamesMin:["CN","T2","T3","T4","T5","T6","T7"],weekHeader:"Tu",dateFormat:"dd/mm/yy",firstDay:0,isRTL:!1,showMonthAfterYear:!1,yearSuffix:""},e.datepicker.setDefaults(e.datepicker.regional.vi)});

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-CN.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional["zh-CN"]={closeText:"Qs•í",prevText:"&#x3C;N g ",nextText:"N g
&#x3E;",currentText:"NÊY)",monthNames:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Q
g "],monthNamesShort:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Qkg ","N]g ","SAg
N ","f g VÛ","f g N”","f g Qm"],dayNamesShort:["Theå","ThN ","ThNŒ","ThN ","ThVÛ","ThN”","
["eå","N ","NŒ","N ","VÛ","N”","Qm"],weekHeader:"Th",dateFormat:"yy-mm-dd",firstDay:1,isRT
1,showMonthAfterYear:!
0,yearSuffix:"^t"},e.datepicker.setDefaults(e.datepicker.regional["zh-CN"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-HK.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional["zh-HK"]={closeText:"•Ü•‰",prevText:"&#x3C;N g ",nextText:"N g
&#x3E;",currentText:"NÊY)",monthNames:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Q
g "],monthNamesShort:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Qkg ","N]g ","SAg
N ","f g VÛ","f g N”","f g Qm"],dayNamesShort:["Theå","ThN ","ThNŒ","ThN ","ThVÛ","ThN”","
["eå","N ","NŒ","N ","VÛ","N”","Qm"],weekHeader:"Th",dateFormat:"dd-mm-yy",firstDay:0,isRT
1,showMonthAfterYear:!
0,yearSuffix:"^t"},e.datepicker.setDefaults(e.datepicker.regional["zh-HK"])});
```

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-TW.min.js

```
/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Copyright 2014
jQuery Foundation and other contributors; Licensed MIT */ÞjQuery(function(e)
{e.datepicker.regional["zh-TW"]={closeText:"•Ü•‰",prevText:"&#x3C;N g ",nextText:"N g
&#x3E;",currentText:"NÊY)",monthNames:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Q
g "],monthNamesShort:["N g ","NŒg ","N g ","VÛg ","N”g ","Qmg ","N g ","Qkg ","N]g ","SAg
N ","f g VÛ","f g N”","f g Qm"],dayNamesShort:["Theå","ThN ","ThNŒ","ThN ","ThVÛ","ThN”","
["eå","N ","NŒ","N ","VÛ","N”","Qm"],weekHeader:"Th",dateFormat:"yy/mm/dd",firstDay:1,isRT
1,showMonthAfterYear:!
0,yearSuffix:"^t"},e.datepicker.setDefaults(e.datepicker.regional["zh-TW"])});
```

public\assets\js\plugins\jquery-ui\jquery-ui.js

/*! jQuery UI - v1.10.4 - 2014-01-17Ð http://jqueryui.comÐ Includes: jquery.ui.core.js, jquery.ui.widget.js, jquery.ui.mouse.js, jquery.ui.draggable.js, jquery.ui.droppable.js, jquery.ui.resizable.js, jquery.ui.selectable.js, jquery.ui.sortable.js, jquery.ui.effect.js, jquery.ui.accordion.js, jquery.ui.autocomplete.js, jquery.ui.button.js, jquery.ui.datepicker.js, jquery.ui.dialog.js, jquery.ui.effect-blind.js, jquery.ui.effect-bounce.js, jquery.ui.effect-clip.js, jquery.ui.effect-drop.js, jquery.ui.effect-explode.js, jquery.ui.effect-fade.js, jquery.ui.effect-fold.js, jquery.ui.effect-highlight.js, jquery.ui.effect-pulsate.js, jquery.ui.effect-scale.js, jquery.ui.effect-shake.js, jquery.ui.effect-slide.js, jquery.ui.effect-transfer.js, jquery.ui.menu.js, jquery.ui.position.js, jquery.ui.progressbar.js, jquery.ui.slider.js, jquery.ui.spinner.js, jquery.ui.tabs.js, jquery.ui.tooltip.jsÐ Copyright 2014 jQuery Foundation and other contributors; Licensed MIT */Ðfunction($, undefined) {Ðar uuid = 0,Ð'Væ— VT–B Ò õçV'Ö–BÕÆB²BóØ/ $.ui might exist from components with no dependencies, e.g., $.ui.positionÐ$.ui = $.ui || {};Ð $.extend($.ui, {ÐfW'6–öã¢ # ã ãB"Ð¶W"6öFS¢ ™BACKSPACE: 8,ÐOMMA: 188,ÐELETE: 46,ÐDOWN: 40,ÐND: 35,ÐNTER: 13,ÐSCAPE: 27,ÐHOME: 36,ÐEFT: 37,ÐNUMPAD_ADD: 107,Ð NUMPAD_DECIMAL: 110,ÐNUMPAD_DIVIDE: 111,ÐNUMPAD_ENTER: 108,ÐNUMPAD_MULTIPLY: 106,Ð NUMPAD_SUBTRACT: 109,ÐPAGE_DOWN: 34,ÐAGE_UP: 33,ÐERIOD: 190,ÐIGHT: 39,ÐPACE: 32,ÐTAB: 9,ÐP: 38});Ð/ pluginsÐ$.fn.extend({Ðfö7W3¢ †gVæ7F–öâ, ÷&–r ' ½return function(delay, fn) {Ð—&WGW&â G— Vöb FVÆ ' ÓÓÒ &çVÖ&W""™ythis.each(function() {Ð—f " VÆVÒ Ò F†—3½6WEF–ÖV÷WB†gVæ7F–öâ,' ½$(elem).focus(),Ðf (fn) {Ð fn.call(elem);Ð }ÐÂ FVÆ ' ½)ÐrÐrig.apply(this, arguments);Ð}};Ð• ($.fn.focus),Ð67&öÆÅ &VçC¢ gVæ7F–öâ,' ½var scrollParent,Ðf (($.ui.ie && (/(static|relative)/).test(this.css("position"))) || (/absolute/).test(this.css("position"))) {Ð—67&öÆÅ &VçB Ò this.parents().filter(function() {Ðreturn (/(relative|absolute|fixed)/).test($.css(this,"position")) && (/(auto|scroll)/).test($.css(this,"overflow")+$.css(this,"overflow-y")+$.css(this,"overflow-x"));Ð—Ò'æW ƒ ½ else {Ð67&öÆÅ &VçB Ò this.parents().filter(function() {Ðreturn (/(auto|scroll)/).test($.css(this,"overflow")+$.css(this,"overflow-y")+$.css(this,"overflow-x"));Ð—Ò'æW ƒ ½ÐÐreturn (/fixed/).test(this.css("position")) || !scrollParent.length ? $(document) : scrollParent;ÐÒÐ¤–æFWƒ¢ gVæ7F–öâ, ¤–æFW, ' ½if (zIndex !== undefined) {Ð return this.css("zIndex", zIndex);ÐÐÐf (this.length) {Ðf " VÆVÒ Ò $(this[0]), position, value;Ð—v†–ÆR , VÆVÒæÆVæwF, bb VÆVÕ² Ò ÓÒ document) {Ð// Ignore z-index if position is set to a value where z-index is ignored by the browserÐ// This makes behavior of this function consistent across browsersÐ// WebKit always returns auto if the element is positionedÐ position = elem.css("position");Ðif (position === "absolute" || position === "relative" || position === "fixed") {Ð'òò "R &WGW&ç2 v†Vâ ¤–æFW, —2 æ÷B specifiedÐ'òò ÷F†W" '&÷w6W'2 &WGW&â 7G&–æ}òò vR –væ÷&R F†R 6 6R öb æW7FVB elements with an explicit value of 0Ð'òò ÆF—b 7G–ÆSÒ'¢Ö–æFWƒ¢ Ó ²#ãÆF—b style="z-index: 0;"> Ð—f ÇVR Ò '6T–çB, VÆVÒæ772, '¤–æFW," 'Â ½ if (!isNaN(value) && value !== 0) {Ðreturn value;ÐÐelem = elem.parent();ÐÐ return 0;ÐÒÐVæ— VT–C¢ gVæ7F–öâ,' ½return this.each(function() {Ð–b , F†—2æ–B ' {Ðthis.id = "ui-id-" + (++uuid);Ð});ÐÐ&VÖ÷fUVæ— VT–C¢ gVæ7F–öâ,' ½return this.each(function() {Ð––b , 'Væ— VT–BçFW7B, F†—2æ–B ' '½ $(this).removeAttr("id");Ð});Ð});Ð/ selectorsÐunction focusable(element, isTabIndexNotNaN) {Ðf " Ö Â Ö æ ÖRÂ –ÖrÐnodeName = element.nodeName.toLowerCase();Ð–b , & &V " ÓÓÒ æöFTæ ÖR ' ½map = element.parentNode;Ðmap.name,Ðf (!element.href || !mapName || map.nodeName.toLowerCase() !== "map") {Ð—&WGW&â f Ç6S½Ðmg = $("img[usemap=#" + mapName + "]")[0];Ðreturn !!img && visible(img);Ð&WGW&â , ö–ç WGÇ6VÆV7GÀ textarea|button|object/.test(nodeName) ?Ð!element.disabled :Ða" === nodeName ?Ð–VÆVÖVçBæ‡&Vb ÇÂ —5F $–æFW„æ÷Dæ â™––5F $–æFW„æ÷Dæ â' Ð/ the element and all of its ancestors must be visibleÐ

™visible(element)}Ðfunction
visible(element) {Ð&WGW&â BæW‡ "æf–ÇFW'2çf—6–&ÆR, VÆVÖVçB ’ bm!
$(element).parents().addBack().filter(function() {™—&WGW&â Bæ772, F†—2Â
"visibility") === "hidden";™}).length}Ð$.extend($.expr[":"], {ÐF F ¢
$.expr.createPseudo ?™$.expr.createPseudo(function(dataName) {™Ð&WGW&â
function(elem) {™return !!$.data(elem, dataName);™½) ™Ð/ support: jQuery
<1.8™function(elem, i, match) {™Ð&WGW&â BæF F , VÆVÒÂ Ö F6…² 2 Ò ™½ÐÐ
focusable: function(element) {™return focusable(element, !
isNaN($.attr(element, "tabindex")));ÐÒÉF && &ÆS¢ gVæ7F–öâ, VÆVÖVçB ’ ™½var
tabIndex = $.attr(element, "tabindex");™——5F $–æFW„æ â Ò —4æ â, F $–æFW, ™½
return (isTabIndexNaN || tabIndex >= 0) && focusable(element, !
isTabIndexNaN);Ð});Ð/ support: jQuery <1.8™if (!
$("<a>").outerWidth(1).jquery) {™BæV 6,, ² %v–GF,"Â $†V–v‡B" ÒÂ
function(i, name) {™var side = name === "Width" ? ["Left", "Right"] :
["Top", "Bottom"];™—G— R Ò æ ÖRçFôÆ÷vW$6 6R,™Í÷&–r Ò™½innerWidth:
$.fn.innerWidth,™™innerHeight: $.fn.innerHeight,™™™ÐouterWidth: $.fn.outerWidth,™™Ð
outerHeight: $.fn.outerHeight™—™½function reduce(elem, size, border, margin) {™Ð
$.each(side, function() {™size -= parseFloat($.css(elem, "padding" +
this)) || 0;™if (border) {™™™Ð6—¦R ÓÒ '6TfÆö B, Bæ772, VÆVÒÂ &&÷&FW"" ² F†—2
+ "Width")) || 0;™™™™™if (margin) {™™™Ð6—¦R ÓÒ '6TfÆö B, Bæ772, VÆVÒÂ &Ö &v–â"
+ this)) || 0;™}™™™½&WGW&â 6—¦S™™™$.fn["inner" + name] = function(size) {™Ð
if (size === undefined) {™™return orig["inner" + name].call(this);™™™™&WGW&â
this.each(function() {™$(this).css(type, reduce(this, size) + "px");™™™½™™Ð
$.fn["outer" + name] = function(size, margin) {™--b , G— Vöb 6—¦R ÓÒ
"number") {™return orig["outer" + name].call(this, size);™™™™&WGW&â
this.each(function() {™$(this).css(type, reduce(this, size, true, margin)
+ "px");™—Ò™½÷Ò“™½™Ð/ support: jQuery <1.8™if (!$.fn.addBack) {™BæfâæFD& 6² Ò
function(selector) {™return this.add(selector == null ?™ÐF†—2ç &Wdö&¦V7B ¢
this.prevObject.filter(selector);™);™Ó™½™Ð/ support: jQuery 1.6.1, 1.6.2
(http://bugs.jquery.com/ticket/9413)™if ($("<a>").data("a-b",
"a").removeData("a-b").data("a-b")) {™BæfâÇ&VÖ÷fTF F Ò
(function(removeData) {™return function(key) {™–b , &wVÖVçG2æÆVæwF, ’™™½
return removeData.call(this, $.camelCase(key));™—Ò VÇ6R™™™return
removeData.call(this);™—™Ý÷™Ð’, BæfâÇ&VÖ÷fTF F “™½™Ð/ deprecated™$.ui.ie = !!/
msie [\w.]+/.exec(navigator.userAgent.toLowerCase());™$.support.selectstart
= "onselectstart" in document.createElement("div");™$.fn.extend({™Ð
disableSelection: function() {™return this.bind(($.support.selectstart ?
"selectstart" : "mousedown") +™’"çV’ÖF—6 &ÆU6VÆV7F–öâ"Â gVæ7F–öâ, WfVçB ’™™½
event.preventDefault();™—Ò“™™™™Ðæ &ÆU6VÆV7F–öã¢ gVæ7F–öâ,’ ™½return
this.unbind(".ui-disableSelection");™™™™™

™} catch(e) {}Ðö6ÆV äF F , VÆV×2 “½;Ð.widget = function(name, base, prototype) {Ðf " gVÆÄæ ÖRÂ W†—7F–æt6öç7G'V7F÷"Â 6öç7G'V7F÷"Â basePrototype,Ð// proxiedPrototype allows the provided prototype to remain unmodifiedÐ// so that it can be used as a mixin for multiple widgets (#8876)Ð proxiedPrototype = {},Ðnamespace = name.split(".")[0];ÐÐ ÖR Ò name.split(".")[1];ÐgVÆÄæ ÖR Ò æ ÖW7 6R ² "Ò" ² æ ÖSÐ–b , &÷F÷G— R ’ ½ prototype = base;Ðbase = $.Widget;ÐÓòò 7&V FR 6VÆV7F÷" f÷" ÇVv–1BæW‡ %² #¢" Ð [fullName.toLowerCase()] = function(elem) {Ðreturn !!$.data(elem, fullName);ÐÓÐE² æ ÖW7 6R Ò Ò E² æ ÖW7 6R Ò ÇÂ ·Ó½W†—7F–æt6öç7G'V7F÷" Ò $[namespace][name];Ð6öç7G'V7F÷" Ò E² æ ÖW7 6R Õ² æ ÖR Ò Ò function(options, element) {Ð// allow instantiation without "new" keywordÐif (!this._createWidget) {Ð—&WGW&â æWr 6öç7G'V7F÷", ÷ F–öç2Â VÆVÖVçB ™ÐÐ// allow instantiation without initializing for simple inheritanceÐ// must use "new" keyword (the code above always passes args)Ðif (arguments.length) {Ð this._createWidget(options, element);Ð}Ó½òò W‡FVæB v—F, F†R W†—7F–ær constructor to carry over any static propertiesÐBæW‡FVæB, 6öç7G'V7F÷"Â existingConstructor, {Ðversion: prototype.version,Ð// copy the object used to create the prototype in case we need toÐ// redefine the widget lateraÐproto: $.extend({}, prototype),Ð// track widgets that inherit from this widget in case this widget isÐ// redefined after a widget inherits from itÐ _childConstructors: []ÐÒ“Ð& 6U &÷F÷G— R Ò æWr & 6R,“½òò vR æVVB Fò Ö ¶R F†R options hash a property directly on the new instanceÐòò ÷F†W'v—6R vRvÆÂ ÖöF–g’ the options hash on the prototype that we'reÐòò –æ†W&—F–ær g&öÝ basePrototype.options = $.widget.extend({}, basePrototype.options);Ð $.each(prototype, function(prop, value) {Ðif (!$.isFunction(value)) {Ð proxiedPrototype[prop] = value;Ð—&WGW&â½ÐproxiedPrototype[prop] = (function() {Ð—f " ÷7W W" Ò gVæ7F–öâ,’™½—&WGW&â base.prototype[prop].apply(this, arguments);Ð™™™},Ðsuper Apply = function(args) {Ð™—&WGW&â & 6Rç &÷F÷G— U² &÷ Òæ Ç’, F†—2Â &w2™™™½÷ÐWGW&â function() {Ð™var __super = this._super,Ðõ÷7W W$ Ç’ Ò F†—2å÷7W W$ Ç’í returnValue;Ð™this._super = _super,Ðthis._superApply = _superApply;Ð™Ðeturn value = value.apply(this, arguments);Ð™this._super = __super,Ðthis._superApply = __superApply;Ð™return returnValue;Ð½)();Ð“½6öç7G'V7F÷"ç &÷F÷G— R Ò $.widget.extend(basePrototype, {Ð// TODO: remove support for widgetEventPrefixÐ ™// always use the name + a colon as the prefix, e.g., draggable:startÐ// don't prefix for widgets that aren't DOM-basedÐwidgetEventPrefix: existingConstructor ? (basePrototype.widgetEventPrefix || name) : nameÐÒÂ proxiedPrototype, {Ðconstructor: constructor,Ðnamespace: namespace,Ðwidget Name: name,Ðwidget FullName: fullNameÐ“½òò –b F†—2 v–FvWB —2 &V–ær &VFVf–æVB F†Vâ vR need to find all widgets thatÐòò &R –æ†W&—F–ær g&öÒ —B æB &VFVf–æR ÆÂ öb them so that they inherit fromÐòò F†R æWr fW'6–öâ öb F†—2 v–FvWBâ vRw&R essentially trying to replace oneÐòò ÆWfVÂ –â F†R &÷F÷G— R 6† –âí–b (existingConstructor) {Ð$.each(existingConstructor._childConstructors, function(i, child) {Ð—f " 6†–ÆE &÷F÷G— R Ò 6†–ÆBç &÷F÷G— Ð½òò &VFVf–æR F†R child widget using the same prototype that wasÐ’òò ÷&–v–æ ÆÇ’ W6VBÂ 'WB –æ†W&—B from the new version of the baseÐ’Bçv–FvWB, 6†–ÆE &÷F÷G— Rææ ÖW7 6R ² "â" ² childPrototype.widgetName, constructor, child._proto);Ð});Ð// remove the list of existing child constructors from the old constructorÐ// so the old child constructors can be garbage collectedÐdelete existingConstructor._childConstructors;ÐÒ VÇ6R ™ ½ base._childConstructors.push(constructor);ÐÐBçv–FvWBæ'&–FvR, æ ÖRÂ constructor);Ð};Ð$.widget.extend = function(target) {Ðf " –ç WB Ò slice.call(arguments, 1),ÐinputIndex = 0,ÐinputLength = input.length,Ðkey,Ð value;Ðf÷" , ² –ç WD–æFW, Â –ç WDÆVæwFƒ² –ç WD–æFW,²² ’ ½for (key in input[inputIndex]) {Ð—f ÇVR Ò –ç WE² –ç WD–æFW, Õ² ¶W’ Ò½–b (input[inputIndex].hasOwnProperty(key) && value !== undefined) {Ð™// Clone objectsÐ™if ($.isPlainObject(value))™™™ÐF &vWE² ¶W’ Ò Ò $.isPlainObject(target[key]) ?Ð™™™$.widget.extend({}, target[key], value) :Ð™™™// Don't extend strings, arrays, etc. with objectsÐ $.widget.extend({}, value);Ð

™™// Copy everything else by reference™™Ð else™™Ð
target[key] = value;™™Ð }™™Ð&WGW&â F &vWC½;™™Ð.widget.bridge = function(name,
object) {™™Ðif " gVÆÄæ ÖR Ò ö&¦V7Bç &÷F÷G— Rçv–FvWDgVÆÄæ ÖR ÇÂ æ ÖS½Bæfå² æ ÖR Ò
= function(options) {™™Ðvar isMethodCall = typeof options === "string";™™Ð &w2 Ò
slice.call(arguments, 1);™™Ð—&WGW&åf ÇVR Ò F†—™™Ð½// allow multiple hashes to be
passed on init™™Ðoptions = !isMethodCall && args.length ?™™Ð
$.widget.extend.apply(null, [options].concat(args)) :™™Ð÷ F–öç™™Ð½f
(isMethodCall) {™™Ð—F†—2æV 6,†gVæ7F–öâ,'™™Ð½var methodValue;™™Ð–ç7F æ6R Ò
$.data(this, fullName);™™Ðif (!instance)™™Ð{™™Ð&WGW&â BæW'&÷", &6 ææ÷B 6 ÆÂ
methods on " + name + " prior to initialization; " +™™Ð"attempted to call method
'" + options + "'");™™Ð}™™Ðif (!$.isFunction(instance[options]) ||
options.charAt(0) === "_") {™™Ð—&WGW&â BæW'&÷", &æò 7V6, ÖWF†öB r" ² ÷ F–öç2 ²
"' for " + name + " widget instance");™™Ð™™Ðmethod Value =
instance[options].apply(instance, args);™™Ðif (methodValue !== instance &&
methodValue !== undefined) {™™Ð—&WGW&åf ÇVR Ò ÖWF†öEf ÇVR bb ÖWF†öEf ÇVRæ§ VW'™™Ð™
returnValue.pushStack(methodValue.get()) :™™Ð™™Ðmethod Value;™™Ð&WGW&â f ÇÖS½™™Ð½
else {™™Ð—F†—2æV 6,†gVæ7F–öâ,'™™Ð½var instance = $.data(this, fullName);™™Ðif
(instance) {™™Ð--ç7F æ6Ræ÷ F–öâ, ÷ F–öç2 ÇÂ ·Ò 'åö–æ—B,™™Ð½ else™™Ð™™ÐBæF F , F†—2Â
fullName, new object(options, this));™™Ð}™™Ð™™Ðreturn returnValue;™™Ð½;™™Ð.Widget
= function(/* options, element */) {};™™Ð.Widget._childConstructors = [];™™Ð
$.Widget.prototype = {™™Ðv–FvWDæ ÖS¢ 'v–FvWB"Ív–FvWDWfVçE &Vf—ƒ¢ ""Í™™Ð
defaultElement: " ",™™Ð÷ F–öç3¢ ½disabled: false™™Ð™™Ð// callbacks™™Ðcreate: nullÒÍ™™Ð
_createWidget: function(options, element) {™™Ðelement = $(element ||
this.defaultElement || this)[0];™™Ðthis.element = $(element);™™Ðthis.uuid =
uuid++;™™Ðthis.eventNamespace = "." + this.widgetName + this.uuid;™™Ðthis.options =
$.widget.extend({},™™Ð—F†—2æ÷ F–öç™™ÍF†—2åövWD7&V FT÷ F–öç2,™™Í÷ F–öç2 ™™Ð½
this.bindings = $();™™Ðthis.hoverable = $();™™Ðthis.focusable = $();™™Ð™™Ðif (element !
== this) {™™Ð'BæF F , VÆVÖVçBÂ F†—2çv–FvWDgVÆÄæ ÖRÂ F†—2 ™™½F†—2åööâ, G'VRÂ
this.element, {™™Ðremove: function(event)™™Ð{™™Ð–b , WfVçBçF &vWB ÓÓÒ VÆVÖVçB ™™½
this.destroy();™™Ð™™Ð™™Ð™™½F†—2æFö7VÖVçB Ò B, VÆVÖVçBç7G–ÆR™™Ð// element within the
document™™Ðelement.ownerDocument™™Ð// element is window or document™™Ð
element.document || element);™™Ð—F†—2çv–æF÷r Ò B, F†—2æFö7VÖVçE³ ÒæFVf VÇEf–Wr
|| this.document[0].parentWindow);™™Ð™™Ðthis._create();™™Ðthis._trigger("create",
null, this._getCreateEventData());™™Ðthis._init();™™Ð÷™™ÍövWD7&V FT÷ F–öç3¢ Bææö÷ Í™™Ð
_getCreateEventData: $.noop,™™Ðö7&V FS¢ Bææö÷ Íö–æ—C¢ Bææö÷ ™™ÐFW7G&÷"¢ gVæ7F–öâ,'
{™™Ðthis._destroy();™™Ð// we can probably remove the unbind calls in 2.0™™Ð// all
event bindings should go through this._on()™™Ðthis.element™™Ð
™'çVæ&–æB, F†—2æWfVçDæ ÖW7 6R™'òò ã' $2 f÷" 3s™'òò DôDò &VÖ÷fR GV Â 7F÷& v]
™'ç&VÖ÷fTF F , F†—2çv–FvWDæ ÖR™'ç&VÖ÷fTF F , F†—2çv–FvWDgVÆÄæ ÖR™'òò 7W ÷'C¢
jquery <1.6.3™™Ð'òò ‡GG ¢öö'Vw2æ§ VW''æ6öÒ÷F–6¶WBó"C =
™'ç&VÖ÷fTF F , Bæ6 ÖVÄ6 6R, F†—2çv–FvWDgVÆÄæ ÖR ' ™™½this.widget()™™Ð
™'çVæ&–æB, F†—2æWfVçDæ ÖW7 6R™'ç&VÖ÷fT GG", & &– ÖF—6 &ÆVB"™'ç&VÖ÷fT6Æ 72™™Ð
this.widgetFullName + "-disabled " +™™Ð™™Ð"ui-state-disabled" ™™Ð™™Ð// clean up events
and states™™Ðthis.bindings.unbind(this.eventNamespace);™™Ð
this.hoverable.removeClass("ui-state-hover");™™Ð
this.focusable.removeClass("ui-state-focus");™™ÐÒÍöFW7G&÷"¢ Bææö÷ ™™Ðv–FvWC¢
function() {™™Ðreturn this.element;™™Ð™™Ð÷ F–öã¢ gVæ7F–öâ, ¶W'Â f ÇVR ' ™™½var options
= key,™™Ð— 'G2Í7W$÷ F–öã™™Í™™Ð½f (arguments.length === 0) {™™ÐÒòò FöâwB &WGW&â
reference to the internal hash™™Ð—&WGW&â Bçv–FvWBæW‡FVæB, ·ÒÂ F†—2æ÷ F–öç2 ™™Ð™™Ðif
(typeof key === "string") {™™Ð'òò † æFÆR æW7FVB ¶W—2Â RærâÂ &fööæ& "" Ó™™Ðâ ² fööó¢
{ bar: ___ } }™™Ð–÷ F–öç2 Ò ·™™Ó½ 'G2 Ò ¶W'ç7 Æ—B, "â" ™™½¶W' Ò 'G2ç6†–gB,™™½–b
(parts.length) {™™Ðcur Option = options[key] = $.widget.extend({},
this.options[key]);™™Ðfor (i = 0; i < parts.length - 1; i++)™™Ð{™™Ð
curOption[parts[i]] = curOption[parts[i]] || {};™™Ð–7W$÷ F–öâ Ò
curOption[parts[i]];™™Ð™™Ð}™™Ðkey = parts.pop();™™Ðif (arguments.length === 1)™™Ð{™™Ð
return curOption[key] === undefined ? null : curOption[key];™™Ð™™Ð}™™Ð
curOption[key] = value;™™Ð—Ò VÇ6R™™½if (arguments.length === 1)™™Ð{™™Ð&WGW&â
this.options[key] === undefined ? null : this.options[key];™™Ð™™Ð}™™Ð
options[key] = value;™™Ð—™™Ðthis._setOptions(options);™™Ðreturn this;™™ÐÍ™™Ð
_setOptions: function(options) {™™Ð

™var key;™for (key in options) {™
this._setOption(key, options[key]);™™return this;™÷6WD÷ F–öã¢
function(key, value) {™this.options[key] = value;™if (key === "disabled")
{™–F†–2çv–FvWB,™™.toggleClass(this.widgetFullName + "-disabled ui-state-
disabled", !!value);™™.attr("aria-disabled", value);™
this.hoverable.removeClass("ui-state-hover");™™
this.focusable.removeClass("ui-state-focus");™™return this;™™Æ &ÆS¢
function() {™return this._setOption("disabled", false);™F–6 &ÆS¢ gVæ7F–öâ,’
{™return this._setOption("disabled", true);™öõã¢
function(suppressDisabledCheck, element, handlers) {™var delegateElement,™™
instance = this;™// no suppressDisabledCheck flag, shuffle arguments™if
(typeof suppressDisabledCheck !== "boolean") {™–† æFÆW'2 Ò VÆVÖVçC½VÆVÖVçB Ò
suppressDisabledCheck;™–7W &W74F–6 &ÆVD6†V6² Ò f Ç6™™/ no element argument,
shuffle and use this.element™if (!handlers) {™† æFÆW'2 Ò VÆVÖVçC½VÆVÖVçB Ò
this.element;™–FVÆVv FTVÆVÖVçB Ò F†–2çv–FvWB,™½ else {™Òòò 66W B 6VÆV7F÷'2Â DôÒ
elements™–VÆVÖVçB Ò FVÆVv FTVÆVÖVçB Ò B, VÆVÖVçB ™½F†–2æ&–æF–æw2 Ò
this.bindings.add(element);™™™.each(handlers, function(event, handler) {™
function handlerProxy() {™™// allow widgets to customize the disabled handling™
™™// - disabled as an array instead of boolean™™/ - disabled class as method for
disabling individual parts™™if (!suppressDisabledCheck &&™™
(instance.options.disabled === true ||™™™’B, F†–2 ’æ† 46Æ 72, 'V’×7F FR™
disabled"))) {™–&WGW&™™™

™™Ðhasoptions = !$.isEmptyObject(options);™Ð
options.complete = callback;™Ðif (options.delay) {™Ð
element.delay(options.delay);™™Ðif (hasOptions && $.effects &&
$.effects.effect[effectName]) {™Ð–VÆVÖVçE² ÖWF†öB Ò, ÷ F–öç2 ™™½ else if
(effectName !== method && element[effectName]) {™Ð–VÆVÖVçE² VffV7Dæ ÖR Ð
(options.duration, options.easing, callback);™Ð} else {™Ð
element.queue(function(next) {™™$(this)[method](™™Ðif (callback)™™Ð
callback.call(element[0]);™™™Ðext(™÷Ð™™½Ó½);™Ð)(jQuery);™Ðfunction($,
undefined) {™Ðar mouseHandled = false;™Ð(document).mouseup(function() {™Ð
mouseHandled = false;™Ð);™Ð.widget("ui.mouse", {™ÐfW'6–öã¢ # ã ãB"™Í÷ F–öç3¢ ™™½
cancel: "input,textarea,button,select,option",™Ðdistance: 1,™™Ðelay: 0™™ÒÍ
_mouseInit: function() {™™Ðvar that = this;™™Ðthis.element™Ð
™™'æ&–æB,&Ö÷W6VF÷vâ"·F†–2çv–FvWDæ ÖRÂ gVæ7F–öâ†WfVçB'™™½return
that._mouseDown(event);™™™Ó'æ&–æB,&6Æ–6²â"·F†–2çv–FvWDæ ÖRÂ gVæ7F–öâ†WfVçB'™™½if
(true === $.data(event.target, that.widgetName + ".preventClickEvent")) {™™™•
$.removeData(event.target, that.widgetName + ".preventClickEvent");™™™•
event.stopImmediatePropagation();™™™–&WGW&â f ÇÖS™™½™™™this.started = false;™™™Òòò
TODO: make sure destroying one instance of mouse doesn't mess with™™Òòò ÷F†W"
instances of mouse™™öÖ÷W6TFW7G&÷"¢ gVæ7F–öâ,' ™™½
this.element.unbind("."+this.widgetName);™™Ðif (this._mouseMoveDelegate) {™™Ð
$(document)™™™.unbind("mousemove."+this.widgetName, this._mouseMoveDelegate)™™Ð
™™™.unbind("mouseup."+this.widgetName, this._mouseUpDelegate);™™™öÖ÷W6TF÷vã¢
function(event) {™™™// don't let more than one widget handle mouseStart™™™Ð
if(mouseHandled) { return; }™™™// we may have missed mouseup (out of window)™™™Ð
(this._mouseStarted && this._mouseUp(event));™™™this._mouseDownEvent = event;™™™Ðar
that = this,™™™–'Fä–4ÆVgB Ò †WfVçBçv†–6, ÓÓÒ ™™™Íòò WfVçBçF &vWBææöFTæ ÖR v÷&·2
around a bug in IE 8 with™™™'òò F–6 &ÆVB –ç WG2 ,3sc#™™™•VÄ–46 æ6VÂ Ò ‡G– Vöb
this.options.cancel === "string" && event.target.nodeName ?
$(event.target).closest(this.options.cancel).length : false);™™™Ðif (!btnIsLeft
|| elIsCancel || !this._mouseCapture(event)) {™™™–&WGW&â G'VS™™™

ÐöÖ÷W6TFVÆ ”ÖWC¢ gVæ7F–öâ,ò¢ WfVçB ¢ò’ ™½return this.mouseDelayMet;ÐÍòò F†W6R
are placeholder methods, to be overriden by extending pluginÐöÖ÷W6U7F 'C¢
function(/* event */) {},ÐöÖ÷W6TG& s¢ gVæ7F–öâ,ò¢ WfVçB ¢ò’ ·ÒÍöÖ÷W6U7F÷ ¢
function(/* event */) {},ÐöÖ÷W6T6 GW&S¢ gVæ7F–öâ,ò¢ WfVçB ¢ò’ ² &WGW&â G'VS² Ý
});Ð})(jQuery);Ðfunction($, undefined) {Ð.widget("ui.draggable", $.ui.mouse,
{ÐfW'6–öã¢ # ã ãB"Ív–FvWDWfVçE &Vf–ƒ¢ &G& r"Í÷ F–öç3¢ ™½addClasses: true,™Ð
appendTo: "parent",™Ðaxis: false,™ÐconnectToSortable: false,™Ðcontainment: false,™Ð
cursor: "auto",™ÐcursorAt: false,™Ðgrid: false,™Ðhandle: false,™Ðhelper: "original",™Ð
iframeFix: false,™Ðopacity: false,™ÐrefreshPositions: false,™Ðrevert: false,™Ð
revertDuration: 500,™Ðscope: "default",™Ðscroll: true,™ÐscrollSensitivity: 20,™Ð
scrollSpeed: 20,™Ðsnap: false,™ÐsnapMode: "both",™ÐsnapTolerance: 20,™Ðstack: false,™Ð
zIndex: false,™Ð// callback™Ðdrag: null,™Ðstart: null,™Ðstop: null™ÐÍö7&V FS¢
function() {™Ðif (this.options.helper === "original" && !(/^(?:r|a|
f)/).test(this.element.css("position"))) {™Ð–F†–2æVÆVÖVçE³ Òç7G–ÆRç ÷6–F–öâ Ò
"relative";™Ð™Ðif (this.options.addClasses)™ÐF†–2æVÆVÖVçBæ FD6Æ 72,'V’Ð
draggable");™Ð™Ðif (this.options.disabled)™ÐF†–2æVÆVÖVçBæ FD6Æ 72,'V’ÖG& vv &ÆRÐ
disabled");™Ð™Ðthis._mouseInit();™ÐÍöFW7G&÷“¢ gVæ7F–öâ,’ ™½
this.element.removeClass("ui-draggable ui-draggable-dragging ui-draggable-
disabled");™Ðthis._mouseDestroy();™ÐÍöÖ÷W6T6 GW&S¢ gVæ7F–öâ†WfVçB’ ™Ðvar o =
this.options;™Ð// among others, prevent a drag on a resizable-handle™Ðif
(this.helper || o.disabled || $(event.target).closest(".ui-resizable-
handle").length > 0) {™Ð–&WGW&â f Ç6S™™Ð//Quit if we're not on a valid handle™Ð
this.handle = this._getHandle(event);™Ðif (!this.handle) {™Ð&WGW&â f Ç6S™™Ð
$(o.iframeFix === true ? "iframe" : o.iframeFix).each(function() {™Ð’B,#ÆF–b
class='ui-draggable-iframeFix' style='background: #fff;'> ")™Ð’æ772‡½width:
this.offsetWidth+"px", height: this.offsetHeight+"px",™Ðposition: "absolute",
opacity: "0.001", zIndex: 1000™Ð–Ù‘æ772,B‡F†–2’æöfg6WB,™‘æ VæEFò,&&öG’"™½)™Ð
return true;ÐÒÍöÖ÷W6U7F 'C¢ gVæ7F–öâ†WfVçB’ ™Ðvar o = this.options;™Ð//Create and
append the visible helper™Ðthis.helper = this._createHelper(event);™Ð
this.helper.addClass("ui-draggable-dragging");™Ð//Cache the helper size™Ð
this._cacheHelperProportions();™Ð//If ddmanager is used for droppables, set the
global draggable™Ðif($.ui.ddmanager) {™ÐBçV’æFFÖ æ vW"æ7W'&VçB Ò F†–S™™Ð™Ð* -
Position generation -™Ð * This block generates everything position related -
it's the core of draggables.™Ð *™Ð//Cache the margins of the original element™Ð
this._cacheMargins();™Ð//Store the helper's css position™Ðthis.cssPosition =
this.helper.css("position");™Ðthis.scrollParent = this.helper.scrollParent();™Ð
this.offsetParent = this.helper.offsetParent();™Ðthis.offsetParentCssPosition =
this.offsetParent.css("position");™Ð//The element's absolute position on the
page minus margins™Ðthis.offset = this.positionAbs = this.element.offset();™Ð
this.offset = {™Ð–F÷ ¢ F†–2æöfg6WBçF÷ Ò F†–2æÖ &v–ç2çF÷™ÍÆVgC¢ F†–2æöfg6WBæÆVgB
- this.margins.left™Ð}™Ð//Reset scroll cache™Ðthis.offset.scroll = false™Ð
$.extend(this.offset, {™Ð–6Æ–6³¢ ² òõv†W&R F†R 6Æ–6² † VæVBÂ &VÆ F–fR Fò F†R
element™Ðleft: event.pageX - this.offset.left,™Ðtop: event.pageY - this.offset.top™Ð
™–™Í &VçC¢ F†–2åövWE &VçDöfg6WB,™Í&VÆ F–fS¢ F†–2åövWE&VÆ F–fTöfg6WB,’ òõF†–2
is a relative to absolute position minus the actual position calculation -
only used for relative positioned helper™Ð}™Ð//Generate the original position™Ð
this.originalPosition = this.position = this._generatePosition(event);™Ð
this.originalPageX = event.pageX;™Ðthis.originalPageY = event.pageY;™Ð//Adjust
the mouse offset relative to the helper if "cursorAt" is supplied™Ð(o.cursorAt
&& this._adjustOffsetFromHelper(o.cursorAt));™Ð//Set a containment if given in
the options™Ðthis._setContainment();™Ð//Trigger event + callback™Ð
if(this._trigger("start", event) === false) {™Ð–F†–2åö6ÆV ,™½&WGW&â f Ç6S™™Ð//
Recache the helper size™Ðthis._cacheHelperProportions();™Ð//Prepare the droppable
offsets™Ðif ($.ui.ddmanager && !o.dropBehaviour) {™Ð
$.ui.ddmanager.prepareOffsets(this, event);™Ð™Ðthis._mouseDrag(event, true); //
Execute the drag once - this causes the helper not to be visible before
getting its correct position™Ð//If the ddmanager is used for droppables, inform
the manager that dragging has started (see #5003)™Ðif ($.ui.ddmanager) {™Ð
$.ui.ddmanager.dragStart(this, event);™Ð™Ðreturn true;ÐÍöÖ÷W6TG& s¢
function(event, noPropagation) {Ð

™// reset any necessary cached properties (see
#5009)Ðif (this.offsetParentCssPosition === "fixed") {ÐF†—2æöfg6WBç &VçB Ò
this._getParentOffset();ÐÐÐ/Compute the helpers positionÐthis.position =
this._generatePosition(event);Ðthis.positionAbs =
this._convertPositionTo("absolute");Ð//Call plugins and callbacks and use the
resulting position if something is returnedÐif (!noPropagation) {Ðf " V’ Ò
this._uiHash();Ð--b‡F†—2å÷G&–vvW",&G& r"Â WfVçBÂ V’’ ÓÓÒ f Ç6R’™½
this._mouseUp({});Ð™return false;ÐF†—2ç ÷6—F–öâ Ò V’ç ÷6—F–öâÐÐf(!
this.options.axis || this.options.axis !== "y") {Ð—F†—2æ†VÇ W%³ Òç7G–ÆRæÆVgB Ò
this.position.left+"px";Ð}Ðif(!this.options.axis || this.options.axis !== "x") {Ð
this.helper[0].style.top = this.position.top+"px";Ð}Ðif($.ui.ddmanager) {Ð
$.ui.ddmanager.drag(this, event);ÐÐÐreturn false;ÐÓöÖ÷W6U7F÷ ¢ gVæ7F–öâ†WfVçB’ Ð
™//If we are using droppables, inform the manager about the droppÐvar that =
this,Ð–G&÷ VB Ò f Ç6S½f ($.ui.ddmanager && !this.options.dropBehaviour) {Ð
dropped = $.ui.ddmanager.drop(this, event);ÐÐÐ/if a drop comes from outside (a
sortable)Ðif(this.dropped) {ÐG&÷ VB Ò F†—2æG&÷ VC½F†—2æG&÷ VB Ò f Ç6SÐÐ/if
the original element is no longer in the DOM don't bother to continue (see
#8269)Ðif (this.options.helper === "original" && !
$.contains(this.element[0].ownerDocument, this.element[0])) {Ð—&WGW&â
false;ÐÐÐf((this.options.revert === "invalid" && !dropped) ||
(this.options.revert === "valid" && dropped) || this.options.revert === true
|| ($.isFunction(this.options.revert) &&
this.options.revert.call(this.element, dropped))) {Ð•
$(this.helper).animate(this.originalPosition,
parseInt(this.options.revertDuration, 10), function() {Ð™
if(that._trigger("stop", event) !== false) {Ð™—F† Båö6ÆV "‚½Ð™½ else {Ð
if(this._trigger("stop", event) !== false) {Ð™this._clear();ÐÐreturn false;ÐÓ
_mouseUp: function(event) {Ð//Remove frame helperÐ™Ð("div.ui-draggable-
iframeFix").each(function() {Ð—F†—2ç &VçDæöFRç&VÖ÷fT6†–ÆB‡F†—2™½);ÐÐ/If the
ddmanager is used for droppables, inform the manager that dragging has
stopped (see #5003)Ðif($.ui.ddmanager) {ÐBçV’æFFÖ æ vW"æG& u7F÷ ‡F†—2Â WfVçB“½
™ÐÐreturn $.ui.mouse.prototype._mouseUp.call(this, event);ÐÓ6 æ6VÃ¢ gVæ7F–öâ,’ Ð
if(this.helper.is(".ui-draggable-dragging")) {Ð—F†—2åöÖ÷W6UW ‡·Ò™½ else {Ð
this._clear();ÐÐÐreturn thisÐÐÐövWD† æFÆS¢ gVæ7F–öâ†WfVçB’ ½return
this.options.handle ?Ð’
$(event.target).closest(this.element.find(this.options.handle)).length :Ð•
true;ÐÒÓö7&V FT†VÇ W#¢ gVæ7F–öâ†WfVçB’ Ðvar o = this.options,Ð†VÇ W" Ò
$.isFunction(o.helper) ? $(o.helper.apply(this.element[0], [event])) :
(o.helper === "clone" ? this.element.clone().removeAttr("id") : this.element);Ð
if(!helper.parents("body").length) {Ð–†VÇ W"æ VæEFò,†òæ VæEFò ÓÓÒ
"parent" ? this.element[0].parentNode : o.appendTo));ÐÐÐf(helper[0] !==
this.element[0] && !(/(fixed|absolute)/).test(helper.css("position"))) {Ð•
helper.css("position", "absolute");ÐÐÐreturn helperÐÐÐö F§W7Döfg6WDg&öÔ†VÇ W#¢
function(obj) {Ðif (typeof obj === "string") {Ðö&¢ Ò ö&¢ç7 Æ—B," "‚½Ðf
($.isArray(obj)) {Ð–ö&¢ Ò ¶ÆVgC¢ ¶ö&¥³ ÒÂ F÷ ¢ ¶ö&¥³ Ò ÇÂ ÓÐÐf ("left" in
obj) {Ð—F†—2æöfg6WBæ6Æ–6²æÆVgB Ò ö&¢æÆVgB ² F†—2æÖ &v–ç2æÆVgCÐÐf ("right" in
obj) {Ð—F†—2æöfg6WBæ6Æ–6²æÆVgB Ò F†—2æ†VÇ W% &÷ ÷'F–öç2çv–GF, Ò ö&¢ç&–v‡B ²
this.margins.left;Ð}Ðif ("top" in obj) {ÐF†—2æöfg6WBæ6Æ–6²çF÷ Ò ö&¢çF÷ ²
this.margins.top;Ð}Ðif ("bottom" in obj) {ÐF†—2æöfg6WBæ6Æ–6²çF÷ Ò
this.helperProportions.height - obj.bottom + this.margins.top;Ð}ÐÓ
_getParentOffset: function() {Ð//Get the offsetParent and cache its positioÐ™Ð
var po = this.offsetParent.offset();Ð// This is a special case where we need
to modify a offset calculated on start, since the following happened:Ð// 1.
The position of the helper is absolute, so it's position is calculated based
on the next positioned parentÐ// 2. The actual offset parent is a child of the
scroll parent, and the scroll parent isn't the document, which means thatÐ
™//   the scroll is included in the initial calculation of the offset of the
parent, and never recalculated upon dragÐif(this.cssPosition === "absolute" &&
this.scrollParent[0] !== document && $.contains(this.scrollParent[0],
this.offsetParent[0])) {Ð

™— òæÆVgB ³Ò F†—2ç67&öÆÅ &VçBç67&öÆÄÆVgB,™½ òçF÷ ³Ò
this.scrollParent.scrollTop();™™™/This needs to be actually done for all
browsers, since pageX/pageY includes this information™//Ugly IE fi™
if((this.offsetParent[0] === document.body) ||™'‡F†—2æöfg6WE &VçE³ ÒçF tæ ÖR
&& this.offsetParent[0].tagName.toLowerCase() === "html" && $.ui.ie)) {™— ò Ò
{ top: 0, left: 0 };™™™eturn {™F÷ ¢ òçF÷ ²
(parseInt(this.offsetParent.css("borderTopWidth"),10) || 0),™–ÆVgC¢ òæÆVgB ²
(parseInt(this.offsetParent.css("borderLeftWidth"),10) || 0)™}™™™
_getRelativeOffset: function() {™if(this.cssPosition === "relative") {™f "   Ò
this.element.position();™—&WGW&â™½top: p.top -
(parseInt(this.helper.css("top"),10) || 0) + this.scrollParent.scrollTop(),™™
left: p.left - (parseInt(this.helper.css("left"),10) || 0) +
this.scrollParent.scrollLeft()™—™½ else {™&WGW&â ² F÷ ¢ Â ÆVgC¢   ™™™
_cacheMargins: function() {™this.margins = {™ÆVgC¢
(parseInt(this.element.css("marginLeft"),10) || 0),™—F÷ ¢
(parseInt(this.element.css("marginTop"),10) || 0),™—&–v‡C¢
(parseInt(this.element.css("marginRight"),10) || 0),™–&÷GFöÓ¢
(parseInt(this.element.css("marginBottom"),10) || 0)™}™™™
_cacheHelperProportions: function() {™this.helperProportions = {™v–GFƒ¢
this.helper.outerWidth(),™–†V–v‡C¢ F†—2æ†VÇ W"æ÷WFW$†V–v‡B™}™™™
_setContainment: function() {™var over, c, ce™Òò Ò F†—2æ÷ F–öçÐ½f (!
o.containment) {™—F†—2æ6öçF –æÖVçB Ò çVÆÄ½&WGW&™™™f (o.containment ===
"window") {™—F†—2æ6öçF –æÖVçB Ò™½$(window).scrollLeft() -
this.offset.relative.left - this.offset.parent.left,™$(window).scrollTop() -
this.offset.relative.top - this.offset.parent.top,™$(window).scrollLeft() +
$(window).width() - this.helperProportions.width - this.margins.left,™
$(window).scrollTop() + ($(window).height() ||
document.body.parentNode.scrollHeight) - this.helperProportions.height -
this.margins.top™•™½&WGW&™™™f (o.containment === "document") {™
this.containment = [™™™™™™0,™,™(document).width() - this.helperProportions.width
- this.margins.left,™($(document).height() ||
document.body.parentNode.scrollHeight) - this.helperProportions.height -
this.margins.top™•™½&WGW&™™™f (o.containment.constructor === Array) {™
this.containment = o.containment;™—&WGW&™™™f (o.containment === "parent") {™
o.containment = this.helper[0].parentNode;™™™ = $(o.containment)™e =
c[0];™if(!ce) {™&WGW&™™™over = c.css("overflow") !== "hidden"™™
this.containment = [™',   '6T–çB, 2æ772, &&÷&FW$ÆVgEv–GF," 'Â   ' ÇÂ   ' ²
(parseInt(c.css("paddingLeft"), 10) || 0),™•
(parseInt(c.css("borderTopWidth"), 10) || 0) +
(parseInt(c.css("paddingTop"), 10) || 0) ,™', ÷fW" ò
Math.max(ce.scrollWidth, ce.offsetWidth) : ce.offsetWidth) -
(parseInt(c.css("borderRightWidth"), 10) || 0) -
(parseInt(c.css("paddingRight"), 10) || 0) -
this.helperProportions.width - this.margins.left - this.margins.right,™•
(over ? Math.max(ce.scrollHeight, ce.offsetHeight) : ce.offsetHeight) -
(parseInt(c.css("borderBottomWidth"), 10) || 0) -
(parseInt(c.css("paddingBottom"), 10) || 0) -
this.helperProportions.height - this.margins.top - this.margins.bottom™]™™
this.relative_container = c;™™™ö6öçfW'E ÷6—F–öåFó¢ gVæ7F–öâ†BÂ ÷2' ™if(!pos) {™
pos = this.position;™™™ar mod = d === "absolute" ? 1 : -1™™67&öÆÂ Ò
this.cssPosition === "absolute" && !(this.scrollParent[0] !== document &&
$.contains(this.scrollParent[0], this.offsetParent[0])) ?
this.offsetParent : this.scrollParent;™//Cache the scroll™f (!
this.offset.scroll) {™—F†—2æöfg6WBç67&öÆÂ Ò ·F÷ ¢ 67&öÆÂç67&öÆÅF÷ ,'Â ÆVgB ¢
scroll.scrollLeft()};™™™eturn {™F÷ ¢™•pos.top'¹™™™™™™™'òò F†R '6öÇWFR Ö÷W™R ÷6—F–öí
this.offset.relative.top * mod +™™™™™// Only for relative positioned nodes:
Relative offset from element to offset parent™this.offset.parent.top * mod -™™™™™//
The offsetParent's offset without borders (offset + border)™
((this.cssPosition === "fixed" ? -this.scrollParent.scrollTop() :
this.offset.scroll.top) * mod)™

™’™ÍÆVgC¢™•pos.left +™™™™™™™// The absolute mouse
positionÐ™this.offset.relative.left * mod +™™™™™™// Only for relative positioned
nodes: Relative offset from element to offset parentÐ™this.offset.parent.left *
mod’Ù™™™™’òò F†R öfg6WE &VçBw2 öfg6WB v—F†÷WB &÷&FW'2 †öfg6WB ² &™™&FW"•
((this.cssPosition === "fixed" ? -this.scrollParent.scrollLeft() :
this.offset.scroll.left) * mod)Ð™}ÐÐÐÐÓövVæW& FU ÷6—F–öã¢ gVæ7F–öâ†WfVçB’ ÐÐvar
containment, co, top, left,Ð–ò Ò F†—2æ÷ F–öç2Í67&öÆÂ Ò F†—2æ775 ÷6—F–öâ ÓÓÒ
"absolute" && !(this.scrollParent[0] !== document &&
$.contains(this.scrollParent[0], this.offsetParent[0])) ?
this.offsetParent : this.scrollParent,Ð— vU, Ò WfVçBç vU™Í vU’ Ò WfVçBç vUÐ½
™//Cache the scrollÐif (!this.offset.scroll) {ÐF†—2æöfg6WBç67&öÆÂ Ò ·F÷ ¢
scroll.scrollTop(), left : scroll.scrollLeft()};ÐÐÐ™Ð* - Position constraining
-Ð * Constrain the position to a mix of grid, containment.Ð*ÐÐ/ If we are not
dragging yet, we won't check for optionsÐif (this.originalPosition) {Ð–b
(this.containment) {Ð™if (this.relative_container){Ð6ò Ò
this.relative_container.offset();Ð™–6öçF –æÖVçB Ò™½this.containment[0] +
co.left,Ð™this.containment[1] + co.top,Ðthis.containment[2] + co.left,Ð
this.containment[3] + co.topÐ™Ó½Ðelse {Ð6öçF –æÖVçB Ò F†—2æ6öçF –æÖVçÐ½Ð
if(event.pageX - this.offset.click.left < containment[0]) {Ð™— vU, Ò
containment[0] + this.offset.click.left;Ð™}Ðif(event.pageY -
this.offset.click.top < containment[1]) {Ð™— vU’ Ò 6öçF –æÖVçE³ Ò ²
this.offset.click.top;Ð™}Ðif(event.pageX - this.offset.click.left >
containment[2]) {Ð™— vU, Ò 6öçF –æÖVçE³%Ò ² F†—2æöfg6WBæ6Æ–6²æÆVgC½Ð
if(event.pageY - this.offset.click.top > containment[3]) {Ð™— vU’ Ò
containment[3] + this.offset.click.top;Ð™ÐÍ–b†òæw&–B’™½//Check for grid
elements set to 0 to prevent divide by 0 error causing invalid argument
errors in IE (see ticket #6950)Ð™top = o.grid[1] ? this.originalPageY +
Math.round((pageY - this.originalPageY) / o.grid[1]) * o.grid[1] :
this.originalPageY;Ð™pageY = containment ? ((top - this.offset.click.top >=
containment[1] || top - this.offset.click.top > containment[3]) ? top : ((top
- this.offset.click.top >= containment[1]) ? top - o.grid[1] : top +
o.grid[1])) : top;Ð™left = o.grid[0] ? this.originalPageX + Math.round((pageX -
this.originalPageX) / o.grid[0]) * o.grid[0] : this.originalPageX;Ð™pageX =
containment ? ((left - this.offset.click.left >= containment[0] || left -
this.offset.click.left > containment[2]) ? left : ((left -
this.offset.click.left >= containment[0]) ? left - o.grid[0] : left +
o.grid[0])) : left;ÐÐÐÍÐreturn {ÐF÷ ¢™•pageY -™™™™™™™™’òò F†R '6öÇWFR Ö÷W6R ÷6—F–öí
this.offset.click.top’Ù™™™™™™™’òò 6Æ–6² öfg6WB ‡&VÆ F—fR Fò F†R VÆVÖVçB•
this.offset.relative.top -™™™™™™™™// Only for relative positioned nodes: Relative
offset from element to offset parentÐ™this.offset.parent.top +™™™™™™™™// The
offsetParent's offset without borders (offset + border)Ð™(this.cssPosition ===
"fixed" ? -this.scrollParent.scrollTop() : this.offset.scroll.top)Ð’™ÍÆVgC¢™•
pageX -™™™™™™™™™™’òò F†R '6öÇWFR Ö÷W6R™™this.offset.click.left -™™™™™™™™// Click offset
(relative to the element)Ð™this.offset.relative.left -™™™™™™™™// Only for relative
positioned nodes: Relative offset from element to offset parentÐ™
this.offset.parent.left +™™™™™™™™// The offsetParent's offset without borders (offset
+ border)Ð™(this.cssPosition === "fixed" ? -this.scrollParent.scrollLeft() :
this.offset.scroll.left)Ð™}ÐÐÐÍÐö6ÆV #¢ gVæ7F–öâ,’ ½this.helper.removeClass("ui-
draggable-dragging");Ðif(this.helper[0] !== this.element[0] && !
this.cancelHelperRemoval) {Ð™—F†—2æ†VÇ W"ç&VÖ÷fR,™½Ðthis.helper = null;Ð
this.cancelHelperRemoval = false;ÐÐÍÒòò g&öÒ æ÷r öâ 'VÆ² 7GVfb Ò Ö –æÇ’ †VÇ W'Ð
_trigger: function(type, event, ui) {Ðui = ui || this._uiHash();Ð
$.ui.plugin.call(this, type, [event, ui]);Ð//The absolute position has to be
recalculated after pluginsÐif(type === "drag") {ÐF†—2ç ÷6—F–öä '2 Ò
this._convertPositionTo("absolute");Ð™}Ðreturn
$.Widget.prototype._trigger.call(this, type, event, ui);ÐÒÍÐ ÇVv–ç3¢ ·ÒÍÐ
_uiHash: function() {Ðreturn ™Ð†VÇ W#¢ F†—2æ†VÇ W™Í ÷6—F–öã¢ F†—2ç ÷6—F–öãÍ
originalPosition: this.originalPosition,Ð–öfg6WC¢ F†—2ç ÷6—F–öä ™}÷Ð);Ð
$.ui.plugin.add("draggable", "connectToSortable", {Ð7F 'C¢ gVæ7F–öâ†WfVçBÂ V’’
{Ð

™Ðvar inst = $(this).data("ui-draggable"), o = inst.options;™ÐV•6÷'F &ÆR Ò
$.extend({}, ui, { item: inst.element });™Ðinst.sortables = [];™Ð
$(o.connectToSortable).each(function() {™Ð—f " 6÷'F &ÆR Ò BæF F ‡F†—2Â 'V'Ð
sortable");™Ð––b ‡6÷'F &ÆR bb 6÷'F &ÆRæ÷ F–öç2æF—6 &ÆVB'™½inst.sortables.push({™Ð
instance: sortable,™Ð—6†÷VÆE&WfW'C¢ 6÷'F &ÆRæ÷ F–öç2ç&WfW™™™™™™);™Ð
sortable.refreshPositions();'òò 6 ÆÂ F†R 6÷'F &ÆRw2 &Vg&W6… ÷6—F–öç2 B G& r
start to refresh the containerCache since the sortable container cache is
used in drag and needs to be up to date (this will ensure it's initialised as
well as being kept in step with any changes that might have happened on the
page).™Ðsortable._trigger("activate", event, uiSortable);™Ð™™™™™™

™™—F†—2æ–ç7F æ6Ræöfg6WBç &VçBçF÷ ÓÒ
inst.offset.parent.top - this.instance.offset.parent.top;Ð™•
inst._trigger("toSortable", event);Ð™––ç7BæG&÷ VB Ò F†—2æ–ç7F æ6RæVÆVÖVçC² òð
draggable revert needs thatÐ™’òö† 6² 6ò &V6V—fR÷W F FR 6 ÆÆ& 6·2 v÷&² †Ö÷7FÇ™•
inst.currentItem = inst.element;Ð™—F†—2æ–ç7F æ6Ræg&öÔ÷WG6–FR Ò –çÐ™½Ð/Provided
we did all the previous steps, we can fire the drag event of the sortable on
every draggable drag, when it intersects with the sortableÐ™
if(this.instance.currentItem) {Ð™—F†—2æ–ç7F æ6RåöÖ÷W6TG& r†WfVçBÐ™½Ò VÇ6RÐ™½//If
it doesn't intersect with the sortable, and it intersected before,Ð™//we fake
the drag stop of the sortable, but make sure it doesn't remove the helper by
using cancelHelperRemovalÐ™if(this.instance.isOver)Ð™{ÐF†—2æ–ç7F æ6Ræ—4÷fW" Ò™™½
this.instance.cancelHelperRemoval = true;Ð™’òõ &WfVçB &WfW'F–ær öâ F†—2 f÷&6VB
stopÐ™—F†—2æ–ç7F æ6Ræ÷ F–öç2ç&WfW'B Ò f ÇÐS½òò F†R ÷WB WfVçB æVVG2 Fò &R
triggered independentlyÐ™—F†—2æ–ç7F æ6Rå÷G&–vvW",&÷WB"Â WfVçBÂ
this.instance._uiHash(this.instance));Ð™—F†—2æ–ç7F æ6RåöÖ÷W6U7F÷ †WfVçBÂ G'VR™½
this.instance.options.helper = this.instance.options._helper;Ð™’òôæ÷r vR &VÖ÷fR
our currentItem, the list group clone again, and the placeholder, and animate
the helper back to it's original sizeÐ™—F†—2æ–ç7F æ6Ræ7W'&VçD—FVÒç&VÖ÷fR™½
if(this.instance.placeholder) {Ð™this.instance.placeholder.remove();Ð™
inst._trigger("fromSortable", event);Ð™––ç7BæG&÷ VB Ò f Ç6S² òöG& vv &ÆR &WfW'B
needs thatÐ™½Ð™½);Ð™½.ui.plugin.add("draggable", "cursor", {Ð™7F 'C¢ gVæ7F–öâ,’ ™½
var t = $("body"), o = $(this).data("ui-draggable").options;Ð™if
(t.css("cursor")) {Ð™–òåö7W'6÷" Ò Bæ772,&7W'6÷""™½Ð™½.css("cursor", o.cursor);Ð™½
stop: function() {Ð™var o = $(this).data("ui-draggable").options;Ð™if (o._cursor)
{Ð™’B,&&öG’"’æ772,&7W'6÷""Â òåö7W'6÷""™½Ð™½);Ð™½.ui.plugin.add("draggable",
"opacity", {Ð™7F 'C¢ gVæ7F–öâ†WfVçBÂ V’’ ™½var t = $(ui.helper), o =
$(this).data("ui-draggable").options;Ð™if(t.css("opacity")) {Ð™òåö÷ 6—G’ Ò
t.css("opacity");Ð™}Ð™½.css("opacity", o.opacity);Ð™½7F÷ ¢ gVæ7F–öâ†WfVçBÂ V’’ ™½
var o = $(this).data("ui-draggable").options;Ð™if(o._opacity) {Ð™
$(ui.helper).css("opacity", o._opacity);Ð™}Ð™½);Ð™½.ui.plugin.add("draggable",
"scroll", {Ð™7F 'C¢ gVæ7F–öâ,’ ™½var i = $(this).data("ui-draggable");Ð™
if(i.scrollParent[0] !== document && i.scrollParent[0].tagName !== "HTML") {Ð™•
i.overflowOffset = i.scrollParent.offset();Ð™}Ð™½G& s¢ gVæ7F–öâ, WfVçB ’ ™½var i
= $(this).data("ui-draggable"), o = i.options, scrolled = false;Ð™
if(i.scrollParent[0] !== document && i.scrollParent[0].tagName !== "HTML") {Ð™•
if(!o.axis || o.axis !== "x") {Ð™if((i.overflowOffset.top +
i.scrollParent[0].offsetHeight) - event.pageY < o.scrollSensitivity) {Ð™•
i.scrollParent[0].scrollTop = scrolled = i.scrollParent[0].scrollTop +
o.scrollSpeed;Ð™} else if(event.pageY - i.overflowOffset.top <
o.scrollSensitivity) {Ð™–’ç67&öÆÅ &VçE³ Òç67&öÆÅF÷ Ò 67&öÆÆVB Ò
i.scrollParent[0].scrollTop - o.scrollSpeed;Ð™Ð™½–b, òæ †—2 ÇÂ òæ †—2 ÓÒ '’"’™™½
if((i.overflowOffset.left + i.scrollParent[0].offsetWidth) - event.pageX <
o.scrollSensitivity) {Ð™–’ç67&öÆÅ &VçE³ Òç67&öÆÄÆVgB Ò 67&öÆÆVB Ò
i.scrollParent[0].scrollLeft + o.scrollSpeed;Ð™} else if(event.pageX -
i.overflowOffset.left < o.scrollSensitivity) {Ð™–’ç67&öÆÅ &VçE³ Òç67&öÆÄÆVgB Ò
scrolled = i.scrollParent[0].scrollLeft - o.scrollSpeed;Ð™Ð™½ else {Ð™½–b, òæ †—2
|| o.axis !== "x") {Ð™if(event.pageY - $(document).scrollTop() <
o.scrollSensitivity) {Ð™—67&öÆÆVB Ò
$(document).scrollTop($(document).scrollTop() - o.scrollSpeed);Ð™} else
if($(window).height() - (event.pageY - $(document).scrollTop()) <
o.scrollSensitivity) {Ð™—67&öÆÆVB Ò
$(document).scrollTop($(document).scrollTop() + o.scrollSpeed);Ð™Ð™½–b, òæ †—2
|| o.axis !== "y") {Ð™if(event.pageX - $(document).scrollLeft() <
o.scrollSensitivity) {Ð™—67&öÆÆVB Ò
$(document).scrollLeft($(document).scrollLeft() - o.scrollSpeed);Ð™} else
if($(window).width() - (event.pageX - $(document).scrollLeft()) <
o.scrollSensitivity) {Ð™—67&öÆÆVB Ò
$(document).scrollLeft($(document).scrollLeft() + o.scrollSpeed);Ð™Ð™½Ð
if(scrolled !== false && $.ui.ddmanager && !o.dropBehaviour) {Ð™•
$.ui.ddmanager.prepareOffsets(i, event);Ð

™Ð Ý});Ð.ui.plugin.add("draggable",
"snap", {Ð7F 'C¢ gVæ7F–öâ,' ™Ðvar i = $(this).data("ui-draggable");™Ðò Ò
i.options;™Ði.snapElements = [];™Ð(o.snap.constructor !== String ?
(o.snap.items || ":data(ui-draggable)") : o.snap).each(function() {™Ð–f " GB Ò
$(this),™Ð™$o = $t.offset();™Ðb‡F†–2 ÓÒ ’æVÆVÖVçE³ Ò’™½i.snapElements.push(™Ð
item: this,™Ð–v–GFƒ¢ GBæ÷WFW%v–GF,,’Â †V–v‡C¢ GBæ÷WFW$†V–v‡B,™Í÷F÷ ¢ FòçF÷ Â
left: $o.left™Ð});™Ý});™ÐÒÍG& s¢ gVæ7F–öâ†WfVçBÂ V’’ ™Ðvar ts, bs, ls, rs, l, r, t,
b, i, first,™Ð––ç7B Ò B‡F†–2’æF F ,'V’ÖG& vv &ÆR"™Íò Ò –ç7Bæ÷ F–öç2ÍB Ò
o.snapTolerance,™Ð–ƒ Ò V’æöfg6WBæÆVgBÂ ƒ" Ò ƒ ² –ç7Bæ†VÇ W% &÷ ÷'F–öç2çv–GF™Í
y1 = ui.offset.top, y2 = y1 + inst.helperProportions.height;™Ðfor (i =
inst.snapElements.length - 1; i >= 0; i--){™Ð–Â Ò –ç7Bç6æ VÆVÖVçG5¶•ÒæÆVgC½" Ò
l + inst.snapElements[i].width;™Ð–B Ò –ç7Bç6æ VÆVÖVçG5¶•ÒçF÷™½" Ò B ²
inst.snapElements[i].height;™Ð––b , ƒ" Â Â Ò B ÇÂ ƒ â " ² B ÇÂ “" Â B Ò B ÇÂ “
> b + d || !$.contains(inst.snapElements[i].item.ownerDocument,
inst.snapElements[i].item)) {™Ðif(inst.snapElements[i].snapping)™Ð
(inst.options.snap.release && inst.options.snap.release.call(inst.element,
event, $.extend(inst._uiHash(), { snapItem: inst.snapElements[i].item })));™Ð}Ð
inst.snapElements[i].snapping = false;™Ðcontinue;™Ð–b†òç6æ ÖöFR ÓÒ &–ææW"”’™½
ts = Math.abs(t - y2) <= d;™Ðbs = Math.abs(b - y1) <= d;™Ðls = Math.abs(l - x2)
<= d;™Ðrs = Math.abs(r - x1) <= d;™Ðif(ts)™ÐV’ç ÷6–F–öâçF÷ Ò
inst._convertPositionTo("relative", { top: t - inst.helperProportions.height,
left: 0 }).top - inst.margins.top;™Ð}™Ðif(bs)™ÐV’ç ÷6–F–öâçF÷ Ò
inst._convertPositionTo("relative", { top: b, left: 0 }).top -
inst.margins.top;™Ð}™Ðif(ls)™ÐV’ç ÷6–F–öâæÆVgB Ò
inst._convertPositionTo("relative", { top: 0, left: l -
inst.helperProportions.width }).left - inst.margins.left;™Ð}™Ðif(rs)™Ð
ui.position.left = inst._convertPositionTo("relative", { top: 0, left:
r }).left - inst.margins.left;™Ý™Ýif–'7B Ò ‡G2 ÇÂ '2 ÇÂ Ç2 ÇÂ '2™½–b†òç6æ ÖöFR
== "outer") {™Ðts = Math.abs(t - y1) <= d;™Ðbs = Math.abs(b - y2) <= d;™Ðls =
Math.abs(l - x1) <= d;™Ðrs = Math.abs(r - x2) <= d;™Ðif(ts)™ÐV’ç ÷6–F–öâçF÷ Ò
inst._convertPositionTo("relative", { top: t, left: 0 }).top -
inst.margins.top;™Ð}™Ðif(bs)™ÐV’ç ÷6–F–öâçF÷ Ò
inst._convertPositionTo("relative", { top: b - inst.helperProportions.height,
left: 0 }).top - inst.margins.top;™Ð}™Ðif(ls)™ÐV’ç ÷6–F–öâæÆVgB Ò
inst._convertPositionTo("relative", { top: 0, left: l }).left -
inst.margins.left;™Ð}™Ðif(rs)™ÐV’ç ÷6–F–öâæÆVgB Ò
inst._convertPositionTo("relative", { top: 0, left: r -
inst.helperProportions.width }).left - inst.margins.left;™Ý™Ý–b,
inst.snapElements[i].snapping && (ts || bs || ls || rs || first)) {™Ð
(inst.options.snap.snap && inst.options.snap.snap.call(inst.element, event,
$.extend(inst._uiHash(), { snapItem: inst.snapElements[i].item })));™Ý™Ý
inst.snapElements[i].snapping = (ts || bs || ls || rs || first);™Ý™Ý});Ð
$.ui.plugin.add("draggable", "stack", {Ð7F 'C¢ gVæ7F–öâ,’ ™½var min,™Ðò Ò
this.data("ui-draggable").options,™Ð–w&÷W Ò
$.makeArray($(o.stack)).sort(function(a,b) {™Ðreturn
(parseInt($(a).css("zIndex"),10) || 0) - (parseInt($(b).css("zIndex"),10) ||
0);™Ð–Ò™½if (!group.length) { return; ™Ðmin = parseInt($(group[0]).css("zIndex"),
10) || 0;™Ð$(group).each(function(i) {™ÐB‡F†–2’æ772,'¤–æFW,"Â Ö–â ² ’™½);™Ð
this.css("zIndex", (min + group.length));™Ý});™Ð.ui.plugin.add("draggable",
"zIndex", {Ð7F 'C¢ gVæ7F–öâ†WfVçBÂ V’’ ™½var t = $(ui.helper), o =
$(this).data("ui-draggable").options;™Ðif(t.css("zIndex")) {™Ðòå÷¤–æFW, Ò
t.css("zIndex");™Ð}™Ð.css("zIndex", o.zIndex);™ÐÍ7F÷ ¢ gVæ7F–öâ†WfVçBÂ V’’ ™½var o
= $(this).data("ui-draggable").options;™Ðif(o._zIndex) {™Ð
$(ui.helper).css("zIndex", o._zIndex);™Ý});™Ý});™Ý(jQuery);™Ðfunction($,
undefined) {™Ðunction isOverAxis(x, reference, size) {™Ð&WGW&â , , â
reference) && (x < (reference + size));™Ðwidget("ui.droppable", {™Ð
version: "1.10.4",™Ðv–FvWDWfVçE &Vf–ƒ¢ &G&÷ "Í÷ F–öç3¢ ™½accept: "*",™Ð
activeClass: false,™ÐaddClasses: true,™Ðgreedy: false,™ÐhoverClass: false,™Ðscope:
"default",™Ðtolerance: "intersect",™Ð// callbacks™Ðactivate: null,™Ðdeactivate: null,™Ð
drop: null,™Ð

™out: null™Ð over: null™Ð var proportions™Ð ò Ò
this.options,™Ð– 66W B Ò òæ 66W Ð½this.isover = false™Ð this.isout = true™Ð
this.accept = $.isFunction(accept) ? accept : function(d) {™Ð—&WGW&â
d.is(accept);™Ð}™Ð this.proportions = function(/* valueToWrite */) {™Ð–b
(arguments.length) {™Ð// Store the droppable's proportions™Ð proportions =
arguments[0];™Ð—Ò VÇ6R™½// Retrieve or derive the droppable's proportions™Ð
return proportions ?™Ð— &÷ ÷'F–öç2™Ð— &÷ ÷'F–öç2 Ò™½width:
this.element[0].offsetWidth,™Ð height: this.element[0].offsetHeight™Ð½™Ð/
Add the reference and positions to the manager™Ð
$.ui.ddmanager.droppables[o.scope] = $.ui.ddmanager.droppables[o.scope] || [];™Ð
$.ui.ddmanager.droppables[o.scope].push(this);™Ð(o.addClasses &&
this.element.addClass("ui-droppable"));ÐÒÓöFW7G&÷“¢ gVæ7F–öâ,’ ½var i = 0™ÐG&÷
= $.ui.ddmanager.droppables[this.options.scope];™Ð for (; i < drop.length; i+
+) {™Ð––b , G&÷ ¶•Ò ÓÓÒ F†—2 ’™½drop.splice(i, 1);™Ð™Ð
this.element.removeClass("ui-droppable ui-droppable-disabled");ÐÒÓ÷6WD÷ F–öã¢
function(key, value) {™Ð if(key === "accept") {™ÐF†—2æ 66W B Ò
$.isFunction(value) ? value : function(d) {™Ð return d.is(value);™Ð½™Ð
$.Widget.prototype._setOption.apply(this, arguments);ÐÒÓöö 7F—f FS¢
function(event) {™Ð var draggable = $.ui.ddmanager.current™Ð
if(this.options.activeClass) {™Ð—F†—2æVÆVÖVçBæ FD6Æ 72‡F†—2æ÷ F–öç2æ 7F—fT6Æ 72“½
™Ð}™Ð if(draggable)™ÐF†—2å÷G&–vvW",& 7F—f FR"Â WfVçBÂ F†—2çV’†G& vv &ÆR’™½ÒÓ
_deactivate: function(event) {™Ð var draggable = $.ui.ddmanager.current™Ð
if(this.options.activeClass) {™Ð•
this.element.removeClass(this.options.activeClass);™Ð}™Ð if(draggable)™Ð
this._trigger("deactivate", event, this.ui(draggable));™Ð}™ÐÓöö÷fW#¢
function(event) {™Ð var draggable = $.ui.ddmanager.current™Ð½/ Bail if draggable
and droppable are same element™Ð if (!draggable || (draggable.currentItem ||
draggable.element)[0] === this.element[0]) {™Ð—&WGW&™Ð½™Ð if
(this.accept.call(this.element[0],(draggable.currentItem ||
draggable.element))) {™Ð––b‡F†—2æ÷ F–öç2æ†÷fW$6Æ 72’™½
this.element.addClass(this.options.hoverClass);™Ð—ÝF†—2å÷G&–vvW",&÷fW""Â WfVçBÂ
this.ui(draggable));™Ð™ÐÓöö÷WC¢ gVæ7F–öâ†WfVçB’ ½var draggable =
$.ui.ddmanager.current;™Ð// Bail if draggable and droppable are same element™Ð if
(!draggable || (draggable.currentItem || draggable.element)[0] ===
this.element[0]) {™Ð—&WGW&™Ð½™Ð if (this.accept.call(this.element[0],
(draggable.currentItem || draggable.element))) {™Ð––b‡F†—2æ÷ F–öç2æ†÷fW$6Æ 72’™½
this.element.removeClass(this.options.hoverClass);™Ð—ÝF†—2å÷G&–vvW",&÷WB"Â
event, this.ui(draggable));™Ð™ÐÓöG&÷ ¢ gVæ7F–öâ†WfVçBÆ7W7FöÒ’ ½var draggable =
custom || $.ui.ddmanager.current,™Ð–6†–ÆG&Vä–çFW'6V7F–öâ Ò f Ç6™Ð½/ Bail if
draggable and droppable are same element™Ð if (!draggable ||
(draggable.currentItem || draggable.element)[0] === this.element[0]) {™Ð—&WGW&â
false;™Ð™Ð this.element.find(":data(ui-droppable)").not(".ui-draggable-
dragging").each(function() {™Ð—f " –ç7B Ò BæF F ‡F†—2Â 'V’ÖG&÷ &ÆR"™½–™Ð•
inst.options.greedy &&™Ð!inst.options.disabled &&™Ð inst.options.scope ===
draggable.options.scope &&™Ð inst.accept.call(inst.element[0],
(draggable.currentItem || draggable.element)) &&™Ð$.ui.intersect(draggable,
$.extend(inst, { offset: inst.element.offset() }), inst.options.tolerance)™Ð’’
{ childrenIntersection = true; return false; }™Ð});™Ð if(childrenIntersection) {™Ð
return false;™Ð™Ð if(this.accept.call(this.element[0],(draggable.currentItem ||
draggable.element))) {™Ð––b‡F†—2æ÷ F–öç2æ 7F—fT6Æ 72’™½
this.element.removeClass(this.options.activeClass);™Ð—Ý
if(this.options.hoverClass) {™Ð™
this.element.removeClass(this.options.hoverClass);™Ð—ÝF†—2å÷G&–vvW",&G&÷ "Â
event, this.ui(draggable));™Ð—&WGW&â F†—2æVÆVÖVçC™Ð½™Ð return false™Ð™ÐÓöV“¢
function(c) {™Ð return {™ÐG& vv &ÆS¢ †2æ7W'&VçD–FVÒ ÇÂ 2æVÆVÖVçB™Í†VÇ W#¢ 2æ†VÇ W™Í
position: c.position,™Ð–öfg6WC¢ 2ç ÷6—F–öä ™Ð™Ð);™Ð.ui.intersect =
function(draggable, droppable, toleranceMode) {™Ð–b , G&÷ &ÆRæöfg6WB’ ½return
false;™Ð™Ð if " G& vv &ÆTÆVgBÂ G& vv &ÆUF÷ ™Ix1 = (draggable.positionAbs ||
draggable.position.absolute).left,™Ð y1 = (draggable.positionAbs ||
draggable.position.absolute).top,™Ð

™x2 = x1 + draggable.helperProportions.width,™Ð
y2 = y1 + draggable.helperProportions.height,™Ðl = droppable.offset.left,™Ð =
droppable.offset.top,™Ðr = l + droppable.proportions().width,™Ð = t +
droppable.proportions().height;™Ð7v–F6, ‡FöÆW& æ6TÖöFR’ ™½case "fit":™Ð&WGW&â †Â
<= x1 && x2 <= r && t <= y1 && y2 <= b);™Ðcase "intersect":™Ð&WGW&â †Â Â ƒ ²
(draggable.helperProportions.width / 2) && // Right Half™Ðx2 -
(draggable.helperProportions.width / 2) < r && // Left Half™Ðt < y1 +
(draggable.helperProportions.height / 2) && // Bottom Half™Ðy2 -
(draggable.helperProportions.height / 2) < b); // Top Half™Ðcase "pointer":™Ð
draggableLeft = ((draggable.positionAbs || draggable.position.absolute).left
+ (draggable.clickOffset || draggable.offset.click).left);™Ð–G& vv &ÆUF÷ Ò
((draggable.positionAbs || draggable.position.absolute).top +
(draggable.clickOffset || draggable.offset.click).top);™Ð—&WGW&â
isOverAxis(draggableTop, t, droppable.proportions().height) &&
isOverAxis(draggableLeft, l, droppable.proportions().width);™Ðcase "touch":™Ð
return (™Ð™(y1 >= t && y1 <= b) ||’òò F÷ VFvR F÷V6†–æ™y2 >= t && y2 <= b) ||’òò
Bottom edge touching™Ð™(y1 < t && y2 > b)™// Surrounded vertically™Ðbb™•(x1 >= l
&& x1 <= r) ||’òò ÆVgB VFvR F÷V6†–æ™™(x2 >= l && x2 <= r) ||’òò &–v‡B VFvR
touching™Ð™(x1 < l && x2 > r)™// Surrounded horizontally™Ðdefault:™Ð&WGW&â f Ç6™™™™Ð
/*™ÐF†—2 Ö æ vW" G& 6·2 öfg6WG2 öb G& vv &ÆW2 æB G&÷ &ÆW±/™Ð.ui.ddmanager = {™Ð
current: null,™ÐG&÷ &ÆW3¢ ² &FVf VÇB#¢ µÒ ÒÍ &W &Töfg6WG3¢ gVæ7F–öâ‡BÂ
event) {™Ðvar i, j,™ÐÒ Ò BçV’æFFÖ æ vW"æG&÷ &ÆW5·Bæ÷ F–öç2ç66÷ UÒ ÇÂ µÒÍG— R Ò
event ? event.type : null, // workaround for #2317™Ð–Æ—7B Ò ‡Bæ7W'&VçD—FVÒ ÇÂ
t.element).find(":data(ui-droppable)").addBack();™ÐdroppablesLoop: for (i = 0;
i < m.length; i++) {™Ð’òôæò F—6 &ÆVB æB æöâÖ 66W FV™–b†Õ¶•Òæ÷ F–öç2æF—6 &ÆVB ÇÂ
(t && !m[i].accept.call(m[i].element[0],(t.currentItem || t.element)))) {™Ð™
continue;™Ð™™™Ýòò f–ÇFW" ÷WB VÆVÖVçG2 –â F†R 7W'&VçB G& vvVB —FV™¥f÷" †£Ó ² ¢ Â
list.length; j++) {™Ð™if(list[j] === m[i].element[0])™™™™ÐÕ¶•Òç &÷ ÷'F–öç2,’æ†V–v‡B
= 0;™Ð™–6öçF–çVR G&÷ &ÆW4ÆÖ™™™™

™™—&WGW&â BæF F ‡F†—2Â 'V’Ð
droppable").options.scope === scope;Ð™}Ð™Ð,Ðif (parent.length)™™Ð &VçD–ç7F æ6R Ò
$.data(parent[0], "ui-droppable");Ð™— &VçD–ç7F æ6Ræw&VVG”6†–ÆB Ò †2 ÓÓÒ
"isover");Ð™ÐÝòò vR §W7B Ö÷fVB –çFò   w&VVG’ 6†–Æ™–b ‡ &VçD–ç7F æ6R bb 2 ÓÓÒ
"isover") {Ð™parentInstance.isover = false™Ð;parentInstance.isout = true™Ð
parentInstance._out.call(parentInstance, event);ÐÐÝF†—5¶5Ò Ò G'VS½F†—5¶2 ÓÓÒ
"isout" ? "isover" : "isout"] = false;Ð™—F†—5¶2 ÓÓÒ &—6÷fW"" ò %ö÷fW"" ¢
"_out"].call(this, event);Ð’òò vR §W7B Ö÷fVB ÷WB öb   w&VVG’ 6†–Æ™–b
(parentInstance && c === "isout") {Ð™parentInstance.isout = false™Ð;
parentInstance.isover = true;Ð™parentInstance._over.call(parentInstance, event);Ð
™™Ý)ÐÐÍG& u7F÷ ¢ gVæ7F–öâ, G& vv &ÆRÂ WfVçB ’ ½
draggable.element.parentsUntil("body").unbind("scroll.droppable");Ð™//Call
prepareOffsets one final time since IE does not fire return scroll events
when overflow was caused by drag (see #5003)Ð™if(!
draggable.options.refreshPositions) {Ð™•
$.ui.ddmanager.prepareOffsets(draggable, event);Ð™}Ý;Ð)(jQuery);Ð
(function($, undefined) {Ðfunction num(v) {Ð&WGW&â   '6T–çB‡bÂ   ’ ÇÂ ½Ð
function isNumber(value) {Ð&WGW&â —4æ â‡ '6T–çB‡f ÇVRÂ   ’“½Ð
$.widget("ui.resizable", $.ui.mouse, {ÐfW'6–öã¢ # ã ãB"Ív–FvWDWfVçE &Vf—ƒ¢
"resize",Ð÷ F–öç3¢ ½alsoResize: false™Ð,animate: false™Ð,animateDuration: "slow"™Ð
animateEasing: "swing",Ð™aspectRatio: false™Ð,autoHide: false™Ð,containment: false™Ð
ghost: false,Ð™grid: false™Ð,handles: "e,s,se"™Ð,helper: false™Ð,maxHeight: null™Ð
maxWidth: null,Ð™minHeight: 10™Ð,minWidth: 10™Ð,Ð/ See #7960™ÐIndex: 90™ÐÐ/ callbackS™Ð
resize: null,Ð™start: null™Ð,stop: null™ÐÍö7&V FS¢ gVæ7F–öâ,’ ™Ðvar n, i, handle,
axis, hname,Ð™—F† B Ò F†—2™Íò Ò F†—2æ÷ F–öç3½this.element.addClass("ui-
resizable");Ð™$.extend(this, ™Ðö 7 V7E& F–ó¢   †òæ 7 V7E& F–ò™Í 7 V7E& F–ó¢
o.aspectRatio,Ð™–÷&–v–æ ÄVÆVÖVçC¢ F†—2æVÆVÖVçBÍ÷ &÷ ÷'F–öæ ÆÇ•&W6—¦TVÆVÖVçG3¢ µÐÍ
_helper: o.helper || o.ghost || o.animate ? o.helper || "ui-resizable-
helper" : nullÐ™})™ÐÐ/Wrap the element if it cannot hold child node™Ð
if(this.element[0].nodeName.match(/canvas|textarea|input|select|button|img/
i)) {Ð’òô7&V FR   w&   W" VÆVÖVçB æB 6WB F†R w&   W" Fò F†R æWr 7W'&VçB
internal element™Ð—F†—2æVÆVÖVçBçw& ™™•$("<div class='ui-wrapper' style='overflow:
hidden;'> ").css({™Ð™— ÷6—F–öã¢ F†—2æVÆVÖVçBæ772,' ÷6—F–öâ™™™Ív–GFƒ¢
this.element.outerWidth(),™Ð™–†V–v‡C¢ F†—2æVÆVÖVçBæ÷WFW$†V–v‡B™™™ÍF÷ ¢
this.element.css("top"),™Ð™–ÆVgC¢ F†—2æVÆVÖVçBæ772,&ÆVgB™™™}™Ð½òô÷fW'w&—FR F†R
original this.element™Ð—F†—2æVÆVÖVçB Ò F†—2æVÆVÖVçBç &VçB,’æF F™™•"ui-
resizable", this.element.data("ui-resizable")™Ð™Ð½F†—2æVÆVÖVçD—5w&   W" Ò G'VÐ½òð
Move margins to the wrapper™Ð—F†—2æVÆVÖVçBæ772‡² Ö &v–äÆVgC¢
this.originalElement.css("marginLeft"), marginTop:
this.originalElement.css("marginTop"), marginRight:
this.originalElement.css("marginRight"), marginBottom:
this.originalElement.css("marginBottom") });™Ð™•
this.originalElement.css({ marginLeft: 0, marginTop: 0, marginRight: 0,
marginBottom: 0});Ð’òõ &WfVçB 6 f &’ FW‡F &V &W6—¦™]F†—2æ÷&–v–æ Å&W6—¦U7G–ÆR Ò
this.originalElement.css("resize");Ð™—F†—2æ÷&–v–æ ÄVÆVÖVçBæ772,'&W6—¦R"Â &æöæR"Ð½
™’òõ W6, F†R 7GV Â VÆVÖVçB Fò ÷W" &÷ ÷'F–öæ ÆÇ•&W6—¦R –çFW&æ Â '&™•
this._proportionallyResizeElements.push(this.originalElement.css({ position:
"static", zoom: 1, display: "block" }));Ð’òò fö–B ”R §V× †† &B 6WB F†R Ö &v–ä™•
this.originalElement.css({ margin: this.originalElement.css("margin") });™Ð’òò
fix handlers offset™Ð—F†—2å÷ &÷ ÷'F–öæ ÆÇ•&W6—¦R,™™™Ðthis.handles = o.handles ||
(!$(".ui-resizable-handle", this.element).length ? "e,s,se" : { n: ".ui-
resizable-n", e: ".ui-resizable-e", s: ".ui-resizable-s", w: ".ui-resizable-
w", se: ".ui-resizable-se", sw: ".ui-resizable-sw", ne: ".ui-resizable-ne",
nw: ".ui-resizable-nw" });™™™Ðif(this.handles.constructor === String) {™™Ð–b
(this.handles === "all") {™™this.handles = "n,e,s,w,se,sw,ne,nw™™™ÐÍâ Ò
this.handles.split(",");™™™Ð—F†—2æ† æFÆW2 Ò ·™™™Ð½f÷"†’ Ò ² ’ Â âæÆVæwFƒ² ’²²’™™™Ð½
handle = $.trim(n[i]);™™™Ðhname = "ui-resizable-"+handle™™™Ðaxis = $("<div class='ui-
resizable-handle " + hname + "'> ");™™™// Apply zIndex to all handles - see
#7960™™™Ðaxis.css({ zIndex: o.zIndex }™™™Ð,Ð/TODO : What's going on here?™™™Ðif ("se"
=== handle) {Ð

™™™– †–2æ FD6Æ 72,'V’Ö–6öâ V’Ö–6öâÖw&– 6Ö ÆÂÖF– vöæ Â×6R™™™Ð½Ð/Insert
into internal handles object and append to elementÐ™this.handles[handle] = ".ui-
resizable-"+handle;Ð™this.element.append(axis);™™™Ð½Ð this.._renderAxis =
function(target) {Ð™–f " ’Â †–2Â E ÷2Â Ew& W™™™Ð½F &vWB Ò F &vWB ÇÂ
this.element;Ð™–f÷"†’ –â F†–2æ† æFÆW2’Ð™½if(this.handles[i].constructor ===
String) {Ð™–F†–2æ† æFÆW5¶•Ò Ò B‡F†–2æ† æFÆW5¶•ÒÂ F†–2æVÆVÖVçB’ç6†÷r™™™Ð½Ð/Apply
pad to wrapper element, needed to fix axis position (textarea, inputs,
scrolls)Ð™if (this.elementIsWrapper && this.originalElement[0].nodeName.match(/
textarea|input|select|button/i)) {Ð™– †–2 Ò B‡F†–2æ† æFÆW5¶•ÒÂ F†–2æVÆVÖVçÐ™½òð
Checking the correct pad and borderÐ™– Ew& W" Ò ÷7wÆæWÆçwÇ6WÆçÇ2òçFW7B†’’ ò
axis.outerHeight() : axis.outerWidth();Ð™’òõF†R FF–ær G– R ’ † fR Fò Ç’ãáí
padPos = ["padding",™™™/ne|nw|n/.test(i) ? "Top™™™Ð½se|sw|s/.test(i) ? "Bottom" :Ð
™™™/^e$/.test(i) ? "Right" : "Left"].join("™™™);Ð &vWBæ772‡ E ÷2Â Ew& W™™™½
this._proportionallyResize();™™™Ð½}Ð½/TODO: What's that good for? There's not
anything to be executed leftÐ™if(!$(this.handles[i]).length)™™™Ð6öçF–çVS½™™™Ð½Ð/
TODO: make renderAxis a prototype functionÐ™this._renderAxis(this.element);™™™Ð
this._handles = $(".ui-resizable-handle", this.element)™™™Ð’æF–6 &ÆU6VÆV7F–öâ,™™™Ð½/
Matching axis nameÐ™this._handles.mouseover(function() {™™™Ð–b , F† Bç&W6–¦–ær’™™™½if
(this.className) {Ð™– †–2 Ò F†–2æ6Æ 74æ ÖRæÖ F6,,÷V’×&W6–¦ &ÆRÒ‡6WÇ7wÆæWÆçwÆçÆWÀ
s|w)/i);™™™Ð½}™™™Ð½/Axis, default = seÐ™hat.axis = axis && axis[1] ? axis[1] : "se™™™Ð½)™™™Ð
™//If we want to auto hide the elementsÐ™if (o.autoHide) {™™™ÐF†–2åö† æFÆW2æ†–FR,™™™½
$(this.element)™™™Ð½.addClass("ui-resizable-autohide™™™Ð½)™™™Ð½mouseenter(function()™™™Ð½{™™™Ð–b
(o.disabled) {™™™Ð½retu™™™Ð½™™™Ð½B‡F†–2’ç&VÖ÷fT6Æ 72,'V’×&W6–¦ &ÆRÖ WFö†–FR™™™½
that._handles.show();™™™Ð½}™™™Ð½mouseleave(function()™™™Ð½{™™™Ð–b †òæF–6 &ÆVB™™™½retu™™™Ð½™™™Ð½–b ,
that.resizing) {™™™Ð½$(this).addClass("ui-resizable-autohide™™™Ð½);™™™Ð½
that._handles.hide();™™™Ð½}™™™Ð½}™™™Ð½/Initialize the mouse interactionÐ™this._mouseInit();™™™Ð½
–ÒÓöFW7G&÷“¢ gVæ7F–öâ,’ Ð™this._mouseDestroy();™™™Ð½var wrapper,™™™ÐöFW7G&÷’ Ò
function(exp) {™™™Ð½$(exp).removeClass("ui-resizable ui-resizable-disabled ui-
resizable-resizing")™™™Ð½’ç&VÖ÷fTF F ,'&W6–¦ &ÆR"’ç&VÖ÷fTF F ,'V’Ð
resizable").unbind(".resizable").find(".ui-resizable-handle").remove();™™™Ð½–™™™Ð½/
TODO: Unwrap at same DOM positionÐ™if (this.elementIsWrapper) {™™™Ð
_destroy(this.element);™™™Ð½–w& W" Ò F†–2æVÆVÖVçC½F†–2æ÷&–v–æ ÄVÆVÖVçBæ772‡™™™½
position: wrapper.css("position"),™™™Ð½width: wrapper.outerWidth(),™™™Ð½height:
wrapper.outerHeight(),™™™Ð½top: wrapper.css("top"),™™™Ð½left: wrapper.css("left")™™™Ð
™–Ò’æ–ç6W'D gFW", w& W" ™™™½w& W"ç&VÖ÷fR,™™™½™™™Ð
this.originalElement.css("resize", this.originalResizeStyle);™™™Ð
_destroy(this.originalElement);™™™Ð½return this;™™™ÐöÖ÷W6T6 GW&S¢ gVæ7F–öâ†WfVçB’ ™™™½
var i, handle,™™™Ð½–6 GW&R Ò f Ç6™™™Ð½or (i in this.handles) {™™™Ð½† æFÆR Ò
$(this.handles[i])[0];™™™Ð½––b †† æFÆR ÓÓÒ WfVçBçF &vWB ÇÂ Bæ6öçF –ç2†† æFÆRÂ
event.target)) {™™™Ð½capture = true;™™™Ð½return !this.options.disabled && capture;™™™Ð½
_mouseStart: function(event) {™™™Ð½var curleft, curtop, cursor,™™™Ð½ò Ò F†–2æ÷ F–öç2™™™Ð½
iniPos = this.element.position(),™™™Ð½–VÂ Ò F†–2æVÆVÖVçÐ™½this.resizing = true;™™™Ð½/
bugfix for http://dev.jquery.com/ticket/1749™™™Ð½if ((/
absolute/).test(el.css("position"))) {™™™Ð½–VÂæ772‡² ÷6–F–öã¢ & '6öÇWFR"Â F÷ ¢
el.css("top"), left: el.css("left") });™™™Ð½} else if (el.is(".ui-draggable")) {™™™Ð
el.css({ position: "absolute", top: iniPos.top, left: iniPos.left });™™™Ð½™™™Ð
this._renderProxy();™™™Ð½curleft = num(this.helper.css("left"));™™™Ð½curtop =
num(this.helper.css("top"));™™™Ð½if (o.containment) {™™™Ð7W&ÆVgB ³Ò
$(o.containment).scrollLeft() || 0;™™™Ð½–7W'F÷ ³Ò B†òæ6öçF –æÖVçB’ç67&öÆÅF÷ ,’ ÇÂ
0;™™™Ð½™™™Ð½/Store needed variablesÐ™this.offset = this.helper.offset();™™™Ð½this.position =
{ left: curleft, top: curtop };™™™Ð½this.size = this._helper ? { width:
this.helper.width(), height: this.helper.height() } : { width: el.width(),
height: el.height() };™™™Ð½this.originalSize = this._helper ? { width:
el.outerWidth(), height: el.outerHeight() } : { width: el.width(), height:
el.height() };™™™Ð½this.originalPosition = { left: curleft, top: curtop };™™™Ð
this.sizeDiff = { width: el.outerWidth() - el.width(), height:
el.outerHeight() - el.height() };™™™Ð½this.originalMousePosition = { left:
event.pageX, top: event.pageY };™™™Ð½//Aspect RatioÐ™this.aspectRatio = (typeof
o.aspectRatio === "number") ? o.aspectRatio : ((this.originalSize.width /
this.originalSize.height) || 1);™™™Ð

™cursor = $(".ui-resizable-" +
this.axis).css("cursor");™$("body").css("cursor", cursor === "auto" ?
this.axis + "-resize" : cursor);™el.addClass("ui-resizable-resizing");™
this._propagate("start", event);™return true;™öÖ÷W6TG& s¢ gVæ7F–öâ†WfVçB’ ™// Increase performance, avoid regex™var data;™VÂ Ò F†—2æ†VÇ W"Â &÷ 2 Ò ·™6× Ò
this.originalMousePosition,™– Ò F†—2æ †—™ &WeF÷ Ò F†—2ç ÷6—F–öâçF÷™ &WdÆVgB
= this.position.left,™– &Wev–GF, Ò F†—2ç6—¦Rçv–GF™ &Wd†V–v‡B Ò
this.size.height,™–G, Ò †WfVçBç vU,×6× æÆVgB—ÇÃ™G’ Ò †WfVçBç vU’×6× çF÷ —ÇÃ™
trigger = this._change[a];™if (!trigger) {™&WGW&â f Ç6™/ Calculate the attrs
that will be change™data = trigger.apply(this, [event, dx, dy]);™/ Put this in
the mouseDrag handler since the user can start pressing shift while resizing™
this._updateVirtualBoundaries(event.shiftKey);™if (this._aspectRatio ||
event.shiftKey) {™–F F Ò F†—2å÷W F FU& F–ò†F F Â WfVçB™™data =
this._respectSize(data, event);™this._updateCache(data);™/ plugins callbacks
need to be called first™this._propagate("resize", event);™if
(this.position.top !== prevTop) {™– &÷ 2çF÷ Ò F†—2ç ÷6—F–öâçF÷ ² ' ,™™if
(this.position.left !== prevLeft) {™– &÷ 2æÆVgB Ò F†—2ç ÷6—F–öâæÆVgB ² ' ,™™if
(this.size.width !== prevWidth) {™– &÷ 2çv–GF, Ò F†—2ç6—¦Rçv–GF, ² ' ,™™if
(this.size.height !== prevHeight) {™– &÷ 2æ†V–v‡B Ò F†—2ç6—¦Ræ†V–v‡B ² ' ,™™
el.css(props);™if (!this._helper && this._proportionallyResizeElements.length)
{™–F†—2å÷ &÷ ÷'F–öæ ÆÇ•&W6—¦R,™™/ Call the user callback if the element was
resized™if (! $.isEmptyObject(props)) {™F†—2å÷G&–vvW","&W6—¦R"Â WfVçBÂ
this.ui());™™return false;™öÖ÷W6U7F÷ ¢ gVæ7F–öâ†WfVçB’ ™this.resizing = false;™
var pr, ista, soffseth, soffsetw, s, left, top,™–ò Ò F†—2æ÷ F–öç2Â F† B Ò F†—™½
if(this._helper) {™– " Ò F†—2å÷ &÷ ÷'F–öæ ÆÇ•&W6—¦TVÆVÖVçG™½—7F Ò "æÆVæwF, bb
(/textarea/i).test(pr[0].nodeName);™–6öfg6WF, Ò —7F bb BçV’æ† 567&öÆÂ‡ %³ ÒÂ
"left") /* TODO - jump height */ ? 0 : that.sizeDiff.height;™–6öfg6WGr Ò —7F ò
0 : that.sizeDiff.width;™–2 Ò ² v–GFƒ¢ ‡F† Bæ†VÇ W"çv–GF,,’ Ò 6öfg6WGr’Â
height: (that.helper.height() - soffseth) };™–ÆVgB Ò
(parseInt(that.element.css("left"), 10) + (that.position.left -
that.originalPosition.left)) || null;™–F÷ Ò ‡ '6T–çB‡F† BæVÆVÖVçBæ772,'F÷ "’Â
10) + (that.position.top - that.originalPosition.top)) || null;™––b ,
o.animate) {™™this.element.css($.extend(s, { top: top, left: left }));™™
that.helper.height(that.size.height);™–F† Bæ†VÇ W"çv–GF,‡F† Bç6—¦Rçv–GF,™½–b
(this._helper && !o.animate) {™™this._proportionallyResize();™™
$("body").css("cursor", "auto");™this.element.removeClass("ui-resizable-
resizing");™this._propagate("stop", event);™if (this._helper) {™
this.helper.remove();™™return false;™öÖ÷W F FUf—'GV Ä&÷VæF &–W3¢
function(forceAspectRatio) {™var pMinWidth, pMaxWidth, pMinHeight, pMaxHeight,
b,™–ò Ò F†—2æ÷ F–öç™½ = {™Ö–åv–GFƒ¢ —4çVÖ&W"†òæÖ–åv–GF,’ ò òæÖ–åv–GF, ¢ ™
maxWidth: isNumber(o.maxWidth) ? o.maxWidth : Infinity,™–Ö–ä†V–v‡C¢
isNumber(o.minHeight) ? o.minHeight : 0,™–Ö „†V–v‡C¢ —4çVÖ&W"†òæÖ „†V–v‡B’ ò
o.maxHeight : Infinity};™if(this._aspectRatio || forceAspectRatio) {™òò vR v çB
to create an enclosing box whose aspect ration is the requested one™’òò f—'7BÂ
compute the "projected" size for each dimension based on the aspect ratio and
other dimension™– Ö–åv–GF, Ò "æÖ–ä†V–v‡B ¢ F†—2æ 7 V7E& F–O™½ Ö–ä†V–v‡B Ò
b.minWidth / this.aspectRatio;™– Ö …v–GF, Ò "æÖ „†V–v‡B ¢ F†—2æ 7 V7E& F–O™½
pMaxHeight = b.maxWidth / this.aspectRatio;™––b‡ Ö–åv–GF, â "æÖ–åv–GF,’™™½
b.minWidth = pMinWidth;™–Ý–b‡ Ö–ä†V–v‡B â "æÖ–ä†V–v‡B’™™½b.minHeight =
pMinHeight;™–Ý–b‡ Ö …v–GF, Â "æÖ …v–GF,’™™½b.maxWidth = pMaxWidth;™–b‡ Ö „†V–v‡B
< b.maxHeight) {™b.maxHeight = pMaxHeight;™™this._vBoundaries = b;™™
_updateCache: function(data) {™this.offset = this.helper.offset();™if
(isNumber(data.left)) {™–F†—2ç ÷6—F–öâæÆVgB Ò F F æÆVgC™™if
(isNumber(data.top)) {™–F†—2ç ÷6—F–öâçF÷ Ò F F çF÷™™if
(isNumber(data.height)) {™–F†—2ç6—¦Ræ†V–v‡B Ò F F æ†V–v‡C™™if
(isNumber(data.width)) {™–F†—2ç6—¦Rçv–GF, Ò F F çv–GF™™öÖ÷W F FU& F–ó¢
function(data) {™var cpos = this.position;™D76—¦R Ò F†—2ç6—¦R™ Ò F†—2æ †—™½if
(isNumber(data.height)) {™–F F çv–GF, Ò †F F æ†V–v‡B ¢ F†—2æ 7 V7E& F–ò™½ else
if (isNumber(data.width)) {™–F F æ†V–v‡B Ò †F F çv–GF, ò F†—2æ 7 V7E& F–ò™™if
(a === "sw") {™

```
            ™–F F æÆVgB Ò 7 ÷2æÆVgB ² †76–¦Rçv–GF, Ò F F çv–GF,™½F F çF÷  Ò
null;Ð™Ð if (a === "nw") {ÐF F çF÷  Ò 7 ÷2çF÷  ² †76–¦Ræ†V–v‡B Ò F F æ†V–v‡B™½
data.left = cpos.left + (csize.width - data.width);ÐÐÐeturn data;ÒÐ
_respectSize: function( data ) {Ðvar o = this._vBoundaries,™Ð  Ò F†–2æ †–™Í
ismaxw = isNumber(data.width) && o.maxWidth && (o.maxWidth < data.width),
ismaxh = isNumber(data.height) && o.maxHeight && (o.maxHeight < data.height),™•
isminw = isNumber(data.width) && o.minWidth && (o.minWidth > data.width),
isminh = isNumber(data.height) && o.minHeight && (o.minHeight > data.height),™•
dw = this.originalPosition.left + this.originalSize.width,Ð–F, Ò
this.position.top + this.size.height,Ð–7r Ò ÷7wÆçwÇròçFW7B† ’Â 6, Ò öçwÆæWÀ
n/.test(a);Ðif (isminw) {™ÐF F çv–GF, Ò òæÖ–åv–GF™½Ðif (isminh) {™ÐF F æ†V–v‡B Ò
o.minHeight;Ð™Ð if (ismaxw) {™ÐF F çv–GF, Ò òæÖ …v–GF™½Ðif (ismaxh) {™ÐF F æ†V–v‡B Ò
o.maxHeight;ÐÐÐif (isminw && cw) {™ÐF F æÆVgB Ò Gr Ò òæÖ–åv–GF™½Ðif (ismaxw &&
cw) {Ð–F F æÆVgB Ò Gr Ò òæÖ …v–GF™½Ðif (isminh && ch) {™ÐF F çF÷  Ò F, Ò
o.minHeight;Ð™Ð if (ismaxh && ch) {™ÐF F çF÷  Ò F, Ò òæÖ „†V–v‡™ÐÐ/ fixing jump
error on top/left - bug #2330Ðif (!data.width && !data.height && !data.left &&
data.top) {Ð–F F çF÷  Ò çVÆÃ½ else if (!data.width && !data.height && !
data.top && data.left) {Ð–F F æÆVgB Ò çVÆÃ½ÐÐeturn data;ÒÐ
_proportionallyResize: function() {Ðif (!
this._proportionallyResizeElements.length) {Ð–&WGW&â™ÐÐar i, j, borders,
paddings, prel,Ð–VÆVÖVçB Ò F†–2æ†VÇ W" ÇÂ F†–2æVÆVÖVçÐ½or ( i=0; i <
this._proportionallyResizeElements.length; i++) {Ð– &VÂ Ò
this._proportionallyResizeElements[i];Ð––b , F†–2æ&÷&FW$F–b’™½this.borderDif =
[];Ð™borders = [prel.css("borderTopWidth"), prel.css("borderRightWidth"),
prel.css("borderBottomWidth"), prel.css("borderLeftWidth")];Ð™paddings =
[prel.css("paddingTop"), prel.css("paddingRight"), prel.css("paddingBottom"),
prel.css("paddingLeft")];Ð™for ( j = 0; j < borders.length; j++ )™™Ð
this.borderDif[ j ] = ( parseInt( borders[ j ], 10 ) || 0 ) +
( parseInt( paddings[ j ], 10 ) || 0 );Ð™™™ &VÂæ772‡™½height: (element.height()
- this.borderDif[0] - this.borderDif[2]) || 0,Ð™width: (element.width() -
this.borderDif[1] - this.borderDif[3]) || 0Ð–ÒÐÐ÷&VæFW% &÷‡“¢ gVæ7F–öâ,’ Ð
var el = this.element, o = this.options;Ðthis.elementOffset = el.offset();ÐÐ
if(this._helper) {Ð–F†–2æ†VÇ W" Ò F†–2æ†VÇ W" ÇÂ B,#ÆF–b
style='overflow:hidden;'></div>");Ð–F†–2æ†VÇ W"æ FD6Æ 72‡F†–2åö†VÇ W"’æ772™½
width: this.element.outerWidth() - 1,Ð™height: this.element.outerHeight() - 1,Ð
position: "absolute",Ð™left: this.elementOffset.left +"px",™™™Ðop:
this.elementOffset.top +"px",Ð™zIndex: ++o.zIndex //TODO: Don't modify optiÒnÐÐ½
this.helperÐ™.appendTo("body™™™)ÐdisableSelection();Ðelse {™ÐF†–2æ†VÇ W" Ò
this.element;ÐÐÐÐö6† ævS¢ ½e: function(event, dx) {™Ð&WGW&â ² v–GFƒ¢
this.originalSize.width + dx };Ð™},™Ð: function(event, dx) {™Ðf " 72 Ò
this.originalSize, sp = this.originalPosition;Ð–&WGW&â ² ÆVgC¢ 7 æÆVgB ² G,Â
width: cs.width - dx };Ð™},™Ð: function(event, dx, dy) {™Ðf " 72 Ò
this.originalSize, sp = this.originalPosition;Ð–&WGW&â ² F÷ ¢ 7 çF÷  ² G’Â
height: cs.height - dy };Ð™},™Ð: function(event, dx, dy) {™Ð&WGW&â ² †V–v‡C¢
this.originalSize.height + dy };Ð™},™Ðe: function(event, dx, dy) {™Ð&WGW&â
$.extend(this._change.s.apply(this, arguments), this._change.e.apply(this,
[event, dx, dy]));Ð™},™Ðw: function(event, dx, dy) {™Ð&WGW&â
$.extend(this._change.s.apply(this, arguments), this._change.w.apply(this,
[event, dx, dy]));Ð™},™Ðe: function(event, dx, dy) {™Ð&WGW&â
$.extend(this._change.n.apply(this, arguments), this._change.e.apply(this,
[event, dx, dy]));Ð™},™Ðw: function(event, dx, dy) {™Ð&WGW&â
$.extend(this._change.n.apply(this, arguments), this._change.w.apply(this,
[event, dx, dy]));Ð™ÒÐ÷ &÷  v FS¢ gVæ7F–öâ†âÂ WfVçB’ ½$.ui.plugin.call(this,
n, [event, this.ui()]);Ð™(n !== "resize" && this._trigger(n, event, this.ui()));Ð
–ÒÐ ÇVv–ç3¢ ·ÒÐV“¢ gVæ7F–öâ,’ ½return ™Ð÷&–v–æ ÄVÆVÖVçC¢ F†–2æ÷&–v–æ ÄVÆVÖVçB™Í
element: this.element,Ð–†VÇ W#¢ F†–2æ†VÇ W™™Í ÷6–F–öã¢ F†–2ç ÷6–F–öã™Í6–¦S¢
this.size,Ð–÷&–v–æ Å6–¦S¢ F†–2æ÷&–v–æ Å6–¦™Í÷&–v–æ Å ÷6–F–öã¢
this.originalPositionÐ}÷Ð);Ð*Ð* Resizable ExtensionsÐ*/Ð
$.ui.plugin.add("resizable", "animate", {Ð7F÷ ¢ gVæ7F–öâ, WfVçB ’ ™½var that =
$(this).data("ui-resizable"),Ð
```

™–ò Ò F† Bæ÷ F–öçƒÍ " Ò
that._proportionallyResizeElements,Ð––7F Ò "æÆVæwF, bb ,÷FW‡F &V ð
i).test(pr[0].nodeName),Ð—6öfg6WF, Ò –7F bb BçV’æ† 567&öÆÂ‡ %³ ÒÂ &ÆVgB"’ ò¢
TODO - jump height */ ? 0 : that.sizeDiff.height,Ð—6öfg6WGr Ò –7F ò ¢
that.sizeDiff.width,Ð—7G–ÆR Ò ² v–GFƒ¢ ‡F† Bç6–¦Rçv–GF, Ò 6öfg6WGr’Â †V–v‡C¢
(that.size.height - soffseth) },Ð–ÆVgB Ò ‡ '6T–çB‡F† BæVÆVÖVçBæ772,&ÆVgB"’Â
10) + (that.position.left - that.originalPosition.left)) || null,Ð—F÷ Ò
(parseInt(that.element.css("top"), 10) + (that.position.top -
that.originalPosition.top)) || null;Ðthat.element.animate(ÐBæW‡FVæB‡7G–ÆRÂ F÷
&& left ? { top: top, left: left } : {}), {Ð™duration: o.animateDuration,Ð
easing: o.animateEasing,Ð™step: function()Ð™{Ðf " F F Ò™½width:
parseInt(that.element.css("width"), 10),Ð™™height:
parseInt(that.element.css("height"), 10),Ð™™top:
parseInt(that.element.css("top"), 10),Ð™™left:
parseInt(that.element.css("left"), 10)Ð ÐÓ½–b ‡ " bb "æÆVæwF, ™™™½
$(pr[0]).css({ width: data.width, height: data.height });ÐÐ™Ýòò &÷ v F–ær
resize, and updating values for each animation stepÐ™—F† Bå÷W F FT6 6†R†F F™™½
that._propagate("resize", event);Ð™™™½Ñ÷Ð);Ð$.ui.plugin.add("resizable",
"containment", {Ð7F 'C¢ gVæ7F–öâ,’ ½var element, p, co, ch, cw, width, height,Ð
that = $(this).data("ui-resizable"),Ð–ò Ò F† Bæ÷ F–öçƒÍVÂ Ò F† BæVÆVÖVçBƒÍö2 Ò
o.containment,Ð–6R Ò †ö2 –ç7F æ6Vöb B’ ò ö2ævWBƒ ’ ¢ ,÷ &VçBòçFW7B†ö2’’ ò
el.parent().get(0) : oc;Ðif (!ce) {Ð&WGW&a½Ðthat.containerElement = $(ce);Ðif (/
document/.test(oc) || oc === document) {Ð—F† Bæ6öçF –æW$öfg6WB Ò ² ÆVgC¢ Â
top: 0 };Ð—F† Bæ6öçF –æW% ÷6—F–öâ Ò ² ÆVgC¢ Â F÷ ¢ Ð½F† Bç &VçDF F Ò™½
element: $(document), left: 0, top: 0,Ð™width: $(document).width(), height:
$(document).height() || document.body.parentNode.scrollHeightÐ—Ó½Ð/ i'm a
node, so compute top, left, right, bottomÐelse {ÐVÆVÖVçB Ò B†6R™½ Ò µÓ½
$(["Top", "Right", "Left", "Bottom"]).each(function(i, name) { p[i] =
num(element.css("padding" + name)); });Ð—F† Bæ6öçF –æW$öfg6WB Ò
element.offset();Ð—F† Bæ6öçF –æW% ÷6—F–öâ Ò VÆVÖVçBç ÷6—F–öâ,™½
that.containerSize = { height: (element.innerHeight() - p[3]), width:
(element.innerWidth() - p[1]) };Ð–6ò Ò F† Bæ6öçF –æW$öfg6WC½6, Ò
that.containerSize.height;Ð–7r Ò F† Bæ6öçF –æW%6–¦Rçv–GF™½v–GF, Ò
($.ui.hasScroll(ce, "left") ? ce.scrollWidth : cw);Ð–†V–v‡B Ò
($.ui.hasScroll(ce) ? ce.scrollHeight : ch);Ð—F† Bç &VçDF F Ò™½element: ce,
left: co.left, top: co.top, width: width, height: heightÐ—Ó½ÐÍ&W6–¦S¢
function(event) {Ðvar woset, hoset, isParent, isOffsetRelative,ÐF† B Ò
$(this).data("ui-resizable"),Ð–ò Ò F† Bæ÷ F–öçƒÍ6ò Ò F† Bæ6öçF –æW$öfg6WBÂ 7 Ò
that.position,Ð— & F–ò Ò F† Båö 7 V7E& F–ò ÇÂ WfVçBç6†–gD¶W™Í6÷ Ò ² F÷ £ Â
left:0 }, ce = that.containerElement;Ðif (ce[0] !== document && (/
static/).test(ce.css("position"))) {Ð–6÷ Ò 6Ó½Ðif (cp.left < (that._helper ?
co.left : 0)) {Ð—F† Bç6–¦Rçv–GF, Ò F† Bç6–¦Rçv–GF, ² ‡F† Båö†VÇ W" ò
(that.position.left - co.left) : (that.position.left - cop.left));Ð––b ‡ & F–ò’
{Ð™that.size.height = that.size.width / that.aspectRatio;ÐF† Bç ÷6—F–öâæÆVgB Ò
o.helper ? co.left : 0;Ð½Ðif (cp.top < (that._helper ? co.top : 0)) {Ð
that.size.height = that.size.height + (that._helper ? (that.position.top -
co.top) : that.position.top);Ð––b ‡ & F–ò’™™½that.size.width = that.size.height
* that.aspectRatio;Ð™ÝF† Bç ÷6—F–öâçF÷ Ò F† Båö†VÇ W" ò 6òçF÷ ¢ ™½Ð
that.offset.left = that.parentData.left+that.position.left;Ðthat.offset.top =
that.parentData.top+that.position.top;Ðwoset = Math.abs((that._helper ?
that.offset.left - cop.left : (that.offset.left - cop.left)) +
that.sizeDiff.width);Ðhoset = Math.abs((that._helper ? that.offset.top -
cop.top : (that.offset.top - co.top)) + that.sizeDiff.height);ÐisParent =
that.containerElement.get(0) === that.element.parent().get(0);Ð
isOffsetRelative = /relative|
absolute/.test(that.containerElement.css("position"));Ðif (isParent &&
isOffsetRelative) {Ð—v÷6WB ÓÒ Ö F,æ '2, F† Bç &VçDF F æÆVgB ™½Ðif (woset +
that.size.width >= that.parentData.width) {Ð—F† Bç6–¦Rçv–GF, Ò
that.parentData.width - woset;Ð––b ‡ & F–ò’™™½that.size.height =
that.size.width / that.aspectRatio;Ð

™™Ð–Ðif (hoset + that.size.height >=
that.parentData.height) {™Ð–F† Bç6–¦Ræ†V–v‡B Ò F† Bç &VçDF F æ†V–v‡B Ò †÷6W™½–b
(pRatio) {™Ð™that.size.width = that.size.height * that.aspectRatio;™Ð™Ò™Ð™7F÷ ¢
function(){™Ðvar that = $(this).data("ui-resizable");™Ðò Ò F† Bæ÷ F–öç™Í6ò Ò
that.containerOffset,™Ð–6÷ Ò F† Bæ6öçF –æW% ÷6–F–öç™Í6R Ò F† Bæ6öçF –æW$VÆVÖVçB™Í
helper = $(that.helper),™Ð–†ò Ò †VÇ W"æöfg6WB,™Ír Ò †VÇ W"æ÷WFW%v–GF,,’ Ò
that.sizeDiff.width,™Ð–, Ò †VÇ W"æ÷WFW$†V–v‡B,’ Ò F† Bç6–¦TF–fbæ†V–v‡™½f
(that._helper && !o.animate && (/relative/).test(ce.css("position"))) {™Ð•
$(this).css({ left: ho.left - cop.left - co.left, width: w, height: h });™Ð™Ðif
(that._helper && !o.animate && (/static/).test(ce.css("position"))) {™Ð•
$(this).css({ left: ho.left - cop.left - co.left, width: w, height: h });™Ð™Ð™});Ð
$.ui.plugin.add("resizable", "alsoResize", {™Ð7F 'C¢ gVæ7F–öâ ,’ ™½var that =
$(this).data("ui-resizable"),™Ð–ò Ò F† Bæ÷ F–öç™Í÷7F÷&R Ò gVæ7F–öâ †W‡ ’™™½
$(exp).each(function() {™Ð™–f " VÂ Ò B‡F†–™™½VÂæF F ,'V’×&W6–¦ &ÆRÖ Ç6÷&W6–¦R"™™½
width: parseInt(el.width(), 10), height: parseInt(el.height(), 10),™Ð™™™left:
parseInt(el.css("left"), 10), top: parseInt(el.css("top"), 10)™Ð™–™™½÷™™½f
(typeof(o.alsoResize) === "object" && !o.alsoResize.parentNode) {™Ð––b
(o.alsoResize.length) { o.alsoResize = o.alsoResize[0];
_store(o.alsoResize); }™Ð–VÇ6R ² BæV 6,†òæ Ç6õ&W6–¦RÂ gVæ7F–öâ †W‡ ’
{ _store(exp); }); }™Ð}else{™Ð÷7F÷&R†òæ Ç6õ&W6–¦R™™½™™™&W6–¦S¢ gVæ7F–öâ †WfVçBÂ
ui) {™Ðvar that = $(this).data("ui-resizable");™Ðò Ò F† Bæ÷ F–öç™Í÷2 Ò
that.originalSize,™Ð–÷ Ò F† Bæ÷&–v–æ Å ÷6–F–öç™ÍFVçF Ò™™height:
(that.size.height - os.height) || 0, width: (that.size.width - os.width) || 0,™Ð™
top: (that.position.top - op.top) || 0, left: (that.position.left - op.left)
|| 0™Ð–™™™iö Ç6õ&W6–¦R Ò gVæ7F–öâ †W‡ Â 2’™™½$(exp).each(function()™™™Ðif " VÂ Ò
$(this), start = $(this).data("ui-resizable-alsoresize"), style = {},™Ð™™™css = c
&& c.length ? c : el.parents(ui.originalElement[0]).length ? ["width",
"height"] : ["width", "height", "top", "left"];™Ð™’BæV 6,†772Â gVæ7F–öâ †’Â &÷ ’
{™Ð™™™var sum = (start[prop]||0) + (delta[prop]||0);™Ðif (sum && sum >= 0) {™Ð™™™™Ð
style[prop] = sum || null;™Ð™™™}™Ð™™™™

™–F† Bç6–¦Rçv–GF, Ò æWuv–GF™½F† Bç6–¦Ræ†V–v‡B Ò æWt†V–v‡C™½
that.position.left = op.left - ox;Ð} else {Ð–b , æWt†V–v‡B Ò w&–E’ â ’™™½
that.size.height = newHeight;Ð™that.position.top = op.top - oy;Ð VÇ6R™½
that.size.height = gridY;Ð™that.position.top = op.top + os.height - gridY;Ð–b
(newWidth - gridX > 0) {Ð™that.size.width = newWidth;Ðthat.position.left =
op.left - ox;Ð–Ò VÇ6R™½that.size.width = gridX;Ðthat.position.left = op.left +
os.width - gridX;Ð–}Ð});Ð})(jQuery);Ðfunction($, undefined) {Ð
$.widget("ui.selectable", $.ui.mouse, {ÐfW'6–öã¢ # ã ãB"Í÷ F–öç3¢ ™½appendTo:
"body",ÐautoRefresh: true,Ðdistance: 0,Ðfilter: "*",Ðtolerance: "touch",ÐØ/
callbacksÐselected: null,Ðselecting: null,Ðstart: null,Ðstop: null,Ðunselected:
null,Ðunselecting: null–ÒÍö7&V FS¢ gVæ7F–öâ,’ ™½var selectees,ÐF† B Ò F†–Ð½
this.element.addClass("ui-selectable");Ðthis.dragged = false;ÐØ/ cache selectee
children based on filterÐthis.refresh = function() {Ð6VÆV7FVW2 Ò
$(that.options.filter, that.element[0]);Ð–6VÆV7FVW2æ FD6Æ 72,'V’×6VÆV7FVR"™½
selectees.each(function() {Ð™var $this = $(this);Ð ÷2 Ò GF†–2æöfg6WB,™™½
$.data(this, "selectable-item", {Ð™–VÆVÖVçC¢ F†™™ÍFVÆVÖVçC¢ GF†™™ÍÆVgC¢ ÷2æÆVgB™™Í
top: pos.top,Ð™–&–v‡C¢ ÷2æÆVgB ² GF†–2æ÷WFW%v–GF,™™Í&÷GFöÓ¢ ÷2çF÷ ²
$this.outerHeight(),Ð™–7F 'G6VÆV7FVC¢ f ÇÓRÍ6VÆV7FVC¢ GF†–2æ† 46Æ 72,'V’Ð
selected"),Ð™–6VÆV7F–æs¢ GF†–2æ† 46Æ 72,'V’×6VÆV7F–ær™™™ÍVç6VÆV7F–æs¢
$this.hasClass("ui-unselecting")Ð™}};Ð™½;Ðthis.refresh();ÐØthis.selectees =
selectees.addClass("ui-selectee");Ðthis._mouseInit();ÐØthis.helper = $("<div
class='ui-selectable-helper'> ");ÐÒÓöFW7G&÷“¢ gVæ7F–öâ,’ ™½this.selecteesÐ
™’ç&VÖ÷fT6Æ 72,'V’×6VÆV7FVR™‘ç&VÖ÷fTF F ,'6VÆV7F &ÆRÖ–FVÒ"™™½his.elementÐ
™’ç&VÖ÷fT6Æ 72,'V’×6VÆV7F &ÆR V’×6VÆV7F &ÆRÖF–6 &ÆVB"™™½his._mouseDestroy();ÐØ
_mouseStart: function(event) {Ðvar that = this;Ð÷ F–öç2 Ò F†–2æ÷ F–öçÐ½
this.opos = [event.pageX, event.pageY];Ðif (this.options.disabled) {Ð&WGW&ãØØÐ
this.selectees = $(options.filter, this.element[0]);Ðthis._trigger("start",
event);Ð$(options.appendTo).append(this.helper);ÐØ/ position helper (lasso)Ð
this.helper.css({Ð’&ÆVgB#¢ WfVçBç vU™Í'F÷ #¢ WfVçBç vU™Í'v–GF,#¢ ™Í&†V–v‡B#¢
™});ÐØif (options.autoRefresh) {ÐF†–2ç&Vg&W6,™™™½Ðthis.selectees.filter(".ui-
selected").each(function() {Ð–f " 6VÆV7FVR Ò BæF F ‡F†–2Â '6VÆV7F &ÆRÖ–FVÒ"™™½
selectee.startselected = true;Ð––b , WfVçBæÖWF ¶W’ bb WfVçBæ7G&Ä¶W’’™™½selectee.
$element.removeClass("ui-selected");Ð™selectee.selected = false;Ðselectee.
$element.addClass("ui-unselecting");Ð™selectee.unselecting = true;ÐØ/ selectable
UNSELECTING callbackÐ™that._trigger("unselecting", event, {ÐVç6VÆV7F–æs¢
selectee.elementÐ™});™™™Ó;ÐØ(event.target).parents().addBack().each(function() {Ð
var doSelect,Ð™selectee = $.data(this, "selectable-item");Ðb ‡6VÆV7FVR’™™½
doSelect = (!event.metaKey && !event.ctrlKey) || !selectee.
$element.hasClass("ui-selected");Ð™selectee.$elementÐç&VÖ÷fT6Æ 72†Fõ6VÆV7B ò 'V’Ð
unselecting" : "ui-selected")Ð™’æ FD6Æ 72†Fõ6VÆV7B ò 'V’×6VÆV7F–ær" ¢ 'V’Ð
unselecting");Ð™selectee.unselecting = !doSelect;Ðselectee.selecting = doSelect;Ð
selectee.selected = doSelect;Ð™// selectable (UN)SELECTING callbackÐif
(doSelect) {Ð™–F† Bå÷G&–vvW","6VÆV7F–ær"Â WfVçBÂ™™™½selecting: selectee.elementÐ“½
™™} else {ÐF† Bå÷G&–vvW","Vç6VÆV7F–ær"Â WfVçBÂ™™™½unselecting: selectee.elementÐ™™½Ð
return false;Ð–}};ÐØÓöÖ÷W6TG& s¢ gVæ7F–öâ†WfVçB’ ™Ðthis.dragged = true;ÐØif
(this.options.disabled) {Ð–&WGW&ãØØvar tmp;ÐF† B Ò F†–2Í÷ F–öç2 Ò F†–2æ÷ F–öçÍ
x1 = this.opos[0],Ð–“ Ò F†–2æ÷ ÷5³ ÓÍƒ" Ò WfVçBç vU™Í"" Ò WfVçBç vUÐ½if (x1
> x2) { tmp = x2; x2 = x1; x1 = tmp; }Ðif (y1 > y2) { tmp = y2; y2 = y1; y1 =
tmp; }Ðthis.helper.css({left: x1, top: y1, width: x2-x1, height: y2-y1});ÐØ
this.selectees.each(function() {Ð–f " 6VÆV7FVR Ò BæF F ‡F†–2Â '6VÆV7F &ÆRÐ
item"),Ð™hit = false;Ð÷ &WfVçB †VÇ W" g&öÒ &V–ær 6VÆV7FVB –b VæEFó¢
selectableÐ––b , 6VÆV7FVR ÇÂ 6VÆV7FVRæVÆVÖVçB ÓÓÒ F† BæVÆVÖVçE³ Ò’™™½return;ÐØ–b
(options.tolerance === "touch") {Ð™hit = (!(selectee.left > x2 ||
selectee.right < x1 || selectee.top > y2 || selectee.bottom < y1));Ð–Ò VÇ6R –b
(options.tolerance === "fit") {Ð™hit = (selectee.left > x1 && selectee.right <
x2 && selectee.top > y1 && selectee.bottom < y2);ÐØÝ–b ††–B’™™½// SELECTÐif
(selectee.selected) {Ð™–6VÆV7FVRâFVÆVÖVçBç&VÖ÷fT6Æ 72,'V’×6VÆV7FVB™™™½
selectee.selected = false;Ð™}Øif (selectee.unselecting)™™{Ð6VÆV7FVRà
$element.removeClass("ui-unselecting");Ð™–6VÆV7FVRçVç6VÆV7F–ær Ò f ÇÓ3™™½Øif (!
selectee.selecting) {Ð

™™—6VÆV7FVRâFVÆVÖVçBæ FD6Æ 72,'V’×6VÆV7F–ær™™½
selectee.selecting = true;Ð™’òò 6VÆV7F &ÆR 4TÄT5D”är 6 ÆÆ&™™½
that._trigger("selecting", event, {Ð™™selecting: selectee.element™™Ð½Ð VÇ6R™™½// UNSELECTÐ™if (selectee.selecting)™™Ð–b ,†WfVçBæÖWF ¶W’ ÇÂ WfVçBæ7G&Ä¶W’’ bb selectee.startselected) {Ð™™selectee.$element.removeClass("ui-selecting");Ð selectee.selecting = false;Ð™™selectee.$element.addClass("ui-selected");Ð selectee.selected = true;Ð™—Ò VÇ6R™™½selectee.$element.removeClass("ui-selecting");Ð™™selectee.selecting = false;Ð™™if (selectee.startselected) {Ð™™6VÆV7FVRà $element.addClass("ui-unselecting");Ð™™—6VÆV7FVRçVç6VÆV7F–ær Ò G™™VS½Ð/ selectable UNSELECTING callbackÐ™™that._trigger("unselecting", event, {Ð unselecting: selectee.element™™™

™–7W'&VçD—FVÒ Ò
$(event.target);ÐÐif(!currentItem) {Ð&WGW&â f Ç6S½if(this.options.handle && !
overrideHandle) {Ð'B‡F†—2æ÷ F–öç2æ† æFÆRÂ
currentItem).find("*").addBack().each(function() {Ðif(this === event.target) {Ð
validHandle = true;Ð}Ð½–b, f Æ–D† æFÆR'½return false;ÐÐthis.currentItem =
currentItem;Ðthis._removeCurrentsFromItems();Ðreturn true;ÐÐöÖ÷W6U7F 'C¢
function(event, overrideHandle, noActivation) {Ðvar i, body,Ðò Ò F†—2æ÷ F–öçÐ½
this.currentContainer = this;Ð//We only need to call refreshPositions, because
the refreshItems call has been moved to mouseCaptureÐthis.refreshPositions();ÐÐ/
Create and append the visible helperÐthis.helper = this._createHelper(event);ÐÐ/
Cache the helper sizeÐthis._cacheHelperProportions();ÐÐ'Ð* - Position
generation -Ð * This block generates everything position related - it's the
core of draggables.Ð *ÐÐ/Cache the margins of the original elementÐ
this._cacheMargins();Ð//Get the next scrolling parentÐthis.scrollParent =
this.helper.scrollParent();Ð//The element's absolute position on the page
minus marginsÐthis.offset = this.currentItem.offset();Ðthis.offset = {ÐF÷ ¢
this.offset.top - this.margins.top,Ð–ÆVgC¢ F†—2æöfg6WBæÆVgB Ò F†—2æÖ &v–ç2æÆVgM
'}ÐÐ.extend(this.offset, {Ð6Æ–6³¢ ² òõv†W&R F†R 6Æ–6² † VæVBÂ &VÆ F—fR Fò F†R
elementÐ'left: event.pageX - this.offset.left,Ðtop: event.pageY - this.offset.topÐ
'—ÒÍ &VçC¢ F†—2åövWE &VçDöfg6WB,'Í&VÆ F—fS¢ F†—2åövWE&VÆ F—fTöfg6WB,' òõF†—2
is a relative to absolute position minus the actual position calculation -
only used for relative positioned helperÐ})ÐÐ/ Only after we got the offset,
we can change the helper's position to absoluteÐ// TODO: Still need to figure
out a way to make relative sorting possibleÐthis.helper.css("position",
"absolute");Ðthis.cssPosition = this.helper.css("position");ÐÐ/Generate the
original positionÐthis.originalPosition = this._generatePosition(event);Ð
this.originalPageX = event.pageX;Ðthis.originalPageY = event.pageY;ÐÐ/Adjust
the mouse offset relative to the helper if "cursorAt" is suppliedÐ(o.cursorAt
&& this._adjustOffsetFromHelper(o.cursorAt));Ð//Cache the former DOM positionÐ
this.domPosition = { prev: this.currentItem.prev()[0], parent:
this.currentItem.parent()[0] };Ð//If the helper is not the original, hide the
original so it's not playing any role during the drag, won't cause anything
bad this wayÐif(this.helper[0] !== this.currentItem[0]) {Ð
this.currentItem.hide();ÐÐÐ/Create the placeholderÐthis._createPlaceholder();ÐÐ/
Set a containment if given in the optionsÐif(o.containment) {Ð
this._setContainment();ÐÐif(o.cursor && o.cursor !== "auto") { // cursor
optionÐ–&öG' Ò F†—2æFö7VÖVçBæf–æB, &&öG'" Ð½òò 7W ÷'C¢]F†—2ç7F÷&VD7W'6÷" Ò
body.css("cursor");Ð–&öG'æ772, &7W'6÷""Â òæ7W'6÷" Ð½F†—2ç7F÷&VE7G–ÆW6†VWB Ò
$("<style>*{ cursor: "+o.cursor+" !important; }</style>").appendTo(body);ÐÐÐ
if(o.opacity) { // opacity optionÐ––b ‡F†—2æ†VÇ W"æ772,&÷ 6—G'"'½
this._storedOpacity = this.helper.css("opacity");Ð—ÝF†—2æ†VÇ W"æ772,&÷ 6—G'"Â
o.opacity);ÐÐif(o.zIndex) { // zIndex optionÐ–b ‡F†—2æ†VÇ W"æ772,'¤–æFW,"'½
this._storedZIndex = this.helper.css("zIndex");Ð—ÝF†—2æ†VÇ W"æ772,'¤–æFW,"Â
o.zIndex);ÐÐÐ/Prepare scrollingÐif(this.scrollParent[0] !== document &&
this.scrollParent[0].tagName !== "HTML") {Ð—F†—2æ÷fW&fÆ÷töfg6WB Ò
this.scrollParent.offset();ÐÐÐ/Call callbacksÐthis._trigger("start", event,
this._uiHash());Ð//Recache the helper sizeÐif(!this._preserveHelperProportions)
{Ð—F†—2åö6 6†T†VÇ W% &÷ ÷'F–öç2,ÐÐÐ/Post "activate" events to possible
containersÐif(!noActivation) {Ðf÷" , ' Ò F†—2æ6öçF –æW'2æÆVæwF, Ò ² ' ãÒ ²
i--) {Ð™this.containers[i]._trigger("activate", event,
this._uiHash(this));Ð—ÐÐ/Prepare possible droppablesÐif($.ui.ddmanager) {Ð
$.ui.ddmanager.current = this;ÐÐif ($.ui.ddmanager && !o.dropBehaviour) {Ð
$.ui.ddmanager.prepareOffsets(this, event);ÐÐthis.dragging = true;Ð
this.helper.addClass("ui-sortable-helper");Ðthis._mouseDrag(event); //Execute
the drag once - this causes the helper not to be visible before getting its
correct positionÐreturn true;ÐÐöÖ÷W6TG& s¢ gVæ7F–öâ†WfVçB' ½var i, item,
itemElement, intersection,Ð–ò Ò F†—2æ÷ F–öç2Í67&öÆÆVB Ò f Ç6Ð½/Compute the
helpers positionÐthis.position = this._generatePosition(event);Ð
this.positionAbs = this._convertPositionTo("absolute");Ðif (!
this.lastPositionAbs) {Ð

™–F†–2æÆ 7E ÷6–F–öä '2 Ò F†–2ç ÷6–F–öä '3™ÐÐ/Do scrolling™Ð
if(this.options.scroll) {™Ð–-b‡F†–2ç67&öÆÅ &VçE³ Ò ÓÒ Fö7VÖVçB bb
this.scrollParent[0].tagName !== "HTML") {™Ðif((this.overflowOffset.top +
this.scrollParent[0].offsetHeight) - event.pageY < o.scrollSensitivity) {™Ð•
this.scrollParent[0].scrollTop = scrolled = this.scrollParent[0].scrollTop +
o.scrollSpeed;™Ð} else if(event.pageY - this.overflowOffset.top <
o.scrollSensitivity) {™Ð–F†–2ç67&öÆÅ &VçE³ Òç67&öÆÅF÷ Ò 67&öÆÆVB Ò
this.scrollParent[0].scrollTop - o.scrollSpeed;™Ð™Ð}™Ðif((this.overflowOffset.left
+ this.scrollParent[0].offsetWidth) - event.pageX < o.scrollSensitivity) {™Ð•
this.scrollParent[0].scrollLeft = scrolled = this.scrollParent[0].scrollLeft
+ o.scrollSpeed;™Ð} else if(event.pageX - this.overflowOffset.left <
o.scrollSensitivity) {™Ð–F†–2ç67&öÆÅ &VçE³ Òç67&öÆÄÆVgB Ò 67&öÆÆVB Ò
this.scrollParent[0].scrollLeft - o.scrollSpeed;™Ð™Ð}™Ð VÇ6RÐ½if(event.pageY -
$(document).scrollTop() < o.scrollSensitivity) {™Ð–67&öÆÆVB Ò
$(document).scrollTop($(document).scrollTop() - o.scrollSpeed);™Ð} else
if($(window).height() - (event.pageY - $(document).scrollTop()) <
o.scrollSensitivity) {™Ð–67&öÆÆVB Ò
$(document).scrollTop($(document).scrollTop() + o.scrollSpeed);™Ð™Ð}™Ð
if(event.pageX - $(document).scrollLeft() < o.scrollSensitivity) {™Ð–67&öÆÆVB Ò
$(document).scrollLeft($(document).scrollLeft() - o.scrollSpeed);™Ð} else
if($(window).width() - (event.pageX - $(document).scrollLeft()) <
o.scrollSensitivity) {™Ð–67&öÆÆVB Ò
$(document).scrollLeft($(document).scrollLeft() + o.scrollSpeed);™Ð™Ð™Ð™Ð
if(scrolled !== false && $.ui.ddmanager && !o.dropBehaviour) {™Ð™
$.ui.ddmanager.prepareOffsets(this, event);™Ð™Ð™Ð/Regenerate the absolute
position used for position checks™Ðthis.positionAbs =
this._convertPositionTo("absolute");™Ð//Set the helper position™Ðif(!
this.options.axis || this.options.axis !== "y") {™Ð–F†–2æ†VÇ W%³ Òç7G–ÆRæÆVgB Ò
this.position.left+"px";™Ð™Ð}™Ðif(!this.options.axis || this.options.axis !== "x") {™Ð
this.helper[0].style.top = this.position.top+"px";™Ð™Ð™Ð™Ð/Rearrange™Ðfor (i =
this.items.length - 1; i >= 0; i--) {™Ð'òô6 6†R f &– &ÆW2 æB –çFW'6V7F–öâÂ
continue if no intersection™Ð–-FVÒ Ò F†–2æ–FV×5¶•Ó½–FVÔVÆVÖVçB Ò –FVÒæ–FVÕ³ Ó½
intersection = this._intersectsWithPointer(item);™Ð–-b , –çFW'6V7F–öâ'™½continue;™Ð
™ÐÝòò öæÇ' WB F†R Æ 6V†öÆFW" –ç6–FR F†R 7W'&VçB 6öçF –æW"Â 6¶– ™ÍÍòò –FV×2
from other containers. This works because when moving™Ð'òò â –FVÒ g&öÒ öæR
container to another the™Ð'òò 7W'&VçD6öçF –æW" –2 7v–F6†VB &Vf÷&R F†R
placeholder is moved.™Ð'™Ýòò v–F†÷WB F†–2Â Ö÷f–ær –FV×2 –â '7V"×6÷'F &ÆW2" 6 â
cause™Ð'òò F†R Æ 6V†öÆFW" Fò ¦–GFW" &VWGvVVâ F†R ÷WFW" æB –ææW" 6öçF –æW™í–b
(item.instance !== this.currentContainer) {™Ðcontinue™Ð™Ðòò 6 ææ÷B –çFW'6V7B v–F,
itself™Ð'òò æò W6VÆW72 7F–öç2 F† B † fR &VVâ FöæR &Vf÷&™]òò æò 7F–öâ –b F†R
item moved is the parent of the item checked™Ð–-b †–FVÔVÆVÖVçB ÓÒ
this.currentItem[0] &&™Ðthis.placeholder[intersection === 1 ? "next" : "prev"]()
[0] !== itemElement &&™Ð!$.contains(this.placeholder[0], itemElement) &&™Ð™Ð™Ð
(this.options.type === "semi-dynamic" ? !$.contains(this.element[0],
itemElement) : true)™Ð''™Ð%this.direction = intersection === 1 ? "down" : "up™Ð™Ð™Ðif
(this.options.tolerance === "pointer" || this._intersectsWithSides(item)) {™Ð•
this._rearrange(event, item);™Ð™Ð} else {™Ð'&V™Ð™Ð™Ð™Ðthis._trigger("change", event,
this._uiHash());™Ðbreak;™Ð™Ð™Ð™Ð

™™¥F†—2ç&WfW'F–ær Ò
true;Ð’B‡F†—2æ†VÇ W"’æ æ–Ö FR, æ–Ö F–öâÂ '6T–çB‡F†—2æ÷ F–öç2ç&WfW'BÂ ’ ÇÂ
500, function() {Ð™that._clear(event)÷Ð™½ else {ÐF†—2åö6ÆV "†WfVçBÂ
noPropagation);ÐÐÐeturn falseÐÐÉ6 æ6VÃ¢ gVæ7F–öâ,’ Ðif(this.dragging) {ÐÐ
this._mouseUp({ target: null });Ð––b‡F†—2æ÷ F–öç2æ†VÇ W" ÓÓÒ &÷&–v–æ Â"’™½
this.currentItem.css(this._storedCSS).removeClass("ui-sortable-helper");Ð—Ò
else {Ð™this.currentItem.show()ÐÉòõ ÷7B FV 7F—f F–ær WfVçG2 Fò 6öçF –æW™=f÷"
(var i = this.containers.length - 1; i >= 0; i--){Ð™
this.containers[i]._trigger("deactivate", null, this._uiHash(this));Ð™
if(this.containers[i].containerCache.over) {Ð™•
this.containers[i]._trigger("out", null, this._uiHash(this));Ð™•
this.containers[i].containerCache.over = 0;Ð™ÐÉif (this.placeholder) {Ðòð
$(this.placeholder[0]).remove(); would have been the jQuery way -
unfortunately, it unbinds ALL events from the original node!Ð•
if(this.placeholder[0].parentNode) {Ð™
this.placeholder[0].parentNode.removeChild(this.placeholder[0]);Ð™¥
if(this.options.helper !== "original" && this.helper &&
this.helper[0].parentNode) {Ð™this.helper.remove()ÐÉBæW‡FVæB‡F†—2Â™½helper:
null,Ð™dragging: false,Ðeverting: false,ÐnoFinalSort: nullÐÒ½
if(this.domPosition.prev) {Ð™$(this.domPosition.prev).after(this.currentItem)÷Ð
else {Ð™$(this.domPosition.parent).prepend(this.currentItem)÷ÐÐeturn thisÐÒÉ
serialize: function(o) {Ðvar items = this._getItemsAsjQuery(o && o.connected),Ð
str = [];Ðo = o || {};ÐÐ(items).each(function() {Ðf " &W2 Ò ,B†òæ—FVÒ ÇÂ
this).attr(o.attribute || "id") || "").match(o.expression || (/(.+)[\-=_](.
+)/));Ð––b ‡&W2’™½str.push((o.key || res[1]+"[]")+"="+(o.key && o.expression ?
res[1] : res[2]));Ð¥}ÐÐif(!str.length && o.key) {Ð7G"ç W6,†òæ¶W’ ² #Ò"™ÐÐeturn
str.join("&");ÐÒÉFô '& “¢ gVæ7F–öâ†ò’ Ðvar items = this._getItemsAsjQuery(o &&
o.connected),Ð—&WB Ò µÐ½ = o || {};ÐÐitems.each(function() { ret.push($(o.item
|| this).attr(o.attribute || "id") || ""); });Ðreturn retÐÒÉòc &R 6 &VgVÂ v–F,
the following core functions */Ðö–çFW'6V7G5v–Fƒ¢ gVæ7F–öâ†–FVÒ’ Ðvar x1 =
this.positionAbs.left,Ð—ƒ" Ò ƒ ² F†—2æ†VÇ W% &÷ ÷'F–öç2çv–GF™Í“ Ò
this.positionAbs.top,Ð—“" Ò “ ² F†—2æ†VÇ W% &÷ ÷'F–öç2æ†V–v‡ÐÍÂ Ò —FVÒæÆVgÐÍ"
= l + item.width,Ð—B Ò —FVÒçF÷™Í" Ò B ² —FVÒæ†V–v‡ÐÍG”6Æ–6² Ò
this.offset.click.top,Ð–G„6Æ–6² Ò F†—2æöfg6WBæ6Æ–6²æÆVgÐÍ—4÷fW$VÆVÖVçD†V–v‡B Ò
(this.options.axis === "x") || ((y1 + dyClick) > t && (y1 + dyClick) <
b),Ð––4÷fW$VÆVÖVçEv–GF, Ò , F†—2æ÷ F–öç2æ †—2 ÓÓÒ ''" ’ ÇÂ , , ƒ ² G„6Æ–6² ’
> l && (x1 + dxClick) < r),Ð––4÷fW$VÆVÖVçB Ò —4÷fW$VÆVÖVçD†V–v‡B bb
isOverElementWidth;Ðif (this.options.tolerance === "pointer" |¶Ð
this.options.forcePointerForContainers ||Ð’‡F†—2æ÷ F–öç2çFöÆW& æ6R ÓÒ
"pointer" && this.helperProportions[this.floating ? "width" : "height"] >
item[this.floating ? "width" : "height"])Ð) {Ð&WGW&â —4÷fW$VÆVÖVçC½ else {ÐÐ
return (l < x1 + (this.helperProportions.width / 2) && // Right HalfÐ™x2 -
(this.helperProportions.width / 2) < r && // Left HalfÐ™t < y1 +
(this.helperProportions.height / 2) && // Bottom HalfÐ™y2 -
(this.helperProportions.height / 2) < b); // Top HalfÐ}ÐÉ
_intersectsWithPointer: function(item) {Ðvar isOverElementHeight =
(this.options.axis === "x") || isOverAxis(this.positionAbs.top +
this.offset.click.top, item.top, item.height),Ð––4÷fW$VÆVÖVçEv–GF, Ò
(this.options.axis === "y") || isOverAxis(this.positionAbs.left +
this.offset.click.left, item.left, item.width),Ð––4÷fW$VÆVÖVçB Ò
isOverElementHeight && isOverElementWidth,Ð—fW'F–6 ÄF—&V7F–öâ Ò
this._getDragVerticalDirection(),Ð–†÷&—¦öçF ÄF—&V7F–öâ Ò
this._getDragHorizontalDirection();Ðif (!isOverElement) {Ð&WGW&â f Ç6SÐeturn
this.floating ?Ð’, ,††÷&—¦öçF ÄF—&V7F–öâ bb †÷&—¦öçF ÄF—&V7F–öâ ÓÓÒ '&–v‡B"’ ÇÂ
verticalDirection === "down") ? 2 : 1)Ð“¢ , fW'F–6 ÄF—&V7F–öâ bb
(verticalDirection === "down" ? 2 : 1));ÐÒÉö–çFW'6V7G5v–F…6–FW3¢
function(item) {Ðvar isOverBottomHalf = isOverAxis(this.positionAbs.top +
this.offset.click.top, item.top + (item.height/2), item.height),Ð•
isOverRightHalf = isOverAxis(this.positionAbs.left + this.offset.click.left,
item.left + (item.width/2), item.width),Ð

™–fW'F–6 ÄF–&V7F–öâ Ò
this._getDragVerticalDirection(),Ð–†÷&–¦öçF ÄF–&V7F–öâ Ò
this._getDragHorizontalDirection();Ðif (this.floating && horizontalDirection) {Ð
return ((horizontalDirection === "right" && isOverRightHalf) ||
(horizontalDirection === "left" && !isOverRightHalf));Ð} else {Ð&WGW&â
verticalDirection && ((verticalDirection === "down" && isOverBottomHalf) ||
(verticalDirection === "up" && !isOverBottomHalf));ÐÐÒÐ
_getDragVerticalDirection: function() {Ðvar delta = this.positionAbs.top -
this.lastPositionAbs.top;Ðreturn delta !== 0 && (delta > 0 ? "down" : "up");ÒÐ
_getDragHorizontalDirection: function() {Ðvar delta = this.positionAbs.left -
this.lastPositionAbs.left;Ðreturn delta !== 0 && (delta > 0 ? "right" :
"left");ÐÒÐ&Vg&W6ƒ¢ gVæ7F–öâ†WfVçB’ ½this._refreshItems(event);Ð
this.refreshPositions();Ðreturn this;ÒÐö6öææV7Ev–Fƒ¢ gVæ7F–öâ,’ ½var options =
this.options;Ðreturn options.connectWith.constructor === String ?
[options.connectWith] : options.connectWith;ÐÒÐövWD–FV×4 6¥ VW'“¢
function(connected) {Ðvar i, j, cur, inst;Ð–FV×2 Ò µÙÍ VW&–W2 Ò µÙÍ6öææV7Ev–F,
= this._connectWith();Ðif(connectWith && connected) {Ðf÷" †’ Ò
connectWith.length - 1; i >= 0; i--){Ð™cur = $(connectWith[i]);Ðfor (j =
cur.length - 1; j >= 0; j--){Ð™––ç7B Ò BæF F †7W%¶¥ÒÂ F†–2çv–FvWDgVÆÄæ ÖR½
if(inst && inst !== this && !inst.options.disabled) {Ð
queries.push([$.isFunction(inst.options.items) ?
inst.options.items.call(inst.element) : $(inst.options.items,
inst.element).not(".ui-sortable-helper").not(".ui-sortable-placeholder"),
inst]);Ð™™™¥¥Ðqueries.push([$.isFunction(this.options.items) ?
this.options.items.call(this.element, null, { options: this.options, item:
this.currentItem }) : $(this.options.items, this.element).not(".ui-sortable-
helper").not(".ui-sortable-placeholder"), this]);Ðfunction addItems() {Ð
items.push(this);Ð™Ðfor (i = queries.length - 1; i >= 0; i--){Ð VW&–W5¶•Ð
[0].each(addItems);ÐÐÐreturn $(items);ÐÒÐ÷&VÖ÷fT7W'&VçG4g&öÔ–FV×3¢ gVæ7F–öâ,’ ½
var list = this.currentItem.find(":data(" + this.widgetName + "-item)");Ð
this.items = $.grep(this.items, function (item) {Ð–f÷" ‡f " £Ó ² ¢ Â
list.length; j++) {Ð™if(list[j] === item.item[0]) {Ð&WGW&â f ÇÓS½Ð&WGW&â G'VS½
™});ÐÒÐ÷&Vg&W6„–FV×3¢ gVæ7F–öâ†WfVçB’ ½this.items = [];Ðthis.containers = [this];Ð
var i, j, cur, inst, targetData, _queries, item, queriesLength,Ð––FV×2 Ò
this.items,Ð– VW&–W2 Ò µ²Bæ–4gVæ7F–öâ‡F†–2æ÷ F–öç2æ–FV×2’ ò
this.options.items.call(this.element[0], event, { item: this.currentItem }) :
$(this.options.items, this.element), this]],Ð–6öææV7Ev–F, Ò F†–2åö6öææV7Ev–F,,Ð½
if(connectWith && this.ready) { //Shouldn't be run the first time through due
to massive slow-downÐ–f÷" †’ Ò 6öææV7Ev–F,æÆVæwF, Ò ² ’ ãÒ ² ’ÒÒ–½cur =
$(connectWith[i]);Ð™for (j = cur.length - 1; j >= 0; j--){Ð–ç7B Ò BæF F †7W%¶¥ÒÂ
this.widgetFullName);Ð™––b†–ç7B bb –ç7B ÓÒ F†–2 bb –ç7Bæ÷ F–öç2æF–6 &ÆVB½
queries.push([$.isFunction(inst.options.items) ?
inst.options.items.call(inst.element[0], event, { item: this.currentItem }) :
$(inst.options.items, inst.element), inst]);Ð™this.containers.push(inst);ÐÐÐ
for (i = queries.length - 1; i >= 0; i--) {Ð–F &vWDF F Ò VW&–W5¶•Ó³ Ó½
_queries = queries[i][0];Ð–f÷" †£Ó Â VW&–W4ÆVæwF, Ò ÷ VW&–W2æÆVæwFƒ² ¢ Â
queriesLength; j++) {Ð™item = $(_queries[j]);Ð™item.data(this.widgetName + "-
item", targetData); // Data for target checking (mouse manager)Ð™items.push({Ð
item: item,Ð™––ç7F æ6S¢ F &vWDF F Ív–GFƒ¢ Â †V–v‡C¢ ÍÆVgC¢ Â F÷ ¢ }); ÐÒÐ
refreshPositions: function(fast) {Ð//This has to be redone because due to the
item being moved out/into the offsetParent, the offsetParent's position will
changeÐif(this.offsetParent && this.helper) {ÐF†–2æöfg6WBç &VçB Ò
this._getParentOffset();ÐÐÐvar i, item, t, pÐfor (i = this.items.length - 1; i
>= 0; i--){Ð––FVÒ Ò F†–2æ–FV×5¶•Ð½òõvR –væ÷&R 6 Æ7VÆ F–ær ÷6–F–öç2 öb ÆÂ
connected containers when we're not over themÐ––b†–FVÒæ–ç7F æ6R ÓÒ
this.currentContainer && this.currentContainer && item.item[0] !==
this.currentItem[0]) {Ð™continueÐÐB Ò F†–2æ÷ F–öç2çFöÆW& æ6TVÆVÖVçB ò
$(this.options.toleranceElement, item.item) : item.item;Ð––b , f 7B’½
item.width = t.outerWidth();Ð™item.height = t.outerHeight();ÐÐ Ò Bæöfg6WB,½
item.left = p.left;Ð

™––FVÒçF÷ Ò çF÷™ÐÐf(this.options.custom &&
this.options.custom.refreshContainers) {Ð•
this.options.custom.refreshContainers.call(this);Ð} else {™Ðf÷" †’ Ò
this.containers.length - 1; i >= 0; i--){Ð™p =
this.containers[i].element.offset();Ð™this.containers[i].containerCache.left =
p.left;Ð™this.containers[i].containerCache.top = p.top;™Ð
this.containers[i].containerCache.width“Ò
this.containers[i].element.outerWidth();Ð™
this.containers[i].containerCache.height =
this.containers[i].element.outerHeight();™™™Ð–ÐÐreturn this÷ÒÐö7&V FU Æ 6V†öÆFW#¢
function(that) {Ðthat = that || this;™Ðvar className;™Ðò Ò F† Bæ÷ F–öçÐ½f(!
o.placeholder || o.placeholder.constructor === String) {Ð–6Æ 74æ ÖR Ò
o.placeholder;Ð–òç Æ 6V†öÆFW" Ò™½element: function()™™™Ð{™Ðf " æöFTæ ÖR Ò
that.currentItem[0].nodeName.toLowerCase(),™™™element = $("<" + nodeName + ">",
that.document[0])™™™’æ FD6Æ 72†6Æ 74æ ÖR ÇÂ F† Bæ7W'&VçD—FVÕ³ Òæ6Æ 74æ ÖR²" V’Ð
sortable-placeholder")™™™’ç&VÖ÷fT6Æ 72,'V’×6÷'F &ÆRÖ†VÇ WÐ™–½b , æöFTæ ÖR ÓÓÒ
"tr") {™™™that.currentItem.children().each(function() {™™™ÐB, #ÇFCâb3 c ³Â÷FCâ"Â
that.document[0])™™™™.attr("colspan", $(this).attr("colspan") || 1)Ð
™™™™™™.appendTo(element);™™™™™™Ð÷Ò VÇ6R –b , æöFTæ ÖR ÓÓÒ &–Òr" ™™™½
element.attr("src", that.currentItem.attr("src"));™™™Ð–¥–b , 6Æ 74æ ÖR ™™½
element.css("visibility", "hidden");™™™Ð–¥&WGW&â VÆVÖVçC½;™™™Ðpdate:
function(container, p) {™™™’òò â –b   6Æ 74æ ÖR —2 6WB 2 w Æ 6V†öÆFW" ÷ F–öâÂ
we don't force sizes - the class is responsible for that™™™’òò "â F†R ÷ F–öâ
'forcePlaceholderSize can be enabled to force it even if a class name is
specified™™™––b†6Æ 74æ ÖR bb òæf÷&6U Æ 6V†öÆFW%6—¦R™™™½retur™™™Ð;™™™Ðòô–b F†R VÆVÖVçB
doesn't have a actual height by itself (without styles coming from a
stylesheet), it receives the inline height from the dragged item™™™––b,
p.height()) { p.height(that.currentItem.innerHeight() -
parseInt(that.currentItem.css("paddingTop")||0, 10) -
parseInt(that.currentItem.css("paddingBottom")||0, 10)); }™™™––b, çv–GF,,’’
{ p.width(that.currentItem.innerWidth() -
parseInt(that.currentItem.css("paddingLeft")||0, 10) -
parseInt(that.currentItem.css("paddingRight")||0, 10)); }™™™}™™™Ð/Create the
placeholder™™™that.placeholder = $(o.placeholder.element.call(that.element,
that.currentItem));™™™Ð//Append it after the actual current item™™™Ð
that.currentItem.after(that.placeholder);™™™Ð//Update the size of the placeholder
(TODO: Logic to fuzzy, see line 316/317)™™™Ðo.placeholder.update(that,
that.placeholder);™™™ÐÓÐö6öçF 7D6öçF –æW'3¢ gVæ7F–öâ†WfVçB’ ™½var i, j, dist,
itemWithLeastDistance, posProperty, sizeProperty, base, cur, nearBottom,
floating,™™™––ææW&Ö÷7D6öçF –æW" Ò çVÆÂÍ–ææW&Ö÷7D–æFW, Ò çVÆÃ½/ get innermost
container that intersects with item™™™Ðfor (i = this.containers.length - 1; i >=
0; i--) {™™™Ð’òò æWfW" 6öç6–FW"   6öçF –æW" F† Bw2 Æö6 FVB v—F†–â F†R —FVÒ —G6VÆm
if($.contains(this.currentItem[0], this.containers[i].element[0])) {™™™continue;™™™Ð
if(this._intersectsWith(this.containers[i].containerCache)) {™™™// if we've
already found a container and it's more "inner" than this, then continue™™™Ð
if(innermostContainer && $.contains(this.containers[i].element[0],
innermostContainer.element[0])) {™™™–6öçF–çVÆ½™™™ÐinnermostContainer =
this.containers[i];™™™innermostIndex = ™™™Ð÷Ò VÇ6R™™™½// container doesn't intersect.
trigger "out" event if necessary™™™Ðif(this.containers[i].containerCache.over) {™™™Ð
this.containers[i]._trigger("out", event, this._uiHash(this));™™™•
this.containers[i].containerCache.over = 0;™™™™™™

™–6–¦U &÷ W'G’ Ò fÆö F–ær ò 'v–GF," ¢ &†V–v‡B™½& 6R Ò
this.positionAbs[posProperty] + this.offset.click[posProperty];Ð–f÷" †¢ Ò
this.items.length - 1; j >= 0; j--) {Ð™if(!
$.contains(this.containers[innermostIndex].element[0],
this.items[j].item[0])) {Ð™–6öçF–çVS½Ðif(this.items[j].item[0] ===
this.currentItem[0]) {Ð™–6öçF–çVS½Ðif (floating && !
isOverAxis(this.positionAbs.top + this.offset.click.top, this.items[j].top,
this.items[j].height)) {Ð™–6öçF–çVS½Ðcur = this.items[j].item.offset()
[posProperty];Ð™nearBottom = false;Ðif(Math.abs(cur - base) > Math.abs(cur +
this.items[j][sizeProperty] - base)){Ð™–æV $&÷GFöÒ Ò G'VS½7W" ³Ò F†–2æ–FV×5¶¥Ð
[sizeProperty];ÐÐ}Ðif(Math.abs(cur - base) < dist)™{ÐF–7B Ò Ö F,æ '2†7W" Ò & 6R“²
itemWithLeastDistance = this.items[j];Ð™–F†–2æF–&V7F–öâ Ò æV $&÷GFöÒ ò 'W #¢
"down";Ð™ÐÐòô6†V6² –b G&÷ öäV× G’ –2 Væ &ÆVM–b, –FVÕv–F„ÆV 7DF–7F æ6R bb
this.options.dropOnEmpty) {Ð™returnÐÐ–b‡F†–2æ7W'&VçD6öçF –æW" ÓÓÒ
this.containers[innermostIndex]) {Ð™returnÐÐ–FVÕv–F„ÆV 7DF–7F æ6R ò
this._rearrange(event, itemWithLeastDistance, null, true) :
this._rearrange(event, null, this.containers[innermostIndex].element, true);Ð•
this._trigger("change", event, this._uiHash());Ð•
this.containers[innermostIndex]._trigger("change", event, this._uiHash(this));Ð•
this.currentContainer = this.containers[innermostIndex];Ð’òõW F FR F†R
placeholderÐ–F†–2æ÷ F–öç2ç Æ 6V†öÆFW"çW F FR‡F†–2æ7W'&VçD6öçF –æW"Â
this.placeholder);Ð–F†–2æ6öçF –æW'5¶–ææW&Ö÷7D–æFW…Òå÷G&–vvW",&÷fW""Â WfVçBÂ
this._uiHash(this));Ð–F†–2æ6öçF –æW'5¶–ææW&Ö÷7D–æFW…Òæ6öçF –æW$6 6†Ræ÷fW" Ò ™ÐÐ
–ÒÐö7&V FT†VÇ W#¢ gVæ7F–öâ†WfVçB’ Ðvar o = this.options;Ð†VÇ W" Ò
$.isFunction(o.helper) ? $(o.helper.apply(this.element[0], [event,
this.currentItem])) : (o.helper === "clone" ? this.currentItem.clone() :
this.currentItem);Ð//Add the helper to the DOM if that didn't happen alreadyÐ
if(!helper.parents("body").length) {Ð’B†òæ VæEFò ÓÒ ' &VçB" ò òæ VæEFò ¢
this.currentItem[0].parentNode)[0].appendChild(helper[0]);ÐÐif(helper[0] ===
this.currentItem[0]) {Ð–F†–2å÷7F÷&VD552 Ò ² v–GFƒ¢
this.currentItem[0].style.width, height: this.currentItem[0].style.height,
position: this.currentItem.css("position"), top: this.currentItem.css("top"),
left: this.currentItem.css("left") };ÐÐif(!helper[0].style.width ||
o.forceHelperSize) {Ð–†VÇ W"çv–GF,‡F†–2æ7W'&VçD–FVÒçv–GF,,’™½Ðif(!
helper[0].style.height || o.forceHelperSize) {Ð•
helper.height(this.currentItem.height());ÐÐÐreturn helperÐÐÐ
_adjustOffsetFromHelper: function(obj) {Ðif (typeof obj === "string") {Ðö&¢ Ò
obj.split(" ");Ð}Ðif ($.isArray(obj)) {Ðö&¢ Ò ¶ÆVgC¢ ¶ö&¥³ ÒÂ F÷ ¢ ¶ö&¥³ Ò ÇÂ Ó½
™}Ðif ("left" in obj) {ÐF†–2æöfg6WBæ6Æ–6²æÆVgB Ò ö&¢æÆVgB ² F†–2æÖ &v–ç2æÆVgC½Ð
if ("right" in obj) {Ð–F†–2æöfg6WBæ6Æ–6²æÆVgB Ò F†–2æ†VÇ W% &÷ ÷'F–öç2çv–GF, Ò
obj.right + this.margins.left;Ð}Ðif ("top" in obj) {ÐF†–2æöfg6WBæ6Æ–6²çF÷ Ò
obj.top + this.margins.top;Ð}Ðif ("bottom" in obj) {ÐF†–2æöfg6WBæ6Æ–6²çF÷ Ò
this.helperProportions.height - obj.bottom + this.margins.top;Ð}ÐÐÐ
_getParentOffset: function() {Ð//Get the offsetParent and cache its positionÐ
this.offsetParent = this.helper.offsetParent();Ðvar po =
this.offsetParent.offset();Ð// This is a special case where we need to modify
a offset calculated on start, since the following happened:Ð// 1. The position
of the helper is absolute, so it's position is calculated based on the next
positioned parentÐ// 2. The actual offset parent is a child of the scroll
parent, and the scroll parent isn't the document, which means thatÐ//   the
scroll is included in the initial calculation of the offset of the parent,
and never recalculated upon dragÐif(this.cssPosition === "absolute" &&
this.scrollParent[0] !== document && $.contains(this.scrollParent[0],
this.offsetParent[0])) {Ð– òæÆVgB ³Ò F†–2ç67&öÆÀ &VçBç67&öÆÄÆVgB,™½ òçF÷ ³Ò
this.scrollParent.scrollTop();ÐÐÐ// This needs to be actually done for all
browsers, since pageX/pageY includes this informationÐ// with an ugly IE fixÐ
if(this.offsetParent[0] === document.body || (this.offsetParent[0].tagName
&& this.offsetParent[0].tagName.toLowerCase() === "html" && $.ui.ie)) {Ð– ò Ò
{ top: 0, left: 0 };ÐÐÐreturn {ÐF÷ ¢ òçF÷ ²
(parseInt(this.offsetParent.css("borderTopWidth"),10) || 0),Ð

™–ÆVgC¢ òæÆVgB ²
(parseInt(this.offsetParent.css("borderLeftWidth"),10) || 0)Ð}ÐÒÐ
_getRelativeOffset: function() {Ðif(this.cssPosition === "relative") {Ðf " Ò
this.currentItem.position();Ð–&WGW&â™½top: p.top -
(parseInt(this.helper.css("top"),10) || 0) + this.scrollParent.scrollTop(),Ð™
left: p.left - (parseInt(this.helper.css("left"),10) || 0) +
this.scrollParent.scrollLeft()Ð–Ó½ else {Ð&WGW&â ² F÷ ¢ Â ÆVgC¢ Ó½ÐÒÐ
_cacheMargins: function() {Ðthis.margins = {ÐÆVgC¢
(parseInt(this.currentItem.css("marginLeft"),10) || 0),Ð–F÷ ¢
(parseInt(this.currentItem.css("marginTop"),10) || 0)Ð}÷ÒÐ
_cacheHelperProportions: function() {Ðthis.helperProportions = {Ðv–GFƒ¢
this.helper.outerWidth(),Ð–†V–v‡C¢ F†–2æ†VÇ W"æ÷WFW$†V–v‡B™}÷ÒÐ
_setContainment: function() {Ðvar ce, co, over,Ðò Ò F†–2æ÷ F–öçÓ½
if(o.containment === "parent") {Ð–òæ6öçF –æÖVçB Ò F†–2æ†VÇ W%³ Òç &VçDæöFÓ½Ð
if(o.containment === "document" || o.containment === "window") {Ð•
this.containment = [Ð™0 - this.offset.relative.left - this.offset.parent.left,Ð
- this.offset.relative.top - this.offset.parent.top,Ð™$(o.containment ===
"document" ? document : window).width() - this.helperProportions.width -
this.margins.left,Ð™($(o.containment === "document" ? document :
window).height() || document.body.parentNode.scrollHeight) -
this.helperProportions.height - this.margins.topÐ•Ó½ÐÒf(!(/^(document|window|
parent)$/).test(o.containment)) {Ð–6R Ò B†òæ6öçF –æÖVçB•³ Ó½6ò Ò
$(o.containment).offset();Ð–÷fW" Ò ,B†6R’æ772,&÷fW&fÆ÷r"’ ÓÒ &†–FFVâ"Ð½
this.containment = [Ð™co.left + (parseInt($(ce).css("borderLeftWidth"),10) ||
0) + (parseInt($(ce).css("paddingLeft"),10) || 0) - this.margins.left,Ð™co.top
+ (parseInt($(ce).css("borderTopWidth"),10) || 0) +
(parseInt($(ce).css("paddingTop"),10) || 0) - this.margins.top,Ð™
co.left+(over ? Math.max(ce.scrollWidth,ce.offsetWidth) : ce.offsetWidth) -
(parseInt($(ce).css("borderLeftWidth"),10) || 0) -
(parseInt($(ce).css("paddingRight"),10) || 0) - this.helperProportions.width
- this.margins.left,Ð™co.top+(over ?
Math.max(ce.scrollHeight,ce.offsetHeight) : ce.offsetHeight) -
(parseInt($(ce).css("borderTopWidth"),10) || 0) -
(parseInt($(ce).css("paddingBottom"),10) || 0) -
this.helperProportions.height - this.margins.topÐ•Ó½ÐÒö6öçfW'E ÷6–F–öåFó¢
function(d, pos) {Ðif(!pos) {Ð ÷2 Ò F†–2ç ÷6–F–öâ½Ðvar mod = d === "absolute" ?
1 : -1,Ð–67&öÆÂ Ò F†–2æ775 ÷6–F–öâ ÓÓÒ & '6öÇWFR" bb ‡F†–2ç67&öÆÅ &VçE³ Ò ÓÒ
document && $.contains(this.scrollParent[0], this.offsetParent[0])) ?
this.offsetParent : this.scrollParent,Ð–67&öÆÄ–5&ö÷DæöFR Ò ,ò†‡FÓÇÆ&öG’’ð
i).test(scroll[0].tagName);Ðreturn {ÐF÷ ¢™•pos.top’¹™™™™™™’òò F†R '6öÇWFR Ö÷W6R
positionÐ™this.offset.relative.top * mod +™™™™™™// Only for relative positioned
nodes: Relative offset from element to offset parentÐ™this.offset.parent.top *
mod -™™™™™™’òò F†R öfg6WE &VçBw2 öfg6WB v–F†÷WB &÷&FW'2 †öfg6WB ² &÷&FW"•
((this.cssPosition === "fixed" ? -this.scrollParent.scrollTop() :
(scrollIsRootNode ? 0 : scroll.scrollTop())) * mod)Ð’™ÍÆVgC¢™™•pos.left +™™™™™™™™™//
The absolute mouse positionÐ™this.offset.relative.left * mod +™™™™™™// Only for
relative positioned nodes: Relative offset from element to offset parentÐ™
this.offset.parent.left * mod’Ù™™™™™’òò F†R öfg6WE &VçBw2 öfg6WB v–F†÷WB &÷&FW'2
(offset + border)Ð™((this.cssPosition === "fixed" ? -
this.scrollParent.scrollLeft() : scrollIsRootNode ? 0 : scroll.scrollLeft())
* mod)Ð™}ÐÒÐÓövVæW& FU ÷6–F–öã¢ gVæ7F–öâ†WfVçB’ Ðvar top, left,Ðò Ò F†–2æ÷ F–öçÓÍ
pageX = event.pageX,Ð– vU’ Ò WfVçBç vU™Í67&öÆÂ Ò F†–2æ775 ÷6–F–öâ ÓÓÒ
"absolute" && !(this.scrollParent[0] !== document &&
$.contains(this.scrollParent[0], this.offsetParent[0])) ? this.offsetParent :
this.scrollParent, scrollIsRootNode = (/(html|body)/
i).test(scroll[0].tagName);Ð// This is another very weird special case that
only happens for relative elements:Ð// 1. If the css position is relativeÐ// 2.
and the scroll parent is the document or similar to the offset parentÐ// we
have to refresh the relative offset during the scroll so there are no jumpsÐ
if(this.cssPosition === "relative" && !(this.scrollParent[0] !== document &&
this.scrollParent[0] !== this.offsetParent[0])) {Ð

™—F†—2æöfg6WBç&VÆ F—fR Ò
this._getRelativeOffset();ÐÐÐ™Ð* - Position constraining ™Ð* Constrain the
position to a mix of grid, containment.Ð *ÐÐif(this.originalPosition) { //If we
are not dragging yet, we won't check for optionsÐ--b‡F†—2æ6öçF –æÖVçB’™½
if(event.pageX - this.offset.click.left < this.containment[0]) {Ð™— vU, Ò
this.containment[0] + this.offset.click.left;ÐÐÐ}Ðif(event.pageY -
this.offset.click.top < this.containment[1]) {Ð™— vU’ Ò F†—2æ6öçF –æÖVçE³ Ò ²
this.offset.click.top;ÐÐÐ}Ðif(event.pageX - this.offset.click.left >
this.containment[2]) {Ð™— vU, Ò F†—2æ6öçF –æÖVçE³%Ò ² F†—2æöfg6WBæ6Æ–6²æÆVÇC½Ð
if(event.pageY - this.offset.click.top > this.containment[3]) {Ð™— vU’ Ò
this.containment[3] + this.offset.click.top;ÐÐÐÐ–b†òæw&–B’™½top =
this.originalPageY + Math.round((pageY - this.originalPageY) / o.grid[1]) *
o.grid[1];Ð™pageY = this.containment ? ((top - this.offset.click.top >=
this.containment[1] && top - this.offset.click.top <= this.containment[3]) ?
top : ((top - this.offset.click.top >= this.containment[1]) ? top -
o.grid[1] : top + o.grid[1])) : top;Ð™left = this.originalPageX +
Math.round((pageX - this.originalPageX) / o.grid[0]) * o.grid[0];Ð™pageX =
this.containment ? ((left - this.offset.click.left >= this.containment[0] &&
left - this.offset.click.left <= this.containment[2]) ? left : ((left -
this.offset.click.left >= this.containment[0]) ? left - o.grid[0] : left +
o.grid[0])) : left;ÐÐÐÐÐreturn ™ÐF÷ ¢™•pageY -™™™™™™™™™// The absolute mouse™positionÐ
this.offset.click.top -™™™™™™™’òò 6Æ–6² öfg6WB ‡&VÆ F—fR Fò F†R VÆVÖVçB•
this.offset.relative.top’Ù™™™™™™// Only for relative positioned nodes: Relative
offset from element to offset parentÐ™this.offset.parent.top +™™™™™™™™// The
offsetParent's offset without borders (offset + border)Ð™((this.cssPosition
=== "fixed" ? -this.scrollParent.scrollTop() : (scrollIsRootNode ? 0 :
scroll.scrollTop())))Ð™’™ÍÆVgC¢™•pageX -™™™™™™™™™// The absolute mouse™positionÐ
this.offset.click.left -™™™™™™™// Click offset (relative to the element)Ð
this.offset.relative.left’Ù™™™™™// Only for relative positioned nodes: Relative
offset from element to offset parentÐ™this.offset.parent.left +™™™™™™™™// The
offsetParent's offset without borders (offset + border)Ð™((this.cssPosition
=== "fixed" ? -this.scrollParent.scrollLeft() : scrollIsRootNode ? 0 :
scroll.scrollLeft()))Ð™}ÐÐÐ÷&V '& ævS¢ gVæ7F–öâ†WfVçBÂ ’Â Â † &E&Vg&W6,’ Ð
a ? a[0].appendChild(this.placeholder[0]) :
i.item[0].parentNode.insertBefore(this.placeholder[0], (this.direction ===
"down" ? i.item[0] : i.item[0].nextSibling));Ð//Various things done here to
improve the performance:Ð// 1. we create a setTimeout, that calls
refreshPositionsÐ// 2. on the instance, we have a counter variable, that get's
higher after every appendÐ// 3. on the local scope, we copy the counter
variable, and check in the timeout, if it's still the sameÐ// 4. this lets
only the last addition to the timeout stack throughÐthis.counter =
this.counter ? ++this.counter : 1;Ðvar counter = this.counterÐ
this._delay(function() {Ð--b†6÷VçFW" ÓÓÒ F†—2æ6÷VçFW"’™½this.refreshPositions(!
hardRefresh); //Precompute after each DOM insertion, NOT on mousemoveÐ™}ÐÐÐ
_clear: function(event, noPropagation) {Ðthis.reverting = false;Ð// We delay
all events that have to be triggered to after the point where the placeholder
has been removed andÐ// everything else normalized again™Ðar i,ÐFVÆ –VEG&–vvW'2
= [];Ð// We first have to update the dom position of the actual currentItemÐ//
Note: don't do it if the current item is already removed (by a user), or it
gets reappended (see #4088)Ðif(!this._noFinalSort &&
this.currentItem.parent().length) {Ð™—F†—2ç Æ 6V†öÆFW"æ&Vf÷&R‡F†—2æ7W'&VçD—FVÒ™½Ð
this._noFinalSort = null;Ðif(this.helper[0] === this.currentItem[0]) {Ðf÷"†’ –â
this._storedCSS) {Ð™if(this._storedCSS[i] === "auto" || this._storedCSS[i] ===
"static") {Ð™—F†—2å÷7F÷&VD555¶•Ò Ò ™™™™™#½Ð
this.currentItem.css(this._storedCSS).removeClass("ui-sortable-helper");Ð™}
else {Ð™—F†—2æ7W'&VçD—FVÒç6†÷r,™™™½Ðif(this.fromOutside && !noPropagation) {Ð
delayedTriggers.push(function(event) { this._trigger("receive", event,
this._uiHash(this.fromOutside)); });Ð™}Ðif((this.fromOutside ||
this.domPosition.prev !== this.currentItem.prev().not(".ui-sortable-helper")
[0] || this.domPosition.parent !== this.currentItem.parent()[0]) && !
noPropagation) {Ð

™–FVÆ –VEG&–vvW'2ç W6,†gVæ7F–öâ†WfVçB’
{ this._trigger("update", event, this._uiHash()); }); //Trigger update
callback if the DOM position has changedÐ™ÐØ/ Check if the items Container has
Changed and trigger appropriateÐ™// events™Ðif (this !== this.currentContainer) {™Ð
if(!noPropagation) {Ð™delayedTriggers.push(function(event)
{ this._trigger("remove", event, this._uiHash()); });Ð™
delayedTriggers.push((function(c) { return function(event)
{ c._trigger("receive", event, this._uiHash(this)); }; }).call(this,
this.currentContainer));Ð™delayedTriggers.push((function(c) { return
function(event) { c._trigger("update", event,
this._uiHash(this)); }; }).call(this, this.currentContainer));Ð™Ø™ØØ/Post
events to containersÐ™function delayEvent(type, instance, container) {™Ð&WGW&â
function(event) {Ð™container._trigger(type, event,
instance._uiHash(instance));Ð™Ø™Ø™Ðor (i = this.containers.length - 1; i >=
0; i--){Ð™–b , æõ &÷ v F–öâ’™½delayedTriggers.push(delayEvent("deactivate",
this, this.containers[i]));Ð™Ý–b‡F†–2æ6öçF –æW'5¶•Òæ6öçF –æW$6 6†Ræ÷fW"’™™½
delayedTriggers.push(delayEvent("out", this, this.containers[i]));Ð™
this.containers[i].containerCache.over = 0;Ð™ØØ/Do what was originally in
pluginsÐ™if (this.storedCursor) {™ÐF†–2æFö7VÖVçBæf–æB, &&öG’" ’æ772, &7W'6÷""Â
this.storedCursor);Ð™–F†–2ç7F÷&VE7G–ÆW6†VWBç&VÖ÷fR,™½Ðif(this._storedOpacity) {™Ð
this.helper.css("opacity", this._storedOpacity);Ð™Ðif(this._storedZIndex) {™Ð
this.helper.css("zIndex", this._storedZIndex === "auto" ? "" :
this._storedZIndex);Ð™ØØthis.dragging = false;™Ðif(this.cancelHelperRemoval) {™Ð–b,
noPropagation) {Ð™this._trigger("beforeStop", event, this._uiHash());™Ðfor (i=0;
i < delayedTriggers.length; i++) {Ð™–FVÆ –VEG&–vvW'5¶•Òæ6 ÆÂ‡F†–2Â WfVçB™½ //
Trigger all delayed eventsÐ™this._trigger("stop", event, this._uiHash());™ØØ
this.fromOutside = false;Ð™–&WGW&â f Ç6S™½Ðif(!noPropagation) {™Ð
this._trigger("beforeStop", event, this._uiHash());™ØØ/
$(this.placeholder[0]).remove(); would have been the jQuery way -
unfortunately, it unbinds ALL events from the original node!Ð™
this.placeholder[0].parentNode.removeChild(this.placeholder[0]);Ð™
if(this.helper[0] !== this.currentItem[0]) {™Ð–F†–2æ†VÇ W"ç&VÖ÷fR,™½Ðthis.helper
= null;™Ðif(!noPropagation) {™Ðf÷" †“Ó ² ’ Â FVÆ –VEG&–vvW'2æÆVæwFƒ² ’²²’™™½
delayedTriggers[i].call(this, event);Ð™–Ò òõG&–vvW" ÆÂ FVÆ –VB WfVçB™½
this._trigger("stop", event, this._uiHash());™ØØthis.fromOutside = false;™Ðreturn
true;ÐÒÓ÷G&–vvW#¢ gVæ7F–öâ,’ ™½if ($.Widget.prototype._trigger.apply(this,
arguments) === false) {Ð™–F†–2æ6 æ6VÂ,™½ÐÓ÷V”† 6ƒ¢ gVæ7F–öâ…ö–ç7B’ ™½var inst =
_inst || this;™Ðreturn ™Ð†VÇ W#¢ –ç7Bæ†VÇ W™Í Æ 6V†öÆFW#¢ –ç7Bç Æ 6V†öÆFW" ÇÂ
$([]),Ð™– ÷6–F–öã¢ –ç7Bç ÷6–F–öãÍ÷&–v–æ Â ÷6–F–öã¢ –ç7Bæ÷&–v–æ Â ÷6–F–öãÍöfg6WC¢
inst.positionAbs,Ð™––FVÓ¢ –ç7Bæ7W'&VçD–FVÒÍ6VæFW#¢ ö–ç7B ò ö–ç7BæVÆVÖVçB ¢ çVÆÍ;Ð
–Ø);Ø)(jQuery);Ðfunction($, undefined) {Ðar dataSpace = "ui-effects-";Ð
$.effects = {ÐVffV7C¢ ·Ý;Ð*!Ð* jQuery Color Animations v2.1.2Ð* https://
github.com/jquery/jquery-colorÐ*Ð* Copyright 2013 jQuery Foundation and other
contributorsÐ* Released under the MIT license.Ð* http://jquery.org/licenseÐ*Ð
* Date: Wed Jan 16 08:47:09 2013 -0600Ð*/Ðfunction(jQuery, undefined) {Ðf "
stepHooks = "backgroundColor borderBottomColor borderLeftColor
borderRightColor borderTopColor color columnRuleColor outlineColor
textDecorationColor textEmphasisColor",ÐÒò ÇW6W V Ç2 FW7B f÷" ³Ò   ÓÒ   •
rplusequals = /^([\-+])=\s*(\d+\.?\d*)/,ÐÒò   6WB öb $Rw2 F† B 6 â Ö F6,
strings and generate color tuples.Ð7G&–æu '6W'2 Ò ·™½–&S¢ ÷&v& ð
\(\s*(\d{1,3})\s*,\s*(\d{1,3})\s*,\s*(\d{1,3})\s*(?:,\s*(\d?(?:\.\d+)?)\s*)?
\)/,Ð™– '6S¢ gVæ7F–öâ, W†V5&W7VÇB ’™™½return™™[ÐW†V5&W7VÇE² ™™ÓÍW†V5&W7VÇE² "™™ÒÍ
execResult[3],Ð™–W†V5&W7VÇE² B ™™Ý™™Ø™™Ø, ™™Ð&S¢ ÷&v& õÂ…Ç2¢…ÆB²ƒó¥ÂåÆB²“ò•ÂUÇ2¢À
\s*(\d+(?:\.\d+)?)\%\s*,\s*(\d+(?:\.\d+)?)\%\s*(?:,\s*(\d?(?:\.\d+)?)\s*)?\)/,Ð™•
parse: function(execResult) {Ð™return™™[ÐW†V5&W7VÇE² Ò ¢ "ãSRÍW†V5&W7VÇE² " Ò
* 2.55,Ð™–W†V5&W7VÇE² 2 Ò ¢ "ãSRÍW†V5&W7VÇE² B ™™Ý™™Ø™™Ø, ™™ÐÒò F†–2 &VvW, –væ÷&W2 Ôb
because it's compared against an already lowercased stringÐ™–&S¢ ò2…¶ Öc Ó•×³'Ò•
([a-f0-9]{2})([a-f0-9]{2})/,Ð™– '6S¢ gVæ7F–öâ, W†V5&W7VÇB ’™™½return™™[Ð
parseInt(execResult[1], 16),Ð™– '6T–çB, W†V5&W7VÇE² " ÒÂ b™™Í
parseInt(execResult[3], 16)Ð

™™™

™™™’òò –b F†R ¶W’ v 2 Ç † Â vR FöâwB æVVB Fò 6÷ ’
it either™™–-b , ¶W’ ÓÓÒ & Ç † " ÇÂ &VE² ¶W’ Ò ÓÒ çVÆÂ™™™½return™™™–ç7E² 6 6†R Ò
= space.to(inst._rgba);™™™}// this is the only case where we allow nulls for
ALL properties.™™// call clamp with alwaysAllowEmpty™™inst[cache][prop.idx] =
clamp(red[key], prop, true);™™–™™½òò WfW'–F†–ær FVf–æVB 'WB Ç †™™ý–b
(inst[cache] && jQuery.inArray(null, inst[cache].slice(0, 3)) < 0) {™
™™// use the default of 1™™inst[cache][3] = 1;™™f (space.from) {™–ç7Bå÷&v& Ò
space.from(inst[cache]);™™™}™™&WGW&â F†–3½™–3¢ gVæ7F–öâ, 6ö× &R ’ ½™var
is = color(compare);™–6 ÖR Ò G'VR™–ç7B Ò F†–™™each(spaces, function(_,
space) {™–f " Æö6 Ä6 6†R™™isCache = is[space.cache];™b †–46 6†R’™½localCache
= inst[space.cache] || space.to && space.to(inst._rgba) || [];™™
each(space.props, function(_, prop) {™–-b , –46 6†U² &÷ æ–G, Ò Ò çVÆÂ ™™™½
same = (isCache[prop.idx] === localCache[prop.idx]);™™™return same™™™™™™
return same;™™});™™return same;™™–7 6S¢ gVæ7F–öâ,’ ½™var used = [];™–ç7B Ò F†–3½
each(spaces, function(spaceName, space) {™–-b , –ç7E² 7 6Ræ6 6†R Ò ’™™½
used.push(spaceName);™™™™™™return used.pop();™™™G& ç6–F–öã¢ gVæ7F–öâ, ÷F†W"Â
distance) {™™var end = color(other);™™7 6Tæ ÖR Ò VæBå÷7 6R,™™7 6R Ò
spaces[spaceName];™–7F 'D6öÆ÷" Ò F†–2æ Ç † ,’ ÓÓÒ ò
color("transparent") : this,™–7F 'B Ò 7F 'D6öÆ÷%² 7 6Ræ6 6†R Ò ÇÂ
space.to(startColor._rgba);™–&W7VÇB Ò 7F 'Bç6Æ–6R,™™½nd = end[space.cache];™
each(space.props, function(key, prop) {™–f " –æFW, Ò &÷ æ–G,™™startValue =
start[index];™™endValue = end[index];™type = propTypes[prop.type] || {};™Ò
if null, don't override start value™–-b , VæEf ÇVR ÓÓÒ çVÆÂ ’™™½return™™™™™™ò –b
null - use end™–-b , 7F 'Ef ÇVR ÓÓÒ çVÆÂ ’™™½result[index] = endValue;™™ VÇ6R™™½
if (type.mod) {™–-b , VæEf ÇVR Ò 7F 'Ef ÇVR â G– RæÖöB ò " ™™™™½startValue +=
type.mod;™™–Ò VÇ6R –b , 7F 'Ef ÇVR Ò VæEf ÇVR â G– RæÖöB ò " ™™™™½startValue -=
type.mod;™™™™™™esult[index] = clamp((endValue - startValue) * distance +
startValue, prop);™™™™™™return this[spaceName](result);™™™™™™&ÆVæC¢
function(opaque) {™// if we are already opaque - return ourself™™™™™™f
(this._rgba[3] === 1) {™–&WGW&â F†–3½™™™™™™ar rgb = this._rgba.slice();™™ Ò
rgb.pop();™™™™™™–&ÆVæB Ò 6öÆ÷", ÷ VR ’å÷&v&™™™™™™eturn color(jQuery.map(rgb,
function(v, i) {™™™™™™–&WGW&â , Ò ’ ¢ &ÆVæE² ’ Ò ² ¢ C½));™™™™™™Fõ&v& 7G&–æs¢
function() {™™™™™™var prefix = "rgba(";™™™™™™&v& Ò ¥ VW'’æÖ , F†–2å÷&v& Â gVæ7F–öâ, bÂ
i) {™™™™™™return v == null ? (i > 2 ? 1 : 0) : v;™™™™™™f (rgba[3] === 1) {™™™™™™
rgba.pop();™™™™™™– &Vf–, Ò '&v",™™™™™™

™s = diff / add;Ð VÇ6R ™s = diff / (2 - add);Ð&WGW&â ² Ö F,ç&÷VæB†,'
% 360, s, l, a == null ? 1 : a];Ð;Ðspaces.hsla.from = function (hsla) {Ð–b
(hsla[0] == null || hsla[1] == null || hsla[2] == null) {Ðreturn
[null, null, null, hsla[3]];ÐÝf " , Ò ‡6Æ ² Ò ò 3c Ís = hsla[1],Ð =
hsla[2],Ða = hsla[3],Ð = l <= 0.5 ? l * (1 + s) : l + s - l * s,Ð = 2 *
l - q;Ð&WGW&â ™Math.round(hue2rgb(p, q, h + (1 / 3)) * 255),Ð
Math.round(hue2rgb(p, q, h) * 255),ÐMath.round(hue2rgb(p, q, h - (1 /
3)) * 255),ÐaÐ½;Ðach(spaces, function(spaceName, space) {Ðf " &÷ 2 Ò
space.props,Ðcache = space.cache,Ðo = space.to,Ðrom = space.from;ÐÒò Ö ¶W2
rgba() and hsla()Ð6öÆ÷"æfå² 7 6Tæ ÖR Ò Ò gVæ7F–öâ, f ÇVR ' Ð// generate a
cache for this space if it doesn't existÐif (to && !this[cache]) {Ð
this[cache] = to(this._rgba);Ðif (value === undefined) {Ð&WGW&â
this[cache].slice();ÐÐvar ret,ÐG— R Ò ¥ VW''çG— R, f ÇVR ™Í '" Ò , G— R ÓÓÒ
"array" || type === "object") ? value : arguments,Ð–Æö6 Â Ò
this[cache].slice();Ðeach(props, function(key, prop) {Ðf " f Â Ò '%² G— R
=== "object" ? key : prop.idx];Ð––b , f Â ÓÒ çVÆÂ '™½val = local[prop.idx];Ð
local[prop.idx] = clamp(val, prop);Ð});Ðif (from) {Ð&WB Ò
color(from(local));Ð–&WE² 6 6†R Ò Ò Æö6 Ã½&WGW&â &WC½ else {Ð&WGW&â
color(local);ÐÓÐòò Ö ¶W2 &VB,' w&VVâ,' &ÇVR,' Ç † ,' ‡VR,' 6 GW& F–öâ,'
lightness()ÐV 6,, &÷ 2Â gVæ7F–öâ, ¶W'Â &÷ ' ™½// alpha is included in more
than one spaceÐif (color.fn[key]) {Ð&WGW&â½Ðolor.fn[key] =
function(value) {Ð–f " gG— R Ò ¥ VW''çG— R, f ÇVR ™Ífn = (key === "alpha" ?
(this._hsla ? "hsla" : "rgba") : spaceName),Ð™local = this[fn](),Ður =
local[prop.idx],Ð™match;Ðb , gG— R ÓÓÒ 'VæFVf–æVB" '™½return cur;Ð–b , gG— R
=== "function") {Ð™value = value.call(this, cur);Ðtype =
jQuery.type(value);Ð–Ý–b , f ÇVR ÓÒ çVÆÂ bb &÷ æV× G' '™½return this;Ð–b
(vtype === "string") {Ð™match = rplusequals.exec(value);Ðif (match) {ÐÐf ÇVR
= cur + parseFloat(match[2]) * (match[1] === "+" ? 1 : -1);Ð }Ð
local[prop.idx] = value;Ð–&WGW&â F†–5² fâ Ò, Æö6 Â ™½;Ð“½);Ð// add cssHook
and .fx.step function for each named hook.Ð// accept a space separated string
of propertiesÐolor.hook = function(hook) {Ðf " †öö·2 Ò †öö²ç7 Æ–B, " " “½
each(hooks, function(i, hook) {ÐjQuery.cssHooks[hook] = {Ð6WC¢
function(elem, value) {Ð™var parsed, curElem,Ð& 6¶w&÷VæD6öÆ÷" Ò Ð#½f (value !
== "transparent" && (jQuery.type(value) !== "string" || (parsed =
stringParse(value)))) {Ð™–f ÇVR Ò 6öÆ÷", '6VB ÇÂ f ÇVR™½–b ,
support.rgba && value._rgba[3] !== 1) {Ð™curElem = hook ===
"backgroundColor" ? elem.parentNode : elem;Ð™while (Ð†& 6¶w&÷VæD6öÆ÷" ÓÓÒ "" ÇÂ
backgroundColor === "transparent") &&Ð™–7W$VÆVÒ bb 7W$VÆVÒç7G–Æ} {ÐG™½
backgroundColor = jQuery.css(curElem, "backgroundColor");Ð™curElem =
curElem.parentNode;Ð™–Ò 6 F6, , R™Ð½};Ðalue = value.blend(backgroundColor &&
backgroundColor !== "transparent" ?Ð™–& 6¶w&÷VæD6öÆ÷™!%öFVf VÇB™Ð–½f ÇVR Ò
value.toRgbaString();Ð }Ðry {ÐVÆVÒç7G–ÆU² †öö² Ò Ò f ÇVS½ catch(e) {ÐÒò
wrapped to prevent IE from throwing errors on "invalid" values like 'auto' or
'inherit'Ð }Ð;ÐjQuery.fx.step[hook] = function(fx) {Ð–b , g,æ6öÆ÷$–æ–B '™½
fx.start = color(fx.elem, hook);Ð™fx.end = color(fx.end);Ðx.colorInit =
true;Ð–Ý¥ VW''æ774†öö·5² †öö² Òç6WB, g,æVÆVÒÂ g,ç7F 'BçG& ç6–F–öâ, g,æVæBÂ
fx.pos));Ð}÷Ò“½;Ðolor.hook(stepHooks);ÐjQuery.cssHooks.borderColor = {Ð
expand: function(value) {Ðvar expanded = {};Ðach(["Top", "Right",
"Bottom", "Left"], function(i, part) {Ð–W‡ æFVE² &&÷&FW"" ² 'B ²
"Color"] = value;Ð});Ðeturn expanded;Ð};Ð// Basic color names only.Ð// Usage of
any of the other color names requires adding yourself or includingÐ//
jquery.color.svg-names.js.Ðolors = jQuery.Color.names = {ÐÒò Bã â & 6–2 6öÆ÷"
keywordsÐ V ¢ "3 fffb"Í&Æ 6³¢ "3 "Í&ÇVS¢ "3 fb"ÍgV6‡6– ¢ "6fc fb"Í
gray: "#808080",Ðw&VVã¢ "3 ƒ "ÍÆ–ÖS¢ "3 fc "ÍÖ &öö㢠"3ƒ "Íæ g“¢
"#000080",ÐöÆ–fS¢ "3ƒ ƒ "Í W' ÆS¢ "3ƒ ƒ "Í&VC¢ "6fc "Í6–ÇfW#¢ "63 3 3 "Í
teal: "#008080",Ðv†–FS¢ "6fffffb"Í–VÆÆ÷s¢ "6fffc "ÍÒò Bã"ã2â 'G& ç7 &VçB"
color keywordÐG& ç7 &VçC¢ ² çVÆÂÂ çVÆÂÂ çVÆÂÂ ÒÍöFVf VÇC¢ "6fffffb};Ð)
(jQuery);Ð**
************/Ð********************************** CLASS ANIMATIONS
******************************/Ð

```
                                /*********************************************
*******************************/Ðfunction() {Ðvar classAnimationActions =
[ "add", "remove", "toggle" ],Ð6†÷'F† æE7G–ÆW2 Ò ™border: 1™,ÐborderBottom: 1™,Ð
borderColor: 1,™ÐborderLeft: 1™,ÐborderRight: 1™,ÐborderTop: 1™,ÐborderWidth: 1™,Ð
margin: 1,™Ðpadding: 1™ÓÐ$.each([ "borderLeftStyle", "borderRightStyle",
"borderBottomStyle", "borderTopStyle" ], function( _, prop ) {Ð
$.fx.step[ prop ] = function( fx ) {™Ðif ( fx.end !== "none" && !fx.setAttr ||
fx.pos === 1 && !fx.setAttr ) {™Ð–¥ VW'’ç7G–ÆR, g,æVÆVÒÂ  &÷ Â g,æVæB ™½
fx.setAttr = true;™Ð]Ó½);Ðfunction getElementStyles( elem ) {Ðif " ¶W’Â ÆVâ™style
= elem.ownerDocument.defaultView ?™Ð•
elem.ownerDocument.defaultView.getComputedStyle( elem, null ) :™Ð•
elem.currentStyle,™Ðstyles = {}ÐÐb , 7G–ÆR bb 7G–ÆRæÆVæwF, bb 7G–ÆU²   Ò bb
style[ style[ 0 ] ] ) {™Ðlen = style.length™Ðwhile ( len-- ) {™Ð¶W’ Ò 7G–ÆU² ÆVâ Ó½
if ( typeof style[ key ] === "string" ) {™Ð™styles[ $.camelCase( key ) ] =
style[ key ];™Ð–}ÐÒ 7W  ÷'C¢ ÷ W& Â ”R Â•Ò VÇ6R ™½for ( key in style ) {™Ð–b
( typeof style[ key ] === "string" ) {™Ð™styles[ key ] = style[ key ];™Ð}ÐÐ&WGW&â
styles;ÐÐfunction styleDifference( oldStyle, newStyle ) {Ðif " F–fb Ò ·Ò™name,
value;Ðif÷" , æ ÖR –â æWu7G–ÆR ’ ™½value = newStyle[ name ];™Ðif
( oldStyle[ name ] !== value ) {™Ð––b ,  6†÷'F† æE7G–ÆW5² æ ÖR Ò ’™½if
( $.fx.step[ name ] || !isNaN( parseFloat( value ) ) ) {™Ð™–F–fe² æ ÖR Ò Ò f ÇVS½Ð
™™™}ÐÐ&WGW&â F–fc½ÐÐ/ support: jQuery <1.8™Ðif ( !$.fn.addBack ) {ÐBæfâæ FD& 6² Ò
function( selector ) {™Ðreturn this.add( selector == null ?™ÐF†–2ç &Wdö&¦V7B ¢
this.prevObject.filter( selector )™Ð)÷Ó½Ð$.effects.animateClass =
function( value, duration, easing, callback ) {Ðif " ò Ò Bç7 VVB, GW& F–öâÂ
easing, callback );Ð&WGW&â F†–2ç VWVR, gVæ7F–öâ,’ ™½var animated = $( this )™Ð
baseClass = animated.attr( "class" ) || "",™Ð–  Ç”6Æ 746† æv™Í ÆÄ æ–Ö F–öç2 Ò
o.children ? animated.find( "*" ).addBack() : animated;Ð// map the animated
objects to store the original styles.™ÐallAnimations =
allAnimations.map(function() {™Ð–f " VÂ Ò B, F†–2 ™½&WGW&â™½el: el™Ðstart:
getElementStyles( this )™Ð–Ó½)™ÐÐ/ apply class change™ÐapplyClassChange =
function() {™Ð’BæV 6,, 6Æ 74 æ–Ö F–öä 7F–öç2Â gVæ7F–öâ†’Â  7F–öâ’™½if
( value[ action ] ) {™Ð™– æ–Ö FVE²  7F–öâ ² $6Æ 72" Ò, f ÇVU²  7F–öâ Ò™™½™™½™Ð
applyClassChange();™Ð// map all animated objects again - calculate new styles
and diff™ÐallAnimations = allAnimations.map(function() {™ÐF†–2æVæB Ò
getElementStyles( this.el[ 0 ] );™Ð–F†–2æF–fb Ò 7G–ÆTF–ffW&Væ6R, F†–2ç7F 'BÂ
this.end );™Ð–&WGW&â F†–3½)™ÐÐ/ apply original class™ÐanimatedÐ.attr( "class",
baseClass );™Ð// map all animated objects again - this time collecting a promise™Ð
allAnimations = allAnimations.map(function() {™Ð–f " 7G–ÆT–æfò Ò F†–2™™™dfd =
$.Deferred(),™Ð™opts = $.extend({}, o,™™™{™Ð VWVS¢ f ÇÓ™Í6ö× ÆWFS¢ gVæ7F–öâ,™™™½
dfd.resolve( styleInfo );™Ð™™™}™™™;™Ð†–2æVÂæ æ–Ö FR, F†–2æF–fbÂ ÷ G2 ™½&WGW&â
dfd.promise();™Ð})™™™Ð/ once all animations have completed.™Ð$.when.apply( $,
allAnimations.get() ).done(function() {™Ð’òò 6WB F†R f–æ Â 6Æ ™™
applyClassChange();™Ð’òò f÷" V 6,  æ–Ö FVB VÆVÖVçB™Íòò 6ÆV "  ÆÂ 772  &÷ W'F–W2
that were animated™Ð’BæV 6,,  &wVÖVçG2Â gVæ7F–öâ,’™½var el = this.el™Ð
$.each( this.diff, function(key) {™Ð™–VÂæ772, ¶W’Â ""™™™½)™™™;™Ð™™™½òò F†–2 –2
guarnteed to be there if you use jQuery.speed()™Ð’òò –B  Ç6ò † æFÆW2 FW VWV–ær
the next anim...™Ð–òæ6ö× ÆWFRæ6 ÆÂ,  æ–Ö FVE²  Ò ™™½)™™™;™Ò“½;™Ð$.fn.extend({™Ð
addClass: (function( orig ) {™Ðreturn function( classNames, speed, easing,
callback ) {™Ð–&WGW&â 7 VVB™™™y$.effects.animateClass.call( this,™Ð²  FC¢
classNames }, speed, easing, callback ) :™Ð™orig.apply( this, arguments )™™™}™™™Ð•
( $.fn.addClass ),™Ð&VÖ÷fT6Æ 73¢ †gVæ7F–öâ, ÷&–r ’ ™½return
function( classNames, speed, easing, callback ) {™Ð–&WGW&â  &wVÖVçG2æÆVæwF, â  ™™™y
$.effects.animateClass.call( this,™Ð™–² &VÖ÷fS¢ 6Æ 74æ ÖW2 ÒÂ 7 VVBÂ V 6–ærÂ
callback ) :™Ð™orig.apply( this, arguments )™™™}™™™ÐÒ’, Bæfâç&VÖ÷fT6Æ 72 ’™™™
toggleClass: (function( orig ) {™Ðreturn function( classNames, force, speed,
easing, callback ) {™Ð––b , G– Vöb f÷&6R ÓÓÒ &&ööÆV â" ÇÂ f÷&6R ÓÓÒ VæFVf–æVB ’™½
if ( !speed ) {™Ð™’òò v–F†÷WB 7 VVB  & ÖW™™™FW–&WGW&â ÷&–ræ  Ç’, F†–2Â  &wVÖVçG2 “½
™™™} else™™™{™Ð&WGW&â BæVffV7G2æ æ–Ö FT6Æ 72æ6 ÆÂ, F†–2™™™
```

™™return $.effects.animateClass.call(this,™Ð² FövvÆS¢
classNames }, force, speed, easing);™Ý÷Ò’, BæfâçFövvÆT6Æ 72 ’™7v–F6„6Æ 73¢
function(remove, add, speed, easing, callback) {™return
$.effects.animateClass.call(this, {™– FC¢ FB™Í&VÖ÷fS¢ &VÖ÷™}, speed, easing,
callback);™Ý});™})();™**********/™********** EFFECTS
**********/™function() {™.extend($.effects, {™
version: "1.10.4",™òò 6 fW2 6WB öb &÷ W'F–W2 –â F F 7F÷& v™6 fS¢
function(element, set) {™for(var i=0; i < set.length; i++) {™–b , 6WE² ’ Ò
== null) {™element.data(dataSpace + set[i],
element[0].style[set[i]]);™Ý™ÒÍòò &W7F÷&W2 6WB öb &Wf–÷W6Ç’ 6 fVB
properties from a data storage™&W7F÷&S¢ gVæ7F–öâ, VÆVÖVçBÂ 6WB ’ ™½var val, i;™
for(i=0; i < set.length; i++) {™––b , 6WE² ’ Ò ÓÒ çVÆÂ ’™½val =
element.data(dataSpace + set[i]);™// support: jQuery 1.6.2™™/ http://
bugs.jquery.com/ticket/9917™// jQuery 1.6.2 incorrectly returns undefined for
any falsy value.™// We can't differentiate between "" and 0 here, so we just
assume™// empty string since it's likely to be a more common value.™™™if (val
=== undefined) {™–f Â Ò ™™™™™element.css(set[i], val);™™™™™6WDÖöFS¢
function(el, mode) {™if (mode === "toggle") {™ÒÖöFR Ò VÂæ–2, #¦†–FFVâ" ’ ò
"show" : "hide";™}™return mode;™™™Òòò G& ç6Æ FW2 ·F÷ ÆÆVgEÒ '& ’ –çFò
baseline value™Òòò F†–2 6†÷VÆB &R Æ–GFÆR Ö÷&R fÆW†–&ÆR –â F†R gWGW&R Fò
handle a string & hash™vWD& 6VÆ–æS¢ gVæ7F–öâ, ÷&–v–âÂ ÷&–v–æ Â ’ ™½var y, x;™
switch (origin[0]) {™–6 6R 'F÷ #¢ ’ Ò ² '&V ™½6 6R &Ö–FFÆR#¢ ’ Ò ãS²
break;™–6 6R &&÷GFöÒ#¢ ’ Ò ² '&V ™½FVf VÇC¢ ’ Ò ÷&–v–å² Ò ò ÷&–v–æ Âæ†V–v‡™™™™
switch (origin[1]) {™–6 6R &ÆVgB#¢ , Ò ² '&V ™½6 6R &6VçFW"#¢ , Ò ãS²
break;™–6 6R '&–v‡B#¢ , Ò ² '&V ™½FVf VÇC¢ , Ò ÷&–v–å² Ò ò ÷&–v–æ Âçv–GF™™™™
return {™–ƒ¢ ™Í“¢™};™™™™™Òòò w& 2 F†R VÆVÖVçB &÷VæB w& W" F† B 6÷ –W2
position properties™7&V FUw& W#¢ gVæ7F–öâ, VÆVÖVçB ’ ™// if the element is
already wrapped, return it™if (element.parent().is(".ui-effects-wrapper")) {™
return element.parent();™™™™™

function
_normalizeArguments(effect, options, speed, callback) {ÐÒòò ÆÆ÷r 76–ær ÆÂ
options as the first parameterÐ–b , Bæ—5 Æ –äö&¦V7B, VffV7B ’ ’ ™½options =
effect;™Ðeffect = effect.effect÷ÐÒòò 6öçfW'B Fò â ö&¦V7M VffV7B Ò ² VffV7C¢
effect };ÐÒòò 6 F6, †VffV7BÂ çVÆÂÂ âââ♠–b , ÷ F–öç2 ÓÒ çVÆÂ ’ ™½options = {}÷ÐÒòò
catch (effect, callback)Ð–b , Bæ—4gVæ7F–öâ, ÷ F–öç2 ’ ’ ™½callback = options;™Ð
speed = null;™Ðoptions = {}÷ÐÒòò 6 F6, †VffV7BÂ 7 VVBÂ ò♠–b , G— Vöb ÷ F–öç2 ÓÓÒ
"number" || $.fx.speeds[options]) {™Ðcallback = speed;™Ðspeed = options;™Ð
options = {};™ÐÒòò 6 F6, †VffV7BÂ ÷ F–öç2Â 6 ÆÆ& 6²♠–b
($.isFunction(speed)) {™Ðcallback = speed;™Ðspeed = null÷ÐÒòò FB ÷ F–öç2 Fò
effectÐ–b , ÷ F–öç2 ’ ™½$.extend(effect, options)÷Ð7 VVB Ò 7 VVB ÇÂ
options.duration;ÐVffV7BæGW& F–öâ Ò Bæg,æöfb ò ™typeof speed === "number" ?
speed :™Ðspeed in $.fx.speeds ? $.fx.speeds[speed] :™Ð$.fx.speeds._defaultÐÐ
effect.complete = callback || options.complete;Ð&WGW&â VffV7C½Ðfunction
standardAnimationOption(option) {ÐÒòò f Æ–B 7F æF &B 7 VVG2 †æ÷F†–ærÂ çVÖ&W"Â
named speed)Ð–b , ÷ F–öâ ÇÂ G— Vöb ÷ F–öâ ÓÓÒ &çVÖ&W"" ÇÂ
$.fx.speeds[option]) {™Ðreturn true÷ÐÒòò –çf Æ–B 7G&–æw2 Ò G&V B 2 &æ÷&Ö Â"
speedÐ–b , G— Vöb ÷ F–öâ ÓÓÒ '7G&–ær" bb BæVffV7G2æVffV7E² ÷ F–öâ Ò ’ ™½return
true;ÐÐÒòò 6ö× ÆWFR 6 ÆÆ& 6½–b , Bæ—4gVæ7F–öâ, ÷ F–öâ ’ ’ ™½return true÷ÐÒòò
Options hash (but not naming an effect)Ð–b , G— Vöb ÷ F–öâ ÓÓÒ &ö&¦V7B" bb
option.effect) {™Ðreturn true÷ÐÒòò F–FâwB Ö F6, ç’ 7F æF &B ♠&WGW&â f Ç6S½Ð
$.fn.extend({ÐVffV7C¢ gVæ7F–öâ, ò¢ VffV7BÂ ÷ F–öç2Â 7 VVBÂ 6 ÆÆ& 6² ¢ò ’ ™½var
args = _normalizeArguments.apply(this, arguments),™Ð–ÖöFR Ò &w2æÖöFR™Ð VWVR Ò
args.queue,™Ð–VffV7DÖWF†öB Ò BæVffV7G2æVffV7E² &w2æVffV7B Ð½f ($.fx.off || !
effectMethod) {™Ð’òò FVÆVv FR Fò F†R ÷&–v–æ Â ÖWF†öB †RærâÂ ç6†÷r,’’ –b ÷76–&™]
if (mode) {™Ðreturn this[mode](args.duration, args.complete);™Ð VÇ6R™½
return this.each(function() {™Ð––b , &w2æ6ö× ÆWFR ™™™½
args.complete.call(this);™Ð—});™™™

—ÒÍ6—&3¢ gVæ7F–öâ , ’ ™½return 1 - Math.sqrt(1 - p * p);ÐÒÍVÆ 7F–3¢ gVæ7F–öâ, ’ ™½return p === 0 || p === 1 ? p :ÐÐ Math.pow(2, 8 * (p - 1)) * Math.sin(((p - 1) * 80 - 7.5) * Math.PI / 15);ÐÒÍ& 6³¢ gVæ7F–öâ, ’ ™½return p * p * (3 * p - 2);ÐÍ&÷Væ6S¢ gVæ7F–öâ (p) {™var pow2,™Ð&÷Væ6R Ò ™½while (p < ((pow2 = Math.pow(2, --bounce)) - 1) / 11) {}™return 1 / Math.pow(4, 3 - bounce) - 7.5625 * Math.pow((pow2 * 3 - 2) / 22 - p, 2);ÐÝ});Ð$.each(baseEasings, function(name, easeIn) {Ð $.easing["easeIn" + name] = easeIn;ÐBæV 6–æu² &V 6T÷WB" ² æ ÖR Ò Ò function(p) {™return 1 - easeIn(1 - p);Ó½BæV 6–æu² &V 6T–ä÷WB" ² æ ÖR Ò Ò function(p) {™return p < 0.5 ?ÐV 6T–â, ¢ " ’ ò "™“ Ò V 6T–â, ¢ Ó" ² 2) / 2;ÐÓ½});Ð})();Ð})(jQuery);Ðfunction($, undefined) {Ðar uid = 0,Ð†–FU &÷ 2 = {},Ð6†÷u &÷ 2 Ò ·ÓÐhideProps.height = hideProps.paddingTop = hideProps.paddingBottom =Ð†–FU &÷ 2æ&÷&FW%F÷ v–GF, Ò hideProps.borderBottomWidth = "hide";ÐshowProps.height = showProps.paddingTop = showProps.paddingBottom =Ð6†÷u &÷ 2æ&÷&FW%F÷ v–GF, Ò showProps.borderBottomWidth = "show";Ð.widget("ui.accordion", {ÐfW'6–öã¢ "1.10.4",Ð÷ F–öç3¢ ™½active: 0,™Ðanimate: {},™Ðcollapsible: false,™Ðevent: "click",™Ð header: "> li > :first-child,> :not(li):even",™ÐheightStyle: "auto",™Ðicons: {™Ð activeHeader: "ui-icon-triangle-1-s",™Ð–†V FW#¢ 'V’Ö–6öâ×G&– ævÆRÓ ÖR™}™Ð/ callbacks™Ðactivate: null,™ÐeforeActivate: null™ÐÓö7&V FS¢ gVæ7F–öâ,’ ™½var options = this.options;™Ðthis.prevShow = this.prevHide = $();™Ð this.element.addClass("ui-accordion ui-widget ui-helper-reset")™Ð’òò $” ™’æ GG", '&öÆR"Â 'F &Æ—7B" ™½/ don't allow collapsible: false and active: false / null™Ðif (!options.collapsible && (options.active === false || options.active == null)) {™Ð–÷ F–öç2æ 7F—fR Ò ™½™Ðthis._processPanels();™Ð/ handle negative values™Ðif (options.active < 0) {™Ð÷ F–öç2æ 7F—fR ³Ò this.headers.length;™Ð™Ðthis._refresh();ÐÓövWD7&V FTWfVçDF F ¢ gVæ7F–öâ,’ ™½ return {™Ð–†V FW#¢ F†—2æ 7F—fRÍ æVÃ¢ F†—2æ 7F—fRæÆVæwF, ò B,’ ¢ this.active.next(),™Ð–6öçFVçC¢ F†—2æ 7F—fRæÆVæwF, ò B,’ ¢ F†—2æ 7F—fRææW‡B™};ÐÐ _createIcons: function() {™Ðvar icons = this.options.icons;™Ðif (icons) {™Ð $("")™Ð™.addClass("ui-accordion-header-icon ui-icon " + icons.header)Ð ™™.prependTo(this.headers);™Ð†—2æ 7F—fRæ6†–ÆG&Vâ, "çV’Ö 66÷&F–öâÖ†V FW"Ö–6öâ" • ™™.removeClass(icons.header™)™ÐaddClass(icons.activeHeader);™Ð this.headers.addClass("ui-accordion-icons");™Ð}™ÐÓöFW7G&÷”–6öç3¢ gVæ7F–öâ,’ ™½ this.headers™Ð’ç&VÖ÷fT6Æ 72, 'V’Ö 66÷&F–öâÖ–6öç2"™‘æ6†–ÆG&Vâ, "çV’Ö 66÷&F–öâÐ header-icon")™Ð™.remove();™ÐÓöFW7G&÷“¢ gVæ7F–öâ,’ ™½var contents™Ð/ clean up main element™Ðthis.element™Ðç&VÖ÷fT6Æ 72, 'V’Ö 66÷&F–öâ V’×v–FvWB V’Ö†VÇ W"×&W6WB" • ™’ç&VÖ÷fT GG", '&öÆR" ™½/ clean up header™Ðthis.header™Ðç&VÖ÷fT6Æ 72, 'V’Ð accordion-header ui-accordion-header-active ui-helper-reset ui-state-default ui-corner-all ui-state-active ui-state-disabled ui-corner-top")Ð ™’ç&VÖ÷fT GG", '&öÆR"™‘ç&VÖ÷fT GG", & &– ÖW‡ æFVB"™‘ç&VÖ÷fT GG", & &– Ð selected")™Ð’ç&VÖ÷fT GG", & &– Ö6öçG&öÇ2"™‘ç&VÖ÷fT GG", 'F $–æFW," • ™’æV 6,†gVæ7F–öâ,’™½if (/^ui-accordion/.test(this.id))™{™Ð this.removeAttribute("id");™Ð™}™Ð™½this._destroyIcons();™Ð/ clean up content panels™Ðcontents = this.headers.next();™Ðæ772, &F—7 Æ ’"Â ""™‘ç&VÖ÷fT GG", '&öÆR" • ™’ç&VÖ÷fT GG", & &– Ö†–FFVâ"™‘ç&VÖ÷fT GG", & &– ÖÆ &VÆÆVF''"™‘ç&VÖ÷fT6Æ 72, 'V’Ð helper-reset ui-widget-content ui-corner-bottom ui-accordion-content ui-accordion-content-active ui-state-disabled")™Ð’æV 6,†gVæ7F–öâ,’™½if (/^ui-accordion/.test(this.id)) {™Ð—F†—2ç&VÖ÷fT GG&–'WFR, &–B"™™½™Ð™½f (this.options.heightStyle !== "content") {™Ð–6öçFVçG2æ772, &†V–v‡B"Â "" ™½™ÐÓ _setOption: function(key, value) {™Ðif (key === "active") {™Ðòò ö 7F—f FR,’ will handle invalid values and update this.options™Ð—F†—2åö 7F—f FR, f ÇVR ™½ return;™Ð™Ðif (key === "event") {™Ð–b , F†—2æ÷ F–öç2æWfVçB ’™½ this._off(this.headers, this.options.event);™Ð™ÝF†—2å÷6WGW WfVçG2, f ÇVR ™½™Ð this._super(key, value);™Ð// setting collapsible: false while collapsed; open first panel™Ðif (key === "collapsible" && !value && this.options.active === false) {™Ð—F†—2åö 7F—f FR, ™½™Ðif (key === "icons") {™ÐF†—2åöFW7G&÷”–6öç2,™½–b (value) {™Ðthis._createIcons();™Ð™ÓÐ/ #5332 - opacity doesn't cascade to positioned elements in IE™Ð// so we need to add the disabled class to the headers and panels™Ð

™if (key === "disabled") {™Ð
this.headers.add(this.headers.next())Ð™.toggleClass("ui-state-disabled", !!
value);Ð™}ÒÉö¶W–F÷vã¢ gVæ7F–öâ, WfVçB ’ ™½if (event.altKey || event.ctrlKey) {™Ð
return;Ð™Ð™var keyCode = $.ui.keyCode,™ÐÆVæwF, Ò F†–2æ†V FW'2æÆVæwF™Í7W'&VçD–æFW,
= this.headers.index(event.target),Ð™–Fôfö7W2 Ò f Ç6™½switch (event.keyCode)
{Ð™–6 6R ¶W”6öFRå$”t…Ç–6 6R ¶W”6öFRäDõtã™toFocus = this.headers[(currentIndex
+ 1) % length];Ð™break;Ð™ 6R ¶W”6öFRäÄTeÇ–6 6R ¶W”6öFRåU™™toFocus =
this.headers[(currentIndex - 1 + length) % length];Ð™break;Ð™ 6R
keyCode.SPACE:Ð™–6 6R ¶W”6öFRäTåDU#™this._eventHandler(event);Ð™break;Ð™ 6R
keyCode.HOME:Ð™toFocus = this.headers[0];Ð™break;Ð™ 6R ¶W”6öFRäTäÇ™toFocus =
this.headers[length - 1];Ð™breakÐ™Ð™if (toFocus) {™Ð
$(event.target).attr("tabIndex", -1);Ð™’B, Fôfö7W2 ’æ GG", 'F $–æFW,"Â ™½
toFocus.focus();Ð™–WfVçBç &WfVçDFVf VÇB,™½ÐÉ÷ æVÄ¶W”F÷vâ ¢ gVæ7F–öâ, WfVçB ’ ™½
if (event.keyCode === $.ui.keyCode.UP && event.ctrlKey) {Ð™•
$(event.currentTarget).prev().focus();Ð™}ÒÉ&Vg&W6ƒ¢ gVæ7F–öâ,’ ™½var options =
this.options;Ð™this._processPanels();Ð™Ð™// was collapsed or no panel™Ð™if
((options.active === false && options.collapsible === true) || !
this.headers.length) {Ð™–÷ F–öç2æ 7F–fR Ò f Ç6™½F†–2æ 7F–fR Ò B,™½// active
false only when collapsible is trueÐ™} else if (options.active === false) {™Ð
this._activate(0);Ð™// was active, but active panel is gone™Ð™} else if
(this.active.length && !$.contains(this.element[0], this.active[0])) {Ð
™’òò ÆÂ &VÖ –æ–ær æVÂ &R F–6 &ÆVM–b , F†–2æ†V FW'2æÆVæwF, ÓÓÒ
this.headers.find(".ui-state-disabled").length) {Ð™options.active = false;™™Ð
this.active = $();Ð™’òò 7F–f FR &Wf–÷W2 æVÍÒ VÇ6R™½
this._activate(Math.max(0, options.active - 1));Ð™Ý// was active, active
panel still existsÐ™} else {™Ðòò Ö ¶R 7W&R 7F–fR –æFW, –2 6÷'&V™M÷ F–öç2æ 7F–fR
= this.headers.index(this.active);Ð™Ð™this._destroyIcons();Ð™this._refresh();ÐÉ
_processPanels: function() {™Ðthis.headers =
this.element.find(this.options.header)Ð™’æ FD6Æ 72, 'V’Ö 66÷&F–öâÖ†V FW" V’Ð
helper-reset ui-state-default ui-corner-all");Ð™this.headers.next()Ð
™’æ FD6Æ 72, 'V’Ö 66÷&F–öâÖ6öçFVçB V’Ö†VÇ W"×&W6WB V’×v–FvWBÖ6öçFVçB V’Ö6÷&æW"Ð
bottom")Ð™’æf–ÇFW",#¦æ÷B,çV’Ö 66÷&F–öâÖ6öçFVçBÖ 7F–fR’™‘æ†–FR,™ÐÉ÷&Vg&W6ƒ¢
function() {™Ðvar maxHeight;™Ð÷ F–öç2 Ò F†–2æ÷ F–öç™Í†V–v‡E7G–ÆR Ò
options.heightStyle,™Ð– &VçB Ò F†–2æVÆVÖVçBç &VçB,™Í 66÷&F–öä–B Ò
this.accordionId = "ui-accordion-" +™Ð™(this.element.attr("id") || ++uid™Ð™);Ð
this.active = this._findActive(options.active)™Ð’æ FD6Æ 72, 'V’Ö 66÷&F–öâÐ
header-active ui-state-active ui-corner-top")™Ð’ç&VÖ÷fT6Æ 72, 'V’Ö6÷&æW"Ö ÆÂ" ™½
this.active.next()™Ð’æ FD6Æ 72, 'V’Ö 66÷&F–öâÖ6öçFVçBÖ 7F–fR"™‘ç6†÷r,™½
this.headers™Ð’æ GG", '&öÆR"Â 'F ""™‘æV 6,†gVæ7F–öâ, ’ ’™½var header = $(this);™Ð
headerId = header.attr("id"),Ð™– æVÂ Ò †V FW"ææW‡B,™Í æVÄ–B Ò
panel.attr("id");Ð™if (!headerId)™{Ð†V FW$–B Ò 66÷&F–öä–B ² "Ö†V FW"Ò" ²™™½
header.attr("id", headerId);Ð™™™}™™™Ð™if (!panelId)™{Ð æVÄ–B Ò 66÷&F–öä–B ² "Ð
panel-" + i;Ð™– æVÂæ GG", &–B"Â æVÄ–B™™™™™½™™™™Ðeader.attr("aria-controls",
panelId);Ð™panel.attr("aria-labelledby", headerId);™™Ð‘ææW‡B,™•.attr("role",
"tabpanel");Ð™this.headers™™™Ðæ÷B, F†–2æ 7F–fR™‘æ GG"‡½™™™"aria-selected": "false",Ð
™™™"aria-expanded": "false",™™™™™

™™™

™™Ðif (!toShow.length) {™Ð&WGW&â Fô†–FRæ æ–Ö FR, †–FU &÷ 2Â
duration, easing, complete);™™™Ðtotal = toShow.show().outerHeight();™Ð
toHide.animate(hideProps, {™Ð–GW& F–öã¢ GW& F–öã™Í V 6–æs¢ V 6–æ™Í7FW ¢
function(now, fx) {™™™fx.now = Math.round(now);™™™Ð;™™™ÐdoShow™™™Ðæ†–FR,•
™'æ æ–Ö FR, 6†÷u &÷ 2Â™½duration: duration™™™Ðasing: easing™™™Ðomplete: complete™™™Ð
step: function(now, fx) {™™™–g,ææ÷r Ò Ö F,ç&÷VæB, æ÷r™™™½–b , g,ç &÷ ÓÒ
"height") {™™™™adjust += fx.now™™™÷Ð VÇ6R –b , F† Bæ÷ F–öç2æ†V–v‡E7G–ÆR ÓÒ
"content") {™™™™fx.now = Math.round(total - toHide.outerHeight() - adjust™™™™Ð
adjust = 0;™™™™

™™–'&V™™½case keyCode.PAGE_DOWN:ÐF†–2åöÖ÷fR, &æW‡E vR"Â WfVçB™™½'&V™™½
case keyCode.UP:Ð™–F†–2åö¶W”WfVçB, ' &Wf–÷W2"Â WfVçB™™½'&V™™½case keyCode.DOWN:Ð
this._keyEvent("next", event);Ð™–'&V™™½ÐÍ–ç WC¢ gVæ7F–öâ, WfVçB ’™™½if
(suppressInput) {Ð™–7W &W74–ç WB Ò f ÇÖS½WfVçBç &WfVçDFVf VÇB™™½&WGW&a½Ð
this._searchTimeout(event);Ð–ÒÍfö7W3¢ gVæ7F–öâ,’™™½this.selectedItem = null™Ð
this.previous = this._value();Ð–ÒÍ&ÇW#¢ gVæ7F–öâ, WfVçB ’™™½if
(this.cancelBlur) {Ð™–FVÆWFR F†–2æ6 æ6VÄ&ÇW#™™½&WGW&Ð™½Ð
clearTimeout(this.searching);Ð™this.close(event);Ðthis._change(event);™™½)™™Ð
this._initSource();Ðthis.menu = $("<ul>")™™Ðæ FD6Æ 72, 'V’Ö WFö6ö× ÆWFR V’Ð
front")™™Ð’æ VæEFò, F†–2åö VæEFò,’™™‘æÖVçR™™½// disable ARIA support, the live
region takes care of that™™role: null™™Ð‘æ†–FR™™‘æF F , 'V’ÖÖVçR" ™™½
this._on(this.menu.element, {™™–Ö÷W6VF÷vã¢ gVæ7F–öâ, WfVçB ’™™½// prevent moving
focus out of the text field™™event.preventDefault();™™Ð// IE doesn't prevent
moving focus even with event.preventDefault()™™// so we set a flag to know when
we should ignore the blur event™™this.cancelBlur = true™™Ðthis._delay(function()™™{™™Ð
delete this.cancelBlur;™™}™™Ð// clicking on the scrollbar causes focus to shift
to the body™™// but we can't detect a mouseup or a click immediately afterward™™Ð
™™// so we have to track the next mousedown and close the menu if™™Ð// the user
clicks somewhere outside of the autocomplete™™var menuElement =
this.menu.element[0];™™if (!$(event.target).closest(".ui-menu-
item").length) {™™–F†–2åöFVÆ ’†gVæ7F–öâ,™™½var that = this™™Ð
this.document.one("mousedown", function(event) {™™–-b , WfVçBçF &vWB ÓÒ
that.element[0] &&™™™™–WfVçBçF &vWB ÓÒ ÖVçTVÆVÖVçB™™™™bm Bæ6öçF –ç2, ÖVçTVÆVÖVçBÂ
event.target)) {™™™™that.close();™™™™

™™™Ð}Ðif (key === "disabled" &&
value && this.xhr) {Ð™–F†–2ç†‡"æ &÷'B,™½ÐÐÐö VæEFó¢ gVæ7F–öâ,’ ™½var element =
this.options.appendTo;Ðif (element) {ÐVÆVÖVçB Ò VÆVÖVçBæ§ VW'’ ÇÂ
element.nodeType ?Ð™$(element)™™™Ðthis.document.find(element).eq(0)™™™Ðif (!
element) {Ð–VÆVÖVçB Ò F†–2æVÆVÖVçBæ6Æ÷6W7B, "çV’Ög&öçB" ™™™Ðif (!
element.length) {Ð–VÆVÖVçB Ò F†–2æFö7VÖVçE³ Òæ&öG™™™Ðreturn element;ÐÐÐ
_initSource: function() {Ðvar array, url,™™™ÐF† B Ò F†–3½™™™Ðif
($.isArray(this.options.source)) {Ð™– '& ’ Ò F†–2æ÷ F–öç2ç6÷W&6™½F†–2ç6÷W&6R Ò
function(request, response) {Ð™™response($.ui.autocomplete.filter(array,
request.term));Ð™–Ó½ else if (typeof this.options.source === "string") {™™™ÐW&Â
= this.options.source;Ð™–F†–2ç6÷W&6R Ò gVæ7F–öâ, &W VW7BÂ &W7 öç6R ’™™™½if
(that.xhr) {Ð™™–F† Bç†‡"æ &÷'B,™™™½Ðthat.xhr = $.ajax({™™™ÐW&Ã¢ W&™™™ÂÎF F ¢ &W VW™™™BÎ
dataType: "json",Ð™™–7V66W73¢ gVæ7F–öâ, F F ™™™½response(data™™™™™™ÐÍW'&÷#¢
function() {Ð™™™response([])™™™™™™

™™™

this.menu.isLastItem() && /^next/.test(direction)) {™•
this._value(this.term);™–F†–2æÖVçRæ&ÇW"," ™½&WGW&ä™™Ðthis.menu[direction]
(event);ÐÒÉv–FvWC¢ gVæ7F–öâ,' ™return this.menu.element÷ÒÉ÷f ÇVS¢ gVæ7F–öâ,'
{™return this.valueMethod.apply(this.element, arguments)÷ÒÉö¶W"WfVçC¢
function(keyEvent, event) {™if (!this.isMultiLine ||
this.menu.element.is(":visible")) {™–F†–2åöÖ÷fR, ¶W"WfVçBÂ WfVçB ™½òò
prevents moving cursor to beginning/end of the text field in some browsers™•
event.preventDefault();™}É});Ð.extend($.ui.autocomplete, {ÐW66 U&VvWƒ¢
function(value) {™return value.replace(/[\-\[\]{}()*+?.,\\\^$|#\s]/g, "\\
$&");ÐÒÍf–ÇFW#¢ gVæ7F–öâ† '& 'Â FW&Ò' ™var matcher = new
RegExp($.ui.autocomplete.escapeRegex(term), "i");™return $.grep(array,
function(value) {™–&WGW&â Ö F6†W"çFW7B, f ÇVRæÆ &VÂ ÇÂ f ÇVRçf ÇVR ÇÂ f ÇVR "½
™})÷É});Ð/ live region extension, adding a `messages` optionÐ/ NOTE: This is
an experimental API. We are still investigatingÐ/ a full solution for string
manipulation and internationalization.Ð.widget("ui.autocomplete",
$.ui.autocomplete, {Ð÷ F–öç3¢ ™messages: {™Ðæõ&W7VÇG3¢ $æò 6V &6, &W7VÇG2â™Í
results: function(amount) {™™return amount + (amount > 1 ? " results are" :
" result is") +™™'" f –Æ &ÆRÂ W6R W æB F÷vâ '&÷r ¶W–2 Fò æ f–v FRä™™#½ÒÉ
__response: function(content) {™var message;™this._superApply(arguments);™if
(this.options.disabled || this.cancelSearch) {™–&WGW&ä™™Ðif (content &&
content.length) {™–ÖW76 vR Ò F†–2æ÷ F–öç2æÖW76 vW2ç&W7VÇG2, 6öçFVçBæÆVæwF, ™½
else {™–ÖW76 vR Ò F†–2æ÷ F–öç2æÖW76 vW2ææõ&W7VÇG3™™Ð
this.liveRegion.text(message);™É});Ð(jQuery));™function($, undefined) {Ð
var lastActive,Ð& 6T6Æ 76W2 Ò 'V'Ö'WGFöâ V'×v–FvWB V'×7F FRÖFVf VÇB V'Ö6÷&æW"Ð
all",ÐG– T6Æ 76W2 Ò 'V'Ö'WGFöâÖ–6öç2ÖöæÇ' V'Ö'WGFöâÖ–6öâÖöæÇ' V'Ö'WGFöâ×FW‡BÐ
icons ui-button-text-icon-primary ui-button-text-icon-secondary ui-button-
text-only",Ðf÷&Õ&W6WD† æFÆW" Ò gVæ7F–öâ,' ™var form = $(this);™Ð
setTimeout(function() {™–f÷&Òæf–æB, #§V'Ö'WGFöâ" 'æ'WGFöâ, '&Vg&W6," ™½, 1)÷ÒÍ
radioGroup = function(radio) {™var name = radio.name;™Ðf÷&Ò Ò & F–òæf÷&ÒÍ
radios = $([]);™if (name) {™Ðæ ÖR Ò æ ÖRç&W Æ 6R, òrörÂ %ÅÂr" ™½–b , f÷&Ò '™½
radios = $(form).find("[name='" + name + "']");™–Ò VÇ6R™½radios =
$("[name='" + name + "']", radio.ownerDocument)™™'æf–ÇFW"†gVæ7F–öâ,™™™½return !
this.form;™™–Ò™™½™™return radios÷É});Ð.widget("ui.button", {ÐfW'6–öã¢ # ã ãB"Í
defaultElement: "<button>",Ð÷ F–öç3¢ ™½disabled: null,™Ðext: true,™Ðabel: null,™Ð
icons: {™– &–Ö '"¢ çVÆÂÍ6V6öæF '"¢ çVÆ‡ÒÍö7&V FS¢ gVæ7F–öâ,' ™
this.element.closest("form")™'çVæ&–æB, '&W6WB" ² F†–2æWfVçDæ ÖW7 6R •
™'æ&–æB, '&W6WB" ² F†–2æWfVçDæ ÖW7 6RÂ f÷&Õ&W6WD† æFÆW" ™½f (typeof
this.options.disabled !== "boolean") {™–F†–2æ÷ F–öç2æF–6 &ÆVB Ò
this.element.prop("disabled");™} else {™F†–2æVÆVÖVçBç &÷ , &F–6 &ÆVB"Â
this.options.disabled);™™™™this._determineButtonType();™this.hasTitle = !!
this.buttonElement.attr("title");™var that = this;™÷ F–öç2 Ò F†–2æ÷ F–öç2Í
toggleButton = this.type === "checkbox" || this.type === "radio",™– 7F–fT6Æ 72
= !toggleButton ? "ui-state-active" : "";™if (options.label === null) {™Ð
options.label = (this.type === "input" ? this.buttonElement.val() :
this.buttonElement.html());™™™™this._hoverable(this.buttonElement);™Ð
this.buttonElement™'æ FD6Æ 72, & 6T6Æ 76W2™'æ GG", '&öÆR"Â &'WGFöâ" •
™'æ&–æB, &Ö÷W6VVçFW"" ² F†–2æWfVçDæ ÖW7 6RÂ gVæ7F–öâ,'™™if
(options.disabled) {™™–&WGW&ä™™™™Ðif (this === lastActive)™{™Ð
$(this).addClass("ui-state-active");™™}™'æ&–æB, &Ö÷W6VÆV fR" ²
this.eventNamespace, function() {™™if (options.disabled)™{™Ð&WGW&ä™™™™Ð
$(this).removeClass(activeClass);™–™'æ&–æB, &6Æ–6²" ² F†–2æWfVçDæ ÖW7 6RÂ
function(event) {™™if (options.disabled)™{™™™™

™ÐÐif (this.type === "checkbox") {™ÐF†—2æ'WGFöäVÆVÖVçBæ&–æB, &6Æ–6²" ²
this.eventNamespace, function() {Ð™if (options.disabled)™{Ð&WGW&â f ÇÓS½Ð™½
else if (this.type === "radio") {Ð™—F†—2æ'WGFöäVÆVÖVçBæ&–æB, &6Æ–6²" ²
this.eventNamespace, function() {Ð™if (options.disabled)™{Ð&WGW&â f ÇÓS½Ð
$(this).addClass("ui-state-active");Ð™that.buttonElement.attr("aria-
pressed", "true");Ð™var radio = that.element[0],ÐadioGroup(radio)Ð
™'ææ÷B, & F–Ö™‘æÖ †gVæ7F–öâ,™½return $(this).button("widget")[0™];Ò•
™'ç&VÖ÷fT6Æ 72, 'V'×7F FRÖ 7F—fR™‘æ GG", & &– × &W76VB"Â &f Ç6R"™—Ø½ else {Ð
this.buttonElementÐ™.bind("mousedown" + this.eventNamespace, function()™{Ð–b
(options.disabled) {Ð™™return false;ÐB, F†—2 'æ FD6Æ 72, 'V'×7F FRÖ 7F—fR"™™½
lastActive = this;Ð™—F† BæFö7VÖVçBæöæR, &Ö÷W6WW "Â gVæ7F–öâ,™½lastActive = null;Ð
™—Ö½™™™Ðbind("mouseup" + this.eventNamespace, function()™{Ð–b
(options.disabled) {Ð™™return false;ÐB, F†—2 'ç&VÖ÷fT6Æ 72, 'V'×7F FRÐ
active");Ð™™™Ðbind("keydown" + this.eventNamespace, function(event)™{Ð–b
(options.disabled) {Ð™™return false;Ð–b , WfVçBæ¶W"6öFR ÓÓÒ BçV'æ¶W"6öFRå5 4R
|| event.keyCode === $.ui.keyCode.ENTER) {Ð™™$(this).addClass("ui-state-
active");Ð™™™™Ð/ see #8559, we bind to blur here in case the button element
losesÐ™// focus between keydown and keyup, it would be left in an "active" stateÐ
™.bind("keyup" + this.eventNamespace + " blur" + this.eventNamespace,
function() {Ð™'B, F†—2 'ç&VÖ÷fT6Æ 72, 'V'×7F FRÖ 7F—fR"™™½Ð™÷Ðb
(this.buttonElement.is("a")) {Ð™this.buttonElement.keyup(function(event)™{Ð–b
(event.keyCode === $.ui.keyCode.SPACE) {Ð™™™// TODO pass through original event
correctly (just as 2nd argument doesn't work)Ð™™$(this).click()™;Ð™™™Ð/ TODO:
pull out $.Widget's handling for the disabled option intoÐ™//
$.Widget.prototype._setOptionDisabled so it's easy to proxy and canÐ™// be
overridden by individual pluginsÐ™this._setOption("disabled",
options.disabled);Ð™this._resetButton()™;ÐÓöFWFW&Ò–æT'WGFöåG— S¢ gVæ7F–öâ,' ™½
var ancestor, labelSelector, checked;Ð™if
(this.element.is("[type=checkbox]")) {Ð™—F†—2çG— R Ò &6†V6¶&÷,™½ else if
(this.element.is("[type=radio]")) {Ð™—F†—2çG— R Ò '& F–ò™½ else if
(this.element.is("input")) {Ð™—F†—2çG— R Ò &–ç WB™½ else {ÐF†—2çG— R Ò
"button";Ð™™™Ðif (this.type === "checkbox" || this.type === "radio") {Ðòò vR
don't search against the document in case the elementÐ™'òò —2 F—66öææV7FVB g&öÒ
the DOMÐ™– æ6W7F÷" Ò F†—2æVÆVÖVçBç &VçG2,'æÆ 7B,™½Æ &VÅ6VÆV7F÷" Ò &Æ &VÅ¶f÷#Òr"
+ this.element.attr("id") + "']";Ð™—F†—2æ'WGFöäVÆVÖVçB Ò
ancestor.find(labelSelector);Ð™––b , F†—2æ'WGFöäVÆVÖVçBæÆVæwF, '™½ancestor =
ancestor.length ? ancestor.siblings() : this.element.siblings();Ð™
this.buttonElement = ancestor.filter(labelSelector);Ð™if (!
this.buttonElement.length) {Ð™™—F†—2æ'WGFöäVÆVÖVçB Ò
ancestor.find(labelSelector);Ð™™™™ÓÐF†—2æVÆVÖVçBæ FD6Æ 72, 'V'Ö†VÇ W"Ö†–FFVâÐ
accessible");Ð™–6†V6¶VB Ò F†—2æVÆVÖVçBæ—2, #¦6†V6¶VB" ™½–b , 6†V6¶VB '™½
this.buttonElement.addClass("ui-state-active");Ð™™Ý
this.buttonElement.prop("aria-pressed", checked);Ð™} else {ÐF†—2æ'WGFöäVÆVÖVçB
= this.element;Ð™™™ÐÐv–FvWC¢ gVæ7F–öâ,' ™½return this.buttonElement™;ÐÐöFW7G&÷"¢
function() {Ðthis.elementÐç&VÖ÷fT6Æ 72, 'V'Ö†VÇ W"Ö†–FFVâÖ 66W76–&ÆR" ™½
this.buttonElementÐ™'ç&VÖ÷fT6Æ 72, & 6T6Æ 76W2 ² " V'×7F FRÖ 7F—fR " ²
typeClasses)Ð™'ç&VÖ÷fT GG", '&öÆR"™‘ç&VÖ÷fT GG", & &– × &W76VB" •
™'æ‡FÖÂ, F†—2æ'WGFöäVÆVÖVçBæf–æB,"çV'Ö'WGFöâ×FW‡B"'æ‡FÖÂ,' Ð™½f (!
this.hasTitle) {Ð™—F†—2æ'WGFöäVÆVÖVçBç&VÖ÷fT GG", 'F—FÆR" ™½™™™™

™™™™.removeClass("ui-state-active™™™™)Ðattr("aria-
pressed", "false");™™™}Ð™™½ else if (this.type === "checkbox") {™™Ð–b
(this.element.is(":checked")) {™™™this.buttonElement™™™™Ðæ FD6Æ 72, 'V'×7F FRÐ
active")™™™'æ GG", & &– × &W76VB"Â 'G'VR"™™™“Ò VÇ6R™™½this.buttonElementÐ
™™™'ç&VÖ÷fT6Æ 72, 'V'×7F FRÖ 7F–fR™™™‘æ GG", & &– × &W76VB"Â &f Ç6R"™™™¾ÒÐ
_resetButton: function() {™™if (this.type === "input") {™™Ð–b
(this.options.label) {™™™this.element.val(this.options.label);™™™Ð&WGW&a½™™™Ðar
buttonElement = this.buttonElement.removeClass(typeClasses);™™™Ð–'WGFöåFW‡B Ò
$("", this.document[0])™™™.addClass("ui-button-text")Ð
™™™.html(this.options.label™™™)™™™ÐappendTo(buttonElement.empty()™™™)™™™Ðtext();™™™Ð6öç2 Ò
this.options.icons,™™™Ð–×VÇF– ÆT–6öç2 Ò –6öç2ç &–Ö '' bb –6öç2ç6V6öæF '™™™Í
buttonClasses = [];™™™Ðif (icons.primary || icons.secondary) {™™™Ð–b
(this.options.text) {™™™buttonClasses.push("ui-button-text-icon" +
(multipleIcons ? "s" : (icons.primary ? "-primary" : "-secondary")));™™™™™™™Ý–b
(icons.primary) {™™™buttonElement.prepend("<span class='ui-button-icon-
primary ui-icon " + icons.primary + "'>");™™™™™™Ý–b , –6öç2ç6V6öæF '' ' ™™™½
buttonElement.append("<span class='ui-button-icon-secondary ui-icon " +
icons.secondary + "'>");™™™™™™Ý–b , F†–2æ÷ F–öç2çFW‡B '™™™½
buttonClasses.push(multipleIcons ? "ui-button-icons-only" : "ui-button-icon-
only");™™™if (!this.hasTitle)™™™™™™Ð'WGFöäVÆVÖVçBæ GG", 'F–FÆR"Â
$.trim(buttonText));™™™™™™™

—F†—2ç&Vv–öæ Â Ò µÓ² òò f –Æ &ÆR &Vv–öæ Â
settings, indexed by language codeÐF†—2ç&Vv–öæ Â²"%Ò Ò ² òò FVf VÇB &Vv–öæ Â
settingsÐcloseText: "Done", // Display text for close linkÐprevText: "Prev", //
Display text for previous month linkÐnextText: "Next", // Display text for
next month linkÐcurrentText: "Today", // Display text for current month linkÐ
monthNames: ["January","February","March","April","May","June",Ð
™'$§VÇ'"Â$ VwW7B"Â%6W FVÖ&W""Â$ö7Fö&W""Â$æ÷fVÖ&W""Â$FV6VÖ&W"%ÒÂ òò æ ÖW2 öb
months for drop-down and formattingÐmonthNamesShort: ["Jan", "Feb", "Mar",
"Apr", "May", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec"], // For
formattingÐdayNames: ["Sunday", "Monday", "Tuesday", "Wednesday", "Thursday",
"Friday", "Saturday"], // For formattingÐdayNamesShort: ["Sun", "Mon", "Tue",
"Wed", "Thu", "Fri", "Sat"], // For formattingÐdayNamesMin:
["Su","Mo","Tu","We","Th","Fr","Sa"], // Column headings for days starting at
SundayÐweekHeader: "Wk", // Column header for week of the yearÐdateFormat: "mm/
dd/yy", // See format options on parseDateÐfirstDay: 0, // The first day of
the week, Sun = 0, Mon = 1, ...ÐisRTL: false, // True if right-to-left
language, false if left-to-rightÐshowMonthAfterYear: false, // True if the
year select precedes month, false for month then yearÐyearSuffix: "" //
Additional text to append to the year in the month headersÐÓ½F†—2åöFVf VÇG2 Ò
{ // Global defaults for all the date picker instancesÐshowOn: "focus", //
"focus" for popup on focus,Ð'òò &'WGFöâ" f÷" G&–vvW" 'WGFöâÂ ÷" &&÷F," f÷"
eitherÐshowAnim: "fadeIn", // Name of jQuery animation for popupsÐshowOptions:
{}, // Options for enhanced animationsÐdefaultDate: null, // Used when field
is blank: actual date,Ð'òò ²òÖçVÖ&W" f÷" öfg6WB g&öÒ FöF 'Â çVÆÂ f÷" FöF™•
appendText: "", // Display text following the input box, e.g. showing the
formatÐbuttonText: "...", // Text for trigger buttonÐbuttonImage: "", // URL
for trigger button imageÐbuttonImageOnly: false, // True if the image appears
alone, false if it appears on a buttonÐhideIfNoPrevNext: false, // True to
hide next/previous month linksÐ'òò –b æ÷B Æ–6 &ÆRÂ f Ç6R Fò §W7B F—6 &ÆR F†ÐÝ
navigationAsDateFormat: false, // True if date formatting applied to prev/
today/next linksÐgotoCurrent: false, // True if today link goes back to
current selection insteadÐchangeMonth: false, // True if month can be selected
directly, false if only prev/nextÐchangeYear: false, // True if year can be
selected directly, false if only prev/nextÐyearRange: "c-10:c+10", // Range of
years to display in drop-down,Ð'òò V—F†W" &VÆ F—fR Fò FöF 'w2 –V " ,Öæã¢¶æâ'Â
relative to currently displayed yearÐ'òò †2Öæã¦2¶æâ'Â '6öÇWFR †æææã¦æææâ'Â ÷"
a combination of the above (nnnn:-n)ÐshowOtherMonths: false, // True to show
dates in other months, false to leave blankÐselectOtherMonths: false, // True
to allow selection of dates in other months, false for unselectableÐshowWeek:
false, // True to show week of the year, false to not show itÐcalculateWeek:
this.iso8601Week, // How to calculate the week of the year,Ð'òò F ¶W2 F FR
and returns the number of the week for itÐshortYearCutoff: "+10", // Short
year values < this are in the current century,Ð'òò â F†—2 &R –â F†R &Wf–÷W2
century,Ð'òò 7G&–ær f ÇVR 7F 'F–ær v—F, "²" f÷" 7W'&VçB –V " ² f ÇVÐminDate:
null, // The earliest selectable date, or null for no limitÐmaxDate: null, //
The latest selectable date, or null for no limitÐduration: "fast", // Duration
of display/closureÐbeforeShowDay: null, // Function that takes a date and
returns an array withÐ'òò ³ Ò Ò G'VR –b 6VÆV7F &ÆRÂ f Ç6R –b æ÷BÂ ³ Ò Ò 7W7FöÒ
CSS class name(s) or "",Ð'òò ³%Ò Ò 6VÆÂ F—FÆR †÷ F–öæ Â'Â Rærâ
$.datepicker.noWeekendsÐbeforeShow: null, // Function that takes an input
field andÐ'òò &WGW&ç2 6WB öb 7W7FöÒ 6WGF–æw2 f÷" F†R F FR –6¶WÐonSelect:
null, // Define a callback function when a date is selectedÐonChangeMonthYear:
null, // Define a callback function when the month or year is changedÐonClose:
null, // Define a callback function when the datepicker is closedÐ
numberOfMonths: 1, // Number of months to show at a timeÐshowCurrentAtPos:
0, // The position in multipe months at which to show the current month
(starting at 0)ÐstepMonths: 1, // Number of months to step back/forwardÐ
stepBigMonths: 12, // Number of months to step back/forward for the big linksÐ
altField: "", // Selector for an alternate field to store selected dates intoÐ
altFormat: "", // The date format to use for the alternate fieldÐ

™

constrainInput: true, // The input is constrained by the current date formatÐ™
showButtonPanel: false, // True to show button panel, false to not show itÐ™
autoSize: false, // True to size the input for the date format, false to
leave as isÐ™disabled: false // The initial disabled stateÐÓ½
$.extend(this._defaults, this.regional[""]);ÐÞF†–2æG F–b Ò &–æD†÷fW",B,#ÆF–b
id='" + this._mainDivId + "' class='ui-datepicker ui-widget ui-widget-content
ui-helper-clearfix ui-corner-all'> "));ÐÞÐ.extend(Datepicker.prototype, {Ðð
* Class name added to elements to indicate already configured with a date
picker. */ÐÖ &¶W$6Æ 74æ ÖS¢ &† 4F FW –6¶W"ÐÓòô¶VW G& 6² öb F†R Ö †–×VÒ çVÖ&W"
of rows displayed (see #7043)ÐÖ …&÷w3¢ BÐÓòò DôDò &Væ ÖR Fò 'v–FvWB" v†Vâ
switching to widget factoryÐ÷v–FvWDF FW –6¶W#¢ gVæ7F–öâ,’ ½return this.dpDiv÷ÒÐÓ
’ò¢ ÷fW'&–FR F†R FVf VÇB 6WGF–æw2 f÷" ÆÂ –ç7F æ6W2 öb F†R F FR –6¶W"Í ¢
@param settings object - the new settings to use as defaults (anonymous
object)Ð ¢ &WGW&â F†R Ö æ vW" ö&¦V7Ñ ¢ý6WDFVf VÇG3¢ gVæ7F–öâ‡6WGF–æw2’ ½
extendRemove(this._defaults, settings || {});Ð™return this÷ÒÐÓò¢ GF 6, F†R F FR
picker to a jQuery selection.Ð ¢   & Ò F &vWIelement - the target input
field or division or spanÐ ¢   & Ò 6WGF–æw2 ö&¦V7B Ò F†R æWr 6WGF–æw2 Fò
use for this date picker instance (anonymous)Ð ¢ýö GF 6„F FW –6¶W#¢
function(target, settings) {Ð™var nodeName, inline, inst;Ð™nodeName =
target.nodeName.toLowerCase();Ð™inline = (nodeName === "div" || nodeName ===
"span");Ð™if (!target.id) {ÐÞF†–2çWV–B ³Ò ™½F &vWBæ–B Ò &G " ² F†–2çWV–C½Ð™nst =
this._newInst($(target), inline);Ð™inst.settings = $.extend({}, settings || {});Ð™
if (nodeName === "input") {Ð™–F†–2åö6öææV7DF FW –6¶W"‡F &vWBÂ –ç7B™½ else if
(inline) {Ð™–F†–2åö–æÆ–æTF FW –6¶W"‡F &vWBÂ –ç7B™½ÐÓòò¢ 7&V FR   æWr –ç7F æ6R
object. */ÐöæWt–ç7C¢ gVæ7F–öâ‡F &vWBÂ –æÆ–æR’ ½var id = target[0].id.replace(/
([^A-Za-z0-9_\-])/g, "\\\\$1"); // escape jQuery meta charsÐ™return {id: id,
input: target, // associated targetÐ™–6VÆV7FVDF “¢ Â 6VÆV7FVDÖöçFƒ¢ Â
selectedYear: 0, // current selectionÐ™–G& tÖöçFƒ¢ Â G& u–V #¢ Â òò ÖöçF,
being drawnÐ™––æÆ–æS¢ –æÆ–æRÂ òò –2 F FW –6¶W" –æÆ–æR ÷" æ÷™MG F–c¢ , –æÆ–æR ò
this.dpDiv : // presentation divÐ™–&–æD†÷fW",B,#ÆF–b 6Æ 73Òr" ²
this._inlineClass + " ui-datepicker ui-widget ui-widget-content ui-helper-
clearfix ui-corner-all'> ")))};ÐÒÐÓòò¢ GF 6, F†R F FR –6¶W" Fò â –ç WB
field. */Ðö6öææV7DF FW –6¶W#¢ gVæ7F–öâ‡F &vWBÂ –ç7B’ ½var input = $(target);Ð™
inst.append = $([]);Ð™inst.trigger = $([]);Ð™if
(input.hasClass(this.markerClassName)) {Ð™–&WGW&â½Ð™this._attachments(input,
inst);Ð™input.addClass(this.markerClassName).keydown(this._doKeyDown);Ð™
keypress(this._doKeyPress).keyup(this._doKeyUp);Ð™this._autoSize(inst);Ð™
$.data(target, PROP_NAME, inst);Ð™//If disabled option is true, disable the
datepicker once it has been attached to the input (see ticket #5665)Ð™
if(inst.settings.disabled) {Ð™–F†–2åöF–6 &ÆTF FW –6¶W", F &vWB ™½ÐÓòò¢ Ö ¶R
attachments based on settings. */Ðö GF 6†ÖVçG3¢ gVæ7F–öâ†–ç WBÂ –ç7B’ ½var
showOn, buttonText, buttonImage,Ð™–   VæEFW‡B Ò F†–2åövWB†–ç7BÂ &   VæEFW‡B"™Í
isRTL = this._get(inst, "isRTL");Ð™if (inst.append) {Ð™–ç7Bæ   VæBç&VÖ÷fR,™½Ð™f
(appendText) {Ð™––ç7Bæ   VæB Ò B,#Ç7 â 6Æ 73Òr" ² F†–2åö   VæD6Æ 72 ² "sâ" ²
appendText + "");Ð™––ç WE¶–5%DÂ ò &&Vf÷&R" ¢ & gFW"%Ò†–ç7Bæ   VæB™½Ð
input.unbind("focus", this._showDatepicker);Ð™if (inst.trigger) {Ð™
inst.trigger.remove();Ð™½ÐshowOn = this._get(inst, "showOn");Ð™if (showOn ===
"focus" || showOn === "both") { // pop-up date picker when in the marked fieldÐ™•
input.focus(this._showDatepicker);Ð™}Ð™if (showOn === "button" || showOn ===
"both") { // pop-up date picker when button clickedÐ™–'WGFöåFW‡B Ò
this._get(inst, "buttonText");Ð™–'WGFöä–Ö vR Ò F†–2åövWB†–ç7BÂ &'WGFöä–Ö vR"™½
inst.trigger = $(this._get(inst, "buttonImageOnly") ?Ð™$("<img/
>").addClass(this._triggerClass).Ð™– GG"‡² 7&3¢ 'WGFöä–Ö vRÂ ÇC¢ 'WGFöåFW‡BÂ
title: buttonText }) :Ð™$("<button type='button'></
button>").addClass(this._triggerClass).Ð™–‡FÖÂ, 'WGFöä–Ö vR ò 'WGFöåFW‡B ¢
$("<img/>").attr(Ð™–² 7&3¦'WGFöä–Ö vRÂ ÇC¦'WGFöåFW‡BÂ F–FÆS¦'WGFöåFW‡B Ò’™½
input[isRTL ? "before" : "after"](inst.trigger);Ð™––ç7BçG&–vvW"æ6Æ–6²†gVæ7F–öâ,’
{Ð™if ($.datepicker._datepickerShowing && $.datepicker._lastInput === input[0])
{Ð

™™'BæF FW –6¶W"åö†–FTF FW –6¶W"™™½ else if ($.datepicker._datepickerShowing &&
$.datepicker._lastInput !== input[0]) {™™'BæF FW –6¶W"åö†–FTF FW –6¶W"™™½
$.datepicker._showDatepicker(input[0]);™™} else™™{™™
$.datepicker._showDatepicker(input[0]);™™}™™return false™™;™™½™™Ò¢ Ç' F†R
maximum length for the date format. */™™ö WFõ6–¦S¢ gVæ7F–öâ†–ç7B' ™™½if
(this._get(inst, "autoSize") && !inst.inline) {™™–f " f–æDÖ ,Â Ö ,Â Ö „'Â ™™Ídate
= new Date(2009, 12 - 1, 20), // Ensure double digits™™dateFormat =
this._get(inst, "dateFormat");™™––b †F FTf÷&Ö BæÖ F6,,õ´DÕÒò''™™½findMax =
function(names) {™™–Ö , Ò™™™½Ö „' Ò™™™½f÷" †' Ò ² ' Â æ ÖW2æÆVæwFƒ² '²²™™™½if
(names[i].length > max) {™™™™–Ö , Ò æ ÖW5¶•ÒæÆVæW™™™™

™™unbind("focus",
this._showDatepicker).Ð™unbind("keydown", this._doKeyDown)™Ðnbind("keypress",
this._doKeyPress).Ð™unbind("keyup", this._doKeyUp)™}Ðelse if (nodeName ===
"div" || nodeName === "span") {Ð•
$target.removeClass(this.markerClassName).empty();Ð™}ÐÓÒò¢ Væ &ÆR F†R F FR
picker to a jQuery selection.Ð ¢ & Ò F &vWIelement - the target input
field or division or spanÐ ¢ýöVæ &ÆTF FW –6¶W#¢ gVæ7F–öâ‡F &vWB’ ½var
nodeName, inline,Ð’GF &vWB Ò B‡F &vWB™Í–ç7B Ò BæF F ‡F &vWBÂ $õ ôä ÔRÐ½f (!
$target.hasClass(this.markerClassName)) {Ð—&WGW&â™ÐnodeName =
target.nodeName.toLowerCase();Ð™if (nodeName === "input") {Ð™F &vWBæF—6 &ÆVB Ò
false;Ð™––ç7BçG&–vvW"æf–ÇFW",&'WGFöâ"™™each(function() { this.disabled =
false; }).end().Ð™filter("img").css({opacity: "1.0", cursor: ""});Ð™}Ðelse if
(nodeName === "div" || nodeName === "span") {Ð™––æÆ–æR Ò GF &vWBæ6†–ÆG&Vâ,"â" ²
this._inlineClass);Ð™––æÆ–æRæ6†–ÆG&Vâ,’ç&VÖ÷fT6Æ 72,'V’×7F FRÖF—6 &ÆVB"™½
inline.find("select.ui-datepicker-month, select.ui-datepicker-year").Ð™
prop("disabled", false);Ð™}Ðthis._disabledInputs = $.map(this._disabledInputs,Ð™
function(value) { return (value === target ? null : value); }); // delete
entryÐÒÓÒò¢ F—6 &ÆR F†R F FR –6¶W" Fò ¥ VW'’ 6VÆV7F–öâÍ ¢ & Ò F &vWI
element - the target input field or division or spanÐ ¢ýöF—6 &ÆTF FW –6¶W#¢
function(target) {Ð™var nodeName, inline,Ð™GF &vWB Ò B‡F &vWB™Í–ç7B Ò
$.data(target, PROP_NAME);Ð™if (!$target.hasClass(this.markerClassName)) {Ð™
return;Ð™Ð™nodeName = target.nodeName.toLowerCase();Ð™if (nodeName === "input") {Ð™
target.disabled = true;Ð™––ç7BçG&–vvW"æf–ÇFW",&'WGFöâ"™™each(function()
{ this.disabled = true; }).end().Ð™filter("img").css({opacity: "0.5", cursor:
"default"});Ð™} else if (nodeName === "div" || nodeName === "span") {Ð™–æÆ–æR Ò
$target.children("." + this._inlineClass);Ð™––æÆ–æRæ6†–ÆG&Vâ,’æ FD6Æ 72,'V’Ð
state-disabled");Ð™––æÆ–æRæf–æB,'6VÆV7BçV’ÖF FW –6¶W"ÖÖöçF,Â 6VÆV7BçV’Ð
datepicker-year").Ð™prop("disabled", true);Ð™}Ðthis._disabledInputs =
$.map(this._disabledInputs,Ð™–gVæ7F–öâ‡f ÇVR’ ² &WGW&â ‡f ÇVR ÓÓÒ F &vWB ò
null : value); }); // delete entryÐ™
this._disabledInputs[this._disabledInputs.length] = target;ÐÒÓÒò¢ —2 F†R f—'7B
field in a jQuery collection disabled as a datepicker?Ð ¢ & Ò F &vWI
element - the target input field or division or spanÐ ¢ &WGW&â &öö&V â Ò G'VR
if disabled, false if enabledÐ ¢ýö—4F—6 &ÆVDF FW –6¶W#¢ gVæ7F–öâ‡F &vWB’ ½if (!
target) {Ð™—&WGW&â f Ç6S½Ð™or (var i = 0; i < this._disabledInputs.length; i++) {Ð™
if (this._disabledInputs[i] === target) {Ð™return true;Ð™Ð™Ðeturn false;ÐÓÒò¢
Retrieve the instance data for the target control.Ð ¢ & Ò F &vWB VÆVÖVçB
- the target input field or division or spanÐ ¢ &WGW&â ö&¦V7B Ò F†R
associated instance dataÐ ¢ F‡&÷w2 W'&÷" –b ¥ VW'’ &ö&ÆVÒ vWGF–ær F F’ ¢ý
_getInst: function(target) {Ð™try {Ð™&WGW&â BæF F ‡F &vWBÂ $õ ôä ÔR™½Ð™atch
(err) {Ð™—F‡&÷r $Ö—76–ær –ç7F æ6R F F f÷" F†—2 F FW –6¶W"#½ÐÓÒò¢ W F FR ÷"
retrieve the settings for a date picker attached to an input field or
division.Ð ¢ & Ò F &vWB VÆVÖVçB Ò F†R F &vWB –ç WB f–VÆB ÷" F—f—6–öâ ÷"
spanÐ ¢ & Ò æ ÖYobject - the new settings to update orÐ©™—7G&–ær Ò F†R æ ÖR
of the setting to change or retrieve,Ð ©™—v†Vâ &WG&–Wf–ær Ç6ò & ÆÂ" f÷" ÆÂ
instance settings orÐ ©™’&FVf VÇG2" f÷" ÆÂ vÆö& Â FVf VÇG¢ & Ò f ÇVR
any - the new value for the settingÐ ©™’†öÖ—B –b &÷fR —2 â ö&¦V7B ÷" Fò
retrieve a value)Ð ¢ýö÷ F–öäF FW –6¶W#¢ gVæ7F–öâ‡F &vWBÂ æ ÖRÂ f ÇVR’ ½var
settings, date, minDate, maxDate,Ð––ç7B Ò F†—2åövWD–ç7B‡F &vWBÐ½f
(arguments.length === 2 && typeof name === "string") {Ð™—&WGW&â †æ ÖR ÓÓÒ
"defaults" ? $.extend({}, $.datepicker._defaults) :Ð™(inst ? (name === "all" ?
$.extend({}, inst.settings) :Ð™this._get(inst, name)) : null);Ð™Ðettings = name
|| {};Ð™if (typeof name === "string") {Ð™6WGF–æw2 Ò ·Ö½6WGF–æw5¶æ ÖUÒ Ò f ÇVS½Ð™f
(inst) {Ð™––b ‡F†—2åö7W$–ç7B ÓÓÒ –ç7B’™½this._hideDatepicker();Ð™ÐF FR Ò
this._getDateDatepicker(target, true);Ð™–Ö–äF FR Ò F†—2åövWDÖ–äÖ „F FR†–ç7BÂ
"min");Ð™–Ö „F FR Ò F†—2åövWDÖ–äÖ „F FR†–ç7BÂ &Ö ,"™½W‡FVæE&VÖ÷fR†–ç7Bç6WGF–æw2Â
settings);Ð™’òò &Vf÷&Ö B F†R öÆB Ö–äF FRöÖ „F FR f ÇVW2 –b F FTf÷&Ö B 6† ævW2
and a new minDate/maxDate isn't providedÐ™––b †Ö–äF FR ÓÒ çVÆÂ bb
settings.dateFormat !== undefined && settings.minDate === undefined) {Ð™
inst.settings.minDate = this._formatDate(inst, minDate);Ð

™¥–b †Ö „F FR ÓÒ çVÆÂ
&& settings.dateFormat !== undefined && settings.maxDate === undefined) {Ð™
inst.settings.maxDate = this._formatDate(inst, maxDate);Ð™¥–b , &F—6 &ÆVB" –â
settings) {Ð™if (settings.disabled)™{ÐF†—2åöF—6 &ÆTF FW –6¶W"‡F &vWB™½ else™{Ð
this._enableDatepicker(target);Ð™}ÐF†—2åö GF 6†ÖVçG2,B‡F &vWB'Â –ç7B™½
this._autoSize(inst);Ð—F†—2å÷6WDF FR†–ç7BÂ F FR™½F†—2å÷W F FT ÇFW&æ FR†–ç7B™½
this._updateDatepicker(inst);Ð}ÒÐòò 6† ævR ÖWF†öB FW &V6 FVMö6† ævTF FW –6¶W#¢
function(target, name, value) {Ðthis._optionDatepicker(target, name, value);ÒÐð
* Redraw the date picker attached to an input field or division.Ð ¢   & Ò
target element - the target input field or division or spanÐ ¢ý
_refreshDatepicker: function(target) {Ðvar inst = this._getInst(target);Ðif
(inst) {Ð—F†—2å÷W F FTF FW –6¶W"†–ç7B™½ÒÐòò¢ 6WB F†R F FW2 f÷"   ¥ VW''
selection.Ð ¢   & Ò F &vWB VÆVÖVçB Ò F†R F &vWB –ç WB f–VÆB ÷" F—f—6–öâ ÷"
spanÐ ¢   & Ò F FYDate - the new dateÐ¢ý÷6WDF FTF FW –6¶W#¢ gVæ7F–öâ‡F &vWBÂ
date) {Ðvar inst = this._getInst(target);Ðif (inst) {ÐF†—2å÷6WDF FR†–ç7BÂ F FR™½
this._updateDatepicker(inst);Ð—F†—2å÷W F FT ÇFW&æ FR†–ç7B™½ÒÐòò¢ vWB F†R
date(s) for the first entry in a jQuery selection.Ð ¢   & Ò F &vWB VÆVÖVçB Ò
the target input field or division or spanÐ ¢   & Ò æâFVf VÇB &ööÆV â Ò G'VR
if no default date is to be usedÐ ¢ &WGW&â F FR Ò F†R 7W'&VçB F F] ¢ý
_getDateDatepicker: function(target, noDefault) {Ðvar inst =
this._getInst(target);Ðif (inst && !inst.inline) {ÐF†—2å÷6WDF FTg&öÔf–VÆB†–ç7BÂ
noDefault);Ð}Ðeturn (inst ? this._getDate(inst) : null);ÒÐòò¢ † æFÆR
keystrokes. */ÐööFô¶W"F÷vã¢ gVæ7F–öâ†WfVçB' ½var onSelect, dateStr, sel,Ð–ç7B Ò
$.datepicker._getInst(event.target),Ð–† æFÆVB Ò G'VRÍ—5%DÂ Ò –ç7BæG F—bæ—2,"çV'Ð
datepicker-rtl");Ðinst._keyEvent = true;Ðif ($.datepicker._datepickerShowing) {Ð
switch (event.keyCode) {Ð™case 9: $.datepicker._hideDatepicker();Ðhandled =
false;Ð™break; // hide on tab OutÐcase 13: sel = $("td." +
$.datepicker._dayOverClass + ":not(." +Ð™'BæF FW –6¶W"åö7W'&VçD6Æ 72 ² "'"Â
inst.dpDiv);Ð™if (sel[0]) {ÐBæF FW –6¶W"å÷6VÆV7DF '†WfVçBçF &vWBÂ
inst.selectedMonth, inst.selectedYear, sel[0]);ÐÐ™}ÐonSelect =
$.datepicker._get(inst, "onSelect");Ð™if (onSelect) {ÐF FU7G" Ò
$.datepicker._formatDate(inst);Ð™'òò G&–vvW" 7W7FöÒ 6 ÆÆ& ó½
onSelect.apply((inst.input ? inst.input[0] : null), [dateStr, inst]);Ð™} else™{Ð
$.datepicker._hideDatepicker();ÐÐ™}Ðeturn false; // don't submit the formÐcase
27: $.datepicker._hideDatepicker();Ð™break; // hide on escapeÐcase 33:
$.datepicker._adjustDate(event.target, (event.ctrlKey ?Ð™'Ð
$.datepicker._get(inst, "stepBigMonths") :Ð™'ÒBæF FW –6¶W"åövWB†–ç7BÂ
"stepMonths")), "M");Ð™break; // previous month/year on page up/+ ctrlÐcase 34:
$.datepicker._adjustDate(event.target, (event.ctrlKey ?Ð™'°
$.datepicker._get(inst, "stepBigMonths") :Ð™'²BæF FW –6¶W"åövWB†–ç7BÂ
"stepMonths")), "M");Ð™break; // next month/year on page down/+ ctrlÐcase 35: if
(event.ctrlKey || event.metaKey) {Ð™'BæF FW –6¶W"åö6ÆV $F FR†WfVçBçF &vWB™½Ð
handled = event.ctrlKey || event.metaKey;Ð™break; // clear on ctrl or command
+endÐ™case 36: if (event.ctrlKey || event.metaKey) {Ð™
$.datepicker._gotoToday(event.target);Ð™}Ðandled = event.ctrlKey ||
event.metaKey;Ð™break; // current on ctrl or command +homeÐcase 37: if
(event.ctrlKey || event.metaKey) {Ð™'BæF FW –6¶W"åö F§W7DF FR†WfVçBçF &vWBÂ
(isRTL ? +1 : -1), "D");Ð™}Ðandled = event.ctrlKey || event.metaKey;Ð// -1 day
on ctrl or command +leftÐ™if (event.originalEvent.altKey) {Ð
$.datepicker._adjustDate(event.target, (event.ctrlKey ?Ð™™-
$.datepicker._get(inst, "stepBigMonths") :Ð™™-$.datepicker._get(inst,
"stepMonths")), "M");Ð™}Ð// next month/year on alt +left on MacÐbreakçÐcase 38: if
(event.ctrlKey || event.metaKey) {Ð™'BæF FW –6¶W"åö F§W7DF FR†WfVçBçF &vWBÂ ÓrÂ
"D");Ð™}Ðandled = event.ctrlKey || event.metaKey;Ðbreak; // -1 week on ctrl or
command +upÐ™case 39: if (event.ctrlKey || event.metaKey) {Ð™
$.datepicker._adjustDate(event.target, (isRTL ? -1 : +1), "D");Ð™}Ðandled =
event.ctrlKey || event.metaKey;Ð™// +1 day on ctrl or command +rightÐif
(event.originalEvent.altKey) {Ð™'BæF FW –6¶W"åö F§W7DF FR†WfVçBçF &vWBÂ
(event.ctrlKey ?Ð™™+$.datepicker._get(inst, "stepBigMonths") :Ð
$.datepicker._get(inst, "stepMonths")), "M");Ð

}Ð/ next month/year on alt +right
break;case 40: if (event.ctrlKey || event.metaKey){Ð•
$.datepicker._adjustDate(event.target, +7, "D");}handled = event.ctrlKey ||
event.metaKey;break; // +1 week on ctrl or command +doWndefault: handled =
false;} else if (event.keyCode === 36 && event.ctrlKey) { // display the
date picker on ctrl+homeÐ'BæF FW –6¶W"å÷6†÷tF FW –6¶W"‡F†–2 ½ else †æFÆVB Ò
false;}Ðif (handled) {ÐWfVçBç &WfVçDFVf VÇB,½WfVçBç7F÷ &÷ v F–öâ,½ÒÒò¢
Filter entered characters - based on date format. */ÐöFô¶W• &W73¢
function(event) {var chars, chr,Ð–ç7B Ò BæF FW –6¶W"åövWD–ç7B†WfVçBçF &vWBÐ½f
($.datepicker._get(inst, "constrainInput")) {Ð–6† '2 Ò
$.datepicker._possibleChars($.datepicker._get(inst, "dateFormat"));Ð–6‡" Ò
String.fromCharCode(event.charCode == null ? event.keyCode : event.charCode);Ð•
return event.ctrlKey || event.metaKey || (chr < " " || !chars ||
chars.indexOf(chr) > -1);}ÒÒò¢ 7–æ6‡&öæ–6R Ö çV Â VçG'' æB f–VÆBö ÇFW&æ FR
field. */ÐöFô¶W•W ¢ gVæ7F–öâ†WfVçB' ½var date,Ð–ç7B Ò
$.datepicker._getInst(event.target);Ðif (inst.input.val() !== inst.lastVal) {Ð
try {Ðdate = $.datepicker.parseDate($.datepicker._get(inst, "dateFormat"),Ð
(inst.input ? inst.input.val() : null),Ð'BæF FW –6¶W"åövWDf÷&Ö D6öæf–r†–ç7BÐ½
if (date) { // only if validÐ'BæF FW –6¶W"å÷6WDF FTg&öÔf–VÆB†–ç7B½
$.datepicker._updateAlternate(inst);Ð'BæF FW –6¶W"å÷W F FTF FW –6¶W"†–ç7B½Ð
catch (err) {}Ðreturn true;ÒÒò¢ ÷ ×W F†R F FR –6¶W" f÷"   v–fVâ –ç WB
field.Ð ¢ –b f Ç6R &WGW&æVB g&öÒ &Vf÷&U6†÷r WfVçB † æFÆW" Fò æ÷B 6†÷rí ¢
@param input element - the input field attached to the date picker orÐ ©
event - if triggered by focusÐ ¢÷6†÷tF FW –6¶W#¢ gVæ7F–öâ†–ç WB' ½input =
input.target || input;Ðif (input.nodeName.toLowerCase() !== "input") { // find
from button/image triggerÐ––ç WB Ò B,&–ç WB"Â –ç WBç &VçDæöFR•³ ÓÐ½Ðf
($.datepicker._isDisabledDatepicker(input) || $.datepicker._lastInput ===
input) { // already hereÐ–&WGW&æÐÐvar inst, beforeShow, beforeShowSettings,
isFixed,Ð–öfg6WBÂ 6†÷t æ–ÒÂ GW& F–öÐ½nst = $.datepicker._getInst(input);Ðf
($.datepicker._curInst && $.datepicker._curInst !== inst) {Ð•
$.datepicker._curInst.dpDiv.stop(true, true);Ð––b , –ç7B bb
$.datepicker._datepickerShowing) {Ð
$.datepicker._hideDatepicker($.datepicker._curInst.input[0]);Ð–ÐbeforeShow =
$.datepicker._get(inst, "beforeShow");ÐbeforeShowSettings = beforeShow ?
beforeShow.apply(input, [input, inst]) : {};Ðif(beforeShowSettings === false){Ð
return;}ÐextendRemove(inst.settings, beforeShowSettings);ÐÐnst.lastVal = null,Ð
$.datepicker._lastInput = input;Ð$.datepicker._setDateFromField(inst);ÐÐf
($.datepicker._inDialog) { // hide cursorÐ––ç WBçf ÇVR Ò "#½Ðf (!
$.datepicker._pos) { // position below inputÐ'BæF FW –6¶W"å÷ ÷2 Ò
$.datepicker._findPos(input);Ð'BæF FW –6¶W"å÷ ÷5³ Ò ³Ò –ç WBæöfg6WD†V–v‡C² òò
add the heightÐÐsFixed = false,Ð(input).parents().each(function() {Ð–4f–†VB ÃÒ
$(this).css("position") === "fixed";Ð–&WGW&â –4f–†VC½)ÐÐffset = {left:
$.datepicker._pos[0], top: $.datepicker._pos[1]};Ð$.datepicker._pos = null,Ð/
to avoid flashes on FirefoxÐinst.dpDiv.empty();Ð/ determine sizing offscreeÐÐ
inst.dpDiv.css({position: "absolute", display: "block", top: "-1000px"});Ð
$.datepicker._updateDatepicker(inst);Ð// fix width for dynamic number of date
pickersÐ// and adjust position before showingÐffset =
$.datepicker._checkOffset(inst, offset, isFixed);Ðinst.dpDiv.css({position:
($.datepicker._inDialog && $.blockUI ?Ð''7F F–2" ¢ †–4f–†VB ò &f–†VB" ¢
"absolute")), display: "none",Ð–ÆVgC¢ öfg6WBæÆVgB ² ' ,"Â F÷ ¢ öfg6WBçF÷ ²
"px"});Ðif (!inst.inline) {Ð6†÷t æ–Ò Ò BæF FW –6¶W"åövWB†–ç7BÂ '6†÷t æ–Ò"½
duration = $.datepicker._get(inst, "duration");Ð•
inst.dpDiv.zIndex($(input).zIndex()+1);Ð'BæF FW –6¶W"åöF FW –6¶W%6†÷v–ær Ò G'VÐ½
if ($.effects && $.effects.effect[showAnim]) {Ðinst.dpDiv.show(showAnim,
$.datepicker._get(inst, "showOptions"), duration);Ð–Ò VÇ6R½inst.dpDiv[showAnim
|| "show"](showAnim ? duration : null);ÐÐ–b
($.datepicker._shouldFocusInput(inst)) {Ðinst.input.focus();ÐÐ
$.datepicker._curInst = inst;}ÒÒò¢ vVæW& FR F†R F FR –6¶W" 6öçFVçBâ ¢
_updateDatepicker: function(inst) {Ðthis.maxRows = 4; //Reset the max number
of rows being displayed (see #7043)Ð

™instActive = inst; // for delegate hover
eventsÐinst.dpDiv.empty().append(this._generateHTML(inst));™Ð
this._attachHandlers(inst);™Ðinst.dpDiv.find("." + this._dayOverClass + "
a").mouseover();™Ðvar origyearshtml;™ÐçVÔÖöçF‡2 Ò F†—2åövWDçVÖ&W$ödÖöçF‡2†–ç7B™Í
cols = numMonths[1],™Ð—v–GF, Ò ™Ðinst.dpDiv.removeClass("ui-datepicker-multi-2
ui-datepicker-multi-3 ui-datepicker-multi-4").width("");™Ðif (cols > 1) {™Ð
inst.dpDiv.addClass("ui-datepicker-multi-" + cols).css("width", (width *
cols) + "em");™Ð™™™Ðinst.dpDiv[(numMonths[0] !== 1 || numMonths[1] !== 1 ? "add" :
"remove") +™Ð'$6Æ 72%Ò,'V'ÖF FW –6¶W"Ö×VÇF'"™™Ðinst.dpDiv[(this._get(inst,
"isRTL") ? "add" : "remove") +™Ð'$6Æ 72%Ò,'V'ÖF FW –6¶W"×'FÂ"™™Ðif (inst ===
$.datepicker._curInst && $.datepicker._datepickerShowing &&
$.datepicker._shouldFocusInput(inst)) {™Ð––ç7Bæ–ç WBæfö7W2,™™™Ð// deffered
render of the years select (to avoid flashes on Firefox)™Ðif(inst.yearshtml){™Ð
origyearshtml = inst.yearshtml;™Ð—6WEF–ÖV÷WB†gVæ7F–öâ,™™™//assure that
inst.yearshtml didn't change.™Ðif(origyearshtml === inst.yearshtml &&
inst.yearshtml){™Ð™––ç7BæG F—bæf–æB,'6VÆV7BçV'ÖF FW –6¶W"Ð
year:first").replaceWith(inst.yearshtml);™Ð™™™Ðorigyearshtml = inst.yearshtml =
null;™Ð—ÒÂ ™™™ÐÍòò 3cc“B Ò FöâwB fö7W2 F†R –ç WB –b —Bw2 Ç&V G' fö7W6VÍòò F†—2
breaks the change event in IEÍòò 7W ÷'C¢ ”R æB ¥ VW'' Ã ã•÷6†÷VÆDfö7W4–ç WC¢
function(inst) {™Ðreturn inst.input && inst.input.is(":visible") && !
inst.input.is(":disabled") && !inst.input.is(":focus");™ÐÒÍòò¢ 6†V6²
positioning to remain on screen. */™Ðö6†V6´öfg6WC¢ gVæ7F–öâ†–ç7BÂ öfg6WBÂ
isFixed) {™Ðvar dpWidth = inst.dpDiv.outerWidth();™ÐG †V–v‡B Ò
inst.dpDiv.outerHeight();™Ð––ç WEv–GF, Ò –ç7Bæ–ç WB ò –ç7Bæ–ç WBæ÷WFW%v–GF,,' ¢
0,™Ð––ç WD†V–v‡B Ò –ç7Bæ–ç WB ò –ç7Bæ–ç WBæ÷WFW$†V–v‡B,' ¢ ™Íf–Wuv–GF, Ò
document.documentElement.clientWidth + (isFixed ? 0 :
$(document).scrollLeft());™Ð—f–Wt†V–v‡B Ò Fö7VÖVçBæFö7VÖVçDVÆVÖVçBæ6Æ–VçD†V–v‡B
+ (isFixed ? 0 : $(document).scrollTop());™Ðoffset.left -= (this._get(inst,
"isRTL") ? (dpWidth - inputWidth) : 0);™Ðoffset.left -= (isFixed && offset.left
=== inst.input.offset().left) ? $(document).scrollLeft() : 0;™Ðoffset.top -=
(isFixed && offset.top === (inst.input.offset().top + inputHeight)) ?
$(document).scrollTop() : 0;™Ð// now check if datepicker is showing outside
window viewport - move to a better place if so.™Ðoffset.left -=
Math.min(offset.left, (offset.left + dpWidth > viewWidth && viewWidth >
dpWidth) ?™Ð”Ö F,æ '2†öfg6WBæÆVgB ² G v–GF, Ò f–Wuv–GF,' ¢ ™™™Ðffset.top -=
Math.min(offset.top, (offset.top + dpHeight > viewHeight && viewHeight >
dpHeight) ?™Ð”Ö F,æ '2†G †V–v‡B ² –ç WD†V–v‡B' ¢ ™™™Ðeturn offset;™ÐÍòò¢ f–æB â
object's position on the screen. */™Ðöf–æE ÷3¢ gVæ7F–öâ†ö&¢' ™™™Ðvar position;™Ð–ç7B
= this._getInst(obj),™Ð––5%DÂ Ò F†—2åövWB†–ç7BÂ &—5%DÂ"™™™Ðwhile (obj && (obj.type
=== "hidden" || obj.nodeType !== 1 || $.expr.filters.hidden(obj))) {™Ð–ö&¢ Ò
obj[isRTL ? "previousSibling" : "nextSibling"];™™™Ðposition = $(obj).offset();™Ð
return [position.left, position.top];™ÐÒÍòò¢ †–FR F†R F FR –6¶W" g&öÒ f–Wr1 ¢
@param input element - the input field attached to the date picker™Ð ¢™™
_hideDatepicker: function(input) {™Ðvar showAnim, duration, postProcess,
onClose,™Ð––ç7B Ò F†—2åö7W$–ç7™™™Ðif (!inst || (input && inst !== $.data(input,
PROP_NAME))) {™Ð—&WGW&™™™Ðif (this._datepickerShowing) {™Ð6†÷t æ–Ò Ò
this._get(inst, "showAnim");™Ð–GW& F–öâ Ò F†—2åövWB†–ç7BÂ &GW& F–öâ"™™™
postProcess = function() {™Ð™™™$.datepicker._tidyDialog(inst);™Ð™™™ÍÍòò DU $T4 DTC¢
after BC for 1.8.x $.effects[showAnim] is not needed™Ð––b , BæVffV7G2 bb
($.effects.effect[showAnim] || $.effects[showAnim])) {™Ð™™™
inst.dpDiv.hide(showAnim, $.datepicker._get(inst, "showOptions"), duration,
postProcess);™Ð—Ò VÇ6R™™™

™}ÒÐÓò¢ F–G’ W gFW" F– Æör F—7 Æ ’â ¢ý÷F–G”F– Æös¢ gVæ7F–öâ†–ç7B’ ™½
inst.dpDiv.removeClass(this._dialogClass).unbind(".ui-datepicker-calendar");ÐÒÓÐ
’ò¢ 6Æ÷6R F FR –6¶W" –b 6Æ–6¶VB VÇ6Wv†W&Râ ¢ýö6†V6´W‡FW&æ Ä6Æ–6³¢
function(event) {™Ðif (!$.datepicker._curInst) ™Ð&WGW&â™Ðvar $target =
$(event.target),™Ð––ç7B Ò BæF FW –6¶W"åövWD–ç7B,GF &vWE³ ÒÐ™½f
((($target[0].id !== $.datepicker._mainDivId &&™Ð™$target.parents("#" +
$.datepicker._mainDivId).length === 0 &&™Ð™!
$target.hasClass($.datepicker.markerClassName) &&™Ð™!$target.closest("." +
$.datepicker._triggerClass).length &&™Ð™$.datepicker._datepickerShowing && !
($.datepicker._inDialog && $.blockUI))) ||™Ð•
($target.hasClass($.datepicker.markerClassName) && $.datepicker._curInst !==
inst)) {™Ð™$.datepicker._hideDatepicker();™}ÒÐÓò¢ F§W7B öæR öb F†R F FR 7V"Ð
fields. */Ðö F§W7DF FS¢ gVæ7F–öâ†–BÂ öfg6WBÂ W&–öB’ ™½var target = $(id),™Ð–ç7B
= this._getInst(target[0]);™Ðif (this._isDisabledDatepicker(target[0])) ™Ð&WGW&ã½
™™Ðthis._adjustInstDate(inst, offset ™Ð‡ W&–öB ÓÓÒ $Ò" ò F†—2åövWB†–ç7BÂ
"showCurrentAtPos") : 0), // undo positioning™Ð— W&–öB™½
this._updateDatepicker(inst);ÐÒÓÐÒò¢ 7F–öâ f÷" 7W'&VçB Æ–æ²â ¢ýöv÷FõFöF “¢
function(id) {™Ðvar date,™ÐF &vWB Ò B†–B™Í–ç7B Ò F†—2åövWD–ç7B‡F &vWE³ ÒÐ™½f
(this._get(inst, "gotoCurrent") && inst.currentDay) {™Ð––ç7Bç6VÆV7FVDF ’ Ò
inst.currentDay;™Ð––ç7BæG& tÖöçF, Ò –ç7Bç6VÆV7FVDÖöçF, Ò –ç7Bæ7W'&VçDÖöçF™½
inst.drawYear = inst.selectedYear = inst.currentYear;™Ð} else {™ÐF FR Ò æWr
Date();™Ð––ç7Bç6VÆV7FVDF ’ Ò F FRæVWDF FR,™½–ç7BæG& tÖöçF, Ò –ç7Bç6VÆV7FVDÖöçF,
= date.getMonth();™Ð––ç7BæG& u–V " Ò –ç7Bç6VÆV7FVE–V " Ò F FRæVWDgVÆÂ–V ",™½Ð
this._notifyChange(inst);™Ðthis._adjustDate(target);ÐÒÓÐÒò¢ 7F–öâ f÷" 6VÆV7F–ær
new month/year. */Ð÷6VÆV7DÖöçF…–V #¢ gVæ7F–öâ†–BÂ 6VÆV7BÂ W&–öB’ ™½var target
= $(id),™Ð––ç7B Ò F†—2åövWD–ç7B‡F &vWE³ ÒÐ™½nst["selected" + (period === "M" ?
"Month" : "Year")] =™Ðinst["draw" + (period === "M" ? "Month" : "Year")] =™Ð
parseInt(select.options[select.selectedIndex].value,10);™Ð
this._notifyChange(inst);™Ðthis._adjustDate(target);ÐÒÓÐÒò¢ 7F–öâ f÷" 6VÆV7F–ær
day. */Ð÷6VÆV7DF “¢ gVæ7F–öâ†–BÂ ÖöçF,Â –V "Â FB’ ™½var inst,™ÐF &vWB Ò B†–BÐ™½f
($(td).hasClass(this._unselectableClass) ||
this._isDisabledDatepicker(target[0])) {™Ð—&WGW&â™Ðinst =
this._getInst(target[0]);™Ðinst.selectedDay = inst.currentDay = $("a",
td).html();™Ðinst.selectedMonth = inst.currentMonth = month,™Ðinst.selectedYear =
inst.currentYear = year;™Ðthis._selectDate(id, this._formatDate(inst,™Ð
inst.currentDay, inst.currentMonth, inst.currentYear));ÐÒÓÐÒò¢ W& 6R F†R –ç WB
field and hide the date picker. */Ðö6ÆV $F FS¢ gVæ7F–öâ†–B’ ™½var target =
$(id);™Ðthis._selectDate(target, "");ÐÒÓÐÒò¢ W F FR F†R –ç WB f–VÆB v—F, F†R
selected date. */Ð÷6VÆV7DF FS¢ gVæ7F–öâ†–BÂ F FU7G"’ ™½var onSelect,™ÐF &vWB Ò
$(id),™Ð––ç7B Ò F†—2åövWD–ç7B‡F &vWE³ ÒÐ™½dateStr = (dateStr != null ? dateStr :
this._formatDate(inst));™Ðif (inst.input) {™Ð–ç7Bæ–ç WBçf Â†F FU7G"™½Ð
this._updateAlternate(inst);™ÐonSelect = this._get(inst, "onSelect");™Ðif
(onSelect) {™Ð–öå6ÆV7Bæ Ç’,†–ç7Bæ–ç WB ò –ç7Bæ–ç WE³ Ò ¢ çVÆÂ’Â ¶F FU7G"Â
inst]); // trigger custom callback™Ð} else if (inst.input) {™Ð
inst.input.trigger("change"); // fire the change event™Ð™Ðif (inst.inline){™Ð
this._updateDatepicker(inst);™Ð} else {™ÐF†—2åö†–FTF FW –6¶W",™½F†—2åöÆ 7D–ç WB Ò
inst.input[0];™Ð––b ‡G— Vöb†–ç7Bæ–ç WE³ Ò’ ÓÒ &ö&¦V7B"’™™½inst.input.focus(); //
restore focus™Ð™™ÝF†—2åöÆ 7D–ç WB Ò çVÆÂ™½ÐÒÓÐÒò¢ W F FR ç’ ÇFW&æ FR f–VÆB Fò
synchronise with the main field. */Ð÷W F FT ÇFW&æ FS¢ gVæ7F–öâ†–ç7B’ ™½var
altFormat, date, dateStr,™Ð– ÇDf–VÆB Ò F†—2åövWB†–ç7BÂ & ÇDf–VÆB"™½f (altField)
{ // update alternate field too™Ð– ÇDf÷&Ö B Ò F†—2åövWB†–ç7BÂ & ÇDf÷&Ö B"’ ÇÂ
this._get(inst, "dateFormat");™Ð–F FR Ò F†—2åövWDF FR†–ç7B™½F FU7G" Ò
this.formatDate(altFormat, date, this._getFormatConfig(inst));™Ð•
$(altField).each(function() { $(this).val(dateStr); });™Ð}ÒÐÓò¢ 6WB 2
beforeShowDay function to prevent selection of weekends.™Ð ¢ & Ò F FR F FR
- the date to customise™Ð ¢ &WGW&â ¶&ööÆV âÂ 7G&–æuÒ Ò —2 F†—2 F FR
selectable?, what is its CSS class?™Ð ¢ýæõvVV¶VæG3¢ gVæ7F–öâ†F FR’ ™½var day =
date.getDay();™Ðreturn [(day > 0 && day < 6), ""];ÐÒÓÐÒò¢ 6WB 2 6 Æ7VÆ FUvVV² Fò
determine the week of the year based on the ISO 8601 definition.™Ð ¢ & Ò
date Date - the date to get the week for™Ð

’ ¢ &WGW&â çVÖ&W" Ò F†R çVÖ&W" öb
the week within the year that contains this date. ¢ý–6óƒc vVV³¢
function(date) {var time = date.getTime();var checkDate = new Date(date.getFullYear(), 0, 1);// Find Thursday of this week starting on Monday checkDate.setDate(checkDate.getDate() + 4 - (checkDate.getDay() || 7));time = checkDate.getTime();checkDate.setMonth(0); // Compare with Jan 1 checkDate.setDate(1);return Math.floor(Math.round((time - checkDate) / 86400000) / 7) + 1;}¢ '6R string value into a date object. ¢ 6VR f÷&Ö DF FR &VÆ÷r f÷" F†R ÷76–&ÆR formats. ’ ¢ & Ò f÷&Ö B 7G&–ær Ò F†R W‡ V7FVB f÷&Ö B öb F†R F F] ¢
@param value string - the date in the above format ¢ & Ò 6WGF–æw2 ö&¦V7B - attributes include: ©™shortYearCutoff number - the cutoff year for determining the century (optional) ©™dayNamesShort–7G&–æu³uÒ Ò &'&Wf– FVB names of the days from Sunday (optional) ©™dayNames™string[7] - names of the days from Sunday (optional) ©™monthNamesShort string[12] - abbreviated names of the months (optional) ©™monthNames™string[12] - names of the months (optional) ¢ &WGW&â F FR Ò F†R W‡G& 7FVB F FR f ÇVR ÷" çVÆÂ –b f ÇVR —2 blank ¢ý '6TF FS¢ gVæ7F–öâ †f÷&Ö BÂ f ÇVRÂ 6WGF–æw2’ ½if (format == null || value == null) {—F‡&÷r $–çf Æ–B &wVÖVçG2#½value = (typeof value === "object" ? value.toString() : value + "");if (value === "") {&WGW&â çVÆÂ½var iFormat, dim, extra,–•f ÇVR Ò ™Í6†÷'E–V $7WFöfeFV× Ò ‡6WGF–æw2 ò settings.shortYearCutoff : null) || this._defaults.shortYearCutoff,• shortYearCutoff = (typeof shortYearCutoffTemp !== "string" ? shortYearCutoffTemp :™new Date().getFullYear() % 100 + parseInt(shortYearCutoffTemp, 10)),–F ”æ ÖW56†÷'B Ò ‡6WGF–æw2 ò settings.dayNamesShort : null) || this._defaults.dayNamesShort,–F ”æ ÖW2 Ò (settings ? settings.dayNames : null) || this._defaults.dayNames,• monthNamesShort = (settings ? settings.monthNamesShort : null) || this._defaults.monthNamesShort,–ÖöçF„æ ÖW2 Ò ‡6WGF–æw2 ò 6WGF–æw2æÖöçF„æ ÖW2 ¢ null) || this._defaults.monthNames,––V " Ò ™ÍÖöçF, Ò ™ÍF ’ Ò ™ÍF÷’ Ò ™Í literal = false,–F FRÍòò 6†V6² v†WF†W" f÷&Ö B 6† & 7FW" —2 F÷V&ÆVMÆöö´ †V B = function(match) {™var matches = (iFormat + 1 < format.length && format.charAt(iFormat + 1) === match);™if (matches) {”f÷&Ö B™½return matches;™—ÍÒòò W‡G& 7B çVÖ&W" g&öÒ F†R 7G&–ær f ÇV]vWDçVÖ&W" Ò gVæ7F–öâ†Ö F6,’™½var isDoubled = lookAhead(match),™—6—¦R Ò †Ö F6, ÓÓÒ $ " ò B ¢ †Ö F6, ÓÓÒ " " ò 20 :™’†Ö F6, ÓÓÒ ''" bb —4F÷V&ÆVB ò B ¢ †Ö F6, ÓÓÒ &ò" ò 2 ¢ "’’™ÍF–v—G2 Ò æWr RegExp("^\\d{1," + size + "}"),™–çVÒ Ò f ÇVRç7V'7G&–ær†•f ÇVR’æÖ F6,†F–v—G2 ½f (!num) {™—F‡&÷r $Ö—76–ær çVÖ&W" B ÷6—F–öâ " ² •f ÇVS½Value += num[0].length;™return parseInt(num[0], 10);™—ÍÒòò W‡G& 7B æ ÖR g&öÒ F†R 7G&–ær f ÇVR æB convert to an index™–vWDæ ÖR Ò gVæ7F–öâ†Ö F6,Â 6†÷'Dæ ÖW2Â Æöætæ ÖW2’½var index = -1,™–æ ÖW2 Ò BæÖ †Æöö´ †V B†Ö F6,’ ò Æöætæ ÖW2 ¢ 6†÷'Dæ ÖW2Â gVæ7F–öâ (v, k) {™return [[k, v]];™’ç6÷'B†gVæ7F–öâ † Â "™½return -(a[1].length - b[1].length);™—Ö $.each(names, function (i, pair) {™f " æ ÖR Ò —%³™Ö½–b (value.substr(iValue, name.length).toLowerCase() === name.toLowerCase()) {™index = pair[0];™iValue += name.length;™return false;™});™if (index !== -1) {™return index + 1;™} else {™F‡&÷r %Væ¶æ÷vâ æ ÖR B ÷6—F–öâ " ² •f ÇVS½™ÍÒòò Confirm that a literal character matches the string value.™–6†V6´Æ—FW& Â Ò function() {™if (value.charAt(iValue) !== format.charAt(iFormat)) {™F‡&÷r "Unexpected literal at position " + iValue;™}™iValue++;™½for (iFormat = 0; iFormat < format.length; iFormat++) {™––b †Æ—FW& Â’™½if (format.charAt(iFormat) === "'" && !lookAhead("'")) {™–Æ—FW& Â Ò f Ç6S½ else {™6†V6´Æ—FW& Â,™½™ VÇ6R™½ switch (format.charAt(iFormat)) {™–6 6R &B#-day = getNumber("d");™break;™ 6R $B#-getName("D", dayNamesShort, dayNames);™break;™ 6R &Ö#-doy = getNumber("o");™break;™–6 6R &Ö#-month = getNumber("m");™break;™ 6R $Ö#-month = getName("M", monthNamesShort, monthNames);™break;™ 6R '™#-year = getNumber("y");™break;™ 6R "@":™date = new Date(getNumber("@"));™year = date.getFullYear();™month = date.getMonth() + 1;™day = date.getDate();™break;™ 6R "™#-date = new Date((getNumber("!") - this._ticksTo1970) / 10000);™year = date.getFullYear();™month = date.getMonth() + 1;™day = date.getDate();™break;™ 6R "™#-if (lookAhead("'")){™–6†V6´Æ—FW& Â,™½ else {™Æ—FW& Â Ò G™VS½™break;™Vf VÇC-checkLiteral();™

™™™

™–6† '2 Ò "™ÍÆ–FW& Â Ò f Ç6RÍòò 6†V6² v†WF†W" f÷&Ö B 6† & 7FW" –2
doubledÐ–Æöö´ †V B Ò gVæ7F–öâ†Ö F6,'™½var matches = (iFormat + 1 <
format.length && format.charAt(iFormat + 1) === match);Ð™if (matches)™{Ð"f÷&Ö B°
+;Ð™}Ðeturn matches;Ð½for (iFormat = 0; iFormat < format.length; iFormat++) ™{Ð–b
(literal) {Ð™if (format.charAt(iFormat) === "'" && !lookAhead("'"))™{ÐÆ–FW& Â Ò
false;Ð™} else™{Ð6† '2 ³Ò f÷&Ö Bæ6† $ B†"f÷&Ö B™½Ò VÇ6R™½switch
(format.charAt(iFormat)) {Ð™–6 6R &B#¢ 6 6R &Ò#¢ 6 6R '′#¢ 6 6R $™#-chars +=
"0123456789";Ð™™break;Ð 6R $B#¢ 6 6R $Ò#-return null; // Accept anything™Ð 6R "™#-
if (lookAhead("'")) {Ð™™–6† '2 ³Ò ™′#½ else™{ÐÆ–FW& Â Ò G™VS½Ðreak;ÐVf VÇC-chars
+= format.charAt(iFormat);Ð™™}Ðeturn chars;ÐÍòò¢ vWB 6WGF–ær f ÇVRÂ
defaulting if necessary. */ÐövWC¢ gVæ7F–öâ†–ç7BÂ æ ÖR' ™½return
inst.settings[name] !== undefined ?Ð–-ç7Bç6WGF–æw5¶æ ÖUÒ ¢ F†–2åöFVf VÇG5¶æ ÖUÓ½
–ÒÍòò¢ '6R W†–7F–ær F FR æB –æ–F– Æ–6R F FR –6¶W"â ¢ý÷6WDF FTg&öÔf–VÆC¢
function(inst, noDefault) {Ðif (inst.input.val() === inst.lastVal) ™{Ð&WGW&ãÐ
var dateFormat = this._get(inst, "dateFormat");Ð–F FW2 Ò –ç7BæÆ 7Ef Â Ò
inst.input ? inst.input.val() : null;Ð–FVf VÇDF FR Ò F†–2åövWDFVf VÇDF FR†–ç7B™Í
date = defaultDate;Ð–6WGF–æw2 Ò F†–2åövWDf÷&Ö D6öæf–r†–ç7BÐ½ry ™ÐF FR Ò
this.parseDate(dateFormat, dates, settings) || defaultDate;Ð™} catch (event) ™Ð
dates = (noDefault ? "" : dates);Ð™}Ðinst.selectedDay = date.getDate();Ð
inst.drawMonth = inst.selectedMonth = date.getMonth();Ðinst.drawYear =
inst.selectedYear = date.getFullYear();Ðinst.currentDay = (dates ?
date.getDate() : 0);Ðinst.currentMonth = (dates ? date.getMonth() : 0);Ð
inst.currentYear = (dates ? date.getFullYear() : 0);Ð
this._adjustInstDate(inst);ÐÒÍòò¢ &WG&–WfR F†R FVf VÇB F FR 6†÷vâ öâ ÷ Væ–ærâ ¢ý
_getDefaultDate: function(inst) {Ðreturn this._restrictMinMax(inst,Ð
this._determineDate(inst, this._get(inst, "defaultDate"), new Date()));ÐÒÍòò¢
date may be specified as an exact value or a relative one. */ÐöVFWFW&Ö–æTF FS¢
function(inst, date, defaultDate) {Ðvar offsetNumeric = function(offset) {Ðvar
date = new Date();Ð™date.setDate(date.getDate() + offset);Ðeturn date;ÐÍ
offsetString = function(offset) {Ð™try™{Ð&WGW&â
$.datepicker.parseDate($.datepicker._get(inst, "dateFormat"),Ð™™offset,
$.datepicker._getFormatConfig(inst));Ð™}Ðatch (e)™{Ðòò –æ÷&™}Ðar date =
(offset.toLowerCase().match(/^c/) ?Ð™'BæF FW –6¶W"åövWDF FR†–ç7B' ¢ çVÆÂ' ÇÂ æWr
Date(),Ð™––V " Ò F FRævWDgVÆÅ–V ",™ÍÖöçF, Ò F FRævWDÖöçF,™™ÍF ' Ò F FRævWDF FR,™™Í
pattern = /([+\-]?[0-9]+)\s*(d|D|w|W|m|M|y|Y)?/g,Ð™–Ö F6†W2 Ò
pattern.exec(offset);Ð™while (matches)™{Ð7v–F6, †Ö F6†W5³%Ò ÇÂ &B"™™½case "d" :
case "D" :Ð™–F ' ³Ò '6T–çB†Ö F6†W5³ ÒÃ "² '&V™½case "w" : case "W™™:ÐF ' ³Ò
parseInt(matches[1],10) * 7; break;Ð™case "m" : case "M™™:ÐÖöçF, ³Ò
parseInt(matches[1],10);Ð™–F ' Ò Ö F,æÖ–â†F 'Â
$.datepicker._getDaysInMonth(year, month));Ð™–'&V™½case "y": case "Y™™:Ð–V " ³Ò
parseInt(matches[1],10);Ð™–F ' Ò Ö F,æÖ–â†F 'Â
$.datepicker._getDaysInMonth(year, month));Ð™–'&V™½Ö F6†W2 Ò
pattern.exec(offset);Ð™}Ðeturn new Date(year, month, day);ÐÍæWtF FR Ò †F FR ÓÒ
null || date === "" ? defaultDate : (typeof date === "string" ?
offsetString(date) :Ð™(typeof date === "number" ? (isNaN(date) ? defaultDate :
offsetNumeric(date)) : new Date(date.getTime()))));ÐnewDate = (newDate &&
newDate.toString() === "Invalid Date" ? defaultDate : newDate);Ðif (newDate) ™{Ð
newDate.setHours(0);Ð–æWtF FRç6WDÖ–çWFW2ƒ ™½æWtF FRç6WE6V6öæG2ƒ ™½
newDate.setMilliseconds(0);Ð™}Ðeturn this._daylightSavingAdjust(newDate);ÐÍòò¢
Handle switch to/from daylight saving.Ð ¢ †÷W'2 Ö ' &R æöâ×¦W&ò öâ F –Æ–v‡B
saving cut-over:Ð ¢ â " v†Vâ Ö–Fæ–v‡B 6† ævV÷fW"Â 'WB F†Vâ 6 ææ÷B vVæW& F] ¢
midnight datetime, so jump to 1AM, otherwise reset.Ð ¢ & Ò F FR „F FR'
the date to checkÐ ¢ &WGW&â „F FR' F†R 6÷'&V7FVB F F] ¢ý
_daylightSavingAdjust: function(date) {Ðif (!date) ™{Ð&WGW&â çVÆÃ½Ð
date.setHours(date.getHours() > 12 ? date.getHours() + 2 : 0);Ðreturn date;ÐÍò
* Set the date(s) directly. */Ð÷6WDF FS¢ gVæ7F–öâ†–ç7BÂ F FRÂ æô6† ævR' ™½var
clear = !date,Ð–÷&–tÖöçF, Ò –ç7Bç6VÆV7FVDÖöçF,™Í÷&–u–V " Ò –ç7Bç6VÆV7FVE–V ™™Í
newDate = this._restrictMinMax(inst, this._determineDate(inst, date, new
Date()));Ðinst.selectedDay = inst.currentDay = newDate.getDate();Ð
inst.drawMonth = inst.selectedMonth = inst.currentMonth = newDate.getMonth();Ð

™
inst.drawYear = inst.selectedYear = inst.currentYear = newDate.getFullYear();™Ð
if ((origMonth !== inst.selectedMonth || origYear !== inst.selectedYear) && !
noChange) {™Ð–F†–2åöæ÷F–g”6† ævR†–ç7B™½™Ðthis._adjustInstDate(inst);™Ðf
(inst.input) {™Ð––ç7Bæ–ç WBçf Â†6ÆV " ò "" ¢ F†–2åöf÷&Ö DF FR†–ç7B’™½™ÐÒò¢
Retrieve the date(s) directly. */ÐövWDF FS¢ gVæ7F–öâ†–ç7B’ ™½var startDate = (!
inst.currentYear || (inst.input && inst.input.val() === "") ? null :™Ð•
this._daylightSavingAdjust(new Date(™Ð––ç7Bæ7W'&VçE–V "Â –ç7Bæ7W'&VçDÖöçF,Â
inst.currentDay)));™Ð–&WGW&â 7F 'DF FS™Ð™Ðò¢ GF 6, F†R öç‡‡, † æFÆW'2â F†W6R
are declared statically so™Ð ¢ F†W’ v÷&² v–F, 7F F–2 6öFR G& ç6f÷&ÖW'2 Æ–¶R
Caja.™Ð ¢ýö GF 6„† æFÆW'3¢ gVæ7F–öâ†–ç7B’ ™½var stepMonths = this._get(inst,
"stepMonths"),™Ð––B Ò "2" ² –ç7Bæ–Bç&W Æ 6R, õÅÅÅÂörÂ %ÅÂ" ™½
inst.dpDiv.find("[data-handler]").map(function () {™Ð–f " † æFÆW" Ò™½prev:
function () {™Ð™’BæF FW –6¶W"åö F§W7DF FR†–BÂ ×7FW ÖöçF‡2Â $Ò™™½™½™Ðnext: function
() {™Ð™’BæF FW –6¶W"åö F§W7DF FR†–BÂ ·7FW ÖöçF‡2Â $Ò™™½™½™Ðhide: function ()™™Ð
$.datepicker._hideDatepicker();™Ð™™Ð},™Ðtoday: function () ™™Ð
$.datepicker._gotoToday(id);™Ð™™Ð},™ÐselectDay: function () ™™Ð
$.datepicker._selectDay(id, +this.getAttribute("data-month"),
+this.getAttribute("data-year"), this);™Ð™–&WGW&â f ÇÖS™½™½™Ðselect Month: function
() {™Ð™’BæF FW –6¶W"å÷6VÆV7DÖöçF…–V "†–BÂ F†–2Â $Ò™™½™½&WGW&â f ÇÖS™½™½™ÐselectYear:
function () {™Ð™’BæF FW –6¶W"å÷6VÆV7DÖöçF…–V "†–BÂ F†–2Â %’™™½™½&WGW&â f ÇÖS™½™½™Ð½
$(this).bind(this.getAttribute("data-event"), handler[this.getAttribute("data-
handler")]);™Ð});™ÐÒò¢ vVæW& FR F†R …DÔÂ f÷" F†R 7W'&VçB 7F FR öb F†R F FR
picker. */ÐövVæW& FT…DÔÃ¢ gVæ7F–öâ†–ç7B’ ™½var maxDraw, prevText, prev,
nextText, next, currentText, gotoDate,™Ð–6öçG&öÇ2Â 'WGFöå æVÂÂ f–'7DF ’Â
showWeek, dayNames, dayNamesMin,™Ð–ÖöçF„æ ÖW2Â ÖöçF„æ ÖW56†÷'BÂ &Vf÷&U6†÷tF ’Â
showOtherMonths,™Ð–6VÆV7D÷F†W$ÖöçF‡2Â FVf VÇDF FRÂ ‡FÖÂÂ F÷rÂ &÷rÂ w&÷W Â 6öÂÂ
selectedDate,™Ð–6÷&æW$6Æ 72Â 6 ÆVæFW"Â F†V BÂ F ’Â F –4–äÖöçF,Â ÆV DF –2Â
curRows, numRows,™Ð– &–çDF FRÂ E&÷rÂ F&öG’Â F •6WGF–æw2Â ÷F†W$ÖöçF,Â
unselectable,™Ð–FV× F FR Ò æWr F FR,™ÍFöF ’ Ò F†–2åöF –Æ–v‡E6 f–æt F§W7B™™new
Date(tempDate.getFullYear(), tempDate.getMonth(), tempDate.getDate())), //
clear time™Ð––5%DÂ Ò F†–2åövWB†–ç7BÂ &–5%DÂ"™Í6†÷t'WGFöå æVÂ Ò F†–2åövWB†–ç7BÂ
"showButtonPanel"),™Ð–†–FT–dæõ &WdæW‡B Ò F†–2åövWB†–ç7BÂ &†–FT–dæõ &WdæW‡B"™Í
navigationAsDateFormat = this._get(inst, "navigationAsDateFormat"),™Ð–çVÔÖöçF‡2
= this._getNumberOfMonths(inst),™Ð–6†÷t7W'&VçD E ÷2 Ò F†–2åövWB†–ç7BÂ
"showCurrentAtPos"),™Ð–7FW ÖöçF‡2 Ò F†–2åövWB†–ç7BÂ '7FW ÖöçF‡2"™Í–4×VÇF”ÖöçF, Ò
(numMonths[0] !== 1 || numMonths[1] !== 1),™Ð–7W'&VçDF FR Ò
this._daylightSavingAdjust((!inst.currentDay ? new Date(9999, 9, 9) :™Ð™new
Date(inst.currentYear, inst.currentMonth, inst.currentDay))),™Ð–Ö–äF FR Ò
this._getMinMaxDate(inst, "min"),™Ð–Ö „F FR Ò F†–2åövWDÖ–äÖ „F FR†–ç7BÂ &Ö ,"™Í
drawMonth = inst.drawMonth - showCurrentAtPos,™Ð–G& u–V " Ò –ç7BæG& u–V ™½™½f
(drawMonth < 0) {™Ð–G& tÖöçF, ³Ò ™½G& u–V "ÒÒ™½™½™Ðf (maxDate) ™ÐÖ „G& r Ò
this._daylightSavingAdjust(new Date(maxDate.getFullYear(),™Ð™maxDate.getMonth()
- (numMonths[0] * numMonths[1]) + 1, maxDate.getDate()));™Ð–Ö „G& r Ò †Ö–äF FR
&& maxDraw < minDate ? minDate : maxDraw);™Ð–v†–ÆR
(this._daylightSavingAdjust(new Date(drawYear, drawMonth, 1)) > maxDraw) {™Ð™
drawMonth--;™Ð™if (drawMonth < 0)™™½™½{™ÐG& tÖöçF, Ò ™™½G& u–V "ÒÒ™½™½™Ðinst.drawMonth =
drawMonth;™Ðinst.drawYear = drawYear;™Ðprev Text = this._get(inst, "prevText");™Ð
prevText = (!navigationAsDateFormat ? prevText : this.formatDate(prevText,™Ð•
this._daylightSavingAdjust(new Date(drawYear, drawMonth - stepMonths, 1)),™Ð•
this._getFormatConfig(inst)));™Ðprev = (this._canAdjustMonth(inst, -1,
drawYear, drawMonth) ?™Ð’#Æ 6Æ 73ÒwV’ÖF FW –6¶W"× &Wb V’Ö6÷&æW"Ö ÆÂr F F Ð
handler='prev' data-event='click'" +™Ð’" F–FÆSÒr" ² &WeFW‡B ² "sãÇ7 â
class='ui-icon ui-icon-circle-triangle-" + (isRTL ? "e" : "w") + "'>" +
prevText + "</a>" :™Ð’††–FT–dæõ &WdæW‡B ò "" ¢ #Æ 6Æ 73ÒwV’ÖF FW –6¶W"Ð
prev ui-corner-all ui-state-disabled' title='"+ prevText +"'><span class='ui-
icon ui-icon-circle-triangle-" + (isRTL ? "e" : "w") + "'>" + prevText + "</
span></a>"));™Ðnext Text = this._get(inst, "nextText");™ÐnextText = (!
navigationAsDateFormat ? nextText : this.formatDate(nextText,™Ð•
this._daylightSavingAdjust(new Date(drawYear, drawMonth + stepMonths, 1)),Ð

™•
this._getFormatConfig(inst)));Ðnext = (this._canAdjustMonth(inst, +1,
drawYear, drawMonth) ?Ð'#Æ 6Æ 73ÒwV'ÖF FW –6¶W"ÖæW‡B V'Ö6÷&æW"Ö ÆÂr F F Ð
handler='next' data-event='click'" +Ð'" F–FÆSÒr" ² æW‡EFW‡B ² "sãÇ7 â
class='ui-icon ui-icon-circle-triangle-" + (isRTL ? "w" : "e") + "'>" +
nextText + "</a>" :Ð'††–FT–dæõ &WdæW‡B ò "" ¢ #Æ 6Æ 73ÒwV'ÖF FW –6¶W"Ð
next ui-corner-all ui-state-disabled' title='"+ nextText + "'><span class='ui-
icon ui-icon-circle-triangle-" + (isRTL ? "w" : "e") + "'>" + nextText + "</
span></a>"));ÐcurrentText = this._get(inst, "currentText");ÐgotoDate =
(this._get(inst, "gotoCurrent") && inst.currentDay ? currentDate : today);Ð
currentText = (!navigationAsDateFormat ? currentText :Ð•
this.formatDate(currentText, gotoDate, this._getFormatConfig(inst)));Ðcontrols
= (!inst.inline ? "<button type='button' class='ui-datepicker-close ui-state-
default ui-priority-primary ui-corner-all' data-handler='hide' data-
event='click'>" +Ð–F†–2åövWB†–ç7BÂ &6Æ÷6UFW‡B"' ² #Âö'WGFöãâ" ¢ ""Ð½uttonPanel
= (showButtonPanel) ? "<div class='ui-datepicker-buttonpane ui-widget-
content'>" + (isRTL ? controls : "") +Ð'‡F†–2åö–4–å& ævR†–ç7BÂ v÷FôF FR' ò
"<button type='button' class='ui-datepicker-current ui-state-default ui-
priority-secondary ui-corner-all' data-handler='today' data-event='click'" +Ð
™'#â" ² 7W'&VçEFW‡B ² #Âö'WGFöãâ" ¢ ""' ² †–5%DÂ ò "" ¢ 6öçG&öÇ2' ² #ÂöF–câ" ¢
";ÐfirstDay = parseInt(this._get(inst, "firstDay"),10);ÐfirstDay =
(isNaN(firstDay) ? 0 : firstDay);ÐshowWeek = this._get(inst, "showWeek");Ð
dayNames = this._get(inst, "dayNames");ÐdayNamesMin = this._get(inst,
"dayNamesMin");ÐmonthNames = this._get(inst, "monthNames");ÐmonthNamesShort =
this._get(inst, "monthNamesShort");ÐbeforeShowDay = this._get(inst,
"beforeShowDay");ÐshowOtherMonths = this._get(inst, "showOtherMonths");Ð
selectOtherMonths = this._get(inst, "selectOtherMonths");ÐdefaultDate =
this._getDefaultDate(inst);Ðhtml = "";ÐdowÐfor (row = 0; row < numMonths[0];
row++) {Ð–w&÷W Ò "#½F†–2æÖ …&÷w2 Ò C½f÷" †6öÂ Ò ² 6öÂ Â çVÔÖöçF‡5³ Ó² 6öÂ²²'™½
selectedDate = this._daylightSavingAdjust(new Date(drawYear, drawMonth,
inst.selectedDay));Ð™cornerClass = " ui-corner-all";Ðalender = "";Ðif
(isMultiMonth) {Ð™–6 ÆVæFW" ³Ò #ÆF–b 6Æ 73ÒwV'ÖF FW –6¶W"Öw&÷W #½–b
(numMonths[1] > 1) {Ð™™switch (col) {Ð6 6R ¢ 6 ÆVæFW" ³Ò " V'ÖF FW –6¶W"Öw&÷W Ð
first";Ð™™cornerClass = " ui-corner-" + (isRTL ? "right" : "left"); break;Ð 6R
numMonths[1]-1: calender += " ui-datepicker-group-last";Ð™™cornerClass = " ui-
corner-" + (isRTL ? "left" : "right"); break;Ð™–FVf VÇC¢ 6 ÆVæFW" ³Ò " V'Ð
datepicker-group-middle"; cornerClass = ""; break;Ð™ }Ð6 ÆVæFW" ³Ò "sã#½Ð
calender += "<div class='ui-datepicker-header ui-widget-header ui-helper-
clearfix" + cornerClass + "'>" +Ð™',ö ÆÇÆÆVgBòçFW7B†6÷&æW$6Æ 72' bb &÷r ÓÓÒ ò
(isRTL ? next : prev) : "") +Ð™',ö ÆÇÇ&–v‡BòçFW7B†6÷&æW$6Æ 72' bb &÷r ÓÓÒ ò
(isRTL ? prev : next) : "") +Ð™–F†–2åövVæW& FTÖöçF…–V $†V FW"†–ç7BÂ G& tÖöçF,Â
drawYear, minDate, maxDate,Ð™–&÷r â ÇÂ 6öÂ â Â ÖöçF„æ ÖW2Â ÖöçF„æ ÖW56†÷'B'
+ // draw month headersÐ™'#ÂöF–cãçF &ÆR 6Æ 73ÒwV'ÖF FW –6¶W"Ö6 ÆVæF "sãÇF†V Câ" ½
™'#ÇG#a#½head = (showWeek ? "<th class='ui-datepicker-week-col'>" +
this._get(inst, "weekHeader") + "</th>" : "");Ð™for (dow = 0; dow < 7; dow++)
{ // days of the weekÐ™–F ' Ò †F÷r ² f–'7DF '' R™½F†V B ³Ò #ÇF," ² ,†F÷r ²
firstDay + 6) % 7 >= 5 ? " class='ui-datepicker-week-end'" : "") + ">" +Ð
™™™"" + dayNamesMin[day] + "</th> }Ð
calender += thead + "</tr></thead><tbody>";Ð™daysInMonth =
this._getDaysInMonth(drawYear, drawMonth);Ð™if (drawYear === inst.selectedYear
&& drawMonth === inst.selectedMonth) {Ð™––ç7Bç6VÆV7FVDF ' Ò
Math.min(inst.selectedDay, daysInMonth);Ð™ }ÐleadDays =
(this._getFirstDayOfMonth(drawYear, drawMonth) - firstDay + 7) % 7;Ð™curRows =
Math.ceil((leadDays + daysInMonth) / 7); // calculate the number of rows to
generateÐ™numRows = (isMultiMonth ? this.maxRows > curRows ? this.maxRows :
curRows : curRows); //If multiple months, use the higher number of rows (see
#7043)Ð™this.maxRows = numRows;ÐprintDate = this._daylightSavingAdjust(new
Date(drawYear, drawMonth, 1 - leadDays));Ð™for (dRow = 0; dRow < numRows; dRow+
+) { // create date picker rowsÐ™–6 ÆVæFW" ³Ò #ÇG#a#½F&öG' Ò , 6†÷uvVV² ò "" ¢
"<td class='ui-datepicker-week-col'>" +Ð

™™™this._get(inst, "calculateWeek")
(printDate) + "</td>");Ð™–f÷" †F÷r Ò ² F÷r Â s² F÷r²²’ ² òò 7&V FR F FR –6¶W"
daysÐ™™™daySettings = (beforeShowDay™™™?Ð&Vf÷&U6†÷tF ’æ Ç’,†–ç7Bæ–ç WB ò
inst.input[0] : null), [printDate]) : [true, ""]);Ð™™™otherMonth =
(printDate.getMonth() !== drawMonth);Ð™™™unselectable = (otherMonth && !
selectOtherMonths) || !daySettings[0] ||Ð™™™’†Ö–äF FR bb &–çDF FR Â Ö–äF FR’ ÇÂ
(maxDate && printDate > maxDate);Ð™™™tbody += "<td class='™™™Ð,†F÷r ² f–'7DF ’ ²
6) % 7 >= 5 ? " ui-datepicker-week-end" : "") + // highlight weekendsÐ™™™•
(otherMonth ? " ui-datepicker-other-month" : "") + // highlight days from
other monthsÐ™™™’,‡ &–çDF FRævWEF–ÖR,’ ÓÓÒ 6VÆV7FVDF FRævWEF–ÖR,’ bb G& tÖöçF, ÓÓÒ
inst.selectedMonth && inst._keyEvent) || // user pressed keyÐ™™™•
(defaultDate.getTime() === printDate.getTime() && defaultDate.getTime() ===
selectedDate.getTime()) ?Ð™™™’òò ÷" FVf VÇDF FR –2 7W'&VçB &–çFVDF FR æB
defaultDate is selectedDateÐ™™™’" " ² F†–2åöF ”÷fW$6Æ 72 ¢ ""’ ² òò †–v†Æ–v‡B
selected dayÐ™™™’‡Vç6VÆV7F &ÆR ò " " ² F†–2å÷Vç6VÆV7F &ÆT6Æ 72 ² " V’×7F FRÐ
disabled": "") + // highlight unselectable daysÐ™™™’†÷F†W$ÖöçF, bb
showOtherMonths ? "" : " " + daySettings[1] + // highlight custom datesÐ™™™•
(printDate.getTime() === currentDate.getTime() ? " " + this._currentClass :
"") + // highlight selected dayÐ™™™’‡ &–çDF FRævWEF–ÖR,’ ÓÓÒ FöF ’ævWEF–ÖR,’ ò "
ui-datepicker-today" : "")) + "'" + // highlight today (if different)Ð™™™’,,
otherMonth || showOtherMonths) && daySettings[2] ? " title='" +
daySettings[2].replace(/'/g, "'") + "'" : "") + // cell titleÐ™™™•
(unselectable ? "" : " data-handler='selectDay' data-event='click' data-
month='" + printDate.getMonth() + "' data-year='" + printDate.getFullYear() +
"'") + ">" + // actionsÐ™™™’†÷F†W$ÖöçF, bb 6†÷t÷F†W$ÖöçF‡2 ò "b7† ²" ¢ òò
display for other monthsÐ™™™’‡Vç6VÆV7F &ÆR ò #Ç7 â 6Æ 73ÒwV’×7F FRÖFVf VÇBsâ" ²
printDate.getDate() + "" : "<a class='ui-state-default" +Ð™™™•
(printDate.getTime() === today.getTime() ? " ui-state-highlight" : "") +Ð™™™•
(printDate.getTime() === currentDate.getTime() ? " ui-state-active" : "")
+ // highlight selected dayÐ™™™’†÷F†W$ÖöçF, ò " V’× &–÷&–G’×6V6öæF ’’" ¢ ""’ ² òò
distinguish dates from other monthsÐ™™™’"r ‡&VcÒr2sâ" ² &–çDF FRævWDF FR,’ ² #Âð
a>")) + "</td>"; // display selectable dateÐ™™™
printDate.setDate(printDate.getDate() + 1);Ð™™™printDate =
this._daylightSavingAdjust(printDate);Ð™™™Ý6 ÆVæFW" ³Ò F&öG’ ² #Â÷G#™™™™™™drawMonth+
+;Ð™™™if (drawMonth > 11)™™™{ÐG& tÖöçF, Ò™™™½G& u–V "™™™™™™

™™thisYear = new Date().getFullYear();™™determineYear =
function(value) {™™–f " –V " Ò ‡f ÇVRæÖ F6,,ö5²µÃÕÒâ¢ò’ ò G& u–V " ²
parseInt(value.substring(1), 10) :™™™(value.match(/[+\-].*/) ? thisYear +
parseInt(value, 10) :™™™parseInt(value, 10));™™÷ÐWGW&â †–4æ â‡–V "’ ò F†–5–V " ¢
year);™™™™};™™year = determineYear(years[0]);™™endYear = Math.max(year,
determineYear(years[1] || ""));™™year = (minDate ? Math.max(year,
minDate.getFullYear()) : year);™™endYear = (maxDate ? Math.min(endYear,
maxDate.getFullYear()) : endYear);™™inst.yearshtml += "<select class='ui-
datepicker-year' data-handler='selectYear' data-event='change'>";™™for (; year
<= endYear; year++) {™™––ç7Bç–V '6‡FÖÂ ³Ò #Æ÷ F–öâ f ÇVSÒr" ² –V " ² "r™™™½(year
=== drawYear ? " selected='selected'" : "") +™™™">" + year + "</option>™™™};™™
inst.yearshtml += "</select>";™™html += inst.yearshtml;™™inst.yearshtml = null;™™™™
html += this._get(inst, "yearSuffix");™™if (showMonthAfterYear) {™™‡FÖÂ ³Ò
(secondary || !(changeMonth && changeYear) ? " " : "") + monthHtml;™™}™™html
+= " "; // Close datepicker_header™™return html;™™÷ÐÓÒò¢ F§W7B öæR öb F†R
date sub-fields. */™™Ðö F§W7D–ç7DF FS¢ gVæ7F–öâ†–ç7BÂ öfg6WBÂ W&–öB’ ½var year
= inst.drawYear + (period === "Y" ? offset : 0),™™–ÖöçF, Ò –ç7BæG& tÖöçF, ²
(period === "M" ? offset : 0),™™–F ’ Ò Ö F,æÖ–â†–ç7Bç6VÆV7FVDF ’Â
this._getDaysInMonth(year, month)) + (period === "D" ? offset : 0),™™–F FR Ò
this._restrictMinMax(inst, this._daylightSavingAdjust(new Date(year, month,
day)));™™inst.selectedDay = date.getDate();™™inst.drawMonth = inst.selectedMonth
= date.getMonth();™™inst.drawYear = inst.selectedYear = date.getFullYear();™™if
(period === "M" || period === "Y") {™™–F†–2åöæ÷F–g”6† ævR†–ç7B™™½™™™ÒÓÒò¢ Vç7W&R
date is within any min/max bounds. */™™÷&W7G&–7DÖ–äÖ ƒ¢ gVæ7F–öâ†–ç7BÂ F FR’ ½
var minDate = this._getMinMaxDate(inst, "min"),™™–Ö „F FR Ò
this._getMinMaxDate(inst, "max"),™™–æWtF FR Ò †Ö–äF FR bb F FR Â Ö–äF FR ò
minDate : date);™™return (maxDate && newDate > maxDate ? maxDate : newDate);™™÷ÐÓÒò
* Notify change of month/year. */™™öæ÷F–g”6† ævS¢ gVæ7F–öâ†–ç7B’ ½var onChange
= this._get(inst, "onChangeMonthYear");™™if (onChange) {™™
onChange.apply((inst.input ? inst.input[0] : null),™™[inst.selectedYear,
inst.selectedMonth + 1, inst]);™™}™™÷ÐÓÒò¢ FWFW&Ö–æR F†R çVÖ&W" öb ÖöçF‡2 Fò 6†÷râ
*/™™ÖövWDçVÖ&W$ödÖöçF‡3¢ gVæ7F–öâ†–ç7B’ ½var numMonths = this._get(inst,
"numberOfMonths");™™return (numMonths == null ? [1, 1] : (typeof numMonths ===
"number" ? [1, numMonths] : numMonths));™™÷ÐÓÒò¢ FWFW&Ö–æR F†R 7W'&VçB Ö †–×VÒ
date - ensure no time components are set. */™™ÖövWDÖ–äÖ „F FS¢ gVæ7F–öâ†–ç7BÂ
minMax) {™™return this._determineDate(inst, this._get(inst, minMax + "Date"),
null);™™÷ÐÓÒò¢ f–æB F†R çVÖ&W" öb F –2 –â v–fVâ ÖöçF,â ¢ÿÖövWDF –4–äÖöçFƒ¢
function(year, month) {™™return 32 - this._daylightSavingAdjust(new Date(year,
month, 32)).getDate();™™÷ÐÓÒò¢ f–æB F†R F ’ öb F†R vVV² öb F†R f–'7B öb ÖöçF,â
*/™™ÖövWDf–'7DF ”ödÖöçFƒ¢ gVæ7F–öâ‡–V "Â ÖöçF,’ ½return new Date(year, month,
1).getDay();™™÷ÐÓÒò¢ FWFW&Ö–æW2 –b vR 6†÷VÆB ÆÆ÷r &æW‡B÷ &Wb" ÖöçF, F–7 Æ ’
change. */™™Ö6 ä F§W7DÖöçFƒ¢ gVæ7F–öâ†–ç7BÂ öfg6WBÂ 7W%–V "Â 7W$ÖöçF,’ ½var
numMonths = this._getNumberOfMonths(inst),™™–F FR Ò
this._daylightSavingAdjust(new Date(curYear,™™–7W$ÖöçF, ² †öfg6WB Â ò öfg6WB ¢
numMonths[0] * numMonths[1]), 1));™™if (offset < 0) {™™
date.setDate(this._getDaysInMonth(date.getFullYear(), date.getMonth()));™™}™™
return this._isInRange(inst, date);™™÷ÐÓÒò¢ –2 F†R v–fVâ F FR –â F†R 66W FVB
range? */™™Ö–4–å& ævS¢ gVæ7F–öâ†–ç7BÂ F FR’ ½var yearSplit, currentYear,™™Ö–äF FR
= this._getMinMaxDate(inst, "min"),™™–Ö „F FR Ò F†–2åövWDÖ–äÖ „F FR†–ç7BÂ &Ö ,"™™™™
minYear = null,™™–Ö …–V " Ò çVÆÂÍ–V '2 Ò F†–2åövWB†–ç7BÂ '–V %& ævR"™™½–b ‡–V '2™™™™½
yearSplit = years.split(":");™™currentYear = new Date().getFullYear();™™minYear =
parseInt(yearSplit[0], 10);™™maxYear = parseInt(yearSplit[1], 10);™™if
(yearSplit[0].match(/[+\-].*/)) {™™–Ö–å–V " ³Ò 7W'&VçE–V™™™™

™–æWr
Date().getFullYear() % 100 + parseInt(shortYearCutoff, 10));™return
{shortYearCutoff: shortYearCutoff,™–F ”æ ÖW56†÷'C¢ F†–2åövWB†–ç7BÂ
"dayNamesShort"), dayNames: this._get(inst, "dayNames"),™–ÖöçF„æ ÖW56†÷'C¢
this._get(inst, "monthNamesShort"), monthNames: this._get(inst,
"monthNames")};™ÒÒò¢ f÷&Ö B F†R v–fVâ F FR f÷" F–7 Æ ’â ¢ýöf÷&Ö DF FS¢
function(inst, day, month, year) {™if (!day) {™–ç7Bæ7W'&VçDF ’ Ò
inst.selectedDay;™––ç7Bæ7W'&VçDÖöçF, Ò –ç7Bç6VÆV7FVDÖöçF™½–ç7Bæ7W'&VçE–V " Ò
inst.selectedYear;™™™var date = (day ? (typeof day === "object" ? day :™
this._daylightSavingAdjust(new Date(year, month, day))) :™•
this._daylightSavingAdjust(new Date(inst.currentYear, inst.currentMonth,
inst.currentDay)));™return this.formatDate(this._get(inst, "dateFormat"),
date, this._getFormatConfig(inst));™Ý});™*™* Bind hover events for datepicker
elements.™* Done via delegate so the binding only occurs once in the lifetime
of the parent div.™* Global instActive, set by _updateDatepicker allows the
handlers to find their way back to the active picker.™*/™function
bindHover(dpDiv) {™f " 6VÆV7F÷" Ò &'WGFöâÂ çV’ÖF FW –6¶W"× &WbÂ çV’ÖF FW –6¶W"™
next, .ui-datepicker-calendar td a";™&WGW&â G F–bæFVÆVv FR‡6VÆV7F÷"Â
"mouseout", function() {™’B‡F†–2’ç&VÖ÷fT6Æ 72,'V’×7F FRÖ†÷fW""™½–b
(this.className.indexOf("ui-datepicker-prev") !== -1) {™™
$(this).removeClass("ui-datepicker-prev-hover");™™Ý–b
(this.className.indexOf("ui-datepicker-next") !== -1) {™™
$(this).removeClass("ui-datepicker-next-hover");™™Ý™™delegate(selector,
"mouseover", function(){™––b ,
$.datepicker._isDisabledDatepicker(instActive.inline ? dpDiv.parent()[0] :
instActive.input[0])) {™™$(this).parents(".ui-datepicker-
calendar").find("a").removeClass("ui-state-hover");™™$(this).addClass("ui-state-
hover");™™if (this.className.indexOf("ui-datepicker-prev") !== -1)™™™{™
$(this).addClass("ui-datepicker-prev-hover");™™™

™dialogClass: "",Ðdraggable: true,Ðide: null,Ðeight: "auto",Ð
maxHeight: null,ÐmaxWidth: null,ÐinHeight: 150,ÐinWidth: 150,Ðodal: false,Ð
position: {Ð–×“¢ &6VçFW"™Í C¢ &6VçFW"™Íöc¢ v–æF÷™Í6öÆÆ–6–öã¢ &f–B™Íòò Vç7W&R
the titlebar is always visibleÐ–W6–æs¢ gVæ7F–öâ, ÷2 ’™½var topOffset =
$(this).css(pos).offset().top;Ð™if (topOffset < 0) {ÐB, F†–2 ’æ772, 'F÷ "Â
pos.top - topOffset);Ð™ÐÐ,Ðesizable: true,Ðhow: null,Ðitle: null,Ðidth: 300ÐÐ
™// callbacksÐeforeClose: null,Ðlose: null,Ðrag: null,ÐragStart: null,Ð
dragStop: null,Ðfocus: null,Ðpen: null,Ðesize: null,ÐesizeStart: null,Ð
resizeStop: nullÐÒÐöö7&V FS¢ gVæ7F–öâ,’ ™½this.originalCss = {ÐF–7 Æ “¢
this.element[0].style.display,Ð–v–GFƒ¢ F†–2æVÆVÖVçE³ Òç7G–ÆRçv–GF™ÍÖ–ä†V–v‡C¢
this.element[0].style.minHeight,Ð–Ö „†V–v‡C¢ F†–2æVÆVÖVçE³ Òç7G–ÆRæÖ „†V–v‡B™Í
height: this.element[0].style.heightÐ}™Ðhis.originalPosition = {Ð &VçC¢
this.element.parent(),Ð––æFWƒ¢
this.element.parent().children().index(this.element)Ð}™Ðhis.originalTitle =
this.element.attr("title");Ðthis.options.title = this.options.title ||
this.originalTitle;Ðthis._createWrapper()™ÐÐhis.elementÐç6†÷r,•
™’ç&VÖ÷fT GG','F–FÆR™‘æ FD6Æ 72,'V’ÖF– ÆörÖ6öçFVçB V’×v–FvWBÖ6öçFVçB"•
™’æ VæEFò, F†–2çV”F– Æör Ð™½his._createTitlebar()™Ðhis._createButtonPane()™ÐÐf
(this.options.draggable && $.fn.draggable) {Ð–F†–2åöÖ ¶TG& vv &ÆR,™½ÐÐf
(this.options.resizable && $.fn.resizable) {Ð–F†–2åöÖ ¶U&W6–¦ &ÆR,™½ÐÐ
this._isOpen = false;ÐÒÐöö–æ–C¢ gVæ7F–öâ,’ ™½if (this.options.autoOpen) {™Ð
this.open();Ð™}ÐÐöö VæEFó¢ gVæ7F–öâ,’ ™½var element = this.options.appendTo;™Ðf
(element && (element.jquery || element.nodeType)) {Ð–&WGW&â B, VÆVÖVçB ™½Ð
return this.document.find(element || "body").eq(0);ÐÒÐöFW7G&÷“¢ gVæ7F–öâ,’
{Ðvar next,Ð÷&–v–æ Å ÷6–F–öâ Ò F†–2æ÷&–v–æ Å ÷6–F–öÐ™½his._destroyOverlay()™ÐÐ
this.elementÐ’ç&VÖ÷fUVæ– VT–B™‘ç&VÖ÷fT6Æ 72,'V’ÖF– ÆörÖ6öçFVçB V’×v–FvWBÐ
content")Ð’æ772, F†–2æ÷&–v–æ Ä772™‘òò v–F†÷WB FWF 6†–ær f–'7BÂ F†R föÆÆ÷v–ær
becomes really slowÐ’æFWF 6,,Ð™½his.uiDialog.stop(true, true).remove()™ÐÐf
(this.originalTitle) {Ð–F†–2æVÆVÖVçBæ GG", 'F–FÆR"Â F†–2æ÷&–v–æ ÅF–FÆR ™½Ð
next = originalPosition.parent.children().eq(originalPosition.index);Ð™//
Don't try to place the dialog next to itself (#8613)Ðif (next.length &&
next[0] !== this.element[0]) {Ð–æW‡Bæ&Vf÷&R, F†–2æVÆVÖVçB ™½ else {Ð
originalPosition.parent.append(this.element);Ð™}ÐÐv–FvWC¢ gVæ7F–öâ,’ ™½return
this.uiDialog;ÐÒÐF–6 &ÆS¢ Bææö÷ ÍVæ &ÆS¢ Bææö÷ Ð6Æ÷6S¢ gVæ7F–öâ, WfVçB ’ ™½var
activeElement,Ð–F† B Ò F†–Ð™½f (!this._isOpen || this._trigger("beforeClose",
event) === false) {Ð–&WGW&â™½Ðhis._isOpen = false,Ðhis._destroyOverlay()™ÐÐf
(!this.opener.filter(":focusable").focus().length) {Ð’òò 7W ÷'C¢ ”S‘òò ”S’
throws an "Unspecified error" accessing document.activeElement from an
<iframe>Ð–G'’™™½activeElement = this.document[0].activeElementÐ™Ð// Support:
IE9, IE10Ð™// If the <body> is blurred, IE will switch windows, see #4520™Ðf
(activeElement && activeElement.nodeName.toLowerCase() !== "body") {Ð™’òò
Hiding a focused element doesn't trigger blur in WebKitÐ™’òò 6ò –â 6 6R vR † fR
nothing to focus on, explicitly blur the active elementÐ™’òò ‡GG 3¢òð
bugs.webkit.org/show_bug.cgi?id=47182Ð™’B, 7F–fTVÆVÖVçB ’æ&ÇW",™™½Ð 6 F6,
(error) {}™™Ðhis._hide(this.uiDialog, this.options.hide, function() {Ð
that._trigger("close", event);Ð™})÷ÐÐ–4÷ Vã¢ gVæ7F–öâ,’ ™½return this._isOpen;Ð
–ÒÐÖ÷fUFõF÷ ¢ gVæ7F–öâ,’ ™½this._moveToTop()÷ÐÐöÖ÷fUFõF÷ ¢ gVæ7F–öâ, WfVçBÂ
silent) {Ðvar moved = !!
this.uiDialog.nextAll(":visible").insertBefore(this.uiDialog).length;Ðif
(moved && !silent) {Ð–F†–2å÷G&–vvW", &fö7W2"Â WfVçB ™½Ðeturn moved÷ÐÐ÷ Vã¢
function() {Ðvar that = this,Ðf (this._isOpen) {Ð–b , F†–2åöÖ÷fUFõF÷ ,’ ’™½
this._focusTabbable();Ð™Ý&WGW&â™½Ðhis._isOpen = true,Ðhis.opener =
$(this.document[0].activeElement);Ðthis._size()™Ðhis._position()™Ð
this._createOverlay();Ðthis._moveToTop(null, true)™Ð
this._show(this.uiDialog, this.options.show, function() {Ð•
that._focusTabbable();Ð–F† Bå÷G&–vvW",&fö7W2"™½)™ÐÐhis._trigger("open")÷ÐÐ
_focusTabbable: function() {Ð// Set focus to the first match™Ð// 1. First
element inside the dialog matching [autofocus]Ð// 2. Tabbable element inside
the content elementÐ// 3. Tabbable element inside the buttonpaneÐ™Ð// 4. The
close buttonÐ

™// 5. The dialog itselfÐvar hasFocus =
this.element.find("[autofocus]");Ðif (!hasFocus.length) {Ð† 4fö7W2 Ò
this.element.find(":tabbable");Ð™}Ðif (!hasFocus.length) {Ð† 4fö7W2 Ò
this.uiDialogButtonPane.find(":tabbable");Ð™}Ðif (!hasFocus.length) {Ð† 4fö7W2
= this.uiDialogTitlebarClose.filter(":tabbable");Ð™}Ðif (!hasFocus.length) {Ð
hasFocus = this.uiDialog;Ð™}ÐhasFocus.eq(0).focus();÷ÐÉö¶VW fö7W3¢
function(event) {Ðfunction checkFocus() {Ðvar " 7F–fTVÆVÖVçB Ò
this.document[0].activeElement,Ð™isActive = this.uiDialog[0] === activeElement
||Ð™'Bæ6öçF –ç2, F†–2çV"F– Æöu³ ÒÂ 7F–fTVÆVÖVçB™“½b , –4 7F–fR '™½
this._focusTabable();Ð™}Ðevent.preventDefault();ÐcheckFocus.call(this);Ð/
support: IEÐ// IE <= 8 doesn't prevent moving focus even with
event.preventDefault()Ð// so we check again lateÐthis._delay(checkFocus);÷ÐÉ
_createWrapper: function() {Ðthis.uiDialog = $(" ")Ðæ FD6Æ 72, 'V'ÖF– Æör
ui-widget ui-widget-content ui-corner-all ui-front " +Ð™
this.options.dialogClass)Ð'æ†–FR™‘æ GG"‡½// Setting tabIndex makes the div
focusableÐ™tabIndex: -1,Ðole: "dialog"Ð'æ VæEFò, F†–2åö VæEFò,' Ð½
this._on(this.uiDialog, {Ð–¶W–F÷vã¢ gVæ7F–öâ, WfVçB '™½if
(this.options.closeOnEscape && !event.isDefaultPrevented() && event.keyCode
&&Ð™event.keyCode === $.ui.keyCode.ESCAPE) {ÐfVçBç &WfVçDFVf VÇB,™½
this.close(event);Ð™–&WGW&Ð½Ð/ prevent tabbing out of dialogÐif
(event.keyCode !== $.ui.keyCode.TAB) {Ð™–&WGW&a½Ðvar tabbables =
this.uiDialog.find(":tabbable"),Ð™–f–'7B Ò F && &ÆW2æf–ÇFW",#¦f–'7B™ÍÆ 7B Ò
tabbables.filter(":last");Ð™if ((event.target === last[0] || event.target ===
this.uiDialog[0]) && !event.shiftKey) {Ð™–f–'7Bæfö7W2, ™½
event.preventDefault();Ð™} else if ((event.target === first[0] ||
event.target === this.uiDialog[0]) && event.shiftKey) {Ð™–Æ 7Bæfö7W2, ™½
event.preventDefault();Ð™}ÐÍÖ÷W6VF÷vã¢ gVæ7F–öâ, WfVçB '™½if
(this._moveToTop(event)) {Ð™–F†–2åöfö7W5F && &ÆR,™½Ð)ÐÐ/ We assume that
any existing aria-describedby attribute meansÐ// that the dialog content is
marked up properlyÐ// otherwise we brute force the content as the descriptioÐ™
if (!this.element.find("[aria-describedby]").length) {Ð–F†–2çV"F– Æöræ GG"‡½
™"aria-describedby": this.element.uniqueId().attr("id")Ð™½ÐÉö7&V FUF–FÆV& #¢
function() {Ðvar uiDialogTitlebar,Ðthis.uiDialogTitlebar = $(" ")Ðæ FD6Æ 72,'V'Ð
dialog-titlebar ui-widget-header ui-corner-all ui-helper-clearfix")Ð
™'ç &W VæEFò, F†–2çV"F– Æör ™½this._on(this.uiDialogTitlebar, {ÐÖ÷W6VF÷vã¢
function(event) {Ð™// Don't prevent click on close button (#8838)Ð/ Focusing
a dialog that is partially scrolled out of viewÐ™// causes the browser to
scroll it into view, preventing the click eventÐ™if (!
$(event.target).closest(".ui-dialog-titlebar-close")) {Ð™'òò F– Æör –6âwB
getting focus when dragging (#8063)Ð™–F†–2çV"F– Æöræfö7W2,™½Ð)ÐÐ/ support: IEÐ
™// Use type="button" to prevent enter keypresses in textboxes from closing theÐ
™// dialog in IE (#9312)Ðthis.uiDialogTitlebarClose = $("<button
type='button'></button>")Ð'æ'WGFöâ‡½label: this.options.closeText,Ðicons: {Ð
primary: "ui-icon-closethick"Ð },Ðext: falseÐ'æ FD6Æ 72,'V'ÖF– Æör×F–FÆV& "Ð
close")Ð'æ VæEFò, F†–2çV"F– ÆöuF–FÆV& " ™½
this._on(this.uiDialogTitlebarClose, {Ð–6Æ–6³¢ gVæ7F–öâ, WfVçB '™½
event.preventDefault();Ð™this.close(event);Ð)ÐuiDialogTitle = $("")Ð
™'çVæ– VT–B™‘æ FD6Æ 72,'V'ÖF– Æör×F–FÆR™‘ç &W VæEFò, F†–2çV"F– ÆöuF–FÆV& " ™½
this._title(uiDialogTitle);Ðthis.uiDialog.attr({Ð& &– ÖÆ &VÆÆVF''#¢
uiDialogTitle.attr("id")Ð})÷ÐÉ÷F–FÆS¢ gVæ7F–öâ, F–FÆR ' ™½if (!
this.options.title) {Ð–F–FÆRæ‡FÖÂ,"b3 c ²"™½Ðitle.text(this.options.title);Ð
–ÒÉö7&V FT'WGFöå æS¢ gVæ7F–öâ,' ™½this.uiDialogButtonPane = $(" ")Ð
™'æ FD6Æ 72,'V'ÖF– ÆörÖ'WGFöç æR V'×v–FvWBÖ6öçFVçB V'Ö†VÇ W"Ö6ÆV &f–,"Ð½
this.uiButtonSet = $(" ")Ð'æ FD6Æ 72,'V'ÖF– ÆörÖ'WGFöç6WB"•
™'æ VæEFò, F†–2çV"F– Æöt'WGFöå æR Ð½this._createButtons();ÐÉö7&V FT'WGFöç3¢
function() {Ðvar that = this,Ð'WGFöç2 Ò F†–2æ÷ F–öç2æ'WGFöçÐ½/ if we already
have a button pane, remove itÐthis.uiDialogButtonPane.remove();Ð
this.uiButtonSet.empty();Ðif ($.isEmptyObject(buttons) ||
($.isArray(buttons) && !buttons.length)) {Ð–F†–2çV"F– Æörç&VÖ÷fT6Æ 72,'V'Ð
dialog-buttons");Ð

™—&WGW&â™Ð.each(buttons, function(name, props) {Ðf " 6Æ–6²Â
buttonOptions;Ð— &÷ 2 Ò Bæ—4gVæ7F–öâ, &÷ 2 ’™Ý{ click: props, text: name }™:Ð
props;Ð’òò FVf VÇB Fò æöâ×7V&Ö—GF–ær 'WGFÖ¼ &÷ 2 Ò BæW‡FVæB, ² G— S¢
"button" }, props);Ð’òò 6† æVR F†R 6öçFW‡B f÷" F†R 6Æ–6² 6 ÆÆ& 6² Fò &R F†R
main elementÐ–6Æ–6² Ò &÷ 2æ6Æ–6™½ &÷ 2æ6Æ–6² Ò gVæ7F–öâ,’™½
click.apply(that.element[0], arguments);Ð—Ö½'WGFöä÷ F–öç2 Ò™½icons:
props.icons,Ð™text: props.showTeXtÐ½FVÆWFR &÷ 2æ–6öç3½FVÆWFR &÷ 2ç6†÷uFW‡Ö½
$("<button></button>", props)Ð™.button(buttonOptions)Ð
™™.appendTo(that.uiButtonSet);Ð™Ð;Ðthis.uiDialog.addClass("ui-dialog-buttons");Ð
this.uiDialogButtonPane.appendTo(this.uiDialog);ÐÒÉöÖ ¶TG& vv &ÆS¢
function() {Ðvar that = this,Ð÷ F–öç2 Ò F†—2æ÷ F–öçÐ½unction filteredUi(ui) {Ð
return {Ð™position: ui.position,™Ðoffset: ui.offsetÐ½Ðthis.uiDialog.draggable(™Ð
cancel: ".ui-dialog-content, .ui-dialog-titlebar-close",Ð–† æFÆS¢ "çV’ÖF– ÆörÐ
titlebar",Ð–6öçF –æÖVçC¢ &Fö7VÖVçB™Í7F 'C¢ gVæ7F–öâ, WfVçBÂ V’ ’™½
$(this).addClass("ui-dialog-dragging");Ð™that._blockFrames();Ð
that._trigger("dragStart", event, filteredUi(ui));Ð—ÖÍG& s¢
function(event, ui) {Ð™that._trigger("drag", event, filteredUi(ui));ÐÍ
stop: function(event, ui) {Ð™options.position =™Ð™Ð’ç ÷6—F–öâæÆVgB Ò
that.document.scrollLeft(),Ð™—V’ç ÷6—F–öâçF÷ Ò F† BæFö7VÖVçBç67&öÆÅF÷™™™™,Ð
$(this).removeClass("ui-dialog-dragging");Ð™that._unblockFrames();Ð
that._trigger("dragStop", event, filteredUi(ui));Ð—Ý);ÐÉöÖ ¶U&W6—¦ &ÆS¢
function() {Ðvar that = this,Ð÷ F–öç2 Ò F†—2æ÷ F–öçÍ† æFÆW2 Ò
options.resizable,Ð’òò çV’×&W6—¦ &ÆR † 2 ÷6—F–öã¢ &VÆ F—fR FVf–æVB –â F†R
stylesheetÐ’òò 'WB F– Æöw2 † fR Fò W6R '6öÇWFR ÷" f—†VB ÷6—F–öæ–æ} ÷6—F–öâ Ò
this.uiDialog.css("position"),Ð—&W6—¦T† æFÆW2 Ò G— Vöb † æFÆW2 ÓÓÒ '7G&–ær"™Ý
handles“™™"n,e,s,w,se,sw,ne,nwÐ;Ðunction filteredUi(ui) {Ð&WGW&â™½
originalPosition: ui.originalPosition,Ð™originalSize: ui.originalSizeÐ;Ðposition:
ui.position,Ð™size: ui.sizeÐ½Ðthis.uiDialog.resizable({Ð6 æ6VÃ¢ "çV’ÖF– ÆörÐ
content",Ð–6öçF –æÖVçC¢ &Fö7VÖVçB™Í Ç6õ&W6—¦S¢ F†—2æVÆVÖVçBÍÖ …v–GFƒ¢
options.maxWidth,Ð–Ö „†V–v‡C¢ ÷ F–öç2æÖ „†V–v‡BÍÖ–åv–GFƒ¢ ÷ F–öç2æÖ–åv–GF™Í
minHeight: this._minHeight(),Ð–† æFÆW3¢ &W6—¦T† æFÆW2Í7F 'C¢ gVæ7F–öâ, WfVçBÂ
ui) {Ð™$(this).addClass("ui-dialog-resizing");Ð™that._blockFrames();Ð
that._trigger("resizeStart", event, filteredUi(ui));Ð—ÖÍ&W6—¦S¢
function(event, ui) {Ð™that._trigger("resize", event, filteredUi(ui));ÐÍ
stop: function(event, ui) {Ð™options.height = $(this).height();Ð
options.width = $(this).width();Ð™$(this).removeClass("ui-dialog-resizing");Ð
that._unblockFrames();Ð™that._trigger("resizeStop", event, filteredUi(ui));Ð
™});Ðcss("position", position);ÐÉöÖ–ä†V–v‡C¢ gVæ7F–öâ,’ ½var options =
this.options;Ðreturn options.height === "auto" ?Ð÷ F–öç2æÖ–ä†V–v‡B™•
Math.min(options.minHeight, options.height);ÐÒÉ÷ ÷6—F–öã¢ gVæ7F–öâ,’ ½//
Need to show the dialog to get the actual offset in the position pluginÐvar
isVisible = this.uiDialog.is(":visible");Ðif (!isVisible) {Ð
this.uiDialog.show();Ð}Ðthis.uiDialog.position(this.options.position);Ðif (!
isVisible) {Ð—F†—2çV”F– Æöræ†–FR,™½ÐÉ÷6WD÷ F–öç3¢ gVæ7F–öâ, ÷ F–öç2 ’ ½var
that = this,Ð—&W6—¦R Ò f Ç6RÍ&W6—¦ &ÆT÷ F–öç2 Ò ·Ð½.each(options,
function(key, value) {Ð—F† Bå÷6WD÷ F–öâ, ¶W’Â f ÇVR Ð½–b , ¶W’ –â
sizeRelatedOptions) {Ð™resize = true,Ð–b , ¶W’ –â &W6—¦ &ÆU&VÆ FVD÷ F–öç2 ’™½
resizableOptions[key] = value;Ð—Ý);Ðif (resize) {ÐF†—2å÷6—¦R,™½
this._position();Ð}Ðif (this.uiDialog.is(":data(ui-resizable)")) {Ð
this.uiDialog.resizable("option", resizableOptions);Ð}ÐÉ÷6WD÷ F–öã¢
function(key, value) {Ðvar isDraggable, isResizable,ÐV”F– Æör Ò F†—2çV”F– ÆöÐ½
if (key === "dialogClass") {Ð—V”F– ÆÖ}.removeClass(this.options.dialogClass)Ð
™™.addClass(value);Ðif (key === "disabled") {Ð&WGW&â™Ðthis._super(key,
value);Ðif (key === "appendTo") {ÐF†—2çV”F– Æöræ VæEFò, F†—2åö VæEFò,’ “½
™Ðif (key === "buttons") {ÐF†—2åö7&V FT'WGFöç2,™Ðif (key === "closeText") {Ð
this.uiDialogTitlebarClose.button({Ð™// Ensure that we always pass a stringÐ
label: "" + valueÐ—Ö™Ðif (key === "draggable") {Ð—4G& vv &ÆR Ò
uiDialog.is(":data(ui-draggable)");Ð—–b , —4G& vv &ÆR bb f ÇVR ’™½
uiDialog.draggable("destroy");ÐÐÝ–b , —4G& vv &ÆR bb f ÇVR ’™½
this._makeDraggable();Ð

™™™™Ð–ÐÐif (key === "position") {™™ÐF†–2å÷ ÷6–F–öâ,™™™™Ðif (key
=== "resizable") {™™Ð'òò 7W'&VçFÇ' &W6–¦ &ÆRÂ &V6öÖ–ær æöâ×&W6–¦ &Æ™]–5&W6–¦ &ÆR
= uiDialog.is(":data(ui-resizable)");™™Ð--b , –5&W6–¦ &ÆR bb f ÇVR '™™½
uiDialog.resizable("destroy");™™™™ÐÝòò 7W'&VçFÇ' &W6–¦ &ÆRÂ 6† æv–ær † æFÆW™™–b
(isResizable && typeof value === "string") {™™™uiDialog.resizable("option",
"handles", value);™™™™ÐÝòò 7W'&VçFÇ' æöâ×&W6–¦ &ÆRÂ &V6öÖ–ær &W6–¦ &Æ™]–b ,
isResizable && value !== false) {™™™this._makeResizable();™™™™Ðif (key ===
"title") {™™Ð–F†–2å÷F–FÆR, F†–2çV"F– ÆöuF–FÆV& "æf–æB,"çV'ÖF– Æör×F–FÆR"' ™™½™™™™ÐÐ
_size: function() {™™Ð// If the user has resized the dialog, the .ui-dialog
and .ui-dialog-content™™Ð// divs will both have width and height set, so we need
to reset them™™Ðvar nonContentHeight, minContentHeight, maxContentHeight,™™Ð÷ F–öç2
= this.options;™™Ð// Reset content sizing™™Ðthis.element.show().css({™™Ðv–GFƒ¢ & WFò™™™™Í
minHeight: 0,™™Ð–Ö „†V–v‡C¢ &æöæR™™™™Í†V–v‡C¢™™});™™™™Ðif (options.minWidth >
options.width) {™™Ð–÷ F–öç2çv–GF, Ò ÷ F–öç2æÖ–åv–GF™™™™™™Ð/ reset wrapper sizing™™™™Ð/
determine the height of all the non-content elements™™™™ÐnonContentHeight =
this.uiDialog.css({™™™height: "auto",™™™™Ðwidth: options.width™™™™™™

™™™™™™™™position = $.extend({},
$.ui.dialog.prototype.options.position, position);™—Ò VÇ6R™™position =
$.ui.dialog.prototype.options.position;™™™Yòò æVVB Fò 6†÷r F†R F– Æör Fò vWB F†R
actual offset in the position plugin™––5f—6–&ÆR Ò F†–2çV”F– Æöræ—2,#§f—6–&ÆR"™™½
if (!isVisible) {™™this.uiDialog.show();™™™F†–2çV”F– Æörç ÷6—F–öâ, ÷6—F–öâ ™½
if (!isVisible) {™™this.uiDialog.hide();™™™™“½™(jQuery));™function($,
undefined) {™var rvertical = /up|down|vertical/,™' ÷6—F—fVÖ÷F–öâ Ò ÷W ÆÆVgGÀ
vertical|horizontal/;™$.effects.effect.blind = function(o, done) {™Òòò 7&V FR
element™™f " VÂ Ò B, F†—2 ’™™props = ["position", "top", "bottom", "left",
"right", "height", "width"],™™mode = $.effects.setMode(el, o.mode || "hide");™™
direction = o.direction || "up",™™vertical = rvertical.test(direction);™™def =
vertical ? "height" : "width",™™ref2 = vertical ? "top" : "left";™™motion =
rpositivemotion.test(direction);™™animation = {};™™show = mode === "show";™™
wrapper, distance, margin;™™Òòò –b Ç&V G’ w& VBÂ F†R w& W"w2 &÷ W'F–W2 &R
my property. #6245™–b , VÂç &VçB,’æ—2, "çV’ÖVffV7G2×w& W"" ’ ’ ™
$.effects.save(el.parent(), props);™™Ò VÇ6R ™$.effects.save(el, props);™™
el.show();™w& W" Ò BæVffV7G2æ7&V FUw& W", VÂ ’æ772‡™overflow: "hidden";™™Ò“™™
distance = wrapper[ref]();™™Ö &v–â Ò '6TfÆö B, w& W"æ772, &Vc" ’ ’ ÇÂ ™™
animation[ref] = show ? distance : 0;™–b , Ö÷F–öâ ’ ™eT™™æ772, fW'F–6 Â ò
"bottom" : "right", 0)™™’æ772, fW'F–6 Â ò 'F÷ " ¢ &ÆVgB"Â & WFò" •
™’æ772‡² ÷6—F–öã¢ & '6öÇWFR" Ò™™™animation[ref2] = show ? margin : distance +
margin;™™™Òòò 7F 'B B –b vR &R 6†÷v–æ}–b , 6†÷r ’ ™wrapper.css(ref, 0);™™™f
(! motion) {™™—w& W"æ772, &Vc"Â Ö &v–â ² F—7F æ6R ™™™™Òòò æ–Ö F•
wrapper.animate(animation, {™™duration: o.duration,™™easing: o.easing,™™queue:
false,™™complete: function() {™™–b , ÖöFR ÓÓÒ &†–FR" ’™™™el.hide();™™™
$.effects.restore(el, props);™™’BæVffV7G2ç&VÖ÷fUw& W", VÂ ™½FöæR,™™™Ò“™™;™™)
(jQuery);™function($, undefined) {™$.effects.effect.bounce = function(o,
done) {™™f " VÂ Ò B, F†—2 ’™™™™™™™™

™mode = $.effects.setMode(el,
o.mode || "hide"),™Ðshow = mode === "show",™Ðdirection = o.direction ||
"vertical",™Ðvert = direction === "vertical",™Ðsize = vert ? "height" : "width",™Ð
position = vert ? "top" : "left",™Ðanimation = {},™Ðwrapper, animate, distance;ÐÐòò
Save & ShowÐBæVffV7G2ç6 fR, VÂÂ &÷ 2 “½VÂç6†÷r,“ÐòÒ 7&V FR w& W–w& W" O
$.effects.createWrapper(el).css({™Ðoverflow: "hidden"™Ð“½ æ–Ö FR Ò
(el[0].tagName === "IMG") ? wrapper : el;™ÐF–7F æ6R Ò æ–Ö FU² 6–¦R Ò,“ÐòÒ
ShiftÐ–b , 6†÷r ’ ™½animate.css(size, 0),™Ðanimate.css(position, distance /
2);™ÐÐòÒ 7&V FR æ–Ö F–öâ ö&¦V7C– æ–Ö F–öå² 6–¦R Ò Ò 6†÷r ò F–7F æ6R ¢ ½
animation[position] = show ? 0 : distance / 2;™ÐòÒ æ–Ö F™
animate.animate(animation, {™Ðqueue: false,™Ðduration: o.duration,™Ðeasing:
o.easing,™Ðcomplete: function() {™Ð–b , 6†÷r ’™½el.hide();™™Ð
$.effects.restore(el, props);™Ð’BæVffV7G2ç&VÖ÷fUw& W", VÂ ™½FöæR,™½Ð“½;™Ð)
(jQuery);™Ðfunction($, undefined) {™Ð$.effects.effect.drop = function(o,
done) {™Ðvar " VÂ Ò B, F†–2 ’™Ðprops = ["position", "top", "bottom", "left",
"right", "opacity", "height", "width"],™Ðmode = $.effects.setMode(el, o.mode
|| "hide"),™Ðshow = mode === "show",™Ðdirection = o.direction || "left",™Ðref =
(direction === "up" || direction === "down") ? "top" : "left",™Ðmotion =
(direction === "up" || direction === "left") ? "pos" : "neg",™Ðanimation = {™Ð
opacity: show ? 1 : 0™Ð},™Ðdistance;ÐÐòÒ F§W7™BæVffV7G2ç6 fR, VÂÂ &÷ 2 “½
el.show();™ÐBæVffV7G2æ7&V FUw& W", VÂ “™ÐF–7F æ6R Ò òæF–7F æ6R ÇÂ VÅ² &Vb ÓÓÒ
"top" ? "outerHeight": "outerWidth"](true) / 2;™Ð–b , 6†÷r ’ ™½elÐ
™’æ772, &÷ 6–G’"Â ™‘æ772, &VbÂ Ö÷F–öâ ÓÓÒ ' ÷2" ò ÖF–7F æ6R ¢ F–7F æ6R “™ÐòÒ
AnimationÐ æ–Ö F–öå² &Vb Ò Ò , 6†÷r ™(motion === "pos" ? "+=" : "-=") :™Ð
(motion === "pos" ? "-=" : "+=")) +™ÐdistanceÐÐòÒ æ–Ö F™
el.animate(animation, {™Ðqueue: false,™Ðduration: o.duration,™Ðeasing: o.easing,™Ð
complete: function() {™Ð–b , ÖöFR ÓÓÒ &†–FR" ’™½el.hide();™™Ð
$.effects.restore(el, props);™Ð’BæVffV7G2ç&VÖ÷fUw& W", VÂ ™½FöæR,™½Ð“½;™Ð)
(jQuery);™Ðfunction($, undefined) {™Ð$.effects.effect.explode = function(o,
done) {™Ðvar " &÷w2 Ò òç –V6W2 ò Ö F,ç&÷VæB, Ö F,ç7 'B, òç –V6W2 ’ ’ ¢ 2™Ðcells =
rows,™Ðel = $(this),™Ðmode = $.effects.setMode(el, o.mode || "hide"),™Ðshow =
mode === "show",™Ð// show and then visibility:hidden the element before
calculating offset™Ðoffset = el.show().css("visibility", "hidden").offset();™Ð
™// width and height of a piece™Ðwidth = Math.ceil(el.outerWidth() / cells),™Ð
height = Math.ceil(el.outerHeight() / rows),™Ðpieces = [];™Ð// loop™Ði, j, left,
top, mx, my;™ÐòÒ 6†–ÆG&Vâ æ–Ö FR 6ö× ÆWFS–gVæ7F–öâ 6†–ÆD6ö× ÆWFR,’ ™½
pieces.push(this);™Ðif (pieces.length === rows * cells) {™Ð æ–Ô6ö× ÆWFR,™½™Ð
’òò 6ÆöæR F†R VÆVÖVçB f÷" V 6, &÷r æB 6VÆÂ¿f÷", ’ Ò ² ’ Â &÷w2 ² ’²² ’ ² òò
===>™Ðtop = offset.top + i * height;™Ðy = i - (rows - 1) / 2 ™Ðfor(j = 0; j <
cells ; j++) { // |||™Ð–ÆVgB Ò öfg6WBæÆVgB ² ¢ ¢ v–GF™½×, Ò ¢ Ò , 6VÆÇ2 Ò ’ ò
2 ;™Ð’òò 7&V FR 6ÆöæR öb F†R æ÷r †–FFVâ Ö –â VÆVÖVçB F† B v–ÆÂ &R '6öÇWFR
positioned™Ð’òò v–F†–â w& W" F–b öfb F†R ÖÆVgB æB ×F÷ W V Â Fò 6–¦R öb ÷W"
pieces™Ð–V™.clone();™ÐappendTo("body");™Ðwrap(" ");™Ðcss({™Ð ÷6–F–öã¢
"absolute",™Ð–f–6–&–Æ–G“¢ 'f–6–&ÆR™¿ÆVgC¢ Ö¢ ¢ v–GF™¿F÷ ¢ Ö’ ¢ †V–V‡™™¿™™™

™show = mode === "show",Ðide = mode
=== "hide",™size = o.size || 15,™percent = /([0-9]+)%/.exec(size),™ÐorizFirst
= !!o.horizFirst,™widthFirst = show !== horizFirst,™Ðef = widthFirst ?
["width", "height"] : ["height", "width"],™Ðuration = o.duration / 2,™Ð
wrapper, distance,™Ðanimation1 = {},™Ðnimation2 = {};™ÐæVffV7G2ç6 fR, VÂÂ &÷ 2 “½
el.show();™Ðòò 7&V FR w& W—w& W" Ò BæVffV7G2æ7&V FUw& W", VÂ ’æ772‡™½
overflow: "hidden"™ÐÒ“½F—7F æ6R Ò v–GF„f—'7B ™[wrapper.width(),
wrapper.height()] :™[wrapper.height(), wrapper.width()];™Ðb , W&6VçB ’ ™½
size = parseInt(percent[1], 10) / 100 * distance[hide ? 0 : 1];™Ð¥–b
(show) {™Ðwrapper.css(horizFirst ? ™Ð†V–v‡C¢ ™Í÷v–GƒÇ 6—™} : ™Ð†V–v‡C¢ 6—¦™Í
width: 0™Ð});™Ðòò æ–Ö F–öí æ–Ö F–öã ² &Ve² Ò Ò Ò 6†÷r ò F—7F æ6U² Ò ¢ 6—¦S½
animation2[ref[1]] = show ? distance[1] : 0;™Ðòò æ–Ö F‡w& W-
™.animate(animation1, duration, o.easing);™Ðanimate(animation2, duration,
o.easing, function() {™Ð--b , †–FR ’™½el.hide();™ÐBæVffV7G2ç&W7F÷&R, VÂÂ &÷ 2 ™½
$.effects.removeWrapper(el);™Ð–FöæR,™½);™Ð™Ð)(jQuery);™Ðfunction($,
undefined) {™Ð.effects.effect.highlight = function(o, done) {™Ðf " VÆVÒ Ò
$(this),™Ðprops = ["backgroundImage", "backgroundColor", "opacity"],™Ðode =
$.effects.setMode(elem, o.mode || "show"),™Ðanimation = {™Ð& 6¶w&÷VæD6öÆ÷#¢
elem.css("backgroundColor")™Ð};™Ðb †ÖöFR ÓÓÒ &†–FR"’ ™½animation.opacity = 0;™Ð
$.effects.save(elem, props);™ÐVÆVÝ.show();™Ðcss({™Ð& 6¶w&÷VæD–Ö vS¢ &æöæR™Í
backgroundColor: o.color || "#ffff99"™Ð});™Ðanimate(animation, ™Ð VWVS¢ f Ç6R™Í
duration: o.duration,™Ð–V 6–æs¢ òæV 6–ær™Í6ö× ÆWFS¢ gVæ7F–öâ,’™½if (mode ===
"hide") {™Ð™–VÆVÒæ†–FR,™½™™™

™outerWidth: original.outerWidth * factor.x
’òò f FR ÷ F–öâ Fò 7W ÷'B Vfm–b , ÷ F–öç2æf FR ’ ½if (mode === "show") {
options.from.opacity = 0;–÷ F–öç2çFòæ÷ 6—G’ Ò ½if (mode === "hide") {
options.from.opacity = 1;–÷ F–öç2çFòæ÷ 6—G’ Ò ½Òòò æ–Ö F
el.effect(options);$.effects.effect.size = function(o, done) {Òòò 7&V FR
elementf " ÷&–v–æ ÂÂ & 6VÆ–æRÂ f 7F÷"Iel = $(this),Ôprops0 = ["position",
"top", "bottom", "left", "right", "width", "height", "overflow", "opacity"],
™// Always restoreÔprops1 = ["position", "top", "bottom", "left", "right",
"overflow", "opacity"],–// Copy for childrenÔprops2 = ["width", "height",
"overflow"],–cProps = ["fontSize"],–Ôprops = ["borderTopWidth",
"borderBottomWidth", "paddingTop", "paddingBottom"],–hProps =
["borderLeftWidth", "borderRightWidth", "paddingLeft", "paddingRight"],–//
Set optionsÔmode = $.effects.setMode(el, o.mode || "effect"),Ôestore =
o.restore || mode !== "effect",–scale = o.scale || "both",Ôrigin = o.origin ||
["middle", "center"],–position = el.css("position"),Ôprops = restore ?
props0 : props1,–zero = {Ô†V–v‡C¢ ™Ív–GFƒ¢ ™Í÷WFW$†V–v‡C¢ ™Í÷WFW%v–GFƒ¢™}–Ôb
(mode === "show") {–el.show();–÷&–v–æ Â Ò ½height: el.height(),Ôwidth:
el.width(),–outerHeight: el.outerHeight(),Ôouterwidth: el.outerWidth();–b
(o.mode === "toggle" && mode === "show") {–el.from = o.to || zero,Ôel.to =
o.from || original;ÔÒ VÇ6R ½el.from = o.from || (mode === "show" ? zero :
original);–el.to = o.to || (mode === "hide" ? zero : original);–Òòò 6WB
scaling factorÔf 7F÷" Ò ½from: {Ô“¢ VÂæg&öÒæ†V–v‡B ò ÷&–v–æ Âæ†V–v‡BÍƒ¢
el.from.width / original.width},Ôto: {Ô“¢ VÂçFòæ†V–v‡B ò ÷&–v–æ Âæ†V–v‡BÍƒ¢
el.to.width / original.width}–ÒÒòò 66 ÆR F†R 772 &÷•–b , 66 ÆR ÓÓÒ &&÷," ÇÂ
scale === "both") {–// Vertical props scalingÔf (factor.from.y !==
factor.to.y) {–— &÷ 2 Ò &÷ 2æ6öæ6 B, e &÷ 2 ™½VÂæg&öÒ Ò
$.effects.setTransition(el, vProps, factor.from.y, el.from);–VÂçFò Ò
$.effects.setTransition(el, vProps, factor.to.y, el.to);–Ô–/ Horizontal
props scalingÔif (factor.from.x !== factor.to.x) {Ô &÷ 2 Ò
props.concat(hProps);–VÂæg&öÒ Ò BæVffV7G2ç6WEG& ç6—F–öâ, VÂÂ … &÷ 2Â
factor.from.x, el.from);–VÂçFò Ò BæVffV7G2ç6WEG& ç6—F–öâ, VÂÂ … &÷ 2Â
factor.to.x, el.to);–ÒÒòò 66 ÆR F†R 6öçFVçM–b , 66 ÆR ÓÓÒ &6öçFVçB" ÇÂ 66 ÆR
=== "both") {–// Vertical props scalingÔif (factor.from.y !== factor.to.y) {Ô
props = props.concat(cProps).concat(props2);–VÂæg&öÒ Ò
$.effects.setTransition(el, cProps, factor.from.y, el.from);–VÂçFò Ò
$.effects.setTransition(el, cProps, factor.to.y, el.to);–Ô
$.effects.save(el, props);ÔVÂç6†÷r,“½BæVffV7G2æ7&V FUw& W", VÂ “½
el.css("overflow", "hidden").css(el.from);ÔÒòò F§W7M–b †÷&–v–â’ ² òò
Calculate baseline shiftsÔbaseline = $.effects.getBaseline(origin, original),Ô
el.from.top = (original.outerHeight - el.outerHeight()) * baseline.y;–
el.from.left = (original.outerWidth - el.outerWidth()) * baseline.x;–
el.to.top = (original.outerHeight - el.to.outerHeight) * baseline.y;–
el.to.left = (original.outerWidth - el.to.outerWidth) * baseline.x;–
el.css(el.from); // set top & leftÔòò æ–Ö F–b , 66 ÆR ÓÓÒ &6öçFVçB" ÇÂ
scale === "both") { // Scale the childrenÔ// Add margins/font-sizeÔprops =
vProps.concat(["marginTop", "marginBottom"]).concat(cProps);–hProps =
hProps.concat(["marginLeft", "marginRight"]);–props2 =
props0.concat(vProps).concat(hProps);–el.find("*[width]").each(function(){Ô
var child = $(this),–c_original ={Ô†V–v‡C¢ 6†–ÆBæ†V–v‡B,–Ív–GFƒ¢
child.width(),–÷WFW$†V–v‡C¢ 6†–ÆBæ÷WFW$†V–v‡B,–Í÷WFW%v–GFƒ¢ 6†–ÆBæ÷WFW%v–GF,,•
};–Ôb ‡&W7F÷&R’½$.effects.save(child, props2)–Ô6†–ÆBæg&öÒ Ò½height:
c_original.height * factor.from.y,–width: c_original.width * factor.from.x,Ô
outerHeight: c_original.outerHeight * factor.from.y,–outerWidth:
c_original.outerWidth * factor.from.xÔ—Ó½6†–ÆBçFò Ò½height: c_original.height
* factor.to.y,–width: c_original.width * factor.to.x,Ôouterheight:
c_original.height * factor.to.y,–outerWidth: c_original.width * factor.to.x
’òò fW'F–6 Â &÷ 2 66 Æ–æ}–b , f 7F÷"æg&öÒç’ ÓÒ f 7F÷"çFòç’ ’½child.from =
$.effects.setTransition(child, vProps, factor.from.y, child.from);–child.to
= $.effects.setTransition(child, vProps, factor.to.y, child.to);–Ôòò
Horizontal props scalingÔ

™––b , f 7F÷"æg&öÒç, ÓÒ f 7F÷"çFòç, ’™½child.from =
$.effects.setTransition(child, hProps, factor.from.x, child.from);Ð™child.to
= $.effects.setTransition(child, hProps, factor.to.x, child.to);ÐÐÝòò æ–Ö FR
childrenÐ–6†–ÆBæ772, 6†–ÆBæg&öÒ ™½6†–ÆBæ æ–Ö FR, 6†–ÆBçFòÂ òæGW& F–öâÂ
o.easing, function() {Ð™// Restore childrenÐif (restore)™{Ð
$.effects.restore(child, props2);Ð™]Ð™½)÷Ðòò æ–Ö F]VÂæ æ–Ö FR, VÂçFòÂ ™½
queue: false,Ðduration: o.duration,™Ðasing: o.easing,™Ðomplete: function() {Ð–b
(el.to.opacity === 0) {Ð™el.css("opacity", el.from.opacity)™Ð–b, ÖöFR ÓÓÒ
"hide") {Ð™el.hide()™ÐBæVffV7G2ç&W7F÷&R, VÂÂ &÷ 2 ™½–b , &W7F÷&R ’Ð™½// we
need to calculate our new positioning based on the scalingÐ™if (position ===
"static") {Ð™–VÂæ772‡™½position: "relative",™Ðop: el.to.top,™Ðeft: el.to.left™Ð½
else {Ð™’BæV 6,…² 'F÷ "Â &ÆVgB" ÒÂ gVæ7F–öâ, –G,Â ÷2 ™½el.css(pos,
function(_, str) {Ð™™–f " f Â Ò '6T–çB, 7G"Â ™™™™™ÎtoRef = idx ? el.to.left :
el.to.top;Ð™’òò –b ÷&–v–æ Â v 2 & WFò"Â &V6 Æ7VÆ FR F†R æWr f ÇVR g&öÒ w& ™™™W––b
(str === "auto") {Ð™™™return toRef + "™™™™™

™’æ VæEFò, Fö7VÖVçBæ&öG’ •
™’æ FD6Æ 72, òæ6Æ 74æ ÖR™‘æ772‡½top: startPosition.top - fixTop™,Ðleft:
startPosition.left - fixLeft ,Ð™height: elem.innerHeight(),Ðwidth:
elem.innerWidth(),Ð™position: targetFixed ? "fixed" : "absolute"—Ò•
™’æ æ–Ö FR, æ–Ö F–öâÂ òæGW& F–öâÂ òæV 6–ærÂ gVæ7F–öâ,’™½transfer.remove(),Ð™
done();Ð—Ò½½Ð)(jQuery);Ðfunction($, undefined) {Ð$.widget("ui.menu", {Ð
version: "1.10.4",ÐFVf VÇDVÆVÖVçC¢ #ÇVÃâ"ÍFVÆ “¢ 3 Í÷ F–öç3¢ ™icons: {Ð™
submenu: "ui-icon-carat-1-e"Ð},Ð™menus: "ul",Ðposition: {Ð×“¢ &ÆVgB F÷ ™Í C¢
"right top"Ð},Ð™role: "menu"ÐØ/ callbacksÐblur: null,Ð™focus: null,Ð™select: nullÒÐ
_create: function() {Ð™this.activeMenu = this.element,Ð™// flag used to prevent
firing of the click handlerÐ™// as the event bubbles up through nested menusÐ™
this.mouseHandled = false;Ð™this.elementÐçVæ— VT–B™‘æ FD6Æ 72, 'V’ÖÖVçR V’Ð
widget ui-widget-content ui-corner-all")Ð™’çFövvÆT6Æ 72, 'V’ÖÖVçRÖ–6öç2"Â
this.element.find(".ui-icon").length)Ð™’æ GG"‡½role: this.options.role™,Ð™
tabIndex: 0Ð—Ò‘òò æVVB Fò 6 F6, ÆÂ 6Æ–6·2 öâ F—6 &ÆVB ÖVÇ™]òò æ÷B ÷76–&ÆR
through _onÐ™’æ&–æB, &6Æ–6² ² F†—2æWfVçDæ ÖW7 6RÂ Bç &÷‡’†gVæ7F–öâ, WfVçB ’™½
if (this.options.disabled) {Ð™–WfVçBç &WfVçDFVf VÇB™½ÒÂ F†—2 ’Ð½f
(this.options.disabled) {Ð—F†—2æVÆVÖVÇ™.addClass("ui-state-disabled")Ð
™™.attr("aria-disabled", "true")ÐØthis._on({™Ðòò &WfVçB fö7W2 g&öÒ 7F–6¶–ær Fò
links inside menu after clickingÐ™’òò F†VÒ †fö7W2 6†÷VÆB Çv —2 7F ’ öâ TÂ
during navigation).Ð™’&Ö÷W6VF÷vâ çV’ÖÖVçRÖ—FVÒ â #¢ gVæ7F–öâ, WfVçB ’™½
event.preventDefault();Ð—ÒÍ&6Æ–6² çV’×7F FRÖF—6 &ÆVB â #¢ gVæ7F–öâ, WfVçB ’™½
event.preventDefault();Ð—ÒÍ&6Æ–6² çV’ÖÖVçRÖ—FVÓ¦† 2† ’#¢ gVæ7F–öâ, WfVçB ’™½var
target = $(event.target).closest(".ui-menu-item");Ð™if (!this.mouseHandled
&& target.not(".ui-state-disabled").length) {Ð™—F†—2ç6VÆV7B, WfVçBÐ™½òò öæÇ’
set the mouseHandled flag if the event will bubble, see #9469.Ð™––b ,
event.isPropagationStopped()) {Ð™™this.mouseHandled = truÐ™ÐØòò ÷ Vâ 7V&ÖVçR öâ
clickÐ™––b , F &vWBæ† 2, "çV’ÖÖVçR" ’æÆVæwF, ™™½this.expand(event™);÷Ð VÇ6R –b
(!this.element.is(":focus") &&
$(this.document[0].activeElement).closest(".ui-menu").length) {Ð™™™//
Redirect focus to the menuÐ™™this.element.trigger("focus", [true]Ð™);Ð™/ If the
active item is on the top level, let it stay active.Ð™™™// Otherwise, blur the
active item since it is no longer visible.Ð™™™if (this.active &&
this.active.parents(".ui-menu").length === 1) {Ð™™™–6ÆV %F–ÖV÷WB, F†—2çF–ÖW™™™™½Ð
™™™™™—}ÐÍ&Ö÷W6VVçFW" çV’ÖÖVçRÖ—FVÒ#¢ gVæ7F–öâ, WfVçB ’™½var target =
$(event.currentTarget);Ð™™// Remove ui-state-active class from siblings of the
newly focused menu itemÐ™™// to avoid a jump caused by adjacent elements both
having a class with a borderÐ™™target.siblings().children(".ui-state-
active").removeClass("ui-state-active");Ð™™this.focus(event, target);÷ÐÍ
mouseleave: "collapseAll",Ð™’&Ö÷W6VÆV fR çV’ÖÖVçR#¢ &6öÆÆ 6T ÆÂ™Ífö7W3¢
function(event, keepActiveItem) {Ð™™// If there's already an active item, keep
it activeÐ™™// If not, activate the first itemÐ™™var item = this.active ||
this.element.children(".ui-menu-item").eq(0);Ð™™if (!keepActiveItem)Ð™™{Ð
this.focus(event, item);Ð™™}ÐÍ&ÇW#¢ gVæ7F–öâ, WfVçB ’™½this._delay(function()™{Ð™™
if (!$.contains(this.element[0], this.document[0].activeElement)) {Ð™™™
this.collapseAll(event);Ð™™™™™

™™.children().each(function() {Ðf " VÆVÒ Ò
$(this);Ð™––b , VÆVÒæF F , 'V’ÖÖVçR×7V&ÒVçRÖ6 & B" ’ ™™½elem.remove();ÐÐ/Ð
Destroy menu dividersÐthis.element.find(".ui-menu-divider").removeClass("ui-
menu-divider ui-widget-content");ÐÒÉö¶W–F÷vã¢ gVæ7F–öâ, WfVçB ’ ½var match,
prev, character, skip, regex,Ð– &WfVçDFVf VÇB Ò G'VÐ½unction escape(value) {Ð
return value.replace(/[\-\[\]{}()*+?.,\\\^$|#\s]/g, "\\$&");ÐÐÐwitch
(event.keyCode) {Ðcase $.ui.keyCode.PAGE_UP:ÐF†–2ç &Wf–÷W5 vR, WfVçB ™½'&V ™½
case $.ui.keyCode.PAGE_DOWN:Ð–F†–2ææW‡E vR, WfVçB ™½'&V ™½case
$.ui.keyCode.HOME:Ð–F†–2åöÖ÷fR, &f–'7B"Â &f–'7B"Â WfVçB ™½'&V ™½case
$.ui.keyCode.END:Ð–F†–2åöÖ÷fR, &Æ 7B"Â &Æ 7B"Â WfVçB ™½'&V ™½case
$.ui.keyCode.UP:Ð–F†–2ç &Wf–÷W2, WfVçB ™½'&V ™½case $.ui.keyCode.DOWN:Ð
this.next(event);Ð–'&V ™½case $.ui.keyCode.LEFT:ÐF†–2æ6öÆÆ 6R, WfVçB ™½'&V ™½
case $.ui.keyCode.RIGHT:Ð––b , F†–2æ 7F–fR bb F†–2æ 7F–fRæ–2, "çV’×7F FRÐ
disabled")) {Ð™this.expand(event);ÐÉ'&V ™½case $.ui.keyCode.ENTER:Ðase
$.ui.keyCode.SPACE:Ð–F†–2åö 7F–f FR, WfVçB ™½'&V ™½case $.ui.keyCode.ESCAPE:Ð
this.collapse(event);Ð–'&V ™½default:Ð &WfVçDFVf VÇB Ò f Ç6S½ &Wb Ò
this.previousFilter || "";Ð–6† & 7FW" Ò 7G&–æræg&öÔ6† $6öFR, WfVçBæ¶W”6öFR ™½
skip = false;Ð–6ÆV %F–ÖV÷WB, F†–2æf–ÇFW%F–ÖW" Ð½–b , 6† & 7FW" ÓÓÒ &Wb ’™½skip
= true;Ð–Ò VÇ6R™½character = prev + characterÐÐÉ&VvW, Ò æWr &VtW‡ , %â" ²
escape(character), "i");Ð–Ö F6, Ò F†–2æ 7F–fTÖVçRæ6†–ÆG&Vâ, "çV’ÖÖVçRÐ
item").filter(function() {Ð™return
regex.test($(this).children("a").text());Ð–Ò™½Ö F6, Ò 6¶– bb
match.index(this.active.next()) !== -1 ?Ð™this.active.nextAll(".ui-menu-
item") :Ð™matchÐ;Ðò –b æò Ö F6†W2 öâ F†R 7W'&VçB f–ÇFW"Â &W6WB Fò F†R Æ 7B
character pressedÐ’òò Fò Ö÷fR F÷vâ F†R ÖVçR Fò F†R f–'7B –FVÒ F† B 7F 'G2 v–F,
that characterÐ––b , Ö F6,æÆVæwF, ’™½character =
String.fromCharCode(event.keyCode);Ð™regex = new RegExp("^" +
escape(character), "i");Ð™match = this.activeMenu.children(".ui-menu-
item").filter(function() {Ð™–&WGW&â
regex.test($(this).children("a").text());Ð™}ÐÐ–b , Ö F6,æÆVæwF, ’™½
this.focus(event, match);Ð™if (match.length > 1) {ÐF†–2ç &Wf–÷W4f–ÇFW" Ò
character;Ð™–F†–2æf–ÇFW%F–ÖW" Ò F†–2åöFVÆ ’†gVæ7F–öâ,™½delete
this.previousFilter;Ð™–ÒÂ ™™½ else™{ÐFVÆWFR F†–2ç &Wf–÷W4f–ÇFW#½Ò VÇ6R™½
delete this.previousFilter;Ð–ÐÉf (preventDefault) {ÐWfVçBç &WfVçDFVf VÇB,™½ÒÐ
_activate: function(event) {Ðif (!this.active.is(".ui-state-disabled")) {Ð
if (this.active.children("a[aria-haspopup='true']").length) {Ð™
this.expand(event);Ð–Ò VÇ6R™½this.select(event);ÐÉ&Vg&W6ƒ¢ gVæ7F–öâ,’ ½
var menus,Ð––6öâ Ò F†–2æ÷ F–öç2æ–6öç2ç7V&ÖVçRÍ7V&ÖVçW2 Ò
this.element.find(this.options.menus);Ðthis.element.toggleClass("ui-menu-
icons", !!this.element.find(".ui-icon").length);Ð// Initialize nested menusÐ
submenus.filter(":not(.ui-menu)")Ð’æ FD6Æ 72, 'V’ÖÖVçR V’×v–FvWB V’×v–FvWBÐ
content ui-corner-all")Ð’æ†–FR™‘æ GG"™™½role: this.options.role,Ðaria-hidden":
"true",Ð™"aria-expanded": "false"Ð™‘æV 6,†gVæ7F–öâ,’™½var menu = $(this);Ð–FVÒ
= menu.prev("a");Ð™–7V&ÖVçT6 & B Ò B, #Ç7 ãâ™™•.addClass("ui-menu-icon ui-
icon " + icon)Ð™™.data("ui-menu-submenu-carat", trueÐ);ÐemÐæ GG", & &– Ð
haspopup", "true")Ð™’ç &W VæB, 7V&ÖVçT6 & B™™menu.attr("aria-labelledby",
item.attr("id"));Ð–ÒÐmenus = submenus.add(this.element);ÐÐ/ Don't refresh
list items that are already adaptedÐmenus.children(":not(.ui-menu-
item):has(a)")Ð’æ FD6Æ 72, 'V’ÖÖVçRÖ–FVÒ"™‘æ GG", '&öÆR"Â ' &W6VçF F–öâ" •
™’æ6†–ÆG&Vâ, & "™•.uniqueId()ÐaddClass("ui-corner-all"™)Ðattr({ÐF $–æFWƒ¢ Ó™Í
role: this._itemRole()Ð™}Ð/Ð Initialize unlinked menu-items containing spaces
and/or dashes only as dividersÐmenus.children(":not(.ui-menu-
item)").each(function() {Ð–f " –FVÒ Ò B, F†–2 ™½òò ‡– †VâÂ VÒ F 6,Â Vâ F Ó•–b
(!/[^\-\u2014\u2013\s]/.test(item.text())) {Ð™item.addClass("ui-widget-
content ui-menu-divider");Ð–™Ý}ÐÐ/ Add aria-disabled attribute to any disabled
menu itemÐmenus.children(".ui-state-disabled").attr("aria-disabled",
"true");Ð// If the active item has been removed, blur the menuÐf
(this.active && !$.contains(this.element[0], this.active[0])) {Ð•
this.blur();Ð}ÒÉö–FVÕ&öÆS¢ gVæ7F–öâ,’ ½return {ÐÖVçS¢ &ÖVçV–FVÒ™ÍÆ–7F&÷ƒ¢
"option"Ð

™}[this.options.role];ÒÉ÷6WD÷ F–öã¢ gVæ7F–öâ, ¶W’Â f ÇVR ’ ™½if (key
=== "icons") {Ð—F†–2æVÆVÖVçBæf–æB, "çV’ÖÖVçRÖ–6öâ" •
™™.removeClass(this.options.icons.submenu™)ÐaddClass(value.submenu ™)}Ð
this._super(key, value);ÐÒÉfö7W3¢ gVæ7F–öâ, WfVçBÂ —FVÒ ’ ™½var nested,
focused;Ðthis.blur(event, event && event.type === "focus")™Ð
this._scrollIntoView(item);Ðthis.active = item.first();™Ðocused =
this.active.children("a").addClass("ui-state-focus");Ð// Only update aria-
activedescendant if there's a roleÐ// otherwise we assume focus is managed
elsewhereÐif (this.options.role) {™ÐF†–2æVÆVÖVçBæ GG", & &– Ð
activedescendant", focused.attr("id"));™™Ð// Highlight active parent menu
item, if anyÐthis.activeÐÇ &VçB™‘æ6Æ÷6W7B, "çV’ÖÖVçRÖ—FVÒ" •
™’æ6†–ÆG&Vâ, & ¦f–'7B"™‘æ FD6Æ 72, 'V’×7F FRÖ 7F—fR" Ð½f (event && event.type
=== "keydown") {Ð—F†–2åö6Æ÷6R,™½ else {™ÐF†–2çF–ÖW" Ò F†–2åöFVÆ ’†gVæ7F–öâ,’™™½
this._close();Ð—ÒÂ F†–2æFVÆ ’ ™™½Ðested = item.children(".ui-menu");™Ðif
(nested.length && event && (/^mouse/.test(event.type))) {Ð•
this._startOpening(nested);Ð}™™Ðhis.activeMenu = item.parent()™Ð
this._trigger("focus", event, { item: item });ÐÒÉ÷67&öÆÄ–çFõf–Ws¢
function(item) {Ðvar borderTop, paddingTop, offset, scroll, elementHeight,
itemHeight;Ðif (this._hasScroll()) {™Ð&÷&FW%F÷ Ò
parseFloat($.css(this.activeMenu[0], "borderTopWidth")) || 0;Ð— FF–æuF÷ Ò
parseFloat($.css(this.activeMenu[0], "paddingTop")) || 0;Ð–öfg6WB Ò
item.offset().top - this.activeMenu.offset().top - borderTop - paddingTop;Ð•
scroll = this.activeMenu.scrollTop();Ð–VÆVÖVçD†V–v‡B Ò F†–2æ 7F—fTÖVçRæ†V–v‡B,™½
itemHeight = item.height();Ð––b , öfg6WB Â ’™™½
this.activeMenu.scrollTop(scroll + offset);Ð—Ò VÇ6R –b , öfg6WB ² —FVÔ†V–v‡B
> elementHeight) {Ð™this.activeMenu.scrollTop(scroll + offset - elementHeight
+ itemHeight);Ð™}™ÐÉ&ÇW#¢ gVæ7F–öâ, WfVçBÂ g&öÔfö7W2 ’ ™½if (!fromFocus) {™Ð
clearTimeout(this.timer);™™Ðif (!this.active) {™Ð&WGW&a™™Ð
this.active.children("a").removeClass("ui-state-focus");Ðthis.active =
null;Ðthis._trigger("blur", event, { item: this.active });ÐÉ÷7F 'D÷ Væ–æs¢
function(submenu) {™ÐclearTimeout(this.timer)™™Ð// Don't open if already open
fixes a Firefox bug that caused a .5 pixelÐ// shift in the submenu position
when mousing over the carat iconÐif (submenu.attr("aria-hidden") !==
"true") {Ð—&WGW&a™™Ðhis.timer = this._delay(function() {™ÐF†–2åö6Æ÷6R,™½
this._open(submenu);Ð}, this.delay);ÐÉö÷ Vã¢ gVæ7F–öâ, 7V&ÖVçR ’ ™½var
position = $.extend({Ð–öc¢ F†–2æ 7F—f™}, this.options.position)™Ð
clearTimeout(this.timer);Ðthis.element.find(".ui-
menu").not(submenu.parents(".ui-menu"))™’æ†–FR™‘æ GG", & &– Ö†–FFVâ"Â
"true");Ðsubmenu™Ðç6†÷r™‘ç&VÖ÷fT GG", & &– Ö†–FFVâ"™‘æ GG", & &– ÖW‡ æFVB"Â
"true")™’ç ÷6—F–öâ, ÷6—F–öâ —™™ÐÉ6öÆÆ 6T ÆÃ¢ gVæ7F–öâ, WfVçBÂ ÆÂ ’ ™½
clearTimeout(this.timer);Ðthis.timer = this._delay(function() {™Ðòò –b vR vW&R
passed an event, look for the submenu that contains the event™Ð—f " 7W'&VçDÖVçR
= all ? this.element :™™$(event &&
event.target).closest(this.element.find(".ui-menu"));™’òò –b vR f÷VæB æò
valid submenu ancestor, use the main menu to close all sub menus anywayÐ––b ,
currentMenu.length) {™™currentMenu = this.element™™™

™—F†—2åöFVÆ ’†gVæ7F–öâ,’™™½
this.focus(event, newItem);™—Ò™½ÒÉæW‡C¢ gVæ7F–öâ, WfVçB ’ ™½
this._move("next", "first", event);ÐÒÉ &Wf–÷W3¢ gVæ7F–öâ, WfVçB ’ ™½
this._move("prev", "last", event);ÐÒÉ—4f—'7D—FVÓ¢ gVæ7F–öâ,’ ™½return
this.active && !this.active.prevAll(".ui-menu-item").length;ÐÒÉ—4Æ 7D—FVÓ¢
function() {™return this.active && !this.active.nextAll(".ui-menu-
item").length;ÐÒÉöÖ÷fS¢ gVæ7F–öâ, F—&V7F–öâÂ f–ÇFW"Â WfVçB ’ ™½var next™™Ðif
(this.active) {™––b , F—&V7F–öâ ÓÓÒ &f—'7B" ÇÂ F—&V7F–öâ ÓÓÒ &Æ 7B" ’™½next =
this.active™™•² F—&V7F–öâ ÓÓÒ &f—'7B" ò ' &Wd ÆÂ" ¢ &æW‡D ÆÂ" Ò, "çV’ÖÖVçRÐ
item")™™’æW , Ó ™™—Ò VÇ6R™™½next = this.active™™Ð² F—&V7F–öâ ² $ ÆÂ" Ò, "çV’ÖÖVçRÐ
item")™™’æW , ™™™½™™Ðif (!next || !next.length || !this.active) {™™ÐæW‡B Ò
this.activeMenu.children(".ui-menu-item")[filter]();™™™™Ðthis.focus(event,
next);ÐÒÉæW‡E vS¢ gVæ7F–öâ, WfVçB ’ ™½var item, base, height™™Ðif (!
this.active) {™—F†—2ææW‡B, WfVçB ™™½&WGW&â™™½™™Ðif (this.isLastItem()) {™™Ð&WGW&â™™½™™Ð
if (this._hasScroll()) {™—& 6R Ò F†—2æ 7F—fRæöfg6WB,’çF÷™½†V–v‡B Ò
this.element.height();™—F†—2æ 7F—fRææW‡D ÆÂ, "çV’ÖÖVçRÖ—FVÒ" ’æV 6,†gVæ7F–öâ,’™™½
item = $(this);™™™return item.offset().top - base - height < ™™—÷™™™½
this.focus(event, item);™™} else {™™ÐF†—2æfö7W2, WfVçBÂ
this.activeMenu.children(".ui-menu-item")™™™[!this.active ? "first" : "last"]
());™™}ÐÒÉ &Wf–÷W5 vS¢ gVæ7F–öâ, WfVçB ’ ™½var item, base, height™™Ðif (!
this.active) {™—F†—2ææW‡B, WfVçB ™™½&WGW&â™™½™™Ðif (this.isFirstItem()) {™™Ð&WGW&â™™½™™Ð
if (this._hasScroll()) {™—& 6R Ò F†—2æ 7F—fRæöfg6WB,’çF÷™½†V–v‡B Ò
this.element.height();™—F†—2æ 7F—fRç &Wd ÆÂ, "çV’ÖÖVçRÖ—FVÒ" ’æV 6,†gVæ7F–öâ,’™™½
item = $(this);™™™return item.offset().top - base + height > ™™—÷™™™½
this.focus(event, item);™™} else {™™ÐF†—2æfö7W2, WfVçBÂ
this.activeMenu.children(".ui-menu-item").first());™™}ÐÒÉö† 567&öÆÃ¢
function() {™™return this.element.outerHeight() <
this.element.prop("scrollHeight");ÐÒÉ6VÆV7C¢ gVæ7F–öâ, WfVçB ’ ™½// TODO: It
should never be possible to not have an active item at this™™// point, but the
tests don't trigger mouseenter before click.™™this.active = this.active ||
$(event.target).closest(".ui-menu-item");™™var ui = { item: this.active };™™Ð
if (!this.active.has(".ui-menu").length) {™™—F†—2æ6öÆÆ 6T ÆÂ, WfVçBÂ G'VR “½
™™}™™Ðthis._trigger("select", event, ui);™™™™);™™Ð(jQuery));™™Ðfunction($,
undefined) {™™Ð.ui = $.ui || {};™™Ðvar cachedScrollbarWidth,™™ÐÖ , Ò Ö F,æÖ ,™™É '2 Ò
Math.abs,™™Ð&÷VæB Ò Ö F,ç&÷VæB™™É&†÷&—¦öçF Â Ò öÆVgGÆ6VçFW'Ç&–v‡BÒ™™É'fW'F–6 Â Ò ð
top|center|bottom/,™™Ð&öfg6WB Ò õµÂµÂÕÕÆB²…ÂåµÆEÒ²“ÒSÒò™™É' ÷6—F–öâ Ò õåÇr²ò™™É
rpercent = /%$/,™™Ð÷ ÷6—F–öâ Ò Bæfâç ÷6—F–öã™™Ðfunction getOffsets(offsets,
width, height) {™™Ð&WGW&â ™™½parseFloat(offsets[0]) *
(rpercent.test(offsets[0]) ? width / 100 : 1),™™™™Ð
parseFloat(offsets[1]) * (rpercent.test(offsets[1]) ? height / 100 :
1)™™ÐÓ½™™Ðfunction parseCss(element, property) {™™Ð&WGW&â
parseInt($.css(element, property), 10) || 0;™™™™Ðfunction
getDimensions(elem) {™™Ðif " & r Ò VÆVÕ³ Ó½–b , & rææöFUG— R ÓÓÒ ’ ’ ™™½return ™™™™Ð
width: elem.width(),™™™™Ð–†V–v‡C¢ VÆVÒæ†V–v‡B,™™™™É™™™™öfg6WC¢ ² F÷ ¢ Â ÆVgC¢ ™™™™É™™™™–b
($.isWindow(raw)) {™™™™Ðreturn ™™™™Ðv–GFƒ¢ VÆVÒçv–GF,,™™™™É™™™™V–v‡C¢ VÆVÒæ†V–v‡B,™™™™É
offset: { top: elem.scrollTop(), left: elem.scrollLeft() }™™™™}™™™™É–b
(raw.preventDefault) {™™™™Ðreturn ™™™™Ðv–GFƒ¢ ™™™™É™™™™V–v‡C¢ ™™™™É™™™™öfg6WC¢ ² F÷ ¢ & rç vU’Â
left: raw.pageX }™™™™Ð}™™™™É™™™™É&WGW&â ™™™™½width: elem.outerWidth(),™™™™Ðeight:
elem.outerHeight(),™™™™Ðoffset: elem.offset(™™™™)™™™™Ó½™™™™Ð.position = {™™™™Ð67&öÆÆ& %v–GFƒ¢
function() {™™™™Ðif (cachedScrollbarWidth !== undefined) {™™™™Ð&WGW&â
cachedScrollbarWidth;™™™™Ð}™™™™Ðvar w1, w2,™™™™ÐF—b Ò B, #ÆF—b 7G–ÆSÒvF—7 Æ “¦&Æö6³· ÷6—F–öã
absolute;width:50px;height:50px;overflow:hidden;'><div
style='height:100px;width:auto;'> "),™™™™É––ææW$F—b Ò F—bæ6†–ÆG&Vâ,•³ ™™™™É½
$("body").append(div);™™™™Ðw1 = innerDiv.offsetWidth;™™™™Ðdiv.css("overflow",
"scroll");™™™™Ðw2 = innerDiv.offsetWidth;™™™™Ðif (w1 === w2) {™™™™Ðs" Ò
div[0].clientWidth;™™™™Ð™™™™Ðdiv.remove();™™™™Ðreturn (cachedScrollbarWidth = w1 - w2);™™™™ÐÍ
getScrollInfo: function(within) {™™™™Ðvar overflowX = within.isWindow ||
within.isDocument ? "" :™™™™Ðwithin.element.css("overflow-x");™™™™ÐfW&fÆ÷u’ Ò
within.isWindow || within.isDocument ? "" :™™™™Ðwithin.element.css("overflow-y");™™™™Ð
hasOverflowX = overflowX === "scroll" ||™™™™Ð

™™(overflowX === "auto" &&
within.width < within.element[0].scrollWidth),™–† 4÷fW&fÆ÷u’ Ò ÷fW&fÆ÷u’ ÓÓÒ
"scroll" ||™(overflowY === "auto" && within.height <
within.element[0].scrollHeight);™return {™v–GFƒ¢ † 4÷fW&fÆ÷u’ ò
$.position.scrollbarWidth() : 0,™–†V–v‡C¢ † 4÷fW&fÆ÷u, ò
$.position.scrollbarWidth() : 0™}™;™ívWEv—F†–ä–æfó¢ gVæ7F–öâ, VÆVÖVçB ’ ™var
withinElement = $(element || window),™––5v–æF÷r Ò
$.isWindow(withinElement[0]),™––4Fö7VÖVçB Ò v—F†–äVÆVÖVçE² Ò bb
withinElement[0].nodeType === 9;™return {™VÆVÖVçC¢ v—F†–äVÆVÖVçB™í—5v–æF÷s¢
isWindow,™––4Fö7VÖVçC¢ —4Fö7VÖVçB™íöfg6WC¢ v—F†–äVÆVÖVçBæöfg6WB,’ ÇÂ ² ÆVgC¢ Â
top: 0 },™—67&öÆÄÆVgC¢ v—F†–äVÆVÖVçBç67&öÆÄÆVgB,™í67&öÆÅF÷ ¢
withinElement.scrollTop(),™–v–GFƒ¢ —5v–æF÷r ò v—F†–äVÆVÖVçBçv–GF,,’ ¢
withinElement.outerWidth(),™–†V–v‡C¢ —5v–æF÷r ò v—F†–äVÆVÖVçBæ†V–v‡B,’ ¢
withinElement.outerHeight()™}™;™;™.fn.position = function(options) {™–b ,
options || !options.of) {™return _position.apply(this, arguments);™;™òò Ó ¶R
a copy, we don't want to modify arguments™÷ F–öç2 Ò BæW‡FVæB, ·ÒÂ ÷ F–öç2 “™
var atOffset, targetWidth, targetHeight, targetOffset, basePosition,
dimensions,™target = $(options.of),™within =
$.position.getWithinInfo(options.within),™scrollInfo =
$.position.getScrollInfo(within),™collision = (options.collision ||
"flip").split(" "),™offsets = {}™;™–ÖVç6–öç2 Ò vWDF–ÖVç6–öç2, F &vWB “½–b
(target[0].preventDefault) {™// force left top to allow flipping™options.at =
"left top";™ÝF &vWEv–GF, Ò F–ÖVç6–öç2çv–GFƒ½F &vWD†V–v‡B Ò F–ÖVç6–öç2æ†V–v‡C½
targetOffset = dimensions.offset;™òò 6ÆöæR Fò &WW6R ÷&–v–æ Â F &vWDöfg6WB Æ FW•
basePosition = $.extend({}, targetOffset);™òò f÷&6R ×’ æB B Fò † fR f Æ–B
horizontal and vertical positions™òò –b f ÇVR —2 Ö—76–ær ÷" –çf Æ–BÂ —B v–ÆÂ
be converted to center™BæV 6,, ² &×’"Â & B" ÒÂ gVæ7F–öâ,’ ™var pos =
(options[this] || "").split(" "),™–†÷&—¦öçF Äöfg6WB™ífW'F–6 Äöfg6WD™½f
(pos.length === 1) {™— ÷2 Ò &†÷&—¦öçF ÂçFW7B, ÷5² Ò ’™™Ý
pos.concat(["center"]) :™™rvertical.test(pos[0])™?™
["center"].concat(pos) :™™•² &6VçFW""Â &6VçFW""™™pos[0] =
rhorizontal.test(pos[0]) ? pos[0] : "center";™pos[1] =
rvertical.test(pos[1]) ? pos[1] : "center";™// calculate offset™
horizontalOffset = roffset.exec(pos[0]);™verticalOffset =
roffset.exec(pos[1]);™offsets[this] = [™†÷&—¦öçF Äöfg6WB ò
horizontalOffset[0] : 0,™—fW'F–6 Äöfg6WB ò fW'F–6 Äöfg6WE² Ò ¢™]™™/ reduce
to just the positions without the offsets™options[this] = [™
rposition.exec(pos[0])[0],™—' ÷6—F–öâæW†V2, ÷5² Ò •² ™™;™“™òò
normalize collision option™–b , 6öÆÆ—6–öâæÆVæwF, ÓÓÒ ’ ™collision[1] =
collision[0];™™–b , ÷ F–öç2æ E² Ò ÓÓÒ '&–v‡B" ’ ™basePosition.left +=
targetWidth;™Ò VÇ6R –b , ÷ F–öç2æ E² Ò ÓÓÒ &6VçFW"" ’ ™basePosition.left +=
targetWidth / 2;™™–b , ÷ F–öç2æ E² Ò ÓÓÒ &&÷GFöÒ" ’ ™basePosition.top +=
targetHeight;™Ò VÇ6R –b , ÷ F–öç2æ E² Ò ÓÓÒ &6VçFW"" ’ ™basePosition.top +=
targetHeight / 2;™™ Döfg6WB Ò vWDöfg6WG2, öfg6WG2æ BÂ F &vWEv–GF,Â
targetHeight);™& 6U ÷6—F–öâæÆVgB ³Ò Döfg6WE² Ó½& 6U ÷6—F–öâçF÷ ³Ò
atOffset[1];™&WGW&â F†—2æV 6,†gVæ7F–öâ,’ ™var collisionPosition, using,™VÆVÒ
= $(this),™–VÆVÕv–GF, Ò VÆVÒæ÷WFW%v–GF,,™íVÆVÔ†V–v‡B Ò VÆVÒæ÷WFW$†V–v‡B,™í
marginLeft = parseCss(this, "marginLeft"),™–Ö &v–åF÷ Ò '6T772, F†—2Â
"marginTop"),™–6öÆÆ—6–öåv–GF, Ò VÆVÕv–GF, ² Ö &v–äÆVgB ² '6T772, F†—2Â
"marginRight") + scrollInfo.width,™–6öÆÆ—6–öä†V–v‡B Ò VÆVÔ†V–v‡B ² Ö &v–åF÷ ²
parseCss(this, "marginBottom") + scrollInfo.height,™— ÷6—F–öâ Ò BæW‡FVæB, ·ÒÂ
basePosition),™–×”öfg6WB Ò vWDöfg6WG2, öfg6WG2æ×’Â VÆVÒæ÷WFW%v–GF,,’Â
elem.outerHeight());™if (options.my[0] === "right") {™ ÷6—F–öâæÆVgB ÓÒ
elemWidth;™} else if (options.my[0] === "center") {™ ÷6—F–öâæÆVgB ÓÒ
elemWidth / 2;™™™if (options.my[1] === "bottom") {™ ÷6—F–öâçF÷ ÓÒ
elemHeight;™} else if (options.my[1] === "center") {™ ÷6—F–öâçF÷ ÓÒ
elemHeight / 2;™™™position.left += myOffset[0];™position.top += myOffset[1];™™
™// if the browser doesn't support fractions, then round for consistent results™
if (!$.support.offsetFractions) {™— ÷6—F–öâæÆVgB Ò &÷VæB, ÷6—F–öâæÆVgB ™½
position.top = round(position.top);™

™ÐÐollisionPosition = {™ÐÖ &v–äÆVgC¢
marginLeft,™Ð–Ö &v–åF÷ ¢ Ö &v–åF™}™ÐÐ.each(["left", "top"], function(i,
dir) {™Ð––b , BçV’ç ÷6—F–öå² 6öÆÆ—6–öå² ’ Ò Ò ’™½$.ui.position[collision[i]]
[dir](position, {™Ð™—F &vWEv–GFƒ¢ F &vWEv–GF™,íF &vWD†V–v‡C¢ F &vWD†V–v‡™BÍ
elemWidth: elemWidth,™Ð™–VÆVÔ†V–v‡C¢ VÆVÔ†V–v‡™BÍ6öÆÆ—6–öå ÷6—F–öã¢
collisionPosition,™Ð™–6öÆÆ—6–öåv–GFƒ¢ 6öÆÆ—6–öåv–GF™,í6öÆÆ—6–öä†V–v‡C¢
collisionHeight,™Ð™–öfg6WC¢ ² Döfg6WE² Ò ² ×”öfg6WE² ÒÂ Döfg6WB ² Ò ²
myOffset[1]],™Ð™–×“¢ ÷ F–öç2æ™™Í C¢ ÷ F–öç2æ™™BÍv—F†–ã¢ v—F†™ãíVÆVÒ ¢ VÆVÝ™÷™Ð
™})™ÐÐf (options.using) {™ÐòÒ FG2 fVVF& 6² 2 6V6öæB &wVÖVçB Fò W6–ær
callback, if present™Ð—W6–ær Ò gVæ7F–öâ, &÷ 2 ’™½var left = targetOffset.left -
position.left,™Ð™—&–v‡B Ò ÆVgB ² F &vWEv–GF, Ò VÆVÕv–GF™,íF÷ Ò F &vWDöfg6WBçF÷ Ò
position.top,™Ð™–&÷GFöÒ Ò F÷ ² F &vWD†V–v‡B Ò VÆVÔ†V–v‡™BÍfVVF& 6² Ò™½target: {™Ð
element: target,™Ð™™–ÆVgC¢ F &vWDöfg6WBæÆVgBÍF÷ ¢ F &vWDöfg6WBçF™÷™™Ív–GFƒ¢
targetWidth,™Ð™™–†V–v‡C¢ F &vWD†V™™v‡™™™,™Ðlement: {™ÐVÆVÖVçC¢ VÆVÖÍÆVgC¢ ÷6—F–öâæÆVgBÍ
top: position.top,™Ð™™—v–GFƒ¢ VÆVÕv–GF™,í†V–v‡C¢ VÆVÔ†V™™v‡™™™,™Ðorizontal: right <
0 ? "left" : left > 0 ? "right" : "center",™Ð™™vertical: bottom < 0 ? "top" : top
> 0 ? "bottom" : "middle"™Ð™™™Ó½f (targetWidth < elemWidth && abs(left +
right) < targetWidth) {™Ð™–fVVF& 6²æ†÷&—¦öçF Â Ò &6VçFW™#½™Ðf (targetHeight <
elemHeight && abs(top + bottom) < targetHeight) {™Ð™–fVVF& 6²çfW'F–6 Â Ò
"middle";™Ð™™}™Ðf (max(abs(left), abs(right)) > max(abs(top),
abs(bottom))) {™Ð™–fVVF& 6²æ–× ÷'F çB Ò &†÷&—¦öçF Â™#½ else™™Ð
feedback.important = "vertical";™Ð™™}™Ðptions.using.call(this, props, feedback);™Ð
™—Ó½™™™Ðlem.offset($.extend(position, { using: using }))™™÷Ò“½;™Ð.ui.position =
{™Ðf—C¢ ½™™™left: function(position, data) {™Ðf " v—F†–â Ò F F çv—F†–ãÍ™™™
withinOffset = within.isWindow ? within.scrollLeft : within.offset.left,™Ð™™
outerWidth = within.width,™Ð™™collisionPosLeft = position.left -
data.collisionPosition.marginLeft,™Ð™™overLeft = withinOffset - collisionPosLeft,™Ð
overRight = collisionPosLeft + data.collisionWidth - outerWidth -
withinOffset,™Ð™™newOverRight™™;™™™Ðòò VÆVÖVçB —2 v–FW" F† â v—F†™í–b
(data.collisionWidth > outerWidth) {™Ð™™// element is initially over the left
side of within™Ð™™if (overLeft > 0 && overRight <= 0) {™Ð™™æWt÷fW%&–v‡B Ò
position.left + overLeft + data.collisionWidth - outerWidth - withinOffset;™Ð™•
position.left += overLeft - newOverRight;™Ð™™// element is initially over right
side of within™Ð™™} else if (overRight > 0 && overLeft <= 0) {™Ð™™÷6—F–öâæÆVgB Ò
withinOffset;™Ð™™// element is initially over both left and right sides of within™Ð
™™™} else™™™{™Ð™™–b , ÷fW$ÆVgB â ÷fW%&–v‡B ™™™½position.left = withinOffset +
outerWidth - data.collisionWidth;™Ð™™—Ò VÇ6R™™™½position.left = withinOffset;™™™

™–f " v–F†–â Ò F F çv–F†–âÍwithinOffset =
within.offset.left + within.scrollLeft,Ð™outerWidth = within.width™,ÐoffsetLeft =
within.isWindow ? within.scrollLeft : within.offset.left,Ð™collisionPosLeft =
position.left - data.collisionPosition.marginLeft,Ð™overLeft = collisionPosLeft
- offsetLeft,Ð™overRight = collisionPosLeft + data.collisionWidth - outerWidth
- offsetLeft,Ð™myOffset = data.my[0] === "left"™ÐÒÖF F æVÆVÕv–GF™•
data.my[0] === "right" ?Ð™™™data.elemWidth :ÐaÐOffset = data.at[0] ===
"left" ?Ð™–F F çF &vWEv–GF™–F F æ E² Ò ÓÓÒ '&–v‡B ™Ý-data.targetWidth™™™,Ð
offset = -2 * data.offset[0],Ð™newOverRight™™,ÐnewOverLeftÐ™÷Ðb , ÷fW$ÆVgB Â ’™½
newOverRight = position.left + myOffset + atOffset + offset +
data.collisionWidth - outerWidth - withinOffset;Ð™if (newOverRight < 0 ||
newOverRight < abs(overLeft)) {Ð™— ÷6–F–öâæÆVgB ³Ò ×”öfg6WB ² Döfg6WB ²
offset;Ð™™ÐÝVÇ6R –b , ÷fW%&–v‡B â ’™½newOverLeft = position.left -
data.collisionPosition.marginLeft + myOffset + atOffset + offset - offsetLeft;Ð™
if (newOverLeft > 0 || abs(newOverLeft) < overRight) {Ð™— ÷6–F–öâæÆVgB ³Ò
myOffset + atOffset + offset;Ð™™™ÝÐ,Ðop: function(position, data) {Ðf " v–F†–â
= data.within,Ð™withinOffset = within.offset.top + within.scrollTop™,ÐouterHeight
= within.height,Ð™offsetTop = within.isWindow ? within.scrollTop :
within.offset.top,Ð™collisionPosTop = position.top -
data.collisionPosition.marginTop,Ð™overTop = collisionPosTop - offsetTop™,Ð
overBottom = collisionPosTop + data.collisionHeight - outerHeight - offsetTop,Ð™
top = data.my[1] === "top",Ð™myOffset = top™™™ÐÒÖF F æVÆVÔ†V–v‡B™–F F æ×•² Ò
=== "bottom" ?Ð™™™™data.elemHeight :ÐaÐOffset = data.at[1] === "top"™™™ÐÐ
data.targetHeight :Ð™–F F æ E² Ò ÓÓÒ &&÷GFöÒ™™™™Ý-data.targetHeight™™™™,Ðoffset =
-2 * data.offset[1],Ð™newOverTop™™™,ÐnewOverBottom™™™÷Ðb , ÷fW%F÷ Â ’™½
newOverBottom = position.top + myOffset + atOffset + offset +
data.collisionHeight - outerHeight - withinOffset;Ð™if ((position.top +
myOffset + atOffset + offset) > overTop && (newOverBottom < 0 ||
newOverBottom < abs(overTop))) {Ð™— ÷6–F–öâçF÷ ³Ò ×”öfg6WB ² Döfg6WB ²
offset;Ð™™ÐÝVÇ6R –b , ÷fW$&÷GFöÒ â ’™½newOverTop = position.top -
data.collisionPosition.marginTop + myOffset + atOffset + offset - offsetTop;Ð™
if ((position.top + myOffset + atOffset + offset) > overBottom &&
(newOverTop > 0 || abs(newOverTop) < overBottom)) {Ð™— ÷6–F–öâçF÷ ³Ò
myOffset + atOffset + offset;Ð™™™ÝÐÍfÆ– f–C¢ ™½left: function() {Ð™Ð
$.ui.position.flip.left.apply(this, arguments);Ð™•
$.ui.position.fit.left.apply(this, arguments);Ð},Ð™Ðop: function() {Ð™Ð
$.ui.position.flip.top.apply(this, arguments);Ð™•
$.ui.position.fit.top.apply(this, arguments);Ð™™™ÝÐ;Ð/ fraction support testÐ
(function () {Ðf " FW7DVÆVÖVçBÂ FW7DVÆVÖVçE &VçBÂ FW7DVÆVÖVçE7G–ÆRÂ
offsetLeft, i,Ðbody = document.getElementsByTagName("body")[0],™™Ðdiv =
document.createElement("div");ÐÒòô7&V FR &f ¶R &öG’" f÷" FW7F–ær & 6VB öâ
method used in jQuery.supportÐFW7DVÆVÖVçB Ò Fö7VÖVçBæ7&V FTVÆVÖVçB, &öG’ ò
"div" : "body");ÐFW7DVÆVÖVçE7G–ÆR Ò ™½visibility: "hidden",™Ðwidth: 0,™Ðheight: 0,™Ð
border: 0,Ðmargin: 0,™Ðbackground: "none"™Ð½–b , &öG’ ’ ™½
$.extend(testElementStyle, {Ð™— ÷6–F–öã¢ & '6öÇWFR™™ÍÆVgC¢ "Ó ,™™ÍF÷ ¢
"-1000px"™Ð});™™Ðf÷" , ’ –â FW7DVÆVÖVçE7G–ÆR ’ ™½testElement.style[i] =
testElementStyle[i];ÐÝFW7DVÆVÖVçBæ VæD6†–ÆB, F–b “½FW7DVÆVÖVçE &VçB Ò
body || document.documentElement;ÐFW7DVÆVÖVçE &VçBæ–ç6W'D&Vf÷&R, FW7DVÆVÖVçBÂ
testElementParent.firstChild);ÐF–bç7G–ÆRæ775FW‡B Ò ' ÷6–F–öã¢ '6öÇWFS² ÆVgC¢
10.7432222px;";™™Ðöfg6WDÆVgB Ò B, F–b ’æöfg6WB,’æÆVgC½Bç7W ÷'Bæöfg6WDg& 7F–öç2
= offsetLeft > 10 && offsetLeft < 11;ÐFW7DVÆVÖVçBæ–ææW$…DÔÂ Ò "#½
testElementParent.removeChild(testElement);™™™)();™™(jQuery));™™™(function($,
undefined) {™™™™

™’æ VæEFò, F†–2æVÆVÖVçB ™½this._refreshValue();ÒÓöFW7G&÷“¢ gVæ7F–öâ,’ ™
this.elementÐ’ç&VÖ÷fT6Æ 72, 'V’× &öw&W76& " V’×v–FvWB V’×v–FvWBÖ6öçFVçB V’Ð
corner-all")Ð’ç&VÖ÷fT GG", '&öÆR"™‘ç&VÖ÷fT GG", & &– ×f ÇVVÖ–â" •
™’ç&VÖ÷fT GG", & &– ×f ÇVVÖ ,"™‘ç&VÖ÷fT GG", & &– ×f ÇVVæ÷r" ™½
this.valueDiv.remove();ÒÒÓf ÇVS¢ gVæ7F–öâ, æWuf ÇVR ’ ™½if (newValue ===
undefined) {Ð–&WGW&â F†–2æ÷ F–öç2çf ÇVS¢Ð this.options.value =
this._constrainedValue(newValue);Ðthis._refreshValue();ÒÓö6öç7G& –æVEf ÇVS¢
function(newValue) {Ðif (newValue === undefined) {ÐæWuf ÇVR Ò
this.options.value;ÐÐthis.indeterminate = newValue === false;Ð// sanitize valueÐ
if (typeof newValue !== "number") {Ð–æWuf ÇVR Ò ™ÐÐreturn
this.indeterminate ? false :Ð”Ö F,æÖ–â, F†–2æ÷ F–öç2æÖ ,Â Ö F,æÖ ,, F†–2æÖ–âÂ
newValue));ÒÓÓ÷6WD÷ F–öç3¢ gVæ7F–öâ, ÷ F–öç2 ’ ™½// Ensure "value" option is
set after other values (like max)Ðvar value = options.value;Ðdelete
options.value;Ðthis._super(options);ÐÐthis.options.value =
this._constrainedValue(value);Ðthis._refreshValue();ÒÓ÷6WD÷ F–öã¢
function(key, value) {Ðif (key === "max") {ÐÒòò FöâwB ÆÆ÷r Ö , ÆW72 F† â
minÐ–f ÇVR Ò Ö F,æÖ ,, F†–2æÖ–âÂ f ÇVR ™ÐÐthis._super(key, value);ÒÓ
_percentage: function() {Ðreturn this.indeterminate ? 100 : 100 *
(this.options.value - this.min) / (this.options.max - this.min);ÒÒÓ
_refreshValue: function() {Ðvar value = this.options.value;Ð W&6VçF vR Ò
this._percentage();Ðthis.valueDivÐçFövvÆR, F†–2æ–æFWFW&Ö–æ FR ÇÂ f ÇVR â
this.min)Ð’çFövvÆT6Æ 72, 'V’Ö6÷&æW"×&–v‡B"Â f ÇVR ÓÓÒ F†–2æ÷ F–öç2æÖ , •
™’çv–GF,, W&6VçF vRçFôf–†VBƒ ’ ² "R" Ð™½this.element.toggleClass("ui-
progressbar-indeterminate", this.indeterminate);Ðif (this.indeterminate) {Ð
this.element.removeAttr("aria-valuenow");Ð––b , F†–2æ÷fW&Æ ”F–b ’™½
this.overlayDiv = $(" </
div>").appendTo(this.valueDiv);Ð™‘} else {ÐF†–2æVÆVÖVçBæ GG"‡½"aria-
valuemax": this.options.max,Ð™"aria-valuenow": valueÐ™½–b , F†–2æ÷fW&Æ ”F–b ’™½
this.overlayDiv.remove();Ð™this.overlayDiv = null;ÐÐif (this.oldValue !==
value) {Ð–F†–2æöÆEf ÇVR Ò f ÇVS½F†–2å÷G&–vvW", &6† ævR" ™½Ðif (value ===
this.options.max) {Ð–F†–2å÷G&–vvW", &6ö× ÆWFR" ™½ÐÐ);Ð)(jQuery);Ð
(function($, undefined) {Ð// number of pages in a sliderÐ// (how many times
can you page up/down to go through the whole range)Ðvar numPages = 5;Ð
$.widget("ui.slider", $.ui.mouse, {ÐfW'6–öã¢ # ã ãB"Ív–FvWDWfVçE &Vf–ƒ¢
"slide",Ð÷ F–öç3¢ ™animate: false,Ðdistance: 0,Ðmax: 100,Ðmin: 0,Ðorientation:
"horizontal",Ðrange: false,Ðstep: 1,Ðvalue: 0,Ðvalues: null,ÐÐ// callbacksÐchange:
null,Ðslide: null,Ðstart: null,Ðstop: nullÒÓö7&V FS¢ gVæ7F–öâ,’ ™
this._keySliding = false;Ðthis._mouseSliding = false;Ðthis._animateOff = true;Ð
this._handleIndex = null;Ðthis._detectOrientation();Ðthis._mouseInit();ÐÐ
this.elementÐ’æ FD6Æ 72, 'V’×6Æ–FW""™½" ui-slider-" + this.orientation+Ð ui-
widget" +Ð™" ui-widget-content"™+Ð ui-corner-all"Ð;Ðthis._refresh();Ð
this._setOption("disabled", this.options.disabled);Ðthis._animateOff = false;Ð
–ÒÓ÷&Vg&W6ƒ¢ gVæ7F–öâ,’ ™this._createRange();Ðthis._createHandles();Ð
this._setupEvents();Ðthis._refreshValue();ÒÓö7&V FT† æFÆW3¢ gVæ7F–öâ,’ ™½var i,
handleCount,Ð–÷ F–öç2 Ò F†–2æ÷ F–öçÍW†–7F–æt† æFÆW2 Ò F†–2æVÆVÖVçBæf–æB, "çV’Ð
slider-handle").addClass("ui-state-default ui-corner-all"),Ð–† æFÆR Ò #Æ
class='ui-slider-handle ui-state-default ui-corner-all' href='#'></a>",Ð•
handles = [];ÐhandleCount = (options.values && options.values.length) || 1;ÐÐ
if (existingHandles.length > handleCount) {Ð•
existingHandles.slice(handleCount).remove();Ð–W†–7F–æt† æFÆW2 Ò
existingHandles.slice(0, handleCount);ÐÐfor (i = existingHandles.length; i
< handleCount; i++) {Ð–† æFÆW2ç W6,, † æFÆR ™ÐÐthis.handles =
existingHandles.add($(handles.join("")).appendTo(this.element));Ð
this.handle = this.handles.eq(0);Ðthis.handles.each(function(i) {Ð
$(this).data("ui-slider-handle-index", i);Ð});ÒÓö7&V FU& ævS¢ gVæ7F–öâ,’ ™
var options = this.options,Ð–6Æ 76W2 Ò "Ð½f (options.range) {Ð–b
(options.range === true) {Ð™if (!options.values)™{Ð÷ F–öç2çf ÇVW2 Ò
[this._valueMin(), this._valueMin()];Ð™} else if (options.values.length &&
options.values.length !== 2) {Ð

™™–÷ F–öç2çf ÇVW2 Ò ² ÷ F–öç2çf ÇVW5³ ÒÂ
options.values[0]];Ð™} else if ($.isArray(options.values)){Ð™÷ F–öç2çf ÇVW2
= options.values.slice(0);Ð™Ð™–b , F†–2ç& ævR ÇÂ F†–2ç& ævRæÆVæwF, ’™½
this.range = $(" ")Ð™’æ VæEFò, F†–2æVÆVÖVçBÐ™½classes = "ui-slider-
range" +Ð™// note: the most fittingly semantic framework class for
this element,Ð™// but worked best visually with a variety of themesÐ™ ui-widget-
header ui-corner-all";Ð™Ò VÇ6R™½this.range.removeClass("ui-slider-range-min ui-
slider-range-max")Ð™’òò † æFÆR & ævR 7v–F6†–ær g&öÒ G'VR Fò Ö–âöÐ™‘æ772‡½
™™™"left": "",Ðbottom":™™™ÒÐ™½F†–2ç& ævRæ FD6Æ 72, 6Æ 76W2™½((options.range
=== "min" || options.range === "max") ? " ui-slider-range-" +
options.range : ""));Ð™} else {Ð–b , F†–2ç& ævR ’™½this.range.remove();Ð™
this.range = null;Ð™}ÒÐ™÷6WGW WfVçG3¢ gVæ7F–öâ,’ ™½var elements =
this.handles.add(this.range).filter("a");Ð™this._off(elements);Ð™
this._on(elements, this._handleEvents);Ð™this._hoverable(elements);Ð™
this._focusable(elements);ÐÒÐöFW7G&÷“¢ gVæ7F–öâ,’ ™½this.handles.remove();Ð™if
(this.range) {Ð™–F†–2ç& ævRç&VÖ÷fR,™™Ð™this.elementÐç&VÖ÷fT6Æ 72, 'V’×6Æ–FW""™™½"
ui-slider-horizontal" +Ð™" ui-slider-vertical"™™Ð™ ui-widget"™™Ð™ ui-widget-
content" +Ð™" ui-corner-all");Ð™this._mouseDestroy();ÒÐöÖ÷W6T6 GW&S¢
function(event) {Ð™var position, normValue, distance, closestHandle, index,
allowed, offset, mouseOverHandle,Ð™–F† B Ò F†–2Íò Ò F†–2æ÷ F–öçÐ™½if
(o.disabled) {Ð™–&WGW&â f Ç6S™™Ð™this.elementSize = {Ð™v–GFƒ¢
this.element.outerWidth(),Ð™–†V–v‡C¢ F†–2æVÆVÖVçBæ÷WFW$†V–v‡B™,}™Ð
this.elementOffset = this.element.offset();Ð™position = { x: event.pageX, y:
event.pageY };Ð™normValue = this._normValueFromMouse(position);Ð™distance =
this._valueMax() - this._valueMin() + 1;Ð™this.handles.each(function(i) {Ð™if "
thisDistance = Math.abs(normValue - that.values(i));Ð™––b ,, F–7F æ6R â
thisDistance) ||Ð™(distance === thisDistance &&Ð™†’ ÓÓÒ F† BåöÆ 7D6† ævVEf ÇVR
|| that.values(i) === o.min))) {Ð™distance = thisDistance;Ð™™closestHandle =
$(this);Ð™index = i;™™Ð™allowed = this._start(event, index);Ð™if (allowed
=== false) {Ð™–&WGW&â f Ç6S™™Ð™this._mouseSliding = true;Ð™this._handleIndex =
index;Ð™closestHandleÐæ FD6Æ 72, 'V’×7F FRÖ 7F–fR"™‘æfö7W2,™™offset =
closestHandle.offset();Ð™mouseOverHandle = !
$(event.target).parents().addBack().is(".ui-slider-handle");Ð™
this._clickOffset = mouseOverHandle ? { left: 0, top: 0 } : {Ð™–ÆVgC¢
event.pageX - offset.left - (closestHandle.width() / 2),Ð™–F÷ ¢ WfVçBç vU’ Ò
offset.top -Ð™(closestHandle.height() / 2)™™Ð
(parseInt(closestHandle.css("borderTopWidth"), 10) || 0) -Ð™™
(parseInt(closestHandle.css("borderBottomWidth"), 10) || 0) +Ð™™
(parseInt(closestHandle.css("marginTop"), 10) || 0)Ð™}™™Ð™if (!
this.handles.hasClass("ui-state-hover")) {Ð™–F†–2å÷6Æ–FR, WfVçBÂ –æFW,Â
normValue);Ð™}™™Ð™this._animateOff = true;™™Ð™return true;ÒÐöÖ÷W6U7F 'C¢ gVæ7F–öâ,’ ™½
return true;ÒÐöÖ÷W6TG& s¢ gVæ7F–öâ, WfVçB ’ ™½var position = { x: event.pageX,
y: event.pageY },Ð™–æ÷&Õf ÇVR Ò F†–2åöæ÷&Õf ÇVTg&öÔÖ÷W6R, ÷6–F–öâ Ð™½
this._slide(event, this._handleIndex, normValue);Ð™return false;ÒÐöÖ÷W6U7F÷ ¢
function(event) {Ð™this.handles.removeClass("ui-state-active");Ð™
this._mouseSliding = false;Ð™this._stop(event, this._handleIndex);Ð™
this._change(event, this._handleIndex);Ð™this._handleIndex = null;Ð™
this._clickOffset = null;Ð™this._animateOff = false;™™Ð™return false;ÒÐöÖ
_detectOrientation: function() {Ð™this.orientation = (this.options.orientation
=== "vertical") ? "vertical" : "horizontal";ÒÐöæ÷&Õf ÇVTg&öÔÖ÷W6S¢
function(position) {Ð™var pixelTotal,™™Ð –†VÄÖ÷W6RÍ W&6VçDÖ÷W6RÍf ÇVUF÷F ÂÍ
valueMouse;Ð™if (this.orientation === "horizontal") {™™Ð –†VÅF÷F Â Ò
this.elementSize.width;Ð™– –†VÄÖ÷W6R Ò ÷6–F–öâç, Ò F†–2æVÆVÖVçDöfg6WBæÆVgB Ò
(this._clickOffset ? this._clickOffset.left : 0);Ð™} else {™™Ð –†VÅF÷F Â Ò
this.elementSize.height;Ð™– –†VÄÖ÷W6R Ò ÷6–F–öâç’ Ò F†–2æVÆVÖVçDöfg6WBçF÷ Ò
(this._clickOffset ? this._clickOffset.top : 0);™™™™Ð™percentMouse =
(pixelMouse / pixelTotal);Ð™if (percentMouse > 1) {™™Ð W&6VçDÖ÷W6R Ò ™™™½if
(percentMouse < 0) {™™Ð– W&6VçDÖ÷W6R Ò ™™™½if (this.orientation ===
"vertical") {™™Ð– W&6VçDÖ÷W6R Ò Ò W&6VçDÖ÷W6S™™™Ð™valueTotal = this._valueMax()
- this._valueMin();Ð

™valueMouse = this._valueMin() + percentMouse * valueTotalÐÐ
return this._trimAlignValue(valueMouse);ÐÒÓÐ÷7F 'C¢ gVæ7F–öâ, WfVçBÂ –æFW, ' ™½
var uiHash = {Ð–† æFÆS¢ F†–2æ† æFÆW5² –æFW, ÒÍf ÇVS¢ F†–2çf ÇVR™},™Ðif
(this.options.values && this.options.values.length) {Ð—V”† 6,çf ÇVR Ò
this.values(index);Ð—V”† 6,çf ÇVW2 Ò F†–2çf ÇVW2,™™½Ðeturn
this._trigger("start", event, uiHash);ÐÒÓÐ÷6Æ–FS¢ gVæ7F–öâ, WfVçBÂ –æFW,Â
newVal) {Ðvar otherVal,™ÐæWuf ÇVW2Í ÆÆ÷vVÐ½f (this.options.values &&
this.options.values.length) {Ð–÷F†W%f Â Ò F†–2çf ÇVW2, –æFW, ò ¢ Ð½–b
((this.options.values.length === 2 && this.options.range === true) &&Ð™•
((index === 0 && newVal > otherVal) || (index === 1 && newVal <
otherVal))Ð™)™™{ÐewVal = otherVal™™Ð–b , æWuf Â ÓÒ F†–2çf ÇVW2, –æFW, ' '™™½
newValues = this.values();Ð™newValues[index] = newVal,™Ð/ A slide can be
canceled by returning false from the slide callbackÐ™allowed =
this._trigger("slide", event, {Ð–† æFÆS¢ F†–2æ† æFÆW5² –æFW,™ÒÍf ÇVS¢ æWuf™Âí
values: newValuesÐ™})™™,ÐtherVal = this.values(index ? 0 : 1)™™,Ðif (allowed !==
false) {Ð™—F†–2çf ÇVW2, –æFW,Â æWuf Â™™™½Ð else ™Ð–b , æWuf Â ÓÒ
this.value()) {Ð™// A slide can be canceled by returning false from the slide
callbackÐ™allowed = this._trigger("slide", event,™™Ð† æFÆS¢
this.handles[index],Ð™—f ÇVS¢ æWuf™™™})™™,Ðif (allowed !== false)™™Ð
this.value(newVal);Ð™™™½ÐÒÓÐ÷7F÷ ¢ gVæ7F–öâ, WfVçBÂ –æFW, ' ™½var uiHash = {™Ð
handle: this.handles[index],Ð—f ÇVS¢ F†–2çf ÇVR™},™Ðif (this.options.values
&& this.options.values.length) {Ð—V”† 6,çf ÇVR Ò F†–2çf ÇVW2, –æFW, ™½
uiHash.values = this.values();™™Ðthis._trigger("stop", event, uiHash)÷ÐÒÓÐ
_change: function(event, index) {Ðif (!this._keySliding && !
this._mouseSliding) {Ð—f " V”† 6, Ò™½handle: this.handles[index],™™Ðalue:
this.value()™™Ð—Ó½–b , F†–2æ÷ F–öç2çf ÇVW2 bb F†–2æ÷ F–öç2çf ÇVW2æÆVæwF, '™™½
uiHash.value = this.values(index);Ð™uiHash.values = this.values()™™™™™™Ò÷7F÷&R
the last changed value index for reference when handles overlapÐ™
this._lastChangedValue = index;Ð—F†–2å÷G&–vvW", &6† ævR"Â WfVçBÂ V”† 6, ™™½ÒÓÐ
value: function(newValue) {Ðif (arguments.length) {™™ÐF†–2æ÷ F–öç2çf ÇVR Ò
this._trimAlignValue(newValue);Ð—F†–2å÷&Vg&W6…f ÇVR,™™½F†–2åö6† ævR, çVÆÂÂ ™™½
return;™™™™™™

’òò ÷f ÇVW2, –æFW, ’ &WGW&ç2 6–æv Æ R
value trimmed by min and max, aligned by step Ð÷f ÇVW3¢ gVæ7F–öâ, –æFW, ’ ™½var
val,™–f Ç2™Í™½f (arguments.length) {™Ðf Â Ò F†–2æ÷ F–öç2çf ÇVW5² –æFW, ™½f Â Ò
this._trimAlignValue(val);™–&WGW&â f Â™½ else if (this.options.values &&
this.options.values.length) {™’òò ç6Æ–6R,’ 7&V FW2 6÷ ’ öb F†R '&™‘òò F†–2
copy gets trimmed by min and max and then returned™–f Ç2 Ò
this.options.values.slice();™–f÷" , ’ Ò ² ’ Â f Ç2æÆVæwFƒ² ’³Ò ’™™½vals[i] =
this._trimAlignValue(vals[i]);™™™Ý&WGW&â f Ç3™½ else {™Ð&WGW&â µÓ™½™™Ò
returns the step-aligned value that val is closest to, between (inclusive)
min and max Ð÷G&–Ô Æ–våf ÇVS¢ gVæ7F–öâ, f Â ’ ™½if (val <= this._valueMin()) {™Ð
return this._valueMin();™™™½if (val >= this._valueMax()) {™Ð&WGW&â
this._valueMax();™™™}Ðar step = (this.options.step > 0) ? this.options.step :
1,™–f ÄÖöE7FW Ò ‡f Â Ò F†–2å÷f ÇVTÖ–â,’’ R 7FW™Í Æ–våf ÇVR Ò f Â Ò f ÄÖöE7FW™™½
if (Math.abs(valModStep) * 2 >= step) {™– Æ–våf ÇVR ³Ò , f ÄÖöE7FW â ’ ò
step : (-step);™™™Ð/ Since JavaScript has problems with large floats, round™™Ð/
the final value to 5 digits after the decimal point (see #4124)™™return
parseFloat(alignValue.toFixed(5));™™™Ò™™Ð÷f ÇVTÖ–ã¢ gVæ7F–öâ,’ ™½return
this.options.min;™™™Ò™™Ð÷f ÇVTÖ ƒ¢ gVæ7F–öâ,’ ™½return this.options.max;™™™Ò™™
_refreshValue: function() {™™™var lastValPercent, valPercent, value, valueMin,
valueMax,™–õ& ævR Ò F†–2æ÷ F–öç2& æv™Íò Ò F†–2æ÷ F–öç2™ÍF† B Ò F†–2™Í æ–Ö FR Ò
(!this._animateOff) ? o.animate : false,™™•÷6WB Ò ·™™½f (this.options.values
&& this.options.values.length) {™–F†–2æ† æFÆW2æV 6,†gVæ7F–öâ, ’ ’™½valPercent
= (that.values(i) - that._valueMin()) / (that._valueMax() -
that._valueMin()) * 100;™™™_set[that.orientation === "horizontal" ? "left" :
"bottom"] = valPercent + "%";™™™$(this).stop(1, 1)[animate ? "animate" :
"css"](_set, o.animate);™™™if (that.options.range === true) {™™–b
(that.orientation === "horizontal") {™™™™if (i === 0) {™™™F† Bç& ævRç7F÷ , Â •
[animate ? "animate" : "css"]({ left: valPercent + "%" }, o.animate);™™™™

™™–æWuf Â Ò F†–2å÷f ÇVTÖ–â,™½'&V™%ase $.ui.keyCode.END™:Ð
newVal = this._valueMax();Ð™–'&V™%ase $.ui.keyCode.PAGE_UP™:ÐæWuf Â Ò
this._trimAlignValue(curVal + ((this._valueMax() - this._valueMin()) /
numPages));Ð™–'&V™%ase $.ui.keyCode.PAGE_DOWN™:ÐæWuf Â Ò
this._trimAlignValue(curVal - ((this._valueMax() - this._valueMin()) /
numPages));Ð™–'&V™%ase $.ui.keyCode.UP™:Ðase $.ui.keyCode.RIGHT™:Ð–b , 7W%f Â
=== this._valueMax()) {Ð™™™return™™™ÐæWuf Â Ò F†–2å÷G&–Ô Æ–våf ÇVR, 7W%f Â ²
step);Ð™–'&V™%ase $.ui.keyCode.DOWN™:Ðase $.ui.keyCode.LEFT™:Ð–b , 7W%f Â ÓÓÒ
this._valueMin()) {Ð™™™return™™™ÐæWuf Â Ò F†–2å÷G&–Ô Æ–våf ÇVR, 7W%f Â Ò 7FW ™™½
break;ÐÐ¥F†–2å÷6Æ–FR, WfVçBÂ –æFW,Â æWuf Â ™½™™Ðlick: function(event) {Ð
event.preventDefault();Ð};™™keyup: function(event) {Ðf " –æFW, Ò
$(event.target).data("ui-slider-handle-index");Ð––b , F†–2åö¶W•6Æ–F–ær '™½™
this._keySliding = false;Ð™this._stop(event, index);™™Ðhis._change(event,
index);Ð™$(event.target).removeClass("ui-state-active");™™™™);™™™);Ð(jQuery));Ð
(function($) {™™Ðunction modifier(fn) {™™Ð&WGW&â gVæ7F–öâ,' ™½var previous =
this.element.val();™™Ðfn.apply(this, arguments);™™Ðhis._refresh();™™Ðf (previous !
== this.element.val()) {™™–F†–2å÷G&–vvW", &6† æVR" ™½™™Ð
$.widget("ui.spinner", {™™ÐfW'6–öã¢ # ã ãB"ÍFVf VÇDVÆVÖVçC¢ #Æ–ç WCâ"Í
widgetEventPrefix: "spin",™™Ð÷ F–öç3¢ ™½culture: null,™™Ðcons: {™™ÐF÷vã¢ 'V'Ö–6öâÐ
triangle-1-s",™™Ð–W ¢ 'V'Ö–6öâ×G&– æVÆRÓ Öã},™™Ðncremental: true,™™Ðax: null,™™Ðin:
null,™™ÐnumberFormat: null,™™Ðage: 10,™™Ðtep: 1,™™Ðhange: null,™™Ðpin: null,™™Ðtart: null,™™Ð
stop: null™™ÐÒÓö7&V FS¢ gVæ7F–öâ,' ™½// handle string values that need to be
parsed™™Ðthis._setOption("max", this.options.max);™™Ðhis._setOption("min",
this.options.min);™™Ðthis._setOption("step", this.options.step);™™Ð// Only
format if there is a value, prevents the field from being marked™™Ð// as invalid
in Firefox, see #9573.™™Ðif (this.value() !== "") {™™Ðòò f÷&Ö B F†R f ÇVRÂ 'WB
don't constrain.™™Ð–F†–2å÷f ÇVR, F†–2æVÆVÖVçBçf Â,'Â G'VR ™™½™™Ðhis._draw();™™Ð
this._on(this._events);™™Ðthis._refresh();™™Ð// turning off autocomplete prevents
the browser from remembering the™™Ð// value when navigating through history, so
we re-enable autocomplete™™Ð// if the page is unloaded before the widget is
destroyed. #7790™™Ðthis._on(this.window, {™™Ð&Vf÷&WVæÆö C¢ gVæ7F–öâ,'™™½
this.element.removeAttr("autocomplete");™™Ð–};™™Ð¥övWD7&V FT÷ F–öç3¢ gVæ7F–öâ,'
{™™Ðvar options = {};™™ÐVÆVÖVçB Ò F†–2æVÆVÖVçB™™Ð$.each(["min", "max", "step"],
function(i, option) {™™Ð–f " f ÇVR Ò VÆVÖVçBæ GG", ÷ F–öâ ™½–b , f ÇVR ÓÒ
undefined && value.length) {™™Ðoptions[option] = value;™™™™);™™™™Ðeturn options;™™ÐÒ
_events: {™™Ðkeydown: function(event) {™™Ð–b , F†–2å÷7F 'B, WfVçB ' bb
this._keydown(event)) {™™Ðevent.preventDefault();™™™™,™™Ðeyup: "_stop",™™Ðocus:
function() {™™Ð–F†–2ç &Wf–÷W2 Ò F†–2æVÆVÖVçBçf Â,™™½™™Ðlur: function(event) {™™Ð–b
(this.cancelBlur) {™™Ðdelete this.cancelBlur;™™Ðeturn™™™™ÐF†–2å÷7F÷ ,™™½
this._refresh();™™Ð––b , F†–2ç &Wf–÷W2 ÓÒ F†–2æVÆVÖVçBçf Â,' '™™½
this._trigger("change", event);™™™™

™’òò 6ò vR 6WB fÆ r Fò ¶æ÷r v†Vâ vR 6†÷VÆB –væ÷&R
the blur eventÐ’òò æB 6†V6² † v –â’ –b fö7W2 Ö÷fVB öfb öb F†R –ç WÐ
this.cancelBlur = true;Ð–F†–2åöFVÆ ’†gVæ7F–öâ,’™½delete this.cancelBlur;Ð
checkFocus.call(this);Ð–ÒÐ½–b , F†–2å÷7F 'B, WfVçB ’ ÓÓÒ f Ç6R ’™½return;ÐÐ
this._repeat(null, $(event.currentTarget).hasClass("ui-spinner-up") ?
1 : -1, event);Ð},Ðmouseup .ui-spinner-button": "_stop",Ðmouseenter .ui-
spinner-button": function(event) {Ð’òò 'WGFöâ v–ÆÂ FB V’×7F FRÖ 7F–fR –b
mouse was down while mouseleave and kept downÐ––b ,
$(event.currentTarget).hasClass("ui-state-active")) {Ð™return;ÐÐ–b
(this._start(event) === false) {Ð™return false;ÐF†–2å÷&W V B, çVÆÂÂ
$(event.currentTarget).hasClass("ui-spinner-up") ? 1 : -1, event);Ð},Ð/
TODO: do we really want to consider this a stop?Ð// shouldn't we just stop the
repeater and wait until mouseup beforeÐ// we trigger the stop event?Ð
™"mouseleave .ui-spinner-button": "_stop"–ÐÓöG& s¢ gVæ7F–öâ,’ ½var uiSpinner =
this.uiSpinner = this.elementÐ’æ FD6Æ 72, 'V’×7 –ææW"Ö–ç WB" •
™’æ GG", & WFö6ö× ÆWFR"Â &öfb"™‘çw& , F†–2å÷V•7 –ææW$‡FÖÂ,’™‘ç &VçB,™•// add
buttonsÐ™.append(this._buttonHtml());Ð// this.element.attr("role",
"spinbutton");Ð// button bindingsÐthis.buttons = uiSpinner.find(".ui-spinner-
button")Ð’æ GG", 'F $–æFW,"Â Ó ™‘æ'WGFöâ,™‘ç&VÖ÷fT6Æ 72, 'V’Ö6÷&æW"Ö ÆÂ" Ð½/
IE 6 doesn't understand height: 50% for the buttonsÐ// unless the wrapper has
an explicit heightÐif (this.buttons.height() > Math.ceil(uiSpinner.height()
* 0.5) &&Ð™uiSpinner.height() > 0)™{Ð•7 –ææW"æ†V–v‡B, V•7 –ææW"æ†V–v‡B,’ ™ÐÐ
™// disable spinner if element was already disabledÐif
(this.options.disabled) {Ð–F†–2æF–6 &ÆR,™½ÐÓöö¶W–F÷vã¢ gVæ7F–öâ, WfVçB ’ ½var
options = this.options,Ð–¶W”6öFR Ò BçV’æ¶W”6öFÐswitch (event.keyCode) {Ðcase
keyCode.UP:Ð–F†–2å÷&W V B, çVÆÂÂ Â WfVçB ™½&WGW&â G'VSÐcase keyCode.DOWN:Ð
this._repeat(null, -1, event);Ð–&WGW&â G'VSÐcase keyCode.PAGE_UP:Ð
this._repeat(null, options.page, event);Ð–&WGW&â G'VSÐcase keyCode.PAGE_DOWN:Ð
this._repeat(null, -options.page, event);Ð–&WGW&â G'VSÐÐreturn false;ÐÐ
_uiSpinnerHtml: function() {Ðreturn "<span class='ui-spinner ui-widget ui-
widget-content ui-corner-all'>";ÐÒÓöö'WGFöä‡FÖÃ¢ gVæ7F–öâ,’ ½return "" +Ð
™’#Æ 6Æ 73ÒwV’×7 –ææW"Ö'WGFöâ V’×7 –ææW"×W V’Ö6÷&æW"×G"sâ"™½"<span class='ui-
icon " + this.options.icons.up + "'>▲" +Ð’#Âö â"™½#Æ 6Æ 73ÒwV’Ð
spinner-button ui-spinner-down ui-corner-br'>" +Ð™"<span class='ui-icon " +
this.options.icons.down + "'>▼" +Ð’#Âö â#ÒÓ÷7F 'C¢
function(event) {Ðif (!this.spinning && this._trigger("start", event) ===
false) {Ð–&WGW&â f Ç6SÐÐif (!this.counter) {ÐF†–2æ6÷VçFW" Ò ™ÐÐthis.spinning
= true;Ðreturn true;ÐÓ÷&W V C¢ gVæ7F–öâ, ’Â 7FW 2Â WfVçB ’ ½i = i || 500;ÐÐ
clearTimeout(this.timer);Ðthis.timer = this._delay(function() {Ð
this._repeat(40, steps, event);Ð}, i);ÐÐthis._spin(steps *
this.options.step, event);ÐÒÓ÷7 –ã¢ gVæ7F–öâ, 7FW Â WfVçB ’ ½var value =
this.value() || 0;Ðif (!this.counter) {ÐF†–2æ6÷VçFW" Ò ™ÐÐvalue =
this._adjustValue(value + step * this._increment(this.counter));Ðif (!
this.spinning || this._trigger("spin", event, { value: value }) !== false) {Ð•
this._value(value);Ð–F†–2æ6÷VçFW"²™½ÐÓöö–æ7&VÖVçC¢ gVæ7F–öâ, ’ ’ ½var
incremental = this.options.incremental;Ðif (incremental) {Ð&WGW&â
$.isFunction(incremental) ?Ð™incremental(i)™:ÐMath.floor(i*i*i/50000 -
i*i/500 + 17*i/200 + 1);ÐÐreturn 1;ÐÓ÷ &V6–6–öã¢ gVæ7F–öâ,’ ½var precision =
this._precisionOf(this.options.step);Ðif (this.options.min !== null) {Ð
precision = Math.max(precision, this._precisionOf(this.options.min));Ð}Ð
return precision;ÐÒÓ÷ &V6–6–öäöc¢ gVæ7F–öâ, çVÒ ’ ½var str = num.toString();Ð
decimal = str.indexOf(".");Ðreturn decimal === -1 ? 0 : str.length - decimal
- 1;ÐÒÓö F§W7Ef ÇVS¢ gVæ7F–öâ, f ÇVR ’ ½var base, aboveMin;Ð÷ F–öç2 Ò
this.options;Ð// make sure we're at a valid stepÐ// - find out where we are
relative to the base (min or 0)Ðbase = options.min !== null ? options.min : 0;Ð
aboveMin = value - base;Ð// - round to the nearest stepÐaboveMin =
Math.round(aboveMin / options.step) * options.step;Ð// - rounding is based on
0, so adjust back to our baseÐvalue = base + aboveMin;ÐÐ// fix precision from
bad JS floating point mathÐvalue =
parseFloat(value.toFixed(this._precision()));Ð

™Ð// clamp the valueÐif
(options.max !== null && value > options.max) {™Ð–&WGW&â ÷ F–öç2æÖ ™½Ðif
(options.min !== null && value < options.min) {™Ð–&WGW&â ÷ F–öç2æÖ–â™½Ðreturn
value;ÐÒÓ÷7F÷ ¢ gVæ7F–öâ, WfVçB ’ ™½if (!this.spinning) {™Ð&WGW&â™½Ð
clearTimeout(this.timer);™ÐclearTimeout(this.mousewheelTimer);™Ðthis.counter
= 0;™Ðthis.spinning = false;™Ðthis._trigger("stop", event);÷ÒÓ÷6WD÷ F–öã¢
function(key, value) {™Ðif (key === "culture" || key === "numberFormat") {™Ð
var prevValue = this._parse(this.element.val());™Ð–F†–2æ÷ F–öç5² ¶W’ Ò Ò f ÇVS½
this.element.val(this._format(prevValue));™Ð–&WGW&â™½Ðif (key === "max" ||
key === "min" || key === "step") {™Ð––b , G– Vöb f ÇVR ÓÓÒ '7G&–ær" ’™½value =
this._parse(value);™Ð–}™½Ðif (key === "icons") {™Ð
this.buttons.first().find(".ui-icon")™Ð™.removeClass(this.options.icons.up)Ð
™™.addClass(value.up);™Ð†–2æ'WGFöç2æÆ 7B,’æf–æB, "çV’Ö–6öâ" •
™™.removeClass(this.options.icons.down™™ÐaddClass(value.down)™½Ð
this._super(key, value);™Ðif (key === "disabled") {™Ð–b , f ÇVR ’™½
this.element.prop("disabled", true);™Ðthis.buttons.button("disable");™ÐVÇ6R
{™Ðthis.element.prop("disabled", false);™Ðthis.buttons.button("enable");™½ÐÒÓ
_setOptions: modifier(function(options) {™Ðthis._super(options);™Ð
this._value(this.element.val());ÐÒ’Ó÷ '6S¢ gVæ7F–öâ, f Â ’ ™½if (typeof val
=== "string" && val !== "") {™Ð–f Â Ò v–æF÷räv Æö& Æ–¦R bb
this.options.numberFormat ?™Ð™Globalize.parseFloat(val, 10,
this.options.culture) : +val;™Ð}™½Ðreturn val === "" || isNaN(val) ? null : val;Ð
–ÒÓöf÷&Ö C¢ gVæ7F–öâ, f ÇVR ’ ™½if (value === "") {™Ð&WGW&â "™½Ðreturn
window.Globalize && this.options.numberFormat ?™Ð”vÆö& Æ–¦Ræf÷&Ö B, f ÇVRÂ
this.options.numberFormat, this.options.culture) :™Ð–f ÇVS¢ÒÓ÷&Vg&W6ƒ¢
function() {™Ðthis.element.attr({™Ð& &– ×f ÇVVÖ–â#¢ F†–2æ÷ F–öç2æÖ–â™½& &– Ð
valuemax": this.options.max,™Ð’òò DôDó¢ v† B 6†÷VÆB vR Fò v–F, f ÇVW2 F† B 6 âwB
be parsed?™Ð’& &– ×f ÇVVæ÷r#¢ F†–2å÷ '6R, F†–2æVÆVÖVçBçf Â,’™½})÷ÒÓòò W F FR
the value without triggering change™Ð÷f ÇVS¢ gVæ7F–öâ, f ÇVRÂ ÆÆ÷t ç’ ’ ™½var
parsed;™Ðif (value !== "") {™Ð '6VB Ò F†–2å÷ '6R, f ÇVR ™½–b , '6VB ÓÒ
null) {™Ðif (!allowAny)™½{™Ð '6VB Ò F†–2åö F§W7Ef ÇVR, '6VB™™½™½Ðvalue =
this._format(parsed);™Ð–}™½Ðthis.element.val(value);™Ðthis._refresh();÷ÒÓ
_destroy: function() {™Ðthis.element™½Ðç&VÖ÷fT6Æ 72, 'V’×7 –ææW"Ö–ç WB" •
™’ç &÷ , &F–6 &ÆVB"Â f Ç6R™‘ç&VÖ÷fT GG", & WFö6ö× ÆWFR"™‘ç&VÖ÷fT GG", '&öÆR" •
™’ç&VÖ÷fT GG", & &– ×f ÇVVÖ–â"™‘ç&VÖ÷fT GG", & &– ×f ÇVVÖ ," •
™’ç&VÖ÷fT GG", & &– ×f ÇVVæ÷r" ™½this.uiSpinner.replaceWith(this.element);÷ÒÓ
stepUp: modifier(function(steps) {™Ðthis._stepUp(steps);™Ð’Í÷7FW W ¢
function(steps) {™Ðif (this._start()) {™ÐF†–2å÷7 –â, ‡7FW 2 ÇÂ ’ ¢
this.options.step);™Ð–F†–2å÷7F÷ ,™½™½ÒÓ7FW F÷vã¢ ÖöF–f–W"†gVæ7F–öâ, 7FW 2 ’ ™½
this._stepDown(steps);™ÐÒ’Í÷7FW F÷vã¢ gVæ7F–öâ, 7FW 2 ’ ™½if (this._start())
{™Ð–F†–2å÷7 –â, ‡7FW 2 ÇÂ ’ ¢ ×F†–2æ÷ F–öç2ç7FW ™½™½F†–2å÷7F÷ ,™½™½ÒÓ vUW ¢
modifier(function(pages) {™Ðthis._stepUp((pages || 1) * this.options.page);Ð
–Ò’Ó vTF÷vã¢ ÖöF–f–W"†gVæ7F–öâ, vW2 ’ ™½this._stepDown((pages || 1) *
this.options.page);™ÐÒ’Ó™½Ðf ÇVS¢ gVæ7F–öâ, æWuf Â ’ ™½if (!arguments.length) {™Ð
return this._parse(this.element.val());™Ð}™½Ðmodifier(this._value).call(this,
newVal);™ÐÒÓv–FvWC¢ gVæ7F–öâ,’ ™½return this.uiSpinner;™½});™½Ð(jQuery));Ð
(function($, undefined) {™Ðar tabId = 0,™Ð&† 6, Ò ò2â¢BóÓ™½Ðunction
getNextTabId() {™Ð&WGW&â ²·F $–C™½Ðunction isLocal(anchor) {™ÐÒòò 7W ÷'C¢ ”S}òò
IE7 doesn't normalize the href property when set via script (#9317)™Ð æ6†÷" Ò
anchor.cloneNode(false);™Ð&WGW&â æ6†÷"æ† 6,æÆVæwF, â bm™
decodeURIComponent(anchor.href.replace(rhash, "")) ===™Ð•
decodeURIComponent(location.href.replace(rhash, ""));™½Ð
$.widget("ui.tabs", {™ÐfW'6–öã¢ # ã ãB"ÍFVÆ “¢ 3 Í÷ F–öç3¢ ™½active: null,™Ð
collapsible: false,™Ðevent: "click",™ÐheightStyle: "content",™Ðhide: null,™Ðshow:
null,™Ð// callbacks™½Ðactivate: null,™ÐbeforeActivate: null,™ÐbeforeLoad: null,™Ðload:
null™½ÐÒÓö7&V FS¢ gVæ7F–öâ,’ ™½var that = this,™Ð÷ F–öç2 Ò F†–2æ÷ F–öçÐ™½
this.running = false;™Ðthis.element™½Ðæ FD6Æ 72, 'V’×F '2 V’×v–FvWB V’×v–FvWB™½Ð
content ui-corner-all")™Ð’çFövvÆT6Æ 72, 'V’×F '2Ö6öÆÆ 6–&ÆR"Â
options.collapsible)™Ð’òò &WfVçB W6W'2 g&öÒ fö7W6–ær F–6 &ÆVB F '2 f– 6Æ–6½
™’æFVÆVv FR, "çV’×F '2Öæ b â Æ’"Â &Ö÷W6VF÷vâ" ² F†–2æWfVçDæ ÖW7 6RÂ
function(event) {™Ð

™™if ($(this).is(".ui-state-disabled"))™™Ð
event.preventDefault();™™}™™Ò‘òò 7W ÷'C¢ ”R Ã‘òò &WfVçF–ær F†R FVf VÇB 7F–öâ
in mousedown doesn't prevent IE™™’òò g&öÒ fö7W6–ær F†R VÆVÖVçBÂ 6ò –b F†R æ6†÷"
gets focused, blur.™™’òò vR FöâwB † fR Fò v÷''' &÷WB fö7W6–ær F†R &Wf–÷W6Ç’
focused™™’òò VÆVÖVçB 6–æ6R 6Æ–6¶–ær öâ   æöâÖfö7W6 &ÆR VÆVÖVçB 6†÷VÆB fö7™™–òò
the body anyway.™™’æFVÆVv FR, "çV’×F '2Ö æ6†÷""Â &fö7W2" ² F†–2æWfVçDæ ÖW7 6RÂ
function() {™™if ($(this).closest("li").is(".ui-state-disabled"))™™Ð
this.blur();™™}™™Ò½his._processTabs()™™Ðoptions.active = this._initialActive()™™Ð/
Take disabling tabs via class attribute from HTML™™// into account and update
option properly.™™if ($.isArray(options.disabled)) {™™Ð÷ F–öç2æF–6 &ÆVB Ò
$.unique(options.disabled.concat(™™$.map(this.tabs.filter(".ui-state-
disabled"), function(li) {™™–&WGW&â F† BçF '2æ–æFW,, Æ’™™½™™Ð ’ç6÷'B,™™™™Ð/
check for length avoids error when initializing empty list™™if
(this.options.active !== false && this.anchors.length) {™™–F†–2æ 7F–fR Ò
this._findActive(options.active);™™} else {™™F†–2æ 7F–fR Ò B,™™™™this._refresh()™™Ð
if (this.active.length) {™™–F†–2æÆö B, ÷ F–öç2æ 7F–fR ™™½™™Ö–æ–F– Ä 7F–fS¢
function() {™™var active = this.options.active™™Ð6öÆÆ 6–&ÆR Ò
this.options.collapsible,™™–Æö6 F–öä† 6, Ò Æö6 F–öâæ† 6,ç7V'7G&–ær,   ™™½f
(active === null) {™™’òò 6†V6² F†R g& vÖVçB –FVçF–f–W" –â F†R U™™Í–b
(locationHash) {™™this.tabs.each(function(i, tab) {™™–b
($(tab).attr("aria-controls") === locationHash) {™™active = ™™™™Ðeturn
false;™™™™

™•
this._activate(this._focusNextTab(this.options.active - 1, false));Ð—&WGW&â
true;Ð}ÐÐif (event.altKey && event.keyCode === $.ui.keyCode.PAGE_DOWN) {Ð
this._activate(this._focusNextTab(this.options.active + 1, true));Ð—&WGW&â
true;Ð}ÐÓöf–æDæW‡EF #¢ gVæ7F–öâ, –æFW,Â vö–ætf÷'v &B ’ ½var lastTabIndex =
this.tabs.length - 1;Ðfunction constrain() {Ð–b , –æFW, â Æ 7EF $–æFW, ’™½index
= 0;Ð—Ý–b , –æFW, Â ’™½index = lastTabIndex;Ð&WGW&â –æFW;ÐÐwhile
($.inArray(constrain(), this.options.disabled) !== -1) {Ð––æFW, Ò
goingForward ? index + 1 : index - 1;ÐÐreturn index;ÐÓöfö7W4æW‡EF #¢
function(index, goingForward) {Ðindex = this._findNextTab(index,
goingForward);Ðthis.tabs.eq(index).focus();Ðreturn index;ÐÓ÷6WD÷ F–öã¢
function(key, value) {Ðif (key === "active") {ÐÒòò ö 7F—f FR,’ v–ÆÂ † æFÆR
invalid values and update this.optionsÐ—F†—2åö 7F—f FR, f ÇVR ™½&WGW&âÐif
(key === "disabled") {Ð’òò FöâwB W6R F†R v–FvWB f 7F÷''w2 F—6 &ÆVB † æFÆ–æ}
this._setupDisabled(value);Ð—&WGW&âÐthis._super(key, value);Ðif (key ===
"collapsible") {Ð—F†—2æVÆVÖVçBçFövvÆT6Æ 72, 'V’×F '2Ö6öÆÆ 6–&ÆR"Â f ÇVR ™½òò
Setting collapsible: false while collapsed; open first panelÐ––b , f ÇVR bb
this.options.active === false) {Ð™this._activate(0);ÐÐif (key === "event")
{Ð—F†—2å÷6WGW WfVçG2, f ÇVR ™ÐÐif (key === "heightStyle") {Ð
this._setupHeightStyle(value);Ð}ÐÓ÷F $–C¢ gVæ7F–öâ, F " ’ ™½return
tab.attr("aria-controls") || "ui-tabs-" + getNextTabId();ÐÒÓÐ
_sanitizeSelector: function(hash) {Ðreturn hash ? hash.replace(/[!"$
%&'()*+,.\/:;<=>?@\[\]\^`{|}~]/g, "\\$&") : "";ÐÒÓÐ&Vg&W6ƒ¢ gVæ7F–öâ,’ ™½var
options = this.options,Ð–Æ—2 Ò F†—2çF &Æ—7Bæ6†–ÆG&Vâ, #¦† 2† ¶‡&VeÒ’" Ð½/ get
disabled tabs from class attribute from HTMLÐ// this will get converted to a
boolean if needed in _refresh()Ðoptions.disabled = $.map(lis.filter(".ui-
state-disabled"), function(tab) {Ð—&WGW&â Æ—2æ–æFW,, F " ™½)ÐÐ
this._processTabs();Ð// was collapsed or no tabsÐif (options.active === false
|| !this.anchors.length) {Ð–÷ F–öç2æ 7F—fR Ò f Ç6™½F†—2æ 7F—fR Ò B,™½/ was
active, but active tab is goneÐ} else if (this.active.length && !
$.contains(this.tablist[0], this.active[0])) {Ð’òò ÆÂ &VÖ –æ–ær F '2
are disabledÐ––b , F†—2çF '2æÆVæwF, ÓÓÒ ÷ F–öç2æF—6 &ÆVBæÆVæwF, ’™½
options.active = false;Ð™this.active = $(™‘);Ðò 7F—f FR &Wf–÷W2 F™—Ò VÇ6R™™
this._activate(this._findNextTab(Math.max(0, options.active - 1),
false));Ð—Ý// was active, active tab still existsÐ else {Ðòò Ö ¶R 7W&R 7F—fR
index is correctÐ–÷ F–öç2æ 7F—fR Ò F†—2çF '2æ–æFW,, F†—2æ 7F—fR ™ÐÐ
this._refresh();ÐÒÓ÷&Vg&W6ƒ¢ gVæ7F–öâ,’ ™
this._setupDisabled(this.options.disabled);Ð
this._setupEvents(this.options.event);Ð
this._setupHeightStyle(this.options.heightStyle);Ð
this.tabs.not(this.active).attr({Ð’& &– ×6VÆV7FVB#¢ &f Ç6R™ÍF $–æFWƒ¢ Ó});Ð
this.panels.not(this._getPanelForTab(this.active))Ð’æ†–FR™‘æ GG"™™"aria-
expanded": "false",Ð™"aria-hidden": "true"—ÐÐ½/ Make sure one tab is in the tab
orderÐif (!this.active.length) {ÐF†—2çF '2æW , ’æ GG", 'F $–æFW,"Â ™½
else {Ð—F†—2æ 7F—f™™].addClass("ui-tabs-active ui-state-active")Ðattr({Ð& &– Ð
selected": "true",Ð™—F $–æFWƒ¢ }™;Ð†—2åövWE æVÄf÷%F ", F†—2æ 7F—fR™•.show()Ð
™™.attr({Ð& &– ÖW‡ æFVB#¢ 'G'VR™Í& &– Ö†–FFVâ#¢ &f ÇÖR™}™;ÐÓ÷ &ö6W75F '3¢
function() {Ðvar that = this;ÐÐthis.tablist = this._getList();ÐÆ FD6Æ 72, 'V’×F '2Ð
nav ui-helper-reset ui-helper-clearfix ui-widget-header ui-corner-all")Ð
™’æ GG", '&öÆR"Â 'F &Æ—7B" Ð½this.tabs = this.tablist.find(">
li:has(a[href])")Ð’æ FD6Æ 72, 'V’×7F FRÖFVf VÇB V’Ö6÷&æW"×F÷ "™‘æ GG"™™½role:
"tab",Ð™tabIndex: ™-1ÐÐ½this.anchors = this.tabs.map(function() {Ðreturn $("a",
this)[0];Ð—Ò‘æ FD6Æ 72, 'V’×F '2Ö æ6†÷""™‘æ GG"™™½role: "presentation",Ð
tabIndex: -1Ð—ÒÐ½this.panels = $()ÐÐthis.anchors.each(function(i, anchor) {Ðf "
selector, panel, panelId,Ð™anchorId = $(anchor).uniqueId().attr("id");Ðab =
$(anchor).closest("li");Ð™originalAriaControls = tab.attr("aria-
controls");Ð’òò –æÆ–æR F™––b , —4Æö6 Â, æ6†÷" ’ ’™½selector = anchor.hash;Ð
panel = that.element.find(that._sanitizeSelector(selector));Ð’òò &VÖ÷FR F -
™—Ò VÇ6R™™½panelId = that._tabId(tab);Ðselector = "#" + panelId;Ðpanel =
that.element.find(selector);Ð

™™if (!panel.length) {Ð æVÂ Ò
that._createPanel(panelId);Ð™— æVÂæ–ç6W'D gFW", F† Bç æVÇ5² ' Ò   Ò ÇÂ
that.tablist);Ð™™}Ðpanel.attr("aria-live", "polite");Ð™–b ,   æVÂæÆVæwF,'™™½
that.panels = that.panels.add(panel);Ð™¥–b , ÷&–v–æ Ä &– 6öçG&öÇ2 '™™½
tab.data("ui-tabs-aria-controls", originalAriaControls);Ð™¥F "æ GG"™™½"aria-
controls": selector.substring(1),Ð™"aria-labelledby": anchorId½
panel.attr("aria-labelledby", anchorId);Ð™})Ðthis.panels™Ðæ FD6Æ 72, 'V'×F '2Ð
panel ui-widget-content ui-corner-bottom")Ð™'æ GG", '&öÆR"Â 'F ' æVÂ" "ÒÐòò
allow overriding how to find the list for rare usage scenarios (#7715)Ð
_getList: function() {Ðreturn this.tablist ||
this.element.find("ol,ul").eq(0);ÐÒÐö7&V FU æVÃ¢ gVæ7F–öâ, –B ' ™½return
$(" ")Ð'æ GG", &–B"Â –B™‘æ FD6Æ 72, 'V'×F '2× æVÂ V'×v–FvWBÖ6öçFVçB V'Ð
corner-bottom")Ð'æF F , 'V'×F '2ÖFW7G&÷'"Â G'VR "ÒÐ÷6WGW F—6 &ÆVC¢
function(disabled) {Ðif ($.isArray(disabled)) {Ð–b , F—6 &ÆVBæÆVæwF, '™™½
disabled = false;Ð—Ò VÇ6R –b , F—6 &ÆVBæÆVæwF, ÓÓÒ F†—2æ æ6†÷'2æÆVæwF, '™™½
disabled = true;Ð—ÐÐ/ disable tabsÐfor (var i = 0, li; (li =
this.tabs[i]); i++) {Ð––b , F—6 &ÆVB ÓÓÒ G'VR ÇÂ Bæ–ä '& ', 'Â F—6 &ÆVB '
== -1) {Ð™$(li)™™Ðæ FD6Æ 72, 'V'×7F FRÖF—6 &ÆVB™™™‘æ GG", & &– ÖF—6 &ÆVB"Â
"true");Ð—Ò VÇ6R ™½$(li)™™™Ðç&VÖ÷fT6Æ 72, 'V'×7F FRÖF—6 &ÆVB™™™‘ç&VÖ÷fT GG", & &– Ð
disabled");Ð—ÐÐthis.options.disabled = disabled;ÐÒÐ÷6WGW WfVçG3¢
function(event) {Ðvar events = {Ð6Æ–6³¢ gVæ7F–öâ, WfVçB '™™½
event.preventDefault();Ð—};Ðif (event) {ÐBæV 6,, WfVçBç7 Æ—B," "'Â
function(index, eventName) {Ðevents[eventName] = "_eventHandler";ÐÐ
this._off(this.anchors.add(this.tabs).add(this.panels));Ð
this._on(this.anchors, events);Ðthis._on(this.tabs, { keydown:
"_tabKeydown" });Ðthis._on(this.panels, { keydown: "_panelKeydown" });Ð
this._focusable(this.tabs);Ðthis._hoverable(this.tabs);ÐÒÐ
_setupHeightStyle: function(heightStyle) {Ðvar maxHeight;Ð &VçB Ò
this.element.parent();Ðif (heightStyle === "fill") {ÐÖ „†V–v‡B Ò
parent.height();Ð–Ö „†V–v‡B ÓÒ F†—2æVÆVÖVçBæ÷WFW$†V–v‡B,' Ò
this.element.height();Ð—F†—2æVÆVÖVçBç6–&Æ–æw2, #§f—6–&ÆR" 'æV 6,†gVæ7F–öâ,'™™½
var elem = $(this);Ð™— ÷6—F–öâ Ò VÆVÒæ772, ' ÷6—F–öâ"Ð™½f (position ===
"absolute" || position === "fixed") {Ð™—&WGW&™™™™maxHeight -=
elem.outerHeight(true);Ð—ÒÐ™½
this.element.children().not(this.panels).each(function() {ÐmaxHeight -=
$(this).outerHeight(true);Ð—ÒÐ™½F†—2ç æVÇ2æV 6,†gVæ7F–öâ,'™™½
$(this).height(Math.max(0, maxHeight -Ð™'B, F†—2 'æ–ææW$†V–v‡B,' ²
$(this).height()));Ð—Ò™‘æ772, &÷fW&fÆ÷r"Â & WFò" ™½ else if (heightStyle
=== "auto") {Ð–Ö „†V–v‡B Ò ™½F†—2ç æVÇ2æV 6,†gVæ7F–öâ,'™™½maxHeight =
Math.max(maxHeight, $(this).height("").height());Ð—Ò'æ†V–v‡B, Ö „†V–v‡B "½
™}ÐÐöWfVçD† æFÆW#¢ gVæ7F–öâ, WfVçB ' ™½var options = this.options;Ð 7F—fR Ò
this.active,Ð– æ6†÷" Ò B, WfVçBæ7W'&VçEF &vWB ™ÍF " Ò æ6†÷"æ6Æ÷6W7B, &Æ'" ™™Í
clickedIsActive = tab[0] === active[0],Ð–6öÆÆ 6–ær Ò 6Æ–6¶VD—4 7F—fR bb
options.collapsible,Ð—Fõ6†÷r Ò 6öÆÆ 6–ær ò B,' ¢ F†—2åövWE æVÄf÷%F ", F " ™™Í
toHide = !active.length ? $() : this._getPanelForTab(active);Ð–WfVçDF F Ò™™½
oldTab: active,Ð™oldPanel: toHide,Ðnewtab: collapsing ? $() : tab;Ðnewpanel:
toShowÐ—ÐÐevent.preventDefault();Ðif (tab.hasClass("ui-state-disabled") ||Ð//
tab is already loadingÐ™tab.hasClass("ui-tabs-loading") ||Ð/ can't switch
durning an animationÐ™this.running ||Ð/ click on active header, but not
collapsibleÐ™(clickedIsActive && !options.collapsible) ||Ð/ allow canceling
activationÐ™(this._trigger("beforeActivate", event, eventData) === false))
{Ð—&WGW&™™™™Ðoptions.active = collapsing ? false : this.tabs.index(tab);ÐÐ
this.active = clickedIsActive ? $() : tab;Ðif (this.xhr) {ÐF†—2ç†‡"æ &÷'B,™™™ÐÐ
if (!toHide.length && !toShow.length) {Ð'BæW'&÷", &¥ VW'' T' F '3¢
Mismatching fragment identifier.");ÐÐif (toShow.length) {Ð
this.load(this.tabs.index(tab), event);Ð}Ðthis._toggle(event, eventData);Ð
—ÒÐòò † æFÆW2 6†÷rö†–FR f÷" 6VÆV7F–ær F '™÷FövvÆS¢ gVæ7F–öâ, WfVçBÂ
eventData) {Ðvar that = this;ÐFõ6†÷r Ò WfVçDF F ææWu æVÄ™FÔ†–FR Ò
eventData.oldPanel;Ðthis.running = true;ÐÐunction complete() {ÐF† Bç'Vææ–ær Ò
false;Ð

™—F† Bå÷G&–vvW", & 7F—f FR"Â WfVçBÂ WfVçDF F function show() {
eventData.newTab.closest("li").addClass("ui-tabs-active ui-state-active");
if (toShow.length && that.options.show) {that._show(toShow,
that.options.show, complete);—Ò VÇ6R toShow.show(), complete();// start out
by hiding, then showing, then completingif (toHide.length &&
this.options.hide) {—F†—2åö†–FR, Fô†–FRÂ F†—2æ÷ F–öç2æ†–FRÂ gVæ7F–öâ,'
eventData.oldTab.closest("li").removeClass("ui-tabs-active ui-state-
active");show();— else {WfVçDF F æöÆEF "æ6Æ÷6W7B, &Æ' 'ç&VÖ÷fT6Æ 72, 'V'
tabs-active ui-state-active");—Fô†–FRæ†–FR, 6†÷r, oHide.attr({& &–
expanded": "false",'& &– Ö†–FFVâ#¢ 'G'VR}),eventData.oldTab.attr("aria-
selected", "false");// If we're switching tabs, remove the old tab from the
tab order.// If we're opening from collapsed state, remove the previous tab
from the tab order.// If we're collapsing, then keep the collapsing tab in
the tab order.if (toShow.length && toHide.length) {
eventData.oldTab.attr("tabIndex", -1);} else if (toShow.length) {
this.tabs.filter(function() {return $(this).attr("tabIndex") ===
'æ GG", 'F $–æFW,"Â Ó oShow.attr({& &– ÖW‡ æFVB#¢ 'G'VR& &– Ö†–FFVâ#¢
"false"});eventData.newTab.attr({& &– ×6VÆV7FVB#¢ 'G'VRF $–æFW¢™})
_activate: function(index) {var anchor, 7F—fR Ò F†—2åöf–æD 7F—fR, –æFW,
// trying to activate the already active paneif (active[0] ===
this.active[0]) {—&WGW&// trying to collapse, simulate a click on the
current active headerif (!active.length) { 7F—fR Ò F†—2æ 7F—fSanchor =
active.find(".ui-tabs-anchor")[0];this._eventHandler({F &vWC¢ æ6†÷
currentTarget: anchor, — &WfVçDFVf VÇC¢ Bæöf–æD 7F—fS¢
function(index) {return index === false ? $() : this.tabs.eq(index)
_getIndex: function(index) {// meta-function to give users option to
provide a href string instead of a numerical index.if (typeof index ===
"string") {––æFW, Ò F†—2æ æ6†÷'2æ–æFW,, F†—2æ æ6†÷'2æf–ÇFW", %¶‡&VbCÒr" ²
index + "']"));return index;öFW7G&÷“¢ gVæ7F–öâ,' ½if (this.xhr) {
this.xhr.abort();this.element.removeClass("ui-tabs ui-widget ui-widget-
content ui-corner-all ui-tabs-collapsible");this.tablistç&VÖ÷fT6Æ 72, 'V'
tabs-nav ui-helper-reset ui-helper-clearfix ui-widget-header ui-corner-all")
'ç&VÖ÷fT GG", '&öÆR"this.anchorSç&VÖ÷fT6Æ 72, 'V'×F '2Ö æ6†÷"" •
'ç&VÖ÷fT GG", '&öÆR"ç&VÖ÷fT GG", 'F $–æFW,"ç&VÖ÷fUVæ— VT–B,
this.tabs.add(this.panels).each(function() {––b , BæF F , F†—2Â 'V'×F '2
destroy")) {$(this).remove(); VÇ6R$(this)ç&VÖ÷fT6Æ 72, 'V'×7F FR
default ui-state-active ui-state-disabled " +"ui-corner-top ui-corner-bottom
ui-widget-content ui-tabs-active ui-tabs-panel")'ç&VÖ÷fT GG", 'F $–æFW," •
'ç&VÖ÷fT GG", & &– ÖÆ—fR'ç&VÖ÷fT GG", & &– Ö'W7''ç&VÖ÷fT GG", & &–
selected")'ç&VÖ÷fT GG", & &– ÖÆ &VÆÆVF''ç&VÖ÷fT GG", & &– Ö†–FFVâ" •
'ç&VÖ÷fT GG", & &– ÖW‡ æFVB'ç&VÖ÷fT GG", '&öÆR")
this.tabs.each(function() {—f " Æ' Ò B, F†—2 prev = li.data("ui-tabs-aria-
controls");––b , &Wb ' liæ GG", & &– Ö6öçG&öÇ2Â &WD'ç&VÖ÷fTF F , 'V'
tabs-aria-controls");—Ò VÇ6R li.removeAttr("aria-controls")
this.panels.show();if (this.options.heightStyle !== "content") {
this.panels.css("height", "");}—ÒVæ &ÆS¢ gVæ7F–öâ, –æFW, ' ½var disabled =
this.options.disabled;if (disabled === false) {&WGW&if (index ===
undefined) {–F—6 &ÆVB Ò f Ç6S½ else {–æFW, Ò F†—2åövWD–æFW,, –æFW, ½–b
($.isArray(disabled)) {disabled = $.map(disabled, function(num) {
return num !== index ? num : null;}); VÇ6R disabled = $.map(this.tabs,
function(li, num) {—&WGW&â çVÒ ÓÒ –æFW, ò çVÒ ¢ çVÆÃ½)
this._setupDisabled(disabled);—F—6 &ÆS¢ gVæ7F–öâ, –æFW, ' ½var disabled =
this.options.disabled;if (disabled === true) {&WGW&if (index ===
undefined) {–F—6 &ÆVB Ò G'VS½ else {–æFW, Ò F†—2åövWD–æFW,, –æFW, ½–b
($.inArray(index, disabled) !== -1) {return–b , Bæ—4 '& ', F—6 &ÆVB ' '
{disabled = $.merge([index], disabled).sort(); VÇ6R disabled =
[index];—this._setupDisabled(disabled);Æö C¢ gVæ7F–öâ, –æFW,Â WfVçB ' ½
index = this._getIndex(index);var that = this,F " Ò F†—2çF '2æW , –æFW,
anchor = tab.find(".ui-tabs-anchor"),— æVÂ Ò F†—2åövWE æVÄf÷%F ", F "
eventData = {

™™tab: tab™,Ðpanel: panel™ÐÝ½/ not remote™Ðif
(isLocal(anchor[0])) {™–&WGW&â™ÐÐthis.xhr =
$.ajax(this._ajaxSettings(anchor, event, eventData));™Ð// support: jQuery
<1.8™Ð// jQuery <1.8 returns false if the request is canceled in beforeSend™,Ð/
but as of 1.8, $.ajax() always returns a jqXHR object.™Ðif (this.xhr &&
this.xhr.statusText !== "canceled") {™–F "æ FD6Æ 72, 'V'×F '2ÖÆö F–ær" ™½
panel.attr("aria-busy", "true");™–F†–2ç†‡™.success(function(response) {™™Ðòò
support: jQuery <1.8™Ð'òò ‡GG ¢òö'Vw2æ§ VW''æ6öÒ÷F–6¶WBó ™™•
setTimeout(function() {™™™panel.html(response™™™);™Ðthat._trigger("load", event,
eventData);™–ÒÂ ™™™™½™™Ðcomplete(function(jqXHR, status) {™™™Ðòò 7W ÷'C¢ ¥ VW''
<1.8™Ð'òò ‡GG ¢òö'Vw2æ§ VW''æ6öÒ÷F–6¶WBó ™™•6WEF–ÖV÷WB†gVæ7F–öâ,™™½if (status
=== "abort") {™™™–F† Bç æVÇ2ç7F÷ , f Ç6RÂ G'V™™™™™½™Ðab.removeClass("ui-tabs-
loading");™™™panel.removeAttr("aria-busy"™™™);™Ðif (jqXHR === that.xhr) {™™™ÐFVÆWFR
that.xhr;™™™™ÐÂ ™™™™½™™™Ðöö ¦ …6WGF–æw3¢ gVæ7F–öâ, æ6†÷"Â WfVçBÂ WfVçDF F ' ™½
var that = this;™Ðreturn ™™™Ð™™™W&Ã¢ æ6†÷"æ GG", &‡&Vb" ™Í&Vf÷&U6VæC¢
function(jqXHR, settings) {™™™™™

™if (!target.length || target.data("ui-tooltip-id")) {™–&WGW&â F†–2åö÷ Vâ, WfVçBÂ F &vWBÂ 6öçFVçD÷ F–öâ ™™™™if (target.attr("title")) {™™ target.data("ui-tooltip-title", target.attr("title"));™™™™target.data("ui-tooltip-open", true);™™// kill parent tooltips, custom or native, for hover™™if (event && event.type === "mouseover") {™™–F &vWBç &VçG2,’æV 6,†gVæ7F–öâ,’™™½ var parent = $(this),™™–&ÇW$WfVÇÇ½™™if (parent.data("ui-tooltip-open"))™™{™™ blurEvent = $.Event("blur");™™–&ÇW$WfVçBçF &vWB Ò &ÇW$WfVçBæ7W'&VçEF &vWB Ò this;™™–F† Bæ6Æ÷6R, &ÇW$WfVçBÂ G'VR™™™™½™™if (parent.attr("title"))™™{™™ parent.uniqueId();™™–F† Bç &VçG5² F†–2æ–B Ò Ò™™™½element: this,™™title: parent.attr("title")™™™™™™–Ò½ &VçBæ GG", 'F–FÆR"Â ""™™™™½™™™™ this._updateContent(target, event);™™ÒÓ™™÷W F FT6öçFVçC¢ gVæ7F–öâ, F &vWBÂ event) {™™var content,™™6öçFVçD÷ F–öâ Ò F†–2æ÷ F–öç2æ6öçFVçB™™F† B Ò F†–2™™ eventType = event ? event.type : null;™™if (typeof contentOption === "string") {™™–&WGW&â F†–2åö÷ Vâ, WfVçBÂ F &vWBÂ 6öçFVçD÷ F–öâ ™™™™™™™™content = contentOption.call(target[0], function(response) {™™’òò –væ÷&R 7–æ2 &W7 öç6R if tooltip was closed already™™––b , F &vWBæF F , 'V’×FööÇF– Ö÷ Vâ" ’ ’™™½return;™™™™Ýòò ”R Ö ’ –ç7F çFÇ’ 6W'fR 6 6†VB &W7 öç6R f÷" ¦ , &W VW7G™™–òò FVÆ ’ F†–2 call to _open so the other call to _open runs first™™–F† BåöFVÆ ’†gVæ7F–öâ,’™™½// jQuery creates a special event for focusin when it doesn't™™// exist natively. To improve performance, the native event™™// object is reused and the type is changed. Therefore, we can't™™// rely on the type being correct after the event finished™™// bubbling, so we set it back to the previous value. (#8740)™™™™if (event) {™™–WfVçBçG– R Ò WfVçEG–™™™™½™™this._open(event, target, response);™™÷Ò“½ ™™});™™if (content) {™™F†–2åö÷ Vâ, WfVçBÂ F &vWBÂ 6öçFVçB ™™½™™™™Ö÷ Vã¢ function(event, target, content) {™™var tooltip, events, delayedShow,™™ positionOption = $.extend({}, this.options.position);™™if (!content) {™™ return;™™™™™™™™

™// to avoid an infinite loop
in case the tooltip becomes disabled on closeÐif (this.closing) {™Ð&WGW&ãÐÐ/
Clear the interval for delayed tracking tooltipsÐ
clearInterval(this.delayedShow);Ð// only set title if we had one before (see
comment in _open())Ðif (target.data("ui-tooltip-title")) {™Ð
target.attr("title", target.data("ui-tooltip-title"));ÐÐÐ
removeDescribedBy(target);Ðtooltip.stop(true);™Ðthis._hide(tooltip,
this.options.hide, function() {™—F† Bå÷&VÖ÷fUFööÇF— , B, F†—2 ’ ™½);™Ð
target.removeData("ui-tooltip-open");™Ðthis._off(target, "mouseleave
focusout keyup");™Ð// Remove 'remove' binding only on delegated targetsÐif
(target[0] !== this.element[0]) {™—F†—2åööfb, F &vWBÂ '&VÖ÷fR" ™½Ð
this._off(this.document, "mousemove");™Ðif (event && event.type ===
"mouseleave") {™Ð’BæV 6,, F†—2ç &VçG2Â gVæ7F–öâ, –BÂ &VçB ’™™½
$(parent.element).attr("title", parent.title);™Ðdelete that.parents[id];Ð
™—Ò™½Ðthis.closing = true;™Ðthis._trigger("close", event, { tooltip: tooltip });™Ð
this.closing = false;ÐÒÐ÷FööÇF— ¢ gVæ7F–öâ, VÆVÖVçB ’ ™½var id = "ui-tooltip-"
+ increments++,™Ð—FööÇF— Ò B, #ÆF—câ"™™•.attr({™Ð–C¢ –™Í&öÆS¢ 'FööÇF—™™})Ð
™™.addClass("ui-tooltip ui-widget ui-corner-all ui-widget-content "™™Ð
(this.options.tooltipClass || ""));™Ð$(" ")™Ðæ FD6Æ 72, 'V’×FööÇF— Ð
content")™Ð’æ VæEFò, FööÇF— ™½ooltip.appendTo(this.document[0].body);™Ð
this.tooltips[id] = element;™Ðreturn tooltip;ÐÓöf–æC¢ gVæ7F–öâ, F &vWB ’ ™½var
id = target.data("ui-tooltip-id");™Ðreturn id ? $("#" + id) : $();ÐÓÐ
_removeTooltip: function(tooltip) {™Ðtooltip.remove();™Ðdelete
this.tooltips[tooltip.attr("id")];ÐÓöFW7G&÷“¢ gVæ7F–öâ,’ ™½var that = this;ÐÐ
™// close open tooltipsÐ™Ð.each(this.tooltips, function(id, element) {™Ðòò
Delegate to close method to handle common cleanup™Ð—f " WfVçB Ò
$.Event("blur");™Ð–WfVçBçF &vWB Ò WfVçBæ7W'&VçEF &vWB Ò VÆVÖVçE³ Ó™½
that.close(event, true);™Ð’òò &VÖ÷fR –ÖÖVF– FVÇ“² FW7G&÷––ær â ÷ Vâ FööÇF—
doesn't use the™Ð’òò †–FR æ–Ö F–Ó™1B, "2" ² –B ’ç&VÖ÷fR,™Ð½òò &W7F÷&R F†R F—FÆ]–b
(element.data("ui-tooltip-title")) {™Ðelement.attr("title",
element.data("ui-tooltip-title"));™Ðelement.removeData("ui-tooltip-title");Ð
™™Ý);÷Ð);Ð(jQuery));Ð

public\assets\js\plugins\jsKnob\jquery.knob.js

```
/*!jQuery Knob*/Ð**Ð* Downward compatible, touchable dialÐ*Ð* Version: 1.2.8Ð
* Requires: jQuery v1.7+Ð*Ð* Copyright (c) 2012 Anthony TerrienÐ* Under MIT
License (http://www.opensource.org/licenses/mit-license.php)Ð*Ð* Thanks to
vor, eskimoblood, spiffistan, FabrizioCÐ*/Ðfunction($) {Ð   /**Ð    * Kontrol
libraryÐ    */Ð   "use strict";Ð   /**Ð    * Definition of globals and coreÐ
     */Ð   var k = {}, // kontrolÐ       max = Math.max,Ð       min =
Math.min;Ð   k.c = {};Ð   k.c.d = $(document);Ð   k.c.t = function (e) {Ð
        return e.originalEvent.touches.length - 1;Ð   };Ð   /**Ð    * Kontrol
ObjectÐ    *Ð    * Definition of an abstract UI controlÐ    *Ð    * Each
concrete component must call this one.Ð    * <code>Ð    * k.o.call(this);Ð
* </code>Ð    */Ð   k.o = function () {Ð       var s = this;Ð       this.o =
null; // array of optionsÐ       this.$ = null; // jQuery wrapped elementÐ
        this.i = null; // mixed HTMLInputElement or array of HTMLInputElementÐ
        this.g = null; // deprecated 2D graphics context for 'pre-rendering'Ð
        this.v = null; // value ; mixed array or integerÐ       this.cv =
null; // change value ; not commited valueÐ       this.x = 0; // canvas x
positionÐ       this.y = 0; // canvas y positionÐ       this.w = 0; // canvas
widthÐ       this.h = 0; // canvas heightÐ       this.$c = null; // jQuery
canvas elementÐ       this.c = null; // rendered canvas contextÐ       this.t
= 0; // touches indexÐ       this.isInit = false;Ð       this.fgColor =
null; // main colorÐ       this.pColor = null; // previous colorÐ
this.dH = null; // draw hookÐ       this.cH = null; // change hookÐ
this.eH = null; // cancel hookÐ       this.rH = null; // release hookÐ
this.scale = 1; // scale factorÐ       this.relative = false;Ð
this.relativeWidth = false;Ð       this.relativeHeight = false;Ð       this.
$div = null; // component divÐ       this.run = function () {Ð           var
cf = function (e, conf) {Ð               var k;Ð               for (k in
conf) {Ð                   s.o[k] = conf[k];Ð               }Ð
s._carve().init();Ð               s._configure()Ð                   ._draw();Ð
            };Ð           if(this.$.data('kontroled')) return;Ð
this.$.data('kontroled', true);Ð           this.extend();Ð           this.o =
$.extend(Ð               {Ð                   // ConfigÐ
min : this.$.data('min') !== undefined ? this.$.data('min') : 0,Ð
                    max : this.$.data('max') !== undefined ? this.
$.data('max') : 100,Ð                   stopper : true,Ð
readOnly : this.$.data('readonly') || (this.$.attr('readonly') ===
'readonly'),Ð                   // UIÐ                   cursor : (this.
$.data('cursor') === true && 30) ||Ð                   this.
$.data('cursor') || 0,Ð                   thickness : (Ð
                        this.$.data('thickness') &&Ð
                            Math.max(Math.min(this.$.data('thickness'), 1),
0.01)Ð                        ) || 0.35,Ð                   lineCap : this.
$.data('linecap') || 'butt',Ð                   width : this.$.data('width')
|| 200,Ð                   height : this.$.data('height') || 200,Ð
                    displayInput : this.$.data('displayinput') == null ||
this.$.data('displayinput'),Ð                   displayPrevious : this.
$.data('displayprevious'),Ð                   fgColor : this.
$.data('fgcolor') || '#87CEEB',Ð                   inputColor: this.
$.data('inputcolor'),Ð                   font: this.$.data('font') || 'Arial',Ð
                    fontWeight: this.$.data('font-weight') || 'bold',Ð
                    inline : false,Ð                   step : this.
$.data('step') || 1,Ð                   rotation: this.$.data('rotation'),Ð
                    // HooksÐ                   draw : null, // function () {}Ð
                    change : null, // function (value) {}Ð
cancel : null, // function () {}Ð                   release : null, //
function (value) {}Ð                   // Output formatting, allows to add
unit: %, ms ...Ð                   format: function(v) {Ð
                        return v;Ð                   },Ð
parse: function (v) {Ð
```

```
                                                return parseFloat(v);Ð
                    }Ð                }, this.oÐ            );Ð            //
finalize optionsÐ            this.o.flip = this.o.rotation === 'anticlockwise'
|| this.o.rotation === 'acw';Ð            if(!this.o.inputColor) {Ð
                this.o.inputColor = this.o.fgColor;Ð            }Ð
            // routing valueÐ            if(this.$.is('fieldset')) {Ð
                // fieldset = array of integerÐ                this.v = {};Ð
                this.i = this.$.find('input');Ð
this.i.each(function(k) {Ð                    var $this = $(this);Ð
                    s.i[k] = $this;Ð                    s.v[k] =
s.o.parse($this.val());Ð                    $this.bind(Ð
'change blur'Ð                    , function () {Ð
                            var val = {};Ð                            val[k] =
$this.val();Ð                            s.val(val);Ð                    }Ð
                    );Ð                });Ð                this.
$.find('legend').remove();Ð            } else {Ð                // input =
integerÐ                this.i = this.$;Ð                this.v =
this.o.parse(this.$.val());Ð                (this.v === '') && (this.v =
this.o.min);Ð                this.$.bind(Ð                    'change blur'Ð
                    , function () {Ð
s.val(s._validate(s.o.parse(s.$.val())));Ð                    }Ð
                );Ð            }Ð            (!this.o.displayInput) && this.
$.hide();Ð            // adds needed DOM elements (canvas, div)Ð
this.$c = $(document.createElement('canvas')).attr({Ð                width:
this.o.width,Ð                height: this.o.heightÐ            });Ð
            // wraps all elements in a divÐ            // add to DOM before
Canvas init is triggeredÐ            this.$div = $('<div style="'Ð
                + (this.o.inline ? 'display:inline;' : '')Ð                +
'width:' + this.o.width + 'px;height:' + this.o.height + 'px;'Ð
+ '"></div>');Ð            this.$.wrap(this.$div).before(this.$c);Ð
this.$div = this.$.parent();Ð            if (typeof G_vmlCanvasManager !==
'undefined') {Ð                G_vmlCanvasManager.initElement(this.$c[0]);Ð
            }Ð            this.c = this.$c[0].getContext ? this.
$c[0].getContext('2d') : null;Ð            if (!this.c) {Ð                throw
{Ð                    name:        "CanvasNotSupportedException",Ð
                    message:     "Canvas not supported. Please use excanvas
on IE8.0.",Ð                    toString:    function(){return this.name + ":
" + this.message}Ð                }Ð            }Ð            // hdpi supportÐ
            this.scale = (window.devicePixelRatio || 1) /Ð                (Ð
                    this.c.webkitBackingStorePixelRatio ||Ð
                        this.c.mozBackingStorePixelRatio ||Ð
                        this.c.msBackingStorePixelRatio ||Ð
                        this.c.oBackingStorePixelRatio ||Ð
                        this.c.backingStorePixelRatio || 1Ð
                    );Ð            // detects relative width / heightÐ
            this.relativeWidth = ((this.o.width % 1 !== 0) &&Ð
this.o.width.indexOf('%'));Ð            this.relativeHeight = ((this.o.height
% 1 !== 0) &&Ð                this.o.height.indexOf('%'));Ð
this.relative = (this.relativeWidth || this.relativeHeight);Ð            //
computes size and carves the componentÐ            this._carve();Ð
            // prepares props for transactionÐ            if (this.v
instanceof Object) {Ð                this.cv = {};Ð
this.copy(this.v, this.cv);Ð            } else {Ð                this.cv =
this.v;Ð            }Ð            // binds configure eventÐ            this.$Ð
                .bind("configure", cf)Ð                .parent()Ð
                .bind("configure", cf);Ð            // finalize initÐ
            this._listen()Ð                ._configure()Ð                ._xy()Ð
                .init();Ð            this.isInit = true;Ð            this.
$.val(this.o.format(this.v));Ð            this._draw();Ð            return this;Ð
        };Ð
```

```
          Ð       this._carve = function() {Ð           if(this.relative) {Ð
                var w = this.relativeWidth ?Ð                        this.
$div.parent().width() *Ð                          parseInt(this.o.width) /
100 :Ð                        this.$div.parent().width(),Ð                    h
= this.relativeHeight ?Ð                        this.$div.parent().height() *Ð
                           parseInt(this.o.height) / 100 :Ð
                          this.$div.parent().height();Ð              // apply
relativeÐ                 this.w = this.h = Math.min(w, h);Ð           } else {Ð
                this.w = this.o.width;Ð               this.h = this.o.height;Ð
            }Ð           // finalize divÐ            this.$div.css({Ð
                'width': this.w + 'px',Ð               'height': this.h + 'px'Ð
            });Ð           // finalize canvas with computed widthÐ
this.$c.attr({Ð               width: this.w,Ð               height: this.hÐ
            });Ð           // scalingÐ           if (this.scale !== 1) {Ð
                this.$c[0].width = this.$c[0].width * this.scale;Ð
                this.$c[0].height = this.$c[0].height * this.scale;Ð
                this.$c.width(this.w);Ð               this.$c.height(this.h);Ð
            }Ð           return this;Ð       }Ð       this._draw = function
() {Ð           // canvas pre-renderingÐ           var d = true;Ð
s.g = s.c;Ð           s.clear();Ð           s.dHÐ           && (d = s.dH());Ð
            (d !== false) && s.draw();Ð       };Ð       this._touch =
function (e) {Ð           var touchMove = function (e) {Ð               var v
= s.xy2val(Ð                    e.originalEvent.touches[s.t].pageX,Ð
                    e.originalEvent.touches[s.t].pageYÐ               );Ð
                if (v == s.cv) return;Ð               if (s.cH && (s.cH(v)
=== false)) return;Ð               s.change(s._validate(v));Ð
s._draw();Ð           };Ð           // get touches indexÐ           this.t =
k.c.t(e);Ð           // First touchÐ           touchMove(e);Ð           //
Touch events listenersÐ           k.c.dÐ               .bind("touchmove.k",
touchMove)Ð               .bind(Ð               "touchend.k"Ð               ,
function () {Ð                   k.c.d.unbind('touchmove.k touchend.k');Ð
                    s.val(s.cv);Ð               }Ð           );Ð
return this;Ð       };Ð       this._mouse = function (e) {Ð           var
mouseMove = function (e) {Ð               var v = s.xy2val(e.pageX, e.pageY);Ð
                if (v == s.cv) return;Ð               if (s.cH && (s.cH(v)
=== false)) return;Ð               s.change(s._validate(v));Ð
s._draw();Ð           };Ð           // First clickÐ           mouseMove(e);Ð
            // Mouse events listenersÐ           k.c.dÐ
                .bind("mousemove.k", mouseMove)Ð               .bind(Ð
                // Escape key cancel current changeÐ               "keyup.k"Ð
                , function (e) {Ð                   if (e.keyCode === 27) {Ð
                        k.c.d.unbind("mouseup.k mousemove.k keyup.k");Ð
                        if (Ð                           s.eHÐ
                                && (s.eH() === false)Ð
                            ) return;Ð                       s.cancel();Ð
                    }Ð               }Ð           )Ð               .bind(Ð
                "mouseup.k"Ð               , function (e) {Ð
                    k.c.d.unbind('mousemove.k mouseup.k keyup.k');Ð
                    s.val(s.cv);Ð               }Ð           );Ð
return this;Ð       };Ð       this._xy = function () {Ð           var o =
this.$c.offset();Ð           this.x = o.left;Ð           this.y = o.top;Ð
            return this;Ð       };Ð       this._listen = function () {Ð
            if (!this.o.readOnly) {Ð               this.$cÐ
                    .bind(Ð                   "mousedown"Ð
                    , function (e) {Ð
e.preventDefault();Ð                       s._xy()._mouse(e);Ð
                    }Ð               )Ð                   .bind(Ð
                    "touchstart"Ð                   , function (e) {Ð
                        e.preventDefault();Ð
s._xy()._touch(e);Ð
```

```
                                        }Ð                );Ð
this.listen();Ð           } else {Ð                this.$.attr('readonly',
'readonly');Ð           }Ð           if(this.relative) {Ð
$(window).resize(function() {Ð                    s._carve()Ð
                        .init();Ð                    s._draw();Ð
                 });Ð           }Ð           return this;Ð       };Ð
this._configure = function () {Ð           // HooksÐ           if
(this.o.draw) this.dH = this.o.draw;Ð           if (this.o.change) this.cH =
this.o.change;Ð           if (this.o.cancel) this.eH = this.o.cancel;Ð
            if (this.o.release) this.rH = this.o.release;Ð           if
(this.o.displayPrevious) {Ð               this.pColor =
this.h2rgba(this.o.fgColor, "0.4");Ð               this.fgColor =
this.h2rgba(this.o.fgColor, "0.6");Ð           } else {Ð
this.fgColor = this.o.fgColor;Ð           }Ð           return this;Ð       };Ð
        this._clear = function () {Ð           this.$c[0].width = this.
$c[0].width;Ð       };Ð       this._validate = function(v) {Ð
return (~~ (((v < 0) ? -0.5 : 0.5) + (v/this.o.step))) * this.o.step;Ð
        };Ð       // Abstract methodsÐ       this.listen = function () {}; //
on start, one timeÐ       this.extend = function () {}; // each time
configure triggeredÐ       this.init = function () {}; // each time configure
triggeredÐ       this.change = function (v) {}; // on changeÐ       this.val
= function (v) {}; // on releaseÐ       this.xy2val = function (x, y) {}; //Ð
        this.draw = function () {}; // on change / on releaseÐ
this.clear = function () { this._clear(); };Ð       // UtilsÐ
this.h2rgba = function (h, a) {Ð           var rgb;Ð           h =
h.substring(1,7)Ð           rgb = [parseInt(h.substring(0,2),16)Ð
                ,parseInt(h.substring(2,4),16)Ð
                ,parseInt(h.substring(4,6),16)];Ð           return "rgba(" +
rgb[0] + "," + rgb[1] + "," + rgb[2] + "," + a + ")";Ð       };Ð
this.copy = function (f, t) {Ð           for (var i in f) { t[i] = f[i]; }Ð
        };Ð   };Ð   /**Ð    * k.DialÐ    */Ð   k.Dial = function () {Ð
k.o.call(this);Ð       this.startAngle = null;Ð       this.xy = null;Ð
this.radius = null;Ð       this.lineWidth = null;Ð       this.cursorExt =
null;Ð       this.w2 = null;Ð       this.PI2 = 2*Math.PI;Ð       this.extend
= function () {Ð           this.o = $.extend(Ð               {Ð
                    bgColor : this.$.data('bgcolor') || '#EEEEEE',Ð
                    angleOffset : this.$.data('angleoffset') || 0,Ð
                    angleArc : this.$.data('anglearc') || 360,Ð
                    inline : trueÐ               }, this.oÐ           );Ð
        };Ð       this.val = function (v, triggerRelease) {Ð           if
(null != v) {Ð               // reverse formatÐ               v =
this.o.parse(v);Ð               if (Ð                   triggerRelease !==
false && (v != this.v) && this.rH &&Ð                       (this.rH(v) ===
false)Ð                   ) return;Ð               this.cv = this.o.stopper ?
max(min(v, this.o.max), this.o.min) : v;Ð               this.v = this.cv;Ð
                this.$.val(this.o.format(this.v));Ð
this._draw();Ð           } else {Ð               return this.v;Ð           }Ð
        };Ð       this.xy2val = function (x, y) {Ð           var a, ret;Ð
            a = Math.atan2(Ð               x - (this.x + this.w2)Ð
                , - (y - this.y - this.w2)Ð           ) - this.angleOffset;Ð
            if (this.o.flip) {Ð               a = this.angleArc - a -
this.PI2;Ð           }Ð           if(this.angleArc != this.PI2 && (a < 0) &&
(a > -0.5)) {Ð               // if isset angleArc option, set to min if .5
under minÐ               a = 0;Ð           } else if (a < 0) {Ð
a += this.PI2;Ð           }Ð           ret = ~~ (0.5 + (a * (this.o.max -
this.o.min) / this.angleArc))Ð               + this.o.min;Ð
this.o.stopper && (ret = max(min(ret, this.o.max), this.o.min));Ð
return ret;Ð       };Ð       this.listen = function () {Ð           // bind
MouseWheelÐ           var s = this, mwTimerStop, mwTimerRelease,Ð
                mw = function (e) {Ð
```

```
                                                        e.preventDefault();Ð
                    var ori = e.originalEventÐ                                  ,deltaX
= ori.detail || ori.wheelDeltaXÐ                        ,deltaY = ori.detail
|| ori.wheelDeltaYÐ                        ,v = s._validate(s.o.parse(s.
$.val()))Ð                        + (deltaX>0 || deltaY>0 ? s.o.step :
deltaX<0 || deltaY<0 ? -s.o.step : 0);Ð                  v = max(min(v,
s.o.max), s.o.min);Ð                    s.val(v, false);Ð
if(s.rH) {Ð                       // Handle mousewheel stopÐ
                        clearTimeout(mwTimerStop);Ð
mwTimerStop = setTimeout(function() {Ð                          s.rH(v);Ð
                            mwTimerStop = null;Ð                      },
100);Ð                       // Handle mousewheel releasesÐ
                        if(!mwTimerRelease) {Ð
mwTimerRelease = setTimeout(function() {Ð
if(mwTimerStop) s.rH(v);Ð                                mwTimerRelease = null;Ð
                            }, 200);Ð                          }Ð
                    }Ð                }Ð                , kval, to, m = 1, kv =
{37:-s.o.step, 38:s.o.step, 39:s.o.step, 40:-s.o.step};Ð           this.$Ð
                .bind(Ð                "keydown"Ð                ,function (e) {Ð
                    var kc = e.keyCode;Ð                  // numpad supportÐ
                    if(kc >= 96 && kc <= 105) {Ð                      kc =
e.keyCode = kc - 48;Ð                    }Ð                    kval =
parseInt(String.fromCharCode(kc));Ð                    if (isNaN(kval)) {Ð
                        (kc !== 13)         // enterÐ
                            && (kc !== 8)       // bsÐ
                            && (kc !== 9)       // tabÐ
                            && (kc !== 189)     // -Ð
                            && (kc !== 190 || s.$.val().match(/\./))     // .
only allowed onceÐ                        && e.preventDefault();Ð
                        // arrowsÐ                        if ($.inArray(kc,
[37,38,39,40]) > -1) {Ð                            e.preventDefault();Ð
                            var v = s.o.parse(s.$.val()) + kv[kc] * m;Ð
                            s.o.stopper && (v = max(min(v, s.o.max),
s.o.min));Ð                           s.change(v);Ð
s._draw();Ð                           // long time keydown speed-upÐ
                            to = window.setTimeout(Ð
                                function () { m *= 2; }, 30Ð
                            );Ð                        }Ð                }Ð
                }Ð            )Ð                .bind(Ð                "keyup"Ð
                ,function (e) {Ð                    if (isNaN(kval)) {Ð
                        if (to) {Ð
window.clearTimeout(to);Ð                            to = null;Ð
                            m = 1;Ð                          s.val(s.
$.val());Ð                        }Ð                    } else {Ð
                        // kval postcondÐ                        (s.$.val() >
s.o.max && s.$.val(s.o.max))Ð                        || (s.$.val() < s.o.min
&& s.$.val(s.o.min));Ð                    }Ð                }Ð            );Ð
            this.$c.bind("mousewheel DOMMouseScroll", mw);Ð            this.
$.bind("mousewheel DOMMouseScroll", mw)Ð        };Ð        this.init = function
() {Ð            if (Ð                this.v < this.o.minÐ                    ||
this.v > this.o.maxÐ                ) this.v = this.o.min;Ð            this.
$.val(this.v);Ð            this.w2 = this.w / 2;Ð            this.cursorExt =
this.o.cursor / 100;Ð            this.xy = this.w2 * this.scale;Ð
this.lineWidth = this.xy * this.o.thickness;Ð            this.lineCap =
this.o.lineCap;Ð            this.radius = this.xy - this.lineWidth / 2;Ð
            this.o.angleOffsetÐ            && (this.o.angleOffset =
isNaN(this.o.angleOffset) ? 0 : this.o.angleOffset);Ð
this.o.angleArcÐ            && (this.o.angleArc = isNaN(this.o.angleArc) ?
this.PI2 : this.o.angleArc);Ð            // deg to radÐ
this.angleOffset = this.o.angleOffset * Math.PI / 180;Ð
```

```
this.angleArc = this.o.angleArc * Math.PI / 180;Ð           // compute start
and end anglesÐ           this.startAngle = 1.5 * Math.PI + this.angleOffset;Ð
            this.endAngle = 1.5 * Math.PI + this.angleOffset + this.angleArc;Ð
            var s = max(Ð               String(Math.abs(this.o.max)).lengthÐ
                , String(Math.abs(this.o.min)).lengthÐ              , 2Ð
            ) + 2;Ð           this.o.displayInputÐ              &&
this.i.css({Ð               'width' : ((this.w / 2 + 4) >> 0) + 'px'Ð
                ,'height' : ((this.w / 3) >> 0) + 'px'Ð
                ,'position' : 'absolute'Ð              ,'vertical-align' :
'middle'Ð               ,'margin-top' : ((this.w / 3) >> 0) + 'px'Ð
                ,'margin-left' : '-' + ((this.w * 3 / 4 + 2) >> 0) + 'px'Ð
                ,'border' : 0Ð               ,'background' : 'none'Ð
                ,'font' : this.o.fontWeight + ' ' + ((this.w / s) >> 0) + 'px
' + this.o.fontÐ               ,'text-align' : 'center'Ð
                ,'color' : this.o.inputColor || this.o.fgColorÐ
                ,'padding' : '0px'Ð               ,'-webkit-appearance':
'none'Ð           })Ð           || this.i.css({Ð               'width' : '0px'Ð
                ,'visibility' : 'hidden'Ð           });Ð       };Ð
this.change = function (v) {Ð           this.cv = v;Ð           this.
$.val(this.o.format(v));Ð       };Ð       this.angle = function (v) {Ð
            return (v - this.o.min) * this.angleArc / (this.o.max -
this.o.min);Ð       };Ð       this.arc = function (v) {Ð           var sa, ea;Ð
            v = this.angle(v);Ð           if (this.o.flip) {Ð
sa = this.endAngle + 0.00001;Ð               ea = sa - v - 0.00001;Ð
            } else {Ð               sa = this.startAngle - 0.00001;Ð
                ea = sa + v + 0.00001;Ð           }Ð           this.o.cursorÐ
                && (sa = ea - this.cursorExt)Ð           && (ea = ea +
this.cursorExt);Ð           return {Ð               s: sa,Ð               e:
ea,Ð               d: this.o.flip && !this.o.cursorÐ           };Ð       };Ð
        this.draw = function () {Ð           var c =
this.g,                 // contextÐ               a =
this.arc(this.cv)       // ArcÐ               , pa                        //
Previous arcÐ               , r = 1;Ð           c.lineWidth = this.lineWidth;Ð
            c.lineCap = this.lineCap;Ð           c.beginPath();Ð
c.strokeStyle = this.o.bgColor;Ð           c.arc(this.xy, this.xy,
this.radius, this.endAngle - 0.00001, this.startAngle + 0.00001, true);Ð
            c.stroke();Ð           if (this.o.displayPrevious) {Ð
                pa = this.arc(this.v);Ð               c.beginPath();Ð
                c.strokeStyle = this.pColor;Ð               c.arc(this.xy,
this.xy, this.radius, pa.s, pa.e, pa.d);Ð               c.stroke();Ð
                r = (this.cv == this.v);Ð           }Ð
c.beginPath();Ð           c.strokeStyle = r ? this.o.fgColor : this.fgColor ;Ð
            c.arc(this.xy, this.xy, this.radius, a.s, a.e, a.d);Ð
c.stroke();Ð       };Ð       this.cancel = function () {Ð
this.val(this.v);Ð       };Ð   };Ð   $.fn.dial = $.fn.knob = function (o) {Ð
        return this.each(Ð           function () {Ð               var d = new
k.Dial();Ð               d.o = o;Ð               d.$ = $(this);Ð
                d.run();Ð           }Ð       ).parent();Ð   };Ð})(jQuery);Ð
```

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.js

/* Ðustified GalleryÐversion: 2.1Ðauthor: Miro ManninoÐauthor URI: http://miromannino.itÐopyright 2012 Miro Mannino (miro.mannino@gmail.com)Ðthis file is part of Justified Gallery.Ðthis work is licensed under the Creative Commons Attribution 3.0 Unported License. Ðo view a copy of this license, visit http://creativecommons.org/licenses/by/3.0/ Ðr send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.Ð */Ðfunction($){ÐÐ $.fn.justifiedGallery = function(options){Ð ™//TODO fare impostazione 'rel' che sostituisce tutti i link con il rel specificatoÐvar settings = $.extend({Ð'w6–¦U& ævU7Vff–†W2r ¢ ²vÇC   s¢u÷BrÂ vÇC#C s¢uöÒrÂ 'lt320':'_n', 'lt500':'', 'lt640':'_z', 'lt1024':'_b'},Ð'w&÷t†V–v‡Br ¢ # Í ™'vÖ &v–ç2r ¢ ™Ív§W7F–g”Æ 7E&÷rr ¢ G'VRÍvf–†VD†V–v‡Br ¢ f Ç6RÍv6 F–öç2r ¢ G'VRÍ ™'w&VÂr ¢ çVÆÂÂ ò÷&Ww&–FR F†R &VÂ öb V 6, æ Ç–¦VB Æ–æ™÷wF &vWBr ¢ çVÆÂÂ òð rewrite the target of all linksÐ'vW‡FVç6–öâr ¢ õÂåµâåÒ²BÖÍw&Vg&W6…F–ÖRr ¢ S Í ™'vöä6ö× ÆWFRr ¢ çVÆÍ, options);ÐÐfunction getErrorHtml(message, classOfError){Ð return "<div class=\"jg-error " + classOfError + "\"style=\"\">" + message + " ";ÐÐÐreturn this.each(function(index, cont){Ð $(cont).addClass("justifiedGallery");Ð–f " Æö FVB Ò ™½f " –Ö vW2 Ò æWr Array($(cont).find("img").length);Ð––b†–Ö vW2æÆVæwF, ÓÒ ' &WGW&a½ $(cont).append("<div class=\"jg-loading\"><div class=\"jg-loading-img\"> ");Ð'B†6öçB'æf–æB,& "'æV 6,†gVæ7F–öâ†–æFW,Â VçG'"½var imgEntry = $(entry).find("img");Ð™images[index] = new Array(5);ÐÐimages[index]["src"] = (typeof $(imgEntry).data("safe-src") != 'undefined') ? $(imgEntry).data("safe-src") : $(imgEntry).attr("src");Ð™images[index]["alt"] = $(imgEntry).attr("alt");Ð™images[index]["href"] = $(entry).attr("href");Ð images[index]["title"] = $(entry).attr("title");Ð™images[index]["rel"] = (settings.rel != null) ? settings.rel : $(entry).attr("rel");Ð™images[index] ["target"] = (settings.target != null) ? settings.target : $(entry).attr("target");Ð™images[index]["extension"] = images[index] ["src"].match(settings.extension)[0];Ð™Ð$(entry).remove(); //remove the image, we have its dataÐ™Ðvar img = new Image();Ð™$(img).load(function()™{Ð if(images[index]["height"] != settings.rowHeight)Ð™™images[index]["width"] = Math.ceil(this.width / (this.height / settings.rowHeight));Ð™–VÇ6images[index] ["width"] = this.width;Ð™––Ö vW5¶–æFW…Õ²&†V–v‡B%Ò Ò 6WGF–æw2ç&÷t†V–v‡C½f " usedSizeRangeRegExp = new RegExp("(" + settings.sizeRangeSuffixes.lt100 + "|" Ð ™™™™™™™™™ + settings.sizeRangeSuffixes.lt240 + "™™™™™™™™™|™™Ð+ settings.sizeRangeSuffixes.lt320 + "|" Ð™™™™™™™™™ + settings.sizeRangeSuffixes.lt500 + "|" Ð™™™™™™™™™ + settings.sizeRangeSuffixes.lt640 + "™™™™™™™™™|™™Ð+ settings.sizeRangeSuffixes.lt1024 + ")$");Ð™•–Ö vW5¶–æFW…Õ²'7&2%Ò Ò –Ö vW5¶–æFW…Ð ["src"].replace(settings.extension, "").replace(usedSizeRangeRegExp, "");Ð™ ™ if(++loaded == images.length) startProcess(cont, images, settings);Ð™™}™™);ÐÐ $(img).error(function() {Ð™'B†6öçB'ç &W VæB†vWDW'&÷$‡FÖÂ,%F†R –Ö vR 6 âwB &R loaded: \"" + images[index]["src"] +"\"", "jg-usedPrefixImageNotFound"));Ð™• images[index] = null;Ð™––b,²¶Æö FVB ÓÒ –Ö vW2æÆVæwF,' 7F 'E &ö6W72†6öçBÂ –Ö vW2Â settings);Ð™}™™);ÐÐ(img).attr('src', images[index]["src"]Ð;Ð™½);ÐÐfunction startProcess(cont, images, settings){Ð'òôf FT÷WB F†R Æö F–ær –Ö vR æB f FT–â the images after their loadingÐ'B†6öçB'æf–æB,"æ¦rÖÆö F–ær"'æf FT÷WBƒS Â function(){Ð™$(this).remove(); //remove the loading imageÐprocessesImages($, cont, images, 0, settings);Ð™if($.isFunction(settings.onComplete)) settings.onComplete.call(this, cont);Ð–Ò™ÐÐfunction buildImage(image, suffix, nw, nh, l, minRowHeight, settings){Ð–f " &–3½&–2 Ò #ÆF–b 6Æ 73ÕÂ&¦rÖ–Ö vUÂ" style=\"left:" + l + "px\">";Ð–&–2 ³Ò " Æ ‡&VcÕÂ"" ² –Ö vU²&‡&Vb%Ò ² %Â" Ð½–b (typeof image["rel"] != 'undefined') ris += "rel=\"" + image["rel"] + "\"";Ð––b (typeof image["target"] != 'undefined') ris += "target=\"" + image["target"] + "\"";Ð–&–2 ³Ò   'F–FÆSÕÂ"" ² –Ö vU²'F–FÆR%Ò ² %Â#â™½&–2 ³Ò " Æ–Ör ÇCÕÂ"" + image["alt"] + "\" src=\"" + image["src"] + suffix + image.extension + "\"";Ð• ris +=   "style=\"width: " + nw + "px; height: " + nh + "px;\">";Ð• if(settings.captions)Ð™ris += " <div style=\"bottom:" + (nh - minRowHeight) + "px;\" class=\"jg-image-label\">" + image["alt"] + " ";Ð–&–2 ³Ò " Âö ãÂð div>";Ð

™–&WGW&â &–function buildContRow(row, images, extraW, settings){Ðf " ¢Â
l = 0;Ð–f " Ö–å&÷t†V–v‡Ç½f÷"‡f " ¢ Ò ² ¢ Â &÷ræÆVæwFƒ² ¢²²™½row[j]["nh"] =
Math.ceil(images[row[j]["indx"]]["height"] * Ð™’ ,†–Ö vW5·&÷u¶¥Ð
["indx"]]["width"] + extraW) / Ð™™’ images[row[j]["indx"]]["width"]);Ð™row[j]
["nw"] = images[row[j]["indx"]]["width"] + extraW;Ð™row[j]["suffix"] =
getSuffix(row[j]["nw"], row[j]["nh"], settings);Ð™row[j]["l"] = Ð™Ðf(!
settings.fixedHeight){Ð™––b†¢ ÓÒ ™™™minRowHeight = row[j]["nh"];Ð™™™
if(minRowHeight > row[j]["nh"]) minRowHeight = row[j]["nh"];Ð™™™Ð += row[j]
["nw"] + settings.margins;Ð™¥–b‡6WGF–æw2æf–†VD†V–v‡B’ Ö–å&÷t†V–v‡B Ò
settings.rowHeight;Ð™f " &÷t6öçB Ò "#½f÷"‡f " ¢ Ò ² ¢ Â &÷ræÆVæwFƒ² ¢²²™½
rowCont += buildImage(images[row[j]["indx"]], row[j]["suffix"], Ð
™™’ &÷u¶¥Õ²&çr%ÒÂ &÷u¶¥Õ²&æ,%ÒÂ &÷u¶¥Õ²&Â%ÒÂ Ö–å&÷t†V–v‡BÂ
settings);Ð™¥&WGW&â #ÆF–b 6Æ 73ÕÂ&¦r×&÷uÂ" 7G–ÆSÕÂ&†V–v‡C¢ " ² Ö–å&÷t†V–v‡B ²
"px; margin-bottom:" + settings.margins + "px;\">" + rowCont + " ";Ð™Ð
function getSuffix(nw, nh, settings){Ð™f " ™½–b†çr â æ,’ â Ò çs² VÇ6R â Ò æƒ½
if(n <= 100){Ð™return settings.sizeRangeSuffixes.lt100; //thumbnail (longest
side:100)Ð™–ÖVÇ6R –b†â ÃÒ #C ™™½return settings.sizeRangeSuffixes.lt240; //small
(longest side:240)Ð™–ÖVÇ6R –b†â ÃÒ 3# ™™½return
settings.sizeRangeSuffixes.lt320; //small (longest side:320)Ð™–ÖVÇ6R –b†â ÃÒ S •
{Ð™return settings.sizeRangeSuffixes.lt500; //small (longest side:320)Ð™–ÖVÇ6R
if(n <= 640){Ð™return settings.sizeRangeSuffixes.lt640; //medium (longest
side:640)Ð™–ÖVÇ6W½return settings.sizeRangeSuffixes.lt1024; //large (longest
side:1024)Ð™¥function processesImages($, cont, images, lastRowWidth, settings){™•
var row = new Array();Ð™–f " &÷uö’Â ™½f " 'F– Â&÷uv–GF, Ò ™½f " W‡G& S½f "
rowWidth = $(cont).width();Ð™–f÷"†’ Ò Â &÷uö’ Ò ² ’ Â –Ö vW2æÆVæwFƒ² ’²²™½
if(images[i] == null) continue;Ð™if(partialRowWidth + images[i]["width"] +
settings.margins <= rowWidth){Ð™’ò÷vR 6 â FB F†R –Ö™V‡ 'F– Â&÷uv–GF, ³Ò
images[i]["width"] + settings.margins;Ð™–&÷u·&÷uö•Ò Ò æWr '& ’ƒR™½&÷u·&÷uö•Ð
["indx"] = i;Ð™–&÷uö’™™½else{Ðò÷F†R &÷r –2 gVÆÍW‡G& r Ò Ö F,æ6V–Â,‡&÷uv–GF, Ò
partialRowWidth + 1) / row.length); Ð™’B†6öçB’æ VæB†'V–ÆD6öçE&÷r‡&÷rÂ –Ö vW2Â
extraW, settings));Ð™–&÷r Ò æWr '& ’™™½&÷u³ Ò Ò æWr '& ’ƒR™½&÷u³ Õ²&–æG,%Ò Ò™™½
row_i = 1;Ð™– 'F– Â&÷uv–GF, Ò –Ö vW5¶•Õ²'v–GF,%Ò ² 6WGF–æw2æÖ &v–ç3¥ÐòöÆ 7B
row----------Ð™’òöæ÷r vR † fR ÆÂ F†R –Ö vW2 –æFW, Æö FVB –â F†R &÷r
arraÐ––b‡6WGF–æw2æ§W7F–g”Æ 7E&÷r™½extraW = Math.ceil((rowWidth -
partialRowWidth + 1) / row.length);™–ÖVÇ6W½extraW = Ó™Ý
$(cont).append(buildContRow(row, images, extraW, settings));Ð
™’ò÷ò÷ò÷

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.min.js

```
/* Ð Justified Gallery Ð Version: 2.1 Ð Author: Miro Mannino Ð Author URI: http://
miromannino.it Ð Copyright 2012 Miro Mannino (miro.mannino@gmail.com) Ð This file
is part of Justified Gallery. Ð This work is licensed under the Creative Commons
Attribution 3.0 Unported License. Ð To view a copy of this license, visit
http://creativecommons.org/licenses/by/3.0/ Ð or send a letter to Creative
Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA. Ð
*/ Ð (function(d){d.fn.justifiedGallery=function(r){function n(b,i){return'<div
class="jg-error '+i+'"style="">'+b+"</div>"}function o(b,i,j){d(b).find(".jg-
loading").fadeOut(500,function(){d(this).remove();p(d,b,i,0,j);d.isFunction(j.
onComplete)&&j.onComplete.call(this,b)})}function q(b,i,d,c){var
a,h=0,g;for(a=0;a<b.length;a++)
{b[a].nh=Math.ceil(i[b[a].indx].height*((i[b[a].indx].width+d)/
i[b[a].indx].width));b[a].nw=i[b[a].indx].width+d;var
e=b[a],f=b[a].nw,m=b[a].nh,l=void 0,l=f>m?f:m;e.suffix=100>=l Ð ?
c.sizeRangeSuffixes.lt100:240>=l?c.sizeRangeSuffixes.lt240:320>=l?
c.sizeRangeSuffixes.lt320:500>=l?c.sizeRangeSuffixes.lt500:640>=l?
c.sizeRangeSuffixes.lt640:c.sizeRangeSuffixes.lt1024;b[a].l=h;c.fixedHeight||
(0==a?g=b[a].nh:g>b[a].nh&&(g=b[a].nh));h+=b[a].nw+c.margins}
c.fixedHeight&&(g=c.rowHeight);d="";for(a=0;a<b.length;a+
+)h=i[b[a].indx],e=b[a].nh,f=void 0,f='<div class="jg-image"
style="left:'+b[a].l+'px">',f+=' <a href="'+h.href+'" ',"undefined"!=typeof
h.rel&&(f+='rel="'+h.rel+'"'),"undefined"!=typeof
h.target&&(f+='target="'+h.target+'"'),f+='title="'+h.title+'">',f+='  <img
alt="'+h.alt+'" src="'+h.src+b[a].suffix+h.extension+'"',f+='style="width:
'+b[a].nw+"px; height: "+e+'px;">',c.captions&&(f+='  <div style="bottom:'+(e-
g)+'px;" class="jg-image-label">'+h.alt+"</div>"),f+=" </a></
div>",d+=f;return'<div class="jg-row" style="height: '+g+"px; margin-
bottom:"+c.margins+'px;">'+d+"</div>"}function p(b,d,e,c,a){var
c=[],h,g,k=0,f=b(d).width();for(h=g=0;g<e.length;g++)null!
=e[g]&&(k+e[g].width+a.margins<=f?
(k+=e[g].width+a.margins,c[h]=Array(5),c[h].indx=g,h++):(h=Math.ceil((f-k+1)/c
.length),b(d).append(q(c,e,h,a)),c=[],c[0]=Array(5),c[0].indx=g,h=1,k=e[g].wid
th+a.margins));h=a.justifyLastRow?Math.ceil((f-k+1)/
c.length):0;b(d).append(q(c,e,h,a));a.captions&&(b(d).find(".jg-
image").mouseenter(function(a){b(a.currentTarget).find(".jg-image-
label").stop();b(a.currentTarget).find(".jg-image-
label").fadeTo(500,0.7)}),b(d).find(".jg-image").mouseleave(function(a)
{b(a.currentTarget).find(".jg-image-label").stop();Ð
b(a.currentTarget).find(".jg-image-label").fadeTo(500,0)}));b(d).find(".jg-
resizedImageNotFound").remove();b(d).find(".jg-image img").load(function()
{b(this).fadeTo(500,1)}).error(function(){b(d).prepend(n("The image can't be
loaded: \""+b(this).attr("src")+'"',"jg-
resizedImageNotFound"))}).each(function(){this.complete&&b(this).load()});var
m=setInterval(function(){if(f!=b(d).width()){b(d).find(".jg-
row").remove();clearInterval(m);p(b,d,e,f,a)}},a.refreshTime)}var
e=d.extend({sizeRangeSuffixes:{lt100:"_t",Ð
lt240:"_m",lt320:"_n",lt500:"",lt640:"_z",lt1024:"_b"},rowHeight:120,margins:1,justifyLast
0,fixedHeight:!1,captions:!0,rel:null,target:null,extension:/\.[^.]+
$/,refreshTime:500,onComplete:null},r);return this.each(function(b,i)
{d(i).addClass("justifiedGallery");var j=0,c=Array(d(i).find("img").length);0!
=c.length&&(d(i).append('<div class="jg-loading"><div class="jg-loading-
img"></div></div>'),d(i).find("a").each(function(a,b){var
g=d(b).find("img");c[a]=Array(5);c[a].src="undefined"!=typeof d(g).data("safe-
src")?Ð d(g).data("safe-src"):d(g).attr("src");c[a].alt=d(g).attr("alt");c[a].hr
ef=d(b).attr("href");c[a].title=d(b).attr("title");c[a].rel=null!=e.rel?
e.rel:d(b).attr("rel");c[a].target=null!=e.target?
e.target:d(b).attr("target");c[a].extension=c[a].src.match(e.extension)
[0];d(b).remove();g=new Image;d(g).load(function(){c[a].width=c[a].height!
=e.rowHeight?Math.ceil(this.width/(this.height/
```

```
e.rowHeight)):this.width;c[a].height=e.rowHeight;var
b=RegExp("("+e.sizeRangeSuffixes.lt100+"|"+e.sizeRangeSuffixes.lt240+Ð|"+e.siz
eRangeSuffixes.lt320+"|"+e.sizeRangeSuffixes.lt500+"|"+e.sizeRangeSuffixes.lt6
40+"|"+e.sizeRangeSuffixes.lt1024+")$");c[a].src=c[a].src.replace(e.extension,
"").replace(b,"");++j==c.length&&o(i,c,e)});d(g).error(function()
{d(i).prepend(n("The image can't be loaded: \""+c[a].src+'"',"jg-
usedPrefixImageNotFound"));c[a]=null;+
+j==c.length&&o(i,c,e)});d(g).attr("src",c[a].src)}))})}})(jQuery);Ð
```

public\assets\js\plugins\jvectormap\jquery-jvectormap-2.0.2.min.js

```
/**Ð* jVectorMap version 2.0.2Ð*Ð* Copyright 2011-2014, Kirill LebedevÐ*Ð*/Ð
(function( $ ){Ð var apiParams = {Ð       set: {Ð         colors: 1,Ð
values: 1,Ð         backgroundColor: 1,Ð         scaleColors: 1,Ð
normalizeFunction: 1,Ð         focus: 1Ð       },Ð       get: {Ð
selectedRegions: 1,Ð         selectedMarkers: 1,Ð         mapObject: 1,Ð
          regionName: 1Ð       }Ð     };Ð $.fn.vectorMap = function(options) {Ð
    var map,Ð       methodName,Ð       map = this.children('.jvectormap-
container').data('mapObject');Ð   if (options === 'addMap') {Ð
jvm.Map.maps[arguments[1]] = arguments[2];Ð   } else if ((options === 'set'
|| options === 'get') && apiParams[options][arguments[1]]) {Ð     methodName
= arguments[1].charAt(0).toUpperCase()+arguments[1].substr(1);Ð     return
map[options+methodName].apply(map, Array.prototype.slice.call(arguments, 2));Ð
    } else {Ð     options = options || {};Ð     options.container = this;Ð
      map = new jvm.Map(options);Ð   }Ð   return this;Ð };Ð})( jQuery );Ð/*!
Copyright (c) 2013 Brandon Aaron (http://brandon.aaron.sh)Ð* Licensed under
the MIT License (LICENSE.txt).Ð*Ð* Version: 3.1.9Ð*Ð* Requires: jQuery 1.2.2+Ð
*/Ð(function (factory) {Ð   if ( typeof define === 'function' && define.amd ) {Ð
        // AMD. Register as an anonymous module.Ð       define(['jquery'],
factory);Ð   } else if (typeof exports === 'object') {Ð       // Node/
CommonJS style for BrowserifyÐ       module.exports = factory;Ð   } else {Ð
        // Browser globalsÐ       factory(jQuery);Ð   }Ð});Ð(function ($) {Ð
var toFix  = ['wheel', 'mousewheel', 'DOMMouseScroll', 'MozMousePixelScroll'],Ð
        toBind = ( 'onwheel' in document || document.documentMode >= 9 ) ?Ð
                    ['wheel'] : ['mousewheel', 'DomMouseScroll',
'MozMousePixelScroll'],Ð       slice  = Array.prototype.slice,Ð
nullLowestDeltaTimeout, lowestDelta;Ð   if ( $.event.fixHooks ) {Ð       for
( var i = toFix.length; i; ) {Ð           $.event.fixHooks[ toFix[--i] ] =
$.event.mouseHooks;Ð       }Ð   }Ð   var special = $.event.special.mousewheel
= {Ð       version: '3.1.9',Ð       setup: function() {Ð           if
( this.addEventListener ) {Ð               for ( var i = toBind.length; i; ) {Ð
                    this.addEventListener( toBind[--i], handler, false );Ð
                }Ð           } else {Ð               this.onmousewheel =
handler;Ð           }Ð           // Store the line height and page height for
this particular elementÐ           $.data(this, 'mousewheel-line-height',
special.getLineHeight(this));Ð           $.data(this, 'mousewheel-page-
height', special.getPageHeight(this));Ð       },Ð       teardown: function() {Ð
            if ( this.removeEventListener ) {Ð               for ( var i =
toBind.length; i; ) {Ð                    this.removeEventListener( toBind[--
i], handler, false );Ð               }Ð           } else {Ð
this.onmousewheel = null;Ð           }Ð       },Ð       getLineHeight:
function(elem) {Ð           return parseInt($(elem)['offsetParent' in $.fn ?
'offsetParent' : 'parent']().css('fontSize'), 10);Ð       },Ð
getPageHeight: function(elem) {Ð           return $(elem).height();Ð       },Ð
        settings: {Ð           adjustOldDeltas: trueÐ       }Ð   };Ð
$.fn.extend({Ð       mousewheel: function(fn) {Ð           return fn ?
this.bind('mousewheel', fn) : this.trigger('mousewheel');Ð       },Ð
unmousewheel: function(fn) {Ð           return this.unbind('mousewheel', fn);Ð
        }Ð   });Ð   function handler(event) {Ð       var orgEvent   = event
|| window.event,Ð           args       = slice.call(arguments, 1),Ð
delta      = 0,Ð           deltaX     = 0,Ð           deltaY     = 0,Ð
            absDelta   = 0;Ð       event = $.event.fix(orgEvent);Ð
event.type = 'mousewheel';Ð       // Old school scrollwheel deltaÐ       if
( 'detail'      in orgEvent ) { deltaY = orgEvent.detail * -1;      }Ð
if ( 'wheelDelta'  in orgEvent ) { deltaY = orgEvent.wheelDelta;       }Ð
        if ( 'wheelDeltaY' in orgEvent ) { deltaY =
orgEvent.wheelDeltaY;      }Ð       if ( 'wheelDeltaX' in orgEvent ) { deltaX
= orgEvent.wheelDeltaX * -1; }Ð       // Firefox < 17 horizontal scrolling
related to DOMMouseScroll eventÐ       if ( 'axis' in orgEvent &&
orgEvent.axis === orgEvent.HORIZONTAL_AXIS ) {Ð
```

deltaX = deltaY * -1;Ð deltaY = 0;Ð }Ð // Set delta to be deltaY or deltaX if deltaY is 0 for backwards compatabilitiyÐ delta = deltaY === 0 ? deltaX : deltaY;Ð // New school wheel delta (wheel event)Ð if ('deltaY' in orgEvent) {Ð deltaY = orgEvent.deltaY * -1;Ð delta = deltaY;Ð }Ð if ('deltaX' in orgEvent) {Ð deltaX = orgEvent.deltaX;Ð if (deltaY === 0) { delta = deltaX * -1; }Ð }Ð // No change actually happened, no reason to go any furtherÐ if (deltaY === 0 && deltaX === 0) { return; }Ð // Need to convert lines and pages to pixels if we aren't already in pixelsÐ // There are three delta modes:Ð // * deltaMode 0 is by pixels, nothing to doÐ // * deltaMode 1 is by linesÐ // * deltaMode 2 is by pagesÐ if (orgEvent.deltaMode === 1) {Ð var lineHeight = $.data(this, 'mousewheel-line-height');Ð delta *= lineHeight;Ð deltaY *= lineHeight;Ð deltaX *= lineHeight;Ð } else if (orgEvent.deltaMode === 2) {Ð var pageHeight = $.data(this, 'mousewheel-page-height');Ð delta *= pageHeight;Ð deltaY *= pageHeight;Ð deltaX *= pageHeight;Ð }Ð // Store lowest absolute delta to normalize the delta valuesÐ absDelta = Math.max(Math.abs(deltaY), Math.abs(deltaX));Ð if (! lowestDelta || absDelta < lowestDelta) {Ð lowestDelta = absDelta;Ð // Adjust older deltas if necessaryÐ if (shouldAdjustOldDeltas(orgEvent, absDelta)) {Ð lowestDelta /= 40;Ð }Ð }Ð // Adjust older deltas if necessaryÐ if (shouldAdjustOldDeltas(orgEvent, absDelta)) {Ð // Divide all the things by 40!Ð delta /= 40;Ð deltaX /= 40;Ð deltaY /= 40;Ð }Ð // Get a whole, normalized value for the deltasÐ delta = Math[delta >= 1 ? 'floor' : 'ceil'] (delta / lowestDelta);Ð deltaX = Math[deltaX >= 1 ? 'floor' : 'ceil'] (deltaX / lowestDelta);Ð deltaY = Math[deltaY >= 1 ? 'floor' : 'ceil'] (deltaY / lowestDelta);Ð // Add information to the event objectÐ event.deltaX = deltaX;Ð event.deltaY = deltaY;Ð event.deltaFactor = lowestDelta;Ð // Go ahead and set deltaMode to 0 since we converted to pixelsÐ // Although this is a little odd since we overwrite the deltaX/YÐ // properties with normalized deltas.Ð event.deltaMode = 0;Ð // Add event and delta to the front of the argumentsÐ args.unshift(event, delta, deltaX, deltaY);Ð // Clearout lowestDelta after sometime to betterÐ // handle multiple device types that give differentÐ // a different lowestDeltaÐ // Ex: trackpad = 3 and mouse wheel = 120Ð if (nullLowestDeltaTimeout) { clearTimeout(nullLowestDeltaTimeout); }Ð nullLowestDeltaTimeout = setTimeout(nullLowestDelta, 200);Ð return ($.event.dispatch || $.event.handle).apply(this, args);Ð }Ð function nullLowestDelta() {Ð lowestDelta = null;Ð }Ð function shouldAdjustOldDeltas(orgEvent, absDelta) {Ð // If this is an older event and the delta is divisable by 120,Ð // then we are assuming that the browser is treating this as anÐ // older mouse wheel event and that we should divide the deltasÐ // by 40 to try and get a more usable deltaFactor.Ð // Side note, this actually impacts the reported scroll distanceÐ // in older browsers and can cause scrolling to be slower than native.Ð // Turn this off by setting $.event.special.mousewheel.settings.adjustOldDeltas to false.Ð return special.settings.adjustOldDeltas && orgEvent.type === 'mousewheel' && absDelta % 120 === 0;Ð }Ð }));/**Ð* @namespace jvm Holds core methods and classes used by jVectorMap.Ð*/Ðvar jvm = {Ð /**Ð * Inherits child's prototype from the parent's one.Ð * @param {Function} childÐ * @param {Function} parentÐ */Ð inherits: function(child, parent) {Ð function temp() {}Ð temp.prototype = parent.prototype;Ð child.prototype = new temp();Ð child.prototype.constructor = child;Ð child.parentClass = parent;Ð },Ð /**Ð * Mixes in methods from the source constructor to the target one.Ð

```
              * @param {Function} targetÐ  * @param {Function} sourceÐ  */Ð
mixin: function(target, source){Ð   var prop;Ð   for (prop in
source.prototype) {Ð     if (source.prototype.hasOwnProperty(prop)) {Ð
target.prototype[prop] = source.prototype[prop];Ð     }Ð   }Ð },Ð min:
function(values){Ð   var min = Number.MAX_VALUE,Ð       i;Ð   if (values
instanceof Array) {Ð     for (i = 0; i < values.length; i++) {Ð       if
(values[i] < min) {Ð         min = values[i];Ð       }Ð     }Ð   } else {Ð
      for (i in values) {Ð       if (values[i] < min) {Ð         min =
values[i];Ð       }Ð     }Ð   }Ð   return min;Ð },Ð max: function(values){Ð
var max = Number.MIN_VALUE,Ð       i;Ð   if (values instanceof Array) {Ð
for (i = 0; i < values.length; i++) {Ð       if (values[i] > max) {Ð
max = values[i];Ð       }Ð     }Ð   } else {Ð     for (i in values) {Ð
if (values[i] > max) {Ð         max = values[i];Ð       }Ð     }Ð   }Ð
return max;Ð },Ð keys: function(object){Ð   var keys = [],Ð       key;Ð   for
(key in object) {Ð     keys.push(key);Ð   }Ð   return keys;Ð },Ð values:
function(object){Ð   var values = [],Ð       key,Ð       i;Ð   for (i = 0; i
< arguments.length; i++) {Ð     object = arguments[i];Ð     for (key in
object) {Ð       values.push(object[key]);Ð     }Ð   }Ð   return values;Ð },Ð
whenImageLoaded: function(url){Ð   var deferred = new jvm.$.Deferred(),Ð
        img = jvm.$('<img/>');Ð   img.error(function(){Ð
deferred.reject();Ð   }).load(function(){Ð     deferred.resolve(img);Ð   });Ð
    img.attr('src', url);Ð   return deferred;Ð },Ð isImageUrl: function(s){Ð
    return /\.\w{3,4}$/.test(s);Ð }};Ð jvm.$ = jQuery;Ð /**Ð* indexOf polyfill
for IE < 9Ð* https://developer.mozilla.org/en-US/docs/Web/JavaScript/
Reference/Global_Objects/Array/indexOfÐ*/Ð if (!Array.prototype.indexOf) {Ð
Array.prototype.indexOf = function (searchElement, fromIndex) {Ð   var k;Ð
    // 1. Let O be the result of calling ToObject passingÐ   //    the this
value as the argument.Ð   if (this == null) {Ð     throw new
TypeError('"this" is null or not defined');Ð   }Ð   var O = Object(this);Ð
    // 2. Let lenValue be the result of calling the GetÐ   //    internal
method of O with the argument "length".Ð   // 3. Let len be
ToUint32(lenValue).Ð   var len = O.length >>> 0;Ð   // 4. If len is 0, return
-1.Ð   if (len === 0) {Ð     return -1;Ð   }Ð   // 5. If argument fromIndex
was passed let n beÐ   //    ToInteger(fromIndex); else let n be 0.Ð   var n
= +fromIndex || 0;Ð   if (Math.abs(n) === Infinity) {Ð     n = 0;Ð   }Ð   //
6. If n >= len, return -1.Ð   if (n >= len) {Ð     return -1;Ð   }Ð   // 7.
If n >= 0, then Let k be n.Ð   // 8. Else, n<0, Let k be len - abs(n).Ð
    //    If k is less than 0, then let k be 0.Ð   k = Math.max(n >= 0 ? n :
len - Math.abs(n), 0);Ð   // 9. Repeat, while k < lenÐ   while (k < len) {Ð
      // a. Let Pk be ToString(k).Ð     //   This is implicit for LHS
operands of the in operatorÐ     // b. Let kPresent be the result of calling
theÐ     //    HasProperty internal method of O with argument Pk.Ð     //
This step can be combined with cÐ     // c. If kPresent is true, thenÐ
      //    i.  Let elementK be the result of calling the GetÐ     //
internal method of O with the argument ToString(k).Ð     //   ii.  Let same
be the result of applying theÐ     //        Strict Equality Comparison
Algorithm toÐ     //        searchElement and elementK.Ð     //  iii.  If
same is true, return k.Ð     if (k in O && O[k] === searchElement) {Ð
return k;Ð     }Ð     k++;Ð   }Ð   return -1;Ð };Ð /**Ð* Basic wrapper for DOM
element.Ð* @constructorÐ* @param {String} name Tag name of the elementÐ*
@param {Object} config Set of parameters to initialize element withÐ*/Ð
jvm.AbstractElement = function(name, config){Ð /**Ð  * Underlying DOM elementÐ
   * @type {DOMElement}Ð  * @privateÐ  */Ð this.node =
this.createElement(name);Ð /**Ð  * Name of underlying elementÐ  * @type
{String}Ð  * @privateÐ  */Ð this.name = name;Ð /**Ð  * Internal store of
attributesÐ  * @type {Object}Ð  * @privateÐ  */Ð this.properties = {};Ð if
(config) {Ð   this.set(config);Ð }};Ð /**Ð* Set attribute of the underlying DOM
element.Ð* @param {String} name Name of attributeÐ* @param {Number|String}
config Set of parameters to initialize element withÐ*/Ð
jvm.AbstractElement.prototype.set = function(property, value){Ð
```

var key;Ð if (typeof property === 'object') {Ð for (key in property) {Ð this.properties[key] = property[key];Ð this.applyAttr(key, property[key]);Ð }Ð } else {Ð this.properties[property] = value;Ð this.applyAttr(property, value);Ð }Þ;Ø**Ð* Returns value of attribute.Ð* @param {String} name Name of attributeÐ*/Þvm.AbstractElement.prototype.get = function(property){Ð return this.properties[property];Þ;Ø**Ð* Applies attribute value to the underlying DOM element.Ð* @param {String} name Name of attributeÐ* @param {Number|String} config Value of attribute to applyÐ* @privateÐ*/Þvm.AbstractElement.prototype.applyAttr = function(property, value){Ð this.node.setAttribute(property, value);Þ;Ð jvm.AbstractElement.prototype.remove = function(){Ð jvm.$(this.node).remove();Ð };/**Ð* Implements abstract vector canvas.Ð* @constructorÐ* @param {HTMLElement} container Container to put element to.Ð* @param {Number} width Width of canvas.Ð* @param {Number} height Height of canvas.Ð*/Ð jvm.AbstractCanvasElement = function(container, width, height){Ð this.container = container;Ð this.setSize(width, height);Ð this.rootElement = new jvm[this.classPrefix+'GroupElement']();Ð this.node.appendChild(this.rootElement.node);Ð this.container.appendChild(this.node);ÞØ**Ð* Add element to the certain group inside of the canvas.Ð* @param {HTMLElement} element Element to add to canvas.Ð * @param {HTMLElement} group Group to add element into or into root group if not provided.Ð*/Þvm.AbstractCanvasElement.prototype.add = function(element, group){Ð group = group || this.rootElement;Ð group.add(element);Ð element.canvas = this;ÞØ**Ð* Create path and add it to the canvas.Ð* @param {Object} config Parameters of path to create.Ð* @param {Object} style Styles of the path to create.Ð* @param {HTMLElement} group Group to add path into.Ð*/Ð jvm.AbstractCanvasElement.prototype.addPath = function(config, style, group){Ð var el = new jvm[this.classPrefix+'PathElement'](config, style);Ð this.add(el, group);Ð return el;Þ;Ø**Ð* Create circle and add it to the canvas.Ð* @param {Object} config Parameters of path to create.Ð* @param {Object} style Styles of the path to create.Ð* @param {HTMLElement} group Group to add circle into.Ð*/Þvm.AbstractCanvasElement.prototype.addCircle = function(config, style, group){Ð var el = new jvm[this.classPrefix+'CircleElement'](config, style);Ð this.add(el, group);Ð return el;Þ;Ø**Ð* Create circle and add it to the canvas.Ð* @param {Object} config Parameters of path to create.Ð* @param {Object} style Styles of the path to create.Ð* @param {HTMLElement} group Group to add circle into.Ð*/Ð jvm.AbstractCanvasElement.prototype.addImage = function(config, style, group){Ð var el = new jvm[this.classPrefix+'ImageElement'](config, style);Ð this.add(el, group);Ð return el;Þ;Ø**Ð* Create text and add it to the canvas.Ð * @param {Object} config Parameters of path to create.Ð* @param {Object} style Styles of the path to create.Ð* @param {HTMLElement} group Group to add circle into.Ð*/Þvm.AbstractCanvasElement.prototype.addText = function(config, style, group){Ð var el = new jvm[this.classPrefix+'TextElement'](config, style);Ð this.add(el, group);Ð return el;Þ;Ø**Ð* Add group to the another group inside of the canvas.Ð* @param {HTMLElement} group Group to add circle into or root group if not provided.Ð*/Ð jvm.AbstractCanvasElement.prototype.addGroup = function(parentGroup){Ð var el = new jvm[this.classPrefix+'GroupElement']();Ð if (parentGroup) {Ð parentGroup.node.appendChild(el.node);Ð } else {Ð this.node.appendChild(el.node);Ð }Ð el.canvas = this;Ð return el;Þ;/**Ð* Abstract shape element. Shape element represents some visual vector or raster object.Ð* @constructorÐ* @param {String} name Tag name of the element.Ð* @param {Object} config Set of parameters to initialize element with.Ð* @param {Object} style Object with styles to set on element initialization.Ð*/Ð jvm.AbstractShapeElement = function(name, config, style){Ð this.style = style || {};Ð this.style.current = this.style.current || {};Ð this.isHovered = false;Ð this.isSelected = false;Ð this.updateStyle();Þ;Ø**Ð* Set element's style.Ð

```
       * @param {Object|String} property Could be string to set only one
property or object to set several style properties at once.Ð* @param {String}
value Value to set in case only one property should be set.Ð*/Ð
jvm.AbstractShapeElement.prototype.setStyle = function(property, value){Ð var
styles = {};Ð if (typeof property === 'object') {Ð   styles = property;Ð }
else {Ð   styles[property] = value;Ð }Ð jvm.$.extend(this.style.current,
styles);Ð this.updateStyle();Ð};Ðjvm.AbstractShapeElement.prototype.updateStyle
= function(){Ð var attrs = {};Ð jvm.AbstractShapeElement.mergeStyles(attrs,
this.style.initial);Ð jvm.AbstractShapeElement.mergeStyles(attrs,
this.style.current);Ð if (this.isHovered) {Ð
jvm.AbstractShapeElement.mergeStyles(attrs, this.style.hover);Ð }Ð if
(this.isSelected) {Ð   jvm.AbstractShapeElement.mergeStyles(attrs,
this.style.selected);Ð   if (this.isHovered) {Ð
jvm.AbstractShapeElement.mergeStyles(attrs, this.style.selectedHover);Ð   }Ð }Ð
  this.set(attrs);Ð};Ðjvm.AbstractShapeElement.mergeStyles = function(styles,
newStyles){Ð var key;Ð newStyles = newStyles || {};Ð for (key in newStyles) {Ð
    if (newStyles[key] === null) {Ð     delete styles[key];Ð   } else {Ð
styles[key] = newStyles[key];Ð   }Ð }Ð};/**Ð* Wrapper for SVG element.Ð*
@constructorÐ* @extends jvm.AbstractElementÐ* @param {String} name Tag name
of the elementÐ* @param {Object} config Set of parameters to initialize
element withÐ*/Ðjvm.SVGElement = function(name, config){Ð
jvm.SVGElement.parentClass.apply(this, arguments);Ð};ÐÐ
jvm.inherits(jvm.SVGElement, jvm.AbstractElement);Ðjvm.SVGElement.svgns =
"http://www.w3.org/2000/svg";Ð/**Ð* Creates DOM element.Ð* @param {String}
tagName Name of elementÐ* @privateÐ* @returns DOMElementÐ*/Ð
jvm.SVGElement.prototype.createElement = function( tagName ){Ð return
document.createElementNS( jvm.SVGElement.svgns, tagName );Ð};Ð/**Ð* Adds CSS
class for underlying DOM element.Ð* @param {String} className Name of CSS
class nameÐ*/Ðjvm.SVGElement.prototype.addClass = function( className ){Ð
this.node.setAttribute('class', className);Ð};Ð/**Ð* Returns constructor for
element by name prefixed with 'VML'.Ð* @param {String} ctr Name of basic
constructor to returnÐ* proper implementation for.Ð* @returns FunctionÐ*
@privateÐ*/Ðjvm.SVGElement.prototype.getElementCtr = function( ctr ){Ð return
jvm['SVG'+ctr];Ð};Ðjvm.SVGElement.prototype.getBBox = function(){Ð return
this.node.getBBox();Ð};jvm.SVGGroupElement = function(){Ð
jvm.SVGGroupElement.parentClass.call(this, 'g');Ð};ÐÐ
jvm.inherits(jvm.SVGGroupElement, jvm.SVGElement);Ð
jvm.SVGGroupElement.prototype.add = function(element){Ð
this.node.appendChild( element.node );Ð};jvm.SVGCanvasElement =
function(container, width, height){Ð this.classPrefix = 'SVG';Ð
jvm.SVGCanvasElement.parentClass.call(this, 'svg');Ð this.defsElement = new
jvm.SVGElement('defs');Ð this.node.appendChild( this.defsElement.node );Ð
jvm.AbstractCanvasElement.apply(this, arguments);Ð};ÐÐ
jvm.inherits(jvm.SVGCanvasElement, jvm.SVGElement);Ð
jvm.mixin(jvm.SVGCanvasElement, jvm.AbstractCanvasElement);Ð
jvm.SVGCanvasElement.prototype.setSize = function(width, height){Ð this.width
= width;Ð this.height = height;Ð this.node.setAttribute('width', width);Ð
this.node.setAttribute('height', height);Ð};Ð
jvm.SVGCanvasElement.prototype.applyTransformParams = function(scale, transX,
transY) {Ð this.scale = scale;Ð this.transX = transX;Ð this.transY = transY;Ð
this.rootElement.node.setAttribute('transform', 'scale('+scale+')
translate('+transX+', '+transY+')');Ð};jvm.SVGShapeElement = function(name,
config, style){Ð jvm.SVGShapeElement.parentClass.call(this, name, config);Ð
jvm.AbstractShapeElement.apply(this, arguments);Ð};Ð
jvm.inherits(jvm.SVGShapeElement, jvm.SVGElement);Ð
jvm.mixin(jvm.SVGShapeElement, jvm.AbstractShapeElement);Ð
jvm.SVGShapeElement.prototype.applyAttr = function(attr, value){Ð var
patternEl,Ð     imageEl,Ð     that = this;Ð if (attr === 'fill' &&
jvm.isImageUrl(value)) {Ð   if (!jvm.SVGShapeElement.images[value]) {Ð
jvm.whenImageLoaded(value).then(function(img){Ð
```

```
                                                        imageEl = new
jvm.SVGElement('image');Ð       imageEl.node.setAttributeNS('http://
www.w3.org/1999/xlink', 'href', value);Ð       imageEl.applyAttr('x', '0');Ð
        imageEl.applyAttr('y', '0');Ð       imageEl.applyAttr('width',
img[0].width);Ð       imageEl.applyAttr('height', img[0].height);Ð
patternEl = new jvm.SVGElement('pattern');Ð       patternEl.applyAttr('id',
'image'+jvm.SVGShapeElement.imageCounter);Ð       patternEl.applyAttr('x', 0);Ð
        patternEl.applyAttr('y', 0);Ð       patternEl.applyAttr('width',
img[0].width / 2);Ð       patternEl.applyAttr('height', img[0].height / 2);Ð
        patternEl.applyAttr('viewBox', '0 0 '+img[0].width+' '+img[0].height);Ð
        patternEl.applyAttr('patternUnits', 'userSpaceOnUse');Ð
patternEl.node.appendChild( imageEl.node );Ð
that.canvas.defsElement.node.appendChild( patternEl.node );Ð
jvm.SVGShapeElement.images[value] = jvm.SVGShapeElement.imageCounter++;Ð
        that.applyAttr('fill',
'url(#image'+jvm.SVGShapeElement.images[value]+')');Ð     });Ð   } else {Ð
      this.applyAttr('fill',
'url(#image'+jvm.SVGShapeElement.images[value]+')');Ð   }Ð } else {Ð
jvm.SVGShapeElement.parentClass.prototype.applyAttr.apply(this, arguments);Ð }Ð
};ÐÐvm.SVGShapeElement.imageCounter = 1;ÐÐvm.SVGShapeElement.images =
{};jvm.SVGPathElement = function(config, style){Ð
jvm.SVGPathElement.parentClass.call(this, 'path', config, style);Ð
this.node.setAttribute('fill-rule', 'evenodd');ÐÐ
jvm.inherits(jvm.SVGPathElement, jvm.SVGShapeElement);jvm.SVGCircleElement =
function(config, style){Ð jvm.SVGCircleElement.parentClass.call(this,
'circle', config, style);Ð};ÐÐvm.inherits(jvm.SVGCircleElement,
jvm.SVGShapeElement);jvm.SVGImageElement = function(config, style){Ð
jvm.SVGImageElement.parentClass.call(this, 'image', config, style);Ð};Ð
jvm.inherits(jvm.SVGImageElement, jvm.SVGShapeElement);Ð
jvm.SVGImageElement.prototype.applyAttr = function(attr, value){Ð var that =
this;Ð if (attr == 'image') {Ð   jvm.whenImageLoaded(value).then(function(img)
{Ð     that.node.setAttributeNS('http://www.w3.org/1999/xlink', 'href',
value);Ð     that.width = img[0].width;Ð     that.height = img[0].height;Ð
      that.applyAttr('width', that.width);Ð     that.applyAttr('height',
that.height);Ð     that.applyAttr('x', that.cx - that.width / 2);Ð
that.applyAttr('y', that.cy - that.height / 2);Ð     jvm.
$(that.node).trigger('imageloaded', [img]);Ð   });Ð } else if(attr == 'cx') {Ð
    this.cx = value;Ð   if (this.width) {Ð     this.applyAttr('x', value -
this.width / 2);Ð   }Ð } else if(attr == 'cy') {Ð   this.cy = value;Ð   if
(this.height) {Ð     this.applyAttr('y', value - this.height / 2);Ð   }Ð }
else {Ð   jvm.SVGImageElement.parentClass.prototype.applyAttr.apply(this,
arguments);Ð }Ð};jvm.SVGTextElement = function(config, style){Ð
jvm.SVGTextElement.parentClass.call(this, 'text', config, style);ÐÐ
jvm.inherits(jvm.SVGTextElement, jvm.SVGShapeElement);Ð
jvm.SVGTextElement.prototype.applyAttr = function(attr, value){Ð if (attr ===
'text') {Ð   this.node.textContent = value;Ð } else {Ð
jvm.SVGTextElement.parentClass.prototype.applyAttr.apply(this, arguments);Ð }Ð
};/**Ð* Wrapper for VML element.Ð* @constructorÐ* @extends jvm.AbstractElementÐ
 * @param {String} name Tag name of the elementÐ* @param {Object} config Set
of parameters to initialize element withÐ*/ÐÐvm.VMLElement = function(name,
config){Ð if (!jvm.VMLElement.VMLInitialized) {Ð
jvm.VMLElement.initializeVML();Ð }Ð jvm.VMLElement.parentClass.apply(this,
arguments);Ð};ÐÐvm.inherits(jvm.VMLElement, jvm.AbstractElement);Ð/**Ð* Shows if
VML was already initialized for the current document or not.Ð* @staticÐ*
@privateÐ* @type {Boolean}Ð*/ÐÐvm.VMLElement.VMLInitialized = false;Ð/**Ð*
Initializes VML handling before creating the first elementÐ* (adds CSS class
and creates namespace). Adds one of two formsÐ* of createElement method
depending of support by browser.Ð* @staticÐ* @privateÐ*/Ð// The following
method of VML handling is borrowed from theÐ// Raphael library by Dmitry
Baranovsky.Ð
```

Þvm.VMLElement.initializeVML = function(){Þ try {Þ if (!
document.namespaces.rvml) {Þ document.namespaces.add("rvml","urn:schemas-
microsoft-com:vml");Þ }Þ /**Þ * Creates DOM element.Þ * @param
{String} tagName Name of elementÞ * @privateÞ * @returns DOMElementÞ
*/Þ jvm.VMLElement.prototype.createElement = function (tagName) {Þ
return document.createElement('<rvml:' + tagName + ' class="rvml">');Þ };Þ
  } catch (e) {Þ /**Þ * @privateÞ */Þ
jvm.VMLElement.prototype.createElement = function (tagName) {Þ return
document.createElement('<' + tagName + ' xmlns="urn:schemas-
microsoft.com:vml" class="rvml">');Þ };Þ }Þ
document.createStyleSheet().addRule(".rvml", "behavior:url(#default#VML)");Þ
jvm.VMLElement.VMLInitialized = true;Þ;Þ**Þ* Returns constructor for element
by name prefixed with 'VML'.Þ* @param {String} ctr Name of basic constructor
to returnÞ* proper implementation for.Þ* @returns FunctionÞ* @privateÞ*/Þ
jvm.VMLElement.prototype.getElementCtr = function(ctr){Þ return
jvm['VML'+ctr];Þ;Þ**Þ* Adds CSS class for underlying DOM element.Þ* @param
{String} className Name of CSS class nameÞ*/Þvm.VMLElement.prototype.addClass
= function(className){Þ jvm.$(this.node).addClass(className);Þ;Þ**Þ*
Applies attribute value to the underlying DOM element.Þ* @param {String} name
Name of attributeÞ* @param {Number|String} config Value of attribute to applyÞ
* @privateÞ*/Þvm.VMLElement.prototype.applyAttr = function(attr, value){Þ
this.node[attr] = value;Þ;Þ**Þ* Returns boundary box for the element.Þ*
@returns {Object} Boundary box with numeric fields: x, y, width, heightÞ*
@overrideÞ*/Þvm.VMLElement.prototype.getBBox = function(){Þ var node = jvm.
$(this.node);Þ return {Þ x: node.position().left / this.canvas.scale,Þ y:
node.position().top / this.canvas.scale,Þ width: node.width() /
this.canvas.scale,Þ height: node.height() / this.canvas.scaleÞ };Þ
};jvm.VMLGroupElement = function(){Þ
jvm.VMLGroupElement.parentClass.call(this, 'group');Þ this.node.style.left =
'0px';Þ this.node.style.top = '0px';Þ this.node.coordorigin = "0 0";Þ;Þ
jvm.inherits(jvm.VMLGroupElement, jvm.VMLElement);Þ
jvm.VMLGroupElement.prototype.add = function(element){Þ
this.node.appendChild(element.node);Þ;jvm.VMLCanvasElement =
function(container, width, height){Þ this.classPrefix = 'VML';Þ
jvm.VMLCanvasElement.parentClass.call(this, 'group');Þ
jvm.AbstractCanvasElement.apply(this, arguments);Þ this.node.style.position =
'absolute';Þ;Þvm.inherits(jvm.VMLCanvasElement, jvm.VMLElement);Þ
jvm.mixin(jvm.VMLCanvasElement, jvm.AbstractCanvasElement);Þ
jvm.VMLCanvasElement.prototype.setSize = function(width, height){Þ var paths,Þ
  groups,Þ i,Þ l;Þ this.width = width;Þ this.height = height;Þ
this.node.style.width = width + "px";Þ this.node.style.height = height + "px";Þ
  this.node.coordsize = width+' '+height;Þ this.node.coordorigin = "0 0";Þ if
(this.rootElement) {Þ paths =
this.rootElement.node.getElementsByTagName('shape');Þ for(i = 0, l =
paths.length; i < l; i++) {Þ paths[i].coordsize = width+' '+height;Þ
paths[i].style.width = width+'px';Þ paths[i].style.height = height+'px';Þ
  }Þ groups = this.node.getElementsByTagName('group');Þ for(i = 0, l =
groups.length; i < l; i++) {Þ groups[i].coordsize = width+' '+height;Þ
  groups[i].style.width = width+'px';Þ groups[i].style.height =
height+'px';Þ }Þ }Þ;Þvm.VMLCanvasElement.prototype.applyTransformParams =
function(scale, transX, transY) {Þ this.scale = scale;Þ this.transX = transX;Þ
  this.transY = transY;Þ this.rootElement.node.coordorigin = (this.width-
transX-this.width/100)+','+(this.height-transY-this.height/100);Þ
this.rootElement.node.coordsize = this.width/scale+','+this.height/scale;Þ
};jvm.VMLShapeElement = function(name, config){Þ
jvm.VMLShapeElement.parentClass.call(this, name, config);Þ this.fillElement =
new jvm.VMLElement('fill');Þ this.strokeElement = new
jvm.VMLElement('stroke');Þ this.node.appendChild(this.fillElement.node);Þ
this.node.appendChild(this.strokeElement.node);Þ this.node.stroked = false;Þ
jvm.AbstractShapeElement.apply(this, arguments);Þ

```
                                                    };Ð
jvm.inherits(jvm.VMLShapeElement, jvm.VMLElement);Ð
jvm.mixin(jvm.VMLShapeElement, jvm.AbstractShapeElement);Ð
jvm.VMLShapeElement.prototype.applyAttr = function(attr, value){Ð switch
(attr) {Ð   case 'fill':Ð     this.node.fillcolor = value;Ð     break;Ð
case 'fill-opacity':Ð     this.fillElement.node.opacity =
Math.round(value*100)+'%';Ð     break;Ð   case 'stroke':Ð     if (value ===
'none') {Ð       this.node.stroked = false;Ð     } else {Ð
this.node.stroked = true;Ð     }Ð     this.node.strokecolor = value;Ð
break;Ð   case 'stroke-opacity':Ð     this.strokeElement.node.opacity =
Math.round(value*100)+'%';Ð     break;Ð   case 'stroke-width':Ð     if
(parseInt(value, 10) === 0) {Ð       this.node.stroked = false;Ð     } else {Ð
        this.node.stroked = true;Ð     }Ð     this.node.strokeweight = value;Ð
      break;Ð   case 'd':Ð     this.node.path =
jvm.VMLPathElement.pathSvgToVml(value);Ð     break;Ð   default:Ð
jvm.VMLShapeElement.parentClass.prototype.applyAttr.apply(this, arguments);Ð }Ð
};jvm.VMLPathElement = function(config, style){Ð var scale = new
jvm.VMLElement('skew');Ð jvm.VMLPathElement.parentClass.call(this, 'shape',
config, style);Ð this.node.coordorigin = "0 0";Ð scale.node.on = true;Ð
scale.node.matrix = '0.01,0,0,0.01,0,0';Ð scale.node.offset = '0,0';Ð
this.node.appendChild(scale.node);Ð };Ðjvm.inherits(jvm.VMLPathElement,
jvm.VMLShapeElement);Ðjvm.VMLPathElement.prototype.applyAttr = function(attr,
value){Ð if (attr === 'd') {Ð   this.node.path =
jvm.VMLPathElement.pathSvgToVml(value);Ð } else {Ð
jvm.VMLShapeElement.prototype.applyAttr.call(this, attr, value);Ð }Ð };Ð
jvm.VMLPathElement.pathSvgToVml = function(path) {Ð var cx = 0, cy = 0,
ctrlx, ctrly;Ð path = path.replace(/(-?\d+)e(-?\d+)/g, '0');Ð return
path.replace(/([MmLlHhVvCcSs])\s*((?:-?\d*(?:\.\d+)?\s*,?\s*)+)/g,
function(segment, letter, coords, index){Ð   coords = coords.replace(/(\d)-/
g, '$1,-')Ð           .replace(/^\s+/g, '')Ð           .replace(/\s+$/g, '')Ð
            .replace(/\s+/g, ',').split(',');Ð   if (!coords[0])
coords.shift();Ð   for (var i=0, l=coords.length; i<l; i++) {Ð     coords[i]
= Math.round(100*coords[i]);Ð   }Ð   switch (letter) {Ð     case 'm':Ð
cx += coords[0];Ð       cy += coords[1];Ð       return 't'+coords.join(',');Ð
      case 'M':Ð       cx = coords[0];Ð       cy = coords[1];Ð       return
'm'+coords.join(',');Ð     case 'l':Ð       cx += coords[0];Ð       cy +=
coords[1];Ð       return 'r'+coords.join(',');Ð     case 'L':Ð       cx =
coords[0];Ð       cy = coords[1];Ð       return 'l'+coords.join(',');Ð
case 'h':Ð       cx += coords[0];Ð       return 'r'+coords[0]+',0';Ð     case
'H':Ð       cx = coords[0];Ð       return 'l'+cx+','+cy;Ð     case 'v':Ð
        cy += coords[0];Ð       return 'r0,'+coords[0];Ð     case 'V':Ð
cy = coords[0];Ð       return 'l'+cx+','+cy;Ð     case 'c':Ð       ctrlx = cx
+ coords[coords.length-4];Ð       ctrly = cy + coords[coords.length-3];Ð
        cx += coords[coords.length-2];Ð       cy += coords[coords.length-1];Ð
        return 'v'+coords.join(',');Ð     case 'C':Ð       ctrlx =
coords[coords.length-4];Ð       ctrly = coords[coords.length-3];Ð       cx =
coords[coords.length-2];Ð       cy = coords[coords.length-1];Ð       return
'c'+coords.join(',');Ð     case 's':Ð       coords.unshift(cy-ctrly);Ð
coords.unshift(cx-ctrlx);Ð       ctrlx = cx + coords[coords.length-4];Ð
ctrly = cy + coords[coords.length-3];Ð       cx += coords[coords.length-2];Ð
        cy += coords[coords.length-1];Ð       return 'v'+coords.join(',');Ð
      case 'S':Ð       coords.unshift(cy+cy-ctrly);Ð
coords.unshift(cx+cx-ctrlx);Ð       ctrlx = coords[coords.length-4];Ð
ctrly = coords[coords.length-3];Ð       cx = coords[coords.length-2];Ð
cy = coords[coords.length-1];Ð       return 'c'+coords.join(',');Ð   }Ð
return '';Ð }).replace(/z/g, 'e');Ð };jvm.VMLCircleElement = function(config,
style){Ð jvm.VMLCircleElement.parentClass.call(this, 'oval', config, style);Ð };Ð
jvm.inherits(jvm.VMLCircleElement, jvm.VMLShapeElement);Ð
jvm.VMLCircleElement.prototype.applyAttr = function(attr, value){Ð switch
(attr) {Ð
```

```
            case 'r':Ð     this.node.style.width = value*2+'px';Ð
this.node.style.height = value*2+'px';Ð     this.applyAttr('cx',
this.get('cx') || 0);Ð     this.applyAttr('cy', this.get('cy') || 0);Ð
break;Ð   case 'cx':Ð     if (!value) return;Ð     this.node.style.left =
value - (this.get('r') || 0) + 'px';Ð     break;Ð   case 'cy':Ð     if (!
value) return;Ð     this.node.style.top = value - (this.get('r') || 0) + 'px';Ð
      break;Ð   default:Ð
jvm.VMLCircleElement.parentClass.prototype.applyAttr.call(this, attr, value);Ð
  }Ð;/**Ð* Class for vector images manipulations.Ð* @constructorÐ* @param
{DOMElement} container to place canvas toÐ* @param {Number} widthÐ* @param
{Number} heightÐ*/Ðjvm.VectorCanvas = function(container, width, height) {Ð
this.mode = window.SVGAngle ? 'svg' : 'vml';Ð if (this.mode == 'svg') {Ð
this.impl = new jvm.SVGCanvasElement(container, width, height);Ð } else {Ð
this.impl = new jvm.VMLCanvasElement(container, width, height);Ð }Ð
this.impl.mode = this.mode;Ð return this.impl;Ð};jvm.SimpleScale =
function(scale){Ð this.scale = scale;Ð};Ðjvm.SimpleScale.prototype.getValue =
function(value){Ð return value;Ð};jvm.OrdinalScale = function(scale){Ð
this.scale = scale;Ð};Ðjvm.OrdinalScale.prototype.getValue = function(value){Ð
return this.scale[value];Ð};Ðjvm.OrdinalScale.prototype.getTicks = function(){Ð
var ticks = [],Ð     key;Ð for (key in this.scale) {Ð   ticks.push({Ð
label: key,Ð     value: this.scale[key]Ð   });Ð }Ð return ticks;Ð
};jvm.NumericScale = function(scale, normalizeFunction, minValue, maxValue) {Ð
  this.scale = [];Ð normalizeFunction = normalizeFunction || 'linear';Ð if
(scale) this.setScale(scale);Ð if (normalizeFunction)
this.setNormalizeFunction(normalizeFunction);Ð if (typeof minValue !==
'undefined' ) this.setMin(minValue);Ð if (typeof maxValue !== 'undefined' )
this.setMax(maxValue);Ð};Ðjvm.NumericScale.prototype = {Ð setMin: function(min)
{Ð   this.clearMinValue = min;Ð   if (typeof this.normalize === 'function') {Ð
      this.minValue = this.normalize(min);Ð   } else {Ð     this.minValue =
min;Ð   }Ð },Ð setMax: function(max) {Ð   this.clearMaxValue = max;Ð   if
(typeof this.normalize === 'function') {Ð     this.maxValue =
this.normalize(max);Ð   } else {Ð     this.maxValue = max;Ð   }Ð },Ð
setScale: function(scale) {Ð   var i;Ð   this.scale = [];Ð   for (i = 0; i <
scale.length; i++) {Ð     this.scale[i] = [scale[i]];Ð   }Ð },Ð
setNormalizeFunction: function(f) {Ð   if (f === 'polynomial') {Ð
this.normalize = function(value) {Ð       return Math.pow(value, 0.2);Ð     }Ð
    } else if (f === 'linear') {Ð     delete this.normalize;Ð   } else {Ð
this.normalize = f;Ð   }Ð   this.setMin(this.clearMinValue);Ð
this.setMax(this.clearMaxValue);Ð },Ð getValue: function(value) {Ð   var
lengthes = [],Ð       fullLength = 0,Ð       l,Ð       i = 0,Ð       c;Ð   if
(typeof this.normalize === 'function') {Ð     value = this.normalize(value);Ð
    }Ð   for (i = 0; i < this.scale.length-1; i++) {Ð     l =
this.vectorLength(this.vectorSubtract(this.scale[i+1], this.scale[i]));Ð
lengthes.push(l);Ð     fullLength += l;Ð   }Ð   c = (this.maxValue -
this.minValue) / fullLength;Ð   for (i=0; i<lengthes.length; i++) {Ð
lengthes[i] *= c;Ð   }Ð   i = 0;Ð   value -= this.minValue;Ð   while (value -
lengthes[i] >= 0) {Ð     value -= lengthes[i];Ð     i++;Ð   }Ð   if (i ==
this.scale.length - 1) {Ð     value = this.vectorToNum(this.scale[i])Ð   }
else {Ð     value = (Ð       this.vectorToNum(Ð
this.vectorAdd(this.scale[i],Ð           this.vectorMult(Ð
this.vectorSubtract(this.scale[i+1], this.scale[i]),Ð             (value) /
(lengthes[i])Ð           )Ð         )Ð       )Ð     );Ð   }Ð   return value;Ð
  },Ð vectorToNum: function(vector) {Ð   var num = 0,Ð       i;Ð   for (i =
0; i < vector.length; i++) {Ð     num += Math.round(vector[i])*Math.pow(256,
vector.length-i-1);Ð   }Ð   return num;Ð },Ð vectorSubtract:
function(vector1, vector2) {Ð   var vector = [],Ð       i;Ð   for (i = 0; i <
vector1.length; i++) {Ð     vector[i] = vector1[i] - vector2[i];Ð   }Ð
return vector;Ð },Ð vectorAdd: function(vector1, vector2) {Ð   var vector =
[],Ð       i;Ð   for (i = 0; i < vector1.length; i++) {Ð     vector[i] =
vector1[i] + vector2[i];Ð
```

}Ð return vector;Ð },Ð vectorMult: function(vector, num) {Ð var result = [],Ð i;Ð for (i = 0; i < vector.length; i++) {Ð result[i] = vector[i] * num;Ð }Ð return result;Ð },Ð vectorLength: function(vector) {Ð var result = 0,Ð i;Ð for (i = 0; i < vector.length; i++) {Ð result += vector[i] * vector[i];Ð }Ð return Math.sqrt(result);Ð },Ð /* Derived from d3 implementation https://github.com/mbostock/d3/blob/master/src/scale/linear.js#L94 */Ð getTicks: function(){Ð var m = 5,Ð extent = [this.clearMinValue, this.clearMaxValue],Ð span = extent[1] - extent[0],Ð step = Math.pow(10, Math.floor(Math.log(span / m) / Math.LN10)),Ð err = m / span * step,Ð ticks = [],Ð tick,Ð v;Ð if (err <= .15) step *= 10;Ð else if (err <= .35) step *= 5;Ð else if (err <= .75) step *= 2;Ð extent[0] = Math.floor(extent[0] / step) * step;Ð extent[1] = Math.ceil(extent[1] / step) * step;Ð tick = extent[0];Ð while (tick <= extent[1]) {Ð if (tick == extent[0]) {Ð v = this.clearMinValue;Ð } else if (tick == extent[1]) {Ð v = this.clearMaxValue;Ð } else {Ð v = tick;Ð }Ð ticks.push({Ð label: tick,Ð value: this.getValue(v)Ð });Ð tick += step;Ð }Ð return ticks;Ð }};Ð jvm.ColorScale = function(colors, normalizeFunction, minValue, maxValue) {Ð jvm.ColorScale.parentClass.apply(this, arguments);}ÐÐ jvm.inherits(jvm.ColorScale, jvm.NumericScale);Ð jvm.ColorScale.prototype.setScale = function(scale) {Ð var i;Ð for (i = 0; i < scale.length; i++) {Ð this.scale[i] = jvm.ColorScale.rgbToArray(scale[i]);Ð }};Ð jvm.ColorScale.prototype.getValue = function(value) {Ð return jvm.ColorScale.numToRgb(jvm.ColorScale.parentClass.prototype.getValue.call(this, value));Ð };Ð jvm.ColorScale.arrayToRgb = function(ar) {Ð var rgb = '#',Ð d,Ð i;Ð for (i = 0; i < ar.length; i++) {Ð d = ar[i].toString(16);Ð rgb += d.length == 1 ? '0'+d : d;Ð }Ð return rgb;}};Ð jvm.ColorScale.numToRgb = function(num) {Ð num = num.toString(16);Ð while (num.length < 6) {Ð num = '0' + num;Ð }Ð return '#'+num;}};Ð jvm.ColorScale.rgbToArray = function(rgb) {Ð rgb = rgb.substr(1);Ð return [parseInt(rgb.substr(0, 2), 16), parseInt(rgb.substr(2, 2), 16), parseInt(rgb.substr(4, 2), 16)];}};/**Ð* Represents map legend.Ð* @constructorÐ* @param {Object} params Configuration parameters.Ð* @param {String} params.cssClass Additional CSS class to apply to legend element.Ð* @param {Boolean} params.vertical If <code>true</code> legend will be rendered as vertical.Ð* @param {String} params.title Legend title.Ð* @param {Function} params.labelRender Method to convert series values to legend labels.Ð*/Ð jvm.Legend = function(params) {Ð this.params = params || {};Ð this.map = this.params.map;Ð this.series = this.params.series;Ð this.body = jvm.$('<div/>');Ð this.body.addClass('jvectormap-legend');Ð if (this.params.cssClass) {Ð this.body.addClass(this.params.cssClass);Ð }Ð if (params.vertical) {Ð this.map.legendCntVertical.append(this.body);Ð } else {Ð this.map.legendCntHorizontal.append(this.body);Ð }Ð this.render();Ð }}Ð jvm.Legend.prototype.render = function(){Ð var ticks = this.series.scale.getTicks(),Ð i,Ð inner = jvm.$(' ').addClass('jvectormap-legend-inner'),Ð tick,Ð sample,Ð label;Ð this.body.html('');Ð if (this.params.title) {Ð this.body.append(Ð jvm.$('<div/>').addClass('jvectormap-legend-title').html(this.params.title)Ð);Ð }Ð this.body.append(inner);Ð for (i = 0; i < ticks.length; i++) {Ð tick = jvm.$(' ').addClass('jvectormap-legend-tick');Ð sample = jvm.$('<div/>').addClass('jvectormap-legend-tick-sample');Ð switch (this.series.params.attribute) {Ð case 'fill':Ð if (jvm.isImageUrl(ticks[i].value)) {Ð sample.css('background', 'url('+ticks[i].value+')');Ð } else {Ð sample.css('background', ticks[i].value);Ð }Ð break;Ð case 'stroke':Ð sample.css('background', ticks[i].value);Ð break;Ð case 'image':Ð sample.css('background', 'url('+ticks[i].value+') no-repeat center center');Ð break;Ð case 'r':Ð jvm.$(' ').css({Ð 'border-radius': ticks[i].value,Ð border: this.map.params.markerStyle.initial['stroke-width']+'px '+Ð

this.map.params.markerStyle.initial['stroke']+' solid',Ð width: ticks[i].value * 2 + 'px',Ð height: ticks[i].value * 2 + 'px',Ð background: this.map.params.markerStyle.initial['fill']Ð }).appendTo(sample);Ð break;Ð }Ð tick.append(sample);Ð label = ticks[i].label;Ð if (this.params.labelRender) {Ð label = this.params.labelRender(label);Ð }Ð tick.append(jvm.$('<div>'+label+' </div>').addClass('jvectormap-legend-tick-text'));Ð inner.append(tick);Ð }Ð inner.append(jvm.$(' ').css('clear', 'both'));Ð/**Ð* Creates data series.Ð* @constructorÐ* @param {Object} params Parameters to initialize series with.Ð* @param {Array} params.values The data set to visualize.Ð* @param {String} params.attribute Numberic or color attribute to use for data visualization. This could be: <code>fill</code>, <code>stroke</code>, <code>fill-opacity</code>, <code>stroke-opacity</code> for markers and regions and <code>r</code> (radius) for markers only.Ð* @param {Array} params.scale Values used to map a dimension of data to a visual representation. The first value sets visualization for minimum value from the data set and the last value sets visualization for the maximum value. There also could be intermidiate values. Default value is <code>['#C8EEFF', '#0071A4']</code>Ð* @param {Function|String} params.normalizeFunction The function used to map input values to the provided scale. This parameter could be provided as function or one of the strings: <code>'linear'</code> or <code>'polynomial'</code>, while <code>'linear'</code> is used by default. The function provided takes value from the data set as an input and returns corresponding value from the scale.Ð* @param {Number} params.min Minimum value of the data set. Could be calculated automatically if not provided.Ð* @param {Number} params.min Maximum value of the data set. Could be calculated automatically if not provided.Ð*/Ðjvm.DataSeries = function(params, elements, map) {Ð var scaleConstructor;Ð params = params || {};Ð params.attribute = params.attribute || 'fill';Ð this.elements = elements;Ð this.params = params;Ð this.map = map;Ð if (params.attributes) {Ð this.setAttributes(params.attributes);Ð }Ð if (jvm.$.isArray(params.scale)) {Ð scaleConstructor = (params.attribute === 'fill' || params.attribute === 'stroke') ? jvm.ColorScale : jvm.NumericScale;Ð this.scale = new scaleConstructor(params.scale, params.normalizeFunction, params.min, params.max);Ð } else if (params.scale) {Ð this.scale = new jvm.OrdinalScale(params.scale);Ð } else {Ð this.scale = new jvm.SimpleScale(params.scale);Ð }Ð this.values = params.values || {};Ð this.setValues(this.values);Ð if (this.params.legend) {Ð this.legend = new jvm.Legend($.extend({Ð map: this.map,Ð series: thisÐ },Ð this.params.legend))Ð }Ð};Ðjvm.DataSeries.prototype = {Ð setAttributes: function(key, attr){Ð var attrs = key,Ð code;Ð if (typeof key == 'string') {Ð if (this.elements[key]) {Ð this.elements[key].setStyle(this.params.attribute, attr);Ð }Ð } else {Ð for (code in attrs) {Ð if (this.elements[code]) {Ð this.elements[code].element.setStyle(this.params.attribute, attrs[code]);Ð }Ð }Ð }Ð },Ð /**Ð * Set values for the data set.Ð * @param {Object} values Object which maps codes of regions or markers to values.Ð */Ð setValues: function(values) {Ð var max = -Number.MAX_VALUE,Ð min = Number.MAX_VALUE,Ð val,Ð cc,Ð attrs = {};Ð if (!(this.scale instanceof jvm.OrdinalScale) && !(this.scale instanceof jvm.SimpleScale)) {Ð // we have a color scale as an arrayÐ if (typeof this.params.min === 'undefined' || typeof this.params.max === 'undefined') {Ð // min and/or max are not defined, so calculate themÐ for (cc in values) {Ð val = parseFloat(values[cc]);Ð if (val > max) max = val;Ð if (val < min) min = val;Ð }Ð }Ð if (typeof this.params.min === 'undefined') {Ð this.scale.setMin(min);Ð this.params.min = min;Ð } else {Ð this.scale.setMin(this.params.min);Ð }Ð if (typeof this.params.max === 'undefined') {Ð

```
                            this.scale.setMax(max);Ð       this.params.max =
max;Ð     } else {Ð       this.scale.setMax(this.params.max);Ð     }Ð     for
(cc in values) {Ð       if (cc != 'indexOf') {Ð         val =
parseFloat(values[cc]);Ð         if (!isNaN(val)) {Ð           attrs[cc] =
this.scale.getValue(val);Ð         } else {Ð           attrs[cc] =
this.elements[cc].element.style.initial[this.params.attribute];Ð         }Ð
        }Ð     }Ð   } else {Ð     for (cc in values) {Ð       if (values[cc])
{Ð         attrs[cc] = this.scale.getValue(values[cc]);Ð       } else {Ð
          attrs[cc] =
this.elements[cc].element.style.initial[this.params.attribute];Ð       }Ð
      }Ð   }Ð   this.setAttributes(attrs);Ð   jvm.$.extend(this.values,
values);Ð },Ð clear: function(){Ð   var key,Ð       attrs = {};Ð   for (key
in this.values) {Ð     if (this.elements[key]) {Ð       attrs[key] =
this.elements[key].element.shape.style.initial[this.params.attribute];Ð     }Ð
    }Ð   this.setAttributes(attrs);Ð   this.values = {};Ð },Ð /**Ð  * Set
scale of the data series.Ð  * @param {Array} scale Values representing scale.Ð
   */Ð setScale: function(scale) {Ð   this.scale.setScale(scale);Ð   if
(this.values) {Ð     this.setValues(this.values);Ð   }Ð },Ð /**Ð  * Set
normalize function of the data series.Ð  * @param {Function|String}
normilizeFunction.Ð  */Ð setNormalizeFunction: function(f) {Ð
this.scale.setNormalizeFunction(f);Ð   if (this.values) {Ð
this.setValues(this.values);Ð   }Ð },Ð /**Ð* Contains methods for transforming
point on sphere toÐ* Cartesian coordinates using various projections.Ð* @classÐ
 */Ð jvm.Proj = {Ð degRad: 180 / Math.PI,Ð radDeg: Math.PI / 180,Ð radius:
6381372,Ð sgn: function(n){Ð   if (n > 0) {Ð     return 1;Ð   } else if (n <
0) {Ð     return -1;Ð   } else {Ð     return n;Ð   }Ð },Ð /**Ð  * Converts
point on sphere to the Cartesian coordinates using Miller projectionÐ  *
@param {Number} lat Latitude in degreesÐ  * @param {Number} lng Longitude in
degreesÐ  * @param {Number} c Central meridian in degreesÐ  */Ð mill:
function(lat, lng, c){Ð   return {Ð     x: this.radius * (lng - c) *
this.radDeg,Ð     y: - this.radius * Math.log(Math.tan((45 + 0.4 * lat) *
this.radDeg)) / 0.8Ð   };Ð },Ð /**Ð  * Inverse function of mill()Ð  *
Converts Cartesian coordinates to point on sphere using Miller projectionÐ  *
@param {Number} x X of point in Cartesian system as integerÐ  * @param
{Number} y Y of point in Cartesian system as integerÐ  * @param {Number} c
Central meridian in degreesÐ  */Ð mill_inv: function(x, y, c){Ð   return {Ð
      lat: (2.5 * Math.atan(Math.exp(0.8 * y / this.radius)) - 5 * Math.PI /
8) * this.degRad,Ð     lng: (c * this.radDeg + x / this.radius) * this.degRadÐ
    };Ð },Ð /**Ð  * Converts point on sphere to the Cartesian coordinates
using Mercator projectionÐ  * @param {Number} lat Latitude in degreesÐ  *
@param {Number} lng Longitude in degreesÐ  * @param {Number} c Central
meridian in degreesÐ  */Ð merc: function(lat, lng, c){Ð   return {Ð     x:
this.radius * (lng - c) * this.radDeg,Ð     y: - this.radius *
Math.log(Math.tan(Math.PI / 4 + lat * Math.PI / 360))Ð   };Ð },Ð /**Ð  *
Inverse function of merc()Ð  * Converts Cartesian coordinates to point on
sphere using Mercator projectionÐ  * @param {Number} x X of point in
Cartesian system as integerÐ  * @param {Number} y Y of point in Cartesian
system as integerÐ  * @param {Number} c Central meridian in degreesÐ  */Ð
merc_inv: function(x, y, c){Ð   return {Ð     lat: (2 *
Math.atan(Math.exp(y / this.radius)) - Math.PI / 2) * this.degRad,Ð     lng:
(c * this.radDeg + x / this.radius) * this.degRadÐ   };Ð },Ð /**Ð  * Converts
point on sphere to the Cartesian coordinates using Albers Equal-Area ConicÐ
* projectionÐ  * @see <a href="http://mathworld.wolfram.com/AlbersEqual-
AreaConicProjection.html">Albers Equal-Area Conic projection</a>Ð  * @param
{Number} lat Latitude in degreesÐ  * @param {Number} lng Longitude in degreesÐ
   * @param {Number} c Central meridian in degreesÐ  */Ð aea: function(lat,
lng, c){Ð   var fi0 = 0,Ð       lambda0 = c * this.radDeg,Ð       fi1 = 29.5
* this.radDeg,Ð       fi2 = 45.5 * this.radDeg,Ð       fi = lat * this.radDeg,Ð
        lambda = lng * this.radDeg,Ð       n =
(Math.sin(fi1)+Math.sin(fi2)) / 2,Ð
```

```
                                        C =
Math.cos(fi1)*Math.cos(fi1)+2*n*Math.sin(fi1),Ð       theta = n*(lambda-
lambda0),Ð       ro = Math.sqrt(C-2*n*Math.sin(fi))/n,Ð       ro0 =
Math.sqrt(C-2*n*Math.sin(fi0))/n;Ð   return {Ð     x: ro * Math.sin(theta) *
this.radius,Ð     y: - (ro0 - ro * Math.cos(theta)) * this.radiusÐ   };Ð },Ð /
**Ð  * Converts Cartesian coordinates to the point on sphere using Albers
Equal-Area ConicÐ  * projectionÐ  * @see <a href="http://
mathworld.wolfram.com/AlbersEqual-AreaConicProjection.html">Albers Equal-Area
Conic projection</a>Ð  * @param {Number} x X of point in Cartesian system as
integerÐ  * @param {Number} y Y of point in Cartesian system as integerÐ  *
@param {Number} c Central meridian in degreesÐ  */Ð aea_inv: function(xCoord,
yCoord, c){Ð   var x = xCoord / this.radius,Ð       y = yCoord / this.radius,Ð
        fi0 = 0,Ð       lambda0 = c * this.radDeg,Ð       fi1 = 29.5 *
this.radDeg,Ð       fi2 = 45.5 * this.radDeg,Ð       n =
(Math.sin(fi1)+Math.sin(fi2)) / 2,Ð       C =
Math.cos(fi1)*Math.cos(fi1)+2*n*Math.sin(fi1),Ð       ro0 =
Math.sqrt(C-2*n*Math.sin(fi0))/n,Ð       ro = Math.sqrt(x*x+(ro0-y)*(ro0-y)),Ð
        theta = Math.atan( x / (ro0 - y) );Ð   return {Ð     lat:
(Math.asin((C - ro * ro * n * n) / (2 * n))) * this.degRad,Ð     lng:
(lambda0 + theta / n) * this.degRadÐ   };Ð },Ð /**Ð  * Converts point on
sphere to the Cartesian coordinates using Lambert conformalÐ  * conic
projectionÐ  * @see <a href="http://mathworld.wolfram.com/
LambertConformalConicProjection.html">Lambert Conformal Conic Projection</a>Ð
   * @param {Number} lat Latitude in degreesÐ  * @param {Number} lng
Longitude in degreesÐ  * @param {Number} c Central meridian in degreesÐ  */Ð
lcc: function(lat, lng, c){Ð   var fi0 = 0,Ð       lambda0 = c * this.radDeg,Ð
        lambda = lng * this.radDeg,Ð       fi1 = 33 * this.radDeg,Ð       fi2
= 45 * this.radDeg,Ð       fi = lat * this.radDeg,Ð       n =
Math.log( Math.cos(fi1) * (1 / Math.cos(fi2)) ) /
Math.log( Math.tan( Math.PI / 4 + fi2 / 2) * (1 / Math.tan( Math.PI / 4 +
fi1 / 2) ) ),Ð       F = ( Math.cos(fi1) * Math.pow( Math.tan( Math.PI / 4 +
fi1 / 2 ), n ) ) / n,Ð       ro = F * Math.pow( 1 / Math.tan( Math.PI / 4 +
fi / 2 ), n ),Ð       ro0 = F * Math.pow( 1 / Math.tan( Math.PI / 4 + fi0 /
2 ), n );Ð   return {Ð     x: ro * Math.sin( n * (lambda - lambda0) ) *
this.radius,Ð     y: - (ro0 - ro * Math.cos( n * (lambda - lambda0) ) ) *
this.radiusÐ   };Ð },Ð /**Ð  * Converts Cartesian coordinates to the point on
sphere using Lambert conformal conicÐ  * projectionÐ  * @see <a href="http://
mathworld.wolfram.com/LambertConformalConicProjection.html">Lambert Conformal
Conic Projection</a>Ð  * @param {Number} x X of point in Cartesian system as
integerÐ  * @param {Number} y Y of point in Cartesian system as integerÐ  *
@param {Number} c Central meridian in degreesÐ  */Ð lcc_inv: function(xCoord,
yCoord, c){Ð   var x = xCoord / this.radius,Ð       y = yCoord / this.radius,Ð
        fi0 = 0,Ð       lambda0 = c * this.radDeg,Ð       fi1 = 33 *
this.radDeg,Ð       fi2 = 45 * this.radDeg,Ð       n =
Math.log( Math.cos(fi1) * (1 / Math.cos(fi2)) ) /
Math.log( Math.tan( Math.PI / 4 + fi2 / 2) * (1 / Math.tan( Math.PI / 4 +
fi1 / 2) ) ),Ð       F = ( Math.cos(fi1) * Math.pow( Math.tan( Math.PI / 4 +
fi1 / 2 ), n ) ) / n,Ð       ro0 = F * Math.pow( 1 / Math.tan( Math.PI / 4 +
fi0 / 2 ), n ),Ð       ro = this.sgn(n) * Math.sqrt(x*x+(ro0-y)*(ro0-y)),Ð
        theta = Math.atan( x / (ro0 - y) );Ð   return {Ð     lat: (2 *
Math.atan(Math.pow(F/ro, 1/n)) - Math.PI / 2) * this.degRad,Ð     lng:
(lambda0 + theta / n) * this.degRadÐ   };Ð }};Ð jvm.MapObject = function(config)
{};Ð jvm.MapObject.prototype.getLabelText = function(key){Ð var text;Ð if
(this.config.label) {Ð   if (typeof this.config.label.render === 'function') {Ð
      text = this.config.label.render(key);Ð   } else {Ð     text = key;Ð   }Ð
  } else {Ð   text = null;Ð }Ð return text;Ð }Ð
jvm.MapObject.prototype.getLabelOffsets = function(key){Ð var offsets;Ð if
(this.config.label) {Ð   if (typeof this.config.label.offsets === 'function')
{Ð     offsets = this.config.label.offsets(key);Ð   } else if (typeof
this.config.label.offsets === 'object') {Ð
```

offsets = this.config.label.offsets[key];Ð }Ð }Ð return offsets || [0, 0];ÐÐÐ**Ð* Set hovered state to the element. Hovered state means mouse cursor is over element. Styles will be updates respectively.Ð* @param {Boolean} isHovered <code>true</code> to make element hovered, <code>false</code> otherwise.Ð*/Ð jvm.MapObject.prototype.setHovered = function(isHovered){Ð if (this.isHovered !== isHovered) {Ð this.isHovered = isHovered;Ð this.shape.isHovered = isHovered;Ð this.shape.updateStyle();Ð if (this.label) {Ð this.label.isHovered = isHovered;Ð this.label.updateStyle();Ð }Ð }ÐÐ;ÐÐ**Ð* Set selected state to the element. Styles will be updates respectively.Ð* @param {Boolean} isSelected <code>true</code> to make element selected, <code>false</code> otherwise.Ð*/Ð jvm.MapObject.prototype.setSelected = function(isSelected){Ð if (this.isSelected !== isSelected) {Ð this.isSelected = isSelected;Ð this.shape.isSelected = isSelected;Ð this.shape.updateStyle();Ð if (this.label) {Ð this.label.isSelected = isSelected;Ð this.label.updateStyle();Ð }Ð jvm.$(this.shape).trigger('selected', [isSelected]);Ð }ÐÐ;ÐÐjvm.MapObject.prototype.setStyle = function(){Ð this.shape.setStyle.apply(this.shape, arguments);ÐÐ;Ð jvm.MapObject.prototype.remove = function(){Ð this.shape.remove();Ð if (this.label) {Ð this.label.remove();Ð }ÐÐ;jvm.Region = function(config){Ð var bbox,Ð text,Ð offsets,Ð labelDx,Ð labelDy;Ð this.config = config;Ð this.map = this.config.map;Ð this.shape = config.canvas.addPath({Ð d: config.path,Ð 'data-code': config.codeÐ }, config.style, config.canvas.rootElement);Ð this.shape.addClass('jvectormap-region jvectormap-element');Ð bbox = this.shape.getBBox();Ð text = this.getLabelText(config.code);Ð if (this.config.label && text) {Ð offsets = this.getLabelOffsets(config.code);Ð this.labelX = bbox.x + bbox.width / 2 + offsets[0];Ð this.labelY = bbox.y + bbox.height / 2 + offsets[1];Ð this.label = config.canvas.addText({Ð text: text,Ð 'text-anchor': 'middle',Ð 'alignment-baseline': 'central',Ð x: this.labelX,Ð y: this.labelY,Ð 'data-code': config.codeÐ }, config.labelStyle, config.labelsGroup);Ð this.label.addClass('jvectormap-region jvectormap-element');Ð }ÐÐ;ÐÐjvm.inherits(jvm.Region, jvm.MapObject);Ð jvm.Region.prototype.updateLabelPosition = function(){Ð if (this.label) {Ð this.label.set({Ð x: this.labelX * this.map.scale + this.map.transX * this.map.scale,Ð y: this.labelY * this.map.scale + this.map.transY * this.map.scaleÐ });Ð }ÐÐ;jvm.Marker = function(config){Ð var text,Ð offsets;Ð this.config = config;Ð this.map = this.config.map;Ð this.isImage = !!this.config.style.initial.image;Ð this.createShape();Ð text = this.getLabelText(config.index);Ð if (this.config.label && text) {Ð this.offsets = this.getLabelOffsets(config.index);Ð this.labelX = config.cx / this.map.scale - this.map.transX;Ð this.labelY = config.cy / this.map.scale - this.map.transY;Ð this.label = config.canvas.addText({Ð text: text,Ð 'data-index': config.index,Ð dy: "0.6ex",Ð x: this.labelX,Ð y: this.labelYÐ }, config.labelStyle, config.labelsGroup);Ð this.label.addClass('jvectormap-marker jvectormap-element');Ð }ÐÐ;Ð jvm.inherits(jvm.Marker, jvm.MapObject);ÐÐjvm.Marker.prototype.createShape = function(){Ð var that = this;Ð if (this.shape) {Ð this.shape.remove();Ð }Ð this.shape = this.config.canvas[this.isImage ? 'addImage' : 'addCircle'](Ð "data-index": this.config.index,Ð cx: this.config.cx,Ð cy: this.config.cyÐ }, this.config.style, this.config.group);Ð this.shape.addClass('jvectormap-marker jvectormap-element');Ð if (this.isImage) {Ð jvm.$(this.shape.node).on('imageloaded', function(){Ð that.updateLabelPosition();Ð });Ð }ÐÐ;Ð jvm.Marker.prototype.updateLabelPosition = function(){Ð if (this.label) {Ð this.label.set({Ð x: this.labelX * this.map.scale + this.offsets[0] +Ð this.map.transX * this.map.scale + 5 + (this.isImage ? (this.shape.width || 0) / 2 : this.shape.properties.r),Ð y: this.labelY * this.map.scale + this.map.transY * this.map.scale + this.offsets[1]Ð

```
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
});Ð }Ð
};ÐÐvm.Marker.prototype.setStyle = function(property, value){Ð var isImage;Ð
jvm.Marker.parentClass.prototype.setStyle.apply(this, arguments);Ð if
(property === 'r') {Ð   this.updateLabelPosition();Ð }Ð isImage = !!
this.shape.get('image');Ð if (isImage != this.isImage) {Ð   this.isImage =
isImage;Ð   this.config.style = jvm.$.extend(true, {}, this.shape.style);Ð
this.createShape();Ð }Ð};/**Ð* Creates map, draws paths, binds events.Ð*
@constructorÐ* @param {Object} params Parameters to initialize map with.Ð*
@param {String} params.map Name of the map in the format
<code>territory_proj_lang</code> where <code>territory</code> is a unique
code or name of the territory which the map represents (ISO 3166 standard is
used where possible), <code>proj</code> is a name of projection used to
generate representation of the map on the plane (projections are named
according to the conventions of proj4 utility) and <code>lang</code> is a
code of the language, used for the names of regions.Ð* @param {String}
params.backgroundColor Background color of the map in CSS format.Ð* @param
{Boolean} params.zoomOnScroll When set to true map could be zoomed using
mouse scroll. Default value is <code>true</code>.Ð* @param {Boolean}
params.zoomOnScrollSpeed Mouse scroll speed. Number from 1 to 10. Default
value is <code>3</code>.Ð* @param {Boolean} params.panOnDrag When set to
true, the map pans when being dragged. Default value is <code>true</code>.Ð*
@param {Number} params.zoomMax Indicates the maximum zoom ratio which could
be reached zooming the map. Default value is <code>8</code>.Ð* @param
{Number} params.zoomMin Indicates the minimum zoom ratio which could be
reached zooming the map. Default value is <code>1</code>.Ð* @param {Number}
params.zoomStep Indicates the multiplier used to zoom map with +/- buttons.
Default value is <code>1.6</code>.Ð* @param {Boolean} params.zoomAnimate
Indicates whether or not to animate changing of map zoom with zoom buttons.Ð*
@param {Boolean} params.regionsSelectable When set to true regions of the map
could be selected. Default value is <code>false</code>.Ð* @param {Boolean}
params.regionsSelectableOne Allow only one region to be selected at the
moment. Default value is <code>false</code>.Ð* @param {Boolean}
params.markersSelectable When set to true markers on the map could be
selected. Default value is <code>false</code>.Ð* @param {Boolean}
params.markersSelectableOne Allow only one marker to be selected at the
moment. Default value is <code>false</code>.Ð* @param {Object}
params.regionStyle Set the styles for the map's regions. Each region or
marker has four states: <code>initial</code> (default state), <code>hover</
code> (when the mouse cursor is over the region or marker), <code>selected</
code> (when region or marker is selected), <code>selectedHover</code> (when
the mouse cursor is over the region or marker and it's selected
simultaneously). Styles could be set for each of this states. Default value
for that parameter is:Ð<pre>{Ð initial: {Ð   fill: 'white',Ð   "fill-opacity":
1,Ð   stroke: 'none',Ð   "stroke-width": 0,Ð   "stroke-opacity": 1Ð },Ð
hover: {Ð   "fill-opacity": 0.8,Ð   cursor: 'pointer'Ð },Ð selected: {Ð
fill: 'yellow'Ð },Ð selectedHover: {Ð }Ð}</pre>Ð* @param {Object}
params.regionLabelStyle Set the styles for the regions' labels. Each region
or marker has four states: <code>initial</code> (default state), <code>hover</
code> (when the mouse cursor is over the region or marker), <code>selected</
code> (when region or marker is selected), <code>selectedHover</code> (when
the mouse cursor is over the region or marker and it's selected
simultaneously). Styles could be set for each of this states. Default value
for that parameter is:Ð<pre>{Ð initial: {Ð   'font-family': 'Verdana',Ð
'font-size': '12',Ð   'font-weight': 'bold',Ð   cursor: 'default',Ð   fill:
'black'Ð },Ð hover: {Ð   cursor: 'pointer'Ð }Ð}</pre>Ð* @param {Object}
params.markerStyle Set the styles for the map's markers. Any parameter
suitable for <code>regionStyle</code> could be used as well as numeric
parameter <code>r</code> to set the marker's radius. Default value for that
parameter is:Ð<pre>{Ð initial: {Ð   fill: 'grey',Ð   stroke: '#505050',Ð
"fill-opacity": 1,Ð
```

"stroke-width": 1,Ð "stroke-opacity": 1,Ð r: 5Ð },Ð hover: {Ð stroke: 'black',Ð "stroke-width": 2,Ð cursor: 'pointer'Ð },Ð selected: {Ð fill: 'blue'Ð },Ð selectedHover: {Ð }Ð}</pre>Ð* @param {Object} params.markerLabelStyle Set the styles for the markers' labels. Default value for that parameter is:Ð<pre>{Ð initial: {Ð 'font-family': 'Verdana',Ð 'font-size': '12',Ð 'font-weight': 'bold',Ð cursor: 'default',Ð fill: 'black'Ð },Ð hover: {Ð cursor: 'pointer'Ð }Ð}</pre>Ð* @param {Object|Array} params.markers Set of markers to add to the map during initialization. In case of array is provided, codes of markers will be set as string representations of array indexes. Each marker is represented by <code>latLng</code> (array of two numeric values), <code>name</code> (string which will be show on marker's tip) and any marker styles.Ð* @param {Object} params.series Object with two keys: <code>markers</code> and <code>regions</code>. Each of which is an array of series configs to be applied to the respective map elements. See <a href="jvm.DataSeries.html">DataSeries</a> description for a list of parameters available.Ð* @param {Object|String} params.focusOn This parameter sets the initial position and scale of the map viewport. See <code>setFocus</code> docuemntation for possible parameters.Ð* @param {Object} params.labels Defines parameters for rendering static labels. Object could contain two keys: <code>regions</code> and <code>markers</code>. Each key value defines configuration object with the following possible options:Ð <ul>Ð <li><code>render {Function}</code> - defines method for converting region code or marker index to actual label value.</li>Ð <li><code>offsets {Object|Function}</code> - provides method or object which could be used to define label offset by region code or marker index.</li>Ð</ul>ÐPlase note: static labels feature is not supported in Internet Explorer 8 and below.Ð * @param {Array|Object|String} params.selectedRegions Set initially selected regions.Ð* @param {Array|Object|String} params.selectedMarkers Set initially selected markers.Ð* @param {Function} params.onRegionTipShow <code>(Event e, Object tip, String code)</code> Will be called right before the region tip is going to be shown.Ð* @param {Function} params.onRegionOver <code>(Event e, String code)</code> Will be called on region mouse over event.Ð* @param {Function} params.onRegionOut <code>(Event e, String code)</code> Will be called on region mouse out event.Ð* @param {Function} params.onRegionClick <code>(Event e, String code)</code> Will be called on region click event.Ð* @param {Function} params.onRegionSelected <code>(Event e, String code, Boolean isSelected, Array selectedRegions)</code> Will be called when region is (de)selected. <code>isSelected</code> parameter of the callback indicates whether region is selected or not. <code>selectedRegions</code> contains codes of all currently selected regions.Ð* @param {Function} params.onMarkerTipShow <code>(Event e, Object tip, String code)</code> Will be called right before the marker tip is going to be shown.Ð* @param {Function} params.onMarkerOver <code>(Event e, String code)</code> Will be called on marker mouse over event.Ð* @param {Function} params.onMarkerOut <code>(Event e, String code)</code> Will be called on marker mouse out event.Ð * @param {Function} params.onMarkerClick <code>(Event e, String code)</code> Will be called on marker click event.Ð* @param {Function} params.onMarkerSelected <code>(Event e, String code, Boolean isSelected, Array selectedMarkers)</code> Will be called when marker is (de)selected. <code>isSelected</code> parameter of the callback indicates whether marker is selected or not. <code>selectedMarkers</code> contains codes of all currently selected markers.Ð* @param {Function} params.onViewportChange <code>(Event e, Number scale)</code> Triggered when the map's viewport is changed (map was panned or zoomed).Ð*/Ðjvm.Map = function(params) {Ð var map = this,Ð e;Ð this.params = jvm.$.extend(true, {}, jvm.Map.defaultParams, params);Ð if (!jvm.Map.maps[this.params.map]) {Ð throw new Error('Attempt to use map which was not loaded: '+this.params.map);Ð }Ð this.mapData = jvm.Map.maps[this.params.map];Ð this.markers = {};Ð this.regions = {};Ð this.regionsColors = {};Ð this.regionsData = {};Ð this.container = jvm.$(' ').addClass('jvectormap-container');Ð

if (this.params.container) {Ð
this.params.container.append(this.container);Ð }Ð
this.container.data('mapObject', this);Ð this.defaultWidth =
this.mapData.width;Ð this.defaultHeight = this.mapData.height;Ð
this.setBackgroundColor(this.params.backgroundColor);Ð this.onResize =
function(){Ð map.updateSize();Ð }Ð jvm.$(window).resize(this.onResize);Ð
for (e in jvm.Map.apiEvents) {Ð if (this.params[e]) {Ð
this.container.bind(jvm.Map.apiEvents[e]+'.jvectormap', this.params[e]);Ð }Ð
}Ð this.canvas = new jvm.VectorCanvas(this.container[0], this.width,
this.height);Ð if (('ontouchstart' in window) || (window.DocumentTouch &&
document instanceof DocumentTouch)) {Ð if (this.params.bindTouchEvents) {Ð
this.bindContainerTouchEvents();Ð }Ð }Ð this.bindContainerEvents();Ð
this.bindElementEvents();Ð this.createTip();Ð if (this.params.zoomButtons) {Ð
this.bindZoomButtons();Ð }Ð this.createRegions();Ð
this.createMarkers(this.params.markers || {});Ð this.updateSize();Ð if
(this.params.focusOn) {Ð if (typeof this.params.focusOn === 'string') {Ð
this.params.focusOn = {region: this.params.focusOn};Ð } else if (jvm.
$.isArray(this.params.focusOn)) {Ð this.params.focusOn = {regions:
this.params.focusOn};Ð }Ð this.setFocus(this.params.focusOn);Ð }Ð if
(this.params.selectedRegions) {Ð
this.setSelectedRegions(this.params.selectedRegions);Ð }Ð if
(this.params.selectedMarkers) {Ð
this.setSelectedMarkers(this.params.selectedMarkers);Ð }Ð
this.legendCntHorizontal = jvm.$(' ').addClass('jvectormap-legend-cnt
jvectormap-legend-cnt-h');Ð this.legendCntVertical = jvm.$('<div/
>').addClass('jvectormap-legend-cnt jvectormap-legend-cnt-v');Ð
this.container.append(this.legendCntHorizontal);Ð
this.container.append(this.legendCntVertical);Ð if (this.params.series) {Ð
this.createSeries();Ð }Ð };Ð jvm.Map.prototype = {Ð transX: 0,Ð transY: 0,Ð
scale: 1,Ð baseTransX: 0,Ð baseTransY: 0,Ð baseScale: 1,Ð width: 0,Ð height:
0,Ð /**Ð * Set background color of the map.Ð * @param {String}
backgroundColor Background color in CSS format.Ð */Ð setBackgroundColor:
function(backgroundColor) {Ð this.container.css('background-color',
backgroundColor);Ð },Ð resize: function() {Ð var curBaseScale =
this.baseScale;Ð if (this.width / this.height > this.defaultWidth /
this.defaultHeight) {Ð this.baseScale = this.height / this.defaultHeight;Ð
this.baseTransX = Math.abs(this.width - this.defaultWidth *
this.baseScale) / (2 * this.baseScale);Ð } else {Ð this.baseScale =
this.width / this.defaultWidth;Ð this.baseTransY = Math.abs(this.height -
this.defaultHeight * this.baseScale) / (2 * this.baseScale);Ð }Ð
this.scale *= this.baseScale / curBaseScale;Ð this.transX *=
this.baseScale / curBaseScale;Ð this.transY *= this.baseScale /
curBaseScale;Ð },Ð /**Ð * Synchronize the size of the map with the size of
the container. Suitable in situations where the size of the container is
changed programmatically or container is shown after it became visible.Ð */Ð
updateSize: function(){Ð this.width = this.container.width();Ð
this.height = this.container.height();Ð this.resize();Ð
this.canvas.setSize(this.width, this.height);Ð this.applyTransform();Ð },Ð /
**Ð * Reset all the series and show the map with the initial zoom.Ð */Ð
reset: function() {Ð var key,Ð i;Ð for (key in this.series) {Ð
for (i = 0; i < this.series[key].length; i++) {Ð this.series[key]
[i].clear();Ð }Ð }Ð this.scale = this.baseScale;Ð this.transX =
this.baseTransX;Ð this.transY = this.baseTransY;Ð this.applyTransform();Ð
},Ð applyTransform: function() {Ð var maxTransX,Ð maxTransY,Ð
minTransX,Ð minTransY;Ð if (this.defaultWidth * this.scale <=
this.width) {Ð maxTransX = (this.width - this.defaultWidth *
this.scale) / (2 * this.scale);Ð minTransX = (this.width -
this.defaultWidth * this.scale) / (2 * this.scale);Ð } else {Ð
maxTransX = 0;Ð minTransX = (this.width - this.defaultWidth *
this.scale) / this.scale;Ð

```
                              }Ð   if (this.defaultHeight * this.scale <=
this.height) {Ð     maxTransY = (this.height - this.defaultHeight *
this.scale) / (2 * this.scale);Ð     minTransY = (this.height -
this.defaultHeight * this.scale) / (2 * this.scale);Ð   } else {Ð
maxTransY = 0;Ð     minTransY = (this.height - this.defaultHeight *
this.scale) / this.scale;Ð   }Ð   if (this.transY > maxTransY) {Ð
this.transY = maxTransY;Ð   } else if (this.transY < minTransY) {Ð
this.transY = minTransY;Ð   }Ð   if (this.transX > maxTransX) {Ð
this.transX = maxTransX;Ð   } else if (this.transX < minTransX) {Ð
this.transX = minTransX;Ð   }Ð   this.canvas.applyTransformParams(this.scale,
this.transX, this.transY);Ð   if (this.markers) {Ð
this.repositionMarkers();Ð   }Ð   this.repositionLabels();Ð
this.container.trigger('viewportChange', [this.scale/this.baseScale,
this.transX, this.transY]);Ð },Ð bindContainerEvents: function(){Ð   var
mouseDown = false,Ð       oldPageX,Ð       oldPageY,Ð       map = this;Ð   if
(this.params.panOnDrag) {Ð     this.container.mousemove(function(e){Ð
if (mouseDown) {Ð         map.transX -= (oldPageX - e.pageX) / map.scale;Ð
          map.transY -= (oldPageY - e.pageY) / map.scale;Ð
map.applyTransform();Ð         oldPageX = e.pageX;Ð         oldPageY =
e.pageY;Ð       }Ð       return false;Ð     }).mousedown(function(e){Ð
mouseDown = true;Ð       oldPageX = e.pageX;Ð       oldPageY = e.pageY;Ð
        return false;Ð     });Ð     this.onContainerMouseUp = function(){Ð
        mouseDown = false;Ð     };Ð     jvm.
$('body').mouseup(this.onContainerMouseUp);Ð   }Ð   if
(this.params.zoomOnScroll) {Ð     this.container.mousewheel(function(event,
delta, deltaX, deltaY) {Ð       var offset = jvm.$(map.container).offset(),Ð
            centerX = event.pageX - offset.left,Ð           centerY =
event.pageY - offset.top,Ð           zoomStep = Math.pow(1 +
map.params.zoomOnScrollSpeed / 1000, event.deltaFactor * event.deltaY);Ð
        map.tip.hide();Ð       map.setScale(map.scale * zoomStep, centerX,
centerY);Ð       event.preventDefault();Ð     });Ð   }Ð },Ð
bindContainerTouchEvents: function(){Ð   var touchStartScale,Ð
touchStartDistance,Ð       map = this,Ð       touchX,Ð       touchY,Ð
centerTouchX,Ð       centerTouchY,Ð       lastTouchesLength,Ð
handleTouchEvent = function(e){Ð         var touches =
e.originalEvent.touches,Ð             offset,Ð             scale,Ð
              transXOld,Ð             transYOld;Ð         if (e.type ==
'touchstart') {Ð           lastTouchesLength = 0;Ð         }Ð         if
(touches.length == 1) {Ð           if (lastTouchesLength == 1) {Ð
transXOld = map.transX;Ð             transYOld = map.transY;Ð
map.transX -= (touchX - touches[0].pageX) / map.scale;Ð
map.transY -= (touchY - touches[0].pageY) / map.scale;Ð
map.applyTransform();Ð             map.tip.hide();Ð             if
(transXOld != map.transX || transYOld != map.transY) {Ð
e.preventDefault();Ð             }Ð           }Ð           touchX =
touches[0].pageX;Ð           touchY = touches[0].pageY;Ð         } else if
(touches.length == 2) {Ð           if (lastTouchesLength == 2) {Ð
scale = Math.sqrt(Ð               Math.pow(touches[0].pageX -
touches[1].pageX, 2) +Ð               Math.pow(touches[0].pageY -
touches[1].pageY, 2)Ð             ) / touchStartDistance;Ð
map.setScale(Ð               touchStartScale * scale,Ð
centerTouchX,Ð               centerTouchYÐ             )Ð
map.tip.hide();Ð             e.preventDefault();Ð           } else {Ð
              offset = jvm.$(map.container).offset();Ð             if
(touches[0].pageX > touches[1].pageX) {Ð               centerTouchX =
touches[1].pageX + (touches[0].pageX - touches[1].pageX) / 2;Ð             }
else {Ð               centerTouchX = touches[0].pageX + (touches[1].pageX -
touches[0].pageX) / 2;Ð             }Ð             if (touches[0].pageY >
touches[1].pageY) {Ð               centerTouchY = touches[1].pageY +
(touches[0].pageY - touches[1].pageY) / 2;Ð
```

```
                                                        } else {Ð
                centerTouchY = touches[0].pageY + (touches[1].pageY -
touches[0].pageY) / 2;Ð             }Ð             centerTouchX -=
offset.left;Ð             centerTouchY -= offset.top;Ð
touchStartScale = map.scale;Ð             touchStartDistance = Math.sqrt(Ð
                Math.pow(touches[0].pageX - touches[1].pageX, 2) +Ð
                Math.pow(touches[0].pageY - touches[1].pageY, 2)Ð
              );Ð           }Ð         }Ð         lastTouchesLength =
touches.length;Ð       };Ð   jvm.$(this.container).bind('touchstart',
handleTouchEvent);Ð   jvm.$(this.container).bind('touchmove',
handleTouchEvent);Ð },Ð bindElementEvents: function(){Ð   var map = this,Ð
        mouseMoved;Ð   this.container.mousemove(function(){Ð     mouseMoved =
true;Ð   });Ð   /* Can not use common class selectors here because of the bug
in jQueryÐ      SVG handling, use with caution. */Ð
this.container.delegate("[class~='jvectormap-element']", 'mouseover
mouseout', function(e){Ð     var baseVal = jvm.$(this).attr('class').baseVal
|| jvm.$(this).attr('class'),Ð         type = baseVal.indexOf('jvectormap-
region') === -1 ? 'marker' : 'region',Ð         code = type == 'region' ? jvm.
$(this).attr('data-code') : jvm.$(this).attr('data-index'),Ð         element
= type == 'region' ? map.regions[code].element : map.markers[code].element,Ð
          tipText = type == 'region' ? map.mapData.paths[code].name :
(map.markers[code].config.name || ''),Ð         tipShowEvent = jvm.
$.Event(type+'TipShow.jvectormap'),Ð         overEvent = jvm.
$.Event(type+'Over.jvectormap');Ð     if (e.type == 'mouseover') {Ð
map.container.trigger(overEvent, [code]);Ð       if (!
overEvent.isDefaultPrevented()) {Ð         element.setHovered(true);Ð       }Ð
        map.tip.text(tipText);Ð       map.container.trigger(tipShowEvent,
[map.tip, code]);Ð       if (!tipShowEvent.isDefaultPrevented()) {Ð
map.tip.show();Ð         map.tipWidth = map.tip.width();Ð
map.tipHeight = map.tip.height();Ð       }Ð     } else {Ð
element.setHovered(false);Ð       map.tip.hide();Ð
map.container.trigger(type+'Out.jvectormap', [code]);Ð     }Ð   });Ð   /* Can
not use common class selectors here because of the bug in jQueryÐ      SVG
handling, use with caution. */Ð
this.container.delegate("[class~='jvectormap-element']", 'mousedown',
function(){Ð     mouseMoved = false;Ð   });Ð   /* Can not use common class
selectors here because of the bug in jQueryÐ      SVG handling, use with
caution. */Ð   this.container.delegate("[class~='jvectormap-element']",
'mouseup', function(){Ð     var baseVal = jvm.$(this).attr('class').baseVal ?
jvm.$(this).attr('class').baseVal : jvm.$(this).attr('class'),Ð         type
= baseVal.indexOf('jvectormap-region') === -1 ? 'marker' : 'region',Ð
code = type == 'region' ? jvm.$(this).attr('data-code') : jvm.
$(this).attr('data-index'),Ð         clickEvent = jvm.
$.Event(type+'Click.jvectormap'),Ð         element = type == 'region' ?
map.regions[code].element : map.markers[code].element;Ð     if (!mouseMoved) {Ð
        map.container.trigger(clickEvent, [code]);Ð       if ((type ===
'region' && map.params.regionsSelectable) || (type === 'marker' &&
map.params.markersSelectable)) {Ð         if (!
clickEvent.isDefaultPrevented()) {Ð           if
(map.params[type+'sSelectableOne']) {Ð
map.clearSelected(type+'s');Ð           }Ð           element.setSelected(!
element.isSelected);Ð         }Ð       }Ð     }Ð   });Ð },Ð bindZoomButtons:
function() {Ð   var map = this;Ð   jvm.$('<div/>').addClass('jvectormap-
zoomin').text('+').appendTo(this.container);Ð   jvm.$('<div/
>').addClass('jvectormap-zoomout').html('&#x2212;').appendTo(this.container);Ð
    this.container.find('.jvectormap-zoomin').click(function(){Ð
map.setScale(map.scale * map.params.zoomStep, map.width / 2, map.height / 2,
false, map.params.zoomAnimate);Ð   });Ð   this.container.find('.jvectormap-
zoomout').click(function(){Ð     map.setScale(map.scale /
map.params.zoomStep, map.width / 2, map.height / 2, false,
map.params.zoomAnimate);Ð
```

```
                            });Ð },Ð createTip: function(){Ð   var map = this;Ð
    this.tip = jvm.$('<div/>').addClass('jvectormap-tip').appendTo(jvm.
$('body'));Ð   this.container.mousemove(function(e){Ð     var left =
e.pageX-15-map.tipWidth,Ð         top = e.pageY-15-map.tipHeight;Ð     if
(left < 5) {Ð       left = e.pageX + 15;Ð     }Ð     if (top < 5) {Ð
top = e.pageY + 15;Ð     }Ð     map.tip.css({Ð       left: left,Ð       top:
topÐ     });Ð   });Ð },Ð setScale: function(scale, anchorX, anchorY,
isCentered, animate) {Ð   var viewportChangeEvent = jvm.
$.Event('zoom.jvectormap'),Ð       interval,Ð       that = this,Ð       i = 0,Ð
        count = Math.abs(Math.round((scale - this.scale) * 60 /
Math.max(scale, this.scale))),Ð       scaleStart,Ð       scaleDiff,Ð
transXStart,Ð       transXDiff,Ð       transYStart,Ð       transYDiff,Ð
transX,Ð       transY,Ð       deferred = new jvm.$.Deferred();Ð   if (scale >
this.params.zoomMax * this.baseScale) {Ð     scale = this.params.zoomMax *
this.baseScale;Ð   } else if (scale < this.params.zoomMin * this.baseScale) {Ð
      scale = this.params.zoomMin * this.baseScale;Ð   }Ð   if (typeof
anchorX != 'undefined' && typeof anchorY != 'undefined') {Ð     zoomStep =
scale / this.scale;Ð     if (isCentered) {Ð       transX = anchorX +
this.defaultWidth * (this.width / (this.defaultWidth * scale)) / 2;Ð
transY = anchorY + this.defaultHeight * (this.height / (this.defaultHeight *
scale)) / 2;Ð     } else {Ð       transX = this.transX - (zoomStep - 1) /
scale * anchorX;Ð       transY = this.transY - (zoomStep - 1) / scale *
anchorY;Ð     }Ð   }Ð   if (animate && count > 0)  {Ð     scaleStart =
this.scale;Ð     scaleDiff = (scale - scaleStart) / count;Ð     transXStart =
this.transX * this.scale;Ð     transYStart = this.transY * this.scale;Ð
transXDiff = (transX * scale - transXStart) / count;Ð     transYDiff =
(transY * scale - transYStart) / count;Ð     interval = setInterval(function()
{Ð       i += 1;Ð       that.scale = scaleStart + scaleDiff * i;Ð
that.transX = (transXStart + transXDiff * i) / that.scale;Ð       that.transY
= (transYStart + transYDiff * i) / that.scale;Ð       that.applyTransform();Ð
        if (i == count) {Ð         clearInterval(interval);Ð
that.container.trigger(viewportChangeEvent, [scale/that.baseScale]);Ð
deferred.resolve();Ð       }Ð     }, 10);Ð   } else {Ð     this.transX =
transX;Ð     this.transY = transY;Ð     this.scale = scale;Ð
this.applyTransform();Ð     this.container.trigger(viewportChangeEvent,
[scale/this.baseScale]);Ð     deferred.resolve();Ð   }Ð   return deferred;Ð },Ð
  /**Ð  * Set the map's viewport to the specific point and set zoom of the
map to the specific level. Point and zoom level could be defined in two ways:
using the code of some region to focus on or a central point and zoom level
as numbers.Ð  * @param This method takes a configuration object as the single
argument. The options passed to it are the following:Ð  * @param {Array}
params.regions Array of region codes to zoom to.Ð  * @param {String}
params.region Region code to zoom to.Ð  * @param {Number} params.scale Map
scale to set.Ð  * @param {Number} params.lat Latitude to set viewport to.Ð  *
@param {Number} params.lng Longitude to set viewport to.Ð  * @param {Number}
params.x Number from 0 to 1 specifying the horizontal coordinate of the
central point of the viewport.Ð  * @param {Number} params.y Number from 0 to
1 specifying the vertical coordinate of the central point of the viewport.Ð
* @param {Boolean} params.animate Indicates whether or not to animate the
scale change and transition.Ð  */Ð setFocus: function(config){Ð   var bbox,Ð
        itemBbox,Ð       newBbox,Ð       codes,Ð       i,Ð       point;Ð
config = config || {};Ð   if (config.region) {Ð     codes = [config.region];Ð
    } else if (config.regions) {Ð     codes = config.regions;Ð   }Ð   if
(codes) {Ð     for (i = 0; i < codes.length; i++) {Ð       if
(this.regions[codes[i]]) {Ð         itemBbox =
this.regions[codes[i]].element.shape.getBBox();Ð         if (itemBbox) {Ð
            if (typeof bbox == 'undefined') {Ð             bbox = itemBbox;Ð
            } else {Ð             newBbox = {Ð               x:
Math.min(bbox.x, itemBbox.x),Ð               y: Math.min(bbox.y, itemBbox.y),Ð
                width: Math.max(bbox.x + bbox.width, itemBbox.x +
itemBbox.width) - Math.min(bbox.x, itemBbox.x),Ð
```

```
                                                                height:
Math.max(bbox.y + bbox.height, itemBbox.y + itemBbox.height) -
Math.min(bbox.y, itemBbox.y)Ð              }Ð              bbox = newBbox;Ð
            }Ð         }Ð       }Ð     }Ð     return this.setScale(Ð
Math.min(this.width / bbox.width, this.height / bbox.height),Ð       -
(bbox.x + bbox.width / 2),Ð       - (bbox.y + bbox.height / 2),Ð       true,Ð
        config.animateÐ     );Ð   } else {Ð     if (config.lat && config.lng)
{Ð       point = this.latLngToPoint(config.lat, config.lng);Ð       config.x
= this.transX - point.x / this.scale;Ð       config.y = this.transY -
point.y / this.scale;Ð     } else if (config.x && config.y) {Ð       config.x
*= -this.defaultWidth;Ð       config.y *= -this.defaultHeight;Ð     }Ð
return this.setScale(config.scale * this.baseScale, config.x, config.y, true,
config.animate);Ð   }Ð },Ð getSelected: function(type){Ð   var key,Ð
selected = [];Ð   for (key in this[type]) {Ð     if (this[type]
[key].element.isSelected) {Ð       selected.push(key);Ð     }Ð   }Ð   return
selected;Ð },Ð /**Ð  * Return the codes of currently selected regions.Ð  *
@returns {Array}Ð  */Ð getSelectedRegions: function(){Ð   return
this.getSelected('regions');Ð },Ð /**Ð  * Return the codes of currently
selected markers.Ð  * @returns {Array}Ð  */Ð getSelectedMarkers: function(){Ð
    return this.getSelected('markers');Ð },Ð setSelected: function(type, keys)
{Ð   var i;Ð   if (typeof keys != 'object') {Ð     keys = [keys];Ð   }Ð   if
(jvm.$.isArray(keys)) {Ð     for (i = 0; i < keys.length; i++) {Ð
this[type][keys[i]].element.setSelected(true);Ð     }Ð   } else {Ð     for (i
in keys) {Ð       this[type][i].element.setSelected(!!keys[i]);Ð     }Ð   }Ð
  },Ð /**Ð  * Set or remove selected state for the regions.Ð  * @param
{String|Array|Object} keys If <code>String</code> or <code>Array</code> the
region(s) with the corresponding code(s) will be selected. If <code>Object</
code> was provided its keys are  codes of regions, state of which should be
changed. Selected state will be set if value is true, removed otherwise.Ð  */Ð
  setSelectedRegions: function(keys){Ð   this.setSelected('regions', keys);Ð
  },Ð /**Ð  * Set or remove selected state for the markers.Ð  * @param
{String|Array|Object} keys If <code>String</code> or <code>Array</code> the
marker(s) with the corresponding code(s) will be selected. If <code>Object</
code> was provided its keys are  codes of markers, state of which should be
changed. Selected state will be set if value is true, removed otherwise.Ð  */Ð
  setSelectedMarkers: function(keys){Ð   this.setSelected('markers', keys);Ð
  },Ð clearSelected: function(type){Ð   var select = {},Ð       selected =
this.getSelected(type),Ð       i;Ð   for (i = 0; i < selected.length; i++) {Ð
      select[selected[i]] = false;Ð   };Ð   this.setSelected(type, select);Ð
  },Ð /**Ð  * Remove the selected state from all the currently selected
regions.Ð  */Ð clearSelectedRegions: function(){Ð
this.clearSelected('regions');Ð },Ð /**Ð  * Remove the selected state from
all the currently selected markers.Ð  */Ð clearSelectedMarkers: function(){Ð
    this.clearSelected('markers');Ð },Ð /**Ð  * Return the instance of Map.
Useful when instantiated as a jQuery plug-in.Ð  * @returns {Map}Ð  */Ð
getMapObject: function(){Ð   return this;Ð },Ð /**Ð  * Return the name of the
region by region code.Ð  * @returns {String}Ð  */Ð getRegionName:
function(code){Ð   return this.mapData.paths[code].name;Ð },Ð createRegions:
function(){Ð   var key,Ð       region,Ð       map = this;Ð
this.regionLabelsGroup = this.regionLabelsGroup || this.canvas.addGroup();Ð
for (key in this.mapData.paths) {Ð     region = new jvm.Region({Ð       map:
this,Ð       path: this.mapData.paths[key].path,Ð       code: key,Ð
style: jvm.$.extend(true, {}, this.params.regionStyle),Ð       labelStyle:
jvm.$.extend(true, {}, this.params.regionLabelStyle),Ð       canvas:
this.canvas,Ð       labelsGroup: this.regionLabelsGroup,Ð       label:
this.canvas.mode != 'vml' ? (this.params.labels &&
this.params.labels.regions) : nullÐ     });Ð     jvm.
$(region.shape).bind('selected', function(e, isSelected){Ð
map.container.trigger('regionSelected.jvectormap', [jvm.
$(this.node).attr('data-code'), isSelected, map.getSelectedRegions()]);Ð
```

```
      });Ð     this.regions[key] = {Ð       element: region,Ð       config:
this.mapData.paths[key]Ð     };Ð   }Ð },Ð createMarkers: function(markers) {Ð
    var i,Ð       marker,Ð       point,Ð       markerConfig,Ð
markersArray,Ð       map = this;Ð   this.markersGroup = this.markersGroup ||
this.canvas.addGroup();Ð   this.markerLabelsGroup = this.markerLabelsGroup ||
this.canvas.addGroup();Ð   if (jvm.$.isArray(markers)) {Ð     markersArray =
markers.slice();Ð     markers = {};Ð     for (i = 0; i < markersArray.length;
i++) {Ð       markers[i] = markersArray[i];Ð     }Ð   }Ð   for (i in markers)
{Ð     markerConfig = markers[i] instanceof Array ? {latLng: markers[i]} :
markers[i];Ð     point = this.getMarkerPosition( markerConfig );Ð     if
(point !== false) {Ð       marker = new jvm.Marker({Ð         map: this,Ð
          style: jvm.$.extend(true, {}, this.params.markerStyle, {initial:
markerConfig.style || {}}),Ð         labelStyle: jvm.$.extend(true, {},
this.params.markerLabelStyle),Ð         index: i,Ð         cx: point.x,Ð
          cy: point.y,Ð         group: this.markersGroup,Ð         canvas:
this.canvas,Ð         labelsGroup: this.markerLabelsGroup,Ð         label:
this.canvas.mode != 'vml' ? (this.params.labels &&
this.params.labels.markers) : nullÐ       });Ð       jvm.
$(marker.shape).bind('selected', function(e, isSelected){Ð
map.container.trigger('markerSelected.jvectormap', [jvm.
$(this.node).attr('data-index'), isSelected, map.getSelectedMarkers()]);Ð
        });Ð       if (this.markers[i]) {Ð         this.removeMarkers([i]);Ð
        }Ð       this.markers[i] = {element: marker, config: markerConfig};Ð
      }Ð   }Ð },Ð repositionMarkers: function() {Ð   var i,Ð       point;Ð
for (i in this.markers) {Ð     point =
this.getMarkerPosition( this.markers[i].config );Ð     if (point !== false) {Ð
        this.markers[i].element.setStyle({cx: point.x, cy: point.y});Ð     }Ð
    }Ð },Ð repositionLabels: function() {Ð   var key;Ð   for (key in
this.regions) {Ð     this.regions[key].element.updateLabelPosition();Ð   }Ð
for (key in this.markers) {Ð
this.markers[key].element.updateLabelPosition();Ð   }Ð },Ð getMarkerPosition:
function(markerConfig) {Ð   if (jvm.Map.maps[this.params.map].projection) {Ð
      return this.latLngToPoint.apply(this, markerConfig.latLng || [0, 0]);Ð
    } else {Ð     return {Ð       x: markerConfig.coords[0]*this.scale +
this.transX*this.scale,Ð       y: markerConfig.coords[1]*this.scale +
this.transY*this.scaleÐ     };Ð   }Ð },Ð /**Ð  * Add one marker to the map.Ð
* @param {String} key Marker unique code.Ð  * @param {Object} marker Marker
configuration parameters.Ð  * @param {Array} seriesData Values to add to the
data series.Ð  */Ð addMarker: function(key, marker, seriesData){Ð   var
markers = {},Ð       data = [],Ð       values,Ð       i,Ð       seriesData =
seriesData || [];Ð   markers[key] = marker;Ð   for (i = 0; i <
seriesData.length; i++) {Ð     values = {};Ð     if (typeof seriesData[i] !==
'undefined') {Ð       values[key] = seriesData[i];Ð     }Ð
data.push(values);Ð   }Ð   this.addMarkers(markers, data);Ð },Ð /**Ð  * Add
set of marker to the map.Ð  * @param {Object|Array} markers Markers to add to
the map. In case of array is provided, codes of markers will be set as string
representations of array indexes.Ð  * @param {Array} seriesData Values to add
to the data series.Ð  */Ð addMarkers: function(markers, seriesData){Ð   var i;Ð
    seriesData = seriesData || [];Ð   this.createMarkers(markers);Ð   for (i
= 0; i < seriesData.length; i++) {Ð
this.series.markers[i].setValues(seriesData[i] || {});Ð   };Ð },Ð /**Ð  *
Remove some markers from the map.Ð  * @param {Array} markers Array of marker
codes to be removed.Ð  */Ð removeMarkers: function(markers){Ð   var i;Ð   for
(i = 0; i < markers.length; i++) {Ð
this.markers[ markers[i] ].element.remove();Ð     delete
this.markers[ markers[i] ];Ð   };Ð },Ð /**Ð  * Remove all markers from the
map.Ð  */Ð removeAllMarkers: function(){Ð   var i,Ð       markers = [];Ð
for (i in this.markers) {Ð     markers.push(i);Ð   }Ð
this.removeMarkers(markers)Ð
```

},Ð /**Ð * Converts coordinates expressed as latitude and longitude to the coordinates in pixels on the map.Ð * @param {Number} lat Latitide of point in degrees.Ð * @param {Number} lng Longitude of point in degrees.Ð */Ð latLngToPoint: function(lat, lng) {Ð var point,Ð proj = jvm.Map.maps[this.params.map].projection,Ð centralMeridian = proj.centralMeridian,Ð inset,Ð bbox;Ð if (lng < (-180 + centralMeridian)) {Ð lng += 360;Ð }Ð point = jvm.Proj[proj.type](lat, lng, centralMeridian);Ð inset = this.getInsetForPoint(point.x, point.y);Ð if (inset) {Ð bbox = inset.bbox;Ð point.x = (point.x - bbox[0].x) / (bbox[1].x - bbox[0].x) * inset.width * this.scale;Ð point.y = (point.y - bbox[0].y) / (bbox[1].y - bbox[0].y) * inset.height * this.scale;Ð return {Ð x: point.x + this.transX*this.scale + inset.left*this.scale,Ð y: point.y + this.transY*this.scale + inset.top*this.scaleÐ };Ð } else {Ð return false;Ð }Ð },Ð /**Ð * Converts cartesian coordinates into coordinates expressed as latitude and longitude.Ð * @param {Number} x X-axis of point on map in pixels.Ð * @param {Number} y Y-axis of point on map in pixels.Ð */Ð pointToLatLng: function(x, y) {Ð var proj = jvm.Map.maps[this.params.map].projection,Ð centralMeridian = proj.centralMeridian,Ð insets = jvm.Map.maps[this.params.map].insets,Ð i,Ð inset,Ð bbox,Ð nx,Ð ny;Ð for (i = 0; i < insets.length; i++) {Ð inset = insets[i];Ð bbox = inset.bbox;Ð nx = x - (this.transX*this.scale + inset.left*this.scale);Ð ny = y - (this.transY*this.scale + inset.top*this.scale);Ð nx = (nx / (inset.width * this.scale)) * (bbox[1].x - bbox[0].x) + bbox[0].x;Ð ny = (ny / (inset.height * this.scale)) * (bbox[1].y - bbox[0].y) + bbox[0].y;Ð if (nx > bbox[0].x && nx < bbox[1].x && ny > bbox[0].y && ny < bbox[1].y) {Ð return jvm.Proj[proj.type + '_inv'](nx, -ny, centralMeridian);Ð }Ð }Ð return false;Ð },Ð getInsetForPoint: function(x, y){Ð var insets = jvm.Map.maps[this.params.map].insets,Ð i,Ð bbox;Ð for (i = 0; i < insets.length; i++) {Ð bbox = insets[i].bbox;Ð if (x > bbox[0].x && x < bbox[1].x && y > bbox[0].y && y < bbox[1].y) {Ð return insets[i];Ð }Ð }Ð },Ð createSeries: function(){Ð var i,Ð key;Ð this.series = {Ð markers: [],Ð regions: []Ð };Ð for (key in this.params.series) {Ð for (i = 0; i < this.params.series[key].length; i++) {Ð this.series[key][i] = new jvm.DataSeries(Ð this.params.series[key][i],Ð this[key],Ð thisÐ);Ð }Ð }Ð },Ð /**Ð * Gracefully remove the map and and all its accessories, unbind event handlers.Ð */Ð remove: function(){Ð this.tip.remove();Ð this.container.remove();Ð jvm.$(window).unbind('resize', this.onResize);Ð jvm.$('body').unbind('mouseup', this.onContainerMouseUp);Ð }Ð };Ð jvm.Map.maps = {};Ð jvm.Map.defaultParams = {Ð map: 'world_mill_en',Ð backgroundColor: '#505050',Ð zoomButtons: true,Ð zoomOnScroll: true,Ð zoomOnScrollSpeed: 3,Ð panOnDrag: true,Ð zoomMax: 8,Ð zoomMin: 1,Ð zoomStep: 1.6,Ð zoomAnimate: true,Ð regionsSelectable: false,Ð markersSelectable: false,Ð bindTouchEvents: true,Ð regionStyle: {Ð initial: {Ð fill: 'white',Ð "fill-opacity": 1,Ð stroke: 'none',Ð "stroke-width": 0,Ð "stroke-opacity": 1Ð },Ð hover: {Ð "fill-opacity": 0.8,Ð cursor: 'pointer'Ð },Ð selected: {Ð fill: 'yellow'Ð },Ð selectedHover: {Ð }Ð },Ð regionLabelStyle: {Ð initial: {Ð 'font-family': 'Verdana',Ð 'font-size': '12',Ð 'font-weight': 'bold',Ð cursor: 'default',Ð fill: 'black'Ð },Ð hover: {Ð cursor: 'pointer'Ð }Ð },Ð markerStyle: {Ð initial: {Ð fill: 'grey',Ð stroke: '#505050',Ð "fill-opacity": 1,Ð "stroke-width": 1,Ð "stroke-opacity": 1,Ð r: 5Ð },Ð hover: {Ð stroke: 'black',Ð "stroke-width": 2,Ð cursor: 'pointer'Ð },Ð selected: {Ð fill: 'blue'Ð },Ð selectedHover: {Ð }Ð },Ð markerLabelStyle: {Ð initial: {Ð 'font-family': 'Verdana',Ð 'font-size': '12',Ð 'font-weight': 'bold',Ð cursor: 'default',Ð fill: 'black'Ð },Ð hover: {Ð cursor: 'pointer'Ð }Ð }Ð };Ð jvm.Map.apiEvents = {Ð

```
   onRegionTipShow: 'regionTipShow',Ð onRegionOver: 'regionOver',Ð
onRegionOut: 'regionOut',Ð onRegionClick: 'regionClick',Ð onRegionSelected:
'regionSelected',Ð onMarkerTipShow: 'markerTipShow',Ð onMarkerOver:
'markerOver',Ð onMarkerOut: 'markerOut',Ð onMarkerClick: 'markerClick',Ð
onMarkerSelected: 'markerSelected',Ð onViewportChange: 'viewportChange'Ð};Ð/**Ð
* Creates map with drill-down functionality.Ð* @constructorÐ* @param {Object}
params Parameters to initialize map with.Ð* @param {Number} params.maxLevel
Maximum number of levels user can go throughÐ* @param {Object} params.main
Config of the main map. See <a href="./jvm-map/">jvm.Map</a> for more
information.Ð* @param {Function} params.mapNameByCode Function go generate
map name by region code. Default value is:Ð* <pre>Ð* function(code, multiMap) {Ð
return code.toLowerCase()+'_'+Ð        multiMap.defaultProjection+'_en';ÐÐ*/
pre>Ð* @param {Function} params.mapUrlByCode Function to generate map url by
region code. Default value is:Ð* <pre>Ð* function(code, multiMap){Ð return 'jquery-
jvectormap-data-'+Ð        code.toLowerCase()+'-'+Ð
multiMap.defaultProjection+'-en.js';ÐÐ*/pre>Ð*/Ðjvm.MultiMap = function(params)
{Ð var that = this;Ð this.maps = {};Ð this.params = jvm.$.extend(true, {},
jvm.MultiMap.defaultParams, params);Ð this.params.maxLevel =
this.params.maxLevel || Number.MAX_VALUE;Ð this.params.main =
this.params.main || {};Ð this.params.main.multiMapLevel = 0;Ð this.history =
[ this.addMap(this.params.main.map, this.params.main) ];Ð
this.defaultProjection = this.history[0].mapData.projection.type;Ð
this.mapsLoaded = {};Ð this.params.container.css({position: 'relative'});Ð
this.backButton = jvm.$('<div/>').addClass('jvectormap-
goback').text('Back').appendTo(this.params.container);Ð
this.backButton.hide();Ð this.backButton.click(function(){Ð   that.goBack();Ð
  });Ð this.spinner = jvm.$('<div/>').addClass('jvectormap-
spinner').appendTo(this.params.container);Ð this.spinner.hide();Ð};Ð
jvm.MultiMap.prototype = {Ð addMap: function(name, config){Ð   var cnt = jvm.
$('<div/>').css({Ð     width: '100%',Ð     height: '100%'Ð   });Ð
this.params.container.append(cnt);Ð   this.maps[name] = new jvm.Map(jvm.
$.extend(config, {container: cnt}));Ð   if (this.params.maxLevel >
config.multiMapLevel) {Ð
this.maps[name].container.on('regionClick.jvectormap', {scope: this},
function(e, code){Ð       var multimap = e.data.scope,Ð           mapName =
multimap.params.mapNameByCode(code, multimap);Ð       if (!
multimap.drillDownPromise || multimap.drillDownPromise.state() !== 'pending')
{Ð         multimap.drillDown(mapName, code);Ð       }Ð     });Ð   }Ð
return this.maps[name];Ð },Ð downloadMap: function(code){Ð   var that = this,Ð
        deferred = jvm.$.Deferred();Ð   if (!this.mapsLoaded[code]) {Ð
jvm.$.get(this.params.mapUrlByCode(code, this)).then(function(){Ð
that.mapsLoaded[code] = true;Ð       deferred.resolve();Ð     }, function(){Ð
        deferred.reject();Ð     });Ð   } else {Ð     deferred.resolve();Ð   }Ð
    return deferred;Ð },Ð drillDown: function(name, code){Ð   var currentMap
= this.history[this.history.length - 1],Ð       that = this,Ð
focusPromise = currentMap.setFocus({region: code, animate: true}),Ð
downloadPromise = this.downloadMap(code);Ð   focusPromise.then(function(){Ð
      if (downloadPromise.state() === 'pending') {Ð       that.spinner.show();Ð
      }Ð   });Ð   downloadPromise.always(function(){Ð     that.spinner.hide();Ð
    });Ð   this.drillDownPromise = jvm.$.when(downloadPromise, focusPromise);Ð
    this.drillDownPromise.then(function(){Ð
currentMap.params.container.hide();Ð     if (!that.maps[name]) {Ð
that.addMap(name, {map: name, multiMapLevel: currentMap.params.multiMapLevel
+ 1});Ð     } else {Ð       that.maps[name].params.container.show();Ð     }Ð
      that.history.push( that.maps[name] );Ð     that.backButton.show();Ð
    });Ð },Ð goBack: function(){Ð   var currentMap = this.history.pop(),Ð
        prevMap = this.history[this.history.length - 1],Ð       that = this;Ð
    currentMap.setFocus({scale: 1, x: 0.5, y: 0.5, animate:
true}).then(function(){Ð     currentMap.params.container.hide();Ð
prevMap.params.container.show();Ð
```

```
                                        prevMap.updateSize();Ð     if
(that.history.length === 1) {Ð       that.backButton.hide();Ð     }Ð
prevMap.setFocus({scale: 1, x: 0.5, y: 0.5, animate: true});Ð   });Ð }Ð;Ð
jvm.MultiMap.defaultParams = {Ð mapNameByCode: function(code, multiMap){Ð
return code.toLowerCase()+'_'+multiMap.defaultProjection+'_en';Ð },Ð
mapUrlByCode: function(code, multiMap){Ð   return 'jquery-jvectormap-
data-'+code.toLowerCase()+'-'+multiMap.defaultProjection+'-en.js';Ð }ÐÐ
```

public\assets\js\plugins\ladda\ladda.jquery.min.js

```
/*!Ð* Ladda for jQueryÐ* http://lab.hakim.se/laddaÐ* MIT licensedÐ*Ð*
Copyright (C) 2015 Hakim El Hattab, http://hakim.seÐ*/Ðfunction(t,e){if(void
0===e)return console.error("jQuery required for Ladda.jQuery");var
i=[];e=e.extend(e,{ladda:function(e)
{"stopAll"===e&&t.stopAll()}}),e.fn=e.extend(e.fn,{ladda:function(n){var
r=i.slice.call(arguments,1);return"bind"===n?
(r.unshift(e(this).selector),t.bind.apply(t,r)):e(this).each(function(){var
i,o=e(this);void 0===n?o.data("ladda",t.create(this)):
(i=o.data("ladda"),i[n].apply(i,r))}),this}})})(this.Ladda,this.jQuery);
```

public\assets\js\plugins\morris\morris.js

```
/* @licenseÐMorris.js v0.5.0ÐCopyright 2014 Olly Smith All rights reserved.Ð
Licensed under the BSD-2-Clause License.Ð/*Ð(function() {Ð var $, Morris,
minutesSpecHelper, secondsSpecHelper,Ð   __slice = [].slice,Ð   __bind =
function(fn, me){ return function(){ return fn.apply(me, arguments); }; },Ð
__hasProp = {}.hasOwnProperty,Ð   __extends = function(child, parent) { for
(var key in parent) { if (__hasProp.call(parent, key)) child[key] =
parent[key]; } function ctor() { this.constructor = child; } ctor.prototype =
parent.prototype; child.prototype = new ctor(); child.__super__ =
parent.prototype; return child; },Ð   __indexOf = [].indexOf ||
function(item) { for (var i = 0, l = this.length; i < l; i++) { if (i in this
&& this[i] === item) return i; } return -1; };Ð Morris = window.Morris = {};Ð
$ = jQuery;Ð Morris.EventEmitter = (function() {Ð   function EventEmitter() {}Ð
    EventEmitter.prototype.on = function(name, handler) {Ð     if
(this.handlers == null) {Ð       this.handlers = {};Ð     }Ð     if
(this.handlers[name] == null) {Ð       this.handlers[name] = [];Ð     }Ð
this.handlers[name].push(handler);Ð     return this;Ð   };Ð
EventEmitter.prototype.fire = function() {Ð     var args, handler, name, _i,
_len, _ref, _results;Ð     name = arguments[0], args = 2 <=
arguments.length ? __slice.call(arguments, 1) : [];Ð     if ((this.handlers !
= null) && (this.handlers[name] != null)) {Ð       _ref = this.handlers[name];Ð
        _results = [];Ð       for (_i = 0, _len = _ref.length; _i < _len; _i+
+) {Ð         handler = _ref[_i];Ð         _results.push(handler.apply(null,
args));Ð       }Ð       return _results;Ð     }Ð   };Ð   return EventEmitter;Ð
  })();Ð Morris.commas = function(num) {Ð   var absnum, intnum, ret,
strabsnum;Ð   if (num != null) {Ð     ret = num < 0 ? "-" : "";Ð     absnum =
Math.abs(num);Ð     intnum = Math.floor(absnum).toFixed(0);Ð     ret +=
intnum.replace(/(?=(?:\d{3})+$)(?!^)/g, ',');Ð     strabsnum =
absnum.toString();Ð     if (strabsnum.length > intnum.length) {Ð       ret +=
strabsnum.slice(intnum.length);Ð     }Ð     return ret;Ð   } else {Ð
return '-';Ð   }Ð };Ð Morris.pad2 = function(number) {Ð   return (number <
10 ? '0' : '') + number;Ð };Ð Morris.Grid = (function(_super) {Ð
__extends(Grid, _super);Ð   function Grid(options) {Ð     this.resizeHandler
= __bind(this.resizeHandler, this);Ð     var _this = this;Ð     if (typeof
options.element === 'string') {Ð       this.el =
$(document.getElementById(options.element));Ð     } else {Ð       this.el =
$(options.element);Ð     }Ð     if ((this.el == null) || this.el.length ===
0) {Ð       throw new Error("Graph container element not found");Ð     }Ð
if (this.el.css('position') === 'static') {Ð       this.el.css('position',
'relative');Ð     }Ð     this.options = $.extend({}, this.gridDefaults,
this.defaults || {}, options);Ð     if (typeof this.options.units ===
'string') {Ð       this.options.postUnits = options.units;Ð     }Ð
this.raphael = new Raphael(this.el[0]);Ð     this.elementWidth = null;Ð
this.elementHeight = null;Ð     this.dirty = false;Ð     this.selectFrom =
null;Ð     if (this.init) {Ð       this.init();Ð     }Ð
this.setData(this.options.data);Ð     this.el.bind('mousemove', function(evt)
{Ð       var left, offset, right, width, x;Ð       offset = _this.el.offset();Ð
        x = evt.pageX - offset.left;Ð       if (_this.selectFrom) {Ð
left = _this.data[_this.hitTest(Math.min(x, _this.selectFrom))]._x;Ð
right = _this.data[_this.hitTest(Math.max(x, _this.selectFrom))]._x;Ð
width = right - left;Ð         return _this.selectionRect.attr({Ð
x: left,Ð           width: widthÐ         });Ð       } else {Ð         return
_this.fire('hovermove', x, evt.pageY - offset.top);Ð       }Ð     });Ð
this.el.bind('mouseleave', function(evt) {Ð       if (_this.selectFrom) {Ð
          _this.selectionRect.hide();Ð         _this.selectFrom = null;Ð
        }Ð       return _this.fire('hoverout');Ð     });Ð
this.el.bind('touchstart touchmove touchend', function(evt) {Ð       var
offset, touch;Ð       touch = evt.originalEvent.touches[0] ||
evt.originalEvent.changedTouches[0];Ð       offset = _this.el.offset();Ð
        return _this.fire('hovermove', touch.pageX - offset.left, touch.pageY
```

```
- offset.top);Ð     });Ð     this.el.bind('click', function(evt) {Ð       var
offset;Ð       offset = _this.el.offset();Ð       return
_this.fire('gridclick', evt.pageX - offset.left, evt.pageY - offset.top);Ð
      });Ð     if (this.options.rangeSelect) {Ð       this.selectionRect =
this.raphael.rect(0, 0, 0, this.el.innerHeight()).attr({Ð         fill:
this.options.rangeSelectColor,Ð         stroke: falseÐ
        }).toBack().hide();Ð       this.el.bind('mousedown', function(evt) {Ð
          var offset;Ð         offset = _this.el.offset();Ð         return
_this.startRange(evt.pageX - offset.left);Ð       });Ð
this.el.bind('mouseup', function(evt) {Ð         var offset;Ð         offset
= _this.el.offset();Ð         _this.endRange(evt.pageX - offset.left);Ð
          return _this.fire('hovermove', evt.pageX - offset.left, evt.pageY -
offset.top);Ð       });Ð     }Ð     if (this.options.resize) {Ð
$(window).bind('resize', function(evt) {Ð         if (_this.timeoutId !=
null) {Ð           window.clearTimeout(_this.timeoutId);Ð         }Ð
return _this.timeoutId = window.setTimeout(_this.resizeHandler, 100);Ð
        });Ð     }Ð     this.el.css('-webkit-tap-highlight-color',
'rgba(0,0,0,0)');Ð     if (this.postInit) {Ð       this.postInit();Ð     }Ð
    }Ð   Grid.prototype.gridDefaults = {Ð     dateFormat: null,Ð     axes:
true,Ð     grid: true,Ð     gridLineColor: '#aaa',Ð     gridStrokeWidth: 0.5,Ð
      gridTextColor: '#888',Ð     gridTextSize: 12,Ð     gridTextFamily:
'sans-serif',Ð     gridTextWeight: 'normal',Ð     hideHover: false,Ð
yLabelFormat: null,Ð     xLabelAngle: 0,Ð     numLines: 5,Ð     padding: 25,Ð
      parseTime: true,Ð     postUnits: '',Ð     preUnits: '',Ð     ymax:
'auto',Ð     ymin: 'auto 0',Ð     goals: [],Ð     goalStrokeWidth: 1.0,Ð
goalLineColors: ['#666633', '#999966', '#cc6666', '#663333'],Ð     events: [],Ð
      eventStrokeWidth: 1.0,Ð     eventLineColors: ['#005a04', '#ccffbb',
'#3a5f0b', '#005502'],Ð     rangeSelect: null,Ð     rangeSelectColor: '#eef',Ð
      resize: falseÐ   };Ð   Grid.prototype.setData = function(data, redraw) {Ð
      var e, idx, index, maxGoal, minGoal, ret, row, step, total, y, ykey,
ymax, ymin, yval, _ref;Ð     if (redraw == null) {Ð       redraw = true;Ð
      }Ð     this.options.data = data;Ð     if ((data == null) || data.length
=== 0) {Ð       this.data = [];Ð       this.raphael.clear();Ð       if
(this.hover != null) {Ð         this.hover.hide();Ð       }Ð       return;Ð
      }Ð     ymax = this.cumulative ? 0 : null;Ð     ymin = this.cumulative ?
0 : null;Ð     if (this.options.goals.length > 0) {Ð       minGoal =
Math.min.apply(Math, this.options.goals);Ð       maxGoal =
Math.max.apply(Math, this.options.goals);Ð       ymin = ymin != null ?
Math.min(ymin, minGoal) : minGoal;Ð       ymax = ymax != null ?
Math.max(ymax, maxGoal) : maxGoal;Ð     }Ð     this.data = (function() {Ð
        var _i, _len, _results;Ð       _results = [];Ð       for (index = _i
= 0, _len = data.length; _i < _len; index = ++_i) {Ð         row =
data[index];Ð         ret = {Ð           src: rowÐ         };Ð
ret.label = row[this.options.xkey];Ð         if (this.options.parseTime) {Ð
            ret.x = Morris.parseDate(ret.label);Ð           if
(this.options.dateFormat) {Ð             ret.label =
this.options.dateFormat(ret.x);Ð           } else if (typeof ret.label ===
'number') {Ð             ret.label = new Date(ret.label).toString();Ð
            }Ð         } else {Ð           ret.x = index;Ð           if
(this.options.xLabelFormat) {Ð             ret.label =
this.options.xLabelFormat(ret);Ð           }Ð         }Ð         total = 0;Ð
          ret.y = (function() {Ð           var _j, _len1, _ref, _results1;Ð
            _ref = this.options.ykeys;Ð           _results1 = [];Ð
for (idx = _j = 0, _len1 = _ref.length; _j < _len1; idx = ++_j) {Ð
              ykey = _ref[idx];Ð             yval = row[ykey];Ð
if (typeof yval === 'string') {Ð               yval = parseFloat(yval);Ð
              }Ð             if ((yval != null) && typeof yval !== 'number') {Ð
                yval = null;Ð             }Ð             if (yval != null) {Ð
                if (this.cumulative) {Ð                 total += yval;Ð
                } else {Ð
```

```
                                        if (ymax != null) {Ð
                    ymax = Math.max(yval, ymax);Ð                    ymin =
Math.min(yval, ymin);Ð                  } else {Ð                    ymax =
ymin = yval;Ð                }Ð                }Ð              }Ð
if (this.cumulative && (total != null)) {Ð               ymax =
Math.max(total, ymax);Ð               ymin = Math.min(total, ymin);Ð
             }Ð             _results1.push(yval);Ð           }Ð
return _results1;Ð         }).call(this);Ð         _results.push(ret);Ð
        }Ð       return _results;Ð     }).call(this);Ð     if
(this.options.parseTime) {Ð       this.data = this.data.sort(function(a, b) {Ð
          return (a.x > b.x) - (b.x > a.x);Ð       });Ð     }Ð     this.xmin
= this.data[0].x;Ð     this.xmax = this.data[this.data.length - 1].x;Ð
this.events = [];Ð     if (this.options.events.length > 0) {Ð       if
(this.options.parseTime) {Ð         this.events = (function() {Ð
var _i, _len, _ref, _results;Ð           _ref = this.options.events;Ð
            _results = [];Ð           for (_i = 0, _len = _ref.length; _i <
_len; _i++) {Ð             e = _ref[_i];Ð
_results.push(Morris.parseDate(e));Ð           }Ð           return _results;Ð
          }).call(this);Ð       } else {Ð         this.events =
this.options.events;Ð       }Ð       this.xmax = Math.max(this.xmax,
Math.max.apply(Math, this.events));Ð       this.xmin = Math.min(this.xmin,
Math.min.apply(Math, this.events));Ð     }Ð     if (this.xmin === this.xmax) {Ð
        this.xmin -= 1;Ð       this.xmax += 1;Ð     }Ð     this.ymin =
this.yboundary('min', ymin);Ð     this.ymax = this.yboundary('max', ymax);Ð
      if (this.ymin === this.ymax) {Ð       if (ymin) {Ð         this.ymin -=
1;Ð       }Ð       this.ymax += 1;Ð     }Ð     if (((_ref =
this.options.axes) === true || _ref === 'both' || _ref === 'y') ||
this.options.grid === true) {Ð       if (this.options.ymax ===
this.gridDefaults.ymax && this.options.ymin === this.gridDefaults.ymin) {Ð
          this.grid = this.autoGridLines(this.ymin, this.ymax,
this.options.numLines);Ð         this.ymin = Math.min(this.ymin,
this.grid[0]);Ð         this.ymax = Math.max(this.ymax,
this.grid[this.grid.length - 1]);Ð       } else {Ð         step = (this.ymax
- this.ymin) / (this.options.numLines - 1);Ð         this.grid = (function() {Ð
            var _i, _ref1, _ref2, _results;Ð           _results = [];Ð
            for (y = _i = _ref1 = this.ymin, _ref2 = this.ymax; step > 0 ? _i
<= _ref2 : _i >= _ref2; y = _i += step) {Ð             _results.push(y);Ð
            }Ð           return _results;Ð         }).call(this);Ð       }Ð
      }Ð     this.dirty = true;Ð     if (redraw) {Ð       return
this.redraw();Ð     }Ð   };Ð   Grid.prototype.yboundary =
function(boundaryType, currentValue) {Ð     var boundaryOption,
suggestedValue;Ð     boundaryOption = this.options["y" + boundaryType];Ð
if (typeof boundaryOption === 'string') {Ð       if (boundaryOption.slice(0,
4) === 'auto') {Ð         if (boundaryOption.length > 5) {Ð
suggestedValue = parseInt(boundaryOption.slice(5), 10);Ð           if
(currentValue == null) {Ð             return suggestedValue;Ð           }Ð
            return Math[boundaryType](currentValue, suggestedValue);Ð
          } else {Ð           if (currentValue != null) {Ð             return
currentValue;Ð           } else {Ð             return 0;Ð           }Ð
          }Ð       } else {Ð         return parseInt(boundaryOption, 10);Ð
        }Ð     } else {Ð       return boundaryOption;Ð     }Ð   };Ð
Grid.prototype.autoGridLines = function(ymin, ymax, nlines) {Ð     var gmax,
gmin, grid, smag, span, step, unit, y, ymag;Ð     span = ymax - ymin;Ð
ymag = Math.floor(Math.log(span) / Math.log(10));Ð     unit = Math.pow(10,
ymag);Ð     gmin = Math.floor(ymin / unit) * unit;Ð     gmax =
Math.ceil(ymax / unit) * unit;Ð     step = (gmax - gmin) / (nlines - 1);Ð
if (unit === 1 && step > 1 && Math.ceil(step) !== step) {Ð       step =
Math.ceil(step);Ð       gmax = gmin + step * (nlines - 1);Ð     }Ð     if
(gmin < 0 && gmax > 0) {Ð       gmin = Math.floor(ymin / step) * step;Ð
gmax = Math.ceil(ymax / step) * step;Ð
```

}Ð if (step < 1) {Ð smag = Math.floor(Math.log(step) / Math.log(10));Ð grid = (function() {Ð var _i, _results;Ð _results = [];Ð for (y = _i = gmin; step > 0 ? _i <= gmax : _i >= gmax; y = _i += step) {Ð _results.push(parseFloat(y.toFixed(1 - smag)));Ð }Ð return _results;Ð })();Ð } else {Ð grid = (function() {Ð var _i, _results;Ð _results = [];Ð for (y = _i = gmin; step > 0 ? _i <= gmax : _i >= gmax; y = _i += step) {Ð _results.push(y);Ð }Ð return _results;Ð })();Ð }Ð return grid;Ð };Ð Grid.prototype._calc = function() {Ð var bottomOffsets, gridLine, h, i, w, yLabelWidths, _ref, _ref1;Ð w = this.el.width();Ð h = this.el.height();Ð if (this.elementWidth !== w || this.elementHeight !== h || this.dirty) {Ð this.elementWidth = w;Ð this.elementHeight = h;Ð this.dirty = false;Ð this.left = this.options.padding;Ð this.right = this.elementWidth - this.options.padding;Ð this.top = this.options.padding;Ð this.bottom = this.elementHeight - this.options.padding;Ð if ((_ref = this.options.axes) === true || _ref === 'both' || _ref === 'y') {Ð yLabelWidths = (function() {Ð var _i, _len, _ref1, _results;Ð _ref1 = this.grid;Ð _results = [];Ð for (_i = 0, _len = _ref1.length; _i < _len; _i++) {Ð gridLine = _ref1[_i];Ð _results.push(this.measureText(this.yAxisFormat(gridLine)).width);Ð }Ð return _results;Ð }).call(this);Ð this.left += Math.max.apply(Math, yLabelWidths);Ð }Ð if ((_ref1 = this.options.axes) === true || _ref1 === 'both' || _ref1 === 'x') {Ð bottomOffsets = (function() {Ð var _i, _ref2, _results;Ð _results = [];Ð for (i = _i = 0, _ref2 = this.data.length; 0 <= _ref2 ? _i < _ref2 : _i > _ref2; i = 0 <= _ref2 ? ++_i : --_i) {Ð _results.push(this.measureText(this.data[i].text, -this.options.xLabelAngle).height);Ð }Ð return _results;Ð }).call(this);Ð this.bottom -= Math.max.apply(Math, bottomOffsets);Ð }Ð this.width = Math.max(1, this.right - this.left);Ð this.height = Math.max(1, this.bottom - this.top);Ð this.dx = this.width / (this.xmax - this.xmin);Ð this.dy = this.height / (this.ymax - this.ymin);Ð if (this.calc) {Ð return this.calc();Ð }Ð }Ð };Ð Grid.prototype.transY = function(y) {Ð return this.bottom - (y - this.ymin) * this.dy;Ð };Ð Grid.prototype.transX = function(x) {Ð if (this.data.length === 1) {Ð return (this.left + this.right) / 2;Ð } else {Ð return this.left + (x - this.xmin) * this.dx;Ð }Ð };Ð Grid.prototype.redraw = function() {Ð this.raphael.clear();Ð this._calc();Ð this.drawGrid();Ð this.drawGoals();Ð this.drawEvents();Ð if (this.draw) {Ð return this.draw();Ð }Ð };Ð Grid.prototype.measureText = function(text, angle) {Ð var ret, tt;Ð if (angle == null) {Ð angle = 0;Ð }Ð tt = this.raphael.text(100, 100, text).attr('font-size', this.options.gridTextSize).attr('font-family', this.options.gridTextFamily).attr('font-weight', this.options.gridTextWeight).rotate(angle);Ð ret = tt.getBBox();Ð tt.remove();Ð return ret;Ð };Ð Grid.prototype.yAxisFormat = function(label) {Ð return this.yLabelFormat(label);Ð };Ð Grid.prototype.yLabelFormat = function(label) {Ð if (typeof this.options.yLabelFormat === 'function') {Ð return this.options.yLabelFormat(label);Ð } else {Ð return "" + this.options.preUnits + (Morris.commas(label)) + this.options.postUnits;Ð }Ð };Ð Grid.prototype.drawGrid = function() {Ð var lineY, y, _i, _len, _ref, _ref1, _ref2, _results;Ð if (this.options.grid === false && ((_ref = this.options.axes) !== true && _ref !== 'both' && _ref !== 'y')) {Ð return;Ð }Ð _ref1 = this.grid;Ð _results = [];Ð for (_i = 0, _len = _ref1.length; _i < _len; _i++) {Ð

```
                                                        lineY = _ref1[_i];Ð
        y = this.transY(lineY);Ð       if ((_ref2 = this.options.axes) ===
true || _ref2 === 'both' || _ref2 === 'y') {Ð
this.drawYAxisLabel(this.left - this.options.padding / 2, y,
this.yAxisFormat(lineY));Ð       }Ð       if (this.options.grid) {Ð
_results.push(this.drawGridLine("M" + this.left + "," + y + "H" + (this.left
+ this.width)));Ð       } else {Ð         _results.push(void 0);Ð       }Ð
      }Ð     return _results;Ð   };Ð   Grid.prototype.drawGoals = function() {Ð
      var color, goal, i, _i, _len, _ref, _results;Ð     _ref =
this.options.goals;Ð     _results = [];Ð     for (i = _i = 0, _len =
_ref.length; _i < _len; i = ++_i) {Ð       goal = _ref[i];Ð       color =
this.options.goalLineColors[i % this.options.goalLineColors.length];Ð
_results.push(this.drawGoal(goal, color));Ð     }Ð     return _results;Ð   };Ð
    Grid.prototype.drawEvents = function() {Ð     var color, event, i, _i,
_len, _ref, _results;Ð     _ref = this.events;Ð     _results = [];Ð     for
(i = _i = 0, _len = _ref.length; _i < _len; i = ++_i) {Ð       event =
_ref[i];Ð       color = this.options.eventLineColors[i %
this.options.eventLineColors.length];Ð
_results.push(this.drawEvent(event, color));Ð     }Ð     return _results;Ð
    };Ð   Grid.prototype.drawGoal = function(goal, color) {Ð     return
this.raphael.path("M" + this.left + "," + (this.transY(goal)) + "H" +
this.right).attr('stroke', color).attr('stroke-width',
this.options.goalStrokeWidth);Ð   };Ð   Grid.prototype.drawEvent =
function(event, color) {Ð     return this.raphael.path("M" +
(this.transX(event)) + "," + this.bottom + "V" + this.top).attr('stroke',
color).attr('stroke-width', this.options.eventStrokeWidth);Ð   };Ð
Grid.prototype.drawYAxisLabel = function(xPos, yPos, text) {Ð     return
this.raphael.text(xPos, yPos, text).attr('font-size',
this.options.gridTextSize).attr('font-family',
this.options.gridTextFamily).attr('font-weight',
this.options.gridTextWeight).attr('fill',
this.options.gridTextColor).attr('text-anchor', 'end');Ð   };Ð
Grid.prototype.drawGridLine = function(path) {Ð     return
this.raphael.path(path).attr('stroke',
this.options.gridLineColor).attr('stroke-width',
this.options.gridStrokeWidth);Ð   };Ð   Grid.prototype.startRange =
function(x) {Ð     this.hover.hide();Ð     this.selectFrom = x;Ð     return
this.selectionRect.attr({Ð       x: x,Ð       width: 0Ð     }).show();Ð   };Ð
    Grid.prototype.endRange = function(x) {Ð     var end, start;Ð     if
(this.selectFrom) {Ð       start = Math.min(this.selectFrom, x);Ð       end =
Math.max(this.selectFrom, x);Ð       this.options.rangeSelect.call(this.el, {Ð
          start: this.data[this.hitTest(start)].x,Ð         end:
this.data[this.hitTest(end)].xÐ       });Ð       return this.selectFrom =
null;Ð     }Ð   };Ð   Grid.prototype.resizeHandler = function() {Ð
this.timeoutId = null;Ð     this.raphael.setSize(this.el.width(),
this.el.height());Ð     return this.redraw();Ð   };Ð   return Grid;Ð })
(Morris.EventEmitter);Ð Morris.parseDate = function(date) {Ð   var isecs, m,
msecs, n, o, offsetmins, p, q, r, ret, secs;Ð   if (typeof date === 'number')
{Ð     return date;Ð   }Ð   m = date.match(/^(\d+) Q(\d)$/);Ð   n =
date.match(/^(\d+)-(\d+)$/);Ð   o = date.match(/^(\d+)-(\d+)-(\d+)$/);Ð   p =
date.match(/^(\d+) W(\d+)$/);Ð   q = date.match(/^(\d+)-(\d+)-(\d+)[ T](\d+):
(\d+)(Z|([+-])(\d\d):?(\d\d))?$/);Ð   r = date.match(/^(\d+)-(\d+)-(\d+)[ T]
(\d+):(\d+):(\d+(\.\d+)?)(Z|([+-])(\d\d):?(\d\d))?$/);Ð   if (m) {Ð
return new Date(parseInt(m[1], 10), parseInt(m[2], 10) * 3 - 1, 1).getTime();Ð
    } else if (n) {Ð     return new Date(parseInt(n[1], 10), parseInt(n[2],
10) - 1, 1).getTime();Ð   } else if (o) {Ð     return new Date(parseInt(o[1],
10), parseInt(o[2], 10) - 1, parseInt(o[3], 10)).getTime();Ð   } else if (p) {Ð
      ret = new Date(parseInt(p[1], 10), 0, 1);Ð     if (ret.getDay() !== 4) {Ð
        ret.setMonth(0, 1 + ((4 - ret.getDay()) + 7) % 7);Ð     }Ð     return
ret.getTime() + parseInt(p[2], 10) * 604800000;Ð
```

```
                                                    } else if (q) {Ð     if (!
q[6]) {Ð       return new Date(parseInt(q[1], 10), parseInt(q[2], 10) - 1,
parseInt(q[3], 10), parseInt(q[4], 10), parseInt(q[5], 10)).getTime();Ð     }
else {Ð       offsetmins = 0;Ð       if (q[6] !== 'Z') {Ð         offsetmins
= parseInt(q[8], 10) * 60 + parseInt(q[9], 10);Ð         if (q[7] === '+') {Ð
            offsetmins = 0 - offsetmins;Ð         }Ð       }Ð       return
Date.UTC(parseInt(q[1], 10), parseInt(q[2], 10) - 1, parseInt(q[3], 10),
parseInt(q[4], 10), parseInt(q[5], 10) + offsetmins);Ð     }Ð   } else if (r)
{Ð     secs = parseFloat(r[6]);Ð     isecs = Math.floor(secs);Ð     msecs =
Math.round((secs - isecs) * 1000);Ð     if (!r[8]) {Ð       return new
Date(parseInt(r[1], 10), parseInt(r[2], 10) - 1, parseInt(r[3], 10),
parseInt(r[4], 10), parseInt(r[5], 10), isecs, msecs).getTime();Ð     } else {Ð
        offsetmins = 0;Ð       if (r[8] !== 'Z') {Ð         offsetmins =
parseInt(r[10], 10) * 60 + parseInt(r[11], 10);Ð         if (r[9] === '+') {Ð
            offsetmins = 0 - offsetmins;Ð         }Ð       }Ð       return
Date.UTC(parseInt(r[1], 10), parseInt(r[2], 10) - 1, parseInt(r[3], 10),
parseInt(r[4], 10), parseInt(r[5], 10) + offsetmins, isecs, msecs);Ð     }Ð
    } else {Ð     return new Date(parseInt(date, 10), 0, 1).getTime();Ð   }Ð
  };Ð Morris.Hover = (function() {Ð   Hover.defaults = {Ð     "class":
'morris-hover morris-default-style'Ð   };Ð   function Hover(options) {Ð
if (options == null) {Ð       options = {};Ð     }Ð     this.options =
$.extend({}, Morris.Hover.defaults, options);Ð     this.el = $("<div class='"
+ this.options["class"] + "'></div>");Ð     this.el.hide();Ð
this.options.parent.append(this.el);Ð   }Ð   Hover.prototype.update =
function(html, x, y) {Ð     if (!html) {Ð       return this.hide();Ð     }
else {Ð       this.html(html);Ð       this.show();Ð       return
this.moveTo(x, y);Ð     }Ð   };Ð   Hover.prototype.html = function(content) {Ð
      return this.el.html(content);Ð   };Ð   Hover.prototype.moveTo =
function(x, y) {Ð     var hoverHeight, hoverWidth, left, parentHeight,
parentWidth, top;Ð     parentWidth = this.options.parent.innerWidth();Ð
parentHeight = this.options.parent.innerHeight();Ð     hoverWidth =
this.el.outerWidth();Ð     hoverHeight = this.el.outerHeight();Ð     left =
Math.min(Math.max(0, x - hoverWidth / 2), parentWidth - hoverWidth);Ð     if
(y != null) {Ð       top = y - hoverHeight - 10;Ð       if (top < 0) {Ð
          top = y + 10;Ð         if (top + hoverHeight > parentHeight) {Ð
            top = parentHeight / 2 - hoverHeight / 2;Ð         }Ð       }Ð
      } else {Ð       top = parentHeight / 2 - hoverHeight / 2;Ð     }Ð
return this.el.css({Ð       left: left + "px",Ð       top: parseInt(top) +
"px"Ð     });Ð   };Ð   Hover.prototype.show = function() {Ð     return
this.el.show();Ð   };Ð   Hover.prototype.hide = function() {Ð     return
this.el.hide();Ð   };Ð   return Hover;Ð })();Ð Morris.Line =
(function(_super) {Ð   __extends(Line, _super);Ð   function Line(options) {Ð
      this.hilight = __bind(this.hilight, this);Ð     this.onHoverOut =
__bind(this.onHoverOut, this);Ð     this.onHoverMove =
__bind(this.onHoverMove, this);Ð     this.onGridClick =
__bind(this.onGridClick, this);Ð     if (!(this instanceof Morris.Line)) {Ð
        return new Morris.Line(options);Ð     }Ð
Line.__super__.constructor.call(this, options);Ð   }Ð   Line.prototype.init =
function() {Ð     if (this.options.hideHover !== 'always') {Ð
this.hover = new Morris.Hover({Ð         parent: this.elÐ       });Ð
this.on('hovermove', this.onHoverMove);Ð       this.on('hoverout',
this.onHoverOut);Ð       return this.on('gridclick', this.onGridClick);Ð     }Ð
    };Ð   Line.prototype.defaults = {Ð     lineWidth: 3,Ð     pointSize: 4,Ð
      lineColors: ['#0b62a4', '#7A92A3', '#4da74d', '#afd8f8', '#edc240',
'#cb4b4b', '#9440ed'],Ð     pointStrokeWidths: [1],Ð     pointStrokeColors:
['#ffffff'],Ð     pointFillColors: [],Ð     smooth: true,Ð     xLabels:
'auto',Ð     xLabelFormat: null,Ð     xLabelMargin: 24,Ð     hideHover: falseÐ
    };Ð   Line.prototype.calc = function() {Ð     this.calcPoints();Ð
return this.generatePaths();Ð   };Ð   Line.prototype.calcPoints = function() {Ð
      var row, y, _i, _len, _ref, _results;Ð
```

```
                                                    _ref = this.data;Ð
_results = [];Ð     for (_i = 0, _len = _ref.length; _i < _len; _i++) {Ð
        row = _ref[_i];Ð       row._x = this.transX(row.x);Ð       row._y =
(function() {Ð         var _j, _len1, _ref1, _results1;Ð         _ref1 =
row.y;Ð         _results1 = [];Ð         for (_j = 0, _len1 = _ref1.length;
_j < _len1; _j++) {Ð           y = _ref1[_j];Ð           if (y != null) {Ð
              _results1.push(this.transY(y));Ð           } else {Ð
              _results1.push(y);Ð           }Ð         }Ð         return
_results1;Ð       }).call(this);Ð       _results.push(row._ymax =
Math.min.apply(Math, [this.bottom].concat((function() {Ð         var _j,
_len1, _ref1, _results1;Ð         _ref1 = row._y;Ð         _results1 = [];Ð
          for (_j = 0, _len1 = _ref1.length; _j < _len1; _j++) {Ð           y
= _ref1[_j];Ð           if (y != null) {Ð             _results1.push(y);Ð
            }Ð         }Ð         return _results1;Ð       })()))));Ð     }Ð
      return _results;Ð   };Ð   Line.prototype.hitTest = function(x) {Ð
var index, r, _i, _len, _ref;Ð     if (this.data.length === 0) {Ð
return null;Ð     }Ð     _ref = this.data.slice(1);Ð     for (index = _i = 0,
_len = _ref.length; _i < _len; index = ++_i) {Ð       r = _ref[index];Ð
if (x < (r._x + this.data[index]._x) / 2) {Ð         break;Ð       }Ð     }Ð
      return index;Ð   };Ð   Line.prototype.onGridClick = function(x, y) {Ð
      var index;Ð     index = this.hitTest(x);Ð     return this.fire('click',
index, this.data[index].src, x, y);Ð   };Ð   Line.prototype.onHoverMove =
function(x, y) {Ð     var index;Ð     index = this.hitTest(x);Ð     return
this.displayHoverForRow(index);Ð   };Ð   Line.prototype.onHoverOut =
function() {Ð     if (this.options.hideHover !== false) {Ð       return
this.displayHoverForRow(null);Ð     }Ð   };Ð
Line.prototype.displayHoverForRow = function(index) {Ð     var _ref;Ð     if
(index != null) {Ð       (_ref = this.hover).update.apply(_ref,
this.hoverContentForRow(index));Ð       return this.hilight(index);Ð     }
else {Ð       this.hover.hide();Ð       return this.hilight();Ð     }Ð   };Ð
    Line.prototype.hoverContentForRow = function(index) {Ð     var content,
j, row, y, _i, _len, _ref;Ð     row = this.data[index];Ð     content = "<div
class='morris-hover-row-label'>" + row.label + "</div>";Ð     _ref = row.y;Ð
      for (j = _i = 0, _len = _ref.length; _i < _len; j = ++_i) {Ð       y =
_ref[j];Ð       content += "<div class='morris-hover-point' style='color: " +
(this.colorFor(row, j, 'label')) + "'>\n  " + this.options.labels[j] + ":\n
" + (this.yLabelFormat(y)) + "\n</div>";Ð     }Ð     if (typeof
this.options.hoverCallback === 'function') {Ð       content =
this.options.hoverCallback(index, this.options, content, row.src);Ð     }Ð
      return [content, row._x, row._ymax];Ð   };Ð
Line.prototype.generatePaths = function() {Ð     var coords, i, r, smooth;Ð
      return this.paths = (function() {Ð       var _i, _ref, _ref1, _results;Ð
        _results = [];Ð       for (i = _i = 0, _ref =
this.options.ykeys.length; 0 <= _ref ? _i < _ref : _i > _ref; i = 0 <= _ref ?
++_i : --_i) {Ð         smooth = typeof this.options.smooth === "boolean" ?
this.options.smooth : (_ref1 = this.options.ykeys[i],
__indexOf.call(this.options.smooth, _ref1) >= 0);Ð         coords =
(function() {Ð           var _j, _len, _ref2, _results1;Ð           _ref2 =
this.data;Ð           _results1 = [];Ð           for (_j = 0, _len =
_ref2.length; _j < _len; _j++) {Ð             r = _ref2[_j];Ð             if
(r._y[i] !== void 0) {Ð               _results1.push({Ð                 x:
r._x,Ð                 y: r._y[i]Ð               });Ð             }Ð
           }Ð           return _results1;Ð         }).call(this);Ð
if (coords.length > 1) {Ð
_results.push(Morris.Line.createPath(coords, smooth, this.bottom));Ð
          } else {Ð           _results.push(null);Ð         }Ð       }Ð
return _results;Ð     }).call(this);Ð   };Ð   Line.prototype.draw =
function() {Ð     var _ref;Ð     if ((_ref = this.options.axes) === true ||
_ref === 'both' || _ref === 'x') {Ð       this.drawXAxis();Ð     }Ð
this.drawSeries();Ð
```

```
                        if (this.options.hideHover === false) {Ð       return
this.displayHoverForRow(this.data.length - 1);Ð     }Ð   };Ð
Line.prototype.drawXAxis = function() {Ð     var drawLabel, l, labels,
prevAngleMargin, prevLabelMargin, row, ypos, _i, _len, _results,Ð       _this
= this;Ð     ypos = this.bottom + this.options.padding / 2;Ð
prevLabelMargin = null;Ð     prevAngleMargin = null;Ð     drawLabel =
function(labelText, xpos) {Ð       var label, labelBox, margin, offset,
textBox;Ð       label = _this.drawXAxisLabel(_this.transX(xpos), ypos,
labelText);Ð       textBox = label.getBBox();Ð       label.transform("r" + (-
_this.options.xLabelAngle));Ð       labelBox = label.getBBox();Ð
label.transform("t0," + (labelBox.height / 2) + "...");Ð       if
(_this.options.xLabelAngle !== 0) {Ð         offset = -0.5 * textBox.width *
Math.cos(_this.options.xLabelAngle * Math.PI / 180.0);Ð
label.transform("t" + offset + ",0...");Ð       }Ð       labelBox =
label.getBBox();Ð       if (((prevLabelMargin == null) || prevLabelMargin >=
labelBox.x + labelBox.width || (prevAngleMargin != null) && prevAngleMargin
>= labelBox.x) && labelBox.x >= 0 && (labelBox.x + labelBox.width) <
_this.el.width()) {Ð         if (_this.options.xLabelAngle !== 0) {Ð
            margin = 1.25 * _this.options.gridTextSize /
Math.sin(_this.options.xLabelAngle * Math.PI / 180.0);Ð
prevAngleMargin = labelBox.x - margin;Ð         }Ð         return
prevLabelMargin = labelBox.x - _this.options.xLabelMargin;Ð       } else {Ð
          return label.remove();Ð       }Ð     };Ð     if
(this.options.parseTime) {Ð       if (this.data.length === 1 &&
this.options.xLabels === 'auto') {Ð         labels = [[this.data[0].label,
this.data[0].x]];Ð       } else {Ð         labels =
Morris.labelSeries(this.xmin, this.xmax, this.width, this.options.xLabels,
this.options.xLabelFormat);Ð       }Ð     } else {Ð       labels =
(function() {Ð         var _i, _len, _ref, _results;Ð         _ref =
this.data;Ð         _results = [];Ð         for (_i = 0, _len = _ref.length;
_i < _len; _i++) {Ð           row = _ref[_i];Ð
_results.push([row.label, row.x]);Ð         }Ð         return _results;Ð
        }).call(this);Ð     }Ð     labels.reverse();Ð     _results = [];Ð
for (_i = 0, _len = labels.length; _i < _len; _i++) {Ð       l = labels[_i];Ð
        _results.push(drawLabel(l[0], l[1]));Ð     }Ð     return _results;Ð
    };Ð   Line.prototype.drawSeries = function() {Ð     var i, _i, _j, _ref,
_ref1, _results;Ð     this.seriesPoints = [];Ð     for (i = _i = _ref =
this.options.ykeys.length - 1; _ref <= 0 ? _i <= 0 : _i >= 0; i = _ref <= 0 ?
++_i : --_i) {Ð       this._drawLineFor(i);Ð     }Ð     _results = [];Ð
for (i = _j = _ref1 = this.options.ykeys.length - 1; _ref1 <= 0 ? _j <= 0 :
_j >= 0; i = _ref1 <= 0 ? ++_j : --_j) {Ð
_results.push(this._drawPointFor(i));Ð     }Ð     return _results;Ð   };Ð
Line.prototype._drawPointFor = function(index) {Ð     var circle, row, _i,
_len, _ref, _results;Ð     this.seriesPoints[index] = [];Ð     _ref =
this.data;Ð     _results = [];Ð     for (_i = 0, _len = _ref.length; _i <
_len; _i++) {Ð       row = _ref[_i];Ð       circle = null;Ð       if
(row._y[index] != null) {Ð         circle = this.drawLinePoint(row._x,
row._y[index], this.colorFor(row, index, 'point'), index);Ð       }Ð
_results.push(this.seriesPoints[index].push(circle));Ð     }Ð     return
_results;Ð   };Ð   Line.prototype._drawLineFor = function(index) {Ð     var
path;Ð     path = this.paths[index];Ð     if (path !== null) {Ð       return
this.drawLinePath(path, this.colorFor(null, index, 'line'), index);Ð     }Ð
    };Ð   Line.createPath = function(coords, smooth, bottom) {Ð     var
coord, g, grads, i, ix, lg, path, prevCoord, x1, x2, y1, y2, _i, _len;Ð
path = "";Ð     if (smooth) {Ð       grads = Morris.Line.gradients(coords);Ð
      }Ð     prevCoord = {Ð       y: nullÐ     };Ð     for (i = _i = 0, _len
= coords.length; _i < _len; i = ++_i) {Ð       coord = coords[i];Ð       if
(coord.y != null) {Ð         if (prevCoord.y != null) {Ð           if
(smooth) {Ð             g = grads[i];Ð             lg = grads[i - 1];Ð
              ix = (coord.x - prevCoord.x) / 4;Ð
```

```
                                                                    x1 = prevCoord.x
+ ix;Ð             y1 = Math.min(bottom, prevCoord.y + ix * lg);Ð
x2 = coord.x - ix;Ð             y2 = Math.min(bottom, coord.y - ix * g);Ð
              path += "C" + x1 + "," + y1 + "," + x2 + "," + y2 + "," +
coord.x + "," + coord.y;Ð           } else {Ð             path += "L" +
coord.x + "," + coord.y;Ð           }Ð         } else {Ð           if (!
smooth || (grads[i] != null)) {Ð             path += "M" + coord.x + "," +
coord.y;Ð           }Ð         }Ð       }Ð       prevCoord = coord;Ð     }Ð
      return path;Ð   };Ð   Line.gradients = function(coords) {Ð     var
coord, grad, i, nextCoord, prevCoord, _i, _len, _results;Ð     grad =
function(a, b) {Ð       return (a.y - b.y) / (a.x - b.x);Ð     };Ð
_results = [];Ð     for (i = _i = 0, _len = coords.length; _i < _len; i = +
+_i) {Ð       coord = coords[i];Ð       if (coord.y != null) {Ð
nextCoord = coords[i + 1] || {Ð           y: nullÐ         };Ð
prevCoord = coords[i - 1] || {Ð           y: nullÐ         };Ð         if
((prevCoord.y != null) && (nextCoord.y != null)) {Ð
_results.push(grad(prevCoord, nextCoord));Ð         } else if (prevCoord.y !=
null) {Ð           _results.push(grad(prevCoord, coord));Ð         } else if
(nextCoord.y != null) {Ð           _results.push(grad(coord, nextCoord));Ð
          } else {Ð           _results.push(null);Ð         }Ð       } else {Ð
          _results.push(null);Ð       }Ð     }Ð     return _results;Ð   };Ð
Line.prototype.hilight = function(index) {Ð     var i, _i, _j, _ref, _ref1;Ð
      if (this.prevHilight !== null && this.prevHilight !== index) {Ð
for (i = _i = 0, _ref = this.seriesPoints.length - 1; 0 <= _ref ? _i <=
_ref : _i >= _ref; i = 0 <= _ref ? ++_i : --_i) {Ð         if
(this.seriesPoints[i][this.prevHilight]) {Ð           this.seriesPoints[i]
[this.prevHilight].animate(this.pointShrinkSeries(i));Ð         }Ð       }Ð
      }Ð     if (index !== null && this.prevHilight !== index) {Ð       for
(i = _j = 0, _ref1 = this.seriesPoints.length - 1; 0 <= _ref1 ? _j <= _ref1 :
_j >= _ref1; i = 0 <= _ref1 ? ++_j : --_j) {Ð         if (this.seriesPoints[i]
[index]) {Ð           this.seriesPoints[i]
[index].animate(this.pointGrowSeries(i));Ð         }Ð       }Ð     }Ð
return this.prevHilight = index;Ð   };Ð   Line.prototype.colorFor =
function(row, sidx, type) {Ð     if (typeof this.options.lineColors ===
'function') {Ð       return this.options.lineColors.call(this, row, sidx,
type);Ð     } else if (type === 'point') {Ð       return
this.options.pointFillColors[sidx % this.options.pointFillColors.length] ||
this.options.lineColors[sidx % this.options.lineColors.length];Ð     } else {Ð
        return this.options.lineColors[sidx % this.options.lineColors.length];Ð
      }Ð   };Ð   Line.prototype.drawXAxisLabel = function(xPos, yPos, text) {Ð
      return this.raphael.text(xPos, yPos, text).attr('font-size',
this.options.gridTextSize).attr('font-family',
this.options.gridTextFamily).attr('font-weight',
this.options.gridTextWeight).attr('fill', this.options.gridTextColor);Ð   };Ð
    Line.prototype.drawLinePath = function(path, lineColor, lineIndex) {Ð
return this.raphael.path(path).attr('stroke', lineColor).attr('stroke-width',
this.lineWidthForSeries(lineIndex));Ð   };Ð   Line.prototype.drawLinePoint =
function(xPos, yPos, pointColor, lineIndex) {Ð     return
this.raphael.circle(xPos, yPos,
this.pointSizeForSeries(lineIndex)).attr('fill', pointColor).attr('stroke-
width', this.pointStrokeWidthForSeries(lineIndex)).attr('stroke',
this.pointStrokeColorForSeries(lineIndex));Ð   };Ð
Line.prototype.pointStrokeWidthForSeries = function(index) {Ð     return
this.options.pointStrokeWidths[index % this.options.pointStrokeWidths.length];Ð
    };Ð   Line.prototype.pointStrokeColorForSeries = function(index) {Ð
return this.options.pointStrokeColors[index %
this.options.pointStrokeColors.length];Ð   };Ð
Line.prototype.lineWidthForSeries = function(index) {Ð     if
(this.options.lineWidth instanceof Array) {Ð       return
this.options.lineWidth[index % this.options.lineWidth.length];Ð
```

```
                                                                    } else {Đ
        return this.options.lineWidth;Đ     }Đ   };Đ
Line.prototype.pointSizeForSeries = function(index) {Đ     if
(this.options.pointSize instanceof Array) {Đ       return
this.options.pointSize[index % this.options.pointSize.length];Đ     } else {Đ
        return this.options.pointSize;Đ     }Đ   };Đ
Line.prototype.pointGrowSeries = function(index) {Đ     return
Raphael.animation({Đ       r: this.pointSizeForSeries(index) + 3Đ     }, 25,
'linear');Đ   };Đ   Line.prototype.pointShrinkSeries = function(index) {Đ
return Raphael.animation({Đ       r: this.pointSizeForSeries(index)Đ     },
25, 'linear');Đ   };Đ   return Line;Đ })(Morris.Grid);Đ Morris.labelSeries =
function(dmin, dmax, pxwidth, specName, xLabelFormat) {Đ   var d, d0,
ddensity, name, ret, s, spec, t, _i, _len, _ref;Đ   ddensity = 200 * (dmax -
dmin) / pxwidth;Đ   d0 = new Date(dmin);Đ   spec =
Morris.LABEL_SPECS[specName];Đ   if (spec === void 0) {Đ     _ref =
Morris.AUTO_LABEL_ORDER;Đ     for (_i = 0, _len = _ref.length; _i < _len; _i+
+) {Đ       name = _ref[_i];Đ       s = Morris.LABEL_SPECS[name];Đ       if
(ddensity >= s.span) {Đ         spec = s;Đ         break;Đ       }Đ     }Đ   }Đ
    if (spec === void 0) {Đ     spec = Morris.LABEL_SPECS["second"];Đ   }Đ
if (xLabelFormat) {Đ     spec = $.extend({}, spec, {Đ       fmt: xLabelFormatĐ
      });Đ   }Đ   d = spec.start(d0);Đ   ret = [];Đ   while ((t =
d.getTime()) <= dmax) {Đ     if (t >= dmin) {Đ       ret.push([spec.fmt(d),
t]);Đ     }Đ     spec.incr(d);Đ   }Đ   return ret;Đ };Đ minutesSpecHelper =
function(interval) {Đ   return {Đ     span: interval * 60 * 1000,Đ     start:
function(d) {Đ       return new Date(d.getFullYear(), d.getMonth(),
d.getDate(), d.getHours());Đ     },Đ     fmt: function(d) {Đ       return ""
+ (Morris.pad2(d.getHours())) + ":" + (Morris.pad2(d.getMinutes()));Đ     },Đ
      incr: function(d) {Đ       return d.setUTCMinutes(d.getUTCMinutes() +
interval);Đ     }Đ   };Đ };Đ secondsSpecHelper = function(interval) {Đ
return {Đ     span: interval * 1000,Đ     start: function(d) {Đ       return
new Date(d.getFullYear(), d.getMonth(), d.getDate(), d.getHours(),
d.getMinutes());Đ     },Đ     fmt: function(d) {Đ       return "" +
(Morris.pad2(d.getHours())) + ":" + (Morris.pad2(d.getMinutes())) + ":" +
(Morris.pad2(d.getSeconds()));Đ     },Đ     incr: function(d) {Đ       return
d.setUTCSeconds(d.getUTCSeconds() + interval);Đ     }Đ   };Đ };Đ
Morris.LABEL_SPECS = {Đ   "decade": {Đ     span: 172800000000,Đ     start:
function(d) {Đ       return new Date(d.getFullYear() - d.getFullYear() % 10,
0, 1);Đ     },Đ     fmt: function(d) {Đ       return "" + (d.getFullYear());Đ
      },Đ     incr: function(d) {Đ       return d.setFullYear(d.getFullYear()
+ 10);Đ     }Đ   },Đ   "year": {Đ     span: 17280000000,Đ     start:
function(d) {Đ       return new Date(d.getFullYear(), 0, 1);Đ     },Đ
fmt: function(d) {Đ       return "" + (d.getFullYear());Đ     },Đ     incr:
function(d) {Đ       return d.setFullYear(d.getFullYear() + 1);Đ     }Đ   },Đ
    "month": {Đ     span: 2419200000,Đ     start: function(d) {Đ       return
new Date(d.getFullYear(), d.getMonth(), 1);Đ     },Đ     fmt: function(d) {Đ
        return "" + (d.getFullYear()) + "-" + (Morris.pad2(d.getMonth() + 1));Đ
      },Đ     incr: function(d) {Đ       return d.setMonth(d.getMonth() + 1);Đ
      }Đ   },Đ   "week": {Đ     span: 604800000,Đ     start: function(d) {Đ
        return new Date(d.getFullYear(), d.getMonth(), d.getDate());Đ     },Đ
      fmt: function(d) {Đ       return "" + (d.getFullYear()) + "-" +
(Morris.pad2(d.getMonth() + 1)) + "-" + (Morris.pad2(d.getDate()));Đ     },Đ
      incr: function(d) {Đ       return d.setDate(d.getDate() + 7);Đ     }Đ
    },Đ   "day": {Đ     span: 86400000,Đ     start: function(d) {Đ
return new Date(d.getFullYear(), d.getMonth(), d.getDate());Đ     },Đ
fmt: function(d) {Đ       return "" + (d.getFullYear()) + "-" +
(Morris.pad2(d.getMonth() + 1)) + "-" + (Morris.pad2(d.getDate()));Đ     },Đ
      incr: function(d) {Đ       return d.setDate(d.getDate() + 1);Đ     }Đ
    },Đ   "hour": minutesSpecHelper(60),Đ   "30min": minutesSpecHelper(30),Đ
    "15min": minutesSpecHelper(15),Đ   "10min": minutesSpecHelper(10),Đ
"5min": minutesSpecHelper(5),Đ
```

```
                                    "minute": minutesSpecHelper(1),Ð   "30sec":
secondsSpecHelper(30),Ð   "15sec": secondsSpecHelper(15),Ð   "10sec":
secondsSpecHelper(10),Ð   "5sec": secondsSpecHelper(5),Ð   "second":
secondsSpecHelper(1)Ð };Ð Morris.AUTO_LABEL_ORDER = ["decade", "year",
"month", "week", "day", "hour", "30min", "15min", "10min", "5min", "minute",
"30sec", "15sec", "10sec", "5sec", "second"];Ð Morris.Area =
(function(_super) {Ð   var areaDefaults;Ð   __extends(Area, _super);Ð
areaDefaults = {Ð     fillOpacity: 'auto',Ð     behaveLikeLine: falseÐ   };Ð
    function Area(options) {Ð     var areaOptions;Ð     if (!(this instanceof
Morris.Area)) {Ð       return new Morris.Area(options);Ð     }Ð
areaOptions = $.extend({}, areaDefaults, options);Ð     this.cumulative = !
areaOptions.behaveLikeLine;Ð     if (areaOptions.fillOpacity === 'auto') {Ð
        areaOptions.fillOpacity = areaOptions.behaveLikeLine ? .8 : 1;Ð     }Ð
      Area.__super__.constructor.call(this, areaOptions);Ð   }Ð
Area.prototype.calcPoints = function() {Ð     var row, total, y, _i, _len,
_ref, _results;Ð     _ref = this.data;Ð     _results = [];Ð     for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð       row = _ref[_i];Ð       row._x =
this.transX(row.x);Ð       total = 0;Ð       row._y = (function() {Ð
var _j, _len1, _ref1, _results1;Ð         _ref1 = row.y;Ð         _results1 =
[];Ð         for (_j = 0, _len1 = _ref1.length; _j < _len1; _j++) {Ð
            y = _ref1[_j];Ð           if (this.options.behaveLikeLine) {Ð
              _results1.push(this.transY(y));Ð           } else {Ð
              total += y || 0;Ð
_results1.push(this.transY(total));Ð           }Ð         }Ð         return
_results1;Ð       }).call(this);Ð       _results.push(row._ymax =
Math.max.apply(Math, row._y));Ð     }Ð     return _results;Ð   };Ð
Area.prototype.drawSeries = function() {Ð     var i, range, _i, _j, _k, _len,
_ref, _ref1, _results, _results1, _results2;Ð     this.seriesPoints = [];Ð
      if (this.options.behaveLikeLine) {Ð       range = (function() {Ð
          _results = [];Ð         for (var _i = 0, _ref =
this.options.ykeys.length - 1; 0 <= _ref ? _i <= _ref : _i >= _ref; 0 <=
_ref ? _i++ : _i--){ _results.push(_i); }Ð         return _results;Ð
        }).apply(this);Ð     } else {Ð       range = (function() {Ð
_results1 = [];Ð         for (var _j = _ref1 = this.options.ykeys.length - 1;
_ref1 <= 0 ? _j <= 0 : _j >= 0; _ref1 <= 0 ? _j++ : _j--)
{ _results1.push(_j); }Ð         return _results1;Ð       }).apply(this);Ð
      }Ð     _results2 = [];Ð     for (_k = 0, _len = range.length; _k <
_len; _k++) {Ð       i = range[_k];Ð       this._drawFillFor(i);Ð
this._drawLineFor(i);Ð       _results2.push(this._drawPointFor(i));Ð     }Ð
      return _results2;Ð   };Ð   Area.prototype._drawFillFor =
function(index) {Ð     var path;Ð     path = this.paths[index];Ð     if
(path !== null) {Ð       path = path + ("L" + (this.transX(this.xmax)) + ","
+ this.bottom + "L" + (this.transX(this.xmin)) + "," + this.bottom + "Z");Ð
        return this.drawFilledPath(path, this.fillForSeries(index));Ð     }Ð
    };Ð   Area.prototype.fillForSeries = function(i) {Ð     var color;Ð
color = Raphael.rgb2hsl(this.colorFor(this.data[i], i, 'line'));Ð     return
Raphael.hsl(color.h, this.options.behaveLikeLine ? color.s * 0.9 : color.s *
0.75, Math.min(0.98, this.options.behaveLikeLine ? color.l * 1.2 : color.l *
1.25));Ð   };Ð   Area.prototype.drawFilledPath = function(path, fill) {Ð
return this.raphael.path(path).attr('fill', fill).attr('fill-opacity',
this.options.fillOpacity).attr('stroke', 'none');Ð   };Ð   return Area;Ð })
(Morris.Line);Ð Morris.Bar = (function(_super) {Ð   __extends(Bar, _super);Ð
    function Bar(options) {Ð     this.onHoverOut = __bind(this.onHoverOut,
this);Ð     this.onHoverMove = __bind(this.onHoverMove, this);Ð
this.onGridClick = __bind(this.onGridClick, this);Ð     if (!(this instanceof
Morris.Bar)) {Ð       return new Morris.Bar(options);Ð     }Ð
Bar.__super__.constructor.call(this, $.extend({}, options, {Ð
parseTime: falseÐ     }));Ð   }Ð   Bar.prototype.init = function() {Ð
this.cumulative = this.options.stacked;Ð     if (this.options.hideHover !==
'always') {Ð
```

```
                    this.hover = new Morris.Hover({Ð         parent: this.elÐ
        });Ð       this.on('hovermove', this.onHoverMove);Ð
this.on('hoverout', this.onHoverOut);Ð       return this.on('gridclick',
this.onGridClick);Ð     }Ð   };Ð   Bar.prototype.defaults = {Ð
barSizeRatio: 0.75,Ð     barGap: 3,Ð     barColors: ['#0b62a4', '#7a92a3',
'#4da74d', '#afd8f8', '#edc240', '#cb4b4b', '#9440ed'],Ð     barOpacity: 1.0,Ð
      barRadius: [0, 0, 0, 0],Ð     xLabelMargin: 50Ð   };Ð
Bar.prototype.calc = function() {Ð     var _ref;Ð     this.calcBars();Ð
if (this.options.hideHover === false) {Ð       return (_ref =
this.hover).update.apply(_ref, this.hoverContentForRow(this.data.length - 1));Ð
      }Ð   };Ð   Bar.prototype.calcBars = function() {Ð     var idx, row, y,
_i, _len, _ref, _results;Ð     _ref = this.data;Ð     _results = [];Ð     for
(idx = _i = 0, _len = _ref.length; _i < _len; idx = ++_i) {Ð       row =
_ref[idx];Ð       row._x = this.left + this.width * (idx + 0.5) /
this.data.length;Ð       _results.push(row._y = (function() {Ð         var
_j, _len1, _ref1, _results1;Ð         _ref1 = row.y;Ð         _results1 = [];Ð
          for (_j = 0, _len1 = _ref1.length; _j < _len1; _j++) {Ð           y
= _ref1[_j];Ð           if (y != null) {Ð
_results1.push(this.transY(y));Ð           } else {Ð
_results1.push(null);Ð           }Ð         }Ð         return _results1;Ð
        }).call(this));Ð     }Ð     return _results;Ð   };Ð
Bar.prototype.draw = function() {Ð     var _ref;Ð     if ((_ref =
this.options.axes) === true || _ref === 'both' || _ref === 'x') {Ð
this.drawXAxis();Ð     }Ð     return this.drawSeries();Ð   };Ð
Bar.prototype.drawXAxis = function() {Ð     var i, label, labelBox, margin,
offset, prevAngleMargin, prevLabelMargin, row, textBox, ypos, _i, _ref,
_results;Ð     ypos = this.bottom + (this.options.xAxisLabelTopPadding ||
this.options.padding / 2);Ð     prevLabelMargin = null;Ð     prevAngleMargin
= null;Ð     _results = [];Ð     for (i = _i = 0, _ref = this.data.length; 0
<= _ref ? _i < _ref : _i > _ref; i = 0 <= _ref ? ++_i : --_i) {Ð       row =
this.data[this.data.length - 1 - i];Ð       label =
this.drawXAxisLabel(row._x, ypos, row.label);Ð       textBox =
label.getBBox();Ð       label.transform("r" + (-this.options.xLabelAngle));Ð
        labelBox = label.getBBox();Ð       label.transform("t0," +
(labelBox.height / 2) + "...");Ð       if (this.options.xLabelAngle !== 0) {Ð
          offset = -0.5 * textBox.width * Math.cos(this.options.xLabelAngle *
Math.PI / 180.0);Ð         label.transform("t" + offset + ",0...");Ð       }Ð
        if (((prevLabelMargin == null) || prevLabelMargin >= labelBox.x +
labelBox.width || (prevAngleMargin != null) && prevAngleMargin >= labelBox.x)
&& labelBox.x >= 0 && (labelBox.x + labelBox.width) < this.el.width()) {Ð
          if (this.options.xLabelAngle !== 0) {Ð           margin = 1.25 *
this.options.gridTextSize / Math.sin(this.options.xLabelAngle * Math.PI /
180.0);Ð           prevAngleMargin = labelBox.x - margin;Ð         }Ð
_results.push(prevLabelMargin = labelBox.x - this.options.xLabelMargin);Ð
        } else {Ð         _results.push(label.remove());Ð       }Ð     }Ð
return _results;Ð   };Ð   Bar.prototype.drawSeries = function() {Ð     var
barWidth, bottom, groupWidth, idx, lastTop, left, leftPadding, numBars, row,
sidx, size, spaceLeft, top, ypos, zeroPos;Ð     groupWidth = this.width /
this.options.data.length;Ð     numBars = this.options.stacked ? 1 :
this.options.ykeys.length;Ð     barWidth = (groupWidth *
this.options.barSizeRatio - this.options.barGap * (numBars - 1)) / numBars;Ð
      if (this.options.barSize) {Ð       barWidth = Math.min(barWidth,
this.options.barSize);Ð     }Ð     spaceLeft = groupWidth - barWidth *
numBars - this.options.barGap * (numBars - 1);Ð     leftPadding = spaceLeft /
2;Ð     zeroPos = this.ymin <= 0 && this.ymax >= 0 ? this.transY(0) : null;Ð
      return this.bars = (function() {Ð       var _i, _len, _ref, _results;Ð
        _ref = this.data;Ð       _results = [];Ð       for (idx = _i = 0,
_len = _ref.length; _i < _len; idx = ++_i) {Ð         row = _ref[idx];Ð
          lastTop = 0;Ð         _results.push((function() {Ð           var
_j, _len1, _ref1, _results1;Ð
```

```
                                        _ref1 = row._y;Ð           _results1
= [];Ð           for (sidx = _j = 0, _len1 = _ref1.length; _j < _len1; sidx =
++_j) {Ð             ypos = _ref1[sidx];Ð             if (ypos !== null) {Ð
                if (zeroPos) {Ð                 top = Math.min(ypos, zeroPos);Ð
                  bottom = Math.max(ypos, zeroPos);Ð               } else {Ð
                  top = ypos;Ð                 bottom = this.bottom;Ð
                }Ð               left = this.left + idx * groupWidth +
leftPadding;Ð               if (!this.options.stacked) {Ð
left += sidx * (barWidth + this.options.barGap);Ð               }Ð
                size = bottom - top;Ð               if
(this.options.verticalGridCondition &&
this.options.verticalGridCondition(row.x)) {Ð
this.drawBar(this.left + idx * groupWidth, this.top, groupWidth,
Math.abs(this.top - this.bottom), this.options.verticalGridColor,
this.options.verticalGridOpacity, this.options.barRadius);Ð               }Ð
                if (this.options.stacked) {Ð                 top -= lastTop;Ð
                }Ð               this.drawBar(left, top, barWidth, size,
this.colorFor(row, sidx, 'bar'), this.options.barOpacity,
this.options.barRadius);Ð               _results1.push(lastTop += size);Ð
              } else {Ð               _results1.push(null);Ð             }Ð
            }Ð           return _results1;Ð         }).call(this));Ð       }Ð
        return _results;Ð     }).call(this);Ð   };Ð   Bar.prototype.colorFor
= function(row, sidx, type) {Ð     var r, s;Ð     if (typeof
this.options.barColors === 'function') {Ð       r = {Ð         x: row.x,Ð
          y: row.y[sidx],Ð         label: row.labelÐ       };Ð       s = {Ð
          index: sidx,Ð         key: this.options.ykeys[sidx],Ð
label: this.options.labels[sidx]Ð       };Ð       return
this.options.barColors.call(this, r, s, type);Ð     } else {Ð       return
this.options.barColors[sidx % this.options.barColors.length];Ð     }Ð   };Ð
Bar.prototype.hitTest = function(x) {Ð     if (this.data.length === 0) {Ð
        return null;Ð     }Ð     x = Math.max(Math.min(x, this.right),
this.left);Ð     return Math.min(this.data.length - 1, Math.floor((x -
this.left) / (this.width / this.data.length)));Ð   };Ð
Bar.prototype.onGridClick = function(x, y) {Ð     var index;Ð     index =
this.hitTest(x);Ð     return this.fire('click', index, this.data[index].src,
x, y);Ð   };Ð   Bar.prototype.onHoverMove = function(x, y) {Ð     var index,
_ref;Ð     index = this.hitTest(x);Ð     return (_ref =
this.hover).update.apply(_ref, this.hoverContentForRow(index));Ð   };Ð
Bar.prototype.onHoverOut = function() {Ð     if (this.options.hideHover !==
false) {Ð       return this.hover.hide();Ð     }Ð   };Ð
Bar.prototype.hoverContentForRow = function(index) {Ð     var content, j,
row, x, y, _i, _len, _ref;Ð     row = this.data[index];Ð     content = "<div
class='morris-hover-row-label'>" + row.label + "</div>";Ð     _ref = row.y;Ð
      for (j = _i = 0, _len = _ref.length; _i < _len; j = ++_i) {Ð       y =
_ref[j];Ð       content += "<div class='morris-hover-point' style='color: " +
(this.colorFor(row, j, 'label')) + "'>\n  " + this.options.labels[j] + ":\n
" + (this.yLabelFormat(y)) + "\n</div>";Ð     }Ð     if (typeof
this.options.hoverCallback === 'function') {Ð       content =
this.options.hoverCallback(index, this.options, content, row.src);Ð     }Ð
      x = this.left + (index + 0.5) * this.width / this.data.length;Ð
return [content, x];Ð   };Ð   Bar.prototype.drawXAxisLabel = function(xPos,
yPos, text) {Ð     var label;Ð     return label = this.raphael.text(xPos,
yPos, text).attr('font-size', this.options.gridTextSize).attr('font-family',
this.options.gridTextFamily).attr('font-weight',
this.options.gridTextWeight).attr('fill', this.options.gridTextColor);Ð   };Ð
    Bar.prototype.drawBar = function(xPos, yPos, width, height, barColor,
opacity, radiusArray) {Ð     var maxRadius, path;Ð     maxRadius =
Math.max.apply(Math, radiusArray);Ð     if (maxRadius === 0 || maxRadius >
height) {Ð       path = this.raphael.rect(xPos, yPos, width, height);Ð     }
else {Ð
```

```
              path = this.raphael.path(this.roundedRect(xPos, yPos, width,
height, radiusArray));Ð     }Ð     return path.attr('fill',
barColor).attr('fill-opacity', opacity).attr('stroke', 'none');Ð   };Ð
Bar.prototype.roundedRect = function(x, y, w, h, r) {Ð     if (r == null) {Ð
        r = [0, 0, 0, 0];Ð     }Ð     return ["M", x, r[0] + y, "Q", x, y, x
+ r[0], y, "L", x + w - r[1], y, "Q", x + w, y, x + w, y + r[1], "L", x + w,
y + h - r[2], "Q", x + w, y + h, x + w - r[2], y + h, "L", x + r[3], y + h,
"Q", x, y + h, x, y + h - r[3], "Z"];Ð   };Ð   return Bar;Ð })(Morris.Grid);Ð
Morris.Donut = (function(_super) {Ð   __extends(Donut, _super);Ð
Donut.prototype.defaults = {Ð     colors: ['#0B62A4', '#3980B5', '#679DC6',
'#95BBD7', '#B0CCE1', '#095791', '#095085', '#083E67', '#052C48', '#042135'],Ð
      backgroundColor: '#FFFFFF',Ð     labelColor: '#000000',Ð     formatter:
Morris.commas,Ð     resize: falseÐ   };Ð   function Donut(options) {Ð
this.resizeHandler = __bind(this.resizeHandler, this);Ð     this.select =
__bind(this.select, this);Ð     this.click = __bind(this.click, this);Ð
var _this = this;Ð     if (!(this instanceof Morris.Donut)) {Ð       return
new Morris.Donut(options);Ð     }Ð     this.options = $.extend({},
this.defaults, options);Ð     if (typeof options.element === 'string') {Ð
        this.el = $(document.getElementById(options.element));Ð     } else {Ð
        this.el = $(options.element);Ð     }Ð     if (this.el === null ||
this.el.length === 0) {Ð       throw new Error("Graph placeholder not
found.");Ð     }Ð     if (options.data === void 0 || options.data.length ===
0) {Ð       return;Ð     }Ð     this.raphael = new Raphael(this.el[0]);Ð
if (this.options.resize) {Ð       $(window).bind('resize', function(evt) {Ð
          if (_this.timeoutId != null) {Ð
window.clearTimeout(_this.timeoutId);Ð         }Ð         return
_this.timeoutId = window.setTimeout(_this.resizeHandler, 100);Ð       });Ð
      }Ð     this.setData(options.data);Ð   }Ð   Donut.prototype.redraw =
function() {Ð     var C, cx, cy, i, idx, last, max_value, min, next, seg,
total, value, w, _i, _j, _k, _len, _len1, _len2, _ref, _ref1, _ref2, _results;Ð
      this.raphael.clear();Ð     cx = this.el.width() / 2;Ð     cy =
this.el.height() / 2;Ð     w = (Math.min(cx, cy) - 10) / 3;Ð     total = 0;Ð
      _ref = this.values;Ð     for (_i = 0, _len = _ref.length; _i < _len; _i+
+) {Ð       value = _ref[_i];Ð       total += value;Ð     }Ð     min = 5 / (2
* w);Ð     C = 1.9999 * Math.PI - min * this.data.length;Ð     last = 0;Ð
idx = 0;Ð     this.segments = [];Ð     _ref1 = this.values;Ð     for (i = _j
= 0, _len1 = _ref1.length; _j < _len1; i = ++_j) {Ð       value = _ref1[i];Ð
        next = last + min + C * (value / total);Ð       seg = new
Morris.DonutSegment(cx, cy, w * 2, w, last, next, this.data[i].color ||
this.options.colors[idx % this.options.colors.length],
this.options.backgroundColor, idx, this.raphael);Ð       seg.render();Ð
this.segments.push(seg);Ð       seg.on('hover', this.select);Ð
seg.on('click', this.click);Ð       last = next;Ð       idx += 1;Ð     }Ð
this.text1 = this.drawEmptyDonutLabel(cx, cy - 10, this.options.labelColor,
15, 800);Ð     this.text2 = this.drawEmptyDonutLabel(cx, cy + 10,
this.options.labelColor, 14);Ð     max_value = Math.max.apply(Math,
this.values);Ð     idx = 0;Ð     _ref2 = this.values;Ð     _results = [];Ð
      for (_k = 0, _len2 = _ref2.length; _k < _len2; _k++) {Ð       value =
_ref2[_k];Ð       if (value === max_value) {Ð         this.select(idx);Ð
          break;Ð       }Ð       _results.push(idx += 1);Ð     }Ð     return
_results;Ð   };Ð   Donut.prototype.setData = function(data) {Ð     var row;Ð
      this.data = data;Ð     this.values = (function() {Ð       var _i, _len,
_ref, _results;Ð       _ref = this.data;Ð       _results = [];Ð       for (_i
= 0, _len = _ref.length; _i < _len; _i++) {Ð         row = _ref[_i];Ð
_results.push(parseFloat(row.value));Ð       }Ð       return _results;Ð
      }).call(this);Ð     return this.redraw();Ð   };Ð
Donut.prototype.click = function(idx) {Ð     return this.fire('click', idx,
this.data[idx]);Ð   };Ð   Donut.prototype.select = function(idx) {Ð     var
row, s, segment, _i, _len, _ref;Ð     _ref = this.segments;Ð     for (_i = 0,
_len = _ref.length; _i < _len; _i++) {Ð
```

```
                                                s = _ref[_i];Ð
s.deselect();Ð     }Ð     segment = this.segments[idx];Ð     segment.select();Ð
      row = this.data[idx];Ð     return this.setLabels(row.label,
this.options.formatter(row.value, row));Ð   };Ð   Donut.prototype.setLabels =
function(label1, label2) {Ð     var inner, maxHeightBottom, maxHeightTop,
maxWidth, text1bbox, text1scale, text2bbox, text2scale;Ð     inner =
(Math.min(this.el.width() / 2, this.el.height() / 2) - 10) * 2 / 3;Ð
maxWidth = 1.8 * inner;Ð     maxHeightTop = inner / 2;Ð     maxHeightBottom =
inner / 3;Ð     this.text1.attr({Ð       text: label1,Ð       transform: ''Ð
      });Ð     text1bbox = this.text1.getBBox();Ð     text1scale =
Math.min(maxWidth / text1bbox.width, maxHeightTop / text1bbox.height);Ð
this.text1.attr({Ð       transform: "S" + text1scale + "," + text1scale + ","
+ (text1bbox.x + text1bbox.width / 2) + "," + (text1bbox.y + text1bbox.height)Ð
      });Ð     this.text2.attr({Ð       text: label2,Ð       transform: ''Ð
      });Ð     text2bbox = this.text2.getBBox();Ð     text2scale =
Math.min(maxWidth / text2bbox.width, maxHeightBottom / text2bbox.height);Ð
      return this.text2.attr({Ð       transform: "S" + text2scale + "," +
text2scale + "," + (text2bbox.x + text2bbox.width / 2) + "," + text2bbox.yÐ
      });Ð   };Ð   Donut.prototype.drawEmptyDonutLabel = function(xPos, yPos,
color, fontSize, fontWeight) {Ð     var text;Ð     text =
this.raphael.text(xPos, yPos, '').attr('font-size', fontSize).attr('fill',
color);Ð     if (fontWeight != null) {Ð       text.attr('font-weight',
fontWeight);Ð     }Ð     return text;Ð   };Ð   Donut.prototype.resizeHandler
= function() {Ð     this.timeoutId = null;Ð
this.raphael.setSize(this.el.width(), this.el.height());Ð     return
this.redraw();Ð   };Ð   return Donut;Ð })(Morris.EventEmitter);Ð
Morris.DonutSegment = (function(_super) {Ð   __extends(DonutSegment, _super);Ð
    function DonutSegment(cx, cy, inner, outer, p0, p1, color,
backgroundColor, index, raphael) {Ð     this.cx = cx;Ð     this.cy = cy;Ð
this.inner = inner;Ð     this.outer = outer;Ð     this.color = color;Ð
this.backgroundColor = backgroundColor;Ð     this.index = index;Ð
this.raphael = raphael;Ð     this.deselect = __bind(this.deselect, this);Ð
      this.select = __bind(this.select, this);Ð     this.sin_p0 =
Math.sin(p0);Ð     this.cos_p0 = Math.cos(p0);Ð     this.sin_p1 =
Math.sin(p1);Ð     this.cos_p1 = Math.cos(p1);Ð     this.is_long = (p1 - p0)
> Math.PI ? 1 : 0;Ð     this.path = this.calcSegment(this.inner + 3,
this.inner + this.outer - 5);Ð     this.selectedPath =
this.calcSegment(this.inner + 3, this.inner + this.outer);Ð     this.hilight
= this.calcArc(this.inner);Ð   }Ð   DonutSegment.prototype.calcArcPoints =
function(r) {Ð     return [this.cx + r * this.sin_p0, this.cy + r *
this.cos_p0, this.cx + r * this.sin_p1, this.cy + r * this.cos_p1];Ð   };Ð
DonutSegment.prototype.calcSegment = function(r1, r2) {Ð     var ix0, ix1,
iy0, iy1, ox0, ox1, oy0, oy1, _ref, _ref1;Ð     _ref =
this.calcArcPoints(r1), ix0 = _ref[0], iy0 = _ref[1], ix1 = _ref[2], iy1 =
_ref[3];Ð     _ref1 = this.calcArcPoints(r2), ox0 = _ref1[0], oy0 = _ref1[1],
ox1 = _ref1[2], oy1 = _ref1[3];Ð     return ("M" + ix0 + "," + iy0) + ("A" +
r1 + "," + r1 + ",0," + this.is_long + ",0," + ix1 + "," + iy1) + ("L" + ox1
+ "," + oy1) + ("A" + r2 + "," + r2 + ",0," + this.is_long + ",1," + ox0 +
"," + oy0) + "Z";Ð   };Ð   DonutSegment.prototype.calcArc = function(r) {Ð
      var ix0, ix1, iy0, iy1, _ref;Ð     _ref = this.calcArcPoints(r), ix0 =
_ref[0], iy0 = _ref[1], ix1 = _ref[2], iy1 = _ref[3];Ð     return ("M" + ix0
+ "," + iy0) + ("A" + r + "," + r + ",0," + this.is_long + ",0," + ix1 + ","
+ iy1);Ð   };Ð   DonutSegment.prototype.render = function() {Ð     var _this
= this;Ð     this.arc = this.drawDonutArc(this.hilight, this.color);Ð
return this.seg = this.drawDonutSegment(this.path, this.color,
this.backgroundColor, function() {Ð       return _this.fire('hover',
_this.index);Ð     }, function() {Ð       return _this.fire('click',
_this.index);Ð     });Ð   };Ð   DonutSegment.prototype.drawDonutArc =
function(path, color) {Ð     return this.raphael.path(path).attr({Ð
stroke: color,Ð
```

```
                        'stroke-width': 2,Ð       opacity: 0Ð     });Ð   };Ð
DonutSegment.prototype.drawDonutSegment = function(path, fillColor,
strokeColor, hoverFunction, clickFunction) {Ð     return
this.raphael.path(path).attr({Ð       fill: fillColor,Ð       stroke:
strokeColor,Ð       'stroke-width': 3Ð
      }).hover(hoverFunction).click(clickFunction);Ð   };Ð
DonutSegment.prototype.select = function() {Ð     if (!this.selected) {Ð
        this.seg.animate({Ð         path: this.selectedPathÐ       }, 150,
'<>');Ð       this.arc.animate({Ð         opacity: 1Ð       }, 150, '<>');Ð
        return this.selected = true;Ð     }Ð   };Ð
DonutSegment.prototype.deselect = function() {Ð     if (this.selected) {Ð
        this.seg.animate({Ð         path: this.pathÐ       }, 150, '<>');Ð
        this.arc.animate({Ð         opacity: 0Ð       }, 150, '<>');Ð
return this.selected = false;Ð     }Ð   };Ð   return DonutSegment;Ð })
(Morris.EventEmitter);Ð }).call(this);Ð
```

public\assets\js\plugins\nestable\jquery.nestable.js

```
/*!Ð* Nestable jQuery Plugin - Copyright (c) 2012 David Bushell - http://
dbushell.com/Ð* Dual-licensed under the BSD or MIT licensesÐ*/Ð(function($,
window, document, undefined)ÐÐ   var hasTouch = 'ontouchstart' in document;Ð
    /**Ð    * Detect CSS pointer-events propertyÐ    * events are normally
disabled on the dragging element to avoid conflictsÐ    * https://github.com/
ausi/Feature-detection-technique-for-pointer-events/blob/master/modernizr-
pointerevents.jsÐ    */Ð   var hasPointerEvents = (function()Ð   {Ð       var
el    = document.createElement('div'),Ð           docEl =
document.documentElement;Ð       if (!('pointerEvents' in el.style)) {Ð
            return false;Ð       }Ð       el.style.pointerEvents = 'auto';Ð
        el.style.pointerEvents = 'x';Ð       docEl.appendChild(el);Ð
var supports = window.getComputedStyle && window.getComputedStyle(el,
'').pointerEvents === 'auto';Ð       docEl.removeChild(el);Ð       return !!
supports;Ð   })();Ð   var defaults = {Ð       listNodeName    : 'ol',Ð
itemNodeName    : 'li',Ð       rootClass       : 'dd',Ð
listClass       : 'dd-list',Ð       itemClass       : 'dd-item',Ð
dragClass       : 'dd-dragel',Ð       handleClass     : 'dd-handle',Ð
collapsedClass  : 'dd-collapsed',Ð       placeClass      : 'dd-placeholder',Ð
        noDragClass     : 'dd-nodrag',Ð       emptyClass      : 'dd-empty',Ð
        expandBtnHTML   : '<button data-action="expand" type="button">Expand</
button>',Ð       collapseBtnHTML : '<button data-action="collapse"
type="button">Collapse</button>',Ð       group           : 0,Ð
maxDepth        : 5,Ð       threshold       : 20Ð   };Ð   function
Plugin(element, options)Ð   {Ð       this.w  = $(document);Ð       this.el =
$(element);Ð       this.options = $.extend({}, defaults, options);Ð
this.init();Ð   }Ð   Plugin.prototype = {Ð       init: function()Ð       {Ð
            var list = this;Ð           list.reset();Ð
list.el.data('nestable-group', this.options.group);Ð           list.placeEl =
$('<div class="' + list.options.placeClass + '"/>');Ð
$.each(this.el.find(list.options.itemNodeName), function(k, el) {Ð
                list.setParent($(el));Ð           });Ð
list.el.on('click', 'button', function(e) {Ð               if (list.dragEl) {Ð
                    return;Ð               }Ð               var target =
$(e.currentTarget),Ð                   action = target.data('action'),Ð
                    item   = target.parent(list.options.itemNodeName);Ð
                if (action === 'collapse') {Ð
list.collapseItem(item);Ð               }Ð               if (action ===
'expand') {Ð                   list.expandItem(item);Ð               }Ð
            });Ð           var onStartEvent = function(e)Ð           {Ð
                var handle = $(e.target);Ð               if (!
handle.hasClass(list.options.handleClass)) {Ð                   if
(handle.closest('.' + list.options.noDragClass).length) {Ð
                        return;Ð                   }Ð
handle = handle.closest('.' + list.options.handleClass);Ð               }Ð
                if (!handle.length || list.dragEl) {Ð
return;Ð               }Ð               list.isTouch = /^touch/.test(e.type);Ð
                if (list.isTouch && e.touches.length !== 1) {Ð
                    return;Ð               }Ð
e.preventDefault();Ð               list.dragStart(e.touches ? e.touches[0] :
e);Ð           };Ð           var onMoveEvent = function(e)Ð           {Ð
                if (list.dragEl) {Ð                   e.preventDefault();Ð
                    list.dragMove(e.touches ? e.touches[0] : e);Ð
                }Ð           };Ð           var onEndEvent = function(e)Ð
            {Ð               if (list.dragEl) {Ð
e.preventDefault();Ð                   list.dragStop(e.touches ?
e.touches[0] : e);Ð               }Ð           };Ð           if (hasTouch) {Ð
                list.el[0].addEventListener('touchstart', onStartEvent,
false);Ð               window.addEventListener('touchmove', onMoveEvent,
false);Ð
```

```
                        window.addEventListener('touchend', onEndEvent, false);Ð
                    window.addEventListener('touchcancel', onEndEvent, false);Ð
            }Ð           list.el.on('mousedown', onStartEvent);Ð
list.w.on('mousemove', onMoveEvent);Ð           list.w.on('mouseup',
onEndEvent);Ð       },Ð       serialize: function()Ð       {Ð           var
data,Ð               depth = 0,Ð               list  = this;Ð           step
= function(level, depth)Ð           {Ð               var array = [ ],Ð
                    items = level.children(list.options.itemNodeName);Ð
                    items.each(function()Ð               {Ð                  var
li   = $(this),Ð                        item = $.extend({}, li.data()),Ð
                        sub  = li.children(list.options.listNodeName);Ð
                    if (sub.length) {Ð                        item.children =
step(sub, depth + 1);Ð                    }Ð
array.push(item);Ð               });Ð               return array;Ð
            };Ð           data =
step(list.el.find(list.options.listNodeName).first(), depth);Ð
return data;Ð       },Ð       serialise: function()Ð       {Ð
return this.serialize();Ð       },Ð       reset: function()Ð       {Ð
            this.mouse = {Ð               offsetX   : 0,Ð
offsetY   : 0,Ð               startX    : 0,Ð               startY    : 0,Ð
                lastX     : 0,Ð               lastY     : 0,Ð
nowX      : 0,Ð               nowY      : 0,Ð               distX     : 0,Ð
                distY     : 0,Ð               dirAx     : 0,Ð
dirX      : 0,Ð               dirY      : 0,Ð               lastDirX  : 0,Ð
                lastDirY  : 0,Ð               distAxX   : 0,Ð
distAxY   : 0Ð           };Ð           this.isTouch    = false;Ð
this.moving     = false;Ð           this.dragEl     = null;Ð
this.dragRootEl = null;Ð           this.dragDepth  = 0;Ð
this.hasNewRoot = false;Ð           this.pointEl    = null;Ð       },Ð
expandItem: function(li)Ð       {Ð
li.removeClass(this.options.collapsedClass);Ð           li.children('[data-
action="expand"]').hide();Ð           li.children('[data-
action="collapse"]').show();Ð
li.children(this.options.listNodeName).show();Ð       },Ð       collapseItem:
function(li)Ð       {Ð           var lists =
li.children(this.options.listNodeName);Ð           if (lists.length) {Ð
                li.addClass(this.options.collapsedClass);Ð
li.children('[data-action="collapse"]').hide();Ð
li.children('[data-action="expand"]').show();Ð
li.children(this.options.listNodeName).hide();Ð           }Ð       },Ð
expandAll: function()Ð       {Ð           var list = this;Ð
list.el.find(list.options.itemNodeName).each(function() {Ð
list.expandItem($(this));Ð           });Ð       },Ð       collapseAll:
function()Ð       {Ð           var list = this;Ð
list.el.find(list.options.itemNodeName).each(function() {Ð
list.collapseItem($(this));Ð           });Ð       },Ð       setParent:
function(li)Ð       {Ð           if
(li.children(this.options.listNodeName).length) {Ð
li.prepend($(this.options.expandBtnHTML));Ð
li.prepend($(this.options.collapseBtnHTML));Ð           }Ð
li.children('[data-action="expand"]').hide();Ð       },Ð       unsetParent:
function(li)Ð       {Ð           li.removeClass(this.options.collapsedClass);Ð
            li.children('[data-action]').remove();Ð
li.children(this.options.listNodeName).remove();Ð       },Ð       dragStart:
function(e)Ð       {Ð           var mouse    = this.mouse,Ð
target   = $(e.target),Ð               dragItem =
target.closest(this.options.itemNodeName);Ð
this.placeEl.css('height', dragItem.height());Ð           mouse.offsetX =
e.offsetX !== undefined ? e.offsetX : e.pageX - target.offset().left;Ð
            mouse.offsetY = e.offsetY !== undefined ? e.offsetY : e.pageY -
target.offset().top;Ð
```

```
                                mouse.startX = mouse.lastX = e.pageX;Ð
            mouse.startY = mouse.lastY = e.pageY;Ð           this.dragRootEl
= this.el;Ð           this.dragEl = $(document.createElement(this.options.list
NodeName)).addClass(this.options.listClass + ' ' + this.options.dragClass);Ð
            this.dragEl.css('width', dragItem.width());Ð
dragItem.after(this.placeEl);Ð
dragItem[0].parentNode.removeChild(dragItem[0]);Ð
dragItem.appendTo(this.dragEl);Ð
$(document.body).append(this.dragEl);Ð           this.dragEl.css({Ð
                'left' : e.pageX - mouse.offsetX,Ð               'top'  :
e.pageY - mouse.offsetYÐ           });Ð           // total depth of dragging
itemÐ           var i, depth,Ð               items =
this.dragEl.find(this.options.itemNodeName);Ð           for (i = 0; i <
items.length; i++) {Ð               depth =
$(items[i]).parents(this.options.listNodeName).length;Ð               if
(depth > this.dragDepth) {Ð                   this.dragDepth = depth;Ð
                }Ð           }Ð       },Ð       dragStop: function(e)Ð       {Ð
            var el = this.dragEl.children(this.options.itemNodeName).first();Ð
            el[0].parentNode.removeChild(el[0]);Ð
this.placeEl.replaceWith(el);Ð           this.dragEl.remove();Ð
this.el.trigger('change');Ð           if (this.hasNewRoot) {Ð
this.dragRootEl.trigger('change');Ð           }Ð           this.reset();Ð
        },Ð       dragMove: function(e)Ð       {Ð           var list, parent,
prev, next, depth,Ð               opt   = this.options,Ð               mouse
= this.mouse;Ð           this.dragEl.css({Ð               'left' : e.pageX -
mouse.offsetX,Ð               'top'  : e.pageY - mouse.offsetYÐ           });Ð
            // mouse position last eventsÐ           mouse.lastX = mouse.nowX;Ð
            mouse.lastY = mouse.nowY;Ð           // mouse position this eventsÐ
            mouse.nowX  = e.pageX;Ð           mouse.nowY  = e.pageY;Ð
            // distance mouse moved between eventsÐ           mouse.distX =
mouse.nowX - mouse.lastX;Ð           mouse.distY = mouse.nowY - mouse.lastY;Ð
            // direction mouse was movingÐ           mouse.lastDirX =
mouse.dirX;Ð           mouse.lastDirY = mouse.dirY;Ð           // direction
mouse is now moving (on both axis)Ð           mouse.dirX = mouse.distX ===
0 ? 0 : mouse.distX > 0 ? 1 : -1;Ð           mouse.dirY = mouse.distY === 0 ?
0 : mouse.distY > 0 ? 1 : -1;Ð           // axis mouse is now moving onÐ
            var newAx   = Math.abs(mouse.distX) > Math.abs(mouse.distY) ? 1 :
0;Ð           // do nothing on first moveÐ           if (!mouse.moving) {Ð
                mouse.dirAx  = newAx;Ð               mouse.moving = true;Ð
                return;Ð           }Ð           // calc distance moved on
this axis (and direction)Ð           if (mouse.dirAx !== newAx) {Ð
                mouse.distAxX = 0;Ð               mouse.distAxY = 0;Ð
            } else {Ð               mouse.distAxX += Math.abs(mouse.distX);Ð
                if (mouse.dirX !== 0 && mouse.dirX !== mouse.lastDirX) {Ð
                    mouse.distAxX = 0;Ð               }Ð
mouse.distAxY += Math.abs(mouse.distY);Ð               if (mouse.dirY !== 0
&& mouse.dirY !== mouse.lastDirY) {Ð               mouse.distAxY = 0;Ð
                }Ð           }Ð           mouse.dirAx = newAx;Ð           /**Ð
             * move horizontalÐ           */Ð           if (mouse.dirAx &&
mouse.distAxX >= opt.threshold) {Ð               // reset move distance on x-
axis for new phaseÐ               mouse.distAxX = 0;Ð               prev =
this.placeEl.prev(opt.itemNodeName);Ð               // increase horizontal
level if previous sibling exists and is not collapsedÐ               if
(mouse.distX > 0 && prev.length && !prev.hasClass(opt.collapsedClass)) {Ð
                    // cannot increase level when item above is collapsedÐ
                    list = prev.find(opt.listNodeName).last();Ð
                    // check if depth limit has reachedÐ
depth = this.placeEl.parents(opt.listNodeName).length;Ð               if
(depth + this.dragDepth <= opt.maxDepth) {Ð                   // create
new sub-level if one doesn't existÐ
```

```
                                                        if (!list.length) {Ð
                            list = $('<' + opt.listNodeName + '/
>').addClass(opt.listClass);Ð
list.append(this.placeEl);Ð                             prev.append(list);Ð
                            this.setParent(prev);Ð                      }
else {Ð                           // else append to next level upÐ
                            list = prev.children(opt.listNodeName).last();Ð
                            list.append(this.placeEl);Ð
                        }Ð                  }Ð              }Ð
                // decrease horizontal levelÐ              if (mouse.distX <
0) {Ð                   // we can't decrease a level if an item preceeds the
current oneÐ                    next = this.placeEl.next(opt.itemNodeName);Ð
                    if (!next.length) {Ð                      parent =
this.placeEl.parent();Ð
this.placeEl.closest(opt.itemNodeName).after(this.placeEl);Ð
                        if (!parent.children().length) {Ð
                            this.unsetParent(parent.parent());Ð
                        }Ð                  }Ð              }Ð           }Ð
            var isEmpty = false;Ð           // find list item under cursorÐ
            if (!hasPointerEvents) {Ð
this.dragEl[0].style.visibility = 'hidden';Ð           }Ð
this.pointEl = $(document.elementFromPoint(e.pageX -
document.body.scrollLeft, e.pageY - (window.pageYOffset ||
document.documentElement.scrollTop)));Ð           if (!hasPointerEvents) {Ð
                this.dragEl[0].style.visibility = 'visible';Ð           }Ð
            if (this.pointEl.hasClass(opt.handleClass)) {Ð
this.pointEl = this.pointEl.parent(opt.itemNodeName);Ð           }Ð
if (this.pointEl.hasClass(opt.emptyClass)) {Ð               isEmpty = true;Ð
            }Ð           else if (!this.pointEl.length || !
this.pointEl.hasClass(opt.itemClass)) {Ð               return;Ð           }Ð
            // find parent list of item under cursorÐ           var
pointElRoot = this.pointEl.closest('.' + opt.rootClass),Ð
isNewRoot   = this.dragRootEl.data('nestable-id') !==
pointElRoot.data('nestable-id');Ð           /**Ð            * move verticalÐ
             */Ð           if (!mouse.dirAx || isNewRoot || isEmpty) {Ð
                // check if groups match if dragging over new rootÐ
                if (isNewRoot && opt.group !== pointElRoot.data('nestable-
group')) {Ð                   return;Ð               }Ð               //
check depth limitÐ               depth = this.dragDepth - 1 +
this.pointEl.parents(opt.listNodeName).length;Ð               if (depth >
opt.maxDepth) {Ð                   return;Ð               }Ð
var before = e.pageY < (this.pointEl.offset().top + this.pointEl.height() /
2);Ð               parent = this.placeEl.parent();Ð               // if empty
create new list to replace empty placeholderÐ               if (isEmpty) {Ð
                    list =
$(document.createElement(opt.listNodeName)).addClass(opt.listClass);Ð
                    list.append(this.placeEl);Ð
this.pointEl.replaceWith(list);Ð               }Ð               else if
(before) {Ð                   this.pointEl.before(this.placeEl);Ð
                }Ð               else {Ð
this.pointEl.after(this.placeEl);Ð               }Ð               if (!
parent.children().length) {Ð
this.unsetParent(parent.parent());Ð               }Ð               if (!
this.dragRootEl.find(opt.itemNodeName).length) {Ð
this.dragRootEl.append('<div class="' + opt.emptyClass + '"/>');Ð
                }Ð               // parent root list has changedÐ
                if (isNewRoot) {Ð                   this.dragRootEl =
pointElRoot;Ð                   this.hasNewRoot = this.el[0] !==
this.dragRootEl[0];Ð               }Ð           }Ð       }Ð   };Ð
$.fn.nestable = function(params)Ð
```

```
                                    {Ð       var lists  = this,Ð
retval = this;Ð       lists.each(function()Ð       {Ð           var plugin =
$(this).data("nestable");Ð           if (!plugin) {Ð
$(this).data("nestable", new Plugin(this, params));Ð
$(this).data("nestable-id", new Date().getTime());Ð           } else {Ð
                if (typeof params === 'string' && typeof plugin[params] ===
'function') {Ð                    retval = plugin[params]();Ð               }Ð
            }Ð       });Ð       return retval || lists;Ð   };Ð
}(window.jQuery
|| window.Zepto, window, document);Ð
```

public\assets\js\plugins\nouslider\jquery.nouislider.min.js

```
/*Ð.classVal - WTFPL - refreshless.com/classval/ */Ðfunction(b){function
h(a,e){var d=!1;b.each(a?q:g,function(a){if(b(e).hasClass(a))return d=a,!
1});return d}var n=b.fn.val,g={},q={},u={};b.classVal=function(a,b,d,l)
{"string"===typeof a&&"boolean"===typeof
l&&(b&&(g[a]=b),d&&(q[a]=d),u[a]=l)};b.fn.val=function(){var
a=Array.prototype.slice.call(arguments,0),e,d;return a.length?
this.each(function(){(e=h(!0,this))?(d=u[e]?
b(this):this,d[q[e]].apply(this,a)):n.apply(b(this),a)}):(e=h(!1,this))?
(d=u[e]?this:this[0],d[g[e]].apply(d)):n.apply(this)}})(window.jQuery||Ð
window.Zepto);/*Ð.Link (part of noUiSlider) - WTFPL */Ðfunction(b){function
h(a,b,d){if((a[b]||a[d])&&a[b]===a[d])throw Error("(Link) '"+b+"' can't match
'"+d+"'.'");}function n(a){void 0===a&&(a={});if("object"!==typeof a)throw
Error("(Format) 'format' option must be an object.");var
e={};b(q).each(function(b,l){if(void 0===a[l])e[l]=u[b];else if(typeof
a[l]===typeof u[b]){if("decimals"===l&&(0>a[l]||7<a[l]))throw Error("(Format)
'format.decimals' option must be between 0 and 7.");e[l]=a[l]}else throw
Error("(Format) 'format."+l+"' must be a "+typeof u[b]+Ð
".");});h(e,"mark","thousand");h(e,"prefix","negative");h(e,"prefix","negativeBefore");thi
function g(a,e){"object"!==typeof a&&b.error("(Link) Initialize with an
object.");return new g.prototype.p(a.target||function(){},a.method,a.format||
{},e)}var q="decimals mark thousand prefix postfix encoder decoder negative
negativeBefore to from".split(" "),u=[2,".","","","",function(a){return
a},function(a){return a},"-","",function(a){return a},function(a){return
a}];n.prototype.a=function(a){return this.r[a]};Ð.prototype.L=function(a)
{function b(a){return a.split("").reverse().join("")}a=this.a("encoder")
(a);var d=this.a("decimals"),l="",g="",h="",n="";0===parseFloat(a.toFixed(d))&
&(a="0");0>a&&(l=this.a("negative"),g=this.a("negativeBefore"));a=Math.abs(a).
toFixed(d).toString();a=a.split(".");this.a("thousand")?(h=b(a[0]).match(/.
{1,3}/
g),h=b(h.join(b(this.a("thousand")))):h=a[0];this.a("mark")&&1<a.length&&(n=this.a("mark"
this.a("to")(g+this.a("prefix")+l+h+n+this.a("postfix"))};n.prototype.w=Ð
function(a){function b(a){return a.replace(/[\-\/\\\^$*+?.()|\[\]{}]/g,"\\
$&")}var d;if(null===a||void 0===a)return!1;a=this.a("from")
(a);a=a.toString();d=a.replace(RegExp("^"+b(this.a("negativeBefore"))),"");a!
==d?(a=d,d="-"):d="";a=a.replace(RegExp("^"+b(this.a("prefix"))),"");this.a("n
egative")&&(d="",a=a.replace(RegExp("^"+b(this.a("negative"))),"-"));a=a.repla
ce(RegExp(b(this.a("postfix"))+"$"),"").replace(RegExp(b(this.a("thousand")),"
g"),"").replace(this.a("mark"),".");a=this.a("decoder")(parseFloat(d+Ð
a));return isNaN(a)?!1:a};g.prototype.K=function(a,e)
{this.method=e||"html";this.j=b(a.replace("-tooltip-","")||"<div/>")
[0]};g.prototype.H=function(a)
{this.method="val";this.j=document.createElement("input");this.j.name=a;this.j.type="hidde
{function e(a,b){return[b?null:a,b?a:null]}var
d=this;this.method="val";this.target=a.on("change",function(a)
{d.B.val(e(b(a.target).val(),d.t),{link:d,set:!
0})})};g.prototype.p=function(a,e,d,g){this.g=d;this.update=!g;if("string"===Ð
typeof a&&0===a.indexOf("-tooltip-"))this.K(a,e);else if("string"===typeof
a&&0!==a.indexOf("-"))this.H(a);else if("function"===typeof a)this.target=!
1,this.method=a;else{if(a instanceof b||b.zepto&&b.zepto.isZ(a)){if(!e)
{if(a.is("input, select, textarea")){this.G(a);return}e="html"}
if("function"===typeof e||"string"===typeof e&&a[e])
{this.method=e;this.target=a;return}}throw new RangeError("(Link) Invalid
Link.");}};g.prototype.write=function(a,b,d,g){if(!this.update||!1!
==g)if(this.u=a,this.F=a=Ðthis.format(a),"function"===typeof
this.method)this.method.call(this.target[0]||d[0],a,b,d);else
this.target[this.method](a,b,d)};g.prototype.q=function(a){this.g=new
n(b.extend({},a,this.g instanceof n?
this.g.r:this.g))};g.prototype.J=function(a)
{this.B=a};g.prototype.I=function(a){this.t=a};g.prototype.format=function(a)
```

```
{return this.g.L(a)};g.prototype.A=function(a){return
this.g.w(a)};g.prototype.p.prototype=g.prototype;b.Link=g})(window.jQuery||
window.Zepto);/*Ð.fn.noUiSlider - WTFPL - refreshless.com/nouislider/ */Ð
(function(b){function h(a){return"number"===typeof a&&!isNaN(a)&&isFinite(a)}
function n(a){return b.isArray(a)?a:[a]}function g(a,c)
{a.addClass(c);setTimeout(function(){a.removeClass(c)},300)}function q(a,c)
{return 100*c/(a[1]-a[0])}function u(a,c){if(c>=a.d.slice(-1)[0])return
100;for(var b=1,f,d,e;c>=a.d[b];)b+
+;f=a.d[b-1];d=a.d[b];e=a.c[b-1];f=[f,d];return e+q(f,0>f[0]?
c+Math.abs(f[0]):c-f[0])/(100/(a.c[b]-e))}function a(a,c){if(100<=c)return
a.d.slice(-1)[0];for(var b=1,f,d,e;c>=a.c[b];)b++;f=Ð
a.d[b-1];d=a.d[b];e=a.c[b-1];f=[f,d];return 100/(a.c[b]-e)*(c-e)*(f[1]-
f[0])/100+f[0]}function e(a,c){for(var b=1,f;c>=a.c[b];)b++;if(a.m)return
f=a.c[b-1],b=a.c[b],c-f>(b-f)/2?b:f;a.h[b-1]?
(f=a.h[b-1],b=a.c[b-1]+Math.round((c-a.c[b-1])/f)*f):b=c;return b}function
d(a,c){if(!h(c))throw Error("noUiSlider: 'step' is not numeric.");a.h[0]=c}
function l(a,c){if("object"!==typeof c||b.isArray(c))throw Error("noUiSlider:
'range' is not an object.");b.each(c,function(c,f){var d;"number"===typeof
f&&(f=[f]);Ðf(!b.isArray(f))throw Error("noUiSlider: 'range' contains invalid
value.");d="min"===c?0:"max"===c?100:parseFloat(c);if(!h(d)||!h(f[0]))throw
Error("noUiSlider: 'range' value isn't
numeric.");a.c.push(d);a.d.push(f[0]);d?a.h.push(isNaN(f[1])?!
1:f[1]):isNaN(f[1])||(a.h[0]=f[1])});b.each(a.h,function(c,b){if(!b)return!
0;a.h[c]=q([a.d[c],a.d[c+1]],b)/(100/(a.c[c+1]-a.c[c]))})}function z(a,c)
{"number"===typeof c&&(c=[c]);if(!b.isArray(c)||!c.length||2<c.length)throw
Error("noUiSlider: 'start' option is incorrect.");Ða.b=c.length;a.start=c}
function A(a,c){a.m=c;if("boolean"!==typeof c)throw Error("noUiSlider: 'snap'
option must be a boolean.");}function B(a,c)
{if("lower"===c&&1===a.b)a.i=1;else if("upper"===c&&1===a.b)a.i=2;else if(!
0===c&&2===a.b)a.i=3;else if(!1===c)a.i=0;else throw Error("noUiSlider:
'connect' option doesn't match handle count.");}function y(a,c){switch(c)
{case "horizontal":a.k=0;break;case "vertical":a.k=1;break;default:throw
Error("noUiSlider: 'orientation' option is invalid.");}}function I(a,Ð)
{if(2<a.c.length)throw Error("noUiSlider: 'margin' option is only supported
on linear sliders.");a.margin=q(a.d,c);if(!h(c))throw Error("noUiSlider:
'margin' option must be numeric.");}function J(a,c){switch(c){case
"ltr":a.dir=0;break;case "rtl":a.dir=1;a.i=[0,2,1,3][a.i];break;default:throw
Error("noUiSlider: 'direction' option was not recognized.");}}function K(a,c)
{if("string"!==typeof c)throw Error("noUiSlider: 'behaviour' must be a string
containing options.");var b=0<=c.indexOf("snap");a.n={Ðs:0<=c.indexOf("tap")||b
,extend:0<=c.indexOf("extend"),v:0<=c.indexOf("drag"),fixed:0<=c.indexOf("fixe
d"),m:b}}function L(a,c,d)
{a.o=[c.lower,c.upper];a.g=c.format;b.each(a.o,function(a,e){if(!
b.isArray(e))throw Error("noUiSlider: 'serialization."+(a?"upper":"lower")+"'
must be an array.");b.each(e,function(){if(!(this instanceof b.Link))throw
Error("noUiSlider: 'serialization."+(a?"upper":"lower")+"' can only contain
Link
instances.");this.I(a);this.J(d);this.q(c.format)})});a.dir&&1<a.b&&a.o.reverse()}Ð
function M(a,c){var e={c:[],d:[],h:[!1],margin:0},f;f={step:{e:!1,f:d},range:
{e:!0,f:l},start:{e:!0,f:z},snap:{e:!1,f:A},connect:{e:!0,f:B},orientation:
{e:!1,f:y},margin:{e:!1,f:I},direction:{e:!0,f:J},behaviour:{e:!
0,f:K},serialization:{e:!0,f:L}};a=b.extend({connect:!
1,direction:"ltr",behaviour:"tap",orientation:"horizontal"},a);a.serialization=b.extend({l
[],upper:[],format:{}},a.serialization);b.each(f,function(b,d){if(void
0===a[b]){if(d.e)throw Error("noUiSlider: '"+b+"' is required.");Ðeturn!0}
d.f(e,a[b],c)});e.style=e.k?"top":"left";return e}function N(a,c){var
d=b("<div><div/></div>").addClass(k[2]),f=["-lower","-
upper"];a.dir&&f.reverse();d.children().addClass(k[3]+" "+k[3]+f[c]);return d}
function O(a,c){c.j&&(c=new
b.Link({target:b(c.j).clone().appendTo(a),method:c.method,format:c.g},!
0));return c}function P(a,c){var d,f=[];for(d=0;d<a.b;d++){var
```

```
e=f,g=d,k=a.o[d],h=c[d].children(),l=a.g,n=void 0,q=[],n=new b.Link({},!
0);n.q(l);q.push(n);for(n=0;n<k.length;n++)q.push(O(h,k[n]));Ð[g]=q}return f}
function Q(a,c,b){switch(a){case
1:c.addClass(k[7]);b[0].addClass(k[6]);break;case 3:b[1].addClass(k[6]);case
2:b[0].addClass(k[7]);case 0:c.addClass(k[6])}}function R(a,b){var
d,f=[];for(d=0;d<a.b;d++)f.push(N(a,d).appendTo(b));return f}function S(a,c)
{c.addClass([k[0],k[8+a.dir],k[4+a.k]].join(" "));return b("<div/
>").appendTo(c).addClass(k[1])}function T(d,c,h){function f(){return
r[["width","height"][c.k]]()}function l(a){var
b,c=[s.val()];for(b=0;b<a.length;b++)s.trigger(a[b],Ð)}function q(d,p,f){var
g=d[0]!==m[0][0]?1:0,H=v[0]+c.margin,l=v[1]-c.margin;f&&1<m.length&&(p=g?
Math.max(p,H):Math.min(p,l));100>p&&(p=e(c,p));p=Math.max(Math.min(parseFloat(p.toFixed(7)
1===m.length?!1:p===H||p===l?0:!1;d.css(c.style,p+"%");d.is(":first-
child")&&d.toggleClass(k[17],50<p);v[g]=p;c.dir&&(p=100-
p);b(w[g]).each(function(){this.write(a(c,p),d.children(),s)});return!0}
function G(a,b,c){c||g(s,k[14]);q(a,b,!1);l(["slide","set","change"])}
function t(a,b,d,f){a=Ð.replace(/\s/g,".nui ")+".nui";b.on(a,function(a){var
b=s.attr("disabled");if(s.hasClass(k[14])||void 0!==b&&null!==b)return!
1;a.preventDefault();var b=0===a.type.indexOf("touch"),p=0===a.type.indexOf("m
ouse"),e=0===a.type.indexOf("pointer"),D,g,l=a;0===a.type.indexOf("MSPointer")
&&(e=!0);a.originalEvent&&(a=a.originalEvent);b&&(D=a.changedTouches[0].pageX,
g=a.changedTouches[0].pageY);if(p||e)e||void 0!==window.pageXOffset||
(window.pageXOffset=document.documentElement.scrollLeft,window.pageYOffset=Ð
document.documentElement.scrollTop),D=a.clientX+window.pageXOffset,g=a.clientY+window.page
function y(a,b){var c=b.b||m,d,e=!1,e=100*(a.l-b.start)/f(),g=c[0][0]!==m[0]
[0]?1:0;var k=b.D;d=e+k[0];e+=k[1];1<c.length?
(0>d&&(e+=Math.abs(d)),100<e&&(d-
=e-100),d=[Math.max(Math.min(d,100),0),Math.max(Math.min(e,100),0)]):d=[d,e];e=q(c[0],d[g]
0:1],!1)||e);e&&l(["slide"])}function z(a){b("."+k[15]).removeClass(k[15]);Ð
a.cursor&&b("body").css("cursor","").off(".nui");E.off(".nui");s.removeClass(k[12]);l(["se
function C(a,c)
{1===c.b.length&&c.b[0].children().addClass(k[15]);a.stopPropagation();t(x.move,E,y,
{start:a.l,b:c.b,D:[v[0],v[m.length-1]]});t(x.end,E,z,null);a.cursor&&(b("body
").css("cursor",b(a.target).css("cursor")),1<m.length&&s.addClass(k[12]),b("bo
dy").on("selectstart.nui",!1))}function A(a){var
d=a.l,e=0;a.stopPropagation();b.each(m,function(){e+=this.offset()
[c.style]});e=d<e/2||1===m.length?Ð:1;d-=r.offset()[c.style];d=100*d/
f();G(m[e],d,c.n.m);c.n.m&&C(a,{b:[m[e]]})}function B(a){var
b=(a=a.l<r.offset()[c.style])?0:100;a=a?0:m.length-1;G(m[a],b,!1)}var
s=b(d),v=[-1,-1],r,w,m;if(s.hasClass(k[0]))throw Error("Slider was already
initialized.");r=S(c,s);m=R(c,r);w=P(c,m);Q(c.i,s,m);(function(a){var b;if(!
a.fixed)for(b=0;b<m.length;b++)t(x.start,m[b].children(),C,{b:
[m[b]]});a.s&&t(x.start,r,A,
{b:m});a.extend&&(s.addClass(k[16]),a.s&&t(x.start,s,B,
{b:m}));a.v&&(b=r.find("."+k[7]).addClass(k[10]),Ð
a.fixed&&(b=b.add(r.children().not(b).children())),t(x.start,b,C,{b:m}))})
(c.n);d.vSet=function(){var
a=Array.prototype.slice.call(arguments,0),d,e,f,h,r,F,t=n(a[0]);"object"===typeof
a[1]?(d=a[1].set,e=a[1].link,f=a[1].update,h=a[1].animate):!0===a[1]&&(d=!
0);c.dir&&1<c.b&&t.reverse();h&&g(s,k[14]);a=1<m.length?
3:1;1===t.length&&(a=1);for(r=0;r<a;r++)h=e||w[r%2][0],h=h.A(t[r%2]),!1!
==h&&(h=u(c,h),c.dir&&(h=100-h),!0!==q(m[r%2],h,!
0)&&b(w[r%2]).each(function(a){if(!a)return F=this.u,!0;this.write(F,Ð
m[r%2].children(),s,f)}));!0===d&&l(["set"]);return this};d.vGet=function()
{var a,b=[];for(a=0;a<c.b;a++)b[a]=w[a][0].F;return 1===b.length?b[0]:c.dir?
b.reverse():b};d.destroy=function(){b.each(w,function(){b.each(this,function()
{this.target&&this.target.off(".nui")})});b(this).off(".nui").removeClass(k.join("
")).empty();return h};s.val(c.start)}function U(a){if(!this.length)throw
Error("noUiSlider: Can't initialize slider on empty selection.");var
b=M(a,this);return this.each(function(){T(this,Ð
```

```
                                                    b,a)})}function V(a){return
this.each(function(){var
c=b(this).val(),d=this.destroy(),e=b.extend({},d,a);b(this).noUiSlider(e);d.start===e.star
var E=b(document),x=window.navigator.pointerEnabled?
{start:"pointerdown",move:"pointermove",end:"pointerup"}:window.navigator.msPointerEnabled
{start:"MSPointerDown",move:"MSPointerMove",end:"MSPointerUp"}:
{start:"mousedown touchstart",move:"mousemove touchmove",end:"mouseup
touchend"},k="noUi-target noUi-base noUi-origin noUi-handle noUi-horizontal
noUi-vertical noUi-background noUi-connect noUi-ltr noUi-rtl noUi-dragable
noUi-state-drag  noUi-state-tap noUi-active noUi-extended noUi-
stacking".split(" ");Ð.noUiSlider={Link:b.Link};b.fn.noUiSlider=function(a,b)
{return(b?V:U).call(this,a)};b.classVal(k[0],"vGet","vSet",!1)})
(window.jQuery||window.Zepto);Ð
```

public\assets\js\plugins\peity\jquery.peity.min.js

```
// Peity jQuery plugin version 2.0.3Ð// (c) 2014 Ben PicklesÐ// http://
benpickles.github.io/peityÐ// Released under MIT license.Ðfunction(e,q,h)
{var o=function(a,b){var c=q.createElementNS("http://www.w3.org/2000/
svg",a);e.each(b,function(a,b){c.setAttribute(a,b)});return
c},t="createElementNS"in q&&o("svg",{}).createSVGRect,r=1/
(window.devicePixelRatio||1),j=e.fn.peity=function(a,b)
{t&&this.each(function(){var
c=e(this),d=c.data("peity");if(d)a&&(d.type=a),e.extend(d.opts,b);else{var
f=j.defaults[a],g={};e.each(c.data(),function(a,b){a in f&&(g[a]=b)});var
h=e.extend({},f,g,b),d=new s(c,a,h);c.change(function()
{d.draw()}).data("peity",Ð   d)}d.draw()});return this},s=function(a,b,c)
{this.$el=a;this.type=b;this.opts=c},m=s.prototype;m.draw=function()
{j.graphers[this.type].call(this,this.opts)};m.fill=function(){var
a=this.opts.fill,b=a;e.isFunction(b)||(b=function(b,d){return
a[d%a.length]});return b};m.prepare=function(a,b){var c;this.svg?
c=e(this.svg).empty():(this.svg=o("svg",{"class":"peity"}),this.$el.hide().aft
er(this.svg),c=e(this.svg).data("peity",this));this.svg.setAttribute("height",
b);this.svg.setAttribute("width",a);return c};Ð   m.values=function(){return
e.map(this.$el.text().split(this.opts.delimiter),function(a){return
parseFloat(a)})};j.defaults={};j.graphers={};j.register=function(a,b,c)
{this.defaults[a]=b;this.graphers[a]=c};j.register("pie",
{delimiter:null,diameter:16,fill:["#ff9900","#fff4dd","#ffc66e"]},function(a)
{if(!a.delimiter){var b=this.$el.text().match(/[^0-9\.]/);a.delimiter=b?
b[0]:","}b=this.values();if("/"==a.delimiter)var c=b[0],b=[c,h.max(0,b[1]-
c)];for(var d=0,c=b.length,f=0;d<c;d++)f+=b[d];for(var a=Ð
this.prepare(a.width||a.diameter,a.height||
a.diameter),d=a.width(),g=a.height(),a=d/2,g=g/2,p=h.min(a,g),e=h.PI,j=this.fill(),i=-
e/2,d=0;d<c;d++){var n=b[d],l=n/f,k;if(0!=l){if(1==l)k=o("circle",
{cx:a,cy:g,r:p});else{k=2*l*e;var
l=i+k,m=p*h.cos(i)+a,i=p*h.sin(i)+g,q=p*h.cos(l)+a,r=p*h.sin(l)+g;k=o("path",
{d:["M",a,g,"L",m,i,"A",p,p,0,k>e?1:0,1,q,r,"Z"].join(" ")});i=l}
k.setAttribute("fill",j.call(this,n,d,b));this.svg.appendChild(k)}}});j.register("line",
{delimiter:",",fill:"#c6d9fd",height:16,max:null,Ð
min:0,stroke:"#4d89f9",strokeWidth:1,width:32},function(a){var
b=this.values();1==b.length&&b.push(b[0]);for(var c=h.max.apply(h,b.concat([a.
max])),d=h.min.apply(h,b.concat([a.min])),f=this.prepare(a.width,a.height),g=f
.width(),f=f.height()-a.strokeWidth,e=g/(b.length-1),c=c-d,j=0==c?f:f/
c,m=f+d*j,c=[0,m],i=0;i<b.length;i++)c.push(i*e,f-j*(b[i]-
d)+a.strokeWidth/2);c.push(g,m);b=o("polygon",{fill:a.fill,points:c.join("
")});this.svg.appendChild(b);a.strokeWidth&&(a=o("polyline",
{fill:"transparent",Ð       points:c.slice(2,c.length-2).join("
"),stroke:a.stroke,"stroke-width":a.strokeWidth,"stroke-
linecap":"square"}),this.svg.appendChild(a))});j.register("bar",
{delimiter:",",fill:
["#4D89F9"],gap:1,height:16,max:null,min:0,width:32},function(a){for(var b=thi
s.values(),c=h.max.apply(h,b.concat([a.max])),d=h.min.apply(h,b.concat([a.min]
)),f=this.prepare(a.width,a.height),g=f.width(),f=f.height(),e=c-d,j=0==e?0:f/
e,a=a.gap,g=(g+a)/b.length,m=this.fill(),i=0;i<b.length;i++){var n=b[i],l=f-
j*(n-d),k=j*n;if(0==Ð       k){if(k=r,0>=d&&0<c||0==e)l-=r}else 0>k&&(l+=k,k=-
k);n=o("rect",{fill:m.call(this,n,i,b),x:i*g,y:l,width:g-
a,height:k});this.svg.appendChild(n)}})})(jQuery,document,Math);Ð
```

public\assets\js\plugins\preetyTextDiff\jquery.pretty-text-diff.min.js

```
// Generated by CoffeeScript 1.7.1Ð*Ð@preserve jQuery.PrettyTextDiff 1.0.4Ð
See https://github.com/arnab/jQuery.PrettyTextDiff/Ð*/Ðfunction() {Ð   var $;Ð
    $ = jQuery;Ð   $.fn.extend({Ð       prettyTextDiff: function(options) {Ð
            var dmp, settings;Ð           settings = {Ð
originalContainer: ".original",Ð               changedContainer: ".changed",Ð
                diffContainer: ".diff",Ð               cleanup: true,Ð
                debug: falseÐ           };Ð           settings =
$.extend(settings, options);Ð           $.fn.prettyTextDiff.debug("Options:
", settings, settings);Ð           dmp = new diff_match_patch();Ð
return this.each(function() {Ð               var changed, diff_as_html,
diffs, original;Ð               if (settings.originalContent &&
settings.changedContent) {Ð                   original = $('<div />
>').html(settings.originalContent).text();Ð                   changed =
$('<div />').html(settings.changedContent).text();Ð               } else {Ð
                    original = $(settings.originalContainer, this).text();Ð
                    changed = $(settings.changedContainer, this).text();Ð
                }Ð               $.fn.prettyTextDiff.debug("Original text
found: ", original, settings);Ð
$.fn.prettyTextDiff.debug("Changed  text found: ", changed, settings);Ð
                diffs = dmp.diff_main(original, changed);Ð               if
(settings.cleanup) {Ð                   dmp.diff_cleanupSemantic(diffs);Ð
                }Ð               $.fn.prettyTextDiff.debug("Diffs: ", diffs,
settings);Ð               diff_as_html = $.map(diffs, function(diff) {Ð
                    return $.fn.prettyTextDiff.createHTML(diff);Ð
                });Ð               $(settings.diffContainer,
this).html(diff_as_html.join(''));Ð               return this;Ð           });Ð
        }Ð   });Ð   $.fn.prettyTextDiff.debug = function(message, object,
settings) {Ð       if (settings.debug) {Ð           return
console.log(message, object);Ð       }Ð   };Ð
$.fn.prettyTextDiff.createHTML = function(diff) {Ð       var data, html,
operation, pattern_amp, pattern_gt, pattern_lt, pattern_para, text;Ð
html = [];Ð       pattern_amp = /&/g;Ð       pattern_lt = /</g;Ð
pattern_gt = />/g;Ð       pattern_para = /\n/g;Ð       operation = diff[0],
data = diff[1];Ð       text = data.replace(pattern_amp,
'&amp;').replace(pattern_lt, '&lt;').replace(pattern_gt,
'&gt;').replace(pattern_para, '<br>');Ð       switch (operation) {Ð
case DIFF_INSERT:Ð               return '<ins>' + text + '</ins>';Ð
case DIFF_DELETE:Ð               return '<del>' + text + '</del>';Ð
case DIFF_EQUAL:Ð               return '<span>' + text + '</span>';Ð       }Ð
    };Ð}).call(this);Ð
```

public\assets\js\plugins\slimscroll\jquery.slimscroll.js

```
/*! Copyright (c) 2011 Piotr Rochala (http://rocha.la)Ð* Dual licensed under
the MIT (http://www.opensource.org/licenses/mit-license.php)Ð* and GPL
(http://www.opensource.org/licenses/gpl-license.php) licenses.Ð*Ð* Version:
1.3.6Ð*Ð*/Ðfunction($) {Ð $.fn.extend({Ð   slimScroll: function(options) {Ð
      var defaults = {Ð       // width in pixels of the visible scroll areaÐ
        width : 'auto',Ð       // height in pixels of the visible scroll areaÐ
        height : '250px',Ð       // width in pixels of the scrollbar and railÐ
        size : '7px',Ð       // scrollbar color, accepts any hex/color valueÐ
        color: '#000',Ð       // scrollbar position - left/rightÐ
position : 'right',Ð       // distance in pixels between the side edge and
the scrollbarÐ       distance : '1px',Ð       // default scroll position on
load - top / bottom / $('selector')Ð       start : 'top',Ð       // sets
scrollbar opacityÐ       opacity : .4,Ð       // enables always-on mode for
the scrollbarÐ       alwaysVisible : false,Ð       // check if we should hide
the scrollbar when user is hovering overÐ       disableFadeOut : false,Ð
        // sets visibility of the railÐ       railVisible : false,Ð       //
sets rail colorÐ       railColor : '#333',Ð       // sets rail opacityÐ
railOpacity : .2,Ð       // whether  we should use jQuery UI Draggable to
enable bar draggingÐ       railDraggable : true,Ð       // defautlt CSS class
of the slimscroll railÐ       railClass : 'slimScrollRail',Ð       //
defautlt CSS class of the slimscroll barÐ       barClass : 'slimScrollBar',Ð
        // defautlt CSS class of the slimscroll wrapperÐ       wrapperClass :
'slimScrollDiv',Ð       // check if mousewheel should scroll the window if we
reach top/bottomÐ       allowPageScroll : false,Ð       // scroll amount
applied to each mouse wheel stepÐ       wheelStep : 20,Ð       // scroll
amount applied when user is using gesturesÐ       touchScrollStep : 200,Ð
        // sets border radiusÐ       borderRadius: '7px',Ð       // sets
border radius of the railÐ       railBorderRadius : '7px'Ð     };Ð     var o
= $.extend(defaults, options);Ð     // do it for every element that matches
selectorÐ     this.each(function(){Ð       var isOverPanel, isOverBar,
isDragg, queueHide, touchDif,Ð           barHeight, percentScroll, lastScroll,Ð
            divS = '<div></div>',Ð           minBarHeight = 30,Ð
releaseScroll = false;Ð       // used in event handlers and for better
minificationÐ       var me = $(this);Ð       // ensure we are not binding it
againÐ       if (me.parent().hasClass(o.wrapperClass))Ð       {Ð         //
start from last bar positionÐ         var offset = me.scrollTop();Ð
          // find bar and railÐ         bar = me.closest('.' + o.barClass);Ð
          rail = me.closest('.' + o.railClass);Ð         getBarHeight();Ð
          // check if we should scroll existing instanceÐ         if
($.isPlainObject(options))Ð         {Ð           // Pass height: auto to an
existing slimscroll object to force a resize after contents have changedÐ
            if ( 'height' in options && options.height == 'auto' ) {Ð
              me.parent().css('height', 'auto');Ð
me.css('height', 'auto');Ð             var height =
me.parent().parent().height();Ð             me.parent().css('height', height);Ð
              me.css('height', height);Ð           }Ð           if
('scrollTo' in options)Ð           {Ð             // jump to a static pointÐ
              offset = parseInt(o.scrollTo);Ð           }Ð           else if
('scrollBy' in options)Ð           {Ð             // jump by value pixelsÐ
              offset += parseInt(o.scrollBy);Ð           }Ð           else if
('destroy' in options)Ð           {Ð             // remove slimscroll elementsÐ
              bar.remove();Ð             rail.remove();Ð
me.unwrap();Ð             return;Ð           }Ð           // scroll content
by the given offsetÐ           scrollContent(offset, false, true);Ð         }Ð
          return;Ð       }Ð       else if ($.isPlainObject(options))Ð       {Ð
          if ('destroy' in options)Ð         {Ð           return;Ð         }Ð
        }Ð       // optionally set height to the parent's heightÐ
o.height = (o.height == 'auto') ? me.parent().height() : o.height;Ð       //
wrap contentÐ
```

```
                    var wrapper = $(divS)Ð           .addClass(o.wrapperClass)Ð
            .css({Ð             position: 'relative',Ð             overflow:
'hidden',Ð             width: o.width,Ð             height: o.heightÐ
            });Ð       // update style for the divÐ       me.css({Ð
overflow: 'hidden',Ð         width: o.width,Ð         height: o.heightÐ
        });Ð       // create scrollbar railÐ       var rail = $(divS)Ð
            .addClass(o.railClass)Ð           .css({Ð             width:
o.size,Ð             height: '100%',Ð             position: 'absolute',Ð
              top: 0,Ð             display: (o.alwaysVisible &&
o.railVisible) ? 'block' : 'none',Ð             'border-radius':
o.railBorderRadius,Ð             background: o.railColor,Ð
opacity: o.railOpacity,Ð             zIndex: 90Ð           });Ð       //
create scrollbarÐ       var bar = $(divS)Ð           .addClass(o.barClass)Ð
            .css({Ð             background: o.color,Ð             width:
o.size,Ð             position: 'absolute',Ð             top: 0,Ð
opacity: o.opacity,Ð             display: o.alwaysVisible ? 'block' : 'none',Ð
              'border-radius' : o.borderRadius,Ð             BorderRadius:
o.borderRadius,Ð             MozBorderRadius: o.borderRadius,Ð
WebkitBorderRadius: o.borderRadius,Ð             zIndex: 99Ð           });Ð
        // set positionÐ       var posCss = (o.position == 'right') ?
{ right: o.distance } : { left: o.distance };Ð       rail.css(posCss);Ð
bar.css(posCss);Ð       // wrap itÐ       me.wrap(wrapper);Ð       // append
to parent divÐ       me.parent().append(bar);Ð       me.parent().append(rail);Ð
        // make it draggable and no longer dependent on the jqueryUIÐ
if (o.railDraggable){Ð         bar.bind("mousedown", function(e) {Ð
var $doc = $(document);Ð           isDragg = true;Ð           t =
parseFloat(bar.css('top'));Ð           pageY = e.pageY;Ð
$doc.bind("mousemove.slimscroll", function(e){Ð             currTop = t +
e.pageY - pageY;Ð             bar.css('top', currTop);Ð
scrollContent(0, bar.position().top, false);// scroll contentÐ           });Ð
            $doc.bind("mouseup.slimscroll", function(e) {Ð
isDragg = false;hideBar();Ð             $doc.unbind('.slimscroll');Ð
            });Ð           return false;Ð
          }).bind("selectstart.slimscroll", function(e){Ð
e.stopPropagation();Ð           e.preventDefault();Ð           return false;Ð
          });Ð       }Ð       // on rail overÐ       rail.hover(function(){Ð
          showBar();Ð       }, function(){Ð         hideBar();Ð       });Ð
        // on bar overÐ       bar.hover(function(){Ð         isOverBar = true;Ð
        }, function(){Ð         isOverBar = false;Ð       });Ð       // show
on parent mouseoverÐ       me.hover(function(){Ð         isOverPanel = true;Ð
          showBar();Ð         hideBar();Ð       }, function(){Ð
isOverPanel = false;Ð         hideBar();Ð       });Ð       // support for
mobileÐ       me.bind('touchstart', function(e,b){Ð         if
(e.originalEvent.touches.length)Ð         {Ð           // record where touch
startedÐ           touchDif = e.originalEvent.touches[0].pageY;Ð         }Ð
        });Ð       me.bind('touchmove', function(e){Ð         // prevent
scrolling the page if necessaryÐ         if(!releaseScroll)Ð         {Ð
            e.originalEvent.preventDefault();Ð         }Ð         if
(e.originalEvent.touches.length)Ð         {Ð           // see how far user
swipedÐ           var diff = (touchDif - e.originalEvent.touches[0].pageY) /
o.touchScrollStep;Ð           // scroll contentÐ
scrollContent(diff, true);Ð           touchDif =
e.originalEvent.touches[0].pageY;Ð         }Ð       });Ð       // set up
initial heightÐ       getBarHeight();Ð       // check start positionÐ
if (o.start === 'bottom')Ð       {Ð         // scroll content to bottomÐ
          bar.css({ top: me.outerHeight() - bar.outerHeight() });Ð
scrollContent(0, true);Ð       }Ð       else if (o.start !== 'top')Ð       {Ð
          // assume jQuery selectorÐ
scrollContent($(o.start).position().top, null, true);Ð         // make sure
bar stays hiddenÐ
```

```
                        if (!o.alwaysVisible) { bar.hide(); }Ð       }Ð
        // attach scroll eventsÐ       attachWheel(this);Ð       function
_onWheel(e)Ð       {Ð         // use mouse wheel only when mouse is overÐ
          if (!isOverPanel) { return; }Ð         var e = e || window.event;Ð
          var delta = 0;Ð         if (e.wheelDelta) { delta = -
e.wheelDelta/120; }Ð         if (e.detail) { delta = e.detail / 3; }Ð
var target = e.target || e.srcTarget || e.srcElement;Ð         if
($(target).closest('.' + o.wrapperClass).is(me.parent())) {Ð           //
scroll contentÐ           scrollContent(delta, true);Ð         }Ð         //
stop window scrollÐ         if (e.preventDefault && !releaseScroll)
{ e.preventDefault(); }Ð         if (!releaseScroll) { e.returnValue =
false; }Ð       }Ð       function scrollContent(y, isWheel, isJump)Ð       {Ð
          releaseScroll = false;Ð         var delta = y;Ð         var maxTop
= me.outerHeight() - bar.outerHeight();Ð         if (isWheel)Ð         {Ð
            // move bar with mouse wheelÐ           delta =
parseInt(bar.css('top')) + y * parseInt(o.wheelStep) / 100 *
bar.outerHeight();Ð           // move bar, make sure it doesn't go outÐ
            delta = Math.min(Math.max(delta, 0), maxTop);Ð           // if
scrolling down, make sure a fractional change to theÐ           // scroll
position isn't rounded away when the scrollbar's CSS is setÐ           //
this flooring of delta would happened automatically whenÐ           //
bar.css is set below, but we floor here for clarityÐ           delta = (y >
0) ? Math.ceil(delta) : Math.floor(delta);Ð           // scroll the scrollbarÐ
            bar.css({ top: delta + 'px' });Ð         }Ð         // calculate
actual scroll amountÐ         percentScroll = parseInt(bar.css('top')) /
(me.outerHeight() - bar.outerHeight());Ð         delta = percentScroll *
(me[0].scrollHeight - me.outerHeight());Ð         if (isJump)Ð         {Ð
            delta = y;Ð           var offsetTop = delta / me[0].scrollHeight
* me.outerHeight();Ð           offsetTop = Math.min(Math.max(offsetTop, 0),
maxTop);Ð           bar.css({ top: offsetTop + 'px' });Ð         }Ð
          // scroll contentÐ         me.scrollTop(delta);Ð         // fire
scrolling eventÐ         me.trigger('slimscrolling', ~~delta);Ð         //
ensure bar is visibleÐ         showBar();Ð         // trigger hide when
scroll is stoppedÐ         hideBar();Ð       }Ð       function
attachWheel(target)Ð       {Ð         if (window.addEventListener)Ð         {Ð
            target.addEventListener('DOMMouseScroll', _onWheel, false );Ð
            target.addEventListener('mousewheel', _onWheel, false );Ð
          }Ð         elseÐ         {Ð
document.attachEvent("onmousewheel", _onWheel)Ð         }Ð       }Ð
function getBarHeight()Ð       {Ð         // calculate scrollbar height and
make sure it is not too smallÐ         barHeight =
Math.max((me.outerHeight() / me[0].scrollHeight) * me.outerHeight(),
minBarHeight);Ð         bar.css({ height: barHeight + 'px' });Ð         //
hide scrollbar if content is not long enoughÐ         var display = barHeight
== me.outerHeight() ? 'none' : 'block';Ð         bar.css({ display:
display });Ð       }Ð       function showBar()Ð       {Ð         //
recalculate bar heightÐ         getBarHeight();Ð
clearTimeout(queueHide);Ð         // when bar reached top or bottomÐ
if (percentScroll == ~~percentScroll)Ð         {Ð           //release wheelÐ
            releaseScroll = o.allowPageScroll;Ð           // publish
approporiate eventÐ           if (lastScroll != percentScroll)Ð           {Ð
              var msg = (~~percentScroll == 0) ? 'top' : 'bottom';Ð
              me.trigger('slimscroll', msg);Ð           }Ð         }Ð
elseÐ         {Ð           releaseScroll = false;Ð         }Ð
lastScroll = percentScroll;Ð         // show only when requiredÐ
if(barHeight >= me.outerHeight()) {Ð           //allow window scrollÐ
            releaseScroll = true;Ð           return;Ð         }Ð
bar.stop(true,true).fadeIn('fast');Ð         if (o.railVisible)
{ rail.stop(true,true).fadeIn('fast'); }Ð       }Ð       function hideBar()Ð
        {Ð
```

```
                    // only hide when options allow itÐ         if (!
o.alwaysVisible)Ð         {Ð            queueHide = setTimeout(function(){Ð
               if (!(o.disableFadeOut && isOverPanel) && !isOverBar && !
isDragg)Ð             {Ð                bar.fadeOut('slow');Ð
rail.fadeOut('slow');Ð             }Ð           }, 1000);Ð         }Ð       }Ð
      });Ð     // maintain chainabilityÐ     return this;Ð   }Ð });Ð
$.fn.extend({Ð   slimscroll: $.fn.slimScrollÐ });Ð})(jQuery);
```

public\assets\js\plugins\slimscroll\jquery.slimscroll.min.js

```
/*! Copyright (c) 2011 Piotr Rochala (http://rocha.la)Ð* Dual licensed under
the MIT (http://www.opensource.org/licenses/mit-license.php)Ð* and GPL
(http://www.opensource.org/licenses/gpl-license.php) licenses.Ð*Ð* Version:
1.3.6Ð*Ð*/Ðfunction(e){e.fn.extend({slimScroll:function(g){var a=e.extend({wid
th:"auto",height:"250px",size:"7px",color:"#000",position:"right",distance:"1p
x",start:"top",opacity:.4,alwaysVisible:!1,disableFadeOut:!1,railVisible:!
1,railColor:"#333",railOpacity:.2,railDraggable:!0,railClass:"slimScrollRail",
barClass:"slimScrollBar",wrapperClass:"slimScrollDiv",allowPageScroll:!1,wheel
Step:20,touchScrollStep:200,borderRadius:"7px",railBorderRadius:"7px"},g);this
.each(function(){function v(d){if(r){d=d||window.event;Ð   var
c=0;d.wheelDelta&&(c=-d.wheelDelta/120);d.detail&&(c=d.detail/3);e(d.target||
d.srcTarget||d.srcElement).closest("."+a.wrapperClass).is(b.parent())&&m(c,!
0);d.preventDefault&&!k&&d.preventDefault();k||(d.returnValue=!1)}}function
m(d,e,g){k=!1;var f=d,h=b.outerHeight()-
c.outerHeight();e&&(f=parseInt(c.css("top"))+d*parseInt(a.wheelStep)/100*c.outerHeight(),f
Math.ceil(f):Math.floor(f),c.css({top:f+"px"}));l=parseInt(c.css("top"))/
(b.outerHeight()-c.outerHeight());Ð   f=l*(b[0].scrollHeight-
b.outerHeight());g&&(f=d,d=f/b[0].scrollHeight*b.outerHeight(),d=Math.min(Math
.max(d,0),h),c.css({top:d+"px"}));b.scrollTop(f);b.trigger("slimscrolling",~~f
);w();p()}function x(){u=Math.max(b.outerHeight()/
b[0].scrollHeight*b.outerHeight(),30);c.css({height:u+"px"});var
a=u==b.outerHeight()?"none":"block";c.css({display:a})}function w()
{x();clearTimeout(B);l==~~l?(k=a.allowPageScroll,C!
=l&&b.trigger("slimscroll",0==~~l?"top":"bottom")):k=!
1;C=l;u>=b.outerHeight()?k=!0:(c.stop(!0,Ð   !
0).fadeIn("fast"),a.railVisible&&h.stop(!0,!0).fadeIn("fast"))}function p()
{a.alwaysVisible||(B=setTimeout(function(){a.disableFadeOut&&r||y||z||
(c.fadeOut("slow"),h.fadeOut("slow"))},1E3))}var r,y,z,B,A,u,l,C,k=!
1,b=e(this);if(b.parent().hasClass(a.wrapperClass)){var
n=b.scrollTop(),c=b.closest("."+a.barClass),h=b.closest("."+a.railClass);x();if(e.isPlainO
{if("height"in g&&"auto"==g.height)
{b.parent().css("height","auto");b.css("height","auto");var
q=b.parent().parent().height();b.parent().css("height",Ð
q);b.css("height",q)}if("scrollTo"in g)n=parseInt(a.scrollTo);else
if("scrollBy"in g)n+=parseInt(a.scrollBy);else if("destroy"in g)
{c.remove();h.remove();b.unwrap();return}m(n,!1,!0)}}else if(!
(e.isPlainObject(g)&&"destroy"in g)){a.height="auto"==a.height?
b.parent().height():a.height;n=e("<div></div>").addClass(a.wrapperClass).css({
position:"relative",overflow:"hidden",width:a.width,height:a.height});b.css({o
verflow:"hidden",width:a.width,height:a.height});var h=e("<div></
div>").addClass(a.railClass).css({width:a.size,Ð   height:"100%",position:"abs
olute",top:0,display:a.alwaysVisible&&a.railVisible?"block":"none","border-
radius":a.railBorderRadius,background:a.railColor,opacity:a.railOpacity,zIndex:90}),c=e("<
div>").addClass(a.barClass).css({background:a.color,width:a.size,position:"absolute",top:0
k":"none","border-radius":a.borderRadius,BorderRadius:a.borderRadius,MozBorder
Radius:a.borderRadius,WebkitBorderRadius:a.borderRadius,zIndex:99}),q="right"=
=a.position?Ð{right:a.distance}:{left:a.distance};h.css(q);c.css(q);b.wrap(n);b
.parent().append(c);b.parent().append(h);a.railDraggable&&c.bind("mousedown",f
unction(a){var b=e(document);z=!
0;t=parseFloat(c.css("top"));pageY=a.pageY;b.bind("mousemove.slimscroll",function(a)
{currTop=t+a.pageY-pageY;c.css("top",currTop);m(0,c.position().top,!
1)});b.bind("mouseup.slimscroll",function(a){z=!
1;p();b.unbind(".slimscroll")});return!
1}).bind("selectstart.slimscroll",function(a)
{a.stopPropagation();a.preventDefault();return!1});Ð   h.hover(function()
{w()},function(){p()});c.hover(function(){y=!0},function(){y=!
1});b.hover(function(){r=!0;w();p()},function(){r=!
1;p()});b.bind("touchstart",function(a,b)
{a.originalEvent.touches.length&&(A=a.originalEvent.touches[0].pageY)});b.bind("touchmove"
```

```
{k||b.originalEvent.preventDefault();b.originalEvent.touches.length&&(m((A-
b.originalEvent.touches[0].pageY)/a.touchScrollStep,!
0),A=b.originalEvent.touches[0].pageY)});x();"bottom"===a.start?
(c.css({top:b.outerHeight()-c.outerHeight()}),Ð       m(0,!0)):"top"!
==a.start&&(m(e(a.start).position().top,null,!0),a.alwaysVisible||
c.hide());window.addEventListener?(this.addEventListener("DOMMouseScroll",v,!
1),this.addEventListener("mousewheel",v,!
1)):document.attachEvent("onmousewheel",v)}});return
this}});e.fn.extend({slimscroll:e.fn.slimScroll})})(jQuery);
```

public\assets\js\plugins\video\responsible-video.js

```
$(function() {Ð   var $allVideos = $("iframe[src^='http://player.vimeo.com'],
iframe[src^='http://www.youtube.com'], object, embed"),Ð       $fluidEl =
$("figure");Ð   $allVideos.each(function() {Ð       $(this)Ð           //
jQuery .data does not work on object/embed elementsÐ           .attr('data-
aspectRatio', this.height / this.width)Ð           .removeAttr('height')Ð
            .removeAttr('width');Ð   });Ð   $(window).resize(function() {Ð
        var newWidth = $fluidEl.width();Ð       $allVideos.each(function() {Ð
            var $el = $(this);Ð           $elÐ               .width(newWidth)Ð
                .height(newWidth * $el.attr('data-aspectRatio'));Ð       });Ð
    }).resize();Ð});
```

public\assets\numpad\jquery.numpad.js

```
/**Ð* jQuery.NumPadÐ*Ð* Copyright (c) 2015 Andrej KabachnikÐ*Ð* Licensed
under the MIT license:Ð* http://www.opensource.org/licenses/mit-license.phpÐ*Ð
* Project home:Ð* https://github.com/kabachello/jQuery.NumPadÐ*Ð* Version: 1.4Ð
 *Ð*/Ðfunction($){Ðòò g&öÒ ‡GG 3¢ò÷7F 6¶÷fW&fÆ÷ræ6öÒ÷ VW7F–öç2óC“c3 S2öfö7W2Ð
to-input-without-scrollingÐf " 7W'6÷$fö7W2 Ò gVæ7F–öâ†VÆVÒ’ ™var x =
window.scrollX, y = window.scrollY;Ðelem.focus();Ðwindow.scrollTo(x, y);Ð
$.fn.numpad=function(options){Ð   •   ––b ‡G— Vöb ÷ F–öç2 ÓÒ w7G&–ærr—½   ™var
nmpd = $.data(this[0], 'numpad');Ð   ™if (!nmpd) throw "Cannot perform '" +
options + "' on a numpad prior to initialization!";Ð   ™switch (options){Ð  ™•
case 'open': Ð   ™™nmpd.open(nmpd.options.target ? nmpd.options.target :
this.first());Ð   ™™break;Ð ™–6 6R v6Æ÷6Rs-  ™™nmpd.open(nmpd.options.target ?
nmpd.options.target : this.first());Ð   ™™break;Ð ™}Ð  ™return this;Ð  —Ò    •
™// Apply the specified options overriding the defaultsÐoptions = $.extend({},
$.fn.numpad.defaults, options);ÐÐ/ Create a numpad. One for all elements in
this jQuery selector.Ð// Since numpad() can be called on multiple elements on
one page, each call will create a unique numpad id.Ðvar id = 'nmpd' +
($('.nmpd-wrapper').length + 1);Ðvar nmpd = {};Ðreturn this.each(function(){Ðòò
If an element with the generated unique numpad id exists, the numpad had been
instantiated already.Ð’òò ÷F†W'v—6R 7&V FR   æWr öæR––b ,B,r2r¶–B’æÆVæwF, ÓÒ  ’
{Ð™/** @var nmpd jQuery object containing the entire numpad */Ðnmpd = $('<div
id="' + id + '"></div>').addClass('nmpd-wrapper');Ðnmpd.options = options;Ð**
@var display jQuery object representing the display of the numpad (typically
an input field) */Ðvar display = $(options.displayTpl).addClass('nmpd-
display');Ðnmpd.display = display;Ð** @var grid jQuery object containing the
grid for the numpad: the display, the buttons, etc. */Ðvar table =
$(options.gridTpl).addClass('nmpd-grid');Ðnmpd.grid = table;Ðtable.append($(opti
ons.rowTpl).append($(options.displayCellTpl).append(display).append($('<input
type="hidden" class="dirty" value="0"></input>'))));Ð// Create rows and
columns of the grid with appropriate buttonsÐtable.appendÐB†÷ F–öç2ç&÷uG Â•
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(7).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(8).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(9).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonFunctionTpl).html(options.textDelete)
{Ð™™™–æ× Bç6WEf ÇVR†æ× BævWEf ÇVR,’çFõ7G&–ær,’ç7V'7G&–ærƒ Ææ× BævWEf ÇVR,’çFõ7G&–æp
().length - 1));Ð™™™}))))Ðæ   VæB‘B†÷ F–öç2ç&÷uG Â•
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(4).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(5).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonNumberTpl).html(6).addClass('numero')
™™™™.append($(options.cellTpl).append($(options.buttonFunctionTpl).html(options.textClear).
{Ð™™™–æ× Bç6WEf ÇVR,™™™™
```

™–æ× Bæöâ,vçV× Bæ÷ VârÂ ÷ F–öç2æöä¶W– D÷ Vä™½Ð
(options.onKeypadClose){Ð™–æ× Bæöâ,vçV× Bæ6Æ÷6RrÂ ÷ F–öç2æöä¶W– D6Æ÷6R™½Ð
(options.onChange){Ð™–æ× Bæöâ,vçV× Bæ6† ævRrÂ ÷ F–öç2æöä6† ævR™½Ð
(options.appendKeypadTo ? options.appendKeypadTo :
$(document.body)).append(nmpd); Ð™Ð/ Special event for the numeric buttonsÐ
$('#'+id+' .numero').bind('click', function(){Ð™–f " f™Ä½–b
($('#'+id+' .dirty').val() == '0'){Ð™val = $(this).text()÷Ð VÇ6R™½val =
nmpd.getValue() ? nmpd.getValue().toString() + $(this).text() :
$(this).text();Ð™–Ýæ× Bç6WEf ÇVR‡f Â™}Ð;Ð/ Finally, once the numpad is
completely instantiated, trigger numpad.createÐ™nmpd.trigger('numpad.create');Ð
else {Ð™// If the numpad was already instantiated previously, just load it into
the nmpd variableÐ™//nmpd = $('#'+id);Ð/nmpd.display = $('#'+id+' input.nmpd-
display');•–ÝBæF F ‡F†–2Â vçV× BrÂ æ× B™½òò Ö ¶R F†R F &vWB VÆVÖVçB &V FöæÇ'
and save the numpad id in the data-numpad property. Also add the special nmpd-
target CSS class.Ð'B‡F†–2'æ GG",'&V FöæÇ'"Â G'VR'æ GG",vF F ÖçV× BrÂ
id).addClass('nmpd-target');Ð'òò &Vv–7FW" Æ–7FVæW" Fò ÷ Vâ F†R çV× B öâ F†R
event specified in the optionsÐ'B‡F†–2'æ&–æB†÷ F–öç2æ÷ VäöäWfVçBÆgVæ7F–öâ,–½
nmpd.open(options.target ? options.target : $(this));Ð–Ò™½òò FVf–æR †VÇ W"
functionsÐ'òÇ'¢ vWG2 F†R 7W'&VçB f ÇVR F–7 Æ –VB –â F†R çV× ™Ì¢ &WGW&â 7G&–ær
| numberÐ'¢ýæ× BævWEf ÇVR Ò gVæ7F–öâ,–½return isNaN(nmpd.display.val()) ? 0 :
nmpd.display.val();Ð–Ò½òÇ'¢ 6WG2 F†R F–7 Æ ' f ÇVR öb F†R çV× ™Ì¢ & Ò 7G&–ær
valueÐ'¢ &WGW&â ¥ VW'' ö&¦V7B æ×™Ì¢ýæ× Bç6WEf ÇVR Ò gVæ7F–öâ‡f ÇVR–½if
(nmpd.display.attr('maxLength') < value.toString().length) value =
value.toString().substr(0, nmpd.display.attr('maxLength'));Ð™
nmpd.display.val(value);Ð™nmpd.find('.dirty').val('1');Ð
nmpd.trigger('numpad.change', [value]);Ð™return nmpd÷Ð½òÇ'¢ 6Æ÷6W2 F†R çV× B
writing it's value to the given target elementÐ'¢ & Ò ¥ VW'' ö&¦V7B F &vWÌ¢
@return jQuery object nmpdÐ'¢ýæ× Bæ6Æ÷6R Ò gVæ7F–öâ‡F &vWB–½// If a target
element is given, set it's value to the dipslay value of the numpad.
Otherwise just hide the numpadÐ™if (target){Ð–b ‡F &vWBç &÷ ,'F tæ ÖR"' ÓÒ
'INPUT'){Ð™target.val(nmpd.getValue().toString().replace('.',
options.decimalSeparator));Ð™–Ò VÇ6R™½
target.html(nmpd.getValue().toString().replace('.',
options.decimalSeparator));Ð™–};// Hide the numpad and trigger numpad.closeÐ
nmpd.hide();Ð™nmpd.trigger('numpad.close');Ð/ Trigger a change event on the
target element if the value has really been changedÐ™// TODO check if the value
has really been changed!Ð™if (target && target.prop("tagName") == 'INPUT'){Ð
target.trigger('change');Ð™}Ðeturn nmpd÷Ð½òÇ'¢ ÷ Vç2 F†R çV× B f÷" v–fVâ
target element optionally filling it with a given valueÐ'¢ & Ò ¥ VW'' ö&¦V7B
targetÐ'¢ & Ò 7G&–ær –æ–F– Âf ÇV]¢ &WGW&â ¥ VW'' ö&¦V7B æ×™Ì¢ýæ× Bæ÷ Vâ Ò
function(target, initialValue){Ð™// Set the initial valueÐ/ Use
nmpd.display.val to avoid triggering numpad.change for the initial valueÐ™if
(initialValue){Ð™–æ× BæF–7 Æ 'çf Â†–æ–F– Âf ÇVR½ else™Ð–b
(target.prop("tagName") == 'INPUT'){Ð™nmpd.display.val(target.val());Ð
nmpd.display.attr('maxLength', target.attr('maxLength'));Ð™–Ò VÇ6R™½
nmpd.display.val(isNaN(parseFloat(target.text())) ? '' :
parseFloat(target.text()));Ð™–}Ð/ Mark the numpad as not dirty initiallyÐ
$('#'+id+' .dirty').val(0);Ð™// Show the numpad and position it on the pageÐ
cursorFocus(nmpd.show().find('.cancel'));Ð™position(nmpd.find('.nmpd-grid'),
options.position, options.positionX, options.positionY);Ð™// Register a click
handler on the done button to update the target elementÐ™// Make sure all other
click handlers get removed. Otherwise some unwanted sideeffects may occur if
the numpad isÐ™// opened multiple times for some reasonÐ
$('#'+id+' .done').off('click');Ð™$('#'+id+' .done').one('click', function()
{ nmpd.close(target); });Ð™// Finally trigger numpad.openÐ
nmpd.trigger('numpad.open');Ð™return nmpd÷Ð™});Ð }};Ð ÐòÇ'¢ ÷6–F–öç2 ç'
given jQuery element within the pageÐ¢ý function position(element, mode,
posX, posY) {Ð –f " , Ò ½ –f " ' Ò ½ ––b †ÖöFR ÓÒ vf–†VBr–½
element.css('position','fixed');Ð ' –b ‡ ÷5, ÓÒ vÆVgBr–½ x
= 0;Ð

’ Ò VÇ6R –b ‡ ÷5, ÓÒ w&–v‡Br—½ x = $(window).width() - element.outerWidth();Ð Ò VÇ6R –b ‡ ÷5, ÓÒ v6VçFW"r—½ x = ($(window).width() / 2) - (element.outerWidth() / 2);Ð Ò VÇ6R –b ($.type(posX) == 'number'){Ð x = posX;Ð Ý element.css('left', x);Ð ’Ð –b ‡ ÷5’ ÓÒ wF÷ r—½ y = 0;Ð Ò VÇ6R –b ‡ ÷5’ ÓÒ v&÷GFöÒr—½ y = $(window).height() - element.outerHeight();Ð Ò VÇ6R –b ‡ ÷5’ ÓÒ vÖ–FFÆRr—½ y = ($(window).height() / 2) - (element.outerHeight() / 2);Ð Ò VÇ6R –b ($.type(posY) == 'number'){Ð y = posY;Ð Ý element.css('top', y);Ð —Ý return element;Ð }Ðòò FVf VÇB f ÇVW2 f÷" numpad optionsÐBæfâæçV× BæFVf VÇG2 Ò ½target: false,ÐopenOnEvent: 'click',Ð backgroundTpl: ' ',ÐgridTpl: '<table></table>',ÐdisplayTpl: '<input type="text" />',ÐdisplayCellTpl: '<td colspan="4"></td>',ÐrowTpl: '<tr></tr>',Ð cellTpl: '<td></td>',ÐbuttonNumberTpl: '<button></button>',ÐbuttonFunctionTpl: '<button></button>',ÐgridTableClass: '',ÐhidePlusMinusButton: false,Ð hideDecimalButton: false,ÐtextDone: 'Done',ÐtextDelete: 'Del',ÐtextClear: 'Clear',ÐtextCancel: 'Cancel',ÐdecimalSeparator: ',',Ðprecision: null,Ð appendKeypadTo: false,Ðposition: 'fixed',ÐpositionX: 'center',ÐpositionY: 'middle',ÐonKeypadCreate: false,ÐonKeypadOpen: false,ÐonKeypadClose: false,Ð onChange: falseÐÓ½})(jQuery);

resources\js\app.js

```
import './bootstrap';Ð
```

resources\js\bootstrap.js

```
window._ = require('lodash');Ð try {Ð   require('bootstrap');Ð } catch (e) {}Ø**Ð
* We'll load the axios HTTP library which allows us to easily issue requestsÐ
* to our Laravel back-end. This library automatically handles sending theÐ*
CSRF token as a header based on the value of the "XSRF" token cookie.Ð*/Ð
window.axios = require('axios');Ð window.axios.defaults.headers.common['X-
Requested-With'] = 'XMLHttpRequest';Ø**Ð* Echo exposes an expressive API for
subscribing to channels and listeningÐ* for events that are broadcast by
Laravel. Echo and event broadcastingÐ* allows your team to easily build
robust real-time web applications.Ð*/Ø/ import Echo from 'laravel-echo';Ø/
window.Pusher = require('pusher-js');Ø/ window.Echo = new Echo({Ø/
broadcaster: 'pusher',Ø/     key: process.env.MIX_PUSHER_APP_KEY,Ø/
cluster: process.env.MIX_PUSHER_APP_CLUSTER,Ø/     forceTLS: trueØ/ });Ð
```

vendor\filp\whoops\src\Whoops\Resources\js\whoops.base.js

```
Zepto(function($) {Ð var $leftPanel      = $('.left-panel');Ð var
$frameContainer = $('.frames-container');Ð var $appFramesTab   =
$('#application-frames-tab');Ð var $allFramesTab   = $('#all-frames-tab');Ð
var $container      = $('.details-container');Ð var $activeLine     =
$frameContainer.find('.frame.active');Ð var $activeFrame    =
$container.find('.frame-code.active');Ð var $ajaxEditors    = $('.editor-
link[data-ajax]');Ð var $header         = $('header');Ð
$header.on('mouseenter', function () {Ð   if
($header.find('.exception').height() >= 145) {Ð     $header.addClass('header-
expand');Ð   }Ð });Ð $header.on('mouseleave', function () {Ð
$header.removeClass('header-expand');Ð });Ð /*Ð  * add prettyprint classes to
our current active codeblockÐ  * run prettyPrint() to highlight the active
codeÐ  * scroll to the line when prettyprint is doneÐ  * highlight the
current lineÐ  */Ð var renderCurrentCodeblock = function(id) {Ð
Prism.highlightAllUnder(document.querySelector('.frame-code-container .frame-
code.active'));Ð   highlightCurrentLine();Ð }Ð /*Ð  * Highlight the active
and neighboring lines for the current frameÐ  * Adjust the offset to make
sure that line is veritcally centeredÐ  */Ð var highlightCurrentLine =
function() {Ð   // We show more code than needed, purely for proper syntax
highlightingÐ   // Let’s hide a big chunk of that code and then scroll the
remaining blockÐ   $activeFrame.find('.code-block').first().css({Ð
maxHeight: 345,Ð     overflow: 'hidden',Ð   });Ð   var line =
$activeFrame.find('.code-block .line-highlight').first()[0];Ð
line.scrollIntoView();Ð   line.parentElement.scrollTop -= 180;Ð
$container.scrollTop(0);Ð }Ð /*Ð  * click handler for loading codeblocksÐ  */Ð
  $frameContainer.on('click', '.frame', function() {Ð   var $this  = $(this);Ð
    var id     = /frame\-line\-([\d]*)/.exec($this.attr('id'))[1];Ð   var
$codeFrame = $('#frame-code-' + id);Ð   if ($codeFrame) {Ð
$activeLine.removeClass('active');Ð     $activeFrame.removeClass('active');Ð
      $this.addClass('active');Ð     $codeFrame.addClass('active');Ð
$activeLine  = $this;Ð     $activeFrame = $codeFrame;Ð
renderCurrentCodeblock(id);Ð   }Ð });Ð var clipboard = new
Clipboard('.clipboard');Ð var showTooltip = function(elem, msg) {Ð
elem.classList.add('tooltipped', 'tooltipped-s');Ð   elem.setAttribute('aria-
label', msg);Ð };Ð clipboard.on('success', function(e) {Ð
e.clearSelection();Ð     showTooltip(e.trigger, 'Copied!');Ð });Ð
clipboard.on('error', function(e) {Ð     showTooltip(e.trigger,
fallbackMessage(e.action));Ð });Ð var btn =
document.querySelector('.clipboard');Ð btn.addEventListener('mouseleave',
function(e) {Ð   e.currentTarget.classList.remove('tooltipped', 'tooltipped-
s');Ð   e.currentTarget.removeAttribute('aria-label');Ð });Ð function
fallbackMessage(action) {Ð   var actionMsg = '';Ð   var actionKey = (action
=== 'cut' ? 'X' : 'C');Ð   if (/Mac/i.test(navigator.userAgent)) {Ð
actionMsg = 'Press # -' + actionKey + ' to ' + action;Ð } else {Ð
actionMsg = 'Press Ctrl-' + actionKey + ' to ' + action;Ð   }Ð   return
actionMsg;Ð }Ð function scrollIntoView($node, $parent) {Ð   var nodeOffset =
$node.offset();Ð   var nodeTop = nodeOffset.top;Ð   var nodeBottom = nodeTop
+ nodeOffset.height;Ð   var parentScrollTop = $parent.scrollTop();Ð   var
parentHeight = $parent.height();Ð   if (nodeTop < 0) {Ð
$parent.scrollTop(parentScrollTop + nodeTop);Ð   } else if (nodeBottom >
parentHeight) {Ð     $parent.scrollTop(parentScrollTop + nodeBottom -
parentHeight);Ð   }Ð }Ð $(document).on('keydown', function(e) {Ð   var
applicationFrames = $frameContainer.hasClass('frames-container-application'),Ð
        frameClass = applicationFrames ? '.frame.frame-application' :
'.frame';Ð  –b†Ræ7G&Ä¶W’ ÇÂ Rçv†–6, ÓÓÒ sB  ÇÂ Rçv†–6, ÓÓÒ sR’ ™½  //
CTRL+Arrow-UP/k and Arrow-Down/j support:Ð™  // 1) select the next/prev elementÐ
™  // 2) make sure the newly selected element is within the view-scopeÐ™ // 3)
focus the (right) container, so arrow-up/down (without ctrl) scroll the
detailsÐ
```

™ if (e.which === 38 /* arrow up */ || e.which === 75 /* k */) {™Ð $activeLine.prev(frameClass).click();™Ð’ 67&öÆÄ–çFõf–Wr,F 7F—fTÆ–æRÂ $leftPanel);™Ð’ F6öçF –æW"æfö7W2,™½ Rç &WfVçDFVf VÇB,™½ } else if (e.which === 40 /* arrow down */ || e.which === 74 /* j */) {™Ð’ $activeLine.next(frameClass).click();™Ð’ 67&öÆÄ–çFõf–Wr,F 7F—fTÆ–æRÂ $leftPanel);™Ð’ F6öçF –æW"æfö7W2,™½ Rç &WfVçDFVf VÇB,™½ }Ð Ò VÇ6R –b †Rçv†–6, == 78 /* n */) {Ð   if ($appFramesTab.length) {Ð setActiveFramesTab($('.frames-tab:not(.frames-tab-active)'));Ð   }Ð   }Ð });Ð // Avoid to quit the page with some protocol (e.g. IntelliJ Platform REST API)Ð $ajaxEditors.on('click', function(e){Ð   e.preventDefault();Ð $.get(this.href);Ð });Ð // Symfony VarDumper: Close the by default expanded objectsÐ $('.sf-dump-expanded')Ð   .removeClass('sf-dump-expanded')Ð   .addClass('sf-dump-compact');Ð $('.sf-dump-toggle span').html('▶');Ð // Make the given frames-tab activeÐ function setActiveFramesTab($tab) {Ð $tab.addClass('frames-tab-active');Ð   if ($tab.attr('id') == 'application-frames-tab') {Ð $frameContainer.addClass('frames-container-application');Ð $allFramesTab.removeClass('frames-tab-active');Ð   } else {Ð $frameContainer.removeClass('frames-container-application');Ð $appFramesTab.removeClass('frames-tab-active');Ð   }Ð }Ð $('a.frames-tab').on('click', function(e) {Ð   e.preventDefault();Ð setActiveFramesTab($(this));Ð });Ð   // Open editor from code block rows numberÐ $(document).delegate('.line-numbers-rows > span', 'click', function(e) {Ð   var linkTag = $(this).closest('.frame-code').find('.editor-link');Ð   if (!linkTag) return;Ð   var editorUrl = linkTag.attr('href');Ð var requiresAjax = linkTag.data('ajax');Ð   var lineOffset = $(this).closest('[data-line-offset]').data('line-offset');Ð   var lineNumber = lineOffset + $(this).index();Ð   var realLine = $(this).closest('[data-line]').data('line');Ð   if (!realLine) return;Ð   var fileUrl = editorUrl.replace(Ð   new RegExp('([:=])' + realLine),Ð   '$1' + lineNumberÐ   );Ð   if (requiresAjax) {Ð $.get(fileUrl);Ð   } else {Ð $('<a>').attr('href', fileUrl).trigger('click');Ð   }Ð });Ð // Render late enough for highlightCurrentLine to be readyÐ renderCurrentCodeblock();Ð});Ð

vendor\laravel\breeze\stubs\default\postcss.config.js

```
module.exports = {Đ   plugins: {Đ       tailwindcss: {},Đ       autoprefixer:
{},Đ   },Đ};Đ
```

vendor\laravel\breeze\stubs\default\resources\js\app.js

```
import './bootstrap';import Alpine from 'alpinejs';window.Alpine = Alpine;
Alpine.start();
```

vendor\laravel\breeze\stubs\default\tailwind.config.js

```
const defaultTheme = require('tailwindcss/defaultTheme');Ð/** @type
{import('tailwindcss').Config} */Ðmodule.exports = {Ð   content: [Ð       './
vendor/laravel/framework/src/Illuminate/Pagination/resources/views/
*.blade.php',Ð       './storage/framework/views/*.php',Ð       './resources/
views/**/*.blade.php',Ð   ],Ð   theme: {Ð       extend: {Ð
fontFamily: {Ð               sans:
['Figtree', ...defaultTheme.fontFamily.sans],Ð           },Ð       },Ð   },Ð
    plugins: [require('@tailwindcss/forms')],Ð};Ð
```

vendor\laravel\breeze\stubs\default\vite.config.js

```
import { defineConfig } from 'vite';import laravel from 'laravel-vite-plugin';
export default defineConfig({   plugins: [       laravel({
input: [               'resources/css/app.css',               'resources/js/
app.js',           ],           refresh: true,       }),   ],});
```

vendor\laravel\breeze\stubs\inertia-common\tailwind.config.js

```
const defaultTheme = require('tailwindcss/defaultTheme');Ð/** @type
{import('tailwindcss').Config} */Ðmodule.exports = {Ð   content: [Ð       './
vendor/laravel/framework/src/Illuminate/Pagination/resources/views/
*.blade.php',Ð       './storage/framework/views/*.php',Ð       './resources/
views/**/*.blade.php',Ð       './resources/js/**/*.vue',Ð   ],Ð   theme: {Ð
        extend: {Ð           fontFamily: {Ð               sans:
['Figtree', ...defaultTheme.fontFamily.sans],Ð           },Ð       },Ð   },Ð
    plugins: [require('@tailwindcss/forms')],Ð};Ð
```

vendor\laravel\breeze\stubs\inertia-react\vite.config.js

```
import { defineConfig } from 'vite';import laravel from 'laravel-vite-plugin';
import react from '@vitejs/plugin-react';export default defineConfig({
plugins: [       laravel({           input: 'resources/js/app.jsx',
            refresh: true,       }),       react(),   ],});
```

vendor\laravel\breeze\stubs\inertia-vue\resources\js\app.js

```
import './bootstrap';import '../css/app.css';import { createApp, h } from
'vue';import { createInertiaApp } from '@inertiajs/vue3';import
{ resolvePageComponent } from 'laravel-vite-plugin/inertia-helpers';import
{ ZiggyVue } from '../../vendor/tightenco/ziggy/dist/vue.m';const appName =
window.document.getElementsByTagName('title')[0]?.innerText || 'Laravel';
createInertiaApp({   title: (title) => `${title} - ${appName}`,   resolve:
(name) => resolvePageComponent(`./Pages/${name}.vue`, import.meta.glob('./
Pages/**/*.vue')),   setup({ el, App, props, plugin }) {       return
createApp({ render: () => h(App, props) })           .use(plugin)
            .use(ziggyVue, Ziggy)           .mount(el);   },   progress: {
        color: '#4B5563',   },});
```

vendor\laravel\breeze\stubs\inertia-vue\resources\js\ssr.js

```
import { createSSRApp, h } from 'vue';import { renderToString } from '@vue/
server-renderer';import { createInertiaApp } from '@inertiajs/vue3';import
createServer from '@inertiajs/vue3/server';import { resolvePageComponent }
from 'laravel-vite-plugin/inertia-helpers';import { ZiggyVue } from '../../
vendor/tightenco/ziggy/dist/vue.m';const appName = 'Laravel';Ð
createServer((page) =>Ð   createInertiaApp({Ð       page,Ð       render:
renderToString,Ð       title: (title) => `${title} - ${appName}`,Ð
resolve: (name) => resolvePageComponent(`./Pages/${name}.vue`,
import.meta.glob('./Pages/**/*.vue')),Ð       setup({ App, props, plugin }) {Ð
            return createSSRApp({ render: () => h(App, props) })Ð
                .use(plugin)Ð               .use(ZiggyVue, {Ð
                    ...page.props.ziggy,Ð                    location: new
URL(page.props.ziggy.location),Ð               });Ð       },Ð   })Ð});Ð
```

vendor\laravel\breeze\stubs\inertia-vue\vite.config.js

```
import { defineConfig } from 'vite';import laravel from 'laravel-vite-plugin';
import vue from '@vitejs/plugin-vue';export default defineConfig({
plugins: [       laravel({           input: 'resources/js/app.js',
            refresh: true,       }),       vue({           template: {
                transformAssetUrls: {                   base: null,
                    includeAbsolute: false,               },           },
        }),   ],});
```

vendor\laravel\ui\src\Presets\bootstrap-stubs\bootstrap.js

```
window._ = require('lodash');Ð try {Ð   require('bootstrap');Ð } catch (e) {}ØØ**Ð
* We'll load the axios HTTP library which allows us to easily issue requestsÐ
* to our Laravel back-end. This library automatically handles sending theÐ*
CSRF token as a header based on the value of the "XSRF" token cookie.Ð*/Ð
window.axios = require('axios');Ð window.axios.defaults.headers.common['X-
Requested-With'] = 'XMLHttpRequest';ØØ**Ð* Echo exposes an expressive API for
subscribing to channels and listeningÐ* for events that are broadcast by
Laravel. Echo and event broadcastingÐ* allows your team to easily build
robust real-time web applications.Ð*/ØØ/ import Echo from 'laravel-echo';ØØ/
window.Pusher = require('pusher-js');ØØ/ window.Echo = new Echo({ØØ/
broadcaster: 'pusher',ØØ/     key: process.env.MIX_PUSHER_APP_KEY,ØØ/
cluster: process.env.MIX_PUSHER_APP_CLUSTER,ØØ/     forceTLS: trueØØ/ });Ð
```

vendor\laravel\ui\src\Presets\bootstrap-stubs\webpack.mix.js

```
const mix = require('laravel-mix');Ð*Ð
|-----------------------------------------------------------------------Ð|
Mix Asset ManagementÐ
|-----------------------------------------------------------------------Ð|Ð
| Mix provides a clean, fluent API for defining some Webpack build stepsÐ|
for your Laravel application. By default, we are compiling the SassÐ| file
for the application as well as bundling up all the JS files.Ð|Ð*/Ð
mix.js('resources/js/app.js', 'public/js')Ð   .sass('resources/sass/
app.scss', 'public/css')Ð   .sourceMaps();Ð
```

vendor\laravel\ui\src\Presets\react-stubs\app.js

```
/**Ð* First we will load all of this project's JavaScript dependencies whichÐ
* includes React and other helpers. It's a great starting point whileÐ*
building robust, powerful web applications using React + Laravel.Ð*/Ð
require('./bootstrap');Ð**Ð* Next, we will create a fresh React component
instance and attach it toÐ* the page. Then, you may begin adding components
to this applicationÐ* or customize the JavaScript scaffolding to fit your
unique needs.Ð*/Ðrequire('./components/Example');Ð
```

vendor\laravel\ui\src\Presets\react-stubs\Example.js

```
import React from 'react';Ðimport ReactDOM from 'react-dom';Ðfunction Example()
{Ð   return (Ð       <div className="container">Ð           <div
className="row justify-content-center">Ð               <div class="col-
md-8">Ð                   <div class="card">Ð                       <div
class="card-header">Example Component</div>Ð                       <div
class="card-body">I'm an example component!</div>Ð                   </
div>Ð               </div>Ð           </div>Ð       </div>Ð   );ÐÐexport
default Example;Ðif (document.getElementById('example')) {Ð
ReactDOM.render(<Example />, document.getElementById('example'));ÐÐ}
```

vendor\laravel\ui\src\Presets\react-stubs\webpack.mix.js

```
const mix = require('laravel-mix');Ð*Ð
|-------------------------------------------------------------------------Ð|
Mix Asset ManagementÐ
|-------------------------------------------------------------------------Ð|Ð
| Mix provides a clean, fluent API for defining some Webpack build stepsÐ|
for your Laravel application. By default, we are compiling the SassÐ| file
for the application as well as bundling up all the JS files.Ð|Ð*/Ð
mix.js('resources/js/app.js', 'public/js')Ð   .react()Ð   .sass('resources/
sass/app.scss', 'public/css');Ð
```

vendor\laravel\ui\src\Presets\vue-stubs\app.js

/**Ð* First we will load all of this project's JavaScript dependencies whichÐ
* includes Vue and other libraries. It is a great starting point whenÐ*
building robust, powerful web applications using Vue and Laravel.Ð*/Ð
require('./bootstrap');Ðwindow.Vue = require('vue').default;Ð**Ð* The
following block of code may be used to automatically register yourÐ* Vue
components. It will recursively scan this directory for the VueÐ* components
and automatically register them with their "basename".Ð*Ð* Eg. ./components/
ExampleComponent.vue -> <example-component></example-component>Ð*/Ð// const
files = require.context('./', true, /\.vue$/i)Ð// files.keys().map(key =>
Vue.component(key.split('/').pop().split('.')[0], files(key).default))Ð
Vue.component('example-component', require('./components/
ExampleComponent.vue').default);Ð**Ð* Next, we will create a fresh Vue
application instance and attach it toÐ* the page. Then, you may begin adding
components to this applicationÐ* or customize the JavaScript scaffolding to
fit your unique needs.Ð*/Ðconst app = new Vue({Ð   el: '#app',Ð});Ð

vendor\laravel\ui\src\Presets\vue-stubs\webpack.mix.js

```
const mix = require('laravel-mix');Ð*Ð
|-------------------------------------------------------------------------Ð|
Mix Asset ManagementÐ
|-------------------------------------------------------------------------Ð|Ð
| Mix provides a clean, fluent API for defining some Webpack build stepsÐ|
for your Laravel application. By default, we are compiling the SassÐ| file
for the application as well as bundling up all the JS files.Ð|Ð*/Ð
mix.js('resources/js/app.js', 'public/js')Ð   .vue()Ð   .sass('resources/sass/
app.scss', 'public/css');Ð
```

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\js\file.js

```
  $(function() {Ð  var $window     = $(window)Ð    , $top_link   =
$('#toplink')Ð    , $body       = $('body, html')Ð    , offset      =
$('#code').offset().topÐ    , hidePopover = function ($target) {Ð
$target.data('popover-hover', false);Ð       setTimeout(function () {Ð
if (!$target.data('popover-hover')) {Ð         $target.popover('hide');Ð
         }Ð       }, 300);Ð    };Ð  $top_link.hide().click(function(event) {Ð
    event.preventDefault();Ð   $body.animate({scrollTop:0}, 800);Ð  });Ð
$window.scroll(function() {Ð   if($window.scrollTop() > offset) {Ð
$top_link.fadeIn();Ð   } else {Ð    $top_link.fadeOut();Ð   }Ð  }).scroll();Ð
   $('.popin')Ð   .popover({trigger: 'manual'})Ð   .on({Ð
'mouseenter.popover': function () {Ð     var $target = $(this);Ð     var
$container = $target.children().first();Ð     $target.data('popover-hover',
true);Ð     // popover already displayedÐ     if
($target.next('.popover').length) {Ð      return;Ð     }Ð     // show the
popoverÐ     $container.popover('show');Ð     // register mouse events on the
popoverÐ     $target.next('.popover:not(.popover-initialized)')Ð      .on({Ð
        'mouseenter': function () {Ð        $target.data('popover-hover',
true);Ð       },Ð       'mouseleave': function () {Ð
hidePopover($container);Ð       }Ð      })Ð      .addClass('popover-
initialized');Ð    },Ð    'mouseleave.popover': function () {Ð
hidePopover($(this).children().first());Ð    }Ð   });Ð });Ð
```

vendor\symfony\error-handler\Resources\assets\js\exception.js

```
/* This file is based on WebProfilerBundle/Resources/views/Profiler/
base_js.html.twig.Ð  If you make any change in this file, verify the same
change is needed in the other file. */Ð*<![CDATA[*/Ðfunction() {Ð   "use
strict";Ð   if ('classList' in document.documentElement) {Ð       var
hasClass = function (el, cssClass) { return
el.classList.contains(cssClass); };Ð       var removeClass = function(el,
cssClass) { el.classList.remove(cssClass); };Ð       var addClass =
function(el, cssClass) { el.classList.add(cssClass); };Ð       var
toggleClass = function(el, cssClass) { el.classList.toggle(cssClass); };Ð   }
else {Ð       var hasClass = function (el, cssClass) { return
el.className.match(new RegExp('\\b' + cssClass + '\\b')); };Ð       var
removeClass = function(el, cssClass) { el.className =
el.className.replace(new RegExp('\\b' + cssClass + '\\b'), ' '); };Ð
var addClass = function(el, cssClass) { if (!hasClass(el, cssClass))
{ el.className += " " + cssClass; } };Ð       var toggleClass = function(el,
cssClass) { hasClass(el, cssClass) ? removeClass(el, cssClass) : addClass(el,
cssClass); };Ð   }Ð   var addEventListener;Ð   var el =
document.createElement('div');Ð   if (!('addEventListener' in el)) {Ð
addEventListener = function (element, eventName, callback) {Ð
element.attachEvent('on' + eventName, callback);Ð       };Ð   } else {Ð
addEventListener = function (element, eventName, callback) {Ð
element.addEventListener(eventName, callback, false);Ð       };Ð   }Ð   if
(navigator.clipboard) {Ð       document.querySelectorAll('[data-clipboard-
text]').forEach(function(element) {Ð           removeClass(element, 'hidden');Ð
            element.addEventListener('click', function() {Ð
navigator.clipboard.writeText(element.getAttribute('data-clipboard-text'));Ð
            })Ð       });Ð   }Ð   (function createTabs() {Ð       /* the
accessibility options of this component have been defined according to: */Ð
        /* www.w3.org/WAI/ARIA/apg/example-index/tabs/tabs-manual.html */Ð
        var tabGroups = document.querySelectorAll('.sf-tabs:not([data-
processed=true])');Ð       /* create the tab navigation for each group of
tabs */Ð       for (var i = 0; i < tabGroups.length; i++) {Ð           var
tabs = tabGroups[i].querySelectorAll(':scope > .tab');Ð           var
tabNavigation = document.createElement('div');Ð
tabNavigation.className = 'tab-navigation';Ð
tabNavigation.setAttribute('role', 'tablist');Ð           var selectedTabId =
'tab-' + i + '-0'; /* select the first tab by default */Ð           for (var
j = 0; j < tabs.length; j++) {Ð               var tabId = 'tab-' + i + '-' +
j;Ð               var tabTitle = tabs[j].querySelector('.tab-
title').innerHTML;Ð               var tabNavigationItem =
document.createElement('button');Ð               addClass(tabNavigationItem,
'tab-control');Ð               tabNavigationItem.setAttribute('data-tab-id',
tabId);Ð               tabNavigationItem.setAttribute('role', 'tab');Ð
                tabNavigationItem.setAttribute('aria-controls', tabId);Ð
                if (hasClass(tabs[j], 'active')) { selectedTabId = tabId; }Ð
                if (hasClass(tabs[j], 'disabled')) {Ð
addClass(tabNavigationItem, 'disabled');Ð               }Ð
tabNavigationItem.innerHTML = tabTitle;Ð
tabNavigation.appendChild(tabNavigationItem);Ð               var tabContent =
tabs[j].querySelector('.tab-content');Ð
tabContent.parentElement.setAttribute('id', tabId);Ð           }Ð
tabGroups[i].insertBefore(tabNavigation, tabGroups[i].firstChild);Ð
addClass(document.querySelector('[data-tab-id="' + selectedTabId + '"]'),
'active');Ð       }Ð       /* display the active tab and add the 'click'
event listeners */Ð       for (i = 0; i < tabGroups.length; i++) {Ð
tabNavigation = tabGroups[i].querySelectorAll(':scope > .tab-navigation .tab-
control');Ð           for (j = 0; j < tabNavigation.length; j++) {Ð
                tabId = tabNavigation[j].getAttribute('data-tab-id');Ð
                var tabPanel = document.getElementById(tabId);Ð
```

```
tabPanel.setAttribute('role', 'tabpanel');Ð
tabPanel.setAttribute('aria-labelledby', tabId);Ð
tabPanel.querySelector('.tab-title').className = 'hidden';Ð               if
(hasClass(tabNavigation[j], 'active')) {Ð
tabPanel.className = 'block';Ð
tabNavigation[j].setAttribute('aria-selected', 'true');Ð
tabNavigation[j].removeAttribute('tabindex');Ð               } else {Ð
                    tabPanel.className = 'hidden';Ð
tabNavigation[j].removeAttribute('aria-selected');Ð
tabNavigation[j].setAttribute('tabindex', '-1');Ð               }Ð
                tabNavigation[j].addEventListener('click', function(e) {Ð
                    var activeTab = e.target || e.srcElement;Ð
                    /* needed because when the tab contains HTML contents,
user can click */Ð                   /* on any of those elements instead of
their parent '<button>' element */Ð                   while
(activeTab.tagName.toLowerCase() !== 'button') {Ð
activeTab = activeTab.parentNode;Ð                   }Ð                   /*
get the full list of tabs through the parent of the active tab element */Ð
                    var tabNavigation = activeTab.parentNode.children;Ð
                    for (var k = 0; k < tabNavigation.length; k++) {Ð
                        var tabId = tabNavigation[k].getAttribute('data-tab-
id');Ð                        document.getElementById(tabId).className =
'hidden';Ð                        removeClass(tabNavigation[k], 'active');Ð
                        tabNavigation[k].removeAttribute('aria-selected');Ð
                        tabNavigation[k].setAttribute('tabindex', '-1');Ð
                    }Ð                   addClass(activeTab, 'active');Ð
                    activeTab.setAttribute('aria-selected', 'true');Ð
                    activeTab.removeAttribute('tabindex');Ð
var activeTabId = activeTab.getAttribute('data-tab-id');Ð
document.getElementById(activeTabId).class‌Name = 'block';Ð               });Ð
            }Ð           tabGroups[i].setAttribute('data-processed', 'true');Ð
        }Ð   })();Ð   (function createToggles() {Ð       var toggles =
document.querySelectorAll('.sf-toggle:not([data-processed=true])');Ð
for (var i = 0; i < toggles.length; i++) {Ð           var elementSelector =
toggles[i].getAttribute('data-toggle-selector');Ð           var element =
document.querySelector(elementSelector);Ð           addClass(element, 'sf-
toggle-content');Ð           if (toggles[i].hasAttribute('data-toggle-
initial') && toggles[i].getAttribute('data-toggle-initial') == 'display') {Ð
                addClass(toggles[i], 'sf-toggle-on');Ð
addClass(element, 'sf-toggle-visible');Ð           } else {Ð
addClass(toggles[i], 'sf-toggle-off');Ð               addClass(element, 'sf-
toggle-hidden');Ð           }Ð           addEventListener(toggles[i],
'click', function(e) {Ð               var toggle = e.currentTarget;Ð
                if (e.target.closest('a, span[data-clipboard-text], .sf-
toggle') !== toggle) {Ð                   return;Ð               }Ð
                e.preventDefault();Ð               if ('' !==
window.getSelection().toString()) {Ð                   /* Don't do anything
on text selection */Ð                   return;Ð               }Ð
                var element =
document.querySelector(toggle.getAttribute('data-toggle-selector'));Ð
                toggleClass(toggle, 'sf-toggle-on');Ð
toggleClass(toggle, 'sf-toggle-off');Ð               toggleClass(element, 'sf-
toggle-hidden');Ð               toggleClass(element, 'sf-toggle-visible');Ð
                /* the toggle doesn't change its contents when clicking on it
*/Ð               if (!toggle.hasAttribute('data-toggle-alt-content')) {Ð
                    return;Ð               }Ð               if (!
toggle.hasAttribute('data-toggle-original-content')) {Ð
toggle.setAttribute('data-toggle-original-content', toggle.innerHTML);Ð
                }Ð
```

```
                 Ð               var currentContent = toggle.innerHTML;Ð
                var originalContent = toggle.getAttribute('data-toggle-
original-content');Ð               var altContent = toggle.getAttribute('data-
toggle-alt-content');Ð               toggle.innerHTML = currentContent !==
altContent ? altContent : originalContent;Ð          });Ð
toggles[i].setAttribute('data-processed', 'true');Ð       }Ð   })();Ð
(function createFilters() {Ð       document.querySelectorAll('[data-filters]
[data-filter]').forEach(function (filter) {Ð           var filters =
filter.closest('[data-filters]'),Ð               type = 'choice',Ð
                name = filter.dataset.filter,Ð               ucName =
name.charAt(0).toUpperCase()+name.slice(1),Ð               list =
document.createElement('ul'),Ð               values =
filters.dataset['filter'+ucName] || filters.querySelectorAll('[data-
filter-'+name+']'),Ð               labels = {},Ð               defaults =
null,Ð               indexed = {},Ð               processed = {};Ð
if (typeof values === 'string') {Ð               type = 'level';Ð
                labels = values.split(',');Ð               values =
values.toLowerCase().split(',');Ð               defaults = values.length - 1;Ð
            }Ð           addClass(list, 'filter-list');Ð
addClass(list, 'filter-list-'+type);Ð           values.forEach(function
(value, i) {Ð               if (value instanceof HTMLElement) {Ð
                    value = value.dataset['filter'+ucName];Ð               }Ð
                if (value in processed) {Ð                   return;Ð
                }Ð               var option = document.createElement('li'),Ð
                    label = i in labels ? labels[i] : value,Ð
                    active = false,Ð                   matches;Ð
                if ('' === label) {Ð                   option.innerHTML =
'<em>(none)</em>';Ð               } else {Ð
option.innerText = label;Ð               }Ð
option.dataset.filter = value;Ð               option.setAttribute('title', 1
=== (matches = filters.querySelectorAll('[data-
filter-'+name+'="'+value+'"]').length) ? 'Matches 1 row' : 'Matches
'+matches+' rows');Ð               indexed[value] = i;Ð
list.appendChild(option);Ð               addEventListener(option, 'click',
function () {Ð                   if ('choice' === type) {Ð
                        filters.querySelectorAll('[data-
filter-'+name+']').forEach(function (row) {Ð                           if
(option.dataset.filter === row.dataset['filter'+ucName]) {Ð
                                toggleClass(row, 'filter-hidden-'+name);Ð
                            }Ð                       });Ð
                        toggleClass(option, 'active');Ð                   }
else if ('level' === type) {Ð                       if (i ===
this.parentNode.querySelectorAll('.active').length - 1) {Ð
                            return;Ð                       }Ð

this.parentNode.querySelectorAll('li').forEach(function (currentOption, j) {Ð
                            if (j <= i) {Ð
addClass(currentOption, 'active');Ð                               if (i ===
j) {Ð                                   addClass(currentOption, 'last-
active');Ð                                } else {Ð
                                    removeClass(currentOption, 'last-active');Ð
                                }Ð                           } else {Ð
                                removeClass(currentOption, 'active');Ð
                                removeClass(currentOption, 'last-active');Ð
                            }Ð                       });Ð
                        filters.querySelectorAll('[data-
filter-'+name+']').forEach(function (row) {Ð                           if (i
< indexed[row.dataset['filter'+ucName]]) {Ð
addClass(row, 'filter-hidden-'+name);Ð                           } else {Ð
                                removeClass(row, 'filter-hidden-'+name);Ð
```

```
                            }Ð                        });Ð                    }Ð
                 });Ð                if ('choice' === type) {Ð
                     active = null === defaults || 0 <=
defaults.indexOf(value);Ð                } else if ('level' === type) {Ð
                     active = i <= defaults;Ð                    if (active &&
i === defaults) {Ð                        addClass(option, 'last-active');Ð
                     }Ð                }Ð                if (active) {Ð
                     addClass(option, 'active');Ð                } else {Ð
                     filters.querySelectorAll('[data-
filter-'+name+'="'+value+'"]').forEach(function (row) {Ð
                         toggleClass(row, 'filter-hidden-'+name);Ð
                     });Ð                }Ð                processed[value] =
true;Ð           });Ð           if (1 < list.childNodes.length) {Ð
                 filter.appendChild(list);Ð
filter.dataset.filtered = '';Ð           }Ð       });Ð   })();Ð})();Ð*]]>*/Ð
```

vendor\symfony\var-dumper\Resources\js\htmlDescriptor.js

```
document.addEventListener('DOMContentLoaded', function() {Đ let prev = null;Đ
Array.from(document.getElementsByTagName('article')).reverse().forEach(functio
n (article) {Đ   const dedupId = article.dataset.dedupId;Đ   if (dedupId ===
prev) {Đ     article.getElementsByTagName('header')
[0].classList.add('hidden');Đ   }Đ   prev = dedupId;Đ });Đ});Đ
```

webpack.mix.js

```
const mix = require('laravel-mix');Ð*Ð
|-------------------------------------------------------------------------Ð|
Mix Asset ManagementÐ
|-------------------------------------------------------------------------Ð|Ð
| Mix provides a clean, fluent API for defining some Webpack build stepsÐ|
for your Laravel application. By default, we are compiling the SassÐ| file
for the application as well as bundling up all the JS files.Ð|Ð*/Ð
mix.js('resources/js/app.js', 'public/js')Ð   .sass('resources/sass/
app.scss', 'public/css')Ð   .sourceMaps();Ð
```

public\assets\frontend\fonts\glyphicons-halflings-regular-2.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/fonts/glyphicons-halflings-regular.woff was not found on this server. Ð Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request. Ð/body></html>Ð

public\assets\frontend\fonts\glyphicons-halflings-regular-3.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/fonts/glyphicons-halflings-regular.ttf was not found on this server. Ð Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request. Ð/body></html>Ð

public\assets\frontend\fonts\glyphicons-halflings-regular-4.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/fonts/glyphicons-halflings-regular.svg was not found on this server. Ð Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request. Ð/body></html>Ð

public\assets\frontend\fonts\glyphicons-halflings-regular.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/fonts/glyphicons-halflings-regular.eot was not found on this server. Ð Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request. Ð/body></html>Ð

public\assets\frontend\fonts\glyphicons-halflings-regulard41d.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/fonts/glyphicons-halflings-regular.eot was not found on this server. Ð Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request. Ð/body></html>Ð

public\assets\frontend\img\hr-spec.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/img/hr-spec.png was not found on this server.</p>Ðp>Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request.</p>Ð/body></html>Ð

public\assets\frontend\img\sky-bottom.html

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">Ðhtml><head>Ðtitle>404 Not Found</title>Ð/head><body>Ðh1>Not Found</h1>Ðp>The requested URL /themes/kada/html/img/sky-bottom.jpg was not found on this server.</p>Ðp>Additionally, a 404 Not FoundÐrror was encountered while trying to use an ErrorDocument to handle the request.</p>Ð/body></html>Ð

public\assets\js\plugins\codemirror\mode\apl\index.html


```
<!doctype html>Ðtitle>CodeMirror: APL mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="./apl.js"></script>Ðstyle>Ðä6öFTÖ—'&÷" ² &÷&FW#¢ ' , –ç6WB 6FVS² Ý   </
style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">APL</a>Ð </ul>Ð/div>Ðarticle>Ðh2>APL mode</h2>Ðform><textarea
id="code" name="code">Ð] Conway's game of life ÐÐ]ÐThis example was inspired by the
impressive demo atÐ] http://www.youtube.com/watch?v=a9xAKttWgP4ÐÐ]ÐCreate a matrix:Ð
#]     0 1#]ÐÐ]     1 1#]ÐÐ]     0 1cÐÐature !• (3 3 #t #s 9) "  1 2 3 4 7   #] Original
creature from demoÐreature !• (3 3 #t #s 9)¯"  1 3 6 7 8  ÐÐ]ÐPlaceÐ]ÐGlider the creature
on a larger board, near the centreÐboard !• ¯1 "– ¯2 #= 5 7 !' ÐÐ]ÐNextÐ]ÐA function to
move from one generation to the nextÐlife !• {"(/ 1 #u "' 3 4 = ",+/ +#? 1 0 ¯1 " ."– 1 0 ¯
"ÐÐ]ÐuÇÐCompute n-th generation and format it as#ÐÐ]ÐcharacterÐmatrixÐ]ÐxÐ !• {' #'[(life
#c #u) boardÐÐ]ÐÐ]ÐÐ]
```

public\assets\js\plugins\codemirror\mode\asterisk\index.html


```
<!doctype html>Ðtitle>CodeMirror: Asterisk dialplan mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="asterisk.js"></script>Ðstyle>Ð
      .CodeMirror {border: 1px solid #999;}Ð     .cm-s-default span.cm-arrow
{ color: red; }Ð   </style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Asterisk dialplan</a>Ð </ul>Ð/div>Ð
<article>Ðh2>Asterisk dialplan mode</h2>Ðform><textarea id="code" name="code">Ð
; extensions.conf - the Asterisk dial planÐÐ[general]ÐÐ If static is set to
no, or omitted, then the pbx_config will rewriteÐ this file when extensions
are modified.  Remember that all commentsÐ made in the file will be lost when
that happens.Ðstatic=yesÐinclude "/etc/asterisk/additional_general.confÐ
[iaxprovider]Ðswitch => IAX2/user:[key]@myserver/mycontextÐ[dynamic]Ðexec /usr/
bin/dynamic-peers.plÐ[trunkint]ÐÐ International long distance through trunkÐÐ
exten => _9011.,1,Macro(dundi-e164,${EXTEN:4})Ðexten =>
_9011.,n,Dial(${GLOBAL(TRUNK)}/${FILTER(0-9,${EXTEN:${GLOBAL(TRUNKMSD)}})})Ð
[local]ÐÐ Master context for local, toll-free, and iaxtel calls onlyÐÐ
ignorepat => 9Ðinclude => defaultÐ[demo]Ðinclude => stdextenÐÐ We start with
what to do when a call first comes in.ÐÐexten => s,1,Wait(1)™“² v –B   6V6öæBÂ
just for funÐsame  => n,Answer™“²  ç7vW" F†R Æ–æ3ame  =>
n,Set(TIMEOUT(digit)=5)“² 6WB F–v–B F–ÖV÷WB Fò R 6V6öæGÐsame  =>
n,Set(TIMEOUT(response)=10)“² 6WB &W7 öç6R F–ÖV÷WB Fò    6V6öæGÐsame  =>
n(restart),BackGround(demo-congrats)“²  Æ ’   6öæw& GVÆ F÷'’ ÖW76 vÐsame  =>
n(instruct),BackGround(demo-instruct)“²  Æ ’ 6öÖR –ç7G'V7F–öçÐsame  =>
n,WaitExten™“² v –B f÷"  â W‡FVç6–öâ Fò &R F– ÆVÐÐxten => 2,1,BackGround(demo-
moreinfo)“² v–fR 6öÖR Ö÷&R –æf÷&Ö F–öâÐexten => 2,n,Goto(s,instruct)Ðexten =>
3,1,Set(LANGUAGE()=fr)™; Set language to frenchÐexten => 3,n,Goto(s,restart)™;
Start with the congratulationsÐexten => 1000,1,Goto(default,s,1)ÐÐ We also
create an example user, 1234, who is on the console and hasÐ voicemail, etc.ÐÐ
exten => 1234,1,Playback(transfer,skip)™; "Please hold while..."™“² †'WB 6¶–  –b
channel is not up)Ðexten => 1234,n,Gosub(${EXTEN},stdexten(${GLOBAL(CONSOLE)}))Ð
exten => 1234,n,Goto(default,s,1)™; exited VoicemailÐexten =>
1235,1,Voicemail(1234,u)™; Right to voicemailÐexten => 1236,1,Dial(Console/
dsp)™; Ring foreverÐexten => 1236,n,Voicemail(1234,b)™; Unless busyÐÐ # for when
they're done with the demoÐÐexten => #,1,Playback(demo-thanks)“² %F† æ·2 f÷"
trying the demo"Ðexten => #,n,Hangup™“² † ær F†VÒ WÐÐ A timeout and "invalid
extension rule"ÐÐexten => t,1,Goto(#,1)™“² –b F†W’ F ¶R Föò ÆöærÂ v–fR Wexten
=> i,1,Playback(invalid)™; "That's not valid, try againÐÐ Create an
extension, 500, for dialing theÐ Asterisk demo.ÐÐexten => 500,1,Playback(demo-
abouttotry); Let them know what's going onÐexten => 500,n,Dial(IAX2/
guest@pbx.digium.com/s@default)“² 6 ÆÂ F†R  7FW&–6² FVÖÐexten =>
500,n,Playback(demo-nogo)“² 6÷VÆFâwB 6öææV7B Fò F†R FVÖò 6–FÐexten =>
500,n,Goto(s,6)™; Return to the start over messageÐÐ Create an extension,
600, for evaluating echo latency.ÐÐexten => 600,1,Playback(demo-echotest)“² ÆWB
them know what's going onÐexten => 600,n,Echo™“² Fò F†R V6†ò FWÐexten =>
600,n,Playback(demo-echodone)“² ÆWB F†VÒ ¶æ÷r –Bw2 ÷fWexten =>
600,n,Goto(s,6)™; Start overÐÐ•–÷R 6 â W6R F†R Ö 7&ò   vR Fò –çFW&6öÒ
individual userÐexten => 76245,1,Macro(page,SIP/Grandstream1)Ð or if your
peernames are the same as extensionsÐexten => _7XXX,1,Macro(page,SIP/${EXTEN})ÐÐ
;Ð System Wide Page at extension 7999ÐÐexten =>
7999,1,Set(TIMEOUT(absolute)=60)Ðexten => 7999,2,Page(Local/
Grandstream1@page&Local/Xlite1@page&Local/1234@page/n,d)Ð Give voicemail at
extension 8500ÐÐexten => 8500,1,VoicemailMainÐexten => 8500,n,Goto(s,6)Ð   </
textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
```

```
                                                                    mode: "text/
x-asterisk",Ð       matchBrackets: true,Ð       lineNumber: trueÐ     });Ð
</script>Ð   <p><strong>MIME types defined:</strong> <code>text/x-asterisk</
code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\clike\index.html


```
<!doctype html>Ðtitle>CodeMirror: C-like mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðlink
rel="stylesheet" href="../../addon/hint/show-hint.css">Ðscript src="../../
addon/hint/show-hint.js"></script>Ðscript src="clike.js"></script>Ð
<style>.CodeMirror {border: 2px inset #dee;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">C-like</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>C-like mode</h2>Ðdiv><textarea id="c-code">Ð/* C demo
code */Ðinclude <zmq.h>Ðinclude <pthread.h>Ðinclude <semaphore.h>Ðinclude
<time.h>Ðinclude <stdio.h>Ðinclude <fcntl.h>Ðinclude <malloc.h>Ðtypedef struct
{Ð void* arg_socket;Ð zmq_msg_t* arg_msg;Ð char* arg_string;Ð unsigned long
arg_len;Ð int arg_int, arg_command;Ð int signal_fd;Ð int pad;Ð void* context;Ð
  sem_t sem;Ð} acl_zmq_context;Ðdefine p(X) (context->arg_##X)Ðvoid*
zmq_thread(void* context_pointer) {Ð acl_zmq_context* context =
(acl_zmq_context*)context_pointer;Ð char ok = 'K', err = 'X';Ð int res;Ð
while (1) {Ð   while ((res = sem_wait(&amp;context->sem)) == EINTR);Ð   if
(res) {write(context->signal_fd, &amp;err, 1); goto cleanup;}Ð
switch(p(command)) {Ð   case 0: goto cleanup;Ð   case 1: p(socket) =
zmq_socket(context->context, p(int)); break;Ð   case 2: p(int) =
zmq_close(p(socket)); break;Ð   case 3: p(int) = zmq_bind(p(socket),
p(string)); break;Ð   case 4: p(int) = zmq_connect(p(socket), p(string));
break;Ð   case 5: p(int) = zmq_getsockopt(p(socket), p(int),
(void*)p(string), &amp;p(len)); break;Ð   case 6: p(int) =
zmq_setsockopt(p(socket), p(int), (void*)p(string), p(len)); break;Ð   case
7: p(int) = zmq_send(p(socket), p(msg), p(int)); break;Ð   case 8: p(int) =
zmq_recv(p(socket), p(msg), p(int)); break;Ð   case 9: p(int) =
zmq_poll(p(socket), p(int), p(len)); break;Ð   }Ð   p(command) = errno;Ð
write(context->signal_fd, &amp;ok, 1);Ð }Ðcleanup:Ð close(context->signal_fd);Ð
  free(context_pointer);Ð return 0;ÐÐvoid* zmq_thread_init(void* zmq_context,
int signal_fd) {Ð acl_zmq_context* context = malloc(sizeof(acl_zmq_context));Ð
  pthread_t thread;Ð context->context = zmq_context;Ð context->signal_fd =
signal_fd;Ð sem_init(&amp;context->sem, 1, 0);Ð pthread_create(&amp;thread,
0, &amp;zmq_thread, context);Ð pthread_detach(thread);Ð return context;ÐÐ/
textarea></div>Ðh2>C++ example</h2>Ðdiv><textarea id="cpp-code">Ðinclude
<iostream>Ðinclude "mystuff/util.h"Ðnamespace {Ðenum Enum {Ð VAL1, VAL2, VAL3Ð};Ð
char32_t unicode_string = U"\U0010FFFF";Ðstring raw_string = R"delim(anything Ð
you want)delim";Ðint Helper(const MyType& param) {Ð return 0;ÐÐ} // namespaceÐ
class ForwardDec;Ðtemplate <class T, class V>Ðclass Class : public BaseClass {Ð
const MyType<T, V> member_;Ðpublic:Ð const MyType<T, V>& Method() const {Ð
return member_;Ð }Ð void Method2(MyType<T, V>* value);ÐÐtemplate <class T,
class V>Ðvoid Class::Method2(MyType<T, V>* value) {Ð std::out << 1 >> method();Ð
  value->Method3(member_);Ð member_ = value;ÐÐ/textarea></div>Ðh2>Java
example</h2>Ðdiv><textarea id="java-code">Ðimport com.demo.util.MyType;Ðimport
com.demo.util.MyInterface;Ðpublic enum Enum {Ð VAL1, VAL2, VAL3Ð}ÐÐpublic class
Class<T, V> implements MyInterface {Ð public static final MyType<T, V> member;Ð
  Ð private class InnerClass {Ð   public int zero() {Ð     return 0;Ð   }Ð }Ð
@OverrideÐ public MyType method() {Ð   return member;Ð }Ð public void
method2(MyType<T, V> value) {Ð   method();Ð   value.method3();Ð   member =
value;Ð }ÐÐ/textarea></div>Ðh2>Scala example</h2>Ðdiv><textarea id="scala-
code">Ðbject FilterTest extends App {Ð def filter(xs: List[Int], threshold:
Int) = {Ð   def process(ys: List[Int]): List[Int] =Ð     if (ys.isEmpty) ysÐ
      else if (ys.head < threshold) ys.head :: process(ys.tail)Ð     else
process(ys.tail)Ð   process(xs)Ð }Ð println(filter(List(1, 9, 2, 8, 3, 7, 4),
5))Ð
```

```
   }ÐÐ/textarea></div>Ð   <script>Ð     var cEditor =
CodeMirror.fromTextArea(document.getElementById("c-code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-csrc"Ð
      });Ð     var cppEditor =
CodeMirror.fromTextArea(document.getElementById("cpp-code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-c++src"Ð
      });Ð     var javaEditor =
CodeMirror.fromTextArea(document.getElementById("java-code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-java"Ð
      });Ð     var scalaEditor =
CodeMirror.fromTextArea(document.getElementById("scala-code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-scala"Ð
      });Ð     var mac = CodeMirror.keyMap.default ==
CodeMirror.keyMap.macDefault;Ð     CodeMirror.keyMap.default[(mac ? "Cmd" :
"Ctrl") + "-Space"] = "autocomplete";Ð   </script>ÐÐ   <p>Simple mode that
tries to handle C-like languages as well as itÐ   can. Takes two
configuration parameters: <code>keywords</code>, anÐ   object whose property
names are the keywords in the language,Ð   and <code>useCPP</code>, which
determines whether C preprocessorÐ   directives are recognized.</p>ÐÐ
<p><strong>MIME types defined:</strong> <code>text/x-csrc</code>Ð   (C),
<code>text/x-c++src</code> (C++), <code>text/x-java</code>Ð   (Java),
<code>text/x-csharp</code> (C#),Ð   <code>text/x-scala</code> (Scala),
<code>text/x-vertex</code>Ð   and <code>x-shader/x-fragment</code> (shader
programs).</p>ÐÐ/article>Ð
```

public\assets\js\plugins\codemirror\mode\clike\scala.html

```
<!doctype html>Ðtitle>CodeMirror: Scala mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
ambiance.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="../../addon/edit/matchbrackets.js"></script>Ðscript src="clike.js"></
script>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Scala</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Scala mode</h2>Ðform>Ðtextarea
id="code" name="code">Ð /*
__                                                  *\Ð **    ________
___    / /  ___      Scala API                          **Ð **    / __/ __//
_ | / /  / _ |    (c) 2003-2011, LAMP/EPFL             **Ð **  __\ \/ /__/ __
|/ /__/ __ |    http://scala-lang.org/               **Ð ** /____/\___/_/ |_/
____/_/ | |                                           **Ð
**                          |/                                                **Ð
\*                                                                            */Ð
package scala.collectionÐ import generic._Ð import mutable.{ Builder,
ListBuffer }Ð import annotation.{tailrec, migration, bridge}Ð import
annotation.unchecked.{ uncheckedVariance => uV }Ð import parallel.ParIterableÐ
  /** A template trait for traversable collections of type `Traversable[A]`.Ð
   *  Ð  *  $traversableInfoÐ  *  @define mutabilityÐ  *  @define
traversableInfoÐ  *  This is a base trait of all kinds of $mutability Scala
collections. ItÐ  *  implements the behavior common to all collections, in
terms of a methodÐ  *  `foreach` with signature:Ð  * {{{Ð  *     def
foreach[U](f: Elem => U): UnitÐ  * }}}Ð  *  Collection classes mixing in this
trait provide a concrete Ð  *  `foreach` method which traverses all theÐ  *
elements contained in the collection, applying a given function to each.Ð  *
They also need to provide a method `newBuilder`Ð  *  which creates a builder
for collections of the same kind.Ð  *  Ð  *  A traversable class might or
might not have two properties: strictnessÐ  *  and orderedness. Neither is
represented as a type.Ð  *  Ð  *  The instances of a strict collection class
have all their elementsÐ  *  computed before they can be used as values. By
contrast, instances ofÐ  *  a non-strict collection class may defer
computation of some of theirÐ  *  elements until after the instance is
available as a value.Ð  *  A typical example of a non-strict collection class
is aÐ  *  <a href="../immutable/Stream.html" target="ContentFrame">Ð  *
`scala.collection.immutable.Stream`</a>.Ð  *  A more general class of
examples are `TraversableViews`.Ð  *  Ð  *  If a collection is an instance of
an ordered collection class, traversingÐ  *  its elements with `foreach` will
always visit elements in theÐ  *  same order, even for different runs of the
program. If the class is notÐ  *  ordered, `foreach` can visit elements in
different orders forÐ  *  different runs (but it will keep the same order in
the same run).'Ð  * Ð  *  A typical example of a collection class which is
not ordered is aÐ  *  `HashMap` of objects. The traversal order for hash maps
willÐ  *  depend on the hash codes of its elements, and these hash codes mightÐ
   *  differ from one run to the next. By contrast, a `LinkedHashMap`Ð  *  is
ordered because it's `foreach` method visits elements in theÐ  *  order they
were inserted into the `HashMap`.Ð  *Ð  *  @author Martin OderskyÐ  *
@version 2.8Ð  *  @since   2.8Ð  *  @tparam A    the element type of the
collectionÐ  *  @tparam Repr the type of the actual collection containing the
elements.Ð  *Ð  *  @define Coll TraversableÐ  *  @define coll traversable
collectionÐ  */Ð trait TraversableLike[+A, +Repr] extends HasNewBuilder[A,
Repr] Ð                                     with FilterMonadic[A, Repr]Ð
                                      with TraversableOnce[A]Ð
                                      with GenTraversableLike[A, Repr]Ð
                                      with Parallelizable[A, ParIterable[A]]Ð
```

{Ð self =>Ð import Traversable.breaks._Ð /** The type implementing this traversable */Ð protected type Self = ReprÐ /** The collection of type $coll underlying this `TraversableLike` object.Ð * By default this is implemented as the `TraversableLike` object itself,Ð * but this can be overridden.Ð */Ð def repr: Repr = this.asInstanceOf[Repr]Ð /** The underlying collection seen as an instance of `$Coll`.Ð * By default this is implemented as the current collection object itself,Ð * but this can be overridden.Ð */Ð protected[this] def thisCollection: Traversable[A] = this.asInstanceOf[Traversable[A]]Ð /** A conversion from collections of type `Repr` to `$Coll` objects.Ð * By default this is implemented as just a cast, but this can be overridden.Ð */Ð protected[this] def toCollection(repr: Repr): Traversable[A] = repr.asInstanceOf[Traversable[A]]Ð /** Creates a new builder for this collection type.Ð */Ð protected[this] def newBuilder: Builder[A, Repr]Ð protected[this] def parCombiner = ParIterable.newCombiner[A]Ð /** Applies a function `f` to all elements of this $coll.Ð * Ð * Note: this method underlies the implementation of most other bulk operations.Ð * It's important to implement this method in an efficient way.Ð * Ð *Ð * @param f the function that is applied for its side-effect to every element.Ð * The result of function `f` is discarded.Ð * Ð * @tparam U the type parameter describing the result of function `f`. Ð * This result will always be ignored. Typically `U` is `Unit`,Ð * but this is not necessary.Ð *Ð * @usecase def foreach(f: A => Unit): UnitÐ */Ð def foreach[U](f: A => U): UnitÐ /** Tests whether this $coll is empty.Ð *Ð * @return `true` if the $coll contain no elements, `false` otherwise.Ð */Ð def isEmpty: Boolean = {Ð var result = trueÐ breakable {Ð for (x <- this) {Ð result = falseÐ breakÐ }Ð }Ð resultÐ }Ð /** Tests whether this $coll is known to have a finite size.Ð * All strict collections are known to have finite size. For a non-strict collectionÐ * such as `Stream`, the predicate returns `true` if all elements have been computed.Ð * It returns `false` if the stream is not yet evaluated to the end.Ð *Ð * Note: many collection methods will not work on collections of infinite sizes. Ð *Ð * @return `true` if this collection is known to have finite size, `false` otherwise.Ð */Ð def hasDefiniteSize = trueÐ def ++[B >: A, That](that: GenTraversableOnce[B])(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð val b = bf(repr)Ð if (that.isInstanceOf[IndexedSeqLike[_, _]]) b.sizeHint(this, that.seq.size)Ð b ++= thisCollectionÐ b ++= that.seqÐ b.resultÐ }Ð @bridgeÐ def ++[B >: A, That](that: TraversableOnce[B])(implicit bf: CanBuildFrom[Repr, B, That]): That =Ð ++(that: GenTraversableOnce[B])(bf)Ð /** Concatenates this $coll with the elements of a traversable collection.Ð * It differs from ++ in that the right operand determines the type of theÐ * resulting collection rather than the left one.Ð * Ð * @param that the traversable to append.Ð * @tparam B the element type of the returned collection. Ð * @tparam That $thatinfoÐ * @param bf $bfinfoÐ * @return a new collection of type `That` which contains all elementsÐ * of this $coll followed by all elements of `that`.Ð * Ð * @usecase def ++:[B](that: TraversableOnce[B]): $Coll[B]Ð * Ð * @return a new $coll which contains all elements of this $collÐ * followed by all elements of `that`.Ð */Ð def ++:[B >: A, That](that: TraversableOnce[B])(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð val b = bf(repr)Ð if (that.isInstanceOf[IndexedSeqLike[_, _]]) b.sizeHint(this, that.size)Ð b ++= thatÐ b ++= thisCollectionÐ b.resultÐ }Ð /** This overload exists because: for the implementation of ++: we should reuseÐ * that of ++ because many collections override it with more efficient versions.Ð * Since TraversableOnce has no '++' method, we have to implement that directly,Ð

```
              *  but Traversable and down can use the overload.Ð    */Ð   def
++:[B >: A, That](that: Traversable[B])(implicit bf: CanBuildFrom[Repr, B,
That]): That =Ð     (that ++ seq)(breakOut)Ð   def map[B, That](f: A => B)
(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð     val b = bf(repr)Ð
      b.sizeHint(this) Ð     for (x <- this) b += f(x)Ð     b.resultÐ   }Ð
def flatMap[B, That](f: A => GenTraversableOnce[B])(implicit bf:
CanBuildFrom[Repr, B, That]): That = {Ð     val b = bf(repr)Ð     for (x <-
this) b ++= f(x).seqÐ     b.resultÐ   }Ð   /** Selects all elements of this
$coll which satisfy a predicate.Ð    *Ð    *  @param p     the predicate used
to test elements.Ð    *  @return      a new $coll consisting of all elements
of this $coll that satisfy the givenÐ    *               predicate `p`. The
order of the elements is preserved.Ð    */Ð   def filter(p: A => Boolean):
Repr = {Ð     val b = newBuilderÐ     for (x <- this) Ð       if (p(x)) b += xÐ
      b.resultÐ   }Ð   /** Selects all elements of this $coll which do not
satisfy a predicate.Ð    *Ð    *  @param p     the predicate used to test
elements.Ð    *  @return      a new $coll consisting of all elements of this
$coll that do not satisfy the givenÐ    *               predicate `p`. The
order of the elements is preserved.Ð    */Ð   def filterNot(p: A => Boolean):
Repr = filter(!p(_))Ð   def collect[B, That](pf: PartialFunction[A, B])
(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð     val b = bf(repr)Ð
      for (x <- this) if (pf.isDefinedAt(x)) b += pf(x)Ð     b.resultÐ   }Ð
    /** Builds a new collection by applying an option-valued function to allÐ
     *  elements of this $coll on which the function is defined.Ð    *Ð    *
@param f      the option-valued function which filters and maps the $coll.Ð
     *  @tparam B     the element type of the returned collection.Ð    *
@tparam That  $thatinfoÐ    *  @param bf     $bfinfoÐ    *  @return       a
new collection of type `That` resulting from applying the option-valued
functionÐ    *               `f` to each element and collecting all defined
results.Ð    *               The order of the elements is preserved.Ð    *Ð
     *  @usecase def filterMap[B](f: A => Option[B]): $Coll[B]Ð    *  Ð    *
@param pf     the partial function which filters and maps the $coll.Ð    *
@return       a new $coll resulting from applying the given option-valued
functionÐ    *               `f` to each element and collecting all defined
results.Ð    *               The order of the elements is preserved.Ð   def
filterMap[B, That](f: A => Option[B])(implicit bf: CanBuildFrom[Repr, B,
That]): That = {Ð     val b = bf(repr)Ð     for (x <- this) Ð       f(x)
match {Ð         case Some(y) => b += yÐ         case _ =>Ð       }Ð
b.resultÐ   }Ð    */Ð   /** Partitions this $coll in two ${coll}s according
to a predicate.Ð    *Ð    *  @param p the predicate on which to partition.Ð
     *  @return  a pair of ${coll}s: the first $coll consists of all elements
that Ð    *           satisfy the predicate `p` and the second $coll consists
of all elementsÐ    *           that don't. The relative order of the
elements in the resulting ${coll}sÐ    *           is the same as in the
original $coll.Ð    */Ð   def partition(p: A => Boolean): (Repr, Repr) = {Ð
      val l, r = newBuilderÐ     for (x <- this) (if (p(x)) l else r) += xÐ
      (l.result, r.result)Ð   }Ð   def groupBy[K](f: A => K):
immutable.Map[K, Repr] = {Ð     val m = mutable.Map.empty[K, Builder[A, Repr]]Ð
      for (elem <- this) {Ð       val key = f(elem)Ð       val bldr =
m.getOrElseUpdate(key, newBuilder)Ð       bldr += elemÐ     }Ð     val b =
immutable.Map.newBuilder[K, Repr]Ð     for ((k, v) <- m)Ð       b += ((k,
v.result))Ð     b.resultÐ   }Ð   /** Tests whether a predicate holds for all
elements of this $coll.Ð    *Ð    *  $mayNotTerminateInfÐ    *Ð    *
@param   p     the predicate used to test elements.Ð    *  @return
`true` if the given predicate `p` holds for all elementsÐ
*                 of this $coll, otherwise `false`.Ð    */Ð   def forall(p: A
=> Boolean): Boolean = {Ð     var result = trueÐ     breakable {Ð       for
(x <- this)Ð         if (!p(x)) { result = false; break }Ð     }Ð     resultÐ
    }Ð   /** Tests whether a predicate holds for some of the elements of this
$coll.Ð    *Ð    *  $mayNotTerminateInfÐ    *Ð    *  @param   p     the
predicate used to test elements.Ð
```

```
                                    *  @return        `true` if the given
predicate `p` holds for some of theÐ    *                 elements of this
$coll, otherwise `false`.Ð    */Ð   def exists(p: A => Boolean): Boolean = {Ð
      var result = falseÐ     breakable {Ð       for (x <- this)Ð         if
(p(x)) { result = true; break }Ð     }Ð     resultÐ   }Ð   /** Finds the
first element of the $coll satisfying a predicate, if any.Ð    * Ð    *
$mayNotTerminateInfÐ    *  $orderDependentÐ    *Ð    *  @param p    the
predicate used to test elements.Ð    *  @return     an option value
containing the first element in the $collÐ    *              that satisfies
`p`, or `None` if none exists.Ð    */Ð   def find(p: A => Boolean): Option[A]
= {Ð     var result: Option[A] = NoneÐ     breakable {Ð       for (x <- this)Ð
          if (p(x)) { result = Some(x); break }Ð     }Ð     resultÐ   }Ð
def scan[B >: A, That](z: B)(op: (B, B) => B)(implicit cbf:
CanBuildFrom[Repr, B, That]): That = scanLeft(z)(op)Ð   def scanLeft[B, That]
(z: B)(op: (B, A) => B)(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð
      val b = bf(repr)Ð     b.sizeHint(this, 1)Ð     var acc = zÐ     b += accÐ
      for (x <- this) { acc = op(acc, x); b += acc }Ð     b.resultÐ   }Ð
@migration(2, 9,Ð     "This scanRight definition has changed in 2.9.\n" +Ð
      "The previous behavior can be reproduced with scanRight.reverse."Ð   )Ð
    def scanRight[B, That](z: B)(op: (A, B) => B)(implicit bf:
CanBuildFrom[Repr, B, That]): That = {Ð     var scanned = List(z)Ð     var
acc = zÐ     for (x <- reversed) {Ð       acc = op(x, acc)Ð       scanned ::=
accÐ     }Ð     val b = bf(repr)Ð     for (elem <- scanned) b += elemÐ
b.resultÐ   }Ð   /** Selects the first element of this $coll.Ð    *
$orderDependentÐ    *  @return  the first element of this $coll.Ð    *
@throws `NoSuchElementException` if the $coll is empty.Ð    */Ð   def head: A
= {Ð     var result: () => A = () => throw new NoSuchElementExceptionÐ
breakable {Ð       for (x <- this) {Ð         result = () => xÐ         breakÐ
        }Ð     }Ð     result()Ð   }Ð   /** Optionally selects the first
element.Ð    *  $orderDependentÐ    *  @return  the first element of this
$coll if it is nonempty, `None` if it is empty.Ð    */Ð   def headOption:
Option[A] = if (isEmpty) None else Some(head)Ð   /** Selects all elements
except the first.Ð    *  $orderDependentÐ    *  @return  a $coll consisting
of all elements of this $collÐ    *           except the first one.Ð    *
@throws `UnsupportedOperationException` if the $coll is empty.Ð    */ Ð
override def tail: Repr = {Ð     if (isEmpty) throw new
UnsupportedOperationException("empty.tail")Ð     drop(1)Ð   }Ð   /** Selects
the last element.Ð     * $orderDependentÐ     * @return The last element of
this $coll.Ð     * @throws NoSuchElementException If the $coll is empty.Ð
*/Ð   def last: A = {Ð     var lst = headÐ     for (x <- this)Ð       lst = xÐ
      lstÐ   }Ð   /** Optionally selects the last element.Ð    *
$orderDependentÐ    *  @return  the last element of this $coll$ if it is
nonempty, `None` if it is empty.Ð    */Ð   def lastOption: Option[A] = if
(isEmpty) None else Some(last)Ð   /** Selects all elements except the last.Ð
     *  $orderDependentÐ    *  @return  a $coll consisting of all elements of
this $collÐ    *           except the last one.Ð    *  @throws
`UnsupportedOperationException` if the $coll is empty.Ð    */Ð   def init:
Repr = {Ð     if (isEmpty) throw new
UnsupportedOperationException("empty.init")Ð     var lst = headÐ     var
follow = falseÐ     val b = newBuilderÐ     b.sizeHint(this, -1)Ð     for (x
<- this.seq) {Ð       if (follow) b += lstÐ       else follow = trueÐ
lst = xÐ     }Ð     b.resultÐ   }Ð   def take(n: Int): Repr = slice(0, n)Ð
def drop(n: Int): Repr = Ð     if (n <= 0) {Ð       val b = newBuilderÐ
b.sizeHint(this)Ð       b ++= thisCollection resultÐ     }Ð     else
sliceWithKnownDelta(n, Int.MaxValue, -n)Ð   def slice(from: Int, until: Int):
Repr = sliceWithKnownBound(math.max(from, 0), until)Ð   // Precondition: from
>= 0, until > 0, builder already configured for building.Ð   private[this]
def sliceInternal(from: Int, until: Int, b: Builder[A, Repr]): Repr = {Ð
var i = 0Ð     breakable {Ð       for (x <- this.seq) {Ð         if (i >=
from) b += xÐ
```

```
                    i += 1Ð         if (i >= until) breakÐ       }Ð     }Ð
      b.resultÐ   }Ð   // Precondition: from >= 0Ð   private[scala] def
sliceWithKnownDelta(from: Int, until: Int, delta: Int): Repr = {Ð     val b =
newBuilderÐ     if (until <= from) b.resultÐ     else {Ð
b.sizeHint(this, delta)Ð       sliceInternal(from, until, b)Ð     }Ð   }Ð
    // Precondition: from >= 0Ð   private[scala] def
sliceWithKnownBound(from: Int, until: Int): Repr = {Ð     val b = newBuilderÐ
      if (until <= from) b.resultÐ     else {Ð       b.sizeHintBounded(until
- from, this)      Ð       sliceInternal(from, until, b)Ð     }Ð   }Ð   def
takeWhile(p: A => Boolean): Repr = {Ð     val b = newBuilderÐ     breakable {Ð
        for (x <- this) {Ð         if (!p(x)) breakÐ         b += xÐ       }Ð
      }Ð     b.resultÐ   }Ð   def dropWhile(p: A => Boolean): Repr = {Ð
val b = newBuilderÐ     var go = falseÐ     for (x <- this) {Ð       if (!
p(x)) go = trueÐ       if (go) b += xÐ     }Ð     b.resultÐ   }Ð   def
span(p: A => Boolean): (Repr, Repr) = {Ð     val l, r = newBuilderÐ     var
toLeft = trueÐ     for (x <- this) {Ð       toLeft = toLeft && p(x)Ð
(if (toLeft) l else r) += xÐ     }Ð     (l.result, r.result)Ð   }Ð   def
splitAt(n: Int): (Repr, Repr) = {Ð     val l, r = newBuilderÐ
l.sizeHintBounded(n, this)Ð     if (n >= 0) r.sizeHint(this, -n)Ð     var i =
0Ð     for (x <- this) {Ð       (if (i < n) l else r) += xÐ       i += 1Ð
      }Ð     (l.result, r.result)Ð   }Ð   /** Iterates over the tails of this
$coll. The first value will be thisÐ    *  $coll and the final one will be an
empty $coll, with the interveningÐ    *  values the results of successive
applications of `tail`.Ð    *Ð    *  @return   an iterator over all the tails
of this $collÐ    *  @example  `List(1,2,3).tails = Iterator(List(1,2,3),
List(2,3), List(3), Nil)`Ð    */  Ð   def tails: Iterator[Repr] =
iterateUntilEmpty(_.tail)Ð   /** Iterates over the inits of this $coll. The
first value will be thisÐ    *  $coll and the final one will be an empty
$coll, with the interveningÐ    *  values the results of successive
applications of `init`.Ð    *Ð    *  @return  an iterator over all the inits
of this $collÐ    *  @example  `List(1,2,3).inits = Iterator(List(1,2,3),
List(1,2), List(1), Nil)`Ð    */Ð   def inits: Iterator[Repr] =
iterateUntilEmpty(_.init)Ð   /** Copies elements of this $coll to an array.Ð
     *  Fills the given array `xs` with at most `len` elements ofÐ    *  this
$coll, starting at position `start`.Ð    *  Copying will stop once either the
end of the current $coll is reached,Ð    *  or the end of the array is
reached, or `len` elements have been copied.Ð    *Ð    *  $willNotTerminateInfÐ
     * Ð    *  @param  xs     the array to fill.Ð    *  @param  start  the
starting index.Ð    *  @param  len    the maximal number of elements to copy.Ð
     *  @tparam B      the type of the elements of the array. Ð    * Ð    *Ð
     *  @usecase def copyToArray(xs: Array[A], start: Int, len: Int): UnitÐ
     */Ð   def copyToArray[B >: A](xs: Array[B], start: Int, len: Int) {Ð
var i = startÐ     val end = (start + len) min xs.lengthÐ     breakable {Ð
        for (x <- this) {Ð         if (i >= end) breakÐ         xs(i) = xÐ
          i += 1Ð       }Ð     }Ð   }Ð   def toTraversable: Traversable[A] =
thisCollectionÐ   def toIterator: Iterator[A] = toStream.iteratorÐ   def
toStream: Stream[A] = toBuffer.toStreamÐ   /** Converts this $coll to a
string.Ð    *Ð    *  @return   a string representation of this collection. By
default thisÐ    *            string consists of the `stringPrefix` of this
$coll,Ð    *            followed by all elements separated by commas and
enclosed in parentheses.Ð    */Ð   override def toString =
mkString(stringPrefix + "(", ", ", ")")Ð   /** Defines the prefix of this
object's `toString` representation.Ð    *Ð    *  @return  a string
representation which starts the result of `toString`Ð    *            applied
to this $coll. By default the string prefix is theÐ    *            simple
name of the collection class $coll.Ð    */Ð   def stringPrefix : String = {Ð
      var string = repr.asInstanceOf[AnyRef].getClass.getNameÐ     val idx1 =
string.lastIndexOf('.' : Int)Ð     if (idx1 != -1) string =
string.substring(idx1 + 1)Ð     val idx2 = string.indexOf('$')Ð     if (idx2 !
= -1) string = string.substring(0, idx2)Ð
```

stringÐ }Ð /** Creates a non-strict view of this $coll.Ð * Ð * @return a non-strict view of this $coll.Ð */Ð def view = new TraversableView[A, Repr] {Ð protected lazy val underlying = self.reprÐ override def foreach[U](f: A => U) = self foreach fÐ }Ð /** Creates a non-strict view of a slice of this $coll.Ð *Ð * Note: the difference between `view` and `slice` is that `view` producesÐ * a view of the current $coll, whereas `slice` produces a new $coll.Ð * Ð * Note: `view(from, to)` is equivalent to `view.slice(from, to)`Ð * $orderDependentÐ * Ð * @param from the index of the first element of the viewÐ * @param until the index of the element following the viewÐ * @return a non-strict view of a slice of this $coll, starting at index `from`Ð * and extending up to (but not including) index `until`.Ð */Ð def view(from: Int, until: Int): TraversableView[A, Repr] = view.slice(from, until)Ð /** Creates a non-strict filter of this $coll.Ð *Ð * Note: the difference between `c filter p` and `c withFilter p` is thatÐ * the former creates a new collection, whereas the latter onlyÐ * restricts the domain of subsequent `map`, `flatMap`, `foreach`,Ð * and `withFilter` operations.Ð * $orderDependentÐ * Ð * @param p the predicate used to test elements.Ð * @return an object of class `WithFilter`, which supportsÐ * `map`, `flatMap`, `foreach`, and `withFilter` operations.Ð * All these operations apply to those elements of this $coll whichÐ * satisfy the predicate `p`.Ð */Ð def withFilter(p: A => Boolean): FilterMonadic[A, Repr] = new WithFilter(p)Ð /** A class supporting filtered operations. Instances of this class areÐ * returned by method `withFilter`.Ð */Ð class WithFilter(p: A => Boolean) extends FilterMonadic[A, Repr] {Ð /** Builds a new collection by applying a function to all elements of theÐ * outer $coll containing this `WithFilter` instance that satisfy predicate `p`.Ð *Ð * @param f the function to apply to each element.Ð * @tparam B the element type of the returned collection.Ð * @tparam That $thatinfoÐ * @param bf $bfinfoÐ * @return a new collection of type `That` resulting from applyingÐ * the given function `f` to each element of the outer $collÐ * that satisfies predicate `p` and collecting the results.Ð *Ð * @usecase def map[B](f: A => B): $Coll[B] Ð * Ð * @return a new $coll resulting from applying the given functionÐ * `f` to each element of the outer $coll that satisfiesÐ * predicate `p` and collecting the results.Ð */Ð def map[B, That](f: A => B)(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð val b = bf(repr)Ð for (x <- self) Ð if (p(x)) b += f(x)Ð b.resultÐ }Ð /** Builds a new collection by applying a function to all elements of theÐ * outer $coll containing this `WithFilter` instance that satisfyÐ * predicate `p` and concatenating the results. Ð *Ð * @param f the function to apply to each element.Ð * @tparam B the element type of the returned collection.Ð * @tparam That $thatinfoÐ * @param bf $bfinfoÐ * @return a new collection of type `That` resulting from applyingÐ * the given collection-valued function `f` to each elementÐ * of the outer $coll that satisfies predicate `p` andÐ * concatenating the results.Ð *Ð * @usecase def flatMap[B](f: A => TraversableOnce[B]): $Coll[B]Ð * Ð * @return a new $coll resulting from applying the given collection-valued functionÐ * `f` to each element of the outer $coll that satisfies predicate `p` and concatenating the results.Ð */Ð def flatMap[B, That](f: A => GenTraversableOnce[B])(implicit bf: CanBuildFrom[Repr, B, That]): That = {Ð val b = bf(repr)Ð for (x <- self) Ð if (p(x)) b ++= f(x).seqÐ b.resultÐ }Ð /** Applies a function `f` to all elements of the outer $coll containingÐ * this `WithFilter` instance that satisfy predicate `p`.Ð

```
                                        *Ð      *  @param  f   the
function that is applied for its side-effect to every element.Ð
*              The result of function `f` is discarded.Ð      *              Ð
       *  @tparam  U  the type parameter describing the result of function
`f`. Ð      *              This result will always be ignored. Typically `U`
is `Unit`,Ð      *              but this is not necessary.Ð      *Ð      *
@usecase def foreach(f: A => Unit): UnitÐ      */   Ð     def foreach[U](f: A
=> U): Unit = Ð       for (x <- self) Ð         if (p(x)) f(x)Ð     /**
Further refines the filter for this $coll.Ð      *Ð      *  @param q   the
predicate used to test elements.Ð      *  @return    an object of class
`WithFilter`, which supportsÐ      *             `map`, `flatMap`, `foreach`,
and `withFilter` operations.Ð      *             All these operations apply
to those elements of this $coll whichÐ      *             satisfy the
predicate `q` in addition to the predicate `p`.Ð      */Ð     def
withFilter(q: A => Boolean): WithFilter = Ð       new WithFilter(x => p(x) &&
q(x))Ð   }Ð   // A helper for tails and inits.Ð   private def
iterateUntilEmpty(f: Traversable[A @uV] => Traversable[A @uV]):
Iterator[Repr] = {Ð     val it = Iterator.iterate(thisCollection)(f)
takeWhile (x => !x.isEmpty)Ð     it ++ Iterator(Nil) map (newBuilder ++= _
result)Ð   }Ð }Ð</textarea>Ð</form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       theme: "ambiance",Ð
        mode: "text/x-scala"Ð     });Ð   </script>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\clojure\index.html


```
<!doctype html>Ðtitle>CodeMirror: Clojure mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="clojure.js"></script>Ðstyle>.CodeMirror {background:
#f8f8f8;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Clojure</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Clojure mode</h2>Ðform><textarea id="code" name="code">Ð; Conway's Game of
Life, based on the work of:Ð; Laurent Petit https://gist.github.com/1200343Ð;
Christophe Grand http://clj-me.cgrand.net/2011/08/19/conways-game-of-lifeÐ(ns
^{:doc "Conway's Game of Life."}Ðgame-of-life)Ð; Core game of life's
algorithm functionsÐ(defn neighboursÐ "Given a cell's coordinates, returns the
coordinates of its neighbours."Ð [[x y]]Ð (for [dx [-1 0 1] dy (if (zero? dx)
[-1 1] [-1 0 1])]Ð   [(+ dx x) (+ dy y)]))Ð(defn stepÐ "Given a set of living
cells, computes the new set of living cells."Ð [cells]Ð (set (for [[cell n]
(frequencies (mapcat neighbours cells))Ð            :when (or (= n 3) (and (=
n 2) (cells cell)))]Ð        cell)))Ð; Utility methods for displaying game on
a text terminalÐ(defn print-boardÐ "Prints a board on *out*, representing a
step in the game."Ð [board w h]Ð (doseq [x (range (inc w)) y (range (inc h))]Ð
    (if (= y 0) (print "\n"))Ð   (print (if (board [x y]) "[X]" " . "))))Ð
(defn display-gridsÐ "Prints a squence of boards on *out*, representing
several steps."Ð [grids w h]Ð (doseq [board grids]Ð   (print-board board w h)Ð
    (print "\n")))Ð; Launches an example boardÐ(defÐ ^{:doc "board represents
the initial set of living cells"}Ð  board #{[2 1] [2 2] [2 3]})Ð(display-grids
(take 3 (iterate step board)) 5 5)Ð; Let's play with charactersÐ(println \1 \a
\# \\Ð        \" \( \newlineÐ        \} \" \spaceÐ        \tab \return
\backspaceÐ        \u1000 \uAaAa \u9F9F)Ð/textarea></form>Ð   <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {});Ð
</script>Ð   <p><strong>MIME types defined:</strong> <code>text/x-clojure</
code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\cobol\index.html

```
<!doctype html>Ðtitle>CodeMirror: COBOL mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
neat.css">Ðlink rel="stylesheet" href="../../theme/elegant.css">Ðlink
rel="stylesheet" href="../../theme/erlang-dark.css">Ðlink rel="stylesheet"
href="../../theme/night.css">Ðlink rel="stylesheet" href="../../theme/
monokai.css">Ðlink rel="stylesheet" href="../../theme/cobalt.css">Ðlink
rel="stylesheet" href="../../theme/eclipse.css">Ðlink rel="stylesheet"
href="../../theme/rubyblue.css">Ðlink rel="stylesheet" href="../../theme/
lesser-dark.css">Ðlink rel="stylesheet" href="../../theme/xq-dark.css">Ðlink
rel="stylesheet" href="../../theme/xq-light.css">Ðlink rel="stylesheet"
href="../../theme/ambiance.css">Ðlink rel="stylesheet" href="../../theme/
blackboard.css">Ðlink rel="stylesheet" href="../../theme/vibrant-ink.css">Ð
<link rel="stylesheet" href="../../theme/solarized.css">Ðlink
rel="stylesheet" href="../../theme/twilight.css">Ðlink rel="stylesheet"
href="../../theme/midnight.css">Ðlink rel="stylesheet" href="../../addon/
dialog/dialog.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="../../addon/edit/matchbrackets.js"></script>Ðscript src="cobol.js"></
script>Ðscript src="../../addon/selection/active-line.js"></script>Ðscript
src="../../addon/search/search.js"></script>Ðscript src="../../addon/dialog/
dialog.js"></script>Ðscript src="../../addon/search/searchcursor.js"></script>Ð
<style>Ð       .CodeMirror {Ð         border: 1px solid #eee;Ð         font-
size : 20px;Ð         height : auto !important;Ð       }Ð       .CodeMirror-
activeline-background {background: #555555 !important;}Ð   </style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">COBOL</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>COBOL mode</h2>Ð   <p> Select Theme <select
onchange="selectTheme()" id="selectTheme">Ð       <option>default</option>Ð
        <option>ambiance</option>Ð       <option>blackboard</option>Ð
<option>cobalt</option>Ð       <option>eclipse</option>Ð
<option>elegant</option>Ð       <option>erlang-dark</option>Ð
<option>lesser-dark</option>Ð       <option>midnight</option>Ð
<option>monokai</option>Ð       <option>neat</option>Ð       <option>night</
option>Ð       <option>rubyblue</option>Ð       <option>solarized dark</
option>Ð       <option>solarized light</option>Ð       <option
selected>twilight</option>Ð       <option>vibrant-ink</option>Ð
<option>xq-dark</option>Ð       <option>xq-light</option>Ð   </select>
Select Font Size <select onchange="selectFontsize()" id="selectFontSize">Ð
          <option value="13px">13px</option>Ð         <option
value="14px">14px</option>Ð         <option value="16px">16px</option>Ð
          <option value="18px">18px</option>Ð         <option value="20px"
selected="selected">20px</option>Ð         <option value="24px">24px</option>Ð
          <option value="26px">26px</option>Ð         <option
value="28px">28px</option>Ð         <option value="30px">30px</option>Ð
          <option value="32px">32px</option>Ð         <option
value="34px">34px</option>Ð         <option value="36px">36px</option>Ð
</select>Ðlabel for="checkBoxReadOnly">Read-only</label>Ðinput
type="checkbox" id="checkBoxReadOnly" onchange="selectReadOnly()">Ðlabel
for="id_tabToIndentSpace">Insert Spaces on Tab</label>Ðinput type="checkbox"
id="id_tabToIndentSpace" onchange="tabToIndentSpace()">Ð/p>Ðtextarea
id="code" name="code">Ð
---------1---------2---------3---------4---------5---------6---------7---------8Ð
12345678911234567892123456789312345678941234567895123456789612345678971234567898Ð
000010 IDENTIFICATION DIVISION.
MODTGHEREÐ000020 PROGRAM-ID.       SAMPLE.Ð000030 AUTHOR.           TEST SAM. Ð
000040 DATE-WRITTEN.     5 February 2013Ð
```

000041Ð00042* A sample program just
to show the form.Ð00043* The program copies its input to the output,Ð00044*
and counts the number of records.Ð00045* At the end this number is printed.Ð
000046Ð00050 ENVIRONMENT DIVISION.Ð00060 INPUT-OUTPUT SECTION.Ð00070 FILE-
CONTROL.Ð00080 SELECT STUDENT-FILE ASSIGN TO SYSINÐ00090
ORGANIZATION IS LINE SEQUENTIAL.Ð00100 SELECT PRINT-FILE ASSIGN TO
SYSOUTÐ00110 ORGANIZATION IS LINE SEQUENTIAL.Ð00120Ð00130 DATA
DIVISION.Ð00140 FILE SECTION.Ð00150 FD STUDENT-FILEÐ00160 RECORD
CONTAINS 43 CHARACTERSÐ00170 DATA RECORD IS STUDENT-IN.Ð00180 01 STUDENT-
IN PIC X(43).Ð00190Ð00200 FD PRINT-FILEÐ00210 RECORD
CONTAINS 80 CHARACTERSÐ00220 DATA RECORD IS PRINT-LINE.Ð00230 01 PRINT-
LINE PIC X(80).Ð00240Ð00250 WORKING-STORAGE SECTION.Ð00260 01
DATA-REMAINS-SWITCH PIC X(2) VALUE SPACES.Ð00261 01 RECORDS-
WRITTEN PIC 99.Ð00270Ð00280 01 DETAIL-LINE.Ð00290 05
FILLER PIC X(7) VALUE SPACES.Ð00300 05 RECORD-
IMAGE PIC X(43).Ð00310 05 FILLER PIC X(30) VALUE
SPACES.Ð00311 Ð00312 01 SUMMARY-LINE.Ð00313 05 FILLER PIC
X(7) VALUE SPACES.Ð00314 05 TOTAL-READ PIC 99.Ð00315
05 FILLER PIC X VALUE SPACE.Ð00316 05
FILLER PIC X(17) Ð00317 VALUE 'Records were
read'.Ð00318 05 FILLER PIC X(53) VALUE SPACES.Ð00319Ð
000320 PROCEDURE DIVISION.Ð00321Ð00330 PREPARE-SENIOR-REPORT.Ð00340 OPEN
INPUT STUDENT-FILEÐ00350 OUTPUT PRINT-FILE.Ð00351 MOVE ZERO TO
RECORDS-WRITTEN.Ð00360 READ STUDENT-FILEÐ00370 AT END MOVE 'NO'
TO DATA-REMAINS-SWITCHÐ00380 END-READ.Ð00390 PERFORM PROCESS-RECORDSÐ
000410 UNTIL DATA-REMAINS-SWITCH = 'NO'.Ð00411 PERFORM PRINT-
SUMMARY.Ð00420 CLOSE STUDENT-FILEÐ00430 PRINT-FILE.Ð00440
STOP RUN.Ð00450Ð00460 PROCESS-RECORDS.Ð00470 MOVE STUDENT-IN TO RECORD-
IMAGE.Ð00480 MOVE DETAIL-LINE TO PRINT-LINE.Ð00490 WRITE PRINT-LINE.Ð
000500 ADD 1 TO RECORDS-WRITTEN.Ð00510 READ STUDENT-FILEÐ
000520 AT END MOVE 'NO' TO DATA-REMAINS-SWITCHÐ00530 END-READ. Ð
000540Ð00550 PRINT-SUMMARY.Ð00560 MOVE RECORDS-WRITTEN TO TOTAL-READ.Ð
000570 MOVE SUMMARY-LINE TO PRINT-LINE.Ð00571 WRITE PRINT-LINE. Ð00572Ð
000580Ð/textarea>Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð matchBrackets: true,Ð mode: "text/x-cobol",Ð
theme : "twilight",Ð styleActiveLine: true,Ð
showCursorWhenSelecting : true, Ð });Ð function selectTheme() {Ð
var themeInput = document.getElementById("selectTheme");Ð var
theme = themeInput.options[themeInput.selectedIndex].innerHTML;Ð
editor.setOption("theme", theme);Ð }Ð function selectFontsize() {Ð
var fontSizeInput = document.getElementById("selectFontSize");Ð
var fontSize = fontSizeInput.options[fontSizeInput.selectedIndex].innerHTML;Ð
editor.getWrapperElement().style.fontSize = fontSize;Ð
editor.refresh();Ð }Ð function selectReadOnly() {Ð
editor.setOption("readOnly",
document.getElementById("checkBoxReadOnly").checked);Ð }Ð function
tabToIndentSpace() {Ð if
(document.getElementById("id_tabToIndentSpace").checked) {Ð
editor.setOption("extraKeys", {Tab: function(cm) { cm.replaceSelection("
", "end"); }});Ð } else {Ð editor.setOption("extraKeys",
{Tab: function(cm) { cm.replaceSelection(" ", "end"); }});Ð }Ð }Ð
</script>Ð </article>Ð

public\assets\js\plugins\codemirror\mode\coffeescript\index.html

<!doctype html>Ðtitle>CodeMirror: CoffeeScript mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="coffeescript.js"></script>Ð <style>.CodeMirror {border-top: 1px solid silver; border-bottom: 1px solid silver;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">CoffeeScript</a>Ð </ul>Ð/div>Ðarticle>Ðh2>CoffeeScript mode</h2>Ð <form><textarea id="code" name="code">Ð CoffeeScript mode for CoMirrorÐ Copyright (c) 2011 Jeff Pickhardt, released underÐ the MIT License.ÐÐ Modified from the Python CoMirror mode, which also is Ð under the MIT License Copyright (c) 2010 Timothy Farrell.ÐÐ The following script, Underscore.coffee, is used to Ð demonstrate CoffeeScript mode for CoMirror.ÐÐ # To download CoffeeScript mode for CoMirror, go to:Ð https://github.com/pickhardt/coffeescript-codemirror-modeÐ **Underscore.coffeeÐ (c) 2011 Jeremy Ashkenas, DocumentCloud Inc.**Ð Underscore is freely distributable under the terms of theÐ [MIT license](http://en.wikipedia.org/wiki/MIT_License).Ð Portions of Underscore are inspired by or borrowed fromÐ [Prototype.js](http://prototypejs.org/api), Oliver Steele'sÐ [Functional](http://osteele.com), and John Resig'sÐ [Micro-Templating](http://ejohn.org).Ð For all details and documentation:Ð http://documentcloud.github.com/underscore/Ð Baseline setupÐ ----------Ð Establish the root object, `window` in the browser, or `global` on the server.Ðoot = thisÐ Save the previous value of the `_` variable.ÐpreviousUnderscore = root._Ð## MultilineÐ commentÐ###Ð Establish the object that gets thrown to break out of a loop iteration.Ð `StopIteration` is SOP on Mozilla.Ðreaker = if typeof(StopIteration) is 'undefined' then '__break__' else StopIterationÐ### Docco style single line comment (title)Ð Helper function to escape **RegExp** contents, because JS doesn't have one.ÐscapeRegExp = (string) -> string.replace(/([.*+?^${}()|[\]\/\\])/g, '\\$1')Ð Save bytes in the minified (but not gzipped) version:Ð ArrayProto = Array.prototypeÐbjProto = Object.prototypeÐ Create quick reference variables for speed access to core prototypes.Ðlice = ArrayProto.sliceÐnshift = ArrayProto.unshiftÐoString = ObjProto.toStringÐ hasOwnProperty = ObjProto.hasOwnPropertyÐropertyIsEnumerable = ObjProto.propertyIsEnumerableÐ All **ECMA5** native implementations we hope to use are declared here.ÐativeForEach = ArrayProto.forEachÐativeMap = ArrayProto.mapÐativeReduce = ArrayProto.reduceÐativeReduceRight = ArrayProto.reduceRightÐativeFilter = ArrayProto.filterÐativeEvery = ArrayProto.everyÐativeSome = ArrayProto.someÐativeIndexOf = ArrayProto.indexOfÐ nativeLastIndexOf = ArrayProto.lastIndexOfÐativeIsArray = Array.isArrayÐ nativeKeys = Object.keysÐ Create a safe reference to the Underscore object for use below.Ð = (obj) -> new wrapper(obj)Ð Export the Underscore object for **CommonJS**.Ðf typeof(exports) != 'undefined' then exports._ = _Ð Export Underscore to global scope.Ðoot._ = _Ð Current version.Ð.VERSION = '1.1.0'Ð Collection FunctionsÐ ----------Ð The cornerstone, an **each** implementation.Ð Handles objects implementing **forEach**, arrays, and raw objects.Ð.each = (obj, iterator, context) ->Ð tryÐ if nativeForEach and obj.forEach is nativeForEachÐ obj.forEach iterator, contextÐ else if _.isNumber obj.lengthÐ iterator.call context, obj[i], i, obj for i in [0...obj.length]Ð elseÐ iterator.call context, val, key, obj for own key, val of objÐ catch eÐ throw e if e isnt breakerÐ objÐ Return the results of applying the iterator to each element. Use JavaScriptÐ 1.6's version of **map**, if possible.Ð.map = (obj, iterator, context) ->Ð return obj.map(iterator, context) if nativeMap and obj.map is nativeMapÐ results = []Ð _.each obj, (value, index, list) ->Ð results.push iterator.call context, value, index, listÐ

resultsÐ **Reduce** builds up a single result from a list of values. Also known asÐ **inject**, or **foldl**. Uses JavaScript 1.8's version of **reduce**, if possible.Ð.reduce = (obj, iterator, memo, context) ->Ð if nativeReduce and obj.reduce is nativeReduceÐ iterator = _.bind iterator, context if contextÐ return obj.reduce iterator, memoÐ _.each obj, (value, index, list) ->Ð memo = iterator.call context, memo, value, index, listÐ memoÐ The right-associative version of **reduce**, also known as **foldr**. UsesÐ JavaScript 1.8's version of **reduceRight**, if available.Ð _.reduceRight = (obj, iterator, memo, context) ->Ð if nativeReduceRight and obj.reduceRight is nativeReduceRightÐ iterator = _.bind iterator, context if contextÐ return obj.reduceRight iterator, memoÐ reversed = _.clone(_.toArray(obj)).reverse()Ð _.reduce reversed, iterator, memo, contextÐ # Return the first value which passes a truth test.Ð.detect = (obj, iterator, context) ->Ð result = nullÐ _.each obj, (value, index, list) ->Ð if iterator.call context, value, index, listÐ result = valueÐ _.breakLoop()Ð resultÐ Return all the elements that pass a truth test. Use JavaScript 1.6'sÐ **filter**, if it exists.Ð.filter = (obj, iterator, context) ->Ð return obj.filter iterator, context if nativeFilter and obj.filter is nativeFilterÐ results = []Ð _.each obj, (value, index, list) ->Ð results.push value if iterator.call context, value, index, listÐ resultsÐ Return all the elements for which a truth test fails.Ð.reject = (obj, iterator, context) ->Ð results = []Ð _.each obj, (value, index, list) ->Ð results.push value if not iterator.call context, value, index, listÐ resultsÐ Determine whether all of the elements match a truth test. Delegate toÐ JavaScript 1.6's **every**, if it is present.Ð.every = (obj, iterator, context) ->Ð iterator ||= _.identityÐ return obj.every iterator, context if nativeEvery and obj.every is nativeEveryÐ result = trueÐ _.each obj, (value, index, list) ->Ð _.breakLoop() unless (result = result and iterator.call(context, value, index, list))Ð resultÐ Determine if at least one element in the object matches a truth test. UseÐ JavaScript 1.6's **some**, if it exists.Ð.some = (obj, iterator, context) ->Ð iterator ||= _.identityÐ return obj.some iterator, context if nativeSome and obj.some is nativeSomeÐ result = falseÐ _.each obj, (value, index, list) ->Ð _.breakLoop() if (result = iterator.call(context, value, index, list))Ð resultÐ # Determine if a given value is included in the array or object,Ð based on `===`.Ð.include = (obj, target) ->Ð return _.indexOf(obj, target) isnt -1 if nativeIndexOf and obj.indexOf is nativeIndexOfÐ return true for own key, val of obj when val is targetÐ falseÐ Invoke a method with arguments on every item in a collection.Ð.invoke = (obj, method) ->Ð args = _.rest arguments, 2Ð (if method then val[method] else val).apply(val, args) for val in objÐ Convenience version of a common use case of **map**: fetching a property.Ð _.pluck = (obj, key) ->Ð _.map(obj, (val) -> val[key])Ð Return the maximum item or (item-based computation).Ð.max = (obj, iterator, context) ->Ð return Math.max.apply(Math, obj) if not iterator and _.isArray(obj)Ð result = computed: -InfinityÐ _.each obj, (value, index, list) ->Ð computed = if iterator then iterator.call(context, value, index, list) else valueÐ computed >= result.computed and (result = {value: value, computed: computed})Ð result.valueÐ Return the minimum element (or element-based computation).Ð _.min = (obj, iterator, context) ->Ð return Math.min.apply(Math, obj) if not iterator and _.isArray(obj)Ð result = computed: InfinityÐ _.each obj, (value, index, list) ->Ð computed = if iterator then iterator.call(context, value, index, list) else valueÐ computed < result.computed and (result = {value: value, computed: computed})Ð result.valueÐ Sort the object's values by a criterion produced by an iterator.Ð.sortBy = (obj, iterator, context) ->Ð _.pluck(((_.map obj, (value, index, list) ->Ð {value: value, criteria: iterator.call(context, value, index, list)}Ð).sort((left, right) ->Ð a = left.criteria; b = right.criteriaÐ if a < b then -1 else if a > b then 1 else 0Ð)), 'value')Ð Use a comparator function to figure out at what index an object shoulÐ be inserted so as to maintain order. Uses binary search.Ð _.sortedIndex = (array, obj, iterator) ->Ð

iterator ||= _.identityÐ low = 0Ð high = array.lengthÐ while low < highÐ mid = (low + high) >> 1Ð if iterator(array[mid]) < iterator(obj) then low = mid + 1 else high = midÐ lowÐ Convert anything iterable into a real, live array.Ð.toArray = (iterable) ->Ð return [] if (!iterable)Ð return iterable.toArray() if (iterable.toArray)Ð return iterable if (_.isArray(iterable))Ð return slice.call(iterable) if (_.isArguments(iterable))Ð _.values(iterable)Ð Return the number of elements in an object.Ð.size = (obj) -> _.toArray(obj).lengthÐ Array FunctionsÐ ----------Ð Get the first element of an array. Passing `n` will return the first NÐ values in the array. Aliased as **head**. The `guard` check allows it to workÐ with **map**.Ð.first = (array, n, guard) ->Ð if n and not guard then slice.call(array, 0, n) else array[0]Ð Returns everything but the first entry of the array. Aliased as **tail**.Ð Especially useful on the arguments object. Passing an `index` will returnÐ the rest of the values in the array from that index onward. The `guard`Ð check allows it to work with **map**.Ð.rest = (array, index, guard) ->Ð slice.call(array, if _.isUndefined(index) or guard then 1 else index)Ð Get the last element of an array.Ð.last = (array) -> array[array.length - 1]Ð Trim out all falsy values from an array.Ð.compact = (array) -> item for item in array when itemÐ Return a completely flattened version of an array.Ð.flatten = (array) ->Ð _.reduce array, (memo, value) ->Ð return memo.concat(_.flatten(value)) if _.isArray valueÐ memo.push valueÐ memoÐ , []Ð Return a version of the array that does not contain the specified value(s).Ð.without = (array) ->Ð values = _.rest argumentsÐ val for val in _.toArray(array) when not _.include values, valÐ Produce a duplicate-free version of the array. If the array has alreadyÐ been sorted, you have the option of using a faster algorithm.Ð.uniq = (array, isSorted) ->Ð memo = []Ð for el, i in _.toArray arrayÐ memo.push el if i is 0 || (if isSorted is true then _.last(memo) isnt el else not _.include(memo, el))Ð memoÐ Produce an array that contains every item shared between all theÐ passed-in arrays.Ð.intersect = (array) ->Ð rest = _.rest argumentsÐ _.select _.uniq(array), (item) ->Ð _.all rest, (other) ->Ð _.indexOf(other, item) >= 0Ð Zip together multiple lists into a single array -- elements that shareÐ an index go together.Ð.zip = ->Ð length = _.max _.pluck arguments, 'length'Ð results = new Array lengthÐ for i in [0...length]Ð results[i] = _.pluck arguments, String iÐ resultsÐ If the browser doesn't supply us with **indexOf** (I'm looking at you, MSIE),Ð we need this function. Return the position of the first occurrence of anÐ item in an array, or -1 if the item is not included in the array.Ð.indexOf = (array, item) ->Ð return array.indexOf item if nativeIndexOf and array.indexOf is nativeIndexOfÐ i = 0; l = array.lengthÐ while l - iÐ if array[i] is item then return i else i++Ð -1Ð Provide JavaScript 1.6's **lastIndexOf**, delegating to the native function,Ð if possible.Ð.lastIndexOf = (array, item) ->Ð return array.lastIndexOf(item) if nativeLastIndexOf and array.lastIndexOf is nativeLastIndexOfÐ i = array.lengthÐ while iÐ if array[i] is item then return i else i--Ð -1Ð Generate an integer Array containing an arithmetic progression. A port ofÐ [the native Python **range** function](http://docs.python.org/library/functions.html#range).Ð.range = (start, stop, step) ->Ð a = argumentsÐ solo = a.length <= 1Ð i = start = if solo then 0 else a[0]Ð stop = if solo then a[0] else a[1]Ð step = a[2] or 1Ð len = Math.ceil((stop - start) / step)Ð return [] if len <= 0Ð range = new Array lenÐ idx = 0Ð loopÐ return range if (if step > 0 then i - stop else stop - i) >= 0Ð range[idx] = iÐ idx++Ð i+= stepÐ Function FunctionsÐ ----------Ð Create a function bound to a given object (assigning `this`, and arguments,Ð optionally). Binding with arguments is also known as **curry**.Ð.bind = (func, obj) ->Ð args = _.rest arguments, 2Ð -> func.apply obj or root, args.concat argumentsÐ Bind all of an object's methods to that object. Useful for ensuring thatÐ all callbacks defined on an object belong to it.Ð.bindAll = (obj) ->Ð funcs = if arguments.length > 1 then _.rest(arguments) else _.functions(obj)Ð _.each funcs, (f) -> obj[f] = _.bind obj[f], objÐ objÐ Delays a function for the given number of milliseconds, and then callsÐ

it with the arguments supplied.Ð.delay = (func, wait) ->Ð args = _.rest arguments, 2Ð setTimeout((-> func.apply(func, args)), wait)Ð Memoize an expensive function by storing its results.Ð.memoize = (func, hasher) ->Ð memo = {}Ð hasher or= _.identityÐ ->Ð key = hasher.apply this, argumentsÐ return memo[key] if key of memoÐ memo[key] = func.apply this, argumentsÐ Defers a function, scheduling it to run after the current call stack hasÐ cleared.Ð.defer = (func) ->Ð _.delay.apply _, [func, 1].concat _.rest argumentsÐ Returns the first function passed as an argument to the second,Ð allowing you to adjust arguments, run code before and after, andÐ conditionally execute the original function.Ð.wrap = (func, wrapper) ->Ð -> wrapper.apply wrapper, [func].concat argumentsÐ Returns a function that is the composition of a list of functions, eachÐ consuming the return value of the function that follows.Ð.compose = ->Ð funcs = argumentsÐ ->Ð args = argumentsÐ for i in [funcs.length - 1..0] by -1Ð args = [funcs[i].apply(this, args)]Ð args[0]Ð Object FunctionsÐ ----------Ð Retrieve the names of an object's properties.Ð.keys = nativeKeys or (obj) ->Ð return _.range 0, obj.length if _.isArray(obj)Ð key for key, val of objÐ Retrieve the values of an object's properties.Ð.values = (obj) ->Ð _.map obj, _.identityÐ Return a sorted list of the function names available in Underscore.Ð.functions = (obj) ->Ð _.filter(_.keys(obj), (key) -> _.isFunction(obj[key])).sort()Ð Extend a given object with all of the properties in a source object.Ð.extend = (obj) ->Ð for source in _.rest(arguments)Ð obj[key] = val for key, val of sourceÐ objÐ Create a (shallow-cloned) duplicate of an object.Ð.clone = (obj) ->Ð return obj.slice 0 if _.isArray objÐ _.extend {}, objÐ Invokes interceptor with the obj, and then returns obj.Ð The primary purpose of this method is to "tap into" a method chain,Ð in order to perform operations on intermediate results withinÐ the chain.Ð.tap = (obj, interceptor) ->Ð interceptor objÐ objÐ Perform a deep comparison to check if two objects are equal.Ð.isEqual = (a, b) ->Ð # Check object identity.Ð return true if a is bÐ # Different types?Ð atype = typeof(a); btype = typeof(b)Ð return false if atype isnt btypeÐ # Basic equality test (watch out for coercions).Ð return true if `a == b`Ð # One is falsy and the other truthy.Ð return false if (!a and b) or (a and !b)Ð # One of them implements an `isEqual()`?Ð return a.isEqual(b) if a.isEqualÐ # Check dates' integer values.Ð return a.getTime() is b.getTime() if _.isDate(a) and _.isDate(b)Ð # Both are NaN?Ð return false if _.isNaN(a) and _.isNaN(b)Ð # Compare regular expressions.Ð if _.isRegExp(a) and _.isRegExp(b)Ð return a.source is b.source andÐ a.global is b.global andÐ a.ignoreCase is b.ignoreCase andÐ a.multiline is b.multilineÐ # If a is not an object by this point, we can't handle it.Ð return false if atype isnt 'object'Ð # Check for different array lengths before comparing contents.Ð return false if a.length and (a.length isnt b.length)Ð # Nothing else worked, deep compare the contents.Ð aKeys = _.keys(a); bKeys = _.keys(b)Ð # Different object sizes?Ð return false if aKeys.length isnt bKeys.lengthÐ # Recursive comparison of contents.Ð return false for key, val of a when !(key of b) or !_.isEqual(val, b[key])Ð trueÐ Is a given array or object empty?Ð _.isEmpty = (obj) ->Ð return obj.length is 0 if _.isArray(obj) or _.isString(obj)Ð return false for own key of objÐ trueÐ Is a given value a DOM element?Ð.isElement = (obj) -> obj and obj.nodeType is 1Ð Is a given value an array?Ð.isArray = nativeIsArray or (obj) -> !!(obj and obj.concat and obj.unshift and not obj.callee)Ð Is a given variable an arguments object?Ð _.isArguments = (obj) -> obj and obj.calleeÐ Is the given value a function?Ð _.isFunction = (obj) -> !!(obj and obj.constructor and obj.call and obj.apply)Ð # Is the given value a string?Ð.isString = (obj) -> !!(obj is '' or (obj and obj.charCodeAt and obj.substr))Ð Is a given value a number?Ð.isNumber = (obj) -> (obj is +obj) or toString.call(obj) is '[object Number]'Ð Is a given value a boolean?Ð.isBoolean = (obj) -> obj is true or obj is falseÐ Is a given value a Date?Ð.isDate = (obj) -> !!(obj and obj.getTimezoneOffset and obj.setUTCFullYear)Ð

Ð Is the given value a regular expression?Ð.isRegExp =
(obj) -> !!(obj and obj.exec and (obj.ignoreCase or obj.ignoreCase is false))Ð
Is the given value NaN -- this one is interesting. `NaN != NaN`, andÐ
`isNaN(undefined) == true`, so we make sure it's a number first.Ð.isNaN =
(obj) -> _.isNumber(obj) and window.isNaN(obj)Ð Is a given value equal to
null?Ð.isNull = (obj) -> obj is nullÐ Is a given variable undefined?Ð
_.isUndefined = (obj) -> typeof obj is 'undefined'Ð Utility FunctionsÐ
----------Ð Run Underscore.js in noConflict mode, returning the `_`
variable to itsÐ previous owner. Returns a reference to the Underscore object.Ð
.noConflict = ->Ð root. = previousUnderscoreÐ thisÐ Keep the identity
function around for default iterators.Ð.identity = (value) -> valueÐ Run a
function `n` times.Ð.times = (n, iterator, context) ->Ð iterator.call
context, i for i in [0...n]Ð Break out of the middle of an iteration.Ð
_.breakLoop = -> throw breakerÐ Add your own custom functions to the
Underscore object, ensuring thatÐ they're correctly added to the OOP wrapper
as well.Ð.mixin = (obj) ->Ð for name in _.functions(obj)Ð addToWrapper
name, _[name] = obj[name]Ð Generate a unique integer id (unique within the
entire client session).Ð Useful for temporary DOM ids.ÐidCounter = 0Ð.uniqueId
= (prefix) ->Ð (prefix or '') + idCounter++Ð By default, Underscore uses
ERB-style template delimiters, change theÐ following template settings to
use alternative delimiters.Ð.templateSettings = {Ð start: '<%'Ð end: '%>'Ð
interpolate: /<%=(.+?)%>/gÐ}Ð JavaScript templating a-la **ERB**, pilfered
from John Resig'sÐ *Secrets of the JavaScript Ninja*, page 83.Ð Single-quote
fix from Rick Strahl.Ð With alterations for arbitrary delimiters, and to
preserve whitespace.Ð.template = (str, data) ->Ð c = _.templateSettingsÐ
endMatch = new RegExp("'(?=[^"+c.end.substr(0,
1)+"]*"+escapeRegExp(c.end)+")","g")Ð fn = new Function 'obj',Ð 'var
p=[],print=function(){p.push.apply(p,arguments);};' +Ð 'with(obj||{})
{p.push(\'' +Ð str.replace(/\r/g, '\\r')Ð .replace(/\n/g, '\\n')Ð
  .replace(/\t/g, '\\t')Ð .replace(endMatch,"ÿýýýýý")Ð
  .split("'").join("\\'")Ð .split("ÿýýýýý").join("'")Ð
  .replace(c.interpolate, "',$1,'")Ð .split(c.start).join("');")Ð
  .split(c.end).join("p.push('") +Ð "');}return p.join('');"Ð if
data then fn(data) else fnÐ AliasesÐ -------Ð.forEach = _.eachÐ.foldl =
_.inject = _.reduceÐ.foldr = _.reduceRightÐ.select = _.filterÐ.all = _.everyÐ
_.any = _.someÐ.contains = _.includeÐ.head = _.firstÐ.tail = _.restÐ.methods
= _.functionsÐ Setup the OOP WrapperÐ ----------Ð If Underscore is
called as a function, it returns a wrapped object thatÐ can be used OO-style.
This wrapper holds altered versions of all theÐ underscore functions. Wrapped
objects may be chained.Ðwrapper = (obj) ->Ð this._wrapped = objÐ thisÐ Helper
function to continue chaining intermediate results.Ðesult = (obj, chain) ->Ð
if chain then _(obj).chain() else objÐ A method to easily add functions to
the OOP wrapper.ÐaddToWrapper = (name, func) ->Ð wrapper.prototype[name] = ->Ð
  args = _.toArray argumentsÐ unshift.call args, this._wrappedÐ result
func.apply(_, args), this._chainÐ Add all ofthe Underscore functions to the
wrapper object.Ð.mixin _Ð Add all mutator Array functions to the wrapper.Ð
_.each ['pop', 'push', 'reverse', 'shift', 'sort', 'splice', 'unshift'],
(name) ->Ð method = Array.prototype[name]Ð wrapper.prototype[name] = ->Ð
method.apply(this._wrapped, arguments)Ð result(this._wrapped, this._chain)Ð
Add all accessor Array functions to the wrapper.Ð.each ['concat', 'join',
'slice'], (name) ->Ð method = Array.prototype[name]Ð wrapper.prototype[name]
= ->Ð result(method.apply(this._wrapped, arguments), this._chain)Ð Start
chaining a wrapped Underscore object.Ðwrapper::chain = ->Ð this._chain = trueÐ
thisÐ Extracts the result from a wrapped and chained object.Ðwrapper::value = -
> this._wrappedÐ/textarea></form>Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð </script>Ð
MIME types defined: <code>text/x-coffeescript</code>. Ð
  The CoffeeScript mode was written by Jeff Pickhardt. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\commonlisp\index.html

```
<!doctype html>Ðtitle>CodeMirror: Common Lisp mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="commonlisp.js"></script>Ð
<style>.CodeMirror {background: #f8f8f8;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Common Lisp</a>Ð
  </ul>Ð/div>Ðarticle>Ðh2>Common Lisp mode</h2>Ðform><textarea id="code"
name="code">(in-package :cl-postgres)Ð; These are used to synthesize reader
and writer names for integerÐ; reading/writing functions when the amount of
bytes and theÐ; signedness is known. Both the macro that creates the
functions andÐ; some macros that use them create names this way.Ð(eval-when
(:compile-toplevel :load-toplevel :execute)Ð (defun integer-reader-name
(bytes signed)Ð   (intern (with-standard-io-syntaxÐ             (format nil
"~a~a~a~a" '#:read- (if signed "" '#:u) '#:int bytes))))Ð (defun integer-
writer-name (bytes signed)Ð   (intern (with-standard-io-syntaxÐ
(format nil "~a~a~a~a" '#:write- (if signed "" '#:u) '#:int bytes)))))Ð
(defmacro integer-reader (bytes)Ð "Create a function to read integers from a
binary stream."Ð (let ((bits (* bytes 8)))Ð   (labels ((return-form (signed)Ð
               (if signedÐ                  `(if (logbitp ,(1- bits) result)Ð
                        (dpb result (byte ,(1- bits) 0) -1)Ð
                        result)Ð                  `result))Ð
(generate-reader (signed)Ð              `(defun ,(integer-reader-name bytes
signed) (socket)Ð                  (declare (type stream socket)Ð
                         #.*optimize*)Ð                  ,(if (= bytes 1)Ð
                       `(let ((result (the (unsigned-byte 8) (read-byte
socket))))Ð                         (declare (type (unsigned-byte 8) result))Ð
                         ,(return-form signed))Ð                       `(let
((result 0))Ð                         (declare (type (unsigned-byte ,bits)
result))Ð                         ,@(loop :for byte :from (1- bytes) :downto 0Ð
                                   :collect `(setf (ldb (byte 8 ,(* 8 byte))
result)Ð                                                  (the (unsigned-byte
8) (read-byte socket))))Ð                          ,(return-form signed))))))Ð
      `(prognÐ; This causes weird errors on SBCL in some circumstances.
Disabled for now.Ð;         (declaim (inline ,(integer-reader-name bytes t)Ð
;;                          ,(integer-reader-name bytes nil)))Ð
(declaim (ftype (function (t) (signed-byte ,bits))Ð                       ,
(integer-reader-name bytes t)))Ð        ,(generate-reader t)Ð        (declaim
(ftype (function (t) (unsigned-byte ,bits))Ð                        ,(integer-
reader-name bytes nil)))Ð        ,(generate-reader nil)))))Ðdefmacro integer-
writer (bytes)Ð "Create a function to write integers to a binary stream."Ð
(let ((bits (* 8 bytes)))Ð   `(prognÐ     (declaim (inline ,(integer-writer-
name bytes t)Ð                      ,(integer-writer-name bytes nil)))Ð
(defun ,(integer-writer-name bytes nil) (socket value)Ð       (declare (type
stream socket)Ð                (type (unsigned-byte ,bits) value)Ð
                #.*optimize*)Ð       ,@(if (= bytes 1)Ð             `((write-
byte value socket))Ð             (loop :for byte :from (1- bytes) :downto 0Ð
                    :collect `(write-byte (ldb (byte 8 ,(* byte 8)) value)Ð
                              socket)))Ð       (values))Ð     (defun ,
(integer-writer-name bytes t) (socket value)Ð       (declare (type stream
socket)Ð                (type (signed-byte ,bits) value)Ð
#.*optimize*)Ð       ,@(if (= bytes 1)Ð             `((write-byte (ldb (byte
8 0) value) socket))Ð             (loop :for byte :from (1- bytes) :downto 0Ð
                    :collect `(write-byte (ldb (byte 8 ,(* byte 8)) value)Ð
                              socket)))Ð       (values)))))Ð; All the
instances of the above that we need.Ð
```

Ð(integer-reader 1)Ð(integer-reader 2)Ð
(integer-reader 4)Ð(integer-reader 8)Ð(integer-writer 1)Ð(integer-writer 2)Ð
(integer-writer 4)Ðdefun write-bytes (socket bytes)Ð "Write a byte-array to a
stream."Ð (declare (type stream socket)Ð (type (simple-array
(unsigned-byte 8)) bytes)Ð #.*optimize*)Ð (write-sequence bytes
socket))Ðdefun write-str (socket string)Ð "Write a null-terminated string to
a stream \(encoding it when UTF-8 support is enabled.)."Ð (declare (type
stream socket)Ð (type string string)Ð #.*optimize*)Ð (enc-
write-string string socket)Ð (write-uint1 socket 0))Ðdeclaim (ftype (function
(t unsigned-byte)Ð (simple-array (unsigned-byte 8)
(*)))Ð read-bytes))Ðdefun read-bytes (socket length)Ð "Read a
byte array of the given length from a stream."Ð (declare (type stream socket)Ð
(type fixnum length)Ð #.*optimize*)Ð (let ((result (make-
array length :element-type '(unsigned-byte 8))))Ð (read-sequence result
socket)Ð result))Ðdeclaim (ftype (function (t) string) read-str))Ðdefun
read-str (socket)Ð "Read a null-terminated string from a stream. Takes care
of encoding when UTF-8 support is enabled."Ð (declare (type stream socket)Ð
#.*optimize*)Ð (enc-read-string socket :null-terminated t))Ðdefun
skip-bytes (socket length)Ð "Skip a given number of bytes in a binary stream."Ð
(declare (type stream socket)Ð (type (unsigned-byte 32) length)Ð
#.*optimize*)Ð (dotimes (i length)Ð (read-byte socket)))Ðdefun
skip-str (socket)Ð "Skip a null-terminated string."Ð (declare (type stream
socket)Ð #.*optimize*)Ð (loop :for char :of-type fixnum = (read-byte
socket)Ð :until (zerop char)))Ðdefun ensure-socket-is-closed (socket
&key abort)Ð (when (open-stream-p socket)Ð (handler-caseÐ (close
socket :abort abort)Ð (error (error)Ð (warn "Ignoring the error
which happened while trying to close PostgreSQL socket: ~A" error)))))Ð</
textarea></form>Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {lineNumbers: true});Ð
</script>Ð MIME types defined: <code>text/x-common-
lisp</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\css\index.html


```
<!doctype html>Ðtitle>CodeMirror: CSS mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="css.js"></script>Ðstyle>.CodeMirror {background: #f8f8f8;}
</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">CSS</a>Ð </ul>Ð/div>Ðarticle>Ðh2>CSS mode</h2>Ðform><textarea
id="code" name="code">Ð/* Some example CSS */Ð@import url("something.css");Ðbody
{Ð margin: 0;Ð padding: 3em 6em;Ð font-family: tahoma, arial, sans-serif;Ð
color: #000;ÐÐnavigation a {Ð font-weight: bold;Ð text-decoration: none !
important;ÐÐh1 {Ð font-size: 2.5em;ÐÐh2 {Ð font-size: 1.7em;ÐÐh1:before,
h2:before {Ð content: "::";ÐÐcode {Ð font-family: courier, monospace;Ð font-
size: 80%;Ð color: #418A8A;ÐÐ/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/css</code>, <code>text/x-
scss</code> (<a href="scss.html">demo</a>), <code>text/x-less</code> (<a
href="less.html">demo</a>).</p>Ð   <p><strong>Parsing/Highlighting Tests:</
strong> <a href="../../test/index.html#css_*">normal</a>,  <a href="../../
test/index.html#verbose,css_*">verbose</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\css\less.html


```
<!doctype html>Ðtitle>CodeMirror: LESS mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="css.js"></script>Ðstyle>.CodeMirror {border: 1px solid #ddd; line-
height: 1.2;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">LESS</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>LESS mode</h2>Ðform><textarea id="code" name="code">@media screen and
(device-aspect-ratio: 16/9) { … }@media screen and (device-aspect-ratio:
1280/720) { … }@media screen and (device-aspect-ratio: 2560/1440) { … }Ð
html:lang(fr-be)Ðtr:nth-child(2n+1) /* represents every odd row of an HTML
table */Ðimg:nth-of-type(2n+1) { float: right; }Ðimg:nth-of-type(2n) { float:
left; }Ðbody > h2:not(:first-of-type):not(:last-of-type)Ðhtml|
*:not(:link):not(:visited)Ð|*:not(:hover)Ðp::first-line { text-transform:
uppercase }@namespace foo url(http://www.example.com);Ðfoo|h1 { color:
blue }  /* first rule */Ðspan[hello="Ocean"][goodbye="Land"]Ð[foo]{Ð
padding:65px;ÐÐinput[type="search"]::-webkit-search-decoration,Ð
input[type="search"]::-webkit-search-cancel-button {Ð -webkit-appearance:
none; // Inner-padding issues in Chrome OSX, Safari 5ÐÐbutton::-moz-focus-
inner,Ðinput::-moz-focus-inner { // Inner padding and border oddities in FF3/4Ð
  padding: 0;Ð border: 0;ÐÐbtn {Ð // reset here as of 2.0.3 due to Recess
property orderÐ border-color: #ccc;Ð border-color: rgba(0,0,0,.1)
rgba(0,0,0,.1) rgba(0,0,0,.25);ÐÐfieldset span button, fieldset span
input[type="file"] {Ð font-size:12px;ÐföçBÖf Ö–Ç“¤ &– ÂÂ †VÇfWF–6 Â 6 ç2×6W&–c½
}Ðrounded-corners (@radius: 5px) {Ð border-radius: @radius;Ð -webkit-border-
radius: @radius;Ð -moz-border-radius: @radius;ÐÐ@import url("something.css");Ð
@light-blue:   hsl(190, 50%, 65%);Ðmenu {Ð position: absolute;Ð width: 100%;Ð
z-index: 3;Ð clear: both;Ð display: block;Ð background-color: @blue;Ð height:
42px;Ð border-top: 2px solid lighten(@alpha-blue, 20%);Ð border-bottom: 2px
solid darken(@alpha-blue, 25%);Ð .box-shadow(0, 1px, 8px, 0.6);Ð -moz-box-
shadow: 0 0 0 #000; // Because firefox sucks.Ð &.docked {Ð   background-
color: hsla(210, 60%, 40%, 0.4);Ð }Ð &:hover {Ð   background-color: @blue;Ð }Ð
  #dropdown {Ð   margin: 0 0 0 117px;Ð   padding: 0;Ð   padding-top: 5px;Ð
display: none;Ð   width: 190px;Ð   border-top: 2px solid @medium;Ð   color:
@highlight;Ð   border: 2px solid darken(@medium, 25%);Ð   border-left-color:
darken(@medium, 15%);Ð   border-right-color: darken(@medium, 15%);Ð   border-
top-width: 0;Ð   background-color: darken(@medium, 10%);Ð   ul {Ð
padding: 0px;  Ð   }Ð   li {Ð     font-size: 14px;Ð     display: block;Ð
text-align: left;Ð     padding: 0;Ð     border: 0;Ð     a {Ð       display:
block;Ð       padding: 0px 15px;  Ð       text-decoration: none;Ð
color: white;  Ð       &:hover {Ð         background-color: darken(@medium,
15%);Ð         text-decoration: none;Ð       }Ð     }Ð   }Ð   .border-
radius(5px, bottom);Ð   .box-shadow(0, 6px, 8px, 0.5);Ð }ÐÐ/textarea></form>Ð
    <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers : true,Ð       matchBrackets : true,Ð       mode: "text/x-less"Ð
      });Ð   </script>Ð   <p>The LESS mode is a sub-mode of the <a
href="index.html">CSS mode</a> (defined in <code>css.js</code>.</p>Ð
<p><strong>Parsing/Highlighting Tests:</strong> <a href="../../test/
index.html#less_*">normal</a>,  <a href="../../test/
index.html#verbose,less_*">verbose</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\css\scss.html

<!doctype html>Ðtitle>CodeMirror: SCSS mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="css.js"></script>Ðstyle>.CodeMirror {background: #f8f8f8;}
</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../
index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
  <li><a href="../index.html">Language modes</a>Ð <li><a class=active
href="#">SCSS</a>Ð </ul>Ð/div>Ðarticle>Ðh2>SCSS mode</h2>Ðform><textarea
id="code" name="code">Ð/* Some example SCSS */Ð@import "compass/css3";Ð
$variable: #333;Ðblue: #3bbfce;Ðmargin: 16px;Ðcontent-navigation {Ð #nested {Ð
  background-color: black;Ð }Ð border-color: $blue;Ð color:Ð
darken($blue, 9%);ÐÐborder {Ð padding: $margin / 2;Ð margin: $margin / 2;Ð
border-color: $blue;ÐÐ@mixin table-base {Ð th {Ð text-align: center;Ð font-
weight: bold;Ð }Ð td, th {padding: 2px}ÐÐtable.hl {Ð margin: 2em 0;Ð td.ln {Ð
  text-align: right;Ð }ÐÐli {Ð font: {Ð family: serif;Ð weight: bold;Ð
size: 1.2em;Ð }ÐÐ@mixin left($dist) {Ð float: left;Ð margin-left: $dist;ÐÐdata
{Ð @include left(10px);Ð @include table-base;ÐÐsource {Ð @include flow-
into(target);Ð border: 10px solid green;Ð margin: 20px;Ð width: 200px; }Ðnew-
container {Ð @include flow-from(target);Ð border: 10px solid red;Ð margin:
20px;Ð width: 200px; }Ðbody {Ð margin: 0;Ð padding: 3em 6em;Ð font-family:
tahoma, arial, sans-serif;Ð color: #000;ÐÐ@mixin yellow() {Ð background:
yellow;ÐÐbig {Ð font-size: 14px;ÐÐnested {Ð @include border-radius(3px);Ð
@extend .big;Ð p {Ð background: whitesmoke;Ð a {Ð color: red;Ð }Ð }ÐÐ
#navigation a {Ð font-weight: bold;Ð text-decoration: none !important;ÐÐh1 {Ð
font-size: 2.5em;ÐÐh2 {Ð font-size: 1.7em;ÐÐh1:before, h2:before {Ð content:
"::";ÐÐcode {Ð font-family: courier, monospace;Ð font-size: 80%;Ð color:
#418A8A;ÐÐ/textarea></form>Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð matchBrackets: true,Ð mode: "text/x-scss"Ð
  });Ð </script>Ð The SCSS mode is a sub-mode of the <a
href="index.html">CSS mode</a> (defined in <code>css.js</code>. Ð
Parsing/Highlighting Tests: <a href="../../test/
index.html#scss_*">normal</a>, <a href="../../test/
index.html#verbose,scss_*">verbose</a>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\cypher\index.html

```
<!doctype html>Ðtitle>CodeMirror: Cypher Mode for CodeMirror</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css" />Ðlink rel="stylesheet"
href="../../theme/neo.css" />Ðscript src="../../lib/codemirror.js"></script>Ð
<script src="cypher.js"></script>Ðstyle>ÐCodeMirror {Ð   border-top: 1px
solid black;Ð   border-bottom: 1px solid black;ÐÐ       </style>Ðdiv id=nav>Ð
<a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../
doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Cypher Mode
for CodeMirror</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Cypher Mode for CodeMirror</h2>Ð
<form>Ð           <textarea id="code" name="code">// Cypher Mode for
CodeMirror, using the neo themeÐMATCH (joe { name: 'Joe' })-[:knows*2..2]-
(friend_of_friend)ÐWHERE NOT (joe)-[:knows]-(friend_of_friend)ÐRETURN
friend_of_friend.name, COUNT(*)ÐORDER BY COUNT(*) DESC , friend_of_friend.nameÐ
</textarea>Ð           </form>Ð           <p><strong>MIME types defined:</
strong> Ð           <code><a href="?mime=application/x-cypher-
query">application/x-cypher-query</a></code>Ð       </p>Ðscript>Ðwindow.onload
= function() {Ð var mime = 'application/x-cypher-query';Ð // get mime typeÐ
if (window.location.href.indexOf('mime=') > -1) {Ð   mime =
window.location.href.substr(window.location.href.indexOf('mime=') + 5);Ð }Ð
window.editor = CodeMirror.fromTextArea(document.getElementById('code'), {Ð
mode: mime,Ð   indentWithTabs: true,Ð   smartIndent: true,Ð   lineNumbers:
true,Ð   matchBrackets : true,Ð   autofocus: true,Ð   theme: 'neo'Ð });Ð};Ð/
script>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\d\index.html

<!doctype html>Ðtitle>CodeMirror: D mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript src="d.js"></script>Ð <style>.CodeMirror {border: 2px inset #dee;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">D</a>Ð </ul>Ð/div>Ðarticle>Ðh2>D mode</h2>Ðform><textarea id="code" name="code">Ð/* D demo code // copied from phobos/sd/metastrings.d */Ð// Written in the D programming language.Ð/**Ðemplates with which to do compile-time manipulation of strings.Ð Macros:ÐWIKI = Phobos/StdMetastringsÐCopyright: Copyright Digital Mars 2007 - 2009.Ðicense: <a href="http://www.boost.org/LICENSE_1_0.txt">Boost License 1.0</a>.ÐAuthors: $(WEB digitalmars.com, Walter Bright),Ð Don ClugstonÐSource: $(PHOBOSSRC std/_metastrings.d)Ð*/Ð/*Ð Copyright Digital Mars 2007 - 2009.Ðistributed under the Boost Software License, Version 1.0.Ð (See accompanying file LICENSE_1_0.txt or copy atÐ http://www.boost.org/LICENSE_1_0.txt)Ð*/Ðodule std.metastrings;Ð/**ÐFormats constants into a string at compile time. Analogous to $(XREFÐstring,format).Ð Parameters:Ð = tuple of constants, which can be strings, characters, or integralÐ values.ÐFormats:Ð* The formats supported are %s for strings, and %%Ð* for the % character.ÐExample:Ð--Ðmport std.metastrings;Ðmport std.stdio;Ðoid main()ÐÐ{Ð string s = Format!("Arg %s = %s", "foo", 27);Ð writefln(s); // "Arg foo = 27"ÐÐ}Ð/* ---Ð*/Ðemplate Format(A...)ÐÐ{Ð static if (A.length == 0)Ð enum Format = "";Ð else static if (is(typeof(A[0]) : const(char)[]))Ð enum Format = FormatString!(A[0], A[1..$]);Ð elseÐ enum Format = toStringNow!(A[0]) ~ Format!(A[1..$]);ÐÐ}Ðemplate FormatString(const(char)[] F, A...)ÐÐ{Ð static if (F.length == 0)Ð enum FormatString = Format!(A);Ð else static if (F.length == 1)Ð enum FormatString = F[0] ~ Format!(A);Ð else static if (F[0..2] == "%s")Ð enum FormatStringÐ = toStringNow!(A[0]) ~ FormatString!(F[2..$],A[1..$]);Ð else static if (F[0..2] == "%%")Ð enum FormatString = "%" ~ FormatString!(F[2..$],A);Ð elseÐ {Ð static assert(F[0] != '%', "unrecognized format %" ~ F[1]);Ð enum FormatString = F[0] ~ FormatString!(F[1..$],A);Ð }ÐÐ}ÐunittestÐ{Ð auto s = Format!("hel%slo", "world", -138, 'c', true);Ð assert(s == "helworldlo-138ctrue", "[" ~ s ~ "]");ÐÐ}Ð/**Ð* Convert constant argument to a string.Ð*/Ðemplate toStringNow(ulong v)ÐÐ{Ð static if (v < 10)Ð enum toStringNow = "" ~ cast(char)(v + '0');Ð elseÐ enum toStringNow = toStringNow!(v / 10) ~ toStringNow!(v % 10);ÐÐ}ÐunittestÐ{Ð static assert(toStringNow!(1uL << 62) == "4611686018427387904");ÐÐ}Ð// dittoÐemplate toStringNow(long v)ÐÐ{Ð static if (v < 0)Ð enum toStringNow = "-" ~ toStringNow!(cast(ulong) -v);Ð elseÐ enum toStringNow = toStringNow!(cast(ulong) v);ÐÐ}ÐunittestÐ{Ð static assert(toStringNow!(0x100000000) == "4294967296");Ð static assert(toStringNow!(-138L) == "-138");ÐÐ}Ð// dittoÐemplate toStringNow(uint U)ÐÐ{Ð enum toStringNow = toStringNow!(cast(ulong)U);ÐÐ}Ð// dittoÐemplate toStringNow(int I)ÐÐ{Ð enum toStringNow = toStringNow!(cast(long)I);ÐÐ}Ð// dittoÐ template toStringNow(bool B)ÐÐ{Ð enum toStringNow = B ? "true" : "false";ÐÐ}Ð// dittoÐemplate toStringNow(string S)ÐÐ{Ð enum toStringNow = S;ÐÐ}Ð// dittoÐ template toStringNow(char C)ÐÐ{Ð enum toStringNow = "" ~ C;ÐÐ}Ð********Ð* Parse unsigned integer literal from the start of string s.Ð* returns:Ð* .value = the integer literal as a string,Ð* .rest = the string following the integer literalÐ* Otherwise:Ð* .value = null,Ð* .rest = sÐ*/Ðemplate parseUinteger(const(char)[] s)ÐÐ{Ð static if (s.length == 0)Ð {Ð enum value = "";Ð enum rest = "";Ð }Ð else static if (s[0] >= '0' && s[0] <= '9')Ð {Ð enum value = s[0] ~ parseUinteger!(s[1..$]).value;Ð enum rest = parseUinteger!(s[1..$]).rest;Ð

```
                                                        }Ð   elseÐ   {Ð
enum value = "";Ð       enum rest = s;Ð   }ÐÐ**********Ð parse integer literal
optionally preceded by $(D '-') from the startÐ of string $(D s).Ð returns:Ð
   .value = the integer literal as a string,Ð  .rest = the string following
the integer literalÐ otherwise:Ð  .value = null,Ð  .rest = sÐ */Ð template
parseInteger(const(char)[] s)ÐÐ{ÐÐ   static if (s.length == 0)Ð   {Ð       enum
value = "";Ð       enum rest = "";Ð   }Ð   else static if (s[0] >= '0' &&
s[0] <= '9')Ð   {Ð       enum value = s[0] ~ parseUinteger!(s[1..$]).value;Ð
        enum rest = parseUinteger!(s[1..$]).rest;Ð   }Ð   else static if
(s.length >= 2 &&Ð           s[0] == '-' && s[1] >= '0' && s[1] <= '9')Ð   {Ð
        enum value = s[0..2] ~ parseUinteger!(s[2..$]).value;Ð       enum
rest = parseUinteger!(s[2..$]).rest;Ð   }Ð   elseÐ   {Ð       enum value = "";Ð
        enum rest = s;Ð   }ÐÐ}ÐÐunittestÐÐ{ÐÐ   assert(parseUinteger!
("1234abc").value == "1234");Ð   assert(parseUinteger!("1234abc").rest ==
"abc");Ð   assert(parseInteger!("-1234abc").value == "-1234");Ð
assert(parseInteger!("-1234abc").rest == "abc");ÐÐ}ÐÐ**Ð Deprecated aliases held
for backward compatibility.Ð */Ð deprecated alias toStringNow ToString;Ð// DittoÐ
deprecated alias parseUinteger ParseUinteger;Ð// DittoÐ deprecated alias
parseUinteger ParseInteger;Ð</textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       indentUnit: 4,Ð
mode: "text/x-d"Ð     });Ð   </script>Ð   <p>Simple mode that handle D-Syntax
(<a href="http://www.dlang.org">DLang Homepage</a>).</p>Ð   <p><strong>MIME
types defined:</strong> <code>text/x-d</code>Ð   .</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\diff\index.html


```
<!doctype html>Ðtitle>CodeMirror: Diff mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="diff.js"></script>Ðstyle>Ð     .CodeMirror {border-top:
1px solid #ddd; border-bottom: 1px solid #ddd;}Ð     span.cm-meta {color:
#a0b !important;}Ð     span.cm-error { background-color: black; opacity: 0.4;}Ð
      span.cm-error.cm-string { background-color: red; }Ð     span.cm-
error.cm-tag { background-color: #2b2; }Ð   </style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Diff</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>Diff mode</h2>Ðform><textarea id="code" name="code">Ðdiff --
git a/index.html b/index.htmlÐindex c1d9156..7764744 100644Ð-- a/index.htmlÐ++
b/index.htmlÐ@@ -95,7 +95,8 @@ StringStream.prototype = {Ð    <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
         lineNumbers: true,Ð        autoMatchBrackets: trueÐ
autoMatchBrackets: true,Ð      onGutterClick: function(x){console.log(x);}Ð
       });Ð    </script>Ð  </body>Ðdiff --git a/lib/codemirror.js b/lib/
codemirror.jsÐindex 04646a9..9a39cc7 100644Ð-- a/lib/codemirror.jsÐ++ b/lib/
codemirror.jsÐ@@ -399,10 +399,16 @@ var CodeMirror = (function() {Ð    }ÐÐ
function onMouseDown(e) {Ð      var start = posFromMouse(e), last = start;    Ð
+      var start = posFromMouse(e), last = start, target = e.target();Ð
if (!start) return;Ð      setCursor(start.line, start.ch, false);Ð      if
(e.button() != 1) return;Ð      if (target.parentNode == gutter) {    Ð
+        if (options.onGutterClick)Ð
options.onGutterClick(indexOf(gutter.childNodes, target) + showingFrom);Ð
+        return;Ð      }ÐÐ      if (!focused) onFocus();ÐÐ      e.stop();Ð@@
-808,7 +814,7 @@ var CodeMirror = (function() {Ð      for (var i =
showingFrom; i < showingTo; ++i) {Ð        var marker = lines[i].gutterMarker;Ð
         if (marker) html.push('<div class="' + marker.style + '">' +
htmlEscape(marker.text) + '</div>');Ð        else html.push("<div>" +
(options.lineNumbers ? i + 1 : "\u00a0") + "</div>");Ð        else
html.push("<div>" + (options.lineNumbers ? i + options.firstLineNumber :
"\u00a0") + "</div>");Ð      }Ð      gutter.style.display = "none"; // TODO
test whether this actually helpsÐ      gutter.innerHTML = html.join("");Ð@@
-1371,10 +1377,8 @@ var CodeMirror = (function() {Ð        if (option ==
"parser") setParser(value);Ð        else if (option === "lineNumbers")
setLineNumbers(value);Ð        else if (option === "gutter") setGutter(value);Ð
-        else if (option === "readOnly") options.readOnly = value;Ð
else if (option === "indentUnit") {options.indentUnit = indentUnit = value;
setParser(options.parser);}Ð        else if (/^(?:enterMode|tabMode|
indentWithTabs|readOnly|autoMatchBrackets|undoDepth)$/.test(option))
options[option] = value;Ð        else throw new Error("Can't set option " +
option);Ð        else if (option === "indentUnit") {options.indentUnit =
value; setParser(options.parser);}Ð        else options[option] = value;Ð
       },Ð      cursorCoords: cursorCoords,Ð      undo: operation(undo),Ð@@
-1402,7 +1406,8 @@ var CodeMirror = (function() {Ð      replaceRange:
operation(replaceRange),ÐÐ      operation: function(f){return operation(f)
();},Ð      refresh: function(){updateDisplay([{from: 0, to: lines.length}]);}Ð
+      refresh: function(){updateDisplay([{from: 0, to: lines.length}]);},Ð
+      getInputField: function(){return input;}Ð    };Ð    return instance;Ð
   }Ð@@ -1420,6 +1425,7 @@ var CodeMirror = (function() {Ð    readOnly: false,Ð
     onChange: null,Ð    onCursorActivity: null,Ð    onGutterClick: null,Ð
autoMatchBrackets: false,Ð    workTime: 200,Ð    workDelay: 300,Ð/textarea></
form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-diff</code>.</p>Ð
```

Ð </article>Ð

public\assets\js\plugins\codemirror\mode\django\index.html

```
<!doctype html>Đtitle>CodeMirror: Django template mode</title>Đmeta
charset="utf-8"/>Đlink rel=stylesheet href="../../doc/docs.css">Đlink
rel="stylesheet" href="../../lib/codemirror.css">Đscript src="../../lib/
codemirror.js"></script>Đscript src="../../addon/mode/overlay.js"></script>Đ
<script src="../xml/xml.js"></script>Đscript src="../htmlmixed/
htmlmixed.js"></script>Đscript src="django.js"></script>Đstyle type="text/
css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid
black;}</style>Đdiv id=nav>Đ <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Đ <ul>Đ   <li><a href="../../
index.html">Home</a>Đ   <li><a href="../../doc/manual.html">Manual</a>Đ
<li><a href="https://github.com/codemirror/codemirror">Code</a>Đ </ul>Đ <ul>Đ
    <li><a href="../index.html">Language modes</a>Đ   <li><a class=active
href="#">Django</a>Đ </ul>Đ/div>Đarticle>Đh2>Django template mode</h2>Đ
<form><textarea id="code" name="code">Đ!doctype html>Đhtml>Đ   <head>Đ
<title>My Django web application</title>Đ   </head>Đ   <body>Đ       <h1>Đ
            {{ page.title }}Đ       </h1>Đ       <ul class="my-list">Đ
            {% for item in items %}Đ               <li>{% item.name %}</li>Đ
            {% empty %}Đ               <li>You have no items in your list.</
li>Đ           {% endfor %}Đ       </ul>Đ   </body>Đ/html>Đ/textarea></form>Đ
    <script>Đ     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Đ
lineNumbers: true,Đ       mode: "django",Đ       indentUnit: 4,Đ
indentWithTabs: trueĐ     });Đ   </script>Đ   <p>Mode for HTML with embedded
Django template markup.</p>Đ   <p><strong>MIME types defined:</strong>
<code>text/x-django</code></p>Đ </article>Đ
```

public\assets\js\plugins\codemirror\mode\dtd\index.html


```
<!doctype html>Ðtitle>CodeMirror: DTD mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="dtd.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">DTD</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>DTD mode</h2>Ðform><textarea id="code" name="code"><?xml
version="1.0" encoding="UTF-8"?>Ð!ATTLIST titleÐ xmlns”4D D #FIXED’&‡GG ¢òð
docbook.org/ns/docbook"Ð role”4D D #IMPLIEDÐ%db.common.attributes;Ð
%db.common.linking.attributes;ÐÐ!--Ð Ð Try: http://docbook.org/xml/5.0/dtd/
docbook.dtdÐ->Ð!DOCTYPE xsl:stylesheetÐ [Ð   <!ENTITY nbsp   "&amp;#160;">Ð
<!ENTITY copy   "&amp;#169;">Ð   <!ENTITY reg    "&amp;#174;">Ð   <!ENTITY
trade  "&amp;#8482;">Ð   <!ENTITY mdash  "&amp;#8212;">Ð   <!ENTITY ldquo
"&amp;#8220;">Ð   <!ENTITY rdquo  "&amp;#8221;">Ð   <!ENTITY pound
"&amp;#163;">Ð   <!ENTITY yen    "&amp;#165;">Ð   <!ENTITY euro
"&amp;#8364;">Ð   <!ENTITY mathml "http://www.w3.org/1998/Math/MathML">Ð ]ÐÐ!
ELEMENT title (#PCDATA|inlinemediaobject|remark|superscript|subscript|xref|
link|olink|anchor|biblioref|alt|annotation|indexterm|abbrev|acronym|date|
emphasis|footnote|footnoteref|foreignphrase|phrase|quote|wordasword|firstterm|
glossterm|coref|trademark|productnumber|productname|database|application|
hardware|citation|citerefentry|citetitle|citebiblioid|author|person|
personname|org|orgname|editor|jobtitle|replaceable|package|parameter|termdef|
nonterminal|systemitem|option|optional|property|inlineequation|tag|markup|
token|symbol|literal|code|constant|email|uri|guiicon|guibutton|guimenuitem|
guimenu|guisubmenu|guilabel|menuchoice|mousebutton|keycombo|keycap|keycode|
keysym|shortcut|accel|prompt|envar|filename|command|computeroutput|userinput|
function|varname|returnvalue|type|classname|exceptionname|interfacename|
methodname|modifier|initializer|ooclass|ooexception|oointerface|errorcode|
errortext|errorname|errortype)*>Ð!ENTITY % db.common.attributes "Ð xml:id””I
#IMPLIEDÐ version”4D D #IMPLIEDÐxml:lang”4D D #IMPLIEDÐxml:base”4D D #IMPLIEDÐ
remap”4D D #IMPLIEDÐxreflabel”4D D #IMPLIEDÐrevisionflag’†6† ævVGÆ FFVGÀ
deleted|off)’4”Õ Ä”TM dir’†ÇG'Ç'FÇÆÇ&÷Ç&Æò™#IMPLIEDÐarch”4D D #IMPLIEDÐ
audience”4D D #IMPLIEDÐcondition”4D D #IMPLIEDÐconformance”4D D #IMPLIEDÐos•
CDATA’4”Õ Ä”TM revision”4D D #IMPLIEDÐsecurity”4D D #IMPLIEDÐuserlevel”4D D
#IMPLIEDÐ vendor”4D D #IMPLIEDÐwordsize”4D D #IMPLIEDÐannotations”4D D #IMPLIEÐÐ
"></textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
{name: "dtd", alignCDATA: true},Ð       lineNumbers: true,Ð
lineWrapping: trueÐ     });Ð   </script>Ð   <p><strong>MIME types defined:</
strong> <code>application/xml-dtd</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\dylan\index.html


```
<!doctype html>Ðtitle>CodeMirror: Dylan mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="../../addon/comment/continuecomment.js"></script>Ðscript src="../../
addon/comment/comment.js"></script>Ðscript src="dylan.js"></script>Ðstyle
type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px
solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Dylan</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Dylan mode</h2>Ðdiv><textarea id="code" name="code">ÐModule:
locators-internalsÐSynopsis:     Abstract modeling of locationsÐAuthor:
Andy ArmstrongÐCopyright:    Original Code is Copyright (c) 1995-2004
Functional Objects, Inc.Ð             All rights reserved.ÐLicense:      See
License.txt in this distribution for details.ÐWarranty:     Distributed
WITHOUT WARRANTY OF ANY KINDÐdefine open generic locator-serverÐ   (locator ::
<locator>) => (server :: false-or(<server-locator>));Ðdefine open generic
locator-hostÐ   (locator :: <locator>) => (host :: false-or(<string>));Ðdefine
open generic locator-volumeÐ   (locator :: <locator>) => (volume :: false-
or(<string>));Ðdefine open generic locator-directoryÐ   (locator :: <locator>)
=> (directory :: false-or(<directory-locator>));Ðdefine open generic locator-
relative?Ð   (locator :: <locator>) => (relative? :: <boolean>);Ðdefine open
generic locator-pathÐ   (locator :: <locator>) => (path :: <sequence>);Ðdefine
open generic locator-baseÐ   (locator :: <locator>) => (base :: false-
or(<string>));Ðdefine open generic locator-extensionÐ   (locator :: <locator>)
=> (extension :: false-or(<string>));Ð// Locator classesÐdefine open abstract
class <directory-locator> (<physical-locator>)Ðend class <directory-locator>;Ð
define open abstract class <file-locator> (<physical-locator>)Ðend class <file-
locator>;Ðdefine method asÐ   (class == <directory-locator>, string ::
<string>)Ð=> (locator :: <directory-locator>)Ð as(<native-directory-locator>,
string)Ðend method as;Ðdefine method makeÐ   (class == <directory-locator>,Ð
#key server :: false-or(<server-locator>) = #f,Ð         path :: <sequence> =
#[],Ð         relative? :: <boolean> = #f,Ð         name :: false-
or(<string>) = #f)Ð=> (locator :: <directory-locator>)Ð make(<native-
directory-locator>,Ð      server:    server,Ð      path:      path,Ð
relative?: relative?,Ð      name:      name)Ðend method make;Ðdefine method asÐ
    (class == <file-locator>, string :: <string>)Ð=> (locator :: <file-
locator>)Ð as(<native-file-locator>, string)Ðend method as;Ðdefine method makeÐ
    (class == <file-locator>,Ð    #key directory :: false-or(<directory-
locator>) = #f,Ð         base :: false-or(<string>) = #f,Ð
extension :: false-or(<string>) = #f,Ð         name :: false-or(<string>) =
#f)Ð=> (locator :: <file-locator>)Ð make(<native-file-locator>,Ð
directory: directory,Ð      base:      base,Ð      extension: extension,Ð
       name:      name)Ðend method make;Ð// Locator coercionÐ//---*** andrewa:
This caching scheme doesn't work yet, so disable it.Ðdefine constant $cache-
locators?        = #f;Ðdefine constant $cache-locator-strings? = #f;Ðdefine
constant $locator-to-string-cache = make(<object-table>, weak: #"key");Ðdefine
constant $string-to-locator-cache = make(<string-table>, weak: #"value");Ð
define open generic locator-as-stringÐ   (class :: subclass(<string>),
locator :: <locator>)Ð=> (string :: <string>);Ðdefine open generic string-as-
locatorÐ   (class :: subclass(<locator>), string :: <string>)Ð=> (locator ::
<locator>);Ðdefine sealed sideways method asÐ   (class :: subclass(<string>),
locator :: <locator>)Ð=> (string :: <string>)Ð let string = element($locator-
to-string-cache, locator, default: #f);Ð if (string)Ð   as(class, string)Ð
elseÐ   let string = locator-as-string(class, locator);Ð   if ($cache-locator-
strings?)Ð
```

element($locator-to-string-cache, locator) := string;Ð elseÐ
stringÐ endÐ endÐnd method as;Ðefine sealed sideways method asÐ
(class :: subclass(<locator>), string :: <string>)Ð=> (locator :: <locator>)Ð
let locator = element($string-to-locator-cache, string, default: #f);Ð if
(instance?(locator, class))Ð locatorÐ elseÐ let locator = string-as-
locator(class, string);Ð if ($cache-locators?)Ð element($string-to-
locator-cache, string) := locator;Ð elseÐ locatorÐ endÐ endÐnd method
as;Ð// Locator conditionsÐefine class <locator-error> (<format-string-
condition>, <error>)Ðnd class <locator-error>;Ðefine function locator-errorÐ
(format-string :: <string>, #rest format-arguments)Ð error(make(<locator-
error>, Ð format-string: format-string,Ð format-
arguments: format-arguments))Ðnd function locator-error;Ð// Useful locator
protocolsÐefine open generic locator-testÐ (locator :: <directory-locator>)
=> (test :: <function>);Ðefine method locator-testÐ (locator :: <directory-
locator>) => (test :: <function>)Ð \=Ðnd method locator-test;Ðefine open
generic locator-might-have-links?Ð (locator :: <directory-locator>) =>
(links? :: <boolean>);Ðefine method locator-might-have-links?Ð (locator ::
<directory-locator>) => (links? :: singleton(#f))Ð #fÐnd method locator-might-
have-links?;Ðefine method locator-relative?Ð (locator :: <file-locator>) =>
(relative? :: <boolean>)Ð let directory = locator.locator-directory;Ð
~directory | directory.locator-relative?Ðnd method locator-relative?;Ðefine
method current-directory-locator?Ð (locator :: <directory-locator>) =>
(current-directory? :: <boolean>)Ð locator.locator-relative?Ð &
locator.locator-path = #["self"]Ðnd method current-directory-locator?;Ðefine
method locator-directoryÐ (locator :: <directory-locator>) => (parent ::
false-or(<directory-locator>))Ð let path = locator.locator-path;Ð unless
(empty?(path))Ð make(object-class(locator),Ð server:
locator.locator-server,Ð path: copy-sequence(path, end: path.size
- 1),Ð relative?: locator.locator-relative?)Ð endÐnd method locator-
directory;Ð// Simplify locatorÐefine open generic simplify-locatorÐ
(locator :: <physical-locator>)Ð=> (simplified-locator :: <physical-locator>);Ð
define method simplify-locatorÐ (locator :: <directory-locator>)Ð=>
(simplified-locator :: <directory-locator>)Ð let path = locator.locator-path;Ð
let relative? = locator.locator-relative?;Ð let resolve-parent? =
~locator.locator-might-have-links?;Ð let simplified-pathÐ = simplify-
path(path, Ð resolve-parent?: resolve-parent?,Ð
relative?: relative?);Ð if (path ~= simplified-path)Ð
make(object-class(locator),Ð server: locator.locator-server,Ð
path: simplified-path,Ð relative?: locator.locator-
relative?)Ð elseÐ locatorÐ endÐ endÐnd method simplify-locator;Ðefine method
simplify-locatorÐ (locator :: <file-locator>) => (simplified-locator ::
<file-locator>)Ð let directory = locator.locator-directory;Ð let simplified-
directory = directory & simplify-locator(directory);Ð if (directory ~=
simplified-directory)Ð make(object-class(locator),Ð directory:
simplified-directory,Ð base: locator.locator-base,Ð
extension: locator.locator-extension)Ð elseÐ locatorÐ endÐ endÐnd method
simplify-locator;Ð// Subdirectory locatorÐefine open generic subdirectory-
locatorÐ (locator :: <directory-locator>, #rest sub-path)Ð=>
(subdirectory :: <directory-locator>);Ðefine method subdirectory-locatorÐ
(locator :: <directory-locator>, #rest sub-path)Ð=> (subdirectory ::
<directory-locator>)Ð let old-path = locator.locator-path;Ð let new-path =
concatenate-as(<simple-object-vector>, old-path, sub-path);Ð make(object-
class(locator),Ð server: locator.locator-server,Ð path: new-
path,Ð relative?: locator.locator-relative?)Ð endÐnd method subdirectory-
locator;Ð// Relative locatorÐefine open generic relative-locatorÐ
(locator :: <physical-locator>, from-locator :: <physical-locator>)Ð=>
(relative-locator :: <physical-locator>);Ðefine method relative-locatorÐ
(locator :: <directory-locator>, from-locator :: <directory-locator>)Ð=>
(relative-locator :: <directory-locator>)Ð let path = locator.locator-path;Ð
let from-path = from-locator.locator-path;Ð

```
                                                caseÐ   ~locator.locator-
relative? & from-locator.locator-relative? =>Ð     locator-errorÐ
("Cannot find relative path of absolute locator %= from relative locator %=",Ð
         locator, from-locator);Ð   locator.locator-server ~= from-
locator.locator-server =>Ð     locator;Ð   path = from-path =>Ð
make(object-class(locator),Ð          path: vector(#"self"),Ð
relative?: #t);Ð   otherwise =>Ð     make(object-class(locator),Ð
path: relative-path(path, from-path, test: locator.locator-test),Ð
relative?: #t);Ð endÐend method relative-locator;Ðdefine method relative-locatorÐ
    (locator :: <file-locator>, from-directory :: <directory-locator>)Ð=>
(relative-locator :: <file-locator>)Ð let directory = locator.locator-
directory;Ð let relative-directory = directory & relative-locator(directory,
from-directory);Ð if (relative-directory ~= directory)Ð   simplify-locatorÐ
      (make(object-class(locator),Ð           directory: relative-directory,Ð
            base:      locator.locator-base,Ð           extension:
locator.locator-extension))Ð elseÐ   locatorÐ endÐend method relative-locator;Ð
define method relative-locatorÐ   (locator :: <physical-locator>, from-
locator :: <file-locator>)Ð=> (relative-locator :: <physical-locator>)Ð let
from-directory = from-locator.locator-directory;Ð caseÐ   from-directory =>Ð
      relative-locator(locator, from-directory);Ð   ~locator.locator-
relative? =>Ð     locator-errorÐ       ("Cannot find relative path of
absolute locator %= from relative locator %=",Ð        locator, from-locator);Ð
    otherwise =>Ð     locator;Ð endÐend method relative-locator;Ð// Merge
locatorsÐdefine open generic merge-locatorsÐ   (locator :: <physical-locator>,
from-locator :: <physical-locator>)Ð=> (merged-locator :: <physical-locator>);Ð
/// Merge locatorsÐdefine method merge-locatorsÐ   (locator :: <directory-
locator>, from-locator :: <directory-locator>)Ð=> (merged-locator ::
<directory-locator>)Ð if (locator.locator-relative?)Ð   let path =
concatenate(from-locator.locator-path, locator.locator-path);Ð   simplify-
locatorÐ     (make(object-class(locator),Ð           server:    from-
locator.locator-server,Ð           path:      path,Ð           relative?:
from-locator.locator-relative?))Ð elseÐ   locatorÐ endÐend method merge-
locators;Ðdefine method merge-locatorsÐ   (locator :: <file-locator>, from-
locator :: <directory-locator>)Ð=> (merged-locator :: <file-locator>)Ð let
directory = locator.locator-directory;Ð let merged-directory Ð   = if
(directory)Ð       merge-locators(directory, from-locator)Ð     elseÐ
simplify-locator(from-locator)Ð     end;Ð if (merged-directory ~= directory)Ð
    make(object-class(locator),Ð        directory: merged-directory,Ð
base:      locator.locator-base,Ð        extension: locator.locator-extension)Ð
  elseÐ   locatorÐ endÐend method merge-locators;Ðdefine method merge-locatorsÐ
    (locator :: <physical-locator>, from-locator :: <file-locator>)Ð=>
(merged-locator :: <physical-locator>)Ð let from-directory = from-
locator.locator-directory;Ð if (from-directory)Ð   merge-locators(locator,
from-directory)Ð elseÐ   locatorÐ endÐend method merge-locators;Ð// Locator
protocolsÐdefine sideways method supports-open-locator?Ð   (locator :: <file-
locator>) => (openable? :: <boolean>)Ð ~locator.locator-relative?Ðend method
supports-open-locator?;Ðdefine sideways method open-locatorÐ   (locator ::
<file-locator>, #rest keywords, #key, #all-keys)Ð=> (stream :: <stream>)Ð
apply(open-file-stream, locator, keywords)Ðend method open-locator;Ð</
textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: "text/
x-dylan",Ð       lineNumbers: true,Ð       matchBrackets: true,Ð
continueComments: "Enter",Ð       extraKeys: {"Ctrl-Q": "toggleComment"},Ð
        tabMode: "indent",Ð       indentUnit: 2Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-dylan</code>.</p>Ð</
article>Ð
```

public\assets\js\plugins\codemirror\mode\ecl\index.html


```
<!doctype html>Ðtitle>CodeMirror: ECL mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="ecl.js"></script>Ðstyle>.CodeMirror {border: 1px solid
black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">ECL</a>Ð </ul>Ð/div>Ðarticle>Ðh2>ECL mode</h2>Ðform><textarea
id="code" name="code">Ø*Ðample useless code to demonstrate ecl syntax
highlightingÐthis is a multiline comment!Ð/Ø/  this is a singleline comment!Ð
import ut;Ð := Ð recordÐ  string22 s1 := '123';Ð  integer4 i1 := 123;Ð end;Ð
#option('tmp', true);Ð := dataset('tmp::qb', r, thor);Ðutput(d);Ð/textarea></
form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p>Based on CodeMirror's clike mode.  For more information see <a
href="http://hpccsystems.com">HPCC Systems</a> web site.</p>Ð
<p><strong>MIME types defined:</strong> <code>text/x-ecl</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\eiffel\index.html

```
<!doctype html>Ðtitle>CodeMirror: Eiffel mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
neat.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="eiffel.js"></script>Ðstyle>Ð     .CodeMirror {border-top: 1px solid
black; border-bottom: 1px solid black;}Ð     .cm-s-default span.cm-arrow
{ color: red; }Ð   </style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Eiffel</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Eiffel mode</h2>Ðform><textarea id="code" name="code">ÐnoteÐ
description: "[Ð       Project-wide universal properties.Ð       This class
is an ancestor to all developer-written classes.Ð       ANY may be customized
for individual projects or teams.Ð       ]"Ð   library: "Free implementation
of ELKS library"Ð   status: "See notice at end of class."Ð   legal: "See
notice at end of class."Ð   date: "$Date: 2013-01-25 11:49:00 -0800 (Fri, 25
Jan 2013) $"Ð   revision: "$Revision: 712 $"ÐclassÐ   ANYÐfeature --
CustomizationÐfeature -- AccessÐ   generator: STRINGÐ           -- Name of
current object's generating classÐ           -- (base class of the type of
which it is a direct instance)Ð       externalÐ           "built_in"Ð
ensureÐ           generator_not_void: Result /= VoidÐ
generator_not_empty: not Result.is_emptyÐ       endÐ   generating_type: TYPE
[detachable like Current]Ð           -- Type of current objectÐ           --
(type of which it is a direct instance)Ð       doÐ           Result :=
{detachable like Current}Ð       ensureÐ           generating_type_not_void:
Result /= VoidÐ       endÐfeature -- Status reportÐ   conforms_to (other:
ANY): BOOLEANÐ           -- Does type of current object conform to typeÐ
            -- of `other' (as per Eiffel: The Language, chapter 13)?Ð
requireÐ           other_not_void: other /= VoidÐ       externalÐ
"built_in"Ð       endÐ   same_type (other: ANY): BOOLEANÐ           -- Is
type of current object identical to type of `other'?Ð       requireÐ
            other_not_void: other /= VoidÐ       externalÐ
"built_in"Ð       ensureÐ           definition: Result = (conforms_to (other)
andÐ                                       other.conforms_to (Current))Ð
        endÐfeature -- ComparisonÐ   is_equal (other: like Current): BOOLEANÐ
            -- Is `other' attached to an object considereduÐ           --
equal to current object?Ð       requireÐ           other_not_void: other /=
VoidÐ       externalÐ           "built_in"Ð       ensureÐ
symmetric: Result implies other ~ CurrentÐ           consistent:
standard_is_equal (other) implies ResultÐ       endÐ   frozen
standard_is_equal (other: like Current): BOOLEANÐ           -- Is `other'
attached to an object of the same typeÐ           -- as current object, and
field-by-field identical to it?Ð       requireÐ           other_not_void:
other /= VoidÐ       externalÐ           "built_in"Ð       ensureÐ
same_type: Result implies same_type (other)Ð           symmetric: Result
implies other.standard_is_equal (Current)Ð       endÐ   frozen equal (a:
detachable ANY; b: like a): BOOLEANÐ           -- Are `a' and `b' either both
void or attachedÐ           -- to objects considered equal?Ð       doÐ
            if a = Void thenÐ               Result := b = VoidÐ           elseÐ
                Result := b /= Void and thenÐ
a.is_equal (b)Ð           endÐ       ensureÐ           definition: Result =
(a = Void and b = Void) or elseÐ                       ((a /= Void and b /=
Void) and thenÐ                       a.is_equal (b))Ð       endÐ   frozen
standard_equal (a: detachable ANY; b: like a): BOOLEANÐ           -- Are `a'
and `b' either both void or attached toÐ           -- field-by-field
identical objects of the same type?Ð           -- Always uses default object
comparison criterion.Ð
```

doÐ if a = Void thenÐ
Result := b = VoidÐ elseÐ Result := b /= Void and thenÐ
a.standard_is_equal (b)Ð endÐ
ensureÐ definition: Result = (a = Void and b = Void) or elseÐ
((a /= Void and b /= Void) and thenÐ
a.standard_is_equal (b))Ð endÐ frozen
is_deep_equal (other: like Current): BOOLEANÐ -- Are `Current' and
`other' attached to isomorphic object structures?Ð requireÐ
other_not_void: other /= VoidÐ externalÐ "built_in"Ð
ensureÐ shallow_implies_deep: standard_is_equal (other) implies
ResultÐ same_type: Result implies same_type (other)Ð
symmetric: Result implies other.is_deep_equal (Current)Ð endÐ frozen
deep_equal (a: detachable ANY; b: like a): BOOLEANÐ -- Are `a' and
`b' either both voidÐ -- or attached to isomorphic object
structures?Ð doÐ if a = Void thenÐ Result := b
= VoidÐ elseÐ Result := b /= Void and then
a.is_deep_equal (b)Ð endÐ ensureÐ
shallow_implies_deep: standard_equal (a, b) implies ResultÐ
both_or_none_void: (a = Void) implies (Result = (b = Void))Ð
same_type: (Result and (a /= Void)) implies (b /= Void and then a.same_type
(b))Ð symmetric: Result implies deep_equal (b, a)Ð endÐfeature
-- DuplicationÐ frozen twin: like CurrentÐ -- New object equal to
`Current'Ð -- `twin' calls `copy'; to change copying/twinning
semantics, redefine `copy'.Ð externalÐ "built_in"Ð
ensureÐ twin_not_void: Result /= VoidÐ is_equal: Result ~
CurrentÐ endÐ copy (other: like Current)Ð -- Update current
object using fields of object attachedÐ -- to `other', so as to
yield equal objects.Ð requireÐ other_not_void: other /= VoidÐ
type_identity: same_type (other)Ð externalÐ
"built_in"Ð ensureÐ is_equal: Current ~ otherÐ endÐ
frozen standard_copy (other: like Current)Ð -- Copy every field of
`other' onto corresponding fieldÐ -- of current object.Ð
requireÐ other_not_void: other /= VoidÐ type_identity:
same_type (other)Ð externalÐ "built_in"Ð ensureÐ
is_standard_equal: standard_is_equal (other)Ð endÐ frozen
clone (other: detachable ANY): like otherÐ -- Void if `other' is
void; otherwise new objectÐ -- equal to `other'Ð --Ð
-- For non-void `other', `clone' calls `copy';Ð -- to
change copying/cloning semantics, redefine `copy'.Ð obsoleteÐ
"Use `twin' instead."Ð doÐ if other /= Void thenÐ
Result := other.twinÐ endÐ ensureÐ
equal: Result ~ otherÐ endÐ frozen standard_clone (other: detachable
ANY): like otherÐ -- Void if `other' is void; otherwise new objectÐ
-- field-by-field identical to `other'.Ð -- Always uses
default copying semantics.Ð obsoleteÐ "Use `standard_twin'
instead."Ð doÐ if other /= Void thenÐ Result :=
other.standard_twinÐ endÐ ensureÐ equal:
standard_equal (Result, other)Ð endÐ frozen standard_twin: like
CurrentÐ -- New object field-by-field identical to `other'.Ð
-- Always uses default copying semantics.Ð externalÐ
"built_in"Ð ensureÐ standard_twin_not_void:
Result /= VoidÐ equal: standard_equal (Result, Current)Ð endÐ
frozen deep_twin: like CurrentÐ -- New object structure
recursively duplicated from Current.Ð externalÐ "built_in"Ð
ensureÐ deep_twin_not_void: Result /= VoidÐ
deep_equal: deep_equal (Current, Result)Ð endÐ frozen deep_clone
(other: detachable ANY): like otherÐ -- Void if `other' is void:
otherwise, new object structureÐ -- recursively duplicated from the
one attached to `other'Ð obsoleteÐ "Use `deep_twin' instead."Ð
doÐ

if other /= Void thenÐ Result :=
other.deep_twinÐ endÐ ensureÐ deep_equal:
deep_equal (other, Result)Ð endÐ frozen deep_copy (other: like
Current)Ð -- Effect equivalent to that of:Ð --
`copy' (`other' . `deep_twin')Ð requireÐ other_not_void:
other /= VoidÐ doÐ copy (other.deep_twin)Ð ensureÐ
deep_equal: deep_equal (Current, other)Ð endÐfeature {NONE}
-- RetrievalÐ frozen internal_correct_mismatchÐ -- Called from
runtime to perform a proper dynamic dispatch on `correct_mismatch'Ð
-- from MISMATCH_CORRECTOR.Ð localÐ l_msg: STRINGÐ
l_exc: EXCEPTIONSÐ doÐ if attached {MISMATCH_CORRECTOR}
Current as l_corrector thenÐ l_corrector.correct_mismatchÐ
elseÐ create l_msg.make_from_string ("Mismatch: ")Ð
create l_excÐ l_msg.append
(generating_type.name)Ð l_exc.raise_retrieval_exception (l_msg)Ð
endÐ endÐfeature -- OutputÐ io: STD_FILESÐ --
Handle to standard file setupÐ onceÐ create ResultÐ
Result.set_output_defaultÐ ensureÐ io_not_void: Result /= VoidÐ
endÐ out: STRINGÐ -- New string containing terse
printable representationÐ -- of current objectÐ doÐ
Result := tagged_outÐ ensureÐ out_not_void: Result /= VoidÐ
endÐ frozen tagged_out: STRINGÐ -- New string containing
terse printable representationÐ -- of current objectÐ externalÐ
"built_in"Ð ensureÐ tagged_out_not_void: Result /
= VoidÐ endÐ print (o: detachable ANY)Ð -- Write terse
external representation of `o'Ð -- on standard output.Ð doÐ
if o /= Void thenÐ io.put_string (o.out)Ð
endÐ endÐfeature -- PlatformÐ Operating_environment:
OPERATING_ENVIRONMENTÐ -- Objects available from the operating
systemÐ onceÐ create ResultÐ ensureÐ
operating_environment_not_void: Result /= VoidÐ endÐfeature {NONE} --
InitializationÐ default_createÐ -- Process instances of classes
with no creation clause.Ð -- (Default: do nothing.)Ð doÐ
endÐfeature -- Basic operationsÐ default_rescueÐ --
Process exception for routines with no Rescue clause.Ð -- (Default:
do nothing.)Ð doÐ endÐ frozen do_nothingÐ -- Execute
a null action.Ð doÐ endÐ frozen default: detachable like CurrentÐ
-- Default value of object's typeÐ doÐ endÐ frozen
default_pointer: POINTERÐ -- Default value of type `POINTER'Ð
-- (Avoid the need to write `p'.`default' forÐ -- some
`p' of type `POINTER'.)Ð doÐ ensureÐ -- Result =
Result.defaultÐ endÐ frozen as_attached: attached like CurrentÐ
-- Attached version of CurrentÐ -- (Can be used during
transitional period to convertÐ -- non-void-safe classes to void-
safe ones.)Ð doÐ Result := CurrentÐ endÐinvariantÐ
reflexive_equality: standard_is_equal (Current)Ð reflexive_conformance:
conforms_to (Current)ÐnoteÐ copyright: "Copyright (c) 1984-2012, Eiffel
Software and others"Ð license: "Eiffel Forum License v2 (see http://
www.eiffel.com/licensing/forum.txt)"Ð source: "[Ð Eiffel SoftwareÐ
5949 Hollister Ave., Goleta, CA 93117 USAÐ Telephone
805-685-1006, Fax 805-685-6869Ð Website http://www.eiffel.comÐ
Customer support http://support.eiffel.comÐ]"ÐendÐ/
textarea></form>Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð mode: "text/
x-eiffel",Ð indentUnit: 4,Ð lineNumbers: true,Ð theme:
"neat"Ð });Ð </script>Ð MIME types defined:
<code>text/x-eiffel</code>. ÐÐ Created by <a href="https://github.com/
ynh">YNH</a>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\erlang\index.html

```
<!doctype html>Ðtitle>CodeMirror: Erlang mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
erlang-dark.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="../../addon/edit/matchbrackets.js"></script>Ðscript src="erlang.js"></
script>Ðstyle type="text/css">.CodeMirror {border-top: 1px solid black;
border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Erlang</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Erlang mode</h2>Ðform><textarea id="code" name="code">%% -*- mode:
erlang; erlang-indent-level: 2 -*-%%% Created :  7 May 2012 by mats cronqvist
<masse@klarna.com>%% @docÐ%% Demonstrates how to print a record.%% @endÐ
module('ex').Ðauthor('mats cronqvist').Ðexport([demo/0,Ð        rec_info/1]).Ð
record(demo,{a="One",b="Two",c="Three",d="Four"}).Ðrec_info(demo) ->
record_info(fields,demo).Ðdemo() -> expand_recs(?MODULE,#demo{a="A",b="BB"}).Ð
expand_recs(M,List) when is_list(List) ->Ð [expand_recs(M,L)||L<-List];Ð
expand_recs(M,Tup) when is_tuple(Tup) ->Ð case tuple_size(Tup) ofÐ   L when L
< 1 -> Tup;Ð   L ->Ð     tryÐ       Fields = M:rec_info(element(1,Tup)),Ð
        L = length(Fields)+1,Ð
lists:zip(Fields,expand_recs(M,tl(tuple_to_list(Tup))))Ð     catchÐ       _:_
-> list_to_tuple(expand_recs(M,tuple_to_list(Tup)))Ð     endÐ end;Ð
expand_recs(_,Term) ->Ð Term.Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       extraKeys: {"Tab":
"indentAuto"},Ð       theme: "erlang-dark"Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-erlang</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\fortran\index.html

```
<!doctype html>Ðtitle>CodeMirror: Fortran mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="fortran.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Fortran</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Fortran mode</h2>Ðdiv><textarea id="code" name="code">Ð
Example Fortran codeÐ program averageÐ ! Read in some numbers and take the
averageÐ ! As written, if there are no data points, an average of zero is
returnedÐ ! While this may not be desired behavior, it keeps this example
simpleÐ implicit noneÐ real, dimension(:), allocatable :: pointsÐ
integer                          :: number_of_pointsÐ
real                             :: average_points=0., positive_average=0.,
negative_average=0.Ð write (*,*) "Input number of points to average:"Ð read
(*,*) number_of_pointsÐ allocate (points(number_of_points))Ð write (*,*)
"Enter the points to average:"Ð read  (*,*) pointsÐ ! Take the average by
summing points and dividing by number_of_pointsÐ if (number_of_points > 0)
average_points = sum(points) / number_of_pointsÐ ! Now form average over
positive and negative points onlyÐ if (count(points > 0.) > 0) thenÐ
positive_average = sum(points, points > 0.) / count(points > 0.)Ð end ifÐ if
(count(points < 0.) > 0) thenÐ    negative_average = sum(points, points <
0.) / count(points < 0.)Ð end ifÐ deallocate (points)Ð ! Print result to
terminalÐ write (*,'(a,g12.4)') 'Average = ', average_pointsÐ write
(*,'(a,g12.4)') 'Average of positive points = ', positive_averageÐ write
(*,'(a,g12.4)') 'Average of negative points = ', negative_averageÐ end
program averageÐ/textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       mode: "text/x-fortran"Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-Fortran</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\gas\index.html

```
<!doctype html>Ðtitle>CodeMirror: Gas mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="gas.js"></script>Ðstyle>.CodeMirror {border: 2px inset
#dee;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Gas</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Gas mode</h2>Ðform>Ðtextarea
id="code" name="code">Ðsyntax unifiedÐglobal mainÐ* Ð*  AÐ*  multi-lineÐ*
comment.Ð*/Ð@ A single line comment.Ðmain:Ð       push    {sp, lr}Ð
ldr     r0, =messageÐ       bl      putsÐ       mov     r0, #0Ð       pop
{sp, pc}Ðmessage:Ð       .asciz "Hello world!<br />"Ð/textarea>Ð       </form>Ð
        <script>Ð           var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð               mode: {name: "gas", architecture: "ARMv6"},Ð
            });Ð       </script>Ð       <p>Handles AT&amp;T assembler syntax
(more specifically this handlesÐ       the GNU Assembler (gas) syntax.)Ð
        It takes a single optional configuration parameter:Ð
<code>architecture</code>, which can be one of <code>"ARM"</code>,Ð
<code>"ARMv6"</code> or <code>"x86"</code>.Ð       Including the parameter
adds syntax for the registers and specialÐ       directives for the supplied
architecture.Ð       <p><strong>MIME types defined:</strong> <code>text/x-
gas</code></p>Ð   </article>Ð
```

public\assets\js\plugins\codemirror\mode\gfm\index.html


```
<!doctype html>Ðtitle>CodeMirror: GFM mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/mode/overlay.js"></script>Ðscript src="../xml/
xml.js"></script>Ðscript src="../markdown/markdown.js"></script>Ðscript
src="gfm.js"></script>Ðscript src="../javascript/javascript.js"></script>Ð
<script src="../css/css.js"></script>Ðscript src="../htmlmixed/
htmlmixed.js"></script>Ðscript src="../clike/clike.js"></script>Ðstyle
type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px
solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">GFM</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>GFM mode</h2>Ðform><textarea id="code" name="code">ÐGitHub Flavored
MarkdownÐ========================Ðeverything from markdown plus GFM features:Ð#
URL autolinkingÐunderscores_are_allowed_between_words.Ð# Fenced code blocks
(and syntax highlighting)Ð```javascriptÐfor (var i = 0; i &lt; items.length; i+
+) {Ð   console.log(items[i], i); // log themÐ}Ð```Ð# Task ListsÐ [ ]
Incomplete task list itemÐ [x] **Completed** task list itemÐ# A bit of GitHub
spiceÐ SHA: be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2Ð User@SHA ref:
mojombo@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2Ð User/Project@SHA: mojombo/
god@be6a8cc1c1ecfe9489fb51e4869af15a13fc2cd2Ð \#Num: #1Ð User/#Num: mojombo#1Ð
* User/Project#Num: mojombo/god#1Ðsee http://github.github.com/github-flavored-
markdown/.Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: 'gfm',Ð
        lineNumbers: true,Ð       theme: "default"Ð     });Ð   </script>Ð
<p>Optionally depends on other modes for properly highlighted code blocks.</p>Ð
    <p><strong>Parsing/Highlighting Tests:</strong> <a href="../../test/
index.html#gfm_*">normal</a>,  <a href="../../test/
index.html#verbose,gfm_*">verbose</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\gherkin\index.html


```
<!doctype html>Ðtitle>CodeMirror: Gherkin mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="gherkin.js"></script>Ðstyle>.CodeMirror { border-top: 1px
solid #ddd; border-bottom: 1px solid #ddd; }</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Gherkin</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Gherkin mode</h2>Ðform><textarea id="code" name="code">Ð
Feature: Using GoogleÐ Background: Ð   Something somethingÐ   Something elseÐ
Scenario: Has a homepageÐ   When I navigate to the google home pageÐ   Then
the home page should contain the menu and the search formÐ Scenario:
Searching for a term Ð   When I navigate to the google home pageÐ   When I
search for TofuÐ   Then the search results page is displayedÐ   Then the
search results page contains 10 individual search resultsÐ   Then the search
results contain a link to the wikipedia tofu pageÐ/textarea></form>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-feature</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\go\index.html

<!doctype html>Ðtitle>CodeMirror: Go mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/elegant.css">Ð <script src="../../lib/codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript src="go.js"></script>Ðstyle>.CodeMirror {border:1px solid #999; background:#ffc}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">Go</a>Ð </ul>Ðdiv>Ðarticle>Ðh2>Go mode</h2>Ðform><textarea id="code" name="code">Ð// Prime Sieve in Go.Ð// Taken from the Go specification.Ð// Copyright © The Go Authors.Ðpackage mainÐimport "fmt"Ð// Send the sequence 2, 3, 4, ... to channel 'ch'.Ðfunc generate(ch chan<- int) {Ðf÷" ′ £Ò #² ² ′²² ™½ch <- i // Send 'i' to channel 'ch'.™½ÐÐ// Copy the values from channel 'src' to channel 'dst',Ð// removing those divisible by 'prime'.Ðfunc filter(src <-chan int, dst chan<- int, prime int) {Ðf÷" ′ £Ò & æ›vR 7&2 ² òò Æö÷ ÷fW" f ÇVW2 &V6V—fVB g&öÒ w7&2r™if i%prime != 0 {Ð–G7B fÇC²Ò ′ òò 6VæB v’r Fò 6† ææVÂ vG7Br™1™½ÐÐ// The prime sieve: Daisy-chain filter processes together.Ðfunc sieve() {Ð6, £Ò Ö ¶R†6† â int) // Create a new channel.Ðvò vVæW& FR†6,′ òò 7F 'B vVæW& FR,′ 2 subprocess.Ðf÷" ™½prime := <-ch™Ðfmt.Print(prime, "\n")™Ðh1 := make(chan int)™Ðgo filter(ch, ch1, prime)™Ðch = ch1™½ÐÐfunc main() {Ð6–WfR,™½Ð</textarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð theme: "elegant",Ð matchBrackets: true,Ð indentUnit: 8,Ð tabSize: 8,Ð indentWithTabs: true,Ð mode: "text/x-go"Ð });Ð </script>Ð MIME type: <code>text/x-go</code> Ð </article>Ð

public\assets\js\plugins\codemirror\mode\groovy\index.html


```
<!doctype html>Ðtitle>CodeMirror: Groovy mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="groovy.js"></script>Ðstyle>.CodeMirror {border-top: 1px solid #500;
border-bottom: 1px solid #500;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Groovy</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Groovy mode</h2>Ðform><textarea id="code" name="code">Ð/Pattern for
groovy scriptÐdef p = ~/.*\.groovy/Ðnew File( 'd:\\scripts' ).eachFileMatch(p)
{f ->Ð // imports listÐ def imports = []Ð f.eachLine {Ð   // condition to
detect an import instructionÐ   ln -> if ( ln =~ '^import .*' ) {Ð
imports << "${ln - 'import '}"Ð   }Ð }Ð // print thmenÐ if ( !
imports.empty ) {Ð   println fÐ   imports.each{ println "   $it" }Ð }ÐÐ/* Coin
changer demo code from http://groovy.codehaus.org */Ðnum UsCoin {Ð
quarter(25), dime(10), nickel(5), penny(1)Ð UsCoin(v) { value = v }Ð final
valueÐ}Ðnum OzzieCoin {Ð fifty(50), twenty(20), ten(10), five(5)Ð OzzieCoin(v)
{ value = v }Ð final valueÐ}Ðdef plural(word, count) {Ð if (count == 1) return
wordÐ word[-1] == 'y' ? word[0..-2] + "ies" : word + "s"Ð}Ðdef change(currency,
amount) {Ð currency.values().inject([]){ list, coin ->Ð    int count =
amount / coin.valueÐ    amount = amount % coin.valueÐ    list += "$count
${plural(coin.toString(), count)}"Ð }Ð}ÐÐ/textarea></form>Ð   <script>Ð     var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-groovy"Ð
      });Ð   </script>Ð   <p><strong>MIME types defined:</strong> <code>text/
x-groovy</code></p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\haml\index.html


```
<!doctype html>Ðtitle>CodeMirror: HAML mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../xml/xml.js"></script>Ðscript src="../htmlmixed/
htmlmixed.js"></script>Ðscript src="../javascript/javascript.js"></script>Ð
<script src="../ruby/ruby.js"></script>Ðscript src="haml.js"></script>Ð
<style>.CodeMirror {background: #f8f8f8;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">HAML</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>HAML mode</h2>Ðform><textarea id="code" name="code">Ð!!Ð
#contentÐleft.column(title="title"){:href => "/hello", :test => "#{hello}
_#{world}"}Ð   <!-- This is a comment -->Ð   %h2 Welcome to our site!Ð   %p=
puts "HAML MODE"Ð .right.columnÐ   = render :partial => "sidebar"ÐcontainerÐ
  .rowÐ   .span8Ð     %h1.title= @page_titleÐ%p.title= @page_titleÐ%pÐ /Ð   The
same as HTML commentÐ   Hello multiline commentÐ -# haml commentÐ     This
wont be displayedÐ     nor will thisÐ Date/Time:Ð - now = DateTime.nowÐ
%strong= nowÐ - if now > DateTime.parse("December 31, 2006")Ð   = "Happy new
" + "year!"Ð%titleÐ = @titleÐ \= @titleÐ <h1>Title</h1>Ð <h1 title="HELLO">Ð
TitleÐ </h1>Ð   </textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       mode: "text/x-haml"Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-haml</code>.</p>Ð
<p><strong>Parsing/Highlighting Tests:</strong> <a href="../../test/
index.html#haml_*">normal</a>,  <a href="../../test/
index.html#verbose,haml_*">verbose</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\haskell\index.html

```
<!doctype html>Ðtitle>CodeMirror: Haskell mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
elegant.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="../../addon/edit/matchbrackets.js"></script>Ðscript src="haskell.js"></
script>Ðstyle type="text/css">.CodeMirror {border-top: 1px solid black;
border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Haskell</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Haskell mode</h2>Ðform><textarea id="code" name="code">Ðmodule UniquePerms
(Ð   uniquePermsÐ   )ÐwhereÐ- | Find all unique permutations of a list where
there might be duplicates.ÐuniquePerms :: (Eq a) => [a] -> [[a]]ÐuniquePerms =
permBag . makeBagÐ- | An unordered collection where duplicate values are
allowed,Ð- but represented with a single value and a count.ÐType Bag a = [(a,
Int)]ÐmakeBag :: (Eq a) => [a] -> Bag aÐmakeBag [] = []ÐmakeBag (a:as) = mix a $
makeBag asÐ whereÐ   mix a []                          = [(a,1)]Ð   mix a
(bn@(b,n):bs) | a == b    = (b,n+1):bsÐ                          | otherwise =
bn : mix a bsÐpermBag :: Bag a -> [[a]]ÐpermBag [] = [[]]ÐpermBag bs = concatMap
(\(f,cs) -> map (f:) $ permBag cs) . oneOfEach $ bsÐ whereÐ   oneOfEach [] =
[]Ð   oneOfEach (an@(a,n):bs) =Ð       let bs' = if n == 1 then bs else
(a,n-1):bsÐ       in (a,bs') : mapSnd (an:) (oneOfEach bs)Ð   Ð   apSnd f
(a,b) = (a, f b)Ð   mapSnd = map . apSndÐ/textarea></form>Ð   <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
        lineNumbers: true,Ð       matchBrackets: true,Ð       theme: "elegant"Ð
      });Ð   </script>Ð   <p><strong>MIME types defined:</strong> <code>text/
x-haskell</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\haxe\index.html


```
<!doctype html>Ðtitle>CodeMirror: Haxe mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="haxe.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Haxe</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>Haxe mode</h2>Ðdiv><p><textarea id="code-haxe" name="code">Ð
import one.two.Three;Ðattr("test")ÐÐlass Foo&lt;T&gt; extends ThreeÐÐ V&Æ–2
function new()Ð™noFoo = 12;Ð V&Æ–2 7F F–2 –æÆ–æR gVæ7F–öâ FôfÖò†ö&£§¶³¤–çBÂ
l:Float}):IntÐ™for(i in 0...10){ÐÖ&¢æ²²™½G& 6R†'™½f " f #  Ò æWr  '& ',™½
if(var1.length > 1)Ð™throw "Error";Ð/ The following line should not be
colored, the variable is scoped outÐvar1;Ð* Multi lineÐ* Comment testÐ*/Ðreturn
obj.k;ÐÝ &–f FR gVæ7F–öâ & ",“¥fö–M½#if flashÐvar t1:String = "1.21";ÐenÐdry {Ð
doFoo({k:3, l:1.2});Ð}Ðatch (e : String) {ÐG& 6R†R™½Ðvar t2:Float = cast(3.2);Ð
var t3:haxe.Timer = new haxe.Timer();Ðvar t4 = {k:Std.int(t2),
l:Std.parseFloat(t1)};Ðvar t5 = ~/123+.*$/i;ÐdoFoo(t4);Ðntyped t1 = 4;Ðob = new
Foo&lt;Int&gt;;ÐÝ V&Æ–2 f " ö´fÖò†FVf VÇBÂ æWfW"“¤fÆö C½f " æôfÖò†vWDfÖòÂ
null):Int;ÐgVæ7F–öâ vWDfÖò,“¤–çB ½return noFoo;Ð V&Æ–2 f " F‡&VS¤–çC½Ðnum
ColorÐÐ&VC½w&VVã½&ÇVS½w&W', b ¢ –çB “½&v" ‡#¤–çBÆs¤–çBÆ#¤–çB“½Ð/textarea></p>Ð
<p>Hxml mode:</p>Ðp><textarea id="code-hxml">Ðcp testÐjs path/to/file.jsÐ-
remap nme:flashÐ-nextÐD source-map-contentÐcmd 'test'Ðlib limeÐ/textarea></p>Ð
</div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code-haxe"), {Ð     –ÖöFS¢
"haxe",Ð       lineNumbers: true,Ð       indentUnit: 4,Ð
indentWithTabs: trueÐ     });Ð     Ð     editor =
CodeMirror.fromTextArea(document.getElementById("code-hxml"), {Ð     –ÖöFS¢
"hxml",Ð       lineNumbers: true,Ð       indentUnit: 4,Ð
indentWithTabs: trueÐ     });Ð   </script>Ð   <p><strong>MIME types defined:</
strong> <code>text/x-haxe, text/x-hxml</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\htmlembedded\index.html


```
<!doctype html>Ðtitle>CodeMirror: Html Embedded Scripts mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../xml/xml.js"></script>Ðscript src="../
javascript/javascript.js"></script>Ðscript src="../css/css.js"></script>Ð
<script src="../htmlmixed/htmlmixed.js"></script>Ðscript
src="htmlembedded.js"></script>Ðstyle type="text/css">.CodeMirror {border-
top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð
<a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../
doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Html Embedded
Scripts</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Html Embedded Scripts mode</h2>Ð
<form><textarea id="code" name="code">Ð%Ðfunction hello(who) {Ð&WGW&â $†VÆÆò "
+ who;Ð%>Ðthis is an example of EJS (embedded javascript)Ðp>The program says
<%= hello("world") %>.</p>Ðscript>Ð ÆW'B,$ æB †W&R –2 6öÖR æ÷&Ö Â ¥2
code"); // also coloredÐ/script>Ð/textarea></form>Ð   <script>Ð     var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       mode: "application/x-ejs",Ð       indentUnit: 4,Ð
        indentWithTabs: trueÐ     });Ð   </script>Ð   <p>Mode for html
embedded scripts like JSP and ASP.NET. Depends on HtmlMixed which in turn
depends onÐ   JavaScript, CSS and XML.<br />Other dependancies include those
of the scriping language chosen.</p>Ð   <p><strong>MIME types defined:</
strong> <code>application/x-aspx</code> (ASP.NET), Ð   <code>application/x-
ejs</code> (Embedded Javascript), <code>application/x-jsp</code> (JavaServer
Pages)</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\htmlmixed\index.html

```
<!doctype html>Ðtitle>CodeMirror: HTML mixed mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../xml/xml.js"></script>Ðscript src="../
javascript/javascript.js"></script>Ðscript src="../css/css.js"></script>Ð
<script src="../vbscript/vbscript.js"></script>Ðscript src="htmlmixed.js"></
script>Ðstyle>.CodeMirror {border-top: 1px solid black; border-bottom: 1px
solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">HTML mixed</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>HTML mixed mode</h2>Ðform><textarea id="code" name="code">Ðhtml
style="color: green">Ð <!-- this is a comment -->Ð <head>Ð   <title>Mixed
HTML Example</title>Ð   <style type="text/css">Ð     h1 {font-family: comic
sans; color: #f0f;}Ð     div {background: yellow !important;}Ð     body {Ð
        max-width: 50em;Ð       margin: 1em 2em 1em 5em;Ð     }Ð   </style>Ð
</head>Ð <body>Ð   <h1>Mixed HTML Example</h1>Ð   <script>Ð     function
jsFunc(arg1, arg2) {Ð       if (arg1 && arg2) document.body.innerHTML =
"achoo";Ð     }Ð   </script>Ð </body>Ð/html>Ð/textarea></form>Ð   <script>Ð
      // Define an extended mixed-mode that understands vbscript andÐ     //
leaves mustache/handlebars embedded templates in html modeÐ     var mixedMode
= {Ð       name: "htmlmixed",Ð       scriptTypes: [{matches: /\/x-handlebars-
template|\/x-mustache/i,Ð                       mode: null},Ð
                      {matches: /(text|application)\/(x-)?vb(a|script)/i,Ð
                       mode: "vbscript"}]Ð     };Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {mode: mixedMode});Ð
    </script>Ð   <p>The HTML mixed mode depends on the XML, JavaScript, and
CSS modes.</p>Ð   <p>It takes an optional mode configurationÐ   option,
<code>scriptTypes</code>, which can be used to add customÐ   behavior for
specific <code>&lt;script type="..."></code> tags. IfÐ   given, it should
hold an array of <code>{matches, mode}</code>Ð   objects, where
<code>matches</code> is a string or regexp thatÐ   matches the script type,
and <code>mode</code> isÐ   either <code>null</code>, for script types that
should stay inÐ   HTML mode, or a <a href="../../doc/
manual.html#option_mode">modeÐ   spec</a> corresponding to the mode that
should be used for theÐ   script.</p>Ð   <p><strong>MIME types defined:</
strong> <code>text/html</code>Ð   (redefined, only takes effect if you load
this parser after theÐ   XML parser).</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\http\index.html

<!doctype html>Ðtitle>CodeMirror: HTTP mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="http.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../
index.html">Language modes</a>Ð <li><a class=active href="#">HTTP</a>Ð </ul>Ð
Ðarticle>Ðh2>HTTP mode</h2>Ðdiv><textarea id="code" name="code">ÐOST /
somewhere HTTP/1.1ÐHost: example.comÐf-Modified-Since: Sat, 29 Oct 1994
19:43:31 GMTÐontent-Type: application/x-www-form-urlencoded;Ð6† '6WC×WFbÓÚser-
Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/536.11 (KHTML, like Gecko)
Ubuntu/12.04 Chromium/20.0.1132.47 Chrome/20.0.1132.47 Safari/536.11ÐThis is
the request body!Ð/textarea> Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð </script>Ð
MIME types defined: <code>message/http</code>. Ð </
article>Ð

public\assets\js\plugins\codemirror\mode\index.html


```
<!doctype html>Ðtitle>CodeMirror: Language Modes</title>Ðmeta charset="utf-8"/
>Ðlink rel=stylesheet href="../doc/docs.css">Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../doc/logo.png"></a>Ð
<ul>Ð   <li><a href="../index.html">Home</a>Ð   <li><a href="../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a class=active href="#">Language
modes</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Language modes</h2>Ðp>This is a list of
every mode in the distribution. Each mode lives in a subdirectory of the
<code>mode/</code> directory, and typically defines a single JavaScript file
that implements the mode. Loading such file will make the language available
to CodeMirror, through the <a href="manual.html#option_mode"><code>mode</
code></a> option.</p>Ðdiv style="-webkit-columns: 100px 2; -moz-columns: 100px
2; columns: 100px 2;">Ð   <ul style="margin-top: 0">Ð     <li><a href="apl/
index.html">APL</a></li>Ð     <li><a href="asterisk/index.html">Asterisk
dialplan</a></li>Ð     <li><a href="clike/index.html">C, C++, C#</a></li>Ð
      <li><a href="clojure/index.html">Clojure</a></li>Ð     <li><a
href="cobol/index.html">COBOL</a></li>Ð     <li><a href="coffeescript/
index.html">CoffeeScript</a></li>Ð     <li><a href="commonlisp/
index.html">Common Lisp</a></li>Ð     <li><a href="css/index.html">CSS</a></
li>Ð     <li><a href="cypher/index.html">Cypher</a></li>Ð     <li><a
href="python/index.html">Cython</a></li>Ð     <li><a href="d/index.html">D</
a></li>Ð     <li><a href="django/index.html">Django</a> (templating
language)</li>Ð     <li><a href="diff/index.html">diff</a></li>Ð     <li><a
href="dtd/index.html">DTD</a></li>Ð     <li><a href="dylan/index.html">Dylan</
a></li>Ð     <li><a href="ecl/index.html">ECL</a></li>Ð     <li><a
href="eiffel/index.html">Eiffel</a></li>Ð     <li><a href="erlang/
index.html">Erlang</a></li>Ð     <li><a href="fortran/index.html">Fortran</
a></li>Ð     <li><a href="mllike/index.html">F#</a></li>Ð     <li><a
href="gas/index.html">Gas</a> (AT&amp;T-style assembly)</li>Ð     <li><a
href="gherkin/index.html">Gherkin</a></li>Ð     <li><a href="go/
index.html">Go</a></li>Ð     <li><a href="groovy/index.html">Groovy</a></li>Ð
      <li><a href="haml/index.html">HAML</a></li>Ð     <li><a href="haskell/
index.html">Haskell</a></li>Ð     <li><a href="haxe/index.html">Haxe</a></li>Ð
      <li><a href="htmlembedded/index.html">HTML embedded scripts</a></li>Ð
      <li><a href="htmlmixed/index.html">HTML mixed-mode</a></li>Ð     <li><a
href="http/index.html">HTTP</a></li>Ð     <li><a href="clike/
index.html">Java</a></li>Ð     <li><a href="jade/index.html">Jade</a></li>Ð
      <li><a href="javascript/index.html">JavaScript</a></li>Ð     <li><a
href="jinja2/index.html">Jinja2</a></li>Ð     <li><a href="julia/
index.html">Julia</a></li>Ð     <li><a href="kotlin/index.html">Kotlin</a></
li>Ð     <li><a href="css/less.html">LESS</a></li>Ð     <li><a
href="livescript/index.html">LiveScript</a></li>Ð     <li><a href="lua/
index.html">Lua</a></li>Ð     <li><a href="markdown/index.html">Markdown</a>
(<a href="gfm/index.html">GitHub-flavour</a>)</li>Ð     <li><a href="mirc/
index.html">mIRC</a></li>Ð     <li><a href="modelica/index.html">Modelica</
a></li>Ð     <li><a href="nginx/index.html">Nginx</a></li>Ð     <li><a
href="ntriples/index.html">NTriples</a></li>Ð     <li><a href="mllike/
index.html">OCaml</a></li>Ð     <li><a href="octave/index.html">Octave</a>
(MATLAB)</li>Ð     <li><a href="pascal/index.html">Pascal</a></li>Ð
<li><a href="pegjs/index.html">PEG.js</a></li>Ð     <li><a href="perl/
index.html">Perl</a></li>Ð     <li><a href="php/index.html">PHP</a></li>Ð
<li><a href="pig/index.html">Pig Latin</a></li>Ð     <li><a href="properties/
index.html">Properties files</a></li>Ð     <li><a href="puppet/
index.html">Puppet</a></li>Ð     <li><a href="python/index.html">Python</a></
li>Ð     <li><a href="q/index.html">Q</a></li>Ð     <li><a href="r/
index.html">R</a></li>Ð     <li><a href="rpm/index.html">RPM</a></li>Ð
<li><a href="rst/index.html">reStructuredText</a></li>Ð     <li><a href="ruby/
index.html">Ruby</a></li>Ð     <li><a href="rust/index.html">Rust</a></li>Ð
      <li><a href="sass/index.html">Sass</a></li>Ð
```

```
                                                        <li><a href="clike/
scala.html">Scala</a></li>Ð     <li><a href="scheme/index.html">Scheme</a></
li>Ð     <li><a href="css/scss.html">SCSS</a></li>Ð     <li><a href="shell/
index.html">Shell</a></li>Ð     <li><a href="sieve/index.html">Sieve</a></li>Ð
      <li><a href="slim/index.html">Slim</a></li>Ð     <li><a href="smalltalk/
index.html">Smalltalk</a></li>Ð     <li><a href="smarty/index.html">Smarty</
a></li>Ð     <li><a href="smartymixed/index.html">Smarty/HTML mixed</a></li>Ð
      <li><a href="solr/index.html">Solr</a></li>Ð     <li><a href="sql/
index.html">SQL</a> (several dialects)</li>Ð     <li><a href="sparql/
index.html">SPARQL</a></li>Ð     <li><a href="stex/index.html">sTeX, LaTeX</
a></li>Ð     <li><a href="tcl/index.html">Tcl</a></li>Ð     <li><a
href="textile/index.html">Textile</a></li>Ð     <li><a href="tiddlywiki/
index.html">Tiddlywiki</a></li>Ð     <li><a href="tiki/index.html">Tiki wiki</
a></li>Ð     <li><a href="toml/index.html">TOML</a></li>Ð     <li><a
href="tornado/index.html">Tornado</a> (templating language)</li>Ð     <li><a
href="turtle/index.html">Turtle</a></li>Ð     <li><a href="vb/
index.html">VB.NET</a></li>Ð     <li><a href="vbscript/index.html">VBScript</
a></li>Ð     <li><a href="velocity/index.html">Velocity</a></li>Ð     <li><a
href="verilog/index.html">Verilog/SystemVerilog</a></li>Ð     <li><a
href="xml/index.html">XML/HTML</a></li>Ð     <li><a href="xquery/
index.html">XQuery</a></li>Ð     <li><a href="yaml/index.html">YAML</a></li>Ð
      <li><a href="z80/index.html">Z80</a></li>Ð   </ul>Ð </div>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\jade\index.html

```
<!doctype html>Ðtitle>CodeMirror: Jade Templating Mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../javascript/javascript.js"></script>Ð
<script src="../css/css.js"></script>Ðscript src="../xml/xml.js"></script>Ð
<script src="../htmlmixed/htmlmixed.js"></script>Ðscript src="jade.js"></
script>Ðstyle type="text/css">.CodeMirror {border-top: 1px solid black;
border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Jade Templating Mode</a>Ð </ul>Ð/
div>Ðarticle>Ðh2>Jade Templating Mode</h2>Ðform><textarea id="code"
name="code">Ðdoctype htmlÐ htmlÐ   headÐ     title= "Jade Templating
CodeMirror Mode Example"Ð     link(rel='stylesheet', href='/css/
bootstrap.min.css')Ð     link(rel='stylesheet', href='/css/index.css')Ð
script(type='text/javascript', src='/js/jquery-1.9.1.min.js')Ð
script(type='text/javascript', src='/js/bootstrap.min.js')Ð   bodyÐ
div.headerÐ       h1 Welcome to this ExampleÐ     div.spotsÐ       if
locals.spotsÐ         each spot in spotsÐ           div.spot.wellÐ        divÐ
            if spot.logoÐ            img.img-rounded.logo(src=spot.logo)Ð
            elseÐ            img.img-rounded.logo(src="img/placeholder.png")Ð
         h3Ð          a(href=spot.hash) ##{spot.hash}Ð          if spot.titleÐ
             span.title #{spot.title}Ð          if spot.descÐ            div
#{spot.desc}Ð       elseÐ         h3 There are no spots currently available.Ð/
textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
{name: "jade", alignCDATA: true},Ð       lineNumbers: trueÐ     });Ð   </
script>Ð   <h3>The Jade Templating Mode</h3>Ð     <p> Created by Forbes
Lindesay. Managed as part of a Brackets extension at <a href="https://
github.com/ForbesLindesay/jade-brackets">https://github.com/ForbesLindesay/
jade-brackets</a>.</p>Ð   <p><strong>MIME type defined:</strong> <code>text/x-
jade</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\javascript\index.html


```
<!doctype html>Ðtitle>CodeMirror: JavaScript mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></
script>Ðscript src="../../addon/comment/continuecomment.js"></script>Ðscript
src="../../addon/comment/comment.js"></script>Ðscript src="javascript.js"></
script>Ðstyle type="text/css">.CodeMirror {border-top: 1px solid black;
border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">JavaScript</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>JavaScript mode</h2>Ðdiv><textarea id="code" name="code">Ø/ Demo code
(the actual new parser character stream implementation)Ðfunction
StringStream(string) {Ð this.pos = 0;Ð this.string = string;ÐÐ
StringStream.prototype = {Ð done: function() {return this.pos >=
this.string.length;},Ð peek: function() {return
this.string.charAt(this.pos);},Ð next: function() {Ð   if (this.pos &lt;
this.string.length)Ð     return this.string.charAt(this.pos++);Ð },Ð eat:
function(match) {Ð   var ch = this.string.charAt(this.pos);Ð   if (typeof
match == "string") var ok = ch == match;Ð   else var ok = ch &amp;&amp;
match.test ? match.test(ch) : match(ch);Ð   if (ok) {this.pos++; return ch;}Ð
  },Ð eatWhile: function(match) {Ð   var start = this.pos;Ð   while
(this.eat(match));Ð   if (this.pos > start) return this.string.slice(start,
this.pos);Ð },Ð backUp: function(n) {this.pos -= n;},Ð column: function()
{return this.pos;},Ð eatSpace: function() {Ð   var start = this.pos;Ð   while
(/\s/.test(this.string.charAt(this.pos))) this.pos++;Ð   return this.pos -
start;Ð },Ð match: function(pattern, consume, caseInsensitive) {Ð   if
(typeof pattern == "string") {Ð     function cased(str) {return
caseInsensitive ? str.toLowerCase() : str;}Ð     if
(cased(this.string).indexOf(cased(pattern), this.pos) == this.pos) {Ð
if (consume !== false) this.pos += str.length;Ð       return true;Ð     }Ð   }Ð
    else {Ð     var match = this.string.slice(this.pos).match(pattern);Ð
if (match &amp;&amp; consume !== false) this.pos += match[0].length;Ð
return match;Ð   }Ð }};Ð/textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       continueComments:
"Enter",Ð       extraKeys: {"Ctrl-Q": "toggleComment"}Ð     });Ð   </script>Ð
    <p>Ð     JavaScript mode supports several configuration options:Ð     <ul>Ð
        <li><code>json</code> which will set the mode to expect JSONÐ
data rather than a JavaScript program.</li>Ð       <li><code>jsonld</code>
which will set the mode to expectÐ       <a href="http://json-ld.org">JSON-
LD</a> linked data ratherÐ       than a JavaScript program (<a href="json-
ld.html">demo</a>).</li>Ð       <li><code>typescript</code> which will
activate additionalÐ       syntax highlighting and some other things for
TypeScript codeÐ       (<a href="typescript.html">demo</a>).</li>Ð
<li><code>statementIndent</code> which (given a number) willÐ       determine
the amount of indentation to use for statementsÐ       continued on a new
line.</li>Ð       <li><code>wordCharacters</code>, a regexp that indicates
whichÐ       characters should be considered part of an identifier.Ð
Defaults to <code>/[\w$]/</code>, which does not handleÐ       non-ASCII
identifiers. Can be set to something more elaborateÐ       to improve Unicode
support.</li>Ð     </ul>Ð   </p>Ð   <p><strong>MIME types defined:</strong>
<code>text/javascript</code>, <code>application/json</code>,
<code>application/ld+json</code>, <code>text/typescript</code>,
<code>application/typescript</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\javascript\json-ld.html

```
<!doctype html>Ðtitle>CodeMirror: JSON-LD mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="../../addon/comment/continuecomment.js"></script>Ðscript src="../../
addon/comment/comment.js"></script>Ðscript src="javascript.js"></script>Ð
<style type="text/css">.CodeMirror {border-top: 1px solid black; border-
bottom: 1px solid black;}</style>Ðdiv id="nav">Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"/></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">JSON-LD</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>JSON-LD mode</h2>Ðdiv><textarea id="code" name="code">{Ð "@context": {Ð
"name": "http://schema.org/name",Ð   "description": "http://schema.org/
description",Ð   "image": {Ð     "@id": "http://schema.org/image",Ð
"@type": "@id"Ð   },Ð   "geo": "http://schema.org/geo",Ð   "latitude": {Ð
"@id": "http://schema.org/latitude",Ð     "@type": "xsd:float"Ð   },Ð
"longitude": {Ð     "@id": "http://schema.org/longitude",Ð     "@type":
"xsd:float"Ð   },Ð   "xsd": "http://www.w3.org/2001/XMLSchema#"Ð },Ð "name":
"The Empire State Building",Ð "description": "The Empire State Building is a
102-story landmark in New York City.",Ð "image": "http://
www.civil.usherbrooke.ca/cours/gci215a/empire-state-building.jpg",Ð "geo": {Ð
    "latitude": "40.75",Ð   "longitude": "73.98"Ð }}ÐÐ/textarea></div>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
matchBrackets: true,Ð       autoCloseBrackets: true,Ð       mode:
"application/ld+json",Ð       lineWrapping: trueÐ     });Ð   </script>Ð   Ð
<p>This is a specialization of the <a href="index.html">JavaScript mode</a>.</
p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\javascript\typescript.html

```
<!doctype html>Ðtitle>CodeMirror: TypeScript mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="javascript.js"></script>Ðstyle
type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px
solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">TypeScript</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>TypeScript mode</h2>Ðdiv><textarea id="code" name="code">Ðlass Greeter {Ð
greeting: string;Ð6öç7G'V7F÷" †ÖW76 vS¢ 7G&–ær’ ™½this.greeting = message;Ý
greet() {Þreturn "Hello, " + this.greeting;Ý   Ðar greeter = new
Greeter("world");Ðar button = document.createElement('button')Ð
button.innerText = "Say Hello"Ðutton.onclick = function() {Ð
alert(greeter.greet())}ÐÐocument.body.appendChild(button)Ð/textarea></div>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/typescript"Ð
      });Ð   </script>Ð   <p>This is a specialization of the <a
href="index.html">JavaScript mode</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\jinja2\index.html

```
<!doctype html>Ðtitle>CodeMirror: Jinja2 mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="jinja2.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Jinja2</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Jinja2 mode</h2>Ðform><textarea id="code" name="code">Ð
{# this is a comment #}Ð{%- for item in li -%}Ð &lt;li&gt;{{ item.label }}&lt;/
li&gt;Ð{% endfor -%}Ð{{ item.sand == true and item.keyword == false ? 1 : 0 }}Ð
{{ app.get(55, 1.2, true) }}Ð{% if app.get(&#39;_route&#39;) ==
(&#39;_home&#39;) %}home{% endif %}Ð{% if
app.session.flashbag.has(&#39;message&#39;) %}Ð {% for message in
app.session.flashbag.get(&#39;message&#39;) %}Ð   {{ message.content }}Ð {%
endfor %}Ð{% endif %}Ð{{ path(&#39;_home&#39;, {&#39;section&#39;:
app.request.get(&#39;section&#39;)}) }}Ð{{ path(&#39;_home&#39;, {Ð
&#39;section&#39;: app.request.get(&#39;section&#39;),Ð   &#39;boolean&#39;:
true,Ð   &#39;number&#39;: 55.33Ð })Ð}}Ð{% include
(&#39;test.incl.html.twig&#39;) %}Ð/textarea></form>Ð   <script>Ð     var
editor =Ð     CodeMirror.fromTextArea(document.getElementById("code"), {mode:Ð
        {name: "jinja2", htmlMode: true}});Ð   </script>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\julia\index.html

<!doctype html>Ðtitle>CodeMirror: Julia mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="julia.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../
index.html">Language modes</a>Ð <li><a class=active href="#">Julia</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Julia mode</h2>Ð <textarea id="code" name="code">Ð
#numbersÐ1234Ð1234imÐ234Ð234imÐ2.23imÐ2.3f3Ð3e2ÐÐx234ÐstringsÐa'ÐasdfÐ"regex"Ð
b"bytestring"Ð"""Ðmultiline stringÐ"""ÐidentifiersÐÐas123Ðfunction_name!Ðunicode
identifiersÐ a = x\ddotÐ a × =#xÐ a•= v\dotÐ a × =#vÐ\vec = m \cdotp a\vecÐ × = mÐa ×Ð
#literal identifier multiplesÐxÐ[1, 2, 3]ÐdictsÐ and indexingÐ=[1, 2, 3]Ð
x[end-1]Ð={"julia"=>"language of technical computing"}Ðexception handlingÐtryÐ
f()ÐcatchÐ @printf "Error"ÐfinallyÐ g()ÐendÐtypesÐmmutable Color{T<:Number}Ð r::TÐ
  g::TÐ b::TÐendÐfunctionsÐfunction change!(x::Vector{Float64})Ð for i =
1:length(x)Ð x[i] *= 2Ð endÐendÐfunction invocationÐ('b', (2, 3)...)Ð
#operatorsÐ|=Ð&=Ð>>>=Ð-=Ð%=Ð*=Ð÷=Ð$=Ð⊻=Ð&&=Ð||=Ð<:Ð<Ð>Ð<=Ð<<Ð>>Ð>>>Ð>=Ð>>=Ð<=Ð
<<<=Ð<=Ð>=Ð==Ð>Ø/ÐnÐ..Ø/Ð=Ð//=Ð*=Ð/=Ð^=Ð%=Ð+=Ð-=Ð\=Ð|Ð==Ð&&Ð=Ð|=Ð:Ð:Ð|>Ð|Ð:Ð
x ? y : zÐmacrosÐspawnat 2 1+1Ðeval(:x)Ðkeywords and operatorsÐif else elseif
while forÐbegin let end doÐtry catch finally return break continueÐglobal local
const ÐexportÐ import importall usingÐfunction macro module baremodule ÐtypeÐ
immutable quoteÐtrue false enumerateÐ </textarea> Ð <script>Ð var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
mode: {name: "julia",Ð },Ð lineNumbers: true,Ð
indentUnit: 4,Ð matchBrackets: trueÐ });Ð </script>Ð
MIME types defined: <code>text/x-julia</code>. Ð/
article>Ð

public\assets\js\plugins\codemirror\mode\kotlin\index.html


```
<!doctype html>Ðtitle>CodeMirror: Kotlin mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="kotlin.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Kotlin</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Kotlin mode</h2>Ðdiv><textarea id="code" name="code">Ð
package org.wasabi.http.Ðimport java.util.concurrent.Executors.Ðimport
java.net.InetSocketAddress.Ðimport org.wasabi.app.AppConfiguration.Ðimport
io.netty.bootstrap.ServerBootstrap.Ðimport
io.netty.channel.nio.NioEventLoopGroup.Ðimport
io.netty.channel.socket.nio.NioServerSocketChannel.Ðimport
org.wasabi.app.AppServer.Ðpublic class HttpServer(private val appServer:
AppServer) {Ð   val bootstrap: ServerBootstrapÐ   val primaryGroup:
NioEventLoopGroupÐ   val workerGroup:  NioEventLoopGroupÐ   {Ð       //
Define worker groupsÐ       primaryGroup = NioEventLoopGroup()Ð
workerGroup = NioEventLoopGroup()Ð       // Initialize bootstrap of serverÐ
        bootstrap = ServerBootstrap()Ð       bootstrap.group(primaryGroup,
workerGroup)Ð       bootstrap.channel(javaClass<NioServerSocketChannel>())Ð
        bootstrap.childHandler(NettyPipelineInitializer(appServer))Ð   }Ð
public fun start(wait: Boolean = true) {Ð       val channel =
bootstrap.bind(appServer.configuration.port)?.sync()?.channel()Ð       if
(wait) {Ð           channel?.closeFuture()?.sync()Ð       }Ð   }Ð   public
fun stop() {Ð       // Shutdown all event loopsÐ
primaryGroup.shutdownGracefully()Ð       workerGroup.shutdownGracefully()Ð
        // Wait till all threads are terminatedÐ
primaryGroup.terminationFuture().sync()Ð
workerGroup.terminationFuture().sync()Ð   }ÐÐ/textarea></div>Ð   <script>Ð
        var editor = CodeMirror.fromTextArea(document.getElementById("code"),
{Ð           mode: {name: "kotlin"},Ð           lineNumbers: true,Ð
indentUnit: 4Ð       });Ð   </script>Ð   <h3>Mode for Kotlin (http://
kotlin.jetbrains.org/)</h3>Ð   <p>Developed by Hadi Hariri (https://
github.com/hhariri).</p>Ð   <p><strong>MIME type defined:</strong> <code>text/
x-kotlin</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\livescript\index.html


```
<!doctype html>Ðtitle>CodeMirror: LiveScript mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðlink rel="stylesheet"
href="../../theme/solarized.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="livescript.js"></script>Ðstyle>.CodeMirror {font-size:
80%;border-top: 1px solid silver; border-bottom: 1px solid silver;}</style>Ð
<div id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">LiveScript</a>Ð
  </ul>Ð/div>Ðarticle>Ðh2>LiveScript mode</h2>Ðform><textarea id="code"
name="code">Ð LiveScript mode for CodeMirrorÐ The following script,
prelude.ls, is used toÐ demonstrate LiveScript mode for CodeMirror.Ð
https://github.com/gkz/prelude-lsÐexport objToFunc = objToFunc = (obj) ->Ð
(key) -> obj[key]Ðexport each = (f, xs) -->Ð if typeof! xs is \ObjectÐ   for ,
x of xs then f xÐ elseÐ   for x in xs then f xÐ xsÐexport map = (f, xs) -->Ð f
= objToFunc f if typeof! f isnt \FunctionÐ type = typeof! xsÐ if type is
\ObjectÐ   {[key, f x] for key, x of xs}Ð elseÐ   result = [f x for x in xs]Ð
    if type is \String then result * '' else resultÐexport filter = (f, xs) -->Ð
  f = objToFunc f if typeof! f isnt \FunctionÐ type = typeof! xsÐ if type is
\ObjectÐ   {[key, x] for key, x of xs when f x}Ð elseÐ   result = [x for x in
xs when f x]Ð   if type is \String then result * '' else resultÐexport reject
= (f, xs) -->Ð f = objToFunc f if typeof! f isnt \FunctionÐ type = typeof! xsÐ
  if type is \ObjectÐ   {[key, x] for key, x of xs when not f x}Ð elseÐ
result = [x for x in xs when not f x]Ð   if type is \String then result * ''
else resultÐexport partition = (f, xs) -->Ð f = objToFunc f if typeof! f isnt
\FunctionÐ type = typeof! xsÐ if type is \ObjectÐ   passed = {}Ð   failed = {}Ð
    for key, x of xsÐ     (if f x then passed else failed)[key] = xÐ elseÐ
passed = []Ð   failed = []Ð   for x in xsÐ     (if f x then passed else
failed)push xÐ   if type is \StringÐ     passed *= ''Ð     failed *= ''Ð
[passed, failed]Ðexport find = (f, xs) -->Ð f = objToFunc f if typeof! f isnt
\FunctionÐ if typeof! xs is \ObjectÐ   for , x of xs when f x then return xÐ
elseÐ   for x in xs when f x then return xÐ voidÐexport head = export first =
(xs) ->Ð return void if not xs.lengthÐ xs.0Ðexport tail = (xs) ->Ð return void
if not xs.lengthÐ xs.slice 1Ðexport last = (xs) ->Ð return void if not
xs.lengthÐ xs[*-1]Ðexport initial = (xs) ->Ð return void if not xs.lengthÐ
xs.slice 0 xs.length - 1Ðexport empty = (xs) ->Ð if typeof! xs is \ObjectÐ
for x of xs then return falseÐ   return yesÐ not xs.lengthÐexport values =
(obj) ->Ð [x for , x of obj]Ðexport keys = (obj) ->Ð [x for x of obj]Ðexport
len = (xs) ->Ð xs = values xs if typeof! xs is \ObjectÐ xs.lengthÐexport cons
= (x, xs) -->Ð if typeof! xs is \String then x + xs else [x] ++ xsÐexport
append = (xs, ys) -->Ð if typeof! ys is \String then xs + ys else xs ++ ysÐ
export join = (sep, xs) -->Ð xs = values xs if typeof! xs is \ObjectÐ xs.join
sepÐexport reverse = (xs) ->Ð if typeof! xs is \StringÐ then (xs / '')reverse!
* ''Ð else xs.slice!reverse!Ðexport fold = export foldl = (f, memo, xs) -->Ð
if typeof! xs is \ObjectÐ   for , x of xs then memo = f memo, xÐ elseÐ   for
x in xs then memo = f memo, xÐ memoÐexport fold1 = export foldl1 = (f, xs) -->
fold f, xs.0, xs.slice 1Ðexport foldr = (f, memo, xs) --> fold f, memo,
xs.slice!reverse!Ðexport foldr1 = (f, xs) -->Ð xs.=slice!reverse!Ð fold f,
xs.0, xs.slice 1Ðexport unfoldr = export unfold = (f, b) -->Ð if (f b)?Ð
[that.0] ++ unfoldr f, that.1Ð elseÐ   []Ðexport andList = (xs) ->Ð for x in
xs when not xÐ   return falseÐ trueÐexport orList = (xs) ->Ð for x in xs when xÐ
    return trueÐ falseÐexport any = (f, xs) -->Ð f = objToFunc f if typeof! f
isnt \FunctionÐ for x in xs when f xÐ   return yesÐ noÐexport all = (f, xs) -->Ð
  f = objToFunc f if typeof! f isnt \FunctionÐ for x in xs when not f xÐ
return noÐ yesÐexport unique = (xs) ->Ð result = []Ð if typeof! xs is \ObjectÐ
    for , x of xs when x not in result then result.push xÐ elseÐ   for x   in
xs when x not in result then result.push xÐ
```

```
                                                if typeof! xs is \String then
result * '' else resultÐexport sort = (xs) ->Ð xs.concat!sort (x, y) ->Ð   | x
> y =>  1Ð   | x < y => -1Ð   | _     =>  0Ðexport sortBy = (f, xs) -->Ð
return [] unless xs.lengthÐ xs.concat!sort fÐexport compare = (f, x, y) -->Ð |
(f x) > (f y) =>  1Ð | (f x) < (f y) => -1Ð | otherwise     =>  0Ðexport sum =
(xs) ->Ð result = 0Ð if typeof! xs is \ObjectÐ   for , x of xs then result +=
xÐ elseÐ   for x   in xs then result += xÐ resultÐexport product = (xs) ->Ð
result = 1Ð if typeof! xs is \ObjectÐ   for , x of xs then result *= xÐ elseÐ
    for x   in xs then result *= xÐ resultÐexport mean = export average = (xs)
-> (sum xs) / len xsÐexport concat = (xss) -> fold append, [], xssÐexport
concatMap = (f, xs) --> fold ((memo, x) -> append memo, f x), [], xsÐexport
listToObj = (xs) ->Ð {[x.0, x.1] for x in xs}Ðexport maximum = (xs) -> fold1
(>?), xsÐexport minimum = (xs) -> fold1 (<?), xsÐexport scan = export scanl =
(f, memo, xs) -->Ð last = memoÐ if typeof! xs is \ObjectÐ then [memo] ++
[last = f last, x for , x of xs]Ð else [memo] ++ [last = f last, x for x in
xs]Ðexport scan1 = export scanl1 = (f, xs) --> scan f, xs.0, xs.slice 1Ðexport
scanr = (f, memo, xs) -->Ð xs.=slice!reverse!Ð scan f, memo, xs .reverse!Ð
export scanr1 = (f, xs) -->Ð xs.=slice!reverse!Ð scan f, xs.0, xs.slice
1 .reverse!Ðexport replicate = (n, x) -->Ð result = []Ð i = 0Ð while i < n, +
+i then result.push xÐ resultÐexport take = (n, xs) -->Ð | n <= 0Ð   if
typeof! xs is \String then '' else []Ð | not xs.length => xsÐ | otherwise
=> xs.slice 0, nÐexport drop = (n, xs) -->Ð | n <= 0        => xsÐ | not
xs.length => xsÐ | otherwise     => xs.slice nÐexport splitAt = (n, xs) -->
[(take n, xs), (drop n, xs)]Ðexport takeWhile = (p, xs) -->Ð return xs if not
xs.lengthÐ p = objToFunc p if typeof! p isnt \FunctionÐ result = []Ð for x in
xsÐ   break if not p xÐ   result.push xÐ if typeof! xs is \String then result
* '' else resultÐexport dropWhile = (p, xs) -->Ð return xs if not xs.lengthÐ p
= objToFunc p if typeof! p isnt \FunctionÐ i = 0Ð for x in xsÐ   break if not
p xÐ   ++iÐ drop i, xsÐexport span = (p, xs) --> [(takeWhile p, xs),
(dropWhile p, xs)]Ðexport breakIt = (p, xs) --> span (not) << p, xsÐexport zip
= (xs, ys) -->Ð result = []Ð for zs, i in [xs, ys]Ð   for z, j in zsÐ
result.push [] if i is 0Ð     result[j]?push zÐ resultÐexport zipWith = (f,xs,
ys) -->Ð f = objToFunc f if typeof! f isnt \FunctionÐ if not xs.length or not
ys.lengthÐ   []Ð elseÐ   [f.apply this, zs for zs in zip.call this, xs, ys]Ð
export zipAll = (...xss) ->Ð result = []Ð for xs, i in xssÐ   for x, j in xsÐ
      result.push [] if i is 0Ð     result[j]?push xÐ resultÐexport zipAllWith
= (f, ...xss) ->Ð f = objToFunc f if typeof! f isnt \FunctionÐ if not
xss.0.length or not xss.1.lengthÐ   []Ð elseÐ   [f.apply this, xs for xs in
zipAll.apply this, xss]Ðexport compose = (...funcs) ->Ð ->Ð   args = argumentsÐ
    for f in funcsÐ     args = [f.apply this, args]Ð   args.0Ðexport curry =
(f) ->Ð curry$ f # using util method curry$ from livescriptÐexport id = (x) ->
xÐexport flip = (f, x, y) --> f y, xÐexport fix = (f) ->Ð ( (g, x) -> -> f(g
g) ...arguments ) doÐ   (g, x) -> -> f(g g) ...argumentsÐexport lines = (str) -
>Ð return [] if not str.lengthÐ str / \\nÐexport unlines = (strs) -> strs * \\nÐ
export words = (str) ->Ð return [] if not str.lengthÐ str / /[ ]+/Ðexport
unwords = (strs) -> strs * ' 'Ðexport max = (>?)Ðexport min = (<?)Ðexport negate
= (x) -> -xÐexport abs = Math.absÐexport signum = (x) ->Ð | x < 0     => -1Ð |
x > 0     =>  1Ð | otherwise =>  0Ðexport quot = (x, y) --> ~~(x / y)Ðexport
rem = (%)Ðexport div = (x, y) --> Math.floor x / yÐexport mod = (%%)Ðexport
recip = (1 /)Ðexport pi = Math.PIÐexport tau = pi * 2Ðexport exp = Math.expÐ
export sqrt = Math.sqrtÐ changed from log as log is aÐ common function for
logging thingsÐexport ln = Math.logÐexport pow = (^)Ðexport sin = Math.sinÐexport
tan = Math.tanÐexport cos = Math.cosÐexport asin = Math.asinÐexport acos =
Math.acosÐexport atan = Math.atanÐexport atan2 = (x, y) --> Math.atan2 x, yÐ
sinhÐ tanhÐ coshÐ asinhÐ atanhÐ acoshÐexport truncate = (x) -> ~~xÐexport round
= Math.roundÐexport ceiling = Math.ceilÐexport floor = Math.floorÐexport isItNaN
= (x) -> x isnt xÐexport even = (x) -> x % 2 == 0Ðexport odd = (x) -> x % 2 != 0Ð
export gcd = (x, y) -->Ð x = Math.abs xÐ y = Math.abs yÐ until y is 0Ð   z =
x % yÐ   x = yÐ   y = zÐ xÐexport lcm = (x, y) -->Ð Math.abs Math.floor (x /
(gcd x, y) * y)Ð
```

Ð metaÐexport installPrelude = !(target) ->Ð unless target.prelude?isInstalledÐ target <<< out$ # using out$ generated by livescriptÐ target <<< target.prelude.isInstalled = trueÐexport prelude = out$Ð</textarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð theme: "solarized light",Ð lineNumbers: trueÐ });Ð </script>Ð MIME types defined: <code>text/x-livescript</code>. Ð The LiveScript mode was written by Kenneth Bentley. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\lua\index.html

```
<!doctype html>Ðtitle>CodeMirror: Lua mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
neat.css">Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="../../lib/codemirror.js"></script>Ðscript src="lua.js"></script>Ð
<style>.CodeMirror {border: 1px solid black;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Lua</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>Lua mode</h2>Ðform><textarea id="code" name="code">Ð-[[Ð
example useless code to show lua syntax highlightingÐthis is multiline commentÐ
]]Ðfunction blahblahblah(x)Ð local table = {Ð   "asd" = 123,Ð   "x" = 0.34,  Ð
  }Ð if x ~= 3 thenÐ   print( x )Ð elseif x == "string"Ð
my_custom_function( 0x34 )Ð elseÐ   unknown_function( "some string" )Ð endÐ --
single line commentÐ endÐfunction blablabla3()Ð for k,v in ipairs( table ) doÐ
    --abcde..Ð   y=[=[Ð x=[[Ð     x is a multi line stringÐ  ]]Ð but its
definition is iside a highest level string!Ð ]=]Ð   print(" \"\" ")Ð   s =
math.sin( x )Ð endÐendÐ/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
matchBrackets: true,Ð       theme: "neat"Ð     });Ð   </script>Ð   <p>Loosely
based on FranciszekÐ   Wawrzak's <a href="http://codemirror.net/1/contrib/
lua">CodeMirrorÐ   1 mode</a>. One configuration parameter isÐ   supported,
<code>specials</code>, to which you can provide anÐ   array of strings to
have those identifiers highlighted withÐ   the <code>lua-special</code>
style.</p>Ð   <p><strong>MIME types defined:</strong> <code>text/x-lua</
code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\markdown\index.html


```
<!doctype html>Ðtitle>CodeMirror: Markdown mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/continuelist.js"></script>Ðscript
src="../xml/xml.js"></script>Ðscript src="markdown.js"></script>Ðstyle
type="text/css">Ð     .CodeMirror {border-top: 1px solid black; border-
bottom: 1px solid black;}Ð     .cm-s-default .cm-trailing-space-a:before,Ð
      .cm-s-default .cm-trailing-space-b:before {position: absolute; content:
"\00B7"; color: #777;}Ð     .cm-s-default .cm-trailing-space-new-line:before
{position: absolute; content: "\21B5"; color: #777;}Ð   </style>Ðdiv id=nav>Ð
<a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../
doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Markdown</a>Ð
</ul>Ð/div>Ðarticle>Ðh2>Markdown mode</h2>Ðform><textarea id="code"
name="code">ÐMarkdown: BasicsÐ===============Ð&lt;ul id="ProjectSubmenu"&gt;Ð
&lt;li&gt;&lt;a href="/projects/markdown/" title="Markdown Project
Page"&gt;Main&lt;/a&gt;&lt;/li&gt;Ð   &lt;li&gt;&lt;a class="selected"
title="Markdown Basics"&gt;Basics&lt;/a&gt;&lt;/li&gt;Ð   &lt;li&gt;&lt;a
href="/projects/markdown/syntax" title="Markdown Syntax
Documentation"&gt;Syntax&lt;/a&gt;&lt;/li&gt;Ð   &lt;li&gt;&lt;a href="/
projects/markdown/license" title="Pricing and License
Information"&gt;License&lt;/a&gt;&lt;/li&gt;Ð   &lt;li&gt;&lt;a href="/
projects/markdown/dingus" title="Online Markdown Web Form"&gt;Dingus&lt;/
a&gt;&lt;/li&gt;Ð&lt;/ul&gt;ÐGetting the Gist of Markdown's Formatting SyntaxÐ
---------------------------------------------------Ð This page offers a brief
overview of what it's like to use Markdown.Ð The [syntax page] [s] provides
complete, detailed documentation forÐ every feature, but Markdown should be
very easy to pick up simply byÐ looking at a few examples of it in action. The
examples on this pageÐ are written in a before/after style, showing example
syntax and theÐ HTML output produced by Markdown.Ð It's also helpful to simply
try Markdown out; the [Dingus] [d] is aÐ web application that allows you type
your own Markdown-formatted textÐ and translate it to XHTML.Ð *Note:** This
document is itself written using Markdown; youÐ can [see the source for it by
adding '.text' to the URL] [src].Ð [s]: /projects/markdown/syntax  "Markdown
Syntax"Ð [d]: /projects/markdown/dingus  "Markdown Dingus"Ð [src]: /projects/
markdown/basics.textÐ# Paragraphs, Headers, Blockquotes ##Ð A paragraph is
simply one or more consecutive lines of text, separatedÐ by one or more blank
lines. (A blank line is any line that looks likeÐ a blank line -- a line
containing nothing but spaces or tabs isÐ considered blank.) Normal paragraphs
should not be indented withÐ spaces or tabs.Ð Markdown offers two styles of
headers: *Setext* and *atx*.Ð Setext-style headers for `&lt;h1&gt;` and
`&lt;h2&gt;` are created byÐ "underlining" with equal signs (`=`) and hyphens
(`-`), respectively.Ð To create an atx-style header, you put 1-6 hash marks
(`#`) at theÐ beginning of the line -- the number of hashes equals the resultingÐ
HTML header level.Ð Blockquotes are indicated using email-style ''&gt;`' angle
brackets.Ð Markdown:Ð   A First Level HeaderÐ   ====================Ð   Ð   A
Second Level HeaderÐ   ----------------------Ð   Now is the time for all good
men to come toÐ   the aid of their country. This is just aÐ   regular
paragraph.Ð   The quick brown fox jumped over the lazyÐ   dog's back.Ð   Ð
### Header 3Ð   &gt; This is a blockquote.Ð   &gt; Ð   &gt; This is the
second paragraph in the blockquote.Ð   &gt;Ð   &gt; ## This is an H2 in a
blockquoteÐ Output:Ð   &lt;h1&gt;A First Level Header&lt;/h1&gt;Ð   Ð
&lt;h2&gt;A Second Level Header&lt;/h2&gt;Ð   Ð   &lt;p&gt;Now is the time
for all good men to come toÐ   the aid of their country. This is just aÐ
regular paragraph.&lt;/p&gt;Ð   Ð   &lt;p&gt;The quick brown fox jumped over
the lazyÐ   dog's back.&lt;/p&gt;Ð   Ð   &lt;h3&gt;Header 3&lt;/h3&gt;Ð   Ð
&lt;blockquote&gt;Ð
```

<p>This is a blockquote.</p>Ð Ð
<p>This is the second paragraph in the blockquote.</p>Ð
Ð <h2>This is an H2 in a blockquote</h2>Ð </
blockquote>Ð## Phrase Emphasis ###ÐMarkdown uses asterisks and underscores
to indicate spans of emphasis.ÐMarkdown:Ð Some of these words *are
emphasized*.Ð Some of these words _are emphasized also_.Ð Ð Use two
asterisks for **strong emphasis**.Ð Or, if you prefer, __use two
underscores instead__.ÐOutput:Ð <p>Some of these words <em>are
emphasized</em>.Ð Some of these words <em>are emphasized
also</em>.</p>Ð Ð <p>Use two asterisks for
<strong>strong emphasis</strong>.Ð Or, if you prefer,
<strong>use two underscores instead</strong>.</p>Ð Ð#
Lists ##ÐUnordered (bulleted) lists use asterisks, pluses, and hyphens (`*`,Ð
`+`, and `-`) as list markers. These three markers areÐinterchangable; this:Ð
* Candy.Ð * Gum.Ð * Booze.ÐThis:Ð + Candy.Ð + Gum.Ð
+ Booze.ÐAnd this:Ð - Candy.Ð - Gum.Ð - Booze.ÐAll produce the
same output:Ð <ul>Ð <li>Candy.</li>Ð
<li>Gum.</li>Ð <li>Booze.</li>Ð </ul>Ð
Ordered (numbered) lists use regular numbers, followed by periods, asÐlist
markers:Ð 1. RedÐ 2. GreenÐ 3. BlueÐOutput:Ð <ol>Ð
<li>Red</li>Ð <li>Green</li>Ð <li>Blue</
li>Ð </ol>ÐIf you put blank lines between items, you'll get
`<p>` tags for theÐlist item text. You can create multi-paragraph list
items by indentingÐthe paragraphs by 4 spaces or 1 tab:Ð * A list item.Ð Ð
With multiple paragraphs.Ð * Another item in the list.ÐOutput:Ð
<ul>Ð <li><p>A list item.</p>Ð <p>With
multiple paragraphs.</p></li>Ð <li><p>Another item
in the list.</p></li>Ð </ul>Ð Ð## Links ###ÐMarkdown
supports two styles for creating links: *inline* andÐ*reference*. With both
styles, you use square brackets to delimit theÐtext you want to turn into a
link.ÐInline-style links use parentheses immediately after the link text.ÐFor
example:Ð This is an [example link](http://example.com/).ÐOutput:Ð
<p>This is an <a href="http://example.com/">Ð example link</
a>.</p>ÐOptionally, you may include a title attribute in the
parentheses:Ð This is an [example link](http://example.com/ "With a Title").Ð
Output:Ð <p>This is an <a href="http://example.com/" title="With a
Title">Ð example link</a>.</p>ÐReference-style links allow
you to refer to your links by names, whichÐyou define elsewhere in your
document:Ð I get 10 times more traffic from [Google][1] than fromÐ [Yahoo]
[2] or [MSN][3].Ð [1]: http://google.com/ "Google"Ð [2]: http://
search.yahoo.com/ "Yahoo Search"Ð [3]: http://search.msn.com/ "MSN
Search"ÐOutput:Ð <p>I get 10 times more traffic from <a
href="http://google.com/"Ð title="Google">Google</a> than from
<a href="http://search.yahoo.com/"Ð title="Yahoo Search">Yahoo</
a> or <a href="http://search.msn.com/"Ð title="MSN Search">MSN</
a>.</p>ÐThe title attribute is optional. Link names may contain
letters,Ðnumbers and spaces, but are *not* case sensitive:Ð I start my
morning with a cup of coffee andÐ [The New York Times][NY Times].Ð [ny
times]: http://www.nytimes.com/ÐOutput:Ð <p>I start my morning with a
cup of coffee andÐ <a href="http://www.nytimes.com/">The New York
Times</a>.</p>Ð## Images ###ÐImage syntax is very much like link
syntax.ÐInline (titles are optional):Ð ![alt text](/path/to/img.jpg "Title")Ð
Reference-style:Ð ![alt text][id]Ð [id]: /path/to/img.jpg "Title"ÐBoth of
the above examples produce the same output:Ð <img src="/path/to/img.jpg"
alt="alt text" title="Title" />Ð## Code ###ÐIn a regular paragraph, you can
create code span by wrapping text inÐbacktick quotes. Any ampersands (`&`)
and angle brackets (`<` orÐ`>`) will automatically be translated into
HTML entities. This makesÐit easy to use Markdown to write about HTML example
code:Ð I strongly recommend against using any `<blink>` tags.Ð I
wish SmartyPants used named entities like `—`Ð

instead of decimal-encoded entites like `—`.Ðutput:Ð <p>I strongly recommend against using anyÐ <code><blink></code> tags.</p>Ð Ð <p>I wish SmartyPants used named entities likeÐ <code>—</code> instead of decimal-encodedÐ entites like <code>—</code>.</p>Ðo specify an entire block of pre-formatted code, indent every line ofÐhe block by 4 spaces or 1 tab. Just like with code spans, `&`, `<`,Ðnd `>` characters will be escaped automatically.Ðarkdown:Ð If you want your page to validate under XHTML 1.0 Strict,Ð you've got to put paragraph tags in your blockquotes:Ð <blockquote>Ð <p>For example.</p>Ð </blockquote>Ðutput:Ð <p>If you want your page to validate under XHTML 1.0 Strict,Ð you've got to put paragraph tags in your blockquotes:</p>Ð Ð <pre><code><blockquote>Ð <p>For example.</p>Ð </blockquote>Ð </code></pre>Ð/textarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð mode: 'markdown',Ð lineNumbers: true,Ð theme: "default",Ð extraKeys: {"Enter": "newlineAndIndentContinueMarkdownList"}Ð });Ð </script>Ð Optionally depends on the XML mode for properly highlighted inline XML blocks. Ð MIME types defined: <code>text/x-markdown</code>. Ð Parsing/Highlighting Tests: <a href="../../test/index.html#markdown_*">normal</a>, <a href="../../test/index.html#verbose,markdown_*">verbose</a>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\mirc\index.html

```
<!doctype html>Ðtitle>CodeMirror: mIRC mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
twilight.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="mirc.js"></script>Ðstyle>.CodeMirror {border: 1px solid black;}</style>Ð
<div id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">mIRC</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>mIRC mode</h2>Ðform><textarea id="code" name="code">ÐAKA
Nick Tracker by Ford_Lawnmower irc.GeekShed.net #Script-HelpÐ
;*****************************************************************************;Ð
;**Start SetupÐChange JoinDisplay, below, for On Join AKA Display. On = 1 -
Off = 0Ðalias -l JoinDisplay { return 1 }ÐChange MaxNicks, below, to the
number of nicknames you want to store for each hostmask. I wouldn't go over
400 with this ;/Ðalias -l MaxNicks { return 20 }ÐChange AKALogo, below, To the
text you want displayed before each AKA result.Ðalias -l AKALogo { return 3 g
3 T 06K3 t  06r*ÝEnd SetupÐ
;*****************************************************************************;Ð
On *:Join:#: {Ð if ($nick == $me) { .timer 1 1 ialupdateCheck $chan }Ð
NickNamesAdd $nick $+($network,$wildsite)Ð if ($JoinDisplay)
{ .timerNickNames $+ $nick 1 2 NickNames.display $nick $chan $network
$wildsite }ÐÐÐon *:Nick: { NickNamesAdd $newnick $+($network,$wildsite) $nick }Ð
alias -l NickNames.display {Ð if ($gettok($hget(NickNames,$+($3,$4)),0,126) >
1) {Ð   echo -g $2 $AKALogo $+(3 ’ÂC ’ D ´ Æövò 07
$mid($replace($hget(NickNames,$+($3,$4)),$chr(126),$chr(44)),2,-1)Ð }ÐÐÐalias -
l NickNamesAdd {Ð if ($hget(NickNames,$2)) {Ð   if (!$regex($hget(NickNames,
$2),/~\Q $+ $replacecs($1,\E,\E\\E\Q) $+ \E~/i)) {Ð     if
($gettok($hget(NickNames,$2),0,126) <= $MaxNicks) {Ð       hadd NickNames $2 $
+($hget(NickNames,$2),$1,~)Ð     }Ð     else {Ð       hadd NickNames $2 $
+($mid($hget(NickNames,$2),$pos($hget(NickNames,$2),~,2)),$1,~)Ð     }Ð   }Ð }Ð
  else {Ð   hadd -m NickNames $2 $+(~,$1,~,$iif($3,$+($3,~)))Ð }ÐÐÐalias -l
Fix.All.MindUser {Ð var %Fix.Count = $hfind(NickNames,/[^~]+[0-9]{4}
~/,0,r).dataÐ while (%Fix.Count) {Ð   if ($Fix.MindUser($hget(NickNames,
$hfind(NickNames,/[^~]+[0-9]{4}~/,%Fix.Count,r).data))) {Ð     echo -ag
Record %Fix.Count - $v1 - Was CleanedÐ     hadd NickNames $hfind(NickNames,/
[^~]+[0-9]{4}~/,%Fix.Count,r).data $v1Ð   }Ð   dec %Fix.CountÐ }ÐÐÐalias -l
Fix.MindUser { return $regsubex($1,/[^~]+[0-9]{4}~/g,$null) }ÐÐmenu
nicklist,query {Ð -Ð .AKAÐ ..Check $$1: {Ð   if ($gettok($hget(NickNames,$
+($network,$address($1,2))),0,126) > 1) {Ð     NickNames.display $1 $active
$network $address($1,2)Ð   }Ð   else { echo -ag $AKALogo $+(3 ’ÂC ’ 07has not
been known by any other nicknames while I have been watching. }Ð }Ð ..Cleanup
$$1:hadd NickNames $+($network,$address($1,2)) $fix.minduser($hget(NickNames,$
+($network,$address($1,2))))Ð ..Clear $$1:hadd NickNames $+($network,
$address($1,2)) $+(~,$1,~)Ð ..AKA Search Dialog:dialog
$iif($dialog(AKA_Search),-v,-m) AKA_Search AKA_SearchÐ -ÐÐÐmenu status,channel {Ð
  -Ð .AKAÐ ..AKA Search Dialog:dialog $iif($dialog(AKA_Search),-v,-m)
AKA_Search AKA_SearchÐ ..Clean All Records:Fix.All.MinduserÐ -ÐÐÐdialog
AKA_Search {Ð title "AKA Search Engine"Ð size -1 -1 206 221Ð option dbuÐ edit
"", 1, 8 5 149 10, autohsÐ button "Search", 2, 163 4 32 12Ð radio "Search
HostMask", 4, 61 22 55 10Ð radio "Search Nicknames", 5, 123 22 56 10Ð list 6,
8 38 190 169, sort extsel vsbarÐ button "Check Selected", 7, 67 206 40 12Ð
button "Close", 8, 160 206 38 12, cancelÐ box "Search Type", 3, 11 17 183 18Ð
button "Copy to Clipboard", 9, 111 206 46 12ÐÐÐon *:Dialog:Aka_Search:init:*:
{ did -c $dname 5 }Ðon *:Dialog:Aka_Search:Sclick:2,7,9: {Ð if ($did == 2) &&
($did($dname,1)) {Ð   did -r $dname 6Ð   var %search $+(*,$v1,*), %type
$iif($did($dname,5).state,data,item), %matches = $hfind(NickNames,
%search,0,w). [ $+ [ %type ] ]Ð
```

while (%matches) {Ð did -a $dname 6 $hfind(NickNames,%search,%matches,w). [$+ [%type]]Ð dec %matchesÐ }Ð did -c $dname 6 1Ð }Ð elseif ($did == 7) && ($did($dname,6).seltext) { echo -ga $AKALogo 3 r FÖ–B,G&W Æ 6R,F†vWB„æ–6´æ ÖW2ÂGc ’ÂF6‡"ƒ #b’À $chr(44)),2,-1) }Ð elseif ($did == 9) && ($did($dname,6).seltext) { clipboard $mid($v1,$pos($v1,*,1)) }ÐÐn *:Start:{Ð if (!$hget(NickNames)) { hmake NickNames 10 }Ð if ($isfile(NickNames.hsh)) { hload NickNames NickNames.hsh }Ð }Ðn *:Exit: { if ($hget(NickNames)) { hsave NickNames NickNames.hsh } }Ðn *:Disconnect: { if ($hget(NickNames)) { hsave NickNames NickNames.hsh } }Ðn *:Unload: { hfree NickNames }Ðalias -l ialupdateCheck {Ð inc -z $ +(%,ialupdateCheck,$network) $calc($nick($1,0) / 4)Ð ;If your ial is already being updated on join .who $1 out.Ð ;If you are using /names to update ial you will still need this line.Ð .who $1ÐÐraw 352:*: {Ð if ($($ +(%,ialupdateCheck,$network),2)) haltdefÐ NickNamesAdd $6 $+($network, $address($6,2))ÐÐraw 315:*: {Ð if ($($+(%,ialupdateCheck,$network),2)) haltdefÐÐ</textarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð theme: "twilight",Ð lineNumbers: true,Ð matchBrackets: true,Ð indentUnit: 4,Ð mode: "text/mirc"Ð });Ð </script>Ð MIME types defined: <code>text/mirc</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\mllike\index.html

<!doctype html>Ðtitle>CodeMirror: ML-like mode</title>Ðmeta charset="utf-8"/>Ð <link rel=stylesheet href="../../doc/docs.css">Ðlink rel=stylesheet href=../../lib/codemirror.css>Ðscript src=../../lib/codemirror.js></script>Ð <script src=../../addon/edit/matchbrackets.js></script>Ðscript src=mllike.js></script>Ðstyle type=text/css>Ð .CodeMirror {border-top: 1px solid black; border-bottom: 1px solid black;}Ð/style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">ML-like</a>Ð </ul>Ð/div>Ðarticle>Ðh2>OCaml mode</h2>Ðtextarea id="ocamlCode">Ð(* Summing a list of integers *)Ðlet rec sum xs =Ð match xs withÐ | [] -> 0Ð | x :: xs' -> x + sum xs'Ð(* Quicksort *)Ðlet rec qsort = functionÐ | [] -> []Ð | pivot :: rest ->Ð let is_less x = x < pivot inÐ let left, right = List.partition is_less rest inÐ qsort left @ [pivot] @ qsort rightÐ(* Fibonacci Sequence *)Ðlet rec fib_aux n a b =Ð match n withÐ | 0 -> aÐ | _ -> fib_aux (n - 1) (a + b) aÐlet fib n = fib_aux n 0 1Ð(* Birthday paradox *)Ðlet year_size = 365.Ðlet rec birthday_paradox prob people =Ð let prob' = (year_size -. float people) /. year_size *. prob inÐ if prob' < 0.5 thenÐ Printf.printf "answer = %d\n" (people+1)Ð elseÐ birthday_paradox prob' (people+1) ;;Ðbirthday_paradox 1.0 1Ð(* Church numerals *)Ðlet zero f x = xÐlet succ n f x = f (n f x)Ðlet one = succ zeroÐlet two = succ (succ zero)Ðlet add n1 n2 f x = n1 f (n2 f x)Ðlet to_string n = n (fun k -> "S" ^ k) "0"Ðlet _ = to_string (add (succ two) two)Ð(* Elementary functions *)Ðlet square x = x * x;;Ðlet rec fact x =Ð if x <= 1 then 1 else x * fact (x - 1);;Ð(* Automatic memory management *)Ðlet l = 1 :: 2 :: 3 :: [];;Ð[1; 2; 3];;Ð :: l;;Ð(* Polymorphism: sorting lists *)Ðlet rec sort = functionÐ | [] -> []Ð | x :: l -> insert x (sort l)Ðand insert elem = functionÐ | [] -> [elem]Ð | x :: l ->Ð if elem < x then elem :: x :: l else x :: insert elem l;;Ð(* Imperative features *)Ðlet add_polynom p1 p2 =Ð let n1 = Array.length p1Ð and n2 = Array.length p2 inÐ let result = Array.create (max n1 n2) 0 inÐ for i = 0 to n1 - 1 do result.(i) <- p1.(i) done;Ð for i = 0 to n2 - 1 do result.(i) <- result.(i) + p2.(i) done;Ð result;;Ð add_polynom [| 1; 2 |] [| 1; 2; 3 |];;Ð(* We may redefine fact using a reference cell and a for loop *)Ðlet fact n =Ð let result = ref 1 inÐ for i = 2 to n doÐ result := i * !resultÐ done;Ð !result;;Ðfact 5;;Ð(* Triangle (graphics) *)Ðlet () =Ð ignore(Glut.init Sys.argv);Ð Glut.initDisplayMode ~double_buffer:true ();Ð ignore (Glut.createWindow ~title:"OpenGL Demo");Ð let angle t = 10. *. t *. t inÐ let render () =Ð GlClear.clear [`color ];Ð  GlMat.load_identity ();Ð  GlMat.rotate ~angle: (angle (Sys.time ())) ~z:1. ();Ð  GlDraw.begins `triangles;Ð List.iter GlDraw.vertex2 [-1., -1.; 0., 1.; 1., -1.];Ð GlDraw.ends ();Ð Glut.swapBuffers () inÐ GlMat.mode `modelview;Ð Glut.displayFunc ~cb:render;Ð Glut.idleFunc ~cb:(Some Glut.postRedisplay);Ð Glut.mainLoop ()Ð(* A Hundred Lines of Caml - http://caml.inria.fr/about/taste.en.html *)Ð(* OCaml page on Wikipedia - http://en.wikipedia.org/wiki/OCaml *)Ð/textarea>Ðh2>F# mode</h2>Ðtextarea id="fsharpCode">Ðmodule CodeMirror.FSharpÐlet rec fib = functionÐ | 0 -> 0Ð | 1 -> 1Ð | n -> fib (n - 1) + fib (n - 2)Ðtype Point =Ð {Ð x : intÐ y : intÐ }Ðtype Color =Ð | RedÐ | GreenÐ | BlueÐ[0 .. 10]Ð> List.map ((+) 2)Ð> List.fold (fun x y -> x + y) 0Ð> printf "%i"Ð/textarea>Ð <script>Ð var ocamlEditor = CodeMirror.fromTextArea(document.getElementById('ocamlCode'), {Ð mode: 'text/x-ocaml',Ð lineNumbers: true,Ð matchBrackets: trueÐ });Ð var fsharpEditor = CodeMirror.fromTextArea(document.getElementById('fsharpCode'), {Ð mode: 'text/x-fsharp',Ð lineNumbers: true,Ð matchBrackets: trueÐ });Ð </script>Ðp>MIME types defined: <code>text/x-ocaml</code> (OCaml) and <code>text/x-fsharp</code> (F#).</p>Ð/article>Ð

public\assets\js\plugins\codemirror\mode\modelica\index.html

```
<!doctype html>Ðtitle>CodeMirror: Modelica mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðlink
rel="stylesheet" href="../../addon/hint/show-hint.css">Ðscript src="../../
addon/hint/show-hint.js"></script>Ðscript src="modelica.js"></script>Ð
<style>.CodeMirror {border: 2px inset #dee;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Modelica</a>Ð
</ul>Ð/div>Ðarticle>Ðh2>Modelica mode</h2>Ðdiv><textarea id="modelica">Ðmodel
BouncingBallÐ parameter Real e = 0.7;Ð parameter Real g = 9.81;Ð Real
h(start=1);Ð Real v;Ð Boolean flying(start=true);Ð Boolean impact;Ð Real
v_new;ÐequationÐ impact = h <= 0.0;Ð der(v) = if flying then -g else 0;Ð
der(h) = v;Ð when {h <= 0.0 and v <= 0.0, impact} thenÐ   v_new = if
edge(impact) then -e*pre(v) else 0;Ð   flying = v_new > 0;Ð   reinit(v,
v_new);Ð end when;Ð annotation (uses(Modelica(version="3.2")));Ðend
BouncingBall;Ð/textarea></div>Ð   <script>Ð     var modelicaEditor =
CodeMirror.fromTextArea(document.getElementById("modelica"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-modelica"Ð
      });Ð     var mac = CodeMirror.keyMap.default ==
CodeMirror.keyMap.macDefault;Ð     CodeMirror.keyMap.default[(mac ? "Cmd" :
"Ctrl") + "-Space"] = "autocomplete";Ð   </script>Ð   <p>Simple mode that
tries to handle Modelica as well as it can.</p>Ð   <p><strong>MIME types
defined:</strong> <code>text/x-modelica</code>Ð   (Modlica code).</p>Ð/
article>Ð
```

public\assets\js\plugins\codemirror\mode\nginx\index.html

<!doctype html>Ðtitle>CodeMirror: NGINX mode</title>Ðmeta charset="utf-8"/>Ð <link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="nginx.js"></script>Ðstyle>.CodeMirror {background: #f8f8f8;}</style>Ð <link rel="stylesheet" href="../../doc/docs.css">Ð </head>Ð <style>Ð body {Ð margin: 0em auto;Ð }Ð .CodeMirror, .CodeMirror-scroll {Ð height: 600px;Ð }Ð </style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">NGINX</a>Ð </ul>Ð/div>Ðarticle>Ðh2>NGINX mode</h2>Ðform><textarea id="code" name="code" style="height: 800px;">Ðserver {Ð listen 173.255.219.235:80;Ð server_name website.com.au;Ð rewrite / $scheme://www.$host$request_uri permanent; ## Forcibly prepend a www}ÐÐserver {Ð listen 173.255.219.235:443;Ð server_name website.com.au;Ð rewrite / $scheme://www.$host$request_uri permanent; ## Forcibly prepend a www}ÐÐserver {Ð listen 173.255.219.235:80;Ð server_name www.website.com.au;Ð root /data/www;Ð index index.html index.php;Ð location / {Ð index index.html index.php; ## Allow a static html file to be shown firstÐ try_files $uri $uri/ @handler; ## If missing pass the URI to Magento's front handlerÐ expires 30d; ## Assume all files are cachableÐ }Ð ## These locations would be hidden by .htaccess normallyÐ location /app/ { deny all; }Ð location /includes/ { deny all; }Ð location /lib/ { deny all; }Ð location /media/downloadable/ { deny all; }Ð location /pkginfo/ { deny all; }Ð location /report/config.xml { deny all; }Ð location /var/ { deny all; }Ð location /var/export/ { ## Allow admins only to view export folderÐ auth_basic "Restricted"; ## Message shown in login windowÐ auth_basic_user_file /rs/passwords/testfile; ## See /etc/nginx/htpasswordÐ autoindex on;Ð }Ð location /. { ## Disable .htaccess and other hidden filesÐ return 404;Ð }Ð location @handler { ## Magento uses a common front handlerÐ rewrite / /index.php;Ð }Ð location ~ .php/ { ## Forward paths like /js/index.php/x.js to relevant handlerÐ rewrite ^/(.*.php)/ /$1 last;Ð }Ð location ~ \.php$ {Ð if (!-e $request_filename) { rewrite / /index.php last; } ## Catch 404s that try_files missÐ fastcgi_pass 127.0.0.1:9000;Ð fastcgi_index index.php;Ð fastcgi_param PATH_INFO $fastcgi_script_name;Ð fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;Ð include /rs/confs/nginx/fastcgi_params;Ð }ÐÐserver {Ð listen 173.255.219.235:443;Ð server_name website.com.au www.website.com.au;Ð root /data/www;Ð index index.html index.php;Ð ssl on;Ð ssl_certificate /rs/ssl/ssl.crt;Ð ssl_certificate_key /rs/ssl/ssl.key;Ð ssl_session_timeout 5m;Ð ssl_protocols SSLv2 SSLv3 TLSv1;Ð ssl_ciphers ALL:!ADH:!EXPORT56:RC4+RSA:+HIGH:+MEDIUM:+LOW:+SSLv2:+EXP;Ð ssl_prefer_server_ciphers on;Ð location / {Ð index index.html index.php; ## Allow a static html file to be shown firstÐ try_files $uri $uri/ @handler; ## If missing pass the URI to Magento's front handlerÐ expires 30d; ## Assume all files are cachableÐ }Ð ## These locations would be hidden by .htaccess normallyÐ location /app/ { deny all; }Ð location /includes/ { deny all; }Ð location /lib/ { deny all; }Ð location /media/downloadable/ { deny all; }Ð location /pkginfo/ { deny all; }Ð location /report/config.xml { deny all; }Ð location /var/ { deny all; }Ð location /var/export/ { ## Allow admins only to view export folderÐ auth_basic "Restricted"; ## Message shown in login windowÐ auth_basic_user_file htpasswd; ## See /etc/nginx/htpasswordÐ autoindex on;Ð }Ð location /. { ## Disable .htaccess and other hidden filesÐ return 404;Ð }Ð location @handler { ## Magento uses a common front handlerÐ

```
                                                rewrite / /index.php;Ð }Ð
location ~ .php/ { ## Forward paths like /js/index.php/x.js to relevant
handlerÐ   rewrite ^/(.*.php)/ /$1 last;Ð }Ð location ~ .php$ { ## Execute
PHP scriptsÐ   if (!-e $request_filename) { rewrite  /index.php last; } ##
Catch 404s that try_files missÐ   fastcgi_pass 127.0.0.1:9000;Ð
fastcgi_index  index.php;Ð   fastcgi_param PATH_INFO $fastcgi_script_name;Ð
fastcgi_param  SCRIPT_FILENAME $document_root$fastcgi_script_name;Ð
include        /rs/confs/nginx/fastcgi_params;Ð   fastcgi_param HTTPS on;Ð }ÐÐ
</textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/nginx</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\ntriples\index.html


```
<!doctype html>Ðtitle>CodeMirror: NTriples mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="ntriples.js"></script>Ðstyle type="text/css">Ð
      .CodeMirror {Ð       border: 1px solid #eee;Ð     }Ð   </style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">NTriples</a>Ð
</ul>Ð/div>Ðarticle>Ðh2>NTriples mode</h2>Ðform>Ðtextarea id="ntriples"
name="ntriples">    Ðhttp://Sub1>     <http://pred1>     <http://obj> .Ð
<http://Sub2>     <http://pred2#an2> "literal 1" .Ðhttp://Sub3#an3> <http://
pred3>     _:bnode3 .Ð:bnode4          <http://pred4>     "literal 2"@lang .Ð
_:bnode5          <http://pred5>     "literal 3"^^<http://type> .Ð/textarea>Ð/
form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("ntriples"), {});Ð   </script>Ð
    <p><strong>MIME types defined:</strong> <code>text/n-triples</code>.</p>Ð
</article>Ð
```

public\assets\js\plugins\codemirror\mode\octave\index.html


```
<!doctype html>Ðtitle>CodeMirror: Octave mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="octave.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Octave</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Octave mode</h2>Ð   <div><textarea id="code"
name="code">%numbersÐ1234 1234i 1234jÐ.234 .234j 2.23iÐ23e2 12E1j 123D-4
0x234]%stringsÐasda''a'Ðasda""a"%identifiersÐ + as123 - __asd__%operatorsÐÐÐÐ=Ð
>ÐÐ=Ð=ÐÐ..Ðbreak zeros default margin round ones randÐeil floor size clear
zeros eye mean std covÐrror eval functionÐabs acos atan asin cos cosh exp log
prod sumÐog10 max min sign sin sinh sqrt tan reshapeÐeturnÐase switchÐlse
elseif end if otherwiseÐo for whileÐry catchÐlassdef properties events methodsÐ
global persistent%one line comment%{ multi Ðline commment %}Ð   </textarea></
div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
{name: "octave",Ð              version: 2,Ð
singleLineStringErrors: false},Ð       lineNumbers: true,Ð       indentUnit:
4,Ð       matchBrackets: trueÐ     });Ð   </script>Ð   <p><strong>MIME types
defined:</strong> <code>text/x-octave</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\pascal\index.html


```
<!doctype html>Ðtitle>CodeMirror: Pascal mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="pascal.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Pascal</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Pascal mode</h2>Ðdiv><textarea id="code" name="code">Ð(*
Example Pascal code *)Ðwhile a <> b do writeln('Waiting');ÐÐif a > b then Ð
writeln('Condition met')Ðelse Ð writeln('Condition not met');ÐÐfor i := 1 to 10
do Ð writeln('Iteration: ', i:1);ÐÐrepeatÐ a := a + 1Ðuntil a = 10;ÐÐcase i ofÐ
0: write('zero');Ð 1: write('one');Ð 2: write('two')Ðend;Ð/textarea></div>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       mode: "text/x-pascal"Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-pascal</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\pegjs\index.html

```
<!doctype html>Ðhtml>Ð <head>Ð   <title>CodeMirror: PEG.js Mode</title>Ð
<meta charset="utf-8"/>Ð   <link rel=stylesheet href="../../doc/docs.css">Ð
<link rel="stylesheet" href="../../lib/codemirror.css">Ð   <script src="../../
lib/codemirror.js"></script>Ð   <script src="../javascript/javascript.js"></
script>Ð   <script src="pegjs.js"></script>Ð   <style type="text/
css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid
black;}</style>Ð </head>Ð <body>Ð   <div id=nav>Ð     <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
      <ul>Ð       <li><a href="../../index.html">Home</a>Ð       <li><a
href="../../doc/manual.html">Manual</a>Ð       <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð     </ul>Ð     <ul>Ð       <li><a
href="../index.html">Language modes</a>Ð       <li><a class=active
href="#">PEG.js Mode</a>Ð     </ul>Ð   </div>Ð   <article>Ð     <h2>PEG.js
Mode</h2>Ð     <form><textarea id="code" name="code">Ð/*Ð* Classic example
grammar, which recognizes simple arithmetic expressions likeÐ* "2*(3+4)". The
parser generated from this grammar then computes their value.Ð*/Ð startÐ =
additiveÐadditiveÐ = left:multiplicative "+" right:additive { return left +
right; }Ð / multiplicativeÐmultiplicativeÐ = left:primary "*"
right:multiplicative { return left * right; }Ð / primaryÐprimaryÐ = integerÐ /
"(" additive:additive ")" { return additive; }Ðinteger "integer"Ð = digits:
[0-9]+ { return parseInt(digits.join(""), 10); }Ðletter = [a-z]+</textarea></
form>Ð     <script>Ð       var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð         mode:
{name: "pegjs"},Ð         lineNumbers: trueÐ       });Ð     </script>Ð
<h3>The PEG.js Mode</h3>Ð     <p> Created by Forbes Lindesay.</p>Ð   </
article>Ð </body>Ð/html>Ð
```

public\assets\js\plugins\codemirror\mode\perl\index.html

<!doctype html>Ðtitle>CodeMirror: Perl mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="perl.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð
  <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../
index.html">Language modes</a>Ð <li><a class=active href="#">Perl</a>Ð </ul>Ð
Ðarticle>Ðh2>Perl mode</h2>Ðdiv><textarea id="code" name="code">Ð!/usr/
bin/perlÐuse Something qw(func1 func2);Ð stringsÐmy $s1 = qq'single line';Ðour
$s2 = q(multi-Ð line);Ðitem SomethingÐW† × ÆR±cutÐmy $html=<<'HTML'Ð
<html>Ðtitle>hi!</title>Ð/html>ÐHTMLÐprint "first,".join(',', 'second',
qq~third~);Ðif($s1 =~ m[(?<!\s)(l.ne)\z]o) {ÐF,Óç²C ÓÒBBâr &VFVf–æVB
variables';ÐG3" ×â 2õÂÖÆ–æRòö÷ƒ½G3 ×â 5™ line ™™Ð [™™Ð block™™Ðox}Ð; # numbers and
commentsÐ__END__Ðomething...Ð/textarea> Ð <script>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: trueÐ });Ð </script>Ð MIME types defined:</
strong> <code>text/x-perl</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\php\index.html


```
<!doctype html>Ðtitle>CodeMirror: PHP mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="../htmlmixed/htmlmixed.js"></script>Ðscript src="../xml/xml.js"></script>Ð
<script src="../javascript/javascript.js"></script>Ðscript src="../css/
css.js"></script>Ðscript src="../clike/clike.js"></script>Ðscript
src="php.js"></script>Ðstyle type="text/css">.CodeMirror {border-top: 1px
solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">PHP</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>PHP mode</h2>Ðform><textarea id="code" name="code">Ð?phpÐa
= array('a' => 1, 'b' => 2, 3 => 'c');Ðcho "$a[a] ${a[3] /* } comment */}
{$a[b]} \$a[a]";Ðunction hello($who) {Ð&WGW&â $†VÆÆò Gv†ò #%ÐÐ>Ðp>The program
says <?= hello("World") ?>.</p>Ðscript>Ð ÆW'B,$ æB †W&R –2 6öÖR ¥2 6öFR"“² òò
also coloredÐ/script>Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "application/x-
httpd-php",Ð       indentUnit: 4,Ð       indentWithTabs: trueÐ     });Ð   </
script>Ð   <p>Simple HTML/PHP mode based onÐ   the <a href="../clike/">C-
like</a> mode. Depends on XML,Ð   JavaScript, CSS, HTMLMixed, and C-like
modes.</p>Ð   <p><strong>MIME types defined:</strong> <code>application/x-
httpd-php</code> (HTML with PHP code), <code>text/x-php</code> (plain, non-
wrapped PHP code).</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\pig\index.html

<!doctype html>Ðtitle>CodeMirror: Pig Latin mode</title>Ðmeta charset="utf-8"/
>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="pig.js"></script>Ðstyle>.CodeMirror {border: 2px inset
#dee;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../
index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
  <li><a href="../index.html">Language modes</a>Ð <li><a class=active
href="#">Pig Latin</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Pig Latin mode</h2>Ð
<form><textarea id="code" name="code">Ð- Apache Pig (Pig Latin Language) DemoÐ
* ÐThis is a multiline comment.Ð/Ða = LOAD "\path\to\input" USING
PigStorage('\t') AS (x:long, y:chararray, z:bytearray);Ðb = GROUP a BY
(x,y,3+4);Ðc = FOREACH b GENERATE flatten(group) as (x,y), SUM(group.$2) as z;Ð
STORE c INTO "\path\to\output";Ð-Ð/textarea></form>Ð <script>Ð var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð indentUnit: 4,Ð mode: "text/x-pig"Ð });Ð
  </script>Ð <p>Ð Simple mode that handles Pig Latin language.Ð </
p>Ð <p>MIME type defined: <code>text/x-pig</code>Ð (PIG
code)Ð/html>Ð/article>Ð

public\assets\js\plugins\codemirror\mode\properties\index.html

```
<!doctype html>Ðtitle>CodeMirror: Properties files mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="properties.js"></script>Ð
<style>.CodeMirror {border-top: 1px solid #ddd; border-bottom: 1px solid
#ddd;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Properties files</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Properties files mode</
h2>Ðform><textarea id="code" name="code">Ð This is a properties fileÐa.key = A
valueÐanother.key = http://example.comÐ Exclamation mark as commentÐ
but.not=Within ! A value # indeedÐ  # Spaces at the beginning of a lineÐ
spaces.before.key=valueÐbackslash=Used for multi\Ð         line entries,\Ð
          that's convenient.Ð Unicode sequencesÐunicode.key=This is \u0020
UnicodeÐno.multiline=hereÐ ColonsÐolons : can be used tooÐ SpacesÐpaces\ in\
keys=Not very common...Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-properties</code>,Ð
<code>text/x-ini</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\puppet\index.html


```
<!doctype html>Ðtitle>CodeMirror: Puppet mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="puppet.js"></script>Ðstyle>Ð     .CodeMirror {border-top: 1px solid
black; border-bottom: 1px solid black;}Ð     .cm-s-default span.cm-arrow
{ color: red; }Ð   </style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Puppet</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Puppet mode</h2>Ðform><textarea id="code" name="code">Ð == Class:
automysqlbackupÐÐ Puppet module to install AutoMySQLBackup for periodic MySQL
backups.ÐÐ class { 'automysqlbackup':Ð   backup_dir => '/mnt/backups',Ð }ÐÐ
class automysqlbackup (Ð $bin_dir = $automysqlbackup::params::bin_dir,Ð
$etc_dir = $automysqlbackup::params::etc_dir,Ð $backup_dir =
$automysqlbackup::params::backup_dir,Ð $install_multicore = undef,Ð $config =
{},Ð $config_defaults = {},Ð) inherits automysqlbackup::params {Ð Ensure valid
paths are assignedÐ validate_absolute_path($bin_dir)Ð
validate_absolute_path($etc_dir)Ð validate_absolute_path($backup_dir)Ð Create
a subdirectory in /etc for config filesÐ file { $etc_dir:Ð   ensure =>
directory,Ð   owner => 'root',Ð   group => 'root',Ð   mode => '0750',Ð }Ð
Create an example backup file, useful for referenceÐ file { "${etc_dir}/
automysqlbackup.conf.example":Ð   ensure => file,Ð   owner => 'root',Ð
group => 'root',Ð   mode => '0660',Ð   source => 'puppet:///modules/
automysqlbackup/automysqlbackup.conf',Ð }Ð Add files from the developerÐ file
{ "${etc_dir}/AMB_README":Ð   ensure => file,Ð   source => 'puppet:///modules/
automysqlbackup/AMB_README',Ð }Ð file { "${etc_dir}/AMB_LICENSE":Ð   ensure
=> file,Ð   source => 'puppet:///modules/automysqlbackup/AMB_LICENSE',Ð }Ð
Install the actual binary fileÐ file { "${bin_dir}/automysqlbackup":Ð
ensure => file,Ð   owner => 'root',Ð   group => 'root',Ð   mode => '0755',Ð
source => 'puppet:///modules/automysqlbackup/automysqlbackup',Ð }Ð Create the
base backup directoryÐ file { $backup_dir:Ð   ensure => directory,Ð   owner
=> 'root',Ð   group => 'root',Ð   mode => '0755',Ð }Ð If you'd like to keep
your config in hiera and pass it to this classÐ if !empty($config) {Ð
create_resources('automysqlbackup::backup', $config, $config_defaults)Ð }Ð If
using RedHat family, must have the RPMforge repo's enabledÐ if
$install_multicore {Ð   package { ['pigz', 'pbzip2']: ensure => installed }Ð }Ð
}Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: "text/
x-puppet",Ð       matchBrackets: true,Ð       indentUnit: 4Ð     });Ð   </
script>Ð   <p><strong>MIME types defined:</strong> <code>text/x-puppet</
code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\python\index.html


```
<!doctype html>Ðtitle>CodeMirror: Python mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="python.js"></script>Ðstyle type="text/css">.CodeMirror {border-top: 1px
solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð  <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð  </ul>Ð  <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Python</a>Ð  </
ul>Ð/div>Ðarticle>Ðh2>Python mode</h2>Ð   <div><textarea id="code"
name="code">Ð Literalsð1234Ð0.0e101Ð123Ðb01010011100Ðo01234567Ðx0987654321abcdefÐ
7ð2147483647ÐLð79228162514264337593543950336LÐx100000000LÐ
79228162514264337593543950336Ðxdeadbeefð3.14jð10.jð10jð001jð1e100jð3.14e-10jð
String LiteralsÐFor\'''ÐGod\"""Ð""so lovedÐthe world"""Ð'''that he gavеÐis only
begotten\' '''ÐthatÐwhosoever believeth \ðin him'''Ð Identifiersð_a__ð a.bð a.b.cÐ
#Unicode identifiers on Python3Ð a = x\ddotð × =#xð•= v\dotð × =ÐÐ\vec = m
\cdot a\vecÐ × = m•ð × ÐOperatorsÐ - * / % & | ^ ~ < >Ð= != <= >= <> << >> // **Ð
and or not in isÐinfix matrix multiplication operator (PEP 465)ð @ BÐ
Delimitersð() [] {} , : ` = ; @ .  # Note that @ and . require the proper
context on Python 2.Ð= -= *= /= %= &= |= ^=Ð//= >>= <<= **=Ð Keywordsð as assert
break class continue def del elif else exceptÐfinally for from global if
import lambda pass raiseÐreturn try while with yieldÐ Python 2 Keywords
(otherwise Identifiers)Ðexec printÐ Python 3 Keywords (otherwise Identifiers)Ð
nonlocalÐ TypesÐbool classmethod complex dict enumerate float frozenset int
list objectÐproperty reversed set slice staticmethod str super tuple typeÐ
Python 2 Types (otherwise Identifiers)Ðbasestring buffer file long unicode
xrangeÐ Python 3 Types (otherwise Identifiers)Ðbytearray bytes filter map
memoryview open range zipÐ Some Example codeÐimport osÐfrom package import
ParentClassð@nonsenseDecoratorÐdef doesNothing():Ð   passÐclass
ExampleClass(ParentClass):Ð   @staticmethodÐ   def example(inputStr):Ð
a = list(inputStr)Ð       a.reverse()Ð       return ''.join(a)Ð   def
__init__(self, mixin = 'Hello'):Ð       self.mixin = mixinÐ/textarea></div>Ð
<h2>Cython mode</h2>Ðdiv><textarea id="code-cython" name="code-cython">Ðimport
numpy as npÐimport cythonÐfrom libc.math cimport sqrtð@cython.boundscheck(False)Ð
@cython.wraparound(False)Ðdef pairwise_cython(double[:, ::1] X):Ð   cdef int M
= X.shape[0]Ð   cdef int N = X.shape[1]Ð   cdef double tmp, dÐ   cdef
double[:, ::1] D = np.empty((M, M), dtype=np.float64)Ð   for i in range(M):Ð
        for j in range(M):Ð           d = 0.0Ð           for k in range(N):Ð
                tmp = X[i, k] - X[j, k]Ð               d += tmp * tmpÐ
            D[i, j] = sqrt(d)Ð   return np.asarray(D)Ð/textarea></div>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
{name: "python",Ð              version: 3,Ð
singleLineStringErrors: false},Ð       lineNumbers: true,Ð       indentUnit:
4,Ð       matchBrackets: trueÐ   });Ð
CodeMirror.fromTextArea(document.getElementById("code-cython"), {Ð
mode: {name: "text/x-cython",Ð              version: 2,Ð
singleLineStringErrors: false},Ð       lineNumbers: true,Ð       indentUnit:
4,Ð       matchBrackets: trueÐ     });Ð   </script>Ð   <h2>Configuration
Options for Python mode:</h2>Ð   <ul>Ð     <li>version - 2/3 - The version of
Python to recognize.  Default is 2.</li>Ð     <li>singleLineStringErrors -
true/false - If you have a single-line string that is not terminated at the
end of the line, this will show subsequent lines as errors if true, otherwise
it will consider the newline as the end of the string. Default is false.</li>Ð
      <li>hangingIndent - int - If you want to write long arguments to a
function starting on a new line, how much that line should be indented.
Defaults to one normal indentation unit.</li>Ð
```

</ul>Ð <h2>Advanced Configuration Options:</h2>Ð Usefull for superset of python syntax like Enthought enaml, IPython magics and questionmark help Ð <ul>Ð <li>singleOperators - RegEx - Regular Expression for single operator matching, default : <pre>^[\\+\\-*/%&|\\^~<>!]</pre> including <pre>@</pre> on Python 3</li>Ð <li>singleDelimiters - RegEx - Regular Expression for single delimiter matching, default : <pre>^[\\(\\)\\[\\]\\{\\}@,:`=;\\.]</pre></li>Ð <li>doubleOperators - RegEx - Regular Expression for double operators matching, default : <pre>^((==)|(!=)|(<=)|(>=)|(<>)|(<<)|(>>)|(//)|(**))</pre></li>Ð <li>doubleDelimiters - RegEx - Regular Expressoin for double delimiters matching, default : <pre>^((\\+=)|(\\-=)|(*=)|(%=)|(/=)|(&=)|(\\|=)|(\\^=))</pre></li>Ð <li>tripleDelimiters - RegEx - Regular Expression for triple delimiters matching, default : <pre>^((//=)|(>>=)|(<<=)|(**=))</pre></li>Ð <li>identifiers - RegEx - Regular Expression for identifier, default : <pre>^[_A-Za-z][_A-Za-z0-9]*</pre> on Python 2 and <pre>^[_A-Za-z\u00A1-\uFFFF][_A-Za-z0-9\u00A1-\uFFFF]*</pre> on Python 3.</li>Ð <li>extra_keywords - list of string - List of extra words ton consider as keywords</li>Ð <li>extra_builtins - list of string - List of extra words ton consider as builtins</li>Ð </ul>Ð MIME types defined: <code>text/x-python</code> and <code>text/x-cython</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\q\index.html

<!doctype html>Ðtitle>CodeMirror: Q mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript src="q.js"></script>Ð <style type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">Q</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Q mode</h2>Ðdiv><textarea id="code" name="code">Ø utilities to quickly load a csv file - for more exhaustive analysis of the csv contents see csvguess.qØ 2009.09.20 - updated to match latest csvguess.q Ø .csv.colhdrs[file] - return a list of colhdrs from fileØ info:.csv.info[file] - return a table of information about the fileØ columns are: Ø–2 Ò 6öÇVÖâ æ ÖS² 6′ Ò 6öÇVÖâ –æFWƒ² t - load type; mw - max width; Ø–F6† " Ò F—7F–æ7B 6† & 7FW'2 –â f ÇVW3² 'VÆR Ò rule that caught the typeØ–Ö –&R Ò æVVG2 6†V6¶–ærÂ ö6÷VÆEò &R 6 ′ F FRÂ 'WB perhaps just a float?Ø .csv.info0[file;onlycols] - like .csv.info except that it only analyses <onlycols>Ø example:Ø––æfó¢æ77bæ–æfó ¶f–ÆS²,æ77bæ6öÆ†G'2 file)like"*price"]Ø––æfó¢æ77bæ–æföÆ–¶U¶f–ÆS²"§ &–6R%Ý—6†÷r FVÆWFR g&öÒ –æfò where t=" "Ø .csv.data[file;info] - use the info from .csv.info to read the dataØ .csv.data10[file;info] - like .csv.data but only returns the first 10 rowsØ bulkload[file;info] - bulk loads file into table DATA (which must be already defined :: DATA:())Ø .csv.read[file]/read10[file] - for when you don't care about checking/tweaking the <info> before reading Ðd .csvÐELIM:","Ð ZAPHDRS:0b / lowercase and remove _ from colhdrs (junk characters are always removed)ÐWIDTHHDR:25000 / number of characters read to get the headerÐ READLINES:222 / number of lines read and used to guess the typesÐ SYMMAXWIDTH:11 / character columns narrower than this are stored as symbolsÐ SYMMAXGR:10 / max symbol granularity% before we give up and keep as a * stringÐ FORCECHARWIDTH:30 / every field (of any type) with values this wide or more is forced to character "*"ÐISCARDEMPTY:0b / completely ignore empty columns if true else set them to "C"ÐHUNKSIZE:50000000 / used in fs2 (modified .Q.fs)Ð k)nameltrim:{$[~@x;.z.s'x;~(*x)in aA:.Q.a,.Q.A;(+/&\~x in aA)_x;x]}Ð)fs2: {[f;s]((-7!s)>){[f;s;x]i:1+last@&0xa=r:1:(s;x;CHUNKSIZE);f@`\:i#r;x+i} [f;s]/0j}Ðleanhdrs:{{$[ZAPHDRS;lower x except"_";x]}x where x in DELIM,.Q.an}Ð cancast:{nw:x$"";if[not x in"BXCS";nw:(min 0#;max 0#;::)@\:nw];$[not any nw in x$(11&count y)#y;$[11<count y;not any nw in x$y;1b];0b]}Ðread: {[file]data[file;info[file]]} Ðread10:{[file]data10[file;info[file]]} Ð colhdrs:{[file]Ð Fæ ÖVÇG&–Ò DTÄ”Ò g2 6ÆV æ†G'2 f—'7B &V C †f–ÆS³ ³ ¶f—'7B where 0xa=read1(file;0;WIDTHHDR))}Ðdata:{[file;info]Ð†W†V2 2 g&öÒ –æfò v†W&R not t=" ")xcol(exec t from info;enlist DELIM)0:file}Ðdata10:{[file;info]Ð data[;info](file;0;1+last 11#where 0xa=read1(file;0;15*WIDTHHDR))}Ðinfo0: {[file;onlycols]Ð6öÆ†G'3¦ Fæ ÖVÇG&–Ò DTÄ”Ò g2 6ÆV æ†G'2 f—'7B head:read0(file;0;1+last where 0xa=read1(file;0;WIDTHHDR));ÐÆö Ff×G3¢†6÷VçB colhdrs)#"S";if[count onlycols;loadfmts[where not colhdrs in onlycols]:"C"];Ð breaks:where 0xa=read1(file;0;floor(10+READLINES)*WIDTHHDR%count head);Ð nas:count as:colhdrs xcol(loadfmts;enlist DELIM)0: (file;0;1+last((1+READLINES)&count breaks)#breaks);Ð–æfó¢…µÖ3¦¶W′ fÆ— as;v:value flip as);as:();Ð&W6W'fVC¦¶W– ç ·&W6W'fVBÃ¢å ç&W3·&W6W'fVBÃ¦ “½ info:update res:c in reserved from info;Ð–æfó§W F FR 6“¦’ÇC¢#ò"Æ— £ "ÆÖF÷C£ ÆÐ w:0,rule:0,gr:0,ndv:0,maybe:0b,empty:0b,j10:0b,j12:0b from info;Ð–æfó§W F FR ci:`s#ci from info;Ð–e¶6÷VçB öæÇ–6öÇ3¶–æfó§W F FR C¢" "Ç'VÆS£ g&öÒ –æfò where not c in onlycols];Ð–æfó§W F FR 6Gc§·7G&–ær†F—7F–æ7B ,–W†6W F × V 6, b from info; Ð–æfó§W F FR æGc¦6÷VçB V 6, 6Gb g&öÒ –æfó½–æfó§W F FR w#¦fÆö÷" 0.5+100*ndv%nas,mw:{max count each x}peach sdv from info where 0<ndv;Ð info:update t:"*",rule:20 from info where mw>.csv.FORCECHARWIDTH; / long valuesÐ

––æfó§W F FR C¢$2 %²æ77bäD•44 $DTÕ E•ÒÇ'VÆS£3 ÆV× G“£ " g&öÒ –æfò v†W&R
t="?",mw=0; / empty columnsÐ–æfó§W F FR F6† #§¶ 62 F—7F–æ7B & ¦R ‡× V 6, 6Gb
from info where t="?";Ð–æfó§W F FR ÖF÷C§¶Ö , 7VÒ V 6,"â#×‡× V 6, 6Gb g&öÒ –æfò
where t="?",{"."in x}each dchar;Ð–æfó§W F FR C¢&â"Ç'VÆS£C g&öÒ –æfò v†W&R
t="?",{any x in"0123456789"}each dchar; / vaguely numeric..Ð–æfó§W F FR
t:"I",rule:50,ipa:1b from info where t="n",mw within 7 15,mdot=3,{all x
in".0123456789"}each dchar,.csv.cancast["I"]peach sdv; / ip-addressÐ
info:update t:"J",rule:60 from info where t="n",mdot=0,{all x
in"+-0123456789"}each dchar,.csv.cancast["J"]peach sdv;Ð–æfó§W F FR
t:"I",rule:70 from info where t="J",mw<12,.csv.cancast["I"]peach sdv;Ð
info:update t:"H",rule:80 from info where t="I",mw<7,.csv.cancast["H"]peach
sdv;Ð–æfó§W F FR C¢$b"Ç'VÆS£“ g&öÒ –æfò v†W&R
t="n",mdot<2,mw>1,.csv.cancast["F"]peach sdv;Ð–æfó§W F FR
t:"E",rule:100,maybe:1b from info where t="F",mw<9;Ð–æfó§W F FR
t:"M",rule:110,maybe:1b from info where t in"nIHEF",mdot<2,mw within 4
7,.csv.cancast["M"]peach sdv; Ð–æfó§W F FR C¢$B"Ç'VÆS£ # ÆÖ –&S£ " g&öÒ –æfò
where t in"nI",mdot in 0 2,mw within 6 11,.csv.cancast["D"]peach sdv; Ð
info:update t:"V",rule:130,maybe:1b from info where t="I",mw in 5 6,7<count
each dchar,{all x like"*[0-9][0-5][0-9][0-5][0-9]"}peach
sdv,.csv.cancast["V"]peach sdv; / 235959 12345   Ð–æfó§W F FR
t:"U",rule:140,maybe:1b from info where t="H",mw in 3 4,7<count each dchar,
{all x like"*[0-9][0-5][0-9]"}peach sdv,.csv.cancast["U"]peach sdv; /2359Ð
info:update t:"U",rule:150,maybe:0b from info where t="n",mw in 4 5,mdot=0,
{all x like"*[0-9]:[0-5][0-9]"}peach sdv,.csv.cancast["U"]peach sdv;Ð
info:update t:"T",rule:160,maybe:0b from info where t="n",mw within 7
12,mdot<2,{all x like"*[0-9]:[0-5][0-9]:[0-5][0-9]*"}peach
sdv,.csv.cancast["T"]peach sdv;Ð–æfó§W F FR C¢%b"Ç'VÆS£ s ÆÖ –&S£ " g&öÒ –æfò
where t="T",mw in 7 8,mdot=0,.csv.cancast["V"]peach sdv;Ð–æfó§W F FR
t:"T",rule:180,maybe:1b from info where t in"EF",mw within 7 10,mdot=1,{all x
like"*[0-9][0-5][0-9][0-5][0-9].*"}peach sdv,.csv.cancast["T"]peach sdv;Ð
info:update t:"Z",rule:190,maybe:0b from info where t="n",mw within 11
24,mdot<4,.csv.cancast["Z"]peach sdv;Ð–æfó§W F FR C¢% "Ç'VÆS£# ÆÖ –&S£ " g&öÒ
info where t="n",mw within 12 29,mdot<4,{all x like"[12]*"}peach
sdv,.csv.cancast["P"]peach sdv;Ð–æfó§W F FR C¢$â"Ç'VÆS£# ÆÖ –&S£ " g&öÒ –æfò
where t="n",mw within 3 28,mdot=1,.csv.cancast["N"]peach sdv;Ð–æfó§W F FR
t:"?",rule:220,maybe:0b from info where t="n"; / reset remaining maybe numericÐ
info:update t:"C",rule:230,maybe:0b from info where t="?",mw=1; / charÐ
info:update t:"B",rule:240,maybe:0b from info where t in"HC",mw=1,mdot=0,
{$[all x in"01tTfFyYnN";(any"0fFnN"in x)and any"1tTyY"in x;0b]}each dchar; /
booleanÐ–æfó§W F FR C¢$""Ç'VÆS£#S ÆÖ –&S£ " g&öÒ –æfò v†W&R B
in"HC",mw=1,mdot=0,{all x in"01tTfFyYnN"}each dchar; / booleanÐ–æfó§W F FR
t:"X",rule:260,maybe:0b from info where t="?",mw=2,{$[all x
in"0123456789abcdefABCDEF";(any .Q.n in x)and any"abcdefABCDEF"in x;0b]}each
dchar; /hexÐ–æfó§W F FR C¢%2"Ç'VÆS£#s ÆÖ –&S£ " g&öÒ –æfò v†W&R
t="?",mw<.csv.SYMMAXWIDTH,mw>1,gr<.csv.SYMMAXGR; / symbols (max width
permitting)Ð–æfó§W F FR C¢"¢"Ç'VÆS£#ƒ ÆÖ –&S£ " g&öÒ –æfò v†W&R CÒ#ò#² ò F†R
rest as stringsÐò fÆ r F†÷6R 2ò¢ 6öÇVÖç2 v†–6, 6÷VÆB &R Væ6öFVB Fò –çFVvW'2
(.Q.j10/x10/j12/x12) to avoid symbolsÐ–æfó§W F FR £ #£ " g&öÒ –æfò v†W&R B
in"S*",mw<13,{all x in .Q.nA}each dchar;Ð–æfó§W F FR £ £ " g&öÒ –æfò v†W&R B
in"S*",mw<11,{all x in .Q.b6}each dchar; Ð6VÆV7B
c,ci,t,maybe,empty,res,j10,j12,ipa,mw,mdot,rule,gr,ndv,dchar from info}Ð
info:info0[;()] / by default don't restrict columnsÐnfolike:{[file;pattern]
info0[file;{x where x like y}[lower
colhdrs[file];pattern]]} / .csv.infolike[file;"*time"]Ðd .Ð DATA:()Ðulkload:
{[file;info]Ð–e¶æ÷F D D –â 7—7FVÒ'b#²v D D ææ÷BæFVf–æVEÓ½–e¶6÷VçB
DATA;'`DATA.not.empty];ÐÆö F†G'3¦W†V2 2 g&öÒ –æfò v†W&R æ÷B CÒ"
";loadfmts:exec t from info;Ðæ77bæg3%·µ¶f–ÆS¶Æö F†G'3¶Æö Ff×G5Ò D D –ç6W'B
$[count DATA;flip loadhdrs!(loadfmts;.csv.DELIM)0:file;loadhdrs
xcol(loadfmts;enlist .csv.DELIM)0:file]}[file;loadhdrs;loadfmts]];Ð6÷VçB D D Ý
@[.:;"\\l csvutil.custom.q";::]; / save your custom settings in
csvutil.custom.q to override those set at the beginning of the file Ð

```
                                                                    </
textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: trueÐ     });Ð   </script>Ð
<p><strong>MIME type defined:</strong> <code>text/x-q</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\r\index.html


```
<!doctype html>Ðtitle>CodeMirror: R mode</title>Ðmeta charset="utf-8"/>Ðlink
rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../
lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="r.js"></script>Ðstyle>Ð     .CodeMirror { border-top: 1px solid silver;
border-bottom: 1px solid silver; }Ð     .cm-s-default span.cm-semi { color:
blue; font-weight: bold; }Ð     .cm-s-default span.cm-dollar { color: orange;
font-weight: bold; }Ð     .cm-s-default span.cm-arrow { color: brown; }Ð
      .cm-s-default span.cm-arg-is { color: brown; }Ð   </style>Ðdiv id=nav>Ð
<a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../
doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">R</a>Ð </ul>Ð/
div>Ðarticle>Ðh2>R mode</h2>Ðform><textarea id="code" name="code">Ð Code from
http://www.mayin.org/ajayshah/KB/R/Ð FIRST LEARN ABOUT LISTS --Ðx =
list(height=5.4, weight=54);Ðprint("Use default printing --");Ðprint(X)Ð
print("Accessing individual elements --");Ðcat("Your height is ", X$height, "
and your weight is ", X$weight, "\n");Ð FUNCTIONS --Ðsquare <- function(x) {Ð
return(x*x);}ÐÐcat("The square of 3 is ", square(3), "\n");Ð                #
default value of the arg is set to 5.Ðcube <- function(x=5) {Ð return(x*x*x);}ÐÐ
cat("Calling cube with 2 : ", cube(2), "\n")    # will give 2^3Ðcat("Calling
cube        : ", cube(), "\n")     # will default to 5^3.Ð LEARN ABOUT
FUNCTIONS THAT RETURN MULTIPLE OBJECTS --Ðpowers <- function(x) {Ð parcel =
list(x2=x*x, x3=x*x*x, x4=x*x*x*x);Ð return(parcel);}ÐX = powers(3);Ð
print("Showing powers of 3 --"); print(X);Ð WRITING THIS COMPACTLY (4 lines
instead of 7)Ðpowerful <- function(x) {Ð return(list(x2=x*x, x3=x*x*x,
x4=x*x*x*x));}ÐÐprint("Showing powers of 3 --"); print(powerful(3));Ð In R, the
last expression in a function is, by default, what isÐ returned. So you could
equally just say:Ðpowerful <- function(x) {list(x2=x*x, x3=x*x*x, x4=x*x*x*x)}Ð
</textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-rsrc</code>.</p>Ð
<p>Development of the CodeMirror R mode was kindly sponsoredÐ   by <a
href="https://twitter.com/ubalo">Ubalo</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\rpm\changes\index.html

<!doctype html>Ðtitle>CodeMirror: RPM changes mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ð <link rel="stylesheet" href="../../../lib/codemirror.css">Ð <script src="../../../lib/codemirror.js"></script>Ð <script src="changes.js"></script>Ð <link rel="stylesheet" href="../../../doc/docs.css">Ð <style type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../../index.html">Home</a>Ð <li><a href="../../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../../index.html">Language modes</a>Ð <li><a class=active href="#">RPM changes</a>Ð </ul>Ð/div>Ð <article>Ðh2>RPM changes mode</h2>Ð <textarea id="code" name="code">Ð ----------Ðue Oct 18 13:58:40 UTC 2011 - misterx@example.comÐ Update to r60.3Ð Fixes bug in the reflect packageÐ * disallow Interface method on Value obtained via unexported nameÐ----------Ðhu Oct 6 08:14:24 UTC 2011 - misterx@example.comÐ Update to r60.2Ð Fixes memory leak in certain map typesÐ ----------Ðed Oct 5 14:34:10 UTC 2011 - misterx@example.comÐ Tweaks for gdb debuggingÐ go.spec changes:Ð - move %go_arch definition to %prep sectionÐ - pass correct location of go specific gdb pretty printer andÐ functions to cpp as HOST_EXTRA_CFLAGS macroÐ - install go gdb functions & printerÐ gdb-printer.patchÐ - patch linker (src/cmd/ld/dwarf.c) to emit correct location of goÐ gdb functions and pretty printerÐ/textarea> Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð mode: {name: "changes"},Ð lineNumbers: true,Ð indentUnit: 4Ð });Ð </script>Ð MIME types defined: <code>text/x-rpm-changes</code>. Ð/article>Ð

public\assets\js\plugins\codemirror\mode\rpm\index.html


```
<!doctype html>Ðtitle>CodeMirror: RPM changes mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ð   <link
rel="stylesheet" href="../../lib/codemirror.css">Ð   <script src="../../lib/
codemirror.js"></script>Ð   <script src="rpm.js"></script>Ð   <link
rel="stylesheet" href="../../doc/docs.css">Ð   <style type="text/
css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid
black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">RPM</a>Ð </ul>Ð/div>Ðarticle>Ðh2>RPM changes mode</h2>Ð
<div><textarea id="code" name="code">Ð
-------------------------------------------------------------------Ðue Oct 18
13:58:40 UTC 2011 - misterx@example.comÐ Update to r60.3Ð Fixes bug in the
reflect packageÐ * disallow Interface method on Value obtained via unexported
nameÐ-------------------------------------------------------------------Ðhu
Oct  6 08:14:24 UTC 2011 - misterx@example.comÐ Update to r60.2Ð Fixes memory
leak in certain map typesÐ
-------------------------------------------------------------------Ðed Oct  5
14:34:10 UTC 2011 - misterx@example.comÐ Tweaks for gdb debuggingÐ go.spec
changes:Ð - move %go_arch definition to %prep sectionÐ - pass correct
location of go specific gdb pretty printer andÐ   functions to cpp as
HOST_EXTRA_CFLAGS macroÐ - install go gdb functions & printerÐ gdb-
printer.patchÐ - patch linker (src/cmd/ld/dwarf.c) to emit correct location
of goÐ   gdb functions and pretty printerÐ/textarea></div>Ð   <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
        mode: {name: "rpm-changes"},Ð       lineNumbers: true,Ð
indentUnit: 4Ð     });Ð   </script>Ðh2>RPM spec mode</h2>Ð   Ð
<div><textarea id="code2" name="code2">ÐÐ spec file for package minidlnaÐÐ
Copyright (c) 2011, Sascha Peilicke <saschpe@gmx.de>ÐÐ All modifications and
additions to the file contributed by third partiesÐ remain the property of
their copyright owners, unless otherwise agredÐ upon. The license for this
file, and modifications and additions to theÐ file, is the same license as
for the pristine package itself (unless theÐ license for the pristine package
is not an Open Source License, in whichÐ case the license is the MIT
License). An "Open Source License" is aÐ license that conforms to the Open
Source Definition (Version 1.9)Ð published by the Open Source Initiative.Ð
Name:           libupnp6Ðersion:        1.6.13Ðelease:        0Ð
Summary:        Portable Universal Plug and Play (UPnP) SDKÐroup:
System/LibrariesÐicense:        BSD-3-ClauseÐrl:            http://
sourceforge.net/projects/pupnp/Ðource0:        http://
downloads.sourceforge.net/pupnp/libupnp-%{version}.tar.bz2ÐuildRoot:
%{_tmppath}/%{name}-%{version}-build%ÐdescriptionÐhe portable Universal Plug
and Play (UPnP) SDK provides support for buildingÐPnP-compliant control
points, devices, and bridges on several operatingÐystems.%package -n libupnp-
develÐummary:        Portable Universal Plug and Play (UPnP) SDKÐ
Group:          Development/Libraries/C and C++Ðrovides:
pkgconfig(libupnp)Ðequires:       %{name} = %{version}%ÐdescriptionÐ-n libupnp-
develÐhe portable Universal Plug and Play (UPnP) SDK provides support for
buildingÐPnP-compliant control points, devices, and bridges on several
operatingÐystems.%prep%setup -n libupnp-%{version}%build%configure --disable-
staticÐake %{?_smp_mflags}%install%makeinstallÐind %{buildroot} -type f -name
'*.la' -exec rm -f {} ';'%post -p /sbin/ldconfig%postun -p /sbin/ldconfigÐ
%files%defattr(-,root,root,-)%doc ChangeLog NEWS README TODO%{_libdir}/
libixml.so.*%{_libdir}/libthreadutil.so.*%{_libdir}/libupnp.so.*%files -n
libupnp-devel%defattr(-,root,root,-)%{_libdir}/pkgconfig/libupnp.pc%{_libdir}/
libixml.so%{_libdir}/libthreadutil.so%{_libdir}/libupnp.so%{_includedir}/upnp/Ð
%changelog</textarea></div>Ð
```

```
                                <script>Đ     var editor =
CodeMirror.fromTextArea(document.getElementById("code2"), {Đ       mode:
{name: "rpm-spec"},Đ       lineNumbers: true,Đ       indentUnit: 4Đ     });Đ
    </script>Đ   <p><strong>MIME types defined:</strong> <code>text/x-rpm-
spec</code>, <code>text/x-rpm-changes</code>.</p>Đ</article>Đ
```

public\assets\js\plugins\codemirror\mode\rst\index.html

<!doctype html>Ðtitle>CodeMirror: reStructuredText mode</title>Ðmeta charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="../../addon/mode/overlay.js"></script>Ð <script src="rst.js"></script>Ðstyle type="text/css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">reStructuredText</a>Ð </ul>Ð/div>Ðarticle>Ðh2>reStructuredText mode</h2>Ðform><textarea id="code" name="code">Ð. This is an excerpt from Sphinx documentation: http://sphinx.pocoo.org/_sources/rest.txtÐ. highlightlang::restÐ. _rst-primer:ÐeStructuredText PrimerÐ==========ÐThis section is a brief introduction to reStructuredText (reST) concepts andÐsyntax, intended to provide authors with enough information to author documentsÐ productively. Since reST was designed to be a simple, unobtrusive markupÐ language, this will not take too long.Ð. seealso::Ð The authoritative `reStructuredText User DocumentationÐ  <http://docutils.sourceforge.net/rst.html>`_. The "ref" links in thisÐ document link to the description of the individual constructs in the reSTÐ reference.ÐparagraphsÐ---------ÐThe paragraph (:duref:`ref <paragraphs>`) is the most basic block in a reSTÐ document. Paragraphs are simply chunks of text separated by one or more blankÐ lines. As in Python, indentation is significant in reST, so all lines of theÐ same paragraph must be left-aligned to the same level of indentation.Ð. _inlinemarkup:ÐInline markupÐ------------ÐThe standard reST inline markup is quite simple: useÐ one asterisk: ``*text*`` for emphasis (italics),Ð two asterisks: ``**text**`` for strong emphasis (boldface), andÐ backquotes: ``text`` for code samples.ÐIf asterisks or backquotes appear in running text and could be confused withÐinline markup delimiters, they have to be escaped with a backslash.ÐBe aware of some restrictions of this markup:Ð it may not be nested,Ð content may not start or end with whitespace: ``* text*`` is wrong,Ð it must be separated from surrounding text by non-word characters. Use aÐ backslash escaped space to work around that: ``thisis\ *one*\ word``.ÐThese restrictions may be lifted in future versions of the docutils.ÐreST also allows for custom "interpreted text roles"', which signify that theÐenclosed text should be interpreted in a specific way. Sphinx uses this toÐprovide semantic markup and cross-referencing of identifiers, as described inÐthe appropriate section. The general syntax is ``:rolename:`content```.ÐStandard reST provides the following roles:Ð * :durole:`emphasis` -- alternate spelling for ``*emphasis*``Ð * :durole:`strong` -- alternate spelling for ``**strong**``Ð * :durole:`literal` -- alternate spelling for ``literal``Ð * :durole:`subscript` -- subscript textÐ :durole:`superscript` -- superscript textÐ :durole:`title-reference` -- for titles of books, periodicals, and otherÐ materialsÐSee :ref:`inline-markup` for roles added by Sphinx.ÐLists and Quote-like blocksÐ----------ÐList markup (:duref:`ref <bullet-lists>`) is natural: just place an asterisk atÐthe start of a paragraph and indent properly. The same goes for numbered lists;ÐThey can also be autonumbered using a ``#`` sign::Ð * This is a bulleted list.Ð * It has two items, the secondÐ item uses two lines.Ð 1. This is a numbered list.Ð 2. It has two items too.Ð #. This is a numbered list.Ð #. It has two items too.Ð Nested lists are possible, but be aware that they must be separated from theÐ parent list items by blank lines::Ð * this isÐ * a listÐ * with a nested listÐ * and some subitemsÐ * and here the parent list continuesÐdefinition lists (:duref:`ref <definition-lists>`) are created as follows::Ð term (up to a line of text)Ð Definition of the term, which must be indentedÐ and can even consist of multiple paragraphsÐ

Ð next termÐ
Description.Ð Note that the term cannot have more than one line of text.Ð Quoted
paragraphs (:duref:`ref <block-quotes>`) are created by just indentingÐ
them more than the surrounding paragraphs.Ð Line blocks (:duref:`ref <line-
blocks>`) are a way of preserving line breaks::Ð | These lines areÐ |
broken exactly like inÐ | the source file.Ð There are also several more
special blocks available:Ð field lists (:duref:`ref <field-lists>`)Ð
option lists (:duref:`ref <option-lists>`)Ð quoted literal blocks
(:duref:`ref <quoted-literal-blocks>`)Ð doctest blocks (:duref:`ref
<doctest-blocks>`)Ð Source CodeÐ----------Ð Literal code blocks
(:duref:`ref <literal-blocks>`) are introduced by ending aÐ paragraph
with the special marker ``::``. The literal block must be indentedÐ (and, like
all paragraphs, separated from the surrounding ones by blank lines)::Ð This
is a normal text paragraph. The next paragraph is a code sample::Ð   It is
not processed in any way, exceptÐ   that the indentation is removed.Ð
It can span multiple lines.Ð This is a normal text paragraph again.Ð The
handling of the ``::`` marker is smart:Ð If it occurs as a paragraph of its
own, that paragraph is completely leftÐ out of the document.Ð If it is
preceded by whitespace, the marker is removed.Ð If it is preceded by non-
whitespace, the marker is replaced by a singleÐ colon.Ð That way, the second
sentence in the above example's first paragraph would beÐ rendered as "The next
paragraph is a code sample:".Ð. _rst-tables:Ð TablesÐ-----Ð Two forms of tables
are supported. For *grid tables* (:duref:`refÐ <grid-tables>`), you have
to "paint" the cell grid yourself. They look likeÐ this::Ð
+------------------------+------------+----------+----------+Ð | Header row,
column 1 | Header 2 | Header 3 | Header 4 |Ð | (header rows optional)
| | | |Ð
+========================+============+==========+==========+Ð | body row 1,
column 1 | column 2 | column 3 | column 4 |Ð +------------------------
+------------+----------+----------+Ð | body row 2 | ...
| ... | |Ð +------------------------+------------+----------
+----------+Ð Simple tables* (:duref:`ref <simple-tables>`) are easier
to write, butÐ limited: they must contain more than one row, and the first
column cannotÐ contain multiple lines. They look like this::Ð ===== =====
=======Ð A   B   A and BÐ ===== ===== =======Ð False False FalseÐ
   True   False FalseÐ False True   FalseÐ True   True   TrueÐ =====
===== =======Ð Hyperlinks:Ð---------Ð External linksÐ^^^^^^^^^^^^^^Ð Use ```Link
text <http://example.com/>`_`` for inline web links. If the linkÐ text
should be the web address, you don't need special markup at all, the parserÐ
finds links and mail addresses in ordinary text.Ð You can also separate the
link and the target definition (:duref:`refÐ <hyperlink-targets>`), like
this::Ð This is a paragraph that contains `a link`_.Ð .. _a link: http://
example.com/Ð Internal linksÐ^^^^^^^^^^^^^^Ð Internal linking is done via a
special reST role provided by Sphinx, see theÐ section on specific
markup, :ref:`ref-role`.Ð SectionsÐ-------Ð Section headers (:duref:`ref
<sections>`) are created by underlining (andÐ optionally overlining) the
section title with a punctuation character, at leastÐ as long as the text::Ð
==================Ð This is a headingÐ ==================Ð Normally, there are
no heading levels assigned to certain characters as theÐ structure is
determined from the succession of headings. However, for theÐ Python
documentation, this convention is used which you may follow:Ð ``#`` with
overline, for partsÐ ``*`` with overline, for chaptersÐ ``=``, for sectionsÐ
``-``, for subsections:Ð ``^``, for subsubsections:Ð ``"``, for paragraphsÐ Of
course, you are free to use your own marker characters (see the reSTÐ
documentation), and use a deeper nesting level, but keep in mind that mostÐ
target formats (HTML, LaTeX) have a limited supported nesting depth.Ð Explicit
MarkupÐ--------------Ð Explicit markup" (:duref:`ref <explicit-markup-
blocks>`) is used in reST forÐ most constructs that need special handling,
such as footnotes,Ð specially-highlighted paragraphs, comments, and generic
directives.Ð

Ð An explicit markup block begins with a line starting with ``..`` followed by Ðwhitespace and is terminated by the next paragraph at the same level of Ðindentation. (There needs to be a blank line between explicit markup and normal Ðparagraphs. This may all sound a bit complicated, but it is intuitive enough Ðwhen you write it.)Ð. _directives:ÐDirectivesÐ---------Ð A directive (:duref:`ref <directives>`) is a generic block of explicit markup.Ðesides roles, it is one of the extension mechanisms of reST, and Sphinx makes Ðheavy use of it.Ðocutils supports the following directives:Ð Admonitions: :dudir:`attention`, :dudir:`caution`, :dudir:`danger`,Ð :dudir:`error`, :dudir:`hint`, :dudir:`important`, :dudir:`note`,Ð :dudir:`tip`, :dudir:`warning` and the generic :dudir:`admonition`.Ð (Most themes style only "note" and "warning" specially.)Ð Images:Ð - :dudir:`image` (see also Images_ below)Ð - :dudir:`figure` (an image with caption and optional legend)Ð Additional body elements:Ð - :dudir:`contents` (a local, i.e. for the current file only, table ofÐ contents)Ð - :dudir:`container` (a container with a custom class, useful to generate anÐ outer ``<div>`` in HTML)Ð - :dudir:`rubric` (a heading without relation to the document sectioning)Ð - :dudir:`topic`, :dudir:`sidebar` (special highlighted body elements)Ð - :dudir:`parsed-literal` (literal block that supports inline markup)Ð - :dudir:`epigraph` (a block quote with optional attribution line)Ð - :dudir:`highlights`, :dudir:`pull-quote` (block quotes with their ownÐ class attribute)Ð - :dudir:`compound` (a compound paragraph)Ð * Special tables:Ð - :dudir:`table` (a table with title)Ð - :dudir:`csv-table` (a table generated from comma-separated values)Ð - :dudir:`list-table` (a table generated from a list of lists)Ð Special directives:Ð - :dudir:`raw` (include raw target-format markup)Ð - :dudir:`include` (include reStructuredText from another file)Ð -- in Sphinx, when given an absolute include file path, this directive takesÐ it as relative to the source directoryÐ - :dudir:`class` (assign a class attribute to the next element) [1]_Ð HTML specifics:Ð - :dudir:`meta` (generation of HTML ``<meta>`` tags)Ð - :dudir:`title` (override document title)Ð Influencing markup:Ð - :dudir:`default-role` (set a new default role)Ð - :dudir:`role` (create a new role)Ð Since these are only per-file, better use Sphinx' facilities for setting theÐ :confval:`default_role`.Ðo *not* use the directives :dudir:`sectnum`, :dudir:`header` andÐdudir:`footer`.Ðirectives added by Sphinx are described in :ref:`sphinxmarkup`.Ðasically, a directive consists of a name, arguments, options and content. (KeepÐhis terminology in mind, it is used in the next chapter describing customÐirectives.) Looking at this example, ::Ð .. function:: foo(x)Ð foo(y, z)Ð :module: some.module.nameÐ Return a line of text input from the user.Ð`function`` is the directive name.  It is given two arguments here, theÐ remainder of the first line and the second line, as well as one optionÐ ``module`` (as you can see, options are given in the lines immediately followingÐhe arguments and indicated by the colons). Options must be indented to theÐame level as the directive content.Ðhe directive content follows after a blank line and is indented relative to theÐirective start.Ð ImagesÐ-----ÐeST supports an image directive (:dudir:`ref <image>`), used like so::Ð .. image:: gnu.pngÐ (options)Ðhen used within Sphinx, the file name given (here ``gnu.png``) must either beÐelative to the source file, or absolute which means that they are relative toÐhe top source directory. For example, the file ``sketch/spam.rst`` could referÐo the image ``images/spam.png`` as ``../images/spam.png`` orÐ`/images/spam.png``.Ðphinx will automatically copy image files over to a subdirectory of the outputÐ directory on building (e.g. the ``_static`` directory for HTML output.)Ð Interpretation of image size options (``width`` and ``height``) is as follows:Ð if the size has no unit or the unit is pixels, the given size will only beÐ respected for output channels that support pixels (i.e. not in LaTeX output).Ð Other units (like ``pt`` for points) will be used for HTML and LaTeX output.Ð Sphinx extends the standard docutils behavior by allowing an asterisk for theÐ extension::Ð

Ð .. image:: gnu.*Ðphinx then searches for all images matching the provided pattern and determinesÐheir type. Each builder then chooses the best image out of these candidates.Ðor instance, if the file name ``gnu.*`` was given and two files :file:`gnu.pdf`Ðnd :file:`gnu.png` existed in the source tree, the LaTeX builder would chooseÐhe former, while the HTML builder would prefer the latter.Ð. versionchanged:: 0.4Ð Added the support for file names ending in an asterisk.Ð. versionchanged:: 0.6Ð Image paths can now be absolute.ÐootnotesÐ--------Ðor footnotes (:duref:`ref <footnotes>`), use ``[#name]_`` to mark the footnoteÐocation, and add the footnote body at the bottom of the document after aÐFootnotes" rubric heading, like so::Ð Lorem ipsum [#f1]_ dolor sit amet ... [#f2]_Ð .. rubric:: FootnotesÐ .. [#f1] Text of the first footnote.Ð .. [#f2] Text of the second footnote.ÐYou can also explicitly number the footnotes (``[1]_``) or use auto-numberedÐ footnotes without names (``[#]_``).ÐitationsÐ--------ÐtandardreST citations (:duref:`ref <citations>`) are supported, with theÐdditional feature that they are "global", i.e. all citations can be referencedÐrom all files. Use them like so::Ð Lorem ipsum [Ref]_ dolor sit amet.Ð .. [Ref] Book or article reference, URL or whatever.Ðitation usage is similar to footnote usage, but with a label that is notÐumeric or begins with ``#``.ÐubstitutionsÐ ----------ÐeST supports "substitutions" (:duref:`ref <substitution-definitions>`), whichÐre pieces of text and/or markup referred to in the text by ``|name|``. TheyÐre defined like footnotes with explicit markup blocks, like this::Ð .. |name| replace:: replacement *text*Ðr this::Ð .. |caution| image:: warning.pngÐ   :alt: Warning!ÐSee the :duref:`reST reference for substitutions <substitution-definitions>`Ð for details.ÐIf you want to use some substitutions for all documents, put them intoÐconfval:`rst_prolog` or put them into a separate file and include it into allÐocuments you want to use them in, using the :rst:dir:`include` directive. (BeÐure to give the include file a file name extension differing from that of otherÐource files, to avoid Sphinx finding it as a standalone document.)ÐphinxdefinesÐome default substitutions, see :ref:`default-substitutions`.ÐommentsÐ--------ÐEvery explicit markup block which isn't a valid markup construct (like theÐootnotes above) is regarded as a comment (:duref:`ref <comments>`). ForÐxample::Ð .. This is a comment.ÐYou can indent text after a comment start to form multiline comments::Ð ..Ð   This whole indented blockÐ   is a comment.Ð   Still in the comment.ÐSource encodingÐ--------------ÐSince the easiest way to include special characters like em dashes or copyrightÐigns in reST is to directly write them as Unicode characters, one has toÐpecify an encoding. Sphinx assumes source files to be encoded in UTF-8 byÐefault; you can change this with the :confval:`source_encoding` config value.ÐotchasÐ--------ÐThere are some problems one commonly runs into while authoring reST documents:Ð **Separation of inline markup:** As said above, inline markup spans must beÐ separated from the surrounding text by non-word characters, you have to use aÐ backslash-escaped space to get around that. See `the referenceÐ <http://docutils.sf.net/docs/ref/rst/restructuredtext.html#inline-markup>`_Ð for the details.Ð **No nested inline markup:** Something like ``*see :func:`foo`*`` is notÐ possible.Ð. rubric:: FootnotesÐ. [1] When the default domain contains a :rst:dir:`class` directive, this directiveÐ will be shadowed. Therefore, Sphinx re-exports it as :rst:dir:`rst-class`.Ð</textarea></form>Ð <script>Ð   var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð lineNumbers: true,Ð   });Ð </script>Ð Ð   The <code>python</code> mode will be used for highlighting blocksÐ   containing Python/IPython terminal sessions: blocks starting withÐ   <code>>>></code> (for Python) or <code>In [num]:</code> (forÐ   IPython).Ð Further, the <code>stex</code> mode will be used for highlightingÐ blocks containing LaTex code.Ð Ð MIME types defined: <code>text/x-rst</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\ruby\index.html

<!doctype html>Ðtitle>CodeMirror: Ruby mode</title>Ðmeta charset="utf-8"/>Ð <link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript src="ruby.js"></script>Ðstyle>Ð .CodeMirror {border-top: 1px solid black; border-bottom: 1px solid black;}Ð .cm-s-default span.cm-arrow { color: red; }Ð </style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">Ruby</a>Ð </ul>Ð/div>Ðarticle>Ð <h2>Ruby mode</h2>Ðform><textarea id="code" name="code">Ð Code from http://sandbox.mc.edu/~bennet/ruby/code/poly_rb.htmlÐÐ This program evaluates polynomials. It first asks for the coefficientsÐ of a polynomial, which must be entered on one line, highest-order first.Ð It then requests values of x and will compute the value of the poly forÐ each x. It will repeatly ask for x values, unless you the user entersÐ a blank line. It that case, it will ask for another polynomial. If theÐ user types quit for either input, the program immediately exits.ÐÐÐ Function to evaluate a polynomial at x. The polynomial is givenÐ as a list of coefficients, from the greatest to the least.Ðdef polyval(x, coef)Ð sum = 0Ð coef = coef.clone # Don't want to destroy the originalÐ while trueÐ sum += coef.shift # Add and remove the next coefÐ break if coef.empty? # If no more, done entirely.Ð sum *= x # This happens the right number of times.Ð endÐ return sumÐendÐÐ Function to read a line containing a list of integers and returnÐ them as an array of integers. If the string conversion fails, itÐ throws TypeError. If the input line is the word 'quit', then itÐ converts it to an end-of-file exceptionÐdef readints(prompt)Ð # Read a lineÐ print promptÐ line = readline.chompÐ raise EOFError.new if line == 'quit' # You can also use a real EOF.Ð Ð # Go through each item on the line, converting each one and adding itÐ # to retval.Ð retval = [ ]Ð for str in line.split(/\s+/)Ð if str =~ /^\-?\d+$/Ð retval.push(str.to_i)Ð elseÐ raise TypeError.newÐ endÐ endÐ return retvalÐendÐÐ Take a coeff and an exponent and return the string representation, ignoringÐ the sign of the coefficient.Ðdef term_to_str(coef, exp)Ð ret = ""Ð # Show coeff, unless it's 1 or at the rightÐ coef = coef.absÐ ret = coef.to_s unless coef == 1 && exp > 0Ð ret += "x" if exp > 0 # x if exponent not 0Ð ret += "^" + exp.to_s if exp > 1 # ^exponent, if > 1.Ð return retÐendÐÐ Create a string of the polynomial in sort-of-readable form.Ðdef polystr(p)Ð # Get the exponent of first coefficient, plus 1.Ð exp = p.lengthÐ # Assign exponents to each term, making pairs of coeff and exponent,Ð # Then get rid of the zero terms.Ð p = (p.map { |c| exp -= 1; [c, exp] }).select { |p| p[0] != 0 }Ð # If there's nothing left, it's a zeroÐ return "0" if p.empty?Ð # *** Now p is a non-empty list of [coef, exponent] pairs. ***Ð # Convert the first term, preceded by a "-" if it's negative.Ð result = (if p[0][0] < 0 then "-" else "" end) + term_to_str(*p[0])Ð # Convert the rest of the terms, in each case adding the appropriateÐ # + or - separating them. Ð for term in p[1...p.length]Ð # Add the separator then the rep. of the term.Ð result += (if term[0] < 0 then " - " else " + " end) + Ð term_to_str(*term)Ð endÐ return resultÐendÐ ÐÐ Run until some kind of endfile.ÐbeginÐ # Repeat until an exception or quit gets us out.Ð while trueÐ # Read a poly until it works. An EOF will except out of theÐ # program.Ð print "\n"Ð beginÐ poly = readints("Enter a polynomial coefficients: ")Ð rescue TypeErrorÐ print "Try again.\n"Ð retryÐ endÐ break if poly.empty?Ð

```
            Ð       # Read and evaluate x values until the user types a blank
line.Ð       # Again, an EOF will except out of the pgm.Ð       while trueÐ
             # Request an integer.Ð           print "Enter x value or blank
line: "Ð           x = readline.chompÐ           break if x == ''Ð
raise EOFError.new if x == 'quit'Ð           # If it looks bad, let's try
again.Ð           if x !~ /^\-?\d+$/Ð               print "That doesn't look
like an integer.  Please try again.\n"Ð               nextÐ           endÐ
             # Convert to an integer and print the result.Ð           x =
x.to_iÐ           print "p(x) = ", polystr(poly), "\n"Ð           print "p(",
x, ") = ", polyval(x, poly), "\n"Ð       endÐ   endÐrescue EOFErrorÐ   print
"\n=== EOF ===\n"Ðrescue Interrupt, SignalExceptionÐ   print "\n===
Interrupted ===\n"ÐelseÐ   print "--- Bye ---\n"ÐendÐ</textarea></form>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: "text/
x-ruby",Ð       matchBrackets: true,Ð       indentUnit: 4Ð     });Ð   </
script>Ð   <p><strong>MIME types defined:</strong> <code>text/x-ruby</code>.</
p>Ð   <p>Development of the CodeMirror Ruby mode was kindly sponsoredÐ   by
<a href="http://ubalo.com/">Ubalo</a>, who holdÐ   the <a
href="LICENSE">license</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\rust\index.html

```
<!doctype html>Ðtitle>CodeMirror: Rust mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="rust.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Rust</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>Rust mode</h2>Ðdiv><textarea id="code" name="code">Ø/ Demo
code.Ðtype foo<T> = int;Ðnum bar {Ð   some(int, foo<float>),Ð   none}ÐÐfn
check_crate(x: int) {Ð   let v = 10;Ð   alt foo {Ð     1 to 3 {Ð
print_foo();Ð       if x {Ð           blah() + 10;Ð       }Ð     }Ð     (x,
y) { "bye" }Ð     _ { "hi" }Ð   }}ÐØ/textarea></div>Ð   <script>Ð     var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: trueÐ     });Ð   </script>Ð   <p><strong>MIME types defined:</
strong> <code>text/x-rustsrc</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\sass\index.html


```
<!doctype html>Ðtitle>CodeMirror: Sass mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="sass.js"></script>Ðstyle>.CodeMirror {border: 1px solid #ddd; font-
size:12px; height: 400px}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Sass</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Sass mode</h2>Ðform><textarea id="code" name="code">// Variable
DefinitionsÐpage-width:    800pxÐsidebar-width: 200pxÐprimary-color: #eeeeeeÐ
// Global AttributesÐbodyÐ font:Ð   family: sans-serifÐ   size: 30emÐ
weight: boldÐ/ Scoped StylesÐcontentsÐ width: $page-widthÐ #sidebarÐ   float:
rightÐ   width: $sidebar-widthÐ #mainÐ   width: $page-width - $sidebar-widthÐ
    background: $primary-colorÐ   h2Ð     color: blueÐfooterÐ height: 200pxÐ/
textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers : true,Ð       matchBrackets : trueÐ     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-sass</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\scheme\index.html

<!doctype html>Ðtitle>CodeMirror: Scheme mode</title>Ðmeta charset="utf-8"/>Ð <link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="scheme.js"></script>Ðstyle>.CodeMirror {background: #f8f8f8;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">Scheme</a>Ð </ul>Ðdiv>Ðarticle>Ð <h2>Scheme mode</h2>Ðform><textarea id="code" name="code">Ð; See if the input starts with a given symbol.Ð(define (match-symbol input pattern)Ð (cond ((null? (remain input)) #f)Ð,†W cò †6 " ‡&VÖ –â –ç WB’’ GFW&â’ ‡"Ö6G" –ç WB’• (else #f)))Ð; Allow the input to start with one of a list of patterns.Ð(define (match-or input pattern)Ð (cond ((null? pattern) #f)Ð,†Ö F6,× GFW&â –ç WB (car pattern)))Ð†VÇ6R †Ö F6,Ö÷" –ç WB †6G" GFW&â’’’’Ð; Allow a sequence of patterns.Ð(define (match-seq input pattern)Ð (if (null? pattern)Ð inputÐ (let ((match (match-pattern input (car pattern))))Ð†–b Ö F6, †Ö F6,×6W match (cdr pattern)) #f)))))Ð; Match with the pattern but no problem if it does not match.Ð(define (match-opt input pattern)Ð (let ((match (match-pattern input (car pattern))))Ð (if match match input)))Ð; Match anything (other than '()), until pattern is found. The rather Ð; clumsy form of requiring an ending pattern is needed to decide where Ð; the end of the match is. If none is given, this will match the rest Ð; of the sentence.Ð(define (match-any input pattern)Ð (cond ((null? (remain input)) #f)Ð,†çVÆÃò GFW&â’ †bÖ6öç2 ‡&VÖ –â input) (clear-remain input)))Ð†VÇ6] †ÆWB ,† 67VÒÖ ç’ †6öÆÆV7F÷"’’‘ †FVf–æR (match-pattern-any input pattern)Ð †6öæB ,†çVÆÃò ‡&VÖ –â –ç WB’’ 6b™ (else (accum-any (car (remain input)))™’ †6öæB ,†Ö F6,× GFW&â ‡"Ö6G" –ç WB’ pattern))™’ †VÇ6R †Ö F6,× GFW&âÖ ç’ ‡"Ö6G" –ç WB’ GFW&â’’’’’• †ÆWB ((retval (match-pattern-any input (car pattern))))Ð †–b &WGf Ï (f-cons (accum-any) retval)™ #f)))))}ÐÐtextarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {});Ð </script>Ð MIME types defined: <code>text/x-scheme</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\shell\index.html


```
<!doctype html>Ðtitle>CodeMirror: Shell mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel=stylesheet
href=../../lib/codemirror.css>Ðscript src=../../lib/codemirror.js></script>Ð
<script src="../../addon/edit/matchbrackets.js"></script>Ðscript
src=shell.js></script>Ðstyle type=text/css>Ð .CodeMirror {border-top: 1px
solid black; border-bottom: 1px solid black;}Ð/style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Shell</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Shell mode</h2>Ðtextarea id=code>Ð!/bin/bashÐ clone the
repositoryÐgit clone http://github.com/garden/treeÐ generate HTTPS credentialsÐ
cd treeÐopenssl genrsa -aes256 -out https.key 1024Ðopenssl req -new -nodes -key
https.key -out https.csrÐopenssl x509 -req -days 365 -in https.csr -signkey
https.key -out https.crtÐcp https.key{,.orig}Ðopenssl rsa -in https.key.orig -
out https.keyÐ start the server in HTTPS modeÐcd webÐsudo node ../server.js 443
'yes' &gt;&gt; ../node.log &amp;Ð here is how to stop the serverÐfor pid in
`ps aux | grep 'node ../server.js' | awk '{print $2}'` ; doÐ sudo kill -9
$pid 2&gt; /dev/nullÐdoneÐexit 0</textarea>Ðscript>Ð var editor =
CodeMirror.fromTextArea(document.getElementById('code'), {Ð   mode: 'shell',Ð
    lineNumbers: true,Ð   matchBrackets: trueÐ });Ð/script>Ðp><strong>MIME
types defined:</strong> <code>text/x-sh</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\sieve\index.html


```
<!doctype html>Ðtitle>CodeMirror: Sieve (RFC5228) mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="sieve.js"></script>Ðstyle>.CodeMirror
{background: #f8f8f8;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Sieve (RFC5228)</a>Ð </ul>Ð/div>Ð
<article>Ðh2>Sieve (RFC5228) mode</h2>Ðform><textarea id="code" name="code">ÐÐ
# Example Sieve FilterÐ Declare any optional features or extension used by
the scriptÐÐrequire ["fileinto", "reject"];ÐÐ Reject any large messages (note
that the four leading dots getÐ "stuffed" to three)ÐÐif size :over 1MÐ{Ð reject
text:Ðlease do not send me large attachments.Ðut your file on a server and
send me the URL.ÐThank you.Ð... FredÐ}ÐÐ stop;ÐÐÐ Handle messages from known
mailing listsÐ Move messages from IETF filter discussion list to filter folderÐ
#Ðif header :is "Sender" "owner-ietf-mta-filters@imc.org"{Ð fileinto
"filter";  # move to "filter" folderÐ}ÐÐ Keep all messages to or from people
in my companyÐÐelsif address :domain :is ["From", "To"] "example.com"{Ð
keep;               # keep in "In" folderÐ}ÐÐ Try and catch unsolicited
email.  If a message is not to me,Ð or it contains a subject known to be
spam, file it away.ÐÐelsif anyof (not address :all :containsÐ
["To", "Cc", "Bcc"] "me@example.com",Ð            header :matches "subject"Ð
               ["*make*money*fast*", "*university*dipl*mas*"]){Ð # If message
header does not contain my address,Ð # it's from a list.Ð fileinto "spam";
# move to "spam" folderÐ}ÐelseÐ{Ð # Move all other (non-company) mail to
"personal"Ð # folder.Ð fileinto "personal";Ð}Ð/textarea></form>Ð   <script>Ð
      var editor = CodeMirror.fromTextArea(document.getElementById("code"),
{});Ð   </script>Ð   <p><strong>MIME types defined:</strong>
<code>application/sieve</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\slim\index.html


```
<!doctype html>Ðtitle>CodeMirror: SLIM mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
ambiance.css">Ðscript src="https://code.jquery.com/jquery-1.11.1.min.js"></
script>Ðscript src="https://code.jquery.com/ui/1.11.0/jquery-ui.min.js"></
script>Ðlink rel="stylesheet" href="https://code.jquery.com/ui/1.11.0/themes/
smoothness/jquery-ui.css">Ðscript src="../../lib/codemirror.js"></script>Ð
<script src="../xml/xml.js"></script>Ðscript src="../htmlembedded/
htmlembedded.js"></script>Ðscript src="../htmlmixed/htmlmixed.js"></script>Ð
<script src="../coffeescript/coffeescript.js"></script>Ðscript src="../
javascript/javascript.js"></script>Ðscript src="../ruby/ruby.js"></script>Ð
<script src="../markdown/markdown.js"></script>Ðscript src="slim.js"></script>Ð
<style>.CodeMirror {background: #f8f8f8;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">SLIM</a>Ð </ul>Ð
</div>Ðarticle>Ð <h2>SLIM mode</h2>Ð <form><textarea id="code" name="code">Ð
bodyÐ tableÐ   - for user in usersÐ     td id="user_#{user.id}"
class=user.roleÐ       a href=user_action(user, :edit) Edit #{user.name}Ð
        a href=(path_to_user user) = user.nameÐbodyÐ h1(id="logo") = page_logoÐ
  h2[id="tagline" class="small tagline"] = page_taglineÐh2[id="tagline"Ð
class="small tagline"] = page_taglineÐh1 id = "logo" = page_logoÐh2 [ id =
"tagline" ] = page_taglineÐ commentÐ second lineÐ! html commentÐ  second lineÐ
<!-- html comment -->Ða href="#{'hello' if set}">link</a>Ða.slim href="work"
disabled=false running==:atom Text <b>bold</b>Ðclazz data-id="test" ==
'hello' unless quarkÐ| Text mode #{12}Ð  Second lineÐ x ||= :ruby_atomÐ
#menu.leftÐ - @env.each do |x|Ð   li: a = xÐ@dyntag attr="val"Ðfirst *{:class
=> [:second, :third]} TextÐsecond class=["text","more"]Ðthird
class=:text,:symbolÐ </textarea></form>Ð <script>Ð   var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð     lineNumbers:
true,Ð     theme: "ambiance",Ð     mode: "application/x-slim"Ð   });Ð
$('.CodeMirror').resizable({Ð     resize: function() {Ð
editor.setSize($(this).width(), $(this).height());Ð       //editor.refresh();Ð
      }Ð   });Ð </script>Ð <p><strong>MIME types defined:</strong>
<code>application/x-slim</code>.</p>Ð <p>Ð   <strong>Parsing/Highlighting
Tests:</strong>Ð   <a href="../../test/index.html#slim_*">normal</a>,Ð   <a
href="../../test/index.html#verbose,slim_*">verbose</a>.Ð </p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\smalltalk\index.html


```
<!doctype html>Ðtitle>CodeMirror: Smalltalk mode</title>Ðmeta charset="utf-8"/
>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="smalltalk.js"></script>Ðstyle>Ð     .CodeMirror {border: 2px solid #dee;
border-right-width: 10px;}Ð     .CodeMirror-gutter {border: none; background:
#dee;}Ð     .CodeMirror-gutter pre {color: white; font-weight: bold;}Ð   </
style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Smalltalk</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Smalltalk mode</h2>Ð
<form><textarea id="code" name="code">Ð Ð   This is a test of the Smalltalk
codeÐÐseaside.WAComponent subclass: #MyCounter [Ð   | count |Ð   MyCounter
class &gt;&gt; canBeRoot [ ^true ]Ð   initialize [Ð       super initialize.Ð
        count := 0.Ð   ]Ð   states [ ^{ self } ]Ð   renderContentOn: html [Ð
        html heading: count.Ð       html anchor callback: [ count := count +
1 ]; with: '++'.Ð       html space.Ð       html anchor callback: [ count :=
count - 1 ]; with: '--'.Ð   ]ÐMyCounter registerAsApplication: 'mycounter'Ð/
textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       matchBrackets: true,Ð       mode: "text/x-stsrc",Ð
        indentUnit: 4Ð     });Ð   </script>Ð   <p>Simple Smalltalk mode.</p>Ð
    <p><strong>MIME types defined:</strong> <code>text/x-stsrc</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\smarty\index.html


```
<!doctype html>Ðtitle>CodeMirror: Smarty mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="smarty.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Smarty</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Smarty mode</h2>Ðform><textarea id="code" name="code">Ð
{extends file="parent.tpl"}Ð{include file="template.tpl"}Ð{* some example
Smarty content *}Ð{if isset($name) && $name == 'Blog'}Ð This is a {$var}.Ð
{$integer = 451}, {$array[] = "a"}, {$stringvar = "string"}Ð {assign
var='bob' value=$var.prop}Ð{elseif $name == $foo}Ð {function name=menu level=0}Ð
    {foreach $data as $entry}Ð     {if is_array($entry)}Ð       - {$entry@key}Ð
        {menu data=$entry level=$level+1}Ð     {else}Ð       {$entry}Ð     {/
if}Ð   {/foreach}Ð {/function}Ð{/if}</textarea></form>Ð   <script>Ð     var
editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       mode: "smarty"Ð     });Ð   </script>Ð   <br />Ð
<h3>Smarty 2, custom delimiters</h3>Ð   <form><textarea id="code2"
name="code2">Ð{--extends file="parent.tpl"--}Ð{--include file="template.tpl"--}Ð
{--* some example Smarty content *--}Ð{--if isset($name) && $name == 'Blog'--}Ð
  This is a {--$var--}.Ð {--$integer = 451--}, {--$array[] = "a"--}, {--
$stringvar = "string"--}Ð {--assign var='bob' value=$var.prop--}Ð{--elseif
$name == $foo--}Ð {--function name=menu level=0--}Ð   {--foreach $data as
$entry--}Ð     {--if is_array($entry)--}Ð       - {--$entry@key--}Ð       {--
menu data=$entry level=$level+1--}Ð     {--else--}Ð       {--$entry--}Ð
{--/if--}Ð   {--/foreach--}Ð {--/function--}Ð{--/if--}</textarea></form>Ð
<script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code2"), {Ð
lineNumbers: true,Ð       mode: {Ð         name: "smarty",Ð
leftDelimiter: "{--",Ð         rightDelimiter: "--}"Ð       }Ð     });Ð   </
script>ÐÆ'" óÐÆƒ3å6Ö 'G’ 3Âöƒ3ÐÇFW‡F &V  –CÒ&6öFS2" æ ÖSÒ&6öFS2#Ñested tags
{$foo={counter one=1 two={inception}}+3} are now valid in Smarty 3.ÐÐscript>Ð
function test() {Ð6öç6öÆRæÆör,%6Ö 'G’ 2  W&Ö—G2 6–ævÆR 7W&Ç’ '& 6W2 föÆÆ÷vVB
by whitespace to NOT slip into Smarty mode.");ÐÐ/script>Ð{assign var=foo
value=[1,2,3]}Ð{assign var=foo value=['y'=>'yellow','b'=>'blue']}Ð{assign
var=foo value=[1,[9,8],3]}Ð{$foo=$bar+2} {* a comment *}Ð{$foo.bar=1}  {*
another comment *}Ð{$foo = myfunct(($x+$y)*3)}Ð{$foo = strlen($bar)}Ð
{$foo.bar.baz=1}, {$foo[]=1}Ðsmarty "dot" syntax (note: embedded {} are used
to address ambiguities):Ð{$foo.a.b.c}      => $foo['a']['b']['c']Ð{$foo.a.
$b.c}     => $foo['a'][$b]['c']Ð{$foo.a.{$b+4}.c} => $foo['a'][$b+4]['c']Ð
{$foo.a.{$b.c}}   => $foo['a'][$b['c']]Ð{$object->method1($x)->method2($y)}</
textarea>ÐÇ67&— CÍvar editor =
CodeMirror.fromTextArea(document.getElementById("code3"), {Ð–Æ–æTçVÖ&W'3¢ G'VRÍ
mode: "smarty",Ð—6Ö 'G•fW'6–öã¢™});Ð÷67&— CÐ   <p>A plain text/Smarty version
2 or 3 mode, which allows for custom delimiter tags.</p>Ð   <p><strong>MIME
types defined:</strong> <code>text/x-smarty</code></p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\smartymixed\index.html


```
<!doctype html>Ðtitle>CodeMirror: Smarty mixed mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../../mode/xml/xml.js"></script>Ðscript
src="../../mode/javascript/javascript.js"></script>Ðscript src="../../mode/
css/css.js"></script>Ðscript src="../../mode/htmlmixed/htmlmixed.js"></script>Ð
<script src="../../mode/smarty/smarty.js"></script>Ðscript src="../../mode/
smartymixed/smartymixed.js"></script>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Smarty mixed</a>Ð </ul>Ð/div>Ð
<article>Ðh2>Smarty mixed mode</h2>Ðform><textarea id="code" name="code">Ð{**Ð
@brief Smarty mixed modeÐ @author Ruslan OsmanovÐ @date 29.06.2013Ð}Ðhtml>Ð
<head>Ð <title>{$title|htmlspecialchars|truncate:30}</title>Ð/head>Ðbody
class="{$bodyclass}">Ð {* Multiline smartyÐ * comment, no {$variables} hereÐ
*}Ð {literal}Ð {literal} is just an HTML text.Ð <script type="text/
javascript">//<![CDATA[Ð   var a = {$just_a_normal_js_object : "value"};Ð
var myCodeMirror = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
      mode           : "smartymixed",Ð     tabSize        : 2,Ð
indentUnit     : 2,Ð     indentWithTabs : false,Ð     lineNumbers    : true,Ð
      smartyVersion  : 3Ð   });Ð   // ]]>Ð </script>Ð <style>Ð   /* CSS
content Ð   {$no_smarty} */Ð   .some-class { font-weight: bolder; color:
"orange"; }Ð </style>Ð {/literal}Ð {extends file="parent.tpl"}Ð {include
file="template.tpl"}Ð {* some example Smarty content *}Ð {if isset($name) &&
$name == 'Blog'}Ð   This is a {$var}.Ð   {$integer = 4511}, {$array[] = "a"},
{$stringvar = "string"}Ð   {$integer = 4512} {$array[] = "a"} {$stringvar =
"string"}Ð   {assign var='bob' value=$var.prop}Ð {elseif $name == $foo}Ð
{function name=menu level=0}Ð   {foreach $data as $entry}Ð     {if
is_array($entry)}Ð     - {$entry@key}Ð     {menu data=$entry level=$level+1}Ð
      {else}Ð     {$entry}Ð     {* OneÐ     * TwoÐ     * ThreeÐ     *}Ð     {/
if}Ð   {/foreach}Ð   {/function}Ð {/if}Ð </body>Ð <!-- R.O. -->Ð/html>Ð/
textarea></form>Ð   <script type="text/javascript">Ð     var myCodeMirror =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
mode           : "smartymixed",Ð       tabSize        : 2,Ð
indentUnit     : 2,Ð       indentWithTabs : false,Ð       lineNumbers    :
true,Ð       smartyVersion  : 3,Ð       matchBrackets  : true,Ð     });Ð   </
script>Ð   <p>The Smarty mixed mode depends on the Smarty and HTML mixed
modes. HTMLÐ   mixed mode itself depends on XML, JavaScript, and CSS modes.</
p>Ð   <p>It takes the same options, as Smarty and HTML mixed modes.</p>Ð
<p><strong>MIME types defined:</strong> <code>text/x-smarty</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\solr\index.html

```
<!doctype html>Ðtitle>CodeMirror: Solr mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="solr.js"></script>Ðstyle type="text/css">Ð .CodeMirror {Ð
    border-top: 1px solid black;Ð   border-bottom: 1px solid black;Ð }Ð
  .CodeMirror .cm-operator {Ð   color: orange;Ð }Ð/style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Solr</a>Ð </ul>Ð
</div>Ðarticle>Ð <h2>Solr mode</h2>Ð <div>Ð   <textarea id="code"
name="code">author:CamusÐtitle:"The Rebel" and author:CamusÐ
philosophy:Existentialism -author:KierkegaardÐardToSpell:Dostoevsky~Ðpublished:
[194* TO 1960] and author:(Sartre or "Simone de Beauvoir")</textarea>Ð </div>Ð
  <script>Ð   var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð     mode: 'solr',Ð
      lineNumbers: trueÐ   });Ð </script>Ð <p><strong>MIME types defined:</
strong> <code>text/x-solr</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\sparql\index.html

```
<!doctype html>Ðtitle>CodeMirror: SPARQL mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="sparql.js"></script>Ðstyle>.CodeMirror {border-top: 1px solid black;
border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">SPARQL</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>SPARQL mode</h2>Ðform><textarea id="code" name="code">ÐPREFIX a:
&lt;http://www.w3.org/2000/10/annotation-ns#>ÐPREFIX dc: &lt;http://purl.org/
dc/elements/1.1/>ÐPREFIX foaf: &lt;http://xmlns.com/foaf/0.1/>Ð Comment!Ð
SELECT ?given ?familyÐWHERE {Ð ?annot a:annotates &lt;http://www.w3.org/TR/rdf-
sparql-query/> .Ð ?annot dc:creator ?c .Ð OPTIONAL {?c foaf:given ?given ;Ð
                foaf:family ?family } .Ð FILTER isBlank(?c)ÐÐ}Ð/textarea></form>Ð
    <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
"application/x-sparql-query",Ð       matchBrackets: trueÐ     });Ð   </script>Ð
    <p><strong>MIME types defined:</strong> <code>application/x-sparql-query</
code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\sql\index.html


```
<!doctype html>Ðtitle>CodeMirror: SQL Mode for CodeMirror</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css" />Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="sql.js"></script>Ðlink rel="stylesheet"
href="../../addon/hint/show-hint.css" />Ðscript src="../../addon/hint/show-
hint.js"></script>Ðscript src="../../addon/hint/sql-hint.js"></script>Ðstyle>Ð
.CodeMirror {Ð   border-top: 1px solid black;Ð   border-bottom: 1px solid
black;ÐÐ       </style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">SQL Mode for CodeMirror</a>Ð </ul>Ð/
div>Ðarticle>Ðh2>SQL Mode for CodeMirror</h2>Ðform>Ð           <textarea
id="code" name="code">-- SQL Mode for CodeMirrorÐSELECT SQL_NO_CACHE DISTINCTÐ
@var1 AS `val1`, @'val2', @global.'sql_mode',Ð1.1 AS `float_val`, .14 AS
`another_float`, 0.09e3 AS `int_with_esp`,Ð0xFA5 AS `hex`, x'fa5' AS `hex2`,
0b101 AS `bin`, b'101' AS `bin2`,ÐDATE '1994-01-01' AS `sql_date`, { T
"1994-01-01" } AS `odbc_date`,Ð'my string', _utf8'your string', N'her string',Ð
        TRUE, FALSE, UNKNOWNÐe$ôÒ ET ÍÒÒ 7  6R æVVFVB  gFW" rÒÒ}2   Æ–æR
commentÐò¢ ×VÇF–Æ–æ]6öÖÖVçB  ¢ÿÄ”Ô•B   ôde4UB  ½/textarea>Ð           </form>Ð
            <p><strong>MIME types defined:</strong> Ð           <code><a
href="?mime=text/x-sql">text/x-sql</a></code>,Ð           <code><a href="?
mime=text/x-mysql">text/x-mysql</a></code>,Ð           <code><a href="?
mime=text/x-mariadb">text/x-mariadb</a></code>,Ð           <code><a href="?
mime=text/x-cassandra">text/x-cassandra</a></code>,Ð           <code><a
href="?mime=text/x-plsql">text/x-plsql</a></code>,Ð           <code><a href="?
mime=text/x-mssql">text/x-mssql</a></code>,Ð           <code><a href="?
mime=text/x-hive">text/x-hive</a></code>.Ð       </p>Ðscript>Ðwindow.onload =
function() {Ð var mime = 'text/x-mariadb';Ð // get mime typeÐ if
(window.location.href.indexOf('mime=') > -1) {Ð   mime =
window.location.href.substr(window.location.href.indexOf('mime=') + 5);Ð }Ð
window.editor = CodeMirror.fromTextArea(document.getElementById('code'), {Ð
mode: mime,Ð   indentWithTabs: true,Ð   smartIndent: true,Ð   lineNumbers:
true,Ð   matchBrackets : true,Ð   autofocus: true,Ð   extraKeys: {"Ctrl-
Space": "autocomplete"},Ð   hintOptions: {tables: {Ð     users: {name: null,
score: null, birthDate: null},Ð     countries: {name: null, population: null,
size: null}Ð   }}Ð });Ð;Ð/script>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\stex\index.html

```
<!doctype html>Ð<title>CodeMirror: sTeX mode</title>Ð<meta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ð<link rel="stylesheet"
href="../../lib/codemirror.css">Ð<script src="../../lib/codemirror.js"></
script>Ð<script src="stex.js"></script>Ð<style>.CodeMirror {background:
#f8f8f8;}</style>Ð<div id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">sTeX</a>Ð </ul>Ð</div>Ð<article>Ð
<h2>sTeX mode</h2>Ð<form><textarea id="code" name="code">Ð\begin{module}[id=bbt-
size]Ð\importmodule[balanced-binary-trees]{balanced-binary-trees}Ð
\importmodule[\KWARCslides{dmath/en/cardinality}]{cardinality}Ð\begin{frame}Ð
\frametitle{Size Lemma for Balanced Trees}Ð \begin{itemize}Ð \itemÐ
\begin{assertion}[id=size-lemma,type=lemma] Ð   Let $G=\tup{V,E}$ be a
\termref[cd=binary-trees]{balanced binary tree} Ð   of \termref[cd=graph-
depth,name=vertex-depth]{depth}$n>i$, then the setÐ    $\defeq{\livar{V}i}
{\setst{\inset{v}{V}}{\gdepth{v} = i}}$ ofÐ   \termref[cd=graphs-
intro,name=node]{nodes} at Ð   \termref[cd=graph-depth,name=vertex-depth]
{depth} $i$ hasÐ   \termref[cd=cardinality,name=cardinality]{cardinality} $
\power2i$.Ð  \end{assertion}Ð \itemÐ   \begin{sproof}[id=size-lemma-
pf,proofend=,for=size-lemma]{via induction over the depth $i$.}Ð
\begin{spfcases}{We have to consider two cases}Ð       \begin{spfcase}{$i=0$}Ð
          \begin{spfstep}[display=flow]Ð           then $\livar{V}
i=\set{\livar{v}r}$, where $\livar{v}r$ is the root, soÐ           $
\eq{\card{\livar{V}0},\card{\set{\livar{v}r}},1,\power20}$.Ð
\end{spfstep}Ð       \end{spfcase}Ð       \begin{spfcase}{$i>0$}Ð
\begin{spfstep}[display=flow]Ð          then $\livar{V}{i-1}$ contains $
\power2{i-1}$ vertexes Ð          \begin{justification}[method=byIH]
(IH)\end{justification}Ð         \end{spfstep}Ð         \begin{spfstep}Ð
           By the \begin{justification}[method=byDef]definition of a binaryÐ
              tree\end{justification}, each $\inset{v}{\livar{V}{i-1}}$ is a
leaf or hasÐ           two children that are at depth $i$.Ð
\end{spfstep}Ð         \begin{spfstep}Ð          As $G$ is
\termref[cd=balanced-binary-trees,name=balanced-binary-tree]{balanced} and $
\gdepth{G}=n>i$, $\livar{V}{i-1}$ cannot containÐ           leaves.Ð
\end{spfstep}Ð         \begin{spfstep}[type=conclusion]Ð          Thus $
\eq{\card{\livar{V}i},{\atimes[cdot]{2,\card{\livar{V}{i-1}}}},{\atimes[cdot]
{2,\power2{i-1}}},\power2i}$.Ð         \end{spfstep}Ð       \end{spfcase}Ð
      \end{spfcases}Ð   \end{sproof}Ð \item Ð   \begin{assertion}
[id=fbbt,type=corollary]•     A fully balanced tree of depth $d$ has $
\power2{d+1}-1$ nodes.Ð   \end{assertion}Ð \itemÐ     \begin{sproof}
[for=fbbt,id=fbbt-pf]{}Ð       \begin{spfstep}Ð         Let $\defeq{G}
{\tup{V,E}}$ be a fully balanced treeÐ       \end{spfstep}Ð
\begin{spfstep}Ð         Then $\card{V}=\Sumfromto{i}1d{\power2i}=
\power2{d+1}-1$.Ð       \end{spfstep}Ð     \end{sproof}Ð   \end{itemize}Ð
\end{frame}Ð\begin{note}Ð \begin{omtext}[type=conclusion,for=binary-tree]Ð
This shows that balanced binary trees grow in breadth very quickly, a
consequence ofÐ   this is that they are very shallow (and this compute very
fast), which is the essence ofÐ   the next result.Ð \end{omtext}Ð\end{note}Ð
\end{module}Ð%%% Local Variables: %%% mode: LaTeX%%% TeX-master: "all"%%% End:
\end{document}Ð</textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {});Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-stex</code>.</p>Ð
<p><strong>Parsing/Highlighting Tests:</strong> <a href="../../test/
index.html#stex_*">normal</a>,  <a href="../../test/
index.html#verbose,stex_*">verbose</a>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\tcl\index.html

```
<!doctype html>Ðtitle>CodeMirror: Tcl mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
night.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="tcl.js"></script>Ðscript src="../../addon/scroll/scrollpastend.js"></
script>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Tcl</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Tcl mode</h2>Ðform><textarea
id="code" name="code">Ð
##################################################################################
##  ##     whois.tcl for eggdrop by Ford_Lawnmower irc.geekshed.net #Script-
Help        ##  ##Ð
##################################################################################
## To use this script you must set channel flag +whois (ie .chanset #chan
+whois)           ##Ð
##################################################################################
##      ____                    __
##########################################  ##Ð#     / __/___ _ ___ _ ___/ /
____ ___    ___    ##########################################  ##Ð#    / _/ /
_ `// _ `// _  // __// _ \ / _ \
##########################################  ##Ð#   /___/ \_, / \_, / \_,_//
_/   \___// .__/  ##########################################  ##Ð#        /
___/ /___/                  /_/
##########################################  ##Ð
##
##########################################  ##Ð
##################################################################################
##  ##                              Start
Setup.                                          ##  ##Ð
##################################################################################
namespace eval whois {Ð# change cmdchar to the trigger you want to
use                                        ##  ##Ð variable cmdchar "!"Ð#
change command to the word trigger you would like to
use.                            ##  ##Ð# Keep in mind, This will also change
the .chanset +/-command                         ##  ##Ð variable command
"whois"Ð# change textf to the colors you want for the
text.                                      ##  ##Ð variable textf "\017\00304"Ð
## change tagf to the colors you want for
tags:                                           ##  ##Ð variable tagf "\017\002"Ð
## Change logo to the logo you want at the start of the
line.                           ##  ##Ð variable logo
"\017\00304\002\[\00306W\003hois\00304\]\017"Ð# Change lineout to the results
you want. Valid results are channel users modes topic  ##  ##Ð variable
lineout "channel users modes topic"Ð
##################################################################################
##  ##                              End
Setup.                                                  ## ##Ð
##################################################################################
  variable channel ""Ð setudef flag $whois::commandÐ bind pub -|- [string
trimleft $whois::cmdchar]${whois::command} whois::listÐ bind raw -|- "311"
whois::311Ð bind raw -|- "312" whois::312Ð bind raw -|- "319" whois::319Ð
bind raw -|- "317" whois::317Ð bind raw -|- "313" whois::multiÐ bind raw -|-
"310" whois::multiÐ bind raw -|- "335" whois::multiÐ bind raw -|- "301"
whois::301Ð bind raw -|- "671" whois::multiÐ bind raw -|- "320" whois::multiÐ
bind raw -|- "401" whois::multiÐ bind raw -|- "318" whois::318Ð bind raw -|-
"307" whois::307Ð
```

```
                }Ðproc whois::311 {from key text} {Ð if {[regexp -- {^[^\s]+
\s(.+?)\s(.+?)\s(.+?)\s\*\s\:(.+)$} $text wholematch nick ident host
realname]} {Ð   putserv "PRIVMSG $whois::channel :${whois::logo}
${whois::tagf}Host:${whois::textf} \Ð       $nick \(${ident}@${host}\)
${whois::tagf}Realname:${whois::textf} $realname"Ð }ÐÞproc whois::multi {from
key text} {Ð if {[regexp {\:(.*)$} $text match $key]} {Ð   putserv "PRIVMSG
$whois::channel :${whois::logo} ${whois::tagf}Note:${whois::textf} [subst $
$key]"Ð       return 1Ð }ÐÞproc whois::312 {from key text} {Ð regexp
{([^\s]+)\s\:} $text match serverÐ putserv "PRIVMSG $whois::channel :
${whois::logo} ${whois::tagf}Server:${whois::textf} $server"ÐÞproc whois::319
{from key text} {Ð if {[regexp {.+\:(.+)$} $text match channels]} {Ð
putserv "PRIVMSG $whois::channel :${whois::logo} ${whois::tagf}Channels:
${whois::textf} $channels"Ð }ÐÞproc whois::317 {from key text} {Ð if {[regexp
-- {.*\s(\d+)\s(\d+)\s\:} $text wholematch idle signon]} {Ð   putserv
"PRIVMSG $whois::channel :${whois::logo} ${whois::tagf}Connected:
${whois::textf} \Ð       [ctime $signon] ${whois::tagf}Idle:${whois::textf}
[duration $idle]"Ð }ÐÞproc whois::301 {from key text} {Ð if {[regexp {^.+
\s[^\s]+\s\:(.*)$} $text match awaymsg]} {Ð   putserv "PRIVMSG
$whois::channel :${whois::logo} ${whois::tagf}Away:${whois::textf} $awaymsg"Ð
  }ÐÞproc whois::318 {from key text} {Ð namespace eval whois {Ð       variable
channel ""Ð }Ð variable whois::channel ""ÐÞproc whois::307 {from key text} {Ð
putserv "PRIVMSG $whois::channel :${whois::logo} ${whois::tagf}Services:
${whois::textf} Registered Nick"ÐÞproc whois::list {nick host hand chan text} {Ð
  if {[lsearch -exact [channel info $chan] "+${whois::command}"] != -1} {Ð
namespace eval whois {Ð         variable channel ""Ð       }Ð   variable
whois::channel $chanÐ   putserv "WHOIS $text"Ð }ÐÞputlog "\002*Loaded*
\017\00304\002\[\00306W\003hois\00304\]\017 \002by \Ðord_Lawnmower
irc.GeekShed.net #Script-Help"Ð/textarea></form>Ð   <script>Ð     var editor
= CodeMirror.fromTextArea(document.getElementById("code"), {Ð       theme:
"night",Ð       lineNumbers: true,Ð       indentUnit: 2,Ð
scrollPastEnd: true,Ð       mode: "text/x-tcl"Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/x-tcl</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\textile\index.html

```
<!doctype html>Ðtitle>CodeMirror: Textile mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="textile.js"></script>Ðstyle>.CodeMirror {background:
#f8f8f8;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/marijnh/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class="active" href="#">Textile</a>Ð </ul>Ð/div>Ðarticle>Ð
    <h2>Textile mode</h2>Ð   <form><textarea id="code" name="code">Ð1.
Textile ModeÐA paragraph without formatting.Ð. A simple Paragraph.Ð2. Phrase
ModifiersÐere are some simple phrase modifiers: *strong*, _emphasis_,
**bold**, and __italic__.Ð ??citation??, -deleted text-, +inserted text+,
some ^superscript^, and some ~subscript~.Ð %span element% and @code element@Ð
"link":http://example.com, a "link with (alt text)":urlAliasÐurlAlias]http://
example.com/Ðan image: !http://example.com/image.png! and an image with a
link: !http://example.com/image.png!:http://example.comÐA sentence with a
footnote.[123]Ðfn123. The footnote is defined here.ÐRegistered(r),
Trademark(tm), and Copyright(c)Ð2. HeadersÐ1. Top levelÐ2. Second levelÐ3.
Third levelÐ4. Fourth levelÐ5. Fifth levelÐ6. Lowest levelÐ2.  ListsÐ An
unordered listÐ* foo barÐ** foo barÐ*** foo barÐ* foo barÐ An ordered listÐ#
foo barÐ## foo barÐ### foo barÐ# foo barÐ definition list := descriptionÐ
another item    := foo barÐ spanning ines   :=Ð                    foo barÐ
                    foo bar =:Ð2. AttributesÐayouts and phrase modifiers can
be modified with various kinds of attributes: alignment, CSS ID, CSS class
names, language, padding, and CSS styles.Ð3. AlignmentÐiv<. left alignÐiv>.
right alignÐ3. CSS ID and class namesÐou are a %(my-id#my-classname) rad%
person.Ð3. LanguageÐ[en_CA]. Strange weather, eh?Ð3. Horizontal PaddingÐ
p((())). 2em left padding, 3em right paddingÐ3. CSS stylingÐ{background: red}.
Fire!Ð2. TablesÐ_.              Header 1                |_.      Header
2        |Ð{background:#ddd}. Cell with background|         Normal         |Ð
\2.         Cell spanning 2 columns                           |Ð/2.
Cell spanning 2 rows       |(cell-class). one       |Ð
|                                          two             |Ð
>.                  Right aligned cell |<. Left aligned cell    |Ð3. A table
with attributes:Ðable(#prices).ÐAdults|$5|ÐChildren|$2|Ð2. Code blocksÐc.Ð
function factorial(n) {Ð   if (n === 0) {Ð       return 1;Ð   }Ð   return n *
factorial(n - 1);ÐÐpre..Ð               ,,,,,,Ð           o#'9MMHb':'-,o,Ð
         .oH":HH$' "' ' -*R&o,Ð       dMMM*""'`'      .oM"HM?.Ð
       ,MMM'          "HLbd< ?&H\Ð     .:MH ."\           ` MM  MM&bÐ    .
"*H    -        &MMMMMMMMMH:Ð    .    dboo        MMMMMMMMMMMM.Ð    .
dMMMMMMb      *MMMMMMMMMP.Ð    .    MMMMMMMP        *MMMMMP .Ð
`#MMMMM           MM6P ,Ð      '    `MMMP"           HM*`,Ð
'    :MM             .- ,Ð        '.   `#?..  .       ..'Ð
-.   .         .-Ð             ''-.oo,oo.-''Ð. _(9>Ð\==_)Ð -'=Ð2. Temporarily
disabling textile markupÐotextile. Don't __touch this!__Ðurround text with
double-equals to disable textile inline. Example: Use ==*asterisks*== for
*strong* text.Ð2. HTMLÐome block layouts are simply textile versions of HTML
tags with the same name, like @div@, @pre@, and @p@. HTML tags can also exist
on their own line:Ðsection>Ð <h1>Title</h1>Ð <p>Hello!</p>Ð/section>Ð/
textarea></form>Ð   <script>Ð       var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð           mode: "text/x-textile"Ð       });Ð   </script>Ð
    <p><strong>MIME types defined:</strong> <code>text/x-textile</code>.</p>Ð
    <p><strong>Parsing/Highlighting Tests:</strong> <a href="../../test/
index.html#textile_*">normal</a>,  <a href="../../test/
index.html#verbose,textile_*">verbose</a>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\tiddlywiki\index.html


```
<!doctype html>Ðtitle>CodeMirror: TiddlyWiki mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðlink rel="stylesheet"
href="tiddlywiki.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="../../addon/edit/matchbrackets.js"></script>Ðscript
src="tiddlywiki.js"></script>Ðstyle type="text/css">.CodeMirror {border-top:
1px solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">TiddlyWiki</a>Ð
  </ul>Ð/div>Ðarticle>Ðh2>TiddlyWiki mode</h2>Ðdiv><textarea id="code"
name="code">ÐTiddlyWiki FormattingÐ Rendered versions can be found at: http://
www.tiddlywiki.com/#ReferenceÐ!Option            | !Syntax            |Ðbold
font          | ''bold''           |Ðitalic type        | //italic//         |Ð
|underlined text    | __underlined__      |Ðstrikethrough text | --
strikethrough--  |Ðsuperscript text   | super^^script^^    |Ðsubscript
text     | sub~~script~~      |Ðhighlighted text   | @@highlighted@@    |Ð
preformatted text  | {{{preformatted}}} |ÐBlock ElementsÐ<<ÐHeading 1Ð!
Heading 2Ð!!Heading 3Ð!!!Heading 4Ð!!!!Heading 5Ð<<Ð!ListsÐ<<Ð unordered
list, level 1Ð* unordered list, level 2Ð** unordered list, level 3Ð ordered
list, level 1Ð# ordered list, level 2Ð## unordered list, level 3Ð definition
list, termÐ definition list, descriptionÐ<<Ð!BlockquotesÐ<<Ð blockquote,
level 1Ð> blockquote, level 2Ð>> blockquote, level 3Ð blockquoteÐ<<Ð!
Preformatted TextÐ<<Ð{{{preformatted (e.g. code)}}}Ð<<Ð!Code SectionsÐ<<Ð{{{Ð
Text style codeÐ}}}Ð/{{{ÐS styled code. TiddlyWiki mixed mode should support
highlighter switching in the future.Ð/}}}Ð!--{{{-->ÐML styled code.
TiddlyWiki mixed mode should support highlighter switching in the future.Ð
<!--}}}-->Ð<<Ð!TablesÐ<<ÐCssClass|kÐ!heading column 1|!heading column 2|Ðrow
1, column 1|row 1, column 2|Ðrow 2, column 1|row 2, column 2|Ð>|COLSPAN|Ð
ROWSPAN| ... |Ð~| ... |ÐCssProperty:value;...| ... |Ðcaption|cÐ'Annotation:''Ð
* The {{{>}}} marker creates a "colspan", causing the current cell to merge
with the one to the right.Ð The {{{~}}} marker creates a "rowspan", causing
the current cell to merge with the one above.Ð<<Ð!Images /% TODO %/Ðf.
[[TiddlyWiki.com|http://www.tiddlywiki.com/#EmbeddedImages]]ÐHyperlinksÐ
[[WikiWords|WikiWord]] are automatically transformed to hyperlinks to the
respective tiddlerÐ* the automatic transformation can be suppressed by
preceding the respective WikiWord with a tilde ({{{~}}}): {{{~WikiWord}}}Ð
[[PrettyLinks]] are enclosed in square brackets and contain the desired
tiddler name: {{{[[tiddler name]]}}}Ð* optionally, a custom title or
description can be added, separated by a pipe character ({{{|}}}): {{{[[title|
target]]}}}<br>'''N.B.:''' In this case, the target can also be any website
(i.e. URL).ÐCustom StylingÐ {{{@@CssProperty:value;CssProperty:value;...@@}}}
<br>''N.B.:'' CSS color definitions should use lowercase letters to prevent
the inadvertent creation of WikiWords.Ð <html><code>{{customCssClass{...}}}</
code></html>Ð raw HTML can be inserted by enclosing the respective code in
HTML tags: {{{<html> ... </html>}}}ÐSpecial MarkersÐ {{{<br>}}} forces a
manual line breakÐ {{{----}}} creates a horizontal rulerÐ [[HTML entities|
http://www.tiddlywiki.com/#HtmlEntities]]Ð [[HTML entities local|
HtmlEntities]]Ð {{{<<macroName>>}}} calls the respective [[macro|Macros]]Ð To
hide text within a tiddler so that it is not displayed, it can be wrapped in
{{{/%}}} and {{{%/}}}.<br/>This can be a useful trick for hiding drafts or
annotating complex markup.Ð To prevent wiki markup from taking effect for a
particular section, that section can be enclosed in three double quotes: e.g.
{{{"""WikiWord"""}}}.Ð/textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
'tiddlywiki',      Ð       lineNumbers: true,Ð       matchBrackets: trueÐ
      });Ð
```

</script>Ð TiddlyWiki mode supports a single configuration. Ð MIME types defined: <code>text/x-tiddlywiki</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\tiki\index.html


```
<!doctype html>Ðtitle>CodeMirror: Tiki wiki mode</title>Ðmeta charset="utf-8"/
>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="tiki.css">Ð
<script src="../../lib/codemirror.js"></script>Ðscript src="tiki.js"></script>Ð
<style type="text/css">.CodeMirror {border-top: 1px solid black; border-
bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a href="http://
codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð
  <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a href="../../doc/
manual.html">Manual</a>Ð   <li><a href="https://github.com/codemirror/
codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../index.html">Language
modes</a>Ð   <li><a class=active href="#">Tiki wiki</a>Ð </ul>Ð/div>Ðarticle>Ð
<h2>Tiki wiki mode</h2>Ðdiv><textarea id="code" name="code">ÐHeadingsÐHeader 1Ð
!!Header 2Ð!!Header 3Ð!!!Header 4Ð!!!!Header 5Ð!!!!!Header 6ÐStylingÐ
=titlebar=-Ð^ Box on multiÐlinesÐf content^^Ð__bold__Ð'italic''Ð==underline===Ð
::center::Ð-Line Through--ÐoperatorsÐnp~No parse~/np~ÐlinkÐ[link|desc|nocache]Ð
WikiÐ((Wiki))Ð((Wiki|desc))Ð((Wiki|desc|timeout))ÐtableÐ|row1 col1|row1 col2|row1
col3Ðow2 col1|row2 col2|row2 col3Ðow3 col1|row3 col2|row3 col3||ÐlistsÐblaÐ
**bla-1Ð+continue-bla-1Ð**bla-2Ð+continue-bla-1ÐblaÐcontinue-blaÐblaÐ* tra-la-
laÐcontinue-blaÐblaÐplugin (standard):Ð{PLUGIN(attr="my attr")}ÐplugIn BodyÐ
{PLUGIN}ÐplugIn (inline):Ð{plugin attr="my attr"}Ð/textarea></div>Ðscript
type="text/javascript">Ðf " VF—F÷" Ò
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
'tiki',      Ð       lineNumbers: trueÐ   });Ð/script>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\toml\index.html


```
<!doctype html>Ðtitle>CodeMirror: TOML Mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="toml.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">TOML Mode</a>Ð
</ul>Ð/div>Ðarticle>Ðh2>TOML Mode</h2>Ðform><textarea id="code" name="code">Ð
This is a TOML document. Boom.Ðtitle = "TOML Example"Ð[owner]Ðname = "Tom
Preston-Werner"Ðorganization = "GitHub"Ðbio = "GitHub Cofounder &amp;
CEO\nLikes tater tots and beer."Ðdob = 1979-05-27T07:32:00Z # First class
dates? Why not?Ð[database]Ðserver = "192.168.1.1"Ðports = [ 8001, 8001, 8002 ]Ð
connection_max = 5000Ðenabled = trueÐ[servers]Ð # You can indent as you please.
Tabs or spaces. TOML don't care.Ð [servers.alpha]Ð ip = "10.0.0.1"Ð dc =
"eqdc10"Ð Ð [servers.beta]Ð ip = "10.0.0.2"Ð dc = "eqdc10"Ð [clients]Ðdata =
[ ["gamma", "delta"], [1, 2] ]Ð Line breaks are OK when inside arraysÐhosts = [Ð
  "alpha",Ð "omega"ÐÐ/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode:
{name: "toml"},Ð       lineNumbers: trueÐ     });Ð   </script>Ð   <h3>The
TOML Mode</h3>Ð     <p> Created by Forbes Lindesay.</p>Ð   <p><strong>MIME
type defined:</strong> <code>text/x-toml</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\tornado\index.html

```
<!doctype html>Ðtitle>CodeMirror: Tornado template mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../../addon/mode/overlay.js"></script>Ð
<script src="../xml/xml.js"></script>Ðscript src="../htmlmixed/
htmlmixed.js"></script>Ðscript src="tornado.js"></script>Ðstyle type="text/
css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid
black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/marijnh/codemirror">Code</a>Ð </ul>Ð <ul>Ð
<li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Tornado</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Tornado template mode</h2>Ð
<form><textarea id="code" name="code">Ð!doctype html>Ðhtml>Ð   <head>Ð
<title>My Tornado web application</title>Ð   </head>Ð   <body>Ð       <h1>Ð
            {{ title }}Ð       </h1>Ð       <ul class="my-list">Ð
{% for item in items %}Ð               <li>{% item.name %}</li>Ð           {%
empty %}Ð               <li>You have no items in your list.</li>Ð
{% end %}Ð       </ul>Ð   </body>Ð/html>Ð/textarea></form>Ð   <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
        lineNumbers: true,Ð       mode: "tornado",Ð       indentUnit: 4,Ð
        indentWithTabs: trueÐ     });Ð   </script>Ð   <p>Mode for HTML with
embedded Tornado template markup.</p>Ð   <p><strong>MIME types defined:</
strong> <code>text/x-tornado</code></p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\turtle\index.html


```
<!doctype html>Ðtitle>CodeMirror: Turtle mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="turtle.js"></script>Ðstyle>.CodeMirror {border-top: 1px
solid black; border-bottom: 1px solid black;}</style>Ðdiv id=nav>Ð <a
href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/
logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð   <li><a
href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://github.com/
codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Turtle</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>Turtle mode</h2>Ðform><textarea id="code" name="code">Ð
@prefix foaf: <http://xmlns.com/foaf/0.1/> .Ð@prefix geo: <http://
www.w3.org/2003/01/geo/wgs84_pos#> .Ð@prefix rdf: <http://
www.w3.org/1999/02/22-rdf-syntax-ns#> .Ðhttp://purl.org/net/bsletten> Ð   a
foaf:Person;Ð   foaf:interest <http://www.w3.org/2000/01/sw/>;Ð
foaf:based_near [Ð       geo:lat "34.0736111" ;Ð       geo:lon "-118.3994444"Ð
   ]Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: "text/
turtle",Ð       matchBrackets: trueÐ     });Ð   </script>Ð   <p><strong>MIME
types defined:</strong> <code>text/turtle</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\vb\index.html


```
<!doctype html>Ðtitle>CodeMirror: VB.NET mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink href="http://fonts.googleapis.com/css?
family=Inconsolata" rel="stylesheet" type="text/css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="vb.js"></script>Ðscript type="text/
javascript" src="../../addon/runmode/runmode.js"></script>Ðstyle>Ð
      .CodeMirror {border: 1px solid #aaa; height:210px; height: auto;}Ð
      .CodeMirror-scroll { overflow-x: auto; overflow-y: hidden;}Ð
      .CodeMirror pre { font-family: Inconsolata; font-size: 14px}Ð   </style>Ð
<div id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">VB.NET</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>VB.NET mode</h2>Ðscript type="text/javascript">Ðfunction
test(golden, text) {Ð var ok = true;Ð var i = 0;Ð function callback(token,
style, lineNo, pos){Ð//console.log(String(token) + " " + String(style) + " " +
String(lineNo) + " " + String(pos));Ð   var result = [String(token),
String(style)];Ð   if (golden[i][0] != result[0] || golden[i][1] != result[1])
{Ð     return "Error, expected: " + String(golden[i]) + ", got: " +
String(result);Ð     ok = false;Ð   }Ð   i++;Ð }Ð CodeMirror.runMode(text,
"text/x-vb",callback); Ð if (ok) return "Tests OK";ÐÐfunction testTypes() {Ð
var golden = [['Integer','keyword'],[' ','null'],['Float','keyword']]Ð var
text =  "Integer Float";Ð return test(golden,text);ÐÐfunction testIf(){Ð var
golden = [['If','keyword'],[' ','null'],['True','keyword'],[' ','null'],
['End','keyword'],[' ','null'],['If','keyword']];Ð var text = 'If True End
If';Ð return test(golden, text);ÐÐfunction testDecl(){Ð  var golden =
[['Dim','keyword'],[' ','null'],['x','variable'],[' ','null'],
['as','keyword'],[' ','null'],['Integer','keyword']];Ð  var text = 'Dim x as
Integer';Ð  return test(golden, text);ÐÐfunction testAll(){Ð var result = "";Ð
result += testTypes() + "\n";Ð result += testIf() + "\n";Ð result +=
testDecl() + "\n";Ð return result;ÐÐfunction initText(editor) {Ð var content =
'Class rocket\nPrivate quality as Double\nPublic Sub launch() as String\nif
quality > 0.8\nlaunch = "Successful"\nElse\nlaunch = "Failed"\nEnd If\nEnd
sub\nEnd class\n';Ð editor.setValue(content);Ð for (var i =0; i<
editor.lineCount(); i++) editor.indentLine(i);ÐÐfunction init() {Ð   editor =
CodeMirror.fromTextArea(document.getElementById("solution"), {Ð
lineNumbers: true,Ð       mode: "text/x-vb",Ð       readOnly: falseÐ   });Ð
runTest();ÐÐfunction runTest() {Ð
document.getElementById('testresult').innerHTML = testAll();Ð
initText(editor);ÐÐdocument.body.onload = init;Ð/script>Ð <div id="edit">Ð
<textarea style="width:95%;height:200px;padding:5px;" name="solution"
id="solution" ></textarea>Ð </div>Ð <pre id="testresult"></pre>Ð <p>MIME type
defined: <code>text/x-vb</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\vbscript\index.html

```
<!doctype html>Ðtitle>CodeMirror: VBScript mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="vbscript.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">VBScript</a>Ð
</ul>Ð/div>Ðarticle>Ðh2>VBScript mode</h2>Ðdiv><textarea id="code"
name="code">Ð Pete GuhlÐ 03-04-2012ÐÐ Basic VBScript support for codemirror2Ð
Const ForReading = 1, ForWriting = 2, ForAppending = 8Ðall
Sub020_PostBroadcastToUrbanAirship(strUserName, strPassword, intTransmitID,
strResponse)ÐIf Not IsNull(strResponse) AND Len(strResponse) = 0 ThenÐ
boolTransmitOkYN = FalseÐElseÐr u67&— BäV6†ò $ö, †   ' F '  ö, †   ' D ' •
boolTransmitOkYN = TrueÐEnd IfÐ/textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: true,Ð       indentUnit: 4Ð     });Ð   </script>Ð
<p><strong>MIME types defined:</strong> <code>text/vbscript</code>.</p>Ð </
article>Ð
```

public\assets\js\plugins\codemirror\mode\velocity\index.html

```
<!doctype html>Ðtitle>CodeMirror: Velocity mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/
night.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="velocity.js"></script>Ðstyle>.CodeMirror {border: 1px solid black;}</
style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img
id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Velocity</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Velocity mode</h2>Ð
<form><textarea id="code" name="code">Ð# Velocity Code DemoÐ*Ð  based on PL/
SQL mode by Peter Raganitsch, adapted to Velocity by Steve O'Hara ( http://
www.pivotal-solutions.co.uk )Ð  August 2011Ð#Ð*Ð  This is a multiline comment.Ð
   This is the second lineÐ#Ð[[ hello steveÐ  This has invalid syntax that
would normally need "poor man's escaping" like:Ð  #define()Ð  ${blahÐ]#Ð
#include( "disclaimer.txt" "opinion.txt" )Ðinclude( $foo $bar )Ð
#parse( "lecorbusier.vm" )Ðparse( $foo )Ðevaluate( 'string with VTL
#if(true)will be displayed#end' )Ðdefine( $hello ) Hello $who #end #set( $who
= "World!") $hello ## displays Hello World!Ðforeach( $customer in
$customerList )Ð   $foreach.count $customer.NameÐ   #if( $foo == ${bar})Ð
        it's true!Ð       #breakÐ   #{else}Ð       it's not!Ð       #stopÐ
#endÐ   #if ($foreach.parent.hasNext)Ð       $velocityCountÐ   #endÐendÐ
$someObject.getValues("this is a string splitÐ       across lines")Ð
$someObject("This plus $something in the middle").method(7567).propertyÐ
#macro( tablerows $color $somelist )Ð   #foreach( $something in $somelist )Ð
        <tr><td bgcolor=$color>$something</td></tr>Ð       <tr><td
bgcolor=$color>$bodyContent</td></tr>Ð   #endÐendÐ
#tablerows("red" ["dadsdf","dsa"])Ð@tablerows("red" ["dadsdf","dsa"]) some
body content #endÐ  Variable reference: #set( $monkey = $bill )Ð  String
literal: #set( $monkey.Friend = 'monica' )Ð  Property reference:
#set( $monkey.Blame = $whitehouse.Leak )Ð  Method reference:
#set( $monkey.Plan = $spindoctor.weave($web) )Ð  Number literal:
#set( $monkey.Number = 123 )Ð  Range operator: #set( $monkey.Numbers =
[1..3] )Ð  Object list: #set( $monkey.Say = ["Not", $my, "fault"] )Ð  Object
map: #set( $monkey.Map = {"banana" : "good", "roast beef" : "bad"})Ðthe RHS
can also be a simple arithmetic expression, such as:ÐAddition: #set( $value =
$foo + 1 )Ð  Subtraction: #set( $value = $bar - 1 )Ð  Multiplication:
#set( $value = $foo * $bar )Ð  Division: #set( $value = $foo / $bar )Ð
Remainder: #set( $value = $foo % $bar )Ð/textarea></form>Ð   <script>Ð
var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð
        theme: "night",Ð       lineNumbers: true,Ð       indentUnit: 4,Ð
        mode: "text/velocity"Ð     });Ð   </script>Ð   <p><strong>MIME types
defined:</strong> <code>text/velocity</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\verilog\index.html


```
<!doctype html>Ðtitle>CodeMirror: Verilog/SystemVerilog mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="../../addon/edit/matchbrackets.js"></
script>Ðscript src="verilog.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">Verilog/
SystemVerilog</a>Ð </ul>Ð/div>Ðarticle>Ðh2>SystemVerilog mode</h2>Ð
<div><textarea id="code" name="code">Ð// LiteralsÐ1'b0Ð1'bxÐ1'bzÐ16'hDC78ÐhdeadbeefÐ
'b0011xxzzÐ1234Ð2'd5678Ð3.4e6Ð128.7Ð// Macro definitionÐdefine BUS_WIDTH = 8;Ð// 
Module definitionÐmodule block(Ð input                    clk,Ð
input                    rst_n,Ð input  [`BUS_WIDTH-1:0] data_in,Ð output
[`BUS_WIDTH-1:0] data_outÐ);Ð Ð always @(posedge clk or negedge rst_n) beginÐ
    if (~rst_n) beginÐ     data_out <= 8'b0;Ð   end else beginÐ     data_out
<= data_in;Ð   endÐ   Ð   if (~rst_n)Ð     data_out <= 8'b0;Ð   elseÐ
data_out <= data_in;Ð   Ð   if (~rst_n)Ð     beginÐ       data_out <= 8'b0;Ð
      endÐ   elseÐ     beginÐ       data_out <= data_in;Ð     endÐ endÐ Ð
endmoduleÐ// Class definitionÐclass test;Ð /**Ð  * Sum two integersÐ  */Ð
function int sum(int a, int b);Ð   int result = a + b;Ð   string msg =
$sformatf("%d + %d = %d", a, b, result);Ð   $display(msg);Ð   return result;Ð
endfunctionÐ Ð task delay(int num_cycles);Ð   repeat(num_cycles) #1;Ð endtaskÐ
  ÐendclassÐ/textarea></div>Ðscript>Ð var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð   lineNumbers:
true,Ð   matchBrackets: true,Ð   mode: {Ð     name: "verilog",Ð
noIndentKeywords: ["package"]Ð   }Ð });Ð/script>Ðp>ÐSyntax highlighting and
indentation for the Verilog and SystemVerilog languages (IEEE 1800).Ð
<h2>Configuration options:</h2>Ð <ul>Ð   <li><strong>noIndentKeywords</
strong> - List of keywords which should not cause identation to increase.
E.g. ["package", "module"]. Default: None</li>Ð </ul>Ð/p>Ðp><strong>MIME
types defined:</strong> <code>text/x-verilog</code> and <code>text/x-
systemverilog</code>.</p>Ð/article>Ð
```

public\assets\js\plugins\codemirror\mode\xml\index.html


```
<!doctype html>Ðtitle>CodeMirror: XML mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></
script>Ðscript src="xml.js"></script>Ðstyle type="text/css">.CodeMirror
{border-top: 1px solid black; border-bottom: 1px solid black;}</style>Ðdiv
id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">XML</a>Ð </ul>Ð
</div>Ðarticle>Ðh2>XML mode</h2>Ðform><textarea id="code" name="code">Ð
&lt;html style="color: green"&gt;Ð &lt;!-- this is a comment --&gt;Ð
&lt;head&gt;Ð   &lt;title&gt;HTML Example&lt;/title&gt;Ð &lt;/head&gt;Ð
&lt;body&gt;Ð   The indentation tries to be &lt;em&gt;somewhat &amp;quot;do
whatÐ   I mean&amp;quot;&lt;/em&gt;... but might not match your style.Ð &lt;/
body&gt;Ð&lt;/html&gt;Ð/textarea></form>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð       mode: "text/
html",Ð       lineNumbers: trueÐ     });Ð   </script>Ð   <p>The XML mode
supports two configuration parameters:</p>Ð   <dl>Ð     <dt><code>htmlMode
(boolean)</code></dt>Ð     <dd>This switches the mode to parse HTML instead
of XML. ThisÐ     means attributes do not have to be quoted, and some elementsÐ
      (such as <code>br</code>) do not require a closing tag.</dd>Ð
<dt><code>alignCDATA (boolean)</code></dt>Ð     <dd>Setting this to true will
force the opening tag of CDATAÐ     blocks to not be indented.</dd>Ð   </dl>Ð
    <p><strong>MIME types defined:</strong> <code>application/xml</code>,
<code>text/html</code>.</p>Ð </article>Ð
```

public\assets\js\plugins\codemirror\mode\xquery\index.html


```
<!doctype html>Ðtitle>CodeMirror: XQuery mode</title>Ðmeta charset="utf-8"/>Ð
<link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet"
href="../../lib/codemirror.css">Ðlink rel="stylesheet" href="../../theme/xq-
dark.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript
src="xquery.js"></script>Ðstyle type="text/css">Ðä6öFTÖ—'&÷" ½  &÷&FW"×F÷ ¢
1px solid black; border-bottom: 1px solid black;Ð  †V–v‡C£C   ƒ½Ý   </style>Ð
<div id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo
src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../index.html">Home</a>Ð
    <li><a href="../../doc/manual.html">Manual</a>Ð   <li><a href="https://
github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð   <li><a href="../
index.html">Language modes</a>Ð   <li><a class=active href="#">XQuery</a>Ð </
ul>Ð/div>Ðarticle>Ðh2>XQuery mode</h2>ÐÐÐdiv class="cm-s-default"> ÐÇFW‡F &V
id="code" name="code"> Ðxquery version &quot;1.0-ml&quot;;Ð(: this isÐ: a Ð
"comment" :)Ðlet $let := &lt;x
attr=&quot;value&quot;&gt;&quot;test&quot;&lt;func&gt;function() $var
{function()} {$var}&lt;/func&gt;&lt;/x&gt;Ðlet $joe:=1Ðreturn element element {Ð
attribute attribute { 1 },ÐVÆVÖVçB FW7B ² b33“¶ b33“² ÒÂ– GG&–'WFR föò
{ &quot;bar&quot; },Ðfã¦Fö2,•² fööô & " W  FÆWB ÒÍò÷, Ò    Ð(: a more 'evil'
test :)Ð(: Modified Blakeley example (: with nested comment :) ... :)Ðdeclare
private function local:declare() {()};Ðdeclare private function
local:private() {()};Ðdeclare private function local:function() {()};Ðdeclare
private function local:local() {()};Ðlet $let := &lt;let&gt;let $let :=
&quot;let&quot;&lt;/let&gt;Ðreturn element element {Ð GG&–'WFR  GG&–'WFR ² G''
{ xdmp:version() } catch($e) { xdmp:log($e) } },Ð GG&–'WFR fã¦Fö2
{ &quot;bar&quot; castable as xs:string },ÐVÆVÖVçB FW‡B ² FW‡B
{ &quot;text&quot; } },Ðfã¦Fö2,•² 6†–ÆC£¦W ò„ & " Â  GG&–'WFS£¦ GG&–'WFR’ W
$let ],ÐòöÐfã¦Fö}ÐÐxquery version &quot;1.0-ml&quot;;Ð(: Copyright 2006-2010 Mark
Logic Corporation. :)Ð(:Ð: Licensed under the Apache License, Version 2.0 (the
&quot;License&quot;);Ð: you may not use this file except in compliance with
the License.Ð: You may obtain a copy of the License atÐ:Ð:     http://
www.apache.org/licenses/LICENSE-2.0Ð:Ð: Unless required by applicable law or
agreed to in writing, softwareÐ: distributed under the License is distributed
on an &quot;AS IS&quot; BASIS,Ð: WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied.Ð: See the License for the specific language
governing permissions andÐ: limitations under the License.Ð:)Ðmodule namespace
json = &quot;http://marklogic.com/json&quot;;Ðdeclare default function
namespace &quot;http://www.w3.org/2005/xpath-functions&quot;;Ð(: Need to
backslash escape any double quotes, backslashes, and newlines :)Ðdeclare
function json:escape($s as xs:string) as xs:string {Ð let $s := replace($s,
&quot;\\&quot;, &quot;\\\\&quot;)Ð let $s := replace($s,
&quot;&quot;&quot;&quot;, &quot;\\&quot;&quot;&quot;)Ð let $s := replace($s,
codepoints-to-string((13, 10)), &quot;\\n&quot;)Ð let $s := replace($s,
codepoints-to-string(13), &quot;\\n&quot;)Ð let $s := replace($s, codepoints-
to-string(10), &quot;\\n&quot;)Ð return $sÐ};Ðdeclare function json:atomize($x
as element()) as xs:string {Ð if (count($x/node()) = 0) then 'null'Ð else if
($x/@type = &quot;number&quot;) thenÐ   let $castable := $x castable as
xs:float orÐ                    $x castable as xs:double orÐ
                    $x castable as xs:decimalÐ   returnÐ   if ($castable)
then xs:string($x)Ð   else error(concat(&quot;Not a number: &quot;,
xdmp:describe($x)))Ð else if ($x/@type = &quot;boolean&quot;) thenÐ   let
$castable := $x castable as xs:booleanÐ   returnÐ   if ($castable) then
xs:string(xs:boolean($x))Ð   else error(concat(&quot;Not a boolean: &quot;,
xdmp:describe($x)))Ð else concat('&quot;', json:escape($x), '&quot;')Ð};Ð(:
Print the thing that comes after the colon :)Ðdeclare function json:print-
value($x as element()) as xs:string {Ð if (count($x/*) = 0) thenÐ
json:atomize($x)Ð else if ($x/@quote = &quot;true&quot;) thenÐ
concat('&quot;', json:escape(xdmp:quote($x/node())), '&quot;')Ð elseÐ
string-join(('{',Ð     string-join(for $i in $x/* return json:print-name-
value($i), &quot;,&quot;),Ð
```

'}'), "")Ð};Ð (: Print the name and value both :)Ðdeclare function json:print-name-value($x as element()) as xs:string? {Ð let $name := name($x)Ð let $first-in-array :=Ð count($x/preceding-sibling::*[name(.) = $name]) = 0 andÐ (count($x/following-sibling::*[name(.) = $name]) > 0 or $x/@array = "true")Ð let $later-in-array := count($x/preceding-sibling::*[name(.) = $name]) > 0Ð returnÐ if ($later-in-array) thenÐ () (: I was handled previously :)Ð else if ($first-in-array) thenÐ string-join(('"', json:escape($name), '":[',Ð string-join((for $i in ($x, $x/following-sibling::*[name(.) = $name]) return json:print-value($i)), ","),Ð ']'), "")Ð elseÐ string-join(('"', json:escape($name), '":', json:print-value($x)), "")Ð};Ð (:~Ð Transforms an XML element into a JSON string representation. See http://json.org.Ð <p/>Ð Sample usage:Ð <pre>Ð xquery version "1.0-ml";Ð import module namespace json="http://marklogic.com/json" at "json.xqy";Ð json:serialize(<foo><bar>kid</bar></foo>)Ð </pre>Ð Sample transformations:Ð <pre>Ð <e/> becomes {"e":null}Ð <e>text</e> becomes {"e":"text"}Ð <e>quote " escaping</e> becomes {"e":"quote \" escaping"}Ð <e>backslash \ escaping</e> becomes {"e":"backslash \\ escaping"}Ð <e><a>text1</a><b>text2</b></e> becomes {"e": {"a":"text1","b":"text2"}}Ð <e><a>text1</a><a>text2</a></e> becomes {"e":{"a":["text1","text2"]}}Ð <e><a array="true">text1</a></e> becomes {"e":{"a": ["text1"]}}Ð <e><a type="boolean">false</a></e> becomes {"e":{"a":false}}Ð <e><a type="number">123.5</a></e> becomes {"e":{"a":123.5}}Ð <e quote="true"><div attrib="value"/></e> becomes {"e":"<div attrib=\"value\"/>"}Ð </pre>Ð <p/>Ð Namespace URIs are ignored. Namespace prefixes are included in the JSON name.Ð <p/>Ð Attributes are ignored, except for the special attribute @array="true" thatÐ indicates the JSON serialization should write the node, even if single, as anÐ array, and the attribute @type that can be set to "boolean" or "number" toÐ dictate the value should be written as that type (unquoted). There's alsoÐ an @quote attribute that when set to true writes the inner content as textÐ rather than as structured JSON, useful for sending some XHTML over theÐ wire.Ð <p/>Ð Text nodes within mixed content are ignored.Ð @param $x Element node to convertÐ @return String holding JSON serialized representation of $xÐ @author Jason HunterÐ @version 1.0.1Ð Ð Ported to xquery 1.0-ml; double escaped backslashes in json:escapeÐ)Ðdeclare function json:serialize($x as element()) as xs:string {Ð string-join(('{', json:print-name-value($x), '}'), "")Ð};Ð </textarea> Ð ÐÐ <script> Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {Ð lineNumbers: true,Ð matchBrackets: true,Ð theme: "xq-dark"Ð });Ð </script> ÐÐ MIME types defined: <code>application/xquery</code>. ÐÐ Development of the CodeMirror XQuery mode was sponsored by Ð <a href="http://marklogic.com">MarkLogic</a> and developed by Ð

```
                                <a href="https://twitter.com/mbrevoort">Mike
Brevoort</a>.Đ   </p>ĐĐ </article>Đ
```

public\assets\js\plugins\codemirror\mode\yaml\index.html

<!doctype html>Ðtitle>CodeMirror: YAML mode</title>Ðmeta charset="utf-8"/>Ð <link rel=stylesheet href="../../doc/docs.css">Ðlink rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/codemirror.js"></script>Ðscript src="yaml.js"></script>Ðstyle>.CodeMirror { border-top: 1px solid #ddd; border-bottom: 1px solid #ddd; }</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð <li><a href="../../index.html">Home</a>Ð <li><a href="../../doc/manual.html">Manual</a>Ð <li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð <li><a href="../index.html">Language modes</a>Ð <li><a class=active href="#">YAML</a>Ð </ul>Ð Ðarticle>Ðh2>YAML mode</h2>Ðform><textarea id="code" name="code">Ð-- # Favorite moviesÐ CasablancaÐ North by NorthwestÐ The Man Who Wasn't ThereÐ-- # Shopping listÐmilk, pumpkin pie, eggs, juice]Ð-- # Indented Blocks, common in YAML data files, use indentation and new lines to separate the key: value pairsÐ name: John SmithÐ age: 33Ð-- # Inline Blocks, common in YAML data streams, use commas to separate the key: value pairs between bracesÐ{name: John Smith, age: 33}Ð--Ðreceipt: Oz-Ware Purchase InvoiceÐdate: 2007-08-06Ðcustomer:Ð given: DorothyÐ family: GaleÐitems:Ð - part_no: A4786Ð descrip: Water Bucket (Filled)Ð price: 1.47Ð quantity: 4Ð - part_no: E1628Ð descrip: High Heeled "Ruby" SlippersÐ size: 8Ð price: 100.27Ð quantity: 1Ðbill-to: &id001Ð street: |Ð 123 Tornado AlleyÐ Suite 16Ð city: East CentervilleÐ state: KSÐship-to: *id001ÐspecialDelivery: >Ð Follow the Yellow BrickÐ Road to the Emerald City.Ð Pay no attention to theÐ man behind the curtain.Ð..Ð/textarea></form>Ð <script>Ð var editor = CodeMirror.fromTextArea(document.getElementById("code"), {});Ð </script>Ð MIME types defined: <code>text/x-yaml</code>. Ð </article>Ð

public\assets\js\plugins\codemirror\mode\z80\index.html

```
<!doctype html>Ðtitle>CodeMirror: Z80 assembly mode</title>Ðmeta
charset="utf-8"/>Ðlink rel=stylesheet href="../../doc/docs.css">Ðlink
rel="stylesheet" href="../../lib/codemirror.css">Ðscript src="../../lib/
codemirror.js"></script>Ðscript src="z80.js"></script>Ðstyle type="text/
css">.CodeMirror {border-top: 1px solid black; border-bottom: 1px solid
black;}</style>Ðdiv id=nav>Ð <a href="http://codemirror.net"><h1>CodeMirror</
h1><img id=logo src="../../doc/logo.png"></a>Ð <ul>Ð   <li><a href="../../
index.html">Home</a>Ð   <li><a href="../../doc/manual.html">Manual</a>Ð
<li><a href="https://github.com/codemirror/codemirror">Code</a>Ð </ul>Ð <ul>Ð
    <li><a href="../index.html">Language modes</a>Ð   <li><a class=active
href="#">Z80 assembly</a>Ð </ul>Ð/div>Ðarticle>Ðh2>Z80 assembly mode</h2>Ð
<div><textarea id="code" name="code">Ðinclude    "ti83plus.inc"Ðdefine
progStart   $9D95Ðorg        progStart-2Ðdb         $BB,$6DÐ
bcall(_ClrLCDFull)Ð   ld  HL, 0Ð   ld  (PenCol),   HLÐ   ld  HL, MessageÐ
bcall(_PutS) ; Displays the stringÐ   bcall(_NewLine)Ð   retÐMessage:Ð
.db         "Hello world!",0Ð/textarea></div>Ð   <script>Ð     var editor =
CodeMirror.fromTextArea(document.getElementById("code"), {Ð
lineNumbers: trueÐ     });Ð   </script>Ð   <p><strong>MIME type defined:</
strong> <code>text/x-z80</code>.</p>Ð </article>Ð
```

public\assets\css\animate.css

@charset "UTF-8";Ð/*!Ð animate.css - http://daneden.me/animateÐ Licensed under the MIT licenseÐ Copyright (c) 2013 Daniel EdenÐ Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:Ð The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.Ð THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.Ð */Ð .animated {Ð -webkit-animation-duration: 1s;Ð animation-duration: 1s;Ð -webkit-animation-fill-mode: both;Ð animation-fill-mode: both;Ð z-index: 100;ÐÐ .animated.infinite {Ð -webkit-animation-iteration-count: infinite;Ð animation-iteration-count: infinite;ÐÐ .animated.hinge {Ð -webkit-animation-duration: 2s;Ð animation-duration: 2s;ÐÐ @-webkit-keyframes bounce {Ð 0%, 20%, 50%, 80%, 100% {Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 40% {Ð -webkit-transform: translateY(-30px);Ð transform: translateY(-30px);Ð }Ð 60% {Ð -webkit-transform: translateY(-15px);Ð transform: translateY(-15px);Ð }ÐÐ @keyframes bounce {Ð 0%, 20%, 50%, 80%, 100% {Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 40% {Ð -webkit-transform: translateY(-30px);Ð -ms-transform: translateY(-30px);Ð transform: translateY(-30px);Ð }Ð 60% {Ð -webkit-transform: translateY(-15px);Ð -ms-transform: translateY(-15px);Ð transform: translateY(-15px);Ð }ÐÐ .bounce {Ð -webkit-animation-name: bounce;Ð animation-name: bounce;ÐÐ @-webkit-keyframes flash {Ð 0%, 50%, 100% {Ð opacity: 1;Ð }Ð 25%, 75% {Ð opacity: 0;Ð }ÐÐ @keyframes flash {Ð 0%, 50%, 100% {Ð opacity: 1;Ð }Ð 25%, 75% {Ð opacity: 0;Ð }ÐÐ .flash {Ð -webkit-animation-name: flash;Ð animation-name: flash;ÐÐ /* originally authored by Nick Pettit - https://github.com/nickpettit/glide */Ð @-webkit-keyframes pulse {Ð 0% {Ð -webkit-transform: scale(1);Ð transform: scale(1);Ð }Ð 50% {Ð -webkit-transform: scale(1.1);Ð transform: scale(1.1);Ð }Ð 100% {Ð -webkit-transform: scale(1);Ð transform: scale(1);Ð }ÐÐ @keyframes pulse {Ð 0% {Ð -webkit-transform: scale(1);Ð -ms-transform: scale(1);Ð transform: scale(1);Ð }Ð 50% {Ð -webkit-transform: scale(1.1);Ð -ms-transform: scale(1.1);Ð transform: scale(1.1);Ð }Ð 100% {Ð -webkit-transform: scale(1);Ð -ms-transform: scale(1);Ð transform: scale(1);Ð }ÐÐ .pulse {Ð -webkit-animation-name: pulse;Ð animation-name: pulse;ÐÐ @-webkit-keyframes rubberBand {Ð 0% {Ð -webkit-transform: scale(1);Ð transform: scale(1);Ð }Ð 30% {Ð -webkit-transform: scaleX(1.25) scaleY(0.75);Ð transform: scaleX(1.25) scaleY(0.75);Ð }Ð 40% {Ð -webkit-transform: scaleX(0.75) scaleY(1.25);Ð transform: scaleX(0.75) scaleY(1.25);Ð }Ð 60% {Ð -webkit-transform: scaleX(1.15) scaleY(0.85);Ð transform: scaleX(1.15) scaleY(0.85);Ð }Ð 100% {Ð -webkit-transform: scale(1);Ð transform: scale(1);Ð }ÐÐ @keyframes rubberBand {Ð 0% {Ð -webkit-transform: scale(1);Ð -ms-transform: scale(1);Ð transform: scale(1);Ð }Ð 30% {Ð -webkit-transform: scaleX(1.25) scaleY(0.75);Ð -ms-transform: scaleX(1.25) scaleY(0.75);Ð transform: scaleX(1.25) scaleY(0.75);Ð }Ð 40% {Ð -webkit-transform: scaleX(0.75) scaleY(1.25);Ð -ms-transform: scaleX(0.75) scaleY(1.25);Ð

transform: scaleX(0.75) scaleY(1.25);Ð }Ð 60% {Ð -webkit-transform: scaleX(1.15) scaleY(0.85);Ð -ms-transform: scaleX(1.15) scaleY(0.85);Ð transform: scaleX(1.15) scaleY(0.85);Ð }Ð 100% {Ð -webkit-transform: scale(1);Ð -ms-transform: scale(1);Ð transform: scale(1);Ð }ÐÐrubberBand {Ð -webkit-animation-name: rubberBand;Ð animation-name: rubberBand;ÐÐ@-webkit-keyframes shake {Ð 0%, 100% {Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 10%, 30%, 50%, 70%, 90% {Ð -webkit-transform: translateX(-10px);Ð transform: translateX(-10px);Ð }Ð 20%, 40%, 60%, 80% {Ð -webkit-transform: translateX(10px);Ð transform: translateX(10px);Ð }ÐÐ @keyframes shake {Ð 0%, 100% {Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 10%, 30%, 50%, 70%, 90% {Ð -webkit-transform: translateX(-10px);Ð -ms-transform: translateX(-10px);Ð transform: translateX(-10px);Ð }Ð 20%, 40%, 60%, 80% {Ð -webkit-transform: translateX(10px);Ð -ms-transform: translateX(10px);Ð transform: translateX(10px);Ð }ÐÐshake {Ð -webkit-animation-name: shake;Ð animation-name: shake;ÐÐ@-webkit-keyframes swing {Ð 20% {Ð -webkit-transform: rotate(15deg);Ð transform: rotate(15deg);Ð }Ð 40% {Ð -webkit-transform: rotate(-10deg);Ð transform: rotate(-10deg);Ð }Ð 60% {Ð -webkit-transform: rotate(5deg);Ð transform: rotate(5deg);Ð }Ð 80% {Ð -webkit-transform: rotate(-5deg);Ð transform: rotate(-5deg);Ð }Ð 100% {Ð -webkit-transform: rotate(0deg);Ð transform: rotate(0deg);Ð }ÐÐ@keyframes swing {Ð 20% {Ð -webkit-transform: rotate(15deg);Ð -ms-transform: rotate(15deg);Ð transform: rotate(15deg);Ð }Ð 40% {Ð -webkit-transform: rotate(-10deg);Ð -ms-transform: rotate(-10deg);Ð transform: rotate(-10deg);Ð }Ð 60% {Ð -webkit-transform: rotate(5deg);Ð -ms-transform: rotate(5deg);Ð transform: rotate(5deg);Ð }Ð 80% {Ð -webkit-transform: rotate(-5deg);Ð -ms-transform: rotate(-5deg);Ð transform: rotate(-5deg);Ð }Ð 100% {Ð -webkit-transform: rotate(0deg);Ð -ms-transform: rotate(0deg);Ð transform: rotate(0deg);Ð }ÐÐswing {Ð -webkit-transform-origin: top center;Ð -ms-transform-origin: top center;Ð transform-origin: top center;Ð -webkit-animation-name: swing;Ð animation-name: swing;ÐÐ@-webkit-keyframes tada {Ð 0% {Ð -webkit-transform: scale(1);Ð transform: scale(1);Ð }Ð 10%, 20% {Ð -webkit-transform: scale(0.9) rotate(-3deg);Ð transform: scale(0.9) rotate(-3deg);Ð }Ð 30%, 50%, 70%, 90% {Ð -webkit-transform: scale(1.1) rotate(3deg);Ð transform: scale(1.1) rotate(3deg);Ð }Ð 40%, 60%, 80% {Ð -webkit-transform: scale(1.1) rotate(-3deg);Ð transform: scale(1.1) rotate(-3deg);Ð }Ð 100% {Ð -webkit-transform: scale(1) rotate(0);Ð transform: scale(1) rotate(0);Ð }ÐÐ@keyframes tada {Ð 0% {Ð -webkit-transform: scale(1);Ð -ms-transform: scale(1);Ð transform: scale(1);Ð }Ð 10%, 20% {Ð -webkit-transform: scale(0.9) rotate(-3deg);Ð -ms-transform: scale(0.9) rotate(-3deg);Ð transform: scale(0.9) rotate(-3deg);Ð }Ð 30%, 50%, 70%, 90% {Ð -webkit-transform: scale(1.1) rotate(3deg);Ð -ms-transform: scale(1.1) rotate(3deg);Ð transform: scale(1.1) rotate(3deg);Ð }Ð 40%, 60%, 80% {Ð -webkit-transform: scale(1.1) rotate(-3deg);Ð -ms-transform: scale(1.1) rotate(-3deg);Ð transform: scale(1.1) rotate(-3deg);Ð }Ð 100% {Ð -webkit-transform: scale(1) rotate(0);Ð -ms-transform: scale(1) rotate(0);Ð transform: scale(1) rotate(0);Ð }ÐÐtada {Ð -webkit-animation-name: tada;Ð animation-name: tada;ÐÐ/* originally authored by Nick Pettit - https://github.com/nickpettit/glide */ÐÐ@-webkit-keyframes wobble {Ð 0% {Ð -webkit-transform: translateX(0%);Ð transform: translateX(0%);Ð }Ð 15% {Ð -webkit-transform: translateX(-25%) rotate(-5deg);Ð transform: translateX(-25%) rotate(-5deg);Ð }Ð 30% {Ð -webkit-transform: translateX(20%) rotate(3deg);Ð

transform: translateX(20%) rotate(3deg);Ð
}Ð 45% {Ð -webkit-transform: translateX(-15%) rotate(-3deg);Ð
transform: translateX(-15%) rotate(-3deg);Ð }Ð 60% {Ð -
webkit-transform: translateX(10%) rotate(2deg);Ð transform:
translateX(10%) rotate(2deg);Ð }Ð 75% {Ð -webkit-transform:
translateX(-5%) rotate(-1deg);Ð transform: translateX(-5%)
rotate(-1deg);Ð }Ð 100% {Ð -webkit-transform: translateX(0%);Ð
transform: translateX(0%);Ð }ÐÐ@keyframes wobble {Ð 0% {Ð -
webkit-transform: translateX(0%);Ð -ms-transform: translateX(0%);Ð
transform: translateX(0%);Ð }Ð 15% {Ð -webkit-transform:
translateX(-25%) rotate(-5deg);Ð -ms-transform: translateX(-25%)
rotate(-5deg);Ð transform: translateX(-25%) rotate(-5deg);Ð }Ð 30% {Ð
-webkit-transform: translateX(20%) rotate(3deg);Ð -ms-
transform: translateX(20%) rotate(3deg);Ð transform: translateX(20%)
rotate(3deg);Ð }Ð 45% {Ð -webkit-transform: translateX(-15%)
rotate(-3deg);Ð -ms-transform: translateX(-15%) rotate(-3deg);Ð
transform: translateX(-15%) rotate(-3deg);Ð }Ð 60% {Ð -webkit-
transform: translateX(10%) rotate(2deg);Ð -ms-transform:
translateX(10%) rotate(2deg);Ð transform: translateX(10%) rotate(2deg);Ð
}Ð 75% {Ð -webkit-transform: translateX(-5%) rotate(-1deg);Ð
-ms-transform: translateX(-5%) rotate(-1deg);Ð transform:
translateX(-5%) rotate(-1deg);Ð }Ð 100% {Ð -webkit-transform:
translateX(0%);Ð -ms-transform: translateX(0%);Ð transform:
translateX(0%);Ð }ÐÐwobble {Ð -webkit-animation-name: wobble;Ð
animation-name: wobble;ÐÐ@-webkit-keyframes bounceIn {Ð 0% {Ð opacity:
0;Ð -webkit-transform: scale(.3);Ð transform: scale(.3);Ð }Ð
50% {Ð opacity: 1;Ð -webkit-transform: scale(1.05);Ð
transform: scale(1.05);Ð }Ð 70% {Ð -webkit-transform: scale(.9);Ð
transform: scale(.9);Ð }Ð 100% {Ð opacity: 1;Ð -
webkit-transform: scale(1);Ð transform: scale(1);Ð }ÐÐ@keyframes
bounceIn {Ð 0% {Ð opacity: 0;Ð -webkit-transform: scale(.3);Ð
-ms-transform: scale(.3);Ð transform: scale(.3);Ð }Ð 50% {Ð
opacity: 1;Ð -webkit-transform: scale(1.05);Ð -ms-
transform: scale(1.05);Ð transform: scale(1.05);Ð }Ð 70% {Ð -
webkit-transform: scale(.9);Ð -ms-transform: scale(.9);Ð
transform: scale(.9);Ð }Ð 100% {Ð opacity: 1;Ð -webkit-
transform: scale(1);Ð -ms-transform: scale(1);Ð transform:
scale(1);Ð }ÐÐbounceIn {Ð -webkit-animation-name: bounceIn;Ð animation-
name: bounceIn;ÐÐ@-webkit-keyframes bounceInDown {Ð 0% {Ð opacity: 0;Ð
-webkit-transform: translateY(-2000px);Ð transform:
translateY(-2000px);Ð }Ð 60% {Ð opacity: 1;Ð -webkit-
transform: translateY(30px);Ð transform: translateY(30px);Ð }Ð 80% {Ð
-webkit-transform: translateY(-10px);Ð transform:
translateY(-10px);Ð }Ð 100% {Ð -webkit-transform: translateY(0);Ð
transform: translateY(0);Ð }ÐÐ@keyframes bounceInDown {Ð 0% {Ð
opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð -ms-
transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð }Ð
60% {Ð opacity: 1;Ð -webkit-transform: translateY(30px);Ð
-ms-transform: translateY(30px);Ð transform: translateY(30px);Ð
}Ð 80% {Ð -webkit-transform: translateY(-10px);Ð -ms-
transform: translateY(-10px);Ð transform: translateY(-10px);Ð }Ð
100% {Ð -webkit-transform: translateY(0);Ð -ms-transform:
translateY(0);Ð transform: translateY(0);Ð }ÐÐbounceInDown {Ð -
webkit-animation-name: bounceInDown;Ð animation-name: bounceInDown;ÐÐ@-
webkit-keyframes bounceInLeft {Ð 0% {Ð opacity: 0;Ð -webkit-
transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð
60% {Ð opacity: 1;Ð -webkit-transform: translateX(30px);Ð
transform: translateX(30px);Ð }Ð 80% {Ð -webkit-transform:
translateX(-10px);Ð transform: translateX(-10px);Ð }Ð 100% {Ð
-webkit-transform: translateX(0);Ð

transform: translateX(0);Ð   }ÐÐ
@keyframes bounceInLeft {Ð   0% {Ð   opacity: 0;Ð   -webkit-
transform: translateX(-2000px);Ð   -ms-transform: translateX(-2000px);Ð
        transform: translateX(-2000px);Ð   }Ð   60% {Ð   opacity: 1;Ð
        -webkit-transform: translateX(30px);Ð   -ms-transform:
translateX(30px);Ð   transform: translateX(30px);Ð   }Ð   80% {Ð   -
webkit-transform: translateX(-10px);Ð   -ms-transform: translateX(-10px);Ð
        transform: translateX(-10px);Ð   }Ð   100% {Ð   -webkit-
transform: translateX(0);Ð   -ms-transform: translateX(0);Ð
transform: translateX(0);Ð   }ÐÐbounceInLeft {Ð   -webkit-animation-name:
bounceInLeft;Ð   animation-name: bounceInLeft;ÐÐ@-webkit-keyframes
bounceInRight {Ð   0% {Ð   opacity: 0;Ð   -webkit-transform:
translateX(2000px);Ð   transform: translateX(2000px);Ð   }Ð   60% {Ð
        opacity: 1;Ð   -webkit-transform: translateX(-30px);Ð
transform: translateX(-30px);Ð   }Ð   80% {Ð   -webkit-transform:
translateX(10px);Ð   transform: translateX(10px);Ð   }Ð   100% {Ð   -
webkit-transform: translateX(0);Ð   transform: translateX(0);Ð   }ÐÐ
@keyframes bounceInRight {Ð   0% {Ð   opacity: 0;Ð   -webkit-
transform: translateX(2000px);Ð   -ms-transform: translateX(2000px);Ð
        transform: translateX(2000px);Ð   }Ð   60% {Ð   opacity: 1;Ð
        -webkit-transform: translateX(-30px);Ð   -ms-transform:
translateX(-30px);Ð   transform: translateX(-30px);Ð   }Ð   80% {Ð   -
webkit-transform: translateX(10px);Ð   -ms-transform: translateX(10px);Ð
        transform: translateX(10px);Ð   }Ð   100% {Ð   -webkit-transform:
translateX(0);Ð   -ms-transform: translateX(0);Ð   transform:
translateX(0);Ð   }ÐÐbounceInRight {Ð   -webkit-animation-name: bounceInRight;Ð
    animation-name: bounceInRight;ÐÐ@-webkit-keyframes bounceInUp {Ð   0% {Ð
        opacity: 0;Ð   -webkit-transform: translateY(2000px);Ð
transform: translateY(2000px);Ð   }Ð   60% {Ð   opacity: 1;Ð   -
webkit-transform: translateY(-30px);Ð   transform: translateY(-30px);Ð   }Ð
    80% {Ð   -webkit-transform: translateY(10px);Ð   transform:
translateY(10px);Ð   }Ð   100% {Ð   -webkit-transform: translateY(0);Ð
        transform: translateY(0);Ð   }ÐÐ@keyframes bounceInUp {Ð   0% {Ð
opacity: 0;Ð   -webkit-transform: translateY(2000px);Ð   -ms-
transform: translateY(2000px);Ð   transform: translateY(2000px);Ð   }Ð
60% {Ð   opacity: 1;Ð   -webkit-transform: translateY(-30px);Ð   -
ms-transform: translateY(-30px);Ð   transform: translateY(-30px);Ð   }Ð
80% {Ð   -webkit-transform: translateY(10px);Ð   -ms-transform:
translateY(10px);Ð   transform: translateY(10px);Ð   }Ð   100% {Ð   -
webkit-transform: translateY(0);Ð   -ms-transform: translateY(0);Ð
transform: translateY(0);Ð   }ÐÐbounceInUp {Ð   -webkit-animation-name:
bounceInUp;Ð   animation-name: bounceInUp;ÐÐ@-webkit-keyframes bounceOut {Ð
0% {Ð   -webkit-transform: scale(1);Ð   transform: scale(1);Ð   }Ð
25% {Ð   -webkit-transform: scale(.95);Ð   transform: scale(.95);Ð   }Ð
    50% {Ð   opacity: 1;Ð   -webkit-transform: scale(1.1);Ð
transform: scale(1.1);Ð   }Ð   100% {Ð   opacity: 0;Ð   -webkit-
transform: scale(.3);Ð   transform: scale(.3);Ð   }ÐÐ@keyframes bounceOut {Ð
    0% {Ð   -webkit-transform: scale(1);Ð   -ms-transform: scale(1);Ð
        transform: scale(1);Ð   }Ð   25% {Ð   -webkit-transform:
scale(.95);Ð   -ms-transform: scale(.95);Ð   transform: scale(.95);Ð
    }Ð   50% {Ð   opacity: 1;Ð   -webkit-transform: scale(1.1);Ð
        -ms-transform: scale(1.1);Ð   transform: scale(1.1);Ð   }Ð   100%
{Ð   opacity: 0;Ð   -webkit-transform: scale(.3);Ð   -ms-
transform: scale(.3);Ð   transform: scale(.3);Ð   }ÐÐbounceOut {Ð   -
webkit-animation-name: bounceOut;Ð   animation-name: bounceOut;ÐÐ@-webkit-
keyframes bounceOutDown {Ð   0% {Ð   -webkit-transform: translateY(0);Ð
        transform: translateY(0);Ð   }Ð   20% {Ð   opacity: 1;Ð   -
webkit-transform: translateY(-20px);Ð   transform: translateY(-20px);Ð   }Ð
    100% {Ð   opacity: 0;Ð   -webkit-transform: translateY(2000px);Ð
        transform: translateY(2000px);Ð

}ÐÐ@keyframes bounceOutDown {Ð 0% {Ð
-webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð
transform: translateY(0);Ð }Ð 20% {Ð opacity: 1;Ð -
webkit-transform: translateY(-20px);Ð -ms-transform: translateY(-20px);Ð
transform: translateY(-20px);Ð }Ð 100% {Ð opacity: 0;Ð
-webkit-transform: translateY(2000px);Ð -ms-transform:
translateY(2000px);Ð transform: translateY(2000px);Ð }ÐÐbounceOutDown
{Ð -webkit-animation-name: bounceOutDown;Ð animation-name: bounceOutDown;ÐÐ
@-webkit-keyframes bounceOutLeft {Ð 0% {Ð -webkit-transform:
translateX(0);Ð transform: translateX(0);Ð }Ð 20% {Ð opacity:
1;Ð -webkit-transform: translateX(20px);Ð transform:
translateX(20px);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform:
translateX(-2000px);Ð transform: translateX(-2000px);Ð }ÐÐ@keyframes
bounceOutLeft {Ð 0% {Ð -webkit-transform: translateX(0);Ð -ms-
transform: translateX(0);Ð transform: translateX(0);Ð }Ð 20% {Ð
opacity: 1;Ð -webkit-transform: translateX(20px);Ð -ms-
transform: translateX(20px);Ð transform: translateX(20px);Ð }Ð 100%
{Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð -
ms-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð
}ÐbounceOutLeft {Ð -webkit-animation-name: bounceOutLeft;Ð animation-
name: bounceOutLeft;ÐÐ@-webkit-keyframes bounceOutRight {Ð 0% {Ð -
webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 20%
{Ð opacity: 1;Ð -webkit-transform: translateX(-20px);Ð
transform: translateX(-20px);Ð }Ð 100% {Ð opacity: 0;Ð -
webkit-transform: translateX(2000px);Ð transform: translateX(2000px);Ð
}ÐÐ@keyframes bounceOutRight {Ð 0% {Ð -webkit-transform:
translateX(0);Ð -ms-transform: translateX(0);Ð transform:
translateX(0);Ð }Ð 20% {Ð opacity: 1;Ð -webkit-transform:
translateX(-20px);Ð -ms-transform: translateX(-20px);Ð transform:
translateX(-20px);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-
transform: translateX(2000px);Ð -ms-transform: translateX(2000px);Ð
transform: translateX(2000px);Ð }ÐÐbounceOutRight {Ð -webkit-
animation-name: bounceOutRight;Ð animation-name: bounceOutRight;ÐÐ@-webkit-
keyframes bounceOutUp {Ð 0% {Ð -webkit-transform: translateY(0);Ð
transform: translateY(0);Ð }Ð 20% {Ð opacity: 1;Ð -
webkit-transform: translateY(20px);Ð transform: translateY(20px);Ð }Ð
100% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð
transform: translateY(-2000px);Ð }ÐÐ@keyframes bounceOutUp {Ð 0% {Ð
-webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð
transform: translateY(0);Ð }Ð 20% {Ð opacity: 1;Ð -
webkit-transform: translateY(20px);Ð -ms-transform: translateY(20px);Ð
transform: translateY(20px);Ð }Ð 100% {Ð opacity: 0;Ð
-webkit-transform: translateY(-2000px);Ð -ms-transform:
translateY(-2000px);Ð transform: translateY(-2000px);Ð }ÐÐbounceOutUp
{Ð -webkit-animation-name: bounceOutUp;Ð animation-name: bounceOutUp;ÐÐ@-
webkit-keyframes fadeIn {Ð 0% {Ð opacity: 0;Ð }Ð 100% {Ð
opacity: 1;Ð }ÐÐ@keyframes fadeIn {Ð 0% {Ð opacity: 0;Ð }Ð 100% {Ð
opacity: 1;Ð }ÐÐfadeIn {Ð -webkit-animation-name: fadeIn;Ð
animation-name: fadeIn;ÐÐ@-webkit-keyframes fadeInDown {Ð 0% {Ð
opacity: 0;Ð -webkit-transform: translateY(-20px);Ð transform:
translateY(-20px);Ð }Ð 100% {Ð opacity: 1;Ð -webkit-
transform: translateY(0);Ð transform: translateY(0);Ð }ÐÐ@keyframes
fadeInDown {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateY(-20px);Ð -ms-transform: translateY(-20px);Ð transform:
translateY(-20px);Ð }Ð 100% {Ð opacity: 1;Ð -webkit-
transform: translateY(0);Ð -ms-transform: translateY(0);Ð
transform: translateY(0);Ð }ÐÐfadeInDown {Ð -webkit-animation-name:
fadeInDown;Ð animation-name: fadeInDown;ÐÐ@-webkit-keyframes fadeInDownBig {Ð
0% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð
transform: translateY(-2000px);Ð

}Ð 100% {Ð opacity: 1;Ð
-webkit-transform: translateY(0);Ð transform: translateY(0);Ð
}ÐÐ@keyframes fadeInDownBig {Ð 0% {Ð opacity: 0;Ð -webkit-
transform: translateY(-2000px);Ð -ms-transform: translateY(-2000px);Ð
transform: translateY(-2000px);Ð }Ð 100% {Ð opacity: 1;Ð
-webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð
transform: translateY(0);Ð }ÐÐfadeInDownBig {Ð -webkit-animation-
name: fadeInDownBig;Ð animation-name: fadeInDownBig;ÐÐ@-webkit-keyframes
fadeInLeft {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateX(-20px);Ð transform: translateX(-20px);Ð }Ð 100% {Ð
opacity: 1;Ð -webkit-transform: translateX(0);Ð transform:
translateX(0);Ð }ÐÐ@keyframes fadeInLeft {Ð 0% {Ð opacity: 0;Ð
-webkit-transform: translateX(-20px);Ð -ms-transform: translateX(-20px);Ð
transform: translateX(-20px);Ð }Ð 100% {Ð opacity: 1;Ð
-webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð
transform: translateX(0);Ð }ÐÐfadeInLeft {Ð -webkit-animation-
name: fadeInLeft;Ð animation-name: fadeInLeft;ÐÐ@-webkit-keyframes
fadeInLeftBig {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð 100% {Ð
opacity: 1;Ð -webkit-transform: translateX(0);Ð
transform: translateX(0);Ð }ÐÐ@keyframes fadeInLeftBig {Ð 0% {Ð
opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð -ms-
transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð
100% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð
-ms-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐ
.fadeInLeftBig {Ð -webkit-animation-name: fadeInLeftBig;Ð animation-name:
fadeInLeftBig;ÐÐ@-webkit-keyframes fadeInRight {Ð 0% {Ð opacity: 0;Ð
-webkit-transform: translateX(20px);Ð transform:
translateX(20px);Ð }Ð 100% {Ð opacity: 1;Ð -webkit-transform:
translateX(0);Ð transform: translateX(0);Ð }ÐÐ@keyframes fadeInRight {Ð
0% {Ð opacity: 0;Ð -webkit-transform: translateX(40px);Ð
-ms-transform: translateX(40px);Ð transform: translateX(40px);Ð
}Ð 100% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð
-ms-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐ
.fadeInRight {Ð -webkit-animation-name: fadeInRight;Ð animation-name:
fadeInRight;ÐÐ@-webkit-keyframes fadeInRightBig {Ð 0% {Ð opacity: 0;Ð
-webkit-transform: translateX(2000px);Ð transform:
translateX(2000px);Ð }Ð 100% {Ð opacity: 1;Ð -webkit-
transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐ@keyframes
fadeInRightBig {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateX(2000px);Ð -ms-transform: translateX(2000px);Ð
transform: translateX(2000px);Ð }Ð 100% {Ð opacity: 1;Ð -
webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð
transform: translateX(0);Ð }ÐÐfadeInRightBig {Ð -webkit-animation-name:
fadeInRightBig;Ð animation-name: fadeInRightBig;ÐÐ@-webkit-keyframes
fadeInUp {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateY(20px);Ð transform: translateY(20px);Ð }Ð 100% {Ð
opacity: 1;Ð -webkit-transform: translateY(0);Ð transform:
translateY(0);Ð }ÐÐ@keyframes fadeInUp {Ð 0% {Ð opacity: 0;Ð -
webkit-transform: translateY(20px);Ð -ms-transform: translateY(20px);Ð
transform: translateY(20px);Ð }Ð 100% {Ð opacity: 1;Ð
-webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð
transform: translateY(0);Ð }ÐÐfadeInUp {Ð -webkit-animation-name:
fadeInUp;Ð animation-name: fadeInUp;ÐÐ@-webkit-keyframes fadeInUpBig {Ð 0%
{Ð opacity: 0;Ð -webkit-transform: translateY(2000px);Ð
transform: translateY(2000px);Ð }Ð 100% {Ð opacity: 1;Ð -
webkit-transform: translateY(0);Ð transform: translateY(0);Ð }ÐÐ
@keyframes fadeInUpBig {Ð 0% {Ð opacity: 0;Ð -webkit-transform:
translateY(2000px);Ð -ms-transform: translateY(2000px);Ð
transform: translateY(2000px);Ð

}Ð 100% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }ÐÐfadeInUpBig {Ð -webkit-animation-name: fadeInUpBig;Ð animation-name: fadeInUpBig;ÐÐ@-webkit-keyframes fadeOut {Ð 0% {Ð opacity: 1;Ð }Ð 100% {Ð opacity: 0;Ð }ÐÐ@keyframes fadeOut {Ð 0% {Ð opacity: 1;Ð }Ð 100% {Ð opacity: 0;Ð }ÐÐ .fadeOut {Ð -webkit-animation-name: fadeOut;Ð animation-name: fadeOut;ÐÐ@-webkit-keyframes fadeOutDown {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(20px);Ð transform: translateY(20px);Ð }ÐÐ@keyframes fadeOutDown {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(20px);Ð -ms-transform: translateY(20px);Ð transform: translateY(20px);Ð }ÐÐfadeOutDown {Ð -webkit-animation-name: fadeOutDown;Ð animation-name: fadeOutDown;ÐÐ@-webkit-keyframes fadeOutDownBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(2000px);Ð transform: translateY(2000px);Ð }ÐÐ@keyframes fadeOutDownBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(2000px);Ð -ms-transform: translateY(2000px);Ð transform: translateY(2000px);Ð }ÐÐ .fadeOutDownBig {Ð -webkit-animation-name: fadeOutDownBig;Ð animation-name: fadeOutDownBig;ÐÐ@-webkit-keyframes fadeOutLeft {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-20px);Ð transform: translateX(-20px);Ð }ÐÐ@keyframes fadeOutLeft {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-20px);Ð -ms-transform: translateX(-20px);Ð transform: translateX(-20px);Ð }ÐÐfadeOutLeft {Ð -webkit-animation-name: fadeOutLeft;Ð animation-name: fadeOutLeft;ÐÐ@-webkit-keyframes fadeOutLeftBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }ÐÐ @keyframes fadeOutLeftBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð -ms-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }ÐÐfadeOutLeftBig {Ð -webkit-animation-name: fadeOutLeftBig;Ð animation-name: fadeOutLeftBig;ÐÐ@-webkit-keyframes fadeOutRight {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(20px);Ð transform: translateX(20px);Ð }ÐÐ@keyframes fadeOutRight {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(20px);Ð -ms-transform: translateX(20px);Ð transform: translateX(20px);Ð }ÐÐfadeOutRight {Ð -webkit-animation-name: fadeOutRight;Ð animation-name: fadeOutRight;ÐÐ@-webkit-keyframes fadeOutRightBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(2000px);Ð transform: translateX(2000px);Ð }ÐÐ@keyframes fadeOutRightBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð

-webkit-transform: translateX(2000px);Ð -ms-transform: translateX(2000px);Ð transform: translateX(2000px);Ð }ÐÐ .fadeOutRightBig {Ð -webkit-animation-name: fadeOutRightBig;Ð animation-name: fadeOutRightBig;ÐÐ @-webkit-keyframes fadeOutUp {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(-20px);Ð transform: translateY(-20px);Ð }ÐÐ @keyframes fadeOutUp {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(-20px);Ð -ms-transform: translateY(-20px);Ð transform: translateY(-20px);Ð }ÐÐ .fadeOutUp {Ð -webkit-animation-name: fadeOutUp;Ð animation-name: fadeOutUp;ÐÐ @-webkit-keyframes fadeOutUpBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð }ÐÐ @keyframes fadeOutUpBig {Ð 0% {Ð opacity: 1;Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð -ms-transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð }ÐÐ .fadeOutUpBig {Ð -webkit-animation-name: fadeOutUpBig;Ð animation-name: fadeOutUpBig;ÐÐ @-webkit-keyframes flip {Ð 0% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(0) scale(1);Ð transform: perspective(400px) translateZ(0) rotateY(0) scale(1);Ð -webkit-animation-timing-function: ease-out;Ð animation-timing-function: ease-out;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) translateZ(150px) rotateY(170deg) scale(1);Ð transform: perspective(400px) translateZ(150px) rotateY(170deg) scale(1);Ð -webkit-animation-timing-function: ease-out;Ð animation-timing-function: ease-out;Ð }Ð 50% {Ð -webkit-transform: perspective(400px) translateZ(150px) rotateY(190deg) scale(1);Ð transform: perspective(400px) translateZ(150px) rotateY(190deg) scale(1);Ð -webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }Ð 80% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(.95);Ð transform: perspective(400px) translateZ(0) rotateY(360deg) scale(.95);Ð -webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }Ð 100% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(1);Ð transform: perspective(400px) translateZ(0) rotateY(360deg) scale(1);Ð -webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }ÐÐ @keyframes flip {Ð 0% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(0) scale(1);Ð -ms-transform: perspective(400px) translateZ(0) rotateY(0) scale(1);Ð transform: perspective(400px) translateZ(0) rotateY(0) scale(1);Ð -webkit-animation-timing-function: ease-out;Ð animation-timing-function: ease-out;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) translateZ(150px) rotateY(170deg) scale(1);Ð -ms-transform: perspective(400px) translateZ(150px) rotateY(170deg) scale(1);Ð transform: perspective(400px) translateZ(150px) rotateY(170deg) scale(1);Ð -webkit-animation-timing-function: ease-out;Ð animation-timing-function: ease-out;Ð }Ð 50% {Ð -webkit-transform: perspective(400px) translateZ(150px) rotateY(190deg) scale(1);Ð -ms-transform: perspective(400px) translateZ(150px) rotateY(190deg) scale(1);Ð transform: perspective(400px) translateZ(150px) rotateY(190deg) scale(1);Ð -webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }Ð 80% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(.95);Ð -ms-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(.95);Ð transform: perspective(400px) translateZ(0) rotateY(360deg) scale(.95);Ð

-webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }Ð 100% {Ð -webkit-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(1);Ð -ms-transform: perspective(400px) translateZ(0) rotateY(360deg) scale(1);Ð transform: perspective(400px) translateZ(0) rotateY(360deg) scale(1);Ð -webkit-animation-timing-function: ease-in;Ð animation-timing-function: ease-in;Ð }ÐÐ animated.flip {Ð -webkit-backface-visibility: visible;Ð -ms-backface-visibility: visible;Ð backface-visibility: visible;Ð -webkit-animation-name: flip;Ð animation-name: flip;ÐÐ @-webkit-keyframes flipInX {Ð 0% {Ð -webkit-transform: perspective(400px) rotateX(90deg);Ð transform: perspective(400px) rotateX(90deg);Ð opacity: 0;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) rotateX(-10deg);Ð transform: perspective(400px) rotateX(-10deg);Ð }Ð 70% {Ð -webkit-transform: perspective(400px) rotateX(10deg);Ð -ms-transform: perspective(400px) rotateX(10deg);Ð transform: perspective(400px) rotateX(10deg);Ð }Ð 100% {Ð -webkit-transform: perspective(400px) rotateX(0deg);Ð transform: perspective(400px) rotateX(0deg);Ð opacity: 1;Ð }ÐÐ @keyframes flipInX {Ð 0% {Ð -webkit-transform: perspective(400px) rotateX(90deg);Ð -ms-transform: perspective(400px) rotateX(90deg);Ð transform: perspective(400px) rotateX(90deg);Ð opacity: 0;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) rotateX(-10deg);Ð -ms-transform: perspective(400px) rotateX(-10deg);Ð transform: perspective(400px) rotateX(-10deg);Ð }Ð 70% {Ð -webkit-transform: perspective(400px) rotateX(10deg);Ð -ms-transform: perspective(400px) rotateX(10deg);Ð transform: perspective(400px) rotateX(10deg);Ð }Ð 100% {Ð -webkit-transform: perspective(400px) rotateX(0deg);Ð -ms-transform: perspective(400px) rotateX(0deg);Ð transform: perspective(400px) rotateX(0deg);Ð opacity: 1;Ð }ÐÐ flipInX {Ð -webkit-backface-visibility: visible !important;Ð -ms-backface-visibility: visible !important;Ð backface-visibility: visible !important;Ð -webkit-animation-name: flipInX;Ð animation-name: flipInX;ÐÐ @-webkit-keyframes flipInY {Ð 0% {Ð -webkit-transform: perspective(400px) rotateY(90deg);Ð transform: perspective(400px) rotateY(90deg);Ð opacity: 0;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) rotateY(-10deg);Ð transform: perspective(400px) rotateY(-10deg);Ð }Ð 70% {Ð -webkit-transform: perspective(400px) rotateY(10deg);Ð transform: perspective(400px) rotateY(10deg);Ð }Ð 100% {Ð -webkit-transform: perspective(400px) rotateY(0deg);Ð transform: perspective(400px) rotateY(0deg);Ð opacity: 1;Ð }ÐÐ @keyframes flipInY {Ð 0% {Ð -webkit-transform: perspective(400px) rotateY(90deg);Ð -ms-transform: perspective(400px) rotateY(90deg);Ð transform: perspective(400px) rotateY(90deg);Ð opacity: 0;Ð }Ð 40% {Ð -webkit-transform: perspective(400px) rotateY(-10deg);Ð -ms-transform: perspective(400px) rotateY(-10deg);Ð transform: perspective(400px) rotateY(-10deg);Ð }Ð 70% {Ð -webkit-transform: perspective(400px) rotateY(10deg);Ð -ms-transform: perspective(400px) rotateY(10deg);Ð transform: perspective(400px) rotateY(10deg);Ð }Ð 100% {Ð -webkit-transform: perspective(400px) rotateY(0deg);Ð -ms-transform: perspective(400px) rotateY(0deg);Ð transform: perspective(400px) rotateY(0deg);Ð opacity: 1;Ð }ÐÐ flipInY {Ð -webkit-backface-visibility: visible !important;Ð -ms-backface-visibility: visible !important;Ð backface-visibility: visible !important;Ð -webkit-animation-name: flipInY;Ð animation-name: flipInY;ÐÐ @-webkit-keyframes flipOutX {Ð 0% {Ð -webkit-transform: perspective(400px) rotateX(0deg);Ð transform: perspective(400px) rotateX(0deg);Ð opacity: 1;Ð }Ð 100% {Ð -webkit-transform: perspective(400px) rotateX(90deg);Ð transform: perspective(400px) rotateX(90deg);Ð opacity: 0;Ð }ÐÐ @keyframes flipOutX {Ð 0% {Ð -webkit-transform: perspective(400px) rotateX(0deg);Ð -ms-transform: perspective(400px) rotateX(0deg);Ð transform: perspective(400px) rotateX(0deg);Ð opacity: 1;Ð

```
                }Ð   100% {Ð       -webkit-transform: perspective(400px)
rotateX(90deg);Ð       -ms-transform: perspective(400px) rotateX(90deg);Ð
        transform: perspective(400px) rotateX(90deg);Ð       opacity: 0;Ð   }ÐÐ
.flipOutX {Ð   -webkit-animation-name: flipOutX;Ð   animation-name: flipOutX;Ð
    -webkit-backface-visibility: visible !important;Ð   -ms-backface-
visibility: visible !important;Ð   backface-visibility: visible !important;ÐÐ@-
webkit-keyframes flipOutY {Ð   0% {Ð       -webkit-transform:
perspective(400px) rotateY(0deg);Ð       transform: perspective(400px)
rotateY(0deg);Ð       opacity: 1;Ð   }Ð   100% {Ð       -webkit-transform:
perspective(400px) rotateY(90deg);Ð       transform: perspective(400px)
rotateY(90deg);Ð       opacity: 0;Ð   }ÐÐ@keyframes flipOutY {Ð   0% {Ð       -
webkit-transform: perspective(400px) rotateY(0deg);Ð       -ms-transform:
perspective(400px) rotateY(0deg);Ð       transform: perspective(400px)
rotateY(0deg);Ð       opacity: 1;Ð   }Ð   100% {Ð       -webkit-transform:
perspective(400px) rotateY(90deg);Ð       -ms-transform: perspective(400px)
rotateY(90deg);Ð       transform: perspective(400px) rotateY(90deg);Ð
opacity: 0;Ð   }ÐÐflipOutY {Ð   -webkit-backface-visibility: visible !
important;Ð   -ms-backface-visibility: visible !important;Ð   backface-
visibility: visible !important;Ð   -webkit-animation-name: flipOutY;Ð
animation-name: flipOutY;ÐÐ@-webkit-keyframes lightSpeedIn {Ð   0% {Ð       -
webkit-transform: translateX(100%) skewX(-30deg);Ð       transform:
translateX(100%) skewX(-30deg);Ð       opacity: 0;Ð   }Ð   60% {Ð       -
webkit-transform: translateX(-20%) skewX(30deg);Ð       transform:
translateX(-20%) skewX(30deg);Ð       opacity: 1;Ð   }Ð   80% {Ð       -
webkit-transform: translateX(0%) skewX(-15deg);Ð       transform:
translateX(0%) skewX(-15deg);Ð       opacity: 1;Ð   }Ð   100% {Ð       -
webkit-transform: translateX(0%) skewX(0deg);Ð       transform:
translateX(0%) skewX(0deg);Ð       opacity: 1;Ð   }ÐÐ@keyframes lightSpeedIn {Ð
    0% {Ð       -webkit-transform: translateX(100%) skewX(-30deg);Ð       -ms-
transform: translateX(100%) skewX(-30deg);Ð       transform: translateX(100%)
skewX(-30deg);Ð       opacity: 0;Ð   }Ð   60% {Ð       -webkit-transform:
translateX(-20%) skewX(30deg);Ð       -ms-transform: translateX(-20%)
skewX(30deg);Ð       transform: translateX(-20%) skewX(30deg);Ð
opacity: 1;Ð   }Ð   80% {Ð       -webkit-transform: translateX(0%)
skewX(-15deg);Ð       -ms-transform: translateX(0%) skewX(-15deg);Ð
transform: translateX(0%) skewX(-15deg);Ð       opacity: 1;Ð   }Ð   100% {Ð
        -webkit-transform: translateX(0%) skewX(0deg);Ð       -ms-transform:
translateX(0%) skewX(0deg);Ð       transform: translateX(0%) skewX(0deg);Ð
        opacity: 1;Ð   }ÐÐlightSpeedIn {Ð   -webkit-animation-name:
lightSpeedIn;Ð   animation-name: lightSpeedIn;Ð   -webkit-animation-timing-
function: ease-out;Ð   animation-timing-function: ease-out;ÐÐ@-webkit-
keyframes lightSpeedOut {Ð   0% {Ð       -webkit-transform: translateX(0%)
skewX(0deg);Ð       transform: translateX(0%) skewX(0deg);Ð       opacity: 1;Ð
    }Ð   100% {Ð       -webkit-transform: translateX(100%) skewX(-30deg);Ð
        transform: translateX(100%) skewX(-30deg);Ð       opacity: 0;Ð   }ÐÐ
@keyframes lightSpeedOut {Ð   0% {Ð       -webkit-transform: translateX(0%)
skewX(0deg);Ð       -ms-transform: translateX(0%) skewX(0deg);Ð
transform: translateX(0%) skewX(0deg);Ð       opacity: 1;Ð   }Ð   100% {Ð
        -webkit-transform: translateX(100%) skewX(-30deg);Ð       -ms-
transform: translateX(100%) skewX(-30deg);Ð       transform: translateX(100%)
skewX(-30deg);Ð       opacity: 0;Ð   }ÐÐlightSpeedOut {Ð   -webkit-animation-
name: lightSpeedOut;Ð   animation-name: lightSpeedOut;Ð   -webkit-animation-
timing-function: ease-in;Ð   animation-timing-function: ease-in;ÐÐ@-webkit-
keyframes rotateIn {Ð   0% {Ð       -webkit-transform-origin: center center;Ð
        transform-origin: center center;Ð       -webkit-transform:
rotate(-200deg);Ð       transform: rotate(-200deg);Ð       opacity: 0;Ð   }Ð
    100% {Ð       -webkit-transform-origin: center center;Ð       transform-
origin: center center;Ð       -webkit-transform: rotate(0);Ð       transform:
rotate(0);Ð       opacity: 1;Ð   }ÐÐ@keyframes rotateIn {Ð   0% {Ð       -
webkit-transform-origin: center center;Ð
```

-ms-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(-200deg);Ð -ms-transform: rotate(-200deg);Ð transform: rotate(-200deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: center center;Ð -ms-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ .rotateIn {Ð -webkit-animation-name: rotateIn;Ð animation-name: rotateIn;ÐÐ @-webkit-keyframes rotateInDownLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ @keyframes rotateInDownLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(-90deg);Ð -ms-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ .rotateInDownLeft {Ð -webkit-animation-name: rotateInDownLeft;Ð animation-name: rotateInDownLeft;ÐÐ @-webkit-keyframes rotateInDownRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ @keyframes rotateInDownRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(90deg);Ð -ms-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ .rotateInDownRight {Ð -webkit-animation-name: rotateInDownRight;Ð animation-name: rotateInDownRight;ÐÐ @-webkit-keyframes rotateInUpLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ @keyframes rotateInUpLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(90deg);Ð -ms-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ .rotateInUpLeft {Ð -webkit-animation-name: rotateInUpLeft;Ð animation-name: rotateInUpLeft;ÐÐ @-webkit-keyframes rotateInUpRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }Ð 100% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ @keyframes rotateInUpRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð

transform-origin: right bottom;Ð -webkit-transform: rotate(-90deg);Ð -ms-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }ÐÐ 100% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ.rotateInUpRight {Ð -webkit-animation-name: rotateInUpRight;Ð animation-name: rotateInUpRight;ÐÐ@-webkit-keyframes rotateOut {Ð 0% {Ð -webkit-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(200deg);Ð transform: rotate(200deg);Ð opacity: 0;Ð }ÐÐ@keyframes rotateOut {Ð 0% {Ð -webkit-transform-origin: center center;Ð -ms-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: center center;Ð -ms-transform-origin: center center;Ð transform-origin: center center;Ð -webkit-transform: rotate(200deg);Ð -ms-transform: rotate(200deg);Ð transform: rotate(200deg);Ð opacity: 0;Ð }ÐÐ .rotateOut {Ð -webkit-animation-name: rotateOut;Ð animation-name: rotateOut;ÐÐ@-webkit-keyframes rotateOutDownLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }ÐÐ@keyframes rotateOutDownLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(90deg);Ð -ms-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }ÐÐ.rotateOutDownLeft {Ð -webkit-animation-name: rotateOutDownLeft;Ð animation-name: rotateOutDownLeft;ÐÐ@-webkit-keyframes rotateOutDownRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }ÐÐ@keyframes rotateOutDownRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(-90deg);Ð -ms-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }ÐÐ.rotateOutDownRight {Ð -webkit-animation-name: rotateOutDownRight;Ð animation-name: rotateOutDownRight;ÐÐ@-webkit-keyframes rotateOutUpLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }ÐÐ 100% {Ð -webkit-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }ÐÐ@keyframes rotateOutUpLeft {Ð 0% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð

transform-origin: left bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }Ð 100% {Ð -webkit-transform-origin: left bottom;Ð -ms-transform-origin: left bottom;Ð transform-origin: left bottom;Ð -webkit-transform: rotate(-90deg);Ð -ms-transform: rotate(-90deg);Ð transform: rotate(-90deg);Ð opacity: 0;Ð }ÐÐ .rotateOutUpLeft {Ð -webkit-animation-name: rotateOutUpLeft;Ð animation-name: rotateOutUpLeft;ÐÐ@-webkit-keyframes rotateOutUpRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }Ð 100% {Ð -webkit-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }ÐÐ @keyframes rotateOutUpRight {Ð 0% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(0);Ð -ms-transform: rotate(0);Ð transform: rotate(0);Ð opacity: 1;Ð }Ð 100% {Ð -webkit-transform-origin: right bottom;Ð -ms-transform-origin: right bottom;Ð transform-origin: right bottom;Ð -webkit-transform: rotate(90deg);Ð -ms-transform: rotate(90deg);Ð transform: rotate(90deg);Ð opacity: 0;Ð }ÐÐrotateOutUpRight {Ð -webkit-animation-name: rotateOutUpRight;Ð animation-name: rotateOutUpRight;ÐÐ @-webkit-keyframes slideInDown {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð }Ð 100% {Ð -webkit-transform: translateY(0);Ð transform: translateY(0);Ð }ÐÐ@keyframes slideInDown {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð -ms-transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð }Ð 100% {Ð -webkit-transform: translateY(0);Ð -ms-transform: translateY(0);Ð transform: translateY(0);Ð }ÐÐslideInDown {Ð -webkit-animation-name: slideInDown;Ð animation-name: slideInDown;ÐÐ@-webkit-keyframes slideInLeft {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð 100% {Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐ@keyframes slideInLeft {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð -ms-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }Ð 100% {Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐslideInLeft {Ð -webkit-animation-name: slideInLeft;Ð animation-name: slideInLeft;ÐÐ@-webkit-keyframes slideInRight {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateX(2000px);Ð transform: translateX(2000px);Ð }Ð 100% {Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐ@keyframes slideInRight {Ð 0% {Ð opacity: 0;Ð -webkit-transform: translateX(2000px);Ð -ms-transform: translateX(2000px);Ð transform: translateX(2000px);Ð }Ð 100% {Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }ÐÐslideInRight {Ð -webkit-animation-name: slideInRight;Ð animation-name: slideInRight;ÐÐ@-webkit-keyframes slideOutLeft {Ð 0% {Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }ÐÐ@keyframes slideOutLeft {Ð 0% {Ð -webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-transform: translateX(-2000px);Ð -ms-transform: translateX(-2000px);Ð transform: translateX(-2000px);Ð }ÐÐ .slideOutLeft {Ð -webkit-animation-name: slideOutLeft;Ð animation-name: slideOutLeft;ÐÐ@-webkit-keyframes slideOutRight {Ð 0% {Ð -webkit-transform: translateX(0);Ð transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð

-webkit-transform: translateX(2000px);Ð
transform: translateX(2000px);Ð }ÐÐ@keyframes slideOutRight {Ð 0% {Ð
-webkit-transform: translateX(0);Ð -ms-transform: translateX(0);Ð
transform: translateX(0);Ð }Ð 100% {Ð opacity: 0;Ð -webkit-
transform: translateX(2000px);Ð -ms-transform: translateX(2000px);Ð
transform: translateX(2000px);Ð }ÐÐslideOutRight {Ð -webkit-
animation-name: slideOutRight;Ð animation-name: slideOutRight;ÐÐ@-webkit-
keyframes slideOutUp {Ð 0% {Ð -webkit-transform: translateY(0);Ð
transform: translateY(0);Ð }Ð 100% {Ð opacity: 0;Ð -
webkit-transform: translateY(-2000px);Ð transform: translateY(-2000px);Ð
}ÐÐ@keyframes slideOutUp {Ð 0% {Ð -webkit-transform: translateY(0);Ð
-ms-transform: translateY(0);Ð transform: translateY(0);Ð }Ð
100% {Ð opacity: 0;Ð -webkit-transform: translateY(-2000px);Ð
-ms-transform: translateY(-2000px);Ð transform:
translateY(-2000px);Ð }ÐÐslideOutUp {Ð -webkit-animation-name: slideOutUp;Ð
animation-name: slideOutUp;ÐÐ@-webkit-keyframes slideOutDown {Ð 0% {Ð
-webkit-transform: translateY(0);Ð transform: translateY(0);Ð
}Ð 100% {Ð opacity: 0;Ð -webkit-transform:
translateY(2000px);Ð transform: translateY(2000px);Ð }ÐÐ@keyframes
slideOutDown {Ð 0% {Ð -webkit-transform: translateY(0);Ð -ms-
transform: translateY(0);Ð transform: translateY(0);Ð }Ð 100% {Ð
opacity: 0;Ð -webkit-transform: translateY(2000px);Ð -ms-
transform: translateY(2000px);Ð transform: translateY(2000px);Ð }ÐÐ
.slideOutDown {Ð -webkit-animation-name: slideOutDown;Ð animation-name:
slideOutDown;ÐÐ@-webkit-keyframes hinge {Ð 0% {Ð -webkit-transform:
rotate(0);Ð transform: rotate(0);Ð -webkit-transform-origin: top
left;Ð transform-origin: top left;Ð -webkit-animation-timing-
function: ease-in-out;Ð animation-timing-function: ease-in-out;Ð }Ð
20%, 60% {Ð -webkit-transform: rotate(80deg);Ð transform:
rotate(80deg);Ð -webkit-transform-origin: top left;Ð transform-
origin: top left;Ð -webkit-animation-timing-function: ease-in-out;Ð
animation-timing-function: ease-in-out;Ð }Ð 40% {Ð -webkit-
transform: rotate(60deg);Ð transform: rotate(60deg);Ð -webkit-
transform-origin: top left;Ð transform-origin: top left;Ð -webkit-
animation-timing-function: ease-in-out;Ð animation-timing-function:
ease-in-out;Ð }Ð 80% {Ð -webkit-transform: rotate(60deg)
translateY(0);Ð transform: rotate(60deg) translateY(0);Ð -webkit-
transform-origin: top left;Ð transform-origin: top left;Ð -webkit-
animation-timing-function: ease-in-out;Ð animation-timing-function:
ease-in-out;Ð opacity: 1;Ð }Ð 100% {Ð -webkit-transform:
translateY(700px);Ð transform: translateY(700px);Ð opacity: 0;Ð
}ÐÐ@keyframes hinge {Ð 0% {Ð -webkit-transform: rotate(0);Ð -
ms-transform: rotate(0);Ð transform: rotate(0);Ð -webkit-
transform-origin: top left;Ð -ms-transform-origin: top left;Ð
transform-origin: top left;Ð -webkit-animation-timing-function: ease-in-
out;Ð animation-timing-function: ease-in-out;Ð }Ð 20%, 60% {Ð
-webkit-transform: rotate(80deg);Ð -ms-transform: rotate(80deg);Ð
transform: rotate(80deg);Ð -webkit-transform-origin: top left;Ð -
ms-transform-origin: top left;Ð transform-origin: top left;Ð -
webkit-animation-timing-function: ease-in-out;Ð animation-timing-
function: ease-in-out;Ð }Ð 40% {Ð -webkit-transform: rotate(60deg);Ð
-ms-transform: rotate(60deg);Ð transform: rotate(60deg);Ð
-webkit-transform-origin: top left;Ð -ms-transform-origin: top left;Ð
transform-origin: top left;Ð -webkit-animation-timing-function:
ease-in-out;Ð animation-timing-function: ease-in-out;Ð }Ð 80% {Ð
-webkit-transform: rotate(60deg) translateY(0);Ð -ms-transform:
rotate(60deg) translateY(0);Ð transform: rotate(60deg) translateY(0);Ð
-webkit-transform-origin: top left;Ð -ms-transform-origin: top
left;Ð transform-origin: top left;Ð -webkit-animation-timing-
function: ease-in-out;Ð

animation-timing-function: ease-in-out;Ð
opacity: 1;Ð   }Ð   100% {Ð   -webkit-transform: translateY(700px);Ð
        -ms-transform: translateY(700px);Ð   transform: translateY(700px);Ð
        opacity: 0;Ð   }ÐÐhinge {Ð   -webkit-animation-name: hinge;Ð
animation-name: hinge;ÐÐ* originally authored by Nick Pettit - https://
github.com/nickpettit/glide */Ð@-webkit-keyframes rollIn {Ð   0% {Ð
opacity: 0;Ð   -webkit-transform: translateX(-100%) rotate(-120deg);Ð
        transform: translateX(-100%) rotate(-120deg);Ð   }Ð   100% {Ð
opacity: 1;Ð   -webkit-transform: translateX(0px) rotate(0deg);Ð
transform: translateX(0px) rotate(0deg);Ð   }ÐÐ@keyframes rollIn {Ð   0% {Ð
        opacity: 0;Ð   -webkit-transform: translateX(-100%)
rotate(-120deg);Ð   -ms-transform: translateX(-100%) rotate(-120deg);Ð
        transform: translateX(-100%) rotate(-120deg);Ð   }Ð   100% {Ð
opacity: 1;Ð   -webkit-transform: translateX(0px) rotate(0deg);Ð   -
ms-transform: translateX(0px) rotate(0deg);Ð   transform: translateX(0px)
rotate(0deg);Ð   }ÐÐrollIn {Ð   -webkit-animation-name: rollIn;Ð   animation-
name: rollIn;ÐÐ* originally authored by Nick Pettit - https://github.com/
nickpettit/glide */Ð@-webkit-keyframes rollOut {Ð   0% {Ð   opacity: 1;Ð
        -webkit-transform: translateX(0px) rotate(0deg);Ð   transform:
translateX(0px) rotate(0deg);Ð   }Ð   100% {Ð   opacity: 0;Ð   -
webkit-transform: translateX(100%) rotate(120deg);Ð   transform:
translateX(100%) rotate(120deg);Ð   }ÐÐ@keyframes rollOut {Ð   0% {Ð
opacity: 1;Ð   -webkit-transform: translateX(0px) rotate(0deg);Ð   -
ms-transform: translateX(0px) rotate(0deg);Ð   transform: translateX(0px)
rotate(0deg);Ð   }Ð   100% {Ð   opacity: 0;Ð   -webkit-transform:
translateX(100%) rotate(120deg);Ð   -ms-transform: translateX(100%)
rotate(120deg);Ð   transform: translateX(100%) rotate(120deg);Ð   }ÐÐ
.rollOut {Ð   -webkit-animation-name: rollOut;Ð   animation-name: rollOut;Ð

public\assets\css\bootstrap.css

/*!Ð* Bootstrap v3.3.6 (http://getbootstrap.com)Ð* Copyright 2011-2015 Twitter, Inc.Ð* Licensed under MIT (https://github.com/twbs/bootstrap/blob/master/LICENSE)Ð*/Ð*! normalize.css v3.0.3 | MIT License | github.com/necolas/normalize.css */Ðhtml {Ð font-family: sans-serif;Ð -webkit-text-size-adjust: 100%;Ð -ms-text-size-adjust: 100%;ÐÐbody {Ð margin: 0;ÐÐarticle,Ðaside,Ð details,Ðfigcaption,Ðfigure,Ðfooter,Ðheader,Ðhgroup,Ðmain,Ðmenu,Ðnav,Ðsection,Ðsummary {Ð display: block;ÐÐaudio,Ðcanvas,Ðprogress,Ðvideo {Ð display: inline-block;Ð vertical-align: baseline;ÐÐaudio:not([controls]) {Ð display: none;Ð height: 0;ÐÐ[hidden],Ðtemplate {Ð display: none;ÐÐa {Ð background-color: transparent;ÐÐa:active,Ða:hover {Ð outline: 0;ÐÐabbr[title] {Ð border-bottom: 1px dotted;ÐÐb,Ð strong {Ð font-weight: bold;ÐÐdfn {Ð font-style: italic;ÐÐh1 {Ð margin: .67em 0;Ð font-size: 2em;ÐÐmark {Ð color: #000;Ð background: #ff0;ÐÐsmall {Ð font-size: 80%;ÐÐsub,Ðsup {Ð position: relative;Ð font-size: 75%;Ð line-height: 0;Ð vertical-align: baseline;ÐÐsup {Ð top: -.5em;ÐÐsub {Ð bottom: -.25em;ÐÐimg {Ð border: 0;ÐÐsvg:not(:root) {Ð overflow: hidden;ÐÐfigure {Ð margin: 1em 40px;ÐÐhr {Ð height: 0;Ð -webkit-box-sizing: content-box;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÐÐpre {Ð overflow: auto;ÐÐcode,Ðkbd,Ðpre,Ð samp {Ð font-family: monospace, monospace;Ð font-size: 1em;ÐÐbutton,Ðinput,Ð optgroup,Ðselect,Ðtextarea {Ð margin: 0;Ð font: inherit;Ð color: inherit;ÐÐbutton {Ð overflow: visible;ÐÐbutton,Ðselect {Ð text-transform: none;ÐÐbutton,Ð html input[type="button"],Ðinput[type="reset"],Ðinput[type="submit"] {Ð -webkit-appearance: button;Ð cursor: pointer;ÐÐbutton[disabled],Ðhtml input[disabled] {Ð cursor: default;ÐÐbutton::-moz-focus-inner,Ðinput::-moz-focus-inner {Ð padding: 0;Ð border: 0;ÐÐinput {Ð line-height: normal;ÐÐinput[type="checkbox"],Ð input[type="radio"] {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;Ð padding: 0;ÐÐinput[type="number"]::-webkit-inner-spin-button,Ðinput[type="number"]::-webkit-outer-spin-button {Ð height: auto;ÐÐinput[type="search"] {Ð -webkit-box-sizing: content-box;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;Ð -webkit-appearance: textfield;ÐÐinput[type="search"]::-webkit-search-cancel-button,Ðinput[type="search"]::-webkit-search-decoration {Ð -webkit-appearance: none;ÐÐfieldset {Ð padding: .35em .625em .75em;Ð margin: 0 2px;Ð border: 1px solid #c0c0c0;ÐÐlegend {Ð padding: 0;Ð border: 0;ÐÐtextarea {Ð overflow: auto;ÐÐoptgroup {Ð font-weight: bold;ÐÐtable {Ð border-spacing: 0;Ð border-collapse: collapse;ÐÐtd,Ðth {Ð padding: 0;ÐÐ*! Source: https://github.com/h5bp/html5-boilerplate/blob/master/src/css/main.css */@media print {Ð *,Ð *:before,Ð *:after {Ð color: #000 !important;Ð text-shadow: none !important;Ð background: transparent !important;Ð -webkit-box-shadow: none !important;Ð box-shadow: none !important;Ð }Ð a,Ð a:visited {Ð text-decoration: underline;Ð }Ð a[href]:after {Ð content: " (" attr(href) ")";Ð }Ð abbr[title]:after {Ð content: " (" attr(title) ")";Ð }Ð a[href^="#"]:after,Ð a[href^="javascript:"]:after {Ð content: "";Ð }Ð pre,Ð blockquote {Ð border: 1px solid #999;Ð page-break-inside: avoid;Ð }Ð thead {Ð display: table-header-group;Ð }Ð tr,Ð img {Ð page-break-inside: avoid;Ð }Ð img {Ð max-width: 100% !important;Ð }Ð p,Ð h2,Ð h3 {Ð orphans: 3;Ð widows: 3;Ð }Ð h2,Ð h3 {Ð page-break-after: avoid;Ð }Ð .navbar {Ð display: none;Ð }Ð .btn > .caret,Ð .dropup > .btn > .caret {Ð border-top-color: #000 !important;Ð }Ð .label {Ð border: 1px solid #000;Ð }Ð .table {Ð border-collapse: collapse !important;Ð }Ð .table td,Ð .table th {Ð background-color: #fff !important;Ð }Ð .table-bordered th,Ð .table-bordered td {Ð border: 1px solid #ddd !important;Ð }ÐÐ@font-face {Ð font-family: 'Glyphicons Halflings';Ð src: url('../fonts/glyphicons-halflings-regular.eot');Ð src: url('../fonts/glyphicons-halflings-regular.eot?#iefix') format('embedded-opentype'), url('../fonts/glyphicons-halflings-regular.woff2') format('woff2'), url('../fonts/glyphicons-halflings-regular.woff') format('woff'), url('../fonts/glyphicons-halflings-regular.ttf') format('truetype'), url('../fonts/glyphicons-halflings-regular.svg#glyphicons_halflingsregular') format('svg');ÐÐglyphicon {Ð position: relative;Ð

top: 1px;Ð display: inline-block;Ð font-family: 'Glyphicons Halflings';Ð font-style: normal;Ð font-weight: normal;Ð line-height: 1;Ð -webkit-font-smoothing: antialiased;Ð -moz-osx-font-smoothing: grayscale;ÐÐglyphicon-asterisk:before {Ð content: "\002a";ÐÐglyphicon-plus:before {Ð content: "\002b";ÐÐglyphicon-euro:before,Ðglyphicon-eur:before {Ð content: "\20ac";ÐÐglyphicon-minus:before {Ð content: "\2212";ÐÐglyphicon-cloud:before {Ð content: "\2601";ÐÐglyphicon-envelope:before {Ð content: "\2709";ÐÐglyphicon-pencil:before {Ð content: "\270f";ÐÐglyphicon-glass:before {Ð content: "\e001";ÐÐglyphicon-music:before {Ð content: "\e002";Ð }Ðglyphicon-search:before {Ð content: "\e003";ÐÐglyphicon-heart:before {Ð content: "\e005";ÐÐglyphicon-star:before {Ð content: "\e006";ÐÐglyphicon-star-empty:before {Ð content: "\e007";ÐÐglyphicon-user:before {Ð content: "\e008";ÐÐ .glyphicon-film:before {Ð content: "\e009";ÐÐglyphicon-th-large:before {Ð content: "\e010";ÐÐglyphicon-th:before {Ð content: "\e011";ÐÐglyphicon-th-list:before {Ð content: "\e012";ÐÐglyphicon-ok:before {Ð content: "\e013";ÐÐ .glyphicon-remove:before {Ð content: "\e014";ÐÐglyphicon-zoom-in:before {Ð content: "\e015";ÐÐglyphicon-zoom-out:before {Ð content: "\e016";ÐÐglyphicon-off:before {Ð content: "\e017";ÐÐglyphicon-signal:before {Ð content: "\e018";ÐÐ .glyphicon-cog:before {Ð content: "\e019";ÐÐglyphicon-trash:before {Ð content: "\e020";ÐÐglyphicon-home:before {Ð content: "\e021";ÐÐglyphicon-file:before {Ð content: "\e022";ÐÐglyphicon-time:before {Ð content: "\e023";ÐÐ .glyphicon-road:before {Ð content: "\e024";ÐÐglyphicon-download-alt:before {Ð content: "\e025";ÐÐglyphicon-download:before {Ð content: "\e026";ÐÐglyphicon-upload:before {Ð content: "\e027";ÐÐglyphicon-inbox:before {Ð content: "\e028";ÐÐglyphicon-play-circle:before {Ð content: "\e029";ÐÐglyphicon-repeat:before {Ð content: "\e030";ÐÐglyphicon-refresh:before {Ð content: "\e031";ÐÐglyphicon-list-alt:before {Ð content: "\e032";ÐÐglyphicon-lock:before {Ð content: "\e033";ÐÐglyphicon-flag:before {Ð content: "\e034";ÐÐ .glyphicon-headphones:before {Ð content: "\e035";ÐÐglyphicon-volume-off:before {Ð content: "\e036";ÐÐglyphicon-volume-down:before {Ð content: "\e037";ÐÐglyphicon-volume-up:before {Ð content: "\e038";ÐÐglyphicon-qrcode:before {Ð content: "\e039";ÐÐglyphicon-barcode:before {Ð content: "\e040";ÐÐglyphicon-tag:before {Ð content: "\e041";ÐÐglyphicon-tags:before {Ð content: "\e042";ÐÐglyphicon-book:before {Ð content: "\e043";ÐÐglyphicon-bookmark:before {Ð content: "\e044";ÐÐglyphicon-print:before {Ð content: "\e045";ÐÐglyphicon-camera:before {Ð content: "\e046";ÐÐglyphicon-font:before {Ð content: "\e047";ÐÐglyphicon-bold:before {Ð content: "\e048";ÐÐglyphicon-italic:before {Ð content: "\e049";ÐÐglyphicon-text-height:before {Ð content: "\e050";ÐÐglyphicon-text-width:before {Ð content: "\e051";ÐÐglyphicon-align-left:before {Ð content: "\e052";ÐÐglyphicon-align-center:before {Ð content: "\e053";ÐÐglyphicon-align-right:before {Ð content: "\e054";ÐÐglyphicon-align-justify:before {Ð content: "\e055";ÐÐglyphicon-list:before {Ð content: "\e056";ÐÐglyphicon-indent-left:before {Ð content: "\e057";ÐÐglyphicon-indent-right:before {Ð content: "\e058";ÐÐglyphicon-facetime-video:before {Ð content: "\e059";ÐÐglyphicon-picture:before {Ð content: "\e060";ÐÐglyphicon-map-marker:before {Ð content: "\e062";ÐÐglyphicon-adjust:before {Ð content: "\e063";ÐÐglyphicon-tint:before {Ð content: "\e064";ÐÐglyphicon-edit:before {Ð content: "\e065";ÐÐglyphicon-share:before {Ð content: "\e066";ÐÐglyphicon-check:before {Ð content: "\e067";ÐÐglyphicon-move:before {Ð content: "\e068";ÐÐ .glyphicon-step-backward:before {Ð content: "\e069";ÐÐglyphicon-fast-backward:before {Ð content: "\e070";ÐÐglyphicon-backward:before {Ð content: "\e071";ÐÐglyphicon-play:before {Ð content: "\e072";ÐÐglyphicon-pause:before {Ð content: "\e073";ÐÐglyphicon-stop:before {Ð content: "\e074";ÐÐglyphicon-forward:before {Ð content: "\e075";ÐÐglyphicon-fast-forward:before {Ð content: "\e076";ÐÐglyphicon-step-forward:before {Ð content: "\e077";ÐÐ .glyphicon-eject:before {Ð content: "\e078";ÐÐglyphicon-chevron-left:before {Ð content: "\e079";ÐÐglyphicon-chevron-right:before {Ð content: "\e080";ÐÐ .glyphicon-plus-sign:before {Ð content: "\e081";ÐÐglyphicon-minus-sign:before {Ð content: "\e082";ÐÐglyphicon-remove-sign:before {Ð content: "\e083";ÐÐ .glyphicon-ok-sign:before {Ð

content: "\e084";ÐÐglyphicon-question-
sign:before {Ð content: "\e085";ÐÐglyphicon-info-sign:before {Ð content:
"\e086";ÐÐglyphicon-screenshot:before {Ð content: "\e087";ÐÐglyphicon-remove-
circle:before {Ð content: "\e088";ÐÐglyphicon-ok-circle:before {Ð content:
"\e089";ÐÐglyphicon-ban-circle:before {Ð content: "\e090";ÐÐglyphicon-arrow-
left:before {Ð content: "\e091";ÐÐglyphicon-arrow-right:before {Ð content:
"\e092";ÐÐglyphicon-arrow-up:before {Ð content: "\e093";ÐÐglyphicon-arrow-
down:before {Ð content: "\e094";ÐÐglyphicon-share-alt:before {Ð content:
"\e095";ÐÐglyphicon-resize-full:before {Ð content: "\e096";ÐÐglyphicon-resize-
small:before {Ð content: "\e097";ÐÐglyphicon-exclamation-sign:before {Ð
content: "\e101";ÐÐglyphicon-gift:before {Ð content: "\e102";ÐÐglyphicon-
leaf:before {Ð content: "\e103";ÐÐglyphicon-fire:before {Ð content: "\e104";ÐÐ
.glyphicon-eye-open:before {Ð content: "\e105";ÐÐglyphicon-eye-close:before {Ð
content: "\e106";ÐÐglyphicon-warning-sign:before {Ð content: "\e107";ÐÐ
.glyphicon-plane:before {Ð content: "\e108";ÐÐglyphicon-calendar:before {Ð
content: "\e109";ÐÐglyphicon-random:before {Ð content: "\e110";ÐÐglyphicon-
comment:before {Ð content: "\e111";ÐÐglyphicon-magnet:before {Ð content:
"\e112";ÐÐglyphicon-chevron-up:before {Ð content: "\e113";ÐÐglyphicon-chevron-
down:before {Ð content: "\e114";ÐÐglyphicon-retweet:before {Ð content:
"\e115";ÐÐglyphicon-shopping-cart:before {Ð content: "\e116";ÐÐglyphicon-
folder-close:before {Ð content: "\e117";ÐÐglyphicon-folder-open:before {Ð
content: "\e118";ÐÐglyphicon-resize-vertical:before {Ð content: "\e119";ÐÐ
.glyphicon-resize-horizontal:before {Ð content: "\e120";ÐÐglyphicon-
hdd:before {Ð content: "\e121";ÐÐglyphicon-bullhorn:before {Ð content:
"\e122";ÐÐglyphicon-bell:before {Ð content: "\e123";ÐÐglyphicon-
certificate:before {Ð content: "\e124";ÐÐglyphicon-thumbs-up:before {Ð
content: "\e125";ÐÐglyphicon-thumbs-down:before {Ð content: "\e126";ÐÐ
.glyphicon-hand-right:before {Ð content: "\e127";ÐÐglyphicon-hand-left:before
{Ð content: "\e128";ÐÐglyphicon-hand-up:before {Ð content: "\e129";ÐÐ
.glyphicon-hand-down:before {Ð content: "\e130";ÐÐglyphicon-circle-arrow-
right:before {Ð content: "\e131";ÐÐglyphicon-circle-arrow-left:before {Ð
content: "\e132";ÐÐglyphicon-circle-arrow-up:before {Ð content: "\e133";ÐÐ
.glyphicon-circle-arrow-down:before {Ð content: "\e134";ÐÐglyphicon-
globe:before {Ð content: "\e135";ÐÐglyphicon-wrench:before {Ð content:
"\e136";ÐÐglyphicon-tasks:before {Ð content: "\e137";ÐÐglyphicon-
filter:before {Ð content: "\e138";ÐÐglyphicon-briefcase:before {Ð content:
"\e139";ÐÐglyphicon-fullscreen:before {Ð content: "\e140";ÐÐglyphicon-
dashboard:before {Ð content: "\e141";ÐÐglyphicon-paperclip:before {Ð content:
"\e142";ÐÐglyphicon-heart-empty:before {Ð content: "\e143";ÐÐglyphicon-
link:before {Ð content: "\e144";ÐÐglyphicon-phone:before {Ð content: "\e145";ÐÐ
.glyphicon-pushpin:before {Ð content: "\e146";ÐÐglyphicon-usd:before {Ð
content: "\e148";ÐÐglyphicon-gbp:before {Ð content: "\e149";ÐÐglyphicon-
sort:before {Ð content: "\e150";ÐÐglyphicon-sort-by-alphabet:before {Ð
content: "\e151";ÐÐglyphicon-sort-by-alphabet-alt:before {Ð content: "\e152";ÐÐ
.glyphicon-sort-by-order:before {Ð content: "\e153";ÐÐglyphicon-sort-by-order-
alt:before {Ð content: "\e154";ÐÐglyphicon-sort-by-attributes:before {Ð
content: "\e155";ÐÐglyphicon-sort-by-attributes-alt:before {Ð content:
"\e156";ÐÐglyphicon-unchecked:before {Ð content: "\e157";ÐÐglyphicon-
expand:before {Ð content: "\e158";ÐÐglyphicon-collapse-down:before {Ð
content: "\e159";ÐÐglyphicon-collapse-up:before {Ð content: "\e160";ÐÐ
.glyphicon-log-in:before {Ð content: "\e161";ÐÐglyphicon-flash:before {Ð
content: "\e162";ÐÐglyphicon-log-out:before {Ð content: "\e163";ÐÐglyphicon-
new-window:before {Ð content: "\e164";ÐÐglyphicon-record:before {Ð content:
"\e165";ÐÐglyphicon-save:before {Ð content: "\e166";ÐÐglyphicon-open:before {Ð
content: "\e167";ÐÐglyphicon-saved:before {Ð content: "\e168";ÐÐglyphicon-
import:before {Ð content: "\e169";ÐÐglyphicon-export:before {Ð content:
"\e170";ÐÐglyphicon-send:before {Ð content: "\e171";ÐÐglyphicon-floppy-
disk:before {Ð content: "\e172";ÐÐglyphicon-floppy-saved:before {Ð content:
"\e173";ÐÐglyphicon-floppy-remove:before {Ð content: "\e174";ÐÐglyphicon-
floppy-save:before {Ð

content: "\e175";ÐÐglyphicon-floppy-open:before {Ð
content: "\e176";ÐÐglyphicon-credit-card:before {Ð content: "\e177";ÐÐ
.glyphicon-transfer:before {Ð content: "\e178";ÐÐglyphicon-cutlery:before {Ð
content: "\e179";ÐÐglyphicon-header:before {Ð content: "\e180";ÐÐglyphicon-
compressed:before {Ð content: "\e181";ÐÐglyphicon-earphone:before {Ð content:
"\e182";ÐÐglyphicon-phone-alt:before {Ð content: "\e183";ÐÐglyphicon-
tower:before {Ð content: "\e184";ÐÐglyphicon-stats:before {Ð content: "\e185";Ð
}Ðglyphicon-sd-video:before {Ð content: "\e186";ÐÐglyphicon-hd-video:before {Ð
content: "\e187";ÐÐglyphicon-subtitles:before {Ð content: "\e188";ÐÐ
.glyphicon-sound-stereo:before {Ð content: "\e189";ÐÐglyphicon-sound-
dolby:before {Ð content: "\e190";ÐÐglyphicon-sound-5-1:before {Ð content:
"\e191";ÐÐglyphicon-sound-6-1:before {Ð content: "\e192";ÐÐglyphicon-
sound-7-1:before {Ð content: "\e193";ÐÐglyphicon-copyright-mark:before {Ð
content: "\e194";ÐÐglyphicon-registration-mark:before {Ð content: "\e195";ÐÐ
.glyphicon-cloud-download:before {Ð content: "\e197";ÐÐglyphicon-cloud-
upload:before {Ð content: "\e198";ÐÐglyphicon-tree-conifer:before {Ð content:
"\e199";ÐÐglyphicon-tree-deciduous:before {Ð content: "\e200";ÐÐglyphicon-
cd:before {Ð content: "\e201";ÐÐglyphicon-save-file:before {Ð content:
"\e202";ÐÐglyphicon-open-file:before {Ð content: "\e203";ÐÐglyphicon-level-
up:before {Ð content: "\e204";ÐÐglyphicon-copy:before {Ð content: "\e205";ÐÐ
.glyphicon-paste:before {Ð content: "\e206";ÐÐglyphicon-alert:before {Ð
content: "\e209";ÐÐglyphicon-equalizer:before {Ð content: "\e210";ÐÐglyphicon-
king:before {Ð content: "\e211";ÐÐglyphicon-queen:before {Ð content: "\e212";ÐÐ
.glyphicon-pawn:before {Ð content: "\e213";ÐÐglyphicon-bishop:before {Ð
content: "\e214";ÐÐglyphicon-knight:before {Ð content: "\e215";ÐÐglyphicon-
baby-formula:before {Ð content: "\e216";ÐÐglyphicon-tent:before {Ð content:
"\26fa";ÐÐglyphicon-blackboard:before {Ð content: "\e218";ÐÐglyphicon-
bed:before {Ð content: "\e219";ÐÐglyphicon-apple:before {Ð content: "\f8ff";ÐÐ
.glyphicon-erase:before {Ð content: "\e221";ÐÐglyphicon-hourglass:before {Ð
content: "\231b";ÐÐglyphicon-lamp:before {Ð content: "\e223";ÐÐglyphicon-
duplicate:before {Ð content: "\e224";ÐÐglyphicon-piggy-bank:before {Ð
content: "\e225";ÐÐglyphicon-scissors:before {Ð content: "\e226";ÐÐglyphicon-
bitcoin:before {Ð content: "\e227";ÐÐglyphicon-btc:before {Ð content: "\e227";Ð
}Ðglyphicon-xbt:before {Ð content: "\e227";ÐÐglyphicon-yen:before {Ð content:
"\00a5";ÐÐglyphicon-jpy:before {Ð content: "\00a5";ÐÐglyphicon-ruble:before {Ð
content: "\20bd";ÐÐglyphicon-rub:before {Ð content: "\20bd";ÐÐglyphicon-
scale:before {Ð content: "\e230";ÐÐglyphicon-ice-lolly:before {Ð content:
"\e231";ÐÐglyphicon-ice-lolly-tasted:before {Ð content: "\e232";ÐÐglyphicon-
education:before {Ð content: "\e233";ÐÐglyphicon-option-horizontal:before {Ð
content: "\e234";ÐÐglyphicon-option-vertical:before {Ð content: "\e235";ÐÐ
.glyphicon-menu-hamburger:before {Ð content: "\e236";ÐÐglyphicon-modal-
window:before {Ð content: "\e237";ÐÐglyphicon-oil:before {Ð content: "\e238";ÐÐ
.glyphicon-grain:before {Ð content: "\e239";ÐÐglyphicon-sunglasses:before {Ð
content: "\e240";ÐÐglyphicon-text-size:before {Ð content: "\e241";ÐÐglyphicon-
text-color:before {Ð content: "\e242";ÐÐglyphicon-text-background:before {Ð
content: "\e243";ÐÐglyphicon-object-align-top:before {Ð content: "\e244";ÐÐ
.glyphicon-object-align-bottom:before {Ð content: "\e245";ÐÐglyphicon-object-
align-horizontal:before {Ð content: "\e246";ÐÐglyphicon-object-align-
left:before {Ð content: "\e247";ÐÐglyphicon-object-align-vertical:before {Ð
content: "\e248";ÐÐglyphicon-object-align-right:before {Ð content: "\e249";ÐÐ
.glyphicon-triangle-right:before {Ð content: "\e250";ÐÐglyphicon-triangle-
left:before {Ð content: "\e251";ÐÐglyphicon-triangle-bottom:before {Ð
content: "\e252";ÐÐglyphicon-triangle-top:before {Ð content: "\e253";ÐÐ
.glyphicon-console:before {Ð content: "\e254";ÐÐglyphicon-superscript:before {Ð
content: "\e255";ÐÐglyphicon-subscript:before {Ð content: "\e256";ÐÐ
.glyphicon-menu-left:before {Ð content: "\e257";ÐÐglyphicon-menu-right:before
{Ð content: "\e258";ÐÐglyphicon-menu-down:before {Ð content: "\e259";ÐÐ
.glyphicon-menu-up:before {Ð content: "\e260";ÐÐ {Ð -webkit-box-sizing:
border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÐÐ
*:before,Ð

*:after {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÞÐhtml {Ð font-size: 10px;Ð -webkit-tap-highlight-color: rgba(0, 0, 0, 0);ÞÐbody {Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 14px;Ð line-height: 1.42857143;Ð color: #333;Ð background-color: #fff;ÞÐinput,Ðbutton,Ðselect,Ð textarea {Ð font-family: inherit;Ð font-size: inherit;Ð line-height: inherit;ÞÐ a {Ð color: #337ab7;Ð text-decoration: none;ÞÐa:hover,Ða:focus {Ð color: #23527c;Ð text-decoration: underline;ÞÐa:focus {Ð outline: thin dotted;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÞÐfigure {Ð margin: 0;ÞÐimg {Ð vertical-align: middle;ÞÐimg-responsive,Ðthumbnail > img,Ð .thumbnail a > img,Ðcarousel-inner > .item > img,Ðcarousel-inner > .item > a > img {Ð display: block;Ð max-width: 100%;Ð height: auto;ÞÐimg-rounded {Ð border-radius: 6px;ÞÐimg-thumbnail {Ð display: inline-block;Ð max-width: 100%;Ð height: auto;Ð padding: 4px;Ð line-height: 1.42857143;Ð background-color: #fff;Ð border: 1px solid #ddd;Ð border-radius: 4px;Ð -webkit-transition: all .2s ease-in-out;Ð -o-transition: all .2s ease-in-out;Ð transition: all .2s ease-in-out;ÞÐimg-circle {Ð border-radius: 50%;ÞÐhr {Ð margin-top: 20px;Ð margin-bottom: 20px;Ð border: 0;Ð border-top: 1px solid #eee;ÞÐsr-only {Ð position: absolute;Ð width: 1px;Ð height: 1px;Ð padding: 0;Ð margin: -1px;Ð overflow: hidden;Ð clip: rect(0, 0, 0, 0);Ð border: 0;ÞÐsr-only-focusable:active,Ðsr-only-focusable:focus {Ð position: static;Ð width: auto;Ð height: auto;Ð margin: 0;Ð overflow: visible;Ð clip: auto;ÞÐ [role="button"] {Ð cursor: pointer;ÞÐh1,Ðh2,Ðh3,Ðh4,Ðh5,Ðh6,Ðh1,Ðh2,Ðh3,Ðh4,Ðh5,Ðh6 {Ð font-family: inherit;Ð font-weight: 500;Ð line-height: 1.1;Ð color: inherit;ÞÐh1 small,Ðh2 small,Ðh3 small,Ðh4 small,Ðh5 small,Ðh6 small,Ðh1 small,Ðh2 small,Ðh3 small,Ðh4 small,Ðh5 small,Ðh6 small,Ðh1 .small,Ðh2 .small,Ðh3 .small,Ð h4 .small,Ðh5 .small,Ðh6 .small,Ðh1 .small,Ðh2 .small,Ðh3 .small,Ðh4 .small,Ð .h5 .small,Ðh6 .small {Ð font-weight: normal;Ð line-height: 1;Ð color: #777;ÞÐ h1,Ðh1,Ðh2,Ðh2,Ðh3,Ðh3 {Ð margin-top: 20px;Ð margin-bottom: 10px;ÞÐh1 small,Ðh1 small,Ðh2 small,Ðh2 small,Ðh3 small,Ðh3 small,Ðh1 .small,Ðh1 .small,Ðh2 .small,Ð .h2 .small,Ðh3 .small,Ðh3 .small {Ð font-size: 65%;ÞÐh4,Ðh4,Ðh5,Ðh5,Ðh6,Ðh6 {Ð margin-top: 10px;Ð margin-bottom: 10px;ÞÐh4 small,Ðh4 small,Ðh5 small,Ðh5 small,Ð h6 small,Ðh6 small,Ðh4 .small,Ðh4 .small,Ðh5 .small,Ðh5 .small,Ðh6 .small,Ð .h6 .small {Ð font-size: 75%;ÞÐh1,Ðh1 {Ð font-size: 36px;ÞÐh2,Ðh2 {Ð font-size: 30px;ÞÐh3,Ðh3 {Ð font-size: 24px;ÞÐh4,Ðh4 {Ð font-size: 18px;ÞÐh5,Ðh5 {Ð font-size: 14px;ÞÐh6,Ðh6 {Ð font-size: 12px;ÞÐp {Ð margin: 0 0 10px;ÞÐlead {Ð margin-bottom: 20px;Ð font-size: 16px;Ð font-weight: 300;Ð line-height: 1.4;Þ@media (min-width: 768px) {Ð .lead {Ð font-size: 21px;Ð }ÞÐsmall,Ðsmall {Ð font-size: 85%;ÞÐmark,Ðmark {Ð padding: .2em;Ð background-color: #fcf8e3;ÞÐtext-left {Ð text-align: left;ÞÐtext-right {Ð text-align: right;ÞÐtext-center {Ð text-align: center;ÞÐtext-justify {Ð text-align: justify;ÞÐtext-nowrap {Ð white-space: nowrap;ÞÐtext-lowercase {Ð text-transform: lowercase;ÞÐtext-uppercase {Ð text-transform: uppercase;ÞÐtext-capitalize {Ð text-transform: capitalize;ÞÐtext-muted {Ð color: #777;ÞÐtext-primary {Ð color: #337ab7;ÞÐ a.text-primary:hover,Ða.text-primary:focus {Ð color: #286090;ÞÐtext-success {Ð color: #3c763d;ÞÐa.text-success:hover,Ða.text-success:focus {Ð color: #2b542c;ÞÐ .text-info {Ð color: #31708f;ÞÐa.text-info:hover,Ða.text-info:focus {Ð color: #245269;ÞÐtext-warning {Ð color: #8a6d3b;ÞÐa.text-warning:hover,Ða.text-warning:focus {Ð color: #66512c;ÞÐtext-danger {Ð color: #a94442;ÞÐa.text-danger:hover,Ða.text-danger:focus {Ð color: #843534;ÞÐbg-primary {Ð color: #fff;Ð background-color: #337ab7;ÞÐa.bg-primary:hover,Ða.bg-primary:focus {Ð background-color: #286090;ÞÐbg-success {Ð background-color: #dff0d8;ÞÐa.bg-success:hover,Ða.bg-success:focus {Ð background-color: #c1e2b3;ÞÐbg-info {Ð background-color: #d9edf7;ÞÐa.bg-info:hover,Ða.bg-info:focus {Ð background-color: #afd9ee;ÞÐbg-warning {Ð background-color: #fcf8e3;ÞÐa.bg-warning:hover,Ð a.bg-warning:focus {Ð background-color: #f7ecb5;ÞÐbg-danger {Ð background-color: #f2dede;ÞÐa.bg-danger:hover,Ða.bg-danger:focus {Ð background-color: #e4b9b9;ÞÐpage-header {Ð padding-bottom: 9px;Ð margin: 40px 0 20px;Ð border-bottom: 1px solid #eee;ÞÐul,Ðol {Ð margin-top: 0;Ð margin-bottom: 10px;ÞÐul ul,Ð ol ul,Ð

ul ol,Ðl ol {Ð margin-bottom: 0;ÐÐlist-unstyled {Ð padding-left: 0;Ð list-style: none;ÐÐlist-inline {Ð padding-left: 0;Ð margin-left: -5px;Ð list-style: none;ÐÐlist-inline > li {Ð display: inline-block;Ð padding-right: 5px;Ð padding-left: 5px;ÐÐdl {Ð margin-top: 0;Ð margin-bottom: 20px;ÐÐdt,Ðdd {Ð line-height: 1.42857143;ÐÐdt {Ð font-weight: bold;ÐÐdd {Ð margin-left: 0;ÐÐ@media (min-width: 768px) {Ð .dl-horizontal dt {Ð float: left;Ð width: 160px;Ð overflow: hidden;Ð clear: left;Ð text-align: right;Ð text-overflow: ellipsis;Ð white-space: nowrap;Ð }Ð .dl-horizontal dd {Ð margin-left: 180px;Ð }ÐÐabbr[title],Ðabbr[data-original-title] {Ð cursor: help;Ð border-bottom: 1px dotted #777;ÐÐinitialism {Ð font-size: 90%;Ð text-transform: uppercase;ÐÐblockquote {Ð padding: 10px 20px;Ð margin: 0 0 20px;Ð font-size: 17.5px;Ð border-left: 5px solid #eee;ÐÐblockquote p:last-child,Ðblockquote ul:last-child,Ðblockquote ol:last-child {Ð margin-bottom: 0;ÐÐblockquote footer,Ð blockquote small,Ðblockquote .small {Ð display: block;Ð font-size: 80%;Ð line-height: 1.42857143;Ð color: #777;ÐÐblockquote footer:before,Ðblockquote small:before,Ðblockquote .small:before {Ð content: '\2014 \00A0';ÐÐblockquote-reverse,Ðblockquote.pull-right {Ð padding-right: 15px;Ð padding-left: 0;Ð text-align: right;Ð border-right: 5px solid #eee;Ð border-left: 0;ÐÐblockquote-reverse footer:before,Ðblockquote.pull-right footer:before,Ðblockquote-reverse small:before,Ðblockquote.pull-right small:before,Ðblockquote-reverse .small:before,Ðblockquote.pull-right .small:before {Ð content: '';ÐÐ .blockquote-reverse footer:after,Ðblockquote.pull-right footer:after,Ð .blockquote-reverse small:after,Ðblockquote.pull-right small:after,Ðblockquote-reverse .small:after,Ðblockquote.pull-right .small:after {Ð content: '\00A0 \2014';ÐÐaddress {Ð margin-bottom: 20px;Ð font-style: normal;Ð line-height: 1.42857143;ÐÐcode,Ðkbd,Ðpre,Ðsamp {Ð font-family: Menlo, Monaco, Consolas, "Courier New", monospace;ÐÐcode {Ð padding: 2px 4px;Ð font-size: 90%;Ð color: #c7254e;Ð background-color: #f9f2f4;Ð border-radius: 4px;ÐÐkbd {Ð padding: 2px 4px;Ð font-size: 90%;Ð color: #fff;Ð background-color: #333;Ð border-radius: 3px;Ð -webkit-box-shadow: inset 0 -1px 0 rgba(0, 0, 0, .25);Ð box-shadow: inset 0 -1px 0 rgba(0, 0, 0, .25);ÐÐkbd kbd {Ð padding: 0;Ð font-size: 100%;Ð font-weight: bold;Ð -webkit-box-shadow: none;Ð box-shadow: none;ÐÐpre {Ð display: block;Ð padding: 9.5px;Ð margin: 0 0 10px;Ð font-size: 13px;Ð line-height: 1.42857143;Ð color: #333;Ð word-break: break-all;Ð word-wrap: break-word;Ð background-color: #f5f5f5;Ð border: 1px solid #ccc;Ð border-radius: 4px;ÐÐpre code {Ð padding: 0;Ð font-size: inherit;Ð color: inherit;Ð white-space: pre-wrap;Ð background-color: transparent;Ð border-radius: 0;ÐÐpre-scrollable {Ð max-height: 340px;Ð overflow-y: scroll;ÐÐ .container {Ð padding-right: 15px;Ð padding-left: 15px;Ð margin-right: auto;Ð margin-left: auto;ÐÐ@media (min-width: 768px) {Ð .container {Ð width: 750px;Ð }ÐÐ@media (min-width: 992px) {Ð .container {Ð width: 970px;Ð }ÐÐ@media (min-width: 1200px) {Ð .container {Ð width: 1170px;Ð }ÐÐcontainer-fluid {Ð padding-right: 15px;Ð padding-left: 15px;Ð margin-right: auto;Ð margin-left: auto;ÐÐrow {Ð margin-right: -15px;Ð margin-left: -15px;ÐÐcol-xs-1, .col-sm-1, .col-md-1, .col-lg-1, .col-xs-2, .col-sm-2, .col-md-2, .col-lg-2, .col-xs-3, .col-sm-3, .col-md-3, .col-lg-3, .col-xs-4, .col-sm-4, .col-md-4, .col-lg-4, .col-xs-5, .col-sm-5, .col-md-5, .col-lg-5, .col-xs-6, .col-sm-6, .col-md-6, .col-lg-6, .col-xs-7, .col-sm-7, .col-md-7, .col-lg-7, .col-xs-8, .col-sm-8, .col-md-8, .col-lg-8, .col-xs-9, .col-sm-9, .col-md-9, .col-lg-9, .col-xs-10, .col-sm-10, .col-md-10, .col-lg-10, .col-xs-11, .col-sm-11, .col-md-11, .col-lg-11, .col-xs-12, .col-sm-12, .col-md-12, .col-lg-12 {Ð position: relative;Ð min-height: 1px;Ð padding-right: 15px;Ð padding-left: 15px;ÐÐcol-xs-1, .col-xs-2, .col-xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8, .col-xs-9, .col-xs-10, .col-xs-11, .col-xs-12 {Ð float: left;Ð }Ðcol-xs-12 {Ð width: 100%;ÐÐcol-xs-11 {Ð width: 91.66666667%;ÐÐcol-xs-10 {Ð width: 83.33333333%;ÐÐcol-xs-9 {Ð width: 75%;ÐÐcol-xs-8 {Ð width: 66.66666667%;ÐÐcol-xs-7 {Ð width: 58.33333333%;ÐÐcol-xs-6 {Ð width: 50%;ÐÐcol-xs-5 {Ð width: 41.66666667%;ÐÐcol-xs-4 {Ð width: 33.33333333%;ÐÐcol-xs-3 {Ð width: 25%;ÐÐcol-xs-2 {Ð width: 16.66666667%;ÐÐcol-xs-1 {Ð width: 8.33333333%;Ð }Ð

.col-xs-pull-12 {Ð right: 100%;ÐÐcol-xs-pull-11 {Ð right: 91.66666667%;ÐÐcol-xs-pull-10 {Ð right: 83.33333333%;ÐÐcol-xs-pull-9 {Ð right: 75%;ÐÐcol-xs-pull-8 {Ð right: 66.66666667%;ÐÐcol-xs-pull-7 {Ð right: 58.33333333%;ÐÐcol-xs-pull-6 {Ð right: 50%;ÐÐcol-xs-pull-5 {Ð right: 41.66666667%;ÐÐcol-xs-pull-4 {Ð right: 33.33333333%;ÐÐcol-xs-pull-3 {Ð right: 25%;ÐÐcol-xs-pull-2 {Ð right: 16.66666667%;ÐÐcol-xs-pull-1 {Ð right: 8.33333333%;ÐÐcol-xs-pull-0 {Ð right: auto;ÐÐcol-xs-push-12 {Ð left: 100%;ÐÐcol-xs-push-11 {Ð left: 91.66666667%;ÐÐ.col-xs-push-10 {Ð left: 83.33333333%;ÐÐcol-xs-push-9 {Ð left: 75%;ÐÐcol-xs-push-8 {Ð left: 66.66666667%;ÐÐcol-xs-push-7 {Ð left: 58.33333333%;ÐÐcol-xs-push-6 {Ð left: 50%;ÐÐcol-xs-push-5 {Ð left: 41.66666667%;ÐÐcol-xs-push-4 {Ð left: 33.33333333%;ÐÐcol-xs-push-3 {Ð left: 25%;ÐÐcol-xs-push-2 {Ð left: 16.66666667%;ÐÐcol-xs-push-1 {Ð left: 8.33333333%;ÐÐcol-xs-push-0 {Ð left: auto;ÐÐcol-xs-offset-12 {Ð margin-left: 100%;ÐÐcol-xs-offset-11 {Ð margin-left: 91.66666667%;ÐÐcol-xs-offset-10 {Ð margin-left: 83.33333333%;ÐÐcol-xs-offset-9 {Ð margin-left: 75%;ÐÐcol-xs-offset-8 {Ð margin-left: 66.66666667%;ÐÐ.col-xs-offset-7 {Ð margin-left: 58.33333333%;ÐÐcol-xs-offset-6 {Ð margin-left: 50%;ÐÐcol-xs-offset-5 {Ð margin-left: 41.66666667%;ÐÐcol-xs-offset-4 {Ð margin-left: 33.33333333%;ÐÐcol-xs-offset-3 {Ð margin-left: 25%;ÐÐcol-xs-offset-2 {Ð margin-left: 16.66666667%;ÐÐcol-xs-offset-1 {Ð margin-left: 8.33333333%;ÐÐcol-xs-offset-0 {Ð margin-left: 0;ÐÐ@media (min-width: 768px) {Ð .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-sm-7, .col-sm-8, .col-sm-9, .col-sm-10, .col-sm-11, .col-sm-12 {Ð float: left;Ð }Ð .col-sm-12 {Ð width: 100%;Ð }Ð .col-sm-11 {Ð width: 91.66666667%;Ð }Ð .col-sm-10 {Ð width: 83.33333333%;Ð }Ð .col-sm-9 {Ð width: 75%;Ð }Ð .col-sm-8 {Ð width: 66.66666667%;Ð }Ð .col-sm-7 {Ð width: 58.33333333%;Ð }Ð .col-sm-6 {Ð width: 50%;Ð }Ð .col-sm-5 {Ð width: 41.66666667%;Ð }Ð .col-sm-4 {Ð width: 33.33333333%;Ð }Ð .col-sm-3 {Ð width: 25%;Ð }Ð .col-sm-2 {Ð width: 16.66666667%;Ð }Ð .col-sm-1 {Ð width: 8.33333333%;Ð }Ð .col-sm-pull-12 {Ð right: 100%;Ð }Ð .col-sm-pull-11 {Ð right: 91.66666667%;Ð }Ð .col-sm-pull-10 {Ð right: 83.33333333%;Ð }Ð .col-sm-pull-9 {Ð right: 75%;Ð }Ð .col-sm-pull-8 {Ð right: 66.66666667%;Ð }Ð .col-sm-pull-7 {Ð right: 58.33333333%;Ð }Ð .col-sm-pull-6 {Ð right: 50%;Ð }Ð .col-sm-pull-5 {Ð right: 41.66666667%;Ð }Ð .col-sm-pull-4 {Ð right: 33.33333333%;Ð }Ð .col-sm-pull-3 {Ð right: 25%;Ð }Ð .col-sm-pull-2 {Ð right: 16.66666667%;Ð }Ð .col-sm-pull-1 {Ð right: 8.33333333%;Ð }Ð .col-sm-pull-0 {Ð right: auto;Ð }Ð .col-sm-push-12 {Ð left: 100%;Ð }Ð .col-sm-push-11 {Ð left: 91.66666667%;Ð }Ð .col-sm-push-10 {Ð left: 83.33333333%;Ð }Ð .col-sm-push-9 {Ð left: 75%;Ð }Ð .col-sm-push-8 {Ð left: 66.66666667%;Ð }Ð .col-sm-push-7 {Ð left: 58.33333333%;Ð }Ð .col-sm-push-6 {Ð left: 50%;Ð }Ð .col-sm-push-5 {Ð left: 41.66666667%;Ð }Ð .col-sm-push-4 {Ð left: 33.33333333%;Ð }Ð .col-sm-push-3 {Ð left: 25%;Ð }Ð .col-sm-push-2 {Ð left: 16.66666667%;Ð }Ð .col-sm-push-1 {Ð left: 8.33333333%;Ð }Ð .col-sm-push-0 {Ð left: auto;Ð }Ð .col-sm-offset-12 {Ð margin-left: 100%;Ð }Ð .col-sm-offset-11 {Ð margin-left: 91.66666667%;Ð }Ð .col-sm-offset-10 {Ð margin-left: 83.33333333%;Ð }Ð .col-sm-offset-9 {Ð margin-left: 75%;Ð }Ð .col-sm-offset-8 {Ð margin-left: 66.66666667%;Ð }Ð .col-sm-offset-7 {Ð margin-left: 58.33333333%;Ð }Ð .col-sm-offset-6 {Ð margin-left: 50%;Ð }Ð .col-sm-offset-5 {Ð margin-left: 41.66666667%;Ð }Ð .col-sm-offset-4 {Ð margin-left: 33.33333333%;Ð }Ð .col-sm-offset-3 {Ð margin-left: 25%;Ð }Ð .col-sm-offset-2 {Ð margin-left: 16.66666667%;Ð }Ð .col-sm-offset-1 {Ð margin-left: 8.33333333%;Ð }Ð .col-sm-offset-0 {Ð margin-left: 0;Ð }ÐÐ@media (min-width: 992px) {Ð .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8, .col-md-9, .col-md-10, .col-md-11, .col-md-12 {Ð float: left;Ð }Ð .col-md-12 {Ð width: 100%;Ð }Ð .col-md-11 {Ð width: 91.66666667%;Ð }Ð .col-md-10 {Ð width: 83.33333333%;Ð }Ð .col-md-9 {Ð width: 75%;Ð }Ð .col-md-8 {Ð width: 66.66666667%;Ð }Ð .col-md-7 {Ð width: 58.33333333%;Ð }Ð .col-md-6 {Ð width: 50%;Ð }Ð .col-md-5 {Ð width: 41.66666667%;Ð }Ð .col-md-4 {Ð width: 33.33333333%;Ð }Ð .col-md-3 {Ð width: 25%;Ð }Ð .col-md-2 {Ð width: 16.66666667%;Ð

}Ð .col-md-1 {Ð width: 8.33333333%;Ð }Ð .col-md-pull-12 {Ð right: 100%;Ð }Ð .col-md-pull-11 {Ð right: 91.66666667%;Ð }Ð .col-md-pull-10 {Ð right: 83.33333333%;Ð }Ð .col-md-pull-9 {Ð right: 75%;Ð }Ð .col-md-pull-8 {Ð right: 66.66666667%;Ð }Ð .col-md-pull-7 {Ð right: 58.33333333%;Ð }Ð .col-md-pull-6 {Ð right: 50%;Ð }Ð .col-md-pull-5 {Ð right: 41.66666667%;Ð }Ð .col-md-pull-4 {Ð right: 33.33333333%;Ð }Ð .col-md-pull-3 {Ð right: 25%;Ð }Ð .col-md-pull-2 {Ð right: 16.66666667%;Ð }Ð .col-md-pull-1 {Ð right: 8.33333333%;Ð }Ð .col-md-pull-0 {Ð right: auto;Ð }Ð .col-md-push-12 {Ð left: 100%;Ð }Ð .col-md-push-11 {Ð left: 91.66666667%;Ð }Ð .col-md-push-10 {Ð left: 83.33333333%;Ð }Ð .col-md-push-9 {Ð left: 75%;Ð }Ð .col-md-push-8 {Ð left: 66.66666667%;Ð }Ð .col-md-push-7 {Ð left: 58.33333333%;Ð }Ð .col-md-push-6 {Ð left: 50%;Ð }Ð .col-md-push-5 {Ð left: 41.66666667%;Ð }Ð .col-md-push-4 {Ð left: 33.33333333%;Ð }Ð .col-md-push-3 {Ð left: 25%;Ð }Ð .col-md-push-2 {Ð left: 16.66666667%;Ð }Ð .col-md-push-1 {Ð left: 8.33333333%;Ð }Ð .col-md-push-0 {Ð left: auto;Ð }Ð .col-md-offset-12 {Ð margin-left: 100%;Ð }Ð .col-md-offset-11 {Ð margin-left: 91.66666667%;Ð }Ð .col-md-offset-10 {Ð margin-left: 83.33333333%;Ð }Ð .col-md-offset-9 {Ð margin-left: 75%;Ð }Ð .col-md-offset-8 {Ð margin-left: 66.66666667%;Ð }Ð .col-md-offset-7 {Ð margin-left: 58.33333333%;Ð }Ð .col-md-offset-6 {Ð margin-left: 50%;Ð }Ð .col-md-offset-5 {Ð margin-left: 41.66666667%;Ð }Ð .col-md-offset-4 {Ð margin-left: 33.33333333%;Ð }Ð .col-md-offset-3 {Ð margin-left: 25%;Ð }Ð .col-md-offset-2 {Ð margin-left: 16.66666667%;Ð }Ð .col-md-offset-1 {Ð margin-left: 8.33333333%;Ð }Ð .col-md-offset-0 {Ð margin-left: 0;Ð }ÐÐ@media (min-width: 1200px) {Ð .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-lg-6, .col-lg-7, .col-lg-8, .col-lg-9, .col-lg-10, .col-lg-11, .col-lg-12 {Ð float: left;Ð }Ð .col-lg-12 {Ð width: 100%;Ð }Ð .col-lg-11 {Ð width: 91.66666667%;Ð }Ð .col-lg-10 {Ð width: 83.33333333%;Ð }Ð .col-lg-9 {Ð width: 75%;Ð }Ð .col-lg-8 {Ð width: 66.66666667%;Ð }Ð .col-lg-7 {Ð width: 58.33333333%;Ð }Ð .col-lg-6 {Ð width: 50%;Ð }Ð .col-lg-5 {Ð width: 41.66666667%;Ð }Ð .col-lg-4 {Ð width: 33.33333333%;Ð }Ð .col-lg-3 {Ð width: 25%;Ð }Ð .col-lg-2 {Ð width: 16.66666667%;Ð }Ð .col-lg-1 {Ð width: 8.33333333%;Ð }Ð .col-lg-pull-12 {Ð right: 100%;Ð }Ð .col-lg-pull-11 {Ð right: 91.66666667%;Ð }Ð .col-lg-pull-10 {Ð right: 83.33333333%;Ð }Ð .col-lg-pull-9 {Ð right: 75%;Ð }Ð .col-lg-pull-8 {Ð right: 66.66666667%;Ð }Ð .col-lg-pull-7 {Ð right: 58.33333333%;Ð }Ð .col-lg-pull-6 {Ð right: 50%;Ð }Ð .col-lg-pull-5 {Ð right: 41.66666667%;Ð }Ð .col-lg-pull-4 {Ð right: 33.33333333%;Ð }Ð .col-lg-pull-3 {Ð right: 25%;Ð }Ð .col-lg-pull-2 {Ð right: 16.66666667%;Ð }Ð .col-lg-pull-1 {Ð right: 8.33333333%;Ð }Ð .col-lg-pull-0 {Ð right: auto;Ð }Ð .col-lg-push-12 {Ð left: 100%;Ð }Ð .col-lg-push-11 {Ð left: 91.66666667%;Ð }Ð .col-lg-push-10 {Ð left: 83.33333333%;Ð }Ð .col-lg-push-9 {Ð left: 75%;Ð }Ð .col-lg-push-8 {Ð left: 66.66666667%;Ð }Ð .col-lg-push-7 {Ð left: 58.33333333%;Ð }Ð .col-lg-push-6 {Ð left: 50%;Ð }Ð .col-lg-push-5 {Ð left: 41.66666667%;Ð }Ð .col-lg-push-4 {Ð left: 33.33333333%;Ð }Ð .col-lg-push-3 {Ð left: 25%;Ð }Ð .col-lg-push-2 {Ð left: 16.66666667%;Ð }Ð .col-lg-push-1 {Ð left: 8.33333333%;Ð }Ð .col-lg-push-0 {Ð left: auto;Ð }Ð .col-lg-offset-12 {Ð margin-left: 100%;Ð }Ð .col-lg-offset-11 {Ð margin-left: 91.66666667%;Ð }Ð .col-lg-offset-10 {Ð margin-left: 83.33333333%;Ð }Ð .col-lg-offset-9 {Ð margin-left: 75%;Ð }Ð .col-lg-offset-8 {Ð margin-left: 66.66666667%;Ð }Ð .col-lg-offset-7 {Ð margin-left: 58.33333333%;Ð }Ð .col-lg-offset-6 {Ð margin-left: 50%;Ð }Ð .col-lg-offset-5 {Ð margin-left: 41.66666667%;Ð }Ð .col-lg-offset-4 {Ð margin-left: 33.33333333%;Ð }Ð .col-lg-offset-3 {Ð margin-left: 25%;Ð }Ð .col-lg-offset-2 {Ð margin-left: 16.66666667%;Ð }Ð .col-lg-offset-1 {Ð margin-left: 8.33333333%;Ð }Ð .col-lg-offset-0 {Ð margin-left: 0;Ð }ÐÐtable {Ð background-color: transparent;ÐÐcaption {Ð padding-top: 8px;Ð padding-bottom: 8px;Ð color: #777;Ð text-align: left;ÐÐth {Ð text-align: left;ÐÐtable {Ð width: 100%;Ð max-width: 100%;Ð margin-bottom: 20px;ÐÐtable > thead > tr > th,Ðtable > tbody > tr > th,Ðtable > tfoot > tr > th,Ðtable > thead > tr > td,Ð

.table > tbody > tr > td,Ðtable > tfoot > tr > td {Ð padding: 8px;Ð line-height: 1.42857143;Ð vertical-align: top;Ð border-top: 1px solid #ddd;ÞÐtable > thead > tr > th {Ð vertical-align: bottom;Ð border-bottom: 2px solid #ddd;ÞÐtable > caption + thead > tr:first-child > th,Ðtable > colgroup + thead > tr:first-child > th,Ðtable > thead:first-child > tr:first-child > th,Ðtable > caption + thead > tr:first-child > td,Ðtable > colgroup + thead > tr:first-child > td,Ðtable > thead:first-child > tr:first-child > td {Ð border-top: 0;ÞÐtable > tbody + tbody {Ð border-top: 2px solid #ddd;ÞÐ .table .table {Ð background-color: #fff;ÞÐtable-condensed > thead > tr > th,Ð .table-condensed > tbody > tr > th,Ðtable-condensed > tfoot > tr > th,Ðtable-condensed > thead > tr > td,Ðtable-condensed > tbody > tr > td,Ðtable-condensed > tfoot > tr > td {Ð padding: 5px;ÞÐtable-bordered {Ð border: 1px solid #ddd;ÞÐtable-bordered > thead > tr > th,Ðtable-bordered > tbody > tr > th,Ðtable-bordered > tfoot > tr > th,Ðtable-bordered > thead > tr > td,Ðtable-bordered > tbody > tr > td,Ðtable-bordered > tfoot > tr > td {Ð border: 1px solid #ddd;ÞÐtable-bordered > thead > tr > th,Ðtable-bordered > thead > tr > td {Ð border-bottom-width: 2px;ÞÐtable-striped > tbody > tr:nth-of-type(odd) {Ð background-color: #f9f9f9;ÞÐtable-hover > tbody > tr:hover {Ð background-color: #f5f5f5;ÞÐable col[class*="col-"] {Ð position: static;Ð display: table-column;Ð float: none;ÞÐable td[class*="col-"],Ðable th[class*="col-"] {Ð position: static;Ð display: table-cell;Ð float: none;ÞÐtable > thead > tr > td.active,Ðtable > tbody > tr > td.active,Ðtable > tfoot > tr > td.active,Ð .table > thead > tr > th.active,Ðtable > tbody > tr > th.active,Ðtable > tfoot > tr > th.active,Ðtable > thead > tr.active > td,Ðtable > tbody > tr.active > td,Ðtable > tfoot > tr.active > td,Ðtable > thead > tr.active > th,Ðtable > tbody > tr.active > th,Ðtable > tfoot > tr.active > th {Ð background-color: #f5f5f5;ÞÐtable-hover > tbody > tr > td.active:hover,Ðtable-hover > tbody > tr > th.active:hover,Ðtable-hover > tbody > tr.active:hover > td,Ðtable-hover > tbody > tr:hover > .active,Ðtable-hover > tbody > tr.active:hover > th {Ð background-color: #e8e8e8;ÞÐtable > thead > tr > td.success,Ðtable > tbody > tr > td.success,Ðtable > tfoot > tr > td.success,Ð .table > thead > tr > th.success,Ðtable > tbody > tr > th.success,Ðtable > tfoot > tr > th.success,Ðtable > thead > tr.success > td,Ðtable > tbody > tr.success > td,Ðtable > tfoot > tr.success > td,Ðtable > thead > tr.success > th,Ðtable > tbody > tr.success > th,Ðtable > tfoot > tr.success > th {Ð background-color: #dff0d8;ÞÐtable-hover > tbody > tr > td.success:hover,Ð .table-hover > tbody > tr > th.success:hover,Ðtable-hover > tbody > tr.success:hover > td,Ðtable-hover > tbody > tr:hover > .success,Ðtable-hover > tbody > tr.success:hover > th {Ð background-color: #d0e9c6;ÞÐtable > thead > tr > td.info,Ðtable > tbody > tr > td.info,Ðtable > tfoot > tr > td.info,Ð .table > thead > tr > th.info,Ðtable > tbody > tr > th.info,Ðtable > tfoot > tr > th.info,Ðtable > thead > tr.info > td,Ðtable > tbody > tr.info > td,Ð .table > tfoot > tr.info > td,Ðtable > thead > tr.info > th,Ðtable > tbody > tr.info > th,Ðtable > tfoot > tr.info > th {Ð background-color: #d9edf7;ÞÐ .table-hover > tbody > tr > td.info:hover,Ðtable-hover > tbody > tr > th.info:hover,Ðtable-hover > tbody > tr.info:hover > td,Ðtable-hover > tbody > tr:hover > .info,Ðtable-hover > tbody > tr.info:hover > th {Ð background-color: #c4e3f3;ÞÐtable > thead > tr > td.warning,Ðtable > tbody > tr > td.warning,Ðtable > tfoot > tr > td.warning,Ðtable > thead > tr > th.warning,Ð .table > tbody > tr > th.warning,Ðtable > tfoot > tr > th.warning,Ðtable > thead > tr.warning > td,Ðtable > tbody > tr.warning > td,Ðtable > tfoot > tr.warning > td,Ðtable > thead > tr.warning > th,Ðtable > tbody > tr.warning > th,Ðtable > tfoot > tr.warning > th {Ð background-color: #fcf8e3;ÞÐtable-hover > tbody > tr > td.warning:hover,Ðtable-hover > tbody > tr > th.warning:hover,Ðtable-hover > tbody > tr.warning:hover > td,Ðtable-hover > tbody > tr:hover > .warning,Ðtable-hover > tbody > tr.warning:hover > th {Ð background-color: #faf2cc;ÞÐtable > thead > tr > td.danger,Ðtable > tbody > tr > td.danger,Ðtable > tfoot > tr > td.danger,Ðtable > thead > tr > th.danger,Ðtable > tbody > tr > th.danger,Ðtable > tfoot > tr > th.danger,Ð .table > thead > tr.danger > td,Ð

.table > tbody > tr.danger > td,Ðtable > tfoot > tr.danger > td,Ðtable > thead > tr.danger > th,Ðtable > tbody > tr.danger > th,Ðtable > tfoot > tr.danger > th {Ð background-color: #f2dede;ÐÐ .table-hover > tbody > tr > td.danger:hover,Ðtable-hover > tbody > tr > th.danger:hover,Ðtable-hover > tbody > tr.danger:hover > td,Ðtable-hover > tbody > tr:hover > .danger,Ðtable-hover > tbody > tr.danger:hover > th {Ð background-color: #ebcccc;ÐÐtable-responsive {Ð min-height: .01%;Ð overflow-x: auto;ÐÐ@media screen and (max-width: 767px) {Ð .table-responsive {Ð width: 100%;Ð margin-bottom: 15px;Ð overflow-y: hidden;Ð -ms-overflow-style: -ms-autohiding-scrollbar;Ð border: 1px solid #ddd;Ð }Ð .table-responsive > .table {Ð margin-bottom: 0;Ð }Ð .table-responsive > .table > thead > tr > th,Ð .table-responsive > .table > tbody > tr > th,Ð .table-responsive > .table > tfoot > tr > th,Ð .table-responsive > .table > thead > tr > td,Ð .table-responsive > .table > tbody > tr > td,Ð .table-responsive > .table > tfoot > tr > td {Ð white-space: nowrap;Ð }Ð .table-responsive > .table-bordered {Ð border: 0;Ð }Ð .table-responsive > .table-bordered > thead > tr > th:first-child,Ð .table-responsive > .table-bordered > tbody > tr > th:first-child,Ð .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ð .table-responsive > .table-bordered > thead > tr > td:first-child,Ð .table-responsive > .table-bordered > tbody > tr > td:first-child,Ð .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left: 0;Ð }Ð .table-responsive > .table-bordered > thead > tr > th:last-child,Ð .table-responsive > .table-bordered > tbody > tr > th:last-child,Ð .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ð .table-responsive > .table-bordered > thead > tr > td:last-child,Ð .table-responsive > .table-bordered > tbody > tr > td:last-child,Ð .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-right: 0;Ð }Ð .table-responsive > .table-bordered > tbody > tr:last-child > th,Ð .table-responsive > .table-bordered > tfoot > tr:last-child > th,Ð .table-responsive > .table-bordered > tbody > tr:last-child > td,Ð .table-responsive > .table-bordered > tfoot > tr:last-child > td {Ð border-bottom: 0;Ð }ÐÐfieldset {Ð min-width: 0;Ð padding: 0;Ð margin: 0;Ð border: 0;ÐÐlegend {Ð display: block;Ð width: 100%;Ð padding: 0;Ð margin-bottom: 20px;Ð font-size: 21px;Ð line-height: inherit;Ð color: #333;Ð border: 0;Ð border-bottom: 1px solid #e5e5e5;ÐÐ label {Ð display: inline-block;Ð max-width: 100%;Ð margin-bottom: 5px;Ð font-weight: bold;ÐÐinput[type="search"] {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÐÐ input[type="radio"],Ðinput[type="checkbox"] {Ð margin: 4px 0 0;Ð margin-top: 1px \9;Ð line-height: normal;ÐÐinput[type="file"] {Ð display: block;ÐÐ input[type="range"] {Ð display: block;Ð width: 100%;ÐÐselect[multiple],Ð select[size] {Ð height: auto;ÐÐinput[type="file"]:focus,Ð input[type="radio"]:focus,Ðinput[type="checkbox"]:focus {Ð outline: thin dotted;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐ output {Ð display: block;Ð padding-top: 7px;Ð font-size: 14px;Ð line-height: 1.42857143;Ð color: #555;ÐÐform-control {Ð display: block;Ð width: 100%;Ð height: 34px;Ð padding: 6px 12px;Ð font-size: 14px;Ð line-height: 1.42857143;Ð color: #555;Ð background-color: #fff;Ð background-image: none;Ð border: 1px solid #ccc;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);Ð -webkit-transition: border-color ease-in-out .15s, -webkit-box-shadow ease-in-out .15s;Ð -o-transition: border-color ease-in-out .15s, box-shadow ease-in-out .15s;Ð transition: border-color ease-in-out .15s, box-shadow ease-in-out .15s;ÐÐform-control:focus {Ð border-color: #66afe9;Ð outline: 0;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0,0,0,.075), 0 0 8px rgba(102, 175, 233, .6);Ð box-shadow: inset 0 1px 1px rgba(0,0,0,.075), 0 0 8px rgba(102, 175, 233, .6);ÐÐform-control::-moz-placeholder {Ð color: #999;Ð opacity: 1;ÐÐform-control:-ms-input-placeholder {Ð color: #999;ÐÐform-control::-webkit-input-placeholder {Ð color: #999;ÐÐform-control::-ms-expand {Ð background-color: transparent;Ð border: 0;ÐÐform-control[disabled],Ðform-control[readonly],Ð

fieldset[disabled] .form-control {Ð background-color: #eee;Ð
  opacity: 1;ÐÐform-control[disabled],Ðfieldset[disabled] .form-control {Ð
cursor: not-allowed;ÐÐtextarea.form-control {Ð height: auto;ÐÐ
input[type="search"] {Ð -webkit-appearance: none;ÐÐ@media screen and (-webkit-
min-device-pixel-ratio: 0) {Ð input[type="date"].form-control,Ð
input[type="time"].form-control,Ð input[type="datetime-local"].form-control,Ð
input[type="month"].form-control {Ð   line-height: 34px;Ð }Ð
input[type="date"].input-sm,Ð input[type="time"].input-sm,Ð
input[type="datetime-local"].input-sm,Ð input[type="month"].input-sm,Ð .input-
group-sm input[type="date"],Ð .input-group-sm input[type="time"],Ð .input-
group-sm input[type="datetime-local"],Ð .input-group-sm input[type="month"] {Ð
    line-height: 30px;Ð }Ð input[type="date"].input-lg,Ð
input[type="time"].input-lg,Ð input[type="datetime-local"].input-lg,Ð
input[type="month"].input-lg,Ð .input-group-lg input[type="date"],Ð .input-
group-lg input[type="time"],Ð .input-group-lg input[type="datetime-local"],Ð
  .input-group-lg input[type="month"] {Ð   line-height: 46px;Ð }ÐÐform-group {Ð
  margin-bottom: 15px;ÐÐradio,Ðcheckbox {Ð position: relative;Ð display:
block;Ð margin-top: 10px;Ð margin-bottom: 10px;ÐÐradio label,Ðcheckbox label {Ð
  min-height: 20px;Ð padding-left: 20px;Ð margin-bottom: 0;Ð font-weight:
normal;Ð cursor: pointer;ÐÐradio input[type="radio"],Ðradio-inline
input[type="radio"],Ðcheckbox input[type="checkbox"],Ðcheckbox-inline
input[type="checkbox"] {Ð position: absolute;Ð margin-top: 4px \9;Ð margin-
left: -20px;ÐÐradio + .radio,Ðcheckbox + .checkbox {Ð margin-top: -5px;ÐÐ
.radio-inline,Ðcheckbox-inline {Ð position: relative;Ð display: inline-block;Ð
  padding-left: 20px;Ð margin-bottom: 0;Ð font-weight: normal;Ð vertical-
align: middle;Ð cursor: pointer;ÐÐradio-inline + .radio-inline,Ðcheckbox-
inline + .checkbox-inline {Ð margin-top: 0;Ð margin-left: 10px;ÐÐ
input[type="radio"][disabled],Ðinput[type="checkbox"][disabled],Ð
input[type="radio"].disabled,Ðinput[type="checkbox"].disabled,Ð
fieldset[disabled] input[type="radio"],Ðfieldset[disabled]
input[type="checkbox"] {Ð cursor: not-allowed;ÐÐradio-inline.disabled,Ð
.checkbox-inline.disabled,Ðfieldset[disabled] .radio-inline,Ð
fieldset[disabled] .checkbox-inline {Ð cursor: not-allowed;ÐÐradio.disabled
label,Ðcheckbox.disabled label,Ðfieldset[disabled] .radio label,Ð
fieldset[disabled] .checkbox label {Ð cursor: not-allowed;ÐÐform-control-
static {Ð min-height: 34px;Ð padding-top: 7px;Ð padding-bottom: 7px;Ð margin-
bottom: 0;ÐÐform-control-static.input-lg,Ðform-control-static.input-sm {Ð
padding-right: 0;Ð padding-left: 0;ÐÐinput-sm {Ð height: 30px;Ð padding: 5px
10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐselect.input-
sm {Ð height: 30px;Ð line-height: 30px;ÐÐtextarea.input-sm,Ð
select[multiple].input-sm {Ð height: auto;ÐÐform-group-sm .form-control {Ð
height: 30px;Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð
border-radius: 3px;ÐÐform-group-sm select.form-control {Ð height: 30px;Ð line-
height: 30px;ÐÐform-group-sm textarea.form-control,Ðform-group-sm
select[multiple].form-control {Ð height: auto;ÐÐform-group-sm .form-control-
static {Ð height: 30px;Ð min-height: 32px;Ð padding: 6px 10px;Ð font-size:
12px;Ð line-height: 1.5;ÐÐinput-lg {Ð height: 46px;Ð padding: 10px 16px;Ð
font-size: 18px;Ð line-height: 1.3333333;Ð border-radius: 6px;ÐÐselect.input-
lg {Ð height: 46px;Ð line-height: 46px;ÐÐtextarea.input-lg,Ð
select[multiple].input-lg {Ð height: auto;ÐÐform-group-lg .form-control {Ð
height: 46px;Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.3333333;Ð
  border-radius: 6px;ÐÐform-group-lg select.form-control {Ð height: 46px;Ð
line-height: 46px;ÐÐform-group-lg textarea.form-control,Ðform-group-lg
select[multiple].form-control {Ð height: auto;ÐÐform-group-lg .form-control-
static {Ð height: 46px;Ð min-height: 38px;Ð padding: 11px 16px;Ð font-size:
18px;Ð line-height: 1.3333333;ÐÐhas-feedback {Ð position: relative;ÐÐhas-
feedback .form-control {Ð padding-right: 42.5px;ÐÐform-control-feedback {Ð
position: absolute;Ð top: 0;Ð right: 0;Ð z-index: 2;Ð display: block;Ð width:
34px;Ð height: 34px;Ð line-height: 34px;Ð text-align: center;Ð pointer-
events: none;Ð

}Ðinput-lg + .form-control-feedback,Ðinput-group-lg + .form-control-feedback,Ðform-group-lg .form-control + .form-control-feedback {Ð width: 46px;Ð height: 46px;Ð line-height: 46px;ÐÐinput-sm + .form-control-feedback,Ðinput-group-sm + .form-control-feedback,Ðform-group-sm .form-control + .form-control-feedback {Ð width: 30px;Ð height: 30px;Ð line-height: 30px;ÐÐhas-success .help-block,Ðhas-success .control-label,Ðhas-success .radio,Ðhas-success .checkbox,Ðhas-success .radio-inline,Ðhas-success .checkbox-inline,Ðhas-success.radio label,Ðhas-success.checkbox label,Ð .has-success.radio-inline label,Ðhas-success.checkbox-inline label {Ð color: #3c763d;ÐÐhas-success .form-control {Ð border-color: #3c763d;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);ÐÐhas-success .form-control:focus {Ð border-color: #2b542c;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #67b168;Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #67b168;ÐÐhas-success .input-group-addon {Ð color: #3c763d;Ð background-color: #dff0d8;Ð border-color: #3c763d;ÐÐhas-success .form-control-feedback {Ð color: #3c763d;ÐÐhas-warning .help-block,Ðhas-warning .control-label,Ðhas-warning .radio,Ðhas-warning .checkbox,Ðhas-warning .radio-inline,Ðhas-warning .checkbox-inline,Ðhas-warning.radio label,Ðhas-warning.checkbox label,Ð .has-warning.radio-inline label,Ðhas-warning.checkbox-inline label {Ð color: #8a6d3b;ÐÐhas-warning .form-control {Ð border-color: #8a6d3b;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);ÐÐhas-warning .form-control:focus {Ð border-color: #66512c;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #c0a16b;Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #c0a16b;ÐÐhas-warning .input-group-addon {Ð color: #8a6d3b;Ð background-color: #fcf8e3;Ð border-color: #8a6d3b;ÐÐhas-warning .form-control-feedback {Ð color: #8a6d3b;ÐÐhas-error .help-block,Ðhas-error .control-label,Ðhas-error .radio,Ðhas-error .checkbox,Ðhas-error .radio-inline,Ðhas-error .checkbox-inline,Ðhas-error.radio label,Ðhas-error.checkbox label,Ðhas-error.radio-inline label,Ðhas-error.checkbox-inline label {Ð color: #a94442;ÐÐ .has-error .form-control {Ð border-color: #a94442;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075);ÐÐhas-error .form-control:focus {Ð border-color: #843534;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #ce8483;Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, .075), 0 0 6px #ce8483;ÐÐ .has-error .input-group-addon {Ð color: #a94442;Ð background-color: #f2dede;Ð border-color: #a94442;ÐÐhas-error .form-control-feedback {Ð color: #a94442;ÐÐ .has-feedback label ~ .form-control-feedback {Ð top: 25px;ÐÐhas-feedback label.sr-only ~ .form-control-feedback {Ð top: 0;ÐÐhelp-block {Ð display: block;Ð margin-top: 5px;Ð margin-bottom: 10px;Ð color: #737373;ÐÐ@media (min-width: 768px) {Ð .form-inline .form-group {Ð display: inline-block;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .form-inline .form-control {Ð display: inline-block;Ð width: auto;Ð vertical-align: middle;Ð }Ð .form-inline .form-control-static {Ð display: inline-block;Ð }Ð .form-inline .input-group {Ð display: inline-table;Ð vertical-align: middle;Ð }Ð .form-inline .input-group .input-group-addon,Ð .form-inline .input-group .input-group-btn,Ð .form-inline .input-group .form-control {Ð width: auto;Ð }Ð .form-inline .input-group > .form-control {Ð width: 100%;Ð }Ð .form-inline .control-label {Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .form-inline .radio,Ð .form-inline .checkbox {Ð display: inline-block;Ð margin-top: 0;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .form-inline .radio label,Ð .form-inline .checkbox label {Ð padding-left: 0;Ð }Ð .form-inline .radio input[type="radio"],Ð .form-inline .checkbox input[type="checkbox"] {Ð position: relative;Ð margin-left: 0;Ð }Ð .form-inline .has-feedback .form-control-feedback {Ð top: 0;Ð }ÐÐform-horizontal .radio,Ðform-horizontal .checkbox,Ðform-horizontal .radio-inline,Ð .form-horizontal .checkbox-inline {Ð padding-top: 7px;Ð margin-top: 0;Ð margin-bottom: 0;ÐÐform-horizontal .radio,Ðform-horizontal .checkbox {Ð min-height: 27px;Ð

}Ðform-horizontal .form-group {Ð margin-right: -15px;Ð margin-left: -15px;ÐÐ@media (min-width: 768px) {Ð .form-horizontal .control-label {Ð padding-top: 7px;Ð margin-bottom: 0;Ð text-align: right;Ð }ÐÐform-horizontal .has-feedback .form-control-feedback {Ð right: 15px;ÐÐ@media (min-width: 768px) {Ð .form-horizontal .form-group-lg .control-label {Ð padding-top: 11px;Ð font-size: 18px;Ð }ÐÐ@media (min-width: 768px) {Ð .form-horizontal .form-group-sm .control-label {Ð padding-top: 6px;Ð font-size: 12px;Ð }ÐÐbtn {Ð display: inline-block;Ð padding: 6px 12px;Ð margin-bottom: 0;Ð font-size: 14px;Ð font-weight: normal;Ð line-height: 1.42857143;Ð text-align: center;Ð white-space: nowrap;Ð vertical-align: middle;Ð -ms-touch-action: manipulation;Ð touch-action: manipulation;Ð cursor: pointer;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð user-select: none;Ð background-image: none;Ð border: 1px solid transparent;Ð border-radius: 4px;ÐÐbtn:focus,Ðbtn:active:focus,Ð .btn.active:focus,Ðbtn.focus,Ðbtn:active.focus,Ðbtn.active.focus {Ð outline: thin dotted;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐbtn:hover,Ðbtn:focus,Ðbtn.focus {Ð color: #333;Ð text-decoration: none;Ð }Ðbtn:active,Ðbtn.active {Ð background-image: none;Ð outline: 0;Ð -webkit-box-shadow: inset 0 3px 5px rgba(0, 0, 0, .125);Ð box-shadow: inset 0 3px 5px rgba(0, 0, 0, .125);ÐÐbtn.disabled,Ðbtn[disabled],Ðfieldset[disabled] .btn {Ð cursor: not-allowed;Ð filter: alpha(opacity=65);Ð -webkit-box-shadow: none;Ð box-shadow: none;Ð opacity: .65;ÐÐa.btn.disabled,Ðfieldset[disabled] a.btn {Ð pointer-events: none;ÐÐbtn-default {Ð color: #333;Ð background-color: #fff;Ð border-color: #ccc;ÐÐbtn-default:focus,Ðbtn-default.focus {Ð color: #333;Ð background-color: #e6e6e6;Ð border-color: #8c8c8c;ÐÐbtn-default:hover {Ð color: #333;Ð background-color: #e6e6e6;Ð border-color: #adadad;ÐÐbtn-default:active,Ðbtn-default.active,Ðopen > .dropdown-toggle.btn-default {Ð color: #333;Ð background-color: #e6e6e6;Ð border-color: #adadad;ÐÐ .btn-default:active:hover,Ðbtn-default.active:hover,Ðopen > .dropdown-toggle.btn-default:hover,Ðbtn-default:active:focus,Ðbtn-default.active:focus,Ð .open > .dropdown-toggle.btn-default:focus,Ðbtn-default:active.focus,Ðbtn-default.active.focus,Ðopen > .dropdown-toggle.btn-default.focus {Ð color: #333;Ð background-color: #d4d4d4;Ð border-color: #8c8c8c;ÐÐbtn-default:active,Ð .btn-default.active,Ðopen > .dropdown-toggle.btn-default {Ð background-image: none;ÐÐbtn-default.disabled:hover,Ðbtn-default[disabled]:hover,Ð fieldset[disabled] .btn-default:hover,Ðbtn-default.disabled:focus,Ðbtn-default[disabled]:focus,Ðfieldset[disabled] .btn-default:focus,Ðbtn-default.disabled.focus,Ðbtn-default[disabled].focus,Ðfieldset[disabled] .btn-default.focus {Ð background-color: #fff;Ð border-color: #ccc;ÐÐbtn-default .badge {Ð color: #fff;Ð background-color: #333;ÐÐbtn-primary {Ð color: #fff;Ð background-color: #337ab7;Ð border-color: #2e6da4;ÐÐbtn-primary:focus,Ðbtn-primary.focus {Ð color: #fff;Ð background-color: #286090;Ð border-color: #122b40;ÐÐbtn-primary:hover {Ð color: #fff;Ð background-color: #286090;Ð border-color: #204d74;ÐÐbtn-primary:active,Ðbtn-primary.active,Ð .open > .dropdown-toggle.btn-primary {Ð color: #fff;Ð background-color: #286090;Ð border-color: #204d74;ÐÐbtn-primary:active:hover,Ðbtn-primary.active:hover,Ðopen > .dropdown-toggle.btn-primary:hover,Ðbtn-primary:active:focus,Ðbtn-primary.active:focus,Ðopen > .dropdown-toggle.btn-primary:focus,Ðbtn-primary:active.focus,Ðbtn-primary.active.focus,Ðopen > .dropdown-toggle.btn-primary.focus {Ð color: #fff;Ð background-color: #204d74;Ð border-color: #122b40;ÐÐbtn-primary:active,Ðbtn-primary.active,Ð .open > .dropdown-toggle.btn-primary {Ð background-image: none;ÐÐbtn-primary.disabled:hover,Ðbtn-primary[disabled]:hover,Ðfieldset[disabled] .btn-primary:hover,Ðbtn-primary.disabled:focus,Ðbtn-primary[disabled]:focus,Ð fieldset[disabled] .btn-primary:focus,Ðbtn-primary.disabled.focus,Ðbtn-primary[disabled].focus,Ðfieldset[disabled] .btn-primary.focus {Ð background-color: #337ab7;Ð border-color: #2e6da4;ÐÐbtn-primary .badge {Ð color: #337ab7;Ð background-color: #fff;ÐÐbtn-success {Ð color: #fff;Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÐÐbtn-success:focus,Ðbtn-success.focus {Ð color: #fff;Ð

background-color: #449d44;Ð border-color: #255625;ÐÐbtn-
success:hover {Ð color: #fff;Ð background-color: #449d44;Ð border-color:
#398439;ÐÐbtn-success:active,Ðbtn-success.active,Ðopen > .dropdown-toggle.btn-
success {Ð color: #fff;Ð background-color: #449d44;Ð border-color: #398439;ÐÐ
.btn-success:active:hover,Ðbtn-success.active:hover,Ðopen > .dropdown-
toggle.btn-success:hover,Ðbtn-success:active:focus,Ðbtn-success.active:focus,Ð
.open > .dropdown-toggle.btn-success:focus,Ðbtn-success:active.focus,Ðbtn-
success.active.focus,Ðopen > .dropdown-toggle.btn-success.focus {Ð color:
#fff;Ð background-color: #398439;Ð border-color: #255625;ÐÐbtn-success:active,Ð
.btn-success.active,Ðopen > .dropdown-toggle.btn-success {Ð background-image:
none;ÐÐbtn-success.disabled:hover,Ðbtn-success[disabled]:hover,Ð
fieldset[disabled] .btn-success:hover,Ðbtn-success.disabled:focus,Ðbtn-
success[disabled]:focus,Ðfieldset[disabled] .btn-success:focus,Ðbtn-
success.disabled.focus,Ðbtn-success[disabled].focus,Ðfieldset[disabled] .btn-
success.focus {Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÐÐbtn-
success .badge {Ð color: #5cb85c;Ð background-color: #fff;ÐÐbtn-info {Ð
color: #fff;Ð background-color: #5bc0de;Ð border-color: #46b8da;ÐÐbtn-
info:focus,Ðbtn-info.focus {Ð color: #fff;Ð background-color: #31b0d5;Ð
border-color: #1b6d85;ÐÐbtn-info:hover {Ð color: #fff;Ð background-color:
#31b0d5;Ð border-color: #269abc;ÐÐbtn-info:active,Ðbtn-info.active,Ðopen
> .dropdown-toggle.btn-info {Ð color: #fff;Ð background-color: #31b0d5;Ð
border-color: #269abc;ÐÐbtn-info:active:hover,Ðbtn-info.active:hover,Ðopen
> .dropdown-toggle.btn-info:hover,Ðbtn-info:active:focus,Ðbtn-
info.active:focus,Ðopen > .dropdown-toggle.btn-info:focus,Ðbtn-
info:active.focus,Ðbtn-info.active.focus,Ðopen > .dropdown-toggle.btn-
info.focus {Ð color: #fff;Ð background-color: #269abc;Ð border-color: #1b6d85;Ð
}Ðbtn-info:active,Ðbtn-info.active,Ðopen > .dropdown-toggle.btn-info {Ð
background-image: none;ÐÐbtn-info.disabled:hover,Ðbtn-info[disabled]:hover,Ð
fieldset[disabled] .btn-info:hover,Ðbtn-info.disabled:focus,Ðbtn-
info[disabled]:focus,Ðfieldset[disabled] .btn-info:focus,Ðbtn-
info.disabled.focus,Ðbtn-info[disabled].focus,Ðfieldset[disabled] .btn-
info.focus {Ð background-color: #5bc0de;Ð border-color: #46b8da;ÐÐbtn-
info .badge {Ð color: #5bc0de;Ð background-color: #fff;ÐÐbtn-warning {Ð
color: #fff;Ð background-color: #f0ad4e;Ð border-color: #eea236;ÐÐbtn-
warning:focus,Ðbtn-warning.focus {Ð color: #fff;Ð background-color: #ec971f;Ð
border-color: #985f0d;ÐÐbtn-warning:hover {Ð color: #fff;Ð background-color:
#ec971f;Ð border-color: #d58512;ÐÐbtn-warning:active,Ðbtn-warning.active,Ð
.open > .dropdown-toggle.btn-warning {Ð color: #fff;Ð background-color:
#ec971f;Ð border-color: #d58512;ÐÐbtn-warning:active:hover,Ðbtn-
warning.active:hover,Ðopen > .dropdown-toggle.btn-warning:hover,Ðbtn-
warning:active:focus,Ðbtn-warning.active:focus,Ðopen > .dropdown-toggle.btn-
warning:focus,Ðbtn-warning:active.focus,Ðbtn-warning.active.focus,Ðopen
> .dropdown-toggle.btn-warning.focus {Ð color: #fff;Ð background-color:
#d58512;Ð border-color: #985f0d;ÐÐbtn-warning:active,Ðbtn-warning.active,Ð
.open > .dropdown-toggle.btn-warning {Ð background-image: none;ÐÐbtn-
warning.disabled:hover,Ðbtn-warning[disabled]:hover,Ðfieldset[disabled] .btn-
warning:hover,Ðbtn-warning.disabled:focus,Ðbtn-warning[disabled]:focus,Ð
fieldset[disabled] .btn-warning:focus,Ðbtn-warning.disabled.focus,Ðbtn-
warning[disabled].focus,Ðfieldset[disabled] .btn-warning.focus {Ð background-
color: #f0ad4e;Ð border-color: #eea236;ÐÐbtn-warning .badge {Ð color: #f0ad4e;Ð
background-color: #fff;ÐÐbtn-danger {Ð color: #fff;Ð background-color:
#d9534f;Ð border-color: #d43f3a;ÐÐbtn-danger:focus,Ðbtn-danger.focus {Ð
color: #fff;Ð background-color: #c9302c;Ð border-color: #761c19;ÐÐbtn-
danger:hover {Ð color: #fff;Ð background-color: #c9302c;Ð border-color:
#ac2925;ÐÐbtn-danger:active,Ðbtn-danger.active,Ðopen > .dropdown-toggle.btn-
danger {Ð color: #fff;Ð background-color: #c9302c;Ð border-color: #ac2925;ÐÐ
.btn-danger:active:hover,Ðbtn-danger.active:hover,Ðopen > .dropdown-
toggle.btn-danger:hover,Ðbtn-danger:active:focus,Ðbtn-danger.active:focus,Ð
.open > .dropdown-toggle.btn-danger:focus,Ðbtn-danger:active.focus,Ðbtn-
danger.active.focus,Ð

.open > .dropdown-toggle.btn-danger.focus {Ð color: #fff;Ð
  background-color: #ac2925;Ð border-color: #761c19;ÐÐbtn-danger:active,Ðbtn-
danger.active,Ðopen > .dropdown-toggle.btn-danger {Ð background-image: none;ÐÐ
.btn-danger.disabled:hover,Ðbtn-danger[disabled]:hover,Ð
fieldset[disabled] .btn-danger:hover,Ðbtn-danger.disabled:focus,Ðbtn-
danger[disabled]:focus,Ðfieldset[disabled] .btn-danger:focus,Ðbtn-
danger.disabled.focus,Ðbtn-danger[disabled].focus,Ðfieldset[disabled] .btn-
danger.focus {Ð background-color: #d9534f;Ð border-color: #d43f3a;ÐÐbtn-
danger .badge {Ð color: #d9534f;Ð background-color: #fff;ÐÐbtn-link {Ð font-
weight: normal;Ð color: #337ab7;Ð border-radius: 0;ÐÐbtn-link,Ðbtn-
link:active,Ðbtn-link.active,Ðbtn-link[disabled],Ðfieldset[disabled] .btn-link
{Ð background-color: transparent;Ð -webkit-box-shadow: none;Ð box-
shadow: none;ÐÐbtn-link,Ðbtn-link:hover,Ðbtn-link:focus,Ðbtn-link:active {Ð
border-color: transparent;ÐÐbtn-link:hover,Ðbtn-link:focus {Ð color: #23527c;Ð
  text-decoration: underline;Ð background-color: transparent;ÐÐbtn-
link[disabled]:hover,Ðfieldset[disabled] .btn-link:hover,Ðbtn-
link[disabled]:focus,Ðfieldset[disabled] .btn-link:focus {Ð color: #777;Ð text-
decoration: none;ÐÐbtn-lg,Ðbtn-group-lg > .btn {Ð padding: 10px 16px;Ð font-
size: 18px;Ð line-height: 1.3333333;Ð border-radius: 6px;ÐÐbtn-sm,Ðbtn-group-
sm > .btn {Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-
radius: 3px;ÐÐbtn-xs,Ðbtn-group-xs > .btn {Ð padding: 1px 5px;Ð font-size:
12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐbtn-block {Ð display: block;Ð
width: 100%;ÐÐbtn-block + .btn-block {Ð margin-top: 5px;ÐÐ
input[type="submit"].btn-block,Ðinput[type="reset"].btn-block,Ð
input[type="button"].btn-block {Ð width: 100%;ÐÐfade {Ð opacity: 0;Ð -webkit-
transition: opacity .15s linear;Ð -o-transition: opacity .15s linear;Ð
transition: opacity .15s linear;ÐÐfade.in {Ð opacity: 1;ÐÐcollapse {Ð
  display: none;ÐÐcollapse.in {Ð display: block;ÐÐtr.collapse.in {Ð display:
table-row;ÐÐtbody.collapse.in {Ð display: table-row-group;ÐÐcollapsing {Ð
position: relative;Ð height: 0;Ð overflow: hidden;Ð -webkit-transition-timing-
function: ease;Ð -o-transition-timing-function: ease;Ð
transition-timing-function: ease;Ð -webkit-transition-duration: .35s;Ð -
o-transition-duration: .35s;Ð transition-duration: .35s;Ð -webkit-
transition-property: height, visibility;Ð -o-transition-property:
height, visibility;Ð transition-property: height, visibility;ÐÐcaret {Ð
  display: inline-block;Ð width: 0;Ð height: 0;Ð margin-left: 2px;Ð vertical-
align: middle;Ð border-top: 4px dashed;Ð border-top: 4px solid \9;Ð border-
right: 4px solid transparent;Ð border-left: 4px solid transparent;ÐÐdropup,Ð
.dropdown {Ð position: relative;ÐÐdropdown-toggle:focus {Ð outline: 0;ÐÐ
.dropdown-menu {Ð position: absolute;Ð top: 100%;Ð left: 0;Ð z-index: 1000;Ð
display: none;Ð float: left;Ð min-width: 160px;Ð padding: 5px 0;Ð margin: 2px
0 0;Ð font-size: 14px;Ð text-align: left;Ð list-style: none;Ð background-
color: #fff;Ð -webkit-background-clip: padding-box;Ð background-clip:
padding-box;Ð border: 1px solid #ccc;Ð border: 1px solid rgba(0, 0, 0, .15);Ð
border-radius: 4px;Ð -webkit-box-shadow: 0 6px 12px rgba(0, 0, 0, .175);Ð
box-shadow: 0 6px 12px rgba(0, 0, 0, .175);ÐÐdropdown-menu.pull-
right {Ð right: 0;Ð left: auto;ÐÐdropdown-menu .divider {Ð height: 1px;Ð
margin: 9px 0;Ð overflow: hidden;Ð background-color: #e5e5e5;ÐÐdropdown-menu
> li > a {Ð display: block;Ð padding: 3px 20px;Ð clear: both;Ð font-weight:
normal;Ð line-height: 1.42857143;Ð color: #333;Ð white-space: nowrap;ÐÐ
.dropdown-menu > li > a:hover,Ðdropdown-menu > li > a:focus {Ð color: #262626;Ð
  text-decoration: none;Ð background-color: #f5f5f5;ÐÐdropdown-menu > .active
> a,Ðdropdown-menu > .active > a:hover,Ðdropdown-menu > .active > a:focus {Ð
color: #fff;Ð text-decoration: none;Ð background-color: #337ab7;Ð outline: 0;ÐÐ
.dropdown-menu > .disabled > a,Ðdropdown-menu > .disabled > a:hover,Ðdropdown-
menu > .disabled > a:focus {Ð color: #777;ÐÐdropdown-menu > .disabled >
a:hover,Ðdropdown-menu > .disabled > a:focus {Ð text-decoration: none;Ð
cursor: not-allowed;Ð background-color: transparent;Ð background-image: none;Ð
  filter: progid:DXImageTransform.Microsoft.gradient(enabled = false);ÐÐopen
> .dropdown-menu {Ð

display: block;ÐÐopen > a {Ð outline: 0;ÐÐdropdown-menu-right {Ð right: 0;Ð left: auto;ÐÐdropdown-menu-left {Ð right: auto;Ð left: 0;ÐÐ .dropdown-header {Ð display: block;Ð padding: 3px 20px;Ð font-size: 12px;Ð line-height: 1.42857143;Ð color: #777;Ð white-space: nowrap;ÐÐdropdown-backdrop {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 990;ÐÐpull-right > .dropdown-menu {Ð right: 0;Ð left: auto;ÐÐ .dropup .caret,Ðnavbar-fixed-bottom .dropdown .caret {Ð content: "";Ð border-top: 0;Ð border-bottom: 4px dashed;Ð border-bottom: 4px solid \9;ÐÐ .dropup .dropdown-menu,Ðnavbar-fixed-bottom .dropdown .dropdown-menu {Ð top: auto;Ð bottom: 100%;Ð margin-bottom: 2px;ÐÐ@media (min-width: 768px) {Ð .navbar-right .dropdown-menu {Ð right: 0;Ð left: auto;Ð }Ð .navbar-right .dropdown-menu-left {Ð right: auto;Ð left: 0;Ð }ÐÐbtn-group,Ðbtn-group-vertical {Ð position: relative;Ð display: inline-block;Ð vertical-align: middle;ÐÐbtn-group > .btn,Ðbtn-group-vertical > .btn {Ð position: relative;Ð float: left;ÐÐbtn-group > .btn:hover,Ðbtn-group-vertical > .btn:hover,Ðbtn-group > .btn:focus,Ðbtn-group-vertical > .btn:focus,Ðbtn-group > .btn:active,Ðbtn-group-vertical > .btn:active,Ðbtn-group > .btn.active,Ðbtn-group-vertical > .btn.active {Ð z-index: 2;ÐÐbtn-group .btn + .btn,Ðbtn-group .btn + .btn-group,Ðbtn-group .btn-group + .btn,Ð .btn-group .btn-group + .btn-group {Ð margin-left: -1px;ÐÐbtn-toolbar {Ð margin-left: -5px;ÐÐbtn-toolbar .btn,Ðbtn-toolbar .btn-group,Ðbtn-toolbar .input-group {Ð float: left;ÐÐbtn-toolbar > .btn,Ðbtn-toolbar > .btn-group,Ðbtn-toolbar > .input-group {Ð margin-left: 5px;ÐÐbtn-group > .btn:not(:first-child):not(:last-child):not(.dropdown-toggle) {Ð border-radius: 0;ÐÐbtn-group > .btn:first-child {Ð margin-left: 0;ÐÐbtn-group > .btn:first-child:not(:last-child):not(.dropdown-toggle) {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÐÐbtn-group > .btn:last-child:not(:first-child),Ðbtn-group > .dropdown-toggle:not(:first-child) {Ð border-top-left-radius: 0;Ð border-bottom-left-radius: 0;ÐÐbtn-group > .btn-group {Ð float: left;ÐÐbtn-group > .btn-group:not(:first-child):not(:last-child) > .btn {Ð border-radius: 0;ÐÐbtn-group > .btn-group:first-child:not(:last-child) > .btn:last-child,Ðbtn-group > .btn-group:first-child:not(:last-child) > .dropdown-toggle {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÐÐbtn-group > .btn-group:last-child:not(:first-child) > .btn:first-child {Ð border-top-left-radius: 0;Ð border-bottom-left-radius: 0;ÐÐbtn-group .dropdown-toggle:active,Ðbtn-group.open .dropdown-toggle {Ð outline: 0;ÐÐbtn-group > .btn + .dropdown-toggle {Ð padding-right: 8px;Ð padding-left: 8px;ÐÐbtn-group > .btn-lg + .dropdown-toggle {Ð padding-right: 12px;Ð padding-left: 12px;ÐÐbtn-group.open .dropdown-toggle {Ð -webkit-box-shadow: inset 0 3px 5px rgba(0, 0, 0, .125);Ð box-shadow: inset 0 3px 5px rgba(0, 0, 0, .125);ÐÐbtn-group.open .dropdown-toggle.btn-link {Ð -webkit-box-shadow: none;Ð box-shadow: none;ÐÐbtn .caret {Ð margin-left: 0;ÐÐbtn-lg .caret {Ð border-width: 5px 5px 0;Ð border-bottom-width: 0;ÐÐ .dropup .btn-lg .caret {Ð border-width: 0 5px 5px;ÐÐbtn-group-vertical > .btn,Ð .btn-group-vertical > .btn-group,Ðbtn-group-vertical > .btn-group > .btn {Ð display: block;Ð float: none;Ð width: 100%;Ð max-width: 100%;ÐÐbtn-group-vertical > .btn-group > .btn {Ð float: none;ÐÐbtn-group-vertical > .btn + .btn,Ðbtn-group-vertical > .btn + .btn-group,Ðbtn-group-vertical > .btn-group + .btn,Ðbtn-group-vertical > .btn-group + .btn-group {Ð margin-top: -1px;Ð margin-left: 0;ÐÐbtn-group-vertical > .btn:not(:first-child):not(:last-child) {Ð border-radius: 0;ÐÐbtn-group-vertical > .btn:first-child:not(:last-child) {Ð border-top-left-radius: 4px;Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;ÐÐbtn-group-vertical > .btn:last-child:not(:first-child) {Ð border-top-left-radius: 0;Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 4px;ÐÐbtn-group-vertical > .btn-group:not(:first-child):not(:last-child) > .btn {Ð border-radius: 0;ÐÐbtn-group-vertical > .btn-group:first-child:not(:last-child) > .btn:last-child,Ðbtn-group-vertical > .btn-group:first-child:not(:last-child) > .dropdown-toggle {Ð border-bottom-right-radius: 0;Ð

border-bottom-left-radius: 0;ÐÐbtn-group-vertical > .btn-group:last-child:not(:first-child) > .btn:first-child {Ð border-top-left-radius: 0;Ð border-top-right-radius: 0;ÐÐbtn-group-justified {Ð display: table;Ð width: 100%;Ð table-layout: fixed;Ð border-collapse: separate;ÐÐbtn-group-justified > .btn,Ðbtn-group-justified > .btn-group {Ð display: table-cell;Ð float: none;Ð width: 1%;ÐÐbtn-group-justified > .btn-group .btn {Ð width: 100%;ÐÐbtn-group-justified > .btn-group .dropdown-menu {Ð left: auto;ÐÐ[data-toggle="buttons"] > .btn input[type="radio"],Ð[data-toggle="buttons"] > .btn-group > .btn input[type="radio"],Ð[data-toggle="buttons"] > .btn input[type="checkbox"],Ð[data-toggle="buttons"] > .btn-group > .btn input[type="checkbox"] {Ð position: absolute;Ð clip: rect(0, 0, 0, 0);Ð pointer-events: none;ÐÐinput-group {Ð position: relative;Ð display: table;Ð border-collapse: separate;ÐÐinput-group[class*="col-"] {Ð float: none;Ð padding-right: 0;Ð padding-left: 0;ÐÐinput-group .form-control {Ð position: relative;Ð z-index: 2;Ð float: left;Ð width: 100%;Ð margin-bottom: 0;ÐÐinput-group .form-control:focus {Ð z-index: 3;ÐÐinput-group-lg > .form-control,Ð .input-group-lg > .input-group-addon,Ðinput-group-lg > .input-group-btn > .btn {Ð height: 46px;Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.3333333;Ð border-radius: 6px;ÐÐselect.input-group-lg > .form-control,Ð select.input-group-lg > .input-group-addon,Ðselect.input-group-lg > .input-group-btn > .btn {Ð height: 46px;Ð line-height: 46px;ÐÐtextarea.input-group-lg > .form-control,Ðtextarea.input-group-lg > .input-group-addon,Ðtextarea.input-group-lg > .input-group-btn > .btn,Ðselect[multiple].input-group-lg > .form-control,Ðselect[multiple].input-group-lg > .input-group-addon,Ð select[multiple].input-group-lg > .input-group-btn > .btn {Ð height: auto;ÐÐ .input-group-sm > .form-control,Ðinput-group-sm > .input-group-addon,Ðinput-group-sm > .input-group-btn > .btn {Ð height: 30px;Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐselect.input-group-sm > .form-control,Ðselect.input-group-sm > .input-group-addon,Ðselect.input-group-sm > .input-group-btn > .btn {Ð height: 30px;Ð line-height: 30px;ÐÐ textarea.input-group-sm > .form-control,Ðtextarea.input-group-sm > .input-group-addon,Ðtextarea.input-group-sm > .input-group-btn > .btn,Ð select[multiple].input-group-sm > .form-control,Ðselect[multiple].input-group-sm > .input-group-addon,Ðselect[multiple].input-group-sm > .input-group-btn > .btn {Ð height: auto;ÐÐinput-group-addon,Ðinput-group-btn,Ðinput-group .form-control {Ð display: table-cell;ÐÐinput-group-addon:not(:first-child):not(:last-child),Ðinput-group-btn:not(:first-child):not(:last-child),Ð .input-group .form-control:not(:first-child):not(:last-child) {Ð border-radius: 0;ÐÐinput-group-addon,Ðinput-group-btn {Ð width: 1%;Ð white-space: nowrap;Ð vertical-align: middle;ÐÐinput-group-addon {Ð padding: 6px 12px;Ð font-size: 14px;Ð font-weight: normal;Ð line-height: 1;Ð color: #555;Ð text-align: center;Ð background-color: #eee;Ð border: 1px solid #ccc;Ð border-radius: 4px;ÐÐinput-group-addon.input-sm {Ð padding: 5px 10px;Ð font-size: 12px;Ð border-radius: 3px;ÐÐinput-group-addon.input-lg {Ð padding: 10px 16px;Ð font-size: 18px;Ð border-radius: 6px;ÐÐinput-group-addon input[type="radio"],Ðinput-group-addon input[type="checkbox"] {Ð margin-top: 0;ÐÐinput-group .form-control:first-child,Ðinput-group-addon:first-child,Ð .input-group-btn:first-child > .btn,Ðinput-group-btn:first-child > .btn-group > .btn,Ðinput-group-btn:first-child > .dropdown-toggle,Ðinput-group-btn:last-child > .btn:not(:last-child):not(.dropdown-toggle),Ðinput-group-btn:last-child > .btn-group:not(:last-child) > .btn {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÐÐinput-group-addon:first-child {Ð border-right: 0;ÐÐinput-group .form-control:last-child,Ðinput-group-addon:last-child,Ð .input-group-btn:last-child > .btn,Ðinput-group-btn:last-child > .btn-group > .btn,Ðinput-group-btn:last-child > .dropdown-toggle,Ðinput-group-btn:first-child > .btn:not(:first-child),Ðinput-group-btn:first-child > .btn-group:not(:first-child) > .btn {Ð border-top-left-radius: 0;Ð border-bottom-left-radius: 0;ÐÐinput-group-addon:last-child {Ð border-left: 0;ÐÐinput-group-btn {Ð position: relative;Ð font-size: 0;Ð white-space: nowrap;ÐÐinput-group-btn > .btn {Ð

position: relative;ÐÐinput-group-btn > .btn + .btn {Ð margin-
left: -1px;ÐÐinput-group-btn > .btn:hover,Ðinput-group-btn > .btn:focus,Ð
.input-group-btn > .btn:active {Ð z-index: 2;ÐÐinput-group-btn:first-child
> .btn,Ðinput-group-btn:first-child > .btn-group {Ð margin-right: -1px;ÐÐ
.input-group-btn:last-child > .btn,Ðinput-group-btn:last-child > .btn-group {Ð
z-index: 2;Ð margin-left: -1px;ÐÐnav {Ð padding-left: 0;Ð margin-bottom: 0;Ð
list-style: none;ÐÐnav > li {Ð position: relative;Ð display: block;ÐÐnav >
li > a {Ð position: relative;Ð display: block;Ð padding: 10px 15px;ÐÐnav > li
> a:hover,Ðnav > li > a:focus {Ð text-decoration: none;Ð background-color:
#eee;ÐÐnav > li.disabled > a {Ð color: #777;ÐÐnav > li.disabled > a:hover,Ð
.nav > li.disabled > a:focus {Ð color: #777;Ð text-decoration: none;Ð cursor:
not-allowed;Ð background-color: transparent;ÐÐnav .open > a,Ðnav .open >
a:hover,Ðnav .open > a:focus {Ð background-color: #eee;Ð border-color:
#337ab7;ÐÐnav .nav-divider {Ð height: 1px;Ð margin: 9px 0;Ð overflow: hidden;Ð
background-color: #e5e5e5;ÐÐnav > li > a > img {Ð max-width: none;ÐÐnav-
tabs {Ð border-bottom: 1px solid #ddd;ÐÐnav-tabs > li {Ð float: left;Ð margin-
bottom: -1px;ÐÐnav-tabs > li > a {Ð margin-right: 2px;Ð line-height:
1.42857143;Ð border: 1px solid transparent;Ð border-radius: 4px 4px 0 0;ÐÐnav-
tabs > li > a:hover {Ð border-color: #eee #eee #ddd;ÐÐnav-tabs > li.active >
a,Ðnav-tabs > li.active > a:hover,Ðnav-tabs > li.active > a:focus {Ð color:
#555;Ð cursor: default;Ð background-color: #fff;Ð border: 1px solid #ddd;Ð
border-bottom-color: transparent;ÐÐnav-tabs.nav-justified {Ð width: 100%;Ð
border-bottom: 0;ÐÐnav-tabs.nav-justified > li {Ð float: none;ÐÐnav-tabs.nav-
justified > li > a {Ð margin-bottom: 5px;Ð text-align: center;ÐÐnav-tabs.nav-
justified > .dropdown .dropdown-menu {Ð top: auto;Ð left: auto;ÐÐ@media (min-
width: 768px) {Ð .nav-tabs.nav-justified > li {Ð display: table-cell;Ð
width: 1%;Ð }Ð .nav-tabs.nav-justified > li > a {Ð margin-bottom: 0;Ð }ÐÐ
.nav-tabs.nav-justified > li > a {Ð margin-right: 0;Ð border-radius: 4px;ÐÐ
.nav-tabs.nav-justified > .active > a,Ðnav-tabs.nav-justified > .active >
a:hover,Ðnav-tabs.nav-justified > .active > a:focus {Ð border: 1px solid #ddd;Ð
}Ð@media (min-width: 768px) {Ð .nav-tabs.nav-justified > li > a {Ð border-
bottom: 1px solid #ddd;Ð border-radius: 4px 4px 0 0;Ð }Ð .nav-tabs.nav-
justified > .active > a,Ð .nav-tabs.nav-justified > .active > a:hover,Ð .nav-
tabs.nav-justified > .active > a:focus {Ð border-bottom-color: #fff;Ð }ÐÐ
.nav-pills > li {Ð float: left;ÐÐnav-pills > li > a {Ð border-radius: 4px;ÐÐ
.nav-pills > li + li {Ð margin-left: 2px;ÐÐnav-pills > li.active > a,Ðnav-
pills > li.active > a:hover,Ðnav-pills > li.active > a:focus {Ð color: #fff;Ð
background-color: #337ab7;ÐÐnav-stacked > li {Ð float: none;ÐÐnav-stacked >
li + li {Ð margin-top: 2px;Ð margin-left: 0;ÐÐnav-justified {Ð width: 100%;ÐÐ
.nav-justified > li {Ð float: none;ÐÐnav-justified > li > a {Ð margin-bottom:
5px;Ð text-align: center;ÐÐnav-justified > .dropdown .dropdown-menu {Ð top:
auto;Ð left: auto;ÐÐ@media (min-width: 768px) {Ð .nav-justified > li {Ð
display: table-cell;Ð width: 1%;Ð }Ð .nav-justified > li > a {Ð margin-
bottom: 0;Ð }ÐÐnav-tabs-justified {Ð border-bottom: 0;ÐÐnav-tabs-justified >
li > a {Ð margin-right: 0;Ð border-radius: 4px;ÐÐnav-tabs-justified > .active
> a,Ðnav-tabs-justified > .active > a:hover,Ðnav-tabs-justified > .active >
a:focus {Ð border: 1px solid #ddd;ÐÐ@media (min-width: 768px) {Ð .nav-tabs-
justified > li > a {Ð border-bottom: 1px solid #ddd;Ð border-radius: 4px
4px 0 0;Ð }Ð .nav-tabs-justified > .active > a,Ð .nav-tabs-justified
> .active > a:hover,Ð .nav-tabs-justified > .active > a:focus {Ð border-
bottom-color: #fff;Ð }ÐÐtab-content > .tab-pane {Ð display: none;ÐÐtab-
content > .active {Ð display: block;ÐÐnav-tabs .dropdown-menu {Ð margin-top:
-1px;Ð border-top-left-radius: 0;Ð border-top-right-radius: 0;ÐÐnavbar {Ð
position: relative;Ð min-height: 50px;Ð margin-bottom: 20px;Ð border: 1px
solid transparent;ÐÐ@media (min-width: 768px) {Ð .navbar {Ð border-radius:
4px;Ð }ÐÐ@media (min-width: 768px) {Ð .navbar-header {Ð float: left;Ð }ÐÐ
.navbar-collapse {Ð padding-right: 15px;Ð padding-left: 15px;Ð overflow-x:
visible;Ð -webkit-overflow-scrolling: touch;Ð border-top: 1px solid
transparent;Ð -webkit-box-shadow: inset 0 1px 0 rgba(255, 255, 255, .1);Ð
box-shadow: inset 0 1px 0 rgba(255, 255, 255, .1);Ð

}Ðnavbar-
collapse.in {Ð overflow-y: auto;ÐÐ@media (min-width: 768px) {Ð .navbar-
collapse {Ð width: auto;Ð border-top: 0;Ð -webkit-box-shadow: none;Ð
box-shadow: none;Ð }Ð .navbar-collapse.collapse {Ð display:
block !important;Ð height: auto !important;Ð padding-bottom: 0;Ð
overflow: visible !important;Ð }Ð .navbar-collapse.in {Ð overflow-y:
visible;Ð }Ð .navbar-fixed-top .navbar-collapse,Ð .navbar-static-top .navbar-
collapse,Ð .navbar-fixed-bottom .navbar-collapse {Ð padding-right: 0;Ð
padding-left: 0;Ð }ÐÐ.navbar-fixed-top .navbar-collapse,Ðnavbar-fixed-
bottom .navbar-collapse {Ð max-height: 340px;ÐÐ@media (max-device-width:
480px) and (orientation: landscape) {Ð .navbar-fixed-top .navbar-collapse,Ð
.navbar-fixed-bottom .navbar-collapse {Ð max-height: 200px;Ð }ÐÐcontainer
> .navbar-header,Ðcontainer-fluid > .navbar-header,Ðcontainer > .navbar-
collapse,Ðcontainer-fluid > .navbar-collapse {Ð margin-right: -15px;Ð margin-
left: -15px;ÐÐ@media (min-width: 768px) {Ð .container > .navbar-header,Ð
.container-fluid > .navbar-header,Ð .container > .navbar-collapse,Ð
.container-fluid > .navbar-collapse {Ð margin-right: 0;Ð margin-left: 0;Ð
}ÐÐnavbar-static-top {Ð z-index: 1000;Ð border-width: 0 0 1px;ÐÐ@media (min-
width: 768px) {Ð .navbar-static-top {Ð border-radius: 0;Ð }ÐÐnavbar-fixed-
top,Ðnavbar-fixed-bottom {Ð position: fixed;Ð right: 0;Ð left: 0;Ð z-index:
1030;ÐÐ@media (min-width: 768px) {Ð .navbar-fixed-top,Ð .navbar-fixed-bottom {Ð
border-radius: 0;Ð }ÐÐnavbar-fixed-top {Ð top: 0;Ð border-width: 0 0 1px;ÐÐ
.navbar-fixed-bottom {Ð bottom: 0;Ð margin-bottom: 0;Ð border-width: 1px 0 0;ÐÐ
.navbar-brand {Ð float: left;Ð height: 50px;Ð padding: 15px 15px;Ð font-size:
18px;Ð line-height: 20px;ÐÐnavbar-brand:hover,Ðnavbar-brand:focus {Ð text-
decoration: none;ÐÐnavbar-brand > img {Ð display: block;ÐÐ@media (min-width:
768px) {Ð .navbar > .container .navbar-brand,Ð .navbar > .container-
fluid .navbar-brand {Ð margin-left: -15px;Ð }ÐÐnavbar-toggle {Ð position:
relative;Ð float: right;Ð padding: 9px 10px;Ð margin-top: 8px;Ð margin-right:
15px;Ð margin-bottom: 8px;Ð background-color: transparent;Ð background-image:
none;Ð border: 1px solid transparent;Ð border-radius: 4px;ÐÐnavbar-
toggle:focus {Ð outline: 0;ÐÐnavbar-toggle .icon-bar {Ð display: block;Ð
width: 22px;Ð height: 2px;Ð border-radius: 1px;ÐÐnavbar-toggle .icon-bar
+ .icon-bar {Ð margin-top: 4px;ÐÐ@media (min-width: 768px) {Ð .navbar-toggle {Ð
display: none;Ð }ÐÐnavbar-nav {Ð margin: 7.5px -15px;ÐÐnavbar-nav > li >
a {Ð padding-top: 10px;Ð padding-bottom: 10px;Ð line-height: 20px;ÐÐ@media
(max-width: 767px) {Ð .navbar-nav .open .dropdown-menu {Ð position: static;Ð
float: none;Ð width: auto;Ð margin-top: 0;Ð background-color:
transparent;Ð border: 0;Ð -webkit-box-shadow: none;Ð box-
shadow: none;Ð }Ð .navbar-nav .open .dropdown-menu > li > a,Ð .navbar-
nav .open .dropdown-menu .dropdown-header {Ð padding: 5px 15px 5px 25px;Ð }Ð
.navbar-nav .open .dropdown-menu > li > a {Ð line-height: 20px;Ð }Ð
.navbar-nav .open .dropdown-menu > li > a:hover,Ð .navbar-
nav .open .dropdown-menu > li > a:focus {Ð background-image: none;Ð }ÐÐ
@media (min-width: 768px) {Ð .navbar-nav {Ð float: left;Ð margin: 0;Ð }Ð
.navbar-nav > li {Ð float: left;Ð }Ð .navbar-nav > li > a {Ð padding-
top: 15px;Ð padding-bottom: 15px;Ð }ÐÐnavbar-form {Ð padding: 10px 15px;Ð
margin-top: 8px;Ð margin-right: -15px;Ð margin-bottom: 8px;Ð margin-left:
-15px;Ð border-top: 1px solid transparent;Ð border-bottom: 1px solid
transparent;Ð -webkit-box-shadow: inset 0 1px 0 rgba(255, 255, 255, .1), 0
1px 0 rgba(255, 255, 255, .1);Ð box-shadow: inset 0 1px 0 rgba(255,
255, 255, .1), 0 1px 0 rgba(255, 255, 255, .1);ÐÐ@media (min-width: 768px) {Ð
.navbar-form .form-group {Ð display: inline-block;Ð margin-bottom: 0;Ð
vertical-align: middle;Ð }Ð .navbar-form .form-control {Ð display:
inline-block;Ð width: auto;Ð vertical-align: middle;Ð }Ð .navbar-
form .form-control-static {Ð display: inline-block;Ð }Ð .navbar-form .input-
group {Ð display: inline-table;Ð vertical-align: middle;Ð }Ð .navbar-
form .input-group .input-group-addon,Ð .navbar-form .input-group .input-group-
btn,Ð .navbar-form .input-group .form-control {Ð width: auto;Ð }Ð .navbar-
form .input-group > .form-control {Ð

width: 100%;Ð }Ð .navbar-form .control-
label {Ð   margin-bottom: 0;Ð   vertical-align: middle;Ð }Ð .navbar-
form .radio,Ð .navbar-form .checkbox {Ð   display: inline-block;Ð   margin-
top: 0;Ð   margin-bottom: 0;Ð   vertical-align: middle;Ð }Ð .navbar-
form .radio label,Ð .navbar-form .checkbox label {Ð   padding-left: 0;Ð }Ð
  .navbar-form .radio input[type="radio"],Ð .navbar-form .checkbox
input[type="checkbox"] {Ð   position: relative;Ð   margin-left: 0;Ð }Ð
  .navbar-form .has-feedback .form-control-feedback {Ð   top: 0;Ð }ÐÐ@media
(max-width: 767px) {Ð .navbar-form .form-group {Ð   margin-bottom: 5px;Ð }Ð
  .navbar-form .form-group:last-child {Ð   margin-bottom: 0;Ð }ÐÐ@media (min-
width: 768px) {Ð .navbar-form {Ð   width: auto;Ð   padding-top: 0;Ð   padding-
bottom: 0;Ð   margin-right: 0;Ð   margin-left: 0;Ð   border: 0;Ð   -webkit-
box-shadow: none;Ð   box-shadow: none;Ð }ÐÐnavbar-nav > li
> .dropdown-menu {Ð margin-top: 0;Ð border-top-left-radius: 0;Ð border-top-
right-radius: 0;ÐÐnavbar-fixed-bottom .navbar-nav > li > .dropdown-menu {Ð
margin-bottom: 0;Ð border-top-left-radius: 4px;Ð border-top-right-radius: 4px;Ð
  border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;ÐÐnavbar-btn {Ð
  margin-top: 8px;Ð margin-bottom: 8px;ÐÐnavbar-btn.btn-sm {Ð margin-top:
10px;Ð margin-bottom: 10px;ÐÐnavbar-btn.btn-xs {Ð margin-top: 14px;Ð margin-
bottom: 14px;ÐÐnavbar-text {Ð margin-top: 15px;Ð margin-bottom: 15px;ÐÐ@media
(min-width: 768px) {Ð .navbar-text {Ð   float: left;Ð   margin-right: 15px;Ð
    margin-left: 15px;Ð }ÐÐ@media (min-width: 768px) {Ð .navbar-left {Ð
float: left !important;Ð }Ð .navbar-right {Ð   float: right !important;Ð
margin-right: -15px;Ð }Ð .navbar-right ~ .navbar-right {Ð   margin-right: 0;Ð
  }ÐÐnavbar-default {Ð background-color: #f8f8f8;Ð border-color: #e7e7e7;ÐÐ
.navbar-default .navbar-brand {Ð color: #777;ÐÐnavbar-default .navbar-
brand:hover,Ðnavbar-default .navbar-brand:focus {Ð color: #5e5e5e;Ð
background-color: transparent;ÐÐnavbar-default .navbar-text {Ð color: #777;ÐÐ
.navbar-default .navbar-nav > li > a {Ð color: #777;ÐÐnavbar-default .navbar-
nav > li > a:hover,Ðnavbar-default .navbar-nav > li > a:focus {Ð color: #333;Ð
  background-color: transparent;ÐÐnavbar-default .navbar-nav > .active > a,Ð
.navbar-default .navbar-nav > .active > a:hover,Ðnavbar-default .navbar-nav
> .active > a:focus {Ð color: #555;Ð background-color: #e7e7e7;ÐÐnavbar-
default .navbar-nav > .disabled > a,Ðnavbar-default .navbar-nav > .disabled >
a:hover,Ðnavbar-default .navbar-nav > .disabled > a:focus {Ð color: #ccc;Ð
background-color: transparent;ÐÐnavbar-default .navbar-toggle {Ð border-
color: #ddd;ÐÐnavbar-default .navbar-toggle:hover,Ðnavbar-default .navbar-
toggle:focus {Ð background-color: #ddd;ÐÐnavbar-default .navbar-toggle .icon-
bar {Ð background-color: #888;ÐÐnavbar-default .navbar-collapse,Ðnavbar-
default .navbar-form {Ð border-color: #e7e7e7;ÐÐnavbar-default .navbar-nav
> .open > a,Ðnavbar-default .navbar-nav > .open > a:hover,Ðnavbar-
default .navbar-nav > .open > a:focus {Ð color: #555;Ð background-color:
#e7e7e7;ÐÐ@media (max-width: 767px) {Ð .navbar-default .navbar-
nav .open .dropdown-menu > li > a {Ð   color: #777;Ð }Ð .navbar-
default .navbar-nav .open .dropdown-menu > li > a:hover,Ð .navbar-
default .navbar-nav .open .dropdown-menu > li > a:focus {Ð   color: #333;Ð
background-color: transparent;Ð }Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a,Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a:hover,Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a:focus {Ð   color: #555;Ð   background-
color: #e7e7e7;Ð }Ð .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a,Ð .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a:hover,Ð .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a:focus {Ð   color: #ccc;Ð   background-color: transparent;Ð }ÐÐ
.navbar-default .navbar-link {Ð color: #777;ÐÐnavbar-default .navbar-
link:hover {Ð color: #333;ÐÐnavbar-default .btn-link {Ð color: #777;ÐÐnavbar-
default .btn-link:hover,Ðnavbar-default .btn-link:focus {Ð color: #333;ÐÐ
.navbar-default .btn-link[disabled]:hover,Ðfieldset[disabled] .navbar-
default .btn-link:hover,Ðnavbar-default .btn-link[disabled]:focus,Ð
fieldset[disabled] .navbar-default .btn-link:focus {Ð

color: #ccc;ÐÐnavbar-
inverse {Ð background-color: #222;Ð border-color: #080808;ÐÐnavbar-
inverse .navbar-brand {Ð color: #9d9d9d;ÐÐnavbar-inverse .navbar-brand:hover,Ð
.navbar-inverse .navbar-brand:focus {Ð color: #fff;Ð background-color:
transparent;ÐÐnavbar-inverse .navbar-text {Ð color: #9d9d9d;ÐÐnavbar-
inverse .navbar-nav > li > a {Ð color: #9d9d9d;ÐÐnavbar-inverse .navbar-nav >
li > a:hover,Ðnavbar-inverse .navbar-nav > li > a:focus {Ð color: #fff;Ð
background-color: transparent;ÐÐnavbar-inverse .navbar-nav > .active > a,Ð
.navbar-inverse .navbar-nav > .active > a:hover,Ðnavbar-inverse .navbar-nav
> .active > a:focus {Ð color: #fff;Ð background-color: #080808;ÐÐnavbar-
inverse .navbar-nav > .disabled > a,Ðnavbar-inverse .navbar-nav > .disabled >
a:hover,Ðnavbar-inverse .navbar-nav > .disabled > a:focus {Ð color: #444;Ð
background-color: transparent;ÐÐnavbar-inverse .navbar-toggle {Ð border-
color: #333;ÐÐnavbar-inverse .navbar-toggle:hover,Ðnavbar-inverse .navbar-
toggle:focus {Ð background-color: #333;ÐÐnavbar-inverse .navbar-toggle .icon-
bar {Ð background-color: #fff;ÐÐnavbar-inverse .navbar-collapse,Ðnavbar-
inverse .navbar-form {Ð border-color: #101010;ÐÐnavbar-inverse .navbar-nav
> .open > a,Ðnavbar-inverse .navbar-nav > .open > a:hover,Ðnavbar-
inverse .navbar-nav > .open > a:focus {Ð color: #fff;Ð background-color:
#080808;ÐÐ@media (max-width: 767px) {Ð .navbar-inverse .navbar-
nav .open .dropdown-menu > .dropdown-header {Ð border-color: #080808;Ð }Ð
 .navbar-inverse .navbar-nav .open .dropdown-menu .divider {Ð background-
color: #080808;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu > li > a
{Ð color: #9d9d9d;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu >
li > a:hover,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > li >
a:focus {Ð color: #fff;Ð background-color: transparent;Ð }Ð .navbar-
inverse .navbar-nav .open .dropdown-menu > .active > a,Ð .navbar-
inverse .navbar-nav .open .dropdown-menu > .active > a:hover,Ð .navbar-
inverse .navbar-nav .open .dropdown-menu > .active > a:focus {Ð color: #fff;Ð
 background-color: #080808;Ð }Ð .navbar-inverse .navbar-
nav .open .dropdown-menu > .disabled > a,Ð .navbar-inverse .navbar-
nav .open .dropdown-menu > .disabled > a:hover,Ð .navbar-inverse .navbar-
nav .open .dropdown-menu > .disabled > a:focus {Ð color: #444;Ð
background-color: transparent;Ð }ÐÐnavbar-inverse .navbar-link {Ð color:
#9d9d9d;ÐÐnavbar-inverse .navbar-link:hover {Ð color: #fff;ÐÐnavbar-
inverse .btn-link {Ð color: #9d9d9d;ÐÐnavbar-inverse .btn-link:hover,Ðnavbar-
inverse .btn-link:focus {Ð color: #fff;ÐÐnavbar-inverse .btn-
link[disabled]:hover,Ðfieldset[disabled] .navbar-inverse .btn-link:hover,Ð
.navbar-inverse .btn-link[disabled]:focus,Ðfieldset[disabled] .navbar-
inverse .btn-link:focus {Ð color: #444;ÐÐbreadcrumb {Ð padding: 8px 15px;Ð
margin-bottom: 20px;Ð list-style: none;Ð background-color: #f5f5f5;Ð border-
radius: 4px;ÐÐbreadcrumb > li {Ð display: inline-block;ÐÐbreadcrumb > li +
li:before {Ð padding: 0 5px;Ð color: #ccc;Ð content: "/\00a0";ÐÐbreadcrumb
> .active {Ð color: #777;ÐÐpagination {Ð display: inline-block;Ð padding-
left: 0;Ð margin: 20px 0;Ð border-radius: 4px;ÐÐpagination > li {Ð display:
inline;ÐÐpagination > li > a,Ðpagination > li > span {Ð position: relative;Ð
float: left;Ð padding: 6px 12px;Ð margin-left: -1px;Ð line-height: 1.42857143;Ð
 color: #337ab7;Ð text-decoration: none;Ð background-color: #fff;Ð border:
1px solid #ddd;ÐÐpagination > li:first-child > a,Ðpagination > li:first-child
> span {Ð margin-left: 0;Ð border-top-left-radius: 4px;Ð border-bottom-left-
radius: 4px;ÐÐpagination > li:last-child > a,Ðpagination > li:last-child >
span {Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 4px;ÐÐ
.pagination > li > a:hover,Ðpagination > li > span:hover,Ðpagination > li >
a:focus,Ðpagination > li > span:focus {Ð z-index: 2;Ð color: #23527c;Ð
background-color: #eee;Ð border-color: #ddd;ÐÐpagination > .active > a,Ð
.pagination > .active > span,Ðpagination > .active > a:hover,Ðpagination
> .active > span:hover,Ðpagination > .active > a:focus,Ðpagination > .active
> span:focus {Ð z-index: 3;Ð color: #fff;Ð cursor: default;Ð background-
color: #337ab7;Ð border-color: #337ab7;ÐÐpagination > .disabled > span,Ð
.pagination > .disabled > span:hover,Ð

.pagination > .disabled > span:focus,Ð
.pagination > .disabled > a,Ðpagination > .disabled > a:hover,Ðpagination
> .disabled > a:focus {Ð color: #777;Ð cursor: not-allowed;Ð background-
color: #fff;Ð border-color: #ddd;ÐÐpagination-lg > li > a,Ðpagination-lg > li
> span {Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.3333333;ÐÐ
.pagination-lg > li:first-child > a,Ðpagination-lg > li:first-child > span {Ð
border-top-left-radius: 6px;Ð border-bottom-left-radius: 6px;ÐÐpagination-lg
> li:last-child > a,Ðpagination-lg > li:last-child > span {Ð border-top-right-
radius: 6px;Ð border-bottom-right-radius: 6px;ÐÐpagination-sm > li > a,Ð
.pagination-sm > li > span {Ð padding: 5px 10px;Ð font-size: 12px;Ð line-
height: 1.5;ÐÐpagination-sm > li:first-child > a,Ðpagination-sm > li:first-
child > span {Ð border-top-left-radius: 3px;Ð border-bottom-left-radius: 3px;ÐÐ
.pagination-sm > li:last-child > a,Ðpagination-sm > li:last-child > span {Ð
border-top-right-radius: 3px;Ð border-bottom-right-radius: 3px;ÐÐpager {Ð
padding-left: 0;Ð margin: 20px 0;Ð text-align: center;Ð list-style: none;ÐÐ
.pager li {Ð display: inline;ÐÐpager li > a,Ðpager li > span {Ð display:
inline-block;Ð padding: 5px 14px;Ð background-color: #fff;Ð border: 1px solid
#ddd;Ð border-radius: 15px;ÐÐpager li > a:hover,Ðpager li > a:focus {Ð text-
decoration: none;Ð background-color: #eee;ÐÐpager .next > a,Ðpager .next >
span {Ð float: right;ÐÐpager .previous > a,Ðpager .previous > span {Ð float:
left;ÐÐpager .disabled > a,Ðpager .disabled > a:hover,Ðpager .disabled >
a:focus,Ðpager .disabled > span {Ð color: #777;Ð cursor: not-allowed;Ð
background-color: #fff;ÐÐlabel {Ð display: inline;Ð padding: .2em .6em .3em;Ð
font-size: 75%;Ð font-weight: bold;Ð line-height: 1;Ð color: #fff;Ð text-
align: center;Ð white-space: nowrap;Ð vertical-align: baseline;Ð border-
radius: .25em;ÐÐa.label:hover,Ða.label:focus {Ð color: #fff;Ð text-decoration:
none;Ð cursor: pointer;ÐÐlabel:empty {Ð display: none;ÐÐbtn .label {Ð
position: relative;Ð top: -1px;ÐÐlabel-default {Ð background-color: #777;ÐÐ
.label-default[href]:hover,Ðlabel-default[href]:focus {Ð background-color:
#5e5e5e;ÐÐlabel-primary {Ð background-color: #337ab7;ÐÐlabel-
primary[href]:hover,Ðlabel-primary[href]:focus {Ð background-color: #286090;ÐÐ
.label-success {Ð background-color: #5cb85c;ÐÐlabel-success[href]:hover,Ð
.label-success[href]:focus {Ð background-color: #449d44;ÐÐlabel-info {Ð
background-color: #5bc0de;ÐÐlabel-info[href]:hover,Ðlabel-info[href]:focus {Ð
background-color: #31b0d5;ÐÐlabel-warning {Ð background-color: #f0ad4e;ÐÐ
.label-warning[href]:hover,Ðlabel-warning[href]:focus {Ð background-color:
#ec971f;ÐÐlabel-danger {Ð background-color: #d9534f;ÐÐlabel-
danger[href]:hover,Ðlabel-danger[href]:focus {Ð background-color: #c9302c;ÐÐ
.badge {Ð display: inline-block;Ð min-width: 10px;Ð padding: 3px 7px;Ð font-
size: 12px;Ð font-weight: bold;Ð line-height: 1;Ð color: #fff;Ð text-align:
center;Ð white-space: nowrap;Ð vertical-align: middle;Ð background-color:
#777;Ð border-radius: 10px;ÐÐbadge:empty {Ð display: none;ÐÐbtn .badge {Ð
position: relative;Ð top: -1px;ÐÐbtn-xs .badge,Ðbtn-group-xs > .btn .badge {Ð
top: 0;Ð padding: 1px 5px;ÐÐa.badge:hover,Ða.badge:focus {Ð color: #fff;Ð text-
decoration: none;Ð cursor: pointer;ÐÐlist-group-item.active > .badge,Ðnav-
pills > .active > a > .badge {Ð color: #337ab7;Ð background-color: #fff;ÐÐ
.list-group-item > .badge {Ð float: right;ÐÐlist-group-item > .badge + .badge
{Ð margin-right: 5px;ÐÐnav-pills > li > a > .badge {Ð margin-left: 3px;ÐÐ
.jumbotron {Ð padding-top: 30px;Ð padding-bottom: 30px;Ð margin-bottom: 30px;Ð
color: inherit;Ð background-color: #eee;ÐÐjumbotron h1,Ðjumbotron .h1 {Ð
color: inherit;ÐÐjumbotron p {Ð margin-bottom: 15px;Ð font-size: 21px;Ð font-
weight: 200;ÐÐjumbotron > hr {Ð border-top-color: #d5d5d5;ÐÐ
.container .jumbotron,Ðcontainer-fluid .jumbotron {Ð padding-right: 15px;Ð
padding-left: 15px;Ð border-radius: 6px;ÐÐjumbotron .container {Ð max-width:
100%;ÐÐ@media screen and (min-width: 768px) {Ð .jumbotron {Ð padding-top:
48px;Ð padding-bottom: 48px;Ð }Ð .container .jumbotron,Ð .container-
fluid .jumbotron {Ð padding-right: 60px;Ð padding-left: 60px;Ð }Ð
.jumbotron h1,Ð .jumbotron .h1 {Ð font-size: 63px;Ð }ÐÐthumbnail {Ð
display: block;Ð padding: 4px;Ð margin-bottom: 20px;Ð line-height: 1.42857143;Ð
background-color: #fff;Ð

```
                            border: 1px solid #ddd;Ð border-radius: 4px;Ð -
webkit-transition: border .2s ease-in-out;Ð      -o-transition: border .2s
ease-in-out;Ð         transition: border .2s ease-in-out;ÐÐthumbnail > img,Ð
.thumbnail a > img {Ð margin-right: auto;Ð margin-left: auto;ÐÐ
a.thumbnail:hover,Ð a.thumbnail:focus,Ð a.thumbnail.active {Ð border-color:
#337ab7;ÐÐthumbnail .caption {Ð padding: 9px;Ð color: #333;ÐÐalert {Ð
padding: 15px;Ð margin-bottom: 20px;Ð border: 1px solid transparent;Ð border-
radius: 4px;ÐÐalert h4 {Ð margin-top: 0;Ð color: inherit;ÐÐalert .alert-link {Ð
  font-weight: bold;ÐÐalert > p,Ð alert > ul {Ð margin-bottom: 0;ÐÐalert > p +
p {Ð margin-top: 5px;ÐÐalert-dismissable,Ð alert-dismissible {Ð padding-right:
35px;ÐÐalert-dismissable .close,Ð alert-dismissible .close {Ð position:
relative;Ð top: -2px;Ð right: -21px;Ð color: inherit;ÐÐalert-success {Ð
color: #3c763d;Ð background-color: #dff0d8;Ð border-color: #d6e9c6;ÐÐalert-
success hr {Ð border-top-color: #c9e2b3;ÐÐalert-success .alert-link {Ð color:
#2b542c;ÐÐalert-info {Ð color: #31708f;Ð background-color: #d9edf7;Ð border-
color: #bce8f1;ÐÐalert-info hr {Ð border-top-color: #a6e1ec;ÐÐalert-
info .alert-link {Ð color: #245269;ÐÐalert-warning {Ð color: #8a6d3b;Ð
background-color: #fcf8e3;Ð border-color: #faebcc;ÐÐalert-warning hr {Ð
border-top-color: #f7e1b5;ÐÐalert-warning .alert-link {Ð color: #66512c;ÐÐ
.alert-danger {Ð color: #a94442;Ð background-color: #f2dede;Ð border-color:
#ebccd1;ÐÐalert-danger hr {Ð border-top-color: #e4b9c0;ÐÐalert-danger .alert-
link {Ð color: #843534;ÐÐ@-webkit-keyframes progress-bar-stripes {Ð from {Ð
background-position: 40px 0;Ð }Ð to {Ð   background-position: 0 0;Ð }ÐÐ@-o-
keyframes progress-bar-stripes {Ð from {Ð   background-position: 40px 0;Ð }Ð
to {Ð   background-position: 0 0;Ð }ÐÐ@keyframes progress-bar-stripes {Ð from {Ð
    background-position: 40px 0;Ð }Ð to {Ð   background-position: 0 0;Ð }ÐÐ
.progress {Ð height: 20px;Ð margin-bottom: 20px;Ð overflow: hidden;Ð
background-color: #f5f5f5;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0
1px 2px rgba(0, 0, 0, .1);Ð         box-shadow: inset 0 1px 2px rgba(0, 0,
0, .1);ÐÐprogress-bar {Ð float: left;Ð width: 0;Ð height: 100%;Ð font-size:
12px;Ð line-height: 20px;Ð color: #fff;Ð text-align: center;Ð background-
color: #337ab7;Ð -webkit-box-shadow: inset 0 -1px 0 rgba(0, 0, 0, .15);Ð
          box-shadow: inset 0 -1px 0 rgba(0, 0, 0, .15);Ð -webkit-transition:
width .6s ease;Ð      -o-transition: width .6s ease;Ð         transition:
width .6s ease;ÐÐprogress-striped .progress-bar,Ð progress-bar-striped {Ð
background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, .15)
25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%,
rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-
image:      -o-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%,
transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255,
255, 255, .15) 75%, transparent 75%, transparent);Ð background-image:
linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%,
transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%,
transparent 75%, transparent);Ð -webkit-background-size: 40px 40px;Ð
background-size: 40px 40px;ÐÐprogress.active .progress-bar,Ð progress-
bar.active {Ð -webkit-animation: progress-bar-stripes 2s linear infinite;Ð
       -o-animation: progress-bar-stripes 2s linear infinite;Ð
animation: progress-bar-stripes 2s linear infinite;ÐÐprogress-bar-success {Ð
background-color: #5cb85c;ÐÐprogress-striped .progress-bar-success {Ð
background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, .15)
25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%,
rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-
image:      -o-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%,
transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255,
255, 255, .15) 75%, transparent 75%, transparent);Ð background-image:
linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%,
transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%,
transparent 75%, transparent);ÐÐprogress-bar-info {Ð background-color:
#5bc0de;ÐÐprogress-striped .progress-bar-info {Ð background-image: -webkit-
linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%,
transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%,
```

transparent 75%, transparent);Ð background-image: -o-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);ÐÐprogress-bar-warning {Ð background-color: #f0ad4e;ÐÐprogress-striped .progress-bar-warning {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-image: -o-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);ÐÐ .progress-bar-danger {Ð background-color: #d9534f;ÐÐprogress-striped .progress-bar-danger {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-image: -o-linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, .15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, .15) 50%, rgba(255, 255, 255, .15) 75%, transparent 75%, transparent);ÐÐ .media {Ð margin-top: 15px;ÐÐmedia:first-child {Ð margin-top: 0;ÐÐmedia,Ð .media-body {Ð overflow: hidden;Ð zoom: 1;ÐÐmedia-body {Ð width: 10000px;ÐÐ .media-object {Ð display: block;ÐÐmedia-object.img-thumbnail {Ð max-width: none;ÐÐmedia-right,Ðmedia > .pull-right {Ð padding-left: 10px;ÐÐmedia-left,Ð .media > .pull-left {Ð padding-right: 10px;ÐÐmedia-left,Ðmedia-right,Ðmedia-body {Ð display: table-cell;Ð vertical-align: top;ÐÐmedia-middle {Ð vertical-align: middle;ÐÐmedia-bottom {Ð vertical-align: bottom;ÐÐmedia-heading {Ð margin-top: 0;Ð margin-bottom: 5px;ÐÐmedia-list {Ð padding-left: 0;Ð list-style: none;ÐÐlist-group {Ð padding-left: 0;Ð margin-bottom: 20px;ÐÐlist-group-item {Ð position: relative;Ð display: block;Ð padding: 10px 15px;Ð margin-bottom: -1px;Ð background-color: #fff;Ð border: 1px solid #ddd;ÐÐlist-group-item:first-child {Ð border-top-left-radius: 4px;Ð border-top-right-radius: 4px;ÐÐlist-group-item:last-child {Ð margin-bottom: 0;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 4px;ÐÐa.list-group-item,Ð button.list-group-item {Ð color: #555;ÐÐa.list-group-item .list-group-item-heading,Ðbutton.list-group-item .list-group-item-heading {Ð color: #333;ÐÐ a.list-group-item:hover,Ðbutton.list-group-item:hover,Ða.list-group-item:focus,Ð button.list-group-item:focus {Ð color: #555;Ð text-decoration: none;Ð background-color: #f5f5f5;ÐÐbutton.list-group-item {Ð width: 100%;Ð text-align: left;ÐÐlist-group-item.disabled,Ðlist-group-item.disabled:hover,Ðlist-group-item.disabled:focus {Ð color: #777;Ð cursor: not-allowed;Ð background-color: #eee;ÐÐlist-group-item.disabled .list-group-item-heading,Ðlist-group-item.disabled:hover .list-group-item-heading,Ðlist-group-item.disabled:focus .list-group-item-heading {Ð color: inherit;ÐÐlist-group-item.disabled .list-group-item-text,Ðlist-group-item.disabled:hover .list-group-item-text,Ðlist-group-item.disabled:focus .list-group-item-text {Ð color: #777;ÐÐlist-group-item.active,Ðlist-group-item.active:hover,Ðlist-group-item.active:focus {Ð z-index: 2;Ð color: #fff;Ð background-color: #337ab7;Ð border-color: #337ab7;ÐÐlist-group-item.active .list-group-item-heading,Ðlist-group-item.active:hover .list-group-item-heading,Ðlist-group-item.active:focus .list-group-item-heading,Ðlist-group-item.active .list-group-item-heading > small,Ðlist-group-item.active:hover .list-group-item-heading > small,Ðlist-group-item.active:focus .list-group-item-heading > small,Ð

.list-group-item.active .list-group-item-heading > .small,Ðlist-group-item.active:hover .list-group-item-heading > .small,Ðlist-group-item.active:focus .list-group-item-heading > .small {Ð color: inherit;ÞÐlist-group-item.active .list-group-item-text,Ðlist-group-item.active:hover .list-group-item-text,Ðlist-group-item.active:focus .list-group-item-text {Ð color: #c7ddef;ÞÐlist-group-item-success {Ð color: #3c763d;Ð background-color: #dff0d8;ÞÐa.list-group-item-success,Ðbutton.list-group-item-success {Ð color: #3c763d;ÞÐa.list-group-item-success .list-group-item-heading,Ðbutton.list-group-item-success .list-group-item-heading {Ð color: inherit;ÞÐa.list-group-item-success:hover,Ðbutton.list-group-item-success:hover,Ða.list-group-item-success:focus,Ðbutton.list-group-item-success:focus {Ð color: #3c763d;Ð background-color: #d0e9c6;ÞÐa.list-group-item-success.active,Ðbutton.list-group-item-success.active,Ða.list-group-item-success.active:hover,Ðbutton.list-group-item-success.active:hover,Ða.list-group-item-success.active:focus,Ðbutton.list-group-item-success.active:focus {Ð color: #fff;Ð background-color: #3c763d;Ð border-color: #3c763d;ÞÐlist-group-item-info {Ð color: #31708f;Ð background-color: #d9edf7;ÞÐa.list-group-item-info,Ðbutton.list-group-item-info {Ð color: #31708f;ÞÐa.list-group-item-info .list-group-item-heading,Ðbutton.list-group-item-info .list-group-item-heading {Ð color: inherit;ÞÐa.list-group-item-info:hover,Ðbutton.list-group-item-info:hover,Ða.list-group-item-info:focus,Ðbutton.list-group-item-info:focus {Ð color: #31708f;Ð background-color: #c4e3f3;ÞÐa.list-group-item-info.active,Ðbutton.list-group-item-info.active,Ða.list-group-item-info.active:hover,Ðbutton.list-group-item-info.active:hover,Ða.list-group-item-info.active:focus,Ðbutton.list-group-item-info.active:focus {Ð color: #fff;Ð background-color: #31708f;Ð border-color: #31708f;ÞÐlist-group-item-warning {Ð color: #8a6d3b;Ð background-color: #fcf8e3;ÞÐa.list-group-item-warning,Ðbutton.list-group-item-warning {Ð color: #8a6d3b;ÞÐa.list-group-item-warning .list-group-item-heading,Ðbutton.list-group-item-warning .list-group-item-heading {Ð color: inherit;ÞÐa.list-group-item-warning:hover,Ðbutton.list-group-item-warning:hover,Ða.list-group-item-warning:focus,Ðbutton.list-group-item-warning:focus {Ð color: #8a6d3b;Ð background-color: #faf2cc;ÞÐa.list-group-item-warning.active,Ðbutton.list-group-item-warning.active,Ða.list-group-item-warning.active:hover,Ðbutton.list-group-item-warning.active:hover,Ða.list-group-item-warning.active:focus,Ðbutton.list-group-item-warning.active:focus {Ð color: #fff;Ð background-color: #8a6d3b;Ð border-color: #8a6d3b;ÞÐlist-group-item-danger {Ð color: #a94442;Ð background-color: #f2dede;ÞÐa.list-group-item-danger,Ðbutton.list-group-item-danger {Ð color: #a94442;ÞÐa.list-group-item-danger .list-group-item-heading,Ðbutton.list-group-item-danger .list-group-item-heading {Ð color: inherit;ÞÐa.list-group-item-danger:hover,Ðbutton.list-group-item-danger:hover,Ða.list-group-item-danger:focus,Ðbutton.list-group-item-danger:focus {Ð color: #a94442;Ð background-color: #ebcccc;ÞÐa.list-group-item-danger.active,Ðbutton.list-group-item-danger.active,Ða.list-group-item-danger.active:hover,Ðbutton.list-group-item-danger.active:hover,Ða.list-group-item-danger.active:focus,Ðbutton.list-group-item-danger.active:focus {Ð color: #fff;Ð background-color: #a94442;Ð border-color: #a94442;ÞÐlist-group-item-heading {Ð margin-top: 0;Ð margin-bottom: 5px;ÞÐlist-group-item-text {Ð margin-bottom: 0;Ð line-height: 1.3;ÞÐ .panel {Ð margin-bottom: 20px;Ð background-color: #fff;Ð border: 1px solid transparent;Ð border-radius: 4px;Ð -webkit-box-shadow: 0 1px 1px rgba(0, 0, 0, .05);Ð box-shadow: 0 1px 1px rgba(0, 0, 0, .05);ÞÐpanel-body {Ð padding: 15px;ÞÐpanel-heading {Ð padding: 10px 15px;Ð border-bottom: 1px solid transparent;Ð border-top-left-radius: 3px;Ð border-top-right-radius: 3px;ÞÐpanel-heading > .dropdown .dropdown-toggle {Ð color: inherit;ÞÐpanel-title {Ð margin-top: 0;Ð margin-bottom: 0;Ð font-size: 16px;Ð color: inherit;ÞÐ .panel-title > a,Ðpanel-title > small,Ðpanel-title > .small,Ðpanel-title > small > a,Ðpanel-title > .small > a {Ð color: inherit;ÞÐpanel-footer {Ð padding: 10px 15px;Ð background-color: #f5f5f5;Ð border-top: 1px solid #ddd;Ð border-bottom-right-radius: 3px;Ð border-bottom-left-radius: 3px;ÞÐpanel > .list-group,Ðpanel > .panel-collapse > .list-group {Ð margin-bottom: 0;ÞÐ .panel > .list-group .list-group-item,Ð

.panel > .panel-collapse > .list-group .list-group-item {Ð border-width: 1px 0;Ð border-radius: 0;ÐÐpanel > .list-group:first-child .list-group-item:first-child,Ðpanel > .panel-collapse > .list-group:first-child .list-group-item:first-child {Ð border-top: 0;Ð border-top-left-radius: 3px;Ð border-top-right-radius: 3px;ÐÐpanel > .list-group:last-child .list-group-item:last-child,Ðpanel > .panel-collapse > .list-group:last-child .list-group-item:last-child {Ð border-bottom: 0;Ð border-bottom-right-radius: 3px;Ð border-bottom-left-radius: 3px;ÐÐpanel > .panel-heading + .panel-collapse > .list-group .list-group-item:first-child {Ð border-top-left-radius: 0;Ð border-top-right-radius: 0;ÐÐpanel-heading + .list-group .list-group-item:first-child {Ð border-top-width: 0;ÐÐlist-group + .panel-footer {Ð border-top-width: 0;ÐÐpanel > .table,Ðpanel > .table-responsive > .table,Ðpanel > .panel-collapse > .table {Ð margin-bottom: 0;ÐÐ .panel > .table caption,Ðpanel > .table-responsive > .table caption,Ðpanel > .panel-collapse > .table caption {Ð padding-right: 15px;Ð padding-left: 15px;ÐÐpanel > .table:first-child,Ðpanel > .table-responsive:first-child > .table:first-child {Ð border-top-left-radius: 3px;Ð border-top-right-radius: 3px;ÐÐpanel > .table:first-child > thead:first-child > tr:first-child,Ð .panel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child,Ðpanel > .table:first-child > tbody:first-child > tr:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child {Ð border-top-left-radius: 3px;Ð border-top-right-radius: 3px;ÐÐpanel > .table:first-child > thead:first-child > tr:first-child td:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child td:first-child,Ð .panel > .table:first-child > tbody:first-child > tr:first-child td:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child td:first-child,Ðpanel > .table:first-child > thead:first-child > tr:first-child th:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child th:first-child,Ðpanel > .table:first-child > tbody:first-child > tr:first-child th:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child th:first-child {Ð border-top-left-radius: 3px;ÐÐpanel > .table:first-child > thead:first-child > tr:first-child td:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child td:last-child,Ð .panel > .table:first-child > tbody:first-child > tr:first-child td:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child td:last-child,Ðpanel > .table:first-child > thead:first-child > tr:first-child th:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child th:last-child,Ðpanel > .table:first-child > tbody:first-child > tr:first-child th:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child th:last-child {Ð border-top-right-radius: 3px;ÐÐpanel > .table:last-child,Ðpanel > .table-responsive:last-child > .table:last-child {Ð border-bottom-right-radius: 3px;Ð border-bottom-left-radius: 3px;ÐÐpanel > .table:last-child > tbody:last-child > tr:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child {Ð border-bottom-right-radius: 3px;Ð border-bottom-left-radius: 3px;ÐÐpanel > .table:last-child > tbody:last-child > tr:last-child td:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child td:first-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child td:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child td:first-child,Ðpanel > .table:last-child > tbody:last-child > tr:last-child th:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child th:first-child,Ð

.panel > .table:last-child > tfoot:last-child > tr:last-child th:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child th:first-child {Ð border-bottom-left-radius: 3px;ÞÐpanel > .table:last-child > tbody:last-child > tr:last-child td:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child td:last-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child td:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child td:last-child,Ðpanel > .table:last-child > tbody:last-child > tr:last-child th:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child th:last-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child th:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child th:last-child {Ð border-bottom-right-radius: 3px;ÞÐpanel > .panel-body + .table,Ðpanel > .panel-body + .table-responsive,Ðpanel > .table + .panel-body,Ðpanel > .table-responsive + .panel-body {Ð border-top: 1px solid #ddd;ÞÐpanel > .table > tbody:first-child > tr:first-child th,Ðpanel > .table > tbody:first-child > tr:first-child td {Ð border-top: 0;ÞÐpanel > .table-bordered,Ðpanel > .table-responsive > .table-bordered {Ð border: 0;ÞÐpanel > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-bordered > tfoot > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left: 0;ÞÐpanel > .table-bordered > thead > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > th:last-child,Ðpanel > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-bordered > thead > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:last-child,Ðpanel > .table-bordered > tbody > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > td:last-child,Ðpanel > .table-bordered > tfoot > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-right: 0;ÞÐ .panel > .table-bordered > thead > tr:first-child > td,Ðpanel > .table-responsive > .table-bordered > thead > tr:first-child > td,Ðpanel > .table-bordered > tbody > tr:first-child > td,Ðpanel > .table-responsive > .table-bordered > tbody > tr:first-child > td,Ðpanel > .table-bordered > thead > tr:first-child > th,Ðpanel > .table-responsive > .table-bordered > thead > tr:first-child > th,Ðpanel > .table-bordered > tbody > tr:first-child > th,Ð .panel > .table-responsive > .table-bordered > tbody > tr:first-child > th {Ð border-bottom: 0;ÞÐpanel > .table-bordered > tbody > tr:last-child > td,Ð .panel > .table-responsive > .table-bordered > tbody > tr:last-child > td,Ð .panel > .table-bordered > tfoot > tr:last-child > td,Ðpanel > .table-responsive > .table-bordered > tfoot > tr:last-child > td,Ðpanel > .table-bordered > tbody > tr:last-child > th,Ðpanel > .table-responsive > .table-bordered > tbody > tr:last-child > th,Ðpanel > .table-bordered > tfoot > tr:last-child > th,Ðpanel > .table-responsive > .table-bordered > tfoot > tr:last-child > th {Ð border-bottom: 0;ÞÐpanel > .table-responsive {Ð margin-bottom: 0;Ð border: 0;ÞÐpanel-group {Ð margin-bottom: 20px;ÞÐpanel-group .panel {Ð margin-bottom: 0;Ð border-radius: 4px;ÞÐpanel-group .panel + .panel {Ð margin-top: 5px;ÞÐpanel-group .panel-heading {Ð border-bottom: 0;ÞÐ .panel-group .panel-heading + .panel-collapse > .panel-body,Ðpanel-group .panel-heading + .panel-collapse > .list-group {Ð

```
                                                        border-top: 1px solid
#ddd;ÐÐpanel-group .panel-footer {Ð border-top: 0;ÐÐpanel-group .panel-footer
+ .panel-collapse .panel-body {Ð border-bottom: 1px solid #ddd;ÐÐpanel-
default {Ð border-color: #ddd;ÐÐpanel-default > .panel-heading {Ð color: #333;Ð
  background-color: #f5f5f5;Ð border-color: #ddd;ÐÐpanel-default > .panel-
heading + .panel-collapse > .panel-body {Ð border-top-color: #ddd;ÐÐpanel-
default > .panel-heading .badge {Ð color: #f5f5f5;Ð background-color: #333;ÐÐ
.panel-default > .panel-footer + .panel-collapse > .panel-body {Ð border-
bottom-color: #ddd;ÐÐpanel-primary {Ð border-color: #337ab7;ÐÐpanel-primary
> .panel-heading {Ð color: #fff;Ð background-color: #337ab7;Ð border-color:
#337ab7;ÐÐpanel-primary > .panel-heading + .panel-collapse > .panel-body {Ð
border-top-color: #337ab7;ÐÐpanel-primary > .panel-heading .badge {Ð color:
#337ab7;Ð background-color: #fff;ÐÐpanel-primary > .panel-footer + .panel-
collapse > .panel-body {Ð border-bottom-color: #337ab7;ÐÐpanel-success {Ð
border-color: #d6e9c6;ÐÐpanel-success > .panel-heading {Ð color: #3c763d;Ð
background-color: #dff0d8;Ð border-color: #d6e9c6;ÐÐpanel-success > .panel-
heading + .panel-collapse > .panel-body {Ð border-top-color: #d6e9c6;ÐÐpanel-
success > .panel-heading .badge {Ð color: #dff0d8;Ð background-color: #3c763d;Ð
}Ðpanel-success > .panel-footer + .panel-collapse > .panel-body {Ð border-
bottom-color: #d6e9c6;ÐÐpanel-info {Ð border-color: #bce8f1;ÐÐpanel-info
> .panel-heading {Ð color: #31708f;Ð background-color: #d9edf7;Ð border-
color: #bce8f1;ÐÐpanel-info > .panel-heading + .panel-collapse > .panel-body {Ð
  border-top-color: #bce8f1;ÐÐpanel-info > .panel-heading .badge {Ð color:
#d9edf7;Ð background-color: #31708f;ÐÐpanel-info > .panel-footer + .panel-
collapse > .panel-body {Ð border-bottom-color: #bce8f1;ÐÐpanel-warning {Ð
border-color: #faebcc;ÐÐpanel-warning > .panel-heading {Ð color: #8a6d3b;Ð
background-color: #fcf8e3;Ð border-color: #faebcc;ÐÐpanel-warning > .panel-
heading + .panel-collapse > .panel-body {Ð border-top-color: #faebcc;ÐÐpanel-
warning > .panel-heading .badge {Ð color: #fcf8e3;Ð background-color: #8a6d3b;Ð
}Ðpanel-warning > .panel-footer + .panel-collapse > .panel-body {Ð border-
bottom-color: #faebcc;ÐÐpanel-danger {Ð border-color: #ebccd1;ÐÐpanel-danger
> .panel-heading {Ð color: #a94442;Ð background-color: #f2dede;Ð border-
color: #ebccd1;ÐÐpanel-danger > .panel-heading + .panel-collapse > .panel-
body {Ð border-top-color: #ebccd1;ÐÐpanel-danger > .panel-heading .badge {Ð
color: #f2dede;Ð background-color: #a94442;ÐÐpanel-danger > .panel-footer
+ .panel-collapse > .panel-body {Ð border-bottom-color: #ebccd1;ÐÐembed-
responsive {Ð position: relative;Ð display: block;Ð height: 0;Ð padding: 0;Ð
overflow: hidden;ÐÐembed-responsive .embed-responsive-item,Ðembed-responsive
iframe,Ðembed-responsive embed,Ðembed-responsive object,Ðembed-responsive
video {Ð position: absolute;Ð top: 0;Ð bottom: 0;Ð left: 0;Ð width: 100%;Ð
height: 100%;Ð border: 0;ÐÐembed-responsive-16by9 {Ð padding-bottom: 56.25%;ÐÐ
.embed-responsive-4by3 {Ð padding-bottom: 75%;ÐÐwell {Ð min-height: 20px;Ð
padding: 19px;Ð margin-bottom: 20px;Ð background-color: #f5f5f5;Ð border: 1px
solid #e3e3e3;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 1px
rgba(0, 0, 0, .05);Ð         box-shadow: inset 0 1px 1px rgba(0, 0, 0, .05);ÐÐ
.well blockquote {Ð border-color: #ddd;Ð border-color: rgba(0, 0, 0, .15);ÐÐ
.well-lg {Ð padding: 24px;Ð border-radius: 6px;ÐÐwell-sm {Ð padding: 9px;Ð
border-radius: 3px;ÐÐclose {Ð float: right;Ð font-size: 21px;Ð font-weight:
bold;Ð line-height: 1;Ð color: #000;Ð text-shadow: 0 1px 0 #fff;Ð filter:
alpha(opacity=20);Ð opacity: .2;ÐÐclose:hover,Ðclose:focus {Ð color: #000;Ð
text-decoration: none;Ð cursor: pointer;Ð filter: alpha(opacity=50);Ð
opacity: .5;ÐÐbutton.close {Ð -webkit-appearance: none;Ð padding: 0;Ð cursor:
pointer;Ð background: transparent;Ð border: 0;ÐÐmodal-open {Ð overflow:
hidden;ÐÐmodal {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð
z-index: 1050;Ð display: none;Ð overflow: hidden;Ð -webkit-overflow-
scrolling: touch;Ð outline: 0;ÐÐmodal.fade .modal-dialog {Ð -webkit-
transition: -webkit-transform .3s ease-out;Ð      -o-transition:      -o-
transform .3s ease-out;Ð         transition:         transform .3s ease-out;Ð
-webkit-transform: translate(0, -25%);Ð     -ms-transform: translate(0, -25%);Ð
       -o-transform: translate(0, -25%);Ð
```

transform: translate(0, -25%);ÐÐmodal.in .modal-dialog {Ð -webkit-transform: translate(0, 0);Ð -ms-transform: translate(0, 0);Ð -o-transform: translate(0, 0);Ð transform: translate(0, 0);ÐÐmodal-open .modal {Ð overflow-x: hidden;Ð overflow-y: auto;ÐÐmodal-dialog {Ð position: relative;Ð width: auto;Ð margin: 10px;ÐÐmodal-content {Ð position: relative;Ð background-color: #fff;Ð -webkit-background-clip: padding-box;Ð background-clip: padding-box;Ð border: 1px solid #999;Ð border: 1px solid rgba(0, 0, 0, .2);Ð border-radius: 6px;Ð outline: 0;Ð -webkit-box-shadow: 0 3px 9px rgba(0, 0, 0, .5);Ð box-shadow: 0 3px 9px rgba(0, 0, 0, .5);ÐÐmodal-backdrop {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 1040;Ð background-color: #000;ÐÐmodal-backdrop.fade {Ð filter: alpha(opacity=0);Ð opacity: 0;ÐÐmodal-backdrop.in {Ð filter: alpha(opacity=50);Ð opacity: .5;ÐÐmodal-header {Ð padding: 15px;Ð border-bottom: 1px solid #e5e5e5;ÐÐmodal-header .close {Ð margin-top: -2px;ÐÐmodal-title {Ð margin: 0;Ð line-height: 1.42857143;ÐÐmodal-body {Ð position: relative;Ð padding: 15px;ÐÐmodal-footer {Ð padding: 15px;Ð text-align: right;Ð border-top: 1px solid #e5e5e5;ÐÐmodal-footer .btn + .btn {Ð margin-bottom: 0;Ð margin-left: 5px;ÐÐmodal-footer .btn-group .btn + .btn {Ð margin-left: -1px;ÐÐmodal-footer .btn-block + .btn-block {Ð margin-left: 0;ÐÐ .modal-scrollbar-measure {Ð position: absolute;Ð top: -9999px;Ð width: 50px;Ð height: 50px;Ð overflow: scroll;ÐÐ@media (min-width: 768px) {Ð .modal-dialog {Ð width: 600px;Ð margin: 30px auto;Ð }Ð .modal-content {Ð -webkit-box-shadow: 0 5px 15px rgba(0, 0, 0, .5);Ð box-shadow: 0 5px 15px rgba(0, 0, 0, .5);Ð }Ð .modal-sm {Ð width: 300px;Ð }ÐÐ@media (min-width: 992px) {Ð .modal-lg {Ð width: 900px;Ð }ÐÐtooltip {Ð position: absolute;Ð z-index: 1070;Ð display: block;Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 12px;Ð font-style: normal;Ð font-weight: normal;Ð line-height: 1.42857143;Ð text-align: left;Ð text-align: start;Ð text-decoration: none;Ð text-shadow: none;Ð text-transform: none;Ð letter-spacing: normal;Ð word-break: normal;Ð word-spacing: normal;Ð word-wrap: normal;Ð white-space: normal;Ð filter: alpha(opacity=0);Ð opacity: 0;Ð line-break: auto;ÐÐtooltip.in {Ð filter: alpha(opacity=90);Ð opacity: .9;ÐÐ .tooltip.top {Ð padding: 5px 0;Ð margin-top: -3px;ÐÐtooltip.right {Ð padding: 0 5px;Ð margin-left: 3px;ÐÐtooltip.bottom {Ð padding: 5px 0;Ð margin-top: 3px;Ð }Ðtooltip.left {Ð padding: 0 5px;Ð margin-left: -3px;ÐÐtooltip-inner {Ð max-width: 200px;Ð padding: 3px 8px;Ð color: #fff;Ð text-align: center;Ð background-color: #000;Ð border-radius: 4px;ÐÐtooltip-arrow {Ð position: absolute;Ð width: 0;Ð height: 0;Ð border-color: transparent;Ð border-style: solid;ÐÐtooltip.top .tooltip-arrow {Ð bottom: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000;ÐÐtooltip.top-left .tooltip-arrow {Ð right: 5px;Ð bottom: 0;Ð margin-bottom: -5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000;ÐÐtooltip.top-right .tooltip-arrow {Ð bottom: 0;Ð left: 5px;Ð margin-bottom: -5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000;ÐÐtooltip.right .tooltip-arrow {Ð top: 50%;Ð left: 0;Ð margin-top: -5px;Ð border-width: 5px 5px 5px 0;Ð border-right-color: #000;ÐÐ .tooltip.left .tooltip-arrow {Ð top: 50%;Ð right: 0;Ð margin-top: -5px;Ð border-width: 5px 0 5px 5px;Ð border-left-color: #000;ÐÐ .tooltip.bottom .tooltip-arrow {Ð top: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000;ÐÐtooltip.bottom-left .tooltip-arrow {Ð top: 0;Ð right: 5px;Ð margin-top: -5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000;ÐÐtooltip.bottom-right .tooltip-arrow {Ð top: 0;Ð left: 5px;Ð margin-top: -5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000;ÐÐpopover {Ð position: absolute;Ð top: 0;Ð left: 0;Ð z-index: 1060;Ð display: none;Ð max-width: 276px;Ð padding: 1px;Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 14px;Ð font-style: normal;Ð font-weight: normal;Ð line-height: 1.42857143;Ð text-align: left;Ð text-align: start;Ð text-decoration: none;Ð text-shadow: none;Ð text-transform: none;Ð letter-spacing: normal;Ð word-break: normal;Ð word-spacing: normal;Ð word-wrap: normal;Ð white-space: normal;Ð background-color: #fff;Ð -webkit-background-clip: padding-box;Ð

background-clip: padding-box;Ð
border: 1px solid #ccc;Ð border: 1px solid rgba(0, 0, 0, .2);Ð border-radius:
6px;Ð -webkit-box-shadow: 0 5px 10px rgba(0, 0, 0, .2);Ð box-shadow:
0 5px 10px rgba(0, 0, 0, .2);Ð line-break: auto;ÐÐpopover.top {Ð margin-top:
-10px;ÐÐpopover.right {Ð margin-left: 10px;ÐÐpopover.bottom {Ð margin-top:
10px;ÐÐpopover.left {Ð margin-left: -10px;ÐÐpopover-title {Ð padding: 8px
14px;Ð margin: 0;Ð font-size: 14px;Ð background-color: #f7f7f7;Ð border-
bottom: 1px solid #ebebeb;Ð border-radius: 5px 5px 0 0;ÐÐpopover-content {Ð
padding: 9px 14px;ÐÐpopover > .arrow,Ðpopover > .arrow:after {Ð position:
absolute;Ð display: block;Ð width: 0;Ð height: 0;Ð border-color: transparent;Ð
border-style: solid;ÐÐpopover > .arrow {Ð border-width: 11px;ÐÐpopover
> .arrow:after {Ð content: "";Ð border-width: 10px;ÐÐpopover.top > .arrow {Ð
bottom: -11px;Ð left: 50%;Ð margin-left: -11px;Ð border-top-color: #999;Ð
border-top-color: rgba(0, 0, 0, .25);Ð border-bottom-width: 0;ÐÐpopover.top
> .arrow:after {Ð bottom: 1px;Ð margin-left: -10px;Ð content: " ";Ð border-
top-color: #fff;Ð border-bottom-width: 0;ÐÐpopover.right > .arrow {Ð top: 50%;Ð
left: -11px;Ð margin-top: -11px;Ð border-right-color: #999;Ð border-right-
color: rgba(0, 0, 0, .25);Ð border-left-width: 0;ÐÐpopover.right
> .arrow:after {Ð bottom: -10px;Ð left: 1px;Ð content: " ";Ð border-right-
color: #fff;Ð border-left-width: 0;ÐÐpopover.bottom > .arrow {Ð top: -11px;Ð
left: 50%;Ð margin-left: -11px;Ð border-top-width: 0;Ð border-bottom-color:
#999;Ð border-bottom-color: rgba(0, 0, 0, .25);ÐÐpopover.bottom
> .arrow:after {Ð top: 1px;Ð margin-left: -10px;Ð content: " ";Ð border-top-
width: 0;Ð border-bottom-color: #fff;ÐÐpopover.left > .arrow {Ð top: 50%;Ð
right: -11px;Ð margin-top: -11px;Ð border-right-width: 0;Ð border-left-color:
#999;Ð border-left-color: rgba(0, 0, 0, .25);ÐÐpopover.left > .arrow:after {Ð
right: 1px;Ð bottom: -10px;Ð content: " ";Ð border-right-width: 0;Ð border-
left-color: #fff;ÐÐcarousel {Ð position: relative;ÐÐcarousel-inner {Ð
position: relative;Ð width: 100%;Ð overflow: hidden;ÐÐcarousel-inner > .item {Ð
position: relative;Ð display: none;Ð -webkit-transition: .6s ease-in-out
left;Ð -o-transition: .6s ease-in-out left;Ð transition: .6s
ease-in-out left;ÐÐcarousel-inner > .item > img,Ðcarousel-inner > .item > a >
img {Ð line-height: 1;ÐÐ@media all and (transform-3d), (-webkit-transform-3d) {Ð
.carousel-inner > .item {Ð -webkit-transition: -webkit-transform .6s ease-
in-out;Ð -o-transition: -o-transform .6s ease-in-out;Ð
transition: transform .6s ease-in-out;Ð -webkit-backface-
visibility: hidden;Ð backface-visibility: hidden;Ð -webkit-
perspective: 1000px;Ð perspective: 1000px;Ð }Ð .carousel-inner
> .item.next,Ð .carousel-inner > .item.active.right {Ð left: 0;Ð -webkit-
transform: translate3d(100%, 0, 0);Ð transform: translate3d(100%,
0, 0);Ð }Ð .carousel-inner > .item.prev,Ð .carousel-inner > .item.active.left
{Ð left: 0;Ð -webkit-transform: translate3d(-100%, 0, 0);Ð
transform: translate3d(-100%, 0, 0);Ð }Ð .carousel-inner > .item.next.left,Ð
.carousel-inner > .item.prev.right,Ð .carousel-inner > .item.active {Ð
left: 0;Ð -webkit-transform: translate3d(0, 0, 0);Ð transform:
translate3d(0, 0, 0);Ð }ÐÐcarousel-inner > .active,Ðcarousel-inner > .next,Ð
.carousel-inner > .prev {Ð display: block;ÐÐcarousel-inner > .active {Ð left:
0;ÐÐcarousel-inner > .next,Ðcarousel-inner > .prev {Ð position: absolute;Ð
top: 0;Ð width: 100%;ÐÐcarousel-inner > .next {Ð left: 100%;ÐÐcarousel-inner
> .prev {Ð left: -100%;ÐÐcarousel-inner > .next.left,Ðcarousel-inner
> .prev.right {Ð left: 0;ÐÐcarousel-inner > .active.left {Ð left: -100%;ÐÐ
.carousel-inner > .active.right {Ð left: 100%;ÐÐcarousel-control {Ð position:
absolute;Ð top: 0;Ð bottom: 0;Ð left: 0;Ð width: 15%;Ð font-size: 20px;Ð
color: #fff;Ð text-align: center;Ð text-shadow: 0 1px 2px rgba(0, 0, 0, .6);Ð
background-color: rgba(0, 0, 0, 0);Ð filter: alpha(opacity=50);Ð opacity: .5;ÐÐ
.carousel-control.left {Ð background-image: -webkit-linear-gradient(left,
rgba(0, 0, 0, .5) 0%, rgba(0, 0, 0, .0001) 100%);Ð background-image: -o-
linear-gradient(left, rgba(0, 0, 0, .5) 0%, rgba(0, 0, 0, .0001) 100%);Ð
background-image: -webkit-gradient(linear, left top, right top, from(rgba(0,
0, 0, .5)), to(rgba(0, 0, 0, .0001)));Ð

background-image: linear-gradient(to right, rgba(0, 0, 0, .5) 0%, rgba(0, 0, 0, .0001) 100%);Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#80000000', endColorstr='#00000000', GradientType=1);Ð background-repeat: repeat-x;ÞÐ .carousel-control.right {Ð right: 0;Ð left: auto;Ð background-image: -webkit-linear-gradient(left, rgba(0, 0, 0, .0001) 0%, rgba(0, 0, 0, .5) 100%);Ð background-image: -o-linear-gradient(left, rgba(0, 0, 0, .0001) 0%, rgba(0, 0, 0, .5) 100%);Ð background-image: -webkit-gradient(linear, left top, right top, from(rgba(0, 0, 0, .0001)), to(rgba(0, 0, 0, .5)));Ð background-image: linear-gradient(to right, rgba(0, 0, 0, .0001) 0%, rgba(0, 0, 0, .5) 100%);Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#00000000', endColorstr='#80000000', GradientType=1);Ð background-repeat: repeat-x;ÞÐ .carousel-control:hover,Ðcarousel-control:focus {Ð color: #fff;Ð text-decoration: none;Ð filter: alpha(opacity=90);Ð outline: 0;Ð opacity: .9;ÞÐ .carousel-control .icon-prev,Ðcarousel-control .icon-next,Ðcarousel-control .glyphicon-chevron-left,Ðcarousel-control .glyphicon-chevron-right {Ð position: absolute;Ð top: 50%;Ð z-index: 5;Ð display: inline-block;Ð margin-top: -10px;ÞÐcarousel-control .icon-prev,Ðcarousel-control .glyphicon-chevron-left {Ð left: 50%;Ð margin-left: -10px;ÞÐcarousel-control .icon-next,Ð .carousel-control .glyphicon-chevron-right {Ð right: 50%;Ð margin-right: -10px;ÞÐcarousel-control .icon-prev,Ðcarousel-control .icon-next {Ð width: 20px;Ð height: 20px;Ð font-family: serif;Ð line-height: 1;ÞÐcarousel-control .icon-prev:before {Ð content: '\2039';ÞÐcarousel-control .icon-next:before {Ð content: '\203a';ÞÐcarousel-indicators {Ð position: absolute;Ð bottom: 10px;Ð left: 50%;Ð z-index: 15;Ð width: 60%;Ð padding-left: 0;Ð margin-left: -30%;Ð text-align: center;Ð list-style: none;ÞÐcarousel-indicators li {Ð display: inline-block;Ð width: 10px;Ð height: 10px;Ð margin: 1px;Ð text-indent: -999px;Ð cursor: pointer;Ð background-color: #000 \9;Ð background-color: rgba(0, 0, 0, 0);Ð border: 1px solid #fff;Ð border-radius: 10px;ÞÐcarousel-indicators .active {Ð width: 12px;Ð height: 12px;Ð margin: 0;Ð background-color: #fff;ÞÐcarousel-caption {Ð position: absolute;Ð right: 15%;Ð bottom: 20px;Ð left: 15%;Ð z-index: 10;Ð padding-top: 20px;Ð padding-bottom: 20px;Ð color: #fff;Ð text-align: center;Ð text-shadow: 0 1px 2px rgba(0, 0, 0, .6);ÞÐcarousel-caption .btn {Ð text-shadow: none;ÞÐ@media screen and (min-width: 768px) {Ð .carousel-control .glyphicon-chevron-left,Ð .carousel-control .glyphicon-chevron-right,Ð .carousel-control .icon-prev,Ð .carousel-control .icon-next {Ð width: 30px;Ð height: 30px;Ð margin-top: -10px;Ð font-size: 30px;Ð }Ð .carousel-control .glyphicon-chevron-left,Ð .carousel-control .icon-prev {Ð margin-left: -10px;Ð }Ð .carousel-control .glyphicon-chevron-right,Ð .carousel-control .icon-next {Ð margin-right: -10px;Ð }Ð .carousel-caption {Ð right: 20%;Ð left: 20%;Ð padding-bottom: 30px;Ð }Ð .carousel-indicators {Ð bottom: 20px;Ð }ÞÐclearfix:before,Ð .clearfix:after,Ðdl-horizontal dd:before,Ðdl-horizontal dd:after,Ð .container:before,Ðcontainer:after,Ðcontainer-fluid:before,Ðcontainer-fluid:after,Ðrow:before,Ðrow:after,Ðform-horizontal .form-group:before,Ðform-horizontal .form-group:after,Ðbtn-toolbar:before,Ðbtn-toolbar:after,Ðbtn-group-vertical > .btn-group:before,Ðbtn-group-vertical > .btn-group:after,Ð .nav:before,Ðnav:after,Ðnavbar:before,Ðnavbar:after,Ðnavbar-header:before,Ð .navbar-header:after,Ðnavbar-collapse:before,Ðnavbar-collapse:after,Ð .pager:before,Ðpager:after,Ðpanel-body:before,Ðpanel-body:after,Ðmodal-header:before,Ðmodal-header:after,Ðmodal-footer:before,Ðmodal-footer:after {Ð display: table;Ð content: " ";ÞÐclearfix:after,Ðdl-horizontal dd:after,Ð .container:after,Ðcontainer-fluid:after,Ðrow:after,Ðform-horizontal .form-group:after,Ðbtn-toolbar:after,Ðbtn-group-vertical > .btn-group:after,Ð .nav:after,Ðnavbar:after,Ðnavbar-header:after,Ðnavbar-collapse:after,Ð .pager:after,Ðpanel-body:after,Ðmodal-header:after,Ðmodal-footer:after {Ð clear: both;ÞÐcenter-block {Ð display: block;Ð margin-right: auto;Ð margin-left: auto;ÞÐpull-right {Ð float: right !important;ÞÐpull-left {Ð float: left !important;Ð

}Ðhide {Ð display: none !important;ÐÐshow {Ð display: block !important;ÐÐinvisible {Ð visibility: hidden;ÐÐtext-hide {Ð font: 0/0 a;Ð color: transparent;Ð text-shadow: none;Ð background-color: transparent;Ð border: 0;ÐÐhidden {Ð display: none !important;ÐÐaffix {Ð position: fixed;Ð@-ms-viewport {Ð width: device-width;ÐÐvisible-xs,Ðvisible-sm,Ðvisible-md,Ð .visible-lg {Ð display: none !important;ÐÐvisible-xs-block,Ðvisible-xs-inline,Ð .visible-xs-inline-block,Ðvisible-sm-block,Ðvisible-sm-inline,Ðvisible-sm-inline-block,Ðvisible-md-block,Ðvisible-md-inline,Ðvisible-md-inline-block,Ð .visible-lg-block,Ðvisible-lg-inline,Ðvisible-lg-inline-block {Ð display: none !important;Ð@media (max-width: 767px) {Ð .visible-xs {Ð display: block !important;Ð }Ð table.visible-xs {Ð display: table !important;Ð }Ð tr.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-xs,Ð td.visible-xs {Ð display: table-cell !important;Ð }Ð@media (max-width: 767px) {Ð .visible-xs-block {Ð display: block !important;Ð }Ð@media (max-width: 767px) {Ð .visible-xs-inline {Ð display: inline !important;Ð }ÐÐ @media (max-width: 767px) {Ð .visible-xs-inline-block {Ð display: inline-block !important;Ð }Ð@media (min-width: 768px) and (max-width: 991px) {Ð .visible-sm {Ð display: block !important;Ð }Ð table.visible-sm {Ð display: table !important;Ð }Ð tr.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-sm,Ð td.visible-sm {Ð display: table-cell !important;Ð }Ð@media (min-width: 768px) and (max-width: 991px) {Ð .visible-sm-block {Ð display: block !important;Ð }Ð@media (min-width: 768px) and (max-width: 991px) {Ð .visible-sm-inline {Ð display: inline !important;Ð }ÐÐ @media (min-width: 768px) and (max-width: 991px) {Ð .visible-sm-inline-block {Ð display: inline-block !important;Ð }Ð@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md {Ð display: block !important;Ð }Ð table.visible-md {Ð display: table !important;Ð }Ð tr.visible-md {Ð display: table-row !important;Ð }Ð th.visible-md,Ð td.visible-md {Ð display: table-cell !important;Ð }Ð@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md-block {Ð display: block !important;Ð }Ð@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md-inline {Ð display: inline !important;Ð }Ð@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md-inline-block {Ð display: inline-block !important;Ð }Ð@media (min-width: 1200px) {Ð .visible-lg {Ð display: block !important;Ð }Ð table.visible-lg {Ð display: table !important;Ð }Ð tr.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-lg,Ð td.visible-lg {Ð display: table-cell !important;Ð }Ð@media (min-width: 1200px) {Ð .visible-lg-block {Ð display: block !important;Ð }Ð@media (min-width: 1200px) {Ð .visible-lg-inline {Ð display: inline !important;Ð }Ð@media (min-width: 1200px) {Ð .visible-lg-inline-block {Ð display: inline-block !important;Ð }ÐÐ @media (max-width: 767px) {Ð .hidden-xs {Ð display: none !important;Ð }ÐÐ @media (min-width: 768px) and (max-width: 991px) {Ð .hidden-sm {Ð display: none !important;Ð }Ð@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-md {Ð display: none !important;Ð }Ð@media (min-width: 1200px) {Ð .hidden-lg {Ð display: none !important;Ð }ÐÐvisible-print {Ð display: none !important;Ð@media print {Ð .visible-print {Ð display: block !important;Ð }Ð table.visible-print {Ð display: table !important;Ð }Ð tr.visible-print {Ð display: table-row !important;Ð }Ð th.visible-print,Ð td.visible-print {Ð display: table-cell !important;Ð }ÐÐvisible-print-block {Ð display: none !important;Ð@media print {Ð .visible-print-block {Ð display: block !important;Ð }ÐÐvisible-print-inline {Ð display: none !important;Ð@media print {Ð .visible-print-inline {Ð display: inline !important;Ð }ÐÐvisible-print-inline-block {Ð display: none !important;Ð@media print {Ð .visible-print-inline-block {Ð display: inline-block !important;Ð }Ð }@media print {Ð .hidden-print {Ð display: none !important;Ð }ÐÐ*# sourceMappingURL=bootstrap.css.map */Ð

public\assets\css\custom.css

.heading-size_image {ÐÖ &v–ã¢ g , –× ÷'F çCÐföçB×6—¦S¢ G ƒÐò¢ Ö &v–âÐ
bottom: 10px !important; */Ðext-align:center !important;Ð†V–v‡C¢ CW ,
important;ÐÐheading-size {ÐÖ &v–ã¢ ÓG , #‡ , –× ÷'F çCÐföçB×6—¦S¢ #7 ƒÐ
font-weight: bold; /* margin-bottom: 10px !important; */Ð†V–v‡C¢ CW ,
important;ÐÐtag-margin {ÐÖ &v–â×&–v‡C¢ ' , –× ÷'F çCÐÐtag-btn {Ð FF–æs¢ W ,
10px !important;ÐÐwhite-bg {Ð FF–æs¢ W , , W , , –× ÷'F çCÐÐall {Ð
margin: 0px !important;Ð FF–æs¢ W , –× ÷'F çCÐÐportfolio {Ð†V–v‡C¢ S ƒÐ
overflow-y: auto;ÐÖ &v–ã¢ ÓW ƒÐÐcart-table-wrap {Ð†V–v‡C¢ ## ƒÐ÷fW&fÆ÷r×ƒ¢
hidden;ÐÐCartHTML td {ÐfW'F–6 ÂÖ Æ–vã¢ F÷ ÐÐconfirm-modal .modal-header {Ð
padding: 15px;ÐÐconfirm-modal .modal-body {Ð& 6¶w&÷VæBÖ6öÆ÷#¢ G& ç7 &VçCÐÐ
.payment-option-icon {ÐÐmedia screen and (max-width:992px) {Ð
’æ'Fâä–æ7&V 6UFô6 'BÂ æ'FâäFV7&V 6UFô6 'B ÐÐdisplay: blockÐÐÐ

public\assets\css\customer.css

/* --- Global Settings --- */Ð, *::before, *::after {Ð box-sizing: border-box;ÐÐhtml, body {Ð height: 100%;Ð margin: 0;Ð padding: 0;ÐÐbody {Ð
font-family: 'Helvetica Neue', Helvetica, Arial, sans-serif;Ð background-color: #2e5a3d;Ð display: flex;Ð flex-direction: column;ÐÐ* --- Header (Fixed) --- */Ðheader-area {Ð position: fixed;Ð top: 0;Ð left: 0;Ð
width: 100%;Ð height: 180px; /* Adjust as needed */Ð z-index: 1000;Ð
background: #fff; /* Optional: set a background for the header */Ð display: flex;Ð align-items: center;Ð justify-content: center;ÐÐ* Logo section within header */Ðlogo-sec {Ð display: flex;Ð align-items: center;Ð
justify-content: center;ÐÐlogo-sec .logo img {Ð height: 180px; /* This can be adjusted; you might want a smaller value */Ð max-height: 120px; /* Responsive max height */Ð width: auto;Ð display: block;Ð margin: 0 auto 15px;ÐÐ* --- Main Page Container --- */Ðpage-container {Ð flex: 1;Ð
display: flex;Ð flex-direction: column;ÐÐ* Main content area below the fixed header */Ðwrapper-content {Ð flex: 1;Ð padding: 20px;Ð max-width: 1600px;Ð width: 100%;Ð margin: 0 auto;Ð /* Push content below header */Ð
margin-top: 180px; /* Should match the header height */ÐÐ* --- Content Pair (Cart and Products) --- */Ðcontent-pair {Ð display: flex;Ð flex-wrap: wrap;Ð gap: 30px;Ð justify-content: center;ÐÐ* --- Cart Section --- */Ðcart-section {Ð background: #fff;Ð padding: 15px;Ð border: 1px solid #ddd;Ð border-radius: 8px;Ð min-width: 350px;Ð max-width: 400px;ÐÐcart-section h5 {Ð margin-bottom: 15px;ÐÐ* --- Products Section --- */Ðproducts-section {Ð flex: 1;Ð max-width: 1000px;ÐÐ* Category Navigation */Ð
.category-nav {Ð margin-bottom: 20px;ÐÐcategory-btn {Ð margin-right: 10px;Ð
margin-bottom: 10px;ÐÐcategory-btn.active {Ð background-color: #27ae60;Ð
border-color: #27ae60;Ð color: #fff;ÐÐ* --- Product Item and Card --- */Ð
.product-item {Ð flex: 1 1 200px; /* Minimum width 200px */Ð max-width: 33%; /* Approximately 3 items per row (adjust as needed) */ÐÐproduct_list {Ð
background: #fcfcfc;Ð border: 1px solid #eaeaea;Ð border-radius: 8px;Ð
padding: 20px;Ð margin-bottom: 20px;Ð transition: box-shadow 0.3s ease;Ð min-height: 320px;Ð width: 100%;Ð display: flex;Ð flex-direction: column;Ð align-items: center;Ð justify-content: space-between;ÐÐ
.product_list:hover {Ð box-shadow: 0 4px 20px rgba(0,0,0,0.1);ÐÐ
.product_list img {Ð width: 150px;Ð height: 150px;Ð object-fit: cover;Ð
border-radius: 50%;Ð margin-bottom: 10px;Ð transition: transform 0.3s ease;ÐÐproduct_list img:hover {Ð transform: scale(1.05);ÐÐ* Ensure the entire product card is clickable */ÐAddToCart {Ð cursor: pointer;ÐÐ* --- Footer --- */Ðfooter {Ð background-color: #f1f1f1;Ð font-size: 12px;Ð
color: #666;Ð text-align: center;Ð padding: 10px 0;Ð margin-top: auto; /* Push footer to bottom if content is short */ÐÐ* --- Utility Elements --- */Ðquantity-input {Ð width: 60px;Ð text-align: center;ÐÐ
h4, .TotalAmount {Ð font-size: 16px;Ð font-weight: 600;ÐÐ* Modal tweaks (if needed) */Ðmodal-content {Ð padding: 20px;ÐÐmodal-body h4 {Ð font-size: 20px;Ð font-weight: 600;ÐÐ

public\assets\css\plugins\awesome-bootstrap-checkbox\awesome-bootstrap-checkbox.css

.checkbox {Ð padding-left: 20px;ÞÐcheckbox label {Ð display: inline-block;Ð vertical-align: middle;Ð position: relative;Ð padding-left: 5px;ÞÐcheckbox label::before {Ð content: "";Ð display: inline-block;Ð position: absolute;Ð width: 17px;Ð height: 17px;Ð left: 0;Ð margin-left: -20px;Ð border: 1px solid #cccccc;Ð border-radius: 3px;Ð background-color: #fff;Ð -webkit-transition: border 0.15s ease-in-out, color 0.15s ease-in-out;Ð -o-transition: border 0.15s ease-in-out, color 0.15s ease-in-out;Ð transition: border 0.15s ease-in-out, color 0.15s ease-in-out;ÞÐcheckbox label::after {Ð display: inline-block;Ð position: absolute;Ð width: 16px;Ð height: 16px;Ð left: 0;Ð top: 0;Ð margin-left: -20px;Ð padding-left: 3px;Ð padding-top: 1px;Ð font-size: 11px;Ð color: #555555;ÞÐcheckbox input[type="checkbox"],Ðcheckbox input[type="radio"] {Ð opacity: 0;Ð z-index: 1;ÞÐcheckbox input[type="checkbox"]:focus + label::before,Ðcheckbox input[type="radio"]:focus + label::before {Ð outline: thin dotted;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÞÐcheckbox input[type="checkbox"]:checked + label::after,Ðcheckbox input[type="radio"]:checked + label::after {Ð font-family: "FontAwesome";Ð content: "\f00c";ÞÐcheckbox input[type="checkbox"]:disabled + label,Ðcheckbox input[type="radio"]:disabled + label {Ð opacity: 0.65;ÞÐcheckbox input[type="checkbox"]:disabled + label::before,Ðcheckbox input[type="radio"]:disabled + label::before {Ð background-color: #eeeeee;Ð cursor: not-allowed;ÞÐcheckbox.checkbox-circle label::before {Ð border-radius: 50%;ÞÐcheckbox.checkbox-inline {Ð margin-top: 0;ÞÐcheckbox-primary input[type="checkbox"]:checked + label::before,Ðcheckbox-primary input[type="radio"]:checked + label::before {Ð background-color: #337ab7;Ð border-color: #337ab7;ÞÐcheckbox-primary input[type="checkbox"]:checked + label::after,Ðcheckbox-primary input[type="radio"]:checked + label::after {Ð color: #fff;ÞÐcheckbox-danger input[type="checkbox"]:checked + label::before,Ð .checkbox-danger input[type="radio"]:checked + label::before {Ð background-color: #d9534f;Ð border-color: #d9534f;ÞÐcheckbox-danger input[type="checkbox"]:checked + label::after,Ðcheckbox-danger input[type="radio"]:checked + label::after {Ð color: #fff;ÞÐcheckbox-info input[type="checkbox"]:checked + label::before,Ðcheckbox-info input[type="radio"]:checked + label::before {Ð background-color: #5bc0de;Ð border-color: #5bc0de;ÞÐcheckbox-info input[type="checkbox"]:checked + label::after,Ðcheckbox-info input[type="radio"]:checked + label::after {Ð color: #fff;ÞÐcheckbox-warning input[type="checkbox"]:checked + label::before,Ð .checkbox-warning input[type="radio"]:checked + label::before {Ð background-color: #f0ad4e;Ð border-color: #f0ad4e;ÞÐcheckbox-warning input[type="checkbox"]:checked + label::after,Ðcheckbox-warning input[type="radio"]:checked + label::after {Ð color: #fff;ÞÐcheckbox-success input[type="checkbox"]:checked + label::before,Ðcheckbox-success input[type="radio"]:checked + label::before {Ð background-color: #5cb85c;Ð border-color: #5cb85c;ÞÐcheckbox-success input[type="checkbox"]:checked + label::after,Ðcheckbox-success input[type="radio"]:checked + label::after {Ð color: #fff;ÞÐradio {Ð padding-left: 20px;ÞÐradio label {Ð display: inline-block;Ð vertical-align: middle;Ð position: relative;Ð padding-left: 5px;ÞÐ .radio label::before {Ð content: "";Ð display: inline-block;Ð position: absolute;Ð width: 17px;Ð height: 17px;Ð left: 0;Ð margin-left: -20px;Ð border: 1px solid #cccccc;Ð border-radius: 50%;Ð background-color: #fff;Ð -webkit-transition: border 0.15s ease-in-out;Ð -o-transition: border 0.15s ease-in-out;Ð transition: border 0.15s ease-in-out;ÞÐradio label::after {Ð display: inline-block;Ð position: absolute;Ð content: " ";Ð width: 11px;Ð height: 11px;Ð left: 3px;Ð top: 3px;Ð margin-left: -20px;Ð border-radius: 50%;Ð background-color: #555555;Ð -webkit-transform: scale(0, 0);Ð -ms-transform: scale(0, 0);Ð -o-transform: scale(0, 0);Ð transform: scale(0, 0);Ð -webkit-transition: -webkit-transform 0.1s cubic-bezier(0.8, -0.33, 0.2, 1.33);Ð -moz-transition: -moz-transform 0.1s cubic-bezier(0.8, -0.33, 0.2, 1.33);Ð

```
                                                                    -o-
transition: -o-transform 0.1s cubic-bezier(0.8, -0.33, 0.2, 1.33);Đ
transition: transform 0.1s cubic-bezier(0.8, -0.33, 0.2, 1.33);ÞÞradio
input[type="radio"] {Đ opacity: 0;Đ z-index: 1;ÞÞradio
input[type="radio"]:focus + label::before {Đ outline: thin dotted;Đ outline:
5px auto -webkit-focus-ring-color;Đ outline-offset: -2px;ÞÞradio
input[type="radio"]:checked + label::after {Đ -webkit-transform: scale(1, 1);Đ
  -ms-transform: scale(1, 1);Đ -o-transform: scale(1, 1);Đ transform:
scale(1, 1);ÞÞradio input[type="radio"]:disabled + label {Đ opacity: 0.65;ÞÞ
.radio input[type="radio"]:disabled + label::before {Đ cursor: not-allowed;ÞÞ
.radio.radio-inline {Đ margin-top: 0;ÞÞradio-primary input[type="radio"] +
label::after {Đ background-color: #337ab7;ÞÞradio-primary
input[type="radio"]:checked + label::before {Đ border-color: #337ab7;ÞÞradio-
primary input[type="radio"]:checked + label::after {Đ background-color:
#337ab7;ÞÞradio-danger input[type="radio"] + label::after {Đ background-
color: #d9534f;ÞÞradio-danger input[type="radio"]:checked + label::before {Đ
border-color: #d9534f;ÞÞradio-danger input[type="radio"]:checked +
label::after {Đ background-color: #d9534f;ÞÞradio-info input[type="radio"] +
label::after {Đ background-color: #5bc0de;ÞÞradio-info
input[type="radio"]:checked + label::before {Đ border-color: #5bc0de;ÞÞradio-
info input[type="radio"]:checked + label::after {Đ background-color: #5bc0de;ÞÞ
.radio-warning input[type="radio"] + label::after {Đ background-color:
#f0ad4e;ÞÞradio-warning input[type="radio"]:checked + label::before {Đ border-
color: #f0ad4e;ÞÞradio-warning input[type="radio"]:checked + label::after {Đ
background-color: #f0ad4e;ÞÞradio-success input[type="radio"] + label::after {Đ
  background-color: #5cb85c;ÞÞradio-success input[type="radio"]:checked +
label::before {Đ border-color: #5cb85c;ÞÞradio-success
input[type="radio"]:checked + label::after {Đ background-color: #5cb85c;ÞÞ
input[type="checkbox"].styled:checked + label:after,Đ
input[type="radio"].styled:checked + label:after {Đ font-family:
'FontAwesome';Đ content: "\f00c";ÞÞinput[type="checkbox"] .styled:checked +
label::before,Đinput[type="radio"] .styled:checked + label::before {Đ color:
#fff;ÞÞinput[type="checkbox"] .styled:checked + label::after,Đ
input[type="radio"] .styled:checked + label::after {Đ color: #fff;ÞÞ
```

public\assets\css\plugins\blueimp\css\blueimp-gallery-indicator.css

```
@charset "UTF-8";Ð*Ð* blueimp Gallery Indicator CSS 1.1.0Ð* https://
github.com/blueimp/GalleryÐ*Ð* Copyright 2013, Sebastian TschanÐ* https://
blueimp.netÐ*Ð* Licensed under the MIT license:Ð* http://www.opensource.org/
licenses/MITÐ*/ÐÐblueimp-gallery > .indicator {Ð position: absolute;Ð top:
auto;Ð right: 15px;Ð bottom: 15px;Ð left: 15px;Ð margin: 0 40px;Ð padding: 0;Ð
  list-style: none;Ð text-align: center;Ð line-height: 10px;Ð display: none;ÐÞÐ
.blueimp-gallery > .indicator > li {Ð display: inline-block;Ð width: 9px;Ð
height: 9px;Ð margin: 6px 3px 0 3px;Ð -webkit-box-sizing: content-box;Ð    -
moz-box-sizing: content-box;Ð         box-sizing: content-box;Ð border: 1px
solid transparent;Ð background: #ccc;Ð background: rgba(255, 255, 255, 0.25)
center no-repeat;Ð border-radius: 5px;Ð box-shadow: 0 0 2px #000;Ð opacity:
0.5;Ð cursor: pointer;ÐÞÐblueimp-gallery > .indicator > li:hover,Ðblueimp-
gallery > .indicator > .active {Ð background-color: #fff;Ð border-color: #fff;Ð
  opacity: 1;ÐÞÐblueimp-gallery-controls > .indicator {Ð display: block;Ð /*
Fix z-index issues (controls behind slide element) on Android: */Ð -webkit-
transform: translateZ(0);Ð    -moz-transform: translateZ(0);Ð     -ms-
transform: translateZ(0);Ð      -o-transform: translateZ(0);Ð
transform: translateZ(0);ÐÞÐblueimp-gallery-single > .indicator {Ð display:
none;ÐÞÐblueimp-gallery > .indicator {Ð -webkit-user-select: none;Ð  -khtml-
user-select: none;Ð    -moz-user-select: none;Ð     -ms-user-select: none;Ð
          user-select: none;ÐÞÐ* IE7 fixes */Ð+html .blueimp-gallery
> .indicator > li {Ð display: inline;ÐÞÐ
```

public\assets\css\plugins\blueimp\css\blueimp-gallery-video.css

@charset "UTF-8";Ð*Ð* blueimp Gallery Video Factory CSS 1.3.0Ð* https://github.com/blueimp/GalleryÐ*Ð* Copyright 2013, Sebastian TschanÐ* https://blueimp.netÐ*Ð* Licensed under the MIT license:Ð* http://www.opensource.org/licenses/MITÐ*/Ðblueimp-gallery > .slides > .slide > .video-content > img {Ð position: absolute;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð margin: auto;Ð width: auto;Ð height: auto;Ð max-width: 100%;Ð max-height: 100%;Ð /* Prevent artifacts in Mozilla Firefox: */Ð -moz-backface-visibility: hidden;ÐÐblueimp-gallery > .slides > .slide > .video-content > video {Ð position: absolute;Ð top: 0;Ð left: 0;Ð width: 100%;Ð height: 100%;ÐÐblueimp-gallery > .slides > .slide > .video-content > iframe {Ð position: absolute;Ð top: 100%;Ð left: 0;Ð width: 100%;Ð height: 100%;Ð border: none;ÐÐblueimp-gallery > .slides > .slide > .video-playing > iframe {Ð top: 0;ÐÐblueimp-gallery > .slides > .slide > .video-content > a {Ð position: absolute;Ð top: 50%;Ð right: 0;Ð left: 0;Ð margin: -64px auto 0;Ð width: 128px;Ð height: 128px;Ð background: url(../img/video-play.png) center no-repeat;Ð opacity: 0.8;Ð cursor: pointer;ÐÐ .blueimp-gallery > .slides > .slide > .video-content > a:hover {Ð opacity: 1;ÐÐ .blueimp-gallery > .slides > .slide > .video-playing > a,Ðblueimp-gallery > .slides > .slide > .video-playing > img {Ð display: none;ÐÐblueimp-gallery > .slides > .slide > .video-content > video {Ð display: none;ÐÐblueimp-gallery > .slides > .slide > .video-playing > video {Ð display: block;ÐÐ .blueimp-gallery > .slides > .slide > .video-loading > a {Ð background: url(../img/loading.gif) center no-repeat;Ð background-size: 64px 64px;ÐÐ* Replace PNGs with SVGs for capable browsers (excluding IE<9) */Ðbody:last-child .blueimp-gallery > .slides > .slide > .video-content:not(.video-loading) > a {Ð background-image: url(../img/video-play.svg);ÐÐ* IE7 fixes */Ð *+html .blueimp-gallery > .slides > .slide > .video-content {Ð height: 100%;ÐÐ *+html .blueimp-gallery > .slides > .slide > .video-content > a {Ð left: 50%;Ð margin-left: -64px;ÐÐ

public\assets\css\plugins\blueimp\css\blueimp-gallery.css

@charset "UTF-8";Ð*Ð* blueimp Gallery CSS 2.11.1Ð* https://github.com/blueimp/GalleryÐ*Ð* Copyright 2013, Sebastian TschanÐ* https://blueimp.netÐ*Ð* Licensed under the MIT license:Ð* http://www.opensource.org/licenses/MITÐ*/Ð .blueimp-gallery,Ðblueimp-gallery > .slides > .slide > .slide-content {Ð position: absolute;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð /* Prevent artifacts in Mozilla Firefox: */Ð -moz-backface-visibility: hidden;ÐÐblueimp-gallery > .slides > .slide > .slide-content {Ð margin: auto;Ð width: auto;Ð height: auto;Ð max-width: 100%;Ð max-height: 100%;Ð opacity: 1;ÐÐblueimp-gallery {Ð position: fixed;Ð z-index: 999999;Ð overflow: hidden;Ð background: #000;Ð background: rgba(0, 0, 0, 0.9);Ð opacity: 0;Ð display: none;Ð direction: ltr;Ð -ms-touch-action: none;Ð touch-action: none;ÐÐblueimp-gallery-carousel {Ð position: relative;Ð z-index: auto;Ð margin: 1em auto;Ð /* Set the carousel width/height ratio to 16/9: */Ð padding-bottom: 56.25%;Ð box-shadow: 0 0 10px #000;Ð -ms-touch-action: pan-y;Ð touch-action: pan-y;ÐÐ .blueimp-gallery-display {Ð display: block;Ð opacity: 1;ÐÐblueimp-gallery > .slides {Ð position: relative;Ð height: 100%;Ð overflow: hidden;ÐÐblueimp-gallery-carousel > .slides {Ð position: absolute;ÐÐblueimp-gallery > .slides > .slide {Ð position: relative;Ð float: left;Ð height: 100%;Ð text-align: center;Ð -webkit-transition-timing-function: cubic-bezier(0.645, 0.045, 0.355, 1.000); Ð -moz-transition-timing-function: cubic-bezier(0.645, 0.045, 0.355, 1.000); Ð -ms-transition-timing-function: cubic-bezier(0.645, 0.045, 0.355, 1.000); Ð -o-transition-timing-function: cubic-bezier(0.645, 0.045, 0.355, 1.000); Ð transition-timing-function: cubic-bezier(0.645, 0.045, 0.355, 1.000);ÐÐblueimp-gallery,Ðblueimp-gallery > .slides > .slide > .slide-content {Ð -webkit-transition: opacity 0.5s linear;Ð -moz-transition: opacity 0.5s linear;Ð -ms-transition: opacity 0.5s linear;Ð -o-transition: opacity 0.5s linear;Ð transition: opacity 0.5s linear;ÐÐblueimp-gallery > .slides > .slide-loading {Ð background: url(../img/loading.gif) center no-repeat;Ð background-size: 64px 64px;ÐÐblueimp-gallery > .slides > .slide-loading > .slide-content {Ð opacity: 0;ÐÐblueimp-gallery > .slides > .slide-error {Ð background: url(../img/error.png) center no-repeat;ÐÐblueimp-gallery > .slides > .slide-error > .slide-content {Ð display: none;ÐÐblueimp-gallery > .prev,Ðblueimp-gallery > .next {Ð position: absolute;Ð top: 50%;Ð left: 15px;Ð width: 40px;Ð height: 40px;Ð margin-top: -23px;Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 60px;Ð font-weight: 100;Ð line-height: 30px;Ð color: #fff;Ð text-decoration: none;Ð text-shadow: 0 0 2px #000;Ð text-align: center;Ð background: #222;Ð background: rgba(0, 0, 0, 0.5);Ð -webkit-box-sizing: content-box;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;Ð border: 3px solid #fff;Ð -webkit-border-radius: 23px;Ð -moz-border-radius: 23px;Ð border-radius: 23px;Ð opacity: 0.5;Ð cursor: pointer;Ð display: none;ÐÐblueimp-gallery > .next {Ð left: auto;Ð right: 15px;ÐÐblueimp-gallery > .close,Ðblueimp-gallery > .title {Ð position: absolute;Ð top: 15px;Ð left: 15px;Ð margin: 0 40px 0 0;Ð font-size: 20px;Ð line-height: 30px;Ð color: #fff;Ð text-shadow: 0 0 2px #000;Ð opacity: 0.8;Ð display: none;ÐÐ .blueimp-gallery > .close {Ð padding: 15px;Ð right: 15px;Ð left: auto;Ð margin: -15px;Ð font-size: 30px;Ð text-decoration: none;Ð cursor: pointer;ÐÐ .blueimp-gallery > .play-pause {Ð position: absolute;Ð right: 15px;Ð bottom: 15px;Ð width: 15px;Ð height: 15px;Ð background: url(../img/play-pause.png) 0 0 no-repeat;Ð cursor: pointer;Ð opacity: 0.5;Ð display: none;ÐÐblueimp-gallery-playing > .play-pause {Ð background-position: -15px 0;ÐÐblueimp-gallery > .prev:hover,Ðblueimp-gallery > .next:hover,Ðblueimp-gallery > .close:hover,Ðblueimp-gallery > .title:hover,Ðblueimp-gallery > .play-pause:hover {Ð color: #fff;Ð opacity: 1;ÐÐblueimp-gallery-controls > .prev,Ð .blueimp-gallery-controls > .next,Ðblueimp-gallery-controls > .close,Ðblueimp-gallery-controls > .title,Ðblueimp-gallery-controls > .play-pause {Ð display: block;Ð /* Fix z-index issues (controls behind slide element) on Android: */Ð -webkit-transform: translateZ(0);Ð -moz-transform: translateZ(0);Ð -ms-transform: translateZ(0);Ð

```
                                    -o-transform: translateZ(0);Ð
transform: translateZ(0);ÞÐblueimp-gallery-single > .prev,Ðblueimp-gallery-
left > .prev,Ðblueimp-gallery-single > .next,Ðblueimp-gallery-right > .next,Ð
.blueimp-gallery-single > .play-pause {Ð display: none;ÞÐblueimp-gallery
> .slides > .slide > .slide-content,Ðblueimp-gallery > .prev,Ðblueimp-gallery
> .next,Ðblueimp-gallery > .close,Ðblueimp-gallery > .play-pause {Ð -webkit-
user-select: none;Ð  -khtml-user-select: none;Ð    -moz-user-select: none;Ð
      -ms-user-select: none;Ð         user-select: none;ÞÐ* Replace PNGs with
SVGs for capable browsers (excluding IE<9) */Ðbody:last-child .blueimp-gallery
> .slides > .slide-error {Ð background-image: url(../img/error.svg);ÞÐ
body:last-child .blueimp-gallery > .play-pause {Ð width: 20px;Ð height: 20px;Ð
  background-size: 40px 20px;Ð background-image: url(../img/play-pause.svg);ÞÐ
body:last-child .blueimp-gallery-playing > .play-pause {Ð background-
position: -20px 0;ÞÐ* IE7 fixes */Ð+html .blueimp-gallery > .slides > .slide {Ð
  min-height: 300px;ÞÐ+html .blueimp-gallery > .slides > .slide > .slide-
content {Ð position: relative;ÞÐ
```

public\assets\css\plugins\blueimp\css\demo.css

```
/*Ð* blueimp Gallery Demo CSS 2.0.0Ð* https://github.com/blueimp/GalleryÐ*Ð*
Copyright 2013, Sebastian TschanÐ* https://blueimp.netÐ*Ð* Licensed under the
MIT license:Ð* http://www.opensource.org/licenses/MITÐ*/Ðbody {Ð max-width:
750px;Ð margin: 0 auto;Ð padding: 1em;Ð font-family: 'Lucida Grande', 'Lucida
Sans Unicode', Arial, sans-serif;Ð font-size: 1em;Ð line-height: 1.4em;Ð
background: #222;Ð color: #fff;Ð -webkit-text-size-adjust: 100%;Ð     -ms-
text-size-adjust: 100%;ÐÐa {Ð color: orange;Ð text-decoration: none;ÐÐimg {Ð
border: 0;Ð vertical-align: middle;ÐÐh1 {Ð line-height: 1em;ÐÐh2,Ðlinks {Ð text-
align: center;ÐÐ@media (min-width: 481px) {Ð .navigation {Ð   list-style: none;Ð
    padding: 0;Ð }Ð .navigation li {Ð   display: inline-block;Ð }Ð
  .navigation li:not(:first-child):before {Ð   content: '| ';Ð }ÐÐ
```

public\assets\css\plugins\bootstrap-rtl\bootstrap-rtl.css

```
/*****************************************************************************
**Ð*              bootstrap-rtl (version 3.3.1)Ð*      Author: Morteza
Ansarinia (http://github.com/morteza)Ð*  Created on: January 21,2015Ð*
Project: bootstrap-rtlÐ*   Copyright: Unlicensed Public DomainÐ***************
*****************************************************************/Ðhtml {Ð
direction: rtl;ÐÐbody {Ð direction: rtl;ÐÐlist-unstyled {Ð padding-right: 0;Ð
padding-left: initial;ÐÐlist-inline {Ð padding-right: 0;Ð padding-left:
initial;Ð margin-right: -5px;Ð margin-left: 0;ÐÐdd {Ð margin-right: 0;Ð margin-
left: initial;ÐÐ@media (min-width: 768px) {Ð .dl-horizontal dt {Ð   float:
right;Ð   clear: right;Ð   text-align: left;Ð }Ð .dl-horizontal dd {Ð
margin-right: 180px;Ð   margin-left: 0;Ð }ÐÐblockquote {Ð border-right: 5px
solid #eeeeee;Ð border-left: 0;ÐÐblockquote-reverse,Ðblockquote.pull-left {Ð
padding-left: 15px;Ð padding-right: 0;Ð border-left: 5px solid #eeeeee;Ð
border-right: 0;Ð text-align: left;ÐÐcol-xs-1, .col-sm-1, .col-md-1, .col-
lg-1, .col-xs-2, .col-sm-2, .col-md-2, .col-lg-2, .col-xs-3, .col-sm-3, .col-
md-3, .col-lg-3, .col-xs-4, .col-sm-4, .col-md-4, .col-lg-4, .col-xs-5, .col-
sm-5, .col-md-5, .col-lg-5, .col-xs-6, .col-sm-6, .col-md-6, .col-lg-6, .col-
xs-7, .col-sm-7, .col-md-7, .col-lg-7, .col-xs-8, .col-sm-8, .col-md-8, .col-
lg-8, .col-xs-9, .col-sm-9, .col-md-9, .col-lg-9, .col-xs-10, .col-
sm-10, .col-md-10, .col-lg-10, .col-xs-11, .col-sm-11, .col-md-11, .col-
lg-11, .col-xs-12, .col-sm-12, .col-md-12, .col-lg-12 {Ð position: relative;Ð
min-height: 1px;Ð padding-left: 15px;Ð padding-right: 15px;ÐÐcol-xs-1, .col-
xs-2, .col-xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8, .col-
xs-9, .col-xs-10, .col-xs-11, .col-xs-12 {Ð float: right;ÐÐcol-xs-12 {Ð
width: 100%;ÐÐcol-xs-11 {Ð width: 91.66666667%;ÐÐcol-xs-10 {Ð width:
83.33333333%;ÐÐcol-xs-9 {Ð width: 75%;ÐÐcol-xs-8 {Ð width: 66.66666667%;ÐÐcol-
xs-7 {Ð width: 58.33333333%;ÐÐcol-xs-6 {Ð width: 50%;ÐÐcol-xs-5 {Ð width:
41.66666667%;ÐÐcol-xs-4 {Ð width: 33.33333333%;ÐÐcol-xs-3 {Ð width: 25%;ÐÐcol-
xs-2 {Ð width: 16.66666667%;ÐÐcol-xs-1 {Ð width: 8.33333333%;ÐÐcol-xs-pull-12
{Ð left: 100%;Ð right: auto;ÐÐcol-xs-pull-11 {Ð left: 91.66666667%;Ð right:
auto;ÐÐcol-xs-pull-10 {Ð left: 83.33333333%;Ð right: auto;ÐÐcol-xs-pull-9 {Ð
left: 75%;Ð right: auto;ÐÐcol-xs-pull-8 {Ð left: 66.66666667%;Ð right: auto;ÐÐ
.col-xs-pull-7 {Ð left: 58.33333333%;Ð right: auto;ÐÐcol-xs-pull-6 {Ð left:
50%;Ð right: auto;ÐÐcol-xs-pull-5 {Ð left: 41.66666667%;Ð right: auto;ÐÐcol-
xs-pull-4 {Ð left: 33.33333333%;Ð right: auto;ÐÐcol-xs-pull-3 {Ð left: 25%;Ð
right: auto;ÐÐcol-xs-pull-2 {Ð left: 16.66666667%;Ð right: auto;ÐÐcol-xs-
pull-1 {Ð left: 8.33333333%;Ð right: auto;ÐÐcol-xs-pull-0 {Ð left: auto;Ð
right: auto;ÐÐcol-xs-push-12 {Ð right: 100%;Ð left: 0;ÐÐcol-xs-push-11 {Ð
right: 91.66666667%;Ð left: 0;ÐÐcol-xs-push-10 {Ð right: 83.33333333%;Ð left:
0;ÐÐcol-xs-push-9 {Ð right: 75%;Ð left: 0;ÐÐcol-xs-push-8 {Ð right:
66.66666667%;Ð left: 0;ÐÐcol-xs-push-7 {Ð right: 58.33333333%;Ð left: 0;ÐÐcol-
xs-push-6 {Ð right: 50%;Ð left: 0;ÐÐcol-xs-push-5 {Ð right: 41.66666667%;Ð
left: 0;ÐÐcol-xs-push-4 {Ð right: 33.33333333%;Ð left: 0;ÐÐcol-xs-push-3 {Ð
right: 25%;Ð left: 0;ÐÐcol-xs-push-2 {Ð right: 16.66666667%;Ð left: 0;ÐÐcol-
xs-push-1 {Ð right: 8.33333333%;Ð left: 0;ÐÐcol-xs-push-0 {Ð right: auto;Ð
left: 0;ÐÐcol-xs-offset-12 {Ð margin-right: 100%;Ð margin-left: 0;ÐÐcol-xs-
offset-11 {Ð margin-right: 91.66666667%;Ð margin-left: 0;ÐÐcol-xs-offset-10 {Ð
  margin-right: 83.33333333%;Ð margin-left: 0;ÐÐcol-xs-offset-9 {Ð margin-
right: 75%;Ð margin-left: 0;ÐÐcol-xs-offset-8 {Ð margin-right: 66.66666667%;Ð
margin-left: 0;ÐÐcol-xs-offset-7 {Ð margin-right: 58.33333333%;Ð margin-left:
0;ÐÐcol-xs-offset-6 {Ð margin-right: 50%;Ð margin-left: 0;ÐÐcol-xs-offset-5 {Ð
  margin-right: 41.66666667%;Ð margin-left: 0;ÐÐcol-xs-offset-4 {Ð margin-
right: 33.33333333%;Ð margin-left: 0;ÐÐcol-xs-offset-3 {Ð margin-right: 25%;Ð
margin-left: 0;ÐÐcol-xs-offset-2 {Ð margin-right: 16.66666667%;Ð margin-left:
0;ÐÐcol-xs-offset-1 {Ð margin-right: 8.33333333%;Ð margin-left: 0;ÐÐcol-xs-
offset-0 {Ð margin-right: 0%;Ð margin-left: 0;ÐÐ@media (min-width: 768px) {Ð
  .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-
sm-7, .col-sm-8, .col-sm-9, .col-sm-10, .col-sm-11, .col-sm-12 {Ð   float:
right;Ð
```

}Ð .col-sm-12 {Ð width: 100%;Ð }Ð .col-sm-11 {Ð width: 91.66666667%;Ð }Ð .col-sm-10 {Ð width: 83.33333333%;Ð }Ð .col-sm-9 {Ð width: 75%;Ð }Ð .col-sm-8 {Ð width: 66.66666667%;Ð }Ð .col-sm-7 {Ð width: 58.33333333%;Ð }Ð .col-sm-6 {Ð width: 50%;Ð }Ð .col-sm-5 {Ð width: 41.66666667%;Ð }Ð .col-sm-4 {Ð width: 33.33333333%;Ð }Ð .col-sm-3 {Ð width: 25%;Ð }Ð .col-sm-2 {Ð width: 16.66666667%;Ð }Ð .col-sm-1 {Ð width: 8.33333333%;Ð }Ð .col-sm-pull-12 {Ð left: 100%;Ð right: auto;Ð }Ð .col-sm-pull-11 {Ð left: 91.66666667%;Ð right: auto;Ð }Ð .col-sm-pull-10 {Ð left: 83.33333333%;Ð right: auto;Ð }Ð .col-sm-pull-9 {Ð left: 75%;Ð right: auto;Ð }Ð .col-sm-pull-8 {Ð left: 66.66666667%;Ð right: auto;Ð }Ð .col-sm-pull-7 {Ð left: 58.33333333%;Ð right: auto;Ð }Ð .col-sm-pull-6 {Ð left: 50%;Ð right: auto;Ð }Ð .col-sm-pull-5 {Ð left: 41.66666667%;Ð right: auto;Ð }Ð .col-sm-pull-4 {Ð left: 33.33333333%;Ð right: auto;Ð }Ð .col-sm-pull-3 {Ð left: 25%;Ð right: auto;Ð }Ð .col-sm-pull-2 {Ð left: 16.66666667%;Ð right: auto;Ð }Ð .col-sm-pull-1 {Ð left: 8.33333333%;Ð right: auto;Ð }Ð .col-sm-pull-0 {Ð left: auto;Ð right: auto;Ð }Ð .col-sm-push-12 {Ð right: 100%;Ð left: 0;Ð }Ð .col-sm-push-11 {Ð right: 91.66666667%;Ð left: 0;Ð }Ð .col-sm-push-10 {Ð right: 83.33333333%;Ð left: 0;Ð }Ð .col-sm-push-9 {Ð right: 75%;Ð left: 0;Ð }Ð .col-sm-push-8 {Ð right: 66.66666667%;Ð left: 0;Ð }Ð .col-sm-push-7 {Ð right: 58.33333333%;Ð left: 0;Ð }Ð .col-sm-push-6 {Ð right: 50%;Ð left: 0;Ð }Ð .col-sm-push-5 {Ð right: 41.66666667%;Ð left: 0;Ð }Ð .col-sm-push-4 {Ð right: 33.33333333%;Ð left: 0;Ð }Ð .col-sm-push-3 {Ð right: 25%;Ð left: 0;Ð }Ð .col-sm-push-2 {Ð right: 16.66666667%;Ð left: 0;Ð }Ð .col-sm-push-1 {Ð right: 8.33333333%;Ð left: 0;Ð }Ð .col-sm-push-0 {Ð right: auto;Ð left: 0;Ð }Ð .col-sm-offset-12 {Ð margin-right: 100%;Ð margin-left: 0;Ð }Ð .col-sm-offset-11 {Ð margin-right: 91.66666667%;Ð margin-left: 0;Ð }Ð .col-sm-offset-10 {Ð margin-right: 83.33333333%;Ð margin-left: 0;Ð }Ð .col-sm-offset-9 {Ð margin-right: 75%;Ð margin-left: 0;Ð }Ð .col-sm-offset-8 {Ð margin-right: 66.66666667%;Ð margin-left: 0;Ð }Ð .col-sm-offset-7 {Ð margin-right: 58.33333333%;Ð margin-left: 0;Ð }Ð .col-sm-offset-6 {Ð margin-right: 50%;Ð margin-left: 0;Ð }Ð .col-sm-offset-5 {Ð margin-right: 41.66666667%;Ð margin-left: 0;Ð }Ð .col-sm-offset-4 {Ð margin-right: 33.33333333%;Ð margin-left: 0;Ð }Ð .col-sm-offset-3 {Ð margin-right: 25%;Ð margin-left: 0;Ð }Ð .col-sm-offset-2 {Ð margin-right: 16.66666667%;Ð margin-left: 0;Ð }Ð .col-sm-offset-1 {Ð margin-right: 8.33333333%;Ð margin-left: 0;Ð }Ð .col-sm-offset-0 {Ð margin-right: 0%;Ð margin-left: 0;Ð }ÐÐmedia (min-width: 992px) {Ð .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8, .col-md-9, .col-md-10, .col-md-11, .col-md-12 {Ð float: right;Ð }Ð .col-md-12 {Ð width: 100%;Ð }Ð .col-md-11 {Ð width: 91.66666667%;Ð }Ð .col-md-10 {Ð width: 83.33333333%;Ð }Ð .col-md-9 {Ð width: 75%;Ð }Ð .col-md-8 {Ð width: 66.66666667%;Ð }Ð .col-md-7 {Ð width: 58.33333333%;Ð }Ð .col-md-6 {Ð width: 50%;Ð }Ð .col-md-5 {Ð width: 41.66666667%;Ð }Ð .col-md-4 {Ð width: 33.33333333%;Ð }Ð .col-md-3 {Ð width: 25%;Ð }Ð .col-md-2 {Ð width: 16.66666667%;Ð }Ð .col-md-1 {Ð width: 8.33333333%;Ð }Ð .col-md-pull-12 {Ð left: 100%;Ð right: auto;Ð }Ð .col-md-pull-11 {Ð left: 91.66666667%;Ð right: auto;Ð }Ð .col-md-pull-10 {Ð left: 83.33333333%;Ð right: auto;Ð }Ð .col-md-pull-9 {Ð left: 75%;Ð right: auto;Ð }Ð .col-md-pull-8 {Ð left: 66.66666667%;Ð right: auto;Ð }Ð .col-md-pull-7 {Ð left: 58.33333333%;Ð right: auto;Ð }Ð .col-md-pull-6 {Ð left: 50%;Ð right: auto;Ð }Ð .col-md-pull-5 {Ð left: 41.66666667%;Ð right: auto;Ð }Ð .col-md-pull-4 {Ð left: 33.33333333%;Ð right: auto;Ð }Ð .col-md-pull-3 {Ð left: 25%;Ð right: auto;Ð }Ð .col-md-pull-2 {Ð left: 16.66666667%;Ð right: auto;Ð }Ð .col-md-pull-1 {Ð left: 8.33333333%;Ð right: auto;Ð }Ð .col-md-pull-0 {Ð left: auto;Ð right: auto;Ð }Ð .col-md-push-12 {Ð right: 100%;Ð left: 0;Ð }Ð .col-md-push-11 {Ð right: 91.66666667%;Ð left: 0;Ð }Ð .col-md-push-10 {Ð right: 83.33333333%;Ð left: 0;Ð }Ð .col-md-push-9 {Ð right: 75%;Ð left: 0;Ð }Ð .col-md-push-8 {Ð right: 66.66666667%;Ð

left: 0;Ð }Ð .col-md-push-7 {Ð right: 58.33333333%;Ð left: 0;Ð }Ð .col-md-push-6 {Ð right: 50%;Ð left: 0;Ð }Ð .col-md-push-5 {Ð right: 41.66666667%;Ð left: 0;Ð }Ð .col-md-push-4 {Ð right: 33.33333333%;Ð left: 0;Ð }Ð .col-md-push-3 {Ð right: 25%;Ð left: 0;Ð }Ð .col-md-push-2 {Ð right: 16.66666667%;Ð left: 0;Ð }Ð .col-md-push-1 {Ð right: 8.33333333%;Ð left: 0;Ð }Ð .col-md-push-0 {Ð right: auto;Ð left: 0;Ð }Ð .col-md-offset-12 {Ð margin-right: 100%;Ð margin-left: 0;Ð }Ð .col-md-offset-11 {Ð margin-right: 91.66666667%;Ð margin-left: 0;Ð }Ð .col-md-offset-10 {Ð margin-right: 83.33333333%;Ð margin-left: 0;Ð }Ð .col-md-offset-9 {Ð margin-right: 75%;Ð margin-left: 0;Ð }Ð .col-md-offset-8 {Ð margin-right: 66.66666667%;Ð margin-left: 0;Ð }Ð .col-md-offset-7 {Ð margin-right: 58.33333333%;Ð margin-left: 0;Ð }Ð .col-md-offset-6 {Ð margin-right: 50%;Ð margin-left: 0;Ð }Ð .col-md-offset-5 {Ð margin-right: 41.66666667%;Ð margin-left: 0;Ð }Ð .col-md-offset-4 {Ð margin-right: 33.33333333%;Ð margin-left: 0;Ð }Ð .col-md-offset-3 {Ð margin-right: 25%;Ð margin-left: 0;Ð }Ð .col-md-offset-2 {Ð margin-right: 16.66666667%;Ð margin-left: 0;Ð }Ð .col-md-offset-1 {Ð margin-right: 8.33333333%;Ð margin-left: 0;Ð }Ð .col-md-offset-0 {Ð margin-right: 0%;Ð margin-left: 0;Ð }ÐÐ@media (min-width: 1200px) {Ð .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-lg-6, .col-lg-7, .col-lg-8, .col-lg-9, .col-lg-10, .col-lg-11, .col-lg-12 {Ð float: right;Ð }Ð .col-lg-12 {Ð width: 100%;Ð }Ð .col-lg-11 {Ð width: 91.66666667%;Ð }Ð .col-lg-10 {Ð width: 83.33333333%;Ð }Ð .col-lg-9 {Ð width: 75%;Ð }Ð .col-lg-8 {Ð width: 66.66666667%;Ð }Ð .col-lg-7 {Ð width: 58.33333333%;Ð }Ð .col-lg-6 {Ð width: 50%;Ð }Ð .col-lg-5 {Ð width: 41.66666667%;Ð }Ð .col-lg-4 {Ð width: 33.33333333%;Ð }Ð .col-lg-3 {Ð width: 25%;Ð }Ð .col-lg-2 {Ð width: 16.66666667%;Ð }Ð .col-lg-1 {Ð width: 8.33333333%;Ð }Ð .col-lg-pull-12 {Ð left: 100%;Ð right: auto;Ð }Ð .col-lg-pull-11 {Ð left: 91.66666667%;Ð right: auto;Ð }Ð .col-lg-pull-10 {Ð left: 83.33333333%;Ð right: auto;Ð }Ð .col-lg-pull-9 {Ð left: 75%;Ð right: auto;Ð }Ð .col-lg-pull-8 {Ð left: 66.66666667%;Ð right: auto;Ð }Ð .col-lg-pull-7 {Ð left: 58.33333333%;Ð right: auto;Ð }Ð .col-lg-pull-6 {Ð left: 50%;Ð right: auto;Ð }Ð .col-lg-pull-5 {Ð left: 41.66666667%;Ð right: auto;Ð }Ð .col-lg-pull-4 {Ð left: 33.33333333%;Ð right: auto;Ð }Ð .col-lg-pull-3 {Ð left: 25%;Ð right: auto;Ð }Ð .col-lg-pull-2 {Ð left: 16.66666667%;Ð right: auto;Ð }Ð .col-lg-pull-1 {Ð left: 8.33333333%;Ð right: auto;Ð }Ð .col-lg-pull-0 {Ð left: auto;Ð right: auto;Ð }Ð .col-lg-push-12 {Ð right: 100%;Ð left: 0;Ð }Ð .col-lg-push-11 {Ð right: 91.66666667%;Ð left: 0;Ð }Ð .col-lg-push-10 {Ð right: 83.33333333%;Ð left: 0;Ð }Ð .col-lg-push-9 {Ð right: 75%;Ð left: 0;Ð }Ð .col-lg-push-8 {Ð right: 66.66666667%;Ð left: 0;Ð }Ð .col-lg-push-7 {Ð right: 58.33333333%;Ð left: 0;Ð }Ð .col-lg-push-6 {Ð right: 50%;Ð left: 0;Ð }Ð .col-lg-push-5 {Ð right: 41.66666667%;Ð left: 0;Ð }Ð .col-lg-push-4 {Ð right: 33.33333333%;Ð left: 0;Ð }Ð .col-lg-push-3 {Ð right: 25%;Ð left: 0;Ð }Ð .col-lg-push-2 {Ð right: 16.66666667%;Ð left: 0;Ð }Ð .col-lg-push-1 {Ð right: 8.33333333%;Ð left: 0;Ð }Ð .col-lg-push-0 {Ð right: auto;Ð left: 0;Ð }Ð .col-lg-offset-12 {Ð margin-right: 100%;Ð margin-left: 0;Ð }Ð .col-lg-offset-11 {Ð margin-right: 91.66666667%;Ð margin-left: 0;Ð }Ð .col-lg-offset-10 {Ð margin-right: 83.33333333%;Ð margin-left: 0;Ð }Ð .col-lg-offset-9 {Ð margin-right: 75%;Ð margin-left: 0;Ð }Ð .col-lg-offset-8 {Ð margin-right: 66.66666667%;Ð margin-left: 0;Ð }Ð .col-lg-offset-7 {Ð margin-right: 58.33333333%;Ð margin-left: 0;Ð }Ð .col-lg-offset-6 {Ð margin-right: 50%;Ð margin-left: 0;Ð }Ð .col-lg-offset-5 {Ð margin-right: 41.66666667%;Ð margin-left: 0;Ð }Ð .col-lg-offset-4 {Ð margin-right: 33.33333333%;Ð margin-left: 0;Ð }Ð .col-lg-offset-3 {Ð margin-right: 25%;Ð margin-left: 0;Ð }Ð .col-lg-offset-2 {Ð margin-right: 16.66666667%;Ð margin-left: 0;Ð }Ð .col-lg-offset-1 {Ð margin-right: 8.33333333%;Ð margin-left: 0;Ð }Ð .col-lg-offset-0 {Ð margin-right: 0%;Ð margin-left: 0;Ð }ÐÐcaption {Ð text-align: right;Ð }Ðth {Ð text-align: right;Ð

}Ð@media screen and (max-width: 767px) {Ð .table-responsive > .table-bordered {Ð border: 0;Ð }Ð .table-responsive > .table-bordered > thead > tr > th:first-child,Ð .table-responsive > .table-bordered > tbody > tr > th:first-child,Ð .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ð .table-responsive > .table-bordered > thead > tr > td:first-child,Ð .table-responsive > .table-bordered > tbody > tr > td:first-child,Ð .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-right: 0;Ð border-left: initial;Ð }Ð .table-responsive > .table-bordered > thead > tr > th:last-child,Ð .table-responsive > .table-bordered > tbody > tr > th:last-child,Ð .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ð .table-responsive > .table-bordered > thead > tr > td:last-child,Ð .table-responsive > .table-bordered > tbody > tr > td:last-child,Ð .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-left: 0;Ð border-right: initial;Ð }ÐÐradio label,Ðcheckbox label {Ð padding-right: 20px;Ð padding-left: initial;ÐÐradio input[type="radio"],Ð .radio-inline input[type="radio"],Ðcheckbox input[type="checkbox"],Ðcheckbox-inline input[type="checkbox"] {Ð margin-right: -20px;Ð margin-left: auto;ÐÐ .radio-inline,Ðcheckbox-inline {Ð padding-right: 20px;Ð padding-left: 0;ÐÐ .radio-inline + .radio-inline,Ðcheckbox-inline + .checkbox-inline {Ð margin-right: 10px;Ð margin-left: 0;ÐÐhas-feedback .form-control {Ð padding-left: 42.5px;Ð padding-right: 12px;ÐÐform-control-feedback {Ð left: 0;Ð right: auto;Ð }Ð@media (min-width: 768px) {Ð .form-inline label {Ð padding-right: 0;Ð padding-left: initial;Ð }Ð .form-inline .radio input[type="radio"],Ð .form-inline .checkbox input[type="checkbox"] {Ð margin-right: 0;Ð margin-left: auto;Ð }ÐÐ@media (min-width: 768px) {Ð .form-horizontal .control-label {Ð text-align: left;Ð }ÐÐform-horizontal .has-feedback .form-control-feedback {Ð left: 15px;Ð right: auto;ÐÐcaret {Ð margin-right: 2px;Ð margin-left: 0;ÐÐ .dropdown-menu {Ð right: 0;Ð left: auto;Ð float: left;Ð text-align: right;ÐÐ .dropdown-menu.pull-right {Ð left: 0;Ð right: auto;Ð float: right;ÐÐdropdown-menu-right {Ð left: auto;Ð right: 0;ÐÐdropdown-menu-left {Ð left: 0;Ð right: auto;ÐÐ@media (min-width: 768px) {Ð .navbar-right .dropdown-menu {Ð left: auto;Ð right: 0;Ð }Ð .navbar-right .dropdown-menu-left {Ð left: 0;Ð right: auto;Ð }ÐÐbtn-group > .btn,Ðbtn-group-vertical > .btn {Ð float: right;ÐÐ .btn-group .btn + .btn,Ðbtn-group .btn + .btn-group,Ðbtn-group .btn-group + .btn,Ðbtn-group .btn-group + .btn-group {Ð margin-right: -1px;Ð margin-left: 0px;ÐÐbtn-toolbar {Ð margin-right: -5px;Ð margin-left: 0px;ÐÐbtn-toolbar .btn-group,Ðbtn-toolbar .input-group {Ð float: right;ÐÐbtn-toolbar > .btn,Ðbtn-toolbar > .btn-group,Ðbtn-toolbar > .input-group {Ð margin-right: 5px;Ð margin-left: 0px;ÐÐbtn-group > .btn:first-child {Ð margin-right: 0;ÐÐ .btn-group > .btn:first-child:not(:last-child):not(.dropdown-toggle) {Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÐÐbtn-group > .btn:last-child:not(:first-child),Ðbtn-group > .dropdown-toggle:not(:first-child) {Ð border-top-left-radius: 4px;Ð border-bottom-left-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-top-right-radius: 0;ÐÐbtn-group > .btn-group {Ð float: right;ÐÐbtn-group.btn-group-justified > .btn,Ðbtn-group.btn-group-justified > .btn-group {Ð float: none;ÐÐbtn-group > .btn-group:not(:first-child):not(:last-child) > .btn {Ð border-radius: 0;ÐÐbtn-group > .btn-group:first-child > .btn:last-child,Ðbtn-group > .btn-group:first-child > .dropdown-toggle {Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÐÐbtn-group > .btn-group:last-child > .btn:first-child {Ð border-top-left-radius: 4px;Ð border-bottom-left-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-top-right-radius: 0;ÐÐbtn .caret {Ð margin-right: 0;ÐÐbtn-group-vertical > .btn + .btn,Ðbtn-group-vertical > .btn + .btn-group,Ðbtn-group-vertical > .btn-group + .btn,Ðbtn-group-vertical > .btn-group + .btn-group {Ð margin-top: -1px;Ð margin-right: 0;ÐÐinput-group .form-control {Ð float: right;ÐÐ .input-group .form-control:first-child,Ðinput-group-addon:first-child,Ðinput-group-btn:first-child > .btn,Ðinput-group-btn:first-child > .btn-group > .btn,Ð .input-group-btn:first-child > .dropdown-toggle,Ð

.input-group-btn:last-child > .btn:not(:last-child):not(.dropdown-toggle),Ðinput-group-btn:last-child > .btn-group:not(:last-child) > .btn {Ð border-bottom-right-radius: 4px;Ð border-top-right-radius: 4px;Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÞÐinput-group-addon:first-child {Ð border-right-width: 1px;Ð border-right-style: solid;Ð border-left: 0px;ÞÐinput-group .form-control:last-child,Ð .input-group-addon:last-child,Ðinput-group-btn:last-child > .btn,Ðinput-group-btn:last-child > .btn-group > .btn,Ðinput-group-btn:last-child > .dropdown-toggle,Ðinput-group-btn:first-child > .btn:not(:first-child),Ðinput-group-btn:first-child > .btn-group:not(:first-child) > .btn {Ð border-bottom-left-radius: 4px;Ð border-top-left-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-top-right-radius: 0;ÞÐinput-group-addon:last-child {Ð border-left-width: 1px;Ð border-left-style: solid;Ð border-right: 0px;ÞÐinput-group-btn > .btn + .btn {Ð margin-right: -1px;Ð margin-left: auto;ÞÐinput-group-btn:first-child > .btn,Ðinput-group-btn:first-child > .btn-group {Ð margin-left: -1px;Ð margin-right: auto;ÞÐinput-group-btn:last-child > .btn,Ðinput-group-btn:last-child > .btn-group {Ð margin-right: -1px;Ð margin-left: auto;ÞÐ .nav {Ð padding-right: 0;Ð padding-left: initial;ÞÐnav-tabs > li {Ð float: right;ÞÐnav-tabs > li > a {Ð margin-left: auto;Ð margin-right: -2px;Ð border-radius: 4px 4px 0 0;ÞÐnav-pills > li {Ð float: right;ÞÐnav-pills > li > a {Ð border-radius: 4px;ÞÐnav-pills > li + li {Ð margin-right: 2px;Ð margin-left: auto;ÞÐnav-stacked > li {Ð float: none;ÞÐnav-stacked > li + li {Ð margin-right: 0;Ð margin-left: auto;ÞÐnav-justified > .dropdown .dropdown-menu {Ð right: auto;ÞÐnav-tabs-justified > li > a {Ð margin-left: 0;Ð margin-right: auto;Þ@media (min-width: 768px) {Ð .nav-tabs-justified > li > a {Ð border-radius: 4px 4px 0 0;Ð }Þ@media (min-width: 768px) {Ð .navbar-header {Ð float: right;Ð }ÞÐnavbar-collapse {Ð padding-right: 15px;Ð padding-left: 15px;Ð }Ðnavbar-brand {Ð float: right;Þ@media (min-width: 768px) {Ð .navbar > .container .navbar-brand,Ð .navbar > .container-fluid .navbar-brand {Ð margin-right: -15px;Ð margin-left: auto;Ð }ÞÐnavbar-toggle {Ð float: left;Ð margin-left: 15px;Ð margin-right: auto;Þ@media (max-width: 767px) {Ð .navbar-nav .open .dropdown-menu > li > a,Ð .navbar-nav .open .dropdown-menu .dropdown-header {Ð padding: 5px 25px 5px 15px;Ð }Þ@media (min-width: 768px) {Ð .navbar-nav {Ð float: right;Ð }Ð .navbar-nav > li {Ð float: right;Ð }Þ@media (min-width: 768px) {Ð .navbar-left.flip {Ð float: right !important;Ð }Ð .navbar-right:last-child {Ð margin-left: -15px;Ð margin-right: auto;Ð }Ð .navbar-right.flip {Ð float: left !important;Ð margin-left: -15px;Ð margin-right: auto;Ð }Ð .navbar-right .dropdown-menu {Ð left: 0;Ð right: auto;Ð }Þ@media (min-width: 768px) {Ð .navbar-text {Ð float: right;Ð }Ð .navbar-text.navbar-right:last-child {Ð margin-left: 0;Ð margin-right: auto;Ð }ÞÐpagination {Ð padding-right: 0;ÞÐpagination > li > a,Ðpagination > li > span {Ð float: right;Ð margin-right: -1px;Ð margin-left: 0px;ÞÐpagination > li:first-child > a,Ðpagination > li:first-child > span {Ð margin-left: 0;Ð border-bottom-right-radius: 4px;Ð border-top-right-radius: 4px;Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÞÐ .pagination > li:last-child > a,Ðpagination > li:last-child > span {Ð margin-right: -1px;Ð border-bottom-left-radius: 4px;Ð border-top-left-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-top-right-radius: 0;ÞÐpager {Ð padding-right: 0;Ð padding-left: initial;ÞÐpager .next > a,Ðpager .next > span {Ð float: left;ÞÐpager .previous > a,Ðpager .previous > span {Ð float: right;ÞÐ .nav-pills > li > a > .badge {Ð margin-left: 0px;Ð margin-right: 3px;ÞÐlist-group-item > .badge {Ð float: left;ÞÐlist-group-item > .badge + .badge {Ð margin-left: 5px;Ð margin-right: auto;ÞÐalert-dismissable,Ðalert-dismissible {Ð padding-left: 35px;Ð padding-right: 15px;ÞÐalert-dismissable .close,Ðalert-dismissible .close {Ð right: auto;Ð left: -21px;ÞÐprogress-bar {Ð float: right;ÞÐmedia > .pull-left {Ð margin-right: 10px;ÞÐmedia > .pull-left.flip {Ð margin-right: 0;Ð margin-left: 10px;ÞÐmedia > .pull-right {Ð margin-left: 10px;ÞÐmedia > .pull-right.flip {Ð margin-left: 0;Ð margin-right: 10px;ÞÐ .media-right,Ðmedia > .pull-right {Ð padding-right: 10px;Ð padding-left: initial;Ð

}Ðmedia-left,Ðmedia > .pull-left {Ð padding-left: 10px;Ð padding-right: initial;ÐÐmedia-list {Ð padding-right: 0;Ð padding-left: initial;Ð list-style: none;ÐÐlist-group {Ð padding-right: 0;Ð padding-left: initial;ÐÐ .panel > .table:first-child > thead:first-child > tr:first-child td:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child td:first-child,Ðpanel > .table:first-child > tbody:first-child > tr:first-child td:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child td:first-child,Ðpanel > .table:first-child > thead:first-child > tr:first-child th:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child th:first-child,Ð .panel > .table:first-child > tbody:first-child > tr:first-child th:first-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child th:first-child {Ð border-top-right-radius: 3px;Ð border-top-left-radius: 0;ÐÐpanel > .table:first-child > thead:first-child > tr:first-child td:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child td:last-child,Ð .panel > .table:first-child > tbody:first-child > tr:first-child td:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child td:last-child,Ðpanel > .table:first-child > thead:first-child > tr:first-child th:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > thead:first-child > tr:first-child th:last-child,Ðpanel > .table:first-child > tbody:first-child > tr:first-child th:last-child,Ðpanel > .table-responsive:first-child > .table:first-child > tbody:first-child > tr:first-child th:last-child {Ð border-top-left-radius: 3px;Ð border-top-right-radius: 0;ÐÐpanel > .table:last-child > tbody:last-child > tr:last-child td:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child td:first-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child td:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child td:first-child,Ðpanel > .table:last-child > tbody:last-child > tr:last-child th:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child th:first-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child th:first-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child th:first-child {Ð border-bottom-left-radius: 3px;Ð border-top-right-radius: 0;ÐÐpanel > .table:last-child > tbody:last-child > tr:last-child td:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child td:last-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child td:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child td:last-child,Ðpanel > .table:last-child > tbody:last-child > tr:last-child th:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tbody:last-child > tr:last-child th:last-child,Ðpanel > .table:last-child > tfoot:last-child > tr:last-child th:last-child,Ðpanel > .table-responsive:last-child > .table:last-child > tfoot:last-child > tr:last-child th:last-child {Ð border-bottom-right-radius: 3px;Ð border-top-left-radius: 0;ÐÐpanel > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-bordered > tfoot > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-right: 0;Ð border-left: none;ÐÐpanel > .table-bordered > thead > tr > th:last-child,Ð

.panel > .table-responsive > .table-bordered > thead > tr > th:last-child,Ðpanel > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-bordered > thead > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:last-child,Ðpanel > .table-bordered > tbody > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > td:last-child,Ðpanel > .table-bordered > tfoot > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-right: none;Ð border-left: 0;ÞÐembed-responsive .embed-responsive-item,Ðembed-responsive iframe,Ðembed-responsive embed,Ðembed-responsive object {Ð right: 0;Ð left: auto;ÞÐclose {Ð float: left;ÞÐmodal-footer {Ð text-align: left;ÞÐ .modal-footer .btn + .btn {Ð margin-left: auto;Ð margin-right: 5px;ÞÐmodal-footer .btn-group .btn + .btn {Ð margin-right: -1px;Ð margin-left: auto;ÞÐ .modal-footer .btn-block + .btn-block {Ð margin-right: 0;Ð margin-left: auto;ÞÐ .popover {Ð left: auto;Ð text-align: right;ÞÐpopover.top > .arrow {Ð right: 50%;Ð left: auto;Ð margin-right: -11px;Ð margin-left: auto;ÞÐpopover.top > .arrow:after {Ð margin-right: -10px;Ð margin-left: auto;ÞÐpopover.bottom > .arrow {Ð right: 50%;Ð left: auto;Ð margin-right: -11px;Ð margin-left: auto;Ð }Ðpopover.bottom > .arrow:after {Ð margin-right: -10px;Ð margin-left: auto;ÞÐ .carousel-control {Ð right: 0;Ð bottom: 0;ÞÐcarousel-control.left {Ð right: auto;Ð left: 0;Ð background-image: -webkit-linear-gradient(left, color-stop(rgba(0, 0, 0, 0.5) 0%), color-stop(rgba(0, 0, 0, 0.0001) 100%));Ð background-image: -o-linear-gradient(left, rgba(0, 0, 0, 0.5) 0%, rgba(0, 0, 0, 0.0001) 100%);Ð background-image: linear-gradient(to right, rgba(0, 0, 0, 0.5) 0%, rgba(0, 0, 0, 0.0001) 100%);Ð background-repeat: repeat-x;Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#80000000', endColorstr='#00000000', GradientType=1);ÞÐcarousel-control.right {Ð left: auto;Ð right: 0;Ð background-image: -webkit-linear-gradient(left, color-stop(rgba(0, 0, 0, 0.0001) 0%), color-stop(rgba(0, 0, 0, 0.5) 100%));Ð background-image: -o-linear-gradient(left, rgba(0, 0, 0, 0.0001) 0%, rgba(0, 0, 0, 0.5) 100%);Ð background-image: linear-gradient(to right, rgba(0, 0, 0, 0.0001) 0%, rgba(0, 0, 0, 0.5) 100%);Ð background-repeat: repeat-x;Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#00000000', endColorstr='#80000000', GradientType=1);ÞÐcarousel-control .icon-prev,Ð .carousel-control .glyphicon-chevron-left {Ð left: 50%;Ð right: auto;Ð margin-right: -10px;ÞÐcarousel-control .icon-next,Ðcarousel-control .glyphicon-chevron-right {Ð right: 50%;Ð left: auto;Ð margin-left: -10px;ÞÐcarousel-indicators {Ð right: 50%;Ð left: 0;Ð margin-right: -30%;Ð margin-left: 0;Ð padding-left: 0;ÞÐmedia screen and (min-width: 768px) {Ð .carousel-control .glyphicon-chevron-left,Ð .carousel-control .icon-prev {Ð margin-left: 0;Ð margin-right: -15px;Ð }Ð .carousel-control .glyphicon-chevron-right,Ð .carousel-control .icon-next {Ð margin-left: 0;Ð margin-right: -15px;Ð }Ð .carousel-caption {Ð left: 20%;Ð right: 20%;Ð padding-bottom: 30px;Ð }ÞÐpull-right.flip {Ð float: left !important;ÞÐpull-left.flip {Ð float: right !important;ÞØ*# sourceMappingURL=bootstrap-rtl.css.map */

public\assets\css\plugins\chartist\chartist.min.css

.ct-label {Ð fill: rgba(0, 0, 0, 0.4);Ð color: rgba(0, 0, 0, 0.4);Ð
font-size: 1rem;Ð line-height: 1;ÞÐct-chart-line .ct-label,Ðct-chart-
bar .ct-label {Ð display: block;Ð display: -webkit-box;Ð display: -moz-
box;Ð display: -ms-flexbox;Ð display: -webkit-flex;Ð display: flex;ÞÐct-
label.ct-horizontal.ct-start {Ð -webkit-box-align: flex-end;Ð -webkit-
align-items: flex-end;Ð -ms-flex-align: flex-end;Ð align-items: flex-end;Ð
    -webkit-box-pack: flex-start;Ð -webkit-justify-content: flex-start;Ð -
ms-flex-pack: flex-start;Ð justify-content: flex-start;Ð text-align: left;Ð
    text-anchor: start;ÞÐct-label.ct-horizontal.ct-end {Ð -webkit-box-
align: flex-start;Ð -webkit-align-items: flex-start;Ð -ms-flex-align:
flex-start;Ð align-items: flex-start;Ð -webkit-box-pack: flex-start;Ð -
webkit-justify-content: flex-start;Ð -ms-flex-pack: flex-start;Ð justify-
content: flex-start;Ð text-align: left;Ð text-anchor: start;ÞÐct-label.ct-
vertical.ct-start {Ð -webkit-box-align: flex-end;Ð -webkit-align-items:
flex-end;Ð -ms-flex-align: flex-end;Ð align-items: flex-end;Ð -webkit-
box-pack: flex-end;Ð -webkit-justify-content: flex-end;Ð -ms-flex-pack:
flex-end;Ð justify-content: flex-end;Ð text-align: right;Ð text-anchor:
end;ÞÐct-label.ct-vertical.ct-end {Ð -webkit-box-align: flex-end;Ð -
webkit-align-items: flex-end;Ð -ms-flex-align: flex-end;Ð align-items:
flex-end;Ð -webkit-box-pack: flex-start;Ð -webkit-justify-content: flex-
start;Ð -ms-flex-pack: flex-start;Ð justify-content: flex-start;Ð text-
align: left;Ð text-anchor: start;ÞÐct-chart-bar .ct-label.ct-horizontal.ct-
start {Ð -webkit-box-align: flex-end;Ð -webkit-align-items: flex-end;Ð -
ms-flex-align: flex-end;Ð align-items: flex-end;Ð -webkit-box-pack:
center;Ð -webkit-justify-content: center;Ð -ms-flex-pack: center;Ð
justify-content: center;Ð text-align: center;Ð text-anchor: start;ÞÐct-
chart-bar .ct-label.ct-horizontal.ct-end {Ð -webkit-box-align: flex-start;Ð
    -webkit-align-items: flex-start;Ð -ms-flex-align: flex-start;Ð align-
items: flex-start;Ð -webkit-box-pack: center;Ð -webkit-justify-content:
center;Ð -ms-flex-pack: center;Ð justify-content: center;Ð text-align:
center;Ð text-anchor: start;ÞÐct-chart-bar.ct-horizontal-bars .ct-label.ct-
horizontal.ct-start {Ð -webkit-box-align: flex-end;Ð -webkit-align-items:
flex-end;Ð -ms-flex-align: flex-end;Ð align-items: flex-end;Ð -webkit-
box-pack: flex-start;Ð -webkit-justify-content: flex-start;Ð -ms-flex-
pack: flex-start;Ð justify-content: flex-start;Ð text-align: left;Ð
text-anchor: start;ÞÐct-chart-bar.ct-horizontal-bars .ct-label.ct-
horizontal.ct-end {Ð -webkit-box-align: flex-start;Ð -webkit-align-items:
flex-start;Ð -ms-flex-align: flex-start;Ð align-items: flex-start;Ð -
webkit-box-pack: flex-start;Ð -webkit-justify-content: flex-start;Ð -ms-
flex-pack: flex-start;Ð justify-content: flex-start;Ð text-align: left;Ð
    text-anchor: start;ÞÐct-chart-bar.ct-horizontal-bars .ct-label.ct-
vertical.ct-start {Ð -webkit-box-align: center;Ð -webkit-align-items:
center;Ð -ms-flex-align: center;Ð align-items: center;Ð -webkit-box-
pack: flex-end;Ð -webkit-justify-content: flex-end;Ð -ms-flex-pack: flex-
end;Ð justify-content: flex-end;Ð text-align: right;Ð text-anchor: end;ÞÐ
.ct-chart-bar.ct-horizontal-bars .ct-label.ct-vertical.ct-end {Ð -webkit-
box-align: center;Ð -webkit-align-items: center;Ð -ms-flex-align: center;Ð
    align-items: center;Ð -webkit-box-pack: flex-start;Ð -webkit-justify-
content: flex-start;Ð -ms-flex-pack: flex-start;Ð justify-content: flex-
start;Ð text-align: left;Ð text-anchor: end;ÞÐct-grid {Ð stroke:
rgba(0, 0, 0, 0.2);Ð stroke-width: 1px;Ð stroke-dasharray: 2px;ÞÐct-point
{Ð stroke-width: 10px;Ð stroke-linecap: round;ÞÐct-line {Ð fill: none;Ð
    stroke-width: 4px;ÞÐct-area {Ð stroke: none;Ð fill-opacity: 0.1;ÞÐct-
bar {Ð fill: none;Ð stroke-width: 10px;ÞÐct-slice-donut {Ð fill: none;Ð
    stroke-width: 60px;ÞÐct-series-a .ct-point, .ct-series-a .ct-line, .ct-
series-a .ct-bar, .ct-series-a .ct-slice-donut {Ð stroke: #1AB394;ÞÐct-
series-a .ct-slice-pie, .ct-series-a .ct-area {Ð fill: #1AB394;ÞÐct-series-
b .ct-point, .ct-series-b .ct-line, .ct-series-b .ct-bar, .ct-series-b .ct-
slice-donut {Ð

stroke: #79D2C0;ÐÐct-series-b .ct-slice-pie, .ct-series-b .ct-area {Ð fill: #79D2C0;ÐÐct-series-c .ct-point, .ct-series-c .ct-line, .ct-series-c .ct-bar, .ct-series-c .ct-slice-donut {Ð stroke: #D3D3D3;Ð }ÐÐct-series-c .ct-slice-pie, .ct-series-c .ct-area {Ð fill: #D3D3D3;ÐÐct-series-d .ct-point, .ct-series-d .ct-line, .ct-series-d .ct-bar, .ct-series-d .ct-slice-donut {Ð stroke: #BABABA;ÐÐct-series-d .ct-slice-pie, .ct-series-d .ct-area {Ð fill: #BABABA;ÐÐct-series-e .ct-point, .ct-series-e .ct-line, .ct-series-e .ct-bar, .ct-series-e .ct-slice-donut {Ð stroke: #453d3f;ÐÐct-series-e .ct-slice-pie, .ct-series-e .ct-area {Ð fill: #453d3f;Ð }ÐÐct-series-f .ct-point, .ct-series-f .ct-line, .ct-series-f .ct-bar, .ct-series-f .ct-slice-donut {Ð stroke: #59922b;ÐÐct-series-f .ct-slice-pie, .ct-series-f .ct-area {Ð fill: #59922b;ÐÐct-series-g .ct-point, .ct-series-g .ct-line, .ct-series-g .ct-bar, .ct-series-g .ct-slice-donut {Ð stroke: #0544d3;ÐÐct-series-g .ct-slice-pie, .ct-series-g .ct-area {Ð fill: #0544d3;ÐÐct-series-h .ct-point, .ct-series-h .ct-line, .ct-series-h .ct-bar, .ct-series-h .ct-slice-donut {Ð stroke: #6b0392;ÐÐct-series-h .ct-slice-pie, .ct-series-h .ct-area {Ð fill: #6b0392;ÐÐct-series-i .ct-point, .ct-series-i .ct-line, .ct-series-i .ct-bar, .ct-series-i .ct-slice-donut {Ð stroke: #f05b4f;ÐÐct-series-i .ct-slice-pie, .ct-series-i .ct-area {Ð fill: #f05b4f;ÐÐct-series-j .ct-point, .ct-series-j .ct-line, .ct-series-j .ct-bar, .ct-series-j .ct-slice-donut {Ð stroke: #dda458;ÐÐct-series-j .ct-slice-pie, .ct-series-j .ct-area {Ð fill: #dda458;ÐÐct-series-k .ct-point, .ct-series-k .ct-line, .ct-series-k .ct-bar, .ct-series-k .ct-slice-donut {Ð stroke: #eacf7d;ÐÐct-series-k .ct-slice-pie, .ct-series-k .ct-area {Ð fill: #eacf7d;ÐÐct-series-l .ct-point, .ct-series-l .ct-line, .ct-series-l .ct-bar, .ct-series-l .ct-slice-donut {Ð stroke: #86797d;ÐÐct-series-l .ct-slice-pie, .ct-series-l .ct-area {Ð fill: #86797d;ÐÐct-series-m .ct-point, .ct-series-m .ct-line, .ct-series-m .ct-bar, .ct-series-m .ct-slice-donut {Ð stroke: #b2c326;ÐÐct-series-m .ct-slice-pie, .ct-series-m .ct-area {Ð fill: #b2c326;ÐÐct-series-n .ct-point, .ct-series-n .ct-line, .ct-series-n .ct-bar, .ct-series-n .ct-slice-donut {Ð stroke: #6188e2;ÐÐct-series-n .ct-slice-pie, .ct-series-n .ct-area {Ð fill: #6188e2;ÐÐct-series-o .ct-point, .ct-series-o .ct-line, .ct-series-o .ct-bar, .ct-series-o .ct-slice-donut {Ð stroke: #a748ca;ÐÐct-series-o .ct-slice-pie, .ct-series-o .ct-area {Ð fill: #a748ca;ÐÐct-square {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-square:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 100%;ÐÐct-square:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-square > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-minor-second {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-minor-second:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 93.75%;ÐÐct-minor-second:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-minor-second > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-second {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-second:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 88.88889%;ÐÐct-major-second:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-second > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-minor-third {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-minor-third:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 83.33333%;ÐÐct-minor-third:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-minor-third > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-third {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-third:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 80%;ÐÐct-major-third:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-third > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-perfect-fourth {Ð display: block;Ð

position: relative;Ð width: 100%;ÐÐct-perfect-fourth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 75%;ÐÐct-perfect-fourth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-perfect-fourth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-perfect-fifth {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-perfect-fifth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 66.66667%;ÐÐct-perfect-fifth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-perfect-fifth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-minor-sixth {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-minor-sixth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 62.5%;ÐÐct-minor-sixth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-minor-sixth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-golden-section {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-golden-section:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 61.8047%;ÐÐct-golden-section:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-golden-section > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-sixth {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-sixth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 60%;ÐÐct-major-sixth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-sixth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-minor-seventh {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-minor-seventh:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 56.25%;ÐÐct-minor-seventh:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-minor-seventh > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-seventh {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-seventh:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 53.33333%;ÐÐct-major-seventh:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-seventh > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-octave {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-octave:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 50%;ÐÐct-octave:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-octave > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-tenth {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-tenth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 40%;ÐÐct-major-tenth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-tenth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-eleventh {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-eleventh:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 37.5%;ÐÐct-major-eleventh:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-eleventh > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-major-twelfth {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-major-twelfth:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 33.33333%;ÐÐct-major-twelfth:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-major-twelfth > svg {Ð display: block;Ð position: absolute;Ð top: 0;Ð left: 0;ÐÐct-double-octave {Ð display: block;Ð position: relative;Ð width: 100%;ÐÐct-double-octave:before {Ð display: block;Ð float: left;Ð content: "";Ð width: 0;Ð height: 0;Ð padding-bottom: 25%;ÐÐct-double-octave:after {Ð content: "";Ð display: table;Ð clear: both;ÐÐct-double-octave > svg {Ð display: block;Ð position: absolute;Ð

top: 0;Ð left: 0;ÞÐ

public\assets\css\plugins\chosen\chosen.css

/*!ÐChosen, a Select Box Enhancer for jQuery and PrototypeÐby Patrick Filler for Harvest, http://getharvest.comÐVersion 1.1.0ÐFull source at https://github.com/harvesthq/chosenÐCopyright (c) 2011 Harvest http://getharvest.comÐMIT License, https://github.com/harvesthq/chosen/blob/master/LICENSE.mdÐThis file is generated by `grunt build`, do not edit it by hand.Þ/Ð* @group Base */Ð .chosen-container {Ð position: relative;Ð display: inline-block;Ð vertical-align: middle;Ð font-size: 13px;Ð zoom: 1;Ð *display: inline;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð user-select: none;ÞÐchosen-container .chosen-drop {Ð position: absolute;Ð top: 100%;Ð left: -9999px;Ð z-index: 1010;Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;Ð width: 100%;Ð border: 1px solid #aaa;Ð border-top: 0;Ð background: #fff;Ð box-shadow: 0 4px 5px rgba(0, 0, 0, 0.15);ÞÐchosen-container.chosen-with-drop .chosen-drop {Ð left: 0;ÞÐchosen-container a {Ð cursor: pointer;ÞÐ* @end */Ð* @group Single Chosen */Ðchosen-container-single .chosen-single {Ð position: relative;Ð display: block;Ð overflow: hidden;Ð padding: 0 0 0 8px;Ð height: 23px;Ð border: 1px solid #aaa;Ð border-radius: 5px;Ð background-color: #fff;Ð background: -webkit-gradient(linear, 50% 0%, 50% 100%, color-stop(20%, #ffffff), color-stop(50%, #f6f6f6), color-stop(52%, #eeeeee), color-stop(100%, #f4f4f4));Ð background: -webkit-linear-gradient(top, #ffffff 20%, #f6f6f6 50%, #eeeeee 52%, #f4f4f4 100%);Ð background: -moz-linear-gradient(top, #ffffff 20%, #f6f6f6 50%, #eeeeee 52%, #f4f4f4 100%);Ð background: -o-linear-gradient(top, #ffffff 20%, #f6f6f6 50%, #eeeeee 52%, #f4f4f4 100%);Ð background: linear-gradient(top, #ffffff 20%, #f6f6f6 50%, #eeeeee 52%, #f4f4f4 100%);Ð background-clip: padding-box;Ð box-shadow: 0 0 3px white inset, 0 1px 1px rgba(0, 0, 0, 0.1);Ð color: #444;Ð text-decoration: none;Ð white-space: nowrap;Ð line-height: 24px;ÞÐchosen-container-single .chosen-default {Ð color: #999;ÞÐchosen-container-single .chosen-single span {Ð display: block;Ð overflow: hidden;Ð margin-right: 26px;Ð text-overflow: ellipsis;Ð white-space: nowrap;ÞÐ .chosen-container-single .chosen-single-with-deselect span {Ð margin-right: 38px;ÞÐchosen-container-single .chosen-single abbr {Ð position: absolute;Ð top: 6px;Ð right: 26px;Ð display: block;Ð width: 12px;Ð height: 12px;Ð background: url('chosen-sprite.png') -42px 1px no-repeat;Ð font-size: 1px;ÞÐchosen-container-single .chosen-single abbr:hover {Ð background-position: -42px -10px;ÞÐchosen-container-single.chosen-disabled .chosen-single abbr:hover {Ð background-position: -42px -10px;ÞÐchosen-container-single .chosen-single div {Ð position: absolute;Ð top: 0;Ð right: 0;Ð display: block;Ð width: 18px;Ð height: 100%;ÞÐchosen-container-single .chosen-single div b {Ð display: block;Ð width: 100%;Ð height: 100%;Ð background: url('chosen-sprite.png') no-repeat 0px 2px;ÞÐchosen-container-single .chosen-search {Ð position: relative;Ð z-index: 1010;Ð margin: 0;Ð padding: 3px 4px;Ð white-space: nowrap;ÞÐchosen-container-single .chosen-search input[type="text"] {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;Ð margin: 1px 0;Ð padding: 4px 20px 4px 5px;Ð width: 100%;Ð height: auto;Ð outline: 0;Ð border: 1px solid #aaa;Ð background: white url('chosen-sprite.png') no-repeat 100% -20px;Ð background: url('chosen-sprite.png') no-repeat 100% -20px;Ð font-size: 1em;Ð font-family: sans-serif;Ð line-height: normal;Ð border-radius: 0;ÞÐchosen-container-single .chosen-drop {Ð margin-top: -1px;Ð border-radius: 0 0 4px 4px;Ð background-clip: padding-box;ÞÐchosen-container-single.chosen-container-single-nosearch .chosen-search {Ð position: absolute;Ð left: -9999px;ÞÐ* @end */Ð* @group Results */Ðchosen-container .chosen-results {Ð position: relative;Ð overflow-x: hidden;Ð overflow-y: auto;Ð margin: 0 4px 4px 0;Ð padding: 0 0 0 4px;Ð max-height: 240px;Ð -webkit-overflow-scrolling: touch;ÞÐchosen-container .chosen-results li {Ð display: none;Ð margin: 0;Ð padding: 5px 6px;Ð list-style: none;Ð line-height: 15px;Ð -webkit-touch-callout: none;Ð

}Ðchosen-container .chosen-results li.active-result {Ð display: list-item;Ð cursor: pointer;ÞÐchosen-container .chosen-results li.disabled-result {Ð display: list-item;Ð color: #ccc;Ð cursor: default;ÞÐchosen-container .chosen-results li.highlighted {Ð background-color: #3875d7;Ð background-image: -webkit-gradient(linear, 50% 0%, 50% 100%, color-stop(20%, #3875d7), color-stop(90%, #2a62bc));Ð background-image: -webkit-linear-gradient(#3875d7 20%, #2a62bc 90%);Ð background-image: -moz-linear-gradient(#3875d7 20%, #2a62bc 90%);Ð background-image: -o-linear-gradient(#3875d7 20%, #2a62bc 90%);Ð background-image: linear-gradient(#3875d7 20%, #2a62bc 90%);Ð color: #fff;ÞÐchosen-container .chosen-results li.no-results {Ð display: list-item;Ð background: #f4f4f4;ÞÐ .chosen-container .chosen-results li.group-result {Ð display: list-item;Ð font-weight: bold;Ð cursor: default;ÞÐchosen-container .chosen-results li.group-option {Ð padding-left: 15px;ÞÐchosen-container .chosen-results li em {Ð font-style: normal;Ð text-decoration: underline;ÞØ* @end */Ø* @group Multi Chosen */Ðchosen-container-multi .chosen-choices {Ð -moz-box-sizing: border-box;Ð background-color: #FFFFFF;Ð border: 1px solid #CBD5DD;Ð border-radius: 2px;Ð cursor: text;Ð height: auto !important;Ð margin: 0;Ð min-height: 30px;Ð overflow: hidden;Ð padding: 2px;Ð position: relative;Ð width: 100%;ÞÐchosen-container-multi .chosen-choices li {Ð float: left;Ð list-style: none;ÞÐchosen-container-multi .chosen-choices li.search-field {Ð margin: 0;Ð padding: 0;Ð white-space: nowrap;Ð }Ðchosen-container-multi .chosen-choices li.search-field input[type="text"] {Ð margin: 1px 0;Ð padding: 5px;Ð height: 25px;Ð outline: 0;Ð border: 0 !important;Ð background: transparent !important;Ð box-shadow: none;Ð color: #666;Ð font-size: 100%;Ð font-family: sans-serif;Ð line-height: normal;Ð border-radius: 0;ÞÐchosen-container-multi .chosen-choices li.search-field .default {Ð color: #999;ÞÐchosen-container-multi .chosen-choices li.search-choice {Ð position: relative;Ð margin: 3px 0 3px 5px;Ð padding: 3px 20px 3px 5px;Ð border: 1px solid #aaa;Ð border-radius: 3px;Ð background-color: #e4e4e4;Ð background-image: -webkit-gradient(linear, 50% 0%, 50% 100%, color-stop(20%, #f4f4f4), color-stop(50%, #f0f0f0), color-stop(52%, #e8e8e8), color-stop(100%, #eeeeee));Ð background-image: -webkit-linear-gradient(#f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: -moz-linear-gradient(#f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: -o-linear-gradient(#f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: linear-gradient(#f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-clip: padding-box;Ð box-shadow: 0 0 2px white inset, 0 1px 0 rgba(0, 0, 0, 0.05);Ð color: #333;Ð line-height: 13px;Ð cursor: default;ÞÐchosen-container-multi .chosen-choices li.search-choice .search-choice-close {Ð position: absolute;Ð top: 4px;Ð right: 3px;Ð display: block;Ð width: 12px;Ð height: 12px;Ð background: url('chosen-sprite.png') -42px 1px no-repeat;Ð font-size: 1px;ÞÐchosen-container-multi .chosen-choices li.search-choice .search-choice-close:hover {Ð background-position: -42px -10px;ÞÐ .chosen-container-multi .chosen-choices li.search-choice-disabled {Ð padding-right: 5px;Ð border: 1px solid #ccc;Ð background-color: #e4e4e4;Ð background-image: -webkit-gradient(linear, 50% 0%, 50% 100%, color-stop(20%, #f4f4f4), color-stop(50%, #f0f0f0), color-stop(52%, #e8e8e8), color-stop(100%, #eeeeee));Ð background-image: -webkit-linear-gradient(top, #f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: -moz-linear-gradient(top, #f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: -o-linear-gradient(top, #f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð background-image: linear-gradient(top, #f4f4f4 20%, #f0f0f0 50%, #e8e8e8 52%, #eeeeee 100%);Ð color: #666;ÞÐchosen-container-multi .chosen-choices li.search-choice-focus {Ð background: #d4d4d4;ÞÐchosen-container-multi .chosen-choices li.search-choice-focus .search-choice-close {Ð background-position: -42px -10px;ÞÐchosen-container-multi .chosen-results {Ð margin: 0;Ð padding: 0;ÞÐchosen-container-multi .chosen-drop .result-selected {Ð

display: list-item;Ð
color: #ccc;Ð cursor: default;ÐÐ* @end */Ð* @group Active */Ðchosen-
container-active .chosen-single {Ð border: 1px solid #5897fb;Ð box-
shadow: 0 0 5px rgba(0, 0, 0, 0.3);ÐÐchosen-container-active.chosen-with-
drop .chosen-single {Ð border: 1px solid #aaa;Ð -moz-border-radius-
bottomright: 0;Ð border-bottom-right-radius: 0;Ð -moz-border-radius-
bottomleft: 0;Ð border-bottom-left-radius: 0;Ð background-image: -webkit-
gradient(linear, 50% 0%, 50% 100%, color-stop(20%, #eeeeee), color-stop(80%,
#ffffff));Ð background-image: -webkit-linear-gradient(#eeeeee 20%, #ffffff
80%);Ð background-image: -moz-linear-gradient(#eeeeee 20%, #ffffff 80%);Ð
background-image: -o-linear-gradient(#eeeeee 20%, #ffffff 80%);Ð background-
image: linear-gradient(#eeeeee 20%, #ffffff 80%);Ð box-shadow: 0 1px 0 #fff
inset;ÐÐchosen-container-active.chosen-with-drop .chosen-single div {Ð
border-left: none;Ð background: transparent;ÐÐchosen-container-
active.chosen-with-drop .chosen-single div b {Ð background-position: -18px
2px;ÐÐchosen-container-active .chosen-choices {Ð border: 1px solid #5897fb;Ð
    box-shadow: 0 0 5px rgba(0, 0, 0, 0.3);ÐÐchosen-container-active .chosen-
choices li.search-field input[type="text"] {Ð color: #111 !important;ÐÐ*
@end */Ð* @group Disabled Support */Ðchosen-disabled {Ð opacity: 0.5 !
important;Ð cursor: default;ÐÐchosen-disabled .chosen-single {Ð cursor:
default;ÐÐchosen-disabled .chosen-choices .search-choice .search-choice-close
{Ð cursor: default;ÐÐ* @end */Ð* @group Right to Left */Ðchosen-rtl {Ð
text-align: right;ÐÐchosen-rtl .chosen-single {Ð overflow: visible;Ð
padding: 0 8px 0 0;ÐÐchosen-rtl .chosen-single span {Ð margin-right: 0;Ð
margin-left: 26px;Ð direction: rtl;ÐÐchosen-rtl .chosen-single-with-
deselect span {Ð margin-left: 38px;ÐÐchosen-rtl .chosen-single div {Ð
right: auto;Ð left: 3px;ÐÐchosen-rtl .chosen-single abbr {Ð right: auto;Ð
    left: 26px;ÐÐchosen-rtl .chosen-choices li {Ð float: right;ÐÐchosen-
rtl .chosen-choices li.search-field input[type="text"] {Ð direction: rtl;ÐÐ
.chosen-rtl .chosen-choices li.search-choice {Ð margin: 3px 5px 3px 0;Ð
padding: 3px 5px 3px 19px;ÐÐchosen-rtl .chosen-choices li.search-
choice .search-choice-close {Ð right: auto;Ð left: 4px;ÐÐchosen-
rtl.chosen-container-single-nosearch .chosen-search,Ðchosen-rtl .chosen-drop {Ð
    left: 9999px;ÐÐchosen-rtl.chosen-container-single .chosen-results {Ð
margin: 0 0 4px 4px;Ð padding: 0 4px 0 0;ÐÐchosen-rtl .chosen-results
li.group-option {Ð padding-right: 15px;Ð padding-left: 0;ÐÐchosen-
rtl.chosen-container-active.chosen-with-drop .chosen-single div {Ð border-
right: none;ÐÐchosen-rtl .chosen-search input[type="text"] {Ð padding: 4px
5px 4px 20px;Ð background: white url('chosen-sprite.png') no-repeat -30px
-20px;Ð background: url('chosen-sprite.png') no-repeat -30px -20px;Ð
direction: rtl;ÐÐchosen-rtl.chosen-container-single .chosen-single div b {Ð
background-position: 6px 2px;ÐÐchosen-rtl.chosen-container-single.chosen-with-
drop .chosen-single div b {Ð background-position: -12px 2px;ÐÐ* @end */Ð*
@group Retina compatibility */@media only screen and (-webkit-min-device-
pixel-ratio: 2), only screen and (min-resolution: 144dpi) {Ð .chosen-
rtl .chosen-search input[type="text"],Ð .chosen-container-single .chosen-
single abbr,Ð .chosen-container-single .chosen-single div b,Ð .chosen-
container-single .chosen-search input[type="text"],Ð .chosen-container-
multi .chosen-choices .search-choice .search-choice-close,Ð .chosen-
container .chosen-results-scroll-down span,Ð .chosen-container .chosen-
results-scroll-up span {Ð background-image: url('chosen-
sprite@2x.png') !important;Ð background-size: 52px 37px !important;Ð
  background-repeat: no-repeat !important;Ð }ÐÐ* @end */Ð

public\assets\css\plugins\clockpicker\clockpicker.css

/*!Ð* ClockPicker v{package.version} for Bootstrap (http://weareoutman.github.io/clockpicker/)Ð* Copyright 2014 Wang Shenwei.Ð* Licensed under MIT (https://github.com/weareoutman/clockpicker/blob/gh-pages/LICENSE)Ð */Ðclockpicker .input-group-addon {Ð7W'6÷#¢ ö–çFW#½Ðclockpicker-moving {Ð cursor: move;ÐÐclockpicker-align-left.popover > .arrow {ÐÆVgC¢ #W ƒ½Ð .clockpicker-align-top.popover > .arrow {ÐF÷ ¢ w ƒ½Ðclockpicker-align-right.popover > .arrow {ÐÆVgC¢ WFó½&–v‡C¢ #W ƒ½Ðclockpicker-align-bottom.popover > .arrow {ÐF÷ ¢ WFó½&÷GFöÓ¢ g ƒ½Ðclockpicker-popover .popover-title {Ð& 6¶w&÷VæBÖ6öÆ÷#¢ 6ffc½6öÆ÷#¢ 3""“½föçB×6–¦S¢ #G ƒ½föçB×vV–v‡C¢ &öÆC½ line-height: 30px;ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðclockpicker-popover .popover-title span {Ð7W'6÷#¢ ö–çFW#½Ðclockpicker-popover .popover-content {Ð& 6¶w&÷VæBÐ color: #f8f8f8;Ð FF–æs¢ ' ƒ½Ðpopover-content:last-child {Ð&÷&FW"Ö&÷GFöÒÖÆVgBÐ radius: 5px;Ð&÷&FW"Ö&÷GFöÒ×&–v‡B×& F—W3¢ W ƒ½Ðclockpicker-plate {Ð& 6¶w&÷VæBÐ color: #fff;Ð&÷&FW#¢ , 6öÆ–B 6663½&÷&FW"×& F—W3¢ S S½v–GƒÐ¢ # ƒ½†V–v‡C¢ 200px;Ð÷fW&fÆ÷s¢ f—6–&ÆS½ ÷6—F–öã¢ &VÆ F—fS½ò¢ F—6 &ÆR FW‡B 6VÆV7F–öâ highlighting. Thanks to Hermanya */Ð×vV&¶—B×F÷V6,Ö6 ÆÆ÷WC¢ æöæS½×vV&¶—B×W6W"Ð select: none;ÐÖ¶‡FÖÂ×W6W"×6VÆV7C¢ æöæS½ÖÖ÷¢×W6W"×6VÆV7C¢ æöæS½Ö×2×W6W"×6VÆV7C¢ none;ÐW6W"×6VÆV7C¢ æöæS½Ðclockpicker-canvas,Ðclockpicker-dial {Ðv–GFƒ¢ # ƒ½ height: 200px;Ð ÷6—F–öã¢ '6öÇWFS½ÆVgC¢ Ó ƒ½F÷ ¢ Ó ƒ½Ðclockpicker-minutes {Ð visibility: hidden;ÐÐclockpicker-tick {Ð&÷&FW"×& F—W3¢ S S½6öÆ÷#¢ 3ccc½Æ–æRÐ height: 26px;ÐFW‡BÖ Æ–vã¢ 6VçFW#½v–GƒÐ¢ #g ƒ½†V–v‡C¢ #g ƒ½ ÷6—F–öã¢ '6öÇWFS½ cursor: pointer;ÐÐclockpicker-tick.active,Ðclockpicker-tick:hover {Ð& 6¶w&÷VæBÐ color: rgb(192, 229, 247);Ð& 6¶w&÷VæBÖ6öÆ÷#¢ &v& ƒ Â C’Â ## Â ã#R“½Ð .clockpicker-button {Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½& 6¶w&÷VæBÖ6öÆ÷#¢ 6ffc½&÷&FW"Ð width: 1px 0 0;Ð&÷&FW"×F÷ ÖÆVgB×& F—W3¢ ½&÷&FW"×F÷ ×&–v‡B×& F—W3¢ ½Ö &v–ã¢ ½ padding: 10px 0;ÐÐclockpicker-button:hover {Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½& 6¶w&÷VæBÐ color: #ebebeb;ÐÐclockpicker-button:focus {Ð÷WFÆ–æS¢ æöæR –× ÷'F çC½Ð .clockpicker-dial {Ð×vV&¶—B×G& ç6—F–öã¢ ×vV&¶—B×G& ç6f÷&Ò 3S ×2Â ÷ 6—G’ 3S ×3½ ’ÖÖ÷¢×G& ç6—F–öã¢ ÖÖ÷¢×G& ç6f÷&Ó 3S ×2Â ÷ 6—G’ 3S ×3½Ö×2×G& ç6—F–öã¢ Ö×2Ð transform 350ms, opacity 350ms;ÐÖÒ×G& ç6—F–öã¢ Öò×G& ç6f÷&Ò 3S ×2Â ÷ 6—G’ 350ms;ÐG& ç6—F–öã¢ G& ç6f÷&Ò 3S ×2Â ÷ 6—G’ 3S ×3½Ðclockpicker-dial-out {Ð opacity: 0;ÐÐclockpicker-hours.clockpicker-dial-out {Ð×vV&¶—B×G& ç6f÷&Ó¢ scale(1.2, 1.2);ÐÖÖ÷¢×G& ç6f÷&Ó¢ 66 ÆRƒ ã"Â ã"“½Ö×2×G& ç6f÷&Ó¢ 66 ÆRƒ ã"Â 1.2);ÐÖÒ×G& ç6f÷&Ó¢ 66 ÆRƒ ã"Â ã"“½G& ç6f÷&Ó¢ 66 ÆRƒ ã"Â ã"“½Ðclockpicker-minutes.clockpicker-dial-out {Ð×vV&¶—B×G& ç6f÷&Ó¢ 66 ÆR,ã,Â ã,“½ÖÖ÷¢Ð transform: scale(.8, .8);ÐÖ×2×G& ç6f÷&Ó¢ 66 ÆR,ã,Â ã,“½Öò×G& ç6f÷&Ó¢ scale(.8, .8);ÐG& ç6f÷&Ó¢ 66 ÆR,ã,Â ã,“½Ðclockpicker-canvas {Ð×vV&¶—BÐ transition: opacity 175ms;ÐÖÖ÷¢×G& ç6—F–öã¢ ÷ 6—G’ sV×3½Ö×2×G& ç6—F–öã¢ opacity 175ms;ÐÖÒ×G& ç6—F–öã¢ ÷ 6—G’ sV×3½G& ç6—F–öã¢ ÷ 6—G’ sV×3½Ð .clockpicker-canvas-out {Ð÷ 6—G“¢ ã#S½Ðclockpicker-canvas-bearing,Ð .clockpicker-canvas-fg {Ð7G&ö¶S¢ æöæS½f–ÆÃ¢ &v"ƒ Â C’Â ## “½Ðclockpicker-canvas-bg {Ð7G&ö¶S¢ æöæS½f–ÆÃ¢ &v"ƒ ""Â ##’Â #Cr“½Ðclockpicker-canvas-bg-trans {Ðf–ÆÃ¢ &v& ƒ Â C’Â ## Â ã#R“½Ðclockpicker-canvas line {Ð7G&ö¶S¢ &v"ƒ Â 149, 221);Ð7G&ö¶R×v–GƒÐ¢ ½7G&ö¶RÖÆ–æV6 ¢ &÷VæC½ò§6† R×&VæFW&–æs¢ crispEdges;*/ÐÐclockpicker-button.am-button {ÐÖ &v–ã¢ ƒ½ FF–æs¢ W ƒ½&÷&FW#¢ 1px solid rgba(0, 0, 0, .2);Ð&÷&FW"×& F—W3¢ G ƒ½Ðclockpicker-button.pm-button {ÐÖ &v–ã¢ , , , 3g ƒ½ FF–æs¢ W ƒ½&÷&FW#¢ , 6öÆ–B &v& ƒ Â Â Â ã"“½ border-radius: 4px;ÐÐ

public\assets\css\plugins\codemirror\codemirror.css

/* BASICS */ÐCodeMirror {Ð /* Set height, width, borders, and global font properties here */Ð font-family: monospace;Ð height: 300px;ÞÐCodeMirror-scroll {Ð /* Set scrolling behaviour here */Ð overflow: auto;ÞÐ* PADDING */Ð .CodeMirror-lines {Ð padding: 4px 0; /* Vertical padding around content */ÞÐ .CodeMirror pre {Ð padding: 0 4px; /* Horizontal padding of content */ÞÐ .CodeMirror-scrollbar-filler, .CodeMirror-gutter-filler {Ð background-color: white; /* The little square between H and V scrollbars */ÞÐ* GUTTER */Ð .CodeMirror-gutters {Ð border-right: 1px solid #ddd;Ð background-color: #f7f7f7;Ð white-space: nowrap;ÞÐCodeMirror-linenumbers {}ÐCodeMirror-linenumber {Ð padding: 0 3px 0 5px;Ð min-width: 20px;Ð text-align: right;Ð color: #999;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÞÐ .CodeMirror-guttermarker { color: black; }ÐCodeMirror-guttermarker-subtle { color: #999; }Ð* CURSOR */ÐCodeMirror div.CodeMirror-cursor {Ð border-left: 1px solid black;ÞÐ* Shown when moving in bi-directional text */ÐCodeMirror div.CodeMirror-secondarycursor {Ð border-left: 1px solid silver;ÞÐ .CodeMirror.cm-keymap-fat-cursor div.CodeMirror-cursor {Ð width: auto;Ð border: 0;Ð background: #7e7;ÞÐCodeMirror.cm-keymap-fat-cursor div.CodeMirror-cursors {Ð z-index: 1;ÞÐcm-animate-fat-cursor {Ð width: auto;Ð border: 0;Ð -webkit-animation: blink 1.06s steps(1) infinite;Ð -moz-animation: blink 1.06s steps(1) infinite;Ð animation: blink 1.06s steps(1) infinite;ÞÐ@-moz-keyframes blink {Ð 0% { background: #7e7; }Ð 50% { background: none; }Ð 100% { background: #7e7; }ÞÐ@-webkit-keyframes blink {Ð 0% { background: #7e7; }Ð 50% { background: none; }Ð 100% { background: #7e7; }ÞÐ@keyframes blink {Ð 0% { background: #7e7; }Ð 50% { background: none; }Ð 100% { background: #7e7; }ÞÐ* Can style cursor different in overwrite (non-insert) mode */Ðdiv.CodeMirror-overwrite div.CodeMirror-cursor {}Ðcm-tab { display: inline-block; text-decoration: inherit; }ÐCodeMirror-ruler {Ð border-left: 1px solid #ccc;Ð position: absolute;ÞÐ* DEFAULT THEME */Ðcm-s-default .cm-keyword {color: #708;}Ðcm-s-default .cm-atom {color: #219;}Ðcm-s-default .cm-number {color: #164;}Ðcm-s-default .cm-def {color: #00f;}Ðcm-s-default .cm-variable,Ðcm-s-default .cm-punctuation,Ðcm-s-default .cm-property,Ðcm-s-default .cm-operator {}Ðcm-s-default .cm-variable-2 {color: #05a;}Ðcm-s-default .cm-variable-3 {color: #085;}Ðcm-s-default .cm-comment {color: #a50;}Ðcm-s-default .cm-string {color: #a11;}Ðcm-s-default .cm-string-2 {color: #f50;}Ðcm-s-default .cm-meta {color: #555;}Ðcm-s-default .cm-qualifier {color: #555;}Ðcm-s-default .cm-builtin {color: #30a;}Ðcm-s-default .cm-bracket {color: #997;}Ð .cm-s-default .cm-tag {color: #170;}Ðcm-s-default .cm-attribute {color: #00c;}Ð .cm-s-default .cm-header {color: blue;}Ðcm-s-default .cm-quote {color: #090;}Ð .cm-s-default .cm-hr {color: #999;}Ðcm-s-default .cm-link {color: #00c;}Ðcm-negative {color: #d44;}Ðcm-positive {color: #292;}Ðcm-header, .cm-strong {font-weight: bold;}Ðcm-em {font-style: italic;}Ðcm-link {text-decoration: underline;}Ðcm-s-default .cm-error {color: #f00;}Ðcm-invalidchar {color: #f00;}Ð* Default styles for common addons */Ðdiv.CodeMirror span.CodeMirror-matchingbracket {color: #0f0;}Ðdiv.CodeMirror span.CodeMirror-nonmatchingbracket {color: #f22;}ÐCodeMirror-matchingtag { background: rgba(255, 150, 0, .3); }ÐCodeMirror-activeline-background {background: #e8f2ff;}Ð* STOP */Ð* The rest of this file contains styles related to the mechanics ofÐ the editor. You probably shouldn't touch them. */ÐCodeMirror {Ð line-height: 1;Ð position: relative;Ð overflow: hidden;Ð background: white;Ð color: black;ÞÐCodeMirror-scroll {Ð /* 30px is the magic margin used to hide the element's real scrollbars */Ð /* See overflow: hidden in .CodeMirror */Ð margin-bottom: -30px; margin-right: -30px;Ð padding-bottom: 30px;Ð height: 100%;Ð outline: none; /* Prevent dragging from highlighting the element */Ð position: relative;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÞÐCodeMirror-sizer {Ð position: relative;Ð border-right: 30px solid transparent;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÞÐ* The fake, visible scrollbars. Used to force redraw during scrollingÐ before actuall scrolling happens, thus preventing shaking andÐ flickering artifacts. */Ð

.CodeMirror-vscrollbar, .CodeMirror-hscrollbar, .CodeMirror-scrollbar-filler, .CodeMirror-gutter-filler {Ð position: absolute;Ð z-index: 6;Ð display: none;ÐÐCodeMirror-vscrollbar {Ð right: 0; top: 0;Ð overflow-x: hidden;Ð overflow-y: scroll;ÐÐCodeMirror-hscrollbar {Ð bottom: 0; left: 0;Ð overflow-y: hidden;Ð overflow-x: scroll;ÐÐCodeMirror-scrollbar-filler {Ð right: 0; bottom: 0;ÐÐCodeMirror-gutter-filler {Ð left: 0; bottom: 0;ÐÐ .CodeMirror-gutters {Ð position: absolute; left: 0; top: 0;Ð padding-bottom: 30px;Ð z-index: 3;ÐÐCodeMirror-gutter {Ð white-space: normal;Ð height: 100%;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;Ð padding-bottom: 30px;Ð margin-bottom: -32px;Ð display: inline-block;Ð /* Hack to make IE7 behave */Ð *zoom:1;Ð *display:inline;ÐÐCodeMirror-gutter-elt {Ð position: absolute;Ð cursor: default;Ð z-index: 4;ÐÐCodeMirror-lines {Ð cursor: text;Ð min-height: 1px; /* prevents collapsing before first draw */ÐÐCodeMirror pre {Ð /* Reset some styles that the rest of the page might have set */Ð -moz-border-radius: 0; -webkit-border-radius: 0; border-radius: 0;Ð border-width: 0;Ð background: transparent;Ð font-family: inherit;Ð font-size: inherit;Ð margin: 0;Ð white-space: pre;Ð word-wrap: normal;Ð line-height: inherit;Ð color: inherit;Ð z-index: 2;Ð position: relative;Ð overflow: visible;ÐÐCodeMirror-wrap pre {Ð word-wrap: break-word;Ð white-space: pre-wrap;Ð word-break: normal;ÐÐ .CodeMirror-linebackground {Ð position: absolute;Ð left: 0; right: 0; top: 0; bottom: 0;Ð z-index: 0;ÐÐCodeMirror-linewidget {Ð position: relative;Ð z-index: 2;Ð overflow: auto;ÐÐCodeMirror-widget {}ÐCodeMirror-wrap .CodeMirror-scroll {Ð overflow-x: hidden;ÐÐCodeMirror-measure {Ð position: absolute;Ð width: 100%;Ð height: 0;Ð overflow: hidden;Ð visibility: hidden;ÐÐCodeMirror-measure pre { position: static; }ÐCodeMirror div.CodeMirror-cursor {Ð position: absolute;Ð border-right: none;Ð width: 0;ÐÐdiv.CodeMirror-cursors {Ð visibility: hidden;Ð position: relative;Ð z-index: 3;ÐÐCodeMirror-focused div.CodeMirror-cursors {Ð visibility: visible;ÐÐCodeMirror-selected { background: #d9d9d9; }ÐCodeMirror-focused .CodeMirror-selected { background: #d7d4f0; }ÐCodeMirror-crosshair { cursor: crosshair; }Ðcm-searching {Ð background: #ffa;Ð background: rgba(255, 255, 0, .4);ÐÐ* IE7 hack to prevent it from returning funny offsetTops on the spans */ÐCodeMirror span { *vertical-align: text-bottom; }ÐÐ* Used to force a border model for a node */Ðcm-force-border { padding-right: .1px; }@media print {Ð /* Hide the cursor when printing */Ð .CodeMirror div.CodeMirror-cursors {Ð visibility: hidden;Ð }ÐÐ* Help users use markselection to safely style text background */Ð span.CodeMirror-selectedtext { background: none; }Ð

public\assets\css\plugins\cropper\cropper.css

/*!Ð* Cropper v3.0.0-rc.3Ð* https://github.com/fengyuanchen/cropperÐ*Ð* Copyright (c) 2017 Fengyuan ChenÐ* Released under the MIT licenseÐ*Ð* Date: 2017-07-07T13:00:47.346ZÐ*/Ðcropper-container {Ð font-size: 0;Ð line-height: 0;Ð position: relative;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð user-select: none;Ð direction: ltr;Ð -ms-touch-action: none;Ð touch-action: noneÞÐcropper-container img {Ð /* Avoid margin top issue (Occur only when margin-top <= -height) */Ð display: block;Ð min-width: 0 !important;Ð max-width: none !important;Ð min-height: 0 !important;Ð max-height: none !important;Ð width: 100%;Ð height: 100%;Ð image-orientation: 0degÞÐcropper-wrap-box,Ðcropper-canvas,Ðcropper-drag-box,Ð .cropper-crop-box,Ðcropper-modal {Ð position: absolute;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;ÞÐcropper-wrap-box {Ð overflow: hidden;ÞÐcropper-drag-box {Ð opacity: 0;Ð background-color: #fff;ÞÐcropper-modal {Ð opacity: .5;Ð background-color: #000;ÞÐcropper-view-box {Ð display: block;Ð overflow: hidden;Ð width: 100%;Ð height: 100%;Ð outline: 1px solid #39f;Ð outline-color: rgba(51, 153, 255, 0.75);ÞÐcropper-dashed {Ð position: absolute;Ð display: block;Ð opacity: .5;Ð border: 0 dashed #eeeÞÐcropper-dashed.dashed-h {Ð top: 33.33333%;Ð left: 0;Ð width: 100%;Ð height: 33.33333%;Ð border-top-width: 1px;Ð border-bottom-width: 1pxÞÐcropper-dashed.dashed-v {Ð top: 0;Ð left: 33.33333%;Ð width: 33.33333%;Ð height: 100%;Ð border-right-width: 1px;Ð border-left-width: 1pxÞÐcropper-center {Ð position: absolute;Ð top: 50%;Ð left: 50%;Ð display: block;Ð width: 0;Ð height: 0;Ð opacity: .75ÞÐcropper-center:before,Ð .cropper-center:after {Ð position: absolute;Ð display: block;Ð content: ' ';Ð background-color: #eeeÞÐcropper-center:before {Ð top: 0;Ð left: -3px;Ð width: 7px;Ð height: 1pxÞÐcropper-center:after {Ð top: -3px;Ð left: 0;Ð width: 1px;Ð height: 7pxÞÐcropper-face,Ðcropper-line,Ðcropper-point {Ð position: absolute;Ð display: block;Ð width: 100%;Ð height: 100%;Ð opacity: .1;ÞÐcropper-face {Ð top: 0;Ð left: 0;Ð background-color: #fff;ÞÐ .cropper-line {Ð background-color: #39fÞÐcropper-line.line-e {Ð top: 0;Ð right: -3px;Ð width: 5px;Ð cursor: e-resizeÞÐcropper-line.line-n {Ð top: -3px;Ð left: 0;Ð height: 5px;Ð cursor: n-resizeÞÐcropper-line.line-w {Ð top: 0;Ð left: -3px;Ð width: 5px;Ð cursor: w-resizeÞÐcropper-line.line-s {Ð bottom: -3px;Ð left: 0;Ð height: 5px;Ð cursor: s-resizeÞÐcropper-point {Ð width: 5px;Ð height: 5px;Ð opacity: .75;Ð background-color: #39fÞÐcropper-point.point-e {Ð top: 50%;Ð right: -3px;Ð margin-top: -3px;Ð cursor: e-resizeÞÐcropper-point.point-n {Ð top: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: n-resizeÞÐ .cropper-point.point-w {Ð top: 50%;Ð left: -3px;Ð margin-top: -3px;Ð cursor: w-resizeÞÐcropper-point.point-s {Ð bottom: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: s-resizeÞÐcropper-point.point-ne {Ð top: -3px;Ð right: -3px;Ð cursor: ne-resizeÞÐcropper-point.point-nw {Ð top: -3px;Ð left: -3px;Ð cursor: nw-resizeÞÐcropper-point.point-sw {Ð bottom: -3px;Ð left: -3px;Ð cursor: sw-resizeÞÐcropper-point.point-se {Ð right: -3px;Ð bottom: -3px;Ð width: 20px;Ð height: 20px;Ð cursor: se-resize;Ð opacity: 1ÞÐmedia (min-width: 768px) {Ð .cropper-point.point-se {Ð width: 15px;Ð height: 15pxÐ }ÞÐmedia (min-width: 992px) {Ð .cropper-point.point-se {Ð width: 10px;Ð height: 10pxÐ }ÞÐ @media (min-width: 1200px) {Ð .cropper-point.point-se {Ð width: 5px;Ð height: 5px;Ð opacity: .75Ð }ÞÐcropper-point.point-se:before {Ð position: absolute;Ð right: -50%;Ð bottom: -50%;Ð display: block;Ð width: 200%;Ð height: 200%;Ð content: ' ';Ð opacity: 0;Ð background-color: #39fÞÐcropper-invisible {Ð opacity: 0;ÞÐcropper-bg {Ð background-image: url('');ÞÐcropper-hide {Ð position: absolute;Ð display: block;Ð width: 0;Ð height: 0;ÞÐcropper-hidden {Ð display: none !important;ÞÐcropper-move {Ð cursor: move;ÞÐcropper-crop {Ð cursor: crosshair;ÞÐ .cropper-disabled .cropper-drag-box,Ðcropper-disabled .cropper-face,Ðcropper-disabled .cropper-line,Ðcropper-disabled .cropper-point {Ð cursor: not-allowed;Ð

}Ð

public\assets\css\plugins\datapicker\datepicker3.css

/*!Ð* Datepicker for BootstrapÐ*Ð* Copyright 2012 Stefan PetreÐ* Improvements by Andrew RowlsÐ* Licensed under the Apache License v2.0Ð* http://www.apache.org/licenses/LICENSE-2.0Ð*Ð*/Ðdatepicker {Ð padding: 4px;Ð border-radius: 4px;Ð direction: ltr;Ð /*.dow {Ðborder-top: 1px solid #ddd !important;Ð */ÐÐdatepicker-inline {Ð width: 220px;ÐÐdatepicker.datepicker-rtl {Ð direction: rtl;ÐÐdatepicker.datepicker-rtl table tr td span {Ð float: right;ÐÐ .datepicker-dropdown {Ð top: 0;Ð left: 0;ÐÐdatepicker-dropdown:before {Ð content: '';Ð display: inline-block;Ð border-left: 7px solid transparent;Ð border-right: 7px solid transparent;Ð border-bottom: 7px solid #ccc;Ð border-top: 0;Ð border-bottom-color: rgba(0, 0, 0, 0.2);Ð position: absolute;ÐÐ .datepicker-dropdown:after {Ð content: '';Ð display: inline-block;Ð border-left: 6px solid transparent;Ð border-right: 6px solid transparent;Ð border-bottom: 6px solid #fff;Ð border-top: 0;Ð position: absolute;ÐÐdatepicker-dropdown.datepicker-orient-left:before {Ð left: 6px;ÐÐdatepicker-dropdown.datepicker-orient-left:after {Ð left: 7px;ÐÐdatepicker-dropdown.datepicker-orient-right:before {Ð right: 6px;ÐÐdatepicker-dropdown.datepicker-orient-right:after {Ð right: 7px;ÐÐdatepicker-dropdown.datepicker-orient-top:before {Ð top: -7px;ÐÐdatepicker-dropdown.datepicker-orient-top:after {Ð top: -6px;ÐÐdatepicker-dropdown.datepicker-orient-bottom:before {Ð bottom: -7px;Ð border-bottom: 0;Ð border-top: 7px solid #999;ÐÐdatepicker-dropdown.datepicker-orient-bottom:after {Ð bottom: -6px;Ð border-bottom: 0;Ð border-top: 6px solid #fff;ÐÐ .datepicker > div {Ð display: none;ÐÐdatepicker.days div.datepicker-days {Ð display: block;ÐÐdatepicker.months div.datepicker-months {Ð display: block;ÐÐ .datepicker.years div.datepicker-years {Ð display: block;ÐÐdatepicker table {Ð margin: 0;Ð -webkit-touch-callout: none;Ð -webkit-user-select: none;Ð -khtml-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð user-select: none;ÐÐdatepicker table tr td,Ðdatepicker table tr th {Ð text-align: center;Ð width: 30px;Ð height: 30px;Ð border-radius: 4px;Ð border: none;ÐÐtable-striped .datepicker table tr td,Ðtable-striped .datepicker table tr th {Ð background-color: transparent;ÐÐdatepicker table tr td.day:hover,Ð .datepicker table tr td.day.focused {Ð background: #eeeeee;Ð cursor: pointer;ÐÐ .datepicker table tr td.old,Ðdatepicker table tr td.new {Ð color: #999999;ÐÐ .datepicker table tr td.disabled,Ðdatepicker table tr td.disabled:hover {Ð background: none;Ð color: #999999;Ð cursor: default;ÐÐdatepicker table tr td.today,Ðdatepicker table tr td.today:hover,Ðdatepicker table tr td.today.disabled,Ðdatepicker table tr td.today.disabled:hover {Ð color: #000000;Ð background-color: #ffdb99;Ð border-color: #ffb733;ÐÐdatepicker table tr td.today:hover,Ðdatepicker table tr td.today:hover:hover,Ðdatepicker table tr td.today.disabled:hover,Ðdatepicker table tr td.today.disabled:hover:hover,Ðdatepicker table tr td.today:focus,Ðdatepicker table tr td.today:hover:focus,Ðdatepicker table tr td.today.disabled:focus,Ð .datepicker table tr td.today.disabled:hover:focus,Ðdatepicker table tr td.today:active,Ðdatepicker table tr td.today:hover:active,Ðdatepicker table tr td.today.disabled:active,Ðdatepicker table tr td.today.disabled:hover:active,Ðdatepicker table tr td.today.active,Ð .datepicker table tr td.today:hover.active,Ðdatepicker table tr td.today.disabled.active,Ðdatepicker table tr td.today.disabled:hover.active,Ð .open .dropdown-toggle.datepicker table tr td.today,Ðopen .dropdown-toggle.datepicker table tr td.today:hover,Ðopen .dropdown-toggle.datepicker table tr td.today.disabled,Ðopen .dropdown-toggle.datepicker table tr td.today.disabled:hover {Ð color: #000000;Ð background-color: #ffcd70;Ð border-color: #f59e00;ÐÐdatepicker table tr td.today:active,Ðdatepicker table tr td.today:hover:active,Ðdatepicker table tr td.today.disabled:active,Ð .datepicker table tr td.today.disabled:hover:active,Ðdatepicker table tr td.today.active,Ðdatepicker table tr td.today:hover.active,Ðdatepicker table tr td.today.disabled.active,Ðdatepicker table tr td.today.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr td.today,Ð

.open .dropdown-toggle.datepicker table tr td.today:hover,Ð
.open .dropdown-toggle.datepicker table tr td.today.disabled,Ðopen .dropdown-
toggle.datepicker table tr td.today.disabled:hover {Ð background-image: none;ÞÐ
.datepicker table tr td.today.disabled,Ðdatepicker table tr
td.today:hover.disabled,Ðdatepicker table tr td.today.disabled.disabled,Ð
.datepicker table tr td.today.disabled:hover.disabled,Ðdatepicker table tr
td.today[disabled],Ðdatepicker table tr td.today:hover[disabled],Ðdatepicker
table tr td.today.disabled[disabled],Ðdatepicker table tr
td.today.disabled:hover[disabled],Ðfieldset[disabled] .datepicker table tr
td.today,Ðfieldset[disabled] .datepicker table tr td.today:hover,Ð
fieldset[disabled] .datepicker table tr td.today.disabled,Ð
fieldset[disabled] .datepicker table tr td.today.disabled:hover,Ðdatepicker
table tr td.today.disabled:hover,Ðdatepicker table tr
td.today:hover.disabled:hover,Ðdatepicker table tr
td.today.disabled.disabled:hover,Ðdatepicker table tr
td.today.disabled:hover.disabled:hover,Ðdatepicker table tr
td.today[disabled]:hover,Ðdatepicker table tr td.today:hover[disabled]:hover,Ð
.datepicker table tr td.today.disabled[disabled]:hover,Ðdatepicker table tr
td.today.disabled:hover[disabled]:hover,Ðfieldset[disabled] .datepicker table
tr td.today:hover,Ðfieldset[disabled] .datepicker table tr
td.today:hover:hover,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:hover,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:hover:hover,Ðdatepicker table tr td.today.disabled:focus,Ð
.datepicker table tr td.today:hover.disabled:focus,Ðdatepicker table tr
td.today.disabled.disabled:focus,Ðdatepicker table tr
td.today.disabled:hover.disabled:focus,Ðdatepicker table tr
td.today[disabled]:focus,Ðdatepicker table tr td.today:hover[disabled]:focus,Ð
.datepicker table tr td.today.disabled[disabled]:focus,Ðdatepicker table tr
td.today.disabled:hover[disabled]:focus,Ðfieldset[disabled] .datepicker table
tr td.today:focus,Ðfieldset[disabled] .datepicker table tr
td.today:hover:focus,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:focus,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:hover:focus,Ðdatepicker table tr td.today.disabled:active,Ð
.datepicker table tr td.today:hover.disabled:active,Ðdatepicker table tr
td.today.disabled.disabled:active,Ðdatepicker table tr
td.today.disabled:hover.disabled:active,Ðdatepicker table tr
td.today[disabled]:active,Ðdatepicker table tr
td.today:hover[disabled]:active,Ðdatepicker table tr
td.today.disabled[disabled]:active,Ðdatepicker table tr
td.today.disabled:hover[disabled]:active,Ðfieldset[disabled] .datepicker table
tr td.today:active,Ðfieldset[disabled] .datepicker table tr
td.today:hover:active,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:active,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:hover:active,Ðdatepicker table tr td.today.disabled.active,Ð
.datepicker table tr td.today:hover.disabled.active,Ðdatepicker table tr
td.today.disabled.disabled.active,Ðdatepicker table tr
td.today.disabled:hover.disabled.active,Ðdatepicker table tr
td.today[disabled].active,Ðdatepicker table tr
td.today:hover[disabled].active,Ðdatepicker table tr
td.today.disabled[disabled].active,Ðdatepicker table tr
td.today.disabled:hover[disabled].active,Ðfieldset[disabled] .datepicker table
tr td.today.active,Ðfieldset[disabled] .datepicker table tr
td.today:hover.active,Ðfieldset[disabled] .datepicker table tr
td.today.disabled.active,Ðfieldset[disabled] .datepicker table tr
td.today.disabled:hover.active {Ð background-color: #ffdb99;Ð border-color:
#ffb733;ÞÐdatepicker table tr td.today:hover:hover {Ð color: #000;ÞÐ
.datepicker table tr td.today.active:hover {Ð color: #fff;ÞÐdatepicker table
tr td.range,Ðdatepicker table tr td.range:hover,Ðdatepicker table tr
td.range.disabled,Ðdatepicker table tr td.range.disabled:hover {Ð background:
#eeeeee;Ð

border-radius: 0;ÐÐdatepicker table tr td.range.today,Ðdatepicker
table tr td.range.today:hover,Ðdatepicker table tr td.range.today.disabled,Ð
.datepicker table tr td.range.today.disabled:hover {Ð color: #000000;Ð
background-color: #f7ca77;Ð border-color: #f1a417;Ð border-radius: 0;ÐÐ
.datepicker table tr td.range.today:hover,Ðdatepicker table tr
td.range.today:hover:hover,Ðdatepicker table tr td.range.today.disabled:hover,Ð
.datepicker table tr td.range.today.disabled:hover:hover,Ðdatepicker table tr
td.range.today:focus,Ðdatepicker table tr td.range.today:hover:focus,Ð
.datepicker table tr td.range.today.disabled:focus,Ðdatepicker table tr
td.range.today.disabled:hover:focus,Ðdatepicker table tr
td.range.today:active,Ðdatepicker table tr td.range.today:hover:active,Ð
.datepicker table tr td.range.today.disabled:active,Ðdatepicker table tr
td.range.today.disabled:hover:active,Ðdatepicker table tr
td.range.today.active,Ðdatepicker table tr td.range.today:hover.active,Ð
.datepicker table tr td.range.today.disabled.active,Ðdatepicker table tr
td.range.today.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table
tr td.range.today,Ðopen .dropdown-toggle.datepicker table tr
td.range.today:hover,Ðopen .dropdown-toggle.datepicker table tr
td.range.today.disabled,Ðopen .dropdown-toggle.datepicker table tr
td.range.today.disabled:hover {Ð color: #000000;Ð background-color: #f4bb51;Ð
border-color: #bf800c;ÐÐdatepicker table tr td.range.today:active,Ðdatepicker
table tr td.range.today:hover:active,Ðdatepicker table tr
td.range.today.disabled:active,Ðdatepicker table tr
td.range.today.disabled:hover:active,Ðdatepicker table tr
td.range.today.active,Ðdatepicker table tr td.range.today:hover.active,Ð
.datepicker table tr td.range.today.disabled.active,Ðdatepicker table tr
td.range.today.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table
tr td.range.today,Ðopen .dropdown-toggle.datepicker table tr
td.range.today:hover,Ðopen .dropdown-toggle.datepicker table tr
td.range.today.disabled,Ðopen .dropdown-toggle.datepicker table tr
td.range.today.disabled:hover {Ð background-image: none;ÐÐdatepicker table tr
td.range.today.disabled,Ðdatepicker table tr td.range.today:hover.disabled,Ð
.datepicker table tr td.range.today.disabled.disabled,Ðdatepicker table tr
td.range.today.disabled:hover.disabled,Ðdatepicker table tr
td.range.today[disabled],Ðdatepicker table tr td.range.today:hover[disabled],Ð
.datepicker table tr td.range.today.disabled[disabled],Ðdatepicker table tr
td.range.today.disabled:hover[disabled],Ðfieldset[disabled] .datepicker table
tr td.range.today,Ðfieldset[disabled] .datepicker table tr
td.range.today:hover,Ðfieldset[disabled] .datepicker table tr
td.range.today.disabled,Ðfieldset[disabled] .datepicker table tr
td.range.today.disabled:hover,Ðdatepicker table tr
td.range.today.disabled:hover,Ðdatepicker table tr
td.range.today:hover.disabled:hover,Ðdatepicker table tr
td.range.today.disabled.disabled:hover,Ðdatepicker table tr
td.range.today.disabled:hover.disabled:hover,Ðdatepicker table tr
td.range.today[disabled]:hover,Ðdatepicker table tr
td.range.today:hover[disabled]:hover,Ðdatepicker table tr
td.range.today.disabled[disabled]:hover,Ðdatepicker table tr
td.range.today.disabled:hover[disabled]:hover,Ðfieldset[disabled] .datepicker
table tr td.range.today:hover,Ðfieldset[disabled] .datepicker table tr
td.range.today:hover:hover,Ðfieldset[disabled] .datepicker table tr
td.range.today.disabled:hover,Ðfieldset[disabled] .datepicker table tr
td.range.today.disabled:hover:hover,Ðdatepicker table tr
td.range.today.disabled:focus,Ðdatepicker table tr
td.range.today:hover.disabled:focus,Ðdatepicker table tr
td.range.today.disabled.disabled:focus,Ðdatepicker table tr
td.range.today.disabled:hover.disabled:focus,Ðdatepicker table tr
td.range.today[disabled]:focus,Ðdatepicker table tr
td.range.today:hover[disabled]:focus,Ðdatepicker table tr
td.range.today.disabled[disabled]:focus,Ð

.datepicker table tr td.range.today.disabled:hover[disabled]:focus,Ðfieldset[disabled] .datepicker table tr td.range.today:focus,Ðfieldset[disabled] .datepicker table tr td.range.today:hover:focus,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled:focus,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled:hover:focus,Ðdatepicker table tr td.range.today.disabled:active,Ðdatepicker table tr td.range.today:hover.disabled:active,Ðdatepicker table tr td.range.today.disabled.disabled:active,Ðdatepicker table tr td.range.today.disabled:hover.disabled:active,Ðdatepicker table tr td.range.today[disabled]:active,Ðdatepicker table tr td.range.today:hover[disabled]:active,Ðdatepicker table tr td.range.today.disabled[disabled]:active,Ðdatepicker table tr td.range.today.disabled:hover[disabled]:active,Ðfieldset[disabled] .datepicker table tr td.range.today:active,Ðfieldset[disabled] .datepicker table tr td.range.today:hover:active,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled:active,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled:hover:active,Ðdatepicker table tr td.range.today.disabled.active,Ðdatepicker table tr td.range.today:hover.disabled.active,Ðdatepicker table tr td.range.today.disabled.disabled.active,Ðdatepicker table tr td.range.today.disabled:hover.disabled.active,Ðdatepicker table tr td.range.today[disabled].active,Ðdatepicker table tr td.range.today:hover[disabled].active,Ðdatepicker table tr td.range.today.disabled[disabled].active,Ðdatepicker table tr td.range.today.disabled:hover[disabled].active,Ðfieldset[disabled] .datepicker table tr td.range.today.active,Ðfieldset[disabled] .datepicker table tr td.range.today:hover.active,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled.active,Ðfieldset[disabled] .datepicker table tr td.range.today.disabled:hover.active {Ð background-color: #f7ca77;Ð border-color: #f1a417;ÐÐdatepicker table tr td.selected,Ðdatepicker table tr td.selected:hover,Ðdatepicker table tr td.selected.disabled,Ðdatepicker table tr td.selected.disabled:hover {Ð color: #ffffff;Ð background-color: #999999;Ð border-color: #555555;Ð text-shadow: 0 -1px 0 rgba(0, 0, 0, 0.25);ÐÐ .datepicker table tr td.selected:hover,Ðdatepicker table tr td.selected:hover:hover,Ðdatepicker table tr td.selected.disabled:hover,Ð .datepicker table tr td.selected.disabled:hover:hover,Ðdatepicker table tr td.selected:focus,Ðdatepicker table tr td.selected:hover:focus,Ðdatepicker table tr td.selected.disabled:focus,Ðdatepicker table tr td.selected.disabled:hover:focus,Ðdatepicker table tr td.selected:active,Ð .datepicker table tr td.selected:hover:active,Ðdatepicker table tr td.selected.disabled:active,Ðdatepicker table tr td.selected.disabled:hover:active,Ðdatepicker table tr td.selected.active,Ð .datepicker table tr td.selected:hover.active,Ðdatepicker table tr td.selected.disabled.active,Ðdatepicker table tr td.selected.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr td.selected,Ðopen .dropdown-toggle.datepicker table tr td.selected:hover,Ð .open .dropdown-toggle.datepicker table tr td.selected.disabled,Ð .open .dropdown-toggle.datepicker table tr td.selected.disabled:hover {Ð color: #ffffff;Ð background-color: #858585;Ð border-color: #373737;ÐÐ .datepicker table tr td.selected:active,Ðdatepicker table tr td.selected:hover:active,Ðdatepicker table tr td.selected.disabled:active,Ð .datepicker table tr td.selected.disabled:hover:active,Ðdatepicker table tr td.selected.active,Ðdatepicker table tr td.selected:hover.active,Ðdatepicker table tr td.selected.disabled.active,Ðdatepicker table tr td.selected.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr td.selected,Ðopen .dropdown-toggle.datepicker table tr td.selected:hover,Ð .open .dropdown-toggle.datepicker table tr td.selected.disabled,Ð .open .dropdown-toggle.datepicker table tr td.selected.disabled:hover {Ð background-image: none;Ð

}Ðdatepicker table tr td.selected.disabled,Ðdatepicker table tr td.selected:hover.disabled,Ðdatepicker table tr td.selected.disabled.disabled,Ðdatepicker table tr td.selected.disabled:hover.disabled,Ðdatepicker table tr td.selected[disabled],Ðdatepicker table tr td.selected:hover[disabled],Ð .datepicker table tr td.selected.disabled[disabled],Ðdatepicker table tr td.selected.disabled:hover[disabled],Ðfieldset[disabled] .datepicker table tr td.selected,Ðfieldset[disabled] .datepicker table tr td.selected:hover,Ð fieldset[disabled] .datepicker table tr td.selected.disabled,Ð fieldset[disabled] .datepicker table tr td.selected.disabled:hover,Ð .datepicker table tr td.selected.disabled:hover,Ðdatepicker table tr td.selected:hover.disabled:hover,Ðdatepicker table tr td.selected.disabled.disabled:hover,Ðdatepicker table tr td.selected.disabled:hover.disabled:hover,Ðdatepicker table tr td.selected[disabled]:hover,Ðdatepicker table tr td.selected:hover[disabled]:hover,Ðdatepicker table tr td.selected.disabled[disabled]:hover,Ðdatepicker table tr td.selected.disabled:hover[disabled]:hover,Ðfieldset[disabled] .datepicker table tr td.selected:hover,Ðfieldset[disabled] .datepicker table tr td.selected:hover:hover,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:hover,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:hover:hover,Ðdatepicker table tr td.selected.disabled:focus,Ðdatepicker table tr td.selected:hover.disabled:focus,Ðdatepicker table tr td.selected.disabled.disabled:focus,Ðdatepicker table tr td.selected.disabled:hover.disabled:focus,Ðdatepicker table tr td.selected[disabled]:focus,Ðdatepicker table tr td.selected:hover[disabled]:focus,Ðdatepicker table tr td.selected.disabled[disabled]:focus,Ðdatepicker table tr td.selected.disabled:hover[disabled]:focus,Ðfieldset[disabled] .datepicker table tr td.selected:focus,Ðfieldset[disabled] .datepicker table tr td.selected:hover:focus,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:focus,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:hover:focus,Ðdatepicker table tr td.selected.disabled:active,Ðdatepicker table tr td.selected:hover.disabled:active,Ðdatepicker table tr td.selected.disabled.disabled:active,Ðdatepicker table tr td.selected.disabled:hover.disabled:active,Ðdatepicker table tr td.selected[disabled]:active,Ðdatepicker table tr td.selected:hover[disabled]:active,Ðdatepicker table tr td.selected.disabled[disabled]:active,Ðdatepicker table tr td.selected.disabled:hover[disabled]:active,Ðfieldset[disabled] .datepicker table tr td.selected:active,Ðfieldset[disabled] .datepicker table tr td.selected:hover:active,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:active,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:hover:active,Ðdatepicker table tr td.selected.disabled.active,Ðdatepicker table tr td.selected:hover.disabled.active,Ðdatepicker table tr td.selected.disabled.disabled.active,Ðdatepicker table tr td.selected.disabled:hover.disabled.active,Ðdatepicker table tr td.selected[disabled].active,Ðdatepicker table tr td.selected:hover[disabled].active,Ðdatepicker table tr td.selected.disabled[disabled].active,Ðdatepicker table tr td.selected.disabled:hover[disabled].active,Ðfieldset[disabled] .datepicker table tr td.selected.active,Ðfieldset[disabled] .datepicker table tr td.selected:hover.active,Ðfieldset[disabled] .datepicker table tr td.selected.disabled.active,Ðfieldset[disabled] .datepicker table tr td.selected.disabled:hover.active {Ð background-color: #999999;Ð border-color: #555555;}ÐÐdatepicker table tr td.active,Ðdatepicker table tr td.active:hover,Ð

.datepicker table tr td.active.disabled,Ðdatepicker table tr td.active.disabled:hover {Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #357ebd;Ð text-shadow: 0 -1px 0 rgba(0, 0, 0, 0.25);ÐÐ .datepicker table tr td.active:hover,Ðdatepicker table tr td.active:hover:hover,Ðdatepicker table tr td.active.disabled:hover,Ð .datepicker table tr td.active.disabled:hover:hover,Ðdatepicker table tr td.active:focus,Ðdatepicker table tr td.active:hover:focus,Ðdatepicker table tr td.active.disabled:focus,Ðdatepicker table tr td.active.disabled:hover:focus,Ðdatepicker table tr td.active:active,Ð .datepicker table tr td.active:hover:active,Ðdatepicker table tr td.active.disabled:active,Ðdatepicker table tr td.active.disabled:hover:active,Ðdatepicker table tr td.active.active,Ð .datepicker table tr td.active:hover.active,Ðdatepicker table tr td.active.disabled.active,Ðdatepicker table tr td.active.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr td.active,Ðopen .dropdown-toggle.datepicker table tr td.active:hover,Ð .open .dropdown-toggle.datepicker table tr td.active.disabled,Ðopen .dropdown-toggle.datepicker table tr td.active.disabled:hover {Ð color: #ffffff;Ð background-color: #3276b1;Ð border-color: #285e8e;ÐÐdatepicker table tr td.active:active,Ðdatepicker table tr td.active:hover:active,Ðdatepicker table tr td.active.disabled:active,Ðdatepicker table tr td.active.disabled:hover:active,Ðdatepicker table tr td.active.active,Ð .datepicker table tr td.active:hover.active,Ðdatepicker table tr td.active.disabled.active,Ðdatepicker table tr td.active.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr td.active,Ðopen .dropdown-toggle.datepicker table tr td.active:hover,Ð .open .dropdown-toggle.datepicker table tr td.active.disabled,Ðopen .dropdown-toggle.datepicker table tr td.active.disabled:hover {Ð background-image: none;Ð }Ðdatepicker table tr td.active.disabled,Ðdatepicker table tr td.active:hover.disabled,Ðdatepicker table tr td.active.disabled.disabled,Ð .datepicker table tr td.active.disabled:hover.disabled,Ðdatepicker table tr td.active[disabled],Ðdatepicker table tr td.active:hover[disabled],Ð .datepicker table tr td.active.disabled[disabled],Ðdatepicker table tr td.active.disabled:hover[disabled],Ðfieldset[disabled] .datepicker table tr td.active,Ðfieldset[disabled] .datepicker table tr td.active:hover,Ð fieldset[disabled] .datepicker table tr td.active.disabled,Ð fieldset[disabled] .datepicker table tr td.active.disabled:hover,Ðdatepicker table tr td.active.disabled:hover,Ðdatepicker table tr td.active:hover.disabled:hover,Ðdatepicker table tr td.active.disabled.disabled:hover,Ðdatepicker table tr td.active.disabled:hover.disabled:hover,Ðdatepicker table tr td.active[disabled]:hover,Ðdatepicker table tr td.active:hover[disabled]:hover,Ðdatepicker table tr td.active.disabled[disabled]:hover,Ðdatepicker table tr td.active.disabled:hover[disabled]:hover,Ðfieldset[disabled] .datepicker table tr td.active:hover,Ðfieldset[disabled] .datepicker table tr td.active:hover:hover,Ðfieldset[disabled] .datepicker table tr td.active.disabled:hover,Ðfieldset[disabled] .datepicker table tr td.active.disabled:hover:hover,Ðdatepicker table tr td.active.disabled:focus,Ð .datepicker table tr td.active:hover.disabled:focus,Ðdatepicker table tr td.active.disabled.disabled:focus,Ðdatepicker table tr td.active.disabled:hover.disabled:focus,Ðdatepicker table tr td.active[disabled]:focus,Ðdatepicker table tr td.active:hover[disabled]:focus,Ðdatepicker table tr td.active.disabled[disabled]:focus,Ðdatepicker table tr td.active.disabled:hover[disabled]:focus,Ðfieldset[disabled] .datepicker table tr td.active:focus,Ðfieldset[disabled] .datepicker table tr td.active:hover:focus,Ðfieldset[disabled] .datepicker table tr td.active.disabled:focus,Ðfieldset[disabled] .datepicker table tr td.active.disabled:hover:focus,Ð

.datepicker table tr td.active.disabled:active,Ð
.datepicker table tr td.active:hover.disabled:active,Ðdatepicker table tr
td.active.disabled.disabled:active,Ðdatepicker table tr
td.active.disabled:hover.disabled:active,Ðdatepicker table tr
td.active[disabled]:active,Ðdatepicker table tr
td.active:hover[disabled]:active,Ðdatepicker table tr
td.active.disabled[disabled]:active,Ðdatepicker table tr
td.active.disabled:hover[disabled]:active,Ðfieldset[disabled] .datepicker
table tr td.active:active,Ðfieldset[disabled] .datepicker table tr
td.active:hover:active,Ðfieldset[disabled] .datepicker table tr
td.active.disabled:active,Ðfieldset[disabled] .datepicker table tr
td.active.disabled:hover:active,Ðdatepicker table tr
td.active.disabled.active,Ðdatepicker table tr
td.active:hover.disabled.active,Ðdatepicker table tr
td.active.disabled.disabled.active,Ðdatepicker table tr
td.active.disabled:hover.disabled.active,Ðdatepicker table tr
td.active[disabled].active,Ðdatepicker table tr
td.active:hover[disabled].active,Ðdatepicker table tr
td.active.disabled[disabled].active,Ðdatepicker table tr
td.active.disabled:hover[disabled].active,Ðfieldset[disabled] .datepicker
table tr td.active.active,Ðfieldset[disabled] .datepicker table tr
td.active:hover.active,Ðfieldset[disabled] .datepicker table tr
td.active.disabled.active,Ðfieldset[disabled] .datepicker table tr
td.active.disabled:hover.active {Ð background-color: #428bca;Ð border-color:
#357ebd;ÐÐÐdatepicker table tr td span {Ð display: block;Ð width: 23%;Ð
height: 54px;Ð line-height: 54px;Ð float: left;Ð margin: 1%;Ð cursor: pointer;Ð
  border-radius: 4px;ÐÐÐdatepicker table tr td span:hover {Ð background:
#eeeeee;ÐÐÐdatepicker table tr td span.disabled,Ðdatepicker table tr td
span.disabled:hover {Ð background: none;Ð color: #999999;Ð cursor: default;ÐÐÐ
.datepicker table tr td span.active,Ðdatepicker table tr td span.active:hover,Ð
.datepicker table tr td span.active.disabled,Ðdatepicker table tr td
span.active.disabled:hover {Ð color: #ffffff;Ð background-color: #428bca;Ð
border-color: #357ebd;Ð text-shadow: 0 -1px 0 rgba(0, 0, 0, 0.25);ÐÐÐ
.datepicker table tr td span.active:hover,Ðdatepicker table tr td
span.active:hover:hover,Ðdatepicker table tr td span.active.disabled:hover,Ð
.datepicker table tr td span.active.disabled:hover:hover,Ðdatepicker table tr
td span.active:focus,Ðdatepicker table tr td span.active:hover:focus,Ð
.datepicker table tr td span.active.disabled:focus,Ðdatepicker table tr td
span.active.disabled:hover:focus,Ðdatepicker table tr td span.active:active,Ð
.datepicker table tr td span.active:hover:active,Ðdatepicker table tr td
span.active.disabled:active,Ðdatepicker table tr td
span.active.disabled:hover:active,Ðdatepicker table tr td span.active.active,Ð
.datepicker table tr td span.active:hover.active,Ðdatepicker table tr td
span.active.disabled.active,Ðdatepicker table tr td
span.active.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr
td span.active,Ðopen .dropdown-toggle.datepicker table tr td
span.active:hover,Ðopen .dropdown-toggle.datepicker table tr td
span.active.disabled,Ðopen .dropdown-toggle.datepicker table tr td
span.active.disabled:hover {Ð color: #ffffff;Ð background-color: #3276b1;Ð
border-color: #285e8e;ÐÐÐdatepicker table tr td span.active:active,Ðdatepicker
table tr td span.active:hover:active,Ðdatepicker table tr td
span.active.disabled:active,Ðdatepicker table tr td
span.active.disabled:hover:active,Ðdatepicker table tr td span.active.active,Ð
.datepicker table tr td span.active:hover.active,Ðdatepicker table tr td
span.active.disabled.active,Ðdatepicker table tr td
span.active.disabled:hover.active,Ðopen .dropdown-toggle.datepicker table tr
td span.active,Ðopen .dropdown-toggle.datepicker table tr td
span.active:hover,Ðopen .dropdown-toggle.datepicker table tr td
span.active.disabled,Ðopen .dropdown-toggle.datepicker table tr td
span.active.disabled:hover {Ð

background-image: none;ÐÐdatepicker table tr td span.active.disabled,Ðdatepicker table tr td span.active:hover.disabled,Ð .datepicker table tr td span.active.disabled.disabled,Ðdatepicker table tr td span.active.disabled:hover.disabled,Ðdatepicker table tr td span.active[disabled],Ðdatepicker table tr td span.active:hover[disabled],Ð .datepicker table tr td span.active.disabled[disabled],Ðdatepicker table tr td span.active.disabled:hover[disabled],Ðfieldset[disabled] .datepicker table tr td span.active,Ðfieldset[disabled] .datepicker table tr td span.active:hover,Ðfieldset[disabled] .datepicker table tr td span.active.disabled,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover,Ðdatepicker table tr td span.active.disabled:hover,Ð .datepicker table tr td span.active:hover.disabled:hover,Ðdatepicker table tr td span.active.disabled.disabled:hover,Ðdatepicker table tr td span.active.disabled:hover.disabled:hover,Ðdatepicker table tr td span.active[disabled]:hover,Ðdatepicker table tr td span.active:hover[disabled]:hover,Ðdatepicker table tr td span.active.disabled[disabled]:hover,Ðdatepicker table tr td span.active.disabled:hover[disabled]:hover,Ðfieldset[disabled] .datepicker table tr td span.active:hover,Ðfieldset[disabled] .datepicker table tr td span.active:hover:hover,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover:hover,Ðdatepicker table tr td span.active.disabled:focus,Ðdatepicker table tr td span.active:hover.disabled:focus,Ðdatepicker table tr td span.active.disabled.disabled:focus,Ðdatepicker table tr td span.active.disabled:hover.disabled:focus,Ðdatepicker table tr td span.active[disabled]:focus,Ðdatepicker table tr td span.active:hover[disabled]:focus,Ðdatepicker table tr td span.active.disabled[disabled]:focus,Ðdatepicker table tr td span.active.disabled:hover[disabled]:focus,Ðfieldset[disabled] .datepicker table tr td span.active:focus,Ðfieldset[disabled] .datepicker table tr td span.active:hover:focus,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:focus,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover:focus,Ðdatepicker table tr td span.active.disabled:active,Ðdatepicker table tr td span.active:hover.disabled:active,Ðdatepicker table tr td span.active.disabled.disabled:active,Ðdatepicker table tr td span.active.disabled:hover.disabled:active,Ðdatepicker table tr td span.active[disabled]:active,Ðdatepicker table tr td span.active:hover[disabled]:active,Ðdatepicker table tr td span.active.disabled[disabled]:active,Ðdatepicker table tr td span.active.disabled:hover[disabled]:active,Ðfieldset[disabled] .datepicker table tr td span.active:active,Ðfieldset[disabled] .datepicker table tr td span.active:hover:active,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:active,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover:active,Ðdatepicker table tr td span.active.disabled.active,Ðdatepicker table tr td span.active:hover.disabled.active,Ðdatepicker table tr td span.active.disabled.disabled.active,Ðdatepicker table tr td span.active.disabled:hover.disabled.active,Ðdatepicker table tr td span.active[disabled].active,Ðdatepicker table tr td span.active:hover[disabled].active,Ðdatepicker table tr td span.active.disabled[disabled].active,Ðdatepicker table tr td span.active.disabled:hover[disabled].active,Ðfieldset[disabled] .datepicker table tr td span.active.active,Ðfieldset[disabled] .datepicker table tr td span.active:hover.active,Ðfieldset[disabled] .datepicker table tr td span.active.disabled.active,Ðfieldset[disabled] .datepicker table tr td span.active.disabled:hover.active {Ð background-color: #428bca;Ð border-color: #357ebd;ÐÐdatepicker table tr td span.old,Ðdatepicker table tr td span.new {Ð

color: #999999;ÐÐdatepicker th.datepicker-switch {Ð width: 145px;ÐÐ
.datepicker thead tr:first-child th,Ðdatepicker tfoot tr th {Ð cursor:
pointer;ÐÐdatepicker thead tr:first-child th:hover,Ðdatepicker tfoot tr
th:hover {Ð background: #eeeeee;ÐÐdatepicker .cw {Ð font-size: 10px;Ð width:
12px;Ð padding: 0 2px 0 5px;Ð vertical-align: middle;ÐÐdatepicker thead
tr:first-child th.cw {Ð cursor: default;Ð background-color: transparent;ÐÐ
.input-group.date .input-group-addon i {Ð cursor: pointer;Ð width: 16px;Ð
height: 16px;ÐÐinput-daterange input {Ð text-align: center;ÐÐinput-daterange
input:first-child {Ð border-radius: 3px 0 0 3px;ÐÐinput-daterange input:last-
child {Ð border-radius: 0 3px 3px 0;ÐÐinput-daterange .input-group-addon {Ð
width: auto;Ð min-width: 16px;Ð padding: 4px 5px;Ð font-weight: normal;Ð line-
height: 1.428571429;Ð text-align: center;Ð text-shadow: 0 1px 0 #fff;Ð
vertical-align: middle;Ð background-color: #eeeeee;Ð border-width: 1px 0;Ð
margin-left: -5px;Ð margin-right: -5px;ÐÐdatepicker.dropdown-menu {Ð
position: absolute;Ð top: 100%;Ð left: 0;Ð z-index: 1000;Ð float: left;Ð
display: none;Ð min-width: 160px;Ð list-style: none;Ð background-color:
#ffffff;Ð border: 1px solid #ccc;Ð border: 1px solid rgba(0, 0, 0, 0.2);Ð
border-radius: 5px;Ð -webkit-box-shadow: 0 5px 10px rgba(0, 0, 0, 0.2);Ð -moz-
box-shadow: 0 5px 10px rgba(0, 0, 0, 0.2);Ð box-shadow: 0 5px 10px rgba(0, 0,
0, 0.2);Ð -webkit-background-clip: padding-box;Ð -moz-background-clip:
padding;Ð background-clip: padding-box;Ð *border-right-width: 2px;Ð *border-
bottom-width: 2px;Ð color: #333333;Ð font-family: "Helvetica Neue",
Helvetica, Arial, sans-serif;Ð font-size: 13px;Ð line-height: 1.428571429;ÐÐ
.datepicker.dropdown-menu th,Ðdatepicker.dropdown-menu td {Ð padding: 4px 5px;Ð
}Ð

public\assets\css\plugins\daterangepicker\daterangepicker-bs3.css

/*!Ð* Stylesheet for the Date Range Picker, for use with Bootstrap 3.xÐ*Ð* Copyright 2013-2015 Dan Grossman (http://www.dangrossman.info)Ð* Licensed under the MIT license. See http://www.opensource.org/licenses/mit-license.phpÐ *Ð* Built for http://www.improvely.comÐ*/Ð.daterangepicker.dropdown-menu {Ð max-width: none;Ð z-index: 3000;ÐÐ
.daterangepicker.opensleft .ranges, .daterangepicker.opensleft .calendar {Ð float: left;Ð margin: 4px;ÐÐ
.daterangepicker.opensright .ranges, .daterangepicker.opensright .calendar,Ð
.daterangepicker.openscenter .ranges, .daterangepicker.openscenter .calendar {Ð
  float: right;Ð margin: 4px;ÐÐ
.daterangepicker.single .ranges, .daterangepicker.single .calendar {Ð float: none;ÐÐdaterangepicker .ranges {Ð width: 160px;Ð text-align: left;ÐÐ
.daterangepicker .ranges .range_inputs>div {Ð float: left;ÐÐ
.daterangepicker .ranges .range_inputs>div:nth-child(2) {Ð padding-left: 11px;Ð }ÐÐdaterangepicker .calendar {Ð display: none;Ð max-width: 270px;ÐÐ
.daterangepicker.show-calendar .calendar {Ð   display: block;ÐÐ
.daterangepicker .calendar.single .calendar-date {Ð border: none;ÐÐ
.daterangepicker .calendar th, .daterangepicker .calendar td {Ð font-family: 'Helvetica Neue', Helvetica, Arial, sans-serif;Ð white-space: nowrap;Ð text-align: center;Ð min-width: 32px;ÐÐ
.daterangepicker .daterangepicker_start_input label,Ð
.daterangepicker .daterangepicker_end_input label {Ð color: #333;Ð display: block;Ð font-size: 11px;Ð font-weight: normal;Ð height: 20px;Ð line-height: 20px;Ð margin-bottom: 2px;Ð text-shadow: #fff 1px 1px 0px;Ð text-transform: uppercase;Ð width: 74px;ÐÐdaterangepicker .ranges input {Ð font-size: 11px;ÐÐ
.daterangepicker .ranges .input-mini {Ð border: 1px solid #ccc;Ð border-radius: 4px;Ð color: #555;Ð display: block;Ð font-size: 11px;Ð height: 30px;Ð line-height: 30px;Ð vertical-align: middle;Ð margin: 0 0 10px 0;Ð padding: 0 6px;Ð width: 74px;ÐÐdaterangepicker .ranges ul {Ð list-style: none;Ð margin: 0;Ð padding: 0;ÐÐdaterangepicker .ranges li {Ð font-size: 13px;Ð background: #f5f5f5;Ð border: 1px solid #f5f5f5;Ð color: #08c;Ð padding: 3px 12px;Ð margin-bottom: 8px;Ð -webkit-border-radius: 5px;Ð -moz-border-radius: 5px;Ð border-radius: 5px;Ð cursor: pointer;ÐÐdaterangepicker .ranges li.active, .daterangepicker .ranges li:hover {Ð background: #08c;Ð border: 1px solid #08c;Ð color: #fff;ÐÐdaterangepicker .calendar-date {Ð border: 1px solid #ddd;Ð padding: 4px;Ð border-radius: 4px;Ð background: #fff;ÐÐ
.daterangepicker .calendar-time {Ð text-align: center;Ð margin: 8px auto 0 auto;Ð line-height: 30px;ÐÐdaterangepicker {Ð position: absolute;Ð background: #fff;Ð top: 100px;Ð left: 20px;Ð padding: 4px;Ð margin-top: 1px;Ð -webkit-border-radius: 4px;Ð -moz-border-radius: 4px;Ð border-radius: 4px;ÐÐ
.daterangepicker.opensleft:before {Ð position: absolute;Ð top: -7px;Ð right: 9px;Ð display: inline-block;Ð border-right: 7px solid transparent;Ð border-bottom: 7px solid #ccc;Ð border-left: 7px solid transparent;Ð border-bottom-color: rgba(0, 0, 0, 0.2);Ð content: '';ÐÐdaterangepicker.opensleft:after {Ð position: absolute;Ð top: -6px;Ð right: 10px;Ð display: inline-block;Ð border-right: 6px solid transparent;Ð border-bottom: 6px solid #fff;Ð border-left: 6px solid transparent;Ð content: '';ÐÐdaterangepicker.openscenter:before {Ð position: absolute;Ð top: -7px;Ð left: 0; Ð right: 0;Ð width: 0;Ð margin-left: auto;Ð margin-right: auto;Ð display: inline-block;Ð border-right: 7px solid transparent;Ð border-bottom: 7px solid #ccc;Ð border-left: 7px solid transparent;Ð border-bottom-color: rgba(0, 0, 0, 0.2);Ð content: '';ÐÐ
.daterangepicker.openscenter:after {Ð position: absolute;Ð top: -6px;Ð left: 0; Ð right: 0; Ð width: 0;Ð margin-left: auto;Ð margin-right: auto;Ð display: inline-block;Ð border-right: 6px solid transparent;Ð border-bottom: 6px solid #fff;Ð border-left: 6px solid transparent;Ð content: '';ÐÐ
.daterangepicker.opensright:before {Ð position: absolute;Ð top: -7px;Ð left: 9px;Ð display: inline-block;Ð border-right: 7px solid transparent;Ð border-bottom: 7px solid #ccc;Ð border-left: 7px solid transparent;Ð border-bottom-color: rgba(0, 0, 0, 0.2);Ð

content: '';ÐÐdaterangepicker.opensright:after {Ð position: absolute;Ð top: -6px;Ð left: 10px;Ð display: inline-block;Ð border-right: 6px solid transparent;Ð border-bottom: 6px solid #fff;Ð border-left: 6px solid transparent;Ð content: '';ÐÐdaterangepicker.dropup{Ð margin-top: -5px;ÐÐdaterangepicker.dropup:before{Ð top: initial;Ð bottom:-7px;Ð border-bottom: initial;Ð border-top: 7px solid #ccc;ÐÐdaterangepicker.dropup:after{Ð top: initial;Ð bottom:-6px;Ð border-bottom: initial;Ð border-top: 6px solid #fff;ÐÐdaterangepicker table {Ð width: 100%;Ð margin: 0;ÐÐdaterangepicker td, .daterangepicker th {Ð text-align: center;Ð width: 20px;Ð height: 20px;Ð -webkit-border-radius: 4px;Ð -moz-border-radius: 4px;Ð border-radius: 4px;Ð cursor: pointer;Ð white-space: nowrap;ÐÐdaterangepicker td.off {Ð color: #999;Ð }Ðdaterangepicker td.disabled, .daterangepicker option.disabled {Ð color: #999;ÐÐdaterangepicker td.available:hover, .daterangepicker th.available:hover {Ð background: #eee;ÐÐdaterangepicker td.in-range {Ð background: #ebf4f8;Ð -webkit-border-radius: 0;Ð -moz-border-radius: 0;Ð border-radius: 0;ÐÐdaterangepicker td.start-date {Ð -webkit-border-radius: 4px 0 0 4px;Ð -moz-border-radius: 4px 0 0 4px;Ð border-radius: 4px 0 0 4px;ÐÐ .daterangepicker td.end-date {Ð -webkit-border-radius: 0 4px 4px 0;Ð -moz-border-radius: 0 4px 4px 0;Ð border-radius: 0 4px 4px 0;ÐÐdaterangepicker td.start-date.end-date {Ð -webkit-border-radius: 4px;Ð -moz-border-radius: 4px;Ð border-radius: 4px;ÐÐdaterangepicker td.active, .daterangepicker td.active:hover {Ð background-color: #357ebd;Ð border-color: #3071a9;Ð color: #fff;ÐÐdaterangepicker td.week, .daterangepicker th.week {Ð font-size: 80%;Ð color: #ccc;ÐÐdaterangepicker select.monthselect, .daterangepicker select.yearselect {Ð font-size: 12px;Ð padding: 1px;Ð height: auto;Ð margin: 0;Ð cursor: default;ÐÐdaterangepicker select.monthselect {Ð margin-right: 2%;Ð width: 56%;ÐÐdaterangepicker select.yearselect {Ð width: 40%;ÐÐ .daterangepicker select.hourselect, .daterangepicker select.minuteselect, .daterangepicker select.secondselect, .daterangepicker select.ampmselect {Ð width: 50px;Ð margin-bottom: 0;ÐÐ .daterangepicker_start_input {Ð float: left;ÐÐdaterangepicker_end_input {Ð float: left; Ð padding-left: 11pxÐÐdaterangepicker th.month {Ð width: auto;ÐÐ

public\assets\css\plugins\dropzone\basic.css

/* The MIT License */Ðdropzone,Ðdropzone *,Ðdropzone-previews,Ðdropzone-previews * {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÞÐdropzone {Ð position: relative;Ð border: 1px solid rgba(0,0,0,0.08);Ð background: rgba(0,0,0,0.02);Ð padding: 1em;ÞÐdropzone.dz-clickable {Ð cursor: pointer;ÞÐdropzone.dz-clickable .dz-message,Ðdropzone.dz-clickable .dz-message span {Ð cursor: pointer;ÞÐdropzone.dz-clickable * {Ð cursor: default;ÞÐdropzone .dz-message {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;ÞÐdropzone.dz-drag-hover {Ð border-color: rgba(0,0,0,0.15);Ð background: rgba(0,0,0,0.04);ÞÐdropzone.dz-started .dz-message {Ð display: none;ÞÐdropzone .dz-preview,Ðdropzone-previews .dz-preview {Ð background: rgba(255,255,255,0.8);Ð position: relative;Ð display: inline-block;Ð margin: 17px;Ð vertical-align: top;Ð border: 1px solid #acacac;Ð padding: 6px 6px 6px 6px;ÞÐdropzone .dz-preview.dz-file-preview [data-dz-thumbnail],Ðdropzone-previews .dz-preview.dz-file-preview [data-dz-thumbnail] {Ð display: none;ÞÐ .dropzone .dz-preview .dz-details,Ðdropzone-previews .dz-preview .dz-details {Ð width: 100px;Ð height: 100px;Ð position: relative;Ð background: #ebebeb;Ð padding: 5px;Ð margin-bottom: 22px;ÞÐdropzone .dz-preview .dz-details .dz-filename,Ðdropzone-previews .dz-preview .dz-details .dz-filename {Ð overflow: hidden;Ð height: 100%;ÞÐdropzone .dz-preview .dz-details img,Ðdropzone-previews .dz-preview .dz-details img {Ð position: absolute;Ð top: 0;Ð left: 0;Ð width: 100px;Ð height: 100px;ÞÐdropzone .dz-preview .dz-details .dz-size,Ð .dropzone-previews .dz-preview .dz-details .dz-size {Ð position: absolute;Ð bottom: -28px;Ð left: 3px;Ð height: 28px;Ð line-height: 28px;ÞÐdropzone .dz-preview.dz-error .dz-error-mark,Ðdropzone-previews .dz-preview.dz-error .dz-error-mark {Ð display: block;ÞÐdropzone .dz-preview.dz-success .dz-success-mark,Ðdropzone-previews .dz-preview.dz-success .dz-success-mark {Ð display: block;ÞÐdropzone .dz-preview:hover .dz-details img,Ðdropzone-previews .dz-preview:hover .dz-details img {Ð display: none;ÞÐdropzone .dz-preview .dz-success-mark,Ðdropzone-previews .dz-preview .dz-success-mark,Ðdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark {Ð display: none;Ð position: absolute;Ð width: 40px;Ð height: 40px;Ð font-size: 30px;Ð text-align: center;Ð right: -10px;Ð top: -10px;ÞÐdropzone .dz-preview .dz-success-mark,Ðdropzone-previews .dz-preview .dz-success-mark {Ð color: #8cc657;ÞÐdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark {Ð color: #ee162d;ÞÐdropzone .dz-preview .dz-progress,Ð .dropzone-previews .dz-preview .dz-progress {Ð position: absolute;Ð top: 100px;Ð left: 6px;Ð right: 6px;Ð height: 6px;Ð background: #d7d7d7;Ð display: none;ÞÐdropzone .dz-preview .dz-progress .dz-upload,Ðdropzone-previews .dz-preview .dz-progress .dz-upload {Ð display: block;Ð position: absolute;Ð top: 0;Ð bottom: 0;Ð left: 0;Ð width: 0%;Ð background-color: #8cc657;ÞÐ .dropzone .dz-preview.dz-processing .dz-progress,Ðdropzone-previews .dz-preview.dz-processing .dz-progress {Ð display: block;ÞÐdropzone .dz-preview .dz-error-message,Ðdropzone-previews .dz-preview .dz-error-message {Ð display: none;Ð position: absolute;Ð top: -5px;Ð left: -20px;Ð background: rgba(245,245,245,0.8);Ð padding: 8px 10px;Ð color: #800;Ð min-width: 140px;Ð max-width: 500px;Ð z-index: 500;ÞÐdropzone .dz-preview:hover.dz-error .dz-error-message,Ðdropzone-previews .dz-preview:hover.dz-error .dz-error-message {Ð display: block;ÞÐ

public\assets\css\plugins\dropzone\dropzone.css

/* The MIT License */Ðdropzone,Ðdropzone *,Ðdropzone-previews,Ðdropzone-previews * {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÞÐdropzone {Ð position: relative;Ð border: 1px solid rgba(0,0,0,0.08);Ð background: rgba(0,0,0,0.02);Ð padding: 1em;ÞÐdropzone.dz-clickable {Ð cursor: pointer;ÞÐdropzone.dz-clickable .dz-message,Ðdropzone.dz-clickable .dz-message span {Ð cursor: pointer;ÞÐdropzone.dz-clickable * {Ð cursor: default;ÞÐdropzone .dz-message {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;ÞÐdropzone.dz-drag-hover {Ð border-color: rgba(0,0,0,0.15);Ð background: rgba(0,0,0,0.04);ÞÐdropzone.dz-started .dz-message {Ð display: none;ÞÐdropzone .dz-preview,Ðdropzone-previews .dz-preview {Ð background: rgba(255,255,255,0.8);Ð position: relative;Ð display: inline-block;Ð margin: 17px;Ð vertical-align: top;Ð border: 1px solid #acacac;Ð padding: 6px 6px 6px 6px;ÞÐdropzone .dz-preview.dz-file-preview [data-dz-thumbnail],Ðdropzone-previews .dz-preview.dz-file-preview [data-dz-thumbnail] {Ð display: none;ÞÐ .dropzone .dz-preview .dz-details,Ðdropzone-previews .dz-preview .dz-details {Ð width: 100px;Ð height: 100px;Ð position: relative;Ð background: #ebebeb;Ð padding: 5px;Ð margin-bottom: 22px;ÞÐdropzone .dz-preview .dz-details .dz-filename,Ðdropzone-previews .dz-preview .dz-details .dz-filename {Ð overflow: hidden;Ð height: 100%;ÞÐdropzone .dz-preview .dz-details img,Ðdropzone-previews .dz-preview .dz-details img {Ð position: absolute;Ð top: 0;Ð left: 0;Ð width: 100px;Ð height: 100px;ÞÐdropzone .dz-preview .dz-details .dz-size,Ð .dropzone-previews .dz-preview .dz-details .dz-size {Ð position: absolute;Ð bottom: -28px;Ð left: 3px;Ð height: 28px;Ð line-height: 28px;ÞÐdropzone .dz-preview.dz-error .dz-error-mark,Ðdropzone-previews .dz-preview.dz-error .dz-error-mark {Ð display: block;ÞÐdropzone .dz-preview.dz-success .dz-success-mark,Ðdropzone-previews .dz-preview.dz-success .dz-success-mark {Ð display: block;ÞÐdropzone .dz-preview:hover .dz-details img,Ðdropzone-previews .dz-preview:hover .dz-details img {Ð display: none;ÞÐdropzone .dz-preview .dz-success-mark,Ðdropzone-previews .dz-preview .dz-success-mark,Ðdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark {Ð display: none;Ð position: absolute;Ð width: 40px;Ð height: 40px;Ð font-size: 30px;Ð text-align: center;Ð right: -10px;Ð top: -10px;ÞÐdropzone .dz-preview .dz-success-mark,Ðdropzone-previews .dz-preview .dz-success-mark {Ð color: #8cc657;ÞÐdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark {Ð color: #ee162d;ÞÐdropzone .dz-preview .dz-progress,Ð .dropzone-previews .dz-preview .dz-progress {Ð position: absolute;Ð top: 100px;Ð left: 6px;Ð right: 6px;Ð height: 6px;Ð background: #d7d7d7;Ð display: none;ÞÐdropzone .dz-preview .dz-progress .dz-upload,Ðdropzone-previews .dz-preview .dz-progress .dz-upload {Ð display: block;Ð position: absolute;Ð top: 0;Ð bottom: 0;Ð left: 0;Ð width: 0%;Ð background-color: #8cc657;ÞÐ .dropzone .dz-preview.dz-processing .dz-progress,Ðdropzone-previews .dz-preview.dz-processing .dz-progress {Ð display: block;ÞÐdropzone .dz-preview .dz-error-message,Ðdropzone-previews .dz-preview .dz-error-message {Ð display: none;Ð position: absolute;Ð top: -5px;Ð left: -20px;Ð background: rgba(245,245,245,0.8);Ð padding: 8px 10px;Ð color: #800;Ð min-width: 140px;Ð max-width: 500px;Ð z-index: 500;ÞÐdropzone .dz-preview:hover.dz-error .dz-error-message,Ðdropzone-previews .dz-preview:hover.dz-error .dz-error-message {Ð display: block;ÞÐdropzone {Ð border: 1px solid rgba(0,0,0,0.03);Ð min-height: 360px;Ð -webkit-border-radius: 3px;Ð border-radius: 3px;Ð background: rgba(0,0,0,0.03);Ð padding: 23px;ÞÐdropzone .dz-default.dz-message {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;Ð -webkit-transition: opacity 0.3s ease-in-out;Ð -moz-transition: opacity 0.3s ease-in-out;Ð -o-transition: opacity 0.3s ease-in-out;Ð -ms-transition: opacity 0.3s ease-in-out;Ð transition: opacity 0.3s ease-in-out;Ð background-image: url("../images/spritemap.png");Ð background-repeat: no-repeat;Ð background-position: 0 0;Ð position: absolute;Ð width: 428px;Ð height: 123px;Ð margin-left: -214px;Ð margin-top: -61.5px;Ð top: 50%;Ð left: 50%;ÞÐmedia all and (-webkit-min-device-pixel-ratio:1.5),(min--moz-device-pixel-ratio:1.5),(-o-min-device-pixel-ratio:1.5/1),(min-device-pixel-ratio:1.5),(min-resolution:138dpi),(min-

resolution:1.5dppx) {Ð .dropzone .dz-default.dz-message {Ð background-image: url("../images/spritemap@2x.png");Ð -webkit-background-size: 428px 406px;Ð -moz-background-size: 428px 406px;Ð background-size: 428px 406px;Ð }ÞÐdropzone .dz-default.dz-message span {Ð display: none;ÞÐdropzone.dz-square .dz-default.dz-message {Ð background-position: 0 -123px;Ð width: 268px;Ð margin-left: -134px;Ð height: 174px;Ð margin-top: -87px;ÞÐdropzone.dz-drag-hover .dz-message {Ð opacity: 0.15;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=15)";Ð filter: alpha(opacity=15);ÞÐdropzone.dz-started .dz-message {Ð display: block;Ð opacity: 0;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=0)";Ð filter: alpha(opacity=0);ÞÐdropzone .dz-preview,Ðdropzone-previews .dz-preview {Ð -webkit-box-shadow: 1px 1px 4px rgba(0,0,0,0.16);Ð box-shadow: 1px 1px 4px rgba(0,0,0,0.16);Ð font-size: 14px;ÞÐdropzone .dz-preview.dz-image-preview:hover .dz-details img,Ðdropzone-previews .dz-preview.dz-image-preview:hover .dz-details img {Ð display: block;Ð opacity: 0.1;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=10)";Ð filter: alpha(opacity=10);ÞÐdropzone .dz-preview.dz-success .dz-success-mark,Ð .dropzone-previews .dz-preview.dz-success .dz-success-mark {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;ÞÐdropzone .dz-preview.dz-error .dz-error-mark,Ð .dropzone-previews .dz-preview.dz-error .dz-error-mark {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;ÞÐdropzone .dz-preview.dz-error .dz-progress .dz-upload,Ðdropzone-previews .dz-preview.dz-error .dz-progress .dz-upload {Ð background: #ee1e2d;ÞÐdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark,Ðdropzone .dz-preview .dz-success-mark,Ð .dropzone-previews .dz-preview .dz-success-mark {Ð display: block;Ð opacity: 0;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=0)";Ð filter: alpha(opacity=0);Ð -webkit-transition: opacity 0.4s ease-in-out;Ð -moz-transition: opacity 0.4s ease-in-out;Ð -o-transition: opacity 0.4s ease-in-out;Ð -ms-transition: opacity 0.4s ease-in-out;Ð transition: opacity 0.4s ease-in-out;Ð background-image: url("../images/spritemap.png");Ð background-repeat: no-repeat;Þ@media all and (-webkit-min-device-pixel-ratio:1.5),(min--moz-device-pixel-ratio:1.5),(-o-min-device-pixel-ratio:1.5/1),(min-device-pixel-ratio:1.5),(min-resolution:138dpi),(min-resolution:1.5dppx) {Ð .dropzone .dz-preview .dz-error-mark,Ð .dropzone-previews .dz-preview .dz-error-mark,Ð .dropzone .dz-preview .dz-success-mark,Ð .dropzone-previews .dz-preview .dz-success-mark {Ð background-image: url("../images/spritemap@2x.png");Ð -webkit-background-size: 428px 406px;Ð -moz-background-size: 428px 406px;Ð background-size: 428px 406px;Ð }ÞÐ .dropzone .dz-preview .dz-error-mark span,Ðdropzone-previews .dz-preview .dz-error-mark span,Ðdropzone .dz-preview .dz-success-mark span,Ðdropzone-previews .dz-preview .dz-success-mark span {Ð display: none;ÞÐdropzone .dz-preview .dz-error-mark,Ðdropzone-previews .dz-preview .dz-error-mark {Ð background-position: -268px -123px;ÞÐdropzone .dz-preview .dz-success-mark,Ð .dropzone-previews .dz-preview .dz-success-mark {Ð background-position: -268px -163px;ÞÐdropzone .dz-preview .dz-progress .dz-upload,Ðdropzone-previews .dz-preview .dz-progress .dz-upload {Ð -webkit-animation: loading 0.4s linear infinite;Ð -moz-animation: loading 0.4s linear infinite;Ð -o-animation: loading 0.4s linear infinite;Ð -ms-animation: loading 0.4s linear infinite;Ð animation: loading 0.4s linear infinite;Ð -webkit-transition: width 0.3s ease-in-out;Ð -moz-transition: width 0.3s ease-in-out;Ð -o-transition: width 0.3s ease-in-out;Ð -ms-transition: width 0.3s ease-in-out;Ð transition: width 0.3s ease-in-out;Ð -webkit-border-radius: 2px;Ð border-radius: 2px;Ð position: absolute;Ð top: 0;Ð left: 0;Ð width: 0%;Ð height: 100%;Ð background-image: url("../images/spritemap.png");Ð background-repeat: repeat-x;Ð background-position: 0px -400px;Þ@media all and (-webkit-min-device-pixel-ratio:1.5),(min--moz-device-pixel-ratio:1.5),(-o-min-device-pixel-ratio:1.5/1),(min-device-pixel-ratio:1.5),(min-resolution:138dpi),(min-resolution:1.5dppx) {Ð .dropzone .dz-preview .dz-progress .dz-upload,Ð .dropzone-previews .dz-preview .dz-progress .dz-upload {Ð background-image: url("../images/spritemap@2x.png");Ð

-webkit-background-size: 428px 406px;Ð -moz-background-size: 428px 406px;Ð background-size: 428px 406px;Ð }ÐÐdropzone .dz-preview.dz-success .dz-progress,Ðdropzone-previews .dz-preview.dz-success .dz-progress {Ð display: block;Ð opacity: 0;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=0)";Ð filter: alpha(opacity=0);Ð -webkit-transition: opacity 0.4s ease-in-out;Ð -moz-transition: opacity 0.4s ease-in-out;Ð -o-transition: opacity 0.4s ease-in-out;Ð -ms-transition: opacity 0.4s ease-in-out;Ð transition: opacity 0.4s ease-in-out;ÐÐdropzone .dz-preview .dz-error-message,Ðdropzone-previews .dz-preview .dz-error-message {Ð display: block;Ð opacity: 0;Ð -ms-filter: "progid:DXImageTransform.Microsoft.Alpha(Opacity=0)";Ð filter: alpha(opacity=0);Ð -webkit-transition: opacity 0.3s ease-in-out;Ð -moz-transition: opacity 0.3s ease-in-out;Ð -o-transition: opacity 0.3s ease-in-out;Ð -ms-transition: opacity 0.3s ease-in-out;Ð transition: opacity 0.3s ease-in-out;ÐÐdropzone .dz-preview:hover.dz-error .dz-error-message,Ðdropzone-previews .dz-preview:hover.dz-error .dz-error-message {Ð opacity: 1;Ð -ms-filter: none;Ð filter: none;ÐÐdropzone a.dz-remove,Ðdropzone-previews a.dz-remove {Ð background-image: -webkit-linear-gradient(top, #fafafa, #eee);Ð background-image: -moz-linear-gradient(top, #fafafa, #eee);Ð background-image: -o-linear-gradient(top, #fafafa, #eee);Ð background-image: -ms-linear-gradient(top, #fafafa, #eee);Ð background-image: linear-gradient(to bottom, #fafafa, #eee);Ð -webkit-border-radius: 2px;Ð border-radius: 2px;Ð border: 1px solid #eee;Ð text-decoration: none;Ð display: block;Ð padding: 4px 5px;Ð text-align: center;Ð color: #aaa;Ð margin-top: 26px;ÐÐdropzone a.dz-remove:hover,Ðdropzone-previews a.dz-remove:hover {Ð color: #666;ÐÐ@-moz-keyframes loading {Ð 0% {Ð background-position: 0 -400px;Ð }Ð 100% {Ð background-position: -7px -400px;Ð }ÐÐ@-webkit-keyframes loading {Ð 0% {Ð background-position: 0 -400px;Ð }Ð 100% {Ð background-position: -7px -400px;Ð }ÐÐ@-o-keyframes loading {Ð 0% {Ð background-position: 0 -400px;Ð }Ð 100% {Ð background-position: -7px -400px;Ð }ÐÐ@-ms-keyframes loading {Ð 0% {Ð background-position: 0 -400px;Ð }Ð 100% {Ð background-position: -7px -400px;Ð }ÐÐ@keyframes loading {Ð 0% {Ð background-position: 0 -400px;Ð }Ð 100% {Ð background-position: -7px -400px;Ð }ÐÐ

public\assets\css\plugins\footable\footable.core.css

@font-face {Ð font-family: 'footable';Ð src: url('fonts/footable.eot');Ð src: url('fonts/footable.eot?#iefix') format('embedded-opentype'), url('fonts/footable.woff') format('woff'), url('fonts/footable.ttf') format('truetype'), url('fonts/footable.svg#footable') format('svg');Ð font-weight: normal;Ð font-style: normal;ÐÐ@media screen and (-webkit-min-device-pixel-ratio: 0) {Ð @font-face {Ð font-family: 'footable';Ð src: url('fonts/footable.svg#footable') format('svg');Ð font-weight: normal;Ð font-style: normal;Ð }ÐÐfootable {Ð width: 100%;Ð /** SORTING **/Ð /** PAGINATION **/ÐÐfootable.breakpoint > tbody > tr.footable-detail-show > td {Ð border-bottom: none;ÐÐ .footable.breakpoint > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e001";ÐÐfootable.breakpoint > tbody > tr:hover:not(.footable-row-detail) {Ð cursor: pointer;ÐÐfootable.breakpoint > tbody > tr > td.footable-cell-detail {Ð background: #eee;Ð border-top: none;ÐÐ .footable.breakpoint > tbody > tr > td > span.footable-toggle {Ð display: inline-block;Ð font-family: 'footable';Ð speak: none;Ð font-style: normal;Ð font-weight: normal;Ð font-variant: normal;Ð text-transform: none;Ð -webkit-font-smoothing: antialiased;Ð padding-right: 5px;Ð font-size: 14px;Ð color: #888888;ÐÐfootable.breakpoint > tbody > tr > td > span.footable-toggle:before {Ð content: "\e000";ÐÐfootable.breakpoint.toggle-circle > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e005";ÐÐ .footable.breakpoint.toggle-circle > tbody > tr > td > span.footable-toggle:before {Ð content: "\e004";ÐÐfootable.breakpoint.toggle-circle-filled > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e003";ÐÐfootable.breakpoint.toggle-circle-filled > tbody > tr > td > span.footable-toggle:before {Ð content: "\e002";ÐÐ .footable.breakpoint.toggle-square > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e007";ÐÐfootable.breakpoint.toggle-square > tbody > tr > td > span.footable-toggle:before {Ð content: "\e006";ÐÐ .footable.breakpoint.toggle-square-filled > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e009";ÐÐ .footable.breakpoint.toggle-square-filled > tbody > tr > td > span.footable-toggle:before {Ð content: "\e008";ÐÐfootable.breakpoint.toggle-arrow > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e00f";ÐÐfootable.breakpoint.toggle-arrow > tbody > tr > td > span.footable-toggle:before {Ð content: "\e011";ÐÐfootable.breakpoint.toggle-arrow-small > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e013";ÐÐfootable.breakpoint.toggle-arrow-small > tbody > tr > td > span.footable-toggle:before {Ð content: "\e015";ÐÐfootable.breakpoint.toggle-arrow-circle > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e01b";ÐÐfootable.breakpoint.toggle-arrow-circle > tbody > tr > td > span.footable-toggle:before {Ð content: "\e01d";ÐÐ .footable.breakpoint.toggle-arrow-circle-filled > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e00b";ÐÐ .footable.breakpoint.toggle-arrow-circle-filled > tbody > tr > td > span.footable-toggle:before {Ð content: "\e00d";ÐÐfootable.breakpoint.toggle-arrow-tiny > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e01f";ÐÐfootable.breakpoint.toggle-arrow-tiny > tbody > tr > td > span.footable-toggle:before {Ð content: "\e021";ÐÐ .footable.breakpoint.toggle-arrow-alt > tbody > tr.footable-detail-show > td > span.footable-toggle:before {Ð content: "\e017";ÐÐ .footable.breakpoint.toggle-arrow-alt > tbody > tr > td > span.footable-toggle:before {Ð content: "\e019";ÐÐfootable.breakpoint.toggle-medium > tbody > tr > td > span.footable-toggle {Ð font-size: 18px;ÐÐ .footable.breakpoint.toggle-large > tbody > tr > td > span.footable-toggle {Ð font-size: 24px;ÐÐfootable > thead > tr > th {Ð -webkit-touch-callout: none;Ð -webkit-user-select: none;Ð -khtml-user-select: none;Ð -moz-user-select: -moz-none;Ð -ms-user-select: none;Ð user-select: none;ÐÐfootable > thead > tr > th.footable-sortable:hover {Ð cursor: pointer;ÐÐfootable > thead > tr > th.footable-sorted > span.footable-sort-indicator:before {Ð

content: "\e013";ÞÐ
.footable > thead > tr > th.footable-sorted-desc > span.footable-sort-indicator:before {Ð content: "\e012";ÞÐfootable > thead > tr > th > span.footable-sort-indicator {Ð display: inline-block;Ð font-family: 'footable';Ð speak: none;Ð font-style: normal;Ð font-weight: normal;Ð font-variant: normal;Ð text-transform: none;Ð -webkit-font-smoothing: antialiased;Ð padding-left: 5px;ÞÐfootable > thead > tr > th > span.footable-sort-indicator:before {Ð content: "\e022";ÞÐfootable > tfoot .pagination {Ð margin: 0;ÞÐfootable.no-paging .hide-if-no-paging {Ð display: none;ÞÐfootable-row-detail-inner {Ð display: table;ÞÐfootable-row-detail-row {Ð display: table-row;Ð line-height: 1.5em;ÞÐfootable-row-detail-group {Ð display: block;Ð line-height: 2em;Ð font-size: 1.2em;Ð font-weight: bold;ÞÐfootable-row-detail-name {Ð display: table-cell;Ð font-weight: bold;Ð padding-right: 0.5em;Ð }ÐfootableÐrow-detail-value {Ð display: table-cell;ÞÐfootable-odd {Ð background-color: #f7f7f7;ÞÐ

public\assets\css\plugins\fullcalendar\fullcalendar.css

/*!Ð* FullCalendar v2.2.0 StylesheetÐ* Docs & License: http://arshaw.com/fullcalendar/Ð* (c) 2013 Adam ShawÐ*/Ðfc {Ð direction: ltr;Ð text-align: left;ÞÐfc-rtl {Ð text-align: right;ÞÐbody .fc { /* extra precedence to overcome jqui */Ð font-size: 1em;ÞÐ* ColorsÐ

/Ðfc-unthemed th,Ðfc-unthemed td,Ðfc-unthemed hr,Ðfc-unthemed thead,Ðfc-unthemed tbody,Ðfc-unthemed .fc-row,Ðfc-unthemed .fc-popover {Ð border-color: #ddd;ÞÐfc-unthemed .fc-popover {Ð background-color: #fff;ÞÐfc-unthemed hr,Ðfc-unthemed .fc-popover .fc-header {Ð background: #eee;ÞÐfc-unthemed .fc-popover .fc-header .fc-close {Ð color: #666;ÞÐfc-unthemed .fc-today {Ð background: #fcf8e3;ÞÐfc-highlight { / when user is selecting cells */Ð background: #bce8f1;Ð opacity: .3;Ð filter: alpha(opacity=30); /* for IE */ÞÐfc-bgevent { /* default look for background events */Ð background: rgb(143, 223, 130);Ð opacity: .3;Ð filter: alpha(opacity=30); /* for IE */ÞÐfc-nonbusiness { /* default look for non-business-hours areas */Ð /* will inherit .fc-bgevent's styles */Ð background: #ccc;ÞÐ* Icons (inline elements with styled text that mock arrow icons)Ð----------
----------*/Ðfc-icon {Ð display: inline-block;Ð font-size: 2em;Ð line-height: .5em;Ð height: .5em; /* will make the total height 1em */Ð font-family: "Courier New", Courier, monospace;ÞÐfc-icon-left-single-arrow:after {Ð content: "\02039";Ð font-weight: bold;ÞÐfc-icon-right-single-arrow:after {Ð content: "\0203A";Ð font-weight: bold;ÞÐ.fc-icon-left-double-arrow:after {Ð content: "\000AB";ÞÐfc-icon-right-double-arrow:after {Ð content: "\000BB";ÞÐfc-icon-x:after {Ð content: "\000D7";ÞÐ* Buttons (styled <button> tags, normalized to work cross-browser)Ð

/Ðfc button {Ð / force height to include the border and padding */Ð -moz-box-sizing: border-box;Ð -webkit-box-sizing: border-box;Ð box-sizing: border-box;Ð /* dimensions */Ð margin: 0;Ð height: 2.1em;Ð padding: 0 .6em;Ð /* text & cursor */Ð font-size: 1em; /* normalize */Ð white-space: nowrap;Ð cursor: pointer;ÞÐ* Firefox has an annoying inner border */Ð.fc button::-moz-focus-inner { margin: 0; padding: 0; }Ðfc-state-default { /* non-theme */Ð border: 1px solid;ÞÐfc-state-default.fc-corner-left { /* non-theme */Ð border-top-left-radius: 4px;Ð border-bottom-left-radius: 4px;ÞÐ.fc-state-default.fc-corner-right { /* non-theme */Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 4px;ÞÐ* icons in buttons */Ðfc button .fc-icon { /* non-theme */Ð position: relative;Ð top: .05em; /* seems to be a good adjustment across browsers */Ð margin: 0 .1em;ÞÐ*Ð button statesÐ borrowed from twitter bootstrap (http://twitter.github.com/bootstrap/)Ð/Ðfc-state-default {Ð background-color: #f5f5f5;Ð background-image: -moz-linear-gradient(top, #ffffff, #e6e6e6);Ð background-image: -webkit-gradient(linear, 0 0, 0 100%, from(#ffffff), to(#e6e6e6));Ð background-image: -webkit-linear-gradient(top, #ffffff, #e6e6e6);Ð background-image: -o-linear-gradient(top, #ffffff, #e6e6e6);Ð background-image: linear-gradient(to bottom, #ffffff, #e6e6e6);Ð background-repeat: repeat-x;Ð border-color: #e6e6e6 #e6e6e6 #bfbfbf;Ð border-color: rgba(0, 0, 0, 0.1) rgba(0, 0, 0, 0.1) rgba(0, 0, 0, 0.25);Ð color: #333;Ð text-shadow: 0 1px 1px rgba(255, 255, 255, 0.75);Ð box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.2), 0 1px 2px rgba(0, 0, 0, 0.05);ÞÐfc-state-hover,Ðfc-state-down,Ðfc-state-active,Ðfc-state-disabled {Ð color: #333333;Ð background-color: #e6e6e6;ÞÐfc-state-hover {Ð color: #333333;Ð text-decoration: none;Ð background-position: 0 -15px;Ð -webkit-transition: background-position 0.1s linear;Ð -moz-transition: background-position 0.1s linear;Ð -o-transition: background-position 0.1s linear;Ð transition: background-position 0.1s linear;ÞÐfc-state-down,Ðfc-state-active {Ð background-color: #cccccc;Ð background-image: none;Ð box-shadow: inset 0 2px 4px rgba(0, 0, 0, 0.15), 0 1px 2px rgba(0, 0, 0, 0.05);ÞÐfc-state-disabled {Ð

```
              cursor: default;Ð   background-image: none;Ð   opacity: 0.65;Ð
    filter: alpha(opacity=65);Ð   box-shadow: none;ÞÞ* Buttons GroupsÐ
-------------------------------------------------------------------------------------------
*/Ðfc-button-group {Ð   display: inline-block;ÞÞ*Ðevery button that is not
first in a button group should scootch over one pixel and cover theÐprevious
button's border...Ð/Ðfc .fc-button-group > * { /* extra precedence b/c
buttons have margin set to zero */Ð   float: left;Ð   margin: 0 0 0 -1px;ÞÐ
.fc .fc-button-group > :first-child { /* same */Ð   margin-left: 0;ÞÞ* PopoverÐ
-------------------------------------------------------------------------------------------
*/Ðfc-popover {Ð   position: absolute;Ð   box-shadow: 0 2px 6px
rgba(0,0,0,.15);ÞÐfc-popover .fc-header {Ð   padding: 2px 4px;ÞÐfc-
popover .fc-header .fc-title {Ð   margin: 0 2px;ÞÐfc-popover .fc-header .fc-
close {Ð   cursor: pointer;ÞÐfc-ltr .fc-popover .fc-header .fc-title,Ðfc-
rtl .fc-popover .fc-header .fc-close {Ð   float: left;ÞÐfc-rtl .fc-
popover .fc-header .fc-title,Ðfc-ltr .fc-popover .fc-header .fc-close {Ð
float: right;ÞÞ* unthemed */Ðfc-unthemed .fc-popover {Ð   border-width: 1px;Ð
    border-style: solid;ÞÐfc-unthemed .fc-popover .fc-header .fc-close {Ð
font-size: 25px;Ð   margin-top: 4px;ÞÞ* jqui themed */Ðfc-popover > .ui-
widget-header + .ui-widget-content {Ð   border-top: 0; /* where they meet,
let the header have the border */ÞÞ* Misc Reusable ComponentsÐ
-------------------------------------------------------------------------------------------
*/Ðfc hr {Ð   height: 0;Ð   margin: 0;Ð   padding: 0 0 2px; /* height is
unreliable across browsers, so use padding */Ð   border-style: solid;Ð
border-width: 1px 0;ÞÐfc-clear {Ð   clear: both;ÞÐfc-bg,Ðfc-bgevent-skeleton,Ð
.fc-highlight-skeleton,Ðfc-helper-skeleton {Ð   /* these element should
always cling to top-left/right corners */Ð   position: absolute;Ð   top: 0;Ð
    left: 0;Ð   right: 0;ÞÐfc-bg {Ð   bottom: 0; /* strech bg to bottom edge
*/ÞÐfc-bg table {Ð   height: 100%; /* strech bg to bottom edge */ÞÞ* TablesÐ
-------------------------------------------------------------------------------------------
*/Ðfc table {Ð   width: 100%;Ð   table-layout: fixed;Ð   border-collapse:
collapse;Ð   border-spacing: 0;Ð   font-size: 1em; /* normalize cross-browser
*/ÞÐfc th {Ð   text-align: center;ÞÐfc th,Ðfc td {Ð   border-style: solid;Ð
border-width: 1px;Ð   padding: 0;Ð   vertical-align: top;ÞÐfc td.fc-today {Ð
    border-style: double; /* overcome neighboring borders */ÞÞ* Fake Table
RowsÐ-------------------------------------------------------------------------
------------------------*/Ðfc .fc-row { /* extra precedence to overcome
themes w/ .ui-widget-content forcing a 1px border */Ð   /* no visible border
by default. but make available if need be (scrollbar width compensation) */Ð
    border-style: solid;Ð   border-width: 0;ÞÐfc-row table {Ð   /* don't put
left/right border on anything within a fake row.Ð      the outer tbody will
worry about this */Ð   border-left: 0 hidden transparent;Ð   border-right: 0
hidden transparent;Ð   /* no bottom borders on rows */Ð   border-bottom: 0
hidden transparent;ÞÐfc-row:first-child table {Ð   border-top: 0 hidden
transparent; /* no top border on first row */ÞÞ* Day Row (used within the
header and the DayGrid)Ð
-------------------------------------------------------------------------------------------
*/Ðfc-row {Ð   position: relative;ÞÐfc-row .fc-bg {Ð   z-index: 1;ÞÞ*
highlighting cells & background event skeleton */Ðfc-row .fc-bgevent-skeleton,Ð
.fc-row .fc-highlight-skeleton {Ð   bottom: 0; /* stretch skeleton to bottom
of row */ÞÐfc-row .fc-bgevent-skeleton table,Ðfc-row .fc-highlight-skeleton
table {Ð   height: 100%; /* stretch skeleton to bottom of row */ÞÐfc-row .fc-
highlight-skeleton td,Ðfc-row .fc-bgevent-skeleton td {Ð   border-color:
transparent;ÞÐfc-row .fc-bgevent-skeleton {Ð   z-index: 2;ÞÐfc-row .fc-
highlight-skeleton {Ð   z-index: 3;ÞÞ*Ðow content (which contains day/week
numbers and events) as well as "helper" (which containsÐemporary rendered
events).*/Ðfc-row .fc-content-skeleton {Ð   position: relative;Ð   z-index: 4;Ð
    padding-bottom: 2px; /* matches the space above the events */ÞÐfc-row .fc-
helper-skeleton {Ð   z-index: 5;ÞÐfc-row .fc-content-skeleton td,Ðfc-row .fc-
helper-skeleton td {Ð   /* see-through to the background below */Ð
background: none; /* in case <td>s are globally styled */Ð
```

```
                                                            border-color:
transparent;Ð   /* don't put a border between events and/or the day number */Ð
    border-bottom: 0;ÞÞfc-row .fc-content-skeleton tbody td, /* cells with
events inside (so NOT the day number cell) */Ðfc-row .fc-helper-skeleton
tbody td {Ð   /* don't put a border between event cells */Ð   border-top: 0;ÞØ
* Scrolling ContainerÐ
-------------------------------------------------------------------------------------
*/Ðfc-scroller { /* this class goes on elements for guaranteed vertical
scrollbars */Ð   overflow-y: scroll;Ð   overflow-x: hidden;ÞÞfc-scroller > *
{ /* we expect an immediate inner element */Ð   position: relative; /* re-
scope all positions */Ð   width: 100%; /* hack to force re-sizing this inner
element when scrollbars appear/disappear */Ð   overflow: hidden; /* don't let
negative margins or absolute positioning create further scroll */ÞØ* Global
Event StylesÐ-------------------------------------------------------------------
--------------------------------*/Ðfc-event {Ð   position: relative; /* for
resize handle and other inner positioning */Ð   display: block; /* make the
<a> tag block */Ð   font-size: .85em;Ð   line-height: 1.3;Ð   border-radius:
3px;Ð   border: 1px solid #3a87ad; /* default BORDER color */Ð   background-
color: #3a87ad; /* default BACKGROUND color */Ð   font-weight: normal; /*
undo jqui's ui-widget-header bold */ÞØ* overpower some of bootstrap's and
jqui's styles on <a> tags */Ðfc-event,Ðfc-event:hover,Ðui-widget .fc-event {Ð
    color: #fff; /* default TEXT color */Ð   text-decoration: none; /* if <a>
has an href */ÞØfc-event[href],Ðfc-event.fc-draggable {Ð   cursor: pointer; /
* give events with links and draggable events a hand mouse pointer */ÞØfc-not-
allowed, /* causes a "warning" cursor. applied on body */Ðfc-not-allowed .fc-
event { /* to override an event's custom cursor */Ð   cursor: not-allowed;ÞØ*
DayGrid eventsÐ-----------------------------------------------------------------
-----------------------------------------We use the full "fc-day-grid-event" class
instead of using descendants because the event won'tÐe a descendant of the
grid when it is being dragged.Ð*/ÐÐfc-day-grid-event {Ð   margin: 1px 2px 0; /*
spacing between events and edges */Ð   padding: 0 1px;ÞØ* events that are
continuing to/from another week. kill rounded corners and butt up against
edge */Ðfc-ltr .fc-day-grid-event.fc-not-start,Ðfc-rtl .fc-day-grid-event.fc-
not-end {Ð   margin-left: 0;Ð   border-left-width: 0;Ð   padding-left: 1px; /
* replace the border with padding */Ð   border-top-left-radius: 0;Ð   border-
bottom-left-radius: 0;ÞÞfc-ltr .fc-day-grid-event.fc-not-end,Ðfc-rtl .fc-day-
grid-event.fc-not-start {Ð   margin-right: 0;Ð   border-right-width: 0;Ð
padding-right: 1px; /* replace the border with padding */Ð   border-top-right-
radius: 0;Ð   border-bottom-right-radius: 0;ÞÞfc-day-grid-event > .fc-content
{ /* force events to be one-line tall */Ð   white-space: nowrap;Ð   overflow:
hidden;ÞÞfc-day-grid-event .fc-time {Ð   font-weight: bold;ÞØ* resize handle
(outside of fc-content, so can go outside of bounds) */Ðfc-day-grid-event .fc-
resizer {Ð   position: absolute;Ð   top: 0;Ð   bottom: 0;Ð   width: 7px;ÞÞfc-
ltr .fc-day-grid-event .fc-resizer {Ð   right: -3px;Ð   cursor: e-resize;ÞÞfc-
rtl .fc-day-grid-event .fc-resizer {Ð   left: -3px;Ð   cursor: w-resize;ÞØ*
Event LimitingÐ-----------------------------------------------------------------
-----------------------------------*/Ø* "more" link that represents hidden
events */Ðfc.fc-more {Ð   margin: 1px 3px;Ð   font-size: .85em;Ð   cursor:
pointer;Ð   text-decoration: none;ÞÞfc.fc-more:hover {Ð   text-decoration:
underline;ÞÞfc-limited { /* rows and cells that are hidden because of a
"more" link */Ð   display: none;ÞØ* popover that appears when "more" link is
clicked */Ðfc-day-grid .fc-row {Ð   z-index: 1; /* make the "more" popover
one higher than this */ÞØfc-more-popover {Ð   z-index: 2;Ð   width: 220px;ÞØ
.fc-more-popover .fc-event-container {Ð   padding: 10px;ÞØ* ToolbarÐ
-------------------------------------------------------------------------------------
*/Ðfc-toolbar {Ð   text-align: center;Ð   margin-bottom: 1em;ÞØfc-toolbar .fc-
left {Ð   float: left;ÞØfc-toolbar .fc-right {Ð   float: right;ÞØfc-
toolbar .fc-center {Ð   display: inline-block;ÞØ* the things within each left/
right/center section */Ðfc .fc-toolbar > * > * { /* extra precedence to
override button border margins */Ð
```

float: left;Ð margin-left: .75em;ÞÐ* the first thing within each left/center/right section */Ðfc .fc-toolbar > * > :first-child { /* extra precedence to override button border margins */Ð margin-left: 0;ÞÐ* title text */Ðfc-toolbar h2 {Ð margin: 0;ÞÐ* button layering (for border precedence) */Ðfc-toolbar button {Ð position: relative;Ð }Ðfc-toolbar .fc-state-hover,Ðfc-toolbar .ui-state-hover {Ð z-index: 2;ÞÐfc-toolbar .fc-state-down {Ð z-index: 3;ÞÐfc-toolbar .fc-state-active,Ðfc-toolbar .ui-state-active {Ð z-index: 4;ÞÐfc-toolbar button:focus {Ð z-index: 5;ÞÐ* View StructureÐ

/Ð undo twitter bootstrap's box-sizing rules. normalizes positioning techniques */Ð* don't do this for the toolbar because we'll want bootstrap to style those buttons as some pt */Ðfc-view-container *,Ðfc-view-container *:before,Ðfc-view-container *:after {Ð -webkit-box-sizing: content-box;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÞÐfc-view, /* scope positioning and z-index's for everything within the view */Ðfc-view > table { /* so dragged elements can be above the view's main element */Ð position: relative;Ð z-index: 1;ÞÐ* BasicViewÐ

/Ð day row structure */Ðfc-basicWeek-view .fc-content-skeleton,Ðfc-basicDay-view .fc-content-skeleton {Ð /* we are sure there are no day numbers in these views, so... */Ð padding-top: 1px; /* add a pixel to make sure there are 2px padding above events */Ð padding-bottom: 1em; /* ensure a space at bottom of cell for user selecting/clicking */ÞÐfc-basic-view tbody .fc-row {Ð min-height: 4em; /* ensure that all rows are at least this tall */ÞÐ* a "rigid" row will take up a constant amount of height because content-skeleton is absolute */Ðfc-row.fc-rigid {Ð overflow: hidden;ÞÐfc-row.fc-rigid .fc-content-skeleton {Ð position: absolute;Ð top: 0;Ð left: 0;Ð right: 0;ÞÐ /* week and day number styling */Ðfc-basic-view .fc-week-number,Ðfc-basic-view .fc-day-number {Ð padding: 0 2px;ÞÐfc-basic-view td.fc-week-number span,Ðfc-basic-view td.fc-day-number {Ð padding-top: 2px;Ð padding-bottom: 2px;ÞÐfc-basic-view .fc-week-number {Ð text-align: center;ÞÐfc-basic-view .fc-week-number span {Ð /* work around the way we do column resizing and ensure a minimum width */Ð display: inline-block;Ð min-width: 1.25em;ÞÐfc-ltr .fc-basic-view .fc-day-number {Ð text-align: right;ÞÐ .fc-rtl .fc-basic-view .fc-day-number {Ð text-align: left;ÞÐfc-day-number.fc-other-month {Ð opacity: 0.3;Ð filter: alpha(opacity=30); /* for IE */Ð /* opacity with small font can sometimes look too fadedÐ might want to set the 'color' property insteadÐ making day-numbers bold also fixes the problem */ÞÐ* AgendaView all-day areaÐ

/Ðfc-agenda-view .fc-day-grid {Ð position: relative;Ð z-index: 2; / so the "more.." popover will be over the time grid */ÞÐfc-agenda-view .fc-day-grid .fc-row {Ð min-height: 3em; /* all-day section will never get shorter than this */ÞÐfc-agenda-view .fc-day-grid .fc-row .fc-content-skeleton {Ð padding-top: 1px; /* add a pixel to make sure there are 2px padding above events */Ð padding-bottom: 1em; /* give space underneath events for clicking/selecting days */ÞÐ* TimeGrid axis running down the side (for both the all-day area and the slot area)Ð

/Ðfc .fc-axis { / .fc to overcome default cell styles */Ð vertical-align: middle;Ð padding: 0 4px;Ð white-space: nowrap;ÞÐfc-ltr .fc-axis {Ð text-align: right;ÞÐfc-rtl .fc-axis {Ð text-align: left;ÞÐui-widget td.fc-axis {Ð font-weight: normal; /* overcome jqui theme making it bold */ÞÐ* TimeGrid StructureÐ----------*/Ðfc-time-grid-container, /* so scroll container's z-index is below all-day */Ðfc-time-grid { /* so slats/bg/content/ etc positions get scoped within here */Ð position: relative;Ð z-index: 1;ÞÐ .fc-time-grid {Ð min-height: 100%; /* so if height setting is 'auto', .fc-bg stretches to fill height */Ð

}Ðfc-time-grid table { /* don't put outer borders on slats/bg/content/etc */Ð border: 0 hidden transparent;ÞÐfc-time-grid > .fc-bg {Ð z-index: 1;ÞÐfc-time-grid .fc-slats,Ðfc-time-grid > hr { /* the <hr> AgendaView injects when grid is shorter than scroller */Ð position: relative;Ð z-index: 2;ÞÐfc-time-grid .fc-bgevent-skeleton,Ðfc-time-grid .fc-content-skeleton {Ð position: absolute;Ð top: 0;Ð left: 0;Ð right: 0;ÞÐfc-time-grid .fc-bgevent-skeleton {Ð z-index: 3;ÞÐfc-time-grid .fc-highlight-skeleton {Ð z-index: 4;ÞÐfc-time-grid .fc-content-skeleton {Ð z-index: 5;ÞÐfc-time-grid .fc-helper-skeleton {Ð z-index: 6;ÞÐ* TimeGrid Slats (lines that run horizontally)Ð

/Ðfc-slats td {Ð height: 1.5em;Ð border-bottom: 0; / each cell is responsible for its top border */ÞÐfc-slats .fc-minor td {Ð border-top-style: dotted;ÞÐfc-slats .ui-widget-content { /* for jqui theme */Ð background: none; /* see through to fc-bg */ÞÐ* TimeGrid Highlighting SlotsÐ

/Ðfc-time-grid .fc-highlight-container { / a div within a cell within the fc-highlight-skeleton */Ð position: relative; /* scopes the left/right of the fc-highlight to be in the column */ÞÐfc-time-grid .fc-highlight {Ð position: absolute;Ð left: 0;Ð right: 0;Ð /* top and bottom will be in by JS */ÞÐ* TimeGrid Event ContainmentÐ

/Ðfc-time-grid .fc-event-container, / a div within a cell within the fc-content-skeleton */Ðfc-time-grid .fc-bgevent-container { /* a div within a cell within the fc-bgevent-skeleton */Ð position: relative;ÞÐfc-ltr .fc-time-grid .fc-event-container { /* space on the sides of events for LTR (default) */Ð margin: 0 2.5% 0 2px;ÞÐfc-rtl .fc-time-grid .fc-event-container { /* space on the sides of events for RTL */Ð margin: 0 2px 0 2.5%;ÞÐfc-time-grid .fc-event,Ðfc-time-grid .fc-bgevent {Ð position: absolute;Ð z-index: 1; /* scope inner z-index's */ÞÐfc-time-grid .fc-bgevent {Ð /* background events always span full width */Ð left: 0;Ð right: 0;ÞÐ* TimeGrid Event StylingÐ

We use the full "fc-time-grid-event" class instead of using descendants because the event won'tÐe a descendant of the grid when it is being dragged.Ð/Ð .fc-time-grid-event.fc-not-start { /* events that are continuing from another day */Ð /* replace space made by the top border with padding */Ð border-top-width: 0;Ð padding-top: 1px;Ð /* remove top rounded corners */Ð border-top-left-radius: 0;Ð border-top-right-radius: 0;ÞÐfc-time-grid-event.fc-not-end {Ð /* replace space made by the top border with padding */Ð border-bottom-width: 0;Ð padding-bottom: 1px;Ð /* remove bottom rounded corners */Ð border-bottom-left-radius: 0;Ð border-bottom-right-radius: 0;ÞÐfc-time-grid-event {Ð overflow: hidden; /* don't let the bg flow over rounded corners */ÞÐfc-time-grid-event > .fc-content { /* contains the time and title, but no bg and resizer */Ð position: relative;Ð z-index: 2; /* above the bg */ÞÐfc-time-grid-event .fc-time,Ðfc-time-grid-event .fc-title {Ð padding: 0 1px;ÞÐfc-time-grid-event .fc-time {Ð font-size: .85em;Ð white-space: nowrap;ÞÐfc-time-grid-event .fc-bg {Ð z-index: 1;Ð background: #fff;Ð opacity: .25;Ð filter: alpha(opacity=25); /* for IE */ÞÐ* short mode, where time and title are on the same line */Ðfc-time-grid-event.fc-short .fc-content {Ð /* don't wrap to second line (now that contents will be inline) */Ð white-space: nowrap;ÞÐfc-time-grid-event.fc-short .fc-time,Ðfc-time-grid-event.fc-short .fc-title {Ð /* put the time and title on the same line */Ð display: inline-block;Ð vertical-align: top;ÞÐfc-time-grid-event.fc-short .fc-time span {Ð display: none; /* don't display the full time text... */ÞÐfc-time-grid-event.fc-short .fc-time:before {Ð content: attr(data-start); /* ...instead, display only the start time */ÞÐ .fc-time-grid-event.fc-short .fc-time:after {Ð content: "\000A0-\000A0"; /* seperate with a dash, wrapped in nbsp's */ÞÐfc-time-grid-event.fc-short .fc-title {Ð

```
            font-size: .85em; /* make the title text the same size as the time
*/Ð   padding: 0; /* undo padding from above */ÐÐÐ* resizer */Ðfc-time-grid-
event .fc-resizer {Ð   position: absolute;Ð   z-index: 3; /* above content */Ð
    left: 0;Ð   right: 0;Ð   bottom: 0;Ð   height: 8px;Ð   overflow: hidden;Ð
    line-height: 8px;Ð   font-size: 11px;Ð   font-family: monospace;Ð   text-
align: center;Ð   cursor: s-resize;ÐÐÐfc-time-grid-event .fc-resizer:after {Ð
    content: "=";ÐÐ
```

public\assets\css\plugins\fullcalendar\fullcalendar.print.css

```
/*!Ð* FullCalendar v2.2.0 Print StylesheetÐ* Docs & License: http://
arshaw.com/fullcalendar/Ð* (c) 2013 Adam ShawÐ*/Ø*Ð* Include this stylesheet
on your page to get a more printer-friendly calendar.Ð* When including this
stylesheet, use the media='print' attribute of the <link> tag.Ð* Make sure to
include this stylesheet IN ADDITION to the regular fullcalendar.css.Ð*/Ðfc {Þ
max-width: 100% !important;ÞØ* Global Event RestylingÐ
-----------------------------------------------------------------------------------------------
*/Ðfc-event {Þ& 6¶w&÷VæC¢ 6ffb  –× ÷'F çC½6öÆ÷#¢ 3     –× ÷'F çC½  vRÖ'&V ²Ð
inside: avoid;ÞÐfc-event .fc-resizer {ÞF—7 Æ “¢ æöæS½Ø* Table & Day-Row
RestylingÐ-----------------------------------------------------------------------
-----------------------------*/Ðh,Ðd,Ðr,Ðhead,Ðbody,Ðfc-row {Þ&÷&FW"Ö6öÆ÷#¢
#ccc !important;Þ& 6¶w&÷VæC¢ 6ffb  –× ÷'F çC½Ø* kill the overlaid, absolutely-
positioned common components */Ðfc-bg,Ðfc-bgevent-skeleton,Ðfc-highlight-
skeleton,Ðfc-helper-skeleton {ÞF—7 Æ “¢ æöæS½Ø* don't force a min-height on
rows (for DayGrid) */Ðfc tbody .fc-row {Þ†V–v‡C¢  WFò  –× ÷'F çC² ò¢ VæFò
height that JS set in distributeHeight */ÞÖ–âÖ†V–v‡C¢    –× ÷'F çC² ò¢ VæFò
the min-height from each view's specific stylesheet */ÞÐfc tbody .fc-row .fc-
content-skeleton {Þ ÷6—F–öã¢ 7F F–3² ò¢ VæFò æf2×&–v–B ¢ý  FF–ærÖ&÷GFöÓ¢
important; /* use a more border-friendly method for this... */ÞÐfc tbody .fc-
row .fc-content-skeleton tbody tr:last-child td { /* only works in newer
browsers */Þ  FF–ærÖ&÷GFöÓ¢  VÓ² ò¢ ââæv—fW2 7  6R v—F†–â F†R 6¶VÆWFöââ  Ç6ò
ensures min height in a way */ÞÐfc tbody .fc-row .fc-content-skeleton table {Ðð
* provides a min-height for the row, but only effective for IE, which
exaggerates this value,Ð   Ö ¶–ær —B Æöö² Ö÷&R Æ–¶R 6VÒâ f÷" ÷F†W" '&÷vW'2Â —B
will already be this tall */Þ†V–v‡C¢  VÓ½Ø* Undo month-view event limiting.
Display all events and hide the "more" linksÐ
-----------------------------------------------------------------------------------------------
*/Ðfc-more-cell,Ðfc-more {ÞF—7 Æ “¢ æöæR  –× ÷'F çC½Ðfc tr.fc-limited {Þ
display: table-row !important;ÞÐfc td.fc-limited {ÞF—7 Æ “¢ F &ÆRÖ6VÆÂ
important;ÞÐfc-popover {ÞF—7 Æ “¢ æöæS² ò¢ æWfW" F—7 Æ ’ F†R &Ö÷&Rââ"  ÷ ÷fW"
in print mode */ÞØ* TimeGrid RestylingÐ
-----------------------------------------------------------------------------------------------
*/Ø* undo the min-height 100% trick used to fill the container's height */Ðfc-
time-grid {ÞÖ–âÖ†V–v‡C¢    –× ÷'F çC½Ø* don't display the side axis at all
("all-day" and time cells) */Ðfc-agenda-view .fc-axis {ÞF—7 Æ “¢ æöæS½Ø*
don't display the horizontal lines */Ðfc-slats,Ðfc-time-grid hr { /* this hr
is used when height is underused and needs to be filled */ÞF—7 Æ “¢ æöæR
important; /* important overrides inline declaration */ÞØ* let the container
that holds the events be naturally positioned and create real height */Ðfc-
time-grid .fc-content-skeleton {Þ ÷6—F–öã¢ 7F F–3½Ø* in case there are no
events, we still want some height */Ðfc-time-grid .fc-content-skeleton table {Þ
height: 4em;ÞØ* kill the horizontal spacing made by the event container.
event margins will be done below */Ðfc-time-grid .fc-event-container {ÞÖ &v–ã¢
0 !important;ÞØ* TimeGrid *Event* RestylingÐ
-----------------------------------------------------------------------------------------------
*/Ø* naturally position events, vertically stacking them */Ðfc-time-grid .fc-
event {Þ ÷6—F–öã¢ 7F F–2  –× ÷'F çC½Ö &v–ã¢ 7 , ' ,  –× ÷'F çC½Ø* for events
that continue to a future day, give the bottom border back */Ðfc-time-
grid .fc-event.fc-not-end {Þ&÷&FW"Ö&÷GFöÒ×v–GFƒ¢   ,  –× ÷'F çC½Ø* indicate
the event continues via "..." text */Ðfc-time-grid .fc-event.fc-not-end:after
{Þ6öçFVçC¢ "âââ#½Ø* for events that are continuations from previous days,
give the top border back */Ðfc-time-grid .fc-event.fc-not-start {Þ&÷&FW"×F÷ Ð
width: 1px !important;ÞØ* indicate the event is a continuation via "..." text
*/Ðfc-time-grid .fc-event.fc-not-start:before {Þ6öçFVçC¢ "âââ#½Ø* time */Ø*
undo a previous declaration and let the time text span to a second line */Ðfc-
time-grid .fc-event .fc-time {Þv†—FR×7  6S¢ æ÷&Ö Â  –× ÷'F çC½Ø* hide the the
time that is normally displayed... */Ðfc-time-grid .fc-event .fc-time span {Þ
display: none;ØØ* ...replace it with a more verbose version (includes AM/PM)
stored in an html attribute */Ð
```

.fc-time-grid .fc-event .fc-time:after {Þ
content: attr(data-full);ÞÞ* Vertical Scroller & ContainersÐ

/Ø kill the scrollbars and allow natural height */Ðfc-scroller,Ðfc-day-grid-
container, /* these divs might be assigned height, which we need to
cleared */Ðfc-time-grid-container { /* */Ð÷fW&fÆ÷s¢ f—6–&ÆR –× ÷'F çC½
height: auto !important;ÞØ* kill the horizontal border/padding used to
compensate for scrollbars */Ðfc-row {Ð&÷&FW#¢ –× ÷'F çC½Ö &v–ã¢
important;ÞØ* Button ControlsÐ
---
*/Ðfc-button-group,Ðfc button {ÐF—7 Æ “¢ æöæS² ò¢ FöâwB F—7 Æ ’ ç’ 'WGFöâÐ
related controls */ÞÐ

public\assets\css\plugins\iCheck\custom.css

```
/* iCheck plugin Square skin, greenĐ----------------------------------- */Đ
.icheckbox_square-green,Điradio_square-green {Đ   display: inline-block;Đ
*display: inline;Đ   vertical-align: middle;Đ   margin: 0;Đ   padding: 0;Đ
width: 22px;Đ   height: 22px;Đ   background: url(green.png) no-repeat;Đ
border: none;Đ   cursor: pointer;ĐĐ.icheckbox_square-green {Đ   background-
position: 0 0;ĐĐ.icheckbox_square-green.hover {Đ   background-position: -24px
0;ĐĐ.icheckbox_square-green.checked {Đ   background-position: -48px 0;ĐĐ
.icheckbox_square-green.disabled {Đ   background-position: -72px 0;Đ
cursor: default;ĐĐ.icheckbox_square-green.checked.disabled {Đ   background-
position: -96px 0;ĐĐ.iradio_square-green {Đ   background-position: -120px 0;ĐĐ
.iradio_square-green.hover {Đ   background-position: -144px 0;ĐĐ.iradio_square-
green.checked {Đ   background-position: -168px 0;ĐĐ.iradio_square-
green.disabled {Đ   background-position: -192px 0;Đ   cursor: default;ĐĐ
.iradio_square-green.checked.disabled {Đ   background-position: -216px 0;ĐĐ/*
HiDPI support */@media (-o-min-device-pixel-ratio: 5/4), (-webkit-min-device-
pixel-ratio: 1.25), (min-resolution: 120dpi) {Đ   .icheckbox_square-green,Đ
    .iradio_square-green {Đ       background-image: url(green@2x.png);Đ
-webkit-background-size: 240px 24px;Đ       background-size: 240px 24px;Đ   }Đ
```

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.css

```
/* Ion.RangeSliderØ/ css version 1.8.5Ø/ by Denis Ineshin | ionden.comØ/ =====
==============================================================================
================================*/Ø* ==========================================
==============================================================================Ð
// RangeSlider */Ðirs {Ð   position: relative; display: block;ÞÐ   .irs-line {Ð
        position: relative; display: block;Ð       overflow: hidden;Ð   }Ð
        .irs-line-left, .irs-line-mid, .irs-line-right {Ð           position:
absolute; display: block;Ð           top: 0;Ð       }Ð       .irs-line-left {Ð
            left: 0; width: 10%;Ð       }Ð       .irs-line-mid {Ð
left: 10%; width: 80%;Ð       }Ð       .irs-line-right {Ð           right: 0;
width: 10%;Ð       }Ð   .irs-diapason {Ð       position: absolute; display:
block;Ð       left: 0; width: 100%;Ð   }Ð   .irs-slider {Ð       position:
absolute; display: block;Ð       cursor: default;Ð       z-index: 1;Ð   }Ð
        .irs-slider.single {Ð           left: 10px;Ð       }Ð           .irs-
slider.single:before {Ð               position: absolute; display: block;
content: "";Ð               top: -30%; left: -30%;Ð               width:
160%; height: 160%;Ð               background: rgba(0,0,0,0.0);Ð           }Ð
        .irs-slider.from {Ð           left: 100px;Ð       }Ð           .irs-
slider.from:before {Ð               position: absolute; display: block;
content: "";Ð               top: -30%; left: -30%;Ð               width:
130%; height: 160%;Ð               background: rgba(0,0,0,0.0);Ð           }Ð
        .irs-slider.to {Ð           left: 300px;Ð       }Ð           .irs-
slider.to:before {Ð               position: absolute; display: block;
content: "";Ð               top: -30%; left: 0;Ð               width: 130%;
height: 160%;Ð               background: rgba(0,0,0,0.0);Ð           }Ð
        .irs-slider.last {Ð           z-index: 2;Ð       }Ð   .irs-min {Ð
        position: absolute; display: block;Ð       left: 0;Ð       cursor:
default;Ð   }Ð   .irs-max {Ð       position: absolute; display: block;Ð
right: 0;Ð       cursor: default;Ð   }Ð   .irs-from, .irs-to, .irs-single {Ð
        position: absolute; display: block;Ð       top: 0; left: 0;Ð
cursor: default;Ð       white-space: nowrap;Ð   }Ðirs-grid {Ð   position:
absolute; display: none;Ð   bottom: 0; left: 0;Ð   width: 100%; height: 20px;ÞÐ
.irs-with-grid .irs-grid {Ð   display: block;ÞÐ   .irs-grid-pol {Ð
position: absolute;Ð       top: 0; left: 0;Ð       width: 1px; height: 8px;Ð
        background: #000;Ð   }Ð   .irs-grid-pol.small {Ð       height: 4px;Ð
    }Ð   .irs-grid-text {Ð       position: absolute;Ð       bottom: 0; left:
0;Ð       width: 100px;Ð       white-space: nowrap;Ð       text-align: center;Ð
        font-size: 9px; line-height: 9px;Ð       color: #000;Ð   }Ðirs-
disable-mask {Ð   position: absolute; display: block;Ð   top: 0; left: 0;Ð
width: 100%; height: 100%;Ð   cursor: default;Ð   background: rgba(0,0,0,0.0);Ð
    z-index: 2;ÞÐirs-disabled {Ð   opacity: 0.4;Þ
```

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinFlat.css

```
/* Ion.RangeSlider, Flat UI SkinØ/ css version 1.8.5Ø/ by Denis Ineshin |
ionden.comØ/ ==================================================================
==================================================*/Ø* =======================
==============================================================================
================Ø/ Skin details */Ðirs-line-mid,Ðirs-line-left,Ðirs-line-
right,Ðirs-diapason,Ðirs-slider {Ð   background: url(../images/sprite-skin-
flat.png) repeat-x;ÞÐirs {Ð   height: 40px;ÞÐirs-with-grid {Ð   height: 60px;ÞÐ
.irs-line {Ð   height: 12px; top: 25px;ÞÐ   .irs-line-left {Ð       height:
12px;Ð       background-position: 0 -30px;Ð   }Ð   .irs-line-mid {Ð
height: 12px;Ð       background-position: 0 0;Ð   }Ð   .irs-line-right {Ð
        height: 12px;Ð       background-position: 100% -30px;Ð   }Ðirs-
diapason {Ð   height: 12px; top: 25px;Ð   background-position: 0 -60px;ÞÐirs-
slider {Ð   width: 16px; height: 18px;Ð   top: 22px;Ð   background-position:
0 -90px;ÞÐirs-active-slider, .irs-slider:hover {Ð   background-position: 0
-120px;ÞÐirs-min, .irs-max {Ð   color: #999;Ð   font-size: 10px; line-height:
1.333;Ð   text-shadow: none;Ð   top: 0; padding: 1px 3px;Ð   background:
#e1e4e9;Ð   border-radius: 4px;ÞÐirs-from, .irs-to, .irs-single {Ð   color:
#fff;Ð   font-size: 10px; line-height: 1.333;Ð   text-shadow: none;Ð
padding: 1px 5px;Ð   background: #ed5565;Ð   border-radius: 4px;ÞÐirs-
from:after, .irs-to:after, .irs-single:after {Ð   position: absolute;
display: block; content: "";Ð   bottom: -6px; left: 50%;Ð   width: 0; height:
0;Ð   margin-left: -3px;Ð   overflow: hidden;Ð   border: 3px solid
transparent;Ð   border-top-color: #ed5565;ÞÐirs-grid-pol {Ð   background:
#e1e4e9;ÞÐirs-grid-text {Ð   color: #999;ÞÐirs-disabled {Þ
```

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinNice.css

/* Ion.RangeSlider, Nice SkinØ/ css version 1.8.5Ø/ by Denis Ineshin | ionden.comØ/ ==========*/Ø* ==========Ø/ Skin details */Ðirs-line-mid,Ðirs-line-left,Ðirs-line-right,Ðirs-diapason,Ðirs-slider {Ð background: url(../img/sprite-skin-nice.png) repeat-x;ÞÐirs {Ð height: 40px;ÞÐirs-with-grid {Ð height: 60px;ÞÐ .irs-line {Ð height: 8px; top: 25px;ÞÐ .irs-line-left {Ð height: 8px;Ð background-position: 0 -30px;Ð }Ð .irs-line-mid {Ð height: 8px;Ð background-position: 0 0;Ð }Ð .irs-line-right {Ð height: 8px;Ð background-position: 100% -30px;Ð }Ðirs-diapason {Ð height: 8px; top: 25px;Ð background-position: 0 -60px;ÞÐirs-slider {Ð width: 22px; height: 22px;Ð top: 17px;Ð background-position: 0 -90px;ÞÐirs-active-slider, .irs-slider:hover {Ð background-position: 0 -120px;ÞÐirs-min, .irs-max {Ð color: #999;Ð font-size: 10px; line-height: 1.333;Ð text-shadow: none;Ð top: 0; padding: 1px 3px;Ð background: rgba(0,0,0,0.1);Ð border-radius: 3px;ÞÐlt-ie9 .irs-min, .lt-ie9 .irs-max {Ð background: #ccc;ÞÐirs-from, .irs-to, .irs-single {Ð color: #fff;Ð font-size: 10px; line-height: 1.333;Ð text-shadow: none;Ð padding: 1px 5px;Ð background: rgba(0,0,0,0.3);Ð border-radius: 3px;ÞÐlt-ie9 .irs-from, .lt-ie9 .irs-to, .lt-ie9 .irs-single {Ð background: #999;ÞÐirs-grid-pol {Ð background: #99a4ac;ÞÐirs-grid-text {Ð color: #99a4ac;ÞÐirs-disabled {Þ

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinSimple.css

```
/* Ion.RangeSlider, Simple SkinØ/ css version 1.8.5Ø/ by Denis Ineshin |
ionden.comØ/ ====================================================================
=================================================*/Ø* ========================
==========================================================================
================Ø/ Skin details */Ðirs-line-mid,Ðirs-line-left,Ðirs-line-
right,Ðirs-diapason,Ðirs-slider {Ð   background: url(../img/sprite-skin-
simple.png) repeat-x;ÞÐirs {Ð   height: 40px;ÞÐirs-with-grid {Ð   height:
60px;ÞÐirs-line {Ð   height: 6px; top: 25px;ÞÐ   .irs-line-left {Ð
height: 6px;Ð       background-position: 0 -30px;Ð   }Ð   .irs-line-mid {Ð
        height: 6px;Ð       background-position: 0 0;Ð   }Ð   .irs-line-right
{Ð       height: 6px;Ð       background-position: 100% -30px;Ð   }Ðirs-
diapason {Ð   height: 6px; top: 25px;Ð   background-position: 0 -60px;ÞÐirs-
slider {Ð   width: 8px; height: 15px;Ð   top: 21px;Ð   background-position: 0
-90px;ÞÐirs-active-slider, .irs-slider:hover {Ð   background-position: 0
-120px;ÞÐirs-min, .irs-max {Ð   color: #c0c0c0;Ð   font-size: 10px; line-
height: 1.333;Ð   text-shadow: none;Ð   top: 0; padding: 1px 3px;Ð
background: rgba(0,0,0,0.1);Ð   border-radius: 3px;ÞÐlt-ie9 .irs-min, .lt-
ie9 .irs-max {Ð   background: #3654b0;ÞÐirs-from, .irs-to, .irs-single {Ð
color: #000;Ð   font-size: 10px; line-height: 1.333;Ð   text-shadow: none;Ð
padding: 1px 5px;Ð   background: rgba(255,255,255,0.8);Ð   border-radius: 3px;Ð
}Ðlt-ie9 .irs-from, .lt-ie9 .irs-to, .lt-ie9 .irs-single {Ð   background:
#d8dff3;ÞÐirs-grid-pol {Ð   background: #777;ÞÐirs-grid-text {Ð   color:
#e0e0e0;ÞÐirs-disabled {Þ
```

public\assets\css\plugins\jqGrid\ui.jqgrid.css

/*Grid*/Ðui-jqgrid {position: relative;}Ðui-jqgrid .ui-jqgrid-view {position: relative;left:0; top: 0; padding: 0; font-size:11px;}Ø* caption*/Ðui-jqgrid .ui-jqgrid-titlebar {padding: .3em .2em .2em .3em; position: relative; font-size: 12px; border-left: 0 none;border-right: 0 none; border-top: 0 none;}Ðui-jqgrid .ui-jqgrid-caption {text-align: left;}Ðui-jqgrid .ui-jqgrid-title { margin: .1em 0 .2em; }Ðui-jqgrid .ui-jqgrid-titlebar-close { position: absolute;top: 50%; width: 19px; margin: -10px 0 0 0; padding: 1px; height:18px; cursor:pointer;}Ðui-jqgrid .ui-jqgrid-titlebar-close span { display: block; margin: 1px; }Ðui-jqgrid .ui-jqgrid-titlebar-close:hover { padding: 0; }Ø* header*/Ðui-jqgrid .ui-jqgrid-hdiv {position: relative; margin: 0;padding: 0; overflow-x: hidden; border-left: 0 none !important; border-top : 0 none !important; border-right : 0 none !important;}Ðui-jqgrid .ui-jqgrid-hbox {float: left; padding-right: 20px;}Ðui-jqgrid .ui-jqgrid-htable {table-layout:fixed;margin:0;}Ðui-jqgrid .ui-jqgrid-htable th {height:22px;padding: 0 2px 0 2px;}Ðui-jqgrid .ui-jqgrid-htable th div {overflow: hidden; position:relative; height:17px;}Ðui-th-column, .ui-jqgrid .ui-jqgrid-htable th.ui-th-column {overflow: hidden;white-space: nowrap;text-align:center;border-top : 0 none;border-bottom : 0 none;}Ðui-th-ltr, .ui-jqgrid .ui-jqgrid-htable th.ui-th-ltr {border-left : 0 none;}Ðui-th-rtl, .ui-jqgrid .ui-jqgrid-htable th.ui-th-rtl {border-right : 0 none;}Ðui-first-th-ltr {border-right: 1px solid; }Ðui-first-th-rtl {border-left: 1px solid; }Ðui-jqgrid .ui-th-div-ie {white-space: nowrap; zoom :1; height:17px;}Ð .ui-jqgrid .ui-jqgrid-resize {height:20px !important;position: relative; cursor :e-resize;display: inline;overflow: hidden;}Ðui-jqgrid .ui-grid-ico-sort {overflow:hidden;position:absolute;display:inline; cursor: pointer ! important;}Ðui-jqgrid .ui-icon-asc {margin-top:-3px; height:12px;}Ðui-jqgrid .ui-icon-desc {margin-top:3px;height:12px;}Ðui-jqgrid .ui-i-asc {margin-top:0;height:16px;}Ðui-jqgrid .ui-i-desc {margin-top:0;margin-left:13px;height:16px;}Ðui-jqgrid .ui-jqgrid-sortable {cursor:pointer;}Ðui-jqgrid tr.ui-search-toolbar th { border-top-width: 1px !important; border-top-color: inherit !important; border-top-style: ridge !important }Ðr.ui-search-toolbar input {margin: 1px 0 0 0}Ðr.ui-search-toolbar select {margin: 1px 0 0 0}Ø* body */ Ðui-jqgrid .ui-jqgrid-bdiv {position: relative; margin: 0; padding:0; overflow: auto; text-align:left;}Ðui-jqgrid .ui-jqgrid-btable {table-layout:fixed; margin:0; outline-style: none; }Ðui-jqgrid tr.jqgrow { outline-style: none; }Ðui-jqgrid tr.jqgroup { outline-style: none; }Ðui-jqgrid tr.jqgrow td {font-weight: normal; overflow: hidden; white-space: pre; height: 22px;padding: 0 2px 0 2px;border-bottom-width: 1px; border-bottom-color: inherit; border-bottom-style: solid;}Ðui-jqgrid tr.jqgfirstrow td {padding: 0 2px 0 2px;border-right-width: 1px; border-right-style: solid;}Ðui-jqgrid tr.jqgroup td {font-weight: normal; overflow: hidden; white-space: pre; height: 22px;padding: 0 2px 0 2px;border-bottom-width: 1px; border-bottom-color: inherit; border-bottom-style: solid;}Ðui-jqgrid tr.jqfoot td {font-weight: bold; overflow: hidden; white-space: pre; height: 22px;padding: 0 2px 0 2px;border-bottom-width: 1px; border-bottom-color: inherit; border-bottom-style: solid;}Ðui-jqgrid tr.ui-row-ltr td {text-align:left;border-right-width: 1px; border-right-color: inherit; border-right-style: solid;}Ðui-jqgrid tr.ui-row-rtl td {text-align:right;border-left-width: 1px; border-left-color: inherit; border-left-style: solid;}Ðui-jqgrid td.jqgrid-rownum { padding: 0 2px 0 2px; margin: 0; border: 0 none;}Ðui-jqgrid .ui-jqgrid-resize-mark { width:2px; left:0; background-color:#777; cursor: e-resize; cursor: col-resize; position:absolute; top:0; height:100px; overflow:hidden; display:none; border:0 none; z-index: 99999;}Ø* footer */Ðui-jqgrid .ui-jqgrid-sdiv {position: relative; margin: 0;padding: 0; overflow: hidden; border-left: 0 none !important; border-top : 0 none !important; border-right : 0 none !important;}Ðui-jqgrid .ui-jqgrid-ftable {table-layout:fixed; margin-bottom:0;}Ðui-jqgrid tr.footrow td {font-weight: bold; overflow: hidden; white-space:nowrap; height: 21px;padding: 0 2px 0 2px;border-top-width: 1px; border-top-color: inherit; border-top-style: solid;}Ð

.ui-jqgrid tr.footrow-ltr td {text-align:left;border-right-width: 1px; border-right-color: inherit; border-right-style: solid;}Đui-jqgrid tr.footrow-rtl td {text-align:right;border-left-width: 1px; border-left-color: inherit; border-left-style: solid;}Ø* Pager*/Đui-jqgrid .ui-jqgrid-pager { border-left: 0 none !important;border-right: 0 none !important; border-bottom: 0 none !important; margin: 0 !important; padding: 0 !important; position: relative; height: 25px;white-space: nowrap;overflow: hidden;font-size:11px;}Đui-jqgrid .ui-pager-control {position: relative;}Đui-jqgrid .ui-pg-table {position: relative; padding-bottom:2px; width:auto; margin: 0;}Đui-jqgrid .ui-pg-table td {font-weight:normal; vertical-align:middle; padding:1px;}Đui-jqgrid .ui-pg-button { height:19px !important;}Đui-jqgrid .ui-pg-button span { display: block; margin: 1px; float:left;}Đui-jqgrid .ui-pg-button:hover { padding: 0; }Đ .ui-jqgrid .ui-state-disabled:hover {padding:1px;}Đui-jqgrid .ui-pg-input { height:13px;font-size:.8em; margin: 0;}Đui-jqgrid .ui-pg-selbox {font-size:.8em; line-height:18px; display:block; height:18px; margin: 0;}Đui-jqgrid .ui-separator {height: 18px; border-left: 1px solid #ccc ; border-right: 1px solid #ccc ; margin: 1px; float: right;}Đui-jqgrid .ui-paging-info {font-weight: normal;height:19px; margin-top:3px;margin-right:4px;}Đui-jqgrid .ui-jqgrid-pager .ui-pg-div {padding:1px 0;float:left;position:relative;}Đui-jqgrid .ui-jqgrid-pager .ui-pg-button { cursor:pointer; }Đui-jqgrid .ui-jqgrid-pager .ui-pg-div span.ui-icon {float:left;margin:0 2px;}Đui-jqgrid td input, .ui-jqgrid td select .ui-jqgrid td textarea { margin: 0;}Đui-jqgrid td textarea {width:auto;height:auto;}Đui-jqgrid .ui-jqgrid-toppager {border-left: 0 none !important;border-right: 0 none !important; border-top: 0 none !important; margin: 0 !important; padding: 0 !important; position: relative; height: 25px !important;white-space: nowrap;overflow: hidden;}Đui-jqgrid .ui-jqgrid-toppager .ui-pg-div {padding:1px 0;float:left;position:relative;}Đui-jqgrid .ui-jqgrid-toppager .ui-pg-button { cursor:pointer; }Đui-jqgrid .ui-jqgrid-toppager .ui-pg-div span.ui-icon {float:left;margin:0 2px;}Ø*subgrid*/Đ .ui-jqgrid .ui-jqgrid-btable .ui-sgcollapsed span {display: block;}Đui-jqgrid .ui-subgrid {margin:0;padding:0; width:100%;}Đui-jqgrid .ui-subgrid table {table-layout: fixed;}Đui-jqgrid .ui-subgrid tr.ui-subtblcell td {height:18px;border-right-width: 1px; border-right-color: inherit; border-right-style: solid;border-bottom-width: 1px; border-bottom-color: inherit; border-bottom-style: solid;}Đui-jqgrid .ui-subgrid td.subgrid-data {border-top: 0 none !important;}Đui-jqgrid .ui-subgrid td.subgrid-cell {border-width: 0 0 1px 0;}Đui-jqgrid .ui-th-subgrid {height:20px;}Ø* loading */Đui-jqgrid .loading {position: absolute; top: 45%;left: 45%;width: auto;z-index:101;padding: 6px; margin: 5px;text-align: center;font-weight: bold;display: none;border-width: 2px !important; font-size:11px;}Đui-jqgrid .jqgrid-overlay {display:none;z-index:100;}Ø* IE * html .jqgrid-overlay {width: expression(this.parentNode.offsetWidth+'px');height: expression(this.parentNode.offsetHeight+'px');} */Đ .jqgrid-overlay iframe {position:absolute;top:0;left:0;z-index:-1;}Ø* IE width: expression(this.parentNode.offsetWidth+'px');height: expression(this.parentNode.offsetHeight+'px');}*/Ø* end loading div */Ø* toolbar */Đui-jqgrid .ui-userdata {border-left: 0 none; border-right: 0 none;–†V–v‡B ¢ # ƒ¶÷fW&fÆ÷s¢ †–FFVã¹ƒÐModal Window */Đui-jqdialog { display: none; width: 300px; position: absolute; padding: .2em; font-size:11px; overflow:visible;}Đui-jqdialog .ui-jqdialog-titlebar { padding: .3em .2em; position: relative; }Đui-jqdialog .ui-jqdialog-title { margin: .1em 0 .2em; } Đui-jqdialog .ui-jqdialog-titlebar-close { position: absolute; top: 50%; width: 19px; margin: -10px 0 0 0; padding: 1px; height: 18px; cursor:pointer;}Đui-jqdialog .ui-jqdialog-titlebar-close span { display: block; margin: 1px; }Đui-jqdialog .ui-jqdialog-titlebar-close:hover, .ui-jqdialog .ui-jqdialog-titlebar-close:focus { padding: 0; }Đui-jqdialog-content, .ui-jqdialog .ui-jqdialog-content { border: 0; padding: .3em .2em; background: none; height:auto;}Đ

.ui-jqdialog .ui-jqconfirm {padding: .4em 1em;
border-width:3px;position:absolute;bottom:10px;right:10px;overflow:visible;dis
play:none;height:80px;width:220px;text-align:center;}Ðui-jqdialog>.ui-
resizable-se { bottom: -3px; right: -3px}Ðui-jqgrid>.ui-resizable-se
{ bottom: -3px; right: -3px }Ø* end Modal window*/Ø* Form edit */Ðui-jqdialog-
content .FormGrid {margin: 0;}Ðui-jqdialog-content .EditTable { width: 100%;
margin-bottom:0;}Ðui-jqdialog-content .DelTable { width: 100%; margin-
bottom:0;}ÐEditTable td input, .EditTable td select, .EditTable td textarea
{margin: 0;}ÐEditTable td textarea { width:auto; height:auto;}Ðui-jqdialog-
content td.EditButton {text-align: right;border-top: 0 none;border-left: 0
none;border-right: 0 none; padding-bottom:5px; padding-top:5px;}Ðui-jqdialog-
content td.navButton {text-align: center; border-left: 0 none;border-top: 0
none;border-right: 0 none; padding-bottom:5px; padding-top:5px;}Ðui-jqdialog-
content input.FormElement {padding:.3em}Ðui-jqdialog-content
select.FormElement {padding:.3em}Ðui-jqdialog-content .data-line {padding-
top:.1em;border: 0 none;}Ðui-jqdialog-content .CaptionTD {vertical-align:
middle;border: 0 none; padding: 2px;white-space: nowrap;}Ðui-jqdialog-
content .DataTD {padding: 2px; border: 0 none; vertical-align: top;}Ðui-
jqdialog-content .form-view-data {white-space:pre}Ðfm-button { display:
inline-block; margin:0 4px 0 0; padding: .4em .5em; text-decoration:none !
important; cursor:pointer; position: relative; text-align: center; zoom: 1; }Ð
.fm-button-icon-left { padding-left: 1.9em; }Ðfm-button-icon-right { padding-
right: 1.9em; }Ðfm-button-icon-left .ui-icon { right: auto; left: .2em;
margin-left: 0; position: absolute; top: 50%; margin-top: -8px; }Ðfm-button-
icon-right .ui-icon { left: auto; right: .2em; margin-left: 0; position:
absolute; top: 50%; margin-top: -8px;}ÐnData, #pData { float: left;
margin:3px;padding: 0; width: 15px; }Ø* End Eorm edit */Ø*.ui-jqgrid .edit-
cell {}*/Ðui-jqgrid .selected-row, div.ui-jqgrid .selected-row td {font-
style : normal;border-left: 0 none;}Ø* inline edit actions button*/Ðui-inline-
del.ui-state-hover span, .ui-inline-edit.ui-state-hover span,Ðui-inline-
save.ui-state-hover span, .ui-inline-cancel.ui-state-hover span {Ð margin:
-1px;ÐØ* Tree Grid */Ðui-jqgrid .tree-wrap {float: left; position:
relative;height: 18px;white-space: nowrap;overflow: hidden;}Ðui-jqgrid .tree-
minus {position: absolute; height: 18px; width: 18px; overflow: hidden;}Ðui-
jqgrid .tree-plus {position: absolute;–†V–v‡C¢ ‡ ƒ² v–GFƒ¢ ‡ ƒ¹overflow:
hidden;}Ðui-jqgrid .tree-leaf {position: absolute;–†V–v‡C¢ ‡ ƒ² v–GFƒ¢
18px;overflow: hidden;}Ðui-jqgrid .treeclick {cursor: pointer;}Ø* moda dialog
/Ð iframe.jqm {position:absolute;top:0;left:0;z-index:-1;}Ø’ v–GFƒ¢
expression(this.parentNode.offsetWidth+'px');height:
expression(this.parentNode.offsetHeight+'px');}*/Ðui-jqgrid-dnd tr td {border-
right-width: 1px; border-right-color: inherit; border-right-style: solid;
height:20px}Ø* RTL Support */Ðui-jqgrid .ui-jqgrid-caption-rtl {text-align:
right;}Ðui-jqgrid .ui-jqgrid-hbox-rtl {float: right; padding-left: 20px;}Ðui-
jqgrid .ui-jqgrid-resize-ltr {float: right;margin: -2px -2px -2px 0;}Ðui-
jqgrid .ui-jqgrid-resize-rtl {float: left;margin: -2px 0 -1px -3px;}Ðui-
jqgrid .ui-sort-rtl {left:0;}Ðui-jqgrid .tree-wrap-ltr {float: left;}Ðui-
jqgrid .tree-wrap-rtl {float: right;}Ðui-jqgrid .ui-ellipsis {-moz-text-
overflow:ellipsis;text-overflow:ellipsis;}Ø* Toolbar Search Menu */Ðui-search-
menu { position: absolute; padding: 2px 5px;}Ðui-jqgrid .ui-search-table
{ padding: 0; border: 0 none; height:20px; width:100%;}Ðui-jqgrid .ui-search-
table .ui-search-oper { width:20px; }Ð a.g-menu-item, a.soptclass,
a.clearsearchclass { cursor: pointer; }Ðui-jqgrid .ui-search-table .ui-search-
input>input,Ðui-jqgrid .ui-search-table .ui-search-input>selectÐÐ display:
block;Ð -moz-box-sizing: border-box;Ð -webkit-box-sizing: border-box;Ð
box-sizing: border-box;Ð Ðui-jqgrid .ui-jqgrid-view input,Ðui-jqgrid .ui-
jqgrid-view select,Ðui-jqgrid .ui-jqgrid-view textarea,Ðui-jqgrid .ui-jqgrid-
view button {Ð font-size: 11pxÐÐ

public\assets\css\plugins\jQueryUI\jquery-ui.css

/*! jQuery UI - v1.10.4 - 2014-02-18Þ http://jqueryui.comÞ Includes: jquery.ui.core.css, jquery.ui.resizable.css, jquery.ui.selectable.css, jquery.ui.accordion.css, jquery.ui.autocomplete.css, jquery.ui.button.css, jquery.ui.datepicker.css, jquery.ui.dialog.css, jquery.ui.menu.css, jquery.ui.progressbar.css, jquery.ui.slider.css, jquery.ui.spinner.css, jquery.ui.tabs.css, jquery.ui.tooltip.css, jquery.ui.theme.cssÞ Copyright 2014 jQuery Foundation and other contributors; Licensed MIT */Ø* Layout helpersÞ----------*/Þui-helper-hidden {ÞF—7 Æ “¢ æöæS½Þ .ui-helper-hidden-accessible {Þ&÷&FW#¢ ½6Æ— ¢ &V7Bƒ “½†V–v‡C¢ ƒ½ margin: -1px;Þ÷fW&fÆ÷s¢ †–FFVã½ FF–æs¢ ½ ÷6—F–öã¢ '6öÇWFS½v–GFƒ¢ ƒ½Þui-helper-reset {ÞÖ &v–ã¢ ½ FF–æs¢ ½&÷&FW#¢ ½÷WFÆ–æS¢ ½Æ–æRÖ†V–v‡C¢ ã3½FW‡BÞ decoration: none;ÞföçB×6—¦S¢ S½Æ—7B×7G–ÆS¢ æöæS½Þui-helper-clearfix:before,Þ .ui-helper-clearfix:after {Þ6öçFVçC¢ "#½F—7 Æ “¢ F &ÆS½&÷&FW"Ö6öÆÆ 6S¢ collapse;ÞÞui-helper-clearfix:after {Þ6ÆV #¢ &÷Fƒ½Þui-helper-clearfix {ÞÖ–âÞ height: 0; /* support: IE7 */ÞÞui-helper-zfix {Þv–GFƒ¢ S½†V–v‡C¢ S½F÷ ¢ 0;ÞÆVgC¢ ½ ÷6—F–öã¢ '6öÇWFS½÷ 6—G“¢ ½f–ÇFW#¤ Ç † „÷ 6—G“Ó “½Þui-front {Þ¢Þ index: 100;ÞØ* Interaction CuesÞ----------*/Þui-state-disabled {Þ7W'6÷#¢ FVf VÇB –× ÷'F çC½Ø* IconsÞ ----------*/Ø* states and images */Þui-icon {ÞF—7 Æ “¢ block;ÞFW‡BÖ–æFVçC¢ Ó“""“— ƒ½÷fW&fÆ÷s¢ †–FFVã½& 6¶w&÷VæB×&W V C¢ æò×&W V C½Ø* Misc visualsÞ----------*/Ø* Overlays */Þui-widget-overlay {Þ ÷6—F–öã¢ f—†VC½F÷ ¢ ½ÆVgC¢ ½v–GFƒ¢ S½†V–v‡C¢ S½Þui-resizable {Þ ÷6—F–öã¢ &VÆ F—fS½Þui-resizable-handle {Þ ÷6—F–öã¢ '6öÇWFS½föçBÞ size: 0.1px;ÞF—7 Æ “¢ &Æö6³½Þui-resizable-disabled .ui-resizable-handle,Þui-resizable-autohide .ui-resizable-handle {ÞF—7 Æ “¢ æöæS½Þui-resizable-n {Þ cursor: n-resize;Þ†V–v‡C¢ w ƒ½v–GFƒ¢ S½F÷ ¢ ÓW ƒ½ÆVgC¢ ½Þui-resizable-s {Þ cursor: s-resize;Þ†V–v‡C¢ w ƒ½v–GFƒ¢ S½&÷GFöÓ¢ ÓW ƒ½ÆVgC¢ ½Þui-resizable-e {Þ7W'6÷#¢ R×&W6—¦S½v–GFƒ¢ w ƒ½&–v‡C¢ ÓW ƒ½F÷ ¢ ½†V–v‡C¢ S½Þui-resizable-w {Þ7W'6÷#¢ r×&W6—¦S½v–GFƒ¢ w ƒ½ÆVgC¢ ÓW ƒ½F÷ ¢ ½†V–v‡C¢ S½Þui-resizable-se {Þ7W'6÷#¢ 6R×&W6—¦S½v–GFƒ¢ ' ƒ½†V–v‡C¢ ' ƒ½&–v‡C¢ ƒ½&÷GFöÓ¢ ƒ½Þui-resizable-sw {Þ7W'6÷#¢ 7r×&W6—¦S½v–GFƒ¢ — ƒ½†V–v‡C¢ — ƒ½ÆVgC¢ ÓW ƒ½&÷GFöÓ¢ -5px;ÞÞui-resizable-nw {Þ7W'6÷#¢ çr×&W6—¦S½v–GFƒ¢ — ƒ½†V–v‡C¢ — ƒ½ÆVgC¢ ÓW ƒ½ top: -5px;ÞÞui-resizable-ne {Þ7W'6÷#¢ æR×&W6—¦S½v–GFƒ¢ — ƒ½†V–v‡C¢ — ƒ½&–v‡C¢ -5px;ÞF÷ ¢ ÓW ƒ½Þui-selectable-helper {Þ ÷6—F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ ½ border: 1px dotted black;ÞÞui-accordion .ui-accordion-header {ÞF—7 Æ “¢ &Æö6³½ cursor: pointer;Þ ÷6—F–öã¢ &VÆ F—fS½Ö &v–â×F÷ ¢ ' ƒ½ padding: .5em .5em .5em .7em;ÞÖ–âÖ†V–v‡C¢ ² ò¢ 7W ÷'C¢ ”Sr ¢ÿÞui-accordion .ui-accordion-icons {Þ FF–ærÖÆVgC¢ "ã&VÓ½Þui-accordion .ui-accordion-noicons {Þ FF–ærÖÆVgC¢ ãvVÓ½Þui-accordion .ui-accordion-icons .ui-accordion-icons {Þ FF–ærÖÆVgC¢ "ã&VÓ½Þui-accordion .ui-accordion-header .ui-accordion-header-icon {Þ ÷6—F–öã¢ '6öÇWFS½ÆVgC¢ ãVVÓ½F÷ ¢ S S½Ö &v–â×F÷ ¢ -8px;ÞÞui-accordion .ui-accordion-content {Þ FF–æs¢ VÒ "ã&VÓ½&÷&FW"×F÷ ¢ ½ overflow: auto;ÞÞui-autocomplete {Þ ÷6—F–öã¢ '6öÇWFS½F÷ ¢ ½ÆVgC¢ ½7W'6÷#¢ default;ÞÞui-button {ÞF—7 Æ “¢ –æÆ–æRÖ&Æö6³½ ÷6—F–öã¢ &VÆ F—fS½ FF–æs¢ ½Æ–æRÞ height: normal;ÞÖ &v–â×&–v‡C¢ ã VÓ½7W'6÷#¢ ö–çFW#½fW'F–6 ÂÖ Æ–vã¢ Ö–FFÆS½FW‡BÞ align: center;Þ÷fW&fÆ÷s¢ f—6–&ÆS² ò¢ &VÖ÷fW2 W‡G& v–GF, –â ”R ¢ÿÞui-button,Þ .ui-button:link,Þui-button:visited,Þui-button:hover,Þui-button:active {ÞFW‡BÞ decoration: none;ØØ* to make room for the icon, a width needs to be set here */Þui-button-icon-only {Þv–GFƒ¢ "ã&VÓ½Ø* button elements seem to need a little more width */Þutton.ui-button-icon-only {Þv–GFƒ¢ "ãFVÓ½Þui-button-icons-only {Þv–GFƒ¢ 2ãFVÓ½Þutton.ui-button-icons-only {Þv–GFƒ¢ 2ãvVÓ½Ø* button text element */Þui-button .ui-button-text {ÞF—7 Æ “¢ &Æö6³½Æ–æRÖ†V–v‡C¢ normal;ØØui-button-text-only .ui-button-text {Þ FF–æs¢ ãFVÒ VÓ½Þui-button-icon-only .ui-button-text,Þui-button-icons-only .ui-button-text {Þ padding: .4em;ÞFW‡BÖ–æFVçC¢ Ó“"""""— ƒ½Þui-button-text-icon-primary .ui-button-text,Þui-button-text-icons .ui-button-text {Þ FF–æs¢ ãFVÒ VÒ ãFVÒ 2.1em;ØØui-button-text-icon-secondary .ui-button-text,Þui-button-text-icons .ui-button-text {Þ FF–æs¢ ãFVÒ "ã VÒ ãFVÒ VÓ½Þui-button-text-icons .ui-button-text {Þ

— FF–ærÖÆVgC¢ "ã VÓ½ FF–ær×&–v‡C¢ "ã VÓ½Ð* no icon
support for input elements, provide padding by default */Ðnput.ui-button {Ð
padding: .4em 1em;ÐÐ* button icon element(s) */Ðui-button-icon-only .ui-icon,Ð
.ui-button-text-icon-primary .ui-icon,Ðui-button-text-icon-secondary .ui-icon,Ð
.ui-button-text-icons .ui-icon,Ðui-button-icons-only .ui-icon {Ð ÷6—F–öã¢
absolute;ÐF÷ ¢ S S½Ö &v–â×F÷ ¢ Ó‡ ƒ½Ðui-button-icon-only .ui-icon {ÐÆVgC¢ S S½
margin-left: -8px;ÐÐui-button-text-icon-primary .ui-button-icon-primary,Ðui-
button-text-icons .ui-button-icon-primary,Ðui-button-icons-only .ui-button-
icon-primary {ÐÆVgC¢ ãVVÓ½Ðui-button-text-icon-secondary .ui-button-icon-
secondary,Ðui-button-text-icons .ui-button-icon-secondary,Ðui-button-icons-
only .ui-button-icon-secondary {Ð&–v‡C¢ ãVVÓ½Ð* button sets */Ðui-buttonset {Ð
margin-right: 7px;ÐÐui-buttonset .ui-button {ÐÖ &v–âÖÆVgC¢ ½Ö &v–â×&–v‡C¢
-.3em;ÐÐ* workarounds */Ð* reset extra padding in Firefox, see h5bp.com/l */Ð
input.ui-button::-moz-focus-inner,Ðutton.ui-button::-moz-focus-inner {Ð&÷&FW#¢
0;Ð FF–æs¢ ½Ðui-datepicker {Ðv–GFƒ¢ vVÓ½ FF–æs¢ ã&VÒ ã&VÒ ½F—7 Æ “¢ æöæS½Ð
.ui-datepicker .ui-datepicker-header {Ð ÷6—F–öã¢ &VÆ F—fS½ FF–æs¢ ã&VÒ ½Ðui-
datepicker .ui-datepicker-prev,Ðui-datepicker .ui-datepicker-next {Ð ÷6—F–öã¢
absolute;ÐF÷ ¢ ' ƒ½v–GFƒ¢ ã†VÓ½†V–v‡C¢ ã†VÓ½Ðui-datepicker .ui-datepicker-
prev-hover,Ðui-datepicker .ui-datepicker-next-hover {ÐF÷ ¢ ƒ½Ðui-
datepicker .ui-datepicker-prev {ÐÆVgC¢ ' ƒ½Ðui-datepicker .ui-datepicker-next
{Ð&–v‡C¢ ' ƒ½Ðui-datepicker .ui-datepicker-prev-hover {ÐÆVgC¢ ƒ½Ðui-
datepicker .ui-datepicker-next-hover {Ð&–v‡C¢ ƒ½Ðui-datepicker .ui-
datepicker-prev span,Ðui-datepicker .ui-datepicker-next span {ÐF—7 Æ “¢ &Æö6³½
position: absolute;ÐÆVgC¢ S S½Ö &v–âÖÆVgC¢ Ó‡ ƒ½F÷ ¢ S S½Ö &v–â×F÷ ¢ Ó‡ ƒ½Ðui-
datepicker .ui-datepicker-title {ÐÖ &v–ã¢ "ã6VÓ½Æ–æRÖ†V–v‡C¢ ã†VÓ½FW‡BÐ
align: center;ÐÐui-datepicker .ui-datepicker-title select {ÐföçB×6—¦S¢ VÓ½
margin: 1px 0;ÐÐui-datepicker select.ui-datepicker-month,Ðui-datepicker
select.ui-datepicker-year {Ðv–GFƒ¢ C’S½Ðui-datepicker table {Ðv–GFƒ¢ S½föçBÐ
size: .9em;Ð&÷&FW"Ö6öÆÆ 6S¢ 6öÆÆ 6S½Ö &v–ã¢ ãFVÓ½Ðui-datepicker th {Ð
padding: .7em .3em;ÐFW‡BÖ Æ–vã¢ 6VçFW#½föçB×vV–v‡C¢ &öÆC½&÷&FW#¢ ½Ðui-
datepicker td {Ð&÷&FW#¢ ½ FF–æs¢ ƒ½Ðui-datepicker td span,Ðui-datepicker
td a {ÐF—7 Æ “¢ &Æö6³½ FF–æs¢ ã&VÓ½FW‡BÖ Æ–vã¢ &–v‡C½FW‡BÖFV6÷& F–öã¢ æöæS½Ð
.ui-datepicker .ui-datepicker-buttonpane {Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ö &v–ã¢ ãvVÒ
0 0 0;Ð FF–æs¢ ã&VÓ½&÷&FW"ÖÆVgC¢ ½&÷&FW"×&–v‡C¢ ½&÷&FW"Ö&÷GFöÓ¢ ½Ðui-
datepicker .ui-datepicker-buttonpane button {ÐfÆö C¢ &–v‡C½
margin: .5em .2em .4em;Ð7W'6÷#¢ ö–çFW#½ FF–æs¢ ã&VÒ ãfVÒ ã6VÒ ãfVÓ½v–GFƒ¢
auto;Ð÷fW&fÆ÷s¢ f—6–&ÆS½Ðui-datepicker .ui-datepicker-buttonpane button.ui-
datepicker-current {ÐfÆö C¢ ÆVgC½Ð* with multiple calendars */Ðui-
datepicker.ui-datepicker-multi {Ðv–GFƒ¢ WFó½Ðui-datepicker-multi .ui-
datepicker-group {ÐfÆö C¢ ÆVgC½Ðui-datepicker-multi .ui-datepicker-group
table {Ðv–GFƒ¢ “RS½Ö &v–ã¢ WFò ãFVÓ½Ðui-datepicker-multi-2 .ui-datepicker-
group {Ðv–GFƒ¢ S S½Ðui-datepicker-multi-3 .ui-datepicker-group {Ðv–GFƒ¢ 32ã2S½Ð
.ui-datepicker-multi-4 .ui-datepicker-group {Ðv–GFƒ¢ #RS½Ðui-datepicker-
multi .ui-datepicker-group-last .ui-datepicker-header,Ðui-datepicker-
multi .ui-datepicker-group-middle .ui-datepicker-header {Ð&÷&FW"ÖÆVgB×v–GFƒ¢ ½
}Ðui-datepicker-multi .ui-datepicker-buttonpane {Ð6ÆV #¢ ÆVgC½Ðui-datepicker-
row-break {Ð6ÆV #¢ &÷Fƒ½v–GFƒ¢ S½föçB×6—¦S¢ ½Ð* RTL support */Ðui-
datepicker-rtl {ÐF—&V7F–öã¢ 'FÃ½Ðui-datepicker-rtl .ui-datepicker-prev {Ð
right: 2px;ÐÆVgC¢ WFó½Ðui-datepicker-rtl .ui-datepicker-next {ÐÆVgC¢ ' ƒ½
right: auto;ÐÐui-datepicker-rtl .ui-datepicker-prev:hover {Ð&–v‡C¢ ƒ½ÆVgC¢
auto;ÐÐui-datepicker-rtl .ui-datepicker-next:hover {ÐÆVgC¢ ƒ½&–v‡C¢ WFó½Ð
.ui-datepicker-rtl .ui-datepicker-buttonpane {Ð6ÆV #¢ &–v‡C½Ðui-datepicker-
rtl .ui-datepicker-buttonpane button {ÐfÆö C¢ ÆVgC½Ðui-datepicker-rtl .ui-
datepicker-buttonpane button.ui-datepicker-current,Ðui-datepicker-rtl .ui-
datepicker-group {ÐfÆö C¢ &–v‡C½Ðui-datepicker-rtl .ui-datepicker-group-
last .ui-datepicker-header,Ðui-datepicker-rtl .ui-datepicker-group-middle .ui-
datepicker-header {Ð&÷&FW"×&–v‡B×v–GFƒ¢ ½&÷&FW"ÖÆVgB×v–GFƒ¢ ƒ½Ðui-dialog {Ð
overflow: hidden;Ð ÷6—F–öã¢ '6öÇWFS½F÷ ¢ ½ÆVgC¢ ½ FF–æs¢ ã&VÓ½÷WFÆ–æS¢ ½Ð
.ui-dialog .ui-dialog-titlebar {Ð FF–æs¢ ãFVÒ VÓ½ ÷6—F–öã¢ &VÆ F—fS½Ðui-
dialog .ui-dialog-title {Ð

–fÆö C¢ ÆVgC½Ö &v–ã¢ ã VÒ ½v†—FR×7 6S¢ æ÷w& ½
width: 90%;Þ÷fW&fÆ÷s¢ †–FFVã½FW‡BÖ÷fW&fÆ÷s¢ VÆÆ– 6—3⅝Þui-dialog .ui-dialog-
titlebar-close {Þ ÷6—F–öã¢ '6öÇWFS½&–v‡C¢ ã6VÓ½F÷ ¢ S S½v–GFƒ¢ # ƒ½Ö &v–ã¢
-10px 0 0 0;Þ FF–æs¢ ƒ½†V–v‡C¢ # ƒ⅝Þui-dialog .ui-dialog-content {Þ
position: relative;Þ&÷&FW#¢ ½ FF–æs¢ ãVVÒ VÓ½& 6¶w&÷VæC¢ æöæS½÷fW&fÆ÷s¢
auto;ÞÞui-dialog .ui-dialog-buttonpane {ÞFW‡BÖ Æ–vã¢ ÆVgC½&÷&FW"×v–GFƒ¢ ,
0 0;Þ& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ö &v–â×F÷ ¢ ãVVÓ½ FF–æs¢ ã6VÒ VÒ ãVVÒ ãFVÓ⅝Þui-
dialog .ui-dialog-buttonpane .ui-dialog-buttonset {ÞfÆö C¢ &–v‡C⅝Þui-
dialog .ui-dialog-buttonpane button {ÞÖ &v–ã¢ ãVVÒ ãFVÒ ãVVÒ ½7W'6÷#¢ ö–çFW#½
}Þui-dialog .ui-resizable-se {Þv–GFƒ¢ ' ƒ½†V–v‡C¢ ' ƒ½&–v‡C¢ ÓW ƒ½&÷GFöÓ¢
-5px;Þ& 6¶w&÷VæB× ÷6—F–öã¢ g , g ƒ⅝Þui-draggable .ui-dialog-titlebar {Þ
cursor: move;ÞÞui-menu {ÞÆ—7B×7G–ÆS¢ æöæS½ FF–æs¢ ' ƒ½Ö &v–ã¢ ½F—7 Æ “¢
block;Þ÷WFÆ–æS¢ æöæS⅝Þui-menu .ui-menu {ÞÖ &v–â×F÷ ¢ Ó7 ƒ½ ÷6—F–öã¢ '6öÇWFS⅝Þ
.ui-menu .ui-menu-item {ÞÖ &v–ã¢ ½ FF–æs¢ ½v–GFƒ¢ S½ò¢ 7W ÷'C¢ ”S Â
see #8844 */ÞÆ—7B×7G–ÆRÖ–Ö vS¢ W&Â†F F ¦–Ö vRð
gifbase64,R0lGODlhAQABAIAAAAAAAP///yH5BAEAAAAALAAAAAABAAEAAAIBRAA7);ÞÞui-
menu .ui-menu-divider {ÞÖ &v–ã¢ W , Ó' , W , Ó' ƒ½†V–v‡C¢ ½föçB×6—¦S¢ ½Æ–æRÐ
height: 0;Þ&÷&FW"×v–GFƒ¢ , ⅝Þui-menu .ui-menu-item a {ÞFW‡BÖFV6÷& F–öã¢
none;ÞF—7 Æ “¢ &Æö6³½ FF–æs¢ ' , ãFVÓ½Æ–æRÖ†V–v‡C¢ ãS½Ö–âÖ†V–v‡C¢ ² ò¢
support: IE7 */ÞföçB×vV–v‡C¢ æ÷&Ö Ã⅝Þui-menu .ui-menu-item a.ui-state-focus,Þ
.ui-menu .ui-menu-item a.ui-state-active {ÞföçB×vV–v‡C¢ æ÷&Ö Ã½Ö &v–ã¢ Ó ƒ⅝Þ
.ui-menu .ui-state-disabled {ÞföçB×vV–v‡C¢ æ÷&Ö Ã½Ö &v–ã¢ ãFVÒ ã&VÓ½Æ–æRÐ
height: 1.5;ÞÞui-menu .ui-state-disabled a {Þ7W'6÷#¢ FVf VÇC⅝Ð* icon support
*/Þui-menu-icons {Þ ÷6—F–öã¢ &VÆ F—fS⅝Þui-menu-icons .ui-menu-item a {Þ
position: relative;Þ FF–ærÖÆVgC¢ &VÓ⅝Ð* left-aligned */Þui-menu .ui-icon {Þ
position: absolute;ÞF÷ ¢ ã&VÓ½ÆVgC¢ ã&VÓ⅝Ð* right-aligned */Þui-menu .ui-menu-
icon {Þ ÷6—F–öã¢ 7F F–3½fÆö C¢ &–v‡C⅝Þui-progressbar {Þ†V–v‡C¢ &VÓ½FW‡BÖ Æ–vã¢
left;Þ÷fW&fÆ÷s¢ †–FFVã⅝Þui-progressbar .ui-progressbar-value {ÞÖ &v–ã¢ Ó ƒ½
height: 100%;ÞÞui-progressbar .ui-progressbar-overlay {Þ& 6¶w&÷VæC¢
url("images/animated-overlay.gif");Þ†V–v‡C¢ S½f–ÇFW#¢ Ç † †÷ 6—G“Ó#R“½
opacity: 0.25;ÞÞui-progressbar-indeterminate .ui-progressbar-value {Þ
background-image: none;ÞÞui-slider {Þ ÷6—F–öã¢ &VÆ F—fS½FW‡BÖ Æ–vã¢ ÆVgC⅝Þui-
slider .ui-slider-handle {Þ ÷6—F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ #½v–GFƒ¢ ã&VÓ½†V–v‡C¢
1.2em;Þ7W'6÷#¢ FVf VÇC⅝Þui-slider .ui-slider-range {Þ ÷6—F–öã¢ '6öÇWFS½¢Þ
index: 1;ÞföçB×6—¦S¢ ãvVÓ½F—7 Æ “¢ &Æö6³½&÷&FW#¢ ½& 6¶w&÷VæB× ÷6—F–öã¢ ⅝Ð
* For IE8 - See #6727 */Þui-slider.ui-state-disabled .ui-slider-handle,Þui-
slider.ui-state-disabled .ui-slider-range {Þf–ÇFW#¢ –æ†W&—C⅝Þui-slider-
horizontal {Þ†V–v‡C¢ ã†VÓ⅝Þui-slider-horizontal .ui-slider-handle {ÞF÷ ¢ Òã6VÓ½
margin-left: -.6em;ÞÞui-slider-horizontal .ui-slider-range {ÞF÷ ¢ ½†V–v‡C¢
100%;ÞÞui-slider-horizontal .ui-slider-range-min {ÞÆVgC¢ ⅝Þui-slider-
horizontal .ui-slider-range-max {Þ&–v‡C¢ ⅝Þui-slider-vertical {Þv–GFƒ¢ ã†VÓ½
height: 100px;ÞÞui-slider-vertical .ui-slider-handle {ÞÆVgC¢ Òã6VÓ½Ö &v–âÐ
left: 0;ÞÖ &v–âÖ&÷GFöÓ¢ ÒãfVÓ⅝Þui-slider-vertical .ui-slider-range {ÞÆVgC¢ ½
width: 100%;ÞÞui-slider-vertical .ui-slider-range-min {Þ&÷GFöÓ¢ ⅝Þui-slider-
vertical .ui-slider-range-max {ÞF÷ ¢ ⅝Þui-spinner {Þ ÷6—F–öã¢ &VÆ F—fS½
display: inline-block;Þ÷fW&fÆ÷s¢ †–FFVã½ FF–æs¢ ½fW'F–6 ÂÖ Æ–vã¢ Ö–FFÆS⅝Þui-
spinner-input {Þ&÷&FW#¢ æöæS½& 6¶w&÷VæC¢ æöæS½6öÆ÷#¢ –æ†W&—C½ FF–æs¢ ½
margin: .2em 0;ÞfW'F–6 ÂÖ Æ–vã¢ Ö–FFÆS½Ö &v–âÖÆVgC¢ ãFVÓ½Ö &v–â×&–v‡C¢ #' ƒ⅝Þ
.ui-spinner-button {Þv–GFƒ¢ g ƒ½†V–v‡C¢ S S½föçB×6—¦S¢ ãVVÓ½ FF–æs¢ ½
margin: 0;ÞFW‡BÖ Æ–vã¢ 6VçFW#½ ÷6—F–öã¢ '6öÇWFS½7W'6÷#¢ FVf VÇC½F—7 Æ “¢
block;Þ÷fW&fÆ÷s¢ †–FFVã½&–v‡C¢ ⅝Ð* more specificity required here to
override default borders */Þui-spinner a.ui-spinner-button {Þ&÷&FW"×F÷ ¢ æöæS½
border-bottom: none;Þ&÷&FW"×&–v‡C¢ æöæS⅝Ð* vertically center icon */Þui-
spinner .ui-icon {Þ ÷6—F–öã¢ '6öÇWFS½Ö &v–â×F÷ ¢ Ó‡ ƒ½F÷ ¢ S S½ÆVgC¢ ⅝Þui-
spinner-up {ÞF÷ ¢ ⅝Þui-spinner-down {Þ&÷GFöÓ¢ ⅝Ð* TR overrides */Þui-
spinner .ui-icon-triangle-1-s {Þò¢ æVVB Fò f—, –6öç2 7 &—FR ¢ý& 6¶w&÷VæBÐ
position: -65px -16px;ÞÞui-tabs {Þ ÷6—F–öã¢ &VÆ F—fS²ò¢ ÷6—F–öã¢ &VÆ F—fR
prevents IE scroll bug (element with position: relative inside container with
overflow: auto appear as "fixed") */Þ FF–æs¢ ã&VÓ⅝Þui-tabs .ui-tabs-nav {Þ
margin: 0;Þ

— FF–æs¢ ã&VÒ ã&VÒ ⅌Đui-tabs .ui-tabs-nav li {ÐÆ—7B×7G–ÆS¢ æöæS½
float: left;Ð ÷6—F–öã¢ &VÆ F—fS½F÷ ¢ ½Ö &v–ã¢ , ã&VÒ ½&÷&FW"Ö&÷GFöÒÐ
width: 0;Ð FF–æs¢ ½v†—FR×7 6S¢ æ÷w& ⅌Đui-tabs .ui-tabs-nav .ui-tabs-
anchor {ÐfÆö C¢ ÆVgC½ FF–æs¢ ãVVÒ VÓ½FW‡BÖFV6÷& F–öã¢ æöæS⅌Đui-tabs .ui-
tabs-nav li.ui-tabs-active {ÐÖ &v–âÖ&÷GFöÓ¢ Ó ƒ½ FF–ærÖ&÷GFöÓ¢ ƒ⅌Đui-
tabs .ui-tabs-nav li.ui-tabs-active .ui-tabs-anchor,Đui-tabs .ui-tabs-nav
li.ui-state-disabled .ui-tabs-anchor,Đui-tabs .ui-tabs-nav li.ui-tabs-
loading .ui-tabs-anchor {Ð7W'6÷#¢ FW‡C⅌Đui-tabs-collapsible .ui-tabs-nav
li.ui-tabs-active .ui-tabs-anchor {Ð7W"6÷#¢ ö–çFW#⅌Đui-tabs .ui-tabs-panel {Ð
display: block;Ð&÷&FW"×v–GFƒ¢ ½ FF–æs¢ VÒ ãFVÓ½& 6¶w&÷VæC¢ æöæS⅌Đui-
tooltip {Ð FF–æs¢ ‡ ƒ½ ÷6—F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ “”“”½Ö ,×v–GFƒ¢ 3 ƒ½Ð
webkit-box-shadow: 0 0 5px #aaa;Ð&÷,×6† F÷s¢ W , 6 ⅌Đody .ui-tooltip {Ð
border-width: 2px;ÐÐ* Component containersÐ----------*/Đ
.ui-widget {ÐföçBÖf Ö–Ç“¢ fW&F æ Ä &– ÂÇ6 ç2×6W&–bò§¶fdFVf VÇGÒ¢ó½föçB×6—¦S¢
1.1em/*{fsDefault}*/;ÐÐui-widget .ui-widget {ÐföçB×6—¦S¢ VÓ⅌Đui-widget input,Đ
.ui-widget select,Đui-widget textarea,Đui-widget button {ÐföçBÖf Ö–Ç“¢
Verdana,Arial,sans-serif/*{ffDefault}*/;ÐföçB×6—¦S¢ VÓ⅌Đui-widget-content {Ð
border: 1px solid #aaaaaa/*{borderColorContent}*/;Ð& 6¶w&÷VæC¢ 6fffffbð
{bgColorContent}/ url(images/ui-bg_flat_75_ffffff_40x100.png)/
{bgImgUrlContent}/ 50%/*{bgContentXPos}*/ 50%/*{bgContentYPos}*/ repeat-x/
{bgContentRepeat}/;Ð6öÆ÷#¢ 3#####"ò§¶f46öçFVçGÒ¢ó⅌Đui-widget-content a {Ð
color: #222222/*{fcContent}*/;ÐÐui-widget-header {Ð&÷&FW#¢ , 6öÆ–B 6 ð
{borderColorHeader}/;Ð& 6¶w&÷VæC¢ 6666662ò§¶&t6öÆ÷$†V FW'Ò¢ò W&Â†–Ö vW2÷V’Đ
bg_highlight-soft_75_cccccc_1x100.png)/*{bgImgUrlHeader}*/ 50%/*{bgHeaderXPos}
/ 50%/{bgHeaderYPos}*/ repeat-x/*{bgHeaderRepeat}*/;Ð6öÆ÷#¢ 3#####"ð
{fcHeader}/;ÐföçB×vV–v‡C¢ &öÆC⅌Đui-widget-header a {Ð6öÆ÷#¢ 3#####"ð
{fcHeader}/;ÐÐ* Interaction statesÐ----------*/Đui-
state-default,Đui-widget-content .ui-state-default,Đui-widget-header .ui-
state-default {Ð&÷&FW#¢ , 6öÆ–B 6C6C6C2ò§¶&÷&FW$6öÆ÷$FVf VÇGÒ¢ó½& 6¶w&÷VæC¢
#e6e6e6/*{bgColorDefault}*/ url(images/ui-bg_glass_75_e6e6e6_1x400.png)/
{bgImgUrlDefault}/ 50%/*{bgDefaultXPos}*/ 50%/*{bgDefaultYPos}*/ repeat-x/
{bgDefaultRepeat}/;ÐföçB×vV–v‡C¢ æ÷&Ö Âò§¶gtFVf VÇGÒ¢ó½6öÆ÷#¢ 3SSSSSRð
{fcDefault}/;ÐÐui-state-default a,Đui-state-default a:link,Đui-state-
default a:visited {Ð6öÆ÷#¢ 3SSSSSRò§¶f4FVf VÇGÒ¢ó½FW‡BÖFV6÷& F–öã¢ æöæS⅌Đui-
state-hover,Đui-widget-content .ui-state-hover,Đui-widget-header .ui-state-
hover,Đui-state-focus,Đui-widget-content .ui-state-focus,Đui-widget-
header .ui-state-focus {Ð&÷&FW#¢ , 6öÆ–B 3“”“”“”’ò§¶&÷&FW$6öÆ÷$†÷fW'Ò¢ó½
background: #dadada/*{bgColorHover}*/ url(images/ui-
bg_glass_75_dadada_1x400.png)/*{bgImgUrlHover}*/ 50%/*{bgHoverXPos}*/ 50%/
{bgHoverYPos}/ repeat-x/*{bgHoverRepeat}*/;ÐföçB×vV–v‡C¢ æ÷&Ö Âò§¶gtFVf VÇGÐ
*/;Ð6öÆ÷#¢ 3# # # ò§¶f4†÷fW'Ò¢ó⅌Đui-state-hover a,Đui-state-hover a:hover,Đui-
state-hover a:link,Đui-state-hover a:visited,Đui-state-focus a,Đui-state-
focus a:hover,Đui-state-focus a:link,Đui-state-focus a:visited {Ð6öÆ÷#¢
#212121/*{fcHover}*/;ÐFW‡BÖFV6÷& F–öã¢ æöæS⅌Đui-state-active,Đui-widget-
content .ui-state-active,Đui-widget-header .ui-state-active {Ð&÷&FW#¢ ,
solid #aaaaaa/*{borderColorActive}*/;Ð& 6¶w&÷VæC¢ 6fffffbò§¶&t6öÆ÷$ 7F—fWÒ¢ò
url(images/ui-bg_glass_65_ffffff_1x400.png)/*{bgImgUrlActive}*/ 50%/
{bgActiveXPos}/ 50%/*{bgActiveYPos}*/ repeat-x/*{bgActiveRepeat}*/;ÐföçBÐ
weight: normal/*{fwDefault}*/;Ð6öÆ÷#¢ 3# # # ò§¶f4 7F—fWÒ¢ó⅌Đui-state-active
a,Đui-state-active a:link,Đui-state-active a:visited {Ð6öÆ÷#¢ 3# # # ð
{fcActive}/;ÐFW‡BÖFV6÷& F–öã¢ æöæS⅌Ð* Interaction CuesÐ
----------*/Đui-state-highlight,Đui-widget-
content .ui-state-highlight,Đui-widget-header .ui-state-highlight {Ð&÷&FW#¢
1px solid #fcefa1/*{borderColorHighlight}*/;Ð& 6¶w&÷VæC¢ 6f&c–VRð
{bgColorHighlight}/ url(images/ui-bg_glass_55_fbf9ee_1x400.png)/
{bgImgUrlHighlight}/ 50%/*{bgHighlightXPos}*/ 50%/*{bgHighlightYPos}*/
repeat-x/*{bgHighlightRepeat}*/;Ð6öÆ÷#¢ 33c3c3bò§¶f4†–v†Æ–v‡GÒ¢ó⅌Đui-state-
highlight a,Đui-widget-content .ui-state-highlight a,Đui-widget-header .ui-
state-highlight a {Ð6öÆ÷#¢ 33c3c3bò§¶f4†–v†Æ–v‡GÒ¢ó⅌Đui-state-error,Đui-
widget-content .ui-state-error,Đ

.ui-widget-header .ui-state-error {Ð&÷&FW#¢ ,
solid #cd0a0a/*{borderColorError}*/;Ð& 6¶w&÷VæC¢ 6fVc V2ò§¶&t6öÆ÷$W'&÷'Ò¢ò
url(images/ui-bg_glass_95_fef1ec_1x400.png)/*{bgImgUrlError}*/ 50%/
{bgErrorXPos}/ 50%/*{bgErrorYPos}*/ repeat-x/*{bgErrorRepeat}*/;Ð6öÆ÷#¢
#cd0a0a/*{fcError}*/;ÐÐui-state-error a,Ðui-widget-content .ui-state-error a,Ð
.ui-widget-header .ui-state-error a {Ð6öÆ÷#¢ 66C ò§¶f4W'&÷'Ò¢ó½Ðui-state-
error-text,Ðui-widget-content .ui-state-error-text,Ðui-widget-header .ui-
state-error-text {Ð6öÆ÷#¢ 66C ò§¶f4W'&÷'Ò¢ó½Ðui-priority-primary,Ðui-
widget-content .ui-priority-primary,Ðui-widget-header .ui-priority-primary {Ð
font-weight: bold;ÐÐui-priority-secondary,Ðui-widget-content .ui-priority-
secondary,Ðui-widget-header .ui-priority-secondary {Ð÷ 6—G“¢ ãs½
filter:Alpha(Opacity=70);ÐföçB×vV–v‡C¢ æ÷&Ö Ã½Ðui-state-disabled,Ðui-widget-
content .ui-state-disabled,Ðui-widget-header .ui-state-disabled {Ð÷ 6—G“¢ ã3S½
filter:Alpha(Opacity=35);Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ðui-state-disabled .ui-icon {Ð
filter:Alpha(Opacity=35); /* For IE8 - See #6059 */ÐÐ* IconsÐ
----------*/Ð* states and images */Ðui-icon {Ðv–GFƒ¢
16px;Ð†V–v‡C¢ g ƒ½Ðui-icon,Ðui-widget-content .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢
url(images/ui-icons_222222_256x240.png)/*{iconsContent}*/;ÐÐui-widget-
header .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ö–6öç5ó#####%ó#Sgƒ#C ç ær’ð
{iconsHeader}/;ÐÐui-state-default .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_888888_256x240.png)/*{iconsDefault}*/;ÐÐui-state-hover .ui-icon,Ðui-
state-focus .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_454545_256x240.png)/*{iconsHover}*/;ÐÐui-state-active .ui-icon {Ð
background-image: url(images/ui-icons_454545_256x240.png)/*{iconsActive}*/;ÐÐ
.ui-state-highlight .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_2e83ff_256x240.png)/*{iconsHighlight}*/;ÐÐui-state-error .ui-icon,Ðui-
state-error-text .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_cd0a0a_256x240.png)/*{iconsError}*/;ÐÐ* positioning */Ðui-icon-blank
{ background-position: 16px 16px; }Ðui-icon-carat-1-n { background-position:
0 0; }Ðui-icon-carat-1-ne { background-position: -16px 0; }Ðui-icon-carat-1-e
{ background-position: -32px 0; }Ðui-icon-carat-1-se { background-position:
-48px 0; }Ðui-icon-carat-1-s { background-position: -64px 0; }Ðui-icon-
carat-1-sw { background-position: -80px 0; }Ðui-icon-carat-1-w { background-
position: -96px 0; }Ðui-icon-carat-1-nw { background-position: -112px 0; }Ðui-
icon-carat-2-n-s { background-position: -128px 0; }Ðui-icon-carat-2-e-w
{ background-position: -144px 0; }Ðui-icon-triangle-1-n { background-
position: 0 -16px; }Ðui-icon-triangle-1-ne { background-position: -16px
-16px; }Ðui-icon-triangle-1-e { background-position: -32px -16px; }Ðui-icon-
triangle-1-se { background-position: -48px -16px; }Ðui-icon-triangle-1-s
{ background-position: -64px -16px; }Ðui-icon-triangle-1-sw { background-
position: -80px -16px; }Ðui-icon-triangle-1-w { background-position: -96px
-16px; }Ðui-icon-triangle-1-nw { background-position: -112px -16px; }Ðui-icon-
triangle-2-n-s { background-position: -128px -16px; }Ðui-icon-triangle-2-e-w
{ background-position: -144px -16px; }Ðui-icon-arrow-1-n { background-
position: 0 -32px; }Ðui-icon-arrow-1-ne { background-position: -16px -32px; }Ð
.ui-icon-arrow-1-e { background-position: -32px -32px; }Ðui-icon-arrow-1-se
{ background-position: -48px -32px; }Ðui-icon-arrow-1-s { background-
position: -64px -32px; }Ðui-icon-arrow-1-sw { background-position: -80px
-32px; }Ðui-icon-arrow-1-w { background-position: -96px -32px; }Ðui-icon-
arrow-1-nw { background-position: -112px -32px; }Ðui-icon-arrow-2-n-s
{ background-position: -128px -32px; }Ðui-icon-arrow-2-ne-sw { background-
position: -144px -32px; }Ðui-icon-arrow-2-e-w { background-position: -160px
-32px; }Ðui-icon-arrow-2-se-nw { background-position: -176px -32px; }Ðui-icon-
arrowstop-1-n { background-position: -192px -32px; }Ðui-icon-arrowstop-1-e
{ background-position: -208px -32px; }Ðui-icon-arrowstop-1-s { background-
position: -224px -32px; }Ðui-icon-arrowstop-1-w { background-position: -240px
-32px; }Ðui-icon-arrowthick-1-n { background-position: 0 -48px; }Ðui-icon-
arrowthick-1-ne { background-position: -16px -48px; }Ðui-icon-arrowthick-1-e
{ background-position: -32px -48px; }Ðui-icon-arrowthick-1-se { background-
position: -48px -48px; }Ð

.ui-icon-arrowthick-1-s { background-position: -64px -48px; }Đui-icon-arrowthick-1-sw { background-position: -80px -48px; }Đui-icon-arrowthick-1-w { background-position: -96px -48px; }Đui-icon-arrowthick-1-nw { background-position: -112px -48px; }Đui-icon-arrowthick-2-n-s { background-position: -128px -48px; }Đui-icon-arrowthick-2-ne-sw { background-position: -144px -48px; }Đui-icon-arrowthick-2-e-w { background-position: -160px -48px; }Đui-icon-arrowthick-2-se-nw { background-position: -176px -48px; }Đui-icon-arrowthickstop-1-n { background-position: -192px -48px; }Đui-icon-arrowthickstop-1-e { background-position: -208px -48px; }Đui-icon-arrowthickstop-1-s { background-position: -224px -48px; }Đui-icon-arrowthickstop-1-w { background-position: -240px -48px; }Đui-icon-arrowreturnthick-1-w { background-position: 0 -64px; }Đui-icon-arrowreturnthick-1-n { background-position: -16px -64px; }Đui-icon-arrowreturnthick-1-e { background-position: -32px -64px; }Đui-icon-arrowreturnthick-1-s { background-position: -48px -64px; }Đui-icon-arrowreturn-1-w { background-position: -64px -64px; }Đui-icon-arrowreturn-1-n { background-position: -80px -64px; }Đui-icon-arrowreturn-1-e { background-position: -96px -64px; }Đui-icon-arrowreturn-1-s { background-position: -112px -64px; }Đui-icon-arrowrefresh-1-w { background-position: -128px -64px; }Đui-icon-arrowrefresh-1-n { background-position: -144px -64px; }Đui-icon-arrowrefresh-1-e { background-position: -160px -64px; }Đui-icon-arrowrefresh-1-s { background-position: -176px -64px; }Đui-icon-arrow-4 { background-position: 0 -80px; }Đui-icon-arrow-4-diag { background-position: -16px -80px; }Đui-icon-extlink { background-position: -32px -80px; }Đui-icon-newwin { background-position: -48px -80px; }Đui-icon-refresh { background-position: -64px -80px; }Đui-icon-shuffle { background-position: -80px -80px; }Đ .ui-icon-transfer-e-w { background-position: -96px -80px; }Đui-icon-transferthick-e-w { background-position: -112px -80px; }Đui-icon-folder-collapsed { background-position: 0 -96px; }Đui-icon-folder-open { background-position: -16px -96px; }Đui-icon-document { background-position: -32px -96px; }Đui-icon-document-b { background-position: -48px -96px; }Đui-icon-note { background-position: -64px -96px; }Đui-icon-mail-closed { background-position: -80px -96px; }Đui-icon-mail-open { background-position: -96px -96px; }Đui-icon-suitcase { background-position: -112px -96px; }Đui-icon-comment { background-position: -128px -96px; }Đui-icon-person { background-position: -144px -96px; }Đui-icon-print { background-position: -160px -96px; }Đ .ui-icon-trash { background-position: -176px -96px; }Đui-icon-locked { background-position: -192px -96px; }Đui-icon-unlocked { background-position: -208px -96px; }Đui-icon-bookmark { background-position: -224px -96px; }Đui-icon-tag { background-position: -240px -96px; }Đui-icon-home { background-position: 0 -112px; }Đui-icon-flag { background-position: -16px -112px; }Đui-icon-calendar { background-position: -32px -112px; }Đui-icon-cart { background-position: -48px -112px; }Đui-icon-pencil { background-position: -64px -112px; }Đui-icon-clock { background-position: -80px -112px; }Đ .ui-icon-disk { background-position: -96px -112px; }Đui-icon-calculator { background-position: -112px -112px; }Đui-icon-zoomin { background-position: -128px -112px; }Đui-icon-zoomout { background-position: -144px -112px; }Đui-icon-search { background-position: -160px -112px; }Đui-icon-wrench { background-position: -176px -112px; }Đui-icon-gear { background-position: -192px -112px; }Đui-icon-heart { background-position: -208px -112px; }Đui-icon-star { background-position: -224px -112px; }Đui-icon-link { background-position: -240px -112px; }Đui-icon-cancel { background-position: 0 -128px; }Đ .ui-icon-plus { background-position: -16px -128px; }Đui-icon-plusthick { background-position: -32px -128px; }Đui-icon-minus { background-position: -48px -128px; }Đui-icon-minusthick { background-position: -64px -128px; }Đui-icon-close { background-position: -80px -128px; }Đui-icon-closethick { background-position: -96px -128px; }Đui-icon-key { background-position: -112px -128px; }Đui-icon-lightbulb { background-position: -128px -128px; }Đui-icon-scissors { background-position: -144px -128px; }Đui-icon-clipboard { background-position: -160px -128px; }Đ

.ui-icon-copy { background-position: -176px -128px; }Đui-icon-contact { background-position: -192px -128px; }Đui-icon-image { background-position: -208px -128px; }Đui-icon-video { background-position: -224px -128px; }Đui-icon-script { background-position: -240px -128px; }Đui-icon-alert { background-position: 0 -144px; }Đui-icon-info { background-position: -16px -144px; }Đui-icon-notice { background-position: -32px -144px; }Đui-icon-help { background-position: -48px -144px; }Đui-icon-check { background-position: -64px -144px; }Đui-icon-bullet { background-position: -80px -144px; }Đui-icon-radio-on { background-position: -96px -144px; }Đui-icon-radio-off { background-position: -112px -144px; }Đui-icon-pin-w { background-position: -128px -144px; }Đui-icon-pin-s { background-position: -144px -144px; }Đui-icon-play { background-position: 0 -160px; }Đui-icon-pause { background-position: -16px -160px; }Đui-icon-seek-next { background-position: -32px -160px; }Đui-icon-seek-prev { background-position: -48px -160px; }Đui-icon-seek-end { background-position: -64px -160px; }Đui-icon-seek-start { background-position: -80px -160px; }Đ* ui-icon-seek-first is deprecated, use ui-icon-seek-start instead */Đui-icon-seek-first { background-position: -80px -160px; }Đui-icon-stop { background-position: -96px -160px; }Đui-icon-eject { background-position: -112px -160px; }Đui-icon-volume-off { background-position: -128px -160px; }Đui-icon-volume-on { background-position: -144px -160px; }Đui-icon-power { background-position: 0 -176px; }Đui-icon-signal-diag { background-position: -16px -176px; }Đui-icon-signal { background-position: -32px -176px; }Đui-icon-battery-0 { background-position: -48px -176px; }Đui-icon-battery-1 { background-position: -64px -176px; }Đui-icon-battery-2 { background-position: -80px -176px; }Đui-icon-battery-3 { background-position: -96px -176px; }Đui-icon-circle-plus { background-position: 0 -192px; }Đui-icon-circle-minus { background-position: -16px -192px; }Đui-icon-circle-close { background-position: -32px -192px; }Đui-icon-circle-triangle-e { background-position: -48px -192px; }Đui-icon-circle-triangle-s { background-position: -64px -192px; }Đui-icon-circle-triangle-w { background-position: -80px -192px; }Đui-icon-circle-triangle-n { background-position: -96px -192px; }Đui-icon-circle-arrow-e { background-position: -112px -192px; }Đui-icon-circle-arrow-s { background-position: -128px -192px; }Đui-icon-circle-arrow-w { background-position: -144px -192px; }Đui-icon-circle-arrow-n { background-position: -160px -192px; }Đui-icon-circle-zoomin { background-position: -176px -192px; }Đui-icon-circle-zoomout { background-position: -192px -192px; }Đui-icon-circle-check { background-position: -208px -192px; }Đui-icon-circlesmall-plus { background-position: 0 -208px; }Đui-icon-circlesmall-minus { background-position: -16px -208px; }Đui-icon-circlesmall-close { background-position: -32px -208px; }Đui-icon-squaresmall-plus { background-position: -48px -208px; }Đui-icon-squaresmall-minus { background-position: -64px -208px; }Đui-icon-squaresmall-close { background-position: -80px -208px; }Đui-icon-grip-dotted-vertical { background-position: 0 -224px; }Đui-icon-grip-dotted-horizontal { background-position: -16px -224px; }Đui-icon-grip-solid-vertical { background-position: -32px -224px; }Đui-icon-grip-solid-horizontal { background-position: -48px -224px; }Đui-icon-gripsmall-diagonal-se { background-position: -64px -224px; }Đui-icon-grip-diagonal-se { background-position: -80px -224px; }Đ* Misc visualsĐ ----------*/Đ* Corner radius */Đui-corner-all,Đui-corner-top,Đui-corner-left,Đui-corner-tl {Đ&÷&FW"×F÷ ÖÆVgB×& F—W3¢ G ,ð *{cornerRadius}*/;ÐĐui-corner-all,Đui-corner-top,Đui-corner-right,Đui-corner-tr {Đ&÷&FW"×F÷ ×&–v‡B×& F—W3¢ G ,ò§¶6÷&æW%& F—W7Ò¢ó½Đui-corner-all,Đui-corner-bottom,Đui-corner-left,Đui-corner-bl {Đ&÷&FW"Ö&÷GFöÒÖÆVgB×& F—W3¢ G ,ð *{cornerRadius}*/;ÐĐui-corner-all,Đui-corner-bottom,Đui-corner-right,Đui-corner-br {Đ&÷&FW"Ö&÷GFöÒ×&–v‡B×& F—W3¢ G ,ò§¶6÷&æW%& F—W7Ò¢ó½Đ* Overlays */Đ .ui-widget-overlay {Đ& 6¶w&÷VæC¢ 6 ò§¶&t6öÆ÷$÷fW&Æ —Ò¢ò W&Â†–Ö vW2÷V’Đ bg_flat_0_aaaaaa_40x100.png)/*{bgImgUrlOverlay}*/ 50%/*{bgOverlayXPos}*/ 50%/*{bgOverlayYPos}*/ repeat-x/*{bgOverlayRepeat}*/;Đ÷ 6—G“¢ ã2ò§¶÷ 6—G”÷fW&Æ —Đ */;Đ

–f–ÇFW#¢ Ç † „÷ 6—G“Ó3 ’ò§¶÷ 6—G”f–ÇFW$÷fW&Æ —Ò¢ó½Ðui-widget-shadow {Ð
margin: -8px/*{offsetTopShadow}*/ 0 0 -8px/*{offsetLeftShadow}*/;Ð FF–æs¢ ‡ ,ð
{thicknessShadow}/;Ð& 6¶w&÷VæC¢ 6 ò§¶&t6öÆ÷%6† F÷wÒ¢ò W&Â†–Ö vW2÷V’Ð
bg_flat_0_aaaaaa_40x100.png)/*{bgImgUrlShadow}*/ 50%/*{bgShadowXPos}*/ 50%/
{bgShadowYPos}/ repeat-x/*{bgShadowRepeat}*/;Ð÷ 6—G“¢ ã2ò§¶÷ 6—G•6† F÷wÒ¢ó½
filter: Alpha(Opacity=30)/*{opacityFilterShadow}*/;Ð&÷&FW"×& F—W3¢ ‡ ,ð
{cornerRadiusShadow}/;ÐÐ

public\assets\css\plugins\jsTree\style.css

```
/* jsTree default theme */Ðjstree-node,Ðjstree-children,Ðjstree-container-ul {Ð
  display: block;Ð margin: 0;Ð padding: 0;Ð list-style-type: none;Ð list-
style-image: none;ÞÐjstree-node {Ð white-space: nowrap;ÞÐjstree-anchor {Ð
display: inline-block;Ð color: black;Ð white-space: nowrap;Ð padding: 0 4px 0
1px;Ð margin: 0;Ð vertical-align: top;ÞÐjstree-anchor:focus {Ð outline: 0;ÞÐ
.jstree-anchor,Ðjstree-anchor:link,Ðjstree-anchor:visited,Ðjstree-
anchor:hover,Ðjstree-anchor:active {Ð text-decoration: none;Ð color: inherit;ÞÐ
.jstree-icon {Ð display: inline-block;Ð text-decoration: none;Ð margin: 0;Ð
padding: 0;Ð vertical-align: top;Ð text-align: center;ÞÐjstree-icon:empty {Ð
display: inline-block;Ð text-decoration: none;Ð margin: 0;Ð padding: 0;Ð
vertical-align: top;Ð text-align: center;ÞÐjstree-ocl {Ð cursor: pointer;ÞÐ
.jstree-leaf > .jstree-ocl {Ð cursor: default;ÞÐjstree .jstree-open > .jstree-
children {Ð display: block;ÞÐjstree .jstree-closed > .jstree-children,Ð
.jstree .jstree-leaf > .jstree-children {Ð display: none;ÞÐjstree-anchor
> .jstree-themeicon {Ð margin-right: 2px;ÞÐjstree-no-icons .jstree-themeicon,Ð
.jstree-anchor > .jstree-themeicon-hidden {Ð display: none;ÞÐjstree-
rtl .jstree-anchor {Ð padding: 0 1px 0 4px;ÞÐjstree-rtl .jstree-anchor
> .jstree-themeicon {Ð margin-left: 2px;Ð margin-right: 0;ÞÐjstree-
rtl .jstree-node {Ð margin-left: 0;ÞÐjstree-rtl .jstree-container-ul
> .jstree-node {Ð margin-right: 0;ÞÐjstree-wholerow-ul {Ð position: relative;Ð
  display: inline-block;Ð min-width: 100%;ÞÐjstree-wholerow-ul .jstree-leaf
> .jstree-ocl {Ð cursor: pointer;ÞÐjstree-wholerow-ul .jstree-anchor,Ðjstree-
wholerow-ul .jstree-icon {Ð position: relative;ÞÐjstree-wholerow-ul .jstree-
wholerow {Ð width: 100%;Ð cursor: pointer;Ð position: absolute;Ð left: 0;Ð -
webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð
user-select: none;ÞÐvakata-context {Ð display: none;ÞÐvakata-context,Ðvakata-
context ul {Ð margin: 0;Ð padding: 2px;Ð position: absolute;Ð background:
#f5f5f5;Ð border: 1px solid #979797;Ð -moz-box-shadow: 5px 5px 4px -4px
#666666;Ð -webkit-box-shadow: 2px 2px 2px #999999;Ð box-shadow: 2px 2px 2px
#999999;ÞÐvakata-context ul {Ð list-style: none;Ð left: 100%;Ð margin-top:
-2.7em;Ð margin-left: -4px;ÞÐvakata-context .vakata-context-right ul {Ð left:
auto;Ð right: 100%;Ð margin-left: auto;Ð margin-right: -4px;ÞÐvakata-context
li {Ð list-style: none;Ð display: inline;ÞÐvakata-context li > a {Ð display:
block;Ð padding: 0 2em 0 2em;Ð text-decoration: none;Ð width: auto;Ð color:
black;Ð white-space: nowrap;Ð line-height: 2.4em;Ð -moz-text-shadow: 1px 1px
0 white;Ð -webkit-text-shadow: 1px 1px 0 white;Ð text-shadow: 1px 1px 0 white;Ð
  -moz-border-radius: 1px;Ð -webkit-border-radius: 1px;Ð border-radius: 1px;ÞÐ
.vakata-context li > a:hover {Ð position: relative;Ð background-color:
#e8eff7;Ð -moz-box-shadow: 0 0 2px #0a6aa1;Ð -webkit-box-shadow: 0 0 2px
#0a6aa1;Ð box-shadow: 0 0 2px #0a6aa1;ÞÐvakata-context li > a.vakata-context-
parent {Ð background-image: url("
yH5BAEAAAEALAAAAAALAAcAAAIORI4JlrqN1oMSnmmZDQUAOw==");Ð background-position:
right center;Ð background-repeat: no-repeat;ÞÐvakata-context li > a:focus {Ð
outline: 0;ÞÐvakata-context .vakata-context-hover > a {Ð position: relative;Ð
background-color: #e8eff7;Ð -moz-box-shadow: 0 0 2px #0a6aa1;Ð -webkit-box-
shadow: 0 0 2px #0a6aa1;Ð box-shadow: 0 0 2px #0a6aa1;ÞÐvakata-
context .vakata-context-separator > a,Ðvakata-context .vakata-context-
separator > a:hover {Ð background: white;Ð border: 0;Ð border-top: 1px solid
#e2e3e3;Ð height: 1px;Ð min-height: 1px;Ð max-height: 1px;Ð padding: 0;Ð
margin: 0 0 0 2.4em;Ð border-left: 1px solid #e0e0e0;Ð -moz-text-shadow: 0 0
0 transparent;Ð -webkit-text-shadow: 0 0 0 transparent;Ð text-shadow: 0 0 0
transparent;Ð -moz-box-shadow: 0 0 0 transparent;Ð -webkit-box-shadow: 0 0 0
transparent;Ð box-shadow: 0 0 0 transparent;Ð -moz-border-radius: 0;Ð -webkit-
border-radius: 0;Ð border-radius: 0;ÞÐvakata-context .vakata-contextmenu-
disabled a,Ðvakata-context .vakata-contextmenu-disabled a:hover {Ð color:
silver;Ð background-color: transparent;Ð border: 0;Ð box-shadow: 0 0 0;ÞÐ
.vakata-context li > a > i {Ð text-decoration: none;Ð display: inline-block;Ð
width: 2.4em;Ð
```

height: 2.4em;Ð background: transparent;Ð margin: 0 0 0 -2em;Ð vertical-align: top;Ð text-align: center;Ð line-height: 2.4em;ÞÐvakata-context li > a > i:empty {Ð width: 2.4em;Ð line-height: 2.4em;ÞÐvakata-context li > a .vakata-contextmenu-sep {Ð display: inline-block;Ð width: 1px;Ð height: 2.4em;Ð background: white;Ð margin: 0 0.5em 0 0;Ð border-left: 1px solid #e2e3e3;ÞÐvakata-context .vakata-contextmenu-shortcut {Ð font-size: 0.8em;Ð color: silver;Ð opacity: 0.5;Ð display: none;ÞÐvakata-context-rtl ul {Ð left: auto;Ð right: 100%;Ð margin-left: auto;Ð margin-right: -4px;ÞÐvakata-context-rtl li > a.vakata-context-parent {Ð background-image: url("");Ð background-position: left center;Ð background-repeat: no-repeat;ÞÐvakata-context-rtl .vakata-context-separator > a {Ð margin: 0 2.4em 0 0;Ð border-left: 0;Ð border-right: 1px solid #e2e3e3;ÞÐvakata-context-rtl .vakata-context-left ul {Ð right: auto;Ð left: 100%;Ð margin-left: -4px;Ð margin-right: auto;ÞÐvakata-context-rtl li > a > i {Ð margin: 0 -2em 0 0;ÞÐvakata-context-rtl li > a .vakata-contextmenu-sep {Ð margin: 0 0 0 0.5em;Ð border-left-color: white;Ð background: #e2e3e3;ÞÐ #jstree-marker {Ð position: absolute;Ð top: 0;Ð left: 0;Ð margin: -5px 0 0 0;Ð padding: 0;Ð border-right: 0;Ð border-top: 5px solid transparent;Ð border-bottom: 5px solid transparent;Ð border-left: 5px solid;Ð width: 0;Ð height: 0;Ð font-size: 0;Ð line-height: 0;ÞÐjstree-dnd {Ð line-height: 16px;Ð margin: 0;Ð padding: 4px;ÞÐjstree-dnd .jstree-icon,Ðjstree-dnd .jstree-copy {Ð display: inline-block;Ð text-decoration: none;Ð margin: 0 2px 0 0;Ð padding: 0;Ð width: 16px;Ð height: 16px;ÞÐjstree-dnd .jstree-ok {Ð background: green;ÞÐ #jstree-dnd .jstree-er {Ð background: red;ÞÐjstree-dnd .jstree-copy {Ð margin: 0 2px 0 2px;ÞÐjstree-default .jstree-node,Ðjstree-default .jstree-icon {Ð background-repeat: no-repeat;Ð background-color: transparent;ÞÐjstree-default .jstree-anchor,Ðjstree-default .jstree-wholerow {Ð transition: background-color 0.15s, box-shadow 0.15s;ÞÐjstree-default .jstree-hovered {Ð background: #e7f4f9;Ð border-radius: 2px;Ð box-shadow: inset 0 0 1px #cccccc;ÞÐ .jstree-default .jstree-clicked {Ð background: #beebff;Ð border-radius: 2px;Ð box-shadow: inset 0 0 1px #999999;ÞÐjstree-default .jstree-no-icons .jstree-anchor > .jstree-themeicon {Ð display: none;ÞÐjstree-default .jstree-disabled {Ð background: transparent;Ð color: #666666;ÞÐjstree-default .jstree-disabled.jstree-hovered {Ð background: transparent;Ð box-shadow: none;ÞÐ .jstree-default .jstree-disabled.jstree-clicked {Ð background: #efefef;ÞÐ .jstree-default .jstree-disabled > .jstree-icon {Ð opacity: 0.8;Ð filter: url("data:image/svg+xml;utf8,<svg xmlns=\'http://www.w3.org/2000/svg\'><filter id=\'jstree-grayscale\'><feColorMatrix type=\'matrix\' values=\'0.3333 0.3333 0.3333 0 0 0.3333 0.3333 0.3333 0 0 0.3333 0.3333 0.3333 0 0 0 0 0 1 0\'/></filter></svg>#jstree-grayscale");Ð /* Firefox 10+ */Ð filter: gray;Ð /* IE6-9 */Ð -webkit-filter: grayscale(100%);Ð /* Chrome 19+ & Safari 6+ */ÞÐjstree-default .jstree-search {Ð font-style: italic;Ð color: #8b0000;Ð font-weight: bold;ÞÐjstree-default .jstree-no-checkboxes .jstree-checkbox {Ð display: none !important;ÞÐjstree-default.jstree-checkbox-no-clicked .jstree-clicked {Ð background: transparent;Ð box-shadow: none;ÞÐ .jstree-default.jstree-checkbox-no-clicked .jstree-clicked.jstree-hovered {Ð background: #e7f4f9;ÞÐjstree-default.jstree-checkbox-no-clicked > .jstree-wholerow-ul .jstree-wholerow-clicked {Ð background: transparent;ÞÐjstree-default.jstree-checkbox-no-clicked > .jstree-wholerow-ul .jstree-wholerow-clicked.jstree-wholerow-hovered {Ð background: #e7f4f9;ÞÐjstree-default > .jstree-striped {Ð background: url("") left top repeat;ÞÐjstree-default > .jstree-wholerow-ul .jstree-hovered,Ðjstree-default > .jstree-wholerow-ul .jstree-clicked {Ð background: transparent;Ð box-shadow: none;Ð border-radius: 0;ÞÐjstree-default .jstree-wholerow {Ð -moz-box-sizing: border-box;Ð -webkit-box-sizing: border-box;Ð box-sizing: border-box;ÞÐjstree-default .jstree-wholerow-hovered {Ð

background: #e7f4f9;ÞÐjstree-
default .jstree-wholerow-clicked {Ð background: #beebff;Ð background: -moz-
linear-gradient(top, #beebff 0%, #a8e4ff 100%);Ð background: -webkit-
gradient(linear, left top, left bottom, color-stop(0%, #beebff), color-
stop(100%, #a8e4ff));Ð background: -webkit-linear-gradient(top, #beebff 0%,
#a8e4ff 100%);Ð background: -o-linear-gradient(top, #beebff 0%, #a8e4ff 100%);Ð
background: -ms-linear-gradient(top, #beebff 0%, #a8e4ff 100%);Ð
background: linear-gradient(to bottom, #beebff 0%, #a8e4ff 100%);Ð /*filter:
progid:DXImageTransform.Microsoft.gradient(startColorstr='@color1',
endColorstr='@color2',GradientType=0);*/ÞÐjstree-default .jstree-node {Ð min-
height: 24px;Ð line-height: 24px;Ð margin-left: 24px;Ð min-width: 24px;ÞÐ
.jstree-default .jstree-anchor {Ð line-height: 24px;Ð height: 24px;ÞÐjstree-
default .jstree-icon {Ð width: 24px;Ð height: 24px;Ð line-height: 24px;ÞÐ
.jstree-default .jstree-icon:empty {Ð width: 24px;Ð height: 24px;Ð line-
height: 24px;ÞÐjstree-default.jstree-rtl .jstree-node {Ð margin-right: 24px;ÞÐ
.jstree-default .jstree-wholerow {Ð height: 24px;ÞÐjstree-default .jstree-
node,Ðjstree-default .jstree-icon {Ð background-image: url("32px.png");ÞÐ
.jstree-default .jstree-node {Ð background-position: -292px -4px;Ð background-
repeat: repeat-y;ÞÐjstree-default .jstree-last {Ð background: transparent;ÞÐ
.jstree-default .jstree-open > .jstree-ocl {Ð background-position: -132px
-4px;ÞÐjstree-default .jstree-closed > .jstree-ocl {Ð background-position:
-100px -4px;ÞÐjstree-default .jstree-leaf > .jstree-ocl {Ð background-
position: -68px -4px;ÞÐjstree-default .jstree-themeicon {Ð background-
position: -260px -4px;ÞÐjstree-default > .jstree-no-dots .jstree-node,Ðjstree-
default > .jstree-no-dots .jstree-leaf > .jstree-ocl {Ð background:
transparent;ÞÐjstree-default > .jstree-no-dots .jstree-open > .jstree-ocl {Ð
background-position: -36px -4px;ÞÐjstree-default > .jstree-no-dots .jstree-
closed > .jstree-ocl {Ð background-position: -4px -4px;ÞÐjstree-
default .jstree-disabled {Ð background: transparent;ÞÐjstree-default .jstree-
disabled.jstree-hovered {Ð background: transparent;ÞÐjstree-default .jstree-
disabled.jstree-clicked {Ð background: #efefef;ÞÐjstree-default .jstree-
checkbox {Ð background-position: -164px -4px;ÞÐjstree-default .jstree-
checkbox:hover {Ð background-position: -164px -36px;ÞÐjstree-default.jstree-
checkbox-selection .jstree-clicked > .jstree-checkbox,Ðjstree-default .jstree-
checked > .jstree-checkbox {Ð background-position: -228px -4px;ÞÐjstree-
default.jstree-checkbox-selection .jstree-clicked > .jstree-checkbox:hover,Ð
.jstree-default .jstree-checked > .jstree-checkbox:hover {Ð background-
position: -228px -36px;ÞÐjstree-default .jstree-anchor > .jstree-undetermined
{Ð background-position: -196px -4px;ÞÐjstree-default .jstree-anchor > .jstree-
undetermined:hover {Ð background-position: -196px -36px;ÞÐjstree-default
> .jstree-striped {Ð background-size: auto 48px;ÞÐjstree-default.jstree-
rtl .jstree-node {Ð background-image: url("
AANSUhEUgAAABgAAAACAQMAAAB49I5GAAAABlBMVEUAAAAdHRvEkCwcAAAAAXRSTlMAQObYZgAAAAx
JREFUCNdjAAMOBgAAGAAJMwQHdQAAAABJRU5ErkJggg==");Ð background-position: 100%
1px;Ð background-repeat: repeat-y;ÞÐjstree-default.jstree-rtl .jstree-last {Ð
background: transparent;ÞÐjstree-default.jstree-rtl .jstree-open > .jstree-
ocl {Ð background-position: -132px -36px;ÞÐjstree-default.jstree-rtl .jstree-
closed > .jstree-ocl {Ð background-position: -100px -36px;ÞÐjstree-
default.jstree-rtl .jstree-leaf > .jstree-ocl {Ð background-position: -68px
-36px;ÞÐjstree-default.jstree-rtl > .jstree-no-dots .jstree-node,Ðjstree-
default.jstree-rtl > .jstree-no-dots .jstree-leaf > .jstree-ocl {Ð
background: transparent;ÞÐjstree-default.jstree-rtl > .jstree-no-dots .jstree-
open > .jstree-ocl {Ð background-position: -36px -36px;ÞÐjstree-
default.jstree-rtl > .jstree-no-dots .jstree-closed > .jstree-ocl {Ð
background-position: -4px -36px;ÞÐjstree-default .jstree-themeicon-custom {Ð
background-color: transparent;Ð background-image: none;Ð background-position:
0 0;ÞÐjstree-default > .jstree-container-ul .jstree-loading > .jstree-ocl {Ð
background: url("throbber.gif") center center no-repeat;ÞÐjstree-
default .jstree-file {Ð background: url("32px.png") -100px -68px no-repeat;ÞÐ
.jstree-default .jstree-folder {Ð

background: url("32px.png") -260px -4px no-
repeat;ÐÐjstree-default > .jstree-container-ul > .jstree-node {Ð margin-left:
0;Ð margin-right: 0;ÐÐjstree-dnd.jstree-default {Ð line-height: 24px;Ð
padding: 0 4px;ÐÐjstree-dnd.jstree-default .jstree-ok,Ðjstree-dnd.jstree-
default .jstree-er {Ð background-image: url("32px.png");Ð background-repeat:
no-repeat;Ð background-color: transparent;ÐÐjstree-dnd.jstree-default i {Ð
background: transparent;Ð width: 24px;Ð height: 24px;Ð line-height: 24px;ÐÐ
#jstree-dnd.jstree-default .jstree-ok {Ð background-position: -4px -68px;ÐÐ
#jstree-dnd.jstree-default .jstree-er {Ð background-position: -36px -68px;ÐÐ
.jstree-default.jstree-rtl .jstree-node {Ð background-image: url("
AAAAAXRSTlMAQObYZgAAAAxJREFUCNdjAAMOBgAAGAAJMwQHdQAAAABJRU5ErkJggg==");ÐÐ
.jstree-default.jstree-rtl .jstree-last {Ð background: transparent;ÐÐjstree-
default-small .jstree-node {Ð min-height: 18px;Ð line-height: 18px;Ð margin-
left: 18px;Ð min-width: 18px;ÐÐjstree-default-small .jstree-anchor {Ð line-
height: 18px;Ð height: 18px;ÐÐjstree-default-small .jstree-icon {Ð width:
18px;Ð height: 18px;Ð line-height: 18px;ÐÐjstree-default-small .jstree-
icon:empty {Ð width: 18px;Ð height: 18px;Ð line-height: 18px;ÐÐjstree-default-
small.jstree-rtl .jstree-node {Ð margin-right: 18px;ÐÐjstree-default-
small .jstree-wholerow {Ð height: 18px;ÐÐjstree-default-small .jstree-node,Ð
.jstree-default-small .jstree-icon {Ð background-image: url("32px.png");ÐÐ
.jstree-default-small .jstree-node {Ð background-position: -295px -7px;Ð
background-repeat: repeat-y;ÐÐjstree-default-small .jstree-last {Ð
background: transparent;ÐÐjstree-default-small .jstree-open > .jstree-ocl {Ð
background-position: -135px -7px;ÐÐjstree-default-small .jstree-closed
> .jstree-ocl {Ð background-position: -103px -7px;ÐÐjstree-default-
small .jstree-leaf > .jstree-ocl {Ð background-position: -71px -7px;ÐÐjstree-
default-small .jstree-themeicon {Ð background-position: -263px -7px;ÐÐjstree-
default-small > .jstree-no-dots .jstree-node,Ðjstree-default-small > .jstree-
no-dots .jstree-leaf > .jstree-ocl {Ð background: transparent;ÐÐjstree-
default-small > .jstree-no-dots .jstree-open > .jstree-ocl {Ð background-
position: -39px -7px;ÐÐjstree-default-small > .jstree-no-dots .jstree-closed
> .jstree-ocl {Ð background-position: -7px -7px;ÐÐjstree-default-
small .jstree-disabled {Ð background: transparent;ÐÐjstree-default-
small .jstree-disabled.jstree-hovered {Ð background: transparent;ÐÐjstree-
default-small .jstree-disabled.jstree-clicked {Ð background: #efefef;ÐÐjstree-
default-small .jstree-checkbox {Ð background-position: -167px -7px;ÐÐjstree-
default-small .jstree-checkbox:hover {Ð background-position: -167px -39px;ÐÐ
.jstree-default-small.jstree-checkbox-selection .jstree-clicked > .jstree-
checkbox,Ðjstree-default-small .jstree-checked > .jstree-checkbox {Ð
background-position: -231px -7px;ÐÐjstree-default-small.jstree-checkbox-
selection .jstree-clicked > .jstree-checkbox:hover,Ðjstree-default-
small .jstree-checked > .jstree-checkbox:hover {Ð background-position: -231px
-39px;ÐÐjstree-default-small .jstree-anchor > .jstree-undetermined {Ð
background-position: -199px -7px;ÐÐjstree-default-small .jstree-anchor
> .jstree-undetermined:hover {Ð background-position: -199px -39px;ÐÐjstree-
default-small > .jstree-striped {Ð background-size: auto 36px;ÐÐjstree-
default-small.jstree-rtl .jstree-node {Ð background-image: url("
AAAXRSTlMAQObYZgAAAAxJREFUCNdjAAMOBgAAGAAJMwQHdQAAAABJRU5ErkJggg==");Ð
background-position: 100% 1px;Ð background-repeat: repeat-y;ÐÐjstree-default-
small.jstree-rtl .jstree-last {Ð background: transparent;ÐÐjstree-default-
small.jstree-rtl .jstree-open > .jstree-ocl {Ð background-position: -135px
-39px;ÐÐjstree-default-small.jstree-rtl .jstree-closed > .jstree-ocl {Ð
background-position: -103px -39px;ÐÐjstree-default-small.jstree-rtl .jstree-
leaf > .jstree-ocl {Ð background-position: -71px -39px;ÐÐjstree-default-
small.jstree-rtl > .jstree-no-dots .jstree-node,Ðjstree-default-small.jstree-
rtl > .jstree-no-dots .jstree-leaf > .jstree-ocl {Ð background: transparent;ÐÐ
.jstree-default-small.jstree-rtl > .jstree-no-dots .jstree-open > .jstree-ocl
{Ð

background-position: -39px -39px;ÞÞjstree-default-small.jstree-rtl
> .jstree-no-dots .jstree-closed > .jstree-ocl {Þ background-position: -7px
-39px;ÞÞjstree-default-small .jstree-themeicon-custom {Þ background-color:
transparent;Þ background-image: none;Þ background-position: 0 0;ÞÞjstree-
default-small > .jstree-container-ul .jstree-loading > .jstree-ocl {Þ
background: url("throbber.gif") center center no-repeat;ÞÞjstree-default-
small .jstree-file {Þ background: url("32px.png") -103px -71px no-repeat;ÞÞ
.jstree-default-small .jstree-folder {Þ background: url("32px.png") -263px
-7px no-repeat;ÞÞjstree-default-small > .jstree-container-ul > .jstree-node {Þ
margin-left: 0;Þ margin-right: 0;ÞÞjstree-dnd.jstree-default-small {Þ line-
height: 18px;Þ padding: 0 4px;ÞÞjstree-dnd.jstree-default-small .jstree-ok,Þ
#jstree-dnd.jstree-default-small .jstree-er {Þ background-image:
url("32px.png");Þ background-repeat: no-repeat;Þ background-color:
transparent;ÞÞjstree-dnd.jstree-default-small i {Þ background: transparent;Þ
width: 18px;Þ height: 18px;Þ line-height: 18px;ÞÞjstree-dnd.jstree-default-
small .jstree-ok {Þ background-position: -7px -71px;ÞÞjstree-dnd.jstree-
default-small .jstree-er {Þ background-position: -39px -71px;ÞÞjstree-default-
small.jstree-rtl .jstree-node {Þ background-image: url("
iVBORw0KGgoAAAANSUhEUgAAABIAAAACAQMAAABv1h6PAAAABlBMVEUAAAAdHRvEkCwcAAAAAXRSTl
MAQObYZgAAAAxJREFUCNdjAAMHBgAAiABBI4gz9AAAAABJRU5ErkJggg==");ÞÞjstree-default-
small.jstree-rtl .jstree-last {Þ background: transparent;ÞÞjstree-default-
large .jstree-node {Þ min-height: 32px;Þ line-height: 32px;Þ margin-left:
32px;Þ min-width: 32px;ÞÞjstree-default-large .jstree-anchor {Þ line-height:
32px;Þ height: 32px;ÞÞjstree-default-large .jstree-icon {Þ width: 32px;Þ
height: 32px;Þ line-height: 32px;ÞÞjstree-default-large .jstree-icon:empty {Þ
width: 32px;Þ height: 32px;Þ line-height: 32px;ÞÞjstree-default-large.jstree-
rtl .jstree-node {Þ margin-right: 32px;ÞÞjstree-default-large .jstree-
wholerow {Þ height: 32px;ÞÞjstree-default-large .jstree-node,Þjstree-default-
large .jstree-icon {Þ background-image: url("32px.png");ÞÞjstree-default-
large .jstree-node {Þ background-position: -288px 0px;Þ background-repeat:
repeat-y;ÞÞjstree-default-large .jstree-last {Þ background: transparent;ÞÞ
.jstree-default-large .jstree-open > .jstree-ocl {Þ background-position:
-128px 0px;ÞÞjstree-default-large .jstree-closed > .jstree-ocl {Þ background-
position: -96px 0px;ÞÞjstree-default-large .jstree-leaf > .jstree-ocl {Þ
background-position: -64px 0px;ÞÞjstree-default-large .jstree-themeicon {Þ
background-position: -256px 0px;ÞÞjstree-default-large > .jstree-no-
dots .jstree-node,Þjstree-default-large > .jstree-no-dots .jstree-leaf
> .jstree-ocl {Þ background: transparent;ÞÞjstree-default-large > .jstree-no-
dots .jstree-open > .jstree-ocl {Þ background-position: -32px 0px;ÞÞjstree-
default-large > .jstree-no-dots .jstree-closed > .jstree-ocl {Þ background-
position: 0px 0px;ÞÞjstree-default-large .jstree-disabled {Þ background:
transparent;ÞÞjstree-default-large .jstree-disabled.jstree-hovered {Þ
background: transparent;ÞÞjstree-default-large .jstree-disabled.jstree-
clicked {Þ background: #efefef;ÞÞjstree-default-large .jstree-checkbox {Þ
background-position: -160px 0px;ÞÞjstree-default-large .jstree-checkbox:hover
{Þ background-position: -160px -32px;ÞÞjstree-default-large.jstree-checkbox-
selection .jstree-clicked > .jstree-checkbox,Þjstree-default-large .jstree-
checked > .jstree-checkbox {Þ background-position: -224px 0px;ÞÞjstree-
default-large.jstree-checkbox-selection .jstree-clicked > .jstree-
checkbox:hover,Þjstree-default-large .jstree-checked > .jstree-checkbox:hover
{Þ background-position: -224px -32px;ÞÞjstree-default-large .jstree-anchor
> .jstree-undetermined {Þ background-position: -192px 0px;ÞÞjstree-default-
large .jstree-anchor > .jstree-undetermined:hover {Þ background-position:
-192px -32px;ÞÞjstree-default-large > .jstree-striped {Þ background-size:
auto 64px;ÞÞjstree-default-large.jstree-rtl .jstree-node {Þ background-image:
url("
MVEUAAAAdHRvEkCwcAAAAAXRSTlMAQObYZgAAAAxJREFUCNdjAAMOBgAAGAAJMwQHdQAAAABJRU5Er
kJggg==");Þ background-position: 100% 1px;Þ background-repeat: repeat-y;ÞÞ
.jstree-default-large.jstree-rtl .jstree-last {Þ background: transparent;ÞÞ
.jstree-default-large.jstree-rtl .jstree-open > .jstree-ocl {Þ

background-position: -128px -32px;ÐÐjstree-default-large.jstree-rtl .jstree-closed > .jstree-ocl {Ð background-position: -96px -32px;ÐÐjstree-default-large.jstree-rtl .jstree-leaf > .jstree-ocl {Ð background-position: -64px -32px;ÐÐjstree-default-large.jstree-rtl > .jstree-no-dots .jstree-node,Ð .jstree-default-large.jstree-rtl > .jstree-no-dots .jstree-leaf > .jstree-ocl {Ð background: transparent;ÐÐjstree-default-large.jstree-rtl > .jstree-no-dots .jstree-open > .jstree-ocl {Ð background-position: -32px -32px;ÐÐjstree-default-large.jstree-rtl > .jstree-no-dots .jstree-closed > .jstree-ocl {Ð background-position: 0px -32px;ÐÐjstree-default-large .jstree-themeicon-custom {Ð background-color: transparent;Ð background-image: none;Ð background-position: 0 0;ÐÐjstree-default-large > .jstree-container-ul .jstree-loading > .jstree-ocl {Ð background: url("throbber.gif") center center no-repeat;ÐÐ .jstree-default-large .jstree-file {Ð background: url("32px.png") -96px -64px no-repeat;ÐÐjstree-default-large .jstree-folder {Ð background: url("32px.png") -256px 0px no-repeat;ÐÐjstree-default-large > .jstree-container-ul > .jstree-node {Ð margin-left: 0;Ð margin-right: 0;ÐÐjstree-dnd.jstree-default-large {Ð line-height: 32px;Ð padding: 0 4px;ÐÐjstree-dnd.jstree-default-large .jstree-ok,Ðjstree-dnd.jstree-default-large .jstree-er {Ð background-image: url("32px.png");Ð background-repeat: no-repeat;Ð background-color: transparent;ÐÐjstree-dnd.jstree-default-large i {Ð background: transparent;Ð width: 32px;Ð height: 32px;Ð line-height: 32px;ÐÐ #jstree-dnd.jstree-default-large .jstree-ok {Ð background-position: 0px -64px;Ð }Ðjstree-dnd.jstree-default-large .jstree-er {Ð background-position: -32px -64px;ÐÐjstree-default-large.jstree-rtl .jstree-node {Ð background-image: url("");ÐÐjstree-default-large.jstree-rtl .jstree-last {Ð background: transparent;ÐÐ@media (max-width: 768px) {Ð #jstree-dnd.jstree-dnd-responsive {Ð line-height: 40px;Ð font-weight: bold;Ð font-size: 1.1em;Ð text-shadow: 1px 1px white;Ð }Ð #jstree-dnd.jstree-dnd-responsive > i {Ð background: transparent;Ð width: 40px;Ð height: 40px;Ð }Ð #jstree-dnd.jstree-dnd-responsive > .jstree-ok {Ð background-image: url("40px.png");Ð background-position: 0 -200px;Ð background-size: 120px 240px;Ð }Ð #jstree-dnd.jstree-dnd-responsive > .jstree-er {Ð background-image: url("40px.png");Ð background-position: -40px -200px;Ð background-size: 120px 240px;Ð }Ð #jstree-marker.jstree-dnd-responsive {Ð border-left-width: 10px;Ð border-top-width: 10px;Ð border-bottom-width: 10px;Ð margin-top: -10px;Ð }ÐÐ@media (max-width: 768px) {Ð .jstree-default-responsive {Ð /*Ð ’æ§7G&VRÖ÷ Vâ â æ§7G&VRÖö6ÂÍæ§7G&VRÖ6Æ÷6VB â æ§7G&VRÖö6Â ² &÷&FW"×& F—W3£# ƒ² background-color:white; }Ð¢ý }Ð .jstree-default-responsive .jstree-icon {Ð background-image: url("40px.png");Ð }Ð .jstree-default-responsive .jstree-node,Ð .jstree-default-responsive .jstree-leaf > .jstree-ocl {Ð background: transparent;Ð }Ð .jstree-default-responsive .jstree-node {Ð min-height: 40px;Ð line-height: 40px;Ð margin-left: 40px;Ð min-width: 40px;Ð white-space: nowrap;Ð }Ð .jstree-default-responsive .jstree-anchor {Ð line-height: 40px;Ð height: 40px;Ð }Ð .jstree-default-responsive .jstree-icon,Ð .jstree-default-responsive .jstree-icon:empty {Ð width: 40px;Ð height: 40px;Ð line-height: 40px;Ð }Ð .jstree-default-responsive > .jstree-container-ul > .jstree-node {Ð margin-left: 0;Ð }Ð .jstree-default-responsive.jstree-rtl .jstree-node {Ð margin-left: 0;Ð margin-right: 40px;Ð }Ð .jstree-default-responsive.jstree-rtl .jstree-container-ul > .jstree-node {Ð margin-right: 0;Ð }Ð .jstree-default-responsive .jstree-ocl,Ð .jstree-default-responsive .jstree-themeicon,Ð .jstree-default-responsive .jstree-checkbox {Ð background-size: 120px 240px;Ð }Ð .jstree-default-responsive .jstree-leaf > .jstree-ocl {Ð background: transparent;Ð }Ð .jstree-default-responsive .jstree-open > .jstree-ocl {Ð background-position: 0 0px !important;Ð }Ð .jstree-default-responsive .jstree-closed > .jstree-ocl {Ð background-position: 0 -40px !important;Ð }Ð .jstree-default-responsive.jstree-rtl .jstree-closed > .jstree-ocl {Ð

background-position: -40px 0px !important;Ð }Ð .jstree-default-responsive .jstree-themeicon {Ð background-position: -40px -40px;Ð }Ð .jstree-default-responsive .jstree-checkbox,Ð .jstree-default-responsive .jstree-checkbox:hover {Ð background-position: -40px -80px;Ð }Ð .jstree-default-responsive.jstree-checkbox-selection .jstree-clicked > .jstree-checkbox,Ð .jstree-default-responsive.jstree-checkbox-selection .jstree-clicked > .jstree-checkbox:hover,Ð .jstree-default-responsive .jstree-checked > .jstree-checkbox,Ð .jstree-default-responsive .jstree-checked > .jstree-checkbox:hover {Ð background-position: 0 -80px;Ð }Ð .jstree-default-responsive .jstree-anchor > .jstree-undetermined,Ð .jstree-default-responsive .jstree-anchor > .jstree-undetermined:hover {Ð background-position: 0 -120px;Ð }Ð .jstree-default-responsive .jstree-anchor {Ð font-weight: bold;Ð font-size: 1.1em;Ð text-shadow: 1px 1px white;Ð }Ð .jstree-default-responsive > .jstree-striped {Ð background: transparent;Ð }Ð .jstree-default-responsive .jstree-wholerow {Ð border-top: 1px solid rgba(255, 255, 255, 0.7);Ð border-bottom: 1px solid rgba(64, 64, 64, 0.2);Ð background: #ebebeb;Ð height: 40px;Ð }Ð .jstree-default-responsive .jstree-wholerow-hovered {Ð background: #e7f4f9;Ð }Ð .jstree-default-responsive .jstree-wholerow-clicked {Ð background: #beebff;Ð }Ð .jstree-default-responsive .jstree-children .jstree-last > .jstree-wholerow {Ð box-shadow: inset 0 -6px 3px -5px #666666;Ð }Ð .jstree-default-responsive .jstree-children .jstree-open > .jstree-wholerow {Ð box-shadow: inset 0 6px 3px -5px #666666;Ð border-top: 0;Ð }Ð .jstree-default-responsive .jstree-children .jstree-open + .jstree-open {Ð box-shadow: none;Ð }Ð .jstree-default-responsive .jstree-node,Ð .jstree-default-responsive .jstree-icon,Ð .jstree-default-responsive .jstree-node > .jstree-ocl,Ð .jstree-default-responsive .jstree-themeicon,Ð .jstree-default-responsive .jstree-checkbox {Ð background-image: url("40px.png");Ð background-size: 120px 240px;Ð }Ð .jstree-default-responsive .jstree-node {Ð background-position: -80px 0;Ð background-repeat: repeat-y;Ð }Ð .jstree-default-responsive .jstree-last {Ð background: transparent;Ð }Ð .jstree-default-responsive .jstree-leaf > .jstree-ocl {Ð background-position: -40px -120px;Ð }Ð .jstree-default-responsive .jstree-last > .jstree-ocl {Ð background-position: -40px -160px;Ð }Ð .jstree-default-responsive .jstree-themeicon-custom {Ð background-color: transparent;Ð background-image: none;Ð background-position: 0 0;Ð }Ð .jstree-default-responsive .jstree-file {Ð background: url("40px.png") 0 -160px no-repeat;Ð background-size: 120px 240px;Ð }Ð .jstree-default-responsive .jstree-folder {Ð background: url("40px.png") -40px -40px no-repeat;Ð background-size: 120px 240px;Ð }Ð .jstree-default-responsive > .jstree-container-ul > .jstree-node {Ð margin-left: 0;Ð margin-right: 0;Ð }Ð }Ð

public\assets\css\plugins\morris\morris-0.4.3.min.css

```
.morris-hover{position:absolute;z-index:1000;}.morris-hover.morris-default-
style{border-radius:10px;padding:6px;color:#666;background:rgba(255, 255,
255, 0.8);border:solid 2px rgba(230, 230, 230, 0.8);font-family:sans-
serif;font-size:12px;text-align:center;}.morris-hover.morris-default-
style .morris-hover-row-label{font-weight:bold;margin:0.25em 0;}Ðmorris-
hover.morris-default-style .morris-hover-point{white-
space:nowrap;margin:0.1em 0;}
```

public\assets\css\plugins\nouslider\jquery.nouislider.css

Ð* Functional styling;Ð* These styles are required for noUiSlider to function.Ð
 * You don't need to change these rules to apply your design.Ð*/ÐnoUi-target,Ð
.noUi-target * {Ðwebkit-touch-callout: none;Ðwebkit-user-select: none;Ðms-
touch-action: none;Ðms-user-select: none;Ðmoz-user-select: none;Ðmoz-box-
sizing: border-box;Ð&÷,×6—¦–æs¢ &÷&FW"Ö&÷ƒ½ÐnoUi-base {Ðv–GFƒ¢ S½†V–v‡C¢
100%;Ð ÷6—F–öã¢ &VÆ F—fS½ÐnoUi-origin {Ð ÷6—F–öã¢ '6öÇWFS½&–v‡C¢ ½F÷ ¢ ½
left: 0;Ð&÷GFöÓ¢ ½ÐnoUi-handle {Ð ÷6—F–öã¢ &VÆ F—fS½¢Ö–æFWƒ¢ ½ÐnoUi-
stacking .noUi-handle {Ð* This class is applied to the lower origin whenÐ
its values is > 50%. */Ð¢Ö–æFWƒ¢ ½ÐnoUi-stacking + .noUi-origin {Ð* Fix
stacking order in IE7, which incorrectlyÐ creates a new context for the
origins. */Ð§¢Ö–æFWƒ¢ Ó ½ÐnoUi-state-tap .noUi-origin {Ðwebkit-transition:
left 0.3s, top 0.3s;ÐG& ç6—F–öã¢ ÆVgB ã72Â F÷ ã73½ÐnoUi-state-drag * {Ð
cursor: inherit !important;ÐÐ* Slider size and handle placement;Ð*/ÐnoUi-
horizontal {Ð†V–v‡C¢ ‡ ƒ½ÐnoUi-horizontal .noUi-handle {Ðv–GFƒ¢ 3G ƒ½†V–v‡C¢
28px;ÐÆVgC¢ Ó w ƒ½F÷ ¢ Óg ƒ½ÐnoUi-horizontal.noUi-extended {Ð FF–æs¢ W ƒ½Ð
.noUi-horizontal.noUi-extended .noUi-origin {Ð&–v‡C¢ Ó W ƒ½ÐnoUi-vertical {Ð
width: 18px;ÐÐnoUi-vertical .noUi-handle {Ðv–GFƒ¢ #‡ ƒ½†V–v‡C¢ 3G ƒ½ÆVgC¢ Óg ƒ½
top: -17px;ÐÐnoUi-vertical.noUi-extended {Ð FF–æs¢ W , ½ÐnoUi-
vertical.noUi-extended .noUi-origin {Ð&÷GFöÓ¢ Ó W ƒ½Ð* Styling;Ð*/ÐnoUi-
background {Ð& 6¶w&÷VæC¢ 4d d d ½&÷,×6† F÷s¢ –ç6WB , , 6c c c ½ÐnoUi-
connect {Ð& 6¶w&÷VæC¢ 34d#„ c½&÷,×6† F÷s¢ –ç6WB 7 , &v& ƒS ÃS ÃS Ã ãCR“½
webkit-transition: background 450ms;ÐG& ç6—F–öã¢ & 6¶w&÷VæB CS ×3½ÐnoUi-
origin {Ð&÷&FW"×& F—W3¢ ' ƒ½ÐnoUi-target {Ð&÷&FW"×& F—W3¢ G ƒ½&÷&FW#¢ ,
solid #D3D3D3;Ð&÷,×6† F÷s¢ –ç6WB , , 4c c c Â 7 , g , ÓW , 4$$#½ÐnoUi-
target.noUi-connect {Ð&÷,×6† F÷s¢ –ç6WB 7 , &v& ƒS ÃS ÃS Ã ãCR’Â 7 , g ,
-5px #BBB;ÐÐ* Handles and cursors;Ð*/ÐnoUi-dragable {Ð7W'6÷#¢ r×&W6—¦S½ÐnoUi-
vertical .noUi-dragable {Ð7W'6÷#¢ â×&W6—¦S½ÐnoUi-handle {Ð&÷&FW#¢ , 6öÆ–B
#D9D9D9;Ð&÷&FW"×& F—W3¢ 7 ƒ½& 6¶w&÷VæC¢ 4ddc½7W'6÷#¢ FVf VÇC½&÷,×6† F÷s¢ –ç6WB
0 0 1px #FFF,Ð™inset 0 1px 7px #EBEBEB,™Ð 3px 6px -3px #BBBÐ;ÐnoUi-active {Ð&÷,Ð
shadow: inset 0 0 1px #FFF,Ð™inset 0 1px 7px #DDD,™Ð 3px 6px -3px #BBBÐ;ÐÐ*
Handle stripes;Ð*/ÐnoUi-handle:before,ÐnoUi-handle:after {Ð6öçFVçC¢ "#½
display: block;Ð ÷6—F–öã¢ '6öÇWFS½†V–v‡C¢ G ƒ½v–GFƒ¢ ƒ½& 6¶w&÷VæC¢ 4S„StSc½
left: 14px;ÐF÷ ¢ g ƒ½ÐnoUi-handle:after {ÐÆVgC¢ w ƒ½ÐnoUi-vertical .noUi-
handle:before,ÐnoUi-vertical .noUi-handle:after {Ðv–GFƒ¢ G ƒ½†V–v‡C¢ ƒ½
left: 6px;ÐF÷ ¢ G ƒ½ÐnoUi-vertical .noUi-handle:after {ÐF÷ ¢ w ƒ½Ð*
Disabled state;Ð*/Ð[disabled].noUi-connect,Ð[disabled] .noUi-connect {Ð
background: #B8B8B8;ÐÐ[disabled] .noUi-handle {Ð7W'6÷#¢ æ÷BÖ ÆÆ÷vVC½Ð

public\assets\css\plugins\slick\slick-theme.css

@charset 'UTF-8';Ð/* Slider */Ðslick-loading .slick-listÐÐ background: #fff
url('ajax-loader.gif') center center no-repeat;ÐÐ/* Icons */Ð@font-faceÐÐ
font-family: 'slick';Ð font-weight: normal;Ð font-style: normal;Ð src:
url('fonts/slick.eot');Ð src: url('fonts/slick.eot?#iefix')
format('embedded-opentype'), url('fonts/slick.woff') format('woff'),
url('fonts/slick.ttf') format('truetype'), url('fonts/slick.svg#slick')
format('svg');ÐÐ/* Arrows */Ðslick-prev,Ðslick-nextÐÐ font-size: 0;Ð line-
height: 0;Ð position: absolute;Ð top: 50%;Ð display: block;Ð width:
20px;Ð height: 20px;Ð margin-top: -10px;Ð padding: 0;Ð cursor:
pointer;Ð color: transparent;Ð border: none;Ð outline: none;Ð
background: transparent;ÐÐslick-prev:hover,Ðslick-prev:focus,Ðslick-
next:hover,Ðslick-next:focusÐÐ color: transparent;Ð outline: none;Ð
background: transparent;ÐÐslick-prev:hover:before,Ðslick-prev:focus:before,Ð
.slick-next:hover:before,Ðslick-next:focus:beforeÐÐ opacity: 1;ÐÐslick-
prev.slick-disabled:before,Ðslick-next.slick-disabled:beforeÐÐ opacity: .25;Ð
}Ðslick-prev:before,Ðslick-next:beforeÐÐ font-family: 'slick';Ð font-
size: 20px;Ð line-height: 1;Ð opacity: .75;Ð color: white;Ð -webkit-
font-smoothing: antialiased;Ð -moz-osx-font-smoothing: grayscale;ÐÐslick-
prevÐÐ left: -25px;ÐÐ[dir='rtl'] .slick-prevÐÐ right: -25px;Ð left: auto;Ð
}Ðslick-prev:beforeÐÐ content: '!•}ÐÐ[dir='rtl'] .slick-prev:beforeÐÐ
content: '!’}ÐÐslick-nextÐÐ right: -25px;ÐÐ[dir='rtl'] .slick-nextÐÐ right:
auto;Ð left: -25px;ÐÐslick-next:beforeÐÐ content: '!’}ÐÐ[dir='rtl'] .slick-
next:beforeÐÐ content: '!•}ÐÐ/* Dots */Ðslick-sliderÐÐ margin-bottom: 30px;ÐÐ
.slick-dotsÐÐ position: absolute;Ð bottom: -45px;Ð display: block;Ð
width: 100%;Ð padding: 0;Ð list-style: none;Ð text-align: center;ÐÐ
.slick-dots liÐÐ position: relative;Ð display: inline-block;Ð width:
20px;Ð height: 20px;Ð margin: 0 5px;Ð padding: 0;Ð cursor: pointer;ÐÐ
.slick-dots li buttonÐÐ font-size: 0;Ð line-height: 0;Ð display: block;Ð
width: 20px;Ð height: 20px;Ð padding: 5px;Ð cursor: pointer;Ð
color: transparent;Ð border: 0;Ð outline: none;Ð background:
transparent;ÐÐslick-dots li button:hover,Ðslick-dots li button:focusÐÐ
outline: none;ÐÐslick-dots li button:hover:before,Ðslick-dots li
button:focus:beforeÐÐ opacity: 1;ÐÐslick-dots li button:beforeÐÐ font-
family: 'slick';Ð font-size: 6px;Ð line-height: 20px;Ð position:
absolute;Ð top: 0;Ð left: 0;Ð width: 20px;Ð height: 20px;Ð content:
'•';Ð text-align: center;Ð opacity: .25;Ð color: black;Ð -webkit-font-
smoothing: antialiased;Ð -moz-osx-font-smoothing: grayscale;ÐÐslick-dots
li.slick-active button:beforeÐÐ opacity: .75;Ð color: black;ÐÐ

public\assets\css\plugins\slick\slick.css

```
/* Slider */Ðslick-sliderÐÐ   position: relative;Ð   display: block;Ð   -moz-
box-sizing: border-box;Ð        box-sizing: border-box;Ð   -webkit-user-
select: none;Ð      -moz-user-select: none;Ð       -ms-user-select: none;Ð
            user-select: none;Ð   -webkit-touch-callout: none;Ð   -khtml-user-
select: none;Ð   -ms-touch-action: pan-y;Ð       touch-action: pan-y;Ð   -
webkit-tap-highlight-color: transparent;ÐÐslick-listÐÐ   position: relative;Ð
    display: block;Ð   overflow: hidden;Ð   margin: 0;Ð   padding: 0;ÐÐslick-
list:focusÐÐ   outline: none;ÐÐslick-list.draggingÐÐ   cursor: pointer;Ð
cursor: hand;ÐÐslick-slider .slick-track,Ðslick-slider .slick-listÐÐ   -
webkit-transform: translate3d(0, 0, 0);Ð      -moz-transform: translate3d(0,
0, 0);Ð       -ms-transform: translate3d(0, 0, 0);Ð        -o-transform:
translate3d(0, 0, 0);Ð           transform: translate3d(0, 0, 0);ÐÐslick-trackÐ
{Ð   position: relative;Ð   top: 0;Ð   left: 0;Ð   display: block;ÐÐslick-
track:before,Ðslick-track:afterÐÐ   display: table;Ð   content: '';ÐÐslick-
track:afterÐÐ   clear: both;ÐÐslick-loading .slick-trackÐÐ   visibility:
hidden;ÐÐslick-slideÐÐ   display: none;Ð   float: left;Ð   height: 100%;Ð
min-height: 1px;ÐÐ[dir='rtl'] .slick-slideÐÐ   float: right;ÐÐslick-slide imgÐÐ
    display: block;ÐÐslick-slide.slick-loading imgÐÐ   display: none;ÐÐslick-
slide.dragging imgÐÐ   pointer-events: none;ÐÐslick-initialized .slick-slideÐÐ
    display: block;ÐÐslick-loading .slick-slideÐÐ   visibility: hidden;ÐÐ
.slick-vertical .slick-slideÐÐ   display: block;Ð   height: auto;Ð   border:
1px solid transparent;ÐÐslick-arrow.slick-hidden {Ð   display: none;Ð
```

public\assets\css\plugins\social-buttons\social-buttons.css

@import url(//netdna.bootstrapcdn.com/font-awesome/4.0.3/css/font-awesome.min.css);Ð*Ð* Social Buttons for BootstrapÐ*Ð* Copyright 2013 Panayiotis LipiridisÐ* Licensed under the MIT LicenseÐ*Ð* https://github.com/lipis/bootstrap-socialÐ*/Ðbtn-social{position:relative;padding-left:44px;text-align:left;white-space:nowrap;overflow:hidden;text-overflow:ellipsis}.btn-social :first-child{position:absolute;left:0;top:0;bottom:0;width:32px;line-height:34px;font-size:1.6em;text-align:center;border-right:1px solid rgba(0,0,0,0.2)}Ðbtn-social.btn-lg{padding-left:61px}.btn-social.btn-lg :first-child{line-height:45px;width:45px;font-size:1.8em}Ðbtn-social.btn-sm{padding-left:38px}.btn-social.btn-sm :first-child{line-height:28px;width:28px;font-size:1.4em}Ðbtn-social.btn-xs{padding-left:30px}.btn-social.btn-xs :first-child{line-height:20px;width:20px;font-size:1.2em}Ðbtn-social-icon{position:relative;padding-left:44px;text-align:left;white-space:nowrap;overflow:hidden;text-overflow:ellipsis;height:34px;width:34px;padding-left:0;padding-right:0}.btn-social-icon :first-child{position:absolute;left:0;top:0;bottom:0;width:32px;line-height:34px;font-size:1.6em;text-align:center;border-right:1px solid rgba(0,0,0,0.2)}Ðbtn-social-icon.btn-lg{padding-left:61px}.btn-social-icon.btn-lg :first-child{line-height:45px;width:45px;font-size:1.8em}Ðbtn-social-icon.btn-sm{padding-left:38px}.btn-social-icon.btn-sm :first-child{line-height:28px;width:28px;font-size:1.4em}Ðbtn-social-icon.btn-xs{padding-left:30px}.btn-social-icon.btn-xs :first-child{line-height:20px;width:20px;font-size:1.2em}Ðbtn-social-icon :first-child{border:none;text-align:center;width:100% !important}Ðbtn-social-icon.btn-lg{height:45px;width:45px;padding-left:0;padding-right:0}Ðbtn-social-icon.btn-sm{height:30px;width:30px;padding-left:0;padding-right:0}Ðbtn-social-icon.btn-xs{height:22px;width:22px;padding-left:0;padding-right:0}Ðbtn-bitbucket{color:#fff;background-color:#205081;border-color:rgba(0,0,0,0.2)}.btn-bitbucket:hover,.btn-bitbucket:focus,.btn-bitbucket:active,.btn-bitbucket.active,.open .dropdown-toggle.btn-bitbucket{color:#fff;background-color:#183c60;border-color:rgba(0,0,0,0.2)}Ð .btn-bitbucket:active,.btn-bitbucket.active,.open .dropdown-toggle.btn-bitbucket{background-image:none}Ðbtn-bitbucket.disabled,.btn-bitbucket[disabled],fieldset[disabled] .btn-bitbucket,.btn-bitbucket.disabled:hover,.btn-bitbucket[disabled]:hover,fieldset[disabled] .btn-bitbucket:hover,.btn-bitbucket.disabled:focus,.btn-bitbucket[disabled]:focus,fieldset[disabled] .btn-bitbucket:focus,.btn-bitbucket.disabled:active,.btn-bitbucket[disabled]:active,fieldset[disabled] .btn-bitbucket:active,.btn-bitbucket.disabled.active,.btn-bitbucket[disabled].active,fieldset[disabled] .btn-bitbucket.active{background-color:#205081;border-color:rgba(0,0,0,0.2)}Ðbtn-dropbox{color:#fff;background-color:#1087dd;border-color:rgba(0,0,0,0.2)}.btn-dropbox:hover,.btn-dropbox:focus,.btn-dropbox:active,.btn-dropbox.active,.open .dropdown-toggle.btn-dropbox{color:#fff;background-color:#0d70b7;border-color:rgba(0,0,0,0.2)}Ðbtn-dropbox:active,.btn-dropbox.active,.open .dropdown-toggle.btn-dropbox{background-image:none}Ðbtn-dropbox.disabled,.btn-dropbox[disabled],fieldset[disabled] .btn-dropbox,.btn-dropbox.disabled:hover,.btn-dropbox[disabled]:hover,fieldset[disabled] .btn-dropbox:hover,.btn-dropbox.disabled:focus,.btn-dropbox[disabled]:focus,fieldset[disabled] .btn-dropbox:focus,.btn-dropbox.disabled:active,.btn-dropbox[disabled]:active,fieldset[disabled] .btn-dropbox:active,.btn-dropbox.disabled.active,.btn-dropbox[disabled].active,fieldset[disabled] .btn-dropbox.active{background-color:#1087dd;border-color:rgba(0,0,0,0.2)}Ðbtn-facebook{color:#fff;background-color:#3b5998;border-color:rgba(0,0,0,0.2)}.btn-facebook:hover,.btn-facebook:focus,.btn-

facebook:active,.btn-facebook.active,.open .dropdown-toggle.btn-
facebook{color:#fff;background-color:#30487b;border-color:rgba(0,0,0,0.2)}Ð
.btn-facebook:active,.btn-facebook.active,.open .dropdown-toggle.btn-
facebook{background-image:none}Ðbtn-facebook.disabled,.btn-
facebook[disabled],fieldset[disabled] .btn-facebook,.btn-
facebook.disabled:hover,.btn-facebook[disabled]:hover,fieldset[disabled] .btn-
facebook:hover,.btn-facebook.disabled:focus,.btn-
facebook[disabled]:focus,fieldset[disabled] .btn-facebook:focus,.btn-
facebook.disabled:active,.btn-
facebook[disabled]:active,fieldset[disabled] .btn-facebook:active,.btn-
facebook.disabled.active,.btn-
facebook[disabled].active,fieldset[disabled] .btn-facebook.active{background-
color:#3b5998;border-color:rgba(0,0,0,0.2)}Ðbtn-flickr{color:#fff;background-
color:#ff0084;border-color:rgba(0,0,0,0.2)}.btn-flickr:hover,.btn-
flickr:focus,.btn-flickr:active,.btn-flickr.active,.open .dropdown-toggle.btn-
flickr{color:#fff;background-color:#d6006f;border-color:rgba(0,0,0,0.2)}Ðbtn-
flickr:active,.btn-flickr.active,.open .dropdown-toggle.btn-flickr{background-
image:none}Ðbtn-flickr.disabled,.btn-flickr[disabled],fieldset[disabled] .btn-
flickr,.btn-flickr.disabled:hover,.btn-
flickr[disabled]:hover,fieldset[disabled] .btn-flickr:hover,.btn-
flickr.disabled:focus,.btn-flickr[disabled]:focus,fieldset[disabled] .btn-
flickr:focus,.btn-flickr.disabled:active,.btn-
flickr[disabled]:active,fieldset[disabled] .btn-flickr:active,.btn-
flickr.disabled.active,.btn-flickr[disabled].active,fieldset[disabled] .btn-
flickr.active{background-color:#ff0084;border-color:rgba(0,0,0,0.2)}Ðbtn-
github{color:#fff;background-color:#444;border-color:rgba(0,0,0,0.2)}.btn-
github:hover,.btn-github:focus,.btn-github:active,.btn-
github.active,.open .dropdown-toggle.btn-github{color:#fff;background-
color:#303030;border-color:rgba(0,0,0,0.2)}Ðbtn-github:active,.btn-
github.active,.open .dropdown-toggle.btn-github{background-image:none}Ðbtn-
github.disabled,.btn-github[disabled],fieldset[disabled] .btn-github,.btn-
github.disabled:hover,.btn-github[disabled]:hover,fieldset[disabled] .btn-
github:hover,.btn-github.disabled:focus,.btn-
github[disabled]:focus,fieldset[disabled] .btn-github:focus,.btn-
github.disabled:active,.btn-github[disabled]:active,fieldset[disabled] .btn-
github:active,.btn-github.disabled.active,.btn-
github[disabled].active,fieldset[disabled] .btn-github.active{background-
color:#444;border-color:rgba(0,0,0,0.2)}Ðbtn-google-
plus{color:#fff;background-color:#dd4b39;border-color:rgba(0,0,0,0.2)}.btn-
google-plus:hover,.btn-google-plus:focus,.btn-google-plus:active,.btn-google-
plus.active,.open .dropdown-toggle.btn-google-plus{color:#fff;background-
color:#ca3523;border-color:rgba(0,0,0,0.2)}Ðbtn-google-plus:active,.btn-
google-plus.active,.open .dropdown-toggle.btn-google-plus{background-
image:none}Ðbtn-google-plus.disabled,.btn-google-
plus[disabled],fieldset[disabled] .btn-google-plus,.btn-google-
plus.disabled:hover,.btn-google-plus[disabled]:hover,fieldset[disabled] .btn-
google-plus:hover,.btn-google-plus.disabled:focus,.btn-google-
plus[disabled]:focus,fieldset[disabled] .btn-google-plus:focus,.btn-google-
plus.disabled:active,.btn-google-
plus[disabled]:active,fieldset[disabled] .btn-google-plus:active,.btn-google-
plus.disabled.active,.btn-google-
plus[disabled].active,fieldset[disabled] .btn-google-plus.active{background-
color:#dd4b39;border-color:rgba(0,0,0,0.2)}Ðbtn-
instagram{color:#fff;background-color:#517fa4;border-
color:rgba(0,0,0,0.2)}.btn-instagram:hover,.btn-instagram:focus,.btn-
instagram:active,.btn-instagram.active,.open .dropdown-toggle.btn-
instagram{color:#fff;background-color:#446a89;border-color:rgba(0,0,0,0.2)}Ð
.btn-instagram:active,.btn-instagram.active,.open .dropdown-toggle.btn-
instagram{background-image:none}Ðbtn-instagram.disabled,.btn-
instagram[disabled],fieldset[disabled] .btn-instagram,.btn-
instagram.disabled:hover,.btn-

instagram[disabled]:hover,fieldset[disabled] .btn-instagram:hover,.btn-
instagram.disabled:focus,.btn-
instagram[disabled]:focus,fieldset[disabled] .btn-instagram:focus,.btn-
instagram.disabled:active,.btn-
instagram[disabled]:active,fieldset[disabled] .btn-instagram:active,.btn-
instagram.disabled.active,.btn-
instagram[disabled].active,fieldset[disabled] .btn-
instagram.active{background-color:#517fa4;border-color:rgba(0,0,0,0.2)}Ðbtn-
linkedin{color:#fff;background-color:#007bb6;border-
color:rgba(0,0,0,0.2)}.btn-linkedin:hover,.btn-linkedin:focus,.btn-
linkedin:active,.btn-linkedin.active,.open .dropdown-toggle.btn-
linkedin{color:#fff;background-color:#005f8d;border-color:rgba(0,0,0,0.2)}Ð
.btn-linkedin:active,.btn-linkedin.active,.open .dropdown-toggle.btn-
linkedin{background-image:none}Ðbtn-linkedin.disabled,.btn-
linkedin[disabled],fieldset[disabled] .btn-linkedin,.btn-
linkedin.disabled:hover,.btn-linkedin[disabled]:hover,fieldset[disabled] .btn-
linkedin:hover,.btn-linkedin.disabled:focus,.btn-
linkedin[disabled]:focus,fieldset[disabled] .btn-linkedin:focus,.btn-
linkedin.disabled:active,.btn-
linkedin[disabled]:active,fieldset[disabled] .btn-linkedin:active,.btn-
linkedin.disabled.active,.btn-
linkedin[disabled].active,fieldset[disabled] .btn-linkedin.active{background-
color:#007bb6;border-color:rgba(0,0,0,0.2)}Ðbtn-
pinterest{color:#fff;background-color:#cb2027;border-
color:rgba(0,0,0,0.2)}.btn-pinterest:hover,.btn-pinterest:focus,.btn-
pinterest:active,.btn-pinterest.active,.open .dropdown-toggle.btn-
pinterest{color:#fff;background-color:#a81a20;border-color:rgba(0,0,0,0.2)}Ð
.btn-pinterest:active,.btn-pinterest.active,.open .dropdown-toggle.btn-
pinterest{background-image:none}Ðbtn-pinterest.disabled,.btn-
pinterest[disabled],fieldset[disabled] .btn-pinterest,.btn-
pinterest.disabled:hover,.btn-
pinterest[disabled]:hover,fieldset[disabled] .btn-pinterest:hover,.btn-
pinterest.disabled:focus,.btn-
pinterest[disabled]:focus,fieldset[disabled] .btn-pinterest:focus,.btn-
pinterest.disabled:active,.btn-
pinterest[disabled]:active,fieldset[disabled] .btn-pinterest:active,.btn-
pinterest.disabled.active,.btn-
pinterest[disabled].active,fieldset[disabled] .btn-
pinterest.active{background-color:#cb2027;border-color:rgba(0,0,0,0.2)}Ðbtn-
tumblr{color:#fff;background-color:#2c4762;border-color:rgba(0,0,0,0.2)}.btn-
tumblr:hover,.btn-tumblr:focus,.btn-tumblr:active,.btn-
tumblr.active,.open .dropdown-toggle.btn-tumblr{color:#fff;background-
color:#1f3346;border-color:rgba(0,0,0,0.2)}Ðbtn-tumblr:active,.btn-
tumblr.active,.open .dropdown-toggle.btn-tumblr{background-image:none}Ðbtn-
tumblr.disabled,.btn-tumblr[disabled],fieldset[disabled] .btn-tumblr,.btn-
tumblr.disabled:hover,.btn-tumblr[disabled]:hover,fieldset[disabled] .btn-
tumblr:hover,.btn-tumblr.disabled:focus,.btn-
tumblr[disabled]:focus,fieldset[disabled] .btn-tumblr:focus,.btn-
tumblr.disabled:active,.btn-tumblr[disabled]:active,fieldset[disabled] .btn-
tumblr:active,.btn-tumblr.disabled.active,.btn-
tumblr[disabled].active,fieldset[disabled] .btn-tumblr.active{background-
color:#2c4762;border-color:rgba(0,0,0,0.2)}Ðbtn-twitter{color:#fff;background-
color:#2ba9e1;border-color:rgba(0,0,0,0.2)}.btn-twitter:hover,.btn-
twitter:focus,.btn-twitter:active,.btn-twitter.active,.open .dropdown-
toggle.btn-twitter{color:#fff;background-color:#1c92c7;border-
color:rgba(0,0,0,0.2)}Ðbtn-twitter:active,.btn-twitter.active,.open .dropdown-
toggle.btn-twitter{background-image:none}Ðbtn-twitter.disabled,.btn-
twitter[disabled],fieldset[disabled] .btn-twitter,.btn-
twitter.disabled:hover,.btn-twitter[disabled]:hover,fieldset[disabled] .btn-
twitter:hover,.btn-twitter.disabled:focus,.btn-
twitter[disabled]:focus,fieldset[disabled] .btn-twitter:focus,.btn-

twitter.disabled:active,.btn-twitter[disabled]:active,fieldset[disabled] .btn-twitter:active,.btn-twitter.disabled.active,.btn-twitter[disabled].active,fieldset[disabled] .btn-twitter.active{background-color:#2ba9e1;border-color:rgba(0,0,0,0.2)}Ðbtn-vk{color:#fff;background-color:#587ea3;border-color:rgba(0,0,0,0.2)}.btn-vk:hover,.btn-vk:focus,.btn-vk:active,.btn-vk.active,.open .dropdown-toggle.btn-vk{color:#fff;background-color:#4a6a89;border-color:rgba(0,0,0,0.2)}Ðbtn-vk:active,.btn-vk.active,.open .dropdown-toggle.btn-vk{background-image:none}Ðbtn-vk.disabled,.btn-vk[disabled],fieldset[disabled] .btn-vk,.btn-vk.disabled:hover,.btn-vk[disabled]:hover,fieldset[disabled] .btn-vk:hover,.btn-vk.disabled:focus,.btn-vk[disabled]:focus,fieldset[disabled] .btn-vk:focus,.btn-vk.disabled:active,.btn-vk[disabled]:active,fieldset[disabled] .btn-vk:active,.btn-vk.disabled.active,.btn-vk[disabled].active,fieldset[disabled] .btn-vk.active{background-color:#587ea3;border-color:rgba(0,0,0,0.2)}Ð* Ð* Only for this example - not needed for the buttonsÐ* ---------- */Ðbtn-social-icon {margin-bottom: 4px;}Ðsocial-class .social-hex{font-family:Monaco,Menlo,Consolas,"Courier New",monospace;font-size:10px;opacity:.3;float:right}Ðsocial-class li{margin-bottom:4px}.social-class li:hover .social-hex{opacity:1}Ðsocial-class li:hover code{background-color:#e8e8ee}Ðsocial-class code{cursor:default}

public\assets\css\plugins\steps\jquery.steps.css

/*Ð Commonð/Ðwizard,Ðtabcontrolþð display: block;Ð width: 100%;Ð
overflow: hidden;þðwizard a,Ðtabcontrol aþð outline: 0;þðwizard ul,Ð
.tabcontrol ulþð list-style: none !important;Ð padding: 0;Ð margin: 0;þð
.wizard ul > li,Ðtabcontrol ul > liþð display: block;Ð padding: 0;þð*
Accessibility */Ðwizard > .steps .current-info,Ðtabcontrol > .steps .current-
infoþð position: absolute;Ð left: -999em;þðwizard > .content > .title,Ð
.tabcontrol > .content > .titleþð position: absolute;Ð left: -999em;þð*Ð
    Wizardð/Ðwizard > .stepsþð position: relative;Ð display: block;Ð
width: 100%;þðwizard.vertical > .stepsþð display: inline;Ð float: left;Ð
    width: 30%;þðwizard > .steps > ul > liþð width: 25%;þðwizard > .steps >
ul > li,Ðwizard > .actions > ul > liþð float: left;þðwizard.vertical
> .steps > ul > liþð float: none;Ð width: 100%;þðwizard > .steps a,Ð
.wizard > .steps a:hover,Ðwizard > .steps a:activeþð display: block;Ð
width: auto;Ð margin: 0 0.5em 0.5em;Ð padding: 8px;Ð text-decoration:
none;Ð -webkit-border-radius: 5px;Ð -moz-border-radius: 5px;Ð border-
radius: 5px;þðwizard > .steps .disabled a,Ðwizard > .steps .disabled a:hover,Ð
.wizard > .steps .disabled a:activeþð background: #eee;Ð color: #aaa;Ð
cursor: default;þðwizard > .steps .current a,Ðwizard > .steps .current
a:hover,Ðwizard > .steps .current a:activeþð background: #1AB394;Ð color:
#fff;Ð cursor: default;þðwizard > .steps .done a,Ðwizard > .steps .done
a:hover,Ðwizard > .steps .done a:activeþð background: #6fd1bd;Ð color:
#fff;þðwizard > .steps .error a,Ðwizard > .steps .error a:hover,Ðwizard
> .steps .error a:activeþð background: #ED5565 ;Ð color: #fff;þðwizard
> .contentþð background: #eee;Ð display: block;Ð margin: 5px 5px 10px
5px;Ð min-height: 120px;Ð overflow: hidden;Ð position: relative;Ð
width: auto;Ð -webkit-border-radius: 5px;Ð -moz-border-radius: 5px;Ð
border-radius: 5px;þðwizard-big.wizard > .content {Ð min-height: 320px;þð
.wizard.vertical > .contentþð display: inline;Ð float: left;Ð margin: 0
2.5% 0.5em 2.5%;Ð width: 65%;þðwizard > .content > .bodyþð float: left;Ð
    position: absolute;Ð width: 95%;Ð height: 95%;Ð padding: 2.5%;þð
.wizard > .content > .body ulþð list-style: disc !important;þðwizard
> .content > .body ul > liþð display: list-item;þðwizard > .content > .body
> iframeþð border: 0 none;Ð width: 100%;Ð height: 100%;þðwizard
> .content > .body inputþð display: block;Ð border: 1px solid #ccc;þð
.wizard > .content > .body input[type="checkbox"]þð display: inline-block;þð
.wizard > .content > .body input.errorþð background: rgb(251, 227, 228);Ð
border: 1px solid #fbc2c4;Ð color: #8a1f11;þðwizard > .content > .body labelÐ
{Ð display: inline-block;Ð margin-bottom: 0.5em;þðwizard > .content
> .body label.errorþð color: #8a1f11;Ð display: inline-block;Ð margin-
left: 1.5em;þðwizard > .actionsþð position: relative;Ð display: block;Ð
text-align: right;Ð width: 100%;þðwizard.vertical > .actionsþð display:
inline;Ð float: right;Ð margin: 0 2.5%;Ð width: 95%;þðwizard > .actions
> ulþð display: inline-block;Ð text-align: right;þðwizard > .actions > ul
> liþð margin: 0 0.5em;þðwizard.vertical > .actions > ul > liþð margin: 0
0 0 1em;þðwizard > .actions a,Ðwizard > .actions a:hover,Ðwizard > .actions
a:activeþð background: #1AB394;Ð color: #fff;Ð display: block;Ð
padding: 0.5em 1em;Ð text-decoration: none;Ð -webkit-border-radius: 5px;Ð
    -moz-border-radius: 5px;Ð border-radius: 5px;þðwizard
> .actions .disabled a,Ðwizard > .actions .disabled a:hover,Ðwizard
> .actions .disabled a:activeþð background: #eee;Ð color: #aaa;þðwizard
> .loadingþðÐwizard > .loading .spinnerþðÐ*Ð Tabcontrolð/Ðtabcontrol
> .stepsþð position: relative;Ð display: block;Ð width: 100%;þð
.tabcontrol > .steps > ulþð position: relative;Ð margin: 6px 0 0 0;Ð
top: 1px;Ð z-index: 1;þðtabcontrol > .steps > ul > liþð float: left;Ð
margin: 5px 2px 0 0;Ð padding: 1px;Ð -webkit-border-top-left-radius: 5px;Ð
    -webkit-border-top-right-radius: 5px;Ð -moz-border-radius-topleft: 5px;Ð
    -moz-border-radius-topright: 5px;Ð border-top-left-radius: 5px;Ð
border-top-right-radius: 5px;þðtabcontrol > .steps > ul > li:hoverþð
background: #edecec;Ð

border: 1px solid #bbb;Ð padding: 0;ÞÞtabcontrol > .steps > ul > li.currentÐÐ background: #fff;Ð border: 1px solid #bbb;Ð border-bottom: 0 none;Ð padding: 0 0 1px 0;Ð margin-top: 0;ÞÞ.tabcontrol > .steps > ul > li > aÐÐ color: #5f5f5f;Ð display: inline-block;Ð border: 0 none;Ð margin: 0;Ð padding: 10px 30px;Ð text-decoration: none;ÞÞtabcontrol > .steps > ul > li > a:hoverÐÐ text-decoration: none;ÞÞtabcontrol > .steps > ul > li.current > aÐÐ padding: 15px 30px 10px 30px;ÞÞtabcontrol > .contentÐÐ position: relative;Ð display: inline-block;Ð width: 100%;Ð height: 35em;Ð overflow: hidden;Ð border-top: 1px solid #bbb;Ð padding-top: 20px;ÞÞtabcontrol > .content > .bodyÐÐ float: left;Ð position: absolute;Ð width: 95%;Ð height: 95%;Ð padding: 2.5%;ÞÞtabcontrol > .content > .body ulÐÐ list-style: disc !important;ÞÞtabcontrol > .content > .body ul > liÐÐ display: list-item;Þ

public\assets\css\plugins\summernote\summernote-bs3.css

.note-editor {Ð /*! normalize.css v2.1.3 | MIT License | git.io/normalize */ÞÐ .note-editor article,Ðnote-editor aside,Ðnote-editor details,Ðnote-editor figcaption,Ðnote-editor figure,Ðnote-editor footer,Ðnote-editor header,Ðnote-editor hgroup,Ðnote-editor main,Ðnote-editor nav,Ðnote-editor section,Ðnote-editor summary {Ð display: block;ÞÐnote-editor audio,Ðnote-editor canvas,Ð .note-editor video {Ð display: inline-block;ÞÐnote-editor audio:not([controls]) {Ð display: none;Ð height: 0;ÞÐnote-editor [hidden],Ð .note-editor template {Ð display: none;ÞÐnote-editor html {Ð font-family: sans-serif;Ð -ms-text-size-adjust: 100%;Ð -webkit-text-size-adjust: 100%;ÞÐ .note-editor body {Ð margin: 0;ÞÐnote-editor a {Ð background: transparent;ÞÐ .note-editor a:focus {Ð outline: thin dotted;ÞÐnote-editor a:active,Ðnote-editor a:hover {Ð outline: 0;ÞÐnote-editor h1 {Ð font-size: 2em;Ð margin: 0.67em 0;ÞÐnote-editor abbr[title] {Ð border-bottom: 1px dotted;ÞÐnote-editor b,Ðnote-editor strong {Ð font-weight: bold;ÞÐnote-editor dfn {Ð font-style: italic;ÞÐnote-editor hr {Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;Ð height: 0;ÞÐnote-editor mark {Ð background: #ff0;Ð color: #000;ÞÐnote-editor code,Ðnote-editor kbd,Ðnote-editor pre,Ðnote-editor samp {Ð font-family: monospace, serif;Ð font-size: 1em;ÞÐnote-editor pre {Ð white-space: pre-wrap;ÞÐnote-editor q {Ð quotes: "\201C" "\201D" "\2018" "\2019";ÞÐnote-editor small {Ð font-size: 80%;ÞÐnote-editor sub,Ðnote-editor sup {Ð font-size: 75%;Ð line-height: 0;Ð position: relative;Ð vertical-align: baseline;ÞÐ .note-editor sup {Ð top: -0.5em;ÞÐnote-editor sub {Ð bottom: -0.25em;ÞÐnote-editor img {Ð border: 0;ÞÐnote-editor svg:not(:root) {Ð overflow: hidden;ÞÐ .note-editor figure {Ð margin: 0;ÞÐnote-editor fieldset {Ð border: 1px solid #c0c0c0;Ð margin: 0 2px;Ð padding: 0.35em 0.625em 0.75em;ÞÐnote-editor legend {Ð border: 0;Ð padding: 0;ÞÐnote-editor button,Ðnote-editor input,Ðnote-editor select,Ðnote-editor textarea {Ð font-family: inherit;Ð font-size: 100%;Ð margin: 0;ÞÐnote-editor button,Ðnote-editor input {Ð line-height: normal;ÞÐ .note-editor button,Ðnote-editor select {Ð text-transform: none;ÞÐnote-editor button,Ðnote-editor html input[type="button"],Ðnote-editor input[type="reset"],Ðnote-editor input[type="submit"] {Ð -webkit-appearance: button;Ð cursor: pointer;ÞÐnote-editor button[disabled],Ðnote-editor html input[disabled] {Ð cursor: default;ÞÐnote-editor input[type="checkbox"],Ðnote-editor input[type="radio"] {Ð box-sizing: border-box;Ð padding: 0;ÞÐnote-editor input[type="search"] {Ð -webkit-appearance: textfield;Ð -moz-box-sizing: content-box;Ð -webkit-box-sizing: content-box;Ð box-sizing: content-box;ÞÐnote-editor input[type="search"]::-webkit-search-cancel-button,Ðnote-editor input[type="search"]::-webkit-search-decoration {Ð -webkit-appearance: none;ÞÐnote-editor button::-moz-focus-inner,Ðnote-editor input::-moz-focus-inner {Ð border: 0;Ð padding: 0;ÞÐnote-editor textarea {Ð overflow: auto;Ð vertical-align: top;ÞÐnote-editor table {Ð border-collapse: collapse;Ð border-spacing: 0;Þ@media print {Ð .note-editor * {Ð text-shadow: none !important;Ð color: #000 !important;Ð background: transparent !important;Ð box-shadow: none !important;Ð }Ð .note-editor a,Ð .note-editor a:visited {Ð text-decoration: underline;Ð }Ð .note-editor a[href]:after {Ð content: " (" attr(href) ")";Ð }Ð .note-editor abbr[title]:after {Ð content: " (" attr(title) ")";Ð }Ð .note-editor .ir a:after,Ð .note-editor a[href^="javascript:"]:after,Ð .note-editor a[href^="#"]:after {Ð content: "";Ð }Ð .note-editor pre,Ð .note-editor blockquote {Ð border: 1px solid #999;Ð page-break-inside: avoid;Ð }Ð .note-editor thead {Ð display: table-header-group;Ð }Ð .note-editor tr,Ð .note-editor img {Ð page-break-inside: avoid;Ð }Ð .note-editor img {Ð max-width: 100% !important;Ð }Ð @page {Ð margin: 2cm .5cm;Ð }Ð .note-editor p,Ð .note-editor h2,Ð .note-editor h3 {Ð orphans: 3;Ð widows: 3;Ð }Ð .note-editor h2,Ð .note-editor h3 {Ð page-break-after: avoid;Ð }Ð .note-editor .navbar {Ð display: none;Ð }Ð .note-editor .table td,Ð .note-editor .table th {Ð background-color: #fff !important;Ð }Ð .note-editor .btn > .caret,Ð .note-editor .dropup > .btn > .caret {Ð border-top-color: #000 !important;Ð }Ð .note-editor .label {Ð border: 1px solid #000;Ð

}Ð .note-editor .table {Ð border-collapse: collapse !important;Ð }Ð .note-editor .table-bordered th,Ð .note-editor .table-bordered td {Ð border: 1px solid #ddd !important;Ð }ÐÐnote-editor *,Ðnote-editor *:before,Ðnote-editor *:after {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÐÐnote-editor html {Ð font-size: 62.5%;Ð -webkit-tap-highlight-color: rgba(0, 0, 0, 0);ÐÐnote-editor body {Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 14px;Ð line-height: 1.428571429;Ð color: #333333;Ð background-color: #ffffff;ÐÐnote-editor input,Ðnote-editor button,Ðnote-editor select,Ðnote-editor textarea {Ð font-family: inherit;Ð font-size: inherit;Ð line-height: inherit;ÐÐnote-editor a {Ð color: #428bca;Ð text-decoration: none;ÐÐnote-editor a:hover,Ðnote-editor a:focus {Ð color: #2a6496;Ð text-decoration: underline;ÐÐnote-editor a:focus {Ð outline: thin dotted #333;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐ .note-editor img {Ð vertical-align: middle;ÐÐnote-editor .img-responsive {Ð display: block;Ð max-width: 100%;Ð height: auto;ÐÐnote-editor .img-rounded {Ð border-radius: 6px;ÐÐnote-editor .img-thumbnail {Ð padding: 4px;Ð line-height: 1.428571429;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-radius: 4px;Ð -webkit-transition: all 0.2s ease-in-out;Ð transition: all 0.2s ease-in-out;Ð display: inline-block;Ð max-width: 100%;Ð height: auto;Ð }Ðnote-editor .img-circle {Ð border-radius: 50%;ÐÐnote-editor hr {Ð margin-top: 20px;Ð margin-bottom: 20px;Ð border: 0;Ð border-top: 1px solid #eeeeee;ÐÐ .note-editor .sr-only {Ð position: absolute;Ð width: 1px;Ð height: 1px;Ð margin: -1px;Ð padding: 0;Ð overflow: hidden;Ð clip: rect(0, 0, 0, 0);Ð border: 0;ÐÐnote-editor p {Ð margin: 0 0 10px;ÐÐnote-editor .lead {Ð margin-bottom: 20px;Ð font-size: 16px;Ð font-weight: 200;Ð line-height: 1.4;ÐÐ@media (min-width: 768px) {Ð .note-editor .lead {Ð font-size: 21px;Ð }ÐÐnote-editor small,Ðnote-editor .small {Ð font-size: 85%;ÐÐnote-editor cite {Ð font-style: normal;ÐÐnote-editor .text-muted {Ð color: #999999;ÐÐnote-editor .text-primary {Ð color: #428bca;ÐÐnote-editor .text-primary:hover {Ð color: #3071a9;Ð }Ðnote-editor .text-warning {Ð color: #c09853;ÐÐnote-editor .text-warning:hover {Ð color: #a47e3c;ÐÐnote-editor .text-danger {Ð color: #b94a48;ÐÐ .note-editor .text-danger:hover {Ð color: #953b39;ÐÐnote-editor .text-success {Ð color: #468847;ÐÐnote-editor .text-success:hover {Ð color: #356635;ÐÐnote-editor .text-info {Ð color: #3a87ad;ÐÐnote-editor .text-info:hover {Ð color: #2d6987;ÐÐnote-editor .text-left {Ð text-align: left;ÐÐnote-editor .text-right {Ð text-align: right;ÐÐnote-editor .text-center {Ð text-align: center;ÐÐ .note-editor h1,Ðnote-editor h2,Ðnote-editor h3,Ðnote-editor h4,Ðnote-editor h5,Ðnote-editor h6,Ðnote-editor .h1,Ðnote-editor .h2,Ðnote-editor .h3,Ðnote-editor .h4,Ðnote-editor .h5,Ðnote-editor .h6 {Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-weight: 500;Ð line-height: 1.1;Ð color: inherit;ÐÐnote-editor h1 small,Ðnote-editor h2 small,Ðnote-editor h3 small,Ðnote-editor h4 small,Ðnote-editor h5 small,Ðnote-editor h6 small,Ðnote-editor .h1 small,Ðnote-editor .h2 small,Ðnote-editor .h3 small,Ðnote-editor .h4 small,Ðnote-editor .h5 small,Ðnote-editor .h6 small,Ðnote-editor h1 .small,Ðnote-editor h2 .small,Ðnote-editor h3 .small,Ðnote-editor h4 .small,Ðnote-editor h5 .small,Ðnote-editor h6 .small,Ðnote-editor .h1 .small,Ðnote-editor .h2 .small,Ðnote-editor .h3 .small,Ðnote-editor .h4 .small,Ðnote-editor .h5 .small,Ðnote-editor .h6 .small {Ð font-weight: normal;Ð line-height: 1;Ð color: #999999;ÐÐnote-editor h1,Ðnote-editor h2,Ðnote-editor h3 {Ð margin-top: 20px;Ð margin-bottom: 10px;ÐÐnote-editor h1 small,Ðnote-editor h2 small,Ðnote-editor h3 small,Ðnote-editor h1 .small,Ðnote-editor h2 .small,Ðnote-editor h3 .small {Ð font-size: 65%;ÐÐ .note-editor h4,Ðnote-editor h5,Ðnote-editor h6 {Ð margin-top: 10px;Ð margin-bottom: 10px;ÐÐnote-editor h4 small,Ðnote-editor h5 small,Ðnote-editor h6 small,Ðnote-editor h4 .small,Ðnote-editor h5 .small,Ðnote-editor h6 .small {Ð font-size: 75%;ÐÐnote-editor h1,Ðnote-editor .h1 {Ð font-size: 36px;ÐÐnote-editor h2,Ðnote-editor .h2 {Ð font-size: 30px;ÐÐnote-editor h3,Ðnote-editor .h3 {Ð font-size: 24px;ÐÐnote-editor h4,Ðnote-editor .h4 {Ð font-size: 18px;Ð

}Ðnote-editor h5,Ðnote-editor .h5 {Ð font-size: 14px;ÞÐnote-editor h6,Ð .note-editor .h6 {Ð font-size: 12px;ÞÐnote-editor .page-header {Ð padding-bottom: 9px;Ð margin: 40px 0 20px;Ð border-bottom: 1px solid #eeeeee;ÞÐnote-editor ul,Ðnote-editor ol {Ð margin-top: 0;Ð margin-bottom: 10px;ÞÐnote-editor ul ul,Ðnote-editor ol ul,Ðnote-editor ul ol,Ðnote-editor ol ol {Ð margin-bottom: 0;ÞÐnote-editor .list-unstyled {Ð padding-left: 0;Ð list-style: none;ÞÐnote-editor .list-inline {Ð padding-left: 0;Ð list-style: none;ÞÐ .note-editor .list-inline > li {Ð display: inline-block;Ð padding-left: 5px;Ð padding-right: 5px;ÞÐnote-editor dl {Ð margin-bottom: 20px;ÞÐnote-editor dt,Ð .note-editor dd {Ð line-height: 1.428571429;ÞÐnote-editor dt {Ð font-weight: bold;ÞÐnote-editor dd {Ð margin-left: 0;ÞÐ@media (min-width: 768px) {Ð .note-editor .dl-horizontal dt {Ð float: left;Ð width: 160px;Ð clear: left;Ð text-align: right;Ð overflow: hidden;Ð text-overflow: ellipsis;Ð white-space: nowrap;Ð }Ð .note-editor .dl-horizontal dd {Ð margin-left: 180px;Ð }Ð .note-editor .dl-horizontal dd:before,Ð .note-editor .dl-horizontal dd:after {Ð content: " ";Ð /* 1 */Ð Ð display: table;Ð /* 2 */Ð Ð }Ð .note-editor .dl-horizontal dd:after {Ð clear: both;Ð }Ð .note-editor .dl-horizontal dd:before,Ð .note-editor .dl-horizontal dd:after {Ð content: " ";Ð /* 1 */Ð Ð display: table;Ð /* 2 */Ð Ð }Ð .note-editor .dl-horizontal dd:after {Ð clear: both;Ð }ÞÐnote-editor abbr[title],Ð .note-editor abbr[data-original-title] {Ð cursor: help;Ð border-bottom: 1px dotted #999999;ÞÐnote-editor abbr.initialism {Ð font-size: 90%;Ð text-transform: uppercase;ÞÐnote-editor blockquote {Ð padding: 10px 20px;Ð margin: 0 0 20px;Ð border-left: 5px solid #eeeeee;ÞÐnote-editor blockquote p {Ð font-size: 17.5px;Ð font-weight: 300;Ð line-height: 1.25;ÞÐnote-editor blockquote p:last-child {Ð margin-bottom: 0;ÞÐnote-editor blockquote small {Ð display: block;Ð line-height: 1.428571429;Ð color: #999999;ÞÐnote-editor blockquote small:before {Ð content: '\2014 \00A0';ÞÐnote-editor blockquote.pull-right {Ð padding-right: 15px;Ð padding-left: 0;Ð border-right: 5px solid #eeeeee;Ð border-left: 0;ÞÐnote-editor blockquote.pull-right p,Ðnote-editor blockquote.pull-right small,Ðnote-editor blockquote.pull-right .small {Ð text-align: right;ÞÐnote-editor blockquote.pull-right small:before,Ðnote-editor blockquote.pull-right .small:before {Ð content: '';ÞÐnote-editor blockquote.pull-right small:after,Ðnote-editor blockquote.pull-right .small:after {Ð content: '\00A0 \2014';ÞÐnote-editor blockquote:before,Ð .note-editor blockquote:after {Ð content: "";ÞÐnote-editor address {Ð margin-bottom: 20px;Ð font-style: normal;Ð line-height: 1.428571429;ÞÐnote-editor code,Ðnote-editor kdb,Ðnote-editor pre,Ðnote-editor samp {Ð font-family: Monaco, Menlo, Consolas, "Courier New", monospace;ÞÐnote-editor code {Ð padding: 2px 4px;Ð font-size: 90%;Ð color: #c7254e;Ð background-color: #f9f2f4;Ð white-space: nowrap;Ð border-radius: 4px;ÞÐnote-editor pre {Ð display: block;Ð padding: 9.5px;Ð margin: 0 0 10px;Ð font-size: 13px;Ð line-height: 1.428571429;Ð word-break: break-all;Ð word-wrap: break-word;Ð color: #333333;Ð background-color: #f5f5f5;Ð border: 1px solid #cccccc;Ð border-radius: 4px;ÞÐnote-editor pre code {Ð padding: 0;Ð font-size: inherit;Ð color: inherit;Ð white-space: pre-wrap;Ð background-color: transparent;Ð border-radius: 0;ÞÐnote-editor .pre-scrollable {Ð max-height: 340px;Ð overflow-y: scroll;ÞÐnote-editor .container {Ð margin-right: auto;Ð margin-left: auto;Ð padding-left: 15px;Ð padding-right: 15px;ÞÐnote-editor .container:before,Ðnote-editor .container:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .container:after {Ð clear: both;ÞÐ .note-editor .container:before,Ðnote-editor .container:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .container:after {Ð clear: both;ÞÐnote-editor .row {Ð margin-left: -15px;Ð margin-right: -15px;ÞÐnote-editor .row:before,Ðnote-editor .row:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .row:after {Ð clear: both;ÞÐnote-editor .row:before,Ðnote-editor .row:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .row:after {Ð clear: both;ÞÐnote-editor .col-xs-1, .col-sm-1, .col-md-1, .col-lg-1, .col-xs-2, .col-sm-2, .col-md-2, .col-lg-2, .col-xs-3, .col-sm-3, .col-md-3, .col-lg-3, .col-xs-4, .col-sm-4, .col-md-4, .col-lg-4, .col-xs-5, .col-sm-5, .col-md-5, .col-lg-5, .col-

xs-6, .col-sm-6, .col-md-6, .col-lg-6, .col-xs-7, .col-sm-7, .col-md-7, .col-
lg-7, .col-xs-8, .col-sm-8, .col-md-8, .col-lg-8, .col-xs-9, .col-sm-9, .col-
md-9, .col-lg-9, .col-xs-10, .col-sm-10, .col-md-10, .col-lg-10, .col-
xs-11, .col-sm-11, .col-md-11, .col-lg-11, .col-xs-12, .col-sm-12, .col-
md-12, .col-lg-12 {Ð position: relative;Ð min-height: 1px;Ð padding-left:
15px;Ð padding-right: 15px;ÐÐnote-editor .col-xs-1, .col-xs-2, .col-
xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8, .col-xs-9, .col-
xs-10, .col-xs-11 {Ð float: left;ÐÐnote-editor .col-xs-12 {Ð width: 100%;ÐÐ
.note-editor .col-xs-11 {Ð width: 91.66666666666666%;ÐÐnote-editor .col-xs-10
{Ð width: 83.33333333333334%;ÐÐnote-editor .col-xs-9 {Ð width: 75%;ÐÐnote-
editor .col-xs-8 {Ð width: 66.66666666666666%;ÐÐnote-editor .col-xs-7 {Ð
width: 58.333333333333336%;ÐÐnote-editor .col-xs-6 {Ð width: 50%;ÐÐnote-
editor .col-xs-5 {Ð width: 41.66666666666667%;ÐÐnote-editor .col-xs-4 {Ð
width: 33.33333333333333%;ÐÐnote-editor .col-xs-3 {Ð width: 25%;ÐÐnote-
editor .col-xs-2 {Ð width: 16.666666666666664%;ÐÐnote-editor .col-xs-1 {Ð
width: 8.333333333333332%;ÐÐnote-editor .col-xs-pull-12 {Ð right: 100%;ÐÐnote-
editor .col-xs-pull-11 {Ð right: 91.66666666666666%;ÐÐnote-editor .col-xs-
pull-10 {Ð right: 83.33333333333334%;ÐÐnote-editor .col-xs-pull-9 {Ð right:
75%;ÐÐnote-editor .col-xs-pull-8 {Ð right: 66.66666666666666%;ÐÐnote-
editor .col-xs-pull-7 {Ð right: 58.333333333333336%;ÐÐnote-editor .col-xs-
pull-6 {Ð right: 50%;ÐÐnote-editor .col-xs-pull-5 {Ð right:
41.66666666666667%;ÐÐnote-editor .col-xs-pull-4 {Ð right: 33.33333333333333%;ÐÐ
.note-editor .col-xs-pull-3 {Ð right: 25%;ÐÐnote-editor .col-xs-pull-2 {Ð
right: 16.666666666666664%;ÐÐnote-editor .col-xs-pull-1 {Ð right:
8.333333333333332%;ÐÐnote-editor .col-xs-push-12 {Ð left: 100%;ÐÐnote-
editor .col-xs-push-11 {Ð left: 91.66666666666666%;ÐÐnote-editor .col-xs-
push-10 {Ð left: 83.33333333333334%;ÐÐnote-editor .col-xs-push-9 {Ð left: 75%;Ð
}Ðnote-editor .col-xs-push-8 {Ð left: 66.66666666666666%;ÐÐnote-editor .col-
xs-push-7 {Ð left: 58.333333333333336%;ÐÐnote-editor .col-xs-push-6 {Ð left:
50%;ÐÐnote-editor .col-xs-push-5 {Ð left: 41.66666666666667%;ÐÐnote-
editor .col-xs-push-4 {Ð left: 33.33333333333333%;ÐÐnote-editor .col-xs-
push-3 {Ð left: 25%;ÐÐnote-editor .col-xs-push-2 {Ð left: 16.666666666666664%;Ð
}Ðnote-editor .col-xs-push-1 {Ð left: 8.333333333333332%;ÐÐnote-editor .col-
xs-offset-12 {Ð margin-left: 100%;ÐÐnote-editor .col-xs-offset-11 {Ð margin-
left: 91.66666666666666%;ÐÐnote-editor .col-xs-offset-10 {Ð margin-left:
83.33333333333334%;ÐÐnote-editor .col-xs-offset-9 {Ð margin-left: 75%;ÐÐnote-
editor .col-xs-offset-8 {Ð margin-left: 66.66666666666666%;ÐÐnote-editor .col-
xs-offset-7 {Ð margin-left: 58.333333333333336%;ÐÐnote-editor .col-xs-
offset-6 {Ð margin-left: 50%;ÐÐnote-editor .col-xs-offset-5 {Ð margin-left:
41.66666666666667%;ÐÐnote-editor .col-xs-offset-4 {Ð margin-left:
33.33333333333333%;ÐÐnote-editor .col-xs-offset-3 {Ð margin-left: 25%;ÐÐnote-
editor .col-xs-offset-2 {Ð margin-left: 16.666666666666664%;ÐÐnote-
editor .col-xs-offset-1 {Ð margin-left: 8.333333333333332%;ÐÐ@media (min-
width: 768px) {Ð .note-editor .container {Ð width: 750px;Ð }Ð .note-
editor .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-
sm-7, .col-sm-8, .col-sm-9, .col-sm-10, .col-sm-11 {Ð float: left;Ð }Ð
.note-editor .col-sm-12 {Ð width: 100%;Ð }Ð .note-editor .col-sm-11 {Ð
width: 91.66666666666666%;Ð }Ð .note-editor .col-sm-10 {Ð width:
83.33333333333334%;Ð }Ð .note-editor .col-sm-9 {Ð width: 75%;Ð }Ð .note-
editor .col-sm-8 {Ð width: 66.66666666666666%;Ð }Ð .note-editor .col-sm-7 {Ð
width: 58.333333333333336%;Ð }Ð .note-editor .col-sm-6 {Ð width: 50%;Ð }Ð
.note-editor .col-sm-5 {Ð width: 41.66666666666667%;Ð }Ð .note-
editor .col-sm-4 {Ð width: 33.33333333333333%;Ð }Ð .note-editor .col-sm-3 {Ð
width: 25%;Ð }Ð .note-editor .col-sm-2 {Ð width: 16.666666666666664%;Ð }Ð
.note-editor .col-sm-1 {Ð width: 8.333333333333332%;Ð }Ð .note-
editor .col-sm-pull-12 {Ð right: 100%;Ð }Ð .note-editor .col-sm-pull-11 {Ð
right: 91.66666666666666%;Ð }Ð .note-editor .col-sm-pull-10 {Ð right:
83.33333333333334%;Ð }Ð .note-editor .col-sm-pull-9 {Ð right: 75%;Ð }Ð
.note-editor .col-sm-pull-8 {Ð right: 66.66666666666666%;Ð }Ð .note-
editor .col-sm-pull-7 {Ð

right: 58.333333333333336%;Ð }Ð .note-editor .col-sm-pull-6 {Ð right: 50%;Ð }Ð .note-editor .col-sm-pull-5 {Ð right: 41.66666666666667%;Ð }Ð .note-editor .col-sm-pull-4 {Ð right: 33.33333333333333%;Ð }Ð .note-editor .col-sm-pull-3 {Ð right: 25%;Ð }Ð .note-editor .col-sm-pull-2 {Ð right: 16.666666666666664%;Ð }Ð .note-editor .col-sm-pull-1 {Ð right: 8.333333333333332%;Ð }Ð .note-editor .col-sm-push-12 {Ð left: 100%;Ð }Ð .note-editor .col-sm-push-11 {Ð left: 91.66666666666666%;Ð }Ð .note-editor .col-sm-push-10 {Ð left: 83.33333333333334%;Ð }Ð .note-editor .col-sm-push-9 {Ð left: 75%;Ð }Ð .note-editor .col-sm-push-8 {Ð left: 66.66666666666666%;Ð }Ð .note-editor .col-sm-push-7 {Ð left: 58.333333333333336%;Ð }Ð .note-editor .col-sm-push-6 {Ð left: 50%;Ð }Ð .note-editor .col-sm-push-5 {Ð left: 41.66666666666667%;Ð }Ð .note-editor .col-sm-push-4 {Ð left: 33.33333333333333%;Ð }Ð .note-editor .col-sm-push-3 {Ð left: 25%;Ð }Ð .note-editor .col-sm-push-2 {Ð left: 16.666666666666664%;Ð }Ð .note-editor .col-sm-push-1 {Ð left: 8.333333333333332%;Ð }Ð .note-editor .col-sm-offset-12 {Ð margin-left: 100%;Ð }Ð .note-editor .col-sm-offset-11 {Ð margin-left: 91.66666666666666%;Ð }Ð .note-editor .col-sm-offset-10 {Ð margin-left: 83.33333333333334%;Ð }Ð .note-editor .col-sm-offset-9 {Ð margin-left: 75%;Ð }Ð .note-editor .col-sm-offset-8 {Ð margin-left: 66.66666666666666%;Ð }Ð .note-editor .col-sm-offset-7 {Ð margin-left: 58.333333333333336%;Ð }Ð .note-editor .col-sm-offset-6 {Ð margin-left: 50%;Ð }Ð .note-editor .col-sm-offset-5 {Ð margin-left: 41.66666666666667%;Ð }Ð .note-editor .col-sm-offset-4 {Ð margin-left: 33.33333333333333%;Ð }Ð .note-editor .col-sm-offset-3 {Ð margin-left: 25%;Ð }Ð .note-editor .col-sm-offset-2 {Ð margin-left: 16.666666666666664%;Ð }Ð .note-editor .col-sm-offset-1 {Ð margin-left: 8.333333333333332%;Ð }ÐÐ @media (min-width: 992px) {Ð .note-editor .container {Ð width: 970px;Ð }Ð .note-editor .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8, .col-md-9, .col-md-10, .col-md-11 {Ð float: left;Ð }Ð .note-editor .col-md-12 {Ð width: 100%;Ð }Ð .note-editor .col-md-11 {Ð width: 91.66666666666666%;Ð }Ð .note-editor .col-md-10 {Ð width: 83.33333333333334%;Ð }Ð .note-editor .col-md-9 {Ð width: 75%;Ð }Ð .note-editor .col-md-8 {Ð width: 66.66666666666666%;Ð }Ð .note-editor .col-md-7 {Ð width: 58.333333333333336%;Ð }Ð .note-editor .col-md-6 {Ð width: 50%;Ð }Ð .note-editor .col-md-5 {Ð width: 41.66666666666667%;Ð }Ð .note-editor .col-md-4 {Ð width: 33.33333333333333%;Ð }Ð .note-editor .col-md-3 {Ð width: 25%;Ð }Ð .note-editor .col-md-2 {Ð width: 16.666666666666664%;Ð }Ð .note-editor .col-md-1 {Ð width: 8.333333333333332%;Ð }Ð .note-editor .col-md-pull-12 {Ð right: 100%;Ð }Ð .note-editor .col-md-pull-11 {Ð right: 91.66666666666666%;Ð }Ð .note-editor .col-md-pull-10 {Ð right: 83.33333333333334%;Ð }Ð .note-editor .col-md-pull-9 {Ð right: 75%;Ð }Ð .note-editor .col-md-pull-8 {Ð right: 66.66666666666666%;Ð }Ð .note-editor .col-md-pull-7 {Ð right: 58.333333333333336%;Ð }Ð .note-editor .col-md-pull-6 {Ð right: 50%;Ð }Ð .note-editor .col-md-pull-5 {Ð right: 41.66666666666667%;Ð }Ð .note-editor .col-md-pull-4 {Ð right: 33.33333333333333%;Ð }Ð .note-editor .col-md-pull-3 {Ð right: 25%;Ð }Ð .note-editor .col-md-pull-2 {Ð right: 16.666666666666664%;Ð }Ð .note-editor .col-md-pull-1 {Ð right: 8.333333333333332%;Ð }Ð .note-editor .col-md-push-12 {Ð left: 100%;Ð }Ð .note-editor .col-md-push-11 {Ð left: 91.66666666666666%;Ð }Ð .note-editor .col-md-push-10 {Ð left: 83.33333333333334%;Ð }Ð .note-editor .col-md-push-9 {Ð left: 75%;Ð }Ð .note-editor .col-md-push-8 {Ð left: 66.66666666666666%;Ð }Ð .note-editor .col-md-push-7 {Ð left: 58.333333333333336%;Ð }Ð .note-editor .col-md-push-6 {Ð left: 50%;Ð }Ð .note-editor .col-md-push-5 {Ð left: 41.66666666666667%;Ð }Ð .note-editor .col-md-push-4 {Ð left: 33.33333333333333%;Ð }Ð .note-editor .col-md-push-3 {Ð left: 25%;Ð }Ð .note-editor .col-md-push-2 {Ð left: 16.666666666666664%;Ð }Ð .note-editor .col-md-push-1 {Ð left: 8.333333333333332%;Ð }Ð .note-editor .col-md-offset-12 {Ð margin-left: 100%;Ð }Ð .note-editor .col-md-offset-11 {Ð margin-left: 91.66666666666666%;Ð }Ð .note-editor .col-md-offset-10 {Ð

margin-left: 83.33333333333334%;Ð }Ð
.note-editor .col-md-offset-9 {Ð margin-left: 75%;Ð }Ð .note-editor .col-
md-offset-8 {Ð margin-left: 66.66666666666666%;Ð }Ð .note-editor .col-md-
offset-7 {Ð margin-left: 58.333333333333336%;Ð }Ð .note-editor .col-md-
offset-6 {Ð margin-left: 50%;Ð }Ð .note-editor .col-md-offset-5 {Ð margin-
left: 41.66666666666667%;Ð }Ð .note-editor .col-md-offset-4 {Ð margin-left:
33.33333333333333%;Ð }Ð .note-editor .col-md-offset-3 {Ð margin-left: 25%;Ð
}Ð .note-editor .col-md-offset-2 {Ð margin-left: 16.666666666666664%;Ð }Ð
.note-editor .col-md-offset-1 {Ð margin-left: 8.333333333333332%;Ð }ÞÐ
@media (min-width: 1200px) {Ð .note-editor .container {Ð width: 1170px;Ð }Ð
.note-editor .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-
lg-6, .col-lg-7, .col-lg-8, .col-lg-9, .col-lg-10, .col-lg-11 {Ð float:
left;Ð }Ð .note-editor .col-lg-12 {Ð width: 100%;Ð }Ð .note-editor .col-
lg-11 {Ð width: 91.66666666666666%;Ð }Ð .note-editor .col-lg-10 {Ð width:
83.33333333333334%;Ð }Ð .note-editor .col-lg-9 {Ð width: 75%;Ð }Ð .note-
editor .col-lg-8 {Ð width: 66.66666666666666%;Ð }Ð .note-editor .col-lg-7 {Ð
width: 58.333333333333336%;Ð }Ð .note-editor .col-lg-6 {Ð width: 50%;Ð }Ð
.note-editor .col-lg-5 {Ð width: 41.66666666666667%;Ð }Ð .note-
editor .col-lg-4 {Ð width: 33.33333333333333%;Ð }Ð .note-editor .col-lg-3 {Ð
width: 25%;Ð }Ð .note-editor .col-lg-2 {Ð width: 16.666666666666664%;Ð }Ð
.note-editor .col-lg-1 {Ð width: 8.333333333333332%;Ð }Ð .note-
editor .col-lg-pull-12 {Ð right: 100%;Ð }Ð .note-editor .col-lg-pull-11 {Ð
right: 91.66666666666666%;Ð }Ð .note-editor .col-lg-pull-10 {Ð right:
83.33333333333334%;Ð }Ð .note-editor .col-lg-pull-9 {Ð right: 75%;Ð }Ð
.note-editor .col-lg-pull-8 {Ð right: 66.66666666666666%;Ð }Ð .note-
editor .col-lg-pull-7 {Ð right: 58.333333333333336%;Ð }Ð .note-editor .col-
lg-pull-6 {Ð right: 50%;Ð }Ð .note-editor .col-lg-pull-5 {Ð right:
41.66666666666667%;Ð }Ð .note-editor .col-lg-pull-4 {Ð right:
33.33333333333333%;Ð }Ð .note-editor .col-lg-pull-3 {Ð right: 25%;Ð }Ð
.note-editor .col-lg-pull-2 {Ð right: 16.666666666666664%;Ð }Ð .note-
editor .col-lg-pull-1 {Ð right: 8.333333333333332%;Ð }Ð .note-editor .col-
lg-push-12 {Ð left: 100%;Ð }Ð .note-editor .col-lg-push-11 {Ð left:
91.66666666666666%;Ð }Ð .note-editor .col-lg-push-10 {Ð left:
83.33333333333334%;Ð }Ð .note-editor .col-lg-push-9 {Ð left: 75%;Ð }Ð .note-
editor .col-lg-push-8 {Ð left: 66.66666666666666%;Ð }Ð .note-editor .col-lg-
push-7 {Ð left: 58.333333333333336%;Ð }Ð .note-editor .col-lg-push-6 {Ð
left: 50%;Ð }Ð .note-editor .col-lg-push-5 {Ð left: 41.66666666666667%;Ð }Ð
.note-editor .col-lg-push-4 {Ð left: 33.33333333333333%;Ð }Ð .note-
editor .col-lg-push-3 {Ð left: 25%;Ð }Ð .note-editor .col-lg-push-2 {Ð
left: 16.666666666666664%;Ð }Ð .note-editor .col-lg-push-1 {Ð left:
8.333333333333332%;Ð }Ð .note-editor .col-lg-offset-12 {Ð margin-left: 100%;Ð
}Ð .note-editor .col-lg-offset-11 {Ð margin-left: 91.66666666666666%;Ð }Ð
.note-editor .col-lg-offset-10 {Ð margin-left: 83.33333333333334%;Ð }Ð
.note-editor .col-lg-offset-9 {Ð margin-left: 75%;Ð }Ð .note-editor .col-
lg-offset-8 {Ð margin-left: 66.66666666666666%;Ð }Ð .note-editor .col-lg-
offset-7 {Ð margin-left: 58.333333333333336%;Ð }Ð .note-editor .col-lg-
offset-6 {Ð margin-left: 50%;Ð }Ð .note-editor .col-lg-offset-5 {Ð margin-
left: 41.66666666666667%;Ð }Ð .note-editor .col-lg-offset-4 {Ð margin-left:
33.33333333333333%;Ð }Ð .note-editor .col-lg-offset-3 {Ð margin-left: 25%;Ð
}Ð .note-editor .col-lg-offset-2 {Ð margin-left: 16.666666666666664%;Ð }Ð
.note-editor .col-lg-offset-1 {Ð margin-left: 8.333333333333332%;Ð }ÞÐ
.note-editor table {Ð max-width: 100%;Ð background-color: transparent;ÞÐnote-
editor th {Ð text-align: left;ÞÐnote-editor .table {Ð width: 100%;Ð margin-
bottom: 20px;ÞÐnote-editor .table > thead > tr > th,Ðnote-editor .table >
tbody > tr > th,Ðnote-editor .table > tfoot > tr > th,Ðnote-editor .table >
thead > tr > td,Ðnote-editor .table > tbody > tr > td,Ðnote-editor .table >
tfoot > tr > td {Ð padding: 8px;Ð line-height: 1.428571429;Ð vertical-align:
top;Ð border-top: 1px solid #dddddd;ÞÐnote-editor .table > thead > tr > th {Ð
vertical-align: bottom;Ð border-bottom: 2px solid #dddddd;ÞÐnote-
editor .table > caption + thead > tr:first-child > th,Ð

.note-editor .table > colgroup + thead > tr:first-child > th,Ðnote-editor .table > thead:first-child > tr:first-child > th,Ðnote-editor .table > caption + thead > tr:first-child > td,Ðnote-editor .table > colgroup + thead > tr:first-child > td,Ðnote-editor .table > thead:first-child > tr:first-child > td {Ð border-top: 0;ÐÐ .note-editor .table > tbody + tbody {Ð border-top: 2px solid #dddddd;ÐÐnote-editor .table .table {Ð background-color: #ffffff;ÐÐnote-editor .table-condensed > thead > tr > th,Ðnote-editor .table-condensed > tbody > tr > th,Ð .note-editor .table-condensed > tfoot > tr > th,Ðnote-editor .table-condensed > thead > tr > td,Ðnote-editor .table-condensed > tbody > tr > td,Ðnote-editor .table-condensed > tfoot > tr > td {Ð padding: 5px;ÐÐnote-editor .table-bordered {Ð border: 1px solid #dddddd;ÐÐnote-editor .table-bordered > thead > tr > th,Ðnote-editor .table-bordered > tbody > tr > th,Ð .note-editor .table-bordered > tfoot > tr > th,Ðnote-editor .table-bordered > thead > tr > td,Ðnote-editor .table-bordered > tbody > tr > td,Ðnote-editor .table-bordered > tfoot > tr > td {Ð border: 1px solid #dddddd;ÐÐnote-editor .table-bordered > thead > tr > th,Ðnote-editor .table-bordered > thead > tr > td {Ð border-bottom-width: 2px;ÐÐnote-editor .table-striped > tbody > tr:nth-child(odd) > td,Ðnote-editor .table-striped > tbody > tr:nth-child(odd) > th {Ð background-color: #f9f9f9;ÐÐnote-editor .table-hover > tbody > tr:hover > td,Ðnote-editor .table-hover > tbody > tr:hover > th {Ð background-color: #f5f5f5;ÐÐnote-editor table col[class*="col-"] {Ð float: none;Ð display: table-column;ÐÐnote-editor table td[class*="col-"],Ðnote-editor table th[class*="col-"] {Ð float: none;Ð display: table-cell;ÐÐnote-editor .table > thead > tr > td.active,Ðnote-editor .table > tbody > tr > td.active,Ðnote-editor .table > tfoot > tr > td.active,Ðnote-editor .table > thead > tr > th.active,Ðnote-editor .table > tbody > tr > th.active,Ðnote-editor .table > tfoot > tr > th.active,Ðnote-editor .table > thead > tr.active > td,Ðnote-editor .table > tbody > tr.active > td,Ðnote-editor .table > tfoot > tr.active > td,Ðnote-editor .table > thead > tr.active > th,Ðnote-editor .table > tbody > tr.active > th,Ðnote-editor .table > tfoot > tr.active > th {Ð background-color: #f5f5f5;ÐÐnote-editor .table > thead > tr > td.success,Ðnote-editor .table > tbody > tr > td.success,Ðnote-editor .table > tfoot > tr > td.success,Ðnote-editor .table > thead > tr > th.success,Ðnote-editor .table > tbody > tr > th.success,Ðnote-editor .table > tfoot > tr > th.success,Ðnote-editor .table > thead > tr.success > td,Ðnote-editor .table > tbody > tr.success > td,Ðnote-editor .table > tfoot > tr.success > td,Ðnote-editor .table > thead > tr.success > th,Ðnote-editor .table > tbody > tr.success > th,Ðnote-editor .table > tfoot > tr.success > th {Ð background-color: #dff0d8;Ð border-color: #d6e9c6;ÐÐnote-editor .table-hover > tbody > tr > td.success:hover,Ð .note-editor .table-hover > tbody > tr > th.success:hover,Ðnote-editor .table-hover > tbody > tr.success:hover > td,Ðnote-editor .table-hover > tbody > tr.success:hover > th {Ð background-color: #d0e9c6;Ð border-color: #c9e2b3;ÐÐ .note-editor .table > thead > tr > td.danger,Ðnote-editor .table > tbody > tr > td.danger,Ðnote-editor .table > tfoot > tr > td.danger,Ðnote-editor .table > thead > tr > th.danger,Ðnote-editor .table > tbody > tr > th.danger,Ðnote-editor .table > tfoot > tr > th.danger,Ðnote-editor .table > thead > tr.danger > td,Ðnote-editor .table > tbody > tr.danger > td,Ðnote-editor .table > tfoot > tr.danger > td,Ðnote-editor .table > thead > tr.danger > th,Ðnote-editor .table > tbody > tr.danger > th,Ðnote-editor .table > tfoot > tr.danger > th {Ð background-color: #f2dede;Ð border-color: #ebccd1;ÐÐnote-editor .table-hover > tbody > tr > td.danger:hover,Ð .note-editor .table-hover > tbody > tr > th.danger:hover,Ðnote-editor .table-hover > tbody > tr.danger:hover > td,Ðnote-editor .table-hover > tbody > tr.danger:hover > th {Ð background-color: #ebcccc;Ð border-color: #e4b9c0;ÐÐ .note-editor .table > thead > tr > td.warning,Ðnote-editor .table > tbody > tr > td.warning,Ðnote-editor .table > tfoot > tr > td.warning,Ðnote-editor .table > thead > tr > th.warning,Ðnote-editor .table > tbody > tr > th.warning,Ð

.note-editor .table > tfoot > tr > th.warning,Ðnote-editor .table > thead > tr.warning > td,Ðnote-editor .table > tbody > tr.warning > td,Ðnote-editor .table > tfoot > tr.warning > td,Ðnote-editor .table > thead > tr.warning > th,Ðnote-editor .table > tbody > tr.warning > th,Ðnote-editor .table > tfoot > tr.warning > th {Ð background-color: #fcf8e3;Ð border-color: #faebcc;ÐÐnote-editor .table-hover > tbody > tr > td.warning:hover,Ð .note-editor .table-hover > tbody > tr > th.warning:hover,Ðnote-editor .table-hover > tbody > tr.warning:hover > td,Ðnote-editor .table-hover > tbody > tr.warning:hover > th {Ð background-color: #faf2cc;Ð border-color: #f7e1b5;ÐÐ @media (max-width: 767px) {Ð .note-editor .table-responsive {Ð width: 100%;Ð margin-bottom: 15px;Ð overflow-y: hidden;Ð overflow-x: scroll;Ð -ms-overflow-style: -ms-autohiding-scrollbar;Ð border: 1px solid #dddddd;Ð -webkit-overflow-scrolling: touch;Ð }Ð .note-editor .table-responsive > .table {Ð margin-bottom: 0;Ð }Ð .note-editor .table-responsive > .table > thead > tr > th,Ð .note-editor .table-responsive > .table > tbody > tr > th,Ð .note-editor .table-responsive > .table > tfoot > tr > th,Ð .note-editor .table-responsive > .table > thead > tr > td,Ð .note-editor .table-responsive > .table > tbody > tr > td,Ð .note-editor .table-responsive > .table > tfoot > tr > td {Ð white-space: nowrap;Ð }Ð .note-editor .table-responsive > .table-bordered {Ð border: 0;Ð }Ð .note-editor .table-responsive > .table-bordered > thead > tr > th:first-child,Ð .note-editor .table-responsive > .table-bordered > tbody > tr > th:first-child,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ð .note-editor .table-responsive > .table-bordered > thead > tr > td:first-child,Ð .note-editor .table-responsive > .table-bordered > tbody > tr > td:first-child,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left: 0;Ð }Ð .note-editor .table-responsive > .table-bordered > thead > tr > th:last-child,Ð .note-editor .table-responsive > .table-bordered > tbody > tr > th:last-child,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ð .note-editor .table-responsive > .table-bordered > thead > tr > td:last-child,Ð .note-editor .table-responsive > .table-bordered > tbody > tr > td:last-child,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-right: 0;Ð }Ð .note-editor .table-responsive > .table-bordered > tbody > tr:last-child > th,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr:last-child > th,Ð .note-editor .table-responsive > .table-bordered > tbody > tr:last-child > td,Ð .note-editor .table-responsive > .table-bordered > tfoot > tr:last-child > td {Ð border-bottom: 0;Ð }ÐÐnote-editor fieldset {Ð padding: 0;Ð margin: 0;Ð border: 0;ÐÐnote-editor legend {Ð display: block;Ð width: 100%;Ð padding: 0;Ð margin-bottom: 20px;Ð font-size: 21px;Ð line-height: inherit;Ð color: #333333;Ð border: 0;Ð border-bottom: 1px solid #e5e5e5;ÐÐnote-editor label {Ð display: inline-block;Ð margin-bottom: 5px;Ð font-weight: bold;ÐÐnote-editor input[type="search"] {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÐÐnote-editor input[type="radio"],Ðnote-editor input[type="checkbox"] {Ð margin: 4px 0 0;Ð margin-top: 1px \9;Ð /* IE8-9 */Ð line-height: normal;ÐÐnote-editor input[type="file"] {Ð display: block;ÐÐnote-editor select[multiple],Ðnote-editor select[size] {Ð height: auto;ÐÐnote-editor select optgroup {Ð font-size: inherit;Ð font-style: inherit;Ð font-family: inherit;ÐÐnote-editor input[type="file"]:focus,Ðnote-editor input[type="radio"]:focus,Ðnote-editor input[type="checkbox"]:focus {Ð outline: thin dotted #333;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐnote-editor input[type="number"]::-webkit-outer-spin-button,Ðnote-editor input[type="number"]::-webkit-inner-spin-button {Ð height: auto;ÐÐnote-editor output {Ð display: block;Ð padding-top: 7px;Ð font-size: 14px;Ð line-height: 1.428571429;Ð color: #555555;Ð vertical-align: middle;ÐÐnote-editor .form-control:-moz-placeholder {Ð color: #999999;ÐÐnote-editor .form-control::-moz-placeholder {Ð color: #999999;ÐÐnote-editor .form-control:-ms-input-placeholder {Ð color: #999999;ÐÐnote-editor .form-control::-webkit-input-placeholder {Ð

color: #999999;ÞÞnote-editor .form-control {Ð
display: block;Ð width: 100%;Ð height: 34px;Ð padding: 6px 12px;Ð font-size:
14px;Ð line-height: 1.428571429;Ð color: #555555;Ð vertical-align: middle;Ð
background-color: #ffffff;Ð background-image: none;Ð border: 1px solid
#cccccc;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0,
0, 0.075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);Ð -webkit-
transition: border-color ease-in-out .15s, box-shadow ease-in-out .15s;Ð
transition: border-color ease-in-out .15s, box-shadow ease-in-out .15s;ÞÞnote-
editor .form-control:focus {Ð border-color: #66afe9;Ð outline: 0;Ð -webkit-
box-shadow: inset 0 1px 1px rgba(0,0,0,.075), 0 0 8px rgba(102, 175, 233,
0.6);Ð box-shadow: inset 0 1px 1px rgba(0,0,0,.075), 0 0 8px rgba(102, 175,
233, 0.6);ÞÞnote-editor .form-control[disabled],Ðnote-editor .form-
control[readonly],Ðfieldset[disabled] .note-editor .form-control {Ð cursor:
not-allowed;Ð background-color: #eeeeee;ÞÞtextarea.note-editor .form-control {Ð
height: auto;ÞÞnote-editor .form-group {Ð margin-bottom: 15px;ÞÞnote-
editor .radio,Ðnote-editor .checkbox {Ð display: block;Ð min-height: 20px;Ð
margin-top: 10px;Ð margin-bottom: 10px;Ð padding-left: 20px;Ð vertical-align:
middle;ÞÞnote-editor .radio label,Ðnote-editor .checkbox label {Ð display:
inline;Ð margin-bottom: 0;Ð font-weight: normal;Ð cursor: pointer;ÞÞnote-
editor .radio input[type="radio"],Ðnote-editor .radio-inline
input[type="radio"],Ðnote-editor .checkbox input[type="checkbox"],Ðnote-
editor .checkbox-inline input[type="checkbox"] {Ð float: left;Ð margin-left:
-20px;ÞÞnote-editor .radio + .radio,Ðnote-editor .checkbox + .checkbox {Ð
margin-top: -5px;ÞÞnote-editor .radio-inline,Ðnote-editor .checkbox-inline {Ð
display: inline-block;Ð padding-left: 20px;Ð margin-bottom: 0;Ð vertical-
align: middle;Ð font-weight: normal;Ð cursor: pointer;ÞÞnote-editor .radio-
inline + .radio-inline,Ðnote-editor .checkbox-inline + .checkbox-inline {Ð
margin-top: 0;Ð margin-left: 10px;ÞÞnote-editor input[type="radio"][disabled],Ð
.note-editor input[type="checkbox"][disabled],Ðnote-editor .radio[disabled],Ð
.note-editor .radio-inline[disabled],Ðnote-editor .checkbox[disabled],Ðnote-
editor .checkbox-inline[disabled],Ðfieldset[disabled] .note-editor
input[type="radio"],Ðfieldset[disabled] .note-editor input[type="checkbox"],Ð
fieldset[disabled] .note-editor .radio,Ðfieldset[disabled] .note-editor .radio-
inline,Ðfieldset[disabled] .note-editor .checkbox,Ðfieldset[disabled] .note-
editor .checkbox-inline {Ð cursor: not-allowed;ÞÞnote-editor .input-sm {Ð
height: 30px;Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð
border-radius: 3px;ÞÞselect.note-editor .input-sm {Ð height: 30px;Ð line-
height: 30px;ÞÞtextarea.note-editor .input-sm {Ð height: auto;ÞÞnote-
editor .input-lg {Ð height: 45px;Ð padding: 10px 16px;Ð font-size: 18px;Ð
line-height: 1.33;Ð border-radius: 6px;ÞÞselect.note-editor .input-lg {Ð
height: 45px;Ð line-height: 45px;ÞÞtextarea.note-editor .input-lg {Ð height:
auto;ÞÞnote-editor .has-warning .help-block,Ðnote-editor .has-
warning .control-label {Ð color: #c09853;ÞÞnote-editor .has-warning .form-
control {Ð border-color: #c09853;Ð -webkit-box-shadow: inset 0 1px 1px
rgba(0, 0, 0, 0.075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);ÞÞ
.note-editor .has-warning .form-control:focus {Ð border-color: #a47e3c;Ð -
webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #dbc59e;Ð
box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #dbc59e;ÞÞnote-
editor .has-warning .input-group-addon {Ð color: #c09853;Ð border-color:
#c09853;Ð background-color: #fcf8e3;ÞÞnote-editor .has-error .help-block,Ð
.note-editor .has-error .control-label {Ð color: #b94a48;ÞÞnote-editor .has-
error .form-control {Ð border-color: #b94a48;Ð -webkit-box-shadow: inset 0
1px 1px rgba(0, 0, 0, 0.075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0,
0.075);ÞÞnote-editor .has-error .form-control:focus {Ð border-color: #953b39;Ð
-webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #d59392;Ð
box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #d59392;ÞÞnote-
editor .has-error .input-group-addon {Ð color: #b94a48;Ð border-color:
#b94a48;Ð background-color: #f2dede;ÞÞnote-editor .has-success .help-block,Ð
.note-editor .has-success .control-label {Ð color: #468847;ÞÞnote-editor .has-
success .form-control {Ð

border-color: #468847;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);ÞÐnote-editor .has-success .form-control:focus {Ð border-color: #356635;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #7aba7b;Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #7aba7b;ÞÐ .note-editor .has-success .input-group-addon {Ð color: #468847;Ð border-color: #468847;Ð background-color: #dff0d8;ÞÐnote-editor .form-control-static {Ð margin-bottom: 0;ÞÐnote-editor .help-block {Ð display: block;Ð margin-top: 5px;Ð margin-bottom: 10px;Ð color: #737373;Þ@media (min-width: 768px) {Ð .note-editor .form-inline .form-group {Ð display: inline-block;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .note-editor .form-inline .form-control {Ð display: inline-block;Ð }Ð .note-editor .form-inline .radio,Ð .note-editor .form-inline .checkbox {Ð display: inline-block;Ð margin-top: 0;Ð margin-bottom: 0;Ð padding-left: 0;Ð }Ð .note-editor .form-inline .radio input[type="radio"],Ð .note-editor .form-inline .checkbox input[type="checkbox"] {Ð float: none;Ð margin-left: 0;Ð }ÞÐnote-editor .form-horizontal .control-label,Ðnote-editor .form-horizontal .radio,Ð .note-editor .form-horizontal .checkbox,Ðnote-editor .form-horizontal .radio-inline,Ðnote-editor .form-horizontal .checkbox-inline {Ð margin-top: 0;Ð margin-bottom: 0;Ð padding-top: 7px;ÞÐnote-editor .form-horizontal .form-group {Ð margin-left: -15px;Ð margin-right: -15px;ÞÐnote-editor .form-horizontal .form-group:before,Ðnote-editor .form-horizontal .form-group:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .form-horizontal .form-group:after {Ð clear: both;ÞÐnote-editor .form-horizontal .form-group:before,Ðnote-editor .form-horizontal .form-group:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .form-horizontal .form-group:after {Ð clear: both;ÞÐnote-editor .form-horizontal .form-control-static {Ð padding-top: 7px;Þ@media (min-width: 768px) {Ð .note-editor .form-horizontal .control-label {Ð text-align: right;Ð }ÞÐnote-editor .btn {Ð display: inline-block;Ð margin-bottom: 0;Ð font-weight: normal;Ð text-align: center;Ð vertical-align: middle;Ð cursor: pointer;Ð background-image: none;Ð border: 1px solid transparent;Ð white-space: nowrap;Ð padding: 6px 12px;Ð font-size: 14px;Ð line-height: 1.428571429;Ð border-radius: 4px;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð -o-user-select: none;Ð user-select: none;ÞÐnote-editor .btn:focus {Ð outline: thin dotted #333;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÞÐnote-editor .btn:hover,Ð .note-editor .btn:focus {Ð color: #333333;Ð text-decoration: none;ÞÐnote-editor .btn:active,Ðnote-editor .btn.active {Ð outline: 0;Ð background-image: none;Ð -webkit-box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);Ð box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);ÞÐnote-editor .btn.disabled,Ðnote-editor .btn[disabled],Ðfieldset[disabled] .note-editor .btn {Ð cursor: not-allowed;Ð pointer-events: none;Ð opacity: 0.65;Ð filter: alpha(opacity=65);Ð -webkit-box-shadow: none;Ð box-shadow: none;ÞÐnote-editor .btn-default {Ð color: #333333;Ð background-color: #ffffff;Ð border-color: #cccccc;ÞÐnote-editor .btn-default:hover,Ðnote-editor .btn-default:focus,Ðnote-editor .btn-default:active,Ðnote-editor .btn-default.active,Ðopen .dropdown-toggle.note-editor .btn-default {Ð color: #333333;Ð background-color: #ebebeb;Ð border-color: #adadad;ÞÐnote-editor .btn-default:active,Ðnote-editor .btn-default.active,Ðopen .dropdown-toggle.note-editor .btn-default {Ð background-image: none;ÞÐnote-editor .btn-default.disabled,Ðnote-editor .btn-default[disabled],Ðfieldset[disabled] .note-editor .btn-default,Ðnote-editor .btn-default.disabled:hover,Ðnote-editor .btn-default[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-default:hover,Ðnote-editor .btn-default.disabled:focus,Ðnote-editor .btn-default[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-default:focus,Ðnote-editor .btn-default.disabled:active,Ðnote-editor .btn-default[disabled]:active,Ð fieldset[disabled] .note-editor .btn-default:active,Ðnote-editor .btn-default.disabled.active,Ðnote-editor .btn-default[disabled].active,Ð fieldset[disabled] .note-editor .btn-default.active {Ð

background-color: #ffffff;Ð border-color: #cccccc;ÞÐnote-editor .btn-primary {Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #357ebd;ÞÐnote-editor .btn-primary:hover,Ðnote-editor .btn-primary:focus,Ðnote-editor .btn-primary:active,Ðnote-editor .btn-primary.active,Ðopen .dropdown-toggle.note-editor .btn-primary {Ð color: #ffffff;Ð background-color: #3276b1;Ð border-color: #285e8e;ÞÐnote-editor .btn-primary:active,Ðnote-editor .btn-primary.active,Ðopen .dropdown-toggle.note-editor .btn-primary {Ð background-image: none;ÞÐnote-editor .btn-primary.disabled,Ðnote-editor .btn-primary[disabled],Ðfieldset[disabled] .note-editor .btn-primary,Ðnote-editor .btn-primary.disabled:hover,Ðnote-editor .btn-primary[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-primary:hover,Ðnote-editor .btn-primary.disabled:focus,Ðnote-editor .btn-primary[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-primary:focus,Ðnote-editor .btn-primary.disabled:active,Ðnote-editor .btn-primary[disabled]:active,Ð fieldset[disabled] .note-editor .btn-primary:active,Ðnote-editor .btn-primary.disabled.active,Ðnote-editor .btn-primary[disabled].active,Ð fieldset[disabled] .note-editor .btn-primary.active {Ð background-color: #428bca;Ð border-color: #357ebd;ÞÐnote-editor .btn-warning {Ð color: #ffffff;Ð background-color: #f0ad4e;Ð border-color: #eea236;ÞÐnote-editor .btn-warning:hover,Ðnote-editor .btn-warning:focus,Ðnote-editor .btn-warning:active,Ðnote-editor .btn-warning.active,Ðopen .dropdown-toggle.note-editor .btn-warning {Ð color: #ffffff;Ð background-color: #ed9c28;Ð border-color: #d58512;ÞÐnote-editor .btn-warning:active,Ðnote-editor .btn-warning.active,Ðopen .dropdown-toggle.note-editor .btn-warning {Ð background-image: none;ÞÐnote-editor .btn-warning.disabled,Ðnote-editor .btn-warning[disabled],Ðfieldset[disabled] .note-editor .btn-warning,Ðnote-editor .btn-warning.disabled:hover,Ðnote-editor .btn-warning[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-warning:hover,Ðnote-editor .btn-warning.disabled:focus,Ðnote-editor .btn-warning[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-warning:focus,Ðnote-editor .btn-warning.disabled:active,Ðnote-editor .btn-warning[disabled]:active,Ð fieldset[disabled] .note-editor .btn-warning:active,Ðnote-editor .btn-warning.disabled.active,Ðnote-editor .btn-warning[disabled].active,Ð fieldset[disabled] .note-editor .btn-warning.active {Ð background-color: #f0ad4e;Ð border-color: #eea236;ÞÐnote-editor .btn-danger {Ð color: #ffffff;Ð background-color: #d9534f;Ð border-color: #d43f3a;ÞÐnote-editor .btn-danger:hover,Ðnote-editor .btn-danger:focus,Ðnote-editor .btn-danger:active,Ð .note-editor .btn-danger.active,Ðopen .dropdown-toggle.note-editor .btn-danger {Ð color: #ffffff;Ð background-color: #d2322d;Ð border-color: #ac2925;ÞÐ .note-editor .btn-danger:active,Ðnote-editor .btn-danger.active,Ð .open .dropdown-toggle.note-editor .btn-danger {Ð background-image: none;ÞÐ .note-editor .btn-danger.disabled,Ðnote-editor .btn-danger[disabled],Ð fieldset[disabled] .note-editor .btn-danger,Ðnote-editor .btn-danger.disabled:hover,Ðnote-editor .btn-danger[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-danger:hover,Ðnote-editor .btn-danger.disabled:focus,Ðnote-editor .btn-danger[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-danger:focus,Ðnote-editor .btn-danger.disabled:active,Ðnote-editor .btn-danger[disabled]:active,Ð fieldset[disabled] .note-editor .btn-danger:active,Ðnote-editor .btn-danger.disabled.active,Ðnote-editor .btn-danger[disabled].active,Ð fieldset[disabled] .note-editor .btn-danger.active {Ð background-color: #d9534f;Ð border-color: #d43f3a;ÞÐnote-editor .btn-success {Ð color: #ffffff;Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÞÐnote-editor .btn-success:hover,Ðnote-editor .btn-success:focus,Ðnote-editor .btn-success:active,Ðnote-editor .btn-success.active,Ðopen .dropdown-toggle.note-editor .btn-success {Ð color: #ffffff;Ð background-color: #47a447;Ð border-color: #398439;ÞÐnote-editor .btn-success:active,Ðnote-editor .btn-success.active,Ðopen .dropdown-toggle.note-editor .btn-success {Ð background-image: none;Ð

}Ðnote-editor .btn-success.disabled,Ðnote-editor .btn-success[disabled],Ðfieldset[disabled] .note-editor .btn-success,Ðnote-editor .btn-success.disabled:hover,Ðnote-editor .btn-success[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-success:hover,Ðnote-editor .btn-success.disabled:focus,Ðnote-editor .btn-success[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-success:focus,Ðnote-editor .btn-success.disabled:active,Ðnote-editor .btn-success[disabled]:active,Ð fieldset[disabled] .note-editor .btn-success:active,Ðnote-editor .btn-success.disabled.active,Ðnote-editor .btn-success[disabled].active,Ð fieldset[disabled] .note-editor .btn-success.active {Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÞÐnote-editor .btn-info {Ð color: #ffffff;Ð background-color: #5bc0de;Ð border-color: #46b8da;ÞÐnote-editor .btn-info:hover,Ðnote-editor .btn-info:focus,Ðnote-editor .btn-info:active,Ðnote-editor .btn-info.active,Ðopen .dropdown-toggle.note-editor .btn-info {Ð color: #ffffff;Ð background-color: #39b3d7;Ð border-color: #269abc;ÞÐnote-editor .btn-info:active,Ðnote-editor .btn-info.active,Ðopen .dropdown-toggle.note-editor .btn-info {Ð background-image: none;ÞÐnote-editor .btn-info.disabled,Ðnote-editor .btn-info[disabled],Ðfieldset[disabled] .note-editor .btn-info,Ðnote-editor .btn-info.disabled:hover,Ðnote-editor .btn-info[disabled]:hover,Ðfieldset[disabled] .note-editor .btn-info:hover,Ðnote-editor .btn-info.disabled:focus,Ðnote-editor .btn-info[disabled]:focus,Ð fieldset[disabled] .note-editor .btn-info:focus,Ðnote-editor .btn-info.disabled:active,Ðnote-editor .btn-info[disabled]:active,Ð fieldset[disabled] .note-editor .btn-info:active,Ðnote-editor .btn-info.disabled.active,Ðnote-editor .btn-info[disabled].active,Ð fieldset[disabled] .note-editor .btn-info.active {Ð background-color: #5bc0de;Ð border-color: #46b8da;ÞÐnote-editor .btn-link {Ð color: #428bca;Ð font-weight: normal;Ð cursor: pointer;Ð border-radius: 0;ÞÐnote-editor .btn-link,Ð .note-editor .btn-link:active,Ðnote-editor .btn-link[disabled],Ð fieldset[disabled] .note-editor .btn-link {Ð background-color: transparent;Ð -webkit-box-shadow: none;Ð box-shadow: none;ÞÐnote-editor .btn-link,Ðnote-editor .btn-link:hover,Ðnote-editor .btn-link:focus,Ðnote-editor .btn-link:active {Ð border-color: transparent;ÞÐnote-editor .btn-link:hover,Ðnote-editor .btn-link:focus {Ð color: #2a6496;Ð text-decoration: underline;Ð background-color: transparent;ÞÐnote-editor .btn-link[disabled]:hover,Ð fieldset[disabled] .note-editor .btn-link:hover,Ðnote-editor .btn-link[disabled]:focus,Ðfieldset[disabled] .note-editor .btn-link:focus {Ð color: #999999;Ð text-decoration: none;ÞÐnote-editor .btn-lg {Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð border-radius: 6px;ÞÐnote-editor .btn-sm,Ðnote-editor .btn-xs {Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÞÐnote-editor .btn-xs {Ð padding: 1px 5px;ÞÐnote-editor .btn-block {Ð display: block;Ð width: 100%;Ð padding-left: 0;Ð padding-right: 0;ÞÐnote-editor .btn-block + .btn-block {Ð margin-top: 5px;Ð }Ðnote-editor input[type="submit"].btn-block,Ðnote-editor input[type="reset"].btn-block,Ðnote-editor input[type="button"].btn-block {Ð width: 100%;ÞÐnote-editor .fade {Ð opacity: 0;Ð -webkit-transition: opacity 0.15s linear;Ð transition: opacity 0.15s linear;ÞÐnote-editor .fade.in {Ð opacity: 1;ÞÐnote-editor .collapse {Ð display: none;ÞÐnote-editor .collapse.in {Ð display: block;ÞÐnote-editor .collapsing {Ð position: relative;Ð height: 0;Ð overflow: hidden;Ð -webkit-transition: height 0.35s ease;Ð transition: height 0.35s ease;ÞÐ@font-face {Ð font-family: 'Glyphicons Halflings';Ð src: url('../fonts/glyphicons-halflings-regular.eot');Ð src: url('../fonts/glyphicons-halflings-regular.eot?#iefix') format('embedded-opentype'), url('../fonts/glyphicons-halflings-regular.woff') format('woff'), url('../fonts/glyphicons-halflings-regular.ttf') format('truetype'), url('../fonts/glyphicons-halflings-regular.svg#glyphicons_halflingsregular') format('svg');ÞÐnote-editor .glyphicon {Ð position: relative;Ð top: 1px;Ð display: inline-block;Ð font-family: 'Glyphicons Halflings';Ð font-style: normal;Ð font-weight: normal;Ð line-height: 1;Ð -webkit-font-smoothing: antialiased;Ð

}ÐÐnote-editor .glyphicon:empty {Ð width: 1em;ÐÐnote-
editor .glyphicon-asterisk:before {Ð content: "\2a";ÐÐnote-editor .glyphicon-
plus:before {Ð content: "\2b";ÐÐnote-editor .glyphicon-euro:before {Ð
content: "\20ac";ÐÐnote-editor .glyphicon-minus:before {Ð content: "\2212";ÐÐ
.note-editor .glyphicon-cloud:before {Ð content: "\2601";ÐÐnote-
editor .glyphicon-envelope:before {Ð content: "\2709";ÐÐnote-
editor .glyphicon-pencil:before {Ð content: "\270f";ÐÐnote-editor .glyphicon-
glass:before {Ð content: "\e001";ÐÐnote-editor .glyphicon-music:before {Ð
content: "\e002";ÐÐnote-editor .glyphicon-search:before {Ð content: "\e003";ÐÐ
.note-editor .glyphicon-heart:before {Ð content: "\e005";ÐÐnote-
editor .glyphicon-star:before {Ð content: "\e006";ÐÐnote-editor .glyphicon-
star-empty:before {Ð content: "\e007";ÐÐnote-editor .glyphicon-user:before {Ð
content: "\e008";ÐÐnote-editor .glyphicon-film:before {Ð content: "\e009";ÐÐ
.note-editor .glyphicon-th-large:before {Ð content: "\e010";ÐÐnote-
editor .glyphicon-th:before {Ð content: "\e011";ÐÐnote-editor .glyphicon-th-
list:before {Ð content: "\e012";ÐÐnote-editor .glyphicon-ok:before {Ð
content: "\e013";ÐÐnote-editor .glyphicon-remove:before {Ð content: "\e014";ÐÐ
.note-editor .glyphicon-zoom-in:before {Ð content: "\e015";ÐÐnote-
editor .glyphicon-zoom-out:before {Ð content: "\e016";ÐÐnote-
editor .glyphicon-off:before {Ð content: "\e017";ÐÐnote-editor .glyphicon-
signal:before {Ð content: "\e018";ÐÐnote-editor .glyphicon-cog:before {Ð
content: "\e019";ÐÐnote-editor .glyphicon-trash:before {Ð content: "\e020";ÐÐ
.note-editor .glyphicon-home:before {Ð content: "\e021";ÐÐnote-
editor .glyphicon-file:before {Ð content: "\e022";ÐÐnote-editor .glyphicon-
time:before {Ð content: "\e023";ÐÐnote-editor .glyphicon-road:before {Ð
content: "\e024";ÐÐnote-editor .glyphicon-download-alt:before {Ð content:
"\e025";ÐÐnote-editor .glyphicon-download:before {Ð content: "\e026";ÐÐnote-
editor .glyphicon-upload:before {Ð content: "\e027";ÐÐnote-editor .glyphicon-
inbox:before {Ð content: "\e028";ÐÐnote-editor .glyphicon-play-circle:before {Ð
  content: "\e029";ÐÐnote-editor .glyphicon-repeat:before {Ð content: "\e030";Ð
}ÐÐnote-editor .glyphicon-refresh:before {Ð content: "\e031";ÐÐnote-
editor .glyphicon-list-alt:before {Ð content: "\e032";ÐÐnote-
editor .glyphicon-lock:before {Ð content: "\e033";ÐÐnote-editor .glyphicon-
flag:before {Ð content: "\e034";ÐÐnote-editor .glyphicon-headphones:before {Ð
content: "\e035";ÐÐnote-editor .glyphicon-volume-off:before {Ð content:
"\e036";ÐÐnote-editor .glyphicon-volume-down:before {Ð content: "\e037";ÐÐ
.note-editor .glyphicon-volume-up:before {Ð content: "\e038";ÐÐnote-
editor .glyphicon-qrcode:before {Ð content: "\e039";ÐÐnote-editor .glyphicon-
barcode:before {Ð content: "\e040";ÐÐnote-editor .glyphicon-tag:before {Ð
content: "\e041";ÐÐnote-editor .glyphicon-tags:before {Ð content: "\e042";ÐÐ
.note-editor .glyphicon-book:before {Ð content: "\e043";ÐÐnote-
editor .glyphicon-bookmark:before {Ð content: "\e044";ÐÐnote-
editor .glyphicon-print:before {Ð content: "\e045";ÐÐnote-editor .glyphicon-
camera:before {Ð content: "\e046";ÐÐnote-editor .glyphicon-font:before {Ð
content: "\e047";ÐÐnote-editor .glyphicon-bold:before {Ð content: "\e048";ÐÐ
.note-editor .glyphicon-italic:before {Ð content: "\e049";ÐÐnote-
editor .glyphicon-text-height:before {Ð content: "\e050";ÐÐnote-
editor .glyphicon-text-width:before {Ð content: "\e051";ÐÐnote-
editor .glyphicon-align-left:before {Ð content: "\e052";ÐÐnote-
editor .glyphicon-align-center:before {Ð content: "\e053";ÐÐnote-
editor .glyphicon-align-right:before {Ð content: "\e054";ÐÐnote-
editor .glyphicon-align-justify:before {Ð content: "\e055";ÐÐnote-
editor .glyphicon-list:before {Ð content: "\e056";ÐÐnote-editor .glyphicon-
indent-left:before {Ð content: "\e057";ÐÐnote-editor .glyphicon-indent-
right:before {Ð content: "\e058";ÐÐnote-editor .glyphicon-facetime-
video:before {Ð content: "\e059";ÐÐnote-editor .glyphicon-picture:before {Ð
content: "\e060";ÐÐnote-editor .glyphicon-map-marker:before {Ð content:
"\e062";ÐÐnote-editor .glyphicon-adjust:before {Ð content: "\e063";ÐÐnote-
editor .glyphicon-tint:before {Ð content: "\e064";ÐÐnote-editor .glyphicon-
edit:before {Ð

content: "\e065";ÐÐnote-editor .glyphicon-share:before {Ð
content: "\e066";ÐÐnote-editor .glyphicon-check:before {Ð content: "\e067";ÐÐ
.note-editor .glyphicon-move:before {Ð content: "\e068";ÐÐnote-
editor .glyphicon-step-backward:before {Ð content: "\e069";ÐÐnote-
editor .glyphicon-fast-backward:before {Ð content: "\e070";ÐÐnote-
editor .glyphicon-backward:before {Ð content: "\e071";ÐÐnote-
editor .glyphicon-play:before {Ð content: "\e072";ÐÐnote-editor .glyphicon-
pause:before {Ð content: "\e073";ÐÐnote-editor .glyphicon-stop:before {Ð
content: "\e074";ÐÐnote-editor .glyphicon-forward:before {Ð content: "\e075";ÐÐ
.note-editor .glyphicon-fast-forward:before {Ð content: "\e076";ÐÐnote-
editor .glyphicon-step-forward:before {Ð content: "\e077";ÐÐnote-
editor .glyphicon-eject:before {Ð content: "\e078";ÐÐnote-editor .glyphicon-
chevron-left:before {Ð content: "\e079";ÐÐnote-editor .glyphicon-chevron-
right:before {Ð content: "\e080";ÐÐnote-editor .glyphicon-plus-sign:before {Ð
content: "\e081";ÐÐnote-editor .glyphicon-minus-sign:before {Ð content:
"\e082";ÐÐnote-editor .glyphicon-remove-sign:before {Ð content: "\e083";ÐÐ
.note-editor .glyphicon-ok-sign:before {Ð content: "\e084";ÐÐnote-
editor .glyphicon-question-sign:before {Ð content: "\e085";ÐÐnote-
editor .glyphicon-info-sign:before {Ð content: "\e086";ÐÐnote-
editor .glyphicon-screenshot:before {Ð content: "\e087";ÐÐnote-
editor .glyphicon-remove-circle:before {Ð content: "\e088";ÐÐnote-
editor .glyphicon-ok-circle:before {Ð content: "\e089";ÐÐnote-
editor .glyphicon-ban-circle:before {Ð content: "\e090";ÐÐnote-
editor .glyphicon-arrow-left:before {Ð content: "\e091";ÐÐnote-
editor .glyphicon-arrow-right:before {Ð content: "\e092";ÐÐnote-
editor .glyphicon-arrow-up:before {Ð content: "\e093";ÐÐnote-
editor .glyphicon-arrow-down:before {Ð content: "\e094";ÐÐnote-
editor .glyphicon-share-alt:before {Ð content: "\e095";ÐÐnote-
editor .glyphicon-resize-full:before {Ð content: "\e096";ÐÐnote-
editor .glyphicon-resize-small:before {Ð content: "\e097";ÐÐnote-
editor .glyphicon-exclamation-sign:before {Ð content: "\e101";ÐÐnote-
editor .glyphicon-gift:before {Ð content: "\e102";ÐÐnote-editor .glyphicon-
leaf:before {Ð content: "\e103";ÐÐnote-editor .glyphicon-fire:before {Ð
content: "\e104";ÐÐnote-editor .glyphicon-eye-open:before {Ð content: "\e105";Ð
}Ðnote-editor .glyphicon-eye-close:before {Ð content: "\e106";ÐÐnote-
editor .glyphicon-warning-sign:before {Ð content: "\e107";ÐÐnote-
editor .glyphicon-plane:before {Ð content: "\e108";ÐÐnote-editor .glyphicon-
calendar:before {Ð content: "\e109";ÐÐnote-editor .glyphicon-random:before {Ð
content: "\e110";ÐÐnote-editor .glyphicon-comment:before {Ð content: "\e111";ÐÐ
.note-editor .glyphicon-magnet:before {Ð content: "\e112";ÐÐnote-
editor .glyphicon-chevron-up:before {Ð content: "\e113";ÐÐnote-
editor .glyphicon-chevron-down:before {Ð content: "\e114";ÐÐnote-
editor .glyphicon-retweet:before {Ð content: "\e115";ÐÐnote-editor .glyphicon-
shopping-cart:before {Ð content: "\e116";ÐÐnote-editor .glyphicon-folder-
close:before {Ð content: "\e117";ÐÐnote-editor .glyphicon-folder-open:before {Ð
content: "\e118";ÐÐnote-editor .glyphicon-resize-vertical:before {Ð
content: "\e119";ÐÐnote-editor .glyphicon-resize-horizontal:before {Ð
content: "\e120";ÐÐnote-editor .glyphicon-hdd:before {Ð content: "\e121";ÐÐ
.note-editor .glyphicon-bullhorn:before {Ð content: "\e122";ÐÐnote-
editor .glyphicon-bell:before {Ð content: "\e123";ÐÐnote-editor .glyphicon-
certificate:before {Ð content: "\e124";ÐÐnote-editor .glyphicon-thumbs-
up:before {Ð content: "\e125";ÐÐnote-editor .glyphicon-thumbs-down:before {Ð
content: "\e126";ÐÐnote-editor .glyphicon-hand-right:before {Ð content:
"\e127";ÐÐnote-editor .glyphicon-hand-left:before {Ð content: "\e128";ÐÐnote-
editor .glyphicon-hand-up:before {Ð content: "\e129";ÐÐnote-editor .glyphicon-
hand-down:before {Ð content: "\e130";ÐÐnote-editor .glyphicon-circle-arrow-
right:before {Ð content: "\e131";ÐÐnote-editor .glyphicon-circle-arrow-
left:before {Ð content: "\e132";ÐÐnote-editor .glyphicon-circle-arrow-
up:before {Ð content: "\e133";ÐÐnote-editor .glyphicon-circle-arrow-
down:before {Ð

content: "\e134";ÐÐnote-editor .glyphicon-globe:before {Ð content: "\e135";ÐÐnote-editor .glyphicon-wrench:before {Ð content: "\e136";ÐÐ .note-editor .glyphicon-tasks:before {Ð content: "\e137";ÐÐnote-editor .glyphicon-filter:before {Ð content: "\e138";ÐÐnote-editor .glyphicon-briefcase:before {Ð content: "\e139";ÐÐnote-editor .glyphicon-fullscreen:before {Ð content: "\e140";ÐÐnote-editor .glyphicon-dashboard:before {Ð content: "\e141";ÐÐnote-editor .glyphicon-paperclip:before {Ð content: "\e142";ÐÐnote-editor .glyphicon-heart-empty:before {Ð content: "\e143";ÐÐnote-editor .glyphicon-link:before {Ð content: "\e144";ÐÐnote-editor .glyphicon-phone:before {Ð content: "\e145";ÐÐ .note-editor .glyphicon-pushpin:before {Ð content: "\e146";ÐÐnote-editor .glyphicon-usd:before {Ð content: "\e148";ÐÐnote-editor .glyphicon-gbp:before {Ð content: "\e149";ÐÐnote-editor .glyphicon-sort:before {Ð content: "\e150";ÐÐnote-editor .glyphicon-sort-by-alphabet:before {Ð content: "\e151";ÐÐnote-editor .glyphicon-sort-by-alphabet-alt:before {Ð content: "\e152";ÐÐnote-editor .glyphicon-sort-by-order:before {Ð content: "\e153";ÐÐ .note-editor .glyphicon-sort-by-order-alt:before {Ð content: "\e154";ÐÐnote-editor .glyphicon-sort-by-attributes:before {Ð content: "\e155";ÐÐnote-editor .glyphicon-sort-by-attributes-alt:before {Ð content: "\e156";ÐÐnote-editor .glyphicon-unchecked:before {Ð content: "\e157";ÐÐnote-editor .glyphicon-expand:before {Ð content: "\e158";ÐÐnote-editor .glyphicon-collapse-down:before {Ð content: "\e159";ÐÐnote-editor .glyphicon-collapse-up:before {Ð content: "\e160";ÐÐnote-editor .glyphicon-log-in:before {Ð content: "\e161";ÐÐnote-editor .glyphicon-flash:before {Ð content: "\e162";ÐÐ .note-editor .glyphicon-log-out:before {Ð content: "\e163";ÐÐnote-editor .glyphicon-new-window:before {Ð content: "\e164";ÐÐnote-editor .glyphicon-record:before {Ð content: "\e165";ÐÐnote-editor .glyphicon-save:before {Ð content: "\e166";ÐÐnote-editor .glyphicon-open:before {Ð content: "\e167";ÐÐnote-editor .glyphicon-saved:before {Ð content: "\e168";ÐÐ .note-editor .glyphicon-import:before {Ð content: "\e169";ÐÐnote-editor .glyphicon-export:before {Ð content: "\e170";ÐÐnote-editor .glyphicon-send:before {Ð content: "\e171";ÐÐnote-editor .glyphicon-floppy-disk:before {Ð content: "\e172";ÐÐnote-editor .glyphicon-floppy-saved:before {Ð content: "\e173";ÐÐnote-editor .glyphicon-floppy-remove:before {Ð content: "\e174";ÐÐ .note-editor .glyphicon-floppy-save:before {Ð content: "\e175";ÐÐnote-editor .glyphicon-floppy-open:before {Ð content: "\e176";ÐÐnote-editor .glyphicon-credit-card:before {Ð content: "\e177";ÐÐnote-editor .glyphicon-transfer:before {Ð content: "\e178";ÐÐnote-editor .glyphicon-cutlery:before {Ð content: "\e179";ÐÐnote-editor .glyphicon-header:before {Ð content: "\e180";ÐÐnote-editor .glyphicon-compressed:before {Ð content: "\e181";ÐÐnote-editor .glyphicon-earphone:before {Ð content: "\e182";ÐÐnote-editor .glyphicon-phone-alt:before {Ð content: "\e183";ÐÐnote-editor .glyphicon-tower:before {Ð content: "\e184";ÐÐnote-editor .glyphicon-stats:before {Ð content: "\e185";ÐÐnote-editor .glyphicon-sd-video:before {Ð content: "\e186";ÐÐnote-editor .glyphicon-hd-video:before {Ð content: "\e187";Ð }Ðnote-editor .glyphicon-subtitles:before {Ð content: "\e188";ÐÐnote-editor .glyphicon-sound-stereo:before {Ð content: "\e189";ÐÐnote-editor .glyphicon-sound-dolby:before {Ð content: "\e190";ÐÐnote-editor .glyphicon-sound-5-1:before {Ð content: "\e191";ÐÐnote-editor .glyphicon-sound-6-1:before {Ð content: "\e192";ÐÐnote-editor .glyphicon-sound-7-1:before {Ð content: "\e193";ÐÐnote-editor .glyphicon-copyright-mark:before {Ð content: "\e194";ÐÐnote-editor .glyphicon-registration-mark:before {Ð content: "\e195";ÐÐnote-editor .glyphicon-cloud-download:before {Ð content: "\e197";ÐÐnote-editor .glyphicon-cloud-upload:before {Ð content: "\e198";ÐÐnote-editor .glyphicon-tree-conifer:before {Ð content: "\e199";ÐÐnote-editor .glyphicon-tree-deciduous:before {Ð content: "\e200";ÐÐnote-editor .caret {Ð display: inline-block;Ð width: 0;Ð height: 0;Ð margin-left: 2px;Ð vertical-align: middle;Ð border-top: 4px solid #000000;Ð border-right: 4px solid transparent;Ð

border-left: 4px solid transparent;Ð border-bottom: 0 dotted;ÞÐnote-editor .dropdown {Ð position: relative;ÞÐnote-editor .dropdown-toggle:focus {Ð outline: 0;ÞÐnote-editor .dropdown-menu {Ð position: absolute;Ð top: 100%;Ð left: 0;Ð z-index: 1000;Ð display: none;Ð float: left;Ð min-width: 160px;Ð padding: 5px 0;Ð margin: 2px 0 0;Ð list-style: none;Ð font-size: 14px;Ð background-color: #ffffff;Ð border: 1px solid #cccccc;Ð border: 1px solid rgba(0, 0, 0, 0.15);Ð border-radius: 4px;Ð -webkit-box-shadow: 0 6px 12px rgba(0, 0, 0, 0.175);Ð box-shadow: 0 6px 12px rgba(0, 0, 0, 0.175);Ð background-clip: padding-box;ÞÐnote-editor .dropdown-menu.pull-right {Ð right: 0;Ð left: auto;ÞÐnote-editor .dropdown-menu .divider {Ð height: 1px;Ð margin: 9px 0;Ð overflow: hidden;Ð background-color: #e5e5e5;ÞÐnote-editor .dropdown-menu > li > a {Ð display: block;Ð padding: 3px 20px;Ð clear: both;Ð font-weight: normal;Ð line-height: 1.428571429;Ð color: #333333;Ð white-space: nowrap;ÞÐnote-editor .dropdown-menu > li > a:hover,Ðnote-editor .dropdown-menu > li > a:focus {Ð text-decoration: none;Ð color: #262626;Ð background-color: #f5f5f5;ÞÐnote-editor .dropdown-menu > .active > a,Ðnote-editor .dropdown-menu > .active > a:hover,Ðnote-editor .dropdown-menu > .active > a:focus {Ð color: #ffffff;Ð text-decoration: none;Ð outline: 0;Ð background-color: #428bca;ÞÐnote-editor .dropdown-menu > .disabled > a,Ðnote-editor .dropdown-menu > .disabled > a:hover,Ðnote-editor .dropdown-menu > .disabled > a:focus {Ð color: #999999;ÞÐnote-editor .dropdown-menu > .disabled > a:hover,Ðnote-editor .dropdown-menu > .disabled > a:focus {Ð text-decoration: none;Ð background-color: transparent;Ð background-image: none;Ð filter: progid:DXImageTransform.Microsoft.gradient(enabled = false);Ð cursor: not-allowed;ÞÐnote-editor .open > .dropdown-menu {Ð display: block;ÞÐ .note-editor .open > a {Ð outline: 0;ÞÐnote-editor .dropdown-header {Ð display: block;Ð padding: 3px 20px;Ð font-size: 12px;Ð line-height: 1.428571429;Ð color: #999999;ÞÐnote-editor .dropdown-backdrop {Ð position: fixed;Ð left: 0;Ð right: 0;Ð bottom: 0;Ð top: 0;Ð z-index: 990;ÞÐnote-editor .pull-right > .dropdown-menu {Ð right: 0;Ð left: auto;ÞÐnote-editor .dropup .caret,Ðnote-editor .navbar-fixed-bottom .dropdown .caret {Ð border-top: 0 dotted;Ð border-bottom: 4px solid #000000;Ð content: "";ÞÐnote-editor .dropup .dropdown-menu,Ðnote-editor .navbar-fixed-bottom .dropdown .dropdown-menu {Ð top: auto;Ð bottom: 100%;Ð margin-bottom: 1px;Þ@media (min-width: 768px) {Ð .note-editor .navbar-right .dropdown-menu {Ð right: 0;Ð left: auto;Ð }ÞÐbtn-default .note-editor .caret {Ð border-top-color: #333333;ÞÐbtn-primary .note-editor .caret,Ðbtn-success .note-editor .caret,Ðbtn-warning .note-editor .caret,Ðbtn-danger .note-editor .caret,Ðbtn-info .note-editor .caret {Ð border-top-color: #fff;ÞÐnote-editor .dropup .btn-default .caret {Ð border-bottom-color: #333333;ÞÐnote-editor .dropup .btn-primary .caret,Ðnote-editor .dropup .btn-success .caret,Ð .note-editor .dropup .btn-warning .caret,Ðnote-editor .dropup .btn-danger .caret,Ðnote-editor .dropup .btn-info .caret {Ð border-bottom-color: #fff;ÞÐnote-editor .btn-group,Ðnote-editor .btn-group-vertical {Ð position: relative;Ð display: inline-block;Ð vertical-align: middle;ÞÐnote-editor .btn-group > .btn,Ðnote-editor .btn-group-vertical > .btn {Ð position: relative;Ð float: left;ÞÐnote-editor .btn-group > .btn:hover,Ðnote-editor .btn-group-vertical > .btn:hover,Ðnote-editor .btn-group > .btn:focus,Ðnote-editor .btn-group-vertical > .btn:focus,Ðnote-editor .btn-group > .btn:active,Ðnote-editor .btn-group-vertical > .btn:active,Ðnote-editor .btn-group > .btn.active,Ðnote-editor .btn-group-vertical > .btn.active {Ð z-index: 2;ÞÐ .note-editor .btn-group > .btn:focus,Ðnote-editor .btn-group-vertical > .btn:focus {Ð outline: none;ÞÐnote-editor .btn-group .btn + .btn,Ðnote-editor .btn-group .btn + .btn-group,Ðnote-editor .btn-group .btn-group + .btn,Ð .note-editor .btn-group .btn-group + .btn-group {Ð margin-left: -1px;ÞÐnote-editor .btn-toolbar:before,Ðnote-editor .btn-toolbar:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .btn-toolbar:after {Ð clear: both;ÞÐnote-editor .btn-toolbar:before,Ðnote-editor .btn-toolbar:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÞÐnote-editor .btn-toolbar:after {Ð

clear: both;ÞÞnote-editor .btn-toolbar .btn-group {Þ float: left;ÞÞnote-editor .btn-toolbar > .btn + .btn,Þnote-editor .btn-toolbar > .btn-group + .btn,Þnote-editor .btn-toolbar > .btn + .btn-group,Þnote-editor .btn-toolbar > .btn-group + .btn-group {Þ margin-left: 5px;ÞÞnote-editor .btn-group > .btn:not(:first-child):not(:last-child):not(.dropdown-toggle) {Þ border-radius: 0;ÞÞnote-editor .btn-group > .btn:first-child {Þ margin-left: 0;ÞÞnote-editor .btn-group > .btn:first-child:not(:last-child):not(.dropdown-toggle) {Þ border-bottom-right-radius: 0;Þ border-top-right-radius: 0;ÞÞnote-editor .btn-group > .btn:last-child:not(:first-child),Þ .note-editor .btn-group > .dropdown-toggle:not(:first-child) {Þ border-bottom-left-radius: 0;Þ border-top-left-radius: 0;ÞÞnote-editor .btn-group > .btn-group {Þ float: left;ÞÞnote-editor .btn-group > .btn-group:not(:first-child):not(:last-child) > .btn {Þ border-radius: 0;ÞÞnote-editor .btn-group > .btn-group:first-child > .btn:last-child,Þnote-editor .btn-group > .btn-group:first-child > .dropdown-toggle {Þ border-bottom-right-radius: 0;Þ border-top-right-radius: 0;ÞÞnote-editor .btn-group > .btn-group:last-child > .btn:first-child {Þ border-bottom-left-radius: 0;Þ border-top-left-radius: 0;ÞÞnote-editor .btn-group .dropdown-toggle:active,Þnote-editor .btn-group.open .dropdown-toggle {Þ outline: 0;ÞÞnote-editor .btn-group-xs > .btn {Þ padding: 5px 10px;Þ font-size: 12px;Þ line-height: 1.5;Þ border-radius: 3px;Þ padding: 1px 5px;ÞÞnote-editor .btn-group-sm > .btn {Þ padding: 5px 10px;Þ font-size: 12px;Þ line-height: 1.5;Þ border-radius: 3px;ÞÞnote-editor .btn-group-lg > .btn {Þ padding: 10px 16px;Þ font-size: 18px;Þ line-height: 1.33;Þ border-radius: 6px;ÞÞnote-editor .btn-group > .btn + .dropdown-toggle {Þ padding-left: 5px;Þ padding-right: 5px;ÞÞnote-editor .btn-group > .btn-lg + .dropdown-toggle {Þ padding-left: 12px;Þ padding-right: 12px;ÞÞnote-editor .btn-group.open .dropdown-toggle {Þ -webkit-box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);Þ box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);ÞÞ .note-editor .btn .caret {Þ margin-left: 0;ÞÞnote-editor .btn-lg .caret {Þ border-width: 5px 5px 0;Þ border-bottom-width: 0;ÞÞnote-editor .dropup .btn-lg .caret {Þ border-width: 0 5px 5px;ÞÞnote-editor .btn-group-vertical > .btn,Þ .note-editor .btn-group-vertical > .btn-group {Þ display: block;Þ float: none;Þ width: 100%;Þ max-width: 100%;ÞÞnote-editor .btn-group-vertical > .btn-group:before,Þnote-editor .btn-group-vertical > .btn-group:after {Þ content: " ";Þ /* 1 */Þ display: table;Þ /* 2 */ÞÞnote-editor .btn-group-vertical > .btn-group:after {Þ clear: both;ÞÞnote-editor .btn-group-vertical > .btn-group:before,Þnote-editor .btn-group-vertical > .btn-group:after {Þ content: " ";Þ /* 1 */Þ display: table;Þ /* 2 */ÞÞnote-editor .btn-group-vertical > .btn-group:after {Þ clear: both;ÞÞnote-editor .btn-group-vertical > .btn-group > .btn {Þ float: none;ÞÞnote-editor .btn-group-vertical > .btn + .btn,Þ .note-editor .btn-group-vertical > .btn + .btn-group,Þnote-editor .btn-group-vertical > .btn-group + .btn,Þnote-editor .btn-group-vertical > .btn-group + .btn-group {Þ margin-top: -1px;Þ margin-left: 0;ÞÞnote-editor .btn-group-vertical > .btn:not(:first-child):not(:last-child) {Þ border-radius: 0;ÞÞnote-editor .btn-group-vertical > .btn:first-child:not(:last-child) {Þ border-top-right-radius: 4px;Þ border-bottom-right-radius: 0;Þ border-bottom-left-radius: 0;ÞÞnote-editor .btn-group-vertical > .btn:last-child:not(:first-child) {Þ border-bottom-left-radius: 4px;Þ border-top-right-radius: 0;Þ border-top-left-radius: 0;ÞÞnote-editor .btn-group-vertical > .btn-group:not(:first-child):not(:last-child) > .btn {Þ border-radius: 0;ÞÞnote-editor .btn-group-vertical > .btn-group:first-child > .btn:last-child,Þnote-editor .btn-group-vertical > .btn-group:first-child > .dropdown-toggle {Þ border-bottom-right-radius: 0;Þ border-bottom-left-radius: 0;ÞÞnote-editor .btn-group-vertical > .btn-group:last-child > .btn:first-child {Þ border-top-right-radius: 0;Þ border-top-left-radius: 0;ÞÞnote-editor .btn-group-justified {Þ display: table;Þ width: 100%;Þ table-layout: fixed;Þ border-collapse: separate;ÞÞnote-editor .btn-group-justified .btn {Þ float: none;Þ display: table-cell;Þ width: 1%;ÞÞnote-editor [data-toggle="buttons"] > .btn > input[type="radio"],Þnote-editor [data-toggle="buttons"] > .btn > input[type="checkbox"] {Þ

display: none;ÐÐnote-editor .input-group {Ð
position: relative;Ð display: table;Ð border-collapse: separate;ÐÐnote-
editor .input-group.col {Ð float: none;Ð padding-left: 0;Ð padding-right: 0;ÐÐ
.note-editor .input-group .form-control {Ð width: 100%;Ð margin-bottom: 0;ÐÐ
.note-editor .input-group-lg > .form-control,Ðnote-editor .input-group-lg
> .input-group-addon,Ðnote-editor .input-group-lg > .input-group-btn > .btn {Ð
height: 45px;Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð
border-radius: 6px;ÐÐselect.note-editor .input-group-lg > .form-control,Ð
select.note-editor .input-group-lg > .input-group-addon,Ðselect.note-
editor .input-group-lg > .input-group-btn > .btn {Ð height: 45px;Ð line-
height: 45px;ÐÐtextarea.note-editor .input-group-lg > .form-control,Ð
textarea.note-editor .input-group-lg > .input-group-addon,Ðtextarea.note-
editor .input-group-lg > .input-group-btn > .btn {Ð height: auto;ÐÐnote-
editor .input-group-sm > .form-control,Ðnote-editor .input-group-sm > .input-
group-addon,Ðnote-editor .input-group-sm > .input-group-btn > .btn {Ð height:
30px;Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-
radius: 3px;ÐÐselect.note-editor .input-group-sm > .form-control,Ðselect.note-
editor .input-group-sm > .input-group-addon,Ðselect.note-editor .input-group-
sm > .input-group-btn > .btn {Ð height: 30px;Ð line-height: 30px;ÐÐ
textarea.note-editor .input-group-sm > .form-control,Ðtextarea.note-
editor .input-group-sm > .input-group-addon,Ðtextarea.note-editor .input-group-
sm > .input-group-btn > .btn {Ð height: auto;ÐÐnote-editor .input-group-addon,Ð
.note-editor .input-group-btn,Ðnote-editor .input-group .form-control {Ð
display: table-cell;ÐÐnote-editor .input-group-addon:not(:first-
child):not(:last-child),Ðnote-editor .input-group-btn:not(:first-
child):not(:last-child),Ðnote-editor .input-group .form-control:not(:first-
child):not(:last-child) {Ð border-radius: 0;ÐÐnote-editor .input-group-addon,Ð
.note-editor .input-group-btn {Ð width: 1%;Ð white-space: nowrap;Ð vertical-
align: middle;ÐÐnote-editor .input-group-addon {Ð padding: 6px 12px;Ð font-
size: 14px;Ð font-weight: normal;Ð line-height: 1;Ð color: #555555;Ð text-
align: center;Ð background-color: #eeeeee;Ð border: 1px solid #cccccc;Ð
border-radius: 4px;ÐÐnote-editor .input-group-addon.input-sm {Ð padding: 5px
10px;Ð font-size: 12px;Ð border-radius: 3px;ÐÐnote-editor .input-group-
addon.input-lg {Ð padding: 10px 16px;Ð font-size: 18px;Ð border-radius: 6px;ÐÐ
.note-editor .input-group-addon input[type="radio"],Ðnote-editor .input-group-
addon input[type="checkbox"] {Ð margin-top: 0;ÐÐnote-editor .input-
group .form-control:first-child,Ðnote-editor .input-group-addon:first-child,Ð
.note-editor .input-group-btn:first-child > .btn,Ðnote-editor .input-group-
btn:first-child > .dropdown-toggle,Ðnote-editor .input-group-btn:last-child
> .btn:not(:last-child):not(.dropdown-toggle) {Ð border-bottom-right-radius:
0;Ð border-top-right-radius: 0;ÐÐnote-editor .input-group-addon:first-child {Ð
border-right: 0;ÐÐnote-editor .input-group .form-control:last-child,Ðnote-
editor .input-group-addon:last-child,Ðnote-editor .input-group-btn:last-child
> .btn,Ðnote-editor .input-group-btn:last-child > .dropdown-toggle,Ðnote-
editor .input-group-btn:first-child > .btn:not(:first-child) {Ð border-bottom-
left-radius: 0;Ð border-top-left-radius: 0;ÐÐnote-editor .input-group-
addon:last-child {Ð border-left: 0;ÐÐnote-editor .input-group-btn {Ð
position: relative;Ð white-space: nowrap;ÐÐnote-editor .input-group-btn:first-
child > .btn {Ð margin-right: -1px;ÐÐnote-editor .input-group-btn:last-child
> .btn {Ð margin-left: -1px;ÐÐnote-editor .input-group-btn > .btn {Ð
position: relative;ÐÐnote-editor .input-group-btn > .btn + .btn {Ð margin-
left: -4px;ÐÐnote-editor .input-group-btn > .btn:hover,Ðnote-editor .input-
group-btn > .btn:active {Ð z-index: 2;ÐÐnote-editor .nav {Ð margin-bottom: 0;Ð
padding-left: 0;Ð list-style: none;ÐÐnote-editor .nav:before,Ðnote-
editor .nav:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-
editor .nav:after {Ð clear: both;ÐÐnote-editor .nav:before,Ðnote-
editor .nav:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-
editor .nav:after {Ð clear: both;ÐÐnote-editor .nav > li {Ð position:
relative;Ð display: block;ÐÐnote-editor .nav > li > a {Ð position: relative;Ð
display: block;Ð

padding: 10px 15px;ÐÐnote-editor .nav > li > a:hover,Ðnote-editor .nav > li > a:focus {Ð text-decoration: none;Ð background-color: #eeeeee;ÐÐnote-editor .nav > li.disabled > a {Ð color: #999999;ÐÐnote-editor .nav > li.disabled > a:hover,Ðnote-editor .nav > li.disabled > a:focus {Ð color: #999999;Ð text-decoration: none;Ð background-color: transparent;Ð cursor: not-allowed;ÐÐnote-editor .nav .open > a,Ðnote-editor .nav .open > a:hover,Ðnote-editor .nav .open > a:focus {Ð background-color: #eeeeee;Ð border-color: #428bca;ÐÐnote-editor .nav .open > a .caret,Ðnote-editor .nav .open > a:hover .caret,Ðnote-editor .nav .open > a:focus .caret {Ð border-top-color: #2a6496;Ð border-bottom-color: #2a6496;ÐÐnote-editor .nav .nav-divider {Ð height: 1px;Ð margin: 9px 0;Ð overflow: hidden;Ð background-color: #e5e5e5;ÐÐnote-editor .nav > li > a > img {Ð max-width: none;ÐÐnote-editor .nav-tabs {Ð border-bottom: 1px solid #dddddd;ÐÐnote-editor .nav-tabs > li {Ð float: left;Ð margin-bottom: -1px;ÐÐnote-editor .nav-tabs > li > a {Ð margin-right: 2px;Ð line-height: 1.428571429;Ð border: 1px solid transparent;Ð border-radius: 4px 4px 0 0;ÐÐnote-editor .nav-tabs > li > a:hover {Ð border-color: #eeeeee #eeeeee #dddddd;ÐÐnote-editor .nav-tabs > li.active > a,Ðnote-editor .nav-tabs > li.active > a:hover,Ðnote-editor .nav-tabs > li.active > a:focus {Ð color: #555555;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-bottom-color: transparent;Ð cursor: default;ÐÐnote-editor .nav-tabs.nav-justified {Ð width: 100%;Ð border-bottom: 0;ÐÐnote-editor .nav-tabs.nav-justified > li {Ð float: none;ÐÐnote-editor .nav-tabs.nav-justified > li > a {Ð text-align: center;Ð margin-bottom: 5px;ÐÐ@media (min-width: 768px) {Ð .note-editor .nav-tabs.nav-justified > li {Ð display: table-cell;Ð width: 1%;Ð }Ð .note-editor .nav-tabs.nav-justified > li > a {Ð margin-bottom: 0;Ð }ÐÐnote-editor .nav-tabs.nav-justified > li > a {Ð margin-right: 0;Ð border-radius: 4px;ÐÐnote-editor .nav-tabs.nav-justified > .active > a,Ðnote-editor .nav-tabs.nav-justified > .active > a:hover,Ðnote-editor .nav-tabs.nav-justified > .active > a:focus {Ð border: 1px solid #dddddd;ÐÐ@media (min-width: 768px) {Ð .note-editor .nav-tabs.nav-justified > li > a {Ð border-bottom: 1px solid #dddddd;Ð border-radius: 4px 4px 0 0;Ð }Ð .note-editor .nav-tabs.nav-justified > .active > a,Ð .note-editor .nav-tabs.nav-justified > .active > a:hover,Ð .note-editor .nav-tabs.nav-justified > .active > a:focus {Ð border-bottom-color: #ffffff;Ð }ÐÐnote-editor .nav-pills > li {Ð float: left;ÐÐnote-editor .nav-pills > li > a {Ð border-radius: 4px;ÐÐnote-editor .nav-pills > li + li {Ð margin-left: 2px;ÐÐnote-editor .nav-pills > li.active > a,Ðnote-editor .nav-pills > li.active > a:hover,Ðnote-editor .nav-pills > li.active > a:focus {Ð color: #ffffff;Ð background-color: #428bca;ÐÐnote-editor .nav-pills > li.active > a .caret,Ðnote-editor .nav-pills > li.active > a:hover .caret,Ðnote-editor .nav-pills > li.active > a:focus .caret {Ð border-top-color: #ffffff;Ð border-bottom-color: #ffffff;ÐÐnote-editor .nav-stacked > li {Ð float: none;ÐÐnote-editor .nav-stacked > li + li {Ð margin-top: 2px;Ð margin-left: 0;ÐÐnote-editor .nav-justified {Ð width: 100%;ÐÐnote-editor .nav-justified > li {Ð float: none;ÐÐnote-editor .nav-justified > li > a {Ð text-align: center;Ð margin-bottom: 5px;ÐÐ@media (min-width: 768px) {Ð .note-editor .nav-justified > li {Ð display: table-cell;Ð width: 1%;Ð }Ð .note-editor .nav-justified > li > a {Ð margin-bottom: 0;Ð }ÐÐnote-editor .nav-tabs-justified {Ð border-bottom: 0;ÐÐnote-editor .nav-tabs-justified > li > a {Ð margin-right: 0;Ð border-radius: 4px;ÐÐnote-editor .nav-tabs-justified > .active > a,Ðnote-editor .nav-tabs-justified > .active > a:hover,Ðnote-editor .nav-tabs-justified > .active > a:focus {Ð border: 1px solid #dddddd;ÐÐ @media (min-width: 768px) {Ð .note-editor .nav-tabs-justified > li > a {Ð border-bottom: 1px solid #dddddd;Ð border-radius: 4px 4px 0 0;Ð }Ð .note-editor .nav-tabs-justified > .active > a,Ð .note-editor .nav-tabs-justified > .active > a:hover,Ð .note-editor .nav-tabs-justified > .active > a:focus {Ð border-bottom-color: #ffffff;Ð }ÐÐnote-editor .tab-content > .tab-pane {Ð display: none;ÐÐnote-editor .tab-content > .active {Ð display: block;ÐÐnote-editor .nav .caret {Ð border-top-color: #428bca;Ð border-bottom-color: #428bca;Ð

}Ðnote-editor .nav a:hover .caret {Ð border-top-color: #2a6496;Ð
border-bottom-color: #2a6496;ÐÐnote-editor .nav-tabs .dropdown-menu {Ð margin-
top: -1px;Ð border-top-right-radius: 0;Ð border-top-left-radius: 0;ÐÐnote-
editor .navbar {Ð position: relative;Ð z-index: 1000;Ð min-height: 50px;Ð
margin-bottom: 20px;Ð border: 1px solid transparent;ÐÐnote-
editor .navbar:before,Ðnote-editor .navbar:after {Ð content: " ";Ð /* 1 */Ð
display: table;Ð /* 2 */ÐÐnote-editor .navbar:after {Ð clear: both;ÐÐnote-
editor .navbar:before,Ðnote-editor .navbar:after {Ð content: " ";Ð /* 1 */Ð
display: table;Ð /* 2 */ÐÐnote-editor .navbar:after {Ð clear: both;ÐÐmedia
(min-width: 768px) {Ð .note-editor .navbar {Ð border-radius: 4px;Ð }ÐÐnote-
editor .navbar-header:before,Ðnote-editor .navbar-header:after {Ð content: "
";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-editor .navbar-header:after {Ð
clear: both;ÐÐnote-editor .navbar-header:before,Ðnote-editor .navbar-
header:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-
editor .navbar-header:after {Ð clear: both;ÐÐmedia (min-width: 768px) {Ð
  .note-editor .navbar-header {Ð float: left;Ð }ÐÐnote-editor .navbar-
collapse {Ð max-height: 340px;Ð overflow-x: visible;Ð padding-right: 15px;Ð
padding-left: 15px;Ð border-top: 1px solid transparent;Ð box-shadow: inset 0
1px 0 rgba(255, 255, 255, 0.1);Ð -webkit-overflow-scrolling: touch;ÐÐnote-
editor .navbar-collapse:before,Ðnote-editor .navbar-collapse:after {Ð
content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-editor .navbar-
collapse:after {Ð clear: both;ÐÐnote-editor .navbar-collapse:before,Ðnote-
editor .navbar-collapse:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /*
2 */ÐÐnote-editor .navbar-collapse:after {Ð clear: both;ÐÐnote-editor .navbar-
collapse.in {Ð overflow-y: auto;ÐÐmedia (min-width: 768px) {Ð .note-
editor .navbar-collapse {Ð width: auto;Ð border-top: 0;Ð box-shadow:
none;Ð }Ð .note-editor .navbar-collapse.collapse {Ð display: block !
important;Ð height: auto !important;Ð padding-bottom: 0;Ð overflow:
visible !important;Ð }Ð .note-editor .navbar-collapse.in {Ð overflow-y:
visible;Ð }Ð .note-editor .navbar-collapse .navbar-nav.navbar-left:first-
child {Ð margin-left: -15px;Ð }Ð .note-editor .navbar-collapse .navbar-
nav.navbar-right:last-child {Ð margin-right: -15px;Ð }Ð .note-
editor .navbar-collapse .navbar-text:last-child {Ð margin-right: 0;Ð }ÐÐ
.note-editor .container > .navbar-header,Ðnote-editor .container > .navbar-
collapse {Ð margin-right: -15px;Ð margin-left: -15px;ÐÐmedia (min-width:
768px) {Ð .note-editor .container > .navbar-header,Ð .note-editor .container
> .navbar-collapse {Ð margin-right: 0;Ð margin-left: 0;Ð }ÐÐnote-
editor .navbar-static-top {Ð border-width: 0 0 1px;ÐÐmedia (min-width: 768px)
{Ð .note-editor .navbar-static-top {Ð border-radius: 0;Ð }ÐÐnote-
editor .navbar-fixed-top,Ðnote-editor .navbar-fixed-bottom {Ð position: fixed;Ð
  right: 0;Ð left: 0;Ð border-width: 0 0 1px;ÐÐmedia (min-width: 768px) {Ð
  .note-editor .navbar-fixed-top,Ð .note-editor .navbar-fixed-bottom {Ð
border-radius: 0;Ð }ÐÐnote-editor .navbar-fixed-top {Ð z-index: 1030;Ð top: 0;Ð
}Ðnote-editor .navbar-fixed-bottom {Ð bottom: 0;Ð margin-bottom: 0;ÐÐnote-
editor .navbar-brand {Ð float: left;Ð padding: 15px 15px;Ð font-size: 18px;Ð
line-height: 20px;ÐÐnote-editor .navbar-brand:hover,Ðnote-editor .navbar-
brand:focus {Ð text-decoration: none;ÐÐmedia (min-width: 768px) {Ð .navbar
> .container .note-editor .navbar-brand {Ð margin-left: -15px;Ð }ÐÐnote-
editor .navbar-toggle {Ð position: relative;Ð float: right;Ð margin-right:
15px;Ð padding: 9px 10px;Ð margin-top: 8px;Ð margin-bottom: 8px;Ð background-
color: transparent;Ð border: 1px solid transparent;Ð border-radius: 4px;ÐÐ
.note-editor .navbar-toggle .icon-bar {Ð display: block;Ð width: 22px;Ð
height: 2px;Ð border-radius: 1px;ÐÐnote-editor .navbar-toggle .icon-bar
+ .icon-bar {Ð margin-top: 4px;ÐÐmedia (min-width: 768px) {Ð .note-
editor .navbar-toggle {Ð display: none;Ð }ÐÐnote-editor .navbar-nav {Ð
margin: 7.5px -15px;ÐÐnote-editor .navbar-nav > li > a {Ð padding-top: 10px;Ð
padding-bottom: 10px;Ð line-height: 20px;ÐÐmedia (max-width: 767px) {Ð .note-
editor .navbar-nav .open .dropdown-menu {Ð position: static;Ð float: none;Ð
    width: auto;Ð margin-top: 0;Ð background-color: transparent;Ð
border: 0;Ð

box-shadow: none;Ð }Ð .note-editor .navbar-nav .open .dropdown-menu > li > a,Ð .note-editor .navbar-nav .open .dropdown-menu .dropdown-header {Ð padding: 5px 15px 5px 25px;Ð }Ð .note-editor .navbar-nav .open .dropdown-menu > li > a {Ð line-height: 20px;Ð }Ð .note-editor .navbar-nav .open .dropdown-menu > li > a:hover,Ð .note-editor .navbar-nav .open .dropdown-menu > li > a:focus {Ð background-image: none;Ð }ÐÐ @media (min-width: 768px) {Ð .note-editor .navbar-nav {Ð float: left;Ð margin: 0;Ð }Ð .note-editor .navbar-nav > li {Ð float: left;Ð }Ð .note-editor .navbar-nav > li > a {Ð padding-top: 15px;Ð padding-bottom: 15px;Ð }}ÐÐ@media (min-width: 768px) {Ð .note-editor .navbar-left {Ð float: left !important;Ð }Ð .note-editor .navbar-right {Ð float: right !important;Ð }}ÐÐ .note-editor .navbar-form {Ð margin-left: -15px;Ð margin-right: -15px;Ð padding: 10px 15px;Ð border-top: 1px solid transparent;Ð border-bottom: 1px solid transparent;Ð -webkit-box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.1), 0 1px 0 rgba(255, 255, 255, 0.1);Ð box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.1), 0 1px 0 rgba(255, 255, 255, 0.1);Ð margin-top: 8px;Ð margin-bottom: 8px;}ÐÐ@media (min-width: 768px) {Ð .note-editor .navbar-form .form-group {Ð display: inline-block;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .note-editor .navbar-form .form-control {Ð display: inline-block;Ð }Ð .note-editor .navbar-form .radio,Ð .note-editor .navbar-form .checkbox {Ð display: inline-block;Ð margin-top: 0;Ð margin-bottom: 0;Ð padding-left: 0;Ð }Ð .note-editor .navbar-form .radio input[type="radio"],Ð .note-editor .navbar-form .checkbox input[type="checkbox"] {Ð float: none;Ð margin-left: 0;Ð }}ÐÐ@media (max-width: 767px) {Ð .note-editor .navbar-form .form-group {Ð margin-bottom: 5px;Ð }}ÐÐ@media (min-width: 768px) {Ð .note-editor .navbar-form {Ð width: auto;Ð border: 0;Ð margin-left: 0;Ð margin-right: 0;Ð padding-top: 0;Ð padding-bottom: 0;Ð -webkit-box-shadow: none;Ð box-shadow: none;Ð }}ÐÐ .note-editor .navbar-nav > li > .dropdown-menu {Ð margin-top: 0;Ð border-top-right-radius: 0;Ð border-top-left-radius: 0;}ÐÐnote-editor .navbar-fixed-bottom .navbar-nav > li > .dropdown-menu {Ð border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;}ÐÐnote-editor .navbar-nav.pull-right > li > .dropdown-menu,Ðnote-editor .navbar-nav > li > .dropdown-menu.pull-right {Ð left: auto;Ð right: 0;}ÐÐnote-editor .navbar-btn {Ð margin-top: 8px;Ð margin-bottom: 8px;}ÐÐnote-editor .navbar-text {Ð float: left;Ð margin-top: 15px;Ð margin-bottom: 15px;}ÐÐ@media (min-width: 768px) {Ð .note-editor .navbar-text {Ð margin-left: 15px;Ð margin-right: 15px;Ð }}ÐÐnote-editor .navbar-default {Ð background-color: #f8f8f8;Ð border-color: #e7e7e7;}ÐÐnote-editor .navbar-default .navbar-brand {Ð color: #777777;}ÐÐnote-editor .navbar-default .navbar-brand:hover,Ðnote-editor .navbar-default .navbar-brand:focus {Ð color: #5e5e5e;Ð background-color: transparent;}ÐÐnote-editor .navbar-default .navbar-text {Ð color: #777777;}ÐÐnote-editor .navbar-default .navbar-nav > li > a {Ð color: #777777;}ÐÐnote-editor .navbar-default .navbar-nav > li > a:hover,Ðnote-editor .navbar-default .navbar-nav > li > a:focus {Ð color: #333333;Ð background-color: transparent;}ÐÐnote-editor .navbar-default .navbar-nav > .active > a,Ðnote-editor .navbar-default .navbar-nav > .active > a:hover,Ð .note-editor .navbar-default .navbar-nav > .active > a:focus {Ð color: #555555;Ð background-color: #e7e7e7;}ÐÐnote-editor .navbar-default .navbar-nav > .disabled > a,Ðnote-editor .navbar-default .navbar-nav > .disabled > a:hover,Ðnote-editor .navbar-default .navbar-nav > .disabled > a:focus {Ð color: #cccccc;Ð background-color: transparent;}ÐÐnote-editor .navbar-default .navbar-toggle {Ð border-color: #dddddd;}ÐÐnote-editor .navbar-default .navbar-toggle:hover,Ðnote-editor .navbar-default .navbar-toggle:focus {Ð background-color: #dddddd;}ÐÐnote-editor .navbar-default .navbar-toggle .icon-bar {Ð background-color: #cccccc;}ÐÐnote-editor .navbar-default .navbar-collapse,Ðnote-editor .navbar-default .navbar-form {Ð border-color: #e7e7e7;}ÐÐnote-editor .navbar-default .navbar-nav > .dropdown > a:hover .caret,Ðnote-editor .navbar-default .navbar-nav > .dropdown > a:focus .caret {Ð border-top-color: #333333;Ð border-bottom-color: #333333;Ð

}Ðnote-editor .navbar-default .navbar-nav > .open > a,Ðnote-
editor .navbar-default .navbar-nav > .open > a:hover,Ðnote-editor .navbar-
default .navbar-nav > .open > a:focus {Ð background-color: #e7e7e7;Ð color:
#555555;ÞÐnote-editor .navbar-default .navbar-nav > .open > a .caret,Ðnote-
editor .navbar-default .navbar-nav > .open > a:hover .caret,Ðnote-
editor .navbar-default .navbar-nav > .open > a:focus .caret {Ð border-top-
color: #555555;Ð border-bottom-color: #555555;ÞÐnote-editor .navbar-
default .navbar-nav > .dropdown > a .caret {Ð border-top-color: #777777;Ð
border-bottom-color: #777777;Þ@media (max-width: 767px) {Ð .note-
editor .navbar-default .navbar-nav .open .dropdown-menu > li > a {Ð color:
#777777;Ð }Ð .note-editor .navbar-default .navbar-nav .open .dropdown-menu >
li > a:hover,Ð .note-editor .navbar-default .navbar-nav .open .dropdown-menu
> li > a:focus {Ð color: #333333;Ð background-color: transparent;Ð }Ð
.note-editor .navbar-default .navbar-nav .open .dropdown-menu > .active > a,Ð
.note-editor .navbar-default .navbar-nav .open .dropdown-menu > .active >
a:hover,Ð .note-editor .navbar-default .navbar-nav .open .dropdown-menu
> .active > a:focus {Ð color: #555555;Ð background-color: #e7e7e7;Ð }Ð
.note-editor .navbar-default .navbar-nav .open .dropdown-menu > .disabled >
a,Ð .note-editor .navbar-default .navbar-nav .open .dropdown-menu > .disabled
> a:hover,Ð .note-editor .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a:focus {Ð color: #cccccc;Ð background-color: transparent;Ð
}ÞÐnote-editor .navbar-default .navbar-link {Ð color: #777777;ÞÐnote-
editor .navbar-default .navbar-link:hover {Ð color: #333333;ÞÐnote-
editor .navbar-inverse {Ð background-color: #222222;Ð border-color: #080808;ÞÐ
.note-editor .navbar-inverse .navbar-brand {Ð color: #999999;ÞÐnote-
editor .navbar-inverse .navbar-brand:hover,Ðnote-editor .navbar-
inverse .navbar-brand:focus {Ð color: #ffffff;Ð background-color: transparent;Ð
}Ðnote-editor .navbar-inverse .navbar-text {Ð color: #999999;ÞÐnote-
editor .navbar-inverse .navbar-nav > li > a {Ð color: #999999;ÞÐnote-
editor .navbar-inverse .navbar-nav > li > a:hover,Ðnote-editor .navbar-
inverse .navbar-nav > li > a:focus {Ð color: #ffffff;Ð background-color:
transparent;ÞÐnote-editor .navbar-inverse .navbar-nav > .active > a,Ðnote-
editor .navbar-inverse .navbar-nav > .active > a:hover,Ðnote-editor .navbar-
inverse .navbar-nav > .active > a:focus {Ð color: #ffffff;Ð background-color:
#080808;ÞÐnote-editor .navbar-inverse .navbar-nav > .disabled > a,Ðnote-
editor .navbar-inverse .navbar-nav > .disabled > a:hover,Ðnote-editor .navbar-
inverse .navbar-nav > .disabled > a:focus {Ð color: #444444;Ð background-
color: transparent;ÞÐnote-editor .navbar-inverse .navbar-toggle {Ð border-
color: #333333;ÞÐnote-editor .navbar-inverse .navbar-toggle:hover,Ðnote-
editor .navbar-inverse .navbar-toggle:focus {Ð background-color: #333333;ÞÐ
.note-editor .navbar-inverse .navbar-toggle .icon-bar {Ð background-color:
#ffffff;ÞÐnote-editor .navbar-inverse .navbar-collapse,Ðnote-editor .navbar-
inverse .navbar-form {Ð border-color: #101010;ÞÐnote-editor .navbar-
inverse .navbar-nav > .open > a,Ðnote-editor .navbar-inverse .navbar-nav
> .open > a:hover,Ðnote-editor .navbar-inverse .navbar-nav > .open > a:focus {Ð
background-color: #080808;Ð color: #ffffff;ÞÐnote-editor .navbar-
inverse .navbar-nav > .dropdown > a:hover .caret {Ð border-top-color: #ffffff;Ð
border-bottom-color: #ffffff;ÞÐnote-editor .navbar-inverse .navbar-nav
> .dropdown > a .caret {Ð border-top-color: #999999;Ð border-bottom-color:
#999999;ÞÐnote-editor .navbar-inverse .navbar-nav > .open > a .caret,Ðnote-
editor .navbar-inverse .navbar-nav > .open > a:hover .caret,Ðnote-
editor .navbar-inverse .navbar-nav > .open > a:focus .caret {Ð border-top-
color: #ffffff;Ð border-bottom-color: #ffffff;Þ@media (max-width: 767px) {Ð
.note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .dropdown-
header {Ð border-color: #080808;Ð }Ð .note-editor .navbar-inverse .navbar-
nav .open .dropdown-menu > li > a {Ð color: #999999;Ð }Ð .note-
editor .navbar-inverse .navbar-nav .open .dropdown-menu > li > a:hover,Ð
.note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > li >
a:focus {Ð color: #ffffff;Ð background-color: transparent;Ð }Ð .note-
editor .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a,Ð

.note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a:hover,Ð .note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a:focus {Ð color: #ffffff;Ð background-color: #080808;Ð }Ð .note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a,Ð .note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a:hover,Ð .note-editor .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a:focus {Ð color: #444444;Ð background-color: transparent;Ð }ÐÐnote-editor .navbar-inverse .navbar-link {Ð color: #999999;ÐÐnote-editor .navbar-inverse .navbar-link:hover {Ð color: #ffffff;ÐÐnote-editor .breadcrumb {Ð padding: 8px 15px;Ð margin-bottom: 20px;Ð list-style: none;Ð background-color: #f5f5f5;Ð border-radius: 4px;ÐÐnote-editor .breadcrumb > li {Ð display: inline-block;ÐÐnote-editor .breadcrumb > li + li:before {Ð content: "/\00a0";Ð padding: 0 5px;Ð color: #cccccc;ÐÐnote-editor .breadcrumb > .active {Ð color: #999999;ÐÐnote-editor .pagination {Ð display: inline-block;Ð padding-left: 0;Ð margin: 20px 0;Ð border-radius: 4px;Ð }Ðnote-editor .pagination > li {Ð display: inline;ÐÐnote-editor .pagination > li > a,Ðnote-editor .pagination > li > span {Ð position: relative;Ð float: left;Ð padding: 6px 12px;Ð line-height: 1.428571429;Ð text-decoration: none;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð margin-left: -1px;ÐÐ .note-editor .pagination > li:first-child > a,Ðnote-editor .pagination > li:first-child > span {Ð margin-left: 0;Ð border-bottom-left-radius: 4px;Ð border-top-left-radius: 4px;ÐÐnote-editor .pagination > li:last-child > a,Ð .note-editor .pagination > li:last-child > span {Ð border-bottom-right-radius: 4px;Ð border-top-right-radius: 4px;ÐÐnote-editor .pagination > li > a:hover,Ðnote-editor .pagination > li > span:hover,Ðnote-editor .pagination > li > a:focus,Ðnote-editor .pagination > li > span:focus {Ð background-color: #eeeeee;ÐÐnote-editor .pagination > .active > a,Ðnote-editor .pagination > .active > span,Ðnote-editor .pagination > .active > a:hover,Ðnote-editor .pagination > .active > span:hover,Ðnote-editor .pagination > .active > a:focus,Ðnote-editor .pagination > .active > span:focus {Ð z-index: 2;Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #428bca;Ð cursor: default;ÐÐnote-editor .pagination > .disabled > span,Ðnote-editor .pagination > .disabled > span:hover,Ðnote-editor .pagination > .disabled > span:focus,Ð .note-editor .pagination > .disabled > a,Ðnote-editor .pagination > .disabled > a:hover,Ðnote-editor .pagination > .disabled > a:focus {Ð color: #999999;Ð background-color: #ffffff;Ð border-color: #dddddd;Ð cursor: not-allowed;ÐÐ .note-editor .pagination-lg > li > a,Ðnote-editor .pagination-lg > li > span {Ð padding: 10px 16px;Ð font-size: 18px;ÐÐnote-editor .pagination-lg > li:first-child > a,Ðnote-editor .pagination-lg > li:first-child > span {Ð border-bottom-left-radius: 6px;Ð border-top-left-radius: 6px;ÐÐnote-editor .pagination-lg > li:last-child > a,Ðnote-editor .pagination-lg > li:last-child > span {Ð border-bottom-right-radius: 6px;Ð border-top-right-radius: 6px;ÐÐnote-editor .pagination-sm > li > a,Ðnote-editor .pagination-sm > li > span {Ð padding: 5px 10px;Ð font-size: 12px;ÐÐnote-editor .pagination-sm > li:first-child > a,Ðnote-editor .pagination-sm > li:first-child > span {Ð border-bottom-left-radius: 3px;Ð border-top-left-radius: 3px;ÐÐnote-editor .pagination-sm > li:last-child > a,Ðnote-editor .pagination-sm > li:last-child > span {Ð border-bottom-right-radius: 3px;Ð border-top-right-radius: 3px;ÐÐnote-editor .pager {Ð padding-left: 0;Ð margin: 20px 0;Ð list-style: none;Ð text-align: center;ÐÐnote-editor .pager:before,Ðnote-editor .pager:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-editor .pager:after {Ð clear: both;ÐÐnote-editor .pager:before,Ðnote-editor .pager:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐnote-editor .pager:after {Ð clear: both;ÐÐnote-editor .pager li {Ð display: inline;Ð }Ðnote-editor .pager li > a,Ðnote-editor .pager li > span {Ð display: inline-block;Ð padding: 5px 14px;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-radius: 15px;ÐÐnote-editor .pager li > a:hover,Ðnote-editor .pager li > a:focus {Ð text-decoration: none;Ð background-color: #eeeeee;Ð

}Ðnote-editor .pager .next > a,Ðnote-editor .pager .next > span {Ð
float: right;ÐÐnote-editor .pager .previous > a,Ðnote-editor .pager .previous
> span {Ð float: left;ÐÐnote-editor .pager .disabled > a,Ðnote-
editor .pager .disabled > a:hover,Ðnote-editor .pager .disabled > a:focus,Ð
.note-editor .pager .disabled > span {Ð color: #999999;Ð background-color:
#ffffff;Ð cursor: not-allowed;ÐÐnote-editor .label {Ð display: inline;Ð
padding: .2em .6em .3em;Ð font-size: 75%;Ð font-weight: bold;Ð line-height: 1;Ð
  color: #ffffff;Ð text-align: center;Ð white-space: nowrap;Ð vertical-align:
baseline;Ð border-radius: .25em;ÐÐnote-editor .label[href]:hover,Ðnote-
editor .label[href]:focus {Ð color: #ffffff;Ð text-decoration: none;Ð cursor:
pointer;ÐÐnote-editor .label:empty {Ð display: none;ÐÐnote-editor .label-
default {Ð background-color: #999999;ÐÐnote-editor .label-default[href]:hover,Ð
.note-editor .label-default[href]:focus {Ð background-color: #808080;ÐÐnote-
editor .label-primary {Ð background-color: #428bca;ÐÐnote-editor .label-
primary[href]:hover,Ðnote-editor .label-primary[href]:focus {Ð background-
color: #3071a9;ÐÐnote-editor .label-success {Ð background-color: #5cb85c;ÐÐ
.note-editor .label-success[href]:hover,Ðnote-editor .label-
success[href]:focus {Ð background-color: #449d44;ÐÐnote-editor .label-info {Ð
background-color: #5bc0de;ÐÐnote-editor .label-info[href]:hover,Ðnote-
editor .label-info[href]:focus {Ð background-color: #31b0d5;ÐÐnote-
editor .label-warning {Ð background-color: #f0ad4e;ÐÐnote-editor .label-
warning[href]:hover,Ðnote-editor .label-warning[href]:focus {Ð background-
color: #ec971f;ÐÐnote-editor .label-danger {Ð background-color: #d9534f;ÐÐ
.note-editor .label-danger[href]:hover,Ðnote-editor .label-danger[href]:focus
{Ð background-color: #c9302c;ÐÐnote-editor .badge {Ð display: inline-block;Ð
min-width: 10px;Ð padding: 3px 7px;Ð font-size: 12px;Ð font-weight: bold;Ð
color: #ffffff;Ð line-height: 1;Ð vertical-align: baseline;Ð white-space:
nowrap;Ð text-align: center;Ð background-color: #999999;Ð border-radius: 10px;Ð
}Ðnote-editor .badge:empty {Ð display: none;ÐÐnote-editor a.badge:hover,Ðnote-
editor a.badge:focus {Ð color: #ffffff;Ð text-decoration: none;Ð cursor:
pointer;ÐÐnote-editor .btn .badge {Ð position: relative;Ð top: -1px;ÐÐnote-
editor a.list-group-item.active > .badge,Ðnote-editor .nav-pills > .active >
a > .badge {Ð color: #428bca;Ð background-color: #ffffff;ÐÐnote-editor .nav-
pills > li > a > .badge {Ð margin-left: 3px;ÐÐnote-editor .jumbotron {Ð
padding: 30px;Ð margin-bottom: 30px;Ð font-size: 21px;Ð font-weight: 200;Ð
line-height: 2.1428571435;Ð color: inherit;Ð background-color: #eeeeee;ÐÐnote-
editor .jumbotron h1 {Ð line-height: 1;Ð color: inherit;ÐÐnote-
editor .jumbotron p {Ð line-height: 1.4;ÐÐcontainer .note-editor .jumbotron {Ð
  border-radius: 6px;ÐÐmedia screen and (min-width: 768px) {Ð .note-
editor .jumbotron {Ð   padding-top: 48px;Ð   padding-bottom: 48px;Ð }Ð
  .container .note-editor .jumbotron {Ð   padding-left: 60px;Ð   padding-
right: 60px;Ð }Ð .note-editor .jumbotron h1 {Ð   font-size: 63px;Ð }ÐÐnote-
editor .thumbnail {Ð padding: 4px;Ð line-height: 1.428571429;Ð background-
color: #ffffff;Ð border: 1px solid #dddddd;Ð border-radius: 4px;Ð -webkit-
transition: all 0.2s ease-in-out;Ð transition: all 0.2s ease-in-out;Ð
display: inline-block;Ð max-width: 100%;Ð height: auto;Ð display: block;Ð
margin-bottom: 20px;ÐÐnote-editor .thumbnail > img {Ð display: block;Ð max-
width: 100%;Ð height: auto;ÐÐnote-editor a.thumbnail:hover,Ðnote-editor
a.thumbnail:focus,Ðnote-editor a.thumbnail.active {Ð border-color: #428bca;ÐÐ
.note-editor .thumbnail > img {Ð margin-left: auto;Ð margin-right: auto;ÐÐ
.note-editor .thumbnail .caption {Ð padding: 9px;Ð color: #333333;ÐÐnote-
editor .alert {Ð padding: 15px;Ð margin-bottom: 20px;Ð border: 1px solid
transparent;Ð border-radius: 4px;ÐÐnote-editor .alert h4 {Ð margin-top: 0;Ð
color: inherit;ÐÐnote-editor .alert .alert-link {Ð font-weight: bold;ÐÐnote-
editor .alert > p,Ðnote-editor .alert > ul {Ð margin-bottom: 0;ÐÐnote-
editor .alert > p + p {Ð margin-top: 5px;ÐÐnote-editor .alert-dismissable {Ð
padding-right: 35px;ÐÐnote-editor .alert-dismissable .close {Ð position:
relative;Ð top: -2px;Ð right: -21px;Ð color: inherit;ÐÐnote-editor .alert-
success {Ð background-color: #dff0d8;Ð border-color: #d6e9c6;Ð color: #468847;Ð
}Ð

.note-editor .alert-success hr {Ð border-top-color: #c9e2b3;ÞÞnote-editor .alert-success .alert-link {Ð color: #356635;ÞÞnote-editor .alert-info {Ð background-color: #d9edf7;Ð border-color: #bce8f1;Ð color: #3a87ad;ÞÞnote-editor .alert-info hr {Ð border-top-color: #a6e1ec;ÞÞnote-editor .alert-info .alert-link {Ð color: #2d6987;ÞÞnote-editor .alert-warning {Ð background-color: #fcf8e3;Ð border-color: #faebcc;Ð color: #c09853;ÞÞnote-editor .alert-warning hr {Ð border-top-color: #f7e1b5;ÞÞnote-editor .alert-warning .alert-link {Ð color: #a47e3c;ÞÞnote-editor .alert-danger {Ð background-color: #f2dede;Ð border-color: #ebccd1;Ð color: #b94a48;ÞÞnote-editor .alert-danger hr {Ð border-top-color: #e4b9c0;ÞÞnote-editor .alert-danger .alert-link {Ð color: #953b39;ÞÞ@-webkit-keyframes progress-bar-stripes {Ð from {Ð background-position: 40px 0;Ð }Ð to {Ð background-position: 0 0;Ð }ÞÞ@-moz-keyframes progress-bar-stripes {Ð from {Ð background-position: 40px 0;Ð }Ð to {Ð background-position: 0 0;Ð }ÞÞ@-o-keyframes progress-bar-stripes {Ð from {Ð background-position: 0 0;Ð }Ð to {Ð background-position: 40px 0;Ð }ÞÞ@keyframes progress-bar-stripes {Ð from {Ð background-position: 40px 0;Ð }Ð to {Ð background-position: 0 0;Ð }ÞÞnote-editor .progress {Ð overflow: hidden;Ð height: 20px;Ð margin-bottom: 20px;Ð background-color: #f5f5f5;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 2px rgba(0, 0, 0, 0.1);Ð box-shadow: inset 0 1px 2px rgba(0, 0, 0, 0.1);ÞÞnote-editor .progress-bar {Ð float: left;Ð width: 0%;Ð height: 100%;Ð font-size: 12px;Ð line-height: 20px;Ð color: #ffffff;Ð text-align: center;Ð background-color: #428bca;Ð -webkit-box-shadow: inset 0 -1px 0 rgba(0, 0, 0, 0.15);Ð box-shadow: inset 0 -1px 0 rgba(0, 0, 0, 0.15);Ð -webkit-transition: width 0.6s ease;Ð transition: width 0.6s ease;ÞÞnote-editor .progress-striped .progress-bar {Ð background-image: -webkit-gradient(linear, 0 100%, 100% 0, color-stop(0.25, rgba(255, 255, 255, 0.15)), color-stop(0.25, transparent), color-stop(0.5, transparent), color-stop(0.5, rgba(255, 255, 255, 0.15)), color-stop(0.75, rgba(255, 255, 255, 0.15)), color-stop(0.75, transparent), to(transparent));Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: -moz-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-size: 40px 40px;ÞÞnote-editor .progress.active .progress-bar {Ð -webkit-animation: progress-bar-stripes 2s linear infinite;Ð -moz-animation: progress-bar-stripes 2s linear infinite;Ð -ms-animation: progress-bar-stripes 2s linear infinite;Ð -o-animation: progress-bar-stripes 2s linear infinite;Ð animation: progress-bar-stripes 2s linear infinite;ÞÞnote-editor .progress-bar-success {Ð background-color: #5cb85c;ÞÞprogress-striped .note-editor .progress-bar-success {Ð background-image: -webkit-gradient(linear, 0 100%, 100% 0, color-stop(0.25, rgba(255, 255, 255, 0.15)), color-stop(0.25, transparent), color-stop(0.5, transparent), color-stop(0.5, rgba(255, 255, 255, 0.15)), color-stop(0.75, rgba(255, 255, 255, 0.15)), color-stop(0.75, transparent), to(transparent));Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: -moz-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÞÞnote-editor .progress-bar-info {Ð background-color: #5bc0de;ÞÞprogress-striped .note-editor .progress-bar-info {Ð background-image: -webkit-gradient(linear, 0 100%, 100% 0, color-stop(0.25, rgba(255, 255, 255, 0.15)), color-stop(0.25, transparent), color-stop(0.5, transparent), color-stop(0.5, rgba(255, 255, 255, 0.15)), color-stop(0.75,

rgba(255, 255, 255, 0.15)), color-stop(0.75, transparent), to(transparent));Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: -moz-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÐÐ.note-editor .progress-bar-warning {Ð background-color: #f0ad4e;ÐÐ.progress-striped .note-editor .progress-bar-warning {Ð background-image: -webkit-gradient(linear, 0 100%, 100% 0, color-stop(0.25, rgba(255, 255, 255, 0.15)), color-stop(0.25, transparent), color-stop(0.5, transparent), color-stop(0.5, rgba(255, 255, 255, 0.15)), color-stop(0.75, rgba(255, 255, 255, 0.15)), color-stop(0.75, transparent), to(transparent));Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: -moz-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÐÐ.note-editor .progress-bar-danger {Ð background-color: #d9534f;ÐÐ.progress-striped .note-editor .progress-bar-danger {Ð background-image: -webkit-gradient(linear, 0 100%, 100% 0, color-stop(0.25, rgba(255, 255, 255, 0.15)), color-stop(0.25, transparent), color-stop(0.5, transparent), color-stop(0.5, rgba(255, 255, 255, 0.15)), color-stop(0.75, rgba(255, 255, 255, 0.15)), color-stop(0.75, transparent), to(transparent));Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: -moz-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÐÐ.note-editor .media,Ð.note-editor .media-body {Ð overflow: hidden;Ð zoom: 1;ÐÐ.note-editor .media,Ð.note-editor .media .media {Ð margin-top: 15px;ÐÐ.note-editor .media:first-child {Ð margin-top: 0;ÐÐ.note-editor .media-object {Ð display: block;ÐÐ.note-editor .media-heading {Ð margin: 0 0 5px;ÐÐ.note-editor .media > .pull-left {Ð margin-right: 10px;ÐÐ .note-editor .media > .pull-right {Ð margin-left: 10px;ÐÐ.note-editor .media-list {Ð padding-left: 0;Ð list-style: none;ÐÐ.note-editor .list-group {Ð margin-bottom: 20px;Ð padding-left: 0;ÐÐ.note-editor .list-group-item {Ð position: relative;Ð display: block;Ð padding: 10px 15px;Ð margin-bottom: -1px;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;ÐÐ.note-editor .list-group-item:first-child {Ð border-top-right-radius: 4px;Ð border-top-left-radius: 4px;ÐÐ.note-editor .list-group-item:last-child {Ð margin-bottom: 0;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 4px;ÐÐ .note-editor .list-group-item > .badge {Ð float: right;ÐÐ.note-editor .list-group-item > .badge + .badge {Ð margin-right: 5px;ÐÐ.note-editor a.list-group-item {Ð color: #555555;ÐÐ.note-editor a.list-group-item .list-group-item-heading {Ð color: #333333;ÐÐ.note-editor a.list-group-item:hover,Ð.note-editor a.list-group-item:focus {Ð text-decoration: none;Ð background-color: #f5f5f5;ÐÐ .note-editor a.list-group-item.active,Ð.note-editor a.list-group-item.active:hover,Ð.note-editor a.list-group-item.active:focus {Ð z-index: 2;Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #428bca;ÐÐ.note-editor a.list-group-item.active .list-group-item-heading,Ð.note-editor a.list-group-item.active:hover .list-group-item-heading,Ð

.note-editor a.list-group-item.active:focus .list-group-item-heading {Ð color: inherit;ÐÐÐnote-editor a.list-group-item.active .list-group-item-text,Ðnote-editor a.list-group-item.active:hover .list-group-item-text,Ðnote-editor a.list-group-item.active:focus .list-group-item-text {Ð color: #e1edf7;ÐÐÐnote-editor .list-group-item-heading {Ð margin-top: 0;Ð margin-bottom: 5px;ÐÐÐnote-editor .list-group-item-text {Ð margin-bottom: 0;Ð line-height: 1.3;ÐÐÐnote-editor .panel {Ð
  margin-bottom: 20px;Ð background-color: #ffffff;Ð border: 1px solid transparent;Ð border-radius: 4px;Ð -webkit-box-shadow: 0 1px 1px rgba(0, 0, 0, 0.05);Ð box-shadow: 0 1px 1px rgba(0, 0, 0, 0.05);ÐÐÐnote-editor .panel-body {Ð padding: 15px;ÐÐÐnote-editor .panel-body:before,Ðnote-editor .panel-body:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐÐnote-editor .panel-body:after {Ð clear: both;ÐÐÐnote-editor .panel-body:before,Ð .note-editor .panel-body:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐÐnote-editor .panel-body:after {Ð clear: both;ÐÐÐnote-editor .panel > .list-group {Ð margin-bottom: 0;ÐÐÐnote-editor .panel > .list-group .list-group-item {Ð border-width: 1px 0;ÐÐÐnote-editor .panel > .list-group .list-group-item:first-child {Ð border-top-right-radius: 0;Ð border-top-left-radius: 0;ÐÐÐnote-editor .panel > .list-group .list-group-item:last-child {Ð border-bottom: 0;ÐÐÐnote-editor .panel-heading + .list-group .list-group-item:first-child {Ð border-top-width: 0;ÐÐÐnote-editor .panel > .table,Ðnote-editor .panel > .table-responsive {Ð margin-bottom: 0;ÐÐÐnote-editor .panel > .panel-body + .table,Ðnote-editor .panel > .panel-body + .table-responsive {Ð
  border-top: 1px solid #dddddd;ÐÐÐnote-editor .panel > .table-bordered,Ðnote-editor .panel > .table-responsive > .table-bordered {Ð border: 0;ÐÐÐnote-editor .panel > .table-bordered > thead > tr > th:first-child,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr > th:first-child,Ðnote-editor .panel > .table-bordered > tbody > tr > th:first-child,Ð .note-editor .panel > .table-responsive > .table-bordered > tbody > tr > th:first-child,Ðnote-editor .panel > .table-bordered > tfoot > tr > th:first-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ðnote-editor .panel > .table-bordered > thead > tr > td:first-child,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr > td:first-child,Ðnote-editor .panel > .table-bordered > tbody > tr > td:first-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tbody > tr > td:first-child,Ðnote-editor .panel > .table-bordered > tfoot > tr > td:first-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left: 0;ÐÐÐnote-editor .panel > .table-bordered > thead > tr > th:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr > th:last-child,Ðnote-editor .panel > .table-bordered > tbody > tr > th:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tbody > tr > th:last-child,Ðnote-editor .panel > .table-bordered > tfoot > tr > th:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ðnote-editor .panel > .table-bordered > thead > tr > td:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr > td:last-child,Ðnote-editor .panel > .table-bordered > tbody > tr > td:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tbody > tr > td:last-child,Ðnote-editor .panel > .table-bordered > tfoot > tr > td:last-child,Ðnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr > td:last-child {Ð border-right: 0;ÐÐÐnote-editor .panel > .table-bordered > thead > tr:last-child > th,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr:last-child > th,Ðnote-editor .panel > .table-bordered > tbody > tr:last-child > th,Ðnote-editor .panel > .table-responsive > .table-bordered > tbody > tr:last-child > th,Ðnote-editor .panel > .table-bordered > tfoot > tr:last-child > th,Ðnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr:last-child > th,Ðnote-editor .panel > .table-bordered > thead > tr:last-child > td,Ðnote-editor .panel > .table-responsive > .table-bordered > thead > tr:last-child > td,Ðnote-editor .panel > .table-bordered > tbody > tr:last-child > td,Ðnote-editor .panel > .table-responsive > .table-bordered > tbody > tr:last-child > td,Ð

.note-editor .panel > .table-bordered > tfoot > tr:last-child > td,Đnote-editor .panel > .table-responsive > .table-bordered > tfoot > tr:last-child > td {Đ border-bottom: 0;ÐÐnote-editor .panel-heading {Đ padding: 10px 15px;Đ border-bottom: 1px solid transparent;Đ border-top-right-radius: 3px;Đ border-top-left-radius: 3px;ÐÐnote-editor .panel-title {Đ margin-top: 0;Đ margin-bottom: 0;Đ font-size: 16px;ÐÐnote-editor .panel-title > a {Đ color: inherit;ÐÐ .note-editor .panel-footer {Đ padding: 10px 15px;Đ background-color: #f5f5f5;Đ border-top: 1px solid #dddddd;Đ border-bottom-right-radius: 3px;Đ border-bottom-left-radius: 3px;ÐÐnote-editor .panel-group .panel {Đ margin-bottom: 0;Đ border-radius: 4px;Đ overflow: hidden;ÐÐnote-editor .panel-group .panel + .panel {Đ margin-top: 5px;ÐÐnote-editor .panel-group .panel-heading {Đ border-bottom: 0;ÐÐnote-editor .panel-group .panel-heading + .panel-collapse .panel-body {Đ border-top: 1px solid #dddddd;ÐÐnote-editor .panel-group .panel-footer {Đ border-top: 0;ÐÐnote-editor .panel-group .panel-footer + .panel-collapse .panel-body {Đ border-bottom: 1px solid #dddddd;ÐÐnote-editor .panel-default {Đ border-color: #dddddd;ÐÐnote-editor .panel-default > .panel-heading {Đ color: #333333;Đ background-color: #f5f5f5;Đ border-color: #dddddd;ÐÐnote-editor .panel-default > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #dddddd;ÐÐnote-editor .panel-default > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #dddddd;ÐÐnote-editor .panel-primary {Đ border-color: #428bca;ÐÐnote-editor .panel-primary > .panel-heading {Đ color: #ffffff;Đ background-color: #428bca;Đ border-color: #428bca;ÐÐnote-editor .panel-primary > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #428bca;ÐÐnote-editor .panel-primary > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #428bca;ÐÐnote-editor .panel-success {Đ border-color: #d6e9c6;ÐÐ .note-editor .panel-success > .panel-heading {Đ color: #468847;Đ background-color: #dff0d8;Đ border-color: #d6e9c6;ÐÐnote-editor .panel-success > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #d6e9c6;ÐÐnote-editor .panel-success > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #d6e9c6;ÐÐnote-editor .panel-warning {Đ border-color: #faebcc;ÐÐ .note-editor .panel-warning > .panel-heading {Đ color: #c09853;Đ background-color: #fcf8e3;Đ border-color: #faebcc;ÐÐnote-editor .panel-warning > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #faebcc;ÐÐnote-editor .panel-warning > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #faebcc;ÐÐnote-editor .panel-danger {Đ border-color: #ebccd1;ÐÐ .note-editor .panel-danger > .panel-heading {Đ color: #b94a48;Đ background-color: #f2dede;Đ border-color: #ebccd1;ÐÐnote-editor .panel-danger > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #ebccd1;ÐÐnote-editor .panel-danger > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #ebccd1;ÐÐnote-editor .panel-info {Đ border-color: #bce8f1;ÐÐ .note-editor .panel-info > .panel-heading {Đ color: #3a87ad;Đ background-color: #d9edf7;Đ border-color: #bce8f1;ÐÐnote-editor .panel-info > .panel-heading + .panel-collapse .panel-body {Đ border-top-color: #bce8f1;ÐÐnote-editor .panel-info > .panel-footer + .panel-collapse .panel-body {Đ border-bottom-color: #bce8f1;ÐÐnote-editor .well {Đ min-height: 20px;Đ padding: 19px;Đ margin-bottom: 20px;Đ background-color: #f5f5f5;Đ border: 1px solid #e3e3e3;Đ border-radius: 4px;Đ -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.05);Đ box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.05);ÐÐnote-editor .well blockquote {Đ border-color: #ddd;Đ border-color: rgba(0, 0, 0, 0.15);ÐÐnote-editor .well-lg {Đ padding: 24px;Đ border-radius: 6px;ÐÐnote-editor .well-sm {Đ padding: 9px;Đ border-radius: 3px;ÐÐnote-editor .close {Đ float: right;Đ font-size: 21px;Đ font-weight: bold;Đ line-height: 1;Đ color: #000000;Đ text-shadow: 0 1px 0 #ffffff;Đ opacity: 0.2;Đ filter: alpha(opacity=20);ÐÐnote-editor .close:hover,Đnote-editor .close:focus {Đ color: #000000;Đ text-decoration: none;Đ cursor: pointer;Đ opacity: 0.5;Đ filter: alpha(opacity=50);Đ }Đbutton.note-editor .close {Đ padding: 0;Đ cursor: pointer;Đ background: transparent;Đ border: 0;Đ -webkit-appearance: none;ÐÐmodal-open {Đ overflow: hidden;ÐÐmodal {Đ display: none;Đ overflow: auto;Đ overflow-y: scroll;Đ position: fixed;Đ

top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 1040;ÐÐ
.modal.fade .modal-dialog {Ð -webkit-transform: translate(0, -25%);Ð -ms-transform: translate(0, -25%);Ð transform: translate(0, -25%);Ð -webkit-transition: -webkit-transform 0.3s ease-out;Ð -moz-transition: -moz-transform 0.3s ease-out;Ð -o-transition: -o-transform 0.3s ease-out;Ð transition: transform 0.3s ease-out;ÐÐmodal.in .modal-dialog {Ð -webkit-transform: translate(0, 0);Ð -ms-transform: translate(0, 0);Ð transform: translate(0, 0);Ð }Ðmodal-dialog {Ð margin-left: auto;Ð margin-right: auto;Ð width: auto;Ð padding: 10px;Ð z-index: 1050;ÐÐmodal-content {Ð position: relative;Ð background-color: #ffffff;Ð border: 1px solid #999999;Ð border: 1px solid rgba(0, 0, 0, 0.2);Ð border-radius: 6px;Ð -webkit-box-shadow: 0 3px 9px rgba(0, 0, 0, 0.5);Ð box-shadow: 0 3px 9px rgba(0, 0, 0, 0.5);Ð background-clip: padding-box;Ð outline: none;ÐÐmodal-backdrop {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 1030;Ð background-color: #000000;ÐÐmodal-backdrop.fade {Ð opacity: 0;Ð filter: alpha(opacity=0);ÐÐ
.modal-backdrop.in {Ð opacity: 0.5;Ð filter: alpha(opacity=50);ÐÐmodal-header {Ð padding: 15px;Ð border-bottom: 1px solid #e5e5e5;Ð min-height: 16.428571429px;ÐÐmodal-header .close {Ð margin-top: -2px;ÐÐmodal-title {Ð margin: 0;Ð line-height: 1.428571429;ÐÐmodal-body {Ð position: relative;Ð padding: 20px;ÐÐmodal-footer {Ð margin-top: 15px;Ð padding: 19px 20px 20px;Ð text-align: right;Ð border-top: 1px solid #e5e5e5;ÐÐmodal-footer:before,Ð
.modal-footer:after {Ð content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐ
.modal-footer:after {Ð clear: both;ÐÐmodal-footer:before,Ðmodal-footer:after {Ð
content: " ";Ð /* 1 */Ð display: table;Ð /* 2 */ÐÐmodal-footer:after {Ð clear: both;ÐÐmodal-footer .btn + .btn {Ð margin-left: 5px;Ð margin-bottom: 0;Ð }Ðmodal-footer .btn-group .btn + .btn {Ð margin-left: -1px;ÐÐmodal-footer .btn-block + .btn-block {Ð margin-left: 0;ÐÐ@media screen and (min-width: 768px) {Ð .modal-dialog {Ð width: 600px;Ð padding-top: 30px;Ð padding-bottom: 30px;Ð }Ð .modal-content {Ð -webkit-box-shadow: 0 5px 15px rgba(0, 0, 0, 0.5);Ð box-shadow: 0 5px 15px rgba(0, 0, 0, 0.5);Ð }ÐÐtooltip {Ð position: absolute;Ð z-index: 1030;Ð display: block;Ð visibility: visible;Ð
font-size: 12px;Ð line-height: 1.4;Ð opacity: 0;Ð filter: alpha(opacity=0);ÐÐ
.tooltip.in {Ð opacity: 0.9;Ð filter: alpha(opacity=90);ÐÐtooltip.top {Ð margin-top: -3px;Ð padding: 5px 0;ÐÐtooltip.right {Ð margin-left: 3px;Ð padding: 0 5px;ÐÐtooltip.bottom {Ð margin-top: 3px;Ð padding: 5px 0;ÐÐ
.tooltip.left {Ð margin-left: -3px;Ð padding: 0 5px;ÐÐtooltip-inner {Ð max-width: 200px;Ð padding: 3px 8px;Ð color: #ffffff;Ð text-align: center;Ð text-decoration: none;Ð background-color: #000000;Ð border-radius: 4px;ÐÐtooltip-arrow {Ð position: absolute;Ð width: 0;Ð height: 0;Ð border-color: transparent;Ð border-style: solid;ÐÐtooltip.top .tooltip-arrow {Ð bottom: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000000;ÐÐtooltip.top-left .tooltip-arrow {Ð bottom: 0;Ð left: 5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000000;ÐÐtooltip.top-right .tooltip-arrow {Ð bottom: 0;Ð right: 5px;Ð border-width: 5px 5px 0;Ð border-top-color: #000000;ÐÐtooltip.right .tooltip-arrow {Ð top: 50%;Ð left: 0;Ð margin-top: -5px;Ð border-width: 5px 5px 5px 0;Ð border-right-color: #000000;ÐÐ
.tooltip.left .tooltip-arrow {Ð top: 50%;Ð right: 0;Ð margin-top: -5px;Ð border-width: 5px 0 5px 5px;Ð border-left-color: #000000;ÐÐ
.tooltip.bottom .tooltip-arrow {Ð top: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000000;ÐÐtooltip.bottom-left .tooltip-arrow {Ð top: 0;Ð left: 5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000000;ÐÐtooltip.bottom-right .tooltip-arrow {Ð top: 0;Ð right: 5px;Ð border-width: 0 5px 5px;Ð border-bottom-color: #000000;ÐÐpopover {Ð position: absolute;Ð top: 0;Ð left: 0;Ð z-index: 1010;Ð display: none;Ð max-width: 276px;Ð padding: 1px;Ð text-align: left;Ð background-color: #ffffff;Ð background-clip: padding-box;Ð border: 1px solid #cccccc;Ð border: 1px solid rgba(0, 0, 0, 0.2);Ð border-radius: 6px;Ð -webkit-box-shadow: 0 5px 10px rgba(0, 0, 0, 0.2);Ð box-shadow: 0 5px 10px rgba(0, 0, 0, 0.2);Ð white-space: normal;ÐÐpopover.top {Ð margin-top: -10px;ÐÐpopover.right {Ð margin-left: 10px;Ð

}ÐÐpopover.bottom {Ð margin-top: 10px;ÐÐpopover.left {Ð margin-left: -10px;ÐÐpopover-title {Ð margin: 0;Ð padding: 8px 14px;Ð font-size: 14px;Ð font-weight: normal;Ð line-height: 18px;Ð background-color: #f7f7f7;Ð border-bottom: 1px solid #ebebeb;Ð border-radius: 5px 5px 0 0;ÐÐpopover-content {Ð padding: 9px 14px;ÐÐpopover .arrow,Ðpopover .arrow:after {Ð position: absolute;Ð display: block;Ð width: 0;Ð height: 0;Ð border-color: transparent;Ð border-style: solid;ÐÐpopover .arrow {Ð border-width: 11px;ÐÐ .popover .arrow:after {Ð border-width: 10px;Ð content: "";ÐÐ .popover.top .arrow {Ð left: 50%;Ð margin-left: -11px;Ð border-bottom-width: 0;Ð border-top-color: #999999;Ð border-top-color: rgba(0, 0, 0, 0.25);Ð bottom: -11px;ÐÐpopover.top .arrow:after {Ð content: " ";Ð bottom: 1px;Ð margin-left: -10px;Ð border-bottom-width: 0;Ð border-top-color: #ffffff;ÐÐ .popover.right .arrow {Ð top: 50%;Ð left: -11px;Ð margin-top: -11px;Ð border-left-width: 0;Ð border-right-color: #999999;Ð border-right-color: rgba(0, 0, 0, 0.25);ÐÐpopover.right .arrow:after {Ð content: " ";Ð left: 1px;Ð bottom: -10px;Ð border-left-width: 0;Ð border-right-color: #ffffff;ÐÐ .popover.bottom .arrow {Ð left: 50%;Ð margin-left: -11px;Ð border-top-width: 0;Ð border-bottom-color: #999999;Ð border-bottom-color: rgba(0, 0, 0, 0.25);Ð top: -11px;ÐÐpopover.bottom .arrow:after {Ð content: " ";Ð top: 1px;Ð margin-left: -10px;Ð border-top-width: 0;Ð border-bottom-color: #ffffff;ÐÐ .popover.left .arrow {Ð top: 50%;Ð right: -11px;Ð margin-top: -11px;Ð border-right-width: 0;Ð border-left-color: #999999;Ð border-left-color: rgba(0, 0, 0, 0.25);ÐÐpopover.left .arrow:after {Ð content: " ";Ð right: 1px;Ð border-right-width: 0;Ð border-left-color: #ffffff;Ð bottom: -10px;ÐÐcarousel {Ð position: relative;ÐÐcarousel-inner {Ð position: relative;Ð overflow: hidden;Ð width: 100%;ÐÐcarousel-inner > .item {Ð display: none;Ð position: relative;Ð -webkit-transition: 0.6s ease-in-out left;Ð transition: 0.6s ease-in-out left;ÐÐcarousel-inner > .item > img,Ðcarousel-inner > .item > a > img {Ð display: block;Ð max-width: 100%;Ð height: auto;Ð line-height: 1;ÐÐcarousel-inner > .active,Ðcarousel-inner > .next,Ðcarousel-inner > .prev {Ð display: block;ÐÐcarousel-inner > .active {Ð left: 0;ÐÐcarousel-inner > .next,Ð .carousel-inner > .prev {Ð position: absolute;Ð top: 0;Ð width: 100%;ÐÐ .carousel-inner > .next {Ð left: 100%;ÐÐcarousel-inner > .prev {Ð left: -100%;Ð }Ðcarousel-inner > .next.left,Ðcarousel-inner > .prev.right {Ð left: 0;ÐÐ .carousel-inner > .active.left {Ð left: -100%;ÐÐcarousel-inner > .active.right {Ð left: 100%;ÐÐcarousel-control {Ð position: absolute;Ð top: 0;Ð left: 0;Ð bottom: 0;Ð width: 15%;Ð opacity: 0.5;Ð filter: alpha(opacity=50);Ð font-size: 20px;Ð color: #ffffff;Ð text-align: center;Ð text-shadow: 0 1px 2px rgba(0, 0, 0, 0.6);ÐÐcarousel-control.left {Ð background-image: -webkit-gradient(linear, 0% top, 100% top, from(rgba(0, 0, 0, 0.5)), to(rgba(0, 0, 0, 0.0001)));Ð background-image: -webkit-linear-gradient(left, color-stop(rgba(0, 0, 0, 0.5) 0%), color-stop(rgba(0, 0, 0, 0.0001) 100%));Ð background-image: -moz-linear-gradient(left, rgba(0, 0, 0, 0.5) 0%, rgba(0, 0, 0, 0.0001) 100%);Ð background-image: linear-gradient(to right, rgba(0, 0, 0, 0.5) 0%, rgba(0, 0, 0, 0.0001) 100%);Ð background-repeat: repeat-x;Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#80000000', endColorstr='#00000000', GradientType=1);ÐÐcarousel-control.right {Ð left: auto;Ð right: 0;Ð background-image: -webkit-gradient(linear, 0% top, 100% top, from(rgba(0, 0, 0, 0.0001)), to(rgba(0, 0, 0, 0.5)));Ð background-image: -webkit-linear-gradient(left, color-stop(rgba(0, 0, 0, 0.0001) 0%), color-stop(rgba(0, 0, 0, 0.5) 100%));Ð background-image: -moz-linear-gradient(left, rgba(0, 0, 0, 0.0001) 0%, rgba(0, 0, 0, 0.5) 100%);Ð background-image: linear-gradient(to right, rgba(0, 0, 0, 0.0001) 0%, rgba(0, 0, 0, 0.5) 100%);Ð background-repeat: repeat-x;Ð filter: progid:DXImageTransform.Microsoft.gradient(startColorstr='#00000000', endColorstr='#80000000', GradientType=1);ÐÐcarousel-control:hover,Ðcarousel-control:focus {Ð color: #ffffff;Ð text-decoration: none;Ð opacity: 0.9;Ð filter: alpha(opacity=90);ÐÐcarousel-control .icon-prev,Ðcarousel-control .icon-next,Ð

.carousel-control .glyphicon-chevron-left,Đcarousel-control .glyphicon-chevron-right {Đ position: absolute;Đ top: 50%;Đ z-index: 5;Đ display: inline-block;ÞĐcarousel-control .icon-prev,Đcarousel-control .glyphicon-chevron-left {Đ left: 50%;ÞĐcarousel-control .icon-next,Đ .carousel-control .glyphicon-chevron-right {Đ right: 50%;ÞĐcarousel-control .icon-prev,Đcarousel-control .icon-next {Đ width: 20px;Đ height: 20px;Đ margin-top: -10px;Đ margin-left: -10px;Đ font-family: serif;ÞĐcarousel-control .icon-prev:before {Đ content: '\2039';ÞĐcarousel-control .icon-next:before {Đ content: '\203a';ÞĐcarousel-indicators {Đ position: absolute;Đ bottom: 10px;Đ left: 50%;Đ z-index: 15;Đ width: 60%;Đ margin-left: -30%;Đ padding-left: 0;Đ list-style: none;Đ text-align: center;ÞĐcarousel-indicators li {Đ display: inline-block;Đ width: 10px;Đ height: 10px;Đ margin: 1px;Đ text-indent: -999px;Đ border: 1px solid #ffffff;Đ border-radius: 10px;Đ cursor: pointer;ÞĐcarousel-indicators .active {Đ margin: 0;Đ width: 12px;Đ height: 12px;Đ background-color: #ffffff;ÞĐcarousel-caption {Đ position: absolute;Đ left: 15%;Đ right: 15%;Đ bottom: 20px;Đ z-index: 10;Đ padding-top: 20px;Đ padding-bottom: 20px;Đ color: #ffffff;Đ text-align: center;Đ text-shadow: 0 1px 2px rgba(0, 0, 0, 0.6);ÞĐcarousel-caption .btn {Đ text-shadow: none;ÞĐ @media screen and (min-width: 768px) {Đ .carousel-control .glyphicons-chevron-left,Đ .carousel-control .glyphicons-chevron-right,Đ .carousel-control .icon-prev,Đ .carousel-control .icon-next {Đ width: 30px;Đ height: 30px;Đ margin-top: -15px;Đ margin-left: -15px;Đ font-size: 30px;Đ }Đ .carousel-caption {Đ left: 20%;Đ right: 20%;Đ padding-bottom: 30px;Đ }Đ .carousel-indicators {Đ bottom: 20px;Đ }ÞĐclearfix:before,Đclearfix:after {Đ content: " ";Đ /* 1 */Đ display: table;Đ /* 2 */ÞĐclearfix:after {Đ clear: both;ÞĐ .center-block {Đ display: block;Đ margin-left: auto;Đ margin-right: auto;ÞĐ .pull-right {Đ float: right !important;ÞĐpull-left {Đ float: left !important;ÞĐ .hide {Đ display: none !important;ÞĐshow {Đ display: block !important;ÞĐ .invisible {Đ visibility: hidden;ÞĐtext-hide {Đ font: 0/0 a;Đ color: transparent;Đ text-shadow: none;Đ background-color: transparent;Đ border: 0;ÞĐ .hidden {Đ display: none !important;Đ visibility: hidden !important;ÞĐaffix {Đ position: fixed;Þ@-ms-viewport {Đ width: device-width;ÞĐvisible-xs,Đ tr.visible-xs,Đth.visible-xs,Đtd.visible-xs {Đ display: none !important;Þ@media (max-width: 767px) {Đ .visible-xs {Đ display: block !important;Đ }Đ tr.visible-xs {Đ display: table-row !important;Đ }Đ th.visible-xs,Đ td.visible-xs {Đ display: table-cell !important;Đ }Þ@media (min-width: 768px) and (max-width: 991px) {Đ .visible-xs.visible-sm {Đ display: block !important;Đ }Đ tr.visible-xs.visible-sm {Đ display: table-row !important;Đ }Đ th.visible-xs.visible-sm,Đ td.visible-xs.visible-sm {Đ display: table-cell !important;Đ }Þ@media (min-width: 992px) and (max-width: 1199px) {Đ .visible-xs.visible-md {Đ display: block !important;Đ }Đ tr.visible-xs.visible-md {Đ display: table-row !important;Đ }Đ th.visible-xs.visible-md,Đ td.visible-xs.visible-md {Đ display: table-cell !important;Đ }Þ@media (min-width: 1200px) {Đ .visible-xs.visible-lg {Đ display: block !important;Đ }Đ tr.visible-xs.visible-lg {Đ display: table-row !important;Đ }Đ th.visible-xs.visible-lg,Đ td.visible-xs.visible-lg {Đ display: table-cell !important;Đ }ÞĐvisible-sm,Đtr.visible-sm,Đth.visible-sm,Đtd.visible-sm {Đ display: none !important;Þ@media (max-width: 767px) {Đ .visible-sm.visible-xs {Đ display: block !important;Đ }Đ tr.visible-sm.visible-xs {Đ display: table-row !important;Đ }Đ th.visible-sm.visible-xs,Đ td.visible-sm.visible-xs {Đ display: table-cell !important;Đ }Þ@media (min-width: 768px) and (max-width: 991px) {Đ .visible-sm {Đ display: block !important;Đ }Đ tr.visible-sm {Đ display: table-row !important;Đ }Đ th.visible-sm,Đ td.visible-sm {Đ display: table-cell !important;Đ }Þ@media (min-width: 992px) and (max-width: 1199px) {Đ .visible-sm.visible-md {Đ display: block !important;Đ }Đ tr.visible-sm.visible-md {Đ display: table-row !important;Đ }Đ th.visible-sm.visible-md,Đ td.visible-sm.visible-md {Đ display: table-cell !important;Đ }Þ@media (min-width: 1200px) {Đ .visible-sm.visible-lg {Đ display: block !important;Đ }Đ tr.visible-sm.visible-lg {Đ display: table-row !important;Đ }Đ th.visible-sm.visible-lg,Đ

td.visible-sm.visible-lg {Ð display: table-cell !important;Ð }ÐÐvisible-md,Ðtr.visible-md,Ðth.visible-md,Ðtd.visible-md {Ð display: none !important;ÐÐ@media (max-width: 767px) {Ð .visible-md.visible-xs {Ð display: block !important;Ð }Ð tr.visible-md.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-md.visible-xs,Ð td.visible-md.visible-xs {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .visible-md.visible-sm {Ð display: block !important;Ð }Ð tr.visible-md.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-md.visible-sm,Ð td.visible-md.visible-sm {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md {Ð display: block !important;Ð }Ð tr.visible-md {Ð display: table-row !important;Ð }Ð th.visible-md,Ð td.visible-md {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .visible-md.visible-lg {Ð display: block !important;Ð }Ð tr.visible-md.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-md.visible-lg,Ð td.visible-md.visible-lg {Ð display: table-cell !important;Ð }ÐÐvisible-lg,Ðtr.visible-lg,Ðth.visible-lg,Ð td.visible-lg {Ð display: none !important;ÐÐ@media (max-width: 767px) {Ð .visible-lg.visible-xs {Ð display: block !important;Ð }Ð tr.visible-lg.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-xs,Ð td.visible-lg.visible-xs {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .visible-lg.visible-sm {Ð display: block !important;Ð }Ð tr.visible-lg.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-sm,Ð td.visible-lg.visible-sm {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-lg.visible-md {Ð display: block !important;Ð }Ð tr.visible-lg.visible-md {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-md,Ð td.visible-lg.visible-md {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .visible-lg {Ð display: block !important;Ð }Ð tr.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-lg,Ð td.visible-lg {Ð display: table-cell !important;Ð }ÐÐhidden-xs {Ð display: block !important;ÐÐtr.hidden-xs {Ð display: table-row !important;ÐÐth.hidden-xs,Ð td.hidden-xs {Ð display: table-cell !important;ÐÐ@media (max-width: 767px) {Ð .hidden-xs,Ð tr.hidden-xs,Ð th.hidden-xs,Ð td.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .hidden-xs.hidden-sm,Ð tr.hidden-xs.hidden-sm,Ð th.hidden-xs.hidden-sm,Ð td.hidden-xs.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-xs.hidden-md,Ð tr.hidden-xs.hidden-md,Ð th.hidden-xs.hidden-md,Ð td.hidden-xs.hidden-md {Ð display: none !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .hidden-xs.hidden-lg,Ð tr.hidden-xs.hidden-lg,Ð th.hidden-xs.hidden-lg,Ð td.hidden-xs.hidden-lg {Ð display: none !important;Ð }ÐÐhidden-sm {Ð display: block !important;ÐÐtr.hidden-sm {Ð display: table-row !important;ÐÐth.hidden-sm,Ðtd.hidden-sm {Ð display: table-cell !important;ÐÐ@media (max-width: 767px) {Ð .hidden-sm.hidden-xs,Ð tr.hidden-sm.hidden-xs,Ð th.hidden-sm.hidden-xs,Ð td.hidden-sm.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .hidden-sm,Ð tr.hidden-sm,Ð th.hidden-sm,Ð td.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-sm.hidden-md,Ð tr.hidden-sm.hidden-md,Ð th.hidden-sm.hidden-md,Ð td.hidden-sm.hidden-md {Ð display: none !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .hidden-sm.hidden-lg,Ð tr.hidden-sm.hidden-lg,Ð th.hidden-sm.hidden-lg,Ð td.hidden-sm.hidden-lg {Ð display: none !important;Ð }ÐÐ .hidden-md {Ð display: block !important;ÐÐtr.hidden-md {Ð display: table-row !important;ÐÐth.hidden-md,Ðtd.hidden-md {Ð display: table-cell !important;ÐÐ @media (max-width: 767px) {Ð .hidden-md.hidden-xs,Ð tr.hidden-md.hidden-xs,Ð th.hidden-md.hidden-xs,Ð td.hidden-md.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .hidden-md.hidden-sm,Ð tr.hidden-md.hidden-sm,Ð th.hidden-md.hidden-sm,Ð td.hidden-md.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-md,Ð tr.hidden-md,Ð th.hidden-md,Ð td.hidden-md {Ð display: none !important;Ð

}ÐÐ@media (min-width: 1200px) {Ð .hidden-md.hidden-lg,Ð tr.hidden-md.hidden-lg,Ð th.hidden-md.hidden-lg,Ð td.hidden-md.hidden-lg {Ð display: none !important;Ð }ÐÐhidden-lg {Ð display: block !important;ÐÐ tr.hidden-lg {Ð display: table-row !important;ÐÐh.hidden-lg,Ðd.hidden-lg {Ð display: table-cell !important;ÐÐ@media (max-width: 767px) {Ð .hidden-lg.hidden-xs,Ð tr.hidden-lg.hidden-xs,Ð th.hidden-lg.hidden-xs,Ð td.hidden-lg.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .hidden-lg.hidden-sm,Ð tr.hidden-lg.hidden-sm,Ð th.hidden-lg.hidden-sm,Ð td.hidden-lg.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-lg.hidden-md,Ð tr.hidden-lg.hidden-md,Ð th.hidden-lg.hidden-md,Ð td.hidden-lg.hidden-md {Ð display: none !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .hidden-lg,Ð tr.hidden-lg,Ð th.hidden-lg,Ð td.hidden-lg {Ð display: none !important;Ð }ÐÐ .visible-print,Ðtr.visible-print,Ðh.visible-print,Ðd.visible-print {Ð display: none !important;ÐÐ@media print {Ð .visible-print {Ð display: block !important;Ð }Ð tr.visible-print {Ð display: table-row !important;Ð }Ð th.visible-print,Ð td.visible-print {Ð display: table-cell !important;Ð }Ð .hidden-print,Ð tr.hidden-print,Ð th.hidden-print,Ð td.hidden-print {Ð display: none !important;Ð }ÐÐ

public\assets\css\plugins\summernote\summernote.css

.note-editor {Ð   height: 300px;ÐÐnote-editor .note-dropzone {Ð   position: absolute;Ð   z-index: 1;Ð   display: none;Ð   color: #87cefa;Ð   background-color: white;Ð   border: 2px dashed #87cefa;Ð   opacity: .95;Ð   pointer-event: noneÐÐnote-editor .note-dropzone .note-dropzone-message {Ð   display: table-cell;Ð   font-size: 28px;Ð   font-weight: bold;Ð   text-align: center;Ð   vertical-align: middleÐÐnote-editor .note-dropzone.hover {Ð   color: #098ddf;Ð   border: 2px dashed #098ddfÐÐnote-editor.dragover .note-dropzone {Ð   display: tableÐÐnote-editor.fullscreen {Ð   position: fixed;Ð   top: 0;Ð   left: 0;Ð   z-index: 1050;Ð   width: 100%ÐÐnote-editor.fullscreen .note-editable {Ð   background-color: whiteÐÐnote-editor.fullscreen .note-resizebar {Ð   display: noneÐÐnote-editor.codeview .note-editable {Ð   display: noneÐÐ .note-editor.codeview .note-codable {Ð   display: blockÐÐnote-editor .note-toolbar {Ð   padding-bottom: 5px;Ð   padding-left: 10px;Ð   padding-top: 5px;Ð   margin: 0;Ð   background-color: #f5f5f5;Ð   border-bottom: 1px solid #E7EAECÐÐnote-editor .note-toolbar > .btn-group {Ð   margin-top: 5px;Ð margin-right: 5px;Ð   margin-left: 0ÐÐnote-editor .note-toolbar .note-table .dropdown-menu {Ð   min-width: 0;Ð   padding: 5pxÐÐnote-editor .note-toolbar .note-table .dropdown-menu .note-dimension-picker {Ð   font-size: 18pxÐ }Ðnote-editor .note-toolbar .note-table .dropdown-menu .note-dimension-picker .note-dimension-picker-mousecatcher {Ð   position: absolute !important;Ð   z-index: 3;Ð   width: 10em;Ð   height: 10em;Ð   cursor: pointerÐÐnote-editor .note-toolbar .note-table .dropdown-menu .note-dimension-picker .note-dimension-picker-unhighlighted {Ð   position: relative !important;Ð   z-index: 1;Ð   width: 5em;Ð   height: 5em;Ð   background: url('') repeatÐÐnote-editor .note-toolbar .note-table .dropdown-menu .note-dimension-picker .note-dimension-picker-highlighted {Ð   position: absolute !important;Ð   z-index: 2;Ð   width: 1em;Ð   height: 1em;Ð   background: url('') repeatÐÐnote-editor .note-toolbar .note-style h1, .note-editor .note-toolbar .note-style h2, .note-editor .note-toolbar .note-style h3, .note-editor .note-toolbar .note-style h4, .note-editor .note-toolbar .note-style h5, .note-editor .note-toolbar .note-style h6, .note-editor .note-toolbar .note-style blockquote {Ð   margin: 0ÐÐnote-editor .note-toolbar .note-color .dropdown-toggle {Ð   width: 20px;Ð padding-left: 5pxÐÐnote-editor .note-toolbar .note-color .dropdown-menu {Ð min-width: 290pxÐÐnote-editor .note-toolbar .note-color .dropdown-menu .btn-group {Ð   margin: 0ÐÐnote-editor .note-toolbar .note-color .dropdown-menu .btn-group:first-child {Ð   margin: 0 5pxÐÐnote-editor .note-toolbar .note-color .dropdown-menu .btn-group .note-palette-title {Ð margin: 2px 7px;Ð   font-size: 12px;Ð   text-align: center;Ð   border-bottom: 1px solid #eeeÐÐnote-editor .note-toolbar .note-color .dropdown-menu .btn-group .note-color-reset {Ð   padding: 0 3px;Ð   margin: 5px;Ð   font-size: 12px;Ð   cursor: pointer;Ð   -webkit-border-radius: 5px;Ð   -moz-border-radius: 5px;Ð   border-radius: 5pxÐÐnote-editor .note-toolbar .note-color .dropdown-menu .btn-group .note-color-reset:hover {Ð   background: #eeeÐÐ .note-editor .note-toolbar .note-para .dropdown-menu {Ð   min-width: 216px;Ð   padding: 5pxÐÐnote-editor .note-toolbar .note-para .dropdown-menu > div:first-child {Ð   margin-right: 5pxÐÐnote-editor .note-statusbar {Ð background-color: #f5f5f5ÐÐnote-editor .note-statusbar .note-resizebar {Ð width: 100%;Ð   height: 8px;Ð   cursor: s-resize;Ð   border-top: 1px solid #a9a9a9ÐÐnote-editor .note-statusbar .note-resizebar .note-icon-bar {Ð width: 20px;Ð   margin: 1px auto;Ð   border-top: 1px solid #a9a9a9ÐÐnote-editor .note-popover .popover {Ð   max-width: noneÐÐnote-editor .note-popover .popover .popover-content {Ð

padding: 5px;ÐÐnote-editor .note-popover .popover .popover-content a {Ð display: inline-block;Ð max-width: 200px;Ð overflow: hidden;Ð text-overflow: ellipsis;Ð white-space: nowrap;Ð vertical-align: middleÐÐnote-editor .note-popover .popover .popover-content .btn-group + .btn-group {Ð margin-left: 5pxÐÐnote-editor .note-popover .popover .arrow {Ð left: 20pxÐÐnote-editor .note-handle .note-control-selection {Ð position: absolute;Ð display: none;Ð border: 1px solid blackÐÐnote-editor .note-handle .note-control-selection > div {Ð position: absoluteÐÐnote-editor .note-handle .note-control-selection .note-control-selection-bg {Ð width: 100%;Ð height: 100%;Ð background-color: black;Ð -webkit-opacity: .3;Ð -khtml-opacity: .3;Ð -moz-opacity: .3;Ð opacity: .3;Ð -ms-filter: alpha(opacity=30);Ð filter: alpha(opacity=30)ÐÐnote-editor .note-handle .note-control-selection .note-control-handle {Ð width: 7px;Ð height: 7px;Ð border: 1px solid blackÐÐnote-editor .note-handle .note-control-selection .note-control-holder {Ð width: 7px;Ð height: 7px;Ð border: 1px solid blackÐÐnote-editor .note-handle .note-control-selection .note-control-sizing {Ð width: 7px;Ð height: 7px;Ð background-color: white;Ð border: 1px solid blackÐÐnote-editor .note-handle .note-control-selection .note-control-nw {Ð top: -5px;Ð left: -5px;Ð border-right: 0;Ð border-bottom: 0ÐÐnote-editor .note-handle .note-control-selection .note-control-ne {Ð top: -5px;Ð right: -5px;Ð border-bottom: 0;Ð border-left: noneÐÐnote-editor .note-handle .note-control-selection .note-control-sw {Ð bottom: -5px;Ð left: -5px;Ð border-top: 0;Ð border-right: 0ÐÐnote-editor .note-handle .note-control-selection .note-control-se {Ð right: -5px;Ð bottom: -5px;Ð cursor: se-resizeÐÐnote-editor .note-handle .note-control-selection .note-control-selection-info {Ð right: 0;Ð bottom: 0;Ð padding: 5px;Ð margin: 5px;Ð font-size: 12px;Ð color: white;Ð background-color: black;Ð -webkit-border-radius: 5px;Ð -moz-border-radius: 5px;Ð border-radius: 5px;Ð -webkit-opacity: .7;Ð -khtml-opacity: .7;Ð -moz-opacity: .7;Ð opacity: .7;Ð -ms-filter: alpha(opacity=70);Ð filter: alpha(opacity=70)ÐÐnote-editor .note-dialog > div {Ð display: noneÐÐnote-editor .note-dialog .note-image-dialog .note-dropzone {Ð min-height: 100px;Ð margin-bottom: 10px;Ð font-size: 30px;Ð line-height: 4;Ð color: lightgray;Ð text-align: center;Ð border: 4px dashed lightgrayÐÐnote-editor .note-dialog .note-help-dialog {Ð font-size: 12px;Ð color: #ccc;Ð background: transparent;Ð background-color: #222 !important;Ð border: 0;Ð -webkit-opacity: .9;Ð -khtml-opacity: .9;Ð -moz-opacity: .9;Ð opacity: .9;Ð -ms-filter: alpha(opacity=90);Ð filter: alpha(opacity=90)ÐÐnote-editor .note-dialog .note-help-dialog .modal-content {Ð background: transparent;Ð border: 1px solid white;Ð -webkit-border-radius: 5px;Ð -moz-border-radius: 5px;Ð border-radius: 5px;Ð -webkit-box-shadow: none;Ð -moz-box-shadow: none;Ð box-shadow: noneÐÐnote-editor .note-dialog .note-help-dialog a {Ð font-size: 12px;Ð color: whiteÐÐ .note-editor .note-dialog .note-help-dialog .title {Ð padding-bottom: 5px;Ð font-size: 14px;Ð font-weight: bold;Ð color: white;Ð border-bottom: white 1px solidÐÐnote-editor .note-dialog .note-help-dialog .modal-close {Ð font-size: 14px;Ð color: #dd0;Ð cursor: pointerÐÐnote-editor .note-dialog .note-help-dialog .note-shortcut-layout {Ð width: 100%ÐÐnote-editor .note-dialog .note-help-dialog .note-shortcut-layout td {Ð vertical-align: topÐÐnote-editor .note-dialog .note-help-dialog .note-shortcut {Ð margin-top: 8pxÐÐnote-editor .note-dialog .note-help-dialog .note-shortcut th {Ð font-size: 13px;Ð color: #dd0;Ð text-align: leftÐÐnote-editor .note-dialog .note-help-dialog .note-shortcut td:first-child {Ð min-width: 110px;Ð padding-right: 10px;Ð font-family: "Courier New";Ð color: #dd0;Ð text-align: rightÐÐnote-editor .note-editable {Ð padding: 20px;Ð overflow: auto;Ð outline: 0ÐÐnote-editor .note-editable[contenteditable="false"] {Ð background-color: #e5e5e5ÐÐnote-editor .note-codable {Ð display: none;Ð width: 100%;Ð padding: 10px;Ð margin-bottom: 0;Ð

font-family: Menlo, Monaco, monospace, sans-serif;Đ font-size: 14px;Đ color: #ccc;Đ background-color: #222;Đ border: 0;Đ -webkit-border-radius: 0;Đ -moz-border-radius: 0;Đ border-radius: 0;Đ box-shadow: none;Đ -webkit-box-sizing: border-box;Đ -moz-box-sizing: border-box;Đ -ms-box-sizing: border-box;Đ box-sizing: border-box;Đ resize: noneÞÞnote-editor .dropdown-menu {Đ min-width: 90pxÞÞnote-editor .dropdown-menu.right {Đ right: 0;Đ left: autoÞÞnote-editor .dropdown-menu.right::before {Đ right: 9px;Đ left: auto !importantÞÞ .note-editor .dropdown-menu.right::after {Đ right: 10px;Đ left: auto !importantÞÞnote-editor .dropdown-menu li a i {Đ color: deepskyblue;Đ visibility: hiddenÞÞnote-editor .dropdown-menu li a.checked i {Đ visibility: visibleÞÞnote-editor .note-fontsize-10 {Đ font-size: 10pxÞÞnote-editor .note-color-palette {Đ line-height: 1ÞÞnote-editor .note-color-palette div .note-color-btn {Đ width: 17px;Đ height: 17px;Đ padding: 0;Đ margin: 0;Đ border: 1px solid #fffÞÞnote-editor .note-color-palette div .note-color-btn:hover {Đ border: 1px solid #000Þ

public\assets\css\plugins\switchery\switchery.css

```
/*Ð*Ð* Main stylesheet for Switchery.Ð* http://abpetkov.github.io/switchery/Ð*Ð
 */Ðswitchery {Ð   background-color: #fff;Ð   border: 1px solid #dfdfdf;Ð
border-radius: 20px;Ð   cursor: pointer;Ð   display: inline-block;Ð   height:
30px;Ð   position: relative;Ð   vertical-align: middle;Ð   width: 50px;Ð   -
webkit-box-sizing: content-box;Ð   -moz-box-sizing: content-box;Ð   box-
sizing: content-box;ÐÐswitchery > small {Ð   background: #fff;Ð   border-
radius: 100%;Ð   box-shadow: 0 1px 3px rgba(0, 0, 0, 0.4);Ð   height: 30px;Ð
    position: absolute;Ð   top: 0;Ð   width: 30px;Ð
```

public\assets\css\plugins\toastr\toastr.min.css

.toast-title {Ð   font-weight: 700;ÐÐ.toast-message {Ð   -ms-word-wrap: break-word;Ð   word-wrap: break-word;ÐÐ.toast-message a, .toast-message label {Ð   color: #fff;ÐÐ.toast-message a:hover {Ð   color: #ccc;Ð   text-decoration: none;ÐÐ.toast-close-button {Ð   position: relative;Ð   right: -.3em;Ð   top: -.3em;Ð   float: right;Ð   font-size: 20px;Ð   font-weight: 700;Ð   color: #fff;Ð   -webkit-text-shadow: 0 1px 0 #fff;Ð   text-shadow: 0 1px 0 #fff;Ð   opacity: .8;Ð   -ms-filter: alpha(Opacity=80);Ð   filter: alpha(opacity=80);ÐÐ.toast-close-button:focus, .toast-close-button:hover {Ð   color: #000;Ð   text-decoration: none;Ð   cursor: pointer;Ð   opacity: .4;Ð   -ms-filter: alpha(Opacity=40);Ð   filter: alpha(opacity=40);ÐÐbutton.toast-close-button {Ð   padding: 0;Ð   cursor: pointer;Ð   background: 0 0;Ð   border: 0;Ð   -webkit-appearance: none;ÐÐ.toast-top-center {Ð   top: 0;Ð   right: 0;Ð   width: 100%;ÐÐ.toast-bottom-center {Ð   bottom: 0;Ð   right: 0;Ð   width: 100%;ÐÐ.toast-top-full-width {Ð   top: 0;Ð   right: 0;Ð   width: 100%;ÐÐ.toast-bottom-full-width {Ð   bottom: 0;Ð   right: 0;Ð   width: 100%;ÐÐ.toast-top-left {Ð   top: 12px;Ð   left: 12px;ÐÐ.toast-top-right {Ð   top: 12px;Ð   right: 12px;ÐÐ.toast-bottom-right {Ð   right: 12px;Ð   bottom: 12px;ÐÐ.toast-bottom-left {Ð   bottom: 12px;Ð   left: 12px;ÐÐ.toast-container {Ð   position: fixed;Ð   z-index: 999999;ÐÐ.toast-container * {Ð   -moz-box-sizing: border-box;Ð   -webkit-box-sizing: border-box;Ð   box-sizing: border-box;ÐÐ.toast-container > div {Ð   position: relative;Ð   overflow: hidden;Ð   margin: 0 0 6px;Ð   padding: 15px 15px 15px 50px;Ð   width: 300px;Ð   -moz-border-radius: 3px;Ð   -webkit-border-radius: 3px;Ð   border-radius: 3px;Ð   background-position: 15px center;Ð   background-repeat: no-repeat;Ð   -moz-box-shadow: 0 0 12px #999;Ð   -webkit-box-shadow: 0 0 12px #999;Ð   box-shadow: 0 0 12px #999;Ð   color: #fff;Ð   opacity: .8;Ð   -ms-filter: alpha(Opacity=80);Ð   filter: alpha(opacity=80);ÐÐ.toast-container > :hover {Ð   -moz-box-shadow: 0 0 12px #000;Ð   -webkit-box-shadow: 0 0 12px #000;Ð   box-shadow: 0 0 12px #000;Ð   opacity: 1;Ð   -ms-filter: alpha(Opacity=100);Ð   filter: alpha(opacity=100);Ð   cursor: pointer;ÐÐ.toast-container > .toast-info {Ð   background-image: url() !importantÐÐ#toast-container > .toast-error {Ð   background-image: url() !importantÐÐ#toast-container > .toast-success {Ð   background-image: url() !

importantÐÐtoast-container > .toast-warning {Ð   background-image:
url(
R0IArs4c6QAAAARnQU1BAACxjwv8YQUAAAAJcEhZcwAADsMAAA7DAcdvqGQAAAGYSURBVEhL5ZSvTs
NQFMbXZGICMYGYmJhAQIJAICYQPAACiSDB8AiICQQJT4CqQEwgJvYASAQCiZiYmJhAIBATCARJy+9r
Tsldd8sKu1M0+dLb057v6/lbq/2rK0mS/TRNj9cWNAKPYIJII7gIxCcQ51cvqID+GIEX8ASG4B1bK5
gIZFeQfoJdEXOfgX4QAQg7kH2A65yQ87lyxb27sggkAzAuFhbbg1K2kgCkB1bVwyIR9m2L7PRPIhDU
IXgGtyKw575yz3lTNs6X4JXnjV+LKM/m3MydnTbtOKIjtz6VhCBq4vSm3ncdrD2lk0VgUXSVKjVDJX
JzijW1RQdsU7F77He8u68koNZTz8Oz5yGa6J3H3lZ0xYgXBK2QymlWWA+RWnYhskLBv2vmE+hBMCtb
A7KX5drWyRT/2JsqZ2IvfB9Y4bWDNMFbJRFmC9E74SoS0CqulwjkC0+5bpcV1CZ8NMej4pjy0U+doD
QsGyo1hzVJttIjhQ7GnBtRFN1UarUlH8F3xict+HY07rEzoUGPlWcjRFRr4/
gChZgc3ZL2d8oAAAAASUVORK5CYII=) !importantÐÐtoast-container.toast-bottom-
center > div, #toast-container.toast-top-center > div {Ð   width: 300px;Ð
margin: autoÐÐtoast-container.toast-bottom-full-width > div, #toast-
container.toast-top-full-width > div {Ð   width: 96%;Ð   margin: autoÐÐtoast {Ð
    background-color: #030303ÐÐtoast-success {Ð   background-color: #51a351ÐÐ
.toast-error {Ð   background-color: #bd362fÐÐtoast-info {Ð   background-
color: #2f96b4ÐÐtoast-warning {Ð   background-color: #f89406ÐÐtoast-progress {Ð
    position: absolute;Ð   left: 0;Ð   bottom: 0;Ð   height: 4px;Ð
background-color: #000;Ð   opacity: .4;Ð   -ms-filter: alpha(Opacity=40);Ð
filter: alpha(opacity=40)ÐÐ@media all and (max-width: 240px) {Ð   #toast-
container > div {Ð   padding: 8px 8px 8px 50px;Ð   width: 11emÐ   }Ð
    #toast-container .toast-close-button {Ð   right: -.2em;Ð   top:
-.2emÐ   }ÐÐ@media all and (min-width: 241px) and (max-width: 480px) {Ð
#toast-container > div {Ð   padding: 8px 8px 8px 50px;Ð   width: 18emÐ
    }Ð   #toast-container .toast-close-button {Ð   right: -.2em;Ð
top: -.2emÐ   }ÐÐ@media all and (min-width: 481px) and (max-width: 768px) {Ð
#toast-container > div {Ð   padding: 15px 15px 15px 50px;Ð   width:
25emÐ   }Ð

public\assets\css\plugins\touchspin\jquery.bootstrap-touchspin.min.css

```
/*Ð*  Bootstrap TouchSpin - v3.0.1Ð*  A mobile and touch friendly input
spinner component for Bootstrap 3.Ð*  http://www.virtuosoft.eu/code/bootstrap-
touchspin/Ð*Ð*  Made by István Ujj-MészárosÐ*  Under Apache License v2.0
LicenseÐ*/Ðbootstrap-touchspin .input-group-btn-
vertical{position:relative;white-space:nowrap;width:1%;vertical-
align:middle;display:table-cell}.bootstrap-touchspin .input-group-btn-
vertical>.btn{display:block;float:none;width:100%;max-width:100%;padding:8px
10px;margin-left:-1px;position:relative}.bootstrap-touchspin .input-group-btn-
vertical .bootstrap-touchspin-up{border-radius:0;border-top-right-
radius:4px}.bootstrap-touchspin .input-group-btn-vertical .bootstrap-
touchspin-down{margin-top:-2px;border-radius:0;border-bottom-right-
radius:4px}.bootstrap-touchspin .input-group-btn-vertical
i{position:absolute;top:3px;left:5px;font-size:9px;font-weight:400}
```

public\assets\dist\cropper.css

/*!Ð* Cropper.js v1.0.0-rc.3Ð* https://github.com/fengyuanchen/cropperjsÐ*Ð* Copyright (c) 2017 Fengyuan ChenÐ* Released under the MIT licenseÐ*Ð* Date: 2017-07-07T12:56:42.462ZÐ*/Ðcropper-container {Ð font-size: 0;Ð line-height: 0;Ð position: relative;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð user-select: none;Ð direction: ltr;Ð -ms-touch-action: none;Ð touch-action: none;}ÐÐcropper-container img {Ð /* Avoid margin top issue (Occur only when margin-top <= -height) */Ð display: block;Ð min-width: 0 !important;Ð max-width: none !important;Ð min-height: 0 !important;Ð max-height: none !important;Ð width: 100%;Ð height: 100%;Ð image-orientation: 0deg;}ÐÐcropper-wrap-box,Ðcropper-canvas,Ðcropper-drag-box,Ð .cropper-crop-box,Ðcropper-modal {Ð position: absolute;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;}ÐÐcropper-wrap-box {Ð overflow: hidden;}ÐÐcropper-drag-box {Ð opacity: 0;Ð background-color: #fff;}ÐÐcropper-modal {Ð opacity: .5;Ð background-color: #000;}ÐÐcropper-view-box {Ð display: block;Ð overflow: hidden;Ð width: 100%;Ð height: 100%;Ð outline: 1px solid #39f;Ð outline-color: rgba(51, 153, 255, 0.75);}ÐÐcropper-dashed {Ð position: absolute;Ð display: block;Ð opacity: .5;Ð border: 0 dashed #eee;}ÐÐcropper-dashed.dashed-h {Ð top: 33.33333%;Ð left: 0;Ð width: 100%;Ð height: 33.33333%;Ð border-top-width: 1px;Ð border-bottom-width: 1px;}ÐÐcropper-dashed.dashed-v {Ð top: 0;Ð left: 33.33333%;Ð width: 33.33333%;Ð height: 100%;Ð border-right-width: 1px;Ð border-left-width: 1px;}ÐÐcropper-center {Ð position: absolute;Ð top: 50%;Ð left: 50%;Ð display: block;Ð width: 0;Ð height: 0;Ð opacity: .75;}ÐÐcropper-center:before,Ð .cropper-center:after {Ð position: absolute;Ð display: block;Ð content: ' ';Ð background-color: #eee;}ÐÐcropper-center:before {Ð top: 0;Ð left: -3px;Ð width: 7px;Ð height: 1px;}ÐÐcropper-center:after {Ð top: -3px;Ð left: 0;Ð width: 1px;Ð height: 7px;}ÐÐcropper-face,Ðcropper-line,Ðcropper-point {Ð position: absolute;Ð display: block;Ð width: 100%;Ð height: 100%;Ð opacity: .1;}ÐÐcropper-face {Ð top: 0;Ð left: 0;Ð background-color: #fff;}ÐÐ .cropper-line {Ð background-color: #39f;}ÐÐcropper-line.line-e {Ð top: 0;Ð right: -3px;Ð width: 5px;Ð cursor: e-resize;}ÐÐcropper-line.line-n {Ð top: -3px;Ð left: 0;Ð height: 5px;Ð cursor: n-resize;}ÐÐcropper-line.line-w {Ð top: 0;Ð left: -3px;Ð width: 5px;Ð cursor: w-resize;}ÐÐcropper-line.line-s {Ð bottom: -3px;Ð left: 0;Ð height: 5px;Ð cursor: s-resize;}ÐÐcropper-point {Ð width: 5px;Ð height: 5px;Ð opacity: .75;Ð background-color: #39f;}ÐÐcropper-point.point-e {Ð top: 50%;Ð right: -3px;Ð margin-top: -3px;Ð cursor: e-resize;}ÐÐcropper-point.point-n {Ð top: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: n-resize;}ÐÐ .cropper-point.point-w {Ð top: 50%;Ð left: -3px;Ð margin-top: -3px;Ð cursor: w-resize;}ÐÐcropper-point.point-s {Ð bottom: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: s-resize;}ÐÐcropper-point.point-ne {Ð top: -3px;Ð right: -3px;Ð cursor: ne-resize;}ÐÐcropper-point.point-nw {Ð top: -3px;Ð left: -3px;Ð cursor: nw-resize;}ÐÐcropper-point.point-sw {Ð bottom: -3px;Ð left: -3px;Ð cursor: sw-resize;}ÐÐcropper-point.point-se {Ð right: -3px;Ð bottom: -3px;Ð width: 20px;Ð height: 20px;Ð cursor: se-resize;Ð opacity: 1;}ÐÐmedia (min-width: 768px) {Ð .cropper-point.point-se {Ð width: 15px;Ð height: 15pxÐ }}ÐÐmedia (min-width: 992px) {Ð .cropper-point.point-se {Ð width: 10px;Ð height: 10pxÐ }}ÐÐ @media (min-width: 1200px) {Ð .cropper-point.point-se {Ð width: 5px;Ð height: 5px;Ð opacity: .75Ð }}ÐÐcropper-point.point-se:before {Ð position: absolute;Ð right: -50%;Ð bottom: -50%;Ð display: block;Ð width: 200%;Ð height: 200%;Ð content: ' ';Ð opacity: 0;Ð background-color: #39f;}ÐÐcropper-invisible {Ð opacity: 0;}ÐÐcropper-bg {Ð background-image: url('');}ÐÐcropper-hide {Ð position: absolute;Ð display: block;Ð width: 0;Ð height: 0;}ÐÐcropper-hidden {Ð display: none !important;}ÐÐcropper-move {Ð cursor: move;}ÐÐcropper-crop {Ð cursor: crosshair;}ÐÐ .cropper-disabled .cropper-drag-box,Ðcropper-disabled .cropper-face,Ðcropper-disabled .cropper-line,Ðcropper-disabled .cropper-point {Ð cursor: not-allowed;Ð

}Ð

public\assets\dist\cropper.min.css

/*!Ð* Cropper.js v1.0.0-rc.3Ð* https://github.com/fengyuanchen/cropperjsÐ*Ð* Copyright (c) 2017 Fengyuan ChenÐ* Released under the MIT licenseÐ*Ð* Date: 2017-07-07T12:56:42.462ZÐ*/Ðcropper-container {Ð font-size: 0;Ð line-height: 0;Ð position: relative;Ð -webkit-user-select: none;Ð -moz-user-select: none;Ð -ms-user-select: none;Ð user-select: none;Ð direction: ltr;Ð -ms-touch-action: none;Ð touch-action: noneÞÐcropper-container img {Ð /* Avoid margin top issue (Occur only when margin-top <= -height) */Ð display: block;Ð min-width: 0 !important;Ð max-width: none !important;Ð min-height: 0 !important;Ð max-height: none !important;Ð width: 100%;Ð height: 100%;Ð image-orientation: 0degÞÐcropper-wrap-box,Ðcropper-canvas,Ðcropper-drag-box,Ð .cropper-crop-box,Ðcropper-modal {Ð position: absolute;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;ÞÐcropper-wrap-box {Ð overflow: hidden;ÞÐcropper-drag-box {Ð opacity: 0;Ð background-color: #fff;ÞÐcropper-modal {Ð opacity: .5;Ð background-color: #000;ÞÐcropper-view-box {Ð display: block;Ð overflow: hidden;Ð width: 100%;Ð height: 100%;Ð outline: 1px solid #39f;Ð outline-color: rgba(51, 153, 255, 0.75);ÞÐcropper-dashed {Ð position: absolute;Ð display: block;Ð opacity: .5;Ð border: 0 dashed #eeeÞÐcropper-dashed.dashed-h {Ð top: 33.33333%;Ð left: 0;Ð width: 100%;Ð height: 33.33333%;Ð border-top-width: 1px;Ð border-bottom-width: 1pxÞÐcropper-dashed.dashed-v {Ð top: 0;Ð left: 33.33333%;Ð width: 33.33333%;Ð height: 100%;Ð border-right-width: 1px;Ð border-left-width: 1pxÞÐcropper-center {Ð position: absolute;Ð top: 50%;Ð left: 50%;Ð display: block;Ð width: 0;Ð height: 0;Ð opacity: .75ÞÐcropper-center:before,Ð .cropper-center:after {Ð position: absolute;Ð display: block;Ð content: ' ';Ð background-color: #eeeÞÐcropper-center:before {Ð top: 0;Ð left: -3px;Ð width: 7px;Ð height: 1pxÞÐcropper-center:after {Ð top: -3px;Ð left: 0;Ð width: 1px;Ð height: 7pxÞÐcropper-face,Ðcropper-line,Ðcropper-point {Ð position: absolute;Ð display: block;Ð width: 100%;Ð height: 100%;Ð opacity: .1;ÞÐcropper-face {Ð top: 0;Ð left: 0;Ð background-color: #fff;ÞÐ .cropper-line {Ð background-color: #39fÞÐcropper-line.line-e {Ð top: 0;Ð right: -3px;Ð width: 5px;Ð cursor: e-resizeÞÐcropper-line.line-n {Ð top: -3px;Ð left: 0;Ð height: 5px;Ð cursor: n-resizeÞÐcropper-line.line-w {Ð top: 0;Ð left: -3px;Ð width: 5px;Ð cursor: w-resizeÞÐcropper-line.line-s {Ð bottom: -3px;Ð left: 0;Ð height: 5px;Ð cursor: s-resizeÞÐcropper-point {Ð width: 5px;Ð height: 5px;Ð opacity: .75;Ð background-color: #39fÞÐcropper-point.point-e {Ð top: 50%;Ð right: -3px;Ð margin-top: -3px;Ð cursor: e-resizeÞÐcropper-point.point-n {Ð top: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: n-resizeÞÐ .cropper-point.point-w {Ð top: 50%;Ð left: -3px;Ð margin-top: -3px;Ð cursor: w-resizeÞÐcropper-point.point-s {Ð bottom: -3px;Ð left: 50%;Ð margin-left: -3px;Ð cursor: s-resizeÞÐcropper-point.point-ne {Ð top: -3px;Ð right: -3px;Ð cursor: ne-resizeÞÐcropper-point.point-nw {Ð top: -3px;Ð left: -3px;Ð cursor: nw-resizeÞÐcropper-point.point-sw {Ð bottom: -3px;Ð left: -3px;Ð cursor: sw-resizeÞÐcropper-point.point-se {Ð right: -3px;Ð bottom: -3px;Ð width: 20px;Ð height: 20px;Ð cursor: se-resize;Ð opacity: 1ÞÐmedia (min-width: 768px) {Ð .cropper-point.point-se {Ð width: 15px;Ð height: 15pxÐ }ÞÐmedia (min-width: 992px) {Ð .cropper-point.point-se {Ð width: 10px;Ð height: 10pxÐ }ÞÐ @media (min-width: 1200px) {Ð .cropper-point.point-se {Ð width: 5px;Ð height: 5px;Ð opacity: .75Ð }ÞÐcropper-point.point-se:before {Ð position: absolute;Ð right: -50%;Ð bottom: -50%;Ð display: block;Ð width: 200%;Ð height: 200%;Ð content: ' ';Ð opacity: 0;Ð background-color: #39fÞÐcropper-invisible {Ð opacity: 0;ÞÐcropper-bg {Ð background-image: url('
TjRV2AAAACXBIWXMAAArrAAAK6wGCiw1aAAAAHHRFWHRTb2Z0d2FyZQBBZG9iZSBGaXJld29ya3MgQ1M26LyyjAAAA
AgBVhF/0PAH6/D/HkDxOGAAAAAElFTkSuQmCC');ÞÐcropper-hide {Ð position: absolute;Ð display: block;Ð width: 0;Ð height: 0;ÞÐcropper-hidden {Ð display: none !important;ÞÐcropper-move {Ð cursor: move;ÞÐcropper-crop {Ð cursor: crosshair;ÞÐ .cropper-disabled .cropper-drag-box,Ðcropper-disabled .cropper-face,Ðcropper-disabled .cropper-line,Ðcropper-disabled .cropper-point {Ð cursor: not-allowed;Ð

}Ð

public\assets\editor\codemirror.css

/* BASICS */ÐCodeMirror {Ð /* Set height, width, borders, and global font properties here */Ð font-family: monospace;Ð height: 550px;ÞÐCodeMirror-scroll {Ð /* Set scrolling behaviour here */Ð overflow: auto;ÞÐ* PADDING */Ð .CodeMirror-lines {Ð padding: 4px 0; /* Vertical padding around content */ÞÐ .CodeMirror pre {Ð padding: 0 4px; /* Horizontal padding of content */ÞÐ .CodeMirror-scrollbar-filler {Ð background-color: white; /* The little square between H and V scrollbars */ÞÐ* GUTTER */ÐCodeMirror-gutters {Ð border-right: 1px solid #ddd;Ð background-color: #f7f7f7;ÞÐCodeMirror-linenumbers {}Ð .CodeMirror-linenumber {Ð padding: 0 3px 0 5px;Ð min-width: 20px;Ð text-align: right;Ð color: #999;ÞÐ* CURSOR */ÐCodeMirror div.CodeMirror-cursor {Ð border-left: 1px solid black;Ð z-index: 3;ÞÐ* Shown when moving in bi-directional text */ÐCodeMirror div.CodeMirror-secondarycursor {Ð border-left: 1px solid silver;ÞÐCodeMirror.cm-keymap-fat-cursor div.CodeMirror-cursor {Ð width: auto;Ð border: 0;Ð background: #7e7;Ð z-index: 1;ÞÐ* Can style cursor different in overwrite (non-insert) mode */ÐCodeMirror div.CodeMirror-cursor.CodeMirror-overwrite {}Ðcm-tab { display: inline-block; }Ð* DEFAULT THEME */Ðcm-s-default .cm-keyword {color: #708;}Ðcm-s-default .cm-atom {color: #219;}Ðcm-s-default .cm-number {color: #164;}Ðcm-s-default .cm-def {color: #00f;}Ðcm-s-default .cm-variable {color: black;}Ðcm-s-default .cm-variable-2 {color: #05a;}Ðcm-s-default .cm-variable-3 {color: #085;}Ðcm-s-default .cm-property {color: black;}Ðcm-s-default .cm-operator {color: black;}Ð .cm-s-default .cm-comment {color: #a50;}Ðcm-s-default .cm-string {color: #a11;}Ðcm-s-default .cm-string-2 {color: #f50;}Ðcm-s-default .cm-meta {color: #555;}Ðcm-s-default .cm-error {color: #f00;}Ðcm-s-default .cm-qualifier {color: #555;}Ðcm-s-default .cm-builtin {color: #30a;}Ðcm-s-default .cm-bracket {color: #997;}Ðcm-s-default .cm-tag {color: #170;}Ðcm-s-default .cm-attribute {color: #00c;}Ðcm-s-default .cm-header {color: blue;}Ðcm-s-default .cm-quote {color: #090;}Ðcm-s-default .cm-hr {color: #999;}Ðcm-s-default .cm-link {color: #00c;}Ðcm-negative {color: #d44;}Ðcm-positive {color: #292;}Ðcm-header, .cm-strong {font-weight: bold;}Ðcm-em {font-style: italic;}Ðcm-link {text-decoration: underline;}Ðcm-invalidchar {color: #f00;}Ð div.CodeMirror span.CodeMirror-matchingbracket {color: #0f0;}Ðdiv.CodeMirror span.CodeMirror-nonmatchingbracket {color: #f22;}Ð* STOP */Ð* The rest of this file contains styles related to the mechanics ofÐ the editor. You probably shouldn't touch them. */ÐCodeMirror {Ð line-height: 1;Ð position: relative;Ð overflow: hidden;Ð background: white;Ð color: black;ÞÐCodeMirror-scroll {Ð /* 30px is the magic margin used to hide the element's real scrollbars */Ð /* See overflow: hidden in .CodeMirror */Ð margin-bottom: -30px; margin-right: -30px;Ð padding-bottom: 30px; padding-right: 30px;Ð height: 100%;Ð outline: none; /* Prevent dragging from highlighting the element */Ð position: relative;ÞÐCodeMirror-sizer {Ð position: relative;ÞÐ* The fake, visible scrollbars. Used to force redraw during scrollingÐ before actuall scrolling happens, thus preventing shaking andÐ flickering artifacts. */ÐCodeMirror-vscrollbar, .CodeMirror-hscrollbar, .CodeMirror-scrollbar-filler {Ð position: absolute;Ð z-index: 6;Ð display: none;ÞÐ .CodeMirror-vscrollbar {Ð right: 0; top: 0;Ð overflow-x: hidden;Ð overflow-y: scroll;ÞÐCodeMirror-hscrollbar {Ð bottom: 0; left: 0;Ð overflow-y: hidden;Ð overflow-x: scroll;ÞÐCodeMirror-scrollbar-filler {Ð right: 0; bottom: 0;Ð z-index: 6;ÞÐCodeMirror-gutters {Ð position: absolute; left: 0; top: 0;Ð height: 100%;Ð padding-bottom: 30px;Ð z-index: 3;ÞÐCodeMirror-gutter {Ð height: 100%;Ð padding-bottom: 30px;Ð margin-bottom: -32px;Ð display: inline-block;Ð /* Hack to make IE7 behave */Ð *zoom:1;Ð *display:inline;ÞÐCodeMirror-gutter-elt {Ð position: absolute;Ð cursor: default;Ð z-index: 4;ÞÐCodeMirror-lines {Ð cursor: text;ÞÐCodeMirror pre {Ð /* Reset some styles that the rest of the page might have set */Ð -moz-border-radius: 0; -webkit-border-radius: 0; border-radius: 0;Ð border-width: 0;Ð background: transparent;Ð font-family: inherit;Ð font-size: inherit;Ð margin: 0;Ð white-space: pre;Ð word-wrap: normal;Ð line-height: inherit;Ð color: inherit;Ð z-index: 2;Ð position: relative;Ð

overflow: visible;ÐÐCodeMirror-wrap pre {Ð word-wrap: break-word;Ð white-space: pre-wrap;Ð word-break: normal;ÐÐCodeMirror-linebackground {Ð position: absolute;Ð left: 0; right: 0; top: 0; bottom: 0;Ð z-index: 0;ÐÐ .CodeMirror-linewidget {Ð position: relative;Ð z-index: 2;Ð overflow: auto;ÐÐ .CodeMirror-widget {Ð display: inline-block;ÐÐCodeMirror-wrap .CodeMirror-scroll {Ð overflow-x: hidden;ÐÐCodeMirror-measure {Ð position: absolute;Ð width: 100%; height: 0px;Ð overflow: hidden;Ð visibility: hidden;ÐÐCodeMirror-measure pre { position: static; }ÐCodeMirror div.CodeMirror-cursor {Ð position: absolute;Ð visibility: hidden;Ð border-right: none;Ð width: 0;ÐÐ .CodeMirror-focused div.CodeMirror-cursor {Ð visibility: visible;ÐÐCodeMirror-selected { background: #d9d9d9; }ÐCodeMirror-focused .CodeMirror-selected { background: #d7d4f0; }Ðcm-searching {Ð background: #ffa;Ð background: rgba(255, 255, 0, .4);ÐÐ* IE7 hack to prevent it from returning funny offsetTops on the spans */ÐCodeMirror span { *vertical-align: text-bottom; }Ð @media print {Ð /* Hide the cursor when printing */Ð .CodeMirror div.CodeMirror-cursor {Ð visibility: hidden;Ð }ÐÐ

public\assets\font-awesome\css\font-awesome.css

/*!Ð* Font Awesome 4.3.0 by @davegandy - http://fontawesome.io - @fontawesomeÐ
 * License - http://fontawesome.io/license (Font: SIL OFL 1.1, CSS: MIT License)Ð*/Ð* FONT PATHÐ* ---------- */Ð@font-face {Ð font-family: 'FontAwesome';Ð src: url('../fonts/fontawesome-webfont.eot?v=4.3.0');Ð
  src: url('../fonts/fontawesome-webfont.eot?#iefix&v=4.3.0') format('embedded-opentype'), url('../fonts/fontawesome-webfont.woff2?v=4.3.0') format('woff2'), url('../fonts/fontawesome-webfont.woff?v=4.3.0') format('woff'), url('../fonts/fontawesome-webfont.ttf?v=4.3.0') format('truetype'), url('../fonts/fontawesome-webfont.svg?v=4.3.0#fontawesomeregular') format('svg');Ð font-weight: normal;Ð font-style: normal;ÞÐfa {Ð display: inline-block;Ð font: normal normal normal 14px/1 FontAwesome;Ð font-size: inherit;Ð text-rendering: auto;Ð -webkit-font-smoothing: antialiased;Ð -moz-osx-font-smoothing: grayscale;Ð transform: translate(0, 0);ÞÐ* makes the font 33% larger relative to the icon container */Ðfa-lg {Ð font-size: 1.33333333em;Ð line-height: 0.75em;Ð vertical-align: -15%;ÞÐfa-2x {Ð font-size: 2em;ÞÐfa-3x {Ð font-size: 3em;ÞÐfa-4x {Ð font-size: 4em;ÞÐfa-5x {Ð font-size: 5em;ÞÐfa-fw {Ð width: 1.28571429em;Ð text-align: center;ÞÐfa-ul {Ð padding-left: 0;Ð margin-left: 2.14285714em;Ð list-style-type: none;ÞÐfa-ul > li {Ð position: relative;ÞÐfa-li {Ð position: absolute;Ð left: -2.14285714em;Ð width: 2.14285714em;Ð top: 0.14285714em;Ð text-align: center;ÞÐfa-li.fa-lg {Ð left: -1.85714286em;ÞÐfa-border {Ð padding: .2em .25em .15em;Ð border: solid 0.08em #eeeeee;Ð border-radius: .1em;ÞÐpull-right {Ð float: right;ÞÐpull-left {Ð float: left;ÞÐ .fa.pull-left {Ð margin-right: .3em;ÞÐfa.pull-right {Ð margin-left: .3em;ÞÐfa-spin {Ð -webkit-animation: fa-spin 2s infinite linear;Ð animation: fa-spin 2s infinite linear;ÞÐfa-pulse {Ð -webkit-animation: fa-spin 1s infinite steps(8);Ð
  animation: fa-spin 1s infinite steps(8);Þ@-webkit-keyframes fa-spin {Ð 0% {Ð
    -webkit-transform: rotate(0deg);Ð   transform: rotate(0deg);Ð }Ð 100% {Ð
    -webkit-transform: rotate(359deg);Ð   transform: rotate(359deg);Ð }ÞÐ @keyframes fa-spin {Ð 0% {Ð   -webkit-transform: rotate(0deg);Ð   transform: rotate(0deg);Ð }Ð 100% {Ð   -webkit-transform: rotate(359deg);Ð   transform: rotate(359deg);Ð }ÞÐfa-rotate-90 {Ð filter: progid:DXImageTransform.Microsoft.BasicImage(rotation=1);Ð -webkit-transform: rotate(90deg);Ð -ms-transform: rotate(90deg);Ð transform: rotate(90deg);ÞÐfa-rotate-180 {Ð filter: progid:DXImageTransform.Microsoft.BasicImage(rotation=2);Ð -webkit-transform: rotate(180deg);Ð -ms-transform: rotate(180deg);Ð transform: rotate(180deg);ÞÐ .fa-rotate-270 {Ð filter: progid:DXImageTransform.Microsoft.BasicImage(rotation=3);Ð -webkit-transform: rotate(270deg);Ð -ms-transform: rotate(270deg);Ð transform: rotate(270deg);ÞÐ .fa-flip-horizontal {Ð filter: progid:DXImageTransform.Microsoft.BasicImage(rotation=0, mirror=1);Ð -webkit-transform: scale(-1, 1);Ð -ms-transform: scale(-1, 1);Ð transform: scale(-1, 1);ÞÐfa-flip-vertical {Ð filter: progid:DXImageTransform.Microsoft.BasicImage(rotation=2, mirror=1);Ð -webkit-transform: scale(1, -1);Ð -ms-transform: scale(1, -1);Ð transform: scale(1, -1);ÞÐroot .fa-rotate-90,Ðroot .fa-rotate-180,Ðroot .fa-rotate-270,Ðroot .fa-flip-horizontal,Ðroot .fa-flip-vertical {Ð filter: none;ÞÐfa-stack {Ð position: relative;Ð display: inline-block;Ð width: 2em;Ð height: 2em;Ð line-height: 2em;Ð vertical-align: middle;ÞÐfa-stack-1x,Ðfa-stack-2x {Ð position: absolute;Ð left: 0;Ð width: 100%;Ð text-align: center;ÞÐfa-stack-1x {Ð line-height: inherit;ÞÐfa-stack-2x {Ð font-size: 2em;ÞÐfa-inverse {Ð color: #ffffff;ÞÐ* Font Awesome uses the Unicode Private Use Area (PUA) to ensure screenÐ readers do not read off random characters that represent icons */Ðfa-glass:before {Ð content: "\f000";ÞÐfa-music:before {Ð content: "\f001";ÞÐfa-search:before {Ð content: "\f002";ÞÐfa-envelope-o:before {Ð content: "\f003";ÞÐ .fa-heart:before {Ð content: "\f004";ÞÐfa-star:before {Ð content: "\f005";ÞÐ .fa-star-o:before {Ð content: "\f006";ÞÐfa-user:before {Ð content: "\f007";ÞÐ .fa-film:before {Ð

content: "\f008";ÐÐfa-th-large:before {Ð content: "\f009";ÐÐ
.fa-th:before {Ð content: "\f00a";ÐÐfa-th-list:before {Ð content: "\f00b";ÐÐ
.fa-check:before {Ð content: "\f00c";ÐÐfa-remove:before,Ðfa-close:before,Ðfa-
times:before {Ð content: "\f00d";ÐÐfa-search-plus:before {Ð content: "\f00e";ÐÐ
.fa-search-minus:before {Ð content: "\f010";ÐÐfa-power-off:before {Ð content:
"\f011";ÐÐfa-signal:before {Ð content: "\f012";ÐÐfa-gear:before,Ðfa-
cog:before {Ð content: "\f013";ÐÐfa-trash-o:before {Ð content: "\f014";ÐÐfa-
home:before {Ð content: "\f015";ÐÐfa-file-o:before {Ð content: "\f016";ÐÐfa-
clock-o:before {Ð content: "\f017";ÐÐfa-road:before {Ð content: "\f018";ÐÐfa-
download:before {Ð content: "\f019";ÐÐfa-arrow-circle-o-down:before {Ð
content: "\f01a";ÐÐfa-arrow-circle-o-up:before {Ð content: "\f01b";ÐÐfa-
inbox:before {Ð content: "\f01c";ÐÐfa-play-circle-o:before {Ð content:
"\f01d";ÐÐfa-rotate-right:before,Ðfa-repeat:before {Ð content: "\f01e";ÐÐfa-
refresh:before {Ð content: "\f021";ÐÐfa-list-alt:before {Ð content: "\f022";ÐÐ
.fa-lock:before {Ð content: "\f023";ÐÐfa-flag:before {Ð content: "\f024";ÐÐfa-
headphones:before {Ð content: "\f025";ÐÐfa-volume-off:before {Ð content:
"\f026";ÐÐfa-volume-down:before {Ð content: "\f027";ÐÐfa-volume-up:before {Ð
content: "\f028";ÐÐfa-qrcode:before {Ð content: "\f029";ÐÐfa-barcode:before {Ð
content: "\f02a";ÐÐfa-tag:before {Ð content: "\f02b";ÐÐfa-tags:before {Ð
content: "\f02c";ÐÐfa-book:before {Ð content: "\f02d";ÐÐfa-bookmark:before {Ð
content: "\f02e";ÐÐfa-print:before {Ð content: "\f02f";ÐÐfa-camera:before {Ð
content: "\f030";ÐÐfa-font:before {Ð content: "\f031";ÐÐfa-bold:before {Ð
content: "\f032";ÐÐfa-italic:before {Ð content: "\f033";ÐÐfa-text-
height:before {Ð content: "\f034";ÐÐfa-text-width:before {Ð content: "\f035";ÐÐ
.fa-align-left:before {Ð content: "\f036";ÐÐfa-align-center:before {Ð
content: "\f037";ÐÐfa-align-right:before {Ð content: "\f038";ÐÐfa-align-
justify:before {Ð content: "\f039";ÐÐfa-list:before {Ð content: "\f03a";ÐÐfa-
dedent:before,Ðfa-outdent:before {Ð content: "\f03b";ÐÐfa-indent:before {Ð
content: "\f03c";ÐÐfa-video-camera:before {Ð content: "\f03d";ÐÐfa-
photo:before,Ðfa-image:before,Ðfa-picture-o:before {Ð content: "\f03e";ÐÐfa-
pencil:before {Ð content: "\f040";ÐÐfa-map-marker:before {Ð content: "\f041";ÐÐ
.fa-adjust:before {Ð content: "\f042";ÐÐfa-tint:before {Ð content: "\f043";ÐÐ
.fa-edit:before,Ðfa-pencil-square-o:before {Ð content: "\f044";ÐÐfa-share-
square-o:before {Ð content: "\f045";ÐÐfa-check-square-o:before {Ð content:
"\f046";ÐÐfa-arrows:before {Ð content: "\f047";ÐÐfa-step-backward:before {Ð
content: "\f048";ÐÐfa-fast-backward:before {Ð content: "\f049";ÐÐfa-
backward:before {Ð content: "\f04a";ÐÐfa-play:before {Ð content: "\f04b";ÐÐfa-
pause:before {Ð content: "\f04c";ÐÐfa-stop:before {Ð content: "\f04d";ÐÐfa-
forward:before {Ð content: "\f04e";ÐÐfa-fast-forward:before {Ð content:
"\f050";ÐÐfa-step-forward:before {Ð content: "\f051";ÐÐfa-eject:before {Ð
content: "\f052";ÐÐfa-chevron-left:before {Ð content: "\f053";ÐÐfa-chevron-
right:before {Ð content: "\f054";ÐÐfa-plus-circle:before {Ð content: "\f055";ÐÐ
.fa-minus-circle:before {Ð content: "\f056";ÐÐfa-times-circle:before {Ð
content: "\f057";ÐÐfa-check-circle:before {Ð content: "\f058";ÐÐfa-question-
circle:before {Ð content: "\f059";ÐÐfa-info-circle:before {Ð content: "\f05a";Ð
}Ðfa-crosshairs:before {Ð content: "\f05b";ÐÐfa-times-circle-o:before {Ð
content: "\f05c";ÐÐfa-check-circle-o:before {Ð content: "\f05d";ÐÐfa-
ban:before {Ð content: "\f05e";ÐÐfa-arrow-left:before {Ð content: "\f060";ÐÐ
.fa-arrow-right:before {Ð content: "\f061";ÐÐfa-arrow-up:before {Ð content:
"\f062";ÐÐfa-arrow-down:before {Ð content: "\f063";ÐÐfa-mail-forward:before,Ð
.fa-share:before {Ð content: "\f064";ÐÐfa-expand:before {Ð content: "\f065";ÐÐ
.fa-compress:before {Ð content: "\f066";ÐÐfa-plus:before {Ð content: "\f067";ÐÐ
.fa-minus:before {Ð content: "\f068";ÐÐfa-asterisk:before {Ð content: "\f069";Ð
}Ðfa-exclamation-circle:before {Ð content: "\f06a";ÐÐfa-gift:before {Ð
content: "\f06b";ÐÐfa-leaf:before {Ð content: "\f06c";ÐÐfa-fire:before {Ð
content: "\f06d";ÐÐfa-eye:before {Ð content: "\f06e";ÐÐfa-eye-slash:before {Ð
content: "\f070";ÐÐfa-warning:before,Ðfa-exclamation-triangle:before {Ð
content: "\f071";ÐÐfa-plane:before {Ð content: "\f072";ÐÐfa-calendar:before {Ð
content: "\f073";ÐÐfa-random:before {Ð content: "\f074";ÐÐfa-comment:before
{Ð

content: "\f075";ÐÐfa-magnet:before {Ð content: "\f076";ÐÐfa-chevron-up:before {Ð content: "\f077";ÐÐfa-chevron-down:before {Ð content: "\f078";ÐÐ .fa-retweet:before {Ð content: "\f079";ÐÐfa-shopping-cart:before {Ð content: "\f07a";ÐÐfa-folder:before {Ð content: "\f07b";ÐÐfa-folder-open:before {Ð content: "\f07c";ÐÐfa-arrows-v:before {Ð content: "\f07d";ÐÐfa-arrows-h:before {Ð content: "\f07e";ÐÐfa-bar-chart-o:before,Ðfa-bar-chart:before {Ð content: "\f080";ÐÐfa-twitter-square:before {Ð content: "\f081";ÐÐfa-facebook-square:before {Ð content: "\f082";ÐÐfa-camera-retro:before {Ð content: "\f083";ÐÐfa-key:before {Ð content: "\f084";ÐÐfa-gears:before,Ðfa-cogs:before {Ð content: "\f085";ÐÐfa-comments:before {Ð content: "\f086";ÐÐfa-thumbs-o-up:before {Ð content: "\f087";ÐÐfa-thumbs-o-down:before {Ð content: "\f088";ÐÐ .fa-star-half:before {Ð content: "\f089";ÐÐfa-heart-o:before {Ð content: "\f08a";ÐÐfa-sign-out:before {Ð content: "\f08b";ÐÐfa-linkedin-square:before {Ð content: "\f08c";ÐÐfa-thumb-tack:before {Ð content: "\f08d";ÐÐfa-external-link:before {Ð content: "\f08e";ÐÐfa-sign-in:before {Ð content: "\f090";ÐÐfa-trophy:before {Ð content: "\f091";ÐÐfa-github-square:before {Ð content: "\f092";ÐÐfa-upload:before {Ð content: "\f093";ÐÐfa-lemon-o:before {Ð content: "\f094";ÐÐfa-phone:before {Ð content: "\f095";ÐÐfa-square-o:before {Ð content: "\f096";ÐÐfa-bookmark-o:before {Ð content: "\f097";ÐÐfa-phone-square:before {Ð content: "\f098";ÐÐfa-twitter:before {Ð content: "\f099";ÐÐ .fa-facebook-f:before,Ðfa-facebook:before {Ð content: "\f09a";ÐÐfa-github:before {Ð content: "\f09b";ÐÐfa-unlock:before {Ð content: "\f09c";ÐÐfa-credit-card:before {Ð content: "\f09d";ÐÐfa-rss:before {Ð content: "\f09e";ÐÐ .fa-hdd-o:before {Ð content: "\f0a0";ÐÐfa-bullhorn:before {Ð content: "\f0a1";Ð }Ðfa-bell:before {Ð content: "\f0f3";ÐÐfa-certificate:before {Ð content: "\f0a3";ÐÐfa-hand-o-right:before {Ð content: "\f0a4";ÐÐfa-hand-o-left:before {Ð content: "\f0a5";ÐÐfa-hand-o-up:before {Ð content: "\f0a6";ÐÐfa-hand-o-down:before {Ð content: "\f0a7";ÐÐfa-arrow-circle-left:before {Ð content: "\f0a8";ÐÐfa-arrow-circle-right:before {Ð content: "\f0a9";ÐÐfa-arrow-circle-up:before {Ð content: "\f0aa";ÐÐfa-arrow-circle-down:before {Ð content: "\f0ab";ÐÐfa-globe:before {Ð content: "\f0ac";ÐÐfa-wrench:before {Ð content: "\f0ad";ÐÐfa-tasks:before {Ð content: "\f0ae";ÐÐfa-filter:before {Ð content: "\f0b0";ÐÐfa-briefcase:before {Ð content: "\f0b1";ÐÐfa-arrows-alt:before {Ð content: "\f0b2";ÐÐfa-group:before,Ðfa-users:before {Ð content: "\f0c0";ÐÐfa-chain:before,Ðfa-link:before {Ð content: "\f0c1";ÐÐfa-cloud:before {Ð content: "\f0c2";ÐÐfa-flask:before {Ð content: "\f0c3";ÐÐfa-cut:before,Ðfa-scissors:before {Ð content: "\f0c4";ÐÐfa-copy:before,Ðfa-files-o:before {Ð content: "\f0c5";ÐÐfa-paperclip:before {Ð content: "\f0c6";ÐÐfa-save:before,Ð .fa-floppy-o:before {Ð content: "\f0c7";ÐÐfa-square:before {Ð content: "\f0c8";ÐÐfa-navicon:before,Ðfa-reorder:before,Ðfa-bars:before {Ð content: "\f0c9";ÐÐfa-list-ul:before {Ð content: "\f0ca";ÐÐfa-list-ol:before {Ð content: "\f0cb";ÐÐfa-strikethrough:before {Ð content: "\f0cc";ÐÐfa-underline:before {Ð content: "\f0cd";ÐÐfa-table:before {Ð content: "\f0ce";ÐÐ .fa-magic:before {Ð content: "\f0d0";ÐÐfa-truck:before {Ð content: "\f0d1";ÐÐ .fa-pinterest:before {Ð content: "\f0d2";ÐÐfa-pinterest-square:before {Ð content: "\f0d3";ÐÐfa-google-plus-square:before {Ð content: "\f0d4";ÐÐfa-google-plus:before {Ð content: "\f0d5";ÐÐfa-money:before {Ð content: "\f0d6";ÐÐ .fa-caret-down:before {Ð content: "\f0d7";ÐÐfa-caret-up:before {Ð content: "\f0d8";ÐÐfa-caret-left:before {Ð content: "\f0d9";ÐÐfa-caret-right:before {Ð content: "\f0da";ÐÐfa-columns:before {Ð content: "\f0db";ÐÐfa-unsorted:before,Ð .fa-sort:before {Ð content: "\f0dc";ÐÐfa-sort-down:before,Ðfa-sort-desc:before {Ð content: "\f0dd";ÐÐfa-sort-up:before,Ðfa-sort-asc:before {Ð content: "\f0de";ÐÐfa-envelope:before {Ð content: "\f0e0";ÐÐfa-linkedin:before {Ð content: "\f0e1";ÐÐfa-rotate-left:before,Ðfa-undo:before {Ð content: "\f0e2";ÐÐfa-legal:before,Ðfa-gavel:before {Ð content: "\f0e3";ÐÐ .fa-dashboard:before,Ðfa-tachometer:before {Ð content: "\f0e4";ÐÐfa-comment-o:before {Ð content: "\f0e5";ÐÐfa-comments-o:before {Ð content: "\f0e6";ÐÐfa-flash:before,Ðfa-bolt:before {Ð content: "\f0e7";ÐÐfa-sitemap:before {Ð content: "\f0e8";ÐÐfa-umbrella:before {Ð content: "\f0e9";ÐÐfa-paste:before,Ð .fa-clipboard:before {Ð

content: "\f0ea";ÐÐfa-lightbulb-o:before {Ð content: "\f0eb";ÐÐfa-exchange:before {Ð content: "\f0ec";ÐÐfa-cloud-download:before {Ð content: "\f0ed";ÐÐfa-cloud-upload:before {Ð content: "\f0ee";ÐÐfa-user-md:before {Ð content: "\f0f0";ÐÐfa-stethoscope:before {Ð content: "\f0f1";ÐÐ.fa-suitcase:before {Ð content: "\f0f2";ÐÐfa-bell-o:before {Ð content: "\f0a2";ÐÐfa-coffee:before {Ð content: "\f0f4";ÐÐfa-cutlery:before {Ð content: "\f0f5";ÐÐfa-file-text-o:before {Ð content: "\f0f6";ÐÐfa-building-o:before {Ð content: "\f0f7";ÐÐfa-hospital-o:before {Ð content: "\f0f8";ÐÐfa-ambulance:before {Ð content: "\f0f9";ÐÐfa-medkit:before {Ð content: "\f0fa";ÐÐ.fa-fighter-jet:before {Ð content: "\f0fb";ÐÐfa-beer:before {Ð content: "\f0fc";ÐÐfa-h-square:before {Ð content: "\f0fd";ÐÐfa-plus-square:before {Ð content: "\f0fe";ÐÐfa-angle-double-left:before {Ð content: "\f100";ÐÐfa-angle-double-right:before {Ð content: "\f101";ÐÐfa-angle-double-up:before {Ð content: "\f102";ÐÐfa-angle-double-down:before {Ð content: "\f103";ÐÐfa-angle-left:before {Ð content: "\f104";ÐÐfa-angle-right:before {Ð content: "\f105";ÐÐ.fa-angle-up:before {Ð content: "\f106";ÐÐfa-angle-down:before {Ð content: "\f107";ÐÐfa-desktop:before {Ð content: "\f108";ÐÐfa-laptop:before {Ð content: "\f109";ÐÐfa-tablet:before {Ð content: "\f10a";ÐÐfa-mobile-phone:before,Ðfa-mobile:before {Ð content: "\f10b";ÐÐfa-circle-o:before {Ð content: "\f10c";ÐÐfa-quote-left:before {Ð content: "\f10d";ÐÐfa-quote-right:before {Ð content: "\f10e";ÐÐfa-spinner:before {Ð content: "\f110";ÐÐfa-circle:before {Ð content: "\f111";ÐÐfa-mail-reply:before,Ðfa-reply:before {Ð content: "\f112";ÐÐfa-github-alt:before {Ð content: "\f113";ÐÐfa-folder-o:before {Ð content: "\f114";ÐÐfa-folder-open-o:before {Ð content: "\f115";ÐÐ.fa-smile-o:before {Ð content: "\f118";ÐÐfa-frown-o:before {Ð content: "\f119";ÐÐfa-meh-o:before {Ð content: "\f11a";ÐÐfa-gamepad:before {Ð content: "\f11b";ÐÐfa-keyboard-o:before {Ð content: "\f11c";ÐÐfa-flag-o:before {Ð content: "\f11d";ÐÐfa-flag-checkered:before {Ð content: "\f11e";ÐÐfa-terminal:before {Ð content: "\f120";ÐÐfa-code:before {Ð content: "\f121";ÐÐfa-mail-reply-all:before,Ðfa-reply-all:before {Ð content: "\f122";ÐÐfa-star-half-empty:before,Ðfa-star-half-full:before,Ðfa-star-half-o:before {Ð content: "\f123";ÐÐfa-location-arrow:before {Ð content: "\f124";ÐÐfa-crop:before {Ð content: "\f125";ÐÐfa-code-fork:before {Ð content: "\f126";ÐÐfa-unlink:before,Ð.fa-chain-broken:before {Ð content: "\f127";ÐÐfa-question:before {Ð content: "\f128";ÐÐfa-info:before {Ð content: "\f129";ÐÐfa-exclamation:before {Ð content: "\f12a";ÐÐfa-superscript:before {Ð content: "\f12b";ÐÐfa-subscript:before {Ð content: "\f12c";ÐÐfa-eraser:before {Ð content: "\f12d";ÐÐ.fa-puzzle-piece:before {Ð content: "\f12e";ÐÐfa-microphone:before {Ð content: "\f130";ÐÐfa-microphone-slash:before {Ð content: "\f131";ÐÐfa-shield:before {Ð content: "\f132";ÐÐfa-calendar-o:before {Ð content: "\f133";ÐÐ.fa-fire-extinguisher:before {Ð content: "\f134";ÐÐfa-rocket:before {Ð content: "\f135";ÐÐfa-maxcdn:before {Ð content: "\f136";ÐÐfa-chevron-circle-left:before {Ð content: "\f137";ÐÐfa-chevron-circle-right:before {Ð content: "\f138";ÐÐfa-chevron-circle-up:before {Ð content: "\f139";ÐÐfa-chevron-circle-down:before {Ð content: "\f13a";ÐÐfa-html5:before {Ð content: "\f13b";ÐÐfa-css3:before {Ð content: "\f13c";ÐÐfa-anchor:before {Ð content: "\f13d";ÐÐfa-unlock-alt:before {Ð content: "\f13e";ÐÐfa-bullseye:before {Ð content: "\f140";ÐÐfa-ellipsis-h:before {Ð content: "\f141";ÐÐfa-ellipsis-v:before {Ð content: "\f142";ÐÐfa-rss-square:before {Ð content: "\f143";ÐÐfa-play-circle:before {Ð content: "\f144";ÐÐfa-ticket:before {Ð content: "\f145";ÐÐfa-minus-square:before {Ð content: "\f146";ÐÐfa-minus-square-o:before {Ð content: "\f147";ÐÐfa-level-up:before {Ð content: "\f148";ÐÐfa-level-down:before {Ð content: "\f149";ÐÐfa-check-square:before {Ð content: "\f14a";ÐÐ.fa-pencil-square:before {Ð content: "\f14b";ÐÐfa-external-link-square:before {Ð content: "\f14c";ÐÐfa-share-square:before {Ð content: "\f14d";ÐÐfa-compass:before {Ð content: "\f14e";ÐÐfa-toggle-down:before,Ðfa-caret-square-o-down:before {Ð content: "\f150";ÐÐfa-toggle-up:before,Ðfa-caret-square-o-up:before {Ð content: "\f151";ÐÐfa-toggle-right:before,Ðfa-caret-square-o-right:before {Ð content: "\f152";ÐÐfa-euro:before,Ðfa-eur:before {Ð content: "\f153";Ð

}Ðfa-gbp:before {Ð content: "\f154";ÞÐfa-dollar:before,Ðfa-usd:before {Ð content: "\f155";ÞÐfa-rupee:before,Ðfa-inr:before {Ð content: "\f156";ÞÐfa-cny:before,Ðfa-rmb:before,Ðfa-yen:before,Ðfa-jpy:before {Ð content: "\f157";ÞÐ .fa-ruble:before,Ðfa-rouble:before,Ðfa-rub:before {Ð content: "\f158";ÞÐfa-won:before,Ðfa-krw:before {Ð content: "\f159";ÞÐfa-bitcoin:before,Ðfa-btc:before {Ð content: "\f15a";ÞÐfa-file:before {Ð content: "\f15b";ÞÐfa-file-text:before {Ð content: "\f15c";ÞÐfa-sort-alpha-asc:before {Ð content: "\f15d";ÞÐfa-sort-alpha-desc:before {Ð content: "\f15e";ÞÐfa-sort-amount-asc:before {Ð content: "\f160";ÞÐfa-sort-amount-desc:before {Ð content: "\f161";ÞÐfa-sort-numeric-asc:before {Ð content: "\f162";ÞÐfa-sort-numeric-desc:before {Ð content: "\f163";ÞÐfa-thumbs-up:before {Ð content: "\f164";ÞÐ .fa-thumbs-down:before {Ð content: "\f165";ÞÐfa-youtube-square:before {Ð content: "\f166";ÞÐfa-youtube:before {Ð content: "\f167";ÞÐfa-xing:before {Ð content: "\f168";ÞÐfa-xing-square:before {Ð content: "\f169";ÞÐfa-youtube-play:before {Ð content: "\f16a";ÞÐfa-dropbox:before {Ð content: "\f16b";ÞÐfa-stack-overflow:before {Ð content: "\f16c";ÞÐfa-instagram:before {Ð content: "\f16d";ÞÐfa-flickr:before {Ð content: "\f16e";ÞÐfa-adn:before {Ð content: "\f170";ÞÐfa-bitbucket:before {Ð content: "\f171";ÞÐfa-bitbucket-square:before {Ð content: "\f172";ÞÐfa-tumblr:before {Ð content: "\f173";ÞÐfa-tumblr-square:before {Ð content: "\f174";ÞÐfa-long-arrow-down:before {Ð content: "\f175";ÞÐfa-long-arrow-up:before {Ð content: "\f176";ÞÐfa-long-arrow-left:before {Ð content: "\f177";ÞÐfa-long-arrow-right:before {Ð content: "\f178";ÞÐfa-apple:before {Ð content: "\f179";ÞÐfa-windows:before {Ð content: "\f17a";ÞÐfa-android:before {Ð content: "\f17b";ÞÐfa-linux:before {Ð content: "\f17c";ÞÐfa-dribbble:before {Ð content: "\f17d";ÞÐfa-skype:before {Ð content: "\f17e";ÞÐfa-foursquare:before {Ð content: "\f180";ÞÐfa-trello:before {Ð content: "\f181";ÞÐfa-female:before {Ð content: "\f182";ÞÐfa-male:before {Ð content: "\f183";ÞÐfa-gittip:before,Ðfa-gratipay:before {Ð content: "\f184";ÞÐfa-sun-o:before {Ð content: "\f185";ÞÐfa-moon-o:before {Ð content: "\f186";ÞÐfa-archive:before {Ð content: "\f187";ÞÐfa-bug:before {Ð content: "\f188";ÞÐfa-vk:before {Ð content: "\f189";ÞÐfa-weibo:before {Ð content: "\f18a";ÞÐfa-renren:before {Ð content: "\f18b";ÞÐfa-pagelines:before {Ð content: "\f18c";ÞÐfa-stack-exchange:before {Ð content: "\f18d";ÞÐfa-arrow-circle-o-right:before {Ð content: "\f18e";ÞÐfa-arrow-circle-o-left:before {Ð content: "\f190";ÞÐfa-toggle-left:before,Ðfa-caret-square-o-left:before {Ð content: "\f191";ÞÐfa-dot-circle-o:before {Ð content: "\f192";ÞÐfa-wheelchair:before {Ð content: "\f193";ÞÐfa-vimeo-square:before {Ð content: "\f194";ÞÐfa-turkish-lira:before,Ðfa-try:before {Ð content: "\f195";ÞÐfa-plus-square-o:before {Ð content: "\f196";ÞÐfa-space-shuttle:before {Ð content: "\f197";ÞÐfa-slack:before {Ð content: "\f198";ÞÐfa-envelope-square:before {Ð content: "\f199";ÞÐfa-wordpress:before {Ð content: "\f19a";ÞÐfa-openid:before {Ð content: "\f19b";ÞÐfa-institution:before,Ðfa-bank:before,Ðfa-university:before {Ð content: "\f19c";ÞÐfa-mortar-board:before,Ðfa-graduation-cap:before {Ð content: "\f19d";ÞÐfa-yahoo:before {Ð content: "\f19e";ÞÐfa-google:before {Ð content: "\f1a0";ÞÐfa-reddit:before {Ð content: "\f1a1";ÞÐfa-reddit-square:before {Ð content: "\f1a2";ÞÐfa-stumbleupon-circle:before {Ð content: "\f1a3";ÞÐfa-stumbleupon:before {Ð content: "\f1a4";ÞÐfa-delicious:before {Ð content: "\f1a5";ÞÐfa-digg:before {Ð content: "\f1a6";ÞÐ .fa-pied-piper:before {Ð content: "\f1a7";ÞÐfa-pied-piper-alt:before {Ð content: "\f1a8";ÞÐfa-drupal:before {Ð content: "\f1a9";ÞÐfa-joomla:before {Ð content: "\f1aa";ÞÐfa-language:before {Ð content: "\f1ab";ÞÐfa-fax:before {Ð content: "\f1ac";ÞÐfa-building:before {Ð content: "\f1ad";ÞÐfa-child:before {Ð content: "\f1ae";ÞÐfa-paw:before {Ð content: "\f1b0";ÞÐfa-spoon:before {Ð content: "\f1b1";ÞÐfa-cube:before {Ð content: "\f1b2";ÞÐfa-cubes:before {Ð content: "\f1b3";ÞÐfa-behance:before {Ð content: "\f1b4";ÞÐfa-behance-square:before {Ð content: "\f1b5";ÞÐfa-steam:before {Ð content: "\f1b6";ÞÐfa-steam-square:before {Ð content: "\f1b7";ÞÐfa-recycle:before {Ð content: "\f1b8";ÞÐfa-automobile:before,Ðfa-car:before {Ð content: "\f1b9";ÞÐfa-cab:before,Ðfa-taxi:before {Ð content: "\f1ba";ÞÐfa-tree:before {Ð content: "\f1bb";Ð

}Ðfa-spotify:before {Ð content: "\f1bc";ÐÐfa-deviantart:before {Ð content: "\f1bd";ÐÐfa-soundcloud:before {Ð content: "\f1be";ÐÐfa-database:before {Ð content: "\f1c0";ÐÐfa-file-pdf-o:before {Ð content: "\f1c1";ÐÐfa-file-word-o:before {Ð content: "\f1c2";ÐÐfa-file-excel-o:before {Ð content: "\f1c3";ÐÐfa-file-powerpoint-o:before {Ð content: "\f1c4";ÐÐfa-file-photo-o:before,Ðfa-file-picture-o:before,Ðfa-file-image-o:before {Ð content: "\f1c5";ÐÐfa-file-zip-o:before,Ðfa-file-archive-o:before {Ð content: "\f1c6";ÐÐfa-file-sound-o:before,Ðfa-file-audio-o:before {Ð content: "\f1c7";ÐÐ.fa-file-movie-o:before,Ðfa-file-video-o:before {Ð content: "\f1c8";ÐÐfa-file-code-o:before {Ð content: "\f1c9";ÐÐfa-vine:before {Ð content: "\f1ca";ÐÐfa-codepen:before {Ð content: "\f1cb";ÐÐfa-jsfiddle:before {Ð content: "\f1cc";ÐÐ.fa-life-bouy:before,Ðfa-life-buoy:before,Ðfa-life-saver:before,Ðfa-support:before,Ðfa-life-ring:before {Ð content: "\f1cd";ÐÐfa-circle-o-notch:before {Ð content: "\f1ce";ÐÐfa-ra:before,Ðfa-rebel:before {Ð content: "\f1d0";ÐÐfa-ge:before,Ðfa-empire:before {Ð content: "\f1d1";ÐÐfa-git-square:before {Ð content: "\f1d2";ÐÐfa-git:before {Ð content: "\f1d3";ÐÐfa-hacker-news:before {Ð content: "\f1d4";ÐÐfa-tencent-weibo:before {Ð content: "\f1d5";ÐÐfa-qq:before {Ð content: "\f1d6";ÐÐfa-wechat:before,Ðfa-weixin:before {Ð content: "\f1d7";ÐÐfa-send:before,Ðfa-paper-plane:before {Ð content: "\f1d8";ÐÐfa-send-o:before,Ðfa-paper-plane-o:before {Ð content: "\f1d9";ÐÐfa-history:before {Ð content: "\f1da";ÐÐfa-genderless:before,Ðfa-circle-thin:before {Ð content: "\f1db";ÐÐfa-header:before {Ð content: "\f1dc";Ð}Ðfa-paragraph:before {Ð content: "\f1dd";ÐÐfa-sliders:before {Ð content: "\f1de";ÐÐfa-share-alt:before {Ð content: "\f1e0";ÐÐfa-share-alt-square:before {Ð content: "\f1e1";ÐÐfa-bomb:before {Ð content: "\f1e2";ÐÐfa-soccer-ball-o:before,Ðfa-futbol-o:before {Ð content: "\f1e3";ÐÐfa-tty:before {Ð content: "\f1e4";ÐÐfa-binoculars:before {Ð content: "\f1e5";ÐÐfa-plug:before {Ð content: "\f1e6";ÐÐfa-slideshare:before {Ð content: "\f1e7";ÐÐ.fa-twitch:before {Ð content: "\f1e8";ÐÐfa-yelp:before {Ð content: "\f1e9";ÐÐ.fa-newspaper-o:before {Ð content: "\f1ea";ÐÐfa-wifi:before {Ð content: "\f1eb";ÐÐfa-calculator:before {Ð content: "\f1ec";ÐÐfa-paypal:before {Ð content: "\f1ed";ÐÐfa-google-wallet:before {Ð content: "\f1ee";ÐÐfa-cc-visa:before {Ð content: "\f1f0";ÐÐfa-cc-mastercard:before {Ð content: "\f1f1";Ð}Ðfa-cc-discover:before {Ð content: "\f1f2";ÐÐfa-cc-amex:before {Ð content: "\f1f3";ÐÐfa-cc-paypal:before {Ð content: "\f1f4";ÐÐfa-cc-stripe:before {Ð content: "\f1f5";ÐÐfa-bell-slash:before {Ð content: "\f1f6";ÐÐfa-bell-slash-o:before {Ð content: "\f1f7";ÐÐfa-trash:before {Ð content: "\f1f8";ÐÐfa-copyright:before {Ð content: "\f1f9";ÐÐfa-at:before {Ð content: "\f1fa";ÐÐfa-eyedropper:before {Ð content: "\f1fb";ÐÐfa-paint-brush:before {Ð content: "\f1fc";ÐÐfa-birthday-cake:before {Ð content: "\f1fd";ÐÐfa-area-chart:before {Ð content: "\f1fe";ÐÐfa-pie-chart:before {Ð content: "\f200";ÐÐfa-line-chart:before {Ð content: "\f201";ÐÐfa-lastfm:before {Ð content: "\f202";ÐÐfa-lastfm-square:before {Ð content: "\f203";ÐÐfa-toggle-off:before {Ð content: "\f204";ÐÐfa-toggle-on:before {Ð content: "\f205";ÐÐfa-bicycle:before {Ð content: "\f206";ÐÐfa-bus:before {Ð content: "\f207";ÐÐfa-ioxhost:before {Ð content: "\f208";ÐÐfa-angellist:before {Ð content: "\f209";ÐÐfa-cc:before {Ð content: "\f20a";ÐÐfa-shekel:before,Ðfa-sheqel:before,Ðfa-ils:before {Ð content: "\f20b";ÐÐfa-meanpath:before {Ð content: "\f20c";ÐÐfa-buysellads:before {Ð content: "\f20d";ÐÐfa-connectdevelop:before {Ð content: "\f20e";ÐÐfa-dashcube:before {Ð content: "\f210";ÐÐfa-forumbee:before {Ð content: "\f211";ÐÐfa-leanpub:before {Ð content: "\f212";ÐÐfa-sellsy:before {Ð content: "\f213";ÐÐfa-shirtsinbulk:before {Ð content: "\f214";ÐÐfa-simplybuilt:before {Ð content: "\f215";ÐÐfa-skyatlas:before {Ð content: "\f216";ÐÐfa-cart-plus:before {Ð content: "\f217";ÐÐfa-cart-arrow-down:before {Ð content: "\f218";ÐÐfa-diamond:before {Ð content: "\f219";ÐÐfa-ship:before {Ð content: "\f21a";ÐÐfa-user-secret:before {Ð content: "\f21b";ÐÐfa-motorcycle:before {Ð content: "\f21c";ÐÐfa-street-view:before {Ð content: "\f21d";ÐÐfa-heartbeat:before {Ð content: "\f21e";ÐÐfa-venus:before {Ð content: "\f221";ÐÐfa-mars:before {Ð content: "\f222";ÐÐfa-mercury:before {Ð content: "\f223";Ð

}Ðfa-transgender:before {Ð content: "\f224";þÐfa-transgender-alt:before {Ð content: "\f225";þÐfa-venus-double:before {Ð content: "\f226";þÐ.fa-mars-double:before {Ð content: "\f227";þÐfa-venus-mars:before {Ð content: "\f228";þÐfa-mars-stroke:before {Ð content: "\f229";þÐfa-mars-stroke-v:before {Ð content: "\f22a";þÐfa-mars-stroke-h:before {Ð content: "\f22b";þÐfa-neuter:before {Ð content: "\f22c";þÐfa-facebook-official:before {Ð content: "\f230";þÐfa-pinterest-p:before {Ð content: "\f231";þÐfa-whatsapp:before {Ð content: "\f232";þÐfa-server:before {Ð content: "\f233";þÐfa-user-plus:before {Ð content: "\f234";þÐfa-user-times:before {Ð content: "\f235";þÐfa-hotel:before,Ðfa-bed:before {Ð content: "\f236";þÐfa-viacoin:before {Ð content: "\f237";þÐfa-train:before {Ð content: "\f238";þÐfa-subway:before {Ð content: "\f239";þÐfa-medium:before {Ð content: "\f23a";þÐ

public\assets\frontend\css\blog-style.css

Ð*ÐF†VÖR æ ÖS¢ 6†ö6ôÖ '2 Ò ×VÇF’× W' ÷6R &ö÷G7G& FV× Æ F¶F†VÖR U$“¢ ‡GG ¢òð
themeforest.net/user/responsiveexpertsÐFW67&— F–öã¢ F†—2 772 f–ÆR —2 f÷" Æ–v‡B
template layout alignmentsÐfW'6–öã¢ ã” WF†÷#¢ &W7 öç6—fR W‡ W'G“ WF†÷" U$“¢
http://themeforest.net/user/responsiveexpertsÐF w3•
’ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÝ”åDU$ä Â tR DTÕ Ä DR 5E”ÄU=
’ÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÒÝ/Ð* Blog Page Styles */Ðblog-page-outr-sec {Ð
padding: 110px 0 200px;Ð text-align: center;ÐÐblog-page-outr-sec .blog-left-
sec {Ð margin-bottom: 0;ÐÐblog-sec-all {ÐÖ &v–â×F÷ £cW ƒ½Ðblog-page-outr-
sec p {Ð padding: 0 10%;ÐÐ*
========== */Ð* index page
styles */Ð*
========== */ÐBlog {Ð padding-
top: 125px;ÐÐblog-outr-sec {Ð FF–æs£ , “ , ½& 6¶w&÷VæC¢3 3 C½FW‡BÐ
align:center;ÐÐblog-outr-sec h2 {Ð color:#fff;ÐÆWGFW"×7 6–æs¢ G ƒ½ line-
height: 48px;Ð margin-bottom: 0;ÐÐblog-box-lft {Ð float: left;Ð
width:50%;Ð ÷6—F–öã¢ &VÆ F—fS½Ðblog-box-lft img {Ð width:100%;ÐÐblog-left-
sec {ÐfÆö C¢ ÆVgC½ padding: 0;Ð& 6¶w&÷VæC¢3333 3C½Ö &v–âÖ&÷GFöÓ¢ 3 ƒ½Ðblog-
box-rgt h5 {Ð6öÆ÷#¢63C–Sc ½Æ–æRÖ†V–v‡C£#‡ ƒ½föçB×6—¦S£ ‡ ƒ½föçBÖf Ö–Ç“¢
'Merriweather Sans', sans-serif;ÐÖ &v–âÖ&÷GFöÓ¢ W ƒ½Ðblog-box-rgt p {Ð
color:#666666;Ð font-size: 14px;Ð line-height: 24px;Ð margin-bottom:
15px;Ð FF–æs¢ ½Ðblog-box-rgt a {Ð font-weight: 400;Ð letter-spacing:
2px;ÐföçB×6—¦S¢ G ƒ½Ðblog-box-rgt {ÐFW‡BÖ Æ–vã¢ ÆVgC½ ÷6—F–öã¢ &VÆ F—fS½
float: left;Ð width:50%;Ð FF–æs£#— , 3 ƒ½Ðblog-sec-all .blog-left-sec:nth-
child(3) .blog-box-lft {Ð float: right!important;ÐÐblog-sec-all .blog-left-
sec:nth-child(4) .blog-box-lft {Ð float: right!important;ÐÐblog-sec-
all .blog-left-sec:nth-child(7) .blog-box-lft {Ð float: right!important;ÐÐ
.blog-sec-all .blog-left-sec:nth-child(8) .blog-box-lft {Ð float: right!
important;ÐÐblog-sec-all .blog-left-sec:nth-child(11) .blog-box-lft {Ð
float: right!important;ÐÐblog-left-sec:hover .blog-box-lft .yellow-
solid ,.blog-right-sec:hover .blog-box-lft .yellow-solid {Ð height: 100%;Ð
opacity: 1;ÐG& ç6—F–öã¢ ÆÂ ã72 V 6R 3½ width:100%;ÐÐyellow-solid {Ð
background:rgba(210,166,98,.6);Ð color:#fff;Ð FF–ær×F÷ ¢ ƒ½ text-
align: center;ÐG& ç6—F–öã¢ ÆÂ ã72 V 6R 3½ ÷6—F–öã¢ '6öÇWFS½ top: 0;Ð
opacity:0;ÐÐyellow-solid img {Ð transition: all 0.3s ease 0s;Ð margin: 0
auto;Ð max-width: 60px;Ð text-align: center;ÐÐ********right-
hover**********/Ðblog-left-sec:hover, .blog-right-sec:hover {Ð
background:#d2a662;Ð display: block;Ð opacity: 1;Ð transition: all 0.3s
ease 0s;ÐÐblog-left-sec:hover .blog-box-rgt h5 ,.blog-right-sec:hover .blog-
box-rgt h5,.blog-left-sec:hover .blog-box-rgt p ,.blog-right-sec:hover .blog-
box-rgt p ,.blog-left-sec:hover .blog-box-rgt a ,.blog-right-sec:hover .blog-
box-rgt a {Ð6öÆ÷#¢6ffc½ÐÐview-full {Ð display: table;Ð margin: 0 auto;Ð
padding-top: 55px;Ð text-align: center;Ðv–GFƒ£ S½Ðview-full a {Ð letter-
spacing: 2px;ÐÐ**********pagination**********/Ðpagination {Ð
margin: 65px 0 0;Ðv–GFƒ£ S½Ðpagination li {Ð display: inline-block;Ð
margin: 2px;Ð&÷&FW#£ , 6öÆ–B 6666663½Ðpagination li a {ÐföçBÖf Ö–Ç“¢
'Varela Round', sans-serif;ÐF—7 Æ “¢ &Æö6³½ font-size: 16px;Ð height:
35px;Ð padding: 6px 12px;Ð text-align: center;Ð text-decoration: none !
important;Ð width: 35px;Ð6öÆ÷#¢3cccccb –× ÷'F çC½Ðpagination li:hover {Ð
border:1px solid #333134;Ð& 6¶w&÷VæC¢3333 3C½6öÆ÷#¢6ffc½Ðpagination li
a:hover {Ð& 6¶w&÷VæC¢3333 3C½6öÆ÷#¢6ffb –× ÷'F çC½Ðpagination
li.active ..pagination li a.active {Ð& 6¶w&÷VæC¢3333 3C½6öÆ÷#¢6ffb –× ÷'F çC½
}Ð* Comment Area */Ðcomment-respond {Ð FF–ær×F÷ £CW ƒ½Ðcomment-respond h5 {Ð
margin-bottom: 15px;ÐÐcomment-sec h4 {Ð font-weight: 800;ÐÐcomment-
notes {Ð font-size: 14px;ÐÐcomment-form {Ð FF–æs£ ½Ö &v–ã£ ½Ð
.comment-form input, .comment-form textarea {Ð FF–æs£w , ½†V–v‡C¢ c ƒ½
margin: 0 0 10px;Ð padding: 7px 25px;ÐföçBÖf Ö–Ç“¢ uf &VÆ &÷VæBrÂ 6 ç2Ð
serif;ÐföçB×vV–v‡C£C ½6öÆ÷#¢3cccccc½&÷&FW#£ ½& 6¶w&÷VæC¢6VVVVVS½v–GFƒ£ S½
font-size:16px;ÐÐrespond-textarea > p {Ð margin: 0 0 10px;ÐÐcomment-form
textarea {Ð

–†V–v‡C¢ S ƒ½ padding-top: 10px;ÐÐcomment-form .form-submit
#submit {Ð FF–æs£g , # ƒ½Ö &v–ã£ ½föçBÖf Ö–Ç“¢ uf &VÆ &÷VæBrÂ 6 ç2Ð
serif;ÐföçB×6–¦S£ ‡ ƒ½ÆWGFW"×7 6–æs£' ƒ½6öÆ÷#¢6fffffc½&÷&FW#£ ½föçBÐ
weight:400;ÐFW‡B×G& ç6f÷&Ó§W W&6 6S½& 6¶w&÷VæC¢63C–Sc ½ transition: all
0.5s ease 0s;Ð -webkit-transition: all 0.5s ease 0s;Ð -moz-transition:
all 0.5s ease 0s;ÐF–7 Æ “¦–æÆ–æR×F &ÆS½v–GFƒ£#cW ƒ½†V–v‡C£c ƒ½Ðcomment-
form .form-submit #submit:hover {Ð6öÆ÷#¢6fffffc½& 6¶w&÷VæC¢6 ƒƒ3Cs½Ðcomment-
form #respond-inputs {Ð FF–æs£ , ½Ðcomment-form #respond-inputs p {Ð
padding:0 0 0 0;ÐÖ &v–ã£ ½fÆö C¦ÆVgC½v–GFƒ£32ã332S½Ðcomment-form
#respond-inputs p:nth-child(2) {Ð FF–æs£ ƒ½Ð* Blog Sidebar Styles */Ð
.slidebar-bg {Ð padding: 25px 10px 30px 20px;Ð& 6¶w&÷VæC¢6VVVVVS½Ö &v–ã£C ,
0 0 0;ÐÐsidebar-content .side-two-bar ul li a {Ð display: block;Ð font-
size: 16px;ÐÐsidebar-content .side-three-bar ul li {Ð&÷&FW"Ö&÷GFöÓ¦æöæS½Ð
.sidebar-content {ÐföçB×6–¦S£ G ƒ½Ðsidebar-content a, .sidebar-content
a:focus {Ð6öÆ÷#¢3cccccb ½FW‡BÖFV6÷& F–öã¦æöæS½Ðsidebar-content a:hover {Ð
color:#333333;ÐFW‡BÖFV6÷& F–öã¦æöæS½Ðsidebar-content h5 {ÐföçBÖf Ö–Ç“¢
'Merriweather Sans', sans-serif;ÐföçB×vV–v‡C£ƒ ½ FF–æs£ ½Ö &v–ã£
15px 0;ÐFW‡BÖ Æ–vã¢ ÆVgC½föçB×6–¦S£ ‡ ƒ½FW‡B×G& ç6f÷&Ó¦6 –F Æ–¦S½
color:#000000;ÐÐsidebar-content ul {Ð FF–æs£ ½Ö &v–ã£ ½Æ–7BÐ
style:none;ÐÐsidebar-content ul li {Ð FF–æs£W , ½Ö &v–ã£ ½&÷&FW"Ð
bottom:1px solid #dbdbdb;ÐÐsidebar-content ul li a {ÐföçB×6–¦S¢ G ƒ½
color: hsl(0, 0%, 50%);Ð letter-spacing: 0;Ð text-decoration: none !
important;Ð text-transform: none;ÐÐwidget_search {Ð& 6¶w&÷VæC¢6VVS½†V–v‡C¢
60px;Ð margin: 0;Ð padding: 12px 15px 0 25px;ÐÐwidget_search .search-
field {Ð FF–æs£W , ƒ½Ö &v–ã£ ½&÷&FW#£ ½föçB×6–¦S£ g ƒ½fÆö C¦ÆVgC½
width:80%;Ð6öÆ÷#¢3cccccc½föçBÖf Ö–Ç“¢ uf &VÆ &÷VæBrÂ 6 ç2×6W&–c½föçBÐ
weight:400;Ð& 6¶w&÷VæC¢6VVS½Ðwidget_search .search-btn {Ð FF–æs£W , ƒ½
margin:0 0 0 0;Ð&÷&FW#£ ½& 6¶w&÷VæC¦æöæS½föçB×6–¦S£ W ƒ½fÆö C§&–v‡C½v–GFƒ£# S½
text-align:right;Ð6öÆ÷#¢3333333½Ð**********Blog-details
page**********/Ðblog-main-details {Ð padding:110px 0 190px;ÐÐblog-
single img {Ð margin-bottom: 40px;Ðv–GFƒ£ S½Ðpost-title h4 {ÐföçBÖf Ö–Ç“¢
'Merriweather Sans', sans-serif;ÐföçB×6–¦S£3g ƒ½föçB×vV–v‡C£ƒ ½FW‡BÐ
transform: none;ÐÖ &v–âÖ&÷GFöÓ£3W ƒ½Ðpost-content {Ð margin-top: 50px;ÐÐ
.post-content h4 {ÐföçBÖf Ö–Ç“¢ uf &VÆ &÷VæBrÂ 6 ç2×6W&–c½Ö &v–âÖ&÷GFöÓ£3 ƒ½Ð
.blog-line {Ð background:#cccccc;Ð margin: 0 0 20px;Ð width: 100%;ÐÐ
.comment-lft {Ð float: left;Ð padding-right: 25px;ÐÐcomment-lft img {Ð
width:100%;ÐÐcomment-rgt {Ð float: right;Ð width: 87%;ÐÐcomment-rgt h5 {Ð
font-family: 'Varela Round', sans-serif;Ð font-size: 16px;Ð font-weight:
400;ÐÐcomment-rgt p {Ð font-size: 14px;ÐÆ–æRÖ†V–v‡C¢ #G ƒ½ margin-bottom:
10px;ÐföçBÖf Ö–Ç“¢ uf &VÆ &÷VæBrÂ 6 ç2×6W&–c½Ðcomment-rgt p span {Ð
color:#999999;ÐÐcomment-rgt a {Ð font-size: 14px;Ð letter-spacing: normal;Ð
    text-transform: capitalize;ÐÐ*
========== */Ð* Media
Query */Ð*
========== */Ðmedia (max-
width:1024px) { /* This media query is written for 1100PX resolution devices
*/Ðblog-sec-all .blog-left-sec:nth-child(3) .blog-box-lft {Ð float: left!
important;ÐÐblog-sec-all .blog-left-sec:nth-child(4) .blog-box-lft {Ð
float: left!important;ÐÐblog-sec-all .blog-left-sec:nth-child(7) .blog-box-
lft {Ð float: left!important;ÐÐblog-sec-all .blog-left-sec:nth-
child(8) .blog-box-lft {Ð float: left!important;ÐÐblog-sec-all .blog-left-
sec:nth-child(11) .blog-box-lft {Ð float: left!important;ÐÐblog-sec-
all .blog-left-sec:nth-child(2n+2) .blog-box-lft {Ð float: right!important;ÐÐ
.blog-sec-all .blog-left-sec:nth-child(2n+2) .blog-box-rgt {ÐÆVgC£ ½Ðcomment-
rgt {Ð width: 84%;ÐÐ@media (max-width:480px) { /* This media query is
written for 1100PX resolution devices */Ðblog-left-sec:hover .blog-box-
rgt, .blog-right-sec:hover .blog-box-rgt {Ð position: static;Ðv–GFƒ£ S½Ð
.blog-box-lft {Ð width: 100%;ÐÐblog-box-rgt {Ð width: 100%;ÐÐblog-box-rgt
{Ð position: static;ÐÐcomment-rgt {Ð margin-top: 20px;Ð width: 100%;ÐÐ
.comment-form #respond-inputs p:nth-child(2) {Ð

```
                                                    padding: 0;ÐÐcomment-form
#respond-inputs p {Ð   float: none;Ð   width: 100%;ÐÐ}ÐÐ
```

public\assets\frontend\css\bootstrap.css

/*!Ð* Bootstrap v3.0.3 (http://getbootstrap.com)Ð* Copyright 2013 Twitter, Inc.Ð* Licensed under http://www.apache.org/licenses/LICENSE-2.0Ð*/Ð*! normalize.css v2.1.3 | MIT License | git.io/normalize */article,Ðaside,Ðdetails,Ð figcaption,Ðfigure,Ðfooter,Ðheader,Ðhgroup,Ðmain,Ðnav,Ðsection,Ðsummary {Ð display: block;ÐÐaudio,Ðcanvas,Ðvideo {Ð display: inline-block;ÐÐaudio:not([controls]) {Ð display: none;Ð height: 0;ÐÐhidden],Ðtemplate {Ð display: none;ÐÐhtml {Ð font-family: sans-serif;Ð -webkit-text-size-adjust: 100%;Ð -ms-text-size-adjust: 100%;ÐÐbody {Ð margin: 0;ÐÐa {Ð background: transparent;ÐÐa:focus {Ð outline: thin dotted;ÐÐa:active,Ða:hover {Ð outline: 0;ÐÐh1 {Ð margin: 0.67em 0;Ð font-size: 2em;ÐÐabbr[title] {Ð border-bottom: 1px dotted;ÐÐb,Ðstrong {Ð font-weight: bold;ÐÐdfn {Ð font-style: italic;ÐÐhr {Ð height: 0;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;ÐÐmark {Ð color: #000;Ð background: #ff0;ÐÐcode,Ðkbd,Ðpre,Ðsamp {Ð font-family: monospace, serif;Ð font-size: 1em;ÐÐ pre {Ð white-space: pre-wrap;ÐÐq {Ð quotes: "\201C" "\201D" "\2018" "\2019";ÐÐ small {Ð font-size: 80%;ÐÐsub,Ðsup {Ð position: relative;Ð font-size: 75%;Ð line-height: 0;Ð vertical-align: baseline;ÐÐsup {Ð top: -0.5em;ÐÐsub {Ð bottom: -0.25em;ÐÐimg {Ð border: 0;ÐÐsvg:not(:root) {Ð overflow: hidden;ÐÐfigure {Ð margin: 0;ÐÐfieldset {Ð padding: 0.35em 0.625em 0.75em;Ð margin: 0 2px;Ð border: 1px solid #c0c0c0;ÐÐlegend {Ð padding: 0;Ð border: 0;ÐÐbutton,Ðinput,Ð select,Ðtextarea {Ð margin: 0;Ð font-family: inherit;Ð font-size: 100%;ÐÐbutton,Ð input {Ð line-height: normal;ÐÐbutton,Ðselect {Ð text-transform: none;ÐÐbutton,Ð html input[type="button"],Ðinput[type="reset"],Ðinput[type="submit"] {Ð cursor: pointer;Ð -webkit-appearance: button;ÐÐbutton[disabled],Ðhtml input[disabled] {Ð cursor: default;ÐÐinput[type="checkbox"],Ðinput[type="radio"] {Ð padding: 0;Ð box-sizing: border-box;ÐÐinput[type="search"] {Ð -webkit-box-sizing: content-box;Ð -moz-box-sizing: content-box;Ð box-sizing: content-box;Ð -webkit-appearance: textfield;ÐÐinput[type="search"]::-webkit-search-cancel-button,Ðinput[type="search"]::-webkit-search-decoration {Ð -webkit-appearance: none;ÐÐbutton::-moz-focus-inner,Ðinput::-moz-focus-inner {Ð padding: 0;Ð border: 0;ÐÐtextarea {Ð overflow: auto;Ð vertical-align: top;ÐÐtable {Ð border-collapse: collapse;Ð border-spacing: 0;ÐÐ@media print {Ð * {Ð color: #000 !important;Ð text-shadow: none !important;Ð background: transparent !important;Ð box-shadow: none !important;Ð }Ð a,Ð a:visited {Ð text-decoration: underline;Ð }Ð a[href]:after {Ð content: " (" attr(href) ")";Ð }Ð abbr[title]:after {Ð content: " (" attr(title) ")";Ð }Ð a[href^="javascript:"]:after,Ð a[href^="#"]:after {Ð content: "";Ð }Ð pre,Ð blockquote {Ð border: 1px solid #999;Ð page-break-inside: avoid;Ð }Ð thead {Ð display: table-header-group;Ð }Ð tr,Ð img {Ð page-break-inside: avoid;Ð }Ð img {Ð max-width: 100% !important;Ð }Ð @page {Ð margin: 2cm .5cm;Ð }Ð p,Ð h2,Ð h3 {Ð orphans: 3;Ð widows: 3;Ð }Ð h2,Ð h3 {Ð page-break-after: avoid;Ð }Ð select {Ð background: #fff !important;Ð }Ð .navbar {Ð display: none;Ð }Ð .table td,Ð .table th {Ð background-color: #fff !important;Ð }Ð .btn > .caret,Ð .dropup > .btn > .caret {Ð border-top-color: #000 !important;Ð }Ð .label {Ð border: 1px solid #000;Ð }Ð .table {Ð border-collapse: collapse !important;Ð }Ð .table-bordered th,Ð .table-bordered td {Ð border: 1px solid #ddd !important;Ð }ÐÐ*,Ð*:before,Ð *:after {Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;ÐÐhtml {Ð font-size: 62.5%;Ð -webkit-tap-highlight-color: rgba(0, 0, 0, 0);ÐÐbody {Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-size: 14px;Ð line-height: 1.428571429;Ð color: #333333;Ð background-color: #ffffff;ÐÐinput,Ðbutton,Ðselect,Ðtextarea {Ð font-family: inherit;Ð font-size: inherit;Ð line-height: inherit;ÐÐa {Ð color: #428bca;Ð text-decoration: none;ÐÐa:hover,Ða:focus {Ð color: #2a6496;Ð text-decoration: underline;ÐÐa:focus {Ð outline: thin dotted;Ð outline: 5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐimg {Ð vertical-align: middle;Ð }ÐÐimg-responsive {Ð display: block;Ð height: auto;Ð max-width: 100%;ÐÐimg-rounded {Ð border-radius: 6px;ÐÐimg-thumbnail {Ð display: inline-block;Ð height: auto;Ð max-width: 100%;Ð padding: 4px;Ð line-height: 1.428571429;Ð background-color: #ffffff;Ð

border: 1px solid #dddddd;Ð border-radius: 4px;Ð -webkit-transition: all 0.2s ease-in-out;Ð transition: all 0.2s ease-in-out;ÐÐimg-circle {Ð border-radius: 50%;ÐÐr {Ð margin-top: 20px;Ð margin-bottom: 20px;Ð border: 0;Ð border-top: 1px solid #eeeeee;ÐÐsr-only {Ð position: absolute;Ð width: 1px;Ð height: 1px;Ð padding: 0;Ð margin: -1px;Ð overflow: hidden;Ð clip: rect(0, 0, 0, 0);Ð border: 0;ÐÐ1,Ð2,Ð3,Ð4,Ð5,Ð6,Ðh1,Ð .h2,Ðh3,Ðh4,Ðh5,Ðh6 {Ð font-family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð font-weight: 500;Ð line-height: 1.1;Ð color: inherit;ÐÐ1 small,Ð2 small,Ð3 small,Ð4 small,Ð5 small,Ð6 small,Ðh1 small,Ðh2 small,Ðh3 small,Ðh4 small,Ðh5 small,Ðh6 small,Ð1 .small,Ð2 .small,Ð3 .small,Ð4 .small,Ð5 .small,Ð h6 .small,Ðh1 .small,Ðh2 .small,Ðh3 .small,Ðh4 .small,Ðh5 .small,Ðh6 .small {Ð font-weight: normal;Ð line-height: 1;Ð color: #999999;ÐÐ1,Ð2,Ð3 {Ð margin-top: 20px;Ð margin-bottom: 10px;ÐÐ1 small,Ð2 small,Ð3 small,Ð1 .small,Ð h2 .small,Ð3 .small {Ð font-size: 65%;ÐÐ4,Ð5,Ð6 {Ð margin-top: 10px;Ð margin-bottom: 10px;ÐÐ4 small,Ð5 small,Ð6 small,Ð4 .small,Ð5 .small,Ð6 .small {Ð font-size: 75%;ÐÐ1,Ðh1 {Ð font-size: 36px;ÐÐ2,Ðh2 {Ð font-size: 30px;ÐÐ3,Ðh3 {Ð font-size: 24px;ÐÐ4,Ðh4 {Ð font-size: 18px;ÐÐ5,Ðh5 {Ð font-size: 14px;ÐÐ6,Ð .h6 {Ð font-size: 12px;ÐÐ {Ð margin: 0 0 10px;ÐÐlead {Ð margin-bottom: 20px;Ð font-size: 16px;Ð font-weight: 200;Ð line-height: 1.4;Ð@media (min-width: 768px) {Ð .lead {Ð font-size: 21px;Ð }ÐÐsmall,Ðsmall {Ð font-size: 85%;ÐÐite {Ð font-style: normal;ÐÐtext-muted {Ð color: #999999;ÐÐtext-primary {Ð color: #428bca;ÐÐtext-primary:hover {Ð color: #3071a9;ÐÐtext-warning {Ð color: #8a6d3b;ÐÐtext-warning:hover {Ð color: #66512c;ÐÐtext-danger {Ð color: #a94442;ÐÐtext-danger:hover {Ð color: #843534;ÐÐtext-success {Ð color: #3c763d;ÐÐtext-success:hover {Ð color: #2b542c;ÐÐtext-info {Ð color: #31708f;ÐÐ .text-info:hover {Ð color: #245269;ÐÐtext-left {Ð text-align: left;ÐÐtext-right {Ð text-align: right;ÐÐtext-center {Ð text-align: center;ÐÐpage-header {Ð padding-bottom: 9px;Ð margin: 40px 0 20px;Ð border-bottom: 1px solid #eeeeee;ÐÐl,Ðl {Ð margin-top: 0;Ð margin-bottom: 10px;ÐÐl ul,Ðl ul,Ðl ol,Ðl ol {Ð margin-bottom: 0;ÐÐlist-unstyled {Ð padding-left: 0;Ð list-style: none;ÐÐ .list-inline {Ð padding-left: 0;Ð list-style: none;ÐÐlist-inline > li {Ð display: inline-block;Ð padding-right: 5px;Ð padding-left: 5px;ÐÐlist-inline > li:first-child {Ð padding-left: 0;ÐÐl {Ð margin-top: 0;Ð margin-bottom: 20px;ÐÐt,Ðd {Ð line-height: 1.428571429;ÐÐt {Ð font-weight: bold;ÐÐd {Ð margin-left: 0;Ð@media (min-width: 768px) {Ð .dl-horizontal dt {Ð float: left;Ð width: 160px;Ð overflow: hidden;Ð clear: left;Ð text-align: right;Ð text-overflow: ellipsis;Ð white-space: nowrap;Ð }Ð .dl-horizontal dd {Ð margin-left: 180px;Ð }Ð .dl-horizontal dd:before,Ð .dl-horizontal dd:after {Ð display: table;Ð content: " ";Ð }Ð .dl-horizontal dd:after {Ð clear: both;Ð }Ð .dl-horizontal dd:before,Ð .dl-horizontal dd:after {Ð display: table;Ð content: " ";Ð }Ð .dl-horizontal dd:after {Ð clear: both;Ð }ÐÐbbr[title],Ðbbr[data-original-title] {Ð cursor: help;Ð border-bottom: 1px dotted #999999;ÐÐinitialism {Ð font-size: 90%;Ð text-transform: uppercase;Ð }ÐblockquoteÐ {Ð padding: 10px 20px;Ð margin: 0 0 20px;Ð border-left: 5px solid #eeeeee;ÐÐblockquote p {Ð font-size: 17.5px;Ð font-weight: 300;Ð line-height: 1.25;ÐÐblockquote p:last-child {Ð margin-bottom: 0;ÐÐblockquote small,Ð blockquote .small {Ð display: block;Ð line-height: 1.428571429;Ð color: #999999;ÐÐblockquote small:before,Ðblockquote .small:before {Ð content: '\2014 \00A0';ÐÐblockquote.pull-right {Ð padding-right: 15px;Ð padding-left: 0;Ð border-right: 5px solid #eeeeee;Ð border-left: 0;ÐÐblockquote.pull-right p,Ð blockquote.pull-right small,Ðblockquote.pull-right .small {Ð text-align: right;Ð }Ðblockquote.pull-right small:before,Ðblockquote.pull-right .small:before {Ð content: '';ÐÐblockquote.pull-right small:after,Ðblockquote.pull-right .small:after {Ð content: '\00A0 \2014';ÐÐblockquote:before,Ð blockquote:after {Ð content: "";ÐÐaddress {Ð margin-bottom: 20px;Ð font-style: normal;Ð line-height: 1.428571429;ÐÐode,Ðbd,Ðpre,Ðamp {Ð font-family: Menlo, Monaco, Consolas, "Courier New", monospace;ÐÐode {Ð padding: 2px 4px;Ð font-size: 90%;Ð color: #c7254e;Ð white-space: nowrap;Ð background-color: #f9f2f4;Ð border-radius: 4px;ÐÐre {Ð display: block;Ð padding: 9.5px;Ð margin: 0 0 10px;Ð

font-size: 13px;Ð line-height: 1.428571429;Ð color: #333333;Ð word-break: break-all;Ð word-wrap: break-word;Ð background-color: #f5f5f5;Ð border: 1px solid #cccccc;Ð border-radius: 4px;ÞÞpre code {Ð padding: 0;Ð font-size: inherit;Ð color: inherit;Ð white-space: pre-wrap;Ð background-color: transparent;Ð border-radius: 0;ÞÞpre-scrollable {Ð max-height: 340px;Ð overflow-y: scroll;ÞÞcontainer {Ð padding-right: 15px;Ð padding-left: 15px;Ð margin-right: auto;Ð margin-left: auto;ÞÞcontainer:before,Ðcontainer:after {Ð display: table;Ð content: " ";ÞÞcontainer:after {Ð clear: both;ÞÞ .container:before,Ðcontainer:after {Ð display: table;Ð content: " ";ÞÞ .container:after {Ð clear: both;ÞÞmedia (min-width: 768px) {Ð .container {Ð width: 750px;Ð }ÞÞmedia (min-width: 992px) {Ð .container {Ð width: 970px;Ð }Ð }ÞÞmedia (min-width: 1200px) {Ð .container {Ð width: 1170px;Ð }ÞÞrow {Ð margin-right: -15px;Ð margin-left: -15px;ÞÞrow:before,Ðrow:after {Ð display: table;Ð content: " ";ÞÞrow:after {Ð clear: both;ÞÞrow:before,Ðrow:after {Ð display: table;Ð content: " ";ÞÞrow:after {Ð clear: both;ÞÞcol-xs-1,Ðcol-sm-1,Ð .col-md-1,Ðcol-lg-1,Ðcol-xs-2,Ðcol-sm-2,Ðcol-md-2,Ðcol-lg-2,Ðcol-xs-3,Ðcol-sm-3,Ðcol-md-3,Ðcol-lg-3,Ðcol-xs-4,Ðcol-sm-4,Ðcol-md-4,Ðcol-lg-4,Ðcol-xs-5,Ð .col-sm-5,Ðcol-md-5,Ðcol-lg-5,Ðcol-xs-6,Ðcol-sm-6,Ðcol-md-6,Ðcol-lg-6,Ðcol-xs-7,Ðcol-sm-7,Ðcol-md-7,Ðcol-lg-7,Ðcol-xs-8,Ðcol-sm-8,Ðcol-md-8,Ðcol-lg-8,Ð .col-xs-9,Ðcol-sm-9,Ðcol-md-9,Ðcol-lg-9,Ðcol-xs-10,Ðcol-sm-10,Ðcol-md-10,Ðcol-lg-10,Ðcol-xs-11,Ðcol-sm-11,Ðcol-md-11,Ðcol-lg-11,Ðcol-xs-12,Ðcol-sm-12,Ðcol-md-12,Ðcol-lg-12 {Ð position: relative;Ð min-height: 1px;Ð padding-right: 15px;Ð padding-left: 15px;ÞÞcol-xs-1,Ðcol-xs-2,Ðcol-xs-3,Ðcol-xs-4,Ðcol-xs-5,Ð .col-xs-6,Ðcol-xs-7,Ðcol-xs-8,Ðcol-xs-9,Ðcol-xs-10,Ðcol-xs-11,Ðcol-xs-12 {Ð float: left;ÞÞcol-xs-12 {Ð width: 100%;ÞÞcol-xs-11 {Ð width: 91.66666666666666%;ÞÞcol-xs-10 {Ð width: 83.33333333333334%;ÞÞcol-xs-9 {Ð width: 75%;ÞÞcol-xs-8 {Ð width: 66.66666666666666%;ÞÞcol-xs-7 {Ð width: 58.333333333333336%;ÞÞcol-xs-6 {Ð width: 50%;ÞÞcol-xs-5 {Ð width: 41.66666666666667%;ÞÞcol-xs-4 {Ð width: 33.33333333333333%;ÞÞcol-xs-3 {Ð width: 25%;ÞÞcol-xs-2 {Ð width: 16.666666666666664%;ÞÞcol-xs-1 {Ð width: 8.333333333333332%;ÞÞcol-xs-pull-12 {Ð right: 100%;ÞÞcol-xs-pull-11 {Ð right: 91.66666666666666%;ÞÞcol-xs-pull-10 {Ð right: 83.33333333333334%;ÞÞcol-xs-pull-9 {Ð right: 75%;ÞÞcol-xs-pull-8 {Ð right: 66.66666666666666%;ÞÞcol-xs-pull-7 {Ð right: 58.333333333333336%;ÞÞcol-xs-pull-6 {Ð right: 50%;ÞÞcol-xs-pull-5 {Ð right: 41.66666666666667%;ÞÞcol-xs-pull-4 {Ð right: 33.33333333333333%;ÞÞcol-xs-pull-3 {Ð right: 25%;ÞÞcol-xs-pull-2 {Ð right: 16.666666666666664%;ÞÞcol-xs-pull-1 {Ð right: 8.333333333333332%;ÞÞcol-xs-pull-0 {Ð right: 0;ÞÞcol-xs-push-12 {Ð left: 100%;ÞÞcol-xs-push-11 {Ð left: 91.66666666666666%;ÞÞcol-xs-push-10 {Ð left: 83.33333333333334%;ÞÞcol-xs-push-9 {Ð left: 75%;ÞÞcol-xs-push-8 {Ð left: 66.66666666666666%;ÞÞcol-xs-push-7 {Ð left: 58.333333333333336%;ÞÞcol-xs-push-6 {Ð left: 50%;ÞÞcol-xs-push-5 {Ð left: 41.66666666666667%;ÞÞcol-xs-push-4 {Ð left: 33.33333333333333%;ÞÞcol-xs-push-3 {Ð left: 25%;ÞÞcol-xs-push-2 {Ð left: 16.666666666666664%;ÞÞcol-xs-push-1 {Ð left: 8.333333333333332%;ÞÞcol-xs-push-0 {Ð left: 0;ÞÞcol-xs-offset-12 {Ð margin-left: 100%;ÞÞcol-xs-offset-11 {Ð margin-left: 91.66666666666666%;ÞÞcol-xs-offset-10 {Ð margin-left: 83.33333333333334%;ÞÞcol-xs-offset-9 {Ð margin-left: 75%;ÞÞcol-xs-offset-8 {Ð margin-left: 66.66666666666666%;ÞÞcol-xs-offset-7 {Ð margin-left: 58.333333333333336%;ÞÞcol-xs-offset-6 {Ð margin-left: 50%;ÞÞcol-xs-offset-5 {Ð margin-left: 41.66666666666667%;ÞÞcol-xs-offset-4 {Ð margin-left: 33.33333333333333%;ÞÞcol-xs-offset-3 {Ð margin-left: 25%;ÞÞcol-xs-offset-2 {Ð margin-left: 16.666666666666664%;ÞÞcol-xs-offset-1 {Ð margin-left: 8.333333333333332%;ÞÞcol-xs-offset-0 {Ð margin-left: 0;ÞÞmedia (min-width: 768px) {Ð .col-sm-1,Ð .col-sm-2,Ð .col-sm-3,Ð .col-sm-4,Ð .col-sm-5,Ð .col-sm-6,Ð .col-sm-7,Ð .col-sm-8,Ð .col-sm-9,Ð .col-sm-10,Ð .col-sm-11,Ð .col-sm-12 {Ð float: left;Ð }Ð .col-sm-12 {Ð width: 100%;Ð }Ð .col-sm-11 {Ð width: 91.66666666666666%;Ð }Ð .col-sm-10 {Ð width: 83.33333333333334%;Ð }Ð .col-sm-9 {Ð width: 75%;Ð }Ð .col-sm-8 {Ð width: 66.66666666666666%;Ð }Ð .col-sm-7 {Ð width: 58.333333333333336%;Ð }Ð .col-sm-6 {Ð width: 50%;Ð }Ð .col-sm-5 {Ð

width: 41.66666666666667%;Ð }Ð .col-sm-4 {Ð width: 33.33333333333333%;Ð }Ð .col-sm-3 {Ð width: 25%;Ð }Ð .col-sm-2 {Ð width: 16.666666666666664%;Ð }Ð .col-sm-1 {Ð width: 8.333333333333332%;Ð }Ð .col-sm-pull-12 {Ð right: 100%;Ð }Ð .col-sm-pull-11 {Ð right: 91.66666666666666%;Ð }Ð .col-sm-pull-10 {Ð right: 83.33333333333334%;Ð }Ð .col-sm-pull-9 {Ð right: 75%;Ð }Ð .col-sm-pull-8 {Ð right: 66.66666666666666%;Ð }Ð .col-sm-pull-7 {Ð right: 58.333333333333336%;Ð }Ð .col-sm-pull-6 {Ð right: 50%;Ð }Ð .col-sm-pull-5 {Ð right: 41.66666666666667%;Ð }Ð .col-sm-pull-4 {Ð right: 33.33333333333333%;Ð }Ð .col-sm-pull-3 {Ð right: 25%;Ð }Ð .col-sm-pull-2 {Ð right: 16.666666666666664%;Ð }Ð .col-sm-pull-1 {Ð right: 8.333333333333332%;Ð }Ð .col-sm-pull-0 {Ð right: 0;Ð }Ð .col-sm-push-12 {Ð left: 100%;Ð }Ð .col-sm-push-11 {Ð left: 91.66666666666666%;Ð }Ð .col-sm-push-10 {Ð left: 83.33333333333334%;Ð }Ð .col-sm-push-9 {Ð left: 75%;Ð }Ð .col-sm-push-8 {Ð left: 66.66666666666666%;Ð }Ð .col-sm-push-7 {Ð left: 58.333333333333336%;Ð }Ð .col-sm-push-6 {Ð left: 50%;Ð }Ð .col-sm-push-5 {Ð left: 41.66666666666667%;Ð }Ð .col-sm-push-4 {Ð left: 33.33333333333333%;Ð }Ð .col-sm-push-3 {Ð left: 25%;Ð }Ð .col-sm-push-2 {Ð left: 16.666666666666664%;Ð }Ð .col-sm-push-1 {Ð left: 8.333333333333332%;Ð }Ð .col-sm-push-0 {Ð left: 0;Ð }Ð .col-sm-offset-12 {Ð margin-left: 100%;Ð }Ð .col-sm-offset-11 {Ð margin-left: 91.66666666666666%;Ð }Ð .col-sm-offset-10 {Ð margin-left: 83.33333333333334%;Ð }Ð .col-sm-offset-9 {Ð margin-left: 75%;Ð }Ð .col-sm-offset-8 {Ð margin-left: 66.66666666666666%;Ð }Ð .col-sm-offset-7 {Ð margin-left: 58.333333333333336%;Ð }Ð .col-sm-offset-6 {Ð margin-left: 50%;Ð }Ð .col-sm-offset-5 {Ð margin-left: 41.66666666666667%;Ð }Ð .col-sm-offset-4 {Ð margin-left: 33.33333333333333%;Ð }Ð .col-sm-offset-3 {Ð margin-left: 25%;Ð }Ð .col-sm-offset-2 {Ð margin-left: 16.666666666666664%;Ð }Ð .col-sm-offset-1 {Ð margin-left: 8.333333333333332%;Ð }Ð .col-sm-offset-0 {Ð margin-left: 0;Ð }Ð@media (min-width: 992px) {Ð .col-md-1,Ð .col-md-2,Ð .col-md-3,Ð .col-md-4,Ð .col-md-5,Ð .col-md-6,Ð .col-md-7,Ð .col-md-8,Ð .col-md-9,Ð .col-md-10,Ð .col-md-11,Ð .col-md-12 {Ð float: left;Ð }Ð .col-md-12 {Ð width: 100%;Ð }Ð .col-md-11 {Ð width: 91.66666666666666%;Ð }Ð .col-md-10 {Ð width: 83.33333333333334%;Ð }Ð .col-md-9 {Ð width: 75%;Ð }Ð .col-md-8 {Ð width: 66.66666666666666%;Ð }Ð .col-md-7 {Ð width: 58.333333333333336%;Ð }Ð .col-md-6 {Ð width: 50%;Ð }Ð .col-md-5 {Ð width: 41.66666666666667%;Ð }Ð .col-md-4 {Ð width: 33.33333333333333%;Ð }Ð .col-md-3 {Ð width: 25%;Ð }Ð .col-md-2 {Ð width: 16.666666666666664%;Ð }Ð .col-md-1 {Ð width: 8.333333333333332%;Ð }Ð .col-md-pull-12 {Ð right: 100%;Ð }Ð .col-md-pull-11 {Ð right: 91.66666666666666%;Ð }Ð .col-md-pull-10 {Ð right: 83.33333333333334%;Ð }Ð .col-md-pull-9 {Ð right: 75%;Ð }Ð .col-md-pull-8 {Ð right: 66.66666666666666%;Ð }Ð .col-md-pull-7 {Ð right: 58.333333333333336%;Ð }Ð .col-md-pull-6 {Ð right: 50%;Ð }Ð .col-md-pull-5 {Ð right: 41.66666666666667%;Ð }Ð .col-md-pull-4 {Ð right: 33.33333333333333%;Ð }Ð .col-md-pull-3 {Ð right: 25%;Ð }Ð .col-md-pull-2 {Ð right: 16.666666666666664%;Ð }Ð .col-md-pull-1 {Ð right: 8.333333333333332%;Ð }Ð .col-md-pull-0 {Ð right: 0;Ð }Ð .col-md-push-12 {Ð left: 100%;Ð }Ð .col-md-push-11 {Ð left: 91.66666666666666%;Ð }Ð .col-md-push-10 {Ð left: 83.33333333333334%;Ð }Ð .col-md-push-9 {Ð left: 75%;Ð }Ð .col-md-push-8 {Ð left: 66.66666666666666%;Ð }Ð .col-md-push-7 {Ð left: 58.333333333333336%;Ð }Ð .col-md-push-6 {Ð left: 50%;Ð }Ð .col-md-push-5 {Ð left: 41.66666666666667%;Ð }Ð .col-md-push-4 {Ð left: 33.33333333333333%;Ð }Ð .col-md-push-3 {Ð left: 25%;Ð }Ð .col-md-push-2 {Ð left: 16.666666666666664%;Ð }Ð .col-md-push-1 {Ð left: 8.333333333333332%;Ð }Ð .col-md-push-0 {Ð left: 0;Ð }Ð .col-md-offset-12 {Ð margin-left: 100%;Ð }Ð .col-md-offset-11 {Ð margin-left: 91.66666666666666%;Ð }Ð .col-md-offset-10 {Ð margin-left: 83.33333333333334%;Ð }Ð .col-md-offset-9 {Ð margin-left: 75%;Ð }Ð .col-md-offset-8 {Ð

margin-left: 66.66666666666666%;Ð }Ð .col-md-offset-7 {Ð
margin-left: 58.333333333333336%;Ð }Ð .col-md-offset-6 {Ð margin-left: 50%;Ð
}Ð .col-md-offset-5 {Ð margin-left: 41.66666666666667%;Ð }Ð .col-md-
offset-4 {Ð margin-left: 33.33333333333333%;Ð }Ð .col-md-offset-3 {Ð
margin-left: 25%;Ð }Ð .col-md-offset-2 {Ð margin-left: 16.666666666666664%;Ð
}Ð .col-md-offset-1 {Ð margin-left: 8.333333333333332%;Ð }Ð .col-md-
offset-0 {Ð margin-left: 0;Ð }ÐÐmedia (min-width: 1200px) {Ð .col-lg-1,Ð
.col-lg-2,Ð .col-lg-3,Ð .col-lg-4,Ð .col-lg-5,Ð .col-lg-6,Ð .col-lg-7,Ð
.col-lg-8,Ð .col-lg-9,Ð .col-lg-10,Ð .col-lg-11,Ð .col-lg-12 {Ð float:
left;Ð }Ð .col-lg-12 {Ð width: 100%;Ð }Ð .col-lg-11 {Ð width:
91.66666666666666%;Ð }Ð .col-lg-10 {Ð width: 83.33333333333334%;Ð }Ð .col-
lg-9 {Ð width: 75%;Ð }Ð .col-lg-8 {Ð width: 66.66666666666666%;Ð }Ð .col-
lg-7 {Ð width: 58.333333333333336%;Ð }Ð .col-lg-6 {Ð width: 50%;Ð }Ð .col-
lg-5 {Ð width: 41.66666666666667%;Ð }Ð .col-lg-4 {Ð width:
33.33333333333333%;Ð }Ð .col-lg-3 {Ð width: 25%;Ð }Ð .col-lg-2 {Ð width:
16.666666666666664%;Ð }Ð .col-lg-1 {Ð width: 8.333333333333332%;Ð }Ð .col-
lg-pull-12 {Ð right: 100%;Ð }Ð .col-lg-pull-11 {Ð right:
91.66666666666666%;Ð }Ð .col-lg-pull-10 {Ð right: 83.33333333333334%;Ð }Ð
.col-lg-pull-9 {Ð right: 75%;Ð }Ð .col-lg-pull-8 {Ð right:
66.66666666666666%;Ð }Ð .col-lg-pull-7 {Ð right: 58.333333333333336%;Ð }Ð
.col-lg-pull-6 {Ð right: 50%;Ð }Ð .col-lg-pull-5 {Ð right:
41.66666666666667%;Ð }Ð .col-lg-pull-4 {Ð right: 33.33333333333333%;Ð }Ð
.col-lg-pull-3 {Ð right: 25%;Ð }Ð .col-lg-pull-2 {Ð right:
16.666666666666664%;Ð }Ð .col-lg-pull-1 {Ð right: 8.333333333333332%;Ð }Ð
.col-lg-pull-0 {Ð right: 0;Ð }Ð .col-lg-push-12 {Ð left: 100%;Ð }Ð .col-
lg-push-11 {Ð left: 91.66666666666666%;Ð }Ð .col-lg-push-10 {Ð left:
83.33333333333334%;Ð }Ð .col-lg-push-9 {Ð left: 75%;Ð }Ð .col-lg-push-8 {Ð
left: 66.66666666666666%;Ð }Ð .col-lg-push-7 {Ð left:
58.333333333333336%;Ð }Ð .col-lg-push-6 {Ð left: 50%;Ð }Ð .col-lg-push-5 {Ð
left: 41.66666666666667%;Ð }Ð .col-lg-push-4 {Ð left:
33.33333333333333%;Ð }Ð .col-lg-push-3 {Ð left: 25%;Ð }Ð .col-lg-push-2 {Ð
left: 16.666666666666664%;Ð }Ð .col-lg-push-1 {Ð left:
8.333333333333332%;Ð }Ð .col-lg-push-0 {Ð left: 0;Ð }Ð .col-lg-offset-12 {Ð
margin-left: 100%;Ð }Ð .col-lg-offset-11 {Ð margin-left:
91.66666666666666%;Ð }Ð .col-lg-offset-10 {Ð margin-left:
83.33333333333334%;Ð }Ð .col-lg-offset-9 {Ð margin-left: 75%;Ð }Ð .col-lg-
offset-8 {Ð margin-left: 66.66666666666666%;Ð }Ð .col-lg-offset-7 {Ð
margin-left: 58.333333333333336%;Ð }Ð .col-lg-offset-6 {Ð margin-left: 50%;Ð
}Ð .col-lg-offset-5 {Ð margin-left: 41.66666666666667%;Ð }Ð .col-lg-
offset-4 {Ð margin-left: 33.33333333333333%;Ð }Ð .col-lg-offset-3 {Ð
margin-left: 25%;Ð }Ð .col-lg-offset-2 {Ð margin-left: 16.666666666666664%;Ð
}Ð .col-lg-offset-1 {Ð margin-left: 8.333333333333332%;Ð }Ð .col-lg-
offset-0 {Ð margin-left: 0;Ð }ÐÐtable {Ð max-width: 100%;Ð background-color:
transparent;ÐÐth {Ð text-align: left;ÐÐtable {Ð width: 100%;Ð margin-bottom:
20px;ÐÐtable > thead > tr > th,Ðtable > tbody > tr > th,Ðtable > tfoot > tr >
th,Ðtable > thead > tr > td,Ðtable > tbody > tr > td,Ðtable > tfoot > tr > td
{Ð padding: 8px;Ð line-height: 1.428571429;Ð vertical-align: top;Ð border-
top: 1px solid #dddddd;ÐÐtable > thead > tr > th {Ð vertical-align: bottom;Ð
border-bottom: 2px solid #dddddd;ÐÐtable > caption + thead > tr:first-child >
th,Ðtable > colgroup + thead > tr:first-child > th,Ðtable > thead:first-child
> tr:first-child > th,Ðtable > caption + thead > tr:first-child > td,Ðtable >
colgroup + thead > tr:first-child > td,Ðtable > thead:first-child > tr:first-
child > td {Ð border-top: 0;ÐÐtable > tbody + tbody {Ð border-top: 2px solid
#dddddd;ÐÐtable .table {Ð background-color: #ffffff;ÐÐtable-condensed > thead
> tr > th,Ðtable-condensed > tbody > tr > th,Ðtable-condensed > tfoot > tr >
th,Ðtable-condensed > thead > tr > td,Ðtable-condensed > tbody > tr > td,Ð
.table-condensed > tfoot > tr > td {Ð padding: 5px;ÐÐtable-bordered {Ð
border: 1px solid #dddddd;ÐÐtable-bordered > thead > tr > th,Ðtable-bordered
> tbody > tr > th,Ðtable-bordered > tfoot > tr > th,Ðtable-bordered > thead >
tr > td,Ð

.table-bordered > tbody > tr > td,Ðtable-bordered > tfoot > tr > td {Ð
border: 1px solid #dddddd;ÞÐtable-bordered > thead > tr > th,Ðtable-
bordered > thead > tr > td {Ð border-bottom-width: 2px;ÞÐtable-striped >
tbody > tr:nth-child(odd) > td,Ðtable-striped > tbody > tr:nth-child(odd) >
th {Ð background-color: #f9f9f9;ÞÐtable-hover > tbody > tr:hover > td,Ðtable-
hover > tbody > tr:hover > th {Ð background-color: #f5f5f5;ÞÐable
col[class*="col-"] {Ð position: static;Ð display: table-column;Ð float: none;ÞÐ
table td[class*="col-"],Ðable th[class*="col-"] {Ð display: table-cell;Ð
float: none;ÞÐtable > thead > tr > .active,Ðtable > tbody > tr > .active,Ð
.table > tfoot > tr > .active,Ðtable > thead > .active > td,Ðtable > tbody
> .active > td,Ðtable > tfoot > .active > td,Ðtable > thead > .active > th,Ð
.table > tbody > .active > th,Ðtable > tfoot > .active > th {Ð background-
color: #f5f5f5;ÞÐtable-hover > tbody > tr > .active:hover,Ðtable-hover >
tbody > .active:hover > td,Ðtable-hover > tbody > .active:hover > th {Ð
background-color: #e8e8e8;ÞÐtable > thead > tr > .success,Ðtable > tbody > tr
> .success,Ðtable > tfoot > tr > .success,Ðtable > thead > .success > td,Ð
.table > tbody > .success > td,Ðtable > tfoot > .success > td,Ðtable > thead
> .success > th,Ðtable > tbody > .success > th,Ðtable > tfoot > .success > th
{Ð background-color: #dff0d8;ÞÐtable-hover > tbody > tr > .success:hover,Ð
.table-hover > tbody > .success:hover > td,Ðtable-hover > tbody
> .success:hover > th {Ð background-color: #d0e9c6;ÞÐtable > thead > tr
> .danger,Ðtable > tbody > tr > .danger,Ðtable > tfoot > tr > .danger,Ðtable
> thead > .danger > td,Ðtable > tbody > .danger > td,Ðtable > tfoot > .danger
> td,Ðtable > thead > .danger > th,Ðtable > tbody > .danger > th,Ðtable >
tfoot > .danger > th {Ð background-color: #f2dede;ÞÐtable-hover > tbody > tr
> .danger:hover,Ðtable-hover > tbody > .danger:hover > td,Ðtable-hover >
tbody > .danger:hover > th {Ð background-color: #ebcccc;ÞÐtable > thead > tr
> .warning,Ðtable > tbody > tr > .warning,Ðtable > tfoot > tr > .warning,Ð
.table > thead > .warning > td,Ðtable > tbody > .warning > td,Ðtable > tfoot
> .warning > td,Ðtable > thead > .warning > th,Ðtable > tbody > .warning > th,Ð
.table > tfoot > .warning > th {Ð background-color: #fcf8e3;ÞÐtable-hover >
tbody > tr > .warning:hover,Ðtable-hover > tbody > .warning:hover > td,Ðtable-
hover > tbody > .warning:hover > th {Ð background-color: #faf2cc;ÞÐmedia (max-
width: 767px) {Ð .table-responsive {Ð width: 100%;Ð margin-bottom: 15px;Ð
overflow-x: scroll;Ð overflow-y: hidden;Ð border: 1px solid #dddddd;Ð
-ms-overflow-style: -ms-autohiding-scrollbar;Ð -webkit-overflow-
scrolling: touch;Ð }Ð .table-responsive > .table {Ð margin-bottom: 0;Ð }Ð
.table-responsive > .table > thead > tr > th,Ð .table-responsive > .table >
tbody > tr > th,Ð .table-responsive > .table > tfoot > tr > th,Ð .table-
responsive > .table > thead > tr > td,Ð .table-responsive > .table > tbody >
tr > td,Ð .table-responsive > .table > tfoot > tr > td {Ð white-space:
nowrap;Ð }Ð .table-responsive > .table-bordered {Ð border: 0;Ð }Ð .table-
responsive > .table-bordered > thead > tr > th:first-child,Ð .table-
responsive > .table-bordered > tbody > tr > th:first-child,Ð .table-
responsive > .table-bordered > tfoot > tr > th:first-child,Ð .table-
responsive > .table-bordered > thead > tr > td:first-child,Ð .table-
responsive > .table-bordered > tbody > tr > td:first-child,Ð .table-
responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left:
0;Ð }Ð .table-responsive > .table-bordered > thead > tr > th:last-child,Ð
.table-responsive > .table-bordered > tbody > tr > th:last-child,Ð .table-
responsive > .table-bordered > tfoot > tr > th:last-child,Ð .table-responsive
> .table-bordered > thead > tr > td:last-child,Ð .table-responsive > .table-
bordered > tbody > tr > td:last-child,Ð .table-responsive > .table-bordered >
tfoot > tr > td:last-child {Ð border-right: 0;Ð }Ð .table-responsive
> .table-bordered > tbody > tr:last-child > th,Ð .table-responsive > .table-
bordered > tfoot > tr:last-child > th,Ð .table-responsive > .table-bordered >
tbody > tr:last-child > td,Ð .table-responsive > .table-bordered > tfoot >
tr:last-child > td {Ð border-bottom: 0;Ð }ÞÐfieldset {Ð padding: 0;Ð margin:
0;Ð border: 0;ÞÐlegend {Ð display: block;Ð width: 100%;Ð padding: 0;Ð margin-
bottom: 20px;Ð

```
                font-size: 21px;Ð line-height: inherit;Ð color: #333333;Ð
border: 0;Ð border-bottom: 1px solid #e5e5e5;ÞÞlabel {Ð display: inline-block;Ð
  margin-bottom: 5px;Ð font-weight: bold;ÞÞinput[type="search"] {Ð -webkit-box-
sizing: border-box;Ð    -moz-box-sizing: border-box;Ð         box-sizing:
border-box;ÞÞinput[type="radio"],Þinput[type="checkbox"] {Ð margin: 4px 0 0;Ð
margin-top: 1px \9;Ð /* IE8-9 */Ð line-height: normal;ÞÞinput[type="file"] {Ð
display: block;ÞÞselect[multiple],Þselect[size] {Ð height: auto;ÞÞselect
optgroup {Ð font-family: inherit;Ð font-size: inherit;Ð font-style: inherit;ÞÞ
input[type="file"]:focus,Þinput[type="radio"]:focus,Ð
input[type="checkbox"]:focus {Ð outline: thin dotted;Ð outline: 5px auto -
webkit-focus-ring-color;Ð outline-offset: -2px;ÞÞinput[type="number"]::-webkit-
outer-spin-button,Þinput[type="number"]::-webkit-inner-spin-button {Ð height:
auto;ÞÞoutput {Ð display: block;Ð padding-top: 7px;Ð font-size: 14px;Ð line-
height: 1.428571429;Ð color: #555555;Ð vertical-align: middle;ÞÞform-control {Ð
  display: block;Ð width: 100%;Ð height: 34px;Ð padding: 6px 12px;Ð font-
size: 14px;Ð line-height: 1.428571429;Ð color: #555555;Ð vertical-align:
middle;Ð background-color: #ffffff;Ð background-image: none;Ð border: 1px
solid #cccccc;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 1px
rgba(0, 0, 0, 0.075);Ð         box-shadow: inset 0 1px 1px rgba(0, 0, 0,
0.075);Ð -webkit-transition: border-color ease-in-out 0.15s, box-shadow ease-
in-out 0.15s;Ð         transition: border-color ease-in-out 0.15s, box-shadow
ease-in-out 0.15s;ÞÞform-control:focus {Ð border-color: #66afe9;Ð outline: 0;Ð
  -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 8px rgba(102,
175, 233, 0.6);Ð         box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0
0 8px rgba(102, 175, 233, 0.6);ÞÞform-control:-moz-placeholder {Ð color:
#999999;ÞÞform-control::-moz-placeholder {Ð color: #999999;Ð opacity: 1;ÞÞ
.form-control:-ms-input-placeholder {Ð color: #999999;ÞÞform-control::-webkit-
input-placeholder {Ð color: #999999;ÞÞform-control[disabled],Þform-
control[readonly],Þfieldset[disabled] .form-control {Ð cursor: not-allowed;Ð
background-color: #eeeeee;ÞÞtextarea.form-control {Ð height: auto;ÞÞform-group
{Ð margin-bottom: 15px;ÞÞradio,Þcheckbox {Ð display: block;Ð min-height: 20px;Ð
  padding-left: 20px;Ð margin-top: 10px;Ð margin-bottom: 10px;Ð vertical-
align: middle;ÞÞradio label,Þcheckbox label {Ð display: inline;Ð margin-
bottom: 0;Ð font-weight: normal;Ð cursor: pointer;ÞÞradio input[type="radio"],Ð
.radio-inline input[type="radio"],Þcheckbox input[type="checkbox"],Þcheckbox-
inline input[type="checkbox"] {Ð float: left;Ð margin-left: -20px;ÞÞradio
+ .radio,Þcheckbox + .checkbox {Ð margin-top: -5px;ÞÞradio-inline,Þcheckbox-
inline {Ð display: inline-block;Ð padding-left: 20px;Ð margin-bottom: 0;Ð
font-weight: normal;Ð vertical-align: middle;Ð cursor: pointer;ÞÞradio-inline
+ .radio-inline,Þcheckbox-inline + .checkbox-inline {Ð margin-top: 0;Ð margin-
left: 10px;ÞÞinput[type="radio"][disabled],Þinput[type="checkbox"][disabled],Ð
.radio[disabled],Þradio-inline[disabled],Þcheckbox[disabled],Þcheckbox-
inline[disabled],Þfieldset[disabled] input[type="radio"],Þfieldset[disabled]
input[type="checkbox"],Þfieldset[disabled] .radio,Þfieldset[disabled] .radio-
inline,Þfieldset[disabled] .checkbox,Þfieldset[disabled] .checkbox-inline {Ð
cursor: not-allowed;ÞÞinput-sm {Ð height: 30px;Ð padding: 5px 10px;Ð font-
size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÞÞselect.input-sm {Ð
height: 30px;Ð line-height: 30px;ÞÞtextarea.input-sm {Ð height: auto;ÞÞinput-
lg {Ð height: 46px;Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð
  border-radius: 6px;ÞÞselect.input-lg {Ð height: 46px;Ð line-height: 46px;ÞÞ
textarea.input-lg {Ð height: auto;ÞÞhas-warning .help-block,Þhas-
warning .control-label,Þhas-warning .radio,Þhas-warning .checkbox,Þhas-
warning .radio-inline,Þhas-warning .checkbox-inline {Ð color: #8a6d3b;ÞÞhas-
warning .form-control {Ð border-color: #8a6d3b;Ð -webkit-box-shadow: inset 0
1px 1px rgba(0, 0, 0, 0.075);Ð         box-shadow: inset 0 1px 1px rgba(0, 0,
0, 0.075);ÞÞhas-warning .form-control:focus {Ð border-color: #66512c;Ð -
webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #c0a16b;Ð
          box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0 6px #c0a16b;ÞÞ
.has-warning .input-group-addon {Ð color: #8a6d3b;Ð background-color: #fcf8e3;Ð
  border-color: #8a6d3b;Ð
```

}ÐÐhas-error .help-block,Ðhas-error .control-label,Ð
.has-error .radio,Ðhas-error .checkbox,Ðhas-error .radio-inline,Ðhas-
error .checkbox-inline {Ð color: #a94442;ÐÐhas-error .form-control {Ð border-
color: #a94442;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);Ð
box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);ÐÐhas-error .form-
control:focus {Ð border-color: #843534;Ð -webkit-box-shadow: inset 0 1px 1px
rgba(0, 0, 0, 0.075), 0 0 6px #ce8483;Ð box-shadow: inset 0 1px 1px
rgba(0, 0, 0, 0.075), 0 0 6px #ce8483;ÐÐhas-error .input-group-addon {Ð
color: #a94442;Ð background-color: #f2dede;Ð border-color: #a94442;ÐÐhas-
success .help-block,Ðhas-success .control-label,Ðhas-success .radio,Ðhas-
success .checkbox,Ðhas-success .radio-inline,Ðhas-success .checkbox-inline {Ð
color: #3c763d;ÐÐhas-success .form-control {Ð border-color: #3c763d;Ð -webkit-
box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075);Ð box-shadow: inset
0 1px 1px rgba(0, 0, 0, 0.075);ÐÐhas-success .form-control:focus {Ð border-
color: #2b542c;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0
0 6px #67b168;Ð box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.075), 0 0
6px #67b168;ÐÐhas-success .input-group-addon {Ð color: #3c763d;Ð background-
color: #dff0d8;Ð border-color: #3c763d;ÐÐform-control-static {Ð margin-
bottom: 0;ÐÐhelp-block {Ð display: block;Ð margin-top: 5px;Ð margin-bottom:
10px;Ð color: #737373;ÐÐ@media (min-width: 768px) {Ð .form-inline .form-group {Ð
display: inline-block;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð
.form-inline .form-control {Ð display: inline-block;Ð }Ð .form-inline
select.form-control {Ð width: auto;Ð }Ð .form-inline .radio,Ð .form-
inline .checkbox {Ð display: inline-block;Ð padding-left: 0;Ð margin-
top: 0;Ð margin-bottom: 0;Ð }Ð .form-inline .radio input[type="radio"],Ð
.form-inline .checkbox input[type="checkbox"] {Ð float: none;Ð margin-
left: 0;Ð }ÐÐform-horizontal .control-label,Ðform-horizontal .radio,Ðform-
horizontal .checkbox,Ðform-horizontal .radio-inline,Ðform-
horizontal .checkbox-inline {Ð padding-top: 7px;Ð margin-top: 0;Ð margin-
bottom: 0;ÐÐform-horizontal .radio,Ðform-horizontal .checkbox {Ð min-height:
27px;ÐÐform-horizontal .form-group {Ð margin-right: -15px;Ð margin-left:
-15px;ÐÐform-horizontal .form-group:before,Ðform-horizontal .form-group:after
{Ð display: table;Ð content: " ";ÐÐform-horizontal .form-group:after {Ð
clear: both;ÐÐform-horizontal .form-group:before,Ðform-horizontal .form-
group:after {Ð display: table;Ð content: " ";ÐÐform-horizontal .form-
group:after {Ð clear: both;ÐÐform-horizontal .form-control-static {Ð padding-
top: 7px;ÐÐ@media (min-width: 768px) {Ð .form-horizontal .control-label {Ð
text-align: right;Ð }ÐÐbtn {Ð display: inline-block;Ð padding: 6px 12px;Ð
margin-bottom: 0;Ð font-size: 14px;Ð font-weight: normal;Ð line-height:
1.428571429;Ð text-align: center;Ð white-space: nowrap;Ð vertical-align:
middle;Ð cursor: pointer;Ð background-image: none;Ð border: 1px solid
transparent;Ð border-radius: 4px;Ð -webkit-user-select: none;Ð -moz-user-
select: none;Ð -ms-user-select: none;Ð -o-user-select: none;Ð
user-select: none;ÐÐbtn:focus {Ð outline: thin dotted;Ð outline:
5px auto -webkit-focus-ring-color;Ð outline-offset: -2px;ÐÐbtn:hover,Ð
.btn:focus {Ð color: #333333;Ð text-decoration: none;ÐÐbtn:active,Ðbtn.active
{Ð background-image: none;Ð outline: 0;Ð -webkit-box-shadow: inset 0 3px 5px
rgba(0, 0, 0, 0.125);Ð box-shadow: inset 0 3px 5px rgba(0, 0, 0,
0.125);ÐÐbtn.disabled,Ðbtn[disabled],Ðfieldset[disabled] .btn {Ð pointer-
events: none;Ð cursor: not-allowed;Ð opacity: 0.65;Ð filter:
alpha(opacity=65);Ð -webkit-box-shadow: none;Ð box-shadow: none;ÐÐbtn-
default {Ð color: #333333;Ð background-color: #ffffff;Ð border-color: #cccccc;Ð
}ÐÐbtn-default:hover,Ðbtn-default:focus,Ðbtn-default:active,Ðbtn-
default.active,Ðopen .dropdown-toggle.btn-default {Ð color: #333333;Ð
background-color: #ebebeb;Ð border-color: #adadad;ÐÐbtn-default:active,Ðbtn-
default.active,Ðopen .dropdown-toggle.btn-default {Ð background-image: none;ÐÐ
.btn-default.disabled,Ðbtn-default[disabled],Ðfieldset[disabled] .btn-default,Ð
.btn-default.disabled:hover,Ðbtn-default[disabled]:hover,Ð
fieldset[disabled] .btn-default:hover,Ðbtn-default.disabled:focus,Ðbtn-
default[disabled]:focus,Ð

fieldset[disabled] .btn-default:focus,Ðbtn-default.disabled:active,Ðbtn-default[disabled]:active,Ðfieldset[disabled] .btn-default:active,Ðbtn-default.disabled.active,Ðbtn-default[disabled].active,Ð fieldset[disabled] .btn-default.active {Ð background-color: #ffffff;Ð border-color: #cccccc;ÞÐbtn-default .badge {Ð color: #ffffff;Ð background-color: #fff;ÞÐbtn-primary {Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #357ebd;ÞÐbtn-primary:hover,Ðbtn-primary:focus,Ðbtn-primary:active,Ð .btn-primary.active,Ðopen .dropdown-toggle.btn-primary {Ð color: #ffffff;Ð background-color: #3276b1;Ð border-color: #285e8e;ÞÐbtn-primary:active,Ðbtn-primary.active,Ðopen .dropdown-toggle.btn-primary {Ð background-image: none;ÞÐ .btn-primary.disabled,Ðbtn-primary[disabled],Ðfieldset[disabled] .btn-primary,Ð .btn-primary.disabled:hover,Ðbtn-primary[disabled]:hover,Ð fieldset[disabled] .btn-primary:hover,Ðbtn-primary.disabled:focus,Ðbtn-primary[disabled]:focus,Ðfieldset[disabled] .btn-primary:focus,Ðbtn-primary.disabled:active,Ðbtn-primary[disabled]:active,Ðfieldset[disabled] .btn-primary:active,Ðbtn-primary.disabled.active,Ðbtn-primary[disabled].active,Ð fieldset[disabled] .btn-primary.active {Ð background-color: #428bca;Ð border-color: #357ebd;ÞÐbtn-primary .badge {Ð color: #428bca;Ð background-color: #fff;ÞÐbtn-warning {Ð color: #ffffff;Ð background-color: #f0ad4e;Ð border-color: #eea236;ÞÐbtn-warning:hover,Ðbtn-warning:focus,Ðbtn-warning:active,Ð .btn-warning.active,Ðopen .dropdown-toggle.btn-warning {Ð color: #ffffff;Ð background-color: #ed9c28;Ð border-color: #d58512;ÞÐbtn-warning:active,Ðbtn-warning.active,Ðopen .dropdown-toggle.btn-warning {Ð background-image: none;ÞÐ .btn-warning.disabled,Ðbtn-warning[disabled],Ðfieldset[disabled] .btn-warning,Ð .btn-warning.disabled:hover,Ðbtn-warning[disabled]:hover,Ð fieldset[disabled] .btn-warning:hover,Ðbtn-warning.disabled:focus,Ðbtn-warning[disabled]:focus,Ðfieldset[disabled] .btn-warning:focus,Ðbtn-warning.disabled:active,Ðbtn-warning[disabled]:active,Ðfieldset[disabled] .btn-warning:active,Ðbtn-warning.disabled.active,Ðbtn-warning[disabled].active,Ð fieldset[disabled] .btn-warning.active {Ð background-color: #f0ad4e;Ð border-color: #eea236;ÞÐbtn-warning .badge {Ð color: #f0ad4e;Ð background-color: #fff;ÞÐbtn-danger {Ð color: #ffffff;Ð background-color: #d9534f;Ð border-color: #d43f3a;ÞÐbtn-danger:hover,Ðbtn-danger:focus,Ðbtn-danger:active,Ðbtn-danger.active,Ðopen .dropdown-toggle.btn-danger {Ð color: #ffffff;Ð background-color: #d2322d;Ð border-color: #ac2925;ÞÐbtn-danger:active,Ðbtn-danger.active,Ðopen .dropdown-toggle.btn-danger {Ð background-image: none;ÞÐ .btn-danger.disabled,Ðbtn-danger[disabled],Ðfieldset[disabled] .btn-danger,Ð .btn-danger.disabled:hover,Ðbtn-danger[disabled]:hover,Ð fieldset[disabled] .btn-danger:hover,Ðbtn-danger.disabled:focus,Ðbtn-danger[disabled]:focus,Ðfieldset[disabled] .btn-danger:focus,Ðbtn-danger.disabled:active,Ðbtn-danger[disabled]:active,Ðfieldset[disabled] .btn-danger:active,Ðbtn-danger.disabled.active,Ðbtn-danger[disabled].active,Ð fieldset[disabled] .btn-danger.active {Ð background-color: #d9534f;Ð border-color: #d43f3a;ÞÐbtn-danger .badge {Ð color: #d9534f;Ð background-color: #fff;Ð }Ðbtn-success {Ð color: #ffffff;Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÞÐbtn-success:hover,Ðbtn-success:focus,Ðbtn-success:active,Ðbtn-success.active,Ðopen .dropdown-toggle.btn-success {Ð color: #ffffff;Ð background-color: #47a447;Ð border-color: #398439;ÞÐbtn-success:active,Ðbtn-success.active,Ðopen .dropdown-toggle.btn-success {Ð background-image: none;ÞÐ .btn-success.disabled,Ðbtn-success[disabled],Ðfieldset[disabled] .btn-success,Ð .btn-success.disabled:hover,Ðbtn-success[disabled]:hover,Ð fieldset[disabled] .btn-success:hover,Ðbtn-success.disabled:focus,Ðbtn-success[disabled]:focus,Ðfieldset[disabled] .btn-success:focus,Ðbtn-success.disabled:active,Ðbtn-success[disabled]:active,Ðfieldset[disabled] .btn-success:active,Ðbtn-success.disabled.active,Ðbtn-success[disabled].active,Ð fieldset[disabled] .btn-success.active {Ð background-color: #5cb85c;Ð border-color: #4cae4c;ÞÐbtn-success .badge {Ð color: #5cb85c;Ð background-color: #fff;ÞÐbtn-info {Ð color: #ffffff;Ð background-color: #5bc0de;Ð border-color: #46b8da;ÞÐbtn-info:hover,Ðbtn-info:focus,Ðbtn-info:active,Ðbtn-info.active,Ð .open .dropdown-toggle.btn-info {Ð

color: #ffffff;Ð background-color: #39b3d7;Ð
  border-color: #269abc;ÞÐbtn-info:active,Ðbtn-info.active,Ðopen .dropdown-
toggle.btn-info {Ð background-image: none;ÞÐbtn-info.disabled,Ðbtn-
info[disabled],Ðfieldset[disabled] .btn-info,Ðbtn-info.disabled:hover,Ðbtn-
info[disabled]:hover,Ðfieldset[disabled] .btn-info:hover,Ðbtn-
info.disabled:focus,Ðbtn-info[disabled]:focus,Ðfieldset[disabled] .btn-
info:focus,Ðbtn-info.disabled:active,Ðbtn-info[disabled]:active,Ð
fieldset[disabled] .btn-info:active,Ðbtn-info.disabled.active,Ðbtn-
info[disabled].active,Ðfieldset[disabled] .btn-info.active {Ð background-
color: #5bc0de;Ð border-color: #46b8da;ÞÐbtn-info .badge {Ð color: #5bc0de;Ð
background-color: #fff;ÞÐbtn-link {Ð font-weight: normal;Ð color: #428bca;Ð
cursor: pointer;Ð border-radius: 0;ÞÐbtn-link,Ðbtn-link:active,Ðbtn-
link[disabled],Ðfieldset[disabled] .btn-link {Ð background-color: transparent;Ð
  -webkit-box-shadow: none;Ð box-shadow: none;ÞÐbtn-link,Ðbtn-
link:hover,Ðbtn-link:focus,Ðbtn-link:active {Ð border-color: transparent;ÞÐ
.btn-link:hover,Ðbtn-link:focus {Ð color: #2a6496;Ð text-decoration:
underline;Ð background-color: transparent;ÞÐbtn-link[disabled]:hover,Ð
fieldset[disabled] .btn-link:hover,Ðbtn-link[disabled]:focus,Ð
fieldset[disabled] .btn-link:focus {Ð color: #999999;Ð text-decoration: none;ÞÐ
.btn-lg {Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð border-
radius: 6px;ÞÐbtn-sm {Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height:
1.5;Ð border-radius: 3px;ÞÐbtn-xs {Ð padding: 1px 5px;Ð font-size: 12px;Ð
line-height: 1.5;Ð border-radius: 3px;ÞÐbtn-block {Ð display: block;Ð width:
100%;Ð padding-right: 0;Ð padding-left: 0;ÞÐbtn-block + .btn-block {Ð margin-
top: 5px;ÞÐinput[type="submit"].btn-block,Ðinput[type="reset"].btn-block,Ð
input[type="button"].btn-block {Ð width: 100%;ÞÐfade {Ð opacity: 0;Ð -webkit-
transition: opacity 0.15s linear;Ð transition: opacity 0.15s linear;ÞÐ
.fade.in {Ð opacity: 1;ÞÐcollapse {Ð display: none;ÞÐcollapse.in {Ð display:
block;ÞÐcollapsing {Ð position: relative;Ð height: 0;Ð overflow: hidden;Ð -
webkit-transition: height 0.35s ease;Ð transition: height 0.35s ease;ÞÐ
@font-face {Ð font-family: 'Glyphicons Halflings';Ð src: url('../fonts/
glyphicons-halflings-regular.html');Ð src: url('../fonts/glyphicons-halflings-
regulard41d.html?#iefix') format('embedded-opentype'), url('../fonts/
glyphicons-halflings-regular-2.html') format('woff'), url('../fonts/
glyphicons-halflings-regular-3.html') format('truetype'), url('../fonts/
glyphicons-halflings-regular-4.html#glyphicons-halflingsregular')
format('svg');ÞÐglyphicon {Ð position: relative;Ð top: 1px;Ð display: inline-
block;Ð font-family: 'Glyphicons Halflings';Ð -webkit-font-smoothing:
antialiased;Ð font-style: normal;Ð font-weight: normal;Ð line-height: 1;Ð -
moz-osx-font-smoothing: grayscale;ÞÐglyphicon:empty {Ð width: 1em;ÞÐglyphicon-
asterisk:before {Ð content: "\2a";ÞÐglyphicon-plus:before {Ð content: "\2b";ÞÐ
.glyphicon-euro:before {Ð content: "\20ac";ÞÐglyphicon-minus:before {Ð
content: "\2212";ÞÐglyphicon-cloud:before {Ð content: "\2601";ÞÐglyphicon-
envelope:before {Ð content: "\2709";ÞÐglyphicon-pencil:before {Ð content:
"\270f";ÞÐglyphicon-glass:before {Ð content: "\e001";ÞÐglyphicon-music:before
{Ð content: "\e002";ÞÐglyphicon-search:before {Ð content: "\e003";ÞÐglyphicon-
heart:before {Ð content: "\e005";ÞÐglyphicon-star:before {Ð content: "\e006";ÞÐ
.glyphicon-star-empty:before {Ð content: "\e007";ÞÐglyphicon-user:before {Ð
content: "\e008";ÞÐglyphicon-film:before {Ð content: "\e009";ÞÐglyphicon-th-
large:before {Ð content: "\e010";ÞÐglyphicon-th:before {Ð content: "\e011";ÞÐ
.glyphicon-th-list:before {Ð content: "\e012";ÞÐglyphicon-ok:before {Ð
content: "\e013";ÞÐglyphicon-remove:before {Ð content: "\e014";ÞÐglyphicon-
zoom-in:before {Ð content: "\e015";ÞÐglyphicon-zoom-out:before {Ð content:
"\e016";ÞÐglyphicon-off:before {Ð content: "\e017";ÞÐglyphicon-signal:before {Ð
  content: "\e018";ÞÐglyphicon-cog:before {Ð content: "\e019";ÞÐglyphicon-
trash:before {Ð content: "\e020";ÞÐglyphicon-home:before {Ð content: "\e021";ÞÐ
.glyphicon-file:before {Ð content: "\e022";ÞÐglyphicon-time:before {Ð
content: "\e023";ÞÐglyphicon-road:before {Ð content: "\e024";ÞÐglyphicon-
download-alt:before {Ð content: "\e025";ÞÐglyphicon-download:before {Ð
content: "\e026";Ð

}ÐÐglyphicon-upload:before {Ð content: "\e027";ÐÐglyphicon-inbox:before {Ð content: "\e028";ÐÐglyphicon-play-circle:before {Ð content: "\e029";ÐÐglyphicon-repeat:before {Ð content: "\e030";ÐÐglyphicon-refresh:before {Ð content: "\e031";ÐÐglyphicon-list-alt:before {Ð content: "\e032";ÐÐglyphicon-lock:before {Ð content: "\e033";ÐÐglyphicon-flag:before {Ð content: "\e034";ÐÐglyphicon-headphones:before {Ð content: "\e035";ÐÐ.glyphicon-volume-off:before {Ð content: "\e036";ÐÐglyphicon-volume-down:before {Ð content: "\e037";ÐÐglyphicon-volume-up:before {Ð content: "\e038";ÐÐglyphicon-qrcode:before {Ð content: "\e039";ÐÐglyphicon-barcode:before {Ð content: "\e040";ÐÐglyphicon-tag:before {Ð content: "\e041";Ð}ÐÐglyphicon-tags:before {Ð content: "\e042";ÐÐglyphicon-book:before {Ð content: "\e043";ÐÐglyphicon-bookmark:before {Ð content: "\e044";ÐÐglyphicon-print:before {Ð content: "\e045";ÐÐglyphicon-camera:before {Ð content: "\e046";ÐÐglyphicon-font:before {Ð content: "\e047";ÐÐglyphicon-bold:before {Ð content: "\e048";ÐÐglyphicon-italic:before {Ð content: "\e049";ÐÐglyphicon-text-height:before {Ð content: "\e050";ÐÐglyphicon-text-width:before {Ð content: "\e051";ÐÐglyphicon-align-left:before {Ð content: "\e052";ÐÐ.glyphicon-align-center:before {Ð content: "\e053";ÐÐglyphicon-align-right:before {Ð content: "\e054";ÐÐglyphicon-align-justify:before {Ð content: "\e055";ÐÐglyphicon-list:before {Ð content: "\e056";ÐÐglyphicon-indent-left:before {Ð content: "\e057";ÐÐglyphicon-indent-right:before {Ð content: "\e058";ÐÐglyphicon-facetime-video:before {Ð content: "\e059";ÐÐglyphicon-picture:before {Ð content: "\e060";ÐÐglyphicon-map-marker:before {Ð content: "\e062";ÐÐglyphicon-adjust:before {Ð content: "\e063";ÐÐglyphicon-tint:before {Ð content: "\e064";ÐÐglyphicon-edit:before {Ð content: "\e065";ÐÐglyphicon-share:before {Ð content: "\e066";ÐÐglyphicon-check:before {Ð content: "\e067";Ð}ÐÐglyphicon-move:before {Ð content: "\e068";ÐÐglyphicon-step-backward:before {Ð content: "\e069";ÐÐglyphicon-fast-backward:before {Ð content: "\e070";ÐÐ.glyphicon-backward:before {Ð content: "\e071";ÐÐglyphicon-play:before {Ð content: "\e072";ÐÐglyphicon-pause:before {Ð content: "\e073";ÐÐglyphicon-stop:before {Ð content: "\e074";ÐÐglyphicon-forward:before {Ð content: "\e075";ÐÐglyphicon-fast-forward:before {Ð content: "\e076";ÐÐglyphicon-step-forward:before {Ð content: "\e077";ÐÐglyphicon-eject:before {Ð content: "\e078";ÐÐglyphicon-chevron-left:before {Ð content: "\e079";ÐÐglyphicon-chevron-right:before {Ð content: "\e080";ÐÐglyphicon-plus-sign:before {Ð content: "\e081";ÐÐglyphicon-minus-sign:before {Ð content: "\e082";ÐÐ.glyphicon-remove-sign:before {Ð content: "\e083";ÐÐglyphicon-ok-sign:before {Ð content: "\e084";ÐÐglyphicon-question-sign:before {Ð content: "\e085";ÐÐ.glyphicon-info-sign:before {Ð content: "\e086";ÐÐglyphicon-screenshot:before {Ð content: "\e087";ÐÐglyphicon-remove-circle:before {Ð content: "\e088";ÐÐ.glyphicon-ok-circle:before {Ð content: "\e089";ÐÐglyphicon-ban-circle:before {Ð content: "\e090";ÐÐglyphicon-arrow-left:before {Ð content: "\e091";ÐÐ.glyphicon-arrow-right:before {Ð content: "\e092";ÐÐglyphicon-arrow-up:before {Ð content: "\e093";ÐÐglyphicon-arrow-down:before {Ð content: "\e094";ÐÐ.glyphicon-share-alt:before {Ð content: "\e095";ÐÐglyphicon-resize-full:before {Ð content: "\e096";ÐÐglyphicon-resize-small:before {Ð content: "\e097";ÐÐglyphicon-exclamation-sign:before {Ð content: "\e101";ÐÐglyphicon-gift:before {Ð content: "\e102";ÐÐglyphicon-leaf:before {Ð content: "\e103";ÐÐ.glyphicon-fire:before {Ð content: "\e104";ÐÐglyphicon-eye-open:before {Ð content: "\e105";ÐÐglyphicon-eye-close:before {Ð content: "\e106";ÐÐglyphicon-warning-sign:before {Ð content: "\e107";ÐÐglyphicon-plane:before {Ð content: "\e108";ÐÐglyphicon-calendar:before {Ð content: "\e109";ÐÐglyphicon-random:before {Ð content: "\e110";ÐÐglyphicon-comment:before {Ð content: "\e111";ÐÐglyphicon-magnet:before {Ð content: "\e112";ÐÐglyphicon-chevron-up:before {Ð content: "\e113";ÐÐglyphicon-chevron-down:before {Ð content: "\e114";ÐÐglyphicon-retweet:before {Ð content: "\e115";ÐÐglyphicon-shopping-cart:before {Ð content: "\e116";ÐÐglyphicon-folder-close:before {Ð content: "\e117";ÐÐglyphicon-folder-open:before {Ð content: "\e118";ÐÐglyphicon-resize-vertical:before {Ð content: "\e119";ÐÐglyphicon-resize-horizontal:before {Ð content: "\e120";Ð

}Ðglyphicon-hdd:before {Ð content: "\e121";ÞÐglyphicon-bullhorn:before {Ð content: "\e122";ÞÐglyphicon-bell:before {Ð content: "\e123";ÞÐglyphicon-certificate:before {Ð content: "\e124";ÞÐglyphicon-thumbs-up:before {Ð content: "\e125";ÞÐglyphicon-thumbs-down:before {Ð content: "\e126";ÞÐglyphicon-hand-right:before {Ð content: "\e127";ÞÐglyphicon-hand-left:before {Ð content: "\e128";ÞÐglyphicon-hand-up:before {Ð content: "\e129";ÞÐglyphicon-hand-down:before {Ð content: "\e130";ÞÐglyphicon-circle-arrow-right:before {Ð content: "\e131";ÞÐglyphicon-circle-arrow-left:before {Ð content: "\e132";ÞÐglyphicon-circle-arrow-up:before {Ð content: "\e133";ÞÐ .glyphicon-circle-arrow-down:before {Ð content: "\e134";ÞÐglyphicon-globe:before {Ð content: "\e135";ÞÐglyphicon-wrench:before {Ð content: "\e136";ÞÐglyphicon-tasks:before {Ð content: "\e137";ÞÐglyphicon-filter:before {Ð content: "\e138";ÞÐglyphicon-briefcase:before {Ð content: "\e139";ÞÐglyphicon-fullscreen:before {Ð content: "\e140";ÞÐglyphicon-dashboard:before {Ð content: "\e141";ÞÐglyphicon-paperclip:before {Ð content: "\e142";ÞÐglyphicon-heart-empty:before {Ð content: "\e143";ÞÐglyphicon-link:before {Ð content: "\e144";ÞÐglyphicon-phone:before {Ð content: "\e145";ÞÐ .glyphicon-pushpin:before {Ð content: "\e146";ÞÐglyphicon-usd:before {Ð content: "\e148";ÞÐglyphicon-gbp:before {Ð content: "\e149";ÞÐglyphicon-sort:before {Ð content: "\e150";ÞÐglyphicon-sort-by-alphabet:before {Ð content: "\e151";ÞÐglyphicon-sort-by-alphabet-alt:before {Ð content: "\e152";ÞÐ .glyphicon-sort-by-order:before {Ð content: "\e153";ÞÐglyphicon-sort-by-order-alt:before {Ð content: "\e154";ÞÐglyphicon-sort-by-attributes:before {Ð content: "\e155";ÞÐglyphicon-sort-by-attributes-alt:before {Ð content: "\e156";ÞÐglyphicon-unchecked:before {Ð content: "\e157";ÞÐglyphicon-expand:before {Ð content: "\e158";ÞÐglyphicon-collapse-down:before {Ð content: "\e159";ÞÐglyphicon-collapse-up:before {Ð content: "\e160";ÞÐ .glyphicon-log-in:before {Ð content: "\e161";ÞÐglyphicon-flash:before {Ð content: "\e162";ÞÐglyphicon-log-out:before {Ð content: "\e163";ÞÐglyphicon-new-window:before {Ð content: "\e164";ÞÐglyphicon-record:before {Ð content: "\e165";ÞÐglyphicon-save:before {Ð content: "\e166";ÞÐglyphicon-open:before {Ð content: "\e167";ÞÐglyphicon-saved:before {Ð content: "\e168";ÞÐglyphicon-import:before {Ð content: "\e169";ÞÐglyphicon-export:before {Ð content: "\e170";ÞÐglyphicon-send:before {Ð content: "\e171";ÞÐglyphicon-floppy-disk:before {Ð content: "\e172";ÞÐglyphicon-floppy-saved:before {Ð content: "\e173";ÞÐglyphicon-floppy-remove:before {Ð content: "\e174";ÞÐglyphicon-floppy-save:before {Ð content: "\e175";ÞÐglyphicon-floppy-open:before {Ð content: "\e176";ÞÐglyphicon-credit-card:before {Ð content: "\e177";ÞÐ .glyphicon-transfer:before {Ð content: "\e178";ÞÐglyphicon-cutlery:before {Ð content: "\e179";ÞÐglyphicon-header:before {Ð content: "\e180";ÞÐglyphicon-compressed:before {Ð content: "\e181";ÞÐglyphicon-earphone:before {Ð content: "\e182";ÞÐglyphicon-phone-alt:before {Ð content: "\e183";ÞÐglyphicon-tower:before {Ð content: "\e184";ÞÐglyphicon-stats:before {Ð content: "\e185";Ð }Ðglyphicon-sd-video:before {Ð content: "\e186";ÞÐglyphicon-hd-video:before {Ð content: "\e187";ÞÐglyphicon-subtitles:before {Ð content: "\e188";ÞÐ .glyphicon-sound-stereo:before {Ð content: "\e189";ÞÐglyphicon-sound-dolby:before {Ð content: "\e190";ÞÐglyphicon-sound-5-1:before {Ð content: "\e191";ÞÐglyphicon-sound-6-1:before {Ð content: "\e192";ÞÐglyphicon-sound-7-1:before {Ð content: "\e193";ÞÐglyphicon-copyright-mark:before {Ð content: "\e194";ÞÐglyphicon-registration-mark:before {Ð content: "\e195";ÞÐ .glyphicon-cloud-download:before {Ð content: "\e197";ÞÐglyphicon-cloud-upload:before {Ð content: "\e198";ÞÐglyphicon-tree-conifer:before {Ð content: "\e199";ÞÐglyphicon-tree-deciduous:before {Ð content: "\e200";ÞÐcaret {Ð display: inline-block;Ð width: 0;Ð height: 0;Ð margin-left: 2px;Ð vertical-align: middle;Ð border-top: 4px solid;Ð border-right: 4px solid transparent;Ð border-left: 4px solid transparent;ÞÐdropdown {Ð position: relative;ÞÐ .dropdown-toggle:focus {Ð outline: 0;ÞÐdropdown-menu {Ð position: absolute;Ð top: 100%;Ð left: 0;Ð z-index: 1000;Ð display: none;Ð float: left;Ð min-width: 160px;Ð padding: 5px 0;Ð margin: 2px 0 0;Ð font-size: 14px;Ð list-style: none;Ð

background-color: #ffffff;Ð border: 1px solid #cccccc;Ð border: 1px solid rgba(0, 0, 0, 0.15);Ð border-radius: 4px;Ð -webkit-box-shadow: 0 6px 12px rgba(0, 0, 0, 0.175);Ð box-shadow: 0 6px 12px rgba(0, 0, 0, 0.175);Ð background-clip: padding-box;ÐÐdropdown-menu.pull-right {Ð right: 0;Ð left: auto;ÐÐdropdown-menu .divider {Ð height: 1px;Ð margin: 9px 0;Ð overflow: hidden;Ð background-color: #e5e5e5;ÐÐdropdown-menu > li > a {Ð display: block;Ð padding: 3px 20px;Ð clear: both;Ð font-weight: normal;Ð line-height: 1.428571429;Ð color: #333333;Ð white-space: nowrap;ÐÐdropdown-menu > li > a:hover,Ðdropdown-menu > li > a:focus {Ð color: #262626;Ð text-decoration: none;Ð background-color: #f5f5f5;ÐÐdropdown-menu > .active > a,Ð .dropdown-menu > .active > a:hover,Ðdropdown-menu > .active > a:focus {Ð color: #ffffff;Ð text-decoration: none;Ð background-color: #428bca;Ð outline: 0;ÐÐdropdown-menu > .disabled > a,Ðdropdown-menu > .disabled > a:hover,Ð .dropdown-menu > .disabled > a:focus {Ð color: #999999;ÐÐdropdown-menu > .disabled > a:hover,Ðdropdown-menu > .disabled > a:focus {Ð text-decoration: none;Ð cursor: not-allowed;Ð background-color: transparent;Ð background-image: none;Ð filter: progid:DXImageTransform.Microsoft.gradient(enabled=false);ÐÐopen > .dropdown-menu {Ð display: block;ÐÐopen > a {Ð outline: 0;ÐÐdropdown-header {Ð display: block;Ð padding: 3px 20px;Ð font-size: 12px;Ð line-height: 1.428571429;Ð color: #999999;ÐÐdropdown-backdrop {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 990;ÐÐpull-right > .dropdown-menu {Ð right: 0;Ð left: auto;ÐÐdropup .caret,Ðnavbar-fixed-bottom .dropdown .caret {Ð border-top: 0;Ð border-bottom: 4px solid;Ð content: "";ÐÐdropup .dropdown-menu,Ð .navbar-fixed-bottom .dropdown .dropdown-menu {Ð top: auto;Ð bottom: 100%;Ð margin-bottom: 1px;ÐÐ@media (min-width: 768px) {Ð .navbar-right .dropdown-menu {Ð right: 0;Ð left: auto;Ð }ÐÐbtn-group,Ðbtn-group-vertical {Ð position: relative;Ð display: inline-block;Ð vertical-align: middle;ÐÐbtn-group > .btn,Ð .btn-group-vertical > .btn {Ð position: relative;Ð float: left;ÐÐbtn-group > .btn:hover,Ðbtn-group-vertical > .btn:hover,Ðbtn-group > .btn:focus,Ðbtn-group-vertical > .btn:focus,Ðbtn-group > .btn:active,Ðbtn-group-vertical > .btn:active,Ðbtn-group > .btn.active,Ðbtn-group-vertical > .btn.active {Ð z-index: 2;ÐÐbtn-group > .btn:focus,Ðbtn-group-vertical > .btn:focus {Ð outline: none;ÐÐbtn-group .btn + .btn,Ðbtn-group .btn + .btn-group,Ðbtn-group .btn-group + .btn,Ðbtn-group .btn-group + .btn-group {Ð margin-left: -1px;ÐÐbtn-toolbar:before,Ðbtn-toolbar:after {Ð display: table;Ð content: " ";Ð }ÐÐbtn-toolbar:after {Ð clear: both;ÐÐbtn-toolbar:before,Ðbtn-toolbar:after {Ð display: table;Ð content: " ";ÐÐbtn-toolbar:after {Ð clear: both;ÐÐbtn-toolbar .btn-group {Ð float: left;ÐÐbtn-toolbar > .btn + .btn,Ðbtn-toolbar > .btn-group + .btn,Ðbtn-toolbar > .btn + .btn-group,Ðbtn-toolbar > .btn-group + .btn-group {Ð margin-left: 5px;ÐÐbtn-group > .btn:not(:first-child):not(:last-child):not(.dropdown-toggle) {Ð border-radius: 0;ÐÐbtn-group > .btn:first-child {Ð margin-left: 0;ÐÐbtn-group > .btn:first-child:not(:last-child):not(.dropdown-toggle) {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÐÐbtn-group > .btn:last-child:not(:first-child),Ðbtn-group > .dropdown-toggle:not(:first-child) {Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÐÐbtn-group > .btn-group {Ð float: left;ÐÐbtn-group > .btn-group:not(:first-child):not(:last-child) > .btn {Ð border-radius: 0;ÐÐbtn-group > .btn-group:first-child > .btn:last-child,Ðbtn-group > .btn-group:first-child > .dropdown-toggle {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÐÐbtn-group > .btn-group:last-child > .btn:first-child {Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÐÐbtn-group .dropdown-toggle:active,Ðbtn-group.open .dropdown-toggle {Ð outline: 0;ÐÐ .btn-group-xs > .btn {Ð padding: 1px 5px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐbtn-group-sm > .btn {Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐbtn-group-lg > .btn {Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð border-radius: 6px;Ð }ÐÐbtn-group > .btn + .dropdown-toggle {Ð padding-right: 8px;Ð padding-left: 8px;ÐÐbtn-group > .btn-lg + .dropdown-toggle {Ð padding-right: 12px;Ð padding-left: 12px;Ð

}ÐÐbtn-group.open .dropdown-toggle {Ð -webkit-box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);Ð box-shadow: inset 0 3px 5px rgba(0, 0, 0, 0.125);ÐÐbtn-group.open .dropdown-toggle.btn-link {Ð -webkit-box-shadow: none;Ð box-shadow: none;ÐÐbtn .caret {Ð margin-left: 0;ÐÐbtn-lg .caret {Ð border-width: 5px 5px 0;Ð border-bottom-width: 0;ÐÐdropup .btn-lg .caret {Ð border-width: 0 5px 5px;ÐÐbtn-group-vertical > .btn,Ðbtn-group-vertical > .btn-group,Ðbtn-group-vertical > .btn-group > .btn {Ð display: block;Ð float: none;Ð width: 100%;Ð max-width: 100%;ÐÐbtn-group-vertical > .btn-group:before,Ðbtn-group-vertical > .btn-group:after {Ð display: table;Ð content: " ";ÐÐbtn-group-vertical > .btn-group:after {Ð clear: both;ÐÐbtn-group-vertical > .btn-group:before,Ðbtn-group-vertical > .btn-group:after {Ð display: table;Ð content: " ";ÐÐbtn-group-vertical > .btn-group:after {Ð clear: both;ÐÐbtn-group-vertical > .btn-group > .btn {Ð float: none;ÐÐbtn-group-vertical > .btn + .btn,Ðbtn-group-vertical > .btn + .btn-group,Ðbtn-group-vertical > .btn-group + .btn,Ðbtn-group-vertical > .btn-group + .btn-group {Ð margin-top: -1px;Ð margin-left: 0;ÐÐbtn-group-vertical > .btn:not(:first-child):not(:last-child) {Ð border-radius: 0;ÐÐbtn-group-vertical > .btn:first-child:not(:last-child) {Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;ÐÐbtn-group-vertical > .btn:last-child:not(:first-child) {Ð border-top-right-radius: 0;Ð border-bottom-left-radius: 4px;Ð border-top-left-radius: 0;ÐÐbtn-group-vertical > .btn-group:not(:first-child):not(:last-child) > .btn {Ð border-radius: 0;ÐÐbtn-group-vertical > .btn-group:first-child > .btn:last-child,Ð .btn-group-vertical > .btn-group:first-child > .dropdown-toggle {Ð border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;ÐÐbtn-group-vertical > .btn-group:last-child > .btn:first-child {Ð border-top-right-radius: 0;Ð border-top-left-radius: 0;ÐÐbtn-group-justified {Ð display: table;Ð width: 100%;Ð border-collapse: separate;Ð table-layout: fixed;ÐÐbtn-group-justified > .btn,Ðbtn-group-justified > .btn-group {Ð display: table-cell;Ð float: none;Ð width: 1%;ÐÐbtn-group-justified > .btn-group .btn {Ð width: 100%;ÐÐdata-toggle="buttons"] > .btn > input[type="radio"],Ðdata-toggle="buttons"] > .btn > input[type="checkbox"] {Ð display: none;ÐÐinput-group {Ð position: relative;Ð display: table;Ð border-collapse: separate;ÐÐinput-group[class*="col-"] {Ð float: none;Ð padding-right: 0;Ð padding-left: 0;ÐÐinput-group .form-control {Ð width: 100%;Ð margin-bottom: 0;ÐÐinput-group-lg > .form-control,Ðinput-group-lg > .input-group-addon,Ðinput-group-lg > .input-group-btn > .btn {Ð height: 46px;Ð padding: 10px 16px;Ð font-size: 18px;Ð line-height: 1.33;Ð border-radius: 6px;ÐÐselect.input-group-lg > .form-control,Ðselect.input-group-lg > .input-group-addon,Ðselect.input-group-lg > .input-group-btn > .btn {Ð height: 46px;Ð line-height: 46px;ÐÐtextarea.input-group-lg > .form-control,Ð textarea.input-group-lg > .input-group-addon,Ðtextarea.input-group-lg > .input-group-btn > .btn {Ð height: auto;ÐÐinput-group-sm > .form-control,Ðinput-group-sm > .input-group-addon,Ðinput-group-sm > .input-group-btn > .btn {Ð height: 30px;Ð padding: 5px 10px;Ð font-size: 12px;Ð line-height: 1.5;Ð border-radius: 3px;ÐÐselect.input-group-sm > .form-control,Ðselect.input-group-sm > .input-group-addon,Ðselect.input-group-sm > .input-group-btn > .btn {Ð height: 30px;Ð line-height: 30px;ÐÐtextarea.input-group-sm > .form-control,Ð textarea.input-group-sm > .input-group-addon,Ðtextarea.input-group-sm > .input-group-btn > .btn {Ð height: auto;ÐÐinput-group-addon,Ðinput-group-btn,Ðinput-group .form-control {Ð display: table-cell;ÐÐinput-group-addon:not(:first-child):not(:last-child),Ðinput-group-btn:not(:first-child):not(:last-child),Ð .input-group .form-control:not(:first-child):not(:last-child) {Ð border-radius: 0;ÐÐinput-group-addon,Ðinput-group-btn {Ð width: 1%;Ð white-space: nowrap;Ð vertical-align: middle;ÐÐinput-group-addon {Ð padding: 6px 12px;Ð font-size: 14px;Ð font-weight: normal;Ð line-height: 1;Ð color: #555555;Ð text-align: center;Ð background-color: #eeeeee;Ð border: 1px solid #cccccc;Ð border-radius: 4px;ÐÐinput-group-addon.input-sm {Ð padding: 5px 10px;Ð font-size: 12px;Ð border-radius: 3px;ÐÐinput-group-addon.input-lg {Ð padding: 10px 16px;Ð font-size: 18px;Ð border-radius: 6px;ÐÐinput-group-addon input[type="radio"],Ð

.input-group-addon input[type="checkbox"] {Ð margin-top: 0;ÞÐinput-group .form-control:first-child,Ðinput-group-addon:first-child,Ð .input-group-btn:first-child > .btn,Ðinput-group-btn:first-child > .dropdown-toggle,Ðinput-group-btn:last-child > .btn:not(:last-child):not(.dropdown-toggle) {Ð border-top-right-radius: 0;Ð border-bottom-right-radius: 0;ÞÐinput-group-addon:first-child {Ð border-right: 0;ÞÐinput-group .form-control:last-child,Ðinput-group-addon:last-child,Ðinput-group-btn:last-child > .btn,Ðinput-group-btn:last-child > .dropdown-toggle,Ðinput-group-btn:first-child > .btn:not(:first-child) {Ð border-bottom-left-radius: 0;Ð border-top-left-radius: 0;ÞÐinput-group-addon:last-child {Ð border-left: 0;ÞÐinput-group-btn {Ð position: relative;Ð white-space: nowrap;ÞÐinput-group-btn:first-child > .btn {Ð margin-right: -1px;ÞÐinput-group-btn:last-child > .btn {Ð margin-left: -1px;ÞÐinput-group-btn > .btn {Ð position: relative;ÞÐinput-group-btn > .btn + .btn {Ð margin-left: -4px;ÞÐinput-group-btn > .btn:hover,Ðinput-group-btn > .btn:active {Ð z-index: 2;ÞÐnav {Ð padding-left: 0;Ð margin-bottom: 0;Ð list-style: none;ÞÐnav:before,Ðnav:after {Ð display: table;Ð content: " ";ÞÐnav:after {Ð clear: both;ÞÐnav:before,Ðnav:after {Ð display: table;Ð content: " ";ÞÐnav:after {Ð clear: both;ÞÐnav > li {Ð position: relative;Ð display: block;ÞÐnav > li > a {Ð position: relative;Ð display: block;Ð padding: 10px 15px;ÞÐnav > li > a:hover,Ðnav > li > a:focus {Ð text-decoration: none;Ð background-color: #eeeeee;ÞÐnav > li.disabled > a {Ð color: #999999;ÞÐnav > li.disabled > a:hover,Ðnav > li.disabled > a:focus {Ð color: #999999;Ð text-decoration: none;Ð cursor: not-allowed;Ð background-color: transparent;ÞÐnav .open > a,Ðnav .open > a:hover,Ðnav .open > a:focus {Ð background-color: #eeeeee;Ð border-color: #428bca;ÞÐnav .nav-divider {Ð height: 1px;Ð margin: 9px 0;Ð overflow: hidden;Ð background-color: #e5e5e5;ÞÐ .nav > li > a > img {Ð max-width: none;ÞÐnav-tabs {Ð border-bottom: 1px solid #dddddd;ÞÐnav-tabs > li {Ð float: left;Ð margin-bottom: -1px;ÞÐnav-tabs > li > a {Ð margin-right: 2px;Ð line-height: 1.428571429;Ð border: 1px solid transparent;Ð border-radius: 4px 4px 0 0;ÞÐnav-tabs > li > a:hover {Ð border-color: #eeeeee #eeeeee #dddddd;ÞÐnav-tabs > li.active > a,Ðnav-tabs > li.active > a:hover,Ðnav-tabs > li.active > a:focus {Ð color: #555555;Ð cursor: default;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-bottom-color: transparent;ÞÐnav-tabs.nav-justified {Ð width: 100%;Ð border-bottom: 0;ÞÐnav-tabs.nav-justified > li {Ð float: none;ÞÐnav-tabs.nav-justified > li > a {Ð margin-bottom: 5px;Ð text-align: center;ÞÐnav-tabs.nav-justified > .dropdown .dropdown-menu {Ð top: auto;Ð left: auto;Þ@media (min-width: 768px) {Ð .nav-tabs.nav-justified > li {Ð display: table-cell;Ð width: 1%;Ð }Ð .nav-tabs.nav-justified > li > a {Ð margin-bottom: 0;Ð }ÞÐ .nav-tabs.nav-justified > li > a {Ð margin-right: 0;Ð border-radius: 4px;ÞÐ .nav-tabs.nav-justified > .active > a,Ðnav-tabs.nav-justified > .active > a:hover,Ðnav-tabs.nav-justified > .active > a:focus {Ð border: 1px solid #dddddd;Þ@media (min-width: 768px) {Ð .nav-tabs.nav-justified > li > a {Ð border-bottom: 1px solid #dddddd;Ð border-radius: 4px 4px 0 0;Ð }Ð .nav-tabs.nav-justified > .active > a,Ð .nav-tabs.nav-justified > .active > a:hover,Ð .nav-tabs.nav-justified > .active > a:focus {Ð border-bottom-color: #ffffff;Ð }ÞÐnav-pills > li {Ð float: left;ÞÐnav-pills > li > a {Ð border-radius: 4px;ÞÐnav-pills > li + li {Ð margin-left: 2px;ÞÐnav-pills > li.active > a,Ðnav-pills > li.active > a:hover,Ðnav-pills > li.active > a:focus {Ð color: #ffffff;Ð background-color: #428bca;ÞÐnav-stacked > li {Ð float: none;ÞÐnav-stacked > li + li {Ð margin-top: 2px;Ð margin-left: 0;ÞÐnav-justified {Ð width: 100%;ÞÐnav-justified > li {Ð float: none;ÞÐnav-justified > li > a {Ð margin-bottom: 5px;Ð text-align: center;ÞÐnav-justified > .dropdown .dropdown-menu {Ð top: auto;Ð left: auto;Þ@media (min-width: 768px) {Ð .nav-justified > li {Ð display: table-cell;Ð width: 1%;Ð }Ð .nav-justified > li > a {Ð margin-bottom: 0;Ð }ÞÐnav-tabs-justified {Ð border-bottom: 0;ÞÐnav-tabs-justified > li > a {Ð margin-right: 0;Ð border-radius: 4px;ÞÐnav-tabs-justified > .active > a,Ðnav-tabs-justified > .active > a:hover,Ðnav-tabs-justified > .active > a:focus {Ð border: 1px solid #dddddd;Ð

}ÐÐmedia (min-width: 768px) {Ð .nav-tabs-justified > li > a {Ð
border-bottom: 1px solid #dddddd;Ð   border-radius: 4px 4px 0 0;Ð }Ð .nav-
tabs-justified > .active > a,Ð .nav-tabs-justified > .active > a:hover,Ð .nav-
tabs-justified > .active > a:focus {Ð   border-bottom-color: #ffffff;Ð }ÐÐtab-
content > .tab-pane {Ð display: none;ÐÐtab-content > .active {Ð display:
block;ÐÐnav-tabs .dropdown-menu {Ð margin-top: -1px;Ð border-top-right-
radius: 0;Ð border-top-left-radius: 0;ÐÐnavbar {Ð position: relative;Ð min-
height: 50px;Ð margin-bottom: 20px;Ð border: 1px solid transparent;ÐÐ
.navbar:before,Ðnavbar:after {Ð display: table;Ð content: " ";ÐÐnavbar:after {Ð
  clear: both;ÐÐnavbar:before,Ðnavbar:after {Ð display: table;Ð content: " ";ÐÐ
.navbar:after {Ð clear: both;ÐÐmedia (min-width: 768px) {Ð .navbar {Ð
border-radius: 4px;Ð }ÐÐnavbar-header:before,Ðnavbar-header:after {Ð display:
table;Ð content: " ";ÐÐnavbar-header:after {Ð clear: both;ÐÐnavbar-
header:before,Ðnavbar-header:after {Ð display: table;Ð content: " ";ÐÐnavbar-
header:after {Ð clear: both;ÐÐmedia (min-width: 768px) {Ð .navbar-header {Ð
float: left;Ð }ÐÐnavbar-collapse {Ð max-height: 340px;Ð padding-right: 15px;Ð
padding-left: 15px;Ð overflow-x: visible;Ð border-top: 1px solid transparent;Ð
  box-shadow: inset 0 1px 0 rgba(255, 255, 255, 0.1);Ð -webkit-overflow-
scrolling: touch;ÐÐnavbar-collapse:before,Ðnavbar-collapse:after {Ð display:
table;Ð content: " ";ÐÐnavbar-collapse:after {Ð clear: both;ÐÐnavbar-
collapse:before,Ðnavbar-collapse:after {Ð display: table;Ð content: " ";ÐÐ
.navbar-collapse:after {Ð clear: both;ÐÐnavbar-collapse.in {Ð overflow-y:
auto;ÐÐmedia (min-width: 768px) {Ð .navbar-collapse {Ð   width: auto;Ð
border-top: 0;Ð   box-shadow: none;Ð }Ð .navbar-collapse.collapse {Ð
display: block !important;Ð   height: auto !important;Ð   padding-bottom: 0;Ð
    overflow: visible !important;Ð }Ð .navbar-collapse.in {Ð   overflow-y:
visible;Ð }Ð .navbar-fixed-top .navbar-collapse,Ð .navbar-static-top .navbar-
collapse,Ð .navbar-fixed-bottom .navbar-collapse {Ð   padding-right: 0;Ð
padding-left: 0;Ð }ÐÐcontainer > .navbar-header,Ðcontainer > .navbar-collapse
{Ð margin-right: -15px;Ð margin-left: -15px;ÐÐmedia (min-width: 768px) {Ð
  .container > .navbar-header,Ð .container > .navbar-collapse {Ð   margin-
right: 0;Ð   margin-left: 0;Ð }ÐÐnavbar-static-top {Ð z-index: 1000;Ð border-
width: 0 0 1px;ÐÐmedia (min-width: 768px) {Ð .navbar-static-top {Ð   border-
radius: 0;Ð }ÐÐnavbar-fixed-top,Ðnavbar-fixed-bottom {Ð position: fixed;Ð
right: 0;Ð left: 0;Ð z-index: 1030;ÐÐmedia (min-width: 768px) {Ð .navbar-
fixed-top,Ð .navbar-fixed-bottom {Ð   border-radius: 0;Ð }ÐÐnavbar-fixed-top {Ð
  top: 0;Ð border-width: 0 0 1px;ÐÐnavbar-fixed-bottom {Ð bottom: 0;Ð margin-
bottom: 0;Ð border-width: 1px 0 0;ÐÐnavbar-brand {Ð float: left;Ð padding:
15px 15px;Ð font-size: 18px;Ð line-height: 20px;ÐÐnavbar-brand:hover,Ðnavbar-
brand:focus {Ð text-decoration: none;ÐÐmedia (min-width: 768px) {Ð .navbar
> .container .navbar-brand {Ð   margin-left: -15px;Ð }ÐÐnavbar-toggle {Ð
position: relative;Ð float: right;Ð padding: 9px 10px;Ð margin-top: 8px;Ð
margin-right: 15px;Ð margin-bottom: 8px;Ð background-color: transparent;Ð
background-image: none;Ð border: 1px solid transparent;Ð border-radius: 4px;ÐÐ
.navbar-toggle .icon-bar {Ð display: block;Ð width: 22px;Ð height: 2px;Ð
border-radius: 1px;ÐÐnavbar-toggle .icon-bar + .icon-bar {Ð margin-top: 4px;ÐÐ
@media (min-width: 768px) {Ð .navbar-toggle {Ð   display: none;Ð }ÐÐnavbar-
nav {Ð margin: 7.5px -15px;ÐÐnavbar-nav > li > a {Ð padding-top: 10px;Ð
padding-bottom: 10px;Ð line-height: 20px;ÐÐmedia (max-width: 767px) {Ð
  .navbar-nav .open .dropdown-menu {Ð   position: static;Ð   float: none;Ð
width: auto;Ð   margin-top: 0;Ð   background-color: transparent;Ð   border: 0;Ð
    box-shadow: none;Ð }Ð .navbar-nav .open .dropdown-menu > li > a,Ð .navbar-
nav .open .dropdown-menu .dropdown-header {Ð   padding: 5px 15px 5px 25px;Ð }Ð
  .navbar-nav .open .dropdown-menu > li > a {Ð   line-height: 20px;Ð }Ð
  .navbar-nav .open .dropdown-menu > li > a:hover,Ð .navbar-
nav .open .dropdown-menu > li > a:focus {Ð   background-image: none;Ð }ÐÐ
@media (min-width: 768px) {Ð .navbar-nav {Ð   float: left;Ð   margin: 0;Ð }Ð
  .navbar-nav > li {Ð   float: left;Ð }Ð .navbar-nav > li > a {Ð   padding-
top: 15px;Ð   padding-bottom: 15px;Ð }Ð .navbar-nav.navbar-right:last-child {Ð
    margin-right: -15px;Ð

}ÐÐ@media (min-width: 768px) {Ð .navbar-left {Ð
float: left !important;Ð }Ð .navbar-right {Ð float: right !important;Ð }ÐÐ
.navbar-form {Ð padding: 10px 15px;Ð margin-top: 8px;Ð margin-right: -15px;Ð
margin-bottom: 8px;Ð margin-left: -15px;Ð border-top: 1px solid transparent;Ð
border-bottom: 1px solid transparent;Ð -webkit-box-shadow: inset 0 1px 0
rgba(255, 255, 255, 0.1), 0 1px 0 rgba(255, 255, 255, 0.1);Ð box-
shadow: inset 0 1px 0 rgba(255, 255, 255, 0.1), 0 1px 0 rgba(255, 255, 255,
0.1);ÐÐ@media (min-width: 768px) {Ð .navbar-form .form-group {Ð display:
inline-block;Ð margin-bottom: 0;Ð vertical-align: middle;Ð }Ð .navbar-
form .form-control {Ð display: inline-block;Ð }Ð .navbar-form select.form-
control {Ð width: auto;Ð }Ð .navbar-form .radio,Ð .navbar-form .checkbox {Ð
  display: inline-block;Ð padding-left: 0;Ð margin-top: 0;Ð margin-
bottom: 0;Ð }Ð .navbar-form .radio input[type="radio"],Ð .navbar-
form .checkbox input[type="checkbox"] {Ð float: none;Ð margin-left: 0;Ð }ÐÐ
@media (max-width: 767px) {Ð .navbar-form .form-group {Ð margin-bottom: 5px;Ð
}ÐÐ@media (min-width: 768px) {Ð .navbar-form {Ð width: auto;Ð padding-
top: 0;Ð padding-bottom: 0;Ð margin-right: 0;Ð margin-left: 0;Ð
border: 0;Ð -webkit-box-shadow: none;Ð box-shadow: none;Ð }Ð
.navbar-form.navbar-right:last-child {Ð margin-right: -15px;Ð }ÐÐnavbar-
nav > li > .dropdown-menu {Ð margin-top: 0;Ð border-top-right-radius: 0;Ð
border-top-left-radius: 0;ÐÐnavbar-fixed-bottom .navbar-nav > li > .dropdown-
menu {Ð border-bottom-right-radius: 0;Ð border-bottom-left-radius: 0;ÐÐnavbar-
nav.pull-right > li > .dropdown-menu,Ðnavbar-nav > li > .dropdown-menu.pull-
right {Ð right: 0;Ð left: auto;ÐÐnavbar-btn {Ð margin-top: 8px;Ð margin-
bottom: 8px;ÐÐnavbar-btn.btn-sm {Ð margin-top: 10px;Ð margin-bottom: 10px;ÐÐ
.navbar-btn.btn-xs {Ð margin-top: 14px;Ð margin-bottom: 14px;ÐÐnavbar-text {Ð
margin-top: 15px;Ð margin-bottom: 15px;ÐÐ@media (min-width: 768px) {Ð .navbar-
text {Ð float: left;Ð margin-right: 15px;Ð margin-left: 15px;Ð }Ð
.navbar-text.navbar-right:last-child {Ð margin-right: 0;Ð }ÐÐnavbar-
default {Ð background-color: #f8f8f8;Ð border-color: #e7e7e7;ÐÐnavbar-
default .navbar-brand {Ð color: #777777;ÐÐnavbar-default .navbar-brand:hover,Ð
.navbar-default .navbar-brand:focus {Ð color: #5e5e5e;Ð background-color:
transparent;ÐÐnavbar-default .navbar-text {Ð color: #777777;ÐÐnavbar-
default .navbar-nav > li > a {Ð color: #777777;ÐÐnavbar-default .navbar-nav >
li > a:hover,Ðnavbar-default .navbar-nav > li > a:focus {Ð color: #333333;Ð
background-color: transparent;ÐÐnavbar-default .navbar-nav > .active > a,Ð
.navbar-default .navbar-nav > .active > a:hover,Ðnavbar-default .navbar-nav
> .active > a:focus {Ð color: #555555;Ð background-color: #e7e7e7;ÐÐnavbar-
default .navbar-nav > .disabled > a,Ðnavbar-default .navbar-nav > .disabled >
a:hover,Ðnavbar-default .navbar-nav > .disabled > a:focus {Ð color: #cccccc;Ð
background-color: transparent;ÐÐnavbar-default .navbar-toggle {Ð border-
color: #dddddd;ÐÐnavbar-default .navbar-toggle:hover,Ðnavbar-default .navbar-
toggle:focus {Ð background-color: #dddddd;ÐÐnavbar-default .navbar-
toggle .icon-bar {Ð background-color: #cccccc;ÐÐnavbar-default .navbar-
collapse,Ðnavbar-default .navbar-form {Ð border-color: #e7e7e7;ÐÐnavbar-
default .navbar-nav > .open > a,Ðnavbar-default .navbar-nav > .open > a:hover,Ð
.navbar-default .navbar-nav > .open > a:focus {Ð color: #555555;Ð background-
color: #e7e7e7;ÐÐ@media (max-width: 767px) {Ð .navbar-default .navbar-
nav .open .dropdown-menu > li > a {Ð color: #777777;Ð }Ð .navbar-
default .navbar-nav .open .dropdown-menu > li > a:hover,Ð .navbar-
default .navbar-nav .open .dropdown-menu > li > a:focus {Ð color: #333333;Ð
  background-color: transparent;Ð }Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a,Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a:hover,Ð .navbar-default .navbar-
nav .open .dropdown-menu > .active > a:focus {Ð color: #555555;Ð
background-color: #e7e7e7;Ð }Ð .navbar-default .navbar-nav .open .dropdown-
menu > .disabled > a,Ð .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a:hover,Ð .navbar-default .navbar-nav .open .dropdown-menu
> .disabled > a:focus {Ð color: #cccccc;Ð background-color: transparent;Ð
}Ð

}Ðnavbar-default .navbar-link {Ð color: #777777;ÞÐnavbar-default .navbar-link:hover {Ð color: #333333;ÞÐnavbar-inverse {Ð background-color: #222222;Ð border-color: #080808;ÞÐnavbar-inverse .navbar-brand {Ð color: #999999;ÞÐ .navbar-inverse .navbar-brand:hover,Ðnavbar-inverse .navbar-brand:focus {Ð color: #ffffff;Ð background-color: transparent;ÞÐnavbar-inverse .navbar-text {Ð color: #999999;ÞÐnavbar-inverse .navbar-nav > li > a {Ð color: #999999;ÞÐ .navbar-inverse .navbar-nav > li > a:hover,Ðnavbar-inverse .navbar-nav > li > a:focus {Ð color: #ffffff;Ð background-color: transparent;ÞÐnavbar-inverse .navbar-nav > .active > a,Ðnavbar-inverse .navbar-nav > .active > a:hover,Ðnavbar-inverse .navbar-nav > .active > a:focus {Ð color: #ffffff;Ð background-color: #080808;ÞÐnavbar-inverse .navbar-nav > .disabled > a,Ð .navbar-inverse .navbar-nav > .disabled > a:hover,Ðnavbar-inverse .navbar-nav > .disabled > a:focus {Ð color: #444444;Ð background-color: transparent;ÞÐ .navbar-inverse .navbar-toggle {Ð border-color: #333333;ÞÐnavbar-inverse .navbar-toggle:hover,Ðnavbar-inverse .navbar-toggle:focus {Ð background-color: #333333;ÞÐnavbar-inverse .navbar-toggle .icon-bar {Ð background-color: #ffffff;ÞÐnavbar-inverse .navbar-collapse,Ðnavbar-inverse .navbar-form {Ð border-color: #101010;ÞÐnavbar-inverse .navbar-nav > .open > a,Ðnavbar-inverse .navbar-nav > .open > a:hover,Ðnavbar-inverse .navbar-nav > .open > a:focus {Ð color: #ffffff;Ð background-color: #080808;ÞÐ@media (max-width: 767px) {Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .dropdown-header {Ð border-color: #080808;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu .divider {Ð background-color: #080808;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu > li > a {Ð color: #999999;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu > li > a:hover,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > li > a:focus {Ð color: #ffffff;Ð background-color: transparent;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a:hover,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .active > a:focus {Ð color: #ffffff;Ð background-color: #080808;Ð }Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a:hover,Ð .navbar-inverse .navbar-nav .open .dropdown-menu > .disabled > a:focus {Ð color: #444444;Ð background-color: transparent;Ð }ÞÐnavbar-inverse .navbar-link {Ð color: #999999;ÞÐnavbar-inverse .navbar-link:hover {Ð color: #ffffff;ÞÐbreadcrumb {Ð padding: 8px 15px;Ð margin-bottom: 20px;Ð list-style: none;Ð background-color: #f5f5f5;Ð border-radius: 4px;ÞÐbreadcrumb > li {Ð display: inline-block;ÞÐbreadcrumb > li + li:before {Ð padding: 0 5px;Ð color: #ccccc;Ð content: "/\00a0";ÞÐbreadcrumb > .active {Ð color: #999999;ÞÐpagination {Ð display: inline-block;Ð padding-left: 0;Ð margin: 20px 0;Ð border-radius: 4px;Ð }ÐÐpagination > li {Ð display: inline;ÞÐpagination > li > a,Ðpagination > li > span {Ð position: relative;Ð float: left;Ð padding: 6px 12px;Ð margin-left: -1px;Ð line-height: 1.428571429;Ð text-decoration: none;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;ÞÐpagination > li:first-child > a,Ð .pagination > li:first-child > span {Ð margin-left: 0;Ð border-bottom-left-radius: 4px;Ð border-top-left-radius: 4px;ÞÐpagination > li:last-child > a,Ð .pagination > li:last-child > span {Ð border-top-right-radius: 4px;Ð border-bottom-right-radius: 4px;ÞÐpagination > li > a:hover,Ðpagination > li > span:hover,Ðpagination > li > a:focus,Ðpagination > li > span:focus {Ð background-color: #eeeeee;ÞÐpagination > .active > a,Ðpagination > .active > span,Ðpagination > .active > a:hover,Ðpagination > .active > span:hover,Ð .pagination > .active > a:focus,Ðpagination > .active > span:focus {Ð z-index: 2;Ð color: #ffffff;Ð cursor: default;Ð background-color: #428bca;Ð border-color: #428bca;ÞÐpagination > .disabled > span,Ðpagination > .disabled > span:hover,Ðpagination > .disabled > span:focus,Ðpagination > .disabled > a,Ð .pagination > .disabled > a:hover,Ðpagination > .disabled > a:focus {Ð color: #999999;Ð cursor: not-allowed;Ð background-color: #ffffff;Ð border-color: #dddddd;ÞÐpagination-lg > li > a,Ðpagination-lg > li > span {Ð padding: 10px 16px;Ð

```
       font-size: 18px;ÐÐpagination-lg > li:first-child > a,Ðpagination-lg >
li:first-child > span {Ð border-bottom-left-radius: 6px;Ð border-top-left-
radius: 6px;ÐÐpagination-lg > li:last-child > a,Ðpagination-lg > li:last-
child > span {Ð border-top-right-radius: 6px;Ð border-bottom-right-radius:
6px;ÐÐpagination-sm > li > a,Ðpagination-sm > li > span {Ð padding: 5px 10px;Ð
  font-size: 12px;ÐÐpagination-sm > li:first-child > a,Ðpagination-sm >
li:first-child > span {Ð border-bottom-left-radius: 3px;Ð border-top-left-
radius: 3px;ÐÐpagination-sm > li:last-child > a,Ðpagination-sm > li:last-
child > span {Ð border-top-right-radius: 3px;Ð border-bottom-right-radius:
3px;ÐÐpager {Ð padding-left: 0;Ð margin: 20px 0;Ð text-align: center;Ð list-
style: none;ÐÐpager:before,Ðpager:after {Ð display: table;Ð content: " ";ÐÐ
.pager:after {Ð clear: both;ÐÐpager:before,Ðpager:after {Ð display: table;Ð
content: " ";ÐÐpager:after {Ð clear: both;ÐÐpager li {Ð display: inline;ÐÐ
.pager li > a,Ðpager li > span {Ð display: inline-block;Ð padding: 5px 14px;Ð
background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-radius: 15px;ÐÐ
.pager li > a:hover,Ðpager li > a:focus {Ð text-decoration: none;Ð background-
color: #eeeeee;ÐÐpager .next > a,Ðpager .next > span {Ð float: right;ÐÐ
.pager .previous > a,Ðpager .previous > span {Ð float: left;ÐÐpager .disabled
> a,Ðpager .disabled > a:hover,Ðpager .disabled > a:focus,Ðpager .disabled >
span {Ð color: #999999;Ð cursor: not-allowed;Ð background-color: #ffffff;ÐÐ
.label {Ð display: inline;Ð padding: .2em .6em .3em;Ð font-size: 75%;Ð font-
weight: bold;Ð line-height: 1;Ð color: #ffffff;Ð text-align: center;Ð white-
space: nowrap;Ð vertical-align: baseline;Ð border-radius: .25em;ÐÐ
.label[href]:hover,Ðlabel[href]:focus {Ð color: #ffffff;Ð text-decoration:
none;Ð cursor: pointer;ÐÐlabel:empty {Ð display: none;ÐÐbtn .label {Ð
position: relative;Ð top: -1px;ÐÐlabel-default {Ð background-color: #999999;ÐÐ
.label-default[href]:hover,Ðlabel-default[href]:focus {Ð background-color:
#808080;ÐÐlabel-primary {Ð background-color: #428bca;ÐÐlabel-
primary[href]:hover,Ðlabel-primary[href]:focus {Ð background-color: #3071a9;ÐÐ
.label-success {Ð background-color: #5cb85c;ÐÐlabel-success[href]:hover,Ð
.label-success[href]:focus {Ð background-color: #449d44;ÐÐlabel-info {Ð
background-color: #5bc0de;ÐÐlabel-info[href]:hover,Ðlabel-info[href]:focus {Ð
background-color: #31b0d5;ÐÐlabel-warning {Ð background-color: #f0ad4e;ÐÐ
.label-warning[href]:hover,Ðlabel-warning[href]:focus {Ð background-color:
#ec971f;ÐÐlabel-danger {Ð background-color: #d9534f;ÐÐlabel-
danger[href]:hover,Ðlabel-danger[href]:focus {Ð background-color: #c9302c;ÐÐ
.badge {Ð display: inline-block;Ð min-width: 10px;Ð padding: 3px 7px;Ð font-
size: 12px;Ð font-weight: bold;Ð line-height: 1;Ð color: #ffffff;Ð text-
align: center;Ð white-space: nowrap;Ð vertical-align: baseline;Ð background-
color: #999999;Ð border-radius: 10px;ÐÐbadge:empty {Ð display: none;ÐÐ
.btn .badge {Ð position: relative;Ð top: -1px;ÐÐa.badge:hover,Ða.badge:focus {Ð
color: #ffffff;Ð text-decoration: none;Ð cursor: pointer;ÐÐa.list-group-
item.active > .badge,Ðnav-pills > .active > a > .badge {Ð color: #428bca;Ð
background-color: #ffffff;ÐÐnav-pills > li > a > .badge {Ð margin-left: 3px;ÐÐ
.jumbotron {Ð padding: 30px;Ð margin-bottom: 30px;Ð font-size: 21px;Ð font-
weight: 200;Ð line-height: 2.1428571435;Ð color: inherit;Ð background-color:
#eeeeee;ÐÐjumbotron h1,Ðjumbotron .h1 {Ð line-height: 1;Ð color: inherit;ÐÐ
.jumbotron p {Ð line-height: 1.4;ÐÐcontainer .jumbotron {Ð border-radius: 6px;Ð
}Ðjumbotron .container {Ð max-width: 100%;ÐÐmedia screen and (min-width:
768px) {Ð .jumbotron {Ð   padding-top: 48px;Ð   padding-bottom: 48px;Ð }Ð
  .container .jumbotron {Ð   padding-right: 60px;Ð   padding-left: 60px;Ð }Ð
  .jumbotron h1,Ð .jumbotron .h1 {Ð   font-size: 63px;Ð }ÐÐthumbnail {Ð
display: block;Ð padding: 4px;Ð margin-bottom: 20px;Ð line-height:
1.428571429;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;Ð border-
radius: 4px;Ð -webkit-transition: all 0.2s ease-in-out;Ð         transition:
all 0.2s ease-in-out;ÐÐthumbnail > img,Ðthumbnail a > img {Ð display: block;Ð
height: auto;Ð max-width: 100%;Ð margin-right: auto;Ð margin-left: auto;ÐÐ
a.thumbnail:hover,Ða.thumbnail:focus,Ða.thumbnail.active {Ð border-color:
#428bca;ÐÐthumbnail .caption {Ð padding: 9px;Ð color: #333333;ÐÐalert {Ð
padding: 15px;Ð
```

margin-bottom: 20px;Ð border: 1px solid transparent;Ð border-radius: 4px;ÞÞalert h4 {Ð margin-top: 0;Ð color: inherit;ÞÞalert .alert-link {Ð font-weight: bold;ÞÞalert > p,Ðalert > ul {Ð margin-bottom: 0;ÞÞalert > p + p {Ð margin-top: 5px;ÞÞalert-dismissable {Ð padding-right: 35px;ÞÞalert-dismissable .close {Ð position: relative;Ð top: -2px;Ð right: -21px;Ð color: inherit;ÞÞalert-success {Ð color: #3c763d;Ð background-color: #dff0d8;Ð border-color: #d6e9c6;ÞÞalert-success hr {Ð border-top-color: #c9e2b3;ÞÞalert-success .alert-link {Ð color: #2b542c;ÞÞalert-info {Ð color: #31708f;Ð background-color: #d9edf7;Ð border-color: #bce8f1;ÞÞalert-info hr {Ð border-top-color: #a6e1ec;ÞÞalert-info .alert-link {Ð color: #245269;ÞÞalert-warning {Ð color: #8a6d3b;Ð background-color: #fcf8e3;Ð border-color: #faebcc;ÞÞalert-warning hr {Ð border-top-color: #f7e1b5;ÞÞalert-warning .alert-link {Ð color: #66512c;ÞÞalert-danger {Ð color: #a94442;Ð background-color: #f2dede;Ð border-color: #ebccd1;ÞÞalert-danger hr {Ð border-top-color: #e4b9c0;ÞÞalert-danger .alert-link {Ð color: #843534;ÞÞ@-webkit-keyframes progress-bar-stripes {Ð from {Ð background-position: 40px 0;Ð }Ð to {Ð background-position: 0 0;Ð }ÞÞ@keyframes progress-bar-stripes {Ð from {Ð background-position: 40px 0;Ð }Ð to {Ð background-position: 0 0;Ð }ÞÞprogress {Ð height: 20px;Ð margin-bottom: 20px;Ð overflow: hidden;Ð background-color: #f5f5f5;Ð border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 2px rgba(0, 0, 0, 0.1);Ð box-shadow: inset 0 1px 2px rgba(0, 0, 0, 0.1);ÞÞprogress-bar {Ð float: left;Ð width: 0;Ð height: 100%;Ð font-size: 12px;Ð line-height: 20px;Ð color: #ffffff;Ð text-align: center;Ð background-color: #428bca;Ð -webkit-box-shadow: inset 0 -1px 0 rgba(0, 0, 0, 0.15);Ð box-shadow: inset 0 -1px 0 rgba(0, 0, 0, 0.15);Ð -webkit-transition: width 0.6s ease;Ð transition: width 0.6s ease;ÞÞprogress-striped .progress-bar {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-size: 40px 40px;ÞÞ .progress.active .progress-bar {Ð -webkit-animation: progress-bar-stripes 2s linear infinite;Ð animation: progress-bar-stripes 2s linear infinite;ÞÞ .progress-bar-success {Ð background-color: #5cb85c;ÞÞprogress-striped .progress-bar-success {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÞÞprogress-bar-info {Ð background-color: #5bc0de;ÞÞprogress-striped .progress-bar-info {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÞÞprogress-bar-warning {Ð background-color: #f0ad4e;ÞÞprogress-striped .progress-bar-warning {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÞÞprogress-bar-danger {Ð background-color: #d9534f;ÞÞprogress-striped .progress-bar-danger {Ð background-image: -webkit-linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);Ð

background-image: linear-gradient(45deg, rgba(255, 255, 255, 0.15) 25%, transparent 25%, transparent 50%, rgba(255, 255, 255, 0.15) 50%, rgba(255, 255, 255, 0.15) 75%, transparent 75%, transparent);ÐÐmedia,Ðmedia-body {Ð overflow: hidden;Ð zoom: 1;ÐÐmedia,Ð .media .media {Ð margin-top: 15px;ÐÐmedia:first-child {Ð margin-top: 0;ÐÐ .media-object {Ð display: block;ÐÐmedia-heading {Ð margin: 0 0 5px;ÐÐmedia > .pull-left {Ð margin-right: 10px;ÐÐmedia > .pull-right {Ð margin-left: 10px;Ð }Ðmedia-list {Ð padding-left: 0;Ð list-style: none;ÐÐlist-group {Ð padding-left: 0;Ð margin-bottom: 20px;ÐÐlist-group-item {Ð position: relative;Ð display: block;Ð padding: 10px 15px;Ð margin-bottom: -1px;Ð background-color: #ffffff;Ð border: 1px solid #dddddd;ÐÐlist-group-item:first-child {Ð border-top-right-radius: 4px;Ð border-top-left-radius: 4px;ÐÐlist-group-item:last-child {Ð margin-bottom: 0;Ð border-bottom-right-radius: 4px;Ð border-bottom-left-radius: 4px;ÐÐlist-group-item > .badge {Ð float: right;ÐÐlist-group-item > .badge + .badge {Ð margin-right: 5px;ÐÐa.list-group-item {Ð color: #555555;ÐÐ a.list-group-item .list-group-item-heading {Ð color: #333333;ÐÐa.list-group-item:hover,Ða.list-group-item:focus {Ð text-decoration: none;Ð background-color: #f5f5f5;ÐÐa.list-group-item.active,Ða.list-group-item.active:hover,Ð a.list-group-item.active:focus {Ð z-index: 2;Ð color: #ffffff;Ð background-color: #428bca;Ð border-color: #428bca;ÐÐa.list-group-item.active .list-group-item-heading,Ða.list-group-item.active:hover .list-group-item-heading,Ða.list-group-item.active:focus .list-group-item-heading {Ð color: inherit;ÐÐa.list-group-item.active .list-group-item-text,Ða.list-group-item.active:hover .list-group-item-text,Ða.list-group-item.active:focus .list-group-item-text {Ð color: #e1edf7;ÐÐlist-group-item-heading {Ð margin-top: 0;Ð margin-bottom: 5px;ÐÐlist-group-item-text {Ð margin-bottom: 0;Ð line-height: 1.3;ÐÐpanel {Ð margin-bottom: 20px;Ð background-color: #ffffff;Ð border: 1px solid transparent;Ð border-radius: 4px;Ð -webkit-box-shadow: 0 1px 1px rgba(0, 0, 0, 0.05);Ð box-shadow: 0 1px 1px rgba(0, 0, 0, 0.05);ÐÐpanel-body {Ð padding: 15px;ÐÐpanel-body:before,Ðpanel-body:after {Ð display: table;Ð content: " ";ÐÐpanel-body:after {Ð clear: both;ÐÐpanel-body:before,Ðpanel-body:after {Ð display: table;Ð content: " ";ÐÐpanel-body:after {Ð clear: both;Ð }Ðpanel > .list-group {Ð margin-bottom: 0;ÐÐpanel > .list-group .list-group-item {Ð border-width: 1px 0;ÐÐpanel > .list-group .list-group-item:first-child {Ð border-top-right-radius: 0;Ð border-top-left-radius: 0;ÐÐpanel > .list-group .list-group-item:last-child {Ð border-bottom: 0;ÐÐpanel-heading + .list-group .list-group-item:first-child {Ð border-top-width: 0;ÐÐpanel > .table,Ðpanel > .table-responsive > .table {Ð margin-bottom: 0;ÐÐpanel > .panel-body + .table,Ðpanel > .panel-body + .table-responsive {Ð border-top: 1px solid #dddddd;ÐÐpanel > .table > tbody:first-child th,Ðpanel > .table > tbody:first-child td {Ð border-top: 0;ÐÐpanel > .table-bordered,Ð .panel > .table-responsive > .table-bordered {Ð border: 0;ÐÐpanel > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > th:first-child,Ðpanel > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:first-child,Ðpanel > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:first-child,Ðpanel > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:first-child,Ðpanel > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > td:first-child,Ðpanel > .table-bordered > tfoot > tr > td:first-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > td:first-child {Ð border-left: 0;ÐÐpanel > .table-bordered > thead > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > th:last-child,Ðpanel > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tbody > tr > th:last-child,Ðpanel > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-responsive > .table-bordered > tfoot > tr > th:last-child,Ðpanel > .table-bordered > thead > tr > td:last-child,Ðpanel > .table-responsive > .table-bordered > thead > tr > td:last-child,Ð

.panel > .table-bordered > tbody > tr > td:last-child,Ðpanel
> .table-responsive > .table-bordered > tbody > tr > td:last-child,Ðpanel
> .table-bordered > tfoot > tr > td:last-child,Ðpanel > .table-responsive
> .table-bordered > tfoot > tr > td:last-child {Ð border-right: 0;ÐÐpanel
> .table-bordered > thead > tr:last-child > th,Ðpanel > .table-responsive
> .table-bordered > thead > tr:last-child > th,Ðpanel > .table-bordered >
tbody > tr:last-child > th,Ðpanel > .table-responsive > .table-bordered >
tbody > tr:last-child > th,Ðpanel > .table-bordered > tfoot > tr:last-child >
th,Ðpanel > .table-responsive > .table-bordered > tfoot > tr:last-child > th,Ð
.panel > .table-bordered > thead > tr:last-child > td,Ðpanel > .table-
responsive > .table-bordered > thead > tr:last-child > td,Ðpanel > .table-
bordered > tbody > tr:last-child > td,Ðpanel > .table-responsive > .table-
bordered > tbody > tr:last-child > td,Ðpanel > .table-bordered > tfoot >
tr:last-child > td,Ðpanel > .table-responsive > .table-bordered > tfoot >
tr:last-child > td {Ð border-bottom: 0;ÐÐpanel > .table-responsive {Ð margin-
bottom: 0;Ð border: 0;ÐÐpanel-heading {Ð padding: 10px 15px;Ð border-bottom:
1px solid transparent;Ð border-top-right-radius: 3px;Ð border-top-left-
radius: 3px;ÐÐpanel-heading > .dropdown .dropdown-toggle {Ð color: inherit;ÐÐ
.panel-title {Ð margin-top: 0;Ð margin-bottom: 0;Ð font-size: 16px;Ð color:
inherit;ÐÐpanel-title > a {Ð color: inherit;ÐÐpanel-footer {Ð padding: 10px
15px;Ð background-color: #f5f5f5;Ð border-top: 1px solid #dddddd;Ð border-
bottom-right-radius: 3px;Ð border-bottom-left-radius: 3px;ÐÐpanel-
group .panel {Ð margin-bottom: 0;Ð overflow: hidden;Ð border-radius: 4px;ÐÐ
.panel-group .panel + .panel {Ð margin-top: 5px;ÐÐpanel-group .panel-heading {Ð
border-bottom: 0;ÐÐpanel-group .panel-heading + .panel-collapse .panel-body
{Ð border-top: 1px solid #dddddd;ÐÐpanel-group .panel-footer {Ð border-top: 0;Ð
}Ðpanel-group .panel-footer + .panel-collapse .panel-body {Ð border-bottom:
1px solid #dddddd;ÐÐpanel-default {Ð border-color: #dddddd;ÐÐpanel-default
> .panel-heading {Ð color: #333333;Ð background-color: #f5f5f5;Ð border-
color: #dddddd;ÐÐpanel-default > .panel-heading + .panel-collapse .panel-body
{Ð border-top-color: #dddddd;ÐÐpanel-default > .panel-footer + .panel-
collapse .panel-body {Ð border-bottom-color: #dddddd;ÐÐpanel-primary {Ð
border-color: #428bca;ÐÐpanel-primary > .panel-heading {Ð color: #ffffff;Ð
background-color: #428bca;Ð border-color: #428bca;ÐÐpanel-primary > .panel-
heading + .panel-collapse .panel-body {Ð border-top-color: #428bca;ÐÐpanel-
primary > .panel-footer + .panel-collapse .panel-body {Ð border-bottom-color:
#428bca;ÐÐpanel-success {Ð border-color: #d6e9c6;ÐÐpanel-success > .panel-
heading {Ð color: #3c763d;Ð background-color: #dff0d8;Ð border-color: #d6e9c6;Ð
}Ðpanel-success > .panel-heading + .panel-collapse .panel-body {Ð border-top-
color: #d6e9c6;ÐÐpanel-success > .panel-footer + .panel-collapse .panel-body {Ð
border-bottom-color: #d6e9c6;ÐÐpanel-warning {Ð border-color: #faebcc;ÐÐ
.panel-warning > .panel-heading {Ð color: #8a6d3b;Ð background-color: #fcf8e3;Ð
border-color: #faebcc;ÐÐpanel-warning > .panel-heading + .panel-
collapse .panel-body {Ð border-top-color: #faebcc;ÐÐpanel-warning > .panel-
footer + .panel-collapse .panel-body {Ð border-bottom-color: #faebcc;ÐÐpanel-
danger {Ð border-color: #ebccd1;ÐÐpanel-danger > .panel-heading {Ð color:
#a94442;Ð background-color: #f2dede;Ð border-color: #ebccd1;ÐÐpanel-danger
> .panel-heading + .panel-collapse .panel-body {Ð border-top-color: #ebccd1;ÐÐ
.panel-danger > .panel-footer + .panel-collapse .panel-body {Ð border-bottom-
color: #ebccd1;ÐÐpanel-info {Ð border-color: #bce8f1;ÐÐpanel-info > .panel-
heading {Ð color: #31708f;Ð background-color: #d9edf7;Ð border-color: #bce8f1;Ð
}Ðpanel-info > .panel-heading + .panel-collapse .panel-body {Ð border-top-
color: #bce8f1;ÐÐpanel-info > .panel-footer + .panel-collapse .panel-body {Ð
border-bottom-color: #bce8f1;ÐÐwell {Ð min-height: 20px;Ð padding: 19px;Ð
margin-bottom: 20px;Ð background-color: #f5f5f5;Ð border: 1px solid #e3e3e3;Ð
border-radius: 4px;Ð -webkit-box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.05);Ð
box-shadow: inset 0 1px 1px rgba(0, 0, 0, 0.05);ÐÐwell blockquote {Ð
border-color: #ddd;Ð border-color: rgba(0, 0, 0, 0.15);ÐÐwell-lg {Ð
padding: 24px;Ð border-radius: 6px;ÐÐwell-sm {Ð padding: 9px;Ð border-radius:
3px;Ð

}ÐÐclose {Ð float: right;Ð font-size: 21px;Ð font-weight: bold;Ð line-height: 1;Ð color: #000000;Ð text-shadow: 0 1px 0 #ffffff;Ð opacity: 0.2;Ð filter: alpha(opacity=20);ÞÐclose:hover,Ðclose:focus {Ð color: #000000;Ð text-decoration: none;Ð cursor: pointer;Ð opacity: 0.5;Ð filter: alpha(opacity=50);Ð }ÐÐbutton.close {Ð padding: 0;Ð cursor: pointer;Ð background: transparent;Ð border: 0;Ð -webkit-appearance: none;ÞÐmodal-open {Ð overflow: hidden;ÞÐmodal {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 1040;Ð display: none;Ð overflow: auto;Ð overflow-y: scroll;ÞÐmodal.fade .modal-dialog {Ð -webkit-transform: translate(0, -25%);Ð -ms-transform: translate(0, -25%);Ð transform: translate(0, -25%);Ð -webkit-transition: -webkit-transform 0.3s ease-out;Ð -moz-transition: -moz-transform 0.3s ease-out;Ð -o-transition: -o-transform 0.3s ease-out;Ð transition: transform 0.3s ease-out;ÞÐmodal.in .modal-dialog {Ð -webkit-transform: translate(0, 0);Ð -ms-transform: translate(0, 0);Ð transform: translate(0, 0);ÞÐmodal-dialog {Ð position: relative;Ð z-index: 1050;Ð width: auto;Ð margin: 10px;ÞÐmodal-content {Ð position: relative;Ð background-color: #ffffff;Ð border: 1px solid #999999;Ð border: 1px solid rgba(0, 0, 0, 0.2);Ð border-radius: 6px;Ð outline: none;Ð -webkit-box-shadow: 0 3px 9px rgba(0, 0, 0, 0.5);Ð box-shadow: 0 3px 9px rgba(0, 0, 0, 0.5);Ð background-clip: padding-box;ÞÐmodal-backdrop {Ð position: fixed;Ð top: 0;Ð right: 0;Ð bottom: 0;Ð left: 0;Ð z-index: 1030;Ð background-color: #000000;ÞÐmodal-backdrop.fade {Ð opacity: 0;Ð filter: alpha(opacity=0);ÞÐmodal-backdrop.in {Ð opacity: 0.5;Ð filter: alpha(opacity=50);ÞÐmodal-header {Ð min-height: 16.428571429px;Ð padding: 15px;Ð border-bottom: 1px solid #e5e5e5;ÞÐmodal-header .close {Ð margin-top: -2px;ÞÐmodal-title {Ð margin: 0;Ð line-height: 1.428571429;ÞÐmodal-body {Ð position: relative;Ð padding: 20px;ÞÐmodal-footer {Ð padding: 19px 20px 20px;Ð margin-top: 15px;Ð text-align: right;Ð border-top: 1px solid #e5e5e5;ÞÐ .modal-footer:before,Ðmodal-footer:after {Ð display: table;Ð content: " ";ÞÐ .modal-footer:after {Ð clear: both;ÞÐmodal-footer:before,Ðmodal-footer:after {Ð display: table;Ð content: " ";ÞÐmodal-footer:after {Ð clear: both;ÞÐmodal-footer .btn + .btn {Ð margin-bottom: 0;Ð margin-left: 5px;ÞÐmodal-footer .btn-group .btn + .btn {Ð margin-left: -1px;ÞÐmodal-footer .btn-block + .btn-block {Ð margin-left: 0;ÞÐmedia screen and (min-width: 768px) {Ð .modal-dialog {Ð width: 600px;Ð margin: 30px auto;Ð }Ð .modal-content {Ð -webkit-box-shadow: 0 5px 15px rgba(0, 0, 0, 0.5);Ð box-shadow: 0 5px 15px rgba(0, 0, 0, 0.5);Ð }ÞÐtooltip {Ð position: absolute;Ð z-index: 1030;Ð display: block;Ð font-size: 12px;Ð line-height: 1.4;Ð opacity: 0;Ð filter: alpha(opacity=0);Ð visibility: visible;ÞÐtooltip.in {Ð opacity: 0.9;Ð filter: alpha(opacity=90);ÞÐtooltip.top {Ð padding: 5px 0;Ð margin-top: -3px;ÞÐ .tooltip.right {Ð padding: 0 5px;Ð margin-left: 3px;ÞÐtooltip.bottom {Ð padding: 5px 0;Ð margin-top: 3px;ÞÐtooltip.left {Ð padding: 0 5px;Ð margin-left: -3px;ÞÐtooltip-inner {Ð max-width: 200px;Ð padding: 3px 8px;Ð color: #ffffff;Ð text-align: center;Ð text-decoration: none;Ð background-color: #000000;Ð border-radius: 4px;ÞÐtooltip-arrow {Ð position: absolute;Ð width: 0;Ð height: 0;Ð border-color: transparent;Ð border-style: solid;ÞÐ .tooltip.top .tooltip-arrow {Ð bottom: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-top-color: #000000;Ð border-width: 5px 5px 0;ÞÐtooltip.top-left .tooltip-arrow {Ð bottom: 0;Ð left: 5px;Ð border-top-color: #000000;Ð border-width: 5px 5px 0;ÞÐtooltip.top-right .tooltip-arrow {Ð right: 5px;Ð bottom: 0;Ð border-top-color: #000000;Ð border-width: 5px 5px 0;ÞÐ .tooltip.right .tooltip-arrow {Ð top: 50%;Ð left: 0;Ð margin-top: -5px;Ð border-right-color: #000000;Ð border-width: 5px 5px 5px 0;ÞÐ .tooltip.left .tooltip-arrow {Ð top: 50%;Ð right: 0;Ð margin-top: -5px;Ð border-left-color: #000000;Ð border-width: 5px 0 5px 5px;ÞÐ .tooltip.bottom .tooltip-arrow {Ð top: 0;Ð left: 50%;Ð margin-left: -5px;Ð border-bottom-color: #000000;Ð border-width: 0 5px 5px;ÞÐtooltip.bottom-left .tooltip-arrow {Ð top: 0;Ð left: 5px;Ð border-bottom-color: #000000;Ð border-width: 0 5px 5px;ÞÐtooltip.bottom-right .tooltip-arrow {Ð top: 0;Ð right: 5px;Ð

```
            border-bottom-color: #000000;Ð border-width: 0 5px 5px;ÞÐpopover
{Ð position: absolute;Ð top: 0;Ð left: 0;Ð z-index: 1010;Ð display: none;Ð
max-width: 276px;Ð padding: 1px;Ð text-align: left;Ð white-space: normal;Ð
background-color: #ffffff;Ð border: 1px solid #cccccc;Ð border: 1px solid
rgba(0, 0, 0, 0.2);Ð border-radius: 6px;Ð -webkit-box-shadow: 0 5px 10px
rgba(0, 0, 0, 0.2);Ð         box-shadow: 0 5px 10px rgba(0, 0, 0, 0.2);Ð
background-clip: padding-box;ÞÐpopover.top {Ð margin-top: -10px;ÞÐ
.popover.right {Ð margin-left: 10px;ÞÐpopover.bottom {Ð margin-top: 10px;ÞÐ
.popover.left {Ð margin-left: -10px;ÞÐpopover-title {Ð padding: 8px 14px;Ð
margin: 0;Ð font-size: 14px;Ð font-weight: normal;Ð line-height: 18px;Ð
background-color: #f7f7f7;Ð border-bottom: 1px solid #ebebeb;Ð border-radius:
5px 5px 0 0;ÞÐpopover-content {Ð padding: 9px 14px;ÞÐpopover .arrow,Ð
.popover .arrow:after {Ð position: absolute;Ð display: block;Ð width: 0;Ð
height: 0;Ð border-color: transparent;Ð border-style: solid;ÞÐpopover .arrow {Ð
  border-width: 11px;ÞÐpopover .arrow:after {Ð border-width: 10px;Ð content:
"";ÞÐpopover.top .arrow {Ð bottom: -11px;Ð left: 50%;Ð margin-left: -11px;Ð
border-top-color: #999999;Ð border-top-color: rgba(0, 0, 0, 0.25);Ð border-
bottom-width: 0;ÞÐpopover.top .arrow:after {Ð bottom: 1px;Ð margin-left:
-10px;Ð border-top-color: #ffffff;Ð border-bottom-width: 0;Ð content: " ";ÞÐ
.popover.right .arrow {Ð top: 50%;Ð left: -11px;Ð margin-top: -11px;Ð border-
right-color: #999999;Ð border-right-color: rgba(0, 0, 0, 0.25);Ð border-left-
width: 0;ÞÐpopover.right .arrow:after {Ð bottom: -10px;Ð left: 1px;Ð border-
right-color: #ffffff;Ð border-left-width: 0;Ð content: " ";ÞÐ
.popover.bottom .arrow {Ð top: -11px;Ð left: 50%;Ð margin-left: -11px;Ð
border-bottom-color: #999999;Ð border-bottom-color: rgba(0, 0, 0, 0.25);Ð
border-top-width: 0;ÞÐpopover.bottom .arrow:after {Ð top: 1px;Ð margin-left:
-10px;Ð border-bottom-color: #ffffff;Ð border-top-width: 0;Ð content: " ";ÞÐ
.popover.left .arrow {Ð top: 50%;Ð right: -11px;Ð margin-top: -11px;Ð border-
left-color: #999999;Ð border-left-color: rgba(0, 0, 0, 0.25);Ð border-right-
width: 0;ÞÐpopover.left .arrow:after {Ð right: 1px;Ð bottom: -10px;Ð border-
left-color: #ffffff;Ð border-right-width: 0;Ð content: " ";ÞÐcarousel {Ð
position: relative;ÞÐcarousel-inner {Ð position: relative;Ð width: 100%;Ð
overflow: hidden;ÞÐcarousel-inner > .item {Ð position: relative;Ð display:
none;Ð -webkit-transition: 0.6s ease-in-out left;Ð         transition: 0.6s
ease-in-out left;ÞÐcarousel-inner > .item > img,Ðcarousel-inner > .item > a >
img {Ð display: block;Ð height: auto;Ð max-width: 100%;Ð line-height: 1;ÞÐ
.carousel-inner > .active,Ðcarousel-inner > .next,Ðcarousel-inner > .prev {Ð
display: block;ÞÐcarousel-inner > .active {Ð left: 0;ÞÐcarousel-inner > .next,Ð
.carousel-inner > .prev {Ð position: absolute;Ð top: 0;Ð width: 100%;ÞÐ
.carousel-inner > .next {Ð left: 100%;ÞÐcarousel-inner > .prev {Ð left: -100%;Ð
}Ðcarousel-inner > .next.left,Ðcarousel-inner > .prev.right {Ð left: 0;ÞÐ
.carousel-inner > .active.left {Ð left: -100%;ÞÐcarousel-inner
> .active.right {Ð left: 100%;ÞÐcarousel-control {Ð position: absolute;Ð top:
0;Ð bottom: 0;Ð left: 0;Ð width: 15%;Ð font-size: 20px;Ð color: #ffffff;Ð
text-align: center;Ð text-shadow: 0 1px 2px rgba(0, 0, 0, 0.6);Ð opacity: 0.5;Ð
  filter: alpha(opacity=50);ÞÐcarousel-control.left {Ð background-image: -
webkit-linear-gradient(left, color-stop(rgba(0, 0, 0, 0.5) 0), color-
stop(rgba(0, 0, 0, 0.0001) 100%));Ð background-image: linear-gradient(to
right, rgba(0, 0, 0, 0.5) 0, rgba(0, 0, 0, 0.0001) 100%);Ð background-repeat:
repeat-x;Ð filter:
progid:DXImageTransform.Microsoft.gradient(startColorstr='#80000000',
endColorstr='#00000000', GradientType=1);ÞÐcarousel-control.right {Ð right: 0;Ð
  left: auto;Ð background-image: -webkit-linear-gradient(left, color-
stop(rgba(0, 0, 0, 0.0001) 0), color-stop(rgba(0, 0, 0, 0.5) 100%));Ð
background-image: linear-gradient(to right, rgba(0, 0, 0, 0.0001) 0, rgba(0,
0, 0, 0.5) 100%);Ð background-repeat: repeat-x;Ð filter:
progid:DXImageTransform.Microsoft.gradient(startColorstr='#00000000',
endColorstr='#80000000', GradientType=1);ÞÐcarousel-control:hover,Ðcarousel-
control:focus {Ð color: #ffffff;Ð text-decoration: none;Ð outline: none;Ð
opacity: 0.9;Ð
```

filter: alpha(opacity=90);ÐÐcarousel-control .icon-prev,Ð
.carousel-control .icon-next,Ðcarousel-control .glyphicon-chevron-left,Ð
.carousel-control .glyphicon-chevron-right {Ð position: absolute;Ð top: 50%;Ð
z-index: 5;Ð display: inline-block;ÐÐcarousel-control .icon-prev,Ðcarousel-
control .glyphicon-chevron-left {Ð left: 50%;ÐÐcarousel-control .icon-next,Ð
.carousel-control .glyphicon-chevron-right {Ð right: 50%;ÐÐcarousel-
control .icon-prev,Ðcarousel-control .icon-next {Ð width: 20px;Ð height: 20px;Ð
  margin-top: -10px;Ð margin-left: -10px;Ð font-family: serif;ÐÐcarousel-
control .icon-prev:before {Ð content: '\2039';ÐÐcarousel-control .icon-
next:before {Ð content: '\203a';ÐÐcarousel-indicators {Ð position: absolute;Ð
bottom: 10px;Ð left: 50%;Ð z-index: 15;Ð width: 60%;Ð padding-left: 0;Ð
margin-left: -30%;Ð text-align: center;Ð list-style: none;ÐÐcarousel-
indicators li {Ð display: inline-block;Ð width: 10px;Ð height: 10px;Ð margin:
1px;Ð text-indent: -999px;Ð cursor: pointer;Ð background-color: #000 \9;Ð
background-color: rgba(0, 0, 0, 0);Ð border: 1px solid #ffffff;Ð border-
radius: 10px;ÐÐcarousel-indicators .active {Ð width: 12px;Ð height: 12px;Ð
margin: 0;Ð background-color: #ffffff;ÐÐcarousel-caption {Ð position:
absolute;Ð right: 15%;Ð bottom: 20px;Ð left: 15%;Ð z-index: 10;Ð padding-top:
20px;Ð padding-bottom: 20px;Ð color: #ffffff;Ð text-align: center;Ð text-
shadow: 0 1px 2px rgba(0, 0, 0, 0.6);ÐÐcarousel-caption .btn {Ð text-shadow:
none;ÐÐ@media screen and (min-width: 768px) {Ð .carousel-control .glyphicons-
chevron-left,Ð .carousel-control .glyphicons-chevron-right,Ð .carousel-
control .icon-prev,Ð .carousel-control .icon-next {Ð width: 30px;Ð
height: 30px;Ð margin-top: -15px;Ð margin-left: -15px;Ð font-size: 30px;Ð
  }Ð .carousel-caption {Ð right: 20%;Ð left: 20%;Ð padding-bottom: 30px;Ð
  }Ð .carousel-indicators {Ð bottom: 20px;Ð }ÐÐclearfix:before,Ð
.clearfix:after {Ð display: table;Ð content: " ";ÐÐclearfix:after {Ð clear:
both;ÐÐcenter-block {Ð display: block;Ð margin-right: auto;Ð margin-left:
auto;ÐÐpull-right {Ð float: right !important;ÐÐpull-left {Ð float: left !
important;ÐÐhide {Ð display: none !important;ÐÐshow {Ð display: block !
important;ÐÐinvisible {Ð visibility: hidden;ÐÐtext-hide {Ð font: 0/0 a;Ð
color: transparent;Ð text-shadow: none;Ð background-color: transparent;Ð
border: 0;ÐÐhidden {Ð display: none !important;Ð visibility: hidden !
important;ÐÐaffix {Ð position: fixed;ÐÐ-ms-viewport {Ð width: device-width;ÐÐ
.visible-xs,Ðtr.visible-xs,Ðth.visible-xs,Ðtd.visible-xs {Ð display: none !
important;ÐÐ@media (max-width: 767px) {Ð .visible-xs {Ð display: block !
important;Ð }Ð table.visible-xs {Ð display: table;Ð }Ð tr.visible-xs {Ð
display: table-row !important;Ð }Ð th.visible-xs,Ð td.visible-xs {Ð
display: table-cell !important;Ð }ÐÐ@media (min-width: 768px) and (max-width:
991px) {Ð .visible-xs.visible-sm {Ð display: block !important;Ð }Ð
table.visible-xs.visible-sm {Ð display: table;Ð }Ð tr.visible-xs.visible-sm
{Ð display: table-row !important;Ð }Ð th.visible-xs.visible-sm,Ð td.visible-
xs.visible-sm {Ð display: table-cell !important;Ð }ÐÐ@media (min-width:
992px) and (max-width: 1199px) {Ð .visible-xs.visible-md {Ð display: block !
important;Ð }Ð table.visible-xs.visible-md {Ð display: table;Ð }Ð
tr.visible-xs.visible-md {Ð display: table-row !important;Ð }Ð th.visible-
xs.visible-md,Ð td.visible-xs.visible-md {Ð display: table-cell !important;Ð
  }ÐÐ@media (min-width: 1200px) {Ð .visible-xs.visible-lg {Ð display: block !
important;Ð }Ð table.visible-xs.visible-lg {Ð display: table;Ð }Ð
tr.visible-xs.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-
xs.visible-lg,Ð td.visible-xs.visible-lg {Ð display: table-cell !important;Ð
  }ÐÐvisible-sm,Ðtr.visible-sm,Ðth.visible-sm,Ðtd.visible-sm {Ð display: none !
important;ÐÐ@media (max-width: 767px) {Ð .visible-sm.visible-xs {Ð display:
block !important;Ð }Ð table.visible-sm.visible-xs {Ð display: table;Ð }Ð
tr.visible-sm.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-
sm.visible-xs,Ð td.visible-sm.visible-xs {Ð display: table-cell !important;Ð
  }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .visible-sm {Ð
display: block !important;Ð }Ð table.visible-sm {Ð display: table;Ð }Ð
tr.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-sm,Ð
td.visible-sm {Ð

display: table-cell !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-sm.visible-md {Ð display: block !important;Ð }Ð table.visible-sm.visible-md {Ð display: table;Ð }Ð tr.visible-sm.visible-md {Ð display: table-row !important;Ð }Ð th.visible-sm.visible-md,Ð td.visible-sm.visible-md {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .visible-sm.visible-lg {Ð display: block !important;Ð }Ð table.visible-sm.visible-lg {Ð display: table;Ð }Ð tr.visible-sm.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-sm.visible-lg,Ð td.visible-sm.visible-lg {Ð display: table-cell !important;Ð }ÐÐvisible-md,Ðtr.visible-md,Ðth.visible-md,Ðtd.visible-md {Ð display: none !important;ÐÐ@media (max-width: 767px) {Ð .visible-md.visible-xs {Ð display: block !important;Ð }Ð table.visible-md.visible-xs {Ð display: table;Ð }Ð tr.visible-md.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-md.visible-xs,Ð td.visible-md.visible-xs {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .visible-md.visible-sm {Ð display: block !important;Ð }Ð table.visible-md.visible-sm {Ð display: table;Ð }Ð tr.visible-md.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-md.visible-sm,Ð td.visible-md.visible-sm {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-md {Ð display: block !important;Ð }Ð table.visible-md {Ð display: table;Ð }Ð tr.visible-md {Ð display: table-row !important;Ð }Ð th.visible-md,Ð td.visible-md {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .visible-md.visible-lg {Ð display: block !important;Ð }Ð table.visible-md.visible-lg {Ð display: table;Ð }Ð tr.visible-md.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-md.visible-lg,Ð td.visible-md.visible-lg {Ð display: table-cell !important;Ð }ÐÐ .visible-lg,Ðtr.visible-lg,Ðth.visible-lg,Ðtd.visible-lg {Ð display: none !important;ÐÐ@media (max-width: 767px) {Ð .visible-lg.visible-xs {Ð display: block !important;Ð }Ð table.visible-lg.visible-xs {Ð display: table;Ð }Ð tr.visible-lg.visible-xs {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-xs,Ð td.visible-lg.visible-xs {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .visible-lg.visible-sm {Ð display: block !important;Ð }Ð table.visible-lg.visible-sm {Ð display: table;Ð }Ð tr.visible-lg.visible-sm {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-sm,Ð td.visible-lg.visible-sm {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .visible-lg.visible-md {Ð display: block !important;Ð }Ð table.visible-lg.visible-md {Ð display: table;Ð }Ð tr.visible-lg.visible-md {Ð display: table-row !important;Ð }Ð th.visible-lg.visible-md,Ð td.visible-lg.visible-md {Ð display: table-cell !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .visible-lg {Ð display: block !important;Ð }Ð table.visible-lg {Ð display: table;Ð }Ð tr.visible-lg {Ð display: table-row !important;Ð }Ð th.visible-lg,Ð td.visible-lg {Ð display: table-cell !important;Ð }ÐÐhidden-xs {Ð display: block !important;ÐÐable.hidden-xs {Ð display: table;ÐÐtr.hidden-xs {Ð display: table-row !important;ÐÐth.hidden-xs,Ðtd.hidden-xs {Ð display: table-cell !important;ÐÐ@media (max-width: 767px) {Ð .hidden-xs,Ð tr.hidden-xs,Ð th.hidden-xs,Ð td.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð .hidden-xs.hidden-sm,Ð tr.hidden-xs.hidden-sm,Ð th.hidden-xs.hidden-sm,Ð td.hidden-xs.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-xs.hidden-md,Ð tr.hidden-xs.hidden-md,Ð th.hidden-xs.hidden-md,Ð td.hidden-xs.hidden-md {Ð display: none !important;Ð }ÐÐ@media (min-width: 1200px) {Ð .hidden-xs.hidden-lg,Ð tr.hidden-xs.hidden-lg,Ð th.hidden-xs.hidden-lg,Ð td.hidden-xs.hidden-lg {Ð display: none !important;Ð }ÐÐ .hidden-sm {Ð display: block !important;ÐÐable.hidden-sm {Ð display: table;ÐÐ tr.hidden-sm {Ð display: table-row !important;ÐÐth.hidden-sm,Ðtd.hidden-sm {Ð display: table-cell !important;ÐÐ@media (max-width: 767px) {Ð .hidden-sm.hidden-xs,Ð tr.hidden-sm.hidden-xs,Ð th.hidden-sm.hidden-xs,Ð td.hidden-sm.hidden-xs {Ð display: none !important;Ð }ÐÐ@media (min-width: 768px) and (max-width: 991px) {Ð

.hidden-sm,Ð tr.hidden-sm,Ð th.hidden-sm,Ð td.hidden-sm {Ð display: none !important;Ð }ÐÐ@media (min-width: 992px) and (max-width: 1199px) {Ð .hidden-sm.hidden-md,Ð tr.hidden-sm.hidden-md,Ð th.hidden-sm.hidden-md,Ð td.hidden-sm.hidden-md {Ð display: none !important;Ð }ÐÐ @media (min-width: 1200px) {Ð .hidden-sm.hidden-lg,Ð tr.hidden-sm.hidden-lg,Ð th.hidden-sm.hidden-lg,Ð td.hidden-sm.hidden-lg {Ð display: none !important;Ð }ÐÐhidden-md {Ð display: block !important;ÐÐable.hidden-md {Ð display: table;ÐÐr.hidden-md {Ð display: table-row !important;ÐÐh.hidden-md,Ðd.hidden-md {Ð display: table-cell !important;ÐÐmedia (max-width: 767px) {Ð .hidden-md.hidden-xs,Ð tr.hidden-md.hidden-xs,Ð th.hidden-md.hidden-xs,Ð td.hidden-md.hidden-xs {Ð display: none !important;Ð }ÐÐmedia (min-width: 768px) and (max-width: 991px) {Ð .hidden-md.hidden-sm,Ð tr.hidden-md.hidden-sm,Ð th.hidden-md.hidden-sm,Ð td.hidden-md.hidden-sm {Ð display: none !important;Ð }ÐÐmedia (min-width: 992px) and (max-width: 1199px) {Ð .hidden-md,Ð tr.hidden-md,Ð th.hidden-md,Ð td.hidden-md {Ð display: none !important;Ð }ÐÐ @media (min-width: 1200px) {Ð .hidden-md.hidden-lg,Ð tr.hidden-md.hidden-lg,Ð th.hidden-md.hidden-lg,Ð td.hidden-md.hidden-lg {Ð display: none !important;Ð }ÐÐhidden-lg {Ð display: block !important;ÐÐable.hidden-lg {Ð display: table;ÐÐr.hidden-lg {Ð display: table-row !important;ÐÐh.hidden-lg,Ðd.hidden-lg {Ð display: table-cell !important;ÐÐmedia (max-width: 767px) {Ð .hidden-lg.hidden-xs,Ð tr.hidden-lg.hidden-xs,Ð th.hidden-lg.hidden-xs,Ð td.hidden-lg.hidden-xs {Ð display: none !important;Ð }ÐÐmedia (min-width: 768px) and (max-width: 991px) {Ð .hidden-lg.hidden-sm,Ð tr.hidden-lg.hidden-sm,Ð th.hidden-lg.hidden-sm,Ð td.hidden-lg.hidden-sm {Ð display: none !important;Ð }ÐÐmedia (min-width: 992px) and (max-width: 1199px) {Ð .hidden-lg.hidden-md,Ð tr.hidden-lg.hidden-md,Ð th.hidden-lg.hidden-md,Ð td.hidden-lg.hidden-md {Ð display: none !important;Ð }ÐÐmedia (min-width: 1200px) {Ð .hidden-lg,Ð tr.hidden-lg,Ð th.hidden-lg,Ð td.hidden-lg {Ð display: none !important;Ð }ÐÐ .visible-print,Ðr.visible-print,Ðh.visible-print,Ðd.visible-print {Ð display: none !important;ÐÐmedia print {Ð .visible-print {Ð display: block !important;Ð }Ð table.visible-print {Ð display: table;Ð }Ð tr.visible-print {Ð display: table-row !important;Ð }Ð th.visible-print,Ð td.visible-print {Ð display: table-cell !important;Ð }Ð .hidden-print,Ð tr.hidden-print,Ð th.hidden-print,Ð td.hidden-print {Ð display: none !important;Ð }Ð

public\assets\frontend\css\magnific-popup.css

```
/* Magnific Popup CSS */Đmfp-bg {Đ top: 0;Đ left: 0;Đ width: 100%;Đ height:
100%;Đ z-index: 1042;Đ overflow: hidden;Đ position: fixed;Đ background:
#0b0b0b;Đ opacity: 0.8;Đ filter: alpha(opacity=80); }Đmfp-wrap {Đ top: 0;Đ
left: 0;Đ width: 100%;Đ height: 100%;Đ z-index: 1043;Đ position: fixed;Đ
outline: none !important;Đ -webkit-backface-visibility: hidden; }Đmfp-
container {Đ text-align: center;Đ position: absolute;Đ width: 100%;Đ height:
100%;Đ left: 0;Đ top: 0;Đ padding: 0 8px;Đ -webkit-box-sizing: border-box;Đ -
moz-box-sizing: border-box;Đ box-sizing: border-box; }Đmfp-container:before {Đ
  content: '';Đ display: inline-block;Đ height: 100%;Đ vertical-align:
middle; }Đmfp-align-top .mfp-container:before {Đ display: none; }Đmfp-content
{Đ position: relative;Đ display: inline-block;Đ vertical-align: middle;Đ
margin: 0 auto;Đ text-align: left;Đ z-index: 1045; }Đmfp-inline-holder .mfp-
content,Đmfp-ajax-holder .mfp-content {Đ width: 100%;Đ cursor: auto; }Đmfp-
ajax-cur {Đ cursor: progress; }Đmfp-zoom-out-cur, .mfp-zoom-out-cur .mfp-
image-holder .mfp-close {Đ cursor: -moz-zoom-out;Đ cursor: -webkit-zoom-out;Đ
cursor: zoom-out; }Đmfp-zoom {Đ cursor: pointer;Đ cursor: -webkit-zoom-in;Đ
cursor: -moz-zoom-in;Đ cursor: zoom-in; }Đmfp-auto-cursor .mfp-content {Đ
cursor: auto; }Đmfp-close,Đmfp-arrow,Đmfp-preloader,Đmfp-counter {Đ -webkit-
user-select: none;Đ -moz-user-select: none;Đ user-select: none; }Đmfp-
loading.mfp-figure {Đ display: none; }Đmfp-hide {Đ display: none !important; }Đ
.mfp-preloader {Đ color: #CCC;Đ position: absolute;Đ top: 50%;Đ width: auto;Đ
text-align: center;Đ margin-top: -0.8em;Đ left: 8px;Đ right: 8px;Đ z-index:
1044; }Đ .mfp-preloader a {Đ   color: #CCC; }Đ   .mfp-preloader a:hover {Đ
      color: #FFF; }Đmfp-s-ready .mfp-preloader {Đ display: none; }Đmfp-s-
error .mfp-content {Đ display: none; }Đutton.mfp-close,Đutton.mfp-arrow {Đ
overflow: visible;Đ cursor: pointer;Đ background: transparent;Đ border: 0;Đ -
webkit-appearance: none;Đ display: block;Đ outline: none;Đ padding: 0;Đ z-
index: 1046;Đ -webkit-box-shadow: none;Đ box-shadow: none; }Đutton::-moz-
focus-inner {Đ padding: 0;Đ border: 0; }Đmfp-close {Đ width: 44px;Đ height:
44px;Đ line-height: 44px;Đ position: absolute;Đ right: 0;Đ top: 0;Đ text-
decoration: none;Đ text-align: center;Đ opacity: 0.65;Đ filter:
alpha(opacity=65);Đ padding: 0 0 18px 10px;Đ color: #FFF;Đ font-style: normal;Đ
  font-size: 28px;Đ font-family: Arial, Baskerville, monospace; }Đ .mfp-
close:hover,Đ .mfp-close:focus {Đ   opacity: 1;Đ   filter:
alpha(opacity=100); }Đ .mfp-close:active {Đ   top: 1px; }Đmfp-close-btn-
in .mfp-close {Đ color: #333; }Đmfp-image-holder .mfp-close,Đmfp-iframe-
holder .mfp-close {Đ color: #FFF;Đ right: -6px;Đ text-align: right;Đ padding-
right: 6px;Đ width: 100%; }Đmfp-counter {Đ position: absolute;Đ top: 0;Đ
right: 0;Đ color: #CCC;Đ font-size: 12px;Đ line-height: 18px;Đ white-space:
nowrap; }Đmfp-arrow {Đ position: absolute;Đ opacity: 0.65;Đ filter:
alpha(opacity=65);Đ margin: 0;Đ top: 50%;Đ margin-top: -55px;Đ padding: 0;Đ
width: 90px;Đ height: 110px;Đ -webkit-tap-highlight-color: transparent; }Đ
  .mfp-arrow:active {Đ   margin-top: -54px; }Đ .mfp-arrow:hover,Đ .mfp-
arrow:focus {Đ   opacity: 1;Đ   filter: alpha(opacity=100); }Đ .mfp-
arrow:before,Đ .mfp-arrow:after,Đ .mfp-arrow .mfp-b,Đ .mfp-arrow .mfp-a {Đ
content: '';Đ   display: block;Đ   width: 0;Đ   height: 0;Đ   position:
absolute;Đ   left: 0;Đ   top: 0;Đ   margin-top: 35px;Đ   margin-left: 35px;Đ
    border: medium inset transparent; }Đ .mfp-arrow:after,Đ .mfp-arrow .mfp-a
{Đ   border-top-width: 13px;Đ   border-bottom-width: 13px;Đ   top: 8px; }Đ
  .mfp-arrow:before,Đ .mfp-arrow .mfp-b {Đ   border-top-width: 21px;Đ
border-bottom-width: 21px;Đ   opacity: 0.7; }Đmfp-arrow-left {Đ left: 0; }Đ
  .mfp-arrow-left:after,Đ .mfp-arrow-left .mfp-a {Đ   border-right: 17px
solid #FFF;Đ   margin-left: 31px; }Đ .mfp-arrow-left:before,Đ .mfp-arrow-
left .mfp-b {Đ   margin-left: 25px;Đ   border-right: 27px solid #3F3F3F; }Đ
.mfp-arrow-right {Đ right: 0; }Đ .mfp-arrow-right:after,Đ .mfp-arrow-
right .mfp-a {Đ   border-left: 17px solid #FFF;Đ   margin-left: 39px; }Đ .mfp-
arrow-right:before,Đ .mfp-arrow-right .mfp-b {Đ   border-left: 27px solid
#3F3F3F; }Đmfp-iframe-holder {Đ padding-top: 40px;Đ padding-bottom: 40px; }Đ
  .mfp-iframe-holder .mfp-content {Đ
```

line-height: 0;Ð width: 100%;Ð max-width: 900px; }Ð .mfp-iframe-holder .mfp-close {Ð top: -40px; }Ðmfp-iframe-scaler {Ð width: 100%;Ð height: 0;Ð overflow: hidden;Ð padding-top: 56.25%; }Ð .mfp-iframe-scaler iframe {Ð position: absolute;Ð display: block;Ð top: 0;Ð left: 0;Ð width: 100%;Ð height: 100%;Ð box-shadow: 0 0 8px rgba(0, 0, 0, 0.6);Ð background: #000; }Ð* Main image in popup */Ðimg.mfp-img {Ð width: auto;Ð max-width: 100%;Ð height: auto;Ð display: block;Ð line-height: 0;Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box;Ð padding: 40px 0 40px;Ð margin: 0 auto; }Ð* The shadow behind the image */Ðmfp-figure {Ð line-height: 0; }Ð .mfp-figure:after {Ð content: '';Ð position: absolute;Ð left: 0;Ð top: 40px;Ð bottom: 40px;Ð display: block;Ð right: 0;Ð width: auto;Ð height: auto;Ð z-index: -1;Ð box-shadow: 0 0 8px rgba(0, 0, 0, 0.6);Ð background: #444; }Ð .mfp-figure small {Ð color: #BDBDBD;Ð display: block;Ð font-size: 12px;Ð line-height: 14px; }Ð .mfp-figure figure {Ð margin: 0; }Ðmfp-bottom-bar {Ð margin-top: -36px;Ð position: absolute;Ð top: 100%;Ð left: 0;Ð width: 100%;Ð cursor: auto; }Ðmfp-title {Ð text-align: left;Ð line-height: 18px;Ð color: #F3F3F3;Ð word-wrap: break-word;Ð padding-right: 36px; }Ðmfp-image-holder .mfp-content {Ð max-width: 100%; }Ðmfp-gallery .mfp-image-holder .mfp-figure {Ð cursor: pointer; }Ð@media screen and (max-width: 800px) and (orientation: landscape), screen and (max-height: 300px) {Ð /**Ð * Remove all paddings around the image on small screenÐ */Ð .mfp-img-mobile .mfp-image-holder {Ð padding-left: 0;Ð padding-right: 0; }Ð .mfp-img-mobile img.mfp-img {Ð padding: 0; }Ð .mfp-img-mobile .mfp-figure:after {Ð top: 0;Ð bottom: 0; }Ð .mfp-img-mobile .mfp-figure small {Ð display: inline;Ð margin-left: 5px; }Ð .mfp-img-mobile .mfp-bottom-bar {Ð background: rgba(0, 0, 0, 0.6);Ð bottom: 0;Ð margin: 0;Ð top: auto;Ð padding: 3px 5px;Ð position: fixed;Ð -webkit-box-sizing: border-box;Ð -moz-box-sizing: border-box;Ð box-sizing: border-box; }Ð .mfp-img-mobile .mfp-bottom-bar:empty {Ð padding: 0; }Ð .mfp-img-mobile .mfp-counter {Ð right: 5px;Ð top: 3px; }Ð .mfp-img-mobile .mfp-close {Ð top: 0;Ð right: 0;Ð width: 35px;Ð height: 35px;Ð line-height: 35px;Ð background: rgba(0, 0, 0, 0.6);Ð position: fixed;Ð text-align: center;Ð padding: 0; } }Ð@media all and (max-width: 900px) {Ð .mfp-arrow {Ð -webkit-transform: scale(0.75);Ð transform: scale(0.75); }Ð .mfp-arrow-left {Ð -webkit-transform-origin: 0;Ð transform-origin: 0; }Ð .mfp-arrow-right {Ð -webkit-transform-origin: 100%;Ð transform-origin: 100%; }Ð .mfp-container {Ð padding-left: 6px;Ð padding-right: 6px; } }Ðmfp-ie7 .mfp-img {Ð padding: 0; }Ðmfp-ie7 .mfp-bottom-bar {Ð width: 600px;Ð left: 50%;Ð margin-left: -300px;Ð margin-top: 5px;Ð padding-bottom: 5px; }Ðmfp-ie7 .mfp-container {Ð padding: 0; }Ðmfp-ie7 .mfp-content {Ð padding-top: 44px; }Ðmfp-ie7 .mfp-close {Ð top: 0;Ð right: 0;Ð padding-top: 0; }Ð

public\assets\frontend\css\style.css

/*Ð Theme Name: Taaz Template - Green VariantÐ Theme URI: http://yourdomain.com/taaz-greenÐ Description: This css file is for a light template layout with a green theme, ideal for a dispensary.Ð Version: 1.0Ð Author: M ARFAN (Modified by you)Ð Author URI: http://yourdomain.comÐ Tags: green, dispensary, light, templateÐ Ð ----------Ð MAIN TEMPLATE STYLESÐ ----------Ð Ð TABLE OF CONTENTSÐ 01. Global Content StylesÐ 02. Preloader Content StylesÐ 03. Header Content StylesÐ 04. Banner Content StylesÐ 05. Schedule Content StylesÐ 06. Parallax-02 Content Styles Ð 07. community Content StylesÐ 08. Speak with Us NOW Styles Ð 09. Footer Black StylesÐ 10. Footer Main StylesÐ 11. Contact banner StylesÐ 12. Contact-Map & Form Content StylesÐ 13. Contact-adresss Content StylesÐ 14. About internal page StylesÐ 15. Our Menu internal page StylesÐ 16. Our Menu internal page StylesÐ 17. Media QueryÐ/Ð* ========== */Ð* 01. Global Content Styles */Ð* ========== */Ðfont-face {ÐföçBÐ family: 'FontAwesome';Ð7&3¢ W&Â,rââöföçBÖ vW6öÖRöföçG2öföçF vW6öÖRÐ webfonte0a5.eot?v=4.3.0');Ð7&3¢ W&Â,rââöföçBÖ vW6öÖRöföçG2öföçF vW6öÖRÐ webfontd41d.eot?#iefix&v=4.3.0') format('embedded-opentype'), url('../font-awesome/fonts/fontawesome-webfonte0a5.html?v=4.3.0') format('woff2'), url('../font-awesome/fonts/fontawesome-webfonte0a5.woff?v=4.3.0') format('woff'), url('../font-awesome/fonts/fontawesome-webfonte0a5.ttf?v=4.3.0') format('truetype'), url('../font-awesome/fonts/fontawesome-webfonte0a5.svg?v=4.3.0#fontawesomeregular') format('svg');ÐföçB×vV–v‡C¢ æ÷&Ö Ã½föçB×7G–ÆS¢ normal;ÐÐtml, body {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½föçB×vV–v‡C¢ 3 ½ height: 100%;Ðv–GFƒ¢ S½Æ–æRÖ†V–v‡C¢ #G ƒ½föçB×6—¦S¢ g ƒ½6öÆ÷#¢ 3cccccc½ background-color: #ffffff;ÐØ* Link Styling */Ða, a:hover, a:active, a:visited, a:link {Ð÷WFÆ–æS¢ æöæS½6öÆ÷#¢33#ƒc&c½×vV&¶—B×G& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½ÖÖ÷¢Ð transition: all 0.5s ease 0s;ÐÖ×2×G& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½G& ç6—F–öã¢ ÆÂ 0.5s ease 0s;ÐFW‡BÖFV6÷& F–öã¢ æöæS½Ða {Ð font-size:16px;Ð text-transform: uppercase;Ð6öÆ÷#¢33#ƒc&c½föçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½ letter-spacing:0px;ØØ* Headings */Ðh1 {ÐföçBÖf Ö–Ç“¢ u&ö&÷FòrÂ 6 ç2×6W&–c½föçBÐ size:60px;ÐföçB×vV–v‡C£ƒ ½Ö &v–ã£ , ½FW‡B×G& ç6f÷&Ó¢ W W&6 6S½6öÆ÷#¢ #fff;ØÐh2 {ÐföçBÖf Ö–Ç“¢ u&ö&÷FòrÂ 6 ç2×6W&–c½föçB×6—¦S£C‡ ƒ½Ö &v–ã¢ , ½ text-transform: uppercase;Ð6öÆ÷#¢ 3 ½föçB×vV–v‡C¢ ƒ ½Ðh2 span {ÐÖ &v–ã¢ ½ font-family: 'Cookie';ÐföçB×6—¦S£s ƒ½6öÆ÷#¢ 3&V63s ² ò¢ w&VVâ ¢ýföçBÐ weight:400;ÐÆ–æRÖ†V–v‡C£3W ƒ½FW‡B×G& ç6f÷&Ó¢ 6 —F Æ—¦S½F—7 Æ “¦&Æö6³½Ðh3 {Ð margin: 0;ÐföçBÖf Ö–Ç“¢ u&ö&÷FòrÂ 6 ç2×6W&–c½föçB×6—¦S£3 ƒ½6öÆ÷#¢ 3 ½ font-weight:400;ÐÆ–æRÖ†V–v‡C£CW ƒ½FW‡B×G& ç6f÷&Ó¢ 6 —F Æ—¦S½Ðh4 {Ð color:#000000;ÐföçBÖf Ö–Ç“¢ u&ö&÷FòrÂ 6 ç2×6W&–c½ font-size: 24px;Ð font-weight: 400;Ð margin: 0 0 10px;Ð padding: 0;Ð text-transform:capitalize;Ð }Ðh5 {ÐÖ &v–ã¢ ½föçBÖf Ö–Ç“¢ u&ö&÷FòrÂ 6 ç2×6W&–c½föçB×6—¦S£ g ƒ½6öÆ÷#¢ #000000;ÐföçB×vV–v‡C¢ s ½Ðh6 {ÐÖ &v–ã¢ , ½ FF–æs¢ ½föçBÖf Ö–Ç“¢ 'Roboto', sans-serif;ÐföçB×6—¦S£ G ƒ½6öÆ÷#¢ 6ffc½föçB×vV–v‡C¢ C ½FW‡BÐ transform: uppercase;ØÐr {Ð FF–æs¢ ½Ö &v–ã£ , ½F—7 Æ “¦–æÆ–æRÖ&Æö6³½ width:135px;Ð†V–v‡C£ ƒ½& 6¶w&÷VæC¢33#ƒc&c½&÷&FW#¢ ½Ðr.special {Ð FF–æs¢ ½ margin: 20px 0 0 0;Ð&÷&FW#¢ ½†V–v‡C¢ 3G ƒ½& 6¶w&÷VæC¢ W&Â,ââö–Örö‡"Ð spec.html) no-repeat center center;ØÐmedium-txt {Ð FF–æs¢ , S½föçB×6—¦S¢ 24px;ÐÆ–æRÖ†V–v‡C¢ 3g ƒ½FW‡BÖ Æ–vã¢ 6VçFW#½föçB×vV–v‡C¢ 3 ½föçB×7G–ÆS¢ —F Æ–3½ color: #333333;ØÐcolor {Ð6öÆ÷#¢ 3&V63s ½Ðcontainer {ÐÖ ,×v–GFƒ¢ s ƒ½Ö &v–ã¢ 0 auto;Ðv–GFƒ¢ S½Ð {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½föçB×6—¦S¢ g ƒ½ font-weight: 400;ÐÆ–æRÖ†V–v‡C£3 ƒ½6öÆ÷#¢ 3cccccc½Ö &v–âÖ&÷GFöÓ£3 ƒ½ØØ* animation styles */Ðanimated {Ðf—6–&–Æ—G“¢ †–FFVã½Ðvisible {Ðf—6–&–Æ—G“¢ visible;ØØ* Button Styles */Ðbutton-large, .button-large:focus, .button-large:hover {Ð FF–æs¢ w , #W ƒ½Ö &v–ã¢ #W , # , ½föçBÖf Ö–Ç“¢ u&ö&÷FòrÂ sans-serif;ÐföçB×6—¦S¢ #G ƒ½6öÆ÷#¢ 6fffffc½föçB×vV–v‡C¢ s ½& 6¶w&÷VæC¢ #2ecc71; /* green */ÐF—7 Æ “¢ –æÆ–æR×F &ÆS½×vV&¶—BÖ&÷&FW"×& F—W3¢ W ƒ½ÖÖ÷¢Ð border-radius: 5px;Ð

'Ö×2Ö&÷&FW"×& F—W3¢ W ƒ½&÷&FW"×& F—W3¢ W ƒ½FW‡BÖFV6÷& F–öã¢
none;ÐÐ* Lists */Ðli {ÐÆ—7B×7G–ÆS¢ æöæS½Ðl, ol {ÐÖ &v–ã¢ ½ FF–æs¢ ½Æ—7BÐ
style: none;ÐÐicon-list {Ð FF–æs¢ W ƒ½Ö &v–ã¢ ½Æ—7B×7G–ÆS¢ æöæS½Ð
.icon-list li {Ð FF–æs¢ , ½Ö &v–ã¢ ½Ðicon-list i {Ð FF–ær×&–v‡C¢ ƒ½
color: #2ecc71;ÐföçB×6—¦S¢ ‡ ƒ½Ð* Inner Page Main Content Area */Ðinner-main-
cont-area {Ð FF–æs¢ ƒ , ½Ö &v–ã¢ ½& 6¶w&÷VæC¢ W&Â,ââö–Ör÷6·'Ð
bottom.html) no-repeat bottom center;Ð& 6¶w&÷VæB×6—¦S¢ 6÷fW#½Ð*
========== */Ð* 02. Preloader
Content Styles */Ð*
========== */Ðmask {Ð& 6¶w&÷VæBÐ
color:#fff;Ð&÷GFöÓ¢ ½†V–v‡C¢ S½ÆVgC¢ ½ ÷6—F–öã¢ f—†VC½&–v‡C¢ ½F÷ ¢ ½¢Ð
index: 100000;ÐÐloader {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â,ââö–ÖröÆö FW"æv–b"½& 6¶w&÷VæBÐ
position: center center;Ð& 6¶w&÷VæB×&W V C¢ æò×&W V C½†V–v‡C¢ # ƒ½ÆVgC¢ S S½
margin: -100px 0 0 -100px;Ð ÷6—F–öã¢ '6öÇWFS½F÷ ¢ S S½v–GFƒ¢ # ƒ½Ð*
========== */Ð* 03. Header Content
Styles */Ð*
========== */Ðheader-area {ÐÆVgC¢ ½
margin: 0;Ð padding: 35px 0;Ð position: fixed;Ð transition: all
0.5s ease 0s;Ð width: 100%;Ð z-index: 9;ÐÐheader-area.navbar-fixed-top {Ð
position: fixed;Ð FF–æs¢ # , ½& 6¶w&÷VæC¢ &v& ƒ Ã Ã Ã ãb"½×vV&¶—BÐ
transition: all 0.5s ease 0s;ÐÖÖ÷¢×G& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½Ö×2Ð
transition: all 0.5s ease 0s;ÐG& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½Ðheader-
area.navbar-fixed-top .call-today {ÐF—7 Æ "¦æöæS½Ðheader-area.navbar-fixed-
top .header-right-sec {Ð margin:5px 0 0;Ð FF–æs£7 , ½Ðheader-
area.navbar-fixed-top .header-right-sec .nav-area li a {ÐföçB×6—¦S£ G ƒ½Ð
.header-area.navbar-fixed-top .logo-sec {Ð padding: 0;ÐÐheader-area.navbar-
fixed-top .logo-sec img {Ð height: 40px;ÐG& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½Ð
.header-top {ÐÖ &v–ã¢ ½ FF–æs¢ #W , ½& 6¶w&÷VæBÖ6öÆ÷#¢ &v& ƒ#SRÂ #SRÂ #S2Â
0.4);Ð6öÆ÷#¢ &v& ƒ#SRÂ #SRÂ #S2Â ãB"½Ðlogo-sec {ÐÖ &v–ã¢ ½ FF–æs¢ ½fÆö C¢
left;ÐÐlogo-sec img {ÐG& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½Ðheader-right-sec {ÐÖ &v–ã¢
0;Ð FF–æs£# , ½fÆö C¢ &–v‡C½G& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½Ðnav-area {Ð
margin: 0;Ð FF–æs¢ ½Ðnav-area ul {ÐÆ—7B×7G–ÆS¢ æöæS½Ö &v–ã¢ ½ FF–æs¢ ½Ð
.nav-area li {ÐFW‡BÖFV6÷& F–öã¢ æöæS½F—7 Æ "¢ –æÆ–æR×F &ÆS½ FF–æs¢ # ƒ½
}Ðnav-area li.active, .nav-area li:hover a,.nav-area li.active a {Ð6öÆ÷#¢
#2ecc71;ÐFW‡BÖFV6÷& F–öã§VæFW&Æ–æS½Ðnav-area li a, .sidebar-nav li a {ÐföçBÐ
family: 'Open Sans', sans-serif;ÐFW‡BÖFV6÷& F–öã¢ æöæS½6öÆ÷#¢ 6ffc½FW‡BÐ
transform: uppercase;ÐföçB×6—¦S¢ G ƒ½F—7 Æ "¢ &Æö6³½föçB×vV–v‡C¢ C ½FW‡BÐ
decoration: none !important;ÐÆWGFW"×7 6–æs¢ æ÷&Ö Ã½Ð**********drop
Down**********/Ðnav-area li:hover .sub-menu {Ð display: block;ÐÐnav-
area li .sub-menu li {Ð display: block;Ð margin: 0;Ð padding: 0;Ð
text-align: center;ÐÐnav-area li .sub-menu li:hover a ,.nav-area li .sub-menu
li.active {Ð& 6¶w&÷VæC¢3#v Sc ½ transition: all 0.3s ease-in 0s;ÐFW‡BÐ
decoration:none;ÐÐnav-area li .sub-menu li a {Ð color:#fff;Ð background:
hsl(280, 5%, 11%) none repeat scroll 0 0;Ð border: 0;Ð font-size: 14px;Ð
font-weight: 400;Ð margin: 0;Ð padding: 5px 40px 5px 20px;Ð text-
align: left;Ð text-decoration: none;Ð text-transform: capitalize;Ð
white-space: nowrap;ÐFW‡BÖFV6÷& F–öã¢ æöæR –× ÷'F çC½Ðnav-area li .sub-menu {Ð
display: none;Ð list-style: none;Ð margin: 0;Ð padding: 0;Ð
position: absolute;Ð&÷&FW"Ö&÷GFöÓ£' , 6öÆ–B 3#v Sc ½Ð*
========== */Ð* 04. Banner Content
Styles */Ð*
========== */Ðbanner-sec {Ðv–GFƒ¢
100%;Ð& 6¶w&÷VæC¢3 3 C½Ðbg-banner-full {Ð& 6¶w&÷VæB×6—¦S¦6÷fW#½Ðslider_one {Ð
background:url(../img/banner-img1.jpg) no-repeat fixed;Ð& 6¶w&÷VæB×6—¦S¦6÷fW#½Ð
.slider_two {Ð& 6¶w&÷VæC§W&Â,ââö–Ör& ææW"Ö–Ös"æ§ r' æò×&W V B f—†VC½
background-size:cover;ÐÐslider_three {Ð& 6¶w&÷VæC§W&Â,ââö–Ör& ææW"Ö–Ös2æ§ r'
no-repeat fixed;Ð& 6¶w&÷VæB×6—¦S¦6÷fW#½Ðbalck-solid {Ð margin: 0;Ð
padding: 0;Ð width: 100%;Ð& 6¶w&÷VæC¢ &v& ƒ Â Â Â ãb"½Ðbanner-
sec .flexslider img {Ð width: 100%;ÐÐbanner-sec .flexslider li {Ð
position:relative;Ð

}Ðbanner-sec .flexslider li h1 span {ÐÖ &v–ã¢ ½6öÆ÷#¢
#2ecc71;ÐföçB×vV–v‡C£C ½Æ–æRÖ†V–v‡C£CW ƒ½FW‡B×G& ç6f÷&Ó¢ 6 –F Æ–¦S½
display:block;Ð   font-size: 110px;Ð   line-height: 55px;Ð   font-family:
'Cookie', cursive;ÐÐbanner-sec .flexslider li h1 {ÐföçB×vV–v‡C¢ ƒ ½   font-
size:72px;ÐFW‡B×G& ç6f÷&Ó¢ W W&6 6S½Ö &v–ã¢ ½Ðbanner-sec .flexslider li h5 {Ð
color:#fff;ÐföçB×6–¦S¢ ‡ ƒ½   font-weight: 400;Ð   letter-spacing:4px;Ð
text-transform: uppercase;Ð   word-spacing:25px;ÐÐhr-outtr-line i {Ð   font-
size: 18px;Ð   padding: 10px;Ð   vertical-align: super;Ð6öÆ÷#¢3&V63s ½Ðbanner-
sec .flex-active-slide li .banner-mid-text {Ð ÷6–F–öã¦ '6öÇWFS½Ðbanner-mid-
text {ÐÖ &v–ã¢   WFó½   text-align: center;Ð   width: 100%;Ð   FF–æs¢ 3S ,
300px;ÐÐpara-width {ÐÖ &v–ã¢   WFó½v–GFƒ¢ c S½Ð*****************flex-
slider*************************/Ðflexslider {Ð ÷6–F–öã¢ &VÆ F–fS½Ðflex-
control-paging li a.flex-active {Ð& 6¶w&÷VæC§&v& ƒCbÂ # BÂ   2Ã ã,“½Ðflex-
control-paging li a {Ð& 6¶w&÷VæC§&v& ƒCbÂ # BÂ   2Ã ã2“½&÷&FW"×& F–W3¢ # ƒ½
cursor: pointer;ÐF–7 Æ “¢ &Æö6³½†V–v‡C£3 ƒ½FW‡BÖ–æFVçC¢ Ó"""– ƒ½v–GFƒ£3 ƒ½Ð
.flex-control-nav li {ÐF–7 Æ “¢ –æÆ–æRÖ&Æö6³½Ö &v–ã¢   W ƒ½Ðflex-direction-
nav a {Ð6öÆ÷#¢ ‡6Æ ƒ Â RÂ RÂ ã,“½7W'6÷#¢ ö–çFW#½F–7 Æ “¢ &Æö6³½†V–v‡C¢
50px;ÐÖ &v–ã¢ ½÷ 6–G“¢ ½÷fW&fÆ÷s¢ †–FFVã½ ÷6–F–öã¢ '6öÇWFS½FW‡BÐ
decoration: none;ÐFW‡B×6† F÷s¢   ,   ,   ‡6Æ ƒ Â RÂ   RÂ ã2“½F÷ £#   ƒ½
transition: all 0.3s ease-in-out 0s;Ðv–GFƒ¢ S ƒ½¢Ö–æFWƒ¢   ½Ðflex-direction-
nav a::before {Ð& 6¶w&÷VæC¢ ‡6Æ ƒ Â RÂ RÂ “½& 6¶w&÷VæB×6–¦S¢ 6÷fW#½6öçFVçC¢
"";ÐF–7 Æ “¢ –æÆ–æRÖ&Æö6³½†V–v‡C¢ S ƒ½v–GFƒ¢ S ƒ½Ðflex-direction-nav a.flex-
next::before {Ð& 6¶w&÷VæC¢ ‡6Æ ƒ Â RÂ RÂ “½& 6¶w&÷VæB×6–¦S¢ 6÷fW#½6öçFVçC¢
"";ÐF–7 Æ “¢ –æÆ–æRÖ&Æö6³½†V–v‡C¢ S ƒ½v–GFƒ¢ S ƒ½Ðflex-direction-nav .flex-
next {Ð&–v‡C£ ½FW‡BÖ Æ–vã¢ &–v‡C½Ðflex-direction-nav .flex-prev {Ð   left:0;ÐÐ
#banner-slider .flex-control-paging {Ð   bottom:60px;Ð   margin: 0 auto;Ð
position: absolute;Ð   text-align: center;Ð   width: 100%;Ð   z-index: 5;ÐÐ
.banner-mid-text .hr-outtr-line {Ð   margin: 0;ÐÐbanner-mid-text .hr-outtr-
line hr {Ð   width:235px;ÐÐ*
== */Ð* 05. Our Story
Content Styles   */Ð*
== */Ðstory-area {Ð FF–æs¢
100px 0;Ð   text-align: center;Ð& 6¶w&÷VæC¢ 6ffc½Ðstory-left img {Ð   width:
100%;ÐÖ ,×v–GFƒ¢ c#W ƒ½Ðstory-our-text {Ð FF–ær×F÷ ¢ #W ƒ½Ðhr-outtr-line {Ð
    margin-bottom: 30px;ÐÐstory-our-text > h2 {Ð   margin: 0;ÐÐstory-our-text
> a {Ð&÷&FW#£' , 6öÆ–B 3&V63s ½ FF–æs¢ W ,   ƒ½   font-size:16px;Ð   text-
transform: uppercase;Ð6öÆ÷#¢3&V63s ½föçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½Ð*
== */Ð* 06. Parallax-01
Content Styles   */Ð*
== */Ðbalck-solid-paralax {Ð
    margin: 0;Ð   padding: 0;Ð   width: 100%;Ð& 6¶w&÷VæBÖ6öÆ÷#¢ &v& ƒ Â Â Â
0.7);Ð& 6¶w&÷VæC¢ &v& ƒ Â Â Â ãr“½6öÆ÷#¢ &v& ƒ Â Â Â ãr“½
position:absolute;ÐF÷ £ ½†V–v‡C£   S½Ðparallax-action {Ð FF–æs£#3W ,   #3 ƒ½
text-align: center;Ð& 6¶w&÷VæC§W&Â,ãâö–Ör÷ & Æ ,Ö–Öræ§ r’ æò×&W V C½
background-size:cover;Ð ÷6–F–öã§&VÆ F–fS½& 6¶w&÷VæBÖ GF 6†ÖVçC¦f–†VC½Ð
.parallax-content-sec {Ð   position: relative;Ð   z-index: 8;ÐÐparallax-
content-sec h1 {ÐÆWGFW"×7 6–æs¢ w ƒ½   line-height: 70px;Ð   margin-bottom:
0;ÐÐparallax-content-sec > p {ÐföçB×6–¦S¢ g ƒ½Æ–æRÖ†V–v‡C¢ #‡ ƒ½6öÆ÷#¢
#333333;ÐÐ* == */Ð* 06.
Parallax-02 Content Styles   */Ð*
== */Ðparallax-action-two {Ð
padding:235px 0 230px;ÐFW‡BÖ Æ–vã¢ 6VçFW#½& 6¶w&÷VæC§W&Â,ãâö–Ör÷ & Æ ,Ð
img_02.jpg) no-repeat;Ð& 6¶w&÷VæB×6–¦S¦6÷fW#½ ÷6–F–öã§&VÆ F–fS½& 6¶w&÷VæBÐ
attachment:fixed;ÐÐ* == */Ð
* 07. community Content Styles   */Ð*
== */Ðmenu-area {Ð
background:#fff;Ð FF–æs£ CW ,   #W ƒ½FW‡BÖ Æ–vã¦6VçFW#½Ðmenu-content-mid >
p {Ð   padding:0 9%;ÐÐmenu-items-box {ÐFW‡BÖFV6÷& F–öã¦æöæR –× ÷'F çC½
padding:45px 0;ÐÐmenu-items-box a {ÐFW‡BÖFV6÷& F–öã¦æöæR –× ÷'F çC½÷fW&fÆ÷s¢
hidden;Ð

–ÆWGFW"×7 6–æs¦æ÷&Ö Ã½Ðmenu-items-box strong {Ð6öÆ÷#¢ ‡6Âƒ Â RÂ R“½
    font-family: "Roboto",sans-serif;Ð   font-size: 24px;Ð   font-weight: 400;Ð
    margin: 0 0 10px;Ð   padding: 0;Ð   text-transform: capitalize;}Ðmenu-
items {Ð   margin-bottom:30px;ÞÐimg-hme {Ð   display: block;ÞÐoverlay-sec {Ð
display:table-cell;Ð7W'6÷#¢ ö–çFW#½   height:100%;Ð   background:rgba(46,
204, 113, 0.8);Ð   transition: all 0.3s ease 0s;Ð÷ 6—G“£ ½   position:
absolute;Ð   top: 0;Ð   width:100%;ÐÆVgC£ ½Ðmenu-items-box a:hover .overlay-
sec {Ð   opacity: 1;ÞÐmenu-items figure {Ð   position: relative;ÞÐoverlay-
outr {Ð   position: relative;Ð   margin-bottom: 15px;ÞÐ*
== */Ð* 08. Speak with Us
NOW Styles   */Ð*
== */Ðsubscribe-area {Ð
padding: 65px 0;Ð& 6¶w&÷VæC¢ 3&V63s ½ ÷6—F–öã¢ &VÆ F—fS½Ðsubscribe-right {Ð
float: right;ÞÐsubscribe-left img {Ð   position: absolute;Ð   top: -132px;ÞÐ
.subscribe-newsletr h4 {Ð   color:#fff;Ð   display: inline-block;ÐÖ &v–ã£ ½
vertical-align: text-bottom;ÞÐsubscribe-newsletr input {Ð   background:#fff;Ð
    border: none;Ð   border-radius: 5px;Ð   color:#121013;Ð   font-size: 14px;Ð
    height: 50px;Ð   margin: 0 10px 0 30px;Ð   padding: 15px 20px;Ð   width:
340px;ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½fW'F–6 ÂÖ Æ–vã¢ 7W W#½Ðsubscribe-
newsletr button {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½   background:#000;Ð
border: none;Ð   border-radius: 5px;Ð   color:#fff;Ð   font-size: 18px;Ð
height: 50px;Ð   padding: 14px 20px;Ð   width:155px;Ð   text-transform:
uppercase;Ð   vertical-align: top;ÞÐ*
== */Ð* 09. Footer Black
Styles   */Ð*
== */Ðfooter-black {Ð
padding:90px 0;Ð& 6¶w&÷VæC¢3 #   3½Ðthree-itm-btm p {ÐföçBÖf Ö–Ç“¢ t÷ Vâ
Sans', sans-serif;Ð   color: hsl(0, 0%, 60%);Ð   display: inline-block;Ð
font-size: 14px;Ð   line-height: 30px;Ð   text-align: left;ÐÖ &v–â×&–v‡C£3W ƒ½
margin-bottom: 10px;ÞÐthree-itm-btm span {Ð   display: block;ÞÐftr-black-left
h6 {Ð   font-size: 14px;Ð   font-weight: 900;Ð   letter-spacing: 2px;Ð
margin: 0;ÞÐftr-black-left hr {Ð   width:150px;ÞÐftr-black-rgt .three-itm-btm
> p {Ð   margin-right: 20px;ÐÖ &v–âÖ&÷GFöÓ¢   ƒ½ÐftrÐ-black-rgt h6 {Ð   font-
size: 14px;Ð   font-weight: 900;Ð   letter-spacing: 2px;Ð   margin: 0;ÞÐ*
== */Ð* 10. Footer Main
Styles   */Ð*
== */Ðfooter {Ð   text-
align: center;ÞÐfooter-area {Ð FF–æs£s   , ½& 6¶w&÷VæC¢3 3   C½Ðfooter-area
p {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½föçB×6—¦S£ 7 ƒ½6öÆ÷#¢3cccccc½Ö &v–âÐ
bottom:0;ÞÐfooter-area a {ÐföçB×6—¦S¢ 7 ƒ½   letter-spacing: normal;Ð   text-
decoration: none !important;Ð   text-transform: capitalize;Ð6öÆ÷#¢3cccccc½Ð
.social-icons {Ð   margin:0 0 30px 0;Ð   padding: 0;ÞÐsocial-icons ul {ÐÆ—7BÐ
style: none;Ð   margin: 0;Ð   padding: 0 0 0;ÞÐsocial-icons ul li {Ð
display: inline-table;Ð   margin: 0;Ð   padding:0 5px;ÞÐsocial-icons ul li a
{Ð   background:#333134;Ð   border-radius: 50%;Ð   color:#1c1a1d;Ð   display:
block;Ð   font-size:24px;Ð   height:50px;Ð   margin: 0;Ð   padding:12px 0 0 0;Ð
    text-align: center;Ð   text-decoration: none;Ð   width:50px;ÞÐsocial-
icons ul li a:hover {Ð   background:#777677;Ð   color: #1c1a1d;Ð   text-
decoration: none;ÞÐ*****************slidebar*********************/Ðtogg-navi {Ð
    display: none;ÞÐfirst-field.error, .second-field.error, .third-
field.error, .forth-field.error {Ð   border-bottom: 1px solid hsl(0, 100%,
50%);ÞÐ***
****************************/Ð*   Contact internal
page Styles   */Ð***
***/Ð*
== */Ð*   11.
Contact banner Styles   */Ð*
== */Ðinternal-banner {Ð
background-attachment: fixed;Ð   text-align: center;ÞÐinternal-header {Ð
padding: 225px 0 165px;Ð

}Ðinternal-header h2 {Ð color:#ffffff;Ð font-size: 72px;Ð line-height: 65px;Ð margin-bottom: 0;ÞÐinternal-header .hr-outtr-line hr {Ð width: 155px;ÞÐcontact-area {Þ FF–æs£ # , # W , ½FW‡BÐ align:center;ÞÐcontact-middle-area {Ð margin-bottom:70px;ÞÐcontact-middle-area > p {Ð line-height: 30px;Ð padding:0 10%;ÞföçB×6–¦S£ g ƒ½Ð* ========== */Ð* 12. Contact-Map & Form Content Styles */Ð* ========== */Þmap {Þ†V–v‡C¢ 3s ƒ½ width: 100%;ÞÐquick-contact-box-left {Ð float: left;ÞÐquick-contact-box-right {Ð background:#eeeeee;Ð display: block;Ð float: right;Ð padding: 10px;Ð width: 50%;ÞÐcontact-form-details li {Ð display: list-item;Ð margin-bottom: 20px;ÞÐcontact-form-details li input {ÞföçBÖf Ö–Ç“¢ 'Open Sans', sans-serif;Þ&÷&FW#¦æöæS½& 6¶w&÷VæC¢6VVVVVS½†V–v‡C£c ƒ½ FF–æs£ 25px;ÞföçB×6–¦S£ G ƒ½v–GFƒ£SSW ƒ½ color: #666666;Ð font-size: 16px;ÞÐ .contact-form-details li:nth-child(5n+3), .contact-form-details li:nth-child(5n+4) {Ð margin-right: 0;ÞÐcontact-form-details li textarea {ÞföçBÐ family: 'Open Sans', sans-serif;Þ&÷&FW#¦æöæS½ FF–ær×F÷ ¢ #W ƒ½ background:#eeeeee;Þ†V–v‡C£ S ƒ½ FF–ærÖÆVgC£#W ƒ½ color: #666666;Ð font-size: 16px;Þv–GFƒ£ S½Ðutton.submit {Þ& 6¶w&÷VæC¢3&V63s ½ color: hsl(0, 0%, 100%);Ð display: block;ÞföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½ font-size: 18px;Ð font-weight:400;Ð height:60px;Ð margin: 0 auto;Ð padding-left:15px;Ð padding-top: 3px;Ð text-align: center;Ð vertical-align: middle;Ð width:100%;Þ&÷&FW#¦æöæS½ÆWGFW"×7 6–æs£' ƒ½FW‡B×G& ç6f÷&Ó§W W&6 6S½ }Ðutton.submit:hover {Þ& 6¶w&÷VæC¢ 3#v Sc ½G& ç6—F–öã¢ ÆÂ ãW2 V 6R 3½ color:#fff;ÞÐ**********error-style**********/Ðquick-contact-box-left div {Ð color:#ff0000;Ð font-family: "Open Sans",sans-serif;Ð font-size: 14px;ÞÐ* ========== */Ð * 13. Contact-adresss Content Styles */Ð* ========== */Ðcontact-list {Þ margin:105px 0 0 0;Þ FF–æs£ ½Ðcontact-list ul {ÞÆ—7B×7G–ÆS¦æöæS½Ðcontact-list li {ÞFW‡BÖ Æ–vã¦6VçFW#½Ðcontact-list li i {ÞföçB×6–¦S£C‡ ƒ½6öÆ÷#¢3&V63s ½ margin-bottom:16px;ÞÐcontact-list li h5 {ÞföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½ font-size:18px;Þ6öÆ÷#¢3333333½FW‡B×G& ç6f÷&Ó¦6 —F Æ–¦S½föçB×vV–v‡C£C ½Ö &v–âÐ bottom:22px;ÞÖ &v–âÖ&÷GFöÓ¢ # ƒ½Ðcontact-list li h6 {ÞÖ &v–âÖ&÷GFöÓ£ W ƒ½föçBÐ size:14px;ÞföçB×vV–v‡C£3 ½föçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½FW‡BÐ transform:capitalize;Þ6öÆ÷#¢3333333½Ðcontact-list li a {ÞföçB×vV–v‡C£c ½ color:#2ecc71;ÞföçB×6–¦S£ G ƒ½föçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½ display:block;ÞÆWGFW"×7 6–æs¦æ÷&Ö Ã½FW‡B×G& ç6f÷&Ó¦6 —F Æ–¦S½FW‡BÐ decoration:none !important;ÞÐ**********/Ð * About internal page Styles */Ð**********/Ð* ========== */Ð* 14. About internal page Styles */Ð* ========== */Ðabout-story-area {Þ padding:135px 0 100px 0;ÞFW‡BÖ Æ–vã¦6VçFW#½Ðabut-stry-mid {ÞÖ &v–â×F÷ ¢ SW ƒ½ text-align: left;ÞÐfeatures-more-area {Þ FF–ærÖ&÷GFöÓ¢ cW ƒ½FW‡BÖ Æ–vã¢ center;ÞÐfeatures-more-mid {Þ FF–ær×F÷ ¢ s ƒ½Ðfeatures-more-area p {Þ padding: 0 9%;ÞÐfture-mre-listitem p {ÞföçB×6–¦S¢ G ƒ½Æ–æRÖ†V–v‡C¢ #G ƒ½ margin: 0;ÞÐfture-mre-listitem {ÞÖ &v–âÖ&÷GFöÓ£“ ƒ½Ðfture-mre-listitem i {Þ margin-bottom:25px;ÞföçB×6–¦S£c ƒ½6öÆ÷#¢3&V63s ½Ðfture-mre-listitem h4 {Þ margin-bottom:10px;ÞföçB×6–¦S£# ƒ½6öÆ÷#¢3&V63s ½FW‡B×G& ç6f÷&Ó¦æöæS½föçBÐ weight:800;ÞÐabut-story-left img {Þv–GFƒ¢ S½Ð**********/Ð * Event internal page Styles */Ð**********/Ð* ========== */Ð* 15. Event internal page Styles */Ð

/*
========== */Ðevent-page-all-sec {Ð
margin-top: 70px;ÐÐevent-page-all-sec .blog-box-rgt h5 {Ð6öÆ÷#¢ ‡6Âƒ3rÂ CbRÂ
57%);ÐföçBÖf Ö–Ç“¢ %&ö&÷Fò"Ç6 ç2×6W&–c½föçB×6—¦S¢ ‡ ƒ½föçB×vV–v‡C¢ C ½Æ–æRÐ
height: 28px;ÐÖ &v–âÖ&÷GFöÓ¢ W ƒ½Ðevent-page-all-sec .blog-box-rgt p {Ð6öÆ÷#¢
hsl(0, 0%, 40%);ÐföçB×6—¦S¢ g ƒ½Æ–æRÖ†V–v‡C¢ #G ƒ½Ö &v–âÖ&÷GFöÓ¢ W ƒ½
padding: 0;ÐÐevent-page-all-sec .blog-box-rgt span {ÐföçB×6—¦S¢ w ƒ½föçBÐ
family: "Roboto",sans-serif;ÐÐevent-page-all-sec .blog-box-rgt {Ð FF–æs¢ SW ,
50px;ÐÐevent-page-all-sec .blog-box-lft .yellow-solid {Ð FF–ær×F÷ ¢ 3 S½Ð
.event-page-all-sec .blog-left-sec:nth-child(2n+2) .blog-box-lft {ÐfÆö C¢
right!important;ÐÐevent-page-all-sec .blog-left-sec {ÐÖ &v–âÖ&÷GFöÓ£ ½Ðevent-
page-outr-sec {Ð FF–æs¢ , ## ƒ½FW‡BÖ Æ–vã¢ 6VçFW#½Ðevent-page-outr-
sec p {Ð FF–æs¢ S½Ðevent-page-all-sec .blog-box-rgt a {ÐföçB×6—¦S¢ g ƒ½Ð
****
**********/Ð*
Our Menu internal page
Styles */Ð**********
**********/Ð*
========== */Ð* 16. Our Menu
internal page Styles */Ð*
========== */Ðour-top-sec {Ð
padding:125px 0 30px 0;ÐÐour-menu-bg {Ð FF–ærÖ&÷GFöÓ¢ W ƒ½& 6¶w&÷VæC§W&Â,ââð
img/01_Menu.jpg) no-repeat;Ð& 6¶w&÷VæB×6—¦S£ S½Ðour-menu-details {ÐÖ &v–âÐ
bottom: 60px;ÐÐour-menu-details h4 {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½FW‡BÐ
align: center;ÐföçB×6—¦S£3 ƒ½öÆ÷#¢3“”“”“”½Ö &v–âÖ&÷GFöÓ£c ƒ½Ðor-lft-menu
h5 {ÐföçBÖf Ö–Ç“¢ t÷ Vâ 6 ç2rÂ 6 ç2×6W&–c½F—7 Æ “¢ –æÆ–æRÖ&Æö6³½föçB×6—¦S¢
20px;ÐföçB×vV–v‡C¢ C ½ FF–ær×&–v‡C£W ƒ½fW'F–6 ÂÖ Æ–vã¢ 7W W#½v–GFƒ£ S½*•
background:url(../img/dashed.png) repeat-x;*/Ð& 6¶w&÷VæB× ÷6—F–öã¦6VçFW#½
margin-bottom: 10px;Ð&÷&FW"Ö&÷GFöÓ¢ , F 6†VB 3&V63s ½Ðor-lft-menu span {Ð
padding-right: 10px;ÐÐour-menu-one {ÐF—7 Æ “¢ –æÆ–æRÖ&Æö6³½ FF–ær×&–v‡C¢ SW ƒ½
width: 50%;ÐÖ &v–âÖ&÷GFöÓ¢ 3 ƒ½Ðour-menu-one:nth-last-child(2n+2) {ÐfÆö C¢
right;Ð FF–ærÖÆVgC¢ SW ƒ½ FF–ær×&–v‡C¢ ½Ðor-rgt-menu h1 {Ð& 6¶w&÷VæC¢
#2ecc71;ÐföçB×6—¦S¢ ' ƒ½föçB×vV–v‡C¢ C ½6öÆ÷#¢ 6fffffc½föçBÖf Ö–Ç“¢ t÷ Vâ
Sans', sans-serif;Ð FF–æs¢ W ƒ½&÷&FW"×& F—W3¢ 7 ƒ½FW‡B×G& ç6f÷&Ó¢ 6 —F Æ—¦S½
float: left;ÐÖ &v–ã¢ , G , , ƒ½v–GFƒ¢ ƒ½Ðor-rgt-menu h2{Ð& 6¶w&÷VæC¢
#2ecc71;ÐföçB×6—¦S¢ g ƒ½föçB×vV–v‡C¢ C ½6öÆ÷#¢ 6fffffc½föçBÖf Ö–Ç“¢ t÷ Vâ
Sans', sans-serif;Ð FF–æs¢ 7 , ƒ½&÷&FW"×& F—W3¢ 7 ƒ½FW‡B×G& ç6f÷&Ó¢
capitalize;Ðv–GFƒ¢ bS½FW‡BÖ Æ–vã¢ 6VçFW#½fÆö C¢ ÆVgC½Ðor-lft-menu {ÐfÆö C¢
left;ÐÐor-rgt-menu span {ÐföçB×6—¦S¢ 3g ƒ½Ðor-rgt-menu {ÐfÆö C¢ &–v‡C½Ðor-lft-
menu p {ÐföçB×6—¦S¢ G ƒ½Æ–æRÖ†V–v‡C¢ #G ƒ½Ðparallax-action h2 {ÐÖ &v–ã¢ ½Ð
.parallax-action-two h2 {ÐÖ &v–ã¢ ½Ð* ===== Scroll to Top ==== */Ðreturn-to-
top {Ð ÷6—F–öã¢ f—†VC½&÷GFöÓ¢ # ƒ½&–v‡C¢ # ƒ½& 6¶w&÷VæC¢ &v"ƒ Â Â “½
background: rgba(0, 0, 0, 0.7);Ðv–GFƒ¢ S ƒ½†V–v‡C¢ S ƒ½F—7 Æ “¢ &Æö6³½FW‡BÐ
decoration: none;Ð×vV&¶—BÖ&÷&FW"×& F—W3¢ 3W ƒ½ÖÖ÷¢Ö&÷&FW"×& F—W3¢ 3W ƒ½&÷&FW"Ð
radius: 35px;ÐF—7 Æ “¢ æöæS½×vV&¶—B×G& ç6—F–öã¢ ÆÂ ã72 Æ–æV #½ÖÖ÷¢Ð
transition: all 0.3s ease;ÐÖ×2×G& ç6—F–öã¢ ÆÂ ã72 V 6S½Öò×G& ç6—F–öã¢ ÆÂ
0.3s ease;ÐG& ç6—F–öã¢ ÆÂ ã72 V 6S½¢Ö–æFWƒ£“”“”“”½Ðreturn-to-top i {Ð6öÆ÷#¢
hsl(0, 0%, 100%);ÐföçB×6—¦S¢ — ƒ½ÆVgC¢ g ƒ½Ö &v–ã¢ ½ ÷6—F–öã¢ &VÆ F—fS½FW‡BÐ
decoration: none;ÐF÷ ¢ W ƒ½f—6–&–Æ–G“¢ f—6–&ÆS½¢Ö–æFWƒ¢ “”“”½×vV&¶—BÐ
transition: all 0.3s ease;ÐÖÖ÷¢×G& ç6—F–öã¢ ÆÂ ã72 V 6S½Ö×2×G& ç6—F–öã¢ ÆÂ
0.3s ease;ÐÖò×G& ç6—F–öã¢ ÆÂ ã72 V 6S½G& ç6—F–öã¢ ÆÂ ã72 V 6S½Ðreturn-to-
top:hover {Ð& 6¶w&÷VæC¢ &v& ƒ Â Â Â ã’“½Ðreturn-to-top:hover i {Ð6öÆ÷#¢
#fff;ÐÐ* ========== */Ð* 17. Media
Query */Ð*
========== */Ðmedia (max-width:
1200px) { /* This media query is written for 1400PX resolution devices */Ð
.menu-items img {Ðv–GFƒ¢ S½Ðthree-itm-btm p {ÐÖ &v–â×&–v‡C¢ ' ƒ½Ðthree-
itm-btm span {ÐF—7 Æ “¢ –æÆ–æS½Ðquick-contact-box-left {Ðv–GFƒ¢ C,S½Ðcontact-
form-details li input {Ðv–GFƒ¢ S½Ðquick-contact-box-right {Ðv–GFƒ¢ C’S½Ð
.overlay-sec {Ð†V–v‡C¢ S½v–GFƒ¢ S½ÐÐ@media (max-width: 1100px) { /*
This media query is written for 1100PX resolution devices */Ð

Ðcontact-list li {ÐÖ &v–âÖ&÷GFöÓ¢ # ƒ½ Ðblog-left-sec {Ðv–GFƒ¢ S½fÆö C¦ÆVgC½Ðblog-right-sec {Ðv–GFƒ¢ S½fÆö C¦ÆVgC½Ðyellow-solid {Ð FF–ær×F÷ ¢ C S½Ð **********row**********/Ðparallax-action .row {ÐÖ &v–ã¢ ½Ðmenu-area .row {ÐÖ &v–ã¢ ½Ðchef-outr-sec .row {ÐÖ &v–ã¢ ½Ðblog-outr-sec .row {Ð margin: 0;ÐÐfooter-area .row {ÐÖ &v–ã¢ ½Ðfeatures-more-area .row {ÐÖ &v–ã¢ ½Ð .resrvation-top-area .row {ÐÖ &v–ã¢ ½Ðreservation-more-area .row {ÐÖ &v–ã¢ ½Ð .our-menu-bg .row {ÐÖ &v–ã¢ ½Ðsubscribe-right {Ðv–GFƒ¢ ƒ,S½Ðcontact-middle-area > p {Ð FF–æs¢ W ƒ½Ð**********/ÐÐÐ@media (max-width: 991px) { /* This media query is written for Ipad and tablets */ÐÐthree-itm-btm p {ÐF–7 Æ “¢ &Æö6³½Ðresrvation-top-area p {Ð FF–æs¢ ½Ðabut-story-left {ÐÖ &v–âÖ&÷GFöÓ£3 ƒ½Ðevent-page-all-sec .blog-box-lft {Ðv–GFƒ¢ S½Ð .event-page-all-sec .blog-box-rgt {Ðv–GFƒ¢ S½Ðevent-page-all-sec .blog-box-rgt {Ð FF–æs¢ SW , 3 ƒ½Ðreservation-more-area-last .resrve-sections {ÐÖ &v–âÐ bottom: 50px;ÐÐreserve-select-outr li {ÐÖ &v–âÖ&÷GFöÓ¢ # ƒ½Ðresrve-sections {Ð padding-right: 0;ÐÐÐÐ@media (max-width: 768px) { /* This media query is written for Mobile landscape and Ipad and tablets portrait */ÐÐchef-left-sec h4 {ÐföçB×6–¦S¢ 3' ƒ½Ðor-lft-menu h5{Ð& 6¶w&÷VæB× ÷6–F–öã¢ &÷GFöÓ½Ðor-rgt-menu {Ðò§v–GFƒ¢ #rS²¢ÐÐor-rgt-menu h1 {ÐföçB×6–¦S¢ G ƒ½Ðour-menu-one {Ð padding-right: 0;ÐÐor-lft-menu {Ðv–GFƒ¢ cRS½Ðour-menu-one:nth-last-child(2n+2) {Ð FF–ærÖÆVgC¢ # ƒ½Ðsubscribe-right {Ðv–GFƒ¢ “,S½Ðour-menu-bg {Ð background: none;ÐÐaddTo-cart{ÐföçB×6–¦S¢ ' , –× ÷'F çC½ÐÐ@media (max-width: 767px) { /* This media query is written for Mobile only */ÐÐ.resrve-sections {ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðheader-area.navbar-fixed-top {Ð& 6¶w&÷VæC¢3 ½Ð .header-area {Ð& 6¶w&÷VæC¢3 ½Ðstory-area.reserve {Ð FF–æs¢ 3W , ½Ðmenu-content-mid p {Ð FF–æs¢ S½Ðfeatures-more-area p {Ð FF–æs¢ ½Ðfeatures-more-area {Ð FF–ærÖ&÷GFöÓ¢ CW ƒ½Ðevent-page-outr-sec p {Ð FF–æs£ "S½Ðblog-page-outr-sec p {Ð FF–æs¢ "S½Ðlogo-sec {Ð FF–æs¢ ½Ðtogg-navi {ÐF–7 Æ “¢ block;ÐÐtogg-text-menu {Ð& 6¶w&÷VæC¦æöæS½fÆö C¢ ÆVgC½föçB×6–¦S¢ 3 ƒ½Ö &v–ã¢ auto;Ð FF–æs£ ' , ‡ , , ½FW‡BÖ Æ–vã¢ ÆVgC½v–GFƒ¢ S½6öÆ÷#¢3&V63s ½Ð .menu-main {ÐF–7 Æ “¢ æöæS½Ðnav-area ul {Ð& 6¶w&÷VæC¢ ‡6Æ ƒ Â RÂ RÂ ãB’ none repeat scroll 0 0;Ð FF–ær×F÷ £cW ƒ½ FF–ærÖ&÷GFöÓ¢ 3 ƒ½Ðnav-area li {Ð display: list-item;Ð FF–æs¢ W , ½Ðheader-area {Ð FF–æs£ W , #W ƒ½Ð **********toggle-style**********/Ðnav-area li .sub-menu {Ð display: block;ÐÐlogo-sec {Ðv–GFƒ¢ S½fÆö C¢ ÆVgC½Ö &v–ã¢ WFó½FW‡BÖ Æ–vã¢ center;ÐÐheader-right-sec {ÐfÆö C¢ æöæS½FW‡BÖ Æ–vã¢ 6VçFW#½ FF–æs£ ½Ðtogg-navi {ÐfÆö C¢ &–v‡C½ FF–ær×&–v‡C¢ W ƒ½Ðbanner-mid-text {Ð FF–æs¢ #3 , 200px;ÐÐbanner-sec .flexslider li h1 {ÐföçB×6–¦S¢ S' ƒ½Ðbanner-sec .flexslider li h3 {ÐföçB×6–¦S¢ # ƒ½Ðmenu-items-box a {Ð FF–æs¢ ½Ðmenu-items img {Ðv–GFƒ¢ S½Ðsubscribe-right {Ðv–GFƒ¢ S½Ðchef-left-sec {ÐfÆö C¢ none;Ð FF–ær×F÷ ¢ ƒ½FW‡BÖ Æ–vã¢ 6VçFW#½Ðchef-right-sec {ÐfÆö C¢ æöæS½ padding-top: 40px;ÐFW‡BÖ Æ–vã¢ 6VçFW#½v–GFƒ¢ S½Ðchef-mid-sec {Ð ÷6–F–öã¢ static;ÐÐ**********/Ðquick-contact-box-left {ÐfÆö C¢ æöæS½v–GFƒ¢ 100%;ÐÖ &v–âÖ&÷GFöÓ£C ƒ½Ðquick-contact-box-right {Ðv–GFƒ¢ S½Ðinternal-header h2 {ÐföçB×6–¦S¢ c' ƒ½Ðreservation-more-area.reservation-more-area-last {ÐÖ &v–âÖ&÷GFöÓ¢ S ƒ½Ð**********/Ðresrve-sections img {Ðv–GFƒ¢ S½Ðour-menu-one {ÐF–7 Æ “¢ &Æö6³½fÆö C¢ æöæS½Ö &v–ã¢ WFò 30px;Ðv–GFƒ£ƒ"S½Ðour-menu-one:nth-last-child(2n+2) {ÐfÆö C¢ æöæS½ FF–ærÖÆVgC¢ 0;ÐÐreservation-more-area-last {ÐÖ &v–âÖ&÷GFöÓ¢ c ƒ½Ðlogo {ÐfÆö C¢ ÆVgC½ padding-left: 15px;ÐÐtogg-navi {ÐfÆö C¢ &–v‡C½ FF–ær×&–v‡C¢ W ƒ½Ðbanner-sec .flexslider li h5 {ÐföçB×6–¦S¢ G ƒ½v÷&B×7 6–æs¢ ƒ½Ðreservation-more-area {ÐÖ &v–ã¢ ƒ ƒ½Ðtab-container .our-menu-one {ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðor-lft-menu {Ðv–GFƒ£ S½Ðor-rgt-menu {ÐfÆö C¢ æöæS½Ðtab-container .our-menu-one {Ð& 6¶w&÷VæC¢ ‡6Æ ƒ Â RÂ RÂ ’ W&Â,"ââö–ÖröF 6†VBç ær"’ &W V B×, 67&öÆÂ center bottom;Ð FF–ærÖ&÷GFöÓ£# ƒ½Ðor-lft-menu h5 {Ð& 6¶w&÷VæC¦æöæS½Ðblog-box-rgt {ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðthree-itm-btm p {ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðfooter-black {ÐFW‡BÖ Æ–vã¢ 6VçFW#½Ðinternal-banner,.banner-sec,.slider_one,.slider_two,.slider_three,.bg-banner-full,.parallax-action,.parallax-action-two,.parallax-action-three {Ð& 6¶w&÷VæBÖ GF 6†ÖVçC¢ scroll !important;Ð

–& 6¶w&÷VæB× ÷6—F–öã¢ 6VçFW" 6VçFW" –× ÷'F çC½& 6¶w&÷VæBÐ
size: cover !important;ÐFW‡BÖ Æ–vã¢ 6VçFW" –× ÷'F çC½Ð}Ð@media (max-width:
480px) { /* This media query is written for Mobile only */ÐÐbanner-
sec .flexslider li h1 span {ÐföçB×6—¦S¢ s ƒ½Ðcontact-area {Ð FF–æs¢ # ,
175px;ÐÐflex-direction-nav a {ÐF—7 Æ “¢ æöæS½Ðheader-area {Ð FF–æs£ g ,
20px;ÐÐsubscribe-left img {ÐF÷ ¢ Ó ƒ½Ð**********/Ðsubscribe-
left img {Ðv–GFƒ¢ S½Ðsubscribe-newsletr input {ÐF—7 Æ “¢ &Æö6³½Ö &v–ã¢
auto 15px;Ðv–GFƒ¢ “RS½Ðsubscribe-newsletr button {ÐF—7 Æ “¢ &Æö6³½Ö &v–ã¢
auto;ÐÐparallax-content-sec h1 {ÐföçB×6—¦S¢ 3w ƒ½Æ–æRÖ†V–v‡C¢ c ƒ½Ð3 {ÐföçBÐ
size: 70px;ÐÐbanner-mid-text .hr-outtr-line hr {Ðv–GFƒ¢ 3 S½Ðbanner-mid-text {Ð
padding: 170px 0 160px;ÐÐthree-itm-btm p {ÐÖ &v–â×&–v‡C¢ ½Ðstory-our-text >
h2 {ÐföçB×6—¦S¢ C ƒ½Ðinternal-header h2 {ÐföçB×6—¦S¢ C' ƒ½Ðfeatures-more-
area p {Ð FF–æs¢ ½Ðor-lft-menu {Ðò§v–GFƒ£ S²¢ýÖ &v–â×F÷ ¢ # ƒ½& 6¶w&÷VæC¢
#f9f0e0;Ð FF–æs¢ , W , ƒ½Ðor-rgt-menu {Ðv–GFƒ£ S½Ðor-rgt-menu h1 {Ð
font-size: 14px;Ðv–GFƒ¢ ƒ½Ö &v–â×F÷ ¢ w ƒ½Ðor-rgt-menu h2{ÐÖ &v–ã¢ w ,
7px;Ðv–GFƒ¢ ,S½Ðour-menu-one {Ðv–GFƒ¢ S½Ðbanner-sec .flexslider li h1 {Ð
font-size: 44px;ÐÐ2 span {ÐföçB×6—¦S¢ Sg ƒ½Ðevent-page-outr-sec {Ð FF–æs¢
110px 0 180px;ÐÐÐ@media (max-width: 414px) { /* This media query is written
for Mobile only */ÐÐ.reservation-more-area.reservation-more-area-last {ÐÖ &v–âÐ
bottom: 120px;ÐÐsubscribe-left img {ÐF÷ ¢ Ó“ ƒ½Ðreserve-select-outr ul li
form {Ðv–GFƒ¢ ƒBS½ Ðreserve-select-outr ul li form input {Ðv–GFƒ¢ S½ Ð
.reserve-select-outr ul li select {Ðv–GFƒ¢ ƒBS½ Ðresrvation-top-area a.fint-
table {Ðv–GFƒ¢ S½Ðor-rgt-menu span {ÐföçB×6—¦S¢ #W ƒ½Ðr-lft-menu {Ðð
width:100%;/ÐÖ &v–â×F÷ ¢ # ƒ½& 6¶w&÷VæC¢ 6c–c S ½ FF–æs¢ , W , ƒ½Ðor-
rgt-menu{Ðv–GFƒ£ S½Ðor-rgt-menu h1 {ÐföçB×6—¦S¢ G ƒ½v–GFƒ¢ ƒ½Ö &v–âÐ
top: 17px;ÐÐor-rgt-menu h2{ÐÖ &v–ã¢ w , g ƒ½v–GFƒ¢ ,S½Ðour-menu-one {Ðv–GFƒ¢
100%;ÐÐ*.or-rgt-menu h1 {ÐföçB×6—¦S¢ 3W ƒ½*/Ðor-lft-menu p {ÐÖ &v–âÖ&÷GFöÓ¢
15px;ÐÐour-menu-bg {Ð FF–ærÖ&÷GFöÓ¢ ƒW ƒ½ÐÐ@media (max-width: 380px) { /*
This media query is written for Mobile only */ÐÐr {Ðv–GFƒ¢ C S½ Ðbanner-
sec .flexslider li h1 {ÐföçB×6—¦S¢ 3W ƒ½Ðbanner-sec .flexslider li h3 {ÐföçBÐ
size: 80px;ÐÐstory-our-text > h2 {ÐföçB×6—¦S¢ 3W ƒ½Ð2 {ÐföçB×6—¦S¢ 3W ƒ½Ð
.reserve-select-outr ul li span {Ð FF–ær×&–v‡C¢ — ƒ½Ðbanner-sec .flexslider
li h5 {ÐföçB×6—¦S¢ ƒ½v÷&B×7 6–æs¢ ½Ðtogg-text-menu {Ð FF–æs¢ 7 , ‡ ,
10px;ÐÐsubscribe-left img {ÐF÷ ¢ Óƒ' ƒ½Ðreservation-more-area.reservation-
more-area-last {ÐÖ &v–âÖ&÷GFöÓ¢ “ ƒ½Ðcontact-area {Ð FF–æs¢ # , ½Ðblog-
main-details {Ð FF–æs¢ , c ƒ½ÐÐ@media (max-width: 320px) { /* This
media query is written for Mobile only */ÐÐsubscribe-left img {ÐF÷ ¢ Óc‡ ƒ½Ð
.our-menu-bg {Ð FF–ærÖ&÷GFöÓ¢ SW ƒ½ ÐÐ*========== Custom Css
========== */Ðno-pad{Ð FF–æs¢ , –× ÷'F çC½Ðbg-grey{Ð& 6¶w&÷VæC¢
rgba(46, 204, 113, 0.9);Ð padding: 9px;ÐÐmenu-list h5{Ð& 6¶w&÷VæC¢ 3 ½föçBÐ
size: 14px;Ð margin-bottom: 6px;Ð border-bottom: 1px solid #27ae60;Ð
padding:5px 14px 7px 7px;Ð color: #fff;ÐÐmenu-list ul li{Ð FF–æs¢ , w ƒ½
  color: #fff;Ð font-size: 12px;Ð border-bottom: 1px solid #2ecc71;Ð
font-weight: bold;ÐÐwhite{Ð6öÆ÷#¢ 6ffb –× ÷'F çC½Ðtheme-color{Ð6öÆ÷#¢3&V63s ½Ð
.list-pad{Ð FF–æs¢ #W , w , , w , –× ÷'F çC½ÐbigTotal{ÐföçB×6—¦S¢ # ƒ½Ð
.addTo-cart{Ð& 6¶w&÷VæC¢ 3 ½6öÆ÷#¢ 6ffc½föçB×6—¦S¢ # ƒ½&÷&FW"×& F—W3£ ,
important;ÐÐaddTo-cart:hover{Ð6öÆ÷#¢3&V63s –× ÷'F çC½Ðmodal-header h4{Ð
margin-bottom: 0px !important;ÐÐmarginBtn{ÐÖ &v–âÖ&÷GFöÓ¢ # ƒ½Ðmodal-footer{Ð
border-top:none;ÐÐsubmit-btn{ÐÖ &v–ã¢ # , ½& 6¶w&÷VæC¢ 3&V63s ½föçB×6—¦S¢
17px !important;Ð6öÆ÷#¢ 6ffc½föçB×vV–v‡C£S –× ÷'F çC½&÷&FW"×& F—W3¢ #W ƒ½
padding: 12px 20px !important;ÐFW‡B×G& ç6f÷&Ó¢ W W&6 6S½föçBÖf Ö–Ç“¢ t÷ Vâ
Sans', sans-serif;ÐÐswal2-spacer{ÐF—7 Æ “¢ æöæR –× ÷'F çC½Ðswal2-content{Ð
font-size: 16px !important;ÐÖ &v–âÖ&÷GFöÓ¢ #W , –× ÷'F çC½Ð

public\assets\frontend\menu.css

```
/* ==========================================================================
=========================ÐÔ”ä”Ô Â 5532 ÔTå]
==========================================================================================
*/Ðmain-menu {position: relative;z-index:9;width:auto; float:right;margin:
0;padding: 0;}Ðmain-menu a {-webkit-transition:all 0.3s;-moz-transition:all
0.3s;transition:all 0.3s;}Ðmain-menu ul,Ðmain-menu ul li,Ðmain-menu ul li a
{position: relative; margin: 0;padding: 0;}Ð* Submenu styles */Ðmain-menu ul
li a {display: block;padding:10px;}Ð* First level styles */™main-menu > ul >
li > a {color: #cf0a2c; padding: 2px 10px 15px  10px; font-size:16px;
margin:0; font-weight:500;}Ðsticky .main-menu > ul > li > a {color: #fff;}Ð*
Opacity mask when left open */Ðlayer {display: none; position: fixed; top: 0;
left: 0; width: 100%; min-width: 100%; z-index: 100; min-height: 100%;
background-color: #000; opacity: 0; z-index:9;}Ðlayer-is-visible {display:
block;-webkit-animation: fade-in-layer .3s;-moz-animation: fade-in-layer .3s;-
ms-animation: fade-in-layer .3s; -o-animation: fade-in-layer .3s;animation:
fade-in-layer .3s;opacity: 0.5;}Ðclose_in,#header_menu, .cmn-toggle-
switch{display:none;}Ða.dropdown-toggle.icon-search{display: inline-block;}Ð*
IE9 fix that affect the pages with parallax header (ex.single_hotel.html);
Issue: submenu disappear when move the cursor to the submenu (only if you did
not scroll the page) */Ðie9 a.show-submenu, .ie9 a.show-submenu-
mega{ background:url(../img/fix_ie_9_menu.png);}™Ð All styles for screen size
over 992pxÐ================================================== */@media only
screen and (min-width: 992px) {Ðmain-menu {width: auto;}Ðmain-menu a {white-
space: nowrap;}•main-menu ul li {display: inline-block;}Ðmain-menu ul
li.submenu:hover > a:before,Ðmain-menu ul li.submenu:hover > a:after {bottom:
-20px;opacity: 0;}™Ð Submenu */Ðmain-menu ul ul,Ðmain-menu ul .menu-wrapper
{position: absolute;display: none;z-index: 1;height: auto;left: 3px;top:
100%;margin: 0;padding: 0;background: #fff;min-width:170px;-webkit-box-
shadow: 0 6px 12px rgba(0, 0, 0, .175);box-shadow: 0 6px 12px rgba(0, 0,
0, .175);}Ð* Arrows top */Ðmain-menu ul ul:before{bottom: 100%;left:
15%;border: solid transparent;content: " ";height: 0;width: 0;position:
absolute;pointer-events: none;border-bottom-color: #fff;border-width:
7px;margin-left: -7px;}Ðmain-menu ul .menu-wrapper ul {-webkit-box-
shadow:none;-moz-box-shadow:none;box-shadow:none;border-top: none; margin:0;
padding:0;}Ðmain-menu ul .menu-wrapper ul:before{border:0;}Ðmain-menu ul
li:hover > ul,Ðmain-menu ul li:hover > .menu-wrapper {display:block;padding:
0;}Ðmain-menu ul ul li {display: block;height: auto;padding: 0;}™Ðmain-menu ul
ul li a {font-size: 13px;color: #666;border-bottom:1px solid #ededed;display:
block;}Ðmain-menu ul ul li:last-child a {border-bottom:none;}Ðmain-menu ul ul
li:hover > a {background-color:#f9f9f9;color:#ec008c; padding-left:15px;}Ð
.main-menu ul .menu-wrapper ul {position: relative;display:block;}Ðmain-menu
ul .menu-wrapper ul {margin-bottom:15px;left: 0;}Ð#search_bt
span{ display:none;}™@media only screen and (max-width: 991px) {Ð
#header_menu{text-align:center;padding:10px;position:relative;display:block;
background-color:#CF0A2C;}Ðmain-menu ul li a:hover,Ða.show-submenu:hover,Ð
a.show-submenu:focus,Ða.show-submenu-mega:hover,Ða.show-submenu-
mega:focus{color:#ec008c !important;background-color:#f9f9f9;}•main-menu ul
li  {border-top: none;border-bottom: 1px solid #ededed;color: #fff;}Ð* Menu
mobile first level */•main-menu ul li a  {padding: 15px !important;}Ðmain-
menu h3 {font-size: 12px; line-height:14px;margin: 10px 0 0 0;padding: 0 0
15px 15px;color: #333;text-transform:uppercase;}Ðmegamenu .menu-wrapper > div
{padding:0;}•main-menu li,Ðmain-menu a {display: block;color:#555 !important;}Ð
.main-menu li {position: relative;}Ðmain-menu a:hover {color:#ec008c !
important;}Ðmain-menu ul > li {padding-bottom: 0;}Ðmain-menu ul > li
i{float:right;}Ð* Menu mobile second level */•main-menu ul li.submenu ul{font-
size: 13px;border-left:1px solid #ededed;margin:0 0 15px 25px;}Ðmain-menu ul
li.submenu ul li{font-size: 13px;border:0;}Ð* Menu mobile left panel */•main-
menu {overflow: auto;left: -100%;bottom: 0;width: 45%;height: 100%;opacity:
0;position:fixed;background-color:#fff;Ð
```

-webkit-transition:–ÆVgB ã‡2Â ÷ 6—G’ 0.5s;Ðmoz-transition:–ÆVgB ã‡2Â ÷ 6—G’ ãW3½ransition:left 0.8s, opacity 0.5s; z-index:9999;Ðwebkit-box-shadow: 1px 0px 5px 0px rgba(50, 50, 50, 0.55);Ð -moz-box-shadow: 1px 0px 5px 0px rgba(50, 50, 50, 0.55);Ðox-shadow: 1px 0px 5px 0px rgba(50, 50, 50, 0.55);}Ðmain-menu.show {visibility: visible;left: 0;opacity: 1;}Ðmain-menu .show-submenu + ul,Ð a.show-submenu-mega + .menu-wrapper{display: none;visibility: hidden;}Ð a.show-submenu-mega + .menu-wrapper.show_mega,Ðmain-menu a.show-submenu + ul.show_normal {display: block;visibility: visible;}Ð/* Hamburger menu button*/Ðcmn-toggle-switch {Ð position: relative;Ð display:block;Ð overflow: visible;Ð position:absolute; Ð top:0;Ð right:15px;Ð margin: 0;Ð padding: 0;Ð width: 30px;Ð height: 30px;Ð font-size: 0;Ð text-indent: -9999px;Ð -webkit-appearance: none;Ð -moz-appearance: none;Ð appearance: none;Ð box-shadow: none;Ð border: none;Ð cursor: pointer;}ÐÐcmn-toggle-switch:focus {outline: none;}Ðcmn-toggle-switch span {display: block;position: absolute;top: 10px;left: 0;right: 0;height: 2px;background: white;}Ðcmn-toggle-switch span::before,Ðcmn-toggle-switch span::after {position: absolute;display: block;left: 0;width: 100%;height:2px;background-color: #fff; content: "";}Ð .cmn-toggle-switch span::before {top: -10px;}Ðcmn-toggle-switch span::after {bottom: -10px;}Ðcmn-toggle-switch__htx span::before,Ðcmn-toggle-switch__htx span::after { -webkit-transition-duration: 0.3s, 0.3s;transition-duration: 0.3s, 0.3s;-webkit-transition-delay: 0.3s, 0;transition-delay: 0.3s, 0;}Ðcmn-toggle-switch__htx span::before { -webkit-transition-property: top, -webkit-transform;transition-property: top, transform;}Ðcmn-toggle-switch__htx span::after {-webkit-transition-property: bottom, -webkit-transform;transition-property: bottom, transform;}Ð/* active state, i.e. menu open */Ðcmn-toggle-switch__htx.active span{background:none !important;}Ðcmn-toggle-switch__htx.active span::before {top: 0; -webkit-transform: rotate(45deg);-ms-transform: rotate(45deg);transform: rotate(45deg);}Ðcmn-toggle-switch__htx.active span::after {bottom: 0;-webkit-transform: rotate(-45deg); -ms-transform: rotate(-45deg);transform: rotate(-45deg);}Ðcmn-toggle-switch__htx.active span::before,Ðcmn-toggle-switch__htx.active span::after {-webkit-transition-delay: 0, 0.3s;transition-delay: 0, 0.3s;}ÐÐ @media only screen and (max-width: 767px) {}Ð@media only screen and (max-width: 600px) {Ðmain-menu {width: 100%;}Ð#close_in {display:block;position:absolute;right:15px;top:10px;width:20px;height:20px;}Ð #close_in i{color:#fff !important;font-size:24px;}Ð}

public\assets\frontend\style.css

```
/*ÐTheme Name: madubertheme ÐTheme URI: http://www.maduber.com/quickfood/ÐTable
of contents] Ð1. SITE STRUCTURE and TYPOGRAPHYÐ 1.1 TypographyÐ 1.2 ButtonsÐ
1.3 StructureÐ2. CONTENTÐ 2.1 Home all versionsÐ 2.2 List pageÐ 2.3 Restaurant
menuÐ 2.4  Order processÐ 2.5 Restaurant detail pageÐ 2.6 AboutÐ 2.7 ContactsÐ
3. COMMONÐ3.1 PreloaderÐ3.2 Parallax bgÐ3.4 Login/Register modalsÐ3.5 SpacingÐ3.6
MapÐ3.7 Password strengthÐ3.8 Input form styleÐ3.9 CollapseÐ3.10 TabsÐ3.11 TooltipsÐ
3.12 BlockquoteØ*==================================================================
================================*/Ø* 1.  SITE STRUCTURE and TYPOGRAPHY */Ø*====
==========================================================================================
==========*/Ø*-------- Allert for old browsers IE8 and below --------*/Ð
.chromeframe{background:#ddd;color:#000;padding: 0.2em;position: fixed; top:
0; left: 0; text-align: center; z-index:9999; width: 100%;}Ðchromeframe
a{color:#ed1c24;}Ø* 2.2 List page*/Ðmap{Ðv–GFƒ£   S²–†V–v‡C£CS  ƒ²–&÷&FW"Ð
bottom:1px solid #ddd;ÐÐfilters_col{Ð& 6¶w&÷VæBÖ6öÆ÷#¢6ffc½  FF–æs£#  ƒ½
border: 1px solid #ededed;Ð×vV&¶–BÖ&÷&FW"×& F–W3¢ 7 ƒ½ÖÖ÷¢Ö&÷&FW"×& F–W3¢ 7 ƒ½
border-radius: 3px;ÐÖ &v–âÖ&÷GFöÓ£#W ƒ½6öÆ÷#¢ &Æ 6²  –× ÷'F çC½Ðfilters_col
label{ÐföçB×vV–v‡C¦æ÷&Ö Ã½Ð#filters_col_bt {ÐF–7 Æ "¦&Æö6³½6öÆ÷#¢3CCC½föçBÐ
weight:600;ÐÐ#filters_col_bt .icon_set_1_icon-65{ÐföçB×6–¦S£#  ƒ½
position:relative;ÐF÷ £ ½Ö &v–â×&–v‡C£W ƒ½Ðfilter_type h6{Ð&÷&FW"×F÷ ¢   ,
solid #ddd;ÐÖ &v–ã£ W ,  ½  FF–æs£ W ,      ½Ðfilter_type ul{ÐÆ–7B×7G–ÆS¦æöæS½
padding:0;ÐÖ &v–ã£     W ,  ½Ðfilter_type ul li .rating{ÐföçB×6–¦S£ g ƒ½
left:-7px;Ð ÷6–F–öã§&VÆ F–fS½F÷ £7 ƒ½6öÆ÷#¢6663½Ðfilter_type ul
li .color_1, .filter_type ul li .color_2, .filter_type ul
li .color_3, .filter_type ul li .color_4, .filter_type ul
li .color_5, .filter_type ul li .color_6, .filter_type ul
li .color_7, .filter_type ul li .color_8{Ðv–GFƒ£‡ ƒ½†V–v‡C£‡ ƒ½Ö &v–ã£W , W ,
0 0;ÐfÆö C§&–v‡C½×vV&¶–BÖ&÷&FW"×& F–W3¢ S S½ÖÖ÷¢Ö&÷&FW"×& F–W3¢ S S½&÷&FW"Ð
radius: 50%;ÐÐfilter_type ul li .color_1{Ð& 6¶w&÷VæBÖ6öÆ÷#¢3vF663s½Ð
.filter_type ul li .color_2{Ð& 6¶w&÷VæBÖ6öÆ÷#¢6c#–&3 ½Ðfilter_type ul
li .color_3{Ð& 6¶w&÷VæBÖ6öÆ÷#¢3ƒC“F3ƒ½Ðfilter_type ul li .color_4{Ð& 6¶w&÷VæBÐ
color:#8dc63f;ÐÐfilter_type ul li .color_5{Ð& 6¶w&÷VæBÖ6öÆ÷#¢3ƒF3“–S½Ð
.filter_type ul li .color_6{Ð& 6¶w&÷VæBÖ6öÆ÷#¢6cS“svC½Ðfilter_type ul
li .color_7{Ð& 6¶w&÷VæBÖ6öÆ÷#¢3s&C cC½Ðstrip_list{Ð& 6¶w&÷VæBÖ6öÆ÷#¢ 6fFfFfC½
    border: 1px solid #f5f5f5;Ð   display: block;Ð   line-height: 1.3;Ð
margin-bottom: 8px;Ð   min-height: 130px;Ð   padding: 10px;Ð   position:
relative;ÐÐstrip_list.last{ÐÖ &v–âÖ&÷GFöÓ£#W ƒ½Ð.strip_list{Ð6öÆ÷#¢3SSS½Ð
a.strip_list:hover h3{Ð6öÆ÷#¢3   ½Ðdesc{Ð  FF–ærÖÆVgC£ 3W ƒ½ ÷6–F–öã§&VÆ F–fS½Ð
.desc .rating{Ð 6öÆ÷#¢ 6666663½   padding: 4px 0 ;ÐÐdesc h3{ÐÖ &v–ã£ ½
padding:0;ÐÐdesc h3 a{Ð6öÆ÷#¢3333½Ðdesc h3 a:hover{Ð6öÆ÷#¢44c  $3½Ðtype {Ð
font-style: italic;Ð   padding: 2px 0;ÐÐdesc .opening{Ð6öÆ÷#¢4333½Ðdesc ul{Ð
list-style:none;ÐÖ &v–ã£7 ,      ½  FF–æs£ ½Ðdesc ul li{ÐF–7 Æ "¦–æÆ–æRÖ&Æö6³½
margin-right:15px;ÐÐdesc ul li i.ok{Ð6öÆ÷#¢3d33½ ÷6–F–öã§&VÆ F–fS½F÷ £' ƒ½
left:5px;ÐföçB×6–¦S£ G ƒ½Ðdesc ul li i.no{Ð6öÆ÷#¢ 433 ½ ÷6–F–öã§&VÆ F–fS½
top:2px;ÐÆVgC£W ƒ½föçB×6–¦S£ G ƒ½Ðthumb_strip {Ð   background-color: #f8f8f8;Ð
    border: 1px solid #e8e8e8;Ð   height: 100px;Ð   left: 0;Ð   margin-top:
4px;Ð   overflow: hidden;Ð   padding: 0;Ð   position: absolute;Ð   text-
align: center;Ð   top: 0;Ð   width: 100px;ÐÐthumb_strip img{Ðv–GFƒ£“‡ ƒ½
height:auto;ÐÐstrip_list .go_to{ÐF–7 Æ “§F &ÆS½Ö–âÖ†V–v‡C£  ' ƒ½FW‡BÐ
align:right;Ðv–GFƒ£   S½Ðstrip_list .go_to div{ÐF–7 Æ “¢ F &ÆRÖ6VÆÃ½fW'F–6 ÂÐ
align:middle;ÐÐstrip_list .go_to div{ÐF–7 Æ “¢ F &ÆRÖ6VÆÃ½fW'F–6 ÂÐ
align:middle;ÐÐribbon_1{Ð ÷6–F–öã¦ '6öÇWFS½FW‡BÖ–æFVçC¢Ó“““– ƒ½F÷ ¢ÓW ƒ½
left:-20px;Ð& 6¶w&÷VæC§W&Â,ââö–Ör÷&–&&öå÷ ÷ VÆ "ç ær’ æò×&W V B    ½v–GFƒ£ƒ  ƒ½
height:80px;Ð¢Ö–æFWƒ£3½Ðribbon_1.ribo {Ð   left: -5px;ÐØ*#tools{*/Ðð
*background:#fff;*/Ðò¦Ö &v–âÖ&÷GFöÓ£#W ƒ²¢ýò¦†V–v‡C£3‡ ƒ²¢ýò¢×vV&¶–BÖ&÷&FW"Ð
radius: 5px;*/Ðò¢ÖÖ÷¢Ö&÷&FW"×& F–W3¢ W ƒ²¢ýò¦&÷&FW"×& F–W3¢ W ƒ²¢ýò¦&÷&FW#£  ,
solid #ededed;*/Ø*}*/Ð.bt_filters{Ð†V–v‡C£3g ƒ½v–GFƒ£3g ƒ½6öÆ÷#¢3SSS½
display:inline-block;ÐFW‡BÖ Æ–vã¦6VçFW#½Æ–æRÖ†V–v‡C£3g ƒ½fÆö C§&–v‡C½föçBÐ
size:16px;Ð&÷&FW"ÖÆVgC¢   , 6öÆ–B 6VFVFVC½Ðtools .styled-select {Ðv–GFƒ¢    S½
overflow:hidden;Ð
```

–†V–v‡C¢ 3g ƒ½& 6¶w&÷VæC¢ W&Â,ââö–Örö '&÷uöF÷vâç7fr’ æòÐ
repeat right center ;Ð&÷&FW#¦æöæS½&÷&FW"×&–v‡C¢ , 6öÆ–B 6VFVFVC½Ð* 2.3
Restaurant menu*/Ðbox_style_1{Ð& 6¶w&÷VæC¢6ffc½×vV&¶—BÖ&÷&FW"×& F—W3¢ 7 ƒ½ÖÖ÷¢Ð
border-radius: 3px;Ð&÷&FW"×& F—W3¢ 7 ƒ½ &÷&FW#¢ , 6öÆ–B 6VFVFVC½ Ö &v–âÐ
bottom:30px;ÐÐbox_style_2, #cart_box{Ð& 6¶w&÷VæC¢6ffc½&÷&FW"×& F—W3¢ 7 ƒ½
border: 1px solid #ededed;Ð Ö &v–âÖ&÷GFöÓ£#W ƒ½ &÷&FW"ÖÆVgC¢ ½ FF–æs£ ½
border-top: 0 none;Ð}ÐÐthank-u .box_style_2{Ð&÷&FW"×F÷ £ , 6öÆ–B 4DdDdDc½Ð
.box_style_2#main_menu, .box_style_2.info{Ð FF–ærÖ&÷GFöÓ£ ƒ½Ð
.box_style_2#help{ÐFW‡BÖ Æ–vã¦6VçFW#½Ðbox_style_2#help i{ÐföçB×6—¦S£S' ƒ½
display:inline-block;Ð6öÆ÷#¢3“”“½Ðbox_style_2#help a.phone{ÐföçB×6—¦S£#g ƒ½
display:block;ÐÖ &v–âÖ&÷GFöÓ£ ½6öÆ÷#¢3ƒV3“–C½Ðcart_box {Ð background-color:
#ffffff;Ð border: 1px solid #ededed;Ð margin-bottom: 25px;Ð padding:
15px;Ð transition: all 0.4s ease-in-out 0s;Ð -webkit-transition: all 0.4s
ease-in-out 0s;Ð z-index: 10;ÐÐcart_box h3 {Ð background-color: #f7f7f9;Ð
border-radius: 0;Ð color: #4e4e4e;Ð font-size: 22px;Ð font-weight:
bold;Ð height: 53px;Ð margin: -15px -15px 15px;Ð padding: 13px;ÐÐ
#cart_box h3 i {Ð font-size: 30px;Ð margin-top: -2px;ÐÐall-menu-detail {Ð
background: #ffffff none repeat scroll 0 0;Ð border-top: 1px solid
#ececf3;Ð box-shadow: 0 0 16px 0 #eeeef5;ÐÐ.remove_item{Ð6öÆ÷#¢6FFC½föçBÐ
size:14px;ÐÐ.remove_item:hover{Ð6öÆ÷#¢ 4333½Ðcart_box hr {ÐÖ &v–âÖÆVgC¢Ó W ƒ½
margin-right:-15px;Ð&÷&FW"Ö6öÆ÷#¢6VFVFVC½Ðmain_menu hr {ÐÖ &v–âÖÆVgC¢Ó#W ƒ½
margin-right:-25px;ÐÖ &v–â×F÷ £ ƒ½&÷&FW"Ö6öÆ÷#¢6VFVFVC½Ðorder_process hr {Ð
margin-left:-25px;ÐÖ &v–â×&–v‡C¢Ó#W ƒ½Ö &v–â×F÷ £ ƒ½&÷&FW"Ö6öÆ÷#¢6VFVFVC½Ð
#main_menu h3 {Ð background-position: center center;Ð background-size:
cover;Ð font-size: 24px;Ð text-transform: capitalize;Ð text-align:
center;Ð color: #f6f6f6;Ð margin: 0;Ð padding: 30px 0;Ð font: 400
30px/1.5 'Merienda One', Helvetica, sans-serif;Ð text-shadow: 3px 3px 5px
rgba(0,0,0,0.8);ÐÐul#cat_nav{ÐÆ–7B×7G–ÆS¦æöæS½Ö &v–ã£ ½ FF–æs£ ½Ðcat_nav li
a , #cat_nav li{Ð ÷6—F–öã§&VÆ F—fS½6öÆ÷#¢3SSS½Ðcat_nav li span {Ð position:
absolute;Ð right: 0;Ð top: 10px;Ð font-size:11px;Ð6öÆ÷#¢3“”“½Ðcat_nav
li a.active:after{ÐföçBÖf Ö–Ç“¢ &föçFVÆÆò#½6öçFVçC¢ %ÆSƒ–"#½ left: 15px;Ð
position: absolute;Ð font-size: 18px;Ð top: 6px;ÐÐcat_nav li:last-child{Ð
border-bottom: 0;Ð FF–ærÖ&÷GFöÓ£ ½Ðul#cat_nav li:first-child a:hover,
ul#cat_nav li:first-child a.active{Ð×vV&¶—BÖ&÷&FW"×F÷ ÖÆVgB×& F—W3¢ 7 ƒ½Ð
webkit-border-top-right-radius: 3px;ÐÖÖ÷¢Ö&÷&FW"×& F—W2×F÷ ÆVgC¢ 7 ƒ½ÖÖ÷¢Ð
border-radius-topright: 3px;Ð&÷&FW"×F÷ ÖÆVgB×& F—W3¢ 7 ƒ½&÷&FW"×F÷ ×&–v‡BÐ
radius: 3px;ÐÐul#cat_nav li:last-child a:hover, ul#cat_nav li:last-child
a.active{Ð×vV&¶—BÖ&÷&FW"Ö&÷GFöÒ×&–v‡B×& F—W3¢ 7 ƒ½×vV&¶—BÖ&÷&FW"Ö&÷GFöÒÖÆVgBÐ
radius: 3px;ÐÖÖ÷¢Ö&÷&FW"×& F—W2Ö&÷GFö×&–v‡C¢ 7 ƒ½ÖÖ÷¢Ö&÷&FW"×& F—W2Ð
bottomleft: 3px;Ð&÷&FW"Ö&÷GFöÒ×&–v‡B×& F—W3¢ 7 ƒ½&÷&FW"Ö&÷GFöÒÖÆVgB×& F—W3¢
3px;ÐÐul#cat_nav li a {Ð display: block;Ð overflow: hidden;Ð padding:
10px 30px;Ð text-overflow: ellipsis;Ð white-space: nowrap;Ð width:
180px;ÐÐtab-1 #main_menu {Ð padding-left: 4px;ÐÐul#cat_nav li a:hover,
ul#cat_nav li a.active, ul#cat_nav li a.active::after {Ð color: #cf0a2c;ÐÐ
#sub_content{Ð /*background-color: rgba(255, 255, 255, 0.2);*/Ð display:
table-cell;Ð font-size: 16px;Ð padding: 0 15%;Ð text-align: center;Ð
text-shadow: 1px 1px 0 rgb(0, 0, 0);Ð vertical-align: middle;ÐÐ
#logo_res_main{ÐF—7 Æ “§F &ÆS½Ö &v–ã£ WFó½ÐÐsub_content #thumb.logos {Ð
background-color: #fff;Ð border-radius: 50%;Ð display: table-cell;Ð
height: 150px;Ð text-align: center;Ð vertical-align: middle;Ð width:
150px;ÐÐvenus-links {Ð display: block;Ð float: left;Ð overflow: hidden;Ð
text-overflow: ellipsis;Ð white-space: nowrap;Ð width: 94%;ÐÐ
#sub_content #thumb img {Ð padding: 0;ÐÐsub_content h1 {Ð color: #fff;Ð
font-size: 42px;Ð font-weight: bold;Ð margin: 0 0 15px;Ð opacity: 0.8;Ð
font-weight:normal;Ð text-shadow:none;ÐÐhome #sub_content > p {Ð
color: #000000;Ð font-size: 20px;ÐÐhome #sub_content h1 {Ð color: #000;Ð
font-weight: lighter;Ð text-shadow: 0 0 1px rgba(0, 0, 0, 0.4);Ð font-
family: 'Raleway', sans-serif;ÐÐ#home #sub_content p {Ð text-shadow: 0 0
4px rgba(0, 0, 0, 0.4);ÐÐrating{Ð6öÆ÷#¢6ffc½ FF–ær×F÷ £ ƒ½Ðrating .voted{Ð
color: #FC0;Ð

–Ö &v–â×&–v‡C£7 ƒ½Ðl.additional_links{ÐÆ–7B×7G–ÆS¦æöæS½Ö &v–ã£ ½
padding:0;ÐÐl.additional_links li{ÐF–7 Æ “¦–æÆ–æRÖ&Æö6³½&÷&FW"ÖÆVgC¢ , 6öÆ–B
#ededed;ÐÖ &v–âÖÆVgC£7 ƒ½ FF–ærÖÆVgC£W ƒ½Ðl.additional_links li:first-child{Ð
border-left: none;Ð FF–ærÖÆVgC£ ½Ö &v–âÖÆVgC£ ½Ðtable.cart-list td h5{ÐÖ &v–âÐ
bottom:0;ÐföçB×vV–v‡C£c ½Ðtable.cart-list{ÐÖ &v–âÖ&÷GFöÓ£ ½Ðtable.cart-list
td{ÐfW'F–6 ÂÖ Æ–vã¦Ö–FFÆS½Ðtable.table_summary td {Ðborder: medium none;Ð
padding: 0ÐÐtable td.total_confirm{ÐföçB×vV–v‡C¦&öÆC½föçB×6–¦S£ ‡ ƒ½& 6¶w&÷VæBÐ
color:#333;Ð6öÆ÷#¢6ffc½Ðoptions i{ÐföçB×6–¦S£#g ƒ½Ðrow#options_2{ÐÖ &v–âÐ
bottom:-10px;ÐÖ &v–â×F÷ ¢ÓW ƒ½Ðoptions_2 label{ÐföçB×6–¦S£ ' ƒ½Ðthumb_cart{Ð
border: 1px solid #ddd;Ð overflow:hidden;Ð width:60px;Ð height:60px;Ð
margin-right:10px;Ð float:left;ÐÐthumb_cart img{Ð padding:1px;Ð width:58px;Ð
height:auto;ÐÐitem_cart{ÐF–7 Æ “¢ –æÆ–æRÖ&Æö6³½Ö &v–â×F÷ £# ƒ½Ð* 2.4 Order
process */Ðbs-wizard { width:90%;margin:auto;}Ðbs-wizard > .bs-wizard-step
{padding: 0; position: relative;}Ðbs-wizard > .bs-wizard-step .bs-wizard-
stepnum {font-size: 16px; margin-bottom: 5px;}Ðbs-wizard > .bs-wizard-
step .bs-wizard-info {color: #999; font-size: 14px;}Ðbs-wizard > .bs-wizard-
step > .bs-wizard-dot {position: absolute; width: 30px; height: 30px;
display: block; background: #fbe8aa; top: 45px; left: 50%; margin-top: -11px;
margin-left: -15px; border-radius: 50%;} Ðbs-wizard > .bs-wizard-step > .bs-
wizard-dot:after {content: ' '; width: 14px; height: 14px; background:
#CF0A2C; border-radius: 50px; position: absolute; top: 8px; left: 8px; } Ðbs-
wizard > .bs-wizard-step > .progress {position: relative; border-radius: 0px;
height: 8px; box-shadow: none; margin: 23px 0;}Ðbs-wizard > .bs-wizard-step
> .progress > .progress-bar {width:0px; box-shadow: none; background:
#fbe8aa;}Ðbs-wizard > .bs-wizard-step.complete > .progress > .progress-bar
{width:100%;}Ðbs-wizard > .bs-wizard-step.active > .progress > .progress-bar
{width:50%;}Ðbs-wizard > .bs-wizard-step:first-child.active > .progress
> .progress-bar {width:0%;}Ðbs-wizard > .bs-wizard-step:last-child.active
> .progress > .progress-bar {width: 100%;}Ðbs-wizard > .bs-wizard-
step.disabled > .bs-wizard-dot {background-color: #f5f5f5;}Ðbs-wizard > .bs-
wizard-step.disabled > .bs-wizard-dot:after {opacity: 0;}Ðbs-wizard > .bs-
wizard-step:first-child > .progress {left: 50%; width: 50%;}Ðbs-wizard > .bs-
wizard-step:last-child > .progress {width: 50%;}Ðbs-wizard > .bs-wizard-
step.disabled a.bs-wizard-dot{ pointer-events: none; }Ðrestaurant_bg
#sub_content > h1 {Ð opacity: 1;Ð text-shadow: 0 1px 8px rgba(0, 0, 0,
0.5);ÐÐconfirm{ÐFW‡BÖ Æ–vã¦6VçFW#½Ö &v–âÖ&÷GFöÓ£#W ƒ½ÐÐconfirm i{ÐföçBÐ
size:140px;Ð6öÆ÷#¢ 3ƒV3“–C½Ö &v–â×F÷ ¢ # ƒ½F–7 Æ “¦–æÆ–æRÖ&Æö6³½ÐÐ*2.5
Restaurant detail page*/Ðsummary_review {Ð background-color: #fcfcfe;Ð
border: 1px solid #e7e7e9;Ð box-shadow: 0 5px 13px -16px #000000;Ð
margin: 30px 0 40px;Ð padding: 16px;ÐÐtable_summary #options_2 label
input,#cart_box #options_2 label input[type=radio]{Ð float: left;Ð
margin: 2px 5px 0;ÐÐgeneral_rating{ÐÖ &v–ã£ # , ½föçB×vV–v‡C£c ½föçBÐ
size:16px;ÐÐgeneral_rating .rating{ÐF–7 Æ “¦–æÆ–æS½6öÆ÷#¢6FFC½föçB×6–¦S£# ƒ½Ð
#rating_summary ul{ÐÆ–7B×7G–ÆS¦æöæS½Ö &v–ã£ ½ FF–æs£ ½Ðrating_summary
ul li{ÐföçB×6–¦S£ G ƒ½Ö &v–âÖ&÷GFöÓ£W ƒ½Ðrating_summary ul li .rating{Ð
display:inline-block;ÐfÆö C§&–v‡C½ FF–æs£ ½6öÆ÷#¢6FFC½Ð
.review_strip_single:nth-child(2n) {Ð background-color: #fbfbfb;ÐÐ
.review_strip_single {Ð border-bottom: 1px solid #ededed;Ð padding: 30px
0 20px;Ð position: relative;Ð float:left;Ð width:100%;ÐÐ
.review_strip_single .rating{Ð6öÆ÷#¢6FFC½Ðreview_strip_single.last{ÐÖ &v–âÐ
bottom:0;Ð&÷&FW"Ö&÷GFöÓ£ ½Ðreview_strip_single span.rater-imgs {Ð
background-color: #f9f9f9;Ð background-position: center top;Ð background-
size: cover;Ð border: 2px solid #e9e9e9;Ð float: right;Ð height: 100px;Ð
line-height: 2;Ð margin: -5px 0;Ð text-align: center;Ð width: 100px;Ð
}Ðreview_strip_single h4 {Ð font-size: 20px;Ð text-transform: capitalize;Ð
margin: -10px 0 12px;ÐÐreview_strip_single small {Ð background-color:
#fbfbfb;Ð border: 1px solid #ececec;Ð float: right;Ð font-size: 12px;Ð
font-style: italic;Ð margin-top: -14px;Ð padding: 5px 10px;ÐÐ
.review_strip_single .rating{ÐföçB×6–¦S£ g ƒ½Ðl.opening_list{ÐÆ–7B×7G–ÆS¦æöæS½
margin:0;Ð

```
        –  FF–æs£ ½Ðl.opening_list{ÐÆ–7B×7G–ÆS¦æöæS½Ö &v–ã£#  ,      ½
padding:0;ÐÐl.opening_list li{ÐÖ &v–âÖ&÷GFöÓ£‡ ƒ½föçB×vV–v‡C£c  ½Ð
ul.opening_list li span{ÐfÆö C§&–v‡C½föçB×vV–v‡C£C  ½Ð*2.6 About*/Ðfeatures-
bg {Ð   position: relative;Ð   min-height: 400px;Ð   background: url(../img/
features-intro-01.jpg) no-repeat center center;Ð   background-size: cover;ÐÐ
.nomargin_top.about {Ð   color: #000000;ÐÐfeatures-img {Ð   width: 100%;Ð
height: 400px;Ð   text-align: center;Ð   line-height: 400px;ÐÐfeatures-
content {Ð   position: relative;Ð   padding: 11% 100px 10% 100px;Ð   height:
400px;Ð   background-color: #78cfcf;Ð6öÆ÷#¢6ffc½föçB×6–¦S£ g ƒ½Ðfeatures-
content h3{Ð  font-family: "Gochi Hand", cursive;Ð  color:#fff;Ð  font-
size:32px;Ð  line-height:34px;Ð  text-transform:uppercase;ÐÐfeature {Ð
padding:30px 30px 20px 120px;Ð ÷6–F–öã§&VÆ F–fS½& 6¶w&÷VæC¢6ffc½Ö &v–âÐ
bottom:30px;Ð6öÆ÷#¢3ccc½×vV&¶–BÖ&÷,×6† F÷s¢   ,   , W ,   , &v& ƒ Ã Ã Ã ã “½Ð
moz-box-shadow: 0px 0px 5px 0px rgba(0,0,0,0.1);Ð&÷,×6† F÷s¢   ,   , W ,   ,
rgba(0,0,0,0.1);ÐÐfeature i{ÐÖ &v–ã£ ½ ÷6–F–öã¦ '6öÇWFS²–F÷ £3  ƒ½ÆVgC£3  ƒ½
padding:0;ÐÖ &v–ã£ ½v–GFƒ£cW ƒ½†V–v‡C£cW ƒ½Æ–æRÖ†V–v‡C£c  ƒ½FW‡BÖ Æ–vã¦6VçFW#½Ð
webkit-border-radius: 50%;ÐÖÖ÷¢Ö&÷&FW"×& F–W3¢ S S½&÷&FW"×& F–W3¢ S S½
border:1px dashed #ccc;ÐföçB×6–¦S£3G ƒ½6öÆ÷#¢3fF6fcc½Ð*2.7 Contacts*/Ð
#contacts a{ÐföçB×6–¦S£ ‡ ƒ½Ð*==========================================
==========================================*/Ð* 3.  COMMON  */Ð*==============
==========================================================================
=*/Ð*3.1 Preloader*/Ðpreloader {Ð ÷6–F–öã¢ f–†VC½F÷ £ ½ÆVgC£ ½÷fW&fÆ÷s¦†–FFVã½
right:0;Ðv–GFƒ£   S½†V–v‡C£   S½&÷GFöÓ£ ½& 6¶w&÷VæC¢6ffb W&Â,rââòâäö 76WG2ö–Örð
loader-bg.jpg') no-repeat scroll 0 0 / 100% 100%; Ð¢Ö–æFWƒ£“”“”“²}Ðpreloader
> img {Ð   display: table;Ð   margin: 0 auto;Ð   position: relative;Ð   top:
35%;Ð   width: 240px;ÐÐpreloader #status{ÐF–7 Æ “¦&Æö6²  –× ÷'F çC½Ðsk-
spinner-wave.sk-spinner {Ð margin:-15px 0 0 -25px; Ð position:absolute;Ð
left:50%; Ð top:55%;Ð width: 50px;Ð height: 30px;Ð text-align: center;Ð font-
size: 10px;Ð}Ðsk-spinner-wave div {Ð background-color: #000;Ð height: 100%;Ð
width: 6px;Ð display: inline-block;Ð -webkit-animation: sk-waveStretchDelay
1.2s infinite ease-in-out;Ð  animation: sk-waveStretchDelay 1.2s infinite
ease-in-out;ÐÐsk-spinner-wave .sk-rect2 {-webkit-animation-delay:
-1.1s;animation-delay: -1.1s;}Ðsk-spinner-wave .sk-rect3 {-webkit-animation-
delay: -1s;animation-delay: -1s; }Ðsk-spinner-wave .sk-rect4 {-webkit-
animation-delay: -0.9s;animation-delay: -0.9s;}Ðsk-spinner-wave .sk-rect5 { -
webkit-animation-delay: -0.8s;animation-delay: -0.8s;}Ð@-webkit-keyframes sk-
waveStretchDelay {Ð 0%, 40%, 100% {-webkit-transform: scaleY(0.4);transform:
scaleY(0.4);}Ð 20% { -webkit-transform: scaleY(1);transform: scaleY(1);}ÐÐ
@keyframes sk-waveStretchDelay {Ð 0%, 40%, 100% {-webkit-transform:
scaleY(0.4);transform: scaleY(0.4);}Ð 20% { -webkit-transform:
scaleY(1);transform: scaleY(1);}ÐÐ* 3.2 Parallax bg */Ðparallax-window {Ð
min-height: 470px;Ð& 6¶w&÷VæC§G& ç7  &VçC½ ÷6–F–öã§&VÆ F–fS½Ðparallax-
window#home {Ð   min-height: 550px;ÐÐparallax-window#short {Ð   height: 350px;Ð
min-height:inherit;ÐÐparallax-content{Ð6öÆ÷#¢6ffc½FW‡BÖ Æ–vã¦6VçFW#½F–7 Æ “¢
table;Ð   width:100%;Ð   height:470px;ÐÐparallax-content .sub_content{Ð
display: table-cell;Ð –  FF–æs£   RS½  vertical-align: middle;ÐFW‡BÐ
align:center;ÐföçB×6–¦S£ g ƒ½Ðparallax-content .sub_content h3{ÐÖ &v–ã£
10px 0;ÐföçB×6–¦S£c  ƒ½föçB×vV–v‡C£3  ½6öÆ÷#¢6ffc½föçBÖf Ö–Ç“¢ tÆ FòrÂ
"Helvetica Neue", Helvetica, Arial, sans-serif;ÐÐparallax-
content .sub_content i{ÐföçB×6–¦S£c  ƒ½Ðparallax-window-2 {Ð†V–v‡C¦ WFó½
background: url(../img/bg_office.jpg) no-repeat center center;Ð& 6¶w&÷VæBÐ
attachment:fixed;Ð& 6¶w&÷VæB×6–¦S¦6÷fW#½×vV&¶–BÖ& 6¶w&÷VæB×6–¦S¢ 6÷fW#½ÖÖ÷¢Ð
background-size: cover;ÐÖòÖ& 6¶w&÷VæB×6–¦S¢ 6÷fW#½ ÷6–F–öã§&VÆ F–fS½Ðparallax-
content-2 {Ð   display: table;Ð  width:100%;Ð height:auto;ÐÐparallax-
content-2 > div{Ð display: table-cell;Ð padding:10% 15%;Ð  vertical-align:
middle;ÐFW‡BÖ Æ–vã¦6VçFW#½6öÆ÷#¢6ffc½föçB×6–¦S£ g ƒ½Ðparallax-content-2 div
h3{ÐÖ &v–ã£       ,  ½föçB×6–¦S£c  ƒ½föçB×vV–v‡C£3  ½6öÆ÷#¢6ffc½föçBÖf Ö–Ç“¢
'Lato', "Helvetica Neue", Helvetica, Arial, sans-serif;ÐÐparallax-content-2
div p{ÐÖ &v–âÖ&÷GFöÓ£ ½Ðparallax-content-2 div i{ÐföçB×6–¦S£c  ƒ½Ð* 3.3
Position  breadcrumbs */Ð
```

#position {Þ& 6¶w&÷VæBÖ6öÆ÷#¢6ffc½&÷&FW"Ö&÷GFöÓ£ ,
solid #ededed;Þ FF–æs£ , ½föçB×6–¦S£ ƒ½Þposition ul li:first-child{Þ
padding-left:20px;ÞÞposition ul li:first-child:before{Þ6öçFVçC¢%ÆV cB#½föçBÞ
style: normal;Þ –föçB×vV–v‡C¢ æ÷&Ö Ã½ –föçBÖf Ö–Ç“¢ &föçFVÆÆò#½ •
position:absolute;Þ –ÆVgC£ ½’ F÷ £ ƒ½ –6öÆ÷#¢3““½Þposition ul{ÞÖ &v–ã£ ½
padding:0;Þ6öÆ÷#¢3fff½Þposition ul li a{Þ6öÆ÷#¢3#S#S#S½÷ 6–G“£ ãs½Þposition
ul li a:hover{Þ6öÆ÷#¢3#S#S#S½÷ 6–G“£ ½Þposition ul li{ÞF–7 Æ “¦–æÆ–æRÖ&Æö6³½
padding-right:8px;ÞÖ &v–â×&–v‡C£7 ƒ½ ÷6–F–öã§&VÆ F–fS½Þposition ul li:after{Þ
content:"\e9ee";ÞföçB×7G–ÆS¢ æ÷&Ö Ã½föçB×vV–v‡C¢ æ÷&Ö Ã½föçBÖf Ö–Ç“¢
"fontello";Þ ÷6–F–öã¦ '6öÇWFS½&–v‡C£ ½F÷ £' ƒ½Þposition ul li:last-
child:after{Þ6öçFVçC¢rs½Þmargin_fix {ÞÖ &v–â×F÷ £c ƒ½Ð*3.4 Login/Register
modals*/Þmessage-review .error_message{Þ6öÆ÷#¢4dc“½ ÷6–F–öã§&VÆ F–fS½F÷ ¢Ó3 ƒ½
}Þform-control.form-white {Þ6öÆ÷#¢ 3 ½föçB×6–¦S¢ g ƒ½†V–v‡C£C' ƒ½
position: relative;Þ&÷&FW"×& F–W3¢ ½&÷&FW#£ , 6öÆ–B 6cvcs½Æ–æRÖ†V–v‡C£C' ƒ½ð
background: #ffffff none repeat scroll 0 0;/Ð×vV&¶–B×G& ç6–F–öã¢ & 6¶w&÷VæBÐ
color 0.3s;ÞG& ç6–F–öã¢ & 6¶w&÷VæBÖ6öÆ÷" ã73½&÷,×6† F÷s¢ ½×vV&¶–BÐ
appearance: none;Þ -moz-appearance: none;Þ appearance: none; ÞÐ
select.form-control.form-white{Ð×vV&¶–BÖ V & æ6S¢ æöæS½ -moz-
appearance: none;Þ appearance: none; Þ -webkit-border-radius:
0;Þ -moz-border-radius: 0;Þ box-shadow:0;Þ border-radius: 0;Þ height:42px;Þ
line-height:28px;ÞÞmodal-dialog #review .form-control.form-white{ÞÖ &v–âÐ
bottom:0;ÞÞform-control.form-white:placeholder {Þ÷ 6–G“¢ ½6öÆ÷#¢ 6ffc½Þform-
control.form-white::placeholder {Þ÷ 6–G“¢ ½6öÆ÷#¢ 3v3v#s“½Þform-
control.form-white:focus {Þ& 6¶w&÷VæC¢ &v& ƒ#SRÃ#SRÃ#SRÃ ã""½ ×vV&¶–BÖ&÷,Þ
shadow: none;Ð’ &÷,×6† F÷s¢ æöæS½Þlogin_icon {Þ6öÆ÷#¢ 6CƒC S“½ font-size:
60px;ÞÞmodal-backdrop {Þ¢Ö–æFWƒ£""""""½Þmodal {Þ FF–æs¢ #W , –× ÷'F çC½¢Þ
index:9999999;ÞÐ*.modal-dialog {*/Ð*–v–GFƒ¢ S²¢ÿ*–Ö ,×v–GFƒ¢ Cƒ ƒ²¢ÿ*•
margin: 0 auto;*/Ð*}*/Þmodal-dialog #review {Þv–GFƒ¢ S½Ö ,×v–GFƒ¢ cS ƒ½Þ
.modal-popup {Þ ÷6–F–öã¢ &VÆ F–fS½ FF–æs£ , 3 , , 3 ƒ½FW‡BÖ Æ–vã¢
center;Þ& 6¶w&÷VæC¢ 6cVcVcR æöæR &W V B 67&öÆÂ ½&÷&FW"×& F–W3¢ ƒ½
border:none;ÞÞmodal-popup a{Þ6öÆ÷#¢6ffc½Þmodal-popup a:hover{ÞFW‡BÞ
decoration:underline;ÞÞmodal-popup a.close-link {ÞföçB×6–¦S¢ #' ƒ½ ÷6–F–öã¢
absolute;ÞF÷ ¢ # ƒ½&–v‡C¢ 3 ƒ½6öÆ÷#¢ 66c &3½Þmodal-popup a.close-
link:hover {Þ6öÆ÷#¢ 3333½FW‡BÖFV6÷& F–öã¦æöæS½Þpopup-form {Þv–GFƒ¢ “ S½Ö ,Þ
width: 375px;ÞÖ &v–ã¢ c , WFó½Þpopup-form .form-control {ÞÖ &v–ã¢ # , ½Þ
s.checkbox-holder {Þv†–FR×7 6S¢ æ÷w& ½Þcheckbox {Þ ÷6–F–öã¢ &VÆ F–fS½
display: block;ÞÞcheckbox {Þ ÷6–F–öã¢ &VÆ F–fS½Þcheckbox label:before {Þ
content: '';Þ ÷6–F–öã¢ '6öÇWFS½F÷ ¢ ½ÆVgC¢ ½v–GFƒ¢ # ƒ½†V–v‡C¢ # ƒ½
cursor: pointer;Þ&÷&FW#¢ ' , 6öÆ–B 66c &3½& 6¶w&÷VæC¢ G& ç7 &VçC½×vV&¶–BÐ
transition: background-color 0.3s;ÞG& ç6–F–öã¢ & 6¶w&÷VæBÖ6öÆ÷" ã73½Þ
.checkbox input[type=checkbox]:focus + label:before {Þ& 6¶w&÷VæC¢
rgba(255,255,255,0.2);ÞÞcheckbox label:after {Þ6öçFVçC¢ rs½ ÷6–F–öã¢ '6öÇWFS½
top: 5px;ÞÆVgC¢ W ƒ½v–GFƒ¢ ƒ½†V–v‡C¢ ƒ½÷ 6–G“¢ ½& 6¶w&÷VæC¢ 66c &3½Þ
webkit-transition: all 0.3s ease;ÞG& ç6–F–öã¢ ÆÂ ã72 V 6S½Þcheckbox
input[type=checkbox] {Þ÷ 6–G“¢ ½ ÷6–F–öã¢ '6öÇWFS½v–GFƒ¢ ½†V–v‡C¢ ½Þ
#login_2 .forget {Þ margin-top: 7px;ÞÞcheckbox input[type=checkbox]:checked
+ label:after {Þ÷ 6–G“¢ ½Þcheckbox-holder span {Þ ÷6–F–öã¢ &VÆ F–fS½F–7 Æ “¢
inline-block;ÞÖ &v–ã¢ ƒ½v†–FR×7 6S¢ æ÷&Ö Ã½6öÆ÷#¢ 6ffc½Þbtn.btn-
submit {Þv–GFƒ¢ S½Ö &v–â×F÷ ¢ 3 ƒ½6öÆ÷#¢ 6fffffc½ FF–æs£ ƒ½& 6¶w&÷VæC¢
#cf0a2c none repeat scroll 0 0;ÞföçB×vV–v‡C£c ½÷WFÆ–æS¦æöæS½×vV&¶–BÐ
transition: all 0.2s ease;ÞG& ç6–F–öã¢ ÆÂ ã'2 V 6S½föçB×6–¦S£ g ƒ½Þbtn.btn-
submit:focus {Þ÷WFÆ–æS¦æöæS½Þbtn.btn-submit:hover {Þ6öÆ÷#¢ 6ffc½& 6¶w&÷VæC¢
#444;ÞÐ*3.5 Spacing*/Ðadd_bottom_15 {margin-bottom:15px;}Ðadd_bottom_30
{margin-bottom:30px;}Ðadd_bottom_45 {margin-bottom:45px;}Ðadd_bottom_60
{margin-bottom:60px;}Ðadd_bottom_75 {margin-bottom:75px;}Ðadd_top_20 {padding-
top:20px;}Ðadd_top_60 {padding-top:60px;}Ðmargin_60 {padding-top:60px;
padding-bottom:60px;}Ðmargin_60_35 {padding-top:60px; padding-bottom:35px;}Þ
.margin_30 {margin-top:30px; margin-bottom:30px;}Ðnomargin_top {margin-top:0;}Þ
.nopadding {margin: 0 !important;padding: 0 !important;}Ðnomargin {margin: 0 !
important;}Þ

Ð* 3.6 Map */Ðmarker_info {Ð width: 230px;Ð height: 200px;Ð
padding: 20px;Ð border-radius: 3px;Ð text-align: center;Ð background:
rgba(255, 255, 255, 0.9);Ð position: relative;Ð z-index: 9999999;Ð font-
family: "Helvetica Neue", Helvetica, Arial, sans-serif;Ð border: 1px solid
#ddd;ÐÐmarker_info img {Ð display: block;ÐÖ &v–ã¦ WFó½Ðmarker_info h3 {ÐföçBÐ
size:16px;ÐÆ–æRÖ†V–v‡C£ ‡ ƒ½FW‡B×G& ç6f÷&Ó§W W&6 6S½Ö &v–âÖ&÷GFöÓ£7 ƒ½Ð
.marker_info em {ÐÖ &v–âÖ&÷GFöÓ£ ƒ½F–7 Æ "¦–æÆ–æRÖ&Æö6³½föçB×6–¦S£ 7 ƒ½
color:#999;ÐÐmarker_info span {Ð display: block;Ð padding: 0;Ð font-
size: 12px;ÐÆ–æRÖ†V–v‡C£ g ƒ½6öÆ÷#¢3SSS½Ö &v–âÖ&÷GFöÓ£ W ƒ½Ðmarker_info:after{Ð
right: 100%;ÐF÷ ¢ S S½&÷&FW#¢ 6öÆ–B G& ç7 &VçC½6öçFVçC¢ " #½†V–v‡C¢ ½v–GFƒ¢
0;Ð ÷6–F–öã¢ '6öÇWFS½ ö–çFW"ÖWfVçG3¢ æöæS½&÷&FW"Ö6öÆ÷#¢ &v& ƒ Â Â Â "½
border-right-color: rgba(255, 255, 255, 0.9);Ð&÷&FW"×v–GFƒ¢ ƒ½Ö &v–â×F÷ ¢
-10px;ÐÐinfoBox > img { z-index:999999999; }Ð* 3.7 Password strength */ Ð
#pass-info{Ðv–GFƒ¢ S½Ö &v–âÖ&÷GFöÓ£ W ƒ½6öÆ÷#¢ 3ƒ#"4$C½FW‡BÖ Æ–vã¢ 6VçFW#½
font: 12px/25px Arial, Helvetica, sans-serif;ÐÐpass-info.weakpass{Ð&÷&FW#¢ ,
solid #FF9191;Ð& 6¶w&÷VæC¢ 4dd3t3s½6öÆ÷#¢ 3"CSCdS½FW‡B×6† F÷s¢ , , ,
#FFF;ÐÐpass-info.stillweakpass {Ð&÷&FW#¢ , 6öÆ–B 4d$#½& 6¶w&÷VæC¢ 4dDC½
color: #945870;ÐFW‡B×6† F÷s¢ , , , 4ddc½Ðpass-info.goodpass {Ð&÷&FW#¢
1px solid #C4EEC8;Ð& 6¶w&÷VæC¢ 4SDddSC½6öÆ÷#¢ 3S "#dS½FW‡B×6† F÷s¢ , , ,
#FFF;ÐÐpass-info.strongpass {Ð&÷&FW#¢ , 6öÆ–B 3dTCcdS½& 6¶w&÷VæC¢ 3s"c s"½
color: #348F34;ÐFW‡B×6† F÷s¢ , , , 4ddc½Ðpass-info.vrystrongpass {Ð
border: 1px solid #379137;Ð& 6¶w&÷VæC¢ 3C„#CCƒ½6öÆ÷#¢ 44Ddd4C½FW‡B×6† F÷s¢ ,
1px 1px #296429;ÐÐ* 3.8 Input form style */ Ðloader { margin-left:5px;
position:absolute;}Ðerror_message { color:#fff; font-weight:600; margin-
bottom:4px;padding:10px;}Ðform-control {Ð color: #333;Ð height:40px;Ð border-
radius: 3px;Ð box-shadow:none;Ð border:1px solid #ddd;Ð box-shadow: 0;ÐÐform-
group {ÐÖ &v–âÖ&÷GFöÓ£# ƒ½Ðfooter .form-group {ÐÖ &v–âÖ&÷GFöÓ£ W ƒ½Ð
.payment_select {Ð background-color: #f7f7f9;Ð border: 1px solid #e7e7e9;Ð
  float: left;Ð margin-bottom: 20px;Ð padding-bottom: 0;Ð width: 100%;Ð
}Ðpay_now_data {Ð margin-bottom: 15px;ÐÐthank-u td strong {Ð color:
#cf0a2c;Ð padding: 0 5px;ÐÐthank-u #cart_html tr td:first-child {Ð float:
none;Ð display: table-cell;Ð width: 100%;ÐÐthank-u #cart_html tr {Ð
float: left;Ð width: 100%;ÐÐthank-u #cart_html tr {Ð float: none;Ð
width: auto;ÐÐpayment_select label{ÐföçB×6–¦S£ g ƒ½Ð
.payment_radios.payment_select i {Ð float: right;Ð font-size: 24px;Ð
margin: 23px 10px 0;ÐÐpayment_select#paypal{Ð& 6¶w&÷VæC¢6c c c W&Â,ââö–Örð
paypal.svg) center right no-repeat;ÐÐ*3.9 Collapse*/ Ðpanel {Ð border-
radius: 3px;Ð -webkit-box-shadow: none;Ð box-shadow:none;Ð border-
color:#ededed;ÐÐpanel-title a {display:block; color:#444;}Ðpanel-default
> .panel-heading {Ð background-color: #f9f9f9;Ð padding:20px;Ð border-
bottom:1px solid #ddd;ÐÐpanel-heading {Ð border-top-left-radius: 3px;Ð border-
top-right-radius: 3px;ÐÐpanel-group .panel {Ð border-radius: 3px;ÐÐpanel-body
{Ð FF–æs£3 ƒ½Æ–æRÖ†V–v‡C£ ãb –× ÷'F çC½Ðpanel-title a .indicator{Ð
color:#CF0A2C;ÐÐpanel-title a:hover .indicator{Ð6öÆ÷#¢3333½Ð*3.10 Tabs*/ Ð
.tab-content{Ð FF–æs£3 ƒ²–& 6¶w&÷VæBÖ6öÆ÷#¢6ffc²–&÷&FW#£ , 6öÆ–B 6FFC²•
border-top:none; ÐÖ &v–âÖ&÷GFöÓ£#W ƒ½×vV&¶–BÖ&÷&FW"Ö&÷GFöÒ×&–v‡B×& F–W3¢ 7 ƒ½Ð
webkit-border-bottom-left-radius: 3px;ÐÖÖ÷¢Ö&÷&FW"×& F–W2Ö&÷GFö×&–v‡C¢ 7 ƒ½Ð
moz-border-radius-bottomleft: 3px;Ð&÷&FW"Ö&÷GFöÒ×&–v‡B×& F–W3¢ 7 ƒ½&÷&FW"Ð
bottom-left-radius: 3px;ÐÐ*3.11 Tooltips*/ Ðtooltip_styled {ÐF–7 Æ "¢ –æÆ–æS½
position: relative;Ð¢Ö–æFWƒ¢ """½Ðtooltip-item {Ð7W'6÷#¢ ö–çFW#½F–7 Æ "¢
inline-block;ÐÐtooltip-item::after {Ð6öçFVçC¢ rs½ ÷6–F–öã¢ '6öÇWFS½v–GFƒ¢
180px;Ð†V–v‡C¢ # ƒ½&÷GFöÓ¢ S½ÆVgC¢ S S½ ö–çFW"ÖWfVçG3¢ æöæS½×vV&¶–BÐ
transform: translateX(-50%);ÐG& ç6f÷&Ó¢ G& ç6Æ FU,,ÓS R"½Ð
.tooltip_styled:hover .tooltip-item::after {Ð ö–çFW"ÖWfVçG3¢ WFó½Ðtooltip-
content {Ð ÷6–F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ """½v–GFƒ¢ ƒ ƒ½ÆVgC¢ S S½Ö &v–ã¢
20px -90px;Ð&÷GFöÓ¢ S½FW‡BÖ Æ–vã¢ ÆVgC½Æ–æRÖ†V–v‡C£ ã#½F–7 Æ "¢ &Æö6³½
padding: 15px;ÐföçB×6–¦S£ 7 ƒ½FW‡BÖ Æ–vã¦6VçFW#½föçB×vV–v‡C£c ½6öÆ÷#¢ 6ffc½
box-shadow: -5px -5px 15px rgba(48,54,61,0.2);Ð& 6¶w&÷VæC¢ 3333½÷ 6–G"¢ ½
cursor: default;Ð ö–çFW"ÖWfVçG3¢ æöæS½Ðtooltip-effect-1 .tooltip-content {ÐÐ
webkit-transform: translate3d(0,-10px,0);Ð

—G& ç6f÷&Ó¢ G& ç6Æ FS6Bƒ ÂÓ ,Ã “½Ð
webkit-transition: opacity 0.3s, -webkit-transform 0.3s;ÐG& ç6—F–öã¢ ÷ 6—G’
0.3s, transform 0.3s;ÞÐtooltip-effect-2 .tooltip-content {Ð×vV&¶—B×G& ç6f÷&ÒÐ
origin: 50% calc(100% + 10px);ÐG& ç6f÷&ÒÖ÷&–v–ã¢ S R 6 Æ2ƒ R ² ,“½×vV&¶—BÐ
transform: perspective(1000px) rotate3d(1,0,0,45deg);ÐG& ç6f÷&Ó¢
perspective(1000px) rotate3d(1,0,0,45deg);Ð×vV&¶—B×G& ç6—F–öã¢ ÷ 6—G’ ã'2Â Ð
webkit-transform 0.2s;ÐG& ç6—F–öã¢ ÷ 6—G’ ã'2Â G& ç6f÷&Ò ã'3½Ðtooltip-
effect-3 .tooltip-content {Ð×vV&¶—B×G& ç6f÷&Ó¢ G& ç6Æ FS6Bƒ Ã ,Ã ’
rotate3d(1,1,0,25deg);ÐG& ç6f÷&Ó¢ G& ç6Æ FS6Bƒ Ã ,Ã ’ &÷F FS6Bƒ Ã Ã Ã#VFVr“½Ð
webkit-transition: opacity 0.3s, -webkit-transform 0.3s;ÐG& ç6—F–öã¢ ÷ 6—G’
0.3s, transform 0.3s;ÞÐtooltip-effect-4 .tooltip-content {Ð×vV&¶—B×G& ç6f÷&ÒÐ
origin: 50% 100%;ÐG& ç6f÷&ÒÖ÷&–v–ã¢ S R S½×vV&¶—B×G& ç6f÷&Ó¢
scale3d(0.7,0.3,1);ÐG& ç6f÷&Ó¢ 66 ÆS6Bƒ ãrÃ ã2Ã “½×vV&¶—B×G& ç6—F–öã¢ ÷ 6—G’
0.2s, -webkit-transform 0.2s;ÐG& ç6—F–öã¢ ÷ 6—G’ ã'2Â G& ç6f÷&Ò ã'3½Ð
.tooltip_styled:hover .tooltip-content {Ð ö–çFW"ÖWfVçG3¢ WFó½÷ 6—G“¢ ½Ð
webkit-transform: translate3d(0,0,0) rotate3d(0,0,0,0);ÐG& ç6f÷&Ó¢
translate3d(0,0,0) rotate3d(0,0,0,0);ÞÐtooltip_styled.tooltip-
effect-2:hover .tooltip-content {Ð×vV&¶—B×G& ç6f÷&Ó¢ W'7 V7F—fRƒ ,’
rotate3d(1,0,0,0deg);ÐG& ç6f÷&Ó¢ W'7 V7F—fRƒ ,’ &÷F FS6Bƒ Ã Ã Ã FVr“½Ð
.tooltip-content::after {Ð6öçFVçC¢ rs½F÷ ¢ S½ÆVgC¢ S S½&÷&FW#¢ 6öÆ–B
transparent;Ð†V–v‡C¢ ½v–GFƒ¢ ½ ÷6—F–öã¢ '6öÇWFS½ ö–çFW"ÖWfVçG3¢ æöæS½&÷&FW"Ð
color: transparent;Ð&÷&FW"×F÷ Ö6öÆ÷#¢ 3333½&÷&FW"×v–GFƒ¢ ƒ½Ö &v–âÖÆVgC¢
-10px;ÞÐtooltip-content .label {ÐÖ &v–âÖÆVgC£ ƒ½Ðtooltip-content i{ÐföçBÐ
size:20px !important;ÐF÷ £7 , –× ÷'F çC½ÆVgC¢Ó7 , –× ÷'F çC½
position:relative;ÞÐtooltip-content h4 {ÐF—7 Æ “¦&Æö6³½Ö &v–ã¢ , ½Æ–æRÐ
height:14px;ÐföçB×6—¦S£ G ƒ½6öÆ÷#¢6ffc½FW‡B×G& ç6f÷&Ó§W W&6 6S½Ðtooltip-
content a {ÐföçB×vV–v‡C¢ &öÆC½Ð*3.12 Blockquote*/Ðlockquote.styled {ÐföçBÐ
family:Georgia, "Times New Roman", Times, serif;ÞÐwhite_bg{Ð& 6¶w&÷VæBÐ
color:#fff;ÞÐmobile_app{Ð& 6¶w&÷VæC¢ W&Â,"ââö–Örö Ö&ræ§ r"’ æò×&W V B 67&öÆÂ
0 0 ;Ð& 6¶w&÷VæB×6—¦S¢ R S½fÆö C¢ ÆVgC½v–GFƒ¢ S½Ö &v–âÖ&÷GFöÓ¢ C ƒ½
margin-top: -30px;ÞÐmobile-hnd {Ð margin-top: 50px;ÞÐtable.cart-list td {Ð
padding: 10px 0;ÞÐtable.table.cart-list .col-md-2 img {Ð border: 4px
solid #f7f7f7;Ð border-radius: 2px;Ð margin-top: 10%;Ð width: 95px;Ð
min-height: 95px;Ð ÞÐmad_log{Ð FF–æs¢ sW , ½ÐÐmad_log .mad_logo {Ð
display: table;Ð margin: 0 auto;Ð width: 140px;ÞÐmad_log h3{ÐÖ &v–ã¢ # ,
0 0;ÞÐmad_log h3, .mad_log h4 {Ð color: #ffffff;Ð text-align: center;Ð
text-transform: capitalize;ÞÐmad_log h4 {Ð font-size: 23px;Ð margin: 10px
0 0;ÞÐapp_logos {Ð margin-top: 60px;ÞÐmad_log span {Ð color: #cf0a2c;ÞÐ
.mad_log a img {Ð display: table;Ð margin: 10px auto 0;Ð width: 120px;ÞÐ
#promotion img{Ðv–GFƒ¢ S½ÐparallaxÐcontent.parallax-content1{Ð height:
560px;Ð ÞÐblack_logo img {Ð margin-top: 60px;ÞÐcompany li, #solution li {Ð
padding: 4px 0;ÞÐsupport i {Ð float: left;Ð margin: 2px 10px 0 0;ÞÐ
.sidebar > h3 {Ð background-color: #cf0a2c;Ð border-radius: 3px 3px 0 0;Ð
color: #ffffff;Ð margin: 0;Ð padding: 10px;Ð font-weight: bold;ÞÐ
.btns_sld {Ð display: table;Ð margin: 0 auto;ÞÐbtns_sld .btn_sld{Ð
background-color: #cf0a2c;Ð border-right: 1px solid rgba(0, 0, 0, 0.3);Ð
cursor: pointer;Ð float: left;Ð height: 40px;Ð margin-bottom: 15px;Ð
padding: 8px 10px;ÞÐbtns_sld .btn-active{Ð& 6¶w&÷VæBÖ6öÆ÷#¢ &Æ 6³½Ð
#main_menu .rates {Ð border-bottom: 1px solid #f5f5fc;Ð display: table;Ð
float: right;Ð min-width: 100%;ÞÐpin-wrapper #cart_html .empty_cart td {Ð
font-size: 16px;Ð font-weight: bold;Ð width: 99%;ÞÐmain_menu
a.addtocart i {Ð float: right;Ð font-size: 20px;Ð color: #CF0A2C;Ð
margin: 0 0 5px 5px;ÞÐcart_box #cart_html a i {Ð color: #aaa;Ð float:
left;Ð font-size: 17px;Ð margin: 7px 7px 10px 0;Ð transition:.4s;ÞÐ
#cart_html > tbody {Ð display: block;ÞÐcart_box #cart_html a i:hover{Ð6öÆ÷#¢
#CF0A2C;ÞÐback_white {Ð background-color: #ffffff;Ð border: 1px solid
rgba(0, 0, 0, 0.1);Ð box-shadow: 1px 3px 5px 0 #e6e5e1;Ð float: left;Ð
padding: 15px;Ð width:100%;ÞÐback_white h2.title {Ð margin: 0 0 10px;Ð
text-align: center;ÞÐcart_box strong {Ð color: #cf0a2c;Ð margin: 0 3px 0
0;Ð

}ÐÐcart_html tr {Ð float: left;Ð padding: 8px 0 8px 8px;Ð position: relative;Ð width: 100%;ÐÐcart_box #cart_html tr:nth-child(2n+1) {Ð background-color: #f7f7f7;Ð border-top: 1px solid #f1f1f1;ÐÐcart_html #price_itm {Ð position: absolute;Ð right: 4px;Ð top: 0;ÐÐcart_html tr td:first-child {Ð display: table;Ð float: left;Ð width: 72%;ÐÐcart-total-area table td {Ð padding: 10px 0 0 !important;ÐÐprofile_left_side {Ð list-style: outside none none;Ð margin: 0;Ð padding: 0;ÐÐ .profile_left_side > li.active,.profile_left_side > li.active a,.profile_left_side > li a:hover{Ð background-color: #cf0a2c;Ð color: #fff;ÐÐprofile_left_side li a{Ð6öÆ÷#¢ &Æ 6³½ padding: 10px 15px;Ð font-size: 15px;ÐF—7 Æ “¢ &Æö6³½Ö &v–âÖ&÷GFöÓ£' ƒ½ transition:.4s all ease-in-out;ÐÐorder_process.prfl input {Ð border-radius: 0;ÐÐorder_process.prfl input[type="submit"],#addcard form input.form-control[type="submit"] {Ð background-color: #cf0a2c;Ð color: #ffffff;Ð font-size: 15px;Ð font-weight: bold;ÐÐbs-wizard .bs-wizard-step.active .bs-wizard-dot::after {Ð background-color: #000000;ÐÐmenus li {Ð background-color: #F7F7F9;Ð display: inline;Ð float: left;Ð border-right: 1px solid #e1e1e1;Ð list-style-type: none;Ð width: 25%;Ð transition:.4s all ease-in-out;ÐÐmenus {Ð float: left;Ð padding: 0;Ð width: 100%;ÐÐmenus li.active,.menus li.active a,.menus li a:hover{Ð& 6¶w&÷VæBÖ6öÆ÷#¢ 6ffc½6öÆ÷#¢ 44c $3½ÐÐmenus li a {Ð float: left;Ð color: #4e4e4e;Ð padding: 10px;Ð width: 100%;ÐÐ .menus li a {Ð float: left;Ð font-size: 16px;Ð font-weight: bold;Ð padding: 15px;Ð text-align: center;Ð width: 100%;ÐÐmenus i {Ð padding-right: 4px;ÐÐsidebar .box_style_1{Ð&÷&FW#£ æöæS½ÐÐcontainer_pin #main_menu .table-striped > tbody > tr:nth-of-type(2n+1){Ð& 6¶w&÷VæC¦æöæS½Ð .all-menu-detail .tab-content.current {Ð border: 0 none;Ð display: inherit;Ð float: left;Ð margin: 0;Ð padding: 10px 0 10px;Ð width: 100%;ÐÐall-menu-detail ul.tabs{ÐÖ &v–ã¢ ƒ½ FF–æs¢ ƒ½Æ—7B×7G–ÆS¢ æöæS½¢Ð index: 999;ÐF÷ ¢ , –× ÷'F çC½ÐÐall-menu-detail ul.tabs li {Ð color: #222222;Ð cursor: pointer;Ð display: inline-block;Ð font-size: 16px;Ð height: 53px;Ð padding: 15px 15px 0;Ð text-align: center;ÐÐall-menu-detail ul.tabs li.current{Ð& 6¶w&÷VæC¢ 4ddc½6öÆ÷#¢ 44c $3½föçB×vV–v‡C¢ &öÆC½Ð .all-menu-detail .tab-content{ÐF—7 Æ “¢ æöæSÐÐall-menu-detail .tab-content.current{ÐF—7 Æ “¢ –æ†W&—C½ÐÐall-menu-detail #tab-2 h2 {Ð font-size: 30px;ÐÐmap_restaurant {Ð border: 5px solid #f6f6f6;Ð margin-top: 25px;ÐÐ #tab-2 h3:first-child{Ð display: inline-block; ÐÐall-menu-detail #tab-2 span {Ð display: inline-block;Ð font-size:14px;Ð color:black;ÐÐall-menu-detail #tab-2 span h4{Ð color: black;ÐÐall-menu-detail #tab-2 h3 {Ð font-size: 17px;Ð margin-top: 0;Ð text-align: center;ÐÐall-menu-detail #tab-2 table {Ð width: 90%;ÐÐall-menu-detail #tab-2 tr td:first-child {Ð float: left;ÐÐall-menu-detail #tab-2 tr td:last-child {Ð float: right;ÐÐall-menu-detail #tab-2 tr td {Ð color: #000000;Ð padding: 5px;ÐÐday_selector {Ð background-color: #f7f7f9;Ð border: 1px solid #ebebed;ÐÐtab-3 > h2 {Ð text-align: center;ÐÐrestaurant_bg #subheader{Ð†V–v‡C¢ Cs ƒ½Ðtype_order label i {Ð float: right;Ð margin: 3px 0 0 5px;ÐÐpromotions .col-md-5 {Ð background-color: rgba(0, 0, 0, 0.7);Ð padding-bottom: 15px;Ð padding-top: 15px;Ð text-align: left;ÐÐpromotions .sub_content {Ð padding: 10%;ÐÐ .promotions h2 {Ð color: #ffffff;ÐÐpromotions p {Ð color: #c0c0c0;Ð text-transform: capitalize;ÐÐpromotions a.btn{Ð background-color: #cf0a2c;Ð border: 0 none;Ð border-radius: 6px;Ð font-size: 20px;Ð font-weight: bold;Ð padding: 10px 15px;Ð color: #fff;Ð text-shadow: 0 0 2px rgba(0, 0, 0, 0.6);Ð text-transform: uppercase;Ð margin-top: 13px;ÐÐ .promotions h5 i {Ð border: 1px solid #c0c0c0;Ð border-radius: 50%;Ð color: #c0c0c0;Ð font-size: 15px !important;Ð height: 25px;Ð line-height: 1.5;Ð margin: 0 6px 0 0;Ð text-align: center;Ð width: 25px;ÐÐ .promotions h5,.promotions h5 a{Ð color: #c0c0c0;Ð text-transform: uppercase;ÐÐorder_process h2.title:first-child {Ð color: #4e4e4e;Ð display: inline-block;Ð float: left;Ð font-size: 28px;Ð font-weight: bold;Ð margin: 8px 0 0;Ð padding: 4px 15px;Ð text-align: left;ÐÐ #order_process .logn {Ð

background-color: #cf0a2c;Ð border: medium none;Ð
    border-radius: 3px;Ð box-shadow: 0 0 6px 0 #eeeeee;Ð color: #ffffff;Ð
    display: table;Ð font-size: 18px;Ð font-weight: bold;Ð margin: 0
auto;Ð padding: 10px 43px;ÞÐborder_process span {Ð display: table;Ð
margin:5px auto 0;Ð width:100%;ÞÐborder_process h4.title {Ð display: table;Ð
    font-size: 17px;Ð margin: -9px auto 20px;Ð position: relative;Ð
text-align: center;Ð text-transform: uppercase;ÞÐborder_process
h4.title::after {Ð border-left: 10px solid rgba(0, 0, 0, 0);Ð border-
right: 10px solid rgba(0, 0, 0, 0);Ð border-top: 10px solid #cf0a2c;Ð
bottom: -18px;Ð content: "";Ð position: absolute;Ð right: 28px;ÞÐ
.type_order i {Ð margin-left: 3px;Þ•type_order input {Ð float: left;Ð
margin: 3px 3px 0 0;ÞÐmain_menu table p {Ð margin-top: 6px;Ð min-height:
70px;ÞÐsub_content .frmSearch {Ð display: table;Ð padding:10px 0;Ð
margin: 0 auto;Ð width:100%;ÞÐsearch-area-dv .input-group {Ð width: 100%;ÞÐ
.search-area-dv button.btn {Ð background-color: #cf0a2c;Ð border: medium
none;Ð font-size: 16px;Ð height: 40px;Ð border-radius:0;ÞÐsearch-area-
dv .input-group ul.typeahead {Ð border-radius: 0;Ð max-height: 200px;Ð
overflow-x: hidden;Ð overflow-y: auto;Ð width: 100%;ÞÐstrip_list .view_a {Ð
    padding: 46px 1%;ÞÐtype_order{Ð FF–æs£ –× ÷'F çC½Ðcart_box #cart_html {Ð
    max-height: 320px;Ð overflow-x: hidden;Ð display:block;Ð overflow-
y: auto;ÞÐvendor-info__overview__list strong {Ð font-size: 16px;Ð font-
weight: 800;ÞÐvendor-info__overview__list dt {Ð padding: 8px 0;ÞÐvendor-
info__overview__list.section2{ÞÐpadding-top: 0;}Ðvendor-info__overview__list
dd {Ð font-size: 16px;ÞÐvendor-info__overview__list.section2 img {Ð
width: 38px;ÞÐview_description_p{ÞÐföçB×6—¦S¢ G ƒ½v–GFƒ¢ “ S½Ðnext-restaurent
i {Ð color: #aaaaaa;Ð font-size: 40px;Ð padding: 85% 35%;ÞÐslideshow {Ð
    position: relative;ÞÐslideshow > div { Ð position: absolute; Ð top:
0; Ð left: 0; Ð width:100%;Ð height:550px;Ð z-index:1;ÞÐsld1{Ð
background:url('../../assets/img/slides/Ns-1.jpg') no-repeat scroll center
center / cover;ÞÐsld2{Ð& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ö–Ör÷6Æ–FW2ôç2Ó"æ§ rr’ æòÐ
repeat scroll center center / cover;ÞÐsld3{Ð& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ö–Örð
slides/Ns-3.jpg') no-repeat scroll center center / cover;ÞÐsld4{Ð
background:url('../../assets/img/slides/Ns-4.jpg') no-repeat scroll center
center / cover;ÞÐsld5{Ð& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ö–Ör÷6Æ–FW2ôç2ÓRæ§ rr’ æòÐ
repeat scroll center center / cover;ÞÐ*.sld6{*/Ø*–& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ð
img/slides/N-6.jpg') no-repeat scroll center center / cover;*/Ø*}*/Ø*.sld7{*/Ø
*–& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ö–Ör÷6Æ–FW2ôâÓræ§ rr’ æò×&W V B 67&öÆÂ 6VçFW"
center / cover;*/Ø*}*/Ø*.sld8{*/Ø*–& 6¶w&÷VæC§W&Â,rââòâäö 76WG2ö–Ör÷6Æ–FW2ð
N-8.jpg') no-repeat scroll center center / cover;*/Ø*}*/Øslideshow > div img{Ð
width:100%;Ð†V–v‡C£ S½Ðrestaurent-time {Ð text-align: end;ÞÐ
.no_record_found {Ð text-align: center;ÞÐ.auth__title {ÐÐ color: #eb5c32;Ð
    margin: 10px 0 0px;Ð ÞÐauth__title {Ð text-align: center;Ð color:
#222222;Ð font-family: inherit;Ð font-size: 30px;Ð font-weight: 700;Ð
line-height: 1.1;Ð ÞÐbtn.btn-block.btn-social.btn-facebook {Ð background:
#334d86 none repeat scroll 0 0;Ð padding: 9px;Ð color: #ffffff !important;Ð
    margin-top: 35px;ÞÐlogin_2 a {Ð color: #cf0a2c;Ð font-size: 16px;ÞÐ
.text-right.forget {Ð float: right;Ð padding: 5px 0;Ð width: 50%;ÞÐtext-
left.remember {Ð float: left;Ð padding: 5px 0;Ð width: 50%;ÞÐmyLogin >
#htmlmsg {Ð color: #ff0000 !important;Ð padding: 30px 0 0;ÞÐ
.row.register_model div {Ð padding: 0 8px;ÞÐrow.register_model div input {Ð
    margin: 10px 0;ÞÐread-condition {Ð font-size: 15px;ÞÐread-condition a {Ð
    color: #cf0a2c;ÞÐrow.register_model {Ð padding: 6px;Ð margin-top:18px;Ð
}Ðcheckbox label, .radio label{ÞÐ FF–ærÖÆVgC¢ 3' , –× ÷'F çC½Ö &v–â×F÷ ¢ÓG ƒ½Ð
#line {Ð position: relative;ÞÐline::after {Ð background: #f8f6f1 none
repeat scroll 0 0;Ð content: "OR";Ð color: #666666;Ð left: 46%;Ð
margin-top: 8px;Ð position: absolute;Ð width: 10%;ÞÐline::before {Ð
border-bottom:1px solid #d8d8d8;Ð content: "";Ð left: 0;Ð margin-top:
17px;Ð position: absolute;Ð width: 100%;ÞÐthumb_end {Ð color: #f2f2f2;Ð
    font-size: 50px;Ð position: absolute;Ð right: 0;Ð top: 19px;ÞÐ
.thumb_end i {Ð

text-shadow: 0 1px 1px rgba(0, 0, 0, 0.2);ÐÐcol-
sm-3.delivery_app imgÐÐv–GFƒ£#RS½Ðcol-sm-3.delivery_appÐÐFW‡BÖ Æ–vã¢ 6VçFW#½
margin-top: 40px;ÐÐcol-sm-3.waiter_appÐÐFW‡BÖ Æ–vã¢ 6VçFW#½ Ö &v–â×F÷ ¢ C ƒ½Ð
.col-sm-3.print_mobile > img {Ð width: 25%;ÐÐcol-sm-3.print_mobile {Ð
text-align: end;Ð margin-top: -100px;ÐÐcol-sm-3.print_mobile.one {Ð text-
align: left;ÐÐcol-sm-3.print_mobile.one > img {Ð width: 60%;ÐÐcol-
sm-3.print_mobile.one > p {Ð margin-left: 17%;ÐÐcol-sm-3.waiter_app imgÐÐ
width:25%;ÐÐcol-sm-12.maduber-center {Ð text-align: center;ÐÐcol-
sm-12.maduber-center img {Ð width: 30%;Ð margin-top: -16px;ÐÐcol-
sm-12.point-of-sale div:first-child img {Ð top: 0;Ð width: 40%;ÐÐcol-
sm-12.point-of-sale div:first-child {Ð text-align: center;Ð top: -35px;Ð Ð
}Ðcol-sm-12.point-of-sale div:last-child img {Ð width: 25%;ÐÐcol-
sm-12.point-of-sale div:last-child {Ð text-align: center;Ð top: -50px;ÐÐ
.col-sm-12.restaurant_solution_p p {Ð color: #000000;Ð font-size: 15px;Ð
    font-weight: 600;Ð text-transform: capitalize;ÐÐcol-
sm-6.restaurent_intro {Ð background: rgba(0, 0, 0, 0.1) none repeat scroll 0
0;Ð padding: 0 18px;Ð top: 30px;ÐÐcol-sm-6.restaurent_intro > h2 {Ð
font-size: 17px;Ð font-weight: 600;Ð text-transform: capitalize;ÐÐcol-
sm-6.restaurent_intro > p {Ð color: #000000;Ð font-size: 14px;Ð text-
transform: none;ÐÐcol-sm-6.restaurent_intro > p:last-child {Ð color:
#000000;Ð font-size: 15px;Ð font-weight: bold;Ð ÐÐpoint-of-sale .col-
sm-3 p {Ð color: #000000;Ð font-size: 15px;Ð font-weight: 600;Ð text-
transform: capitalize;ÐÐpadding-left{Ð FF–ærÖÆVgC¢ –× ÷'F çC½Ðpadding-
right{Ð FF–ær×&–v‡C¢ –× ÷'F çC½Ðrestaurant_solution {Ð background-
image: url("../img/lines.png");Ð background-position: center 30px;Ð
background-repeat: no-repeat;Ð background-size: 650px 350px;Ð content: "";Ð
    height: 100%;Ð width: 100%;ÐÐsolution_mad {Ð background: rgba(0, 0,
0, 0) url("../img/Cloud-solutions-5.jpg") no-repeat fixed center center /
cover ;ÐÐ*------------------radio Buttons----------------*/Ðradio_sty ul{Ð
list-style: none;Ð height: 100%;Ð width: 100%;Ð margin: 0;Ð padding: 0;ÐÐ
.radio_sty ul li{Ð border-bottom: 1px dashed #ccc;Ð color: #cf0a2c;Ð
display: block;Ð float: left;Ð height: auto;Ð position: relative;Ð
width: 100%;ÐÐradio_sty ul li input[type=radio]{Ð position: absolute;Ð
visibility: hidden;ÐÐradio_sty ul li label{Ð display: block;Ð position:
relative;Ð font-weight: 300;Ð font-size: 1.35em;Ð padding: 7px 0 0 45px;Ð
margin: 10px auto 5px;Ð height: 30px;Ð z-index: 9;Ð cursor: pointer;Ð -webkit-
transition: all 0.25s linear;ÐÐradio_sty ul li:hover label{Ð6öÆ÷#¢ 3 ½Ð
.radio_sty ul li .check{Ð border: 2px solid #cf0a2c;Ð border-radius: 100%;Ð
    display: block;Ð height: 30px;Ð left: 2px;Ð position: absolute;Ð
top: 24px;Ð transition: border 0.25s linear 0s;Ð width: 30px;Ð z-index:
5;ÐÐradio_sty ul li:hover .check{Ð border: 4px solid #000;ÐÐradio_sty ul
li .check::before{Ð border-radius: 100%;Ð content: "";Ð display: block;Ð
    height: 16px;Ð left: 4px;Ð margin: auto;Ð position: absolute;Ð
top: 4px;Ð transition: background 0.25s linear 0s;Ð -webkit-transition:
background 0.25s linear;Ð width: 16px;ÐÐradio_sty input[type=radio]:checked
~ .check{Ð border: 3px solid #cf0a2c;ÐÐradio_sty input[type=radio]:checked
~ .check::before{Ð background: #cf0a2c;ÐÐradio_sty input[type=radio]:checked
~ label{Ð color: #cf0a2c;ÐÐ*==========================Radio
payments==============================*/Ðpayment_radios{Ð ÷6–F–öã§&VÆ F–fS½Ð
.payment_radios input[type=radio]{Ð position: absolute;Ð visibility: hidden;ÐÐ
.payment_radios label {Ð cursor: pointer;Ð display: inline-block;Ð font-
size: 17px;Ð font-weight: 600;Ð height: 30px;Ð margin: 10px auto 5px;Ð
    padding: 13px 0 40px 50px;Ð position: relative;Ð z-index: 9;Ð -
webkit-transition: all 0.25s linear;ÐÐpayment_radios .check {Ð border: 2px
solid #cf0a2c;Ð border-radius: 100%;Ð display: block;Ð height: 30px;Ð
left: 10px;Ð position: absolute;Ð top: 20px;Ð transition: border 0.25s
linear 0s;Ð width: 30px;Ð z-index: 5;ÐÐpayment_radios .check {Ð border:
4px solid #000;ÐÐpayment_radios .check::before {Ð border-radius: 100%;Ð
content: "";Ð display: block;Ð height: 16px;Ð left: 4px;Ð margin:
auto;Ð

position: absolute;Ð top: 4px;Ð transition: background 0.25s linear 0s;Ð -webkit-transition: background 0.25s linear;Ð width: 16px;ÐÐ .payment_radios input[type=radio]:checked ~ .check {Ð border: 3px solid #cf0a2c;ÐÐpayment_radios input[type=radio]:checked ~ .check::before{Ð background: #cf0a2c;ÐÐpayment_radios input[type=radio]:checked ~ label{Ð color: #cf0a2c;ÐÐ*==========End Radio Payments==========*/Ðloader{Ð ÷6–F–öã¢ f–†VC½ÆVgC¢ ƒ½F÷ ¢ 0px;Ð¢Ö–æFWƒ¢ “”“”“”½v–GFƒ¢ S½†V–v‡C¢ S½& 6¶w&÷VæC¢ W&Â,rââöÆö FW"æv–br’ center no-repeat;Ð& 6¶w&÷VæB×6–¦S¢ cG , cG ƒ½Ðrow.listcuistions a ,.listcuistion a{Ð color: #353535;Ð display: inline-block;Ð font-size: 16px;Ð height:25px;Ð transition:.5s all;Ð letter-spacing: 1px;Ð margin-bottom: 5px;Ð padding-bottom: 4px;Ð text-decoration:none;Ð margin-top:5px;ÐÐCuisines-top .col-md-12 a {Ð Ð border: 2px solid;Ð color: #cf0a2c;Ð display: table;Ð font-size: 15px;Ð height: 40px;Ð margin: 30px auto 0;Ð padding: 8px;Ð text-align: center;Ð Ð width: 180px;ÐÐrow.listcuistions ul li a:hover ,.row.listcuistion ul li a:hover {Ð color: rgb(207,10,44) !important;Ð7W'6÷#¢ ö–çFW#½&÷&FW"Ö&÷GFöÓ£ , 6öÆ–B rgb(207,10,44) ;ÐÐcontacts .box_style_2 p {Ð margin-bottom: 0;Ð padding: 10px 16px;ÐÐrow.listcuistion ul li {Ð list-style: outside none none;ÐÐ .row.listcuistions ul li {ÐÆ–7B×7G–ÆS¢ ÷WG6–FR æöæR æöæS½Ð .container.margin_60.Cuisines-topÐÐ FF–ær×F÷ £ ½Ð #total,#subtotal,#delivery_cost {Ð display: inline-block;ÐÐ #complete_form .btn_full:hover {Ð background-color: #333;ÐÐ #complete_form .btn_full {Ð background-color: #cf0a2c;ÐÐ #complete_form .btn_full i {Ð margin: 0 5px;ÐÐtab-2 h4.text-center span i.fa {Ð margin: 0 2px 0 3px;ÐÐchat-room {Ð bottom: -20px;Ð position: fixed;Ð right: 45px;Ð width: 330px;Ð z-index: 999;ÐÐhide-panel-for-chatÐÐ display:none;}ÐÐhide_show{ÐF–7 Ç“¦æöæS½Ðchat-room span.fa.fa-minus-circle,.chat-room span.fa.fa-plus-circle {Ð cursor: pointer;Ð display: inline-block;Ð font-size: 17px;Ð margin-top: 2px;ÐÐchat-room .glyphicon-comment {Ð float: left;Ð font-size: 20px;Ð margin: 0 8px 0 -3px;ÐÐchat-body.panel-body {Ð height: 330px;Ð padding: 10px !important;ÐÐchat-body.panel-body {Ð max-height: 352px;Ð overflow-x: hidden;Ð overflow-y: auto;ÐÐpanel-footer.chat-footer {Ð padding: 5px 0;ÐÐpanel-footer.chat-footer button {Ð height: 40px;Ð background: #cf0a2c none repeat scroll 0 0;ÐÐchatÐÐ list-style: none;Ð margin: 0;Ð padding: 0;ÐÐchat liÐÐ box-shadow: 0 0 6px rgba(0, 0, 0, 0.22);Ð margin-bottom: 10px;Ð padding: 5px;ÐÐ .chat li:last-childÐÐ margin-bottom: 10px;Ð padding-bottom: 5px;Ð border-bottom: none;ÐÐchat li.left .chat-bodyÐÐ margin-left: 60px;ÐÐchat li.right .chat-bodyÐÐ margin-right: 60px;ÐÐchat li .chat-body pÐÐ margin: 0;Ð color: #777777;ÐÐ::-webkit-scrollbar-trackÐÐ -webkit-box-shadow: inset 0 0 6px rgba(0,0,0,0.3);Ð background-color: #F5F5F5;ÐÐ::-webkit-scrollbarÐÐ width: 12px;Ð background-color: #F5F5F5;ÐÐ::-webkit-scrollbar-thumbÐÐ -webkit-box-shadow: inset 0 0 6px rgba(0,0,0,.3);Ð background-color: #555;ÐÐ .twitter-typeahead {Ð display: block !important;ÐÐtt-dataset-topics {Ð margin-left: 15px;ÐÐhelp-buttons {Ð margin-top: 15px;ÐÐchat-room .panel-heading {Ð background: #cf0a2c none repeat scroll 0 0;Ð border-color: #cf0a2c;ÐÐinstruction {Ð color: #7a715d;Ð font-style: italic;ÐÐcol-md-8.customer-profile-setting input {Ð border: 1px solid #cccccc;Ð color: #8e969d;Ð height: 34px;Ð padding: 6px 12px;Ð transition: border-color 0.15s ease-in-out 0s, box-shadow 0.15s ease-in-out 0s;Ð width: 55%;ÐÐcol-md-8.customer-profile-setting h3 {Ð color: #1b2d3b;Ð font-weight: 400;ÐÐ .customer-profile-setting .form-group > label {Ð color: #000000;Ð font-size: 17px;Ð margin: 0;ÐÐorder_process.prfl tbody tr:nth-child(2n+1) {Ð background-color: #f9f9f9;ÐÐadd_address .modal-content ,#addcard .modal-content{Ð background-color: #f9f9f9;Ð border-radius: 0;ÐÐ #add_address .close ,#addcard .close{Ð border: 1px solid black;Ð border-radius: 50%;Ð height: 20px;Ð line-height: 0;Ð position: absolute;Ð right: 16px;Ð top: 25px;Ð transition: all 0.5s ease 0s;Ð width: 20px;ÐÐ #add_address h4, #addcard h4{Ð

font-size: 26px;Ð text-align: center;ÐÐ
#add_address .modal-body,#addcard .model-body {Ð padding: 20px 25px;ÐÐ
#order_process button.btn-lg ,#addcard button.btn-lg{Ð background-color:
#cf0a2c;Ð border: medium none;Ð border-radius: 0;Ð display: inline-
block;Ð float: right;ÐÐaddcard .modal-header .close > span {Ð display:
block;Ð margin-top: -2px;ÐÐparallax-window.my_profile{ÐÖ–âÖ†V–v‡C¢ #S ƒ½Ð
.modal.fade.personal-info.in .modal-content {Ð& 6¶w&÷VæBÐ
color:rgb(249,249,249);Ð&÷&FW"×& F—W3¢ ½ÐÐpersonal-info .modal-header {Ð
border: medium none;Ð text-align: center;ÐÐchangepassword-content .modal-
header {Ð border: medium none;Ð text-align: center;ÐÐmodal.fade.personal-
info.in .modal-content #update-button{Ð& 6¶w&÷VæBÖ6öÆ÷#§&v"ƒ# rÃ ÃCB“½
color:white;Ð.btn.btn-primary.btn-lg.editifo-button {Ð border-radius: 2px !
important;Ð padding: 8px;Ð margin-right: 2%;ÐÐlookup_field button {Ð
background-color: #cf0a2c;Ð border: medium none;Ð border-radius: 0;Ð
float: right;Ð padding: 10px 0;Ð width: 35%;ÐÐlookup_field input {Ð
float: left;Ð margin-bottom: 20px;Ð width: 60%;ÐÐlookup_field
#idpc_error_message {Ð float: left;Ð width: 100%;ÐÐorder_process table {Ð
float: left;Ð margin-top: 15px;Ð width: 100%;ÐÐform-group.address_css
{Ð float: left;Ð width: 100%;ÐÐmodal-content.changepassword-content {Ð
background-color:rgb(249,249,249);Ð &÷&FW"×& F—W3¢ ½ÐÐmodal-
content.changepassword-content #update-button {Ð background: rgb(207,10,44)
none repeat scroll 0 0;Ð color: #ffffff;Ð font-size: 17px;ÐÐcustomer-
profile-setting .table td a {Ð cursor: pointer;ÐÐchangeimg > img {Ð
border: 2px solid;Ð border-radius: 50%;Ð box-shadow: 0 0 6px rgba(0, 0,
0, 0.22);Ð width: 30%;ÐÐchangeimg {Ð text-align: center;ÐÐchangeimg >
input {Ð margin: 2% auto auto 30%;ÐÐprofile_left_side li i {Ð width: 30px;Ð
}ÐchangePassword {Ð cursor: pointer;ÐÐprofilefront-img > img {Ð border:
2px solid #ffffff;Ð border-radius: 50%;Ð box-shadow: 0 0 6px rgba(0, 0,
0, 0.22);Ð margin-top: 2%;Ð padding: 8px;Ð width: 13%;ÐÐprofilefront-
img {Ð text-align: center;Ð padding: 25px 0;ÐÐprofilefront-img > h2 {Ð
color: #ffffff;Ð font-size: 19px;Ð font-weight: 800;Ð margin-top: 4px;Ð
text-transform: capitalize;ÐÐ*------------------radio
Buttons----------------*/Ðradio_sty ul{Ð list-style: none;Ð height: 100%;Ð
width: 100%;Ð margin: 0;Ð padding: 0;ÐÐradio_sty ul li {Ð border-bottom:
1px dashed #ccc;Ð color: #cf0a2c;Ð display: block;Ð float: left;Ð
height: auto;Ð position: relative;Ð width: 100%;Ð min-height: 60px;ÐÐ
.radio_sty ul li input[type=radio]{Ð position: absolute;Ð visibility: hidden;ÐÐ
.radio_sty ul li label{Ð display: block;Ð position: relative;Ð font-weight:
400;Ð font-size: 1.35em;Ð padding: 7px 0 0 45px;Ð margin: 10px auto 5px;Ð
height: 30px;Ð z-index: 9;Ð cursor: pointer;Ð -webkit-transition: all 0.25s
linear;ÐÐradio_sty ul li:hover label{Ð6öÆ÷#¢ 3 ½ÐÐradio_sty ul li .check {Ð
border: 2px solid #cf0a2c;Ð border-radius: 100%;Ð display: block;Ð
height: 30px;Ð left: 2px;Ð position: absolute;Ð top: 15px;Ð
transition: border 0.25s linear 0s;Ð width: 30px;Ð z-index: 5;ÐÐradio_sty
ul li:hover .check {Ð border: 4px solid #000;ÐÐradio_sty ul li .check::before
{Ð border-radius: 100%;Ð content: "";Ð display: block;Ð height: 16px;Ð
left: 4px;Ð margin: auto;Ð position: absolute;Ð top: 4px;Ð
transition: background 0.25s linear 0s;Ð -webkit-transition: background
0.25s linear;Ð width: 16px;ÐÐradio_sty input[type=radio]:checked ~ .check {Ð
border: 3px solid #cf0a2c;ÐÐradio_sty input[type=radio]:checked
~ .check::before{Ð background: #cf0a2c;ÐÐradio_sty input[type=radio]:checked
~ label{Ð color: #cf0a2c;ÐÐpre_order_dv p {Ð margin-left: 44px;ÐÐdate_time
select {Ð margin-bottom: 15px;ÐÐorder_detail .pre_order .back_white > h3 {Ð
margin-top: 4px;ÐÐorder_msg > span {Ð color: #cf0a2c;Ð display:
inline-block;Ð font-size: 16px;Ð padding: 11px 20px;ÐÐorder_msg >
span::before {Ð border-bottom: 8px solid rgba(0, 0, 0, 0);Ð border-left:
11px solid #cf0a2c;Ð border-top: 8px solid rgba(0, 0, 0, 0);Ð content: "";Ð
left: 2px;Ð position: absolute;Ð top: 15px;ÐÐorder_msg > span {Ð
color: #cf0a2c;Ð cursor: pointer;Ð display: inline-block;Ð font-size:
16px;Ð

padding: 11px 20px;Ð position: relative;ÐÐpre_order button {Ð
background-color: #cf0a2c;Ð border: medium none;Ð border-radius: 0;Ð
margin-top: 20px;Ð transition: all 0.4s ease 0s;Ð color:#fff;ÐÐpre_order
button:hover {Ð background-color:#333333;Ð color:#fff;ÐÐpre_order
textarea{ÐÖ ,×v–GFƒ¢ S½Ð*============================Order
Detail==========================*/Ðorder_detail .order_dt_tb img {Ð
display: table;Ð height: 100px;Ð margin: 0 auto;Ð width: 110px;Ð
background-color: #f7f7f7;ÐÐorder_detail .order_dt_tb h3 {Ð margin: 5px 0
8px;ÐÐorder_detail .rating i {Ð color: #f7f7f7;Ð font-size: 15px;ÐÐ
.order_detail .rating i.voted {Ð color: #f4f401;ÐÐrating #rating_account {Ð
color: #434343;Ð display: inline-block;Ð margin: 0 6px;ÐÐ
.order_detail .table td {Ð display: table-cell;Ð vertical-align: middle;ÐÐ
.order_detail .table td h3 {Ð font-size: 17px;Ð font-weight: 700;ÐÐ
.row.coupen .col-sm-12 {Ð margin-top: -18px;Ð padding: 0 28px;ÐÐ
.row.coupen h2 {Ð color: #777777;Ð font-size: 17px;Ð font-weight: 700;ÐÐ
.row.coupen input {Ð border-radius: 0;Ð height: 34px;Ð width: 50%;Ð
float: left;ÐÐrow.coupen button {Ð background:#cf0a2c none repeat scroll 0
0;Ð border: 1px none;Ð color: #ffffff;Ð font-size: 13px;Ð margin-
left: 6px;Ð padding: 7px 17px;ÐÐrow.deliver{Ð padding: 5px 30px 0 0;ÐÐ
.row.total{Ð font-size: 18px;Ð font-weight: 700;Ð padding: 5px 30px 0
0;Ð text-align: right;ÐÐrow.deliver .col-sm-10 {Ð text-align: center;ÐÐ
.row.total.delivery {Ð font-weight: 300;ÐÐcoupen button:hover {Ð
background: #333333 none repeat scroll 0 0;Ð transition: all 0.4s ease 0s;ÐÐ
.order_detail .table td i {Ð border: 1px solid #bfbfbf;Ð border-radius:
50%;Ð color: #cf0a2c;Ð cursor: pointer;Ð display: block;Ð font-size:
16px;Ð height: 25px;Ð padding: 3px 0 0;Ð text-align: center;Ð width:
25px;ÐÐorder_detail .table.html tr td {Ð padding: 10px;ÐÐ
.order_detail .table td i:hover {Ð color: #cf0a2c;Ð transition: all 0.4s
ease 0s;ÐÐprofile_left_side > li a:hover {Ð background: #ffffff none repeat
scroll 0 0;Ð color: #d52846;Ð transition: all 0.2s ease-in-out 0s;ÐÐ
#price_itm {Ð ÷6—F–öã§&VÆ F—fS½Ðprice_itm strong{Ð position: absolute;Ð
right: 10px;Ð top: 12px;ÐÐcheck-payment-method .side-left h2 {Ð font-
size: 18px;Ð font-weight: 600;Ð text-align: left;ÐÐcheckout-customer-
details {Ð margin: 0;Ð position: relative;ÐÐcheckout-customer-details dt {Ð
color: #000000;Ð font-size: 13px;Ð font-weight: 800;Ð left: 0;Ð
margin-bottom: 5px;Ð position: absolute;Ð width: 150px;ÐÐcheckout-
customer-details dd {Ð margin-bottom: 10px;Ð margin-left: 160px;Ð font-
size: 14px;ÐÐcheckout-form-totals-body {Ð float: right;Ð width: 370px;ÐÐ
.checkout-form-totals-body .well.well.well {Ð background: #e9e7e1 none
repeat scroll 0 0;ÐÐcheckout-form-totals .well {Ð background-color: #f3f3f3;Ð
border: medium none;Ð border-radius: 2px;Ð box-shadow: none;Ð font-
size: 18px;Ð font-weight: 700;Ð margin-bottom: 20px;Ð padding: 14px
20px;ÐÐterms-and-conditions-message, .terms-and-conditions-message a {Ð
color: #a39c90;Ð font-size: 15px;ÐÐterms-and-conditions-message a {Ð text-
decoration: underline;ÐÐcheckout-form-totals-body .btn {Ð background-color:
#cf0a2c;Ð border-radius: 0;Ð color: #ffffff;Ð font-size: 20px;Ð font-
weight: 800;Ð padding: 10px;ÐÐform-input-errors-container {Ð color:
#a39c90;Ð font-size: 15px;ÐÐcredit-card {Ð background: #ffffff none
repeat scroll 0 0;Ð padding: 5px 20px;ÐÐcredit-card label {Ð margin: 0;Ð
padding: 0;ÐÐpayment-type-wrapper > img {Ð width: 10%;ÐÐ
#pay_after_data .payment-type-extras > p {Ð color: #a39c90;Ð font-size:
18px;ÐÐpay_after_data {Ð margin: 0 0 15px;ÐÐpay_after_data .title {Ð font-
size: 17px;Ð font-weight: 700;ÐÐtermandcondition .box_style_1 {Ð padding:
0 20px;ÐÐtermandcondition .box_style_1 .title {Ð border-bottom: 1px solid
#e9e4dc;Ð font-size: 22px;Ð line-height: 22px;Ð padding-bottom: 10px;Ð
font-weight: 600;ÐÐterm-start > h2 {Ð color: #c8181b;Ð font-size:
16px;Ð font-weight: bold;Ð Ð margin-top: 1px;ÐÐ
.termandcondition .box_style_1 > p {Ð font-size: 15px;ÐÐ
.solution_mad .promotions .sub_content {Ð padding: 10% 10% 5%;ÐÐterm-
sidebar > ul li {Ð

border-bottom: 1px solid #efefef;Ð font-size: 16px;ÐÐ
.gettitleÐÐfont-size: 17px;Ð font-weight: 700;Ð float: left;Ð margin-
top: 28px;}Ðselect-customer-address button {Ð border-radius: 3px;Ð font-
size: 15px;Ð padding: 9px;ÐÐselect-customer-address {Ð border-bottom: 1px
dashed #cccccc;Ð display: block;Ð float: left;Ð padding-bottom: 20px;Ð
width: 100%;ÐÐsubmitaddress {Ð background-color: #cf0a2c;Ð border-
radius: 0;Ð color: #ffffff;Ð font-size: 19px;Ð padding: 6px;Ð width:
100%;ÐÐexist_address_data .col-sm-6 {Ð padding-left: 0;ÐÐbtn_full.confirm-
button-checkout{Ð background: #cf0a2c none repeat scroll 0 0;Ð margin-
top: 10px;ÐÐbtn_full_outline.confirm-button-back {Ð border-color: #cf0a2c;Ð
color: #cf0a2c;ÐÐaddNewadd #lookup_field input{ÐÖ &v–ã¢ ½ÐaddNewadd
#lookup_field select {Ð float: left;Ð margin-top: 20px;Ð width: 100%;ÐÐ
.addNewadd #lookup_field #idpc_error_message {Ð margin-bottom: 0;Ð margin-
top: 15px;ÐÐbox_style_2.back_white.check-adress-book > h2 {Ð font-size:
13px;Ð font-weight: 700;Ð margin: 0;Ð text-transform: inherit;ÐÐaddress-
book-detail {Ð margin: 0;Ð position: relative;ÐÐaddress-book-detail dt {Ð
color: #000000;Ð font-size: 17px;Ð font-weight: 700;Ð left: 0;Ð
margin-bottom: 5px;ÐÐaddress-book-detail dd {Ð font-size: 14px;Ð margin-
bottom: 10px;ÐÐbox_style_2.back_white.check-adress-book {Ð box-shadow: 0 0
1px 0 #e6e5e1;ÐÐorder_detail table .bootstrap-touchspin input.add {Ð
background-color: #fafafa;Ð height: 35px;Ð padding: 0;Ð text-align:
center;ÐÐorder_detail table .bootstrap-touchspin button {Ð background-
color: #cf0a2c;Ð border: medium none;Ð border-radius: 0;Ð color:
#ffffff;Ð font-size: 16px;Ð font-weight: bold;Ð height: 35px;Ð
padding: 0;Ð width: 35px;ÐÐsection.restaurant_bg {Ð background-attachment:
scroll;Ð background-repeat: no-repeat;Ð background-size: 100% 100%;ÐÐ
.browsemore {Ð padding: 15px;Ð margin:40 0 !important;ÐÐ
.browsemore .table tr td {Ð border: medium none;ÐÐbrowsemore .table.table-
condensed a {Ð color: #656565;ÐÐbrowsemore h2 {Ð padding: 15px;Ð text-
align: center;ÐÐbrowsemore .browsealfha {Ð background-color: #efefef;Ð
border: 1px solid #cdcdcd;Ð border-radius: 50%;Ð box-shadow: 0 0 6px
#ececec;Ð font-size: 21px;Ð height: 50px;Ð margin: 30px auto 20px;Ð
padding-top: 11px;Ð text-align: center;Ð width: 50px;ÐÐ
.browsemore .box_style_2.back_white {Ð border: medium none;ÐÐ
.browsemore .table.table-condensed a:hover {Ð color: rgb(207,10,44);Ð
text-decoration: underline;Ð transition: all 0.2s ease 0s;ÐÐrestaurent-
content-cousine > h1 {Ð color: #ffffff;Ð padding-top: 8%;Ð text-align:
center;ÐÐrestaurent-content-cousine > p {Ð color: #ffffff;Ð font-size:
15px;Ð text-align: center;ÐÐmaduber-takeaway {Ð background-image: url("../
img/cuisines.jpg");Ð height: 300px;ÐÐmaduber-takeaway.location {Ð
background-image: url("../img/location-restaurant.jpg");ÐÐno-m {Ð margin: 0;Ð
}Ðno-m span {Ð font-size: 15px;ÐÐtab21 #order_product td {Ð padding: 13px;Ð
}Ðtable-striped > tbody > tr:nth-of-type(2n+1) {Ð background-color: #f9f9f9;Ð
}Ðtab21 h2 {Ð font-size: 23px;Ð margin: 0;ÐÐrow.order-invoice {Ð font-
size: 13px;Ð margin-bottom: 15px;Ð margin-top: 15px;ÐÐtab21 .table.table-
striped th {Ð Ð color: black;Ð padding: 14px;ÐÐorder-total-info h4 {Ð
font-size: 16px;Ð font-weight: 700;Ð margin-top: 5px;ÐÐorder-total-
info .col-sm-12 {Ð margin-bottom: 20px;ÐÐorder-total-info .col-sm-12 {Ð
border-bottom: 1px solid #f7f7f7;Ð margin-bottom: 20px;Ð margin-left:
-12px !important;Ð padding-bottom: 4px;Ð padding-left: 0;Ð padding-
right: 0;ÐÐcustomer_address strong {Ð color: #888888;Ð font-size: 15px;ÐÐ
#total_amount.text-success {Ð color: #3c763d;Ð font-size: 25px;ÐÐnav-
tabs.nav-justified > li > a {Ð background: #f5f5f5 none repeat scroll 0 0;ÐÐ
border-radius: 0;Ð color: #000000;Ð padding: 16px;ÐÐnav-tabs
li.active > a {Ð color: rgb(207,10,44) !important;ÐÐ*==================Chat
Room Css====================*/Ðchat-container {Ð width: 100%;Ð margin:
7px 0;ÐÐ .top-header {Ð background-color: #cf0a2c;Ð border-bottom: 4px
solid #f1454e;Ð color: white;Ð padding: 6px 10px;Ð position: relative;Ð
overflow: hidden;ÐÐ header.top-header .fa.fa-comments {Ð font-size:
15px;Ð

margin: 0 3px 0 10px;ÐÐÐchat_area .chat_send {Ð background-color: #ffffff;Ð border-radius: 50%;Ð box-shadow: 0 1px 2px rgba(0, 0, 0, 0.2);Ð cursor: pointer;Ð font-size: 15px;Ð height: 35px;Ð padding: 8px 0 0;Ð position: absolute;Ð right: 13px;Ð text-align: center;Ð top: 25px;Ð width: 35px;Ð z-index: 1;ÐÐchat_area {Ð background-color: #f7f7f7;Ð border-bottom: 1px solid #dddddd;Ð border-left: 1px solid #dddddd;Ð border-right: 1px solid #dddddd;Ð margin-top: 9px;Ð padding: 12px 0 12px 13px;ÐÐchat_area .chat_txt {Ð border: 1px solid #cccccc;Ð max-height: 85px;Ð min-height: 70px;Ð overflow-x: hidden;Ð overflow-y: auto;Ð resize: none;Ð width: 90%;ÐÐ .top-header-tit {Ð display: inline;Ð font-size: 14px;Ð }Ð .top-header .typicons-message {Ð display: inline-block;Ð padding: 2px 5px 2px 5px;Ð font-size: 20px;Ð position: relative;Ð top: 5px;Ð }Ð .top-header .typicons-minus {Ð position: relative;Ð top: 3px;Ð font-size: 15px;Ð cursor:pointer;Ð }Ð .top-header .typicons-times{Ð position: relative;Ð top: 3px;Ð font-size: 15px;Ð cursor:pointer;Ð }Ð .top-header .left {Ð float: left;Ð }Ð .top-header .right {Ð float: right;Ð padding-top: 5px;Ð }Ð .top-header > * {Ð position: relative;Ð }Ð .top-header::before {Ð content: '';Ð position: absolute;Ð top: -100%;Ð left: 0;Ð right: 0;Ð bottom: -100%;Ð opacity: 0.25;Ð background-color: #404040Ð }Ðchat-box {Ð background-color: #f8f8f8;Ð border: 1px solid #e3e3e3;Ð height: 300px;Ð list-style: outside none none;Ð margin: -10px 0;Ð overflow-x: hidden;Ð overflow-y: auto;Ð padding: 10px 8px 50px;ÐÐ .chat-box li {Ð padding: 0.5rem;Ð overflow: hidden;Ð display: flex;Ð }Ð .chat-box .avatar-icon {Ð width: 40px;Ð position: relative;Ð }Ð .chat-box .avatar-icon i {Ð background-color: #1469a6;Ð color: #ffffff;Ð display: block;Ð font-size: 18px;Ð height: 40px;Ð line-height: 2;Ð text-align: center;Ð width: 100%;ÐÐ .another .avatar-icon:after {Ð content: '';Ð position: absolute;Ð top: 0;Ð right: 0;Ð width: 0;Ð height: 0;Ð border: 5px solid white;Ð border-left-color: transparent;Ð border-bottom-color: transparent;Ð }Ð .me {Ð justify-content: flex-end;Ð align-items: flex-end;Ð }Ð .me .messages {Ð order: 1;Ð border-bottom-right-radius: 0;Ð }Ð .me .avatar-icon {Ð order: 2;Ð }Ð .me .avatar-icon:after {Ð content: '';Ð position: absolute;Ð bottom: 0;Ð left: 0;Ð width: 0;Ð height: 0;Ð border: 5px solid white;Ð border-right-color: transparent;Ð border-top-color: transparent;Ð box-shadow: 1px 1px 2px rgba(0, 0, 0, 0.2);Ð }Ð .messages {Ð background: white;Ð padding: 10px;Ð border-radius: 2px;Ð box-shadow: 0 1px 2px rgba(0, 0, 0, 0.2);Ð }Ð .messages p {Ð font-size: 12px;Ð margin: 0 0 0.2rem 0;Ð }Ð .messages time {Ð color: #929292;Ð font-size: 10px;ÐÐ .setting{Ð background-color: #e5e5e5;Ð height: 32px;Ð padding-top: 2px;Ð border-bottom: 1px solid rgba(0,0,0,.1);Ð }Ð .setting .left {Ð float: left;Ð }Ð .setting .right {Ð float: right;Ð }Ð .iconicstroke-user{Ð font-size: 22px;Ð position: relative;Ð top: 4px;Ð left: 10px;Ð color: #414141;Ð cursor:pointer;Ð}Ð.typicons-cog{Ð font-size: 23px;Ð position: relative;Ð top: 7px;Ð right: 4px;Ð color: #414141;Ð cursor:pointer;Ð}Ð.fontawesome-facetime-video{Ð font-size: 18px;Ð position: relative;Ð top: 3px;Ð color: #414141;Ð left: 5px;Ð cursor:pointer;Ð}Ð.iconicstroke-user:hover, .typicons-cog:hover,.fontawesome-facetime-video:hover{Ð color:#000000;ÐÐ #botbuttons .first-line .btn-danger {Ð float: right;ÐÐfeedback-star .fa {Ð font-size: 16px;Ð color: #e2e2e2;ÐÐfeedback-star .fa.voted {Ð color: #ECEC10;ÐÐfeedback-in-quote i.fa {Ð margin: 0 5px;ÐÐset-message-feedback .feedback-in-quote {Ð margin-top: -5px;ÐÐpadding-left{Ð padding-left:0 !important;ÐÐpadding-right{Ð padding-right:0 !important;ÐÐremove-item i {Ð top: -8px;Ð color:#ff0000;ÐÐbotbuttons .second-line button {Ð margin-top: 12px;Ð padding: 6px 18px;ÐÐbotbuttons .first-line button {Ð width: 100% !important;Ð margin-top: 5px;ÐÐfeedback-star .messages {Ð border-radius: 0;Ð margin-top: 5px;Ð text-align: right;ÐÐ .messages .msg_inner {Ð margin: 10px 0;ÐÐmsg_inner .name_s {Ð float: left;Ð }Ðset-message-feedback blockquote {Ð border: medium none;Ð padding: 0;ÐÐ .set-message-feedback .top-header {Ð

margin-bottom: 10px;Ð margin-top: 8px;Ð padding: 6px;ÐÐfeedback-in-quote {Ð margin-top: 10px;ÐÐtab23 blockquote p.fdb-date {Ð font-size: 16px;ÐÐOrderDetailModal .modal-header {Ð border: none;Ð padding: 0;ÐÐOrderDetailModal .close {Ð border: 1px solid #000000;Ð border-radius: 50%;Ð height: 25px;Ð position: absolute;Ð right: 20px;Ð top: 20px;Ð width: 25px;Ð z-index: 10;ÐÐ #scroll_down .fa.fa-comment {Ð margin: 0 4px;ÐÐpost_name.listcuistions ul li {Ð background-color: #ffffff;Ð border-radius: 2px;Ð box-shadow: 0 0 2px 0 #e6e5e1;Ð float: left;Ð margin: 1px;Ð padding: 15px;Ð width: 33%;ÐÐlistcuistions.post_name a:hover {Ð color: rgb(207,10,44);Ð transition: all 0.2s ease 0s;ÐÐpost_name.listcuistions ul li i {Ð float: right;Ð font-size: 17px;ÐÐlistcuistions.post_name > ul {Ð margin-left: -13px;Ð ÐÐlistcuistions.post_name a {Ð color: #000000;ÐÐ .row.listcuistions.post_name {Ð padding-bottom: 20px;ÐÐmodal-dialog.custom_width {Ð width: 500px;ÐÐtabfeedback .lead h2 {Ð font-size: 17px;ÐÐtabfeedback .lead{Ð text-align: center;ÐÐtabfeedback span.glyphicon {Ð color:#cf0a2c;ÐÐtabfeedback .lead:nth-child(2) {Ð border-left: 1px solid #cccccc;Ð border-right: 1px solid #cccccc;Ð padding-bottom: 16px;ÐÐorder-status .table.table-striped th i {Ð color: rgb(207,10,44);Ð float: right;Ð font-size: 25px;ÐÐorder-status .table.table-striped th {Ð padding: 12px;Ð }Ðtable.table-striped span {Ð font-size: 9px;Ð font-style: italic;Ð margin-left: 2%;ÐÐtabfeedback textarea#feedback {Ð max-width: 100%;Ð padding: 4px 7px;Ð min-height: 110px;Ð width: 100%;ÐÐtabfeedback button#feed_sb {Ð background-color: #cf0a2c;Ð border: medium none;Ð color: #ffffff;Ð display: table;Ð font-size: 16px;Ð margin: 20px auto -5px;Ð padding: 9px 0;Ð width: 200px;Ð transition:.4s all;ÐÐtabfeedback button#feed_sb:hover {Ð background-color: #0f0f0f;ÐÐOrderDetailModal .nav-tabs li.active > a {Ð background-color: #ffffff;Ð color: #cf0a2c ! important;ÐÐminimum_order_cl span {Ð margin: 0 0 0 9px;ÐÐminimum_order_cl {Ð position: relative;ÐÐminimum_order_cl > td {Ð bottom: -17px;Ð color: #8b8b8b;Ð font-size: 12px;Ð position: absolute;Ð right: 0;ÐÐtotal {Ð display: block;Ð font-size: 20px;Ð margin: 4px 0;ÐÐcomingsoon {Ð padding-bottom: 30px;Ð padding-top: 30px;Ð text-align: center;ÐÐset-reservation-table-view {Ð padding: 20px;ÐÐsuccess-booking {Ð padding-top: 19px;Ð text-align: center;ÐÐsuccess-booking button {Ð background-color: #cf0a2c;Ð border-radius: 0;Ð color: #ffffff;Ð height: 40px;Ð width: 28%;ÐÐset-reservation-table-view input {Ð border-radius: 0 !important;Ð height: 38px;ÐÐset-reservation-table-view > h2 {Ð font-size: 23px;Ð font-weight: 700;Ð padding-bottom: 15px;Ð text-align: center;ÐÐNext-process {Ð display: none;ÐÐable tbody > tr > td {ÐF—7 Æ “¢ F &ÆRÖ6VÆÃ½fW'F–6 ÂÖ Æ–vã¢ middle !important;ÐÐprofile_img {Ð border: 3px solid #ffffff;Ð border-radius: 50%;Ð box-shadow: 0 0 5px 0 rgba(0, 0, 0, 0.3);Ð display: table;Ð height: 160px;Ð margin: 0 auto 10px;Ð padding: 5px;Ð width: 160px;ÐÐ .profile_img > span {Ð background-position: center center;Ð background-size: cover;Ð border-radius: 50%;Ð display: block;Ð height: 149px;Ð width: 150px;ÐÐsearch-area-dv {Ð background-color: rgba(255, 255, 255, 0.6);Ð display: block;Ð float: left;Ð padding: 25px 0 20px;Ð width: 100%;ÐÐ #thank-u span.pull-right #total {Ð font-size: 18px;ÐÐthank-u #total_tax {Ð text-align: right;ÐÐ*==========Animations Css3==========*/ÐscaleAnimate {Ð animation-name: scale;Ð -webkirgb(207,10,44)me: scale;ÐÐ animation-iteration-count: infinite;Ð -webkit-animation-iteration-count: infinite;ÐÐkeyframes scale {Ð 0% {Ð transform: scale(1);Ð }Ð 50% {Ð transform: scale(1.1); Ð }Ð 100% {Ð transform: scale(1);Ð }ÐÐ-webkit-keyframes scale {Ð 0% {Ð transform: scale(1);Ð }Ð 50% {Ð transform: scale(1.1); Ð }Ð 100% {Ð transform: scale(1);Ð }ÐÐ

public\assets\js\plugins\codemirror\mode\tiddlywiki\tiddlywiki.css

```
span.cm-underlined {Ð text-decoration: underline;ÞÐÐspan.cm-strikethrough {Ð
text-decoration: line-through;ÞÐÐspan.cm-brace {Ð color: #170;Ð font-weight:
bold;ÞÐÐspan.cm-table {Ð color: blue;Ð font-weight: bold;ÞÐ
```

public\assets\js\plugins\codemirror\mode\tiki\tiki.css

.cm-tw-syntaxerror {Ð6öÆ÷#¢ 4ddc½& 6¶w&÷VæBÖ6öÆ÷#¢ 3“ ‚½Ðcm-tw-deleted {ÐFW‡BÐ decoration: line-through;ÐÐcm-tw-header5 {ÐföçB×vV–v‡C¢ &öÆC‚½Ðcm-tw-listitem:first-child { /*Added first child to fix duplicate padding when highlighting*/Ð FF–ærÖÆVgC¢   ƒ‚½Ðcm-tw-box {Ð&÷&FW"×F÷ ×v–GFƒ¢   , important;Ð&÷&FW"×7G–ÆS¢ 6öÆ–C½&÷&FW"×v–GFƒ¢   ƒ½&÷&FW"Ö6öÆ÷#¢ –æ†W&—C‚½Ðcm-tw-underline {ÐFW‡BÖFV6÷& F–öã¢ VæFW&Æ–æS‚½

public\assets\js\plugins\gritter\jquery.gritter.css

/* the norm */Þgritter-notice-wrapper {Þ ÷6—F–öã¦f—†VC½F÷ £C ƒ½&–v‡C£# ƒ½ width:301px;Þ¢Ö–æFWƒ£“”“”Þ -webkit-animation-duration: 1s;Þ animation-duration: 1s;Þ -webkit-animation-fill-mode: both;Þ animation-fill-mode: both;Þ -webkit-animation-name: bounceIn;Þ animation-name: bounceIn;ÞÞ @keyframes bounceIn {Þ 0% {Þ opacity: 0;Þ -webkit-transform: scale(.3);Þ -ms-transform: scale(.3);Þ transform: scale(.3);Þ }Þ 50% {Þ opacity: 1;Þ -webkit-transform: scale(1.05);Þ -ms-transform: scale(1.05);Þ transform: scale(1.05);Þ }Þ 70% {Þ -webkit-transform: scale(.9);Þ -ms-transform: scale(.9);Þ transform: scale(.9);Þ }Þ 100% {Þ opacity: 1;Þ -webkit-transform: scale(1);Þ -ms-transform: scale(1);Þ transform: scale(1);Þ }ÞÞgritter-notice-wrapper.top-left {Þ left: 20px;Þ right: auto;ÞÞgritter-notice-wrapper.bottom-right {Þ top: auto;Þ left: auto;Þ bottom: 20px;Þ right: 20px;ÞÞgritter-notice-wrapper.bottom-left {Þ top: auto;Þ right: auto;Þ bottom: 20px;Þ left: 20px;ÞÞgritter-item-wrapper {Þ position:relative;ÞÖ &v–ã£ , ½& 6¶w&÷VæC§W&Â,v–Ö vW2ö–R×7 6W"æv–br“² ð * ie7/8 fix */ÞÞhover .gritter-top {Þò¦& 6¶w&÷VæB× ÷6—F–öã§&–v‡B Ó3 ƒ²¢ÿÞ .gritter-bottom {Þ†V–v‡C£‡ ƒ½Ö &v–ã£ ½ÞÞgritter-item {ÞF—7 Æ “¦&Æö6³½& 6¶w&÷VæBÞ color: rgba(39,58,75,0.8);Þ border-radius: 4px;Þ6öÆ÷#¢6VVS½ FF–æs£ , , 10px 11px;ÞföçB×6—¦S¢ ƒ½ÞÞhover .gritter-item {Þ& 6¶w&÷VæB× ÷6—F–öã§&–v‡B -40px;ÞÞgritter-item p {Þ FF–æs£ ½Ö &v–ã£ ½v÷&B×w& ¦'&V ²×v÷&C½ÞÞgritter-item a:hover {Þ color: #f8ac59;Þ text-decoration: underline;ÞÞgritter-close {ÞF—7 Æ “¦æöæS½ ÷6—F–öã¦ '6öÇWFS½F÷ £W ƒ½&–v‡C£7 ƒ½& 6¶w&÷VæC§W&Â†–Ö vW2ð gritter.png) no-repeat left top;Þ7W'6÷#§ ö–çFW#½v–GFƒ£3 ƒ½†V–v‡C£3 ƒ½FW‡BÞ indent:-9999em;ÞÞgritter-title {ÞföçB×6—¦S£ ' ƒ½föçB×vV–v‡C¦&öÆC½ FF–æs£ 7px 0;ÞF—7 Æ “¦&Æö6³½ text-transform: uppercase;ÞÞgritter-image {Þv–GFƒ£C‡ ƒ½ height:48px;ÞfÆö C¦ÆVgC½ÞÞgritter-with-image,Þgritter-without-image {Þ FF–æs£ ½ }Þgritter-with-image {Þv–GFƒ£## ƒ½fÆö C§&–v‡C½Ø* for the light (white) version of the gritter notice */Þgritter-light .gritter-item,Þgritter-light .gritter-bottom,Þgritter-light .gritter-top,Þgritter-light .gritter-close {Þ background-image: url(images/gritter-light.png);Þ color: #222;ÞÞ .gritter-light .gritter-title {Þ text-shadow: none;ÞÞ

public\assets\js\plugins\jquery-ui\jquery-ui.css

/*! jQuery UI - v1.10.4 - 2014-01-17Þ http://jqueryui.comÞ Includes: jquery.ui.core.css, jquery.ui.accordion.css, jquery.ui.autocomplete.css, jquery.ui.button.css, jquery.ui.datepicker.css, jquery.ui.dialog.css, jquery.ui.menu.css, jquery.ui.progressbar.css, jquery.ui.resizable.css, jquery.ui.selectable.css, jquery.ui.slider.css, jquery.ui.spinner.css, jquery.ui.tabs.css, jquery.ui.tooltip.css, jquery.ui.theme.cssÞ Copyright 2014 jQuery Foundation and other contributors; Licensed MIT */Ø* Layout helpersÞ----------*/Þui-helper-hidden {ÞF—7 Æ “¢ æöæS½Þ .ui-helper-hidden-accessible {Þ&÷&FW#¢ ½6Æ— ¢ &V7Bƒ “½†V–v‡C¢ ƒ½ margin: -1px;Þ÷fW&fÆ÷s¢ †–FFVã½ FF–æs¢ ½ ÷6—F–öã¢ '6öÇWFS½v–GFƒ¢ ƒ½Þui-helper-reset {ÞÖ &v–ã¢ ½ FF–æs¢ ½&÷&FW#¢ ½÷WFÆ–æS¢ ½Æ–æRÖ†V–v‡C¢ ã3½FW‡BÞ decoration: none;ÞföçB×6—¦S¢ S½Æ—7B×7G–ÆS¢ æöæS½Þui-helper-clearfix:before,Þ .ui-helper-clearfix:after {Þ6öçFVçC¢ "#½F—7 Æ “¢ F &ÆS½&÷&FW"Ö6öÆÆ 6S¢ collapse;ÞÞui-helper-clearfix:after {Þ6ÆV #¢ &÷Fƒ½Þui-helper-clearfix {ÞÖ–âÞ height: 0; /* support: IE7 */ÞÞui-helper-zfix {Þv–GFƒ¢ S½†V–v‡C¢ S½F÷ ¢ 0;ÞÆVgC¢ ½ ÷6—F–öã¢ '6öÇWFS½÷ 6—G“¢ ½f–ÇFW#¤ Ç † „÷ 6—G“Ó “½Þui-front {Þ¢Þ index: 100;ÞØ* Interaction CuesÞ----------*/Þui-state-disabled {Þ7W'6÷#¢ FVf VÇB –× ÷'F çC½Ø* IconsÞ ----------*/Ø* states and images */Þui-icon {ÞF—7 Æ “¢ block;ÞFW‡BÖ–æFVçC¢ Ó“""“— ƒ½÷fW&fÆ÷s¢ †–FFVã½& 6¶w&÷VæB×&W V C¢ æò×&W V C½Ø* Misc visualsÞ----------*/Ø* Overlays */Þui-widget-overlay {Þ ÷6—F–öã¢ f—†VC½F÷ ¢ ½ÆVgC¢ ½v–GFƒ¢ S½†V–v‡C¢ S½Þui-accordion .ui-accordion-header {ÞF—7 Æ “¢ &Æö6³½7W'6÷#¢ ö–çFW#½ ÷6—F–öã¢ relative;ÞÖ &v–â×F÷ ¢ ' ƒ½ FF–æs¢ ãVVÒ ãVVÒ ãVVÒ ãvVÓ½Ö–âÖ†V–v‡C¢ ² ò¢ support: IE7 */ÞÞui-accordion .ui-accordion-icons {Þ FF–ærÖÆVgC¢ "ã&VÓ½Þui-accordion .ui-accordion-noicons {Þ FF–ærÖÆVgC¢ ãvVÓ½Þui-accordion .ui-accordion-icons .ui-accordion-icons {Þ FF–ærÖÆVgC¢ "ã&VÓ½Þui-accordion .ui-accordion-header .ui-accordion-header-icon {Þ ÷6—F–öã¢ '6öÇWFS½ÆVgC¢ ãVVÓ½ top: 50%;ÞÖ &v–â×F÷ ¢ Ó‡ ƒ½Þui-accordion .ui-accordion-content {Þ FF–æs¢ VÒ 2.2em;Þ&÷&FW"×F÷ ¢ ½÷fW&fÆ÷s¢ WFó½Þui-autocomplete {Þ ÷6—F–öã¢ '6öÇWFS½F÷ ¢ 0;ÞÆVgC¢ ½7W'6÷#¢ FVf VÇC½Þui-button {ÞF—7 Æ “¢ –æÆ–æRÖ&Æö6³½ ÷6—F–öã¢ relative;Þ FF–æs¢ ½Æ–æRÖ†V–v‡C¢ æ÷&Ö Ã½Ö &v–â×&–v‡C¢ ã VÓ½7W'6÷#¢ ö–çFW#½ vertical-align: middle;ÞFW‡BÖ Æ–vã¢ 6VçFW#½÷fW&fÆ÷s¢ f—6–&ÆS² ò¢ &VÖ÷fW2 W‡G& width in IE */ÞÞui-button,Þui-button:link,Þui-button:visited,Þui-button:hover,Þ .ui-button:active {ÞFW‡BÖFV6÷& F–öã¢ æöæS½Ø* to make room for the icon, a width needs to be set here */Þui-button-icon-only {Þv–GFƒ¢ "ã&VÓ½Ø* button elements seem to need a little more width */Þutton.ui-button-icon-only {Þ width: 2.4em;ÞÞui-button-icons-only {Þv–GFƒ¢ 2ãFVÓ½Þutton.ui-button-icons-only {Þv–GFƒ¢ 2ãvVÓ½Ø* button text element */Þui-button .ui-button-text {Þ display: block;ÞÆ–æRÖ†V–v‡C¢ æ÷&Ö Ã½Þui-button-text-only .ui-button-text {Þ padding: .4em 1em;ÞÞui-button-icon-only .ui-button-text,Þui-button-icons-only .ui-button-text {Þ FF–æs¢ ãFVÓ½FW‡BÖ–æFVçC¢ Ó“"""""— ƒ½Þui-button-text-icon-primary .ui-button-text,Þui-button-text-icons .ui-button-text {Þ padding: .4em 1em .4em 2.1em;ÞÞui-button-text-icon-secondary .ui-button-text,Þ .ui-button-text-icons .ui-button-text {Þ FF–æs¢ ãFVÒ "ã VÒ ãFVÒ VÓ½Þui-button-text-icons .ui-button-text {Þ FF–ærÖÆVgC¢ "ã VÓ½ FF–ær×&–v‡C¢ "ã VÓ½Ø * no icon support for input elements, provide padding by default */Þnput.ui-button {Þ FF–æs¢ ãFVÒ VÓ½Ø* button icon element(s) */Þui-button-icon-only .ui-icon,Þui-button-text-icon-primary .ui-icon,Þui-button-text-icon-secondary .ui-icon,Þui-button-text-icons .ui-icon,Þui-button-icons-only .ui-icon {Þ ÷6—F–öã¢ '6öÇWFS½F÷ ¢ S S½Ö &v–â×F÷ ¢ Ó‡ ƒ½Þui-button-icon-only .ui-icon {ÞÆVgC¢ S S½Ö &v–âÖÆVgC¢ Ó‡ ƒ½Þui-button-text-icon-primary .ui-button-icon-primary,Þui-button-text-icons .ui-button-icon-primary,Þui-button-icons-only .ui-button-icon-primary {ÞÆVgC¢ ãVVÓ½Þui-button-text-icon-secondary .ui-button-icon-secondary,Þui-button-text-icons .ui-button-icon-secondary,Þui-button-icons-only .ui-button-icon-secondary {Þ&–v‡C¢ ãVVÓ½Ø* button sets */Þ .ui-buttonset {ÞÖ &v–â×&–v‡C¢ w ƒ½Þui-buttonset .ui-button {ÞÖ &v–âÖÆVgC¢ ½ margin-right: -.3em;ÞØ* workarounds */Ø* reset extra padding in Firefox, see h5bp.com/l */Þ

input.ui-button::-moz-focus-inner,Ðutton.ui-button::-moz-focus-
inner {Ð&÷&FW#¢ ½ FF–æs¢ ½ÐÐui-datepicker {Ðv–GFƒ¢ vVÓ½ FF–æs¢ ã&VÒ ã&VÒ ½
display: none;ÐÐÐui-datepicker .ui-datepicker-header {Ð ÷6—F–öã¢ &VÆ F—fS½
padding: .2em 0;ÐÐÐui-datepicker .ui-datepicker-prev,Ðui-datepicker .ui-
datepicker-next {Ð ÷6—F–öã¢ '6öÇWFS½F÷ ¢ ' ƒ½v–GFƒ¢ ã†VÓ½†V–v‡C¢ ã†VÓ½ÐÐui-
datepicker .ui-datepicker-prev-hover,Ðui-datepicker .ui-datepicker-next-hover
{ÐF÷ ¢ ƒ½ÐÐui-datepicker .ui-datepicker-prev {ÐÆVgC¢ ' ƒ½ÐÐui-datepicker .ui-
datepicker-next {Ð&–v‡C¢ ' ƒ½ÐÐui-datepicker .ui-datepicker-prev-hover {ÐÆVgC¢
1px;ÐÐÐui-datepicker .ui-datepicker-next-hover {Ð&–v‡C¢ ƒ½ÐÐui-datepicker .ui-
datepicker-prev span,Ðui-datepicker .ui-datepicker-next span {ÐF—7 Æ “¢ &Æö6³½
position: absolute;ÐÆVgC¢ S S½Ö &v–âÖÆVgC¢ Ó‡ ƒ½F÷ ¢ S S½Ö &v–â×F÷ ¢ Ó‡ ƒ½ÐÐui-
datepicker .ui-datepicker-title {ÐÖ &v–ã¢ "ã6VÓ½Æ–æRÖ†V–v‡C¢ ã†VÓ½FW‡BÐ
align: center;ÐÐÐui-datepicker .ui-datepicker-title select {ÐföçB×6—¦S¢ VÓ½
margin: 1px 0;ÐÐÐui-datepicker select.ui-datepicker-month,Ðui-datepicker
select.ui-datepicker-year {Ðv–GFƒ¢ C’S½ÐÐui-datepicker table {Ðv–GFƒ¢ S½föçBÐ
size: .9em;Ð&÷&FW"Ö6öÆÆ 6S¢ 6öÆÆ 6S½Ö &v–ã¢ ãFVÓ½ÐÐui-datepicker th {Ð
padding: .7em .3em;ÐFW‡BÖ Æ–vã¢ 6VçFW#½föçB×vV–v‡C¢ &öÆC½&÷&FW#¢ ½ÐÐui-
datepicker td {Ð&÷&FW#¢ ½ FF–æs¢ ƒ½ÐÐui-datepicker td span,Ðui-datepicker
td a {ÐF—7 Æ “¢ &Æö6³½ FF–æs¢ ã&VÓ½FW‡BÖ Æ–vã¢ &–v‡C½FW‡BÖFV6÷& F–öã¢ æöæS½ÐÐ
.ui-datepicker .ui-datepicker-buttonpane {Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ö &v–ã¢ ãvVÒ
0 0 0;Ð FF–æs¢ ã&VÓ½&÷&FW"ÖÆVgC¢ ½&÷&FW"×&–v‡C¢ ½&÷&FW"Ö&÷GFöÓ¢ ½ÐÐui-
datepicker .ui-datepicker-buttonpane button {ÐfÆö C¢ &–v‡C½
margin: .5em .2em .4em;Ð7W'6÷#¢ ö–çFW#½ FF–æs¢ ã&VÒ ãfVÒ ã6VÒ ãfVÓ½v–GFƒ¢
auto;Ð÷fW&fÆ÷s¢ f—6–&ÆS½ÐÐui-datepicker .ui-datepicker-buttonpane button.ui-
datepicker-current {ÐfÆö C¢ ÆVgC½ÐÐ* with multiple calendars */Ðui-
datepicker.ui-datepicker-multi {Ðv–GFƒ¢ WFó½ÐÐui-datepicker-multi .ui-
datepicker-group {ÐfÆö C¢ ÆVgC½ÐÐui-datepicker-multi .ui-datepicker-group
table {Ðv–GFƒ¢ “RS½Ö &v–ã¢ WFò ãFVÓ½ÐÐui-datepicker-multi-2 .ui-datepicker-
group {Ðv–GFƒ¢ S S½ÐÐui-datepicker-multi-3 .ui-datepicker-group {Ðv–GFƒ¢ 32ã2S½ÐÐ
.ui-datepicker-multi-4 .ui-datepicker-group {Ðv–GFƒ¢ #RS½ÐÐui-datepicker-
multi .ui-datepicker-group-last .ui-datepicker-header,Ðui-datepicker-
multi .ui-datepicker-group-middle .ui-datepicker-header {Ð&÷&FW"ÖÆVgB×v–GFƒ¢ ½
}ÐÐui-datepicker-multi .ui-datepicker-buttonpane {Ð6ÆV #¢ ÆVgC½ÐÐui-datepicker-
row-break {Ð6ÆV #¢ &÷Fƒ½v–GFƒ¢ S½föçB×6—¦S¢ ½ÐÐ* RTL support */Ðui-
datepicker-rtl {ÐF—&V7F–öã¢ 'FÃ½ÐÐui-datepicker-rtl .ui-datepicker-prev {Ð
right: 2px;ÐÆVgC¢ WFó½ÐÐui-datepicker-rtl .ui-datepicker-next {ÐÆVgC¢ ' ƒ½
right: auto;ÐÐÐui-datepicker-rtl .ui-datepicker-prev:hover {Ð&–v‡C¢ ƒ½ÆVgC¢
auto;ÐÐÐui-datepicker-rtl .ui-datepicker-next:hover {ÐÆVgC¢ ƒ½&–v‡C¢ WFó½ÐÐ
.ui-datepicker-rtl .ui-datepicker-buttonpane {Ð6ÆV #¢ &–v‡C½ÐÐui-datepicker-
rtl .ui-datepicker-buttonpane button {ÐfÆö C¢ ÆVgC½ÐÐui-datepicker-rtl .ui-
datepicker-buttonpane button.ui-datepicker-current,Ðui-datepicker-rtl .ui-
datepicker-group {ÐfÆö C¢ &–v‡C½ÐÐui-datepicker-rtl .ui-datepicker-group-
last .ui-datepicker-header,Ðui-datepicker-rtl .ui-datepicker-group-middle .ui-
datepicker-header {Ð&÷&FW"×&–v‡B×v–GFƒ¢ ½&÷&FW"ÖÆVgB×v–GFƒ¢ ƒ½ÐÐui-dialog {Ð
overflow: hidden;Ð ÷6—F–öã¢ '6öÇWFS½F÷ ¢ ½ÆVgC¢ ½ FF–æs¢ ã&VÓ½÷WFÆ–æS¢ ½ÐÐ
.ui-dialog .ui-dialog-titlebar {Ð FF–æs¢ ãFVÒ VÓ½ ÷6—F–öã¢ &VÆ F—fS½ÐÐui-
dialog .ui-dialog-title {ÐfÆö C¢ ÆVgC½Ö &v–ã¢ ã VÒ ½v†—FR×7 6S¢ æ÷w& ½
width: 90%;Ð÷fW&fÆ÷s¢ †–FFVã½FW‡BÖ÷fW&fÆ÷s¢ VÆÆ— 6—3½ÐÐui-dialog .ui-dialog-
titlebar-close {Ð ÷6—F–öã¢ '6öÇWFS½&–v‡C¢ ã6VÓ½F÷ ¢ S S½v–GFƒ¢ # ƒ½Ö &v–ã¢
-10px 0 0 0;Ð FF–æs¢ ƒ½†V–v‡C¢ # ƒ½ÐÐui-dialog .ui-dialog-content {Ð
position: relative;Ð&÷&FW#¢ ½ FF–æs¢ ãVVÒ VÓ½& 6¶w&÷VæC¢ æöæS½÷fW&fÆ÷s¢
auto;ÐÐÐui-dialog .ui-dialog-buttonpane {ÐFW‡BÖ Æ–vã¢ ÆVgC½&÷&FW"×v–GFƒ¢ ,
0 0;Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ö &v–â×F÷ ¢ ãVVÓ½ FF–æs¢ ã6VÒ VÒ ãVVÒ ãFVÓ½ÐÐui-
dialog .ui-dialog-buttonpane .ui-dialog-buttonset {ÐfÆö C¢ &–v‡C½ÐÐui-
dialog .ui-dialog-buttonpane button {ÐÖ &v–ã¢ ãVVÒ ãFVÒ ãVVÒ ½7W'6÷#¢ ö–çFW#½
}ÐÐui-dialog .ui-resizable-se {Ðv–GFƒ¢ ' ƒ½†V–v‡C¢ ' ƒ½&–v‡C¢ ÓW ƒ½&÷GFöÓ¢
-5px;Ð& 6¶w&÷VæB× ÷6—F–öã¢ g , g ƒ½ÐÐui-draggable .ui-dialog-titlebar {Ð
cursor: move;ÐÐÐui-menu {ÐÆ—7B×7G–ÆS¢ æöæS½ FF–æs¢ ' ƒ½Ö &v–ã¢ ½F—7 Æ “¢
block;Ð÷WFÆ–æS¢ æöæS½ÐÐui-menu .ui-menu {ÐÖ &v–â×F÷ ¢ Ó7 ƒ½ ÷6—F–öã¢ '6öÇWFS½ÐÐ
.ui-menu .ui-menu-item {Ð

–Ö &v–ã¢ ½ FF–æs¢ ½v–GFƒ¢ S½ò¢ 7W ÷'C¢ ”S Â
see #8844 */ÐÆ–7B×7G–ÆRÖ–Ö vS¢ W&Â†F F ¦–Ö vRð
gifbase64,R0lGODlhAQABAIAAAAAAAP///yH5BAEAAAAALAAAAAABAAEAAAIBRAA7);ÐÐui-
menu .ui-menu-divider {ÐÖ &v–ã¢ W , Ó' , W , Ó' ƒ½†V–v‡C¢ ½föçB×6–¦S¢ ½Æ–æRÐ
height: 0;Ð&÷&FW"×v–GFƒ¢ , ½Ðui-menu .ui-menu-item a {ÐFW‡BÖFV6÷& F–öã¢
none;ÐF–7 Æ “¢ &Æö6³½ FF–æs¢ ' , ãFVÓ½Æ–æRÖ†V–v‡C¢ ãS½Ö–âÖ†V–v‡C¢ ² ò¢
support: IE7 */ÐföçB×vV–v‡C¢ æ÷&Ö Ã½Ðui-menu .ui-menu-item a.ui-state-focus,Ð
.ui-menu .ui-menu-item a.ui-state-active {ÐföçB×vV–v‡C¢ æ÷&Ö Ã½Ö &v–ã¢ Ó ƒ½Ð
.ui-menu .ui-state-disabled {ÐföçB×vV–v‡C¢ æ÷&Ö Ã½Ö &v–ã¢ ãFVÒ ã&VÓ½Æ–æRÐ
height: 1.5;ÐÐui-menu .ui-state-disabled a {Ð7W'6÷#¢ FVf VÇC½Ð* icon support
*/Ðui-menu-icons {Ð ÷6–F–öã¢ &VÆ F–fS½Ðui-menu-icons .ui-menu-item a {Ð
position: relative;Ð FF–ærÖÆVgC¢ &VÓ½Ð* left-aligned */Ðui-menu .ui-icon {Ð
position: absolute;ÐF÷ ¢ ã&VÓ½ÆVgC¢ ã&VÓ½Ð* right-aligned */Ðui-menu .ui-menu-
icon {Ð ÷6–F–öã¢ 7F F–3½fÆö C¢ &–v‡C½Ðui-progressbar {Ð†V–v‡C¢ &VÓ½FW‡BÖ Æ–vã¢
left;Ð÷fW&fÆ÷s¢ †–FFVã½Ðui-progressbar .ui-progressbar-value {ÐÖ &v–ã¢ Ó ƒ½
height: 100%;ÐÐui-progressbar .ui-progressbar-overlay {Ð& 6¶w&÷VæC¢
url("images/animated-overlay.gif");Ð†V–v‡C¢ S½f–ÇFW#¢ Ç † †÷ 6–G“Ó#R“½
opacity: 0.25;ÐÐui-progressbar-indeterminate .ui-progressbar-value {Ð
background-image: none;ÐÐui-resizable {Ð ÷6–F–öã¢ &VÆ F–fS½Ðui-resizable-
handle {Ð ÷6–F–öã¢ '6öÇWFS½föçB×6–¦S¢ ã ƒ½F–7 Æ “¢ &Æö6³½Ðui-resizable-
disabled .ui-resizable-handle,Ðui-resizable-autohide .ui-resizable-handle {Ð
display: none;ÐÐui-resizable-n {Ð7W'6÷#¢ â×&W6–¦S½†V–v‡C¢ w ƒ½v–GFƒ¢ S½F÷ ¢
-5px;ÐÆVgC¢ ½Ðui-resizable-s {Ð7W'6÷#¢ 2×&W6–¦S½†V–v‡C¢ w ƒ½v–GFƒ¢ S½
bottom: -5px;ÐÆVgC¢ ½Ðui-resizable-e {Ð7W'6÷#¢ R×&W6–¦S½v–GFƒ¢ w ƒ½&–v‡C¢
-5px;ÐF÷ ¢ ½†V–v‡C¢ S½Ðui-resizable-w {Ð7W'6÷#¢ r×&W6–¦S½v–GFƒ¢ w ƒ½ÆVgC¢
-5px;ÐF÷ ¢ ½†V–v‡C¢ S½Ðui-resizable-se {Ð7W'6÷#¢ 6R×&W6–¦S½v–GFƒ¢ ' ƒ½
height: 12px;Ð&–v‡C¢ ƒ½&÷GFöÓ¢ ƒ½Ðui-resizable-sw {Ð7W'6÷#¢ 7r×&W6–¦S½
width: 9px;Ð†V–v‡C¢ – ƒ½ÆVgC¢ ÓW ƒ½&÷GFöÓ¢ ÓW ƒ½Ðui-resizable-nw {Ð7W'6÷#¢ çrÐ
resize;Ðv–GFƒ¢ – ƒ½†V–v‡C¢ – ƒ½ÆVgC¢ ÓW ƒ½F÷ ¢ ÓW ƒ½Ðui-resizable-ne {Ð7W'6÷#¢
ne-resize;Ðv–GFƒ¢ – ƒ½†V–v‡C¢ – ƒ½&–v‡C¢ ÓW ƒ½F÷ ¢ ÓW ƒ½Ðui-selectable-helper
{Ð ÷6–F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ ½&÷&FW#¢ , F÷GFVB &Æ 6³½Ðui-slider {Ð
position: relative;ÐFW‡BÖ Æ–vã¢ ÆVgC½Ðui-slider .ui-slider-handle {Ð ÷6–F–öã¢
absolute;Ð¢Ö–æFWƒ¢ #½v–GFƒ¢ ã&VÓ½†V–v‡C¢ ã&VÓ½7W'6÷#¢ FVf VÇC½Ðui-
slider .ui-slider-range {Ð ÷6–F–öã¢ '6öÇWFS½¢Ö–æFWƒ¢ ½föçB×6–¦S¢ ãvVÓ½
display: block;Ð&÷&FW#¢ ½& 6¶w&÷VæB× ÷6–F–öã¢ ½Ð* For IE8 - See #6727 */Ð
.ui-slider.ui-state-disabled .ui-slider-handle,Ðui-slider.ui-state-
disabled .ui-slider-range {ÐF–ÇFW#¢ –æ†W&–C½Ðui-slider-horizontal {Ð
height: .8em;ÐÐui-slider-horizontal .ui-slider-handle {ÐF÷ ¢ Òã6VÓ½Ö &v–âÐ
left: -.6em;ÐÐui-slider-horizontal .ui-slider-range {ÐF÷ ¢ ½†V–v‡C¢ S½Ðui-
slider-horizontal .ui-slider-range-min {ÐÆVgC¢ ½Ðui-slider-horizontal .ui-
slider-range-max {Ð&–v‡C¢ ½Ðui-slider-vertical {Ðv–GFƒ¢ ã†VÓ½†V–v‡C¢ ƒ½Ð
.ui-slider-vertical .ui-slider-handle {ÐÆVgC¢ Òã6VÓ½Ö &v–âÖÆVgC¢ ½Ö &v–âÐ
bottom: -.6em;ÐÐui-slider-vertical .ui-slider-range {ÐÆVgC¢ ½v–GFƒ¢ S½Ðui-
slider-vertical .ui-slider-range-min {Ð&÷GFöÓ¢ ½Ðui-slider-vertical .ui-
slider-range-max {ÐF÷ ¢ ½Ðui-spinner {Ð ÷6–F–öã¢ &VÆ F–fS½F–7 Æ “¢ –æÆ–æRÐ
block;Ð÷fW&fÆ÷s¢ †–FFVã½ FF–æs¢ ½fW'F–6 ÂÖ Æ–vã¢ Ö–FFÆS½Ðui-spinner-input {Ð
border: none;Ð& 6¶w&÷VæC¢ æöæS½6öÆ÷#¢ –æ†W&–C½ FF–æs¢ ½Ö &v–ã¢ ã&VÒ ½
vertical-align: middle;ÐÖ &v–âÖÆVgC¢ ãFVÓ½Ö &v–â×&–v‡C¢ #' ƒ½Ðui-spinner-
button {Ðv–GFƒ¢ g ƒ½†V–v‡C¢ S S½föçB×6–¦S¢ ãVVÓ½ FF–æs¢ ½Ö &v–ã¢ ½FW‡BÐ
align: center;Ð ÷6–F–öã¢ '6öÇWFS½7W'6÷#¢ FVf VÇC½F–7 Æ “¢ &Æö6³½÷fW&fÆ÷s¢
hidden;Ð&–v‡C¢ ½Ð* more specificity required here to override default
borders */Ðui-spinner a.ui-spinner-button {Ð&÷&FW"×F÷ ¢ æöæS½&÷&FW"Ö&÷GFöÓ¢
none;Ð&÷&FW"×&–v‡C¢ æöæS½Ð* vertically center icon */Ðui-spinner .ui-icon {Ð
position: absolute;ÐÖ &v–â×F÷ ¢ Ó‡ ƒ½F÷ ¢ S S½ÆVgC¢ ½Ðui-spinner-up {ÐF÷ ¢ ½Ð
.ui-spinner-down {Ð&÷GFöÓ¢ ½Ð* TR overrides */Ðui-spinner .ui-icon-
triangle-1-s {Ðò¢ æVVB Fò f–, –6öç2 7 &–FR ¢ý& 6¶w&÷VæB× ÷6–F–öã¢ ÓcW , Ó g ƒ½Ð
.ui-tabs {Ð ÷6–F–öã¢ &VÆ F–fS²ò¢ ÷6–F–öã¢ &VÆ F–fR &WfVçG2 ”R 67&öÆÂ 'Vr
(element with position: relative inside container with overflow: auto appear
as "fixed") */Ð FF–æs¢ ã&VÓ½Ðui-tabs .ui-tabs-nav {ÐÖ &v–ã¢ ½
padding: .2em .2em 0;Ð

}Ðui-tabs .ui-tabs-nav li {ÐÆ–7B×7G–ÆS¢ æöæS½fÆö C¢ ÆVgC½
position: relative;ÐF÷ ¢ ½Ö &v–ã¢ , ã&VÒ ½&÷&FW"Ö&÷GFöÒ×v–GFƒ¢ ½
padding: 0;Ðv†–FR×7 6S¢ æ÷w& ½Ðui-tabs .ui-tabs-nav .ui-tabs-anchor {ÐfÆö C¢
left;Ð FF–æs¢ ãVVÒ VÓ½FW‡BÖFV6÷& F–öã¢ æöæS½Ðui-tabs .ui-tabs-nav li.ui-
tabs-active {ÐÖ &v–âÖ&÷GFöÓ¢ Ó ƒ½ FF–ærÖ&÷GFöÓ¢ ƒ½Ðui-tabs .ui-tabs-nav
li.ui-tabs-active .ui-tabs-anchor,Ðui-tabs .ui-tabs-nav li.ui-state-
disabled .ui-tabs-anchor,Ðui-tabs .ui-tabs-nav li.ui-tabs-loading .ui-tabs-
anchor {Ð7W'6÷#¢ FW‡C½Ðui-tabs-collapsible .ui-tabs-nav li.ui-tabs-active .ui-
tabs-anchor {Ð7W'6÷#¢ ö–çFW#½Ðui-tabs .ui-tabs-panel {ÐF–7 Æ “¢ &Æö6³½&÷&FW"Ð
width: 0;Ð FF–æs¢ VÒ ãFVÓ½& 6¶w&÷VæC¢ æöæS½Ðui-tooltip {Ð FF–æs¢ ‡ ƒ½
position: absolute;Ð¢Ö–æFWƒ¢ “”“”½Ö ,×v–GFƒ¢ 3 ƒ½×vV&¶–BÖ&÷,×6† F÷s¢ W ,
#aaa;Ð&÷,×6† F÷s¢ W , 6 ½Ðody .ui-tooltip {Ð&÷&FW"×v–GFƒ¢ ' ƒ½Ð*
Component containersÐ----------*/Ðui-widget {ÐföçBÐ
family: Verdana,Arial,sans-serif/*{ffDefault}*/;ÐföçB×6–¦S¢ ã VÒò§¶g4FVf VÇGÐ
*/;ÐÐui-widget .ui-widget {ÐföçB×6–¦S¢ VÓ½Ðui-widget input,Ðui-widget select,Ð
.ui-widget textarea,Ðui-widget button {ÐföçBÖf Ö–Ç“¢ fW&F æ Ä &– ÂÇ6 ç2×6W&–bð
{ffDefault}/;ÐföçB×6–¦S¢ VÓ½Ðui-widget-content {Ð&÷&FW#¢ , 6öÆ–B 6 ð
{borderColorContent}/;Ð& 6¶w&÷VæC¢ 6fffffbò§¶&t6öÆ÷$6öçFVçGÒ¢ò W&Â†–Ö vW2÷V’Ð
bg_flat_75_ffffff_40x100.png)/*{bgImgUrlContent}*/ 50%/*{bgContentXPos}*/ 50%/
{bgContentYPos}/ repeat-x/*{bgContentRepeat}*/;Ð6öÆ÷#¢ 3#####"ò§¶f46öçFVçGÐ
*/;ÐÐui-widget-content a {Ð6öÆ÷#¢ 3#####"ò§¶f46öçFVçGÒ¢ó½Ðui-widget-header {Ð
border: 1px solid #aaaaaa/*{borderColorHeader}*/;Ð& 6¶w&÷VæC¢ 6666662ð
{bgColorHeader}/ url(images/ui-bg_highlight-soft_75_cccccc_1x100.png)/
{bgImgUrlHeader}/ 50%/*{bgHeaderXPos}*/ 50%/*{bgHeaderYPos}*/ repeat-x/
{bgHeaderRepeat}/;Ð6öÆ÷#¢ 3#####"ò§¶f4†V FW'Ò¢ó½föçB×vV–v‡C¢ &öÆC½Ðui-
widget-header a {Ð6öÆ÷#¢ 3#####"ò§¶f4†V FW'Ò¢ó½Ð* Interaction statesÐ
----------*/Ðui-state-default,Ðui-widget-content .ui-
state-default,Ðui-widget-header .ui-state-default {Ð&÷&FW#¢ , 6öÆ–B 6C6C6C2ð
{borderColorDefault}/;Ð& 6¶w&÷VæC¢ 6SfSfSbò§¶&t6öÆ÷$FVf VÇGÒ¢ò W&Â†–Ö vW2÷V’Ð
bg_glass_75_e6e6e6_1x400.png)/*{bgImgUrlDefault}*/ 50%/*{bgDefaultXPos}*/ 50%/
{bgDefaultYPos}/ repeat-x/*{bgDefaultRepeat}*/;ÐföçB×vV–v‡C¢ æ÷&Ö Âð
{fwDefault}/;Ð6öÆ÷#¢ 3SSSSSSRò§¶f4FVf VÇGÒ¢ó½Ðui-state-default a,Ðui-state-
default a:link,Ðui-state-default a:visited {Ð6öÆ÷#¢ 3SSSSSSRò§¶f4FVf VÇGÒ¢ó½
text-decoration: none;ÐÐui-state-hover,Ðui-widget-content .ui-state-hover,Ðui-
widget-header .ui-state-hover,Ðui-state-focus,Ðui-widget-content .ui-state-
focus,Ðui-widget-header .ui-state-focus {Ð&÷&FW#¢ , 6öÆ–B 3“”“”“’ð
{borderColorHover}/;Ð& 6¶w&÷VæC¢ 6F F F ò§¶&t6öÆ÷$†÷fW'Ò¢ò W&Â†–Ö vW2÷V’Ð
bg_glass_75_dadada_1x400.png)/*{bgImgUrlHover}*/ 50%/*{bgHoverXPos}*/ 50%/
{bgHoverYPos}/ repeat-x/*{bgHoverRepeat}*/;ÐföçB×vV–v‡C¢ æ÷&Ö Âò§¶gtFVf VÇGÐ
*/;Ð6öÆ÷#¢ 3# # # ò§¶f4†÷fW'Ò¢ó½Ðui-state-hover a,Ðui-state-hover a:hover,Ðui-
state-hover a:link,Ðui-state-hover a:visited,Ðui-state-focus a,Ðui-state-
focus a:hover,Ðui-state-focus a:link,Ðui-state-focus a:visited {Ð6öÆ÷#¢
#212121/*{fcHover}*/;ÐFW‡BÖFV6÷& F–öã¢ æöæS½Ðui-state-active,Ðui-widget-
content .ui-state-active,Ðui-widget-header .ui-state-active {Ð&÷&FW#¢ ,
solid #aaaaaa/*{borderColorActive}*/;Ð& 6¶w&÷VæC¢ 6fffffbò§¶&t6öÆ÷$ 7F–fWÒ¢ò
url(images/ui-bg_glass_65_ffffff_1x400.png)/*{bgImgUrlActive}*/ 50%/
{bgActiveXPos}/ 50%/*{bgActiveYPos}*/ repeat-x/*{bgActiveRepeat}*/;ÐföçBÐ
weight: normal/*{fwDefault}*/;Ð6öÆ÷#¢ 3# # # ò§¶f4 7F–fWÒ¢ó½Ðui-state-active
a,Ðui-state-active a:link,Ðui-state-active a:visited {Ð6öÆ÷#¢ 3# # # ð
{fcActive}/;ÐFW‡BÖFV6÷& F–öã¢ æöæS½Ð* Interaction CuesÐ
----------*/Ðui-state-highlight,Ðui-widget-
content .ui-state-highlight,Ðui-widget-header .ui-state-highlight {Ð&÷&FW#¢
1px solid #fcefa1/*{borderColorHighlight}*/;Ð& 6¶w&÷VæC¢ 6f&c–VRð
{bgColorHighlight}/ url(images/ui-bg_glass_55_fbf9ee_1x400.png)/
{bgImgUrlHighlight}/ 50%/*{bgHighlightXPos}*/ 50%/*{bgHighlightYPos}*/
repeat-x/*{bgHighlightRepeat}*/;Ð6öÆ÷#¢ 33c3c3bò§¶f4†–v†Æ–v‡GÒ¢ó½Ðui-state-
highlight a,Ðui-widget-content .ui-state-highlight a,Ðui-widget-header .ui-
state-highlight a {Ð6öÆ÷#¢ 33c3c3bò§¶f4†–v†Æ–v‡GÒ¢ó½Ðui-state-error,Ðui-
widget-content .ui-state-error,Ðui-widget-header .ui-state-error {Ð&÷&FW#¢ ,
solid #cd0a0a/*{borderColorError}*/;Ð

–& 6¶w&÷VæC¢ 6fVc V2ò§¶&t6öÆ÷$W'&÷'Ò¢ò
url(images/ui-bg_glass_95_fef1ec_1x400.png)/*{bgImgUrlError}*/ 50%/
{bgErrorXPos}/ 50%/*{bgErrorYPos}*/ repeat-x/*{bgErrorRepeat}*/;Ð6öÆ÷#¢
#cd0a0a/*{fcError}*/;ÐÐui-state-error a,Ðui-widget-content .ui-state-error a,Ð
.ui-widget-header .ui-state-error a {Ð6öÆ÷#¢ 66C   ò§¶f4W'&÷'Ò¢ó½Ðui-state-
error-text,Ðui-widget-content .ui-state-error-text,Ðui-widget-header .ui-
state-error-text {Ð6öÆ÷#¢ 66C   ò§¶f4W'&÷'Ò¢ó½Ðui-priority-primary,Ðui-
widget-content .ui-priority-primary,Ðui-widget-header .ui-priority-primary {Ð
font-weight: bold;ÐÐui-priority-secondary,Ðui-widget-content .ui-priority-
secondary,Ðui-widget-header .ui-priority-secondary {Ð÷ 6—G“¢ ãs½
filter:Alpha(Opacity=70);ÐföçB×vV–v‡C¢ æ÷&Ö Ã½Ðui-state-disabled,Ðui-widget-
content .ui-state-disabled,Ðui-widget-header .ui-state-disabled {Ð÷ 6—G“¢ ã3S½
filter:Alpha(Opacity=35);Ð& 6¶w&÷VæBÖ–Ö vS¢ æöæS½Ðui-state-disabled .ui-icon {Ð
filter:Alpha(Opacity=35); /* For IE8 - See #6059 */ÐÐ* IconsÐ
----------*/Ð* states and images */Ðui-icon {Ðv–GFƒ¢
16px;Ð†V–v‡C¢ g ƒ½Ðui-icon,Ðui-widget-content .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢
url(images/ui-icons_222222_256x240.png)/*{iconsContent}*/;ÐÐui-widget-
header .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ö–6öç5ó#####%ó#Sgƒ#C ç ær’ð
{iconsHeader}/;ÐÐui-state-default .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_888888_256x240.png)/*{iconsDefault}*/;ÐÐui-state-hover .ui-icon,Ðui-
state-focus .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_454545_256x240.png)/*{iconsHover}*/;ÐÐui-state-active .ui-icon {Ð
background-image: url(images/ui-icons_454545_256x240.png)/*{iconsActive}*/;ÐÐ
.ui-state-highlight .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_2e83ff_256x240.png)/*{iconsHighlight}*/;ÐÐui-state-error .ui-icon,Ðui-
state-error-text .ui-icon {Ð& 6¶w&÷VæBÖ–Ö vS¢ W&Â†–Ö vW2÷V’Ð
icons_cd0a0a_256x240.png)/*{iconsError}*/;ÐÐ* positioning */Ðui-icon-blank
{ background-position: 16px 16px; }Ðui-icon-carat-1-n { background-position:
0 0; }Ðui-icon-carat-1-ne { background-position: -16px 0; }Ðui-icon-carat-1-e
{ background-position: -32px 0; }Ðui-icon-carat-1-se { background-position:
-48px 0; }Ðui-icon-carat-1-s { background-position: -64px 0; }Ðui-icon-
carat-1-sw { background-position: -80px 0; }Ðui-icon-carat-1-w { background-
position: -96px 0; }Ðui-icon-carat-1-nw { background-position: -112px 0; }Ðui-
icon-carat-2-n-s { background-position: -128px 0; }Ðui-icon-carat-2-e-w
{ background-position: -144px 0; }Ðui-icon-triangle-1-n { background-
position: 0 -16px; }Ðui-icon-triangle-1-ne { background-position: -16px
-16px; }Ðui-icon-triangle-1-e { background-position: -32px -16px; }Ðui-icon-
triangle-1-se { background-position: -48px -16px; }Ðui-icon-triangle-1-s
{ background-position: -64px -16px; }Ðui-icon-triangle-1-sw { background-
position: -80px -16px; }Ðui-icon-triangle-1-w { background-position: -96px
-16px; }Ðui-icon-triangle-1-nw { background-position: -112px -16px; }Ðui-icon-
triangle-2-n-s { background-position: -128px -16px; }Ðui-icon-triangle-2-e-w
{ background-position: -144px -16px; }Ðui-icon-arrow-1-n { background-
position: 0 -32px; }Ðui-icon-arrow-1-ne { background-position: -16px -32px; }Ð
.ui-icon-arrow-1-e { background-position: -32px -32px; }Ðui-icon-arrow-1-se
{ background-position: -48px -32px; }Ðui-icon-arrow-1-s { background-
position: -64px -32px; }Ðui-icon-arrow-1-sw { background-position: -80px
-32px; }Ðui-icon-arrow-1-w { background-position: -96px -32px; }Ðui-icon-
arrow-1-nw { background-position: -112px -32px; }Ðui-icon-arrow-2-n-s
{ background-position: -128px -32px; }Ðui-icon-arrow-2-ne-sw { background-
position: -144px -32px; }Ðui-icon-arrow-2-e-w { background-position: -160px
-32px; }Ðui-icon-arrow-2-se-nw { background-position: -176px -32px; }Ðui-icon-
arrowstop-1-n { background-position: -192px -32px; }Ðui-icon-arrowstop-1-e
{ background-position: -208px -32px; }Ðui-icon-arrowstop-1-s { background-
position: -224px -32px; }Ðui-icon-arrowstop-1-w { background-position: -240px
-32px; }Ðui-icon-arrowthick-1-n { background-position: 0 -48px; }Ðui-icon-
arrowthick-1-ne { background-position: -16px -48px; }Ðui-icon-arrowthick-1-e
{ background-position: -32px -48px; }Ðui-icon-arrowthick-1-se { background-
position: -48px -48px; }Ðui-icon-arrowthick-1-s { background-position: -64px
-48px; }Ð

.ui-icon-arrowthick-1-sw { background-position: -80px -48px; }Đui-icon-arrowthick-1-w { background-position: -96px -48px; }Đui-icon-arrowthick-1-nw { background-position: -112px -48px; }Đui-icon-arrowthick-2-n-s { background-position: -128px -48px; }Đui-icon-arrowthick-2-ne-sw { background-position: -144px -48px; }Đui-icon-arrowthick-2-e-w { background-position: -160px -48px; }Đui-icon-arrowthick-2-se-nw { background-position: -176px -48px; }Đui-icon-arrowthickstop-1-n { background-position: -192px -48px; }Đui-icon-arrowthickstop-1-e { background-position: -208px -48px; }Đui-icon-arrowthickstop-1-s { background-position: -224px -48px; }Đui-icon-arrowthickstop-1-w { background-position: -240px -48px; }Đui-icon-arrowreturnthick-1-w { background-position: 0 -64px; }Đui-icon-arrowreturnthick-1-n { background-position: -16px -64px; }Đui-icon-arrowreturnthick-1-e { background-position: -32px -64px; }Đui-icon-arrowreturnthick-1-s { background-position: -48px -64px; }Đui-icon-arrowreturn-1-w { background-position: -64px -64px; }Đui-icon-arrowreturn-1-n { background-position: -80px -64px; }Đui-icon-arrowreturn-1-e { background-position: -96px -64px; }Đui-icon-arrowreturn-1-s { background-position: -112px -64px; }Đui-icon-arrowrefresh-1-w { background-position: -128px -64px; }Đui-icon-arrowrefresh-1-n { background-position: -144px -64px; }Đui-icon-arrowrefresh-1-e { background-position: -160px -64px; }Đui-icon-arrowrefresh-1-s { background-position: -176px -64px; }Đui-icon-arrow-4 { background-position: 0 -80px; }Đui-icon-arrow-4-diag { background-position: -16px -80px; }Đui-icon-extlink { background-position: -32px -80px; }Đui-icon-newwin { background-position: -48px -80px; }Đui-icon-refresh { background-position: -64px -80px; }Đui-icon-shuffle { background-position: -80px -80px; }Đ .ui-icon-transfer-e-w { background-position: -96px -80px; }Đui-icon-transferthick-e-w { background-position: -112px -80px; }Đui-icon-folder-collapsed { background-position: 0 -96px; }Đui-icon-folder-open { background-position: -16px -96px; }Đui-icon-document { background-position: -32px -96px; }Đui-icon-document-b { background-position: -48px -96px; }Đui-icon-note { background-position: -64px -96px; }Đui-icon-mail-closed { background-position: -80px -96px; }Đui-icon-mail-open { background-position: -96px -96px; }Đui-icon-suitcase { background-position: -112px -96px; }Đui-icon-comment { background-position: -128px -96px; }Đui-icon-person { background-position: -144px -96px; }Đui-icon-print { background-position: -160px -96px; }Đ .ui-icon-trash { background-position: -176px -96px; }Đui-icon-locked { background-position: -192px -96px; }Đui-icon-unlocked { background-position: -208px -96px; }Đui-icon-bookmark { background-position: -224px -96px; }Đui-icon-tag { background-position: -240px -96px; }Đui-icon-home { background-position: 0 -112px; }Đui-icon-flag { background-position: -16px -112px; }Đui-icon-calendar { background-position: -32px -112px; }Đui-icon-cart { background-position: -48px -112px; }Đui-icon-pencil { background-position: -64px -112px; }Đui-icon-clock { background-position: -80px -112px; }Đ .ui-icon-disk { background-position: -96px -112px; }Đui-icon-calculator { background-position: -112px -112px; }Đui-icon-zoomin { background-position: -128px -112px; }Đui-icon-zoomout { background-position: -144px -112px; }Đui-icon-search { background-position: -160px -112px; }Đui-icon-wrench { background-position: -176px -112px; }Đui-icon-gear { background-position: -192px -112px; }Đui-icon-heart { background-position: -208px -112px; }Đui-icon-star { background-position: -224px -112px; }Đui-icon-link { background-position: -240px -112px; }Đui-icon-cancel { background-position: 0 -128px; }Đ .ui-icon-plus { background-position: -16px -128px; }Đui-icon-plusthick { background-position: -32px -128px; }Đui-icon-minus { background-position: -48px -128px; }Đui-icon-minusthick { background-position: -64px -128px; }Đui-icon-close { background-position: -80px -128px; }Đui-icon-closethick { background-position: -96px -128px; }Đui-icon-key { background-position: -112px -128px; }Đui-icon-lightbulb { background-position: -128px -128px; }Đui-icon-scissors { background-position: -144px -128px; }Đui-icon-clipboard { background-position: -160px -128px; }Đui-icon-copy { background-position: -176px -128px; }Đ

.ui-icon-contact { background-position: -192px -128px; }Ðui-icon-image { background-position: -208px -128px; }Ðui-icon-video { background-position: -224px -128px; }Ðui-icon-script { background-position: -240px -128px; }Ðui-icon-alert { background-position: 0 -144px; }Ðui-icon-info { background-position: -16px -144px; }Ðui-icon-notice { background-position: -32px -144px; }Ðui-icon-help { background-position: -48px -144px; }Ðui-icon-check { background-position: -64px -144px; }Ðui-icon-bullet { background-position: -80px -144px; }Ðui-icon-radio-on { background-position: -96px -144px; }Ðui-icon-radio-off { background-position: -112px -144px; }Ðui-icon-pin-w { background-position: -128px -144px; }Ðui-icon-pin-s { background-position: -144px -144px; }Ðui-icon-play { background-position: 0 -160px; }Ðui-icon-pause { background-position: -16px -160px; }Ðui-icon-seek-next { background-position: -32px -160px; }Ðui-icon-seek-prev { background-position: -48px -160px; }Ðui-icon-seek-end { background-position: -64px -160px; }Ðui-icon-seek-start { background-position: -80px -160px; }Ð* ui-icon-seek-first is deprecated, use ui-icon-seek-start instead */Ðui-icon-seek-first { background-position: -80px -160px; }Ðui-icon-stop { background-position: -96px -160px; }Ðui-icon-eject { background-position: -112px -160px; }Ðui-icon-volume-off { background-position: -128px -160px; }Ðui-icon-volume-on { background-position: -144px -160px; }Ðui-icon-power { background-position: 0 -176px; }Ðui-icon-signal-diag { background-position: -16px -176px; }Ðui-icon-signal { background-position: -32px -176px; }Ðui-icon-battery-0 { background-position: -48px -176px; }Ðui-icon-battery-1 { background-position: -64px -176px; }Ðui-icon-battery-2 { background-position: -80px -176px; }Ðui-icon-battery-3 { background-position: -96px -176px; }Ðui-icon-circle-plus { background-position: 0 -192px; }Ðui-icon-circle-minus { background-position: -16px -192px; }Ðui-icon-circle-close { background-position: -32px -192px; }Ðui-icon-circle-triangle-e { background-position: -48px -192px; }Ðui-icon-circle-triangle-s { background-position: -64px -192px; }Ðui-icon-circle-triangle-w { background-position: -80px -192px; }Ðui-icon-circle-triangle-n { background-position: -96px -192px; }Ðui-icon-circle-arrow-e { background-position: -112px -192px; }Ðui-icon-circle-arrow-s { background-position: -128px -192px; }Ðui-icon-circle-arrow-w { background-position: -144px -192px; }Ðui-icon-circle-arrow-n { background-position: -160px -192px; }Ðui-icon-circle-zoomin { background-position: -176px -192px; }Ðui-icon-circle-zoomout { background-position: -192px -192px; }Ðui-icon-circle-check { background-position: -208px -192px; }Ðui-icon-circlesmall-plus { background-position: 0 -208px; }Ðui-icon-circlesmall-minus { background-position: -16px -208px; }Ðui-icon-circlesmall-close { background-position: -32px -208px; }Ðui-icon-squaresmall-plus { background-position: -48px -208px; }Ðui-icon-squaresmall-minus { background-position: -64px -208px; }Ðui-icon-squaresmall-close { background-position: -80px -208px; }Ðui-icon-grip-dotted-vertical { background-position: 0 -224px; }Ðui-icon-grip-dotted-horizontal { background-position: -16px -224px; }Ðui-icon-grip-solid-vertical { background-position: -32px -224px; }Ðui-icon-grip-solid-horizontal { background-position: -48px -224px; }Ðui-icon-gripsmall-diagonal-se { background-position: -64px -224px; }Ðui-icon-grip-diagonal-se { background-position: -80px -224px; }Ð* Misc visualsÐ ----------*/Ð* Corner radius */Ðui-corner-all,Ðui-corner-top,Ðui-corner-left,Ðui-corner-tl {Ð&÷&FW"×F÷ ÖÆVgB×& F—W3¢ G ,ð *{cornerRadius}*/;ÐÐui-corner-all,Ðui-corner-top,Ðui-corner-right,Ðui-corner-tr {Ð&÷&FW"×F÷ ×&–v‡B×& F—W3¢ G ,ò§¶6÷&æW%& F—W7Ò¢ó½Ðui-corner-all,Ðui-corner-bottom,Ðui-corner-left,Ðui-corner-bl {Ð&÷&FW"Ö&÷GFöÒÖÆVgB×& F—W3¢ G ,ð *{cornerRadius}*/;ÐÐui-corner-all,Ðui-corner-bottom,Ðui-corner-right,Ðui-corner-br {Ð&÷&FW"Ö&÷GFöÒ×&–v‡B×& F—W3¢ G ,ò§¶6÷&æW%& F—W7Ò¢ó½Ð* Overlays */Ð .ui-widget-overlay {Ð& 6¶w&÷VæC¢ 6 ò§¶&t6öÆ÷$÷fW&Æ —Ò¢ò W&Â†–Ö vW2÷V'Ð bg_flat_0_aaaaaa_40x100.png)/*{bgImgUrlOverlay}*/ 50%/*{bgOverlayXPos}*/ 50%/*{bgOverlayYPos}*/ repeat-x/*{bgOverlayRepeat}*/;Ð÷ 6—G“¢ ã2ò§¶÷ 6—G”÷fW&Æ —Ð */;Ðf–ÇFW#¢ Ç † „÷ 6—G“Ó3 'ò§¶÷ 6—G”f–ÇFW$÷fW&Æ —Ò¢ó½Ðui-widget-shadow {Ð margin: -8px/*{offsetTopShadow}*/ 0 0 -8px/*{offsetLeftShadow}*/;Ð

— FF–æs¢ ‡ ,ð
{thicknessShadow}/;Ð& 6¶w&÷VæC¢ 6   ò§¶&t6öÆ÷%6† F÷wÒ¢ò W&Â†–Ö vW2÷V’Ð
bg_flat_0_aaaaaa_40x100.png)/*{bgImgUrlShadow}*/ 50%/*{bgShadowXPos}*/ 50%/
{bgShadowYPos}/ repeat-x/*{bgShadowRepeat}*/;Ð÷ 6—G“¢ ã2ò§¶÷ 6—G•6† F÷wÒ¢ó½
filter: Alpha(Opacity=30)/*{opacityFilterShadow}*/;Ð&÷&FW"×& F—W3¢ ‡ ,ð
{cornerRadiusShadow}/;ÐÐ

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.css

```
/* Ðustified GalleryÐVersion: 2.1ÐAuthor: Miro ManninoÐAuthor URI: http://
miromannino.itÐCopyright 2012 Miro Mannino (miro.mannino@gmail.com)ÐThis file
is part of Justified Gallery.ÐThis work is licensed under the Creative Commons
Attribution 3.0 Unported License. ÐTo view a copy of this license, visit
http://creativecommons.org/licenses/by/3.0/ ÐOr send a letter to Creative
Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.Ð
*/Ðhtml { overflow-y: scroll; } /*to prevent the loop when the scrollbar
appear and disappear*/ÐjustifiedGallery { width: 100%; margin-bottom: 10px; }Ð
.justifiedGallery .jg-image {Ð   position: absolute;Ð   display: inline-block;Ð
    vertical-align: top;Ð   margin-left: 0px;ÐÐjustifiedGallery .jg-image img
{Ð   border: none;Ð   margin: 0;Ð   padding: 0;Ð   display: none;ÐÐ
.justifiedGallery .jg-image a { text-decoration: none; }ÐjustifiedGallery .jg-
image-label {Ð   white-space: normal;Ð   font: normal 12px arial;Ð
background: #000;Ð   color: #fff;Ð   position: absolute;Ð   left: 0;Ð
right: 0;Ð   padding: 5px 5px 10px 8px;Ð   text-align: left;Ð   opacity: 0;Ð
    filter:alpha(opacity=0); /* IE8 or Earlier */ÐÐjustifiedGallery .jg-
loading-img{Ð   margin: auto;Ð   width: 50px;Ð   height: 50px;Ð
background:url(loading.gif) no-repeat center center;ÐÐjustifiedGallery .jg-
loading{Ð   margin: auto;Ð   width: 50px;Ð   height: 50px;Ð   -webkit-border-
radius: 3px;Ð   -moz-border-radius: 3px;Ð   border-radius: 3px;ÐÐ
.justifiedGallery .jg-row {Ð   position: relative;Ð   white-space: nowrap;    Ð
    overflow:hidden;Ð   margin-bottom: 4px;ÐÐjustifiedGallery .jg-error {Ð
font-size: 12px; Ð   border: 1px solid red; Ð   background-color: #faa; Ð
margin: 10px 0px 10px 0px; Ð   padding: 5px 0px 5px 5px;Ð
```

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.min.css

```
/* Ð Justified Gallery Ð Version: 2.1 Ð Author: Miro Mannino Ð Author URI: http://
miromannino.it Ð Copyright 2012 Miro Mannino (miro.mannino@gmail.com) Ð This file
is part of Justified Gallery. Ð This work is licensed under the Creative Commons
Attribution 3.0 Unported License. Ð To view a copy of this license, visit
http://creativecommons.org/licenses/by/3.0/ Ð or send a letter to Creative
Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA. Ð
*/ Ð html{overflow-y:scroll}.justifiedGallery{width:100%;margin-
bottom:10px}.justifiedGallery .jg-image{position:absolute;display:inline-
block;vertical-align:top;margin-left:0}.justifiedGallery .jg-image
img{border:none;margin:0;padding:0;display:none}.justifiedGallery .jg-image
a{text-decoration:none}.justifiedGallery .jg-image-label{white-
space:normal;font:normal 12px
arial;background:#000;color:#fff;position:absolute;left:0;right:0;padding:5px
5px 10px 8px;text-
align:left;opacity:0;filter:alpha(opacity=0)}.justifiedGallery .jg-loading-
img{margin:auto;width:50px;height:50px;background:url(../img/loading.gif) no-
repeat center center}.justifiedGallery .jg-
loading{margin:auto;width:50px;height:50px;-webkit-border-radius:3px;-moz-
border-radius:3px;border-radius:3px}.justifiedGallery .jg-
row{position:relative;white-space:nowrap;overflow:hidden;margin-
bottom:4px}.justifiedGallery .jg-error{font-size:12px;border:1px solid
red;background-color:#faa;margin:10px 0;padding:5px 0 5px 5px}
```

public\assets\numpad\jquery.numpad.css

```
.nmpd-wrapper {display: none;}Ðnmpd-target {cursor: pointer;}Ðnmpd-grid
{position:absolute; left:50px; top:50px; z-index:5000; -khtml-user-select:
none; padding:10px; width: initial;}Ðnmpd-overlay {z-index:4999;}Ðinput.nmpd-
display {text-align: right;}
```

resources\views\vendor\mail\html\themes\default.css

```
body {Ð background-color: #ececec;Ð padding: 0px;Ð margin: 0px; font-family:
Arial,Helvetica,sans-serif;}Ðstrong { font-family: 'HelveticaNeueLTStd-Roman',
Arial,Helvetica,sans-serif;}Ðfont-24 { font-size: 24px!important;}Ðh1, h2, h3,
h4, h5, h6 {Ð font-weight: normal; }Ðimg { max-width: 100%;}Ðtext-center {Ð
text-align: center; }Ðbtn { min-width: 160px; height:50px; padding-left:
15px; padding-right: 15px; line-height: 50px; background-color: #ec7357; text-
transform: uppercase; color:#FFF; font-size:14px; font-family:
'HelveticaNeueLTStd-Md',Arial,Helvetica,sans-serif; display: inline-block;
text-decoration: none; text-align:center;}Ðbtn.round { border-radius: 5px;}Ð
.btn-approval { text-align: center; margin-top: 70px;}Ðemail-wrap {Ð max-
width: 600px;Ð margin: 0 auto;Ð background-color: #FFF; }Ð .email-
wrap .header {Ð   padding:22px 28px; }Ð   .email-wrap .header .logo {Ð
max-width: 130px; }Ð .email-wrap .sub-header {Ð   background-color: #ec7357;Ð
    padding: 35px 28px;Ð   text-align: center; }Ð   .email-wrap .sub-header
h3, .email-wrap .sub-header h4 {Ð     color: #FFF;Ð     margin: 0px;Ð
font-family: 'HelveticaNeueLTStd-Md',Arial,Helvetica,sans-serif;Ð     font-
size: 24px; }Ð   .email-wrap .sub-header h4 {Ð     font-size: 18px; font-
family: 'HelveticaNeueLTStd-Roman',Arial,Helvetica,sans-serif;}Ð .email-
wrap .content {Ð   padding: 28px; }Ð   .email-wrap .content h3 {Ð     font-
family: 'HelveticaNeueLTStd-Roman',Arial,Helvetica,sans-serif;Ð     font-
size: 24px;     word-break: break-word; }Ð   .email-wrap .content p {Ð
font-family: 'HelveticaNeueLTStd-Roman',Arial,Helvetica,sans-serif;Ð     font-
size: 18px;Ð     color: #000;Ð       margin-top: 0px;Ð     line-height:
1.5;     word-break: break-word;}Ðfooter { padding:28px;}Ð     .sm-icons
{ float:right;}Ðsm-icons a { float: left;}Ðsm-icons a + a { margin-left: 8px;}Ð
      .copyrights {Ð         font-size: 12px;Ð         color: #7d7d7d;Ð
          font-family: 'HelveticaNeueLTStd-Lt',Arial,Helvetica,sans-serif;Ð
float: left;Ð   line-height: 28px;}ÐÐbooking-thumb-wrap { max-width:145px;
padding:0 28px; float:left; text-align: center; margin: 5px 0;}Ðbooking-thumb
{ width:145px; height: 145px; border-radius: 50%; overflow: hidden; display:
table-cell; vertical-align: middle;}Ðbooking-thumb img { max-width:145px; max-
height: 145px; width: auto; height: auto; border-radius:50%;}Ðbooking-thumb-
wrap h4 { font-size: 18px; font-family: 'HelveticaNeueLTStd-
Md',Arial,Helvetica,sans-serif; line-height:1.3; margin:5px 0 0;}Ðbooking-
thumb-wrap h4 span { display: block; color: #ec7357;}Ðbooking-detail-box
{ padding:20px 20px; background-color: #FFF; border: #d7d7d7 1px solid;
overflow:hidden; margin:5px 0;}Ðbooking-detail-box h4 { font-size:18px; font-
family: 'HelveticaNeueLTStd-Md',Arial,Helvetica,sans-serif; text-transform:
uppercase; margin: 0px; line-height: 1.3;}Ðbooking-detail-box h4 span
{ color: #ec7357;}Ðbooking-detail-box ul { list-style: none; margin: 0px;
padding: 0px;}Ðbooking-detail-box ul li { display: inline-block; font-family:
'HelveticaNeueLTStd-Roman',Arial,Helvetica,sans-serif;}Ðul.booking-event-types
{ margin: 5px 0 25px;}Ðul.booking-event-types li { position:relative; color:
#ec7357; font-size:14px;}Ðul.booking-event-types li + li { margin-left: 6px;}Ð
ul.booking-event-types li + li:before { content: ''; position: absolute;
width: 1px; background-color: #000; top: 1px; bottom:1px; left:-5px;}Ð
ul.booking-detail { margin-top: 30px;}Ðul.booking-detail li { width: 49%; font-
size:12px; line-height: 26px; margin: 5px 0;}Ðul.booking-detail li.full-width
{ width: 100%;}Ðul.booking-detail li img { width: 21px; float: left;
margin:2px 8px 0 0;}Ðul.booking-detail li i { float: left; margin-right:8px;}Ð
ul.booking-detail li i:before {Ð   font-size: 22px;Ð   color: #000;}ÐÐstatic-
form-group { margin-top:30px;}Ðstatic-form-group h4 { font-size:18px; font-
family: 'HelveticaNeueLTStd-Md',Arial,Helvetica,sans-serif; text-transform:
uppercase; margin:0px 0 10px 0;}Ðstatic-form-control { font-family:
'HelveticaNeueLTStd-Roman',Arial,Helvetica,sans-serif; font-size:18px;
display: inline-block; padding:10px 28px; line-height: 1.4; border:#d7d7d7
1px solid; min-width:230px;}Ðstatic-form-control.special-wish { width:100%;
box-sizing: border-box; padding:28px; border-radius: 5px; border-
color:#ec7357;}Ð
```

```
Đgray-box {Đ   background-color: #ebebeb;Đ   padding: 20px;Đ
margin: 15px 0;Đ   position: relative;ĐĐclearfix:after { content:''; display:
block; clear: both;}Đmedia screen and (max-wdith:767px) {Đ
div[class="booking-detail-box"] { width:100%; margin-top:15px;}Đ
ul[class="booking-detail"] li { width: 100% !important; display:block;
float:none;}Đ   }ĐĐ
```

resources\views\vendor\mail\html\themes\email.css

```
/* CSS Document */Đ@font-face {Đ   font-family: 'HelveticaNeue';Đ   src:
url("fonts/HelveticaNeue.eot");Đ   src: url("fonts/HelveticaNeue.eot")
format("embedded-opentype"), url("fonts/HelveticaNeue.woff2")
format("woff2"), url("fonts/HelveticaNeue.woff") format("woff"), url("fonts/
HelveticaNeue.ttf") format("truetype"), url("fonts/
HelveticaNeue.svg#HelveticaNeue") format("svg");ÞÐ@font-face {Đ   font-family:
'HelveticaNeueLTStd-Lt';Đ   src: url("fonts/333FA9_0_0.eot");Đ   src:
url("fonts/333FA9_0_0.eot?#iefix") format("embedded-opentype"),
url("fonts/333FA9_0_0.woff2") format("woff2"), url("fonts/333FA9_0_0.woff")
format("woff"), url("fonts/333FA9_0_0.ttf") format("truetype");ÞÐ@font-face {Đ
    font-family: 'HelveticaNeueLTStd-Bd';Đ   src: url("fonts/333FA9_1_0.eot");Đ
    src: url("fonts/333FA9_1_0.eot?#iefix") format("embedded-opentype"),
url("fonts/333FA9_1_0.woff2") format("woff2"), url("fonts/333FA9_1_0.woff")
format("woff"), url("fonts/333FA9_1_0.ttf") format("truetype");ÞÐ@font-face {Đ
    font-family: 'HelveticaNeueLTStd-Roman';Đ   src:
url("fonts/333FA9_2_0.eot");Đ   src: url("fonts/333FA9_2_0.eot?#iefix")
format("embedded-opentype"), url("fonts/333FA9_2_0.woff2") format("woff2"),
url("fonts/333FA9_2_0.woff") format("woff"), url("fonts/333FA9_2_0.ttf")
format("truetype");ÞÐ@font-face {Đ   font-family: 'HelveticaNeueLTStd-Th';Đ
src: url("fonts/333FA9_3_0.eot");Đ   src: url("fonts/333FA9_3_0.eot?#iefix")
format("embedded-opentype"), url("fonts/333FA9_3_0.woff2") format("woff2"),
url("fonts/333FA9_3_0.woff") format("woff"), url("fonts/333FA9_3_0.ttf")
format("truetype");ÞÐ@font-face {Đ   font-family: 'HelveticaNeueLTStd-Md';Đ
src: url("fonts/333FA9_4_0.eot");Đ   src: url("fonts/333FA9_4_0.eot?#iefix")
format("embedded-opentype"), url("fonts/333FA9_4_0.woff2") format("woff2"),
url("fonts/333FA9_4_0.woff") format("woff"), url("fonts/333FA9_4_0.ttf")
format("truetype");ÞÐbody {Đ   background-color: #ececec;Đ   padding: 0px;Đ
margin: 0px;ÞÐh1, h2, h3, h4, h5, h6 {Đ   font-weight: normal;ÞÐtext-center {Đ
    text-align: center;ÞÐemail-wrap {Đ   max-width: 600px;Đ   margin: 0 auto;Đ
    background-color: #FFF;ÞÐemail-wrap .header {Đ   padding: 28px;ÞÐemail-
wrap .header .logo {Đ   max-width: 130px;ÞÐemail-wrap .sub-header {Đ
background-color: #ec7357;Đ   padding: 35px 28px;Đ   text-align: center;ÞÐ
.email-wrap .sub-header h3, .email-wrap .sub-header h4 {Đ   color: #FFF;Đ
margin: 0px;Đ   font-family: 'HelveticaNeueLTStd-Md';Đ   font-size: 24px;ÞÐ
.email-wrap .sub-header h4 {Đ   font-size: 18px;ÞÐemail-wrap .content {Đ
padding: 28px;ÞÐemail-wrap .content h3 {Đ   font-family: 'HelveticaNeueLTStd-
Roman';Đ   font-size: 24px;ÞÐemail-wrap .content p {Đ   font-family:
'HelveticaNeueLTStd-Roman';Đ   font-size: 18px;Đ   color: #000;Đ   line-
height: 1.5;ÞÐ
```

vendor\filp\whoops\src\Whoops\Resources\css\whoops.base.css

body {Ð font: 12px "Helvetica Neue", helvetica, arial, sans-serif;Ð color: #131313;Ð background: #eeeeee;Ð padding:0;Ð margin: 0;Ð max-height: 100%;Ð text-rendering: optimizeLegibility;ÐÐ a {Ð text-decoration: none;Ð }Ð .Whoops.container {Ð position: relative;Ð z-index: 9999999999;ÐÐpanel {Ð overflow-y: scroll;Ð height: 100%;Ð position: fixed;Ð margin: 0;Ð left: 0;Ð top: 0;ÐÐbranding {Ð position: absolute;Ð top: 10px;Ð right: 20px;Ð color: #777777;Ð font-size: 10px;Ð z-index: 100;ÐÐ .branding a {Ð color: #e95353;Ð }Ðeader {Ð color: white;Ð box-sizing: border-box;Ð background-color: #2a2a2a;Ð padding: 35px 40px;Ð max-height: 180px;Ð overflow: hidden;Ð transition: 0.5s;ÐÐ header.header-expand {Ð max-height: 1000px;Ð }Ð .exc-title {Ð margin: 0;Ð color: #bebebe;Ð font-size: 14px;Ð }Ð .exc-title-primary, .exc-title-secondary {Ð color: #e95353;Ð }Ð .exc-message {Ð font-size: 20px;Ð word-wrap: break-word;Ð margin: 4px 0 0 0;Ð color: white;Ð }Ð .exc-message span {Ð display: block;Ð }Ð .exc-message-empty-notice {Ð color: #a29d9d;Ð font-weight: 300;Ð }Ðprev-exc-title {Ð margin: 10px 0;ÐÐprev-exc-title + ul {Ð margin: 0;Ð padding: 0 0 0 20px;Ð line-height: 12px;ÐÐprev-exc-title + ul li {Ð font: 12px "Helvetica Neue", helvetica, arial, sans-serif;ÐÐ .prev-exc-title + ul li .prev-exc-code {Ð display: inline-block;Ð color: #bebebe;ÐÐdetails-container {Ð left: 30%;Ð width: 70%;Ð background: #fafafa;ÐÐ .details {Ð padding: 5px;Ð }Ð .details-heading {Ð color: #4288CE;Ð font-weight: 300;Ð padding-bottom: 10px;Ð margin-bottom: 10px;Ð border-bottom: 1px solid rgba(0, 0, 0, .1);Ð }Ð .details pre.sf-dump {Ð white-space: pre;Ð word-wrap: inherit;Ð }Ð .details pre.sf-dump,Ð .details pre.sf-dump .sf-dump-num,Ð .details pre.sf-dump .sf-dump-const,Ð .details pre.sf-dump .sf-dump-str,Ð .details pre.sf-dump .sf-dump-note,Ð .details pre.sf-dump .sf-dump-ref,Ð .details pre.sf-dump .sf-dump-public,Ð .details pre.sf-dump .sf-dump-protected,Ð .details pre.sf-dump .sf-dump-private,Ð .details pre.sf-dump .sf-dump-meta,Ð .details pre.sf-dump .sf-dump-key,Ð .details pre.sf-dump .sf-dump-index {Ð color: #463C54;Ð }Ðleft-panel {Ð width: 30%;Ð background: #ded8d8;ÐÐ .frames-description {Ð background: rgba(0, 0, 0, .05);Ð padding: 8px 15px;Ð color: #a29d9d;Ð font-size: 11px;Ð }Ð .frames-description.frames-description-application {Ð text-align: center;Ð font-size: 12px;Ð }Ð .frames-container.frames-container-application .frame:not(.frame-application) {Ð display: none;Ð }Ð .frames-tab {Ð color: #a29d9d;Ð display: inline-block;Ð padding: 4px 8px;Ð margin: 0 2px;Ð border-radius: 3px;Ð }Ð .frames-tab.frames-tab-active {Ð background-color: #2a2a2a;Ð color: #bebebe;Ð }Ð .frame {Ð padding: 14px;Ð cursor: pointer;Ð transition: all 0.1s ease;Ð background: #eeeeee;Ð }Ð .frame:not(:last-child) {Ð border-bottom: 1px solid rgba(0, 0, 0, .05);Ð }Ð .frame.active {Ð box-shadow: inset -5px 0 0 0 #4288CE;Ð color: #4288CE;Ð }Ð .frame:not(.active):hover {Ð background: #BEE9EA;Ð }Ð .frame-method-info {Ð margin-bottom: 10px;Ð }Ð .frame-class, .frame-function, .frame-index {Ð font-size: 14px;Ð }Ð .frame-index {Ð float: left;Ð }Ð .frame-method-info {Ð margin-left: 24px;Ð }Ð .frame-index {Ð font-size: 11px;Ð color: #a29d9d;Ð background-color: rgba(0, 0, 0, .05);Ð height: 18px;Ð width: 18px;Ð line-height: 18px;Ð border-radius: 5px;Ð padding: 0 1px 0 1px;Ð text-align: center;Ð display: inline-block;Ð }Ð .frame-application .frame-index {Ð background-color: #2a2a2a;Ð color: #bebebe;Ð }Ð .frame-file {Ð font-family: "Inconsolata", "Fira Mono", "Source Code Pro", Monaco, Consolas, "Lucida Console", monospace;Ð color: #a29d9d;Ð }Ð .frame-file .editor-link {Ð color: #a29d9d;Ð }Ð .frame-line {Ð font-weight: bold;Ð }Ð .frame-line:before {Ð content: ":";Ð }Ð .frame-code {Ð padding: 5px;Ð background: #303030;Ð display: none;Ð }Ð .frame-code.active {Ð display: block;Ð }Ð .frame-code .frame-file {Ð color: #a29d9d;Ð padding: 12px 6px;Ð

Ð border-bottom: none;Ð }Ð .code-block {Ð padding: 10px;Ð margin: 0;Ð border-radius: 6px;Ð box-shadow: 0 3px 0 rgba(0, 0, 0, .05),Ð 0 10px 30px rgba(0, 0, 0, .05),Ð inset 0 0 1px 0 rgba(255, 255, 255, .07);Ð -moz-tab-size: 4;Ð -o-tab-size: 4;Ð tab-size: 4;Ð }Ð .linenums {Ð margin: 0;Ð margin-left: 10px;Ð }Ð .frame-comments {Ð border-top: none;Ð margin-top: 15px;Ð font-size: 12px;Ð }Ð .frame-comments.empty {Ð }Ð .frame-comments.empty:before {Ð content: "No comments for this stack frame.";Ð font-weight: 300;Ð color: #a29d9d;Ð }Ð .frame-comment {Ð padding: 10px;Ð color: #e3e3e3;Ð border-radius: 6px;Ð background-color: rgba(255, 255, 255, .05);Ð }Ð .frame-comment a {Ð font-weight: bold;Ð text-decoration: underline;Ð color: #c6c6c6;Ð }Ð .frame-comment:not(:last-child) {Ð border-bottom: 1px dotted rgba(0, 0, 0, .3);Ð }Ð .frame-comment-context {Ð font-size: 10px;Ð color: white;Ð }Ðdelimiter {Ð display: inline-block;ÐÐdata-table-container label {Ð font-size: 16px;Ð color: #303030;Ð font-weight: bold;Ð margin: 10px 0;Ð display: block;Ð margin-bottom: 5px;Ð padding-bottom: 5px;ÐÐ .data-table {Ð width: 100%;Ð margin-bottom: 10px;Ð }Ð .data-table tbody {Ð font: 13px "Inconsolata", "Fira Mono", "Source Code Pro", Monaco, Consolas, "Lucida Console", monospace;Ð }Ð .data-table thead {Ð display: none;Ð }Ð .data-table tr {Ð padding: 5px 0;Ð }Ð .data-table td:first-child {Ð width: 20%;Ð min-width: 130px;Ð overflow: hidden;Ð font-weight: bold;Ð color: #463C54;Ð padding-right: 5px;Ð }Ð .data-table td:last-child {Ð width: 80%;Ð -ms-word-break: break-all;Ð word-break: break-all;Ð word-break: break-word;Ð -webkit-hyphens: auto;Ð -moz-hyphens: auto;Ð hyphens: auto;Ð }Ð .data-table span.empty {Ð color: rgba(0, 0, 0, .3);Ð font-weight: 300;Ð }Ð .data-table label.empty {Ð display: inline;Ð }Ðhandler {Ð padding: 4px 0;Ð font: 14px "Inconsolata", "Fira Mono", "Source Code Pro", Monaco, Consolas, "Lucida Console", monospace;ÐÐplain-exception {Ð display: none;ÐÐ .rightButton {Ð cursor: pointer;Ð border: 0;Ð opacity: .8;Ð background: none;Ð color: rgba(255, 255, 255, 0.1);Ð box-shadow: inset 0 0 0 2px rgba(255, 255, 255, 0.1);Ð border-radius: 3px;Ð outline: none !important;ÐÐ .rightButton:hover {Ð box-shadow: inset 0 0 0 2px rgba(255, 255, 255, 0.3);Ð color: rgba(255, 255, 255, 0.3);Ð }ÐÐ* inspired by githubs kbd styles */kbd {Ð -moz-border-bottom-colors: none;Ð -moz-border-left-colors: none;Ð -moz-border-right-colors: none;Ð -moz-border-top-colors: none;Ð background-color: #fcfcfc;Ð border-color: #ccc #ccc #bbb;Ð border-image: none;Ð border-style: solid;Ð border-width: 1px;Ð color: #555;Ð display: inline-block;Ð font-size: 11px;Ð line-height: 10px;Ð padding: 3px 5px;Ð vertical-align: middle;ÐÐ * == Media queries */ÐÐ* Expand the spacing in the details section */@media (min-width: 1000px) {Ð .details, .frame-code {Ð padding: 20px 40px;Ð }Ð .details-container {Ð left: 32%;Ð width: 68%;Ð }Ð .frames-container {Ð margin: 5px;Ð }Ð .left-panel {Ð width: 32%;Ð }ÐÐ* Stack panels */@media (max-width: 600px) {Ð .panel {Ð position: static;Ð width: 100%;Ð }ÐÐ* Stack details tables */@media (max-width: 400px) {Ð .data-table,Ð .data-table tbody,Ð .data-table tbody tr,Ð .data-table tbody td {Ð display: block;Ð width: 100%;Ð }Ð .data-table tbody tr:first-child {Ð padding-top: 0;Ð }Ð .data-table tbody td:first-child,Ð .data-table tbody td:last-child {Ð padding-left: 0;Ð padding-right: 0;Ð }Ð .data-table tbody td:last-child {Ð padding-top: 3px;Ð }ÐÐtooltipped {Ð position: relativeÐÐtooltipped:after {Ð position: absolute;Ð z-index: 1000000;Ð display: none;Ð padding: 5px 8px;Ð color: #fff;Ð text-align: center;Ð text-decoration: none;Ð text-shadow: none;Ð text-transform: none;Ð letter-spacing: normal;Ð word-wrap: break-word;Ð white-space: pre;Ð pointer-events: none;Ð content: attr(aria-label);Ð background: rgba(0, 0, 0, 0.8);Ð border-radius: 3px;Ð -webkit-font-smoothing: subpixel-antialiasedÐÐtooltipped:before {Ð position: absolute;Ð z-index: 1000001;Ð display: none;Ð width: 0;Ð height: 0;Ð color: rgba(0, 0, 0, 0.8);Ð pointer-events: none;Ð content: "";Ð border: 5px solid transparentÐÐtooltipped:hover:before,Ðtooltipped:hover:after,Ð .tooltipped:active:before,Ð

.tooltipped:active:after,Ðtooltipped:focus:before,Ð .tooltipped:focus:after {Ð display: inline-block;Ð text-decoration: noneÞÐ .tooltipped-s:after {Ð top: 100%;Ð right: 50%;Ð margin-top: 5pxÞÐtooltipped-s:before {Ð top: auto;Ð right: 50%;Ð bottom: -5px;Ð margin-right: -5px;Ð border-bottom-color: rgba(0, 0, 0, 0.8)ÞÐpre.sf-dump {Ð padding: 0px !important;Ð margin: 0px !important;ÞÐsearch-for-help {Ð width: 85%;Ð padding: 0;Ð margin: 10px 0;Ð list-style-type: none;Ð display: inline-block;ÞÐ .search-for-help li {Ð display: inline-block;Ð margin-right: 5px;Ð }Ð .search-for-help li:last-child {Ð margin-right: 0;Ð }Ð .search-for-help li a {Ð }Ð .search-for-help li a i {Ð width: 16px;Ð height: 16px;Ð overflow: hidden;Ð display: block;Ð }Ð .search-for-help li a svg {Ð fill: #fff;Ð }Ð .search-for-help li a svg path {Ð background-size: contain;Ð }Ðline-numbers-rows span {Ð pointer-events: auto;Ð cursor: pointer;ÞÐline-numbers-rows span:hover {Ð text-decoration: underline;ÞÐ

vendor\laravel\breeze\stubs\default\resources\css\app.css

```
@tailwind base;@tailwind components;@tailwind utilities;Ð
```

vendor\laravel\framework\src\Illuminate\Mail\resources\views\html\themes\default.css

/* Base */Ðbody,Ðbody *:not(html):not(style):not(br):not(tr):not(code) {Ð box-sizing: border-box;Ð font-family: -apple-system, BlinkMacSystemFont, 'Segoe UI', Roboto, Helvetica, Arial, sans-serif,Ð 'Apple Color Emoji', 'Segoe UI Emoji', 'Segoe UI Symbol';Ð position: relative;ÐÐbody {Ð -webkit-text-size-adjust: none;Ð background-color: #ffffff;Ð color: #718096;Ð height: 100%;Ð line-height: 1.4;Ð margin: 0;Ð padding: 0;Ð width: 100% !important;ÐÐp,Ðul,Ðol,Ðblockquote {Ð line-height: 1.4;Ð text-align: left;ÐÐa {Ð color: #3869d4;ÐÐa img {Ð border: none;ÐÐ* Typography */Ðh1 {Ð color: #3d4852;Ð font-size: 18px;Ð font-weight: bold;Ð margin-top: 0;Ð text-align: left;ÐÐh2 {Ð font-size: 16px;Ð font-weight: bold;Ð margin-top: 0;Ð text-align: left;ÐÐh3 {Ð font-size: 14px;Ð font-weight: bold;Ð margin-top: 0;Ð text-align: left;ÐÐp {Ð font-size: 16px;Ð line-height: 1.5em;Ð margin-top: 0;Ð text-align: left;ÐÐp.sub {Ð font-size: 12px;ÐÐimg {Ð max-width: 100%;ÐÐ* Layout */Ðwrapper {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 100%;Ð background-color: #edf2f7;Ð margin: 0;Ð padding: 0;Ð width: 100%;ÐÐ.content {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 100%;Ð margin: 0;Ð padding: 0;Ð width: 100%;ÐÐ* Header */Ðheader {Ð padding: 25px 0;Ð text-align: center;ÐÐheader a {Ð color: #3d4852;Ð font-size: 19px;Ð font-weight: bold;Ð text-decoration: none;ÐÐ* Logo */Ðlogo {Ð height: 75px;Ð max-height: 75px;Ð width: 75px;ÐÐ* Body */Ðbody {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 100%;Ð background-color: #edf2f7;Ð border-bottom: 1px solid #edf2f7;Ð border-top: 1px solid #edf2f7;Ð margin: 0;Ð padding: 0;Ð width: 100%;ÐÐinner-body {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 570px;Ð background-color: #ffffff;Ð border-color: #e8e5ef;Ð border-radius: 2px;Ð border-width: 1px;Ð box-shadow: 0 2px 0 rgba(0, 0, 150, 0.025), 2px 4px 0 rgba(0, 0, 150, 0.015);Ð margin: 0 auto;Ð padding: 0;Ð width: 570px;ÐÐ* Subcopy */Ðsubcopy {Ð border-top: 1px solid #e8e5ef;Ð margin-top: 25px;Ð padding-top: 25px;ÐÐ.subcopy p {Ð font-size: 14px;ÐÐ* Footer */Ðfooter {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 570px;Ð margin: 0 auto;Ð padding: 0;Ð text-align: center;Ð width: 570px;ÐÐ.footer p {Ð color: #b0adc5;Ð font-size: 12px;Ð text-align: center;ÐÐ.footer a {Ð color: #b0adc5;Ð text-decoration: underline;ÐÐ* Tables */Ð.table table {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 100%;Ð margin: 30px auto;Ð width: 100%;ÐÐtable th {Ð border-bottom: 1px solid #edeff2;Ð margin: 0;Ð padding-bottom: 8px;ÐÐ.table td {Ð color: #74787e;Ð font-size: 15px;Ð line-height: 18px;Ð margin: 0;Ð padding: 10px 0;ÐÐcontent-cell {Ð max-width: 100vw;Ð padding: 32px;ÐÐ* Buttons */Ðaction {Ð -premailer-cellpadding: 0;Ð -premailer-cellspacing: 0;Ð -premailer-width: 100%;Ð margin: 30px auto;Ð padding: 0;Ð text-align: center;Ð width: 100%;ÐÐbutton {Ð -webkit-text-size-adjust: none;Ð border-radius: 4px;Ð color: #fff;Ð display: inline-block;Ð overflow: hidden;Ð text-decoration: none;ÐÐbutton-blue,Ðbutton-primary {Ð background-color: #2d3748;Ð border-bottom: 8px solid #2d3748;Ð border-left: 18px solid #2d3748;Ð border-right: 18px solid #2d3748;Ð border-top: 8px solid #2d3748;ÐÐbutton-green,Ðbutton-success {Ð background-color: #48bb78;Ð border-bottom: 8px solid #48bb78;Ð border-left: 18px solid #48bb78;Ð border-right: 18px solid #48bb78;Ð border-top: 8px solid #48bb78;ÐÐbutton-red,Ðbutton-error {Ð background-color: #e53e3e;Ð border-bottom: 8px solid #e53e3e;Ð border-left: 18px solid #e53e3e;Ð border-right: 18px solid #e53e3e;Ð border-top: 8px solid #e53e3e;ÐÐ* Panels */Ð.panel {Ð border-left: #2d3748 solid 4px;Ð margin: 21px 0;ÐÐpanel-content {Ð background-color: #edf2f7;Ð color: #718096;Ð padding: 16px;ÐÐpanel-content p {Ð color: #718096;ÐÐpanel-item {Ð padding: 0;ÐÐpanel-item p:last-of-type {Ð

```
    margin-bottom: 0;Đ   padding-bottom: 0;ÞÐÐ* Utilities */Đ
.break-all {Đ   word-break: break-all;ÞÐ
```

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\css\octicons.css

```
.octicon {Ð display: inline-block;Ð vertical-align: text-top;Ð fill:
currentColor;ÐÐ
}
```

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\css\style.css

body {Ðfont-family: sans-serif;Ðfont-size: 1em;Ðfont-kerning: normal;Ðfont-variant-ligatures: common-ligatures;Ðtext-rendering: optimizeLegibility;Ð padding-top: 10px;ÞÐpopover {Ðmax-width: none;ÞÐocticon {Ðmargin-right:.25em;Ð vertical-align: baseline;Ðwidth: 0.75em;ÞÐtable-bordered>thead>tr>td {Ðborder-bottom-width: 1px;ÞÐtable tbody>tr>td, .table thead>tr>td {Ðpadding-top: 3px;Ð padding-bottom: 3px;ÞÐtable-condensed tbody>tr>td {Ðpadding-top: 0;Ðpadding-bottom: 0;ÞÐtable .progress {Ðmargin-bottom: inherit;ÞÐtable-borderless th, .table-borderless td {Ðborder: 0 !important;ÞÐtable tbody tr.covered-by-large-tests, li.covered-by-large-tests, tr.success, td.success, li.success, span.success {Ðbackground-color: #dff0d8;ÞÐtable tbody tr.covered-by-medium-tests, li.covered-by-medium-tests {Ðbackground-color: #c3e3b5;ÞÐtable tbody tr.covered-by-small-tests, li.covered-by-small-tests {Ðbackground-color: #99cb84;ÞÐtable tbody tr.danger, .table tbody td.danger, li.danger, span.danger {Ðbackground-color: #f2dede;ÞÐtable tbody tr.warning, .table tbody td.warning, li.warning, span.warning {Ðbackground-color: #fcf8e3;ÞÐ .table tbody td.info {Ðbackground-color: #d9edf7;ÞÐd.big {Ðvertical-align: middle;Ðwidth: 117px;ÞÐd.small {ÞÐd.codeLine {Ðfont-family: "Source Code Pro", "SFMono-Regular", Menlo, Monaco, Consolas, "Liberation Mono", "Courier New", monospace;Ðwhite-space: pre-wrap;ÞÐd span.comment {Ðcolor: #888a85;ÞÐd span.default {Ðcolor: #2e3436;ÞÐd span.html {Ðcolor: #888a85;ÞÐd span.keyword {Ðcolor: #2e3436;Ðfont-weight: bold;ÞÐpre span.string {Ðcolor: #2e3436;ÞÐ span.success, span.warning, span.danger {Ðmargin-right: 2px;Ðpadding-left: 10px;Ðpadding-right: 10px;Ðtext-align: center;ÞÐtoplink {Ðposition: fixed;Ð left: 5px;Ðbottom: 5px;Ðoutline: 0;ÞÐsvg text {Ðfont-family: "Lucida Grande", "Lucida Sans Unicode", Verdana, Arial, Helvetica, sans-serif;Ðfont-size: 11px;Ð color: #666;Ðfill: #666;ÞÐscrollbox {Ðheight:245px;Ðoverflow-x:scroll;Ð overflow-y:scroll;ÞÐable + .structure-heading {Ðborder-top: 1px solid lightgrey;Ðpadding-top: 0.5em;ÞÐlegend {Ðfont-weight: bold;Ðmargin-right: 2px;Ð padding-left: 10px;Ðpadding-right: 10px;Ðtext-align: center;ÞÐcovered-by-small-tests {Ðbackground-color: #99cb84;ÞÐcovered-by-medium-tests {Ð background-color: #c3e3b5;ÞÐcovered-by-large-tests {Ðbackground-color: #dff0d8;ÞÐnot-covered {Ðbackground-color: #f2dede;ÞÐnot-coverable {Ð background-color: #fcf8e3;ÞÐ

vendor\symfony\error-handler\Resources\assets\css\error.css

```
body { background-color: #fff; color: #222; font: 16px/1.5 -apple-system,
BlinkMacSystemFont, "Segoe UI", Roboto, "Helvetica Neue", Arial, sans-serif;
margin: 0; }Ðcontainer { margin: 30px; max-width: 600px; }Ðh1 { color:
#dc3545; font-size: 24px; }Ðh2 { font-size: 18px; }Ð
```

vendor\symfony\error-handler\Resources\assets\css\exception_full.css

.sf-reset .traces {Ð   padding-bottom: 14px;ÐÐsf-reset .traces li {Ð   font-size: 12px;Ð   color: #868686;Ð   padding: 5px 4px;Ð   list-style-type: decimal;Ð   margin-left: 20px;ÐÐsf-reset #logs .traces li.error {Ð   font-style: normal;Ð   color: #AA3333;Ð   background: #f9ecec;ÐÐsf-reset #logs .traces li.warning {Ð   font-style: normal;Ð   background: #ffcc00;ÐØ* fix for Opera not liking empty <li> */Ðsf-reset .traces li:after {Ð   content: "\00A0";ÐÐsf-reset .trace {Ð   border: 1px solid #D3D3D3;Ð   padding: 10px;Ð   overflow: auto;Ð   margin: 10px 0 20px;ÐÐsf-reset .block-exception {Ð   -moz-border-radius: 16px;Ð   -webkit-border-radius: 16px;Ð   border-radius: 16px;Ð   margin-bottom: 20px;Ð   background-color: #f6f6f6;Ð   border: 1px solid #dfdfdf;Ð   padding: 30px 28px;Ð   word-wrap: break-word;Ð   overflow: hidden;ÐÐsf-reset .block-exception div {Ð   color: #313131;Ð   font-size: 10px;ÐÐsf-reset .block-exception-detected .illustration-exception,Ð   .sf-reset .block-exception-detected .text-exception {Ð   float: left;ÐÐsf-reset .block-exception-detected .illustration-exception {Ð   width: 152px;ÐÐ   .sf-reset .block-exception-detected .text-exception {Ð   width: 670px;Ð   padding: 30px 44px 24px 46px;Ð   position: relative;ÐÐsf-reset .text-exception .open-quote,Ðsf-reset .text-exception .close-quote {Ð   font-family: Arial, Helvetica, sans-serif;Ð   position: absolute;Ð   color: #C9C9C9;Ð   font-size: 8em;ÐÐsf-reset .open-quote {Ð   top: 0;Ð   left: 0;ÐÐ   .sf-reset .close-quote {Ð   bottom: -0.5em;Ð   right: 50px;ÐÐsf-reset .block-exception p {Ð   font-family: Arial, Helvetica, sans-serif;ÐÐsf-reset .block-exception p a,Ðsf-reset .block-exception p a:hover {Ð   color: #565656;ÐÐsf-reset .logs h2 {Ð   float: left;Ð   width: 654px;ÐÐsf-reset .error-count, .sf-reset .support {Ð   float: right;Ð   width: 170px;Ð   text-align: right;ÐÐsf-reset .error-count span {Ð   display: inline-block;Ð   background-color: #aacd4e;Ð   -moz-border-radius: 6px;Ð   -webkit-border-radius: 6px;Ð   border-radius: 6px;Ð   padding: 4px;Ð   color: white;Ð   margin-right: 2px;Ð   font-size: 11px;Ð   font-weight: bold;ÐÐsf-reset .support a {Ð   display: inline-block;Ð   -moz-border-radius: 6px;Ð   -webkit-border-radius: 6px;Ð   border-radius: 6px;Ð   padding: 4px;Ð   color: #000000;Ð   margin-right: 2px;Ð   font-size: 11px;Ð   font-weight: bold;ÐÐsf-reset .toggle {Ð   vertical-align: middle;ÐÐsf-reset .linked ul,Ðsf-reset .linked li {Ð   display: inline;ÐÐsf-reset #output-content {Ð   color: #000;Ð   font-size: 12px;ÐÐsf-reset #traces-text pre {Ð   white-space: pre;Ð   font-size: 12px;Ð   font-family: monospace;Ð   }Ð

vendor\symfony\var-dumper\Resources\css\htmlDescriptor.css

```
body {Ð   display: flex;Ð   flex-direction: column-reverse;Ð   justify-
content: flex-end;Ð   max-width: 1140px;Ð   margin: auto;Ð   padding: 15px;Ð
    word-wrap: break-word;Ð   background-color: #F9F9F9;Ð   color: #222;Ð
font-family: Helvetica, Arial, sans-serif;Ð   font-size: 14px;Ð   line-
height: 1.4;ÞÞ {Ð   margin: 0;ÞÞ {Ð   color: #218BC3;Ð   text-decoration:
none;ÞÞ:hover {Ð   text-decoration: underline;ÞÞtext-small {Ð   font-size:
12px !important;ÞÞarticle {Ð   margin: 5px;Ð   margin-bottom: 10px;ÞÞarticle >
header > .row {Ð   display: flex;Ð   flex-direction: row;Ð   align-items:
baseline;Ð   margin-bottom: 10px;ÞÞarticle > header > .row > .col {Ð   flex: 1;Ð
    display: flex;Ð   align-items: baseline;ÞÞarticle > header > .row > h2 {Ð
    font-size: 14px;Ð   color: #222;Ð   font-weight: normal;Ð   font-family:
"Lucida Console", monospace, sans-serif;Ð   word-break: break-all;Ð   margin:
20px 5px 0 0;Ð   user-select: all;ÞÞarticle > header > .row > h2 > code {Ð
white-space: nowrap;Ð   user-select: none;Ð   color: #cc2255;Ð   background-
color: #f7f7f9;Ð   border: 1px solid #e1e1e8;Ð   border-radius: 3px;Ð
margin-right: 5px;Ð   padding: 0 3px;ÞÞarticle > header > .row > time.col {Ð
flex: 0;Ð   text-align: right;Ð   white-space: nowrap;Ð   color: #999;Ð
font-style: italic;ÞÞarticle > header ul.tags {Ð   list-style: none;Ð
padding: 0;Ð   margin: 0;Ð   font-size: 12px;ÞÞarticle > header ul.tags > li {Ð
    user-select: all;Ð   margin-bottom: 2px;ÞÞarticle > header ul.tags > li >
span.badge {Ð   display: inline-block;Ð   padding: .25em .4em;Ð   margin-
right: 5px;Ð   border-radius: 4px;Ð   background-color: #6c757d3b;Ð   color:
#524d4d;Ð   font-size: 12px;Ð   text-align: center;Ð   font-weight: 700;Ð
line-height: 1;Ð   white-space: nowrap;Ð   vertical-align: baseline;Ð   user-
select: none;ÞÞarticle > section.body {Ð   border: 1px solid #d8d8d8;Ð
background: #FFF;Ð   padding: 10px;Ð   border-radius: 3px;ÞÞpre.sf-dump {Ð
border-radius: 3px;Ð   margin-bottom: 0;ÞÞhidden {Ð   display: none !
important;ÞÞdumped-tag > .sf-dump {Ð   display: inline-block;Ð   margin: 0;Ð
    padding: 1px 5px;Ð   line-height: 1.4;Ð   vertical-align: top;Ð
background-color: transparent;Ð   user-select: auto;ÞÞdumped-tag > pre.sf-
dump,Ðdumped-tag > .sf-dump-default {Ð   color: #CC7832;Ð   background: none;ÞÐ
.dumped-tag > .sf-dump .sf-dump-str { color: #629755; }Ðdumped-tag > .sf-
dump .sf-dump-private,Ðdumped-tag > .sf-dump .sf-dump-protected,Ðdumped-tag
> .sf-dump .sf-dump-public { color: #262626; }Ðdumped-tag > .sf-dump .sf-dump-
note { color: #6897BB; }Ðdumped-tag > .sf-dump .sf-dump-key { color:
#789339; }Ðdumped-tag > .sf-dump .sf-dump-ref { color: #6E6E6E; }Ðdumped-tag
> .sf-dump .sf-dump-ellipsis { color: #CC7832; max-width: 100em; }Ðdumped-tag
> .sf-dump .sf-dump-ellipsis-path { max-width: 5em; }Ðdumped-tag > .sf-
dump .sf-dump-ns { user-select: none; }Ð
```

.vscode\launch.json

```
{Ð   // Use IntelliSense to learn about possible attributes.Ð   // Hover to
view descriptions of existing attributes.Ð   // For more information, visit:
https://go.microsoft.com/fwlink/?linkid=830387Ð   "version": "0.2.0",Ð
"configurations": [Ð       {Ð           "type": "chrome",Ð
"request": "launch",Ð           "name": "Launch Chrome against localhost",Ð
            "url": "http://localhost:8080",Ð           "webRoot":
"${workspaceFolder}"Ð       }Ð   ]Ð}
```

composer.json

{Ð "name": "laravel/laravel",Ð "type": "project",Ð "description": "The Laravel Framework.",Ð "keywords": ["framework", "laravel"],Ð "license": "MIT",Ð "require": {Ð "php": "^8.0.2",Ð "barryvdh/laravel-dompdf": "^1.0",Ð "barryvdh/laravel-translation-manager": "dev-master",Ð "doctrine/dbal": "^3.9",Ð "guzzlehttp/guzzle": "^7.2",Ð "intervention/image": "^2.7",Ð "laravel/framework": "^9.11",Ð "laravel/sanctum": "^2.14.1",Ð "laravel/tinker": "^2.7",Ð "laravel/ui": "^3.4",Ð "stripe/stripe-php": "^4.7",Ð "symfony/browser-kit": "^7.2",Ð "symfony/css-selector": "^7.2",Ð "symfony/http-client": "^7.2"Ð },Ð "require-dev": {Ð "fakerphp/faker": "^1.9.1",Ð "kitloong/laravel-migrations-generator": "^6.7",Ð "laravel/breeze": "^1.9",Ð "laravel/sail": "^1.0.1",Ð "mockery/mockery": "^1.4.4",Ð "nunomaduro/collision": "^6.1",Ð "phpunit/phpunit": "^9.5.10",Ð "spatie/laravel-ignition": "^1.0"Ð },Ð "autoload": {Ð "psr-4": {Ð "App\\": "app/",Ð "Database\\Factories\\": "database/factories/",Ð "Database\\Seeders\\": "database/seeders/"Ð },Ð "files": [Ð "app/Helpers/DiscountHelper.php",Ð Ð Ð "app/Helpers.php"Ð Ð]Ð },Ð Ð "autoload-dev": {Ð "psr-4": {Ð "Tests\\": "tests/"Ð }Ð },Ð "scripts": {Ð "post-autoload-dump": [Ð "Illuminate\\Foundation\\ComposerScripts::postAutoloadDump",Ð "@php artisan package:discover --ansi"Ð],Ð "post-update-cmd": [Ð "@php artisan vendor:publish --tag=laravel-assets --ansi --force"Ð],Ð "post-root-package-install": [Ð "@php -r \"file_exists('.env') || copy('.env.example', '.env');\""Ð],Ð "post-create-project-cmd": [Ð "@php artisan key:generate --ansi"Ð]Ð },Ð "extra": {Ð "laravel": {Ð "dont-discover": []Ð }Ð },Ð "config": {Ð "optimize-autoloader": true,Ð "preferred-install": "dist",Ð "sort-packages": trueÐ },Ð "minimum-stability": "dev",Ð "prefer-stable": trueÐÐ}

package.json

{Ð "private": true,Ð "scripts": {Ð "dev": "npm run development",Ð "development": "mix",Ð "watch": "mix watch",Ð "watch-poll": "mix watch -- --watch-options-poll=1000",Ð "hot": "mix watch --hot",Ð "prod": "npm run production",Ð "production": "mix --production"Ð },Ð "devDependencies": {Ð "@popperjs/core": "^2.10.2",Ð "axios": "^0.25",Ð "bootstrap": "^5.1.3",Ð "laravel-mix": "^6.0.6",Ð "lodash": "^4.17.19",Ð "postcss": "^8.1.14",Ð "sass": "^1.32.11",Ð "sass-loader": "^11.0.1"Ð }ÐÐ}

vendor\barryvdh\laravel-dompdf\composer.json

{Ð   "name": "barryvdh/laravel-dompdf",Ð   "description": "A DOMPDF Wrapper for Laravel",Ð   "license": "MIT",Ð   "keywords": ["laravel", "dompdf", "pdf"],Ð   "authors": [Ð   {Ð   "name": "Barry vd. Heuvel",Ð   "email": "barryvdh@gmail.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2 || ^8.0",Ð   "dompdf/dompdf": "^1.2.1",Ð   "illuminate/support": "^6|^7|^8|^9"Ð   },Ð   "require-dev": {Ð   "orchestra/testbench": "^4|^5|^6|^7",Ð   "squizlabs/php_codesniffer": "^3.5",Ð   "phpro/grumphp": "^1",Ð   "nunomaduro/larastan": "^1|^2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Barryvdh\\DomPDF\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Barryvdh\\DomPDF\\Tests\\": "tests"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "Barryvdh\\DomPDF\\ServiceProvider"Ð   ],Ð   "aliases": {Ð   "PDF": "Barryvdh\\DomPDF\\Facade\\Pdf"Ð   }Ð   }Ð   },Ð   "scripts": {Ð   "test": "phpunit",Ð   "check-style": "phpcs -p --standard=psr12 src/",Ð   "fix-style": "phpcbf -p --standard=psr12 src/",Ð   "phpstan": "phpstan analyze --memory-limit=-1"Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "config": {Ð   "allow-plugins": {Ð   "phpro/grumphp": trueÐ   }Ð   }Ð}Ð

vendor\barryvdh\laravel-translation-manager\composer.json

{Ð "name": "barryvdh/laravel-translation-manager",Ð "description": "Manage Laravel Translations",Ð "keywords": [Ð "laravel",Ð "translations",Ð "translator"Ð],Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Barry vd. Heuvel",Ð "email": "barryvdh@gmail.com"Ð }Ð],Ð "require": {Ð "php": "^8.1",Ð "illuminate/support": "^9|^10|^11|^12",Ð "illuminate/translation": "^9|^10|^11|^12",Ð "symfony/finder": "^6|^7"Ð },Ð "require-dev": {Ð "orchestra/testbench": "^7|^8|^9|^10"Ð },Ð "suggest": {Ð "tanmuhittin/laravel-google-translate": "If you want to translate using Google API"Ð },Ð "autoload": {Ð "psr-4": {Ð "Barryvdh\\TranslationManager\\": "src/"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Barryvdh\\TranslationManager\\Tests\\": "tests/"Ð }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "0.6-dev"Ð },Ð "laravel": {Ð "providers": [Ð "Barryvdh\\TranslationManager\\ManagerServiceProvider"Ð]Ð }Ð },Ð "scripts": {Ð "test": "phpunit"Ð },Ð "minimum-stability": "dev",Ð "prefer-stable": trueÐ}Ð

vendor\brick\math\composer.json

{Ð   "name": "brick/math",Ð   "description": "Arbitrary-precision arithmetic library",Ð   "type": "library",Ð   "keywords": [Ð   "Brick",Ð   "Math",Ð   "Arbitrary-precision",Ð   "Arithmetic",Ð   "BigInteger",Ð   "BigDecimal",Ð   "BigRational",Ð   "Bignum"Ð   ],Ð   "license": "MIT",Ð   "require": {Ð   "php": "^8.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.0",Ð   "php-coveralls/php-coveralls": "^2.2",Ð   "vimeo/psalm": "5.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Brick\\Math\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Brick\\Math\\Tests\\": "tests/"Ð   }Ð   }ÐÐ}

vendor\carbonphp\carbon-doctrine-types\composer.json

{Ð   "name": "carbonphp/carbon-doctrine-types",Ð   "description": "Types to use Carbon in Doctrine",Ð   "type": "library",Ð   "keywords": [Ð   "date",Ð   "time",Ð   "DateTime",Ð   "Carbon",Ð   "Doctrine"Ð   ],Ð   "require": {Ð   "php": "^7.4 || ^8.0"Ð   },Ð   "require-dev": {Ð   "doctrine/dbal": "^3.7.0",Ð   "nesbot/carbon": "^2.71.0 || ^3.0.0",Ð   "phpunit/phpunit": "^10.3"Ð   },Ð   "conflict": {Ð   "doctrine/dbal": "<3.7.0 || >=4.0.0"Ð   },Ð   "license": "MIT",Ð   "autoload": {Ð   "psr-4": {Ð   "Carbon\\Doctrine\\": "src/Carbon/Doctrine/"Ð   }Ð   },Ð   "authors": [Ð   {Ð   "name": "KyleKatarn",Ð   "email": "kylekatarnls@gmail.com"Ð   }Ð   ],Ð   "minimum-stability": "dev"Ð}Ð

vendor\composer\installed.json


```
{Ð   "packages": [Ð       {Ð           "name": "barryvdh/laravel-dompdf",Ð
            "version": "v1.0.2",Ð           "version_normalized": "1.0.2.0",Ð
            "source": {Ð               "type": "git",Ð               "url":
"https://github.com/barryvdh/laravel-dompdf.git",Ð               "reference":
"de83130d029289e1b59f28b41c314ce1d157b4a0"Ð           },Ð           "dist": {Ð
                "type": "zip",Ð               "url": "https://api.github.com/
repos/barryvdh/laravel-dompdf/zipball/
de83130d029289e1b59f28b41c314ce1d157b4a0",Ð               "reference":
"de83130d029289e1b59f28b41c314ce1d157b4a0",Ð               "shasum": ""Ð
            },Ð           "require": {Ð               "dompdf/dompdf":
"^1.2.1",Ð               "illuminate/support": "^6|^7|^8|^9",Ð
"php": "^7.2 || ^8.0"Ð           },Ð           "require-dev": {Ð
                "nunomaduro/larastan": "^1|^2",Ð               "orchestra/
testbench": "^4|^5|^6|^7",Ð               "phpro/grumphp": "^1",Ð
                "squizlabs/php_codesniffer": "^3.5"Ð           },Ð
"time": "2022-05-19T15:08:38+00:00",Ð           "type": "library",Ð
"extra": {Ð               "laravel": {Ð                   "aliases": {Ð
                        "PDF": "Barryvdh\\DomPDF\\Facade\\Pdf"Ð
                    },Ð                   "providers": [Ð
                        "Barryvdh\\DomPDF\\ServiceProvider"Ð
                    ]Ð               },Ð               "branch-alias": {Ð
                    "dev-master": "1.0-dev"Ð               }Ð           },Ð
            "installation-source": "dist",Ð           "autoload": {Ð
                "psr-4": {Ð                   "Barryvdh\\DomPDF\\": "src"Ð
                }Ð           },Ð           "notification-url": "https://
packagist.org/downloads/",Ð           "license": [Ð               "MIT"Ð
            ],Ð           "authors": [Ð               {Ð
"name": "Barry vd. Heuvel",Ð                   "email": "barryvdh@gmail.com"Ð
                }Ð           ],Ð           "description": "A DOMPDF Wrapper
for Laravel",Ð           "keywords": [Ð               "dompdf",Ð
                "laravel",Ð               "pdf"Ð           ],Ð
"support": {Ð               "issues": "https://github.com/barryvdh/laravel-
dompdf/issues",Ð               "source": "https://github.com/barryvdh/laravel-
dompdf/tree/v1.0.2"Ð           },Ð           "funding": [Ð               {Ð
                    "url": "https://fruitcake.nl",Ð                   "type":
"custom"Ð               },Ð               {Ð                   "url":
"https://github.com/barryvdh",Ð                   "type": "github"Ð
                }Ð           ],Ð           "install-path": "../barryvdh/
laravel-dompdf"Ð       },Ð       {Ð           "name": "barryvdh/laravel-
translation-manager",Ð           "version": "dev-master",Ð
"version_normalized": "dev-master",Ð           "source": {Ð
"type": "git",Ð               "url": "https://github.com/barryvdh/laravel-
translation-manager.git",Ð               "reference":
"5be9386b0e11887ad6b7d573d6215e40b9ffce88"Ð           },Ð           "dist": {Ð
                "type": "zip",Ð               "url": "https://api.github.com/
repos/barryvdh/laravel-translation-manager/
zipball/5be9386b0e11887ad6b7d573d6215e40b9ffce88",Ð
"reference": "5be9386b0e11887ad6b7d573d6215e40b9ffce88",Ð
"shasum": ""Ð           },Ð           "require": {Ð               "illuminate/
support": "^9|^10|^11|^12",Ð               "illuminate/translation": "^9|^10|
^11|^12",Ð               "php": "^8.1",Ð               "symfony/finder": "^6|
^7"Ð           },Ð           "require-dev": {Ð               "orchestra/
testbench": "^7|^8|^9|^10"Ð           },Ð           "suggest": {Ð
                "tanmuhittin/laravel-google-translate": "If you want to
translate using Google API"Ð           },Ð           "time":
"2025-02-25T10:48:54+00:00",Ð           "default-branch": true,Ð
"type": "library",Ð           "extra": {Ð               "laravel": {Ð
                    "providers": [Ð                   "Barryvdh\
\TranslationManager\\ManagerServiceProvider"Ð
```

]Ð
},Ð "branch-alias": {Ð "dev-master": "0.6-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Barryvdh\\TranslationManager\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Barry vd. Heuvel",Ð "email": "barryvdh@gmail.com"Ð }Ð],Ð "description": "Manage Laravel Translations",Ð "keywords": [Ð "laravel",Ð "translations",Ð "translator"Ð],Ð "support": {Ð "issues": "https://github.com/barryvdh/laravel-translation-manager/issues",Ð "source": "https://github.com/barryvdh/laravel-translation-manager/tree/v0.6.7"Ð },Ð "install-path": "../barryvdh/laravel-translation-manager"Ð },Ð {Ð "name": "brick/math",Ð "version": "0.11.0",Ð "version_normalized": "0.11.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/brick/math.git",Ð "reference": "0ad82ce168c82ba30d1c01ec86116ab52f589478"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/brick/math/zipball/0ad82ce168c82ba30d1c01ec86116ab52f589478",Ð "reference": "0ad82ce168c82ba30d1c01ec86116ab52f589478",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^8.0"Ð },Ð "require-dev": {Ð "php-coveralls/php-coveralls": "^2.2",Ð "phpunit/phpunit": "^9.0",Ð "vimeo/psalm": "5.0.0"Ð },Ð "time": "2023-01-15T23:15:59+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Brick\\Math\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "description": "Arbitrary-precision arithmetic library",Ð "keywords": [Ð "Arbitrary-precision",Ð "BigInteger",Ð "BigRational",Ð "arithmetic",Ð "bigdecimal",Ð "bignum",Ð "brick",Ð "math"Ð],Ð "support": {Ð "issues": "https://github.com/brick/math/issues",Ð "source": "https://github.com/brick/math/tree/0.11.0"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/BenMorel",Ð "type": "github"Ð }Ð],Ð "install-path": "../brick/math"Ð },Ð {Ð "name": "carbonphp/carbon-doctrine-types",Ð "version": "2.1.0",Ð "version_normalized": "2.1.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/CarbonPHP/carbon-doctrine-types.git",Ð "reference": "99f76ffa36cce3b70a4a6abce41dba15ca2e84cb"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/CarbonPHP/carbon-doctrine-types/zipball/99f76ffa36cce3b70a4a6abce41dba15ca2e84cb",Ð "reference": "99f76ffa36cce3b70a4a6abce41dba15ca2e84cb",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^7.4 || ^8.0"Ð },Ð "conflict": {Ð "doctrine/dbal": "<3.7.0 || >=4.0.0"Ð },Ð "require-dev": {Ð "doctrine/dbal": "^3.7.0",Ð "nesbot/carbon": "^2.71.0 || ^3.0.0",Ð "phpunit/phpunit": "^10.3"Ð },Ð "time": "2023-12-11T17:09:12+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð

"Carbon\\Doctrine\\": "src/Carbon/Doctrine/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "KyleKatarn",Ð "email": "kylekatarnls@gmail.com"Ð }Ð],Ð "description": "Types to use Carbon in Doctrine",Ð "keywords": [Ð "carbon",Ð "date",Ð "datetime",Ð "doctrine",Ð "time"Ð],Ð "support": {Ð "issues": "https://github.com/CarbonPHP/carbon-doctrine-types/issues",Ð "source": "https://github.com/CarbonPHP/carbon-doctrine-types/tree/2.1.0"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/kylekatarnls",Ð "type": "github"Ð },Ð {Ð "url": "https://opencollective.com/Carbon",Ð "type": "open_collective"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/nesbot/carbon",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../carbonphp/carbon-doctrine-types"Ð },Ð {Ð "name": "dflydev/dot-access-data",Ð "version": "v3.0.3",Ð "version_normalized": "3.0.3.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/dflydev/dflydev-dot-access-data.git",Ð "reference": "a23a2bf4f31d3518f3ecb38660c95715dfead60f"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/dflydev/dflydev-dot-access-data/zipball/a23a2bf4f31d3518f3ecb38660c95715dfead60f",Ð "reference": "a23a2bf4f31d3518f3ecb38660c95715dfead60f",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^7.1 || ^8.0"Ð },Ð "require-dev": {Ð "phpstan/phpstan": "^0.12.42",Ð "phpunit/phpunit": "^7.5 || ^8.5 || ^9.3",Ð "scrutinizer/ocular": "1.6.0",Ð "squizlabs/php_codesniffer": "^3.5",Ð "vimeo/psalm": "^4.0.0"Ð },Ð "time": "2024-07-08T12:26:09+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "3.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Dflydev\\DotAccessData\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Dragonfly Development Inc.",Ð "email": "info@dflydev.com",Ð "homepage": "http://dflydev.com"Ð },Ð {Ð "name": "Beau Simensen",Ð "email": "beau@dflydev.com",Ð "homepage": "http://beausimensen.com"Ð },Ð {Ð "name": "Carlos Frutos",Ð "email": "carlos@kiwing.it",Ð "homepage": "https://github.com/cfrutos"Ð },Ð {Ð "name": "Colin O'Dell",Ð "email": "colinodell@gmail.com",Ð "homepage": "https://www.colinodell.com"Ð }Ð],Ð "description": "Given a deep data structure, access data by dot notation.",Ð "homepage": "https://github.com/dflydev/dflydev-dot-access-data",Ð "keywords": [Ð "access",Ð "data",Ð "dot",Ð "notation"Ð],Ð "support": {Ð "issues": "https://github.com/dflydev/dflydev-dot-access-data/issues",Ð "source": "https://github.com/dflydev/dflydev-dot-access-data/tree/v3.0.3"Ð },Ð "install-path": "../dflydev/dot-access-data"Ð

},Ð {Ð
"name": "doctrine/cache",Ð "version": "2.2.0",Ð
"version_normalized": "2.2.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/doctrine/cache.git",Ð "reference": "1ca8f21980e770095a31456042471a57bc4c68fb"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/doctrine/cache/zipball/1ca8f21980e770095a31456042471a57bc4c68fb",Ð
"reference": "1ca8f21980e770095a31456042471a57bc4c68fb",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "~7.1 || ^8.0"Ð },Ð "conflict": {Ð
"doctrine/common": ">2.2,<2.4"Ð },Ð "require-dev": {Ð "cache/integration-tests": "dev-master",Ð
"doctrine/coding-standard": "^9",Ð "phpunit/phpunit": "^7.5 || ^8.5 || ^9.5",Ð "psr/cache": "^1.0 || ^2.0 || ^3.0",Ð "symfony/cache": "^4.4 || ^5.4 || ^6",Ð
"symfony/var-exporter": "^4.4 || ^5.4 || ^6"Ð },Ð
"time": "2022-05-20T20:07:39+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Doctrine\\Common\\Cache\\": "lib/Doctrine/Common/Cache"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Guilherme Blanco",Ð "email": "guilhermeblanco@gmail.com"Ð },Ð {Ð
"name": "Roman Borschel",Ð "email": "roman@code-factory.org"Ð },Ð {Ð
"name": "Benjamin Eberlei",Ð "email": "kontakt@beberlei.de"Ð },Ð {Ð "name": "Jonathan Wage",Ð "email": "jonwage@gmail.com"Ð
},Ð {Ð "name": "Johannes Schmitt",Ð "email": "schmittjoh@gmail.com"Ð }Ð
],Ð "description": "PHP Doctrine Cache library is a popular cache implementation that supports many different drivers such as redis, memcache, apc, mongodb and others.",Ð "homepage": "https://www.doctrine-project.org/projects/cache.html",Ð "keywords": [Ð
"abstraction",Ð "apcu",Ð "cache",Ð
"caching",Ð "couchdb",Ð "memcached",Ð "php",Ð "redis",Ð "xcache"Ð],Ð "support": {Ð "issues": "https://github.com/doctrine/cache/issues",Ð "source": "https://github.com/doctrine/cache/tree/2.2.0"Ð },Ð "funding": [Ð
{Ð "url": "https://www.doctrine-project.org/sponsorship.html",Ð "type": "custom"Ð },Ð
{Ð "url": "https://www.patreon.com/phpdoctrine",Ð "type": "patreon"Ð },Ð
{Ð "url": "https://tidelift.com/funding/github/packagist/doctrine%2Fcache",Ð "type": "tidelift"Ð
}Ð],Ð "install-path": "../doctrine/cache"Ð
},Ð {Ð "name": "doctrine/dbal",Ð "version": "3.9.4",Ð "version_normalized": "3.9.4.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/doctrine/dbal.git",Ð "reference": "ec16c82f20be1a7224e65ac67144a29199f87959"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/doctrine/dbal/zipball/ec16c82f20be1a7224e65ac67144a29199f87959",Ð
"reference": "ec16c82f20be1a7224e65ac67144a29199f87959",Ð
"shasum": ""Ð },Ð "require": {Ð
"composer-runtime-api": "^2",Ð "doctrine/cache": "^1.11|^2.0",Ð

"doctrine/deprecations": "^0.5.3|^1",Ð
"doctrine/event-manager": "^1|^2",Ð "php": "^7.4 || ^8.0",Ð "psr/cache": "^1|^2|^3",Ð "psr/log": "^1|^2|^3"Ð },Ð "require-dev": {Ð
"doctrine/coding-standard": "12.0.0",Ð "fig/log-test": "^1",Ð
"jetbrains/phpstorm-stubs": "2023.1",Ð "phpstan/phpstan": "2.1.1",Ð "phpstan/phpstan-strict-rules": "^2",Ð
"phpunit/phpunit": "9.6.22",Ð "slevomat/coding-standard": "8.13.1",Ð "squizlabs/php_codesniffer": "3.10.2",Ð
"symfony/cache": "^5.4|^6.0|^7.0",Ð "symfony/console": "^4.4|^5.4|^6.0|^7.0"Ð },Ð "suggest": {Ð
"symfony/console": "For helpful console commands such as SQL execution and import of files."Ð },Ð "time": "2025-01-16T08:28:55+00:00",Ð "bin": [Ð "bin/doctrine-dbal"Ð],Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð
"Doctrine\\DBAL\\": "src"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Guilherme Blanco",Ð
"email": "guilhermeblanco@gmail.com"Ð },Ð
{Ð "name": "Roman Borschel",Ð
"email": "roman@code-factory.org"Ð },Ð
{Ð "name": "Benjamin Eberlei",Ð
"email": "kontakt@beberlei.de"Ð },Ð
{Ð "name": "Jonathan Wage",Ð
"email": "jonwage@gmail.com"Ð }Ð
],Ð "description": "Powerful PHP database abstraction layer (DBAL) with many features for database schema introspection and management.",Ð "homepage": "https://www.doctrine-project.org/projects/dbal.html",Ð "keywords": [Ð "abstraction",Ð
"database",Ð "db2",Ð "dbal",Ð
"mariadb",Ð "mssql",Ð "mysql",Ð
"oci8",Ð "oracle",Ð "pdo",Ð
"pgsql",Ð "postgresql",Ð
"queryobject",Ð "sasql",Ð "sql",Ð
"sqlite",Ð "sqlserver",Ð "sqlsrv"Ð],Ð
"support": {Ð "issues": "https://github.com/doctrine/dbal/issues",Ð "source": "https://github.com/doctrine/dbal/tree/3.9.4"Ð },Ð "funding": [Ð {Ð
"url": "https://www.doctrine-project.org/sponsorship.html",Ð "type": "custom"Ð },Ð
{Ð "url": "https://www.patreon.com/phpdoctrine",Ð "type": "patreon"Ð },Ð
{Ð "url": "https://tidelift.com/funding/github/packagist/doctrine%2Fdbal",Ð "type": "tidelift"Ð
}Ð],Ð "install-path": "../doctrine/dbal"Ð
},Ð {Ð "name": "doctrine/deprecations",Ð
"version": "1.1.5",Ð "version_normalized": "1.1.5.0",Ð
"source": {Ð "type": "git",Ð "url": "https://github.com/doctrine/deprecations.git",Ð "reference": "459c2f5dd3d6a4633d3b5f46ee2b1c40f57d3f38"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/doctrine/deprecations/zipball/459c2f5dd3d6a4633d3b5f46ee2b1c40f57d3f38",Ð
"reference": "459c2f5dd3d6a4633d3b5f46ee2b1c40f57d3f38",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.1 || ^8.0"Ð },Ð "conflict": {Ð
"phpunit/phpunit": "<=7.5 || >=13"Ð },Ð
"require-dev": {Ð "doctrine/coding-standard": "^9 || ^12 || ^13",Ð

"phpstan/phpstan": "1.4.10 || 2.1.11",Ð
"phpstan/phpstan-phpunit": "^1.0 || ^2",Ð "phpunit/phpunit":
"^7.5 || ^8.5 || ^9.6 || ^10.5 || ^11.5 || ^12",Ð "psr/log":
"^1 || ^2 || ^3"Ð },Ð "suggest": {Ð "psr/
log": "Allows logging deprecations via PSR-3 logger implementation"Ð
},Ð "time": "2025-04-07T20:06:18+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Doctrine\
\Deprecations\\": "src"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "description": "A small layer
on top of trigger_error(E_USER_DEPRECATED) or PSR-3 logging with options to
disable all deprecations or selectively for packages.",Ð
"homepage": "https://www.doctrine-project.org/",Ð "support": {Ð
"issues": "https://github.com/doctrine/deprecations/issues",Ð
"source": "https://github.com/doctrine/deprecations/
tree/1.1.5"Ð },Ð "install-path": "../doctrine/
deprecations"Ð },Ð {Ð "name": "doctrine/event-manager",Ð
"version": "2.0.1",Ð "version_normalized": "2.0.1.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/doctrine/event-manager.git",Ð "reference":
"b680156fa328f1dfd874fd48c7026c41570b9c6e"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/doctrine/event-manager/zipball/
b680156fa328f1dfd874fd48c7026c41570b9c6e",Ð "reference":
"b680156fa328f1dfd874fd48c7026c41570b9c6e",Ð "shasum": ""Ð
},Ð "require": {Ð "php": "^8.1"Ð
},Ð "conflict": {Ð "doctrine/common":
"<2.9"Ð },Ð "require-dev": {Ð "doctrine/
coding-standard": "^12",Ð "phpstan/phpstan": "^1.8.8",Ð
"phpunit/phpunit": "^10.5",Ð "vimeo/psalm":
"^5.24"Ð },Ð "time": "2024-05-22T20:47:39+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"Doctrine\\Common\\": "src"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Guilherme Blanco",Ð "email":
"guilhermeblanco@gmail.com"Ð },Ð {Ð
"name": "Roman Borschel",Ð "email":
"roman@code-factory.org"Ð },Ð {Ð
"name": "Benjamin Eberlei",Ð "email":
"kontakt@beberlei.de"Ð },Ð {Ð
"name": "Jonathan Wage",Ð "email": "jonwage@gmail.com"Ð
},Ð {Ð "name": "Johannes
Schmitt",Ð "email": "schmittjoh@gmail.com"Ð },Ð
{Ð "name": "Marco Pivetta",Ð
"email": "ocramius@gmail.com"Ð }Ð
],Ð "description": "The Doctrine Event Manager is a
simple PHP event system that was built to be used with the various Doctrine
projects.",Ð "homepage": "https://www.doctrine-project.org/projects/
event-manager.html",Ð "keywords": [Ð "event",Ð
"event dispatcher",Ð "event manager",Ð
"event system",Ð "events"Ð],Ð
"support": {Ð "issues": "https://github.com/
doctrine/event-manager/issues",Ð "source": "https://github.com/
doctrine/event-manager/tree/2.0.1"Ð },Ð "funding": [Ð
{Ð "url": "https://www.doctrine-project.org/
sponsorship.html",Ð "type": "custom"Ð },Ð
{Ð

"url": "https://www.patreon.com/phpdoctrine",Ð "type": "patreon"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/doctrine%2Fevent-manager",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../doctrine/event-manager"Ð },Ð {Ð "name": "doctrine/inflector",Ð "version": "2.0.10",Ð "version_normalized": "2.0.10.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/doctrine/inflector.git",Ð "reference": "5817d0659c5b50c9b950feb9af7b9668e2c436bc"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/doctrine/inflector/zipball/5817d0659c5b50c9b950feb9af7b9668e2c436bc",Ð "reference": "5817d0659c5b50c9b950feb9af7b9668e2c436bc",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^7.2 || ^8.0"Ð },Ð "require-dev": {Ð "doctrine/coding-standard": "^11.0",Ð "phpstan/phpstan": "^1.8",Ð "phpstan/phpstan-phpunit": "^1.1",Ð "phpstan/phpstan-strict-rules": "^1.3",Ð "phpunit/phpunit": "^8.5 || ^9.5",Ð "vimeo/psalm": "^4.25 || ^5.4"Ð },Ð "time": "2024-02-18T20:23:39+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Doctrine\\Inflector\\": "lib/Doctrine/Inflector"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Guilherme Blanco",Ð "email": "guilhermeblanco@gmail.com"Ð },Ð {Ð "name": "Roman Borschel",Ð "email": "roman@code-factory.org"Ð },Ð {Ð "name": "Benjamin Eberlei",Ð "email": "kontakt@beberlei.de"Ð },Ð {Ð "name": "Jonathan Wage",Ð "email": "jonwage@gmail.com"Ð },Ð {Ð "name": "Johannes Schmitt",Ð "email": "schmittjoh@gmail.com"Ð }Ð],Ð "description": "PHP Doctrine Inflector is a small library that can perform string manipulations with regard to upper/lowercase and singular/plural forms of words.",Ð "homepage": "https://www.doctrine-project.org/projects/inflector.html",Ð "keywords": [Ð "inflection",Ð "inflector",Ð "lowercase",Ð "manipulation",Ð "php",Ð "plural",Ð "singular",Ð "strings",Ð "uppercase",Ð "words"Ð],Ð "support": {Ð "issues": "https://github.com/doctrine/inflector/issues",Ð "source": "https://github.com/doctrine/inflector/tree/2.0.10"Ð },Ð "funding": [Ð {Ð "url": "https://www.doctrine-project.org/sponsorship.html",Ð "type": "custom"Ð },Ð {Ð "url": "https://www.patreon.com/phpdoctrine",Ð "type": "patreon"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/doctrine%2Finflector",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../doctrine/inflector"Ð },Ð {Ð "name": "doctrine/instantiator",Ð "version": "2.0.0",Ð "version_normalized": "2.0.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/doctrine/instantiator.git",Ð "reference": "c6222283fa3f4ac679f8b9ced9a4e23f163e80d0"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/doctrine/instantiator/zipball/c6222283fa3f4ac679f8b9ced9a4e23f163e80d0",Ð

"reference": "c6222283fa3f4ac679f8b9ced9a4e23f163e80d0",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^8.1"Ð },Ð "require-dev": {Ð
"doctrine/coding-standard": "^11",Ð "ext-pdo":
"*",Ð "ext-phar": "*",Ð "phpbench/phpbench":
"^1.2",Ð "phpstan/phpstan": "^1.9.4",Ð "phpstan/
phpstan-phpunit": "^1.3",Ð "phpunit/phpunit": "^9.5.27",Ð
"vimeo/psalm": "^5.4"Ð },Ð "time":
"2022-12-30T00:23:10+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Doctrine\\Instantiator\\": "src/Doctrine/
Instantiator/"Ð }Ð },Ð "notification-url":
"https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð],Ð "authors": [Ð {Ð
"name": "Marco Pivetta",Ð "email":
"ocramius@gmail.com",Ð "homepage": "https://
ocramius.github.io/"Ð }Ð],Ð "description":
"A small, lightweight utility to instantiate objects in PHP without invoking
their constructors",Ð "homepage": "https://www.doctrine-project.org/
projects/instantiator.html",Ð "keywords": [Ð
"constructor",Ð "instantiate"Ð],Ð
"support": {Ð "issues": "https://github.com/doctrine/
instantiator/issues",Ð "source": "https://github.com/doctrine/
instantiator/tree/2.0.0"Ð },Ð "funding": [Ð
{Ð "url": "https://www.doctrine-project.org/
sponsorship.html",Ð "type": "custom"Ð },Ð
{Ð "url": "https://www.patreon.com/
phpdoctrine",Ð "type": "patreon"Ð },Ð
{Ð "url": "https://tidelift.com/funding/
github/packagist/doctrine%2Finstantiator",Ð "type":
"tidelift"Ð }Ð],Ð "install-path": "../
doctrine/instantiator"Ð },Ð {Ð "name": "doctrine/lexer",Ð
"version": "3.0.1",Ð "version_normalized": "3.0.1.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/doctrine/lexer.git",Ð "reference":
"31ad66abc0fc9e1a1f2d9bc6a42668d2fbbcd6dd"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/doctrine/lexer/zipball/31ad66abc0fc9e1a1f2d9bc6a42668d2fbbcd6dd",Ð
"reference": "31ad66abc0fc9e1a1f2d9bc6a42668d2fbbcd6dd",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^8.1"Ð },Ð "require-dev": {Ð
"doctrine/coding-standard": "^12",Ð "phpstan/
phpstan": "^1.10",Ð "phpunit/phpunit": "^10.5",Ð
"psalm/plugin-phpunit": "^0.18.3",Ð "vimeo/psalm": "^5.21"Ð
},Ð "time": "2024-02-05T11:56:58+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Doctrine\\Common\
\Lexer\\": "src"Ð }Ð },Ð "notification-
url": "https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð],Ð "authors": [Ð {Ð
"name": "Guilherme Blanco",Ð "email":
"guilhermeblanco@gmail.com"Ð },Ð {Ð
"name": "Roman Borschel",Ð "email":
"roman@code-factory.org"Ð },Ð {Ð
"name": "Johannes Schmitt",Ð "email":
"schmittjoh@gmail.com"Ð }Ð],Ð
"description": "PHP Doctrine Lexer parser library that can be used in Top-
Down, Recursive Descent Parsers.",Ð "homepage": "https://
www.doctrine-project.org/projects/lexer.html",Ð

"keywords": [Ð
"annotations",Ð "docblock",Ð
"lexer",Ð "parser",Ð "php"Ð],Ð
"support": {Ð "issues": "https://github.com/
doctrine/lexer/issues",Ð "source": "https://github.com/doctrine/
lexer/tree/3.0.1"Ð },Ð "funding": [Ð {Ð
"url": "https://www.doctrine-project.org/
sponsorship.html",Ð "type": "custom"Ð },Ð
{Ð "url": "https://www.patreon.com/
phpdoctrine",Ð "type": "patreon"Ð },Ð
{Ð "url": "https://tidelift.com/funding/
github/packagist/doctrine%2Flexer",Ð "type": "tidelift"Ð
}Ð],Ð "install-path": "../doctrine/lexer"Ð
},Ð {Ð "name": "dompdf/dompdf",Ð "version":
"v1.2.2",Ð "version_normalized": "1.2.2.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
dompdf/dompdf.git",Ð "reference":
"5031045d9640b38cfc14aac9667470df09c9e090"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/dompdf/dompdf/zipball/5031045d9640b38cfc14aac9667470df09c9e090",Ð
"reference": "5031045d9640b38cfc14aac9667470df09c9e090",Ð
"shasum": ""Ð },Ð "require": {Ð
"ext-dom": "*",Ð "ext-mbstring": "*",Ð
"phenx/php-font-lib": "^0.5.4",Ð "phenx/php-svg-
lib": "^0.3.3 || ^0.4.0",Ð "php": "^7.1 || ^8.0"Ð },Ð
"require-dev": {Ð "ext-json": "*",Ð
"ext-zip": "*",Ð "mockery/mockery": "^1.3",Ð
"phpunit/phpunit": "^7.5 || ^8 || ^9",Ð "squizlabs/
php_codesniffer": "^3.5"Ð },Ð "suggest": {Ð
"ext-gd": "Needed to process images",Ð "ext-gmagick": "Improves
image processing performance",Ð "ext-imagick": "Improves image
processing performance",Ð "ext-zlib": "Needed for pdf stream
compression"Ð },Ð "time": "2022-04-27T13:50:54+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"Dompdf\\": "src/"Ð },Ð "classmap": [Ð
"lib/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "LGPL-2.1"Ð],Ð "authors": [Ð
{Ð "name": "Fabien Ménager",Ð
"email": "fabien.menager@gmail.com"Ð },Ð
{Ð "name": "Brian Sweeney",Ð
"email": "eclecticgeek@gmail.com"Ð },Ð
{Ð "name": "Gabriel Bull",Ð
"email": "me@gabrielbull.com"Ð }Ð
],Ð "description": "DOMPDF is a CSS 2.1 compliant HTML
to PDF converter",Ð "homepage": "https://github.com/dompdf/dompdf",Ð
"support": {Ð "issues": "https://github.com/dompdf/
dompdf/issues",Ð "source": "https://github.com/dompdf/dompdf/
tree/v1.2.2"Ð },Ð "install-path": "../dompdf/dompdf"Ð
},Ð {Ð "name": "dragonmantank/cron-expression",Ð
"version": "v3.4.0",Ð "version_normalized": "3.4.0.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/dragonmantank/cron-expression.git",Ð
"reference": "8c784d071debd117328803d86b2097615b457500"Ð },Ð
"dist": {Ð "type": "zip",Ð "url":
"https://api.github.com/repos/dragonmantank/cron-expression/
zipball/8c784d071debd117328803d86b2097615b457500",Ð
"reference": "8c784d071debd117328803d86b2097615b457500",Ð
"shasum": ""Ð

},Ð "require": {Ð "php": "^7.2|^8.0",Ð "webmozart/assert": "^1.0"Ð },Ð "replace": {Ð "mtdowling/cron-expression": "^1.0"Ð },Ð "require-dev": {Ð "phpstan/extension-installer": "^1.0",Ð "phpstan/phpstan": "^1.0",Ð "phpunit/phpunit": "^7.0|^8.0|^9.0"Ð },Ð "time": "2024-10-09T13:47:03+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "3.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Cron\\": "src/Cron/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Chris Tankersley",Ð "email": "chris@ctankersley.com",Ð "homepage": "https://github.com/dragonmantank"Ð }Ð],Ð "description": "CRON for PHP: Calculate the next or previous run date and determine if a CRON expression is due",Ð "keywords": [Ð "cron",Ð "schedule"Ð],Ð "support": {Ð "issues": "https://github.com/dragonmantank/cron-expression/issues",Ð "source": "https://github.com/dragonmantank/cron-expression/tree/v3.4.0"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/dragonmantank",Ð "type": "github"Ð }Ð],Ð "install-path": "../dragonmantank/cron-expression"Ð },Ð {Ð "name": "egulias/email-validator",Ð "version": "4.0.4",Ð "version_normalized": "4.0.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/egulias/EmailValidator.git",Ð "reference": "d42c8731f0624ad6bdc8d3e5e9a4524f68801cfa"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/egulias/EmailValidator/zipball/d42c8731f0624ad6bdc8d3e5e9a4524f68801cfa",Ð "reference": "d42c8731f0624ad6bdc8d3e5e9a4524f68801cfa",Ð "shasum": ""Ð },Ð "require": {Ð "doctrine/lexer": "^2.0 || ^3.0",Ð "php": ">=8.1",Ð "symfony/polyfill-intl-idn": "^1.26"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^10.2",Ð "vimeo/psalm": "^5.12"Ð },Ð "suggest": {Ð "ext-intl": "PHP Internationalization Libraries are required to use the SpoofChecking validation"Ð },Ð "time": "2025-03-06T22:45:56+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "4.0.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Egulias\\EmailValidator\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Eduardo Gulias Davis"Ð }Ð],Ð "description": "A library for validating emails against several RFCs",Ð "homepage": "https://github.com/egulias/EmailValidator",Ð "keywords": [Ð "email",Ð "emailvalidation",Ð "emailvalidator",Ð "validation",Ð "validator"Ð],Ð "support": {Ð "issues": "https://github.com/egulias/EmailValidator/issues",Ð "source": "https://github.com/egulias/EmailValidator/tree/4.0.4"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/egulias",Ð "type": "github"Ð }Ð],Ð "install-path": "../egulias/email-validator"Ð

},Ð {Ð
"name": "fakerphp/faker",Ð "version": "v1.24.1",Ð
"version_normalized": "1.24.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/FakerPHP/Faker.git",Ð "reference": "e0ee18eb1e6dc3cda3ce9fd97e5a0689a88a64b5"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/FakerPHP/Faker/zipball/e0ee18eb1e6dc3cda3ce9fd97e5a0689a88a64b5",Ð
"reference": "e0ee18eb1e6dc3cda3ce9fd97e5a0689a88a64b5",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.4 || ^8.0",Ð "psr/container": "^1.0 || ^2.0",Ð "symfony/deprecation-contracts": "^2.2 || ^3.0"Ð
},Ð "conflict": {Ð "fzaninotto/faker": "*"Ð
},Ð "require-dev": {Ð "bamarni/composer-bin-plugin": "^1.4.1",Ð "doctrine/persistence": "^1.3 || ^2.0",Ð
"ext-intl": "*",Ð "phpunit/phpunit": "^9.5.26",Ð
"symfony/phpunit-bridge": "^5.4.16"Ð },Ð
"suggest": {Ð "doctrine/orm": "Required to use Faker\\ORM\\Doctrine",Ð "ext-curl": "Required by Faker\\Provider\\Image to download images.",Ð "ext-dom": "Required by Faker\\Provider\\HtmlLorem for generating random HTML.",Ð "ext-iconv": "Required by Faker\\Provider\\ru_RU\\Text::realText() for generating real Russian text.",Ð "ext-mbstring": "Required for multibyte Unicode string functionality."Ð },Ð "time": "2024-11-21T13:46:39+00:00",Ð
"type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Faker\\": "src/Faker/"Ð }Ð
},Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "François Zaninotto"Ð }Ð],Ð "description": "Faker is a PHP library that generates fake data for you.",Ð
"keywords": [Ð "data",Ð "faker",Ð
"fixtures"Ð],Ð "support": {Ð "issues": "https://github.com/FakerPHP/Faker/issues",Ð "source": "https://github.com/FakerPHP/Faker/tree/v1.24.1"Ð },Ð "install-path": "../fakerphp/faker"Ð },Ð {Ð "name": "filp/whoops",Ð "version": "2.18.0",Ð "version_normalized": "2.18.0.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/filp/whoops.git",Ð
"reference": "a7de6c3c6c3c022f5cfc337f8ede6a14460cf77e"Ð },Ð
"dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/filp/whoops/zipball/a7de6c3c6c3c022f5cfc337f8ede6a14460cf77e",Ð "reference": "a7de6c3c6c3c022f5cfc337f8ede6a14460cf77e",Ð "shasum": ""Ð
},Ð "require": {Ð "php": "^7.1 || ^8.0",Ð
"psr/log": "^1.0.1 || ^2.0 || ^3.0"Ð },Ð
"require-dev": {Ð "mockery/mockery": "^1.0",Ð
"phpunit/phpunit": "^7.5.20 || ^8.5.8 || ^9.3.3",Ð "symfony/var-dumper": "^4.0 || ^5.0"Ð },Ð "suggest": {Ð
"symfony/var-dumper": "Pretty print complex values better with var-dumper available",Ð "whoops/soap": "Formats errors as SOAP responses"Ð
},Ð "time": "2025-03-15T12:00:00+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-alias": {Ð
"dev-master": "2.7-dev"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Whoops\\": "src/Whoops/"Ð
}Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð

"authors": [Ð {Ð
"name": "Filipe Dobreira",Ð "homepage": "https://github.com/filp",Ð "role": "Developer"Ð }Ð],Ð
"description": "php error handling for cool kids",Ð
"homepage": "https://filp.github.io/whoops/",Ð "keywords": [Ð
"error",Ð "exception",Ð
"handling",Ð "library",Ð "throwable",Ð
"whoops"Ð],Ð "support": {Ð
"issues": "https://github.com/filp/whoops/issues",Ð "source": "https://github.com/filp/whoops/tree/2.18.0"Ð },Ð
"funding": [Ð {Ð "url": "https://github.com/denis-sokolov",Ð "type": "github"Ð }Ð
],Ð "install-path": "../filp/whoops"Ð },Ð {Ð
"name": "fruitcake/php-cors",Ð "version": "v1.3.0",Ð
"version_normalized": "1.3.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/fruitcake/php-cors.git",Ð "reference": "3d158f36e7875e2f040f37bc0573956240a5a38b"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/fruitcake/php-cors/zipball/3d158f36e7875e2f040f37bc0573956240a5a38b",Ð
"reference": "3d158f36e7875e2f040f37bc0573956240a5a38b",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.4|^8.0",Ð "symfony/http-foundation": "^4.4|^5.4|^6|^7"Ð },Ð "require-dev": {Ð
"phpstan/phpstan": "^1.4",Ð "phpunit/phpunit": "^9",Ð
"squizlabs/php_codesniffer": "^3.5"Ð },Ð
"time": "2023-10-12T05:21:21+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master": "1.2-dev"Ð }Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"Fruitcake\\Cors\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð],Ð "authors": [Ð {Ð
"name": "Fruitcake",Ð "homepage": "https://fruitcake.nl"Ð },Ð {Ð
"name": "Barryvdh",Ð "email": "barryvdh@gmail.com"Ð
}Ð],Ð "description": "Cross-origin resource sharing library for the Symfony HttpFoundation",Ð
"homepage": "https://github.com/fruitcake/php-cors",Ð "keywords": [Ð
"cors",Ð "laravel",Ð "symfony"Ð
],Ð "support": {Ð "issues": "https://github.com/fruitcake/php-cors/issues",Ð "source": "https://github.com/fruitcake/php-cors/tree/v1.3.0"Ð },Ð
"funding": [Ð {Ð "url": "https://fruitcake.nl",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/barryvdh",Ð
"type": "github"Ð }Ð],Ð
"install-path": "../fruitcake/php-cors"Ð },Ð {Ð
"name": "graham-campbell/result-type",Ð "version": "v1.1.3",Ð
"version_normalized": "1.1.3.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/GrahamCampbell/Result-Type.git",Ð "reference": "3ba905c11371512af9d9bdd27d99b782216b6945"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/GrahamCampbell/Result-Type/zipball/3ba905c11371512af9d9bdd27d99b782216b6945",Ð
"reference": "3ba905c11371512af9d9bdd27d99b782216b6945",Ð
"shasum": ""Ð },Ð "require": {Ð "php": "^7.2.5 || ^8.0",Ð "phpoption/phpoption": "^1.9.3"Ð },Ð
"require-dev": {Ð

"phpunit/phpunit": "^8.5.39 || ^9.6.20 || ^10.5.28"Ð },Ð "time": "2024-07-20T21:45:45+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "GrahamCampbell\\ResultType\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Graham Campbell",Ð "email": "hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/GrahamCampbell"Ð }Ð],Ð "description": "An Implementation Of The Result Type",Ð "keywords": [Ð "Graham Campbell",Ð "GrahamCampbell",Ð "Result Type",Ð "Result-Type",Ð "result"Ð],Ð "support": {Ð "issues": "https://github.com/GrahamCampbell/Result-Type/issues",Ð "source": "https://github.com/GrahamCampbell/Result-Type/tree/v1.1.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/GrahamCampbell",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/graham-campbell/result-type",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../graham-campbell/result-type"Ð },Ð {Ð "name": "guzzlehttp/guzzle",Ð "version": "7.9.3",Ð "version_normalized": "7.9.3.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/guzzle/guzzle.git",Ð "reference": "7b2f29fe81dc4da0ca0ea7d42107a0845946ea77"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/guzzle/guzzle/zipball/7b2f29fe81dc4da0ca0ea7d42107a0845946ea77",Ð "reference": "7b2f29fe81dc4da0ca0ea7d42107a0845946ea77",Ð "shasum": ""Ð },Ð "require": {Ð "ext-json": "*",Ð "guzzlehttp/promises": "^1.5.3 || ^2.0.3",Ð "guzzlehttp/psr7": "^2.7.0",Ð "php": "^7.2.5 || ^8.0",Ð "psr/http-client": "^1.0",Ð "symfony/deprecation-contracts": "^2.2 || ^3.0"Ð },Ð "provide": {Ð "psr/http-client-implementation": "1.0"Ð },Ð "require-dev": {Ð "bamarni/composer-bin-plugin": "^1.8.2",Ð "ext-curl": "*",Ð "guzzle/client-integration-tests": "3.0.2",Ð "php-http/message-factory": "^1.1",Ð "phpunit/phpunit": "^8.5.39 || ^9.6.20",Ð "psr/log": "^1.1 || ^2.0 || ^3.0"Ð },Ð "suggest": {Ð "ext-curl": "Required for CURL handler support",Ð "ext-intl": "Required for Internationalized Domain Name (IDN) support",Ð "psr/log": "Required for using the Log middleware"Ð },Ð "time": "2025-03-27T13:37:11+00:00",Ð "type": "library",Ð "extra": {Ð "bamarni-bin": {Ð "bin-links": true,Ð "forward-command": falseÐ }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "src/functions_include.php"Ð],Ð "psr-4": {Ð "GuzzleHttp\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Graham Campbell",Ð "email": "hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/GrahamCampbell"Ð },Ð {Ð "name": "Michael Dowling",Ð "email": "mtdowling@gmail.com",Ð "homepage": "https://github.com/mtdowling"Ð

},Ð {Ð
"name": "Jeremy Lindblom",Ð "email": "jeremeamia@gmail.com",Ð "homepage": "https://github.com/jeremeamia"Ð },Ð {Ð "name": "George Mponos",Ð "email": "gmponos@gmail.com",Ð "homepage": "https://github.com/gmponos"Ð },Ð {Ð "name": "Tobias Nyholm",Ð "email": "tobias.nyholm@gmail.com",Ð "homepage": "https://github.com/Nyholm"Ð },Ð {Ð "name": "Márk Sági-Kazár",Ð "email": "mark.sagikazar@gmail.com",Ð "homepage": "https://github.com/sagikazarmark"Ð },Ð {Ð "name": "Tobias Schultze",Ð "email": "webmaster@tubo-world.de",Ð "homepage": "https://github.com/Tobion"Ð }Ð],Ð "description": "Guzzle is a PHP HTTP client library",Ð "keywords": [Ð "client",Ð "curl",Ð "framework",Ð "http",Ð "http client",Ð "psr-18",Ð "psr-7",Ð "rest",Ð "web service"Ð],Ð "support": {Ð "issues": "https://github.com/guzzle/guzzle/issues",Ð "source": "https://github.com/guzzle/guzzle/tree/7.9.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/GrahamCampbell",Ð "type": "github"Ð },Ð {Ð "url": "https://github.com/Nyholm",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/guzzlehttp/guzzle",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../guzzlehttp/guzzle"Ð },Ð {Ð "name": "guzzlehttp/promises",Ð "version": "2.2.0",Ð "version_normalized": "2.2.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/guzzle/promises.git",Ð "reference": "7c69f28996b0a6920945dd20b3857e499d9ca96c"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/guzzle/promises/zipball/7c69f28996b0a6920945dd20b3857e499d9ca96c",Ð "reference": "7c69f28996b0a6920945dd20b3857e499d9ca96c",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^7.2.5 || ^8.0"Ð },Ð "require-dev": {Ð "bamarni/composer-bin-plugin": "^1.8.2",Ð "phpunit/phpunit": "^8.5.39 || ^9.6.20"Ð },Ð "time": "2025-03-27T13:27:01+00:00",Ð "type": "library",Ð "extra": {Ð "bamarni-bin": {Ð "bin-links": true,Ð "forward-command": falseÐ }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "GuzzleHttp\\Promise\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Graham Campbell",Ð "email": "hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/GrahamCampbell"Ð },Ð {Ð "name": "Michael Dowling",Ð "email": "mtdowling@gmail.com",Ð "homepage": "https://github.com/mtdowling"Ð },Ð {Ð "name": "Tobias Nyholm",Ð "email": "tobias.nyholm@gmail.com",Ð "homepage": "https://github.com/Nyholm"Ð },Ð {Ð "name": "Tobias Schultze",Ð "email": "webmaster@tubo-world.de",Ð "homepage": "https://github.com/Tobion"Ð

}Ð],Ð
"description": "Guzzle promises library",Ð "keywords": [Ð
"promise"Ð],Ð "support": {Ð
"issues": "https://github.com/guzzle/promises/issues",Ð
"source": "https://github.com/guzzle/promises/tree/2.2.0"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/GrahamCampbell",Ð "type":
"github"Ð },Ð {Ð "url":
"https://github.com/Nyholm",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/guzzlehttp/promises",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../guzzlehttp/promises"Ð },Ð {Ð
"name": "guzzlehttp/psr7",Ð "version": "2.7.1",Ð
"version_normalized": "2.7.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
guzzle/psr7.git",Ð "reference":
"c2270caaabe631b3b44c85f99e5a04bbb8060d16"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/guzzle/psr7/zipball/c2270caaabe631b3b44c85f99e5a04bbb8060d16",Ð
"reference": "c2270caaabe631b3b44c85f99e5a04bbb8060d16",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.2.5 || ^8.0",Ð "psr/http-factory":
"^1.0",Ð "psr/http-message": "^1.1 || ^2.0",Ð
"ralouphie/getallheaders": "^3.0"Ð },Ð "provide": {Ð
"psr/http-factory-implementation": "1.0",Ð "psr/
http-message-implementation": "1.0"Ð },Ð "require-dev": {Ð
"bamarni/composer-bin-plugin": "^1.8.2",Ð "http-
interop/http-factory-tests": "0.9.0",Ð "phpunit/phpunit":
"^8.5.39 || ^9.6.20"Ð },Ð "suggest": {Ð
"laminas/laminas-httphandlerrunner": "Emit PSR-7 responses"Ð },Ð
"time": "2025-03-27T12:30:47+00:00",Ð "type": "library",Ð
"extra": {Ð "bamarni-bin": {Ð
"bin-links": true,Ð "forward-command": falseÐ
}Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"GuzzleHttp\\Psr7\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Graham Campbell",Ð "email":
"hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/
GrahamCampbell"Ð },Ð {Ð "name":
"Michael Dowling",Ð "email": "mtdowling@gmail.com",Ð
"homepage": "https://github.com/mtdowling"Ð
},Ð {Ð "name": "George
Mponos",Ð "email": "gmponos@gmail.com",Ð
"homepage": "https://github.com/gmponos"Ð },Ð {Ð
"name": "Tobias Nyholm",Ð "email":
"tobias.nyholm@gmail.com",Ð "homepage": "https://github.com/
Nyholm"Ð },Ð {Ð "name": "Márk
Sági-Kazár",Ð "email": "mark.sagikazar@gmail.com",Ð
"homepage": "https://github.com/sagikazarmark"Ð
},Ð {Ð "name": "Tobias
Schultze",Ð "email": "webmaster@tubo-world.de",Ð
"homepage": "https://github.com/Tobion"Ð },Ð
{Ð "name": "Márk Sági-Kazár",Ð
"email": "mark.sagikazar@gmail.com",Ð
"homepage": "https://sagikazarmark.hu"Ð }Ð],Ð
"description": "PSR-7 message implementation that also provides
common utility methods",Ð

"keywords": [Ð "http",Ð
"message",Ð "psr-7",Ð "request",Ð
"response",Ð "stream",Ð "uri",Ð
"url"Ð],Ð "support": {Ð
"issues": "https://github.com/guzzle/psr7/issues",Ð "source":
"https://github.com/guzzle/psr7/tree/2.7.1"Ð },Ð
"funding": [Ð {Ð "url": "https://github.com/
GrahamCampbell",Ð "type": "github"Ð },Ð
{Ð "url": "https://github.com/Nyholm",Ð
"type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/
guzzlehttp/psr7",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../guzzlehttp/psr7"Ð },Ð
{Ð "name": "guzzlehttp/uri-template",Ð "version":
"v1.0.4",Ð "version_normalized": "1.0.4.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
guzzle/uri-template.git",Ð "reference":
"30e286560c137526eccd4ce21b2de477ab0676d2"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/guzzle/uri-template/zipball/30e286560c137526eccd4ce21b2de477ab0676d2",Ð
"reference": "30e286560c137526eccd4ce21b2de477ab0676d2",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.2.5 || ^8.0",Ð "symfony/polyfill-
php80": "^1.24"Ð },Ð "require-dev": {Ð
"bamarni/composer-bin-plugin": "^1.8.2",Ð "phpunit/phpunit":
"^8.5.36 || ^9.6.15",Ð "uri-template/tests": "1.0.0"Ð
},Ð "time": "2025-02-03T10:55:03+00:00",Ð
"type": "library",Ð "extra": {Ð "bamarni-bin": {Ð
"bin-links": true,Ð "forward-command":
falseÐ }Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"GuzzleHttp\\UriTemplate\\": "src"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Graham Campbell",Ð "email":
"hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/
GrahamCampbell"Ð },Ð {Ð "name":
"Michael Dowling",Ð "email": "mtdowling@gmail.com",Ð
"homepage": "https://github.com/mtdowling"Ð
},Ð {Ð "name": "George
Mponos",Ð "email": "gmponos@gmail.com",Ð
"homepage": "https://github.com/gmponos"Ð },Ð {Ð
"name": "Tobias Nyholm",Ð "email":
"tobias.nyholm@gmail.com",Ð "homepage": "https://github.com/
Nyholm"Ð }Ð],Ð "description": "A polyfill
class for uri_template of PHP",Ð "keywords": [Ð
"guzzlehttp",Ð "uri-template"Ð],Ð
"support": {Ð "issues": "https://github.com/guzzle/uri-template/
issues",Ð "source": "https://github.com/guzzle/uri-template/
tree/v1.0.4"Ð },Ð "funding": [Ð {Ð
"url": "https://github.com/GrahamCampbell",Ð
"type": "github"Ð },Ð {Ð
"url": "https://github.com/Nyholm",Ð
"type": "github"Ð },Ð {Ð "url":
"https://tidelift.com/funding/github/packagist/guzzlehttp/uri-template",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../guzzlehttp/uri-template"Ð },Ð {Ð
"name": "hamcrest/hamcrest-php",Ð "version": "v2.1.1",Ð
"version_normalized": "2.1.1.0",Ð "source": {Ð
"type": "git",Ð

"url": "https://github.com/hamcrest/hamcrest-php.git",Ð "reference": "f8b1c0173b22fa6ec77a81fe63e5b01eba7e6487"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/hamcrest/hamcrest-php/zipball/f8b1c0173b22fa6ec77a81fe63e5b01eba7e6487",Ð "reference": "f8b1c0173b22fa6ec77a81fe63e5b01eba7e6487",Ð "shasum": ""Ð },Ð "require": {Ð "php": "^7.4|^8.0"Ð },Ð "replace": {Ð "cordoval/hamcrest-php": "*",Ð "davedevelopment/hamcrest-php": "*",Ð "kodova/hamcrest-php": "*"Ð },Ð "require-dev": {Ð "phpunit/php-file-iterator": "^1.4 || ^2.0 || ^3.0",Ð "phpunit/phpunit": "^4.8.36 || ^5.7 || ^6.5 || ^7.0 || ^8.0 || ^9.0"Ð },Ð "time": "2025-04-30T06:54:44+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.1-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "hamcrest"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "description": "This is the PHP port of Hamcrest Matchers",Ð "keywords": [Ð "test"Ð],Ð "support": {Ð "issues": "https://github.com/hamcrest/hamcrest-php/issues",Ð "source": "https://github.com/hamcrest/hamcrest-php/tree/v2.1.1"Ð },Ð "install-path": "../hamcrest/hamcrest-php"Ð },Ð {Ð "name": "intervention/image",Ð "version": "2.7.2",Ð "version_normalized": "2.7.2.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/Intervention/image.git",Ð "reference": "04be355f8d6734c826045d02a1079ad658322dad"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/Intervention/image/zipball/04be355f8d6734c826045d02a1079ad658322dad",Ð "reference": "04be355f8d6734c826045d02a1079ad658322dad",Ð "shasum": ""Ð },Ð "require": {Ð "ext-fileinfo": "*",Ð "guzzlehttp/psr7": "~1.1 || ^2.0",Ð "php": ">=5.4.0"Ð },Ð "require-dev": {Ð "mockery/mockery": "~0.9.2",Ð "phpunit/phpunit": "^4.8 || ^5.7 || ^7.5.15"Ð },Ð "suggest": {Ð "ext-gd": "to use GD library based image processing.",Ð "ext-imagick": "to use Imagick based image processing.",Ð "intervention/imagecache": "Caching extension for the Intervention Image library"Ð },Ð "time": "2022-05-21T17:30:32+00:00",Ð "type": "library",Ð "extra": {Ð "laravel": {Ð "aliases": {Ð "Image": "Intervention\\Image\\Facades\\Image"Ð },Ð "providers": [Ð "Intervention\\Image\\ImageServiceProvider"Ð]Ð },Ð "branch-alias": {Ð "dev-master": "2.4-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Intervention\\Image\\": "src/Intervention/Image"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Oliver Vogel",Ð "email": "oliver@intervention.io",Ð "homepage": "https://intervention.io/"Ð }Ð],Ð "description": "Image handling and manipulation library with support for Laravel integration",Ð "homepage": "http://image.intervention.io/",Ð "keywords": [Ð

"gd",Ð "image",Ð
"imagick",Ð "laravel",Ð
"thumbnail",Ð "watermark"Ð],Ð "support": {Ð
"issues": "https://github.com/Intervention/image/issues",Ð
"source": "https://github.com/Intervention/image/tree/2.7.2"Ð
},Ð "funding": [Ð {Ð
"url": "https://paypal.me/interventionio",Ð "type": "custom"Ð
},Ð {Ð "url": "https://
github.com/Intervention",Ð "type": "github"Ð }Ð
],Ð "install-path": "../intervention/image"Ð },Ð
{Ð "name": "kitloong/laravel-migrations-generator",Ð
"version": "v6.11.1",Ð "version_normalized": "6.11.1.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/kitloong/laravel-migrations-generator.git",Ð
"reference": "0f007e86dce6e0cfd71dc0b757da18851c376c3b"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/kitloong/laravel-
migrations-generator/zipball/0f007e86dce6e0cfd71dc0b757da18851c376c3b",Ð
"reference": "0f007e86dce6e0cfd71dc0b757da18851c376c3b",Ð
"shasum": ""Ð },Ð "require": {Ð
"doctrine/dbal": "^2.4|^3.0",Ð "ext-pdo": "*",Ð
"illuminate/support": "^5.6|^6.0|^7.0|^8.0|^9.0|^10.0",Ð
"myclabs/php-enum": "^1.6|^1.7|^1.8",Ð "php":
">=7.1.3"Ð },Ð "require-dev": {Ð "barryvdh/
laravel-ide-helper": "^2.5",Ð "friendsofphp/php-cs-fixer":
"^2.19.0|^3.1",Ð "larastan/larastan": "^0.4|^0.5|^0.6|^0.7|^1.0|
^2.0",Ð "mockery/mockery": "^1.0",Ð "orchestra/
testbench": "^3.6|^4.0|^5.0|^6.0|^7.0|^8.0",Ð "phpmd/phpmd":
"^2.10",Ð "slevomat/coding-standard": "^6.0|^7.0|^8.5",Ð
"squizlabs/php_codesniffer": "^3.5"Ð },Ð
"time": "2024-02-06T14:42:33+00:00",Ð "type": "library",Ð
"extra": {Ð "laravel": {Ð "providers": [Ð
"KitLoong\\MigrationsGenerator\
\MigrationsGeneratorServiceProvider"Ð]Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "KitLoong\
\MigrationsGenerator\\": "src"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Kit Loong",Ð "email":
"kitloong1008@gmail.com"Ð }Ð],Ð
"description": "Generates Laravel Migrations from an existing database",Ð
"keywords": [Ð "artisan",Ð
"generator",Ð "laravel",Ð "lumen",Ð
"migration",Ð "migrations"Ð],Ð "support": {Ð
"issues": "https://github.com/kitloong/laravel-migrations-
generator/issues",Ð "source": "https://github.com/kitloong/
laravel-migrations-generator/tree/v6.11.1"Ð },Ð
"funding": [Ð {Ð "url": "https://
www.buymeacoffee.com/kitloong",Ð "type": "custom"Ð
}Ð],Ð "install-path": "../kitloong/
laravel-migrations-generator"Ð },Ð {Ð "name": "laravel/
breeze",Ð "version": "v1.19.2",Ð "version_normalized":
"1.19.2.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/laravel/breeze.git",Ð
"reference": "725e0c4fb1f630afdd90b5fba2a7f6d8d547ac29"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/laravel/breeze/
zipball/725e0c4fb1f630afdd90b5fba2a7f6d8d547ac29",Ð
"reference": "725e0c4fb1f630afdd90b5fba2a7f6d8d547ac29",Ð

"shasum": ""Ð },Ð "require": {Ð "illuminate/console": "^9.21|^10.0",Ð "illuminate/filesystem": "^9.21|^10.0",Ð "illuminate/support": "^9.21|^10.0",Ð "illuminate/validation": "^9.21|^10.0",Ð "php": "^8.0.2"Ð },Ð "conflict": {Ð "laravel/framework": "<9.37.0"Ð },Ð "time": "2023-02-18T20:55:43+00:00",Ð "type": "library",Ð "extra": {Ð "laravel": {Ð "providers": [Ð "Laravel\\Breeze\\BreezeServiceProvider"Ð]Ð },Ð "branch-alias": {Ð "dev-master": "1.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Laravel\\Breeze\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Taylor Otwell",Ð "email": "taylor@laravel.com"Ð }Ð],Ð "description": "Minimal Laravel authentication scaffolding with Blade and Tailwind.",Ð "keywords": [Ð "auth",Ð "laravel"Ð],Ð "support": {Ð "issues": "https://github.com/laravel/breeze/issues",Ð "source": "https://github.com/laravel/breeze"Ð },Ð "install-path": "../laravel/breeze"Ð },Ð {Ð "name": "laravel/framework",Ð "version": "v9.52.20",Ð "version_normalized": "9.52.20.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/laravel/framework.git",Ð "reference": "2bb6835af73fcf0d1d0bfb84af71cef236cb8609"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/laravel/framework/zipball/2bb6835af73fcf0d1d0bfb84af71cef236cb8609",Ð "reference": "2bb6835af73fcf0d1d0bfb84af71cef236cb8609",Ð "shasum": ""Ð },Ð "require": {Ð "brick/math": "^0.9.3|^0.10.2|^0.11",Ð "doctrine/inflector": "^2.0.5",Ð "dragonmantank/cron-expression": "^3.3.2",Ð "egulias/email-validator": "^3.2.1|^4.0",Ð "ext-ctype": "*",Ð "ext-filter": "*",Ð "ext-hash": "*",Ð "ext-mbstring": "*",Ð "ext-openssl": "*",Ð "ext-session": "*",Ð "ext-tokenizer": "*",Ð "fruitcake/php-cors": "^1.2",Ð "guzzlehttp/uri-template": "^1.0",Ð "laravel/serializable-closure": "^1.2.2",Ð "league/commonmark": "^2.2.1",Ð "league/flysystem": "^3.8.0",Ð "monolog/monolog": "^2.0",Ð "nesbot/carbon": "^2.62.1",Ð "nunomaduro/termwind": "^1.13",Ð "php": "^8.0.2",Ð "psr/container": "^1.1.1|^2.0.1",Ð "psr/log": "^1.0|^2.0|^3.0",Ð "psr/simple-cache": "^1.0|^2.0|^3.0",Ð "ramsey/uuid": "^4.7",Ð "symfony/console": "^6.0.9",Ð "symfony/error-handler": "^6.0",Ð "symfony/finder": "^6.0",Ð "symfony/http-foundation": "^6.0",Ð "symfony/http-kernel": "^6.0",Ð "symfony/mailer": "^6.0",Ð "symfony/mime": "^6.0",Ð "symfony/process": "^6.0",Ð "symfony/routing": "^6.0",Ð "symfony/uid": "^6.0",Ð "symfony/var-dumper": "^6.0",Ð "tijsverkoyen/css-to-inline-styles": "^2.2.5",Ð "vlucas/phpdotenv": "^5.4.1",Ð "voku/portable-ascii": "^2.0"Ð },Ð "conflict": {Ð "tightenco/collect": "<5.5.33"Ð },Ð "provide": {Ð "psr/container-implementation": "1.1|2.0",Ð

"psr/simple-cache-implementation": "1.0|2.0|3.0"Ð
},Ð "replace": {Ð "illuminate/auth":
"self.version",Ð "illuminate/broadcasting": "self.version",Ð
"illuminate/bus": "self.version",Ð "illuminate/
cache": "self.version",Ð "illuminate/collections":
"self.version",Ð "illuminate/conditionable": "self.version",Ð
"illuminate/config": "self.version",Ð
"illuminate/console": "self.version",Ð "illuminate/container":
"self.version",Ð "illuminate/contracts": "self.version",Ð
"illuminate/cookie": "self.version",Ð
"illuminate/database": "self.version",Ð "illuminate/
encryption": "self.version",Ð "illuminate/events":
"self.version",Ð "illuminate/filesystem": "self.version",Ð
"illuminate/hashing": "self.version",Ð
"illuminate/http": "self.version",Ð "illuminate/log":
"self.version",Ð "illuminate/macroable": "self.version",Ð
"illuminate/mail": "self.version",Ð "illuminate/
notifications": "self.version",Ð "illuminate/pagination":
"self.version",Ð "illuminate/pipeline": "self.version",Ð
"illuminate/queue": "self.version",Ð
"illuminate/redis": "self.version",Ð "illuminate/routing":
"self.version",Ð "illuminate/session": "self.version",Ð
"illuminate/support": "self.version",Ð
"illuminate/testing": "self.version",Ð "illuminate/
translation": "self.version",Ð "illuminate/validation":
"self.version",Ð "illuminate/view": "self.version"Ð },Ð
"require-dev": {Ð "ably/ably-php": "^1.0",Ð
"aws/aws-sdk-php": "^3.235.5",Ð "doctrine/
dbal": "^2.13.3|^3.1.4",Ð "ext-gmp": "*",Ð
"fakerphp/faker": "^1.21",Ð "guzzlehttp/guzzle": "^7.5",Ð
"league/flysystem-aws-s3-v3": "^3.0",Ð "league/
flysystem-ftp": "^3.0",Ð "league/flysystem-path-prefixing":
"^3.3",Ð "league/flysystem-read-only": "^3.3",Ð
"league/flysystem-sftp-v3": "^3.0",Ð "mockery/mockery":
"^1.5.1",Ð "orchestra/testbench-core": "^7.24",Ð
"pda/pheanstalk": "^4.0",Ð "phpstan/phpdoc-parser": "^1.15",Ð
"phpstan/phpstan": "^1.4.7",Ð "phpunit/
phpunit": "^9.5.8",Ð "predis/predis": "^1.1.9|^2.0.2",Ð
"symfony/cache": "^6.0",Ð "symfony/http-
client": "^6.0"Ð },Ð "suggest": {Ð "ably/
ably-php": "Required to use the Ably broadcast driver (^1.0).",Ð
"aws/aws-sdk-php": "Required to use the SQS queue driver,
DynamoDb failed job storage, and SES mail driver (^3.235.5).",Ð
"brianium/paratest": "Required to run tests in parallel (^6.0).",Ð
"doctrine/dbal": "Required to rename columns and drop SQLite
columns (^2.13.3|^3.1.4).",Ð "ext-apcu": "Required to use the
APC cache driver.",Ð "ext-fileinfo": "Required to use the
Filesystem class.",Ð "ext-ftp": "Required to use the Flysystem
FTP driver.",Ð "ext-gd": "Required to use Illuminate\\Http\
\Testing\\FileFactory::image().",Ð "ext-memcached": "Required
to use the memcache cache driver.",Ð "ext-pcntl": "Required to
use all features of the queue worker and console signal trapping.",Ð
"ext-pdo": "Required to use all database features.",Ð
"ext-posix": "Required to use all features of the queue
worker.",Ð "ext-redis": "Required to use the Redis cache and
queue drivers (^4.0|^5.0).",Ð "fakerphp/faker": "Required to
use the eloquent factory builder (^1.9.1).",Ð "filp/whoops":
"Required for friendly error pages in development (^2.14.3).",Ð
"guzzlehttp/guzzle": "Required to use the HTTP Client and the ping methods on
schedules (^7.5).",Ð

"laravel/tinker": "Required to use the tinker console command (^2.0).",Đ "league/flysystem-aws-s3-v3": "Required to use the Flysystem S3 driver (^3.0).",Đ "league/flysystem-ftp": "Required to use the Flysystem FTP driver (^3.0).",Đ "league/flysystem-path-prefixing": "Required to use the scoped driver (^3.3).",Đ "league/flysystem-read-only": "Required to use read-only disks (^3.3)",Đ "league/flysystem-sftp-v3": "Required to use the Flysystem SFTP driver (^3.0).",Đ "mockery/mockery": "Required to use mocking (^1.5.1).",Đ "nyholm/psr7": "Required to use PSR-7 bridging features (^1.2).",Đ "pda/pheanstalk": "Required to use the beanstalk queue driver (^4.0).",Đ "phpunit/phpunit": "Required to use assertions and run tests (^9.5.8).",Đ "predis/predis": "Required to use the predis connector (^1.1.9|^2.0.2).",Đ "psr/http-message": "Required to allow Storage::put to accept a StreamInterface (^1.0).",Đ "pusher/pusher-php-server": "Required to use the Pusher broadcast driver (^6.0|^7.0).",Đ "symfony/cache": "Required to PSR-6 cache bridge (^6.0).",Đ "symfony/filesystem": "Required to enable support for relative symbolic links (^6.0).",Đ "symfony/http-client": "Required to enable support for the Symfony API mail transports (^6.0).",Đ "symfony/mailgun-mailer": "Required to enable support for the Mailgun mail transport (^6.0).",Đ "symfony/postmark-mailer": "Required to enable support for the Postmark mail transport (^6.0).",Đ "symfony/psr-http-message-bridge": "Required to use PSR-7 bridging features (^2.0)."Đ },Đ "time": "2025-01-31T10:09:38+00:00",Đ "type": "library",Đ "extra": {Đ "branch-alias": {Đ "dev-master": "9.x-dev"Đ }Đ },Đ "installation-source": "dist",Đ "autoload": {Đ "files": [Đ "src/Illuminate/Collections/helpers.php",Đ "src/Illuminate/Events/functions.php",Đ "src/Illuminate/Foundation/helpers.php",Đ "src/Illuminate/Support/helpers.php"Đ],Đ "psr-4": {Đ "Illuminate\\": "src/Illuminate/",Đ "Illuminate\\Support\\": [Đ "src/Illuminate/Macroable/",Đ "src/Illuminate/Collections/",Đ "src/Illuminate/Conditionable/"Đ]Đ }Đ },Đ "notification-url": "https://packagist.org/downloads/",Đ "license": [Đ "MIT"Đ],Đ "authors": [Đ {Đ "name": "Taylor Otwell",Đ "email": "taylor@laravel.com"Đ }Đ],Đ "description": "The Laravel Framework.",Đ "homepage": "https://laravel.com",Đ "keywords": [Đ "framework",Đ "laravel"Đ],Đ "support": {Đ "issues": "https://github.com/laravel/framework/issues",Đ "source": "https://github.com/laravel/framework"Đ },Đ "install-path": "../laravel/framework"Đ },Đ {Đ "name": "laravel/sail",Đ "version": "v1.42.0",Đ "version_normalized": "1.42.0.0",Đ "source": {Đ "type": "git",Đ "url": "https://github.com/laravel/sail.git",Đ "reference": "2edaaf77f3c07a4099965bb3d7dfee16e801c0f6"Đ },Đ "dist": {Đ "type": "zip",Đ "url": "https://api.github.com/repos/laravel/sail/zipball/2edaaf77f3c07a4099965bb3d7dfee16e801c0f6",Đ "reference": "2edaaf77f3c07a4099965bb3d7dfee16e801c0f6",Đ "shasum": ""Đ },Đ "require": {Đ "illuminate/console": "^9.52.16|^10.0|^11.0|^12.0",Đ "illuminate/contracts": "^9.52.16|^10.0|^11.0|^12.0",Đ "illuminate/support": "^9.52.16|^10.0|^11.0|^12.0",Đ "php": "^8.0",Đ

"symfony/console": "^6.0|^7.0",Đ
"symfony/yaml": "^6.0|^7.0"Đ },Đ "require-dev": {Đ
"orchestra/testbench": "^7.0|^8.0|^9.0|^10.0",Đ
"phpstan/phpstan": "^1.10"Đ },Đ "time": "2025-04-29T14:26:46+00:00",Đ
"bin": [Đ "bin/sail"Đ
],Đ "type": "library",Đ "extra": {Đ
"laravel": {Đ "providers": [Đ
"Laravel\\Sail\\SailServiceProvider"Đ
]Đ }Đ },Đ "installation-source": "dist",Đ
"autoload": {Đ "psr-4": {Đ
"Laravel\\Sail\\": "src/"Đ }Đ },Đ
"notification-url": "https://packagist.org/downloads/",Đ
"license": [Đ "MIT"Đ],Đ
"authors": [Đ {Đ "name": "Taylor Otwell",Đ
"email": "taylor@laravel.com"Đ }Đ
],Đ "description": "Docker files for running a basic Laravel application.",Đ
"keywords": [Đ "docker",Đ
"laravel"Đ],Đ "support": {Đ
"issues": "https://github.com/laravel/sail/issues",Đ
"source": "https://github.com/laravel/sail"Đ },Đ
"install-path": "../laravel/sail"Đ },Đ {Đ
"name": "laravel/sanctum",Đ "version": "v2.15.1",Đ
"version_normalized": "2.15.1.0",Đ "source": {Đ
"type": "git",Đ "url": "https://github.com/laravel/sanctum.git",Đ
"reference": "31fbe6f85aee080c4dc2f9b03dc6dd5d0ee72473"Đ
},Đ "dist": {Đ "type": "zip",Đ
"url": "https://api.github.com/repos/laravel/sanctum/zipball/31fbe6f85aee080c4dc2f9b03dc6dd5d0ee72473",Đ
"reference": "31fbe6f85aee080c4dc2f9b03dc6dd5d0ee72473",Đ
"shasum": ""Đ },Đ "require": {Đ "ext-json": "*",Đ
"illuminate/console": "^6.9|^7.0|^8.0|^9.0",Đ
"illuminate/contracts": "^6.9|^7.0|^8.0|^9.0",Đ
"illuminate/database": "^6.9|^7.0|^8.0|^9.0",Đ "illuminate/support": "^6.9|^7.0|^8.0|^9.0",Đ
"php": "^7.2|^8.0"Đ
},Đ "require-dev": {Đ "mockery/mockery": "^1.0",Đ
"orchestra/testbench": "^4.0|^5.0|^6.0|^7.0",Đ
"phpunit/phpunit": "^8.0|^9.3"Đ },Đ
"time": "2022-04-08T13:39:49+00:00",Đ "type": "library",Đ
"extra": {Đ "laravel": {Đ "providers": [Đ
"Laravel\\Sanctum\\SanctumServiceProvider"Đ
]Đ },Đ "branch-alias": {Đ
"dev-master": "2.x-dev"Đ }Đ },Đ
"installation-source": "dist",Đ "autoload": {Đ
"psr-4": {Đ "Laravel\\Sanctum\\": "src/"Đ
}Đ },Đ "notification-url": "https://packagist.org/downloads/",Đ
"license": [Đ "MIT"Đ
],Đ "authors": [Đ {Đ
"name": "Taylor Otwell",Đ "email": "taylor@laravel.com"Đ
}Đ],Đ "description": "Laravel Sanctum provides a featherweight authentication system for SPAs and simple APIs.",Đ
"keywords": [Đ "auth",Đ "laravel",Đ
"sanctum"Đ],Đ "support": {Đ
"issues": "https://github.com/laravel/sanctum/issues",Đ
"source": "https://github.com/laravel/sanctum"Đ },Đ
"install-path": "../laravel/sanctum"Đ },Đ {Đ
"name": "laravel/serializable-closure",Đ "version": "v1.3.7",Đ
"version_normalized": "1.3.7.0",Đ "source": {Đ
"type": "git",Đ "url": "https://github.com/laravel/serializable-closure.git",Đ
"reference": "4f48ade902b94323ca3be7646db16209ec76be3d"Đ

},Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/laravel/serializable-closure/zipball/4f48ade902b94323ca3be7646db16209ec76be3d",Ð
"reference": "4f48ade902b94323ca3be7646db16209ec76be3d",Ð
"shasum": ""Ð },Ð "require": {Ð "php": "^7.3|^8.0"Ð },Ð "require-dev": {Ð
"illuminate/support": "^8.0|^9.0|^10.0|^11.0",Ð "nesbot/carbon": "^2.61|^3.0",Ð "pestphp/pest": "^1.21.3",Ð
"phpstan/phpstan": "^1.8.2",Ð "symfony/var-dumper": "^5.4.11|^6.2.0|^7.0.0"Ð },Ð "time": "2024-11-14T18:34:49+00:00",Ð
"type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master": "1.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Laravel\\SerializableClosure\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Taylor Otwell",Ð
"email": "taylor@laravel.com"Ð },Ð
{Ð "name": "Nuno Maduro",Ð
"email": "nuno@laravel.com"Ð }Ð],Ð
"description": "Laravel Serializable Closure provides an easy and secure way to serialize closures in PHP.",Ð
"keywords": [Ð
"closure",Ð "laravel",Ð
"serializable"Ð],Ð "support": {Ð "issues": "https://github.com/laravel/serializable-closure/issues",Ð
"source": "https://github.com/laravel/serializable-closure"Ð },Ð
"install-path": "../laravel/serializable-closure"Ð },Ð
{Ð "name": "laravel/tinker",Ð "version": "v2.10.1",Ð
"version_normalized": "2.10.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/laravel/tinker.git",Ð
"reference": "22177cc71807d38f2810c6204d8f7183d88a57d3"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/laravel/tinker/zipball/22177cc71807d38f2810c6204d8f7183d88a57d3",Ð
"reference": "22177cc71807d38f2810c6204d8f7183d88a57d3",Ð
"shasum": ""Ð },Ð "require": {Ð
"illuminate/console": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð
"illuminate/contracts": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð
"illuminate/support": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð
"php": "^7.2.5|^8.0",Ð "psy/psysh": "^0.11.1|^0.12.0",Ð
"symfony/var-dumper": "^4.3.4|^5.0|^6.0|^7.0"Ð },Ð "require-dev": {Ð "mockery/mockery": "~1.3.3|^1.4.2",Ð
"phpstan/phpstan": "^1.10",Ð
"phpunit/phpunit": "^8.5.8|^9.3.3|^10.0"Ð },Ð
"suggest": {Ð "illuminate/database": "The Illuminate Database package (^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0)."Ð
},Ð "time": "2025-01-27T14:24:01+00:00",Ð
"type": "library",Ð "extra": {Ð "laravel": {Ð
"providers": [Ð "Laravel\\Tinker\\TinkerServiceProvider"Ð]Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Laravel\\Tinker\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Taylor Otwell",Ð "email": "taylor@laravel.com"Ð }Ð],Ð "description": "Powerful REPL for the Laravel framework.",Ð

"keywords": [Ð "REPL",Ð
"Tinker",Ð "laravel",Ð "psysh"Ð
],Ð "support": {Ð "issues": "https://
github.com/laravel/tinker/issues",Ð "source": "https://
github.com/laravel/tinker/tree/v2.10.1"Ð },Ð "install-
path": "../laravel/tinker"Ð },Ð {Ð "name": "laravel/ui",Ð
"version": "v3.4.6",Ð "version_normalized": "3.4.6.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/laravel/ui.git",Ð "reference":
"65ec5c03f7fee2c8ecae785795b829a15be48c2c"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/laravel/ui/zipball/65ec5c03f7fee2c8ecae785795b829a15be48c2c",Ð
"reference": "65ec5c03f7fee2c8ecae785795b829a15be48c2c",Ð
"shasum": ""Ð },Ð "require": {Ð
"illuminate/console": "^8.42|^9.0",Ð
"illuminate/filesystem": "^8.42|^9.0",Ð "illuminate/support":
"^8.82|^9.0",Ð "illuminate/validation": "^8.42|^9.0",Ð
"php": "^7.3|^8.0"Ð },Ð "require-dev": {Ð
"orchestra/testbench": "^6.23|^7.0"Ð },Ð
"time": "2022-05-20T13:38:08+00:00",Ð "type": "library",Ð
"extra": {Ð "laravel": {Ð "providers": [Ð
"Laravel\\Ui\\UiServiceProvider"Ð]Ð
},Ð "branch-alias": {Ð "dev-
master": "3.x-dev"Ð }Ð },Ð "installation-
source": "dist",Ð "autoload": {Ð "psr-4": {Ð
"Laravel\\Ui\\": "src/",Ð "Illuminate\
\Foundation\\Auth\\": "auth-backend/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Taylor Otwell",Ð
"email": "taylor@laravel.com"Ð }Ð
],Ð "description": "Laravel UI utilities and presets.",Ð
"keywords": [Ð "laravel",Ð "ui"Ð
],Ð "support": {Ð "source": "https://
github.com/laravel/ui/tree/v3.4.6"Ð },Ð "install-path":
"../laravel/ui"Ð },Ð {Ð "name": "league/commonmark",Ð
"version": "2.6.2",Ð "version_normalized": "2.6.2.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/thephpleague/commonmark.git",Ð "reference":
"06c3b0bf2540338094575612f4a1778d0d2d5e94"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/thephpleague/commonmark/
zipball/06c3b0bf2540338094575612f4a1778d0d2d5e94",Ð
"reference": "06c3b0bf2540338094575612f4a1778d0d2d5e94",Ð
"shasum": ""Ð },Ð "require": {Ð "ext-
mbstring": "*",Ð "league/config": "^1.1.1",Ð
"php": "^7.4 || ^8.0",Ð "psr/event-dispatcher": "^1.0",Ð
"symfony/deprecation-contracts": "^2.1 || ^3.0",Ð
"symfony/polyfill-php80": "^1.16"Ð },Ð
"require-dev": {Ð "cebe/markdown": "^1.0",Ð
"commonmark/cmark": "0.31.1",Ð "commonmark/commonmark.js":
"0.31.1",Ð "composer/package-versions-deprecated": "^1.8",Ð
"embed/embed": "^4.4",Ð "erusev/parsedown":
"^1.0",Ð "ext-json": "*",Ð "github/gfm": "0.29.0",Ð
"michelf/php-markdown": "^1.4 || ^2.0",Ð
"nyholm/psr7": "^1.5",Ð "phpstan/phpstan": "^1.8.2",Ð
"phpunit/phpunit": "^9.5.21 || ^10.5.9 || ^11.0.0",Ð
"scrutinizer/ocular": "^1.8.1",Ð "symfony/
finder": "^5.3 | ^6.0 | ^7.0",Ð "symfony/process": "^5.4 | ^6.0
| ^7.0",Ð

"symfony/yaml": "^2.3 | ^3.0 | ^4.0 | ^5.0 | ^6.0 | ^7.0",Ð "unleashedtech/php-coding-standard": "^3.1.1",Ð "vimeo/psalm": "^4.24.0 || ^5.0.0"Ð },Ð "suggest": {Ð "symfony/yaml": "v2.3+ required if using the Front Matter extension"Ð },Ð "time": "2025-04-18T21:09:27+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "2.7-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "League\\CommonMark\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Colin O'Dell",Ð "email": "colinodell@gmail.com",Ð "homepage": "https://www.colinodell.com",Ð "role": "Lead Developer"Ð }Ð],Ð "description": "Highly-extensible PHP Markdown parser which fully supports the CommonMark spec and GitHub-Flavored Markdown (GFM)",Ð "homepage": "https://commonmark.thephpleague.com",Ð "keywords": [Ð "commonmark",Ð "flavored",Ð "gfm",Ð "github",Ð "github-flavored",Ð "markdown",Ð "md",Ð "parser"Ð],Ð "support": {Ð "docs": "https://commonmark.thephpleague.com/",Ð "forum": "https://github.com/thephpleague/commonmark/discussions",Ð "issues": "https://github.com/thephpleague/commonmark/issues",Ð "rss": "https://github.com/thephpleague/commonmark/releases.atom",Ð "source": "https://github.com/thephpleague/commonmark"Ð },Ð "funding": [Ð {Ð "url": "https://www.colinodell.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://www.paypal.me/colinpodell/10.00",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/colinodell",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/league/commonmark",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../league/commonmark"Ð },Ð {Ð "name": "league/config",Ð "version": "v1.2.0",Ð "version_normalized": "1.2.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/thephpleague/config.git",Ð "reference": "754b3604fb2984c71f4af4a9cbe7b57f346ec1f3"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/thephpleague/config/zipball/754b3604fb2984c71f4af4a9cbe7b57f346ec1f3",Ð "reference": "754b3604fb2984c71f4af4a9cbe7b57f346ec1f3",Ð "shasum": ""Ð },Ð "require": {Ð "dflydev/dot-access-data": "^3.0.1",Ð "nette/schema": "^1.2",Ð "php": "^7.4 || ^8.0"Ð },Ð "require-dev": {Ð "phpstan/phpstan": "^1.8.2",Ð "phpunit/phpunit": "^9.5.5",Ð "scrutinizer/ocular": "^1.8.1",Ð "unleashedtech/php-coding-standard": "^3.1",Ð "vimeo/psalm": "^4.7.3"Ð },Ð "time": "2022-12-11T20:36:23+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "1.2-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "League\\Config\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð

"name": "Colin O'Dell",Ð
"email": "colinodell@gmail.com",Ð
"homepage": "https://www.colinodell.com",Ð
"role": "Lead Developer"Ð
}Ð
],Ð
"description": "Define configuration arrays with strict schemas and access values with dot notation",Ð
"homepage": "https://config.thephpleague.com",Ð
"keywords": [Ð
"array",Ð
"config",Ð
"configuration",Ð
"dot",Ð
"dot-access",Ð
"nested",Ð
"schema"Ð
],Ð
"support": {Ð
"docs": "https://config.thephpleague.com/",Ð
"issues": "https://github.com/thephpleague/config/issues",Ð
"rss": "https://github.com/thephpleague/config/releases.atom",Ð
"source": "https://github.com/thephpleague/config"Ð
},Ð
"funding": [Ð
{Ð
"url": "https://www.colinodell.com/sponsor",Ð
"type": "custom"Ð
},Ð
{Ð
"url": "https://www.paypal.me/colinpodell/10.00",Ð
"type": "custom"Ð
},Ð
{Ð
"url": "https://github.com/colinodell",Ð
"type": "github"Ð
}Ð
],Ð
"install-path": "../league/config"Ð
},Ð
{Ð
"name": "league/flysystem",Ð
"version": "3.29.1",Ð
"version_normalized": "3.29.1.0",Ð
"source": {Ð
"type": "git",Ð
"url": "https://github.com/thephpleague/flysystem.git",Ð
"reference": "edc1bb7c86fab0776c3287dbd19b5fa278347319"Ð
},Ð
"dist": {Ð
"type": "zip",Ð
"url": "https://api.github.com/repos/thephpleague/flysystem/zipball/edc1bb7c86fab0776c3287dbd19b5fa278347319",Ð
"reference": "edc1bb7c86fab0776c3287dbd19b5fa278347319",Ð
"shasum": ""Ð
},Ð
"require": {Ð
"league/flysystem-local": "^3.0.0",Ð
"league/mime-type-detection": "^1.0.0",Ð
"php": "^8.0.2"Ð
},Ð
"conflict": {Ð
"async-aws/core": "<1.19.0",Ð
"async-aws/s3": "<1.14.0",Ð
"aws/aws-sdk-php": "3.209.31 || 3.210.0",Ð
"guzzlehttp/guzzle": "<7.0",Ð
"guzzlehttp/ringphp": "<1.1.1",Ð
"phpseclib/phpseclib": "3.0.15",Ð
"symfony/http-client": "<5.2"Ð
},Ð
"require-dev": {Ð
"async-aws/s3": "^1.5 || ^2.0",Ð
"async-aws/simple-s3": "^1.1 || ^2.0",Ð
"aws/aws-sdk-php": "^3.295.10",Ð
"composer/semver": "^3.0",Ð
"ext-fileinfo": "*",Ð
"ext-ftp": "*",Ð
"ext-mongodb": "^1.3",Ð
"ext-zip": "*",Ð
"friendsofphp/php-cs-fixer": "^3.5",Ð
"google/cloud-storage": "^1.23",Ð
"guzzlehttp/psr7": "^2.6",Ð
"microsoft/azure-storage-blob": "^1.1",Ð
"mongodb/mongodb": "^1.2",Ð
"phpseclib/phpseclib": "^3.0.36",Ð
"phpstan/phpstan": "^1.10",Ð
"phpunit/phpunit": "^9.5.11|^10.0",Ð
"sabre/dav": "^4.6.0"Ð
},Ð
"time": "2024-10-08T08:58:34+00:00",Ð
"type": "library",Ð
"installation-source": "dist",Ð
"autoload": {Ð
"psr-4": {Ð
"League\\Flysystem\\": "src"Ð
}Ð
},Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð
"MIT"Ð
],Ð
"authors": [Ð
{Ð
"name": "Frank de Jonge",Ð
"email": "info@frankdejonge.nl"Ð
}Ð
],Ð
"description": "File storage abstraction for PHP",Ð
"keywords": [Ð
"WebDAV",Ð
"aws",Ð
"cloud",Ð
"file",Ð
"files",Ð
"filesystem",Ð
"filesystems",Ð

"ftp",Ð "s3",Ð
"sftp",Ð "storage"Ð],Ð "support": {Ð
"issues": "https://github.com/thephpleague/flysystem/issues",Ð
"source": "https://github.com/thephpleague/flysystem/
tree/3.29.1"Ð },Ð "install-path": "../league/flysystem"Ð
},Ð {Ð "name": "league/flysystem-local",Ð
"version": "3.29.0",Ð "version_normalized": "3.29.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://
github.com/thephpleague/flysystem-local.git",Ð "reference":
"e0e8d52ce4b2ed154148453d321e97c8e931bd27"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/thephpleague/flysystem-local/zipball/
e0e8d52ce4b2ed154148453d321e97c8e931bd27",Ð "reference":
"e0e8d52ce4b2ed154148453d321e97c8e931bd27",Ð "shasum": ""Ð
},Ð "require": {Ð "ext-fileinfo": "*",Ð
"league/flysystem": "^3.0.0",Ð "league/mime-
type-detection": "^1.0.0",Ð "php": "^8.0.2"Ð },Ð
"time": "2024-08-09T21:24:39+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "League\\Flysystem\\Local\\": ""Ð
}Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "Frank de Jonge",Ð "email": "info@frankdejonge.nl"Ð
}Ð],Ð "description": "Local filesystem
adapter for Flysystem.",Ð "keywords": [Ð "Flysystem",Ð
"file",Ð "files",Ð "filesystem",Ð
"local"Ð],Ð "support": {Ð
"source": "https://github.com/thephpleague/flysystem-local/tree/3.29.0"Ð
},Ð "install-path": "../league/flysystem-local"Ð
},Ð {Ð "name": "league/mime-type-detection",Ð
"version": "1.16.0",Ð "version_normalized": "1.16.0.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/thephpleague/mime-type-detection.git",Ð
"reference": "2d6702ff215bf922936ccc1ad31007edc76451b9"Ð },Ð
"dist": {Ð "type": "zip",Ð "url":
"https://api.github.com/repos/thephpleague/mime-type-detection/
zipball/2d6702ff215bf922936ccc1ad31007edc76451b9",Ð
"reference": "2d6702ff215bf922936ccc1ad31007edc76451b9",Ð
"shasum": ""Ð },Ð "require": {Ð "ext-
fileinfo": "*",Ð "php": "^7.4 || ^8.0"Ð },Ð
"require-dev": {Ð "friendsofphp/php-cs-fixer": "^3.2",Ð
"phpstan/phpstan": "^0.12.68",Ð "phpunit/
phpunit": "^8.5.8 || ^9.3 || ^10.0"Ð },Ð "time":
"2024-09-21T08:32:55+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "League\\MimeTypeDetection\\": "src"Ð
}Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "Frank de Jonge",Ð "email": "info@frankdejonge.nl"Ð
}Ð],Ð "description": "Mime-type
detection for Flysystem",Ð "support": {Ð "issues":
"https://github.com/thephpleague/mime-type-detection/issues",Ð
"source": "https://github.com/thephpleague/mime-type-detection/tree/1.16.0"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/frankdejonge",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/league/flysystem",Ð
"type": "tidelift"Ð

}Ð],Ð "install-path": "../league/mime-type-detection"Ð },Ð {Ð "name": "masterminds/html5",Ð "version": "2.9.0",Ð "version_normalized": "2.9.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/Masterminds/html5-php.git",Ð "reference": "f5ac2c0b0a2eefca70b2ce32a5809992227e75a6"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/Masterminds/html5-php/zipball/f5ac2c0b0a2eefca70b2ce32a5809992227e75a6",Ð "reference": "f5ac2c0b0a2eefca70b2ce32a5809992227e75a6",Ð "shasum": ""Ð },Ð "require": {Ð "ext-dom": "*",Ð "php": ">=5.3.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^4.8.35 || ^5.7.21 || ^6 || ^7 || ^8 || ^9"Ð },Ð "time": "2024-03-31T07:05:07+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.7-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Masterminds\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Matt Butcher",Ð "email": "technosophos@gmail.com"Ð },Ð {Ð "name": "Matt Farina",Ð "email": "matt@mattfarina.com"Ð },Ð {Ð "name": "Asmir Mustafic",Ð "email": "goetas@gmail.com"Ð }Ð],Ð "description": "An HTML5 parser and serializer.",Ð "homepage": "http://masterminds.github.io/html5-php",Ð "keywords": [Ð "HTML5",Ð "dom",Ð "html",Ð "parser",Ð "querypath",Ð "serializer",Ð "xml"Ð],Ð "support": {Ð "issues": "https://github.com/Masterminds/html5-php/issues",Ð "source": "https://github.com/Masterminds/html5-php/tree/2.9.0"Ð },Ð "install-path": "../masterminds/html5"Ð },Ð {Ð "name": "mockery/mockery",Ð "version": "1.6.12",Ð "version_normalized": "1.6.12.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/mockery/mockery.git",Ð "reference": "1f4efdd7d3beafe9807b08156dfcb176d18f1699"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/mockery/mockery/zipball/1f4efdd7d3beafe9807b08156dfcb176d18f1699",Ð "reference": "1f4efdd7d3beafe9807b08156dfcb176d18f1699",Ð "shasum": ""Ð },Ð "require": {Ð "hamcrest/hamcrest-php": "^2.0.1",Ð "lib-pcre": ">=7.0",Ð "php": ">=7.3"Ð },Ð "conflict": {Ð "phpunit/phpunit": "<8.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^8.5 || ^9.6.17",Ð "symplify/easy-coding-standard": "^12.1.14"Ð },Ð "time": "2024-05-16T03:13:13+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "library/helpers.php",Ð "library/Mockery.php"Ð],Ð "psr-4": {Ð "Mockery\\": "library/Mockery"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Pádraic Brady",Ð "email": "padraic.brady@gmail.com",Ð "homepage": "https://github.com/padraic",Ð "role": "Author"Ð },Ð {Ð

"name": "Dave Marshall",Ð
"email": "dave.marshall@atstsolutions.co.uk",Ð
"homepage": "https://davedevelopment.co.uk",Ð
"role": "Developer"Ð },Ð {Ð
"name": "Nathanael Esayeas",Ð "email": "nathanael.esayeas@protonmail.com",Ð "homepage": "https://github.com/ghostwriter",Ð "role": "Lead Developer"Ð
}Ð],Ð "description": "Mockery is a simple yet flexible PHP mock object framework",Ð "homepage": "https://github.com/mockery/mockery",Ð "keywords": [Ð
"BDD",Ð "TDD",Ð "library",Ð "mock",Ð
"mock objects",Ð "mockery",Ð
"stub",Ð "test",Ð "test double",Ð
"testing"Ð],Ð "support": {Ð "docs": "https://docs.mockery.io/",Ð "issues": "https://github.com/mockery/mockery/issues",Ð "rss": "https://github.com/mockery/mockery/releases.atom",Ð "security": "https://github.com/mockery/mockery/security/advisories",Ð "source": "https://github.com/mockery/mockery"Ð },Ð "install-path": "../mockery/mockery"Ð },Ð {Ð "name": "monolog/monolog",Ð
"version": "2.10.0",Ð "version_normalized": "2.10.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://github.com/Seldaek/monolog.git",Ð "reference": "5cf826f2991858b54d5c3809bee745560a1042a7"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/Seldaek/monolog/zipball/5cf826f2991858b54d5c3809bee745560a1042a7",Ð
"reference": "5cf826f2991858b54d5c3809bee745560a1042a7",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=7.2",Ð "psr/log": "^1.0.1 || ^2.0 || ^3.0"Ð },Ð "provide": {Ð "psr/log-implementation": "1.0.0 || 2.0.0 || 3.0.0"Ð },Ð "require-dev": {Ð "aws/aws-sdk-php": "^2.4.9 || ^3.0",Ð
"doctrine/couchdb": "~1.0@dev",Ð "elasticsearch/elasticsearch": "^7 || ^8",Ð "ext-json": "*",Ð "graylog2/gelf-php": "^1.4.2 || ^2@dev",Ð "guzzlehttp/guzzle": "^7.4",Ð
"guzzlehttp/psr7": "^2.2",Ð "mongodb/mongodb": "^1.8",Ð "php-amqplib/php-amqplib": "~2.4 || ^3",Ð
"phpspec/prophecy": "^1.15",Ð "phpstan/phpstan": "^1.10",Ð "phpunit/phpunit": "^8.5.38 || ^9.6.19",Ð
"predis/predis": "^1.1 || ^2.0",Ð "rollbar/rollbar": "^1.3 || ^2 || ^3",Ð "ruflin/elastica": "^7",Ð
"swiftmailer/swiftmailer": "^5.3|^6.0",Ð
"symfony/mailer": "^5.4 || ^6",Ð "symfony/mime": "^5.4 || ^6"Ð
},Ð "suggest": {Ð "aws/aws-sdk-php": "Allow sending log messages to AWS services like DynamoDB",Ð
"doctrine/couchdb": "Allow sending log messages to a CouchDB server",Ð
"elasticsearch/elasticsearch": "Allow sending log messages to an Elasticsearch server via official client",Ð "ext-amqp": "Allow sending log messages to an AMQP server (1.0+ required)",Ð
"ext-curl": "Required to send log messages using the IFTTTHandler, the LogglyHandler, the SendGridHandler, the SlackWebhookHandler or the TelegramBotHandler",Ð "ext-mbstring": "Allow to work properly with unicode symbols",Ð "ext-mongodb": "Allow sending log messages to a MongoDB server (via driver)",Ð "ext-openssl": "Required to send log messages using SSL",Ð "ext-sockets": "Allow sending log messages to a Syslog server (via UDP driver)",Ð
"graylog2/gelf-php": "Allow sending log messages to a GrayLog2 server",Ð "mongodb/mongodb": "Allow sending log messages to a MongoDB server (via library)",Ð "php-amqplib/php-amqplib": "Allow sending log messages to an AMQP server using php-amqplib",Ð

"rollbar/rollbar": "Allow sending log messages to Rollbar",Đ
"ruflin/elastica": "Allow sending log messages to an Elastic
Search server"Đ },Đ "time": "2024-11-12T12:43:37+00:00",Đ
"type": "library",Đ "extra": {Đ "branch-
alias": {Đ "dev-main": "2.x-dev"Đ }Đ
},Đ "installation-source": "dist",Đ
"autoload": {Đ "psr-4": {Đ "Monolog\\": "src/
Monolog"Đ }Đ },Đ "notification-url":
"https://packagist.org/downloads/",Đ "license": [Đ
"MIT"Đ],Đ "authors": [Đ {Đ
"name": "Jordi Boggiano",Đ "email":
"j.boggiano@seld.be",Đ "homepage": "https://seld.be"Đ
}Đ],Đ "description": "Sends your logs to
files, sockets, inboxes, databases and various web services",Đ
"homepage": "https://github.com/Seldaek/monolog",Đ "keywords": [Đ
"log",Đ "logging",Đ "psr-3"Đ
],Đ "support": {Đ "issues": "https://
github.com/Seldaek/monolog/issues",Đ "source": "https://
github.com/Seldaek/monolog/tree/2.10.0"Đ },Đ "funding": [Đ
{Đ "url": "https://github.com/Seldaek",Đ
"type": "github"Đ },Đ {Đ
"url": "https://tidelift.com/funding/github/packagist/
monolog/monolog",Đ "type": "tidelift"Đ }Đ
],Đ "install-path": "../monolog/monolog"Đ },Đ
{Đ "name": "myclabs/deep-copy",Đ "version":
"1.13.1",Đ "version_normalized": "1.13.1.0",Đ "source": {Đ
"type": "git",Đ "url": "https://github.com/
myclabs/DeepCopy.git",Đ "reference":
"1720ddd719e16cf0db4eb1c6eca108031636d46c"Đ },Đ "dist": {Đ
"type": "zip",Đ "url": "https://api.github.com/
repos/myclabs/DeepCopy/zipball/1720ddd719e16cf0db4eb1c6eca108031636d46c",Đ
"reference": "1720ddd719e16cf0db4eb1c6eca108031636d46c",Đ
"shasum": ""Đ },Đ "require": {Đ
"php": "^7.1 || ^8.0"Đ },Đ "conflict": {Đ
"doctrine/collections": "<1.6.8",Đ "doctrine/
common": "<2.13.3 || >=3 <3.2.2"Đ },Đ "require-dev": {Đ
"doctrine/collections": "^1.6.8",Đ "doctrine/
common": "^2.13.3 || ^3.2.2",Đ "phpspec/prophecy": "^1.10",Đ
"phpunit/phpunit": "^7.5.20 || ^8.5.23 || ^9.5.13"Đ
},Đ "time": "2025-04-29T12:36:36+00:00",Đ
"type": "library",Đ "installation-source": "dist",Đ
"autoload": {Đ "files": [Đ "src/DeepCopy/
deep_copy.php"Đ],Đ "psr-4": {Đ
"DeepCopy\\": "src/DeepCopy/"Đ }Đ },Đ
"notification-url": "https://packagist.org/downloads/",Đ "license":
[Đ "MIT"Đ],Đ "description": "Create deep
copies (clones) of your objects",Đ "keywords": [Đ
"clone",Đ "copy",Đ "duplicate",Đ
"object",Đ "object graph"Đ],Đ "support": {Đ
"issues": "https://github.com/myclabs/DeepCopy/issues",Đ
"source": "https://github.com/myclabs/DeepCopy/tree/1.13.1"Đ
},Đ "funding": [Đ {Đ
"url": "https://tidelift.com/funding/github/packagist/myclabs/deep-copy",Đ
"type": "tidelift"Đ }Đ],Đ
"install-path": "../myclabs/deep-copy"Đ },Đ {Đ
"name": "myclabs/php-enum",Đ "version": "1.8.5",Đ
"version_normalized": "1.8.5.0",Đ "source": {Đ
"type": "git",Đ "url": "https://github.com/
myclabs/php-enum.git",Đ

"reference": "e7be26966b7398204a234f8673fdad5ac6277802"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/myclabs/php-enum/zipball/e7be26966b7398204a234f8673fdad5ac6277802",Ð "reference": "e7be26966b7398204a234f8673fdad5ac6277802",Ð "shasum": ""Ð },Ð "require": {Ð "ext-json": "*",Ð "php": "^7.3 || ^8.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.5",Ð "squizlabs/php_codesniffer": "1.*",Ð "vimeo/psalm": "^4.6.2 || ^5.2"Ð },Ð "time": "2025-01-14T11:49:03+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "MyCLabs\\Enum\\": "src/"Ð },Ð "classmap": [Ð "stubs/Stringable.php"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "PHP Enum contributors",Ð "homepage": "https://github.com/myclabs/php-enum/graphs/contributors"Ð }Ð],Ð "description": "PHP Enum implementation",Ð "homepage": "https://github.com/myclabs/php-enum",Ð "keywords": [Ð "enum"Ð],Ð "support": {Ð "issues": "https://github.com/myclabs/php-enum/issues",Ð "source": "https://github.com/myclabs/php-enum/tree/1.8.5"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/mnapoli",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/myclabs/php-enum",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../myclabs/php-enum"Ð },Ð {Ð "name": "nesbot/carbon",Ð "version": "2.73.0",Ð "version_normalized": "2.73.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/CarbonPHP/carbon.git",Ð "reference": "9228ce90e1035ff2f0db84b40ec2e023ed802075"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/CarbonPHP/carbon/zipball/9228ce90e1035ff2f0db84b40ec2e023ed802075",Ð "reference": "9228ce90e1035ff2f0db84b40ec2e023ed802075",Ð "shasum": ""Ð },Ð "require": {Ð "carbonphp/carbon-doctrine-types": "*",Ð "ext-json": "*",Ð "php": "^7.1.8 || ^8.0",Ð "psr/clock": "^1.0",Ð "symfony/polyfill-mbstring": "^1.0",Ð "symfony/polyfill-php80": "^1.16",Ð "symfony/translation": "^3.4 || ^4.0 || ^5.0 || ^6.0"Ð },Ð "provide": {Ð "psr/clock-implementation": "1.0"Ð },Ð "require-dev": {Ð "doctrine/dbal": "^2.0 || ^3.1.4 || ^4.0",Ð "doctrine/orm": "^2.7 || ^3.0",Ð "friendsofphp/php-cs-fixer": "^3.0",Ð "kylekatarnls/multi-tester": "^2.0",Ð "ondrejmirtes/better-reflection": "<6",Ð "phpmd/phpmd": "^2.9",Ð "phpstan/extension-installer": "^1.0",Ð "phpstan/phpstan": "^0.12.99 || ^1.7.14",Ð "phpunit/php-file-iterator": "^2.0.5 || ^3.0.6",Ð "phpunit/phpunit": "^7.5.20 || ^8.5.26 || ^9.5.20",Ð "squizlabs/php_codesniffer": "^3.4"Ð },Ð "time": "2025-01-08T20:10:23+00:00",Ð "bin": [Ð "bin/carbon"Ð],Ð "type": "library",Ð "extra": {Ð "laravel": {Ð "providers": [Ð "Carbon\\Laravel\\ServiceProvider"Ð]Ð },Ð "phpstan": {Ð "includes": [Ð "extension.neon"Ð]Ð

},Ð "branch-alias": {Ð
"dev-2.x": "2.x-dev",Ð "dev-master":
"3.x-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "psr-4": {Ð
"Carbon\\": "src/Carbon/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Brian Nesbitt",Ð "email":
"brian@nesbot.com",Ð "homepage": "https://markido.com"Ð
},Ð {Ð "name": "kylekatarnls",Ð
"homepage": "https://github.com/kylekatarnls"Ð
}Ð],Ð "description": "An API extension
for DateTime that supports 281 different languages.",Ð "homepage":
"https://carbon.nesbot.com",Ð "keywords": [Ð "date",Ð
"datetime",Ð "time"Ð],Ð
"support": {Ð "docs": "https://carbon.nesbot.com/docs",Ð
"issues": "https://github.com/briannesbitt/Carbon/issues",Ð
"source": "https://github.com/briannesbitt/Carbon"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/sponsors/kylekatarnls",Ð "type":
"github"Ð },Ð {Ð "url":
"https://opencollective.com/Carbon#sponsor",Ð "type":
"opencollective"Ð },Ð {Ð "url":
"https://tidelift.com/subscription/pkg/packagist-nesbot-carbon?
utm_source=packagist-nesbot-carbon&utm_medium=referral&utm_campaign=readme",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../nesbot/carbon"Ð },Ð {Ð
"name": "nette/schema",Ð "version": "v1.3.2",Ð
"version_normalized": "1.3.2.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/nette/schema.git",Ð
"reference": "da801d52f0354f70a638673c4a0f04e16529431d"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/nette/schema/zipball/
da801d52f0354f70a638673c4a0f04e16529431d",Ð "reference":
"da801d52f0354f70a638673c4a0f04e16529431d",Ð "shasum": ""Ð
},Ð "require": {Ð "nette/utils": "^4.0",Ð
"php": "8.1 - 8.4"Ð },Ð "require-dev": {Ð
"nette/tester": "^2.5.2",Ð "phpstan/phpstan-
nette": "^1.0",Ð "tracy/tracy": "^2.8"Ð },Ð
"time": "2024-10-06T23:10:23+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master":
"1.3-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "classmap": [Ð
"src/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "BSD-3-Clause",Ð "GPL-2.0-only",Ð
"GPL-3.0-only"Ð],Ð "authors": [Ð
{Ð "name": "David Grudl",Ð
"homepage": "https://davidgrudl.com"Ð },Ð
{Ð "name": "Nette Community",Ð
"homepage": "https://nette.org/contributors"Ð
}Ð],Ð "description": "Ø=ÜÐ Nette Schema:
validating data structures against a given Schema.",Ð "homepage":
"https://nette.org",Ð "keywords": [Ð "config",Ð
"nette"Ð],Ð "support": {Ð
"issues": "https://github.com/nette/schema/issues",Ð "source":
"https://github.com/nette/schema/tree/v1.3.2"Ð },Ð
"install-path": "../nette/schema"Ð },Ð {Ð "name":
"nette/utils",Ð "version": "v4.0.6",Ð
"version_normalized": "4.0.6.0",Ð

"source": {Ð
"type": "git",Ð "url": "https://github.com/nette/utils.git",Ð
"reference": "ce708655043c7050eb050df361c5e313cf708309"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/nette/utils/zipball/
ce708655043c7050eb050df361c5e313cf708309",Ð "reference":
"ce708655043c7050eb050df361c5e313cf708309",Ð "shasum": ""Ð
},Ð "require": {Ð "php": "8.0 - 8.4"Ð
},Ð "conflict": {Ð "nette/finder": "<3",Ð
"nette/schema": "<1.2.2"Ð },Ð "require-
dev": {Ð "jetbrains/phpstorm-attributes": "dev-master",Ð
"nette/tester": "^2.5",Ð "phpstan/phpstan":
"^1.0",Ð "tracy/tracy": "^2.9"Ð },Ð
"suggest": {Ð "ext-gd": "to use Image",Ð "ext-
iconv": "to use Strings::webalize(), toAscii(), chr() and reverse()",Ð
"ext-intl": "to use Strings::webalize(), toAscii(),
normalize() and compare()",Ð "ext-json": "to use Nette\\Utils\
\Json",Ð "ext-mbstring": "to use Strings::lower() etc...",Ð
"ext-tokenizer": "to use Nette\\Utils\
\Reflection::getUseStatements()"Ð },Ð "time":
"2025-03-30T21:06:30+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master":
"4.0-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "classmap": [Ð
"src/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "BSD-3-Clause",Ð "GPL-2.0-only",Ð
"GPL-3.0-only"Ð],Ð "authors": [Ð
{Ð "name": "David Grudl",Ð
"homepage": "https://davidgrudl.com"Ð },Ð
{Ð "name": "Nette Community",Ð
"homepage": "https://nette.org/contributors"Ð
}Ð],Ð "description": "Ø=Þà Nette Utils:
lightweight utilities for string & array manipulation, image handling, safe
JSON encoding/decoding, validation, slug or strong password generating etc.",Ð
"homepage": "https://nette.org",Ð "keywords": [Ð
"array",Ð "core",Ð "datetime",Ð
"images",Ð "json",Ð "nette",Ð
"paginator",Ð "password",Ð
"slugify",Ð "string",Ð "unicode",Ð
"utf-8",Ð "utility",Ð "validation"Ð],Ð
"support": {Ð "issues": "https://github.com/nette/
utils/issues",Ð "source": "https://github.com/nette/utils/tree/
v4.0.6"Ð },Ð "install-path": "../nette/utils"Ð },Ð
{Ð "name": "nikic/php-parser",Ð "version":
"v5.4.0",Ð "version_normalized": "5.4.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
nikic/PHP-Parser.git",Ð "reference":
"447a020a1f875a434d62f2a401f53b82a396e494"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/nikic/PHP-Parser/zipball/447a020a1f875a434d62f2a401f53b82a396e494",Ð
"reference": "447a020a1f875a434d62f2a401f53b82a396e494",Ð
"shasum": ""Ð },Ð "require": {Ð
"ext-ctype": "*",Ð "ext-json": "*",Ð
"ext-tokenizer": "*",Ð "php": ">=7.4"Ð
},Ð "require-dev": {Ð "ircmaxell/php-
yacc": "^0.0.7",Ð "phpunit/phpunit": "^9.0"Ð },Ð
"time": "2024-12-30T11:07:19+00:00",Ð "bin": [Ð
"bin/php-parse"Ð],Ð "type": "library",Ð
"extra": {Ð

"branch-alias": {Ð
"dev-master": "5.0-dev"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "PhpParser\\": "lib/PhpParser"Ð }Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "BSD-3-Clause"Ð
],Ð "authors": [Ð {Ð
"name": "Nikita Popov"Ð }Ð],Ð
"description": "A PHP parser written in PHP",Ð "keywords": [Ð
"parser",Ð "php"Ð],Ð
"support": {Ð "issues": "https://github.com/nikic/PHP-Parser/
issues",Ð "source": "https://github.com/nikic/PHP-Parser/tree/
v5.4.0"Ð },Ð "install-path": "../nikic/php-parser"Ð
},Ð {Ð "name": "nunomaduro/collision",Ð
"version": "v6.4.0",Ð "version_normalized": "6.4.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://
github.com/nunomaduro/collision.git",Ð "reference":
"f05978827b9343cba381ca05b8c7deee346b6015"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/nunomaduro/collision/zipball/f05978827b9343cba381ca05b8c7deee346b6015",Ð
"reference": "f05978827b9343cba381ca05b8c7deee346b6015",Ð
"shasum": ""Ð },Ð "require": {Ð
"filp/whoops": "^2.14.5",Ð "php": "^8.0.0",Ð
"symfony/console": "^6.0.2"Ð },Ð "require-
dev": {Ð "brianium/paratest": "^6.4.1",Ð "laravel/
framework": "^9.26.1",Ð "laravel/pint": "^1.1.1",Ð
"nunomaduro/larastan": "^1.0.3",Ð "nunomaduro/
mock-final-classes": "^1.1.0",Ð "orchestra/testbench": "^7.7",Ð
"phpunit/phpunit": "^9.5.23",Ð "spatie/
ignition": "^1.4.1"Ð },Ð "time":
"2023-01-03T12:54:54+00:00",Ð "type": "library",Ð
"extra": {Ð "laravel": {Ð "providers": [Ð
"NunoMaduro\\Collision\\Adapters\\Laravel\
\CollisionServiceProvider"Ð]Ð },Ð
"branch-alias": {Ð "dev-develop": "6.x-dev"Ð
}Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"NunoMaduro\\Collision\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Nuno Maduro",Ð "email":
"enunomaduro@gmail.com"Ð }Ð],Ð
"description": "Cli error handling for console/command-line PHP
applications.",Ð "keywords": [Ð "artisan",Ð
"cli",Ð "command-line",Ð
"console",Ð "error",Ð "handling",Ð
"laravel",Ð "laravel-zero",Ð "php",Ð
"symfony"Ð],Ð "support": {Ð
"issues": "https://github.com/nunomaduro/collision/issues",Ð
"source": "https://github.com/nunomaduro/collision"Ð
},Ð "funding": [Ð {Ð
"url": "https://www.paypal.com/paypalme/enunomaduro",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/nunomaduro",Ð "type": "github"Ð
},Ð {Ð "url": "https://
www.patreon.com/nunomaduro",Ð "type": "patreon"Ð
}Ð],Ð "install-path": "../nunomaduro/
collision"Ð },Ð {Ð "name": "nunomaduro/termwind",Ð
"version": "v1.17.0",Ð "version_normalized": "1.17.0.0",Ð
"source": {Ð

"type": "git",Ð "url": "https://github.com/nunomaduro/termwind.git",Ð "reference": "5369ef84d8142c1d87e4ec278711d4ece3cbf301"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/nunomaduro/termwind/zipball/5369ef84d8142c1d87e4ec278711d4ece3cbf301",Ð "reference": "5369ef84d8142c1d87e4ec278711d4ece3cbf301",Ð "shasum": ""Ð },Ð "require": {Ð "ext-mbstring": "*",Ð "php": "^8.1",Ð "symfony/console": "^6.4.15"Ð },Ð "require-dev": {Ð "illuminate/console": "^10.48.24",Ð "illuminate/support": "^10.48.24",Ð "laravel/pint": "^1.18.2",Ð "pestphp/pest": "^2.36.0",Ð "pestphp/pest-plugin-mock": "2.0.0",Ð "phpstan/phpstan": "^1.12.11",Ð "phpstan/phpstan-strict-rules": "^1.6.1",Ð "symfony/var-dumper": "^6.4.15",Ð "thecodingmachine/phpstan-strict-rules": "^1.0.0"Ð },Ð "time": "2024-11-21T10:36:35+00:00",Ð "type": "library",Ð "extra": {Ð "laravel": {Ð "providers": [Ð "Termwind\\Laravel\\TermwindServiceProvider"Ð]Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "src/Functions.php"Ð],Ð "psr-4": {Ð "Termwind\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nuno Maduro",Ð "email": "enunomaduro@gmail.com"Ð }Ð],Ð "description": "Its like Tailwind CSS, but for the console.",Ð "keywords": [Ð "cli",Ð "console",Ð "css",Ð "package",Ð "php",Ð "style"Ð],Ð "support": {Ð "issues": "https://github.com/nunomaduro/termwind/issues",Ð "source": "https://github.com/nunomaduro/termwind/tree/v1.17.0"Ð },Ð "funding": [Ð {Ð "url": "https://www.paypal.com/paypalme/enunomaduro",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/nunomaduro",Ð "type": "github"Ð },Ð {Ð "url": "https://github.com/xiCO2k",Ð "type": "github"Ð }Ð],Ð "install-path": "../nunomaduro/termwind"Ð },Ð {Ð "name": "phar-io/manifest",Ð "version": "2.0.4",Ð "version_normalized": "2.0.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/phar-io/manifest.git",Ð "reference": "54750ef60c58e43759730615a392c31c80e23176"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/phar-io/manifest/zipball/54750ef60c58e43759730615a392c31c80e23176",Ð "reference": "54750ef60c58e43759730615a392c31c80e23176",Ð "shasum": ""Ð },Ð "require": {Ð "ext-dom": "*",Ð "ext-libxml": "*",Ð "ext-phar": "*",Ð "ext-xmlwriter": "*",Ð "phar-io/version": "^3.0.1",Ð "php": "^7.2 || ^8.0"Ð },Ð "time": "2024-03-03T12:33:53+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.0.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð

"BSD-3-Clause"Ð],Ð "authors": [Ð
{Ð "name": "Arne Blankerts",Ð
"email": "arne@blankerts.de",Ð "role":
"Developer"Ð },Ð {Ð "name":
"Sebastian Heuer",Ð "email": "sebastian@phpeople.de",Ð
"role": "Developer"Ð },Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "Developer"Ð
}Ð],Ð "description": "Component for
reading phar.io manifest information from a PHP Archive (PHAR)",Ð
"support": {Ð "issues": "https://github.com/phar-io/manifest/
issues",Ð "source": "https://github.com/phar-io/manifest/
tree/2.0.4"Ð },Ð "funding": [Ð {Ð
"url": "https://github.com/theseer",Ð
"type": "github"Ð }Ð],Ð "install-path":
"../phar-io/manifest"Ð },Ð {Ð "name": "phar-io/version",Ð
"version": "3.2.1",Ð "version_normalized": "3.2.1.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/phar-io/version.git",Ð "reference":
"4f7fd7836c6f332bb2933569e566a0d6c4cbed74"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/phar-io/version/zipball/4f7fd7836c6f332bb2933569e566a0d6c4cbed74",Ð
"reference": "4f7fd7836c6f332bb2933569e566a0d6c4cbed74",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.2 || ^8.0"Ð },Ð "time":
"2022-02-21T01:04:05+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"classmap": [Ð "src/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "BSD-3-Clause"Ð],Ð
"authors": [Ð {Ð "name": "Arne
Blankerts",Ð "email": "arne@blankerts.de",Ð
"role": "Developer"Ð },Ð {Ð
"name": "Sebastian Heuer",Ð "email":
"sebastian@phpeople.de",Ð "role": "Developer"Ð
},Ð {Ð "name": "Sebastian
Bergmann",Ð "email": "sebastian@phpunit.de",Ð
"role": "Developer"Ð }Ð],Ð
"description": "Library for handling version information and
constraints",Ð "support": {Ð "issues": "https://
github.com/phar-io/version/issues",Ð "source": "https://
github.com/phar-io/version/tree/3.2.1"Ð },Ð "install-
path": "../phar-io/version"Ð },Ð {Ð "name": "phenx/php-
font-lib",Ð "version": "0.5.6",Ð "version_normalized":
"0.5.6.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/dompdf/php-font-lib.git",Ð
"reference": "a1681e9793040740a405ac5b189275059e2a9863"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/dompdf/php-font-lib/
zipball/a1681e9793040740a405ac5b189275059e2a9863",Ð
"reference": "a1681e9793040740a405ac5b189275059e2a9863",Ð
"shasum": ""Ð },Ð "require": {Ð "ext-
mbstring": "*"Ð },Ð "require-dev": {Ð
"symfony/phpunit-bridge": "^3 || ^4 || ^5 || ^6"Ð },Ð
"time": "2024-01-29T14:45:26+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "FontLib\\": "src/FontLib"Ð }Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "LGPL-2.1-or-later"Ð
],Ð

"authors": [Ð {Ð
"name": "Fabien Ménager",Ð "email":
"fabien.menager@gmail.com"Ð }Ð],Ð
"description": "A library to read, parse, export and make subsets of
different types of font files.",Ð "homepage": "https://github.com/
PhenX/php-font-lib",Ð "support": {Ð "issues":
"https://github.com/dompdf/php-font-lib/issues",Ð "source":
"https://github.com/dompdf/php-font-lib/tree/0.5.6"Ð },Ð
"install-path": "../phenx/php-font-lib"Ð },Ð {Ð "name":
"phenx/php-svg-lib",Ð "version": "0.4.1",Ð
"version_normalized": "0.4.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/dompdf/php-svg-
lib.git",Ð "reference":
"4498b5df7b08e8469f0f8279651ea5de9626ed02"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/dompdf/php-svg-lib/zipball/4498b5df7b08e8469f0f8279651ea5de9626ed02",Ð
"reference": "4498b5df7b08e8469f0f8279651ea5de9626ed02",Ð
"shasum": ""Ð },Ð "require": {Ð
"ext-mbstring": "*",Ð "php": "^7.1 || ^7.2 ||
^7.3 || ^7.4 || ^8.0",Ð "sabberworm/php-css-parser": "^8.4"Ð
},Ð "require-dev": {Ð "phpunit/phpunit":
"^7.5 || ^8.5 || ^9.5"Ð },Ð "time":
"2022-03-07T12:52:04+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Svg\\": "src/Svg"Ð }Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "LGPL-3.0"Ð],Ð
"authors": [Ð {Ð "name": "Fabien
Ménager",Ð "email": "fabien.menager@gmail.com"Ð
}Ð],Ð "description": "A library to read,
parse and export to PDF SVG files.",Ð "homepage": "https://
github.com/PhenX/php-svg-lib",Ð "support": {Ð
"issues": "https://github.com/dompdf/php-svg-lib/issues",Ð
"source": "https://github.com/dompdf/php-svg-lib/tree/0.4.1"Ð },Ð
"install-path": "../phenx/php-svg-lib"Ð },Ð {Ð
"name": "phpoption/phpoption",Ð "version": "1.9.3",Ð
"version_normalized": "1.9.3.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
schmittjoh/php-option.git",Ð "reference":
"e3fac8b24f56113f7cb96af14958c0dd16330f54"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/schmittjoh/php-option/zipball/e3fac8b24f56113f7cb96af14958c0dd16330f54",Ð
"reference": "e3fac8b24f56113f7cb96af14958c0dd16330f54",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.2.5 || ^8.0"Ð },Ð "require-
dev": {Ð "bamarni/composer-bin-plugin": "^1.8.2",Ð
"phpunit/phpunit": "^8.5.39 || ^9.6.20 || ^10.5.28"Ð
},Ð "time": "2024-07-20T21:41:07+00:00",Ð
"type": "library",Ð "extra": {Ð "bamarni-bin": {Ð
"bin-links": true,Ð "forward-command":
falseÐ },Ð "branch-alias": {Ð
"dev-master": "1.9-dev"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "PhpOption\\": "src/PhpOption/"Ð }Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "Apache-2.0"Ð],Ð
"authors": [Ð {Ð "name":
"Johannes M. Schmitt",Ð "email": "schmittjoh@gmail.com",Ð
"homepage": "https://github.com/schmittjoh"Ð
},Ð

{Ð "name": "Graham Campbell",Ð "email": "hello@gjcampbell.co.uk",Ð "homepage": "https://github.com/GrahamCampbell"Ð }Ð],Ð "description": "Option Type for PHP",Ð "keywords": [Ð "language",Ð "option",Ð "php",Ð "type"Ð],Ð "support": {Ð "issues": "https://github.com/schmittjoh/php-option/issues",Ð "source": "https://github.com/schmittjoh/php-option/tree/1.9.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/GrahamCampbell",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/phpoption/phpoption",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../phpoption/phpoption"Ð },Ð {Ð "name": "phpunit/php-code-coverage",Ð "version": "9.2.32",Ð "version_normalized": "9.2.32.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/php-code-coverage.git",Ð "reference": "85402a822d1ecf1db1096959413d35e1c37cf1a5"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/php-code-coverage/zipball/85402a822d1ecf1db1096959413d35e1c37cf1a5",Ð "reference": "85402a822d1ecf1db1096959413d35e1c37cf1a5",Ð "shasum": ""Ð },Ð "require": {Ð "ext-dom": "*",Ð "ext-libxml": "*",Ð "ext-xmlwriter": "*",Ð "nikic/php-parser": "^4.19.1 || ^5.1.0",Ð "php": ">=7.3",Ð "phpunit/php-file-iterator": "^3.0.6",Ð "phpunit/php-text-template": "^2.0.4",Ð "sebastian/code-unit-reverse-lookup": "^2.0.3",Ð "sebastian/complexity": "^2.0.3",Ð "sebastian/environment": "^5.1.5",Ð "sebastian/lines-of-code": "^1.0.4",Ð "sebastian/version": "^3.0.2",Ð "theseer/tokenizer": "^1.2.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.6"Ð },Ð "suggest": {Ð "ext-pcov": "PHP extension that provides line coverage",Ð "ext-xdebug": "PHP extension that provides line coverage as well as branch and path coverage"Ð },Ð "time": "2024-08-22T04:23:01+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "9.2.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "lead"Ð }Ð],Ð "description": "Library that provides collection, processing, and rendering functionality for PHP code coverage information.",Ð "homepage": "https://github.com/sebastianbergmann/php-code-coverage",Ð "keywords": [Ð "coverage",Ð "testing",Ð "xunit"Ð],Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/php-code-coverage/issues",Ð "security": "https://github.com/sebastianbergmann/php-code-coverage/security/policy",Ð "source": "https://github.com/sebastianbergmann/php-code-coverage/tree/9.2.32"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../phpunit/php-code-coverage"Ð },Ð {Ð "name": "phpunit/php-file-iterator",Ð

"version": "3.0.6",Ð
"version_normalized": "3.0.6.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/sebastianbergmann/
php-file-iterator.git",Ð "reference":
"cf1c2e7c203ac650e352f4cc675a7021e7d1b3cf"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/php-file-iterator/zipball/
cf1c2e7c203ac650e352f4cc675a7021e7d1b3cf",Ð "reference":
"cf1c2e7c203ac650e352f4cc675a7021e7d1b3cf",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=7.3"Ð
},Ð "require-dev": {Ð "phpunit/phpunit":
"^9.3"Ð },Ð "time": "2021-12-02T12:48:52+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "3.0-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "FilterIterator implementation that
filters files based on a list of suffixes.",Ð "homepage": "https://
github.com/sebastianbergmann/php-file-iterator/",Ð "keywords": [Ð
"filesystem",Ð "iterator"Ð],Ð
"support": {Ð "issues": "https://github.com/
sebastianbergmann/php-file-iterator/issues",Ð "source":
"https://github.com/sebastianbergmann/php-file-iterator/tree/3.0.6"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/sebastianbergmann",Ð "type":
"github"Ð }Ð],Ð "install-path": "../
phpunit/php-file-iterator"Ð },Ð {Ð "name": "phpunit/php-
invoker",Ð "version": "3.1.1",Ð "version_normalized":
"3.1.1.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/sebastianbergmann/php-invoker.git",Ð
"reference": "5a10147d0aaf65b58940a0b72f71c9ac0423cc67"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/sebastianbergmann/php-
invoker/zipball/5a10147d0aaf65b58940a0b72f71c9ac0423cc67",Ð
"reference": "5a10147d0aaf65b58940a0b72f71c9ac0423cc67",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "ext-pcntl":
"*",Ð "phpunit/phpunit": "^9.3"Ð },Ð
"suggest": {Ð "ext-pcntl": "*"Ð },Ð "time":
"2020-09-28T05:58:55+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master":
"3.1-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "classmap": [Ð
"src/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "BSD-3-Clause"Ð],Ð "authors": [Ð
{Ð "name": "Sebastian Bergmann",Ð
"email": "sebastian@phpunit.de",Ð
"role": "lead"Ð }Ð],Ð "description":
"Invoke callables with a timeout",Ð "homepage": "https://github.com/
sebastianbergmann/php-invoker/",Ð "keywords": [Ð
"process"Ð],Ð "support": {Ð "issues":
"https://github.com/sebastianbergmann/php-invoker/issues",Ð
"source": "https://github.com/sebastianbergmann/php-invoker/tree/3.1.1"Ð
},Ð

"funding": [Ð {Ð
"url": "https://github.com/sebastianbergmann",Ð "type":
"github"Ð }Ð],Ð "install-path": "../
phpunit/php-invoker"Ð },Ð {Ð "name": "phpunit/php-text-
template",Ð "version": "2.0.4",Ð "version_normalized":
"2.0.4.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/sebastianbergmann/php-text-
template.git",Ð "reference":
"5da5f67fc95621df9ff4c4e5a84d6a8a2acf7c28"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/php-text-template/
zipball/5da5f67fc95621df9ff4c4e5a84d6a8a2acf7c28",Ð
"reference": "5da5f67fc95621df9ff4c4e5a84d6a8a2acf7c28",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "phpunit/
phpunit": "^9.3"Ð },Ð "time": "2020-10-26T05:33:50+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "2.0-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "Simple template engine.",Ð
"homepage": "https://github.com/sebastianbergmann/php-text-
template/",Ð "keywords": [Ð "template"Ð],Ð
"support": {Ð "issues": "https://github.com/
sebastianbergmann/php-text-template/issues",Ð "source":
"https://github.com/sebastianbergmann/php-text-template/tree/2.0.4"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/sebastianbergmann",Ð "type":
"github"Ð }Ð],Ð "install-path": "../
phpunit/php-text-template"Ð },Ð {Ð "name": "phpunit/php-
timer",Ð "version": "5.0.3",Ð "version_normalized":
"5.0.3.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/sebastianbergmann/php-timer.git",Ð
"reference": "5a63ce20ed1b5bf577850e2c4e87f4aa902afbd2"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/sebastianbergmann/php-
timer/zipball/5a63ce20ed1b5bf577850e2c4e87f4aa902afbd2",Ð
"reference": "5a63ce20ed1b5bf577850e2c4e87f4aa902afbd2",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "phpunit/
phpunit": "^9.3"Ð },Ð "time": "2020-10-26T13:16:10+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "5.0-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "Utility class for timing",Ð
"homepage": "https://github.com/sebastianbergmann/php-timer/",Ð
"keywords": [Ð "timer"Ð],Ð
"support": {Ð "issues": "https://github.com/sebastianbergmann/
php-timer/issues",Ð

"source": "https://github.com/sebastianbergmann/php-timer/tree/5.0.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../phpunit/php-timer"Ð },Ð {Ð "name": "phpunit/phpunit",Ð "version": "9.6.22",Ð "version_normalized": "9.6.22.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/phpunit.git",Ð "reference": "f80235cb4d3caa59ae09be3adf1ded27521d1a9c"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/phpunit/zipball/f80235cb4d3caa59ae09be3adf1ded27521d1a9c",Ð "reference": "f80235cb4d3caa59ae09be3adf1ded27521d1a9c",Ð "shasum": ""Ð },Ð "require": {Ð "doctrine/instantiator": "^1.5.0 || ^2",Ð "ext-dom": "*",Ð "ext-json": "*",Ð "ext-libxml": "*",Ð "ext-mbstring": "*",Ð "ext-xml": "*",Ð "ext-xmlwriter": "*",Ð "myclabs/deep-copy": "^1.12.1",Ð "phar-io/manifest": "^2.0.4",Ð "phar-io/version": "^3.2.1",Ð "php": ">=7.3",Ð "phpunit/php-code-coverage": "^9.2.32",Ð "phpunit/php-file-iterator": "^3.0.6",Ð "phpunit/php-invoker": "^3.1.1",Ð "phpunit/php-text-template": "^2.0.4",Ð "phpunit/php-timer": "^5.0.3",Ð "sebastian/cli-parser": "^1.0.2",Ð "sebastian/code-unit": "^1.0.8",Ð "sebastian/comparator": "^4.0.8",Ð "sebastian/diff": "^4.0.6",Ð "sebastian/environment": "^5.1.5",Ð "sebastian/exporter": "^4.0.6",Ð "sebastian/global-state": "^5.0.7",Ð "sebastian/object-enumerator": "^4.0.4",Ð "sebastian/resource-operations": "^3.0.4",Ð "sebastian/type": "^3.2.1",Ð "sebastian/version": "^3.0.2"Ð },Ð "suggest": {Ð "ext-soap": "To be able to generate mocks based on WSDL files",Ð "ext-xdebug": "PHP extension that provides line coverage as well as branch and path coverage"Ð },Ð "time": "2024-12-05T13:48:26+00:00",Ð "bin": [Ð "phpunit"Ð],Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "9.6-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "src/Framework/Assert/Functions.php"Ð],Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "lead"Ð }Ð],Ð "description": "The PHP Unit Testing framework.",Ð "homepage": "https://phpunit.de/",Ð "keywords": [Ð "phpunit",Ð "testing",Ð "xunit"Ð],Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/phpunit/issues",Ð "security": "https://github.com/sebastianbergmann/phpunit/security/policy",Ð "source": "https://github.com/sebastianbergmann/phpunit/tree/9.6.22"Ð },Ð "funding": [Ð {Ð "url": "https://phpunit.de/sponsors.html",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/phpunit/phpunit",Ð

"type": "tidelift"Ð
}Ð],Ð "install-path": "../phpunit/
phpunit"Ð },Ð {Ð "name": "psr/cache",Ð
"version": "3.0.0",Ð "version_normalized": "3.0.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://
github.com/php-fig/cache.git",Ð "reference":
"aa5030cfa5405eccfdcb1083ce040c2cb8d253bf"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/php-fig/cache/zipball/aa5030cfa5405eccfdcb1083ce040c2cb8d253bf",Ð
"reference": "aa5030cfa5405eccfdcb1083ce040c2cb8d253bf",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.0.0"Ð },Ð "time":
"2021-02-03T23:26:27+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master":
"1.0.x-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "psr-4": {Ð
"Psr\\Cache\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "PHP-FIG",Ð "homepage":
"https://www.php-fig.org/"Ð }Ð],Ð
"description": "Common interface for caching libraries",Ð
"keywords": [Ð "cache",Ð "psr",Ð
"psr-6"Ð],Ð "support": {Ð "source":
"https://github.com/php-fig/cache/tree/3.0.0"Ð },Ð
"install-path": "../psr/cache"Ð },Ð {Ð "name": "psr/
clock",Ð "version": "1.0.0",Ð "version_normalized":
"1.0.0.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/php-fig/clock.git",Ð
"reference": "e41a24703d4560fd0acb709162f73b8adfc3aa0d"Ð },Ð
"dist": {Ð "type": "zip",Ð "url":
"https://api.github.com/repos/php-fig/clock/zipball/
e41a24703d4560fd0acb709162f73b8adfc3aa0d",Ð "reference":
"e41a24703d4560fd0acb709162f73b8adfc3aa0d",Ð "shasum": ""Ð
},Ð "require": {Ð "php": "^7.0 || ^8.0"Ð
},Ð "time": "2022-11-25T14:36:26+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Psr\\Clock\\":
"src/"Ð }Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "PHP-FIG",Ð "homepage": "https://www.php-fig.org/"Ð
}Ð],Ð "description": "Common interface
for reading the clock.",Ð "homepage": "https://github.com/php-fig/
clock",Ð "keywords": [Ð "clock",Ð "now",Ð
"psr",Ð "psr-20",Ð "time"Ð
],Ð "support": {Ð "issues": "https://
github.com/php-fig/clock/issues",Ð "source": "https://
github.com/php-fig/clock/tree/1.0.0"Ð },Ð "install-path":
"../psr/clock"Ð },Ð {Ð "name": "psr/container",Ð
"version": "2.0.2",Ð "version_normalized": "2.0.2.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/php-fig/container.git",Ð "reference":
"c71ecc56dfe541dbd90c5360474fbc405f8d5963"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/php-fig/container/zipball/c71ecc56dfe541dbd90c5360474fbc405f8d5963",Ð
"reference": "c71ecc56dfe541dbd90c5360474fbc405f8d5963",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=7.4.0"Ð },Ð "time":
"2021-11-05T16:47:00+00:00",Ð

"type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master":
"2.0.x-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "psr-4": {Ð
"Psr\\Container\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "PHP-FIG",Ð "homepage":
"https://www.php-fig.org/"Ð }Ð],Ð
"description": "Common Container Interface (PHP FIG PSR-11)",Ð
"homepage": "https://github.com/php-fig/container",Ð "keywords": [Ð
"PSR-11",Ð "container",Ð
"container-interface",Ð "container-interop",Ð
"psr"Ð],Ð "support": {Ð "issues": "https://
github.com/php-fig/container/issues",Ð "source": "https://
github.com/php-fig/container/tree/2.0.2"Ð },Ð "install-
path": "../psr/container"Ð },Ð {Ð "name": "psr/event-
dispatcher",Ð "version": "1.0.0",Ð "version_normalized":
"1.0.0.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/php-fig/event-dispatcher.git",Ð
"reference": "dbefd12671e8a14ec7f180cab83036ed26714bb0"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/php-fig/event-dispatcher/
zipball/dbefd12671e8a14ec7f180cab83036ed26714bb0",Ð
"reference": "dbefd12671e8a14ec7f180cab83036ed26714bb0",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.2.0"Ð },Ð "time": "2019-01-08T18:20:26+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "1.0.x-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Psr\
\EventDispatcher\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "PHP-FIG",Ð "homepage": "http://
www.php-fig.org/"Ð }Ð],Ð "description":
"Standard interfaces for event handling.",Ð "keywords": [Ð
"events",Ð "psr",Ð "psr-14"Ð
],Ð "support": {Ð "issues": "https://
github.com/php-fig/event-dispatcher/issues",Ð "source":
"https://github.com/php-fig/event-dispatcher/tree/1.0.0"Ð },Ð
"install-path": "../psr/event-dispatcher"Ð },Ð {Ð
"name": "psr/http-client",Ð "version": "1.0.3",Ð
"version_normalized": "1.0.3.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/php-
fig/http-client.git",Ð "reference":
"bb5906edc1c324c9a05aa0873d40117941e5fa90"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/php-fig/http-client/zipball/bb5906edc1c324c9a05aa0873d40117941e5fa90",Ð
"reference": "bb5906edc1c324c9a05aa0873d40117941e5fa90",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^7.0 || ^8.0",Ð "psr/http-message":
"^1.0 || ^2.0"Ð },Ð "time": "2023-09-23T14:17:50+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "1.0.x-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Psr\\Http\\Client\
\": "src/"Ð }Ð },Ð "notification-url":
"https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð

```
                ],Ð           "authors": [Ð                {Ð
                   "name": "PHP-FIG",Ð                    "homepage":
"https://www.php-fig.org/"Ð                }Ð            ],Ð
"description": "Common interface for HTTP clients",Ð            "homepage":
"https://github.com/php-fig/http-client",Ð           "keywords": [Ð
                "http",Ð               "http-client",Ð               "psr",Ð
                "psr-18"Ð           ],Ð           "support": {Ð
"source": "https://github.com/php-fig/http-client"Ð            },Ð
"install-path": "../psr/http-client"Ð       },Ð       {Ð           "name":
"psr/http-factory",Ð           "version": "1.1.0",Ð
"version_normalized": "1.1.0.0",Ð           "source": {Ð
"type": "git",Ð               "url": "https://github.com/php-fig/http-
factory.git",Ð               "reference":
"2b4765fddfe3b508ac62f829e852b1501d3f6e8a"Ð            },Ð           "dist": {Ð
                "type": "zip",Ð               "url": "https://api.github.com/
repos/php-fig/http-factory/zipball/2b4765fddfe3b508ac62f829e852b1501d3f6e8a",Ð
                "reference": "2b4765fddfe3b508ac62f829e852b1501d3f6e8a",Ð
                "shasum": ""Ð           },Ð           "require": {Ð
                "php": ">=7.1",Ð               "psr/http-message": "^1.0 ||
^2.0"Ð           },Ð           "time": "2024-04-15T12:06:14+00:00",Ð
            "type": "library",Ð           "extra": {Ð               "branch-
alias": {Ð                   "dev-master": "1.0.x-dev"Ð               }Ð
            },Ð           "installation-source": "dist",Ð
"autoload": {Ð               "psr-4": {Ð                   "Psr\\Http\
\Message\\": "src/"Ð               }Ð           },Ð           "notification-
url": "https://packagist.org/downloads/",Ð           "license": [Ð
                "MIT"Ð           ],Ð           "authors": [Ð               {Ð
                   "name": "PHP-FIG",Ð                    "homepage":
"https://www.php-fig.org/"Ð                }Ð            ],Ð
"description": "PSR-17: Common interfaces for PSR-7 HTTP message factories",Ð
            "keywords": [Ð               "factory",Ð               "http",Ð
                "message",Ð               "psr",Ð               "psr-17",Ð
                "psr-7",Ð               "request",Ð               "response"Ð
            ],Ð           "support": {Ð               "source": "https://
github.com/php-fig/http-factory"Ð           },Ð           "install-path": "../
psr/http-factory"Ð       },Ð       {Ð           "name": "psr/http-message",Ð
            "version": "2.0",Ð           "version_normalized": "2.0.0.0",Ð
            "source": {Ð               "type": "git",Ð               "url":
"https://github.com/php-fig/http-message.git",Ð               "reference":
"402d35bcb92c70c026d1a6a9883f06b2ead23d71"Ð            },Ð           "dist": {Ð
                "type": "zip",Ð               "url": "https://api.github.com/
repos/php-fig/http-message/zipball/402d35bcb92c70c026d1a6a9883f06b2ead23d71",Ð
                "reference": "402d35bcb92c70c026d1a6a9883f06b2ead23d71",Ð
                "shasum": ""Ð           },Ð           "require": {Ð
                "php": "^7.2 || ^8.0"Ð           },Ð           "time":
"2023-04-04T09:54:51+00:00",Ð           "type": "library",Ð
"extra": {Ð               "branch-alias": {Ð               "dev-master":
"2.0.x-dev"Ð               }Ð           },Ð           "installation-source":
"dist",Ð           "autoload": {Ð               "psr-4": {Ð
"Psr\\Http\\Message\\": "src/"Ð               }Ð           },Ð
"notification-url": "https://packagist.org/downloads/",Ð           "license":
[Ð               "MIT"Ð           ],Ð           "authors": [Ð               {Ð
                   "name": "PHP-FIG",Ð                    "homepage":
"https://www.php-fig.org/"Ð                }Ð            ],Ð
"description": "Common interface for HTTP messages",Ð           "homepage":
"https://github.com/php-fig/http-message",Ð           "keywords": [Ð
                "http",Ð               "http-message",Ð               "psr",Ð
                "psr-7",Ð               "request",Ð               "response"Ð
            ],Ð           "support": {Ð               "source": "https://
github.com/php-fig/http-message/tree/2.0"Ð
```

},Ð "install-path": "../psr/http-message"Ð },Ð {Ð "name": "psr/log",Ð "version": "3.0.2",Ð "version_normalized": "3.0.2.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/php-fig/log.git",Ð "reference": "f16e1d5863e37f8d8c2a01719f5b34baa2b714d3"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/php-fig/log/zipball/f16e1d5863e37f8d8c2a01719f5b34baa2b714d3",Ð "reference": "f16e1d5863e37f8d8c2a01719f5b34baa2b714d3",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.0.0"Ð },Ð "time": "2024-09-11T13:17:53+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "3.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Psr\\Log\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "PHP-FIG",Ð "homepage": "https://www.php-fig.org/"Ð }Ð],Ð "description": "Common interface for logging libraries",Ð "homepage": "https://github.com/php-fig/log",Ð "keywords": [Ð "log",Ð "psr",Ð "psr-3"Ð],Ð "support": {Ð "source": "https://github.com/php-fig/log/tree/3.0.2"Ð },Ð "install-path": "../psr/log"Ð },Ð {Ð "name": "psr/simple-cache",Ð "version": "3.0.0",Ð "version_normalized": "3.0.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/php-fig/simple-cache.git",Ð "reference": "764e0b3939f5ca87cb904f570ef9be2d78a07865"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/php-fig/simple-cache/zipball/764e0b3939f5ca87cb904f570ef9be2d78a07865",Ð "reference": "764e0b3939f5ca87cb904f570ef9be2d78a07865",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.0.0"Ð },Ð "time": "2021-10-29T13:26:27+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "3.0.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Psr\\SimpleCache\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "PHP-FIG",Ð "homepage": "https://www.php-fig.org/"Ð }Ð],Ð "description": "Common interfaces for simple caching",Ð "keywords": [Ð "cache",Ð "caching",Ð "psr",Ð "psr-16",Ð "simple-cache"Ð],Ð "support": {Ð "source": "https://github.com/php-fig/simple-cache/tree/3.0.0"Ð },Ð "install-path": "../psr/simple-cache"Ð },Ð {Ð "name": "psy/psysh",Ð "version": "v0.12.8",Ð "version_normalized": "0.12.8.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/bobthecow/psysh.git",Ð "reference": "85057ceedee50c49d4f6ecaff73ee96adb3b3625"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/bobthecow/psysh/zipball/85057ceedee50c49d4f6ecaff73ee96adb3b3625",Ð "reference": "85057ceedee50c49d4f6ecaff73ee96adb3b3625",Ð "shasum": ""Ð },Ð "require": {Ð "ext-json": "*",Ð "ext-tokenizer": "*",Ð "nikic/php-parser": "^5.0 || ^4.0",Ð

"php": "^8.0 || ^7.4",Ð "symfony/console": "^7.0 || ^6.0 || ^5.0 || ^4.0 || ^3.4",Ð "symfony/var-dumper": "^7.0 || ^6.0 || ^5.0 || ^4.0 || ^3.4"Ð },Ð "conflict": {Ð "symfony/console": "4.4.37 || 5.3.14 || 5.3.15 || 5.4.3 || 5.4.4 || 6.0.3 || 6.0.4"Ð },Ð "require-dev": {Ð "bamarni/composer-bin-plugin": "^1.2"Ð },Ð "suggest": {Ð "ext-pcntl": "Enabling the PCNTL extension makes PsySH a lot happier :)",Ð "ext-pdo-sqlite": "The doc command requires SQLite to work.",Ð "ext-posix": "If you have PCNTL, you'll want the POSIX extension as well."Ð },Ð "time": "2025-03-16T03:05:19+00:00",Ð "bin": [Ð "bin/psysh"Ð],Ð "type": "library",Ð "extra": {Ð "bamarni-bin": {Ð "bin-links": false,Ð "forward-command": falseÐ },Ð "branch-alias": {Ð "dev-main": "0.12.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "src/functions.php"Ð],Ð "psr-4": {Ð "Psy\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Justin Hileman",Ð "email": "justin@justinhileman.info",Ð "homepage": "http://justinhileman.com"Ð }Ð],Ð "description": "An interactive shell for modern PHP.",Ð "homepage": "http://psysh.org",Ð "keywords": [Ð "REPL",Ð "console",Ð "interactive",Ð "shell"Ð],Ð "support": {Ð "issues": "https://github.com/bobthecow/psysh/issues",Ð "source": "https://github.com/bobthecow/psysh/tree/v0.12.8"Ð },Ð "install-path": "../psy/psysh"Ð },Ð {Ð "name": "ralouphie/getallheaders",Ð "version": "3.0.3",Ð "version_normalized": "3.0.3.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/ralouphie/getallheaders.git",Ð "reference": "120b605dfeb996808c31b6477290a714d356e822"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/ralouphie/getallheaders/zipball/120b605dfeb996808c31b6477290a714d356e822",Ð "reference": "120b605dfeb996808c31b6477290a714d356e822",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=5.6"Ð },Ð "require-dev": {Ð "php-coveralls/php-coveralls": "^2.1",Ð "phpunit/phpunit": "^5 || ^6.5"Ð },Ð "time": "2019-03-08T08:55:37+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "src/getallheaders.php"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Ralph Khattar",Ð "email": "ralph.khattar@gmail.com"Ð }Ð],Ð "description": "A polyfill for getallheaders.",Ð "support": {Ð "issues": "https://github.com/ralouphie/getallheaders/issues",Ð "source": "https://github.com/ralouphie/getallheaders/tree/develop"Ð },Ð "install-path": "../ralouphie/getallheaders"Ð },Ð {Ð "name": "ramsey/collection",Ð "version": "2.1.1",Ð "version_normalized": "2.1.1.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/ramsey/collection.git",Ð "reference": "344572933ad0181accbf4ba763e85a0306a8c5e2"Ð

},Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/ramsey/collection/zipball/344572933ad0181accbf4ba763e85a0306a8c5e2",Ð
"reference": "344572933ad0181accbf4ba763e85a0306a8c5e2",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": "^8.1"Ð },Ð "require-dev": {Ð
"captainhook/plugin-composer": "^5.3",Ð
"ergebnis/composer-normalize": "^2.45",Ð "fakerphp/faker": "^1.24",Ð "hamcrest/hamcrest-php": "^2.0",Ð
"jangregor/phpstan-prophecy": "^2.1",Ð "mockery/mockery": "^1.6",Ð "php-parallel-lint/php-console-highlighter": "^1.0",Ð
"php-parallel-lint/php-parallel-lint": "^1.4",Ð
"phpspec/prophecy-phpunit": "^2.3",Ð "phpstan/extension-installer": "^1.4",Ð "phpstan/phpstan": "^2.1",Ð
"phpstan/phpstan-mockery": "^2.0",Ð "phpstan/phpstan-phpunit": "^2.0",Ð "phpunit/phpunit": "^10.5",Ð "ramsey/coding-standard": "^2.3",Ð "ramsey/conventional-commits": "^1.6",Ð "roave/security-advisories": "dev-latest"Ð },Ð
"time": "2025-03-22T05:38:12+00:00",Ð "type": "library",Ð
"extra": {Ð "captainhook": {Ð
"force-install": trueÐ },Ð "ramsey/conventional-commits": {Ð "configFile": "conventional-commits.json"Ð
}Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"Ramsey\\Collection\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Ben Ramsey",Ð "email": "ben@benramsey.com",Ð "homepage": "https://benramsey.com"Ð
}Ð],Ð "description": "A PHP library for representing and manipulating collections.",Ð "keywords": [Ð
"array",Ð "collection",Ð "hash",Ð
"map",Ð "queue",Ð "set"Ð
],Ð "support": {Ð "issues": "https://github.com/ramsey/collection/issues",Ð "source": "https://github.com/ramsey/collection/tree/2.1.1"Ð },Ð "install-path": "../ramsey/collection"Ð },Ð {Ð "name": "ramsey/uuid",Ð "version": "4.7.6",Ð "version_normalized": "4.7.6.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/ramsey/uuid.git",Ð
"reference": "91039bc1faa45ba123c4328958e620d382ec7088"Ð },Ð
"dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/ramsey/uuid/zipball/91039bc1faa45ba123c4328958e620d382ec7088",Ð
"reference": "91039bc1faa45ba123c4328958e620d382ec7088",Ð
"shasum": ""Ð },Ð "require": {Ð "brick/math": "^0.8.8 || ^0.9 || ^0.10 || ^0.11 || ^0.12",Ð "ext-json": "*",Ð "php": "^8.0",Ð "ramsey/collection": "^1.2 || ^2.0"Ð },Ð "replace": {Ð "rhumsaa/uuid": "self.version"Ð },Ð "require-dev": {Ð
"captainhook/captainhook": "^5.10",Ð
"captainhook/plugin-composer": "^5.3",Ð "dealerdirect/phpcodesniffer-composer-installer": "^0.7.0",Ð "doctrine/annotations": "^1.8",Ð "ergebnis/composer-normalize": "^2.15",Ð
"mockery/mockery": "^1.3",Ð "paragonie/random-lib": "^2",Ð "php-mock/php-mock": "^2.2",Ð "php-mock/php-mock-mockery": "^1.3",Ð "php-parallel-lint/php-parallel-lint": "^1.1",Ð "phpbench/phpbench": "^1.0",Ð
"phpstan/extension-installer": "^1.1",Ð
"phpstan/phpstan": "^1.8",Ð

"phpstan/phpstan-mockery": "^1.1",Ð
"phpstan/phpstan-phpunit": "^1.1",Ð "phpunit/phpunit": "^8.5 || ^9",Ð "ramsey/composer-repl": "^1.4",Ð
"slevomat/coding-standard": "^8.4",Ð "squizlabs/php_codesniffer": "^3.5",Ð "vimeo/psalm": "^4.9"Ð },Ð
"suggest": {Ð "ext-bcmath": "Enables faster math with arbitrary-precision integers using BCMath.",Ð "ext-gmp": "Enables faster math with arbitrary-precision integers using GMP.",Ð
"ext-uuid": "Enables the use of PeclUuidTimeGenerator and PeclUuidRandomGenerator.",Ð "paragonie/random-lib": "Provides RandomLib for use with the RandomLibAdapter",Ð "ramsey/uuid-doctrine": "Allows the use of Ramsey\\Uuid\\Uuid as Doctrine field type."Ð
},Ð "time": "2024-04-27T21:32:50+00:00",Ð
"type": "library",Ð "extra": {Ð "captainhook": {Ð
"force-install": trueÐ }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "src/functions.php"Ð
],Ð "psr-4": {Ð "Ramsey\\Uuid\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð],Ð "description": "A PHP library for generating and working with universally unique identifiers (UUIDs).",Ð
"keywords": [Ð "guid",Ð "identifier",Ð
"uuid"Ð],Ð "support": {Ð
"issues": "https://github.com/ramsey/uuid/issues",Ð "source": "https://github.com/ramsey/uuid/tree/4.7.6"Ð },Ð
"funding": [Ð {Ð "url": "https://github.com/ramsey",Ð
"type": "github"Ð },Ð
{Ð "url": "https://tidelift.com/funding/github/packagist/ramsey/uuid",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../ramsey/uuid"Ð },Ð {Ð
"name": "sabberworm/php-css-parser",Ð "version": "v8.8.0",Ð "version_normalized": "8.8.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/MyIntervals/PHP-CSS-Parser.git",Ð "reference": "3de493bdddfd1f051249af725c7e0d2c38fed740"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/MyIntervals/PHP-CSS-Parser/zipball/3de493bdddfd1f051249af725c7e0d2c38fed740",Ð
"reference": "3de493bdddfd1f051249af725c7e0d2c38fed740",Ð
"shasum": ""Ð },Ð "require": {Ð "ext-iconv": "*",Ð "php": "^5.6.20 || ^7.0.0 || ~8.0.0 || ~8.1.0 || ~8.2.0 || ~8.3.0 || ~8.4.0"Ð },Ð "require-dev": {Ð
"phpunit/phpunit": "5.7.27 || 6.5.14 || 7.5.20 || 8.5.41"Ð
},Ð "suggest": {Ð "ext-mbstring": "for parsing UTF-8 CSS"Ð },Ð "time": "2025-03-23T17:59:05+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-main": "9.0.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð
"Sabberworm\\CSS\\": "src/"Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Raphael Schweikert"Ð },Ð
{Ð "name": "Oliver Klee",Ð
"email": "github@oliverklee.de"Ð },Ð
{Ð "name": "Jake Hotson",Ð
"email": "jake.github@qzdesign.co.uk"Ð }Ð
],Ð "description": "Parser for CSS Files written in PHP",Ð

"homepage": "https://www.sabberworm.com/blog/2010/6/10/php-
css-parser",Ð "keywords": [Ð "css",Ð
"parser",Ð "stylesheet"Ð],Ð "support": {Ð
"issues": "https://github.com/MyIntervals/PHP-CSS-Parser/
issues",Ð "source": "https://github.com/MyIntervals/PHP-CSS-
Parser/tree/v8.8.0"Ð },Ð "install-path": "../sabberworm/
php-css-parser"Ð },Ð {Ð "name": "sebastian/cli-parser",Ð
"version": "1.0.2",Ð "version_normalized": "1.0.2.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/sebastianbergmann/cli-parser.git",Ð
"reference": "2b56bea83a09de3ac06bb18b92f068e60cc6f50b"Ð },Ð
"dist": {Ð "type": "zip",Ð "url":
"https://api.github.com/repos/sebastianbergmann/cli-parser/
zipball/2b56bea83a09de3ac06bb18b92f068e60cc6f50b",Ð
"reference": "2b56bea83a09de3ac06bb18b92f068e60cc6f50b",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "phpunit/
phpunit": "^9.3"Ð },Ð "time": "2024-03-02T06:27:43+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "1.0-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "Library for parsing CLI options",Ð
"homepage": "https://github.com/sebastianbergmann/cli-parser",Ð
"support": {Ð "issues": "https://github.com/
sebastianbergmann/cli-parser/issues",Ð "source": "https://
github.com/sebastianbergmann/cli-parser/tree/1.0.2"Ð },Ð
"funding": [Ð {Ð "url": "https://github.com/
sebastianbergmann",Ð "type": "github"Ð }Ð
],Ð "install-path": "../sebastian/cli-parser"Ð },Ð
{Ð "name": "sebastian/code-unit",Ð "version":
"1.0.8",Ð "version_normalized": "1.0.8.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
sebastianbergmann/code-unit.git",Ð "reference":
"1fc9f64c0927627ef78ba436c9b17d967e68e120"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/code-unit/
zipball/1fc9f64c0927627ef78ba436c9b17d967e68e120",Ð
"reference": "1fc9f64c0927627ef78ba436c9b17d967e68e120",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "phpunit/
phpunit": "^9.3"Ð },Ð "time": "2020-10-26T13:08:54+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "1.0-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "Collection of value objects that
represent the PHP code units",Ð "homepage": "https://github.com/
sebastianbergmann/code-unit",Ð "support": {Ð
"issues": "https://github.com/sebastianbergmann/code-unit/issues",Ð

"source": "https://github.com/sebastianbergmann/code-unit/tree/1.0.8"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/code-unit"Ð },Ð {Ð "name": "sebastian/code-unit-reverse-lookup",Ð "version": "2.0.3",Ð "version_normalized": "2.0.3.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/code-unit-reverse-lookup.git",Ð "reference": "ac91f01ccec49fb77bdc6fd1e548bc70f7faa3e5"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/code-unit-reverse-lookup/zipball/ac91f01ccec49fb77bdc6fd1e548bc70f7faa3e5",Ð "reference": "ac91f01ccec49fb77bdc6fd1e548bc70f7faa3e5",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2020-09-28T05:30:19+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð }Ð],Ð "description": "Looks up which function or method a line of code belongs to",Ð "homepage": "https://github.com/sebastianbergmann/code-unit-reverse-lookup/",Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/code-unit-reverse-lookup/issues",Ð "source": "https://github.com/sebastianbergmann/code-unit-reverse-lookup/tree/2.0.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/code-unit-reverse-lookup"Ð },Ð {Ð "name": "sebastian/comparator",Ð "version": "4.0.8",Ð "version_normalized": "4.0.8.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/comparator.git",Ð "reference": "fa0f136dd2334583309d32b62544682ee972b51a"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/comparator/zipball/fa0f136dd2334583309d32b62544682ee972b51a",Ð "reference": "fa0f136dd2334583309d32b62544682ee972b51a",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.3",Ð "sebastian/diff": "^4.0",Ð "sebastian/exporter": "^4.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2022-09-14T12:41:17+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "4.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð },Ð {Ð "name": "Jeff Welch",Ð "email": "whatthejeff@gmail.com"Ð

},Ð {Ð
"name": "Volker Dusch",Ð "email":
"github@wallbash.com"Ð },Ð {Ð
"name": "Bernhard Schussek",Ð "email":
"bschussek@2bepublished.at"Ð }Ð],Ð
"description": "Provides the functionality to compare PHP values for
equality",Ð "homepage": "https://github.com/sebastianbergmann/
comparator",Ð "keywords": [Ð "comparator",Ð
"compare",Ð "equality"Ð],Ð
"support": {Ð "issues": "https://github.com/sebastianbergmann/
comparator/issues",Ð "source": "https://github.com/
sebastianbergmann/comparator/tree/4.0.8"Ð },Ð "funding": [Ð
{Ð "url": "https://github.com/
sebastianbergmann",Ð "type": "github"Ð }Ð
],Ð "install-path": "../sebastian/comparator"Ð },Ð
{Ð "name": "sebastian/complexity",Ð "version":
"2.0.3",Ð "version_normalized": "2.0.3.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
sebastianbergmann/complexity.git",Ð "reference":
"25f207c40d62b8b7aa32f5ab026c53561964053a"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/complexity/
zipball/25f207c40d62b8b7aa32f5ab026c53561964053a",Ð
"reference": "25f207c40d62b8b7aa32f5ab026c53561964053a",Ð
"shasum": ""Ð },Ð "require": {Ð "nikic/php-
parser": "^4.18 || ^5.0",Ð "php": ">=7.3"Ð },Ð
"require-dev": {Ð "phpunit/phpunit": "^9.3"Ð
},Ð "time": "2023-12-22T06:19:30+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-alias": {Ð
"dev-master": "2.0-dev"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"classmap": [Ð "src/"Ð]Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "BSD-3-Clause"Ð
],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de",Ð "role": "lead"Ð }Ð
],Ð "description": "Library for calculating the
complexity of PHP code units",Ð "homepage": "https://github.com/
sebastianbergmann/complexity",Ð "support": {Ð
"issues": "https://github.com/sebastianbergmann/complexity/issues",Ð
"source": "https://github.com/sebastianbergmann/complexity/
tree/2.0.3"Ð },Ð "funding": [Ð {Ð
"url": "https://github.com/sebastianbergmann",Ð
"type": "github"Ð }Ð],Ð
"install-path": "../sebastian/complexity"Ð },Ð {Ð
"name": "sebastian/diff",Ð "version": "4.0.6",Ð
"version_normalized": "4.0.6.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
sebastianbergmann/diff.git",Ð "reference":
"ba01945089c3a293b01ba9badc29ad55b106b0bc"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/diff/zipball/
ba01945089c3a293b01ba9badc29ad55b106b0bc",Ð "reference":
"ba01945089c3a293b01ba9badc29ad55b106b0bc",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=7.3"Ð
},Ð "require-dev": {Ð "phpunit/phpunit":
"^9.3",Ð "symfony/process": "^4.2 || ^5"Ð },Ð
"time": "2024-03-02T06:30:58+00:00",Ð "type": "library",Ð
"extra": {Ð

"branch-alias": {Ð
"dev-master": "4.0-dev"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"classmap": [Ð "src/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "BSD-3-Clause"Ð],Ð
"authors": [Ð {Ð "name":
"Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð
},Ð {Ð "name": "Kore
Nordmann",Ð "email": "mail@kore-nordmann.de"Ð
}Ð],Ð "description": "Diff
implementation",Ð "homepage": "https://github.com/sebastianbergmann/
diff",Ð "keywords": [Ð "diff",Ð "udiff",Ð
"unidiff",Ð "unified diff"Ð],Ð
"support": {Ð "issues": "https://github.com/
sebastianbergmann/diff/issues",Ð "source": "https://github.com/
sebastianbergmann/diff/tree/4.0.6"Ð },Ð "funding": [Ð
{Ð "url": "https://github.com/
sebastianbergmann",Ð "type": "github"Ð }Ð
],Ð "install-path": "../sebastian/diff"Ð },Ð
{Ð "name": "sebastian/environment",Ð "version":
"5.1.5",Ð "version_normalized": "5.1.5.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
sebastianbergmann/environment.git",Ð "reference":
"830c43a844f1f8d5b7a1f6d6076b784454d8b7ed"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/environment/
zipball/830c43a844f1f8d5b7a1f6d6076b784454d8b7ed",Ð
"reference": "830c43a844f1f8d5b7a1f6d6076b784454d8b7ed",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.3"Ð },Ð "require-dev": {Ð "phpunit/
phpunit": "^9.3"Ð },Ð "suggest": {Ð "ext-
posix": "*"Ð },Ð "time": "2023-02-03T06:03:51+00:00",Ð
"type": "library",Ð "extra": {Ð "branch-
alias": {Ð "dev-master": "5.1-dev"Ð }Ð
},Ð "installation-source": "dist",Ð
"autoload": {Ð "classmap": [Ð "src/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "BSD-3-
Clause"Ð],Ð "authors": [Ð {Ð
"name": "Sebastian Bergmann",Ð "email":
"sebastian@phpunit.de"Ð }Ð],Ð
"description": "Provides functionality to handle HHVM/PHP environments",Ð
"homepage": "http://www.github.com/sebastianbergmann/environment",Ð
"keywords": [Ð "Xdebug",Ð
"environment",Ð "hhvm"Ð],Ð "support": {Ð
"issues": "https://github.com/sebastianbergmann/environment/
issues",Ð "source": "https://github.com/sebastianbergmann/
environment/tree/5.1.5"Ð },Ð "funding": [Ð {Ð
"url": "https://github.com/sebastianbergmann",Ð
"type": "github"Ð }Ð],Ð
"install-path": "../sebastian/environment"Ð },Ð {Ð
"name": "sebastian/exporter",Ð "version": "4.0.6",Ð
"version_normalized": "4.0.6.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
sebastianbergmann/exporter.git",Ð "reference":
"78c00df8f170e02473b682df15bfcdacc3d32d72"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/sebastianbergmann/exporter/
zipball/78c00df8f170e02473b682df15bfcdacc3d32d72",Ð

"reference": "78c00df8f170e02473b682df15bfcdacc3d32d72",Đ
"shasum": ""Đ   },Đ   "require": {Đ   "php":
">=7.3",Đ   "sebastian/recursion-context": "^4.0"Đ   },Đ
            "require-dev": {Đ   "ext-mbstring": "*",Đ
                "phpunit/phpunit": "^9.3"Đ   },Đ   "time":
"2024-03-02T06:33:00+00:00",Đ   "type": "library",Đ
"extra": {Đ   "branch-alias": {Đ   "dev-master":
"4.0-dev"Đ   }Đ   },Đ   "installation-source":
"dist",Đ   "autoload": {Đ   "classmap": [Đ
                "src/"Đ   ]Đ   },Đ
"notification-url": "https://packagist.org/downloads/",Đ   "license":
[Đ   "BSD-3-Clause"Đ   ],Đ   "authors": [Đ
                {Đ   "name": "Sebastian Bergmann",Đ
                    "email": "sebastian@phpunit.de"Đ   },Đ
                {Đ   "name": "Jeff Welch",Đ
"email": "whatthejeff@gmail.com"Đ   },Đ   {Đ
                    "name": "Volker Dusch",Đ   "email":
"github@wallbash.com"Đ   },Đ   {Đ
"name": "Adam Harvey",Đ   "email": "aharvey@php.net"Đ
                },Đ   {Đ   "name": "Bernhard
Schussek",Đ   "email": "bschussek@gmail.com"Đ   }Đ
            ],Đ   "description": "Provides the functionality to
export PHP variables for visualization",Đ   "homepage": "https://
www.github.com/sebastianbergmann/exporter",Đ   "keywords": [Đ
                "export",Đ   "exporter"Đ   ],Đ
"support": {Đ   "issues": "https://github.com/sebastianbergmann/
exporter/issues",Đ   "source": "https://github.com/
sebastianbergmann/exporter/tree/4.0.6"Đ   },Đ   "funding": [Đ
                {Đ   "url": "https://github.com/
sebastianbergmann",Đ   "type": "github"Đ   }Đ
            ],Đ   "install-path": "../sebastian/exporter"Đ   },Đ
        {Đ   "name": "sebastian/global-state",Đ   "version":
"5.0.7",Đ   "version_normalized": "5.0.7.0",Đ   "source": {Đ
                "type": "git",Đ   "url": "https://github.com/
sebastianbergmann/global-state.git",Đ   "reference":
"bca7df1f32ee6fe93b4d4a9abbf69e13a4ada2c9"Đ   },Đ   "dist": {Đ
                "type": "zip",Đ   "url": "https://api.github.com/
repos/sebastianbergmann/global-state/zipball/
bca7df1f32ee6fe93b4d4a9abbf69e13a4ada2c9",Đ   "reference":
"bca7df1f32ee6fe93b4d4a9abbf69e13a4ada2c9",Đ   "shasum": ""Đ
            },Đ   "require": {Đ   "php": ">=7.3",Đ
                "sebastian/object-reflector": "^2.0",Đ
"sebastian/recursion-context": "^4.0"Đ   },Đ   "require-dev":
{Đ   "ext-dom": "*",Đ   "phpunit/phpunit": "^9.3"Đ
            },Đ   "suggest": {Đ   "ext-uopz": "*"Đ
            },Đ   "time": "2024-03-02T06:35:11+00:00",Đ
"type": "library",Đ   "extra": {Đ   "branch-alias": {Đ
                    "dev-master": "5.0-dev"Đ   }Đ   },Đ
            "installation-source": "dist",Đ   "autoload": {Đ
                "classmap": [Đ   "src/"Đ   ]Đ
            },Đ   "notification-url": "https://packagist.org/
downloads/",Đ   "license": [Đ   "BSD-3-Clause"Đ
            ],Đ   "authors": [Đ   {Đ
"name": "Sebastian Bergmann",Đ   "email":
"sebastian@phpunit.de"Đ   }Đ   ],Đ
"description": "Snapshotting of global state",Đ   "homepage": "http://
www.github.com/sebastianbergmann/global-state",Đ   "keywords": [Đ
                "global state"Đ   ],Đ   "support": {Đ
                "issues": "https://github.com/sebastianbergmann/global-state/
issues",Đ

"source": "https://github.com/sebastianbergmann/global-state/tree/5.0.7"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/global-state"Ð },Ð {Ð "name": "sebastian/lines-of-code",Ð "version": "1.0.4",Ð "version_normalized": "1.0.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/lines-of-code.git",Ð "reference": "e1e4a170560925c26d424b6a03aed157e7dcc5c5"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/lines-of-code/zipball/e1e4a170560925c26d424b6a03aed157e7dcc5c5",Ð "reference": "e1e4a170560925c26d424b6a03aed157e7dcc5c5",Ð "shasum": ""Ð },Ð "require": {Ð "nikic/php-parser": "^4.18 || ^5.0",Ð "php": ">=7.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2023-12-22T06:20:34+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "1.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "lead"Ð }Ð],Ð "description": "Library for counting the lines of code in PHP source code",Ð "homepage": "https://github.com/sebastianbergmann/lines-of-code",Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/lines-of-code/issues",Ð "source": "https://github.com/sebastianbergmann/lines-of-code/tree/1.0.4"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/lines-of-code"Ð },Ð {Ð "name": "sebastian/object-enumerator",Ð "version": "4.0.4",Ð "version_normalized": "4.0.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/object-enumerator.git",Ð "reference": "5c9eeac41b290a3712d88851518825ad78f45c71"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/object-enumerator/zipball/5c9eeac41b290a3712d88851518825ad78f45c71",Ð "reference": "5c9eeac41b290a3712d88851518825ad78f45c71",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.3",Ð "sebastian/object-reflector": "^2.0",Ð "sebastian/recursion-context": "^4.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2020-10-26T13:12:34+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "4.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð }Ð],Ð "description": "Traverses array structures and object graphs to enumerate all referenced objects",Ð

"homepage": "https://github.com/sebastianbergmann/object-enumerator/",Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/object-enumerator/issues",Ð "source": "https://github.com/sebastianbergmann/object-enumerator/tree/4.0.4"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/object-enumerator"Ð },Ð {Ð "name": "sebastian/object-reflector",Ð "version": "2.0.4",Ð "version_normalized": "2.0.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/object-reflector.git",Ð "reference": "b4f479ebdbf63ac605d183ece17d8d7fe49c15c7"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/object-reflector/zipball/b4f479ebdbf63ac605d183ece17d8d7fe49c15c7",Ð "reference": "b4f479ebdbf63ac605d183ece17d8d7fe49c15c7",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2020-10-26T13:14:26+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð }Ð],Ð "description": "Allows reflection of object attributes, including inherited and non-public ones",Ð "homepage": "https://github.com/sebastianbergmann/object-reflector/",Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/object-reflector/issues",Ð "source": "https://github.com/sebastianbergmann/object-reflector/tree/2.0.4"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/sebastianbergmann",Ð "type": "github"Ð }Ð],Ð "install-path": "../sebastian/object-reflector"Ð },Ð {Ð "name": "sebastian/recursion-context",Ð "version": "4.0.5",Ð "version_normalized": "4.0.5.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/sebastianbergmann/recursion-context.git",Ð "reference": "e75bd0f07204fec2a0af9b0f3cfe97d05f92efc1"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/sebastianbergmann/recursion-context/zipball/e75bd0f07204fec2a0af9b0f3cfe97d05f92efc1",Ð "reference": "e75bd0f07204fec2a0af9b0f3cfe97d05f92efc1",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "time": "2023-02-03T06:07:39+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "4.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð },Ð {Ð "name": "Jeff Welch",Ð

"email": "whatthejeff@gmail.com"Đ
},Đ {Đ "name": "Adam Harvey",Đ
"email": "aharvey@php.net"Đ }Đ],Đ
"description": "Provides functionality to recursively process PHP variables",Đ "homepage": "https://github.com/sebastianbergmann/recursion-context",Đ "support": {Đ "issues": "https://github.com/sebastianbergmann/recursion-context/issues",Đ "source": "https://github.com/sebastianbergmann/recursion-context/tree/4.0.5"Đ
},Đ "funding": [Đ {Đ "url": "https://github.com/sebastianbergmann",Đ "type": "github"Đ }Đ],Đ "install-path": "../sebastian/recursion-context"Đ },Đ {Đ "name": "sebastian/resource-operations",Đ "version": "3.0.4",Đ "version_normalized": "3.0.4.0",Đ "source": {Đ "type": "git",Đ "url": "https://github.com/sebastianbergmann/resource-operations.git",Đ "reference": "05d5692a7993ecccd56a03e40cd7e5b09b1d404e"Đ },Đ "dist": {Đ "type": "zip",Đ "url": "https://api.github.com/repos/sebastianbergmann/resource-operations/zipball/05d5692a7993ecccd56a03e40cd7e5b09b1d404e",Đ "reference": "05d5692a7993ecccd56a03e40cd7e5b09b1d404e",Đ "shasum": ""Đ },Đ "require": {Đ "php": ">=7.3"Đ },Đ "require-dev": {Đ "phpunit/phpunit": "^9.0"Đ },Đ "time": "2024-03-14T16:00:52+00:00",Đ
"type": "library",Đ "extra": {Đ "branch-alias": {Đ "dev-main": "3.0-dev"Đ }Đ
},Đ "installation-source": "dist",Đ "autoload": {Đ "classmap": [Đ "src/"Đ
]Đ },Đ "notification-url": "https://packagist.org/downloads/",Đ "license": [Đ "BSD-3-Clause"Đ],Đ "authors": [Đ {Đ
"name": "Sebastian Bergmann",Đ "email": "sebastian@phpunit.de"Đ }Đ],Đ "description": "Provides a list of PHP built-in functions that operate on resources",Đ "homepage": "https://www.github.com/sebastianbergmann/resource-operations",Đ "support": {Đ "source": "https://github.com/sebastianbergmann/resource-operations/tree/3.0.4"Đ
},Đ "funding": [Đ {Đ "url": "https://github.com/sebastianbergmann",Đ "type": "github"Đ }Đ],Đ "install-path": "../sebastian/resource-operations"Đ },Đ {Đ "name": "sebastian/type",Đ "version": "3.2.1",Đ "version_normalized": "3.2.1.0",Đ "source": {Đ "type": "git",Đ "url": "https://github.com/sebastianbergmann/type.git",Đ "reference": "75e2c2a32f5e0b3aef905b9ed0b179b953b3d7c7"Đ },Đ "dist": {Đ "type": "zip",Đ "url": "https://api.github.com/repos/sebastianbergmann/type/zipball/75e2c2a32f5e0b3aef905b9ed0b179b953b3d7c7",Đ "reference": "75e2c2a32f5e0b3aef905b9ed0b179b953b3d7c7",Đ "shasum": ""Đ },Đ "require": {Đ "php": ">=7.3"Đ },Đ "require-dev": {Đ "phpunit/phpunit": "^9.5"Đ },Đ "time": "2023-02-03T06:13:03+00:00",Đ
"type": "library",Đ "extra": {Đ "branch-alias": {Đ "dev-master": "3.2-dev"Đ }Đ
},Đ "installation-source": "dist",Đ "autoload": {Đ "classmap": [Đ "src/"Đ
]Đ },Đ "notification-url": "https://packagist.org/downloads/",Đ "license": [Đ "BSD-3-Clause"Đ

```
                    ],Ð           "authors": [Ð                {Ð
                     "name": "Sebastian Bergmann",Ð                    "email":
"sebastian@phpunit.de",Ð                    "role": "lead"Ð                }Ð
            ],Ð           "description": "Collection of value objects that
represent the types of the PHP type system",Ð           "homepage": "https://
github.com/sebastianbergmann/type",Ð           "support": {Ð
"issues": "https://github.com/sebastianbergmann/type/issues",Ð
"source": "https://github.com/sebastianbergmann/type/tree/3.2.1"Ð           },Ð
            "funding": [Ð                {Ð                    "url": "https://
github.com/sebastianbergmann",Ð                    "type": "github"Ð
                }Ð           ],Ð           "install-path": "../sebastian/type"Ð
        },Ð       {Ð           "name": "sebastian/version",Ð
"version": "3.0.2",Ð           "version_normalized": "3.0.2.0",Ð
"source": {Ð                "type": "git",Ð                "url": "https://
github.com/sebastianbergmann/version.git",Ð                "reference":
"c6c1022351a901512170118436c764e473f6de8c"Ð           },Ð           "dist": {Ð
                "type": "zip",Ð                "url": "https://api.github.com/
repos/sebastianbergmann/version/zipball/
c6c1022351a901512170118436c764e473f6de8c",Ð                "reference":
"c6c1022351a901512170118436c764e473f6de8c",Ð                "shasum": ""Ð
            },Ð           "require": {Ð                "php": ">=7.3"Ð
            },Ð           "time": "2020-09-28T06:39:44+00:00",Ð
"type": "library",Ð           "extra": {Ð                "branch-alias": {Ð
                    "dev-master": "3.0-dev"Ð                }Ð           },Ð
            "installation-source": "dist",Ð           "autoload": {Ð
                "classmap": [Ð                    "src/"Ð                ]Ð
            },Ð           "notification-url": "https://packagist.org/
downloads/",Ð           "license": [Ð                "BSD-3-Clause"Ð
            ],Ð           "authors": [Ð                {Ð
"name": "Sebastian Bergmann",Ð                    "email":
"sebastian@phpunit.de",Ð                    "role": "lead"Ð                }Ð
            ],Ð           "description": "Library that helps with managing
the version number of Git-hosted PHP projects",Ð           "homepage":
"https://github.com/sebastianbergmann/version",Ð           "support": {Ð
                "issues": "https://github.com/sebastianbergmann/version/
issues",Ð                "source": "https://github.com/sebastianbergmann/
version/tree/3.0.2"Ð           },Ð           "funding": [Ð                {Ð
                    "url": "https://github.com/sebastianbergmann",Ð
                    "type": "github"Ð                }Ð           ],Ð
            "install-path": "../sebastian/version"Ð       },Ð       {Ð
            "name": "spatie/backtrace",Ð           "version": "1.7.2",Ð
            "version_normalized": "1.7.2.0",Ð           "source": {Ð
                "type": "git",Ð                "url": "https://github.com/
spatie/backtrace.git",Ð                "reference":
"9807de6b8fecfaa5b3d10650985f0348b02862b2"Ð           },Ð           "dist": {Ð
                "type": "zip",Ð                "url": "https://api.github.com/
repos/spatie/backtrace/zipball/9807de6b8fecfaa5b3d10650985f0348b02862b2",Ð
                "reference": "9807de6b8fecfaa5b3d10650985f0348b02862b2",Ð
                "shasum": ""Ð           },Ð           "require": {Ð
                "php": "^7.3 || ^8.0"Ð           },Ð           "require-dev":
{Ð                "ext-json": "*",Ð                "laravel/serializable-
closure": "^1.3 || ^2.0",Ð                "phpunit/phpunit": "^9.3 || ^11.4.3",Ð
                "spatie/phpunit-snapshot-assertions": "^4.2 || ^5.1.6",Ð
                "symfony/var-dumper": "^5.1 || ^6.0 || ^7.0"Ð           },Ð
            "time": "2025-04-28T14:55:53+00:00",Ð           "type": "library",Ð
            "installation-source": "dist",Ð           "autoload": {Ð
                "psr-4": {Ð                    "Spatie\\Backtrace\\": "src"Ð
                }Ð           },Ð           "notification-url": "https://
packagist.org/downloads/",Ð           "license": [Ð                "MIT"Ð
            ],Ð
```

"authors": [Ð {Ð
"name": "Freek Van de Herten",Ð "email": "freek@spatie.be",Ð
"homepage": "https://spatie.be",Ð
"role": "Developer"Ð }Ð],Ð "description":
"A better backtrace",Ð "homepage": "https://github.com/spatie/
backtrace",Ð "keywords": [Ð "Backtrace",Ð
"spatie"Ð],Ð "support": {Ð
"source": "https://github.com/spatie/backtrace/tree/1.7.2"Ð },Ð
"funding": [Ð {Ð "url": "https://
github.com/sponsors/spatie",Ð "type": "github"Ð
},Ð {Ð "url": "https://
spatie.be/open-source/support-us",Ð "type": "other"Ð
}Ð],Ð "install-path": "../spatie/
backtrace"Ð },Ð {Ð "name": "spatie/flare-client-php",Ð
"version": "1.10.1",Ð "version_normalized": "1.10.1.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/spatie/flare-client-php.git",Ð "reference":
"bf1716eb98bd689451b071548ae9e70738dce62f"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/spatie/flare-client-php/zipball/
bf1716eb98bd689451b071548ae9e70738dce62f",Ð "reference":
"bf1716eb98bd689451b071548ae9e70738dce62f",Ð "shasum": ""Ð
},Ð "require": {Ð "illuminate/pipeline":
"^8.0|^9.0|^10.0|^11.0|^12.0",Ð "php": "^8.0",Ð
"spatie/backtrace": "^1.6.1",Ð "symfony/http-foundation": "^5.2|
^6.0|^7.0",Ð "symfony/mime": "^5.2|^6.0|^7.0",Ð
"symfony/process": "^5.2|^6.0|^7.0",Ð "symfony/var-dumper":
"^5.2|^6.0|^7.0"Ð },Ð "require-dev": {Ð
"dms/phpunit-arraysubset-asserts": "^0.5.0",Ð "pestphp/pest":
"^1.20|^2.0",Ð "phpstan/extension-installer": "^1.1",Ð
"phpstan/phpstan-deprecation-rules": "^1.0",Ð
"phpstan/phpstan-phpunit": "^1.0",Ð "spatie/pest-plugin-
snapshots": "^1.0|^2.0"Ð },Ð "time":
"2025-02-14T13:42:06+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-main":
"1.3.x-dev"Ð }Ð },Ð "installation-source":
"dist",Ð "autoload": {Ð "files": [Ð
"src/helpers.php"Ð],Ð "psr-4": {Ð
"Spatie\\FlareClient\\": "src"Ð }Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "MIT"Ð],Ð
"description": "Send PHP errors to Flare",Ð "homepage":
"https://github.com/spatie/flare-client-php",Ð "keywords": [Ð
"exception",Ð "flare",Ð
"reporting",Ð "spatie"Ð],Ð "support": {Ð
"issues": "https://github.com/spatie/flare-client-php/issues",Ð
"source": "https://github.com/spatie/flare-client-php/
tree/1.10.1"Ð },Ð "funding": [Ð {Ð
"url": "https://github.com/spatie",Ð
"type": "github"Ð }Ð],Ð "install-path":
"../spatie/flare-client-php"Ð },Ð {Ð "name": "spatie/
ignition",Ð "version": "1.14.2",Ð "version_normalized":
"1.14.2.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/spatie/ignition.git",Ð
"reference": "5e11c11f675bb5251f061491a493e04a1a571532"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/spatie/ignition/
zipball/5e11c11f675bb5251f061491a493e04a1a571532",Ð
"reference": "5e11c11f675bb5251f061491a493e04a1a571532",Ð
"shasum": ""Ð

},Ð "require": {Ð "ext-json": "*",Ð "ext-mbstring": "*",Ð "php": "^8.0",Ð "spatie/backtrace": "^1.5.3",Ð "spatie/flare-client-php": "^1.4.0",Ð "symfony/console": "^5.4|^6.0|^7.0",Ð "symfony/var-dumper": "^5.4|^6.0|^7.0"Ð },Ð "require-dev": {Ð "illuminate/cache": "^9.52|^10.0|^11.0",Ð "mockery/mockery": "^1.4",Ð "pestphp/pest": "^1.20|^2.0",Ð "phpstan/extension-installer": "^1.1",Ð "phpstan/phpstan-deprecation-rules": "^1.0",Ð "phpstan/phpstan-phpunit": "^1.0",Ð "psr/simple-cache-implementation": "*",Ð "symfony/cache": "^5.4|^6.0|^7.0",Ð "symfony/process": "^5.4|^6.0|^7.0",Ð "vlucas/phpdotenv": "^5.5"Ð },Ð "suggest": {Ð "openai-php/client": "Require get solutions from OpenAI",Ð "simple-cache-implementation": "To cache solutions from OpenAI"Ð },Ð "time": "2024-05-29T08:10:20+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "1.5.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Spatie\\Ignition\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Spatie",Ð "email": "info@spatie.be",Ð "role": "Developer"Ð }Ð],Ð "description": "A beautiful error page for PHP applications.",Ð "homepage": "https://flareapp.io/ignition",Ð "keywords": [Ð "error",Ð "flare",Ð "laravel",Ð "page"Ð],Ð "support": {Ð "docs": "https://flareapp.io/docs/ignition-for-laravel/introduction",Ð "forum": "https://twitter.com/flareappio",Ð "issues": "https://github.com/spatie/ignition/issues",Ð "source": "https://github.com/spatie/ignition"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/spatie",Ð "type": "github"Ð }Ð],Ð "install-path": "../spatie/ignition"Ð },Ð {Ð "name": "spatie/laravel-ignition",Ð "version": "1.7.0",Ð "version_normalized": "1.7.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/spatie/laravel-ignition.git",Ð "reference": "b6d5c33cf0b8260d6540572af2d9bcf9182fe5fb"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/spatie/laravel-ignition/zipball/b6d5c33cf0b8260d6540572af2d9bcf9182fe5fb",Ð "reference": "b6d5c33cf0b8260d6540572af2d9bcf9182fe5fb",Ð "shasum": ""Ð },Ð "require": {Ð "ext-curl": "*",Ð "ext-json": "*",Ð "ext-mbstring": "*",Ð "illuminate/support": "^8.77|^9.27",Ð "monolog/monolog": "^2.3",Ð "php": "^8.0",Ð "spatie/flare-client-php": "^1.0.1",Ð "spatie/ignition": "<= 1.14.2",Ð "symfony/console": "^5.0|^6.0",Ð "symfony/var-dumper": "^5.0|^6.0"Ð },Ð "require-dev": {Ð "filp/whoops": "^2.14",Ð "livewire/livewire": "^2.8|dev-develop",Ð "mockery/mockery": "^1.4",Ð "nunomaduro/larastan": "^1.0",Ð "orchestra/testbench": "^6.23|^7.0",Ð "pestphp/pest": "^1.20",Ð "phpstan/extension-installer": "^1.1",Ð "phpstan/phpstan-deprecation-rules": "^1.0",Ð "phpstan/phpstan-phpunit": "^1.0",Ð "spatie/laravel-ray": "^1.27"Ð },Ð "time": "2024-06-13T07:21:06+00:00",Ð

"type": "library",Ð
"extra": {Ð "laravel": {Ð "aliases": {Ð
"Flare": "Spatie\\LaravelIgnition\\Facades\\Flare"Ð
},Ð "providers": [Ð
"Spatie\\LaravelIgnition\\IgnitionServiceProvider"Ð
]Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð
"src/helpers.php"Ð],Ð
"psr-4": {Ð "Spatie\\LaravelIgnition\\": "src"Ð
}Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "Spatie",Ð "email": "info@spatie.be",Ð
"role": "Developer"Ð }Ð],Ð
"description": "A beautiful error page for Laravel applications.",Ð
"homepage": "https://flareapp.io/ignition",Ð
"keywords": [Ð "error",Ð "flare",Ð
"laravel",Ð "page"Ð],Ð "support": {Ð
"docs": "https://flareapp.io/docs/ignition-for-laravel/introduction",Ð "forum": "https://twitter.com/flareappio",Ð
"issues": "https://github.com/spatie/laravel-ignition/issues",Ð
"source": "https://github.com/spatie/laravel-ignition"Ð
},Ð "funding": [Ð {Ð
"url": "https://github.com/spatie",Ð "type": "github"Ð
}Ð],Ð "install-path": "../spatie/laravel-ignition"Ð },Ð {Ð "name": "stripe/stripe-php",Ð
"version": "v4.13.0",Ð "version_normalized": "4.13.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://github.com/stripe/stripe-php.git",Ð "reference": "834681b9cdfa68d88a27e36ec9e356b598a5f0e6"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/stripe/stripe-php/zipball/834681b9cdfa68d88a27e36ec9e356b598a5f0e6",Ð
"reference": "834681b9cdfa68d88a27e36ec9e356b598a5f0e6",Ð
"shasum": ""Ð },Ð "require": {Ð
"ext-curl": "*",Ð "ext-json": "*",Ð
"ext-mbstring": "*",Ð "php": ">=5.3.3"Ð
},Ð "require-dev": {Ð "phpunit/phpunit": "~4.0",Ð "satooshi/php-coveralls": "~0.6.1",Ð
"squizlabs/php_codesniffer": "~2.0"Ð },Ð "time": "2017-06-20T01:39:06+00:00",Ð "type": "library",Ð
"extra": {Ð "branch-alias": {Ð "dev-master": "2.0-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð
"Stripe\\": "lib/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð
"MIT"Ð],Ð "authors": [Ð {Ð
"name": "Stripe and contributors",Ð
"homepage": "https://github.com/stripe/stripe-php/contributors"Ð
}Ð],Ð "description": "Stripe PHP Library",Ð "homepage": "https://stripe.com/",Ð
"keywords": [Ð "api",Ð "payment processing",Ð
"stripe"Ð],Ð "support": {Ð
"issues": "https://github.com/stripe/stripe-php/issues",Ð
"source": "https://github.com/stripe/stripe-php/tree/master"Ð },Ð
"install-path": "../stripe/stripe-php"Ð },Ð {Ð
"name": "symfony/browser-kit",Ð "version": "v7.2.4",Ð
"version_normalized": "7.2.4.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/browser-kit.git",Ð "reference": "8ce0ee23857d87d5be493abba2d52d1f9e49da61"Ð

},Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/browser-kit/zipball/8ce0ee23857d87d5be493abba2d52d1f9e49da61",Ð
"reference": "8ce0ee23857d87d5be493abba2d52d1f9e49da61",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.2",Ð "symfony/dom-crawler": "^6.4|^7.0"Ð },Ð "require-dev": {Ð "symfony/css-selector": "^6.4|^7.0",Ð "symfony/http-client": "^6.4|^7.0",Ð
"symfony/mime": "^6.4|^7.0",Ð "symfony/process": "^6.4|^7.0"Ð },Ð "time": "2025-02-14T14:27:24+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Symfony\\Component\\BrowserKit\\": ""Ð
},Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð
"name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð
"description": "Simulates the behavior of a web browser, allowing you to make requests, click on links and submit forms programmatically",Ð
"homepage": "https://symfony.com",Ð "support": {Ð
"source": "https://github.com/symfony/browser-kit/tree/v7.2.4"Ð },Ð
"funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../symfony/browser-kit"Ð },Ð
{Ð "name": "symfony/console",Ð "version": "v6.4.20",Ð "version_normalized": "6.4.20.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/console.git",Ð "reference": "2e4af9c952617cc3f9559ff706aee420a8464c36"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/console/zipball/2e4af9c952617cc3f9559ff706aee420a8464c36",Ð
"reference": "2e4af9c952617cc3f9559ff706aee420a8464c36",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/polyfill-mbstring": "~1.0",Ð
"symfony/service-contracts": "^2.5|^3",Ð
"symfony/string": "^5.4|^6.0|^7.0"Ð },Ð "conflict": {Ð
"symfony/dependency-injection": "<5.4",Ð
"symfony/dotenv": "<5.4",Ð "symfony/event-dispatcher": "<5.4",Ð
"symfony/lock": "<5.4",Ð "symfony/process": "<5.4"Ð },Ð "provide": {Ð "psr/log-implementation": "1.0|2.0|3.0"Ð },Ð "require-dev": {Ð
"psr/log": "^1|^2|^3",Ð "symfony/config": "^5.4|^6.0|^7.0",Ð "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð
"symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð
"symfony/http-foundation": "^6.4|^7.0",Ð "symfony/http-kernel": "^6.4|^7.0",Ð "symfony/lock": "^5.4|^6.0|^7.0",Ð
"symfony/messenger": "^5.4|^6.0|^7.0",Ð "symfony/process": "^5.4|^6.0|^7.0",Ð "symfony/stopwatch": "^5.4|^6.0|^7.0",Ð
"symfony/var-dumper": "^5.4|^6.0|^7.0"Ð },Ð
"time": "2025-03-03T17:16:38+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð

"autoload": {Ð
"psr-4": {Ð "Symfony\\Component\\Console\
\": ""Ð },Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Fabien Potencier",Ð "email":
"fabien@symfony.com"Ð },Ð {Ð
"name": "Symfony Community",Ð "homepage": "https://
symfony.com/contributors"Ð }Ð],Ð
"description": "Eases the creation of beautiful and testable command line
interfaces",Ð "homepage": "https://symfony.com",Ð
"keywords": [Ð "cli",Ð "command-line",Ð
"console",Ð "terminal"Ð],Ð
"support": {Ð "source": "https://github.com/symfony/console/
tree/v6.4.20"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/console"Ð },Ð {Ð "name": "symfony/css-
selector",Ð "version": "v7.2.0",Ð "version_normalized":
"7.2.0.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/symfony/css-selector.git",Ð
"reference": "601a5ce9aaad7bf10797e3663faefce9e26c24e2"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/symfony/css-selector/
zipball/601a5ce9aaad7bf10797e3663faefce9e26c24e2",Ð
"reference": "601a5ce9aaad7bf10797e3663faefce9e26c24e2",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=8.2"Ð },Ð "time": "2024-09-25T14:21:43+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð
"Symfony\\Component\\CssSelector\\": ""Ð },Ð
"exclude-from-classmap": [Ð "/Tests/"Ð]Ð
},Ð "notification-url": "https://packagist.org/
downloads/",Ð "license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Fabien
Potencier",Ð "email": "fabien@symfony.com"Ð },Ð
{Ð "name": "Jean-François Simon",Ð
"email": "jeanfrancois.simon@sensiolabs.com"Ð
},Ð {Ð "name": "Symfony
Community",Ð "homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Converts CSS
selectors to XPath expressions",Ð "homepage": "https://symfony.com",Ð
"support": {Ð "source": "https://github.com/symfony/
css-selector/tree/v7.2.0"Ð },Ð "funding": [Ð
{Ð "url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð
"url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð "url":
"https://tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../symfony/css-selector"Ð },Ð {Ð
"name": "symfony/deprecation-contracts",Ð "version":
"v3.5.1",Ð "version_normalized": "3.5.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
symfony/deprecation-contracts.git",Ð

"reference": "74c71c939a79f7d5bf3c1ce9f5ea37ba0114c6f6"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/deprecation-contracts/zipball/74c71c939a79f7d5bf3c1ce9f5ea37ba0114c6f6",Ð "reference": "74c71c939a79f7d5bf3c1ce9f5ea37ba0114c6f6",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1"Ð },Ð "time": "2024-09-25T14:20:29+00:00",Ð "type": "library",Ð "extra": {Ð "thanks": {Ð "url": "https://github.com/symfony/contracts",Ð "name": "symfony/contracts"Ð },Ð "branch-alias": {Ð "dev-main": "3.5-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "function.php"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "A generic function and convention to trigger deprecation notices",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/deprecation-contracts/tree/v3.5.1"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/deprecation-contracts"Ð },Ð {Ð "name": "symfony/dom-crawler",Ð "version": "v7.2.4",Ð "version_normalized": "7.2.4.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/dom-crawler.git",Ð "reference": "19cc7b08efe9ad1ab1b56e0948e8d02e15ed3ef7"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/dom-crawler/zipball/19cc7b08efe9ad1ab1b56e0948e8d02e15ed3ef7",Ð "reference": "19cc7b08efe9ad1ab1b56e0948e8d02e15ed3ef7",Ð "shasum": ""Ð },Ð "require": {Ð "masterminds/html5": "^2.6",Ð "php": ">=8.2",Ð "symfony/polyfill-ctype": "~1.8",Ð "symfony/polyfill-mbstring": "~1.0"Ð },Ð "require-dev": {Ð "symfony/css-selector": "^6.4|^7.0"Ð },Ð "time": "2025-02-17T15:53:07+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Component\\DomCrawler\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Eases DOM navigation for HTML and XML documents",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/dom-crawler/tree/v7.2.4"Ð },Ð "funding": [Ð

{Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/dom-crawler"Ð },Ð {Ð "name": "symfony/error-handler",Ð "version": "v6.4.20",Ð "version_normalized": "6.4.20.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/error-handler.git",Ð "reference": "aa3bcf4f7674719df078e61cc8062e5b7f752031"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/error-handler/zipball/aa3bcf4f7674719df078e61cc8062e5b7f752031",Ð "reference": "aa3bcf4f7674719df078e61cc8062e5b7f752031",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1",Ð "psr/log": "^1|^2|^3",Ð "symfony/var-dumper": "^5.4|^6.0|^7.0"Ð },Ð "conflict": {Ð "symfony/deprecation-contracts": "<2.5",Ð "symfony/http-kernel": "<6.4"Ð },Ð "require-dev": {Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/http-kernel": "^6.4|^7.0",Ð "symfony/serializer": "^5.4|^6.0|^7.0"Ð },Ð "time": "2025-03-01T13:00:38+00:00",Ð "bin": [Ð "Resources/bin/patch-type-declarations"Ð],Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Component\\ErrorHandler\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Provides tools to manage errors and ease debugging PHP code",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/error-handler/tree/v6.4.20"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/error-handler"Ð },Ð {Ð "name": "symfony/event-dispatcher",Ð "version": "v7.2.0",Ð "version_normalized": "7.2.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/event-dispatcher.git",Ð "reference": "910c5db85a5356d0fea57680defec4e99eb9c8c1"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/event-dispatcher/zipball/910c5db85a5356d0fea57680defec4e99eb9c8c1",Ð "reference": "910c5db85a5356d0fea57680defec4e99eb9c8c1",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.2",Ð "symfony/event-dispatcher-contracts": "^2.5|^3"Ð },Ð "conflict": {Ð "symfony/dependency-injection": "<6.4",Ð "symfony/service-contracts": "<2.5"Ð },Ð

"provide": {Ð "psr/event-dispatcher-implementation": "1.0",Ð "symfony/event-dispatcher-implementation": "2.0|3.0"Ð },Ð "require-dev": {Ð "psr/log": "^1|^2|^3",Ð "symfony/config": "^6.4|^7.0",Ð "symfony/dependency-injection": "^6.4|^7.0",Ð "symfony/error-handler": "^6.4|^7.0",Ð "symfony/expression-language": "^6.4|^7.0",Ð "symfony/http-foundation": "^6.4|^7.0",Ð "symfony/service-contracts": "^2.5|^3",Ð "symfony/stopwatch": "^6.4|^7.0"Ð },Ð "time": "2024-09-25T14:21:43+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Component\\EventDispatcher\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Provides tools that allow your application components to communicate with each other by dispatching events and listening to them",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/event-dispatcher/tree/v7.2.0"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/event-dispatcher"Ð },Ð {Ð "name": "symfony/event-dispatcher-contracts",Ð "version": "v3.5.1",Ð "version_normalized": "3.5.1.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/event-dispatcher-contracts.git",Ð "reference": "7642f5e970b672283b7823222ae8ef8bbc160b9f"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/event-dispatcher-contracts/zipball/7642f5e970b672283b7823222ae8ef8bbc160b9f",Ð "reference": "7642f5e970b672283b7823222ae8ef8bbc160b9f",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1",Ð "psr/event-dispatcher": "^1"Ð },Ð "time": "2024-09-25T14:20:29+00:00",Ð "type": "library",Ð "extra": {Ð "thanks": {Ð "url": "https://github.com/symfony/contracts",Ð "name": "symfony/contracts"Ð },Ð "branch-alias": {Ð "dev-main": "3.5-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Contracts\\EventDispatcher\\": ""Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Generic abstractions related to dispatching event",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "abstractions",Ð "contracts",Ð

"decoupling",Ð
"interfaces",Ð "interoperability",Ð "standards"Ð
],Ð "support": {Ð "source": "https://
github.com/symfony/event-dispatcher-contracts/tree/v3.5.1"Ð },Ð
"funding": [Ð {Ð "url": "https://
symfony.com/sponsor",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/
symfony/symfony",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../symfony/event-dispatcher-
contracts"Ð },Ð {Ð "name": "symfony/finder",Ð
"version": "v6.4.17",Ð "version_normalized": "6.4.17.0",Ð
"source": {Ð "type": "git",Ð "url": "https://
github.com/symfony/finder.git",Ð "reference":
"1d0e8266248c5d9ab6a87e3789e6dc482af3c9c7"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/finder/zipball/1d0e8266248c5d9ab6a87e3789e6dc482af3c9c7",Ð
"reference": "1d0e8266248c5d9ab6a87e3789e6dc482af3c9c7",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1"Ð },Ð "require-dev": {Ð
"symfony/filesystem": "^6.0|^7.0"Ð },Ð
"time": "2024-12-29T13:51:37+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Symfony\\Component\\Finder\\": ""Ð
},Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Fabien Potencier",Ð "email":
"fabien@symfony.com"Ð },Ð {Ð
"name": "Symfony Community",Ð "homepage": "https://
symfony.com/contributors"Ð }Ð],Ð
"description": "Finds files and directories via an intuitive fluent
interface",Ð "homepage": "https://symfony.com",Ð
"support": {Ð "source": "https://github.com/symfony/finder/tree/
v6.4.17"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/finder"Ð },Ð {Ð "name": "symfony/http-
client",Ð "version": "v7.2.4",Ð "version_normalized":
"7.2.4.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/symfony/http-client.git",Ð
"reference": "78981a2ffef6437ed92d4d7e2a86a82f256c6dc6"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/symfony/http-client/
zipball/78981a2ffef6437ed92d4d7e2a86a82f256c6dc6",Ð
"reference": "78981a2ffef6437ed92d4d7e2a86a82f256c6dc6",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=8.2",Ð "psr/log": "^1|^2|^3",Ð "symfony/
deprecation-contracts": "^2.5|^3",Ð "symfony/http-client-
contracts": "~3.4.4|^3.5.2",Ð "symfony/service-contracts":
"^2.5|^3"Ð },Ð "conflict": {Ð "amphp/amp":
"<2.5",Ð "php-http/discovery": "<1.15",Ð "symfony/
http-foundation": "<6.4"Ð },Ð "provide": {Ð
"php-http/async-client-implementation": "*",Ð

"php-http/client-implementation": "*",Ð "psr/http-client-implementation": "1.0",Ð "symfony/http-client-implementation": "3.0"Ð },Ð "require-dev": {Ð "amphp/http-client": "^4.2.1|^5.0",Ð "amphp/http-tunnel": "^1.0|^2.0",Ð "amphp/socket": "^1.1",Ð "guzzlehttp/promises": "^1.4|^2.0",Ð "nyholm/psr7": "^1.0",Ð "php-http/httplug": "^1.0|^2.0",Ð "psr/http-client": "^1.0",Ð "symfony/amphp-http-client-meta": "^1.0|^2.0",Ð "symfony/dependency-injection": "^6.4|^7.0",Ð "symfony/http-kernel": "^6.4|^7.0",Ð "symfony/messenger": "^6.4|^7.0",Ð "symfony/process": "^6.4|^7.0",Ð "symfony/rate-limiter": "^6.4|^7.0",Ð "symfony/stopwatch": "^6.4|^7.0"Ð },Ð "time": "2025-02-13T10:27:23+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Component\\HttpClient\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Provides powerful methods to fetch HTTP resources synchronously or asynchronously",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "http"Ð],Ð "support": {Ð "source": "https://github.com/symfony/http-client/tree/v7.2.4"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/http-client"Ð },Ð {Ð "name": "symfony/http-client-contracts",Ð "version": "v3.5.2",Ð "version_normalized": "3.5.2.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/http-client-contracts.git",Ð "reference": "ee8d807ab20fcb51267fdace50fbe3494c31e645"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/http-client-contracts/zipball/ee8d807ab20fcb51267fdace50fbe3494c31e645",Ð "reference": "ee8d807ab20fcb51267fdace50fbe3494c31e645",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1"Ð },Ð "time": "2024-12-07T08:49:48+00:00",Ð "type": "library",Ð "extra": {Ð "thanks": {Ð "url": "https://github.com/symfony/contracts",Ð "name": "symfony/contracts"Ð },Ð "branch-alias": {Ð "dev-main": "3.5-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Contracts\\HttpClient\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Test/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð

}Ð],Ð "description": "Generic abstractions related to HTTP clients",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "abstractions",Ð "contracts",Ð "decoupling",Ð "interfaces",Ð "interoperability",Ð "standards"Ð],Ð "support": {Ð "source": "https://github.com/symfony/http-client-contracts/tree/v3.5.2"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/http-client-contracts"Ð },Ð {Ð "name": "symfony/http-foundation",Ð "version": "v6.4.18",Ð "version_normalized": "6.4.18.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/http-foundation.git",Ð "reference": "d0492d6217e5ab48f51fca76f64cf8e78919d0db"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/http-foundation/zipball/d0492d6217e5ab48f51fca76f64cf8e78919d0db",Ð "reference": "d0492d6217e5ab48f51fca76f64cf8e78919d0db",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1",Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/polyfill-mbstring": "~1.1",Ð "symfony/polyfill-php83": "^1.27"Ð },Ð "conflict": {Ð "symfony/cache": "<6.4.12|>=7.0,<7.1.5"Ð },Ð "require-dev": {Ð "doctrine/dbal": "^2.13.1|^3|^4",Ð "predis/predis": "^1.1|^2.0",Ð "symfony/cache": "^6.4.12|^7.1.5",Ð "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð "symfony/expression-language": "^5.4|^6.0|^7.0",Ð "symfony/http-kernel": "^5.4.12|^6.0.12|^6.1.4|^7.0",Ð "symfony/mime": "^5.4|^6.0|^7.0",Ð "symfony/rate-limiter": "^5.4|^6.0|^7.0"Ð },Ð "time": "2025-01-09T15:48:56+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Component\\HttpFoundation\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Defines an object-oriented layer for the HTTP specification",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/http-foundation/tree/v6.4.18"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/http-foundation"Ð },Ð {Ð "name": "symfony/http-kernel",Ð "version": "v6.4.20",Ð "version_normalized": "6.4.20.0",Ð

"source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/http-kernel.git",Ð "reference": "6be6db31bc74693ce5516e1fd5e5ff1171005e37"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/http-kernel/zipball/6be6db31bc74693ce5516e1fd5e5ff1171005e37",Ð
"reference": "6be6db31bc74693ce5516e1fd5e5ff1171005e37",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "psr/log": "^1|^2|^3",Ð
"symfony/deprecation-contracts": "^2.5|^3",Ð
"symfony/error-handler": "^6.4|^7.0",Ð "symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð "symfony/http-foundation": "^6.4|^7.0",Ð "symfony/polyfill-ctype": "^1.8"Ð },Ð
"conflict": {Ð "symfony/browser-kit": "<5.4",Ð
"symfony/cache": "<5.4",Ð "symfony/config": "<6.1",Ð "symfony/console": "<5.4",Ð "symfony/dependency-injection": "<6.4",Ð "symfony/doctrine-bridge": "<5.4",Ð "symfony/form": "<5.4",Ð "symfony/http-client": "<5.4",Ð "symfony/http-client-contracts": "<2.5",Ð
"symfony/mailer": "<5.4",Ð "symfony/messenger": "<5.4",Ð "symfony/translation": "<5.4",Ð "symfony/translation-contracts": "<2.5",Ð "symfony/twig-bridge": "<5.4",Ð
"symfony/validator": "<6.4",Ð "symfony/var-dumper": "<6.3",Ð "twig/twig": "<2.13"Ð },Ð
"provide": {Ð "psr/log-implementation": "1.0|2.0|3.0"Ð
},Ð "require-dev": {Ð "psr/cache": "^1.0|^2.0|^3.0",Ð "symfony/browser-kit": "^5.4|^6.0|^7.0",Ð
"symfony/clock": "^6.2|^7.0",Ð "symfony/config": "^6.1|^7.0",Ð "symfony/console": "^5.4|^6.0|^7.0",Ð
"symfony/css-selector": "^5.4|^6.0|^7.0",Ð
"symfony/dependency-injection": "^6.4|^7.0",Ð "symfony/dom-crawler": "^5.4|^6.0|^7.0",Ð "symfony/expression-language": "^5.4|^6.0|^7.0",Ð "symfony/finder": "^5.4|^6.0|^7.0",Ð
"symfony/http-client-contracts": "^2.5|^3",Ð
"symfony/process": "^5.4|^6.0|^7.0",Ð "symfony/property-access": "^5.4.5|^6.0.5|^7.0",Ð "symfony/routing": "^5.4|^6.0|^7.0",Ð "symfony/serializer": "^6.4.4|^7.0.4",Ð
"symfony/stopwatch": "^5.4|^6.0|^7.0",Ð "symfony/translation": "^5.4|^6.0|^7.0",Ð "symfony/translation-contracts": "^2.5|^3",Ð
"symfony/uid": "^5.4|^6.0|^7.0",Ð "symfony/validator": "^6.4|^7.0",Ð "symfony/var-dumper": "^5.4|^6.4|^7.0",Ð "symfony/var-exporter": "^6.2|^7.0",Ð
"twig/twig": "^2.13|^3.0.4"Ð },Ð "time": "2025-03-28T13:27:10+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Symfony\\Component\\HttpKernel\\": ""Ð
},Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð
"name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð
"description": "Provides a structured process for converting a Request into a Response",Ð "homepage": "https://symfony.com",Ð
"support": {Ð "source": "https://github.com/symfony/http-kernel/tree/v6.4.20"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð

},Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/http-kernel"Ð },Ð {Ð "name": "symfony/mailer",Ð "version": "v6.4.18",Ð "version_normalized": "6.4.18.0",Ð "source": {Ð "type": "git",Ð
"url": "https://github.com/symfony/mailer.git",Ð
"reference": "e93a6ae2767d7f7578c2b7961d9d8e27580b2b11"Ð
},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/symfony/mailer/zipball/e93a6ae2767d7f7578c2b7961d9d8e27580b2b11",Ð "reference": "e93a6ae2767d7f7578c2b7961d9d8e27580b2b11",Ð "shasum": ""Ð
},Ð "require": {Ð "egulias/email-validator": "^2.1.10|^3|^4",Ð "php": ">=8.1",Ð "psr/event-dispatcher": "^1",Ð "psr/log": "^1|^2|^3",Ð
"symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð "symfony/mime": "^6.2|^7.0",Ð "symfony/service-contracts": "^2.5|^3"Ð },Ð "conflict": {Ð "symfony/http-client-contracts": "<2.5",Ð "symfony/http-kernel": "<5.4",Ð
"symfony/messenger": "<6.2",Ð "symfony/mime": "<6.2",Ð "symfony/twig-bridge": "<6.2.1"Ð },Ð
"require-dev": {Ð "symfony/console": "^5.4|^6.0|^7.0",Ð "symfony/http-client": "^5.4|^6.0|^7.0",Ð "symfony/messenger": "^6.2|^7.0",Ð "symfony/twig-bridge": "^6.2|^7.0"Ð },Ð "time": "2025-01-24T15:27:15+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Symfony\\Component\\Mailer\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð },Ð
{Ð "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Helps sending emails",Ð
"homepage": "https://symfony.com",Ð "support": {Ð
"source": "https://github.com/symfony/mailer/tree/v6.4.18"Ð
},Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð
},Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð
{Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð
}Ð],Ð "install-path": "../symfony/mailer"Ð
},Ð {Ð "name": "symfony/mime",Ð "version": "v6.4.19",Ð "version_normalized": "6.4.19.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/mime.git",Ð "reference": "ac537b6c55ccc2c749f3c979edfa9ec14aaed4f3"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/mime/zipball/ac537b6c55ccc2c749f3c979edfa9ec14aaed4f3",Ð
"reference": "ac537b6c55ccc2c749f3c979edfa9ec14aaed4f3",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/polyfill-intl-idn": "^1.10",Ð
"symfony/polyfill-mbstring": "^1.0"Ð },Ð
"conflict": {Ð

"egulias/email-validator": "~3.0.0",Ð
"phpdocumentor/reflection-docblock": "<3.2.2",Ð
"phpdocumentor/type-resolver": "<1.4.0",Ð "symfony/mailer":
"<5.4",Ð "symfony/serializer": "<6.4.3|>7.0,<7.0.3"Ð
},Ð "require-dev": {Ð "egulias/email-
validator": "^2.1.10|^3.1|^4",Ð "league/html-to-markdown":
"^5.0",Ð "phpdocumentor/reflection-docblock": "^3.0|^4.0|^5.0",Ð
"symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð
"symfony/process": "^5.4|^6.4|^7.0",Ð "symfony/
property-access": "^5.4|^6.0|^7.0",Ð "symfony/property-info":
"^5.4|^6.0|^7.0",Ð "symfony/serializer": "^6.4.3|^7.0.3"Ð
},Ð "time": "2025-02-17T21:23:52+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Symfony\
\Component\\Mime\\": ""Ð },Ð "exclude-from-
classmap": [Ð "/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð },Ð
{Ð "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Allows
manipulating MIME messages",Ð "homepage": "https://symfony.com",Ð
"keywords": [Ð "mime",Ð "mime-type"Ð
],Ð "support": {Ð "source": "https://
github.com/symfony/mime/tree/v6.4.19"Ð },Ð "funding": [Ð
{Ð "url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð
"url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð "url":
"https://tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../symfony/mime"Ð },Ð {Ð
"name": "symfony/polyfill-ctype",Ð "version": "v1.31.0",Ð
"version_normalized": "1.31.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/polyfill-
ctype.git",Ð "reference":
"a3cc8b044a6ea513310cbd48ef7333b384945638"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/polyfill-ctype/zipball/
a3cc8b044a6ea513310cbd48ef7333b384945638",Ð "reference":
"a3cc8b044a6ea513310cbd48ef7333b384945638",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=7.2"Ð
},Ð "provide": {Ð "ext-ctype": "*"Ð
},Ð "suggest": {Ð "ext-ctype": "For best
performance"Ð },Ð "time": "2024-09-09T11:45:10+00:00",Ð
"type": "library",Ð "extra": {Ð "thanks":
{Ð "url": "https://github.com/symfony/polyfill",Ð
"name": "symfony/polyfill"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "bootstrap.php"Ð
],Ð "psr-4": {Ð "Symfony\
\Polyfill\\Ctype\\": ""Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Gert de Pagter",Ð "email":
"BackEndTea@gmail.com"Ð },Ð {Ð
"name": "Symfony Community",Ð "homepage": "https://
symfony.com/contributors"Ð

}Ð],Ð
"description": "Symfony polyfill for ctype functions",Ð "homepage":
"https://symfony.com",Ð "keywords": [Ð
"compatibility",Ð "ctype",Ð "polyfill",Ð
"portable"Ð],Ð "support": {Ð
"source": "https://github.com/symfony/polyfill-ctype/tree/
v1.31.0"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/polyfill-ctype"Ð },Ð {Ð "name": "symfony/
polyfill-intl-grapheme",Ð "version": "v1.31.0",Ð
"version_normalized": "1.31.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/polyfill-
intl-grapheme.git",Ð "reference":
"b9123926e3b7bc2f98c02ad54f6a4b02b91a8abe"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/polyfill-intl-grapheme/zipball/
b9123926e3b7bc2f98c02ad54f6a4b02b91a8abe",Ð "reference":
"b9123926e3b7bc2f98c02ad54f6a4b02b91a8abe",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=7.2"Ð
},Ð "suggest": {Ð "ext-intl": "For best
performance"Ð },Ð "time": "2024-09-09T11:45:10+00:00",Ð
"type": "library",Ð "extra": {Ð "thanks":
{Ð "url": "https://github.com/symfony/polyfill",Ð
"name": "symfony/polyfill"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "bootstrap.php"Ð
],Ð "psr-4": {Ð "Symfony\
\Polyfill\\Intl\\Grapheme\\": ""Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Nicolas Grekas",Ð "email":
"p@tchwork.com"Ð },Ð {Ð "name":
"Symfony Community",Ð "homepage": "https://symfony.com/
contributors"Ð }Ð],Ð "description":
"Symfony polyfill for intl's grapheme_* functions",Ð "homepage":
"https://symfony.com",Ð "keywords": [Ð
"compatibility",Ð "grapheme",Ð "intl",Ð
"polyfill",Ð "portable",Ð "shim"Ð
],Ð "support": {Ð "source": "https://
github.com/symfony/polyfill-intl-grapheme/tree/v1.31.0"Ð },Ð
"funding": [Ð {Ð "url": "https://
symfony.com/sponsor",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/
symfony/symfony",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../symfony/polyfill-intl-grapheme"Ð
},Ð {Ð "name": "symfony/polyfill-intl-idn",Ð
"version": "v1.31.0",Ð "version_normalized": "1.31.0.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/symfony/polyfill-intl-idn.git",Ð
"reference": "c36586dcf89a12315939e00ec9b4474adcb1d773"Ð },Ð
"dist": {Ð "type": "zip",Ð "url":
"https://api.github.com/repos/symfony/polyfill-intl-idn/zipball/
c36586dcf89a12315939e00ec9b4474adcb1d773",Ð

"reference": "c36586dcf89a12315939e00ec9b4474adcb1d773",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=7.2",Ð
"symfony/polyfill-intl-normalizer": "^1.10"Ð },Ð
"suggest": {Ð "ext-intl": "For best performance"Ð
},Ð "time": "2024-09-09T11:45:10+00:00",Ð
"type": "library",Ð "extra": {Ð "thanks": {Ð
"url": "https://github.com/symfony/polyfill",Ð
"name": "symfony/polyfill"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "bootstrap.php"Ð
],Ð "psr-4": {Ð "Symfony\
\Polyfill\\Intl\\Idn\\": ""Ð }Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Laurent Bassin",Ð "email":
"laurent@bassin.info"Ð },Ð {Ð
"name": "Trevor Rowbotham",Ð "email":
"trevor.rowbotham@pm.me"Ð },Ð {Ð
"name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð }Ð],Ð
"description": "Symfony polyfill for intl's idn_to_ascii and
idn_to_utf8 functions",Ð "homepage": "https://symfony.com",Ð
"keywords": [Ð "compatibility",Ð
"idn",Ð "intl",Ð "polyfill",Ð
"portable",Ð "shim"Ð],Ð "support": {Ð
"source": "https://github.com/symfony/polyfill-intl-idn/tree/
v1.31.0"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/polyfill-intl-idn"Ð },Ð {Ð "name": "symfony/
polyfill-intl-normalizer",Ð "version": "v1.31.0",Ð
"version_normalized": "1.31.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/polyfill-
intl-normalizer.git",Ð "reference":
"3833d7255cc303546435cb650316bff708a1c75c"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/polyfill-intl-normalizer/
zipball/3833d7255cc303546435cb650316bff708a1c75c",Ð
"reference": "3833d7255cc303546435cb650316bff708a1c75c",Ð
"shasum": ""Ð },Ð "require": {Ð "php":
">=7.2"Ð },Ð "suggest": {Ð "ext-intl": "For
best performance"Ð },Ð "time":
"2024-09-09T11:45:10+00:00",Ð "type": "library",Ð
"extra": {Ð "thanks": {Ð "url": "https://
github.com/symfony/polyfill",Ð "name": "symfony/polyfill"Ð
}Ð },Ð "installation-source": "dist",Ð
"autoload": {Ð "files": [Ð
"bootstrap.php"Ð],Ð "psr-4": {Ð
"Symfony\\Polyfill\\Intl\\Normalizer\\": ""Ð
},Ð "classmap": [Ð "Resources/
stubs"Ð]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð
},Ð

{Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Symfony polyfill for intl's Normalizer class and related functions",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "compatibility",Ð "intl",Ð "normalizer",Ð "polyfill",Ð "portable",Ð "shim"Ð],Ð "support": {Ð "source": "https://github.com/symfony/polyfill-intl-normalizer/tree/v1.31.0"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/polyfill-intl-normalizer"Ð },Ð {Ð "name": "symfony/polyfill-mbstring",Ð "version": "v1.31.0",Ð "version_normalized": "1.31.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/polyfill-mbstring.git",Ð "reference": "85181ba99b2345b0ef10ce42ecac37612d9fd341"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/polyfill-mbstring/zipball/85181ba99b2345b0ef10ce42ecac37612d9fd341",Ð "reference": "85181ba99b2345b0ef10ce42ecac37612d9fd341",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=7.2"Ð },Ð "provide": {Ð "ext-mbstring": "*"Ð },Ð "suggest": {Ð "ext-mbstring": "For best performance"Ð },Ð "time": "2024-09-09T11:45:10+00:00",Ð "type": "library",Ð "extra": {Ð "thanks": {Ð "url": "https://github.com/symfony/polyfill",Ð "name": "symfony/polyfill"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "bootstrap.php"Ð],Ð "psr-4": {Ð "Symfony\\Polyfill\\Mbstring\\": ""Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Symfony polyfill for the Mbstring extension",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "compatibility",Ð "mbstring",Ð "polyfill",Ð "portable",Ð "shim"Ð],Ð "support": {Ð "source": "https://github.com/symfony/polyfill-mbstring/tree/v1.31.0"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/polyfill-mbstring"Ð },Ð {Ð "name": "symfony/polyfill-php80",Ð "version": "v1.31.0",Ð "version_normalized": "1.31.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/polyfill-php80.git",Ð "reference": "60328e362d4c2c802a54fcbf04f9d3fb892b4cf8"Ð

},Ð "dist": {Ð "type": "zip",Ð
"url": "https://api.github.com/repos/symfony/polyfill-php80/zipball/60328e362d4c2c802a54fcbf04f9d3fb892b4cf8",Ð
"reference": "60328e362d4c2c802a54fcbf04f9d3fb892b4cf8",Ð
"shasum": ""Ð },Ð "require": {Ð "php": ">=7.2"Ð },Ð "time": "2024-09-09T11:45:10+00:00",Ð
"type": "library",Ð "extra": {Ð "thanks": {Ð
"url": "https://github.com/symfony/polyfill",Ð
"name": "symfony/polyfill"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "bootstrap.php"Ð
],Ð "psr-4": {Ð "Symfony\\Polyfill\\Php80\\": ""Ð },Ð "classmap": [Ð
"Resources/stubs"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Ion Bazan",Ð
"email": "ion.bazan@gmail.com"Ð },Ð
{Ð "name": "Nicolas Grekas",Ð
"email": "p@tchwork.com"Ð },Ð
{Ð "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð }Ð],Ð
"description": "Symfony polyfill backporting some PHP 8.0+ features to lower PHP versions",Ð "homepage": "https://symfony.com",Ð
"keywords": [Ð "compatibility",Ð
"polyfill",Ð "portable",Ð "shim"Ð],Ð
"support": {Ð "source": "https://github.com/symfony/polyfill-php80/tree/v1.31.0"Ð },Ð "funding": [Ð
{Ð "url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð
"url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../symfony/polyfill-php80"Ð },Ð {Ð
"name": "symfony/polyfill-php83",Ð "version": "v1.31.0",Ð
"version_normalized": "1.31.0.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/polyfill-php83.git",Ð "reference": "2fb86d65e2d424369ad2905e83b236a8805ba491"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/polyfill-php83/zipball/2fb86d65e2d424369ad2905e83b236a8805ba491",Ð
"reference": "2fb86d65e2d424369ad2905e83b236a8805ba491",Ð
"shasum": ""Ð },Ð "require": {Ð "php": ">=7.2"Ð },Ð "time": "2024-09-09T11:45:10+00:00",Ð
"type": "library",Ð "extra": {Ð "thanks": {Ð
"url": "https://github.com/symfony/polyfill",Ð
"name": "symfony/polyfill"Ð }Ð },Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "bootstrap.php"Ð
],Ð "psr-4": {Ð "Symfony\\Polyfill\\Php83\\": ""Ð },Ð "classmap": [Ð
"Resources/stubs"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Nicolas Grekas",Ð
"email": "p@tchwork.com"Ð },Ð
{Ð

"name": "Symfony Community",Đ
"homepage": "https://symfony.com/contributors"Đ }Đ],Đ
"description": "Symfony polyfill backporting some PHP 8.3+
features to lower PHP versions",Đ "homepage": "https://symfony.com",Đ
"keywords": [Đ "compatibility",Đ
"polyfill",Đ "portable",Đ "shim"Đ],Đ
"support": {Đ "source": "https://github.com/symfony/
polyfill-php83/tree/v1.31.0"Đ },Đ "funding": [Đ
{Đ "url": "https://symfony.com/sponsor",Đ
"type": "custom"Đ },Đ {Đ
"url": "https://github.com/fabpot",Đ
"type": "github"Đ },Đ {Đ "url":
"https://tidelift.com/funding/github/packagist/symfony/symfony",Đ
"type": "tidelift"Đ }Đ],Đ
"install-path": "../symfony/polyfill-php83"Đ },Đ {Đ
"name": "symfony/polyfill-uuid",Đ "version": "v1.31.0",Đ
"version_normalized": "1.31.0.0",Đ "source": {Đ
"type": "git",Đ "url": "https://github.com/
symfony/polyfill-uuid.git",Đ "reference":
"21533be36c24be3f4b1669c4725c7d1d2bab4ae2"Đ },Đ "dist": {Đ
"type": "zip",Đ "url": "https://api.github.com/
repos/symfony/polyfill-uuid/zipball/21533be36c24be3f4b1669c4725c7d1d2bab4ae2",Đ
"reference": "21533be36c24be3f4b1669c4725c7d1d2bab4ae2",Đ
"shasum": ""Đ },Đ "require": {Đ
"php": ">=7.2"Đ },Đ "provide": {Đ
"ext-uuid": "*"Đ },Đ "suggest": {Đ
"ext-uuid": "For best performance"Đ },Đ
"time": "2024-09-09T11:45:10+00:00",Đ "type": "library",Đ
"extra": {Đ "thanks": {Đ "url": "https://
github.com/symfony/polyfill",Đ "name": "symfony/polyfill"Đ
}Đ },Đ "installation-source": "dist",Đ
"autoload": {Đ "files": [Đ
"bootstrap.php"Đ],Đ "psr-4": {Đ
"Symfony\\Polyfill\\Uuid\\": ""Đ }Đ
},Đ "notification-url": "https://packagist.org/
downloads/",Đ "license": [Đ "MIT"Đ],Đ
"authors": [Đ {Đ "name":
"Grégoire Pineau",Đ "email": "lyrixx@lyrixx.info"Đ
},Đ {Đ "name": "Symfony
Community",Đ "homepage": "https://symfony.com/contributors"Đ
}Đ],Đ "description": "Symfony polyfill
for uuid functions",Đ "homepage": "https://symfony.com",Đ
"keywords": [Đ "compatibility",Đ "polyfill",Đ
"portable",Đ "uuid"Đ],Đ
"support": {Đ "source": "https://github.com/symfony/polyfill-
uuid/tree/v1.31.0"Đ },Đ "funding": [Đ {Đ
"url": "https://symfony.com/sponsor",Đ
"type": "custom"Đ },Đ {Đ "url":
"https://github.com/fabpot",Đ "type": "github"Đ
},Đ {Đ "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Đ
"type": "tidelift"Đ }Đ],Đ "install-path":
"../symfony/polyfill-uuid"Đ },Đ {Đ "name": "symfony/
process",Đ "version": "v6.4.20",Đ "version_normalized":
"6.4.20.0",Đ "source": {Đ "type": "git",Đ
"url": "https://github.com/symfony/process.git",Đ
"reference": "e2a61c16af36c9a07e5c9906498b73e091949a20"Đ
},Đ "dist": {Đ "type": "zip",Đ
"url": "https://api.github.com/repos/symfony/process/zipball/
e2a61c16af36c9a07e5c9906498b73e091949a20",Đ

"reference": "e2a61c16af36c9a07e5c9906498b73e091949a20",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=8.1"Ð
},Ð "time": "2025-03-10T17:11:00+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Symfony\
\Component\\Process\\": ""Ð },Ð "exclude-from-
classmap": [Ð "/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð },Ð
{Ð "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Executes commands
in sub-processes",Ð "homepage": "https://symfony.com",Ð
"support": {Ð "source": "https://github.com/symfony/process/
tree/v6.4.20"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/process"Ð },Ð {Ð "name": "symfony/routing",Ð
"version": "v6.4.18",Ð "version_normalized": "6.4.18.0",Ð
"source": {Ð "type": "git",Ð "url":
"https://github.com/symfony/routing.git",Ð "reference":
"e9bfc94953019089acdfb9be51c1b9142c4afa68"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/routing/zipball/e9bfc94953019089acdfb9be51c1b9142c4afa68",Ð
"reference": "e9bfc94953019089acdfb9be51c1b9142c4afa68",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/deprecation-
contracts": "^2.5|^3"Ð },Ð "conflict": {Ð
"doctrine/annotations": "<1.12",Ð "symfony/config": "<6.2",Ð
"symfony/dependency-injection": "<5.4",Ð
"symfony/yaml": "<5.4"Ð },Ð "require-dev": {Ð
"doctrine/annotations": "^1.12|^2",Ð "psr/log":
"^1|^2|^3",Ð "symfony/config": "^6.2|^7.0",Ð
"symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð "symfony/
expression-language": "^5.4|^6.0|^7.0",Ð "symfony/http-
foundation": "^5.4|^6.0|^7.0",Ð "symfony/yaml": "^5.4|^6.0|^7.0"Ð
},Ð "time": "2025-01-09T08:51:02+00:00",Ð
"type": "library",Ð "installation-source": "dist",Ð
"autoload": {Ð "psr-4": {Ð "Symfony\
\Component\\Routing\\": ""Ð },Ð "exclude-from-
classmap": [Ð "/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð "MIT"Ð],Ð
"authors": [Ð {Ð "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð },Ð
{Ð "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Maps an HTTP
request to a set of configuration variables",Ð "homepage": "https://
symfony.com",Ð "keywords": [Ð "router",Ð
"routing",Ð "uri",Ð "url"Ð
],Ð "support": {Ð "source": "https://
github.com/symfony/routing/tree/v6.4.18"Ð

},Ð "funding": [Ð
{Ð "url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð
"url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð "url":
"https://tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð
"install-path": "../symfony/routing"Ð },Ð {Ð
"name": "symfony/service-contracts",Ð "version":
"v3.5.1",Ð "version_normalized": "3.5.1.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/
symfony/service-contracts.git",Ð "reference":
"e53260aabf78fb3d63f8d79d69ece59f80d5eda0"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/service-contracts/zipball/
e53260aabf78fb3d63f8d79d69ece59f80d5eda0",Ð "reference":
"e53260aabf78fb3d63f8d79d69ece59f80d5eda0",Ð "shasum": ""Ð
},Ð "require": {Ð "php": ">=8.1",Ð
"psr/container": "^1.1|^2.0",Ð "symfony/
deprecation-contracts": "^2.5|^3"Ð },Ð "conflict": {Ð
"ext-psr": "<1.1|>=2"Ð },Ð "time":
"2024-09-25T14:20:29+00:00",Ð "type": "library",Ð
"extra": {Ð "thanks": {Ð "url": "https://
github.com/symfony/contracts",Ð "name": "symfony/contracts"Ð
},Ð "branch-alias": {Ð "dev-
main": "3.5-dev"Ð }Ð },Ð "installation-
source": "dist",Ð "autoload": {Ð "psr-4": {Ð
"Symfony\\Contracts\\Service\\": ""Ð },Ð
"exclude-from-classmap": [Ð "/Test/"Ð
]Ð },Ð "notification-url": "https://
packagist.org/downloads/",Ð "license": [Ð "MIT"Ð
],Ð "authors": [Ð {Ð
"name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð
},Ð {Ð "name": "Symfony
Community",Ð "homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Generic
abstractions related to writing services",Ð "homepage": "https://
symfony.com",Ð "keywords": [Ð "abstractions",Ð
"contracts",Ð "decoupling",Ð
"interfaces",Ð "interoperability",Ð "standards"Ð
],Ð "support": {Ð "source": "https://
github.com/symfony/service-contracts/tree/v3.5.1"Ð },Ð
"funding": [Ð {Ð "url": "https://symfony.com/
sponsor",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/fabpot",Ð
"type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/
symfony/symfony",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../symfony/service-contracts"Ð
},Ð {Ð "name": "symfony/string",Ð
"version": "v7.2.0",Ð "version_normalized": "7.2.0.0",Ð
"source": {Ð "type": "git",Ð "url": "https://
github.com/symfony/string.git",Ð "reference":
"446e0d146f991dde3e73f45f2c97a9faad773c82"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/string/zipball/446e0d146f991dde3e73f45f2c97a9faad773c82",Ð
"reference": "446e0d146f991dde3e73f45f2c97a9faad773c82",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.2",Ð "symfony/polyfill-ctype":
"~1.8",Ð

"symfony/polyfill-intl-grapheme": "~1.0",Ð
"symfony/polyfill-intl-normalizer": "~1.0",Ð
"symfony/polyfill-mbstring": "~1.0"Ð },Ð "conflict": {Ð
"symfony/translation-contracts": "<2.5"Ð },Ð
"require-dev": {Ð "symfony/emoji": "^7.1",Ð
"symfony/error-handler": "^6.4|^7.0",Ð "symfony/
http-client": "^6.4|^7.0",Ð "symfony/intl": "^6.4|^7.0",Ð
"symfony/translation-contracts": "^2.5|^3.0",Ð
"symfony/var-exporter": "^6.4|^7.0"Ð },Ð "time":
"2024-11-13T13:31:26+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"files": [Ð "Resources/functions.php"Ð],Ð
"psr-4": {Ð "Symfony\\Component\\String\\":
""Ð },Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license":
[Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Nicolas Grekas",Ð "email":
"p@tchwork.com"Ð },Ð {Ð "name":
"Symfony Community",Ð "homepage": "https://symfony.com/
contributors"Ð }Ð],Ð "description":
"Provides an object-oriented API to strings and deals with bytes, UTF-8 code
points and grapheme clusters in a unified way",Ð "homepage":
"https://symfony.com",Ð "keywords": [Ð "grapheme",Ð
"i18n",Ð "string",Ð "unicode",Ð
"utf-8",Ð "utf8"Ð],Ð
"support": {Ð "source": "https://github.com/symfony/string/tree/
v7.2.0"Ð },Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð
"type": "custom"Ð },Ð {Ð "url":
"https://github.com/fabpot",Ð "type": "github"Ð
},Ð {Ð "url": "https://
tidelift.com/funding/github/packagist/symfony/symfony",Ð
"type": "tidelift"Ð }Ð],Ð "install-path":
"../symfony/string"Ð },Ð {Ð "name": "symfony/
translation",Ð "version": "v6.4.19",Ð
"version_normalized": "6.4.19.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/
translation.git",Ð "reference":
"3b9bf9f33997c064885a7bfc126c14b9daa0e00e"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/
repos/symfony/translation/zipball/3b9bf9f33997c064885a7bfc126c14b9daa0e00e",Ð
"reference": "3b9bf9f33997c064885a7bfc126c14b9daa0e00e",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/deprecation-
contracts": "^2.5|^3",Ð "symfony/polyfill-mbstring": "~1.0",Ð
"symfony/translation-contracts": "^2.5|^3.0"Ð },Ð
"conflict": {Ð "symfony/config": "<5.4",Ð
"symfony/console": "<5.4",Ð "symfony/dependency-
injection": "<5.4",Ð "symfony/http-client-contracts": "<2.5",Ð
"symfony/http-kernel": "<5.4",Ð "symfony/
service-contracts": "<2.5",Ð "symfony/twig-bundle": "<5.4",Ð
"symfony/yaml": "<5.4"Ð },Ð "provide": {Ð
"symfony/translation-implementation": "2.3|3.0"Ð },Ð
"require-dev": {Ð "nikic/php-parser": "^4.18|^5.0",Ð
"psr/log": "^1|^2|^3",Ð "symfony/config": "^5.4|
^6.0|^7.0",Ð "symfony/console": "^5.4|^6.0|^7.0",Ð
"symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð
"symfony/finder": "^5.4|^6.0|^7.0",Ð "symfony/
http-client-contracts": "^2.5|^3.0",Ð

"symfony/http-kernel": "^5.4|^6.0|^7.0",Ð "symfony/intl": "^5.4|^6.0|^7.0",Ð "symfony/polyfill-intl-icu": "^1.21",Ð "symfony/routing": "^5.4|^6.0|^7.0",Ð "symfony/service-contracts": "^2.5|^3",Ð "symfony/yaml": "^5.4|^6.0|^7.0"Ð },Ð "time": "2025-02-13T10:18:43+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "files": [Ð "Resources/functions.php"Ð],Ð "psr-4": {Ð "Symfony\\Component\\Translation\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Fabien Potencier",Ð "email": "fabien@symfony.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Provides tools to internationalize your application",Ð "homepage": "https://symfony.com",Ð "support": {Ð "source": "https://github.com/symfony/translation/tree/v6.4.19"Ð },Ð "funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/translation"Ð },Ð {Ð "name": "symfony/translation-contracts",Ð "version": "v3.5.1",Ð "version_normalized": "3.5.1.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/symfony/translation-contracts.git",Ð "reference": "4667ff3bd513750603a09c8dedbea942487fb07c"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/symfony/translation-contracts/zipball/4667ff3bd513750603a09c8dedbea942487fb07c",Ð "reference": "4667ff3bd513750603a09c8dedbea942487fb07c",Ð "shasum": ""Ð },Ð "require": {Ð "php": ">=8.1"Ð },Ð "time": "2024-09-25T14:20:29+00:00",Ð "type": "library",Ð "extra": {Ð "thanks": {Ð "url": "https://github.com/symfony/contracts",Ð "name": "symfony/contracts"Ð },Ð "branch-alias": {Ð "dev-main": "3.5-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Symfony\\Contracts\\Translation\\": ""Ð },Ð "exclude-from-classmap": [Ð "/Test/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "description": "Generic abstractions related to translation",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "abstractions",Ð "contracts",Ð "decoupling",Ð "interfaces",Ð "interoperability",Ð "standards"Ð],Ð "support": {Ð "source": "https://github.com/symfony/translation-contracts/tree/v3.5.1"Ð

},Ð
"funding": [Ð {Ð "url": "https://symfony.com/sponsor",Ð "type": "custom"Ð },Ð
{Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð {Ð
"url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð
],Ð "install-path": "../symfony/translation-contracts"Ð
},Ð {Ð "name": "symfony/uid",Ð "version": "v6.4.13",Ð "version_normalized": "6.4.13.0",Ð "source": {Ð
"type": "git",Ð "url": "https://github.com/symfony/uid.git",Ð "reference": "18eb207f0436a993fffbdd811b5b8fa35fa5e007"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/uid/zipball/18eb207f0436a993fffbdd811b5b8fa35fa5e007",Ð
"reference": "18eb207f0436a993fffbdd811b5b8fa35fa5e007",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/polyfill-uuid": "^1.15"Ð },Ð "require-dev": {Ð "symfony/console": "^5.4|^6.0|^7.0"Ð },Ð "time": "2024-09-25T14:18:03+00:00",Ð "type": "library",Ð
"installation-source": "dist",Ð "autoload": {Ð
"psr-4": {Ð "Symfony\\Component\\Uid\\": ""Ð
},Ð "exclude-from-classmap": [Ð
"/Tests/"Ð]Ð },Ð
"notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð
"name": "Grégoire Pineau",Ð "email": "lyrixx@lyrixx.info"Ð },Ð {Ð
"name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð
},Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð
}Ð],Ð "description": "Provides an object-oriented API to generate and represent UIDs",Ð "homepage": "https://symfony.com",Ð "keywords": [Ð "UID",Ð
"ulid",Ð "uuid"Ð],Ð "support": {Ð
"source": "https://github.com/symfony/uid/tree/v6.4.13"Ð
},Ð "funding": [Ð {Ð
"url": "https://symfony.com/sponsor",Ð "type": "custom"Ð
},Ð {Ð "url": "https://github.com/fabpot",Ð "type": "github"Ð },Ð
{Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð
}Ð],Ð "install-path": "../symfony/uid"Ð
},Ð {Ð "name": "symfony/var-dumper",Ð
"version": "v6.4.18",Ð "version_normalized": "6.4.18.0",Ð
"source": {Ð "type": "git",Ð "url": "https://github.com/symfony/var-dumper.git",Ð "reference": "4ad10cf8b020e77ba665305bb7804389884b4837"Ð },Ð "dist": {Ð
"type": "zip",Ð "url": "https://api.github.com/repos/symfony/var-dumper/zipball/4ad10cf8b020e77ba665305bb7804389884b4837",Ð
"reference": "4ad10cf8b020e77ba665305bb7804389884b4837",Ð
"shasum": ""Ð },Ð "require": {Ð
"php": ">=8.1",Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/polyfill-mbstring": "~1.0"Ð
},Ð "conflict": {Ð "symfony/console": "<5.4"Ð },Ð "require-dev": {Ð "ext-iconv": "*",Ð
"symfony/console": "^5.4|^6.0|^7.0",Ð
"symfony/error-handler": "^6.3|^7.0",Ð "symfony/http-kernel": "^5.4|^6.0|^7.0",Ð

"symfony/process": "^5.4|^6.0|^7.0",Đ
"symfony/uid": "^5.4|^6.0|^7.0",Đ "twig/twig": "^2.13|^3.0.4"Đ },Đ "time": "2025-01-17T11:26:11+00:00",Đ
"bin": [Đ "Resources/bin/var-dump-server"Đ
],Đ "type": "library",Đ "installation-source": "dist",Đ "autoload": {Đ "files": [Đ
"Resources/functions/dump.php"Đ],Đ
"psr-4": {Đ "Symfony\\Component\\VarDumper\\": ""Đ },Đ "exclude-from-classmap": [Đ
"/Tests/"Đ]Đ },Đ
"notification-url": "https://packagist.org/downloads/",Đ "license": [Đ
"MIT"Đ],Đ "authors": [Đ {Đ
"name": "Nicolas Grekas",Đ "email": "p@tchwork.com"Đ },Đ {Đ "name": "Symfony Community",Đ "homepage": "https://symfony.com/contributors"Đ }Đ],Đ "description": "Provides mechanisms for walking through any arbitrary PHP variable",Đ
"homepage": "https://symfony.com",Đ "keywords": [Đ
"debug",Đ "dump"Đ],Đ
"support": {Đ "source": "https://github.com/symfony/var-dumper/tree/v6.4.18"Đ },Đ "funding": [Đ {Đ
"url": "https://symfony.com/sponsor",Đ
"type": "custom"Đ },Đ {Đ "url": "https://github.com/fabpot",Đ "type": "github"Đ
},Đ {Đ "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Đ
"type": "tidelift"Đ }Đ],Đ "install-path": "../symfony/var-dumper"Đ },Đ {Đ "name": "symfony/yaml",Đ
"version": "v7.2.5",Đ "version_normalized": "7.2.5.0",Đ
"source": {Đ "type": "git",Đ "url": "https://github.com/symfony/yaml.git",Đ "reference": "4c4b6f4cfcd7e52053f0c8bfad0f7f30fb924912"Đ },Đ "dist": {Đ
"type": "zip",Đ "url": "https://api.github.com/repos/symfony/yaml/zipball/4c4b6f4cfcd7e52053f0c8bfad0f7f30fb924912",Đ
"reference": "4c4b6f4cfcd7e52053f0c8bfad0f7f30fb924912",Đ
"shasum": ""Đ },Đ "require": {Đ
"php": ">=8.2",Đ "symfony/deprecation-contracts": "^2.5|^3.0",Đ "symfony/polyfill-ctype": "^1.8"Đ
},Đ "conflict": {Đ "symfony/console": "<6.4"Đ },Đ "require-dev": {Đ "symfony/console": "^6.4|^7.0"Đ },Đ "time": "2025-03-03T07:12:39+00:00",Đ "bin": [Đ "Resources/bin/yaml-lint"Đ],Đ "type": "library",Đ
"installation-source": "dist",Đ "autoload": {Đ
"psr-4": {Đ "Symfony\\Component\\Yaml\\": ""Đ
},Đ "exclude-from-classmap": [Đ
"/Tests/"Đ]Đ },Đ
"notification-url": "https://packagist.org/downloads/",Đ "license": [Đ
"MIT"Đ],Đ "authors": [Đ {Đ
"name": "Fabien Potencier",Đ "email": "fabien@symfony.com"Đ },Đ {Đ
"name": "Symfony Community",Đ "homepage": "https://symfony.com/contributors"Đ }Đ],Đ
"description": "Loads and dumps YAML files",Đ "homepage": "https://symfony.com",Đ "support": {Đ "source": "https://github.com/symfony/yaml/tree/v7.2.5"Đ },Đ "funding": [Đ
{Đ "url": "https://symfony.com/sponsor",Đ
"type": "custom"Đ },Đ {Đ
"url": "https://github.com/fabpot",Đ
"type": "github"Đ

},Ð {Ð "url": "https://tidelift.com/funding/github/packagist/symfony/symfony",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../symfony/yaml"Ð },Ð {Ð "name": "theseer/tokenizer",Ð "version": "1.2.3",Ð "version_normalized": "1.2.3.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/theseer/tokenizer.git",Ð "reference": "737eda637ed5e28c3413cb1ebe8bb52cbf1ca7a2"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/theseer/tokenizer/zipball/737eda637ed5e28c3413cb1ebe8bb52cbf1ca7a2",Ð "reference": "737eda637ed5e28c3413cb1ebe8bb52cbf1ca7a2",Ð "shasum": ""Ð },Ð "require": {Ð "ext-dom": "*",Ð "ext-tokenizer": "*",Ð "ext-xmlwriter": "*",Ð "php": "^7.2 || ^8.0"Ð },Ð "time": "2024-03-03T12:36:25+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Arne Blankerts",Ð "email": "arne@blankerts.de",Ð "role": "Developer"Ð }Ð],Ð "description": "A small library for converting tokenized PHP source code into XML and potentially other formats",Ð "support": {Ð "issues": "https://github.com/theseer/tokenizer/issues",Ð "source": "https://github.com/theseer/tokenizer/tree/1.2.3"Ð },Ð "funding": [Ð {Ð "url": "https://github.com/theseer",Ð "type": "github"Ð }Ð],Ð "install-path": "../theseer/tokenizer"Ð },Ð {Ð "name": "tijsverkoyen/css-to-inline-styles",Ð "version": "v2.3.0",Ð "version_normalized": "2.3.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/tijsverkoyen/CssToInlineStyles.git",Ð "reference": "0d72ac1c00084279c1816675284073c5a337c20d"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/tijsverkoyen/CssToInlineStyles/zipball/0d72ac1c00084279c1816675284073c5a337c20d",Ð "reference": "0d72ac1c00084279c1816675284073c5a337c20d",Ð "shasum": ""Ð },Ð "require": {Ð "ext-dom": "*",Ð "ext-libxml": "*",Ð "php": "^7.4 || ^8.0",Ð "symfony/css-selector": "^5.4 || ^6.0 || ^7.0"Ð },Ð "require-dev": {Ð "phpstan/phpstan": "^2.0",Ð "phpstan/phpstan-phpunit": "^2.0",Ð "phpunit/phpunit": "^8.5.21 || ^9.5.10"Ð },Ð "time": "2024-12-21T16:25:41+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.x-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "TijsVerkoyen\\CssToInlineStyles\\": "src"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "BSD-3-Clause"Ð],Ð "authors": [Ð {Ð "name": "Tijs Verkoyen",Ð "email": "css_to_inline_styles@verkoyen.eu",Ð "role": "Developer"Ð }Ð],Ð "description": "CssToInlineStyles is a class that enables you to convert HTML-pages/files into HTML-pages/files with inline styles. This is very useful when you're sending emails.",Ð "homepage": "https://github.com/tijsverkoyen/CssToInlineStyles",Ð

"support": {Ð
"issues": "https://github.com/tijsverkoyen/CssToInlineStyles/issues",Ð
"source": "https://github.com/tijsverkoyen/CssToInlineStyles/tree/v2.3.0"Ð
},Ð
"install-path": "../tijsverkoyen/css-to-inline-styles"Ð
},Ð
{Ð
"name": "vlucas/phpdotenv",Ð
"version": "v5.6.2",Ð
"version_normalized": "5.6.2.0",Ð
"source": {Ð
"type": "git",Ð
"url": "https://github.com/vlucas/phpdotenv.git",Ð
"reference": "24ac4c74f91ee2c193fa1aaa5c249cb0822809af"Ð
},Ð
"dist": {Ð
"type": "zip",Ð
"url": "https://api.github.com/repos/vlucas/phpdotenv/zipball/24ac4c74f91ee2c193fa1aaa5c249cb0822809af",Ð
"reference": "24ac4c74f91ee2c193fa1aaa5c249cb0822809af",Ð
"shasum": ""Ð
},Ð
"require": {Ð
"ext-pcre": "*",Ð
"graham-campbell/result-type": "^1.1.3",Ð
"php": "^7.2.5 || ^8.0",Ð
"phpoption/phpoption": "^1.9.3",Ð
"symfony/polyfill-ctype": "^1.24",Ð
"symfony/polyfill-mbstring": "^1.24",Ð
"symfony/polyfill-php80": "^1.24"Ð
},Ð
"require-dev": {Ð
"bamarni/composer-bin-plugin": "^1.8.2",Ð
"ext-filter": "*",Ð
"phpunit/phpunit": "^8.5.34 || ^9.6.13 || ^10.4.2"Ð
},Ð
"suggest": {Ð
"ext-filter": "Required to use the boolean validator."Ð
},Ð
"time": "2025-04-30T23:37:27+00:00",Ð
"type": "library",Ð
"extra": {Ð
"bamarni-bin": {Ð
"bin-links": true,Ð
"forward-command": falseÐ
},Ð
"branch-alias": {Ð
"dev-master": "5.6-dev"Ð
}Ð
},Ð
"installation-source": "dist",Ð
"autoload": {Ð
"psr-4": {Ð
"Dotenv\\": "src/"Ð
}Ð
},Ð
"notification-url": "https://packagist.org/downloads/",Ð
"license": [Ð
"BSD-3-Clause"Ð
],Ð
"authors": [Ð
{Ð
"name": "Graham Campbell",Ð
"email": "hello@gjcampbell.co.uk",Ð
"homepage": "https://github.com/GrahamCampbell"Ð
},Ð
{Ð
"name": "Vance Lucas",Ð
"email": "vance@vancelucas.com",Ð
"homepage": "https://github.com/vlucas"Ð
}Ð
],Ð
"description": "Loads environment variables from `.env` to `getenv()`, `$_ENV` and `$_SERVER` automagically.",Ð
"keywords": [Ð
"dotenv",Ð
"env",Ð
"environment"Ð
],Ð
"support": {Ð
"issues": "https://github.com/vlucas/phpdotenv/issues",Ð
"source": "https://github.com/vlucas/phpdotenv/tree/v5.6.2"Ð
},Ð
"funding": [Ð
{Ð
"url": "https://github.com/GrahamCampbell",Ð
"type": "github"Ð
},Ð
{Ð
"url": "https://tidelift.com/funding/github/packagist/vlucas/phpdotenv",Ð
"type": "tidelift"Ð
}Ð
],Ð
"install-path": "../vlucas/phpdotenv"Ð
},Ð
{Ð
"name": "voku/portable-ascii",Ð
"version": "2.0.3",Ð
"version_normalized": "2.0.3.0",Ð
"source": {Ð
"type": "git",Ð
"url": "https://github.com/voku/portable-ascii.git",Ð
"reference": "b1d923f88091c6bf09699efcd7c8a1b1bfd7351d"Ð
},Ð
"dist": {Ð
"type": "zip",Ð
"url": "https://api.github.com/repos/voku/portable-ascii/zipball/b1d923f88091c6bf09699efcd7c8a1b1bfd7351d",Ð
"reference": "b1d923f88091c6bf09699efcd7c8a1b1bfd7351d",Ð
"shasum": ""Ð
},Ð
"require": {Ð
"php": ">=7.0.0"Ð
},Ð
"require-dev": {Ð
"phpunit/phpunit": "~6.0 || ~7.0 || ~9.0"Ð

},Ð
"suggest": {Ð "ext-intl": "Use Intl for transliterator_transliterate() support"Ð },Ð "time": "2024-11-21T01:49:47+00:00",Ð "type": "library",Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "voku\\": "src/voku/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Lars Moelleken",Ð "homepage": "https://www.moelleken.org/"Ð }Ð],Ð "description": "Portable ASCII library - performance optimized (ascii) string functions for php.",Ð "homepage": "https://github.com/voku/portable-ascii",Ð "keywords": [Ð "ascii",Ð "clean",Ð "php"Ð],Ð "support": {Ð "issues": "https://github.com/voku/portable-ascii/issues",Ð "source": "https://github.com/voku/portable-ascii/tree/2.0.3"Ð },Ð "funding": [Ð {Ð "url": "https://www.paypal.me/moelleken",Ð "type": "custom"Ð }Ð {Ð "url": "https://github.com/voku",Ð "type": "github"Ð }Ð {Ð "url": "https://opencollective.com/portable-ascii",Ð "type": "open_collective"Ð }Ð {Ð "url": "https://www.patreon.com/voku",Ð "type": "patreon"Ð },Ð {Ð "url": "https://tidelift.com/funding/github/packagist/voku/portable-ascii",Ð "type": "tidelift"Ð }Ð],Ð "install-path": "../voku/portable-ascii"Ð },Ð {Ð "name": "webmozart/assert",Ð "version": "1.11.0",Ð "version_normalized": "1.11.0.0",Ð "source": {Ð "type": "git",Ð "url": "https://github.com/webmozarts/assert.git",Ð "reference": "11cb2199493b2f8a3b53e7f19068fc6aac760991"Ð },Ð "dist": {Ð "type": "zip",Ð "url": "https://api.github.com/repos/webmozarts/assert/zipball/11cb2199493b2f8a3b53e7f19068fc6aac760991",Ð "reference": "11cb2199493b2f8a3b53e7f19068fc6aac760991",Ð "shasum": ""Ð },Ð "require": {Ð "ext-ctype": "*",Ð "php": "^7.2 || ^8.0"Ð },Ð "conflict": {Ð "phpstan/phpstan": "<0.12.20",Ð "vimeo/psalm": "<4.6.1 || 4.6.2"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^8.5.13"Ð },Ð "time": "2022-06-03T18:03:27+00:00",Ð "type": "library",Ð "extra": {Ð "branch-alias": {Ð "dev-master": "1.10-dev"Ð }Ð },Ð "installation-source": "dist",Ð "autoload": {Ð "psr-4": {Ð "Webmozart\\Assert\\": "src/"Ð }Ð },Ð "notification-url": "https://packagist.org/downloads/",Ð "license": [Ð "MIT"Ð],Ð "authors": [Ð {Ð "name": "Bernhard Schussek",Ð "email": "bschussek@gmail.com"Ð }Ð],Ð "description": "Assertions to validate method input/output with nice error messages.",Ð "keywords": [Ð "assert",Ð "check",Ð "validate"Ð],Ð "support": {Ð "issues": "https://github.com/webmozarts/assert/issues",Ð "source": "https://github.com/webmozarts/assert/tree/1.11.0"Ð },Ð "install-path": "../webmozart/assert"Ð }Ð],Ð "dev": true,Ð "dev-package-names": [Ð "doctrine/instantiator",Ð "fakerphp/faker",Ð "filp/whoops",Ð "hamcrest/hamcrest-php",Ð "kitloong/laravel-migrations-generator",Ð

"laravel/breeze",Ð "laravel/sail",Ð "mockery/mockery",Ð "myclabs/deep-copy",Ð "myclabs/php-enum",Ð "nunomaduro/collision",Ð "phar-io/manifest",Ð "phar-io/version",Ð "phpunit/php-code-coverage",Ð "phpunit/php-file-iterator",Ð "phpunit/php-invoker",Ð "phpunit/php-text-template",Ð "phpunit/php-timer",Ð "phpunit/phpunit",Ð "sebastian/cli-parser",Ð "sebastian/code-unit",Ð "sebastian/code-unit-reverse-lookup",Ð "sebastian/comparator",Ð "sebastian/complexity",Ð "sebastian/diff",Ð "sebastian/environment",Ð "sebastian/exporter",Ð "sebastian/global-state",Ð "sebastian/lines-of-code",Ð "sebastian/object-enumerator",Ð "sebastian/object-reflector",Ð "sebastian/recursion-context",Ð "sebastian/resource-operations",Ð "sebastian/type",Ð "sebastian/version",Ð "spatie/backtrace",Ð "spatie/flare-client-php",Ð "spatie/ignition",Ð "spatie/laravel-ignition",Ð "symfony/yaml",Ð "theseer/tokenizer"Ð]ÞÐ

vendor\dflydev\dot-access-data\composer.json

{Ð   "name": "dflydev/dot-access-data",Ð   "type": "library",Ð
"description": "Given a deep data structure, access data by dot notation.",Ð
    "homepage": "https://github.com/dflydev/dflydev-dot-access-data",Ð
"keywords": ["dot", "access", "data", "notation"],Ð   "license": "MIT",Ð
"authors": [Ð   {Ð   "name": "Dragonfly Development Inc.",Ð
            "email": "info@dflydev.com",Ð   "homepage": "http://
dflydev.com"Ð   },Ð   {Ð   "name": "Beau Simensen",Ð
            "email": "beau@dflydev.com",Ð   "homepage": "http://
beausimensen.com"Ð   },Ð   {Ð   "name": "Carlos Frutos",Ð
            "email": "carlos@kiwing.it",Ð   "homepage": "https://
github.com/cfrutos"Ð   },Ð   {Ð   "name": "Colin O'Dell",Ð
            "email": "colinodell@gmail.com",Ð   "homepage": "https://
www.colinodell.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.1 ||
^8.0"Ð   },Ð   "require-dev": {Ð   "phpstan/phpstan": "^0.12.42",Ð
"phpunit/phpunit": "^7.5 || ^8.5 || ^9.3",Ð   "scrutinizer/ocular":
"1.6.0",Ð   "squizlabs/php_codesniffer": "^3.5",Ð   "vimeo/psalm":
"^4.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Dflydev\
\DotAccessData\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4":
{Ð   "Dflydev\\DotAccessData\\": "tests/"Ð   }Ð   },Ð   "extra": {Ð
        "branch-alias": {Ð   "dev-main": "3.x-dev"Ð   }Ð   },Ð
"scripts": {Ð   "phpcs": "phpcs",Ð   "phpstan": "phpstan analyse",Ð
        "phpunit": "phpunit --no-coverage",Ð   "psalm": "psalm",Ð
"test": [Ð   "@phpcs",Ð   "@phpstan",Ð   "@psalm",Ð
            "@phpunit"Ð   ]Ð   }Ð}

vendor\doctrine\cache\composer.json

{Ð   "name": "doctrine/cache",Ð   "type": "library",Ð   "description": "PHP Doctrine Cache library is a popular cache implementation that supports many different drivers such as redis, memcache, apc, mongodb and others.",Ð   "keywords": [Ð   "php",Ð   "cache",Ð   "caching",Ð   "abstraction",Ð   "redis",Ð   "memcached",Ð   "couchdb",Ð   "xcache",Ð   "apcu"Ð   ],Ð   "homepage": "https://www.doctrine-project.org/projects/cache.html",Ð   "license": "MIT",Ð   "authors": [Ð   {"name": "Guilherme Blanco", "email": "guilhermeblanco@gmail.com"},Ð   {"name": "Roman Borschel", "email": "roman@code-factory.org"},Ð   {"name": "Benjamin Eberlei", "email": "kontakt@beberlei.de"},Ð   {"name": "Jonathan Wage", "email": "jonwage@gmail.com"},Ð   {"name": "Johannes Schmitt", "email": "schmittjoh@gmail.com"}Ð   ],Ð   "require": {Ð   "php": "~7.1 || ^8.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^7.5 || ^8.5 || ^9.5",Ð   "doctrine/coding-standard": "^9",Ð   "psr/cache": "^1.0 || ^2.0 || ^3.0",Ð   "cache/integration-tests": "dev-master",Ð   "symfony/cache": "^4.4 || ^5.4 || ^6",Ð   "symfony/var-exporter": "^4.4 || ^5.4 || ^6"Ð   },Ð   "conflict": {Ð   "doctrine/common": ">2.2,<2.4"Ð   },Ð   "autoload": {Ð   "psr-4": { "Doctrine\\Common\\Cache\\": "lib/Doctrine/Common/Cache" }Ð   },Ð   "autoload-dev": {Ð   "psr-4": { "Doctrine\\Tests\\": "tests/Doctrine/Tests" }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   }Ð   }ÐÐ}

vendor\doctrine\dbal\composer.json

{Ð   "name": "doctrine/dbal",Ð   "type": "library",Ð   "description": "Powerful PHP database abstraction layer (DBAL) with many features for database schema introspection and management.",Ð   "keywords": [Ð "abstraction",Ð   "database",Ð   "dbal",Ð   "db2",Ð "mariadb",Ð   "mssql",Ð   "mysql",Ð   "pgsql",Ð "postgresql",Ð   "oci8",Ð   "oracle",Ð   "pdo",Ð "queryobject",Ð   "sasql",Ð   "sql",Ð   "sqlite",Ð "sqlserver",Ð   "sqlsrv"Ð   ],Ð   "homepage": "https://www.doctrine-project.org/projects/dbal.html",Ð   "license": "MIT",Ð   "authors": [Ð {"name": "Guilherme Blanco", "email": "guilhermeblanco@gmail.com"},Ð {"name": "Roman Borschel", "email": "roman@code-factory.org"},Ð {"name": "Benjamin Eberlei", "email": "kontakt@beberlei.de"},Ð   {"name": "Jonathan Wage", "email": "jonwage@gmail.com"}Ð   ],Ð   "require": {Ð "php": "^7.4 || ^8.0",Ð   "composer-runtime-api": "^2",Ð   "doctrine/cache": "^1.11|^2.0",Ð   "doctrine/deprecations": "^0.5.3|^1",Ð "doctrine/event-manager": "^1|^2",Ð   "psr/cache": "^1|^2|^3",Ð "psr/log": "^1|^2|^3"Ð   },Ð   "require-dev": {Ð   "doctrine/coding-standard": "12.0.0",Ð   "fig/log-test": "^1",Ð   "jetbrains/phpstorm-stubs": "2023.1",Ð   "phpstan/phpstan": "2.1.1",Ð   "phpstan/phpstan-strict-rules": "^2",Ð   "phpunit/phpunit": "9.6.22",Ð   "slevomat/coding-standard": "8.13.1",Ð   "squizlabs/php_codesniffer": "3.10.2",Ð   "symfony/cache": "^5.4|^6.0|^7.0",Ð   "symfony/console": "^4.4|^5.4|^6.0|^7.0"Ð   },Ð   "suggest": {Ð   "symfony/console": "For helpful console commands such as SQL execution and import of files."Ð   },Ð   "bin": ["bin/doctrine-dbal"],Ð   "config": {Ð   "sort-packages": true,Ð "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": true,Ð   "composer/package-versions-deprecated": trueÐ   }Ð   },Ð   "autoload": {Ð   "psr-4": { "Doctrine\\DBAL\\": "src" }Ð   },Ð   "autoload-dev": {Ð   "psr-4": { "Doctrine\\DBAL\\Tests\\": "tests" }Ð   }ÐÐ

vendor\doctrine\deprecations\composer.json

{Ð   "name": "doctrine/deprecations",Ð   "description": "A small layer on top of trigger_error(E_USER_DEPRECATED) or PSR-3 logging with options to disable all deprecations or selectively for packages.",Ð   "license": "MIT",Ð   "type": "library",Ð   "homepage": "https://www.doctrine-project.org/",Ð   "require": {Ð   "php": "^7.1 || ^8.0"Ð   },Ð   "require-dev": {Ð   "doctrine/coding-standard": "^9 || ^12 || ^13",Ð   "phpstan/phpstan": "1.4.10 || 2.1.11",Ð   "phpstan/phpstan-phpunit": "^1.0 || ^2",Ð   "phpunit/phpunit": "^7.5 || ^8.5 || ^9.6 || ^10.5 || ^11.5 || ^12",Ð   "psr/log": "^1 || ^2 || ^3"Ð   },Ð   "conflict": {Ð   "phpunit/phpunit": "<=7.5 || >=13"Ð   },Ð   "suggest": {Ð   "psr/log": "Allows logging deprecations via PSR-3 logger implementation"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Doctrine\\Deprecations\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "DeprecationTests\\": "test_fixtures/src",Ð   "Doctrine\\Foo\\": "test_fixtures/vendor/doctrine/foo"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   }Ð   }Ð}Ð

vendor\doctrine\event-manager\composer.json

{Ð   "name": "doctrine/event-manager",Ð   "description": "The Doctrine Event Manager is a simple PHP event system that was built to be used with the various Doctrine projects.",Ð   "license": "MIT",Ð   "type": "library",Ð   "keywords": [Ð   "events",Ð   "event",Ð   "event dispatcher",Ð   "event manager",Ð   "event system"Ð   ],Ð   "authors": [Ð   {Ð   "name": "Guilherme Blanco",Ð   "email": "guilhermeblanco@gmail.com"Ð   },Ð   {Ð   "name": "Roman Borschel",Ð   "email": "roman@code-factory.org"Ð   },Ð   {Ð   "name": "Benjamin Eberlei",Ð   "email": "kontakt@beberlei.de"Ð   },Ð   {Ð   "name": "Jonathan Wage",Ð   "email": "jonwage@gmail.com"Ð   },Ð   {Ð   "name": "Johannes Schmitt",Ð   "email": "schmittjoh@gmail.com"Ð   },Ð   {Ð   "name": "Marco Pivetta",Ð   "email": "ocramius@gmail.com"Ð   }Ð   ],Ð   "homepage": "https://www.doctrine-project.org/projects/event-manager.html",Ð   "require": {Ð   "php": "^8.1"Ð   },Ð   "require-dev": {Ð   "doctrine/coding-standard": "^12",Ð   "phpstan/phpstan": "^1.8.8",Ð   "phpunit/phpunit": "^10.5",Ð   "vimeo/psalm": "^5.24"Ð   },Ð   "conflict": {Ð   "doctrine/common": "<2.9"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Doctrine\\Common\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Doctrine\\Tests\\Common\\": "tests"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   },Ð   "sort-packages": trueÐ   }Ð}Ð

vendor\doctrine\inflector\composer.json

{Ð   "name": "doctrine/inflector",Ð   "type": "library",Ð   "description": "PHP Doctrine Inflector is a small library that can perform string manipulations with regard to upper/lowercase and singular/plural forms of words.",Ð   "keywords": ["php", "strings", "words", "manipulation", "inflector", "inflection", "uppercase", "lowercase", "singular", "plural"],Ð   "homepage": "https://www.doctrine-project.org/projects/inflector.html",Ð   "license": "MIT",Ð   "authors": [Ð   {"name": "Guilherme Blanco", "email": "guilhermeblanco@gmail.com"},Ð   {"name": "Roman Borschel", "email": "roman@code-factory.org"},Ð   {"name": "Benjamin Eberlei", "email": "kontakt@beberlei.de"},Ð   {"name": "Jonathan Wage", "email": "jonwage@gmail.com"},Ð   {"name": "Johannes Schmitt", "email": "schmittjoh@gmail.com"}Ð   ],Ð   "require": {Ð   "php": "^7.2 || ^8.0"Ð   },Ð   "require-dev": {Ð   "doctrine/coding-standard": "^11.0",Ð   "phpstan/phpstan": "^1.8",Ð   "phpstan/phpstan-phpunit": "^1.1",Ð   "phpstan/phpstan-strict-rules": "^1.3",Ð   "phpunit/phpunit": "^8.5 || ^9.5",Ð   "vimeo/psalm": "^4.25 || ^5.4"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Doctrine\\Inflector\\": "lib/Doctrine/Inflector"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Doctrine\\Tests\\Inflector\\": "tests/Doctrine/Tests/Inflector"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   }Ð   }ÐÐ}

vendor\doctrine\instantiator\.doctrine-project.json


```
{Ð   "active": true,Ð   "name": "Instantiator",Ð   "slug": "instantiator",Ð
"docsSlug": "doctrine-instantiator",Ð   "codePath": "/src",Ð   "versions": [Ð
        {Ð           "name": "1.5",Ð           "branchName": "1.5.x",Ð
            "slug": "latest",Ð           "upcoming": trueÐ       },Ð       {Ð
            "name": "1.4",Ð           "branchName": "1.4.x",Ð
"slug": "1.4",Ð           "aliases": [Ð               "current",Ð
                "stable"Ð           ],Ð           "maintained": true,Ð
            "current": trueÐ       },Ð       {Ð           "name": "1.3",Ð
            "branchName": "1.3.x",Ð           "slug": "1.3",Ð
"maintained": falseÐ       },Ð       {Ð           "name": "1.2",Ð
"branchName": "1.2.x",Ð           "slug": "1.2"Ð       },Ð       {Ð
"name": "1.1",Ð           "branchName": "1.1.x",Ð           "slug": "1.1"Ð
        },Ð       {Ð           "name": "1.0",Ð           "branchName":
"1.0.x",Ð           "slug": "1.0"Ð       }Ð   ]Ð}
```

vendor\doctrine\instantiator\composer.json

{Ð "name": "doctrine/instantiator",Ð "description": "A small, lightweight utility to instantiate objects in PHP without invoking their constructors",Ð "type": "library",Ð "license": "MIT",Ð "homepage": "https://www.doctrine-project.org/projects/instantiator.html",Ð "keywords": [Ð "instantiate",Ð "constructor"Ð],Ð "authors": [Ð {Ð "name": "Marco Pivetta",Ð "email": "ocramius@gmail.com",Ð "homepage": "https://ocramius.github.io/"Ð }Ð],Ð "require": {Ð "php": "^8.1"Ð },Ð "require-dev": {Ð "ext-phar": "*",Ð "ext-pdo": "*",Ð "doctrine/coding-standard": "^11",Ð "phpbench/phpbench": "^1.2",Ð "phpstan/phpstan": "^1.9.4",Ð "phpstan/phpstan-phpunit": "^1.3",Ð "phpunit/phpunit": "^9.5.27",Ð "vimeo/psalm": "^5.4"Ð },Ð "autoload": {Ð "psr-4": {Ð "Doctrine\\Instantiator\\": "src/Doctrine/Instantiator/"Ð }Ð },Ð "autoload-dev": {Ð "psr-0": {Ð "DoctrineTest\\InstantiatorPerformance\\": "tests",Ð "DoctrineTest\\InstantiatorTest\\": "tests",Ð "DoctrineTest\\InstantiatorTestAsset\\": "tests"Ð }Ð },Ð "config": {Ð "allow-plugins": {Ð "dealerdirect/phpcodesniffer-composer-installer": trueÐ }Ð }ÐÐ}

vendor\doctrine\lexer\composer.json

{Ð   "name": "doctrine/lexer",Ð   "description": "PHP Doctrine Lexer parser library that can be used in Top-Down, Recursive Descent Parsers.",Ð   "license": "MIT",Ð   "type": "library",Ð   "keywords": [Ð   "php",Ð   "parser",Ð   "lexer",Ð   "annotations",Ð   "docblock"Ð   ],Ð   "authors": [Ð   {Ð   "name": "Guilherme Blanco",Ð   "email": "guilhermeblanco@gmail.com"Ð   },Ð   {Ð   "name": "Roman Borschel",Ð   "email": "roman@code-factory.org"Ð   },Ð   {Ð   "name": "Johannes Schmitt",Ð   "email": "schmittjoh@gmail.com"Ð   }Ð   ],Ð   "homepage": "https://www.doctrine-project.org/projects/lexer.html",Ð   "require": {Ð   "php": "^8.1"Ð   },Ð   "require-dev": {Ð   "doctrine/coding-standard": "^12",Ð   "phpstan/phpstan": "^1.10",Ð   "phpunit/phpunit": "^10.5",Ð   "psalm/plugin-phpunit": "^0.18.3",Ð   "vimeo/psalm": "^5.21"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Doctrine\\Common\\Lexer\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Doctrine\\Tests\\Common\\Lexer\\": "tests"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "composer/package-versions-deprecated": true,Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   },Ð   "sort-packages": trueÐ   }Ð}

vendor\dompdf\dompdf\composer.json

{Ð   "name": "dompdf/dompdf",Ð   "type": "library",Ð   "description": "DOMPDF is a CSS 2.1 compliant HTML to PDF converter",Ð   "homepage": "https://github.com/dompdf/dompdf",Ð   "license": "LGPL-2.1",Ð   "authors": [Ð   {Ð   "name": "Fabien Ménager",Ð   "email": "fabien.menager@gmail.com"Ð   },Ð   {Ð   "name": "Brian Sweeney",Ð   "email": "eclecticgeek@gmail.com"Ð   },Ð   {Ð   "name": "Gabriel Bull",Ð   "email": "me@gabrielbull.com"Ð   }Ð   ],Ð   "autoload": {Ð   "psr-4": {Ð   "Dompdf\\": "src/"Ð   },Ð   "classmap": [Ð   "lib/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Dompdf\\Tests\\": "tests/"Ð   }Ð   },Ð   "require": {Ð   "php": "^7.1 || ^8.0",Ð   "ext-dom": "*",Ð   "ext-mbstring": "*",Ð   "phenx/php-font-lib": "^0.5.4",Ð   "phenx/php-svg-lib": "^0.3.3 || ^0.4.0"Ð   },Ð   "require-dev": {Ð   "ext-json": "*",Ð   "ext-zip": "*",Ð   "phpunit/phpunit": "^7.5 || ^8 || ^9",Ð   "squizlabs/php_codesniffer": "^3.5",Ð   "mockery/mockery": "^1.3"Ð   },Ð   "suggest": {Ð   "ext-gd": "Needed to process images",Ð   "ext-imagick": "Improves image processing performance",Ð   "ext-gmagick": "Improves image processing performance",Ð   "ext-zlib": "Needed for pdf stream compression"Ð   }Ð}Ð

vendor\dragonmantank\cron-expression\composer.json

{Ð   "name": "dragonmantank/cron-expression",Ð   "type": "library",Ð   "description": "CRON for PHP: Calculate the next or previous run date and determine if a CRON expression is due",Ð   "keywords": ["cron", "schedule"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Chris Tankersley",Ð   "email": "chris@ctankersley.com",Ð   "homepage": "https://github.com/dragonmantank"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2|^8.0",Ð   "webmozart/assert": "^1.0"Ð   },Ð   "require-dev": {Ð   "phpstan/phpstan": "^1.0",Ð   "phpunit/phpunit": "^7.0|^8.0|^9.0",Ð   "phpstan/extension-installer": "^1.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Cron\\": "src/Cron/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Cron\\Tests\\": "tests/Cron/"Ð   }Ð   },Ð   "replace": {Ð   "mtdowling/cron-expression": "^1.0"Ð   },Ð   "scripts": {Ð   "phpstan": "./vendor/bin/phpstan analyze",Ð   "test": "phpunit"Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.x-dev"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "ocramius/package-versions": true,Ð   "phpstan/extension-installer": trueÐ   }Ð   }ÐÐ}

vendor\egulias\email-validator\composer.json

{Ð "name": "egulias/email-validator",Ð "description": "A library for validating emails against several RFCs",Ð "homepage": "https://github.com/egulias/EmailValidator",Ð "keywords": ["email", "validation", "validator", "emailvalidation", "emailvalidator"],Ð "license": "MIT",Ð "authors": [Ð {"name": "Eduardo Gulias Davis"}Ð],Ð "extra": {Ð "branch-alias": {Ð "dev-master": "4.0.x-dev"Ð }Ð },Ð "require": {Ð "php": ">=8.1",Ð "doctrine/lexer": "^2.0 || ^3.0",Ð "symfony/polyfill-intl-idn": "^1.26"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^10.2",Ð "vimeo/psalm": "^5.12"Ð },Ð "suggest": {Ð "ext-intl": "PHP Internationalization Libraries are required to use the SpoofChecking validation"Ð },Ð "autoload": {Ð "psr-4": {Ð "Egulias\\EmailValidator\\": "src"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Egulias\\EmailValidator\\Tests\\": "tests"Ð }Ð }Ð }Ð

vendor\fakerphp\faker\composer.json

{Ð   "name": "fakerphp/faker",Ð   "type": "library",Ð   "description": "Faker is a PHP library that generates fake data for you.",Ð   "keywords": [Ð "faker",Ð   "fixtures",Ð   "data"Ð   ],Ð   "license": "MIT",Ð "authors": [Ð   {Ð   "name": "François Zaninotto"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.4 || ^8.0",Ð   "psr/container": "^1.0 || ^2.0",Ð   "symfony/deprecation-contracts": "^2.2 || ^3.0"Ð   },Ð "require-dev": {Ð   "ext-intl": "*",Ð   "bamarni/composer-bin-plugin": "^1.4.1",Ð   "doctrine/persistence": "^1.3 || ^2.0",Ð "phpunit/phpunit": "^9.5.26",Ð   "symfony/phpunit-bridge": "^5.4.16"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Faker\\": "src/Faker/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Faker\\Test\\": "test/Faker/",Ð   "Faker\\Test\\Fixture\\": "test/Fixture/"Ð   }Ð   },Ð   "conflict": {Ð   "fzaninotto/faker": "*"Ð   },Ð "suggest": {Ð   "ext-curl": "Required by Faker\\Provider\\Image to download images.",Ð   "ext-dom": "Required by Faker\\Provider\\HtmlLorem for generating random HTML.",Ð   "ext-iconv": "Required by Faker\\Provider\\ru_RU\\Text::realText() for generating real Russian text.",Ð "ext-mbstring": "Required for multibyte Unicode string functionality.",Ð   "doctrine/orm": "Required to use Faker\\ORM\\Doctrine"Ð   },Ð "config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-plugin": true,Ð   "composer/package-versions-deprecated": trueÐ   },Ð   "sort-packages": trueÐ   }}ÐÐ

vendor\filp\whoops\composer.json

{Đ   "name": "filp/whoops",Đ   "license": "MIT",Đ   "description": "php error handling for cool kids",Đ   "keywords": ["library", "error", "handling", "exception", "whoops", "throwable"],Đ   "homepage": "https://filp.github.io/whoops/",Đ   "authors": [Đ   {Đ   "name": "Filipe Dobreira",Đ   "homepage": "https://github.com/filp",Đ   "role": "Developer"Đ   }Đ   ],Đ   "scripts": {Đ   "test": "phpunit --testdox tests"Đ   },Đ   "require": {Đ   "php": "^7.1 || ^8.0",Đ   "psr/log": "^1.0.1 || ^2.0 || ^3.0"Đ   },Đ   "require-dev": {Đ   "phpunit/phpunit": "^7.5.20 || ^8.5.8 || ^9.3.3",Đ   "mockery/mockery": "^1.0",Đ   "symfony/var-dumper": "^4.0 || ^5.0"Đ   },Đ   "suggest": {Đ   "symfony/var-dumper": "Pretty print complex values better with var-dumper available",Đ   "whoops/soap": "Formats errors as SOAP responses"Đ   },Đ   "autoload": {Đ   "psr-4": {Đ   "Whoops\\": "src/Whoops/"Đ   }Đ   },Đ   "autoload-dev": {Đ   "psr-4": {Đ   "Whoops\\": "tests/Whoops/"Đ   }Đ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "2.7-dev"Đ   }Đ   }Đ}

vendor\fruitcake\php-cors\composer.json

{Ð   "name": "fruitcake/php-cors",Ð   "description": "Cross-origin resource sharing library for the Symfony HttpFoundation",Ð   "keywords": ["cors", "symfony", "laravel"],Ð   "homepage": "https://github.com/fruitcake/php-cors",Ð   "type": "library",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fruitcake",Ð   "homepage": "https://fruitcake.nl"Ð   },Ð   {Ð   "name": "Barryvdh",Ð   "email": "barryvdh@gmail.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.4|^8.0",Ð   "symfony/http-foundation": "^4.4|^5.4|^6|^7"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9",Ð   "squizlabs/php_codesniffer": "^3.5",Ð   "phpstan/phpstan": "^1.4"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Fruitcake\\Cors\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Fruitcake\\Cors\\Tests\\": "tests/"Ð   }Ð   },Ð   "scripts": {Ð   "actions": "composer test && composer analyse && composer check-style",Ð   "test": "phpunit",Ð   "analyse": "phpstan analyse src tests --level=9",Ð   "check-style": "phpcs -p --standard=PSR12 --exclude=Generic.Files.LineLength --runtime-set ignore_errors_on_exit 1 --runtime-set ignore_warnings_on_exit 1 src tests",Ð   "fix-style": "phpcbf -p --standard=PSR12 --exclude=Generic.Files.LineLength --runtime-set ignore_errors_on_exit 1 --runtime-set ignore_warnings_on_exit 1 src tests"Ð   },Ð   "extra": {Ð "branch-alias": {Ð   "dev-master": "1.2-dev"Ð   }Ð   }Ð}ÐÐ

vendor\graham-campbell\result-type\composer.json

{Ð   "name": "graham-campbell/result-type",Ð   "description": "An Implementation Of The Result Type",Ð   "keywords": ["result", "result-type", "Result", "Result Type", "Result-Type", "Graham Campbell", "GrahamCampbell"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5 || ^8.0",Ð   "phpoption/phpoption": "^1.9.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^8.5.39 || ^9.6.20 || ^10.5.28"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "GrahamCampbell\\ResultType\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "GrahamCampbell\\Tests\\ResultType\\": "tests/"Ð   }Ð   },Ð   "config": {Ð   "preferred-install": "dist"Ð   }Ð}

vendor\guzzlehttp\guzzle\composer.json

{Ð   "name": "guzzlehttp/guzzle",Ð   "description": "Guzzle is a PHP HTTP client library",Ð   "keywords": [Ð   "framework",Ð   "http",Ð   "rest",Ð   "web service",Ð   "curl",Ð   "client",Ð   "HTTP client",Ð   "PSR-7",Ð   "PSR-18"Ð   ],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   },Ð   {Ð   "name": "Michael Dowling",Ð   "email": "mtdowling@gmail.com",Ð   "homepage": "https://github.com/mtdowling"Ð   },Ð   {Ð   "name": "Jeremy Lindblom",Ð   "email": "jeremeamia@gmail.com",Ð   "homepage": "https://github.com/jeremeamia"Ð   },Ð   {Ð   "name": "George Mponos",Ð   "email": "gmponos@gmail.com",Ð   "homepage": "https://github.com/gmponos"Ð   },Ð   {Ð   "name": "Tobias Nyholm",Ð   "email": "tobias.nyholm@gmail.com",Ð   "homepage": "https://github.com/Nyholm"Ð   },Ð   {Ð   "name": "Márk Sági-Kazár",Ð   "email": "mark.sagikazar@gmail.com",Ð   "homepage": "https://github.com/sagikazarmark"Ð   },Ð   {Ð   "name": "Tobias Schultze",Ð   "email": "webmaster@tubo-world.de",Ð   "homepage": "https://github.com/Tobion"Ð   }Ð   ],Ð   "repositories": [Ð   {Ð   "type": "package",Ð   "package": {Ð   "name": "guzzle/client-integration-tests",Ð   "version": "v3.0.2",Ð   "dist": {Ð   "url": "https://codeload.github.com/guzzle/client-integration-tests/zip/2c025848417c1135031fdf9c728ee53d0a7ceaee",Ð   "type": "zip"Ð   },Ð   "require": {Ð   "php": "^7.2.5 || ^8.0",Ð   "phpunit/phpunit": "^7.5.20 || ^8.5.8 || ^9.3.11",Ð   "php-http/message": "^1.0 || ^2.0",Ð   "guzzlehttp/psr7": "^1.7 || ^2.0",Ð   "th3n3rd/cartesian-product": "^0.3"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Http\\Client\\Tests\\": "src/"Ð   }Ð   },Ð   "bin": [Ð   "bin/http_test_server"Ð   ]Ð   }Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5 || ^8.0",Ð   "ext-json": "*",Ð   "guzzlehttp/promises": "^1.5.3 || ^2.0.3",Ð   "guzzlehttp/psr7": "^2.7.0",Ð   "psr/http-client": "^1.0",Ð   "symfony/deprecation-contracts": "^2.2 || ^3.0"Ð   },Ð   "provide": {Ð   "psr/http-client-implementation": "1.0"Ð   },Ð   "require-dev": {Ð   "ext-curl": "*",Ð   "bamarni/composer-bin-plugin": "^1.8.2",Ð   "guzzle/client-integration-tests": "3.0.2",Ð   "php-http/message-factory": "^1.1",Ð   "phpunit/phpunit": "^8.5.39 || ^9.6.20",Ð   "psr/log": "^1.1 || ^2.0 || ^3.0"Ð   },Ð   "suggest": {Ð   "ext-curl": "Required for CURL handler support",Ð   "ext-intl": "Required for Internationalized Domain Name (IDN) support",Ð   "psr/log": "Required for using the Log middleware"Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-plugin": trueÐ   },Ð   "preferred-install": "dist",Ð   "sort-packages": trueÐ   },Ð   "extra": {Ð   "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-command": falseÐ   }Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "GuzzleHttp\\": "src/"Ð   },Ð   "files": [Ð   "src/functions_include.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "GuzzleHttp\\Tests\\": "tests/"Ð   }Ð   }Ð}Ð

vendor\guzzlehttp\promises\composer.json

{Ð   "name": "guzzlehttp/promises",Ð   "description": "Guzzle promises library",Ð   "keywords": ["promise"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   },Ð   {Ð   "name": "Michael Dowling",Ð   "email": "mtdowling@gmail.com",Ð   "homepage": "https://github.com/mtdowling"Ð   },Ð   {Ð   "name": "Tobias Nyholm",Ð   "email": "tobias.nyholm@gmail.com",Ð   "homepage": "https://github.com/Nyholm"Ð   },Ð   {Ð   "name": "Tobias Schultze",Ð   "email": "webmaster@tubo-world.de",Ð   "homepage": "https://github.com/Tobion"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5 || ^8.0"Ð   },Ð   "require-dev": {Ð   "bamarni/composer-bin-plugin": "^1.8.2",Ð   "phpunit/phpunit": "^8.5.39 || ^9.6.20"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "GuzzleHttp\\Promise\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "GuzzleHttp\\Promise\\Tests\\": "tests/"Ð   }Ð   },Ð   "extra": {Ð   "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-command": falseÐ   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-plugin": trueÐ   },Ð   "preferred-install": "dist",Ð   "sort-packages": trueÐ   }Ð}Ð

vendor\guzzlehttp\psr7\composer.json

{Ð   "name": "guzzlehttp/psr7",Ð   "description": "PSR-7 message implementation that also provides common utility methods",Ð   "keywords": [Ð   "request",Ð   "response",Ð   "message",Ð   "stream",Ð   "http",Ð   "uri",Ð   "url",Ð   "psr-7"Ð   ],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   },Ð   {Ð   "name": "Michael Dowling",Ð   "email": "mtdowling@gmail.com",Ð   "homepage": "https://github.com/mtdowling"Ð   },Ð   {Ð   "name": "George Mponos",Ð   "email": "gmponos@gmail.com",Ð   "homepage": "https://github.com/gmponos"Ð   },Ð   {Ð   "name": "Tobias Nyholm",Ð   "email": "tobias.nyholm@gmail.com",Ð   "homepage": "https://github.com/Nyholm"Ð   },Ð   {Ð   "name": "Márk Sági-Kazár",Ð   "email": "mark.sagikazar@gmail.com",Ð   "homepage": "https://github.com/sagikazarmark"Ð   },Ð   {Ð   "name": "Tobias Schultze",Ð   "email": "webmaster@tubo-world.de",Ð   "homepage": "https://github.com/Tobion"Ð   },Ð   {Ð   "name": "Márk Sági-Kazár",Ð   "email": "mark.sagikazar@gmail.com",Ð   "homepage": "https://sagikazarmark.hu"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5 || ^8.0",Ð   "psr/http-factory": "^1.0",Ð   "psr/http-message": "^1.1 || ^2.0",Ð   "ralouphie/getallheaders": "^3.0"Ð   },Ð   "provide": {Ð   "psr/http-factory-implementation": "1.0",Ð   "psr/http-message-implementation": "1.0"Ð   },Ð   "require-dev": {Ð   "bamarni/composer-bin-plugin": "^1.8.2",Ð   "http-interop/http-factory-tests": "0.9.0",Ð   "phpunit/phpunit": "^8.5.39 || ^9.6.20"Ð   },Ð   "suggest": {Ð   "laminas/laminas-httphandlerrunner": "Emit PSR-7 responses"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "GuzzleHttp\\Psr7\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "GuzzleHttp\\Tests\\Psr7\\": "tests/"Ð   }Ð   },Ð   "extra": {Ð   "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-command": falseÐ   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-plugin": trueÐ   },Ð   "preferred-install": "dist",Ð   "sort-packages": trueÐ   }Ð}Ð

vendor\guzzlehttp\uri-template\composer.json

{Ð   "name": "guzzlehttp/uri-template",Ð   "description": "A polyfill class for uri_template of PHP",Ð   "keywords": [Ð   "guzzlehttp",Ð   "uri-template"Ð   ],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   },Ð   {Ð   "name": "Michael Dowling",Ð   "email": "mtdowling@gmail.com",Ð   "homepage": "https://github.com/mtdowling"Ð   },Ð   {Ð   "name": "George Mponos",Ð   "email": "gmponos@gmail.com",Ð   "homepage": "https://github.com/gmponos"Ð   },Ð   {Ð   "name": "Tobias Nyholm",Ð   "email": "tobias.nyholm@gmail.com",Ð   "homepage": "https://github.com/Nyholm"Ð   }Ð   ],Ð   "repositories": [Ð   {Ð   "type": "package",Ð   "package": {Ð   "name": "uri-template/tests",Ð   "version": "1.0.0",Ð   "dist": {Ð   "url": "https://github.com/uri-templates/uritemplate-test/archive/520fdd8b0f78779d12178c357a986e0e727f4bd0.zip",Ð "type": "zip"Ð   }Ð   }Ð   }Ð   ],Ð   "require": {Ð   "php" : "^7.2.5 || ^8.0",Ð   "symfony/polyfill-php80": "^1.24"Ð   },Ð   "require-dev": {Ð   "bamarni/composer-bin-plugin": "^1.8.2",Ð   "phpunit/phpunit" : "^8.5.36 || ^9.6.15",Ð   "uri-template/tests": "1.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð "GuzzleHttp\\UriTemplate\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð "psr-4": {Ð   "GuzzleHttp\\UriTemplate\\Tests\\": "tests"Ð   }Ð   },Ð   "extra": {Ð   "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-command": falseÐ   }Ð   },Ð   "config": {Ð "allow-plugins": {Ð   "bamarni/composer-bin-plugin": trueÐ   },Ð   "preferred-install": "dist",Ð   "sort-packages": trueÐ   }}ÐÐ

vendor\hamcrest\hamcrest-php\composer.json

{Ð&æ ÖR#¢ &† Ö7&W7Bö† Ö7&W7B× ‡ "Í'G— R#¢ &Æ–'& ''"Í&FW67&— F–öâ#¢ %F†—2 —2
the PHP port of Hamcrest Matchers",Ð&¶W—v÷&G2#¢ ²'FW7B%ÒÍ&Æ–6Vç6R#¢ $%4BÓ2Ð
Clause",Ð& WF†÷'2#¢ ½ÒÍ& WFöÆö B#¢ ™"classmap": ["hamcrest"]ÐÍ& WFöÆö BÖFWb#¢ ½
™"classmap": ["tests", "generator"]ÐÍ'&W V—&R#¢ ™"php": "^7.4|^8.0"ÐÍ'&W V—&RÐ
dev": {Ð"phpunit/php-file-iterator": "^1.4 || ^2.0 || ^3.0",Ð"phpunit/phpunit":
"^4.8.36 || ^5.7 || ^6.5 || ^7.0 || ^8.0 || ^9.0"ÐÒÍ'&W Æ 6R#¢ ™"kodova/
hamcrest-php": "*",Ð"davedevelopment/hamcrest-php": "*",Ð"cordoval/hamcrest-
php": "*"ÐÒÍ   "extra": {Ð   "branch-alias": {Ð   "dev-master":
"2.1-dev"Ð   }Ð   }ÐÐ

vendor\intervention\image\composer.json

{Ð   "name": "intervention/image",Ð   "description": "Image handling and manipulation library with support for Laravel integration",Ð   "homepage": "http://image.intervention.io/",Ð   "keywords": ["image", "gd", "imagick", "laravel", "watermark", "thumbnail"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Oliver Vogel",Ð   "email": "oliver@intervention.io",Ð   "homepage": "https://intervention.io/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=5.4.0",Ð   "ext-fileinfo": "*",Ð   "guzzlehttp/psr7": "~1.1 || ^2.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^4.8 || ^5.7 || ^7.5.15",Ð   "mockery/mockery": "~0.9.2"Ð   },Ð   "suggest": {Ð   "ext-gd": "to use GD library based image processing.",Ð   "ext-imagick": "to use Imagick based image processing.",Ð   "intervention/imagecache": "Caching extension for the Intervention Image library"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Intervention\\Image\\": "src/Intervention/Image"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "2.4-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "Intervention\\Image\\ImageServiceProvider"Ð   ],Ð   "aliases": {Ð   "Image": "Intervention\\Image\\Facades\\Image"Ð   }Ð   }Ð   },Ð   "minimum-stability": "stable"ÐÐ}

vendor\intervention\image\provides.json

```
{  "providers": [    "Intervention\\Image\\ImageServiceProvider"  ],
"aliases": [    {      "alias": "Image",      "facade": "Intervention\\Image\
\Facades\\Image"    }  ]}
```

vendor\kitloong\laravel-migrations-generator\composer.json

{Ð   "name": "kitloong/laravel-migrations-generator",Ð   "description": "Generates Laravel Migrations from an existing database",Ð   "keywords": [Ð   "laravel",Ð   "lumen",Ð   "migration",Ð   "generator",Ð   "migrations",Ð   "artisan"Ð   ],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Kit Loong",Ð   "email": "kitloong1008@gmail.com"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.1.3",Ð   "illuminate/support": "^5.6|^6.0|^7.0|^8.0|^9.0|^10.0",Ð   "doctrine/dbal": "^2.4|^3.0",Ð   "myclabs/php-enum": "^1.6|^1.7|^1.8",Ð   "ext-pdo": "*"Ð   },Ð   "require-dev": {Ð   "orchestra/testbench": "^3.6|^4.0|^5.0|^6.0|^7.0|^8.0",Ð   "squizlabs/php_codesniffer": "^3.5",Ð   "mockery/mockery": "^1.0",Ð   "friendsofphp/php-cs-fixer": "^2.19.0|^3.1",Ð   "larastan/larastan": "^0.4|^0.5|^0.6|^0.7|^1.0|^2.0",Ð   "phpmd/phpmd": "^2.10",Ð   "barryvdh/laravel-ide-helper": "^2.5",Ð   "slevomat/coding-standard": "^6.0|^7.0|^8.5"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "KitLoong\\MigrationsGenerator\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "KitLoong\\MigrationsGenerator\\Tests\\": "tests"Ð   }Ð   },Ð   "extra": {Ð   "laravel": {Ð   "providers": [Ð   "KitLoong\\MigrationsGenerator\\MigrationsGeneratorServiceProvider"Ð   ]Ð   }Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "scripts": {Ð   "action-env-setup": [Ð   "@php -r \"file_exists('.env') || copy('.env.action', '.env');\""Ð   ],Ð   "phpcs": [Ð   "phpcs"Ð   ],Ð   "phpmd": [Ð   "phpmd \"src,tests\" xml .phpmd.xml"Ð   ],Ð   "phpstan": [Ð   "phpstan analyse"Ð   ]Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   }Ð   }Ð}Ð

vendor\laravel\breeze\composer.json

{Ð   "name": "laravel/breeze",Ð   "description": "Minimal Laravel authentication scaffolding with Blade and Tailwind.",Ð   "keywords": ["laravel", "auth"],Ð   "license": "MIT",Ð   "support": {Ð   "issues": "https://github.com/laravel/breeze/issues",Ð   "source": "https://github.com/laravel/breeze"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/console": "^9.21|^10.0",Ð   "illuminate/filesystem": "^9.21|^10.0",Ð   "illuminate/support": "^9.21|^10.0",Ð   "illuminate/validation": "^9.21|^10.0"Ð   },Ð   "conflict": {Ð   "laravel/framework": "<9.37.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\Breeze\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.x-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "Laravel\\Breeze\\BreezeServiceProvider"Ð   ]Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐÐ

vendor\laravel\breeze\stubs\inertia-common\jsconfig.json

```
{Ð   "compilerOptions": {Ð       "baseUrl": ".",Ð       "paths": {Ð
"@/*": ["resources/js/*"]Ð       }Ð   },Ð   "exclude": ["node_modules",
"public"]ÐÐ
}
```

vendor\laravel\framework\composer.json

{Ð   "name": "laravel/framework",Ð   "description": "The Laravel Framework.",Ð
    "keywords": ["framework", "laravel"],Ð   "license": "MIT",Ð   "homepage":
"https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/
laravel/framework/issues",Ð   "source": "https://github.com/laravel/
framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð
            "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð
        "php": "^8.0.2",Ð   "ext-ctype": "*",Ð   "ext-filter": "*",Ð
        "ext-hash": "*",Ð   "ext-mbstring": "*",Ð   "ext-openssl":
"*",Ð   "ext-session": "*",Ð   "ext-tokenizer": "*",Ð   "brick/
math": "^0.9.3|^0.10.2|^0.11",Ð   "doctrine/inflector": "^2.0.5",Ð
"dragonmantank/cron-expression": "^3.3.2",Ð   "egulias/email-validator":
"^3.2.1|^4.0",Ð   "fruitcake/php-cors": "^1.2",Ð   "guzzlehttp/uri-
template": "^1.0",Ð   "laravel/serializable-closure": "^1.2.2",Ð
"league/commonmark": "^2.2.1",Ð   "league/flysystem": "^3.8.0",Ð
"monolog/monolog": "^2.0",Ð   "nesbot/carbon": "^2.62.1",Ð
"nunomaduro/termwind": "^1.13",Ð   "psr/container": "^1.1.1|^2.0.1",Ð
        "psr/log": "^1.0|^2.0|^3.0",Ð   "psr/simple-cache": "^1.0|^2.0|
^3.0",Ð   "ramsey/uuid": "^4.7",Ð   "symfony/console": "^6.0.9",Ð
        "symfony/error-handler": "^6.0",Ð   "symfony/finder": "^6.0",Ð
        "symfony/http-foundation": "^6.0",Ð   "symfony/http-kernel":
"^6.0",Ð   "symfony/mailer": "^6.0",Ð   "symfony/mime": "^6.0",Ð
        "symfony/process": "^6.0",Ð   "symfony/routing": "^6.0",Ð
"symfony/uid": "^6.0",Ð   "symfony/var-dumper": "^6.0",Ð
"tijsverkoyen/css-to-inline-styles": "^2.2.5",Ð   "vlucas/phpdotenv":
"^5.4.1",Ð   "voku/portable-ascii": "^2.0"Ð   },Ð   "replace": {Ð
"illuminate/auth": "self.version",Ð   "illuminate/broadcasting":
"self.version",Ð   "illuminate/bus": "self.version",Ð   "illuminate/
cache": "self.version",Ð   "illuminate/collections": "self.version",Ð
        "illuminate/conditionable": "self.version",Ð   "illuminate/
config": "self.version",Ð   "illuminate/console": "self.version",Ð
"illuminate/container": "self.version",Ð   "illuminate/contracts":
"self.version",Ð   "illuminate/cookie": "self.version",Ð
"illuminate/database": "self.version",Ð   "illuminate/encryption":
"self.version",Ð   "illuminate/events": "self.version",Ð
"illuminate/filesystem": "self.version",Ð   "illuminate/hashing":
"self.version",Ð   "illuminate/http": "self.version",Ð   "illuminate/
log": "self.version",Ð   "illuminate/macroable": "self.version",Ð
"illuminate/mail": "self.version",Ð   "illuminate/notifications":
"self.version",Ð   "illuminate/pagination": "self.version",Ð
"illuminate/pipeline": "self.version",Ð   "illuminate/queue":
"self.version",Ð   "illuminate/redis": "self.version",Ð   "illuminate/
routing": "self.version",Ð   "illuminate/session": "self.version",Ð
"illuminate/support": "self.version",Ð   "illuminate/testing":
"self.version",Ð   "illuminate/translation": "self.version",Ð
"illuminate/validation": "self.version",Ð   "illuminate/view":
"self.version"Ð   },Ð   "require-dev": {Ð   "ext-gmp": "*",Ð   "ably/
ably-php": "^1.0",Ð   "aws/aws-sdk-php": "^3.235.5",Ð   "doctrine/
dbal": "^2.13.3|^3.1.4",Ð   "fakerphp/faker": "^1.21",Ð   "guzzlehttp/
guzzle": "^7.5",Ð   "league/flysystem-aws-s3-v3": "^3.0",Ð   "league/
flysystem-ftp": "^3.0",Ð   "league/flysystem-path-prefixing": "^3.3",Ð
        "league/flysystem-read-only": "^3.3",Ð   "league/flysystem-sftp-
v3": "^3.0",Ð   "mockery/mockery": "^1.5.1",Ð   "orchestra/testbench-
core": "^7.24",Ð   "pda/pheanstalk": "^4.0",Ð   "phpstan/phpdoc-
parser": "^1.15",Ð   "phpstan/phpstan": "^1.4.7",Ð   "phpunit/
phpunit": "^9.5.8",Ð   "predis/predis": "^1.1.9|^2.0.2",Ð   "symfony/
cache": "^6.0",Ð   "symfony/http-client": "^6.0"Ð   },Ð   "provide": {Ð
        "psr/container-implementation": "1.1|2.0",Ð   "psr/simple-cache-
implementation": "1.0|2.0|3.0"Ð   },Ð   "conflict": {Ð   "tightenco/
collect": "<5.5.33"Ð

},Đ "autoload": {Đ "files": [Đ "src/Illuminate/Collections/helpers.php",Đ "src/Illuminate/Events/functions.php",Đ "src/Illuminate/Foundation/helpers.php",Đ "src/Illuminate/Support/helpers.php"Đ],Đ "psr-4": {Đ "Illuminate\\": "src/Illuminate/",Đ "Illuminate\\Support\\": [Đ "src/Illuminate/Macroable/",Đ "src/Illuminate/Collections/",Đ "src/Illuminate/Conditionable/"Đ]Đ }Đ },Đ "autoload-dev": {Đ "files": [Đ "tests/Database/stubs/MigrationCreatorFakeMigration.php"Đ],Đ "psr-4": {Đ "Illuminate\\Tests\\": "tests/"Đ }Đ },Đ "extra": {Đ "branch-alias": {Đ "dev-master": "9.x-dev"Đ }Đ },Đ "suggest": {Đ "ext-apcu": "Required to use the APC cache driver.",Đ "ext-fileinfo": "Required to use the Filesystem class.",Đ "ext-ftp": "Required to use the Flysystem FTP driver.",Đ "ext-gd": "Required to use Illuminate\\Http\\Testing\\FileFactory::image().",Đ "ext-memcached": "Required to use the memcache cache driver.",Đ "ext-pcntl": "Required to use all features of the queue worker and console signal trapping.",Đ "ext-pdo": "Required to use all database features.",Đ "ext-posix": "Required to use all features of the queue worker.",Đ "ext-redis": "Required to use the Redis cache and queue drivers (^4.0|^5.0).",Đ "ably/ably-php": "Required to use the Ably broadcast driver (^1.0).",Đ "aws/aws-sdk-php": "Required to use the SQS queue driver, DynamoDb failed job storage, and SES mail driver (^3.235.5).",Đ "brianium/paratest": "Required to run tests in parallel (^6.0).",Đ "doctrine/dbal": "Required to rename columns and drop SQLite columns (^2.13.3|^3.1.4).",Đ "fakerphp/faker": "Required to use the eloquent factory builder (^1.9.1).",Đ "filp/whoops": "Required for friendly error pages in development (^2.14.3).",Đ "guzzlehttp/guzzle": "Required to use the HTTP Client and the ping methods on schedules (^7.5).",Đ "laravel/tinker": "Required to use the tinker console command (^2.0).",Đ "league/flysystem-aws-s3-v3": "Required to use the Flysystem S3 driver (^3.0).",Đ "league/flysystem-ftp": "Required to use the Flysystem FTP driver (^3.0).",Đ "league/flysystem-path-prefixing": "Required to use the scoped driver (^3.3).",Đ "league/flysystem-read-only": "Required to use read-only disks (^3.3)",Đ "league/flysystem-sftp-v3": "Required to use the Flysystem SFTP driver (^3.0).",Đ "mockery/mockery": "Required to use mocking (^1.5.1).",Đ "nyholm/psr7": "Required to use PSR-7 bridging features (^1.2).",Đ "pda/pheanstalk": "Required to use the beanstalk queue driver (^4.0).",Đ "phpunit/phpunit": "Required to use assertions and run tests (^9.5.8).",Đ "predis/predis": "Required to use the predis connector (^1.1.9|^2.0.2).",Đ "psr/http-message": "Required to allow Storage::put to accept a StreamInterface (^1.0).",Đ "pusher/pusher-php-server": "Required to use the Pusher broadcast driver (^6.0|^7.0).",Đ "symfony/cache": "Required to PSR-6 cache bridge (^6.0).",Đ "symfony/filesystem": "Required to enable support for relative symbolic links (^6.0).",Đ "symfony/http-client": "Required to enable support for the Symfony API mail transports (^6.0).",Đ "symfony/mailgun-mailer": "Required to enable support for the Mailgun mail transport (^6.0).",Đ "symfony/postmark-mailer": "Required to enable support for the Postmark mail transport (^6.0).",Đ "symfony/psr-http-message-bridge": "Required to use PSR-7 bridging features (^2.0)."Đ },Đ "config": {Đ "sort-packages": true,Đ "allow-plugins": {Đ "composer/package-versions-deprecated": trueĐ }Đ },Đ "minimum-stability": "stable",Đ "prefer-stable": trueĐ }Đ

vendor\laravel\framework\src\Illuminate\Auth\composer.json

{Ð   "name": "illuminate/auth",Ð   "description": "The Illuminate Auth package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-hash": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/http": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/queue": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Auth\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/console": "Required to use the auth:clear-resets command (^9.0).",Ð   "illuminate/queue": "Required to fire login / logout events (^9.0).",Ð   "illuminate/session": "Required to use the session based guard (^9.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}ÐÐ

vendor\laravel\framework\src\Illuminate\Broadcasting\composer.json

{Ð   "name": "illuminate/broadcasting",Ð   "description": "The Illuminate Broadcasting package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "psr/log": "^1.0|^2.0|^3.0",Ð   "illuminate/bus": "^9.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/queue": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Broadcasting\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "ext-hash": "Required to use the Ably and Pusher broadcast drivers.",Ð   "ably/ably-php": "Required to use the Ably broadcast driver (^1.0).",Ð   "pusher/pusher-php-server": "Required to use the Pusher broadcast driver (^6.0|^7.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}ÐÐ

vendor\laravel\framework\src\Illuminate\Bus\composer.json

{Ð   "name": "illuminate/bus",Ð   "description": "The Illuminate Bus package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/pipeline": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Bus\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/queue": "Required to use closures when chaining jobs (^7.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Cache\composer.json


```
{Ð   "name": "illuminate/cache",Ð   "description": "The Illuminate Cache
package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð
"support": {Ð       "issues": "https://github.com/laravel/framework/issues",Ð
        "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð
        {Ð           "name": "Taylor Otwell",Ð           "email":
"taylor@laravel.com"Ð       }Ð   ],Ð   "require": {Ð       "php": "^8.0.2",Ð
        "illuminate/collections": "^9.0",Ð       "illuminate/contracts":
"^9.0",Ð       "illuminate/macroable": "^9.0",Ð       "illuminate/support":
"^9.0"Ð   },Ð   "provide": {Ð       "psr/simple-cache-implementation": "1.0|
2.0|3.0"Ð   },Ð   "autoload": {Ð       "psr-4": {Ð           "Illuminate\
\Cache\\": ""Ð       }Ð   },Ð   "extra": {Ð       "branch-alias": {Ð
            "dev-master": "9.x-dev"Ð       }Ð   },Ð   "suggest": {Ð
"ext-apcu": "Required to use the APC cache driver.",Ð       "ext-filter":
"Required to use the DynamoDb cache driver.",Ð       "ext-memcached":
"Required to use the memcache cache driver.",Ð       "illuminate/database":
"Required to use the database cache driver (^9.0).",Ð       "illuminate/
filesystem": "Required to use the file cache driver (^9.0).",Ð
"illuminate/redis": "Required to use the redis cache driver (^9.0).",Ð
"symfony/cache": "Required to use PSR-6 cache bridge (^6.0)."Ð   },Ð
"config": {Ð       "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð
```

vendor\laravel\framework\src\Illuminate\Collections\composer.json

{Ð   "name": "illuminate/collections",Ð   "description": "The Illuminate Collections package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/conditionable": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Support\\": ""Ð   },Ð   "files": [Ð   "helpers.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "symfony/var-dumper": "Required to use the dump method (^6.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"ÐÐ}

vendor\laravel\framework\src\Illuminate\Conditionable\composer.json

{Ð   "name": "illuminate/conditionable",Ð   "description": "The Illuminate Conditionable package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Support\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}

vendor\laravel\framework\src\Illuminate\Config\composer.json

{Ð   "name": "illuminate/config",Ð   "description": "The Illuminate Config package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Config\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Console\composer.json

{Ð   "name": "illuminate/console",Ð   "description": "The Illuminate Console package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-mbstring": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "illuminate/view": "^9.0",Ð   "nunomaduro/termwind": "^1.13",Ð   "symfony/console": "^6.0.9",Ð   "symfony/process": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Console\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "ext-pcntl": "Required to use signal trapping.",Ð   "dragonmantank/cron-expression": "Required to use scheduler (^3.3.2).",Ð   "guzzlehttp/guzzle": "Required to use the ping methods on schedules (^7.5).",Ð   "illuminate/bus": "Required to use the scheduled job dispatcher (^9.0).",Ð   "illuminate/container": "Required to use the scheduler (^9.0).",Ð   "illuminate/filesystem": "Required to use the generator command (^9.0).",Ð   "illuminate/queue": "Required to use closures for scheduled jobs (^9.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Container\composer.json

{Ð   "name": "illuminate/container",Ð   "description": "The Illuminate Container package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/contracts": "^9.0",Ð   "psr/container": "^1.1.1|^2.0.1"Ð   },Ð   "provide": {Ð   "psr/container-implementation": "1.1|2.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Container\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Contracts\composer.json

{Ð   "name": "illuminate/contracts",Ð   "description": "The Illuminate Contracts package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "psr/container": "^1.1.1|^2.0.1",Ð   "psr/simple-cache": "^1.0|^2.0|^3.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Contracts\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Cookie\composer.json

{Đ   "name": "illuminate/cookie",Đ   "description": "The Illuminate Cookie package.",Đ   "license": "MIT",Đ   "homepage": "https://laravel.com",Đ   "support": {Đ   "issues": "https://github.com/laravel/framework/issues",Đ   "source": "https://github.com/laravel/framework"Đ   },Đ   "authors": [Đ   {Đ   "name": "Taylor Otwell",Đ   "email": "taylor@laravel.com"Đ   }Đ   ],Đ   "require": {Đ   "php": "^8.0.2",Đ   "ext-hash": "*",Đ   "illuminate/collections": "^9.0",Đ   "illuminate/contracts": "^9.0",Đ   "illuminate/macroable": "^9.0",Đ   "illuminate/support": "^9.0",Đ   "symfony/http-foundation": "^6.0",Đ   "symfony/http-kernel": "^6.0"Đ   },Đ   "autoload": {Đ   "psr-4": {Đ   "Illuminate\\Cookie\\": ""Đ   }Đ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "9.x-dev"Đ   }Đ   },Đ   "config": {Đ   "sort-packages": trueĐ   },Đ   "minimum-stability": "dev"Đ}Đ

vendor\laravel\framework\src\Illuminate\Database\composer.json

{Ð   "name": "illuminate/database",Ð   "description": "The Illuminate Database package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "keywords": ["laravel", "database", "sql", "orm"],Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-pdo": "*",Ð   "brick/math": "^0.9.3|^0.10.2|^0.11",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "symfony/console": "^6.0.9"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Database\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "ext-filter": "Required to use the Postgres database driver.",Ð   "doctrine/dbal": "Required to rename columns and drop SQLite columns (^2.13.3|^3.1.4).",Ð   "fakerphp/faker": "Required to use the eloquent factory builder (^1.21).",Ð   "illuminate/console": "Required to use the database commands (^9.0).",Ð   "illuminate/events": "Required to use the observers with Eloquent (^9.0).",Ð   "illuminate/filesystem": "Required to use the migrations (^9.0).",Ð   "illuminate/pagination": "Required to paginate the result set (^9.0).",Ð   "symfony/finder": "Required to use Eloquent model factories (^6.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Encryption\composer.json

{Ð   "name": "illuminate/encryption",Ð   "description": "The Illuminate Encryption package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-hash": "*",Ð   "ext-mbstring": "*",Ð   "ext-openssl": "*",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Encryption\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Events\composer.json

{Ð   "name": "illuminate/events",Ð   "description": "The Illuminate Events package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/bus": "^9.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Events\\": ""Ð   },Ð   "files": [Ð   "functions.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"ÐÐ}

vendor\laravel\framework\src\Illuminate\Filesystem\composer.json

{Ð   "name": "illuminate/filesystem",Ð   "description": "The Illuminate Filesystem package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "symfony/finder": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Filesystem\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "ext-fileinfo": "Required to use the Filesystem class.",Ð   "ext-ftp": "Required to use the Flysystem FTP driver.",Ð   "ext-hash": "Required to use the Filesystem class.",Ð   "illuminate/http": "Required for handling uploaded files (^7.0).",Ð   "league/flysystem": "Required to use the Flysystem local driver (^3.0.16).",Ð   "league/flysystem-aws-s3-v3": "Required to use the Flysystem S3 driver (^3.0).",Ð   "league/flysystem-ftp": "Required to use the Flysystem FTP driver (^3.0).",Ð   "league/flysystem-sftp-v3": "Required to use the Flysystem SFTP driver (^3.0).",Ð   "psr/http-message": "Required to allow Storage::put to accept a StreamInterface (^1.0).",Ð   "symfony/filesystem": "Required to enable support for relative symbolic links (^6.0).",Ð   "symfony/mime": "Required to enable support for guessing extensions (^6.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Hashing\composer.json

{Ð   "name": "illuminate/hashing",Ð   "description": "The Illuminate Hashing package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Hashing\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Http\composer.json

{Ð   "name": "illuminate/http",Ð   "description": "The Illuminate Http package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-filter": "*",Ð   "fruitcake/php-cors": "^1.2",Ð   "guzzlehttp/uri-template": "^1.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/session": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "symfony/http-foundation": "^6.0",Ð   "symfony/http-kernel": "^6.0",Ð   "symfony/mime": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Http\\": ""Ð   }Ð   },Ð   "suggest": {Ð   "ext-gd": "Required to use Illuminate\\Http\\Testing\\FileFactory::image().",Ð   "guzzlehttp/guzzle": "Required to use the HTTP Client (^7.5)."Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Log\composer.json

{Ð   "name": "illuminate/log",Ð   "description": "The Illuminate Log package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "monolog/monolog": "^2.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Log\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Macroable\composer.json

{Ð   "name": "illuminate/macroable",Ð   "description": "The Illuminate Macroable package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Support\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}

vendor\laravel\framework\src\Illuminate\Mail\composer.json

{Ð   "name": "illuminate/mail",Ð   "description": "The Illuminate Mail package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "league/commonmark": "^2.2",Ð   "psr/log": "^1.0|^2.0|^3.0",Ð   "symfony/mailer": "^6.0",Ð   "tijsverkoyen/css-to-inline-styles": "^2.2.5"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Mail\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "aws/aws-sdk-php": "Required to use the SES mail driver (^3.235.5).",Ð   "symfony/http-client": "Required to use the Symfony API mail transports (^6.0).",Ð   "symfony/mailgun-mailer": "Required to enable support for the Mailgun mail transport (^6.0).",Ð   "symfony/postmark-mailer": "Required to enable support for the Postmark mail transport (^6.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Notifications\composer.json

{Ð   "name": "illuminate/notifications",Ð   "description": "The Illuminate Notifications package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/broadcasting": "^9.0",Ð   "illuminate/bus": "^9.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/filesystem": "^9.0",Ð   "illuminate/mail": "^9.0",Ð   "illuminate/queue": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Notifications\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/database": "Required to use the database transport (^9.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Pagination\composer.json

{Ð   "name": "illuminate/pagination",Ð   "description": "The Illuminate Pagination package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-filter": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Pagination\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Pipeline\composer.json

{Ð   "name": "illuminate/pipeline",Ð   "description": "The Illuminate Pipeline package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Pipeline\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Queue\composer.json

{Ð   "name": "illuminate/queue",Ð   "description": "The Illuminate Queue package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/console": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/database": "^9.0",Ð   "illuminate/filesystem": "^9.0",Ð   "illuminate/pipeline": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "laravel/serializable-closure": "^1.2.2",Ð   "ramsey/uuid": "^4.7",Ð   "symfony/process": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Queue\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "ext-pdo": "Required to use the database queue worker.",Ð   "ext-filter": "Required to use the SQS queue worker.",Ð   "ext-mbstring": "Required to use the database failed job providers.",Ð   "ext-pcntl": "Required to use all features of the queue worker.",Ð   "ext-posix": "Required to use all features of the queue worker.",Ð   "aws/aws-sdk-php": "Required to use the SQS queue driver and DynamoDb failed job storage (^3.235.5).",Ð   "illuminate/redis": "Required to use the Redis queue driver (^9.0).",Ð   "pda/pheanstalk": "Required to use the Beanstalk queue driver (^4.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Redis\composer.json

{Ð   "name": "illuminate/redis",Ð   "description": "The Illuminate Redis package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Redis\\": ""Ð   }Ð   },Ð   "suggest": {Ð   "ext-redis": "Required to use the phpredis connector (^4.0|^5.0).",Ð   "predis/predis": "Required to use the predis connector (^1.1.9|^2.0.2)."Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}

vendor\laravel\framework\src\Illuminate\Routing\composer.json

{Ð   "name": "illuminate/routing",Ð   "description": "The Illuminate Routing package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-filter": "*",Ð   "ext-hash": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/http": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/pipeline": "^9.0",Ð   "illuminate/session": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "symfony/http-foundation": "^6.0",Ð   "symfony/http-kernel": "^6.0",Ð   "symfony/routing": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Routing\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/console": "Required to use the make commands (^9.0).",Ð   "nyholm/psr7": "Required to use PSR-7 bridging features (^1.2).",Ð   "symfony/psr-http-message-bridge": "Required to use PSR-7 bridging features (^2.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Session\composer.json

{Ð   "name": "illuminate/session",Ð   "description": "The Illuminate Session package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-ctype": "*",Ð   "ext-session": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/filesystem": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "symfony/finder": "^6.0",Ð   "symfony/http-foundation": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Session\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/console": "Required to use the session:table command (^9.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Support\composer.json

{Ð   "name": "illuminate/support",Ð   "description": "The Illuminate Support package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-ctype": "*",Ð   "ext-filter": "*",Ð   "ext-mbstring": "*",Ð   "doctrine/inflector": "^2.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/conditionable": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "nesbot/carbon": "^2.62.1",Ð   "voku/portable-ascii": "^2.0"Ð   },Ð   "conflict": {Ð   "tightenco/collect": "<5.5.33"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Support\\": ""Ð   },Ð   "files": [Ð   "helpers.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/filesystem": "Required to use the composer class (^9.0).",Ð   "league/commonmark": "Required to use Str::markdown() and Stringable::markdown() (^2.0.2).",Ð   "ramsey/uuid": "Required to use Str::uuid() (^4.7).",Ð   "symfony/process": "Required to use the composer class (^6.0).",Ð   "symfony/uid": "Required to use Str::ulid() (^6.0).",Ð   "symfony/var-dumper": "Required to use the dd function (^6.0).",Ð   "vlucas/phpdotenv": "Required to use the Env class and env helper (^5.4.1)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Testing\composer.json

{Ð   "name": "illuminate/testing",Ð   "description": "The Illuminate Testing package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-mbstring": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Testing\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "brianium/paratest": "Required to run tests in parallel (^6.0).",Ð   "illuminate/console": "Required to assert console commands (^9.0).",Ð   "illuminate/database": "Required to assert databases (^9.0).",Ð   "illuminate/http": "Required to assert responses (^9.0).",Ð   "mockery/mockery": "Required to use mocking (^1.5.1).",Ð   "phpunit/phpunit": "Required to use assertions and run tests (^9.5.8)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Translation\composer.json

{Ð   "name": "illuminate/translation",Ð   "description": "The Illuminate Translation package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/filesystem": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Translation\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\Validation\composer.json

{Ð   "name": "illuminate/validation",Ð   "description": "The Illuminate Validation package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-filter": "*",Ð   "ext-mbstring": "*",Ð   "brick/math": "^0.9.3|^0.10.2|^0.11",Ð   "egulias/email-validator": "^3.2.1|^4.0",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0",Ð   "illuminate/translation": "^9.0",Ð   "symfony/http-foundation": "^6.0",Ð   "symfony/mime": "^6.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\Validation\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "suggest": {Ð   "illuminate/database": "Required to use the database presence verifier (^9.0)."Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\laravel\framework\src\Illuminate\View\composer.json

{Ð   "name": "illuminate/view",Ð   "description": "The Illuminate View package.",Ð   "license": "MIT",Ð   "homepage": "https://laravel.com",Ð   "support": {Ð   "issues": "https://github.com/laravel/framework/issues",Ð   "source": "https://github.com/laravel/framework"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-tokenizer": "*",Ð   "illuminate/collections": "^9.0",Ð   "illuminate/container": "^9.0",Ð   "illuminate/contracts": "^9.0",Ð   "illuminate/events": "^9.0",Ð   "illuminate/filesystem": "^9.0",Ð   "illuminate/macroable": "^9.0",Ð   "illuminate/support": "^9.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Illuminate\\View\\": ""Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev"Ð}

vendor\laravel\sail\composer.json

{Ð   "name": "laravel/sail",Ð   "description": "Docker files for running a basic Laravel application.",Ð   "keywords": ["laravel", "docker"],Ð   "license": "MIT",Ð   "support": {Ð   "issues": "https://github.com/laravel/sail/issues",Ð   "source": "https://github.com/laravel/sail"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0",Ð   "illuminate/console": "^9.52.16|^10.0|^11.0|^12.0",Ð   "illuminate/contracts": "^9.52.16|^10.0|^11.0|^12.0",Ð   "illuminate/support": "^9.52.16|^10.0|^11.0|^12.0",Ð   "symfony/console": "^6.0|^7.0",Ð   "symfony/yaml": "^6.0|^7.0"Ð   },Ð   "require-dev": {Ð   "orchestra/testbench": "^7.0|^8.0|^9.0|^10.0",Ð   "phpstan/phpstan": "^1.10"Ð   },Ð   "bin": [Ð   "bin/sail"Ð   ],Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\Sail\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "laravel": {Ð   "providers": [Ð   "Laravel\\Sail\\SailServiceProvider"Ð   ]Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐ}Ð

vendor\laravel\sanctum\composer.json

{Ð   "name": "laravel/sanctum",Ð   "description": "Laravel Sanctum provides a featherweight authentication system for SPAs and simple APIs.",Ð   "keywords": ["laravel", "sanctum", "auth"],Ð   "license": "MIT",Ð   "support": {Ð   "issues": "https://github.com/laravel/sanctum/issues",Ð   "source": "https://github.com/laravel/sanctum"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2|^8.0",Ð   "ext-json": "*",Ð   "illuminate/console": "^6.9|^7.0|^8.0|^9.0",Ð   "illuminate/contracts": "^6.9|^7.0|^8.0|^9.0",Ð   "illuminate/database": "^6.9|^7.0|^8.0|^9.0",Ð   "illuminate/support": "^6.9|^7.0|^8.0|^9.0"Ð   },Ð   "require-dev": {Ð   "mockery/mockery": "^1.0",Ð   "orchestra/testbench": "^4.0|^5.0|^6.0|^7.0",Ð   "phpunit/phpunit": "^8.0|^9.3"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\Sanctum\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Laravel\\Sanctum\\Tests\\": "tests/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "2.x-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "Laravel\\Sanctum\\SanctumServiceProvider"Ð   ]Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐ}Ð

vendor\laravel\serializable-closure\composer.json

{Ð   "name": "laravel/serializable-closure",Ð   "description": "Laravel Serializable Closure provides an easy and secure way to serialize closures in PHP.",Ð   "keywords": ["laravel", "Serializable", "closure"],Ð   "license": "MIT",Ð   "support": {Ð   "issues": "https://github.com/laravel/serializable-closure/issues",Ð   "source": "https://github.com/laravel/serializable-closure"Ð   },Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   },Ð   {Ð   "name": "Nuno Maduro",Ð   "email": "nuno@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.3|^8.0"Ð   },Ð   "require-dev": {Ð   "illuminate/support": "^8.0|^9.0|^10.0|^11.0",Ð   "nesbot/carbon": "^2.61|^3.0",Ð   "pestphp/pest": "^1.21.3",Ð   "phpstan/phpstan": "^1.8.2",Ð   "symfony/var-dumper": "^5.4.11|^6.2.0|^7.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\SerializableClosure\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Tests\\": "tests/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.x-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": true,Ð   "allow-plugins": {Ð   "pestphp/pest-plugin": trueÐ   }Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐ}Ð

vendor\laravel\tinker\composer.json

{Ð   "name": "laravel/tinker",Ð   "description": "Powerful REPL for the Laravel framework.",Ð   "keywords": ["tinker", "repl", "psysh", "laravel"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5|^8.0",Ð   "illuminate/console": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð   "illuminate/contracts": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð   "illuminate/support": "^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0",Ð   "psy/psysh": "^0.11.1|^0.12.0",Ð   "symfony/var-dumper": "^4.3.4|^5.0|^6.0|^7.0"Ð   },Ð   "require-dev": {Ð   "mockery/mockery": "~1.3.3|^1.4.2",Ð   "phpstan/phpstan": "^1.10",Ð   "phpunit/phpunit": "^8.5.8|^9.3.3|^10.0"Ð   },Ð   "suggest": {Ð   "illuminate/database": "The Illuminate Database package (^6.0|^7.0|^8.0|^9.0|^10.0|^11.0|^12.0)."Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\Tinker\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Laravel\\Tinker\\Tests\\": "tests/",Ð   "App\\": "tests/fixtures/app",Ð   "One\\Two\\": "tests/fixtures/vendor/one/two"Ð   }Ð   },Ð   "extra": {Ð   "laravel": {Ð   "providers": [Ð   "Laravel\\Tinker\\TinkerServiceProvider"Ð   ]Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐ}Ð

vendor\laravel\ui\composer.json

{Ð   "name": "laravel/ui",Ð   "description": "Laravel UI utilities and presets.",Ð   "keywords": ["laravel", "ui"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Taylor Otwell",Ð   "email": "taylor@laravel.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.3|^8.0",Ð   "illuminate/console": "^8.42|^9.0",Ð   "illuminate/filesystem": "^8.42|^9.0",Ð   "illuminate/support": "^8.82|^9.0",Ð   "illuminate/validation": "^8.42|^9.0"Ð   },Ð   "require-dev": {Ð   "orchestra/testbench": "^6.23|^7.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Laravel\\Ui\\": "src/",Ð   "Illuminate\\Foundation\\Auth\\": "auth-backend/"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.x-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "Laravel\\Ui\\UiServiceProvider"Ð   ]Ð   }Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": trueÐ}Ð

vendor\league\commonmark\composer.json

{Ð "name": "league/commonmark",Ð "type": "library",Ð "description": "Highly-extensible PHP Markdown parser which fully supports the CommonMark spec and GitHub-Flavored Markdown (GFM)",Ð "keywords": ["markdown","parser","commonmark","gfm","github","flavored","github-flavored","md"],Ð "homepage": "https://commonmark.thephpleague.com",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Colin O'Dell",Ð "email": "colinodell@gmail.com",Ð "homepage": "https://www.colinodell.com",Ð "role": "Lead Developer"Ð }Ð],Ð "support": {Ð "docs": "https://commonmark.thephpleague.com/",Ð "forum": "https://github.com/thephpleague/commonmark/discussions",Ð "issues": "https://github.com/thephpleague/commonmark/issues",Ð "rss": "https://github.com/thephpleague/commonmark/releases.atom",Ð "source": "https://github.com/thephpleague/commonmark"Ð },Ð "require": {Ð "php": "^7.4 || ^8.0",Ð "ext-mbstring": "*",Ð "league/config": "^1.1.1",Ð "psr/event-dispatcher": "^1.0",Ð "symfony/deprecation-contracts": "^2.1 || ^3.0",Ð "symfony/polyfill-php80": "^1.16"Ð },Ð "require-dev": {Ð "ext-json": "*",Ð "cebe/markdown": "^1.0",Ð "commonmark/cmark": "0.31.1",Ð "commonmark/commonmark.js": "0.31.1",Ð "composer/package-versions-deprecated": "^1.8",Ð "embed/embed": "^4.4",Ð "erusev/parsedown": "^1.0",Ð "github/gfm": "0.29.0",Ð "michelf/php-markdown": "^1.4 || ^2.0",Ð "nyholm/psr7": "^1.5",Ð "phpstan/phpstan": "^1.8.2",Ð "phpunit/phpunit": "^9.5.21 || ^10.5.9 || ^11.0.0",Ð "scrutinizer/ocular": "^1.8.1",Ð "symfony/finder": "^5.3 | ^6.0 | ^7.0",Ð "symfony/process": "^5.4 | ^6.0 | ^7.0",Ð "symfony/yaml": "^2.3 | ^3.0 | ^4.0 | ^5.0 | ^6.0 | ^7.0",Ð "unleashedtech/php-coding-standard": "^3.1.1",Ð "vimeo/psalm": "^4.24.0 || ^5.0.0"Ð },Ð "minimum-stability": "beta",Ð "suggest": {Ð "symfony/yaml": "v2.3+ required if using the Front Matter extension"Ð },Ð "repositories": [Ð {Ð "type": "package",Ð "package": {Ð "name": "commonmark/commonmark.js",Ð "version": "0.31.1",Ð "dist": {Ð "url": "https://github.com/commonmark/commonmark.js/archive/0.31.1.zip",Ð "type": "zip"Ð }Ð }Ð },Ð {Ð "type": "package",Ð "package": {Ð "name": "commonmark/cmark",Ð "version": "0.31.1",Ð "dist": {Ð "url": "https://github.com/commonmark/cmark/archive/0.31.1.zip",Ð "type": "zip"Ð }Ð }Ð },Ð {Ð "type": "package",Ð "package": {Ð "name": "github/gfm",Ð "version": "0.29.0",Ð "dist": {Ð "url": "https://github.com/github/cmark-gfm/archive/0.29.0.gfm.13.zip",Ð "type": "zip"Ð }Ð }Ð }Ð],Ð "autoload": {Ð "psr-4": {Ð "League\\CommonMark\\": "src"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "League\\CommonMark\\Tests\\Unit\\": "tests/unit",Ð "League\\CommonMark\\Tests\\Functional\\": "tests/functional",Ð "League\\CommonMark\\Tests\\PHPStan\\": "tests/phpstan"Ð }Ð },Ð "scripts": {Ð "phpcs": "phpcs",Ð "phpstan": "phpstan analyse",Ð "phpunit": "phpunit --no-coverage",Ð "psalm": "psalm --stats",Ð "pathological": "tests/pathological/test.php",Ð "test": [Ð "@phpcs",Ð "@phpstan",Ð "@psalm",Ð "@phpunit",Ð "@pathological"Ð]Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-main": "2.7-dev"Ð }Ð },Ð "config": {Ð "allow-plugins": {Ð "composer/package-versions-deprecated": true,Ð "dealerdirect/phpcodesniffer-composer-installer": trueÐ },Ð "sort-packages": trueÐ }ÐÐ

vendor\league\config\composer.json

{Ð   "name": "league/config",Ð   "type": "library",Ð   "description": "Define configuration arrays with strict schemas and access values with dot notation",Ð   "keywords": ["configuration","config","schema","array","nested","dot","dot-access"],Ð   "homepage": "https://config.thephpleague.com",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Colin O'Dell",Ð   "email": "colinodell@gmail.com",Ð   "homepage": "https://www.colinodell.com",Ð   "role": "Lead Developer"Ð   }Ð   ],Ð   "support": {Ð   "docs": "https://config.thephpleague.com/",Ð   "issues": "https://github.com/thephpleague/config/issues",Ð   "rss": "https://github.com/thephpleague/config/releases.atom",Ð   "source": "https://github.com/thephpleague/config"Ð   },Ð   "require": {Ð   "php": "^7.4 || ^8.0",Ð   "dflydev/dot-access-data": "^3.0.1",Ð   "nette/schema": "^1.2"Ð   },Ð   "require-dev": {Ð   "phpstan/phpstan": "^1.8.2",Ð   "phpunit/phpunit": "^9.5.5",Ð   "scrutinizer/ocular": "^1.8.1",Ð   "unleashedtech/php-coding-standard": "^3.1",Ð   "vimeo/psalm": "^4.7.3"Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "autoload": {Ð   "psr-4": {Ð   "League\\Config\\": "src"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "League\\Config\\Tests\\": "tests"Ð   }Ð   },Ð   "scripts": {Ð   "phpcs": "phpcs",Ð   "phpstan": "phpstan analyse",Ð   "phpunit": "phpunit --no-coverage",Ð   "psalm": "psalm",Ð   "test": [Ð   "@phpcs",Ð   "@phpstan",Ð   "@psalm",Ð   "@phpunit"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "1.2-dev"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": true,Ð   "allow-plugins": {Ð   "dealerdirect/phpcodesniffer-composer-installer": trueÐ   }Ð   }Ð}ÐÐ

vendor\league\flysystem\composer.json

{Ð   "name": "league/flysystem",Ð   "description": "File storage abstraction for PHP",Ð   "keywords": [Ð   "filesystem", "filesystems", "files", "storage", "aws",Ð   "s3", "ftp", "sftp", "webdav", "file", "cloud"Ð   ],Ð   "scripts": {Ð   "phpstan": "vendor/bin/phpstan analyse -l 6 src"Ð   },Ð   "type": "library",Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "autoload": {Ð   "psr-4": {Ð   "League\\Flysystem\\": "src"Ð   }Ð   },Ð   "require": {Ð   "php": "^8.0.2",Ð   "league/flysystem-local": "^3.0.0",Ð   "league/mime-type-detection": "^1.0.0"Ð   },Ð   "require-dev": {Ð   "ext-zip": "*",Ð   "ext-fileinfo": "*",Ð   "ext-ftp": "*",Ð   "ext-mongodb": "^1.3",Ð   "microsoft/azure-storage-blob": "^1.1",Ð   "phpunit/phpunit": "^9.5.11|^10.0",Ð   "phpstan/phpstan": "^1.10",Ð   "phpseclib/phpseclib": "^3.0.36",Ð   "aws/aws-sdk-php": "^3.295.10",Ð   "composer/semver": "^3.0",Ð   "friendsofphp/php-cs-fixer": "^3.5",Ð   "google/cloud-storage": "^1.23",Ð   "async-aws/s3": "^1.5 || ^2.0",Ð   "async-aws/simple-s3": "^1.1 || ^2.0",Ð   "mongodb/mongodb": "^1.2",Ð   "sabre/dav": "^4.6.0",Ð   "guzzlehttp/psr7": "^2.6"Ð   },Ð   "conflict": {Ð   "async-aws/core": "<1.19.0",Ð   "async-aws/s3": "<1.14.0",Ð   "symfony/http-client": "<5.2",Ð   "guzzlehttp/ringphp": "<1.1.1",Ð   "guzzlehttp/guzzle": "<7.0",Ð   "aws/aws-sdk-php": "3.209.31 || 3.210.0",Ð   "phpseclib/phpseclib": "3.0.15"Ð   },Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Frank de Jonge",Ð   "email": "info@frankdejonge.nl"Ð   }Ð   ],Ð   "repositories": [Ð   {Ð   "type": "package",Ð   "package": {Ð   "name": "league/flysystem-local",Ð   "version": "3.0.0",Ð   "dist": {Ð   "type": "path",Ð   "url": "src/Local"Ð   }Ð   }Ð   }Ð   ]Ð}

vendor\league\flysystem-local\composer.json

{Ð   "name": "league/flysystem-local",Ð   "description": "Local filesystem adapter for Flysystem.",Ð   "keywords": ["flysystem", "filesystem", "local", "file", "files"],Ð   "type": "library",Ð   "prefer-stable": true,Ð   "autoload": {Ð   "psr-4": {Ð   "League\\Flysystem\\Local\\": ""Ð   }Ð   },Ð   "require": {Ð   "php": "^8.0.2",Ð   "ext-fileinfo": "*",Ð   "league/flysystem": "^3.0.0",Ð   "league/mime-type-detection": "^1.0.0"Ð   },Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Frank de Jonge",Ð   "email": "info@frankdejonge.nl"Ð   }Ð   ]ÐÐ}

vendor\league\mime-type-detection\composer.json

{Ð   "name": "league/mime-type-detection",Ð   "description": "Mime-type detection for Flysystem",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Frank de Jonge",Ð   "email": "info@frankdejonge.nl"Ð   }Ð   ],Ð   "scripts": {Ð   "test": "vendor/bin/phpunit",Ð   "phpstan": "vendor/bin/phpstan analyse -l 6 src"Ð   },Ð   "require": {Ð   "php": "^7.4 || ^8.0",Ð   "ext-fileinfo": "*"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^8.5.8 || ^9.3 || ^10.0",Ð   "phpstan/phpstan": "^0.12.68",Ð   "friendsofphp/php-cs-fixer": "^3.2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "League\\MimeTypeDetection\\": "src"Ð   }Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.4.0"Ð   }Ð   }Ð}Ð

vendor\masterminds\html5\composer.json


```
{    "name": "masterminds/html5",    "description": "An HTML5 parser and
serializer.",    "type": "library",    "homepage": "http://
masterminds.github.io/html5-php",    "license": "MIT",    "keywords": ["xml",
"html", "html5", "dom", "parser", "serializer", "querypath"],    "authors": [
        {            "name": "Matt Butcher",            "email":
"technosophos@gmail.com"        },        {            "name": "Matt Farina",
            "email": "matt@mattfarina.com"        },        {
"name": "Asmir Mustafic",            "email": "goetas@gmail.com"        }
    ],    "require" : {        "ext-dom": "*",        "php" : ">=5.3.0"    },
    "require-dev": {        "phpunit/phpunit" : "^4.8.35 || ^5.7.21 || ^6 ||
^7 || ^8 || ^9"    },    "autoload": {        "psr-4": {"Masterminds\\":
"src"}    },    "autoload-dev": {        "psr-4": {"Masterminds\\HTML5\\Tests\
\": "test/HTML5"}    },    "extra": {        "branch-alias": {
"dev-master": "2.7-dev"        }    }}
```

vendor\mockery\mockery\composer.json

{Ð   "name": "mockery/mockery",Ð   "description": "Mockery is a simple yet flexible PHP mock object framework",Ð   "license": "BSD-3-Clause",Ð   "type": "library",Ð   "keywords": [Ð   "bdd",Ð   "library",Ð   "mock",Ð   "mock objects",Ð   "mockery",Ð   "stub",Ð   "tdd",Ð   "test",Ð   "test double",Ð   "testing"Ð   ],Ð   "authors": [Ð   {Ð   "name": "Pádraic Brady",Ð   "email": "padraic.brady@gmail.com",Ð   "homepage": "https://github.com/padraic",Ð   "role": "Author"Ð   },Ð   {Ð   "name": "Dave Marshall",Ð   "email": "dave.marshall@atstsolutions.co.uk",Ð   "homepage": "https://davedevelopment.co.uk",Ð   "role": "Developer"Ð   },Ð   {Ð   "name": "Nathanael Esayeas",Ð   "email": "nathanael.esayeas@protonmail.com",Ð   "homepage": "https://github.com/ghostwriter",Ð   "role": "Lead Developer"Ð   }Ð   ],Ð   "homepage": "https://github.com/mockery/mockery",Ð   "support": {Ð   "issues": "https://github.com/mockery/mockery/issues",Ð   "source": "https://github.com/mockery/mockery",Ð   "docs": "https://docs.mockery.io/",Ð   "rss": "https://github.com/mockery/mockery/releases.atom",Ð   "security": "https://github.com/mockery/mockery/security/advisories"Ð   },Ð   "require": {Ð   "php": ">=7.3",Ð   "lib-pcre": ">=7.0",Ð   "hamcrest/hamcrest-php": "^2.0.1"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^8.5 || ^9.6.17",Ð   "symplify/easy-coding-standard": "^12.1.14"Ð   },Ð   "conflict": {Ð   "phpunit/phpunit": "<8.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Mockery\\": "library/Mockery"Ð   },Ð   "files": [Ð   "library/helpers.php",Ð   "library/Mockery.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Fixture\\": "tests/Fixture/",Ð   "Mockery\\Tests\\Unit\\": "tests/Unit",Ð   "test\\": "tests/"Ð   },Ð   "files": [Ð   "fixtures/autoload.php",Ð   "vendor/hamcrest/hamcrest-php/hamcrest/Hamcrest.php"Ð   ]Ð   },Ð   "config": {Ð   "optimize-autoloader": true,Ð   "platform": {Ð   "php": "7.3.999"Ð   },Ð   "preferred-install": "dist",Ð   "sort-packages": trueÐ   },Ð   "scripts": {Ð   "check": [Ð   "@composer validate",Ð   "@ecs",Ð   "@test"Ð   ],Ð   "docs": "vendor/bin/phpdoc -d library -t docs/api",Ð   "ecs": [Ð   "@ecs:fix",Ð   "@ecs:check"Ð   ],Ð   "ecs:check": "ecs check --clear-cache || true",Ð   "ecs:fix": "ecs check --clear-cache --fix",Ð   "phive": [Ð   "tools/phive update --force-accept-unsigned",Ð   "tools/phive purge"Ð   ],Ð   "phpunit": "vendor/bin/phpunit --do-not-cache-result --colors=always",Ð   "phpunit:coverage": "@phpunit --coverage-clover=coverage.xml",Ð   "psalm": "tools/psalm --no-cache --show-info=true",Ð   "psalm:alter": "tools/psalm --no-cache --alter --allow-backwards-incompatible-changes=false --safe-types",Ð   "psalm:baseline": "@psalm --no-diff --set-baseline=psalm-baseline.xml",Ð   "psalm:dry-run": "@psalm:alter --issues=all --dry-run",Ð   "psalm:fix": "@psalm:alter --issues=UnnecessaryVarAnnotation,MissingPureAnnotation,MissingImmutableAnnotation",Ð   "psalm:security": "@psalm --no-diff --taint-analysis",Ð   "psalm:shepherd": "@psalm --no-diff --shepherd --stats --output-format=github",Ð   "test": [Ð   "@phpunit --stop-on-defect",Ð   "@psalm",Ð   "@psalm:security",Ð   "@psalm:dry-run"Ð   ]Ð   }ÐÐ

vendor\monolog\monolog\composer.json

{Ð   "name": "monolog/monolog",Ð   "description": "Sends your logs to files, sockets, inboxes, databases and various web services",Ð   "keywords": ["log", "logging", "psr-3"],Ð   "homepage": "https://github.com/Seldaek/monolog",Ð   "type": "library",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Jordi Boggiano",Ð   "email": "j.boggiano@seld.be",Ð   "homepage": "https://seld.be"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2",Ð   "psr/log": "^1.0.1 || ^2.0 || ^3.0"Ð   },Ð   "require-dev": {Ð   "ext-json": "*",Ð   "aws/aws-sdk-php": "^2.4.9 || ^3.0",Ð   "doctrine/couchdb": "~1.0@dev",Ð   "elasticsearch/elasticsearch": "^7 || ^8",Ð   "graylog2/gelf-php": "^1.4.2 || ^2@dev",Ð   "guzzlehttp/guzzle": "^7.4",Ð   "guzzlehttp/psr7": "^2.2",Ð   "mongodb/mongodb": "^1.8",Ð   "php-amqplib/php-amqplib": "~2.4 || ^3",Ð   "phpspec/prophecy": "^1.15",Ð   "phpstan/phpstan": "^1.10",Ð   "phpunit/phpunit": "^8.5.38 || ^9.6.19",Ð   "predis/predis": "^1.1 || ^2.0",Ð   "rollbar/rollbar": "^1.3 || ^2 || ^3",Ð   "ruflin/elastica": "^7",Ð   "swiftmailer/swiftmailer": "^5.3|^6.0",Ð   "symfony/mailer": "^5.4 || ^6",Ð   "symfony/mime": "^5.4 || ^6"Ð   },Ð   "suggest": {Ð   "graylog2/gelf-php": "Allow sending log messages to a GrayLog2 server",Ð   "doctrine/couchdb": "Allow sending log messages to a CouchDB server",Ð   "ruflin/elastica": "Allow sending log messages to an Elastic Search server",Ð   "elasticsearch/elasticsearch": "Allow sending log messages to an Elasticsearch server via official client",Ð   "php-amqplib/php-amqplib": "Allow sending log messages to an AMQP server using php-amqplib",Ð   "ext-amqp": "Allow sending log messages to an AMQP server (1.0+ required)",Ð   "ext-mongodb": "Allow sending log messages to a MongoDB server (via driver)",Ð   "mongodb/mongodb": "Allow sending log messages to a MongoDB server (via library)",Ð   "aws/aws-sdk-php": "Allow sending log messages to AWS services like DynamoDB",Ð   "rollbar/rollbar": "Allow sending log messages to Rollbar",Ð   "ext-mbstring": "Allow to work properly with unicode symbols",Ð   "ext-sockets": "Allow sending log messages to a Syslog server (via UDP driver)",Ð   "ext-curl": "Required to send log messages using the IFTTTHandler, the LogglyHandler, the SendGridHandler, the SlackWebhookHandler or the TelegramBotHandler",Ð   "ext-openssl": "Required to send log messages using SSL"Ð   },Ð   "autoload": {Ð   "psr-4": {"Monolog\\": "src/Monolog"}Ð   },Ð   "autoload-dev": {Ð   "psr-4": {"Monolog\\": "tests/Monolog"}Ð   },Ð   "provide": {Ð   "psr/log-implementation": "1.0.0 || 2.0.0 || 3.0.0"Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "2.x-dev"Ð   }Ð   },Ð   "scripts": {Ð   "test": "@php vendor/bin/phpunit",Ð   "phpstan": "@php vendor/bin/phpstan analyse"Ð   },Ð   "config": {Ð   "lock": false,Ð   "sort-packages": true,Ð   "platform-check": false,Ð   "allow-plugins": {Ð   "composer/package-versions-deprecated": trueÐ   }Ð   }Ð}

vendor\myclabs\deep-copy\composer.json

{Ð   "name": "myclabs/deep-copy",Ð   "description": "Create deep copies (clones) of your objects",Ð   "license": "MIT",Ð   "type": "library",Ð   "keywords": [Ð   "clone",Ð   "copy",Ð   "duplicate",Ð   "object",Ð   "object graph"Ð   ],Ð   "require": {Ð   "php": "^7.1 || ^8.0"Ð   },Ð   "require-dev": {Ð   "doctrine/collections": "^1.6.8",Ð   "doctrine/common": "^2.13.3 || ^3.2.2",Ð   "phpspec/prophecy": "^1.10",Ð   "phpunit/phpunit": "^7.5.20 || ^8.5.23 || ^9.5.13"Ð   },Ð   "conflict": {Ð   "doctrine/collections": "<1.6.8",Ð   "doctrine/common": "<2.13.3 || >=3 <3.2.2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "DeepCopy\\": "src/DeepCopy/"Ð   },Ð   "files": [Ð   "src/DeepCopy/deep_copy.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "DeepCopyTest\\": "tests/DeepCopyTest/",Ð   "DeepCopy\\": "fixtures/"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   }Ð}Ð

vendor\myclabs\php-enum\composer.json

{Đ   "name": "myclabs/php-enum",Đ   "type": "library",Đ   "description": "PHP Enum implementation",Đ   "keywords": ["enum"],Đ   "homepage": "https://github.com/myclabs/php-enum",Đ   "license": "MIT",Đ   "authors": [Đ   {Đ   "name": "PHP Enum contributors",Đ   "homepage": "https://github.com/myclabs/php-enum/graphs/contributors"Đ   }Đ   ],Đ   "autoload": {Đ   "psr-4": {Đ   "MyCLabs\\Enum\\": "src/"Đ   },Đ   "classmap": [Đ   "stubs/Stringable.php"Đ   ]Đ   },Đ   "autoload-dev": {Đ   "psr-4": {Đ   "MyCLabs\\Tests\\Enum\\": "tests/"Đ   }Đ   },Đ   "require": {Đ   "php": "^7.3 || ^8.0",Đ   "ext-json": "*"Đ   },Đ   "require-dev": {Đ   "phpunit/phpunit": "^9.5",Đ   "squizlabs/php_codesniffer": "1.*",Đ   "vimeo/psalm": "^4.6.2 || ^5.2"Đ   }Đ}Đ

vendor\nesbot\carbon\composer.json

{Đ   "name": "nesbot/carbon",Đ   "description": "An API extension for DateTime that supports 281 different languages.",Đ   "license": "MIT",Đ   "type": "library",Đ   "keywords": [Đ   "date",Đ   "time",Đ   "DateTime"Đ   ],Đ   "authors": [Đ   {Đ   "name": "Brian Nesbitt",Đ   "email": "brian@nesbot.com",Đ   "homepage": "https://markido.com"Đ   },Đ   {Đ   "name": "kylekatarnls",Đ   "homepage": "https://github.com/kylekatarnls"Đ   }Đ   ],Đ   "homepage": "https://carbon.nesbot.com",Đ   "support": {Đ   "issues": "https://github.com/briannesbitt/Carbon/issues",Đ   "source": "https://github.com/briannesbitt/Carbon",Đ   "docs": "https://carbon.nesbot.com/docs"Đ   },Đ   "funding": [Đ   {Đ   "url": "https://github.com/sponsors/kylekatarnls",Đ   "type": "github"Đ   },Đ   {Đ   "url": "https://tidelift.com/subscription/pkg/packagist-nesbot-carbon?utm_source=packagist-nesbot-carbon&utm_medium=referral&utm_campaign=readme",Đ   "type": "tidelift"Đ   },Đ   {Đ   "url": "https://opencollective.com/Carbon#sponsor",Đ   "type": "opencollective"Đ   }Đ   ],Đ   "require": {Đ   "php": "^7.1.8 || ^8.0",Đ   "ext-json": "*",Đ   "carbonphp/carbon-doctrine-types": "*",Đ   "psr/clock": "^1.0",Đ   "symfony/polyfill-mbstring": "^1.0",Đ   "symfony/polyfill-php80": "^1.16",Đ   "symfony/translation": "^3.4 || ^4.0 || ^5.0 || ^6.0"Đ   },Đ   "require-dev": {Đ   "doctrine/dbal": "^2.0 || ^3.1.4 || ^4.0",Đ   "doctrine/orm": "^2.7 || ^3.0",Đ   "friendsofphp/php-cs-fixer": "^3.0",Đ   "kylekatarnls/multi-tester": "^2.0",Đ   "ondrejmirtes/better-reflection": "<6",Đ   "phpmd/phpmd": "^2.9",Đ   "phpstan/extension-installer": "^1.0",Đ   "phpstan/phpstan": "^0.12.99 || ^1.7.14",Đ   "phpunit/php-file-iterator": "^2.0.5 || ^3.0.6",Đ   "phpunit/phpunit": "^7.5.20 || ^8.5.26 || ^9.5.20",Đ   "squizlabs/php_codesniffer": "^3.4"Đ   },Đ   "provide": {Đ   "psr/clock-implementation": "1.0"Đ   },Đ   "minimum-stability": "dev",Đ   "prefer-stable": true,Đ   "autoload": {Đ   "psr-4": {Đ   "Carbon\\": "src/Carbon/"Đ   }Đ   },Đ   "autoload-dev": {Đ   "psr-4": {Đ   "Tests\\": "tests/"Đ   },Đ   "files": [Đ   "tests/Laravel/ServiceProvider.php"Đ   ]Đ   },Đ   "bin": [Đ   "bin/carbon"Đ   ],Đ   "config": {Đ   "allow-plugins": {Đ   "phpstan/extension-installer": true,Đ   "composer/package-versions-deprecated": trueĐ   },Đ   "process-timeout": 0,Đ   "sort-packages": trueĐ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "3.x-dev",Đ   "dev-2.x": "2.x-dev"Đ   },Đ   "laravel": {Đ   "providers": [Đ   "Carbon\\Laravel\\ServiceProvider"Đ   ]Đ   },Đ   "phpstan": {Đ   "includes": [Đ   "extension.neon"Đ   ]Đ   }Đ   },Đ   "scripts": {Đ   "phpcs": "php-cs-fixer fix -v --diff --dry-run",Đ   "phpdoc": "php phpdoc.php",Đ   "phpmd": "phpmd src text /phpmd.xml",Đ   "phpmd-test": "phpmd tests text /tests/phpmd-test.xml",Đ   "phpstan": "phpstan analyse --configuration phpstan.neon",Đ   "phpunit": "phpunit --verbose",Đ   "style-check": [Đ   "@phpcs",Đ   "@phpstan",Đ   "@phpmd"Đ   ],Đ   "test": [Đ   "@phpunit",Đ   "@style-check"Đ   ],Đ   "sponsors": "php sponsors.php"Đ   }}ĐĐ

vendor\nette\schema\composer.json

{Ð&æ ÖR#¢ &æWGFR÷66†VÖ "Í&FW67&— F–öâ#¢ -ƒÝÍ æWGFR 66†VÖ ¢ f Æ–F F–ær F F
structures against a given Schema.",Ð&¶W—v÷&G2#¢ ²&æWGFR"Â &6öæf–r%ÒÍ
’&†öÖW vR#¢ &‡GG 3¢òöæWGFRæ÷&r"Í&Æ–6Vç6R#¢ ²$%4BÓ2Ô6Æ W6R"Â $u ÂÓ"ã ÖöæÇ’"Â
"GPL-3.0-only"],Ð& WF†÷'2#¢ ™½™Ð&æ ÖR#¢ $F f–B w'VFÂ™Í&†öÖW vR#¢ &‡GG 3¢òð
davidgrudl.com"Ð},™½™Ð&æ ÖR#¢ $æWGFR 6öÖ×Væ—G’™Í&†öÖW vR#¢ &‡GG 3¢òöæWGFRæ÷&rð
contributors"Ð}ÐÍ'&W V—&R#¢ ™½"php": "8.1 - 8.4",™Ðnette/utils": "^4.0"ÐÍ
’'&W V—&RÖFWb#¢ ™½"nette/tester": "^2.5.2",™Ðtracy/tracy": "^2.8",™Ðphpstan/
phpstan-nette": "^1.0"ÐÒÍ& WFöÆö B#¢ ™½"classmap": ["src/"]ÐÍ&Ö–æ–×VÒÐ
stability": "dev",Ð'67&— G2#¢ ™½"phpstan": "phpstan analyse",™Ðtester": "tester
tests -s"ÐÒÍ&W‡G& #¢ ™½"branch-alias": {™Ð&FWbÖÖ 7FW"#¢ # ã2ÖFWÐ}ÐÐ

vendor\nette\utils\composer.json

{Ð&æ ÖR#¢ &æWGFR÷WF–Ç2"Í&FW67&— F–öâ#¢ -ƒÝî æWGFR WF–Ç3¢ Æ–v‡GvV–v‡B WF–Æ—F–W2
for string & array manipulation, image handling, safe JSON encoding/decoding,
validation, slug or strong password generating etc.",Ð&¶W—v÷&G2#¢ ²&æWGFR"Â
"images", "json", "password", "validation", "utility", "string", "array",
"core", "slugify", "utf-8", "unicode", "paginator", "datetime"],Ð&†öÖW vR#¢
"https://nette.org",Ð&Æ–6Vç6R#¢ ²$%4BÓ2Ô6Æ W6R"Â $u ÂÓ"ã ÖöæÇ'"Â $u ÂÓ2ã Ð
only"],Ð& WF†÷'2#¢ ™{Ð&æ ÖR#¢ $F f–B w'VFÂ™Í&†öÖW vR#¢ &‡GG 3¢òöF f–Fw'VFÂæ6öÒ-
™},™Ð&æ ÖR#¢ $æWGFR 6öÖ×Væ—G'™Í&†öÖW vR#¢ &‡GG 3¢òöæWGFRæ÷&rö6öçG&–'WF÷'™}ÐÍ
''&W V—&R#¢ ™"php": "8.0 - 8.4"ÐÍ'&W V—&RÖFWb#¢ ™"nette/tester": "^2.5",Ðtracy/
tracy": "^2.9",Ð"phpstan/phpstan": "^1.0",Ðjetbrains/phpstorm-attributes":
"dev-master"ÐÒÍ&6öæfÆ–7B#¢ ™"nette/finder": "<3",Ðnette/schema": "<1.2.2"ÐÍ
''7VvvW7B#¢ ™"ext-iconv": "to use Strings::webalize(), toAscii(), chr() and
reverse()",Ð"ext-json": "to use Nette\\Utils\\Json",Ðext-intl": "to use
Strings::webalize(), toAscii(), normalize() and compare()",Ð"ext-mbstring":
"to use Strings::lower() etc...",Ð"ext-gd": "to use Image",Ðext-tokenizer":
"to use Nette\\Utils\\Reflection::getUseStatements()"ÐÒÍ& WFöÆö B#¢ ½
™"classmap": ["src/"]ÐÍ&Ö–æ–×VÒ×7F &–Æ—G'#¢ &FWb"Í'67&— G2#¢ ™"phpstan":
"phpstan analyse",Ð"tester": "tester tests -s"ÐÍ&W‡G& #¢ ™"branch-alias": {Ð
™'&FWbÖÖ 7FW"#¢ #Bã ÖFWÐ]ÐÐ

vendor\nikic\php-parser\composer.json

{Ð   "name": "nikic/php-parser",Ð   "type": "library",Ð   "description": "A PHP parser written in PHP",Ð   "keywords": [Ð   "php",Ð   "parser"Ð   ],Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð "name": "Nikita Popov"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.4",Ð   "ext-tokenizer": "*",Ð   "ext-json": "*",Ð   "ext-ctype": "*"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.0",Ð "ircmaxell/php-yacc": "^0.0.7"Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "5.0-dev"Ð   }Ð   },Ð   "autoload": {Ð "psr-4": {Ð   "PhpParser\\": "lib/PhpParser"Ð   }Ð   },Ð "autoload-dev": {Ð   "psr-4": {Ð   "PhpParser\\": "test/PhpParser/"Ð   }Ð   },Ð   "bin": [Ð   "bin/php-parse"Ð   ]ÐÐ}

vendor\nunomaduro\collision\composer.json

{Ð   "name": "nunomaduro/collision",Ð   "description": "Cli error handling for console/command-line PHP applications.",Ð   "keywords": ["console", "command-line", "php", "cli", "error", "handling", "laravel-zero", "laravel", "artisan", "symfony"],Ð   "license": "MIT",Ð   "support": {Ð   "issues": "https://github.com/nunomaduro/collision/issues",Ð   "source": "https://github.com/nunomaduro/collision"Ð   },Ð   "authors": [Ð   {Ð   "name": "Nuno Maduro",Ð   "email": "enunomaduro@gmail.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.0.0",Ð   "filp/whoops": "^2.14.5",Ð   "symfony/console": "^6.0.2"Ð   },Ð   "require-dev": {Ð   "brianium/paratest": "^6.4.1",Ð   "laravel/framework": "^9.26.1",Ð   "laravel/pint": "^1.1.1",Ð   "nunomaduro/larastan": "^1.0.3",Ð   "nunomaduro/mock-final-classes": "^1.1.0",Ð   "orchestra/testbench": "^7.7",Ð   "phpunit/phpunit": "^9.5.23",Ð   "spatie/ignition": "^1.4.1"Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Tests\\Unit\\": "tests/Unit",Ð   "Tests\\FakeProgram\\": "tests/FakeProgram",Ð   "Tests\\": "tests/LaravelApp/tests",Ð   "App\\": "tests/LaravelApp/app/"Ð   }Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "autoload": {Ð   "psr-4": {Ð   "NunoMaduro\\Collision\\": "src/"Ð   }Ð   },Ð   "config": {Ð   "preferred-install": "dist",Ð   "sort-packages": true,Ð   "allow-plugins": {Ð   "pestphp/pest-plugin": trueÐ   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-develop": "6.x-dev"Ð   },Ð   "laravel": {Ð   "providers": [Ð   "NunoMaduro\\Collision\\Adapters\\Laravel\\CollisionServiceProvider"Ð   ]Ð   }Ð   },Ð   "scripts": {Ð   "lint": "pint -v",Ð   "test:lint": "pint --test -v",Ð   "test:types": "phpstan analyse --ansi",Ð   "test:unit": "phpunit --colors=always",Ð   "test": [Ð   "@test:lint",Ð   "@test:types",Ð   "@test:unit"Ð   ]Ð   }Ð}

vendor\nunomaduro\termwind\composer.json


```
{Ð   "name": "nunomaduro/termwind",Ð   "description": "Its like Tailwind CSS,
but for the console.",Ð   "keywords": ["php", "cli", "package", "console",
"css", "style"],Ð   "license": "MIT",Ð   "authors": [Ð       {Ð
"name": "Nuno Maduro",Ð           "email": "enunomaduro@gmail.com"Ð       }Ð
    ],Ð   "require": {Ð       "php": "^8.1",Ð       "ext-mbstring": "*",Ð
        "symfony/console": "^6.4.15"Ð   },Ð   "require-dev": {Ð
"illuminate/console": "^10.48.24",Ð       "illuminate/support": "^10.48.24",Ð
        "laravel/pint": "^1.18.2",Ð       "pestphp/pest": "^2.36.0",Ð
"pestphp/pest-plugin-mock": "2.0.0",Ð       "phpstan/phpstan": "^1.12.11",Ð
        "phpstan/phpstan-strict-rules": "^1.6.1",Ð       "symfony/var-
dumper": "^6.4.15",Ð       "thecodingmachine/phpstan-strict-rules": "^1.0.0"Ð
    },Ð   "autoload": {Ð       "psr-4": {Ð           "Termwind\\": "src/"Ð
        },Ð       "files": [Ð           "src/Functions.php"Ð       ]Ð   },Ð
"autoload-dev": {Ð       "psr-4": {Ð           "Tests\\": "tests/"Ð       }Ð
    },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "config": {Ð
        "sort-packages": true,Ð       "preferred-install": "dist",Ð
"allow-plugins": {Ð           "pestphp/pest-plugin": trueÐ       }Ð   },Ð
"scripts": {Ð       "lint": "pint -v",Ð       "test:lint": "pint --test -v",Ð
        "test:types": "phpstan analyse --ansi",Ð       "test:unit": "pest --
colors=always",Ð       "test": [Ð           "@test:lint",Ð
"@test:types",Ð           "@test:unit"Ð       ]Ð   },Ð   "extra": {Ð
"laravel": {Ð           "providers": [Ð               "Termwind\\Laravel\
\TermwindServiceProvider"Ð           ]Ð       }Ð   }Ð}
```

vendor\nunomaduro\termwind\pint.json

{Ð   "rules": {Ð   "yoda_style": false,Ð
"nullable_type_declaration": false,Ð
"nullable_type_declaration_for_default_null_value": falseÐ   }Ð
}

vendor\phar-io\manifest\composer.json

{Ð "name": "phar-io/manifest",Ð "description": "Component for reading phar.io manifest information from a PHP Archive (PHAR)",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Arne Blankerts",Ð "email": "arne@blankerts.de",Ð "role": "Developer"Ð },Ð {Ð "name": "Sebastian Heuer",Ð "email": "sebastian@phpeople.de",Ð "role": "Developer"Ð },Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "Developer"Ð }Ð],Ð "support": {Ð "issues": "https://github.com/phar-io/manifest/issues"Ð },Ð "require": {Ð "php": "^7.2 || ^8.0",Ð "ext-dom": "*",Ð "ext-phar": "*",Ð "ext-libxml": "*",Ð "ext-xmlwriter": "*",Ð "phar-io/version": "^3.0.1"Ð },Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.0.x-dev"Ð }Ð }ÐÐ}

vendor\phar-io\version\composer.json

{Ð "name": "phar-io/version",Ð "description": "Library for handling version information and constraints",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Arne Blankerts",Ð "email": "arne@blankerts.de",Ð "role": "Developer"Ð },Ð {Ð "name": "Sebastian Heuer",Ð "email": "sebastian@phpeople.de",Ð "role": "Developer"Ð },Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "Developer"Ð }Ð],Ð "support": {Ð "issues": "https://github.com/phar-io/version/issues"Ð },Ð "require": {Ð "php": "^7.2 || ^8.0"Ð },Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð }ÐÐ}

vendor\phenx\php-font-lib\composer.json


```
{Đ   "name": "phenx/php-font-lib",Đ   "type": "library",Đ   "description": "A
library to read, parse, export and make subsets of different types of font
files.",Đ   "homepage": "https://github.com/PhenX/php-font-lib",Đ
"license": "LGPL-2.1-or-later",Đ   "authors": [Đ       {Đ           "name":
"Fabien Ménager",Đ           "email": "fabien.menager@gmail.com"Đ       }Đ
    ],Đ   "autoload": {Đ       "psr-4": {Đ           "FontLib\\": "src/
FontLib"Đ       }Đ   },Đ   "autoload-dev": {Đ       "psr-4": {Đ
"FontLib\\Tests\\": "tests/FontLib"Đ       }Đ   },Đ   "config": {Đ       "bin-
dir": "bin"Đ   },Đ   "require": {Đ       "ext-mbstring": "*"Đ   },Đ
"require-dev": {Đ       "symfony/phpunit-bridge" : "^3 || ^4 || ^5 || ^6"Đ   }Đ
}Đ
```

vendor\phenx\php-svg-lib\composer.json

{Ð "name": "phenx/php-svg-lib",Ð "type": "library",Ð "description": "A library to read, parse and export to PDF SVG files.",Ð "homepage": "https://github.com/PhenX/php-svg-lib",Ð "license": "LGPL-3.0",Ð "authors": [Ð {Ð "name": "Fabien Ménager",Ð "email": "fabien.menager@gmail.com"Ð }Ð],Ð "autoload": {Ð "psr-4": {Ð "Svg\\": "src/Svg"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Svg\\Tests\\": "tests/Svg"Ð }Ð },Ð "require": {Ð "php": "^7.1 || ^7.2 || ^7.3 || ^7.4 || ^8.0",Ð "ext-mbstring": "*",Ð "sabberworm/php-css-parser": "^8.4"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^7.5 || ^8.5 || ^9.5"Ð }ÐÐ}

vendor\phpoption\phpoption\composer.json

{Ð   "name": "phpoption/phpoption",Ð   "description": "Option Type for PHP",Ð
    "keywords": ["php", "option", "language", "type"],Ð   "license":
"Apache-2.0",Ð   "authors": [Ð   {Ð   "name": "Johannes M.
Schmitt",Ð   "email": "schmittjoh@gmail.com",Ð   "homepage":
"https://github.com/schmittjoh"Ð   },Ð   {Ð   "name": "Graham
Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð
"homepage": "https://github.com/GrahamCampbell"Ð   }Ð   ],Ð   "require": {Ð
        "php": "^7.2.5 || ^8.0"Ð   },Ð   "require-dev": {Ð   "bamarni/
composer-bin-plugin": "^1.8.2",Ð   "phpunit/phpunit": "^8.5.39 || ^9.6.20
|| ^10.5.28"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "PhpOption\
\": "src/PhpOption/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð
            "PhpOption\\Tests\\": "tests/PhpOption/Tests/"Ð   }Ð   },Ð
"config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-
plugin": trueÐ   },Ð   "preferred-install": "dist"Ð   },Ð   "extra": {Ð
        "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-
command": falseÐ   },Ð   "branch-alias": {Ð   "dev-master":
"1.9-dev"Ð   }Ð   }Ð}ÐÐ

vendor\phpunit\php-code-coverage\composer.json

{Ð   "name": "phpunit/php-code-coverage",Ð   "description": "Library that provides collection, processing, and rendering functionality for PHP code coverage information.",Ð   "type": "library",Ð   "keywords": [Ð   "coverage",Ð   "testing",Ð   "xunit"Ð   ],Ð   "homepage": "https://github.com/sebastianbergmann/php-code-coverage",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/php-code-coverage/issues",Ð   "security": "https://github.com/sebastianbergmann/php-code-coverage/security/policy"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "ext-dom": "*",Ð   "ext-libxml": "*",Ð   "ext-xmlwriter": "*",Ð   "nikic/php-parser": "^4.19.1 || ^5.1.0",Ð   "phpunit/php-file-iterator": "^3.0.6",Ð   "phpunit/php-text-template": "^2.0.4",Ð   "sebastian/code-unit-reverse-lookup": "^2.0.3",Ð   "sebastian/complexity": "^2.0.3",Ð   "sebastian/environment": "^5.1.5",Ð   "sebastian/lines-of-code": "^1.0.4",Ð   "sebastian/version": "^3.0.2",Ð   "theseer/tokenizer": "^1.2.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.6"Ð   },Ð   "suggest": {Ð   "ext-pcov": "PHP extension that provides line coverage",Ð   "ext-xdebug": "PHP extension that provides line coverage as well as branch and path coverage"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "files": [Ð   "tests/TestCase.php",Ð   "tests/_files/BankAccountTest.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "9.2.x-dev"Ð   }Ð   }ÐÐ}

vendor\phpunit\php-file-iterator\composer.json

{Ð "name": "phpunit/php-file-iterator",Ð "description": "FilterIterator implementation that filters files based on a list of suffixes.",Ð "type": "library",Ð "keywords": [Ð "iterator",Ð "filesystem"Ð],Ð "homepage": "https://github.com/sebastianbergmann/php-file-iterator/",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de",Ð "role": "lead"Ð }Ð],Ð "support": {Ð "issues": "https://github.com/sebastianbergmann/php-file-iterator/issues"Ð },Ð "config": {Ð "platform": {Ð "php": "7.3.0"Ð },Ð "optimize-autoloader": true,Ð "sort-packages": trueÐ },Ð "prefer-stable": true,Ð "require": {Ð "php": ">=7.3"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^9.3"Ð },Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "3.0-dev"Ð }Ð }ÐÐ}

vendor\phpunit\php-invoker\composer.json

{Ð   "name": "phpunit/php-invoker",Ð   "description": "Invoke callables with a timeout",Ð   "type": "library",Ð   "keywords": [Ð   "process"Ð   ],Ð   "homepage": "https://github.com/sebastianbergmann/php-invoker/",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/php-invoker/issues"Ð   },Ð   "prefer-stable": true,Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "ext-pcntl": "*",Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture/"Ð   ]Ð   },Ð   "suggest": {Ð   "ext-pcntl": "*"Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.1-dev"Ð   }Ð   }Ð}Ð

vendor\phpunit\php-text-template\composer.json

{Ð   "name": "phpunit/php-text-template",Ð   "description": "Simple template engine.",Ð   "type": "library",Ð   "keywords": [Ð   "template"Ð   ],Ð   "homepage": "https://github.com/sebastianbergmann/php-text-template/",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/php-text-template/issues"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "2.0-dev"Ð   }Ð   }Ð}

vendor\phpunit\php-timer\composer.json

{Ð   "name": "phpunit/php-timer",Ð   "description": "Utility class for timing",Ð   "type": "library",Ð   "keywords": [Ð   "timer"Ð   ],Ð   "homepage": "https://github.com/sebastianbergmann/php-timer/",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/php-timer/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "5.0-dev"Ð   }Ð   }Ð}Ð

vendor\phpunit\phpunit\composer.json

{Ð   "name": "phpunit/phpunit",Ð   "description": "The PHP Unit Testing framework.",Ð   "type": "library",Ð   "keywords": [Ð   "phpunit",Ð   "xunit",Ð   "testing"Ð   ],Ð   "homepage": "https://phpunit.de/",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/phpunit/issues",Ð   "security": "https://github.com/sebastianbergmann/phpunit/security/policy"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "ext-dom": "*",Ð   "ext-json": "*",Ð   "ext-libxml": "*",Ð   "ext-mbstring": "*",Ð   "ext-xml": "*",Ð   "ext-xmlwriter": "*",Ð   "doctrine/instantiator": "^1.5.0 || ^2",Ð   "myclabs/deep-copy": "^1.12.1",Ð   "phar-io/manifest": "^2.0.4",Ð   "phar-io/version": "^3.2.1",Ð   "phpunit/php-code-coverage": "^9.2.32",Ð   "phpunit/php-file-iterator": "^3.0.6",Ð   "phpunit/php-invoker": "^3.1.1",Ð   "phpunit/php-text-template": "^2.0.4",Ð   "phpunit/php-timer": "^5.0.3",Ð   "sebastian/cli-parser": "^1.0.2",Ð   "sebastian/code-unit": "^1.0.8",Ð   "sebastian/comparator": "^4.0.8",Ð   "sebastian/diff": "^4.0.6",Ð   "sebastian/environment": "^5.1.5",Ð   "sebastian/exporter": "^4.0.6",Ð   "sebastian/global-state": "^5.0.7",Ð   "sebastian/object-enumerator": "^4.0.4",Ð   "sebastian/resource-operations": "^3.0.4",Ð   "sebastian/type": "^3.2.1",Ð   "sebastian/version": "^3.0.2"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "suggest": {Ð   "ext-soap": "To be able to generate mocks based on WSDL files",Ð   "ext-xdebug": "PHP extension that provides line coverage as well as branch and path coverage"Ð   },Ð   "bin": [Ð   "phpunit"Ð   ],Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ],Ð   "files": [Ð   "src/Framework/Assert/Functions.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/"Ð   ],Ð   "files": [Ð   "tests/_files/CoverageNamespacedFunctionTest.php",Ð   "tests/_files/CoveredFunction.php",Ð   "tests/_files/NamespaceCoveredFunction.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "9.6-dev"Ð   }Ð   }}ÐÐ

vendor\psr\cache\composer.json

{Ð   "name": "psr/cache",Ð   "description": "Common interface for caching libraries",Ð   "keywords": ["psr", "psr-6", "cache"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "PHP-FIG",Ð   "homepage": "https://www.php-fig.org/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Psr\\Cache\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0.x-dev"Ð   }Ð   }Ð}Ð

vendor\psr\clock\composer.json

{Đ "name": "psr/clock",Đ "description": "Common interface for reading the clock.",Đ "keywords": ["psr", "psr-20", "time", "clock", "now"],Đ "homepage": "https://github.com/php-fig/clock",Đ "license": "MIT",Đ "authors": [Đ {Đ "name": "PHP-FIG",Đ "homepage": "https://www.php-fig.org/"Đ }Đ],Đ "require": {Đ "php": "^7.0 || ^8.0"Đ },Đ "autoload": {Đ "psr-4": {Đ "Psr\\Clock\\": "src/"Đ }Đ }ÐÐ

vendor\psr\container\composer.json

{Đ   "name": "psr/container",Đ   "type": "library",Đ   "description": "Common Container Interface (PHP FIG PSR-11)",Đ   "keywords": ["psr", "psr-11", "container", "container-interop", "container-interface"],Đ   "homepage": "https://github.com/php-fig/container",Đ   "license": "MIT",Đ   "authors": [Đ   {Đ   "name": "PHP-FIG",Đ   "homepage": "https://www.php-fig.org/"Đ   }Đ   ],Đ   "require": {Đ   "php": ">=7.4.0"Đ   },Đ   "autoload": {Đ   "psr-4": {Đ   "Psr\\Container\\": "src/"Đ   }Đ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "2.0.x-dev"Đ   }Đ   }Đ}

vendor\psr\event-dispatcher\composer.json

{Ð   "name": "psr/event-dispatcher",Ð   "description": "Standard interfaces for event handling.",Ð   "type": "library",Ð   "keywords": ["psr", "psr-14", "events"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "PHP-FIG",Ð   "homepage": "http://www.php-fig.org/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Psr\\EventDispatcher\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0.x-dev"Ð   }Ð   }Ð}Ð

vendor\psr\http-client\composer.json

{Ð   "name": "psr/http-client",Ð   "description": "Common interface for HTTP clients",Ð   "keywords": ["psr", "psr-18", "http", "http-client"],Ð   "homepage": "https://github.com/php-fig/http-client",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "PHP-FIG",Ð   "homepage": "https://www.php-fig.org/"Ð   }Ð   ],Ð   "support": {Ð   "source": "https://github.com/php-fig/http-client"Ð   },Ð   "require": {Ð   "php": "^7.0 || ^8.0",Ð   "psr/http-message": "^1.0 || ^2.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Psr\\Http\\Client\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0.x-dev"Ð   }Ð   }Ð}Ð

vendor\psr\http-factory\composer.json


```
{Ð   "name": "psr/http-factory",Ð   "description": "PSR-17: Common interfaces
for PSR-7 HTTP message factories",Ð   "keywords": [Ð       "psr",Ð
"psr-7",Ð       "psr-17",Ð       "http",Ð       "factory",Ð       "message",Ð
        "request",Ð       "response"Ð   ],Ð   "license": "MIT",Ð   "authors":
[Ð       {Ð           "name": "PHP-FIG",Ð           "homepage": "https://
www.php-fig.org/"Ð       }Ð   ],Ð   "support": {Ð       "source": "https://
github.com/php-fig/http-factory"Ð   },Ð   "require": {Ð       "php": ">=7.1",Ð
        "psr/http-message": "^1.0 || ^2.0"Ð   },Ð   "autoload": {Ð
"psr-4": {Ð           "Psr\\Http\\Message\\": "src/"Ð       }Ð   },Ð
"extra": {Ð       "branch-alias": {Ð           "dev-master": "1.0.x-dev"Ð
        }Ð   }ÐÐ
```

vendor\psr\http-message\composer.json

{Đ   "name": "psr/http-message",Đ   "description": "Common interface for HTTP messages",Đ   "keywords": ["psr", "psr-7", "http", "http-message", "request", "response"],Đ   "homepage": "https://github.com/php-fig/http-message",Đ   "license": "MIT",Đ   "authors": [Đ   {Đ   "name": "PHP-FIG",Đ   "homepage": "https://www.php-fig.org/"Đ   }Đ   ],Đ   "require": {Đ   "php": "^7.2 || ^8.0"Đ   },Đ   "autoload": {Đ   "psr-4": {Đ   "Psr\\Http\\Message\\": "src/"Đ   }Đ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "2.0.x-dev"Đ   }Đ   }Đ}

vendor\psr\log\composer.json

{Ð   "name": "psr/log",Ð   "description": "Common interface for logging libraries",Ð   "keywords": ["psr", "psr-3", "log"],Ð   "homepage": "https://github.com/php-fig/log",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "PHP-FIG",Ð   "homepage": "https://www.php-fig.org/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Psr\\Log\\": "src"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.x-dev"Ð   }Ð   }Ð}Ð

vendor\psr\simple-cache\composer.json

{Ð   "name": "psr/simple-cache",Ð   "description": "Common interfaces for simple caching",Ð   "keywords": ["psr", "psr-16", "cache", "simple-cache", "caching"],Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "PHP-FIG",Ð   "homepage": "https://www.php-fig.org/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.0.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Psr\\SimpleCache\\": "src/"Ð   }Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.0.x-dev"Ð   }Ð   }Ð}

vendor\psy\psysh\composer.json

{Ð "name": "psy/psysh",Ð "description": "An interactive shell for modern PHP.",Ð "type": "library",Ð "keywords": ["console", "interactive", "shell", "repl"],Ð "homepage": "http://psysh.org",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Justin Hileman",Ð "email": "justin@justinhileman.info",Ð "homepage": "http://justinhileman.com"Ð }Ð],Ð "require": {Ð "php": "^8.0 || ^7.4",Ð "ext-json": "*",Ð "ext-tokenizer": "*",Ð "nikic/php-parser": "^5.0 || ^4.0",Ð "symfony/console": "^7.0 || ^6.0 || ^5.0 || ^4.0 || ^3.4",Ð "symfony/var-dumper": "^7.0 || ^6.0 || ^5.0 || ^4.0 || ^3.4"Ð },Ð "require-dev": {Ð "bamarni/composer-bin-plugin": "^1.2"Ð },Ð "suggest": {Ð "ext-pcntl": "Enabling the PCNTL extension makes PsySH a lot happier :)",Ð "ext-posix": "If you have PCNTL, you'll want the POSIX extension as well.",Ð "ext-pdo-sqlite": "The doc command requires SQLite to work."Ð },Ð "autoload": {Ð "files": ["src/functions.php"],Ð "psr-4": {Ð "Psy\\": "src/"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Psy\\Test\\": "test/"Ð }Ð },Ð "bin": ["bin/psysh"],Ð "config": {Ð "allow-plugins": {Ð "bamarni/composer-bin-plugin": trueÐ }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-main": "0.12.x-dev"Ð },Ð "bamarni-bin": {Ð "bin-links": false,Ð "forward-command": falseÐ }Ð },Ð "conflict": {Ð "symfony/console": "4.4.37 || 5.3.14 || 5.3.15 || 5.4.3 || 5.4.4 || 6.0.3 || 6.0.4"Ð }Ð}Ð

vendor\ralouphie\getallheaders\composer.json

{Ð&æ ÖR#¢ '& Æ÷W †–RövWF ÆÆ†V FW'2"Í&FW67&— F–öâ#¢ $ öÇ–f–ÆÂ f÷"
getallheaders.",Ð&Æ–6Vç6R#¢ $Ô•B"Í& WF†÷'2#¢ ™{Ð&æ ÖR#¢ %& Ç , ¶† GF ""Í
™'&VÖ –Â#¢ '& Ç ,æ¶† GF $ vÖ –Âæ6öÖ}ÒÍ'&W V—&R#¢ ™"php": ">=5.6"ÒÍ'&W V—&RÐ
dev": {Ð"phpunit/phpunit": "^5 || ^6.5",Ðphp-coveralls/php-coveralls": "^2.1"ÒÍ
'& WFöÆö B#¢ ™"files": ["src/getallheaders.php"]ÒÍ& WFöÆö BÖFWb#¢ ™"psr-4": {Ð
™'&vWF ÆÆ†V FW'5ÅÅFW7G5ÅÂ#¢ 'FW7G2Ö}ÒÐ

vendor\ramsey\collection\composer.json

{Ð   "name": "ramsey/collection",Ð   "description": "A PHP library for representing and manipulating collections.",Ð   "license": "MIT",Ð   "type": "library",Ð   "keywords": [Ð   "array",Ð   "collection",Ð   "hash",Ð   "map",Ð   "queue",Ð   "set"Ð   ],Ð   "authors": [Ð   {Ð   "name": "Ben Ramsey",Ð   "email": "ben@benramsey.com",Ð   "homepage": "https://benramsey.com"Ð   }Ð   ],Ð   "require": {Ð   "php": "^8.1"Ð   },Ð   "require-dev": {Ð   "captainhook/plugin-composer": "^5.3",Ð   "ergebnis/composer-normalize": "^2.45",Ð   "fakerphp/faker": "^1.24",Ð   "hamcrest/hamcrest-php": "^2.0",Ð   "jangregor/phpstan-prophecy": "^2.1",Ð   "mockery/mockery": "^1.6",Ð   "php-parallel-lint/php-console-highlighter": "^1.0",Ð   "php-parallel-lint/php-parallel-lint": "^1.4",Ð   "phpspec/prophecy-phpunit": "^2.3",Ð   "phpstan/extension-installer": "^1.4",Ð   "phpstan/phpstan": "^2.1",Ð   "phpstan/phpstan-mockery": "^2.0",Ð   "phpstan/phpstan-phpunit": "^2.0",Ð   "phpunit/phpunit": "^10.5",Ð   "ramsey/coding-standard": "^2.3",Ð   "ramsey/conventional-commits": "^1.6",Ð   "roave/security-advisories": "dev-latest"Ð   },Ð   "prefer-stable": true,Ð   "autoload": {Ð   "psr-4": {Ð   "Ramsey\\Collection\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Ramsey\\Collection\\Test\\": "tests/"Ð   }Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "captainhook/plugin-composer": true,Ð   "dealerdirect/phpcodesniffer-composer-installer": true,Ð   "ergebnis/composer-normalize": true,Ð   "phpstan/extension-installer": trueÐ   },Ð   "sort-packages": trueÐ   },Ð   "extra": {Ð   "captainhook": {Ð   "force-install": trueÐ   },Ð   "ramsey/conventional-commits": {Ð   "configFile": "conventional-commits.json"Ð   }Ð   },Ð   "scripts": {Ð   "dev:analyze": [Ð   "@dev:analyze:phpstan"Ð   ],Ð   "dev:analyze:phpstan": "phpstan analyse --ansi --memory-limit=1G",Ð   "dev:build:clean": "git clean -fX build/",Ð   "dev:lint": [Ð   "@dev:lint:syntax",Ð   "@dev:lint:style"Ð   ],Ð   "dev:lint:fix": "phpcbf",Ð   "dev:lint:style": "phpcs --colors",Ð   "dev:lint:syntax": "parallel-lint --colors src/ tests/",Ð   "dev:test": [Ð   "@dev:lint",Ð   "@dev:analyze",Ð   "@dev:test:unit"Ð   ],Ð   "dev:test:coverage:ci": "phpunit --colors=always --coverage-text --coverage-clover build/coverage/clover.xml --coverage-cobertura build/coverage/cobertura.xml --coverage-crap4j build/coverage/crap4j.xml --coverage-xml build/coverage/coverage-xml --log-junit build/junit.xml",Ð   "dev:test:coverage:html": "phpunit --colors=always --coverage-html build/coverage/coverage-html/",Ð   "dev:test:unit": "phpunit --colors=always",Ð   "test": "@dev:test"Ð   },Ð   "scripts-descriptions": {Ð   "dev:analyze": "Runs all static analysis checks.",Ð   "dev:analyze:phpstan": "Runs the PHPStan static analyzer.",Ð   "dev:build:clean": "Cleans the build/ directory.",Ð   "dev:lint": "Runs all linting checks.",Ð   "dev:lint:fix": "Auto-fixes coding standards issues, if possible.",Ð   "dev:lint:style": "Checks for coding standards issues.",Ð   "dev:lint:syntax": "Checks for syntax errors.",Ð   "dev:test": "Runs linting, static analysis, and unit tests.",Ð   "dev:test:coverage:ci": "Runs unit tests and generates CI coverage reports.",Ð   "dev:test:coverage:html": "Runs unit tests and generates HTML coverage report.",Ð   "dev:test:unit": "Runs unit tests.",Ð   "test": "Runs linting, static analysis, and unit tests."Ð   }}ÐÐ

vendor\ramsey\uuid\composer.json

{Ð "name": "ramsey/uuid",Ð "description": "A PHP library for generating and working with universally unique identifiers (UUIDs).",Ð "license": "MIT",Ð "type": "library",Ð "keywords": [Ð "uuid",Ð "identifier",Ð "guid"Ð],Ð "require": {Ð "php": "^8.0",Ð "ext-json": "*",Ð "brick/math": "^0.8.8 || ^0.9 || ^0.10 || ^0.11 || ^0.12",Ð "ramsey/collection": "^1.2 || ^2.0"Ð },Ð "require-dev": {Ð "captainhook/captainhook": "^5.10",Ð "captainhook/plugin-composer": "^5.3",Ð "dealerdirect/phpcodesniffer-composer-installer": "^0.7.0",Ð "doctrine/annotations": "^1.8",Ð "ergebnis/composer-normalize": "^2.15",Ð "mockery/mockery": "^1.3",Ð "paragonie/random-lib": "^2",Ð "php-mock/php-mock": "^2.2",Ð "php-mock/php-mock-mockery": "^1.3",Ð "php-parallel-lint/php-parallel-lint": "^1.1",Ð "phpbench/phpbench": "^1.0",Ð "phpstan/extension-installer": "^1.1",Ð "phpstan/phpstan": "^1.8",Ð "phpstan/phpstan-mockery": "^1.1",Ð "phpstan/phpstan-phpunit": "^1.1",Ð "phpunit/phpunit": "^8.5 || ^9",Ð "ramsey/composer-repl": "^1.4",Ð "slevomat/coding-standard": "^8.4",Ð "squizlabs/php_codesniffer": "^3.5",Ð "vimeo/psalm": "^4.9"Ð },Ð "replace": {Ð "rhumsaa/uuid": "self.version"Ð },Ð "suggest": {Ð "ext-bcmath": "Enables faster math with arbitrary-precision integers using BCMath.",Ð "ext-gmp": "Enables faster math with arbitrary-precision integers using GMP.",Ð "ext-uuid": "Enables the use of PeclUuidTimeGenerator and PeclUuidRandomGenerator.",Ð "paragonie/random-lib": "Provides RandomLib for use with the RandomLibAdapter",Ð "ramsey/uuid-doctrine": "Allows the use of Ramsey\\Uuid\\Uuid as Doctrine field type."Ð },Ð "minimum-stability": "dev",Ð "prefer-stable": true,Ð "autoload": {Ð "psr-4": {Ð "Ramsey\\Uuid\\": "src/"Ð },Ð "files": [Ð "src/functions.php"Ð]Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Ramsey\\Uuid\\Benchmark\\": "tests/benchmark/",Ð "Ramsey\\Uuid\\StaticAnalysis\\": "tests/static-analysis/",Ð "Ramsey\\Uuid\\Test\\": "tests/"Ð }Ð },Ð "config": {Ð "allow-plugins": {Ð "captainhook/plugin-composer": true,Ð "ergebnis/composer-normalize": true,Ð "phpstan/extension-installer": true,Ð "dealerdirect/phpcodesniffer-composer-installer": true,Ð "ramsey/composer-repl": trueÐ },Ð "sort-packages": trueÐ },Ð "extra": {Ð "captainhook": {Ð "force-install": trueÐ }Ð },Ð "scripts": {Ð "analyze": [Ð "@phpstan",Ð "@psalm"Ð],Ð "build:clean": "git clean -fX build/",Ð "lint": "parallel-lint src tests",Ð "lint:paths": "parallel-lint",Ð "phpbench": "phpbench run",Ð "phpcbf": "phpcbf -vpw --cache=build/cache/phpcs.cache",Ð "phpcs": "phpcs --cache=build/cache/phpcs.cache",Ð "phpstan": [Ð "phpstan analyse --no-progress --memory-limit=1G",Ð "phpstan analyse -c phpstan-tests.neon --no-progress --memory-limit=1G"Ð],Ð "phpunit": "phpunit --verbose --colors=always",Ð "phpunit-coverage": "phpunit --verbose --colors=always --coverage-html build/coverage",Ð "psalm": "psalm --show-info=false --config=psalm.xml",Ð "test": [Ð "@lint",Ð "@phpbench",Ð "@phpcs",Ð "@phpstan",Ð "@psalm",Ð "@phpunit"Ð]Ð }ÐÐ

vendor\sabberworm\php-css-parser\composer.json

{Ð "name": "sabberworm/php-css-parser",Ð "type": "library",Ð "description": "Parser for CSS Files written in PHP",Ð "keywords": [Ð "parser",Ð "css",Ð "stylesheet"Ð],Ð "homepage": "https://www.sabberworm.com/blog/2010/6/10/php-css-parser",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Raphael Schweikert"Ð },Ð {Ð "name": "Oliver Klee",Ð "email": "github@oliverklee.de"Ð },Ð {Ð "name": "Jake Hotson",Ð "email": "jake.github@qzdesign.co.uk"Ð }Ð],Ð "require": {Ð "php": "^5.6.20 || ^7.0.0 || ~8.0.0 || ~8.1.0 || ~8.2.0 || ~8.3.0 || ~8.4.0",Ð "ext-iconv": "*"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "5.7.27 || 6.5.14 || 7.5.20 || 8.5.41"Ð },Ð "suggest": {Ð "ext-mbstring": "for parsing UTF-8 CSS"Ð },Ð "autoload": {Ð "psr-4": {Ð "Sabberworm\\CSS\\": "src/"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Sabberworm\\CSS\\Tests\\": "tests/"Ð }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-main": "9.0.x-dev"Ð }Ð }ÐÐ

vendor\sebastian\cli-parser\composer.json

{Ð   "name": "sebastian/cli-parser",Ð   "description": "Library for parsing CLI options",Ð   "type": "library",Ð   "homepage": "https://github.com/sebastianbergmann/cli-parser",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/cli-parser/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\cli-parser\infection.json

```
{Ð   "source": {Ð       "directories": [Ð           "src"Ð       ]Ð   },Ð
"mutators": {Ð       "@default": trueÐ   },Ð   "minMsi": 100,Ð
"minCoveredMsi": 100ÐÐ
```

vendor\sebastian\code-unit\composer.json

{Ð   "name": "sebastian/code-unit",Ð   "description": "Collection of value objects that represent the PHP code units",Ð   "type": "library",Ð   "homepage": "https://github.com/sebastianbergmann/code-unit",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/code-unit/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture"Ð   ],Ð   "files": [Ð   "tests/_fixture/file_with_multiple_code_units.php",Ð   "tests/_fixture/function.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\code-unit-reverse-lookup\composer.json

{Đ   "name": "sebastian/code-unit-reverse-lookup",Đ   "description": "Looks up which function or method a line of code belongs to",Đ   "homepage": "https://github.com/sebastianbergmann/code-unit-reverse-lookup/",Đ   "license": "BSD-3-Clause",Đ   "authors": [Đ   {Đ   "name": "Sebastian Bergmann",Đ   "email": "sebastian@phpunit.de"Đ   }Đ   ],Đ   "prefer-stable": true,Đ   "config": {Đ   "platform": {Đ   "php": "7.3.0"Đ   },Đ   "optimize-autoloader": true,Đ   "sort-packages": trueĐ   },Đ   "require": {Đ   "php": ">=7.3"Đ   },Đ   "require-dev": {Đ   "phpunit/phpunit": "^9.3"Đ   },Đ   "autoload": {Đ   "classmap": [Đ   "src/"Đ   ]Đ   },Đ   "extra": {Đ   "branch-alias": {Đ   "dev-master": "2.0-dev"Đ   }Đ   }Đ}

vendor\sebastian\comparator\composer.json

{Ð   "name": "sebastian/comparator",Ð   "description": "Provides the functionality to compare PHP values for equality",Ð   "keywords": ["comparator","compare","equality"],Ð   "homepage": "https://github.com/sebastianbergmann/comparator",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   },Ð   {Ð   "name": "Jeff Welch",Ð   "email": "whatthejeff@gmail.com"Ð   },Ð   {Ð   "name": "Volker Dusch",Ð   "email": "github@wallbash.com"Ð   },Ð   {Ð   "name": "Bernhard Schussek",Ð   "email": "bschussek@2bepublished.at"Ð   }Ð   ],Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "sebastian/diff": "^4.0",Ð   "sebastian/exporter": "^4.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "4.0-dev"Ð   }Ð   }Ð}Ð

vendor\sebastian\complexity\composer.json

{Ð   "name": "sebastian/complexity",Ð   "description": "Library for calculating the complexity of PHP code units",Ð   "type": "library",Ð   "homepage": "https://github.com/sebastianbergmann/complexity",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/complexity/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "nikic/php-parser": "^4.18 || ^5.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "2.0-dev"Ð   }Ð   }Ð}ÐÐ

vendor\sebastian\diff\composer.json


```
{Ð   "name": "sebastian/diff",Ð   "description": "Diff implementation",Ð
"keywords": ["diff", "udiff", "unidiff", "unified diff"],Ð   "homepage":
"https://github.com/sebastianbergmann/diff",Ð   "license": "BSD-3-Clause",Ð
"authors": [Ð       {Ð           "name": "Sebastian Bergmann",Ð
"email": "sebastian@phpunit.de"Ð       },Ð       {Ð           "name": "Kore
Nordmann",Ð           "email": "mail@kore-nordmann.de"Ð       }Ð   ],Ð
"prefer-stable": true,Ð   "config": {Ð       "platform": {Ð           "php":
"7.3.0"Ð       },Ð       "optimize-autoloader": true,Ð       "sort-packages":
trueÐ   },Ð   "require": {Ð       "php": ">=7.3"Ð   },Ð   "require-dev": {Ð
        "phpunit/phpunit": "^9.3",Ð       "symfony/process": "^4.2 || ^5"Ð
    },Ð   "autoload": {Ð       "classmap": [Ð           "src/"Ð       ]Ð   },Ð
    "autoload-dev": {Ð       "classmap": [Ð           "tests/"Ð       ]Ð   },Ð
    "extra": {Ð       "branch-alias": {Ð           "dev-master": "4.0-dev"Ð
        }Ð   }Ð}ÐÐ
```

vendor\sebastian\environment\composer.json

{Ð   "name": "sebastian/environment",Ð   "description": "Provides functionality to handle HHVM/PHP environments",Ð   "keywords": ["environment","hhvm","xdebug"],Ð   "homepage": "http://www.github.com/sebastianbergmann/environment",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   }Ð   ],Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "suggest": {Ð   "ext-posix": "*"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "5.1-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\exporter\composer.json

{Ð   "name": "sebastian/exporter",Ð   "description": "Provides the functionality to export PHP variables for visualization",Ð   "keywords": ["exporter","export"],Ð   "homepage": "https://www.github.com/sebastianbergmann/exporter",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   },Ð   {Ð   "name": "Jeff Welch",Ð   "email": "whatthejeff@gmail.com"Ð   },Ð   {Ð   "name": "Volker Dusch",Ð   "email": "github@wallbash.com"Ð   },Ð   {Ð   "name": "Adam Harvey",Ð   "email": "aharvey@php.net"Ð   },Ð   {Ð   "name": "Bernhard Schussek",Ð   "email": "bschussek@gmail.com"Ð   }Ð   ],Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "sebastian/recursion-context": "^4.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3",Ð   "ext-mbstring": "*"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "4.0-dev"Ð   }Ð   }Ð}Ð

vendor\sebastian\global-state\composer.json

{Ð   "name": "sebastian/global-state",Ð   "description": "Snapshotting of global state",Ð   "keywords": ["global state"],Ð   "homepage": "http://www.github.com/sebastianbergmann/global-state",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð "email": "sebastian@phpunit.de"Ð   }Ð   ],Ð   "prefer-stable": true,Ð "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3",Ð   "sebastian/object-reflector": "^2.0",Ð "sebastian/recursion-context": "^4.0"Ð   },Ð   "require-dev": {Ð   "ext-dom": "*",Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "suggest": {Ð   "ext-uopz": "*"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture/"Ð   ],Ð   "files": [Ð   "tests/_fixture/SnapshotFunctions.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "5.0-dev"Ð   }Ð   }Ð}Ð

vendor\sebastian\lines-of-code\composer.json

{Ð   "name": "sebastian/lines-of-code",Ð   "description": "Library for counting the lines of code in PHP source code",Ð   "type": "library",Ð   "homepage": "https://github.com/sebastianbergmann/lines-of-code",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/lines-of-code/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3",Ð   "nikic/php-parser": "^4.18 || ^5.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "1.0-dev"Ð   }Ð   }Ð}

vendor\sebastian\object-enumerator\composer.json

{Ð   "name": "sebastian/object-enumerator",Ð   "description": "Traverses array structures and object graphs to enumerate all referenced objects",Ð "homepage": "https://github.com/sebastianbergmann/object-enumerator/",Ð "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   }Ð   ],Ð   "prefer-stable": true,Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3",Ð   "sebastian/object-reflector": "^2.0",Ð   "sebastian/recursion-context": "^4.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "4.0-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\object-reflector\composer.json

{Ð   "name": "sebastian/object-reflector",Ð   "description": "Allows reflection of object attributes, including inherited and non-public ones",Ð   "homepage": "https://github.com/sebastianbergmann/object-reflector/",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   }Ð   ],Ð   "prefer-stable": true,Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "2.0-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\recursion-context\composer.json

{Ð   "name": "sebastian/recursion-context",Ð   "description": "Provides functionality to recursively process PHP variables",Ð   "homepage": "https://github.com/sebastianbergmann/recursion-context",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   },Ð   {Ð   "name": "Jeff Welch",Ð   "email": "whatthejeff@gmail.com"Ð   },Ð   {Ð   "name": "Adam Harvey",Ð   "email": "aharvey@php.net"Ð   }Ð   ],Ð   "prefer-stable": true,Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "4.0-dev"Ð   }Ð   }ÐÐ}

vendor\sebastian\resource-operations\composer.json

{Ð   "name": "sebastian/resource-operations",Ð   "description": "Provides a list of PHP built-in functions that operate on resources",Ð   "homepage": "https://www.github.com/sebastianbergmann/resource-operations",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de"Ð   }Ð   ],Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.0"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "3.0-dev"Ð   }Ð   },Ð   "abandoned": falseÐ}

vendor\sebastian\type\composer.json

{Ð   "name": "sebastian/type",Ð   "description": "Collection of value objects that represent the types of the PHP type system",Ð   "type": "library",Ð   "homepage": "https://github.com/sebastianbergmann/type",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/type/issues"Ð   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "^9.5"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "classmap": [Ð   "tests/_fixture"Ð   ],Ð   "files": [Ð   "tests/_fixture/callback_function.php",Ð   "tests/_fixture/functions_that_declare_return_types.php"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.2-dev"Ð   }Ð   }Ð}ÐÐ

vendor\sebastian\version\composer.json

{Ð   "name": "sebastian/version",Ð   "description": "Library that helps with managing the version number of Git-hosted PHP projects",Ð   "homepage": "https://github.com/sebastianbergmann/version",Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Sebastian Bergmann",Ð   "email": "sebastian@phpunit.de",Ð   "role": "lead"Ð   }Ð   ],Ð   "support": {Ð   "issues": "https://github.com/sebastianbergmann/version/issues"Ð   },Ð   "config": {Ð   "platform": {Ð   "php": "7.3.0"Ð   },Ð   "optimize-autoloader": true,Ð   "sort-packages": trueÐ   },Ð   "prefer-stable": true,Ð   "require": {Ð   "php": ">=7.3"Ð   },Ð   "autoload": {Ð   "classmap": [Ð   "src/"Ð   ]Ð   },Ð   "extra": {Ð   "branch-alias": {Ð   "dev-master": "3.0-dev"Ð   }Ð   }ÐÐ}

vendor\spatie\backtrace\composer.json

{Ð   "name": "spatie/backtrace",Ð   "description": "A better backtrace",Ð
"license": "MIT",Ð   "keywords": [Ð   "spatie",Ð   "backtrace"Ð   ],Ð
    "authors": [Ð   {Ð   "name": "Freek Van de Herten",Ð
            "email": "freek@spatie.be",Ð   "homepage": "https://
spatie.be",Ð   "role": "Developer"Ð   }Ð   ],Ð   "homepage":
"https://github.com/spatie/backtrace",Ð   "funding": [Ð   {Ð
"type": "github",Ð   "url": "https://github.com/sponsors/spatie"Ð
        },Ð   {Ð   "type": "other",Ð   "url": "https://
spatie.be/open-source/support-us"Ð   }Ð   ],Ð   "require": {Ð
"php": "^7.3 || ^8.0"Ð   },Ð   "require-dev": {Ð   "ext-json": "*",Ð
        "laravel/serializable-closure": "^1.3 || ^2.0",Ð   "phpunit/
phpunit": "^9.3 || ^11.4.3",Ð   "spatie/phpunit-snapshot-assertions":
"^4.2 || ^5.1.6",Ð   "symfony/var-dumper": "^5.1 || ^6.0 || ^7.0"Ð   },Ð
    "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "autoload": {Ð
        "psr-4": {Ð   "Spatie\\Backtrace\\": "src"Ð   }Ð   },Ð
"autoload-dev": {Ð   "psr-4": {Ð   "Spatie\\Backtrace\\Tests\\":
"tests"Ð   }Ð   },Ð   "config": {Ð   "sort-packages": trueÐ   },Ð
"scripts": {Ð   "format": "vendor/bin/php-cs-fixer fix --allow-risky=yes",Ð
        "psalm": "vendor/bin/psalm",Ð   "test": "vendor/bin/phpunit",Ð
        "test-coverage": "vendor/bin/phpunit --coverage-html coverage"Ð   }Ð
}Ð

vendor\spatie\flare-client-php\composer.json

{Ð   "name": "spatie/flare-client-php",Ð   "description": "Send PHP errors to Flare",Ð   "keywords": [Ð   "spatie",Ð   "flare",Ð   "exception",Ð   "reporting"Ð   ],Ð   "homepage": "https://github.com/spatie/flare-client-php",Ð   "license": "MIT",Ð   "require": {Ð   "php": "^8.0",Ð   "illuminate/pipeline": "^8.0|^9.0|^10.0|^11.0|^12.0",Ð   "spatie/backtrace": "^1.6.1",Ð   "symfony/http-foundation": "^5.2|^6.0|^7.0",Ð   "symfony/mime": "^5.2|^6.0|^7.0",Ð   "symfony/process": "^5.2|^6.0|^7.0",Ð   "symfony/var-dumper": "^5.2|^6.0|^7.0"Ð   },Ð   "require-dev": {Ð   "dms/phpunit-arraysubset-asserts": "^0.5.0",Ð   "phpstan/extension-installer": "^1.1",Ð   "phpstan/phpstan-deprecation-rules": "^1.0",Ð   "phpstan/phpstan-phpunit": "^1.0",Ð   "spatie/pest-plugin-snapshots": "^1.0|^2.0",Ð   "pestphp/pest": "^1.20|^2.0"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Spatie\\FlareClient\\": "src"Ð   },Ð   "files": [Ð   "src/helpers.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Spatie\\FlareClient\\Tests\\": "tests"Ð   }Ð   },Ð   "scripts": {Ð   "analyse": "vendor/bin/phpstan analyse",Ð   "baseline": "vendor/bin/phpstan analyse --generate-baseline",Ð   "format": "vendor/bin/php-cs-fixer fix --allow-risky=yes",Ð   "test": "vendor/bin/pest",Ð   "test-coverage": "vendor/bin/phpunit --coverage-html coverage"Ð   },Ð   "config": {Ð   "sort-packages": true,Ð   "allow-plugins": {Ð   "pestphp/pest-plugin": true,Ð   "phpstan/extension-installer": trueÐ   }Ð   },Ð   "prefer-stable": true,Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "1.3.x-dev"Ð   }Ð   }Ð}Ð

vendor\spatie\ignition\composer.json

{Ð   "name" : "spatie/ignition",Ð   "description" : "A beautiful error page for PHP applications.",Ð   "keywords" : [Ð   "error",Ð   "page",Ð   "laravel",Ð   "flare"Ð   ],Ð   "authors" : [Ð   {Ð "name" : "Spatie",Ð   "email" : "info@spatie.be",Ð   "role" : "Developer"Ð   }Ð   ],Ð   "homepage": "https://flareapp.io/ignition",Ð "license": "MIT",Ð   "require": {Ð   "php": "^8.0",Ð   "ext-json": "*",Ð   "ext-mbstring": "*",Ð   "spatie/backtrace": "^1.5.3",Ð "spatie/flare-client-php": "^1.4.0",Ð   "symfony/console": "^5.4|^6.0|^7.0",Ð   "symfony/var-dumper": "^5.4|^6.0|^7.0"Ð   },Ð   "require-dev" : {Ð   "illuminate/cache" : "^9.52|^10.0|^11.0",Ð   "mockery/mockery" : "^1.4",Ð   "pestphp/pest" : "^1.20|^2.0",Ð   "phpstan/extension-installer" : "^1.1",Ð   "phpstan/phpstan-deprecation-rules" : "^1.0",Ð   "phpstan/phpstan-phpunit" : "^1.0",Ð   "psr/simple-cache-implementation" : "*",Ð   "symfony/cache" : "^5.4|^6.0|^7.0",Ð "symfony/process" : "^5.4|^6.0|^7.0",Ð   "vlucas/phpdotenv" : "^5.5"Ð   },Ð   "suggest" : {Ð   "openai-php/client" : "Require get solutions from OpenAI",Ð   "simple-cache-implementation" : "To cache solutions from OpenAI"Ð   },Ð   "config" : {Ð   "sort-packages" : true,Ð   "allow-plugins" : {Ð   "phpstan/extension-installer": true,Ð "pestphp/pest-plugin": true,Ð   "php-http/discovery": falseÐ   }Ð   },Ð   "autoload" : {Ð   "psr-4" : {Ð   "Spatie\\Ignition\\" : "src"Ð   }Ð   },Ð   "autoload-dev" : {Ð   "psr-4" : {Ð "Spatie\\Ignition\\Tests\\" : "tests"Ð   }Ð   },Ð   "minimum-stability" : "dev",Ð   "prefer-stable" : true,Ð   "scripts" : {Ð   "analyse" : "vendor/bin/phpstan analyse",Ð   "baseline" : "vendor/bin/phpstan analyse --generate-baseline",Ð   "format" : "vendor/bin/php-cs-fixer fix --allow-risky=yes",Ð   "test" : "vendor/bin/pest",Ð   "test-coverage" : "vendor/bin/phpunit --coverage-html coverage"Ð   },Ð   "support" : {Ð "issues" : "https://github.com/spatie/ignition/issues",Ð   "forum" : "https://twitter.com/flareappio",Ð   "source" : "https://github.com/spatie/ignition",Ð   "docs" : "https://flareapp.io/docs/ignition-for-laravel/introduction"Ð   },Ð   "extra" : {Ð   "branch-alias" : {Ð   "dev-main" : "1.5.x-dev"Ð   }Ð   }}ÐÐ

vendor\spatie\laravel-ignition\composer.json

{Ð   "name": "spatie/laravel-ignition",Ð   "description": "A beautiful error page for Laravel applications.",Ð   "keywords": [Ð   "error",Ð   "page",Ð   "laravel",Ð   "flare"Ð   ],Ð   "authors": [Ð   {Ð   "name": "Spatie",Ð   "email": "info@spatie.be",Ð   "role": "Developer"Ð   }Ð   ],Ð   "homepage": "https://flareapp.io/ignition",Ð   "license": "MIT",Ð   "require": {Ð   "php": "^8.0",Ð   "ext-curl": "*",Ð   "ext-json": "*",Ð   "ext-mbstring": "*",Ð   "monolog/monolog": "^2.3",Ð   "spatie/ignition": "<= 1.14.2",Ð   "spatie/flare-client-php": "^1.0.1",Ð   "symfony/console": "^5.0|^6.0",Ð   "symfony/var-dumper": "^5.0|^6.0",Ð   "illuminate/support": "^8.77|^9.27"Ð   },Ð   "require-dev": {Ð   "filp/whoops": "^2.14",Ð   "livewire/livewire": "^2.8|dev-develop",Ð   "mockery/mockery": "^1.4",Ð   "nunomaduro/larastan": "^1.0",Ð   "orchestra/testbench": "^6.23|^7.0",Ð   "pestphp/pest": "^1.20",Ð   "phpstan/extension-installer": "^1.1",Ð   "phpstan/phpstan-deprecation-rules": "^1.0",Ð   "phpstan/phpstan-phpunit": "^1.0",Ð   "spatie/laravel-ray": "^1.27"Ð   },Ð   "config": {Ð   "sort-packages": true,Ð   "allow-plugins": {Ð   "phpstan/extension-installer": true,Ð   "pestphp/pest-plugin": trueÐ   }Ð   },Ð   "extra": {Ð   "laravel": {Ð   "providers": [Ð   "Spatie\\LaravelIgnition\\IgnitionServiceProvider"Ð   ],Ð   "aliases": {Ð   "Flare": "Spatie\\LaravelIgnition\\Facades\\Flare"Ð   }Ð   }Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Spatie\\LaravelIgnition\\": "src"Ð   },Ð   "files": [Ð   "src/helpers.php"Ð   ]Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Spatie\\LaravelIgnition\\Tests\\": "tests"Ð   }Ð   },Ð   "minimum-stability": "dev",Ð   "prefer-stable": true,Ð   "scripts": {Ð   "analyse": "vendor/bin/phpstan analyse",Ð   "baseline": "vendor/bin/phpstan --generate-baseline",Ð   "format": "vendor/bin/php-cs-fixer fix --allow-risky=yes",Ð   "test": "vendor/bin/pest",Ð   "test-coverage": "vendor/bin/phpunit --coverage-html coverage"Ð   },Ð   "support": {Ð   "issues": "https://github.com/spatie/laravel-ignition/issues",Ð   "forum": "https://twitter.com/flareappio",Ð   "source": "https://github.com/spatie/laravel-ignition",Ð   "docs": "https://flareapp.io/docs/ignition-for-laravel/introduction"Ð   }Ð}Ð

vendor\stripe\stripe-php\composer.json

{Ð "name": "stripe/stripe-php",Ð "description": "Stripe PHP Library",Ð "keywords": [Ð "stripe",Ð "payment processing",Ð "api"Ð],Ð "homepage": "https://stripe.com/",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Stripe and contributors",Ð "homepage": "https://github.com/stripe/stripe-php/contributors"Ð }Ð],Ð "require": {Ð "php": ">=5.3.3",Ð "ext-curl": "*",Ð "ext-json": "*",Ð "ext-mbstring": "*"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "~4.0",Ð "satooshi/php-coveralls": "~0.6.1",Ð "squizlabs/php_codesniffer": "~2.0"Ð },Ð "autoload": {Ð "psr-4": { "Stripe\\" : "lib/" }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.0-dev"Ð }Ð }Ð }Ð

vendor\symfony\browser-kit\composer.json

{   "name": "symfony/browser-kit",   "type": "library",   "description": "Simulates the behavior of a web browser, allowing you to make requests, click on links and submit forms programmatically",   "keywords": [], "homepage": "https://symfony.com",   "license": "MIT",   "authors": [{   "name": "Fabien Potencier",   "email": "fabien@symfony.com"   },   {   "name": "Symfony Community",   "homepage": "https://symfony.com/contributors"   }   ],   "require": {   "php": ">=8.2",   "symfony/dom-crawler": "^6.4|^7.0"   },   "require-dev": {   "symfony/css-selector": "^6.4|^7.0",   "symfony/http-client": "^6.4|^7.0",   "symfony/mime": "^6.4|^7.0",   "symfony/process": "^6.4|^7.0"   },   "autoload": {   "psr-4": { "Symfony\\Component\\BrowserKit\\": "" },   "exclude-from-classmap": ["/Tests/"   ]   },   "minimum-stability": "dev"}

vendor\symfony\console\composer.json

{Ð   "name": "symfony/console",Ð   "type": "library",Ð   "description": "Eases the creation of beautiful and testable command line interfaces",Ð   "keywords": ["console", "cli", "command-line", "terminal"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-contracts": "^2.5|^3",Ð   "symfony/polyfill-mbstring": "~1.0",Ð   "symfony/service-contracts": "^2.5|^3",Ð   "symfony/string": "^5.4|^6.0|^7.0"Ð   },Ð   "require-dev": {Ð   "symfony/config": "^5.4|^6.0|^7.0",Ð   "symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð   "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð   "symfony/http-foundation": "^6.4|^7.0",Ð   "symfony/http-kernel": "^6.4|^7.0",Ð   "symfony/lock": "^5.4|^6.0|^7.0",Ð   "symfony/messenger": "^5.4|^6.0|^7.0",Ð   "symfony/process": "^5.4|^6.0|^7.0",Ð   "symfony/stopwatch": "^5.4|^6.0|^7.0",Ð   "symfony/var-dumper": "^5.4|^6.0|^7.0",Ð   "psr/log": "^1|^2|^3"Ð   },Ð   "provide": {Ð   "psr/log-implementation": "1.0|2.0|3.0"Ð   },Ð   "conflict": {Ð   "symfony/dependency-injection": "<5.4",Ð   "symfony/dotenv": "<5.4",Ð   "symfony/event-dispatcher": "<5.4",Ð   "symfony/lock": "<5.4",Ð   "symfony/process": "<5.4"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Console\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\css-selector\composer.json

{Ð   "name": "symfony/css-selector",Ð   "type": "library",Ð   "description": "Converts CSS selectors to XPath expressions",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Jean-François Simon",Ð   "email": "jeanfrancois.simon@sensiolabs.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.2"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\CssSelector\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"ÐÐ}

vendor\symfony\deprecation-contracts\composer.json

{Ð   "name": "symfony/deprecation-contracts",Ð   "type": "library",Ð   "description": "A generic function and convention to trigger deprecation notices",Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1"Ð   },Ð   "autoload": {Ð   "files": [Ð   "function.php"Ð   ]Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "3.5-dev"Ð   },Ð   "thanks": {Ð   "name": "symfony/contracts",Ð   "url": "https://github.com/symfony/contracts"Ð   }Ð   }Ð}

vendor\symfony\dom-crawler\composer.json

{   "name": "symfony/dom-crawler",   "type": "library",   "description": "Eases DOM navigation for HTML and XML documents",   "keywords": [], "homepage": "https://symfony.com",   "license": "MIT",   "authors": [{   "name": "Fabien Potencier",   "email": "fabien@symfony.com"   },   {   "name": "Symfony Community",   "homepage": "https://symfony.com/contributors"   }   ],   "require": {   "php": ">=8.2",   "symfony/polyfill-ctype": "~1.8",   "symfony/polyfill-mbstring": "~1.0", "masterminds/html5": "^2.6"   },   "require-dev": {   "symfony/css-selector": "^6.4|^7.0"   },   "autoload": {   "psr-4": { "Symfony\\Component\\DomCrawler\\": "" },   "exclude-from-classmap": ["/Tests/"   ]   },   "minimum-stability": "dev"}

vendor\symfony\error-handler\composer.json

{Ð   "name": "symfony/error-handler",Ð   "type": "library",Ð   "description": "Provides tools to manage errors and ease debugging PHP code",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "psr/log": "^1|^2|^3",Ð   "symfony/var-dumper": "^5.4|^6.0|^7.0"Ð   },Ð   "require-dev": {Ð   "symfony/http-kernel": "^6.4|^7.0",Ð   "symfony/serializer": "^5.4|^6.0|^7.0",Ð   "symfony/deprecation-contracts": "^2.5|^3"Ð   },Ð   "conflict": {Ð   "symfony/deprecation-contracts": "<2.5",Ð   "symfony/http-kernel": "<6.4"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\ErrorHandler\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "bin": [Ð   "Resources/bin/patch-type-declarations"Ð   ],Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\event-dispatcher\composer.json

{Ð   "name": "symfony/event-dispatcher",Ð   "type": "library",Ð
"description": "Provides tools that allow your application components to
communicate with each other by dispatching events and listening to them",Ð
"keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð
"authors": [Ð   {Ð   "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony
Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð
    ],Ð   "require": {Ð   "php": ">=8.2",Ð   "symfony/event-
dispatcher-contracts": "^2.5|^3"Ð   },Ð   "require-dev": {Ð   "symfony/
dependency-injection": "^6.4|^7.0",Ð   "symfony/expression-language":
"^6.4|^7.0",Ð   "symfony/config": "^6.4|^7.0",Ð   "symfony/error-
handler": "^6.4|^7.0",Ð   "symfony/http-foundation": "^6.4|^7.0",Ð
"symfony/service-contracts": "^2.5|^3",Ð   "symfony/stopwatch": "^6.4|
^7.0",Ð   "psr/log": "^1|^2|^3"Ð   },Ð   "conflict": {Ð   "symfony/
dependency-injection": "<6.4",Ð   "symfony/service-contracts": "<2.5"Ð
    },Ð   "provide": {Ð   "psr/event-dispatcher-implementation": "1.0",Ð
        "symfony/event-dispatcher-implementation": "2.0|3.0"Ð   },Ð
"autoload": {Ð   "psr-4": { "Symfony\\Component\\EventDispatcher\\": "" },Ð
        "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð
"minimum-stability": "dev"Ð}Ð

vendor\symfony\event-dispatcher-contracts\composer.json

{Ð   "name": "symfony/event-dispatcher-contracts",Ð   "type": "library",Ð
"description": "Generic abstractions related to dispatching event",Ð
"keywords": ["abstractions", "contracts", "decoupling", "interfaces",
"interoperability", "standards"],Ð   "homepage": "https://symfony.com",Ð
"license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas
Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð
"name": "Symfony Community",Ð   "homepage": "https://symfony.com/
contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð
"psr/event-dispatcher": "^1"Ð   },Ð   "autoload": {Ð   "psr-4":
{ "Symfony\\Contracts\\EventDispatcher\\": "" }Ð   },Ð   "minimum-stability":
"dev",Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "3.5-dev"Ð
        },Ð   "thanks": {Ð   "name": "symfony/contracts",Ð
            "url": "https://github.com/symfony/contracts"Ð   }Ð   }Ð}

vendor\symfony\finder\composer.json

{Đ   "name": "symfony/finder",Đ   "type": "library",Đ   "description": "Finds files and directories via an intuitive fluent interface",Đ   "keywords": [],Đ   "homepage": "https://symfony.com",Đ   "license": "MIT",Đ   "authors": [Đ   {Đ   "name": "Fabien Potencier",Đ   "email": "fabien@symfony.com"Đ   },Đ   {Đ   "name": "Symfony Community",Đ   "homepage": "https://symfony.com/contributors"Đ   }Đ   ],Đ   "require": {Đ   "php": ">=8.1"Đ   },Đ   "require-dev": {Đ   "symfony/filesystem": "^6.0|^7.0"Đ   },Đ   "autoload": {Đ   "psr-4": { "Symfony\\Component\\Finder\\": "" },Đ   "exclude-from-classmap": [Đ   "/Tests/"Đ   ]Đ   },Đ   "minimum-stability": "dev"Đ }Đ

vendor\symfony\http-client\composer.json

{   "name": "symfony/http-client",   "type": "library",   "description": "Provides powerful methods to fetch HTTP resources synchronously or asynchronously",   "keywords": ["http"],   "homepage": "https://symfony.com",   "license": "MIT",   "authors": [{   "name": "Nicolas Grekas",   "email": "p@tchwork.com"   },   {   "name": "Symfony Community",   "homepage": "https://symfony.com/contributors"   }   ],   "provide": {   "php-http/async-client-implementation": "*",   "php-http/client-implementation": "*",   "psr/http-client-implementation": "1.0",   "symfony/http-client-implementation": "3.0"   },   "require": {   "php": ">=8.2",   "psr/log": "^1|^2|^3",   "symfony/deprecation-contracts": "^2.5|^3",   "symfony/http-client-contracts": "~3.4.4|^3.5.2",   "symfony/service-contracts": "^2.5|^3"   },   "require-dev": {   "amphp/http-client": "^4.2.1|^5.0",   "amphp/http-tunnel": "^1.0|^2.0",   "amphp/socket": "^1.1",   "guzzlehttp/promises": "^1.4|^2.0",   "nyholm/psr7": "^1.0",   "php-http/httplug": "^1.0|^2.0",   "psr/http-client": "^1.0",   "symfony/amphp-http-client-meta": "^1.0|^2.0",   "symfony/dependency-injection": "^6.4|^7.0",   "symfony/http-kernel": "^6.4|^7.0",   "symfony/messenger": "^6.4|^7.0",   "symfony/process": "^6.4|^7.0",   "symfony/rate-limiter": "^6.4|^7.0",   "symfony/stopwatch": "^6.4|^7.0"   },   "conflict": {   "amphp/amp": "<2.5",   "php-http/discovery": "<1.15",   "symfony/http-foundation": "<6.4"   },   "autoload": {   "psr-4": { "Symfony\\Component\\HttpClient\\": "" },   "exclude-from-classmap": ["/Tests/"   ]   },   "minimum-stability": "dev"}

vendor\symfony\http-client-contracts\composer.json


```
{    "name": "symfony/http-client-contracts",    "type": "library",
"description": "Generic abstractions related to HTTP clients",    "keywords":
["abstractions", "contracts", "decoupling", "interfaces", "interoperability",
"standards"],    "homepage": "https://symfony.com",    "license": "MIT",
"authors": [        {            "name": "Nicolas Grekas",
"email": "p@tchwork.com"        },        {            "name": "Symfony
Community",            "homepage": "https://symfony.com/contributors"        }
    ],    "require": {        "php": ">=8.1"    },    "autoload": {
"psr-4": { "Symfony\\Contracts\\HttpClient\\": "" },        "exclude-from-
classmap": [            "/Test/"        ]    },    "minimum-stability": "dev",
    "extra": {        "branch-alias": {            "dev-main": "3.5-dev"
        },        "thanks": {            "name": "symfony/contracts",
            "url": "https://github.com/symfony/contracts"        }    }}
```

vendor\symfony\http-foundation\composer.json

{Ð   "name": "symfony/http-foundation",Ð   "type": "library",Ð
"description": "Defines an object-oriented layer for the HTTP specification",Ð
    "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð
    "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð
"email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony
Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð
    ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-
contracts": "^2.5|^3",Ð   "symfony/polyfill-mbstring": "~1.1",Ð
"symfony/polyfill-php83": "^1.27"Ð   },Ð   "require-dev": {Ð   "doctrine/
dbal": "^2.13.1|^3|^4",Ð   "predis/predis": "^1.1|^2.0",Ð   "symfony/
cache": "^6.4.12|^7.1.5",Ð   "symfony/dependency-injection": "^5.4|^6.0|
^7.0",Ð   "symfony/http-kernel": "^5.4.12|^6.0.12|^6.1.4|^7.0",Ð
"symfony/mime": "^5.4|^6.0|^7.0",Ð   "symfony/expression-language": "^5.4|
^6.0|^7.0",Ð   "symfony/rate-limiter": "^5.4|^6.0|^7.0"Ð   },Ð
"conflict": {Ð   "symfony/cache": "<6.4.12|>=7.0,<7.1.5"Ð   },Ð
"autoload": {Ð   "psr-4": { "Symfony\\Component\\HttpFoundation\\": "" },Ð
        "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð
"minimum-stability": "dev"Ð}Ð

vendor\symfony\http-kernel\composer.json

{Ð   "name": "symfony/http-kernel",Ð   "type": "library",Ð   "description": "Provides a structured process for converting a Request into a Response",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-contracts": "^2.5|^3",Ð   "symfony/error-handler": "^6.4|^7.0",Ð   "symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð   "symfony/http-foundation": "^6.4|^7.0",Ð   "symfony/polyfill-ctype": "^1.8",Ð   "psr/log": "^1|^2|^3"Ð   },Ð   "require-dev": {Ð   "symfony/browser-kit": "^5.4|^6.0|^7.0",Ð   "symfony/clock": "^6.2|^7.0",Ð   "symfony/config": "^6.1|^7.0",Ð   "symfony/console": "^5.4|^6.0|^7.0",Ð   "symfony/css-selector": "^5.4|^6.0|^7.0",Ð   "symfony/dependency-injection": "^6.4|^7.0",Ð   "symfony/dom-crawler": "^5.4|^6.0|^7.0",Ð   "symfony/expression-language": "^5.4|^6.0|^7.0",Ð   "symfony/finder": "^5.4|^6.0|^7.0",Ð   "symfony/http-client-contracts": "^2.5|^3",Ð   "symfony/process": "^5.4|^6.0|^7.0",Ð   "symfony/property-access": "^5.4.5|^6.0.5|^7.0",Ð   "symfony/routing": "^5.4|^6.0|^7.0",Ð   "symfony/serializer": "^6.4.4|^7.0.4",Ð   "symfony/stopwatch": "^5.4|^6.0|^7.0",Ð   "symfony/translation": "^5.4|^6.0|^7.0",Ð   "symfony/translation-contracts": "^2.5|^3",Ð   "symfony/uid": "^5.4|^6.0|^7.0",Ð   "symfony/validator": "^6.4|^7.0",Ð   "symfony/var-dumper": "^5.4|^6.4|^7.0",Ð   "symfony/var-exporter": "^6.2|^7.0",Ð   "psr/cache": "^1.0|^2.0|^3.0",Ð   "twig/twig": "^2.13|^3.0.4"Ð   },Ð   "provide": {Ð   "psr/log-implementation": "1.0|2.0|3.0"Ð   },Ð   "conflict": {Ð   "symfony/browser-kit": "<5.4",Ð   "symfony/cache": "<5.4",Ð   "symfony/config": "<6.1",Ð   "symfony/console": "<5.4",Ð   "symfony/form": "<5.4",Ð   "symfony/dependency-injection": "<6.4",Ð   "symfony/doctrine-bridge": "<5.4",Ð   "symfony/http-client": "<5.4",Ð   "symfony/http-client-contracts": "<2.5",Ð   "symfony/mailer": "<5.4",Ð   "symfony/messenger": "<5.4",Ð   "symfony/translation": "<5.4",Ð   "symfony/translation-contracts": "<2.5",Ð   "symfony/twig-bridge": "<5.4",Ð   "symfony/validator": "<6.4",Ð   "symfony/var-dumper": "<6.3",Ð   "twig/twig": "<2.13"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\HttpKernel\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\mailer\composer.json

{Ð   "name": "symfony/mailer",Ð   "type": "library",Ð   "description": "Helps sending emails",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "egulias/email-validator": "^2.1.10|^3|^4",Ð   "psr/event-dispatcher": "^1",Ð   "psr/log": "^1|^2|^3",Ð   "symfony/event-dispatcher": "^5.4|^6.0|^7.0",Ð   "symfony/mime": "^6.2|^7.0",Ð   "symfony/service-contracts": "^2.5|^3"Ð   },Ð   "require-dev": {Ð   "symfony/console": "^5.4|^6.0|^7.0",Ð   "symfony/http-client": "^5.4|^6.0|^7.0",Ð   "symfony/messenger": "^6.2|^7.0",Ð   "symfony/twig-bridge": "^6.2|^7.0"Ð   },Ð   "conflict": {Ð   "symfony/http-client-contracts": "<2.5",Ð   "symfony/http-kernel": "<5.4",Ð   "symfony/messenger": "<6.2",Ð   "symfony/mime": "<6.2",Ð   "symfony/twig-bridge": "<6.2.1"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Mailer\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"ÐÐ}

vendor\symfony\mime\composer.json

{Ð   "name": "symfony/mime",Ð   "type": "library",Ð   "description": "Allows manipulating MIME messages",Ð   "keywords": ["mime", "mime-type"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-contracts": "^2.5|^3",Ð   "symfony/polyfill-intl-idn": "^1.10",Ð   "symfony/polyfill-mbstring": "^1.0"Ð   },Ð   "require-dev": {Ð   "egulias/email-validator": "^2.1.10|^3.1|^4",Ð   "league/html-to-markdown": "^5.0",Ð   "phpdocumentor/reflection-docblock": "^3.0|^4.0|^5.0",Ð   "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð   "symfony/process": "^5.4|^6.4|^7.0",Ð   "symfony/property-access": "^5.4|^6.0|^7.0",Ð   "symfony/property-info": "^5.4|^6.0|^7.0",Ð   "symfony/serializer": "^6.4.3|^7.0.3"Ð   },Ð   "conflict": {Ð   "egulias/email-validator": "~3.0.0",Ð   "phpdocumentor/reflection-docblock": "<3.2.2",Ð   "phpdocumentor/type-resolver": "<1.4.0",Ð   "symfony/mailer": "<5.4",Ð   "symfony/serializer": "<6.4.3|>7.0,<7.0.3"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Mime\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð }Ð

vendor\symfony\polyfill-ctype\composer.json

{Ð "name": "symfony/polyfill-ctype",Ð "type": "library",Ð "description": "Symfony polyfill for ctype functions",Ð "keywords": ["polyfill", "compatibility", "portable", "ctype"],Ð "homepage": "https://symfony.com",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Gert de Pagter",Ð "email": "BackEndTea@gmail.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "require": {Ð "php": ">=7.2"Ð },Ð "provide": {Ð "ext-ctype": "*"Ð },Ð "autoload": {Ð "psr-4": { "Symfony\\Polyfill\\Ctype\\": "" },Ð "files": ["bootstrap.php"]Ð },Ð "suggest": {Ð "ext-ctype": "For best performance"Ð },Ð "minimum-stability": "dev",Ð "extra": {Ð "thanks": {Ð "name": "symfony/polyfill",Ð "url": "https://github.com/symfony/polyfill"Ð }Ð }ÐÐ}

vendor\symfony\polyfill-intl-grapheme\composer.json

{Ð   "name": "symfony/polyfill-intl-grapheme",Ð   "type": "library",Ð   "description": "Symfony polyfill for intl's grapheme_* functions",Ð   "keywords": ["polyfill", "shim", "compatibility", "portable", "intl", "grapheme"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Intl\\Grapheme\\": "" },Ð   "files": ["bootstrap.php"]Ð   },Ð   "suggest": {Ð   "ext-intl": "For best performance"Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }Ð}Ð

vendor\symfony\polyfill-intl-idn\composer.json

{Ð   "name": "symfony/polyfill-intl-idn",Ð   "type": "library",Ð   "description": "Symfony polyfill for intl's idn_to_ascii and idn_to_utf8 functions",Ð   "keywords": ["polyfill", "shim", "compatibility", "portable", "intl", "idn"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Laurent Bassin",Ð   "email": "laurent@bassin.info"Ð   },Ð   {Ð   "name": "Trevor Rowbotham",Ð   "email": "trevor.rowbotham@pm.me"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2",Ð   "symfony/polyfill-intl-normalizer": "^1.10"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Intl\\Idn\\": "" },Ð   "files": ["bootstrap.php"]Ð   },Ð   "suggest": {Ð   "ext-intl": "For best performance"Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }ÐÐ}

vendor\symfony\polyfill-intl-normalizer\composer.json

{Ð   "name": "symfony/polyfill-intl-normalizer",Ð   "type": "library",Ð   "description": "Symfony polyfill for intl's Normalizer class and related functions",Ð   "keywords": ["polyfill", "shim", "compatibility", "portable", "intl", "normalizer"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Intl\\Normalizer\\": "" },Ð   "files": ["bootstrap.php"],Ð   "classmap": ["Resources/stubs"]Ð   },Ð   "suggest": {Ð   "ext-intl": "For best performance"Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }ÐÐ}

vendor\symfony\polyfill-mbstring\composer.json


```
{Ð   "name": "symfony/polyfill-mbstring",Ð   "type": "library",Ð
"description": "Symfony polyfill for the Mbstring extension",Ð   "keywords":
["polyfill", "shim", "compatibility", "portable", "mbstring"],Ð   "homepage":
"https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð       {Ð
            "name": "Nicolas Grekas",Ð           "email": "p@tchwork.com"Ð
        },Ð       {Ð           "name": "Symfony Community",Ð
"homepage": "https://symfony.com/contributors"Ð       }Ð   ],Ð   "require": {Ð
        "php": ">=7.2"Ð   },Ð   "provide": {Ð       "ext-mbstring": "*"Ð   },Ð
    "autoload": {Ð       "psr-4": { "Symfony\\Polyfill\\Mbstring\\": "" },Ð
        "files": [ "bootstrap.php" ]Ð   },Ð   "suggest": {Ð       "ext-
mbstring": "For best performance"Ð   },Ð   "minimum-stability": "dev",Ð
"extra": {Ð       "thanks": {Ð           "name": "symfony/polyfill",Ð
            "url": "https://github.com/symfony/polyfill"Ð       }Ð   }ÐÐ
```

vendor\symfony\polyfill-php80\composer.json

{Ð   "name": "symfony/polyfill-php80",Ð   "type": "library",Ð   "description": "Symfony polyfill backporting some PHP 8.0+ features to lower PHP versions",Ð   "keywords": ["polyfill", "shim", "compatibility", "portable"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Ion Bazan",Ð   "email": "ion.bazan@gmail.com"Ð   },Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Php80\\": "" },Ð   "files": ["bootstrap.php"],Ð   "classmap": ["Resources/stubs"]Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }ÞÐ}

vendor\symfony\polyfill-php83\composer.json

{Ð   "name": "symfony/polyfill-php83",Ð   "type": "library",Ð   "description": "Symfony polyfill backporting some PHP 8.3+ features to lower PHP versions",Ð   "keywords": ["polyfill", "shim", "compatibility", "portable"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Php83\\": "" },Ð   "files": ["bootstrap.php"],Ð   "classmap": ["Resources/stubs"]Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }Ð}Ð

vendor\symfony\polyfill-uuid\composer.json

{Ð   "name": "symfony/polyfill-uuid",Ð   "type": "library",Ð   "description": "Symfony polyfill for uuid functions",Ð   "keywords": ["polyfill", "compatibility", "portable", "uuid"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Grégoire Pineau",Ð   "email": "lyrixx@lyrixx.info"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.2"Ð   },Ð   "provide": {Ð   "ext-uuid": "*"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Polyfill\\Uuid\\": "" },Ð   "files": ["bootstrap.php"]Ð   },Ð   "suggest": {Ð   "ext-uuid": "For best performance"Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "thanks": {Ð   "name": "symfony/polyfill",Ð   "url": "https://github.com/symfony/polyfill"Ð   }Ð   }ÐÐ}

vendor\symfony\process\composer.json

{Ð   "name": "symfony/process",Ð   "type": "library",Ð   "description": "Executes commands in sub-processes",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Process\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð }Ð

vendor\symfony\routing\composer.json

{Ð   "name": "symfony/routing",Ð   "type": "library",Ð   "description": "Maps an HTTP request to a set of configuration variables",Ð   "keywords": ["routing", "router", "url", "uri"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-contracts": "^2.5|^3"Ð   },Ð   "require-dev": {Ð   "symfony/config": "^6.2|^7.0",Ð   "symfony/http-foundation": "^5.4|^6.0|^7.0",Ð   "symfony/yaml": "^5.4|^6.0|^7.0",Ð   "symfony/expression-language": "^5.4|^6.0|^7.0",Ð   "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð   "doctrine/annotations": "^1.12|^2",Ð   "psr/log": "^1|^2|^3"Ð   },Ð   "conflict": {Ð   "doctrine/annotations": "<1.12",Ð   "symfony/config": "<6.2",Ð   "symfony/dependency-injection": "<5.4",Ð   "symfony/yaml": "<5.4"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Routing\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\service-contracts\composer.json

{Ð "name": "symfony/service-contracts",Ð "type": "library",Ð "description": "Generic abstractions related to writing services",Ð "keywords": ["abstractions", "contracts", "decoupling", "interfaces", "interoperability", "standards"],Ð "homepage": "https://symfony.com",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "require": {Ð "php": ">=8.1",Ð "psr/container": "^1.1|^2.0",Ð "symfony/deprecation-contracts": "^2.5|^3"Ð },Ð "conflict": {Ð "ext-psr": "<1.1|>=2"Ð },Ð "autoload": {Ð "psr-4": { "Symfony\\Contracts\\Service\\": "" },Ð "exclude-from-classmap": [Ð "/Test/"Ð]Ð },Ð "minimum-stability": "dev",Ð "extra": {Ð "branch-alias": {Ð "dev-main": "3.5-dev"Ð },Ð "thanks": {Ð "name": "symfony/contracts",Ð "url": "https://github.com/symfony/contracts"Ð }Ð }Ð }Ð

vendor\symfony\string\composer.json

{Ð   "name": "symfony/string",Ð   "type": "library",Ð   "description": "Provides an object-oriented API to strings and deals with bytes, UTF-8 code points and grapheme clusters in a unified way",Ð   "keywords": ["string", "utf8", "utf-8", "grapheme", "i18n", "unicode"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.2",Ð   "symfony/polyfill-ctype": "~1.8",Ð   "symfony/polyfill-intl-grapheme": "~1.0",Ð   "symfony/polyfill-intl-normalizer": "~1.0",Ð   "symfony/polyfill-mbstring": "~1.0"Ð   },Ð   "require-dev": {Ð   "symfony/error-handler": "^6.4|^7.0",Ð   "symfony/emoji": "^7.1",Ð   "symfony/http-client": "^6.4|^7.0",Ð   "symfony/intl": "^6.4|^7.0",Ð   "symfony/translation-contracts": "^2.5|^3.0",Ð   "symfony/var-exporter": "^6.4|^7.0"Ð   },Ð   "conflict": {Ð   "symfony/translation-contracts": "<2.5"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\String\\": "" },Ð   "files": ["Resources/functions.php"],Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\translation\composer.json

{Ð   "name": "symfony/translation",Ð   "type": "library",Ð   "description": "Provides tools to internationalize your application",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/deprecation-contracts": "^2.5|^3",Ð   "symfony/polyfill-mbstring": "~1.0",Ð   "symfony/translation-contracts": "^2.5|^3.0"Ð   },Ð   "require-dev": {Ð   "nikic/php-parser": "^4.18|^5.0",Ð   "symfony/config": "^5.4|^6.0|^7.0",Ð   "symfony/console": "^5.4|^6.0|^7.0",Ð   "symfony/dependency-injection": "^5.4|^6.0|^7.0",Ð   "symfony/http-client-contracts": "^2.5|^3.0",Ð   "symfony/http-kernel": "^5.4|^6.0|^7.0",Ð   "symfony/intl": "^5.4|^6.0|^7.0",Ð   "symfony/polyfill-intl-icu": "^1.21",Ð   "symfony/routing": "^5.4|^6.0|^7.0",Ð   "symfony/service-contracts": "^2.5|^3",Ð   "symfony/yaml": "^5.4|^6.0|^7.0",Ð   "symfony/finder": "^5.4|^6.0|^7.0",Ð   "psr/log": "^1|^2|^3"Ð   },Ð   "conflict": {Ð   "symfony/config": "<5.4",Ð   "symfony/dependency-injection": "<5.4",Ð   "symfony/http-client-contracts": "<2.5",Ð   "symfony/http-kernel": "<5.4",Ð   "symfony/service-contracts": "<2.5",Ð   "symfony/twig-bundle": "<5.4",Ð   "symfony/yaml": "<5.4",Ð   "symfony/console": "<5.4"Ð   },Ð   "provide": {Ð   "symfony/translation-implementation": "2.3|3.0"Ð   },Ð   "autoload": {Ð   "files": ["Resources/functions.php"],Ð   "psr-4": { "Symfony\\Component\\Translation\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð}Ð

vendor\symfony\translation\Resources\data\parents.json

{Ð   "az_Cyrl": "root",Ð   "bs_Cyrl": "root",Ð   "en_150": "en_001",Ð
"en_AG": "en_001",Ð   "en_AI": "en_001",Ð   "en_AT": "en_150",Ð   "en_AU":
"en_001",Ð   "en_BB": "en_001",Ð   "en_BE": "en_150",Ð   "en_BM": "en_001",Ð
    "en_BS": "en_001",Ð   "en_BW": "en_001",Ð   "en_BZ": "en_001",Ð
"en_CC": "en_001",Ð   "en_CH": "en_150",Ð   "en_CK": "en_001",Ð   "en_CM":
"en_001",Ð   "en_CX": "en_001",Ð   "en_CY": "en_001",Ð   "en_DE": "en_150",Ð
    "en_DG": "en_001",Ð   "en_DK": "en_150",Ð   "en_DM": "en_001",Ð
"en_ER": "en_001",Ð   "en_FI": "en_150",Ð   "en_FJ": "en_001",Ð   "en_FK":
"en_001",Ð   "en_FM": "en_001",Ð   "en_GB": "en_001",Ð   "en_GD": "en_001",Ð
    "en_GG": "en_001",Ð   "en_GH": "en_001",Ð   "en_GI": "en_001",Ð
"en_GM": "en_001",Ð   "en_GY": "en_001",Ð   "en_HK": "en_001",Ð   "en_ID":
"en_001",Ð   "en_IE": "en_001",Ð   "en_IL": "en_001",Ð   "en_IM": "en_001",Ð
    "en_IN": "en_001",Ð   "en_IO": "en_001",Ð   "en_JE": "en_001",Ð
"en_JM": "en_001",Ð   "en_KE": "en_001",Ð   "en_KI": "en_001",Ð   "en_KN":
"en_001",Ð   "en_KY": "en_001",Ð   "en_LC": "en_001",Ð   "en_LR": "en_001",Ð
    "en_LS": "en_001",Ð   "en_MG": "en_001",Ð   "en_MO": "en_001",Ð
"en_MS": "en_001",Ð   "en_MT": "en_001",Ð   "en_MU": "en_001",Ð   "en_MV":
"en_001",Ð   "en_MW": "en_001",Ð   "en_MY": "en_001",Ð   "en_NA": "en_001",Ð
    "en_NF": "en_001",Ð   "en_NG": "en_001",Ð   "en_NL": "en_150",Ð
"en_NR": "en_001",Ð   "en_NU": "en_001",Ð   "en_NZ": "en_001",Ð   "en_PG":
"en_001",Ð   "en_PK": "en_001",Ð   "en_PN": "en_001",Ð   "en_PW": "en_001",Ð
    "en_RW": "en_001",Ð   "en_SB": "en_001",Ð   "en_SC": "en_001",Ð
"en_SD": "en_001",Ð   "en_SE": "en_150",Ð   "en_SG": "en_001",Ð   "en_SH":
"en_001",Ð   "en_SI": "en_150",Ð   "en_SL": "en_001",Ð   "en_SS": "en_001",Ð
    "en_SX": "en_001",Ð   "en_SZ": "en_001",Ð   "en_TC": "en_001",Ð
"en_TK": "en_001",Ð   "en_TO": "en_001",Ð   "en_TT": "en_001",Ð   "en_TV":
"en_001",Ð   "en_TZ": "en_001",Ð   "en_UG": "en_001",Ð   "en_VC": "en_001",Ð
    "en_VG": "en_001",Ð   "en_VU": "en_001",Ð   "en_WS": "en_001",Ð
"en_ZA": "en_001",Ð   "en_ZM": "en_001",Ð   "en_ZW": "en_001",Ð   "es_AR":
"es_419",Ð   "es_BO": "es_419",Ð   "es_BR": "es_419",Ð   "es_BZ": "es_419",Ð
    "es_CL": "es_419",Ð   "es_CO": "es_419",Ð   "es_CR": "es_419",Ð
"es_CU": "es_419",Ð   "es_DO": "es_419",Ð   "es_EC": "es_419",Ð   "es_GT":
"es_419",Ð   "es_HN": "es_419",Ð   "es_MX": "es_419",Ð   "es_NI": "es_419",Ð
    "es_PA": "es_419",Ð   "es_PE": "es_419",Ð   "es_PR": "es_419",Ð
"es_PY": "es_419",Ð   "es_SV": "es_419",Ð   "es_US": "es_419",Ð   "es_UY":
"es_419",Ð   "es_VE": "es_419",Ð   "ff_Adlm": "root",Ð   "hi_Latn": "en_IN",Ð
    "ks_Deva": "root",Ð   "nb": "no",Ð   "nn": "no",Ð   "pa_Arab": "root",Ð
"pt_AO": "pt_PT",Ð   "pt_CH": "pt_PT",Ð   "pt_CV": "pt_PT",Ð   "pt_GQ":
"pt_PT",Ð   "pt_GW": "pt_PT",Ð   "pt_LU": "pt_PT",Ð   "pt_MO": "pt_PT",Ð
"pt_MZ": "pt_PT",Ð   "pt_ST": "pt_PT",Ð   "pt_TL": "pt_PT",Ð   "sd_Deva":
"root",Ð   "sr_Latn": "root",Ð   "uz_Arab": "root",Ð   "uz_Cyrl": "root",Ð
"zh_Hant": "root",Ð   "zh_Hant_MO": "zh_Hant_HK"ÐÐ
}

vendor\symfony\translation-contracts\composer.json

{Ð   "name": "symfony/translation-contracts",Ð   "type": "library",Ð   "description": "Generic abstractions related to translation",Ð   "keywords": ["abstractions", "contracts", "decoupling", "interfaces", "interoperability", "standards"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Contracts\\Translation\\": "" },Ð   "exclude-from-classmap": [Ð   "/Test/"Ð   ]Ð   },Ð   "minimum-stability": "dev",Ð   "extra": {Ð   "branch-alias": {Ð   "dev-main": "3.5-dev"Ð   },Ð   "thanks": {Ð   "name": "symfony/contracts",Ð   "url": "https://github.com/symfony/contracts"Ð   }Ð   }Ð}

vendor\symfony\uid\composer.json

{Ð   "name": "symfony/uid",Ð   "type": "library",Ð   "description": "Provides an object-oriented API to generate and represent UIDs",Ð   "keywords": ["uid", "uuid", "ulid"],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Grégoire Pineau",Ð   "email": "lyrixx@lyrixx.info"Ð   },Ð   {Ð   "name": "Nicolas Grekas",Ð   "email": "p@tchwork.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=8.1",Ð   "symfony/polyfill-uuid": "^1.15"Ð   },Ð   "require-dev": {Ð   "symfony/console": "^5.4|^6.0|^7.0"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Uid\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð   "minimum-stability": "dev"Ð }Ð

vendor\symfony\var-dumper\composer.json

{Ð "name": "symfony/var-dumper",Ð "type": "library",Ð "description": "Provides mechanisms for walking through any arbitrary PHP variable",Ð "keywords": ["dump", "debug"],Ð "homepage": "https://symfony.com",Ð "license": "MIT",Ð "authors": [Ð {Ð "name": "Nicolas Grekas",Ð "email": "p@tchwork.com"Ð },Ð {Ð "name": "Symfony Community",Ð "homepage": "https://symfony.com/contributors"Ð }Ð],Ð "require": {Ð "php": ">=8.1",Ð "symfony/deprecation-contracts": "^2.5|^3",Ð "symfony/polyfill-mbstring": "~1.0"Ð },Ð "require-dev": {Ð "ext-iconv": "*",Ð "symfony/console": "^5.4|^6.0|^7.0",Ð "symfony/error-handler": "^6.3|^7.0",Ð "symfony/http-kernel": "^5.4|^6.0|^7.0",Ð "symfony/process": "^5.4|^6.0|^7.0",Ð "symfony/uid": "^5.4|^6.0|^7.0",Ð "twig/twig": "^2.13|^3.0.4"Ð },Ð "conflict": {Ð "symfony/console": "<5.4"Ð },Ð "autoload": {Ð "files": ["Resources/functions/dump.php"],Ð "psr-4": { "Symfony\\Component\\VarDumper\\": "" },Ð "exclude-from-classmap": [Ð "/Tests/"Ð]Ð },Ð "bin": [Ð "Resources/bin/var-dump-server"Ð],Ð "minimum-stability": "dev"Ð }Ð

vendor\symfony\yaml\composer.json

{Ð   "name": "symfony/yaml",Ð   "type": "library",Ð   "description": "Loads and dumps YAML files",Ð   "keywords": [],Ð   "homepage": "https://symfony.com",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð "name": "Fabien Potencier",Ð   "email": "fabien@symfony.com"Ð   },Ð   {Ð   "name": "Symfony Community",Ð   "homepage": "https://symfony.com/contributors"Ð   }Ð   ],Ð   "require": {Ð "php": ">=8.2",Ð   "symfony/deprecation-contracts": "^2.5|^3.0",Ð "symfony/polyfill-ctype": "^1.8"Ð   },Ð   "require-dev": {Ð   "symfony/console": "^6.4|^7.0"Ð   },Ð   "conflict": {Ð   "symfony/console": "<6.4"Ð   },Ð   "autoload": {Ð   "psr-4": { "Symfony\\Component\\Yaml\\": "" },Ð   "exclude-from-classmap": [Ð   "/Tests/"Ð   ]Ð   },Ð "bin": [Ð   "Resources/bin/yaml-lint"Ð   ],Ð   "minimum-stability": "dev"ÐÐ}

vendor\theseer\tokenizer\composer.json

{Ð "name": "theseer/tokenizer",Ð "description": "A small library for converting tokenized PHP source code into XML and potentially other formats",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Arne Blankerts",Ð "email": "arne@blankerts.de",Ð "role": "Developer"Ð }Ð],Ð "support": {Ð "issues": "https://github.com/theseer/tokenizer/issues"Ð },Ð "require": {Ð "php": "^7.2 || ^8.0",Ð "ext-xmlwriter": "*",Ð "ext-dom": "*",Ð "ext-tokenizer": "*"Ð },Ð "autoload": {Ð "classmap": [Ð "src/"Ð]Ð }ÐÐ}

vendor\tijsverkoyen\css-to-inline-styles\composer.json

{Ð "name": "tijsverkoyen/css-to-inline-styles",Ð "type": "library",Ð "description": "CssToInlineStyles is a class that enables you to convert HTML-pages/files into HTML-pages/files with inline styles. This is very useful when you're sending emails.",Ð "homepage": "https://github.com/tijsverkoyen/CssToInlineStyles",Ð "license": "BSD-3-Clause",Ð "authors": [Ð {Ð "name": "Tijs Verkoyen",Ð "email": "css_to_inline_styles@verkoyen.eu",Ð "role": "Developer"Ð }Ð],Ð "require": {Ð "php": "^7.4 || ^8.0",Ð "ext-dom": "*",Ð "ext-libxml": "*",Ð "symfony/css-selector": "^5.4 || ^6.0 || ^7.0"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^8.5.21 || ^9.5.10",Ð "phpstan/phpstan": "^2.0",Ð "phpstan/phpstan-phpunit": "^2.0"Ð },Ð "autoload": {Ð "psr-4": {Ð "TijsVerkoyen\\CssToInlineStyles\\": "src"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "TijsVerkoyen\\CssToInlineStyles\\Tests\\": "tests"Ð }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "2.x-dev"Ð }Ð }ÐÐ}

vendor\vlucas\phpdotenv\composer.json

{Ð   "name": "vlucas/phpdotenv",Ð   "description": "Loads environment variables from `.env` to `getenv()`, `$_ENV` and `$_SERVER` automagically.",Ð   "keywords": ["env", "dotenv", "environment"],Ð   "license": "BSD-3-Clause",Ð   "authors": [Ð   {Ð   "name": "Graham Campbell",Ð   "email": "hello@gjcampbell.co.uk",Ð   "homepage": "https://github.com/GrahamCampbell"Ð   },Ð   {Ð   "name": "Vance Lucas",Ð   "email": "vance@vancelucas.com",Ð   "homepage": "https://github.com/vlucas"Ð   }Ð   ],Ð   "require": {Ð   "php": "^7.2.5 || ^8.0",Ð   "ext-pcre": "*",Ð   "graham-campbell/result-type": "^1.1.3",Ð   "phpoption/phpoption": "^1.9.3",Ð   "symfony/polyfill-ctype": "^1.24",Ð   "symfony/polyfill-mbstring": "^1.24",Ð   "symfony/polyfill-php80": "^1.24"Ð   },Ð   "require-dev": {Ð   "ext-filter": "*",Ð   "bamarni/composer-bin-plugin": "^1.8.2",Ð   "phpunit/phpunit":"^8.5.34 || ^9.6.13 || ^10.4.2"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "Dotenv\\": "src/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "Dotenv\\Tests\\": "tests/Dotenv/"Ð   }Ð   },Ð   "suggest": {Ð   "ext-filter": "Required to use the boolean validator."Ð   },Ð   "config": {Ð   "allow-plugins": {Ð   "bamarni/composer-bin-plugin": trueÐ   },Ð   "preferred-install": "dist"Ð   },Ð   "extra": {Ð   "bamarni-bin": {Ð   "bin-links": true,Ð   "forward-command": falseÐ   },Ð   "branch-alias": {Ð   "dev-master": "5.6-dev"Ð   }Ð   }Ð}Ð

vendor\voku\portable-ascii\composer.json

{Ð   "name": "voku/portable-ascii",Ð   "description": "Portable ASCII library - performance optimized (ascii) string functions for php.",Ð   "type": "library",Ð   "keywords": [Ð   "clean",Ð   "php",Ð   "ascii"Ð   ],Ð   "homepage": "https://github.com/voku/portable-ascii",Ð   "license": "MIT",Ð   "authors": [Ð   {Ð   "name": "Lars Moelleken",Ð   "homepage": "https://www.moelleken.org/"Ð   }Ð   ],Ð   "require": {Ð   "php": ">=7.0.0"Ð   },Ð   "require-dev": {Ð   "phpunit/phpunit": "~6.0 || ~7.0 || ~9.0"Ð   },Ð   "suggest": {Ð   "ext-intl": "Use Intl for transliterator_transliterate() support"Ð   },Ð   "autoload": {Ð   "psr-4": {Ð   "voku\\": "src/voku/"Ð   }Ð   },Ð   "autoload-dev": {Ð   "psr-4": {Ð   "voku\\tests\\": "tests/"Ð   }Ð   }}ÐÐ

vendor\webmozart\assert\composer.json

{Ð "name": "webmozart/assert",Ð "description": "Assertions to validate method input/output with nice error messages.",Ð "license": "MIT",Ð "keywords": [Ð "assert",Ð "check",Ð "validate"Ð],Ð "authors": [Ð {Ð "name": "Bernhard Schussek",Ð "email": "bschussek@gmail.com"Ð }Ð],Ð "require": {Ð "php": "^7.2 || ^8.0",Ð "ext-ctype": "*"Ð },Ð "require-dev": {Ð "phpunit/phpunit": "^8.5.13"Ð },Ð "conflict": {Ð "phpstan/phpstan": "<0.12.20",Ð "vimeo/psalm": "<4.6.1 || 4.6.2"Ð },Ð "autoload": {Ð "psr-4": {Ð "Webmozart\\Assert\\": "src/"Ð }Ð },Ð "autoload-dev": {Ð "psr-4": {Ð "Webmozart\\Assert\\Tests\\": "tests/",Ð "Webmozart\\Assert\\Bin\\": "bin/src"Ð }Ð },Ð "extra": {Ð "branch-alias": {Ð "dev-master": "1.10-dev"Ð }Ð }Ð}ÐÐ

Table of Contents

public\assets\editor\clike.js
..... [object Object]

public\assets\editor\codemirror.js
..... [object Object]

public\assets\editor\css.js
..... [object Object]

public\assets\editor\htmlmixed.js
..... [object Object]

public\assets\editor\javascript.js
..... [object Object]

public\assets\editor\matchbrackets.js
..... [object Object]

public\assets\editor\xml.js
..... [object Object]

public\assets\frontend\js\bootstrap.js
..... [object Object]

public\assets\frontend\js\forms.js
..... [object Object]

public\assets\frontend\js\jquery.flexslider.js
..... [object Object]

public\assets\frontend\js\jquery.isotope.js
..... [object Object]

public\assets\frontend\js\jquery.magnific-popup.js
..... [object Object]

public\assets\frontend\js\map-settings.js
..... [object Object]

public\assets\frontend\js\settings.js
..... [object Object]

public\assets\js\bootstrap.js
..... [object Object]

public\assets\js\customize.js
..... [object Object]

public\assets\js\demo\chartjs-demo.js
..... [object Object]

public\assets\js\demo\dashboard-demo.js
..... [object Object]

public\assets\js\demo\flot-demo2.js
..... [object Object]

public\assets\js\demo\morris-demo.js
..... [object Object]

public\assets\js\demo\peity-demo.js
..... [object Object]

public\assets\js\demo\rickshaw-demo.js
..... [object Object]

public\assets\js\demo\sparkline-demo.js
..... [object Object]

public\assets\js\iframe-content.js
..... [object Object]

public\assets\js\inspinia.js
..... [object Object]

public\assets\js\plugins\bootstrap-markdown\bootstrap-markdown.js
..... [object Object]

public\assets\js\plugins\bootstrap-markdown\markdown.js
..... [object Object]

public\assets\js\plugins\chosen\chosen.jquery.js
..... [object Object]

public\assets\js\plugins\clockpicker\clockpicker.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\apl\apl.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\asterisk\asterisk.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\clike\clike.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\cobol\cobol.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\coffeescript\coffeescript.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\commonlisp\commonlisp.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\css.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\less_test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\scss_test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\cypher\cypher.js

..... [object Object]

public\assets\js\plugins\codemirror\mode\d\d.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\diff\diff.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\django\django.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\dtd\dtd.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\dylan\dylan.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\eiffel\eiffel.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\erlang\erlang.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\fortran\fortran.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\gas\gas.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\gfm\gfm.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\gfm\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\go\go.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\groovy\groovy.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\haml\haml.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\haml\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\haskell\haskell.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\haxe\haxe.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\htmlembedded\htmlembedded.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\htmlmixed\htmlmixed.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\http\http.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\jade\jade.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\javascript\javascript.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\javascript\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\jinja2\jinja2.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\julia\julia.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\kotlin\kotlin.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\livescript\livescript.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\lua\lua.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\markdown\markdown.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\markdown\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\meta.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\mirc\mirc.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\mllike\mllike.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\modelica\modelica.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\ntriples\ntriples.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\octave\octave.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\pascal\pascal.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\pegjs\pegjs.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\perl\perl.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\php\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\pig\pig.js

..... [object Object]

public\assets\js\plugins\codemirror\mode\properties\properties.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\puppet\puppet.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\python\python.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\r\r.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\rpm\rpm.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\rst\rst.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\ruby\ruby.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\ruby\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\rust\rust.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\sass\sass.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\shell\shell.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\shell\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\sieve\sieve.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\slim\slim.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\slim\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\smalltalk\smalltalk.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\smarty\smarty.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\smartymixed\smartymixed.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\solr\solr.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\sparql\sparql.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\stex\stex.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\stex\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\tcl\tcl.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\textile\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\textile\textile.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiddlywiki\tiddlywiki.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiki\tiki.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\toml\toml.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\tornado\tornado.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\turtle\turtle.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\vb\vb.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\vbscript\vbscript.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\velocity\velocity.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\verilog\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\verilog\verilog.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\xml\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\xml\xml.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\xquery\test.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\xquery\xquery.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\yaml\yaml.js
..... [object Object]

public\assets\js\plugins\codemirror\mode\z80\z80.js

..... [object Object]

public\assets\js\plugins\datapicker\bootstrap-datepicker.js
..... [object Object]

public\assets\js\plugins\daterangepicker\daterangepicker.js
..... [object Object]

public\assets\js\plugins\diff_match_patch\javascript\diff_match_patch.js
..... [object Object]

public\assets\js\plugins\dropzone\dropzone.js
..... [object Object]

public\assets\js\plugins\easypiechart\easypiechart.js
..... [object Object]

public\assets\js\plugins\easypiechart\jquery.easypiechart.js
..... [object Object]

public\assets\js\plugins\flot\curvedLines.js
..... [object Object]

public\assets\js\plugins\flot\jquery.flot.pie.js
..... [object Object]

public\assets\js\plugins\flot\jquery.flot.spline.js
..... [object Object]

public\assets\js\plugins\flot\jquery.flot.symbol.js
..... [object Object]

public\assets\js\plugins\flot\jquery.flot.time.js
..... [object Object]

public\assets\js\plugins\iCheck\icheck.min.js
..... [object Object]

public\assets\js\plugins\ionRangeSlider\ion.rangeSlider.min.js
..... [object Object]

public\assets\js\plugins\jeditable\jquery.jeditable.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-ar.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-bg.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-bg1251.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-cat.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-cn.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-cs.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-da.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-de.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-dk.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-el.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-en.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-es.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-fa.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-fi.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-fr.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-gl.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-he.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-hr.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-hr1250.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-hu.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-id.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-is.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-ja.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-kr.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-lt.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-mne.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-nl.js

..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-pl.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-pt-br.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-pt.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-ro.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-ru.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-sk.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-sr-latin.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-sr.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-sv.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-th.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-tr.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-tw.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-ua.js
..... [object Object]

public\assets\js\plugins\jqGrid\i18n\grid.locale-vi.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-af.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ar-DZ.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ar.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-az.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-be.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-bg.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-bs.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ca.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-cs.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-cy-GB.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-da.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-de.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-el.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-AU.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-GB.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-en-NZ.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-eo.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-es.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-et.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-eu.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fa.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fi.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fo.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr-CA.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr-CH.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-fr.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-gl.min.js

..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-he.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hi.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hr.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hu.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-hy.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-id.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-is.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-it.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ja.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ka.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-kk.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-km.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ko.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ky.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lb.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lt.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-lv.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-mk.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ml.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ms.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nb.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nl-BE.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nl.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-nn.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-no.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pl.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pt-BR.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-pt.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-rm.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ro.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ru.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sk.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sl.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sq.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sr-SR.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sr.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-sv.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-ta.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-th.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-tj.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-tr.min.js

..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-uk.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-vi.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-CN.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-HK.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\i18n\jquery.ui.datepicker-zh-TW.min.js
..... [object Object]

public\assets\js\plugins\jquery-ui\jquery-ui.js
..... [object Object]

public\assets\js\plugins\jsKnob\jquery.knob.js
..... [object Object]

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.js
..... [object Object]

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.min.js
..... [object Object]

public\assets\js\plugins\jvectormap\jquery-jvectormap-2.0.2.min.js
..... [object Object]

public\assets\js\plugins\ladda\ladda.jquery.min.js
..... [object Object]

public\assets\js\plugins\morris\morris.js
..... [object Object]

public\assets\js\plugins\nestable\jquery.nestable.js
..... [object Object]

public\assets\js\plugins\nouslider\jquery.nouislider.min.js
..... [object Object]

public\assets\js\plugins\peity\jquery.peity.min.js
..... [object Object]

public\assets\js\plugins\preetyTextDiff\jquery.pretty-text-diff.min.js
..... [object Object]

public\assets\js\plugins\slimscroll\jquery.slimscroll.js
..... [object Object]

public\assets\js\plugins\slimscroll\jquery.slimscroll.min.js
..... [object Object]

public\assets\js\plugins\video\responsible-video.js
..... [object Object]

public\assets\numpad\jquery.numpad.js
..... [object Object]

resources\js\app.js
..... [object Object]

resources\js\bootstrap.js
..... [object Object]

vendor\filp\whoops\src\Whoops\Resources\js\whoops.base.js
..... [object Object]

vendor\laravel\breeze\stubs\default\postcss.config.js
..... [object Object]

vendor\laravel\breeze\stubs\default\resources\js\app.js
..... [object Object]

vendor\laravel\breeze\stubs\default\tailwind.config.js
..... [object Object]

vendor\laravel\breeze\stubs\default\vite.config.js
..... [object Object]

vendor\laravel\breeze\stubs\inertia-common\tailwind.config.js
..... [object Object]

vendor\laravel\breeze\stubs\inertia-react\vite.config.js
..... [object Object]

vendor\laravel\breeze\stubs\inertia-vue\resources\js\app.js
..... [object Object]

vendor\laravel\breeze\stubs\inertia-vue\resources\js\ssr.js
..... [object Object]

vendor\laravel\breeze\stubs\inertia-vue\vite.config.js
..... [object Object]

vendor\laravel\ui\src\Presets\bootstrap-stubs\bootstrap.js
..... [object Object]

vendor\laravel\ui\src\Presets\bootstrap-stubs\webpack.mix.js
..... [object Object]

vendor\laravel\ui\src\Presets\react-stubs\app.js
..... [object Object]

vendor\laravel\ui\src\Presets\react-stubs\Example.js
..... [object Object]

vendor\laravel\ui\src\Presets\react-stubs\webpack.mix.js
..... [object Object]

vendor\laravel\ui\src\Presets\vue-stubs\app.js
..... [object Object]

vendor\laravel\ui\src\Presets\vue-stubs\webpack.mix.js
..... [object Object]

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\js\file.js
..... [object Object]

vendor\symfony\error-handler\Resources\assets\js\exception.js

..... [object Object]

vendor\symfony\var-dumper\Resources\js\htmlDescriptor.js
..... [object Object]

webpack.mix.js
..... [object Object]

public\assets\frontend\fonts\glyphicons-halflings-regular-2.html
..... [object Object]

public\assets\frontend\fonts\glyphicons-halflings-regular-3.html
..... [object Object]

public\assets\frontend\fonts\glyphicons-halflings-regular-4.html
..... [object Object]

public\assets\frontend\fonts\glyphicons-halflings-regular.html
..... [object Object]

public\assets\frontend\fonts\glyphicons-halflings-regulard41d.html
..... [object Object]

public\assets\frontend\img\hr-spec.html
..... [object Object]

public\assets\frontend\img\sky-bottom.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\apl\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\asterisk\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\clike\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\clike\scala.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\clojure\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\cobol\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\coffeescript\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\commonlisp\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\less.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\css\scss.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\cypher\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\d\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\diff\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\django\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\dtd\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\dylan\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\ecl\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\eiffel\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\erlang\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\fortran\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\gas\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\gfm\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\gherkin\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\go\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\groovy\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\haml\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\haskell\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\haxe\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\htmlembedded\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\htmlmixed\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\http\index.html

..... [object Object]

public\assets\js\plugins\codemirror\mode\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\jade\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\javascript\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\javascript\json-ld.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\javascript\typescript.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\jinja2\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\julia\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\kotlin\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\livescript\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\lua\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\markdown\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\mirc\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\mllike\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\modelica\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\nginx\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\ntriples\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\octave\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\pascal\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\pegjs\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\perl\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\php\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\pig\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\properties\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\puppet\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\python\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\q\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\r\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\rpm\changes\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\rpm\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\rst\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\ruby\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\rust\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\sass\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\scheme\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\shell\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\sieve\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\slim\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\smalltalk\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\smarty\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\smartymixed\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\solr\index.html

..... [object Object]

public\assets\js\plugins\codemirror\mode\sparql\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\sql\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\stex\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\tcl\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\textile\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiddlywiki\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiki\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\toml\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\tornado\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\turtle\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\vb\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\vbscript\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\velocity\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\verilog\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\xml\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\xquery\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\yaml\index.html
..... [object Object]

public\assets\js\plugins\codemirror\mode\z80\index.html
..... [object Object]

public\assets\css\animate.css
..... [object Object]

public\assets\css\bootstrap.css
..... [object Object]

public\assets\css\custom.css
..... [object Object]

public\assets\css\customer.css
..... [object Object]

public\assets\css\plugins\awesome-bootstrap-checkbox\awesome-bootstrap-checkbox.css
..... [object Object]

public\assets\css\plugins\blueimp\css\blueimp-gallery-indicator.css
..... [object Object]

public\assets\css\plugins\blueimp\css\blueimp-gallery-video.css
..... [object Object]

public\assets\css\plugins\blueimp\css\blueimp-gallery.css
..... [object Object]

public\assets\css\plugins\blueimp\css\demo.css
..... [object Object]

public\assets\css\plugins\bootstrap-rtl\bootstrap-rtl.css
..... [object Object]

public\assets\css\plugins\chartist\chartist.min.css
..... [object Object]

public\assets\css\plugins\chosen\chosen.css
..... [object Object]

public\assets\css\plugins\clockpicker\clockpicker.css
..... [object Object]

public\assets\css\plugins\codemirror\codemirror.css
..... [object Object]

public\assets\css\plugins\cropper\cropper.css
..... [object Object]

public\assets\css\plugins\datapicker\datepicker3.css
..... [object Object]

public\assets\css\plugins\daterangepicker\daterangepicker-bs3.css
..... [object Object]

public\assets\css\plugins\dropzone\basic.css
..... [object Object]

public\assets\css\plugins\dropzone\dropzone.css
..... [object Object]

public\assets\css\plugins\footable\footable.core.css
..... [object Object]

public\assets\css\plugins\fullcalendar\fullcalendar.css
..... [object Object]

public\assets\css\plugins\fullcalendar\fullcalendar.print.css
..... [object Object]

public\assets\css\plugins\iCheck\custom.css
..... [object Object]

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.css
..... [object Object]

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinFlat.css
..... [object Object]

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinNice.css
..... [object Object]

public\assets\css\plugins\ionRangeSlider\ion.rangeSlider.skinSimple.css
..... [object Object]

public\assets\css\plugins\jqGrid\ui.jqgrid.css
..... [object Object]

public\assets\css\plugins\jQueryUI\jquery-ui.css
..... [object Object]

public\assets\css\plugins\jsTree\style.css
..... [object Object]

public\assets\css\plugins\morris\morris-0.4.3.min.css
..... [object Object]

public\assets\css\plugins\nouslider\jquery.nouislider.css
..... [object Object]

public\assets\css\plugins\slick\slick-theme.css
..... [object Object]

public\assets\css\plugins\slick\slick.css
..... [object Object]

public\assets\css\plugins\social-buttons\social-buttons.css
..... [object Object]

public\assets\css\plugins\steps\jquery.steps.css
..... [object Object]

public\assets\css\plugins\summernote\summernote-bs3.css
..... [object Object]

public\assets\css\plugins\summernote\summernote.css
..... [object Object]

public\assets\css\plugins\switchery\switchery.css
..... [object Object]

public\assets\css\plugins\toastr\toastr.min.css
..... [object Object]

public\assets\css\plugins\touchspin\jquery.bootstrap-touchspin.min.css
..... [object Object]

public\assets\dist\cropper.css
..... [object Object]

public\assets\dist\cropper.min.css

..... [object Object]

public\assets\editor\codemirror.css
..... [object Object]

public\assets\font-awesome\css\font-awesome.css
..... [object Object]

public\assets\frontend\css\blog-style.css
..... [object Object]

public\assets\frontend\css\bootstrap.css
..... [object Object]

public\assets\frontend\css\magnific-popup.css
..... [object Object]

public\assets\frontend\css\style.css
..... [object Object]

public\assets\frontend\menu.css
..... [object Object]

public\assets\frontend\style.css
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiddlywiki\tiddlywiki.css
..... [object Object]

public\assets\js\plugins\codemirror\mode\tiki\tiki.css
..... [object Object]

public\assets\js\plugins\gritter\jquery.gritter.css
..... [object Object]

public\assets\js\plugins\jquery-ui\jquery-ui.css
..... [object Object]

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.css
..... [object Object]

public\assets\js\plugins\justified-gallery\jquery.justifiedgallery.min.css
..... [object Object]

public\assets\numpad\jquery.numpad.css
..... [object Object]

resources\views\vendor\mail\html\themes\default.css
..... [object Object]

resources\views\vendor\mail\html\themes\email.css
..... [object Object]

vendor\filp\whoops\src\Whoops\Resources\css\whoops.base.css
..... [object Object]

vendor\laravel\breeze\stubs\default\resources\css\app.css
..... [object Object]

vendor\laravel\framework\src\Illuminate\Mail\resources\views\html\themes\default.css
..... [object Object]

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\css\octicons.css
..... [object Object]

vendor\phpunit\php-code-coverage\src\Report\Html\Renderer\Template\css\style.css
..... [object Object]

vendor\symfony\error-handler\Resources\assets\css\error.css
..... [object Object]

vendor\symfony\error-handler\Resources\assets\css\exception_full.css
..... [object Object]

vendor\symfony\var-dumper\Resources\css\htmlDescriptor.css
..... [object Object]

.vscode\launch.json
..... [object Object]

composer.json
..... [object Object]

package.json
..... [object Object]

vendor\barryvdh\laravel-dompdf\composer.json
..... [object Object]

vendor\barryvdh\laravel-translation-manager\composer.json
..... [object Object]

vendor\brick\math\composer.json
..... [object Object]

vendor\carbonphp\carbon-doctrine-types\composer.json
..... [object Object]

vendor\composer\installed.json
..... [object Object]

vendor\dflydev\dot-access-data\composer.json
..... [object Object]

vendor\doctrine\cache\composer.json
..... [object Object]

vendor\doctrine\dbal\composer.json
..... [object Object]

vendor\doctrine\deprecations\composer.json
..... [object Object]

vendor\doctrine\event-manager\composer.json
..... [object Object]

vendor\doctrine\inflector\composer.json
..... [object Object]

vendor\doctrine\instantiator\.doctrine-project.json
..... [object Object]

vendor\doctrine\instantiator\composer.json

..... [object Object]

vendor\doctrine\lexer\composer.json
..... [object Object]

vendor\dompdf\dompdf\composer.json
..... [object Object]

vendor\dragonmantank\cron-expression\composer.json
..... [object Object]

vendor\egulias\email-validator\composer.json
..... [object Object]

vendor\fakerphp\faker\composer.json
..... [object Object]

vendor\filp\whoops\composer.json
..... [object Object]

vendor\fruitcake\php-cors\composer.json
..... [object Object]

vendor\graham-campbell\result-type\composer.json
..... [object Object]

vendor\guzzlehttp\guzzle\composer.json
..... [object Object]

vendor\guzzlehttp\promises\composer.json
..... [object Object]

vendor\guzzlehttp\psr7\composer.json
..... [object Object]

vendor\guzzlehttp\uri-template\composer.json
..... [object Object]

vendor\hamcrest\hamcrest-php\composer.json
..... [object Object]

vendor\intervention\image\composer.json
..... [object Object]

vendor\intervention\image\provides.json
..... [object Object]

vendor\kitloong\laravel-migrations-generator\composer.json
..... [object Object]

vendor\laravel\breeze\composer.json
..... [object Object]

vendor\laravel\breeze\stubs\inertia-common\jsconfig.json
..... [object Object]

vendor\laravel\framework\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Auth\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Broadcasting\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Bus\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Cache\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Collections\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Conditionable\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Config\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Console\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Container\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Contracts\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Cookie\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Database\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Encryption\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Events\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Filesystem\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Hashing\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Http\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Log\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Macroable\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Mail\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Notifications\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Pagination\composer.json

..... [object Object]

vendor\laravel\framework\src\Illuminate\Pipeline\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Queue\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Redis\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Routing\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Session\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Support\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Testing\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Translation\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\Validation\composer.json
..... [object Object]

vendor\laravel\framework\src\Illuminate\View\composer.json
..... [object Object]

vendor\laravel\sail\composer.json
..... [object Object]

vendor\laravel\sanctum\composer.json
..... [object Object]

vendor\laravel\serializable-closure\composer.json
..... [object Object]

vendor\laravel\tinker\composer.json
..... [object Object]

vendor\laravel\ui\composer.json
..... [object Object]

vendor\league\commonmark\composer.json
..... [object Object]

vendor\league\config\composer.json
..... [object Object]

vendor\league\flysystem\composer.json
..... [object Object]

vendor\league\flysystem-local\composer.json
..... [object Object]

vendor\league\mime-type-detection\composer.json
..... [object Object]

vendor\masterminds\html5\composer.json
..... [object Object]

vendor\mockery\mockery\composer.json
..... [object Object]

vendor\monolog\monolog\composer.json
..... [object Object]

vendor\myclabs\deep-copy\composer.json
..... [object Object]

vendor\myclabs\php-enum\composer.json
..... [object Object]

vendor\nesbot\carbon\composer.json
..... [object Object]

vendor\nette\schema\composer.json
..... [object Object]

vendor\nette\utils\composer.json
..... [object Object]

vendor\nikic\php-parser\composer.json
..... [object Object]

vendor\nunomaduro\collision\composer.json
..... [object Object]

vendor\nunomaduro\termwind\composer.json
..... [object Object]

vendor\nunomaduro\termwind\pint.json
..... [object Object]

vendor\phar-io\manifest\composer.json
..... [object Object]

vendor\phar-io\version\composer.json
..... [object Object]

vendor\phenx\php-font-lib\composer.json
..... [object Object]

vendor\phenx\php-svg-lib\composer.json
..... [object Object]

vendor\phpoption\phpoption\composer.json
..... [object Object]

vendor\phpunit\php-code-coverage\composer.json
..... [object Object]

vendor\phpunit\php-file-iterator\composer.json
..... [object Object]

vendor\phpunit\php-invoker\composer.json
..... [object Object]

vendor\phpunit\php-text-template\composer.json

..... [object Object]

vendor\phpunit\php-timer\composer.json
..... [object Object]

vendor\phpunit\phpunit\composer.json
..... [object Object]

vendor\psr\cache\composer.json
..... [object Object]

vendor\psr\clock\composer.json
..... [object Object]

vendor\psr\container\composer.json
..... [object Object]

vendor\psr\event-dispatcher\composer.json
..... [object Object]

vendor\psr\http-client\composer.json
..... [object Object]

vendor\psr\http-factory\composer.json
..... [object Object]

vendor\psr\http-message\composer.json
..... [object Object]

vendor\psr\log\composer.json
..... [object Object]

vendor\psr\simple-cache\composer.json
..... [object Object]

vendor\psy\psysh\composer.json
..... [object Object]

vendor\ralouphie\getallheaders\composer.json
..... [object Object]

vendor\ramsey\collection\composer.json
..... [object Object]

vendor\ramsey\uuid\composer.json
..... [object Object]

vendor\sabberworm\php-css-parser\composer.json
..... [object Object]

vendor\sebastian\cli-parser\composer.json
..... [object Object]

vendor\sebastian\cli-parser\infection.json
..... [object Object]

vendor\sebastian\code-unit\composer.json
..... [object Object]

vendor\sebastian\code-unit-reverse-lookup\composer.json
..... [object Object]

vendor\sebastian\comparator\composer.json
..... [object Object]

vendor\sebastian\complexity\composer.json
..... [object Object]

vendor\sebastian\diff\composer.json
..... [object Object]

vendor\sebastian\environment\composer.json
..... [object Object]

vendor\sebastian\exporter\composer.json
..... [object Object]

vendor\sebastian\global-state\composer.json
..... [object Object]

vendor\sebastian\lines-of-code\composer.json
..... [object Object]

vendor\sebastian\object-enumerator\composer.json
..... [object Object]

vendor\sebastian\object-reflector\composer.json
..... [object Object]

vendor\sebastian\recursion-context\composer.json
..... [object Object]

vendor\sebastian\resource-operations\composer.json
..... [object Object]

vendor\sebastian\type\composer.json
..... [object Object]

vendor\sebastian\version\composer.json
..... [object Object]

vendor\spatie\backtrace\composer.json
..... [object Object]

vendor\spatie\flare-client-php\composer.json
..... [object Object]

vendor\spatie\ignition\composer.json
..... [object Object]

vendor\spatie\laravel-ignition\composer.json
..... [object Object]

vendor\stripe\stripe-php\composer.json
..... [object Object]

vendor\symfony\browser-kit\composer.json
..... [object Object]

vendor\symfony\console\composer.json
..... [object Object]

vendor\symfony\css-selector\composer.json

..... [object Object]

vendor\symfony\deprecation-contracts\composer.json
..... [object Object]

vendor\symfony\dom-crawler\composer.json
..... [object Object]

vendor\symfony\error-handler\composer.json
..... [object Object]

vendor\symfony\event-dispatcher\composer.json
..... [object Object]

vendor\symfony\event-dispatcher-contracts\composer.json
..... [object Object]

vendor\symfony\finder\composer.json
..... [object Object]

vendor\symfony\http-client\composer.json
..... [object Object]

vendor\symfony\http-client-contracts\composer.json
..... [object Object]

vendor\symfony\http-foundation\composer.json
..... [object Object]

vendor\symfony\http-kernel\composer.json
..... [object Object]

vendor\symfony\mailer\composer.json
..... [object Object]

vendor\symfony\mime\composer.json
..... [object Object]

vendor\symfony\polyfill-ctype\composer.json
..... [object Object]

vendor\symfony\polyfill-intl-grapheme\composer.json
..... [object Object]

vendor\symfony\polyfill-intl-idn\composer.json
..... [object Object]

vendor\symfony\polyfill-intl-normalizer\composer.json
..... [object Object]

vendor\symfony\polyfill-mbstring\composer.json
..... [object Object]

vendor\symfony\polyfill-php80\composer.json
..... [object Object]

vendor\symfony\polyfill-php83\composer.json
..... [object Object]

vendor\symfony\polyfill-uuid\composer.json
..... [object Object]

vendor\symfony\process\composer.json
..... [object Object]

vendor\symfony\routing\composer.json
..... [object Object]

vendor\symfony\service-contracts\composer.json
..... [object Object]

vendor\symfony\string\composer.json
..... [object Object]

vendor\symfony\translation\composer.json
..... [object Object]

vendor\symfony\translation\Resources\data\parents.json
..... [object Object]

vendor\symfony\translation-contracts\composer.json
..... [object Object]

vendor\symfony\uid\composer.json
..... [object Object]

vendor\symfony\var-dumper\composer.json
..... [object Object]

vendor\symfony\yaml\composer.json
..... [object Object]

vendor\theseer\tokenizer\composer.json
..... [object Object]

vendor\tijsverkoyen\css-to-inline-styles\composer.json
..... [object Object]

vendor\vlucas\phpdotenv\composer.json
..... [object Object]

vendor\voku\portable-ascii\composer.json
..... [object Object]

vendor\webmozart\assert\composer.json
..... [object Object]