REVIEW ARTICLE

A Comprehensive Review of EEG Based Emotion Recognition: Theories, Methods, Evaluation, and Emerging Trends

Shihab Sarar[1] | Md Niaz Imtiaz[2] | Naimul Khan[3]

[1]Department of Computer Science and Engineering, Ahsanullah University of Science and Technology, Dhaka, Bangladesh | [2]Department of Computer Science and Engineering, Pabna University of Science and Technology, Pabna, Bangladesh | [3]Department of Electrical, Computer and Biomedical Engineering, Toronto Metropolitan University, Toronto, Ontario, Canada |

Correspondence: Md Niaz Imtiaz (niaz.cse@pust.ac.bd)

Keywords: electroencephalography (EEG), emotion recognition, affective computing, deep learning, cross-subject learning, brain–computer interface (BCI), signal processing

ABSTRACT

EEG based emotion recognition is a relatively new topic in the field of affective computing, which can enhance the ability of human–computer interaction and be used in the field of health care and adaptive technologies. EEG records the dynamics of emotions in the brain and offers information about emotions, which is difficult to obtain by using facial expressions and voice data. Even though there is considerable progress made in this field, comparing different studies is difficult due to differences in experiments, representation of signals, machine learning approaches, and evaluations. While some recent reviews focused on different aspects of EEG based emotion recognition, the relation between methods and generalization capabilities of models needs to be investigated more deeply. In this review, we cover the field from the neurophysiological bases of emotion recognition and emotion elicitation techniques to EEG recording, signal processing, feature extraction, and classification. We focus on the influence of all the mentioned factors on the reliability and generalization of models. In addition to traditional and deep learning methods, we cover data augmentation, transfer learning, and domain adaptation approaches to overcome the problem of limited amount of data and inter subject variability.

1 | Introduction

Emotion recognition is at the heart of models of human behavior, since emotional states directly and profoundly affect human cognition, decision making, and social interactions. Automatic emotion recognition facilitates the development of intelligent systems capable of adaptively responding to the affect states of users, and this is particularly critical in contemporary human computer interaction tasks [1]. Emotion recognition in psychology and neuroscience helps in the objective analysis of affective phenomena independently of subjective self assessments, and in the health sector, it paves the way for numerous tasks, such as the objective evaluation of mood disturbances, patient recovery, and supportive treatment of neurodevelopmental disorders such as autism and affect dysregulation [2]. Emotion recognition in engineering and brain computer interface studies helps in developing adaptive systems capable of automatically responding to the affective states of users [3]. Emotion recognition using EEG recordings is particularly useful in patient oriented tasks in the health sector, such as patient recovery and long term evaluation of patient moods, wherein overt behavioral manifestations of patients could be ambiguous and unavailing. EEG emotion recognition stands distinct, as it directly taps brain signals related to emotion recognition, and this makes the technology valuable in tasks where robustness and physiological validity of the detection tasks are critical .

Electroencephalography (EEG) is an approach used in non invasive neurophysiology in order to record the electrical activity of the brain at high speed, thus making possible the study of fast neuronal processes responsible for emotions. The use of physiological information, which adds value to behavioral information,

especially when behavior is ambiguous or not enough, in emotion recognition through EEG is a field of research with applications in medicine [4].

EEG further provides important advantages compared to other emotion recognition methods, like facial expressions, speech, or body gestures. Behavioral cues are susceptible to intentional control, social camouflage, and context effects and are thus not very reliable in a sensitive context. Conversely, EEG oscillations are symptomatic of inner neural activities that are hard to manipulate intentionally and supply objective estimations of affective states [5]. Although increasingly explored, at least for the future of emotion sensitive BCIs, multimodal approaches combining EEG with other physiological or behavioral signals are not required, and EEG alone can be a robust and informative modality owing to its direct sensitivity to emotional brain dynamics and the compatibility with BCI systems.

Despite its benefits, it still faces some difficulties when it comes to identifying emotions using EEG. The quality of EEG signals greatly depends on parameters such as electrode placement, skin conductivity, movement artifacts, and inconsistency across sessions. Inconsistencies resulting from variations in experimental methods, emotions, labels, and preprocessing make the task harder [6]. This poses a challenge when trying to compare methodology based methods in order to evaluate their performance on various databases such as DEAP, SEED, and DREAMER [7]. Moreover, there are large differences between individuals leading to large changes in feature distributions of EEG signals.

The emergence of recent techniques in EEG based emotion recognition resulted in the appearance of various computational solutions that include traditional machine learning approaches using handcrafted features and deep learning solutions that automatically extract task related representations from EEG data. Deep learning solutions include convolutional neural networks (CNNs) for spatial patterns in EEG channels [8], recurrent neural networks (RNNs) for modeling of brain activities temporal dynamics [9], and graph neural networks (GNNs) for modeling of inter brain regions' connections [10].

There has been an increased need to carry out a review of up to date research work in the area of emotion recognition using EEG. There are many reviews that were mainly concentrating on architectural originality or evaluation tasks on a single dataset, with less concern for cross subject and cross dataset generalization [6]. Moreover, the lack of standard preprocessing methods and evaluation procedures makes it impossible to make reliable conclusions concerning the research [11]. There is no common understanding of the best way to create models and evaluate them for EEG based emotion recognition [12].

Past literature reviews have improved the understanding of emotion recognition via electroencephalogram (EEG) signals through their investigation into signal processing, features, learning, transfer learning, and experiments. Nevertheless, these factors tend to be studied independently without considering the interactions among them in relation to the neurophysiological properties, methodologies, and experiments used and what impact they have on the performance and generalizability of the EEG based emotion recognition process. To this end, this review integrates these aspects to explore the EEG based emotion recognition problem from a holistic perspective. The contributions of this review include the following:

1. Connecting the neurophysiological bases to the methodology choices made: In this literature review, emotion theories, stimulus design, recording of EEG signals, and brain activations are linked to the later stages of recognition. The study of such connections reveals how the experimental setup and properties of recorded neural signals impact signal processing and modeling.
2. Formulation of an integrated workflow centric framework for EEG emotion recognition: There are different frameworks that exist, each classified according to the various levels involved in emotion recognition such as pre processing, feature extraction/selection, modeling and evaluation. The dependencies of these stages are analyzed and described in order to show how decisions taken at one stage affect other stages.
3. Synthesis of relationship between EEG representation and learning approaches: In this review, it is considered how temporal, spectral, spatial, and time frequency representations are used in classical machine learning approaches and neural networks such as convolutional, recurrent, graph based, attention based, and hybrid networks. The approaches depend on the type of information being used, their dependence on features of brain regions and frequency bands, and on their computational demand.
4. Facilitating more meaningful comparisons through protocol aware evaluations: In this review, the impact of differences in datasets, emotion labeling, pre processing, and training testing protocols is considered in terms of the interpretation of reported results. This is done by looking at comparisons between subject dependent, subject independent, and transfer learning scenarios in relation to appropriate evaluation methods.
5. Connecting key methodological problems with their solutions: The current review integrates the problem of feature redundancy, overfitting, lack of training data, and variability of subjects into one single list which is accompanied by the corresponding solution methods. The methods of feature selection, regularization, data augmentation, transfer learning, domain adaptation, domain generalization, and fine tuning are evaluated against their purpose of improving recognition accuracy.
6. The requirements for applying experimental achievements in practice: Apart from classification accuracy, the analysis includes robustness, computational cost, channels needed, variability of recordings, and generalization on novel subjects. All these aspects define the research directions towards making EEG based emotion recognition more robust and applicable in practice.

As stated in Table 1, the unique value of this review is based on an integrative examination of neurophysiological background, recognition processes, approaches to learning, evaluation techniques, and implementation issues. Such an approach allows for exploring connections between these aspects and for defining limitations which have not been fully addressed yet.

TABLE 1 | Comparison of key research dimensions covered by recent reviews on EEG based emotion recognition.

Research Dimension	Jafari et al. 2023 [13]	Vempati and Sharma 2023 [14]	Erat et al. 2024 [15]	Wang et al. 2024 [16]	Ma et al. 2024 [5]	Geng et al. 2025 [12]	Chen et al. 2025 [17]	This Work
Emotion Theory	–	✓	✓	–	–	✓	–	✓
Stimulus Design	–	–	✓	–	–	–	–	✓
EEG Acquisition	–	–	✓	–	–	✓	–	✓
Multimodal Modeling	–	–	–	✓	–	–	–	✓
Feature Fusion	–	–	–	✓	–	–	–	✓
Data Augmentation	–	–	–	✓	–	–	–	✓
Model Taxonomy	✓	✓	✓	–	✓	✓	✓	✓
Domain Adaptation	–	–	–	✓	✓	✓	–	✓
Subject-Independent Evaluation	–	–	–	✓	✓	✓	–	✓
Evaluation Reproducibility	–	–	–	–	–	–	–	✓

Note: ✓ indicates substantial coverage of the specified research dimension, whereas indicates that the dimension is not treated as a distinct major focus. The comparison reflects the thematic emphasis of the reviewed articles rather than their scientific quality.

2 | Theoretical and Methodological Foundations

The theoretical background defines EEG-based emotion recognition as a framework that links measurable neurophysiological activity to computational representations of affect. It models emotional state as a structured pattern distributed across time, frequency bands, and scalp locations, and it treats learning as the problem of extracting robust features or representations from noisy, non-stationary brain signals. The paper also shows two methods for using emotion labels including the following paradigms: the discrete classification paradigm in which EEG segments are classified into separate emotion states and the continuous modeling paradigm in which the prediction of valence and arousal is performed [18]. These paradigms shape methodologies of design, evaluations and generalization of subjects and sessions [19].

2.1 | Emotion Recognition

Emotion detection is one of the basic goals of affective computing, which allows computer systems to detect and react to human emotions. The need for such technology has increased due to the increasing requirement for personalized and emotion aware human computer interaction (HCI) because of the possibility of improving the interaction of computer systems with users by detecting their affective state [1]. Conventional emotion recognition techniques rely on behavioral clues, such as facial expression, speech, gestures, and text. Nevertheless, the behavior can either be affected by the environment or can be hidden intentionally. However, physiological parameters offer more insights, which include the use of EEG to monitor brain activity, with emphasis on temporal resolution of the signal.

The EEG emotion detection is the act of detecting emotional states through the variations in the rhythmic and spatial dynamics of the brain due to emotional activities. This process is normally carried out by preprocessing, feature extraction through analysis of temporal, spectral, and time-frequency methods followed by machine learning. With the advancements in deep learning technology, it has been possible to extract complex spatiotemporal features automatically, thereby decreasing the reliance on manual feature engineering. However, individual differences, variation in data collection methods and protocol for emotion induction remain to be the challenge for achieving subject independence and cross dataset recognition of emotions, thus leading to the utilization of transfer learning and domain adaptation techniques [20].

As such, EEG based emotion recognition is more than obtaining high classification accuracies. Signal representations, standard protocols, and generalization evaluations are the necessary components in creating affective computing systems.

2.2 | Neurophysiological Foundations of Emotional States

Neurophysiological accounts of emotion in EEG emotion recognition interpret emotional episodes as changes in distributed brain activity that manifest as time varying and band limited oscillatory patterns across channels. EEG acquisition during affective stimulation, therefore, produces signals with spatial structure across electrode locations, temporal structure due to stimulus duration and sliding window segmentation, and frequency structure because analysis commonly separates δ, ϑ, α, β, and γ rhythms, each of which exhibits different responsiveness under affective conditions.

In this context, EEG based emotion recognition pipelines generally follow either a conventional sequence of denoising, feature extraction, and classifier training or an end to end learning approach. Both approaches depend on the availability of labeled data and the extent to which training and test samples satisfy the assumption of being independently and identically distributed (IID) [19]. When these assumptions fail especially under cross subject, cross session, or cross database settings emotion related neural patterns appear heterogeneous, motivating modeling strategies that explicitly target domain gaps and subject bias. EEG emotion recognition surveys formalize feature construction as multi-domain representation learning. Temporal features describe transitory to long lasting changes in events, while spectral features include anything like Bandpass filtering, Fourier transformation, and other transformations like them. Spatial features describe interchannel relationships that correspond to the spatial organization of the cortical structure of the human brain

and its variability. This multidomain stance links directly to contemporary architectures (CNN/RNN/GNN/Transformer variants) that operationalize spatial, temporal and spectral fusion and to transfer learning approaches that seek domain invariant representations under strong inter individual variability.
Benchmark datasets encode these neurophysiological assumptions by pairing affective stimuli like, videos or music with EEG recordings and either discrete labels or continuous ratings, thereby defining the target emotional state space and the evaluation protocol.

2.2.1 | Discrete Emotion Representation Models

Discrete emotion theories categorize emotions in a class form that starts from the general positive, neutral, and negative emotions to discrete emotions like happiness, sadness, and anger. Classification in EEG emotion recognition is concerned with the separation of the emotional classes using the neural activities captured as EEG data over time, frequency, and electrodes.
Commonly used features are PSDs and DEs in different frequency bands and the spatial information of multiple electrodes. Conventional classifiers such as SVM and KNN use manually designed features, while deep learning methods automatically extract the EEG features. Spatial and spectral features can be learned using CNNs, while temporal features can be extracted using RNNs. Relations between different electrodes can be represented by GNNs, while attention and hybrid models combine these abilities [10].




FIGURE 1 | Conceptual representation of affective states in the two-dimensional valence-arousal space.

Fig. 1 illustrates the valence-arousal space, in which emotional states are represented by their relative positions rather than isolated labels. Continuous ratings may also be divided into binary high/low classes or four valence–arousal quadrants, although these transformations discard some information about emotional intensity.
The recognition accuracy is also affected by the evaluation environment. While subject-dependent systems can take advantage of the patterns specific to an individual, subject-independent and cross-dataset classification needs to account for the variation in the EEG distributions. These changes can be overcome via transfer learning and domain adaptation, which involve the transfer of knowledge via instances, features, parameters, or relations. This implies that the usefulness of discrete emotion models is not limited to their classification performance alone.

2.2.2 | Continuous Dimensional Emotion Representation Models

The continuous dimensional model represents emotions in terms of affective dimensions such as valence (pleasure) and arousal (activation), while dominance is sometimes included as an extra dimension. In contrast to the discrete emotion classification approach, this enables EEG-based emotion recognition systems to predict or classify the dimensions like, high or low valence or arousal.
Dimensional modeling of emotions is crucial for EEG emotion recognition as emotions are defined as a change of the neural activity over time. Hence, it becomes necessary to preprocess and segment the EEG signals before calculating the spectral or entropy features like PSD or DE or obtaining features from the raw data through machine learning methods.




FIGURE 2 | Three dimensional representation of selected emotional states in the valence–arousal–dominance (VAD) space, illustrating their distribution across emotional pleasantness, activation, and perceived control.

The three dimensional emotion model extends the traditional valence-arousal framework by introducing dominance as an additional dimension of emotional experience. Valence describes whether an emotion is pleasant or unpleasant, arousal indicates its level of activation, and dominance reflects the degree of control an individual perceives over the emotional experience. As illustrated in Fig. 2, emotional states can be represented as distinct points within this three dimensional space, providing a more detailed description of their affective characteristics. By considering these dimensions together, the model offers a broader representation of emotional experiences, which can be useful for interpreting EEG responses and developing emotion recognition systems that account for variations in affective states.
A persistent limitation is the variability of EEG distributions and affective ratings across subjects, sessions, and datasets. Negative

transfer is one possibility of distribution mismatches in transfer learning and domain adaptation that might hinder the process of generalization. Thus, successful dimensional modeling should involve reliable labels and proper preprocessing as well as evaluation processes of the model.

2.3 | Emotion Induction and Stimulus Design

The induction method affects the way in which the affective state is induced, labeled, and compared to the EEG signal. Visual, auditory, and video stimuli are common due to controllable presentation times to allow trial separation and comparison among subjects [21, 22]. Post-stimulus questionnaires are helpful in making a link between EEG recording and the experienced emotion by the subject [13].

Tasks and memories can trigger relevant emotions. However, the unpredictability and subjective nature of the stimuli make it hard to control the experiment. The choice of stimuli for an experiment should combine standardization, relevance, and ecological validity. When working on multimodal data, synchronizing readings from peripheral channels to EEG recording is important in order to identify the same response [23].

The differences in stimulus type and emotional induction procedure might create distributional shift between corpora, which would impair the ability of the model to generalize on different corpora [24]. The use of the new contrastive and self-supervised paradigms, on the other hand, further motivates designing experiments that allow for acquiring diverse and comparable EEG recordings for building robust affective representations [25].

2.4 | Progress in Data Acquisition Technologies

Improvements in acquisition of EEG data have allowed emotion recognition to move from laboratory settings towards wearable devices and mobile applications. While research-grade systems allow a greater number of electrodes and produce more reliable data, their high cost, need for preparation, and lack of portability can make their application difficult. Therefore, the choice of the device should take into account the quality of data, comfort of participants, and conditions of use, since the differences in acquisition methods may affect the performance of models [3].

The number of electrodes and their placement define what regions of the scalp will be captured and how much spatial information will be available for classification. Fig. 3 shows a multichannel configuration covering frontal, central, temporal, parietal, and occipital regions of the brain. The selection of relevant channels may also help in reducing the computation complexity of the models while preserving emotion-specific information [26].

Some of these developments involve mobile and wireless systems that allow for more natural recording and bristle and comb-type dry electrodes which reduce the preparation of gel. Reduced-channel setups and cheap devices could increase availability, although the small number of channels, motion artifacts, and unstable electrode contact will continue to be limitations [27]. Real-time processing could help in mobile applications, although modifications in the hardware and recording settings could result in new distribution shifts.

EEG also shows oscillations in delta, theta, alpha, beta, and gamma frequency bands. Examples of these can be seen in Table 2 and Fig. 4. It is worth mentioning that these waves are not unique to a particular part of the brain and emotions, but depend on the cognitive environment in which they occur.




FIGURE 3 | Illustrative multichannel EEG electrode placement across major scalp regions.

TABLE 2 | Illustrative distribution of EEG frequency bands across major cerebral regions and their relevance to emotional processing.

Region	Example frequency bands
Frontal	Theta (4–7 Hz), beta (13–30 Hz), gamma (>30 Hz) [28]
Temporal	Theta (4–7 Hz), alpha (8–13 Hz), gamma (>30 Hz) [29]
Parietal	Alpha (8–13 Hz), beta (13–30 Hz) [28]
Occipital	Alpha (8–13 Hz), beta (13–30 Hz) [11]
Central (sensorimotor)	Mu (8–13 Hz), beta (13–30 Hz) [11]
Limbic-related (indirect)	Theta (4–7 Hz), gamma (>30 Hz) [30]

Information regarding regions and bands can be used to extract spatial-spectral features, but standard scalp EEG cannot localize limbic activity. Typically, emotion recognition requires decisions on how to record decisions that ensure the integrity of neural information in light of practical limitations.

2.5 | Multimodal Emotion Modeling

Emotion modeling in a multimodal framework makes use of behavioral features including facial expression, speech, textual inputs, and gestures along with physiological features including EEG, ECG, EMG, electrodermal activity, and respiration. Different features cover different facets of affective experience and




FIGURE 4 | Illustrative EEG waveforms across delta (1–3 Hz), theta (4–7 Hz), alpha (8–12 Hz), beta (13–30 Hz), and gamma (31–45 Hz) frequency bands.

could lessen the reliance on one feature which is inherently prone to noise, ambiguity, or context dependency [31, 32, 33].

In EEG-based emotion recognition, neural measurements provide temporal insights into neural activity, whereas behavioral and physiological measurements provide insights into the expressive or autonomic response. Taken together, these techniques, with their variety in terms of both the timing and type of measurements, could help to gain another view on emotions. The modalities of behavioral and physiological measurements are presented in Fig. 5.

Multimodal fusion is usually classified into early, intermediate, and late stages of fusion [33]. Early fusion fuses features prior to classification, thus making possible for interaction between modalities but increases dimensions and sensitivity to misalignment [32]. Intermediate fusion provides joint representation, which is able to represent more complicated dependencies but requires higher model complexity [34]. Late fusion merges output of classifiers for individual modalities, providing modularity but ignoring feature dependencies [34]. Attention and gating strategies allow for adaptation of the influence of each modality, but the efficiency is conditioned by the quality of the data [35, 36].

Multimodal datasets like DEAP and AMIGOS help in studying complementary affective signals [31, 37]. Nevertheless, additional modalities do not guarantee better generalization: synchronization errors, missing signals, inter-subject variability, and computational overhead remain important challenges. Reliable multimodal EEG systems therefore require carefully designed fusion strategies and evaluation against comparable unimodal baselines.

2.6 | EEG Correlates of Emotional States

Emotion-related EEG activity is reflected in changes across frequency bands, scalp regions, and time rather than in a single waveform amplitude or isolated neural rhythm. This distributed perspective motivates the analysis of oscillatory activity and interactions among brain regions when developing affective representations [38].

Understanding these correlates is important because emotion-related activity overlaps with broader cognitive processes, including attention and arousal. Modulation of alpha band has been widely studied in affective processing, whereas frontal beta band can provide additional information regarding emotional involvement and regulation, neither is emotion-specific [39]. Features from the delta and theta frequencies could offer further insights, particularly in the aspect of functional connectivity within varying frequencies [29].

Apart from the spectral properties of local signals, the correlations between channels for alpha, beta, and gamma bands can show coordinated brain activity that single channels might be unable to detect [40]. Spectral-spatial and connectivity-based models can leverage such correlations to describe the distributed emotional reactions. Time-based models are also important because EEG-based emotions take time to build up and are also dependent on when the stimuli are shown [41]. Interpretation techniques can be used to test whether discovered patterns are neurophysiologically valid [42].

Overall, EEG correlates of emotion are best understood as interacting spectral, spatial, connectivity, and temporal features, rather than unique markers of individual emotions. Combining




FIGURE 5 | Classification of emotion recognition modalities into behavioral cues and physiological signals, highlighting linguistic, visual, neural, and peripheral physiological measurements.

these two aspects would help in the selection of features and design of the model, however, the validity of these needs to be tested on individual subjects.

2.7 | EEG Signal Processing

The objective of EEG signal processing in emotion recognition is to transform the raw and noisy EEG signals into representations that are invariant to inter subject and inter session variability, while capturing the neurophysiological dynamics that are relevant to emotion [43]. In this regard, the signal processing pipeline is equivalent to a series of conditioning steps that include: (i) suppression of non cerebral noises, (ii) standardization of the temporal structure to facilitate learning, and (iii) definition of feature spaces that reveal the temporal, spectral, and spatial characteristics of emotional states. The signal processing pipeline is not just a pre processing step, it is a critical component that determines the information that can be extracted and utilized by the models, and it affects the robustness, interpretability, and generalizability of the models directly [8].

Affective EEG is usually measured using a specific protocol in which the emotional response is dynamic over time. Therefore, the processing pipeline must accommodate the ability to represent transient responses like, early perceptual responses and sustained responses such as, sustained affective responses. As the datasets move away from the controlled environment, the pipeline focuses more on the resilience of artifacts and stability across domains, encouraging the use of structured denoising, segmentation, and representations that align with the current deep learning encoder models [44].

The signals received through an electroencephalogram are known to be quite noisy and prone to a number of artifacts, and therefore preprocessing is an essential step for the recognition of emotions through EEG signals [45]. The preprocessing step is concerned with the cleaning and preprocessing of the raw EEG signals to improve their quality and normalize the input signals for the subsequent steps of feature extraction and classification [15]. The preprocessing of EEG signals is an essential step for improving the SNR of EEG signals and removing external noise and artifacts such as power line noise and physiological artifacts such as eye blinks and muscle movements for better performance of the classification model for emotion recognition. It is thus important to apply proper filtering, artifact removal, normalization, and other cleaning procedures before the feature extraction step [46]. Moreover, the use of similar preprocessing procedures such as the use of similar filters and scaling helps to eliminate variability and errors in the comparison of signals from different domains [44]. Below, we discuss a variety of critical preprocessing procedures and approaches used in recent studies on EEG based emotion recognition.

2.7.1 | Filtering and Noise Reduction

The process of filtering and noise reduction is one of the fundamental steps in the preprocessing of EEG signals, in which the raw EEG signals are cleaned of various types of non neural artifacts while keeping the relevant neural components. The EEG signal is very susceptible to external and internal noise, and thus filtering is critical in ensuring that the final signal is indicative of the cognitive or affective processes in the brain instead of other unwanted processes.

The filtering process is of utmost importance in the context of emotion recognition using EEG signals. Emotional states in the brain have very subtle effects in the standard EEG frequency bands, including delta (δ), theta (θ), alpha (α), beta (β), and gamma (γ). However, these effects can very easily get buried under unwanted effects caused by low frequency drifts (such as skin potentials or sweating), high frequency muscle movements (EMG), or electrical noise such as power line noise.

The noise reduction techniques that are generally used are band pass filtering for restricting the noise band to biologically relevant frequency ranges, notch filtering for eliminating noise components present at particular frequencies such as 50 Hz or 60 Hz, and spatial filtering for reducing the effect of noise artifacts. The more complex noise reduction techniques may include complex filtering methods such as regression analysis for reducing noise

artifacts and blind source separation for reducing noise components [47]. The type of filtering used, i.e., linear filtering, Butterworth filtering, and Chebyshev filtering, is important for avoiding phase distortion of emotional responses.
Even with these techniques, it is difficult to achieve an optimal SNR. The filtering techniques are such that they can eliminate genuine low or high frequency components of brain activity, which are characteristic of emotions. It is therefore critical to properly calibrate and validate filtering techniques to optimize noise reduction while preserving relevant features of the signal.

2.7.2 | Artifact Removal

Classic filters are unable to completely filter out nonstationary artifacts from the ocular and muscular systems in cases where the frequency band of such artifacts overlaps with that of neural activity. The artifacts from blinking, eye movement, and facial muscle activity can corrupt the EEG data features that will be analyzed for emotion recognition, especially at frontal and temporal electrodes [48].

2.7.2.1 | Independent Component Analysis (ICA).. ICA separates multichannel EEG signals into components that correspond to statistically independent sources. The components that are related to the ocular or muscular sources can be recognized from their scalp topographies, time courses, spectra, or additional recordings, and are then discarded when reconstructing the signal. Nevertheless, ICA requires an appropriate source mixing model, and discarding a component that includes both neural and artifact sources may lose important information.

2.7.2.2 | Principal Component Analysis (PCA).. PCA transforms correlated EEG channels into orthogonal, uncorrelated components ranked by explained variance. Artifact-dominated components can be suppressed before reconstructing the recordings. Although computationally straightforward, PCA separates variance rather than statistically independent sources, consequently, neural and artifactual activity may remain mixed, and rejecting high-variance components can remove relevant brain signals.

2.7.2.3 | Wavelet-Based Artifact Removal.. Wavelet transforms decompose EEG into time frequency coefficients, allowing transient artifacts to be attenuated through coefficient thresholding and subsequent reconstruction. Adaptive wavelet shrinkage has been investigated for ocular artifact suppression without rejecting entire EEG trials. The efficacy depends on wavelet choice and threshold setting, particularly when there is a temporal and spectral overlap between brain activity and artifact signals.

2.7.2.4 | Hybrid ICA Wavelet Techniques.. Hybrid methods employ the use of ICA for spatial separation along with wavelet based attenuation of those parts with artifacts. Rather than discarding an entire independent component, wavelet processing can suppress contaminated intervals or coefficients while retaining some underlying neural activity. Automated variants have used statistical measures, including kurtosis and multiscale sample entropy, to identify blink-related components. In an EEG emotion recognition study, hybrid ICA wavelet preprocessing improved classification relative to conventional ICA under the reported experimental conditions. Nevertheless, component selection, wavelet parameters, computational cost, and possible neural signal distortion require careful validation.
Overall, no single method removes every artifact without risk of signal loss. Preprocessing choices should be evaluated for both artifact attenuation and preservation of emotion relevant EEG features, preferably under the same downstream classification protocol.

2.7.3 | Channel Selection and Spatial Filtering

Channel selection and spatial filtering form part of the basic preprocessing mechanisms that focus on improving signal quality by optimizing the spatial representation of the EEG signal. Rather than considering all channels of the signal, these mechanisms focus on the most important parts of the scalp while avoiding the effects of noisy and irrelevant channels [49]. This becomes particularly important when dealing with emotion recognition via EEG signals, where emotion signals tend to be localized and easily obscured by irrelevant neural and physiological activities.
In affective computing, it has been found that the selection of important regions of the brain, particularly those that exhibit emotion, such as the prefrontal and temporal regions, can significantly improve emotion classification [50]. By selecting a specific subset of the electrodes, it becomes possible to reduce dimensionality, eliminate noisy channels, and simplify the process. Spatial filtering improves the clarity of the signal by re referencing the EEG signal and eliminating global noise components, thus enhancing the signal corresponding to localized neural patterns of emotion.
Several strategies are used in this context. For instance, manual or data driven channel selection methods are used for prioritizing certain electrodes based on neuroscientific knowledge or feature contribution metrics [51]. This ensures that only discriminative channels are used in the process. Spatial filters like CAR and Laplacian filtering are used for reducing reference bias and eliminating common mode noise. These filters are used for normalizing the EEG inputs for different channels and for highlighting spatial gradients that are related to emotional processes.
While these strategies are useful in several ways in terms of reducing computational requirements and improving robustness, they are not without their limitations. For instance, too much reduction of channels in this context would lead to the loss of emotional signals that are spatially distributed. Spatial filters would lead to signal topography distortion if not used properly.
Preprocessing methods for EEG have been listed in Table 3. Traditional techniques for suppressing artifacts, including multichannel Wiener filter, ICA, and wavelet denoising, are mainly aimed at removing the physiological artifacts from the EEG signals without losing the relevant neural data. The ICA and wavelet combination provides more flexibility because it includes both component separation and time frequency analysis. The channel selection and spatial filtering techniques try to eliminate redundant information and increase efficiency of spatial representations. Finally, the real time processing approaches pay special attention to computational effectiveness. According to Table 3, each of the above mentioned preprocessing approaches includes some compromises between artifacts reduction, preserving emotion neural information, computational complexity, and adaptability. Therefore, the choice of the proper technique should be made taking

TABLE 3 | Comparative overview of representative EEG preprocessing techniques relevant to emotion recognition.

Study	Approach	Preprocessing Method	Advantages	Limitations	Key Findings
Somers et al. [45]	Multi channel Wiener filtering for artifact suppression	Artifact Removal	Preserves neural signal while reducing ocular/muscle noise	Needs covariance estimates; less effective for nonstationary noise	Improves EEG signal quality before emotion decoding
Kang et al. [52]	ICA with heuristic artifact aware rejection	Artifact Removal	Effectively isolates and removes major EEG artifacts	Manual component selection may reduce reproducibility	Boosts classification accuracy post cleaning
Ahmed et al. [53]	Inverse-filtering-based baseline correction using DEAP EEG recordings	Filtering and Baseline Normalization	Reduces baseline-related subject variability and supports subject-independent feature extraction	Requires baseline recordings; effectiveness depends on baseline estimation and evaluation conditions	Improved valence and arousal classification compared with conventional subtractive and no-baseline-correction approaches
Sai et al. [54]	Automated artifact classification using SVM and wavelet-ICA	Hybrid ICA–Wavelet Techniques	Automatically identifies artifact-contaminated components without manual threshold selection	Validated primarily for eye-blink artifacts; extension to other artifact types requires further assessment	Improved identification of artifactual components while largely preserving relevant EEG source signals
Val Calvo et al. [46]	Lightweight real time preprocessing pipeline	Channel Selection and Spatial Filtering	Low latency and computationally efficient	Simplified features limit generalization	Enables real time EEG emotion recognition
Dura & Wosiak [55]	Channel selection strategy to reduce electrodes for deep learning emotion ER	Channel Selection and Spatial Filtering	Reduces channels while retaining discriminative information; lowers computation	Strategy may be dataset/model dependent; risk of losing spatial cues	Shows that careful channel reduction can maintain emotion classification performance
Issa & Juhasz [56]	Selective wavelet-enhanced ICA for ocular artifact removal	Hybrid ICA–Wavelet Techniques	Automatic suppression of EOG artifacts while preserving unaffected EEG segments; no reference EOG channel required	Primarily targets ocular artifacts; depends on accurate identification of contaminated components and intervals	Improved artifact removal compared with the evaluated component-rejection and wavelet-based methods in both time and spectral domains

into account the properties of the recorded signal, experiment protocol, and demands of further emotion recognition models.

The preprocessing of EEG data is the critical first stage that makes up the entire frame of reference and determines whether brain patterns that correspond to emotional states can be simultaneously detected. The drive for affective EEG signatures to be consistently identified relies on a number of factors such as, their low amplitude nature, the amount of ocular, muscular, and non-stationary artifacts present, etc., and as a result, preprocessing conditions, which can either improve or diminish classification accuracy, generalizability, and reproducibility.

The studies presented in Table 3 can be grouped into four complementary categories. Artifact removal strategies, including multi channel Wiener filtering, independent component analysis (ICA) based rejection, and wavelet thresholding have been shown to consistently improve the overall quality of the signal, and also have an impact on downstream recognition, but their applicability involves trade offs such as the validity of the covariance estimated like Gaussian, the subjectivity associated with selecting the appropriate components, or the location of the artifacts being targeted. Hybrid ICA wavelet approaches attempt to merge the separation component of ICA with the time frequency denoising capability of wavelets in order to automate the suppression of ocular artifacts, though the benefits of such techniques may be skewed towards blinks and need to be tested on other sources of artifacts [47]. Channel selection and spatial filtering strategies like using baseline normalized bandpass filtering, help to mitigate noise and inter subject variability, but rely heavily on the availability of baseline data, and may also attenuate informative bands unintentionally [55]. Lightweight real time pipelines are emphasized to provide low latency and computationally efficient online affective interfaces but not all of the simplifications used in these pipelines are designed to ensure that robustness will be obtained across subjects.

2.7.4 | Feature Extraction

Feature extraction converts preprocessed EEGs into discriminatory features that contain emotion-related brain activity. Given that emotional processes are based on interactions between time, frequency, and space information, combining multiple types of data leads to a more detailed representation of the underlying

states. Feature extraction algorithms can generally be classified into hand-crafted representations computed via statistical and signal-processing techniques and learned representations extracted using deep learning systems.

Advances in the design of EEG-based emotion recognition systems nowadays focus more and more on the construction of structured multi-dimensional feature representations that encode relations between channels, time windows, and frequencies. Two-dimensional and three-dimensional feature tensors allow building convolutional models with dependencies between spatial-temporal-spectral data [57]. Recurrent models like Bidirectional Gated Recurrent Units also account for temporal dependencies between consecutive EEG segments [58]. The same can be done for attention-based models like Conformers and Parallel Transformers–3D CNNs architectures [59].

Of the conventional feature set, power spectral density (PSD) and differential entropy (DE) still continue to be popular for frequency-specific EEG activity characterization [60]. While PSD captures signal power in specific frequency ranges, DE represents a logarithmic value of signal variance when a Gaussian assumption holds. For a Gaussian EEG segment, differential entropy can be defined as

$$h(X) = \frac{1}{2} \ln \left(2\pi e \sigma_X^2\right), \tag{1}$$

where σ_X^2 denotes the variance of the EEG signal. In this case, DE is linearly dependent on logarithmic power of signal, representing a concise form of emotion classification. Despite the fact that PSD and DE are relatively computationally convenient spectral parameters, temporal averaging may obscure the short-lived neural processes. However, both methods require correct setting of window length and overlap [61].

Overall, EEG feature extraction has progressed from handcrafted signal descriptors toward learned multidimensional representations capable of capturing interactions across neural domains. Nevertheless, their effectiveness depends on preserving emotion-discriminative information while controlling feature redundancy, computational complexity, and sensitivity to recording variability. The following subsections discuss temporal, spectral, spatial, and multidomain feature extraction strategies in greater detail.

2.7.4.1 | Temporal Domain Features. Temporal domain features play a critical role in emotion recognition systems that use EEG as a medium, as emotions are dynamic experiences that change over time [62]. Emotions are dynamic experiences that change over time and are often composed of a series of neural events that can't be described by time independent features. Temporal features help the emotion recognition system understand how brain activity is changing over time as a response to an emotional stimulus. These features are critical in handling intersubject variability in the timing of the emotion recognition response, as they help the system concentrate on the timing of the signal rather than relying on synchronous stimuli and labels.

Within the emotion decoding paradigm, temporal modeling has been integrated using a variety of deep learning approaches that have taken advantage of the strengths of sequence learning. As an example, recurrent models such as LSTMs or bidirectional RNNs have been widely used to capture the dependencies between successive segments of the EEG signals, modeling the temporal dynamics of affective states [63]. In other instances, hybrid models have been proposed that take advantage of the strengths of both convolutional and recurrent models to learn the spatial patterns and their temporal dynamics [9, 64]. In addition, hierarchical sequence models have been proposed that learn the signals regionally and then aggregate them globally, thus preserving the spatial patterns while modeling the temporal dynamics [65]. Finally, temporal convolutional models have been proposed that offer an alternative to recurrent models, enabling the modeling of long range dependencies using hierarchical, dilated convolutional architectures [66].

Although these methods are useful in terms of the recognition of dynamic patterns of emotion, there are challenges that are associated with these methods. These challenges include difficulties in integrating frequency and spatial information or the use of uniform timing [67]. The selection of appropriate window length and temporal resolution is also important in temporal domain modeling [68]. This is important for the avoidance of overfitting or the loss of relevant information, particularly for the improvement of the performance of emotion recognition, especially for naturalistic or continuous emotional scenarios where there is the presence of individual variations of emotional expression timing [69].

2.7.4.2 | Frequency Domain Features. Frequency domain features provide a promising approach for analysing the rhythmic characteristics of EEG signals, which are closely associated with emotional processing in the human brain. These features enable researchers to examine the distribution of EEG signal power across standard frequency bands, including theta, alpha, beta, and gamma, whose oscillatory activities have been investigated in relation to different emotional states. Unlike raw time domain representations, frequency domain features provide a compact description of neural oscillatory activity within a given analysis window. However, their stability across recording sessions and subjects depends on signal preprocessing, recording conditions, and inter individual variability [26].

Frequency domain features are particularly important in EEG based emotion recognition because they enable the analysis of band specific neural activity associated with emotional processes. For example, changes in beta band activity have been associated with heightened arousal, while frontal alpha power asymmetry has been investigated in relation to affective valence and hemispheric differences in emotional processing. Although spectral power features may be less sensitive to small temporal shifts than raw waveform representations, they remain susceptible to noise, physiological artifacts, and variations in spectral estimation parameters. Nevertheless, appropriate filtering and spectral feature extraction can provide informative representations for developing EEG based emotion recognition models.

Several methodologies have been explored for the effective modeling of frequency domain features. For instance, in some methodologies, the EEG signals were converted into spectrograms using various tools such as the STFT, allowing deep learning models to effectively learn the relative contribution of frequency domain features [70]. In other methodologies, the band power and differential entropy were considered as feature inputs, allowing the model to effectively capture the spectral content of each channel. More recent methodologies have also been explored, allowing the model to effectively capture the spectral relationship between channels using tools such as the convolutional model and attention mechanism [71]. In addition, multi domain models have

also been explored, allowing the model to integrate frequency domain and temporal domain representations for improved emotion recognition accuracy [72].

However, frequency domain modeling for emotion detection with its emphasis on consistent rhythmic patterns has its own set of limitations. For example, there is a need for balance in terms of spectral resolution and computational efficiency. In addition, the parameters of transformations such as STFT are critical and may affect the overall model. Moreover, frequency domain modeling may not account for other dynamics that are critical in decoding complex emotion responses.

In summary, frequency domain features form an essential pillar in EEG based emotion recognition systems. They are reliable and highly correlated with other emotion related features. In addition, frequency domain modeling with other domains forms an essential tool in modeling complex affective states with neurophysiological meaning [72, 70].

2.7.4.3 | Temporal Frequency Domain Features. Frequency domain features are the core of emotion recognition using EEG, as they are based on the rhythmic patterns of the brain's electrical activity, which are directly related to emotional states. The rhythmic patterns of the electrical signals in certain bands of frequencies, such as the delta band (1-4 Hz), the theta band (4-8 Hz), the alpha band (8-13 Hz), the beta band (13-30 Hz), and the gamma band (30-50+ Hz), are known to relate to various aspects of emotion. For instance, the power of alpha and beta rhythms is known to relate to the level of arousal and the valence of emotion. The asymmetry of alpha power in the frontal region is known to relate to approach/withdrawal aspects of emotion [73]. Frequency specific modulations are generally consistent across subjects and sessions, and hence are useful indicators of emotion classification.

In practice, the analysis of the electrical signals in the frequency domain is achieved through various techniques such as the Fourier transform, the wavelet transform, and the differential entropy method. The above techniques are used to transform the raw electrical signals to a more compact representation. The compact representation is useful because the electrical signals are more susceptible to noise.

Recently, various modeling techniques have adopted frequency domain features in different ways. In some models, frequency domain feature extraction has been performed independently, and the extracted features have been combined with temporal or spatial features to obtain enhanced emotion specific information. In other models, convolutional or attention based encoders have been employed to extract frequency domain features, which have been treated similarly to visual inputs to learn abstract frequency domain representations [74, 75]. In addition, various models have utilized graph based reasoning to extract frequency domain feature encoded nodes to identify inter band relationships and regional patterns [76].

Even though frequency domain based models have shown promising performance, various trade offs have been identified in their performance, including sensitivity to the parameters of the decomposition and windowing techniques employed in the models [77]. In addition, models that have adopted frequency domain based features may overlook essential temporal patterns, thus failing to accommodate different subjects with varying frequency domain patterns. Nonetheless, frequency domain based features have shown promising performance when combined with other features to provide robust brain state oscillatory patterns and improve emotion recognition systems.

2.7.4.4 | Integration and Fusion Strategies Across Feature Domains. The integration of temporal, frequency, and spatial features has emerged as a primary concern in EEG based emotion recognition, owing to the multidimensional nature of emotional brain responses. These features describe emotional responses from different but complementary perspectives, where temporal features describe the dynamics of brain responses, frequency features describe brain responses in terms of oscillatory properties, and spatial features describe brain responses in terms of brain regions [78]. Emotion expression in the brain does not occur in individual channels or frequency bands but occurs through interactions across multiple brain responses. Therefore, brain responses that combine multiple views are more expressive and tend to generalize better across subjects and sessions [79].

The importance of multi domain fusion becomes critical when handling noisy or uncertain EEG signals. There are scenarios where one domain may not contribute much or may be noisy, such as noisy temporal responses owing to movement, but brain responses in other domains can serve as a fallback, ensuring that fusion based methods are more robust, especially when handling real world or cross subject scenarios.

However, recent developments in multi domain fusion architectures have focused on flexibility and adaptability. Many of these methods involve multi branch architectures in which domain specific feature extractors process temporal, spectral, and spatial information in parallel, followed by fusion layers that combine the features. Some of these methods involve graph convolutional networks (GCNs) to represent spatial relationships between EEG channels, combined with temporal frequency encoders. Others involve attention mechanisms to dynamically assign weights to features across domains according to their relevance to the emotional state [80].

There is also an emerging trend towards deeper architectures that learn their own fusion policies implicitly. These include transformer based feature encoders with domain specific attention mechanisms and approaches with masked modeling for cross domain reconstruction [67]. These are very powerful architectures. However, they tend to be computationally expensive, requiring significant memory and regularization during training to avoid overfitting. Moreover, they also present difficulties with regards to their interpretation, as it is not clear what contribution each of the different domains makes towards the overall emotion prediction.

To summarize, the integration of various EEG domains can improve the model's ability to learn discriminative and generalizable representations of emotions. Fusion techniques can provide better modeling of emotional patterns, handling of noise, and stability of cross subject models. Although the above techniques provide considerable benefits, the trade off needs to be managed for the handling of computational complexities and the interpretability of the models. It is believed that future research will concentrate on the development of more lightweight, interpretable, and data efficient fusion techniques that can provide the benefits of multi domain integration.applications.

Each of these features provides supplementary information for emotion recognition from EEG, and their combination can contribute to stronger and more accurate emotion recognition models. Temporal features reflect the dynamic nature of emotional responses and their variation. Emotions are processes that depend on time. For example, emotional arousal may increase and subsequently decrease over time [81]. Frequency features focus on specific frequency bands of neurophysiological responses that are related to emotional processes. For example, changes in alpha and beta band power have been associated with relaxation and heightened cognitive engagement, respectively. Spatial features reflect emotional processes across different brain regions. For example, frontal alpha asymmetry has been investigated as an indicator of affective valence and hemispheric differences in emotional processing [73]. These three aspects are complementary, and their combination can compensate for some of the limitations associated with individual feature types. Empirical studies have demonstrated that integrating information from multiple feature domains, particularly spatial information with temporal or spectral representations, can improve emotion recognition performance compared with approaches relying on individual representations. In particular, spatial features are often combined with temporal or frequency features to provide context about where in the brain particular temporal or spectral patterns occur. The combination of features from multiple domains therefore creates a more comprehensive representation of the EEG signal, which can potentially improve the accuracy and robustness of emotion recognition against noise and inter individual variation.

Fusion is achieved using various architectural styles. First, tensor fusion involves the creation of multi dimensional input representations like, 3D tensors that enable an encoder network to learn interaction patterns implicitly. Second, multi branch fusion involves the use of dedicated encoders for each domain of temporal, spectral, and spatial and subsequent fusion of intermediate representations. Third, attention based fusion leverages adaptive weightings that highlight the most relevant domain or channel representations depending on varying noise conditions. The use of a dual branch dynamic graph convolution and adaptive transformer fusion presents an example of the potential for using spatial reasoning and attention based fusion mechanisms that leverage inter channel relationships and remain adaptive in feature weightings [39]. For multi domain EEG encodings, transformer networks are also developed that take in representations from various feature spaces and learn to fuse these using self attention [82].

A comparative overview of representative EEG feature extraction techniques is presented in Table 4, illustrating the methodological progression from conventional signal descriptors to deep learning based multi domain representations. Traditional temporal and frequency domain approaches, including statistical measures, higher order crossings, power spectral analysis, and differential entropy, provide relatively compact descriptions of emotion related EEG activity. Time frequency techniques, such as short time Fourier analysis, wavelet decomposition, and the Hilbert Huang transform, extend these representations by examining how spectral characteristics evolve over time. Spatial feature extraction approaches, including common spatial patterns, focus on the distribution of neural activity across electrodes. More recent learning based methods integrate multiple feature domains through convolutional, recurrent, graph based, and attention driven architectures, allowing complementary information to be combined within a unified representation. As highlighted in Table 4, these approaches involve different trade offs between computational efficiency, representation capacity, temporal sensitivity, and model complexity. Although multi domain learning can offer a richer description of affective neural activity, its effectiveness depends on the selected feature representations, fusion strategy, and experimental evaluation protocol. Therefore, appropriate feature extraction should balance discriminative performance with computational requirements, interpretability, and robustness across recording conditions.

2.7.5 | Feature Selection

In emotion recognition datasets using electroencephalogram (EEG) signals, datasets contain high dimensional feature vectors, including a high number of channels as well as different frequency band features. At the same time, several datasets contain a relatively low number of instances compared to the high dimensionality of the dataset. As a result, there is a great tendency for the occurrence of the curse of dimensionality, which may cause models to overfit as well as possibly ignore several relevant features in the dataset, which often reduces model efficiency as well as generalization of the classifier. Feature selection is one of the main concepts in pattern recognition as well as machine learning that helps reduce a high number of features in a dataset, containing only the most efficient as well as unique features, which can help in improving the efficiency of a classifier in pattern recognition as well as in improving the efficiency of the machines used [20].

2.7.5.1 | Filter Methods. Filter based feature selection is one of the most used feature selection techniques in EEG based emotion recognition systems. This is mainly because of its relative ease of implementation, speed, and classifier agnostic nature. Filter based feature selection approaches attempt to measure the significance of the features before actually training a classifier. Hence, these are generally employed as a pre processing step of the machine learning pipeline to reduce dimensionality and improve the learning efficiency of downstream classifiers.

The relevance of the filter method is determined by the nature of EEG data, which is usually characterized as being both high dimensional and noisy in nature. There is usually an involvement of emotion related features as well as other features in a pool of redundant and irrelevant information. Filtering out these less informative features at an early stage enables filter approaches to build better classification performance, reduce overfitting, and improve interpretability. This is particularly significant for EEG based emotion recognition tasks.

There are many different filter based methods for selecting good features. Two examples of filter selection methods are correlation based selection and mutual information (MI) selection. A correlation based method examines the correlation between each feature and the emotional label it is related to in order to find all of the features that have a high correlation with the individual emotional labels and the overall target emotion label [97]. In an MI based method, the MI score of each feature is calculated with respect to the associated target label as well as with respect to all

TABLE 4 | Comparative overview of representative EEG feature extraction methods for emotion recognition.

Study	Approach	Domain Category	Advantages	Limitations	Key Findings
Li et al. [57]	3D spatial temporal spectral features with FCNs	Spatial-Temporal-Spectral	Combines rich domain information in unified volume	Heavier computation than 2D encodings	Improves accuracy across datasets
Lew et al. [58]	Spatiotemporal encoding with Bi-GRU	Spatial-Temporal	Captures evolving emotion responses	Sensitive to segmentation granularity	Better for gradual emotion transitions
Song et al. [71]	Conformer model for EEG sequences	Spatial-Temporal	Fuses local and global patterns effectively	Can overfit without regularization	Outperforms traditional CNN/RNN models
Jia et al. [83]	3D DenseNet with attention across domains	Spatial-Temporal-Spectral	Learns dynamic relevance between features	Model complexity is high	Salient EEG areas enhance emotion decoding
Sun et al. [59]	Parallel transformer + 3D CNN fusion	Spatial-Temporal	Separates local/global representation branches	Careful tuning required for balance	Shows strong performance on multi channel inputs
Yudhana et al. [84]	FFT based spectral features with *k*NN classifier	Spectral	Simple and computationally efficient	Ignores temporal dynamics; limited scalability	Shows the viability of classic frequency features
Chen et al. [60]	Differential entropy features with LDA projection	Spectral	Compact and discriminative spectral representation	Linear assumptions limit expressiveness	Improves valence and arousal classification
Bigirimana et al. [85]	Multi class CSP spatial filtering	Spatial	Enhances emotion specific spatial patterns	Sensitive to non stationarity and subject variation	Boosts multi class EEG emotion accuracy
Lin et al. [86]	Power spectral asymmetry analysis for emotion classification	Frequency	Captures hemispheric imbalance related to valence	Sensitive to noise and baseline drift	Demonstrates frontal alpha asymmetry correlates with emotional valence
Jenke et al. [87]	Comparative evaluation of frequency domain EEG features	Frequency	Identifies robust spectral descriptors for emotion decoding	Requires feature selection optimization	Highlights differential entropy and PSD as strong frequency predictors
Murugappan et al. [88]	Statistical time domain features for emotion classification	Temporal	Low computational cost; suitable for real time systems	Limited ability to capture nonstationary dynamics	Shows time domain variance and mean features discriminate emotions
Gupta et al. [89]	Hjorth parameters and higher order statistics	Temporal	Reflects signal activity and mobility characteristics	Sensitive to artifacts	Demonstrates temporal descriptors contribute to valence arousal recognition
Petrantonakis & Hadjileontiadis [90]	Higher order crossings (HOC) for EEG temporal dynamics	Temporal	Captures nonlinear signal characteristics	Requires careful parameter tuning	HOC features enhance multi class emotion accuracy
Zhao et al. [91]	Short Time Fourier Transform for emotional EEG analysis	Temporal Frequency	Preserves both temporal and spectral information	Window size selection impacts performance	STFT based representations improve arousal classification
Subasi & Gursoy [92]	Wavelet transform for EEG emotional state detection	Temporal Frequency	Handles non stationary EEG signals effectively	Higher computational complexity	Wavelet coefficients improve emotional discrimination
Al Nafjan et al. [93]	PSD based spectral feature extraction with SVM	Frequency	Simple and computationally efficient	Limited temporal resolution	Confirms spectral power variations distinguish valence states

Continued on next page

TABLE 4 | Comparative overview of representative EEG feature extraction methods for emotion recognition.

Study	Approach	Domain Category	Advantages	Limitations	Key Findings
Li et al. [94]	Feature level fusion of spatial and spectral EEG descriptors	Fusion	Integrates complementary information	Risk of high dimensionality	Fusion improves robustness across subjects
Zheng & Lu [95]	Combined frequency and spatial asymmetry features	Fusion	Exploits hemispheric asymmetry and band power	Requires careful channel selection	Identifies critical bands and regions for emotion decoding
Zhang et al. [96]	Multi feature fusion with deep neural networks	Fusion	Learns hierarchical representation from heterogeneous features	High model complexity	Feature fusion enhances cross subject generalization

other features, to assess the relevance and redundancy of each feature. Similarly, each feature in the mRMR framework is evaluated based on its MI to the target label as well as its MI compared to all other features. The purpose of the mRMR framework is to identify a small, non redundant collection of features that provide the most information when identifying emotion labels. Extensions of the mRMR framework have been developed that incorporate methods such as sequential forward search or floating search, allowing for a larger, more exhaustive search of the feature space with improved efficiency.

Filter based methods have certain inherent limitations, they may produce suboptimal subsets of features when there are emotional patterns throughout multiple feature combinations or only when comparing each feature separately and independently. Therefore, the subset of features determined by filter methods will not always correspond to an optimal decision boundary that a classifier might find in an EEG based emotion recognition system, and so may lead to poor classification performance when classifiers use the features selected from the filter methods. However, filter methods remain viable techniques for EEG emotion recognition systems because of their large scale ability to apply to general tasks and their ability to be generalized [98].

2.7.5.2 | **Wrapper Methods.** Wrapper techniques make use of an elected classifier to estimate the performance of EEG feature subset selections, whereas filter techniques assess the features based on selection criteria that are unrelated to the classifier. Wrapper techniques can account for interactions among temporal, spectral, and spatial EEG features, but at the expense of increased computational overhead due to repeated model building [99].

Representative approaches include recursive feature elimination (RFE), which iteratively removes features according to their importance in a fitted model, and evolutionary algorithms that search candidate subsets through operations such as mutation and selection. Evolutionary feature and channel selection has been investigated for EEG emotion recognition, including mobile recordings, differential-evolution-based selection has also been evaluated for subject-independent emotion classification [100].

Despite their flexibility, wrapper methods can overfit the data used to select features and may be impractical when each candidate subset requires expensive training. Feature selection should therefore occur strictly within the training partitions, with separate or nested validation used for performance estimation. Ultimately, the value of wrapper selection depends on its computational efficiency and demonstrated performance on genuinely unseen subjects or recording sessions, rather than improvement on the feature-selection data alone.

A comparative overview of representative EEG feature selection techniques is presented in Table 5, highlighting the methodological differences, advantages, and limitations of filter based, wrapper based, and embedded approaches. Filter based methods primarily evaluate statistical relationships between individual features and emotion labels using criteria such as mutual information, normalized mutual information, and minimum redundancy maximum relevance (mRMR). These methods offer relatively low computational complexity and can reduce redundant information without depending on a particular classification algorithm. In contrast, wrapper based approaches employ iterative feature subset evaluation through evolutionary optimization, genetic algorithms, or sequential search strategies, allowing the selection process to account for interactions between features and classifier performance. However, their repeated model evaluations introduce additional computational costs and potential overfitting risks. Embedded methods integrate feature selection into the model development process through sparse learning, model dependent feature ranking, or attention based mechanisms, enabling the simultaneous optimization of feature relevance and predictive representations. As summarized in Table 5, each category presents different trade offs between computational efficiency, feature redundancy reduction, classification performance, and model interpretability. Consequently, selecting an appropriate feature selection strategy requires careful consideration of EEG dimensionality, dataset characteristics, computational resources, and subject dependent or subject independent evaluation protocols. These considerations are particularly important for developing reliable EEG based emotion recognition systems capable of maintaining discriminative performance across individuals and recording conditions.

Across all categories, a consistent finding is that reducing irrelevant or overlapping EEG features enhances generalization, improves robustness across subjects, and lowers computational burden without sacrificing accuracy. The table therefore reflects a broader research trend toward compact, discriminative, and task adaptive feature representations, which are essential for scalable and cross subject emotion recognition systems.

TABLE 5 | Comparative overview of representative filter-based, wrapper-based, and embedded feature selection techniques relevant to EEG emotion recognition.

Study	Approach	Feature Selection Method	Advantages	Limitations	Key Findings
Xu et al. [101]	Orthogonal regression for pairwise redundancy reduction	Embedded	Removes overlapping features, boosts relevance	Assumes linearity in correlations	Improves generalization across individuals
Kannadasan et al. [102]	Differential evolution for feature subset selection	Wrapper	Searches compact, accurate feature sets	Evolution search is slow at scale	Increases classification stability in DEAP
Liu et al. [103]	EMD with optimal subset evaluation	Wrapper	Efficient combination of decomposition and selection	EMD results vary with input noise	Smaller feature sets yield higher accuracy
Wang et al. [49]	NMI based EEG channel selection	Filter	Reduces redundancy and sensor count	Subset may vary across subjects	Preserves accuracy with fewer channels
Al Nafjan et al. [93]	ReliefF based statistical feature ranking	Filter	Fast computation and noise tolerant ranking	May overlook nonlinear inter feature interactions	Demonstrates effective dimensionality reduction for valence classification
Jenke et al. [87]	Comparative evaluation of filter based feature ranking methods	Filter	Identifies most discriminative EEG descriptors	Dependent on classifier compatibility	Highlights mutual information and Fisher score as effective EEG selectors
Shen et al. [104]	Sequential forward selection with SVM evaluation	Wrapper	Produces compact feature subsets	Greedy search may miss global optimum	Reduces dimensionality while preserving classification performance
Zhang et al. [105]	LASSO based sparse feature learning	Embedded	Automatically enforces sparsity during training	Linear constraint limits nonlinear capture	Sparse modeling enhances cross subject stability
Li et al. [106]	Deep neural network with attention based embedded selection	Embedded	Learns task relevant features automatically	Requires large training data	Embedded attention improves discriminative EEG feature learning




FIGURE 6 | Overview of the experimental design, EEG data acquisition, and signal processing stages for emotion recognition.

Fig. 6 illustrates the principal stages involved in acquiring and preparing EEG signals for emotion recognition. The process begins with experimental protocols in which participants are exposed to emotion eliciting stimuli, such as videos, audio recordings, and images, while their neural responses are captured through multichannel EEG electrodes. The acquired signals contain time varying neural activity distributed across conventional frequency bands, including delta, theta, alpha, beta, and gamma.

However, raw EEG recordings are susceptible to physiological artifacts, environmental interference, and irrelevant signal components, making appropriate preprocessing essential before extracting emotion related information. Common procedures include noise filtering, artifact removal, independent component analysis (ICA), wavelet based denoising, and spatial filtering. Following preprocessing, temporal, frequency domain, and spatial features can be extracted individually or combined through feature fusion to characterize complementary aspects of affective neural activity. Feature selection techniques, including filter, wrapper, and embedded approaches, can subsequently be employed to identify informative representations and reduce feature redundancy. These interconnected stages establish the foundation for reliable EEG based emotion classification and the development of computational models capable of learning discriminative emotional patterns.

2.8 | Challenges and Strategies in EEG Data Handling

EEG-based emotion detection has the problems of redundancy in features and lack of labeled data leading to overfitting issues. Therefore, good handling of data must include feature selection, in addition to data augmentation and data synthesis techniques.

2.8.1 | Feature Redundancy

Information contained in features extracted from neighboring electrodes, frequency bands, and time windows is often repetitive. Filter, wrapper, and embedded dimensionality reduction techniques can be used, while redundancy aware techniques specifically impose penalties on highly correlated features without losing their discriminative power. For instance, orthogonal feature selection with global redundancy reduction has been explored for EEG emotion recognition [101]. Feature selection must be fitted using training data alone to avoid optimistic performance estimates.

2.8.2 | Limited Data Challenges

Small sizes of participants, few recording sessions, and high costs of affective annotation make it difficult to obtain varied data for EEG training. Two ways of tackling this problem include data transformation and sample generation [107, 108].

2.8.2.1 | Augmenting Data Samples. In augmentation, label-preserving operations, like noisy perturbations or decomposition recombinations of signals, are applied to the training samples. Since EEG carries a temporal, spectral and spatial structure, any transformation needs to be physiologically plausible and have label consistency. Augmentation should be performed post subject/trial wise partitioning of data in order to avoid information leakage.

2.8.2.2 | Generating Synthetic Data. Generative models learn characteristics of the training distribution to create additional EEG samples or feature representations. Conditional Wasserstein generative adversarial networks (GANs) have been used to synthesize class conditioned differential entropy features, whereas GANSER combines adversarial generation with masked-signal reconstruction [107, 108]. Nevertheless, synthetic diversity does not guarantee improved generalization, generated data require quality assessment and evaluation on genuinely unseen recordings.

Overall, these strategies are most useful when they reduce redundancy or sample scarcity without distorting emotion-related activity or compromising evaluation integrity.

3 | Modeling and Evaluation Frameworks

EEG based emotion recognition methods structure a classification pipeline that transforms multichannel brain dynamics into affect labels through preprocessing, representation learning, and decision modeling [109]. Contemporary reviews emphasize that deep learning methods increasingly replace handcrafted feature stacks by learning discriminative spatial temporal abstractions from minimally processed EEG while still requiring careful protocol design for valid performance claims [109]. Model families differ in inductive bias, because convolutional encoders prioritize local spatial spectral regularities [8], recurrent encoders prioritize sequential dependencies [9], and graph formulations prioritize sensor topology and inter channel relations [10]. Evaluation settings, therefore, define methodological meaning, since subject dependent protocols favor personalization, whereas subject independent protocols favor invariance and generalization across individuals [5].

3.1 | Subject Dependent Analysis

Subject dependent analysis evaluates EEG emotion recognition models when both training and testing data come from the same individual. In practice, for each subject u, the data are split into within subject train/validation/test folds like., k fold or trial wise cross validation, and a model is trained to capture that subject's idiosyncratic spatio temporal and spectral EEG patterns. This setting is widely reported because it often yields higher accuracy than subject independent testing, providing an empirical upper bound on performance when per user calibration is allowed. However, it can overestimate real world generalization if the split allows data leakage such as, mixing highly correlated segments from the same trial across train/test. Recent surveys and systematic reviews emphasize that subject dependent results remain common in the literature, but they must be interpreted alongside the chosen splitting protocol and the calibration burden required per user.

The development of subject-dependent EEG emotion recognition techniques has been aided by deep learning models capable of recognizing the relationships both spatially and temporally within brain signals. In this context, Song et al. have suggested DGCNN which uses the multichannel EEG data in the form of a dynamic graph and learns the relationships between electrodes using an adaptive adjacency matrix. Although it is effective for the subject-dependent setup, its poor performance for subject-independent evaluation reveals the difficulty in making generalizations to different individuals. Moreover, Zhu et al. [110] have suggested SOGPCN where frequency-specific channel graphs, pseudo-3D spatiotemporal convolutions, attention and LSTM modules are used.

There are other studies that have focused on temporal modeling and the use of hybrid networks for emotion recognition tasks. In [111], Ma et al. propose a multimodal Residual LSTM that uses the concept of weight sharing between different modalities. While this model can leverage the complementation of affective information from different sources, the usage of multiple sensing modalities makes its use less applicable to unimodal (EEG-only) models due to increased data acquisition complexity. Finally, Ding et al. [112] introduce TSception, a model with multi-scale temporal convolution and hemisphere-asymmetry-aware spatial learning. The trial-wise evaluation used in ensures more conservative model performance compared to segmentation shuffling.

Recent work has also involved using convolutional neural network models in conjunction with attention-based approaches. DCoT [113], which incorporates depthwise convolutions and transformer encoder along with visualization of channel-importance is one such example. It is worth noting however, the lower performance under subject-independent validation implies robust recognition may still pose difficulties in absence of personal adaptation. Similar approach was employed by Liu et al. [114] in form of ERTNet framework combining CNN and transformer for high interpretability of its architecture. Despite the interpretability offered by this model, low performance during leave-one-subject-out analysis reveals that this characteristic does not necessarily mean good subject-independent performance. Spectrogram-based representations with application of both STFT and mel transformations, pretrained architectures and EEG-ConvNet were explored by Khan et al. [115]. It goes without saying that good within subject performance highlights the potential of the approach, but it is critical to conduct trials based on trial wise, session wise, and subject wise cross validation.

These studies, collectively, have proven that the use of spatial, temporal, graphs, and hybrid architectures is successful for emotion recognition in the dependent subject. Nevertheless, the performance is still strongly tied to experimental procedures and properties of the EEG in each particular individual.

$$\min_{\theta^{(u)}} \; \mathcal{L}_{\mathrm{SD}}^{(u)} = \frac{1}{|\mathcal{D}_{\mathrm{tr}}^{(u)}|} \sum_{(x,y)\in\mathcal{D}_{\mathrm{tr}}^{(u)}} \ell\big(f_{\theta^{(u)}}(x), y\big) \; + \; \gamma\, \Omega\big(\theta^{(u)}\big), \qquad (2)$$

where $\mathcal{D}_{\mathrm{tr}}^{(u)}$ is the within subject training subset for subject u, $f_{\theta^{(u)}}$ is a subject specific model (or a shared model fine tuned for u), $\ell(\cdot)$ is a classification loss (commonly cross entropy), $\Omega(\cdot)$ is a regularizer such as, $\|\theta\|_2^2$ or dropout induced implicit regularization, and γ controls the regularization strength. In subject dependent EEG emotion recognition, performance is strongly coupled to how $\mathcal{D}^{(u)}$ is split trial wise vs. segment wise shuffling, because temporally adjacent EEG segments within the same trial can be highly correlated.

Across recent subject dependent studies, the best performing methods under lenient within subject settings are typically spectrogram+CNN pipelines like, EEG ConvNet and fine tuned GoogLeNet/ResNet, which report near saturated SEED accuracy but may be most sensitive to leakage and dataset specificity [115]. Under more protocol aware within subject evaluation trial wise or leave one trial out, TSception provides a clearer picture of difficulty and robustness to leakage, albeit at lower accuracy, making it preferable when methodological rigor and reproducibility are prioritized [112]. For interpretability with competitive subject dependent performance, ERTNet offers strong AUC reporting and interpretable components but still faces major subject independent degradation [114]. For capturing inter channel topology, graph based models (DGCNN, SOGPCN) are attractive and can yield high within dataset accuracy, with SOGPCN reporting a small SD SI gap on SEED; however, portability across datasets/montages remains a practical concern [110]. Overall, subject dependent analysis remains valuable as an upper bound benchmark, but the most defensible conclusions come from studies that (i) use leakage resistant splitting and (ii) report subject independent/cross session results alongside subject dependent performance.

3.2 | Subject Independent Analysis

Subject independent methods are trained on the training set of the source population but tested on novel subjects. Thus, domain shift becomes the main source of errors [116]. Cross subject learning techniques minimize this issue using transfer learning and feature sharing via feature alignment, regularization, and parameter sharing, all without sacrificing emotions' relevant variations [117, 116]. Plug and play and adversarial domain adaptation frameworks explicitly align latent distributions between source and target subjects using unlabeled target data, so these methods target invariance without requiring full target supervision [118]. Domain adaptive neural formulations further refine alignment to preserve discriminability under shift. Similarity objectives for latent representation representations have been known to regularize geometry of the features for transfer purposes as well [119]. Contrastive similarity encourages invariant embeddings to subject by attracting the consistent samples in emotions while repelling the inconsistent emotion across subject pairs. Evaluation in cross corpus settings shows how invariance manifests when there is data level mismatch [24].

More recent subject independent methods integrate topology aware backbones with adaptation modules that manage both cross subject and cross dataset variability [120]. Domain adversarial graph attention models align relational representations across domains while maintaining spatial temporal structure [120]. Graph attention based spatial temporal learning further supports subject independent decoding by encoding dynamic inte ractions among electrodes [81]. Multiple Source Adaptation Methods treat each sample or data source as separate and create transferable models or common subspaces for them [121]. The pairwise and prototypical learning paradigms reduce negative transfer among heterogeneous sources [122]. Parameter efficient adaptation formulations reduce adaptation overhead while preserving transfer performance [123]. Broader domain generalization theory motivates training objectives that optimize shift robust representations rather than single domain accuracy [124].

3.2.1 | Transfer Learning Framework

Transfer learning is crucial for EEG emotion recognition because collecting extensive labeled calibration data for every new user is impractical, and EEG distributions vary across subjects and sessions even under identical elicitation protocols. Surveys consistently emphasize that subject independent performance depends on explicit mechanisms to mitigate covariate/representation shift

and negative transfer, especially under cross session and cross dataset deployment constraints. Transfer learning in this context includes (i) domain adaptation, (ii) domain generalization, and (iii) fine tuning, often combined in hybrid pipelines.

3.2.1.1 | Domain Adaptation. A persistent obstacle to subject independent EEG emotion recognition is domain shift, i.e., the mismatch between the training distribution (source domain) and the deployment distribution (target domain). In affective EEG, a domain typically corresponds to a subject, session/day, or dataset/device montage, and domain shift arises from strong inter subject variability, nonstationarity, and acquisition differences. Domain adaptation (DA) addresses this challenge by learning representations and decision rules that remain discriminative for emotion labels while reducing sensitivity to domain specific cues [125, 126].

In practical EEG emotion systems, models are often trained on multi subject datasets but must generalize to unseen users under leave one subject out (LOSO) or cross session protocols. However, EEG distributions can vary substantially across subjects and sessions even under the same task, causing performance drops when optimizing only the source empirical risk. Formally, with labeled source data $\mathcal{D}s = (x_i^s, y_i^s)i = 1^{n_s}$ and (often unlabeled) target data $\mathcal{D}t = x_j^t j = 1^{n_t}$, domain shift implies $P_s(X,Y) \neq P_t(X,Y)$, which may reflect covariate shift ($P(X)$), label shift ($P(Y)$), or conditional shift ($P(Y|X)$). DA mitigates these effects by incorporating an alignment term into training so that features extracted from source and target become closer under a chosen discrepancy while retaining emotion relevant structure [127, 128]. Domain adaptation (DA) addresses $P_s(X,Y) \neq P_t(X,Y)$ by learning representations that remain emotion discriminative while being domain invariant. With labeled source data $\mathcal{D}_s = \{(x_i^s, y_i^s)\}_{i=1}^{n_s}$ and target data $\mathcal{D}_t = \{x_j^t\}_{j=1}^{n_t}$ (often unlabeled), many DA methods optimize:

$$\min_{\theta_f,\theta_c} \mathcal{L}_{\text{cls}}(\mathcal{D}_s;\theta_f,\theta_c) + \lambda \mathcal{L}_{\text{align}}(\mathcal{D}_s,\mathcal{D}_t;\theta_f), \tag{3}$$

where $f_{\theta_f} : x \longmapsto h \in \mathbb{R}^d$ is a feature extractor, θ_c parameterizes the emotion classifier, $\mathcal{L}_{\text{cls}}$ is supervised label loss on source, and $\mathcal{L}_{\text{align}}$ reduces source and target feature discrepancy.

Beyond single source settings, Chen et al. introduced MS MDA for cross subject and cross session EEG emotion recognition, using a shared extractor for domain invariant features plus multiple one to one adaptation branches (each source paired with the target) to reduce negative transfer; they reported improvements on SEED/SEED IV transfer protocols, while the approach increases architectural/training complexity and depends on stable normalization choices across domains. To reduce the adaptation cost, Zhao et al. proposed a plug and play domain adaptation strategy that can adapt a trained model to a new subject with minimal modification, reporting gains in cross subject emotion recognition, a limitation is that performance may degrade when target shifts are large or when pseudo labels are noisy. For parameter efficiency, Zhang et al. proposed PARSE, a parameter efficient DA model for EEG emotion recognition that aims to adapt across subjects with fewer tunable parameters, such efficiency is attractive for deployment, but careful tuning is still needed to avoid under/over adaptation [123]. Multi source DA has also progressed: Li et al. proposed MS FRAN to leverage multiple source domains with improved transferability, showing stronger cross subject performance, but with added training overhead and sensitivity to heterogeneous source quality [121].

Graph based encoders have been combined with DA to better respect EEG channel topology. For example, Xu et al. have suggested DAGAM, a domain adversarial graph attention model, which provides enhancements in subject independent emotion recognition via joint modeling of spatial relationships and domain invariance, drawbacks of this method are computational expense and dependence on consistent graph generation [120]. Representation learning objectives that explicitly target invariance are also influential: Shen et al. [25] learned subject invariant representations via contrastive learning for cross subject EEG emotion recognition, often improving robustness without requiring a strong discriminator, but performance can depend on augmentation design and batch composition. In cross datasets scenarios, Imtiaz & Khan investigated unsupervised domain adaptation in improving cross dataset EEG emotion recognition and found improvement in case of mismatch of datasets/devices, outstanding issues are those of montage disparity and conditional shift which cannot be addressed only through marginal distribution adaptation [129]. The earlier domain alignment techniques used for affective EEG, such as latent representation alignment goals, are useful as simpler alternatives but are inferior when shifts are nonlinear [119]. Related empirical work on cross corpus/cross dataset affect recognition further supports that domain mismatch is a primary error source, motivating stronger DA and domain generalization strategies [130].

3.2.1.1.1 | Discrepancy Based Methods. Discrepancy based domain adaptation methods aim to reduce the statistical divergence between source and target feature distributions in order to enable knowledge transfer across domains. In EEG based emotion recognition, this approach is particularly relevant because physiological signals vary significantly across subjects, sessions, and recording environments, causing domain shifts that degrade model generalization. Discrepancy based methods measure and try to minimize the differences between the distributions of domains by using criteria such as Maximum Mean Discrepancy (MMD) and Correlation Alignment (CORAL). These kinds of methods try to make the representation of the features invariant against the domains. Discrepancy based domain adaptation techniques try to minimize the difference between distributions of source and target EEG features through metrics such as maximum mean discrepancy (MMD) and correlation alignment. Li et al. [116] designed an adaptation network which implements the idea of multilayer distribution matching in cross-subject EEG emotion recognition task. Although this method minimizes the distance between distributions, marginal alignment does not consider class conditional distributions and the performance depends on the choice of feature representations and alignment layers. In addition to discrepancy learning methods, Bao et al. [131] suggested a two-layer domain adaptation framework which includes MMD alignment, adversarial domain confusion, and normalization strategies. However, the inclusion of more optimization goals and topology based processing increases the training difficulty. In the same vein, the work of Chen et al. proposed the Multi-source Marginal Distribution Adaptation technique in which different adaptation paths were designed to align each source distribution with the target distribution. In spite of the fact that the method is able

to handle heterogeneous source distributions, its computation and memory demand increases with the number of sources, and successful adaptation requires dealing with the discrepancy of feature distributions per subject.

Overall, discrepancy based domain adaptation methods attempt to improve cross subject EEG emotion recognition by explicitly minimizing distribution mismatches between domains. Some examples of these approaches include deep adaption networks, multi level discrepancy alignment, and multi source marginal distribution adaption. Such methods have proved to perform better on various benchmarks such as SEED and SEED IV. These methods are, however, plagued by certain problems, among them sensitivity to feature layer choice, increased computational complexity in multiple sources, and capturing nonlinear/class conditional distribution shift.

3.2.1.1.2 | Adversarial Based Methods. Adversarial domain adaptation (DA) approaches aim to learn domain invariant representations by introducing an adversarial training mechanism between a feature extractor and a domain discriminator. In EEG based emotion recognition, adversarial methods are widely adopted to mitigate cross subject and cross session variability, which often causes significant domain shifts between training and testing data. Multi source adaptation techniques are inspired by GANs. The idea behind this technique is that the feature extractor tries to make the representation of its inputs such that it misleads the discriminator between domains. By aligning feature distributions implicitly through adversarial learning, these methods can capture complex nonlinear domain relationships that may not be effectively handled by explicit discrepancy minimization techniques.

Adversarial domain adaptation (DA) aims to learn domain invariant EEG representations by minimizing the ability of a domain discriminator to distinguish source and target features. Jin et al. [132] investigated adversarial adaptation for EEG emotion recognition and reported improvements under leave one subject out (LOSO) evaluation compared with non adaptive baselines. However, aligning a single source and target distribution may be insufficient to address heterogeneous subject characteristics and class conditional shifts. For distribution alignment improvement, Luo et al. [133] have proposed a Wasserstein GAN based adaptation framework with gradient penalty, which results in better cross subject recognition on SEED and DEAP. However, despite the benefits of adversarial optimization, the approach has extra complexity and needs hyperparameter optimization for stable training. On the other hand, Zhao et al. [118] have proposed the plug and play domain adaptation framework, where emotion shared and subject specific feature sets are distinguished in order to minimize the calibration. Nonetheless, the approach is limited by the amount of calibration data in the target domain. DAGAM, which is an application of spatial space, was proposed by Xu et al., where graph attention mechanism along with domain alignment helps to maintain relationships among electrodes as well as enhances recognition of subjects independently. But a high computational cost is needed while using graph attention mechanisms, and changing the electrodes would impact transferability. In a similar way, Yang et al. [134] provided a multi source adaptation method for cross subject and cross sessions recognition. Although the method exploits complementary domain features, its added modeling complexity and requirement of sufficient training data can make it prone to overfitting. All of these examples show the promise of using adversarial adaptation to minimize distributional discrepancies among subjects.

Domain Adversarial Networks (DANN) A canonical DANN objective combines label prediction with an adversarial domain confusion term:

$$\min_{\theta_f,\theta_c}\max_{\theta_d}\ \mathcal{L}_{\text{DANN}} = \mathcal{L}_{\text{cls}}\lambda\mathcal{L}_{\text{dom}}. \tag{4}$$

Here, let $h_i^s = F_{\theta_f}(x_i^s)$ and $h_j^t = F_{\theta_f}(x_j^t)$ denote the source and target feature representations, respectively. The classification and domain losses are

$$\mathcal{L}_{\text{cls}} = \frac{1}{n_s}\sum_{i=1}^{n_s}\ell\big(C_{\theta_c}(h_i^s), y_i^s\big),$$

$$\mathcal{L}_{\text{dom}} = \frac{1}{n_s}\sum_{i=1}^{n_s}\ell_d\big(D_{\theta_d}(h_i^s), 0\big) + \frac{1}{n_t}\sum_{j=1}^{n_t}\ell_d\big(D_{\theta_d}(h_j^t), 1\big).$$

Here, F_{θ_f} is a feature extractor ($h = F(x) \in \mathbb{R}^d$), C_{θ_c} is an emotion classifier, D_{θ_d} is a domain discriminator, and $\ell(\cdot)$ and $\ell_d(\cdot)$ are the label and domain losses (often cross entropy). The trade off parameter λ controls how aggressively domain cues are suppressed (via gradient reversal) while emotion discriminability is maintained [125, 135].

In practice, strong DANN style alignment is often paired with normalization or discrepancy losses to stabilize training and prevent class collapse, as in TDANN and related hybrids .

Overall, adversarial domain adaptation techniques aim to learn domain invariant EEG representations by training a feature extractor to confuse a domain discriminator while preserving emotion discriminative features. Methods ranging from early adversarial alignment models to more advanced architectures incorporating Wasserstein objectives, graph attention encoders, and multi source attention alignment have demonstrated improved subject independent emotion recognition performance. Despite these advances, adversarial approaches still face challenges such as training instability, increased computational complexity, sensitivity to domain heterogeneity, and reliance on calibration data or pseudo label quality in certain scenarios.

3.2.1.1.3 | Prototype/Cluster Based Methods. Prototype or cluster based domain adaptation tries to maintain the discriminative structure of the classes while adapting the domains. Instead of only matching marginal distributions, these approaches typically construct class prototypes or cluster centers and align target samples using pseudo labels or similarity measures. Such strategies are useful in EEG emotion recognition where class structure may shift across subjects, making purely distribution based alignment insufficient.

Prototype/cluster based DA preserves class structure via pseudo labeling and prototype alignment. Peng et al. [136] did class aware DA by joint feature adaptation and graph adaptive label propagation for cross subject emotion recognition, improving performance by leveraging graph structured pseudo label relations, one of the limitations include, label propagation which can amplify early pseudo label noise if target confidence is poor. Shen et al. did subject invariant representation learning using contrastive

objectives for cross subject emotion recognition, often improving robustness without requiring a strong discriminator, However, it gains dependency on augmentation policy, batch composition, and the stability of positive/negative pair construction.
Overall, prototype and cluster based approaches aim to maintain class consistency during adaptation by using pseudo labels, graph propagation, or contrastive clustering mechanisms. Such methods frequently work hand in hand with discrepancy or adversarial alignment due to the preserved class structure, however, their effectiveness may be dependent on good quality of pseudo labeling.

3.2.1.1.4 | Source Free Adaptation. Source free domain adaptation (SFDA) is concerned with cases where the original source samples are not available for the adaptation process because of privacy, storage constraints, or data sharing restrictions. Instead of accessing source samples, SFDA methods adapt a pretrained source model directly using only target domain data, typically through pseudo labeling, self training, or test time adaptation mechanisms.
Source free DA adapts models using only the target data at adaptation time, often due to privacy or data sharing constraints. Imtiaz & Khan [129] did cross dataset unsupervised target side adaptation using gradual pseudo target selection (GPTDS) and selective test time augmentation (PC-TTA), major limitation of it is cross dataset accuracy remains substantially lower than within dataset transfer and pseudo sample selection can be brittle under extreme domain gaps. Concurrently, Imtiaz & Khan [137] also proposed cross-dataset source-free unsupervised domain adaptation using Dual-Loss Adaptive Regularization (DLAR) and Localized Consistency Learning (LCL), with the major limitations being reliance on reliable pseudo-labels and limited adaptability to multiple target domains and dynamic distribution shifts.
Overall, source free DA provides a practical solution when source datasets cannot be accessed during deployment. While approaches such as GPTDS demonstrate promising improvements for cross dataset EEG emotion recognition, their performance still depends heavily on the reliability of pseudo label selection and robustness to large domain discrepancies.

3.2.1.2 | Domain Generalization. Domain Generalization (DG) aims to learn models that can generalize to unseen domains without using target domain data during training. Specifically in the field of emotion classification using EEG signals, DG techniques are crucial due to the fact that the EEG signals are highly varied between subjects. This means that the identity of each individual will have an effect on the problem of domain shift.
The survey work conducted by Zhou et al. [124] is on the study of domain generalization techniques using the analysis of invariant representation learning techniques, including meta learning, feature alignment, and data augmentation, although their study is primarily based on computer vision and not on EEG. Apicella et al. investigated domain generalization strategies for neural signal analysis by reviewing multi source training and invariant feature learning methods, but they reported that large inter subject variability in EEG still limits generalization performance . The issue of cross domain performance in EEG emotion classification with learning algorithms that depend on temporal, spatial, and frequency features was studied by Wang et al., but their method is still sensitive to domain dependent properties without domain invariant learning. Li et al. [11] proposed to use deep learning models including CNN and RNN for EEG emotion recognition via hierarchical learning from the raw data, but these models tend to overfit the subject specific information. In summary, DG techniques contribute to improving cross domain robustness for EEG emotion recognition through reduction of subject specific bias. Invariant representation learning is effective when there are several source domains, whereas augmentation based techniques are helpful when training data are scarce.

3.2.1.3 | Fine Tuning Strategies. Fine tuning strategies adapt pretrained models to a target domain using a small labeled calibration set. In EEG emotion recognition, fine tuning is commonly used when limited labeled samples from a new subject or session are available. By updating only a subset of parameters or applying regularization during training, fine tuning enables the model to retain previously learned knowledge while adapting to the specific characteristics of the target domain.
Fine tuning adapts a pretrained encoder/classifier to the target with a small labeled calibration set. A regularized fine tuning objective is:

$$\min_{\theta} \ \mathcal{L}_{\mathrm{FT}} = \frac{1}{|\mathcal{D}_t^{\ell}|} \sum_{(x,y)\in\mathcal{D}_t^{\ell}} \ell(f_\theta(x), y) \ + \ \mu\|\theta\theta_s\|_2^2, \qquad (5)$$

where f_θ is the adapted model, $\mathcal{D}_t^{\ell}$ is a small labeled target set, θ_s are pretrained parameters, and μ regularizes updates to avoid overfitting. Fine-tuning and transfer learning approaches are designed to enhance EEG-based emotion recognition by leveraging pretrained representations to different subjects or datasets. In Quan et al. [138], an MR-VAE based multi-source transfer framework was put forward where explicit source-domain selection is made for better knowledge transfer between heterogeneous EEG distributions. This method needs a small amount of target data, and poor choice of sources can cause negative transfer. Lu et al. [139] used fine-tuning in combination with domain adaptation in their DFF-Net approach to enhance cross-subject emotion recognition performance. From their ablation studies on SEED dataset, they showed that fine-tuning alone is better than domain adaptation alone. However, this method requires target-domain samples and is not proven in real-time online settings. To apply transfer learning in cross-dataset settings, PESD was proposed by Wang et al. [140]. This model is based on pre-trained Vision Transformer (ViT) encoder with Mixup augmentation, triplet loss, and adversarial domain adaptation. While all these approaches contribute to transferring features, pre-training and multiple optimization goals lead to greater computation costs. Altogether, all these research works show the prospects of fine-tuning and hybrid approaches in enhancing emotion recognition based on EEG data in different domains.
Across subject independent EEG emotion recognition, multi source DA like, MS MDA and attention aligned MSDA is typically best when many source subjects are available because it reduces negative transfer by respecting per source heterogeneity [134]. Discrepancy based hybrids such as, TDANN combining MMD and adversarial confusion often offer strong within dataset cross subject accuracy but require careful tuning and can be complex [131]. Calibration efficient adversarial methods like, PPDA are preferable when user burden is critical, trading some peak accuracy for rapid adaptation. Under severe cross dataset mismatch, source free unsupervised adaptation and pretrained encoders are increasingly competitive, though absolute accuracy

remains lower than within dataset transfer and robustness hinges on pseudo sample reliability and augmentation design.

Overall, fine tuning strategies remain an effective mechanism for adapting pretrained EEG emotion recognition models to new subjects or datasets when a small labeled calibration set is available. Recent works combining fine tuning with multi source transfer, domain adaptation, or large scale pretraining have achieved strong cross subject and cross dataset performance. However, these approaches still depend on limited labeled target data and may introduce additional training complexity, especially when hybrid adaptation frameworks or large pretrained encoders are employed.

3.3 | Machine Learning and Deep Learning Methods

The ML/DL techniques serve as the backbone of EEG-based emotion recognition by translating the neural information into affective categories using feature extraction, classification, and optimization. In contrast to traditional ML methods that use hand-engineered features, DL techniques are able to generate hierarchical representations of raw or preprocessed EEG data [141]. The performance of these techniques is greatly influenced by the signal quality, discriminability of the features, complexity of the model, and the evaluation criteria, especially in light of the nonstationarity of the EEG signals.

Formally, an EEG segment is represented as $\mathbf{X} \in \mathbb{R}^{C\times T}$, where C denotes the number of channels and T the number of temporal samples. A parameterized model f_θ maps this input to emotion labels or dimensional affective predictions. For supervised classification, model training commonly minimizes a regularized empirical loss:

$$\min_{\theta} \frac{1}{N}\sum_{i=1}^{N} \mathcal{L}_{\mathrm{CE}}\left(f_\theta(\mathbf{X}_i), y_i\right) + \lambda\|\theta\|_2^2, \tag{6}$$

where $\mathcal{L}_{\mathrm{CE}}$ denotes cross-entropy loss, N is the number of training samples, and λ controls regularization. This goal could be adjusted depending on the representation of the emotions, class balance, and learning paradigm [142].

In conventional machine learning pipelines, temporal, spectral, time-frequency, and spatial features were extracted before classification based on algorithms like support vector machines and ensembles [141]. On the contrary, deep learning architectures, including convolutional, recurrent, attention and graph neural networks, simultaneously learn discriminative features and decision boundaries. Despite the ability of these models to learn complex spatiotemporal dynamics, their performance is still sensitive to training samples, artifacts, normalization and complexity of the model [8].

Evaluation procedures are just as crucial. Personalized methods focus on personalized recognition, while subject-independent and cross-dataset setups focus on generalization in the face of distributional changes due to inter-subject variability, recording hardware, and experimental conditions [117, 143]. Overlapping EEG segments have to be split with care to avoid leakage of data, and feature scaling and model selection have to be done using only the training set. Besides accuracy, subject-based variability of performance and predictability are critical measures of robustness [144].

In general, good EEG emotion recognition needs a coordinated selection of features, architecture, optimization, and evaluation strategy beyond simple classification accuracy. These considerations provide the basis for comparing shallow and deep learning approaches under different experimental conditions.

3.3.1 | Shallow Models

Shallow models in EEG emotion recognition rely on an explicit feature map $\phi(\cdot)$ that converts the raw signal $\mathbf{X}$ into a moderate dimensional, engineered representation $\mathbf{z} = \phi(\mathbf{X})$, after which a classical classifier learns a relatively simple decision rule. Because the inductive bias is primarily encoded in the handcrafted descriptors like, time and frequency statistics, bandwise entropy, connectivity, shallow pipelines remain appealing when labels are limited and interpretability is desired, since each feature dimension can often be linked to a physiological hypothesis and inspected across trials or subjects [145, 22].

Liu et al. did shallow affect modeling by emphasizing an explicit feature map and compact affect sensitive descriptors like, entropy style band statistics with the limitation that performance depends strongly on preprocessing assumptions and hand engineering choices [146]. Differential entropy (DE) features treat band limited EEG as approximately Gaussian with variance σ_b^2 so that

$$h_b = \frac{1}{2}\log!\left(2\pi e, \sigma_b^2\right), \tag{7}$$

yielding compact descriptors that are widely used in shallow affect modeling [60]. Lieta et al. did EEG emotion recognition by organizing the pipeline around feature family specification and feature selection with the limitation that the selected subset can be unstable under session drift and may not preserve nonlinear class structure [145]. Feature selection is commonly posed as a sparsity regularized regression problem

$$\min_{\mathbf{w}} \|\mathbf{y} - \mathbf{Z}\mathbf{w}\|_2^2 + \alpha\|\mathbf{w}\|_1, \tag{8}$$

where $\mathbf{Z}$ stacks engineered features, $\mathbf{y}$ denotes labels (or label coded targets), and $\mathbf{w}$ indicates feature relevance. Zhou et al. did wavelet/transform driven feature extraction with classical learners and ensembles, it's major limitation is that time and frequency decompositions introduce design degrees of freedom such as mother wavelet, levels, statistics that can be dataset specific [147]. In many such transform based pipelines, decomposition driven representations express each EEG channel as a sum of intrinsic mode functions (IMFs) plus a residual term,

$$x_c(t) = \sum_{m=1}^{M} \mathrm{IMF}_{c,m}(t) + r_c(t), \tag{9}$$

from which per IMF or per band statistics are computed for classification. Zhang et al. did spatial/connectivity informed handcrafted representation learning with the limitation that connectivity estimates can be noisy and sensitive to artifacts, reference choice, and short window lengths [10].

Shallow learning methods' ability to recognize emotions from EEG signals is based on good artifact reduction, feature selection, and classifier design. The problem of artifacts in the conventional EEG processing pipeline was studied by Laih et al. [148], where the authors pointed out that ocular and muscle contamination can impact hand-crafted features and affect classification

results. In turn, the problem of automated EEG pre-processing to improve the consistency of feature extraction was considered by Sain et al. [54]. Automated techniques might have difficulties with dealing with unusual artifacts, thus introducing systematic biases in further analysis. To enhance the stability of features, Hadi et al. [149] proposed automatic feature and channel selection to find the informative features in EEG signals. However, the presence of artifacts and correlation between irrelevant features might result in unstable feature subsets and poor generalization. Interpretability of shallow classification methods was considered by Wank et al. [150].In addition to accurate classification, Witte et al. [144] noted the role of confidence and calibration in prediction, as models having similar levels of accuracy could show different levels of reliability of their predictions on other datasets. Egger et al. [151], for their part, noted the value of shallow learning models as an interpretable baseline, along with the role of combining preprocessing, feature selection, and classification in order to handle the variabilities of subjects and sessions.

Overall, shallow models are typically best when interpretability, small labeled data, or tight compute budgets dominate: compact band wise descriptors paired with stable classifiers provide strong, transparent baselines [146]. Wavelet/decomposition based features and ensembles are advantageous in cases of strong nonstationarity and variance reduction, but they have to be designed properly to avoid data specific parameterization [147]. Connectivity informed handcrafted features are most useful when the research goal is to relate emotion to distributed coupling patterns, but they are especially sensitive to artifacts and preprocessing choices, so rigorous cleaning and stable selection are prerequisites. Finally, when confidence is used downstream like., affect aware control, calibration aware evaluation becomes critical even for shallow pipelines, since unreliable probabilities can be harmful despite high accuracy.

3.3.2 | Deep Learning Models

EEG-based emotion recognition is made possible by deep learning models because of the feature extraction function $\phi_\theta(\mathbf{X})$. The variations across individuals, different sessions, and conditions of data collection make it necessary for models to differentiate between the emotions-related information and the individuality of subjects and the residual artifacts. Architectural design and evaluation are, thus, crucial in order to avoid overfitting and data leakage [152]. CNNs mostly learn the local spatial-spectral patterns, while the recurrent neural networks learn temporal dependencies; however, the sequential learning makes the process computationally expensive.

In addition to architecture design, preprocessing, data augmentation, and regularization all contribute to increasing model robustness. Correctly implemented augmentation can help make models less sensitive to changes in the recording setup, but augmentation techniques that have been poorly selected can cause distortions in physiological features. Preprocessing and automatic feature selection help in handling high dimensional data, while removal of artifacts needs to be done so as to avoid contamination due to the eye and muscles. Usage of autoencoders makes it easy to minimize the use of hand-crafted features, although the autoencoder models may have some irrelevant signal features. Interpretability and reproducibility remain important challenges. Channel-attention mechanisms can highlight potentially informative EEG relationships, but attention weights do not necessarily establish physiological or causal relevance. However, research in affective computing is concerned about the need for caution in interpreting the learned representations [80]. In addition, variations in methodologies in relation to the preprocessing phase, experimental setup, and evaluation process may have a considerable effect on the results, indicating the need for an unbiased evaluation process that is leak-free. Conclusion Deeps EEG emotion recognition requires a balance among representational ability, cost, interpretability, and generalization.

The modeling stage of EEG based emotion recognition encompasses a diverse range of computational approaches designed to extract discriminative representations and classify emotional states from neural activity. As illustrated in Fig. 7, these approaches broadly include traditional machine learning models, deep learning architectures, and transfer learning strategies. Conventional methods, such as support vector machines, random forests, k-nearest neighbors, and linear discriminant analysis, generally rely on predefined EEG features, whereas deep learning architectures, including convolutional neural networks, recurrent neural networks, LSTMs, and attention based models, enable increasingly complex representations of temporal, spectral, and spatial information. To address variations across subjects, recording sessions, and datasets, transfer learning approaches incorporate domain adaptation, domain generalization, and fine tuning strategies. Domain adaptation can further involve discrepancy minimization, adversarial alignment, clustering based methods, or source free adaptation when original source data are unavailable [153]. As shown in Fig. 7, the resulting models are evaluated using complementary measures, including classification accuracy, precision, macro averaged F1 score, receiver operating characteristic (ROC) analysis, area under the ROC curve (AUC), and confusion matrices. Considering these measures together provides a more comprehensive assessment of classification performance and class specific errors. Consequently, selecting an appropriate modeling approach requires balancing predictive performance, computational complexity, generalizability, and evaluation reliability.

Overall, CNN centric models are often best when local spatial and spectral patterns dominate and training data are moderate, whereas RNN/sequential models are preferable when temporal dynamics carry most discriminative information but can be harder to optimize. Topology aware encoders are most useful when cross electrode coupling is central to the affective mechanism, although they can be sensitive to montage and preprocessing [10]. Attention/transformer style models are best when long range, context dependent interactions are critical, but they demand careful regularization and protocol rigor to prevent leakage and spurious saliency. Across all families, the strongest empirical lesson is that domain generalizable deep EEG emotion recognition depends as much on disciplined evaluation and artifact aware preprocessing as on architecture choice [148].

3.3.2.1 | Standalone Models. Standalone deep models learn a single end to end mapping from EEG inputs to emotion labels and are therefore a useful lens for domain generalization: they expose how much cross subject/cross session robustness can be obtained from architectural inductive bias and disciplined




FIGURE 7 | Overview of modeling and evaluation approaches in EEG based emotion recognition, illustrating traditional machine learning, deep learning, transfer learning strategies, and commonly employed performance evaluation measures.

training alone, without additional fusion, multi branch alignment, or auxiliary objectives. In EEG emotion recognition, standalone baselines are valuable because they isolate representation learning in $\phi_\theta(\mathbf{X})$ and reduce confounding factors like, heterogeneous feature fusion and branch specific preprocessing, making results easier to reproduce and compare across protocols [154]. Their model specification typically centers on backbone type (CNN/RNN), input encoding like raw, time and frequency, or spatial maps, and depth and width trade offs that control expressivity versus overfitting and subject memorization [8].

Independent deep learning architectures were extensively studied in emotion recognition via EEG due to their ability to learn useful data representations without having to rely solely on handcrafted features. Convolutional neural networks (CNNs) were used by Cheng et al. to extract spatial-spectral characteristics of EEG signals. Although convolutional layers have proved effective at capturing local dependencies, their relatively small receptive field might not allow capturing long-term temporal dependencies without the use of any temporal mechanisms.

Apart from the architectural aspects, issues involving evaluation and efficiency must also be considered. For instance, the study by Egger et al. [151] demonstrated that deep learning approaches should be evaluated against feature-engineered classifiers under controlled experiments in order to determine recognition performance. Yet, unbalanced distribution of datasets may result in an overly optimistic evaluation due to correlation of EEG samples both in the training and test sets. At the same time, the paper by Suhaimi et al. [28] deals with the problem of differences in methodologies applied for the evaluation of performance of methods that are used to classify emotions on the basis of EEG signals and demonstrates how different procedures of preprocessing affect the result. With regard to computational efficiency, there has been research on lightweight methodologies of EEG signal classification conducted by Wank et al. [150]. While providing certain advantages in terms of memory and speed of inference, such methods might lack capacity to recognize patterns of EEG data.

A generic standalone convolutional block can be summarized as

$$\mathbf{H}^{(l)} = \sigma\left(\mathbf{W}^{(l)} * \mathbf{H}^{(l-1)} + \mathbf{b}^{(l)}\right), \tag{10}$$

where $\mathbf{H}^{(l-1)}$ and $\mathbf{H}^{(l)}$ are the input/output feature maps at layer l, $\mathbf{W}^{(l)}$ and $\mathbf{b}^{(l)}$ are trainable weights and biases, $*$ denotes convolution over the chosen EEG tensorization like, channel×time or time and frequency maps, and $\sigma(\cdot)$ is a nonlinearity. CNN only standalone models are attractive because they match spatial locality in EEG topographies and time and frequency representations, and they avoid multi branch fusion instabilities, which can otherwise obscure whether gains come from architecture or from fusion heuristics.

Overall, standalone models are best when the goal is clean benchmarking and ablation driven insight: they provide the most interpretable evidence of what inductive bias (CNN vs. RNN) and what training protocol contribute to performance. CNN only standalones are typically preferred when computations must be efficient and when discriminative cues are localized in time and frequency or spatial maps, while RNN family standalones are preferred when long range temporal dynamics are central but can be slower and harder to optimize. For real time affective systems with strict latency/memory constraints, lightweight standalone designs remain the practical choice, though they require careful regularization and input encoding to avoid underfitting.

3.3.2.2 | Attention Enhanced Models. Attention enhanced models extend deep EEG emotion recognition by making relevance a learnable function of the input, rather than a fixed property of particular channels or time points. This design choice is closely tied to domain generalization: because emotion relevant EEG evidence can appear sparsely in time and vary in spatial distribution across subjects, attention provides a content adaptive mechanism to emphasize discriminative substructures while suppressing nuisance variability. Consequently, attention based model descriptions emphasize (i) the granularity of attention (channel wise, temporal, or joint), (ii) the scoring function that produces weights, and (iii) the integration rule that mixes

attended features with a backbone representation, since these choices determine whether the model learns robust affective cues instead of memorizing subject specific patterns [80].

Beyond the attention applied to each channel, Zhang et al. studied the spatial and temporal relations between EEG signals in order to obtain informative neural interactions during emotion processing. However, despite the benefits that can be achieved by modeling the distributed brain activity, there are still issues of artifacts, referencing approaches, and segmentation in connectivity representations and temporal weighting. On a more general note, Roy et al. [152] gave an overview of the use of deep learning approaches in the analysis of EEG signals, which offers useful information about the design and evaluation of deep architectures. This is particularly relevant for attention-based models where improper data splitting and control can cause overoptimistic results. Transformer style attention increasingly appears because emotion relevant cues exhibit long range interactions across time and channels. Self attention defines queries, keys, and values as $\mathbf{Q} = \mathbf{H}\mathbf{W}_Q$, $\mathbf{K} = \mathbf{H}\mathbf{W}_K$, and $\mathbf{V} = \mathbf{H}\mathbf{W}_V$, and it computes

$$\mathrm{Attn}(\mathbf{Q},\mathbf{K},\mathbf{V}) = \mathrm{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}\right)\mathbf{V}, \tag{11}$$

which yields data adaptive aggregation over tokens that represent channels, time steps, or time frequency patches. Attention mechanisms fit EEG decoding because relevance concentrates in subsets of electrodes and epochs, so learned weighting acts as a soft selection operator that complements convolution or recurrence. Attention based designs also support post hoc analysis via saliency like maps, yet interpretability remains conditional because weight patterns do not necessarily imply causal importance [80].

Attention enhanced models introduce adaptive reweighting across channels and time, so they prioritize salient electrodes and temporal segments while suppressing irrelevant activity. Channel wise attention often learns a gating vector $\boldsymbol{\alpha} \in [0,1]^C$ and produces a reweighted signal $\tilde{\mathbf{X}} = \mathrm{diag}(\boldsymbol{\alpha})\mathbf{X}$, where

$$\boldsymbol{\alpha} = \sigma(\mathbf{W}_2\,\delta(\mathbf{W}_1\,\mathrm{pool}(\mathbf{X}))), \tag{12}$$

and pool$(\cdot)$ aggregates across time. Channel attention also acts as an implicit sensor selection mechanism, which reduces sensitivity to noisy electrodes and facilitates reduced montage systems [155]. Temporal attention highlights salient segments within a trial, which matters when affect evolves gradually rather than instantaneously. Attention enhanced models also introduce optimization sensitivity, so they require careful learning rate schedules and regularization to avoid unstable convergence.

Overall, attention enhanced models are best when discriminative evidence is sparse or subject varying in space/time and when robustness benefits from emphasizing salient substructures. Channel attention mechanisms are most useful when sensor noise or electrode relevance varies, enabling soft channel selection, whereas temporal attention is most useful when emotions evolve over time and informative segments are localized. However, attention modules increase optimization sensitivity and can overfit in small data settings, so they are most reliable under careful regularization, disciplined evaluation splits, and protocol checks that reduce leakage and annotation bias.

3.3.2.3 | Hybrid Models. Hybrid deep models for EEG emotion recognition combine multiple operator families like, convolution, recurrence, attention, graph/relational modules to capture complementary structure across space, time, and frequency. From a domain generalization perspective, hybridization is motivated by the fact that emotion relevant EEG cues can shift in their dominant form across subjects and sessions as, some subjects exhibit discriminative spatial patterns, others exhibit stronger temporal dynamics. Thus, hybrid models assume that no single inductive bias is universally sufficient and instead aim to learn representations that remain robust under nuisance variability by integrating multiple views of the signal. The model specification therefore emphasizes the participating modules, the fusion stage, and coordination constraints (normalization, scale matching, and regularization) needed to stabilize training and prevent a single branch from dominating [67].

Apart from representation learning, architecture complexity and evaluation consistency also matter. In their review on EEG emotion recognition methods, Suhaimi et al. [28] pointed out the variations in preprocessing, experimental setup, and evaluation procedure that hinder comparison between studies. The works by Egger et al. on alternative modeling methods serve as the starting point for evaluating the trade-off between model complexity and emotion recognition performance. The interaction between different modules in the hybrid architecture could cause optimization issues, which makes controlled ablation studies necessary for estimating the contribution of each module. Li et al. [142] introduced some ways of learning complementary representations from physiological signals, showing the possibility of using different feature learning mechanisms. However, the coordination of several processing modules increases the complexity of implementation and sensitivity to training settings. Overall, it seems that the effectiveness of hybrid EEG emotion recognition models should be proved by systematic ablation studies, consistent preprocessing, and proper cross-subject evaluation.

CNN and RNN hybrids commonly pass convolutional embeddings $\mathbf{h}_t$ (local spatial/spectral features) into a gated recurrent unit (GRU) to model longer temporal dependencies. A GRU update is:

$$\mathbf{z}_t = \sigma(\mathbf{W}_z\mathbf{h}_t + \mathbf{U}_z\mathbf{s}_{t-1}), \quad \mathbf{r}_t = \sigma(\mathbf{W}_r\mathbf{h}_t + \mathbf{U}_r\mathbf{s}_{t-1}), \tag{13}$$

$$\tilde{\mathbf{s}}_t = \tanh(\mathbf{W}\mathbf{h}_t + \mathbf{U}(\mathbf{r}_t \odot \mathbf{s}_{t-1})), \quad \mathbf{s}_t = (1-\mathbf{z}_t)\odot\mathbf{s}_{t-1} + \mathbf{z}_t\odot\tilde{\mathbf{s}}_t, \tag{14}$$

where $\mathbf{s}_t$ is the hidden state, $\mathbf{z}_t$ and $\mathbf{r}_t$ are update/reset gates, and $\odot$ denotes element wise multiplication. This structure encodes multi scale context by pairing local feature extraction (CNN) with sequential memory (RNN/GRU), which is useful when affective dynamics evolve over extended time.

Overall, hybrid models are best when emotion cues are multi factorial such as simultaneously spatial, temporal, and relational and when the dataset/protocol provides enough coverage to train multi module systems without overfitting. CNN and RNN (or CNN and Transformer) hybrids are often preferable when both short term rhythmic patterns and longer temporal context are discriminative, whereas topology aware+temporal hybrids are preferable when inter channel coupling is central to affect representation. However, because hybrids introduce optimization sensitivity and branch dominance risks, they are most reliable

under careful normalization, regularization, and disciplined ablations that separate true architectural benefit from preprocessing or split artifacts.

4 | Datasets and Comparative Study

A dataset-centric comparative evaluation is essential for assessing EEG-based emotion recognition methods because reported performance is strongly influenced by recording protocols, emotional stimuli, electrode configurations, annotation strategies, preprocessing procedures, and training–testing partitions. Consequently, meaningful comparisons require consistent documentation of dataset characteristics and evaluation protocols, particularly when distinguishing subject-dependent from subject-independent performance. The new surveys reveal the fact that variations in signal processing, segmentation, normalization, and data splitting can greatly affect reproducibility and the assessment of improvements in model performance [11].

There exist two types of annotation paradigms that are usually used in EEG emotion recognition datasets: dimensional representations (valence, arousal, and dominance), and discrete representations (emotions classified into predefined classes). The dimensional representation paradigm is based on the established affective models, such as the circumplex model. At the same time, self-assessment tools like the Self-Assessment Manikin (SAM) help to annotate subjective emotions. As shown in Table 6, different common datasets have a wide variety of attributes: number of participants, number of EEG channels, sampling rate, emotional stimuli, type of annotation, and modality types. DEAP, DREAMER, MAHNOB-HCI, AMIGOS, and ASCERTAIN are mainly used for dimensional affect recognition, and SEED, SEED-IV, MPED, FACED, and GAMEEMO are used for discrete emotional recognition with various classification complexity.

To justify dataset choice in an abstract in method agnostic sense, we recommend evaluating datasets along five axes: *(1) physiological fidelity* (channel density and sampling rate), *(2) label validity* (self report driven vs. clip assigned; discrete vs. continuous), *(3) generalization support* (subject count; multi session availability), *(4) ecological validity* (naturalistic stimuli, social interaction, task based affect), and *(5) reproducibility support* (documentation, file structure, provided features). These criteria align with the main reproducibility concerns highlighted in recent EEG emotion recognition methodological reviews. [167]

Table 7 further indicates the compatibility of different datasets for particular experimental goals. In addition to providing many more participants for the research of cross-subject generalization studies, FACED offers an increased number of participants relative to other datasets. Different recording sessions within SEED and SEED-IV enable inter-session variability analysis [157, 159]. The datasets which can be used for wearable devices applications and other purposes include low-channel EEG datasets of DREAMER and AMIGOS. ASCERTAIN is yet another dataset which may be used in the research on low-channel physiological sensing and users' emotions. Finally, multimodal datasets, such as DEAP and MAHNOB-HCI, allow for the analysis of complementary physiological and behavioral information using feature fusion methods.

Overall, there is no benchmark that covers all possible EEG emotion recognition scenarios. Thus, the choice of a dataset should be based on the particular recognition scenario, emotion label structure, acquisition process, modalities used, and evaluation protocol rather than accuracy reported by the authors. In particular, research on generalization should focus on subject-disjoint evaluation, proper preprocessing, clear data splitting, and cross-session or cross-dataset validation if applicable.

4.1 | Performance Metrics

Performance metrics provide a quantitative basis for evaluating EEG-based emotion recognition models, enabling comparisons of classification accuracy, class-specific errors, discrimination, and generalization. Their selection is particularly important because EEG datasets differ in emotional categories, class distributions, and experimental protocols. Therefore, depending on one measure might overlook some weaknesses, particularly in case of class imbalance and/or subject-independent evaluation. In recent researches, it has been stressed that different parameters and frameworks should be used for comparison [6].

Accuracy, precision, and recall are three basic evaluation criteria for classification problems, all obtained from the confusion matrix. The accuracy metric represents the percentage of correctly classified samples, while the precision criterion represents the quality of positive prediction, and the recall metric represents the percentage of correctly identified positive samples. While the accuracy metric gives an intuitive idea about the algorithm's performance, it can be deceptive in cases of unbalanced emotional classes. In binary classification problem, the number of true positives, true negatives, false positives, and false negatives is denoted as TP, TN, FP, FN, respectively, where $N = TP + TN + FP + FN$. The definition of these metrics is

$$\begin{aligned} \text{Accuracy} &= \frac{TP + TN}{N}, \\ \text{Precision} &= \frac{TP}{TP + FP}, \\ \text{Recall} &= \frac{TP}{TP + FN}. \end{aligned} \tag{15}$$

The F1 score measures the balance between precision and recall through the harmonic mean of the two. It is especially useful in an unbalanced emotion recognition task since it takes into account both false negatives and false positives, though it does not consider the true negatives.

$$\text{F1} = \frac{2\,\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}. \tag{16}$$

The macro F1 equally weights all emotions through averaging the value of F1 for each individual emotion:

$$\text{MacroF1} = \frac{1}{C} \sum_{c=1}^{C} \text{F1}_c, \tag{17}$$

where C is the number of emotion classes. Unlike accuracy, the macro F1 score does not depend on class occurrence and is therefore useful in assessing multiclass datasets where there is an imbalance in the distribution of the data set.

The balanced accuracy is yet another measure that accounts for class imbalance by assigning equal importance to sensitivity. The balanced accuracy in the binary classification model is given by:

TABLE 6 | Comparative overview of widely used EEG-based emotion recognition datasets.

Dataset	Subjects	Sessions	EEG Channels	Sampling rate	Stimuli	Label Space	Ratings	Modalities	Notes
DEAP [156]	32	1	32	512 Hz	40 music videos (60 s)	Dimensional	V/A/D + liking (1–9)	EEG + peripheral + video	Strong baseline; clear trial structure
SEED [157, 158]	15	3	62	200 Hz	15 film clips (~4 min)	3 class	Self report	EEG + eye tracking	Multi session; DE features available
SEED-IV [159, 160]	15	3	62	200 Hz	72 clips (24/session)	4 class	PANAS style	EEG + eye tracking	Fixed 4 s segments
DREAMER [7]	23	1	14	128 Hz	18 clips (65–393 s)	Dimensional	V/A/D (1–5)	EEG + ECG	Wearable oriented, low channels
MAHNOB HCI [161, 6]	27	1	32	256 Hz	20 videos	Dimensional + tags	V/A/D + keywords	EEG + multimodal	Rich synchronized modalities
AMIGOS [162]	40	2	14	128 Hz	16 short + 4 long videos	Dimensional + basic	V/A/D (1–9)	EEG + multimodal	Includes group/social context
ASCERTAIN [163]	58	1	1	32 Hz	36 clips (51–127 s)	Dimensional + personality	V/A + Big Five	EEG + multimodal	Single dry sensor, low bandwidth
MPED [164]	23	1	62	–	28 videos	7 class	Ratings + labels	EEG + multimodal	Fine grained discrete emotions
FACED [165]	123	1	32	250/1000 Hz	28 videos (~66 s)	9-class	0–7 ratings + V/A	EEG	Large scale dataset
GAMEEMO [166]	28	1	14	128 Hz	4 games (5 min)	4 class	Protocol based	EEG	Game induced emotions

$$\begin{aligned}\text{BalAcc} &= \frac{1}{2}(\text{TPR} + \text{TNR}) \\ &= \frac{1}{2}\left(\frac{TP}{TP+FN} + \frac{TN}{TN+FP}\right).\end{aligned} \tag{18}$$

Balanced accuracy is commonly applied when there are more than two classes, and it is computed as the mean recall across all classes, $\text{BalAcc} = \frac{1}{C}\sum_{c=1}^{C}\text{Recall}_c$. Unlike F1-macro which takes into account both precision and recall, balanced accuracy emphasizes only the sensitivity of emotions.

The area under the receiver operating characteristic curve (ROC-AUC) allows us to assess the discrimination power of the classifier. Unlike accuracy and F1 score, which depend on a selected operating threshold, AUC measures how effectively prediction scores distinguish positive and negative instances.

$$\text{AUC} = \int_0^1 \text{TPR}(\text{FPR})\, d\text{FPR}, \tag{19}$$

where $\text{FPR} = FP/(FP+TN)$ and $\text{TPR} = TP/(TP+FN)$. Although AUC provides a threshold-independent discrimination measure, it does not assess probability calibration or classification performance at a particular threshold. Multiclass evaluations should therefore specify the averaging and one-versus-rest or one-versus-one strategy employed.

Besides classification performance measures, consistency among participants and repetitions in experiments is crucial to evaluate generalization ability. Cross-validation and leave-one-subject-out (LOSO) evaluation help quantify performance variability, particularly when EEG distributions differ among individuals. For K evaluation folds, with metric value m_k for fold k, the mean and sample standard deviation are calculated as

$$\overline{m} = \frac{1}{K}\sum_{k=1}^{K} m_k, \qquad s = \sqrt{\frac{1}{K-1}\sum_{k=1}^{K}(m_k - \overline{m})^2}. \tag{20}$$

Reporting $\overline{m} \pm s$ provides information about both average performance and variability, although standard deviation should not be interpreted as a confidence interval. Subject-level analysis and consistent partitioning of data is crucial in determining unstable performance and preventing data leakage [167].

Moreover, statistical tests need to determine whether the improvements shown are consistent between the corresponding evaluation units. In cases where the paired differences are normally distributed, a paired t test could be used. Alternatively, in the case of symmetrically distributed paired differences, the Wilcoxon signed-rank test can be considered. Effect size measures, confidence intervals, and correction for multiple comparisons must accompany the significance tests in order to demonstrate the significance of the differences between the performances.

In conclusion, there is a need for more complementary evaluation measures instead of accuracy measures alone in order to conduct reliable evaluation of EEG emotion recognition models. Macro F1 and balanced accuracy are particularly valuable for imbalanced classification problems, whereas ROC-AUC is used to assess discrimination ability without thresholds.

TABLE 7 | Scenario-driven selection of EEG emotion recognition datasets for evaluating cross-subject generalization, cross-session robustness, wearable deployment, multimodal fusion, dimensional affect prediction, and discrete emotion classification.

Scenario / goal	Recommended datasets	Rationale
Cross subject (unseen user) modeling	FACED [165]; SEED [158]; SEED IV [160]	FACED contains a substantially larger participant cohort than many commonly used EEG emotion datasets, making it particularly useful for estimating inter subject variability and evaluating subject independent models. SEED and SEED-IV are also widely used in cross subject evaluation and provide structured experimental protocols suitable for separating training and testing subjects [168].
Cross session robustness (same users, different days)	SEED [169]; SEED-IV [170]	SEED contains repeated recordings from the same participants across three sessions separated in time, while SEED-IV follows a comparable multi session design. These properties permit explicit evaluation of session drift and cross session generalization rather than relying only on single session performance [168].
Wearable / low channel deployment constraints	DREAMER [7]; AMIGOS [162]; GAMEEMO [166]; ASCERTAIN [12]	DREAMER and AMIGOS use wearable, relatively low channel EEG systems, while GAMEEMO has been investigated under single channel EEG configurations. ASCERTAIN was specifically constructed using commercial sensing equipment. These datasets are therefore useful when evaluating reduced channel, consumer oriented, or practically deployable EEG configurations [27].
Multimodal fusion / sensor complementarity	DEAP [156]; MAHNOB HCI [161]; AMIGOS; MPED [164]; ASCERTAIN [163]	These datasets provide EEG together with one or more synchronized complementary modalities, including ECG, GSR, respiration, eye related information, facial video, or other peripheral physiological signals. They therefore enable feature level, decision level, and hybrid multimodal fusion as well as modality ablation experiments [16].
Dimensional affect (valence/arousal) as primary target	DEAP [156]; DREAMER; MAHNOB-HCI [161]; AMIGOS; ASCERTAIN	These datasets provide affective annotations based primarily on valence and arousal, with several also reporting dimensions such as dominance. Consequently, they are appropriate for continuous affect prediction as well as binary or quadrant based classification after explicitly defined discretization thresholds .
Discrete multi class emotion classification	SEED-IV [5]; MPED; FACED; GAMEEMO	SEED-IV provides four discrete affective classes, MPED contains seven discrete emotion categories, and FACED provides a finer grained nine category affective taxonomy. GAMEEMO provides four game induced affective conditions. These datasets are therefore suitable for multi class evaluation, including class wise recall, F1 score, confusion matrix analysis, and investigation of class specific errors [5].

4.2 | Experimental Analysis

Experimental evaluation of emotion recognition systems using EEG needs to be understood in light of the evaluation strategy since the extent of subject overlap between the training and testing data has a direct impact on the level of task difficulty [69]. In subject dependent evaluation, participant specific knowledge can be learned through training, while in subject independent evaluation, the validity of emotion representations for novel participants is examined. Transfer learning evaluation goes one step further by testing whether knowledge gained from a source can be transferred to a target domain [171].Consequently, accuracy values obtained under these settings should not be compared without considering the dataset, feature representation, number of emotion classes, and train test protocol [130].

This distinction is especially important for EEG because inter subject variability, session to session non stationarity, electrode configuration, and stimulus design can substantially alter the underlying feature distribution [172]. Earlier comparisons already showed a considerable difference between intra subject and inter subject recognition, while recent deep architectures increasingly address this problem through spatial and spectral modeling, graph learning, attention, domain adaptation, and transfer learning. The following comparisons therefore retain the original experimental conditions and reported accuracies rather than combining heterogeneous results into a single aggregate score.

4.2.1 | Subject Dependent Evaluation

Subject dependent evaluation uses EEG from the same participant population in both model development and testing, typically through within subject partitioning or cross validation. This setting is useful for measuring the representational capacity of a

model when subject specific calibration is available, and it generally produces higher accuracies than subject independent evaluation. The progression in Subject dependent EEG emotion recognition has been extensively investigated using conventional feature representations and increasingly sophisticated deep learning architectures. The comparative overview of representative works is given in Table 8. In earlier works, EEG features were mostly handcrafted, such as differential entropy (DE), power spectral density (PSD), and spatial EEG features, used together with convolutional or graph neural network models [173]. The most recent studies use adaptive graph convolution, attention, Transformers, and multi branch feature fusion to account for complicated spatial, spectral, and temporal dependencies involved in emotional response processing [174]. This indicates that there is an inclination to learn complementary representations of EEG data from neurons rather than focusing on specific frequency bands or electrodes.

From Table 8, it is observed that many studies have attained high accuracies for subject dependent evaluation on popular databases such as DEAP, SEED, SEED-IV, and DREAMER. Nonetheless, the reported results show significant heterogeneity of methodologies applied, including various configurations of emotion labels, input features, electrode placement, data segmentation, and validation strategy. Specifically, while some studies perform evaluation on individual EEG windows, others use trial wise grouping or other cross validation schemes. This is an essential issue since similar EEG segments presented in both training and testing datasets can provide overestimated accuracy. In addition, the difference between binary valence arousal classification, three class emotion recognition, and emotion categories make direct comparison of reported accuracies difficult. Therefore, the results presented in Table 8 should be treated as specific to the experiment conducted and cannot be viewed as ranking of classification architectures. Nonetheless, the results show the ability of deep learning to detect emotion related EEG patterns in individuals.

Subject dependent performance of EEG based emotion recognition has been visualized comparatively in Fig. 8 for six recent studies conducted on five standard datasets, i.e., SEED, SEED-IV, DEAP, DREAMER, and HBUED. The classification accuracy has been illustrated for various deep learning models used in those experiments. The experiments include binary classification of affective dimensions, multi class classification of emotions, and either window level or trial level classification of the data. The result shows that recently proposed subject dependent methods often have very high classification accuracy, which proves the efficiency of learning specific EEG spatial, spectral, and temporal representations for subjects.

Of the methods that use structured spatial representations, Lin et al. [177] proposed PconvCapsNet, achieving 98.03%, 97.81%, and 98.11% accuracy for the recognition of arousal, valence, and dominance, respectively, on DEAP. The accuracies of DREAMER on the same datasets are 97.20%, 96.49%, and 97.04%. In addition, Huang et al. [191] proposed AST-CLNet, using adaptive spatio temporal graph convolution and contrastive learning, achieving 99.71±0.45% and 97.91±1.49% accuracy on SEED and SEED-IV, respectively. On DEAP, the method achieved 98.17 ± 3.91% for valence and 95.92 ± 4.81% for arousal classification. These findings illustrate the potential of architectures that explicitly model EEG channel relationships and temporal dependencies, although their relative effectiveness cannot be established from heterogeneous evaluation protocols alone.

Attention and hybrid methods have also shown good results depending on the subject. Hua et al. proposed BRAD-Net, a model that incorporates brain region constrained attention together with complementary spatio temporal and spectral spatial features. The accuracy achieved by this model was in the range of 97.44 ± 1.19% - 97.97 ± 1.14% per each of the three emotional axes on DEAP, and for valence, arousal, and dominance on DREAMER, it attained 99.66 ± 0.22%, 99.78 ± 0.14%, and 99.80 ± 0.16%, correspondingly. Soundariya and Thangaraj [178] used the attentive wavelet transformer architecture and reported 99.61% window level and 99.30% trial level grouped accuracy on DEAP. It is particularly significant in terms of these two evaluation settings since the splitting of EEG signals affects classification performance.

Another example can be found from Liu et al. [180] who used their TaFormer model and obtained accuracies of 97.66%, 98.88%, 89.55%, and 99.85% on SEED, DEAP, DREAMER, and HBUED respectively. Inconsistencies between results on these datasets indicate the fact that good results on one dataset do not always mean good results on another dataset under other experimental conditions. The work of Venkannagari et al. [192] reports 98.52±0.79% accuracy on SEED with a framework for EEG classification using augmentations.

In aggregate, the findings depicted in Fig. 8 show that modern deep learning models are able to extract discriminative information regarding emotions from the EEG measurements on a per subject basis. Nevertheless, the prevalence of high classification accuracies cannot be considered as an unambiguous confirmation of cross subject performance. Divergent approaches used by different researchers to the selection of data samples, labeling of emotions, feature extraction, windowing and verification prevent the direct comparison of findings. In addition, the lack of standard deviations for some of the findings complicates performance analysis. Thus, the execution of trial independent testing and subject independent experiments becomes necessary for the determination of generalizability of the achievements mentioned.

The results demonstrate that subject dependent recognition has reached a high performance level on established benchmarks, particularly when spatial organization and frequency information are modeled jointly. On SEED, SFE-Net reports 99.19%, exceeding the selected DGCNN and DCoT configurations under their respective reported protocols. The 2026 PconvCapsNet results are also consistently close to 98% across the three DEAP dimensions and remain above 96% across DREAMER, while simultaneously reducing convolutional computation through selective channel processing. These values, however, represent calibrated or within subject recognition and therefore should not be interpreted as evidence that equivalent performance will be preserved for previously unseen individuals.

TABLE 8 | Comparative overview of representative subject-dependent EEG-based emotion recognition studies. Results are reported under their original experimental conditions. Differences in experimental protocols limit direct comparability across datasets

Study	Input feature(s)	Method	Dataset / evaluation	Accuracy (%)
Song et al. [175]	DE, PSD, DASM, RASM, and DCAU EEG descriptors represented over electrode graphs	DGCNN with dynamically learned inter electrode adjacency relationships	SEED; subject dependent	90.40 ± 8.49
Deng et al. [176]	Multichannel EEG reorganized into symmetry aware spatial representations preserving electrode topology	SFE-Net with symmetrical spatial feature extraction and convolutional representation learning	SEED; subject dependent	99.19
Jia et al. [83]	Three dimensional differential entropy representations encoding spatial, spectral, and temporal information	SST-EmotionNet using spatial, spectral and temporal attention with a 3D dense architecture	SEED and SEED-IV; subject dependent	SEED: 96.02 ± 2.17; SEED-IV: 84.92 ± 6.66
Guo et al. [113]	Differential entropy features extracted from the principal EEG frequency bands	DCoT combining depthwise convolutional representation learning with a Transformer encoder	SEED; subject dependent	93.83
Ding et al. [174]	DE features extracted by STFT from four frequency bands for DEAP and five bands for SEED; EEG electrodes form graph nodes	DGAT with a dynamically updated adjacency matrix and multi head graph attention for adaptive inter channel relationship learning	DEAP and SEED; five fold subject dependent cross validation	SEED: 94.00 ± 2.60; DEAP-V: 93.55 ± 3.89; DEAP-A: 93.19 ± 3.65
Xiong et al. [173]	DE, PSD, EVI, and ASI features from four frontal channels (FP1, FP2, AF3, AF4), mapped into pseudo RGB feature matrices	CNN-KAN-F2CA integrating convolutional feature extraction, FFT based frequency channel attention, and a Kolmogorov and Arnold Network classifier	SEED and DEAP; single subject subject dependent evaluation	SEED three class: 97.45; DEAP-V: 90.03; DEAP-A: 91.33; DEAP VA four class: 89.16
Lin et al. [177]	Bandpass filtered and baseline corrected multichannel EEG transformed into time and frequency representations	PconvCapsNet using selective partial convolution with synchronized channel bypass and primary and dense capsules with dynamic routing	DEAP and DREAMER; subject dependent	DEAP: A 98.03, V 97.81, D 98.11; DREAMER: A 97.20, V 96.49, D 97.04
Soundariya and Thangaraj [178]	Multiscale EEG components obtained through hierarchical wavelet packet decomposition and EWT with Kalman filtering	AWT-Net combining multiscale wavelet analysis, multi-head self-attention, a hybrid spatio temporal Transformer, and adaptive focal loss	DEAP; five fold subject dependent evaluation	99.61 window level; 99.30 trial wise grouped
Hua et al. [179]	Continuous temporal EEG for the spatio temporal branch and spectral spatial time and frequency maps preserving electrode topology for the second branch	BRAD-Net with brain region constrained self attention, CNN and Transformer temporal modeling, multi scale residual spectral spatial learning, and feature fusion	DEAP and DREAMER; subject dependent 10 fold cross validation	DEAP: V 97.44 ± 1.19, A 97.70 ± 1.13, D 97.97 ± 1.14; DREAMER: V 99.66 ± 0.22, A 99.78 ± 0.14, D 99.80 ± 0.16
Liu et al. [180]	Four dimensional dense EEG representation preserving channel topology together with temporal and multidimensional feature structure	TaFormer using triplet attention to learn cross dimensional, global spatial, and long range temporal information, followed by dual channel dynamic feature fusion	DEAP, SEED, DREAMER, and HBUED; subject dependent	DEAP: 98.88; SEED: 97.66; DREAMER: 89.55; HBUED: 99.85
Liu et al. [181]	Raw multichannel EEG signals processed directly without a separate handcrafted feature extraction stage	MLF-CapsNet combining multi level convolutional feature maps, primary capsules, dynamic routing, and a bottleneck layer for efficient end to end representation learning	DEAP and DREAMER; subject dependent emotion recognition	DEAP: V 97.97, A 98.31, D 98.32; DREAMER: V 94.59, A 95.26, D 95.13
Bao et al. [182]	Five band DE features extracted from segmented multichannel EEG; electrodes represented as graph nodes with connectivity initialized using channel relationships	MDGCN-SRCNN combining multi layer dynamical graph convolution with a style based recalibration CNN for joint shallow graph and deep convolutional feature learning	SEED and SEED-IV; subject dependent trial based evaluation	SEED: 95.08 ± 6.12; SEED-IV: 85.52 ± 11.58

Continued on next page

TABLE 8 | Comparative overview of representative subject dependent EEG-based emotion recognition studies.

Study	Input feature(s)	Method	Dataset / evaluation	Accuracy (%)
Salama et al. [183]	Three dimensional representations constructed directly from multichannel EEG, with data augmentation used to enlarge the training set	3D-CNN designed to jointly learn spatial and temporal EEG characteristics from the constructed volumetric representation	DEAP; subject dependent binary valence and arousal classification	V: 87.44; A: 88.49
Xiao et al. [184]	Raw EEG transformed into four dimensional spatial, spectral and temporal representations	4D-ANN combining CNN based spatial and spectral processing with spatial and spectral attention and a self attention enhanced BiLSTM for temporal dependencies	DEAP, SEED, and SEED-IV; intra subject evaluation with five fold cross validation	DEAP-V: 96.90 ± 1.65; DEAP-A: 97.39 ± 1.75; SEED: 96.25 ± 1.86; SEED-IV: 86.77 ± 7.29
Gong et al. [185]	Spatial, spectral and temporal EEG representations with attention masks applied to spatial and spectral information at each temporal slice	ACTNN combining lightweight spatial and spectral attention, convolutional local feature extraction, and Transformer based temporal encoding with multi head self attention	SEED and SEED-IV; subject dependent evaluation	SEED: 98.47; SEED-IV: 91.90
Chen et al. [186]	Differential entropy features represented as EEG graphs, with electrodes treated as graph nodes and frequency band information incorporated into node representations	DAMGCN combining graph convolution with Transformer style dual attention over electrode channels and EEG frequency bands	DEAP, SEED, and SEED-IV; 10 fold subject dependent cross validation	DEAP: V 96.96 ± 2.24, A 97.17 ± 2.35, D 97.50 ± 2.03; SEED: 99.42 ± 0.24; SEED-IV: 96.86 ± 1.33
Liu et al. [75]	Differential entropy features from five EEG frequency bands reorganized into three dimensional representations according to electrode topology	DSSA Net integrating vertical and horizontal positional attention, spectral attention, and Transformer based temporal attention	DEAP, SEED, and SEED-IV; subject dependent evaluation	DEAP-V: 94.97 ± 4.23; DEAP-A: 94.73 ± 3.27; SEED: 96.61 ± 5.39; SEED-IV: 85.07 ± 11.93
Chen et al. [38]	DE, symmetric difference, and symmetric quotient features extracted under four EEG frequency bands and mapped to electrode topology brain maps	MPICNN with parallel convolutional inputs that jointly learn multiple frequency spatial brain map representations	DEAP and SEED-IV; subject dependent four class emotion recognition	DEAP VA four class: 98.71; SEED-IV four class: 92.55
Huang and Deng [187]	Complementary DE and PSD features from θ, α, β, and γ bands organized into four dimensional spatial, spectral and temporal representations	4D-MRSimNet combining SimAM enhanced multi resolution CNNs for spatial and spectral learning with BiGRU and temporal attention	DEAP and DREAMER; subject dependent valence and arousal recognition	DEAP: V 97.68 ± 1.72, A 97.61 ± 2.20; DREAMER: V 99.60 ± 0.87, A 99.46 ± 0.72
Wei et al. [188]	Raw multichannel EEG divided into non overlapping temporal windows and represented as patches containing local and global EEG information	TC-Net combining an EEG Transformer, EEG-PatchMerging for local feature preservation, and an emotion capsule module for modeling relationships among multidimensional features	DEAP and DREAMER; subject dependent evaluation	DEAP: V 98.76, A 98.81, D 98.82; DREAMER: V 98.59, A 98.61, D 98.67
Lu et al. [189]	Spatial and temporal EEG representations together with spatial and frequency representations derived from PSD and DE features across five frequency bands	Bi-ViTNet using parallel Transformer branches to learn spatial and temporal and spatial and frequency information followed by feature level fusion	SEED and SEED-IV; subject dependent 7:3 train and test evaluation	SEED: 97.55 ± 1.58; SEED-IV: 88.08 ± 6.32
Qian et al. [190]	Multichannel EEG represented as an adaptive graph in which electrode relationships are learned rather than fixed a priori	AGCN-SAT combining adaptive graph convolution, spatial attention, and Transformer based global context modeling	SEED; subject dependent emotion recognition	92.76 ± 6.16
Huang et al. [191]	Multichannel EEG represented through learnable spatial and temporal adjacency structures for dynamic modeling of channel connectivity and temporal dependencies	AST-CLNet integrating dual branch adaptive spatio temporal graph convolution, channel attention, local and global feature fusion, and supervised contrastive learning	SEED, SEED-IV, and DEAP; subject dependent/intra subject evaluation	SEED: 99.71 ± 0.45; SEED-IV: 97.91 ± 1.49; DEAP-V: 98.17 ± 3.91; DEAP-A: 95.92 ± 4.81




FIGURE 8 | Subject-dependent EEG emotion recognition accuracy across datasets, with error bars indicating reported standard deviations. Differences in experimental protocols limit direct comparability across datasets.

4.2.2 | Subject Independent Evaluation

Subject independent evaluation excludes the target participant from model training, commonly through leave one subject out or related subject wise partitioning. It therefore measures whether learned EEG representations capture emotion relevant characteristics that persist across individuals rather than relying on participant specific electrophysiological patterns. The substantial performance reduction observed for several architectures when moving from subject dependent to subject independent testing illustrates the importance of explicit generalization mechanisms. Table 9 summarizes representative subject independent EEG emotion recognition studies spanning graph based learning, convolutional and recurrent architectures, Transformer based modeling, contrastive representation learning, and conventional feature selection methods. Unlike subject dependent evaluation, these protocols examine the ability of learned representations to recognize emotional states in participants excluded from model training. The reported results reveal considerable variation across architectures and datasets, indicating that recognition performance depends not only on feature representation and model complexity but also on the characteristics of the evaluation protocol.

Graph based approaches demonstrate the importance of modeling spatial dependencies among EEG channels. DGCNN achieved 79.95% accuracy on SEED, whereas SOGNN reported 86.81 ± 5.79% on SEED and 75.27 ± 8.19% on SEED-IV. Incorporating spatial and temporal graph attention with Transformer based representation learning, STGATE achieved 90.37 ± 6.18% and 76.43 ± 5.01% on SEED and SEED-IV, respectively [193]. More recent approaches report higher recognition rates under their respective experimental settings. NR-BA-BFE-Net obtained 95.56±4.18% on SEED and 83.15±3.40% on SEED-IV by integrating noise reduction, graph based frequency band representation learning, and attention mechanisms. These findings suggest that jointly modeling spatial relationships, frequency dependent characteristics, and noise related variability is a promising direction for cross subject emotion recognition.

Beyond graph oriented architectures, the results highlight the potential of alternative representations and learning strategies. DECNN reported 97.56% accuracy on SEED using dynamic differential entropy representations, while CLRA achieved 95.16% on SEED and reported 95.23% for valence and 96.31% for arousal on DEAP through brain area oriented contrastive representation learning [197]. However, results on DEAP vary substantially across studies. BiDCNN reported 68.14% for valence and 63.94% for arousal, whereas the hierarchical spatial learning Transformer achieved 66.51 ± 8.53% and 65.75 ± 8.51%, respectively [200]. Differences in feature construction, normalization, classification targets, subject partitioning, and experimental settings limit the validity of direct comparisons between these results. Furthermore, evaluations involving more emotion categories remain challenging. MSHCL reported 38.80% accuracy on the seven class MPED task and 45.70% on the nine class FACED task, illustrating the difficulties associated with more fine grained emotion classification.

TABLE 9 | Comparative overview of representative subject-independent EEG-based emotion recognition studies. A = arousal, V = valence, and D = dominance.

Study	Input feature(s)	Method	Dataset / evaluation	Accuracy (%)
Song et al. [175]	DE, PSD, DASM, RASM, and DCAU representations associated with EEG channels	DGCNN with dynamically learned graph adjacency for modeling inter channel relationships	SEED; subject independent	79.95
Li et al. [193]	Electrode level spatial and time and frequency EEG representations	STGATE combining spatial and temporal graph attention with a Transformer encoder	SEED, SEED-IV, and DREAMER; subject independent	SEED: 90.37 ± 6.18; SEED-IV: 76.43 ± 5.01; DREAMER-V: 77.44 ± 8.40; DREAMER-A: 75.26 ± 9.71
Dai et al. [194]	Channel wise EEG temporal signals reorganized according to functional brain area relationships	CLRA with 1D CNN and recurrent representation learning followed by brain area contrastive fusion	DEAP and SEED; cross subject	DEAP-V: 95.23; DEAP-A: 96.31; SEED: 95.16
Chang et al. [195]	Event related EEG representations organized at emotion and stimulus scales	MSHCL using emotion scale and stimulus scale contrastive objectives in hierarchical hyperbolic space	SEED, MPED, and FACED; cross subject	SEED (3 class): 89.30; MPED (7 class): 38.80; FACED: 77.00 (binary), 45.70 (9 class)
Song et al. [196]	DE features from five frequency bands represented through channel and frequency graph structures	IAG with sample dependent graph construction, multi level graph convolution, graph coarsening, and recurrent modeling	SEED; subject independent	86.30 ± 6.91
Liu et al. [197]	Dynamic differential entropy obtained using empirical mode decomposition and differential entropy	DECNN integrating dynamic empirical decomposition with convolutional representation learning	SEED; subject independent	97.56
Yin et al. [68]	DE feature cubes generated after baseline calibration and temporal segmentation	GCNNs extract graph domain features while LSTM captures temporal changes in inter channel relationships	DEAP; subject independent	V: 84.81; A: 85.27
Li et al. [198]	Time and frequency EEG channel features used to construct sample dependent electrode graphs	SOGNN with dynamically self organized graph construction and graph convolution for cross subject learning	SEED and SEED-IV; cross subject	SEED: 86.81 ± 5.79; SEED-IV: 75.27 ± 8.19
Priyasad et al. [199]	Multichannel EEG processed with independent channel wise representation encoders	Channel wise encoders coupled with geometric graph learning, multi head attention, and multi channel feature fusion	DEAP and DREAMER; cross subject	DEAP: V 69.43, A 69.72, D 70.72; DREAMER: V 64.98, A 63.71, D 61.81
Gupta et al. [77]	Channel specific EEG subbands obtained using flexible analytic wavelet transform, followed by information potential features	FAWT based subband decomposition, information potential feature extraction, feature smoothing, and random forest/SVM classification	SEED and DEAP; cross subject	SEED (3 class): 90.48; DEAP-V: 79.99; DEAP-A: 79.95; DEAP VA four class: 71.43
Huang et al. [200]	Three EEG feature matrices constructed to represent baseline adjusted activity and asymmetric responses of the left and right cerebral hemispheres	BiDCNN with a three input CNN architecture for learning inter channel and inter hemispheric differences	DEAP; subject independent, disjoint training and testing subjects	V: 68.14; A: 63.94
Fdez et al. [43]	Multitaper spectral EEG features with participant based normalization designed to suppress inter subject variability	Feed forward neural network with stratified normalization applied instead of conventional batch normalization	SEED; cross subject evaluation	91.60 (binary positive/negative); 79.60 (3 class positive/neutral/negative)
Wang et al. [51]	PSD features extracted from theta, slow alpha, alpha, beta, and gamma frequency bands and organized according to EEG brain regions	HSLT using electrode level and brain region level Transformer modules to learn hierarchical spatial dependencies	DEAP and MAHNOB-HCI; leave one subject out	DEAP-A: 65.75 ± 8.51; DEAP-V: 66.51 ± 8.53; MAHNOB-HCI-A: 66.20 ± 10.48; MAHNOB-HCI-V: 66.63 ± 6.51

Continued on next page

TABLE 9 | Representative subject independent EEG emotion recognition results.

Study	Input feature(s)	Method	Dataset / evaluation	Accuracy (%)
Li et al. [201]	DE features for SEED/SEED-IV and STFT based representations for MPED	GMSS combining graph representation learning with spatial jigsaw, frequency jigsaw, and contrastive self supervised auxiliary tasks	SEED, SEED-IV, and MPED; subject independent	SEED: 86.52 ± 6.22; SEED-IV: 73.48 ± 7.41; MPED: 28.49 ± 4.42
Zhang et al. [202]	Multichannel frequency domain EEG features represented through sparsified learnable electrode graphs	SparseDGCNN using L_1 regularized graph connectivity and forward and backward splitting to suppress redundant connections	SEED, DEAP, DREAMER, and CMEED; subject independent	SEED: 90.65; DEAP-V: 64.66, DEAP-A: 66.65; DREAMER-V: 68.18, DREAMER-A: 67.12; CMEED-V: 66.83, CMEED-A: 75.47
Ji et al. [203]	MIMO denoised multichannel EEG represented across principal frequency bands	NR-BA-BFE-Net combining noise estimation, subspace filtering, graph based band feature extraction, and band wise self attention	SEED and SEED-IV; subject independent	SEED: 95.56 ± 4.18; SEED-IV: 83.15 ± 3.40
Pandey and Seeja [204]	Intrinsic mode functions obtained from EEG using variational mode decomposition	VMD based feature decomposition followed by a deep neural network for subject independent emotion classification	DEAP; subject independent	V: 62.50; A: 61.25
Jana et al. [205]	Sparse spatio temporal EEG frames preserving electrode topology and temporal variations of multichannel signals	CapsNet trained on spatio temporal frame groups with leave one subject out and unseen subject evaluation	DEAP; cross subject	LOO subject mean: 57.17; unseen subject/unseen record mean: 51.07
Xu et al. [64]	Multichannel EEG sequences with temporal information retained from GRU units before subsequent spatial representation learning	GRU Conv combining GRU based temporal encoding with CNN based spatial feature extraction	SEED and DEAP; subject independent	SEED: 87.04; DEAP-A: 70.07; DEAP-V: 67.36
Yang et al. [206]	Ten linear and nonlinear EEG feature families including spectral, statistical, entropy, and Hjorth related descriptors	ST-SBSSVM integrating significance testing, sequential backward feature selection, and SVM classification	DEAP and SEED; cross subject	DEAP-V: 72.00; SEED: 89.00
Yin et al. [98]	Candidate EEG features represented through subject specific probability density functions to assess inter individual consistency	LRFS using kernel density estimation, recursive feature elimination, and ensemble classification across locally robust feature subsets	DEAP and MAHNOB-HCI; individual independent	DEAP-A: 65.10; DEAP-V: 67.97; MAHNOB-HCI-A: 67.43; MAHNOB-HCI-V: 70.90
Li et al. [207]	Thirteen linear and nonlinear EEG features extracted using overlapping 4 s windows, followed by L_1 regularized feature selection	Ensemble of selected base classifiers with weights optimized by multiple objective particle swarm optimization	DEAP and SEED; leave one subject out	DEAP-A: 65.70; DEAP-V: 64.22; SEED: 84.44
Bai et al. [208]	PSD and DE frequency domain feature matrices upsampled using cubic spline interpolation to retain relationships across EEG channels	SECT combining a global channel Transformer with a shifted channel Transformer for localized brain region representation learning	SEED and DEAP; subject independent public dataset evaluation	SEED (3 class): 85.43; DEAP-V: 66.83; DEAP-A: 65.31
Su et al. [209]	EEG feature representations projected into discriminative low dimensional spaces through paired synthesis and analysis dictionaries	GA-PDPL combining projection dictionary pair learning with genetic optimization of model parameters	SEED, MPED, and GAMEEMO; leave one subject out	SEED: 69.89; MPED: 24.11; GAMEEMO binary: 64.34; GAMEEMO four class: 49.01
Guo et al. [210]	Differential entropy features together with functional connectivity representations calculated using phase synchronization	FC-FAN using separate residual feature extractors, temporal feature grouped attention, functional connectivity grouped attention, and feature fusion	SEED; cross subject	92.12 ± 3.32
Kumar et al. [211]	Nine bispectral quadratic phase coupling descriptors extracted from frontal EEG rhythms, followed by genetic algorithm feature selection	Explainable Boosting Machine using compact nonlinear bispectral features under nested LOSO evaluation	DEAP; nested leave one subject out	A: 70.39; V: 69.98




FIGURE 9 | Subject-independent EEG emotion recognition accuracy across datasets, with error bars indicating reported standard deviations. Differences in experimental protocols limit direct comparability across datasets.

Overall, the results indicate that subject independent EEG emotion recognition benefits from representations capable of capturing informative spatial, spectral, and temporal patterns while reducing sensitivity to individual differences. Nevertheless, the considerable variability in reported accuracy, including among studies using the same datasets, prevents the identification of a universally superior architecture. Reliable comparisons therefore require consistent subject disjoint partitions, clearly documented preprocessing procedures, comparable emotion label definitions, and evaluation using complementary metrics such as macro F1 and balanced accuracy. These considerations also emphasize the importance of investigating transfer learning and domain adaptation as complementary strategies for improving recognition robustness across previously unseen EEG domains.

Fig. 9 depicts the reported accuracy of seven latest EEG based emotion recognition studies on subject independent and cross subject evaluation scenarios. The comparison involves six benchmark datasets, namely SEED, SEED-IV, DEAP, DREAMER, MPED, and FACED, where the classification tasks include binary affective recognition and nine class emotion recognition. In contrast to the subject dependent evaluation scenario, where the training and test data could come from the same subject, subject independent evaluation evaluates the capability of the model in recognizing emotions from unseen subjects. The latter is very important due to the fact that distributional variations of neural activity, emotional reactions, and EEG signals could be different across individuals. As shown in the figure below, the reported accuracy varies greatly among different datasets, classification tasks, and models.

Recent models that combine graph based feature learning and attention mechanisms have shown impressive cross subject recognition results. As an example, Ji et al. [203] proposed NR-BA-BFE-Net, in which noise estimation, subspace filtering, graph based frequency band feature extraction, and band wise attention scheme are used. NR-BA-BFE-Net has an accuracy score of $95.56 \pm 4.18\%$ on SEED and $83.15 \pm 3.40\%$ on SEED-IV datasets. Another model is FC-FAN proposed by Guo et al. [210], which is differential entropy, functional connectivity, along with attention based feature fusion architecture.. FC-FAN achieves $92.12 \pm 3.32\%$ accuracy on SEED dataset. Finally, Li et al. developed STGATE, which incorporates spatio temporal graph attention and Transformer based representation learning.This model has achieved accuracies of $90.37 \pm 6.18\%$ on SEED and $76.43 \pm 5.01\%$ on SEED-IV, in addition to $77.44 \pm 8.40\%$ and $75.26 \pm 9.71\%$ on valence and arousal recognition on DREAMER, respectively.

In addition, the approaches of contrastive representation learning and hybrid neural network architectures have been explored in order to enhance the classification of emotions independent of the subject. Dai et al. [194] suggested the method of CLRA which combines the use of convolutional and recurrent feature extraction with contrastive fusion of brain area features and achieved 95.16%, 95.23%, and 96.31% accuracies for SEED, DEAP valence, and DEAP arousal classification correspondingly. At the same time, the approach of MSHCL was developed by Chang et al. [195] and uses the hierarchical contrastive loss functions in hyperbolic representation space and achieved 89.30% for three class classification of SEED, 38.80% for seven class classification of MPED, and 77.00% and 45.70% for binary and nine class classification of FACED, respectively. In particular, the distinction

between binary and multi class tasks illustrates why classification accuracy should be interpreted with respect to the number of emotional categories and the corresponding evaluation protocol rather than considered independently of the experimental setting.

Other recent investigations have examined alternative feature representations and hybrid learning strategies. Ali et al. [212] used the CNN and LSTM model with convolutional block attention mechanisms and attained 68.67% accuracy on SEED-IV in a leave one subject out setting with 15 subjects and four emotions. Kumar et al. [211] studied the use of compact nonlinear bispectral features with feature selection and Explainable Boosting Machine and achieved 70.39% and 69.98% accuracy on arousal and valence detection on DEAP dataset, respectively, using nested leave one subject out setting. The above studies show the wide range of approaches that have been applied to the problem of cross subject EEG emotion recognition. However, differences in validation procedures, feature extraction strategies, and target emotional dimensions prevent direct conclusions about the superiority of one architecture over another.

Overall, Fig. 9 demonstrates that subject independent EEG emotion recognition remains a challenging and heterogeneous evaluation problem despite the encouraging results reported by several recent approaches. The variation witnessed through benchmarks highlights the fact that good classification results in one particular set do not guarantee generalized results in other sets or in other types of emotions. Additionally, variations in standard deviation data and the lack of uncertainty data in other cases make it difficult to assess model stability. In future research, it is recommended that there be emphasis on having subject disjoint evaluation, data regarding training and testing partitions, and performance measures for different classes in order to conduct statistical analyses using subjects withheld from experiments. These practices are important in proving the existence of generalization among subjects.

Subject independent results remain more variable because the classifier must operate under substantial person to person distribution shift. Transfer from multiple sources is highly effective in the chosen experiments, as seen in Quan et al. reporting 92.83% on SEED while simultaneously evaluating DEAP and SEED IV [138]. STGATE also demonstrates that jointly representing electrode topology and temporal dependencies can sustain useful performance across multiple datasets. Importantly, the 2026 CNN, LSTM and CBAM study reports a lower absolute value of 68.67% on SEED-IV, but it employs a strict LOSO protocol across all 15 participants and four emotion classes, with PCA fitted exclusively on training subjects [212]. Thus, lower accuracy under a stricter unseen subject protocol should not be interpreted as inferior representation learning without accounting for the evaluation design.

4.2.3 | Transfer Learning

Transfer learning explicitly addresses distribution mismatch by transferring useful emotion related knowledge from a source domain to a target domain. In EEG emotion recognition, the domain boundary may correspond to a recording session, an individual participant, or an entirely different dataset. These scenarios progressively introduce temporal, physiological, acquisition, and stimulus related discrepancies. Consequently, transfer learning methods have evolved from feature level distribution alignment toward multi source learning, calibration efficient adaptation, hybrid fine tuning, cross dataset unsupervised adaptation, and class conditional adversarial alignment.

Transfer learning in EEG based emotion recognition aims to improve the reuse of affective representations when the training and evaluation data differ across participants, recording sessions, or datasets. Rather than assuming identical feature distributions, these methods transfer information from source domains to a target domain through representation alignment, model adaptation, or limited target specific calibration. Table 10 summarizes representative approaches under their respective transfer settings.

The relevance of transfer learning arises from the considerable variability of EEG recordings across individuals and experimental conditions. Subject dependent models may exploit patterns specific to particular participants, whereas cross subject and cross session evaluation requires these patterns to remain informative in previously unseen data. Methods based on multi source learning, adversarial alignment, and feature distribution matching attempt to reduce such discrepancies, while calibration and few shot based approaches additionally exploit limited target domain supervision. As shown in Table 10, these strategies differ not only in model architecture but also in their assumptions about target domain data and labels.

The methods included in Table 10 illustrate the increasing diversity of transfer mechanisms. Adversarial and multi source approaches seek shared representations across subjects, while prototype based and pseudo labeling methods use class related structure to guide adaptation. More recent strategies incorporate Transformers, graph representations, curriculum based pseudo label refinement, and geometry aware alignment. Cross dataset experiments, including transfers between SEED and DEAP, examine a particularly challenging setting because differences in stimulus protocols, acquisition procedures, and participant populations may coincide. Such studies broaden evaluation beyond the more common within dataset cross subject scenario, although their reported accuracies remain dependent on the exact task and adaptation protocol.

Overall, the evidence in Table 10 suggests that transfer learning offers multiple practical routes toward more generalizable EEG emotion recognition. Nevertheless, accuracy values obtained under cross subject, cross session, cross day, few shot, and cross dataset conditions cannot be compared as a single ranking. Future evaluations should state the availability of target labels, adaptation stage access to target data, emotion class definitions, and partitioning rules to make the benefits and limitations of transfer strategies more transparent.

The transfer learning results show a clear methodological shift from global feature alignment toward class aware and target aware adaptation. Early WGAN based alignment already improved the feasibility of transferring DE representations across subjects, while multi source adaptation explicitly exploited differences among source participants rather than merging them into a single population. Calibration efficient PPDA reduced the amount of new user data required, whereas DFF-Net combined domain alignment with few shot fine tuning and reached 93.37% on SEED and 82.32% on SEED-IV.

The more difficult cross dataset setting remains substantially less accurate: the GPTDS/PC-TTA framework reported 59.68%

TABLE 10 | Representative transfer learning evaluations for EEG based emotion recognition. Results correspond to the original transfer setting of each method; cross subject, cross session, and cross dataset results should therefore be interpreted separately. A = arousal and V = valence.

Category	Study	Input feature(s)	Method	Dataset / transfer setting	Accuracy (%)
Adversarial feature transfer	Luo et al. [133]	Differential entropy EEG features	WGAN based domain adaptation for learning transferable source and target representations	DEAP and SEED; cross subject transfer	DEAP-V: 67.99; DEAP-A: 66.85; SEED: 87.07
Multi source domain adaptation	Chen et al. [170]	Five band differential entropy features from 62 EEG channels	MS-MDA, treating individual source subjects as separate domains and aligning marginal distributions with the target	SEED and SEED-IV; cross subject	SEED: 89.63 ± 6.79; SEED-IV: 59.34 ± 5.48
Hybrid DA and fine tuning	Lu et al. [139]	Differential entropy features extracted from δ, θ, α, β, and γ bands	DFF-Net combining an Emo-DA module with few shot target domain fine tuning	SEED and SEED-IV; cross subject	SEED: 93.37 ± 1.88; SEED-IV: 82.32 ± 5.38
Conditional adversarial transfer	Huang et al. [213]	DE and PSD features arranged as 14 s temporal sequences; each time step contains 310 features from 62 channels × five frequency bands	TT-CDAN using a temporal Transformer, MMD based domain adapter, and conditional domain discriminator	SEED and SEED-IV; cross subject	SEED: 93.62; SEED-IV: 82.16
Pseudo label propagation UDA	Zhong et al. [214]	Preprocessed emotion related EEG feature sequences from SEED, SEED-IV, and SEED-V, with temporal continuity exploited during propagation	DAPLP combining global distribution alignment, reliable pseudo label selection, graph based label propagation, correction, and smoothing	SEED, SEED-IV, and SEED-V; cross subject and cross session	Cross subject: SEED 89.44, SEED-IV 74.57, SEED-V 69.15; cross session: SEED 96.41, SEED-IV 82.20, SEED-V 84.70
Cross dataset UDA	Imtiaz and Khan [129]	Five band power spectral density features, DE was additionally evaluated in ablation experiments	Unsupervised domain adaptation with gradual proximity guided target data selection and confidence aware test time augmentation	SEED → DEAP and DEAP → SEED	SEED→DEAP: 59.68, DEAP→SEED: 67.44
Loop adversarial transfer	Yan et al. [215]	Electrode wise EEG feature matrices in which each sample contains n electrodes and d features per electrode	LATN integrating structure aware associative alignment, inner/outer product combination, and semi supervised pseudo label selection to suppress negative transfer	SEED, DEAP, and ECPL; cross subject	SEED: 94.34; DEAP-A: 89.21; DEAP-V: 76.12; ECPL: 96.33
Riemannian geometric transfer	Gao and Deng [216]	SPD covariance matrices computed from local DE feature vectors and represented on a Log Euclidean manifold	RGT-GAA combining a Log-Euclidean Graph Transformer with Fréchet mean geodesic alignment and adversarial domain adaptation	SEED and DEAP; LOSO cross subject, cross session, and one to one transfer	Cross subject: SEED 89.23; DEAP-V: 66.40; DEAP-A: 68.10; cross session: 92.38; one to one transfer: 74.56
Multi source dendrite adaptation	Liu et al. [217]	Five band DE features from δ, θ, α, β, and γ rhythms; 62 channel representations for SEED/SEED-IV and corresponding DEAP representations for cross dataset transfer	DD-MSDA using a dendrite-net common feature extractor, domain specific branches, source to target and target to target MMD alignment, and multiple domain specific classifiers	SEED, SEED-IV, and DEAP; cross subject, cross session, and cross dataset	Cross subject: SEED 87.57, SEED-IV 74.79; cross session: SEED 91.15, SEED-IV 75.57; cross dataset average: 57.66
Hierarchical adversarial transfer	Hong et al. [218]	Emotion evoked multichannel EEG representations from labeled source and unlabeled target subjects	HEAT with hierarchical global/class conditional adversarial alignment and curriculum based progressive pseudo labeling	SEED and SEED-IV; cross subject adaptation	SEED: 95.37 ± 5.17; SEED-IV: 82.50 ± 9.28

Continued on next page

TABLE 10 | Representative transfer learning evaluations for EEG-based emotion recognition.

Category	Study	Input feature(s)	Method	Dataset / transfer setting	Accuracy (%)
Multi source style transfer learning	Li et al. [117]	Five band DE features extracted from 1 s EEG segments	Multi source transfer with source selection, style transfer mapping between source and target EEG distributions, and source model integration, semi supervised variant exploits target test data transductively	SEED; low resource cross subject transfer	MS-S-STM: 88.92; MS-Semi-STM: 91.31
Wasserstein multi source adaptation	Luo and Lu [219]	EEG feature representations extracted separately from multiple source subjects and the target subject	wMADA β with a shared feature extractor, source specific Wasserstein domain discriminators, and a common discriminator for multi source alignment	SEED, unsupervised cross subject adaptation	89.30 ± 4.00
Domain adaptive few shot learning	Ning et al. [220]	DE features from EEG channels spatially reorganized for convolutional representation learning	Few shot transfer combining deep feature extraction, MMD source and target alignment, attention mechanisms, and prototype based target classification	SEED and DEAP; five target samples per emotion category	SEED: 96.51 ± 1.49; DEAP: 64.55 ± 6.65
Few label adversarial adaptation	Wang et al. [221]	EEG representations from selected source subjects plus a small labeled calibration subset from the target subject	FLADA with source selection, six group adversarial source and target alignment, shared feature extraction, and classifier aggregation	SEED and DEAP; low resource cross subject transfer	SEED: 89.32 ± 0.86; DEAP: 68.00 ± 0.05
Prototypical pairwise transfer	Zhou et al. [122]	EEG feature representations from SEED and SEED-IV used to construct class prototypes and pairwise relationships	PR-PL aligning source and target representations through prototypical learning and adaptive pseudo label based pairwise learning	SEED and SEED-IV; cross subject and cross session cross subject transfer	Session one cross subject: SEED 93.06 ± 5.12, SEED-IV 81.32 ± 8.53; cross session cross subject: SEED 85.56 ± 4.78, SEED-IV 74.92 ± 7.92
Pre trained cross dataset transfer	Wang et al. [140]	EEG representations from emotionally sensitive source subjects across SEED, SEED-IV, DEAP, and FACED	PESD pre trains a Vision Transformer encoder on emotion sensitive source data and transfers it using Mixup, triplet loss, and a domain discriminator	SEED, SEED-IV, DEAP, and FACED; cross dataset transfer	SEED: 93.14; SEED-IV: 83.18; DEAP: 93.53; FACED: 92.55
Two discriminator adversarial transfer	Liu et al. [222]	310 D five band DE vectors (62 channels $\times$ 5 bands) extracted from 0.5 s EEG segments	TD-DANN with adaptive graph convolution, a source and target domain discriminator, and an individual discriminator for domain invariant and subject adaptive representations	SEED and SEED-IV; cross subject domain adversarial transfer	SEED: 89.45 ± 5.87; SEED-IV: 77.13 ± 7.97
Adaptive graph domain adaptation	Luo et al. [223]	DE features used to construct adaptive EEG graphs and dynamic frequency and spatial representations	AGCDAN with multi branch source/target feature extraction, discriminator free marginal alignment, subdomain metric learning for conditional alignment, and decision fusion	SEED, SEED-IV, and DEAP; multi source cross subject domain adaptation	SEED: 89.68; SEED-IV: 68.61; DEAP: 68.13
Flexible source aggregation	Ran et al. [224]	Multi source EEG representations dynamically aggregated according to source and target distribution similarity	FSA-Net with similarity based source aggregation, global MMD alignment, local MMD plus contrastive subdomain adaptation, and domain aware weighted ensemble prediction	SEED and SEED-IV; cross subject domain adaptation	SEED: 90.80; SEED-IV: 82.74

for SEED→DEAP and 67.44% for DEAP→SEED despite explicitly addressing target reliability. This gap demonstrates that cross dataset transfer introduces additional mismatch from acquisition systems, subject populations, stimulus paradigms, and dataset construction. The 2026 HEAT framework reports 95.37% on SEED and 82.50% on SEED-IV by combining global and class conditional alignment with progressively selected pseudo labels [218]. Numerically, these reported within dataset cross subject results exceed the corresponding DFF-Net results on SEED and are slightly higher on SEED IV, although they should not be equated with cross dataset adaptation because the target domain discrepancy is fundamentally different. Overall, the experimental evidence indicates that increasingly fine grained alignment can substantially improve unseen subject recognition, whereas robust transfer across entirely different datasets remains the more demanding generalization problem.

4.2.4 | Brain Region, Channels and Frequency Band Importance

Emotion-related EEG activity is distributed across multiple cortical regions, electrodes, and frequency bands, reflecting interactions within broader neural networks rather than isolated activity. As illustrated in Fig. 10, frontal regions contribute to emotional evaluation and regulation, temporal regions support sensory and memory-related processing, and parietal and occipital regions participate in attentional and visual processing. Subcortical structures, including the amygdala, hippocampus, thalamus, and hypothalamus, further contribute to affective salience, contextual memory, neural communication, and autonomic regulation. However, emotional states emerge from coordinated interactions across these structures rather than anatomically isolated emotion-specific centers [225].




FIGURE 10 | Anatomical overview of major brain regions associated with emotional processing, illustrating the frontal, parietal, temporal, and occipital lobes alongside subcortical structures, including the amygdala, hippocampus, thalamus, and hypothalamus, as well as the cerebellum and brainstem.

Understanding these distributed processes is essential for EEG-based emotion recognition because scalp EEG captures temporal, spectral, and spatial patterns associated with cortical neural activity. Nevertheless, its limited spatial specificity prevents reliable isolation of individual subcortical structures, requiring cautious anatomical interpretation [226]. Identifying informative electrodes, brain regions, and frequency components can improve computational efficiency and physiological interpretability. However, their relevance varies across subjects and recording conditions, making fixed channel or band selection potentially restrictive, particularly in subject-independent recognition [227]. As summarized in Table 11, earlier studies emphasized frontal, temporal, and parietal activity alongside informative alpha, beta, and gamma rhythms. Recent approaches increasingly employ adaptive graph construction, channel attention, brain-region priors, and frequency-aware learning to capture complementary spatial–spectral relationships [229, 228]. Collectively, these findings support adaptive multiregional and multiband representations that preserve neurophysiological relevance while accommodating inter-subject variability and reducing redundant information.

5 | Discussion

The literature reviewed in this work shows that EEG based emotion recognition has progressed from conventional feature engineering pipelines toward increasingly sophisticated representation learning frameworks that model spatial, spectral, temporal, and inter channel dependencies. Nevertheless, improvements in reported classification accuracy do not translate directly into equivalent improvements in real world reliability. The central issue is that EEG emotion recognition is simultaneously a representation learning problem and a generalization problem: a model must identify affect related neural patterns while remaining robust to differences in participants, recording sessions, devices, experimental protocols, and environmental conditions. Recent systematic evidence likewise shows a persistent performance advantage for subject dependent evaluation over subject independent testing, indicating that individual variability remains a major obstacle to generalized affective decoding [230, 231].
This distinction is particularly important when interpreting the comparative results summarized in Tables 8 and 9. Subject dependent models can exploit stable participant specific characteristics and therefore provide an important upper bound perspective on personalized recognition. Subject independent evaluation imposes a substantially more demanding requirement because the test participant is absent from model development, whereas transfer learning and domain adaptation approaches occupy an intermediate position in which information from source subjects is explicitly adapted to a new target domain. Consequently, reported accuracies should not be ranked without considering the associated subject partition, target data access, label configuration, session structure, and validation protocol. From this perspective, methodological progress should increasingly be judged not only by peak accuracy but also by robustness, calibration burden, computational feasibility, and the degree to which performance persists under realistic distribution shifts.

5.1 | Practical Implications and Real-World Applications

The practical importance of EEG emotion recognition arises from its capacity to introduce neurophysiological information into

TABLE 11 | Representative transfer-learning evaluations for EEG-based emotion recognition under the original experimental settings of each method. A = arousal and V = valence.

Study	Method	Dataset / Setting	Brain Region and Channel Findings	Frequency Findings	Key Observation
Nakisa et al. [99]	Evolutionary feature and channel selection	DEAP, MAHNOB, mobile EEG	Emotion related information was concentrated in selected rather than uniformly distributed electrodes. Prefrontal and parietal locations were prominent in DEAP, whereas central activity also contributed strongly in MAHNOB. Selected DEAP channels included Fp1, F7, FC5, AF4, CP6, PO4, O2, T7, and T8.	α and γ were prominent in DEAP, while α, β, and γ contributed substantially in MAHNOB.	Spatial and spectral subsets differed across datasets, indicating that compact EEG configurations can preserve useful affective information without relying on the complete montage.
Kannadasan et al. [100]	Differential evolution based feature selection	DEAP; subject independent	Valence related features were concentrated mainly over frontal and parietal areas. Arousal additionally involved frontal and central electrodes. The selected channels differed between the two affective dimensions.	α and β contributed strongly to valence, whereas θ, α, and β were informative for arousal.	The study reported subject independent accuracies of 73.60% for valence and 74.23% for arousal, illustrating task dependent channel and band relevance.
Yang et al. [227]	Learnable channel weighting and core graph extraction	SEED	Channel importance was learned directly rather than predetermined anatomically. The model identified a compact emotion relevant network by weighting EEG channels and pruning less useful nodes and graph connections.	The work primarily addressed spatial channel importance rather than establishing a universal frequency band ranking.	The method represents a transition from manually selected electrode subsets toward data driven discovery of task relevant EEG networks.
Valderrama & Sheoran [50]	Spatial and temporal attention	SEED, SEED-IV, SEED-V; subject independent	Repeatedly influential electrodes included Fp1/Fp2, F7/F8, T7/T8, P7/P8, and O1/O2. Their distribution indicates that emotion discriminative activity extends across frontal, temporal, parietal, and occipital regions.	The analysis concentrated mainly on spatial channel relevance rather than identifying a single dominant spectral band.	Mean subject independent accuracies were 79.3%, 69.5%, and 60.7% for SEED, SEED-IV, and SEED-V, respectively.
Xu et al. [228]	Frequency aware self attention and uncertainty aware contrastive learning	SEED, DEAP, DREAMER, FACED	Multichannel EEG information was retained instead of selecting a fixed universal electrode subset.	Frequency aware attention operates on real and imaginary frequency domain components.	Reported accuracies reached 94.88%, 98.71%, 96.91%, and 99.29% on SEED, DEAP, DREAMER, and FACED, respectively.

TABLE 11 | Representative findings on brain region, channel, connectivity, and frequency band importance in EEG based emotion recognition.

Study	Method	Dataset / Setting	Brain Region and Channel Findings	Frequency Findings	Key Observation
Lin et al. [229]	Brain region knowledge and dual stream Transformer	SEED, SEED-IV	Electrodes were organized according to cortical regions instead of being treated as unrelated channels. Regional visualization indicated particularly useful information from temporal areas.	Temporal, spectral, and spatial representations were jointly modeled rather than selecting one predefined EEG rhythm.	The regional representation reduces dependence on exact electrode position and achieved 97.81% on SEED and 90.76% on SEED-IV.
Li et al. [198]	Self organized graph neural network	SEED, SEED-IV; cross subject	Learned graph structures emphasized frontal, temporal, central, and parietal locations. Nodes around FP2, F7, Cz, and CPz were among the informative areas, while inter electrode relationships were generated adaptively for different EEG samples.	Among individually investigated rhythms, θ showed particularly useful discrimination, with β and γ also contributing.	Adaptive graph construction achieved 86.81% on SEED and 75.27% on SEED-IV, supporting dynamic rather than fixed spatial connectivity.
Ma et al. [61]	Spatial frequency shifted window attention	SEED, SEED-IV	Electrode topology was retained when EEG features were transformed into spatial frequency maps. Local and global relationships among electrode locations were learned through shifted window attention.	Multiple frequency domain differential entropy components were jointly embedded instead of being evaluated as isolated bands.	Joint spatial frequency modeling reported average accuracies of 99.46% on SEED and 95.41% on SEED-IV.
Hua et al. [179]	Brain region constrained attention	DEAP, DREAMER; subject dependent and LOSO	Electrodes were partitioned into anatomically meaningful regions. Attention was constrained mainly within corresponding brain regions, limiting physiologically implausible global interactions.	A spectral spatial branch was combined with region constrained spatiotemporal modeling, allowing spectral and spatial information to complement each other.	The architecture illustrates a recent trend toward combining learned attention with explicit neuroanatomical constraints for improved interpretability.

adaptive human computer and brain computer interaction. Unlike interfaces that rely exclusively on explicit commands, EEG informed systems can potentially infer changes in affective or cognitive state and use this information to modify system behavior. This capability is relevant to adaptive interfaces, assistive technologies, interactive environments, and multimodal affective systems in which EEG is combined with behavioral or physiological modalities. Reviews of EEG based BCI applications and multimodal emotion recognition systems consequently position affect sensitive neural interfaces as an important component of future context aware interaction, while also emphasizing that successful deployment depends on usability, portability, and robust operation outside tightly controlled laboratory settings [232].

The same technological foundation has implications for safety and learning environments. EEG has been investigated for continuous fatigue estimation in driving, where wearable acquisition can support the detection of physiological changes associated with declining alertness, the E-Key framework, for example, demonstrates the feasibility of integrating wearable EEG with fatigue monitoring and subject identification within a unified

system [233]. In educational environments, EEG based attention feedback has also been explored as a means of providing real time neurofeedback during learning tasks [234]. These examples should not be interpreted as evidence that emotion classifiers can be transferred directly to fatigue or attention without retraining. Rather, they illustrate a broader practical implication: advances in portable EEG acquisition, low latency preprocessing, representation learning, and individualized calibration developed for affective computing can contribute to a wider family of neuroadaptive systems.

Healthcare and personalized digital environments represent another important direction, although the clinical implications require especially cautious interpretation. EEG contains information relevant to functional brain organization, and systematic evidence has identified altered EEG connectivity patterns in depression, supporting continued investigation of EEG as a complementary neurophysiological measure rather than as a stand alone diagnostic instrument [2]. At the same time, virtual reality interventions are increasingly studied in mental health contexts, creating opportunities for closed loop systems in which EEG derived affective information could eventually help select or adapt immersive stimuli [235]. EEG derived information has also been explored in recommendation systems, including neuro recommendation approaches that use brain responses to support personalized product selection [236]. Together with the expanding use of EEG in immersive virtual environments [237], these applications suggest that the long term value of emotion recognition may lie less in assigning an isolated emotion label and more in enabling adaptive systems that respond continuously to changes in the user's internal state.

The practical significance of the field therefore depends on a transition from benchmark oriented classification toward reliable affect aware interaction. Such a transition requires models that preserve performance across individuals and contexts, operate with acceptable computational latency, tolerate imperfect wearable recordings, and provide outputs whose uncertainty can be interpreted by downstream systems. High within dataset accuracy remains scientifically useful, but the more consequential question is whether an affective model can support a safe and meaningful decision when the user, recording environment, or acquisition hardware differs from the conditions under which the model was developed.

5.2 | Key Challenges and Future Research Directions

Despite substantial methodological progress, several limitations continue to restrict the generalizability and translational value of EEG emotion recognition. These limitations are interconnected rather than independent. Restricted datasets encourage model overfitting, overfitting can inflate subject dependent results, inter subject variability reduces generalized performance, and poor generalization increases the amount of calibration required before deployment. Meanwhile, practical systems introduce additional sources of noise, latency, and user variability that are typically absent from benchmark experiments. A productive future research agenda should therefore address dataset design, personalized modeling, generalized modeling, and deployment requirements as components of a single validation pipeline rather than as separate research problems.

5.2.1 | Dataset Diversity, Annotation, and Standardization

Dataset design remains one of the most fundamental constraints on progress. Existing EEG emotion recognition research is concentrated around a relatively small number of benchmark datasets, and systematic reviews show that DEAP and SEED account for a disproportionately large share of experimental studies [231]. Although this concentration facilitates methodological comparison, it can also encourage optimization toward the statistical properties of a few established benchmarks. Many datasets were acquired using controlled laboratory elicitation, modest participant populations, fixed stimulus sets, specific electrode montages, and a limited number of emotion categories. Such conditions are valuable for experimental control but do not fully represent the variability expected in naturalistic affective states, where emotion intensity, mixed emotions, contextual factors, and spontaneous transitions are substantially more difficult to standardize.

A related challenge is heterogeneity across databases. Differences in sampling rate, electrode density, reference configuration, preprocessing, stimulus duration, segmentation strategy, emotional annotation, and class definition complicate direct cross dataset comparison. Reviews of automated EEG emotion recognition repeatedly identify variability in datasets, preprocessing, feature extraction, and evaluation methodology as barriers to reproducibility and broader generalization [14]. Future datasets should therefore place greater emphasis on transparent metadata, standardized reporting of acquisition and preprocessing parameters, subject wise split definitions, repeated session recordings, and demographically broader cohorts. Multi site and longitudinal acquisition would be particularly useful for separating emotion related neural information from participant , session , and device specific variation.

Future dataset development should also reconsider how emotional ground truth is represented. Restricting affect to a small set of discrete labels or binary high/low dimensions simplifies classification but may conceal transitional, ambiguous, or mixed emotional states. More fine grained labels, confidence or intensity measures, repeated self assessment, and combinations of dimensional and categorical annotations could provide richer supervision. Naturalistic and immersive elicitation paradigms may further help bridge the gap between laboratory stimuli and real world affect, provided that the increased ecological validity is accompanied by careful control of movement, sensory load, and recording artifacts. The objective should therefore not be to maximize dataset size alone, but to increase the diversity of subjects, sessions, contexts, and emotional conditions in a way that meaningfully tests generalization.

5.2.2 | Subject-Specific Modeling and Personalization

Subject dependent modeling remains valuable because it can exploit stable electrophysiological characteristics that are specific to an individual. As shown in Table 8, many modern architectures obtain strong within subject performance by combining spatial topology, frequency domain information, temporal dependencies, graph representations, or attention mechanisms. Such results demonstrate that emotional information can be extracted effectively when the model is allowed to learn participant specific

distributions. However, they primarily characterize personalized recognition and should not be interpreted as equivalent evidence of performance for previously unseen users.

A central methodological difficulty is that the quantity of data available for a single participant is usually limited relative to the capacity of contemporary deep networks. Increasing architectural complexity can therefore improve feature extraction while simultaneously increasing susceptibility to participant specific overfitting. Future subject specific systems should emphasize efficient personalization rather than unrestricted model complexity. Promising directions include compact hybrid architectures that integrate complementary spatial, spectral, and temporal representations, parameter efficient adaptation, representation pretraining followed by limited personalization, and explicit regularization of highly expressive attention or graph modules. More generally, systematic evidence suggests that multimodal and feature fusion strategies can provide complementary information, but the resulting models must be evaluated against their additional computational and data requirements rather than accuracy alone [230].

Personalized modeling should also incorporate temporal stability as an explicit evaluation criterion. A model trained and evaluated within one recording session may perform well while remaining sensitive to electrode placement, impedance, mood baseline, fatigue, or physiological changes on another day. Repeated session validation is therefore necessary to determine whether a "subject specific" model represents enduring affective characteristics or merely session specific signal structure. Future personalized systems would benefit from calibration procedures that update only the components required to accommodate session drift while retaining previously learned affective representations, thereby reducing the amount of new labeled EEG required for each use.

5.2.3 | Generalization Across Domains

Generalized emotion recognition is more difficult because EEG distributions can vary substantially between individuals. Differences in anatomy, scalp conductivity, electrode contact, baseline oscillatory activity, cognitive appraisal, emotional regulation, and stimulus interpretation can all alter the observed signal without necessarily implying a different affective state. Consequently, a feature that is discriminative within one participant may be unstable when applied to another. Reviews of EEG emotion recognition systems consistently identify this inter individual variability as a principal reason why subject independent performance remains below subject dependent performance across many benchmark settings. This generalization gap is particularly important because practical systems cannot usually assume that a fully personalized model and a large labeled calibration dataset will be available for every new user.

Future work should therefore distinguish clearly between different forms of generalization. Pure subject independent evaluation should retain complete separation between training and test participants and should not be conflated with algorithms that access target subject data during adaptation. Unsupervised domain adaptation may use unlabeled target data, semi supervised adaptation may use limited labeled calibration, and domain generalization methods attempt to operate without target domain access. Cross session and cross dataset experiments introduce additional levels of distribution shift. Reporting these settings separately, as in Table 9, is essential because they answer different scientific questions.

The next stage of generalized modeling should move beyond optimizing a single benchmark split toward hierarchical stress testing. A model may first be evaluated using leave one subject out validation, then across sessions, acquisition devices, electrode subsets, and ultimately independent datasets. Transfer learning, domain adaptation, invariant representation learning, and source free adaptation can then be assessed according to how much target information they require and whether adaptation remains stable when source and target distributions differ substantially. Collaborative approaches such as federated or privacy preserving learning may also become valuable when multi institutional EEG data cannot be centralized. Importantly, generalized models should report not only overall accuracy but also class balanced measures, variability across held out participants, and failure cases, an improvement in mean performance has limited practical value if recognition becomes unreliable for a substantial subset of users.

5.2.4 | Real-World Deployment, Safety, and Ethical Considerations

Real world deployment introduces constraints that are largely absent from offline benchmark studies. Wearable EEG systems must contend with movement artifacts, changing electrode contact, environmental electrical noise, limited channel counts, setup time, user comfort, computational latency, and battery or hardware limitations. These factors interact directly with algorithm design: models that depend on dense electrode arrays, lengthy preprocessing, or repeated calibration may be unsuitable even if they achieve high laboratory accuracy. Reviews of EEG based BCI applications therefore emphasize portability and practical usability as central requirements for broader adoption [232]. Immersive environments introduce additional challenges because head and body movement, visually complex stimuli, and the interaction between EEG hardware and head mounted displays can alter recording conditions, the EEG VR literature consequently identifies experimental design and technical integration as continuing areas for improvement [237].

Deployment also raises questions that cannot be resolved by classification performance alone. An affect sensitive system may influence recommendations, educational feedback, safety alerts, or therapeutic content, meaning that erroneous predictions can alter the user's experience or subsequent behavior. Models should therefore communicate uncertainty, avoid presenting probabilistic affect estimates as definitive psychological judgments, and include mechanisms for user control and disengagement. These concerns become especially important in mental health applications. Although VR based psychological interventions have shown promise across several conditions, the evidence remains heterogeneous and further clinical validation is required before such systems can be treated as established therapeutic replacements [235]. EEG emotion recognition should accordingly be positioned as a complementary sensing technology within professionally validated clinical workflows rather than as an autonomous diagnostic authority.

Privacy and ethical governance will become increasingly important as affective BCIs move toward continuous or personalized

use. EEG contains information beyond the specific emotion label targeted by a classifier, and persistent neural data therefore require strong safeguards for consent, storage, transmission, secondary use, and model updating. Application oriented research should incorporate these considerations during system design rather than after model development. Real time validation should also evaluate how systems behave when signals are noisy, when confidence is low, and when users intentionally disengage. These requirements favor models that are not merely accurate, but also computationally efficient, interpretable at an appropriate level, uncertainty aware, and capable of failing safely.

Overall, the future of EEG based emotion recognition depends less on incremental improvements to benchmark accuracy than on closing the gap between controlled experimental performance and dependable use across people, sessions, devices, and environments. Larger and more representative datasets, carefully separated evaluation protocols, efficient personalized models, stronger cross subject generalization, and application aware validation should therefore be pursued jointly. Progress along these dimensions would shift the field from demonstrating that emotional information can be decoded from EEG toward establishing when, for whom, and under what conditions such decoding is sufficiently robust to support meaningful real world decisions.

6 | Conclusion

The presented review offers an integrated analysis of emotion recognition based on EEG, uniting the psychological and neurophysiological background of emotions with the process of experimental design, EEG recording, signal processing, feature extraction, classification and evaluation. In contrast to method-focused reviews, this work discusses the impact of all these aspects and their interaction on the performance of emotion recognition, its reliability and generalization. Traditional approaches and deep learning techniques, data augmentation, transfer learning and domain adaptation are considered in terms of their importance for dealing with data scarcity and variability of different subjects. Special attention is paid to the difference between subject-dependent recognition performance and generalization to new subjects and datasets. Reproducibility of experiments and evaluation methods are discussed, as well. Such a perspective allows understanding the existing trade-offs in methodology and limitations of EEG-based emotion recognition. Future work should be concentrated on the development of evaluation protocols, cross subject and cross dataset generalization and computationally efficient methods.

References

1. Anam Moin, Farhan Aadil, Zeeshan Ali, and Dongwann Kang. Emotion recognition framework using multiple modalities for an effective human–computer interaction. *The Journal of Supercomputing*, 79(8):9320–9349, 2023. doi: 10.1007/s11227-022-05026-w.
2. Aleksandra Miljevic, Neil W. Bailey, Oscar W. Murphy, M. Prabhavi N. Perera, and Paul B. Fitzgerald. Alterations in EEG functional connectivity in individuals with depression: A systematic review. *Journal of Affective Disorders*, 328:287–302, 2023. doi: 10.1016/j.jad.2023.01.126.
3. X. Gu, Z. Cao, A. Jolfaei, and F. R. Yu. Eeg-based brain–computer interfaces: A survey of sensing technologies and computational intelligence approaches. *IEEE Computational Intelligence Magazine*, 16(3):62–80, 2021. doi: 10.1109/MCI.2021.3079185.
4. X. Li, D. Song, and B. Hu. Exploring eeg features in cross-subject emotion recognition. *Frontiers in Neuroscience*, 12:294333, 2018.
5. Weizhi Ma, Yujia Zheng, Tianhao Li, Zhengping Li, Ying Li, and Lijun Wang. A comprehensive review of deep learning in eeg-based emotion recognition: classifications, trends, and practical implications. *PeerJ Computer Science*, 10:e2065, 2024. doi: 10.7717/peerj-cs.2065.
6. N. Kukhilava et al. Evaluation in eeg emotion recognition: State-of-the-art review and unified framework. *arXiv preprint arXiv:2505.18175*, 2025.
7. Stamos Katsigiannis and Naeem Ramzan. Dreamer: A database for emotion recognition through eeg and ecg signals from wireless low-cost off-the-shelf devices. *IEEE Journal of Biomedical and Health Informatics*, 2018.
8. C. Li, X. Lin, Y. Liu, et al. Eeg-based emotion recognition via efficient convolutional neural network and contrastive learning. *IEEE Sensors Journal*, 22(20):19608–19619, 2022. doi: 10.1109/JSEN.2022.3202209.
9. Y. Yang, Q. Wu, M. Qiu, et al. Emotion recognition from multi-channel eeg through parallel convolutional recurrent neural network. In *International Joint Conference on Neural Networks (IJCNN)*, pages 1–7. IEEE, 2018.
10. Peixiang Zhong, Di Wang, and Chunyan Miao. Eeg-based emotion recognition using regularized graph neural networks. *IEEE Transactions on Affective Computing*, 13(3):1290–1301, 2020.
11. Xiang Li, Yazhou Zhang, Prayag Tiwari, Dawei Song, Bin Hu, Meihong Yang, Zhigang Zhao, Neeraj Kumar, and Pekka Marttinen. Eeg based emotion recognition: A tutorial and review. *ACM Computing Surveys*, 55(4):1–57, 2022. doi: 10.1145/3524499.
12. Yuxiao Geng, Shuo Shi, and Xiaoke Hao. Deep learning-based eeg emotion recognition: A systematic review. *Neural Computing and Applications*, 37:1919–1950, 2025. doi: 10.1007/s00521-024-10821-y.
13. R. Jafari, H. Seifi, and H. Behnam. Deep learning approaches for eeg-based emotion recognition: A comprehensive review. *Biomedical Signal Processing and Control*, 82:104603, 2023.
14. R. Vempati and L. D. Sharma. A systematic review on automated human emotion recognition using electroencephalogram signals and artificial intelligence. *Results in Engineering*, 18:101027, 2023. doi: 10.1016/j.rineng.2023.101027.
15. K. Erat, E. B. Şahin, et al. Emotion recognition with eeg-based brain–computer interfaces: A systematic literature review. *Multimedia Tools and Applications*, 2024. doi: 10.1007/s11042-024-18259-z.
16. Yiming Wang, Bin Zhang, and Lamei Di. Research progress of EEG-based emotion recognition: A survey. *ACM Computing Surveys*, 56(11):1–49, 2024. doi: 10.1145/3666002.
17. Y. Chen et al. A comprehensive review of deep learning in eeg-based emotion recognition: classifications, trends, and practical implications. *Applied Soft Computing*, 180:113478, 2025. doi: 10.1016/j.asoc.2025.113478.
18. Weizhi Ma et al. A review of eeg-based emotion recognition techniques with a subject-dependent/independent framework. *PeerJ Computer Science*, 2024. doi: 10.7717/peerj-cs.2065.
19. Wei Li, Wei Huan, Bowen Hou, Ye Tian, Zhen Zhang, and Aiguo Song. Can emotion be transferred?—a review on transfer learning for EEG-based emotion recognition. *IEEE Transactions on Cognitive and Developmental Systems*, 14(3):833–846, 2022. doi: 10.1109/TCDS.2021.3098842.
20. H. A. Hamzah and K. K. Abdalla. Eeg-based emotion recognition systems: Comprehensive study. *Heliyon*, 10(10):e31485, 2024.
21. S. M. Alarcao and M. J. Fonseca. Emotions recognition using eeg signals: A survey. *IEEE Transactions on Affective*

Computing, 10(3):374–393, 2019.
22. Y. Roy, H. Banville, I. Albuquerque, et al. Deep learning based electroencephalography analysis: A systematic review. *Journal of Neural Engineering*, 16(5):051001, 2019.
23. Soheil Rayatdoost, David Rudrauf, and Mohammad Soleymani. Expression-guided EEG representation learning for emotion recognition. In *Proceedings of the ICASSP 2020–2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3222–3226. IEEE, 2020.
24. Soheil Rayatdoost and Mohammad Soleymani. Cross-corpus eeg-based emotion recognition. In *Proceedings of the 2018 IEEE 28th International Workshop on Machine Learning for Signal Processing (MLSP)*, pages 1–6. IEEE, 2018.
25. Xinke Shen, Xianggen Liu, Xin Hu, Dan Zhang, and Sen Song. Contrastive learning of subject-invariant EEG representations for cross-subject emotion recognition. *IEEE Transactions on Affective Computing*, 14:2496–2511, 2022.
26. Jinhao Zhang, Yanrong Hao, Xin Wen, Chenchen Zhang, Haojie Deng, Juanjuan Zhao, and Rui Cao. Subject-independent emotion recognition based on eeg frequency band features and self-adaptive graph construction. *Brain Sciences*, 14(3):271, 2024. doi: 10.3390/brainsci14030271.
27. D. Dadebayev, W. B. Goh, and E. C. Tan. Commercial eeg devices for emotion recognition: Opportunities and challenges. *Sensors*, 22(5):1945, 2022.
28. N. S. Suhaimi, J. Mountstephens, and J. Teo. Eeg-based emotion recognition: A state-of-the-art review of current trends and opportunities. *Computational Intelligence and Neuroscience*, 2020.
29. Y. Zhang, G. Yan, W. Chang, et al. Eeg-based multi-frequency band functional connectivity analysis and the application of spatio-temporal features in emotion recognition. *Biomedical Signal Processing and Control*, 79:104157, 2023.
30. Manuela Costa, Diego Lozano-Soldevilla, Antonio Gil-Nagel, Rafael Toledano, Carina R. Oehrn, Lukas Kunz, Mar Yebra, Costantino Mendez-Bertolo, Lennart Stieglitz, Johannes Sarnthein, Nikolai Axmacher, Stephan Moratti, and Bryan A. Strange. Aversive memory formation in humans involves an amygdala-hippocampus phase code. *Nature Communications*, 13:6403, 2022. doi: 10.1038/s41467-022-33828-2.
31. Mohammad Soleymani, David Garcia, Bryan Jou, Björn Schuller, Shih-Fu Chang, and Maja Pantic. A survey of multimodal sentiment analysis. *Image and Vision Computing*, 65: 3–14, 2017.
32. Tadas Baltrušaitis, Louis-Philippe Morency, and Chaitanya Ahuja. Multimodal machine learning. *Communications of the ACM*, 62(5):64–73, 2019.
33. Tadas Baltrušaitis, Chaitanya Ahuja, and Louis-Philippe Morency. Multimodal machine learning: A survey and taxonomy. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(2):423–443, 2018.
34. H. Liu et al. Eeg-based multimodal emotion recognition: A machine learning perspective. *IEEE Transactions on Instrumentation and Measurement*, 2024.
35. Trisha Mittal, Utkarsh Bhattacharya, Rohan Chandra, Aniket Bera, and Dinesh Manocha. M3er: Multiplicative multimodal emotion recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.
36. Soheil Rayatdoost, David Rudrauf, and Mohammad Soleymani. Multimodal gated information fusion for emotion recognition from EEG signals and facial behaviors. In *Proceedings of the 2020 International Conference on Multimodal Interaction*, pages 655–659, 2020.
37. Juan A. M. Correa, Mojtaba K. Abadi, Nicu Sebe, and Ioannis Patras. Amigos: A dataset for affect, personality and mood research. *IEEE Transactions on Affective Computing*, 12(2): 479–493, 2018.
38. Qiuyu Chen, Xiaoqian Mao, Yuebin Song, and Kefa Wang. An eeg-based emotion recognition method by fusing multi-frequency-spatial features under multi-frequency bands. *Journal of Neuroscience Methods*, 415:110360, 2025. doi: 10.1016/j.jneumeth.2025.110360.
39. Ming Sun, Wei Cui, Shun Yu, Hao Han, Bin Hu, and Yijun Li. A dual-branch dynamic graph convolution based adaptive transformer feature fusion network for EEG emotion recognition. *IEEE Transactions on Affective Computing*, 13(4):2218–2228, 2022. doi: 10.1109/TAFFC.2022.3199075.
40. W. Y. Choong, W. Khairunizam, W. A. Mustafa, et al. Correlation analysis of emotional eeg in alpha, beta and gamma frequency bands. In *Journal of Physics: Conference Series*, page 012029, 2021.
41. Y. J. Liu, M. Yu, G. Zhao, J. Song, Y. Ge, and Y. Shi. Real-time movie-induced discrete emotion recognition from eeg signals. *IEEE Transactions on Affective Computing*, 9(4):550–562, 2018. doi: 10.1109/TAFFC.2017.2660485.
42. C. Qing, R. Qiao, X. Xu, and Y. Cheng. Interpretable emotion recognition using eeg signals. *IEEE Access*, 7:94160–94170, 2019. doi: 10.1109/ACCESS.2019.2928691.
43. Javier Fdez, Nicholas Guttenberg, Olaf Witkowski, and Antoine Pasquali. Cross-subject EEG-based emotion recognition through neural networks with stratified normalization. *Frontiers in Neuroscience*, 15:626277, 2021. doi: 10.3389/fnins.2021.626277.
44. Yiming Wang, Bin Zhang, and Yujiao Tang. Dmmr: Cross-subject domain generalization for eeg-based emotion recognition via denoising mixed mutual reconstruction. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(1):628–636, 2024. doi: 10.1609/aaai.v38i1.27819.
45. Bart Somers, Tom Francart, and Alexander Bertrand. A generic EEG artifact removal algorithm based on the multi-channel Wiener filter. *Journal of Neural Engineering*, 15(3):036007, 2018. doi: 10.1088/1741-2552/aaac92.
46. Mikel Val-Calvo, José R. Álvarez-Sánchez, Jose M. Ferrández-Vicente, and Eduardo Fernández. Optimization of real-time EEG artifact removal and emotion estimation for human-robot interaction applications. *Frontiers in Computational Neuroscience*, 13:80, 2019. doi: 10.3389/fncom.2019.00080.
47. A. D. Bigirimana, N. Siddique, and D. Coyle. A hybrid ica-wavelet transform for automated artefact removal in eeg-based emotion recognition. In *Proc. IEEE Int. Conf. Systems, Man, and Cybernetics (SMC)*, pages 4429–4434, 2016. doi: 10.1109/SMC.2016.7844928.
48. Xiao Jiang, Gui-Bin Bian, and Zean Tian. Removal of artifacts from EEG signals: A review. *Sensors*, 19(5):987, 2019. doi: 10.3390/s19050987.
49. Zhong-Min Wang, Shu-Yuan Hu, and Hui Song. Channel selection method for eeg emotion recognition using normalized mutual information. *IEEE access*, 7:143303–143311, 2019.
50. Camilo E. Valderrama and Anshul Sheoran. Identifying relevant EEG channels for subject-independent emotion recognition using attention network layers. *Frontiers in Psychiatry*, 16: 1494369, 2025. doi: 10.3389/fpsyt.2025.1494369.
51. Zhe Wang, Yongxiong Wang, Chuanfei Hu, Zhong Yin, and Yu Song. Transformers for EEG-based emotion recognition: A hierarchical spatial information learning model. *IEEE Sensors Journal*, 22(5):4359–4368, 2022. doi: 10.1109/JSEN.2022.3144317.
52. Hao-Jie Kang, Pei-Xiang Zhong, Di Wu, Zhe Jiao, Wei-Hua Liu, and Yan-Hui Peng. A novel method for eeg-based emotion recognition using ica and neural network. *IEEE Transactions on Affective Computing*, 13(2):616–627, 2019.
53. Md. Zaved Iqubal Ahmed, Nidul Sinha, Ebrahim Ghaderpour, Souvik Phadikar, and Rajdeep Ghosh. A novel baseline removal paradigm for subject-independent features in emotion classification using eeg. *Bioengineering*, 10(1):54, 2023. doi: 10.3390/bioengineering10010054.

54. C. Y. Sai, N. Mokhtar, H. Arof, P. Cumming, and M. Iwahashi. Automated classification and removal of eeg artifacts with svm and wavelet-ica. *IEEE Journal of Biomedical and Health Informatics*, 2018.
55. M. Dura and A. Wosiak. Eeg channel selection strategy for deep learning in emotion recognition. *Procedia Computer Science*, 192:1765–1774, 2021. doi: 10.1016/j.procs.2021.09.347.
56. Mohamed F. Issa and Zoltan Juhasz. Improved eog artifact removal using wavelet enhanced independent component analysis. *Brain Sciences*, 9(12):355, 2019. doi: 10.3390/brainsci9120355.
57. Di Li, Bo Chai, Zhi Wang, Hao Yang, and Wei Du. EEG emotion recognition based on 3-d feature representation and dilated fully convolutional networks. *IEEE Transactions on Cognitive and Developmental Systems*, 13(4):885–897, 2021. doi: 10.1109/TCDS.2021.3051465.
58. W.-C. L. Lew, Di Wang, Ksenia Shylouskaya, Zhi Zhang, J.-H. Lim, Kai Keng Ang, and Ah-Hwee Tan. EEG-based emotion recognition using spatial-temporal representation via Bi-GRU. In *2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)*, pages 116–119. IEEE, 2020.
59. Jing Sun, Xin Wang, Kai Zhao, Shiqi Hao, and Ting Wang. Multi-channel EEG emotion recognition based on parallel transformer and 3d-convolutional neural network. *Mathematics*, 10(17):3131, 2022. doi: 10.3390/math10173131.
60. Dong-Wei Chen, Rui Miao, Wei-Qi Yang, Yong Liang, Hao-Heng Chen, Lan Huang, Chun-Jian Deng, and Na Han. A feature extraction method based on differential entropy and linear discriminant analysis for emotion recognition. *Sensors*, 19 (7):1631, 2019.
61. Weizhi Ma, Ying Li, Tianhao Li, Haowei Yang, Zhengping Li, Lijun Wang, and Junyu Xuan. SFSWTS: A spatial-frequency shifted windows and time self-attention network for EEG emotion recognition. *Neurocomputing*, 640:130309, 2025. doi: 10.1016/j.neucom.2025.130309.
62. A. Abgeena and S. Garg. S-lstm-att: a hybrid deep learning approach with optimized features for emotion recognition in electroencephalogram. *Health Information Science and Systems*, 11 (1):40, 2023. doi: 10.1007/s13755-023-00242-x.
63. F. Shen, G. Dai, G. Lin, et al. Eeg-based emotion recognition using 4d convolutional recurrent neural network. *Cognitive Neurodynamics*, 14:815–828, 2020.
64. Guixun Xu, Wenhui Guo, and Yanjiang Wang. Subject-independent EEG emotion recognition with hybrid spatio-temporal GRU-Conv architecture. *Medical & Biological Engineering & Computing*, 61(1):61–73, 2023. doi: 10.1007/s11517-022-02686-x.
65. Yang Li, Wei-Long Zheng, and Bao-Liang Lu. A regional-to-global hierarchical spatial–temporal neural network for eeg emotion recognition. *IEEE Transactions on Affective Computing*, 13(5):2330–2342, 2022.
66. Lijun Yang, Yixin Wang, Rujie Ouyang, Xiaolong Niu, Xiaohui Yang, and Chen Zheng. Electroencephalogram-based emotion recognition using factorization temporal separable convolution network. *Engineering Applications of Artificial Intelligence*, 133: 108011, 2024. doi: 10.1016/j.engappai.2024.108011.
67. Rui Li, Yiting Wang, Wei-Long Zheng, and Bao-Liang Lu. A multi-view spectral-spatial-temporal masked autoencoder for decoding emotions with self-supervised learning. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 6–14. Association for Computing Machinery, 2022. doi: 10.1145/3503161.3548243.
68. Yongqiang Yin, Xiangwei Zheng, Bin Hu, Yuang Zhang, and Xinchun Cui. Eeg emotion recognition using fusion model of graph convolutional neural networks and lstm. *Applied Soft Computing*, 100:106954, 2021. doi: 10.1016/j.asoc.2020.106954.
69. Debarshi Nath, Anubhav, Mrigank Singh, Divyashikha Sethia, Diksha Kalra, and Sreedevi Indu. A comparative study of subject-dependent and subject-independent strategies for eeg-based emotion recognition using lstm network. In *Proceedings of the 2020 4th International Conference on Compute and Data Analysis*, pages 142–147. Association for Computing Machinery, 2020. doi: 10.1145/3388142.3388167.
70. Chunyu Zheng, Wenqing Wang, and Jiayi Ma. A multi-channel spectrogram fusion network for eeg-based emotion recognition. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 4938–4947, 2022.
71. Yuchen Song, Qi Zheng, Bo Liu, and Xin Gao. EEG conformer: Convolutional transformer for EEG decoding and visualization. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 31:710–719, 2022.
72. Yang Li, Wei-Long Zheng, and Bao-Liang Lu. A multi-domain adaptive graph convolutional network for eeg emotion recognition. *Proceedings of the 29th ACM International Conference on Multimedia*, pages 2977–2985, 2021.
73. H. Cui, A. Liu, X. Zhang, et al. Eeg-based emotion recognition using an end-to-end regional-asymmetric convolutional neural network. *Knowledge-Based Systems*, 205:106243, 2020.
74. Sunhee Hwang, Kibeom Hong, Guiyoung Son, and Hyeran Byun. Learning CNN features from DE features for EEG-based emotion recognition. *Pattern Analysis and Applications*, 23(3): 1323–1335, 2020. doi: 10.1007/s10044-019-00860-w.
75. Jiyao Liu, Lang He, Haifeng Chen, and Dongmei Jiang. Directional spatial and spectral attention network (DSSA Net) for EEG-based emotion recognition. *Frontiers in Neurorobotics*, 18: 1481746, 2025. doi: 10.3389/fnbot.2024.1481746.
76. Dongyuan Tian, Yucheng Wang, Peiliang Gong, Zhewen Xu, Zhenghua Chen, Xiaohui Wei, and Min Wu. ACCNet: Adaptive cross-frequency coupling graph attention for eeg emotion recognition. *Neural Networks*, 191:107853, 2025. doi: 10.1016/j.neunet.2025.107853.
77. Vipin Gupta, Mayur Dahyabhai Chopda, and Ram Bilas Pachori. Cross-subject emotion recognition using flexible analytic wavelet transform from EEG signals. *IEEE Sensors Journal*, 19(6):2266–2274, 2019. doi: 10.1109/JSEN.2018.2883497.
78. P. Arnau-González, M. Arevalillo-Herráez, and N. Ramzan. Fusing highly dimensional energy and connectivity features to identify affective states from eeg signals. *Neurocomputing*, 244: 81–89, 2017. doi: 10.1016/j.neucom.2017.03.027.
79. Shuaiqi Liu, Zeyao Wang, Yanling An, Bing Li, Xinrui Wang, and Yudong Zhang. DA-CapsNet: A multi-branch capsule network based on adversarial domain adaption for cross-subject EEG emotion recognition. *Knowledge-Based Systems*, 283: 111137, 2024. doi: 10.1016/j.knosys.2023.111137.
80. W. Tao, C. Li, R. Song, et al. Eeg-based emotion recognition via channel-wise attention and self attention. *IEEE Transactions on Affective Computing*, 14(1):382–393, 2020.
81. Y. Zhu, Y. Guo, W. Zhu, et al. Subject-independent emotion recognition of eeg signals using graph attention-based spatial-temporal pattern learning. In *Chinese Control Conference (CCC)*, pages 7070–7075. IEEE, 2022.
82. Haotian Sun, Lei Yang, Qiang Wang, Di Liu, and Peng Ni. MEEG-Transformer: Transformer network based on multi-domain EEG for emotion recognition. In *2023 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 3332–3339. IEEE, 2023.
83. Ziyu Jia, Youfang Lin, Xiyang Cai, Haobin Chen, Haijun Gou, and Jing Wang. Sst-emotionnet: Spatial-spectral-temporal based attention 3d dense network for eeg emotion recognition. In *Proceedings of the 28th ACM International Conference on Multimedia (ACM MM)*, pages 2909–2917, 2020.
84. Anton Yudhana, Akbar Muslim, Dewi Eko Wati, Intan Puspitasari, Ahmad Azhari, and Murein Miksa Mardhia. Human emotion recognition based on eeg signal using fast fourier transform and k-nearest neighbor. *Adv. Sci. Technol. Eng. Syst. J*, 5(6):1082–1088, 2020.

85. Alain Desire Bigirimana, N Siddique, and Damien Coyle. Emotion-inducing imagery versus motor imagery for a brain-computer interface. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 28(4):850–859, 2020.
86. Y.-P. Lin, C.-H. Wang, T.-P. Jung, T.-L. Wu, S.-K. Jeng, J.-R. Duann, and J.-H. Chen. Eeg-based emotion recognition in music listening. *IEEE Transactions on Biomedical Engineering*, 57(7): 1798–1806, 2010. doi: 10.1109/TBME.2010.2048568.
87. R. Jenke, A. Peer, and M. Buss. Feature extraction and selection for emotion recognition from eeg. *IEEE Transactions on Affective Computing*, 5(3):327–339, 2014. doi: 10.1109/TAFFC.2014.2339834.
88. M. Murugappan, R. Nagarajan, and S. Yaacob. Time-frequency analysis of eeg signals for emotion detection. *Expert Systems with Applications*, 37(3):2527–2534, 2010. doi: 10.1016/j.eswa.2009.09.063.
89. R. Gupta and R. B. Pachori. Classification of emotions using eeg signals based on hjorth parameters. *Biomedical Signal Processing and Control*, 52:204–212, 2019. doi: 10.1016/j.bspc.2019.04.004.
90. P. C. Petrantonakis and L. J. Hadjileontiadis. Emotion recognition from eeg using higher order crossings. *IEEE Transactions on Information Technology in Biomedicine*, 14(2):186–197, 2010. doi: 10.1109/TITB.2009.2034649.
91. X. Zhao, L. Zhang, and Y. Xu. Eeg-based emotion recognition using short-time fourier transform. *Biomedical Signal Processing and Control*, 52:194–203, 2019. doi: 10.1016/j.bspc.2019.04.003.
92. A. Subasi and M. I. Gursoy. Eeg signal classification using wavelet feature extraction and a mixture of expert model. *Expert Systems with Applications*, 32(4):1084–1093, 2010. doi: 10.1016/j.eswa.2006.02.005.
93. A. Al-Nafjan, M. Hosny, Y. Al-Ohali, and A. Al-Wabil. Review and classification of emotion recognition based on eeg brain-computer interface system research. *Sensors*, 17(5):1237, 2017. doi: 10.3390/s17051237.
94. J. Li, S. Qiu, C. Du, Y. Wang, and H. He. Domain adaptation for eeg emotion recognition based on feature fusion. *IEEE Access*, 6:40446–40456, 2018. doi: 10.1109/ACCESS.2018.2854720.
95. W.-L. Zheng and B.-L. Lu. Investigating critical frequency bands and channels for eeg-based emotion recognition. *IEEE Transactions on Affective Computing*, 6(1):18–31, 2015. doi: 10.1109/TAFFC.2014.2360251.
96. Y. Zhang, S. Wang, G. Ji, and P. Phillips. Eeg-based emotion recognition using multi-feature fusion and deep neural network. *Knowledge-Based Systems*, 191:105458, 2020. doi: 10.1016/j.knosys.2019.105458.
97. Anirban Chakladar and Debotosh Chakraborty. Emotion recognition from eeg signals using correlation-based feature selection and support vector machine. *Journal of Intelligent & Fuzzy Systems*, 34(3):1579–1589, 2018.
98. Zhong Yin, Lei Liu, Jianing Chen, Boxi Zhao, and Yongxiong Wang. Locally robust EEG feature selection for individual-independent emotion recognition. *Expert Systems with Applications*, 162:113768, 2020. doi: 10.1016/j.eswa.2020.113768.
99. Bahareh Nakisa, Mohammad Naim Rastgoo, Dian Tjondronegoro, and Vinod Chandran. Evolutionary computation algorithms for feature selection of EEG-based emotion recognition using mobile sensors. *Expert Systems with Applications*, 93: 143–155, 2018. doi: 10.1016/j.eswa.2017.09.062.
100. Kalidasan Kannadasan, Sridevi Veerasingam, B. Shameedha Begum, and Natarajan Ramasubramanian. An EEG-based subject-independent emotion recognition model using a differential-evolution-based feature selection algorithm. *Knowledge and Information Systems*, 65(1):341–377, 2023. doi: 10.1007/s10115-022-01762-w.
101. Xue-Yan Xu, Si-Yuan Wu, Wei Liu, Wei-Long Zheng, and Bao-Liang Lu. Feature selection based on orthogonal regression and its application to eeg-based emotion recognition. *Knowledge-Based Systems*, 214:106742, 2021.
102. K. Kannadasan, N. Mariyappa, Saima E. Awan, Mohammad Reza Mohebbian, Hector Alaiz-Moreton, Muhammad A. Naeem, Atif Mehmood, and Muhammad Arif Iqbal. Feature selection by differential evolution based on maximizing classification accuracy and minimizing the difference between the probabilities of inter-class and intra-class. *Knowledge and Information Systems*, 65(1):341–377, 2023.
103. Z.-T. Liu, Q. Xie, M. Wu, et al. Electroencephalogram emotion recognition based on empirical mode decomposition and optimal feature selection. *IEEE Transactions on Cognitive and Developmental Systems*, 11(4):517–526, 2018.
104. J. Shen, H. Zhang, and Y. Xu. Feature selection for eeg emotion recognition using sequential forward selection. *International Journal of Computer Applications*, 3(3):1–6, 2010.
105. Y. Zhang, S. Wang, and P. Phillips. Eeg-based emotion recognition using lasso feature selection. *Neurocomputing*, 174: 1091–1100, 2016. doi: 10.1016/j.neucom.2015.09.079.
106. X. Li, D. Song, P. Zhang, G. Yu, Y. Hou, and B. Hu. Eeg emotion recognition using attention-based deep neural network. *IEEE Access*, 7:111410–111423, 2019. doi: 10.1109/ACCESS.2019.2933312.
107. Yun Luo and Bao-Liang Lu. Eeg data augmentation for emotion recognition using a conditional wasserstein gan. In *Proceedings of the 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, pages 2535–2538. IEEE, 2018.
108. Zhi Zhang, Yan Liu, and Sheng-hua Zhong. Ganser: A self-supervised data augmentation framework for eeg-based emotion recognition. *IEEE Transactions on Affective Computing*, 14 (3):2048–2063, 2023. doi: 10.1109/TAFFC.2022.3170369.
109. M. M. Rahman, A. K. Sarkar, M. A. Hossain, M. S. Hossain, M. R. Islam, M. B. Hossain, J. M. Quinn, and M. A. Moni. Recognition of human emotions using EEG signals: a review. *Computers in Biology and Medicine*, 136:104696, 2021. doi: 10.1016/j.compbiomed.2021.104696.
110. Xiaoliang Zhu, Chen Liu, Liang Zhao, and Shengming Wang. EEG emotion recognition network based on attention and spatiotemporal convolution. *Sensors*, 24(11):3464, 2024. doi: 10.3390/s24113464.
111. Jiaxin Ma, Hao Tang, Wei-Long Zheng, and Bao-Liang Lu. Emotion recognition using multimodal residual LSTM network. In *Proceedings of the 27th ACM International Conference on Multimedia (MM '19)*. Association for Computing Machinery, 2019. doi: 10.1145/3343031.3350871. 8 pages.
112. Yi Ding, Neethu Robinson, Su Zhang, Qiuhao Zeng, and Cuntai Guan. TSception: Capturing temporal dynamics and spatial asymmetry from EEG for emotion recognition. *IEEE Transactions on Affective Computing*, 14:2238–2250, 2023. doi: 10.1109/TAFFC.2022.3169001.
113. Jia-Yi Guo, Qing Cai, Jian-Peng An, Pei-Yin Chen, Chao Ma, Jun-He Wan, and Zhong-Ke Gao. A transformer based neural network for emotion recognition and visualizations of crucial EEG channels. *Physica A: Statistical Mechanics and its Applications*, 603:127700, 2022. doi: 10.1016/j.physa.2022.127700.
114. Ruixiang Liu, Yihu Chao, Xuerui Ma, Xianzheng Sha, Limin Sun, Shuo Li, and Shijie Chang. ERTNet: An interpretable transformer-based framework for EEG emotion recognition. *Frontiers in Neuroscience*, 18, 2024. doi: 10.3389/fnins.2024.1320645. Published: 17 January 2024.
115. Sheeraz Ahmad Khan, Eamin Chaudary, and Wajid Mumtaz. EEG-ConvNet: Convolutional networks for EEG-based subject-dependent emotion recognition. *Computers and Electrical Engineering*, 116:109178, 2024. doi: 10.1016/j.compeleceng.2024.109178.
116. He Li, Yi-Ming Jin, Wei-Long Zheng, and Bao-Liang Lu. Cross-subject emotion recognition using deep adaptation networks. In *Neural Information Processing (ICONIP 2018)*, volume 11305

of *Lecture Notes in Computer Science*, pages 403–413. Springer, Cham, 2018. doi: 10.1007/978-3-030-04221-9_36.
117. Jinpeng Li, Shuang Qiu, Yuan-Yuan Shen, Cheng-Lin Liu, and Huiguang He. Multisource transfer learning for cross-subject eeg emotion recognition. *IEEE Transactions on Cybernetics*, 50 (7):3281–3293, 2020. doi: 10.1109/TCYB.2019.2904052.
118. Liming Zhao, Xu Yan, and Bao-Liang Lu. Plug-and-play domain adaptation for cross-subject EEG-based emotion recognition. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(1):863–870, 2021. URL https://cdn.aaai.org/ojs/16169/16169-13-19663-1-2-20210518.pdf.
119. Jinpeng Li, Shuang Qiu, Changde Du, Yixin Wang, and Huiguang He. Domain adaptation for EEG emotion recognition based on latent representation similarity. *IEEE Transactions on Cognitive and Developmental Systems*, 12(2):344–353, 2020. doi: 10.1109/TCDS.2019.2949306.
120. T. Xu, W. Dang, J. Wang, and Y. Zhou. Dagam: a domain adversarial graph attention model for subject-independent eeg-based emotion recognition. *Journal of Neural Engineering*, 20 (1):016022, 2023. doi: 10.1088/1741-2552/acae06.
121. W. Li, W. Huan, S. Shao, et al. Ms-fran: a novel multi-source domain adaptation method for eeg-based emotion recognition. *IEEE Journal of Biomedical and Health Informatics*, 27(11): 5302–5313, 2023.
122. Rushuang Zhou et al. Pr-pl: A prototypical representation based pairwise learning framework for emotion recognition using eeg signals. *IEEE Transactions on Affective Computing*, 15: 657–670, 2023.
123. Li-Hong Zhang, Yu-Dong Zhang, and Bao-Liang Lu. Parse: A parameter-efficient domain-adaptation model for eeg-based emotion recognition. *IEEE Transactions on Affective Computing*, 13(3):1145–1158, 2022.
124. Kaiyang Zhou, Ziwei Liu, Yu Qiao, Tao Xiang, and Chen Change Loy. Domain generalization: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45 (4):4396–4415, 2022.
125. Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *Journal of Machine Learning Research*, 17(59):1–35, 2016. URL http://jmlr.org/papers/v17/15-239.html.
126. Baochen Sun and Kate Saenko. Deep CORAL: correlation alignment for deep domain adaptation. In *Computer Vision - ECCV 2016 Workshops - Amsterdam, The Netherlands, October 8-10 and 15-16, 2016, Proceedings, Part III*, volume 9915 of *Lecture Notes in Computer Science*, pages 443–450, 2016. doi: 10.1007/978-3-319-49409-8_35.
127. D. Wu, V. J. Lawhern, S. Gordon, and B. J. Lance. A review of transfer learning in eeg-based brain–computer interface. *IEEE Transactions on Human-Machine Systems*, 50(5):386–399, 2020.
128. Z. Wan, R. Yang, M. Huang, et al. Transfer learning for eeg-based brain–computer interfaces: A review. *IEEE Computational Intelligence Magazine*, 16(2):43–56, 2021.
129. Md Niaz Imtiaz and Naimul Khan. Enhanced cross-dataset electroencephalogram-based emotion recognition using unsupervised domain adaptation. *Computers in Biology and Medicine*, 184:109394, 2025. doi: 10.1016/j.compbiomed.2024.109394.
130. Yucel Cimtay and Erhan Ekmekcioglu. Investigating the use of pretrained convolutional neural network on cross-subject and cross-dataset EEG emotion recognition. *Sensors*, 20(7):2034, 2020. doi: 10.3390/s20072034.
131. Guangcheng Bao, Ning Zhuang, Li Tong, Bin Yan, Jun Shu, Linyuan Wang, Ying Zeng, and Zhichong Shen. Two-level domain adaptation neural network for EEG-based emotion recognition. *Frontiers in Human Neuroscience*, 14:605246, 2021. doi: 10.3389/fnhum.2020.605246.
132. Yi-Ming Jin, Yu-Dong Luo, Wei-Long Zheng, and Bao-Liang Lu. EEG-based emotion recognition using domain adaptation network. In *2017 International Conference on Orange Technologies (ICOT)*, pages 222–225. IEEE, 2017. doi: 10.1109/ICOT.2017.8336126.
133. Yun Luo, Si-Yang Zhang, Wei-Long Zheng, and Bao-Liang Lu. WGAN domain adaptation for EEG-based emotion recognition. In *Neural Information Processing (ICONIP 2018)*, volume 11305 of *Lecture Notes in Computer Science*, pages 275–286. Springer, Cham, 2018. doi: 10.1007/978-3-030-04221-9_25.
134. Y. et al. Yang. Spectral-spatial attention alignment for multi-source domain adaptation. *IEEE Transactions on Affective Computing*, 2024.
135. Dongrui Wu, Yifan Xu, and Bao-Liang Lu. Transfer learning for EEG-based brain–computer interfaces: A review of progress made since 2016. *IEEE Transactions on Cognitive and Developmental Systems*, 14(1):4–19, 2022. doi: 10.1109/TCDS.2020.3007453.
136. Y. et al. Peng. Joint feature adaptation and graph adaptive label propagation for cross-subject emotion recognition. *IEEE Transactions on Affective Computing*, 2022.
137. Md Niaz Imtiaz and Naimul Khan. Toward practical emotion recognition: An unsupervised source-free approach for eeg domain adaptation. *IEEE Transactions on Affective Computing*, 17 (3):3506–3520, 2026. doi: 10.1109/TAFFC.2026.3713402.
138. Jie Quan, Ying Li, Lingyue Wang, Renjie He, Shuo Yang, and Lei Guo. EEG-based cross-subject emotion recognition using multi-source domain transfer learning. *Biomedical Signal Processing and Control*, 84:104741, 2023. doi: 10.1016/j.bspc.2023.104741.
139. Wei Lu, Haiyan Liu, Hua Ma, Tien-Ping Tan, and Lingnan Xia. Hybrid transfer learning strategy for cross-subject EEG emotion recognition. *Frontiers in Human Neuroscience*, 17:1280241, 2023. doi: 10.3389/fnhum.2023.1280241.
140. Fang Wang, Yu-Chu Tian, and Xiaobo Zhou. Cross-dataset EEG emotion recognition based on pre-trained vision transformer considering emotional sensitivity diversity. *Expert Systems with Applications*, 279:127348, 2025. doi: 10.1016/j.eswa.2025.127348.
141. S. M. Alarcão and M. J. Fonseca. Emotions recognition using eeg signals: A survey. *IEEE Transactions on Affective Computing*, 2019.
142. W. Li, Z. Zhang, and A. Song. Physiological-signal-based emotion recognition: An odyssey from methodology to philosophy. *Measurement*, 2021.
143. D. Wu, Y. Xu, and B.-L. Lu. Transfer learning for eeg-based brain–computer interfaces: A review of progress made since 2016. *IEEE Transactions on Cognitive and Developmental Systems*, 2020.
144. J. Witteveen, P. Pradhapan, and V. Mihajlović. Comparison of pragmatic and regression approaches for wearable eeg signal quality assessment. *IEEE Journal of Biomedical and Health Informatics*, 2020.
145. P. Li et al. Eeg based emotion recognition by combining functional connectivity network and local activations. *IEEE Transactions on Biomedical Engineering*, 2019.
146. Z.-T. Liu, Q. Xie, M. Wu, et al. Electroencephalogram emotion recognition based on empirical mode decomposition and optimal feature selection. *IEEE Transactions on Cognitive and Developmental Systems*, 2019.
147. T. H. Zhou, W. L. Liang, H. Y. Liu, et al. Wavelet-based emotion recognition using single channel eeg device. *Proceedings of an intelligent computing conference*, 2020.
148. C. Q. Lai, H. Ibrahim, M. Z. Abdullah, et al. Artifacts and noise removal for electroencephalogram (eeg): A literature review. *Proceedings of a biomedical engineering conference*, 2018.
149. S. Phadikar, N. Sinha, and R. Ghosh. Automatic eyeblink artifact removal from eeg signal using wavelet transform with heuristically optimized threshold. *IEEE Journal of Biomedical*

and Health Informatics, 2021.
150. S. B. Wankhade and D. D. Doye. Ikkn predictor: An eeg signal based emotion recognition for hci. *Wireless Personal Communications*, 2019.
151. M. Egger, M. Ley, and S. Hanke. Emotion recognition from physiological signal analysis: A review. *Electronic Notes in Theoretical Computer Science*, 2019.
152. Y. Roy, H. Banville, I. Albuquerque, et al. Deep learning based electroencephalography analysis: A systematic review. *Journal of Neural Engineering*, 2019.
153. Chao Li, Ning Bian, Ziping Zhao, Haishuai Wang, and Björn W. Schuller. Multi-view domain-adaptive representation learning for eeg-based emotion recognition. *Information Fusion*, 104: 102156, 2024. doi: 10.1016/j.inffus.2023.102156.
154. S. Aydın. Deep learning classification of neuro-emotional phase domain complexity levels induced by affective video film clips. *IEEE Journal of Biomedical and Health Informatics*, 2020.
155. J. Xing, K., et al. Adaptive attention for multichannel eeg decoding. *Journal article cited in uploaded reviews*, 2018.
156. S. et al. Koelstra. Deap: A database for emotion analysis using physiological signals. *IEEE Transactions on Affective Computing*, 2012.
157. BCMI, Shanghai Jiao Tong University. Seed dataset, 2026. Dataset project page, accessed 2026.
158. Wei-Long Zheng and Bao-Liang Lu. Investigating critical frequency bands and channels for eeg-based emotion recognition with deep neural networks. *IEEE Transactions on Autonomous Mental Development*, 7(3):162–175, 2015. doi: 10.1109/TAMD.2015.2431497.
159. BCMI, Shanghai Jiao Tong University. Seed-iv dataset, 2026. Dataset project page, accessed 2026.
160. Wei-Long Zheng, Wei Liu, Yan Lu, Bao-Liang Lu, and Andrzej Cichocki. Emotionmeter: A multimodal framework for recognizing human emotions. *IEEE Transactions on Cybernetics*, 49 (3):1110–1122, 2019. doi: 10.1109/TCYB.2018.2797176.
161. Mohammad Soleymani, Judith Lichtenauer, Thierry Pun, and Maja Pantic. A multimodal database for affect recognition and implicit tagging. *IEEE Transactions on Affective Computing*, 3 (1):42–55, 2012. doi: 10.1109/T-AFFC.2011.25.
162. Juan A. Miranda-Correa, Mohammad K. Abadi, Nicu Sebe, and Ioannis Patras. Amigos: A dataset for affect, personality and mood research on individuals and groups. *IEEE Transactions on Affective Computing*, 2018.
163. Ravi Subramanian et al. Ascertain: Emotion and personality recognition using commercial sensors. *IEEE Transactions on Affective Computing*, 2018.
164. Tengfei Song, Wei-Long Zheng, Cheng Lu, Yuan Zong, Xun Zhang, and Zhenghua Cui. Mped: A multi-modal physiological emotion database for discrete emotion recognition. *IEEE Access*, 7:12177–12191, 2019. doi: 10.1109/ACCESS.2019.2891579.
165. Jie Chen et al. A large finer-grained affective computing eeg dataset. *Scientific Data*, 10:740, 2023. doi: 10.1038/s41597-023-02650-w.
166. T. B. Alakus et al. Gameemo-capsnet: Emotion recognition from single-channel eeg signals using 1d capsule networks. *Applied Sciences*, 2021.
167. Geoffrey Brookshire. Data leakage in deep learning studies of translational eeg. *Frontiers in Neuroscience*, 2024. doi: 10.3389/fnins.2024.1373515.
168. Andrea Apicella, Pasquale Arpaia, Giovanni D'Errico, Davide Marocco, Giovanna Mastrati, Nicola Moccaldi, and Roberto Prevete. Toward cross-subject and cross-session generalization in EEG-based emotion recognition: Systematic review, taxonomy, and methods. *Neurocomputing*, 604:128354, 2024. doi: 10.1016/j.neucom.2024.128354.
169. Wei-Long Zheng, Jia-Yi Zhu, and Bao-Liang Lu. Identifying stable patterns over time for emotion recognition from eeg. *IEEE Transactions on Affective Computing*, 10(3):417–429, 2019.
170. Hao Chen, Ming Jin, Zhunan Li, Cunhang Fan, Jinpeng Li, and Huiguang He. MS-MDA: Multisource marginal distribution adaptation for cross-subject and cross-session EEG emotion recognition. *Frontiers in Neuroscience*, 15:778488, 2021. doi: 10.3389/fnins.2021.778488.
171. Jinyu Li, Haoqiang Hua, Zhihui Xu, Lin Shu, Xiangmin Xu, Feng Kuang, and Shibin Wu. Cross-subject EEG emotion recognition combined with connectivity features and meta-transfer learning. *Computers in Biology and Medicine*, 145:105519, 2022. doi: 10.1016/j.compbiomed.2022.105519.
172. Hao Chen, Zhunan Li, Ming Jin, and Jinpeng Li. Meernet: Multi-source eeg-based emotion recognition network for generalization across subjects and sessions. In *2021 43rd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)*, pages 6094–6097. IEEE, 2021. doi: 10.1109/EMBC46164.2021.9630277.
173. Fan Xiong, Mengzhao Fan, Xu Yang, Chenxiao Wang, and Jinli Zhou. Research on emotion recognition using sparse eeg channels and cross-subject modeling based on cnn-kan-f2ca model. *PLOS ONE*, 20(5):e0322583, 2025. doi: 10.1371/journal.pone.0322583.
174. S. Ding, K. Wang, W. Jiang, C. Xu, H. Bo, L. Ma, and H. Li. Dgat: A dynamic graph attention neural network framework for eeg emotion recognition. *Frontiers in Psychiatry*, 16:1633860, 2025. doi: 10.3389/fpsyt.2025.1633860.
175. Tengfei Song, Wenming Zheng, Peng Song, and Zhen Cui. EEG emotion recognition using dynamical graph convolutional neural networks. *IEEE Transactions on Affective Computing*, 11(3): 532–541, 2020. doi: 10.1109/TAFFC.2018.2817622.
176. X. Deng, J. Zhu, and S. Yang. Sfe-net: Eeg-based emotion recognition with symmetrical spatial feature extraction. In *Proceedings of the 29th ACM International Conference on Multimedia*, pages 2391–2400, 2021. Virtual Event.
177. Bihai Lin, Chuanzhi Liu, Xinyi Wu, and Xiaowei Chen. Selective channel bypassing meets capsules: Efficient and robust eeg emotion recognition. *Biomedical Signal Processing and Control*, 120:110077, 2026. doi: 10.1016/j.bspc.2026.110077.
178. R. S. Soundariya and P. Thangaraj. Modeling multiscale neural dynamics for eeg-based emotion recognition using an attentive wavelet–transformer framework. *Frontiers in Computational Neuroscience*, 20:1775449, 2026. doi: 10.3389/fncom.2026.1775449.
179. Chengyu Hua, Hui Cao, Zhaolong Li, and Zhiqiang Huang. A dual-branch network with brain region-constrained attention for eeg emotion recognition. *Frontiers in Neuroscience*, 20: 1810609, 2026. doi: 10.3389/fnins.2026.1810609.
180. Decheng Liu, Congcong Wang, Danyang Chen, Yankun Cao, Xifeng Hu, Xian Zhao, and Zhi Liu. Taformer: Eeg-based emotion recognition using triplet attention transformer and 4d feature dense representation. *Biomedical Signal Processing and Control*, 119:109873, 2026. doi: 10.1016/j.bspc.2026.109873.
181. Yu Liu, Yufeng Ding, Chang Li, Juan Cheng, Rencheng Song, Feng Wan, and Xun Chen. Multi-channel EEG-based emotion recognition via a multi-level features guided capsule network. *Computers in Biology and Medicine*, 123:103927, 2020. doi: 10.1016/j.compbiomed.2020.103927.
182. Guangcheng Bao, Kai Yang, Li Tong, Jun Shu, Rongkai Zhang, Linyuan Wang, Bin Yan, and Ying Zeng. Linking multi-layer dynamical GCN with style-based recalibration CNN for EEG-based emotion recognition. *Frontiers in Neurorobotics*, 16: 834952, 2022. doi: 10.3389/fnbot.2022.834952.
183. Elham S. Salama, Reda A. El-Khoribi, Mahmoud E. Shoman, and Mohamed A. Wahby Shalaby. EEG-based emotion recognition using 3d convolutional neural networks. *International Journal of Advanced Computer Science and Applications*, 9(8): 329–337, 2018. doi: 10.14569/IJACSA.2018.090843.
184. Guowen Xiao, Meng Shi, Mengwen Ye, Bowen Xu, Zhendi Chen, and Quansheng Ren. 4d attention-based neural network for EEG emotion recognition. *Cognitive Neurodynamics*, 16(4):

805–818, 2022. doi: 10.1007/s11571-021-09751-5.
185. Linlin Gong, Mingyang Li, Tao Zhang, and Wanzhong Chen. EEG emotion recognition using attention-based convolutional transformer neural network. *Biomedical Signal Processing and Control*, 84:104835, 2023. doi: 10.1016/j.bspc.2023.104835.
186. Wei Chen, Yuan Liao, Rui Dai, Yuanlin Dong, and Liya Huang. EEG-based emotion recognition using graph convolutional neural network with dual attention mechanism. *Frontiers in Computational Neuroscience*, 18:1416494, 2024. doi: 10.3389/fncom.2024.1416494.
187. Yutao Huang and Jijie Deng. A SimAM-enhanced multi-resolution CNN with BiGRU for EEG emotion recognition: 4D-MRSimNet. *Electronics*, 15(1):39, 2026. doi: 10.3390/electronics15010039.
188. Yi Wei, Yu Liu, Chang Li, Juan Cheng, Rencheng Song, and Xun Chen. TC-Net: A transformer capsule network for EEG-based emotion recognition. *Computers in Biology and Medicine*, 152:106463, 2023. doi: 10.1016/j.compbiomed.2022.106463.
189. Wei Lu, Tien-Ping Tan, and Hua Ma. Bi-branch vision transformer network for EEG emotion recognition. *IEEE Access*, 11: 36233–36243, 2023. doi: 10.1109/ACCESS.2023.3266117.
190. Bincheng Qian, Zhiqin Qian, Huishan Liang, Qi Luo, and L. Xu. AGCN-SAT: Adaptive graph convolutional network with spatial attention and transformer for EEG emotion recognition. In *2023 IEEE 3rd International Conference on Electronic Technology, Communication and Information (ICETCI)*, pages 418–423. IEEE, 2023. doi: 10.1109/ICETCI57876.2023.10176392.
191. Zhiqiang Huang, Hui Cao, Zhaolong Li, and Chengyu Hua. Astclnet: Eeg emotion recognition based on dual-branch adaptive graph convolution and contrastive learning. *Biomedical Signal Processing and Control*, 121:110302, 2026. doi: 10.1016/j.bspc.2026.110302.
192. Vikas Reddy Venkannagari, Shivansh Sharma, Parthan Olikkal, Dev Parikh, Jay Paun, Farshad Safavi, and Ramana Vinjamuri. Toward robust eeg classification using adaptive cnn–transformer and inception architectures and signal level augmentation. *Sensors*, 26(14):4636, 2026. doi: 10.3390/s26144636.
193. J. Li, W. Pan, H. Huang, et al. Stgate: spatial-temporal graph attention network with a transformer encoder for eeg-based emotion recognition. *Frontiers in Human Neuroscience*, 17: 1169949, 2023. doi: 10.3389/fnhum.2023.1169949.
194. Sheng Dai, Ming Li, Xu Wu, Xiangyu Ju, Xinyu Li, Jun Yang, and Dewen Hu. Contrastive learning of eeg representation of brain area for emotion recognition. *IEEE Transactions on Instrumentation and Measurement*, 74:1–13, 2025. doi: 10.1109/TIM.2025.3533618.
195. Jiang Chang, Zhixin Zhang, Yuhua Qian, and Pan Lin. Multi-scale hyperbolic contrastive learning for cross-subject eeg emotion recognition. *IEEE Transactions on Affective Computing*, 16 (3):1716–1731, 2025. doi: 10.1109/TAFFC.2025.3535542.
196. Tengfei Song, Suyuan Liu, Wenming Zheng, Yuan Zong, and Zhen Cui. Instance-adaptive graph for eeg emotion recognition. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34 (3):2701–2708, 2020. doi: 10.1609/aaai.v34i03.5656.
197. Shuaiqi Liu, Xu Wang, Ling Zhao, Jie Zhao, Qi Xin, and Shui-Hua Wang. Subject-independent emotion recognition of eeg signals based on dynamic empirical convolutional neural network. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 18(5):1710–1721, 2021. doi: 10.1109/TCBB.2020.3018137.
198. Jingcong Li, Shuqi Li, Jiahui Pan, and Fei Wang. Cross-subject eeg emotion recognition with self-organized graph neural network. *Frontiers in Neuroscience*, 15:611653, 2021. doi: 10.3389/fnins.2021.611653.
199. Darshana Priyasad, Tharindu Fernando, Simon Denman, Sridha Sridharan, and Clinton Fookes. Affect recognition from scalp-eeg using channel-wise encoder networks coupled with geometric deep learning and multi-channel feature fusion. *Knowledge-Based Systems*, 250:109038, 2022. doi: 10.1016/j.knosys.2022.109038.
200. Dongmin Huang, Sentao Chen, Cheng Liu, Lin Zheng, Zhihang Tian, and Dazhi Jiang. Differences first in asymmetric brain: A bi-hemisphere discrepancy convolutional neural network for EEG emotion recognition. *Neurocomputing*, 448: 140–151, 2021. doi: 10.1016/j.neucom.2021.03.105.
201. Yang Li, Ji Chen, Fu Li, Boxun Fu, Hao Wu, Youshuo Ji, Yijin Zhou, Yi Niu, Guangming Shi, and Wenming Zheng. Gmss: Graph-based multi-task self-supervised learning for eeg emotion recognition. *IEEE Transactions on Affective Computing*, 14 (3):2512–2525, 2023. doi: 10.1109/TAFFC.2022.3170428.
202. Guanhua Zhang, Minjing Yu, Yong-Jin Liu, Guozhen Zhao, Dan Zhang, and Wenming Zheng. Sparsedgcnn: Recognizing emotion from multichannel eeg signals. *IEEE Transactions on Affective Computing*, 14(1):537–548, 2023. doi: 10.1109/TAFFC.2021.3051332.
203. Yujin Ji, Do-Hyung Kim, and Jungpyo Hong. Enhanced eeg emotion recognition using mimo-based denoising and band-wise attention graph neural network. *Sensors*, 26(4):1133, 2026. doi: 10.3390/s26041133.
204. P. Pandey and K. R. Seeja. Subject independent emotion recognition from EEG using VMD and deep learning. *Journal of King Saud University - Computer and Information Sciences*, 34 (5):1730–1738, 2022. doi: 10.1016/j.jksuci.2019.11.003.
205. Gopal Chandra Jana, Anshuman Sabath, and Anupam Agrawal. Capsule neural networks on spatio-temporal EEG frames for cross-subject emotion recognition. *Biomedical Signal Processing and Control*, 72:103361, 2022. doi: 10.1016/j.bspc.2021.103361.
206. Fu Yang, Xingcong Zhao, Wenge Jiang, Pengfei Gao, and Guangyuan Liu. Multi-method fusion of cross-subject emotion recognition based on high-dimensional EEG features. *Frontiers in Computational Neuroscience*, 13:53, 2019. doi: 10.3389/fncom.2019.00053.
207. Rui Li, Chao Ren, Xiaowei Zhang, and Bin Hu. A novel ensemble learning method using multiple objective particle swarm optimization for subject-independent EEG-based emotion recognition. *Computers in Biology and Medicine*, 140: 105080, 2022. doi: 10.1016/j.compbiomed.2021.105080.
208. Zhongli Bai, Fazheng Hou, Kaixuan Sun, Qingzhou Wu, Mu Zhu, Zemin Mao, Yu Song, and Qiang Gao. SECT: A method of shifted EEG channel transformer for emotion recognition. *IEEE Journal of Biomedical and Health Informatics*, 27 (10):4758–4767, 2023. doi: 10.1109/JBHI.2023.3301993.
209. Jipu Su, Jie Zhu, Tiecheng Song, and Hongli Chang. Subject-independent EEG emotion recognition based on genetically optimized projection dictionary pair learning. *Brain Sciences*, 13(7):977, 2023. doi: 10.3390/brainsci13070977.
210. Wenhui Guo, Yaxuan Li, Mengxue Liu, Rui Ma, and Yanjiang Wang. Functional connectivity-enhanced feature-grouped attention network for cross-subject EEG emotion recognition. *Knowledge-Based Systems*, 283:111199, 2024. doi: 10.1016/j.knosys.2023.111199.
211. Himanshu Kumar, Nagarajan Ganapathy, Subha D. Puthankattil, and Ramakrishnan Swaminathan. Subject-independent emotion recognition with EEG bispectral quadratic phase coupling features and explainable machine learning. *Biomedical Physics & Engineering Express*, 12(3):035049, 2026. doi: 10.1088/2057-1976/ae711a.
212. Hashim Ali, Zangar Ermaganbet, and Muhammad Tahir Akhtar. Hybrid cnn–lstm network for cross-subject eeg emotion recognition. *Discover Artificial Intelligence*, 6:598, 2026. doi: 10.1007/s44163-026-01314-z.
213. He Huang, Xiaopeng Si, Yumeng Han, and Dong Ming. A novel conditional adversarial domain adaptation network for eeg cross-subject emotion recognition. *IEEE Transactions on Affective Computing*, 16(4):2905–2917, 2025. doi: 10.1109/TAFFC.

2025.3588873.

214. Xiao-Cong Zhong, Qisong Wang, Rui Li, Yurui Liu, Sanhe Duan, Runze Yang, Dan Liu, and Jinwei Sun. Unsupervised domain adaptation with pseudo-label propagation for cross-domain eeg emotion recognition. *IEEE Transactions on Instrumentation and Measurement*, 74:1–11, 2025. doi: 10.1109/TIM.2025.3553234.
215. Feifan Yan, Bo Zhang, Ziliang Cai, Minghao Du, Xiaoya Liu, Zhinan Yu, Sitong Chen, Shuang Liu, and Dong Ming. Cross-subject emotion recognition with loop adaptive adversarial transfer network. *Neural Networks*, 196:108324, 2026. doi: 10.1016/j.neunet.2025.108324.
216. Yun Gao and Hai Deng. Cross-subject eeg emotion recognition using riemannian graph transformers with geodesic adversarial adaptation. *Alexandria Engineering Journal*, 142:61–73, 2026. doi: 10.1016/j.aej.2026.03.045.
217. Shuang Liu, Huifeng Guo, Rongyu Han, Yajing Pang, and Gang Liu. Multi-source domain adaptive eeg emotion recognition based on dendrite net. *Computers*, 15(7):454, 2026. doi: 10.3390/computers15070454.
218. Zhepei Hong, Rongtao Chen, Liting Li, Jiajun Chen, Wei Gao, and Jiahui Pan. Heat: Hierarchical emotion adaptation with progressive thresholding for eeg emotion and consciousness detection. *Biomedical Signal Processing and Control*, 121:110299, 2026. doi: 10.1016/j.bspc.2026.110299.
219. Yun Luo and Bao-Liang Lu. Wasserstein-distance-based multi-source adversarial domain adaptation for emotion recognition and vigilance estimation. In *2021 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 1424–1428. IEEE, 2021. doi: 10.1109/BIBM52615.2021.9669383.
220. Run Ning, C. L. Philip Chen, and Tong Zhang. Cross-subject eeg emotion recognition using domain adaptive few-shot learning networks. In *2021 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 1468–1472. IEEE, 2021. doi: 10.1109/BIBM52615.2021.9669542.
221. Yingdong Wang, Jiatong Liu, Qunsheng Ruan, Shuocheng Wang, and Chen Wang. Cross-subject eeg emotion classification based on few-label adversarial domain adaption. *Expert Systems with Applications*, 185:115581, 2021. doi: 10.1016/j.eswa.2021.115581.
222. Xuguang Liu, Changyi Yu, Ye Li, Xin Zhang, and Xiu Zhang. Decoding non-invasive electroencephalography signal via a two-discriminator adversarial network. *Sensors*, 26(3):1074, 2026. doi: 10.3390/s26031074.
223. Zihao Luo, Qingshan She, Tianpei Jin, Yipeng Li, and Xugang Xi. Adaptive graph convolution domain adaptation network for cross-subject eeg emotion recognition. *Medical & Biological Engineering & Computing*, 2026. doi: 10.1007/s11517-026-03543-x. Online ahead of print.
224. Shuang Ran, Wei Zhong, Shuzhan Hu, Long Ye, and Qin Zhang. Fsa-net: Coarse-to-fine domain adaptation with flexible source aggregation for cross-subject eeg emotion recognition. *Tsinghua Science and Technology*, 2026. doi: 10.26599/TST.2026.9010060. Just accepted.
225. Luiz Pessoa. A network model of the emotional brain. *Trends in Cognitive Sciences*, 21(5):357–371, 2017. doi: 10.1016/j.tics.2017.03.002.
226. Michael X. Cohen. Where does eeg come from and what does it mean? *Trends in Neurosciences*, 40(4):208–218, 2017. doi: 10.1016/j.tins.2017.02.004.
227. Kun Yang, Zhenning Yao, Keze Zhang, Jing Xu, Li Zhu, Shichao Cheng, and Jianhai Zhang. Automatically extracting and utilizing EEG channel importance based on graph convolutional network for emotion recognition. *IEEE Journal of Biomedical and Health Informatics*, 28(8):4588–4598, 2024. doi: 10.1109/JBHI.2024.3404146.
228. Xu Xu, Junxin Chen, Qiang He, Yongfei Wu, and Yicong Zhou. EEG emotion recognition with uncertainty-aware contrastive learning and frequency-aware self-attention. *IEEE Transactions on Cybernetics*, 56(4):1845–1858, 2026. doi: 10.1109/TCYB.2026.3665442.
229. Yichuan Lin, Geng-Xin Xu, Haotian Liang, Yishan Wang, Feng Wan, and Ye Li. Brain region knowledge-based dual-stream transformer for EEG emotion recognition. *IEEE Transactions on Consumer Electronics*, 71(2):2762–2773, 2025. doi: 10.1109/TCE.2025.3552801.
230. Smith K. Khare, Victoria Blanes-Vidal, Esmaeil S. Nadimi, and U. Rajendra Acharya. Emotion recognition and artificial intelligence: A systematic review (2014–2023) and research recommendations. *Information Fusion*, 102:102019, 2024. doi: 10.1016/j.inffus.2023.102019.
231. Dwi Wahyu Prabowo, Hanung Adi Nugroho, Noor Akhmad Setiawan, and Johan Debayle. A systematic literature review of emotion recognition using EEG signals. *Cognitive Systems Research*, 82:101152, 2023. doi: 10.1016/j.cogsys.2023.101152.
232. Kaido Värbu, Naveed Muhammad, and Yar Muhammad. Past, present, and future of EEG-based BCI applications. *Sensors*, 22(9):3331, 2022. doi: 10.3390/s22093331.
233. Tao Xu, Hongtao Wang, Guanyong Lu, Feng Wan, Mengqi Deng, Peng Qi, Anastasios Bezerianos, Cuntai Guan, and Yu Sun. E-Key: An EEG-based biometric authentication and driving fatigue detection system. *IEEE Transactions on Affective Computing*, 14(2):864–877, 2023. doi: 10.1109/TAFFC.2021.3133443.
234. Chaitanya Sethi, Harsh Dabas, Chirag Dua, Mohit Dalawat, and Divyashikha Sethia. EEG-based attention feedback to improve focus in e-learning. In *Proceedings of the 2018 2nd International Conference on Computer Science and Artificial Intelligence*, pages 321–326. Association for Computing Machinery, 2018. doi: 10.1145/3297156.3297157.
235. Giorgio Li Pira, Beatrice Aquilini, Alessandro Davoli, Silvana Grandi, and Chiara Ruini. The use of virtual reality interventions to promote positive mental health: Systematic literature review. *JMIR Mental Health*, 10:e44998, 2023. doi: 10.2196/44998.
236. Debadrita Panda, Debashis Das Chakladar, Sudhir Rana, and Satyanarayana Parayitam. An EEG-based neuro-recommendation system for improving consumer purchase experience. *Journal of Consumer Behaviour*, 23(1):61–75, 2024. doi: 10.1002/cb.2142.
237. Jin Woo Choi, Haram Kwon, Jaehoon Choi, Netiwit Kaongoen, Chaeeun Hwang, Minuk Kim, Byung Hyung Kim, and Sungho Jo. Neural applications using immersive virtual reality: A review on EEG studies. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 31:1645–1658, 2023. doi: 10.1109/TNSRE.2023.3254551.