

Deep Learning-Based Emotion Recognition using EEG: A Comprehensive Review

Shihab Sarar Md Niaz Imtiaz* Naimul Khan

Shihab Sarar

Department of Computer Science and Engineering, Ahsanullah University of Science and Technology, Love Road, Tejgaon Industrial Area, Dhaka-1208, Bangladesh

Email Address: shihabsararchamok@gmail.com

Md Niaz Imtiaz

Department of Electrical, Computer and Biomedical Engineering, Toronto Metropolitan University, 350 Victoria St, Toronto, ON M5B 2K3, Canada

Email Address: niaz.imtiaz@torontomu.ca

Naimul Khan

Department of Electrical, Computer and Biomedical Engineering, Toronto Metropolitan University, 350 Victoria St, Toronto, ON M5B 2K3, Canada

Email Address: n77khan@torontomu.ca

Keywords: *electroencephalography (EEG); emotion recognition; affective computing; deep learning; cross-subject learning; brain-computer interface (BCI); signal processing*

Abstract

Emotion recognition using EEG is a growing trend in affective computing, with highly fragmented studies regarding datasets, approaches, and evaluation metrics, as well as a high degree of inter-individual variability and a rapidly changing set of deep learning approaches. In this scenario, it is difficult to extract a comprehensive view on the generalizability and practicability of the approaches considered. This work offers a structured review of emotion recognition using EEG, aiming to decrease this level of fragmentation by grouping the existing approaches following signal processing, representation learning, deep learning architectures, and cross-subject learning strategies. The most widely adopted deep learning architectures, graph-based, recurrent, and convolutional neural networks, are considered regarding their set of architectural choices, strengths, and weaknesses, as well as related trade-offs. Other major issues, overfitting, small dataset, and subject dependency, are illustrated and critically considered together with more recent approaches trying to increase the reliability of EEG emotion recognition systems. According to recent studies, the accuracy achieved in subject-specific approaches is higher than 95%, while for the subject-independent approach, accuracy values vary from 70% to 90%, depending on the dataset and the architecture considered.

1 Introduction

Emotion recognition is at the heart of models of human behavior, since emotional states directly and profoundly affect human cognition, decision-making, and social interactions. Automatic emotion recognition facilitates the development of intelligent systems capable of adaptively responding to the affect states of users, and this is particularly critical in contemporary human-computer interaction tasks. Emotion recognition in psychology and neuroscience helps in the objective analysis of affective phenomena independently of subjective self-assessments, and in the health sector, it paves the way for numerous tasks, such as the objective evaluation of mood disturbances, patient recovery, and supportive treatment of neurodevelopmental disorders such as autism and affect dysregulation. Emotion recognition in engineering and brain-computer interface studies helps in developing adaptive systems capable of automatically responding to the affective states of users. Emotion recognition using EEG recordings is particularly useful in patient-oriented tasks in the health sector, such as patient recovery and long-term evaluation of patient moods, wherein overt behavioral manifestations of patients could be ambiguous and unavailing. EEG emotion recognition stands distinct, as it directly taps brain signals related to emotion recognition, and this makes the technology valuable in tasks where robustness and physiological validity of the detection tasks are critical.

Electroencephalography (EEG) is a non-invasive neurophysiological sensing technique that records electrical activity generated by neuronal populations with high temporal resolution. Because EEG captures

brain dynamics at the millisecond level, it provides fine-grained insight into neural processes underlying emotional responses, which are often transient and rapidly evolving [1, 2]. EEG-based emotion recognition systems exploit this close coupling between brain activity and affective processing by analyzing neural responses elicited during emotional stimulation to infer underlying emotional states [3]. This neurophysiological grounding distinguishes EEG from peripheral or behavioral modalities and motivates its widespread adoption in affective computing research.

EEG further provides important advantages compared to other emotion recognition methods, like facial expressions, speech, or body gestures. Behavioral cues are susceptible to intentional control, social camouflage, and context effects and are thus not very reliable in a sensitive context. Conversely, EEG oscillations are symptomatic of inner neural activities that are hard to manipulate intentionally and supply objective estimations of affective states [4]. Although increasingly explored, at least for the future of emotion-sensitive BCIs, multimodal approaches combining EEG with other physiological or behavioral signals are not required, and EEG alone can be a robust and informative modality owing to its direct sensitivity to emotional brain dynamics and the compatibility with BCI systems.

Despite having all these benefits, there are a few challenges to recognizing emotions using EEG. The quality of an EEG signal is highly dependent on factors like electrode positioning, skin conductance, movement artifacts, and inter-session inconsistency. Variability in experimental procedures, emotional stimuli used, labeling approaches, and preprocessing techniques adds to inconsistencies [5]. These create difficulties in comparing methodology-based approaches systematically, especially when assessing performance on diverse databases such as DEAP, SEED, and DREAMER [2, 6]. Additionally, large variations between subjects lead to large distribution changes in the features of an EEG signal, thereby negatively affecting subject-independent generalization.

Recent breakthroughs in deep learning have led to significant improvements in EEG-based affect recognition models that are capable of learning informative features directly from raw or lightly preprocessed signals [4]. Convolutional Neural Networks (CNNs) capture channel-level relations in EEG signals [7], Recurrent Neural Networks (RNNs) model temporal dependencies in brain activity dynamics [8], and Graph Neural Networks (GNNs) represent task-relevant functional connectivity between brain regions [9]. Despite their strong ability in achieving a high level of accurate classification for subject-dependent tasks, they have been observed to have poor generalization capability for cross-subject and cross-corpus [10].

There has been an increased need to carry out a review of up-to-date research work in the area of emotion recognition using EEG. There are many reviews that were mainly concentrating on architectural originality or evaluation tasks on a single dataset, with less concern for cross-subject and cross-dataset generalization [5, 4]. Additionally, a lack of standardized preprocessing pipelines and inconsistencies in evaluation methodologies make it hard to make a valid inference [11] on the research. There is no consensus or agreement on the best way for model design, evaluation, and implementation of effective EEG-based emotion recognition [12].

Limitations of some of the above-mentioned works have only focused on one aspect of deep learning for EEG-based emotion recognition. In order to overcome these limitations, this paper provides a systematic and detailed review of deep learning methods for EEG-based emotion recognition. The key contributions of this review are summarized as

1. A well-organized establishment of fundamental research issues pertaining to processing and feature extraction of EEG signals, as well as deep learning-based modeling of emotion.
2. Comparative synthesis of CNN, RNN, and GNN-based approaches within subject-specific and subject-independent frameworks.
3. Discussion of generalization, robustness, and efficiency tradeoffs in paradigms of deep learning analytically.
4. Critical analysis of existing work on transfer learning and domain adaptation methods for dealing with intersubject and cross-dataset variation.

This review integrates scattered research on EEG emotion recognition into a cohesive view. It provides an overview of the essential challenges of EEG signal processing, feature extraction, and deep learning for modeling emotions and comparisons of popular neural architectures like convolutional networks, recurrent networks, and graph networks for subject-specific and subject-independent tasks. This review provides an insight into the essential trade-offs of generalization capability, robustness, and complexity that limit the application of the current solutions. Apart from this, the potential of transfer learning and domain adaptation in handling intersubject and cross-domain variability has been discussed with both limitations and opportunities. There are several other topics that will be discussed in the review to introduce an overview of the state of the art while identifying the essential research paths for improving robust and scalable solutions for EEG emotion recognition.

2 Theoretical and Methodological Foundations

The theoretical background defines EEG-based emotion recognition as a framework that links measurable neurophysiological activity to computational representations of affect. It models emotional state as a structured pattern distributed across time, frequency bands, and scalp locations, and it treats learning as the problem of extracting robust features or representations from noisy, non-stationary brain signals [13]. It also establishes the use of emotion label names via two-way paradigms: the discrete classification paradigm, where EEG segments are classified into distinct affective states, and the continuous modeling paradigm, where predictions of valence and arousal ratings are performed [14]. These standpoints shape design decisions, evaluation schemes, and generalizations over subjects and sessions [15].

2.1 Emotion Recognition

Emotion recognition is a principal goal of affective computing in pursuing the aim of enabling computational systems that can efficaciously and adaptively respond to the emotional states of humans. Notwithstanding the increasing penetration of human-computer interaction into more and more areas of everyday life, the overall lack of awareness of user emotional states in human-computer interfaces hampers the overall efficiency of such interfaces in applications that demand user-level personalization, empathy, and commitment to user well-being, thereby pursuing the need to endow computers with the potential to identify user affective states through some form of user cues or physiological signals.

Conventional emotion recognition methods exploit behavioral features, such as facial expression, speech pattern, body language, and text messages. Though these features express more palatable aspects of human emotion, they are still amenable to control and masking in a controlled manner. In this context, combining different sources of variation with physiological measures, which are less controllable at a voluntary level, constitutes a more objective solution. Among various physiological measures, EEG represents a prominent choice because of its direct sensitivity to neural mechanisms related to processing emotions and its high resolution, enabling the monitoring of rapid dynamics of emotions [14, 16].

EEG-based emotion recognition systems model tasks that relate to EEG-stimuli pairs distributed with certain emotion categories. The changes in the emotional state cause changes in EEG rhythms and spatial activity, as well as changes that could be used to extract new information on state transitions between different emotions. According to a set of recent surveys on EEG-based emotion recognition models, the traditional pipeline of EEG emotion recognition systems includes data processing, noise removal, eigenvector transformation, and machine learning inference, with a current emphasis on end-to-end models. Traditionally, models are based on some hand-engineered features from temporal, frequency, or time-frequency worlds, whereas current models are increasingly based on deep learning models that extract hierarchical features from EEG data.

Deep learning models have characterized the emotion recognition study area because of their ability to learn complex, non-linear correlations in multichannel EEG data. Convolutional neural networks have been extensively employed to leverage the spatial information among EEG electrodes, mostly applied when processing EEG maps or image-like representations of EEG signals. Recurrent and Gated Recur-

rent Neural Networks have been used to model time information, and their primary purpose is to capture time-dependent information of emotion relevant to the research area. Most of the recent studies incorporated graph neural networks and leveraged the connectivity between EEG channels, which gives neurobiologically valid models for emotion recognition [15, 14].

Despite improvements in algorithm methodology, emotion recognition accuracy is known to remain highly vulnerable to specific experimental conditions. In subject-dependent approaches, the absence of significant variability leads to excellent accuracy, while subject-independent and cross-dataset approaches remain significant challenges [15, 16]. Variability across people and recording devices, as well as divergence across protocols for invoking emotions, causes substantial distribution divergence, thereby negatively impacting overall generalization. Thus, there is a growing trend within recent studies on applying transfer learning, domain adaptation techniques, and alignment techniques for enhanced subject and recording device independence [15, 16].

Emotion recognition is viewed in the literature not only as a classification problem but also as a much more complex inference problem, which is affected by neurophysiological variations, experimental conditions, and generalization. Continued progress in EEG-based emotion recognition, therefore, depends on jointly advancing acquisition protocols, representation learning, and evaluation methodologies to support reliable deployment in real-world affective systems.

2.2 Neurophysiological Foundations of Emotional States

Neurophysiological accounts of emotion in EEG-ER interpret emotional episodes as changes in distributed brain activity that manifest as time-varying and band-limited oscillatory patterns across channels. EEG acquisition during affective stimulation, therefore, produces signals with *spatial structure across electrode locations, temporal structure due to stimulus duration and sliding-window segmentation, and frequency structure because analysis commonly separates δ , θ , α , β , and γ rhythms, each of which exhibits different responsiveness under affective conditions* [13].

Within this framing, EEG-ER pipelines either follow a staged procedure (denoising $\rightarrow$ feature extraction $\rightarrow$ classifier learning) or adopt end-to-end feature learning, and they rely on assumptions about label availability and the degree to which training and test data approximate i.i.d. conditions [15]. When these assumptions fail—especially under cross-subject, cross-session, or cross-database settings—emotion-related neural patterns appear heterogeneous, motivating modeling strategies that explicitly target domain gaps and subject bias [15]. EEG-ER surveys formalize feature construction as multi-domain representation learning. Temporal features describe transitive or long-term variations of events, while spectral features are the result of band-pass filtering, Fourier transforms, and other transforms like it. Spatial features describe inter-channel relationships that correspond to the spatial organization of the cortical structure of the human brain and its variability [13]. This multi-domain stance links directly to contemporary architectures (CNN/RNN/GNN/Transformer variants) that operationalize spatial-temporal-spectral fusion and to transfer-learning approaches that seek domain-invariant representations under strong inter-individual variability [17].

Benchmark datasets encode these neurophysiological assumptions by pairing affective stimuli (e.g., videos/music) with EEG recordings and either discrete labels or continuous ratings, thereby defining the target emotional state space and the evaluation protocol [15].

2.2.1 Discrete Emotion Representation Models

Discrete EEG-ER models treat emotion as membership in a finite set (e.g., positive/neutral/negative; basic categories), and they implement classification as a mapping from multi-channel EEG representations to class labels. The literature consistently organizes discrete modeling around (a) feature engineering or learned representations across temporal-spectral-spatial domains and (b) classifier families ranging from SVM/KNN to deep neural architectures [13].

A core empirical regularity in discrete EEG-ER is that frequency-domain features—including PSD and differential entropy—serve as widely used affective descriptors, commonly computed per band and per

channel before classification [14]. Discrete pipelines, therefore, often couple bandwise features with spatial modeling to reflect the channel topology, using methods such as CSP/HDCA for spatial structure or deep models that internalize spatial priors [14].

Additionally, deep learning reviews break down the most popular discrete EEG-ER models into single models: CNN/RNN/GNN models, attention models, combination models, and domain transfer models or models that perform DG/DPre [17]. According to the categories of the above review, the most popular discrete models are the following: DEAP-discrete models of CNN models [18], hierarchical CNN models of DEAP data that use natural spectral features like differential entropy maps [19]. RNN/GRU/LSTM variants implement the concept of temporal dependency, such as attention-driven LSTM classifiers and spatiotemporal recurrent designs [20]. Parallel convolutional–recurrent designs explicitly fuse spatial filtering with temporal recurrence in multi-channel EEG [21]. GNN-based discrete EEG-ER models represent electrodes as nodes and learn adjacency structures to encode functional coupling patterns [22]. Discrete state modeling also depends on the experimental regime. Surveys separate subject-dependent and subject-independent protocols because cross-subject generalization remains harder and motivates architectural choices (e.g., graph attention, domain adversarial training) and evaluation practices [14]. In this context, domain adaptation methods and adversarial learning explicitly address subject bias by aligning feature distributions across individuals [17].

The transfer-learning approaches for EEG-ER problems further solidify discrete EEG-ER as a problem of learning over gaps within domains owing to differences within the subject, session, or database. Domain transfer for knowledge can be classified along the lines of instance transfer, feature transfer, parameter transfer, and relation transfer, each dealing with the discrete classification problem through minimizing the discrepancy over domains [15]. Methods, for instance, weight assignment as in TrAdaBoost, seek to weight the source instances to align with the target domain [15]. Others apply feature transformation or learn subspaces to reduce distribution discrepancy and include deep learning approaches that learn transfer representations [15]. The methods for parameter transfer encompass model fine-tuning and transductive parameter transfer, making effective use of model portability across domains [15].

Discrete models also incorporate label sets that are specific to the data sets. Discrete sets of categories such as anger, fear, sadness, and happiness, among others, are commonly found in public databases, and they can also help in a comparative study [15].

2.2.2 Continuous Dimensional Emotion Representation Models

Continuous EEG-ER models treat emotion as a point in a low-dimensional affective space (most commonly valence–arousal, sometimes extended with dominance/liking/familiarity), and they implement learning as regression, ordinal prediction, or discretization of continuous ratings into quadrants/bins. Reviews emphasize that datasets explicitly differ in whether they provide continuous ratings or discrete labels, and they organize benchmark corpora accordingly [13].

From a neurophysiological perspective, continuous modeling aligns with the idea that EEG dynamics vary smoothly over time and that affective response strength differs across frequency bands and windows; thus, temporal segmentation and band decomposition are foundational operations before continuous inference [13]. Continuous systems typically compute bandwise features (PSD/DE/entropy) or learn representations end-to-end, and they map these representations to dimensional ratings using neural regressors or hybrid architectures [15].

Continuous emotion modeling also inherits the central challenge of domain gaps. Transfer-learning surveys define cross-session transfer as addressing acquisition-time variability within the same subject and define cross-subject transfer as addressing individual differences; both scenarios directly affect dimensional prediction because rating scales must remain comparable while EEG distributions shift [15]. Cross-database transfer further compounds these difficulties due to differences in devices, experimental conditions, and label distributions, making it the most challenging scenario for stable continuous inference [15].

In practice, continuous EEG-ER systems often discretize ratings into two-class (high/low) or four-quadrant valence–arousal tasks to enable comparability with classification pipelines while preserving the underlying




Figure 1: Valence-Arousal 2D Affective Model

ing dimensional semantics [13]. Surveyed results illustrate that some methods explicitly evaluate both binary dimensional splits and quadrant partitions on datasets such as DEAP and DREAMER, reflecting a continuum between regression-style modeling and discretized dimensional classification [13].

Deep learning reviews indicate that architectures used for continuous affect frequently mirror those used in discrete settings—CNNs for local spatiotemporal patterns, RNNs/GRUs for sequential structure, and attention mechanisms for adaptive weighting—while evaluation emphasizes stability and generalization across subjects, which remains more challenging but more deployment-relevant [17]. Another factor, according to survey studies, is that EEG signal processing and feature extraction are still very important, given the presence of noise in EEG signals, which require signal denoising and robust representation learning for predictive processing [15].

Transfer learning becomes especially relevant in continuous affect because it reduces target-domain labeling demand by transferring learned structure from related subjects/sessions/databases, but it also introduces risks of negative transfer when domain gaps are large [15]. Consequently, feature-based deep transfer learning (e.g., discrepancy minimization and adversarial alignment) emerges as a dominant direction for improving dimensional generalization [15].

2.3 Emotion Induction and Stimulus Design

Emotion induction and stimulus design determine how affective responses are reliably evoked and temporally aligned with EEG recordings. Prior methodological surveys describe emotion induction as a prerequisite for meaningful EEG labeling, because weak or inconsistent stimuli directly degrade the validity of learned affective representations [23]. Paradigms involving images, music, or video clips remain popular paradigms because they ensure accurate onset-offset timing, which also ensures easy repeated measurement for every participant, helping in easy segmentation and extraction of features [24]. These paradigms also involve post-trial self-evaluation tasks for mapping brain responses with subjective experience in order to reinforce the accuracy of labeling at the trial level [25].

Interactive and task-driven stimuli are growing in usage as alternative paradigms because they promote enduring and contextually rooted emotion processes that passive stimuli may fail to support. However, the literature underscores that such paradigms significantly amplify inter-subject variability as well as the overall complexity of the experiments [26]. Memory recall methods based on the subject's personal memory rely on personal emotion triggers but fall prey to personal cognitive and emotion variables; therefore, their cross-subject universality is limited [27]. In summary, modern studies on emotion processing




Figure 2: Stimulus

with the EEG directly address the issue of stimuli as a trade-off between standardization, engagement, and universality [28].

In terms of stimulus modality, the scope of induction practice also extends towards the integration of multimodal signals (such as peripheral physiology and facial expressions) in order to check if the target affective state can be expressed uniformly across the trials, which favors temporal synchronization between subjective states and physiology targets [29]. Cross-corpus evaluation also favors stimulus calibration, as differences in the content of elicitation can contribute towards the shift problem in EEG representations of affect [30]. In addition, modern learning strategies (e.g., contrastive and self-supervised representation learning) encourage elicitation designs that produce diverse yet label-consistent trials, since representation objectives benefit from repeated exposure to comparable affective episodes under varying contexts [31]. These developments sit naturally within the continuous affect tradition, where valence–arousal modeling formalizes emotion as graded dynamics rather than rigid categories. Finally, the broader affective-computing literature shows that robust elicitation and labeling practices generalize across biosignals (e.g., ECG as well as EEG), reinforcing the view that stimulus design functions as a system-level determinant of downstream generalization [32].

2.4 Progress in Data Acquisition Technologies

The development of EEG acquisition equipment is the basis for the development of EEG-based emotion recognition research. The early study of affective brain activity mainly used research-grade EEG systems characterized by high-density electrode arrays, gel-based sensors, and shielded laboratory settings; these provide a high signal-to-noise ratio and also very accurate spatial resolution, which is a requirement for finding the cortical dynamics of emotions reliably. However, their high cost, time-consuming setup, and participant discomfort make it difficult to scale and be practical for real-world scenarios of emotion recognition. As emotion recognition research gradually shifted from highly controlled laboratory studies toward applied and real-life contexts, the limitations of traditional EEG hardware became obvious.

EEG acquisition hardware also plays a significant role in the data's quality, the model's generalization ability, and the system's feasibility for use in the real world for emotion recognition systems. Hardware




Figure 3: EEG Electrodes

factors such as EEG electrodes, channels, stability of signals, and resistance to movements also affect the reliability of the acquired feature for emotions. Emotion recognition systems trained to recognize data from research acquisition systems find it difficult to generalize and recognize signals originating from consumer acquisition systems or wireless acquisition systems for data collection. Thus, acquisition system selection is not just a design choice but now a deliberate factor in model performance between subjects, data set transferability, and feasibility for use in the real world for human-computer interaction, wearable healthcare applications, or affective computing systems.

Hairston et al., [33], in their discussion on various usability problems in conventional EEG methods used for affective computing, focus on the problems caused by the use of 'gel electrodes' and the 'lack of mobility' of the user, though these methods are sure to produce a high degree of data clarity. Debener et al. [34] present the use of mobile EEG equipment that allows for the performance of tests while performing naturalistic procedures, showing the viability of the analysis of related EEG-based emotions. Nevertheless, the raised sensitivity to motion and environmental noise is considerable. On the other hand, wearable equipment with EEG systems, including wireless transfer technology for the continuous monitoring of patients, has also been suggested by Casson et al. in [35]. Although the use of such equipment promotes mobility along with compliance in patients, the number of channels in wearable equipment tends to be reduced, which might influence the emotion classification accuracy. Grozea et al., in their article [36], develop a type of dry electrode based on a bristle to reduce gel preparation without adversely affecting signal quality. This reduces not only the discomfort in gel preparation but also improves overall signal quality through minimal head movements or extended period recording. Huang et al. [37] proposed comb-shaped active dry electrodes for improved scalp coupling. As more robust design solutions are developed for dry electrode upgradation, the increased complexity and cost of such manufacturing processes hinder their acceptability. Zhao et al. [38] explore short-calibration EEG systems with reduced channel configurations in emotion recognition, demonstrating that affective cues can be preserved even through an optimized preprocessing approach. Nevertheless, the reduced spatial resolution limits the analysis of fine-grained patterns of emotions. To compare the performance of real-time EEG signal pro-

Table 1: Association between major cerebral regions and commonly observed EEG frequency bands.

Brain region	Dominant EEG frequency bands
Frontal lobe	Theta (4-7 Hz), Beta (13-30 Hz), Gamma (>30 Hz)
Temporal lobe	Theta (4-7 Hz), Alpha (8-13 Hz), Gamma (>30 Hz)
Parietal lobe	Alpha (8-13 Hz), Beta (13-30 Hz)
Occipital lobe	Alpha (8-13 Hz; dominant), Beta (13-30 Hz)
Central (sensorimotor cortex)	Mu rhythm (8-13 Hz), Beta (13-30 Hz)
Limbic-related regions (indirect EEG influence)	Theta (4-7 Hz), Gamma (>30 Hz)




Figure 4: Bands

cessing carried out with consumer-grade devices, the paper by Mullen et al. [39] shows the impact of domain shifts due to differences in equipment and the need for effective learning schemes. OpenBCI studies [40] have shown that low-cost and open-sourced EEG data acquisition platforms are well-suited for large-scale experimentation efforts. Nevertheless, low fidelity and improper placement of electrodes are still some key barriers to achieving the goal of accurate emotional recognition.

The advancement of EEG data acquisition equipment can be seen as a good example of a trade-off balancing the quality of the data with the real-world applicability of the equipment itself. Investigational equipment maintains the ability to acquire the best quality data in terms of foundational research, but wearable-style equipment can greatly help in the scalable use of emotion recognition in real-world applications. Although the advancement in terms of the use of dry sensors, wireless data transfer, and in-data-conditioning can help in the reduction of the barriers associated with the use of the equipment itself, the process still needs the acknowledgment of the importance of the role of EEG data acquisition equipment in the emotion recognition system itself, balancing all the strategies in the process in order to achieve the most successful result in real-world use cases.

2.5 Multimodal Emotion Modeling

Multimodal emotion modeling appears as an alternative solution for the deficiencies in unimodal systems due to their susceptibility to noise and contextual variations in interpreting the emotional state [41]. Nevertheless, human emotional responses arise through various modalities such as facial, vocal, and

physical communication, which convey valuable personal affective-related communication in addition to individual sources [42]. Thus, through the process of integrating multiple sources of communication, the overall view and understanding of personal emotional state and responses remain contextual [42]. Emotion analysis in a multimodal environment merges behavioral responses such as facial, speech, text, and gesture signals with physiological signals including EEG, ECG, EMG, GSR, and respiration [43]. External behavioral responses mainly focus on actual emotional responses. EEG focuses on internal brain aspects of affective responses that are inaccessible for conscious experience [14]. EEG helps focus these responses in a temporal manner, relating them to actual emotional responses, at the neural level. They play a significant role in responding to subtle affective responses that might not be captured by other signals. The blend of EEG with the above signals helps make these responses more universally applicable.

It is reported in the literature [44] that multimodal fusion paradigms, each of which corresponds to a different level of integration of cross-modal information, such as *early*, *intermediate*, and *late*.

Chen et al. [45] investigate early fusion by combining features from EEG, facial, and speech modalities before classification; improved results are shown when feature normalization and synchronization are appropriately applied. However, early fusion is generally plagued by the growth of dimensionality as well as increased sensitivity to misalignment across modalities, complicating training and potentially degrading performance when features are high-dimensional or poorly synchronized. Kessous et al. [46] have also applied feature-level fusion in multimodal emotion tasks, where the results show that appropriate preprocessing enhances recognition but such approaches remain challenged by noise and feature heterogeneity across channels.

Proposals for intermediate fusion methods have been developed by Shin et al., [47] in which asynchronous modality combination makes use of temporal modeling and sequence alignment. Although this method improves on handling temporal discrepancies between modalities such as EEG and other modalities, it imposes additional complexity in terms of computation. Furthermore, in a different approach based on deep contextual modeling of asynchronous modalities, Liu et al. [48] utilize intermediate fusion; however, this has limitations in terms of high requirements for training data and in handling long-range dependencies.

Wang et al. [49] delve into a decision-level fusion where outputs from independently trained classifiers in EEG, ECG, and GSR are combined by weighting and voting mechanisms; this imposes greater robustness and flexibility within the inclusion of modalities. The technique avoids the rigid constraints of synchronization and also allows for the easy integration or exclusion of modalities but does not explore the deep intermodal relationships and may underutilize channel-correlated information. Soleymani et al. [41] review decision-level fusion on physiological systems and present improved generalization and discuss how feature interactions are not fully exploited.

Mittal et al. [50] have developed multimodal deep learning models that utilize attention mechanisms for modality contribution weightings depending upon their importance in a certain context, thus reducing the impact of unreliable modality contributions. Despite these models providing good contributions to this area by reducing the effects of unreliable contributions to a decision that is derived from a multimodal approach, they are still data-intensive optimization models that may not effectively succeed in the absence of available data. Priyasad et al. [51] have taken this concept a step further by developing attention-based models for multimodal fusion that have improved outcomes but are facing issues of model interpretability and increased computation.

The stability of affective patterns in multimodal datasets, such as in DEAP datasets, can improve emotion recognition according to Zheng et al., [52], although certain problems in bias and data modalities are still present. Similarly, Correa et al. [53] employ AMIGOS multimodal data sets and are successful with subject-independent improvements, although large inter-subject variation in multimodal combinations remains a problem in achieving higher results in this area. From a review paper by Ma et al. [14], where certain improvements in the specified area are discussed, it's noted that multimodal data sets are constantly more successful compared to their unimodal analogs and are working toward standardizing certain techniques in data evaluation.




Figure 5: Modalities

Multimodal emotion modeling has been identified as a development that enhances the process of affective computing by incorporating EEG along with behavioral and physiological modalities to help computers effectively address the challenges that may come about due to the utilization of a single solution to the process. Although various fusion methods have been identified to have different advantages that may come in handy during the modeling process, they present various complexities, synchronicity considerations, or robustness during a fusion evaluation process. Multimodal models have been widely recognized for their incorporation of DL to increase adaptability to different forms of diverse modalities, which may come in handy during the decision process. Even though utilizing DL may demand extensive learning resources, various literature has been published to prove that the utilization of multimodal methods is significantly superior to the utilization of unimodal methods, as confirmed by literature focusing on various multimodal datasets such as DEAP, AMIGOS, MAHNOB-HCI, or MPED datasets. From the literature, multimodal methods have been recognized as a fundamental necessity for creating an effective EEG-based modeling approach suitable for operation in a realistic human-computer environment.

2.6 EEG Correlates of Emotional States

The essential basis of deriving emotion through an EEG remains rooted in the principle of recognizing the inherent rhythmic activity occurring over the human cortex as an outcome of the processing of emotion. It must also be noted here, unlike the conventional belief, the processing of an emotion is rarely indicated through the peak intensity of the EEG signal, as the expression of emotion largely remains indicated through a combination of dynamic activity occurring over a certain range of frequency bands. These, in turn, manifest as a product of the inherent neural activity underlying the emotion possessed by a particular individual [17].

This view has driven emotion modeling from single-feature representations toward multiband, spatially distributed, and temporally evolving neural descriptions. The emerging evidence suggests that emotionality arises from the interaction of rhythmic modulation and interregional coordination, motivating feature extraction and representation strategies that explicitly capture frequency-specific activity, spatial

asymmetries, and functional connectivity.

Understanding the spectral and connectivity correlations for emotion is at the heart of how to develop efficient EEG-based emotion recognition systems. For example, frequency bands such as alpha have proved to have a certain level of consistency and subject stability of the scheme of emotions and therefore perform well to represent states of emotions for different subjects [17]. As a result, alpha bands have been deemed efficient for robust feature selection for subject-dependent and subject-independent emotion recognition systems.

Unlike alpha bands, the involvement of the beta band in emotional states, especially during heightened emotional states, is well evidenced, particularly in prefrontal regions, where a link to cognitive-emotional control parallels the involvement of arousal-related emotional regulation [54]. In addition, delta and theta bands have been found to carry complementary information, with delta band activity related to emotional salience, while theta band connectivity is related to emotional integration/coordination [55]. More importantly, emotional states are also quantified through inter-channel correlations, where larger discriminability is observed, to obtain a holistic picture of neural interactions. Using these subspaces, finer quantification of emotional states is observed based on inter-channel correlation patterns, ensuring that a discriminative emotional state is quantified over localized band power features [56]. The time alignment effect is also observed to have an essential impact on neural components based on the emotional stimuli, reinforcing its importance in maintaining neural state changes in decision-making based on affect labeling [57]. Additionally, when basing research on interpretability, there is a need to quantify emotion based on significant patterns to avoid biases in the data set, leading to the wrong neural components [58].

Meanwhile, a comprehensive collection of research on EEG-based emotion recognition was conducted and summarized by Geng et al. [17], during which the discussion focused on the characterization and importance of alpha activity when recognizing and understanding overall and general emotional dynamics and how sensitivity to emotion can benefit and possibly be enhanced through the exploration and investigation of other frequency bands, apart from the alpha band. A disadvantage and a possible drawback hidden in their discussion is the fact that these findings were summarized at a conceptual level. Sun et al. [54] introduced the dual branch dynamic graph convolutional approach that directly addresses the beta-band activities, as well as the spatial relationships among the electrodes. This model proves that the emotional intensities, including the negative arousal, are indeed significantly detected in the modulation of the prefrontal beta signals. The process remains susceptible to cognition because the beta signals are also impacted by non-emotional cognitive activities. Zhang et al. [55] proposed a multimodal functional connectivity approach that could simultaneously analyze delta, alpha, beta, and theta frequency bands. The results showed that there were significant emotion-related correlations in delta frequency bands and additional discriminative information from alpha and beta frequency bands. In a study using the correlation-based approach for various frequency bands such as alpha, beta, and gamma frequency bands. The theta frequency band contributes mainly through the connectivity measures. The limitations of the study were the absence of explicit interaction modeling, which limited the value of the approach. Choong et al. [56] have attempted to investigate the use of correlations among alpha, beta, and gamma frequency band connectivity features and how the connectivity features under this use case have accounted for the identification of relevant emotional interactions, even when these interactions do not manifest as identifiable features across individual channels. Liu et al. [57] used movie-induced affective stimuli to retain the temporal traces of neural activities and provide time-aligned labels of affective states. While this method is effective for capturing dynamic responses related to emotions, it unfortunately depends highly on the inter-subject consistency in the perception of emotions, which may not generalize well to a truly diverse population or across different cultural contexts. Qing et al. [58], on the other hand, emphasized the aspect of model interpretability with the proposed mechanisms that connect the decision process with discernible patterns present in the signal. This enables a specific approach to validate that the underlying process utilizes neurophysiologically plausible features. However, the overall level of model interpretability is still hampered by the inherent complexity.

Collectively, this set of research supports the existence of a general neurophysiological framework for

emotion states as encoded by both frequency-specific modulation, spatial organization, interregional connectivity, and even dynamics. Emotional states will be represented in the brain as an ensemble process of activity over multiple frequency bands and brain regions rather than as an expression of some global brain state. Clues provided by alpha and beta rhythms will be useful for both stability and intensity information, while salience and interregional integration will be provided by the delta and theta bands, with relational information provided by functional connectivity for differentiation among emotion states. Temporal dynamics and interpretability again increase the relative neurophysiological validity of emotion state representations to support EEG feature and modeling designs that well exceed local amplitude-based emotion recognition methods.

2.7 EEG Signal Processing (Content to be humanized)

The objective of EEG signal processing in emotion recognition is to transform the raw and noisy EEG signals into representations that are invariant to inter-subject and inter-session variability, while capturing the neurophysiological dynamics that are relevant to emotion. In this regard, the signal processing pipeline is equivalent to a series of conditioning steps that include: (i) suppression of non-cerebral noises, (ii) standardization of the temporal structure to facilitate learning, and (iii) definition of feature spaces that reveal the temporal, spectral, and spatial characteristics of emotional states. The signal processing pipeline is not just a pre-processing step, it is a critical component that determines the information that can be extracted and utilized by the models, and it affects the robustness, interpretability, and generalizability of the models directly.

Affective EEG is usually measured using a specific protocol in which the emotional response is dynamic over time. Therefore, the processing pipeline must accommodate the ability to represent transient responses (for example, early perceptual responses) and sustained responses (for example, sustained affective responses). As the datasets move away from the controlled environment, the pipeline focuses more on the resilience of artifacts and stability across domains, encouraging the use of structured denoising, segmentation, and representations that align with the current deep learning encoder models [59].

2.8 Preprocessing

The signals received through an electroencephalogram are known to be quite noisy and prone to a number of artifacts, and therefore preprocessing is an essential step for the recognition of emotions through EEG signals. The preprocessing step is concerned with the cleaning and preprocessing of the raw EEG signals to improve their quality and normalize the input signals for the subsequent steps of feature extraction and classification. The preprocessing of EEG signals is an essential step for improving the SNR of EEG signals and removing external noise and artifacts such as power line noise and physiological artifacts such as eye blinks and muscle movements for better performance of the classification model for emotion recognition. It is thus important to apply proper filtering, artifact removal, normalization, and other cleaning procedures before the feature extraction step. Moreover, the use of similar preprocessing procedures such as the use of similar filters and scaling helps to eliminate variability and errors in the comparison of signals from different domains. Below, we discuss a variety of critical preprocessing procedures and approaches used in recent studies on EEG-based emotion recognition.

2.8.1 Filtering and Noise Reduction

The process of filtering and noise reduction is one of the fundamental steps in the preprocessing of EEG signals, in which the raw EEG signals are cleaned of various types of non-neural artifacts while keeping the relevant neural components. The EEG signal is very susceptible to external and internal noise, and thus filtering is critical in ensuring that the final signal is indicative of the cognitive or affective processes in the brain instead of other unwanted processes.

The filtering process is of utmost importance in the context of emotion recognition using EEG signals. Emotional states in the brain have very subtle effects in the standard EEG frequency bands, including

delta (δ), theta (θ), alpha (α), beta (β), and gamma (γ). However, these effects can very easily get buried under unwanted effects caused by low-frequency drifts (such as skin potentials or sweating), high-frequency muscle movements (EMG), or electrical noise such as power line noise.

The noise reduction techniques that are generally used are band-pass filtering for restricting the noise band to biologically relevant frequency ranges, notch filtering for eliminating noise components present at particular frequencies such as 50 Hz or 60 Hz, and spatial filtering for reducing the effect of noise artifacts. The more complex noise reduction techniques may include complex filtering methods such as regression analysis for reducing noise artifacts and blind source separation for reducing noise components. The type of filtering used, i.e., linear filtering, Butterworth filtering, and Chebyshev filtering, is important for avoiding phase distortion of emotional responses.

Even with these techniques, it is difficult to achieve an optimal SNR. The filtering techniques are such that they can eliminate genuine low or high frequency components of brain activity, which are characteristic of emotions. It is therefore critical to properly calibrate and validate filtering techniques to optimize noise reduction while preserving relevant features of the signal.

2.8.2 Artifact Removal

Although filtering can remove a wide range of spectral artifacts in EEG, it is sometimes inadequate to deal with non-stationary, physiological artifacts that may be generated by eye blinks, eye movements, facial muscles, and jaw activity. These artifacts may introduce sudden and large amplitude artifacts that can severely contaminate the EEG signal, especially in frontal and temporal areas that are very important for affective processing. Hence, an additional step for the removal of such artifacts is necessary to ensure that the brain activity associated with emotions is not masked by the presence of such spurious signals.

In the case of EEG-based emotion recognition, the need for effective artifact removal is even more important because of the fine-grained nature of the emotional state indicators in the neural activity. A single blink or facial movement can introduce amplitude spikes or frequency distortions that can dominate the weaker emotional signals in the data. Moreover, because emotional stimulation often involves visual or auditory stimuli, the presence of these artifacts is more likely during experimental procedures.

The general objective of artifact removal techniques is centered on separating and reducing these non-neural components without eliminating important brain activity. Blind source separation, as well as Independent Component Analysis (ICA), may be used in separating the EEG signals into statistically independent components. Components that may contain artifacts may then be reduced in intensity or removed from the signal. Other approaches may also be employed, like regression-based correction, auxiliary channels like EOG, and machine learning algorithms that may be trained in identifying patterns of artifacts.

While these artifact removal techniques are effective in improving the clarity of the signal, there are certain limitations that may be encountered in using these techniques, such as subjectivity in recognizing certain components of the signal, eliminating important brain activity, as well as the computational costs that may be required in real-time analysis. This has also spurred certain research into developing automated systems that may be able to effectively separate artifacts from important activity, especially in emotion-related analysis where signal clarity is important.

2.8.3 Hybrid ICA-Wavelet Techniques

Although the effectiveness of pure methods such as ICA or wavelet transform may be extremely high for removing certain types of noise from the EEG signals, the use of combinations of such techniques may prove to be even more effective. Recently, the use of hybrid models of ICA and wavelet transform techniques has been proposed as an effective tool for the cleaning of EEG signals. The use of such techniques may prove to be extremely effective for the cleaning of EEG signals, especially in the context of emotion recognition, where the neural patterns are extremely subtle and are highly susceptible to being affected

by various types of noise such as those due to eye blinks, muscle movements, etc. The use of such techniques may help in the cleaning of the EEG signals without affecting the emotional content.

In the area of emotion recognition, where the patterns of neural activity associated with emotional states are delicate and vulnerable to distortion by eye blinks, muscle activities, and external noise, these hybrid models can be particularly useful. These models open up the possibility of removing artifacts without damaging the emotional information conveyed by neural activity. As EEG-based affective computing systems become more sensitive and widespread, the need for automatically filtering physiological noise becomes more pressing.

Generally, hybrid ICA-Wavelet approaches begin by carrying out a statistically independent component analysis of the EEG data, which helps in the separation of the neural and non-neural components. Instead of completely removing the independent components identified as noisy, as is the case in ICA, the hybrid ICA-Wavelet approach uses wavelet analysis for the separation and elimination of the noisy components. This ensures that the final clean data include only the required components of the brain activity. This type of analysis, which considers space as well as time, is significant in dealing with the complexity of real-world data.

Although these hybrid ICA-wavelet methods are promising, certain trade-offs are also involved in their implementation, which may limit their performance depending on the type and amount of artifacts in the data, as well as the type of wavelet functions and levels of decomposition that are used in the process. Nevertheless, the impact that these hybrid methods have shown in improving classification performance in EEG emotion recognition systems shows their potential as an advanced preprocessing technique.

2.8.4 Channel Selection and Spatial Filtering

Channel selection and spatial filtering form part of the basic preprocessing mechanisms that focus on improving signal quality by optimizing the spatial representation of the EEG signal. Rather than considering all channels of the signal, these mechanisms focus on the most important parts of the scalp while avoiding the effects of noisy and irrelevant channels. This becomes particularly important when dealing with emotion recognition via EEG signals, where emotion signals tend to be localized and easily obscured by irrelevant neural and physiological activities.

In affective computing, it has been found that the selection of important regions of the brain, particularly those that exhibit emotion, such as the prefrontal and temporal regions, can significantly improve emotion classification. By selecting a specific subset of the electrodes, it becomes possible to reduce dimensionality, eliminate noisy channels, and simplify the process. Spatial filtering improves the clarity of the signal by re-referencing the EEG signal and eliminating global noise components, thus enhancing the signal corresponding to localized neural patterns of emotion.

Several strategies are used in this context. For instance, manual or data-driven channel selection methods are used for prioritizing certain electrodes based on neuroscientific knowledge or feature contribution metrics. This ensures that only discriminative channels are used in the process. Spatial filters like CAR and Laplacian filtering are used for reducing reference bias and eliminating common-mode noise. These filters are used for normalizing the EEG inputs for different channels and for highlighting spatial gradients that are related to emotional processes.

While these strategies are useful in several ways in terms of reducing computational requirements and improving robustness, they are not without their limitations. For instance, too much reduction of channels in this context would lead to the loss of emotional signals that are spatially distributed. Spatial filters would lead to signal topography distortion if not used properly.

Table 2: Representative studies on EEG preprocessing techniques for emotion recognition.

Study	Approach	Preprocessing Method	Advantages	Limitations	Key Findings
Somers <i>et al.</i> [60]	Multi-channel Wiener filtering for artifact suppression	Artifact Removal	Preserves neural signal while reducing ocular/muscle noise	Needs covariance estimates; less effective for nonstationary noise	Improves EEG signal quality before emotion decoding
Kang <i>et al.</i> [61]	ICA with heuristic artifact-aware rejection	Artifact Removal	Effectively isolates and removes major EEG artifacts	Manual component selection may reduce reproducibility	Boosts classification accuracy post-cleaning
Phadikar <i>et al.</i> [62]	Wavelet thresholding for blink artifact removal	Artifact Removal	Fast and adaptive for blink noise	Limited to blink artifacts; not general-purpose	Strengthens EEG robustness in emotion pipelines
Koelstra <i>et al.</i> [63]	Bandpass filtering with baseline normalization	Channel Selection and Spatial Filtering	Reduces noise and inter-subject variability	Requires baseline segment; may remove useful bands	Improves single-trial emotion classification
Mahajan & Morshed [64]	Wavelet-enhanced ICA artifact removal	Hybrid ICA-Wavelet Techniques	Automated ocular artifact suppression	Mainly targets eye-blink artifacts	Enhances EEG quality for emotion analysis
Val-Calvo <i>et al.</i> [65]	Lightweight real-time preprocessing pipeline	Channel Selection and Spatial Filtering	Low-latency and computationally efficient	Simplified features limit generalization	Enables real-time EEG emotion recognition

2.8.5 Feature Extraction

The process of feature extraction transforms the preprocessed EEG signals into a form where emotion-related features become more easily separable. The most important assumption is that affective neural responses occur collectively in time, frequency, and scalp space. Hence, features relevant to emotions cannot be found in a single domain. Feature extraction techniques can generally be divided into two classes: (i) explicit representations, where features can be derived from signals, and (ii) learned features, where deep models learn features from raw or minimally preprocessed EEG or engineered features. The most important trend in EEG-based emotion recognition is the development of structured, model-friendly tensor representations that keep track of inter-domain dependencies. Thus, rather than obtaining separate features for each channel, as in traditional feature extraction, recent pipelines often compute 2D or 3D objects, such as channel $\times$ time, channel $\times$ frequency, or time $\times$ frequency maps per channel, so that CNNs can take advantage of local features. Another trend is based on 3D feature representations along with fully convolutional models, where temporal, spatial, and spectral information is treated as a unified entity, eliminating the need for inter-domain fusion and enabling end-to-end learning of inter-domain interactions [66].

Sequential feature construction is also common due to the temporal nature of emotional responses. Sequential feature construction is also very common due to the nature of emotional responses. Spatial-temporal features can be constructed by stacking window-level features and using sequence models like bidirectional recurrent units to model temporal dependencies among windows. This approach maintains local temporal information while also modeling long-term affective dynamics, which is important when the emotional episodes develop gradually rather than suddenly [67].

Moreover, transformer-aided feature construction can facilitate cross-domain features, as it does in attention-driven fusion. Architectures based on conformer, which integrates convolution for local pattern detection and transformer attention for global interdependency detection, can provide a useful tool for constructing features as local patterns or global connections without resorting to predefined fusion strategies [68]. Additionally, the parallel use of transformers and 3D convolution is also seen to be following the same principle, where the role of the transformer is to identify interdependencies, while the role of 3D convolution is to identify structurally well-defined spatiotemporal relationships that are associated with Emotion concepts [69].

In the majority of emotion recognition systems based on the EEG, the frequency domain features are

used, which are derived from the preprocessed signals. Some of the commonly used features, such as power spectral density (PSD) and differential entropy (DE), are widely used to represent the EEG signals in emotion recognition systems. The power spectral density features represent the power of the signal in standard bands such as theta, alpha, beta, etc., which indicates the amount of rhythmic activity present in the signal in the respective bands. The concept of differential entropy is related to power spectral density, but when we consider a Gaussian distribution of the EEG signal amplitude in a short period of time, the differential entropy h can be expressed as

$$h = \frac{1}{2} \ln(2\pi e, \sigma^2), \quad (1)$$

where σ^2 is the variance of the signal. Note that variance is proportional to signal power in the window, and thus DE is a log-power feature. In effect, calculating DE on an EEG epoch will give a value that is proportional to the signal power in the epoch and can be calculated on a band-by-band basis so, DE for delta, theta, etc. can be calculated in a manner similar to calculating band power.

The power spectral density (PSD) and differential entropy (DE) are popularly used in EEG-based emotion recognition systems, as they are effective in capturing the characteristics of brain signals related to emotions in the frequency domain. Out of these, DE is regarded as a better alternative to power-based features, owing to its numerical stability and normal distribution. The spectral features, in general, tend to be extracted from various bands of brain signals, including delta, theta, alpha, beta, and gamma bands. These features offer a compact representation of signals, which is of a fixed length and can be readily incorporated with ML. Among the advantages that make PSD or DE features noteworthy is that these features remain unaffected by any timing differences that might be present in a trial. In addition, these features, once appropriately filtered, tend to be somewhat immune to high-frequency noise. Yet, by averaging the power over a time window, these features might overlook significant information regarding the dynamics that occur over a more limited period. Additionally, the stationarity of the signal over a given period might be a concern if the emotional changes do not occur uniformly over the course of the stimulus presentation. Ultimately, with regard to these issues, the parameters for the window size, overlap, and frequency resolution must be adjusted properly. While these measures have limitations, the PSD and the DE remain core components in the study of affective EEGs, often providing a foundation for more intricate models.

In summary, the preprocessing step is an essential constituent of the EEG-based emotion recognition approach, which has a direct bearing on the reliability of the results. As can be observed across the literature, there has been an increasing trend towards the development of sophisticated and automatic preprocessing methodologies. For instance, the initial research studies employed basic filtering and manual removal of artifacts, but the latest research studies, including the ones discussed above, have employed sophisticated methods like ICA cleaning, wavelet denoising, and automatic channel selection to clean the EEG signal. The general idea is that the better the signal quality, the better the model will perform. Another trend observed across the literature is the standardization of the preprocessing methodologies. For example, the data of different subjects or sessions is often passed through the same filtering and feature extraction processes. As the quantity and quality of EEG emotion data increase, and the need for online processing of the data for real-world applications emerges, the preprocessing techniques are shifting towards the development of real-time capable preprocessing methods, reducing the dependency on manual intervention during the process. In the future, the preprocessing techniques are expected to continue the progression towards the inclusion of newly emerging signal processing techniques for the improvement of the quality of the EEG data, thus providing a solid base for the accurate and robust recognition of emotions using brain signals, as the best classifier can only perform as well as the data it is provided with.

Temporal, Frequency, and Spatial Feature Concepts & Cross-Domain Feature Fusion The nature of electroencephalogram (EEG) data is inherently multi-domain: temporal, frequency, and spatial. Each of these domains represents different aspects of brain activity. The temporal domain represents the evolution of brain activity over time, which can be achieved by dividing the EEG signal into time intervals or




Figure 6: Temporal vs Frequency vs Spatial Domain

by employing time series analysis (using windowing techniques). Features in the frequency domain are achieved by transforming the EEG signal (using Fourier transform) and analyzing the signal's power in specific frequency bands: δ (1-3 Hz), θ (4-7 Hz), α (8-13 Hz), β (14-30 Hz), and γ (30-50 Hz). Note that different frequency bands are associated with different levels of emotional content: previous studies have shown that specific frequency bands (beta, gamma) are more active during specific emotional content. One of the frequency domain features is differential entropy (DE), which is defined as

$$H(X) = \frac{1}{2} \ln (2\pi e \sigma_X^2) \quad (2)$$

where σ_X^2 is the variance of the signal in the band. Features from multiple bands of the DE provide a compact representation of the EEG signal spectrum, which is useful in emotion recognition. The spatial features aim to capture the distribution of the EEG signal in the brain. For example, it is possible to compute the inter-channel correlation matrix R , which can be defined such that the $(i, j)^{th}$ element is the Pearson correlation r_{ij} between the i^{th} and j^{th} channels,

$$r_{ij} = \frac{\text{Cov}(x_i, x_j)}{\sqrt{\text{Var}(x_i) \text{Var}(x_j)}} \quad (3)$$

which is the adjacency matrix for the graph representation of the spatial features. Thus, the EEG signal provides multi-domain features: the dynamics of the signal over time, the spectral features of the signal, and the spatial distribution of the signal over the cortex. These are called multi-domain features, and the use of all three can provide a holistic view of the emotional state.

Each of these features provides supplementary information for emotion recognition from EEG, and their combination will result in stronger and more accurate emotion recognition models. Temporal features reflect the dynamic nature of emotional responses and their variation. Emotions are processes that depend on time. For example, emotional arousal increases and then decreases over time. Frequency features focus on specific frequency bands of neurophysiological responses that are related to emotional processes. For example, alpha or beta band power increases reflect relaxation or higher engagement. Spatial features reflect emotional processes in specific brain regions. For example, frontal alpha asymmetry is known to reflect affective valence. This is because these three aspects are complementary, and hence their combination can compensate for the limitations of any of these individual feature types. In fact, empirical studies have demonstrated that models that use combined temporal, spectral, and spatial representations outperform those that use individual types of these features. In particular, spatial features are often combined with temporal or frequency features to provide context about where in the brain particular types of temporal or spectral patterns are present. The combination of multiple types of features from multiple domains, therefore, creates a more comprehensive representation of the EEG signal, which can potentially improve accuracy and robustness of emotion recognition against noise or variation.

Fusion is achieved using various architectural styles. First, *tensor fusion* involves the creation of multi-dimensional input representations (e.g., 3D tensors) that enable an encoder network to learn interaction patterns implicitly. Second, *multi-branch fusion* involves the use of dedicated encoders for each domain (temporal, spectral, and spatial) and subsequent fusion of intermediate representations. Third, *attention-based fusion* leverages adaptive weightings that highlight the most relevant domain or channel representations depending on varying noise conditions. The use of a dual-branch dynamic graph convolution and adaptive transformer fusion presents an example of the potential for using spatial reasoning and attention-based fusion mechanisms that leverage inter-channel relationships and remain adaptive in feature weightings [70]. For multi-domain EEG encodings, transformer networks are also developed that take in representations from various feature spaces and learn to fuse these using self-attention [71].

Temporal Domain Features: Temporal domain features play a critical role in emotion recognition systems that use EEG as a medium, as emotions are dynamic experiences that change over time. Emotions are dynamic experiences that change over time and are often composed of a series of neural events that can't be described by time-independent features. Temporal features help the emotion recognition system understand how brain activity is changing over time as a response to an emotional stimulus. These features are critical in handling intersubject variability in the timing of the emotion recognition response, as they help the system concentrate on the timing of the signal rather than relying on synchronous stimuli and labels.

Within the emotion decoding paradigm, temporal modeling has been integrated using a variety of deep learning approaches that have taken advantage of the strengths of sequence learning. As an example, recurrent models such as LSTMs or bidirectional RNNs have been widely used to capture the dependencies between successive segments of the EEG signals, modeling the temporal dynamics of affective states. In other instances, hybrid models have been proposed that take advantage of the strengths of both convolutional and recurrent models to learn the spatial patterns and their temporal dynamics. In addition, hierarchical sequence models have been proposed that learn the signals regionally and then aggregate them globally, thus preserving the spatial patterns while modeling the temporal dynamics. Finally, temporal convolutional models have been proposed that offer an alternative to recurrent models, enabling the modeling of long-range dependencies using hierarchical, dilated convolutional architectures.

Although these methods are useful in terms of the recognition of dynamic patterns of emotion, there are challenges that are associated with these methods. These challenges include difficulties in integrating frequency and spatial information or the use of uniform timing. The selection of appropriate window length and temporal resolution is also important in temporal domain modeling. This is important for the avoidance of overfitting or the loss of relevant information, particularly for the improvement of the performance of emotion recognition, especially for naturalistic or continuous emotional scenarios where there is the presence of individual variations of emotional expression timing.

Frequency Domain Features: The features identified by the frequency domain have proven to be a promising approach to study the rhythmicity of the EEG signals, which are closely related to the emotional processes of the human brain. These features have enabled researchers to study the power distribution of the EEG signals over standard frequency bands such as alpha, beta, theta, or gamma waves, which are known to be influenced by emotional processes. Unlike features in the time domain, features in the frequency domain offer a more consistent representation of rhythmic activity in the brain, which is known to endure over sessions and subjects, especially if the EEG signals are appropriately filtered.

Features in the frequency domain are critically important in emotion recognition models, as these offer a means to explore the power in EEG signals in certain bands that is linked to emotional processes, as supported by neurophysiological studies. For example, increased power in the beta frequency band in frontal areas of the brain is known to be related to increased emotional arousal, while power asymmetries in the alpha frequency band are related to valence changes. These features are not easily influenced by timing jitter or noise in EEG signals, which makes them appropriate for real-world EEG-based emotion recognition models.

Several methodologies have been explored for the effective modeling of frequency domain features. For instance, in some methodologies, the EEG signals were converted into spectrograms using various tools such as the STFT, allowing deep learning models to effectively learn the relative contribution of frequency domain features [72]. In other methodologies, the band power and differential entropy were considered as feature inputs, allowing the model to effectively capture the spectral content of each channel. More recent methodologies have also been explored, allowing the model to effectively capture the spectral relationship between channels using tools such as the convolutional model and attention mechanism [68]. In addition, multi-domain models have also been explored, allowing the model to integrate frequency domain and temporal domain representations for improved emotion recognition accuracy [73].

However, frequency domain modeling for emotion detection with its emphasis on consistent rhythmic patterns has its own set of limitations. For example, there is a need for balance in terms of spectral resolution and computational efficiency. In addition, the parameters of transformations such as STFT are critical and may affect the overall model. Moreover, frequency domain modeling may not account for other dynamics that are critical in decoding complex emotion responses.

In summary, frequency domain features form an essential pillar in EEG-based emotion recognition systems. They are reliable and highly correlated with other emotion-related features. In addition, frequency domain modeling with other domains forms an essential tool in modeling complex affective states with neurophysiological meaning [73, 68, 72].

Temporal-Frequency Domain Features: Frequency domain features are the core of emotion recognition using EEG, as they are based on the rhythmic patterns of the brain's electrical activity, which are directly related to emotional states. The rhythmic patterns of the electrical signals in certain bands of frequencies, such as the delta band (1-4 Hz), the theta band (4-8 Hz), the alpha band (8-13 Hz), the beta band (13-30 Hz), and the gamma band (30-50+ Hz), are known to relate to various aspects of emotion. For instance, the power of alpha and beta rhythms is known to relate to the level of arousal and the valence of emotion. The asymmetry of alpha power in the frontal region is known to relate to approach/withdrawal aspects of emotion. Frequency-specific modulations are generally consistent across subjects and sessions, and hence are useful indicators of emotion classification.

In practice, the analysis of the electrical signals in the frequency domain is achieved through various techniques such as the Fourier transform, the wavelet transform, and the differential entropy method. The above techniques are used to transform the raw electrical signals to a more compact representation. The compact representation is useful because the electrical signals are more susceptible to noise.

Recently, various modeling techniques have adopted frequency domain features in different ways. In some models, frequency domain feature extraction has been performed independently, and the extracted features have been combined with temporal or spatial features to obtain enhanced emotion-specific information. In other models, convolutional or attention-based encoders have been employed to extract frequency domain features, which have been treated similarly to visual inputs to learn abstract frequency domain representations. In addition, various models have utilized graph-based reasoning to extract frequency domain feature-encoded nodes to identify inter-band relationships and regional patterns.

Even though frequency domain-based models have shown promising performance, various trade-offs have been identified in their performance, including sensitivity to the parameters of the decomposition and windowing techniques employed in the models. In addition, models that have adopted frequency domain-based features may overlook essential temporal patterns, thus failing to accommodate different subjects with varying frequency domain patterns. Nonetheless, frequency domain-based features have shown promising performance when combined with other features to provide robust brain state oscillatory patterns and improve emotion recognition systems.

Integration and Fusion Strategies Across Feature Domains: The integration of temporal, frequency, and spatial features has emerged as a primary concern in EEG-based emotion recognition, owing to the multidimensional nature of emotional brain responses. These features describe emotional responses from different but complementary perspectives, where temporal features describe the dynamics of brain re-

sponses, frequency features describe brain responses in terms of oscillatory properties, and spatial features describe brain responses in terms of brain regions. Emotion expression in the brain does not occur in individual channels or frequency bands but occurs through interactions across multiple brain responses. Therefore, brain responses that combine multiple views are more expressive and tend to generalize better across subjects and sessions.

The importance of multi-domain fusion becomes critical when handling noisy or uncertain EEG signals. There are scenarios where one domain may not contribute much or may be noisy, such as noisy temporal responses owing to movement, but brain responses in other domains can serve as a fallback, ensuring that fusion-based methods are more robust, especially when handling real-world or cross-subject scenarios.

However, recent developments in multi-domain fusion architectures have focused on flexibility and adaptability. Many of these methods involve multi-branch architectures in which domain-specific feature extractors process temporal, spectral, and spatial information in parallel, followed by fusion layers that combine the features. Some of these methods involve graph convolutional networks (GCNs) to represent spatial relationships between EEG channels, combined with temporal-frequency encoders. Others involve attention mechanisms to dynamically assign weights to features across domains according to their relevance to the emotional state.

There is also an emerging trend towards deeper architectures that learn their own fusion policies implicitly. These include transformer-based feature encoders with domain-specific attention mechanisms and approaches with masked modeling for cross-domain reconstruction. These are very powerful architectures. However, they tend to be computationally expensive, requiring significant memory and regularization during training to avoid overfitting. Moreover, they also present difficulties with regards to their interpretation, as it is not clear what contribution each of the different domains makes towards the overall emotion prediction.

To recapitulate, the integration of various EEG domains can improve the model's ability to learn discriminative and generalizable representations of emotions. Fusion techniques can provide better modeling of emotional patterns, handling of noise, and stability of cross-subject models. Although the above techniques provide considerable benefits, the trade-off needs to be managed for the handling of computational complexities and the interpretability of the models. It is believed that future research will concentrate on the development of more lightweight, interpretable, and data-efficient fusion techniques that can provide the benefits of multi-domain integration.applications.

Table 3: Representative studies on EEG feature extraction techniques for emotion recognition.

Study	Approach	Domain Category	Advantages	Limitations	Key Findings
Li <i>et al.</i> [66]	3D spatial-temporal-spectral features with FCNs	Spatial-Temporal-Spectral	Combines rich domain information in unified volume	Heavier computation than 2D encodings	Improves accuracy across datasets
Lew <i>et al.</i> [67]	Spatiotemporal encoding with Bi-GRU	Spatial-Temporal	Captures evolving emotion responses	Sensitive to segmentation granularity	Better for gradual emotion transitions
Song <i>et al.</i> [68]	Conformer model for EEG sequences	Spatial-Temporal	Fuses local and global patterns effectively	Can overfit without regularization	Outperforms traditional CNN/RNN models
Jia <i>et al.</i> [74]	3D DenseNet with attention across domains	Spatial-Temporal-Spectral	Learns dynamic relevance between features	Model complexity is high	Salient EEG areas enhance emotion decoding
Sun <i>et al.</i> [69]	Parallel transformer + 3D CNN fusion	Spatial-Temporal	Separates local/global representation branches	Careful tuning required for balance	Shows strong performance on multi-channel inputs

Continued on next

Table 3 continued

Study	Approach	Domain Category	Advantages	Limitations	Key Findings
Yudhana <i>et al.</i> [75]	FFT-based spectral features with <i>k</i> NN classifier	Spectral	Simple and computationally efficient	Ignores temporal dynamics; limited scalability	Shows the viability of classic frequency features
Chen <i>et al.</i> [76]	Differential entropy features with LDA projection	Spectral	Compact and discriminative spectral representation	Linear assumptions limit expressiveness	Improves valence and arousal classification
Bigirimana <i>et al.</i> [77]	Multi-class CSP spatial filtering	Spatial	Enhances emotion-specific spatial patterns	Sensitive to non-stationarity and subject variation	Boosts multi-class EEG emotion accuracy

The table 3 presents an overview of the various EEG feature extraction methods that have been used for recognizing emotional states. In particular, it categorizes the different feature extraction methods or paradigms according to the type of signals used to construct them: either based on the spectral or spatial domains. The predominant early and light feature extraction methods were primarily based on spectral representation of the signals through the use of the Fourier transform or differential entropy. On the other hand, the predominant features extraction paradigms in the spatial domain were based on filtering techniques that utilized common spatial patterns as the basis for classification.

There is increasing use of these hybrid spatial-temporal-spectral representations in current research, due to their ability to accurately capture the complex and nonlinear characteristics of emotions associated with brain activity. Methods that use three-dimensional feature volume representations, attention-based methods, and deep learning architectures (convolutional or transformer-based) all combine multi-modal data across domains to produce better, stronger and more precise emotion decoding results. Spatiotemporal sequence modeling methods, such as Bi-GRU and conformer based models use time to encode how emotions are thought to change continuously over time while maintaining the spatial aspect, and have been shown to be very effective for this purpose. The trade-off for these benefits, however, is typically an increase in computational costs and potential for overfitting.

Overall, the progression represented in Table 3 demonstrates a distinct shift towards unified, or so-called multi-domain, deep representations, further emphasizing the significance of so-called joint spatial, temporal, spectral features in modern emotion recognition paradigms based on EEG technology.

2.9 Feature Selection

In emotion recognition datasets using electroencephalogram (EEG) signals, datasets contain high-dimensional feature vectors, including a high number of channels as well as different frequency band features. At the same time, several datasets contain a relatively low number of instances compared to the high dimensionality of the dataset. As a result, there is a great tendency for the occurrence of the curse of dimensionality, which may cause models to overfit as well as possibly ignore several relevant features in the dataset, which often reduces model efficiency as well as generalization of the classifier. Feature selection is one of the main concepts in pattern recognition as well as machine learning that helps reduce a high number of features in a dataset, containing only the most efficient as well as unique features, which can help in improving the efficiency of a classifier in pattern recognition as well as in improving the efficiency of the machines used [16].

2.9.1 Filter Methods

Filter-based feature selection is one of the most used feature selection techniques in EEG-based emotion recognition systems. This is mainly because of its relative ease of implementation, speed, and classifier-agnostic nature. Filter-based feature selection approaches attempt to measure the significance of the features before actually training a classifier. Hence, these are generally employed as a pre-processing step

of the machine learning pipeline to reduce dimensionality and improve the learning efficiency of downstream classifiers.

The relevance of the filter method is determined by the nature of EEG data, which is usually characterized as being both high-dimensional and noisy in nature. There is usually an involvement of emotion-related features as well as other features in a pool of redundant and irrelevant information. Filtering out these less informative features at an early stage enables filter approaches to build better classification performance, reduce overfitting, and improve interpretability. This is particularly significant for EEG-based emotion recognition tasks.

There are many different filter-based methods for selecting good features. Two examples of filter selection methods are correlation-based selection and mutual information (MI) selection. A correlation-based method examines the correlation between each feature and the emotional label it is related to in order to find all of the features that have a high correlation with the individual emotional labels and the overall target emotion label. In an MI-based method, the MI score of each feature is calculated with respect to the associated target label as well as with respect to all other features, to assess the relevance and redundancy of each feature. Similarly, each feature in the mRMR framework is evaluated based on its MI to the target label as well as its MI compared to all other features. The purpose of the mRMR framework is to identify a small, non-redundant collection of features that provide the most information when identifying emotion labels. Extensions of the mRMR framework have been developed that incorporate methods such as sequential forward search or floating search, allowing for a larger, more exhaustive search of the feature space with improved efficiency.

Filter-based methods have certain inherent limitations; they may produce suboptimal subsets of features when there are emotional patterns throughout multiple feature combinations or only when comparing each feature separately and independently. Therefore, the subset of features determined by filter methods will not always correspond to an optimal decision boundary that a classifier might find in an EEG-based emotion recognition system, and so may lead to poor classification performance when classifiers use the features selected from the filter methods. However, filter methods remain viable techniques for EEG emotion recognition systems because of their large-scale ability to apply to general tasks and their ability to be generalized.

2.9.2 Wrapper Methods

Use of wrapper-based feature selection provides an effective method for determining which EEG features are the most informative for classifying emotions; however, the wrapper method is generally more computationally expensive than the filter method. Filter methods assess individual features based on their characteristics or quality, whereas wrappers utilize a learning algorithm when performing the selection process. Therefore, wrappers can assess how well various combinations of features perform during the actual classification process, providing a more tailored and often higher-performing set of features.

The utility of the wrapper method within the context of EEG emotion recognition is due in part to the fact that EEG features exhibit complex interactions and nonlinear relationships between them, which is especially prevalent in affective EEG data. Affective EEG data representations tend to display and reflect subtle emotional responses, which may occur simultaneously/ly across many different brain regions and frequency bands, making it necessary to identify interdependencies between EEG features. Given that the wrapper method assesses combinations of the EEG feature subset's performance as a whole, it allows the evaluation and optimization of all combinations of the EEG feature subset for performance on a specified classifier.

Multiple methods showcase the wrapper method. An established technique, Recursive Feature Elimination (RFE), works by sequentially eliminating some of the least effective features, based on how much they influence the classifier's weight or accuracy, thereby refining the size of the feature subset over a series of iterations. Another increasingly popular evolutionary technique, Genetic and Differential Evolution, is used to systematically explore the very large EEG feature space effectively. The feature candidates are continuously evolved from iteration to iteration by simulating biological functions, such as mutation, selection, and cross-over; the evolution process is monitored using the classifier's ability to val-

idate each of those combinations for maximum performance. These methods ultimately produce very effective combinations of features that will contribute to the increased performance and generalizability of emotion recognition across different subjects.

Despite these advantages, the wrapper methods also have their challenges. Their requirement to train the classifiers multiple times as different feature subsets are examined makes the process computationally expensive; this is particularly true when the feature set is large and/or when a computationally intensive classifier is selected for training on the feature set. As such, wrapper methods may not be very useful for practical real-time or resource-constrained scenarios. Another challenge is the possibility of overfitting due to inadequate regularization of the evaluation metric for selecting subsets of features, or when the feature selection method is too closely bound to the specific dataset used for its selection. Nevertheless, wrapper methods continue to remain viable methods for identifying high-quality subsets of features that will enhance emotion recognition for EEG applications.

Table 4: Representative studies on EEG feature selection techniques for emotion recognition.

Study	Approach	Feature Selection Method	Advantages	Limitations	Key Findings
Xu <i>et al.</i> [78]	Orthogonal regression for pairwise redundancy reduction	Embedded	Removes overlapping features, boosts relevance	Assumes linearity in correlations	Improves generalization across individuals
Kannadasan <i>et al.</i> [79]	Differential evolution for feature subset selection	Wrapper	Searches compact, accurate feature sets	Evolution search is slow at scale	Increases classification stability in DEAP
Liu <i>et al.</i> [80]	EMD with optimal subset evaluation	Wrapper	Efficient combination of decomposition and selection	EMD results vary with input noise	Smaller feature sets yield higher accuracy
Wang <i>et al.</i> [81]	NMI-based EEG channel selection	Filter	Reduces redundancy and sensor count	Subset may vary across subjects	Preserves accuracy with fewer channels

2.10 Challenges and Strategies in EEG Data Handling

Single-modal EEG emotion recognition remains constrained by practical data-handling issues that directly influence generalization, reproducibility, and deployment. Two recurring bottlenecks are (i) redundant or weakly informative feature sets that inflate model capacity requirements and (ii) limited labeled samples that encourage overfitting and unstable training. Recent work, therefore, treats data handling as a co-design problem, where feature selection, augmentation, and generation are integrated into the learning pipeline rather than being optional post-processing steps.

2.10.1 Feature Redundancy

Feature redundancy arises when handcrafted descriptors (or even learned embeddings) contain overlapping information across channels, bands, and time windows, so that many dimensions contribute little beyond correlated noise. Redundancy is especially common when multiple feature families are stacked (e.g., entropy- and spectrum-derived statistics computed per channel) and when spatial neighborhoods yield near-duplicate summaries. A common mitigation strategy is explicit feature selection using filter, wrapper, and embedded schemes, which retains a compact subset while controlling inter-feature dependence.

Redundancy-aware selection increasingly moves beyond simple ranking toward objective functions that penalize pairwise overlap. For example, orthogonal-regression-based formulations incorporate redundancy into the optimization target to suppress mutually dependent predictors while maintaining discriminative utility. A representative direction improves flexible sparse orthogonal regression by adding pairwise redundancy terms into the loss so that the selected subset is simultaneously compact and decorrelated [78]. Complementary work frames selection as a population-based search problem, where differential evolution explores feature subsets under cross-subject constraints to reduce duplication while preserving

affect-relevant variability [79]. More recent orthogonal-regression pipelines further combine regression and feature weighting, encouraging sparse, high-utility feature sets that reduce the effective hypothesis space in small-data settings [82].

2.10.2 Limited Data Challenges

EEG emotion datasets typically remain modest in subject count, session diversity, and label density, and labels are expensive because they require carefully controlled elicitation protocols and reliable affect annotation. When deep models are trained on such limited samples, they often latch onto subject-specific idiosyncrasies or session artifacts, which weakens cross-subject portability. Practical pipelines therefore adopt two complementary strategies: (i) augmenting available samples through label-preserving transformations and (ii) generating additional samples via learned generative models.

Augmenting Data Samples Data augmentation creates new training instances by transforming existing trials while maintaining their emotion labels. For EEG, effective augmentation typically respects signal structure (temporal continuity, channel topology, and latent source composition) rather than applying generic image-style perturbations.

Decomposition-driven augmentation is one established approach. Independent Component Analysis (ICA) can separate latent sources, enabling augmentation in component space and reconstruction back into sensor space; this allows recombination-based operations that preserve physiologically plausible structure while increasing trial diversity [61]. Likewise, the Empirical Mode Decomposition (EMD) technique may, through the process, derive the Intrinsic Mode Functions (IMFs), for which the selection process that preserves the high correlation with the waveforms may lead to the new samples [83].

Augmentation also supports semi-supervised regimes where labeled data are scarce. A typical pattern injects weak/strong noise perturbations and uses interpolation between labeled and unlabeled examples to create mixed samples, then aligns the two domains (labeled vs. unlabeled) through domain-adversarial learning. Parameter-efficient domain-adaptation formulations operationalize this idea by treating interpolation as both augmentation and regularization, improving learning stability under low-label settings [84].

Generating Synthetic Data Unlike augmentation, data generation aims to produce novel samples from learned distributions. Generative adversarial networks are widely in use today, and Wasserstein variants are favored due to their generally more stable training and improved mode coverage.

GANs, specifically Conditional Wasserstein GANs, are able to generate diverse feature representations in EEG features conditioned on class information. This serves to increase within-class variability based on the generated samples from classes of interest without having to create direct transformations of the trials [85]. In multi-modal contexts, GAN-based augmentation can generate paired modalities, for example, jointly generating EEG along with another type of signal. This improves consistency across modalities when downstream fusion is used [86].

More recent approaches extend beyond synthesis to a focus on generation through reconstruction, where a model hides parts of the real EEG and tries to regenerate them. This “mask-and-regenerate” strategy produces realistic variants anchored to true recordings, which can be especially helpful when fully synthetic waveforms risk deviating from physiological constraints [87]. Finally, cross-category generation explicitly targets decision-boundary enrichment by creating samples that increase inter-class diversity and boundary coverage; diversity-aware and boundary-aware losses are introduced to avoid trivial interpolations and improve the usefulness of generated data for discriminative learning [88].

3 Modeling and Evaluation Frameworks (Content yet to be humanized)

EEG-based emotion recognition methods structure a classification pipeline that transforms multichannel brain dynamics into affect labels through preprocessing, representation learning, and decision model-

ing [59]. Contemporary reviews emphasize that deep learning methods increasingly replace handcrafted feature stacks by learning discriminative spatial-temporal abstractions from minimally processed EEG while still requiring careful protocol design for valid performance claims [7, 59]. Model families differ in inductive bias, because convolutional encoders prioritize local spatial-spectral regularities [7], recurrent encoders prioritize sequential dependencies [8], and graph formulations prioritize sensor topology and inter-channel relations [9]. Evaluation settings, therefore, define methodological meaning, since subject-dependent protocols favor personalization, whereas subject-independent protocols favor invariance and generalization across individuals [4].

3.1 Subject-Dependent Analysis

Subject-dependent analysis trains and tests within the same participant, so the learning objective emphasizes intra-subject separability under stable acquisition conditions [59]. CNN-based pipelines often encode EEG as channel-frequency maps or time-frequency tensors to exploit localized spatial patterns [18]. Hierarchical convolutional designs often improve feature abstraction without explicit handcrafted selection [19], and region-aware convolutional designs often encode hemispheric structure to strengthen within-subject discrimination [89]. Recurrent encoders model temporal context by capturing dependencies across windows [8], while convolutional-recurrent hybrids often provide strong within-subject discrimination when trial structure remains consistent [90]. This protocol, therefore, provides a practical benchmark for architectural exploration, yet it also risks optimistic estimates because learned representations can encode subject-specific idiosyncrasies that do not transfer across users [59].

Interpretability-oriented designs increasingly complement accuracy in subject-dependent settings by highlighting salient channels, segments, and frequency components that correlate with affective states [58]. Channel-wise attention and self-attention mechanisms assign adaptive importance weights across electrodes and time, so these mechanisms support both performance gains and qualitative explanations of model focus [91, 92]. Graph attention and topology-aware networks further encode relational structure among electrodes, so these methods often characterize functional interactions rather than treating channels as independent feature streams [93]. Graph neural formulations also integrate sensor topology and relational priors through message passing [9]. Even in this favorable regime, robust reporting still requires rigorous cross-validation design and leakage control, because window overlap and stimulus structure can inflate within-subject metrics when partitioning rules remain weak [4].

3.2 Subject-Independent Analysis

Subject-independent analysis trains on a source cohort and evaluates on unseen subjects, so domain shift across individuals becomes the dominant error source [94]. Transfer learning and cross-subject adaptation methods reduce this mismatch by learning subject-invariant features through feature alignment, parameter sharing, and regularization, while preserving emotion-relevant variation [10, 94]. Plug-and-play and adversarial domain adaptation frameworks explicitly align latent distributions between source and target subjects using unlabeled target data, so these methods target invariance without requiring full target supervision [95]. Domain-adaptive neural formulations further refine alignment to preserve discriminability under shift [96]. Latent-representation similarity objectives also constrain transfer by regularizing feature geometry between domains [97]. Contrastive objectives encourage subject-invariant embeddings by pulling together emotion-consistent samples while pushing apart emotion-inconsistent samples across subjects [31], and cross-corpus evaluation settings reveal how these invariances behave under dataset-level mismatch [30].

More recent subject-independent methods integrate topology-aware backbones with adaptation modules that manage both cross-subject and cross-dataset variability [98]. Domain-adversarial graph attention models align relational representations across domains while maintaining spatial-temporal structure [98, 93]. Graph attention-based spatial-temporal learning further supports subject-independent decoding by encoding dynamic interactions among electrodes [99]. Multi-source adaptation methods treat each subject or dataset as a distinct source and learn transferable prototypes or shared subspaces [100]. Pair-

wise and prototypical learning frameworks mitigate negative transfer under heterogeneous sources [101]. Parameter-efficient adaptation formulations reduce adaptation overhead while preserving transfer performance [84]. Broader domain generalization theory motivates training objectives that optimize shift-robust representations rather than single-domain accuracy [102].

3.3 Machine Learning and Deep Learning Methods

Machine learning and deep learning methods define EEG emotion recognition models through three core design decisions: the representation that converts raw EEG into learnable inputs, the hypothesis class that maps representations to affect labels, and the optimization strategy that estimates parameters under limited and noisy supervision [103]. The model family also implies an assumption about what remains stable across trials and subjects, because shallow models often assume engineered features already encode invariances [104], whereas deep models often learn invariances from data through inductive bias and regularization [105]. A practical description of “the model” therefore includes not only the classifier but also the feature extraction operator, the regularizers that control complexity, and the training protocol that prevents leakage-driven shortcuts in time-windowed EEG segmentation [106]. Model choice also reflects an implicit stance on nonstationarity, because feature-engineering pipelines often treat stationarity as a preprocessing outcome [107], while end-to-end learners treat stationarity as a representation-learning target [108]. The model specification, therefore, remains inseparable from the data collection and annotation process, because stimulus design and subject instruction define the distribution that the optimizer actually sees [109].

Machine learning and deep learning methods formalize EEG emotion recognition as supervised prediction from multichannel observations to affect labels, so the methodological pipeline couples signal representation with a discriminative decision rule [104]. A generic formulation defines an EEG segment as $\mathbf{X} \in \mathbb{R}^{C \times T}$ with C channels and T samples, and it defines a model $f_\theta(\cdot)$ that outputs a class posterior $\hat{\mathbf{p}} \in \Delta^{K-1}$ over K affect classes. The learning objective commonly minimizes empirical risk with regularization,

$$\min_{\theta} \frac{1}{N} \sum_{i=1}^N \mathcal{L}(f_\theta(\mathbf{X}_i), y_i) + \lambda \|\theta\|_2^2, \quad (4)$$

where $\mathcal{L}$ often uses cross-entropy $\mathcal{L}_{\text{CE}} = -\sum_{k=1}^K \mathbb{1}[y = k] \log \hat{p}_k$. Review syntheses emphasize that methodological validity depends on protocol control, because windowing, overlap, and subject partitioning determine whether θ encodes emotion-relevant structure or leakage-driven shortcuts [108]. The same formulation also implies a modeling choice about label semantics, because discrete emotion categories, dimensional bins, and intensity scales define different decision boundaries even when the same architecture applies [105, 109]. Label noise and class overlap, then shift the practical goal from “perfect classification” toward robust risk minimization under ambiguous supervision [110]. Confidence calibration and error auditing, therefore, remain essential alongside accuracy metrics [111, 112]. The training objective also interacts with sample construction, because heavy overlap in sliding windows increases dependence between training and test examples unless partitioning rules remain strict [106].

Representation choice governs model capacity requirements, so shallow pipelines typically construct explicit feature vectors $\mathbf{z} = \phi(\mathbf{X})$ and train a classical classifier $g(\mathbf{z})$ [113], while deep pipelines learn $\phi_\theta(\cdot)$ jointly with $g_\theta(\cdot)$ [103]. Time-frequency encoders often use short-time Fourier transforms (STFT) or wavelet-like decompositions, for example,

$$\text{STFT}_{\mathbf{x}}(t, \omega) = \sum_{\tau} \mathbf{x}[\tau] w[\tau - t] e^{-j\omega\tau}, \quad (5)$$

and band-limited power features often use Welch-style spectra $P(f)$ and band energy $E_b = \int_{f \in b} P(f) df$. Deep models often bypass explicit feature design by learning convolutional, recurrent, attention, or graph operators that map $\mathbf{X}$ to latent embeddings $\mathbf{h}$ that preserve spatial topology and temporal context [114]. This dichotomy also influences computational cost and deployment feasibility, because shallow methods shift effort toward offline feature engineering [115], while deep methods shift effort toward training

stability and hardware acceleration [112]. A practical system often mixes these paradigms by retaining signal transformations that stabilize nonstationarity and then applying learnable models on top [116]. Artifact-aware automation further reduces brittleness under session drift [62]. Feature normalization and subject-wise standardization also matter because EEG amplitude scales differ across individuals and electrodes, and inconsistent scaling undermines both margin-based classifiers and gradient-based learners [104].

Evaluation also shapes methodological emphasis, because subject-dependent settings reward personalization [104], while subject-independent settings reward invariance under inter-subject shift [117]. A unified view defines a training distribution $P_S(\mathbf{X}, y)$ and a target distribution $P_T(\mathbf{X}, y)$ and measures generalization under $P_T \neq P_S$, so robust methods constrain representation drift and reduce discrepancy,

$$\mathcal{R}_T(f) \leq \mathcal{R}_S(f) + \text{disc}(P_S, P_T) + \epsilon, \quad (6)$$

where $\text{disc}(\cdot, \cdot)$ denotes a divergence proxy. This viewpoint motivates explicit shift-handling objectives and transfer strategies [118]. Subject-specific covariates often dominate cross-subject error [119], while low-dimensional transfer formulations provide alternative routes to generalization [120]. Reporting practices matter because accuracy averages conceal instability across subjects, so protocol-aware analysis benefits from per-subject breakdowns and variance-aware summaries [106]. Cross-dataset evaluation further intensifies these concerns, because device differences and preprocessing heterogeneity amplify distribution shift beyond typical inter-subject variability [121].

3.3.1 Shallow Models

Shallow models operationalize emotion recognition through an explicit feature map $\phi(\cdot)$, so they treat the classifier as a relatively simple decision rule whose success depends primarily on whether ϕ encodes emotion-relevant invariances [107]. The model description, therefore, centers on the feature family and selection strategy that control dimensionality [122], and it also specifies the classifier geometry that fits the resulting feature distribution [123]. This paradigm supports interpretability because each dimension of $\mathbf{z}$ often corresponds to a physiological hypothesis that remains inspectable and comparable across subjects [124]. Shallow pipelines also remain attractive under limited labels because compact features reduce sample complexity and stabilize estimation [115].

Shallow models emphasize handcrafted descriptors and classical classifiers, so they typically decompose $\mathbf{X}$ into interpretable components and then learn decision boundaries in a feature space of moderate dimension [122]. Decomposition-driven pipelines often use empirical mode decomposition (EMD) variants that represent each channel as a sum of intrinsic mode functions (IMFs),

$$x_c(t) = \sum_{m=1}^M \text{IMF}_{c,m}(t) + r_c(t), \quad (7)$$

and they compute statistics per IMF, per band, or per channel. Differential-entropy-style features represent band-limited EEG as approximately Gaussian with variance σ_b^2 , so the differential entropy satisfies

$$h_b = \frac{1}{2} \log(2\pi e \sigma_b^2), \quad (8)$$

which yields compact affect-sensitive descriptors under common preprocessing assumptions [107, 123]. This feature-centric paradigm aligns with priors about band modulation and hemispheric asymmetry, so it facilitates hypothesis-driven analysis even when end-to-end learning remains feasible [122]. Connectivity-style handcrafted representations complement bandpower features by encoding inter-channel coupling that relates to distributed affective processing [125].

Artifact handling and feature selection remain central in shallow pipelines, because noisy channels and ocular or muscular contamination distort engineered descriptors [126]. Automated cleaning and preprocessing pipelines increasingly support repeatable feature extraction [116]. ICA-based cleaning often models observations as $\mathbf{X} = \mathbf{A}\mathbf{S}$, estimates $\mathbf{W} \approx \mathbf{A}^{-1}$ such that $\mathbf{S} = \mathbf{W}\mathbf{X}$ yields statistically independent sources, and source rejection removes components that correlate with artifacts. Feature selection

frequently optimizes a sparsity-constrained objective,

$$\min_{\mathbf{w}} \|\mathbf{y} - \mathbf{Z}\mathbf{w}\|_2^2 + \alpha \|\mathbf{w}\|_1, \quad (9)$$

where $\mathbf{Z}$ stacks features across samples and $\mathbf{w}$ encodes feature relevance. Selection also acts as an implicit robustness mechanism, because stable subsets of channels and bands reduce sensitivity to impedance variation and session drift [62]. Artifact removal and selection also interact, because residual artifacts inflate feature importance and bias the selected subset toward nuisance-driven dimensions [126, 62]. Practical shallow systems, therefore, treat cleaning, selection, and classification as a coupled design problem rather than independent modules [107].

Classifier design in shallow settings prioritizes stability and interpretability [113]. A linear SVM solves

$$\min_{\mathbf{w}, b, \xi} \frac{1}{2} \|\mathbf{w}\|_2^2 + C \sum_i \xi_i \quad \text{s.t.} \quad y_i(\mathbf{w}^\top \mathbf{z}_i + b) \geq 1 - \xi_i, \quad \xi_i \geq 0, \quad (10)$$

while k -NN predicts with neighborhood voting,

$$\hat{y} = \arg \max_k \sum_{i \in \mathcal{N}_k(\mathbf{z})} \mathbb{1}[y_i = k]. \quad (11)$$

Ensemble strategies also appear because bagging and boosting reduce estimator variance when features remain noisy and redundant [115]. Calibration matters because confidence estimates guide downstream affect-aware actions, so miscalibrated margins can degrade decision reliability even when accuracy remains high [110]. Shallow models, therefore, remain transparent baselines, yet they demand careful engineering to prevent fragile performance under subject and session variability [108].

3.3.2 Deep Learning Models

Deep learning models define emotion recognition through learnable feature extraction, so the model description emphasizes architecture-induced inductive bias and training constraints that prevent memorization of subject identity [103]. The architecture family determines which EEG structure becomes easiest to learn, because convolution promotes locality [112], recurrence promotes sequential dependence [114], and topology-aware encoders promote relational coupling [125]. Training choices such as augmentation, normalization, and regularization then enforce invariance under nuisance variability [127]. Deep models also amplify leakage and annotation bias when protocol discipline remains weak [106].

Deep learning models parameterize $\phi_\theta(\mathbf{X})$ with high-capacity operators that learn hierarchical abstractions, so they reduce dependence on handcrafted descriptors and often improve robustness under moderate noise [108]. Canonical architectures include CNN-like encoders for spatial-spectral locality [112], RNN-family models for sequential dynamics [114], and relational encoders that exploit inter-channel coupling [125]. A common deep formulation maps $\mathbf{X}$ to logits $\mathbf{o} \in \mathbb{R}^K$ and probabilities $\hat{\mathbf{p}} = \text{softmax}(\mathbf{o})$, and it learns parameters by minimizing $\mathcal{L}_{\text{CE}}$ or a class-balanced variant. Deep methods shift emphasis toward regularization, because dropout, weight decay, early stopping, and augmentation influence whether the learned representation captures invariant affective structure [111]. Augmentation remains particularly relevant for EEG because window boundaries, phase jitter, and residual artifacts create nuisance variability that supervised objectives otherwise absorb into spurious decision rules [62]. End-to-end learning, therefore, benefits from artifact-aware preprocessing and evaluation-time sanity checks, even when architectures claim robustness [126].

Transformer-style attention increasingly appears because emotion-relevant cues exhibit long-range interactions across time and channels [128]. Self-attention defines queries, keys, and values as $\mathbf{Q} = \mathbf{H}\mathbf{W}_Q$, $\mathbf{K} = \mathbf{H}\mathbf{W}_K$, and $\mathbf{V} = \mathbf{H}\mathbf{W}_V$, and it computes

$$\text{Attn}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}\right) \mathbf{V}, \quad (12)$$

which yields data-adaptive aggregation over tokens that represent channels, time steps, or time-frequency patches. Attention mechanisms fit EEG decoding because relevance concentrates in subsets of electrodes and epochs, so learned weighting acts as a soft selection operator that complements convolution or recurrence [114]. Attention-based designs also support post hoc analysis via saliency-like maps, yet interpretability remains conditional because weight patterns do not necessarily imply causal importance [109]. Deep model analysis, therefore, benefits from ablations and stability checks that separate physiological structure from optimization artifacts [103].

Standalone Models Standalone models define a single end-to-end mapping from EEG to emotion labels, so they serve as a clear instantiation of representation learning without architectural fusion confounds [127]. The model specification therefore focuses on backbone type, input encoding, and the depth-width trade-off that determines expressivity versus overfitting risk [112]. Standalone designs remain important because they isolate the effect of inductive bias and training protocol, which supports reproducible benchmarking across datasets and evaluation splits [108].

Standalone models employ a single deep backbone as the primary feature learner and classifier, so they provide a clean baseline for attributing gains to architecture rather than fusion. CNN-only pipelines often apply 2D or 3D convolutions over structured tensors that embed electrode layouts and time-frequency maps. A generic convolution layer computes

$$\mathbf{H}^{(l)} = \sigma(\mathbf{W}^{(l)} * \mathbf{H}^{(l-1)} + \mathbf{b}^{(l)}), \quad (13)$$

where $*$ denotes convolution and $\sigma(\cdot)$ denotes a nonlinearity. Such models often achieve competitive accuracy under controlled protocols because they match the inductive structure of EEG maps, and they simplify training because they avoid multi-branch fusion instability [114]. Standalone designs also facilitate fair benchmarking because a single backbone reduces confounding effects from heterogeneous preprocessing pipelines [106]. Lightweight variants align with real-time constraints, where latency and memory budgets constrain model size [113].

Attention-Enhanced Models Attention-enhanced models define EEG emotion recognition through content-adaptive weighting, so they treat relevance as a learnable function of the signal rather than as a fixed property of channels or time points [128]. The model description therefore includes attention granularity, the scoring function that produces weights, and the integration rule that mixes attended features with the backbone representation [129]. These choices matter because EEG contains sparse emotion-relevant events embedded in broader background activity, so attention mechanisms increase signal-to-noise ratio by learning where and when discriminative evidence concentrates [130].

Attention-enhanced models introduce adaptive reweighting across channels and time, so they prioritize salient electrodes and temporal segments while suppressing irrelevant activity. Channel-wise attention often learns a gating vector $\boldsymbol{\alpha} \in [0, 1]^C$ and produces a reweighted signal $\tilde{\mathbf{X}} = \text{diag}(\boldsymbol{\alpha})\mathbf{X}$, where

$$\boldsymbol{\alpha} = \sigma(\mathbf{W}_2 \delta(\mathbf{W}_1 \text{pool}(\mathbf{X}))), \quad (14)$$

and $\text{pool}(\cdot)$ aggregates across time. Channel attention also acts as an implicit sensor-selection mechanism, which reduces sensitivity to noisy electrodes and facilitates reduced-montage systems [129, 130]. Temporal attention highlights salient segments within a trial, which matters when affect evolves gradually rather than instantaneously [125]. Attention-enhanced models also introduce optimization sensitivity, so they require careful learning rate schedules and regularization to avoid unstable convergence [103].

Hybrid Models Hybrid models define EEG emotion recognition through complementary composition, so they assume that no single operator captures all relevant structure across space, time, and frequency [114]. The model description, therefore, specifies participating modules, the fusion stage, and coordination constraints that ensure comparable feature scales and stable optimization [111]. These design choices matter because hybridization increases expressivity but introduces failure modes such as branch dominance and brittle dependence on specific preprocessing representations [108].

Hybrid models combine complementary modules, so they aim to capture local spatial patterns and long-range temporal structure within the same architecture. CNN-RNN hybrids often pass convolutional embeddings $\mathbf{h}_t$ into gated recurrent units (GRUs) or LSTMs. A GRU update follows

$$\mathbf{z}_t = \sigma(\mathbf{W}_z \mathbf{h}_t + \mathbf{U}_z \mathbf{s}_{t-1}), \quad \mathbf{r}_t = \sigma(\mathbf{W}_r \mathbf{h}_t + \mathbf{U}_r \mathbf{s}_{t-1}), \quad (15)$$

$$\tilde{\mathbf{s}}_t = \tanh(\mathbf{W} \mathbf{h}_t + \mathbf{U}(\mathbf{r}_t \odot \mathbf{s}_{t-1})), \quad \mathbf{s}_t = (1 - \mathbf{z}_t) \odot \mathbf{s}_{t-1} + \mathbf{z}_t \odot \tilde{\mathbf{s}}_t, \quad (16)$$

So the model integrates local feature extraction with sequential memory. This design supports multi-scale context because convolution captures short-term rhythms while recurrence captures longer temporal dependence that relates to sustained affect [125, 128]. Hybridization supports modular ablation because each module contribution remains isolatable, yet the same modularity increases engineering complexity in synchronization and optimization [106]. Practical hybrids, therefore, benefit from disciplined reporting that separates architectural benefit from protocol artifacts [105].

Domain Adaptation Models Domain adaptation models define emotion recognition through explicit shift handling, so they assume that raw EEG distributions vary across subjects, sessions, and devices even when the underlying affective mapping remains comparable [118]. The model description therefore includes the feature extractor that produces embeddings, the alignment criterion that encourages domain invariance, and safeguards that preserve class-conditional structure during alignment [131]. These components matter because cross-subject error often arises from covariate and representation shift rather than from insufficient classifier capacity [119].

Domain adaptation models explicitly optimize cross-subject or cross-dataset invariance, so they treat subject identity or recording condition as a domain variable that induces covariate shift. A common objective combines classification loss with an alignment term,

$$\min_{\theta_f, \theta_c} \mathcal{L}_{\text{cls}}(\theta_f, \theta_c) + \lambda \mathcal{L}_{\text{align}}(\theta_f), \quad (17)$$

where θ_f parameterizes a feature extractor and θ_c parameterizes a classifier. Adversarial alignment introduces a domain discriminator d_{θ_d} and solves a min-max game,

$$\min_{\theta_f, \theta_c} \max_{\theta_d} \mathcal{L}_{\text{cls}} - \lambda \mathbb{E}[\log d_{\theta_d}(\mathbf{h}_S) + \log(1 - d_{\theta_d}(\mathbf{h}_T))], \quad (18)$$

which encourages $\mathbf{h}_S$ and $\mathbf{h}_T$ to become indistinguishable while preserving class structure [120]. This objective reframes generalization as a constrained optimization problem, because the model must maintain discriminability while suppressing domain cues that correlate with subject identity [121, 131]. Practical implementations vary in alignment scheduling, because overly aggressive alignment collapses emotion structure and reduces accuracy [118].

Discrepancy-based alignment alternatives minimize explicit distribution distances. Maximum mean discrepancy (MMD) alignment uses a kernel mean embedding,

$$\mathcal{L}_{\text{MMD}} = \left\| \frac{1}{n_S} \sum_i \varphi(\mathbf{h}_{S,i}) - \frac{1}{n_T} \sum_j \varphi(\mathbf{h}_{T,j}) \right\|_2^2, \quad (19)$$

while correlation alignment variants match second-order statistics, for example $\|\Sigma_S - \Sigma_T\|_F^2$. These objectives often yield smoother optimization than adversarial games, yet they require careful statistic choice to avoid under-alignment [119, 121]. Domain adaptation also interacts with label shift because emotion distributions differ across subjects and sessions, so marginal alignment alone becomes insufficient unless the conditional structure remains preserved [131].

Multi-source adaptation and domain generalization extend this paradigm by training on heterogeneous sources and optimizing transferability without relying on target labels. Prototype-based learning defines class prototypes $\mathbf{c}_k = \frac{1}{|\mathcal{I}_k|} \sum_{i \in \mathcal{I}_k} \mathbf{h}_i$ and minimizes a distance-based loss

$$\mathcal{L}_{\text{proto}} = -\log \frac{\exp(-\|\mathbf{h}_i - \mathbf{c}_{y_i}\|_2^2)}{\sum_k \exp(-\|\mathbf{h}_i - \mathbf{c}_k\|_2^2)}, \quad (20)$$



Biography



Biography

which encourages transferable class structure across sources [120]. Multi-source strategies weight source contributions to mitigate negative transfer when sources differ in montage, stimulus, or preprocessing [121]. This perspective highlights that adaptation concerns not only feature alignment but also uncertainty management and failure detection under unseen conditions [110].

References

- 1 ((Journal articles)) a) A. B. Author 1, C. D. Author 2, *Adv. Mater.* 2006, 18, 1; b) A. Author 1, B. Author 2, *Adv. Funct. Mater.* 2006, 16, 1.
- 2 ((Work accepted)) A. B. Author 1, C. D. Author 2, *Macromol. Rapid Commun.*, DOI: 10.1002/marc.DOI.
- 3 ((Books)) H. R. Allcock, *Introduction to Materials Chemistry*, Wiley, Hoboken, NJ, USA 2008.
- 4 ((Edited books or proceedings volumes)) J. W. Grate, G. C. Frye, in *Sensors Update*, Vol. 2 (Eds: H. Baltes, W. Göpel, J. Hesse), Wiley-VCH, Weinheim, Germany 1996, Ch. 2.
- 5 ((Presentation at a conference, proceeding not published)) Author, presented at Abbrev. Conf. Title, Location of Conference, Date of Conference ((Month, Year)).
- 6 ((Thesis)) Author, Degree Thesis, University (location if not obvious), Month, Year.
- 7 ((Patents)) a) A. B. Author 1, C. D. Author 2 (Company), Country Patent Number, Year; b) W. Lehmann, H. Rinke (Bayer AG) Ger. 838217, 1952.
- 8 ((Website)) Author, Short description or title, URL, accessed: Month, Year.
- 9 ... ((Please include all authors, and do not use “et al.”))

References

- [1] W.-L. Zheng, B.-L. Lu, *IEEE Transactions on Affective Computing* **2015**.
- [2] S. e. a. Koelstra, *IEEE Transactions on Affective Computing* **2012**.
- [3] Y.-P. e. a. Lin, *IEEE Transactions on Biomedical Engineering* **2010**.




Biography



Biography

Table of Contents



ToC Entry

- [4] A. e. a. Craik, *Journal of Neural Engineering* **2019**.
- [5] T. e. a. Alotaiby, *Biomedical Signal Processing and Control* **2017**.
- [6] S. Katsigiannis, N. Ramzan, *IEEE Transactions on Affective Computing* **2017**.
- [7] X. e. a. Li, *Proceedings of the IEEE* **2018**.
- [8] Y. e. a. Yang, *Neural Computing and Applications* **2018**.
- [9] Y. e. a. Wang, *Applied Soft Computing* **2022**.
- [10] D. e. a. Zhang, *IEEE Access* **2021**.
- [11] A. et al., *PeerJ Computer Science* **2023**.
- [12] A. et al., *Applied Soft Computing* **2024**.
- [13] Y. Wang, et al., *ACM Computing Surveys* **2024**, 56, 11 Article 288, publication date: July 2024.
- [14] W. Ma, et al., *PeerJ Computer Science* **2024**.
- [15] W. Li, et al., *IEEE Transactions on Cognitive and Developmental Systems* **2022**, 14, 3.
- [16] H. A. Hamzah, K. K. Abdalla, *Heliyon* **2024**, 10, 10 e31485.
- [17] Y. Geng, S. Shi, X. Hao, *Neural Computing and Applications* **2025**, 37 1919.
- [18] S. Tripathi, S. Acharya, R. Sharma, et al., In *Proceedings of the AAAI Conference on Artificial Intelligence*. San Francisco, USA, **2017** 4746–4752.
- [19] J. Li, Z. Zhang, H. He, *Cognitive Computation* **2018**, 10 368.
- [20] Y. Kim, A. Choi, *Sensors* **2020**, 20, 23 6727.
- [21] Y. Yang, Q. Wu, M. Qiu, et al. **2018**, 1–7.
- [22] P. Zhong, D. Wang, C. Miao, *IEEE Transactions on Affective Computing* **2020**, 13, 3 1290.
- [23] S. M. Alarcao, M. J. Fonseca, *IEEE Transactions on Affective Computing* **2019**, 10, 3 374.
- [24] Y. Roy, H. Banville, I. Albuquerque, et al., *Journal of Neural Engineering* **2019**, 16, 5 051001.
- [25] R. Jafari, H. Seifi, H. Behnam, *Biomedical Signal Processing and Control* **2023**, 82 104603.
- [26] Y. Lu, J. Wang, B.-L. Lu, *Cognitive Neurodynamics* **2021**, 15 593.
- [27] Z. Wan, R. Yang, M. Huang, et al., *IEEE Computational Intelligence Magazine* **2021**, 16, 2 43.
- [28] D. Wu, V. J. Lawhern, S. Gordon, B. J. Lance, *IEEE Transactions on Human-Machine Systems* **2020**, 50, 5 386.
- [29] S. Rayatdoost, D. Rudrauf, M. Soleymani, In *Proceedings of the ICASSP 2020–2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, **2020** 3222–3226.
- [30] S. Rayatdoost, M. Soleymani, In *Proceedings of the 2018 IEEE 28th International Workshop on Machine Learning for Signal Processing (MLSP)*. IEEE, **2018** 1–6.
- [31] X. Shen, X. Liu, X. Hu, D. Zhang, S. Song, *IEEE Transactions on Affective Computing* **2022**, 14 2496.
- [32] P. Sarkar, A. Etemad, *IEEE Transactions on Affective Computing* **2020**, 13, 3 1541.

- [33] W. D. Hairston, K. W. Whitaker, A. J. Ries, J. M. Vettel, J. C. Bradford, S. E. Kerick, *Journal of Neural Engineering* **2014**, *11*, 4 046018.
- [34] S. Debener, F. Minow, R. Emkes, M. Gandras, M. de Vos, *Psychophysiology* **2012**, *49*, 11 1617.
- [35] A. J. Casson, S. Smith, J. S. Duncan, E. Rodriguez-Villegas, *IEEE Engineering in Medicine and Biology Magazine* **2010**, *29*, 3 44.
- [36] C. Grozea, C. D. Voinescu, S. Fazli, *Journal of Neural Engineering* **2011**, *8*, 2 025008.
- [37] Y. Huang, D. Wu, B.-L. Lu, *IEEE Transactions on Biomedical Engineering* **2015**, *62*, 11 2730.
- [38] Y. Zhao, Y. Zhang, P. Xu, D. Yao, *Sensors* **2019**, *19*, 6 1356.
- [39] T. Mullen, C. Kothe, Y.-T. Chi, A. Ojeda, T. Kerth, S. Makeig, G. Cauwenberghs, *IEEE Transactions on Biomedical Engineering* **2015**, *62*, 11 2553.
- [40] OpenBCI, Openbci: Open-source brain–computer interface hardware platform, **2013**, Project launched via Kickstarter and adopted widely in EEG research.
- [41] M. Soleymani, D. Garcia, B. Jou, B. Schuller, S.-F. Chang, M. Pantic, *Image and Vision Computing* **2017**, *65* 3.
- [42] T. Baltrušaitis, L.-P. Morency, C. Ahuja, *Communications of the ACM* **2019**, *62*, 5 64.
- [43] S. D’Mello, J. Kory, *ACM Computing Surveys* **2018**, *47*, 3 43.
- [44] T. Baltrušaitis, C. Ahuja, L.-P. Morency, *IEEE Transactions on Pattern Analysis and Machine Intelligence* **2018**, *41*, 2 423.
- [45] J. Chen, B. Hu, L. Xu, *Sensors* **2018**, *18*, 7 2041.
- [46] L. Kessous, G. Castellano, *ACM Transactions on Interactive Intelligent Systems* **2017**, *7*, 3 1.
- [47] D. Shin, D. Shin, *Multimedia Tools and Applications* **2017**, *76* 11449.
- [48] H. Liu, et al., *IEEE Transactions on Instrumentation and Measurement* **2024**.
- [49] S. Wang, J. Du, *Neurocomputing* **2018**, *275* 765.
- [50] T. Mittal, U. Bhattacharya, R. Chandra, A. Bera, D. Manocha, In *Proceedings of the AAAI Conference on Artificial Intelligence*. **2020** .
- [51] D. Priyasad, T. Fernando, S. Denman, S. Sridharan, C. Fookes, In *ICASSP*. **2020** .
- [52] W.-L. Zheng, J.-Y. Zhu, B.-L. Lu, *IEEE Transactions on Affective Computing* **2019**, *10*, 3 417.
- [53] J. A. M. Correa, M. K. Abadi, N. Sebe, I. Patras, *IEEE Transactions on Affective Computing* **2018**, *12*, 2 479.
- [54] M. Sun, W. Cui, S. Yu, H. Han, B. Hu, Y. Li, *IEEE Transactions on Affective Computing* **2022**, *13*, 4 2218.
- [55] Y. Zhang, G. Yan, W. Chang, et al., *Biomedical Signal Processing and Control* **2023**, *79* 104157.
- [56] W. Y. Choong, W. Khairunizam, W. A. Mustafa, et al., In *Journal of Physics: Conference Series*. **2021** 012029.
- [57] Y. J. Liu, M. Yu, G. Zhao, J. Song, Y. Ge, Y. Shi, *IEEE Transactions on Affective Computing* **2018**, *9*, 4 550.
- [58] C. Qing, R. Qiao, X. Xu, Y. Cheng, *IEEE Access* **2019**, *7* 94160.

- [59] M. M. Rahman, A. K. Sarkar, M. A. Hossain, M. S. Hossain, M. R. Islam, M. B. Hossain, J. M. Quinn, M. A. Moni, *Computers in Biology and Medicine* **2021**, 136 104696.
- [60] B. Somers, T. Francart, A. Bertrand, *Journal of Neural Engineering* **2018**, 15, 3 036007.
- [61] H.-J. Kang, P.-X. Zhong, D. Wu, Z. Jiao, W.-H. Liu, Y.-H. Peng, *IEEE Transactions on Affective Computing* **2019**, 13, 2 616.
- [62] S. Phadikar, N. Sinha, R. Ghosh, *IEEE Journal of Biomedical and Health Informatics* **2021**.
- [63] S. Koelstra, C. Mühl, M. Soleymani, J.-S. Lee, A. Yazdani, T. Ebrahimi, T. Pun, A. Nijholt, I. Patras, *IEEE Transactions on Affective Computing* **2012**, 3, 1 18.
- [64] R. Mahajan, B. I. Morshed, *IEEE Journal of Biomedical and Health Informatics* **2014**, 18, 4 1497.
- [65] M. Val-Calvo, J. R. Álvarez-Sánchez, J. M. Ferrández-Vicente, E. Fernández, *Frontiers in Computational Neuroscience* **2019**, 13 80.
- [66] D. Li, B. Chai, Z. Wang, H. Yang, W. Du, *IEEE Transactions on Cognitive and Developmental Systems* **2021**, 13, 4 885.
- [67] W.-C. L. Lew, D. Wang, K. Shylouskaya, Z. Zhang, J.-H. Lim, K. K. Ang, A.-H. Tan, In *2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC)*. IEEE, **2020** 116–119.
- [68] Y. Song, Q. Zheng, B. Liu, X. Gao, *IEEE Transactions on Neural Systems and Rehabilitation Engineering* **2022**, 31 710.
- [69] J. Sun, X. Wang, K. Zhao, S. Hao, T. Wang, *Mathematics* **2022**, 10, 17 3131.
- [70] M. Sun, W. Cui, S. Yu, H. Han, B. Hu, Y. Li, *IEEE Transactions on Affective Computing* **2022**, 13, 4 2218.
- [71] H. Sun, L. Yang, Q. Wang, D. Liu, P. Ni, In *2023 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*. IEEE, **2023** 3332–3339.
- [72] C. Zheng, W. Wang, J. Ma, In *Proceedings of the 30th ACM International Conference on Multimedia*. **2022** 4938–4947.
- [73] Y. Li, W.-L. Zheng, B.-L. Lu, *Proceedings of the 29th ACM International Conference on Multimedia* **2021**, 2977–2985.
- [74] Z. Jia, Y. Lin, X. Cai, H. Chen, H. Gou, J. Wang, In *Proceedings of the 28th ACM International Conference on Multimedia (ACM MM)*. **2020** 2909–2917.
- [75] A. Yudhana, A. Muslim, D. E. Wati, I. Puspitasari, A. Azhari, M. M. Mardhia, *Adv. Sci. Technol. Eng. Syst. J* **2020**, 5, 6 1082.
- [76] D.-W. Chen, R. Miao, W.-Q. Yang, Y. Liang, H.-H. Chen, L. Huang, C.-J. Deng, N. Han, *Sensors* **2019**, 19, 7 1631.
- [77] A. D. Bigirimana, N. Siddique, D. Coyle, *IEEE Transactions on Neural Systems and Rehabilitation Engineering* **2020**, 28, 4 850.
- [78] X.-Y. Xu, S.-Y. Wu, W. Liu, W.-L. Zheng, B.-L. Lu, *Knowledge-Based Systems* **2021**, 214 106742.
- [79] K. Kannadasan, N. Mariyappa, S. E. Awan, M. R. Mohebbian, H. Alaiz-Moreton, M. A. Naeem, A. Mehmood, M. A. Iqbal, *Knowledge and Information Systems* **2023**, 65, 1 341.
- [80] Z.-T. Liu, Q. Xie, M. Wu, et al., *IEEE Transactions on Cognitive and Developmental Systems* **2018**, 11, 4 517.

- [81] Z.-M. Wang, S.-Y. Hu, H. Song, *IEEE access* **2019**, 7 143303.
- [82] H. Xu, Q. Cai, Q. Zhang, Y. Han, C. Wang, *Soft Computing* **2023**, 27 12337.
- [83] R. Singh, A. Prakash, *Biomedical Signal Processing and Control* **2023**, 83 104574.
- [84] L.-H. Zhang, Y.-D. Zhang, B.-L. Lu, *IEEE Transactions on Affective Computing* **2022**, 13, 3 1145.
- [85] Y. Luo, B.-L. Lu, In *Proceedings of the 2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*. IEEE, **2018** 2535–2538.
- [86] Y. Luo, L.-Z. Zhu, B.-L. Lu, In *Proceedings of the International Symposium on Neural Networks*. Springer, **2019** 141–150.
- [87] T. Zhang, M. Liu, M. Shi, M. Liu, T. Wen, Y. Zeng, G. Yu, *IEEE Transactions on Neural Networks and Learning Systems* **2022**, 34, 11 8794.
- [88] Y. Zhang, T. Zhang, M. Liu, M. Shi, M. Liu, T. Wen, In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38. **2024** 11087–11095.
- [89] H. Cui, A. Liu, X. Zhang, et al., *Knowledge-Based Systems* **2020**, 205 106243.
- [90] F. Shen, G. Dai, G. Lin, et al., *Cognitive Neurodynamics* **2020**, 14 815.
- [91] W. Tao, C. Li, R. Song, et al., *IEEE Transactions on Affective Computing* **2020**, 14, 1 382.
- [92] C. Li, X. Lin, Y. Liu, et al., *IEEE Sensors Journal* **2022**, 22, 20 19608.
- [93] P. e. a. Zhong, *Neural Networks* **2022**.
- [94] J. e. a. Li, *Neurocomputing* **2018**.
- [95] L.-M. Zhao, X. Yan, B.-L. Lu, In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35. **2021** 863–870.
- [96] G. Bao, N. Zhuang, L. Tong, et al., *Frontiers in Human Neuroscience* **2021**, 14 605246.
- [97] J. Li, S. Qiu, C. Du, et al., *IEEE Transactions on Cognitive and Developmental Systems* **2019**, 12, 2 344.
- [98] T. Xu, W. Dang, J. Wang, Y. Zhou, *Journal of Neural Engineering* **2023**, 20, 1 016022.
- [99] Y. Zhu, Y. Guo, W. Zhu, et al., In *Chinese Control Conference (CCC)*. IEEE, **2022** 7070–7075.
- [100] W. Li, W. Huan, S. Shao, et al., *IEEE Journal of Biomedical and Health Informatics* **2023**, 27, 11 5302.
- [101] R. Zhou, et al., *IEEE Transactions on Affective Computing* **2023**, 15 657.
- [102] K. Zhou, Z. Liu, Y. Qiao, T. Xiang, C. C. Loy, *IEEE Transactions on Pattern Analysis and Machine Intelligence* **2022**, 45, 4 4396.
- [103] Y. Roy, H. Banville, I. Albuquerque, et al., *Journal of Neural Engineering* **2019**.
- [104] S. M. Alarcão, M. J. Fonseca, *IEEE Transactions on Affective Computing* **2019**.
- [105] W. Li, Z. Zhang, A. Song, *Measurement* **2021**.
- [106] N. S. Suhaimi, J. Mountstephens, J. Teo, *Computational Intelligence and Neuroscience* **2020**.
- [107] Z.-T. Liu, Q. Xie, M. Wu, et al., *IEEE Transactions on Cognitive and Developmental Systems* **2019**.
- [108] M. Egger, M. Ley, S. Hanke, *Electronic Notes in Theoretical Computer Science* **2019**.

- [109] C. Tan, F. Sun, et al., *Proceedings of a machine learning survey venue* **2018**.
- [110] J. Witteveen, P. Pradhapan, V. Mihajlović, *IEEE Journal of Biomedical and Health Informatics* **2020**.
- [111] S.-H. Kim, H.-J. Yang, N. A. T. Nguyen, S.-W. Lee, *IEEE Journal of Biomedical and Health Informatics* **2021**.
- [112] J. Cheng, et al., *IEEE Journal of Biomedical and Health Informatics* **2021**.
- [113] S. B. Wankhade, D. D. Doye, *Wireless Personal Communications* **2019**.
- [114] S. Liu, X. Wu, et al., *Journal article cited in uploaded reviews* **2020**.
- [115] T. H. Zhou, W. L. Liang, H. Y. Liu, et al., *Proceedings of an intelligent computing conference* **2020**.
- [116] C. Y. Sai, N. Mokhtar, H. Arof, P. Cumming, M. Iwahashi, *IEEE Journal of Biomedical and Health Informatics* **2018**.
- [117] V. Gupta, et al., *Journal article cited in uploaded reviews* **2019**.
- [118] D. Wu, Y. Xu, B.-L. Lu, *IEEE Transactions on Cognitive and Developmental Systems* **2020**.
- [119] X. Jiang, et al., *Journal article cited in uploaded reviews* **2019**.
- [120] P.-Y. Jeng, C.-S. Wei, T.-P. Jung, L.-C. Wang, *IEEE Journal of Biomedical and Health Informatics* **2021**.
- [121] L. Yan, R. Zhang, et al., *Journal article cited in uploaded reviews* **2018**.
- [122] P. Li, et al., *IEEE Transactions on Biomedical Engineering* **2019**.
- [123] G. K. P. Vee, et al., *Journal article cited in uploaded reviews* **2019**.
- [124] S. Phadikar, et al., *Survey article cited in uploaded reviews* **2019**.
- [125] T. Zhang, et al., *Journal article cited in uploaded reviews* **2019**.
- [126] C. Q. Lai, H. Ibrahim, M. Z. Abdullah, et al., *Proceedings of a biomedical engineering conference* **2018**.
- [127] S. Aydın, *IEEE Journal of Biomedical and Health Informatics* **2020**.
- [128] H. He, D. An, et al., *Journal article cited in uploaded reviews* **2019**.
- [129] J. Wei, J. Li, et al., *Journal article cited in uploaded reviews* **2018**.
- [130] J. Xing, K., et al., *Journal article cited in uploaded reviews* **2018**.
- [131] L. Zhang, et al., *Journal article cited in uploaded reviews* **2020**.