



## TAREA: GNS3 Switches 2

Hector.sH

19.1.2026

## Contents

|                           |   |
|---------------------------|---|
| Ips a usar en los equipos | 2 |
| Resultado de los pings    | 4 |





## Ips a usar en los equipos

Estas son las 3 redes que usaremos:

```
Address:      192.168.1.1
Netmask:      255.255.255.252 = 30
Wildcard:     0.0.0.3
=>
Network:      192.168.1.0/30
HostMin:      192.168.1.1
HostMax:      192.168.1.2
Broadcast:    192.168.1.3
Hosts/Net:    2
```

**Figure 1:** red 1

```
Address:      192.168.1.4
Netmask:      255.255.255.252 = 30
Wildcard:     0.0.0.3
=>
Network:      192.168.1.4/30
HostMin:      192.168.1.5
HostMax:      192.168.1.6
Broadcast:    192.168.1.7
Hosts/Net:    2
```

**Figure 2:** red 2

```
Address:      192.168.1.8
Netmask:      255.255.255.252 = 30
Wildcard:     0.0.0.3
=>
Network:      192.168.1.8/30
HostMin:      192.168.1.9
HostMax:      192.168.1.10
Broadcast:    192.168.1.11
Hosts/Net:    2
```

**Figure 3:** red 3



## Resultado de los pings

```
Trying ::1...
Connection failed: Conexión rehusada
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.

Welcome to Virtual PC Simulator, version 0.8.3
Dedicated to Daling.
Build time: Jan 14 2026 08:16:22
Copyright (c) 2007-2015, Paul Meng (mirnshi@gmail.com)
All rights reserved.

VPCS is free software, distributed under the terms of the "BSD" licence.
Source code and license can be found at vpcs.sf.net.
For more information, please visit wiki.freecode.com.cn.

Press '?' to get help.

Executing the startup file

Checking for duplicate address...
VPCS : 192.168.1.1 255.255.255.252

PC1> ping ip 192.168.1.2
Cannot resolve ip

PC1> ping 192.168.1.2

84 bytes from 192.168.1.2 icmp_seq=1 ttl=64 time=0.414 ms
84 bytes from 192.168.1.2 icmp_seq=2 ttl=64 time=0.462 ms
^C
PC1> ping 192.168.1.3

host (192.168.1.3) not reachable

PC1> ping 192.168.1.5

host (255.255.255.252) not reachable

PC1> ping 192.168.1.10

host (255.255.255.252) not reachable

PC1> show ip

NAME       : PC1[1]
IP/MASK    : 192.168.1.1/30
GATEWAY    : 255.255.255.252
DNS        :
MAC        : 00:50:79:66:68:00
LPORT      : 10014
RHOST:PORT : 127.0.0.1:10015
MTU        : 1500

PC1> █
```

**Figure 4:** comandos

Como ves, podemos hacer ping solo a nuestro equipo hermano

