

Rajalakshmi Engineering College

Name: shiloh .s
Email: 240701498@rajalakshmi.edu.in
Roll no: 240701498
Phone: 9488883273
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node*newnode=(struct Node*)malloc(sizeof(struct Node));  
    newnode->item=item;  
    newnode->next=NULL;  
    newnode->prev=NULL;  
    if(*head==NULL)  
    {  
        *head=newnode;  
    }  
    else
```

```

    {
        struct Node*position=*head;
        while(position->next!=NULL)
        {
            position=position->next;
        }
        position->next=newnode;
        newnode->prev=position;
    }
}

void displayForward(struct Node* head) {
    struct Node*temp=head;
    while(temp!=NULL)
    {
        printf(" %c ",temp->item);
        temp=temp->next;
    }
    printf("\n");
}

```

```

void displayBackward(struct Node* tail) {
    struct Node*temp=tail;
    while(temp!=NULL)
    {
        printf(" %c ",temp->item);
        temp=temp->prev;
    }
}

```

```

void freePlaylist(struct Node* head) {
    struct Node*temp;
    while(head!=NULL)
    {
        temp=head;
        head=head->next;
        free(temp);
    }
}

```

```

int main() {
    struct Node* playlist = NULL;
    char item;

```

```
while (1) {
    scanf(" %c", &item);
    if (item == '-') {
        break;
    }
    insertAtEnd(&playlist, item);
}

struct Node* tail = playlist;
while (tail->next != NULL) {
    tail = tail->next;
}

printf("Forward Playlist: ");
displayForward(playlist);

printf("Backward Playlist: ");
displayBackward(tail);

freePlaylist(playlist);

return 0;
}
```

Status : Correct

Marks : 10/10