quadcode

OAuth API

Authorize & Access Token



quadcode

OAuth Authorize **2**
GET /auth/oauth.v5/authorize **2**
Request 2
Responses 4
Response 302 Redirect 4
Response 307 Redirect 5
Response 500 Internal Error 9
OAuth Access Token (SSID) **10**
POST /auth/oauth.v5/token **10**
Request 10
Responses 12
Response 200 Success Response 12
Response 400 Bad Request 13
Response 403 User Is Blocked 16
Response 429 Too Many Requests 17
Response 500 Internal Error 18

OAuth Authorize

GET /auth/oauth.v5/authorize

Initial API for OAuth. Invoked, for example, when clicking on the "Log in via YourBrokerName" button.

Request

response_type* string	Response type, always "code". Indicates that the callback expects to receive an authorization code.
client_id* int64	Client/Application ID.
redirect_uri* string	The page to which the user should be redirected after authorization.
scope* string	Add scopes via a space for authorization, for example, "full offline_access".
state string	A unique status identifier that will be returned in the redirect after authorization.

code_challenge* string	A special code for protection from attacks, must be encoded in ***BASE64URL-ENCODE(SHA256(code_verifier))***. First, the client generates a secret key for each authorization request and then reuses this secret key when exchanging the authorization code for an access token. Thus, if the code is intercepted, it will be useless because the token request relies on the original secret key.
code_challenge_method* string	Encoding method, always **S256**. This parameter specifies that the code must be encoded using SHA-256. This provides an additional security level, as the code cannot be easily guessed or faked.
aff int64	The Aff identifier is responsible for linking the user to the partner.
afftrack string	Additional tracking parameter, used to track the source of traffic.
aff_model string	Indicates the affiliate reward model.

Responses

Response 302 Redirect

Location
string

1. If the user does not have a session, then redirect to the page */login?redirect_url={redirect_url}&aff={aff}&afftrack={afftrack}&aff_model={aff_model}*.
   If **aff, afftrack, aff_model** were specified, they will be added to the end of the URL where redirect_url is the full current one.

2. If the user has a session but has not agreed to use the application, then redirect to the page */oauth/consent?client_id={client_id}&scope={scopes}&redirect_url={redirect_url}*, where **client_id** is the client/application ID, **scopes** is the set of scopes requested by the application when passing them to the api /oauth/authorize, **redirect_url** is the full current request to oauth/authorize. After saving the user's agreement, they will be redirected to this **redirect_url** to continue with oauth/authorize.

3. If the user has a session and has consented to the use of the application, they are redirected to **redirect_uri** (callback) with an authorization code.

Response 307 Redirect

Location
string

- code=oauth_origin_mismatch
- Invalid origin
- Redirects to */oauth/error?code=oauth_origin_mismatch&messages=problem+description&client_id=client+ID*

- code=invalid_oauth_response_type
- Invalid response_type
- Redirects to /oauth/error?code=invalid_oauth_response_type&messages=*problem+description&client_id=client+ID*

- code=invalid_oauth_client_id
- Invalid client_id
- Redirects to */oauth/error?code=invalid_oauth_client_id&messages=problem+description*

- code=oauth_client_disabled
- OAuth client is not active

- Redirects to */oauth/error?code=oauth_client_disabled&messages=problem+description*

- code=invalid_oauth_redirect_uri
- Invalid redirect_uri
- Redirects to */oauth/error?code=invalid_oauth_redirect_uri&messages=problem+description&client_id=client+ID*

- code=oauth_redirect_uri_mismatch
- Redirect_uri does not match with the one specified in the application settings
- Redirects to */oauth/error?code=oauth_redirect_uri_mismatch&messages=problem+description&client_id=client+ID*

- code=invalid_oauth_scopes
- Invalid scope
- Redirects to */oauth/error?code=invalid_oauth_scopes&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client*

- code=missing_oauth_full_scope
- Scope full not passed
- Redirects to
  /oauth/error?code=missing_oauth_full_scope&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client

- code=oauth_client_scopes_mismatch
- The passed scopes do not match with ones specified in the application settings
- Redirects to
  /oauth/error?code=oauth_client_scopes_mismatch&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client

- code=invalid_oauth_code_challenge
- Invalid code_challenge
- Redirects to
  /oauth/error?code=invalid_oauth_code_challenge&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client

- code=invalid_oauth_code_challenge_method
- Invalid code_challenge_method

- Redirects to */oauth/error?code=invalid_oauth_code_challenge_method&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client*

- code=oauth_aff_id_mismatch
- The user is registered under a different affiliate_id
- Redirects to */oauth/error?code=oauth_aff_id_mismatch&messages=problem+description&client_id=client+ID&goback_url=url+return+to+client*

- code=requests_limit_exceeded
- Request limit exceeded
- Redirects to */oauth/error?code=requests_limit_exceeded&messages=problem+description&client_id=client+ID*

- code=internal_error
- Internal error
- Redirects to */oauth/error?code=internal_error&messages=problem+description*

Response 500 Internal Error

The system is not working properly.

code* string	*Error code*
message* string	*Details of the error*

JSON

```
{
  "code": "internal_error",
  "message": "Oops! Something went wrong"
}
```

OAuth Access Token (SSID)

POST /auth/oauth.v5/token

The endpoint for getting an access_token (ssid) by authorization code or refresh token. Invoked after successful user authorization on the authorization page.

Request

grant_type* string	*It could be authorization_code or refresh_token*
code string	*Authorization code, if grant_type=authorization_code*
refresh_token string	*Refresh token if grant_type=refresh_token*
client_id* int64	*Client/Application ID*

Swapping code for an access token (SSID).

JSON

```
{
  "grant_type": "authorization_code",
  "code": "3d4wq23u3sd...dsfw5e443s",
  "redirect_uri": "http://example.com",
  "client_id": 123456789,
  "code_verifier": "c0de123...456789"
}
```

client_secret
string

Client/application secret, if grant_type=refresh_token

redirect_uri
string

Must match the one for which the code was generated when requesting oauth/authorize, if grant_type=authorization_code

code_verifier
string

The original value from which code_challenge should be generated by calculating SHA256(code_verifier). Code_verifier must be 43–128 chars and only ALPHA / DIGIT / - . _ ~ allowed

Swapping an update token for an access token (SSID).

JSON

```
{
  "grant_type": "refresh_token",
  "refresh_token":
"er4wq74u34a...cstw9e14op",
  "client_id": 123456789,
  "client_secret": "s3cret123456789"
}
```

Responses

Response 200 Success Response

Getting SSID as access_token.

access_token* string	*Access token, also known as SSID*
token_type* string	*Always “Bearer”*
expires_in* Integer	*SSID lifetime in seconds*
refresh_token* string	*Token for issuing a new SSID if the scope was “offline_access”*
scope* string	*The scope set that was requested (full offline_access)*

JSON

```
{
  "access_token":
"2/c4aa6d5e97b57998a9c2589f42a2as",
  "token_type": "Bearer",
  "expires_in": 1345234,
  "refresh_token":
"sd7fdsfsd4sajdqwewd2sasfj2qawewqeoge7
rodsv24c2xznv0",
"scope": "full offline_access"
}
```

Response 400 Bad Request

Common error on invalid request.

code* string	*Error code*
message* string	*Details of the error*

Invalid request.

```JSON
{
  "code": "bad_request",
  "message": "Bad request"
}
```

The grant_type is not passed or has an invalid format.

```JSON
{
  "code": "invalid_oauth_grant_type",
  "message": "Error description"
}
```

The code is not passed or has an invalid format.

```JSON
{
  "code": "invalid_oauth_code",
  "message": "Error description"
}
```

The client_id is not passed or has an invalid format.

```JSON
{
  "code": "invalid_oauth_client_id",
  "message": "Error description"
}
```

Code_verifier has an invalid format.

```JSON
{
  "code": "invalid_code_verifier",
  "message": "Error description"
}
```

Token expired.

```JSON
{
  "code": "token_expired",
  "message": "Error description"
}
```

Invalid token.

```JSON
{
  "code": "bad_token",
  "message": "Error description"
}
```

OAuth client inactive.

```JSON
{
  "code": "oauth_client_disabled",
  "message": "Error description"
}
```

Response 403 User Is Blocked

The user account is blocked.

code*
string

Error code

```
JSON
{
  "code": "blocked",
  "message": "User account is blocked"
}
```

The application does not have scope to re-request access_token.

```
JSON
{
  "code": "no_oauth_client_scope",
  "message": "Error description"
}
```

The user did not agree to the access_token re-request.

```
JSON
{
  "code": "no_oauth_user_consent",
  "message": "Error description"
```

message*
string

Details of the error

```
}
```

Response 429 Too Many Requests

The rate limit on requests is triggered.

code* string	*Error code*
message* string	*Details of the error*

```JSON
{
  "code": "requests_limit_exceeded",
  "ttl": 120,
  "message": "Request limit is exceeded"
}
```

Response 500 Internal Error

The system is not working properly.

code* string	*Error code*
message* string	*Details of the error*

JSON

```
{
  "code": "internal_error",
  "message": "Oops! Something went wrong"
}
```