

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Issue date: 7/12/2022 Revision date: 7/12/2022 Version: 1.0

Безопасность Данные Лист

Изменено силикон герметик

SECTION 1 Chemical product and company identification

Chemical English name : Modified silicone sealant
Product code : H922
Name of company : SHANGHAI APHYS DONNTAL CHEMICALS CO.,LTD.
Address : Number 99,Tianzhou Rd, Shanghai,PRC
Fax : +86 21 34227873
Tel. : +86 21 54937114
E-mail : huang@aphysbond.com
Website : [Website: www.aphysbond.com](http://www.aphysbond.com)
Emergency number : +86 21 54937114
Recommended use of the chemical : Bonding and sealing
Restricted use of the chemical : No information available

Химическая

Английский

Имя

Изменено

Сили

SECTION 2 Hazards identification

Продукт

код

Emergency overview

The product is liquid. ШАНХАЙ

GHS hazard classification

Число

99, Т

Not classified

Label elements

Факс

Hazard pictograms (GHS CN) : Not applicable.

Signal word (GHS CN) : Not applicable.

Hazard statements (GHS CN) : Not applicable.

Precautionary statements (GHS CN)

Prevention measures : Not applicable..

Incident response : Not applicable.

Safe storage : Not applicable.

Disposal : Not applicable.

Веб-сайт:

Physical and chemical hazards

No additional information available

Health hazards

No additional information available

Environmental hazards

No additional information available

Other hazards

No additional information available

РАЗДЕЛ

Опас

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519
Revision date: 7/12/2022

Безопасность Данные Лист

SECTION 3 Composition/information on ingredients

Изменено силикон герметик
Product form : Mixture.

Скомпилировано согласно Редакция: 12.07.2022	К	ГБ/Т	ГБ/Т	Concentration or concentration ranges (w/w %)	CAS No.
Ingredient(s):					
Calcium Carbonate				35 – 70	471-34-1
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-[3-(dimethoxymethylsilyl)propyl]-.omega.-[3-(dimethoxymethylsilyl)propoxy]-				РАЗДЕЛ 15 – 30	Состав/информация Not availabl
1,2-Benzene dicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich				15 – 30	68515-48-0 Смесь.
Titanium dioxide				2 – 10	13463-67-7
Silane, ethenyltrimethoxy-				1 – 3	2768-02-7 концентрация
Dibutyltin dilaurate				0 – 0.1	77-58-7

SECTION 4 First-aid measures

Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a poison center or a doctor

First-aid measures after skin contact : Wash skin with plenty of water.
If skin irritation: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.
Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects

Symptoms/effects : No information available

Advices for first aid responders

Do not attempt to take action without suitable protective equipment.

Notes for the doctor

Other medical advice or treatment : Treat symptomatically

SECTION 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Water spray
Dry powder

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519
Revision date: 7/12/2022

Безопасность Данные Лист

Unsuitable extinguishing media : Foam
Carbon dioxide
Изменено СИЛИКОН герметик : Do not use a water jet since it may cause the fire to spread

Specific hazards : Toxic fumes may be released
Скомпиллировано согласно к ГБ/Т ГБ/Т
Hazardous decomposition products in case of fire :
Редакция дата: 12.07.2022

Advice for firefighters and protective measures

Firefighting instructions : Cool down the containers exposed to heat with a water spray
Do not allow run-off from fire fighting to enter drains or water courses
Approach from upwind
Complete protective clothing
Do not allow run-off from fire fighting to enter drains or water courses
Eliminate all ignition sources if safe to do so
Неподходящий тушение СМИ
Protection during firefighting : Do not attempt to take action without suitable protective equipment
Self-contained breathing apparatus
Complete protective clothing
Конкретные опасности

Опасно разложение продукты в Токсичный дым

SECTION 6 Accidental release measures

дело из ОГОНЬ

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Remove all sources of ignition
Совет для пожарные и защитный меры
Emergency procedures :
Пожаротушение инструкции : Ensure good ventilation of the work station
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer)
Only qualified personnel equipped with suitable protective equipment may intervene
Avoid breathing dust/fume/gas/mist/vapours/spray.
Access forbidden to unauthorised personnel
Круто вниз
Делай не разрешит
Подход из
Полное за

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment
For further information refer to section 8: "Exposure controls/personal protection"
Делай не разрешит
устранить все

Environmental precautions

Avoid release to the environment. :
Notify authorities if product enters sewers or public waters
Защита в течение пожаротушение
Делай не попытка
Автономный

Methods and material for containment and cleaning up

Methods for cleaning : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, perlite or universal binding agents).
Collect leaking and spilled liquid in sealable containers as far as possible
Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations
For containment : Collect spillage.
РАЗДЕЛ Случайный

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519
Revision date: 7/12/2022

Безопасность Данные Лист

Prevention measures for secondary accidents

Prevention Measures for Secondary Accidents : Clean contaminated objects and areas thoroughly observing environmental regulations.
Do not discharge the waste into the drain
Do not discharge into drains or rivers
Eliminate all ignition sources if safe to do so.
Other information : Dispose of materials or solid residues at an authorized site

Профилактика меры для вторичный несчастные случаи

SECTION 7 Handling and storage

Handling	Профилактика	Меры для Вторичный	Чистый	загрязненный
Precautions for safe handling	Несчастные случаи	: Ensure good ventilation of the work station Avoid contact with skin and eyes Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment Always wash hands after handling the product Avoid inhalation of vapours Handle and open the container with care Handle in accordance with good industrial hygiene and safety practice	правила.	
Hygiene measures	Другое информация	: Separate working clothes from town clothes. Launder separately Do not eat, drink or smoke when using this product. Always wash hands after handling the product	Делай не разряд Делай не разряд Утилизовать из	все
Storage				
Storage conditions		: Store in a well-ventilated place. Keep cool. Keep away from food, drink and animal feeding stuffs		
Technical measures		: Store in a well-ventilated place. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage Keep only in the original container		
Обработка				
Material used in packaging/containers		: No additional information available		
Incompatible materials	меры предосторожности для	No information available.	Убедитесь, что	хорошо

SECTION 8 Exposure controls / Personal protection equipment

Occupational exposure limits

Calcium Carbonate (471-34-1)	Носить	личный
China - Occupational Exposure Limits	Всегда	мыть
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	Избегайте ингаляция
	Ручка	и
	Ручка	в соо

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519
Revision date: 7/12/2022

Безопасность Данные Лист

Titanium dioxide (13463-67-7)	
China - Occupational Exposure Limits	
Local name	二氧化钛粉尘 #Titanium dioxide dust
OEL PC-TWA	8 mg/m³ (total dust)
Chemical category	Possibly carcinogenic to humans dust
Catalogue of Occupational Hazard Factors	Category 1 - Dusts
Remark (CN)	G2B (对人可疑致癌 (Possibly carcinogenic to humans))
Regulatory reference	GBZ 2.1-2019
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m³
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Dibutyltin dilaurate (77-58-7)	
China - Occupational Exposure Limits	
OEL PC-TWA	0.1 mg/m³
OEL PC-STEL	0.2 mg/m³
Chemical category	Skin notation

Каталог из Профессиональный Опасность Факторы Категория

Biological limit values
No additional information available

Monitoring methods (KH)
No additional information available

Appropriate engineering controls
Ensure good ventilation of the work station

Personal protective equipment

Environmental exposure controls	: Avoid release to the environment.	
Hand protection	: Chemically resistant protective gloves	Пределы
Eye protection	: Chemical goggles or safety glasses	
Skin and body protection	: Wear suitable protective clothing	
Respiratory protection	: Self-contained breathing apparatus	мг/м?

SECTION 9 Physical and chemical properties

Physical state : Paste
Appearance : Black paste
Odour : No data available

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность		Данные	Лист
pH		: No data available	
Melting point	Изменено	: Not applicable	
Freezing point		: No data available	
Boiling point	оставлено	: No data available	
Flash point	Редакция	: No data available	
Auto-ignition temperature	дата: 12.07.2022	: No data available	
Decomposition temperature		: No data available	
Flammability		: No data available	Нет данные ДОСТУПНО
Vapour pressure		: No data available	
Relative vapour density at 20°C	давление	: No data available	
Density		: No data available	
Solubility	Замораживание точка	: No data available	
Partition coefficient n-octanol/water (Log Pow)		: No data available	
Viscosity, kinematic	Кипение точка	: No data available	
Viscosity, dynamic	Флэш точка	: No data available	
Lower explosion limit		: No data available	
Upper explosion limit		: No data available	
Radioactive	Самовоспламенение температура	: No	
Explosive properties		: No data available	
Oxidising properties	Разложение температура	: No data available	

Воспламеняемость

SECTION 10 Stability and reactivity

Chemical stability	давление	: Stable under normal conditions	Нет данные ДОСТУПНО
Possibility of hazardous reactions		: No dangerous reactions known under normal conditions of use	
Conditions to avoid	пар	: Avoid excessive heat for prolonged periods of time. Avoid high temperatures	Нет данные ДОСТУПНО
Incompatible materials		: No additional information available	
Hazardous decomposition products		: Under normal conditions of storage and use, hazardous decomposition products should not be produced	Нет данные ДОСТУПНО

Растворимость

SECTION 11 Toxicological information

Раздел	коэффициент	н-октанол/вода	(Журнал	Нет	данные	доступно
Acute toxicity						
Acute toxicity (oral)		: Not classified				
Acute toxicity (dermal)		: Not classified				
Acute toxicity (inhalation)	кинематический	: Not classified		Нет	данные	доступно

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (68515-48-0)

LD50 oral rat	Вязкость, динамический	> 10000 mg/kg	Нет	данные	доступно
LD50 dermal rabbit	взрыв	> 3160 mg/kg	Нет	данные	доступно

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность Данные Лист

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (68515-48-0)

LC50 Inhalation - Rat Именено СИЛИКОН > 4.4 мг/л герметик

Calcium Carbonate (471-34-1)

LD50 oral rat Редакция дата: 12.07.2022 6450 мг/кг

LD50 dermal rat > 2000 мг/кг bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) 1,2-Бензолдикарбоновая кислота ди-C8-10-разветвленный алкильные

LC50 Inhalation - Rat > 3 мг/л air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) ЛКС0 Вдыхание Крыса

LC50 Inhalation - Rat (Dust/Mist) > 3 мг/л Source: ECHA

Titanium dioxide (13463-67-7) Карбонат

LD50 oral rat > 10000 мг/кг

LC50 Inhalation - Rat 5.09 мг/л/4h Крыса оральным крыса МГ/КГ

LC50 Inhalation - Rat (Dust/Mist) > 6.82 мг/л Source: ECHA

Silane, ethyltrimethoxy (2768-02-7) Крыса

LD50 oral rat 7340 µl/kg

LD50 dermal rabbit 3.54 ml/kg (Острая Кожная

LC50 Inhalation - Rat 16.8 мг/л/4h

Dibutyltin dilaurate (77-58-7)

LD50 Вдыхание Крыса LD50 dermal rat > 2000 мг/кг

Skin corrosion/irritation

ТОКСИЧНОСТЬ),

Skin corrosion/irritation : Not classified

Агентство по охране окружающей среды ОППТС

Calcium Carbonate (471-34-1)

pH 8 – 9 (aqueous solution)

LD50 Вдыхание Крыса (Пыль/Туман) МГ/Л

Titanium dioxide (13463-67-7)

pH 7 Source: ECHA

Serious eye damage/eye irritation Титан диоксид

Serious eye damage/irritation : Not classified

Calcium Carbonate (471-34-1)

pH 8 – 9 (aqueous solution) ЛДС0 оральным крыса МГ/КГ

ЛКС0 Вдыхание Крыса

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность Данные Лист

Titanium dioxide (13463-67-7)

pH Изменено силикон 7 Source: ECHA

Respiratory or skin sensitisation

Скомпилировано согласно к ГБ/Т ГБ/Т

Respiratory or skin sensitisation : No data available

Germ cell mutagenicity

Germ cell mutagenicity : No data available

Carcinogenicity

Carcinogenicity : Not classified

Источник: ЭХА

Titanium dioxide (13463-67-7)

3a

IARC group 2B - Possibly carcinogenic to humans

Дыхательная система или

Reproductive toxicity

Reproductive toxicity : No data available

Нет данные доступн

STOT - single exposure

STOT-single exposure : No data available

STOT - repeated exposure

STOT-repeated exposure : Not classified

Dibutyltin dilaurate (77-58-7)

Нет данные доступн

STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure.

Неф

Calcium Carbonate (471-34-1)

Канцерогенность

NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Канцерогенность

NOAEC (inhalation, rat, dust/mist/fume, 90 days) 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Титан диоксид

Aspiration hazard

Aspiration hazard : No data available

МАИР группа

2Б Возможно

SECTION 12 Ecological information

Ecotoxicity

Репродуктивный

ТОКСИЧНОСТЬ

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Репродуктивный

токсичность

Нет данные доступн

Hazardous to the aquatic environment, short-term (acute) : Not classified

СТОТ

ОДИНОКИЙ

воздействие

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519
Revision date: 7/12/2022

Безопасность	Данные	Лист
Hazardous to the aquatic environment, long-term (chronic)		: Not classified

Изменено	силикон	герметик
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (68515-48-0)		
LC50 - Fish [1]	Скомпилировано согласно к ГБ/Т	0.42 mg/l (Exposure time: 96 h - Species: Ictalurus punctatus [flow-through])
LC50 - Fish [2]	Редакция дата: 12.07.2022	> 0.16 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	Опасно к	> 0.086 mg/l (Exposure time: 48 h - Species: Daphnia magna) классифицированный
EC50 96h - Algae [1]	долгосрочный (хронический)	> 2.8 mg/l (Species: Pseudokirchneriella subcapitata)
Partition coefficient n-octanol/water (Log Pow)		8.8 – 9.7 (at 25 °C (at pH 4.6))

Calcium Carbonate (471-34-1)		
1,2-Бензолдикарбоновая кислота кислота, ди-С8-10-разветвленный алкильные сложн		
LC50 - Fish [1]		> 56000 mg/l Source: ECOTOX
EC50 96h - Algae [1]	Рыба	22000 mg/l Source: Ecological Structure Activity Relationships 0,42 мг/л чер
BCF - Fish [1]		(no bioaccumulation)

Titanium dioxide (13463-67-7)		
(Время воздействия): Мг/л		
LC50 - Fish [1]		> 100 mg/l
EC50 - Other aquatic organisms [1]		> 100 mg/l Test organisms (species):

Silane, ethenyltrimethoxy- (2768-02-7)		
Ракообразные		
LC50 - Fish [1]		191 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [not specified])

Persistence and degradability
EC50 96 часов Водоросли
No additional information available

Bioaccumulative potential

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (68515-48-0)	Раздел коэффициент н-октанол/вода (Журнал Pay)	8,8—9,7 (при
Partition coefficient n-octanol/water (Log Pow)		8.8 – 9.7 (at 25 °C (at pH 4.6))

Calcium Carbonate (471-34-1)		
Карбонат		
BCF - Fish [1]		See section 12.1 on ecotoxicology(no bioaccumulation)

Dibutyltin dilaurate (77-58-9)		
Мг/л		
Partition coefficient n-octanol/water (Log Pow)		4.44 (20.8 °C, OECD Guideline 107)

Mobility in EC50 96 часов Водоросли Мг/л

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (68515-48-0)		
Partition coefficient n-octanol/water (Log Pow)		8.8 – 9.7 (at 25 °C (at pH 4.6)) (нет биоаккумуляция

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность			Данные	Лист
Calcium Carbonate (471-34-1)				
BCF - Fish		Именено	СИЛИКОН	See section 12.1 on ecotoxicology (no bioaccumulation)
Dibutyltin dilaurate (77-58-7)				
Partition coefficient n-octanol/water (Log Pow)		Регистрация	12.07.2022	4.44 (20.8 °C, OECD Guideline 107)

Other adverse effects

Classification procedure (Ozone) : No data available

Кальций Карбонат

SECTION 13 Disposal considerations

Waste treatment methods		до на Рыба	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Dispose of contents/container in accordance with licensed collector's sorting instructions and in accordance to local and regional legislation.
Contaminated container and packaging		ДИБУТИЛОЛОВО развернуть	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Dispose of contents/container in accordance with licensed collector's sorting instructions and in accordance to local and regional legislation.
Additional information		Раздел коэффициент	н-октанол/вода (Журнал Pay) 4,44 (20,8 °C)
		Другое неблагоприятный эффекты	: No additional information available

SECTION 14 Transport information

Overland transport (JT/T 617)	Классификация UN RTDG	процедура Transport by sea	(Озон) Air transport	Inland waterway transport	Нет данные Rail transport
UN number					
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated
Proper shipping name					
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated
Transport hazard class(es)					
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated
Packing group					
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated
Environmental hazards					
Not applicable.	Not applicable.	Not regulated	Not regulated	Not regulated	Not regulated

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность Данные Лист

Special transport precautions

Overland transport (JT/T 617) силикон герметик
Not applicable.

UN RTDG Скомпилировано согласно к ГБ/Т ГБ/Т
Not applicable. дата: 12.07.2022

Transport by sea
Not regulated

Air transport Специальный Транспорт меры предосторожности
Not regulated

Inland waterway transport Сухопутный Транспорт
Not regulated

Rail transport классифицированный применимый.
Not regulated

ООН РТДГ

SECTION 15 Regulatory information

New Chemical Substance Environmental Management Registration Measures (MEE Order 12 of 2020) классифицированный ПРИМЕНИМЫЙ

Inventory of Existing Chemical Substances : Contains listed substance(s)
in China (16CSG) транспорт автор море Calcium Carbonate (CAS-No. 471-34-1)
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (CAS-No. 68515-48-0)
классифицированный регулируемый Titanium oxide (CAS-No. 13463-67-7)
Silane, ethenyltrimethoxy- (CAS-No. 2768-02-7)
Воздух Транспорт Ditin butyl dilaurate (CAS-No. 77-58-7)

Regulations on the Safe Management of Hazardous Chemicals (Decree 591 of the State Council)

Catalogue of Hazardous Chemicals (2015) : Contains Hazardous Chemical(s)
Dibutyltin didodecylate (CAS-No. 77-58-7)

Catalogue of Hazardous Chemicals Prohibited from Inland Waterway Transport : Contains listed substance(s)
водный путь транспорт Dibutyltin dilaurate (UN-No. 2788)

Law of the People's Republic of China on the Prevention and Control of Occupational Diseases классифицированный регулируемый

Catalogue for Classification of Hazardous Factors of Occupational Diseases : Contains listed substance(s)
Железнодорожный Транспорт Calcium Carbonate (CAS-No. 471-34-1)
Titanium dioxide dust (CAS-No. 13463-67-7)

Other domestic regulatory measures классифицированный регулируемый

Dangerous Goods List (GB 12268-2012) : Contains listed substance(s)
ORGANOTIN COMPOUND, LIQUID, N.O.S. (UN-No. 2788)

SECTION 16 Other information

Version : 1.0

Issue date : 7/12/2022

Новый Химическая Вещество Экологическая Управление 7/12/2022 (Revision date) CN - en 11/12

Safety Data Sheet

Modified silicone sealant H922

Compiled according to GB/T 16483, GB/T 17519

Revision date: 7/12/2022

Безопасность Данные Лист

Revision date : 7/12/2022

Data sources : Loli герметик
Изменено силикон ECHA reference
Составлено согласно к ГБ/Т Catalogue of Hazardous Chemicals (2015)
ГБ/Т

Abbreviations and acronyms Редакция дата 12.07.2022

ADN			European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	Редакция	дата	Agreement concerning the International Carriage of Dangerous Goods by Road	12.07.2022
IATA			International Air Transport Association	
IMDG	Данные	источники	International Maritime Dangerous Goods	Лоли
EC50			Median effective concentration	
LC50			Median lethal concentration	ЭХА ссылка
LD50			Median lethal dose	
RID			Regulations concerning the International Carriage of Dangerous Goods by Rail	Каталог из
SDS			Safety Data Sheet	

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging
Сокращения и аббревиатуры

Other information : No information available
ВОПРОС

Indication of changes :
Not applicable. автор Внутренний

Safety Data Sheet (SDS), China

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

ЭКСО				
			медиана	смерть
ЛДСО			медиана	смерть
РИД			Правила	
Паспорт безопасности			Безопасность	Данные