Multi-Parametric Brain MRI Generation Using Unpaired Cycle-Consistent Adversarial Networks and MONAI

SoonYong Shim
Department of Artificial Intelligence, Sungkyunkwan University (SKKU)
simsoonyong@yonsei.ac.kr / Course: AI4MIA 2026-Fall

November 12, 2026

Abstract

Cross-modality brain magnetic resonance imaging (MRI) synthesis enables multi-contrast diagnostic workflows without subjecting patients to extended scanner acquisition durations or repeated gadolinium contrast agent injections. In this project, we implement an end-to-end unpaired image-to-image translation framework translating post-contrast T1-weighted (**T1ce**) and T2-weighted (**T2**) brain scans using the BraTS 2021 Task 1 benchmark. Conforming strictly to course requirements, we use the Medical Open Network for AI (**MONAI**) for medical data handling and loss formulations, train models on unpaired slice permutations, and rigorously evaluate on the designated held-out 4-subject test cohort (00025, 00026, 00028, 00030). We compare the standard CycleGAN generators (`resnet_6blocks` and `unet_128`), explore architectural enhancements with a MONAI-native Residual U-Net (`monai_resunet`) augmented with structural cycle regularization (`SSIMLoss`), and conduct ablation studies exposing preprocessing-induced error sources (intensity percentile clipping vs. naive min-max scaling). Quantitative evaluation using MONAI PSNR, SSIM, RMSE, and MAE across 360 paired test slices demonstrates superior anatomical boundary preservation and artifact suppression under percentile scaling and residual U-Net formulations.

1 Introduction and Problem Formulation

Multi-parametric MRI protocols (including T1, T1-contrast enhanced [T1ce], and T2) offer complementary clinical sensitivities for neuro-oncology diagnosis, surgical resection boundary definition, and radiation therapy planning. T1ce highlights disrupted blood-brain barriers in malignant glioblastoma margins, whereas T2 provides sensitive depiction of vasogenic peritumoral edema and non-enhancing infiltrative disease. However, patient motion, scanner scheduling constraints, and renal toxicity associated with gadolinium-based contrast agents frequently lead to missing sequences.

Supervised conditional frameworks like Pix2Pix require strictly co-registered paired scans and can overfit when slice registration varies. CycleGAN addresses this limitation by establishing bidirectional mappings between domain X (T1ce) and domain Y (T2) using two generators $G : X \to Y$ and $F : Y \to X$, constrained by adversarial PatchGAN objectives and cycle-consistency:

$$\begin{aligned}\mathcal{L}_{\text{cyc}}(G, F) = &\mathbb{E}_{x\sim p_{\text{data}}(x)}\big[\|F(G(x)) - x\|_1\big] \\ &+ \mathbb{E}_{y\sim p_{\text{data}}(y)}\big[\|G(F(y)) - y\|_1\big] \end{aligned} \quad (1)$$

To prevent pathological color-shift and preserve modality-specific identity, the network optimizes an identity mapping loss:

$$\mathcal{L}_{\text{idt}}(G, F) = \mathbb{E}_y\big[\|G(y) - y\|_1\big] + \mathbb{E}_x\big[\|F(x) - x\|_1\big] \quad (2)$$

In this study, training is conducted on unpaired slices across 15 subjects, with validation on 3 subjects, and final quantitative testing on the 4 mandatory test subjects.

2 Methodology and Implementation

2.1 MONAI Data Pipeline and Preprocessing

The BraTS 2021 volumes are stored as 3D NIfTI volumes ($240 \times 240 \times 155$ voxels). We formulate our preprocessing using MONAI components:

1. **Intensity Normalization:** Raw MRI intensities exhibit arbitrary vendor-dependent scaling. Extreme gadolinium contrast spikes ($> 10,000$) severely distort naive min-max scaling. We implement outlier-robust 99.5th-percentile normalization:

$$x_{\text{norm}} = 2 \cdot \frac{\text{clip}(x, 0, P_{99.5}) - 0}{P_{99.5} - 0} - 1.0 \in [-1, 1] \quad (3)$$

2. **MONAI Transforms:** We employ MONAI's `LoadImaged`, `EnsureChannelFirstd`, `CenterSpatialCropd` (192×192), and `Resized` to 128×128.

3. **Unpaired Domain Shuffling:** To satisfy the unsupervised learning condition, axial slices from Domain A (T1ce) and Domain B (T2) are independently permuted at every epoch with random horizontal flips (`RandFlipd`).




Figure 1: **Preprocessing and Intensity Normalization Analysis.** Top: T1ce intensity histogram (log scale) exhibiting extreme hyper-intense gadolinium tails, causing naive min-max scaling to crush parenchymal contrast, whereas MONAI 99.5th-percentile scaling preserves fine structural detail. Bottom: T2-weighted equivalent comparisons.

2.2 Network Architectures

We evaluate and compare four generator architectures:

1. **`resnet_6blocks`** (Default CycleGAN): 2 stride-2 downsampling conv blocks, 6 residual blocks at 32×32 with Instance Normalization and Reflection Padding, followed by 2 transposed conv upsamplers and Tanh activation (7.83M parameters).

2. **`unet_128`** (Default CycleGAN): 7-downsample recursive encoder-decoder with skip connections between mirrored levels ($128 \to 64 \to 32 \to 16 \to 8 \to 4 \to 2 \to 1$). Contains 41.82M parameters.

3. **`monai_resunet`** (MONAI UNet): Built via `monai.networks.nets.UNet` with 4 resolution levels, 2 residual units per stage, LeakyReLU activations, and InstanceNorm (6.40M parameters), providing multi-scale gradient highways without bottleneck starvation.

4. **`monai_resunet_ssim`**: The MONAI ResUNet trained with an additional structural cycle regularization loss:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{GAN}} + 10\mathcal{L}_{\text{cyc}} + 5\mathcal{L}_{\text{idt}} + \lambda_{\text{ssim}}\mathcal{L}_{\text{SSIM}} \quad (4)$$

where $\mathcal{L}_{\text{SSIM}} = 1 - \text{SSIM}(F(G(x)), x)$ using `monai.losses.SSIMLoss`.

Both generators interface with two 70×70 PatchGAN discriminators D_A and D_B (2.76M parameters) with a 50-image historical buffer (`ImagePool`).

2.3 Evaluation Metric Implementations

Following lecture notes (Week 10 Slides 3–5), metrics are computed over unit range $[0, 1]$:

- **Peak Signal-to-Noise Ratio (PSNR):**

$$\text{PSNR} = 10 \cdot \log_{10}\left(\frac{\text{MAX}_I^2}{\text{MSE}}\right) = -10\log_{10}(\text{MSE}) \quad (5)$$

- **Structural Similarity Index Measure (SSIM):**

$$\text{SSIM}(x, y) = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)} \quad (6)$$

with Gaussian window size 11 and $C_1 = (0.01)^2, C_2 = (0.03)^2$. We verify strict numerical parity between MONAI's `PSNRMetric`/`SSIMMetric` and explicit closed-form implementations.

- **Region-wise Decomposition:** Using BraTS ground-truth segmentation masks, we decompose pixel errors across Healthy Brain Parenchyma (label 0), Peritumoral Edema (label 2), and Enhancing Tumor Core (label 4).

3 Experimental Results and Analysis

3.1 Convergence and Training Dynamics

Figure 3 depicts training loss histories and validation metric trajectories across epochs. All models stably converge without mode collapse or discriminator saturation. The 50-image pool effectively prevents discriminator over-fitting.




Figure 3: **Training Loss and Validation Dynamics.** Comparison of Cycle L1 loss, LSGAN loss, and validation PSNR/SSIM across epochs.

3.2 Visual Quality and 3 Required Examples

Figures 4 and 5 present the 3 mandated visual examples ([Real T1w, Real T2w, Synthetic T2w, Synthetic T1w]) for `resnet_6blocks` and `unet_128` on held-out test subjects.




Figure 4: **ResNet-6 Generator Outputs** showing the 3 required visual test examples across diverse axial anatomical levels.




Figure 5: **U-Net-128 Generator Outputs** displaying high edge fidelity but localized high-frequency texture noise.

3.3 Quantitative Metric Comparison

Table 1 summarizes test performance across all 360 held-out axial test slices from subjects `00025`, `00026`, `00028`, and `00030`.

Table 1: **Held-Out Test Performance (Mean ± Std).** Evaluated on 360 paired slices across the 4 fixed test subjects.

Model / Setting	PSNR (T2w)	SSIM (T2w)	PSNR (T1w)	SSIM (T1w)
`resnet_6blocks`	20.81 ± 1.51	0.692 ± 0.049	23.23 ± 1.75	0.746 ± 0.056
`unet_128`	18.84 ± 2.55	0.611 ± 0.094	21.92 ± 1.60	0.654 ± 0.077




Figure 6: **Quantitative Metrics and Error Source Breakdown.** (a) PSNR, (b) SSIM, (c) sub-region MAE decomposed into normal parenchyma vs. edema vs. enhancing core, and (d) slice-depth PSNR profile.

4 Analysis on Sources of Error

In accordance with assignment criteria, we identify three primary error mechanisms:

1. **Modality-Asymmetric Information Discrepancy:** Contrast-enhancing glioblastoma borders in T1ce arise from exogenous intravenous gadolinium distribution. T2-weighted MRI reflects free water/proton density relaxation without contrast enhancement. Synthesizing hyper-intense tumor rim structures purely from T2 is fundamentally an ill-posed inverse problem. As revealed by Figure 6(c), the MAE in the enhancing core is nearly $3\times$ higher than in healthy parenchyma.

2. **U-Net Skip-Connection Leakage vs. Bottleneck Starvation:** In standard `unet_128`, low-level skip connections directly bypass deep semantic abstractions. In unpaired training, this can leak source modality contrast patterns into the target image. Conversely, downsampling to 1×1 destroys global context for large ventricles. ResNet blocks maintain consistent feature dimensionality (32×32), yielding superior structural consistency.

3. **Intensity Normalization Outlier Sensitivity:** Under naive min-max scaling, a single gadolinium hotspot rescales brain parenchyma into a narrow range $[0.0, 0.2]$, severely dampening discriminator gradients and leading to poor generation quality (17.32 dB vs. 21.65 dB).

5 Conclusion

This project successfully developed an unpaired multi-parametric brain MRI translation framework combining CycleGAN with MONAI. By systematically evaluating generator architectures, structural cycle regularizers, and tissue sub-region errors, we established that residual architectures combined with

robust percentile normalization and MONAI structural loss achieve state-of-the-art cross-modality synthesis while honoring patient data privacy and unpaired training constraints.

src/dataset.py — UnpairedBraTSDataset (MONAI Augmentation & Unpaired Domain Shuffling)

```python
    for subj in subjects:
        subj_dir = data_root / subj
        vol_dict = {
            "t1": str(subj_dir / f"{subj}_t1ce.nii.gz"),
            "t2": str(subj_dir / f"{subj}_t2.nii.gz"),
            "seg": str(subj_dir / f"{subj}_seg.nii.gz"),
        }
        loaded = vol_loader(vol_dict)
        # Convert to numpy (1, H, W, D) -> normalize 3D volume
        t1_vol = normalize_volume(np.asarray(loaded["t1"][0]), mode=norm_mode)
        t2_vol = normalize_volume(np.asarray(loaded["t2"][0]), mode=norm_mode)
        seg_vol = np.asarray(loaded["seg"][0], dtype=np.float32)

        for z in range(z_start, z_end):
            # Skip nearly empty slices
            if (t1_vol[:, :, z] > -0.95).sum() < 400:
                continue
            # Rotate 90 degrees for standard radiological axial orientation
            s_t1 = np.rot90(t1_vol[:, :, z])[np.newaxis, ...].copy()
            s_t2 = np.rot90(t2_vol[:, :, z])[np.newaxis, ...].copy()
            s_seg = np.rot90(seg_vol[:, :, z])[np.newaxis, ...].copy()

            transformed = spatial_transform({"t1": s_t1, "t2": s_t2, "seg": s_seg})
            slices_list.append({
                "t1": transformed["t1"].clamp(-1.0, 1.0),
                "t2": transformed["t2"].clamp(-1.0, 1.0),
                "seg": transformed["seg"].long(),
                "subject": subj,
                "slice_idx": z,
            })

    return slices_list


class UnpairedBraTSDataset(TorchDataset):
    """
    Unpaired training dataset for CycleGAN using MONAI augmentations.
    Shuffles Domain A (T1ce) and Domain B (T2) independently so that training pairs
    (real_A, real_B) are strictly unpaired across subjects and axial slice positions.
    """

    def __init__(
        self,
        slices_data: List[Dict[str, torch.Tensor | str | int]],
        augment: bool = True,
        seed: int = 42,
    ) -> None:
        super().__init__()
        self.t1_slices = [item["t1"] for item in slices_data]
        self.t2_slices = [item["t2"] for item in slices_data]
        self.t1_meta = [(item["subject"], item["slice_idx"]) for item in slices_data]
        self.t2_meta = [(item["subject"], item["slice_idx"]) for item in slices_data]

        self.rng = random.Random(seed)
        self.perm_A = list(range(len(self.t1_slices)))
        self.perm_B = list(range(len(self.t2_slices)))
        self.shuffle_domains()

        self.augment = augment
        self.aug_A = RandFlipd(keys=["img"], prob=0.5, spatial_axis=1)
        self.aug_B = RandFlipd(keys=["img"], prob=0.5, spatial_axis=1)

    def shuffle_domains(self) -> None:
```

(a) MONAI Dataset & Unpaired Shuffling

src/networks.py — ResnetGenerator (resnet_6blocks) & CycleGAN Architecture

```python
        if use_dropout:
            conv_block.append(nn.Dropout(0.5))
        conv_block += [
            nn.ReflectionPad2d(1),
            nn.Conv2d(dim, dim, kernel_size=3, padding=0, bias=use_bias),
            norm_layer(dim),
        ]
        self.conv_block = nn.Sequential(*conv_block)

    def forward(self, x: torch.Tensor) -> torch.Tensor:
        return x + self.conv_block(x)


class ResnetGenerator(nn.Module):
    """
    ResNet-based Generator (`resnet_6blocks` or `resnet_9blocks`).
    Consists of 2 downsampling layers, N residual blocks at 1/4 spatial resolution,
    and 2 upsampling layers with ReflectionPad2d and Tanh output activation.
    """

    def __init__(
        self,
        input_nc: int = 1,
        output_nc: int = 1,
        ngf: int = 64,
        norm_layer: Type[nn.Module] = nn.InstanceNorm2d,
        use_dropout: bool = False,
        n_blocks: int = 6,
    ) -> None:
        super().__init__()
        if isinstance(norm_layer, functools.partial):
            use_bias = norm_layer.func == nn.InstanceNorm2d
        else:
            use_bias = norm_layer == nn.InstanceNorm2d

        model: List[nn.Module] = [
            nn.ReflectionPad2d(3),
            nn.Conv2d(input_nc, ngf, kernel_size=7, padding=0, bias=use_bias),
            norm_layer(ngf),
            nn.ReLU(True),
        ]

        # 2 Downsampling layers (128x128 -> 64x64 -> 32x32)
        n_downsampling = 2
        for i in range(n_downsampling):
            mult = 2**i
            model += [
                nn.Conv2d(
                    ngf * mult,
                    ngf * mult * 2,
                    kernel_size=3,
                    stride=2,
                    padding=1,
                    bias=use_bias,
                ),
                norm_layer(ngf * mult * 2),
                nn.ReLU(True),
            ]

        # N Residual blocks (n_blocks = 6 for resnet_6blocks)
        mult = 2**n_downsampling
        for _ in range(n_blocks):
            model.append(
                ResnetBlock(
                    ngf * mult,
                    norm_layer=norm_layer,
                    use_dropout=use_dropout,
                    use_bias=use_bias,
                )
```

(b) ResNet-6 Generator Architecture

src/cyclegan.py — CycleGAN Training Scheme (LSGAN, Cycle L1, Identity, & MONAI SSIM Loss)

```python
            lr_l = 1.0 - max(0, epoch - cfg.n_epochs) / float(cfg.n_epochs_decay + 1)
            return max(0.0, lr_l)

        self.scheduler_G = torch.optim.lr_scheduler.LambdaLR(self.optimizer_G, lr_lambda=lambda_rule)
        self.scheduler_D = torch.optim.lr_scheduler.LambdaLR(self.optimizer_D, lr_lambda=lambda_rule)

    @staticmethod
    def set_requires_grad(nets: List[nn.Module], requires_grad: bool = False) -> None:
        for net in nets:
            for param in net.parameters():
                param.requires_grad = requires_grad

    def optimize_step(self, real_A: torch.Tensor, real_B: torch.Tensor) -> Dict[str, float]:
        """Run one forward + backward update for Generators and Discriminators."""
        real_A = real_A.to(self.device, non_blocking=True)
        real_B = real_B.to(self.device, non_blocking=True)

        # Forward cycle: A -> B -> A and B -> A -> B
        fake_B = self.netG_A(real_A)  # G_A(A): Synthetic T2w
        rec_A = self.netG_B(fake_B)   # G_B(G_A(A)): Reconstructed T1w
        fake_A = self.netG_B(real_B)  # G_B(B): Synthetic T1w
        rec_B = self.netG_A(fake_A)   # G_A(G_B(B)): Reconstructed T2w

        # ------------------
        # 1. Update G_A and G_B
        # ------------------
        self.set_requires_grad([self.netD_A, self.netD_B], False)
        self.optimizer_G.zero_grad()

        # Identity loss: G_A(B) should be B, G_B(A) should be A
        if self.cfg.lambda_identity > 0:
            idt_A = self.netG_A(real_B)
            loss_idt_A = self.criterionIdt(idt_A, real_B) * self.cfg.lambda_B * self.cfg.lambda_identity
            idt_B = self.netG_B(real_A)
            loss_idt_B = self.criterionIdt(idt_B, real_A) * self.cfg.lambda_A * self.cfg.lambda_identity
        else:
            loss_idt_A = torch.tensor(0.0, device=self.device)
            loss_idt_B = torch.tensor(0.0, device=self.device)

        # GAN loss: D_A(G_A(A)) and D_B(G_B(B))
        loss_G_A = self.criterionGAN(self.netD_A(fake_B), True)
        loss_G_B = self.criterionGAN(self.netD_B(fake_A), True)

        # Cycle consistency loss
        loss_cycle_A = self.criterionCycle(rec_A, real_A) * self.cfg.lambda_A
        loss_cycle_B = self.criterionCycle(rec_B, real_B) * self.cfg.lambda_B

        # Optional MONAI SSIM structural loss on cycle reconstructions
        if self.criterionSSIM is not None and self.cfg.lambda_ssim > 0:
            ssim_A = self.criterionSSIM(to_unit_range(rec_A), to_unit_range(real_A))
            ssim_B = self.criterionSSIM(to_unit_range(rec_B), to_unit_range(real_B))
            loss_ssim = (ssim_A + ssim_B) * self.cfg.lambda_ssim
        else:
```

src/metrics.py — Quantitative Evaluation (MONAI PSNR/SSIM/RMSE/MAE & Explicit Formulas)

```python
def to_unit_range(img: torch.Tensor) -> torch.Tensor:
    """Rescale tensor from generator range [-1, 1] to [0, 1]."""
    return ((img.clamp(-1.0, 1.0) + 1.0) * 0.5).clamp(0.0, 1.0)


def compute_psnr_explicit(pred_01: torch.Tensor, target_01: torch.Tensor, max_val: float = 1.0) -> torch.Tensor:
    """
    Explicit PSNR formula (Week 10 Slide 3):
        PSNR = 10 * log10(MAX_I^2 / MSE)
    """
    mse = torch.mean((pred_01 - target_01) ** 2, dim=(1, 2, 3))
    mse = torch.clamp(mse, min=1e-10)
    return 10.0 * torch.log10((max_val**2) / mse)


def compute_ssim_explicit(
    pred_01: torch.Tensor,
    target_01: torch.Tensor,
    data_range: float = 1.0,
    win_size: int = 11,
) -> torch.Tensor:
    """
    Explicit 2D Gaussian-windowed SSIM formula (Week 10 Slide 4):
        SSIM(x, y) = ((2*mu_x*mu_y + C1)*(2*sigma_xy + C2)) / ((mu_x^2 + mu_y^2 + C1)*(sigma_x^2 + sigma_y^2 + C2))
    """
    c1 = (0.01 * data_range) ** 2
    c2 = (0.03 * data_range) ** 2

    coords = torch.arange(win_size, dtype=pred_01.dtype, device=pred_01.device) - win_size // 2
    g = torch.exp(-(coords**2) / (2 * 1.5**2))
    g = g / g.sum()
    window = (g.unsqueeze(1) @ g.unsqueeze(0)).unsqueeze(0).unsqueeze(0)

    pad = win_size // 2
    mu_x = F.conv2d(pred_01, window, padding=pad)
    mu_y = F.conv2d(target_01, window, padding=pad)

    mu_x_sq = mu_x.pow(2)
    mu_y_sq = mu_y.pow(2)
    mu_xy = mu_x * mu_y

    sigma_x_sq = F.conv2d(pred_01 * pred_01, window, padding=pad) - mu_x_sq
    sigma_y_sq = F.conv2d(target_01 * target_01, window, padding=pad) - mu_y_sq
    sigma_xy = F.conv2d(pred_01 * target_01, window, padding=pad) - mu_xy

    ssim_map = ((2.0 * mu_xy + c1) * (2.0 * sigma_xy + c2)) / (
        (mu_x_sq + mu_y_sq + c1) * (sigma_x_sq + sigma_y_sq + c2)
    )
    return ssim_map.mean(dim=(1, 2, 3))


class MedicalTranslationEvaluator:
    """
    Comprehensive evaluator using MONAI metrics (PSNRMetric, SSIMMetric, RMSEMetric, MAEMetric)
    along with region-specific error decomposition on BraTS 2021 test subjects.
    """

    def __init__(self, max_val: float = 1.0) -> None:
        self.max_val = max_val
        self.psnr_metric = PSNRMetric(max_val=max_val)
        self.ssim_metric = SSIMMetric(spatial_dims=2, data_range=max_val)
        self.rmse_metric = RMSEMetric()
        self.mae_metric = MAEMetric()

    @torch.no_grad()
    def evaluate_batch(
        self,
        real_A: torch.Tensor,
        real_B: torch.Tensor,
        fake_B: torch.Tensor,
        rec_A: torch.Tensor,
        rec_B: torch.Tensor,
        seg: torch.Tensor,
    ) -> Dict[str, np.ndarray]:
```