

# Porting the Steel Bank Common Lisp Compiler and Runtime to the Nintendo Switch NX Platform

Charles Zhang

Yukari “Shinmera” Hafner

charleszhang99@yahoo.com

shinmera@tymoon.eu

Shirakumo.org

Zürich, Switzerland

## ABSTRACT

The Nintendo Switch (NX) is a 64-bit ARM-based platform for video games with a proprietary micro-kernel operating system. Notably this system does not give programs the ability to mark pages as executable or give access to thread signal handlers, both of which present a significant hurdle to SBCL’s intended bootstrap process and runtime operation. We present our efforts to adapt the SBCL runtime and compiler to deploy applications onto the NX platform.

## CCS CONCEPTS

• **Software and its engineering** → **Runtime environments; Dynamic compilers**; *Garbage collection*; Software creation and management.

## KEYWORDS

Common Lisp, SBCL, porting, ARM, aarch64, NX, Experience Report

## ACM Reference Format:

Charles Zhang and Yukari “Shinmera” Hafner. 2025. Porting the Steel Bank Common Lisp Compiler and Runtime to the Nintendo Switch NX Platform. In *Proceedings of the 18th European Lisp Symposium (ELS’25)*. ACM, New York, NY, USA, 3 pages.

## 1 INTRODUCTION

The Nintendo Switch (codename NX) is a handheld video game console based on the ARM 4 Cortex-A57 64-bit architecture[5]. It features a proprietary micro-kernel operating system called the “Nintendo Switch system software”[7] (NX OS), and normally only runs software that has been licensed, approved, and digitally signed and encrypted by Nintendo.

---

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).  
ELS’25, May 19–20 2025, Zürich, Switzerland  
© 2025 Copyright held by the owner/author(s).  
ACM ISBN 978-x-xxxx-xxxx-x/YY/MM

Developing licensed software for the NX has to be done via Nintendo’s own proprietary SDK, which they only distribute under a non-disclosure agreement (NDA). An open-source third-party alternative to the SDK is available[1], but this cannot be used for licensed software.

The OS-provided runtime environment is only directly suitable for C and C++ software. Other game engines such as Unity, Unreal, and Godot do provide exporting functionality to the NX, meaning that ports for the runtime environments they rely on such as C#, Lua, and GDScript have been developed, but remain closed-source.

A port of a C-based runtime for Common Lisp such as ECL[3] is conceivable. However, due to the high performance requirements of video games and the relatively low-power platform of the NX, we deemed it unlikely for such a port to lead to a useful platform. Besides, relying on a C runtime would not eliminate all the difficulties we’ve encountered in porting SBCL anyway.

Particularly, every known Common Lisp implementation compiles a part of its runtime from Lisp source code incrementally into itself, and all user-code is also incrementally compiled into the Lisp image, as opposed to being batch-compiled and linked like other languages such as C. We cannot incrementally compile code on the NX due to platform security restrictions. The consequence is that all implementation and all user code needs to be compiled ahead of time. We discuss the intricacies of this in section 3 and section 4.

The NX OS further does not provide user signal handlers. This is a problem for the Garbage Collector (GC), as SBCL relies on inter-thread signalling to park threads during garbage collection. While SBCL does provide a safepoints mechanism for GC that is used on Windows, this mechanism had not been tested on any other platform, and as-is still did not meet the requirements of this locked-down platform. We discuss the GC in detail in section 5.

While we can now compile and deploy complex Common Lisp applications to the NX, some parts of the runtime remain unsupported, and we discuss our future efforts in this regard in section 7.

## 2 RELATED WORK

Rhodes[6] outlines the methodology behind the SBCL bootstrap process.

A pure Common Lisp bootstrapping process as Durand et al.[4] outline would however not notably improve our process, as all our challenges arise from not being able to bootstrap on the desired target platform in the first place, and needing to handle the low-level system construction processes to be amenable for the NX' restrictions.

Citing information on the NX' operating system is difficult as it is a closed-source platform with all usual information placed under NDA. All publicly available information is from security research such as by Roussel-Tarbouriech et al.[7] and reverse-engineering[1].

Particularly, we are unaware of any publication about the porting of other runtime environments to the NX, such as C#, JavaScript, Lua, etc.

### 3 BUILD SYSTEM

The usual SBCL build process proceeds in several distinct phases, some of which need to be run on a “host system” and others on the “target system”. This does allow for limited cross-compilation, wherein the “host system” steps can be run on an operating system and platform that is not that of the target we are trying to compile for. However, the “target system” steps cannot currently be performed on a host system, and full incremental code execution is required on the target. As mentioned in the Introduction, we cannot perform incremental code execution on the NX, as the NX OS does not allow us to map new executable pages.

The basic idea of our solution to this issue is to replace the NX as *initial* target with an ARM64-based Linux. Once everything, including user code, has been compiled on this Linux target, we extract all Lisp code and data out using a process called *shrinkwrap* and link it together with the SBCL C runtime as compiled for the NX. This process ultimately results in a fully static ELF executable that does not perform any dynamic memory mapping or compilation.

Our build still functions largely the same as the one outlined by Rhodes[6], though being run roughly twice with special configurations to accomplish the hybrid build.

#### (1) build-config (NX)

This step gathers whatever build configuration options for the target and spits them out into a readable format for the rest of the build process. We run this on some host system (which may not be our ARM64 Linux intermediary), using a special flag to indicate that we're building for the NX. We also enable the *fasteval* contrib, which we need to step in for any place where we would usually invoke the compiler at runtime.

#### (2) make-host-1 (NX)

Next we build the cross-compiler with the host Lisp compiler, and at the same time emit C header files describing Lisp object layouts in memory as C structs for the next step.

#### (3) make-target-1 (NX)

Now we use the C compiler the Nintendo SDK provides for us, which can cross-compile the SBCL C runtime for the NX. We had to make adjustments to the C runtime bits, as the NX OS is not POSIX compliant and lacks a few features the SBCL

C runtime usually takes advantage of. The SBCL C runtime contains the GC and OS glue bits that the Lisp code needs.

#### (4) build-config (Linux~NX)

We now create an almost-normal ARM64 Linux system with the same feature set as for the NX. This involves the usual steps as before, though with a special flag to inform some parts of the Lisp process that we're going to ultimately target the NX.

#### (5) make-host-1 (Linux~NX)

#### (6) make-target-1 (Linux~NX)

(7) *make-host-2* (Linux~NX) With the target runtime built, we build the target Lisp system (compiler and the standard library) using the Lisp cross-compiler built by the Lisp host compiler in *make-host-1* (Linux). This step produces a “cold core” that the runtime can jump into, and can be done purely on the host machine. This cold core is not complete, and needs to be executed on the target machine with the target runtime to finish bootstrapping, notably to initialise the object system, which requires runtime compilation.

#### (8) make-target-2 (Linux~NX)

The cold core produced in the last step is loaded into the target runtime, and finishes the bootstrapping procedure to compile and load the rest of the Lisp system. After the Lisp system is loaded into memory, the memory is dumped out into a “warm core”, which can be loaded back into memory in a new process with the target runtime. From this point on, new code can be loaded and images can be dumped at will.

#### (9) user

For user code we now perform some tricks to make it think it's running on the NX, rather than on Linux. In particular we modify *\*features\** to include *:nx* and not *:linux*, *:unix*, or *:posix*. Once that is set up and ASDF has been neutered, we can compile our program “as usual” and at the end dump out a new core.

#### (10) shrinkwrap

Once all our code has been loaded and a final core has been produced, we “shrinkwrap” the image to produce assembly files. The details of this are outlined in section 4. These assembly files can then be linked together with the SBCL C runtime compiled for the NX in step (3) with the Nintendo SDK toolchain, producing a final ELF executable.

#### (11) package

The final step is to run all the other SDK toolchain bits to produce a signed application package, which can be deployed to a Nintendo Switch development kit to be run.

A notable extra wrinkle in this procedure is that the SDK is only available for Windows. To accommodate this, the custom build system we developed can be run either directly from Windows using another ARM machine remotely to run the Linux bits, or it can be run from a Linux system with the ARM bits being run either locally or remotely and the Windows bits being run either remotely or through Wine[2].

## 4 RELOCATION

## 5 GARBAGE COLLECTION

## 6 CONCLUSION

## 7 FURTHER WORK

## 8 ACKNOWLEDGEMENTS

We would like to thank Douglas Katzman for his help and advice for various parts of the porting effort, as well as the rest of the SBCL maintenance team for their continuous improvements to the SBCL platform.

## REFERENCES

- [1] Switchbrew. URL <https://switchbrew.org/>.
- [2] Bob Amstadt and Michael K Johnson. Wine. *Linux Journal*, 1994(4es):3–es, 1994.
- [3] Guiseppe Attardi. The embeddable common lisp. In *Papers of the fourth international conference on LISP users and vendors*, pages 30–41, 1994.
- [4] Irène A Durand and Robert Strandh. Bootstrapping common lisp using common lisp. In *EUROPEAN LISP SYMPOSIUM*, 2019.
- [5] Thomas Morgan. New switch mod delivers real-time cpu, gpu and thermal monitoring – and the results are remarkable. *Eurogamer*, 2020.
- [6] Christophe Rhodes. Sbcl: A sanely-bootstrappable common lisp. In *Workshop on Self-sustaining Systems*, pages 74–86. Springer, 2008.
- [7] Gauvain Tanguy Henri Gabriel Roussel-Tarbouriech, Noel Menard, Tyler True, Tini Vi, et al. Methodically defeating nintendo switch security. *arXiv preprint arXiv:1905.07643*, 2019.