

Indexing

StudentID :

StudentName:

```
-- account table
CREATE TABLE account(
    account_id serial PRIMARY KEY,
    name text NOT NULL,
    dob date
);
```

```
-- thread table
CREATE TABLE thread(
    thread_id serial PRIMARY KEY,
    account_id integer NOT NULL REFERENCES account(account_id),
    title text NOT NULL
);
```

```
-- post table
CREATE TABLE post(
    post_id serial PRIMARY KEY,
    thread_id integer NOT NULL REFERENCES thread(thread_id),
    account_id integer NOT NULL REFERENCES account(account_id),
    created timestamp with time zone NOT NULL DEFAULT now(),
    visible boolean NOT NULL DEFAULT TRUE,
    comment text NOT NULL
);``

```sql
-- word table create with word in linux file
CREATE TABLE words (word TEXT) ;
\copy words (word) FROM '/data/words';
```

```
-- create account data
INSERT INTO account (name, dob)
SELECT
 substring('AEIOU', (random()*4)::int + 1, 1) ||
 substring('ctdrdwftmkndnfnjknksntnyprpsrdgrkrmrnzslstwl',
(random()*22*2 + 1)::int, 2) ||
 substring('aeiou', (random()*4 + 1)::int, 1) ||
 substring('ctdrdwftmkndnfnjknksntnyprpsrdgrkrmrnzslstwl',
(random()*22*2 + 1)::int, 2) ||
 substring('aeiou', (random()*4 + 1)::int, 1),
 Now() + ('1 days'::interval * random() * 365)
FROM generate_series (1, 100)
;
```

```
-- create thread data
INSERT INTO thread (account_id, title)
SELECT
 RANDOM () * 99 + 1,
 (
 SELECT initcap(string_agg (word, ' '))
 FROM (TABLE words ORDER BY random() * n LIMIT 5) AS words (word)
)
FROM generate_series (1, 1000) AS s(n)
;
```

```
-- create post data
INSERT INTO post (thread_id, account_id, created, visible, comment)
WITH random_comments AS (
 -- สร้างประโยคสุ่มเตรียมไว้ 1,000 แบบ (ปรับจำนวนได้)
 -- เพื่อลดภาระการ Sort ตาราง words
 SELECT row_number() OVER () as id, sentence
 FROM (
 SELECT (SELECT string_agg(word, ' ') FROM (SELECT word FROM words
ORDER BY random() LIMIT 20) AS w) as sentence
 FROM generate_series(1, 1000)
) s
)
SELECT
 (RANDOM() * 999 + 1)::int,
 (RANDOM() * 99 + 1)::int,
 NOW() - ('1 days'::interval * random() * 1000),
 (RANDOM() > 0.1),
 -- สุ่มหยิบประโยคจากที่เราสร้างไว้ 1,000 แบบมาใช้
 (SELECT sentence FROM random_comments WHERE id = floor(random() * 1000
+ 1)::int)
FROM generate_series(1, 100000)
;
```

## WITHOUT INDEXING

```
-- table and index data
SELECT
 t.table_name,
 pg_size_pretty(pg_total_relation_size('public.' || t.table_name)) AS
total_size,
 pg_size_pretty(pg_indexes_size('public.' || t.table_name)) AS
index_size,
 pg_size_pretty(pg_relation_size('public.' || t.table_name)) AS
table_size,
 COALESCE(pg_class.reltuples::bigint, 0) AS num_rows
FROM
 information_schema.tables t
LEFT JOIN
 pg_class ON pg_class.relname = t.table_name
LEFT JOIN
 pg_namespace ON pg_namespace.oid = pg_class.relnamespace
WHERE
 t.table_schema = 'public'
 AND pg_namespace.nspname = 'public'
ORDER BY
 t.table_name ASC;
```

-- Output

table_name	total_size	index_size	table_size	num_rows
account	32 kB	16 kB	8192 bytes	100
post	27 MB	2208 kB	25 MB	-1
thread	168 kB	40 kB	96 kB	1000
words	10024 kB	0 bytes	9984 kB	235976

## Exercise 2 See all my posts

```
-- Query 1: See all my posts
```

```
EXPLAIN ANALYZE
SELECT * FROM post
WHERE account_id = 1
;
```

```
-- Output
```

QUERY PLAN

```

Gather (cost=1000.00..6067.51 rows=1613 width=53) (actual
time=1.018..38.513 rows=472 loops=1)
 Workers Planned: 2
 Workers Launched: 2
 -> Parallel Seq Scan on post (cost=0.00..4906.21 rows=672 width=53)
(actual time=0.020..7.520 rows=157 loops=3)
 Filter: (account_id = 1)
 Rows Removed by Filter: 33176
Planning Time: 0.139 ms
Execution Time: 38.585 ms
```

### Exercise 3 How many post have i made?

```
-- Query 2: How many post have i made?
EXPLAIN ANALYZE
SELECT COUNT(*) FROM post
WHERE account_id = 1;

-- Output
```

QUERY PLAN

```

Aggregate (cost=4477.24..4477.25 rows=1 width=8) (actual
time=23.642..23.644 rows=1 loops=1)
 -> Seq Scan on post (cost=0.00..4476.00 rows=497 width=0) (actual
time=0.047..23.572 rows=472 loops=1)
 Filter: (account_id = 1)
 Rows Removed by Filter: 99528
Planning Time: 0.430 ms
Execution Time: 23.695 ms
```

### Exercise 4 See all current posts for a Thread

```
-- Query 3: See all current posts for a Thread
EXPLAIN ANALYZE
SELECT * FROM post
WHERE thread_id = 1
AND visible = TRUE;

-- Output
```

QUERY PLAN

```

Seq Scan on post (cost=0.00..4476.00 rows=89 width=219) (actual
time=1.242..21.176 rows=38 loops=1)
 Filter: (visible AND (thread_id = 1))
 Rows Removed by Filter: 99962
Planning Time: 0.225 ms
Execution Time: 21.211 ms
```

### Exercise 5 How many posts have i made to a Thread?

```
-- Query 4: How many posts have i made to a Thread?
EXPLAIN ANALYZE
SELECT COUNT(*)
FROM post
WHERE thread_id = 1 AND visible = TRUE AND account_id = 1;
```

```
-- Output
```

#### QUERY PLAN

```

Aggregate (cost=4726.00..4726.01 rows=1 width=8) (actual
time=23.281..23.283 rows=1 loops=1)
 -> Seq Scan on post (cost=0.00..4726.00 rows=1 width=0) (actual
time=23.273..23.274 rows=0 loops=1)
 Filter: (visible AND (thread_id = 1) AND (account_id = 1))
 Rows Removed by Filter: 100000
Planning Time: 0.182 ms
Execution Time: 23.340 ms
```

### Exercise 6 See all current posts for a Thread for this month, in order

```
-- Query 5: See all current posts for a Thread for this month, in order
EXPLAIN ANALYZE
SELECT *
FROM post
WHERE thread_id = 1 AND visible = TRUE AND created > NOW() - '1
month'::interval
ORDER BY created;
```

```
-- Output
```

#### QUERY PLAN

```

Bitmap Heap Scan on post (cost=8.14..1337.85 rows=497 width=219) (actual
time=0.294..1.800 rows=472 loops=1)
 Recheck Cond: (account_id = 1)
 Heap Blocks: exact=436
 -> Bitmap Index Scan on post_account_id_idx (cost=0.00..8.02 rows=497
width=0) (actual time=0.151..0.152 rows=472 loops=1)
 Index Cond: (account_id = 1)
Planning Time: 0.439 ms
Execution Time: 1.897 ms
```

## CREATE INDEXES

```
----- INDEX -----
CREATE INDEX ON post(account_id);

-- Query 1: See all my posts with Index
EXPLAIN ANALYZE
SELECT * FROM post
WHERE account_id = 1
;

-- Output
```

```
-- Query 2: How many post have i made? with index
EXPLAIN ANALYZE
SELECT COUNT(*) FROM post
WHERE account_id = 1;

-- Output
```

```
-- CREATE another index
CREATE INDEX ON post (thread_id);

-- Query 3: See all current posts for a Thread with index
EXPLAIN ANALYZE
SELECT * FROM post
WHERE thread_id = 1
AND visible = TRUE;

-- Output
```

```
-- Query 4: How many posts have i made to a Thread? with index
EXPLAIN ANALYZE
SELECT COUNT(*)
FROM post
WHERE thread_id = 1 AND visible = TRUE AND account_id = 1;

-- Output
```

```
CREATE INDEX ON post (thread_id, visible);
```

```
-- Query 3: See all current posts for a Thread with multiple indexes
EXPLAIN ANALYZE
SELECT * FROM post
WHERE thread_id = 1
AND visible = TRUE;

-- Output
```

```
-- Query 4: How many posts have i made to a Thread? with multiple indexes
EXPLAIN ANALYZE
SELECT COUNT(*)
FROM post
WHERE thread_id = 1 AND visible = TRUE AND account_id = 1;

-- Output
```

```
CREATE INDEX ON POST (thread_id, visible, account_id);

-- Query 4: How many posts have i made to a Thread? with multiple 3 indexes
EXPLAIN ANALYZE
SELECT COUNT(*)
FROM post
WHERE thread_id = 1 AND visible = TRUE AND account_id = 1;

-- Output
```

```
-- Add indexes name to see detail about tables and indexes
CREATE INDEX ON post(thread_id, account_id)
WHERE visible = TRUE;

SELECT
 t.table_name,
 i.indexname AS index_name,
 COALESCE(pg_class.reltuples::bigint, 0) AS num_rows,
 pg_size_pretty(pg_relation_size('public.' || t.table_name)) AS
table_size,
 pg_size_pretty(pg_relation_size('public.' || i.indexname)) AS
index_size
FROM
 information_schema.tables t
JOIN
 pg_class ON pg_class.relname = t.table_name
JOIN
 pg_namespace ON pg_namespace.oid = pg_class.relnamespace
LEFT JOIN
 pg_indexes i ON i.tablename = t.table_name AND i.schemaname =
t.table_schema
LEFT JOIN
 pg_class ic ON ic.relname = i.indexname
WHERE
 t.table_schema = 'public'
 AND pg_namespace.nspname = 'public'
 AND pg_class.relkind = 'r' -- 'r' is for regular tables
ORDER BY
 t.table_name ASC, i.indexname;

-- Output
```



```
-- Partial Index
-- Query 4: How many posts have i made to a Thread? with partial indexes
EXPLAIN ANALYZE
SELECT COUNT(*)
FROM post
WHERE thread_id = 1 AND visible = TRUE AND account_id = 1;

-- Output
```

```
-- Query 3: See all current posts for a Thread with partial indexes
EXPLAIN ANALYZE
SELECT * FROM post
WHERE thread_id = 1
AND visible = TRUE;

-- Output
```

```
-- Query 5: See all current posts for a Thread for this month, in order all
indexes
EXPLAIN ANALYZE
SELECT *
FROM post
WHERE thread_id = 1 AND visible = TRUE AND created > NOW() - '1
month'::interval
ORDER BY created;

-- Output
```

```
-- Add index for Query 5
CREATE INDEX ON post (thread_id, created)
WHERE visible = TRUE;

-- Query 5: See all current posts for a Thread for this month, in order
specic index
EXPLAIN ANALYZE
SELECT *
FROM post
WHERE thread_id = 1 AND visible = TRUE AND created > NOW() - '1
month'::interval
ORDER BY created;

-- Output
```

กรณีการทดสอบ (Indexing Strategy)	Query No.	Execution Time (ms)	Scan Method (จาก Explain Plan)	ข้อสังเกต / การเปลี่ยนแปลง
Case A: No Index (มีเฉพาะ Primary Key)	Q1			จุดเริ่มต้น (Baseline)
	Q2			
	Q3			
	Q5			
Case B: Single Index	Q1			เปรียบเทียบ กับ Q1 Case A
CREATE INDEX ON post(account_id);	Q2			
Case C: Composite Index	Q3			เปรียบเทียบ กับ Q3 Case A
"CREATE INDEX ON post(thread_id, visible);"	Q4			
Case D: Partial Index	Q3			สังเกตขนาด Index ที่เล็ก ลง
"CREATE INDEX ON post(thread_id, account_id) WHERE visible = TRUE;"	Q4			

กรณีการทดสอบ (Indexing Strategy)	Query No.	Execution Time (ms)	Scan Method (จาก Explain Plan)	ข้อสังเกต / การเปลี่ยนแปลง
Case E: Index for Sorting	Q5			สังเกตว่ามีขั้นตอน Sort หรือไม่
"CREATE INDEX ON post(thread_id, created) WHERE visible = TRUE;"				