

# An Experimental Study of Memory Management in Rust Programming for Big Data Processing

Shinsaku Okazaki

May, 2020





Development of modern Big Data processing tools has some problems!

- ▷ Generative Garbage Collection
- ▷ Stop-The-World
- ▷ Memory Safe implementation



Rust can be an ideal candidate for development of Big Data processing tools.

# Rust

Rust is a **system language** which has unique memory management concept.

- ▷ **A system language does not have Garbage Collection.**
- ▷ **Rust ensures memory safety.**
- ▷ **It is easy to write safe multithreading code in Rust.**



# Problem Description



Do following concepts have impact on runtime performance of algorithms?

- ▷ **Complex object**
- ▷ **Different variable types**
- ▷ **Reference Count**
- ▷ **Multithreading**
- ▷ **Common Big Data algorithms**



# Complex Object

In Big Data processing, data is represented by complex objects.

```
struct CustomerOwned {  
    key: i32,  
    age: i32,  
    num_purchase: i32,  
    total_purchase: f64,  
    duration_spent: f64,  
    duration_since: f64,  
    zip_code: String,  
    address: String,  
    country: String,  
    state: String,  
    first_name: String,  
    last_name: String,  
    province: String,  
    comment: String,  
    order: OrderOwned  
}
```

## Different Variable Types

Each one has different memory representation.

- ▷ **Owner**
- ▷ **Reference**
- ▷ **Slice**

Each one may have different memory access time.

# Reference Counting

## Advantage

- ▷ **Sharing ownership**
- ▷ **Dinamic memory de/allocation**

## Disadvantage

- ▷ **Need to check reference count**
- ▷ **Heap allocation**

# Multithreading

## Atomic Reference Counting

### Advantage

- ▷ **Sharing ownership**
- ▷ **Dinamic memory de/allocation**
- ▷ **Sharing among multithreads**

### Disadvantage

- ▷ **Need to check reference count**
- ▷ **Heap allocation**
- ▷ **Atomic operation**



## Common Big Data algorithms

- ▷ Merge-sort
- ▷ Tree-aggregate
- ▷ K-Nearest-Neighbors (KNN)

# Experiment 1: Accessing Object with Different Variable Type


## Question

- ▷ How much are memory access times different among different variable types used in complex objects?

## Evaluation

- ▷ **Custruct complex objects**
- ▷ With different variable types: **Owner, Reference, Slice**
- ▷ Measure time to **access to fields of complex objects**

# Experiment 1: Accessing Object with Different Variable Type



## Experiment 2: Assessment of different reference methods in Rust


### Question

- ▷ How much does Reference Counting slowdown time for dropping its variable?

### Evaluation

- ▷ **Custruct complex objects**
- ▷ **Reference Counting** vs **reference**
- ▷ Measure time to **drop variables of complex objects**

## Experiment 2: Assessment of different reference methods in Rust



Dropping Reference Counting is about **60 times slower** than normal reference.

## Experiment 3: Merge-sort


### Question

- ▷ How much does sharing set of data with Atomic Reference Counting slowdown merge-sort algorithms?

### Evaluation

- ▷ Share **vector** of complex objects
- ▷ **Atomic Reference Counting (Arc)** vs **normal reference**
- ▷ Measure **runtime of merge-sort algorithms**

## Experiment 3: Merge-sort



Algorithms with Arc are about **21% slower**.

## Experiment 4: Tree-aggregate

### Question


- ▷ How much are runtime differences between sharing elements of data with Arc and deep-copying elements of data?

### Evaluation

- ▷ Share **elements** of complex object
- ▷ **Atomic Reference Counting (ARC)** vs **Deep copy**
- ▷ Measure **runtime of Tree-aggregate algorithms**



## Experiment 4: Tree-aggregate



Algorithms with deep-copy are from **40 to 50% slower**.

# Experiment 5: K-Nearest-Neighbors (KNN)


## Question

- ▷ What are better memory management strategies for common Machine Learning Algorithms?

## Evaluation

- ▷ Document classification on Wikipedia page dataset
- ▷ Preprocessing phase: calculating **Term-frequencies (Tfs)**
- ▷ String manipulation
- ▷ **Atomic Reference Counting (Arc)** vs **Deep copy**
- ▷ **Frequency of memory de/allocation**
  - ▷ batch number
  - ▷ strategy
    - 1: keep intermediate objects in memory until owner is changed
    - 2: remove intermediate objects as soon as it is not needed
- ▷ Measure runtime of **preprocessing time of KNN algorithms**

## Experiment 5: K-Nearest-Neighbors



- ▷ Algorithms with **Arc** are **at most 38 % slower** than deep-copy.
- ▷ Algorithms with **strategy 2** are **at most 85 % slower** than strategy 1.
- ▷ Algorithms with **3 batches** are **at most 40 % slower** than 2 batches.

## Conclusion



- ▷ Use normal reference rather than Reference Counting whenever it is possible.
- ▷ Trade-off between **runtime performance** and **lifetime tracking**.
- ▷ **Avoid using Arc** when we can use reference.
- ▷ Use Arc instead of deep-copy, when **complexity of objects is large**.
- ▷ Use deep-copy, when **complexity of objects is small**, like String.