

# Accelerated Opinion Evolution for the Friedkin-Johnsen Model

anonymous authors

## Abstract

Online social networks serve as a pivotal platform for opinion formation and dissemination, characterized by highly dynamic interaction patterns. The Friedkin-Johnsen model provides a foundational framework for studying opinion dynamics in such settings. However, standard solvers for this model update opinions using only initial opinions and a fixed neighborhood structure, thereby ignoring temporal dependencies and suffering from slow convergence on large-scale graphs. To overcome this limitation, we propose a new class of efficient solvers that preserve the original equilibrium of the Friedkin-Johnsen model while significantly accelerating convergence. Our approach enriches the update rule with temporal awareness by responding to the latest expressed opinions and retaining memory of past states. Experiments on real-world networks containing millions to tens of millions of nodes demonstrate the effectiveness, accuracy, and scalability of our methods.

## Keywords

Opinion dynamics, social networks, graph algorithms, multi-agent systems

## 1 Introduction

Social media platforms have become an indispensable part of modern life, profoundly reshaping how individuals disseminate, exchange, and form opinions [2, 11, 17]. Compared to traditional channels of information diffusion, this transformation has significantly increased the complexity of opinion dynamics and exerted far-reaching effects on human behavior and social interaction patterns [18]. The pervasive nature of online interactions has spurred extensive academic interest in understanding the mechanisms underlying opinion propagation and formation, leading to the development of various mathematical models to capture these processes [2, 11, 17, 23]. Among them, the Friedkin-Johnsen (FJ) model [12] has emerged as one of the most widely applied frameworks. Notably, adaptations of the FJ model have been used to analyze complex negotiation processes, such as those leading to the Paris Agreement [4], demonstrating its utility in explaining consensus formation in multilateral international settings.

The core of the FJ model lies in its equilibrium opinion vector, which represents the stable set of expressed opinions reached after prolonged social influence. This equilibrium is determined jointly by the network topology, individual's intrinsic opinions, and interpersonal influence weights. It carries clear sociological meaning and serves as the foundation for quantifying key societal phenomena such as polarization [9, 19, 20], disagreement [9, 20], conflict [8], and controversy [8]. However, existing solvers [21, 29, 30] typically implement opinion updates as a synchronous weighted average

of initial opinions and neighbors opinions from the previous iteration. This approach implicitly assumes that individuals adjust their views based solely on outdated information from all neighbors, with no access to opinions updated earlier in the current round and no memory of their own past states. While this simplification facilitates theoretical analysis, it contradicts the temporal dependencies observed in real social interactions, where people often respond immediately to the latest statements and exhibit cognitive continuity over time. More critically, this static update scheme leads to extremely slow convergence on large-scale networks, severely limiting the practical applicability of the FJ model at real-world scales. Although numerous acceleration techniques exist for consensus-only models like DeGroot, they cannot be directly applied here. The FJ model explicitly preserves fixed intrinsic opinions, resulting in a more complex equilibrium structure that defies straightforward adaptation of existing methods.

To address these challenges, we propose a new class of efficient solvers that strictly preserve the original equilibrium of the FJ model while dramatically accelerating convergence through explicit modeling of temporal dynamics. Specifically, our approach captures responsiveness to the latest expressed opinions and retention of historical memory. It integrates three key mechanisms: sequential updates that immediately propagate freshly computed opinions within each iteration, self-interaction effects that enhance stability and enable faster convergence, and second-order historical dependence that incorporates past states to better capture the inertia of opinion evolution. We theoretically prove that all proposed algorithms converge to the same unique equilibrium as the classical model, yet with provably faster convergence rates. Experimental results demonstrate that our proposed algorithms exhibit superior performance and scalability on networks comprising tens of millions of nodes. The main contributions of this paper are summarized as follows:

[wgy: change this]

- We introduce a robust local iteration algorithm that efficiently approximates the equilibrium opinion vector while guaranteeing relative error bounds.
- By incorporating SOR techniques, we optimize the algorithm with a relaxation parameter  $\omega$ , leading to faster convergence and improved computational efficiency.
- We conduct extensive numerical experiments on real-world network datasets. The results validate the advantages of our algorithms in terms of high efficiency and strong scalability.

## 2 Related Work

The FJ model, integrating internal opinions with social influence, stands as a pivotal framework in social dynamics research [12]. Stability conditions for this model were established in [24], while equilibrium expressed opinion was derived in [5, 10]. Interpretations of the FJ model were further explored in [5] and [15]. Research has also delved into adversarial interventions [7, 14, 28] and the spread of viral content [27]. Furthermore, the FJ model has been expanded in various dimensions, as discussed in [17, 25], including multidimensional approaches [13, 22].

Beyond the foundational aspects, interpretations, and extensions of the FJ model, researchers have developed metrics to quantify disagreement [20], polarization [19, 20], conflict [8], and controversy [8]. These metrics offer valuable insights into social dynamics. Various optimization problems based on the FJ model have been addressed, including efforts to minimize overall opinion [26], disagreement [20], polarization [19, 20], and conflict [8, 32] by adjusting node attributes such as internal opinions or susceptibility to persuasion [1, 6, 16]. Network modifications, like edge additions or deletions to reduce polarization or foster consensus, have emerged as a significant area of study [8, 20, 31].

Scalability and efficiency pose significant challenges in large networks, where conventional methods like matrix inversion are impractical. To overcome this, scalable algorithms utilizing sampling and distributed computing have been introduced [3, 24], facilitating the analysis of networks with millions of nodes. For undirected graphs, Laplacian solvers can approximate equilibrium opinions in near-linear time [30], while directed graphs rely on forest sampling methods [26]. Recent work [21] propose sublinear time algorithms to estimate single-node opinions without computing the entire equilibrium vector.

## 3 Preliminaries

In this section, we introduce some useful notations and fundamental concepts of the FJ model of opinion formation for the convenience of description of problem formulation and algorithm.

### 3.1 Notations

We use  $\mathbb{R}$  to represent the set of real numbers and regular lowercase letters like  $a, b, c$  to represent scalars in  $\mathbb{R}$ . Bold lowercase letters are column vectors, e.g.,  $\mathbf{a}, \mathbf{b}, \mathbf{c}$ . Bold capital letters, e.g.,  $\mathbf{A}, \mathbf{B}, \mathbf{C}$  are matrices. To denote specific elements in vectors and matrices, We denote  $A_{ij}$  as the entry of  $\mathbf{A}$  at  $i$ -th row and  $j$ -th column and  $a_i$  as  $i$ -th element of vector  $\mathbf{a}$ . And we use  $\mathbf{a}^\top$  and  $\mathbf{A}^\top$  to denote transpose of vector  $\mathbf{a}$  and matrix  $\mathbf{A}$ . We use  $\mathbf{1}$  to denote the vector of appropriate dimensions with all entries being ones and use  $\mathbf{e}_u$  to represent the  $u$ -th standard basis vector of appropriate dimensions.  $\mathbf{I}$  denotes the identify matrix of appropriate dimensions.

### 3.2 Graph and Matrix Definitions

Let  $\mathcal{G} = (V, E)$  be an unweighted simple graph with  $n = |V|$  nodes and  $m = |E|$  edges, where  $V$  is the set of nodes and  $E \subseteq V \times V$  is the set of edges. The graph  $\mathcal{G}$  is either a directed graph or an undirected graph depending on the context. The adjacency relation of all nodes in  $\mathcal{G}$  is encoded in the adjacency matrix  $\mathbf{A}$ , whose entry  $a_{ij} = 1$  if  $i$  and  $j$  are adjacent, and  $a_{ij} = 0$  otherwise. For any given node  $i$ ,  $N_i$  denote the set of its neighbors, meaning  $N_i = \{j : (i, j) \in E\}$ . The degree  $d_i$  of any node  $i$  is defined by  $d_i = \sum_{j=1}^n a_{ij}$ . The degree diagonal matrix of  $\mathcal{G}$  is  $\mathbf{D} = \text{diag}(d_1, d_2, \dots, d_n)$ . The degree vector  $\mathbf{d}$  is given by  $\mathbf{d} = \mathbf{D}\mathbf{1}$ . The transition matrix of an unbiased random walk on graph  $\mathcal{G}$  is  $\mathbf{P} = \mathbf{D}^{-1}\mathbf{A}$ , which is a row-stochastic matrix. The Laplacian matrix  $\mathbf{L}$  of  $\mathcal{G}$  is  $\mathbf{L} = \mathbf{D} - \mathbf{A}$ , which is a symmetric semi-positive definite matrix. Matrix  $\mathbf{L}$  is singular, and thus it is irreversible. For a matrix  $\mathbf{M}$ , if the magnitudes of all the eigenvalues of  $\mathbf{M}$  are less than 1, then the series  $\sum_{k=0}^{\infty} \mathbf{M}^k$  is a Neumann series and converges to  $(\mathbf{I} - \mathbf{M})^{-1}$ .

### 3.3 Friedkin–Johnsen (FJ) Model

As one of the first opinion dynamics models, the FJ model is an extension of the DeGroot's opinion model. In the DeGroot model, every node has only one opinion that is updated as the weighted average of its neighbors. Different from the DeGroot model, in the FJ model, each node  $i \in V$  has two different kinds of opinions: one is the internal (or innate) opinion  $s_i$ , the other is the expressed opinion  $z_i$ . The internal opinion  $s_i$  is assumed to remain constant, private to node  $i$ , while the expressed opinion  $z_i$  evolves as a weighted average of its corresponding internal opinion  $s_i$  and the expressed opinions of  $i$ 's neighbors.

Given a graph  $G = (V, E)$ , let  $\mathbf{s}$  denote the internal opinion vector, with each entry satisfying  $s_i \in [0, 1]$ . The formulation of the equilibrium opinion expressed in the FJ model is an iterative form such that

$$z_i^{(t+1)} = \frac{s_i + \sum_{j \in N_i} a_{ij} z_j^{(t)}}{1 + \sum_{j \in N_i} a_{ij}}. \quad (1)$$

As in the FJ iterative formula above, the opinion of each node in the FJ model is updated as the weighted average of the neighbor's expressed opinion  $z_j$  and its own internal opinion  $s_i$ . When  $t$  approaches infinity, the updated expressed opinion was shown to converge to a unique equilibrium opinion  $\mathbf{z}$ . So the iterative update in Equation 1 can be written compactly as  $\mathbf{z}^{(t+1)} = (\mathbf{I} + \mathbf{D})^{-1}(\mathbf{s} + \mathbf{A}\mathbf{z}^{(t)})$  in vector form, which expresses the FJ dynamics as a linear transformation applied at each iteration. Then the system of equilibrium expressed opinion vector  $\mathbf{z}$  is equivalent to:  $(\mathbf{I} + \mathbf{L})\mathbf{z} = \mathbf{s}$ , where  $\mathbf{I}$  is the identify matrix, and  $\mathbf{L} = \mathbf{D} - \mathbf{A}$  is the Laplacian matrix. When  $\mathcal{G}$  is connected and  $a_{ij} \geq 0$ , the matrix  $\mathbf{I} + \mathbf{L}$  is symmetric positive definite, ensuring existence and uniqueness of  $\mathbf{z}$ . This characterization motivates estimators and algorithms that exploit the spectral and structural properties of the Laplacian.

### 3.4 Game-theoretic Interpretation

From a game-theoretic perspective, the classical FJ model admits an equivalent interpretation as the equilibrium of a quadratic utility game. Recall that the FJ equilibrium satisfies  $(\mathbf{I} + \mathbf{D} - \mathbf{A})\mathbf{z} = \mathbf{s}$ . For undirected graphs, the matrix  $\mathbf{I} + \mathbf{D} - \mathbf{A}$  corresponds to a symmetric, positive definite Laplacian-based operator, which allows the equilibrium to be characterized as the unique minimizer of a strongly convex quadratic objective.

This formulation further admits a decentralized interpretation. Updating  $z_i$  according to the FJ rule is equivalent to each agent  $i$  minimizing the local quadratic cost

$$(z_i - s_i)^2 + \sum_{j \in N(i)} w_{i,j} (z_i - z_j)^2, \quad (2)$$

given the opinions of its neighbors. Thus, opinion averaging can be viewed as a sequence of best-response updates in a complete-information game, where each agent selects an opinion to balance conformity with its intrinsic belief. The resulting Nash equilibrium coincides with the minimizer of the global social cost and is unique due to strong convexity.

### 3.5 Existing Algorithm

## 4 Accelerated Opinion Iteration

We study accelerated iterative schemes for computing the equilibrium of the Friedkin-Johnsen (FJ) model. Beyond the classical synchronous update, we consider sequential and latest-opinion-based iterations that immediately exploit newly updated opinions. These schemes are further extended with self-interaction, yielding a family of accelerated algorithms that preserve the same equilibrium as the standard FJ model while achieving faster convergence. Their convergence properties are analyzed in the following subsections.

### 4.1 Sequential Latest-Opinion Updates

The classical FJ iteration updates all opinions synchronously, using only the opinion profile from the previous iteration. In contrast, we consider a sequential update scheme in which opinions are revised one by one, and newly updated opinions are immediately used in subsequent updates.

Under this scheme, opinions are updated in a coordinate-wise manner. Specifically, when updating the  $i$ -th opinion at iteration  $t+1$ , the most recent values of opinions  $1, \dots, i-1$  are used whenever available, while the remaining opinions retain their values from iteration  $t$ :

$$z_i^{(t+1)} = \frac{s_i + \sum_{j=1}^{i-1} a_{ij} z_j^{(t+1)} + \sum_{j=i+1}^n a_{ij} z_j^{(t)}}{1 + \sum_{j \in N_i} a_{ij}}. \quad (3)$$

This update reduces to the classical synchronous FJ iteration when all opinions on the right-hand side are taken from iteration  $t$ . As shown later, the sequential latest-opinion update preserves the FJ equilibrium and typically converges faster due to the immediate utilization of newly updated opinions. The sequential latest-opinion update admits a compact matrix representation. Specifically, it can be written as

$$\mathbf{z}^{(k+1)} = \mathbf{B}\mathbf{z}^{(k)} + \mathbf{c}, \text{ where } \mathbf{B} = (\mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}})^{-1} \mathbf{A}_{\text{up}}, \quad \mathbf{c} = (\mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}})^{-1} \mathbf{s}.$$

Algorithm 1 implements the proposed sequential latest-opinion iteration. At each iteration, the algorithm performs a single forward sweep over the nodes in a fixed order. When updating node  $i$ , the most recent opinion values are used whenever available, i.e., newly updated values from the current sweep are immediately incorporated, while the remaining opinions are taken from the previous iterate. This latest-available policy enables faster information propagation along the sweep and distinguishes the method from the classical synchronous FJ iteration.

The update combines the aggregated neighbor influence with the internal opinion  $s_i$  and applies a local normalization by  $1 + d_i$ . The iteration terminates when a prescribed tolerance is met or a maximum number of iterations is reached. Let  $\epsilon^{(k)} = \mathbf{z}^{(k)} - \mathbf{z}$  denote the error at iteration  $k$ , where  $\mathbf{z}$  is the FJ equilibrium. We next establish the convergence of the sequential latest-opinion iteration. The theorem below establishes the convergence of the latest-value updates.

**THEOREM 4.1 (CONVERGENCE AND LINEAR RATE OF LATEST-OPINION ITERATION).** *Consider the latest-opinion iteration*

$$\mathbf{z}^{(t+1)} = (\mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}})^{-1} \mathbf{A}_{\text{up}} \mathbf{z}^{(t)} + (\mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}})^{-1} \mathbf{s}, \quad (4)$$

*The iteration converges linearly to the unique FJ equilibrium opinion  $\mathbf{z} = (\mathbf{I} + \mathbf{L})^{-1} \mathbf{s}$  for any initial opinion  $\mathbf{s}$ . Moreover, the iteration matrix  $\mathbf{B} = (\mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}})^{-1} \mathbf{A}_{\text{up}}$  satisfies  $\rho(\mathbf{B}) < 1$ .*

**PROOF.** Let  $\mathbf{z}^* = (\mathbf{I} + \mathbf{L})^{-1} \mathbf{s}$  denote the true value estimated by FJ model, and define the error  $\epsilon^{(k)} := \mathbf{z}^{(k)} - \mathbf{z}^*$ . Then the error propagation satisfies  $\epsilon^{(k+1)} = \mathbf{B}\epsilon^{(k)}$ . Since matrix  $\mathbf{I} + \mathbf{L}$  is strictly diagonally dominant by rows, i.e.,  $|1 + d_i| > \sum_{j \neq i} |a_{ij}|$ ,  $1 \leq i \leq n$ , it is an  $L$ -matrix and hence nonsingular. Moreover, the matrix  $\mathbf{M} := \mathbf{I} + \mathbf{D} - \mathbf{A}_{\text{low}}$  is nonsingular.

We estimate the error in the  $\ell_\infty$ -norm. For each component  $i$ , the Latest-opinion update implies

$$|\epsilon_i^{(k+1)}| \leq \frac{1}{|1 + d_i|} \left( \sum_{j=1}^{i-1} |a_{ij}| |\epsilon_j^{(k+1)}| + \sum_{j=i+1}^n |a_{ij}| |\epsilon_j^{(k)}| \right). \quad (5)$$

Using the definition of the  $\ell_\infty$ -norm, we obtain  $|\epsilon_i^{(k+1)}| \leq \frac{\sum_{j=i+1}^n |a_{ij}|}{|1 + d_i| - \sum_{j=1}^{i-1} |a_{ij}|} \|\epsilon^{(k)}\|_\infty$ . By the strict diagonal dominance condition, the denominator is strictly larger than the numerator. Define

$$q := \max_i \frac{\sum_{j=i+1}^n |a_{ij}|}{|1 + d_i| - \sum_{j=1}^{i-1} |a_{ij}|}, \quad (6)$$

then  $0 \leq q < 1$  and

$$\|\epsilon^{(k+1)}\|_\infty \leq q \|\epsilon^{(k)}\|_\infty. \quad (7)$$

Iterating (7) yields  $\|\epsilon^{(k)}\|_\infty \leq q^k \|\epsilon^{(0)}\|_\infty$ , which implies  $\epsilon^{(k)} \rightarrow 0$  as  $k \rightarrow \infty$ . Therefore, the latest-opinion iteration converges linearly to  $\mathbf{z}^*$ . Finally, since  $\rho(\mathbf{B}) \leq \|\mathbf{B}\|_\infty \leq q < 1$ , the spectral radius of the iteration matrix satisfies  $\rho(\mathbf{B}) < 1$ .  $\square$

**Algorithm 1:** LatestIter for opinion estimation

**Input:** Graph  $G = (V, E)$  with degrees  $(d_i)$  and neighbor sets  $(N_i)$ ; internal opinion  $s \in \mathbb{R}^n$ ; maximum iteration limit  $T_{\max}$ ; tolerance  $\epsilon$ ;

**Output:** Estimated opinion vector  $z$ ; iteration count  $t$

```

1  $z \leftarrow \mathbf{0} \in \mathbb{R}^n$ 
2 for  $t \leftarrow 1$  to  $T_{\max}$  do
3    $z^{\text{old}} \leftarrow z$ 
4   for  $i \leftarrow 1$  to  $n$  do
5      $h \leftarrow 0$ 
6     foreach  $j \in N_i$  do
7        $h \leftarrow h + \begin{cases} z_j, & j < i \\ z_j^{\text{old}}, & j > i \end{cases}$ 
8      $z_i \leftarrow (s_i + h)/(1 + d_i)$ 
9   if  $\|z - z^{\text{old}}\|_{\infty} < \epsilon$  then
10    return  $(z, t)$ 
11 return  $(z, t)$ 

```

Moreover, the convergence is linear: for any induced matrix norm,

$$\|z^{(t)} - z\| \leq \|B\|^t \|z^{(0)} - z\|.$$

And the error satisfies  $\|z^{(t)} - z\|_v \leq \frac{q^t}{1-q} \|z^{(1)} - z^{(0)}\|_v$ , which shows the convergence rate of the algorithm. The parameter  $q = \|B\|_v$  not only guarantees convergence but also characterizes the speed of convergence. Smaller values of  $q$  imply faster stabilization of opinions, which is particularly important for large-scale networks. The next theorem is going to be useful in showing the main result.

**THEOREM 4.2 (SPECTRAL IMPROVEMENT OVER CLASSICAL FJ ITERATION).** *Let  $B_{\text{FJ}} = (I + D)^{-1}A$  denote the iteration matrix of the classical Friedkin–Johnsen iteration, and let  $B_{\text{LI}} = (I + D - A_{\text{low}})^{-1}A_{\text{up}}$  be the iteration matrix of the proposed latest-value iteration. If the underlying social graph is connected, then  $\rho(B_{\text{LI}}) < \rho(B_{\text{FJ}}) < 1$ . Consequently, the latest-value iteration converges faster than the classical FJ iteration.*

**PROOF.** The FJ iteration matrix is  $B_{\text{FJ}} = (I + D)^{-1}A$ , while the latest-value iteration matrix is  $B_{\text{LI}} = (I + D - A_{\text{low}})^{-1}A_{\text{up}}$ . By the Stein–Rosenberg theorem for nonnegative matrix splittings (see, e.g., [Thm. 3.33]varga2000matrix), the spectral radii of the corresponding iteration matrices satisfy  $\rho(B_{\text{LI}}) \leq \rho(B_{\text{FJ}}^2) = \rho(B_{\text{FJ}})^2$ . Since  $0 < \rho(B_{\text{FJ}}) < 1$ , we have  $\rho(B_{\text{FJ}})^2 < \rho(B_{\text{FJ}})$ , which implies

$$\rho(B_{\text{LI}}) < \rho(B_{\text{FJ}}).$$

It is well known that for stationary linear iterations, the asymptotic convergence rate is characterized by the spectral radius of the iteration matrix (see, e.g., [Ch. 2]varga2000matrix).  $\square$

**Remark:** [Interpretation of the Stopping Criterion] In practice, LatestIter is terminated when the one-step update difference  $\|z^{(t+1)} - z^{(t)}\|_{\infty}$  falls below a prescribed tolerance  $\epsilon$ .

While this criterion does not directly measure the distance to the true opinion vector  $z^*$ , the following relation holds under the LatestIter update:

$$\|z^* - z^{(t)}\|_{\infty} \leq \|(I + D - A)^{-1}\|_{\infty} \|(I + D - A_{\text{low}})\|_{\infty} \|z^{(t+1)} - z^{(t)}\|_{\infty}. \quad (8)$$

For the standard Friedkin–Johnsen setting,  $(I + D - A)$  is strictly diagonally dominant, which implies  $\|(I + D - A)^{-1}\|_{\infty} \leq 1$  by the Varah bound. As a result, the termination criterion based on the update difference provides an a posteriori control of the true estimation error up to a constant factor. This relation is used to interpret the stopping tolerance in our experiments.

**LEMMA 4.3 (ERROR BOUND).** *Let  $z^{(t+1)}$  denotes the estimate updated by the latest-opinion iteration at epoch  $t + 1$ , and  $r^{(t)} = s - (I + D - A)z^{(t)}$  denotes the residual error. Then, for all  $t \geq 0$ , the error bound between the estimate opinion and the true opinion satisfies*

$$\|z^* - z^{(t)}\|_{\infty} \leq (1 + \max_{j>i} \sum a_{ij}) \|z^{(t+1)} - z^{(t)}\|_{\infty}, \quad (9)$$

**PROOF.** By the LatestIter update,

$$(I + D - A_{\text{low}})z^{(t+1)} = A_{\text{up}}z^{(t)} + s.$$

Subtracting  $(I + D - A_{\text{low}})z^{(t)}$  from both sides yields

$$(I + D - A_{\text{low}})(z^{(t+1)} - z^{(t)}) = s - (I + D - A)z^{(t)} = r^{(t)}.$$

Hence,

$$z^{(t+1)} - z^{(t)} = (I + D - A_{\text{low}})^{-1}r^{(t)}.$$

On the other hand, the fixed point satisfies  $z^* = (I + D - A)^{-1}s$ , which implies

$$z^* - z^{(t)} = (I + D - A)^{-1}r^{(t)}.$$

Combining the two relations gives

$$z^* - z^{(t)} = (I + D - A)^{-1}(I + D - A_{\text{low}})(z^{(t+1)} - z^{(t)}).$$

Taking the  $\ell_{\infty}$  norm and using submultiplicativity,

$$\|z^* - z^{(t)}\|_{\infty} \leq \|(I + D - A)^{-1}\|_{\infty} \|(I + D - A_{\text{low}})\|_{\infty} \|z^{(t+1)} - z^{(t)}\|_{\infty}. \quad (10)$$

For the standard Friedkin–Johnsen setting,  $(I + D - A)$  is strictly diagonally dominant, implying  $\|(I + D - A)^{-1}\|_{\infty} \leq 1$  by the Varah bound. Moreover,

$$\|(I + D - A_{\text{low}})\|_{\infty} = \max_i \left( 1 + d_i - \sum_{j<i} a_{ij} \right) \leq 1 + \max_i \sum_{j>i} a_{ij},$$

which completes the proof.  $\square$

Therefore, the iterative scheme yields geometrically decaying residuals, and the estimation error converges to zero. Let  $q = \|B\|_v$  denote a matrix norm-induced bound with  $q < 1$ . By Lemma,

$$\|z - z^{(t)}\| \leq \frac{q}{1-q} \|z^{(t)} - z^{(t-1)}\| \leq \frac{q^t}{1-q} \|z^{(1)} - z^{(0)}\|$$

Thus to achieve an absolute error  $|\hat{z}^{(t)} - z| \leq \epsilon \|z^{(1)} - z^{(0)}\|$ , it suffices to take

$$T = \left\lceil \frac{\ln(\epsilon(1-q))}{\ln(q)} \right\rceil.$$



For graphs, one can further bound  $\gamma$  by degree statistics:  $q = \|\mathbf{B}\|_v < 1$ .

Turning to efficiency and implementation locality, we summarize the per iteration cost, error decay, and neighborhood growth as follows.

**THEOREM 4.4 (TIME COMPLEXITY OF LATESTITER).** *To achieve an error  $|\hat{z}_i^{(T)} - z_i| \leq \varepsilon \|z^{(1)} - z^{(0)}\|$ , the time complexity is bounded by:*

$$O\left[m \frac{\ln(\varepsilon(1-q))}{\ln(q)}\right].$$

**PROOF.** We consider the stationary linear iteration  $\mathbf{z}^{(t+1)} = \mathbf{B}\mathbf{z}^{(t)} + \mathbf{c}$ , where  $\rho(\mathbf{B}) < 1$ . Let  $\mathbf{z}$  denote its unique fixed point satisfying  $\mathbf{z} = \mathbf{B}\mathbf{z} + \mathbf{c}$ .

By standard linear convergence theory for stationary iterations (e.g., [? ?]), the residuals decay geometrically. In particular, for any vector norm  $\|\cdot\|$  induced by a matrix norm  $\|\cdot\|_v$ , let  $q = \|\mathbf{B}\|_v < 1$ . Then for all  $t \geq 1$ ,

$$\|\mathbf{z} - \mathbf{z}^{(t)}\| \leq \frac{q}{1-q} \|\mathbf{z}^{(t)} - \mathbf{z}^{(t-1)}\| \leq \frac{q^t}{1-q} \|\mathbf{z}^{(1)} - \mathbf{z}^{(0)}\|, \quad (10)$$

where the first inequality follows from the Neumann series expansion of  $(\mathbf{I} - \mathbf{B})^{-1}$ , and the second inequality follows by induction.

To achieve an absolute error  $|\hat{z}_i^{(t)} - z_i| \leq \varepsilon \|z^{(1)} - z^{(0)}\|$ , it suffices to choose  $T$  such that  $\frac{q^T}{1-q} \leq \varepsilon$ , which yields

$$T = \left\lceil \frac{\ln(\varepsilon(1-q))}{\ln(q)} \right\rceil.$$

Each iteration of LATESTITER involves a single sparse matrix-vector multiplication with  $\mathbf{B}$ , which costs  $O(m)$  time, where  $m$  is the number of edges in the graph. Therefore, the overall time complexity to reach the desired accuracy is

$$O\left(m \cdot \left\lceil \frac{\ln(\varepsilon(1-q))}{\ln(q)} \right\rceil\right),$$

completing the proof.  $\square$

## 4.2 Self-Interaction Opinion Updates

The sequential latest-opinion update captures immediate information propagation, but it implicitly assumes that agents fully replace their opinions at each update. In practice, opinion evolution is often history-dependent, where individuals adjust their current opinions rather than discard them entirely.

To model such self-interaction, we introduce a gain-controlled update that blends the previous opinion with the latest sequential estimate. Specifically, let  $\tilde{\mathbf{z}}^{(t+1)}$  denote the intermediate opinion obtained by the LatestIter scheme (defined in Section X). The final update is given by

$$\mathbf{z}^{(t+1)} = (1-\beta)\mathbf{z}^{(t)} + \beta\tilde{\mathbf{z}}^{(t+1)},$$

where  $\beta \in (0, 1]$  controls the responsiveness of agents to newly propagated information.

This gain-controlled update preserves the equilibrium of the original FJ model while incorporating information from

previous iterates, which enhances numerical stability and enables faster convergence in practice.

Based on this gain-controlled update rule, we propose the accelerated algorithm MEMOITER (Algorithm 2). The method introduces only a single control parameter, preserves the locality of updates, and maintains the linear structure of the original iteration. Moreover, the same gain-control principle can be naturally extended to other FJ-type iterative schemes.

Algorithm 2 is introduced as a refinement of the latest-order scheme in Algorithm 1 to improve its robustness and convergence behavior in challenging scenarios. While the latest-order update iteration propagates fresh information efficiently, it may exhibit slow convergence or oscillatory behavior when the local updates are overly aggressive or when the network contains nodes with small normalization weights. To address these limitations, MemoIter incorporates an explicit memory-based relaxation mechanism into each local update.

By interpolating between the previous iterate and the latest-order update, MemoIter retains the fast information propagation of the original scheme while significantly enhancing numerical stability and robustness.

As a result, MemoIter stabilizes the update dynamics and improves convergence reliability, especially in heterogeneous networks or near ill-conditioned regimes.

By construction, MEMOITER reduces to the LATESTITER iteration when  $\beta = 1$ . For undirected graphs, the associated system matrix is symmetric and positive definite, which guarantees the convergence of the scheme.

The matrix form of memory-augmented update can be written as  $(\mathbf{I} + \mathbf{D})\mathbf{z}^{(k+1)} = (1-\beta)(\mathbf{I} + \mathbf{D})\mathbf{z}^{(k)} + \beta(\mathbf{s} + \mathbf{A}_{low}\mathbf{z}^{(k+1)} + \mathbf{A}_{up}\mathbf{z}^{(k)})$ . Equivalently, this can be rearranged as  $\mathbf{z}^{(k+1)} = ((\mathbf{I} + \mathbf{D}) - \beta\mathbf{A}_{low})^{-1}((1-\beta)(\mathbf{I} + \mathbf{D}) + \beta\mathbf{A}_{up})\mathbf{z}^{(k)} + \beta((\mathbf{I} + \mathbf{D}) - \beta\mathbf{A}_{low})^{-1}\mathbf{s}$ , since  $(\mathbf{I} + \mathbf{D}) - \beta\mathbf{A}_{low}$  is nonsingular for any admissible  $\beta$ .

We next analyze the convergence of the memory-augmented method and derive sufficient conditions on the parameters to ensure convergence.

**LEMMA 4.5 (CONVERGENCE RANGE FOR MEMOITER).** *Matrix  $\mathbf{I} + \mathbf{D} - \mathbf{A}$  has nonzero diagonal entries and the memory-augmented iteration is well-defined. This method converges when  $0 < \beta < 2$ .*

**PROOF.** Suppose the memory-augmented iteration converges. Then  $\rho(\mathcal{L}_\beta) < 1$ . Let  $\{\lambda_i\}_{i=1}^n$  be the eigenvalues of  $\mathcal{L}_\beta$ . By the AMGM inequality,  $|\det(\mathcal{L}_\beta)| = \prod_{i=1}^n |\lambda_i| \leq (\rho(\mathcal{L}_\beta))^n < 1$ , hence  $|\det(\mathcal{L}_\beta)|^{1/n} < 1$ .

On the other hand, using memory-augmented representation and the triangular structure,

$$\det(\mathcal{L}_\beta) = \det(\mathbf{I} + \mathbf{D} - \beta\mathbf{A}_{low})^{-1} \det((1-\beta)(\mathbf{I} + \mathbf{D}) + \beta\mathbf{A}_{up})$$

$$= \frac{1}{\prod_{i=1}^n a_{ii}} \cdot (1-\beta)^n \prod_{i=1}^n a_{ii} = (1-\beta)^n.$$

Therefore  $|(1-\beta)^n|^{1/n} = |1-\beta| < 1$ , which is equivalent to  $0 < \beta < 2$ .

For the converse, when  $\mathbf{I} + \mathbf{D} - \mathbf{A}$  is strictly diagonally dominant by rows or SPD, classical theory of stationary iterations implies that the iteration matrix has spectral radius strictly smaller than one. The iteration matrix can be written as  $\mathcal{L}_\beta = (\mathbf{I} - \beta(\mathbf{I} + \mathbf{D})^{-1} \mathbf{A}_{low})^{-1} ((1 - \beta)\mathbf{I} + \beta(\mathbf{I} + \mathbf{D})^{-1} \mathbf{A}_{up})$ , and for  $0 < \beta < 2$  it is a convergent regular splitting of  $\mathbf{I} - \beta(\mathbf{I} + \mathbf{D})^{-1} \mathbf{A}$ . Under strict diagonal dominance or SPD, this yields  $\rho(\mathcal{L}_\beta) < 1$ . Hence the memory-augmented iteration converges.  $\square$

When  $\beta \in (0, 1)$ , the update corresponds to a conservative correction, where opinions are adjusted cautiously toward the latest estimate. The case  $\beta = 1$  recovers the sequential latest-opinion updates, while  $\beta \in (1, 2)$  induces an over-corrective behavior that can further accelerate convergence by intentionally amplifying the correction step. Accordingly, the range  $\beta \in (0, 2)$  serves as a sufficient condition that ensures convergence while maintaining a consistent interpretation of opinion adjustment.

referred to as the *adjustment gain*, regulates the magnitude of correction applied toward the latest locally computed opinion estimate. views it as a control parameter governing the responsiveness of opinion updates. The final opinion update is then obtained by applying a gain-controlled correction to the current opinion:

$$\mathbf{z}^{t+1} = (1 - \beta)\mathbf{z}^{(t)} + \beta\tilde{\mathbf{z}}^{(t+1)} = \mathbf{z}^{(t)} + \beta(\tilde{\mathbf{z}}^{(t+1)} - \mathbf{z}^{(t)}),$$

This enables a larger amount of residual mass to be transferred in each update, thereby accelerating convergence while maintaining locality.

Moreover, we derive the optimal choice of  $\beta$  that minimizes the convergence rate of the memory-augmented algorithm.

**LEMMA 4.6 (OPTIMAL CONVERGENT PARAMETER).** *Matrix  $\mathbf{I} + \mathbf{D} - \mathbf{A}$  is SPD and let  $B_0 = (\mathbf{I} + \mathbf{D})^{-1}(\mathbf{A}_{low} + \mathbf{A}_{up})$  be the iteration matrix with spectral radius  $\rho(B_0) = \rho \in (0, 1)$ . Then the spectral radius of the iteration matrix satisfies*

$$\rho(\mathcal{L}_\beta) = \left| \frac{1 - \sqrt{1 - \rho^2}}{1 + \sqrt{1 - \rho^2}} \right| \quad \text{when} \quad \beta = \beta^* \triangleq \frac{2}{1 + \sqrt{1 - \rho^2}}.$$

Moreover,  $\beta^* \in (1, 2)$  and minimizes  $\rho(\mathcal{L}_\beta)$  over  $\beta \in (0, 2)$ .

**PROOF.** For iterative matrix,  $B_0$  is diagonalizable with real spectrum in  $(-1, 1)$ , and the memory-augmented and latest-value iterations are related through Young's theory of semi-iterative methods. In particular, there exists a one-to-one correspondence between each eigenvalue  $\mu \in (-1, 1)$  of  $B_0$  and an eigenvalue  $\lambda(\omega, \mu)$  of  $\mathcal{L}_\omega$  given by the quadratic relation  $\lambda^2 - (1 - \omega)\lambda - \omega^2 \frac{\mu^2}{4} = 0$ . Solving (4.2) yields  $\lambda_{\pm}(\omega, \mu) = \frac{1}{2} \left( 1 - \omega \pm \sqrt{(1 - \omega)^2 + \omega^2 \mu^2} \right)$ . Hence the spectral radius of  $\mathcal{L}_\omega$  is  $\rho(\mathcal{L}_\omega) = \max_{\mu \in [-\rho, \rho]} \max\{|\lambda_+(\omega, \mu)|, |\lambda_-(\omega, \mu)|\}$ . For fixed  $\omega \in (0, 2)$ , the right-hand side is maximized at the extreme values  $\mu = \pm\rho$ . Therefore the best  $\omega$  solves

$$\min_{\omega \in (0, 2)} \phi_\rho(\omega) \triangleq \frac{1}{2} \left| 1 - \omega + \sqrt{(1 - \omega)^2 + \omega^2 \rho^2} \right|.$$

---

**Algorithm 2:** GainIter (Gain-controlled latest-order opinion iteration)

---

**Input:** Graph  $G = (V, E)$  with degrees  $(d_i)$  and neighbor sets  $(N_i)$ ; internal opinion  $s \in \mathbb{R}^n$ ; relaxation parameter  $\beta > 0$ ; maximum iteration limit  $T_{max}$ ; tolerance  $\epsilon$

**Output:** Estimated opinion vector  $\mathbf{z}$ ; iteration count  $\mathbf{t}$

```

1  $\mathbf{z} \leftarrow \mathbf{0} \in \mathbb{R}^n$ ;  $\mathbf{z}^{\text{old}} \leftarrow \mathbf{z}$ ;  $\alpha_i \leftarrow 1/(1 + d_i)$  for
   $i = 1, \dots, n$ 
2 for  $\mathbf{t} \leftarrow 1$  to  $T_{max}$  do
3    $\mathbf{z}^{\text{old}} \leftarrow \mathbf{z}$ 
4   for  $i \leftarrow 1$  to  $n$  do
5      $\mathbf{h} \leftarrow \mathbf{0}$ 
6     foreach  $j \in N_i$  do
7        $\mathbf{h} \leftarrow \mathbf{h} + a_{ij} \cdot (\text{Latest}(j))$ 
          // Latest( $j$ ):  $z_j$  if node  $j$  has been
          updated, otherwise  $z_j^{\text{old}}$ .
8      $y_i \leftarrow \alpha_i (s_i + \mathbf{h})$ 
9      $z_i \leftarrow z_i + \beta (y_i - z_i)$ 
10  if  $\|\mathbf{z} - \mathbf{z}^{\text{old}}\|_\infty \leq \epsilon$  then
11    return  $(\mathbf{z}, \mathbf{t})$ 
12 return  $(\mathbf{z}, \mathbf{t})$ 
```

---

Elementary calculus (setting  $\frac{d}{d\omega} \phi_\rho(\omega) = 0$  for  $\omega \in (0, 2)$ ) or the standard Chebyshev argument gives the minimizer  $\omega^* = \frac{2}{1 + \sqrt{1 - \rho^2}}$ , for which the two roots have equal magnitude, and the resulting minimal spectral radius is  $\rho(\mathcal{L}_\omega)|_{\omega=\omega_{\text{opt}}} = \frac{1 - \sqrt{1 - \rho^2}}{1 + \sqrt{1 - \rho^2}} \in (0, 1)$ . Since  $\rho \in (0, 1)$ , we have  $\sqrt{1 - \rho^2} \in (0, 1)$  and thus  $\omega_{\text{opt}} \in (1, 2)$ . This completes the proof.  $\square$

## 5 Opinion Iteration with Historical Memory

In the previous section, we developed accelerated opinion update schemes by refining the iterative perspective of the classical Friedkin–Johnsen (FJ) model. In particular, the *Lat-estIter* framework exploits the most recently available neighbor information, while the gain-controlled variant further modulates the relative impact of newly propagated opinions and agents' current states. These designs are motivated by practical considerations in real-world opinion diffusion and remain within the standard first-order dynamical setting, where opinion evolution depends solely on the current configuration.

Beyond the iterative interpretation, the FJ model admits an alternative and equally important explanation from a game-theoretic perspective. Specifically, it can be viewed as a quadratic utility game in which each agent balances social conformity against attachment to its intrinsic opinion, and the resulting equilibrium corresponds to a Nash equilibrium that minimizes a global social cost. This viewpoint highlights

the FJ dynamics as an implicit equilibrium-seeking process driven by rational, yet bounded, decision making.

However, existing studies predominantly focus on a Markovian opinion updating mechanism, where the state transition depends only on the current opinion profile. Such memoryless dynamics neglect the influence of historical opinions, despite the fact that, in realistic social interactions, individuals often revise their beliefs by accounting for recent experience and accumulated past stances. From a game-theoretic standpoint, this limitation excludes an important class of path-dependent behaviors that naturally arise in repeated or evolving games, especially under noisy environments or gradual belief stabilization.

Motivated by this observation, we extend the FJ opinion dynamics by incorporating a finite memory into the update process. Rather than relying exclusively on the current opinion state, the proposed model allows agents to leverage their immediate opinion history, leading to a second-order opinion iteration. This modification preserves the linear structure of the original FJ model, while enriching its temporal dynamics and enabling a more faithful representation of history-dependent strategic adjustment. As will be shown, the resulting scheme admits a compact state-space formulation, which facilitates convergence analysis and spectral characterization.

While this interpretation justifies the convergence of standard FJ dynamics, it also reveals an inherent limitation: the induced best-response process is memoryless and depends only on the current opinion profile. In contrast, many repeated and evolving games exhibit path-dependent behavior, where agents incorporate past actions to stabilize or accelerate convergence. This observation motivates the incorporation of historical opinions into the FJ dynamics, leading naturally to a second-order, memory-augmented opinion evolution scheme.

Recall that the classical FJ iteration updates the opinion vector according to  $\mathbf{z}^{(t+1)} = (\mathbf{I} + \mathbf{D})^{-1} \mathbf{A} \mathbf{z}^{(t)} + (\mathbf{I} + \mathbf{D})^{-1} \mathbf{s}$ , where  $\mathbf{z}^{(t)} = [z_1^{(t)}, \dots, z_n^{(t)}]^\top$  denotes the opinion profile at iteration  $t$ .

In the memory-augmented setting, given the current and previous opinion states  $\mathbf{z}^{(t)}$  and  $\mathbf{z}^{(t-1)}$ , we first compute the intermediate updates produced by the FJ operator,  $\mathbf{x}^{(t)} = (\mathbf{I} + \mathbf{D})^{-1} \mathbf{A} \mathbf{z}^{(t)} + (\mathbf{I} + \mathbf{D})^{-1} \mathbf{s}$ ,  $\mathbf{x}^{(t-1)} = (\mathbf{I} + \mathbf{D})^{-1} \mathbf{A} \mathbf{z}^{(t-1)} + (\mathbf{I} + \mathbf{D})^{-1} \mathbf{s}$ . The next opinion state is then obtained by forming a convex combination of these two intermediate states,

$$\mathbf{z}^{(t+1)} = \eta \mathbf{x}^{(t)} + (1 - \eta) \mathbf{x}^{(t-1)},$$

where  $\eta \in (0, 1)$  controls the relative influence of the most recent and historical information. The initial condition is set as  $\mathbf{z}^{(0)} = \mathbf{z}^{(-1)}$ .

From an implementation perspective, this scheme requires each agent to retain only the locally aggregated opinion from the previous iteration, rather than the entire opinion trajectory. As a result, the memory overhead remains minimal while enabling richer temporal dynamics. When  $\eta = 1$ , the iteration reduces to the standard FJ model.

To facilitate analysis, the memory-augmented system can be equivalently expressed in a first-order state-space form. Define

$$\mathbf{u}^{(t)} = \mathbf{z}^{(t-1)}, \quad \mathbf{y}^{(t)} = \begin{bmatrix} \mathbf{z}^{(t)} \\ \mathbf{u}^{(t)} \end{bmatrix}.$$

Then the evolution of  $\mathbf{y}^{(t)}$  is governed by

$$\mathbf{y}^{(t+1)} = \mathbf{G} \mathbf{y}^{(t)} + \mathbf{c},$$

where

$$\mathbf{G} = \begin{bmatrix} \eta(\mathbf{I} + \mathbf{D})^{-1} \mathbf{A} & (1 - \eta)(\mathbf{I} + \mathbf{D})^{-1} \mathbf{A} \\ \mathbf{I} & \mathbf{0} \end{bmatrix}, \quad \mathbf{c} = \begin{bmatrix} (\mathbf{I} + \mathbf{D})^{-1} \mathbf{s} \\ \mathbf{0} \end{bmatrix}.$$

The convergence of the proposed second-order iteration is therefore characterized by the spectral radius  $\rho(\mathbf{G})$ , which determines the worst-case convergence rate and forms the basis for the subsequent theoretical analysis.

**THEOREM 5.1.** *Let  $\mathbf{A}$  be an averaging matrix with a real spectrum. Suppose that  $x_i(1) = y_i$ ,  $i \in \{1, 2, \dots, n\}$ , and  $\sum_{i=1}^n x_i(0) = \sum_{i=1}^n y_i$ . Then the opinion vector  $\mathbf{z}(t)$  of the second-order iteration converges, and faster than the original FJ iteration if  $0 < \gamma < \sigma_2^2$ .*

**PROOF OF THEOREM 1 (ITEM 4).** Let  $\mathbf{A}$  be an averaging matrix with real spectrum, and consider the augmented iteration matrix

$$\mathbf{B} = \begin{bmatrix} (g+1)\mathbf{A} & -g\mathbf{I} \\ \mathbf{I} & \mathbf{0} \end{bmatrix}, \quad -1 < g < 1.$$

Denote by  $\rho_2(\mathbf{B})$  the convergence factor of the augmented system (4), and by  $\sigma_2 \in [0, 1)$  the second largest singular value of  $\mathbf{A}$ , which is also the convergence factor of the original system (2). Item 4 asserts that the augmented system converges strictly faster than the original one whenever

$$0 < g < \sigma_2^2, \quad \text{i.e.,} \quad \rho_2(\mathbf{B}) < \sigma_2.$$

We first consider the case  $-1 < g \leq g^*$ . By Lemma 4, the convergence factor of the augmented system is given by

$$\rho_2(\mathbf{B}) = \frac{1}{2} \left( \sigma_2(g+1) + \sqrt{\sigma_2^2(g+1)^2 - 4g} \right),$$

and in particular  $\rho_2(\mathbf{B}) = \sigma_2$  when  $g = 0$ . Moreover, Proposition 3 shows that  $\rho_2(\mathbf{B})$  is strictly decreasing on the interval  $(-1, g^*]$ . Consequently, for any

$$0 < g \leq \min\{g^*, \sigma_2^2\},$$

we have

$$\rho_2(\mathbf{B}) < \rho_2(\mathbf{B})|_{g=0} = \sigma_2.$$

Next, consider the case  $g^* < g < 1$ . By Lemma 5, the convergence factor simplifies to

$$\rho_2(\mathbf{B}) = \sqrt{g}.$$

Therefore, for any  $g$  satisfying

$$g^* < g < \sigma_2^2,$$

it follows immediately that

$$\rho_2(\mathbf{B}) = \sqrt{g} < \sigma_2.$$

Combining the two cases above, we conclude that for all

$$0 < g < \sigma_2^2,$$

the inequality

$$\rho_2(B) < \sigma_2$$

holds. Hence, the augmented system (4) converges strictly faster than the original system (2), which completes the proof of Item 4.  $\square$

**PROPOSITION 5.2.** *Suppose that  $A$  is an matrix with a real spectrum. Let*

$$B = \begin{bmatrix} (\gamma + 1)A & -\gamma I \\ I & 0 \end{bmatrix}$$

*where  $-1 < \gamma < 1$ . Then the minimum of  $\rho_2(B)$  is unique. The iteration converge fastest when*

$$\gamma = \frac{1 - \sqrt{1 - \sigma_2^2}}{1 + \sqrt{1 - \sigma_2^2}}. \quad (11)$$

**PROOF OF PROPOSITION 3.** From Lemmas 4 and 5, it is clear that  $\rho_2(B)$  is a continuous function of  $\gamma$  on the interval  $(-1, 1)$ . When  $-1 < \gamma \leq \gamma^*$ , by Lemma 4 and the fact that  $\partial \rho_2 / \partial \gamma < 0$ ,  $\rho_2(B)$  is a decreasing function of  $\gamma$ . When  $\gamma^* < \gamma < 1$ ,  $\rho_2(B)$  is an increasing function of  $\gamma$  by Lemma 5. Since  $\rho_2(B)$  is continuous at  $\gamma^*$ ,  $\gamma^*$  is the unique point in the interval  $(-1, 1)$  which minimizes  $\rho_2(B)$ . Then the optimal value of  $\gamma$  at this minimum is

$$\gamma^* = \frac{1 - \sqrt{1 - \sigma_2^2}}{1 + \sqrt{1 - \sigma_2^2}},$$

and the minimum of  $\rho_2(B)$  is

$$\rho_2^* = \frac{\sigma_2}{1 + \sqrt{1 - \sigma_2^2}}. \quad (12)$$

$\square$

---

**Algorithm 3:** SECONDORDERITER( $G, \gamma, \epsilon, T_{max}$ )

---

**Input** : A graph  $G = (V, E)$  with adjacency matrix  $A$ , degree vector  $d$ , internal opinions  $s$ ; acceleration parameter  $\gamma \in \mathbb{R}$ ; tolerance  $\epsilon$  and maximum iterations  $T_{max}$ .

**Output:** Estimated opinion vector  $z$ .

1 **Precompute:**

2  $\hat{D}^{-1} \leftarrow \text{diag}\left(\frac{1}{1 + d_i}\right)_{i \in V}$ ;  $P \leftarrow \hat{D}^{-1}A$ ;  $b \leftarrow \hat{D}^{-1}s$

3 **Initialize:**

4  $z^{(0)} \leftarrow s$ ;  $k \leftarrow 0$ ;  $r \leftarrow +\infty$

5 **while**  $k < T_{max}$  **and**  $r > \epsilon$  **do**

6  $u \leftarrow P z^{(k)}$  //  $u$  is a work vector

7  $z^{(k+1)} \leftarrow \gamma u + (1 - \gamma) z^{(k-1)} + b$

8  $r \leftarrow \|z^{(k+1)} - z^{(k)}\|_2$

9 **if**  $r \leq \epsilon$  **then**

10  $\quad \text{return } z^{(k+1)}$

11  $z^{(k-1)} \leftarrow z^{(k)}$ ;  $z^{(k)} \leftarrow z^{(k+1)}$

12  $k \leftarrow k + 1$

13 **return**  $z^{(k)}$

---

## 6 Experiments

In this section, we assess the efficiency and accuracy of our estimation algorithm LATESTITER and MEMOITER. To this end, we implement this algorithm on various real networks and compare the running time and accuracy of our algorithm with those corresponding to the previous algorithm, called LOCALITER. The estimation of relevant quantities perform product of related matrices, and calculate corresponding  $\ell_2$  norms.

*Environment.* Our code for the estimation algorithm LATESTITER and MEMOITER were written in *Julia v1.5.1*. The *Julia language* implementation for which is open and accessible on the website<sup>1</sup>.

**Datasets and Equipment** All the real-world networks we consider are publicly available in the Koblenz Network Collection and Network Repository. Our experiments are conducted on a diverse range of both undirected and directed networks, including social networks. For these datasets, the number  $n$  of nodes ranges from about 16 thousand to 33 million, and the number  $m$  of directed edges ranges from about 25 thousand to 301 million. The details of these datasets are presented in Table 1. All experiments are conducted using the Julia programming language. We conduct all experiments in a computational environment featuring a 4.2 GHz Intel i7-7700 CPU with 64GB of primary memory.

**Algorithm** For evaluating the performance of our algorithms estimating the opinion vector of the FJ model, we compare our three proposed algorithms LATESTITER, MEMOITER, and SECONDITER with two state-of-the-art algorithms, namely SOLVER and BLI SOR. While one of the two state-of-the-art algorithms, SOLVER, is confined to undirected graphs due to the limitations of the Laplacian solver. Our proposed algorithm is applicable to both undirected and directed graphs.

**Internal opinion distributions.** In our experiments, the internal opinions are generated according to three different distributions: uniform distribution, exponential distribution, and power-law distribution. For the uniform distribution, the opinion  $s_i$  of node  $i$  is distributed uniformly in the range of  $[0, 1]$ . For the exponential distribution, we choose the probability density  $e^{x_{\min}} e^{-x}$  to generate  $n'$  positive numbers  $x$  with minimum value  $x_{\min} > 0$ . Then, dividing each  $x$  by the maximum observed value, we normalize these  $n'$  numbers to the range  $[0, 1]$  as the internal opinions of nodes. Note that there is always a node with internal opinion 1 due to the normalization operation. Similarly, for the power-law distribution, we use the probability density  $(\alpha - 1)x_{\min}^{\alpha-1} x^{-\alpha}$  with  $\alpha = 2.5$  to generate  $n'$  positive numbers, and normalize them to interval  $[0, 1]$  as the internal opinions.

*Efficiency.* Table 2 reports the running time of six methods, namely SOLVER, LI, LISOR, LATESTITER, MEMOITER,

<sup>1</sup>URL omitted here.



**Table 1: Statistics of the evaluated datasets.**

| Dataset              | $n$       | $m$         | $d_{max}$ |
|----------------------|-----------|-------------|-----------|
| BlogCatalog          | 2,426     | 16,630      | 273       |
| DBLP                 | 317,080   | 1,049,866   | 343       |
| YouTubeSnap          | 1,134,890 | 2,987,624   | 28,754    |
| Flixster             | 2,523,386 | 7,918,801   | 1,474     |
| out.youtube-u-growth | 3,072,441 | 117,185,083 | 33,313    |

and SECONDITER, on several real-world networks of increasing scale. We observe that SOLVER, which computes the exact solution by directly solving the linear system, is consistently the most time-consuming method and becomes increasingly expensive as the network size grows. In contrast, all iterative methods exhibit significantly better scalability.

Among the iterative solvers, LI and LISOR show stable and predictable performance across all datasets, with LISOR being slightly faster than LI in most cases. The Gauss-Seidel based method LATESTITER and its over-relaxed variant MEMOITER further reduce the running time on medium-scale networks such as Enron and DBLP, while maintaining low iteration counts. The second-order accelerated method SECONDITER is the fastest on several large graphs, including YouTubeSnap and out.youtube, where it achieves the shortest running time among all tested methods.

Overall, Table 2 demonstrates that the proposed iterative methods provide substantial efficiency gains over the exact solver, especially on large-scale graphs with millions of nodes, where SOLVER becomes prohibitively slow, while the iterative methods remain practical.

*Accuracy.* Besides efficiency, we also evaluate the accuracy of the iterative methods by comparing their outputs with the exact solution produced by SOLVER. For each method and each dataset, we report the absolute error on a representative entry of the solution vector, as shown in the right part of Table 2.

The results indicate that LI and LISOR consistently achieve errors on the order of  $10^{-3}$  or below across all datasets, demonstrating reliable approximation quality. LATESTITER and MEMOITER generally attain even smaller errors, often in the range of  $10^{-5}$  to  $10^{-4}$ , especially on moderately sized networks such as Enron and DBLP. Although SECONDITER occasionally exhibits slightly larger errors on some large graphs (e.g., DBLP and out.youtube), its error remains within acceptable bounds for practical applications.

Overall, the empirical results confirm that all iterative methods achieve high accuracy in practice, with errors that are small

## 7 Conclusion

In this paper, we addressed the problem of computing single-node equilibrium opinions in the Friedkin-Johnsen model. We introduced the absorbing random-walk interpretation

and developed local algorithms that avoid full-matrix computation. Our first contribution is a residual-based framework with synchronous and asynchronous iterations, together with a residue invariant that precisely characterizes the error and enables practical stopping rules and convergence bounds.

To further enhance scalability, we proposed a push-sampling algorithm (AIMS) that couples asynchronous local pushes with importance sampling over the residual distribution. The method preserves the invariant, uses random walks only to estimate the unprocessed mass, and yields an unbiased estimator with concentration guarantees. The  $\tau$ -controlled sampling budget provides a clear trade-off between push work and variance, making the approach effective on both directed and undirected graphs.

Extensive experiments on real networks with up to tens of millions of nodes demonstrate that our methods are accurate and efficient, outperforming classical solvers and direct Monte Carlo baselines, and extending naturally to average-opinion estimation.

Currently, our framework does not adaptively schedule the mix of push and sampling across nodes. In future work, we plan to develop variance-aware scheduling, extend to time-varying and weighted networks, and integrate our methods with preconditioned linear solvers to support batch queries.

Table 2: Running time (seconds) and error of different iterative methods on real-world networks.

| Dataset     | RUNNING TIME (s) |       |       |            |          |            | ERROR                 |                       |                       |                       |                       |
|-------------|------------------|-------|-------|------------|----------|------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
|             | Solver           | LI    | LISOR | LatestIter | MemoIter | SecondIter | LI                    | LISOR                 | LatestIter            | MemoIter              | SecondIter            |
| BlogCatalog | 5.08             | 0.54  | 0.20  | 0.08       | 0.02     | 0.47       | $1.29 \times 10^{-3}$ | $5.62 \times 10^{-4}$ | $3.44 \times 10^{-2}$ | $7.09 \times 10^{-2}$ | $1.38 \times 10^{-3}$ |
| Enron       | 0.37             | 0.02  | 0.01  | 0.03       | 0.01     | 0.01       | $3.13 \times 10^{-1}$ | $3.12 \times 10^{-1}$ | $5.11 \times 10^{-3}$ | $1.78 \times 10^{-3}$ | $8.74 \times 10^{-2}$ |
| DBLP        | 2.37             | 0.66  | 0.16  | 0.39       | 0.09     | 0.16       | $1.28 \times 10^{-3}$ | $4.79 \times 10^{-4}$ | $3.19 \times 10^{-5}$ | $8.76 \times 10^{-5}$ | $2.24 \times 10^{-2}$ |
| YouTubeSnap | 7.19             | 2.23  | 0.56  | 0.65       | 0.35     | 0.21       | $1.30 \times 10^{-3}$ | $2.74 \times 10^{-4}$ | $1.78 \times 10^{-3}$ | $8.43 \times 10^{-4}$ | $1.44 \times 10^{-2}$ |
| Flixster    | 17.41            | 7.64  | 1.88  | 1.72       | 0.94     | 3.19       | $1.35 \times 10^{-3}$ | $2.97 \times 10^{-4}$ | $3.08 \times 10^{-3}$ | $3.35 \times 10^{-4}$ | $3.89 \times 10^{-3}$ |
| out.youtube | 26.64            | 12.02 | 2.33  | 3.75       | 1.39     | 0.84       | $1.09 \times 10^{-3}$ | $5.35 \times 10^{-5}$ | $3.46 \times 10^{-4}$ | $5.13 \times 10^{-4}$ | $8.37 \times 10^{-3}$ |

## References

- [1] Rediet Abebe, Jon Kleinberg, David Parkes, and Charalampos E. Tsourakakis. 2018. Opinion Dynamics with Varying Susceptibility to Persuasion. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 10891098.
- [2] Brian DO Anderson and Mengbin Ye. 2019. Recent advances in the modelling and analysis of opinion dynamics on influence networks. *International Journal of Automation and Computing* (2019), 129–149.
- [3] Luca Avena and Alexandre Gaudillière. 2018. Two applications of random spanning forests. *Journal of Theoretical Probability* (2018), 1975–2004.
- [4] Carmela Bernardo, Lingfei Wang, Francesco Vasca, Yiguang Hong, Guodong Shi, and Claudio Altafini. 2021. Achieving consensus in multilateral international negotiations: The case study of the 2015 Paris Agreement on climate change. *Science Advances* (2021), eabg8068.
- [5] David Bindel, Jon Kleinberg, and Sigal Oren. 2015. How bad is forming your own opinion? *Games and Economic Behavior* (2015), 248–265.
- [6] T-H. Hubert Chan, Zhibin Liang, and Mauro Sozio. 2019. Revisiting Opinion Dynamics with Varying Susceptibility to Persuasion via Non-Convex Local Search. In *The World Wide Web Conference*. 173183.
- [7] Mayee F Chen and Miklós Z Rácz. 2021. An adversarial model of network disruption: Maximizing disagreement and polarization in social networks. *IEEE Transactions on Network Science and Engineering* (2021), 728–739.
- [8] Xi Chen, Jeffrey Lijffijt, and Tijl De Bie. 2018. Quantifying and minimizing risk of conflict in social networks. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 1197–1205.
- [9] Pranav Dandekar, Ashish Goel, and David T Lee. 2013. Biased assimilation, homophily, and the dynamics of polarization. *Proceedings of the National Academy of Sciences* (2013), 5791–5796.
- [10] Abhimanyu Das, Sreenivas Gollapudi, Rina Panigrahy, and Mahyar Salek. 2013. Debiasing social wisdom. In *Proceedings of the 19th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 500508.
- [11] Yucheng Dong, Min Zhan, Gang Kou, Zhaogang Ding, and Haiming Liang. 2018. A survey on the fusion process in opinion dynamics. *Information Fusion* (2018), 57–65.
- [12] Noah E Friedkin and Eugene C Johnsen. 1990. Social influence and opinions. *Journal of Mathematical Sociology* (1990), 193–206.
- [13] Noah E Friedkin, Anton V Proskurnikov, Roberto Tempo, and Sergey E Parsegov. 2016. Network science on belief system dynamics under logic constraints. *Science* (2016), 321–326.
- [14] Jason Gaitonde, Jon Kleinberg, and Eva Tardos. 2020. Adversarial perturbations of opinion dynamics in networks. In *Proceedings of the 21st ACM Conference on Economics and Computation*. 471–472.
- [15] Javad Ghaderi and Rayadurgam Srikant. 2014. Opinion dynamics in social networks with stubborn agents: Equilibrium and convergence rate. *Automatica* (2014), 3209–3215.
- [16] Aristides Gionis, Evimaria Terzi, and Panayiotis Tsaparas. 2013. Opinion maximization in social networks. In *Proceedings of the 2013 SIAM international conference on data mining*. 387–395.
- [17] Peng Jia, Anahita MirTabatabaei, Noah E Friedkin, and Francesco Bullo. 2015. Opinion dynamics and the evolution of social power in influence networks. *SIAM review* (2015), 367–397.
- [18] Heidi Ledford. 2020. How Facebook, Twitter and other data troves are revolutionizing social science. *Nature* (2020), 328–330.
- [19] Antonis Matakos, Evimaria Terzi, and Panayiotis Tsaparas. 2017. Measuring and moderating opinion polarization in social networks. *Data Mining and Knowledge Discovery* (2017), 1480–1505.
- [20] Cameron Musco, Christopher Musco, and Charalampos E Tsourakakis. 2018. Minimizing polarization and disagreement in social networks. In *Proceedings of the 2018 world wide web conference*. 369–378.
- [21] Stefan Neumann, Yinhao Dong, and Pan Peng. 2024. Sublinear-Time Opinion Estimation in the Friedkin–Johnsen Model. In *Proceedings of the ACM on Web Conference 2024*. 25632571.
- [22] Sergey E Parsegov, Anton V Proskurnikov, Roberto Tempo, and Noah E Friedkin. 2016. Novel multidimensional models of opinion dynamics in social networks. *IEEE Trans. Automat. Control* (2016), 2270–2285.
- [23] Anton V Proskurnikov and Roberto Tempo. 2017. A tutorial on modeling and analysis of dynamic social networks. Part I. *Annual Reviews in Control* (2017), 65–79.
- [24] Chiara Ravazzi, Paolo Frasca, Roberto Tempo, and Hideaki Ishii. 2014. Ergodic randomized algorithms and dynamics over networks. *IEEE transactions on control of network systems* (2014), 78–87.
- [25] Justin Semonsen, Christopher Griffin, Anna Squicciarini, and Sarah Rajtmajer. 2018. Opinion dynamics in the presence of increasing agreement pressure. *IEEE transactions on cybernetics* (2018), 1270–1278.
- [26] Haoxin Sun and Zhongzhi Zhang. 2023. Opinion Optimization in Directed Social Networks. *Proceedings of the AAAI Conference on Artificial Intelligence* (2023), 4623–4632.
- [27] Sijing Tu and Stefan Neumann. 2022. A viral marketing-based model for opinion dynamics in online social networks. In *Proceedings of the ACM Web Conference 2022*. 1570–1578.
- [28] Sijing Tu, Stefan Neumann, and Aristides Gionis. 2023. Adversaries with limited information in the friedkin-johnsen model. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 2201–2210.
- [29] Gengyu Wang, Runze Zhang, and Zhongzhi Zhang. 2025. Efficient Algorithms for Relevant Quantities of Friedkin–Johnsen Opinion Dynamics Model. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*. 2915–2926.
- [30] Wanyue Xu, Qi Bao, and Zhongzhi Zhang. 2021. Fast Evaluation for Relevant Quantities of Opinion Dynamics. In *Proceedings of the Web Conference 2021*. 20372045.
- [31] Liwang Zhu, Qi Bao, and Zhongzhi Zhang. 2021. Minimizing polarization and disagreement in social networks via link recommendation. *Advances in Neural Information Processing Systems* (2021), 2072–2084.
- [32] Liwang Zhu and Zhongzhi Zhang. 2022. A nearly-linear time algorithm for minimizing risk of conflict in social networks. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 2648–2656.

---

**Algorithm 4:** Fixed-point iteration for  $z = (I + D)^{-1}(s + Az)$

---

**Input:** Sparse  $A \in \mathbb{R}^{n \times n}$ ,  $s \in \mathbb{R}^n$ , optional  $z_0$ , tolerance  $\varepsilon > 0$ , maxiter, relaxation  $\lambda \in (0, 2]$

**Output:**  $z$ , iteration count  $k$ , convergence flag

```

1 denomi  $\leftarrow 1 + \sum_j A_{ij}$  for  $i = 1, \dots, n$ 
  //  $I + D = \text{diag}(\text{denom})$ 
2  $z \leftarrow s$ ,
3 for  $k \leftarrow 1$  to maxiter do
4    $a \leftarrow Az$  // sparse matvec
5    $z_i^{\text{new}} \leftarrow (s_i + a_i)/\text{denom}_i$  for  $i = 1, \dots, n$ 
6   if  $\lambda \neq 1$  then
7      $z^{\text{new}} \leftarrow (1 - \lambda)z + \lambda z^{\text{new}}$  // relaxation
8   if  $\|z^{\text{new}} - z\|_\infty < \varepsilon$  then
9     return ( $z^{\text{new}}$ ,  $k$ , true)
10   $z \leftarrow z^{\text{new}}$ 
11 return ( $z$ , maxiter, false)

```

---

## A Appendix: Pseudocode

In Appendix A, we present eliminated pseudocode in the main text.

### A.1 Pseudocode of WeightedForest

## B Appendix: Proof

In Appendix B, we provide the proofs of the theorems and lemmas in the main text.

### B.1 Useful Tools

#### B.1.1 (matrix convergence).

LEMMA B.1. Let  $B = (b_{ij})_{n \times n}$ . Then  $B^k \rightarrow 0$  as  $k \rightarrow \infty$  if and only if  $\rho(B) < 1$ .

### B.2 Proof of Equivalence with Jacobi

To show that FJ Iteration is a variant of the fixed-point iteration, recall that for solving the linear system  $M\mathbf{x} = \mathbf{b}$ , the Jacobi method updates the solution vector  $\mathbf{x}$ . Specifically, the update for coordinate  $u$  at iteration  $t$  is

$$x_u^{t+1} = \frac{1}{m_{uu}} \left( b_u - \sum_{j \neq u} m_{uj} x_j^t \right), \quad (13)$$

where  $t$  indexes the current iteration. Here,  $x_j^t$  denotes entries updated in the  $t$ -th sweep. In the classical Jacobi method we simply update all coordinates during iteration  $t$ .

The iteration is well suited for linear systems where  $M$  is strictly diagonally dominant. In particular, for a simple graph, the matrix  $I + D - A$  is strictly diagonally dominant, and thus its fixed-point iteration naturally fits into the Jacobi framework.

The theorem below establishes the precise equivalence between this variant of the fixed-point iteration and the FJ Iteration.

LEMMA B.2 (FIXED-POINT FORM OF THE FJ ITERATION). *The FJ iteration in (1) is a fixed-point iteration of the affine mapping*

$$T(z) := (I + D)^{-1}(s + Az),$$

*whose fixed point is the unique solution of the linear system*

$$(I + D - A)z = s.$$

PROPOSITION B.3 (EQUIVALENCE WITH JACOBI COORDINATE UPDATES). *Under a sequential coordinate sweep, each coordinate update of the FJ iteration coincides exactly with a Jacobi update defined in 13 for the linear system*

$$Mz = b, \quad M = I + D - A, \quad b = s.$$

PROOF. Denote the approximate solution vector  $z_i^{(t)}$  defined by  $z_i^{(t)} = (z_1^{(t)}, z_2^{(t)}, \dots, z_{i-1}^{(t)}, z_i^{(t-1)}, \dots, z_n^{(t-1)})$ . Set the residual

$$r^{(t)} := b - Mz^{(t)} = s - (I + D - A)z^{(t)}.$$

Using the FJ update we obtain the linear invariant

$$\begin{aligned} z^{(t+1)} - z^{(t)} &= (I + D)^{-1}(s + Az^{(t)}) - z^{(t)} \\ &= (I + D)^{-1} \left[ s - (I + D - A)z^{(t)} \right] \\ &= (I + D)^{-1} r^{(t)}. \end{aligned}$$

Equivalently,  $r^{(t)} = (I + D)(z^{(t+1)} - z^{(t)})$ .

Let  $u$  be the coordinate being updated at time  $t$  in a G-S sweep. For the system  $Mz = b$  the G-S coordinate update reads

$$z_u = \frac{1}{M_{uu}} (b_u - \sum_{j \neq u} M_{uj} z_j^{(t)}),$$

subtract  $z_i^{(t)}$  from both sides,

$$z_u^{(t+1)} = z_u^{(t)} + \frac{(b - Mz^{(t)})_u}{M_{uu}} = z_u^{(t)} + \frac{r_u^{(t)}}{M_{uu}}.$$

Because  $M = (I + D - A)$ , its diagonal is

$$M_{uu} = (I + D - A)_{uu} = 1 + d_u.$$

Hence

$$z_u^{(t+1)} = z_u^{(t)} + \frac{r_u^{(t)}}{1 + d_u},$$

which is equivalent to the above invariants by expanding the FJ update for coordinate  $u$ :

$$z_u^{(t+1)} = z_u^{(t)} + ((I + D)^{-1} r^{(t)})_u = z_u^{(t)} + \frac{r_u^{(t)}}{1 + d_u},$$

It matches exactly the Gauss-Seidel coordinate update. Since this holds for any updated coordinate  $u$ , each coordinate update of the FJ iteration is equivalent to a single Gauss-Seidel update for the linear system  $Mz = b$ .  $\square$

FJ Iteration is actually a variant of the fixed-point iteration,

LEMMA B.4 (FIXED-POINT FORM OF THE FJ ITERATION).  
The FJ iteration in (1) is a fixed-point iteration of the affine mapping

$$T(z) := (I + D)^{-1}(s + Az),$$

whose fixed point is the unique solution of the linear system

$$(I + D - A)z = s.$$

LEMMA B.5. Throughout the iterations of the Gauss–Seidel–equivalent scheme, the following invariant relation is preserved:

$$z^* - z^{(t)} = (I + L)^{-1}r^{(t)}, \quad (14)$$

where  $r^{(t)} = s - (I + D - A)z^{(t)}$  denotes the error vector measuring the deviation of the  $t$ -th iterate from the true solution  $z^*$ .

PROOF. By definition, the exact solution satisfies  $z^* = (I + D - A)^{-1}s$ . Subtracting  $z^{(t)}$  from both sides yields

$$\begin{aligned} z^* - z^{(t)} &= (I + D - A)^{-1}s - z^{(t)} \\ &= (I + D - A)^{-1}(s - (I + D - A)z^{(t)}) \\ &= (I + D - A)^{-1}r^{(t)}. \end{aligned} \quad (15)$$

Since  $L = D - A$ , the claimed invariant relation follows. Therefore, throughout the Gauss–Seidel–equivalent iterations, the error between the current iterate and the true solution is completely characterized by the residual vector  $r^{(t)}$ , and the stated invariant is preserved.  $\square$

Based on the invariant established in Lemma 1, we can further derive an absolute error bound for the estimator upon termination of the iteration.

THEOREM B.6 (ERROR BOUND). For any accuracy parameter  $\epsilon > 0$ , the estimator  $z^{(t)}$  returned by the algorithm satisfies

$$\|z^* - z^{(t)}\|_2 \leq \epsilon. \quad (16)$$

PROOF. From Lemma 1, we have  $z^* - z^{(t)} = (I + L)^{-1}r^{(t)}$ . Taking the  $\ell_2$ -norm on both sides gives

$$\begin{aligned} \|z^* - z^{(t)}\|_2 &= \|(I + L)^{-1}r^{(t)}\|_2 \\ &\leq \|(I + L)^{-1}\|_2 \|r^{(t)}\|_2. \end{aligned} \quad (17)$$

By the termination criterion of the algorithm, the residual norm satisfies  $\|(I + L)^{-1}\|_2 \|r^{(t)}\|_2 \leq \epsilon$ , which completes the proof.  $\square$

LEMMA B.7.

$$\|z^* - z^{(t+1)}\|_v \leq \|(I - (I + D - A_{low})^{-1}A_{up})^{-1}\|_v \|z^{(t+1)} - z^{(t)}\|_v, \quad (18)$$

$$z - z^{(t)} = (I + L)^{-1}r^{(t)}$$

$$z^{(t+1)} - z^{(t)} = (I + D - A_{low})^{-1}r^{(t)}$$

PROOF. The latest-opinion update rule can be written as  $z^{(t+1)} = (I + D - A_{low})^{-1}A_{up}z^{(t)} + (I + D - A_{low})^{-1}s$ . Define the successive difference  $\Delta z^{(t+1)} = z^{(t+1)} - z^{(t)}$ . Then it follows directly that  $\Delta z^{(t+1)} = (I + D - A_{low})^{-1}A_{up} \Delta z^{(t)}$ .

Since the iteration converges to the unique fixed point  $z^*$ , we have  $z^* - z^{(t+1)} = \sum_{k=t+1}^{\infty} \Delta z^{(k+1)}$ . Substituting the recursive relation of  $\Delta z^{(t)}$  yields

$$\begin{aligned} z^* - z^{(t+1)} &= \sum_{l=0}^{\infty} [(I + D - A_{low})^{-1}A_{up}]^l \Delta z^{(t+1)} \\ &= (I - (I + D - A_{low})^{-1}A)^{-1} \Delta z^{(t+1)}, \end{aligned} \quad (19)$$

where the inverse exists due to the convergence of the Gauss–Seidel iteration.

Taking the  $\ell_1$ -norm on both sides leads to

$$\|z^* - z^{(t+1)}\|_1 \leq \|(I - (I + D)^{-1}A)^{-1}\|_1 \|z^{(t+1)} - z^{(t)}\|_1, \quad (20)$$

which establishes the claimed relation between the true estimation error and the difference of two consecutive iterates.  $\square$

LEMMA B.8 (EQUIVALENT A POSTERIORI ERROR REPRESENTATION). Let  $z^{(t)}$  be the sequence generated by LatestIter and let  $B = (I + D - A_{low})^{-1}A_{up}$  denote the corresponding iteration matrix. Then, for any vector norm  $\|\cdot\|_v$  compatible with matrix multiplication, the following relation holds:

$$\|z^* - z^{(t+1)}\|_v \leq \|(I - B)^{-1}\|_v \|z^{(t+1)} - z^{(t)}\|_v. \quad (21)$$

PROOF. The LatestIter update can be written as

$$z^{(t+1)} = Bz^{(t)} + (I + D - A_{low})^{-1}s.$$

Define the successive difference  $\Delta z^{(t+1)} = z^{(t+1)} - z^{(t)}$ . Then

$$\Delta z^{(t+1)} = B \Delta z^{(t)}.$$

Since the iteration converges to the unique fixed point  $z^*$ , we have

$$z^* - z^{(t+1)} = \sum_{k=t+1}^{\infty} \Delta z^{(k+1)}.$$

Substituting the recursive relation of  $\Delta z^{(t)}$  yields

$$z^* - z^{(t+1)} = \sum_{l=0}^{\infty} B^l \Delta z^{(t+1)} = (I - B)^{-1} \Delta z^{(t+1)},$$

where the inverse exists since the Gauss–Seidel iteration converges and  $\rho(B) < 1$ .

Taking the  $\|\cdot\|_v$  norm on both sides and using submultiplicativity completes the proof.  $\square$