


## Lab 3 Exercises


*These exercise questions are for self-practice. No submission is needed.*

**Notes:** The following partial ERD for AdventureWorks2008R2 was generated by SQL Server Management Studio. Use it to locate data when writing SQL queries.



**Notes:** If we don't have an ERD, we can also use the Object Explorer in SQL Server Management Studio to locate data by following the steps listed below.

- 1) Under Object Explorer in SQL Server Management Studio, expand Databases
- 2) Expand the database we want to work with, such as AdventureWorks2008R2
- 3) Expand Tables
- 4) Expand the table we want to work with, such as Sales.Customer
- 5) Expand Columns
- 6) Then we'll see all columns contained in a table



USE AdventureWorks2008R2;

### **Exercise 1**

```
/*
  SELECT ProductID, Name, ListPrice FROM Production.Product.
  Use the CASE function to display "Expensive" if ListPrice > 3000
                                     "Medium" if ListPrice > 1000
                                     "Low" if ListPrice <= 1000.
  ORDER the results DESC BY ListPrice.
*/
```

### **Exercise 2**

```
/*
  SELECT SalesOrderID, CustomerID, TotalDue
  FROM Sales.SalesOrderHeader
  WHERE TotalDue > 10000
  and RANK them with gaps in the desc order of TotalDue
*/
```

### **Exercise 3**

```
/*
  SELECT SalesOrderID, CustomerID, TotalDue
  FROM Sales.SalesOrderHeader
  WHERE TotalDue > 10000
  and RANK them with gaps in the desc order of TotalDue
  also PARTITION BY CustomerID
*/
```

#### **Exercise 4**

```
/*  
    SELECT SalesOrderID, CustomerID, TotalDue  
    FROM Sales.SalesOrderHeader  
    WHERE TotalDue > 10000  
    and RANK them with gaps in the desc order of TotalDue  
    also PARTITION BY CustomerID  
  
    Display only the highest total due amount for each customer.  
  
    Hints: For this exercise, we need to create a derived table  
           using a subquery. Then SELECT FROM the derived table.  
*/
```

#### **Exercise 5**

```
/* List the product id, product name, and order date of each  
   product sold in 2008.  
  
   Tables needed: Production.Product  
                  Sales.SalesOrderDetail  
                  Sales.SalesOrderHeader  
*/
```

#### **Exercise 6**

```
/* What is the name and average rating for the product with  
   ProductID = 937? */
```

#### **Exercise 7**

```
/* Use the SubTotal value in SalesOrderHeader to calculate  
   total value. What is the total value of products sold to  
   an address in 'Seattle'? */
```

```
/* Some report formatting examples */
```

```
/* Use system functions to format dates and make reports  
look better. */
```

```
/* CONVERT is NOT ANSI standard. */  
-- Display date portion of the system date and time.  
SELECT CONVERT(CHAR(20), GETDATE(), 1) AS [Current Date];
```

```
/* CAST is ANSI standard. */  
-- Display date portion of the system date and time.  
SELECT CAST(GETDATE() AS CHAR(11)) AS [Current Date];
```

```
-- Display both date and time of the system date and time.  
SELECT CAST(GETDATE() AS CHAR(20)) AS [Current Date and Time];
```

```
-- Display only the time portion of the system date and time.  
SELECT RIGHT(CAST(GETDATE() AS CHAR(20)), 8) AS [Current Time];
```

```
/* Use system functions to format numbers and make reports  
look better. */
```

```
SELECT CAST((ROUND(AVG(OrderQty + .0), 2)) AS decimal(5,2)) AS [Average  
Sales]  
FROM Sales.SalesOrderDetail  
WHERE UnitPrice BETWEEN 30 AND 50;
```

```
SELECT STR(ROUND(AVG(OrderQty + .0), 2), 8, 2) AS [Average Sales]  
FROM Sales.SalesOrderDetail  
WHERE UnitPrice BETWEEN 30 AND 50;
```

***Don't look at the solution until you have completed an exercise question.***

## -- Solutions

USE AdventureWorks2008R2;

### -- Exercise 1 Solution

```
/*
  SELECT ProductID, Name, ListPrice FROM Production.Product.
  Use the CASE function to display "Expensive" if ListPrice > 3000
  "Medium" if ListPrice > 1000
  "Low" if ListPrice <= 1000.
  ORDER the results DESC BY ListPrice.
*/
```

```
SELECT ProductID, Name, ListPrice,
CASE
  WHEN LISTPRICE > 3000
    THEN 'Expensive'
  WHEN LISTPRICE <= 1000
    THEN 'Low'
  ELSE 'Medium'
END AS PriceRange
FROM Production.Product
ORDER BY ListPrice DESC;
```

### -- Exercise 2 Solution

```
/*  
    SELECT SalesOrderID, CustomerID, TotalDue  
    FROM Sales.SalesOrderHeader  
    WHERE TotalDue > 10000  
    and RANK them with gaps in the desc order of TotalDue  
*/
```

```
SELECT RANK() OVER (ORDER BY TotalDue DESC) as [Rank],  
SalesOrderID, CustomerID, Totaldue  
FROM Sales.SalesOrderHeader  
WHERE TotalDue >10000;
```

### -- Exercise 3 Solution

```
/*  
    SELECT SalesOrderID, CustomerID, TotalDue  
    FROM Sales.SalesOrderHeader  
    WHERE TotalDue > 10000  
    and RANK them with gaps in the desc order of TotalDue  
    also PARTITION BY CustomerID  
*/
```

```
SELECT RANK() OVER (PARTITION BY CustomerID ORDER BY TotalDue DESC) as  
[Rank],  
SalesOrderID, CustomerID, Totaldue  
FROM Sales.SalesOrderHeader  
WHERE TotalDue >10000;
```



#### -- Exercise 4 Solution

```
/*
    SELECT SalesOrderID, CustomerID, TotalDue
    FROM Sales.SalesOrderHeader
    WHERE TotalDue > 10000
    and RANK them with gaps in the desc order of TotalDue
    also PARTITION BY CustomerID

    Display only the highest total due amount for each customer.

*/
```

```
SELECT * FROM
    (SELECT RANK() OVER (PARTITION BY CustomerID
        ORDER BY TotalDue DESC) as [Rank],
        SalesOrderID, CustomerID, Totaldue
    FROM Sales.SalesOrderHeader
    WHERE TotalDue >10000) a
WHERE a.[Rank] = 1;
```

-- For this exercise, we need to create a derived table using a subquery.  
-- Then SELECT FROM the derived table.

#### -- Exercise 5 Solution

```
/* List the product id, product name, and order date of each
    product sold in 2008.
```

Tables needed: Production.Product  
Sales.SalesOrderDetail  
Sales.SalesOrderHeader

```
*/
```

```
SELECT DISTINCT p.ProductID, Name, OrderDate
FROM Production.Product p
INNER JOIN Sales.SalesOrderDetail od
ON p.ProductID = od.ProductID
INNER JOIN Sales.SalesOrderHeader oh
ON oh.SalesOrderID = od.SalesOrderID
WHERE DATEPART(YEAR, OrderDate) = 2008;
```

### -- Exercise 6 Solution

```
/* What is the name and average rating for the product with  
ProductID = 937? */
```

```
select pdt.name, avg(pr.rating) as rating  
from Production.Product pdt  
join Production.ProductReview pr  
    on pdt.ProductID = pr.ProductID  
where pr.ProductID = 937  
group by pdt.Name;
```

### -- Exercise 7 Solution

```
/* Use the SubTotal value in SalesOrderHeader to calculate  
total value. What is the total value of products sold to  
an address in 'Seattle'? */
```

```
select ad.city, sum(SubTotal) as total_value  
from Sales.SalesOrderHeader soh  
join Person.Address ad on soh.ShipToAddressID = ad.AddressID  
where ad.city = 'Seattle'  
group by ad.city;
```