Let me continue with more pages:

Products.js

```
/app/frontend/src/pages/Products.js
```

```
import React, { useState, useEffect } from 'react';
import axios from 'axios';
import { Link } from 'react-router-dom';
import { Search, Filter } from 'lucide-react';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { toast } from 'sonner';

const BACKEND_URL = process.env.REACT_APP_BACKEND_URL;
const API = `${BACKEND_URL}/api`;

const Products = () => {
  const [products, setProducts] = useState([]);
  const [filteredProducts, setFilteredProducts] = useState([]);
  const [loading, setLoading] = useState(true);
  const [searchTerm, setSearchTerm] = useState('');
  const [selectedCategory, setSelectedCategory] = useState('All');
  const categories = ['All', 'Coffee', 'Tea', 'Pastry'];

  useEffect(() => {
    fetchProducts();
  }, []);

  useEffect(() => {
    filterProducts();
  }, [searchTerm, selectedCategory, products]);

  const fetchProducts = async () => {
    try {
      const response = await axios.get(`${API}/products`);
      setProducts(response.data);
      setFilteredProducts(response.data);
    } catch (error) {
      toast.error('Failed to load products');
    } finally {
      setLoading(false);
    }
  };

  const filterProducts = () => {
    let filtered = products;
```

```
    if (selectedCategory !== 'All') {
      filtered = filtered.filter(p => p.category === selectedCategory);
    }

    if (searchTerm) {
      filtered = filtered.filter(p =>
        p.name.toLowerCase().includes(searchTerm.toLowerCase()) ||
        p.description.toLowerCase().includes(searchTerm.toLowerCase())
      );
    }

    setFilteredProducts(filtered);
  };

  if (loading) {
    return (
      <div className="min-h-screen bg-[#FAF8F5] flex items-center justify-
center">
        <p className="text-[#6C5F5B]">Loading products...</p>
      </div>
    );
  }

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-12">
      <div className="container mx-auto px-6 md:px-12">
        <div className="mb-12">
          <h1 className="text-4xl sm:text-5xl font-medium text-[#2C1E16] mb-
4" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-testid="products-
heading">
            Our Menu
          </h1>
          <p className="text-lg text-[#6C5F5B]">
            Discover our selection of premium coffees, teas, and pastries
          </p>
        </div>

        {/* Search and Filter */}
        <div className="mb-8 flex flex-col md:flex-row gap-4">
          <div className="relative flex-1">
            <Search className="absolute left-4 top-1/2 transform -translate-
y-1/2 text-[#6C5F5B] w-5 h-5" />
            <Input
              type="text"
              placeholder="Search products..."
              value={searchTerm}
              onChange={(e) => setSearchTerm(e.target.value)}
```

```
              className="pl-12 w-full bg-white border border-[#EAE4DC]
rounded-xl px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47]
focus:border-transparent"
              data-testid="search-input"
            />
          </div>

          <div className="flex gap-2">
            {categories.map(cat => (
              <Button
                key={cat}
                onClick={() => setSelectedCategory(cat)}
                className={`px-6 py-3 rounded-full font-medium transition-all
${
                  selectedCategory === cat
                    ? 'bg-[#C05E47] hover:bg-[#A64B36] text-white'
                    : 'bg-white hover:bg-[#F3EFE9] text-[#2C1E16] border
border-[#EAE4DC]'
                }`}
                data-testid={`filter-${cat.toLowerCase()}`}
              >
                {cat}
              </Button>
            ))}
          </div>
        </div>

        {/* Products Grid */}
        <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-
8">
          {filteredProducts.map(product => (
            <Link
              key={product.id}
              to={`/products/${product.id}`}
              className="bg-white rounded-2xl overflow-hidden shadow-
[0_4px_24px_rgba(44,30,22,0.04)] hover:shadow-
[0_12px_48px_rgba(44,30,22,0.12)] transition-all duration-300 hover:-
translate-y-1 group"
              data-testid={`product-card-${product.id}`}
            >
              <div className="aspect-square overflow-hidden bg-[#F3EFE9]">
                <img
                  src={product.imageUrl}
                  alt={product.name}
                  className="w-full h-full object-cover group-hover:scale-105
transition-transform duration-700"
                />
              </div>
```

```
              <div className="p-6">
                <div className="mb-2">
                  <span className="text-xs font-bold uppercase tracking-
[0.2em] text-[#C05E47]">
                    {product.category}
                  </span>
                </div>
                <h3 className="text-2xl font-medium text-[#2C1E16] mb-2"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                  {product.name}
                </h3>
                <p className="text-sm text-[#6C5F5B] mb-4 line-clamp-2">
                  {product.description}
                </p>
                <div className="flex items-center justify-between">
                  <span className="text-2xl font-medium text-[#2C1E16]"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                    ₹{product.price}
                  </span>
                  <span className="text-sm text-[#6C5F5B]">
                    {product.quantity > 0 ? `${product.quantity} in stock` :
'Out of stock'}
                  </span>
                </div>
              </div>
            </Link>
          ))}
        </div>

        {filteredProducts.length === 0 && (
          <div className="text-center py-20">
            <p className="text-[#6C5F5B] text-lg">No products found</p>
          </div>
        )}
      </div>
    </div>
  );
};

export default Products;
```

ProductDetail.js

/app/frontend/src/pages/ProductDetail.js

```
import React, { useState, useEffect } from 'react';
import { useParams, useNavigate } from 'react-router-dom';
import axios from 'axios';
import { useAuth } from '../context/AuthContext';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { Label } from '../components/ui/label';
import { Textarea } from '../components/ui/textarea';
import { ShoppingBag, Package } from 'lucide-react';
import { toast } from 'sonner';

const BACKEND_URL = process.env.REACT_APP_BACKEND_URL;
const API = `${BACKEND_URL}/api`;

const ProductDetail = () => {
  const { id } = useParams();
  const { user, getAuthHeaders } = useAuth();
  const navigate = useNavigate();
  const [product, setProduct] = useState(null);
  const [loading, setLoading] = useState(true);
  const [quantity, setQuantity] = useState(1);
  const [deliveryAddress, setDeliveryAddress] = useState('');
  const [specialNotes, setSpecialNotes] = useState('');
  const [submitting, setSubmitting] = useState(false);

  useEffect(() => {
    fetchProduct();
  }, [id]);

  useEffect(() => {
    if (user && user.address) {
      setDeliveryAddress(user.address);
    }
  }, [user]);

  const fetchProduct = async () => {
    try {
      const response = await axios.get(`${API}/products/${id}`);
      setProduct(response.data);
    } catch (error) {
      toast.error('Product not found');
```

```
      navigate('/products');
    } finally {
      setLoading(false);
    }
  };

  const handleOrder = async () => {
    if (!user) {
      toast.error('Please login to place an order');
      navigate('/login');
      return;
    }

    if (!deliveryAddress.trim()) {
      toast.error('Please enter a delivery address');
      return;
    }

    if (quantity < 1 || quantity > product.quantity) {
      toast.error(`Please enter a quantity between 1 and
${product.quantity}`);
      return;
    }

    setSubmitting(true);
    try {
      const orderData = {
        items: [{ productId: product.id, quantity }],
        deliveryAddress,
        specialNotes
      };

      const response = await axios.post(`${API}/orders`, orderData, {
        headers: getAuthHeaders()
      });

      toast.success('Order placed successfully!');
      navigate(`/invoice/${response.data.id}`);
    } catch (error) {
      toast.error(error.response?.data?.detail || 'Failed to place order');
    } finally {
      setSubmitting(false);
    }
  };

  if (loading) {
    return (
```

```
      <div className="min-h-screen bg-[#FAF8F5] flex items-center justify-
center">
        <p className="text-[#6C5F5B]">Loading product...</p>
      </div>
    );
  }

  if (!product) return null;

  const subTotal = product.price * quantity;
  const tax = subTotal * 0.05;
  const deliveryCharge = 50;
  const total = subTotal + tax + deliveryCharge;

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-12">
      <div className="container mx-auto px-6 md:px-12">
        <div className="grid grid-cols-1 md:grid-cols-2 gap-12">
          {/* Product Image */}
          <div className="bg-white rounded-2xl overflow-hidden shadow-lg">
            <div className="aspect-square">
              <img
                src={product.imageUrl}
                alt={product.name}
                className="w-full h-full object-cover"
              />
            </div>
          </div>

          {/* Product Details & Order Form */}
          <div>
            <div className="mb-8">
              <span className="text-xs font-bold uppercase tracking-[0.2em]
text-[#C05E47] mb-2 block">
                {product.category}
              </span>
              <h1 className="text-4xl sm:text-5xl font-medium text-[#2C1E16]
mb-4" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-
testid="product-name">
                {product.name}
              </h1>
              <p className="text-lg text-[#6C5F5B] mb-6">
                {product.description}
              </p>
              <div className="flex items-center gap-4 mb-6">
                <span className="text-3xl font-medium text-[#2C1E16]"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                  ₹{product.price}
```

```
                </span>
                <div className="flex items-center gap-2 text-[#6C5F5B]">
                  <Package className="w-5 h-5" />
                  <span>{product.quantity} in stock</span>
                </div>
              </div>
            </div>

            {/* Order Form */}
            <div className="bg-white rounded-2xl shadow-lg p-6 space-y-6">
              <h2 className="text-2xl font-medium text-[#2C1E16]" style={{
fontFamily: 'Cormorant Garamond, serif' }}>
                Place Your Order
              </h2>

              <div>
                <Label htmlFor="quantity" className="text-[#2C1E16] mb-2
block">Quantity</Label>
                <Input
                  id="quantity"
                  type="number"
                  min="1"
                  max={product.quantity}
                  value={quantity}
                  onChange={(e) => setQuantity(parseInt(e.target.value) ||
1)}
                  className="w-full bg-white border border-[#EAE4DC] rounded-
xl px-4 py-3"
                  data-testid="quantity-input"
                />
              </div>

              <div>
                <Label htmlFor="address" className="text-[#2C1E16] mb-2
block">Delivery Address *</Label>
                <Textarea
                  id="address"
                  value={deliveryAddress}
                  onChange={(e) => setDeliveryAddress(e.target.value)}
                  className="w-full bg-white border border-[#EAE4DC] rounded-
xl px-4 py-3 min-h-[80px]"
                  placeholder="Enter your delivery address"
                  data-testid="address-input"
                />
              </div>

              <div>
```

```
                <Label htmlFor="notes" className="text-[#2C1E16] mb-2
block">Special Notes (Optional)</Label>
                <Textarea
                  id="notes"
                  value={specialNotes}
                  onChange={(e) => setSpecialNotes(e.target.value)}
                  className="w-full bg-white border border-[#EAE4DC] rounded-
xl px-4 py-3 min-h-[80px]"
                  placeholder="Any special requests?"
                  data-testid="notes-input"
                />
              </div>

              {/* Order Summary */}
              <div className="border-t border-[#EAE4DC] pt-4 space-y-2">
                <div className="flex justify-between text-[#6C5F5B]">
                  <span>Subtotal</span>
                  <span>₹{subTotal.toFixed(2)}</span>
                </div>
                <div className="flex justify-between text-[#6C5F5B]">
                  <span>Tax (5%)</span>
                  <span>₹{tax.toFixed(2)}</span>
                </div>
                <div className="flex justify-between text-[#6C5F5B]">
                  <span>Delivery Charge</span>
                  <span>₹{deliveryCharge.toFixed(2)}</span>
                </div>
                <div className="flex justify-between text-xl font-medium
text-[#2C1E16] pt-2 border-t border-[#EAE4DC]">
                  <span>Total</span>
                  <span>₹{total.toFixed(2)}</span>
                </div>
              </div>

              <Button
                onClick={handleOrder}
                disabled={submitting || product.quantity < 1}
                className="w-full bg-[#C05E47] hover:bg-[#A64B36] text-white
py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg"
                data-testid="place-order-button"
              >
                <ShoppingBag className="w-5 h-5 mr-2" />
                {submitting ? 'Placing Order...' : 'Place Order'}
              </Button>
            </div>
          </div>
        </div>
      </div>
```

```
    </div>
  );
};

export default ProductDetail;
```

Now let me create the remaining pages:

Orders.js

/app/frontend/src/pages/Orders.js

```
import React, { useState, useEffect } from 'react';
import axios from 'axios';
import { Link } from 'react-router-dom';
import { useAuth } from '../context/AuthContext';
import { Package, Calendar, MapPin, X } from 'lucide-react';
import { Button } from '../components/ui/button';
import { toast } from 'sonner';

const BACKEND_URL = process.env.REACT_APP_BACKEND_URL;
const API = `${BACKEND_URL}/api`;

const Orders = () => {
  const { getAuthHeaders } = useAuth();
  const [orders, setOrders] = useState([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    fetchOrders();
  }, []);

  const fetchOrders = async () => {
    try {
      const response = await axios.get(`${API}/orders`, {
        headers: getAuthHeaders()
      });
      setOrders(response.data);
    } catch (error) {
      toast.error('Failed to load orders');
    } finally {
      setLoading(false);
    }
  };
```

```
  const cancelOrder = async (orderId) => {
    try {
      await axios.delete(`${API}/orders/${orderId}`, {
        headers: getAuthHeaders()
      });
      toast.success('Order cancelled successfully');
      fetchOrders();
    } catch (error) {
      toast.error(error.response?.data?.detail || 'Failed to cancel order');
    }
  };

  if (loading) {
    return (
      <div className="min-h-screen bg-[#FAF8F5] flex items-center justify-
center">
        <p className="text-[#6C5F5B]">Loading orders...</p>
      </div>
    );
  }

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-12">
      <div className="container mx-auto px-6 md:px-12">
        <div className="mb-12">
          <h1 className="text-4xl sm:text-5xl font-medium text-[#2C1E16] mb-
4" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-testid="orders-
heading">
            My Orders
          </h1>
          <p className="text-lg text-[#6C5F5B]">
            Track and manage your orders
          </p>
        </div>

        {orders.length === 0 ? (
          <div className="text-center py-20 bg-white rounded-2xl">
            <Package className="w-16 h-16 text-[#EAE4DC] mx-auto mb-4" />
            <p className="text-[#6C5F5B] text-lg mb-6">No orders yet</p>
            <Link to="/products">
              <Button className="bg-[#C05E47] hover:bg-[#A64B36] text-white
px-8 py-3 rounded-full" data-testid="browse-products-button">
                Browse Products
              </Button>
            </Link>
          </div>
        ) : (
          <div className="space-y-6">
```

```
            {orders.map(order => (
              <div key={order.id} className="bg-white rounded-2xl shadow-lg
overflow-hidden" data-testid={`order-card-${order.id}`}>
                <div className="p-6">
                  <div className="flex flex-col md:flex-row md:items-center
justify-between mb-4">
                    <div>
                      <h3 className="text-xl font-medium text-[#2C1E16] mb-1"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                        Order #{order.id.slice(0, 8)}
                      </h3>
                      <div className="flex items-center gap-2 text-sm text-
[#6C5F5B]">
                        <Calendar className="w-4 h-4" />
                        {new Date(order.orderDate).toLocaleDateString('en-
IN', {
                          year: 'numeric',
                          month: 'long',
                          day: 'numeric'
                        })}
                      </div>
                    </div>
                    <div className="flex items-center gap-4 mt-4 md:mt-0">
                      <span className={`px-4 py-2 rounded-full text-sm font-
medium ${
                        order.status === 'Pending' ? 'bg-yellow-100 text-
yellow-800' :
                        order.status === 'Paid' ? 'bg-green-100 text-green-
800' :
                        'bg-red-100 text-red-800'
                      }`}>
                        {order.status}
                      </span>
                    </div>
                  </div>

                  <div className="border-t border-[#EAE4DC] pt-4 mb-4">
                    <div className="space-y-3">
                      {order.items.map(item => (
                        <div key={item.id} className="flex justify-between">
                          <span className="text-[#6C5F5B]">
                            {item.productName} x {item.quantity}
                          </span>
                          <span className="text-[#2C1E16] font-medium">
                            ₹{item.lineTotal.toFixed(2)}
                          </span>
                        </div>
                      ))}
```

```
                    </div>
                  </div>

                  <div className="flex items-start gap-2 text-sm text-
[#6C5F5B] mb-4">
                    <MapPin className="w-4 h-4 mt-1 flex-shrink-0" />
                    <span>{order.deliveryAddress}</span>
                  </div>

                  {order.specialNotes && (
                    <div className="text-sm text-[#6C5F5B] mb-4">
                      <strong>Notes:</strong> {order.specialNotes}
                    </div>
                  )}

                  <div className="border-t border-[#EAE4DC] pt-4 flex flex-
col md:flex-row justify-between items-center gap-4">
                    <div className="text-2xl font-medium text-[#2C1E16]"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                      Total: ₹{order.totalAmount.toFixed(2)}
                    </div>
                    <div className="flex gap-3">
                      <Link to={`/invoice/${order.id}`}>
                        <Button className="bg-[#F3EFE9] hover:bg-[#EAE4DC]
text-[#2C1E16] px-6 py-2 rounded-full" data-testid={`view-invoice-button-
${order.id}`}>
                          View Invoice
                        </Button>
                      </Link>
                      {order.status === 'Pending' && (
                        <Button
                          onClick={() => cancelOrder(order.id)}
                          className="bg-red-50 hover:bg-red-100 text-red-600
px-6 py-2 rounded-full"
                          data-testid={`cancel-order-button-${order.id}`}
                        >
                          <X className="w-4 h-4 mr-2" />
                          Cancel
                        </Button>
                      )}
                    </div>
                  </div>
                </div>
              </div>
            ))}
          </div>
        )}
      </div>
```

```
    </div>
  );
};

export default Orders;
```

Invoice.js

```
import React, { useState, useEffect } from 'react';
import { useParams, useNavigate } from 'react-router-dom';
import axios from 'axios';
import { useAuth } from '../context/AuthContext';
import { Button } from '../components/ui/button';
import { Label } from '../components/ui/label';
import { Printer, CreditCard, Banknote } from 'lucide-react';
import { toast } from 'sonner';

const BACKEND_URL = process.env.REACT_APP_BACKEND_URL;
const API = `${BACKEND_URL}/api`;

const Invoice = () => {
  const { orderId } = useParams();
  const { getAuthHeaders } = useAuth();
  const navigate = useNavigate();
  const [order, setOrder] = useState(null);
  const [bill, setBill] = useState(null);
  const [loading, setLoading] = useState(true);
  const [paymentMethod, setPaymentMethod] = useState('Card');
  const [processing, setProcessing] = useState(false);

  useEffect(() => {
    fetchOrderAndBill();
  }, [orderId]);

  const fetchOrderAndBill = async () => {
    try {
      const [orderRes, billRes] = await Promise.all([
        axios.get(`${API}/orders/${orderId}`, { headers: getAuthHeaders() }),
        axios.get(`${API}/bills/${orderId}`, { headers: getAuthHeaders() })
      ]);
      setOrder(orderRes.data);
      setBill(billRes.data);
    } catch (error) {
```

```
      toast.error('Failed to load invoice');
      navigate('/orders');
    } finally {
      setLoading(false);
    }
  };

  const handlePayment = async () => {
    setProcessing(true);
    try {
      await axios.post(`${API}/bills/${orderId}/pay`,
        { paymentMethod },
        { headers: getAuthHeaders() }
      );
      toast.success('Payment successful!');
      fetchOrderAndBill();
    } catch (error) {
      toast.error(error.response?.data?.detail || 'Payment failed');
    } finally {
      setProcessing(false);
    }
  };

  const handlePrint = () => {
    window.print();
  };

  if (loading) {
    return (
      <div className="min-h-screen bg-[#FAF8F5] flex items-center justify-
center">
        <p className="text-[#6C5F5B]">Loading invoice...</p>
      </div>
    );
  }

  if (!order || !bill) return null;

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-12">
      <div className="container mx-auto px-6 md:px-12 max-w-4xl">
        <div className="bg-white rounded-2xl shadow-lg p-8 md:p-12">
          {/* Invoice Header */}
          <div className="border-b border-[#EAE4DC] pb-6 mb-6">
            <div className="flex justify-between items-start mb-4">
              <div>
```

```
                <h1 className="text-4xl font-medium text-[#2C1E16] mb-2"
style={{ fontFamily: 'Cormorant Garamond, serif' }} data-testid="invoice-
heading">
                  Invoice
                </h1>
                <p className="text-[#6C5F5B]">Order #{order.id.slice(0,
8)}</p>
              </div>
              <div className="text-right">
                <p className="text-[#6C5F5B] text-sm">Date</p>
                <p className="text-[#2C1E16] font-medium">
                  {new Date(bill.billDate).toLocaleDateString('en-IN')}
                </p>
              </div>
            </div>

            {bill.paymentStatus === 'Completed' && (
              <div className="bg-green-50 border border-green-200 rounded-lg
p-4">
                <p className="text-green-800 font-medium">Payment
Completed</p>
                <p className="text-green-600 text-sm">Transaction ID:
{bill.transactionId}</p>
                <p className="text-green-600 text-sm">Payment Method:
{bill.paymentMethod}</p>
              </div>
            )}
          </div>

          {/* Delivery Address */}
          <div className="mb-6">
            <h3 className="text-lg font-medium text-[#2C1E16] mb-2">Delivery
Address</h3>
            <p className="text-[#6C5F5B]">{order.deliveryAddress}</p>
          </div>

          {/* Order Items */}
          <div className="mb-6">
            <h3 className="text-lg font-medium text-[#2C1E16] mb-4">Order
Items</h3>
            <div className="space-y-3">
              {order.items.map(item => (
                <div key={item.id} className="flex justify-between py-3
border-b border-[#EAE4DC]">
                  <div>
                    <p className="text-[#2C1E16] font-
medium">{item.productName}</p>
```

```
                    <p className="text-sm text-[#6C5F5B]">Quantity:
{item.quantity} × ₹{item.unitPrice.toFixed(2)}</p>
                  </div>
                  <p className="text-[#2C1E16] font-
medium">₹{item.lineTotal.toFixed(2)}</p>
                </div>
              ))}
            </div>
          </div>

          {/* Bill Summary */}
          <div className="bg-[#FAF8F5] rounded-xl p-6 mb-6">
            <div className="space-y-3">
              <div className="flex justify-between text-[#6C5F5B]">
                <span>Subtotal</span>
                <span>₹{bill.subTotal.toFixed(2)}</span>
              </div>
              <div className="flex justify-between text-[#6C5F5B]">
                <span>Tax (5%)</span>
                <span>₹{bill.tax.toFixed(2)}</span>
              </div>
              <div className="flex justify-between text-[#6C5F5B]">
                <span>Delivery Charge</span>
                <span>₹50.00</span>
              </div>
              {bill.discount > 0 && (
                <div className="flex justify-between text-green-600">
                  <span>Discount</span>
                  <span>-₹{bill.discount.toFixed(2)}</span>
                </div>
              )}
              <div className="border-t border-[#EAE4DC] pt-3 flex justify-
between text-xl font-medium text-[#2C1E16]">
                <span>Total Amount</span>
                <span>₹{bill.totalAmount.toFixed(2)}</span>
              </div>
            </div>
          </div>

          {/* Payment Section */}
          {bill.paymentStatus === 'Pending' && (
            <div className="border-t border-[#EAE4DC] pt-6">
              <h3 className="text-lg font-medium text-[#2C1E16] mb-4">Payment
Method</h3>
              <div className="grid grid-cols-2 md:grid-cols-4 gap-3 mb-6">
                {['Card', 'Cash', 'Online', 'Cheque'].map(method => (
                  <button
                    key={method}
```

```
                    onClick={() => setPaymentMethod(method)}
                    className={`p-4 border-2 rounded-xl transition-all ${
                      paymentMethod === method
                        ? 'border-[#C05E47] bg-[#C05E47]/5'
                        : 'border-[#EAE4DC] hover:border-[#C05E47]/50'
                    }`}
                    data-testid={`payment-method-${method.toLowerCase()}`}
                  >
                    <div className="flex flex-col items-center gap-2">
                      {method === 'Card' && <CreditCard className="w-6 h-6
text-[#C05E47]" />}
                      {method === 'Cash' && <Banknote className="w-6 h-6
text-[#C05E47]" />}
                      {method === 'Online' && <CreditCard className="w-6 h-6
text-[#C05E47]" />}
                      {method === 'Cheque' && <Banknote className="w-6 h-6
text-[#C05E47]" />}
                      <span className="text-sm font-medium text-
[#2C1E16]">{method}</span>
                    </div>
                  </button>
                ))}
              </div>
              <Button
                onClick={handlePayment}
                disabled={processing}
                className="w-full bg-[#C05E47] hover:bg-[#A64B36] text-white
py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg"
                data-testid="pay-now-button"
              >
                {processing ? 'Processing...' : `Pay Now -
₹${bill.totalAmount.toFixed(2)}`}
              </Button>
            </div>
          )}

          {/* Action Buttons */}
          <div className="flex gap-4 mt-6 print:hidden">
            <Button
              onClick={handlePrint}
              className="flex-1 bg-[#F3EFE9] hover:bg-[#EAE4DC] text-
[#2C1E16] py-3 rounded-full"
              data-testid="print-invoice-button"
            >
              <Printer className="w-4 h-4 mr-2" />
              Print Invoice
            </Button>
            <Button
```

```
              onClick={() => navigate('/orders')}
              className="flex-1 bg-[#F3EFE9] hover:bg-[#EAE4DC] text-
[#2C1E16] py-3 rounded-full"
              data-testid="back-to-orders-button"
            >
              Back to Orders
            </Button>
          </div>
        </div>
      </div>
    </div>
  );
};

export default Invoice;
```

Profile.js

/app/frontend/src/pages/Profile.js

```
import React, { useState, useEffect } from 'react';
import { useAuth } from '../context/AuthContext';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { Label } from '../components/ui/label';
import axios from 'axios';
import { toast } from 'sonner';
import { User, Mail, Phone, MapPin } from 'lucide-react';

const BACKEND_URL = process.env.REACT_APP_BACKEND_URL;
const API = `${BACKEND_URL}/api`;

const Profile = () => {
  const { user, getAuthHeaders } = useAuth();
  const [formData, setFormData] = useState({
    name: '',
    contactNo: '',
    address: ''
  });
  const [loading, setLoading] = useState(false);

  useEffect(() => {
    if (user) {
      setFormData({
```

```
        name: user.name || '',
        contactNo: user.contactNo || '',
        address: user.address || ''
      });
    }
  }, [user]);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    try {
      await axios.put(
        `${API}/auth/profile`,
        formData,
        {
          headers: getAuthHeaders(),
          params: formData
        }
      );
      toast.success('Profile updated successfully');
      window.location.reload();
    } catch (error) {
      toast.error('Failed to update profile');
    } finally {
      setLoading(false);
    }
  };

  if (!user) return null;

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-12">
      <div className="container mx-auto px-6 md:px-12 max-w-2xl">
        <div className="mb-8">
          <h1 className="text-4xl sm:text-5xl font-medium text-[#2C1E16] mb-
4" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-testid="profile-
heading">
            My Profile
          </h1>
          <p className="text-lg text-[#6C5F5B]">
            Manage your account information
          </p>
        </div>

        <div className="bg-white rounded-2xl shadow-lg p-8">
          {/* Account Info */}
          <div className="mb-8 pb-6 border-b border-[#EAE4DC]">
            <div className="flex items-center gap-4 mb-6">
```

```
              <div className="w-16 h-16 bg-[#C05E47] rounded-full flex items-
center justify-center">
                <User className="w-8 h-8 text-white" />
              </div>
              <div>
                <h2 className="text-2xl font-medium text-[#2C1E16]" style={{
fontFamily: 'Cormorant Garamond, serif' }}>
                  {user.name}
                </h2>
                <p className="text-[#6C5F5B] flex items-center gap-2">
                  <Mail className="w-4 h-4" />
                  {user.email}
                </p>
              </div>
            </div>
            <p className="text-sm text-[#6C5F5B]">
              Member since {new
Date(user.createdDate).toLocaleDateString('en-IN', { year: 'numeric', month:
'long' })}
            </p>
          </div>

          {/* Update Form */}
          <form onSubmit={handleSubmit} className="space-y-6">
            <div>
              <Label htmlFor="name" className="text-[#2C1E16] mb-2
block">Full Name</Label>
              <Input
                id="name"
                type="text"
                value={formData.name}
                onChange={(e) => setFormData({ ...formData, name:
e.target.value })}
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3"
                data-testid="profile-name-input"
              />
            </div>

            <div>
              <Label htmlFor="contactNo" className="text-[#2C1E16] mb-2
block">Contact Number</Label>
              <div className="relative">
                <Phone className="absolute left-4 top-1/2 transform -
translate-y-1/2 text-[#6C5F5B] w-5 h-5" />
                <Input
                  id="contactNo"
                  type="tel"
```

```
                  value={formData.contactNo}
                  onChange={(e) => setFormData({ ...formData, contactNo:
e.target.value })}
                  className="w-full bg-white border border-[#EAE4DC] rounded-
xl pl-12 pr-4 py-3"
                  placeholder="9876543210"
                  data-testid="profile-contact-input"
                />
              </div>
            </div>

            <div>
              <Label htmlFor="address" className="text-[#2C1E16] mb-2
block">Address</Label>
              <div className="relative">
                <MapPin className="absolute left-4 top-4 text-[#6C5F5B] w-5
h-5" />
                <Input
                  id="address"
                  type="text"
                  value={formData.address}
                  onChange={(e) => setFormData({ ...formData, address:
e.target.value })}
                  className="w-full bg-white border border-[#EAE4DC] rounded-
xl pl-12 pr-4 py-3"
                  placeholder="123 Coffee Street, Hyderabad"
                  data-testid="profile-address-input"
                />
              </div>
            </div>

            <Button
              type="submit"
              disabled={loading}
              className="w-full bg-[#C05E47] hover:bg-[#A64B36] text-white
py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg"
              data-testid="update-profile-button"
            >
              {loading ? 'Updating...' : 'Update Profile'}
            </Button>
          </form>
        </div>
      </div>
    </div>
  );
};

export default Profile;
```

Now let me create the main App.js with routing and add missing UI components:

App.js

/app/frontend/src/App.js

```
import React from 'react';
import { BrowserRouter, Routes, Route, Navigate } from 'react-router-dom';
import { AuthProvider, useAuth } from './context/AuthContext';
import { Toaster } from './components/ui/sonner';
import Header from './components/Header';
import Home from './pages/Home';
import Login from './pages/Login';
import Register from './pages/Register';
import Products from './pages/Products';
import ProductDetail from './pages/ProductDetail';
import Orders from './pages/Orders';
import Invoice from './pages/Invoice';
import Profile from './pages/Profile';
import './App.css';

const ProtectedRoute = ({ children }) => {
  const { user, loading } = useAuth();

  if (loading) {
    return (
      <div className="min-h-screen bg-[#FAF8F5] flex items-center justify-
center">
        <p className="text-[#6C5F5B]">Loading...</p>
      </div>
    );
  }

  return user ? children : <Navigate to="/login" />;
};

function AppRoutes() {
  return (
    <div className="App min-h-screen bg-[#FAF8F5]">
      <Header />
      <Routes>
        <Route path="/" element={<Home />} />
        <Route path="/login" element={<Login />} />
        <Route path="/register" element={<Register />} />
        <Route path="/products" element={<Products />} />
        <Route path="/products/:id" element={<ProductDetail />} />
        <Route path="/orders" element={
          <ProtectedRoute>
            <Orders />
```

```
          </ProtectedRoute>
        } />
        <Route path="/invoice/:orderId" element={
          <ProtectedRoute>
            <Invoice />
          </ProtectedRoute>
        } />
        <Route path="/profile" element={
          <ProtectedRoute>
            <Profile />
          </ProtectedRoute>
        } />
      </Routes>
      <Toaster position="top-right" />
    </div>
  );
}

function App() {
  return (
    <AuthProvider>
      <BrowserRouter>
        <AppRoutes />
      </BrowserRouter>
    </AuthProvider>
  );
}

export default App;
```

App.css

/app/frontend/src/App.css

```
.App {
  min-height: 100vh;
}

@media print {
  .print\:hidden {
    display: none !important;
  }

  header {
    display: none !important;
```

```
  }

  body {
    background: white;
  }
}
```

textarea.js

/app/frontend/src/components/ui/textarea.js

```
import * as React from "react";

const Textarea = React.forwardRef(({ className, ...props }, ref) => {
  return (
    <textarea
      className={className}
      ref={ref}
      {...props}
    />
  );
});
Textarea.displayName = "Textarea";

export { Textarea };
```