Now let me create the main pages:

`Created3 files`

`/app/frontend/src/pages/Home.js`

```
import React from 'react';
import { Link } from 'react-router-dom';
import { Coffee, ShoppingBag, Star, Clock } from 'lucide-react';
import { Button } from '../components/ui/button';

const Home = () => {
  return (
    <div className="min-h-screen bg-[#FAF8F5]">
      {/* Hero Section */}
      <section className="relative py-20 md:py-32 overflow-hidden">
        <div className="absolute inset-0 z-0">
          <img
            src="https://static.prod-images.emergentagent.com/jobs/6b33f44a-
bec0-46cc-911b-
0cc652506e32/images/ec99bcff6769cc2a6435fe6a4d9f6a697cc5ad70c8deb97f0b4a2bb52
45a7d88.png"
            alt="Coffee background"
            className="w-full h-full object-cover opacity-10"
          />
        </div>
        <div className="container mx-auto px-6 md:px-12 relative z-10">
          <div className="max-w-3xl">
            <p className="text-xs font-bold uppercase tracking-[0.2em] text-
[#C05E47] mb-6" data-testid="hero-overline">
              Welcome to Our Coffee Shop
            </p>
            <h1 className="text-5xl sm:text-6xl font-medium tracking-tight
leading-none text-[#2C1E16] mb-6" style={{ fontFamily: 'Cormorant Garamond,
serif' }} data-testid="hero-heading">
              Artisan Coffee, Crafted with Passion
            </h1>
            <p className="text-lg text-[#6C5F5B] leading-relaxed mb-8 max-w-
2xl" data-testid="hero-description">
              Experience the finest selection of premium coffees, teas, and
freshly baked pastries.
              Order online and enjoy the warmth of our artisanal creations
delivered to your door.
            </p>
            <div className="flex flex-wrap gap-4">
              <Link to="/products" data-testid="hero-browse-button">
```

```
                <Button className="bg-[#C05E47] hover:bg-[#A64B36] text-white
px-8 py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg
hover:-translate-y-0.5">
                  Browse Menu
                </Button>
              </Link>
              <Link to="/register" data-testid="hero-signup-button">
                <Button className="bg-[#F3EFE9] hover:bg-[#EAE4DC] text-
[#2C1E16] px-8 py-6 rounded-full font-medium transition-all">
                  Sign Up
                </Button>
              </Link>
            </div>
          </div>
        </div>
      </section>

      {/* Features Section */}
      <section className="py-20 md:py-32 bg-white">
        <div className="container mx-auto px-6 md:px-12">
          <div className="text-center mb-16">
            <p className="text-xs font-bold uppercase tracking-[0.2em] text-
[#C05E47] mb-4">Why Choose Us</p>
            <h2 className="text-3xl sm:text-4xl font-medium tracking-tight
leading-snug text-[#2C1E16]" style={{ fontFamily: 'Cormorant Garamond, serif'
}}>
              Quality You Can Taste
            </h2>
          </div>

          <div className="grid grid-cols-1 md:grid-cols-3 gap-8">
            <div className="bg-[#FAF8F5] rounded-2xl p-8 text-center
transition-all hover:shadow-lg" data-testid="feature-card-quality">
              <div className="w-16 h-16 bg-[#C05E47] rounded-full flex items-
center justify-center mx-auto mb-6">
                <Coffee className="w-8 h-8 text-white" />
              </div>
              <h3 className="text-2xl font-medium text-[#2C1E16] mb-4"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                Premium Quality
              </h3>
              <p className="text-base text-[#6C5F5B] leading-relaxed">
                Sourced from the finest coffee beans and ingredients
worldwide
              </p>
            </div>
```

```
            <div className="bg-[#FAF8F5] rounded-2xl p-8 text-center
transition-all hover:shadow-lg" data-testid="feature-card-delivery">
              <div className="w-16 h-16 bg-[#C05E47] rounded-full flex items-
center justify-center mx-auto mb-6">
                <ShoppingBag className="w-8 h-8 text-white" />
              </div>
              <h3 className="text-2xl font-medium text-[#2C1E16] mb-4"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                Easy Ordering
              </h3>
              <p className="text-base text-[#6C5F5B] leading-relaxed">
                Simple online ordering with fast delivery to your doorstep
              </p>
            </div>

            <div className="bg-[#FAF8F5] rounded-2xl p-8 text-center
transition-all hover:shadow-lg" data-testid="feature-card-service">
              <div className="w-16 h-16 bg-[#C05E47] rounded-full flex items-
center justify-center mx-auto mb-6">
                <Star className="w-8 h-8 text-white" />
              </div>
              <h3 className="text-2xl font-medium text-[#2C1E16] mb-4"
style={{ fontFamily: 'Cormorant Garamond, serif' }}>
                Expert Service
              </h3>
              <p className="text-base text-[#6C5F5B] leading-relaxed">
                Crafted by experienced baristas who love what they do
              </p>
            </div>
          </div>
        </div>
      </section>

      {/* CTA Section */}
      <section className="py-20 md:py-32 bg-[#C05E47] text-white">
        <div className="container mx-auto px-6 md:px-12 text-center">
          <h2 className="text-3xl sm:text-4xl font-medium tracking-tight mb-
6" style={{ fontFamily: 'Cormorant Garamond, serif' }}>
            Ready to Experience Great Coffee?
          </h2>
          <p className="text-lg mb-8 opacity-90 max-w-2xl mx-auto">
            Join thousands of coffee lovers who trust us for their daily brew
          </p>
          <Link to="/products" data-testid="cta-order-button">
            <Button className="bg-white hover:bg-[#F3EFE9] text-[#C05E47] px-
8 py-6 rounded-full font-medium transition-all shadow-lg">
              Order Now
            </Button>
```

```
          </Link>
        </div>
      </section>
    </div>
  );
};

export default Home;
```

Register.js

/app/frontend/src/pages/Register.js

```
import React, { useState } from 'react';
import { useNavigate, Link } from 'react-router-dom';
import { useAuth } from '../context/AuthContext';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { Label } from '../components/ui/label';
import { toast } from 'sonner';

const Register = () => {
  const [formData, setFormData] = useState({
    name: '',
    email: '',
    password: '',
    contactNo: '',
    address: ''
  });
  const [loading, setLoading] = useState(false);
  const { register } = useAuth();
  const navigate = useNavigate();

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    try {
      await register(formData.name, formData.email, formData.password,
formData.contactNo, formData.address);
      toast.success('Registration successful!');
      navigate('/products');
    } catch (error) {
      toast.error(error.response?.data?.detail || 'Registration failed');
    } finally {
```

```
      setLoading(false);
    }
  };

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-20">
      <div className="container mx-auto px-6 md:px-12 max-w-md">
        <div className="bg-white rounded-2xl shadow-lg p-8">
          <h1 className="text-3xl font-medium text-[#2C1E16] mb-2 text-
center" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-
testid="register-heading">
            Create Account
          </h1>
          <p className="text-base text-[#6C5F5B] text-center mb-8">
            Join our coffee community
          </p>

          <form onSubmit={handleSubmit} className="space-y-6">
            <div>
              <Label htmlFor="name" className="text-[#2C1E16] mb-2
block">Full Name</Label>
              <Input
                id="name"
                type="text"
                value={formData.name}
                onChange={(e) => setFormData({ ...formData, name:
e.target.value })}
                required
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="John Doe"
                data-testid="register-name-input"
              />
            </div>

            <div>
              <Label htmlFor="email" className="text-[#2C1E16] mb-2
block">Email</Label>
              <Input
                id="email"
                type="email"
                value={formData.email}
                onChange={(e) => setFormData({ ...formData, email:
e.target.value })}
                required
```

```
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="you@example.com"
                data-testid="register-email-input"
              />
            </div>

            <div>
              <Label htmlFor="password" className="text-[#2C1E16] mb-2
block">Password</Label>
              <Input
                id="password"
                type="password"
                value={formData.password}
                onChange={(e) => setFormData({ ...formData, password:
e.target.value })}
                required
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="••••••••"
                data-testid="register-password-input"
              />
            </div>

            <div>
              <Label htmlFor="contactNo" className="text-[#2C1E16] mb-2
block">Contact Number (Optional)</Label>
              <Input
                id="contactNo"
                type="tel"
                value={formData.contactNo}
                onChange={(e) => setFormData({ ...formData, contactNo:
e.target.value })}
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="9876543210"
                data-testid="register-contact-input"
              />
            </div>

            <div>
              <Label htmlFor="address" className="text-[#2C1E16] mb-2
block">Address (Optional)</Label>
              <Input
                id="address"
```

```
                type="text"
                value={formData.address}
                onChange={(e) => setFormData({ ...formData, address:
e.target.value })}
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="123 Coffee Street"
                data-testid="register-address-input"
              />
            </div>

            <Button
              type="submit"
              disabled={loading}
              className="w-full bg-[#C05E47] hover:bg-[#A64B36] text-white
py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg"
              data-testid="register-submit-button"
            >
              {loading ? 'Creating Account...' : 'Sign Up'}
            </Button>
          </form>

          <p className="text-center text-[#6C5F5B] mt-6">
            Already have an account?{' '}
            <Link to="/login" className="text-[#C05E47] hover:underline font-
medium" data-testid="login-link">
              Login here
            </Link>
          </p>
        </div>
      </div>
    </div>
  );
};

export default Register;
```

Login.js

/app/frontend/src/pages/Login.js

```
import React, { useState } from 'react';
import { useNavigate, Link } from 'react-router-dom';
import { useAuth } from '../context/AuthContext';
import { Button } from '../components/ui/button';
import { Input } from '../components/ui/input';
import { Label } from '../components/ui/label';
import { toast } from 'sonner';

const Login = () => {
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [loading, setLoading] = useState(false);
  const { login } = useAuth();
  const navigate = useNavigate();

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    try {
      await login(email, password);
      toast.success('Login successful!');
      navigate('/products');
    } catch (error) {
      toast.error(error.response?.data?.detail || 'Login failed');
    } finally {
      setLoading(false);
    }
  };

  return (
    <div className="min-h-screen bg-[#FAF8F5] py-20">
      <div className="container mx-auto px-6 md:px-12 max-w-md">
        <div className="bg-white rounded-2xl shadow-lg p-8">
          <h1 className="text-3xl font-medium text-[#2C1E16] mb-2 text-
center" style={{ fontFamily: 'Cormorant Garamond, serif' }} data-
testid="login-heading">
            Welcome Back
          </h1>
          <p className="text-base text-[#6C5F5B] text-center mb-8">
            Login to your account
          </p>

          <form onSubmit={handleSubmit} className="space-y-6">
```

```
            <div>
              <Label htmlFor="email" className="text-[#2C1E16] mb-2
block">Email</Label>
              <Input
                id="email"
                type="email"
                value={email}
                onChange={(e) => setEmail(e.target.value)}
                required
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="you@example.com"
                data-testid="login-email-input"
              />
            </div>

            <div>
              <Label htmlFor="password" className="text-[#2C1E16] mb-2
block">Password</Label>
              <Input
                id="password"
                type="password"
                value={password}
                onChange={(e) => setPassword(e.target.value)}
                required
                className="w-full bg-white border border-[#EAE4DC] rounded-xl
px-4 py-3 text-[#2C1E16] focus:ring-2 focus:ring-[#C05E47] focus:border-
transparent outline-none transition-all"
                placeholder="••••••••"
                data-testid="login-password-input"
              />
            </div>

            <Button
              type="submit"
              disabled={loading}
              className="w-full bg-[#C05E47] hover:bg-[#A64B36] text-white
py-6 rounded-full font-medium transition-all shadow-md hover:shadow-lg"
              data-testid="login-submit-button"
            >
              {loading ? 'Logging in...' : 'Login'}
            </Button>
          </form>

          <p className="text-center text-[#6C5F5B] mt-6">
            Don't have an account?{' '}
```

```
            <Link to="/register" className="text-[#C05E47] hover:underline
font-medium" data-testid="register-link">
              Sign up here
            </Link>
          </p>
        </div>
      </div>
    </div>
  );
};

export default Login;
```