

Flight and pilot table :

```
mysql> desc flight1;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| f_id  | int(50)       | YES  |     | NULL    |       |
| src   | varchar(50)   | YES  |     | NULL    |       |
| dest  | varchar(50)   | YES  |     | NULL    |       |
| arri_date | date        | YES  |     | NULL    |       |
| arr_time | varchar(50)  | YES  |     | NULL    |       |
| dept_date | date        | YES  |     | NULL    |       |
| dept_time | varchar(50)  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)

mysql> desc pilot1;
ERROR 1146 (42S02): Table 'prince.pilot1' doesn't exist
mysql> desc pilot1;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| f_id  | int(50)       | YES  |     | NULL    |       |
| p_id  | int(50)       | YES  |     | NULL    |       |
| p_name | varchar(50)   | YES  |     | NULL    |       |
| p_age | int(50)       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.01 sec)
```

Values of flight and pilot table:

```
mysql> SELECT * FROM pilot1;
+-----+-----+-----+-----+
| f_id | p_id | p_name | p_age |
+-----+-----+-----+-----+
| 101  | 0    | P      | 10    |
| 102  | 1    | I      | 10    |
| 103  | 2    | L      | 10    |
| 106  | 3    | O      | 10    |
| 107  | 4    | T      | 10    |
| 108  | 5    | E      | 10    |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> SELECT * FROM flight1;
+-----+-----+-----+-----+-----+-----+-----+
| f_id | src | dest | arri_date | arr_time | dept_date | dept_time |
+-----+-----+-----+-----+-----+-----+-----+
| 101  | A   | X    | 2001-02-02 | 2:00    | 2002-02-03 | 3:00    |
| 102  | B   | Y    | 2001-02-02 | 2:00    | 2002-02-03 | 3:00    |
| 103  | C   | Z    | 2001-02-02 | 2:00    | 2002-02-03 | 3:00    |
| 104  | D   | P    | 2001-02-02 | 2:00    | 2002-02-03 | 3:00    |
| 105  | E   | Q    | 2001-02-02 | 2:00    | 2002-02-03 | 3:00    |
+-----+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

IN :

```
mysql> select f_id,dest from flight1
-> where f_id in (select f_id from flight1);
+-----+-----+
| f_id | dest |
+-----+-----+
| 101  | X    |
| 102  | Y    |
| 103  | Z    |
| 104  | P    |
| 105  | Q    |
+-----+-----+
5 rows in set (0.00 sec)
```

NOT IN :

```
mysql> select f_id,dest from flight1 where f_id not in (select f_id from pilot1);
+-----+-----+
| f_id | dest |
+-----+-----+
| 104  | P    |
| 105  | Q    |
+-----+-----+
2 rows in set (0.00 sec)
```

ALL:

```
ERROR 1054 (42S22): Unknown column 'f_name' in 'where clause'
mysql> select * from flight1 where dest="Z" and f_id>all (select p_age from pilot1 where p_name="O");
+-----+-----+-----+-----+-----+-----+-----+
| f_id | src | dest | arri_date | arr_time | dept_date | dept_time |
+-----+-----+-----+-----+-----+-----+-----+
| 103 | C | Z | 2001-02-02 | 2:00 | 2002-02-03 | 3:00 |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

ANY :

```
mysql> select * from flight1 where dest="Z" and f_id>any (select p_age from pilot1 where p_name="O");
+-----+-----+-----+-----+-----+-----+-----+
| f_id | src | dest | arri_date | arr_time | dept_date | dept_time |
+-----+-----+-----+-----+-----+-----+-----+
| 103 | C | Z | 2001-02-02 | 2:00 | 2002-02-03 | 3:00 |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

CO -RELATED NESTED QUERIES :

```
ERROR 1054 (42S22): Unknown column 'flight1' in 'field list'
mysql> select * from flight1 where f_id>(select avg(f_id) from pilot1);
+-----+-----+-----+-----+-----+-----+-----+
| f_id | src | dest | arri_date | arr_time | dept_date | dept_time |
+-----+-----+-----+-----+-----+-----+-----+
| 105 | E | Q | 2001-02-02 | 2:00 | 2002-02-03 | 3:00 |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```