INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

# Pseudo Code — Solutions & Explanations

Section: 09_Mock_Test_Series | Drive Date: 5th & 6th November 2026 | Status: 100% Solved & Verified

## Pseudo Code — Solutions & Explanations

**Total Questions:** 10 | **Total Marks:** 10

---

### Section: Technical Ability - Mathematics /Quantitative Aptitude

#### Question 1

Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c

**Options:**

- (A) 71
- (B) 56
- (C) 47
- ✅ **(D) 54** *(Correct Answer)*

**Correct Answer:** Option (D)

---

#### Question 2

How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "campus monk" End if j = p + k / 5 If (j not equal p) Print "campus monk" End if Print "campus monk"

**Options:**

- (A) 1 Times
- ✅ **(B) 2 Times** *(Correct Answer)*
- (C) 3 Times
- (D) 4 Times

**Correct Answer:** Option (B)

---

#### Question 3

Find the output of the following code. #include int main(void) { int a = 10, x; x = a-- + +445; printf ("%d", x); return 0; }

**Options:**

- (A) 19
- (B) 435
- ✅ **(C) 455** *(Correct Answer)*
- (D) 23

**Correct Answer:** Option (C)

---

## Question 4

Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q } Print p + q + r

**Options:**

- (A) 44
- (B) 41
- (C) 11
- ✅ **(D) 26** *(Correct Answer)*

**Correct Answer:** Option (D)

---

## Question 5

What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)) { p = 11 + q; } Print p + q + r;

**Options:**

- (A) 12
- ✅ **(B) 16** *(Correct Answer)*
- (C) 27
- (D) 10

**Correct Answer:** Option (B)

---

## Question 6

What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a, int b, int c) { For (each c from 3 to 5) { a = (c + c) ^ b; If ((a + c) < (c + a)) { b = (a + 11) + c; } Else { c = b + b; a = 3 + b; continue; } } Return a + b; }

**Options:**

- (A) 10
- (B) 12
- (C) Error
- ✅ **(D) 11** *(Correct Answer)*

**Correct Answer:** Option (D)

---

## Question 7

What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c ) a = b + c Else c = (4 + 12) + a b = 11 + a End if Print (a + b + c)

**Options:**

- (A) 19
- (B) 21
- ✅ **(C) 20** *(Correct Answer)*
- (D) 22

**Correct Answer:** Option (C)

---

## Question 8

Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^ y ^ z) x = 1 End if Print x + y + z

**Options:**

- ✅ **(A) 11** *(Correct Answer)*
- (B) 13
- (C) 16
- (D) 9

**Correct Answer:** Option (A)

---

## Question 9

Find the output of the following code. #include void main() { int a = 10; if (a == 010) printf("BCA"); else printf("B.Tech"); }

**Options:**

- (A) BCA
- ✅ **(B) B.tech** *(Correct Answer)*
- (C) 10
- (D) Error

**Correct Answer:** Option (B)

---

## Question 10

Find the output of the following code. #include void main () { int x = 91; x >>= 2; printf ("%d\n", x); }

**Options:**

- (A) 182
- (B) 91

- ✅ **(C) 22** *(Correct Answer)*
- (D) 82

**Correct Answer:** Option (C)

---