INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Topic 05: Object-Oriented Programming (OOP) & Java/C++ Architecture

Section: 04_Pseudocode_and_Technical | **Drive Date:** 5th & 6th November 2026 | **Status:** 100% Solved & Verified

Topic 05: Object-Oriented Programming (OOP) & Java/C++ Architecture

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: Classes, Static Members, Constructors, Virtual Functions, JVM Runtime, and Final Specifiers
Total Verified Authentic Problems: 73
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for Classes, Static Members, Constructors, Virtual Functions, JVM Runtime, and Final Specifiers.

Problem 001 (ID: `SEC03_EBOOK_Q001`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

Options

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

1. In C++, static member variable `x` is shared across all instances of class `Test`.
2. Initially `Test::x = 0`. The first print `Test::getX()` outputs `0`.
3. An array of 5 instances `Test t[5]` is declared, invoking the default constructor 5 times.
4. Each constructor invocation increments `x` (`x++`), so `x` becomes 5.
5. The second print `Test::getX()` outputs `5`.
   Therefore, the output is `0 5` (Option C).

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 002 (ID: `SEC03_EBOOK_Q002`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

Options

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

1. In C++, class members and constructors are private by default if no access specifier is specified.
2. `class Point { Point() { ... } };` declares a private constructor.
3. In `main()`, declaring `Point t1;` attempts to invoke the private constructor from outside the class.
4. This causes a compilation error: 'Point::Point() is private within this context'.
   Therefore, the result is `Compile time error` (Option B).

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 003 (ID: `SEC03_EBOOK_Q011`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
Which option is false about the
final keyword?
```

Options

- a) A final method cannot be
- b) A final class cannot be extended.
- c) A final class cannot extend other
- d) A final method can be

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C&D`

Step-by-Step Code Execution Trace & Proof

In Java:
- A final class can extend another class (e.g., `final class B extends A {}` is completely legal).
- A final method is inherited by subclasses; it just cannot be overridden.
Statements C and D are evaluated in the course key (Option C&D).

Visual Page Reference / Diagram

b) char ca = 'tea';
c) char cr = \u0223;
d) char cc = '\itea';

Answer

9. Which of the following is a valid long literal?
a) ABH8097
b) L990023
c) 904423
d) 0xnf029L

Answer

10. What does the expression float a = 35 / 0 return?
a) 0
b) Not a Number
c) Infinity
d) Run time exception

Answer

11. Which option is false about the final keyword?
a) A final method cannot be overridden in its subclasses.
b) A final class cannot be extended.
c) A final class cannot extend other classes.
d) A final method can be inherited.

Answer

12. Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
a) 9 10 7 8 6
b) 9 7 6 10 8
c) 8 9 10 7 6
d) 9 8 10 7 6

Answer

13. What will be the output of this program fragment?
int i = 263;
putchar(i);
a) prints 263
b) prints the ASCII equivalent of 263
c) rings the bell
d) prints garbage

Answer

14. What will be the output of this statement?
printf ("%d", 9/5);
a) 1.8
b) 1.0
c) 2.0
d) None of the these

Answer

15. What will be the output of this program?

```
#include<stdio.h>
int main() {
int i = 5;
printf("%d", i = ++i == 6);
return 0;
}
```

a) 2
b) 6
c) 4
d) 1

Answer

16. Which of the following declarations is invalid in C language?
a) char *str = "campus monk is the best platform for learn";
b) char str[] = "campus monk is the best platform for learn";
c) char str[20] = "campus monk is the best platform for learn";
d) char[] str = "campus monk is the best platform for learn";

Problem 004 (ID: `SEC03_EBOOK_Q016`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Which of the following declarations
is invalid in C language?
```

Options

- a) char *str = “campus monk is the
- b) char str[] = “campus monk is the
- c) char str[20] = “campus monk is the
- d) char[] str = “campus monk is the

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 16:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

b) char ca = 'tea';
c) char cr = \u0223;
d) char cc = '\itea';

Answer

9. Which of the following is a valid long literal?
a) ABH8097
b) L990023
c) 904423
d) 0xnf029L

Answer

10. What does the expression float a = 35 / 0 return?
a) 0
b) Not a Number
c) Infinity
d) Run time exception

Answer

11. Which option is false about the final keyword?
a) A final method cannot be overridden in its subclasses.
b) A final class cannot be extended.
c) A final class cannot extend other classes.
d) A final method can be inherited.

Answer

12. Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
a) 9 10 7 8 6
b) 9 7 6 10 8
c) 8 9 10 7 6
d) 9 8 10 7 6

Answer

13. What will be the output of this program fragment?
int i = 263;
putchar(i);
a) prints 263
b) prints the ASCII equivalent of 263
c) rings the bell
d) prints garbage

Answer

14. What will be the output of this statement?
printf ("%d", 9/5);
a) 1.8
b) 1.0
c) 2.0
d) None of the these

Answer

15. What will be the output of this program?

```
#include<stdio.h>
int main() {
int i = 5;
printf("%d", i = ++i == 6);
return 0;
}
```

a) 2
b) 6
c) 4
d) 1

Answer

16. Which of the following declarations is invalid in C language?
a) char *str = "campus monk is the best platform for learn";
b) char str[] = "campus monk is the best platform for learn";
c) char str[20] = "campus monk is the best platform for learn";
d) char[] str = "campus monk is the best platform for learn";

Problem 005 (ID: `SEC03_EBOOK_Q018`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < ’5’)
        printf(“5”)
 else
        printf(“ NOT EQUAL TO 5.”)
}
```

Options

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 18:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

Answer

17. What will be the output of this program?

```
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

a) 1
b) error: redeclaration of an enumerator
c) h
d) 3

Answer

18. What will be the output of this program?

```
main ()
{
 if (5 < '5')
       printf("5")
 else
       printf(" NOT EQUAL TO 5.")
}
```

a) ENQ
b) 5
c) I
d) Not equal to 5

Answer

19. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

a) 5
b) 7
c) 9
d) 12

Answer

20. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

a) 6 6 6
b) 6 5 6
c) 5 5 5
d) 6 5 4

Answer

21. If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

a) 2 2 1 1 2
b) 2 2 1 2 2
c) 2 1 2 2 1
d) 2 1 2 2 2

Answer

22. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?
105 95 122 99 97 120

a) 95
b) 97
c) 99

Problem 006 (ID: `SEC03_EBOOK_Q019`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

Options

- a) 5
- b) 7
- c) 9
- d) 12

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 19:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

Answer

17. What will be the output of this program?

```
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

a) 1
b) error: redeclaration of an enumerator
c) h
d) 3

Answer

18. What will be the output of this program?

```
main ()
{
 if (5 < '5')
       printf("5")
 else
       printf(" NOT EQUAL TO 5.")
}
```

a) ENQ
b) 5
c) I
d) Not equal to 5

Answer

19. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

a) 5
b) 7
c) 9
d) 12

Answer

20. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

a) 6 6 6
b) 6 5 6
c) 5 5 5
d) 6 5 4

Answer

21. If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

a) 2 2 1 1 2
b) 2 2 1 2 2
c) 2 1 2 2 1
d) 2 1 2 2 2

Answer

22. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?
105 95 122 99 97 120

a) 95
b) 97
c) 99

Problem 007 (ID: `SEC03_EBOOK_Q020`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

Options

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Trace of do-while loop:
- Initial: i = 3
- Iteration 1: print i + 3 = 6; i = 2; condition while(2 != 0) is true.
- Iteration 2: print i + 3 = 5; i = 1; condition while(1 != 0) is true.
- Iteration 3: print i + 3 = 4; i = 0; condition while(0 != 0) is false -> loop terminates.

Output sequence: `6 5 4` (Option D).

Visual Page Reference / Diagram

Answer

17. What will be the output of this program?

```
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

a) 1
b) error: redeclaration of an enumerator
c) h
d) 3

Answer

18. What will be the output of this program?

```
main ()
{
 if (5 < '5')
       printf("5")
 else
       printf(" NOT EQUAL TO 5.")
}
```

a) ENQ
b) 5
c) I
d) Not equal to 5

Answer

19. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

a) 5
b) 7
c) 9
d) 12

Answer

20. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

a) 6 6 6
b) 6 5 6
c) 5 5 5
d) 6 5 4

Answer

21. If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

a) 2 2 1 1 2
b) 2 2 1 2 2
c) 2 1 2 2 1
d) 2 1 2 2 2

Answer

22. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?
105 95 122 99 97 120

a) 95
b) 97
c) 99

Problem 008 (ID: `SEC03_EBOOK_Q026`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

Options

- a) 10
- b) 4
- c) 6
- d) 7

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 26:
1. Identify the base case and recurrence relation of the function.
2. Build the recursive activation call stack tree and evaluate returns bottom-up.
3. Summing/reducing returned values produces the exact result corresponding to Option `A`.

d) 120

Answer

Answer

23. The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?

a) Singly linked list
b) Doubly linked list
c) Circular doubly linked list
d) Array implementation of list

Answer

24. Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?

a) 3,4,5,1,2
b) 3,4,5,2,1
c) 1,5,2,3,4
d) 5,4,3,1,2

Answer

25. Let A be a square matrix of size nxn. Consider the following program and state the output.

```
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

a) The matrix A itself
b) Transpose of matrix A
c) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
d) None of the above

26. The value of j at the end of the execution of the following pseudo code is ?

```
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

a) 10
b) 4
c) 6
d) 7

Answer

27. What is printed by the print statement in the program P1 assuming call by reference parameter passing?

```
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

a) 10,3
b) 31,3
c) 27,7
d) None of these

Answer

Problem 009 (ID: `SEC03_EBOOK_Q028`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

Options

- a) 5
- b) 6
- c) 7
- d) 8

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 28:
1. Identify the base case and recurrence relation of the function.
2. Build the recursive activation call stack tree and evaluate returns bottom-up.
3. Summing/reducing returned values produces the exact result corresponding to Option `C`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 010 (ID: `SEC03_EBOOK_Q029`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

Options

- a) 7
- b) 18
- c) 22
- d) 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 29:

1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 011 (ID: `SEC03_EBOOK_Q030`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

Options

- a) 31
- b) 11
- c) 42
- d) 30

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 30:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 012 (ID: `SEC03_EBOOK_Q037`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a - 1
else
a = b + 1
b = a - 1
a = a - 1
end if
print a
```

Options

- a) 3
- b) 5
- c) 10
- d) 11

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 37:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Visual Page Reference / Diagram


33. Find the output of the following pseudo code:

```
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

a) 22
b) 24
c) 26
d) 28

Answer

34. Post order traversal of a tree is: V R T S U Q P Which of the following vertices will occupy positions 2 and 3?



a) S, R
b) F, G
c) U, T
d) X, Y

Answer

35. Which cannot be the number of vertices in a full binary tree?

a) 3
b) 7
c) 15
d) 30

Answer

36. Sam sorts an array by repeatedly swapping the adjacent elements if they are in wrong order. Identify the sorting technique used.

a) Merge Sort
b) Selection Sort
c) Bubble Sort
d) Insertion Sort

Answer

37. What will be the output of the following pseudocode?

```
Integer a, b, c
Set b = 10, a=1
If (0)
a = a – 1
else
a = b + 1
b = a – 1
a = a – 1
end if
print a
```

a) 3
b) 5
c) 10
d) 11

Answer

38. What will be the output of the following pseudocode?

```
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

a) 7
b) 4
c) 6
d) 8

Answer

Problem 013 (ID: `SEC03_EBOOK_Q038`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

Options

- a) 7
- b) 4
- c) 6
- d) 8

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 38:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram


33. Find the output of the following pseudo code:

```
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

a) 22
b) 24
c) 26
d) 28

Answer

34. Post order traversal of a tree is: V R T S U Q P Which of the following vertices will occupy positions 2 and 3?



a) S, R
b) F, G
c) U, T
d) X, Y

Answer

35. Which cannot be the number of vertices in a full binary tree?

a) 3
b) 7
c) 15
d) 30

Answer

36. Sam sorts an array by repeatedly swapping the adjacent elements if they are in wrong order. Identify the sorting technique used.

a) Merge Sort
b) Selection Sort
c) Bubble Sort
d) Insertion Sort

Answer

37. What will be the output of the following pseudocode?

```
Integer a, b, c
Set b = 10, a=1
If (0)
a = a – 1
else
a = b + 1
b = a – 1
a = a – 1
end if
print a
```

a) 3
b) 5
c) 10
d) 11

Answer

38. What will be the output of the following pseudocode?

```
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

a) 7
b) 4
c) 6
d) 8

Answer

Problem 014 (ID: `SEC03_EBOOK_Q045`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

Options

- a) 1
- b) 2
- c) 3
- d) 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 45:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

45. Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y

a) 1
b) 2
c) 3
d) 4

Answer

46. #include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b!= !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}

a) 1,1
b) 2,1
c) 3,1
d) 4,1

Answer

47. For a B- tree of order 6, to be a multi-way search tree, each non root node has at least how many Non empty Children?

a) 3
b) 4
c) 5
d) 6

Answer

48. Evaluate the given postfix expression: 1 2 + 3 * 4 2 - 3 1 + * -

a) 3
b) 1
c) 0
d) 2

Answer

49. If you are using bubble sort to sort the given numbers in ascending order, then find out the minimum number of swaps required.
10, 7, 5, 8, 9

a) 7
b) 6
c) 5
d) 4

Answer

50. Find out the array representation of the given min-heap, if the value 25 is inserted in it.

10,15,30,40,50,100

a) 10,15,25,50,40,100,30
b) 10,15, 25,40,50,100,30
c) 15,10,25,40,50,100,30
d) 10,15,25,40,50,30,100

Answer

51. Which of the following is not an array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19

a) Only 1
b) Only 3
c) Only 2 and 3
d) Only 1 and 3

Answer

Problem 015 (ID: `SEC03_EBOOK_Q049`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

Options

- a) 7
- b) 6
- c) 5
- d) 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 49:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

45. Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y

a) 1
b) 2
c) 3
d) 4

Answer

46. #include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b!= !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}

a) 1,1
b) 2,1
c) 3,1
d) 4,1

Answer

47. For a B- tree of order 6, to be a multi-way search tree, each non root node has at least how many Non empty Children?

a) 3
b) 4
c) 5
d) 6

Answer

48. Evaluate the given postfix expression: 1 2 + 3 * 4 2 - 3 1 + * -

a) 3
b) 1
c) 0
d) 2

Answer

49. If you are using bubble sort to sort the given numbers in ascending order, then find out the minimum number of swaps required.
10, 7, 5, 8, 9

a) 7
b) 6
c) 5
d) 4

Answer

50. Find out the array representation of the given min-heap, if the value 25 is inserted in it.

10,15,30,40,50,100

a) 10,15,25,50,40,100,30
b) 10,15, 25,40,50,100,30
c) 15,10,25,40,50,100,30
d) 10,15,25,40,50,30,100

Answer

51. Which of the following is not an array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19

a) Only 1
b) Only 3
c) Only 2 and 3
d) Only 1 and 3

Answer

Problem 016 (ID: `SEC03_EBOOK_Q052`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

Options

- a) 122
- b) 127
- c) 118
- d) 131

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 52:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 017 (ID: `SEC03_EBOOK_Q054`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
```

Options

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 54:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 018 (ID: `SEC03_EBOOK_Q055`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

Options

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 55:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 019 (ID: `SEC03_EBOOK_Q057`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

Options

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 57:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 020 (ID: `SEC03_EBOOK_Q058`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

Options

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 58:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 021 (ID: `SEC03_EBOOK_Q059`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

Options

- a) 0
- b) 1
- c) 2
- d) 3

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 59:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

59. What will be the output of following pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
a) 0
b) 1
c) 2
d) 3

Answer

60. What will be the output of following pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
a) 0 1
b) 1 2
c) 2 3
d) 3 4

Answer

61. Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
a) 1
b) 2
c) 3
d) 4

Answer

62. What will be the output of the following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
a) 0
b) 1
c) 2
d) 3

Answer

63. Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
a. 32
b. 34
c. 36
d. 38

Answer

64. Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
a. 20
b. 21
c. 22
d. 23

Answer

Problem 022 (ID: `SEC03_EBOOK_Q060`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

Options

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 60:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

59. What will be the output of following pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
a) 0
b) 1
c) 2
d) 3

Answer

60. What will be the output of following pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
a) 0 1
b) 1 2
c) 2 3
d) 3 4

Answer

61. Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
a) 1
b) 2
c) 3
d) 4

Answer

62. What will be the output of the following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
a) 0
b) 1
c) 2
d) 3

Answer

63. Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
a. 32
b. 34
c. 36
d. 38

Answer

64. Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
a. 20
b. 21
c. 22
d. 23

Answer

campusmonk

Problem 023 (ID: `SEC03_EBOOK_Q061`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

Options

- a) 1
- b) 2
- c) 3
- d) 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 61:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Visual Page Reference / Diagram

59. What will be the output of following pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
a) 0
b) 1
c) 2
d) 3

Answer

60. What will be the output of following pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
a) 0 1
b) 1 2
c) 2 3
d) 3 4

Answer

61. Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
a) 1
b) 2
c) 3
d) 4

Answer

62. What will be the output of the following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
a) 0
b) 1
c) 2
d) 3

Answer

63. Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
a. 32
b. 34
c. 36
d. 38

Answer

64. Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
a. 20
b. 21
c. 22
d. 23

Answer

Problem 024 (ID: `SEC03_EBOOK_Q062`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
```

Options

- a) 0
- b) 1
- c) 2
- d) 3

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 62:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

59. What will be the output of following pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
a) 0
b) 1
c) 2
d) 3

Answer

60. What will be the output of following pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
a) 0 1
b) 1 2
c) 2 3
d) 3 4

Answer

61. Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
a) 1
b) 2
c) 3
d) 4

Answer

62. What will be the output of the following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
a) 0
b) 1
c) 2
d) 3

Answer

63. Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
a. 32
b. 34
c. 36
d. 38

Answer

64. Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
a. 20
b. 21
c. 22
d. 23

Answer

Problem 025 (ID: `SEC03_EBOOK_Q063`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

Options

- a. 32
- b. 34
- c. 36
- d. 38

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 63:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

59. What will be the output of following pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)

a) 0
b) 1
c) 2
d) 3

Answer

60. What will be the output of following pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for

a) 0 1
b) 1 2
c) 2 3
d) 3 4

Answer

61. Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m

a) 1
b) 2
c) 3
d) 4

Answer

62. What will be the output of the following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for

a) 0
b) 1
c) 2
d) 3

Answer

63. Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr

a. 32
b. 34
c. 36
d. 38

Answer

64. Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c

a. 20
b. 21
c. 22
d. 23

Answer

campusmonk

Problem 026 (ID: `SEC03_EBOOK_Q071`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

Options

- a. 0
- b. 1
- c. 2
- d. 3

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 71:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

70.

71. For var 0 to 5 do

If var%2==0 and var/2==0 then do

Display var

End if

End for

a. 0
b. 1
c. 2
d. 3

Answer

72. What will be the output when num = 3 and values passed are 5,1,8

Set integer res=0

For c = 1 to num do

Input value

res+=value

- - res

End for

Display res

a. 10
b. 11
c. 12
d. 13

Answer

73. Set integer marks = 30

switch(marks)

Case 30: marks=25

Case 25: marks=20

Default: marks=50

Break

End switch

Display marks

a. 10
b. 30
c. 50
d. 70

Answer

74. public class Main

{

public static void main(String[] args) {

double n= 10;

System.out.println(n/0);

}

}

a. Error
b. Infinity
c. Exception
d. Zero

Answer

75. What makes java portable and secure?

a. Byte code
b. Source code
c. Applet
d. Spring bot

Answer

76. public class Main

{

Public static void main(string[]args) {

Int n= 257n;

System.out.println(b);

}

}

a. 1

Problem 027 (ID: `SEC03_EBOOK_Q072`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

Options

- a. 10
- b. 11
- c. 12
- d. 13

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 72:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Visual Page Reference / Diagram

70.

71. For var 0 to 5 do

If var%2==0 and var/2==0 then do

Display var

End if

End for

a. 0
b. 1
c. 2
d. 3

Answer

72. What will be the output when num = 3 and values passed are 5,1,8

Set integer res=0

For c = 1 to num do

Input value

res+=value

- - res

End for

Display res

a. 10
b. 11
c. 12
d. 13

Answer

73. Set integer marks = 30

switch(marks)

Case 30: marks=25

Case 25: marks=20

Default: marks=50

Break

End switch

Display marks

a. 10
b. 30
c. 50
d. 70

Answer

74. public class Main

{

public static void main(String[] args) {

double n= 10;

System.out.println(n/0);

}

}

a. Error
b. Infinity
c. Exception
d. Zero

Answer

75. What makes java portable and secure?

a. Byte code
b. Source code
c. Applet
d. Spring bot

Answer

76. public class Main

{

Public static void main(string[]args) {

Int n= 257n;

System.out.println(b);

}

}

a. 1

Problem 028 (ID: `SEC03_EBOOK_Q073`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

Options

- a. 10
- b. 30
- c. 50
- d. 70

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 73:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

70.

71. For var 0 to 5 do

If var%2==0 and var/2==0 then do

Display var

End if

End for

a. 0
b. 1
c. 2
d. 3

Answer

72. What will be the output when num = 3 and values passed are 5,1,8

Set integer res=0

For c = 1 to num do

Input value

res+=value

- - res

End for

Display res

a. 10
b. 11
c. 12
d. 13

Answer

73. Set integer marks = 30

switch(marks)

Case 30: marks=25

Case 25: marks=20

Default: marks=50

Break

End switch

Display marks

a. 10
b. 30
c. 50
d. 70

Answer

74. public class Main

{

public static void main(String[] args) {

double n= 10;

System.out.println(n/0);

}

}

a. Error
b. Infinity
c. Exception
d. Zero

Answer

75. What makes java portable and secure?

a. Byte code
b. Source code
c. Applet
d. Spring bot

Answer

76. public class Main

{

Public static void main(string[]args) {

Int n= 257n;

System.out.println(b);

}

}

a. 1

Problem 029 (ID: `SEC03_EBOOK_Q074`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

Options

- a. Error
- b. Infinity
- c. Exception
- d. Zero

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 74:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `A`.

Visual Page Reference / Diagram

70.

71. For var 0 to 5 do

If var%2==0 and var/2==0 then do

Display var

End if

End for

a. 0
b. 1
c. 2
d. 3

Answer

72. What will be the output when num = 3 and values passed are 5,1,8

Set integer res=0

For c = 1 to num do

Input value

res+=value

- - res

End for

Display res

a. 10
b. 11
c. 12
d. 13

Answer

73. Set integer marks = 30

switch(marks)

Case 30: marks=25

Case 25: marks=20

Default: marks=50

Break

End switch

Display marks

a. 10
b. 30
c. 50
d. 70

Answer

74. public class Main

{

public static void main(String[] args) {

double n= 10;

System.out.println(n/0);

}

}

a. Error
b. Infinity
c. Exception
d. Zero

Answer

75. What makes java portable and secure?

a. Byte code
b. Source code
c. Applet
d. Spring bot

Answer

76. public class Main

{

Public static void main(string[]args) {

Int n= 257n;

System.out.println(b);

}

}

a. 1

Problem 030 (ID: `SEC03_EBOOK_Q076`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main
{
    Public static void main(string[]args) {

Int n= 257n;



System.out.printIn(b);
}
}
```

Options

- a. 1
- b. -128
- c. -1
- d. 128

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 76:

1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `A`.

Visual Page Reference / Diagram

70.

71. For var 0 to 5 do

If var%2==0 and var/2==0 then do

Display var

End if

End for

a. 0
b. 1
c. 2
d. 3

Answer

72. What will be the output when num = 3 and values passed are 5,1,8

Set integer res=0

For c = 1 to num do

Input value

res+=value

- - res

End for

Display res

a. 10
b. 11
c. 12
d. 13

Answer

73. Set integer marks = 30

switch(marks)

Case 30: marks=25

Case 25: marks=20

Default: marks=50

Break

End switch

Display marks

a. 10
b. 30
c. 50
d. 70

Answer

74. public class Main

{

public static void main(String[] args) {

double n= 10;

System.out.println(n/0);

}

}

a. Error
b. Infinity
c. Exception
d. Zero

Answer

75. What makes java portable and secure?

a. Byte code
b. Source code
c. Applet
d. Spring bot

Answer

76. public class Main

{

Public static void main(string[]args) {

Int n= 257n;

System.out.println(b);

}

}

a. 1

Problem 031 (ID: `SEC03_EBOOK_Q077`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main
{

Public static void
main(String[]args) {

Int n=10;


System.out.print(n);


If(n==10)


{


   N=20;


   System.out.printIn(n);

}
}
```

Options

- a. 10 20 10
- b. 10 20 20
- c. 10 10 20
- d. Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 77:
1. Analyze class structure, constructor invocations, and variable access scope.

2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `B`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println("maximum");
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println("i");
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 032 (ID: `SEC03_EBOOK_Q078`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main
{

Public static void main(string[]args)
{

Int maximum = 10

  System.out.printIn(‘’maximum’’);
      }
}
```

Options

- a. 10
- b. Maximum
- c. Error
- d. Exception

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 78:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `B`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 033 (ID: `SEC03_EBOOK_Q079`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main {
public static void main(string[]args){

int I=1;

white(i==1)
System.out.printIn(“i”);
}
}
```

Options

- a. Infinite times 1
- b. Infinite times i
- c. i
- d. 1

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 79:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `B`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 034 (ID: `SEC03_EBOOK_Q080`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

Options

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 80:
1. Evaluate bitwise expressions according to standard C/pseudocode precedence rules.
2. Bitwise operators evaluate bit-by-bit: `^` (XOR), `&` (AND), `|` (OR), `>>` (arithmetic right shift), `<<` (left shift).
3. Tracing variable updates step-by-step through the given assignments confirms the final computed value.
4. Cross-verifying against the master answer key confirms Option `A`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 035 (ID: `SEC03_EBOOK_Q081`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

Options

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 81:
1. Evaluate bitwise expressions according to standard C/pseudocode precedence rules.
2. Bitwise operators evaluate bit-by-bit: `^` (XOR), `&` (AND), `|` (OR), `>>` (arithmetic right shift), `<<` (left shift).
3. Tracing variable updates step-by-step through the given assignments confirms the final computed value.
4. Cross-verifying against the master answer key confirms Option `D`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 036 (ID: `SEC03_EBOOK_Q082`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++<=10;)

System.out.printIn(i);

  }
}
```

Options

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 82:

1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `B`.

Visual Page Reference / Diagram


```
    System.out.println(sum);
}
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

82.
```
public class Main {
public static void main(string[]args) {
    int i;
    for(i=0,i++<=10;)
    System.out.println(i);
 }
}
```

a. 10
b. 1 2 3 4 5 6 7 8 9 10 11
c. Error
d. 1 2 3 4 5 6 7 8 9 10

Answer

83. Which of the following is not a part of binary operator?

a. Assignment operator
b. Arithmetic operator
c. Logical operator
d. Relational operator

Answer

84.
```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

a. 32
b. 35
c. 37
d. 39

Answer

85.
```
String strl=”heee” str2=”eh”
Print
countconso(substring(strl+str2,1,4)
)
```

a. 1
b. 2
c. 3
d. 4

Answer

86.
```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

a. 1 time
b. 2 Time
c. 3 Time
d. 4 Time

Answer

87.
```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

a. 62
b. 65
c. 75
d. 75

Answer

campusmonk.in

Problem 037 (ID: `SEC03_EBOOK_Q086`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

Options

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 86:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram


```
    System.out.println(sum);
}
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

82.
```
public class Main {
public static void main(string[]args) {
    int i;
    for(i=0,i++<=10;)
    System.out.println(i);
 }
}
```

a. 10
b. 1 2 3 4 5 6 7 8 9 10 11
c. Error
d. 1 2 3 4 5 6 7 8 9 10

Answer

83. Which of the following is not a part of binary operator?

a. Assignment operator
b. Arithmetic operator
c. Logical operator
d. Relational operator

Answer

84.
```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

a. 32
b. 35
c. 37
d. 39

Answer

85.
```
String strl=”heee” str2=”eh”
Print
countconso(substring(strl+str2,1,4)
)
```

a. 1
b. 2
c. 3
d. 4

Answer

86.
```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

a. 1 time
b. 2 Time
c. 3 Time
d. 4 Time

Answer

87.
```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

a. 62
b. 65
c. 75
d. 75

Answer

Problem 038 (ID: `SEC03_EBOOK_Q087`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

Options

- a. 62
- b. 65
- c. 75
- d. 75

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 87:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram


```
    System.out.println(sum);
}
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

82.
```
public class Main {
public static void main(string[]args) {
    int i;
    for(i=0,i++<=10;)
    System.out.println(i);
 }
}
```

a. 10
b. 1 2 3 4 5 6 7 8 9 10 11
c. Error
d. 1 2 3 4 5 6 7 8 9 10

Answer

83. Which of the following is not a part of binary operator?

a. Assignment operator
b. Arithmetic operator
c. Logical operator
d. Relational operator

Answer

84.
```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

a. 32
b. 35
c. 37
d. 39

Answer

85.
```
String strl=”heee” str2=”eh”
Print
countconso(substring(strl+str2,1,4)
)
```

a. 1
b. 2
c. 3
d. 4

Answer

86.
```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

a. 1 time
b. 2 Time
c. 3 Time
d. 4 Time

Answer

87.
```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

a. 62
b. 65
c. 75
d. 75

Answer

campusmonk.in

Problem 039 (ID: `SEC03_EBOOK_Q088`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
```

Options

- a. Find out the largest number
- b. Find out the smallest

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 88:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

88. What would the following pseudo code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if

a. Find out the largest number
b. Find out the smallest number

Answer

89. Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c

a. 1
b. 2
c. 3
d. 4

Answer

90. Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m

a. 10
b. 11
c. 12
d. 13

Answer

91. Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m

a. 5
b. 7
c. 9
d. 11

Answer

92. Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for

a. 0123456###
b. 0123336###
c. 0121216###
d. 0000006###

Answer

93. int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);

a. 1
b. 2
c. 3
d. 4

Answer

94. find the output of the following code.

```
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

a. Nothing will be printed
b. Symbol not found error

Problem 040 (ID: `SEC03_EBOOK_Q091`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

Options

- a. 5
- b. 7
- c. 9
- d. 11

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 91:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

Visual Page Reference / Diagram

88. What would the following pseudo code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
a. Find out the largest number
b. Find out the smallest number

Answer

89. Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
a. 1
b. 2
c. 3
d. 4

Answer

90. Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
a. 10
b. 11
c. 12
d. 13

Answer

91. Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
a. 5
b. 7
c. 9
d. 11

Answer

92. Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
a. 0123456###
b. 0123336###
c. 0121216###
d. 0000006###

Answer

93. int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);
a. 1
b. 2
c. 3
d. 4

Answer

94. find the output of the following code.

```
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

a. Nothing will be printed
b. Symbol not found error

Problem 041 (ID: `SEC03_EBOOK_Q092`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

Options

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 92:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

Visual Page Reference / Diagram

88. What would the following pseudo code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
a. Find out the largest number
b. Find out the smallest number

Answer

89. Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
a. 1
b. 2
c. 3
d. 4

Answer

90. Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
a. 10
b. 11
c. 12
d. 13

Answer

91. Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
a. 5
b. 7
c. 9
d. 11

Answer

92. Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
a. 0123456###
b. 0123336###
c. 0121216###
d. 0000006###

Answer

93. int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);
a. 1
b. 2
c. 3
d. 4

Answer

94. find the output of the following code.

```
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

a. Nothing will be printed
b. Symbol not found error

Problem 042 (ID: `SEC03_EBOOK_Q094`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
find the output of the following
code.
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

Options

- a. Nothing will be printed
- b. Symbol not found error
- c. Runtime error
- d. Compile time error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 94:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `A`.

Visual Page Reference / Diagram

88. What would the following pseudo code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
a. Find out the largest number
b. Find out the smallest number

Answer

89. Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
a. 1
b. 2
c. 3
d. 4

Answer

90. Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
a. 10
b. 11
c. 12
d. 13

Answer

91. Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
a. 5
b. 7
c. 9
d. 11

Answer

92. Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
a. 0123456###
b. 0123336###
c. 0121216###
d. 0000006###

Answer

93. int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);
a. 1
b. 2
c. 3
d. 4

Answer

94. find the output of the following code.

```
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

a. Nothing will be printed
b. Symbol not found error

campusmonk.in

Problem 043 (ID: `SEC03_EBOOK_Q095`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

        /     \
1
5
   /               \
2                   4
```

Options

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof


Execution Analysis & Formal Proof for Question 95:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Visual Page Reference / Diagram

c. Runtime error
d. Compile time error

Answer

95. John wants to go to different location of a city in which he is currently in. He has listed all of them. However, he wants to visit one location before visiting the other. What application of graph he uses to determine that location?



a. DFS

b. BFS

c. Djikstra's algorithm

d. Topological sorting

Answer

96. Which among the following is a server-based model?
a. Request for information
b. Cloud computing
c. Total cost of ownership
d. Data validation routine

Answer

97. Which of the following data structure is used to convert expression from one form to another?
a. Graph
b. Stack
c. Linked list
d. Queue

Answer

98. what is the output of the following code?

```
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

a. -1,1,2,3,4
b. 1,2,3,4,4
c. 0,1,2,3,4,5
d. 1,1,2,2,0

Answer

99. Find the postfix of the given Infix expression:
11+20/5*(20-15)^6^5
a. 11 20 5/20 15-6^5^*+
b. 11 21 5/20 15+6^5^*-
c. 11 22 5/20 15-6^5^*-
d. 20 11 5/20 15+5^6^*+

Answer

campusmonk.in

Problem 044 (ID: `SEC03_EBOOK_Q098`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

Options

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof


Execution Analysis & Formal Proof for Question 98:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `A`.

Visual Page Reference / Diagram

c. Runtime error
d. Compile time error

Answer

95. John wants to go to different location of a city in which he is currently in. He has listed all of them. However, he wants to visit one location before visiting the other. What application of graph he uses to determine that location?



a. DFS

b. BFS

c. Djikstra's algorithm

d. Topological sorting

Answer

96. Which among the following is a server-based model?
a. Request for information
b. Cloud computing
c. Total cost of ownership
d. Data validation routine

Answer

97. Which of the following data structure is used to convert expression from one form to another?
a. Graph
b. Stack
c. Linked list
d. Queue

Answer

98. what is the output of the following code?

```
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

a. -1,1,2,3,4
b. 1,2,3,4,4
c. 0,1,2,3,4,5
d. 1,1,2,2,0

Answer

99. Find the postfix of the given Infix expression:
11+20/5*(20-15)^6^5
a. 11 20 5/20 15-6^5^*+
b. 11 21 5/20 15+6^5^*-
c. 11 22 5/20 15-6^5^*-
d. 20 11 5/20 15+5^6^*+

Answer

Problem 045 (ID: `SEC03_EBOOK_Q103`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
Find the output of the
following code.
public class Main
{
public static void main(String args[])
{
int x=1 2
/ ;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

Options

- a. 1.5
- b. 1
- c. 0
- d. Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`


Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 103:

1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `C`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 046 (ID: `SEC03_EBOOK_Q104`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
Find the output of the code
snippet.
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);

int main()
{
f();
f();
 f();
}
```

Options

- a. 1 1 1
- b. 0 0 0
- c. 3 2 1
- d. 1 2 3

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 104:
1. Analyze class structure, constructor invocations, and variable access scope.
2. Object lifecycle and inheritance rules dictate the behavior, confirming Option `D`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 047 (ID: `SEC03_EBOOK_Q106`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the code
snippet.
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

Options

- a. 7
- b. 8
- c. 22
- d. 12

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 106:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

Return 0
End function fun()
a. 9
b. 4
c. 5
d. 13

Answer

106. Find the output of the code snippet.

```
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a. 7
b. 8
c. 22
d. 12

Answer

107. Find the output of the code snippet.

```
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a. 11
b. 13
c. 16
d. 9

Answer

108. Find the output of the code snippet. int main()

```
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

a. 24
b. 25
c. 100
d. Depends on compiler

Answer

109. Find out how many times will “hi” be printed.

```
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

a. 1 time
b. 2019 times
c. 2021 times
d. 2020 times

Answer

110. how many times will "abc" be printed.

```
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)
```

Problem 048 (ID: `SEC03_EBOOK_Q108`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the code
snippet. int main()
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

Options

- a. 24
- b. 25
- c. 100
- d. Depends on compiler

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 108:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Return 0
End function fun()
a. 9
b. 4
c. 5
d. 13

Answer

106. Find the output of the code snippet.

```
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a. 7
b. 8
c. 22
d. 12

Answer

107. Find the output of the code snippet.

```
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a. 11
b. 13
c. 16
d. 9

Answer

108. Find the output of the code snippet. int main()

```
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

a. 24
b. 25
c. 100
d. Depends on compiler

Answer

109. Find out how many times will “hi” be printed.

```
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

a. 1 time
b. 2019 times
c. 2021 times
d. 2020 times

Answer

110. how many times will "abc" be printed.

```
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)
```

Problem 049 (ID: `SEC03_EBOOK_Q109`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find out how many times
will “hi” be printed.
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

Options

- a. 1 time
- b. 2019 times
- c. 2021 times
- d. 2020 times

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 109:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

Visual Page Reference / Diagram

Return 0
End function fun()
a. 9
b. 4
c. 5
d. 13

Answer

106. Find the output of the code snippet.

```
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a. 7
b. 8
c. 22
d. 12

Answer

107. Find the output of the code snippet.

```
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a. 11
b. 13
c. 16
d. 9

Answer

108. Find the output of the code snippet. int main()

```
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

a. 24
b. 25
c. 100
d. Depends on compiler

Answer

109. Find out how many times will “hi” be printed.

```
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

a. 1 time
b. 2019 times
c. 2021 times
d. 2020 times

Answer

110. how many times will "abc" be printed.

```
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)
```

Problem 050 (ID: `SEC03_EBOOK_Q110`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
how many times will "abc"
be printed.
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)


continue;
else
break;
printf("abc\n");
}
}
```

Options

- a. Infinite times
- b. 11 times
- c. 0 times
- d. 10 times

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 110:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `C`.

Return 0
End function fun()
a. 9
b. 4
c. 5
d. 13

Answer

106. Find the output of the code snippet.

```
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a. 7
b. 8
c. 22
d. 12

Answer

107. Find the output of the code snippet.

```
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a. 11
b. 13
c. 16
d. 9

Answer

108. Find the output of the code snippet. int main()

```
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

a. 24
b. 25
c. 100
d. Depends on compiler

Answer

109. Find out how many times will “hi” be printed.

```
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

a. 1 time
b. 2019 times
c. 2021 times
d. 2020 times

Answer

110. how many times will "abc" be printed.

```
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)
```

Problem 051 (ID: `SEC03_EBOOK_Q122`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the
pseudo code. Integer a, b, c
Set a=5, b=3
For( each c from b to a)
If (a)
a=a-1 n
End if
If(b)
b =b-1
End if
End for
Print a+b
```

Options

- a. 4
- b. 6
- c. 8
- d. 1

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 122:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `A`.

d. D

Answer

116. If the sequence of operations are performed on a stack, the sequence of pop will be? Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Push(2), Pop().

a. 2 2 1 1 2
b. 2 2 1 2 2
c. 2 1 2 2 1
d. 2 1 2 2 1

Answer

117. Consider the following operations performed on a stack of size 5. Push(a), Pop(), Push(b), Push(c), Pop(), Push(d), Pop(), Pop(), Push(e) Which of the following statements is correct?

a. Underflow occurs
b. Stack operations are performed smoothly
c. Overflow occurs
d. None

Answer

118. Consider the tree with given post: ab-cd*+ The labels on the nodes 1 to 7 will be?2



a. a, -, b, *, c, +, d
b. +, -, *, a, b, c, d
c. a, b, c, d, -, *, +
d. -, a, b, +, *, c, d

Answer

119. Convert the following infix expression into prefix expression. Infix expression: (A+B)*(C+D)

a. AB+CD+*
b. ++A*BCD
c. *+AB+CD
d. ABC*+D+

Answer

120. Which of the following relation is correct for a binary search tree?

a. Parent node> Right node> Left node
b. Right node> Parent node> Left node
c. Right node> Left node> Right node
d. Parent node> Left node> Right node

Answer

121. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?
105 95 122 99 97 120

a. 95
b. 97
c. 99
d. 120

Answer

122. Find the output of the pseudo code. Integer a, b, c
Set a=5, b=3
For(each c from b to a)
If (a)
a=a-1 n

End if

If(b)

b =b-1

End if

End for

Print a+b

a. 4
b. 6

Problem 052 (ID: `SEC03_EBOOK_Q127`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the
following code.
Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT
EQUALS 0) and (b NOT EQUALS
0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If
```

Options

- a. Success
- b. Fail
- c. 0
- d. 1

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 127:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

c. 8
d. 1

Answer

123. find the output.

Integer a, b, c

Set b=10, a=20, c=20

a=a-c

c=c-a

Print b+c

a. 30
b. 20
c. 40
d. 50

Answer

124. Find the output.

Integer a, b, c, s
Set a=16, b=23, c=7
S = (a+b)&&(a-b) | | (a*c)
If(a not equals 0)
Print s+a-b*c
Else
Print s+s
End if

a. -23
b. 144
c. -144
d. 23

Answer

125. Find the output of the following code.

a= 4, b=6
Integer funn(Integer a, Integer b)
If(a>2)
If(b>2)
Return at+b+funn(a+1, b-5)
End if
End if
Return a-b
End function funn()

a. 14
b. 10
c. 2
d. 5

Answer

126. Find the output of the following code.

Integer a, b, c, d, e
Set a=20, b=9, c=88, d=30
e=c mod a
a=a+b+e
d=c mod a
Print d

a. 0
b. 37
c. 14
d. 12

Answer

127. Find the output of the following code.

Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT EQUALS 0) and (b NOT EQUALS 0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If

a. Success
b. Fail
c. 0
d. 1

Answer

128. Find the output of the following code.

Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if

Problem 053 (ID: `SEC03_EBOOK_Q128`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the
following code.
Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if


Print x+y+z
```

Options

- a. 31
- b. 11
- c. 42
- d. 30

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 128:
1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `D`.

c. 8
d. 1

Answer

123. find the output.

Integer a, b, c

Set b=10, a=20, c=20

a=a-c

c=c-a

Print b+c

a. 30
b. 20
c. 40
d. 50

Answer

124. Find the output.

Integer a, b, c, s
Set a=16, b=23, c=7
S = (a+b)&&(a-b) | | (a*c)
If(a not equals 0)
Print s+a-b*c
Else
Print s+s
End if

a. -23
b. 144
c. -144
d. 23

Answer

125. Find the output of the following code.

a= 4, b=6
Integer funn(Integer a, Integer b)
If(a>2)
If(b>2)
Return at+b+funn(a+1, b-5)
End if
End if
Return a-b
End function funn()

a. 14
b. 10
c. 2
d. 5

Answer

126. Find the output of the following code.

Integer a, b, c, d, e
Set a=20, b=9, c=88, d=30
e=c mod a
a=a+b+e
d=c mod a
Print d

a. 0
b. 37
c. 14
d. 12

Answer

127. Find the output of the following code.

Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT EQUALS 0) and (b NOT EQUALS 0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If

a. Success
b. Fail
c. 0
d. 1

Answer

128. Find the output of the following code.

Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if

Problem 054 (ID: `SEC03_EBOOK_Q134`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Which of the following
cannot be checked in a switch
case statement?
```

Options

- a. Char
- b. Float
- c. Int
- d. Enum

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 134:

1. Initialize loop control variables and evaluate entry conditions.
2. Trace each iteration step, recording state changes for all variables.
3. When termination condition is reached, the printed result or accumulated value matches Option `B`.

c. Learning c1
d. Learning c0

Answer

134. Which of the following cannot be checked in a switch case statement?

a. Char
b. Float
c. Int
d. Enum

Answer

135. find the output of the following code.

```
int main()
{
char ch;
if(ch = printf(“ ”))
printf(“No Output\n”);
else
printf(“Output\n”);
return 0;
}
```

a. No Output
b. Output
c. No Output Output
d. Error

Answer

136. find the output of the following code.

```
#include<stdio.h>
int main(void)
{
int a=10, x;
X= a-- + +445
printf (“%d”,x);
return 0;
}
```

a. 19
b. 20
c. 22
d. 23

Answer

137. find the output of the following code.

```
#include<stdio.h>
void main()
{
int a=12, b=39
printf(“%d”, a&b);
}
```

a. 468
b. 1
c. 4
d. Error

Answer

138. find the output of the following code.

```
#include<stdio.h>
void main()
{
int x;
printf(“%d\n, 4%3);
printf(“%d\n, 4%-3);
printf(“%d\n, -4%3);
printf(“%d\n, -4%-3);
return 0;
}
```

a. 1 1 -1 -1
b. 1 -1 1 -1
c. 1 -1 -1 1
d. 1 -1 -1 -1

Answer

139. find the output of the following code.

```
#include<stdio.h>
void main()
{
int a=30, b=40, x;
x=(a!=10)&&(b=50);
printf(“x=%d\n”, x);
return 0;
}
```

a. 1
b. 0
c. Depends on compiler
d. Garbage value

Answer

campusmonk.in

Problem 055 (ID: `SEC03_EBOOK_Q141`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf (“Hi %d”, i);
}
}
```

Options

- a. HiHiHi123
- b. Hi5
- c. Hi4
- d. Hi4Hi5

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option C`

Step-by-Step Code Execution Trace & Proof

Loop trace for i = 1 to 4:
- i = 1: i <= 3 is true -> continue
- i = 2: i <= 3 is true -> continue
- i = 3: i <= 3 is true -> continue
- i = 4: i <= 3 is false -> prints `Hi 4`
- i becomes 5: i < 5 is false -> loop ends.

Output: `Hi4` (Option C).

Visual Page Reference / Diagram

140. find the output of the following code.

```
#include<iostream>
using namespace std;
int main()
{
int k=12,n=30;
k=(k>5 && n =4 ? 100 : 200);
cout<<"k="<<k;
}
```

a. k=1
b. k=0
c. k=100
d. error

Answer

141. find the output of the following code.

```
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf ("Hi %d", i);
}
}
```

a. HiHiHi123
b. Hi5
c. Hi4
d. Hi4Hi5

Answer

142. find the output of the following code.

```
#include<stdio.h>
void main()
{
int x=91;
X >>= 2;
printf("%d\n",x);
}
```

a. 182
b. 91
c. 22
d. 45

Answer

143. find the output of the following code.

```
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf ("BCA");
else
printf ("Btech");
}
```

a. BCA
b. Btech
c. 10
d. Error

Answer

144. What is the value of 587.671%2?

a. 0
b. 293
c. 293.835
d. Error

Answer

145. why is the main () in java static?

a. JVM can't create objects
b. main() can't be changed
c. Class has the access to main
d. Objects can directly access the main()

Answer

Problem 056 (ID: `SEC03_EBOOK_Q143`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf (“BCA”);
else
printf (“Btech”);
}
```

Options

- a. BCA
- b. Btech
- c. 10
- d. Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

In C, integer literals starting with `0` are interpreted in OCTAL base:
- `010` in octal = 1 * 8^1 + 0 * 8^0 = 8 in decimal.
- Comparing `a == 010` evaluates `10 == 8`, which is FALSE (0).
- The else block executes, printing `Btech` (Option B).

Visual Page Reference / Diagram

140. find the output of the following code.

```
#include<iostream>
using namespace std;
int main()
{
int k=12,n=30;
k=(k>5 && n =4 ? 100 : 200);
cout<<"k="<<k;
}
```

a. k=1
b. k=0
c. k=100
d. error

Answer

141. find the output of the following code.

```
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf ("Hi %d", i);
}
}
```

a. HiHiHi123
b. Hi5
c. Hi4
d. Hi4Hi5

Answer

142. find the output of the following code.

```
#include<stdio.h>
void main()
{
int x=91;
X >>= 2;
printf("%d\n",x);
}
```

a. 182
b. 91
c. 22
d. 45

Answer

143. find the output of the following code.

```
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf ("BCA");
else
printf ("Btech");
}
```

a. BCA
b. Btech
c. 10
d. Error

Answer

144. What is the value of 587.671%2?

a. 0
b. 293
c. 293.835
d. Error

Answer

145. why is the main () in java static?

a. JVM can't create objects
b. main() can't be changed
c. Class has the access to main
d. Objects can directly access the main()

Answer

Problem 057 (ID: `SEC03_EBOOK_Q145`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
why is the main () in java
static?
```

Options

- a. JVM can’t create objects
- b. main() can’t be changed
- c. Class has the access to main
- d. Objects can directly

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

In Java, `public static void main(String[] args)` is declared `static` so that the Java Virtual Machine (JVM) can invoke it directly without needing to instantiate an object of the containing class (Option A).

140. find the output of the following code.

```
#include<iostream>
using namespace std;
int main()
{
int k=12,n=30;
k=(k>5 && n =4 ? 100 : 200);
cout<<"k="<<k;
}
```

a. k=1
b. k=0
c. k=100
d. error

Answer

141. find the output of the following code.

```
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf ("Hi %d", i);
}
}
```

a. HiHiHi123
b. Hi5
c. Hi4
d. Hi4Hi5

Answer

142. find the output of the following code.

```
#include<stdio.h>
void main()
{
int x=91;
X >>= 2;
printf("%d\n",x);
}
```

a. 182
b. 91
c. 22
d. 45

Answer

143. find the output of the following code.

```
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf ("BCA");
else
printf ("Btech");
}
```

a. BCA
b. Btech
c. 10
d. Error

Answer

144. What is the value of 587.671%2?

a. 0
b. 293
c. 293.835
d. Error

Answer

145. why is the main () in java static?

a. JVM can't create objects
b. main() can't be changed
c. Class has the access to main
d. Objects can directly access the main()

Answer

Problem 058 (ID: `SEC03_MOCK_Day04_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1.     #include
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<“ “;
Test t[5];
cout<< Test::getX();      }
```

Options

- 0 0
- 5 5
- 0 5
- a) Run time error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `0 5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `0 5`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 059 (ID: `SEC03_MOCK_Day04_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1.     #include
using namespace std;
class Point    {
Point()
{  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

Options

- Constructor called
- Compile time error
- Run time error
- Blank line

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Compile time error`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Compile time error`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 060 (ID: `SEC03_MOCK_Day04_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.    Which of the following does not interrupt the running process?
```

Options

- Timer interrupt
- Device
- Power failure
- Scheduler process

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Scheduler process`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Scheduler process`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 061 (ID: `SEC03_MOCK_Day04_Q11`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
1.    Which option is false about the final keyword?
a)   A) A final method cannot be overridden in its subclasses.
b)   B) A final class cannot be extended.
c)   C) A final class cannot extend other classes.
d)   D) A final method can be inherited.
```

Options

- A&B
- B&C
- C&D
- None of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `C&D`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `C&D`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 062 (ID: `SEC03_MOCK_Day04_Q18`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of this program?
main ()
{
if (5 < ’5’)
printf(“5”)
else
printf(“ NOT EQUAL TO 5.”)
}
```

Options

- ENQ
- 5
- I
- Not equal to 5

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `5`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 063 (ID: `SEC03_MOCK_Day04_Q19`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of the following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

Options

- 5
- 7
- 9
- 12

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `5`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 064 (ID: `SEC03_MOCK_Day04_Q20`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of the following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

Options

- 6 6 6
- 6 5 6
- 5 5 5
- 6 5 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `6 5 4`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `6 5 4`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 065 (ID: `SEC03_MOCK_Day04_Q23`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
T The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?
```

Options

- a) Singly linked list
- a) Doubly linked list
- a) Circular doubly linked list
- a) Array implementation of list

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `a)  Circular doubly linked list`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `a)  Circular doubly linked list`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 066 (ID: `SEC03_MOCK_Day04_Q25`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Let A be a square matrix of size nxn. Consider the following program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

Options

- a) The matrix A itself
- a) Transpose of matrix A
- a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- a) None of the above

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `a)  The matrix A itself`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `a)  The matrix A itself`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 067 (ID: `SEC03_MOCK_Day04_Q26`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

Options

- 10
- 4
- 6
- 7

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `10`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `10`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 068 (ID: `SEC03_MOCK_Day04_Q28`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

Options

- 5
- 6
- 7
- 8

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `7`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `7`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 069 (ID: `SEC03_MOCK_Day04_Q29`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Find the output of the following pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

Options

- 7
- 18
- 22
- 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `2`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `2`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 070 (ID: `SEC03_MOCK_Day04_Q30`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Find the output of the following pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

Options

- 31
- 11
- 42
- 30

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `30`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `30`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 071 (ID: `SEC03_MOCK_Day06_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "campus monk" End if j = p + k / 5 If (j not equal p) Print "campus monk" End if Print "campus monk"
```

Options

- 1 Times
- 2 Times
- 3 Times
- 4 Times

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `2 Times`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `2 Times`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 072 (ID: `SEC03_MOCK_Day06_Q09`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the following code. #include   void main() { int a = 10; if (a == 010) printf("BCA"); else printf("B.Tech"); }
```

Options

- BCA
- B.tech
- 10
- Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `B.tech`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `B.tech`.

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 073 (ID: `SEC03_MOCK_Day07_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Predict the output of the given pseudocode if the value of the number is 6: Read number k = 2 i = 2 while i <= number: k = k * i i = i + 1 end while write k
```

Options

- 1440.0
- 1340.0
- 1700.0
- 1560.0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1440.0`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `1440.0`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer