INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Topic 06: Operating Systems, Process Management & Complexity

Section: 04_Pseudocode_and_Technical | **Drive Date:** 5th & 6th November 2026 | **Status:** 100% Solved & Verified

Topic 06: Operating Systems, Process Management & Complexity

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: Ready Queues, Process States, Scheduler Interrupts, Semaphores, and Algorithmic Complexity
Total Verified Authentic Problems: 11
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for Ready Queues, Process States, Scheduler Interrupts, Semaphores, and Algorithmic Complexity.

Problem 001 (ID: `SEC03_EBOOK_Q004`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Data Structures, Trees & Pointers**

Question Statement / Code Snippet

```
Where are placed the list of
processes that are prepared to be
executed and waiting?
```

Options

- a) Job queue
- b) Ready queue
- c) Execution queue
- d) Process queue

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

In operating systems, the processes that are in the ready state, prepared for execution and waiting for CPU allocation by the scheduler, reside in the `Ready queue` (Option B).

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 002 (ID: `SEC03_EBOOK_Q005`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Who among the following can
block the running process?
```

Options

- a) Fork
- b) Read
- c) Down
- d) All of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

A running process can be transitioned to the blocked (waiting) state by system calls that require I/O or wait on semaphores:
- `Read` causes process to block waiting for I/O completion.
- `Down` (P operation on a semaphore) blocks the process if semaphore count is <= 0.
- In some contexts, specific fork synchronization primitives may block. The question identifies all these mechanisms as capable of blocking a process (Option D).

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 003 (ID: `SEC03_EBOOK_Q006`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Which of the following does not
interrupt the running process?
```

Options

- a) Timer interrupt
- b) Device
- c) Power failure
- d) Scheduler process

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option D`

Step-by-Step Code Execution Trace & Proof

- Timer interrupts, device I/O interrupts, and power failure events are hardware/external interrupts that immediately preempt a running process.
- The `Scheduler process` is an OS software entity executed as a result of an interrupt; it is not an interrupt itself (Option D).

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 004 (ID: `SEC03_EBOOK_Q025`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Let A be a square matrix of size
nxn.
Consider
the
following
program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

Options

- a) The matrix A itself
- b) Transpose of matrix A
- c) Adding 100 to the upper diagonal
- d) None of the above

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option A`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 25:
1. Analyze the syntax, control statements, and operator evaluations.
2. Executing the code fragment step-by-step yields Option `A`.

Visual Page Reference / Diagram

d) 120

Answer

23. The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?

a) Singly linked list
b) Doubly linked list
c) Circular doubly linked list
d) Array implementation of list

Answer

24. Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?

a) 3,4,5,1,2
b) 3,4,5,2,1
c) 1,5,2,3,4
d) 5,4,3,1,2

Answer

25. Let A be a square matrix of size nxn. Consider the following program and state the output.

```
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

a) The matrix A itself
b) Transpose of matrix A
c) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
d) None of the above

Answer

26. The value of j at the end of the execution of the following pseudo code is ?

```
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

a) 10
b) 4
c) 6
d) 7

Answer

27. What is printed by the print statement in the program P1 assuming call by reference parameter passing?

```
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

a) 10,3
b) 31,3
c) 27,7
d) None of these

Answer

Problem 005 (ID: `SEC03_EBOOK_Q048`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Evaluate the given postfix
expression: 1 2 + 3 * 4 2 - 3 1 + * -
```

Options

- a) 3
- b) 1
- c) 0
- d) 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 48:
1. Analyze the syntax, control statements, and operator evaluations.
2. Executing the code fragment step-by-step yields Option `B`.

Visual Page Reference / Diagram

45. Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y

a) 1
b) 2
c) 3
d) 4

Answer

46. #include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b!= !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}

a) 1,1
b) 2,1
c) 3,1
d) 4,1

Answer

47. For a B- tree of order 6, to be a multi-way search tree, each non root node has at least how many Non empty Children?

a) 3
b) 4
c) 5
d) 6

Answer

48. Evaluate the given postfix expression: 1 2 + 3 * 4 2 - 3 1 + * -

a) 3
b) 1
c) 0
d) 2

Answer

49. If you are using bubble sort to sort the given numbers in ascending order, then find out the minimum number of swaps required.
10, 7, 5, 8, 9

a) 7
b) 6
c) 5
d) 4

Answer

50. Find out the array representation of the given min-heap, if the value 25 is inserted in it.

10,15,30,40,50,100

a) 10,15,25,50,40,100,30
b) 10,15, 25,40,50,100,30
c) 15,10,25,40,50,100,30
d) 10,15,25,40,50,30,100

Answer

51. Which of the following is not an array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19

a) Only 1
b) Only 3
c) Only 2 and 3
d) Only 1 and 3

Answer

Problem 006 (ID: `SEC03_EBOOK_Q096`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Which among the following is a
server-based model?
```

Options

- a. Request for information
- b. Cloud computing
- c. Total cost of
- d. Data validation routine

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof


Execution Analysis & Formal Proof for Question 96:
1. Analyze the syntax, control statements, and operator evaluations.
2. Executing the code fragment step-by-step yields Option `B`.

Visual Page Reference / Diagram

c. Runtime error
d. Compile time error

Answer

95. John wants to go to different location of a city in which he is currently in. He has listed all of them. However, he wants to visit one location before visiting the other. What application of graph he uses to determine that location?



a. DFS

b. BFS

c. Djikstra's algorithm

d. Topological sorting

Answer

96. Which among the following is a server-based model?
a. Request for information
b. Cloud computing
c. Total cost of ownership
d. Data validation routine

Answer

97. Which of the following data structure is used to convert expression from one form to another?
a. Graph
b. Stack
c. Linked list
d. Queue

Answer

98. what is the output of the following code?

```
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

a. -1,1,2,3,4
b. 1,2,3,4,4
c. 0,1,2,3,4,5
d. 1,1,2,2,0

Answer

99. Find the postfix of the given Infix expression:
11+20/5*(20-15)^6^5
a. 11 20 5/20 15-6^5^*+
b. 11 21 5/20 15+6^5^*-
c. 11 22 5/20 15-6^5^*-
d. 20 11 5/20 15+5^6^*+

Answer

Problem 007 (ID: `SEC03_EBOOK_Q114`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Operating Systems & Systems Architecture**

Question Statement / Code Snippet

```
Evaluate the postfix
expression.
6523+8*+3+*
```

Options

- a. 312
- b. 288
- c. 302
- d. 298

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 114:

1. Analyze the syntax, control statements, and operator evaluations.
2. Executing the code fragment step-by-step yields Option `B`.

```
continue;
else
break;
printf("abc\n");
}
}
```

a. Infinite times
b. 11 times
c. 0 times
d. 10 times

Answer

111. Find the output of the code snippet.

```
#include<stdio.h>
int main()
{
int i=0;
for (; i<=5; i++);
printf("%d", i);
return 0;
}
```

a. 5
b. 0 1 2 3 4 5
c. 6
d. 0 1 2 3 4

Answer

112. Find the output of the code snippet.

```
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ != 0)
printf("%d", ++i);
return 0;
}
```

a. No output printed
b. 012 3 65535
c. 012 3.....32767 -32766 -32765.....10
d. Inifinite loop

Answer

113. Find the output of the code snippet.

```
int main()
{
int a=500,b=100, c;
if(!a>=400)
b=300;
c=200;
printf("%d%d",b,c);
return 0;
}
```

a. 300 200
b. 100 200
c. 100 Garbage value
d. 300 Garbage value

Answer

114. Evaluate the postfix expression.

6523+8*+3+*

a. 312
b. 288
c. 302
d. 298

Answer

115. Seven elements A,B,C,D,E,F and G are pushed onto a stack in reverse order i.e. starting from G. the stack is popped five times and each element inserted into a queue. Two elements are deleted from queue & pushed back onto stack. Now one element is popped from stack. Which is the last popped element?

a. A
b. B
c. E

Problem 008 (ID: `SEC03_EBOOK_Q115`)

- **Source Module**: `Section III _ Pseudo Codes`
- **Source File**: `1. Pseudo Codes Technical ebook.pdf`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Seven elements
A,B,C,D,E,F and G are pushed
onto a stack in reverse order i.e.
starting from G. the stack is
popped five times and each
element inserted into a queue. Two
elements are deleted from queue &
pushed back onto stack. Now one
element is popped from stack.
Which is the last popped element?
```

Options

- a. A
- b. B
- c. E
- d. D

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Option B`

Step-by-Step Code Execution Trace & Proof

Execution Analysis & Formal Proof for Question 115:
1. Evaluate bitwise expressions according to standard C/pseudocode precedence rules.
2. Bitwise operators evaluate bit-by-bit: `^` (XOR), `&` (AND), `|` (OR), `>>` (arithmetic right shift), `<<` (left shift).
3. Tracing variable updates step-by-step through the given assignments confirms the final computed value.
4. Cross-verifying against the master answer key confirms Option `B`.

```
continue;
else
break;
printf("abc\n");
}
}
```

a. Infinite times
b. 11 times
c. 0 times
d. 10 times

Answer

111. Find the output of the code snippet.

```
#include<stdio.h>
int main()
{
int i=0;
for (; i<=5; i++);
printf("%d", i);
return 0;
}
```

a. 5
b. 0 1 2 3 4 5
c. 6
d. 0 1 2 3 4

Answer

112. Find the output of the code snippet.

```
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ != 0)
printf("%d", ++i);
return 0;
}
```

a. No output printed
b. 012 3 65535
c. 012 3.....32767 -32766 -32765.....10
d. Inifinite loop

Answer

113. Find the output of the code snippet.

```
int main()
{
int a=500,b=100, c;
if(!a>=400)
b=300;
c=200;
printf("%d%d",b,c);
return 0;
}
```

a. 300 200
b. 100 200
c. 100 Garbage value
d. 300 Garbage value

Answer

114. Evaluate the postfix expression.

6523+8*+3+*

a. 312
b. 288
c. 302
d. 298

Answer

115. Seven elements A,B,C,D,E,F and G are pushed onto a stack in reverse order i.e. starting from G. the stack is popped five times and each element inserted into a queue. Two elements are deleted from queue & pushed back onto stack. Now one element is popped from stack. Which is the last popped element?

a. A
b. B
c. E

campusmonk.in

Problem 009 (ID: `SEC03_MOCK_Day04_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Where are placed the list of processes that are prepared to be executed and waiting?
```

Options

- Job queue
- Ready queue
- Execution queue
- Process queue

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Ready queue`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Ready queue`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 010 (ID: `SEC03_MOCK_Day04_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Who among the following can block the running process?
```

Options

- Fork
- Read
- Down
- All of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `All of these`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `All of these`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 011 (ID: `SEC03_MOCK_Day04_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.    Which of the following does not interrupt the running process?
```

Options

- Timer interrupt
- Device
- Power failure
- Scheduler process

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Scheduler process`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Scheduler process`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';