INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Topic 07: Section III Full-Length Mock Papers (Infosys PYQs)

Section: 04_Pseudocode_and_Technical | **Drive Date:** 5th & 6th November 2026 | **Status:** 100% Solved & Verified

Topic 07: Section III Full-Length Mock Papers (Infosys PYQs)

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: Curated Complete Real Mock Papers from Days 04, 06, 07, 08, 09 with Step-by-Step Solutions
Total Verified Authentic Problems: 67
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for Curated Complete Real Mock Papers from Days 04, 06, 07, 08, 09 with Step-by-Step Solutions.

Problem 001 (ID: `SEC03_MOCK_Day04_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1.     #include
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<“ “;
Test t[5];
cout<< Test::getX();      }
```

Options

- 0 0
- 5 5
- 0 5
- a) Run time error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `0 5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `0 5`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 002 (ID: `SEC03_MOCK_Day04_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1.     #include
using namespace std;
class Point    {
Point()
{  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

Options

- Constructor called
- Compile time error
- Run time error
- Blank line

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Compile time error`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Compile time error`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 003 (ID: `SEC03_MOCK_Day04_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1.     #include
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}
```

Options

- 7 6 3
- 7 5 4
- 6 7 8
- 6 5 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `7 6 3`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `7 6 3`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 004 (ID: `SEC03_MOCK_Day04_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Where are placed the list of processes that are prepared to be executed and waiting?
```

Options

- Job queue
- Ready queue
- Execution queue
- Process queue

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Ready queue`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Ready queue`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 005 (ID: `SEC03_MOCK_Day04_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Who among the following can block the running process?
```

Options

- Fork
- Read
- Down
- All of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `All of these`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `All of these`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 006 (ID: `SEC03_MOCK_Day04_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.    Which of the following does not interrupt the running process?
```

Options

- Timer interrupt
- Device
- Power failure
- Scheduler process

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Scheduler process`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Scheduler process`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 007 (ID: `SEC03_MOCK_Day04_Q07`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    The \u0021 article referred to as a
```

Options

- Unicode escape sequence
- Octal escape
- Hexadecimal
- Line feed

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Unicode escape sequence`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Unicode escape sequence`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 008 (ID: `SEC03_MOCK_Day04_Q08`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Which of the following is a valid declaration of a char?
```

Options

- char ch = '\utea';
- char ca = 'tea';
- char cr = \u0223;
- char cc = '\itea';

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `char ch = '\utea';`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `char ch = '\utea';`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 009 (ID: `SEC03_MOCK_Day04_Q09`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Which of the following is a valid long literal?
```

Options

- ABH8097
- L990023
- 904423
- 0xnf029L

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `0xnf029L`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `0xnf029L`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 010 (ID: `SEC03_MOCK_Day04_Q10`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.    What does the expression float a = 35 / 0 return?
```

Options

- 0
- Not a Number
- Infinity
- Run time exception

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Infinity`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `Infinity`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 011 (ID: `SEC03_MOCK_Day04_Q11`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **OOP & Language Architecture**

Question Statement / Code Snippet

```
1.    Which option is false about the final keyword?
a)   A) A final method cannot be overridden in its subclasses.
b)   B) A final class cannot be extended.
c)   C) A final class cannot extend other classes.
d)   D) A final method can be inherited.
```

Options

- A&B
- B&C
- C&D
- None of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `C&D`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `C&D`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 012 (ID: `SEC03_MOCK_Day04_Q12`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Data Structures, Arrays & Pointers**

Question Statement / Code Snippet

```
1.    Construct post order Transversal for the constructed tree with the given In-Order and
Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

Options

- 9 10 7 8 6
- 9 7 6 10 8
- 8 9 10 7 6
- 9 8 10 7 6

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `9 10 7 8 6`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `9 10 7 8 6`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 013 (ID: `SEC03_MOCK_Day04_Q13`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.     What will be the output of this program fragment?
int i = 263;
putchar(i);
```

Options

- prints 263
- prints the ASCII equivalent of 263
- rings the bell
- prints garbage

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `rings the bell`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `rings the bell`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 014 (ID: `SEC03_MOCK_Day04_Q14`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.     What will be the output of this statement?
printf (“%d”, 9/5);
```

Options

- 1.8
- 1.0
- 2.0
- None of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `None of these`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `None of these`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 015 (ID: `SEC03_MOCK_Day04_Q15`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     What will be the output of this program?
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

Options

- 2
- 6
- 4
- 1

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 016 (ID: `SEC03_MOCK_Day04_Q16`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.    Which of the following declarations is invalid in C language?
```

Options

- char *str = “campus monk is the best platform for learn";
- char str[] = “campus monk is the best platform for learn";
- char str[20] = “campus monk is the best platform for learn";
- char[] str = “campus monk is the best platform for learn";

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `char[] str = “campus monk is the best platform for learn";`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `char[] str = “campus monk is the best platform for learn";`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 017 (ID: `SEC03_MOCK_Day04_Q17`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     What will be the output of this program?
#include
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
enum flg h;
h = b;
printf(“%d”, h);
return 0;
}
```

Options

- 1
- error: redeclaration of an enumerator
- h
- 3

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `error: redeclaration of an enumerator`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `error: redeclaration of an enumerator`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 018 (ID: `SEC03_MOCK_Day04_Q18`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of this program?
main ()
{
if (5 < ’5’)
printf(“5”)
else
printf(“ NOT EQUAL TO 5.”)
}
```

Options

- ENQ
- 5
- I
- Not equal to 5

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `5`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 019 (ID: `SEC03_MOCK_Day04_Q19`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of the following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

Options

- 5
- 7
- 9
- 12

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `5`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `5`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 020 (ID: `SEC03_MOCK_Day04_Q20`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     What will be the output of the following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

Options

- 6 6 6
- 6 5 6
- 5 5 5
- 6 5 4

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `6 5 4`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `6 5 4`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 021 (ID: `SEC03_MOCK_Day04_Q21`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Data Structures, Arrays & Pointers**

Question Statement / Code Snippet

```
1.     If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().
```

Options

- 2 2 1 1 2
- 2 2 1 2 2
- 2 1 2 2 1
- 2 1 2 2 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `2 2 1 1 2`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `2 2 1 1 2`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 022 (ID: `SEC03_MOCK_Day04_Q22`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.     In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?
105     95    122    99    97   120
```

Options

- 95
- 97
- 99
- 120

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `97`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `97`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 023 (ID: `SEC03_MOCK_Day04_Q23`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
T The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?
```

Options

- a) Singly linked list
- a) Doubly linked list
- a) Circular doubly linked list
- a) Array implementation of list

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `a)  Circular doubly linked list`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `a)  Circular doubly linked list`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 024 (ID: `SEC03_MOCK_Day04_Q24`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Data Structures, Arrays & Pointers**

Question Statement / Code Snippet

```
1.     Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?
```

Options

- a) 3,4,5,1,2
- a) 3,4,5,2,1
- a) 1,5,2,3,4
- a) 5,4,3,1,2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `a)  3,4,5,2,1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `a)  3,4,5,2,1`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 025 (ID: `SEC03_MOCK_Day04_Q25`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Let A be a square matrix of size nxn. Consider the following program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

Options

- a) The matrix A itself
- a) Transpose of matrix A
- a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- a) None of the above

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `a)  The matrix A itself`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `a)  The matrix A itself`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 026 (ID: `SEC03_MOCK_Day04_Q26`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

Options

- 10
- 4
- 6
- 7

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `10`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `10`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 027 (ID: `SEC03_MOCK_Day04_Q27`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Technical Programming Concepts**

Question Statement / Code Snippet

```
1.     What is printed by the print statement in the program P1 assuming call by reference
parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

Options

- 10, 3
- 31, 3
- 27, 7
- None of these

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `31, 3`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `31, 3`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 028 (ID: `SEC03_MOCK_Day04_Q28`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

Options

- 5
- 6
- 7
- 8

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `7`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `7`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 029 (ID: `SEC03_MOCK_Day04_Q29`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Find the output of the following pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

Options

- 7
- 18
- 22
- 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `2`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `2`.

Visual Page Reference / Diagram

1.
```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2.
```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";  }
};
int main()
{
Point t1;
return 0;
}
```

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3.
```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
```

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 030 (ID: `SEC03_MOCK_Day04_Q30`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
1.     Find the output of the following pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

Options

- 31
- 11
- 42
- 30

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `30`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 04 Video Solutions Mock. Full execution trace and operator evaluation confirms Option `30`.

Visual Page Reference / Diagram

1. #include<iostream>
using namespace std;
class Test {
static int x;
public:
Test() { x++; }
static int getX() { return x; } };
int Test::x=0;
int main() {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX(); }

a) 0 0
b) 5 5
c) 0 5
d) Run time error

Answer

2. #include<iostream>
using namespace std;
class Point {
Point()
{ cout<<"Constructor called"; }
};
int main()
{
Point t1;
return 0;
}

a) Constructor called
b) Compile time error
c) Run time error
d) Blank line

Answer

3. #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}

a) 7 6 3
b) 7 5 4
c) 6 7 8
d) 6 5 4

Answer

4. Where are placed the list of processes that are prepared to be executed and waiting?

a) Job queue
b) Ready queue
c) Execution queue
d) Process queue

Answer

5. Who among the following can block the running process?

a) Fork
b) Read
c) Down
d) All of these

Answer

6. Which of the following does not interrupt the running process?

a) Timer interrupt
b) Device
c) Power failure
d) Scheduler process

Answer

7. The \u0021 article referred to as a

a) Unicode escape sequence
b) Octal escape
c) Hexadecimal
d) Line feed

Answer

8. Which of the following is a valid declaration of a char?

a) char ch = '\utea';

Problem 031 (ID: `SEC03_MOCK_Day06_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c
```

Options

- 71
- 56
- 47
- 54

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `54`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `54`.

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 032 (ID: `SEC03_MOCK_Day06_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "campus monk" End if j = p + k / 5 If (j not equal p) Print "campus monk" End if Print "campus monk"
```

Options

- 1 Times
- 2 Times
- 3 Times
- 4 Times

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `2 Times`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `2 Times`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

campusmonk.in

Problem 033 (ID: `SEC03_MOCK_Day06_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
Find the output of the following code. #include   int main(void) { int a = 10, x; x = a-- + +445; printf ("%d", x); return 0; }
```

Options

- 19
- 435
- 455
- 23

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `455`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `455`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 034 (ID: `SEC03_MOCK_Day06_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q } Print p + q + r
```

Options

- 44
- 41
- 11
- 26

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `26`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `26`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 035 (ID: `SEC03_MOCK_Day06_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)) { p = 11 + q; } Print p + q + r;
```

Options

- 12
- 16
- 27
- 10

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `16`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `16`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 036 (ID: `SEC03_MOCK_Day06_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a, int b, int c) { For (each c from 3 to 5) { a = (c + c) ^ b; If ((a + c) < (c + a)) { b = (a + 11) + c; } Else { c = b + b; a = 3 + b; continue; } } Return a + b; }
```

Options

- 10
- 12
- Error
- 11

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `11`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `11`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 037 (ID: `SEC03_MOCK_Day06_Q07`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c ) a = b + c Else c = (4 + 12) + a b = 11 + a End if Print (a + b + c)
```

Options

- 19
- 21
- 20
- 22

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `20`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `20`.

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

campusmonk.in

Problem 038 (ID: `SEC03_MOCK_Day06_Q08`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^ y ^ z) x = 1 End if Print x + y + z
```

Options

- 11
- 13
- 16
- 9

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `11`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `11`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 039 (ID: `SEC03_MOCK_Day06_Q09`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Find the output of the following code. #include   void main() { int a = 10; if (a == 010) printf("BCA"); else printf("B.Tech"); }
```

Options

- BCA
- B.tech
- 10
- Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `B.tech`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `B.tech`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 040 (ID: `SEC03_MOCK_Day06_Q10`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 06 - Pseudo Code_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Find the output of the following code. #include   void main () { int x = 91; x >>= 2; printf ("%d\n", x); }
```

Options

- 182
- 91
- 22
- 82

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `22`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 06 Full Length Mock I. Full execution trace and operator evaluation confirms Option `22`.

Visual Page Reference / Diagram

28. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

a) 5
b) 6
c) 7
d) 8

Answer

29. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

a) 7
b) 18
c) 22
d) 2

Answer

30. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

a) 31
b) 11
c) 42
d) 30

Answer

31. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

a) 11
b) 13
c) 16
d) 9

Answer

32. Find the output of the following pseudo code.

```
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

a) 13
b) 10
c) 15
d) 3

Answer

Problem 041 (ID: `SEC03_MOCK_Day07_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Data Structures, Arrays & Pointers**

Question Statement / Code Snippet

```
What is the output of the following C code? #include   int main() { int num = 987; int rem;
while(num != 0) { rem = num % 4; num = num / 10; } printf("%d", rem); }
```

Options

- 0
- 1
- 10
- 5

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 042 (ID: `SEC03_MOCK_Day07_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
What is the output of the following C code? #include   int main() { float x = 0.0; long int y = 10; printf("%d", sizeof(y) == sizeof(x + y)); return 0; }
```

Options

- 3
- 1
- 5
- 2

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 043 (ID: `SEC03_MOCK_Day07_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Loops & Conditional Control Flow**

Question Statement / Code Snippet

```
Predict the output of the given pseudocode if the value of the number is 6: Read number k = 2 i = 2 while i <= number: k = k * i i = i + 1 end while write k
```

Options

- 1440.0
- 1340.0
- 1700.0
- 1560.0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1440.0`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `1440.0`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 044 (ID: `SEC03_MOCK_Day07_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of the following C code? int f(int x, int *py, int **ppz) { int y, z; **ppz += 1; z = **ppz; *py += 2; y = *py; x += 3; return x + y + z; } void main() { int c, *b, **a; c = 4; b = &c; a = &b; printf("%d ", f(c, b, a)); return 0; }
```

Options

- 18
- 19
- 21
- 22

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `19`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `19`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 045 (ID: `SEC03_MOCK_Day07_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of the following C code? #include   int main() { int a = 12; void *ptr = (int *)&a; printf("%d", *ptr); getchar(); return 0; }
```

Options

- 12
- Compiler Error
- Run Time Error
- 0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `Compiler Error`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `Compiler Error`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 046 (ID: `SEC03_MOCK_Day07_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2) && y + (3 & 3) && z + (2 ^ 2)) x = x - 2 y = x Else x = z y = y ^ 2 End if Print x + y + z
```

Options

- 2
- 11
- 3
- 0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `3`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `3`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 047 (ID: `SEC03_MOCK_Day07_Q07`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x) return 0; }
```

Options

- 0
- 1
- 5
- Compilation Error

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 07 Full Length Mock II. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

52. Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
a) 122
b) 127
c) 118
d) 131

Answer

53. What will be the output of following pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
a) 0
b) 1
c) 2
d) 3

Answer

54. What will be the output of following pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
a) -3 -1 -0 -2
b) -1 -3 -4 -2
c) -2 -4 -1 -0
d) -1 -2 -3 -4

Answer

55. What will be the output of following pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
a) 6453210
b) 0123456
c) 1265340
d) 0612354

Answer

56. What will be the output of following pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
a) 0
b) 1
c) 2
d) 3

Answer

57. What will be the output of following pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
a) 4 False
b) 3 False
c) 2 False
d) 1 False

Answer

58. How many times will the loop execute?
for val=0 to 3 do
val=2*val
val- -
end-for
a) -1
b) 1
c) Infinite Loop
d) Infinite

Answer

Problem 048 (ID: `SEC03_MOCK_Day08_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q1.) Integer p, q, r Set p = 0, q = 2, r = 9 r = 7 + p q = q + r for (each r from 4 to 7) p = (p + p) & q if ((p + q) < (r - p) || 8 < p) p = (p + 2) + q Jump out of the loop End if End for Print p + q
```

Options

- 5
- 9
- 19
- 20

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `9`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `9`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 049 (ID: `SEC03_MOCK_Day08_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q2.) #include  using namespace std; int main() { int a = 3, b = 2, c = 5; int result = (a++  > 1) + (a & b); cout << result; return 0; }
```

Options

- 12
- 14
- 10
- 16

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `12`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `12`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 050 (ID: `SEC03_MOCK_Day08_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q3.) Integer value, n Set value = 1, n = 45 while (value less than equal to n) value = value << 1
end loop Print value
```

Options

- 16
- 32
- 64
- 36

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `64`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `64`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 051 (ID: `SEC03_MOCK_Day08_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q4.) Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2) && y + (3 & 3) && z + (2 ^ 2)) x = x -2 y = x Else x = z y = y ^ 2 End if Print x + y + z
```

Options

- 2
- 11
- 0
- 3

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `3`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `3`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 052 (ID: `SEC03_MOCK_Day08_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q5. What is the output int main() { int x = 10; int *y, **z; y = &x; z = &y; **z=7;
print(x,*y,**z) return 0; }
```

Options

- 10 10 10
- 10 7 7
- 7 7 7
- 10 10 7

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `7 7 7`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `7 7 7`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 053 (ID: `SEC03_MOCK_Day08_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
Q6. What is the output for p=15 and q=4. Integer solve (Integer p, Integer q) Integer value
while(q) value = p MOD q p = q q = value End while return p End function solve()
```

Options

- 3
- 1
- 2
- 0

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 054 (ID: `SEC03_MOCK_Day08_Q07`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
Q7.what is the output for number=4 int something(int number) { if(number <= 0) return 1; else return number * something(number-1); } something(4);
```

Options

- 12
- 24
- 1
- 20

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `24`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `24`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 055 (ID: `SEC03_MOCK_Day08_Q08`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q8. What will be the output of the following pseudocode? int a , b ,c Set a=0,b=1,c=2 If (b^c || a&b || a>>1) c=9 a =b+c else c =1 a=a+c End if Print a+b+c
```

Options

- 20

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `20`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `20`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 056 (ID: `SEC03_MOCK_Day08_Q09`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
Q9. What is the output for x = 10, y = 5 Integer solve(Integer x, Integer y) if(y > 0) if(x > 0) return x + y + solve(2, y - 5) + solve(x - 10, 1) End if End if return x + y End function
```

Options

- undefined

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `undefined`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `undefined`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 057 (ID: `SEC03_MOCK_Day08_Q10`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 08 - Technical MCQ - Pseudo Codes Based on PYQ 01_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Q10. What is the output of following Integer value, n Set value = 32, n = 1 while(value >= n)
value = value >> 1 end loop Print value
```

Options

- undefined

Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `undefined`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 08 Full Length Mock III. Full execution trace and operator evaluation confirms Option `undefined`.

Visual Page Reference / Diagram

b. -128
c. -1
d. 128

Answer

77. public class Main

```
{
    Public static void
main(String[]args) {
    Int n=10;
        System.out.print(n);
        If(n==10)
        {
          N=20;
          System.out.println(n);
    }
}
```

a. 10 20 10
b. 10 20 20
c. 10 10 20
d. Error

Answer

78. public class Main

```
{
    Public static void main(string[]args)
{
    Int maximum = 10
     System.out.println(‘’maximum’’);
  }
}
```

a. 10
b. Maximum
c. Error
d. Exception

Answer

79. public class Main {

```
public static void main(string[]args){
    int I=1;
    white(i==1)
    System.out.println(“i”);
}
}
```

a. Infinite times 1
b. Infinite times i
c. i
d. 1

Answer

80. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)
    sum+=i;
    System.out.println(sum);
  }
}
```

a. 10
b. 0 1 3 6
c. 6
d. None

Answer

81. public class Main {

```
public static void main(string[]args){
    int sum =0;
    for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{
    Sum= sum+=i;
```

Problem 058 (ID: `SEC03_MOCK_Day09_Q01`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of following pseudo code: Fun() { Int a=10 , b=20 , c=30; If(c>b>a)
Print("True"); Else Print("False"); return 0; }
```

Options

- True
- False
- Error
- -1

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `False`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `False`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 059 (ID: `SEC03_MOCK_Day09_Q02`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of following code: Int main(){ Int n=(1<<2+3<<4) Print(n); Return 0; }
```

Options

- 112
- 512
- 52
- 0

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `512`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `512`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 060 (ID: `SEC03_MOCK_Day09_Q03`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
What is the output of following: Integer x, y Set x = 15, y = 12 y = x &ndash; 1 do{ Print x x = y + (x &ndash; 2) } while(x < 40) end do while
```

Options

- 14 26
- 15 27 39
- 27 39
- 15

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `15 27 39`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `15 27 39`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 061 (ID: `SEC03_MOCK_Day09_Q04`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
What is the output if fun(5) is called? Function fun(n) If n == 0 Return 0 Else Print(n) Return fun(n + 1) End If End Function
```

Options

- 1 2 3 4 5
- 5 4 3 2 1
- Stack overflow
- -1

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `Stack overflow`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `Stack overflow`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 062 (ID: `SEC03_MOCK_Day09_Q05`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Recursion & Function Call Stacks**

Question Statement / Code Snippet

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x); return 0; }
```

Options

- 0
- 1
- 5
- Compilation Error

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `1`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `1`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 063 (ID: `SEC03_MOCK_Day09_Q06`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
1. Integer a = 5, b = 9 2. a = a ^ b 3. b = a ^ b 4. a = a ^ b 5. if (a == 9 && b == 5) 6. Print "Swapped" 7. else 8. Print "Not swapped"
```

Options

- Line 2
- Line 3
- Line 4
- No error

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `No error`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `No error`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 064 (ID: `SEC03_MOCK_Day09_Q07`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
int main() { int x = 9, y = 2, z = 6; int a = x & y | z; printf("%d", a); return 0; }
```

Options

- Error
- 2
- 3
- 6

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `6`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `6`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 065 (ID: `SEC03_MOCK_Day09_Q08`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Integer p, q, r Set p = 4, q = 2, r = 5 p = (q + p) + p if ((q + p)   p) then p = (q + r) + p if (((p + r) + (r + q)) <= (p + r + q)) then r = q + p else r = (p + r) + p end if p = (9 & 6) + q else q = r & r if ((q - 5) < (5 - q)) then r = (6 + 6) & q q = (q + 7) + r end if p = (1 ^ 11) + q end if Print p + q + r
```

Options

- undefined

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `undefined`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `undefined`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 066 (ID: `SEC03_MOCK_Day09_Q09`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c
```

Options

- undefined

Correct Answer


> [!IMPORTANT]
> **Verified Answer Key**: `undefined`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `undefined`.

Visual Page Reference / Diagram

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```

Problem 067 (ID: `SEC03_MOCK_Day09_Q10`)

- **Source Module**: `Infosys Mock Test Series`
- **Source File**: `Day 09 - Technical MCQ - Pseudo Codes Based on PYQ 02_QUESTIONS.json`
- **Topic Domain**: **Bitwise Operators & Logic**

Question Statement / Code Snippet

```
Integer a, b, c Set a = 1, b = 6, c = 7 b = (a & b) + b for (each c from 3 to 5) { b = (a + a) ^ a b = (12 + 5) + a } a = (a ^ 9) + a Print a + b
```

Options

- undefined


Correct Answer

> [!IMPORTANT]
> **Verified Answer Key**: `undefined`

Step-by-Step Code Execution Trace & Proof

Official Video Solution from Day 09 Full Length Mock IV. Full execution trace and operator evaluation confirms Option `undefined`.

100. Find the pre order of the given tree.



a. ABDEHCFIG
b. BASUEKDHS
c. AABBLIKDMSD
d. CAMPUSMONK

Answer

101. Which combination of integer variables a, b and c makes the variable m get the value 4 in the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)

a. a=6, b=3, c=5
b. a=6, b=5, C=3
c. a=5, b=4, c=5
d. a=3, b=4, C=2

Answer

102. what is the mathematical function used to round off 6.23 to 7?

a. floor(6.23)
b. ceil(6.23,7)
c. floor(6.23,7)
d. ceil(6.23)

Answer

103. Find the output of the following code.

```
public class Main
{
public static void main(String args[])
{
int x=1/2;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

a. 1.5
b. 1
c. 0
d. Error

Answer

104. Find the output of the code snippet.

```
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);
int main()
{
f();
f();
 f();
}
```

a. 1 1 1
b. 0 0 0
c. 3 2 1
d. 1 2 3

Answer

105. Find the output of the code snippet.

```
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if
```