Topic 02: Loops, Iteration & Conditional Control Flow

🎯 Infosys Systems Engineer (SE) | 🗓️ 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: For Loops, While Loops, Do-While Iteration, Chained If-Else, and Switch-Case Fallthrough
Total Verified Authentic Problems: 105
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for For Loops, While Loops, Do-While Iteration, Chained If-Else, and Switch-Case Fallthrough.

Problem 001 • Core Practice

🔥 MUST-SOLVE

ID: SEC03_EBOOK_Q003 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
 }
```

- a) 7 6 3
- b) 7 5 4
- c) 6 7 8
- d) 6 5 4

✓ **Verified Answer:** Option A

Problem 002 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q006 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following does not
interrupt the running process?
```

- a) Timer interrupt
- b) Device
- c) Power failure
- d) Scheduler process

✓ **Verified Answer:** Option D

Problem 003 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q010 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** Option C

Problem 004 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q012 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Construct post order Transversal
for the constructed tree with the
given
In-Order
and
Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- a) 9 10 7 8 6
- b) 9 7 6 10 8
- c) 8 9 10 7 6
- d) 9 8 10 7 6

✓ **Verified Answer:** Option A

Problem 005 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q016 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following declarations
is invalid in C language?
```

- a) char *str = “campus monk is the
- b) char str[] = “campus monk is the
- c) char str[20] = “campus monk is the
- d) char[] str = “campus monk is the

✓ **Verified Answer:** Option D

Problem 006 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q018 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < '5')
        printf("5")
 else
        printf(" NOT EQUAL TO 5.")
}
```

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

✓ **Verified Answer:** Option B

Problem 007 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q019 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- a) 5
- b) 7
- c) 9
- d) 12

✓ **Verified Answer:** Option A

Problem 008 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q020 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

✓ **Verified Answer:** Option D

Problem 009 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q021 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of operations are
performed on a stack, the sequence
of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Pop(),
Push(2), Pop().
```

- a) 2 2 1 1 2
- b) 2 2 1 2 2
- c) 2 1 2 2 1
- d) 2 1 2 2 2

✓ **Verified Answer:** Option A

Problem 010 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q023 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The concatenation of two lists is to
be performed in O(1) time. Which of
the following implementation of a
list should be used?
```

- a) Singly linked list
- b) Doubly linked list
- c) Circular doubly linked list
- d) Array implementation of list

✓ **Verified Answer:** Option C

Problem 011 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q025 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Let A be a square matrix of size
nxn.
Consider
the
following
program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp - C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- b) Transpose of matrix A
- c) Adding 100 to the upper diagonal
- d) None of the above

✓ **Verified Answer:** Option A

Problem 012 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q026 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** Option A

Problem 013 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** Option C

Problem 014 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q029 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a) 7
- b) 18
- c) 22
- d) 2

✓ **Verified Answer:** Option D

Problem 015 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q030 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- a) 31
- b) 11
- c) 42
- d) 30

✓ **Verified Answer:** Option D

Problem 016 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q031 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a) 11
- b) 13
- c) 16
- d) 9

✓ **Verified Answer:** Option A

Problem 017 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q032 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

- a) 13
- b) 10
- c) 15
- d) 3

✓ **Verified Answer:** Option A

Problem 018 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q033 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code:
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

- a) 22
- b) 24
- c) 26
- d) 28

✓ **Verified Answer:** Option A

Problem 019 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q037 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a - 1
else
a = b + 1
b = a - 1
a = a - 1
end if
print a
```

- a) 3
- b) 5
- c) 10
- d) 11

✓ **Verified Answer:** Option C

Problem 020 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q038 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

- a) 7
- b) 4
- c) 6
- d) 8

✓ **Verified Answer:** Option D

Problem 021 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q039 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Consider a stack of integers. The
stack is allocated 7 memory cells:
STACK: 12, 34, 66, 79, _, _, _.
Now
consider
the
following
operations:
A. PUSH (STACK, 8)
B. PUSH (STAC, 54)
C. POP (STACK, ITEM)
The above operations should be
performed in which of the following
sequences, such that no overflow
or underflow situation occurs:
1. B→ A→ C
2. A→ B→ C
3. C→ B→ A
```

- a) Only 1
- b) Any of them
- c) Only 2
- d) Only 3

✓ **Verified Answer:** Option B

Problem 022 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q040 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** Option A

Problem 023 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q042 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** Option C

Problem 024 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q044 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option C

Problem 025 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q045 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option A

Problem 026 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q047 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For a B- tree of order 6, to be a
multi-way search tree, each non
root node has at least how many
Non empty Children?
```

- a) 3
- b) 4
- c) 5
- d) 6

✓ **Verified Answer:** Option A

Problem 027 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q049 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

- a) 7
- b) 6
- c) 5
- d) 4

✓ **Verified Answer:** Option B

Problem 028 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q052 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

- a) 122
- b) 127
- c) 118
- d) 131

✓ **Verified Answer:** Option A

Problem 029 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q053 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 030 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q054 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display - y
end-for
```

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

✓ **Verified Answer:** Option D

Problem 031 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q055 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

✓ **Verified Answer:** Option B

Problem 032 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q056 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 033 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q057 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

✓ **Verified Answer:** Option D

Problem 034 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q058 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

✓ **Verified Answer:** Option C

Problem 035 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q059 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option B

Problem 036 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q060 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

✓ **Verified Answer:** Option A

Problem 037 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q061 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option C

Problem 038 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q062 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i++- -I then do
display i
end - if
end - for
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 039 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q063 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

- a. 32
- b. 34
- c. 36
- d. 38

✓ **Verified Answer:** Option A

Problem 040 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q069 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer p,q,r
Set p=9, q=6, r=8
For (each I from 3 to 6)
p= (p^r)+q
if((3+p+r)<(r-q))
p= 1+q
q= 2+q
End if
End for
Print p+q
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** Option Ans

Problem 041 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q071 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

- a. 0
- b. 1
- c. 2
- d. 3

Verified Answer: Option B

Problem 042 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q072 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

- a. 10
- b. 11
- c. 12
- d. 13

Verified Answer: Option C

Problem 043 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q073 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

- a. 10
- b. 30
- c. 50
- d. 70

✓ **Verified Answer:** Option B

Problem 044 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q074 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

- a. Error
- b. Infinity
- c. Exception
- d. Zero

✓ **Verified Answer:** Option A

Problem 045 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q080 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

Verified Answer: Option A

Problem 046 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q081 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** Option D

Problem 047 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q082 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++ ⩽ 10;)

System.out.printIn(i);

  }
}
```

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

✓ **Verified Answer:** Option B

Problem 048 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q086 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

✓ **Verified Answer:** Option B

Problem 049 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q087 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

- a. 62
- b. 65
- c. 75
- d. 75

✓ **Verified Answer:** Option B

Problem 050 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q088 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x⩾y AND x⩾z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z⩾y AND z⩾x)
Print z
End if
```

- a. Find out the largest number
- b. Find out the smallest

✓ **Verified Answer:** Option A

Problem 051 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q089 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** Option A

Problem 052 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q090 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** Option B

Problem 053 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q091 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

- a. 5
- b. 7
- c. 9
- d. 11

✓ **Verified Answer:** Option B

Problem 054 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q092 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

✓ **Verified Answer:** Option A

Problem 055 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q095 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

        /     \
1
5
   /               \
2                   4
```

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

✓ **Verified Answer:** Option C

Problem 056 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q097 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following data
structure is used to convert
expression from one form to
another?
```

- a. Graph
- b. Stack
- c. Linked list
- d. Queue

✓ **Verified Answer:** Option B

Problem 057 • Core Practice CORE SE

ID: SEC03_EBOOK_Q098 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

✓ **Verified Answer:** Option A

Problem 058 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q106 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a. 7
- b. 8
- c. 22
- d. 12

✓ **Verified Answer:** Option D

Problem 059 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q108 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet. int main()
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

- a. 24
- b. 25
- c. 100
- d. Depends on compiler

✓ **Verified Answer:** Option C

Problem 060 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q109 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find out how many times
will “hi” be printed.
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

- a. 1 time
- b. 2019 times
- c. 2021 times
- d. 2020 times

✓ **Verified Answer:** Option D

Problem 061 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q110 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
how many times will "abc"
be printed.
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)


continue;
else
break;
printf("abc\n");
}
}
```

- a. Infinite times
- b. 11 times
- c. 0 times
- d. 10 times

✓ **Verified Answer:** Option C

Problem 062 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q111 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
int i=0;
for (; i⩽5; i++);
printf("%d", i);
return 0;
}
```

- a. 5
- b. 0 1 2 3 4 5
- c. 6
- d. 0 1 2 3 4

✓ **Verified Answer:** Option C

Problem 063 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q112 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ ≠ 0)
printf("%d", ++i);
return 0;
}
```

- a. No output printed
- b. 012 3 65535
- c. 012 3.....32767 -32766 -
- d. Inifinite loop

✓ **Verified Answer:** Option D

Problem 064 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q116 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of
operations are performed on a
stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Push(2),
Pop().
```

- a. 2 2 1 1 2
- b. 2 2 1 2 2
- c. 2 1 2 2 1
- d. 2 1 2 2 1

✓ **Verified Answer:** Option B

Problem 065 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q117 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Consider the following
operations performed on a stack of
size 5. Push(a), Pop(), Push(b),
Push(c), Pop(), Push(d), Pop(),
Pop(), Push(e) Which of the
following statements is correct?
```

- a. Underflow occurs
- b. Stack operations are performed
- c. Overflow occurs
- d. None

✓ **Verified Answer:** Option B

Problem 066 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q120 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
relation is correct for a binary
search tree?
```

- a. Parent node> Right node>
- b. Right node> Parent node>
- c. Right node> Left node>
- d. Parent node> Left

✓ **Verified Answer:** Option B

Problem 067 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q122 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
pseudo code. Integer a, b, c
Set a=5, b=3
For( each c from b to a)
If (a)
a=a-1 n
End if
If(b)
b =b-1
End if
End for
Print a+b
```

- a. 4
- b. 6
- c. 8
- d. 1

✓ **Verified Answer:** Option A

Problem 068 • Core Practice CORE SE

ID: SEC03_EBOOK_Q127 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT
EQUALS 0) and (b NOT EQUALS
0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If
```

- a. Success
- b. Fail
- c. 0
- d. 1

✓ **Verified Answer:** Option B

Problem 069 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q128 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if


Print x+y+z
```

- a. 31
- b. 11
- c. 42
- d. 30

✓ **Verified Answer:** Option D

Problem 070 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q133 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main(void)
{
int i;
for(int j=0; j<1; j++)
{
if(i==0,1)
{
printf(“Be a programmer”);
}
else
{
printf(“Learning c”);
}
}
printf(“%d\n”, ++i);
return 0;
}
```

- a. Be a programmer1
- b. Be a programmer0
- c. Learning c1
- d. Learning c0

✓ **Verified Answer:** Option A

Problem 071 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q134 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
cannot be checked in a switch
case statement?
```

- a. Char
- b. Float
- c. Int
- d. Enum

✓ **Verified Answer:** Option B

Problem 072 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q141 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf (“Hi %d”, i);
}
}
```

- a. HiHiHi123
- b. Hi5
- c. Hi4
- d. Hi4Hi5

✓ **Verified Answer:** Option C

Problem 073 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q143 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf (“BCA”);
else
printf (“Btech”);
}
```

- a. BCA
- b. Btech
- c. 10
- d. Error

✓ **Verified Answer:** Option B

Problem 074 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q03 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}
```

- 7 6 3
- 7 5 4
- 6 7 8
- 6 5 4

✓ **Verified Answer:** 7 6 3

Problem 075 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q06 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
1.     Which of the following does not interrupt the running process?
```

- Timer interrupt
- Device
- Power failure
- Scheduler process

✓ **Verified Answer:** Scheduler process

Problem 076 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q10 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     What does the expression float a = 35 / 0 return?
```

- 0
- Not a Number
- Infinity
- Run time exception

✓ **Verified Answer:** Infinity

Problem 077 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q12 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.    Construct post order Transversal for the constructed tree with the given In-Order and Preo
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- 9 10 7 8 6
- 9 7 6 10 8
- 8 9 10 7 6
- 9 8 10 7 6

✓ **Verified Answer:** 9 10 7 8 6

Problem 078 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q18 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
main ()
{
if (5 < '5')
printf("5")
else
printf(" NOT EQUAL TO 5.")
}
```

- ENQ
- 5
- I
- Not equal to 5

✓ **Verified Answer:** 5

Problem 079 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q19 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of the following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- 5
- 7
- 9
- 12

✓ **Verified Answer:** 5

Problem 080 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q20 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of the following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- 6 6 6
- 6 5 6
- 5 5 5
- 6 5 4

✓ **Verified Answer:** 6 5 4

Problem 081 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q21 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().
```

- 2 2 1 1 2
- 2 2 1 2 2
- 2 1 2 2 1
- 2 1 2 2 2

✓ **Verified Answer:** 2 2 1 1 2

Problem 082 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q23 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
T The concatenation of two lists is to be performed in O(1) time. Which of the following impleme
```

- a) Singly linked list
- a) Doubly linked list
- a) Circular doubly linked list
- a) Array implementation of list

✓ **Verified Answer:** a) Circular doubly linked list

Problem 083 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q25 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     Let A be a square matrix of size nxn. Consider the following program and state the output
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp - C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- a) Transpose of matrix A
- a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- a) None of the above

✓ **Verified Answer:** a) The matrix A itself

Problem 084 • Core Practice

PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q26 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- 10
- 4
- 6
- 7

Verified Answer: 10

Problem 085 • Core Practice

PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q28 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- 5
- 6
- 7
- 8

Verified Answer: 7

Problem 086 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q29 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     Find the output of the following pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- 7
- 18
- 22
- 2

✓ **Verified Answer:** 2

Problem 087 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q30 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     Find the output of the following pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- 31
- 11
- 42
- 30

✓ **Verified Answer:** 30

Problem 088 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day06_Q02 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) P
```

- 1 Times
- 2 Times
- 3 Times
- 4 Times

✓ **Verified Answer:** 2 Times

Problem 089 • Core Practice

PRACTICE VARIANT

ID: SEC03_MOCK_Day06_Q06 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun
```

- 10
- 12
- Error
- 11

Verified Answer: 11

Problem 090 • Core Practice

CORE SE

ID: SEC03_MOCK_Day06_Q07 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c )
```

- 19
- 21
- 20
- 22

Verified Answer: 20

Problem 091 • Core Practice

CORE SE

ID: SEC03_MOCK_Day06_Q09 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   void main() { int a = 10; if (a == 010) printf
```

- BCA
- B.tech
- 10
- Error

Verified Answer: B.tech

Problem 092 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q01 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { int num = 987; int rem; whil
```

- 0
- 1
- 10
- 5

✓ **Verified Answer:** 1

Problem 093 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q03 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
Predict the output of the given pseudocode if the value of the number is 6: Read number k = 2 i
```

- 1440.0
- 1340.0
- 1700.0
- 1560.0

✓ **Verified Answer:** 1440.0

Problem 094 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q06 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x +
```

- 2
- 11
- 3
- 0

✓ **Verified Answer:** 3

Problem 095 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q01 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q1.) Integer p, q, r Set p = 0, q = 2, r = 9 r = 7 + p q = q + r for (each r from 4 to 7) p = (p
```

- 5
- 9
- 19
- 20

✓ **Verified Answer:** 9

Problem 096 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q03 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q3.) Integer value, n Set value = 1, n = 45 while (value less than equal to n) value = value <<
```

- 16
- 32
- 64
- 36

✓ **Verified Answer:** 64

Problem 097 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q04 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q4.) Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if
```

- 2
- 11
- 0
- 3

✓ **Verified Answer:** 3

Problem 098 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q06 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
Q6. What is the output for p=15 and q=4. Integer solve (Integer p, Integer q) Integer value whil
```

- 3
- 1
- 2
- 0

✓ **Verified Answer:** 1

Problem 099 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q07 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
Q7.what is the output for number=4 int something(int number) { if(number ⩽ 0) return 1; else re
```

- 12
- 24
- 1
- 20

✓ **Verified Answer:** 24

Problem 100 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q08 Source: Infosys Mock Test Series Level: Infosys SE Standard

/ Code Snippet

```
Q8. What will be the output of the following pseudocode? int a , b ,c Set a=0,b=1,c=2 If (b^c ||
```

- 20

✓ **Verified Answer:** 20

Problem 101 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q09 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q9. What is the output for x = 10, y = 5 Integer solve(Integer x, Integer y) if(y > 0) if(x > 0)
```

- undefined

✓ **Verified Answer:** undefined

Problem 102 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q10 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q10. What is the output of following Integer value, n Set value = 32, n = 1 while(value ⩾ n) va
```

- undefined

✓ **Verified Answer:** undefined

Problem 103 • Core Practice

CORE SE

ID: SEC03_MOCK_Day09_Q01 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of following pseudo code: Fun() { Int a=10 , b=20 , c=30; If(c>b>a) Print("Tr
```

- True
- False
- Error
- -1

✓ **Verified Answer:** False

Problem 104 • Core Practice

CORE SE

ID: SEC03_MOCK_Day09_Q03 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of following: Integer x, y Set x = 15, y = 12 y = x &ndash; 1 do{ Print x x =
```

- 14 26
- 15 27 39
- 27 39
- 15

✓ **Verified Answer:** 15 27 39

Problem 105 • Core Practice

CORE SE

ID: SEC03_MOCK_Day09_Q10 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c Set a = 1, b = 6, c = 7 b = (a & b) + b for (each c from 3 to 5) { b = (a + a) ^
```

- undefined

✓ **Verified Answer:** undefined