Topic 04: Data Structures, Arrays, Binary Trees & Pointers

Infosys Systems Engineer (SE) | 5-6 Nov 2026 Drive | 100% Pure SE Verified

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: Array Indexing, In-Order/Pre-Order/Post-Order Traversals, Min/Max Heap Insertion, and Pointers
Total Verified Authentic Problems: 57
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for Array Indexing, In-Order/Pre-Order/Post-Order Traversals, Min/Max Heap Insertion, and Pointers.

Problem 001 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q004 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Where are placed the list of
processes that are prepared to be
executed and waiting?
```

- a) Job queue
- b) Ready queue
- c) Execution queue
- d) Process queue

✓ **Verified Answer:** Option B

Problem 002 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q010 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** Option C

Problem 003 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q012 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Construct post order Transversal
for the constructed tree with the
given
In-Order
and
Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- a) 9 10 7 8 6
- b) 9 7 6 10 8
- c) 8 9 10 7 6
- d) 9 8 10 7 6

✓ **Verified Answer:** Option A

Problem 004 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q015 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
int main() {
    int i = 5;
    printf(“%d”, i = ++i == 6);
return 0;
}
```

- a) 2
- b) 6
- c) 4
- d) 1

✓ **Verified Answer:** Option D

Problem 005 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q017 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf(“%d”, h);
   return 0;
}
```

- a) 1
- b) error: redeclaration of an
- c) h
- d) 3

✓ **Verified Answer:** Option B

Problem 006 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q021 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of operations are
performed on a stack, the sequence
of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Pop(),
Push(2), Pop().
```

- a) 2 2 1 1 2
- b) 2 2 1 2 2
- c) 2 1 2 2 1
- d) 2 1 2 2 2

✓ **Verified Answer:** Option A

Problem 007 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q023 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The concatenation of two lists is to
be performed in O(1) time. Which of
the following implementation of a
list should be used?
```

- a) Singly linked list
- b) Doubly linked list
- c) Circular doubly linked list
- d) Array implementation of list

✓ **Verified Answer:** Option C

Problem 008 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q024 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following sequence
can be obtained in the output (in
same
order)
using
a
stack
assuming that the input is in the
sequence 1,2,3,4,5 order?
```

- a) 3,4,5,1,2
- b) 3,4,5,2,1
- c) 1,5,2,3,4
- d) 5,4,3,1,2

✓ **Verified Answer:** Option B

Problem 009 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q026 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** Option A

Problem 010 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q027 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
What is printed by the print
statement in the program P1
assuming
call
by
reference
parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

- a) 10,3
- b) 31,3
- c) 27,7
- d) None of these

✓ **Verified Answer:** Option B

Problem 011 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

Verified Answer: Option C

Problem 012 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q034 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Post order traversal of a tree is: V R
T S U Q P Which of the following
vertices will occupy positions 2 and
3?
```

- a) S, R
- b) F, G
- c) U, T
- d) X, Y

Verified Answer: Option A

Problem 013 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q035 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which cannot be the number of
vertices in a full binary tree?
```

- a) 3
- b) 7
- c) 15
- d) 30

✓ **Verified Answer:** Option D

Problem 014 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q036 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Sam sorts an array by repeatedly
swapping the adjacent elements if
they are in wrong order. Identify the
sorting technique used.
```

- a) Merge Sort
- b) Selection Sort
- c) Bubble Sort
- d) Insertion Sort

✓ **Verified Answer:** Option C

Problem 015 • Core Practice CORE SE

ID: SEC03_EBOOK_Q039 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Consider a stack of integers. The
stack is allocated 7 memory cells:
STACK: 12, 34, 66, 79, _, _, _.
Now
consider
the
following
operations:
A. PUSH (STACK, 8)
B. PUSH (STAC, 54)
C. POP (STACK, ITEM)
The above operations should be
performed in which of the following
sequences, such that no overflow
or underflow situation occurs:
1. B-> A-> C
2. A-> B-> C
3. C-> B-> A
```

- a) Only 1
- b) Any of them
- c) Only 2
- d) Only 3

✓ **Verified Answer:** Option B

Problem 016 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q040 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** Option A

Problem 017 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q046 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b!= !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}
```

- a) 1,1
- b) 2,1
- c) 3,1
- d) 4,1

✓ **Verified Answer:** Option D

Problem 018 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q047 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For a B- tree of order 6, to be a
multi-way search tree, each non
root node has at least how many
Non empty Children?
```

- a) 3
- b) 4
- c) 5
- d) 6

✓ **Verified Answer:** Option A

Problem 019 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q050 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find out the array representation of
the given min-heap, if the value 25
is inserted in it.
10,15,30,40,50,100
```

- a) 10,15,25,50,40,100,30
- b) 10,15, 25,40,50,100,30
- c) 15,10,25,40,50,100,30
- d) 10,15,25,40,50,30,100

✓ **Verified Answer:** Option B

Problem 020 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q051 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is not an
array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19
```

- a) Only 1
- b) Only 3
- c) Only 2 and 3
- d) Only 1 and 3

✓ **Verified Answer:** Option B

Problem 021 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q053 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 022 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q056 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
```

- a) 0
- b) 1
- c) 2
- d) 3

Verified Answer: Option A

Problem 023 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q068 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
Set a=5, b=7, c=9
if((a+b)<c)
a= a+c
b= (c+a)+c
c= (9+9)+a
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

Verified Answer: Option B

Problem 024 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q097 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following data
structure is used to convert
expression from one form to
another?
```

- a. Graph
- b. Stack
- c. Linked list
- d. Queue

Verified Answer: Option B

Problem 025 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q100 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the pre order of the
given tree.
  A

        /         \
     B
          C
   /   \             /   \
D     E        F    G
          \         \
H       I
```

- a. ABDEHCFIG
- b. BASUEKDHS
- c. AABBLIKDMSD
- d. CAMPUSMONK

Verified Answer: Option A

Problem 026 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q111 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
int i=0;
for (; i<=5; i++);
printf("%d", i);
return 0;
}
```

- a. 5
- b. 0 1 2 3 4 5
- c. 6
- d. 0 1 2 3 4

✓ **Verified Answer:** Option C

Problem 027 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q112 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ != 0)
printf("%d", ++i);
return 0;
}
```

- a. No output printed
- b. 012 3 65535
- c. 012 3.....32767 -32766 -
- d. Inifinite loop

✓ **Verified Answer:** Option D

Problem 028 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q113 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
int main()
{
int a=500,b=100, c;
if(!a>=400)
b=300;
c=200;
printf("%d%d",b,c);
return 0;
}
```

- a. 300 200
- b. 100 200
- c. 100 Garbage value
- d. 300 Garbage value

✓ **Verified Answer:** Option B

Problem 029 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q116 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of
operations are performed on a
stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Push(2),
Pop().
```

- a. 2 2 1 1 2
- b. 2 2 1 2 2
- c. 2 1 2 2 1
- d. 2 1 2 2 1

✓ **Verified Answer:** Option B

Problem 030 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q117 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Consider the following
operations performed on a stack of
size 5. Push(a), Pop(), Push(b),
Push(c), Pop(), Push(d), Pop(),
Pop(), Push(e) Which of the
following statements is correct?
```

- a. Underflow occurs
- b. Stack operations are performed
- c. Overflow occurs
- d. None

✓ **Verified Answer:** Option B

Problem 031 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q118 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Consider the tree with
given post: ab-cd*+ The labels on
the nodes 1 to 7 will be?2
```

- a. a, -, b, *, c, +, d
- b. +, -, *, a, b, c, d
- c. a, b, c, d, -, *, +
- d. -, a, b, +, *, c, d

✓ **Verified Answer:** Option B

Problem 032 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q120 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
relation is correct for a binary
search tree?
```

- a. Parent node> Right node>
- b. Right node> Parent node>
- c. Right node> Left node>
- d. Parent node> Left

Verified Answer: Option B

Problem 033 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q125 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
a= 4, b=6
Integer funn(Integer a, Integer b)
If(a>2)
If(b>2)
Return at+b+funn(a+1, b-5)
End if
End if
Return a-b
End function funn()
```

- a. 14
- b. 10
- c. 2
- d. 5

Verified Answer: Option A

Problem 034 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q129 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
int main()
{
int y = 128;
const int x=y;
y=120;
printf(“%d\n”, x);
return 0;
}
```

- a. 0
- b. 128
- c. Garbage Value
- d. Error

✓ **Verified Answer:** Option B

Problem 035 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q131 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#includex<stdio.h>
int main()
{
Printf(“\\n”);
return 0;
}
```

- a. \n
- b. \n
- c. Error
- d. n

✓ **Verified Answer:** Option B

Problem 036 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q132 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the complete of the
following code where the output is
8,14.
#include<stdio.h>
int main()
{
int p=6, q=6;
intr=6*(_____________);
printf (“%d%d”, p,r);
return 0;
}
```

- a. (p + q + p++)
- b. (p++ + q + p)
- c. (p++ +q + p++)
- d. none

Verified Answer: Option C

Problem 037 • Core Practice CORE SE

ID: SEC03_EBOOK_Q133 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main(void)
{
int i;
for(int j=0; j<1; j++)
{
if(i==0,1)
{
printf(“Be a programmer”);
}
else
{
printf(“Learning c”);
}
}
printf(“%d\n”, ++i);
return 0;
}
```

- a. Be a programmer1
- b. Be a programmer0
- c. Learning c1
- d. Learning c0

✓ **Verified Answer:** Option A

Problem 038 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q135 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
int main()
{
char ch;
if(ch = printf(“ ”))
printf(“No Output\n”);
else
printf(“Output\n”);
return 0;
}
```

- a. No Output
- b. Output
- c. No Output Output
- d. Error

✓ **Verified Answer:** Option B

Problem 039 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q136 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
int main(void)
{
int a=10, x;
X= a-- + +445
printf (“%d”,x);
return 0;
}
```

- a. 19
- b. 20
- c. 22
- d. 23

✓ **Verified Answer:** Option B

Problem 040 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q138 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int x;
printf(“%d\n, 4%3);
printf(“%d\n, 4%-3);
printf(“%d\n, -4%3);
printf(“%d\n, -4%-3);
return 0;
}
```

- a. 1 1 -1 -1
- b. 1 -1 1 -1
- c. 1 -1 -1 1
- d. 1 -1 -1 -1

✓ **Verified Answer:** Option A

Problem 041 • Core Practice

PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q10 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     What does the expression float a = 35 / 0 return?
```

- 0
- Not a Number
- Infinity
- Run time exception

✓ **Verified Answer:** Infinity

Problem 042 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q12 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.    Construct post order Transversal for the constructed tree with the given In-Order and Preorder Trav
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- 9 10 7 8 6
- 9 7 6 10 8
- 8 9 10 7 6
- 9 8 10 7 6

✓ **Verified Answer:** 9 10 7 8 6

Problem 043 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q15 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

- 2
- 6
- 4
- 1

✓ **Verified Answer:** 1

Problem 044 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q17 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
enum flg h;
h = b;
printf(“%d”, h);
return 0;
}
```

- 1
- error: redeclaration of an enumerator
- h
- 3

✓ **Verified Answer:** error: redeclaration of an enumerator

Problem 045 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_MOCK_Day04_Q21 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().
```

- 2 2 1 1 2
- 2 2 1 2 2
- 2 1 2 2 1
- 2 1 2 2 2

✓ **Verified Answer:** 2 2 1 1 2

Problem 046 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q24 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     Which of the following sequence can be obtained in the output (in same order) using a stack assumi
```

- a) 3,4,5,1,2
- a) 3,4,5,2,1
- a) 1,5,2,3,4
- a) 5,4,3,1,2

✓ **Verified Answer:** a) 3,4,5,2,1

Problem 047 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q26 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- 10
- 4
- 6
- 7

✓ **Verified Answer:** 10

Problem 048 • Core Practice

CORE SE

ID: SEC03_MOCK_Day04_Q28 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

- 5
- 6
- 7
- 8

✓ **Verified Answer:** 7

Problem 049 • Core Practice

CORE SE

ID: SEC03_MOCK_Day06_Q03 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   int main(void) { int a = 10, x; x = a-- + +445; printf
```

- 19
- 435
- 455
- 23

✓ **Verified Answer:** 455

Problem 050 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q01 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { int num = 987; int rem; while(num !=
```

- 0
- 1
- 10
- 5

Verified Answer: 1

Problem 051 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q02 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { float x = 0.0; long int y = 10; print
```

- 3
- 1
- 5
- 2

Verified Answer: 1

Problem 052 • Core Practice

CORE SE

ID: SEC03_MOCK_Day07_Q07 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x) return 0; }
```

- 0
- 1
- 5
- Compilation Error

Verified Answer: 1

Problem 053 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q06 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q6. What is the output for p=15 and q=4. Integer solve (Integer p, Integer q) Integer value while(q) valu
```

- 3
- 1
- 2
- 0

Verified Answer: 1

Problem 054 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q07 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q7.what is the output for number=4 int something(int number) { if(number <= 0) return 1; else return numb
```

- 12
- 24
- 1
- 20

Verified Answer: 24

Problem 055 • Core Practice

CORE SE

ID: SEC03_MOCK_Day08_Q09 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
Q9. What is the output for x = 10, y = 5 Integer solve(Integer x, Integer y) if(y > 0) if(x > 0) return x
```

- undefined

Verified Answer: undefined

Problem 056 • Core Practice

CORE SE

ID: SEC03_MOCK_Day09_Q04 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
What is the output if fun(5) is called? Function fun(n) If n == 0 Return 0 Else Print(n) Return fun(n + 1
```

- 1 2 3 4 5
- 5 4 3 2 1
- Stack overflow
- -1

✓ **Verified Answer:** Stack overflow

Problem 057 • Core Practice

CORE SE

ID: SEC03_MOCK_Day09_Q05 | Source: Infosys Mock Test Series | Level: Infosys SE Standard

/ Code Snippet

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x); return 0; }
```

- 0
- 1
- 5
- Compilation Error

✓ **Verified Answer:** 1