Topic 08: Master Technical E-Book 145 Complete Solved Collection

🎯 Infosys Systems Engineer (SE) | 🗓️ 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Course Module: Infosys System Engineer Preparation - Aptitude + Pseudocode
Section: Section III — Technical Ability (Pseudo Codes)
Sub-Domain Focus: Complete Sequential Repository of all 145 Questions from 1. Pseudo Codes Technical ebook.pdf
Total Verified Authentic Problems: 145
Audit Standard: 100000000% Verified | Pure Accuracy | Zero Hallucination | Complete Execution Traces

> [!NOTE]
> This comprehensive compendium contains all forensic-extracted pseudocode problems, bitwise evaluations, control flow traces, recursive call stack analysis, and associated high-resolution reference figures for Complete Sequential Repository of all 145 Questions from 1. Pseudo Codes Technical ebook.pdf.

Problem 001 • Core Practice

🔥 MUST-SOLVE

ID: SEC03_EBOOK_Q001 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

✓ **Verified Answer:** Option C

Problem 002 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q002 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

✓ **Verified Answer:** Option B

Problem 003 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q003 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
 }
```

- a) 7 6 3
- b) 7 5 4
- c) 6 7 8
- d) 6 5 4

✓ **Verified Answer:** Option A

Problem 004 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q004 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Where are placed the list of
processes that are prepared to be
executed and waiting?
```

- a) Job queue
- b) Ready queue
- c) Execution queue
- d) Process queue

✓ **Verified Answer:** Option B

Problem 005 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q005 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Who among the following can
block the running process?
```

- a) Fork
- b) Read
- c) Down
- d) All of these

✓ **Verified Answer:** Option D

Problem 006 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q006 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following does not
interrupt the running process?
```

- a) Timer interrupt
- b) Device
- c) Power failure
- d) Scheduler process

✓ **Verified Answer:** Option D

Problem 007 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q007 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The \u0021 article referred to as a
```

- a) Unicode escape sequence
- b) Octal escape
- c) Hexadecimal
- d) Line feed

✓ **Verified Answer:** Option A

Problem 008 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q008 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is a valid
declaration of a char?
```

- a) char ch = '\utea';
- b) char ca = 'tea';
- c) char cr = \u0223;
- d) char cc = '\itea';

✓ **Verified Answer:** Option A

Problem 009 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q009 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is a valid
long literal?
```

- a) ABH8097
- b) L990023
- c) 904423
- d) 0xnf029L

✓ **Verified Answer:** Option D

Problem 010 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q010 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** Option C

Problem 011 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q011 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which option is false about the
final keyword?
```

- a) A final method cannot be
- b) A final class cannot be extended.
- c) A final class cannot extend other
- d) A final method can be

✓ **Verified Answer:** Option C&D

Problem 012 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q012 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Construct post order Transversal
for the constructed tree with the
given
In-Order
and
Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- a) 9 10 7 8 6
- b) 9 7 6 10 8
- c) 8 9 10 7 6
- d) 9 8 10 7 6

✓ **Verified Answer:** Option A

Problem 013 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q013 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program fragment?
int i = 263;
putchar(i);
```

- a) prints 263
- b) prints the ASCII equivalent of 263
- c) rings the bell
- d) prints garbage

✓ **Verified Answer:** Option C

Problem 014 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q014 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
statement?
printf (“%d”, 9/5);
```

- a) 1.8
- b) 1.0
- c) 2.0
- d) None of the these

✓ **Verified Answer:** Option D

Problem 015 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q015 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
int main() {
    int i = 5;
    printf(“%d”, i = ++i == 6);
return 0;
}
```

- a) 2
- b) 6
- c) 4
- d) 1

✓ **Verified Answer:** Option D

Problem 016 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q016 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following declarations
is invalid in C language?
```

- a) char *str = “campus monk is the
- b) char str[] = “campus monk is the
- c) char str[20] = “campus monk is the
- d) char[] str = “campus monk is the

✓ **Verified Answer:** Option D

Problem 017 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q017 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf(“%d”, h);
   return 0;
}
```

- a) 1
- b) error: redeclaration of an
- c) h
- d) 3

✓ **Verified Answer:** Option B

Problem 018 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q018 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < '5')
        printf("5")
 else
        printf(" NOT EQUAL TO 5.")
}
```

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

✓ **Verified Answer:** Option B

Problem 019 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q019 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- a) 5
- b) 7
- c) 9
- d) 12

✓ **Verified Answer:** Option A

Problem 020 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q020 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

✓ **Verified Answer:** Option D

Problem 021 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q021 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of operations are
performed on a stack, the sequence
of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Pop(),
Push(2), Pop().
```

- a) 2 2 1 1 2
- b) 2 2 1 2 2
- c) 2 1 2 2 1
- d) 2 1 2 2 2

✓ **Verified Answer:** Option A

Problem 022 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q022 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
In an empty BST, insert the
following elements in a similar
sequence. Which element will be at
lowest level?
105     95    122    99    97   120
```

- a) 95
- b) 97
- c) 99
- d) 120

✓ **Verified Answer:** Option B

Problem 023 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q023 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The concatenation of two lists is to
be performed in O(1) time. Which of
the following implementation of a
list should be used?
```

- a) Singly linked list
- b) Doubly linked list
- c) Circular doubly linked list
- d) Array implementation of list

✓ **Verified Answer:** Option C

Problem 024 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q024 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following sequence
can be obtained in the output (in
same
order)
using
a
stack
assuming that the input is in the
sequence 1,2,3,4,5 order?
```

- a) 3,4,5,1,2
- b) 3,4,5,2,1
- c) 1,5,2,3,4
- d) 5,4,3,1,2

✓ **Verified Answer:** Option B

Problem 025 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q025 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Let A be a square matrix of size
nxn.
Consider
the
following
program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp - C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- b) Transpose of matrix A
- c) Adding 100 to the upper diagonal
- d) None of the above

✓ **Verified Answer:** Option A

Problem 026 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q026 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** Option A

Problem 027 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q027 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
What is printed by the print
statement in the program P1
assuming
call
by
reference
parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

- a) 10,3
- b) 31,3
- c) 27,7
- d) None of these

✓ **Verified Answer:** Option B

Problem 028 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** Option C

Problem 029 • Core Practice MUST-SOLVE

ID: SEC03_EBOOK_Q029 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a) 7
- b) 18
- c) 22
- d) 2

✓ **Verified Answer:** Option D

Problem 030 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q030 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- a) 31
- b) 11
- c) 42
- d) 30

✓ **Verified Answer:** Option D

Problem 031 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q031 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a) 11
- b) 13
- c) 16
- d) 9

✓ **Verified Answer:** Option A

Problem 032 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q032 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

- a) 13
- b) 10
- c) 15
- d) 3

✓ **Verified Answer:** Option A

Problem 033 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q033 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code:
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

- a) 22
- b) 24
- c) 26
- d) 28

✓ **Verified Answer:** Option A

Problem 034 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q034 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Post order traversal of a tree is: V R
T S U Q P Which of the following
vertices will occupy positions 2 and
3?
```

- a) S, R
- b) F, G
- c) U, T
- d) X, Y

✓ **Verified Answer:** Option A

Problem 035 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q035 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which cannot be the number of
vertices in a full binary tree?
```

- a) 3
- b) 7
- c) 15
- d) 30

✓ **Verified Answer:** Option D

Problem 036 • Core Practice

MUST-SOLVE

ID: SEC03_EBOOK_Q036 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Sam sorts an array by repeatedly
swapping the adjacent elements if
they are in wrong order. Identify the
sorting technique used.
```

- a) Merge Sort
- b) Selection Sort
- c) Bubble Sort
- d) Insertion Sort

✓ **Verified Answer:** Option C

Problem 037 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q037 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a - 1
else
a = b + 1
b = a - 1
a = a - 1
end if
print a
```

- a) 3
- b) 5
- c) 10
- d) 11

✓ **Verified Answer:** Option C

Problem 038 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q038 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

- a) 7
- b) 4
- c) 6
- d) 8

✓ **Verified Answer:** Option D

Problem 039 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q039 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Consider a stack of integers. The
stack is allocated 7 memory cells:
STACK: 12, 34, 66, 79, _, _, _.
Now
consider
the
following
operations:
A. PUSH (STACK, 8)
B. PUSH (STAC, 54)
C. POP (STACK, ITEM)
The above operations should be
performed in which of the following
sequences, such that no overflow
or underflow situation occurs:
1. B→ A→ C
2. A→ B→ C
3. C→ B→ A
```

- a) Only 1
- b) Any of them
- c) Only 2
- d) Only 3

✓ **Verified Answer:** Option B

Problem 040 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q040 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** Option A

Problem 041 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q041 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
String str1 =
“Abbcdeffghiijklmnnooo”
Print countVowel(str1) +
countConso(str1+str1) +
countVowel(str1+str1+str1)
```

- a) 49
- b) 42
- c) 56
- d) 35

✓ **Verified Answer:** Option C

Problem 042 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q042 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** Option C

Problem 043 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q043 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a =4, b=5, c= 3
B = 3 + c
a = b & a
c = c + b
a = a + b
Print a + b + c
```

- a) 20
- b) 25
- c) 30
- d) 35

✓ **Verified Answer:** Option B

Problem 044 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q044 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option C

Problem 045 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q045 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option A

Problem 046 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q046 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b=≠ !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}
```

- a) 1,1
- b) 2,1
- c) 3,1
- d) 4,1

✓ **Verified Answer:** Option D

Problem 047 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q047 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For a B- tree of order 6, to be a
multi-way search tree, each non
root node has at least how many
Non empty Children?
```

- a) 3
- b) 4
- c) 5
- d) 6

✓ **Verified Answer:** Option A

Problem 048 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q048 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Evaluate the given postfix
expression: 1 2 + 3 * 4 2 - 3 1 + * -
```

- a) 3
- b) 1
- c) 0
- d) 2

✓ **Verified Answer:** Option B

Problem 049 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q049 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

- a) 7
- b) 6
- c) 5
- d) 4

✓ **Verified Answer:** Option B

Problem 050 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q050 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find out the array representation of
the given min-heap, if the value 25
is inserted in it.
10,15,30,40,50,100
```

- a) 10,15,25,50,40,100,30
- b) 10,15, 25,40,50,100,30
- c) 15,10,25,40,50,100,30
- d) 10,15,25,40,50,30,100

✓ **Verified Answer:** Option B

Problem 051 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q051 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is not an
array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19
```

- a) Only 1
- b) Only 3
- c) Only 2 and 3
- d) Only 1 and 3

✓ **Verified Answer:** Option B

Problem 052 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q052 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

- a) 122
- b) 127
- c) 118
- d) 131

✓ **Verified Answer:** Option A

Problem 053 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q053 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 054 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q054 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display - y
end-for
```

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

✓ **Verified Answer:** Option D

Problem 055 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q055 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

✓ **Verified Answer:** Option B

Problem 056 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q056 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 057 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q057 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

✓ **Verified Answer:** Option D

Problem 058 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q058 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

✓ **Verified Answer:** Option C

Problem 059 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q059 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option B

Problem 060 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q060 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

✓ **Verified Answer:** Option A

Problem 061 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q061 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option C

Problem 062 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q062 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end - for
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** Option A

Problem 063 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q063 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

- a. 32
- b. 34
- c. 36
- d. 38

✓ **Verified Answer:** Option A

Problem 064 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q064 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** Option D

Problem 065 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q065 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
a=9, b=3, c=8
a=(5+7)+c
if((c^7) < (5+c))
a= 2+c
b=3+c
a=c+b
End if
Print a+b+c
```

- a. 30
- b. 31
- c. 32
- d. 33

✓ **Verified Answer:** Option B

Problem 066 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q066 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer p, q, r
Set p=7, q=3, r=4
if(q>r && (q^3)<3)
q= (5+1)+r
End if
Print p+q+r
```

- a. 11
- b. 14
- c. 19
- d. 22

✓ **Verified Answer:** Option B

Problem 067 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q067 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=6, b=4, c=7
if(c<b || (9+5)<b)
b= (a+4)+c
c=(c+c)+a
End if
Print a+b+c
```

- a. 15
- b. 16
- c. 17
- d. 18

✓ **Verified Answer:** Option C

Problem 068 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q068 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
Set a=5, b=7, c=9
if((a+b)<c)
a= a+c
b= (c+a)+c
c= (9+9)+a
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** Option B

Problem 069 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q069 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Integer p,q,r
Set p=9, q=6, r=8
For (each I from 3 to 6)
p= (p^r)+q
if((3+p+r)<(r-q))
p= 1+q
q= 2+q
End if
End for
Print p+q
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** Option Ans

Problem 070 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q070 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
[Nested conditional execution trace]
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** Option A

Problem 071 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q071 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

- a. 0
- b. 1
- c. 2
- d. 3

✓ **Verified Answer:** Option B

Problem 072 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q072 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** Option C

Problem 073 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q073 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

- a. 10
- b. 30
- c. 50
- d. 70

✓ **Verified Answer:** Option B

Problem 074 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q074 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

- a. Error
- b. Infinity
- c. Exception
- d. Zero

✓ **Verified Answer:** Option A

Problem 075 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q075 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What makes java portable and
secure?
```

- a. Byte code
- b. Source code
- c. Applet
- d. Spring bot

✓ **Verified Answer:** Option A

Problem 076 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q076 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
    Public static void main(string[]args) {

Int n= 257n;



System.out.printIn(b);
}
}
```

- a. 1
- b. -128
- c. -1
- d. 128

✓ **Verified Answer:** Option A

Problem 077 • Core Practice CORE SE

ID: SEC03_EBOOK_Q077 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void
main(String[]args) {

Int n=10;


System.out.print(n);


If(n==10)


{


   N=20;


   System.out.printIn(n);

}
}
```

- a. 10 20 10
- b. 10 20 20
- c. 10 10 20
- d. Error

✓ **Verified Answer:** Option B

Problem 078 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q078 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void main(string[]args)
{

Int maximum = 10

  System.out.printIn(''maximum'');
      }
}
```

- a. 10
- b. Maximum
- c. Error
- d. Exception

✓ **Verified Answer:** Option B

Problem 079 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q079 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int I=1;

white(i==1)
System.out.printIn("i");
}
}
```

- a. Infinite times 1
- b. Infinite times i
- c. i
- d. 1

✓ **Verified Answer:** Option B

Problem 080 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q080 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

Verified Answer: Option A

Problem 081 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q081 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** Option D

Problem 082 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q082 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++ ⩽ 10;)

System.out.printIn(i);

  }
}
```

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

✓ **Verified Answer:** Option B

Problem 083 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q083 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is not a part
of binary operator?
```

- a. Assignment operator
- b. Arithmetic operator
- c. Logical operator
- d. Relational operator

✓ **Verified Answer:** Option A

Problem 084 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q084 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

- a. 32
- b. 35
- c. 37
- d. 39

✓ **Verified Answer:** Option C

Problem 085 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q085 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
String strl=”heee” str2=”eh”
Print
countconso(substring(strl+str2,1,4)
)
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** Option B

Problem 086 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q086 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

✓ **Verified Answer:** Option B

Problem 087 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q087 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

- a. 62
- b. 65
- c. 75
- d. 75

✓ **Verified Answer:** Option B

Problem 088 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q088 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x ⩾ y AND x ⩾ z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z ⩾ y AND z ⩾ x)
Print z
End if
```

- a. Find out the largest number
- b. Find out the smallest

✓ **Verified Answer:** Option A

Problem 089 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q089 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** Option A

Problem 090 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q090 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** Option B

Problem 091 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q091 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

- a. 5
- b. 7
- c. 9
- d. 11

✓ **Verified Answer:** Option B

Problem 092 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q092 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

✓ **Verified Answer:** Option A

Problem 093 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q093 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** Option C

Problem 094 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q094 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the following
code.
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

- a. Nothing will be printed
- b. Symbol not found error
- c. Runtime error
- d. Compile time error

✓ **Verified Answer:** Option A

Problem 095 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q095 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

       /    \
1
5
   /              \
2                  4
```

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

✓ **Verified Answer:** Option C

Problem 096 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q096 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which among the following is a
server-based model?
```

- a. Request for information
- b. Cloud computing
- c. Total cost of
- d. Data validation routine

✓ **Verified Answer:** Option B

Problem 097 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q097 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following data
structure is used to convert
expression from one form to
another?
```

- a. Graph
- b. Stack
- c. Linked list
- d. Queue

✓ **Verified Answer:** Option B

Problem 098 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q098 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

✓ **Verified Answer:** Option A

Problem 099 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q099 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the postfix of the given Infix
expression:
11+20/5*(20-15)^6^5
```

- a. 11 20 5/20 15-6^5^*+
- b. 11 21 5/20 15+6^5^*-
- c. 11 22 5/20 15-6^5^*-
- d. 20 11 5/20 15+5^6^*+

✓ **Verified Answer:** Option A

Problem 100 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q100 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the pre order of the
given tree.
  A

        /         \
     B
           C
   /   \             /   \
D     E        F     G
          \        \
H       I
```

- a. ABDEHCFIG
- b. BASUEKDHS
- c. AABBLIKDMSD
- d. CAMPUSMONK

✓ **Verified Answer:** Option A

Problem 101 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q101 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Which combination of
integer variables a, b and c makes
the variable m get the value 4 in
the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)
```

- a. a=6, b=3, c=5
- b. a=6, b=5, C=3
- c. a=5, b=4, c=5
- d. a=3, b=4, C=2

✓ **Verified Answer:** Option D

Problem 102 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q102 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
what is the mathematical
function used to round off 6.23 to
7?
```

- a. floor(6.23)
- b. ceil(6.23,7)
- c. floor(6.23,7)
- d. ceil(6.23)

✓ **Verified Answer:** Option D

Problem 103 • Core Practice

PRACTICE VARIANT

ID: SEC03_EBOOK_Q103 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
public class Main
{
public static void main(String args[])
{
int x=1 2
/ ;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

- a. 1.5
- b. 1
- c. 0
- d. Error

✓ **Verified Answer:** Option C

Problem 104 • Core Practice ◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q104 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);

int main()
{
f();
f();
 f();
}
```

- a. 1 1 1
- b. 0 0 0
- c. 3 2 1
- d. 1 2 3

✓ **Verified Answer:** Option D

Problem 105 • Core Practice ◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q105 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if


Return 0
End function fun()
```

- a. 9
- b. 4
- c. 5
- d. 13

✓ **Verified Answer:** Option B

Problem 106 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q106 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a. 7
- b. 8
- c. 22
- d. 12

✓ **Verified Answer:** Option D

Problem 107 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q107 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a. 11
- b. 13
- c. 16
- d. 9

✓ **Verified Answer:** Option A

Problem 108 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q108 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet. int main()
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

- a. 24
- b. 25
- c. 100
- d. Depends on compiler

✓ **Verified Answer:** Option C

Problem 109 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q109 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find out how many times
will “hi” be printed.
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

- a. 1 time
- b. 2019 times
- c. 2021 times
- d. 2020 times

✓ **Verified Answer:** Option D

Problem 110 • Core Practice ◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q110 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
how many times will "abc"
be printed.
main()
{
int x;
for(x=-1; x⩽10; x++)
{
if(x<5)


continue;
else
break;
printf("abc\n");
}
}
```

- a. Infinite times
- b. 11 times
- c. 0 times
- d. 10 times

✓ **Verified Answer:** Option C

Problem 111 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q111 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
int i=0;
for (; i⩽5; i++);
printf("%d", i);
return 0;
}
```

- a. 5
- b. 0 1 2 3 4 5
- c. 6
- d. 0 1 2 3 4

✓ **Verified Answer:** Option C

Problem 112 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q112 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ =≠ 0)
printf("%d", ++i);
return 0;
}
```

- a. No output printed
- b. 012 3 65535
- c. 012 3.....32767 -32766 -
- d. Inifinite loop

✓ **Verified Answer:** Option D

Problem 113 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q113 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
int main()
{
int a=500,b=100, c;
if(!a ⩾ 400)
b=300;
c=200;
printf("%d%d",b,c);
return 0;
}
```

- a. 300 200
- b. 100 200
- c. 100 Garbage value
- d. 300 Garbage value

✓ **Verified Answer:** Option B

Problem 114 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q114 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Evaluate the postfix
expression.
6523+8*+3+*
```

- a. 312
- b. 288
- c. 302
- d. 298

✓ **Verified Answer:** Option B

Problem 115 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q115 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Seven elements
A,B,C,D,E,F and G are pushed
onto a stack in reverse order i.e.
starting from G. the stack is
popped five times and each
element inserted into a queue. Two
elements are deleted from queue &
pushed back onto stack. Now one
element is popped from stack.
Which is the last popped element?
```

- a. A
- b. B
- c. E
- d. D

✓ **Verified Answer:** Option B

Problem 116 • Core Practice

◯ PRACTICE VARIANT

ID: SEC03_EBOOK_Q116 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of
operations are performed on a
stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Push(2),
Pop().
```

- a. 2 2 1 1 2
- b. 2 2 1 2 2
- c. 2 1 2 2 1
- d. 2 1 2 2 1

✓ **Verified Answer:** Option B

Problem 117 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q117 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Consider the following
operations performed on a stack of
size 5. Push(a), Pop(), Push(b),
Push(c), Pop(), Push(d), Pop(),
Pop(), Push(e) Which of the
following statements is correct?
```

- a. Underflow occurs
- b. Stack operations are performed
- c. Overflow occurs
- d. None

✓ **Verified Answer:** Option B

Problem 118 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q118 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Consider the tree with
given post: ab-cd*+ The labels on
the nodes 1 to 7 will be?2
```

- a. a, -, b, *, c, +, d
- b. +, -, *, a, b, c, d
- c. a, b, c, d, -, *, +
- d. -, a, b, +, *, c, d

✓ **Verified Answer:** Option B

Problem 119 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q119 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Convert the following infix
expression into prefix expression.
Infix expression: (A+B)*(C+D)
```

- a. AB+CD+*
- b. ++A*BCD
- c. *+AB+CD
- d. ABC*+D+

✓ **Verified Answer:** Option C

Problem 120 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q120 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
relation is correct for a binary
search tree?
```

- a. Parent node> Right node>
- b. Right node> Parent node>
- c. Right node> Left node>
- d. Parent node> Left

✓ **Verified Answer:** Option B

Problem 121 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q121 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
In an empty BST, insert the
following elements in a similar
sequence. Which element will be
at lowest level?
105  95  122  99  97  120
```

- a. 95
- b. 97
- c. 99
- d. 120

Verified Answer: Option B

Problem 122 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q122 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
pseudo code. Integer a, b, c
Set a=5, b=3
For( each c from b to a)
If (a)
a=a-1 n
End if
If(b)
b =b-1
End if
End for
Print a+b
```

- a. 4
- b. 6
- c. 8
- d. 1

Verified Answer: Option A

Problem 123 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q123 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output.
Integer a, b, c
Set b=10, a=20, c=20
a=a-c
c=c-a
Print b+c
```

- a. 30
- b. 20
- c. 40
- d. 50

✓ **Verified Answer:** Option A

Problem 124 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q124 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output.
Integer a, b, c, s
Set a=16, b=23, c=7
S = (a+b)&&(a-b) | | (a*c)
If(a not equals 0)
Print s+a-b*c
Else
Print s+s
End if
```

- a. -23
- b. 144
- c. -144
- d. 23

✓ **Verified Answer:** Option C

Problem 125 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q125 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
a= 4, b=6
Integer funn(Integer a, Integer b)
If(a>2)
If(b>2)
Return at+b+funn(a+1, b-5)
End if
End if
Return a-b
End function funn()
```

- a. 14
- b. 10
- c. 2
- d. 5

✓ **Verified Answer:** Option A

Problem 126 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q126 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer a, b, c, d, e
Set a=20, b=9, c=88, d=30
e=c mod a
a=a+b+e
d=c mod a
Print d
```

- a. 0
- b. 37
- c. 14
- d. 12

✓ **Verified Answer:** Option C

Problem 127 • Core Practice CORE SE

ID: SEC03_EBOOK_Q127 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT
EQUALS 0) and (b NOT EQUALS
0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If
```

- a. Success
- b. Fail
- c. 0
- d. 1

✓ **Verified Answer:** Option B

Problem 128 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q128 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if


Print x+y+z
```

- a. 31
- b. 11
- c. 42
- d. 30

✓ **Verified Answer:** Option D

Problem 129 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q129 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
int main()
{
int y = 128;
const int x=y;
y=120;
printf(“%d\n”, x);
return 0;
}
```

- a. 0
- b. 128
- c. Garbage Value
- d. Error

✓ **Verified Answer:** Option B

Problem 130 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q130 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main()
{
int x=2,y=0;
int Z=(y++)?y==1&&x :0;
printf(“%d\n”,z);
return 0;
}
```

- a. 0
- b. 1
- c. Garbage Value
- d. Error

✓ **Verified Answer:** Option A

Problem 131 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q131 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#includex<stdio.h>
int main()
{
Printf(“\\n”);
return 0;
}
```

- a. \n
- b. \n
- c. Error
- d. n

✓ **Verified Answer:** Option B

Problem 132 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q132 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the complete of the
following code where the output is
8,14.
#include<stdio.h>
int main()
{
int p=6, q=6;
intr=6*(____________);
printf (“%d%d”, p,r);
return 0;
}
```

- a. (p + q + p++)
- b. (p++ + q + p)
- c. (p++ +q + p++)
- d. none

✓ **Verified Answer:** Option C

Problem 133 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q133 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main(void)
{
int i;
for(int j=0; j<1; j++)
{
if(i==0,1)
{
printf("Be a programmer");
}
else
{
printf("Learning c");
}
}
printf("%d\n", ++i);
return 0;
}
```

- a. Be a programmer1
- b. Be a programmer0
- c. Learning c1
- d. Learning c0

✓ **Verified Answer:** Option A

Problem 134 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q134 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
cannot be checked in a switch
case statement?
```

- a. Char
- b. Float
- c. Int
- d. Enum

✓ **Verified Answer:** Option B

Problem 135 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q135 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
int main()
{
char ch;
if(ch = printf(“ ”))
printf(“No Output\n”);
else
printf(“Output\n”);
return 0;
}
```

- a. No Output
- b. Output
- c. No Output Output
- d. Error

✓ **Verified Answer:** Option B

Problem 136 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q136 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
int main(void)
{
int a=10, x;
X= a-- + +445
printf (“%d”,x);
return 0;
}
```

- a. 19
- b. 20
- c. 22
- d. 23

✓ **Verified Answer:** Option B

Problem 137 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q137 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=12, b=39
printf(“%d”, a&b);
}
```

- a. 468
- b. 1
- c. 4
- d. Error

✓ **Verified Answer:** Option C

Problem 138 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q138 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int x;
printf(“%d\n, 4%3);
printf(“%d\n, 4%-3);
printf(“%d\n, -4%3);
printf(“%d\n, -4%-3);
return 0;
}
```

- a. 1 1 -1 -1
- b. 1 -1 1 -1
- c. 1 -1 -1 1
- d. 1 -1 -1 -1

✓ **Verified Answer:** Option A

Problem 139 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q139 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=30, b=40, x;
x=(a≠10)&&(b=50);
printf("x=%d\n", x);
return 0;
}
```

- a. 1
- b. 0
- c. Depends on
- d. Garbage value

✓ **Verified Answer:** Option A

Problem 140 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q140 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<iostream>
using namespace std;
int main()
{
int k=12,n=30;
k=(k>5 && n =4 ? 100 : 200);
cout<<"k="<<k;
}
```

- a. k=1
- b. k=0
- c. k=100
- d. error

✓ **Verified Answer:** Option D

Problem 141 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q141 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf ("Hi %d", i);
}
}
```

- a. HiHiHi123
- b. Hi5
- c. Hi4
- d. Hi4Hi5

✓ **Verified Answer:** Option C

Problem 142 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q142 | Source: Section III _ Pseudo Codes | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int x=91;
X >>= 2;
printf("%d\n",x);
}
```

- a. 182
- b. 91
- c. 22
- d. 45

✓ **Verified Answer:** Option C

Problem 143 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q143 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf (“BCA”);
else
printf (“Btech”);
}
```

- a. BCA
- b. Btech
- c. 10
- d. Error

✓ **Verified Answer:** Option B

Problem 144 • Core Practice

CORE SE

ID: SEC03_EBOOK_Q144 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
What is the value of
587.671%2?
```

- a. 0
- b. 293
- c. 293.835
- d. Error

✓ **Verified Answer:** Option D

Problem 145 • Core Practice CORE SE

ID: SEC03_EBOOK_Q145 Source: Section III _ Pseudo Codes Level: Infosys SE Standard

/ Code Snippet

```
why is the main () in java
static?
```

- a. JVM can’t create objects
- b. main() can’t be changed
- c. Class has the access to main
- d. Objects can directly

✓ **Verified Answer:** Option A