Pseudo Code

Infosys Systems Engineer (SE) | 5-6 Nov 2026 Drive | 100% Pure SE Verified

Total Questions: 10 | **Total Marks:** 10 | **Duration:** 10 Minutes

Section: Technical Ability - Mathematics /Quantitative Aptitude

Problem 1 • [Marks: +1, -0] PRACTICE VARIANT

ID: Q1 | Source: Infosys PYQ | Level: Infosys SE Standard

Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c

A 71

B 56

C 47

D 54

Verified Answer: ✅ **(D) 54** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 2 • [Marks: +1, -0] PRACTICE VARIANT

ID: Q2 | Source: Infosys PYQ | Level: Infosys SE Standard

How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "campus monk" End if j = p + k / 5 If (j not equal p) Print "campus monk" End if Print "campus monk"

A 1 Times

B 2 Times

C 3 Times

D 4 Times

Verified Answer: ✅ **(B) 2 Times** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 3 • [Marks: +1, -0] PRACTICE VARIANT

ID: Q3 | Source: Infosys PYQ | Level: Infosys SE Standard

Find the output of the following code. #include int main(void) { int a = 10, x; x = a-- + +445; printf ("%d", x); return 0; }

A 19

B 435

C 455

D 23

Verified Answer: ✅ **(C) 455** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 4 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q4 Source: Infosys PYQ Level: Infosys SE Standard

Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q } Print p + q + r

A	44	B	41
C	11	D	26

✓ **Verified Answer:** ✅ **(D) 26** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 5 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q5 Source: Infosys PYQ Level: Infosys SE Standard

What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)) { p = 11 + q; } Print p + q + r;

A	12	B	16
C	27	D	10

✓ **Verified Answer:** ✅ **(B) 16** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 6 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q6 Source: Infosys PYQ Level: Infosys SE Standard

What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a, int b, int c) { For (each c from 3 to 5) { a = (c + c) ^ b; If ((a + c) < (c + a)) { b = (a + 11) + c; } Else { c = b + b; a = 3 + b; continue; } } Return a + b; }

A	10	B	12
C	Error	D	11

✓ **Verified Answer:** ✅ **(D) 11** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 7 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q7 Source: Infosys PYQ Level: Infosys SE Standard

What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c) a = b + c Else c = (4 + 12) + a b = 11 + a End if Print (a + b + c)

A 19 B 21

C 20 D 22

✓ **Verified Answer:** ✅ **(C) 20** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 8 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q8 Source: Infosys PYQ Level: Infosys SE Standard

Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^ y ^ z) x = 1 End if Print x + y + z

A 11 B 13

C 16 D 9

✓ **Verified Answer:** ✅ **(A) 11** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 9 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q9 Source: Infosys PYQ Level: Infosys SE Standard

Find the output of the following code. #include void main() { int a = 10; if (a == 010) printf("BCA"); else printf("B.Tech"); }

A BCA B B.tech

C 10 D Error

✓ **Verified Answer:** ✅ **(B) B.tech** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 10 • [Marks: +1, -0] ◯ PRACTICE VARIANT

ID: Q10 Source: Infosys PYQ Level: Infosys SE Standard

Find the output of the following code. #include void main () { int x = 91; x >>= 2; printf ("%d\n", x); }

A 182	**B** 91
C 22	**D** 82

✓ **Verified Answer:** ✅ **(C) 22** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.