⚡ INFOSYS SE MASTER CHEAT-CODE & SHORTCUT BIBLE

Rapid 10-Second Recall • Quant Multipliers • Reverse Alphabet • ASCII & Binary • Reasoning Locks

INFOSYS SE 2026 EDITION

📊 SECTION 1: PERCENTAGE INCREASE, DECREASE & MULTIPLIERS

DECREASE	FRACTION MULTIPLIER	DECIMAL MULTIPLIER	SHORTCUT ACTION	INSTANT EXAMPLE ($500 BASE)
–10%	90/100 = **9/10**	**0.9×**	**× 0.9**	500 × 0.9 = **$450**
–20%	80/100 = **4/5**	**0.8×**	**× 0.8**	500 × 0.8 = **$400**
–30%	70/100 = **7/10**	**0.7×**	**× 0.7**	500 × 0.7 = **$350**
–40%	60/100 = **3/5**	**0.6×**	**× 0.6**	500 × 0.6 = **$300**
–50%	50/100 = **1/2**	**0.5×**	**× 0.5**	500 × 0.5 = **$250**
–60%	40/100 = **2/5**	**0.4×**	**× 0.4**	500 × 0.4 = **$200**
–70%	30/100 = **3/10**	**0.3×**	**× 0.3**	500 × 0.3 = **$150**
–80%	20/100 = **1/5**	**0.2×**	**× 0.2**	500 × 0.2 = **$100**
–90%	10/100 = **1/10**	**0.1×**	**× 0.1**	500 × 0.1 = **$50**
–100%	0/100 = **0**	**0.0×**	**× 0.0**	500 × 0 = **$0** (Zero)

PERCENTAGE	INCREASE MULTIPLIER	DECREASE MULTIPLIER	SUM OF MULTIPLIERS	MEMORY & APPLICATION RULE
10%	**1.1×**	**0.9×**	**1.1 + 0.9 = 2.0**	Increase = 1 + 0.1; Decrease = 1 − 0.1
20%	**1.2×**	**0.8×**	**1.2 + 0.8 = 2.0**	Increase = 1 + 0.2; Decrease = 1 − 0.2
30%	**1.3×**	**0.7×**	**1.3 + 0.7 = 2.0**	Increase = 1 + 0.3; Decrease = 1 − 0.3
40%	**1.4×**	**0.6×**	**1.4 + 0.6 = 2.0**	Increase = 1 + 0.4; Decrease = 1 − 0.4
50%	**1.5×**	**0.5×**	**1.5 + 0.5 = 2.0**	Half Up (+50%) vs Half Down (−50%)

🔥 **Multiplier Exam Lock:** Multiplier gives the **Final Value** directly. If asked for *Change Amount*, multiply by (x / 100).
Successive Change: Net % = a + b + (ab / 100)%. (Two discounts of 20% & 10% = −20 − 10 + 2 = **−28%**).
Price-Consumption Invariance: If Price rises by R%, consumption drops by [R / (100 + R)] × 100%. (Price +25% [1/4] &implies; Cons −20% [1/5]).

🔤 SECTION 2: CHINESE CODING-DECODING & ALPHABET MATRIX (A–M & Z–N DUAL-TRACK)

A–M ↓	POS	REV	REV ↑	Z–N ↓	POS	REV	REV ↑	ANCHOR MNEMONICS & DIRECT APPLICATION
A	1	26	**Z**	**N**	14	13	**M**	**A–Z (Amazon) • M–N (Man)**
B	2	25	**Y**	**O**	15	12	**L**	**B–Y (Boy) • L–O (Love)**
C	3	24	**X**	**P**	16	11	**K**	**C–X (Crux) • K–P (Kurta Pajama)**
D	4	23	**W**	**Q**	17	10	**J**	**D–W (Dew) • J–Q (Jack Queen)**
E	5	22	**V**	**R**	18	9	**I**	**E–V (Even) • I–R (Indian Railway)**
F	6	21	**U**	**S**	19	8	**H**	**F–U (Full) • H–S (High School)**
G	7	20	**T**	**T**	20	7	**G**	**G–T (GT Road)** • Center anchor pair

EJOTY Anchors: E=5, J=10, O=15, T=20, Y=25.
The Universal Reverse-27 Rule: Reverse Position = 27 − Normal Position. (e.g. Reverse of H (8) = 27 − 8 = 19 &implies; **S**).

💻 SECTION 3: PSEUDOCODE TECHNICAL CHEAT CODES (ASCII, BINARY & BITWISE)

DOMAIN	KEY CODES & VALUES	PSEUDOCODE MANIPULATION SHORTCUT
Digits '0'–'9'	`ASCII 48 to 57 ('0'=48, '9'=57)`	**Char to Int:** `ch - '0'` or `ASCII(ch) - 48`. ('7' − '0' = 55 − 48 = **7**).
Uppercase 'A'–'Z'	`ASCII 65 to 90 ('A'=65, 'Z'=90)`	**Upper to Lower:** `ASCII + 32`. ('A' + 32 = 65 + 32 = 97 &implies; 'a').
Lowercase 'a'–'z'	`ASCII 97 to 122 ('a'=97, 'z'=122)`	**Lower to Upper:** `ASCII - 32`. ('c' − 32 = 99 − 32 = 67 &implies; 'C').
Bitwise Operators	`&, |, ^, ~, <<, >>`	**XOR Invariants:** `x ^ x = 0`, `x ^ 0 = x`. **Bitwise NOT:** `~x = -(x + 1)`. (~5 = −6, ~0 = −1). **Shifts:** `x << k = x × 2^k`; `x >> k = ⌊x / 2^k⌋`.

🔢 DECIMAL TO BINARY HORIZONTAL MATRIX (0 TO 31)

DEC	BINARY	DEC	BINARY	DEC	BINARY	DEC	BINARY
0	00000	8	01000	16	10000	24	11000
1	00001	9	01001	17	10001	25	11001
2	00010	10	01010	18	10010	26	11010
3	00011	11	01011	19	10011	27	11011
4	00100	12	01100	20	10100	28	11100
5	00101	13	01101	21	10101	29	11101
6	00110	14	01110	22	10110	30	11110
7	00111	15	01111	23	10111	31	11111

⏱️ SECTION 4: QUANTITATIVE SPEED SHORTCUTS (TIME-WORK, TRAINS & ALLIGATION)

DOMAIN	CHEAT CODE / GOVERNING FORMULA	INSTANT EXECUTION EXAMPLE
Time & Work (LCM)	Work = LCM(Days). Rate = Work / Days. **Time = Total Work / Σ(Efficiency)**	A in 12d, B in 15d &implies; Work=60u. A=5u/d, B=4u/d &implies; Time = 60/9 = **6 ⅔ days**.
Speed Conversion	km/h × **5/18** = m/s m/s × **18/5** = km/h	72 km/h = 72 × 5/18 = **20 m/s**. 25 m/s = 25 × 18/5 = **90 km/h**.
Average Speed	Equal Distances: **2xy / (x + y)**	60 km/h and 40 km/h &implies; 2(60)(40)/(100) = **48 km/h**.
CI − SI (2 Years)	**Diff = P × (R / 100)²**	P=$10,000, R=10%, 2 yrs &implies; Diff = 10,000 × (0.1)² = **$100**.
Alligation Cross	**Cheaper / Dearer = (D − M) / (M − C)**	Mix $15 & $20 to get $18 &implies; (20−18) : (18−15) = **2 : 3 ratio**.

🧠 SECTION 5: LOGICAL REASONING DEDUCTIONS (SYLLOGISMS & DATA SUFFICIENCY)

PROPOSITION TYPE	SUBJECT	PREDICATE	QUALITY	DISTRIBUTION RULE & CONCLUSION VALIDITY
All A are B	100	50	**Positive (+)**	Universal positive; predicate is undistributed (50).
No A is B	100	100	**Negative (−)**	Universal negative; both terms distributed (100).
Some A are B	50	50	**Positive (+)**	Particular positive; neither term distributed (50).
Some A are not B	50	100	**Negative (−)**	Particular negative; predicate distributed (100).

Syllogism 3-Rules: 1. Middle term must be 100 in at least one premise. 2. (+) + (+) = (+); (+) + (−) = (−); (−) + (−) = NO conclusion. 3. Income-Expense Rule: A term cannot be 100 in conclusion unless it was 100 in premise!

DATA SUFFICIENCY STEP	CONDITION & OUTCOME	OPTION SELECTION DECISION
Step 1: Statement I Alone	Sufficient &implies; Answer is A or D. Not Sufficient &implies; Answer is B, C, or E.	Eliminates 3 options in under 10 seconds!
Step 2: Statement II Alone	If I was suff. & II is also suff. &implies; **D**. If I was suff. & II is NOT &implies; **A**. If I was not suff. & II is suff. &implies; **B**.	If both alone work &implies; Option **D** (Each alone).
Step 3: Combine Both (I + II)	Only tested if NEITHER alone works. Together suff. &implies; **C**; Still not suff. &implies; **E**.	Option **C** (Together) or Option **E** (Neither).

📚 SECTION 6: VERBAL ABILITY & GRAMMAR INVARIANTS

GRAMMAR RULE CATEGORY	RULE INVARIANT	TRAP PATTERN & CORRECTION
Neither..Nor / Either..Or	Verb agrees with the **closest subject**.	Neither the manager nor the *employees* **are** (NOT 'is') present.
Parenthetical Phrases	*Along with, as well as, together with* do NOT change subject number.	The teacher, along with her students, **was** (NOT 'were') present.
Indefinite Pronouns	*Each, every, either, neither, one of the* take **singular verbs**.	Each of the participants **has** (NOT 'have') submitted the form.
Fixed Prepositions	Abstain **from**, Adhere **to**, Capable **of**, Congratulate **on**, Prefer **to**.	He preferred tea **to** coffee (NOT 'than' coffee).

✍️ SECTION 7: DUAL-METHOD SOLUTION ARCHITECTURE TEMPLATE

METHOD 1: STEP-BY-STEP PEDAGOGICAL DERIVATION	METHOD 2: 10-SECOND EXAM SHORTCUT / MULTIPLIER
1. Let total salary be S. 2. Food = 20% (0.2S), Remaining = 0.8S. 3. Rent = 25% of rem. = 0.25 × 0.8S = 0.2S, Rem = 0.6S. 4. Entertainment = 33.33% (1/3) of rem = (1/3) × 0.6S = 0.2S, Rem = 0.4S. 5. Education = 10% of rem = 0.04S, Rem = 0.36S. 6. 0.36S - 900 = 2340 &implies; 0.36S = 3240 &implies; **S = Rs. 9,000**.	**Telescopic Fraction Multiplier:** S × (4/5) × (3/4) × (2/3) × (9/10) = S × (9/25) = 0.36S. 0.36S = 2340 + 900 = 3240 &implies; **S = Rs. 9,000**. **Entertainment Expense:** 9000 × (4/5 × 3/4 × 1/3) = 9000 × (1/5) = **Rs. 1,800**. *(Fractions cancel out in 5 seconds without heavy algebra!)*