QUES 1

A shopkeeper has added a new collection of cosmetics to his shop.
A parcel containing cosmetics has arrived from another country, and the number of products is huge.
But, when he received the parcel,
he notices that the price is missing on the product label.
When he speaks to the product vendor,
he gives him a trick to get the price of each product from the barcode printed on it.

The trick is as follows:

The shopkeeper has to find the ASCII value of every character on the barcode i If it's a 2-digit (or 3 digit) ASCII val ue. He has to note down only the maximum of the 2-digits (or 3 digits) for each character. The final price of the prod uct will be the sum of all the numbers obtained from the ASCII value of each character on the barcode.

Given the barcode (B), find the final price of each product.

Note: The barcode can consist of letters (uppercase and lowercase) of the alphabet, numeric characters (0 to 9) and s pecial characters.

the value of the numeric character is added (for example if the numeric character is 6 then 6 is added ignoring the co rresponding ASCII value 54).

Example 1:

Input:
String
>> Value of B = 12ab ------ 1 2 a = 97 b = 98

price = 1+2+9+9 = 21

Output:

21

Explanation:

From the inputs given above:

Barcode is 12ab
1+2+9+9 = 21. Hence, the output is 21

Example 2:

Input:

>> Value of B = CD#34 = 3+4+

Output

27

QUES 2

Each student from class 1 to 10 is given a distinct number. The physical Training (PT) instructs all the N students to stand in a straight line(a[]) in ascending order. But some primary class students don't follow the instructions and start s Tunning around. These students are made to sit aside in the ground.

The PT instructor calls out random numbers(R) to check if the student with the number called is in the line or not. If the student with number R is already present in the line, give the position of the student in the line(index). If the stud ent with number R is not present and sitting aside in the ground, give the position where this student should join in th e line.

Given N, a[], R, the task here is to find the position of the students as per the above instructions.

Note: Position of the students in the line starts from 0.

Example 1:
Input:
-> Value of N = 6
-> Value of R = 3
-> a[] = {1,2,3,4,7,9) - Elements a[0]to a[N-1]

output: 2

QUES 3

Jim is standing on a bus station. There are 2 types of buses:

Passenger Bus: stops at every stop
Express Bus: stops at alternate stops.

All the stations are in a straight line and numbered. Distance between each station is 1 unit. Given the following 2 st ations:

A: Jim's current station number

B: Jim's destination station number

Consider the bus starts from Jim's current location, and he wants to reach the destination as soon as possible. Find ou t which type of bus Jim should catch to reach his destination station.

For eg. Jim is standing at station 2 and want to reach station 5, then he has to catch Passenger. The difference betwee n both stations is 3, if he catches Express, then it will stop at 4, 6 and so on. But, if he catches Passenger, then it will stop at 3,4,5,6. So jim will catch Passenger.

Example 1:
Input: Current station - 2
Destination station - 5

Output: Passenger

Example 2:

Input: Current station - 2
Destination station - 8